SANDIA REPORT

SAND99-8486

Unlimited Release

Printed March 1999

Pulsating Hydrodynamic Instability and Thermal Coupling in an Extended Landau/Levich Model of Liquid-Propellant Combustion --- I. Inviscid Analysis

Stephen B. Margolis and Forman A. Williams

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy under Contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.

RECEIVED

APR 26 1999

OSTI

Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Rd
Springfield, VA 22161

NTIS price codes
Printed copy: A03
Microfiche copy: A01

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

**PULSATING HYDRODYNAMIC INSTABILITY AND THERMAL COUPLING
IN AN EXTENDED LANDAU/LEVICH MODEL OF
LIQUID-PROPELLANT COMBUSTION — I. INVISCID ANALYSIS***

STEPHEN B. MARGOLIS

Combustion Research Facility, MS 9052

Sandia National Laboratories, Livermore, California 94551-0969 USA

E-mail: margoli@sandia.gov

Abstract

Hydrodynamic (Landau) instability in combustion is typically associated with the onset of wrinkling of a flame surface, corresponding to the formation of steady cellular structures as the stability threshold is crossed. In the context of liquid-propellant combustion, such instability has recently been shown to occur for critical values of the pressure sensitivity of the burning rate and the disturbance wavenumber, significantly generalizing previous classical results for this problem that assumed a constant normal burning rate. Additionally, however, a pulsating form of hydrodynamic instability has been shown to occur as well, corresponding to the onset of temporal oscillations in the location of the liquid/gas interface. In the present work, we consider the realistic influence of a nonzero temperature sensitivity in the local burning rate on both types of stability thresholds. It is found that for sufficiently small values of this parameter, there exists a stable range of pressure sensitivities for steady, planar burning such that the classical cellular form of hydrodynamic instability and the more recent pulsating form of hydrodynamic instability can each occur as the corresponding stability threshold is crossed. For larger thermal sensitivities, however, the pulsating stability boundary evolves into a C-shaped curve in the (disturbance-wavenumber, pressure-sensitivity) plane, indicating loss of stability to pulsating perturbations for all sufficiently large disturbance wavelengths. It is thus concluded, based on characteristic parameter values, that an equally likely form of hydrodynamic instability in liquid-propellant combustion is of a nonsteady, long-wave nature, distinct from the steady, cellular form originally predicted by Landau.

*This work was supported by the U.S. Department of Energy under contract DE-AC04-94AL85000 and by the NASA Microgravity Science Research Program under contract C-32031-E.

PULSATING HYDRODYNAMIC INSTABILITY IN AN EXTENDED LANDAU/LEVICH MODEL OF LIQUID-PROPELLANT COMBUSTION

1. Introduction

The notion of hydrodynamic instability in combustion originated with Landau's seminal study of premixed flame propagation (Landau [1]). In that work, it was postulated that a flame could be represented by a surface of discontinuity, with an appropriate density jump across the flame surface, and the normal equations of hydrodynamics governing the flow on either side of the flame surface. Assuming that this surface propagated normal to itself with constant speed, it was then determined through a straightforward linear stability analysis that a premixed gaseous flame was intrinsically unstable to steady (cellular) disturbances whenever, as is generally the case, the density on the burned side of the front was less than that of the unburned mixture. Since this result is at variance with experimental observations of steady, planar laboratory flames, it has sparked numerous other theoretical investigations that have sought to resolve this paradox, through both the inclusion of additional effects and the analysis of less phenomenological combustion models. Today, this specific form of hydrodynamic instability, generally referred to as Landau instability, plays a central role in the study of flame/flow interactions. Though Landau's analysis essentially collapsed all thermal effects to the change in density across the front, Landau instability is nonetheless implicitly associated with the thermal expansion of the gas arising from the heat release during combustion. Indeed, this instability persists even when the entire flame structure is resolved (*cf.* Matalon and Matkowsky [2], Pelcé and Clavin [3]), although it is now recognized as a predominantly long-wave cellular instability that is subject to various stabilizing influences for disturbances corresponding to larger wavenumbers.

A related problem briefly addressed at the end of Landau's original study (for which a more standard and less controversial type of result was obtained), and the one of interest here, was a modest modification of the flame-propagation problem just described. In this modified problem, the unburned mixture was taken to be a liquid propellant while the burned region again consisted of gaseous products. The physical existence of a liquid/gas interface led to the inclusion of additional physics in the model, namely surface tension at the interface and the influence of gravitational acceleration (downward propagation was assumed). As a result, and in contrast to strictly gaseous flame propagation, a stability criterion was derived such that the liquid/gas interface was either hydrodynamically stable or unstable in the Landau (cellular) sense depending on whether the product of the gravitational acceleration and the coefficient of surface tension was greater or less than a critical value. This result was later extended by Levich [4], who considered the effects of (liquid) viscosity in lieu of surface tension and obtained a similar result for the product of the gravitational acceleration and the viscosity of the liquid. These classical models of liquid-propellant

combustion, despite their relative simplicity, have long served as seminal examples that correctly describe the onset of (cellular) hydrodynamic instability in reactive systems.

Although the assumption of a thin reaction region remains a frequently valid and useful simplification in many combustion studies, the classical assumption of a constant normal burning rate has long been regarded as a probable oversimplification when applied to the problem of combustion instability. Early attempts at modification began with the phenomenological assumption of a linear relationship between the burning rate and the flame curvature (*cf.* Markstein [5]), while more modern approaches have employed sophisticated asymptotic methods to analyze the flame structure and to derive formal expressions for the burning rate as a function of local conditions at the combustion front, for both gaseous and condensed combustion waves (*cf.* [2, 3], Sivashinsky [6], Margolis [7]). In propellant combustion, on the other hand, it has long been customary to experimentally measure the pressure response, or pressure sensitivity, of the burning rate, as well as (to a lesser extent), its temperature sensitivity. Although asymptotic models that resolve the combustion-wave structure can be developed, under various approximations, for propellant combustion (*cf.* Margolis and Williams [8, 9], Bechtold and Margolis [10]), it nonetheless remains true that the direct assumption of a combustion surface that propagates according to a prescribed burning-rate law, such as a phenomenological law based on experimental observations, allows one to circumvent the intricacies of the combustion region and to impose fewer restrictive assumptions on the hydrodynamic model for the unburned and burned regions.

Accordingly, for the case of liquid-propellant combustion, the classical Landau/Levich hydrodynamic models may be combined and extended to account for a dynamic dependence, absent in the original formulations, of the instantaneous burning rate on the local pressure and temperature fields (Armstrong and Margolis [11, 12]). Although exact expressions for the neutral stability boundaries in question can be obtained in specific limiting cases, more general results may be obtained by exploiting the realistic smallness of the gas-to-liquid density ratio ρ . Thus, neglecting thermal coupling effects, an asymptotic analytical expression was derived for the cellular stability boundary $A_p(k)$, where A_p is the pressure sensitivity of the burning rate and k is the wavenumber of the disturbance (Margolis [13]). The results demonstrate explicitly the stabilizing effect of gravity on long-wave disturbances, the stabilizing effect of viscosity (both liquid and gas) and surface tension on short-wave perturbations, and the instability associated with intermediate wavenumbers for critical negative values of A_p . In the limiting case of weak gravity, it was shown that hydrodynamic instability in liquid-propellant combustion is a long-wave instability phenomenon, whereas at normal gravity, this instability is first manifested through $O(1)$ wavenumber disturbances. It was also demonstrated that, in general, surface tension and the viscosity of both the liquid and gas phases each produce comparable stabilizing effects in the large-wavenumber regime, thereby providing important modifications to the previous classical analyses in which one or more

of these effects was neglected. For $A_p = 0$, the Landau/Levich results are recovered from the new model in appropriate limiting cases, although, in the realistic limit of small ρ , this corresponds to a hydrodynamically unstable parameter regime [1, 4, 13].

In addition to the classical cellular form of hydrodynamic stability described thus far, there exists in this extended model a pulsating form of hydrodynamic instability corresponding to the loss of stability of the steady, planar solution to time-dependent perturbations (Margolis [14]). This occurs for negative values of the pressure-sensitivity parameter A_p , and is thus absent from the original Landau/Levich models. Nonetheless, its existence in the extended model results in a stable band of negative pressure sensitivities bounded above by the classical Landau type of hydrodynamic instability, and below by the pulsating form of hydrodynamic instability just described. A stable range of negative pressure sensitivities is applicable, for example, to certain types of hydroxylammonium nitrate (HAN)-based liquid propellants at low pressures for which nonsteady modes of combustion have been observed (Vosen [15]). While such nonsteady combustion may correspond to secondary and higher-order bifurcations above the cellular boundary (*cf.* Bechtold and Margolis [16]), it may also be a manifestation of the pulsating form of hydrodynamic instability just described.

In the present work, we explore the effects of incorporating a nonzero temperature sensitivity into our previous asymptotic analyses in the limit of small gas-to-liquid density ratios [13, 14]. This entails a coupling of the energy equation for temperature to the previous purely hydrodynamic problem, and leads to a significant modification to the pulsating boundary such that, for sufficiently large values of the temperature-sensitivity parameter, liquid-propellant combustion can become intrinsically unstable to this newer form of hydrodynamic instability.

2. The Mathematical Model and its Basic Solution

The mathematical model was described previously [13], but is briefly summarized here for completeness. In particular, it is assumed, as in the classical models, that there is no distributed reaction in either the liquid or gas phases, but that there exists either a pyrolysis reaction or an exothermic decomposition at the liquid/gas interface that depends on local conditions there. For simplicity, it is assumed that within the liquid and gas phases separately, the various physical properties are constants, with appropriate jumps in these quantities across the phase boundary.

The nondimensional location of the downward-propagating liquid/gas interface as a function of space and time is denoted by $x_3 = \Phi_s(x_1, x_2, t)$, where x_3 is the vertical coordinate and the adopted coordinate system is fixed with respect to the stationary liquid at $x_3 = -\infty$. Then, in the moving coordinate system $x = x_1$, $y = x_2$, $z = x_3 - \Phi_s(x_1, x_2, t)$, in terms of which the liquid/gas interface always lies at $z = 0$, the complete formulation of the problem is given by conservation of

mass, energy and momentum within each phase as

$$\nabla \cdot \mathbf{v} = 0, \quad z \neq 0, \quad (1)$$

$$\frac{\partial \Theta}{\partial t} - \frac{\partial \Phi_s}{\partial t} \frac{\partial \Theta}{\partial z} + \mathbf{v} \cdot \nabla \Theta = \left\{ \frac{1}{\lambda} \right\} \nabla^2 \Theta, \quad z \lesssim 0, \quad (2)$$

$$\frac{\partial \mathbf{v}}{\partial t} - \frac{\partial \Phi_s}{\partial t} \frac{\partial \mathbf{v}}{\partial z} + (\mathbf{v} \cdot \nabla) \mathbf{v} = (0, 0, -Fr^{-1}) - \left\{ \frac{1}{\rho^{-1}} \right\} \nabla p + \left\{ \frac{Pr_l}{\lambda Pr_g} \right\} \nabla^2 \mathbf{v}, \quad z \lesssim 0, \quad (3)$$

where $\mathbf{v}$, Θ and p denote velocity, temperature and pressure, respectively, Pr_l and Pr_g denote the liquid and gas-phase Prandtl numbers, ρ , λ and c (used below) are the gas-to-liquid density, thermal diffusivity and heat-capacity ratios, and Fr is the Froude number. These nondimensional variables have been defined in terms of their dimensional counterparts (denoted by tildes) as

$$\Theta = \frac{\tilde{T} - \tilde{T}_u}{\tilde{T}_a - \tilde{T}_u}, \quad \mathbf{v} = \frac{\tilde{\mathbf{v}}}{\tilde{U}}, \quad p = \frac{\tilde{p}}{\tilde{\rho}_l \tilde{U}^2}, \quad \Phi_s = \frac{\tilde{\Phi}_s \tilde{U}}{\tilde{\lambda}_l}, \quad t = \frac{\tilde{t} \tilde{U}^2}{\tilde{\lambda}_l}, \quad x_i = \frac{\tilde{x}_i \tilde{U}}{\tilde{\lambda}_l}, \quad (4)$$

where $\tilde{U}$ is the reference propagation speed of the interface for the case of steady, planar deflagration. The nondimensional parameters, some of which first appear below in the conditions at the gas/liquid interface, have been defined as

$$\rho = \frac{\tilde{\rho}_g}{\tilde{\rho}_l}, \quad \sigma_u = \frac{\tilde{T}_u}{\tilde{T}_a}, \quad \lambda = \frac{\tilde{\lambda}_g}{\tilde{\lambda}_l}, \quad c = \frac{\tilde{c}_g}{\tilde{c}_l}, \quad Fr = \frac{\tilde{U}^3}{\tilde{g} \tilde{\lambda}_l}, \quad \gamma = \frac{\tilde{\gamma}}{\tilde{\rho}_l \tilde{\lambda}_l \tilde{U}}, \quad Pr_l = \frac{\tilde{\nu}_l}{\tilde{\lambda}_l}, \quad Pr_g = \frac{\tilde{\nu}_g}{\tilde{\lambda}_g}, \quad (5)$$

where $\tilde{T}_u$ is the unburned (liquid) temperature at $z = -\infty$ and $\tilde{T}_a$ is the adiabatic burned (gas) temperature at $z = +\infty$, $\tilde{\gamma}$ is the coefficient of surface tension for the liquid surface, and $\tilde{\nu}_l$ and $\tilde{\nu}_g$ are the liquid and gas-phase kinematic viscosities. We note that the inverse Froude number Fr^{-1} represents the nondimensional gravitational acceleration and that $\rho \lambda Pr_g = \mu Pr_l$, where $\mu = \tilde{\mu}_g / \tilde{\mu}_l$ is the gas-to-liquid viscosity ratio. The nondimensional mass burning rate appearing in Eq. (9) below is defined by $A(p|_{z=0+}, \Theta|_{z=0}) = \tilde{A}(\tilde{p}|_{\tilde{x}_3=\tilde{\Phi}_s^+}, \tilde{T}|_{\tilde{x}_3=\tilde{\Phi}_s}) / \tilde{\rho}_l \tilde{U}$, and is assumed to be functionally dependent on the local pressure and temperature at the liquid/gas interface. By definition, $A = 1$ for the case of steady, planar burning, but perturbations in pressure and/or temperature result in corresponding perturbations in the local mass burning rate.

Equations (1) - (3) are subject to the boundary conditions

$$\mathbf{v} = 0, \quad \Theta = 0 \text{ at } z = -\infty, \quad \Theta = 1 \text{ at } z = +\infty, \quad \Theta|_{z=0-} = \Theta|_{z=0+} \quad (6)$$

and appropriate jump and continuity conditions at the liquid/gas interface. The latter consist of continuity of the transverse velocity components (no-slip),

$$\hat{\mathbf{n}}_s \times \mathbf{v}_- = \hat{\mathbf{n}}_s \times \mathbf{v}_+, \quad (7)$$

where $\mathbf{v}_\pm = \mathbf{v}|_{z=0^\pm}$, conservation of (normal) mass flux,

$$\hat{\mathbf{n}}_s \cdot (\mathbf{v}_- - \rho \mathbf{v}_+) = (1 - \rho) S(\Phi_s) \frac{\partial \Phi_s}{\partial t}, \quad (8)$$

the mass burning rate (pyrolysis) law,

$$\hat{\mathbf{n}}_s \cdot \mathbf{v}_- - S(\Phi_s) \frac{\partial \Phi_s}{\partial t} = A(p|_{z=0^+}, \Theta|_{z=0}), \quad (9)$$

conservation of flux of the normal and transverse components of momentum,

$$\begin{aligned} p|_{z=0^-} - p|_{z=0^+} = & \hat{\mathbf{n}}_s \cdot [\rho \mathbf{v}_+ (\hat{\mathbf{n}}_s \cdot \mathbf{v}_+) - \mathbf{v}_- (\hat{\mathbf{n}}_s \cdot \mathbf{v}_-) - \rho \lambda Pr_g \mathbf{e}_+ \cdot \hat{\mathbf{n}}_s + Pr_l \mathbf{e}_- \cdot \hat{\mathbf{n}}_s] + \hat{\mathbf{n}}_s \cdot (\mathbf{v}_- - \rho \mathbf{v}_+) S(\Phi_s) \frac{\partial \Phi_s}{\partial t} \\ & - \gamma S^3(\Phi_s) \left\{ \frac{\partial^2 \Phi_s}{\partial x^2} \left[1 + \left(\frac{\partial \Phi_s}{\partial y} \right)^2 \right] + \frac{\partial^2 \Phi_s}{\partial y^2} \left[1 + \left(\frac{\partial \Phi_s}{\partial x} \right)^2 \right] - 2 \frac{\partial \Phi_s}{\partial x} \frac{\partial \Phi_s}{\partial y} \frac{\partial^2 \Phi_s}{\partial x \partial y} \right\}, \end{aligned} \quad (10)$$

$$\hat{\mathbf{n}}_s \times \left[\rho \mathbf{v}_+ (\hat{\mathbf{n}}_s \cdot \mathbf{v}_+) - \mathbf{v}_- (\hat{\mathbf{n}}_s \cdot \mathbf{v}_-) + (\mathbf{v}_- - \rho \mathbf{v}_+) S(\Phi_s) \frac{\partial \Phi_s}{\partial t} \right] = \hat{\mathbf{n}}_s \times (\rho \lambda Pr_g \mathbf{e}_+ \cdot \hat{\mathbf{n}}_s - Pr_l \mathbf{e}_- \cdot \hat{\mathbf{n}}_s), \quad (11)$$

and conservation of heat flux

$$\begin{aligned} \hat{\mathbf{n}}_s \cdot (c \rho \lambda \nabla \Theta|_{z=0^+} - \nabla \Theta|_{z=0^-}) = & \hat{\mathbf{n}}_s \cdot [(c \rho \mathbf{v}_+ - \mathbf{v}_-) \Theta|_{z=0} + \hat{c} (\sigma_u \rho \mathbf{v}_+ - \mathbf{v}_-)] \\ & + [(1 - c \rho) \Theta|_{z=0} + \hat{c} (1 - \sigma_u \rho)] S(\Phi_s) \frac{\partial \Phi_s}{\partial t}, \end{aligned} \quad (12)$$

where $\hat{c} = c/(1 - \sigma_u)$, $\mathbf{e}$ is the rate-of-strain tensor ($\mathbf{e}_\pm = \mathbf{e}|_{z=0^\pm}$), γ is the surface-tension coefficient, σ_u is the unburned-to-burned temperature ratio, and $S(\Phi_s)$ and the unit normal $\hat{\mathbf{n}}_s$ are defined as

$$S(\Phi_s) \equiv [1 + (\partial \Phi_s / \partial x)^2 + (\partial \Phi_s / \partial y)^2]^{-1/2}, \quad \hat{\mathbf{n}}_s = (-\partial \Phi_s / \partial x, -\partial \Phi_s / \partial y, 1) S(\Phi_s). \quad (13)$$

Here, the factor multiplying γ in Eq. (10) is the curvature $-\nabla \cdot \hat{\mathbf{n}}_s$ of the liquid/gas interface in the moving coordinate system, and the corresponding expressions for the gradient operator ∇ and the Laplacian ∇^2 in this system are given by

$$\nabla = \left(\frac{\partial}{\partial x} - \frac{\partial \Phi_s}{\partial x} \frac{\partial}{\partial z}, \frac{\partial}{\partial y} - \frac{\partial \Phi_s}{\partial y} \frac{\partial}{\partial z}, \frac{\partial}{\partial z} \right), \quad (14)$$

$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} + \left[1 + \left(\frac{\partial \Phi_s}{\partial x} \right)^2 + \left(\frac{\partial \Phi_s}{\partial y} \right)^2 \right] \frac{\partial^2}{\partial z^2} - 2 \frac{\partial \Phi_s}{\partial x} \frac{\partial^2}{\partial x \partial z} - 2 \frac{\partial \Phi_s}{\partial y} \frac{\partial^2}{\partial y \partial z} - \left(\frac{\partial^2 \Phi_s}{\partial x^2} + \frac{\partial^2 \Phi_s}{\partial y^2} \right) \frac{\partial}{\partial z}. \quad (15)$$

However, the vector $\mathbf{v}$ still denotes the velocity with respect to the (x_1, x_2, x_3) coordinate system.

We observe that the thermal and hydrodynamic fields are coupled through the temperature dependence of the mass burning rate A appearing in Eq. (9). When A is assumed to depend on pressure only, the strictly hydrodynamic problem for p , $\mathbf{v}$ and Φ_s can be analyzed separately [13, 14]. In the present work, we wish to focus on this more extended coupling to determine

how the hydrodynamic stability boundaries are modified when the local burning rate depends on temperature as well. In connection with this we remark that although the mass burning rate A may be typically decomposed as

$$A(p|_{z=0+}, \Theta|_{z=0}) = \hat{A}(p|_{z=0+}, \Theta|_{z=0}) \exp \left[\frac{N(1 - \sigma_u)(\Theta|_{z=0} - 1)}{\sigma_u + (1 - \sigma_u)\Theta|_{z=0}} \right], \quad (16)$$

where $\hat{A}$ is a rate coefficient and $N = \tilde{E}/\tilde{R}^\circ \tilde{T}_a$ is the nondimensional activation energy ($\tilde{E}$), this more explicit representation will not be needed in the stability analysis that follows. Instead, our (linear) stability results may be expressed in terms of the pressure and temperature sensitivities, defined as

$$A_p = \partial A / \partial p|_{\Theta=1, p=0}, \quad A_\Theta = \partial A / \partial \Theta|_{\Theta=1, p=0} = N(1 - \sigma_u) + \hat{A}_\Theta, \quad (17)$$

respectively. However, we note that if the nondimensional activation energy is large, then the last of Eqs. (17) implies that A_Θ would likely be larger in magnitude than A_p , a fact that will play a role in the relative scalings introduced for A_p and A_Θ below.

A nontrivial basic solution to the above problem, corresponding to the special case of a steady, planar deflagration, is given by

$$\begin{aligned} \Phi_s^0 &= -t, \quad \mathbf{v}^0 = (0, 0, v^0), \quad v^0 = \begin{cases} 0, & z < 0 \\ \rho^{-1} - 1, & z > 0, \end{cases} \\ \Theta^0(z) &= \begin{cases} e^z, & z < 0 \\ 1, & z > 0, \end{cases} \quad p^0(z) = \begin{cases} -Fr^{-1}z + \rho^{-1} - 1, & z < 0 \\ -\rho Fr^{-1}z, & z > 0. \end{cases} \end{aligned} \quad (18)$$

The remainder of the paper is devoted to a linear stability analysis of this solution.

3. The Complete Linear Stability Problem

Prior to introducing any further approximations, we determine, in a standard fashion, the linear stability problem and the corresponding dispersion relation (in the form of a system of algebraic equations) that governs the behavior of harmonic perturbations about the basic solution (18). In particular, in terms of the perturbation quantities $\phi_s(x, y, z, t) = \Phi_s(x, y, z, t) - \Phi_s^0(t)$, $\mathbf{u}(x, y, z, t) = \mathbf{v}(x, y, z, t) - \mathbf{v}^0(z)$, $\zeta(x, y, z, t) = p(x, y, z, t) - p^0(z)$ and $\theta(x, y, z, t) = \Theta - \Theta^0(z) - \phi_s d\Theta^0/dz$, the problem obtained when Eqs. (1) – (3), (6) – (12) are linearized about the basic solution (18) is given by

$$\frac{\partial u_1}{\partial x} + \frac{\partial u_2}{\partial y} + \frac{\partial u_3}{\partial z} = 0, \quad z \neq 0, \quad (19)$$

$$\begin{aligned} \left\{ \frac{1}{\rho} \right\} \frac{\partial \mathbf{u}}{\partial t} + \frac{\partial \mathbf{u}}{\partial z} &= - \left(\frac{\partial \zeta}{\partial x} + \left\{ \frac{1}{\rho} \right\} Fr^{-1} \frac{\partial \phi_s}{\partial x}, \frac{\partial \zeta}{\partial y} + \left\{ \frac{1}{\rho} \right\} Fr^{-1} \frac{\partial \phi_s}{\partial y}, \frac{\partial \zeta}{\partial z} \right) \\ &\quad + \left\{ \frac{Pr_l}{\rho \lambda Pr_g} \right\} \left(\frac{\partial^2 \mathbf{u}}{\partial x^2} + \frac{\partial^2 \mathbf{u}}{\partial y^2} + \frac{\partial^2 \mathbf{u}}{\partial z^2} \right), \quad z \lesssim 0, \end{aligned} \quad (20)$$

$$\left\{ \frac{1}{\rho} \right\} \frac{\partial \theta}{\partial t} + \frac{\partial \theta}{\partial z} = \left\{ \begin{matrix} -u_3 e^z \\ 0 \end{matrix} \right\} + \left\{ \frac{1}{\rho \lambda} \right\} \left(\frac{\partial^2 \theta}{\partial x^2} + \frac{\partial^2 \theta}{\partial y^2} + \frac{\partial^2 \theta}{\partial z^2} \right), \quad z \lesssim 0, \quad (21)$$

$$\mathbf{u} = 0, \quad \theta = 0 \text{ at } z = -\infty, \quad \theta = 0 \text{ at } z = +\infty, \quad \theta|_{z=0+} - \theta|_{z=0-} = \phi_s, \quad (22)$$

$$u_1|_{z=0-} - u_1|_{z=0+} = (\rho^{-1} - 1) \frac{\partial \phi_s}{\partial x}, \quad (23)$$

$$u_2|_{z=0-} - u_2|_{z=0+} = (\rho^{-1} - 1) \frac{\partial \phi_s}{\partial y}, \quad (24)$$

$$u_3|_{z=0-} - \rho u_3|_{z=0+} = (1 - \rho) \frac{\partial \phi_s}{\partial t}, \quad (25)$$

$$u_3|_{z=0-} - \frac{\partial \phi_s}{\partial t} = A_p \zeta|_{z=0+} + A_\Theta \theta|_{z=0+}, \quad (26)$$

$$\begin{aligned} \zeta|_{z=0-} - \zeta|_{z=0+} = (2 - \rho) u_3|_{z=0+} - u_3|_{z=0-} + 2Pr_l \frac{\partial u_3}{\partial z} \Big|_{z=0-} - 2\rho \lambda Pr_g \frac{\partial u_3}{\partial z} \Big|_{z=0+} \\ - (1 - \rho) \frac{\partial \phi_s}{\partial t} - \gamma \left(\frac{\partial^2 \phi_s}{\partial x^2} + \frac{\partial^2 \phi_s}{\partial y^2} \right), \end{aligned} \quad (27)$$

$$\begin{aligned} \rho \lambda Pr_g \left(\frac{\partial u_1}{\partial z} \Big|_{z=0+} + \frac{\partial u_3}{\partial x} \Big|_{z=0+} \right) - Pr_l \left(\frac{\partial u_1}{\partial z} \Big|_{z=0-} + \frac{\partial u_3}{\partial x} \Big|_{z=0-} \right) = \\ (\rho^{-1} - 1) \frac{\partial \phi_s}{\partial x} + u_1|_{z=0+} - u_1|_{z=0-}, \end{aligned} \quad (28)$$

$$\begin{aligned} \rho \lambda Pr_g \left(\frac{\partial u_2}{\partial z} \Big|_{z=0+} + \frac{\partial u_3}{\partial y} \Big|_{z=0+} \right) - Pr_l \left(\frac{\partial u_2}{\partial z} \Big|_{z=0-} + \frac{\partial u_3}{\partial y} \Big|_{z=0-} \right) = \\ (\rho^{-1} - 1) \frac{\partial \phi_s}{\partial y} + u_2|_{z=0+} - u_2|_{z=0-}, \end{aligned} \quad (29)$$

$$c\rho\lambda \frac{\partial \theta}{\partial z} \Big|_{z=0+} - \frac{\partial \theta}{\partial z} \Big|_{z=0-} - c\theta|_{z=0+} + \theta|_{z=0-} = \hat{c} \rho u_3|_{z=0+} - (1 + \hat{c}) u_3|_{z=0-} + [1 + \hat{c}(1 - \rho)] \frac{\partial \phi_s}{\partial t}, \quad (30)$$

where $\hat{c} \equiv c(1 - \sigma_u)^{-1}$.

Nontrivial harmonic solutions for ϕ_s , $\mathbf{u}$ and ζ , proportional to $e^{i\omega t + ik_1 x + ik_2 y}$, that satisfy Eqs. (19) - (21) and the boundary/boundedness conditions at $z = \pm\infty$ are given by

$$\phi_s = e^{i\omega t + ik_1 x + ik_2 y}, \quad (31)$$

$$\zeta = e^{i\omega t + ik_1 x + ik_2 y} \begin{cases} b_1 e^{kz} - Fr^{-1}, & z < 0 \\ b_2 e^{-kz} - \rho Fr^{-1}, & z > 0, \end{cases} \quad (32)$$

$$u_1 = e^{i\omega t + ik_1 x + ik_2 y} \begin{cases} b_3 e^{qz} - ik_1 (i\omega + k)^{-1} b_1 e^{kz}, & z < 0 \\ b_4 e^{rz} - ik_1 (i\omega\rho - k)^{-1} b_2 e^{-kz}, & z > 0, \end{cases} \quad (33)$$

$$u_2 = e^{i\omega t + ik_1 x + ik_2 y} \begin{cases} b_5 e^{qz} - ik_2 (i\omega + k)^{-1} b_1 e^{kz}, & z < 0 \\ b_6 e^{rz} - ik_2 (i\omega\rho - k)^{-1} b_2 e^{-kz}, & z > 0, \end{cases} \quad (34)$$

$$u_3 = e^{i\omega t + ik_1 x + ik_2 y} \begin{cases} b_7 e^{qz} - k(i\omega + k)^{-1} b_1 e^{kz}, & z < 0 \\ b_8 e^{rz} + k(i\omega\rho - k)^{-1} b_2 e^{-kz}, & z > 0, \end{cases} \quad (35)$$

$$\theta = e^{i\omega t + ik_1 x + ik_2 y} \begin{cases} b_9 e^{pz} - [i\omega + k^2 - q(q+1)]^{-1} b_7 e^{(q+1)z} + k[(i\omega)^2 - k^2]^{-1} b_1 e^{(k+1)z}, & z < 0 \\ b_{10} e^{sz}, & z > 0, \end{cases} \quad (36)$$

where we have normalized the above solution by setting the coefficient of the harmonic dependence of ϕ_s to unity. Here, the signs of k_1 and k_2 may be either positive or negative and we have employed the definition $k = \sqrt{k_1^2 + k_2^2}$, and p, q, r and s are defined as

$$2p = 1 + \sqrt{1 + 4(i\omega + k^2)}, \quad (37)$$

$$2Pr_l q = 1 + \sqrt{1 + 4Pr_l(i\omega + Pr_l k^2)}, \quad (38)$$

$$2\mu Pr_l r = 1 - \sqrt{1 + 4\mu Pr_l(i\omega\rho + \mu Pr_l k^2)}, \quad (39)$$

$$2\rho\lambda s = 1 - \sqrt{1 + 4\rho^2\lambda(i\omega + \lambda k^2)}, \quad (40)$$

where we have used the fact, noted below Eq. (5), that $\rho\lambda Pr_g = \mu Pr_l$.

Substituting this solution into the interface conditions (25) - (31) and using Eq. (21) for $z \lesssim 0$ yields eleven conditions for the ten coefficients $b_1 - b_{10}$ and the complex frequency (dispersion relation) $i\omega(k)$. In particular, these conditions are given by

$$ik_1 b_3 + ik_2 b_5 + qb_7 = 0, \quad (41)$$

$$ik_1 b_4 + ik_2 b_6 + rb_8 = 0, \quad (42)$$

$$b_3 - \frac{ik_1}{i\omega + k} b_1 - b_4 + \frac{ik_1}{i\omega\rho - k} b_2 = \left(\frac{1}{\rho} - 1\right) ik_1, \quad (43)$$

$$b_5 - \frac{ik_2}{i\omega + k} b_1 - b_6 + \frac{ik_2}{i\omega\rho - k} b_2 = \left(\frac{1}{\rho} - 1\right) ik_2, \quad (44)$$

$$b_7 - \frac{k}{i\omega + k} b_1 - \rho b_8 - \frac{\rho k}{i\omega\rho - k} b_2 = (1 - \rho)i\omega, \quad (45)$$

$$b_7 - \frac{k}{i\omega + k} b_1 - A_p b_2 - A_\Theta b_{10} = i\omega - \rho Fr^{-1} A_p, \quad (46)$$

$$\begin{aligned} & \left[1 + \frac{k}{i\omega + k} (2kPr_l - 1)\right] b_1 - \left[1 + \frac{k}{i\omega\rho - k} (2k\mu Pr_l + 2 - \rho)\right] b_2 \\ & + (1 - 2Pr_l q) b_7 - (2 - \rho - 2\mu Pr_l r) b_8 = (1 - \rho)(Fr^{-1} - i\omega) + \gamma k^2, \end{aligned} \quad (47)$$

$$(\mu Pr_l r - 1) b_4 + (2k\mu Pr_l + 1) \frac{ik_1}{i\omega\rho - k} b_2 + ik_1 \mu Pr_l b_8 \quad (48)$$

$$+ (1 - Pr_l q) b_3 + (2Pr_l k - 1) \frac{ik_1}{i\omega + k} b_1 - ik_1 Pr_l b_7 = \left(\frac{1}{\rho} - 1\right) ik_1,$$

$$(\mu Pr_l r - 1) b_6 + (2k\mu Pr_l + 1) \frac{ik_2}{i\omega\rho - k} b_2 + ik_2 \mu Pr_l b_8 \quad (49)$$

$$+ (1 - Pr_l q) b_5 + (2Pr_l k - 1) \frac{ik_2}{i\omega + k} b_1 - ik_2 Pr_l b_7 = \left(\frac{1}{\rho} - 1\right) ik_2.$$

$$b_{10} - b_9 + [i\omega + k^2 - q(q+1)]^{-1}b_7 - k[(i\omega)^2 - k^2]^{-1}b_1 = 1, \quad (50)$$

$$(1 - c + c\rho\lambda s)b_{10} - pb_9 + \left[\frac{q+1}{i\omega + k^2 - q(q+1)} + 1 + \hat{c} \right] b_7 \\ - \frac{k}{i\omega + k} \left[\frac{k+1}{i\omega - k} + 1 + \hat{c} \right] b_1 - \hat{c}\rho b_8 - \frac{\hat{c}\rho k}{i\omega\rho - k} b_2 = 1 + i\omega[1 + \hat{c}(1 - \rho)], \quad (51)$$

While the above problem is linear in the coefficients $b_1 - b_8$, the relationship for $i\omega$ is highly nonlinear. Accordingly, we seek asymptotic solutions for the neutral stability boundaries in the limit that the gas-to-liquid density and viscosity ratios ρ and μ are small, as is Fr^{-1} in the case of reduced gravity. We shall also introduce appropriate scalings for the sensitivity parameters A_p and A_Θ , where the limiting results for $A_\Theta = 0$ were derived previously [13, 14]. In particular, we introduce a bookkeeping parameter $\epsilon \ll 1$ and consider the realistic parameter regime

$$\rho = \rho^* \epsilon, \quad \mu = \mu^* \epsilon, \quad Fr^{-1} = \begin{cases} g \sim O(1) \\ g^* \epsilon \sim O(\epsilon), \end{cases} \quad (52)$$

where the the upper (lower) choice for Fr^{-1} corresponds to normal (reduced) gravity. We note that based on characteristic densities for liquid propellants and product gases at elevated temperatures, a realistic value for ϵ is on the order of 10^{-3} or 10^{-4} . In this parameter regime, it was seen that the appropriate scaling for A_p to describe the neutral stability region was $A_p = A_p^* \epsilon$, whereas the appropriate scale that describes the fully-developed effects of thermal coupling turns out to be $A_\Theta = A_\Theta^* \epsilon^{1/4}$, as shown in Section 6 below. Thus, we observe that $A_\Theta/A_p \sim O(\epsilon^{-3/4}) \gtrsim 175$, which is at least several times as large as typical values of the nondimensional activation energy N , but still consistent with the last of Eqs. (17). However, as shown in Section 7, the first significant effects of thermal coupling are in fact felt on an intermediate scale $A_\Theta \sim O(\epsilon^{1/2})$, in which case $A_\Theta/A_p \sim O(\epsilon^{-1/2}) \gtrsim 30$, which is a quite typical value for N . Thus, the parameter regime of interest for describing modifications to the hydrodynamic stability boundaries arising from temperature-sensitivity effects coincides with realistic values of the sensitivity coefficients.

4. The Inviscid Limit

Although both liquid and gas-phase viscous effects were shown to be comparable in general to those due to surface tension when thermal coupling was neglected [13, 14], the qualitative nature of the cellular boundary remains preserved in the zero-viscosity limit, as does the existence of the pulsating boundary. Accordingly, we shall, for simplicity, first consider the effects of thermal sensitivity on hydrodynamic stability in the inviscid limit, reserving consideration of thermal coupling in the more algebraically involved viscous case for a future study (Part II). In particular, before introducing the scalings indicated above, we first set $Pr_l = Pr_g = 0$. Consequently, since $q \rightarrow \infty$ according to Eq. (38), we set $b_3 = b_5 = b_7 = 0$ in Eqs. (33) – (35), and observing that Eqs. (48) – (49) then reduce to the no-slip conditions (43) – (44), we thus eliminate Eqs. (41), (48) and (49)

from the above set. Using the fact that $r \rightarrow -i\omega\rho$, the solution for the remaining coefficients in terms of $i\omega$ is given by

$$b_8 = k \frac{(1-\rho)^2 [(i\omega)^2 \rho + k^2] + \rho(1-\rho^2)Fr^{-1}k + \rho(1+\rho)\gamma k^3}{2\rho(i\omega\rho - k)(i\omega\rho + k)}, \quad (53)$$

$$b_1 = -\frac{i\omega + k}{(1+\rho)k^2} [(i\omega + k)(1-\rho)k - \rho(i\omega\rho - k)b_8], \quad (54)$$

$$b_2 = -\frac{i\omega\rho - k}{\rho(1+\rho)k^2} [(i\omega\rho - k)(1-\rho)k + \rho^2(i\omega + k)b_8], \quad (55)$$

$$b_4 = \frac{\omega\rho k_1}{k^2} b_8, \quad b_6 = \frac{\omega\rho k_2}{k^2} b_8, \quad (56)$$

$$A_\Theta b_{10} = A_p \left[\rho Fr^{-1} + \frac{(i\omega\rho - k)^2(1-\rho)}{\rho(1+\rho)k} + \frac{\rho(i\omega\rho - k)(i\omega + k)}{(1+\rho)k^2} b_8 \right] + \frac{(1-\rho)k - 2i\omega\rho}{1+\rho} - \frac{\rho(i\omega\rho - k)}{(1+\rho)k} b_8, \quad (57)$$

$$b_9 = b_{10} - 1 + \frac{(i\omega + k)(1-\rho)k - \rho(i\omega\rho - k)b_8}{(1+\rho)(i\omega - k)k}. \quad (58)$$

Substitution of these results into Eq. (51) then gives a single implicit equation for $i\omega$ given by

$$\begin{aligned} [c(\rho\lambda s - 1) + 1 - p]b_{10} - \frac{1-\rho}{1+\rho} \left[\frac{i\omega + k}{i\omega - k} (p - k - 1) - (1 + \hat{c} + \hat{c}\rho)i\omega - k \right] \\ + \frac{\rho}{(1+\rho)k} \left[\frac{i\omega\rho - k}{i\omega - k} (p - k - 1) - (i\omega\rho - k) \right] b_8 = 1 - p + i\omega[1 + \hat{c}(1 - \rho)], \end{aligned} \quad (59)$$

where $b_8(i\omega)$ and $b_{10}(i\omega)$ are given explicitly by Eqs. (53) and (57), provided $A_\Theta \neq 0$. Equation (59) is thus the dispersion relation that determines the neutral stability boundaries in that case. In the limit $A_\Theta \rightarrow 0$, the dispersion relation is given by setting the right-hand side of Eq. (57) to zero, in which case Eqs. (58) and (59), which are then decoupled from Eqs. (53) – (57), determine b_9 and b_{10} . Alternatively, we may solve Eq. (59) for $b_{10}(i\omega)$ and substitute this result into Eq. (57), which then becomes the dispersion relation for arbitrary A_Θ . We remark that the special case $A_\Theta = 0$ yields an analytically tractable solution for the neutral stability boundaries [12], but since all other results to be presented are obtained for the parameter regime defined by Eqs. (52), we shall restrict ourselves to this regime for this limiting case as well.

5. Hydrodynamic Stability Boundaries in the Limit $A_\Theta = 0$

In the limit $A_\Theta = 0$, the results obtained from the dispersion relation (57) in the parameter regime (52) are as follows [13]. First (see Figure 1), the pulsating hydrodynamic stability boundary is given, to leading order in ϵ , by $A_p^* = -\rho^*$ for all disturbance wavenumbers [the exact relation is given by $A_p^* = -\rho^*/(1 - \epsilon\rho^*)$], with instability occurring below this critical value. For the

cellular stability boundary, the corresponding leading-order expression depends on the magnitude of the wavenumber k . In particular, there are three wavenumber scales to be considered; the $O(1)$, or outer, scale k , a far outer scale $k_f = k\epsilon$, and an inner scale defined by either $k_i = k/\epsilon$ if $Fr^{-1} \sim O(1)$ or $k_i = k/\epsilon^2$ if $Fr^{-1} \sim O(\epsilon)$. In each of these regions, the cellular stability boundary, on which the complex frequency $i\omega$ is identically zero, is given by

$$A_p^* \sim A_p^{*(o)} \sim -\frac{1}{2}\rho^*, \quad (60)$$

$$A_p^* \sim A_p^{*(f)} \sim \frac{1}{2}\rho^*(\rho^*\gamma k_f - 1), \quad (61)$$

and

$$A_p^* \sim A_p^{*(i)} \sim \begin{cases} \rho^*(\rho^*g - k_i)/2k_i, & Fr^{-1} \sim O(1) \\ \rho^*(\rho^*g^* - k_i)/2k_i, & Fr^{-1} \sim O(\epsilon), \end{cases} \quad (62)$$

respectively. Matching these solutions to one another, a uniformly valid composite expansion $A_p^{*(c)}(k)$ in the region $A_p^* < 0$ (the basic solution can be shown to be unstable for $A_p^* > 0$) may be constructed as

$$\begin{aligned} A_p^{*(c)} &\sim A_p^{*(i)} + A_p^{*(o)} + A_p^{*(f)} - \lim_{k_i \rightarrow \infty} A_p^{*(i)} - \lim_{k_f \rightarrow 0} A_p^{*(f)} \\ &\sim -\frac{1}{2}\rho^* + \frac{1}{2}\epsilon\rho^{*2}\gamma k + \begin{cases} \epsilon\rho^{*2}g/2k, & Fr^{-1} \sim O(1) \\ \epsilon^2\rho^{*2}g^*/2k, & Fr^{-1} \sim O(\epsilon), \end{cases} \end{aligned} \quad (63)$$

where the definitions of k_i and k_f have been used to express the final result in terms of k . We note that this asymptotic result, exhibited in Figure 1, is far simpler than the exact result [12], which, in our present notation, is given by

$$A_p^* = \rho^* \frac{\rho^*\epsilon(1 - \rho^*\epsilon)Fr^{-1} + \rho^*\epsilon\gamma k^2 - (1 - \rho^*\epsilon)k}{\rho^{*2}\epsilon^2(3 - \rho^*\epsilon)Fr^{-1} + \rho^{*2}\epsilon^2\gamma k^2 + (1 - \rho^*\epsilon)(2 - \rho^*\epsilon)k} \leq 0, \quad \omega = 0. \quad (64)$$

It is thus easily seen from Figure 1 that there is a stable region between the pulsating and cellular stability boundaries for $A_\Theta = 0$, and this result is preserved (in fact, enhanced) when viscous effects, which play a stabilizing role with respect to both boundaries for sufficiently large wavenumbers, are included in the analysis [13, 14]. We observe that for the Landau (cellular) form of hydrodynamic instability, gravity and surface tension are stabilizing with respect to sufficiently small and sufficiently large wavenumber disturbances, respectively. The essential difference, as illustrated in Figure 1, between the normal and reduced gravity limits in the realistic parameter regime considered here is that in the latter instance, gravity is only capable of stabilizing disturbances whose wavenumbers are very small, $O(\epsilon^2)$, whereas in the former case, gravity is sufficiently strong to stabilize disturbances whose wavenumbers are $O(\epsilon)$. As a consequence, hydrodynamic instability becomes a long-wave instability phenomenon in the reduced gravity regime considered here, since, from Eq. (63), the most unstable wavenumbers are $O(\sqrt{\epsilon})$, rather than $O(1)$, in that case. We remark that although positive values of the pressure sensitivity A_p are hydrodynamically unstable, zero and negative values of A_p over certain pressure ranges are, in fact, characteristic of

the so-called “plateau” and “mesa” types of solid propellants (*cf.* Timnat [17]), as well as for the HAN-based liquid propellants mentioned above [15].

6. Hydrodynamic Stability Boundaries for $A_\Theta > 0$

Retaining the parameter scalings introduced in Section 3, we first consider the $O(1)$ wavenumber regime. For the case $A_\Theta = 0$ considered previously, it turns out [14] that the appropriate expansion of the dispersion relation $i\omega(k)$ is of the form

$$i\omega \sim \epsilon^{-1/2}(i\omega_0 + \epsilon^{1/4}i\omega_1 + \epsilon^{1/2}i\omega_2 + \dots), \quad (65)$$

where the leading-order term was suggested by the explicit results available for the inviscid case, and the expansion in quarter powers of ϵ is suggested by the leading-order term in the resulting expansion for p given below. We now introduce the scaling $A_\Theta = \epsilon^n A_\Theta^*$, where the value of $n \geq 0$ is to be determined so as to give a nontrivial modification in the dispersion relation at the appropriate order, corresponding to the first effects of a nonzero temperature sensitivity on the neutral stability boundary for $O(1)$ wavenumbers.

Substituting Eq. (65) and the various scalings into Eqs. (37), (40) and (53), expanded forms for p , s and b_8 are obtained as

$$p \sim p_0 \epsilon^{-1/4} + p_1 + p_2 \epsilon^{1/4} + \dots, \quad s \sim O(\epsilon^{1/2}), \quad (66)$$

$$b_8 \sim -\frac{(i\omega_0)^2 \rho^* + k^2}{2\rho^* k} \epsilon^{-1} - \frac{1}{k} (i\omega_0)(i\omega_1) \epsilon^{-3/4} - \frac{1}{2k} [(i\omega_1^2) + 2(i\omega_0)(i\omega_2)] \epsilon^{-1/2} + \dots, \quad (67)$$

where

$$p_0 = (i\omega_0)^{1/2}, \quad p_1 = \frac{1}{2} \left[i\omega_1 / (i\omega_0)^{1/2} + 1 \right], \quad p_2 = \frac{1}{8} (i\omega_0)^{-1/2} [1 + 4k^2 + 4i\omega_2 - (i\omega_1)^2 / i\omega_0]. \quad (68)$$

Consequently, from Eqs. (57) and (67), b_{10} has the expanded form

$$\begin{aligned} b_{10} \sim & \epsilon^{-n} \frac{A_p^*}{A_\Theta^*} \left\{ \frac{k}{\rho^*} + \frac{i\omega_0}{2k^2} [(i\omega_0)^2 \rho^* - 3k^2] \epsilon^{1/2} + \dots \right\} \\ & + \frac{\epsilon^{-n}}{A_\Theta^*} \left\{ -\frac{1}{2k} [(i\omega_0)^2 \rho^* - k^2] - \frac{\rho^*}{k} (i\omega_0)(i\omega_1) \epsilon^{1/4} \right. \\ & \quad \left. + \frac{\rho^*}{2k} \left[\frac{i\omega_0}{k} \{ (i\omega_0)^2 \rho^* - 3k^2 \} - (i\omega_1)^2 - 2(i\omega_0)(i\omega_2) \right] \epsilon^{1/2} + \dots \right\} \\ \sim & \epsilon^{-n} \left[b_{10}^{(0)} + b_{10}^{(1)} \epsilon^{1/4} + b_{10}^{(2)} \epsilon^{1/2} + \dots \right], \end{aligned} \quad (69)$$

which, when substituted into the dispersion relation Eq. (59) along with the other expansions deduced thus far, yields a sequence of equations for the determination of the coefficients in the

expansion (65). Thus, at leading order, $O(\epsilon^{-n-1/4})$, Eq. (59) yields $b_{10}^{(0)} = 0$, which, from the implied definition of $b_{10}^{(0)}$ in Eq. (69) above, gives

$$A_p^* \frac{k}{\rho^*} - \frac{1}{2k} [(i\omega_0)^2 \rho^* - k^2] = 0, \quad (70a)$$

or

$$(i\omega_0)^2 = \left(\frac{k}{\rho^*} \right)^2 (2A_p^* + \rho^*). \quad (70b)$$

Consequently, $i\omega_0$ is identically zero for $A_p^* = -\rho^*/2$, which corresponds to the leading-order hydrodynamic cellular boundary (60) in the $O(1)$ wavenumber regime when $A_\Theta^* = 0$. Values of $A_p^* > -\rho^*/2$ imply cellular instability, since in that case there exists, according to Eq. (70b), a root of the dispersion relation such that $\text{Re}\{i\omega_0\} > 0$, $\text{Im}\{i\omega_0\} = 0$. On the other hand, the stability of the region $A_p^* < -\rho^*/2$ is still indeterminate, since Eq. (70b) indicates that $\text{Re}\{i\omega_0\} = 0$ there. Hence, the next nontrivial term in the expansion of $i\omega$ is required to determine whether this region is stable or unstable, although the fact that $\text{Im}\{i\omega_0\} \neq 0$ implies that disturbances have a pulsating character for values of A_p^* below the cellular stability boundary.

At the next order, $O(\epsilon^{-n})$, in the analysis of the dispersion relation, the equation $b_{10}^{(1)} = 0$ is obtained, whence the definition of $b_{10}^{(1)}$ in Eq. (69) implies that $i\omega_1 = 0$. Proceeding with the next higher order equation obtained at $O(\epsilon^{-n+1/4})$ from the expanded version of Eq. (59), it can be seen that terms other than those proportional to $A_\Theta^*{}^{-1}$ will appear provided the choice $n = 1/4$ is made. In that case, collecting terms of $O(\epsilon^0)$ and using the previous results $b_{10}^{(0)} = b_{10}^{(1)} = 0$ leads to the equation

$$-p_0 b_{10}^{(2)} + 2k - \frac{1}{2k} [(i\omega_0)^2 \rho^* + k^2] = 0, \quad (71a)$$

which, upon using the definitions of p_0 and $b_{10}^{(2)}$, may be solved for $i\omega_2$ as

$$\begin{aligned} i\omega_2 &= \frac{1}{2\rho^* k} [(i\omega_0)^2 \rho^* - 3k^2] \left[A_p^* + \rho^* + k A_\Theta^* (i\omega_0)^{-3/2} \right] \\ &= \frac{k}{\rho^{*2}} (A_p^* - \rho^*) \left[A_p^* + \rho^* + \rho^{*3/2} k^{-1/2} A_\Theta^* (2A_p^* + \rho^*)^{-3/4} \right], \end{aligned} \quad (71b)$$

where the expression (70b) for $i\omega_0$ has been used to obtain the final equality. It is readily seen that for $A_\Theta^* = 0$, $\text{Re}\{i\omega_2\} = 0$ for $A_p^* = -\rho^* < -\rho^*/2$. That is, as described in the previous section, there exists, since $\text{Im}\{i\omega\} \neq 0$, a pulsating neutral stability boundary that lies below the cellular boundary such that the region between the two, namely $-\rho^*/2 < A_p^* < -\rho^*$, is stable [$\text{Re}\{i\omega_2\} < 0$], and the region below the pulsating boundary is unstable [$\text{Re}\{i\omega_2\} > 0$].

For $A_\Theta^* > 0$, the pulsating boundary is modified. In particular, in the region $A_p^* < -\rho^*/2$ below the cellular boundary, the principal value of the complex factor in Eq. (71b) may be written as $(2A_p^* + \rho^*)^{-3/4} = [-(2A_p^* + \rho^*)]^{-3/4} e^{-3i\pi/4}$, and thus the neutral stability condition $\text{Re}\{i\omega_2\} = 0$ is given by

$$A_p^* + \rho^* - \frac{1}{2} \sqrt{2} \rho^{*3/2} k^{-1/2} A_\Theta^* [-(2A_p^* + \rho^*)]^{-3/4} = 0. \quad (72)$$

Writing $A_p^* = -\rho^* + \hat{a}\rho^*/2$, where $\hat{a}$ represents the deviation, in units of $\rho^*/2$, in the pulsating stability boundary from its value in the zero-thermal-sensitivity limit $A_\Theta^* = 0$, the condition (72) becomes $\hat{a} - \sqrt{2}\rho^{*-1/4}k^{-1/2}A_\Theta^*(1 - \hat{a})^{-3/4} = 0$, or equivalently,

$$\hat{a}^4(1 - \hat{a})^3 = 4\rho^{*-1}k^{-2}A_\Theta^{*4}, \quad (73a)$$

Equation (73a) is an implicit expression for the pulsating stability boundary $\hat{a}(k)$, where the value $\hat{a} = 1$ corresponds to the cellular boundary and $\hat{a} = 0$ is the pulsating boundary for $A_\Theta^* = 0$. Alternatively, writing $A_p^* = (-\rho^*/2)(1 + \hat{b})$, where $\hat{b} = 1 - \hat{a}$ is the negative deviation, in units of $\rho^*/2$, from the cellular stability boundary $A_p^* = -\rho^*/2$, Eq. (73a) can be rewritten in terms of $\hat{b}$ as

$$\hat{b}^3(1 - \hat{b})^4 = 4\rho^{*-1}k^{-2}A_\Theta^{*4}, \quad (73b)$$

where $\hat{b} = 1$ ($\hat{b} = 0$) corresponds to the pulsating (cellular) boundary in the limit $A_\Theta^* = 0$. A plot of $k(\hat{b})$ for several different values of A_Θ^* is shown in Figure 2, which, when rotated -90° so that the k -axis is horizontal, is readily interpreted in the context of Figure 1, the lines $A_p^* = -\rho^*/2$ and $A_p^* = -\rho^*$ in that figure corresponding to $\hat{b} = 0$ and $\hat{b} = 1$, respectively, in Figure 2.

Referring to Figure 2, it is seen that for $A_\Theta^* > 0$, the pulsating boundary becomes C-shaped (in the rotated frame of reference), the upper branch approaching the cellular boundary $\hat{b} = 0$ as $k \rightarrow \infty$, and the lower branch approaching the original ($A_\Theta^* = 0$) pulsating boundary $\hat{b} = 1$. These same limits are approached for any fixed value of k as $A_\Theta^* \rightarrow 0$. The portion within the C-shaped curve is the stable region, and thus not only is steady, planar burning intrinsically unstable for sufficiently small wavenumbers, but, for finite values of k , *any* crossing of the C-shaped boundary from the stable to the unstable region corresponds to the onset of a pulsating instability. As A_Θ^* increases, the turning point of the C-shaped pulsating boundary, which occurs at $\hat{b} = \hat{b}_c = 3/7$ (i.e., at $A_p^* = -5\rho^*/7$) corresponding to the critical wavenumber $k = k_c = (343/72)(21/\rho^*)^{1/2}A_\Theta^{*2} \approx 21.83 A_\Theta^{*2}/\rho^{*1/2}$, shifts to larger values of k as A_Θ^* increases. On the other hand, as A_Θ^* becomes small, the turning point shifts to small values of k such that k_c eventually leaves the $O(1)$ wavenumber region for which Eqs. (73) are valid. Thus, as A_Θ^* becomes small, the original pulsating and cellular boundaries are recovered in the $O(1)$ wavenumber regime, but as A_Θ^* becomes large, the original cellular boundary lies within the unstable region for $O(1)$ wavenumbers, and the basic solution becomes intrinsically unstable to oscillatory disturbances.*

A composite asymptotic solution for the neutral stability boundary in the regime $A_\Theta \sim O(\epsilon^{1/4})$ is thus obtained by matching the cellular and pulsating boundaries in the far outer wavenumber regime, where the former is given by Eq. (61) and the latter is given trivially by $A_p^* = -\rho^*$, with

These results correct an erroneous conclusion drawn in a previous study [12], where an algebraic error in a similar, but less formal, calculation incorrectly suggested that the pulsating boundary recedes (to more negative values of A_p^) as A_Θ^* increases, leaving the cellular boundary unaffected.

the appropriate solution branch of Eq. (72) in the $O(1)$ wavenumber region. In particular, we denote the two solution branches of Eq. (72), which correspond to the portions of Figure 2 that lie to the left and to the right of the minimum at $\hat{b} = \hat{b}_c$, by $A_p^{*(o,u)}(k)$ and $A_p^{*(o,l)}(k)$, where the superscript “o” denotes, as before, the outer, or $O(1)$, wavenumber region and the superscripts “u” and “l” denote the upper and lower (rotate Figure 2 by -90°) portions of the double-valued pulsating boundary $A_p^*(k)$. These branches are given implicitly by Eq. (73b), where, by definition, $\hat{b} = -(2A_p^*/\rho^* + 1)$. Along the upper branch, $A_p^{*(o,u)} \rightarrow -\rho^*/2$ (i.e., $\hat{b} \rightarrow 0$) as $k \rightarrow \infty$, which can be matched with Eq. (61) since, from Eq. (61), $A_p^{*(f)} \rightarrow -\rho^*/2$ as $k_f \rightarrow 0$. Similarly, $A_p^{*(o,l)} \rightarrow -\rho^*$ (i.e., $\hat{b} \rightarrow 1$) as $k \rightarrow \infty$, which clearly matches the pulsating boundary $A_p^* = -\rho^*$ in the far outer wavenumber region. As a result, a leading-order composite stability boundary spanning both the outer and far outer wavenumber regions is given by

$$A_p^*(k) \sim \begin{cases} A_p^{*(o,u)}(k) + \epsilon \rho^{*2} \gamma k / 2, & A_p^* \geq -5\rho^*/7 \\ A_p^{*(o,l)}(k), & A_p^* \leq -5\rho^*/7, \end{cases} \quad (74)$$

where the second term in the top expression has been expressed in terms of the outer wavenumber variable k . This composite boundary is shown in Figure 3. We note, based on the above construction, that the lower branch of Eq. (74) is a pulsating boundary for all wavenumbers, whereas the upper branch transitions from a pulsating boundary for $O(1)$ wavenumbers to a cellular boundary for $O(\epsilon^{-1})$ wavenumbers. Indeed, from Eq. (70b), we observe that in the outer wavenumber regime, the size of the upper region of oscillatory instability, which is bounded below by the upper branch of the pulsating stability boundary and above by the region of nonoscillatory instability beyond the old cellular boundary $A_p^* \sim -\rho^*/2$ for $A_\Theta^* = 0$, shrinks to zero as k becomes large.

7. Evolution of the Pulsating Boundary for $A_\Theta^* \ll 1$

The nature of the evolution, as A_Θ^* decreases, of the pulsating stability boundary depicted in Figure 2 to that shown in Figure 1 for the case $A_\Theta^* = 0$ may be determined by analyzing the dispersion relation for smaller order-of-magnitude wavenumbers and appropriately rescaled values of A_Θ . In particular, the results (70b) and (73b) suggest that if we consider $k \sim O(\epsilon^a)$, then $A_\Theta^* \sim O(\epsilon^{a/2})$ and $i\omega_0 \sim O(\epsilon^a)$, where the latter imply that A_Θ and $i\omega$ are $O(\epsilon^{(2a+1)/4})$ and $O(\epsilon^{(2a-1)/2})$, respectively. A preliminary analysis then suggests that qualitative deviations from the C-shaped nature of the pulsating boundary exhibited in Figure 2 occur for wavenumbers of order $\epsilon^{1/2}$, which is another intermediate wavenumber scale that lies between the inner and outer wavenumber regions that were defined in the previous section. The above analysis is thus repeated for $k = \hat{k}\epsilon^{1/2}$ and $A_\Theta = \hat{A}_\Theta\epsilon^{1/2}$, the other parameters remaining unchanged from their previously assumed orders of magnitude. Consequently, in place of Eq. (65), a solution for the dispersion relation is now sought in the form

$$i\omega \sim i\hat{\omega}_0 + \epsilon^{1/4}i\hat{\omega}_1 + \epsilon^{1/2}i\hat{\omega}_2 + \dots \quad (75)$$

Substituting Eq. (75) and the new scalings introduced above into Eqs. (37), (40) and (53), the new expanded forms of p , s and b_8 are given by

$$p \sim \hat{p}_0 + \hat{p}_1 \epsilon^{1/4} + \hat{p}_2 \epsilon^{1/2} + \dots, \quad s \sim O(\epsilon), \quad (76)$$

$$b_8 \sim -\frac{(i\hat{\omega}_0)^2 \rho^* + \hat{k}^2}{2\rho^* \hat{k}} \epsilon^{-1/2} - \frac{1}{\hat{k}} (i\hat{\omega}_0)(i\hat{\omega}_1) \epsilon^{-1/4} - \frac{1}{2\hat{k}} [(i\hat{\omega}_1^2) + 2(i\hat{\omega}_0)(i\hat{\omega}_2)] \epsilon^0 + \dots, \quad (77)$$

where

$$\hat{p}_0 = \frac{1}{2} \left[1 + (i\omega_0)^{1/2} \right], \quad \hat{p}_1 = \frac{1}{4} i\hat{\omega}_1 (1 + 4i\hat{\omega}_0)^{-1/2}, \quad \hat{p}_2 = \frac{1}{4} i\hat{\omega}_2 (1 + 4i\hat{\omega}_0)^{-1/2}. \quad (78)$$

As a result, Eqs. (57) and (67) give the corresponding expansion of b_{10} as

$$\begin{aligned} b_{10} \sim \epsilon^0 \frac{A_p^*}{\hat{A}_\Theta} \left\{ \frac{\hat{k}}{\rho^*} + \frac{i\hat{\omega}_0}{2\hat{k}^2} [(i\hat{\omega}_0)^2 \rho^* - 3\hat{k}^2] \epsilon^{1/2} + \dots \right\} \\ + \frac{\epsilon^0}{\hat{A}_\Theta} \left\{ -\frac{1}{2\hat{k}} [(i\hat{\omega}_0)^2 \rho^* - \hat{k}^2] - \frac{\rho^*}{\hat{k}} (i\hat{\omega}_0)(i\hat{\omega}_1) \epsilon^{1/4} \right. \\ \left. + \frac{\rho^*}{2\hat{k}} \left[\frac{i\hat{\omega}_0}{\hat{k}} \{ (i\hat{\omega}_0)^2 \rho^* - 3\hat{k}^2 \} - (i\hat{\omega}_1)^2 - 2(i\hat{\omega}_0)(i\hat{\omega}_2) \right] \epsilon^{1/2} + \dots \right\} \\ \sim \hat{b}_{10}^{(0)} + \hat{b}_{10}^{(1)} \epsilon^{1/4} + \hat{b}_{10}^{(2)} \epsilon^{1/2} + \dots \end{aligned} \quad (79)$$

Substituting these expansions into the dispersion relation (59), one obtains from the leading $O(\epsilon^0)$ terms in that equation the result $\hat{b}_{10}^{(0)} = 0$, or, according to Eq. (79),

$$(i\hat{\omega}_0)^2 = \left(\frac{\hat{k}}{\rho^*} \right)^2 (2A_p^* + \rho^*). \quad (80)$$

Comparing Eq. (80) with Eq. (70b), it is thus seen that the same leading-order result is obtained for $i\hat{\omega}_0(\hat{k})$ for $A_\Theta \sim O(\epsilon^{1/2})$ as was obtained for $i\omega_0(k)$ for $A_\Theta \sim O(\epsilon^{1/4})$. In particular, $i\hat{\omega}_0$ is real and positive for $A_p^* > -\rho^*/2$, and is pure imaginary for $A_p^* \leq -\rho^*/2$. Thus, the prediction of cellular instability is recovered in the former case, but stability in the latter region can only be ascertained by calculating the next nontrivial term in the expansion (75).

Collecting terms of $O(\epsilon^{1/4})$ in the expanded version of Eq. (59), it is concluded that $b_{10}^{(1)} = 0$, which, from Eq. (79), implies that $i\hat{\omega}_1 = 0$. Proceeding to the next order, we collect terms of $O(\epsilon^{1/2})$ in Eq. (59), which gives rise to the nontrivial equation

$$b_{10}^{(2)} (1 - c - \hat{p}_0) + (2\hat{k} + \rho^* b_8^{(0)}) \left(1 + \frac{1 - \hat{p}_0}{i\hat{\omega}_0} \right) = 0, \quad (81a)$$

where, from Eq. (77), $b_8^{(0)} = -(i\hat{\omega}_0)(i\hat{\omega}_2)/\hat{k}$. Upon substituting the expressions for $b_{10}^{(2)}$ and $(i\hat{\omega}_0)^2$ from Eqs. (79) and (80), we obtain the expression for $i\hat{\omega}_2$ as

$$i\hat{\omega}_2 = \hat{k}(A_p^* - \rho^*) \left[A_p^* + \rho^* - \frac{\hat{A}_\Theta \rho^{*2}}{\hat{k}(2A_p^* + \rho^*)} \left(\frac{1 + 2i\hat{\omega}_0 - \sqrt{1 + 4i\hat{\omega}_0}}{1 - 2c - \sqrt{1 + 4i\hat{\omega}_0}} \right) \right], \quad (81b)$$

where $i\hat{\omega}_0 = (\hat{k}/\rho^*)(2A_p^* + \rho^*)^{1/2} = (\hat{k}/\rho^*)[-(2A_p^* + \rho^*)]^{1/2}e^{i\pi/2}$, the second equality denoting the principal root when $A_p^* < -\rho^*/2$. The expressions (81b) and (71b) for the two growth-rate corrections $i\hat{\omega}_2$ and $i\omega_2$ in their respective wavenumber regimes collapse to the same result in the limit of zero thermal sensitivity, yielding the same pulsating stability boundary $\hat{A}_p^* = -\rho^*$ as before. However, for nonzero $\hat{A}_\Theta$, the forms of these two results differ, leading to qualitative differences in the corresponding neutral stability boundaries. In particular, it will be shown below that the pulsating neutral stability boundary obtained from Eq. (81b) approaches that shown in Figure 1 (*i.e.*, $A_p^* = -\rho^*$) in the limit of zero thermal sensitivity, whereas it approaches the form shown in Figure 2 as $\hat{A}_\Theta$ becomes large. That is, the evolution between these two limiting forms occurs on the $O(\epsilon^{1/2})$ wavenumber scale for $O(\epsilon^{1/2})$ values of the thermal sensitivity parameter A_Θ .

Setting the real part of $i\hat{\omega}_2$ to zero, the equation governing the (pulsating) neutral stability boundary $\hat{A}_p^*(\hat{k})$ in the present wavenumber regime is determined from Eq. (81b) as

$$A_p^* + \rho^* - \frac{\hat{A}_\Theta \rho^{*2}}{\hat{k}(2A_p^* + \rho^*)} \mathcal{Re} \left\{ \frac{1 + 2i\hat{\omega}_0 - \sqrt{1 + 4i\hat{\omega}_0}}{1 - 2c - \sqrt{1 + 4i\hat{\omega}_0}} \right\} = 0, \quad (82)$$

which, since $i\hat{\omega}_0$ depends on $\hat{A}_p$ and $\hat{k}$, is a highly nonlinear equation for $\hat{A}_p(\hat{k})$. Thus, in order to determine the nature of the stability boundary as a function of $\hat{A}_\Theta$, it is useful to consider certain limiting cases. We first consider possible solutions of Eq. (82) in the large (scaled) wavenumber regime $\hat{k} \gg 1$. In that limit, we observe from Eq. (70b) that $i\hat{\omega}_0 \sim O(\hat{k}) \gg 1$, and thus a first approximation to Eq. (81) in this regime is given by

$$A_p^* + \rho^* - \frac{\hat{A}_\Theta \rho^{*2}}{\hat{k}(2A_p^* + \rho^*)} \mathcal{Re} \left\{ -\sqrt{i\hat{\omega}_0} \right\} \sim 0, \quad (83a)$$

or, using the expression for the principal root $i\hat{\omega}_0$ given below Eq. (81b),

$$A_p^* + \rho^* - \frac{1}{2}\sqrt{2}\rho^{*3/2}\hat{k}^{-1/2}\hat{A}_\Theta [-(2A_p^* + \rho^*)]^{-3/4} \sim 0, \quad (83b)$$

which, since $\hat{k}^{-1/2}\hat{A}_\Theta = (k/\epsilon^{1/2})^{-1/2}(A_\Theta/\epsilon^{1/2}) = k^{-1/2}(A_\Theta/\epsilon^{1/4}) = k^{-1/2}A_\Theta^*$, is identical to Eq. (72). According to the discussion of Eq. (72) above, the turning point in the corresponding neutral stability boundary exhibited in Figure 2 occurs at the value $k_c \propto A_\Theta^{*2}$. Thus, we conclude that Eq. (83b) is a valid approximation for Eq. (82) in the large (scaled) wavenumber regime $\hat{k} \gg 1$ provided $\hat{A}_\Theta^2 \gg 1$, where the latter is a necessary condition to insure that $\hat{k}$ is large everywhere along the stability boundary described by Eq. (83b). For such values of $\hat{A}_\Theta$, the pulsating stability boundary for large $\hat{k}$ approaches that illustrated in Figure 2 (with k replaced by $\hat{k}$ and A_Θ^* replaced with $\hat{A}_\Theta$ in the definition of $\hat{b}$).

In addition to the boundary described by Eq. (83b) and Figure 2 for large $\hat{k}$ and $\hat{A}_\Theta$, there is another pulsating branch that is present for small wavenumbers, as suggested by the observation

that there exists a solution of Eq. (82) such that $A_p^* \rightarrow 0$ as $\hat{k} \rightarrow 0$, irrespective of the magnitude of $\hat{A}_\Theta$. To simplify the analysis and further discussion, we mainly consider a simplified form of Eq. (82) by restricting further consideration to the reasonable limit in which the heat-capacity ratio c is small. Since $1 + 2i\hat{\omega}_0 - \sqrt{1 + 4i\hat{\omega}_0} = (1 - \sqrt{1 + 4i\hat{\omega}_0})^2/2$, a first approximation to Eq. (82) in that limit is given by

$$A_p^* + \rho^* + \frac{\hat{A}_\Theta \rho^{*2}}{2\hat{k}(2A_p^* + \rho^*)} \text{Re} \left\{ \sqrt{1 + 4i\hat{\omega}_0} - 1 \right\} \sim 0, \quad c \rightarrow 0, \quad (84)$$

which clearly gives the same limiting approximation (83a) for large $\hat{k}$. To analyze Eq. (84) for arbitrary $\hat{k}$, it is convenient to convert it to an alternative form as follows. Writing $1 + 4i\hat{\omega}_0$ in the polar form $1 + 4i\hat{\omega}_0 = r \cos \vartheta + i \sin \vartheta$, where $r^2 = 1 + 16\hat{\omega}_0^2$, $\cos \vartheta = 1/r$ and $\sin \vartheta = 4\hat{\omega}_0/r$, Eq. (84) may be rewritten as

$$2\hat{\omega}_0^2(A_p^* + \rho^*) = \hat{k}\hat{A}_\Theta \left[\sqrt{\frac{(1 + 16\hat{\omega}_0^2)^{1/2} + 1}{2}} - 1 \right], \quad (85)$$

where, from Eq. (80), $\hat{\omega}_0^2 = -(\hat{k}/\rho^*)^2(2A_p^* + \rho^*)$. Substituting this expression for $\hat{\omega}_0^2$ into Eq. (85) and rearranging/squaring the latter twice so as to remove the fractional powers, a polynomial equation for the inverse relation $\hat{k}(A_p^*; \hat{A}_\Theta)$ is obtained as

$$4\hat{k}^3(2A_p^* + \rho^*)^3(A_p^* + \rho^*)^4 - 8\hat{k}^2\rho^{*2}\hat{A}_\Theta(2A_p^* + \rho^*)^2(A_p^* + \rho^*)^3 + \hat{k} \left[5\rho^{*4}\hat{A}_\Theta^2(2A_p^* + \rho^*)(A_p^* + \rho^*)^2 + \rho^{*6}\hat{A}_\Theta^4 \right] - \rho^{*6}\hat{A}_\Theta^3(A_p^* + \rho^*) = 0, \quad (86a)$$

or, introducing $\hat{b} = -(2A_p^*/\rho^* + 1)$ as before,

$$\hat{k}^3\hat{b}^3(1 - \hat{b})^4 + 4\hat{k}^2\hat{A}_\Theta\hat{b}^2(1 - \hat{b})^3 + \hat{k} \left[5\hat{A}_\Theta^2\hat{b}(1 - \hat{b})^2 - 4\hat{A}_\Theta^4/\rho^* \right] + 2\hat{A}_\Theta^3(1 - \hat{b}) = 0. \quad (86b)$$

An even more compact version is obtained by defining $\tilde{k} = \hat{b}(1 - \hat{b})\hat{k}/\hat{A}_\Theta$, giving the cubic equation

$$\tilde{k}^3 + 4\tilde{k}^2 + (5 - \alpha)\tilde{k} + 2 = 0, \quad (86c)$$

where $\alpha(\hat{b}) = 4\hat{A}_\Theta^2/[\rho^*\hat{b}(1 - \hat{b})^2]$. However, since it is the relation $\hat{A}_p^*(\hat{k}; \hat{A}_\Theta)$, or equivalently, $\hat{k}(\hat{b}; \hat{A}_\Theta)$, that is ultimately desired, we shall mainly consider the form given by Eq. (86b).

In the regime $\hat{A}_\Theta \gg 1$ there exists a solution $\hat{k} \sim O(\hat{A}_\Theta^2)$ as suggested above. More precisely, this solution of Eq. (86b) may be sought in the form

$$\hat{k} \sim \hat{A}_\Theta^2(\hat{k}_0 + \hat{A}_\Theta^{-1}\hat{k}_1 + \hat{A}_\Theta^{-2}\hat{k}_2 + \dots), \quad (87)$$

whence, upon substitution of this expansion into Eq. (86b), the coefficients $\hat{k}_i$ are determined recursively as

$$\hat{k}_0 = 2\hat{b}^{-3/2}(1 - \hat{b})^{-2}/\rho^{*1/2}, \quad \hat{k}_1 = -2\hat{b}^{-1}(1 - \hat{b})^{-1}, \dots \quad (88)$$

As expected, the leading-order approximation $\hat{k} \sim \hat{A}_\Theta^2 \hat{k}_0$ is identical in form to the result (73b) and the next term in the above expansion thus provides a negative correction to this result. On the other hand, for large $\hat{A}_\Theta$ there also exists a solution $\hat{k} \ll 1$ of the form

$$\hat{k} \sim \hat{A}_\Theta^{-1}(\bar{k}_0 + \hat{A}_\Theta^{-1}\bar{k}_1 + \hat{A}_\Theta^{-2}\bar{k}_2 + \dots). \quad (89)$$

Substituting the latter into Eq. (85b), the $\bar{k}_i$ are also determined recursively as

$$\bar{k}_0 = \rho^*(1 - \hat{b})/2, \quad \hat{k}_1 = 0, \quad \bar{k}_2 = 5\rho^{*2}\hat{b}(1 - \hat{b})^3/8, \dots \quad (90)$$

where the last of these provides a positive correction to the leading-order approximation $\hat{k} \sim (2\hat{A}_\Theta)^{-1}\rho^*(1 - \hat{b})$. Although the branches described by Eqs. (87) and (89) were obtained for $\hat{A}_\Theta \gg 1$, they remain reasonably accurate representations of the actual branches even for $O(1)$ values of this parameter, as shown in Figures 4a,b (discussed immediately below).

As $\hat{A}_\Theta$ decreases through $O(1)$ values, the turning point in the stability boundary for large $\hat{k}$ occurs for smaller values of $\hat{k}$, and eventually the expansion for large $\hat{k}$ ceases to be a valid approximation of Eq. (86b). Simultaneously, the branch corresponding to small values of $\hat{k}$ reaches larger values of $\hat{k}$ such that the above expansion for small $\hat{k}$ ceases to be valid as well. These two branches eventually intersect, restoring a region of stability for a range of negative values of A_p^* . This development is illustrated in Figures 4a-e, which were obtained directly from the exact roots of the cubic equation (86b) with respect to $\hat{k}$ [for comparison, we also indicate the asymptotic representation for the upper branch corresponding to one- and two-term truncations of Eq. (87)]. We observe that after the two pulsating branches intersect (as, for example, in Figures 4c-e), there exist two critical values of $\hat{k}$ corresponding to the onset of pulsating instability at corresponding critical values of $\hat{b}$, or equivalently, A_p^* . That is, in this range of temperature sensitivities, a pulsating hydrodynamic instability occurs for either sufficiently small or sufficiently large negative values of A_p^* as either the left or right (upper or lower in the rotated frame of reference) stability boundary is crossed. As $\hat{A}_\Theta$ decreases further, the separated branches move further apart until ultimately, in the limit $\hat{A}_\Theta \rightarrow 0$, we recover from Eqs. (86) the two roots $\hat{b} = 0$ and $\hat{b} = 1$ corresponding to the cellular ($A_p^* = -\rho^*/2$) and pulsating ($A_p^* = -\rho^*$) stability boundaries in the present [$k \sim O(\epsilon^{1/2})$] wavenumber regime. Thus, as the temperature-sensitivity parameter A_Θ decreases to small values on the scale $A_\Theta/A_p \sim O(\epsilon^{-1/2}) \sim 50$, the region of hydrodynamic stability depicted in Figure 1 is recovered.

8. Summary

The present work has continued the formal asymptotic treatment of hydrodynamic instability in liquid-propellant combustion based on a generalized Landau/Levich model that allows for a dynamic dependence of the burning rate on local pressure and temperature perturbations. The

focus in the present study was on the effects of thermal coupling, represented by nonzero values of an appropriately defined temperature-sensitivity parameter A_Θ , on the nature of a pulsating stability boundary that exists for negative values of a corresponding pressure-sensitivity parameter A_p . Again exploiting the smallness of the gas-to-liquid density ratio ρ , which provides the underlying basis for the asymptotic treatment of the stability problem, it was shown that for sufficiently large values of A_Θ , the pulsating boundary possesses a turning point that renders steady, planar burning intrinsically unstable for sufficiently small wavenumber perturbations. As this parameter decreases, the stable region re-emerges such that in the limit that A_Θ vanishes, the original separated pulsating and cellular stability branches are recovered. The evolution of the pulsating boundary between these two structures was shown to occur on an intermediate wavenumber scale relative to the inner, outer and far outer wavenumber scales that emerge in the asymptotic limit of small density ratios in the absence of thermal coupling. Values of the ratio A_Θ/A_p over which this evolution occurs were shown to be roughly of the order of the overall activation energy, suggesting that a pulsating, rather than the classical Landau (cellular), form of hydrodynamic instability may be the more likely manifestation of hydrodynamic instability in at least some types of liquid propellants.

Acknowledgments

This work was supported by the United States Department of Energy under contract DE-AC04-94AL85000 and by the NASA Microgravity Science Research Program under contract C-32031-E.

References

- [1] Landau, L. D., On the Theory of Slow Combustion, *Acta Physicochimica URSS* 19:77-85 (1944), *Zh. Eksp. i Teor. Fiz.* 14:240 (1944).
- [2] Matalon, M., and Matkowsky, B. J., Flames as Gasdynamic Discontinuities, *J. Fluid Mech.* 124:239-259 (1982).
- [3] Pelcé, P., and Clavin, P., Influence of Hydrodynamics and Diffusion Upon the Stability Limits of Laminar Premixed Flames, *J. Fluid Mech.* 124:219-238 (1982).
- [4] Levich, V. G., On the Stability of the Flame Front When a Liquid is Burning Slowly, *Dokl. Akad. Nauk SSSR* 109:975-978 (1956).
- [5] Markstein, G. H., *Non-Steady Flame Propagation*, Pergamon, Press, Oxford, 1964.
- [6] Sivashinsky, G. I., Diffusional-Thermal Theory of Cellular Flames, *Combust. Sci. Tech.* 15:137-146 (1977).
- [7] Margolis, S. B., The Transition to Nonsteady Deflagration in Gasless Combustion, *Prog. Energy Combust. Sci.* 17:135-162 (1991).

- [8] Margolis, S. B., and Williams, F. A., Diffusional-Thermal Coupling and Intrinsic Instability of Solid Propellant Combustion, *Combust. Sci. Tech.* 59:27–84 (1988).
- [9] Margolis, S. B., and Williams, F. A., Diffusional/Thermal Instability of a Solid Propellant Flame, *SIAM J. Appl. Math.* 49:1390–1420 (1989).
- [10] Bechtold, J. K., and Margolis, S. B., Hydrodynamic Stability of Solid and Liquid Propellant Combustion, *Combust. Sci. Tech.* 68:49–84 (1989).
- [11] Armstrong, R. C., and Margolis, S. B., Hydrodynamic and Reactive/Diffusive Instabilities in a Dynamic Model of Liquid Propellant Combustion, *Twenty-Second Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, pp. 1807–1815 (1989).
- [12] Armstrong, R. C., and Margolis, S. B., Hydrodynamic and Reactive/Diffusive Instabilities in a Dynamic Model of Liquid Propellant Combustion—II. Inviscid Fluid Motions, *Combust. Flame* 77:123–138, (1989).
- [13] Margolis, S. B., Hydrodynamic Instability in an Extended Landau/Levich Model of Liquid-Propellant Combustion at Normal and Reduced Gravity, *Combust. Flame* 113:406–423 (1998).
- [14] Margolis, S. B., On Pulsating and Cellular Forms of Hydrodynamic Instability in Liquid-Propellant Combustion, *Twenty-Seventh Symposium (International) on Combustion*, to appear (1998).
- [15] Vosen, S. R., The Burning Rate of Hydroxylammonium Nitrate Based Liquid Propellants, *Twenty-Second Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, pp. 1817–1825 (1989).
- [16] Bechtold, J. K., and Margolis, S. B., Nonlinear Hydrodynamic Stability and Spinning Deflagration of Liquid Propellants, *SIAM J. Appl. Math.* 51:1356–1379 (1991).
- [17] Timnat, Y. M., *Advanced Chemical Rocket Propulsion*, Academic Press, London, 1987.

Figure Captions

Figure 1. Inviscid hydrodynamic stability boundaries in the limit of zero thermal coupling ($A_\Theta = 0$).

Figure 2. Pulsating hydrodynamic stability boundaries for $k \sim O(1)$ and $A_\Theta \sim O(\epsilon^{1/4})$.

Figure 3. Composite hydrodynamic stability boundary for $A_\Theta \sim O(\epsilon^{1/4})$.

Figures 4a–f. Pulsating hydrodynamic stability boundaries for $k = \hat{k}\epsilon^{1/2} \sim O(\epsilon^{1/2})$ and decreasing values of $A_\Theta = \hat{A}_\Theta\epsilon^{1/2} \sim O(\epsilon^{1/2})$. The broken curves denote one- and two-term asymptotic expansions of the upper boundary for $\hat{A}_\Theta \gg 1$, $\hat{k} \gg 1$. (a) $\hat{A}_\Theta = 1$; (b) $\hat{A}_\Theta = 2/3$; (c) $\hat{A}_\Theta = 3/5$; (d) $\hat{A}_\Theta = 1/2$; (e) $\hat{A}_\Theta = 1/4$; (f) $\hat{A}_\Theta = 1/16$.

Figure 1. Inviscid hydrodynamic stability boundaries in the limit of zero thermal coupling ($A_\Theta = 0$).

Figure 2. Pulsating hydrodynamic stability boundaries for $k \sim O(1)$ and $A_\Theta \sim O(\epsilon^{1/4})$.

Figure 3. Composite hydrodynamic stability boundary for $A_{\Theta} \sim O(\epsilon^{1/4})$.

Figure 4a

Figures 4a-f. Pulsating hydrodynamic stability boundaries for $k = \hat{k}\epsilon^{1/2} \sim O(\epsilon^{1/2})$ and decreasing values of $A_\Theta = \hat{A}_\Theta\epsilon^{1/2} \sim O(\epsilon^{1/2})$. The broken curves denote one- and two-term asymptotic expansions of the upper boundary for $\hat{A}_\Theta \gg 1$, $\hat{k} \gg 1$. (a) $\hat{A}_\Theta = 1$; (b) $\hat{A}_\Theta = 2/3$; (c) $\hat{A}_\Theta = 3/5$; (d) $\hat{A}_\Theta = 1/2$; (e) $\hat{A}_\Theta = 1/4$; (f) $\hat{A}_\Theta = 1/16$.

Pulsating Stability Boundary

Figure 4b

Pulsating Stability Boundary

Figure 4c

Pulsating Stability Boundary

Figure 4d

Pulsating Stability Boundary

Figure 4e

Pulsating Stability Boundary

$$\hat{A}_\Theta = 1/16$$

Figure 4f

UNLIMITED RELEASE
INITIAL DISTRIBUTION

Dr. John K. Bechtold
Department of Mathematics
New Jersey Institute of Technology
Newark, NJ 07102-1982

Dr. Mitat A. Birkan
Program Manager
Directorate of Aerospace and Engineering Sciences
Department of the Air Force
Bolling Air Force Base, DC 20332-6448

Prof. Michael Booty
Department of Mathematics
New Jersey Institute of Technology
Newark, NJ 07102-1982

Prof. John D. Buckmaster
Department of Aeronautical and Astronautical Engineering
University of Illinois
Urbana, IL 61801

Prof. Sebastien Candel
Ecole Central des Arts et Manufactures
Grande Voie de Vignes
92290 Chatenay-Malabry
FRANCE

Dr. John Card
Department of Mechanical Engineering
Yale University
New Haven, CT 06520

Prof. J. F. Clarke
College of Aeronautics
Cranfield Institute of Technology
Cranfield-Bedford MK43 0AL
ENGLAND

Prof. Paul Clavin
Laboratoire Dynamique et Thermophysique des Fluides
Universite de Provence
Centre Saint Jerome
13397 Marseille Cedex 4
FRANCE

Prof. F. E. C. Culick
Jet Propulsion Center
California Institute of Technology
Pasadena, CA 91125

Prof. Martin Golubitsky
Department of Mathematics
University of Houston
University Park
Houston, TX 77004

Prof. Michael Gorman
Department of Physics
University of Houston
Houston, TX 77004

Dr. Daryl D. Holm
CNLS, MS 457
Los Alamos National Laboratory
Los Alamos, NM 87545

Prof. G. M. Homsy
Department of Chemical Engineering
Stanford University
Stanford, CA 94305

Dr. G. Joulin
Laboratoire D'Energetique et de Detonique
Universite de Poitiers
Rue Guillaume VII
86034 Poitiers
FRANCE

Dr. Hans Kaper
Applied Mathematics Division
Argonne National Laboratory
9700 S. Cass Ave.
Argonne, IL 60439

Prof. A. K. Kapila
Department of Mathematical Sciences
Rensselaer Polytechnic Institute
Troy, NY 12128

Prof. D. R. Kassoy
Department of Mechanical Engineering
University of Colorado
Boulder, CO 80309

Prof. Joseph B. Keller
Department of Mathematics
Stanford University
Stanford, CA 94305

Prof. Barbara Keyfitz
Department of Mathematics
University of Houston
University Park
Houston, TX 77004

Prof. C. K. Law
Department of Mechanical and Aerospace Engineering
Engineering Quadrangle
Princeton University
Princeton, NJ 08544

Dr. Gary Leaf
Applied Mathematics Division
Argonne National Laboratory
9700 S. Cass Avenue
Argonne, IL 60439

Prof. Amable Liñán
Universidad Politécnica de Madrid
Escuela Técnica Superior de Ingenieros Aeronáuticos
Plaza del Cardenal Cisneros, 3
Madrid - 3
SPAIN

Prof. J. T. C. Liu
Division of Engineering, Box D
Brown University
Providence, RI 02912

Prof. Moshe Matalon
Department of Engineering Sciences and Applied Mathematics
Northwestern University
Evanston, IL 60208

Prof. Bernard J. Matkowsky
Department of Engineering Sciences and Applied Mathematics
Northwestern University
Evanston, IL 60208

Prof. A. C. McIntosh
Department of Fuel and Energy
University of Leeds
Leeds LS2 9JT
United Kingdom

Prof. D. O. Olagunju
Department of Mathematical Sciences
University of Delaware
Newark, DE 19716

Prof. R. E. O'Malley
Department of Applied Mathematics
University of Washington Seattle, WA 98195

Prof. Norbert Peters
Institute für Allgemeine Mechanik
Technische Hochschule Aachen
Aachen
GERMANY

Prof. Victor Roytburd
Department of Mathematical Sciences
Rensselaer Polytechnic Institute
Troy, NY 12128

Prof. W. A. Sirignano
Office of the Dean
School of Engineering
University of California, Irvine
Irvine, CA 92717

Prof. L. Sirovich
Division of Applied Mathematics, Box F
Brown University
Providence, RI 02912

Prof. G. I. Sivashinsky
Department of Mathematics
Tel-Aviv University
Ramat-Aviv, Tel-Aviv 69978
ISRAEL

Prof. Mitchell D. Smooke
Department of Mechanical Engineering
Yale University
New Haven, CT 06520

Prof. D. Scott Stewart
Department of Theoretical and Applied Mechanics
University of Illinois
Urbana, IL 61801

Prof. C. H. Su
Division of Applied Mathematics, Box F
Brown University
Providence, RI 02912

Prof. Cesar Treviño
Departamento de Termica y Fluidos
Universidad Nacional Autonoma de Mexico
Facultad de Ingenieria
Pacios No. 12, Jardines del Sur
MEXICO 23, D.F.

Prof. Vladimir Volpert
Department of Engineering Sciences and Applied Mathematics
Northwestern University
Evanston, IL 60208

Dr. David Weaver
Air Force Rocket Propulsion Laboratory
DYP/Stop 24
Edwards Air Force Base, CA 93523

Prof. Forman A. Williams
Department of Applied Mechanics and Engineering Sciences
University of California, San Diego
La Jolla, CA 92093

Prof. Vigor Yang
Department of Mechanical Engineering
Pennsylvania State University
University Park, PA 16802

Prof. Benn Zinn
Department of Aerospace Engineering
Georgia Institute of Technology
225 North Avenue, NW
Atlanta, GA 30332

C. K. Westbrook, LLNL, L-321

MS 1110 R. C. Allen, 1422
MS 0834 A. C. Ratzel, 9112
MS 0834 M. R. Baer, 9112
MS 0834 M. L. Hobbs, 9112
MS 0834 R. J. Gross, 9112

MS 9001 T. O. Hunter, 8000
MS 9405 R. E. Stoltz, 8008
MS 9004 M. E. John, 8100
MS 9213 S. C. Johnston, 8103
MS 9054 W. J. McLean, 8300
MS 9163 W. Bauer, 8302
MS 9042 C. M. Hartwig, 8345
MS 9056 L. A. Rahn, 8351
MS 9051 W. T. Ashurst, 8351
MS 9051 A. R. Kerstein, 8351
MS 9052 D. R. Hardesty, 8361
MS 9055 R. Behrens, 8361
MS 9052 S. B. Margolis, 8361 (30)
MS 9053 R. W. Carling, 8362
MS 9021 Technical Communications Department, 8815, for DOE/OSTI
MS 9021 Technical Communications Department, 8815/Technical Library, MS 0899, 4916
MS 0899 Technical Library, 4916
MS 9018 Central Technical Files, 8940-2 (3)

Prof. Forman A. Williams
Department of Applied Mechanics and Engineering Sciences
University of California, San Diego
La Jolla, CA 92093

Prof. Vigor Yang
Department of Mechanical Engineering
Pennsylvania State University
University Park, PA 16802

Prof. Benn Zinn
Department of Aerospace Engineering
Georgia Institute of Technology
225 North Avenue, NW
Atlanta, GA 30332

C. K. Westbrook, LLNL, L-321

MS 1110 R. C. Allen, 1422
MS 0834 A. C. Ratzel, 9112
MS 0834 M. R. Baer, 9112
MS 0834 M. L. Hobbs, 9112
MS 0834 R. J. Gross, 9112

MS 9001 T. O. Hunter, 8000
MS 9405 R. E. Stoltz, 8008
MS 9004 M. E. John, 8100
MS 9213 S. C. Johnston, 8103
MS 9054 W. J. McLean, 8300
MS 9163 W. Bauer, 8302
MS 9042 C. M. Hartwig, 8345
MS 9056 L. A. Rahn, 8351
MS 9051 W. T. Ashurst, 8351
MS 9051 A. R. Kerstein, 8351
MS 9052 D. R. Hardesty, 8361
MS 9055 R. Behrens, 8361
MS 9052 S. B. Margolis, 8361 (30)
MS 9053 R. W. Carling, 8362
MS 9021 Technical Communications Department, 8815, for DOE/OSTI
MS 9021 Technical Communications Department, 8815/Technical Library, MS 0899, 4916
MS 0899 Technical Library, 4916
MS 9018 Central Technical Files, 8940-2 (3)