THERMAL PROPERTIES & CHEMICAL REACTIVITY

L. C. Myers

DEVELOPMENT DIVISION

APRIL - JUNE 1971
SANL 804-007

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

For
Lawrence Livermore Laboratory
Livermore, California

MASTER

Mason & Hanger-Silas Mason Co., Inc.
Pantex Plant

P. O. BOX 647
AMARILLO, TEXAS 79105
806-335-1581

operated for the
ATOMIC ENERGY COMMISSION
under

U. S. GOVERNMENT Contract DA-11-173-AMC-487 (A)

71-471

THERMAL PROPERTIES & CHEMICAL REACTIVITY

L. C. Myers

DEVELOPMENT DIVISION

The objective of this project is to determine the thermal and chemical reactivity properties of explosives, and to continue the development and evaluation of useful thermal tests.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

April - June 1971
SANL 804-007

Section F

THERMAL PROPERTIES & CHEMICAL REACTIVITY

ABSTRACT

The thermally aged LX-09 skid test parts were disassembled; the Dow Corning 93-120 silicone used to pot the parts in the aluminum hemisphere was reverting. Thermal analysis of LX-09 samples taken at various locations in the past do not show any variations.

Analyses of the atmosphere from six PASS LX-09 mechanical test specimens are reported.

The technique used to isolate two of the low boiling impurities in FEFO are discussed and an IR spectrum of one is reported.

The results from the thermal analysis of XTX (sample WSI-730) are discussed.

A system for taking digital data from a DSC-1 and the technique used to analyze these data are discussed. Some preliminary runs made on PETN and indium are reported.

DISCUSSION

THERMAL AGING OF SIX LX-09 SKID PARTS

Six LX-09 skid test parts were thermally aged at 70 C for 12 months, and six controlled parts were stored at ambient temperature. The thermally aged parts were potted in aluminum hemisphere shells with 40 mils of DC 93-120. After curing, two hemispheres were coupled with a threaded ring.

On disassembly, it was noted that the potting compound was reverting. The reversion was more severe at the equator (shown in Fig. 1). Near the pole the DC 93-120 was tacky. Inspection of the LX-09 parts showed a change in the color of some (Fig. 2), cracks on the surface (Fig. 3), and some HMX crystals stuck to the 93-120 and pulled out of the LX-09 (Figs. 3 and 4).

To determine if the DC 93-120 had been contaminated on assembly, one of the hemispheres was repotted. After 24 hours it had set up, which indicates that there was no foreign material present to contaminate the DC 93-120.

One of the six thermally aged parts was selected for mechanical and chemical analyses. When the part was sectioned there were many internal cracks and it was impossible to salvage any parts for mechanical testing. However, the sectioning was completed and samples were sent to LLL for chemical analysis, while Pantex retained samples for thermal analysis.

Fig. 1. Aluminum Hemisphere with reverted DC 93-120 Silicone

A. Thermally aged at 70 C for 12 months
B. Controlled sample at ambient temperature
for 12 months

Fig. 2. LX-09 Hemispheres

Fig. 3. Surface of IX-09 Hemisphere aged at 70 C for 12 months

Fig. 4. Surface of IX-09 Hemisphere aged 70 C for 12 months

Fig. 5. Location of Samples Used in Thermal Evaluation of Aged LX-09 Skid Test Fields

Two samples each from four locations in the hemisphere were selected (shown in Fig. 5). These eight samples were tested by DTA, TGA, pyrolysis, Henkin time-to-explosion, and chemical reactivity. None of the tests show any significant variations in any of the samples.

The skid test data are reported in another section of this report.

PASS A LX-09 EVALUATION PROGRAM

Last quarter the analysis of the atmosphere from four tensile specimen containers was reported. Two additional analyses were made this quarter. The results from all six samples are reported in Table I.

There is reasonable agreement between the runs. It was concluded that Sample 7 probably leaked during the time the sample was being removed. There is good agreement between Samples 9 and 13.

The three samples with nitrogen atmosphere are in good agreement with the exception of the water content. Sample 12 shows a greater amount of H_2O because the transfer to the gas chromatograph loop was made with liquid nitrogen.

Mechanical testing of the sample will be done by the Quality Division and samples of the HE will be sent back to the Development Division for thermal evaluation.

IMPURITIES IN FEFO

The recrystallization process outlined by LLL to purify FEFO has been used to concentrate the low boiling impurities. By removing the solvent from the filtrate via high vacuum and then removing the additional amount of FEFO by recrystallizing, it was possible to obtain a 50 ml sample which has approximately 10% of two of the low boiling impurities.

A small portion of the 50 ml sample has been chromatographed and a few micrograms of the two low boilers were obtained for IR analysis. An IR spectrum is shown (Fig. 6) from one of the samples and a IR spectrum will be obtained for the other low boilers, along with mass spectra for both samples. Hopefully, an identification can be made with this information.

THERMAL ANALYSIS OF XTX 8003 SAMPLE WSI-730

LLL provided Pantex with three samples of XTX 8003 (WSI-730, ~ 10 mg each) which undergo an endothermic reaction near 100 C. Because there was a limited amount of sample, an effort was made to get as much information as possible from each sample run. Standard XTX was used to check out the test before a sample of WSI was run.

Table 1. Analysis of the Atmosphere for PASS A IX-09 Samples

	N ₂ /O ₂ /CO ₂ (60/30/10)			N ₂ (100%)		
	Sample #7 mL @ STP	%	Sample #9 mL @ STP	%	Sample #13 mL @ STP	%
N ₂	92.90	75.56	46.37	58.44	46.32	59.75
O ₂	26.45	21.51	20.89	26.33	20.11	25.94
CO						
NO						
CO ₂	4.504	3.66	8.093	10.20	9.58	12.36
N ₂ O	0.319	0.26	1.884	2.37	0.48	0.62
Ar	1.09	0.89				
Acetone	1.777	1.45	0.326	0.42	0.312	0.40
H ₂	0.109	0.08				
H ₂ O	0.7497	0.61	0.352	0.44	0.67	0.86
Methanol	0.0104	0.008	0.096	0.12	0.001	0.001
Trichlorofluoromethane	0.0474	0.03	0.239	0.30	0.049	0.06
Dichlorodifluoromethane						
Total	122.950		78.250		77.52	
					79.3300	
					78.017	
					84.36	

and air used in this sample only to transfer H₂O. Therefore the efficiency was much greater.

Fig. 6. IR Spectrum of a low boiling
impurity removed from FEFO

The first DTA run was made to determine if our instrument could detect the endotherm, with some idea about its size, and to compare it with standard XTX. Figs. 7 and 8 show standard XTX and WCS-730. Both thermograms have a differential temperature (Δt) of 0.1 C/inch.

The second DTA run on WCS-730 was heated to 110 C, cooled and reheated, after which there was no indication of an endotherm.

Another sample was evacuated for five minutes at less than 10^{-4} torr, followed by a DTA to 115 C. The thermogram showed the endotherm, indicating that the vacuum did not remove the endotherm. Thus the same sample was then stored in a moist atmosphere for approximately one week, after which DTA thermograms showed no indication of an endotherm.

Another sample was run in the TGA. Since evacuation did not remove the endotherm, the TGA chamber was evacuated to 1 mm and then filled with helium. The sample was heated to 125 C and then cooled. The atmosphere in the TGA chamber was removed through a liquid nitrogen trap. Figs. 9 and 10 show the TGA thermograms of standard XTX and WSI-730. The WSI-730 sample does have a weight loss which indicates that a material was evolved.

Mass spectrometric analysis of the liquid nitrogen traps from standard XTX and WSI-730 show mostly water. Because of the large amounts of water it was impossible to detect any differences in the two samples.

HEAT OF FUSION OF PETN BY DSC-1

The heat of fusion (ΔH_f) of PETN is a function of the method of crystallization. Therefore, ΔH_f might be useful in the certification of PETN for XTX and LX-13.

A study is being made to determine the accuracy which ΔH_f can be measured using a Perkin-Elmer DSC-1 and the correlation of ΔH_f with the performance of XTX and LX-13.

Perkin-Elmer suggests the use of a planimeter to determine the area of the DSC-1 endotherms, but this method would make it very difficult, if not impossible, to get the desired accuracy. Two other methods currently available are: (1) a Datex DIR gas chromatography integrator, and (2) the Datex DIR as an analog-to-digital converter for a paper tape system.

The first system is undesirable because of the method used to correct the baseline drift. The integration (Fig. 11A) is started at point A and continues to point B. (This area is the shaded portion.) A better measurement of the area is shown in Fig. 11B.

The second method, which uses the Datex as an analog-to-digital converter, stores the digital data on paper tape. This system has three digitizing rates: 10, 1, and 0.1 seconds per point. The area of a curve would be the summation of digital value of each point on the curve and it is possible to make nearly any type of correction for the baseline.

Fig. 7. DTA of Extex Control Sample (11 C/min)

Fig. 8. DTA of Extex WSI-730 Sample (11 C/min)

Fig. 9. TGA of Extex Control Sample (5 C/min), Sample Weight 7.54 mg, (evaluated to 1 mm Hg and back-filled with 61.8 cm Hg of He).

Fig. 10. TGA of Extex WST-730 Sample (5 C/min), Sample Weight 8.41 mg, (evaluated to 1 mm Hg and back-filled with 62.4 cm Hg of He).

Fig. 11

Fig. 12

Methods of Integrating the PETN
Endotherms for the Determination
of the Heat of Fusion.

Table II

PETN

<u>Run No.</u>	<u>Sample Wt (mg)</u>	<u>Area (counts)</u>	<u>Counts/mg</u>	<u>% Variation from Average</u>
(1)	2.160	243,898	112,916	+ 1.5
(2)	1.937	219,012	113,068	+ 1.4
(3)	2.024	232,726	114,983	0.31
(4)	2.143	251,902	117,546	- 2.5

Avg. 114,628 c/mg

Indium

<u>Run No.</u>	<u>Sample Wt (mg)</u>	<u>Area (counts)</u>	<u>Counts/mg</u>	<u>% Variation from Average</u>
(1)	6.69	124,771	18,650	+ 0.80
(2)	6.69	124,279	18,577	+ 0.40
(3)	6.69	122,395	18,295	- 1.2
(4)	6.69	123,691	18,489	- 0.075

Avg. 18,502 c/mg

A Wang 700 desk calculator with a paper tape reader was available and a program was written to detect the slope change at point A (Fig. 11C) and sum the digital data and look for another slope change at B. The initial summation would represent the area of both shaded parts and the area of the trapezoid ABCD would be subtracted to give the area of the peak. Several runs on an indium standard and PETN were analyzed using this program. There was as much as 10% variation in the data.

Fig. 12 illustrates the reasons for the 10% variations. Points A' and B' were used as the starting and ending points. There are two reasons for this: there is some electrical noise on the baseline and the Wang did not have the necessary storage capacity, which limits the program's ability to determine point A.

A second program was written and used on the same runs. This program calculates the area in the same manner but it allows the operator to pick points A and B. Table II gives the results obtained with this technique.

These preliminary runs were made to check out the data acquisition system and analysis of the data. The next step will be refinement of the operating parameters to improve the accuracy. The effects of varying such parameters as the data collection rates, range setting, heating rates, and sample loading techniques will be investigated to determine the optimum operating conditions.

FUTURE WORK; COMMENTS; CONCLUSIONS

The six LX-09 skid test parts were removed from the oven after one year at 70 C. The parts were potted (DC 93-120) into aluminum hemispheres. Upon removal of the LX-09 from the aluminum shell, it was found that the 93-120 was reverting. One hemisphere was repotted without being cleaned up to determine if the DC 93-120 had been contaminated. The DC 93-120 cured with no problem. One of the six hemispheres was set aside for mechanical and chemical testing but it could not be used for mechanical testing due to the internal damage. However, samples were taken at various locations in the hemisphere and sent to LLL for analysis. Similar samples were retained at Pantex for thermal analysis. The thermal analysis of the LX-09 included DTA, TGA, pyrolysis, Henkin time-to-explosion, and chemical reactivity. There was no significant differences among any of the samples tested.

An analysis of the atmosphere in two more of the PASS A LX-09 mechanical test specimens was made. The results are in agreement with those reported last quarter.

The low boiling impurities in FEFC have been concentrated in a 50 mℓ sample by removing FEFC using a recrystallizing process suggested by LLL to purify FEFC. A pure sample of two of the low boilers was obtained using gas chromatography. An IR spectrum has been run on one of the samples, but an identification has not been made. An IR spectrum will be run on the other and mass spectra will be obtained for both samples in the near future. With this information it may be possible to identify these impurities.

Three small samples (~ 10 mg each) of XTX (WSI-730) were sent to Pantex to determine the origin of a small endotherm observed by DTA near 100 C. It has been determined that the endotherm does not reappear when the sample is cooled and reheated even if it is stored in a moist atmosphere for one week. The endotherm cannot be removed by evacuating the sample at 10^{-4} torr for 5 minutes. There is a weight loss associated with the endotherm but the material which is evolved has not been identified.

Some preliminary runs were made on PETN and indium to check out a data acquisition system and two data reduction techniques. The maximum variation in the PETN and indium data is 2.5% and 1.2%, respectively. It should be possible to reduce these variations by optimizing the operation parameters.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**