DE-92148-TOP-07

**DIRECT LIQUEFACTION PROOF OF CONCEPT FACILITY
Hydrocarbon Technologies, Inc., Lawrenceville, NJ**

Final

**Topical Report
POC Bench Run 05 (227-97)**

Work Performed Under Contract No. AC22-92PC92148

For

U.S. Department of Energy

Pittsburgh Energy Technology Center

Performed by

Hydrocarbon Technologies, Lawrenceville, NJ

MASTER

RECEIVED
USDOE/PETC
97 MAY 13 AM 9:17
EDUCATION & ASSISTANCE DIV.

**CLEARED BY
PATENT COUNSEL**

DOE/PC/92148--T6

DIRECT LIQUEFACTION PROOF-OF-CONCEPT PROGRAM
Hydrocarbon Technologies, Inc., Lawrenceville, N.J.

A.G. Comolli
V.R. Pradhan
T.L.K. Lee
W.F. Karolkiewicz
G. Popper

RECEIVED
JUL 07 1997
OSTI

FINAL

Topical Report
Bench Run 05 (227-97)

Work Performed Under Contract No. AC22-92PC92148

For

U.S. Department of Energy
Pittsburgh Energy Technology Center

MASTER

By

Hydrocarbon Technologies Inc., Lawrenceville, NJ,

PH
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

APRIL 1997

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DIRECT LIQUEFACTION PROOF-OF-CONCEPT PROGRAM
Hydrocarbon Technologies, Inc., Lawrenceville, N.J.

A.G. Comolli
V.R. Pradhan
T.L.K. Lee
W.F. Karolkiewicz
G. Popper

FINAL

Topical Report
Bench Run 05 (227-97)

Work Performed Under Contract No. AC22-92PC92148

For

U.S. Department of Energy
Pittsburgh Energy Technology Center

By

Hydrocarbon Technologies Inc., Lawrenceville, NJ,

APRIL 1997

TABLE OF CONTENTS

ABSTRACT	1
EXECUTIVE SUMMARY	2
BACKGROUND, OBJECTIVE, AND SCOPE OF WORK	3
SYSTEM CONFIGURATION	4
MATERIALS USED	5
Feeds	5
Startup/Makeup Oil	5
Catalysts	5
INTERSTAGE SLURRY SAMPLES	5
EXTERNAL SAMPLES	5
SUMMARY OF OPERATIONS	6
Startup Operations	6
Condition 1	6
Condition 2	6
Condition 3	6
Condition 4	7
Condition 5	7
Condition 6	7
Shutdown and Post Run Inspections	8
OPERATING CONDITIONS AND MATERIAL BALANCES	10
PROCESS PERFORMANCE RESULTS	10
Total Coal (mixed-feed) and 524°C ⁺ Residuum Conversion	10
C ₄ -524°C Distillate Yield and 524°C ⁺ Residuum Yield	11
Distillate Yield and Selectivity	11
Hydrogen Consumption and Light Gas (C ₁ -C ₃) Yield	11
Hydrogen Utilization	12

TABLE OF CONTENTS

(Continued)

PRODUCT QUALITY	13
Separator Overhead (SOH) Product	13
Pressure Filter Liquid (PFL) and Pressure Filter Solids (PFS)	13
Analysis of True Boiling Point (TBP) Fractions	14 ^{deleted 14.11}
DISCUSSION OF PROCESS PERFORMANCE RESULTS	15
Effect of Feed Type	15
Effect of Coal Rank/Type on Coprocessing	15
TECHNO-ECONOMIC ASSESSMENT	17
CONCLUSIONS	18
APPENDIX	54
Daily Unit Material Recovery Balance	

LIST OF TABLES

Table 1.	Run Plan for the Bench Run PB-05	19
Table 2.	Analysis of Feed Illinois No. 6 coal	20
Table 3.	Analyses of Heavy Oil, ASR, and Waste Plastics Feed	21
Table 4.	Analysis of Start-up/Make-up Oil	22
Table 5.	Process Performance Summary during PB-05	23
Table 6.	First Stage Separator Overhead (SOH) Properties	24
Table 7.	Second Stage Separator Overhead (SOH) Properties	25
Table 8.	Pressure Filter Liquid (PFL) Properties	26
Table 9.	Interstage PFL Properties	27
Table 10.	Interstage Pressure Filter Solids (PFS) Properties	28
Table 11.	Second Stage Pressure Filter Solids (PFS) Properties	29
Table 12.	Composite Feed Analysis	30
Table 13.	Material Balance for Economic Assessment	31
Table 14.	Hydrogen Balance, Utilities Production, and Thermal Efficiency	32
Table 15.	Liquefaction Plant Investment Details	33
Table 16.	Total Plant Investment Summary	34
Table 17.	Product Cost Calculation	35
Table 18.	Breakdown of Equivalent Crude Oil Price	36
Table 19.	Economic Comparisons at Maximum Reactor Throughput ...	37

LIST OF FIGURES

Figure 1.	Simplified Schematic of HTI's Bench-Scale Unit Configured for Run PB-05	38
Figure 2.	PB-05: Daily Operating Conditions	39
Figure 3.	PB-05: Daily Material Recovery Balance	40
Figure 4.	PB-05: Feed Composition	41
Figure 5.	PB-05: Feed and Resid Conversions	42
Figure 6.	PB-05: C ₄ -524°C Distillate Yield and 524°C ⁺ Yield	43
Figure 7.	PB-05: Distillate Fraction Yields	44
Figure 8.	PB-05: Distillate Fraction Selectivity	45
Figure 9.	PB-05: Hydrogen Consumption and Light C ₁ -C ₃ Gas Yield . . .	46
Figure 10.	PB-05: Hydrogen Efficiency and C ₁ -C ₃ Gas Selectivity	47
Figure 11.	PB-05: Quality of SOH Distillates	48
Figure 12.	PB-05: Product H/C Ratio	49
Figure 13.	PB-05: Solubility of PFL Product	50
Figure 14.	PB-05: Feed Type vs. Process Performance	51
Figure 15.	PB-05: Feed Type vs. Process Performance for Illinois No. 6 vs. Black Thunder mine coal	52
Figure 16.	Economics: Bituminous vs. Subbituminous Coals	53

ABSTRACT

This report presents the results Bench Run PB-05, conducted under the DOE Proof of Concept - Bench Option Program in direct coal liquefaction at Hydrocarbon Technologies, Inc. in Lawrenceville, New Jersey. Bench Run PB-05 was the fifth of the nine runs planned in the POC Bench Option Contract between the U.S. DOE and Hydrocarbon Technologies, Inc. Bench Run PB-05 had multiple goals. These included the evaluation of the effect of using dispersed slurry catalyst in direct liquefaction of a high volatile bituminous Illinois No. 6 coal and in combined coprocessing of coal with organic wastes, such as heavy petroleum resid, MSW plastics, and auto-shredder residue. PB-05 employed a two-stage, back-mixed, slurry reactor system with an interstage V/L separator and an in-line fixed-bed hydrotreater.

Coprocessing of waste plastics with Illinois No. 6 coal did not result in the improvement observed earlier with a subbituminous coal. In particular, decreases in light gas yield and hydrogen consumption were not observed with Illinois No. 6 coal as they were with Black Thunder Mine coal. The higher thermal severity during PB-05 is a possible reason for this discrepancy, plastics being more sensitive to temperatures (cracking) than either coal or heavy resid. The ASR material was poorer than MSW plastics in terms of increasing conversions and yields. HTI's new dispersed catalyst formulation, containing phosphorous-promoted iron gel, was highly effective for the direct liquefaction of Illinois No. 6 coal under the reaction conditions employed; over 95% coal conversion was obtained, along with over 85% residuum conversion and over 73% distillate yields.

EXECUTIVE SUMMARY

Bench Run PB-05 was the fifth of the nine runs planned in the POC Bench Option Contract between the U.S. DOE and Hydrocarbon Technologies, Inc. The primary goal of this bench run was to evaluate the direct liquefaction and coprocessing of a high volatile bituminous coal, (Illinois No.6), with organic wastes, such as MSW plastics (a mixture of HDPE, polypropylene, and polystyrene was used to simulate the MSW plastics), heavy resid, and auto-fluff. The unit was configured to have an interstage vapor-liquid separator and an in-line fixed-bed hydrotreating unit. The run consisted of 25 days of continuous operation, spanning six operating conditions. The effect of dispersed slurry catalyst activity and feed composition were evaluated at target operating conditions of reactor space velocity of 640 kg/h/m³ reactor and reactor temperatures of 449 and 460°C.

The first two reaction conditions were carried out using 'coal-only' feed, with the objective of studying the effect of 50 ppm molybdenum, added as Molyvan-A, in improving performance over use of only iron and phosphorous in the form of HTI's gel catalyst (as in Condition 1 of PB-05). Conditions 3 through 6 focused on the coprocessing of organic wastes with coal; Condition 3 studied the coprocessing of coal with MSW plastics and Hondo VTB oil; Conditions 4 and 5 studied the coprocessing of coal with MSW plastics and auto-fluff material; and Condition 6 looked at coal/oil coprocessing at 50/50 w/w% feed concentration. The run was carried out in an "ashy-recycle" mode of operation, achieved by recycling part of the flash vessel, (O-6), bottoms back to the first stage reactor. The in-line hydrotreater operation was very successful (except for the last run condition); SOH product with a high H/C ratio and low heteroatom content was obtained.

Following were the highlights of Bench Run PB-05:

- HTI's new dispersed catalyst formulation, containing phosphorous-promoted iron gel, was highly effective for the direct liquefaction of Illinois No. 6 coal under the reaction conditions employed; over 95% total coal conversion was obtained, along with over 85% residuum conversion and over 73% distillate yields.
- The addition of 50 ppm molybdenum, in the form of Molyvan-A, to HTI's Fe/P gel catalyst did not bring about any significant improvement in process performance. It appears that the presence of phosphorous masks the effect of the molybdenum additive.

- The coprocessing of equal amounts of coal, MSW plastics, and Hondo VTB resid resulted in improved performance, e.g., about 90% conversion of resid was obtained, along with 79% distillate yield and 3.9% chemical hydrogen consumption.
- Coprocessing waste plastics with Illinois No. 6 coal did not result in the improvement observed earlier with a subbituminous coal. In particular, reduced light gas yields and hydrogen consumption were not observed with Illinois No. 6 coal as was the case with Black Thunder Mine coal. The higher thermal severity during PB-05 could be the reason for this discrepancy, plastics being more sensitive to temperatures (cracking) than either coal or heavy resid. The ASR material was poorer than MSW plastics in terms of contributing to conversion and yields.
- The last run condition, which studied conventional coal/oil coprocessing with minimal recycle, resulted in the best performance, although material recovery balance for that condition was poor.

BACKGROUND, OBJECTIVE, AND SCOPE OF WORK

The POC Bench Option Project (PB-Series) is geared to evaluate different novel processing concepts in catalytic coal liquefaction and coprocessing of organic wastes, such as plastics, heavy resids, waste oils, and ligno-cellulose wastes, with coal. The long-term performance data at the bench scale of operations (30 kg/day) will be used eventually to complement the larger scale process demonstration "Proof-of-Concept" studies for the U.S. DOE. The new ideas being explored in this program include using novel dispersed slurry catalysts, combinations of dispersed and supported catalysts (hybrid mode), coprocessing of coal with waste plastics, low quality resids, waste oils, and ligno-cellulosic wastes, etc. Bench Run PB-05 was carried out for 25 operating days, spanning five process conditions (*Table 1*), to evaluate the effects of an all-dispersed catalyst system (iron and molybdenum based dispersed catalyst only in both reactor stages, K-1 and K-2), on the direct liquefaction of a bituminous Illinois No.6 coal and on the combined processing of Illinois No. 6 coal with waste plastics, heavy petroleum resid, and auto-fluff. The following were the primary objectives:

- To examine the effects of iron, molybdenum, and phosphorous-based dispersed slurry catalysts on the direct liquefaction of Illinois No. 6 coal, using a high-low two-stage temperature sequence, with interstage product separation and in-line distillate hydrotreating.
- To study the coprocessing of Illinois No. 6 coal with heavy petroleum resid, waste plastics, and auto-fluff in an "all-dispersed catalyst" two-stage hydroconversion reaction system.

SYSTEM CONFIGURATION

Bench Run PB-05 involved two equal volume back-mixed reactors with internal recirculation. No supported extrudate catalyst was employed in the hydroconversion reactors; only the in-line HTU treating the net product used 500 cc of Criterion C-411 catalyst. Direct liquefaction of coal and the coprocessing of vacuum resids, waste plastics, and auto-fluff with coal was studied using a coil preheater, interstage separation, and in-line hydrotreating of light products from both stages. The simplified schematic of the unit configuration is shown in *Figure 1*.

Unit 227 was used in this run. Coal, resid, auto-fluff (premixed with recycle PFL) and waste plastics were introduced through the feed system of Unit 227. Light products and gases from the first stage were removed from the interstage separator. After separating out the process water, the oil fraction was repressurized and combined with process knockouts and the second stage hot separator (O-1) overheads for feeding to the in-line hydrotreater. A slurry product was removed from the bottom of the hot separator. An off-line pressure filtration unit was used to recover a solids-free liquid (recycle solvent) from the slurry product. Two independent gas feed and discharge systems were required to handle the gas from the two-stage-interstage separation configuration.

MATERIALS USED

Feeds

Illinois No. 6 coal (HTI #6303) was used for PB-05 (227-97) Bench Run. Hondo VTB was the source of petroleum resid, while a 40/30/30 w/w/w% mixture of HDPE/PP/PS simulated the MSW co-mingled plastics, while ASR was used in the form of a pre-mixed with PFL. The analyses of these feedstocks are listed in *Tables 2 and 3*.

Start-up and Make-up Oil

L-814; analysis shown in *Table 4*.

Catalysts

Hydrotreater: Criterion C-411 Trilobe (HRI-6135)
K-1 & K-2 : HTI's phosphorous-modified iron catalyst and Molyvan-A, added to reactor K-1 by premixing with recycle PFL.

INTERSTAGE (Reactor K-1) SLURRY SAMPLES

Five interstage (reactor K-1) slurry samples, one for each condition, were collected. These samples were taken immediately after the completion of each of the work-up periods.

EXTERNAL SAMPLES

The following samples of different process streams were collected during work-up periods for Consol, Inc.

Feed Coal	100 g	Feed Slurry	200 g
O-6 Bottoms	300 g	First Stage Slurry	300 g
First Stage Overhead Oil	300 g	SOH Product	300 g
PFL	250 g	PFS	250 g

Five gallon SOH distillate samples were also collected for DOE/PETC during the HTU off-line conditions of PB-05.

SUMMARY OF OPERATIONS

Start-up Operations

The 500 cc of Criterion 411 catalyst (HTI-6292) that was charged to the hydrotreater had an outage before charging of 38 $\frac{3}{8}$ " and an outage after charging of 12 $\frac{3}{4}$ ".

The unit was mechanically complete and pressure checked for startup by 0500 hours August 6. Normal start-up commenced without incident. By August 8 the start-up was completed, and the unit was lined out and ready for run operations.

Condition 1 (Periods 1-5)

Condition 1 began at 0400 hours on August 8. The feed for the condition was a blend of 1384 g/hr of coal, 831 g/h of O-6 bottoms slurry, and 553 g/h of Pressure Filtered Liquid (PFL). 13.2 g/h of phosphoric enhanced iron catalyst was also part of the feed slurry. There were minor problems with the feed pumps, J-1 and J-2. Twice plugs developed in the feed lines that could not be cleared with high pressure. A pressure drop began to develop in the coil and in the first stage reactor (K-1) as early as Period 3. By the end of Condition 1 pressure drops in both the first (K-1) and second stage (K-2) were as high as 50 psi. The unit parameters were held until the end of the condition so as not to disturb the unit.

Condition 2 (Periods 6-9)

Condition 2, began at 0400 hours on August 13 with the addition of 0.23 g/h of Molyvan-A catalyst to the reactor feed. All other parameters remained the same. Due to a 300 psi pressure drop in the feed section (namely the coil), which started late in Condition 1, the unit was placed on wash at 1030 hours in subperiod 6A, (the condition transition period). The unit was back on-line by 1500 hours, before the end of subperiod 6A, with restrictions freed. During period 8, at 0600 hours the hydrotreater (HTU) was taken off-line for two hours so the HTU feed pump could be repacked. The hydrotreater was placed back on-line by 0800 hours without incident.

Condition 3 (Periods 10-13)

Condition 3 began at 0400 hours August 17 with the introduction of the plastics blend to the unit. The coal feed was lowered to 471 g/h, and Hondo oil was added to the

unit at 457 g/h. The plastics blend consisted of 183 g/h high density polyethylene (HDPE), 137 g/h Polypropylene (PP), and 137 g/h Polystyrene (PS). At 0800 hours during Period 11, the hydrotreater was taken off-line to obtain non-hydrotreated samples. The hydrotreater was returned to service at 1600 hours with the initiation of subperiod 12B. The unit ran smoothly throughout Condition 3.

Condition 4 (Periods 14-17)

Condition 4, commenced at the start of period 14 at 0400 hours on August 21. The Hondo oil feed was discontinued, and the plastics blend remained the same as in Condition 3. The coal feed rate was raised to 927 g/h, the O-6 bottoms slurry feedrate was raised to 996 g/h, and the pressure filter liquid feedrate was raised to 664 g/h. The viscosity of the feed rose to as high as 10,000 cps; in response the feed pot temperatures were raised from 425°F to 475°F in an effort to lower viscosity. The feed line temperatures were also raised incrementally. Viscosity, however, dropped only modestly. The high viscosity created no operational difficulties, and the unit continued smoothly.

Condition 5 (Periods 18-21)

Condition 5, began at 0400 hours on August 25. The feed composition changes included the introduction of Auto Shredder Residue (ASR) also called auto-fluff, at 229 g/h and a reduction of the plastics blend feed rate by exactly one half. Plastics feed was 92 g/h HDPE, 69 g/h PP, and 69 g/h PS. During Condition 5, the second stage left side buffer pump stopped on several occasions due to restrictions. The restrictions were cleared, pump checks were replaced, and the pump was placed back in service. Feed pump problems continued throughout the condition. During period 21 the hydrotreater plugged and could not be cleared. It was taken off-line for the remainder of the run.

Condition 6 (Periods 22-25)

Condition 6, began at 0400 hours on August 26. The four day condition experienced smooth operations feeding only three components, 692 g/h of coal, 692 g/h of Hondo oil, and 277 g/h of O-6 bottoms slurry.

Shut-down and Post Run Inspection

At 0400 hours on September 2 shut-down procedures were initiated as planned. Unit temperatures were lowered and the unit was washed as specified in the procedure.

Inspection of the unit after shutdown showed that the feedpot, P-2, was approximately half full of hard carbonaceous material. Five gallons of very heavy solids were removed from P-2. The circulation lines to P-2 were plugged. The preheater coil and the L/S buffer line both had plugs as well. The hydrotreater had to be rodded out to recover 684 g of catalyst. The hydrotreater catalyst was mostly black with some white pieces mixed in. Neither the first nor second stage bubble caps came out upon removal of the bottom heads and riser tubes. Both reactor top heads had to be cleaned by maintenance due to modest amounts of hard carbonaceous deposits. Both bottom heads were cleaned by operations to remove small amounts of hard carbonaceous material. The run chronology and statistics can be found in the following Tables. Run 227-98 had an online efficiency of 99.3% during the 25 day run.

RUN 227-97 OPERATIONS-STATUS-CLASSIFICATION CHRONOLOGY

Operations		Start		End		Duration.
Classification	I.D.	Time	Date	Time	Date	
	S/U	0500	8/6/96	0400	8/8	47
Cond. 1	1-5	0400	8/8	0400	8/13	120
Cond. 2	6	0400	8/13	1030	8/13	6.5
Wash		1030	8/13	1500	8/13	4.5
Cond. 2	6-9	1500	8/13	0400	8/17	85
Cond. 3	10-13	0400	8/17	0400	8/21	96
Cond. 4	14-17	0400	8/21	0400	8/25	96
Cond. 5	18-21	0400	8/25	0400	8/29	96
Cond. 6	22-25	0400	8/29	0400	9/2	96
	S/D	0400	9/2	1400	9/3	34

ON-LINE TIME AND DOWN TIME FOR RUN 227-97

<u>Time of S/U & S/D, Hours</u>	<u>Time of Inter- mediate S/U & S/D, Hours</u>	<u>Total On-Line Time, Hours</u>	<u>Down-Time, Hours</u>	<u>On-Line Efficiency, %</u>
81	4.5	681	4.5	99.2

Definitions

S/U = Startup. Time between gas flow initiation and feedstock cut-in during which unit temperatures and/or pressures are being increased.

S/D = Shutdown. Time between feedstock cut-out and liquid flow termination during which unit temperatures and/or pressures are being decreased.

On-Line Time. The sum of S/Us, S/Ds, and Run-Periods.

D/T = Down-Time. The time during which gases and liquids are not being charged to the unit. This is the same as the time between an intermediate shutdown and startup.

On-Line Efficiency = $\text{On-Line Time} / (\text{On-Line Time} + \text{Down-Time} + \text{Unfinished Run-Time.})$

OPERATING CONDITIONS AND MATERIAL RECOVERY BALANCES

Bench run operations were smooth and without any major problems. The overall material recovery balances were on the low side throughout Bench Run PB-05. An average material recovery balance (the daily material balance summary is attached in the Appendix) of about 94.5 W% was obtained (*Figure 3*) for the entire Bench Run PB-05. The operating summary and the process performance of individual periods during PB-05 are shown in *Table 5*. *Figure 2* shows feed space velocities and reactor temperatures during PB-05. As shown in *Figure 2*, the increased reactor temperatures during Conditions 1 through 5 were uniform while the space velocity fluctuated around an average value of 640 kg/h/m³. The feed composition, in terms of weight percents of different feedstocks, is shown in *Figure 4*.

PROCESS PERFORMANCE RESULTS

The conversions and yields of different products, process performance, and product quality for PB-05 are addressed in this Section. The calculation of daily material recovery balances, coal conversions, normalized product yields, and other process performance-related indicators was carried out using programs available in the microvax database. (Some programs were also modified as per the requirement of the process configuration for PB-05, for example, handling of three independent gas streams for material balance). Process performance during PB-05 is summarized in *Table 5*, depicted in *Figures 5 through 10*, and discussed in detail in the following sections.

Total Coal (mixed-feed) and 524°C+ Residuum Conversion

Typical coal (or mixed feed) conversions (based on the solubility of pressure filter solids in quinoline and expressed on an SO₃-free basis), obtained during equilibrated periods of different conditions of PB-05, are shown in *Figure 5*. Coal conversion (W% maf feed) varied between about 95.6 to 99% maf throughout the course of the run. Conversion was the highest for the condition studying the coprocessing of equal amounts of coal, Hondo resid, and MSW plastics. The conversion of 524°C+ residuum from coal is also plotted in *Figure 5*. Residuum conversion varied between about 82 to 90 W% (maf feed). For the operating conditions which processed either

coal alone or a mixture of coal and MSW plastic, the resid conversion was around 85 W% maf. Conversion increased to over 89 W% maf during Conditions 3 and 6 which processed the mixture of equal amounts of coal, Hondo resid, were MSW plastics and the mixture of equal amounts of coal and Hondo resid. During condition 5, which employed auto-fluff, resid conversion was the lowest of all, (81.6 W% maf). The addition of 50 ppm molybdenum as Molyvan-A during condition 2 did not have any major impact on coal and residuum conversions.

C₄-524°C Distillate and 524°C+ Residuum Yields

Distillate yields and 524°C+ residuum yields are shown in *Figure 6*. Distillate yields varied between 72 and 79 W% maf. The highest distillate yields of 79 W% maf were obtained during conditions 3 and 6, both coprocessing conditions. Distillate yields were around 73 W% maf for the first two 'coal only' conditions. The lowest distillate yield and the highest residuum yield were obtained during condition 5, in which part of the mixed MSW plastics were replaced by auto-fluff. Not much effect of the addition of 50 ppm molybdenum was observed in going from condition 1 to condition 2 of the 'coal only' operation.

Distillate Yield/Selectivity

The yields of distillate fractions, such as naphtha (IBP-177°C), middle distillates (177-343°C), and heavy distillates (343°C+), are shown in *Figure 7*. The numbers plotted in this figure, converted to a selectivity basis, are shown in *Figure 8*. Selectivities for different distillate fractions were similar for the first two condition. The addition of plastics to the feed mixture during conditions 3 and 5 increased selectivity to the lightest naphtha fraction. The addition of auto-fluff to the feed mixture during condition 5 reduced light fraction selectivity. The last run condition, condition 6, which studied the coprocessing of coal and Hondo resid, resulted in the highest selectivity/yield of the middle distillate fraction.

Hydrogen Consumption and Light Gas (C₁-C₃) Yield

Hydrogen consumption (*Figure 9*) based on maf coal (mixed feed) varied between 3.4 to 5.8 W%. In general, chemical hydrogen consumption during PB-05 tended to be on the low side, primarily because no supported catalyst was used and space velocities were high; thus, the operating severity was on the low side. Hydrogen consumption was low (<4 W% MAF) for conditions 3 and 6, which both used mixed

feeds containing mixed plastics and Hondo resid with coal. Light gas (C_1 - C_3) yields varied between 5.2 and 9.0 W% maf, with the highest gas yield during the coprocessing condition feeding (33% each of coal/Hondo/plastics) .

Hydrogen Utilization

Hydrogen utilization during coal conversion is characterized by two indicators: hydrogen efficiency and C_1 - C_3 gas selectivity. The former is defined as the amount of C_4 -524°C distillates obtained per unit weight of hydrogen consumed, while the latter is the amount of light hydrocarbon gases produced per unit weight of distillates. As shown in *Figure 10*, hydrogen efficiency varied between 12 to 24%. The lowest hydrogen efficiency of 12% was obtained when auto-fluff was used as part of the feed with coal and mixed plastics. The highest hydrogen efficiency and the lowest light gas selectivity (the most efficient hydrogen utilization) was obtained for the last run condition, condition 6, which studied the coprocessing of 50/50 w/w% coal and Hondo resid.

PRODUCT QUALITY

Different first-stage and second-stage product fractions (product gases, SOH, PFL, and PFS) from work-up periods 4, 9, 13, 17, 21, and 25 were analyzed in detail for their composition. These analyses fractions are listed in Tables 7 through 12.

Separator Overhead Product (SOH)

The SOH oil stream represents the net light distillate (IBP-343°C) from PB-05. While the hydrotreater unit was on-line (all the operating days except for Periods 20 through 25), the only major distillate stream out of the unit was the SOH stream, as the O-1 hot separator overheads, atmospheric flash overheads, first stage overhead oil, and the unit knockouts were being fed to the hydrotreater. The properties of SOH oil from both stages for the work-up periods are shown in *Tables 6 and 7*. The second stage SOH oils, which represent a major portion of the net process distillates, had a typical boiling range of 40-380°C. The API gravities were high (> 35), and the H/C atomic ratios were also high (> 1.70), especially during the operating periods when the HTU was online. Conditions 5 and 6, when the in-line HTU had to be by-passed due to plugging, produced a poorer quality SOH oil. The nitrogen and sulfur contents also increased significantly, as shown in *Figure 11*. The quality of the SOH process distillates (second stage), in terms of heteroatoms content and H/C ratios, is depicted in *Figures 11 and 12*. The first stage overhead oil, SOH, was understandably poorer in quality than the second stage overheads.

Pressure Filter Liquid (PFL) and Pressure Filter Solids (PFS)

The flash vessel (O-6) bottoms go through pressure filtrations for separation of solids from heavy liquid product and recycle oil. The liquid oil, called pressure filter liquid (PFL), is usually heavier than 343°C boiling point and contains unreacted heavy residuum material to a varying degrees. The solids from filtration, PFS, are oil-containing solids, normally extracted with toluene for oil recovery. The oil-free solids are then used for determining the extent of coal or total feed conversion based upon the solubility of the PFS material in a solvent such as quinoline. Detailed analyses of the PFL and PFS streams from PB-05 are listed in *Tables 8 through 11*. As shown in *Tables 8 and 9*, the PFL API gravity was low for most of the run conditions. The resid content of the second stage unit PFL varied between 29 and 36 W%, while resid in the interstage (first stage) PFL varied between 37 and 50 W%. In general, the asphaltene and the preasphaltene contents of the PFL from both reactor stages were

on the high side (*Figure 13*). The H/C ratios were higher for coprocessing conditions than for 'coal-only' conditions. As shown in *Tables 10 and 11*, the H/C ratios of the pressure filter solids (sampled and analyzed prior to extraction with toluene) were high (around 1.00) due to oil retention. The coal conversion, based upon the quinoline solubility of the pressure filter solids corrected to the ash content of feed coal, was around 96 W% maf throughout the run (almost all coal/feed conversion occurred in the first stage).

ANALYSIS OF PROCESS PERFORMANCE RESULTS

Effects of Feed Type

One of the primary objectives of Bench Run PB-05 was to study combined hydroconversion processing of mixed plastics, auto-fluff, and Hondo resid with a high volatile bituminous Illinois No. 6 coal. In previous runs, coprocessing of mixed feeds always resulted in better process performance than liquefaction of coal only. Distillate yields were higher for all of the coprocessing conditions, along with lower gas makes and mostly lower hydrogen consumptions, i.e., higher hydrogen efficiencies for coprocessing operations. The addition of plastics and Hondo resid, both separately and combined, had an overall positive effect on process performance, as shown in *Figure 14*. However, the addition of auto-fluff (ASR) had a negative impact on process performance, especially distillate yields and resid conversion, as shown in *Table 5*.

Effect of Coal Rank/Type on Coprocessing Performance

Coprocessing of waste plastics with Illinois No. 6 coal did not show the improvement observed earlier with a subbituminous coal. In particular the decrease in light gas yield and hydrogen consumption were not observed with Illinois No. 6 coal as was the case with Black Thunder mine coal. The higher reaction severity during PB-05 could be a reason for this discrepancy, plastics being more sensitive to temperature (cracking) than either coal or heavy resid.

It was well established during earlier HTI bench-scale runs that addition of mixed waste plastics improved overall hydrogen utilization in liquefaction of subbituminous Wyoming Black Thunder Mine coal. Mixed plastics addition at 25, 33, and 50 W% had resulted in an improved distillate yield and a lower light gas make. The hydrogen consumption was also lowered by the plastics addition. During PB-05, in which a high volatile bituminous Illinois No. 6 coal used, the effect of mixed plastics on distillate yields and quality was similar to that observed earlier with Black Thunder mine coal. There was an increase in distillate yield during the coal/plastics coprocessing operation compared to the 'coal only' case. However, surprisingly, the light C_1 - C_3 gas makes and hydrogen consumptions were not lower during the coal/plastics coprocessing operations than they were with the 'coal only' operation. This indicates that the effect of plastics on coal conversion is either coal-dependent or reaction severity-dependent or both. It should be noted that the overall thermal severity during

PB-05, feeding Illinois No. 6 coal, was about 20% higher than the earlier runs conducted using Black Thunder Mine coal. Also, as shown in *Figure 15*, the coprocessing of Hondo resid had much more of an impact with Illinois No. 6 coal than with Black Thunder coal.

TECHNO-ECONOMIC ASSESSMENT

Feed to Bench Run PB-05 was automobile shredder residue (ASR) in combination with Illinois coal, residual oil and plastics. The run featured an interstage separator and in-line hydrotreater and used dispersed iron and phosphorus catalysts. Recycle concluded topped separator bottoms containing solids.

Feed compositions are presented in *Table 12* for the periods analyzed in this assessment of the run. Reactor operating conditions were held nearly constant throughout the run as shown in *Table 13*, which also summarizes process performances and yields.

Table 14 presents material balances. Liquids production in coal-only operation was outstanding, even better than observed in PB-04. With residual oil coprocessing, liquids production increased, while with ASR coprocessing the liquid yield decreased. *Table 15* summarizes hydrogen balances, utilities production, and thermal efficiencies for the run conditions analyzed.

Liquefaction plant investment details, listed in *Table 16*, show little difference among the PB-05 run conditions except for Periods 21 and 25. Total plant investment costs are shown in *Table 17*. Coal-only operation investments are more than ten percent below those in PB-04. Use of ASR increases the investment cost slightly, but lowers the cost on a daily barrel cost basis.

Economics are summarized in *Table 18*, and the breakdown of the equivalent crude oil price is shown in *Table 19*. All the periods investigated showed better economics than with coal-only operation. The equivalent crude oil price for coal-only operation is almost \$30/B, even better than in PB-04. *Table 20* shows comparison of the economics of the cases at maximum reactor throughput. *Figure 16* compares economic results feeding subbituminous coal in PB-04 with bituminous coal in PB-05.

In summary, results of the technical assessment of PB-05 again show that use of Automobile Shredder Residue is economically justified when no charge is taken for this feed. The addition of phosphorus, as previously found, is economically beneficial, especially in coal-only operation. The use of oil and plastics is again shown economically attractive.

CONCLUSIONS

The following conclusions can be drawn based upon the data obtained from Bench Run PB-05:

- HTI's new dispersed catalyst formulation, containing phosphorous-promoted iron gel catalyst, was highly effective for the direct liquefaction of Illinois No. 6 coal under the reaction conditions employed; over 95% total coal conversion was obtained along with over 85% residuum conversion, and over 73% distillate yields.
- The addition of 50 ppm molybdenum, in the form of Molyvan-A, to HTI's Fe/P gel catalyst did not bring about any significant improvement in process performance. The presence of phosphorous appears to mask the effect of molybdenum.
- The coprocessing of equal amounts of coal, MSW plastics, and Hondo VTB resid resulted in improved performance, e.g., about 90% conversion of resid was obtained along with 79% distillate yield and 3.9% chemical hydrogen consumption.
- Coprocessing waste plastics with Illinois No. 6 coal did not bring about the improvement observed earlier with a subbituminous coal. In particular, decreases in light gas yield and hydrogen consumption were not observed with Illinois No. 6 coal as was the case with Black Thunder mine coal. The higher thermal severity during PB-05 could be the reason for this discrepancy, since plastics are more sensitive to temperatures (cracking) than either coal or heavy resid. The ASR material was poorer than MSW plastics in terms of contributing to conversions and yields.
- The last run condition, which studied conventional coal/oil coprocessing with minimal recycle resulted in the best performance, although material recovery balances for that condition were poor.

Table 1. Run Plan for Bench Run PB-05

Condition	1	2	3	4	5	6
Period Number	1-5	6-9	10-13	14-17	18-21	22-25
Work-Up Period	5	9	13	17	21	25
Dispersed Catalyst ppm						
Iron	1000	1000	1000	1000	1000	1000
Phosphorus	100	100	100	100	100	100
Molybdenum	0	50	50	50	50	50
Feed Composition, W%						
Coal	100	100	33	67	67	50
Plastics	0	0	33	33	16	0
Hondo Oil	0	0	33	0	0	50
ASR	0	0	0	0	17	0
Recycle Type	=====ASHY=====					
Recycle Ratio	1.0	1.0	1.0	1.0	1.0	0.20
Space Velocity, kg/h/m ³ react	640	640	690	640	640	710
Temperatures, °C						
K-1	449	449	449	449	449	449
K-2	460	460	460	460	460	460
In-line HTU	379	379	379	379	379	379

Table 2. Analysis of Illinois No. 6 Feed Coal

HTI Designation	HTI 6157
Moisture Content, W%	3.39
Proximate Analysis, W% Dry	
Volatile Matter	49.86
Fixed Carbon	57.95
Mineral Matter	10.03
Ultimate Analysis, W% Dry	
Carbon	71.20
Hydrogen	5.25
Nitrogen	1.42
Sulfur	4.02
Ash	10.24
Oxygen (Diff.)	7.87
H/C Atomic Ratio	0.885

Table 3. Analysis of Heavy Oil, ASR, and Waste Plastics Feed

Feed Type	Hondo VTB Resid	ASR	Waste Plastics
Gravity, °API	6.2	N/A	N/A
524°C+ Resid Content, V%	82.0	100	N/A
Ultimate Analysis, W% Dry			
Carbon	83.84	48.87	80.51
Hydrogen	10.13	3.83	11.42
Nitrogen	0.90	3.60	0.00
Sulfur	4.39	0.72	0.21
Oxygen	0.59	23.32	6.06
Ash	0.15	19.68	1.64
Chlorine	N/A		0.16

Table 4. Analysis of Start-up/Make-up Oil

HTI Designation	Filtered L-814
Gravity, °API	0.40
ASTM D-1160 Distillation, °C	
IBP	309
5 V%	351
10 V%	374
20 V%	394
30 V%	409
40 V%	426
50 V%	437
60 V%	449
70 V%	467
80 V%	507
84 V%	524
Weight Percents	
IBP-343°C	5.47
343-454°C	53.99
454-524°C	22.18
524°C ⁺	18.36
Elemental Analysis, W%	
Carbon	88.96
Hydrogen	8.25
Sulfur	2.22
Nitrogen	0.19
NMR Data	
W% Aromatic Carbon	88.03
W% Cyclic Hydrogen	44.36

Table 5. PB-05: Process Performance Summary

DATE	08/11/96	08/16/96	08/20/96	08/24/96	08/28/96	09/01/96
Condition	1	2	3	4	5	6
Period Number	4	9	13	17	21	25

PROCESS CONDITIONS

Space Velocity, mlf fresh feed / reactor volume

K-1 (kg/h/m ³)	617	677	579	669	758	593
K-2 (kg/h/m ³)	617	677	579	669	758	593

Reactor Temperatures, °C

K-1	444	447	447	447	448	447
K-2	454	458	457	458	458	457

Feed Composition, W%

Coal(III. No. 6 Crown II Mine)	100	100	33	67	67	50
Hondo VTB Oil	0	0	33	0	0	50
ASR	0	0	0	0	16	0
MSW Waste Plastics	0	0	33	33	17	0

Dispersed Catalyst Loading,ppm

Iron	1000	1000	1000	1000	1000	1000
Molybdenum	0	50	50	50	50	50
Phosphorous	100	100	100	100	100	100

NET NORMALIZED YIELDS, W% maf fresh feed

C ₁ -C ₃ in Gases	7.23	6.74	9.00	8.23	7.09	5.19
C ₄ -C ₇ in Gases	2.33	2.17	5.06	4.51	2.65	2.29
IBP-177°C (IBP-350°F)	16.90	16.23	27.63	25.21	17.63	15.06
177-260°C (350-500°F)	16.53	15.96	13.84	10.72	12.97	23.84
260-343°C (500-650°F)	16.05	16.31	14.49	12.30	12.46	18.73
343-454°C (650-850°F)	17.00	17.12	13.34	15.77	20.20	14.49
454-524°C (850-975°F)	4.35	5.58	4.47	6.05	6.49	4.63
524°C+ (975+°F)	10.25	10.97	9.53	12.83	14.59	8.68
Unconverted Feed	4.44	3.78	0.91	2.91	3.81	2.29
Water by Forced Oxygen Bal.	4.16	4.27	1.88	3.02	3.26	2.83
CO _x	1.56	1.45	0.85	1.08	1.08	0.63
NH ₃	1.40	1.34	0.61	0.79	1.08	0.76
H ₂ S	3.32	3.33	2.29	2.01	2.52	3.91

PROCESS PERFORMANCE, W% maf fresh feed

Material Recovery Balance	101.08	97.91	94.48	95.62	97.35	91.67
Hydrogen Consumption	5.52	5.23	3.90	5.43	5.80	3.37
Total Feed Conversion						
(SO ₃ Free)	95.6	96.2	99.1	97.1	96.2	97.7
524°C+ Conversion	85.3	85.3	89.6	84.3	81.6	89.0
C ₄ -524°C Distillates	73.2	73.4	78.8	74.6	72.4	79.1

Table 6. First Stage Separator Overhead (SOH) Properties**(Composite Sample)**

Condition	1	2	3	4	5	6
Period	4	9	13	17	21	25
Gravity, ° API	20.3	15.1	30.9	No Sample Available	27.5	30.2
IBP, ° C	66	82	58		63	61
FBP, ° C	387	388	390		397	404
Elemental Analysis						
Carbon, W%	84.22	84.57	86.56		85.68	84.67
Hydrogen, W%	10.13	9.58	11.21		10.96	11.76
Sulfur (Antek), ppm	2112.2	2033.7	1853.0		1917.5	7179.0
Nitrogen (Antek), ppm	2394.5	1731.8	1695.8		2512.4	11600
H/C Ratio	1.44	1.36	1.55		1.54	1.67
ASTM D-86 Distillation, W%						
IBP-177°C	18.0	8.1	44.1		33.7	21.94
177-260°C	42.8	38.8	17.2		21.5	32.91
260-343°C	27.1	36.8	25.1		28.1	30.51
343°C+	11.2	16.0	12.4		15.6	14.29
Loss	0.8	0.3	1.2		1.1	0.35

Table 7. Second Stage Separator Overhead (SOH) Properties

(Composite Sample)

Condition	1	2	3	4	5	6
Period	4	9	13	17	21	25
Gravity, ° API	36.3	34.6	41.7	40.6	36.1	33.2
IBP, °C	41	48	58	42	54	57
FBP, °C	362	367	371	373	386	364
Elemental Analysis						
Carbon, W%	86.91	87.27	87.02	87.11	85.85	85.55
Hydrogen, W%	12.58	12.42	12.94	12.65	11.91	11.85
Sulfur (Antek), ppm	98.14	159	94.23	84.5	1613.7	4724.5
Nitrogen (Antek), ppm	2.82	44.43	4.00	3.40	1849.7	11000
H/C Ratio	1.74	1.71	1.78	1.74	1.66	1.66
ASTM D-86 Distillation, W%						
IBP-177°C	34.0	34.2	46.8	51.7	40.5	26.63
177-260°C	31.0	29.3	22.3	19.2	25.2	39.07
260-343°C	27.3	29.3	22.8	21.4	23.6	28.26
343°C+	5.8	6.1	5.9	6.4	9.9	5.58
Loss	1.9	1.1	2.2	1.3	0.8	0.46

Table 8. Pressure Filter Liquid (PFL) Properties

(Composite Sample)

Condition	1	2	3	4	5	6
Period	4	9	13	17	21	25
Gravity, °API	-6.4	-8.5	0.1	7.0	-3.2	-0.4
IBP, °C	219	229	243	241	239	229
Elemental Analysis, W%						
Carbon	88.56	88.97	88.23	87.87	88.33	88.27
Hydrogen	6.59	6.73	8.77	9.96	9.76	8.21
Sulfur	1.50	1.19	1.43	1.00	0.826	1.07
Nitrogen	1.06	1.15	1.07	0.89	0.62	1.41
H/C Ratio	0.89	0.91	1.19	1.36	1.33	1.12
ASTM D-1160 Distillation, W%						
IBP-343°C	14.24	14.00	9.67	9.78	9.79	16.67
343-454°C	42.09	35.91	37.40	36.20	38.35	38.24
454-524°C	12.82	14.35	16.74	17.22	15.59	15.56
524°C+	30.32	35.13	35.81	36.50	35.72	29.26
Loss	0.53	0.61	0.38	0.30	0.55	0.27
Cyclohexane Insolubles	82.28	88.5	66.34	60.46	74.57	70.16
Toluene Insolubles	21.17	17.7	29.51	29.78	20.87	14.00

Table 9. Pressure Filter Liquid (PFL) Properties

(Interstage Sample)

Condition	1	2	3	4	5	6
Period	5	9	13	17	21	25
Gravity, °API	-6.1	-9.3	-2.2	-4.8	-3.0	-2.3
IBP, °C	231	232	250	274	242	250
Elemental Analysis, W%						
Carbon	88.68	87.68	87.68	87.97	88.36	86.84
Hydrogen	6.95	6.76	8.07	8.04	7.96	8.29
Sulfur	1.29	1.43	1.54	0.94	0.92	1.52
Nitrogen	1.20	1.19	1.06	1.05	1.07	1.35
H/C Ratio	0.94	0.93	1.10	1.10	1.08	1.15
ASTM D-1160 Distillation, W%						
IBP-343°C	13.21	10.09	5.15	5.52	9.08	8.13
343-454°C	31.91	32.16	30.93	27.46	37.24	26.13
454-524°C	13.92	13.97	16.29	16.12	15.62	18.13
524°C+	40.07	43.62	47.11	50.15	37.60	47.50
Loss	0.89	0.16	0.52	0.75	0.46	0.11
Cyclohexane Insolubles		87.63	68.14	74.78	54.19	39.86
Toluene Insolubles		26.71	23.14	28.73	19.40	9.87

Table 10. First Stage Pressure Filter Solid (PFS) Properties

(Composite Sample)

Condition	1	2	3	4	5	6
Period	4	9	13	17	21	25
Elemental Analysis, W%						
Carbon	43.39	42.09	40.81	38.15	36.97	43.99
Hydrogen	2.95	2.79	3.03	2.86	2.87	3.59
Sulfur	5.11	5.01	5.72	5.34	7.09	5.13
Nitrogen	0.59	0.66	0.58	0.51	0.52	0.70
H/C Ratio	0.82	0.80	0.89	0.90	0.93	0.98
Composition, W%						
Quinoline Insolubles	62.00	63.5	67.35	66.96	70.54	56.44
Ash (in Quinoline Filt.)	47.39	47.39	49.44	50.78	55.16	42.81
Sulfur in Ash	1.94	2.13	2.30	2.76	2.95	2.08
ASTM Ash	47.65	48.02	49.75	50.59	54.97	44.92
Sulfur in Ash	1.82	2.13	2.43	2.80	2.83	1.13
Coal Conversion,						
W% MAF	96.43	96.07	95.74	95.98	96.34	96.51

Table 11. Second Stage Pressure Filter Solid (PFS) Properties

(Composite Sample)

Condition	1	2	3	4	5	6
Period	4	9	13	17	21	25
Elemental Analysis, W%						
Carbon	46.97	44.98	41.02	40.80	42.52	48.58
Hydrogen	3.21	3.06	3.09	3.24	3.12	3.99
Sulfur	4.56	4.55	4.95	5.44	5.26	4.46
Nitrogen	0.53	0.61	0.62	0.57	0.51	0.71
H/C Ratio	0.82	0.82	0.90	0.95	0.88	0.99
Composition, W%						
Quinoline Insolubles	58.33	59.70	68.9	66.41	63.49	56.70
Ash (in Quinoline Filt.)	44.08	45.79	49.66	48.54	47.32	41.66
Sulfur in Ash	1.77	1.56	1.45	1.53	2.62	2.18
ASTM Ash	44.38	46.27	50.84	48.69	47.75	40.82
Sulfur in Ash	1.43	0.965	1.44	0.591	1.64	1.50
Coal Conversion,						
W% MAF	96.37	96.66	95.88	96.05	95.96	95.77

Table 12. Composite Feed Analysis

	<u>Period</u> <u>4</u>	<u>Period</u> <u>9</u>	<u>Period</u> <u>13</u>	<u>Period</u> <u>17</u>	<u>Period</u> <u>21</u>	<u>Period</u> <u>25</u>
<u>Feed Composition, W%</u>						
Coal	100.00	100.00	33.33	67.00	67.00	50.00
Oil	0.00	0.00	33.33	0.00	0.00	50.00
Auto Shredder	0.00	0.00	0.00	0.00	16.00	0.00
Residue						
Plastics	0.00	0.00	33.33	33.00	17.00	0.00
TOTAL	100.00	100.00	100.00	100.00	100.00	100.00
<u>Ultimate Analysis, W%</u>						
Carbon	71.20	71.20	78.52	74.27	69.21	77.52
Hydrogen	5.25	5.25	8.93	7.29	6.07	7.69
Nitrogen	1.42	1.42	0.77	0.95	1.53	1.16
Sulfur	4.02	4.02	2.87	2.76	2.84	4.21
Oxygen	7.87	7.87	4.89	7.33	10.06	4.23
Ash	10.24	10.24	4.01	7.40	10.29	5.20
TOTAL	100.00	100.00	100.00	100.00	100.00	100.00
Heating Value, BTU/lb	13,290	13,290	16,863	15,011	13,294	16,043

Table 13. Material Balance For A Feedrate of 12,000T/D

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/pl	coal/plastics	coal/ASR/pl	Coal/.oil
<u>Feed</u>						
Coal, T/D	12,000	12,000	4,000	8,040	8,040	6,000
Oil, B/D	0	0	22,243	0	0	33,365
Auto Shredder Residue, T/D	0	0	0	0	1,920	0
Plastics, T/D	0	0	4,000	3,960	2,040	0
Total, T/D	12,000	12,000	12,000	12,000	12,000	12,000
<u>Liquid Products, B/D</u>						
Gasoline	14,564	14,417	16,201	14,354	13,645	16,655
Diesel Fuel	35,369	35,014	39,346	34,860	33,137	40,446
Total	49,933	49,431	55,547	49,214	46,782	57,101
Barrels of Product/Ton Feed	4.16	4.12	4.63	4.10	3.90	4.76
<u>By-products</u>						
Propane, B/D	2,702	2,526	3,378	3,670	3,646	2,509
Butane, B/D	1,880	1,757	3,989	3,247	1,924	2,161
Sulfur, T/D	413	402	274	257	278	439
Ammonia, T/D	152	146	70	88	117	87
Waste to disposal, T/D	1,505	1,493	631	1,200	3,657	708

Table 14. Hydrogen Balance, Utilities & Thermal Efficiency

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/p	coal/plas	coal/AS	coal/oil
Hydrogen Balance						
<u>Hydrogen Consumption, MMSCFD</u>						
Liquefaction	269.6	258.3	176.6	251.7	282.8	154.6
Product Upgrading	16.8	26.0	0.2	-32.0	-36.3	50.3
Solution & Purge losses	9.9	9.2	11.0	10.2	8.1	6.6
Total	296.3	293.5	187.8	229.9	254.6	211.5
<u>Hydrogen Production, MMSCFD</u>						
Partial Oxidation	142.4	157.9	132.3	181.8	190.6	139.2
Steam Reforming	153.9	135.6	55.5	48.1	64.0	72.3
Total	296.3	293.5	187.8	229.9	254.6	211.5
Utilities Purchased or Produced						
Power, MW	221	221	185	224	227	168
Steam (600 psig) 1000 lb/hr	357	310	341	208	223	339
Cooling water, 1000 GPM	194	185	169	154	158	173
Purchased Natural Gas, MMMBTU/D	88	82	50	52	49	52
Raw water, 1000 Gal/D	9,136	8,853	8,829	8,107	8,267	8,884
Utilities Purchased or Produced						
<u>Inputs, MMMBTU/Day</u>						
Feed	319.0	319.0	404.7	360.3	319.0	385.0
Natural Gas	88.0	81.6	49.6	52.4	49.4	52.5
Total	407.0	400.6	454.3	412.7	368.4	437.5
<u>Outputs, MMMBTU/Day</u>						
Gasoline	81.5	80.7	90.7	80.3	76.3	93.2
Diesel Fuel	205.4	203.4	228.6	202.5	192.4	235.0
Propane & Butane	18.6	17.4	30.4	28.3	22.4	19.1
Sulfur & Ammonia	6.6	6.4	3.8	4.0	4.8	5.6
Total	312.1	307.9	353.5	315.1	295.9	352.9
Thermal Efficiency, %	76.7	76.9	77.8	76.4	80.3	80.7

Table 15. Liquefaction Plant Investment Details

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/pl	coal/plastic	coal/ASR/p	coal/oil
<u>Major Equipment Cost, \$M</u>						
Pumps	24,282	24,331	23,483	24,924	21,800	18,693
Reactors & Hydrotreater	46,380	44,090	48,084	44,649	39,945	42,746
Fired heaters	13,095	13,480	13,375	15,046	12,289	8,042
Exchangers	21,152	21,113	21,267	21,851	19,585	16,589
Drums	31,023	31,062	31,441	32,133	29,882	24,314
Towers	8,609	8,685	8,442	8,826	8,051	6,378
Compressors	33,840	33,284	28,835	33,127	34,648	25,931
HPU	16,200	15,277	17,436	16,491	14,129	12,144
Total	194,581	191,322	192,363	197,047	180,329	154,837
<u>Plant Investment, \$MM</u>						
Materials & Equipment	352.6	346.6	348.5	357.0	326.7	280.5
Labor & Subcontracts	152.5	150.0	150.8	154.5	141.4	121.4
Indirects	126.9	124.8	125.5	128.5	117.6	101.0
Total	632.0	621.4	624.8	640.0	585.7	502.9

Table 16. Total Plant Investment Summary

(Plant Investment in \$MM, 1994 US Gulf Coast Basis)

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/p	coal/plas	coal/AS	coal/oil
			I	tics	R/pl	
Coal Preparation	57.6	57.6	23.9	41.8	41.8	33.1
Oil Storage & Handling	0.0	0.0	22.5	0.0	0.0	29.9
Auto Shredder Residue Prep'n	0.0	0.0	0.0	0.0	17.2	0.0
Plastics Preparation	0.0	0.0	16.8	16.6	9.8	0.0
Liquefaction	632.0	621.4	624.8	640.0	585.7	502.9
Hydrogen Manufacture	268.7	266.0	187.3	212.8	231.7	205.9
Oxygen Plant	69.4	74.6	65.9	82.2	84.8	68.4
Treating	276.0	265.4	302.9	282.4	260.1	239.2
Product Upgrading	108.5	105.3	99.3	106.0	104.1	105.4
Utilities	332.6	309.0	315.2	285.9	289.5	311.6
Tankage, Waste Handling	167.5	166.1	172.6	162.8	176.4	177.4
General Offsites	211.0	211.0	211.0	211.0	211.0	211.0
Subtotal	2,123.3	2,076.4	2,042.2	2,041.5	2,012.1	1,884.8
Contingency & Fee	424.1	414.7	408.0	407.9	402.1	376.4
Total Plant Investment	2,547.4	2,491.1	2,450.2	2,449.4	2,414.2	2,261.2
\$/BPSD of Product	51,016	50,396	44,110	49,770	51,605	39,600

Table 17. Product Cost Calculation

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/pl	coal/plasti cs	coal/ASR/ pl	coal/oil
<u>Operating Costs, \$MM/yr</u>						
Coal, as received (\$20.50/Ton)	89.79	89.79	29.93	60.16	60.16	44.90
Oil (\$8.00/B)	0.00	0.00	58.46	0.00	0.00	87.68
Auto Shredder Residue (no cost)	0.00	0.00	0.00	0.00	0.00	0.00
Plastics (no cost)	0.00	0.00	0.00	0.00	0.00	0.00
Natural Gas (\$2.00/MMBTU)	57.82	53.58	32.57	34.43	32.45	34.48
River Water (\$0.10/Mgal)	0.30	0.29	0.29	0.27	0.27	0.29
Waste Disposal (\$5.00/Ton)	2.47	2.45	1.04	1.97	6.01	1.16
Catalysts & Chemicals	13.49	12.43	7.63	7.18	8.18	8.92
Dispersed Catalyst	6.35	6.35	6.35	6.35	6.35	6.35
Labor	23.07	23.07	23.71	23.39	23.71	23.39
Maintenance	20.67	20.67	21.24	20.95	21.24	20.95
Capital-related costs	384.10	375.98	373.43	370.05	363.95	347.87
Total	598.06	584.61	554.65	524.75	522.32	575.99
<u>By-product Credits, \$MM/yr</u>						
Propane (\$12.50/B)	11.10	10.37	13.87	15.07	14.97	10.30
Butane (\$14.50/B)	8.95	8.37	19.00	15.47	9.16	10.29
Sulfur (\$52.00/Ton)	7.05	6.87	4.68	4.40	4.75	7.50
Ammonia (\$120.00/Ton)	6.01	5.75	2.77	3.48	4.63	3.42
Total	33.11	31.36	40.32	38.42	33.51	31.51
Net Product cost, \$MM/year	564.95	553.25	514.33	486.33	488.81	544.48
, \$/B	34.44	34.07	28.19	30.08	31.81	29.03
Equivalent Crude Oil Price, \$/B	28.38	28.02	22.43	24.20	25.83	23.21

Table 18. Breakdown of Equivalent Crude Oil Price

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/p I	coal/plas tics	coal/AS R/pl	coal/oil
<u>Contribution to Price, \$/B</u>						
Coal	4.51	4.55	1.31	2.99	3.18	1.91
Oil	0.00	0.00	2.55	0.00	0.00	3.74
Auto Shredder Residue	0.00	0.00	0.00	0.00	0.00	0.00
Plastics	0.00	0.00	0.00	0.00	0.00	0.00
Natural Gas	2.90	2.71	1.42	1.71	1.71	1.47
River Water	0.02	0.01	0.01	0.01	0.01	0.01
Waste Disposal	0.12	0.12	0.04	0.10	0.32	0.05
Catalysts & Chemicals	0.68	0.63	0.33	0.36	0.43	0.38
Dispersed Catalyst	0.32	0.32	0.28	0.32	0.34	0.27
Labor	1.16	1.17	1.03	1.16	1.25	1.00
Maintenance	1.04	1.05	0.93	1.04	1.12	0.89
Capital-related costs	19.29	19.04	16.29	18.42	19.24	14.83
By-product credits	-1.66	-1.58	-1.76	-1.91	-1.77	-1.34
Equivalent Crude Oil Price, \$/B	28.38	28.02	22.43	24.20	25.83	23.21

Table 19. Comparison of Cases at Maximum Reactor Throughput

	<u>Period 4</u>	<u>Period 9</u>	<u>Period 13</u>	<u>Period 17</u>	<u>Period 21</u>	<u>Period 25</u>
	coal	coal	coal/oil/pl	coal/plasti cs	coal/ASR/ pl	coal/oil
Total Feed to Liquefaction, T/D	12,000	12,000	12,000	12,000	12,940	15,188
Number of Liquefaction Trains	4	4	4	4	4	4
Total Liquid Product, B/D	49,933	49,431	55,547	49,214	50,432	72,220
Liquefaction Plant Cost, \$MM	632.0	621.4	624.8	640.0	620.6	603.6
Total Plant Investment, \$MM	2,547.4	2,491.1	2,450.2	2,449.4	2,550.8	2,702.6
Net Operating Cost, \$MM/year	565.0	553.3	514.3	486.3	515.9	654.8
, \$/B	34.44	34.07	28.19	30.08	31.14	27.60
Equivalent Crude Oil Price, \$/B	28.38	28.02	22.43	24.20	25.20	21.89

Figure 1. Simplified Schematic of HTI's Bench Unit Configured for Run PB-05

Figure 2. PB-05: Daily Operating Conditions

Figure 3. PB-05: Daily Material Recovery Balance

Figure 4. PB-05: Feed Composition

Figure 5. PB-05: Feed and Residuum Conversions

Figure 6. PB-05: C₄-524°C Distillate Yield and 524°C Residuum Yield

Figure 7. PB-05: Distillate Fraction Yield

Figure 8. PB-05: Distillate Fraction Selectivity

Figure 9. PB-05: Hydrogen Consumption and Light C₁-C₃ Gas Yield

Figure 10. PB-05: Hydrogen Efficiency and C₁-C₃ Gas Selectivity

Figure 11. PB-05: Quality of SOH Distillates

Figure 12. PB-05: Product H/C Ratios

Figure 13. PB-05: Solubility of PFL Product

Figure 14. PB-05: Effect of Feed Type vs. Process Performance

Figure 15. PB-05: Effect of Feed Type on Process Performance: Illinois No. 6 Coal vs. Black Thunder mine Coal

Figure 16. PB-05: Economics of Bituminous vs. Subbituminous Coals

APPENDIX [Daily Material Recovery Balance Data]

The material balance summary and the analysis of product gas streams are listed in appendix. The material balance summary lists all the input streams to the unit, including recycle, and all the output streams, along with the material recovery balance (page 1). The temperatures of various fractionators and separators and pressure filtration data are summarized on page 2. The hourly feed, recycle, and product stream rates are summarized on page 3, while the yield of product stream, based upon W% moisture-free feed, are listed on page 4. The GC analyses of vent and bottom gases is summarized on page 5. The PFL fed to the buffer includes the PFL material pumped to the ebullating pump hot checks. The normalized yields of individual light gases are also included in the appendix.

T-96 15:59

RUN 227-97 (POC PB-05) MATERIAL BALANCE

Illinois Coal-Waste Coprocessing using Dispersed Slurry Catalysts

FEED: Illinois No. 6 Crown II Mine: POC-01 COAL (HTI-6303)

Hondo VTB Oil and Waste Plastics

CATALYSTS: HTI'S Iron GelCat (1000 ppm Fe/100 ppm P)

id Number	01T	02T	03T	04T	05T
(Start of Period)	08/08/96	08/09/96	08/10/96	08/11/96	08/12/96
ion, hrs	24.	24.	24.	24.	24.
of Run (End of Period)	24.	48.	72.	96.	120.

S, GRAMS

total Feed	27143.0	29305.0	33352.0	30621.0	36673.0
akeup Oil to Charge (L-814/extracted oil)	0.0	803.0	4662.0	0.0	1182.0
akeup Oil to Buffer (L-814/extracted oil)	0.0	5739.0	0.0	0.0	0.0
fl Recycled to Charge+K-2 Cat Addition	22236.0	9416.0	10569.0	12235.0	13471.0
AS Btms Recycled to Charge	13607.0	13490.0	18121.0	18385.0	22020.0
ilter Cake Recycled to Charge	0.0	0.0	0.0	0.0	0.0
fl to Stage 1 Buffer	761.0	864.0	827.0	5041.0	2733.0
fl to Stage 2 Buffer	744.0	846.0	1038.0	3307.0	833.0
ater to Hot Separators	10627.0	8778.0	10183.0	9998.0	9057.0
otal Sulfur Added	1016.3	976.2	995.0	920.0	1042.2
dditive (Fe/P+Mo Catalysts)	299.4	279.5	318.1	292.1	349.8
2 to 1st Stage	4638.7	4642.9	4625.1	4637.6	4630.0
2 to 2nd Stage	2057.7	2057.8	2057.8	2058.8	2058.8
ydrogen Bleed	678.6	694.8	694.8	695.2	695.1
OTAL GRAMS IN	83808.6	77892.1	87442.8	88190.6	94744.9

TS, GRAMS

ydrogen Out	4357.4	4055.0	3717.2	3806.5	3654.4
otal Gas Product (N2,H2 Free)	3305.4	4295.2	4316.5	4483.9	5037.2
nit Knockouts	37.0	65.0	41.0	44.0	52.0
eparator Overhead (HTU) Product	22178.0	20888.0	24696.0	26135.0	24450.0
tmospheric Overhead Product (Sample)	0.0	0.0	0.0	0.0	0.0
AS Bottoms	50084.0	36269.0	48241.0	54675.0	49359.0
eed + Interstage Slurry Sample	0.0	0.0	0.0	0.0	0.0
OTAL GRAMS OUT	79961.9	65572.1	81011.6	89144.4	82552.5

Total Material Recovery (Gross)	95.41	84.18	92.65	101.08	87.13
---------------------------------	-------	-------	-------	--------	-------

id Number	01T	02T	03T	04T	05T
CHARGE, PRODUCT, AND RECYCLE RATES-----					
D RATES, GRAMS/HOUR					

total Carbonaceous Feed	1131.0	1221.0	1389.7	1275.9	1528.0
ry Carbonaceous Feed	1092.6	1179.6	1342.6	1232.6	1476.2
total Makeup Oil Rate	0.0	272.6	194.3	0.0	49.3
water to Hot Separator	442.8	365.8	424.3	416.6	377.4
2 to 1st Stage	193.3	193.5	192.7	193.2	192.9
2 to 2nd Stage	85.7	85.7	85.7	85.8	85.8
CYCLE RATES TO REACTOR, GRAMS/HOUR					

FL Recycled to Slurry + Pretreater Buffer	926.5	392.3	440.4	509.8	561.3
CAS Bottoms Recycled	567.0	562.1	755.0	766.0	917.5
fl to 1st Stage Buffer	31.7	36.0	34.5	210.0	113.9
fl to 2nd Stage Buffer	31.0	35.3	43.3	137.8	34.7
COLLECTED PRODUCTS (INCLUDING SAMPLES), GRAMS/HOUR					

total Gas (incl. N2)	356.4	362.6	347.1	358.1	354.1
(N2 free)	319.3	347.9	334.7	345.4	362.1
OH	388.5	406.3	502.4	550.7	471.4
SOH-H2O	535.6	464.0	526.6	538.3	547.3
OH-NET WATER	92.8	98.3	102.3	121.7	170.0
Knockouts	1.5	2.7	1.7	1.8	2.2
filter Cake	32.0	77.7	204.3	206.2	204.2
filter Liquid	210.6	71.8	450.3	290.7	75.9
soh + KO	1.5	2.7	1.7	1.8	2.2
total CAS Bottoms	2086.8	1511.2	2010.0	2278.1	2056.6
reactor 1 Liquid Sample	0.0	0.0	0.0	0.0	0.0
separator Bottoms to CAS	2086.8	1511.2	2010.0	2278.1	2056.6
total Asoh	1.5	2.7	1.7	1.8	2.2
CAS Bottoms to Pressure Filter	1231.8	613.0	1172.6	1354.5	990.0
total Filter Cake	32.0	77.7	204.3	206.2	204.2
total Filter Liquid	1199.8	535.3	968.4	1148.3	785.8
SSURE FILTER					

vg Duration, min					
vg Pressure, psig					
vg Final Top Temp, deg-f					
ressure Filter Charge, g	29564.0	14713.0	28143.0	32508.0	23759.0
ressure Filter Cake, g	769.0	1865.0	4902.0	4949.0	4900.0
ressure Filter Liquid, g	28101.0	12397.0	22422.0	26601.0	18096.0
ressure Filter Loss, g	694.0	451.0	819.0	958.0	763.0
% Pfs	2.60	12.68	17.42	15.22	20.62

Unit number	01T	02T	03T	04T	05T
GAS RATES:-----					
H ₂ to 1st Stage, scfh	40.1	40.2	40.0	40.1	40.0
H ₂ to 1st Stage Recycle, scfh	40.1	40.1	40.0	40.1	40.1
H ₂ to 2nd Stage, scfh	35.6	35.6	35.6	35.6	35.6
bleed H ₂ , scfh	11.7	12.0	12.0	12.0	12.0
vent Gas, Scfh (N ₂ -Free)	79.3	75.1	69.4	70.9	69.0
NET ADJ. PRODUCTS, W% DRY COAL -----					
Total CO + CO ₂	1.16	1.43	1.27	1.48	1.76
Total C1-C3	6.12	7.02	6.74	6.87	6.91
Total C4-C7	2.26	2.27	1.61	2.22	2.06
SOH + KO) Water	8.49	8.33	7.62	9.87	11.51
SOH + KO) Oil	35.56	34.44	37.42	44.68	31.93
fl	44.95	30.96	38.61	34.42	13.16
fs	3.62	10.20	16.28	18.68	15.91
AS Bottoms	0.00	0.00	0.00	0.00	0.00
Reactor 1 Liquid Sample	0.00	0.00	0.00	0.00	0.00
HYDROTREATER OPERATION-----					
Hydrotreater Top Temp, F					
Hydrotreater Middle Temp, F					
Hydrotreater Bottom Temp, F					
Hydrotreater DP, Psi					
OPERATING CONDITIONS-----					
1st Stage Est Reaction Temp, F	805.	835.	833.	831.	834.
2nd Stage Est Reaction Temp, F	810.	854.	854.	853.	854.
Charge Pot Internal Temp, F	199.	211.	245.	283.	314.
Hot Separator Liquid (Stage II) Temp, F	654.	648.	651.	659.	652.
Hot Separator Liquid (Stage I) Temp, F	106.	105.	105.	102.	101.
Unit Back Pressure, psig	2509.	2509.	2504.	2511.	2516.
1st Stage Reactor DP, psi	4.7	5.5	7.5	10.0	9.8
2nd Stage Reactor DP, psi	2.3	3.1	3.2	3.3	3.6
1st Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
2nd Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
1st Stage Dry Coal SV, Lb Feed/Hr/Ft ³	34.1	36.8	41.9	38.5	46.1
2nd Stage Dry coal SV, Lb Feed/Hr/Ft ³	34.1	36.8	41.9	38.5	46.1
Two-Stage Space Velocity, Lb/Hr/Ft ³	17.1	18.4	21.0	19.2	23.0
1st Stage Slurry Residence Time, min	34.6	37.1	32.8	33.3	29.1
2nd Stage Slurry Residence Time, min	34.2	36.5	32.2	31.7	28.7
Moisture in Coal, W%	4.30	4.18	4.18	4.18	4.18
Total Dry Coal Fed to Date, g	26223.	53645.	85867.	115450.	150880.
H ₂ Consumed--Meter, W% Dry Coal	11.5	11.8	11.4	12.1	10.5

96 15:59

RUN 227-97 (POC PB-05) MATERIAL BALANCE

Illinois Coal-Waste Coprocessing using Dispersed Slurry Catalysts

FEED: Illinois No. 6 Crown II Mine: POC-01 COAL (HTI-6303)

Hondo VTB Oil and Waste Plastics

CATALYSTS: HTI'S Iron GelCat (1000 ppm Fe/100 ppm P)

Run Number	06T	07T	08T	09T	10T
(Start of Period)	08/13/96	08/14/96	08/15/96	08/16/96	08/17/96
Run, hrs	24.	24.	24.	24.	24.
Time of Run (End of Period)	144.	168.	192.	216.	240.

IN, GRAMS

Total Feed	27766.0	32377.0	32452.0	33588.0	27164.0
Makeup Oil to Charge (L-814/extracted oil)	7307.0	0.0	0.0	0.0	1168.0
Makeup Oil to Buffer (L-814/extracted oil)	0.0	0.0	0.0	0.0	0.0
Oil Recycled to Charge+K-2 Cat Addition	10328.0	12936.0	12967.0	13421.0	9848.0
AS Btms Recycled to Charge	16672.0	19440.0	19485.0	20168.0	16149.0
Filter Cake Recycled to Charge	0.0	0.0	0.0	0.0	0.0
Oil to Stage 1 Buffer	1136.0	845.0	725.0	1294.0	900.0
Oil to Stage 2 Buffer	846.0	776.0	740.0	1070.0	2117.0
Water to Hot Separators	8863.0	9860.0	9560.0	9717.0	9432.0
Total Sulfur Added	969.0	938.5	938.5	957.4	860.7
Additive (Fe/P+Mo Catalysts)	269.4	314.2	314.9	325.9	263.4
Oil to 1st Stage	4636.7	4641.3	4643.3	4642.7	4644.0
Oil to 2nd Stage	2058.9	2058.9	2057.8	2057.5	2057.4
Hydrogen Bleed	695.3	695.2	695.2	695.2	695.1
TOTAL GRAMS IN	81547.3	84882.1	84578.7	87936.7	75298.6

OUTS, GRAMS

Hydrogen Out	3425.9	3399.4	3416.0	3364.6	3823.5
Total Gas Product (N2,H2 Free)	12616.0	9421.0	9997.1	9583.1	6488.0
Unit Knockouts	37.0	40.0	61.0	42.0	30.0
Separator Overhead (HTU) Product	21807.0	20562.0	22784.0	23905.0	22479.0
Atmospheric Overhead Product (Sample)	0.0	0.0	0.0	0.0	0.0
AS Bottoms	43327.0	45195.0	43448.0	49393.0	42665.0
Feed + Interstage Slurry Sample	393.0	0.0	0.0	0.0	380.0
TOTAL GRAMS OUT	81605.9	78617.4	79706.1	86287.6	75865.5

Total Material Recovery (Gross)	100.07	92.62	94.24	98.12	100.75
---------------------------------	--------	-------	-------	-------	--------

Stream Number	06T	07T	08T	09T	10T
CHARGE, PRODUCT, AND RECYCLE RATES-----					
D RATES, GRAMS/HOUR					

Total Carbonaceous Feed	1156.9	1349.0	1352.2	1399.5	1131.8
ry Carbonaceous Feed	1117.7	1303.3	1306.3	1352.1	1093.5
otal Makeup Oil Rate	304.5	0.0	0.0	0.0	48.7
ater to Hot Separator	369.3	410.8	398.3	404.9	393.0
2 to 1st Stage	193.2	193.4	193.5	193.4	193.5
2 to 2nd Stage	85.8	85.8	85.7	85.7	85.7
CYCLE RATES TO REACTOR, GRAMS/HOUR					

FL Recycled to Slurry + Pretreater Buffer	430.3	539.0	540.3	559.2	410.3
AS Bottoms Recycled	694.7	810.0	811.9	840.3	672.9
fl to 1st Stage Buffer	47.3	35.2	30.2	53.9	37.5
fl to 2nd Stage Buffer	35.3	32.3	30.8	44.6	88.2
COLLECTED PRODUCTS (INCLUDING SAMPLES), GRAMS/HOUR					

otal Gas (incl. N2)	708.1	577.6	593.2	575.9	470.7
(N2 free)	668.4	534.2	558.9	539.5	429.6
OH	461.0	373.6	456.6	460.3	522.5
SOH-H2O	447.6	483.2	492.8	535.8	414.1
OH-NET WATER	78.3	72.3	94.4	130.9	21.1
Knockouts	1.5	1.7	2.5	1.8	1.3
ilter Cake	197.3	188.5	211.3	195.1	135.3
ilter Liquid	399.7	170.9	207.1	104.6	198.3
soh + KO	1.5	1.7	2.5	1.8	1.3
otal CAS Bottoms	1805.3	1883.1	1810.3	2058.0	1777.7
reactor 1 Liquid Sample	16.4	0.0	0.0	0.0	15.8
eparator Bottoms to CAS	1805.3	1883.1	1810.3	2058.0	1777.7
otal Asoh	1.5	1.7	2.5	1.8	1.3
AS Bottoms to Pressure Filter	1109.9	966.0	1019.7	957.4	869.5
otal Filter Cake	197.3	188.5	211.3	195.1	135.3
otal Filter Liquid	912.6	777.5	808.4	762.3	734.3
SSURE FILTER					

vg Duration, min					
vg Pressure, psig					
vg Final Top Temp, deg-f					
ressure Filter Charge, g	26637.0	23184.0	24473.0	22978.0	20869.0
ressure Filter Cake, g	4734.0	4525.0	5071.0	4682.0	3246.0
ressure Filter Liquid, g	20952.0	17425.0	17983.0	17236.0	16111.0
ressure Filter Loss, g	951.0	1234.0	1419.0	1060.0	1512.0
% Pfs	17.77	19.52	20.72	20.38	15.55

id number	06T	07T	08T	09T	10T
GAS RATES:-----					
2 to 1st Stage, scfh	40.1	40.2	40.2	40.2	40.2
2 to 1st Stage Recycle, scfh	40.1	40.1	40.1	40.2	40.2
2 to 2nd Stage, scfh	35.6	35.6	35.6	35.6	35.6
Feed H2, scfh	12.0	12.0	12.0	12.0	12.0
ent Gas, Scfh (N2-Free)	73.2	69.7	70.5	69.1	73.4
NET ADJ. PRODUCTS, W% DRY COAL -----					
total CO + CO2	3.77	2.63	2.85	2.24	1.26
total C1-C3	19.77	14.41	14.95	13.72	11.32
total C4-C7	7.69	3.88	4.64	4.27	4.60
SOH + KO) Water	7.01	5.55	7.23	9.68	1.93
SOH + KO) Oil	41.25	28.66	34.95	34.04	47.79
Fl	35.82	19.73	14.56	23.07	36.30
fs	17.66	16.07	15.84	18.35	15.72
AS Bottoms	0.00	0.00	0.00	0.00	0.00
Reactor 1 Liquid Sample	1.47	0.00	0.00	0.00	1.45
HYDROTREATER OPERATION-----					
Hydrotreater Top Temp, F					
Hydrotreater Middle Temp, F					
Hydrotreater Bottom Temp, F					
Hydrotreater DP, Psi					
OPERATING CONDITIONS-----					
1st Stage Est Reaction Temp, F	836.	836.	834.	836.	834.
2nd Stage Est Reaction Temp, F	856.	856.	856.	856.	858.
Charge Pot Internal Temp, F	294.	278.	280.	297.	416.
1st Separator Liquid (Stage II) Temp, F	656.	657.	650.	650.	661.
2nd Separator Liquid (Stage I) Temp, F	99.	105.	106.	106.	109.
Unit Back Pressure, psig	2523.	2518.	2523.	2525.	2516.
1st Stage Reactor DP, psi	10.9	13.7	18.6	17.7	16.7
2nd Stage Reactor DP, psi	3.4	3.3	3.5	3.4	2.9
1st Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
2nd Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
1st Stage Dry Coal SV, Lb Feed/Hr/Ft3	34.9	40.7	40.8	42.2	34.1
2nd Stage Dry coal SV, Lb Feed/Hr/Ft3	34.9	40.7	40.8	42.2	34.1
Two-Stage Space Velocity, Lb/Hr/Ft3	17.4	20.3	20.4	21.1	17.1
1st Stage Slurry Residence Time, min	34.9	33.7	33.7	32.3	40.1
2nd Stage Slurry Residence Time, min	34.4	33.3	33.3	31.8	38.5
Moisture in Coal, W%	4.19	4.19	4.19	4.19	4.19
Total Dry Coal Fed to Date, g	177704.	208984.	240336.	272785.	299028.
H2 Consumed--Meter, W% Dry Coal	14.8	12.8	12.7	12.4	13.6

-96 16:42

RUN 227-97 (POC PB-05) MATERIAL BALANCE

Illinois Coal-Waste Coprocessing using Dispersed Slurry Catalysts

FEED: Illinois No. 6 Crown II Mine: POC-01 COAL (HTI-6303)

Hondo VTB Oil and Waste Plastics

CATALYSTS: HTI'S Iron GelCat (1000 ppm Fe/100 ppm P)

Number	11T	12T	13T	14T	15T
Start of Period)	08/18/96	08/19/96	08/20/96	08/21/96	08/22/96
on, hrs	24.	24.	24.	24.	24.
of Run (End of Period)	264.	288.	312.	336.	360.

GRAMS

Total Feed	28401.0	29260.0	28714.0	29391.0	32494.0
Makeup Oil to Charge (L-814/extracted oil)	1511.0	0.0	0.0	0.0	0.0
Makeup Oil to Buffer (L-814/extracted oil)	0.0	0.0	0.0	0.0	0.0
Oil Recycled to Charge+K-2 Cat Addition	9849.0	11704.0	11486.0	13964.0	15590.0
AS Btms Recycled to Charge	17041.0	17556.0	17228.0	20950.0	23385.0
Filter Cake Recycled to Charge	0.0	0.0	0.0	0.0	0.0
Oil to Stage 1 Buffer	730.0	884.0	705.0	850.0	821.0
Oil to Stage 2 Buffer	739.0	876.0	679.0	745.0	739.0
Water to Hot Separators	9644.0	9386.0	8829.0	9573.0	9799.0
Total Sulfur Added	960.0	973.8	997.4	952.6	936.1
Additive (Fe/P+Mo Catalysts)	275.4	283.7	278.4	315.6	315.3
Oil to 1st Stage	4643.6	4643.8	4644.2	4645.1	4644.7
Oil to 2nd Stage	2057.2	2057.4	2057.3	2058.4	2058.8
Hydrogen Bleed	695.0	695.1	695.0	695.0	694.9
TOTAL GRAMS IN	76546.2	78319.8	76313.3	84139.6	91477.8

GRAMS

Hydrogen Out	3901.2	3811.1	3902.1	3816.8	4028.1
Total Gas Product (N2,H2 Free)	6229.7	7870.9	5918.4	6151.8	3174.1
Unit Knockouts	38.0	62.0	63.0	69.0	60.0
Separator Overhead (HTU) Product	26703.0	23571.0	24069.0	25951.0	25009.0
Atmospheric Overhead Product (Sample)	0.0	0.0	0.0	0.0	0.0
AS Bottoms	40442.0	39024.0	38145.0	48445.0	51650.0
Feed + Interstage Slurry Sample	0.0	0.0	0.0	340.0	0.0
TOTAL GRAMS OUT	77313.9	74339.1	72097.5	84773.6	83921.2
Total Material Recovery (Gross)	101.00	94.92	94.48	100.75	91.74

Unit Number	11T	12T	13T	14T	15T
CHARGE, PRODUCT, AND RECYCLE RATES-----					
D RATES, GRAMS/HOUR					

Total Carbonaceous Feed	1183.4	1219.2	1196.4	1224.6	1353.9
ry Carbonaceous Feed	1143.3	1177.8	1168.7	1183.1	1308.0
otal Makeup Oil Rate	63.0	0.0	0.0	0.0	0.0
ater to Hot Separator	401.8	391.1	367.9	398.9	408.3
2 to 1st Stage	193.5	193.5	193.5	193.5	193.5
2 to 2nd Stage	85.7	85.7	85.7	85.8	85.8
CYCLE RATES TO REACTOR, GRAMS/HOUR					

FL Recycled to Slurry + Pretreater Buffer	410.4	487.7	478.6	581.8	649.6
CAS Bottoms Recycled	710.0	731.5	717.8	872.9	974.4
fl to 1st Stage Buffer	30.4	36.8	29.4	35.4	34.2
fl to 2nd Stage Buffer	30.8	36.5	28.3	31.0	30.8
COLLECTED PRODUCTS (INCLUDING SAMPLES), GRAMS/HOUR					

otal Gas (incl. N2)	463.2	526.3	443.7	455.5	299.7
(N2 free)	422.1	486.8	409.2	415.4	300.1
OH	696.3	565.3	626.2	594.0	625.1
SOH-H2O	416.3	416.9	376.7	487.3	416.9
OH-NET WATER	14.5	25.8	8.8	88.4	8.6
Knockouts	1.6	2.6	2.6	2.9	2.5
filter Cake	103.7	71.6	60.9	92.6	107.2
filter Liquid	182.5	56.0	-21.4	226.5	396.9
soh + KO	1.6	2.6	2.6	2.9	2.5
otal CAS Bottoms	1685.1	1626.0	1589.4	2018.5	2152.1
reactor 1 Liquid Sample	0.0	0.0	0.0	14.2	0.0
eparator Bottoms to CAS	1685.1	1626.0	1589.4	2018.5	2152.1
otal Asoh	1.6	2.6	2.6	2.9	2.5
CAS Bottoms to Pressure Filter	757.8	688.7	575.8	967.4	1218.6
otal Filter Cake	103.7	71.6	60.9	92.6	107.2
otal Filter Liquid	654.1	617.0	514.9	874.8	1111.5
SSURE FILTER					

vg Duration, min					
vg Pressure, psig					
vg Final Top Temp, deg-f					
ressure Filter Charge, g	18187.0	16528.0	13819.0	23218.0	29247.0
ressure Filter Cake, g	2488.0	1719.0	1462.0	2222.0	2572.0
ressure Filter Liquid, g	14876.0	14063.0	11542.0	20037.0	24641.0
ressure Filter Loss, g	823.0	746.0	815.0	959.0	2034.0
% Pfs	13.68	10.40	10.58	9.57	8.79

number	11T	12T	13T	14T	15T
AS RATES:-----					
to 1st Stage, scfh	40.2	40.2	40.2	40.2	40.2
to 1st Stage Recycle, scfh	40.1	40.2	40.2	40.1	40.1
to 2nd Stage, scfh	35.6	35.6	35.6	35.6	35.6
eed H2, scfh	12.0	12.0	12.0	12.0	12.0
nt Gas, Scfh (N2-Free)	74.2	73.8	73.7	72.5	72.7
ET ADJ. PRODUCTS, W% DRY COAL -----					
tal CO + CO2	0.89	0.81	0.80	1.13	0.53
tal C1-C3	9.59	10.59	8.56	8.70	4.08
tal C4-C7	5.05	6.91	4.81	4.76	3.70
OH + KO) Water	1.27	2.19	0.76	7.47	0.66
OH + KO) Oil	60.90	47.99	53.58	50.21	47.79
l	32.37	20.42	20.80	32.77	27.49
s	11.67	7.90	7.89	9.27	7.92
S Bottoms	0.00	0.00	0.00	0.00	0.00
actor 1 Liquid Sample	0.00	0.00	0.00	1.20	0.00
HYDROTREATER OPERATION-----					
ydrotreater Top Temp, F					
ydrotreater Middle Temp, F					
ydrotreater Bottom Temp, F					
ydrotreater DP, Psi					
OPERATING CONDITIONS-----					
st Stage Est Reaction Temp, F	835.	835.	836.	835.	835.
nd Stage Est Reaction Temp, F	857.	856.	855.	854.	853.
arge Pot Internal Temp, F	431.	431.	433.	432.	460.
ot Separator Liquid (Stage II) Temp, F	657.	654.	656.	666.	669.
ot Separator Liquid (Stage I) Temp, F	109.	108.	104.	106.	109.
nit Back Pressure, psig	2508.	2511.	2513.	2505.	2500.
st Stage Reactor DP, psi	12.1	12.5	11.7	11.6	12.2
nd Stage Reactor DP, psi	2.6	2.6	2.6	2.6	2.6
st Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
nd Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
st Stage Dry Coal SV, Lb Feed/Hr/Ft3	35.7	36.8	36.5	36.9	40.8
nd Stage Dry coal SV, Lb Feed/Hr/Ft3	35.7	36.8	36.5	36.9	40.8
wo-Stage Space Velocity, Lb/Hr/Ft3	17.8	18.4	18.2	18.5	20.4
st Stage Slurry Residence Time, min	38.5	37.2	37.9	33.9	30.6
nd Stage Slurry Residence Time, min	37.9	36.6	37.4	33.5	30.2
isture in Coal, W%	4.19	4.19	3.11	4.28	4.19
otal Dry Coal Fed to Date, g	326466.	354734.	382784.	411178.	442571.
2 Consumed--Meter, W% Dry Coal	12.7	12.7	12.5	12.6	10.7

96 16:43

RUN 227-97 (POC PB-05) MATERIAL BALANCE

Illinois Coal-Waste Coprocessing using Dispersed Slurry Catalysts

FEED: Illinois No. 6 Crown II Mine: POC-01 COAL (HTI-6303)

Hondo VTB Oil and Waste Plastics

CATALYSTS: HTI'S Iron GelCat (1000 ppm Fe/100 ppm P)

Number	16T	17T	18T	19T	20T
Start of Period)	08/23/96	08/24/96	08/25/96	08/26/96	08/27/96
on, hrs	24.	24.	24.	24.	24.
of Run (End of Period)	384.	408.	432.	456.	480.

, GRAMS

tal Feed	35837.0	33212.0	37999.0	43716.0	32663.0
akeup Oil to Charge (L-814/extracted oil)	0.0	0.0	470.0	0.0	3550.0
akeup Oil to Buffer (L-814/extracted oil)	0.0	0.0	0.0	0.0	0.0
l Recycled to Charge+K-2 Cat Addition	17193.0	15934.0	10620.0	4886.0	3644.0
S Btms Recycled to Charge	25791.0	23901.0	23622.0	23628.0	17618.4
lter Cake Recycled to Charge	0.0	0.0	0.0	0.0	0.0
l to Stage 1 Buffer	720.0	712.0	951.0	1123.0	1165.0
l to Stage 2 Buffer	665.0	835.0	1210.0	797.0	7411.0
ter to Hot Separators	9908.0	9904.0	10024.0	9546.0	10136.0
tal Sulfur Added	938.5	830.0	1006.9	962.0	976.2
ditive (Fe/P+Mo Catalysts)	356.4	322.3	318.6	318.6	218.9
to 1st Stage	4644.0	4644.9	4643.0	4643.3	4634.5
to 2nd Stage	2058.7	2058.7	2058.7	2058.6	2058.7
hydrogen Bleed	694.9	694.9	694.9	694.9	694.9
TAL GRAMS IN	98806.5	93048.8	93618.1	92373.4	84770.6

S, GRAMS

hydrogen Out	4031.5	4034.6	3986.1	3971.7	4056.0
tal Gas Product (N2,H2 Free)	2523.0	2432.6	3044.9	3153.0	3235.9
it Knockouts	50.0	58.0	69.0	120.0	70.0
parator Overhead (HTU) Product	25014.0	25466.0	27199.0	25727.0	25741.0
mospheric Overhead Product (Sample)	0.0	0.0	0.0	0.0	0.0
S Bottoms	48323.0	53689.0	54047.0	54298.0	49614.0
ed + Interstage Slurry Sample	0.0	0.0	336.0	0.0	0.0
TAL GRAMS OUT	79941.5	85680.2	88682.0	87269.6	82717.0

Total Material Recovery (Gross)	80.91	92.08	94.73	94.47	97.58
---------------------------------	-------	-------	-------	-------	-------

Number	16T	17T	18T	19T	20T
CHARGE, PRODUCT, AND RECYCLE RATES-----					
RATES, GRAMS/HOUR					

total Carbonaceous Feed	1493.2	1383.8	1583.3	1821.5	1361.0
by Carbonaceous Feed	1442.6	1336.9	1529.6	1759.8	1314.8
total Makeup Oil Rate	0.0	0.0	19.6	0.0	147.9
water to Hot Separator	412.8	412.7	417.7	397.8	422.3
to 1st Stage	193.5	193.5	193.5	193.5	193.1
to 2nd Stage	85.8	85.8	85.8	85.8	85.8
CLE RATES TO REACTOR, GRAMS/HOUR					

L Recycled to Slurry + Pretreater Buffer	716.4	663.9	442.5	203.6	151.8
S Bottoms Recycled	1074.6	995.9	984.3	984.5	734.1
L to 1st Stage Buffer	30.0	29.7	39.6	46.8	48.5
L to 2nd Stage Buffer	27.7	34.8	50.4	33.2	308.8
COLLECTED PRODUCTS (INCLUDING SAMPLES), GRAMS/HOUR					

total Gas (incl. N2)	270.9	264.1	287.8	295.1	301.1
(N2 free)	273.1	269.5	293.0	296.9	303.8
H	622.8	582.0	635.5	575.8	586.9
SOH-H2O	419.5	479.0	497.8	496.2	485.7
H-NET WATER	6.6	66.4	80.2	98.4	63.3
Knockouts	2.1	2.4	2.9	5.0	2.9
Water Cake	138.7	124.0	178.9	167.9	128.5
Water Liquid	132.0	208.4	615.3	759.3	388.7
oil + KO	2.1	2.4	2.9	5.0	2.9
total CAS Bottoms	2013.5	2237.0	2252.0	2262.4	2067.3
Reactor 1 Liquid Sample	0.0	0.0	14.0	0.0	0.0
Separator Bottoms to CAS	2013.5	2237.0	2252.0	2262.4	2067.3
total Asoh	2.1	2.4	2.9	5.0	2.9
S Bottoms to Pressure Filter	1044.8	1060.8	1326.8	1210.8	1026.4
total Filter Cake	138.7	124.0	178.9	167.9	128.5
total Filter Liquid	906.1	936.8	1147.8	1042.9	897.9
PRESSURE FILTER					

g Duration, min					
g Pressure, psig					
g Final Top Temp, deg-f					
Pressure Filter Charge, g	25075.0	25458.0	31842.0	29059.0	24633.0
Pressure Filter Cake, g	3329.0	2975.0	4294.0	4029.0	3084.0
Pressure Filter Liquid, g	20794.0	21544.0	26285.0	23947.0	20718.0
Pressure Filter Loss, g	952.0	939.0	1263.0	1083.0	831.0
% Pfs	13.28	11.69	13.49	13.86	12.52

id number	16T	17T	18T	19T	20T
GAS RATES:-----					
2 to 1st Stage, scfh	40.2	40.2	40.2	40.2	40.1
2 to 1st Stage Recycle, scfh	40.1	40.1	40.1	40.1	40.1
2 to 2nd Stage, scfh	35.6	35.6	35.6	35.6	35.6
Feed H ₂ , scfh	12.0	12.0	12.0	12.0	12.0
ent Gas, Scfh (N ₂ -Free)	72.4	72.4	72.2	72.1	73.6
NET ADJ. PRODUCTS, W% DRY COAL -----					
otal CO + CO ₂	0.45	0.56	0.66	0.61	0.89
otal C1-C3	2.99	3.27	4.22	3.95	5.31
otal C4-C7	1.59	1.36	1.29	1.18	1.70
SOH + KO) Water	0.46	4.96	5.24	5.59	4.82
SOH + KO) Oil	43.17	43.54	41.54	32.72	44.64
fl	2.78	27.51	36.89	46.44	49.97
fs	8.64	10.85	11.18	10.07	12.69
AS Bottoms	0.00	0.00	0.00	0.00	0.00
reactor 1 Liquid Sample	0.00	0.00	0.92	0.00	0.00
HYDROTREATER OPERATION-----					
ydrotreater Top Temp, F					
ydrotreater Middle Temp, F					
ydrotreater Bottom Temp, F					
ydrotreater DP, Psi					
OPERATING CONDITIONS-----					
st Stage Est Reaction Temp, F	837.	836.	836.	837.	834.
nd Stage Est Reaction Temp, F	854.	857.	856.	855.	856.
harge Pot Internal Temp, F	476.	477.	477.	477.	472.
ot Separator Liquid (Stage II) Temp, F	671.	671.	672.	671.	664.
ot Separator Liquid (Stage I) Temp, F	114.	110.	110.	110.	106.
nit Back Pressure, psig	2495.	2495.	2496.	2496.	2488.
st Stage Reactor DP, psi	11.9	11.8	11.5	11.7	11.6
nd Stage Reactor DP, psi	2.5	2.6	2.6	2.7	3.0
st Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	52933.	78077.
nd Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
st Stage Dry Coal SV, Lb Feed/Hr/Ft ³	45.0	41.7	47.7	54.9	41.0
nd Stage Dry coal SV, Lb Feed/Hr/Ft ³	45.0	41.7	47.7	54.9	41.0
wo-Stage Space Velocity, Lb/Hr/Ft ³	22.5	20.9	23.9	27.5	20.5
st Stage Slurry Residence Time, min	36.8	39.6	39.8	40.1	50.1
nd Stage Slurry Residence Time, min	36.5	39.2	39.1	39.6	44.3
oisture in Coal, W%	4.21	4.19	4.08	3.99	3.94
otal Dry Coal Fed to Date, g	477193.	509279.	545990.	588224.	619780.
2 Consumed--Meter, W% Dry Coal	9.7	10.5	9.3	8.1	10.6

-96 16:45

RUN 227-97 (POC PB-05) MATERIAL BALANCE

Illinois Coal-Waste Coprocessing using Dispersed Slurry Catalysts

FEED: Illinois No. 6 Crown II Mine: POC-01 COAL (HTI-6303)

Hondo VTB Oil and Waste Plastics

CATALYSTS: HTI'S Iron GelCat (1000 ppm Fe/100 ppm P)

Number	21T	22T	23T	24T	25T
Start of Period)	08/28/96	08/29/96	08/30/96	08/31/96	09/01/96
on, hrs	24.	24.	24.	24.	24.
of Run (End of Period)	504.	528.	552.	576.	600.

, GRAMS

tal Feed	37239.0	44031.0	39704.0	36224.7	29454.0
akeup Oil to Charge (L-814/extracted oil)	496.0	0.0	0.0	0.0	0.0
akeup Oil to Buffer (L-814/extracted oil)	0.0	0.0	0.0	0.0	0.0
l Recycled to Charge+K-2 Cat Addition	4177.0	0.0	0.0	0.0	0.0
S Btms Recycled to Charge	20197.0	8812.0	7946.0	7250.0	5895.0
lter Cake Recycled to Charge	0.0	0.0	0.0	0.0	0.0
l to Stage 1 Buffer	6032.0	818.0	964.0	738.0	767.0
l to Stage 2 Buffer	913.0	819.0	903.0	716.0	781.0
ter to Hot Separators	9559.0	9647.0	9750.0	9455.0	9730.0
tal Sulfur Added	962.1	532.9	627.3	863.0	973.9
ditive (Fe/P+Mo Catalysts)	272.4	427.3	385.3	351.5	285.8
to 1st Stage	4644.3	4643.4	4643.4	4643.4	4643.3
to 2nd Stage	2058.0	2058.2	2058.2	2058.4	2058.3
hydrogen Bleed	694.7	694.6	694.5	694.6	694.7
TAL GRAMS IN	87244.5	72483.4	67675.7	62994.6	55283.1

S, GRAMS

hydrogen Out	3755.5	3978.4	3916.5	4069.4	4041.3
tal Gas Product (N2,H2 Free)	4611.7	4213.8	3896.3	2858.5	3409.8
it Knockouts	118.0	39.0	20.0	7.0	9.0
parator Overhead (HTU) Product	25352.0	24539.0	25913.0	26443.0	25903.0
mospheric Overhead Product (Sample)	0.0	0.0	0.0	0.0	0.0
S Bottoms	50612.0	40763.0	30096.0	20718.0	17317.0
ed + Interstage Slurry Sample	0.0	529.0	0.0	0.0	0.0
TAL GRAMS OUT	84449.2	74062.2	63841.9	54095.8	50680.2

Total Material Recovery (Gross)	96.80	102.18	94.33	85.87	91.67
---------------------------------	-------	--------	-------	-------	-------

Number	21T	22T	23T	24T	25T
CHARGE, PRODUCT, AND RECYCLE RATES-----					
RATES, GRAMS/HOUR					

total Carbonaceous Feed	1551.6	1834.6	1654.3	1509.4	1227.3
dry Carbonaceous Feed	1499.0	1772.4	1598.3	1458.2	1185.6
total Makeup Oil Rate	20.7	0.0	0.0	0.0	0.0
water to Hot Separator	398.3	402.0	406.3	394.0	405.4
to 1st Stage	193.5	193.5	193.5	193.5	193.5
to 2nd Stage	85.8	85.8	85.8	85.8	85.8
CLE RATES TO REACTOR, GRAMS/HOUR					

Oil Recycled to Slurry + Pretreater Buffer	174.0	0.0	0.0	0.0	0.0
S Bottoms Recycled	841.5	367.2	331.1	302.1	245.6
Oil to 1st Stage Buffer	251.3	34.1	40.2	30.8	32.0
Oil to 2nd Stage Buffer	38.0	34.1	37.6	29.8	32.5
COLLECTED PRODUCTS (INCLUDING SAMPLES), GRAMS/HOUR					

total Gas (incl. N2)	346.9	329.9	321.7	275.4	302.7
(N2 free)	348.6	341.3	325.5	288.7	310.5
H	603.8	554.8	614.6	654.8	620.5
SOH-H2O	452.5	467.7	465.1	447.0	458.8
H-NET WATER	54.2	65.8	58.8	53.0	53.4
Knockouts	4.9	1.6	0.8	0.3	0.4
Filter Cake	223.5	227.7	140.8	99.3	60.2
Filter Liquid	802.5	1020.7	646.4	350.6	221.0
Oil + KO	4.9	1.6	0.8	0.3	0.4
total CAS Bottoms	2108.8	1698.5	1254.0	863.3	721.5
Reactor 1 Liquid Sample	0.0	22.0	0.0	0.0	0.0
Separator Bottoms to CAS	2108.8	1698.5	1254.0	863.3	721.5
total Asoh	4.9	1.6	0.8	0.3	0.4
S Bottoms to Pressure Filter	1489.4	1316.5	865.0	510.5	345.6
total Filter Cake	223.5	227.7	140.8	99.3	60.2
total Filter Liquid	1265.9	1088.9	724.2	411.2	285.5
PRESSURE FILTER					

g Duration, min					
g Pressure, psig					
g Final Top Temp, deg-f					
Pressure Filter Charge, g	35745.0	31597.0	20760.0	12251.0	8295.3
Pressure Filter Cake, g	5363.0	5464.0	3380.0	2382.0	1444.1
Pressure Filter Liquid, g	29050.0	24862.0	16105.0	8959.0	6069.2
Pressure Filter Loss, g	1332.0	1271.0	1275.0	910.0	782.0
Pfs	15.00	17.29	16.28	19.44	17.41

id number	21T	22T	23T	24T	25T
GAS RATES:-----					
2 to 1st Stage, scfh	40.2	40.2	40.2	40.2	40.2
2 to 1st Stage Recycle, scfh	40.1	40.1	40.1	40.1	40.1
2 to 2nd Stage, scfh	35.6	35.6	35.6	35.6	35.6
Feed H2, scfh	12.0	12.0	12.0	12.0	12.0
ent Gas, Scfh (N2-Free)	69.8	73.3	71.8	73.4	73.5
NET ADJ. PRODUCTS, W% DRY COAL -----					
total CO + CO2	1.01	0.68	0.54	0.37	0.60
total C1-C3	6.69	4.36	3.97	3.42	4.88
total C4-C7	2.50	1.61	2.02	1.56	2.16
SOH + KO) Water	3.62	3.71	3.68	3.64	4.51
SOH + KO) Oil	40.28	31.30	38.46	44.90	52.33
Fl	40.94	58.27	43.48	26.85	27.71
fs	12.68	12.99	9.40	7.48	6.99
AS Bottoms	0.00	0.00	0.00	0.00	0.00
Reactor 1 Liquid Sample	0.00	1.24	0.00	0.00	0.00
HYDROTREATER OPERATION-----					
Hydrotreater Top Temp, F					
Hydrotreater Middle Temp, F					
Hydrotreater Bottom Temp, F					
Hydrotreater DP, Psi					
OPERATING CONDITIONS-----					
1st Stage Est Reaction Temp, F	838.	834.	833.	835.	836.
2nd Stage Est Reaction Temp, F	856.	854.	854.	854.	854.
Charge Pot Internal Temp, F	459.	428.	379.	380.	380.
1st Separator Liquid (Stage II) Temp, F	661.	650.	642.	620.	607.
2nd Separator Liquid (Stage I) Temp, F	107.	109.	109.	107.	106.
Unit Back Pressure, psig	2491.	2491.	2492.	2491.	2492.
1st Stage Reactor DP, psi	9.2	9.1	22.8	23.0	23.3
2nd Stage Reactor DP, psi	3.3	6.1	19.9	31.9	16.8
1st Stage Internal Recycle Rate, cc/hr	62528.	55580.	52272.	51412.	57036.
2nd Stage Internal Recycle Rate, cc/hr	47640.	47640.	47640.	47640.	47640.
1st Stage Dry Coal SV, Lb Feed/Hr/Ft3	46.8	55.3	49.9	45.5	37.0
2nd Stage Dry coal SV, Lb Feed/Hr/Ft3	46.8	55.3	49.9	45.5	37.0
Two-Stage Space Velocity, Lb/Hr/Ft3	23.4	27.7	24.9	22.8	18.5
1st Stage Slurry Residence Time, min	43.1	55.2	60.9	67.0	82.0
2nd Stage Slurry Residence Time, min	42.5	54.3	59.8	65.9	80.2
Moisture in Coal, W%	4.00	4.19	4.19	4.19	4.19
Total Dry Coal Fed to Date, gms	655756.	698295.	736653.	771649.	800105.
H2 Consumed--Meter, W% Dry Coal	10.1	8.0	9.1	9.5	11.8

-96 16:48

YIELDS OF GASES FOR RUN 227-97 (PB-05)

: BLACK THUNDER MINE-POC-02 COAL (HRI 6213)

OD NUMBER	1	2	3	4	5	6	7	8
YIELDS (Stage I), W% of mf coal								
	3.60	3.30	2.70	2.89	4.69	5.90	4.87	5.26
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	2.04	2.22	1.68	3.36	1.53	5.97	3.52	4.07
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	2.34	2.75	1.68	5.73	3.73	9.41	3.99	4.77
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
H10	1.10	1.27	0.64	3.08	1.51	4.72	1.66	2.07
H10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
H12	0.45	0.36	0.22	0.79	0.36	0.99	0.42	0.44
H12	0.32	0.22	0.12	0.50	0.20	0.66	0.22	0.26
YL-CYCLOPENTANE	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
OHEXANE	0.08	0.06	0.02	0.53	0.15	0.65	0.12	0.19
H14	0.12	0.09	0.02	0.37	0.06	0.40	0.05	0.12
	0.04	0.03	0.00	0.26	0.00	0.33	0.02	0.07
	0.00	0.08	0.01	0.08	0.14	0.19	0.13	0.19
	0.04	0.06	0.05	0.10	0.11	0.19	0.10	0.17
	10.89	8.39	5.39	15.26	10.12	23.06	10.06	11.19

OD NUMBER	1	2	3	4	5	6	7	8
YIELDS (Stage II), W% of mf coal								
	0.07	0.14	0.07	0.10	0.07	0.09	0.06	0.07
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.08	0.17	0.10	0.13	0.09	0.12	0.09	0.11
	0.01	0.01	0.00	0.01	0.00	0.01	0.00	0.00
	0.13	0.28	0.16	0.21	0.16	0.20	0.15	0.19
	0.01	0.01	0.01	0.01	0.00	0.01	0.01	0.01
H10	0.10	0.20	0.11	0.15	0.11	0.14	0.11	0.13
H10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
H12	0.07	0.09	0.05	0.06	0.04	0.05	0.04	0.05
H12	0.04	0.06	0.03	0.03	0.02	0.03	0.02	0.03
YL-CYCLOPENTANE	0.05	0.06	0.03	0.04	0.03	0.03	0.02	0.03
OHEXANE	0.10	0.12	0.05	0.05	0.05	0.05	0.04	0.05
H14	0.05	0.07	0.04	0.04	0.03	0.04	0.03	0.04
	0.00	0.00	0.03	0.03	0.03	0.03	0.02	0.03
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.01	0.01	0.00	0.01	0.00	0.01	0.00	0.00
	0.84	1.32	0.75	0.97	0.65	0.83	0.59	0.63

-96 16:49

YIELDS OF GASES FOR RUN 227-97 (PB-05)

: BLACK THUNDER MINE-POC-02 COAL (HRI 6213)

OD NUMBER	9	10	11	12	13	14	15	16
YIELDS (Stage I), W% of mf coal								
	4.76	4.37	3.94	3.13	3.04	2.92	1.28	1.00
	0.00	0.00	0.09	0.00	0.00	0.00	0.00	0.00
	3.87	3.65	3.31	2.89	2.93	3.15	1.13	2.10
	0.00	0.00	0.33	0.00	0.00	0.00	0.00	0.00
	4.71	4.72	4.36	4.04	4.20	4.90	1.45	3.77
	0.00	0.00	0.26	0.00	0.00	0.00	0.08	0.00
10	2.08	2.00	1.97	1.94	2.20	2.58	0.37	1.94
10	0.00	0.00	0.00	0.00	0.00	0.00	0.30	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12	0.49	0.68	0.87	0.96	1.34	1.40	0.35	0.97
12	0.27	0.35	0.39	0.40	0.58	0.55	0.11	0.34
L-CYCLOPENTANE	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.02
HEXANE	0.32	0.12	0.03	0.06	0.06	0.18	0.25	0.25
14	0.09	0.06	0.07	0.10	0.27	0.27	0.21	0.21
	0.02	0.00	0.00	0.06	0.03	0.12	0.29	0.12
	0.12	0.00	0.19	0.00	0.00	0.14	0.05	0.03
	0.08	0.09	0.07	0.02	0.03	0.05	0.03	0.04
	10.50	14.73	16.53	17.24	17.30	18.37	3.52	12.85

OD NUMBER	9	10	11	12	13	14	15	16
YIELDS (Stage II), W% of mf coal								
	0.06	0.04	0.04	0.03	0.04	0.06	0.04	0.04
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.09	0.08	0.07	0.06	0.07	0.10	0.77	0.10
	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	0.16	0.16	0.13	0.12	0.14	0.19	0.13	0.18
	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02
10	0.11	0.12	0.10	0.09	0.11	0.14	0.05	0.13
10	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12	0.04	0.08	0.08	0.07	0.08	0.12	0.06	0.09
12	0.02	0.03	0.03	0.03	0.04	0.04	0.02	0.03
L-CYCLOPENTANE	0.03	0.03	0.03	0.03	0.04	0.04	0.03	0.03
HEXANE	0.07	0.05	0.04	0.04	0.04	0.06	0.04	0.06
14	0.03	0.04	0.04	0.04	0.04	0.05	0.04	0.04
	0.00	0.04	0.03	0.03	0.02	0.03	0.03	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.59	0.75	0.71	0.76	0.83	1.07	0.45	1.01

YIELDS OF GASES FOR RUN 227-97 (PB-05)

L: BLACK THUNDER MINE-POC-02 COAL (HRI 6213)

MOD NUMBER	17	18	19	20	21	22	23	24
YIELDS (Stage I), W% of mf coal								
	1.05	1.11	1.10	1.09	1.34	1.11	1.39	0.93
	0.00	0.00	0.00	0.00	0.03	0.03	0.08	0.03
	1.25	1.52	1.14	1.32	1.27	1.18	1.80	1.33
	0.00	0.00	0.00	0.00	0.11	0.09	0.25	0.11
	1.63	2.49	1.50	1.89	1.55	1.38	2.31	1.99
	0.00	0.00	0.00	0.00	0.07	0.06	0.24	0.10
10	0.77	1.23	0.54	0.83	0.69	0.66	1.25	1.16
10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12	0.40	0.62	0.24	0.36	0.34	0.27	0.46	0.42
12	0.15	0.20	0.08	0.12	0.11	0.14	0.33	0.26
1L-CYCLOPENTANE	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.08
HEXANE	0.07	0.13	0.04	0.08	0.07	0.02	0.05	0.13
14	0.08	0.13	0.04	0.12	0.10	0.06	0.08	0.18
	0.08	0.07	0.02	0.06	0.03	0.00	0.03	0.00
	0.05	0.04	0.04	0.03	0.11	0.06	0.07	0.03
	0.04	0.04	0.05	0.01	0.06	0.03	0.03	0.01
	5.83	7.32	4.18	5.84	2.43	3.55	5.95	8.03

MOD NUMBER	17	18	19	20	21	22	23	24
YIELDS (Stage II), W% of mf coal								
	0.05	0.05	0.04	0.04	0.04	0.02	0.02	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.11	0.11	0.08	0.08	0.08	0.05	0.04	0.01
	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00
	0.20	0.21	0.15	0.15	0.16	0.09	0.08	0.02
	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.00
10	0.14	0.14	0.10	0.10	0.11	0.07	0.07	0.02
10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12	0.10	0.10	0.08	0.07	0.07	0.04	0.04	0.01
12	0.03	0.03	0.02	0.02	0.02	0.02	0.03	0.01
1L-CYCLOPENTANE	0.03	0.03	0.03	0.03	0.03	0.02	0.00	0.01
HEXANE	0.07	0.06	0.05	0.04	0.05	0.03	0.02	0.02
14	0.05	0.05	0.04	0.04	0.03	0.02	0.03	0.01
	0.00	0.00	0.00	0.02	0.00	0.00	0.05	0.01
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	1.09	0.99	0.71	0.76	0.64	0.35	0.32	0.10

DETAILED GAS NORMALIZED YIELDS

IOD NUMBER

4 9 13 17 21 25

IOD START

08/11/96 08/16/96 08/20/96 08/24/96 08/28/96 09/01/96

ALIZED YIELDS, W% DRY FRESH FEED

1	3.11	2.92	4.12	3.67	2.89	2.14
2	2.33	2.18	2.87	2.72	2.18	1.66
3	1.79	1.64	2.01	1.84	2.02	1.39
4	1.56	1.61	2.99	2.58	1.63	1.53
5	0.72	0.51	1.77	1.63	0.79	0.71
6-C7	0.05	0.05	0.30	0.30	0.23	0.05