STA 4 <div style="border: 1px solid black; border-radius: 50%; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 5px;"> <div style="border: 1px solid black; border-radius: 50%; width: 15px; height: 15px; display: flex; align-items: center; justify-content: center;">13</div> </div> MAY 03 1995	ENGINEERING DATA TRANSMITTAL	Ave 5/3/95 Page 1 of 21 1. EDT 609627
--	-------------------------------------	---

2. To: (Receiving Organization) Distribution	3. From: (Originating Organization) WRAP 1 Startup	4. Related EDT No.: n/a
5. Proj./Prog./Dept./Div.: W-026	6. Cog. Engr.: B.A. Mayancsik	7. Purchase Order No.: n/a
8. Originator Remarks: N/A		9. Equip./Component No.: n/a
		10. System/Bldg./Facility: n/a
11. Receiver Remarks:		12. Major Assm. Dwg. No.: n/a
		13. Permit/Permit Application No.: n/a
		14. Required Response Date: n/a

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	WHC-SD-W026-PLN-007		0	WRAP Module 1 Treatment Plan	E	2		

16. KEY					
Approval Designator (F)		Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-5, Sec. 12.7)		1. Approval	4. Review	1. Approved	4. Reviewed no/comment
		2. Release	5. Post-Review	2. Approved w/comment	5. Reviewed w/comment
		3. Information	6. Dist. (Receipt Acknow. Required)	3. Disapproved w/comment	6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)										(G)	(H)
Reason	Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(J) Name	(K) Signature	(L) Date	(M) MSIN	Reason	Disp.
1	1	Cog. Eng. B.A. Mayancsik	<i>B.A. Mayancsik</i>	5-1-95	3-01	Central Files			L8-04	3	
1	1	Cog. Mgr. R.J. Bottenus	<i>R.J. Bottenus</i>	5/1/95	3-01	OSTI (2 copies)			L8-07	3	
		QA.									
		Safety.									
1	1	Env. E.M. Greager	<i>E.M. Greager</i>	5/2/95	6-20						
3		A.R. Sherwood			H6-20						
3		W.E. Toebe			H6-20						
3	1	A.G. Miskho	<i>A.G. Miskho</i>		H6-20						
3		D.E. McKenney			N3-13						

18. <i>B.A. Mayancsik</i> B.A. Mayancsik Signature of EDT Originator Date 5-1-95	19. <i>R.J. Bottenus</i> R.J. Bottenus Authorized Representative Date 5/1/95 for Receiving Organization	20. <i>R.J. Bottenus</i> R.J. Bottenus Cognizant Manager Date 5/1/95	21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments
---	---	---	---

BD-7400-172-2 (04/94) GEF097

INSTRUCTIONS FOR COMPLETION OF THE ENGINEERING DATA TRANSMITTAL

(USE BLACK INK OR TYPE)

<u>BLOCK</u>	<u>TITLE</u>	
(1)*	EDT	● Pre-assigned EDT number.
(2)	To: (Receiving Organization)	● Enter the individual's name, title of the organization, or entity (e.g., Distribution) that the EDT is being transmitted to.
(3)	From: (Originating Organization)	● Enter the title of the organization originating and transmitting the EDT.
(4)	Related EDT No.	● Enter EDT numbers which relate to the data being transmitted.
(5)*	Proj./Prog./Dept./Div.	● Enter the Project/Program/Department/Division title or Project/Program acronym or Project Number, Work Order Number or Organization Code.
(6)*	Cognizant Engineer	● Enter the name of the individual identified as being responsible for coordinating disposition of the EDT.
(7)	Purchase Order No.	● Enter related Purchase Order (P.O.) Number, if available.
(8)*	Originator Remarks	● Enter special or additional comments concerning transmittal, or "Key" retrieval words may be entered.
(9)	Equipment/Component No.	● Enter equipment/component number of affected item, if appropriate.
(10)	System/Bldg./Facility	● Enter applicable system, building or facility number, if appropriate.
(11)	Receiver Remarks	● Enter special or additional comments concerning transmittal.
(12)	Major Asm. Dwg. No.	● Enter applicable drawing number of major assembly, if appropriate.
(13)	Permit/Permit Application No.	● Enter applicable permit or permit application number, if appropriate.
(14)	Required Response Date	● Enter the date a response is required from individuals identified in Block 17 (Signature/Distribution).
(15)*	Data Transmitted	
(A)*	Item Number	● Enter sequential number, beginning with 1, of the information listed on EDT.
(B)*	Document/Drawing No.	● Enter the unique identification number assigned to the document or drawing being transmitted.
(C)*	Sheet No.	● Enter the sheet number of the information being transmitted. If no sheet number, leave blank.
(D)*	Rev. No.	● Enter the revision number of the information being transmitted. If no revision number, leave blank.
(E)	Title or Description of Data Transmitted	● Enter the title of the document or drawing or a brief description of the subject if no title is identified.
(F)*	Approval Designator	● Enter the appropriate Approval Designator (Block 15). Also, indicate the appropriate approvals for each item listed, i.e., SQ, ESQ, etc.
(G)	Reason for Transmittal	● Enter the appropriate code to identify the purpose of the data transmittal (see Block 16).
(H)	Originator Disposition	● Enter the appropriate disposition code (see Block 16).
(I)	Receiver Disposition	● Enter the appropriate disposition code (see Block 16).
(16)	Key	● Number codes used in completion of Blocks 15 (G), (H), and (I), and 17 (G), (H) (Signature/Distribution).
(17)	Signature/Distribution	
(G)	Reason	● Enter the code of the reason for transmittal (Block 16).
(H)	Disposition	● Enter the code for the disposition (Block 16).
(J)	Name	● Enter the signature of the individual completing the Disposition 17 (H) and the Transmittal.
(K)*	Signature	● Obtain appropriate signature(s).
(L)*	Date	● Enter date signature is obtained.
(M)*	MSIN	● Enter MSIN. Note: If Distribution Sheet is used, show entire distribution (including that indicated on Page 1 of the EDT) on the Distribution Sheet.
(18)	Signature of EDT Originator	● Enter the signature and date of the individual originating the EDT (entered prior to transmittal to Receiving Organization). If the EDT originator is the cognizant engineer, sign both Blocks 17 and 18.
(19)	Authorized Representative for Receiving Organization	● Enter the signature and date of the individual identified by the Receiving Organization as authorized to approve disposition of the EDT and acceptance of the data transmitted, as applicable.
(20)*	Cognizant Manager	● Enter the signature and date of the cognizant manager. (This signature is authorization for release.)
(21)*	DOE Approval	● Enter DOE approval (if required) by signature or control number that tracks the approval to a signature, and indicate DOE action.

*Asterisk denote the required minimum items check by Configuration Documentation prior to release; these are the minimum release requirements.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

RELEASE AUTHORIZATION

Document Number: WHC-SD-W026-PLN-007, REV.0

Document Title: WRAP Module 1 Treatment Plan

Release Date: May 3, 1995

**This document was reviewed following the
procedures described in WHC-CM-3-4 and is:**

APPROVED FOR PUBLIC RELEASE

WHC Information Release Administration Specialist:

Kara M. Broz

May 3, 1995

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy. Available in paper copy and microfiche. Printed in the United States of America. Available to the U.S. Department of Energy and its contractors from:

U.S. Department of Energy
Office of Scientific and Technical Information (OSTI)
P.O. Box 62
Oak Ridge, TN 37831
Telephone: (615) 576-8401

Available to the public from:

U.S. Department of Commerce
National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161
Telephone: (703) 487-4650

SUPPORTING DOCUMENT		1. Total Pages 22
2. Title WRAP Module 1 Treatment Plan	3. Number WHC-SD-W026-PLN-007	4. Rev No. 0
5. Key Words WRAP 1, waste, plan, treatment, RCRA, WIPP	6. Author Name: B.A. Mayancsik Signature Organization/Charge Code 87370/A4GA1	
7. Abstract <p>This document provides the methodology to treat waste in the Waste Receiving and Processing Module 1 facility to meet the Resource Conservation and Recovery Act (RCRA) land disposal restrictions or the Waste Isolation and Pilot Plant waste acceptance criteria. This includes Low-Level Mixed Waste, Transuranic Waste, and Transuranic Mixed Waste.</p>		
		8. RELEASE STAMP <div style="border: 1px solid black; padding: 5px; text-align: center;"> OFFICIAL RELEASE BY WHC DATE MAY 03 1995 </div>

RECORD OF REVISION

(1) Document Number

WHC-SD-W026-PLN-007

Page 1

(2) Title

WRAP Module 1 Treatment Plan

CHANGE CONTROL RECORD

(3) Revision

(4) Description of Change - Replace, Add, and Delete Pages

Authorized for Release

(5) Cog. Engr.

(6) Cog. Mgr. Date

0 RS

(7) Initial release EDT-609627 5/3/95

BL Magness

R. J. Bellina 5/1/95

WRAP MODULE 1 TREATMENT PLAN

B.A. Mayancsik

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

THIS page left intentionally BLANK

Table of Contents

1.0	PURPOSE	5
2.0	SCOPE	5
3.0	REGULATORY REQUIREMENTS	6
3.1	HAZARDOUS WASTE REQUIREMENTS	6
3.2	WIPP REQUIREMENTS	6
4.0	TREATMENT SUMMARY	7
4.1	CONCENTRATION-BASED TREATMENT STANDARDS	7
4.2	TECHNOLOGY-BASED TREATMENT STANDARD	7
4.3	COMBINATION OF TREATMENT STANDARDS	8
5.0	WASTE CATEGORY SUMMARY	8
5.1	LISTED WASTES	8
5.1.1	Dangerous Waste Sources	8
5.1.2	Discarded Chemicals	9
5.2	CALIFORNIA LIST WASTE	9
5.3	CHARACTERISTIC WASTE	10
5.4	WASTE MIXTURES	13
5.5	TRANSURANIC WASTE	13
5.5.1	Particulate Waste	13
5.5.2	Liquid Waste	14
5.5.3	Ignitable, Corrosive, and Reactive Waste	14
5.5.4	Pyrophoric Waste	14
6.0	WRAP MODULE 1 TREATMENT SUMMARY	14
6.1	DEACTIVATION	15
6.1.1	Absorption	15
6.1.2	Neutralization	15
6.1.3	Controlled Reaction with Water	16
6.1.4	Cementing or Grouting	16
6.2	STABILIZATION	16
6.2.1	Cementing or Grouting	16
6.2.2	Sealing	18
6.2.3	Absorption	18
6.3	AMALGAMATION	18
7.0	WASTE ANALYSIS	18
8.0	HEALTH AND SAFETY	19
9.0	RECORDKEEPING	19
10.0	REFERENCES	20

THIS PAGE LEFT INTENTIONALLY BLANK

1.0 PURPOSE

The purpose of this document is to list the treatments that are performed in the Waste Receiving and Processing (WRAP) Module 1 facility and identify regulatory requirements and standards applicable to these treatments.

2.0 SCOPE

Treatments are performed to meet either Resource Conservation and Recovery Act (RCRA) land disposal restrictions or Waste Isolation Pilot Plant (WIPP) acceptance criteria. The treatments performed in WRAP Module 1 include deactivation (absorption, neutralization, controlled reaction with water, and cementing or grouting) stabilization (cementing or grouting, sealing, and absorption), amalgamation, and immobilization (WIPP terminology). Mixed waste (MW) expected to be treated include low-level waste (LLW) and transuranic (TRU) waste. Some forms of TRU waste will also be treated to meet WIPP criteria. The source of waste treated in WRAP Module 1 is mainly from the retrieved waste stream but newly generated radioactively contaminated waste is not excluded from treatment. Non-radioactive dangerous waste is not treated in WRAP Module 1.

The retrieved waste stream that is processed through WRAP Module 1 was initially generated during the 1970's and 1980's. Recordkeeping requirements on the waste have changed since then. Because of this, records may not contain detailed characterization information to allow for proper treatment of the waste. Also, it may not be clear what mixtures or combinations of hazardous constituents are expected to be found in the waste. Prior to treatment, review of process knowledge and/or additional analysis to properly characterize the waste will be performed. These results are evaluated and the proper treatment and/or a series of treatments (treatment train) is then identified for each stream. Treatments will be performed only when all the treatment standards are identified or in the case of an emergency.

This document is meant to be used as a guide for treating waste. Other treatments than those specified in this document may be considered and evaluated on a case-by-case basis. It should be noted that retrieved wastes will not be designated with any of the listed codes (U, P, or F) unless there is sufficient process knowledge to make the determination that the waste is indeed a discarded chemical or a spent solvent.

3.0 REGULATORY REQUIREMENTS

This section provides a summary of the regulations or requirements that drive the treatment of waste, either hazardous (i.e., MW) for disposal on site or TRU waste for disposal in the WIPP.

3.1 HAZARDOUS WASTE REQUIREMENTS

The basic framework for land disposal restrictions was first established under the Hazardous and Solid Waste Amendments of 1984 (HSWA). The restrictions for solid waste management activities are further governed under RCRA. The basic components of the land disposal restrictions require that for each hazardous waste (this covers MW), the U.S. Environmental Protection Agency (EPA) must establish treatment standards that are protective of human health and the environment when the wastes are land disposed. The EPA has identified the requirements for restrictions in 40 Code of Federal Regulations (CFR) Part 268, *Land Disposal Restrictions* (40 CFR 268). *RCRA Land Disposal Restrictions: A Guide to Compliance* (McCoy 1995) is a good reference document that can be used to evaluate the waste characterization data and determine the treatment technology.

Land disposal restrictions apply to all characteristic and listed RCRA hazardous wastes. When evaluating the treatability of certain characteristic waste, consideration must be given to any additional underlying hazardous constituents that may be found in the waste. The treatment standards, for the most part, are concentration-based. If the constituent concentrations for the waste fall below those specified in 40 CFR 268.40 and/or 268.48 for underlying hazardous constituents, the waste can be land disposed without being treated. If the concentration exceed these limits, then the waste must be treated before disposal.

3.2 WIPP REQUIREMENTS

The EPA is expected to grant the Department of Energy (DOE) a no-migration variance for the land disposal of untreated, restricted TRU MW at the WIPP facility. Although WIPP will have this variance which basically exempts them from land disposal restrictions, they do require that some characteristic wastes and certain waste forms not regulated by RCRA be treated to meet performance criteria for the repository. Requirements that identify waste treatment and/or disposal criteria are covered in the *Waste Acceptance Criteria for the Waste Isolation Pilot Plant* (WIPP WAC), DOE/WIPP-069 (DOE 1991).

4.0 TREATMENT SUMMARY

Land disposal restrictions require that some wastes be treated to meet concentration-based treatment standards and other waste be treated using technology-based standards before land disposal. Standards have been identified for both wastewaters and nonwastewaters.

Wastewaters are wastes that contain less than 1% by weight total organic carbon (TOC) and less than 1% by weight total suspended solids (TSS), with the following exception applicable to Hanford waste: F001, F002, F003, F004, F005 wastewaters are solvent-water mixtures that contain less than 1% by weight TOC or less than 1% by weight total F001, F002, F003, F004, F005 solvent constituents listed in 40 CFR 268.40. Nonwastewaters are simply those wastes that do not meet the criteria for wastewaters.

The following sections provide a summary of these treatment standards.

4.1 CONCENTRATION-BASED TREATMENT STANDARDS

Concentration-based standards are derived from EPA's evaluation of potentially applicable technologies and the selection of one or more best demonstrated available technology (BDAT). If the concentration of the constituent in the waste falls below the limits specified for the treatment standard, then the waste can be land disposed without treatment. If the constituent concentration is above the limit, then the waste must be treated. The constituent concentration of the subsequent treatment residue or extract is then compared against the treatment standard. If the concentration falls below the limit, then the waste can be land disposed. If the concentration is above the limit, then the waste must be treated again until it falls below the established limits. The concentrations are provided in 40 CFR 268.40 and/or 268.48 for underlying hazardous constituents. Although wastes subject to treatment standards based on concentration limits can be treated by any technology, the concentration of hazardous constituents in any of the treatment wastes or residues cannot be higher than those obtained using BDAT.

4.2 TECHNOLOGY-BASED TREATMENT STANDARD

Some treatment standards are based on the use of a required technology. This type of standard is typically used when it is impossible to establish concentration limits. This occurs mainly when there are no acceptable analytical methods to quantify the hazardous waste constituent. Because of this, the agency may have data indicating the waste will be successfully treated by a certain type of technology. In these circumstances, a specific technology is required for treating the hazardous wastes. As long as the wastes are treated by this technology, the treatment residues can be land disposed without further monitoring.

4.3 COMBINATION OF TREATMENT STANDARDS

There may be instances where a hazardous waste must meet a combination of the treatments identified above or multiple concentration-based treatment standards. This can occur due to the fact that there is an underlying hazardous constituent in a characteristic waste, a waste is both characteristic and listed, or there is a mixture of hazardous constituents within a waste that require different treatments. These types of waste are treated using a treatment train philosophy where they are run through all the identified treatments until it meets all the disposal requirements that are specified for each treatment.

5.0 WASTE CATEGORY SUMMARY

This section provides a summary of the waste categories as they apply to WRAP Module 1. These include listed waste (spent solvents and discarded chemicals), California list waste, characteristic waste, waste mixtures, and TRU waste.

5.1 LISTED WASTES

Listed wastes as defined in 40 CFR 261, *Identification and Listing of Hazardous Waste* (40 CFR 261) consists of dangerous waste sources and discarded chemicals. The following sections summarizes each of these categories. Treatments for listed wastes can be either concentration-based or technology-based. For concentration-based standards, if the constituent concentrations for the waste (or treatment residue - but not an extract of the waste or residual) fall below those specified in 40 CFR 268.40, the waste can be land disposed without being treated. If they exceed these limits, the waste must be treated prior to land disposal.

5.1.1 Dangerous Waste Sources

The dangerous waste sources applicable to the Hanford Site are spent solvents designated with hazardous waste numbers F001, F002, F003, F004, and F005. Although these spent solvents have been generated on the Hanford Site (Mayancsik 1995), these codes will not be applied to the retrieved waste stream unless there is sufficient process knowledge to make this determination.

Typical BDATs for spent solvents are incineration for nonwastewaters and biological treatment or wet-air oxidation followed by carbon adsorption for wastewaters. Since these treatments fall outside the scope of treatments performed in WRAP Module 1, spent solvent wastes found in the retrieved waste stream are repackaged for treatment elsewhere. Since these wastes are organic

and do not form insoluble precipitates, they generally are not candidates for stabilization.

5.1.2 Discarded Chemicals

Discarded chemical wastes include any wastes having hazardous waste numbers beginning with U or P. Although discarded chemical wastes have been generated on the Hanford Site, these waste codes will not be applied to the retrieved waste stream unless there is sufficient process knowledge to make the determination that the waste is indeed a discarded chemical.

Typical U and P listed waste that may be found in the retrieved waste stream are the following: U002, U019, U031, U044, U056, U080, U122, U133, U134, U151, U154, U159, U161, U165, U167, U168, U211, U226, U227, U228, U239, P012, P015, and P120 (Mayancsik 1995). The BDAT for most organic nonwastewaters is incineration. Typically, the BDAT for most metal/inorganic nonwastewaters is high-temperature metal recovery/stabilization. Biological treatment and/or chemical precipitation is the BDAT for all wastewaters.

Of the codes listed above, U134 requires neutralization and can be treated in WRAP Module 1. If a U or P waste code is assigned to a waste received from retrieval, one of two things can occur. The first is that the waste may be treated using a stabilization method (i.e., cementing) if there is sufficient knowledge that the waste can meet the concentration limits identified for that constituent. If the listed waste is treated through stabilization and meets the land disposal restriction requirements, the waste must be disposed in a RCRA Subtitle C hazardous waste land disposal unit. The second thing that may occur is that the waste is repackaged for treatment elsewhere. This could occur if there is knowledge that the treated waste can not meet the treatment standards through stabilization.

5.2 CALIFORNIA LIST WASTE

The original purpose of the California list was to establish a safety net to catch hazardous wastes that were not otherwise covered by the land disposal restrictions. Table 5-1 provides a listing of the constituents of concern along with the concentration limits that trigger land disposal restrictions. If the constituents exceed those concentrations listed in the table, then the waste must be treated to meet land disposal restrictions.

TABLE 5-1 CALIFORNIA LIST CONSTITUENTS AND THEIR PROHIBITION LEVELS	
Constituent ¹	Concentration (ml/L)
Liquids with Nickel	134
Liquid with Thallium	130
Liquids with PCBs	50 ppm
Wastes containing HOCs	1,000 mg/kg
¹ Halogenated organic compounds (HOCs) are regulated as solids and liquids.	

The liquids containing nickel and thallium can be treated through stabilization while the PCB waste and the HOCs are repackaged for treatment (incineration) elsewhere. A listing of the HOCs can be found in 40 CFR 268 Appendix III. Note: Some of the constituents originally on the California list are now covered by treatment standards and are therefore not included in the table.

5.3 CHARACTERISTIC WASTE

Characteristic wastes include any wastes having the codes D001-D043. The following table provides a break-down of these codes into the specific categories.

TABLE 5-2 CHARACTERISTIC WASTE SUMMARY	
Waste Code	Category
D001	Ignitable
D002	Corrosive
D003	Reactive
D004-D011	Toxicity Characteristic Metals
D012-D017	Toxicity Characteristic Pesticides
D018-D043	Organic Toxicity Characteristic

For some of the characteristic wastes, subcategories have to be identified and considered when determining the appropriate treatment technology. One example of subcategories is as follows: for reactive waste, the subcategories are

reactive sulfides, explosives, other reactives, water reactives, and reactive cyanides.

Typical characteristic wastes generated on the Hanford Site in the radioactive waste stream fall into all of the categories listed in Table 5-2 except toxicity characteristic pesticides. Specific codes that have been identified within the retrieved waste stream include D001, D002, D003, D004, D005, D006, D007, D008, D009, D011, D018, D019, D022, D035, and D040. Treatments for the characteristic wastes can be either concentration-based, technology-based, or, in the case of underlying hazardous constituents for some characteristic waste, a combination there-of. Table 5-3 lists the codes representative of the retrieved waste and the specific treatments for each.

TABLE 5-3 TREATMENTS FOR CHARACTERISTIC WASTES			
Waste Code	Waste Description	Treatment	
		Wastewater	Nonwastewater
D001	high total organic carbon	n/a	CMBST* (incineration)
	ignitable liquids, low TOC nonwastewater	n/a	DEACT* (incineration, render it nonliquid by absorption) and meet universal treatment standards
	ignitable reactives	n/a	DEACT* (controlled reaction with water, stabilization, incineration) and meet universal treatment standards
	ignitable oxidizers	DEACT* (incineration) and meet universal treatment standards	DEACT* (incineration) and meet universal treatment standards
D002	pH ≤ 2.0 or ≥ 12.5	DEACT* (neutralization) and meet universal treatment standards	DEACT* (neutralization) and meet universal treatment standards
D003	other than reactive cyanides	DEACT* (incineration)	DEACT* (incineration)
D004	arsenic (both EP and TCLP hazardous)	chemical precipitation	vitrification
D005	barium (both EP and TCLP hazardous)	chemical precipitation	stabilization
D006	cadmium (both EP and TCLP hazardous)	chemical precipitation	stabilization
	cadmium-containing batteries	n/a	RTHRM*
D007	chromium (both EP and TCLP hazardous)	chromium reduction followed by chemical precipitation	chromium reduction followed by stabilization
D008	lead (both EP and TCLP hazardous)	stabilization	incinerated then stabilized
	radioactive lead solids	n/a	MACRO*

	lead acid batteries	n/a	RLEAD*
D009	elemental mercury	n/a	AMLGM*
Dy010	selenium (both EP and TCLP hazardous)	chemical precipitation with sulfides	stabilization
D011	silver (both EP and TCLP hazardous)	chemical precipitation	solidification
D018	benzene	biological treatment and/or chemical precipitation	incineration and meet universal treatment standards
D019	carbon tetrachloride	biological treatment and/or chemical precipitation	incineration and meet universal treatment standards
D022	chloroform	biological treatment and/or chemical precipitation	incineration and meet universal treatment standards
D035	methyl ethyl ketone	biological treatment and/or chemical precipitation	incineration and meet universal treatment standards
D040	trichloroethylene	biological treatment and/or chemical precipitation	incineration and meet universal treatment standards
<p>*technology-based standard CMBST: combustion DEACT: deactivation AMLGM: amalgamation RLEAD: thermal recovery MACRO: macroencapsulation RTHRM: thermal recovery</p> <p>EP: extraction procedure TCLP: toxicity characteristic leaching procedure</p>			

Other characteristic waste than those identified in the table may be treated in WRAP Module 1 provided they fall within the bounds of the treatments specified for the facility. As with the listed waste, the metals may be treated by other treatment methods (i.e., cementing). As long as the extract meets the land disposal restriction requirements and does not contain a listed waste, the waste can be land disposed in a Subtitle D nonhazardous waste landfill after treatment. Wastes that can not be treated in WRAP Module 1 are repackaged and sent for treatment elsewhere.

Some characteristic wastes have listed waste counterparts (i.e., lead is D008 but can also be part of compounds having waste codes such as P110, U144, U145, and U146). These wastes will have both the characteristic waste code and the listed waste code if the waste meets the definition, in this case, of a discarded chemical. The treatment standard for the waste code listed in 40 CFR 261, subpart D will operate in lieu of the standard for the waste code under 40 CFR 261, subpart C, provided that the treatment standard for the listed waste includes a treatment standard for the constituent that causes the waste to exhibit the characteristic. Otherwise the waste must meet the treatment standards for all applicable listed and characteristic waste codes. Since the treatment standards can be different or more stringent for the listed waste as opposed to the characteristic waste, it is important that care be taken to (1) properly designate the waste and only identifying the waste as listed if there is sufficient process knowledge to do so and (2) in using this information, identify the proper treatment standard(s) for the waste.

If a toxicity characteristic metal (D004 - D011) is also designated as D001, D002, or toxicity characteristic organic, the waste would be treated to meet the universal treatment standards instead of the metal treatment standards. Treatment of the characteristic would also have to occur to meet all of the land disposal restrictions.

5.4 WASTE MIXTURES

Land disposal restriction regulations become complicated when the waste matrix consists of a mixture of more than one regulated waste. A series of treatments, or treatment train, must then be performed on the waste prior to land disposal. The following general rules are applied to resolve any issues relating to waste mixtures.

At the point of disposal, the waste must comply with the treatment standards for each listed waste in the mixture. If the mixture is also characteristic and its treatment standard is not superseded by a listed waste standard, the characteristic treatment standard must also be met. When identifying the order of the treatments (if more than one applies), consideration must be given as to what treatments are more restrictive, with the more restrictive treatment being performed last.

The effective date for the treatment standard should always be checked. If the effective date has not passed, the treatment standard does not apply and the waste can be land disposed.

The more specific and the more stringent requirements apply if an overlap exists between different treatment standards. When a standard is more specific but less stringent, then the more specific standard takes place.

5.5 TRANSURANIC WASTE

Transuranic wastes are treated to meet WIPP waste acceptance criteria. The following sections summarize the waste forms requiring treatment and the treatments for each.

5.5.1 Particulate Waste

Particulate waste that is less than 10 microns in diameter and makes up greater than 1% by weight of the waste matrix or if it is less than 200 microns and makes up greater than 15% by weight of the waste matrix must be immobilized. The process for immobilization of these particulates is consistent with the stabilization process identified in section 6.2.

Documented evidence or analysis shall exist showing the stability and durability of the waste during the period between packaging and emplacement in the WIPP. As a minimum, generators will provide a letter report supporting

their conclusion on compliance with this criteria. (Note: durability is the resistance of waste particles to abrade into smaller particles during anticipated handling and transportation; and stability is the resistance of a waste to degrade into smaller particles as a function of time.) These wastes are only stabilized to meet WIPP acceptance criteria and therefore are not required to meet any testing requirements for RCRA land disposal restrictions.

5.5.2 Liquid Waste

Liquid waste greater than 1% by volume of the waste container are restricted from disposal at WIPP. Any liquid waste, therefore, must be solidified prior to disposal. The process for solidification of these liquids is consistent with the process identified in section 6.2. Documented evidence such as nondestructive examination shall exist showing the stability of the waste and free liquids less than 1% by volume of the waste container. These wastes are only solidified to meet WIPP acceptance criteria and therefore are not required to meet any testing requirements for RCRA land disposal restrictions.

5.5.3 Ignitable, Corrosive, and Reactive Waste

Although WIPP, in all likelihood, will be granted a no-migration variance for the land disposal of untreated, restricted TRU MW at the WIPP facility, they do require that ignitable, corrosive liquids, and reactive waste be treated prior to land disposal. Treatment of these characteristic wastes within WRAP Module 1 to meet WIPP disposal requirements will be consistent with the treatment technologies identified in sections 6.1 and/or 6.2. Evidence such as pH for corrosive material shall exist documenting the change in characteristic of the waste. Since WIPP is expected to be granted a no migration variance, additional treatment to meet any universal treatment standard is not required.

5.5.4 Pyrophoric Waste

Radionuclides in a pyrophoric form are limited to less than 1% by weight in each waste package sent to WIPP for disposal. Pyrophoric material in excess of this amount shall be rendered safe prior to disposal by changing the chemical form of the material through oxidation or mixing and binding it with an inert material. This material will be processed similar to the processes identified in section 6.1. Again, since these wastes are only rendered safe to meet WIPP acceptance criteria, the treated waste is not required to meet any testing requirements for RCRA land disposal restrictions.

6.0 WRAP MODULE 1 TREATMENT SUMMARY

This section provides a summary of the treatments that have been identified to be performed in WRAP Module 1. They include deactivation, stabilization, and amalgamation.

6.1 DEACTIVATION

Deactivation is used to remove the hazardous characteristics of the waste due to its ignitability (D001), corrosivity (D002), and/or reactivity (D003). In general, deactivation is a technology-based treatment standard. When waste is only required to be deactivated using this type of standard, testing of the extract using toxicity characteristic leaching procedure, extraction procedure, or other methods is not required to be performed to meet land disposal restriction requirements. If there are underlying hazardous constituents in the ignitable or corrosive waste, the waste must also meet universal treatment standards associated with each constituent(s) which are generally concentration-based treatment standards. The methods used in WRAP Module 1 for deactivation include absorption, neutralization, controlled reaction with water, and cementing or grouting. The following sections provide a summary of these methods.

6.1.1 Absorption

Ignitable waste that can be deactivated in WRAP Module 1 include wastes that are liquid, have a low total organic carbon content ($>1\%$ but $<10\%$), and a flashpoint $<60^{\circ}\text{C}$ (140°F). These wastes are deactivated by absorption to render the waste non-liquid. Absorbent material that can be used include polyacrylates, polypropylene, polymer type, superabsorbent polymer, cellulose, or any other absorbent material approved in the *Hanford Site Solid Waste Acceptance Criteria*, WHC-EP-0063 (WHC 1993) or *TRU Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, WIPP-DOE-069 (DOE 1991) for disposal. If the waste contains underlying hazardous constituents or is listed and the absorption process does not meet the universal treatment standards or standards associated with the listed waste, it must also be treated to meet the treatment standard specified for that constituent(s) or listed waste. The absorption portion of the treatment process is inspected visually to verify compliance to the technology-based treatment standard. If the treatment process is completed after the addition of the absorbent and is ready for disposal, a paint filter test may be performed to verify that the waste no longer contains free liquids.

6.1.2 Neutralization

Corrosive wastes that have a $\text{pH} \leq 2$ and/or ≥ 12.5 are deactivated by neutralization. Typical bases used as neutralizing agents include sodium hydroxide, calcium hydroxide, or calcium carbonate. Calcium hydroxide or calcium carbonate may be better choices because the resulting salts are generally less soluble than the sodium salts. Of these two, calcium carbonate offers the advantage in that many carbonate metal salts are insoluble and the carbonates are compatible with portland cement. Neutralizing with calcium carbonate can cause frothing due to evolution of carbon dioxide (Cullinane 1986). Typical acids that can be used to neutralize bases are hydrochloric

acid and sulfuric acid (Corbitt 1990). Titration curves based on the ions found may have to be prepared to determine the quantity and concentration of the neutralizing chemical.

During and after the neutralizing process, the pH is monitored to obtain and maintain a target pH range between 4 and 8. If the acid or caustic contains any underlying hazardous constituent, then the waste will have to be further treated to meet the treatment standards for that particular hazardous constituent. Once the liquid waste is neutralized, the waste is stabilized to meet disposal criteria which restricts free liquids from land disposal. The stabilization process is consistent with the methods discussed in section 6.2.

6.1.3 Controlled Reaction with Water

Controlled reaction with water is used to deactivate reactive material such as sodium metal. After completing this procedure, the resultant waste matrix is visually inspected to verify compliance. The appearance of the sodium material should no longer be a shinney, silvery grey but should now be dull. The matrix may also be tested for reactivity using field screening methods.

6.1.4 Cementing or Grouting

Cementing or grouting is used to deactivate reactive ignitables consisting of metal fines and radioactive pyrophorics or other corrosive material. These types of waste are deactivated by mixing and binding it with an inert material. The inert material generally used is portland cement. An optimum mix that can be used as a base case is as follows: water/cement weight ratio of 0.7 and 3% total weight % of bentonite (Keith 1986).

The resultant matrix is visually inspected for free liquids, stability, and durability after the material has cured. (Note: durability is the resistance of waste particles to abrade into smaller particles during anticipated handling and transportation; and stability is the resistance of a waste to degrade into smaller particles as a function of time.) Since this is a treatment technology and there are no other hazardous constituents, no additional testing to meet RCRA are required.

6.2 STABILIZATION

Stabilization methods used at WRAP Module 1 include cementing or grouting, sealing, and absorption. The following subsections discuss these various stabilization methods.

6.2.1 Cementing or Grouting

Particulates and/or liquid waste containing hazardous constituents may be cemented or grouted in WRAP Module 1 to meet either RCRA land disposal restrictions or WIPP disposal criteria. These types of waste are stabilized

by mixing and binding it with an inert material. The inert material generally used is portland cement. An optimum mix that can be used as a base case is as follows: water/cement weight ratio of 0.7 and 3% total weight % of bentonite (Keith 1986). When dealing with some waste streams such as sludges that may contain an inconsistent or excess liquid content, absorbent may be added to the waste to provide a drier matrix to allow identification of the proper combination of ingredients to ensure a successful stabilization effort.

The resultant matrix is visually inspected for free liquids, stability, and durability after the material has cured. Testing for compliance to land disposal restriction requirements is performed by analyzing the extract using the toxicity characteristic leaching procedure and/or extraction procedure, as appropriate.

Because of the unknowns associated with the retrieved waste stream in so far as the concentration of hazardous constituents or mixture of constituents, treatability testing may need to be performed prior to actual waste treatment to verify that the cementing process will be successful. Some guidelines that could be used in performing treatability testing are as follows:

- o Characterize the waste as well as possible. This should include chemical characteristics, mineral composition, physical properties, and radiological properties.
- o Identify target contaminants and tailor the binder system to low solubility regions of the material of interest.
- o Perform appropriate extraction tests on the untreated waste to serve as a benchmark for subsequent data on the treated waste.
- o Analyze and record pH on the extracts from the untreated waste and treated product.
- o Analyze additives for presence of hazardous constituent. Analyze the mixture of the additive and the waste for the potential for forming a hazardous chemical. Identify critical characteristics of all additives to establish a quality control program. Carefully control and record all additives during the tests. Small variations in additives can greatly affect leachability.
- o When reporting leachate data on treated samples, show the total percent reduction achieved and the extent to which simple dilution has contributed to the reduction.

Other guidelines that are specific to each study can be used, as appropriate.

6.2.2 Sealing

HEPA filters or other waste forms that contain particulates may be required to be sealed to meet WIPP waste acceptance criteria. Sealing agents that can be used are epoxy, silicone, and urethane compounds. Once the waste forms are sealed, they are visually inspected to ensure proper coverage and compliance to the WIPP waste acceptance criteria.

6.2.3 Absorption

Free liquids must be absorbed prior to land disposal. Absorbent material that can be used include polyacrylates, polypropylene, polymer type, superabsorbent polymer, cellulose, or any other absorbent material approved in the *Hanford Site Solid Waste Acceptance Criteria*, WHC-EP-0063 (WHC 1993), or the *Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, DOE/WIPP-069 (DOE 1991), for disposal. The absorbed waste is visually inspected to verify compliance for land disposal.

6.3 AMALGAMATION

Amalgamation of liquid, elemental mercury (D009) is achieved using inorganic reagents such as copper, zinc, nickel, gold, and sulfur. The resultant matrix is a nonliquid, semi-solid amalgam and is visually inspected to verify compliance. Since amalgamation is a technology-based treatment standard, additional testing or laboratory analysis to show compliance to RCRA requirements is not required.

7.0 WASTE ANALYSIS

Facilities that treat or dispose restricted wastes must have a waste analysis plan in effect describing how and when wastes or treatment residues are tested. The wastes or residues must be tested to determine if they meet treatment standards or prohibition levels. The treatment or disposal facility may rely on generators to provide waste analysis data but must conduct periodic physical and chemical analysis on the streams they received to assure that the appropriate treatment standards will be met.

For wastes with treatment standards expressed as concentrations in the waste extract, the owner or operator of the treatment facility must test the treatment residues or an extract of the residues developed using toxicity characteristic leaching procedure. This testing ensures that the treatment residues or extract meet the applicable treatment standards.

For wastes that are prohibited under 40 CFR 268.32 but are not subject to any treatment standards, the owner or operator of the treatment facility must test the treatment residues according to the testing requirements specified in 40

CFR 268.32. This ensures that the treatment residues comply with the applicable prohibitions.

For wastes with treatment standards expressed as concentrations in the waste, the owner or operator of the treatment facility must test the treatment residues (not the extract of the residues). This ensures that the treatment residues meet the applicable treatment standards.

Sampling and analysis of treatment residue/residual or extract is conducted in the same manner as sampling to characterize waste. The quality assurance and quality control requirements specific to sampling and analysis are listed in the waste analysis plan of the Part B Permit application.

8.0 HEALTH AND SAFETY

The personal protective equipment to be worn during the treatment process shall be listed in the treatment procedure, on the job-specific job hazard analysis, and/or radiation work permit for each treatment activity, as appropriate. A pre-job meeting shall be conducted to discuss the work to be performed, the job hazard analysis, the radiation work permit, and the personal protective equipment requirements. This meeting shall be documented with a roster identifying the attendees.

9.0 RECORDKEEPING AND REPORTING

Two important functions that have specific recordkeeping requirements for the management of land disposal restricted wastes are the generator and the treatment facility. WRAP Module 1 falls under both of these functions and must meet the recordkeeping requirements identified in 40 CFR 268.7, Waste Analysis and Recordkeeping. Typical information retained includes:

- o Waste analysis data and/or supporting data for determining process knowledge, where applicable
- o Corresponding treatment standard for F001-F005, F039, and waste prohibited pursuant to 40 CFR 268.32
 - Applicable wastewater or nonwastewater category
 - Applicable subcategory within a waste code based on waste-specific criteria
 - CFR section where applicable treatment standard appears

- If the treatment is a specific technology, then the 5 letter treatment code (listed in 40 CFR 268.42).
- o Records documenting the verification of waste received from a generator and performed by the treatment facility.

10.0 REFERENCES

- Corbitt, R.A., *Standard Handbook of Environmental Engineering*, McGraw-Hill, INC., New York, New York.
- Cullinane, M.J., et.al., 1986, *Handbook for Stabilization/Solidification of Hazardous Waste*, EPA/540/2-86/001, Environmental Protection Agency, Cincinnati, Ohio.
- DOE, 1991, *TRU Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, WIPP-DOE-069, as amended, Westinghouse Waste Isolation Division, Carlsbad, New Mexico.
- Keith, L.M., 1986, *Test Report from Grout Formulation and Mixing Techniques for Immobilization of Solid Shredded CH-TRU Waste at the WRAP Facility*, Rockwell Hanford Operations, Richland, Washington.
- Mayancsik, B.A., 1995, *WRAP Module 1 Sampling and Analysis Plan*, WHC-SD-W026-PLN-006, as amended, Westinghouse Hanford Company, Richland, Washington.
- McCoy, 1995, *The RCRA Land Disposal Restrictions: A Guide to Compliance*, 1995 Edition, McCoy and Associates, Inc., Lakewood, Colorado.
- 40 CFR 261, 1992, *Identification and Listing of Hazardous Waste*, Title 40, Code of Federal Regulations, Part 261 as amended, U.S. Environmental Protection Agency, Washington DC.
- 40 CFR 268, 1994, *Land Disposal Restrictions*, Title 40, Code of Federal Regulations, Part 268 as amended, U.S. Environmental Protection Agency, Washington DC.
- WHC, 1993, *Hanford Site Solid Waste Acceptance Criteria*, WHC-EP-0063, as amended, Westinghouse Hanford Company, Richland, WA.