Project Progress Report
Fiber Optic and Sensor Technology Support

Prepared For:

Los Alamos National Laboratory
P. O. Box 1663
Los Alamos National Laboratory
Los Alamos, NM 87545
Attn: Lynn R. Vesser

Prepared By:

Electromagnetic Technology Division
Optical Electronic Metrology Division
National Bureau of Standards
Boulder, Colorado 80303

October, 1988

Report No: 724-38-88

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Reviewed and Approved by:

R. A. Kamper, Chief
Electromagnetic Technology Division

This document has been prepared for the use of Los Alamos National Laboratory, Los Alamos, NM. Responsibility for its further use rests with that agency. However, NIST requests that if release to the public is contemplated, such action be taken only after consultation with the Program Information Office at the National Institute of Standards and Technology, Boulder, Colorado.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

September 14, 1988

**UNITED STATES DEPARTMENT OF COMMERCE
National Bureau of Standards**

325 Broadway
Boulder, Colorado 80303 - 3328
(now the National Institute
of Standards and Technology)
Reply to the attention of:

Lynn R. Veaser
Los Alamos National Laboratory
P.O. Box 1663
Los Alamos, NM 87545

Dear Lynn:

This briefly summarizes the work we have done under contract to you during FY88.

The major technical development of the year has been substantial progress in reducing the size of fiber current sensors. Coils of 1 cm diameter or smaller and up to 200 turns can now be produced without linear birefringence reducing the magnitude of the Faraday effect. We believe this technology is now ready for further commercial development and will attempt during the coming year to find a company interested in that work.

We have continued the study of the ZnSe magnetic field sensor started last year. We have found the noise equivalent field to be as small as $200 \text{ nT/Hz}^{1/2}$, at low frequencies, improving slightly with increasing frequencies.

We have continued to investigate the possibility of obtaining fibers that would have better properties for magnetic field or current sensing. This year we undertook a joint project with the University of Southampton and York Technology to produce a fiber from the commercial glass, SF-57. We have tested the first samples from that effort and have received, but not yet tested, the final results. It appears that significant progress was made but that more effort will be required to obtain a useful fiber. We have consulted with other companies regarding similar projects.

We investigated a high speed, polarization independent, switch that could be useful for LANL instrumentation applications. It was provided to us by AT&T for testing prior to being released as a commercial product. We find that it meets their specifications, namely, ns switching speeds between either of two output ports. The device we tested was designed for $1.3 \mu\text{m}$ operation.

We have constructed the fixtures for an experiment to study the Kerr electro-optic effect in optical fiber. This could provide a very convenient sensor for large electric fields. We expect to collaborate on the tests during the first part of FY89.

We have done some exploratory work on electro-optic deflection, with a view to possible infrared streak camera applications. This has focused primarily on deflector design, rather than materials, though we may soon be able to test a design with PLZT.

We have made significant progress, primarily on another contract, in construction techniques that will yield more rugged sensors. These developments should have applications in some LANL field experiments.

We have continued to study bismuth germanate as an electro-optic material. We continue to believe that it is a very good choice for those applications where stability is more important than sensitivity. We have accumulated quite a lot of material properties data and have a completed manuscript in review.

Veesser: September 14, 1988, p. 2

We have continued to provide general support on a wide range of fiber and sensor problems. This has been carried out through visits of NIST staff to LANL and NTS, visits of LANL staff to NIST, numerous phone consultations and participation in technical meetings of particular interest. This year, we participated in and made presentations based on NIST/LANL collaborations at the annual Photonics Workshop, the first DoD Fiber Optics Conference, and the annual SPIE Fiber Sensor Symposium. In addition, we have visited companies and attended other conferences and exhibitions to obtain information on new products and techniques that could be of use to LANL staff.

We have prepared several papers and talks, some of which include LANL authors, as follows:

1. Effect of multiple internal reflections on the stability of electro-optic and magneto-optic sensors, K. S. Lee and G. W. Day, accepted in Applied Optics
2. Stability of birefringent linear retarders (waveplates), P. D. Hale and G. W. Day, accepted in Applied Optics
3. Optical fiber sensors for electromagnetic quantities, G. W. Day, K. S. Lee, A. H. Rose, L. R. Veesser, B. J. Papatheofanis, and H. K. Whitesel, DoD Conf. on Fiber Optics, March 1988, also in Proc. 34th Int. Instrumentation Symposium, Instrument Society of America
4. Optical fiber sensors for the measurement of electromagnetic quantities, A. H. Rose, G. W. Day, K. S. Lee, D. Tang, L. R. Veesser, B. J. Papatheofanis, H. K. Whitesel, Sensors 88, Chicago
5. Faraday effect sensors: the state of the art, G. W. Day and A. H. Rose, SPIE Boston, September 1988
6. Optical, Thermo-optic, Electro-optic, and Photo-elastic properties of bismuth germanate ($\text{Bi}_4\text{Ge}_3\text{O}_{12}$), K. S. Lee, D. C. Conrad, G. W. Day, and P. D. Hale, in review, to be submitted to Applied Optics

Our work with LANL continues to provide us with interesting and challenging problems, many of which are closely related to our efforts in other areas. We hope that the collaboration can continue.

Sincerely,

Gordon W. Day
Optical Electronic Metrology Group (724.02)
Electromagnetic Technology Division