**Central Shops Burning/Rubble Pit 631-6G Additional Sampling and
Monitor Well Installation Report**

by

E. Palmer

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

RECEIVED

JUN 11 1998

OSTI

DOE Contract No. DE-AC09-89SR18035

This paper was prepared in connection with work done under the above contract number with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P. O. Box 62, Oak Ridge, TN 37831; prices available from (423) 576-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

DISCLAIMER

**Portions of this document may be illegible
electronic image products. Images are
produced from the best available original
document.**

**CENTRAL SHOPS BURNING/RUBBLE PIT 631-6G
ADDITIONAL SAMPLING AND
MONITOR WELL INSTALLATION REPORT (U)**

SAVANNAH RIVER SITE

FINAL

FEBRUARY 1995

Prepared for:

**Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina**

Prepared by:

**RUST Environment & Infrastructure
33 Varden Drive
Aiken, South Carolina**

TABLE OF CONTENTS

EXECUTIVE SUMMARY	ES-1
1.0 INTRODUCTION	1
1.1 Previous Sampling/Screening Activities	1
1.2 Project Scope and Objectives	5
1.3 Site Location	8
1.4 Geology and Hydrogeology	9
1.4.1 Geology	9
1.4.1.1 Geology of the SRS	9
1.4.1.2 Unit Geology	13
1.4.2 Hydrostratigraphy	13
1.4.2.1 Hydrostratigraphy of SRS	13
1.4.2.2 Local Hydrostratigraphy	24
2.0 FIELD METHODS	27
2.1 Drilling and Geologic Sampling	27
2.2 Temporary Groundwater Monitoring Well Design, Installation, and Sampling	31
2.2.1 Temporary Groundwater Monitoring Well Construction	31
2.2.2 Well Development	34
2.2.3 Groundwater Sampling	36
2.2.4 Field Permeability Testing	36
2.3 Soil Sampling	38
2.3.1 Soil Sample Locations and Intervals	38
2.3.2 Soil Sampling Procedures	42
2.3.3 Soil Sample Results	43
2.4 Surface Water/Sediment Sampling	50
2.4.1 Sampling Locations and Intervals	50
2.4.2 Sampling Procedures	50

**CENTRAL SHOPS BURNING/RUBBLE PIT 631-6G
ADDITIONAL SAMPLING AND MONITOR WELL
INSTALLATION REPORT (U)**

**WSRC-RP-95-81
FEBRUARY 1995**

2.5	Boring Activity/Problems	52
2.5.1	Temporary Groundwater Monitoring Wells	52
2.5.2	Soil Borings	53
2.5.2.1	Soil Borings Located Within the Estimated Boundary of BRP6G	53
2.5.2.2	Soil Borings Located Outside the Estimated Boundary of BRP6G	54
2.5.2.3	Background Soil Boring Locations	55
2.5.2.4	Soil Boring in Drainage Feature	55
3.0	SUMMARY	56
REFERENCES		REF-1
APPENDICES		

<u>List of Figures</u>	<u>Page</u>
Figure 1	SRS Location Map 2
Figure 2	Location of the Burning/Rubble Pit (BRP6G) in the Central Shops Area of SRS 3
Figure 3	Waste Unit Topographical Map 4
Figure 4	Surface Water/Sediment Sampling and Background Soil Sample Locations 7
Figure 5	General Stratigraphic Column for Coastal Plain Sediments 11
Figure 6	Lithologic and Hydrologic Cross Section HXB-5D to CBR-3D 14
Figure 7	Lithologic and Hydrologic Cross Section CBR-3D, CBR-2D, and CBR-1D 15
Figure 8	Stratigraphic Column of the SRS Area with Hydrologic Nomenclature 16
Figure 9	Profile of P-18 Well Cluster 18
Figure 10	Regional Potentiometric Surface Map Aquifer Unit IIA 19
Figure 11	Regional Potentiometric Surface Map Aquifer Unit IB 21
Figure 12	Regional Potentiometric Surface Map Upper Aquifer Unit IA 22
Figure 13	Regional Potentiometric Surface Map Lower Aquifer Unit IA 23
Figure 14	Potentiometric Surface of the Water Table (Aquifer Unit IIB) in the BRP6G area 25
Figure 15	Potentiometric Surface of the Water Table (Aquifer Unit IIB) at the BRP6G 26
Figure 16	Soil Sampling Depths and Analytical Parameters 41
Figure 17	Location of Pit Boundary 51

List of Tables

Page

Table 1	Summary of Groundwater Monitoring Well Installation	29
Table 2	Coordinates and Elevation Details	32
Table 3	Summary of Well Development	35
Table 4	Groundwater Monitoring Well Hydraulic Conductivity Estimates	39
Table 5	Summary of Soil and Surface Water/Sediment Sampling	44

List of Appendices

- Appendix A Addendum to Chapter 4 of the RFI/RI Work Plan for "Additional Soil Sampling and Groundwater Monitoring Well Installation"
- Appendix B Daily Field Logs
- Appendix C Field Reports for Groundwater Monitoring Wells
- Appendix D Field Reports for Individual Boreholes
- Appendix E Daily Sign-In/Out Logs and Work Zone Entry/Exit Logs
- Appendix F Well Development Forms
- Appendix G Groundwater Sampling Information
- Appendix H Field Permeability Testing
- Appendix I Surface Water/Sediment Sampling Information

List of Acronyms/Abbreviations

%	percent
bls	below land surface
BOP	Bottom of Pit
BRP6G	Central Shops Burning/Rubble Pit 631-6G
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
cm	centimeter
COC	Chain of Custody
EEI	Environmental Exploration Inc.
EMS	Environmental Monitoring Section
EMTC	Environmental Monitoring and Testing Corporation
EPA	United States Environmental Protection Agency
EPD	Environmental Protection Department
ft	feet
g	gram
gal	gallon
GC/MS	Gas Chromatograph/Mass Spectrophotometer
GPR	Ground Penetrating Radar
HNu	trace gas analyzer
HP	WSRC Health Protection
HSA	Hollow Stem Auger
ID	Identification
in.	inch
K	hydraulic conductivity
km	kilometer
lbs	pounds
m	meter
mi	mile
MCL	Maximum Contaminant Level
mm	millimeter
msl	mean sea level
O.D.	outside diameter
OVA	Organic Vapor Analyzer

PAH	polycyclic hydrocarbons
PCBs	polychlorinated biphenyls
ppm	parts per million
PVC	polyvinyl chloride
QA/QC	Quality Assurance/Quality Control
RCRA	Resource Conservation and Recovery Act
RFI	RCRA Facility Investigation
RI	Remedial Investigation
RUST E&I	RUST Environment & Infrastructure
SCDHEC	South Carolina Department of Health and Environmental Control
sec	second
SRS	Savannah River Site
STR	Subcontract Technical Representative
SWMU	Solid Waste Management Unit
TAL	Target Analyte List
TCL	Target Compound List
TDS	Total Dissolved Solids
TIC	Tentatively Identified Compounds
TOC	Total Organic Carbon
TOH	Total Organic Halogens
TSS	Total Suspended Solids
USCS	Unified Soil Classification System
VOC	Volatile Organic Compound
WSRC	Westinghouse Savannah River Company

EXECUTIVE SUMMARY

The Central Shops Burning/Rubble Pit 631-6G (BRP6G) was constructed in 1951 as an unlined earthen pit in surficial sediments for disposal and incineration of potentially hazardous substances, such as metals and organic solvents. The BRP6G was removed from service and backfilled in 1955. Some of the hazardous substances, if present, may have migrated into the surrounding soil and/or groundwater. Because of this possibility, the United States Environmental Protection Agency (EPA) has designated the BRP6G as a Solid Waste Management Unit (SWMU) subject to the Resource Conservation Recovery Act/ Comprehensive Environmental Response, Compensation, and Liability Act (RCRA/CERCLA) process.

Preliminary results from the 1994 unit characterization indicate contamination is present in the RCRA Facility Investigation/Remedial Investigation (RFI/RI) unit soils. As stipulated in the Revision 1 RFI/RI Work Plan (1993a), a downgradient groundwater monitoring well will be installed in the water table aquifer because contamination was detected in the unit soils. To help determine the permanent location for this groundwater monitoring well, three temporary groundwater monitoring wells were installed (one to the west, one to the south, and one to the southeast). Water level data from these wells helped determine the hydraulic gradient of the groundwater. These wells were sampled for volatile organic compounds, and later, one or more of the wells will be chosen as the permanent groundwater monitoring well.

Historical aerial photographs implied that the waste unit was actually larger than previously marked and investigated, and indicated the need for further characterization. Based on this additional information from the historical aerial photographs, an additional sampling plan and monitor well installation plan was devised to incorporate the required groundwater monitoring well installation, surface water and sediment sampling, and further soil boring investigation.

As proposed in the Central Shops 631-6G RFI/RI Work Plan, Additional Sampling and Monitor Well Installation Plan, 12 soil borings and three temporary groundwater monitoring wells were installed and sampled. Surficial soil samples were collected at six locations within the ditch located along the railroad, south of the unit. Also, five surface water/sediment samples were collected from the ephemeral stream southeast of the unit. Slug tests were performed at each well and the data was reduced by the Bouwer-Rice method to calculate hydraulic conductivity. Field activities were performed from November 2, 1994 through December 28, 1994 under

Subcontract AA46326P, Task Order 72. Field activities were overseen by RUST Environment & Infrastructure (RUST E&I) personnel.

Data collected and compiled during the project include: soil and groundwater sample collection, surface water and sediment sampling, visual description and logging of soil samples collected via hand auger and split-spoon sampling, hydraulic slug testing and associated data reduction. Field daily activity logs, geologic logs, soil boring installation reports, well installation reports, well development, and monitoring data are presented in this report.

1.0 INTRODUCTION

The Central Shops Burning/Rubble Pit 631-6G (BRP6G) is located in the Central Shops Area near the center of the Savannah River Site (SRS) (Figure 1). The BRP6G Solid Waste Management Unit (SWMU) is on the southeastern side of a divide that separates the drainage basins of the Pen Branch Creek [approximately 1.6 km (1 mi) to the southeast] and Fourmile Branch [approximately 4 km (2.5 mi) to the northwest] (Figure 2). The ground elevation is approximately 88.4 m [290 feet (ft)] above mean sea level (msl) (Gordon et al., 1987). Surface drainage is southward to an unnamed tributary of Pen Branch.

The BRP6G was constructed as an unlined earthen pit, or pits, dug into surficial sediments that were then filled with various waste materials. The location of the BRP6G is shown in relation to major SRS facilities on Figure 1. The region around the BRP6G is shown on Figure 2 and a map of the BRP6G area is shown on Figure 3.

The BRP6G operated from 1951 through 1955 for disposal and burning of waste materials. The unit consisted of a shallow excavation, approximately 3 m (10 ft). Waste oils, rags, paper, cardboard, plastics, degreasers, wood, rubber, and drummed organic solvents were disposed of in the pit and periodically burned. The volume of waste disposed of at BRP6G was not reported. After disposal activities ceased, the area was covered with soil. The materials incinerated in the burning/rubble pit included potentially hazardous substances, such as organic solvents. Some of the hazardous substances, if present, may have migrated into the surrounding soil, and/or groundwater. Because of this possibility, the United States Environmental Protection Agency (EPA) has designated the BRP6G as a SWMU subject to the Resource Conservation and Recovery Act/Comprehensive Environmental Response, Compensation, and Liability Act (RCRA/CERCLA) process.

1.1 Previous Sampling/Screening Activities

Three groundwater monitoring wells (CBR-1D, CBR-2D, and CBR-3D) were installed at the BRP6G in January/February of 1990. The locations of these wells are shown on Figure 3. The analytical data available for the CBR-series wells indicate that sporadic occurrences of contaminants such as 2,4-dichlorophenoxyacetic acid, 1,1,2,2-tetrachloroethane, beryllium, bis(2-ethylhexyl)phthalate (a common laboratory contaminant), chromium, gross alpha, mercury, silver, tetrachloroethylene, toluene, and trichloroethylene were detected. These occurrences were not

Figure 1. SRS Location Map

WSRC-RP-95-81
FEBRUARY 1995

Figure 2. Location of the Burning/Rubble Pit (BRP6G) in the Central Shops Area of SRS

Figure 3. Waste Unit Topographical Map

confirmed by subsequent sampling and were often contradicted by duplicate sample results. The data suggest a potential increase in concentration from the upgradient to the downgradient wells for chloride, iron, magnesium, nitrate, potassium, and tritium.

Dichloromethane (methylene chloride), a common laboratory contaminant, was detected in 14 of 52 samples. Of the 14 results above the detection limit, only samples collected from CBR-2D during the first quarter of 1991 exceeded the Maximum Contaminant Level (MCL) for dichloromethane.

Ten shallow soil borings were installed in the BRP6G in March/April 1994. The locations of these borings (CS6G-01 through CS6G-10) are shown on Figure 3. The objective of the soil sampling investigation was: (1) to confirm the results of the soil gas survey, (2) to determine if hazardous substances such as metals, polychlorinated biphenyls (PCBs), pesticides, dioxins/furans, or radionuclides are present in the soils at the BRP6G, (3) to collect preliminary soil engineering parameters which will be used to screen potential remedial alternatives, and (4) to characterize any potential sources of contamination at the BRP6G and determine the locations of these sources. Review of the analytical data indicates minimal impact to the environment due to pit operations.

The draft report, "Historical Photographic Search of Central Shops Waste Unit 631-6G, Interim Report" (WSRC, 1994b) describes the search through aerial photographs of the Central Shops Area. These photographs provide representation of the changes in the waste unit over time. The photographic review of the area indicates that the waste unit is not accurately marked in the field, and the location is more likely to extend an additional 30.5 - 38.1 m (100 - 125 ft) further east of the waste unit markers (orange balls). In addition, the ditch immediately adjacent to the eastern most edge of the marked unit runs through what may have been the center of the original waste unit and part of the waste unit is more than likely being used currently (1994) as a laydown yard.

All of the details and documentation associated with the technical oversight of the geologic sampling, soil boring installation, temporary monitor well installation groundwater sampling, and field permeability testing of the project are included in this report.

1.2 Project Scope and Objectives

RUST Environment & Infrastructure (RUST E&I) was retained by Westinghouse Savannah River Company (WSRC) under Subcontract AA46326P to provide geologic and technical oversight for

the BRP6G RCRA Facility Investigation/Remedial Investigation (RFI/RI) Work Plan additional unit assessment activities (Appendix A). Additional sampling was proposed for the RCRA/CERLCA unit (Addendum to Chapter 4 of the RFI/RI Work Plan For Central Shops Burning/Rubble Pit, 631-6G). This proposed sampling was suggested based on information obtained during unit characterization sampling conducted in March and April 1994 (WSRC, 1994a) and recent observations in the historical aerial photography of the area.

The project scope included technical oversight of the installation of 11 soil borings using hollow stem auger (HSA) drilling techniques, one soil boring performed by hand auger, collection of six surficial soil samples within the ditch (downgradient from the pit), and installation of three temporary groundwater monitoring wells (see Figures 3 and 4). Five surface water and sediment samples were also obtained from the ephemeral stream, located approximately 60 m (200 ft) southeast of the pit (Figure 4). The data collected during this study included lithologic detail and soil samples from hand auger and split-spoon samples. Following development of the temporary groundwater monitoring wells, groundwater samples were collected. These wells were also slug tested to gain hydraulic conductivity information. The technical oversight also collected the required Quality Assurance/Quality Control (QA/QC) samples as specified in the proposed additional soil sampling and groundwater monitoring well installation for the BRP6G. The Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) Soil Sample Logbooks and validation materials were used for all sampling documentation.

The RUST E&I technical oversight coordinated with WSRC and the drilling subcontractor to ensure that:

- the materials and equipment were decontaminated prior to use
- the drilling, sampling, and borehole abandonments were conducted in an efficient manner and in accordance with WSRC 3Q5 and the RFI/RI Program Plan (WSRC, 1993a)
- proper records were maintained
- composites of the soil samples taken were screened by WSRC Health Protection (HP) prior to offsite shipment of the analytical samples

The objectives of this field investigation were:

**CENTRAL SHOPS BURNING/RUBBLE PIT 631-6G
ADDITIONAL SAMPLING AND MONITOR WELL
INSTALLATION REPORT (U)**

**WSRC-RP-95-81
FEBRUARY 1995**

Figure 4 Surface Water/Sediment Sampling and Background Soil Sample Locations

- to obtain soil samples for laboratory analysis
- to install three temporary groundwater monitoring wells and collect groundwater samples for laboratory analyses
- to collect surficial soil samples at six locations within the ditch located along the railroad, south of the pit for laboratory analysis
- to collect at least five surface water/sediment samples along the ephemeral stream located approximately 61 m (200 ft) southeast of the pit for laboratory analysis
- to perform field permeability tests (slug tests) on the three temporary groundwater monitoring wells

The depths and analyses for this project are described in the proposed additional soil sampling and groundwater monitoring well installations for the BRP6G and in the RFI/RI Work Plan for the BRP6G and as directed by the subcontract technical representative (STR) for the project. This field investigation was designed to provide data that will:

- confirm the presence or absence of hazardous substances in soil within the unit as indicated by the preliminary results of the 1994 unit characterization
- define the pit boundaries in light of the new data provided by historical aerial photographs
- aid in determining hydraulic conductivity (via water levels and field permeability testing)
- identify if a potential source(s) of contamination is present at the BRP6G

1.3 Site Location

The BRP6G is located in the Central Shops Area. The surface drainage is southward to an unnamed tributary of Pen Branch.

Dothan Soil (soil group three of Looney et al., 1989) is at the surface at BRP6G. A review of the soil conservation service soil survey of the Savannah River Plant area indicates that the soils in the BRP6G SWMU are Udorthents (Rogers, 1990). Udorthents are soils comprising heterogeneous materials which are spoil or refuse from excavations and major construction (Rogers, 1990). Specific background soil sample locations were selected in cooperation with a soil taxonomist at the time the sampling is conducted.

Based on historical accounts, the disposal area at BRP6G was initially considered to be within a rectangular area approximately 83.8 m (275 ft) long and 9.1 to 13.7 m (30 to 45 ft) wide. This area is currently delineated by orange marker balls. Data from a ground penetrating radar (GPR) survey indicated that soil in most of the area defined by the RCRA/CERCLA unit marker balls is undisturbed. Therefore, the March/April 1994 unit characterization investigated the two zones that were represented to be disturbed soils on the GPR survey. The delineation of the waste unit was questionable. Historical aerial photographs indicated that the unit was even larger than anticipated. Additional sampling for the BRP6G was amended to investigate these new suggested boundaries.

An ephemeral stream is located approximately 61 m (200 ft) southeast of the pit (Figure 4). At the time of the unit reconnaissance, it appeared that the drain/ditch was hydrologically influenced solely by surface runoff.

An embankment separates BRP6G from a shallow dry ditch and railroad right-of-way. The top of the embankment is approximately 7.6 m (25 ft) south of the southern edge of the suspected rectangular pit. The embankment is approximately 1.5 m (5 ft) high. Soils exposed in the embankment are undisturbed. The shallow dry ditch, which serves to contain drainage from the railroad right-of-way, contains no obvious evidence of contamination. Water has not been observed in the ditch during any unit reconnaissance.

A second dry ditch which was thought to be located east of the BRP6G appears to cut through the unit on the historical aerial photographs. The ditch has eroded away fill material within the pit boundaries. Also, part of the laydown yard on the eastern side of the ditch appears to be part of the waste unit.

1.4 Geology And Hydrogeology

1.4.1 Geology

1.4.1.1 Geology of the SRS

The geology underlying the SRS includes crystalline basement rock and Triassic sediments overlain by Cretaceous and younger Coastal Plain sediments (Aadland and Bledsoe, 1990). The crystalline basement rock is composed of chlorite-hornblende schist, hornblende gneiss, and lesser amounts of other types of crystalline rock. This bedrock is buried beneath approximately 274 m

(900 ft) of sediment. The Triassic bedrock occurs in the southern portion of the SRS. Sediments of the Triassic bedrock are composed of poorly sorted conglomerate, sandstone and mud-rock, and are generally dark red in color.

The stratigraphic units of the Coastal Plain, from oldest to youngest, are the Cape Fear Formation, the Lumbee Group, the Black Mingo Group, the Orangeburg Group, the Barnwell Group, and the Upland Unit (Figure 5). The Cape Fear Formation is composed of Lower Cretaceous poorly sorted, silty to clayey quartz sands and interbedded clays. The Cape Fear thickens across the SRS, ranging from 9.2 m (30 ft) at the northwest Site boundary to more than 55 m (180 ft) at the southeast Site boundary.

The Lumbee Group (Upper Cretaceous) is subdivided into the Middendorf and the Black Creek Formations, and the Steel Creek Member of the Pee Dee Formation. The lower contact between the Middendorf and the Cape Fear is a sharp erosional unconformity. In general, the Lumbee Group is composed of variably colored quartz sands and clays which range in thickness from 116 m (380 ft) to more than 213 m (700 ft) from the northwestern Site boundary to the southeastern Site boundary, respectively.

The Black Mingo Group consists of the Ellenton Member of the Rhems Formation (Early Paleocene), the Snapp Member of the Williamsburg Formation (Late Paleocene), and the Four Mile Member of the Fishburne Formation (Late Paleocene to early Eocene). The Ellenton consists mostly of gray, poorly sorted, micaceous, lignitic, silty and clayey quartz sand interbedded with gray clays. The Ellenton is approximately 12.2 m (40 ft) thick at the northwestern boundary of the SRS and thickens to approximately 30.5 m (100 ft) at the southeastern boundary. The Williamsburg (Snapp Member) sediments are composed of silty quartz sand interbedded with clays. The Williamsburg thickens from 9.1 m (30 ft) at the northwestern boundary of SRS to 15.2 m (50 ft) at the southeastern boundary. The Fishburne (Four Mile Member) sediments are composed of fine to coarse grained, moderately to well sorted, loose sands with an interbedded clayey zone. The Fishburne has been traced in the subsurface into the northwestern area of SRS (Fallaw, 1991).

The Orangeburg Group is subdivided into the lower Middle Eocene Congaree Formation and the upper Middle Eocene Santee Limestone. The Congaree is composed of well sorted, fine-to-coarse quartz sands with thin clay laminae throughout. The Congaree is approximately 18.3 m (60 ft) thick at the northwestern boundary of the SRS and thickens to approximately 25.9 m (85 ft) near

Figure 5. General Stratigraphic Column for Coastal Plain Sediments

the southeastern boundary. The Santee Formation is subdivided into the Warley Hill, the Caw Caw, and the McBean Members, and varies in lithology from carbonates and calcareous quartz sands to quartz and glauconitic sands and clays. The Warley Hill and the Caw Caw Members make up what has been referred to in many SRS reports as the "Green Clay". This unit is composed of glauconitic, silty and clayey quartz sands. The thickness of the formation ranges from 12.2 m (40 ft) to more than 24.4 m (80 ft) from the northwestern boundary of the SRS to the southeastern boundary.

The Barnwell Group (Late Eocene) is subdivided into the Clinchfield, Dry Branch, and Tobacco Road Formations. Quartz sand of the Clinchfield Formation has been distinguished only when contrasting carbonates of the Griffins Landing Member of the Dry Branch Formation and the McBean Member of the Santee Formation occur, with the sand sandwiched between them. This quartz sand was identified at three localities within the SRS, where it is up to 7.6 m (25 ft) thick, but is not generally mappable. The Dry Branch Formation is subdivided into the Griffins Landing, Twiggs Clay, and Irwinton Sand Members, and varies in lithology from carbonates, silty and clayey quartz sand, and interbedded clays. The carbonate portion of the Griffins Landing Member of the Dry Branch Formation is up to 13.9 m (45 ft) thick in the southeastern part of the SRS. The Griffins Landing carbonate occurs locally at the SRS and is not known to be present northwest of Tinker Creek and Upper Three Runs Creek within the SRS boundaries. The Twiggs Clay Member, which is tan, light gray, and brown, is up to 3.7 m (12 ft) thick in the SRS wells but is not laterally continuous. It was referred to as the "Tan Clay" in many SRS reports. The remainder of the Dry Branch Formation within the SRS is made up of the Irwinton Sand Member, which is composed of tan, yellow, and orange, moderately sorted quartz sand, with interlaminated, locally abundant clay. The formation ranges in thickness from 15.2 m (50 ft) to 24.4 m (80 ft) from the northwestern boundary of the SRS to the southeastern boundary. The Tobacco Road Formation consists of red, fine to coarse, moderately to poorly sorted quartz sand with minor clay laminae. The Tobacco Road outcrops at the surface at many locations throughout the Site and ranges in thickness from 6.1 to 9.1 m (20- to 30-ft).

The Upland Unit (previously mapped at SRS as the Hawthorn Formation) is composed of clays and poorly sorted, clayey, silty, pebbly, and cobbly quartz sands with extreme lateral and vertical variation. These sediments represent fluvial channel deposits. The presence of the Upland Unit in this area is inconsistent, occurring at higher elevations around the SRS.

1.4.1.2 Unit Geology

Three monitoring wells (CBR-1D, -2D, -3D) were installed in January and February 1990 at the BRP6G. These wells provide sampling sites for the shallow groundwater aquifer. Locations of these wells are shown on Figure 3. Pilot holes for wells CBR-2D and -3D were drilled at the edge of the large area of disturbed soil. No debris or waste materials were encountered in these boreholes. The wells are currently being used for determining water levels and for monitoring groundwater quality in the Water Table Aquifer. Figures 6 and 7 are lithologic and hydrostratigraphic cross-sections prepared from the monitoring well boring logs. These figures indicate that the wells are screened in the Water Table (Aquifer Zone IIB₂) below a 7.6 to 10.7 m (25- to 35-ft) thick sandy clay layer.

1.4.2 Hydrostratigraphy

1.4.2.1 Hydrostratigraphy of SRS

The SRS is located approximately 48.3 km (30 miles) southeast of the Fall Line, where sediments of the Coastal Plain Physiographic Province pinch-out, exposing crystalline rocks of the Piedmont Physiographic Province. The recharge zone for the SRS includes the surface area of the site as well as the upgradient land extending northwestward to the Fall Line. Normal annual rainfall for the SRS area is 121.2 cm (47.7 in.). The Savannah River and its tributaries, Upper Three Runs Creek, Four Mile Creek, Steel Creek, Pen Branch Creek, and Lower Three Runs Creek, provide the main surface water drainage system at the SRS.

A multilayer hydrologic system exists in the Coastal Plain sediments at the SRS. Confining units within the system are interspersed with more transmissive units. Aadland and Bledsoe (1990) developed an alpha numeric hydrostratigraphic nomenclature system for SRS (Figure 8). Within this nomenclature, the basement complex underlying the Coastal Plain deposits is referred to as the Paleozoic-Triassic Basement Hydrogeologic System. This system is overlain by three aquifer systems of Coastal Plain deposits, Aquifer Systems I and II, separated by the Confining System I-II. These Aquifer systems are separated from the lower Piedmont Hydrogeologic System by the Confining System I. Confining System I is composed of poorly sorted, clayey sediments of the Cape Fear Formation. Confining clay sediments of the middle Black Creek Formation make up Confining Unit IA-IB which separates the Aquifer Units IA and IB. Aquifer System I is composed of sands of the Middendorf Formation and the lower sands of the Black Creek and

Figure 6. Lithologic and Hydrologic Cross Section HXB-5D to CBR-3D

Figure 7. Lithologic and Hydrologic Cross Section CBR-3D, CBR-2D, and CBR-1D

**CENTRAL SHOPS BURNING/RUBBLE PIT 631-6G
ADDITIONAL SAMPLING AND MONITOR WELL
INSTALLATION REPORT (U)**

**WSRC-RP-95-81
FEBRUARY 1995**

Figure 8. Stratigraphic Column of the SRS Area with Hydrologic Nomenclature

lower Peedee Formations. The reader is referred to Aadland and Bledsoe (1990) for the most recent description of SRS hydrogeology.

Aquifer Unit IIB includes the shallow Water Table Aquifer at the SRS, which is composed of sediments from the Tobacco Road, Dry Branch, and McBean Formations. The sediments of Aquifer Unit IIB typically exhibit a wide variation in lithologic composition both vertically and laterally. Local hydrostratigraphy of the shallow Water Table Aquifer is discussed in Section 1.4.2.2.

Below the Water Table Aquifer (Aquifer Unit IIB) is Confining Unit IIA-IIB. This confining unit is referred to as the "Green Clay". At well cluster P-18 (Figure 9), located approximately 2.4 km (1.5 mi) west of the BRP6G (Figure 2) the "Green Clay" is an orange clayey sand with clay seams (Bledsoe et al., 1990). A head difference of 15.6 m (51.1 ft) has been observed between wells P-18D and P-18B, screened above and below Confining Unit IIA-IIB. A downward vertical gradient of 1.1 m/m (0.35 ft/ft) is calculated using this head difference. Vertical flow through the clay is not estimated because lithologies in addition to the clay are present between the screened intervals.

Aquifer Unit IIA underlies Confining Unit IIA-IIB. At P-18, Aquifer Unit IIA consists of a very fine to fine, tan sand with a thickness of approximately 25.9 m (85 ft). The horizontal and vertical gradients within the aquifer are not known in the vicinity of the BRP6G. A regional calibrated flow model (Haselow and Taylor, 1989) used a horizontal hydraulic conductivity of 4.6m/day (15.1 ft/day) and a vertical hydraulic conductivity of 0.3 cm/day (0.01 ft/day) in Aquifer IIA (referred to as the Congaree Aquifer) for the regional SRS area. In the vicinity of the BRP6G, regional flow in the aquifer is to the southwest toward the Savannah River (Figure 10).

The Aquifer Unit IIA overlies Confining System I - II. The Confining System I-II is referred to as the Ellenton Confining Unit. As indicated by the P-18 well cluster, Confining System I-II is actually a sequence of interbedded silts, sands and clays. It is approximately 21.3 m (70 ft) thick in the vicinity of the BRP6G. Undisturbed samples of the Confining System I-II collected at the P-18 well cluster yielded a range of horizontal hydraulic conductivity values of 0.03 to 26.8 cm/day (0.0010 to 0.88 ft/day) and a range of vertical hydraulic conductivity values from 0.0267 to 12.2 cm/day (0.0009 to 0.40 ft/day) (Bledsoe et al., 1990). The downward vertical gradient across the Confining System I-II, as measured at the P-18 well cluster, is 0.013. Using an effective porosity of 0.10 for sandy clay (Todd, 1959), the vertical flow velocity of Confining

Figure 9.

Profile of P-18 Well Cluster

Figure 10. Regional Potentiometric Surface Map Aquifer Unit IIA

System I-II at C Area ranges from approximately 0.0037 to 1.58 cm/day (0.00012 to 0.052 ft/day) or 1.46 to 578.51 cm/year (0.043 to 18.98 ft/year).

Aquifer System I underlies Confining System I-II. Aquifer System I is divided into Aquifer Units IA and IB. Aquifer Unit IA includes the Pee Dee and upper Black Creek Formations. Figure 11 is a regional potentiometric map of Aquifer Unit IA. The map shows that groundwater flow in the aquifer is to the southwest toward the Savannah River.

Confining Unit IA-IB separates Aquifer Units IA and IB and includes the lower Black Creek Formation. Aquifer Unit IB is composed of the Middendorf Formation. Figures 12 and 13 are regional potentiometric surface maps for the upper and lower parts of the Aquifer Unit, respectively. These maps indicate that groundwater flow within the aquifer unit is to the southwest toward the Savannah River.

Aquifer System I supplies drinking water throughout the SRS. Two existing water supply wells in C Area, 905-90C and 905-91CC, are screened in the lower Pee Dee and upper Black Creek Formations of Aquifer System I. At C Area, four wells within the P-18 well cluster are screened in the Aquifer System I. Hydraulic heads measured in these screened zones during 1Q91 indicate the following:

- an upward vertical gradient of 0.019 from P-18A to P-18TD [Confining System I-II to Aquifer Unit IB]
- a downward vertical gradient of 0.003 from P-18TD to P-18TC [Upper Aquifer Unit IB to Lower Aquifer Unit IB]
- an upward vertical gradient of 0.005 from P-18TC to P-18TB [Lower Aquifer Unit IB to Upper Aquifer Unit IA]
- An upward vertical gradient of 0.002 from P-18TB to P-18TA [Upper Aquifer Unit IA to Lower Aquifer Unit IA]

In N Area, a reversal in the vertical hydraulic head between the overlying Aquifer Unit IB and the deeper Aquifer Unit IA is indicated at the P-18 well cluster. A reversal in hydraulic head also occurs between the overlying Confining System I-II and Aquifer Unit IIA. These head reversals inhibit vertical flow of groundwater from the Aquifer Unit IIA into Aquifer Unit IA, and from Aquifer Unit IB to Aquifer Unit IA, limiting the potential for downward migration of contaminants.

Figure 11. Regional Potentiometric Surface Map Aquifer Unit IB

Figure 12. Regional Potentiometric Surface Map Upper Aquifer IA

Figure 13. Regional Potentiometric Surface Map Lower Aquifer Unit IA

1.4.2.2 Local Hydrostratigraphy

Numerous groundwater monitoring wells exist in C Area, including the CBR, HXB, and CSD well clusters. The location of Water Table monitoring wells in the vicinity of BRP6G is illustrated in Figure 14. All of the depicted wells are screened in the shallow Water Table Aquifer [approximately 15.2 m (50 ft) below land surface (bls)]. The "Tan Clay" (Confining Zone IIB₁ - IIB₂) is not reported at well cluster P-18, and not evident at BRP6G also, which indicates that the shallow Water Table Aquifer and lower Water Table Aquifer (Aquifer Zone IIB₁ and IIB₂) are part of the Aquifer Unit IIB.

Water levels are recorded in each well on a quarterly basis. Using recently available groundwater data, the Water Table surface elevation was contoured (Figure 14). The map indicates that the direction of shallow groundwater flow is southward, with probable discharge into a tributary of Pen Branch ("Pen Branch Tributary") where the Water Table contours intersect the ground surface. Figure 15 is a potentiometric surface map of the Water Table (Aquifer Unit IIB) at the BRP6G using water level measurements (12/20/94) from the three temporary groundwater monitoring wells. In-situ measurements of hydraulic conductivity are not available for the Water Table Aquifer in N Area.

Figure 14. Potentiometric Surface of the Water Table (Aquifer Unit IIB) in the BRP6G Area

WSRC-RP-95-81
FEBRUARY 1995

2.0 FIELD METHODS

Field work at BRP6G was conducted between November 2 and December 30, 1994. Field activities included mud rotary drilling techniques for temporary groundwater monitoring well installation, well development, groundwater sampling, field permeability testing (slug testing), hollow stem auger drilling techniques with split-spoon sample collection, visual classification of soil, collection of surficial soil samples, and collection of surface water/sediment samples. Environmental Monitoring and Testing Corporation (EMTC) and Environmental Exploration, Inc. (EEI) was subcontracted by WSRC to provide drilling services. All field activities were conducted in accordance with methods and procedures in the specified "Hydrogeologic Data Collection Methods, Procedures and Specifications", WSRC 3Q5 manual (WSRC, 1992), the RFI/RI Program Plan (1993a), and direction from the WSRC STR. Records for each temporary groundwater monitoring well include daily field logs and monitoring well installation reports. Appendix B presents the daily field logs for the project. Appendix C presents the field records for the individual wells. Records for each soil boring include daily field logs, field geologic logs, and soil boring installation reports. Borehole records for each soil boring are combined and arranged according to soil boring number and are presented as Appendix D. Daily sign-in/sign-out logs and work zone entry/exit logs are included in Appendix E.

2.1 Drilling and Geologic Sampling

Mud rotary drilling methods were used during drilling and installation of the temporary groundwater monitoring wells. A total of three temporary groundwater monitoring wells were installed for this project: CBR-4, CBR-5, and CBR-6.

Name changes of the original staked locations for the temporary groundwater monitoring wells were necessary. The new names are more in keeping with standard reporting format and assisted in data management of the corresponding groundwater sampling locations.

<u>Original Name</u>	<u>New Name</u>
CBR-T1	CBR-6
CBR-T2	CBR-5
CBR-T3	CBR-4

Bentonite-based drilling fluids (Quik-Gel™) were used only during the mud rotary drilling and well installations. Drilling was accomplished with a tri-cone drill bit. The drilling fluid parameters

were carefully monitored and adjusted to properly clean the borehole, enhance stability and reduce drilling fluid loss. For groundwater monitoring well installations the boreholes were drilled to a nominal 20.3-cm (8-in.) diameter for the 5.1-cm (2-in.) diameter polyvinyl chloride (PVC) wells. See Table 1 for groundwater monitoring well installation information.

The field oversight used an organic vapor analyzer (OVA) or an HNu (trace gas analyzer) to monitor for the presence of volatile organics, which could originate from the borehole during drilling. Also, samples of the drill cuttings were collected for screening by WSRC HP to monitor for potential radioactive materials.

Hand auger and hollow stem auger drilling techniques were used throughout the project for soil sample collection. The first two soil samples 0.0 to 0.30 m (0.0 to 1.0-ft depth) and 0.30 to 0.61 m (1.0 to 2.0 ft) were collected at each sample location. A stainless steel 3-inch diameter hand auger was used to collect these samples and advance the borehole to the required sampling depth. Subsurface soil samples [deeper than 0.61 m (2.0 ft)] were collected at each sample location using a truck-mounted auger drill rig. Hollow-stem augers advanced the borehole to the required sampling depth. Soil samples and lithologic samples were obtained by split-spoon from each soil boring. A 61-cm (24-in.) long, 5.1-cm (3-in.) outside diameter (O.D.) stainless steel split-spoon was lowered on drill rod through the hollow stem augers to the desired sampling depth. The split-spoon was hydraulically pushed or hammer driven into the formation. A total of 12 soil borings were installed for this project (CS6G-11 through CS6G-22). The split-spoons were opened in the field onto a clean plastic covered surface and immediately examined and described in the field by the technical oversight. Small portions of each sample were placed in Ziplock bags and later screened with either an OVA or a HNu for the presence of volatile organics. The soil was gently homogenized to ensure a representative composite sample over the depth of the sample interval. Then the soil was placed in appropriate laboratory supplied containers and stored in coolers onsite until prepared for offsite shipment.

Sample handling procedures and associated mobilization, demobilization, decontamination, and quality control procedures are specified in WSRC 3Q5 and the RFI/RI Program Plan. To prevent and minimize cross-contamination between sampling locations, decontamination procedures were utilized. All down-hole drilling equipment (rig, hollow stem augers, etc.) were steam cleaned prior to use at the beginning of each soil boring. Then plastic sheeting was placed under the drill rig. Decontamination procedures for sampling equipment is detailed in Section 2.2.2. Soil cuttings from the augered boreholes were not removed from the waste unit area, but were either placed back

Table 1
Summary of Groundwater Monitoring Well Installation

Well Number	Date Well Installed	Original Ground Surface Elevation	Depth Drilled	Top of Liquid Level Pipe Elevation	Depth To Top Screen	Screen Length	Depth To Bottom Well	Depth To Top of Filter Pack	Depth to Top of Fine Sand	Depth To Top of Bentonite Seal
CBR-4	11/4/94	--	62.0	--	40.2	20.0	60.5	36.6	NA	18.9
CBR-5	11/3/94	--	57.0	--	35.0	20.0	55.2	33.0	NA	30.0
CBR-6	11/3/94	--	62.0	--	40.2	20.0	60.4	35.9	NA	32.5

NOTES:

All depths from original ground surface (ft bls).
All elevations relative to msl in ft.
All wells constructed with screen size 0.016 in.
and filter pack 0.018 - 0.022 in. (FX-50).
-- Not available

ABBREVIATIONS:

NA - Not Applicable

into the borehole in the soil boring abandonment process or dispersed about the unit area as specified in WSRC 3Q5.

Detailed geologic logs were prepared by the RUST E&I environmental engineer in the field. The field logs are included in Appendices C and D and arranged by borehole number. The grain-size classifications were based upon the modified Wentworth Scale in accordance with WSRC 3Q5.

<u>Grain Size Classification</u>	<u>Diameter (mm)</u>
Pebbles	4 - 64
Granules (very fine pebbles)	2 - 4
Very Coarse Sand	1 - 2
Coarse Sand	1/2 - 1
Medium Sand	1/4 - 1/2
Fine Sand	1/8 - 1/4
Very Fine Sand	1/16 - 1/8
Silt	1/256 - 1/16
Clay	< 1/256

Size fraction percentages were based upon visual inspection and comparison with percentage charts. The degree of sorting present in the sample was based upon visual analysis. The following sorting classification system was adopted:

Well Sorted	90% of sample within 2 sand size classes
Moderately Sorted	90% of sample within 3 sand size classes
Poorly Sorted	90% of sample within 4 sand size classes
Very Poorly Sorted	90% of sample within more than 4 size classes

Color descriptions were based upon comparisons with a standard Munsell™ color chart. The features described on the logs consisted primarily of major sediment type, texture, color, carbonate zones, sedimentary structures, fossils, and accessory minerals. In general, grain sizes, percentages, color, roundness, and sphericity were described by comparison with charts. The soil was also visually classified according to the Unified Soil Classification System (USCS).

2.2 Temporary Groundwater Monitoring Well Design, Installation, and Sampling

2.2.1 Temporary Groundwater Monitoring Well Construction

Three temporary groundwater monitoring wells were installed in the Water Table (CBR-4, CBR-5 and CBR-6). Well construction details for each monitoring well are presented in Appendix C and Table 1. The monitoring wells have been surveyed for location and elevation, and the information was included in an as-built report table provided to WSRC. The available as-built survey data for the groundwater monitoring wells are presented in Table 2.

All monitoring wells were constructed in accordance with specifications and procedures described in WSRC 3Q5 for monitoring wells, and the South Carolina Well Standards and Regulations, R.61-71 of the Code of Laws of South Carolina [South Carolina Department of Health and Environmental Control (SCDHEC), 1985]. The monitoring wells will be surveyed for location and elevation by WSRC, and the information will be included in an as-built report provided to WSRC. Screen intervals for the 5-cm (2-in.) diameter wells were selected after considering hydrogeologic data obtained from previous studies, reports and lithology.

The 5-cm (2-in.) diameter wells were constructed of PVC casing, machine slotted PVC screens with 0.041-cm (0.016-in.) slot width, and a bottom plug either 6.1 or 9.1 cm (2.4 or 3.6 in.) in length. Two stainless steel centralizers were installed as presented in Appendix B.

The filter pack consisted of 0.046 to 0.056-cm (0.018 to 0.022-in.) uniform silica sand. The filter pack was installed from the bottom of the borehole to a minimum of 0.6 m (2 ft) above the screen through a tremie pipe placed adjacent to the well screen. A minimum of 0.9 to 1.5-m (3 to 5-ft) thick bentonite pellet seal was installed above the filter pack. After at least 2 hours of hydration time, a cement/bentonite grout cap was installed through a tremie pipe lowered to just above the bentonite seal. The minimum allowable cement weight was 1.58 g/cm³ (13.2 lbs/gal). Any variations in well construction is presented in Appendix C.

A strong effort was made to minimize the potential of introducing contamination into the subsurface or the local environment during drilling operations. This effort was made so that the results of water quality sampling would be representative of actual groundwater conditions. All well construction materials were secured or wrapped in plastic for storage at the drill site. The

Table 2
 Coordinates and Elevation Details

Well Number	Northing	Easting	Top of Casing Elevation*	Pad Elevation*
CBR-4	60218.24 33.24560867	53107.95 81.64393628	295.84	293.4
CBR-5	60158.39 33.24479117	52687.98 81.64492561	295.89	293.3
CBR-6	60413.28 33.24512914	52549.53 81.64578486	303.91	301.4
Soil Boring	Northing	Easting	Ground Surface Elevation*	
CS6G-11	60292.81 33.24547969	52927.78 81.64455530	293.0	
CS6G-12	60278.56 33.24556414	52998.90 81.64434044	294.2	
CS6G-13	60275.55 33.24564386	53051.84 81.64419522	293.9	
CS6G-14	60304.73 33.24558158	52974.07 81.64445658	295.4	
CS6G-15	60257.33 33.24550322	52990.29 81.64432189	293.4	
CS6G-16	60265.53 33.24572022	53112.24 81.64401678	293.4	
CS6G-17	60334.64 33.24560667	52948.92 81.64458086	296.6	
CS6G-18	60393.28 33.24567778	52912.99 81.64478928	298.4	
CS6G-19	59918.47 33.24551744	53458.61 81.64243128	293.3	
CS6G-20	60041.66 33.24455736	52702.91 81.64465972	290.1	

Table 2 (continued)
Coordinates and Elevation Details

Soil Boring	Northing	Easting	Ground Surface Elevation*
CS6G-21	60468.84 33.24428697	51957.93 81.64744997	299.9
CS6G-22	60315.96 33.24553683	52931.42 81.64459067	292.4
CS6G-23	60284.13 33.24531669	52839.65 81.64477044	291.0
CS6G-24	60245.76 33.24544075	52967.73 81.64435880	289.2
CS6G-25	60192.74 33.24563730	53160.10 81.64374947	288.1
CS6G-26	60391.23 33.24498311	52489.87 81.64589911	293.1
CS6G-27	60408.66 33.24491783	52426.24 81.64610044	293.7
CS6G-28	60428.72 33.24486497	52366.66 81.64629622	293.6
CS6G-29	59772.66 33.24398319	52715.75 81.64410372	279.8
CS6G-30	59934.33 33.24472905	52953.74 81.64379108	282.2
CS6G-31	5996.22 33.24504417	53062.99 81.64362364	284.4
CS6G-32	60071.58 33.24532817	53134.87 81.64358072	285.7
CS6G-33	60114.87 33.24549680	53179.56 81.64354711	286.4

* Elevations relative to Mean Sea Level.
 LAT indicates latitude in decimal degrees. LON indicates longitude in decimal degrees.

drilling and downhole equipment, including drilling and development tools, bailers, pumps, well casings, and well screens were steam cleaned just prior to use or installation and between well sites to minimize the chances of cross-contamination. At each site, plastic sheeting was placed under the drilling rig to contain any fluid leaks from service trucks or the drill rig. Any oil or hydraulic leaks present on the plastic sheet were absorbed with dry bentonite powder and disposed of by WSRC drilling subcontract personnel.

2.2.2 Well Development

Following subsurface completion, each well was developed under guidelines outlined in WSRC 3Q5 and under the direction of WSRC personnel. Well development records included such information as pH, specific conductance, and volume of water removed from the wells. Well development reports were prepared by the drilling companies and submitted to WSRC Environmental Protection Department Groundwater Monitoring Group. Well development results are summarized in Table 3 of this report. Appendix F includes well development records from EMTC.

Initially, each well was developed by bailing slowly. This procedure allows the filter-sand to settle around the screen properly, while purging heavy drilling mud from the well casing, and initiating breakdown of the mud cake formed during rotary drilling operations. The wells were bailed as soon as possible after completion in order to facilitate the initial breakdown of the mud cake. As the development process progressed, the wells were surged by rapidly raising and lowering the bailer. The muddy water was then bailed.

If the groundwater monitoring wells required additional development, a submersible pump outfitted with a surge block was used to surge, or swab discreet areas of the screened zone and remove large volumes of fluid. This surge block was made of a rigid rubber stopper attached to the tremie pipe a few feet above the submersible pump. It was only slightly smaller in diameter than the inside diameter of the well being developed, so that the tremie could be raised and lowered to swab an area of the screen. The surge block would push water out of the screen zone as the tremie and pump were lowered and pull water into the screen zone as they were lifted. When the pH and conductivity of the well had stabilized, the submersible pump was removed from the well. Both of these methods were utilized in the development of the groundwater monitoring wells (see Table 3).

Table 3
 Summary of Well Development

Well Number	Development Method**	Development Hours	Approximate Well Yield (gpm) During Development	Estimated Volume of Water Removed in gallons during Development	Specific			Water Level	
					pH Initial/Final	Conductance (umhos/cm) Initial/Final	Water Level Initial/Final (Depth in ft bls)	Initial	Final Elevation (ft msl)
CBR-6	B/S	6.5	0.1	202	6.25/NR	NR	48/53.5		--
CBR-5	B/S	8	0.5	152	6.14/NR	NR	41/50		--
CBR-4	B/S	12	0.75	425	NR	NR	29/41.5		--

** B - Bailing /S - Swabbing and Surging

NR - No Record

-- Not available

Table prepared from well development records from EMTC.

2.2.3 Groundwater Sampling

Groundwater samples were collected in two different sampling phases from the three temporary groundwater monitoring wells (CBR-4, CBR-5, and CBR-6) on December 5 and December 28, 1994. The Addendum to Chapter 4 of the RFI/RI Work Plan for the Central Shops Burning/Rubble Pit, 631-6G lists the sampling analytes (see Appendix A). All wells were sampled in accordance with WSRC 3Q5. A summary table of the sampling data is presented in Appendix G. The analytical results for this groundwater sampling are not yet available and will not be presented in this report.

2.2.4 Field Permeability Testing

After well development was complete, slug tests (both rising and falling head) were performed on each monitoring well to estimate the hydraulic conductivity (K) of the screened formations. The data were analyzed using the Bouwer and Rice (1976) method (Aqtesolv Aquifer Test Solver, version 1.1, Aqtesolv Test Design and Analysis Computer Software by Geraghty & Miller, Inc., Environmental Services Modeling group).

Test Procedure

Slug tests require the instantaneous displacement of a volume of water within a well or piezometer. A field testing system was used which could be easily set up with a PVC slug (cylinder). The slug was a cylinder constructed of nominal PVC pipe. The cylinder or slug was 2.54 cm (1 in.) in diameter. The cylinder had caps secured on both ends and one end cap was fitted with a lifting hook. The pipe was filled with clean water to serve as ballast.

Falling head test data were reported for each of the monitoring wells. The falling head tests were performed by tying a nylon rope to the lifting hook of the cylinder, submerging the cylinder, and measuring the fall in head in the well casing as the water level returned to static conditions. A pressure transducer linked to an electronic data recorder was used to record the fall in head.

A rising head test was performed once the falling head test reached near static conditions. The rising head test measures the rise in head or the recharge of water after the submerged cylinder had been quickly removed from the well or piezometer.

Data Analysis

The Bouwer and Rice Method (1976) was used in this program to analyze the slug test data. It is applicable to fully or partially-penetrating wells in confined and unconfined aquifers and assumes negligible drawdown of the Water Table around the well and no flow above the Water Table. (Aqtesolv Aquifer Test Solver, version 1.1)

The Bouwer and Rice equation for estimating hydraulic conductivity is:

$$K = \frac{r_c^2 \ln(R_e/r_w)}{2L} \times \frac{1}{t} \times \ln \frac{y_o}{y_t}$$

where, R_e = effective radial distance over which the head difference is dissipated
 r_c = radius of the section where the water level is rising. If the water level is rising within the screen,

$$r_c = \sqrt{r_c^2 + n(r_w^2 - r_c^2)}$$

r_w = radial distance between well center and undisturbed aquifer (r_c plus thickness of gravel envelope or developed zone outside casing)
 L = height of perforated, screened, encased or otherwise open section of well through which groundwater enters
 y = the level of water in the well above or below the Water Table
 y_o = y at time zero
 y_t = y at time t
 t = time since y_o

An empirical equation is used that relates R_e to the geometry and boundary conditions of the system:

$$\ln \frac{R_e}{r_w} = \frac{1}{\frac{1.1}{\ln(H/r_w)} + \frac{A + B \ln[(D-H)/r_w]}{(L/r_w)}}$$

where H = vertical distance from the Water Table to the base of L
 D = the aquifer thickness
 A, B = dimensionless parameters found by comparing their relationship to L/r_w
on a graph of curves provided by Bouwer and Rice (1976).

The observed values of y are plotted against t on semilogarithmic paper (y on the log scale).

Results

Hydraulic conductivity estimates for temporary wells CBR-04 through CBR-06 ranged from $2.95E-5$ cm/sec ($9.68E-7$ ft/sec) to $4.2E-4$ cm/sec ($1.378E-5$ ft/sec) and averaged $1.88E-4$ cm/sec ($6.18E-6$ ft/sec). The hydraulic conductivity estimates for all the wells slug tested (rising and falling head) are presented in Table 4. Data plots of the slug tests are included in Appendix H. These hydraulic conductivity estimates were fairly typical for the lithologies encountered.

2.3 Soil Sampling

2.3.1 Soil Sample Locations and Intervals

The objectives of the soil sampling investigation are (1) to confirm the results of the previous soil sampling (2) to define the pit boundaries in light of the new data provided by historical aerial photographs, and (3) to characterize any potential sources of contamination at the BRP6G and to determine the location of these sources. The Addendum to Chapter 4 of the RFI/RI Work Plan for the Central Shops Burning/Rubble Pit, 631-6G, details the changes to the work plan unit assessment activities and lists the sampling interval and analytes (see Appendix A).

Soil boring locations are illustrated in Figures 3 and 4. See Table 2 for coordinates and ground surface elevations. Borings CS6G-11 and CS6G-14 were expected to be located within the proposed expanded pit/unit area. Results from these borings will provide information regarding the presence or absence of contaminants within the area designated by the historical aerial photographs as the BRP6G.

Table 4
 Groundwater Monitoring Well
 Hydraulic Conductivity Estimates *

Well No.	Hydraulic Conductivity (K)		
	(ft/sec)	(ft/day)	(cm/sec)
CBR-4◇	3.19E-6	0.276	9.72E-5
CBR-5	8.48E-6	0.733	2.59E-4
CBR-6	6.78E-6	0.587	2.068E-4
		Average	
Hydrostratigraphic Unit/Zone	Range ft/sec	ft/day	cm/sec
Aquifer Zone IIB ₂ (Water Table)	9.68 E-7 to 1.38E-5	0.53	1.88E-4

* Based on Field Permeability Testing (Slug Tests)

◇ The Falling Head slug test for CBR-4 was not acceptable; therefore the K presented is for the Rising Head slug test only.

Borings CS6G-15, CS6G-16, and CS6G-17 are located outside the proposed expanded unit/area. Results from these borings will provide information regarding the presence or absence of contaminants outside of the area designated as the BRP6G by the historical aerial photographs.

Background soil sample locations (CS6G-18 through CS6G-22) were selected in cooperation with a soil taxonomist at the time the sampling was conducted (Figure 4). Selected locations are considered beyond the area that potentially may have been impacted from waste disposal activities at the unit. In addition, six surficial 0 - 0.3 m (0-1 ft) soil samples were obtained within the ditch located along the railroad, south of the pit. Three of the samples were selected within the ditch, upgradient and beyond the area of potential impact by the unit. The remaining three samples were collected within the ditch, downgradient from the pit.

The first sample was collected at the surface to 0.3 m (1.0 ft) bls. The second sample was collected from 0.3 m to 0.6 m (1.0 to 2.0 ft) bls. Samples were then collected continuously at 0.6 m (2.0 ft) intervals until two consecutive samples screened clean for volatile organics below the bottom of the pit (Figure 16). The bottom of the pit was designated as the interface from observed burn material and residual soil. The Addendum to Chapter 4 of the RFI/RI Work Plan for the Central Shops Burning/Rubble Pit, 631-6G (Appendix A) designates the analyses to be performed at each sampling interval. The list of possible analytes include Target Compound List/Target Analyte List (TCL/TAL) with Tentatively Identified Compounds (Library Scan) (TIC), Dioxins/Furans, Radiological Indicators, Gas Chromatograph/Mass Spectrophotometer (GC/MS) volatile organic compounds (VOCs), RCRA metals, and TCL VOCs only.

A split of each soil sample was screened in the field for organic vapors using an OVA or an HNu, as outlined in WSRC 3Q5 and the RFI/RI Program Plan. As negotiated with SCDHEC, sampling continued when VOCs field screening indicated contamination in either of the last two samples. When elevated VOCs were detected, samples were collected every 1.5 m (5 ft) down to the Water Table or until field screening indicated no contamination in two consecutive samples, whichever came first (see Figure 16 under the heading "anomalies").

In accordance with WSRC 3Q5 and the RFI/RI Program Plan, field quality control samples were collected during the soils investigation. Trip blanks were added to the work plan and were submitted for TCL VOC analytes. Aqueous trip blanks were provided by the laboratory at the

Figure 16. Soil Sampling Depths and Analytical Parameters

frequency of one trip blank per cooler. All samples for VOC analysis were placed in the same cooler for each day's sample shipment.

2.3.2 Soil Sampling Procedures

As previously described in Section 2.1, soil was collected from each soil boring using a stainless steel hand auger or a split-spoon. Caution was taken to ensure minimum loss of volatiles by keeping the split-spoon closed until the soil sample was collected. Scrapings were taken down the length of the split-spoon sample and placed in air tight plastic bags for volatile screening with an OVA. Scrapings were also taken along the length of the split-spoon to fill the VOC containers for laboratory analysis. A small section of the sample was set aside for descriptive purposes (see Section 2.1) and the remainder of the sample was carefully homogenized and the remaining laboratory containers were filled. Sample container, preservation, storage, and holding time requirements are specified in the Central Shops Burning/Rubble Pit 631-6G, Revision 2, RFI/RI Work Plan. All disposable sampling supplies and materials were removed from the waste unit areas and disposed of in accordance with current WSRC procedures.

Preparation for sample collection included pre-printed chain-of-custody (COC) forms, pre-printed labels with bar code identification system, and receipt of required laboratory containers (including laboratory trip blanks). These tasks were handled by EMS. Sample container and documentation kits were then gathered (containers for each interval at each sampling location), and the bar code identification system was put into effect via the accompanying COC forms. There was a bar code printed for the container and corresponding COC form and for the EPD/EMS Soil Sample Logbooks. When the sample interval had been determined in the field, the final phase of the bar code identification system was enacted. The final bar code sticker was placed in the EPD/EMS Soil Sample Logbook under the sample identification (ID) number for that specific sampled interval in that specific soil boring [i.e., sample ID 101876 is the sample collected from 0.00 to 0.61 m (0.00 to 2.00 ft) bls, which is the first sampling interval in soil boring CS6G-11]. The time, date, sampler, sample type, sample matrix, Munsell™ color, lithologic description, soil wetness, associated samples, and unified soil classification are also recorded in the EPD/EMS Soil Sample Logbook.

Preparation for soil sample collection includes decontamination of the soil sampling equipment. Sampling equipment (split-spoons, stainless steel bowls, spatulas, etc.) were decontaminated prior to use in accordance with the following cleaning procedures:

- Sampling equipment or materials not used immediately after decontamination were placed on a plastic sheet and secured to avoid potential contamination.
- Clean with deionized water and phosphate-free laboratory detergent, (Alconox) using a brush if necessary to remove particulate matter and surface films.
- Rinse thoroughly with deionized water.
- Rinse with pesticide-grade isopropanol solvent.
- Rinse thoroughly with deionized water, and allow to air dry before use.
- Wrap sampling equipment completely with aluminum foil, shiny side out, to prevent contamination if equipment is to be stored or transported.

Clean, disposable gloves will be worn while handling sampling equipment or downhole tools during decontamination. Deionized water will be stored in plastic containers and applied from plastic pump sprayers or decanted directly from the storage container. Storage of isopropanol at SRS requires storage in a non-flammable, steel container marked flammable.

2.3.3 Soil Sample Results

Soil borings were installed according to the planned order and consisted of: CS6G-11, CS6G-12, CS6G-13, CS6G-14, CS6G-15, CS6G-16, CS6G-17, CS6G-18, CS6G-19, and CS6G-20, CS6G-21 and CS6G-22. The first borings drilled were those considered most likely to contain elevated contaminant values. In addition, this sequence allowed definition of the pit depths and boundaries in the borings that were located within the pit areas (see Table 5). The depths to pit bottom were used to determine sample depths in the four borings located outside the pit (CS6G-11, CS6G-15, CS6G-16, and CS6G-17) and the background borings (CS6G-18 through CS6G-21).

During soil boring installation, an OVA or HNu was used to screen for the presence of volatile organics to determine the vertical extent for sampling. OVA readings were below detection limits for all borings inside the pit boundaries except for boring CBR-14 with OVA readings as follows:

BORING CS6G-14

<u>Depth Below Ground Surface (ft)</u>	<u>OVA Reading (ppm)</u>
0-1	15
1-2	20
2-4	3
4-6	10
6-8	12
8-10	0
13-15	0

Table 5
 Summary of Soil, Surface Water/Sediment Sampling

Sample Location	Sample Number	Sampling Date	Number of Split-Spoon Samples*	Total Depth HSA	Depth of the BOP	Sample ID Number	Munsell™ Color Primary/ Secondary	Sampling Depths From/To	Unified Soil Classification	Analyte Code	Location
CS6G-11		11/14/94	4	10.0	NA						Outside Pit
	01E					101874	NA NA	0.0-1.0	NA	1,2,3	
	01					101876	10Yr 4/2 NA	0.0-1.0	CL	1,2,3	
	02					101877	10Yr 8/2 10Yr 6/6	1.0-2.0	CL	1,2,3	
	03					101878	10Yr 6/6 10Yr 8/2	2.0-4.0	CL	1,2,3	
	04					101879	5Yr 5/6 NA	4.0-6.0	CL	1,2,3	
	05					101880	10Yr 8/2 NA	6.0-8.0	CL	1,2,3	
	06					101881	10Yr 8/2 NA	8.0-10.0	CL	1,2,3	
CS6G-12		11/15/94	3	8.0	3.5						Inside Pit
	01					101884	5Yr 5/4 NA	0.0-1.0	SM	1,2,3	
	02					101885	5PB 3/2 NA	1.0-2.0	SM	1,2,3	
	03					101886	10Yr 6/2 NA	2.0-4.0	CL	1,2,3	
	04					101887	10Yr 6/6 10Yr 6/2	4.0-6.0	CL	1,2,3	
	05					101888	10Yr 6/6 10Yr 6/2	6.0-8.0	CL	1,2,3	
	07E					101889	NA NA	6.0-8.0	NA	1,2,3	
CS6G-13		11/15/94	3	8.0	3.8						Inside Pit
	01					101890	10Yr 5/4 NA	0.0-1.0	CL	1,2,3	
	02E					101891	NA NA	1.0-2.0	NA	1,2,3	
	02					101892	NA NA	1.0-2.0	NA	1,2,3	
	03					101893	10Yr 8/2 NA	2.0-4.0	CL	1,2,3	
	04					101894	10Yr 8/2 NA	4.0-6.0	CL	1,2,3	
	04D					101895	10Yr 8/2 NA	4.0-6.0	CL	1,2,3	
	05					101896	10Yr 8/2 NA	6.0-8.0	CL	1,2,3	
CS6G-14		11/16/94	5	15.0	7.0						Inside Pit
	01					101897	5Y 4/1 NA	0.0-1.0	SM	1,2,3	
	02					101898	5Yr 6/4 NA	1.0-2.0	SM	1,2,3	
	03					101899	5Yr 6/4 NA	2.0-4.0	CL	1,2,3	
	04					103700		4.0-6.0		1,2,3	
	05					103701		6.0-8.0		1,2,3	
	06					103702	10Yr 8/2 NA	8.0-10.0		1,2,3	
	07A					103703	10Yr 8/2 5Yr 5/6	13.0-15.0	CH	5,6	
	07					103704	10Yr 8/2 5Yr 5/6	13.0-15.0	CH	5,6	
	08E					103706	NA NA	13.0-15.0	NA	5,6	

Table 5 (continued)
Summary of Soil, Surface Water/Sediment Sampling

Sample Location	Sample Number	Sampling Date	Number of Split-Spoon Samples*	Total Depth HSA	Depth of the BOP	Sample ID Number	Munsell™ Color Primary/ Secondary	Sampling Depths From/To	Unified Soil Classification	Analyte Code	Location
CS6G-15		11/17/94	3	12.0	NA						Outside Pit
	01					103707	5Yr 4/1 NA	0.0-1.0	SM	1,2,3	
	01A					103708	5Yr 4/1 NA	0.0-1.0	SM	1,2,3	
	02					103710	10Yr 6/6 NA	1.0-2.0	SM	1,2,3	
	03					103711	10Yr 8/2 5Yr 5/6	2.0-4.0	CL	1,2,3	
	03E					103712	NA NA	2.0-4.0	NA	1,2,3	
	04					103713	10Yr 8/2 5Yr 5/6	4.0-6.0	CL	1,2,3	
	05					103714	10Yr 8/2 5Yr 5/6	10.0-12.0	CL	1,2,3	
CS6G-16		11/17/94	3	12.0	NA						
	01					103716	10Yr 5/4 NA	0.0-1.0	SM	1,2,3	
	02					103717	N2 NA	1.0-2.0	SM	1,2,3	
	03					103718	N2 NA	2.0-4.0	SM	1,2,3	
	04					103719	10Yr 6/2 5Yr 5/6	5.0-7.0	CL	1,2,3	
	05					103720	N8 NA	10.0-12.0	CH	1,2,3	
CS6G-17		11/17/94	3	12.0	NA						
	01					103721	10Yr 7/4 NA	0.0-1.0	SP	1,2,3	
	02					103722	5Yr 6/4 NA	1.0-2.0	CL	1,2,3	
	03					103722	5Yr 6/4 NA	2.0-4.0	CL	1,2,3	
	03A					103724	5Yr 6/4 NA	2.0-4.0	CL	1,2,3	
	04					103725	10Yr 8/2 5Yr 6/4	5.0-7.0	CH	1,2,3	
	05					103726	10Yr 8/2 NA	10.0-12.0	CH	1,2,3	
CS6G-18		11/18/94	10	47.0	NA						Background
	01					103727	5Yr 4/4 NA	0.0-1.0	CL	1,2,3	
	02					103728	5Yr 5/6 NA	1.0-2.0	CL	1,2,3	
	03					103729	5Yr 5/6 NA	2.0-4.0	CL	1,2,3	
	04					103730	5Yr 5/6 NA	5.0-7.0	SP	1,2,3	
	04E					103731	NA NA	5.0-7.0	NA	1,2,3	
	05					103732	5RP 4/2 NA	10.0-12.0	CL	1,2,3	
	06					103733	5RP 4/2 NA	15.0-17.0	CL	5,6	
	07					103734	5R 8/2 5R 7/4	20.0-22.0	CL	5,6	
	07A					103735	5R 8/2 5R 7/4	20.0-22.0	CL	5,6	
	08					103736	5R 8/2 5R 7/4	25.0-27.0	CL	5,6	
	09					103737	5RP 6/2 NA	30.0-32.0	CH	5,6	
	10					103738	5R 6/2 NA	35.0-37.0	CH	5,6	
	11					103739	5R 6/2 NA	40.0-42.0	CH	5,6	
	12					103740	5R 6/2 NA	45.0-47.0	CH	5,6	
	12A					103741	5R 6/2 NA	45.0-47.0	CH	5,6	

Table 5 (continued)
Summary of Soil, Surface Water/Sediment Sampling

Sample Location	Sample Number	Sampling Date	Number of Split-Spoon Samples*	Total Depth HSA	Depth of the BOP	Sample ID Number	Munsell™ Color Primary/ Secondary	Sampling Depths From/To	Unified Soil Classification	Analyte Code	Location
CS6G-19		11/22/94	10	47.0	NA						Background
	01					103743	10Yr 7/4 NA	0.0-1.0	SB	1,2,3	
	02					103744	10Yr 7/4 NA	1.0-2.0	SM	1,2,3	
	03					103745	5Yr 5/6 10Yr 6/2	2.0-4.0	CL	1,2,3	
	04					103746	5Yr 5/6 10Yr 8/2	5.0-7.0	CL	1,2,3	
	04A					103747	5Yr 5/6 10Yr 8/2	5.0-7.0	CL	1,2,3	
	05					103748	5RP 4/2 10Yr 8/2	10.0-12.0	CL	1,2,3	
	06					103749	5RP 4/2 5Y 8/1	15.0-17.0	CL	5,6	
	07					103750	5R 4/6 NA	20.0-22.0	CL	5,6	
	08					103751	5RP 6/2 NA	25.0-27.0	CH	5,6	
	09					103752	5R 4/6 NA	30.0-32.0	CL	5,6	
	10					103753	5P 6/2 NA	35.0-37.0	CL	5,6	
	11					103754	5P 6/2 NA	40.0-42.0	CL	5,6	
	12					103755	5R 7/4 NA	45.0-47.0	SP	5,6	
	12D					103756	5R 7/4 NA	45.0-47.0	SP	5,6	
CS6G-20		11/28/94	10	47.0	NA						Background
	01					103758	10Yr 6/6 10Yr 6/2	0.0-1.0	SC	1,2,3	
	02					103759	10Yr 8/6 NA	1.0-2.0	CL	1,2,3	
	02E					103760	NA NA	1.0-2.0	NA	1,2,3	
	03					103761	10Yr 8/6 NA	2.0-4.0	CL	1,2,3	
	03D					103762	10Yr 8/6 NA	2.0-4.0	CL	1,2,3	
	04					103763	10Yr 6/6 NA	5.0-7.0	CL	1,2,3	
	05					103764	10Y 8/2 10R 5/4	10.0-12.0	CL	5,6	
	06					103768	10Yr 8/2 10R 3/4	15.0-17.0	CL	5,6	
	07					103769	10Yr 8/2 5RP 4/2	20.0-22.0	CH	5,6	
	08					103770	10Yr 8/2 5RP 4/2	25.0-27.0	CH	5,6	
	09					103771	10Yr 8/2 5RP 4/2	30.0-32.0	CH	5,6	
	10					103773	10R 7/4 NA	35.0-37.0	SP	5,6	
	11A					103774	10Yr 8/2 NA	40.0-42.0	SM	5,6	
	11					103775	10Yr 8/2 NA	40.0-42.0	SM	5,6	
	12D					103776	10Yr 8/2 NA	45.0-47.0	SM	5,6	
	12					103777	10Yr 8/2 NA	45.0-47.0	SM	5,6	
CS6G-21		12/1/94	10	47.0	NA						Background
	01					103780	10Yr 6/6 10R 6/4	0.0-1.0	CL	1,2,3	
	02					103781	10Yr 6/6 10R 6/4	1.0-2.0	CL	1,2,3	
	03					103782	10Yr 8/2 5Yr 5/6	2.0-4.0	CL	1,2,3	
	03E					103783	NA NA	2.0-4.0	NA	1,2,3	

Table 5 (continued)
 Summary of Soil, Surface Water/Sediment Sampling

Sample Location	Sample Number	Sampling Date	Number of Split-Spoon Samples*	Total Depth HSA	Depth of the BOP	Sample ID Number	Munsell™ Color		Sampling Depths From/To	Unified Soil Classification	Analyte Code	Location
	04					103784	10Yr 8/2	5Yr 5/6	5.0-7.0	CL	1,2,3	
	05					103785	10Yr 8/2	5Yr 5/6	10.0-12.0	CL	5,6	
	06					103786	10Yr 8/2	5Yr 5/6	15.0-17.0	CH	5,6	
	06A					103787	10Yr 8/2	5Yr 5/6	15.0-17.0	CH	5,6	
	07D					103788	5RP 4/2	NA	20.0-22.0	CH	5,6	
	07					103789	5RP 4/2	NA	20.0-22.0	CH	5,6	
	08					103790	5Y 8/1	5RP 4/2	25.0-27.0	CH	5,6	
	09					103791	10Yr 8/2	NA	30.0-32.0	CH	5,6	
	10					103792	N9	NA	35.0-37.0	CL	5,6	
	11					103793	N9	NA	40.0-42.0	CL	5,6	
	12					103794						
CS6G-22		12/6/94			NA							Drainage feature
	01					102534	10R 6/6	10R 6/2	0.0-1.0	CL	1,2,3	
	02					102535	N1	NA	1.0-2.0	SM	1,2,3	
	03					102536	N1	NA	2.0-4.0	SM	1,2,3	
	03D					102537	N1	NA	2.0-4.0	SM	1,2,3	
CS6G-23	01	12/6/94				102532	10R 6/6	NA	0.0-1.0	SM	1,2,3	
CS6G-24	01	12/5/94				102530	10R 6/6	NA	0.0-1.0	SM	1,2,3	
CS6G-25	01	12/6/94				102531	10R 6/6	NA	0.0-1.0	SM	1,2,3	
CS6G-26	01	12/5/94				102529	5Yr 5/6	NA	0.0-1.0	SM	1,2,3	
CS6G-27	01	12/5/94				102528	5Yr 5/6	NA	0.0-1.0	SM	1,2,3	
CS6G-28	01	12/5/94				102526	5Yr 5/6	NA	0.0-1.0	SM	1,2,3	
	01A					102527	5Yr 5/6	NA	0.0-1.0	SM	1,2,3	

NA Not applicable
 Analyte Codes for Soil Samples:
 1. TCL/TAL w/TIC
 2. Dioxins/Furans
 3. Rad Indicators (gross alpha and non-volatile beta)
 5. GC/MS VOCs
 6. RCRA Metals

7. TCL VOCs only
 8. TCL VOCs w/TIC
 QA/QC Sample Codes:
 A Duplicate
 D Split
 E Rinsate Sample

Table 5 (continued)
Summary of Soil, Surface Water/Sediment Sampling

Sample Location	Sample Number	Sampling Date	Number of Split-Spoon Samples*	Total Depth HSA	Depth of the BOP	Sample ID Number	Munsell™ Color Primary/ Secondary	Sampling Depths From/To	Unified Soil Classification	Analyte Code	Location
CS6G-29		12/7/94									
	01					102540	NA	NA	NA	4,5,6,7,8,9,10,11	
	02					102541	5Yr 5/6	NA	Surface	5,6,7,8,12	
	02E					102542	NA	NA	NA	5,6,7,8,12	
CS6G-30											
	01					102543	NA	NA	NA	4,5,6,7,8,9,10,11	
	02					102544	5Yr 5/6	NA	Surface	5,6,7,8,12	
CS6G-31											
	01					102545	NA	NA	NA	4,5,6,7,8,9,10,11	
	01D					102555	NA	NA	NA	4,5,6,7,8,9,10,11	
	02					102546	5Yr 5/6	NA	Surface	5,6,7,8,12	
	02D					102556	5Yr 5/6	NA	Surface	5,6,7,8,12	
CS6G-32											
	01					102547	NA	NA	NA	4,5,6,7,8,9,19,10	
	02					102548	5Yr 5/6	NA	Surface	5,6,7,8,12	
CS6G-33											
	01					102549	NA	NA	NA	4,5,6,7,8,9,10,11	
	01A					102550	NA	NA	NA	4,5,6,7,8,9,10,11	
	02					102551	5Yr 5/6	NA	Surface	5,6,7,8,12	
	02A					102552	5Yr 5/6	NA	Surface	5,6,7,8,12	

NA Not applicable

Analyte Codes for Surface Water/Sediment Samples:

1. Total organic halogens
2. Metals (Ag, As, Ba, Cd, Cr, Cu, Pb, Mn, Hg, Ni, Se)
3. Semi-volatile organic constituents, including polycyclic hydrocarbons (PAH)
4. Volatile organic constituents (volatile organic analysis, gas chromatography, mass spectrometer (VOA GC/MS)
5. Radionuclide indicators (gross alpha, nonvolatile bet, total radium) and tritium
6. Surface water temperature, dissolved oxygen, pH, depth, flow (estimate)
7. Sediment pH, TOC
8. Inorganics (Cl, F, SO4, NO3, Na, Fe)
9. TOC, TSS, TDS

QA/QC Sample Codes:

- A Duplicate
- D Split
- E Rinsate Sample

Several factors possibly affected the readings that were encountered and the background (ambient readings). The calibration gas (methane) is ± 2 parts per million (ppm with a minimum detectable limit of 0.2 ppm. Another factor is that ambient background readings will vary depending on the geographical location where the instrument is being used. However, background readings should normally be in the range of 3 to 5 ppm when calibrated with methane. An acceptable background reading of 1.0 to 1.5 ppm methane is normal. In addition to the measurement of a normal methane background, 2 to 4 ppm of equivalent methane background can be caused by acceptable levels of contamination in the OVA's hydrogen fuel and/or hydrogen fuel handling system which will result in a total equivalent methane reading of 3 to 5 ppm as background.

Measurements of 6 to 7 ppm may be acceptable background reading depending on site conditions that affect background. The background reading may be zeroed out or nulled even though in reality the background still exists. The background reading is measured by zeroing the meter with the flame out and noting the meter indication after the flame is on.

Possible causes for high background readings from the OVA include:

- impurities in the hydrogen fuel system
- interferences trapped in the porous bronze sample filter of the Mixed/Burner Assembly
- contamination in the air sample line

It is suspected that the listed readings were due to naturally occurring sources, methane from rotting vegetation and/or terpenes from pine tree roots located within the vicinity of the boring. Also, the BRP6G unit is located near a recycling yard that had a generator running at all times during the work day. Other deciding factors that may have provided readings were:

- weather, because humidity can effect the accuracy of the OVA by $\pm 20\%$ of individual full scale
- isopropanol rinse required for equipment decontamination because residual isopropanol on sampling gloves or clothes could have resulted in a high background detection

Table 5 is a summary of drilling depths, sample intervals and other information included in the EPD/EMS Soil Sample Logbook. The bottom of the pit (BOP) and a burnt, black layer with debris

were encountered in three boreholes inside the pit/unit boundaries (see Table 5). All 12 soil borings were installed, sampled, and abandoned. Section 2.5 provides detailed descriptions for all of the soil borings. Figure 17 depicts the outline of the pit boundary.

2.4 Surface Water/Sediment Sampling

2.4.1 Sampling Locations and Intervals

A minimum of five surface water and sediment samples (CS6G-29 through CS6G-33) were obtained from the ephemeral stream, located approximately 61 m (200 ft) southeast of the unit (Figure 4). At the time the unit reconnaissance was made it appeared that the drain was hydrologically influenced solely by surface runoff. Selection of adequate background locations for surface water and sediment sampling does not appear to be possible, considering that the origin of the drain is located downgradient from the unit. The Addendum to Chapter 4 of the RFI/RI Work Plan for the Central Shops Burning/Rubble Pit, 631-6G (Appendix A) provided the proposed analyte list.

Surface water/sediment samples were analyzed for Total Organic Halogens (TOH), RCRA metals, semi-volatile organic compounds [including polycyclic hydrocarbons (PAH)], GC/MS VOC, radionuclide indicators and tritium, sediment pH and TOC, Inorganics, Total Organic Carbon (TOC), Total Suspended Solids (TSS), and Total Dissolved Solids (TDS).

Field measurements of the surface water included water temperature, dissolved oxygen, pH, and estimated flow (Appendix I). QA/QC samples were also analyzed and collected as specified in the Addendum to Chapter 4 of the RFI/RI Work Plan for the Central Shops Burning/Rubble Pit, 631-6G. A summary of the surface water/sediment sampling is provided in Table 5.

2.4.2 Sampling Procedures

Surface water/sediment sampling was conducted in accordance with procedures specified in the RFI/RI Program Plan and WSRC 3Q5.

Samples were collected from downstream to upstream locations in order to prevent compromising the sampling locations. Surface water samples were collected first at each location and then the surface sediment sample for that location was collected. Caution was taken to ensure minimum

WSRC-RP-95-81
FEBRUARY 1995

loss of volatiles. All disposable sampling supplies and materials were removed from the waste unit area and disposed of in accordance with current WSRC procedures.

Preparation for sample collection and the use of the EPD/EMS soil sample logbooks were described previously in Section 2.3.2. This method was also used for the surface water/sediment sampling. Decontamination procedures of the sampling equipment was also described in Section 2.3.2. Where applicable, these same methods were employed.

2.5 Boring Activity/Problems

2.5.1 *Temporary Groundwater Monitoring Wells*

Field logs, well construction diagrams, and monitoring well installation reports are presented in Appendices B and C. This section describes any problems associated with well installation.

CBR-4

Temporary well CBR-4 was installed on November 4, 1994 to a total depth of 18.43 m (60.48 ft) below land surface. This well is located southeast of the pit boundary. Difficulties during well installation included improper placement of the bentonite seal. The use of tremie pipe to place well material (sand, bentonite etc.) at the desired depths is highly effective. However, during installation of bentonite an obstruction between the top of the sandpack 11.15 m (36.30 ft) and the measured top of bentonite 8.38 m (27.5 ft) was encountered. The amount of bentonite added to the well should have raised the bentonite to approximately 10 m (33.0 ft), therefore not accounting for an approximate 1.5 m (5 ft) section of the well. Since this well was to be considered a temporary well additional bentonite was added to the well and allowed to hydrate for over 48 hours to 5.8 m (18.9 ft) bls. The additional bentonite was placed to prevent possible portland cement intrusion during placement. This temporary well was considered acceptable for the specified purposes.

CBR-5

Temporary well CBR-5 was installed on November 3, 1995. The well was installed to a depth of 16.7 m (55 ft) bls south of the pit boundary. No problems were encountered during drilling or well installation.

CBR-6

Temporary well CBR-6 was installed on November 3, 1995. The well was installed to a depth of 18.4 m (60.4 ft) bls east of the pit boundary. No problems were encountered during drilling or well installation.

2.5.2 Soil Borings

Descriptions of drilling and sampling activities for each soil boring are summarized below. Field logs and soil boring installation reports are included in this report as Appendices B and D. Sample numbers, sample dates number of split spoon samples, total depth to the BOP, EPD/EMS Soil Sample Logbook sample ID number, munsell color, sample depth, unified soil classification, analyte code, QA/QC identifier, and location for each soil boring are presented in Table 5. It should be noted all soil borings terminated above the water table were properly abandoned by backfilling with soil cuttings from that soil boring.

2.5.2.1 Soil Borings Located Within the Estimated Boundary of BRP6G

CS6G-11

This soil boring was installed on November 14, 1994. This boring was proposed within the pit boundary, however visual inspection of the soil sample results did not indicate disturbance and was believed to be located outside the unit boundary. The soil boring was terminated at 2.4 m (8.0 ft) bls and the final sample was collected from 2.4 to 3.0 m (8.0 to 10.0 ft) bls. No OVA readings were above background levels.

CS6G-12

This soil boring was installed on November 15, 1994. No drilling problems were encountered. This soil boring was located in the eastern part of the original pit. Burn material was observed at 0.45 m (1.5 ft). Residuum was observed at 1.1 m (3.5 ft) and assumed to be the BOP. The soil boring was terminated at 1.8 m (6.0 ft) bls and the final sample was collected from 1.8 to 2.4 m (6.0 to 8.0 ft) bls. OVA readings were not above background levels.

CS6G-13

This soil boring was installed on November 15, 1994. No drilling problems were encountered. This soil boring was located in the eastern part of the original pit. Burn material, including ash, organics, old nails, copper wire, and gravel was observed at from 0.15 to 0.3 m (0.5 to 1.0 ft) bls. Residuum was observed at 1.2 m (3.8 ft) bls and assumed to be the BOP. The soil boring was terminated at 1.8 m (6.0 ft) bls and the final sample was collected from 1.8 to 2.4 m (6.0 to 8.0 ft) bls. OVA readings were not above background levels.

CS6G-14

This soil boring was installed on November 16, 1994. No drilling problems were encountered. This soil boring was located in the eastern part of the original pit. Burn material, including ash, black burned wood, glass fragments miscellaneous nails, concrete rubble, and yellow plastic was observed at from 1.5 to 2.13 m (5.0 to 7.0 ft) bls. Residuum was observed at 2.13 m (7.0 ft) bls and assumed to be the BOP. The soil boring was terminated at 4.0 m (13.0 ft) bls and the final sample was collected from 4.0 to 4.6 m (13.0 to 15.0 ft) bls. OVA readings were above background levels as noted in Section 2.3.3.

2.5.2.2 Soil Borings Located Outside the Estimated Boundary of BRP6G

CS6G-15

This soil boring was installed on November 17, 1994. No drilling problems were encountered. This soil boring was proposed outside and southeast of the original pit. This soil boring was to be sampled at intervals consistent with the borings inside the pit. This boring was terminated at 3.0 m (10.0 ft) bls and the final sample was collected from 3.0 to 3.6 m (10.0 to 12.0 ft) bls. OVA readings were not above background levels.

CS6G-16

This soil boring was installed on November 17, 1994. No drilling problems were encountered. This soil boring was proposed outside and east of the original pit. This soil boring was to be sampled at intervals consistent with the borings inside the pit. This boring was terminated at 3.0 m (10.0 ft) bls and the final sample was collected from 3.0 to 3.6 m (10.0 to 12.0 ft) bls. OVA

readings above background levels were 6.0 and 15.0 ppm from samples collected from 0.3 to 0.6 m (1.0 to 2.0) ft and 0.6 to 1.2 m (2.0 to 4.0 ft), respectively.

CS6G-17

This soil boring was installed on November 17, 1994. No drilling problems were encountered. This soil boring was proposed outside and east of the original pit. This soil boring was to be sampled at intervals consistent with the borings inside the pit. This boring was terminated at 3.0 m (10.0 ft) bls and the final sample was collected from 3.0 to 3.6 m (10.0 to 12.0 ft) bls. OVA readings above background levels were 3.0 and 6.0 ppm from samples collected from 0.3 to 0.6 m (1.0 to 2.0) ft and 0.6 to 1.2 m (2.0 to 4.0 ft), respectively.

2.5.2.3 Background Soil Boring Locations

CS6G-18 Through CS6G-21

Background soil boring locations, CS6G-18 through CS6G-21, were chosen by a WSRC soil scientist. Presently, the soil boring locations have not been surveyed and not located on Figure 3. These soil borings were installed between November 18 and December 1, 1994 and exact dates are presented on Table 5. All of these borings were drilled and sampled at predetermined depths as shown in Table 5. There were no drilling problems associated with soil boring installation outside of delays due to rain.

2.5.2.4 Soil Boring in Drainage Feature

A drainage feature running through the eastern portion of the pit boundary was suspect as being a source of horizontal impact. A soil boring CS6G-22 was performed on December 6, 1994. This boring was proposed to evaluate the potential for contaminants from the pit to impact storm water runoff associated with the drainage feature. Burn material was observed at 0.45 m (1.5 ft) to boring termination at 1.1 m (3.5 ft) bls.

3.0 SUMMARY

Preliminary results from the 1994 unit characterization indicate that contamination is present in the RFI/RI unit soils. As stipulated in the Rev. 2 RFI/RI work plan, a downgradient groundwater monitoring well is to be installed in the water table aquifer. To help determine a permanent location for the groundwater monitoring well, three temporary groundwater monitoring wells were installed, developed sampled and slug tested (one to the west, one to the south, and one to the southeast. Water level data from these wells helped determine the hydraulic gradient of the groundwater. The hydraulic conductivity estimates were fairly typical for the lithologies encountered. Groundwater samples were collected for VOCs in two separate phases.

Twelve soil borings were installed, sampled, and abandoned in the BRP6G as part of the additional unit assessment activities of the Central Shops 631-6G RFI/RI. Soil samples were collected at designated intervals for TAL/TCL with TIC, Dioxins/Furans, radionuclide indicators, GC/MS VOCs, RCRA metals and/or TCL VOCs only. The bottom of the pit was encountered in three of the boreholes. A burnt, black layer was found in three of these boreholes within the pit.

Surficial soil samples were collected at six locations within the ditch located along the railroad, south of the pit. These samples were analyzed for TAL/TCL with TIC, Dioxins/Furans and radionuclide indicators. Five surface water/sediment samples were collected from the ephemeral stream approximately 61 m (200 ft) southeast of the unit. These samples were analyzed for TOH, RCRA metals, semi-volatiles, GC/MS VOCs, radionuclide indicators and tritium, inorganics, TOC, TSS, and TDS. The surface sediments were analyzed for pH. The surface water was analyzed in the field for water temperature, dissolved oxygen, pH, depth, and estimated flow. The analytical results from these soil samples will be produced by General Engineering Laboratories of Charleston, South Carolina, and published in another report.

REFERENCES

- Aadland, R. K., A. D. Smits, and P. A. Thayer, 1992. *Geology and Hydrostratigraphy of the A/M Area, Savannah River Site (SRS), South Carolina (U)*, WSRC-RP-92-440, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Aadland, R. K., and H. W. Bledsoe, 1990. *Classification of Hydrostratigraphic Units at the Savannah River Site, South Carolina*, WSRC-RP-90-987, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Bledsoe, H.W., R.K. Aadland, and K.A. Sargent, 1990. *SRS Baseline Hydrogeologic Investigation - Summary Report*. WSRC-RP-90-1010, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Bouwer, H. and R. C. Rice, 1976. *A Slug Test for Determining Hydraulic Conductivity Of Unconfined Aquifers with Completely or Partially Penetrating Wells*, Water Resources Research, Vo. 12, No. 3.
- Fallow, W. C., 1991. *Subsurface Stratigraphy and Structure of the A/M Area at the Savannah River Site*, USDOE Report WSRC-RP-91-830, prepared for Westinghouse Savannah River Company, Westinghouse Savannah River Laboratory, Aiken, SC.
- Gordon, D.E., W.F. Johnson, D.S. Kaback, B.B. Looney, R.L. Nichols, C.B. Shedrow, 1987. *Characterization Recommendations for Waste Sites at the Savannah River Plant*, DPST-87-667, E.I. duPont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- Haselow, J.S. and M.D. Taylor, 1989. *Numerical Simulation of Flow and Contaminant Transport at the K, L, and P Areas of the Savannah River Site*. WSRC-RP-89-1198, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Lewis, S. E., and R. K. Aadland, 1992. *Hydrogeologic Setting of the A/M Area: Framework for Groundwater Transport (U)*, WSRC-TR-92-355, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Looney, B.B., M. Randeem, J. Pickett, V. Rogers, P.A. Shirley, and M.T. Scott, 1989. *Geochemical and Physical Properties of Soils and Shallow Sediments at the Savannah River Plant (Draft)*. WSRC-RP-91-1031, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- Price, V., 1988. "Subsurface Hydrogeology," in Stephenson, A.2., ed., *Final Safety Analysis Report for DWPF (Draft)*. DPSTSA-200-10, E.I. duPont de Nemours and Company, Savannah River Plant, Aiken, SC.
- Rogers, V.A., 1990. *Soil Survey of Savannah River Plant Area Parts of Aiken, Barnwell, and Allendale Counties, South Carolina*: USDA Soil Conservation Service.
- South Carolina Department of Health and Environmental Control (SCDHEC), 1985. *South Carolina Well Standards and Regulations*, R. 61-71. June 1985.
- Todd, D.K., 1959. *Ground Water Hydrology*. Wiley and Sons.

CENTRAL SHOPS BURNING/RUBBLE PIT 631-6G
ADDITIONAL SAMPLING AND MONITOR WELL
INSTALLATION REPORT (U)

WSRC-RP-95-81
FEBRUARY 1995

Westinghouse Savannah River Company (WSRC), 1992, or most recent version. *Hydrogeologic Data Collection Methods, Procedures and Specifications*, WSRC 3Q5 (formerly DPSOP 254), adapted by WSRC from E. I. duPont de Nemours and Company, Savannah River Site, Aiken, SC.

Westinghouse Savannah River Company (WSRC), 1993a. *RCRA Facility Investigation/RI Program Plan*. WSRC-RP-89-994, Revision 1, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Westinghouse Savannah River Company (WSRC), 1993b. *RFI/RI Work Plan for Central Shops Burning/Rubble Pit 631-6G*. WSRC-RP-90-1136, Revision 2. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Westinghouse Savannah River Company (WSRC), 1994a. *Central Shops Burning/Rubble Pit 631-6G Soil Sampling Report*. WSRC-RP-94-382, Revision 2. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Westinghouse Savannah River Company (WSRC), 1994b. *Historical Photographic Search of Central Shops Waste Unit 631-6G, Interim Report*. WSRC-RP-94-0000, Draft. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Appendix A

Addendum 4.0

**Additional Sampling and Groundwater Monitor Well Installation
for the
RFI/RI Work Plan for Central Shops Burning/Rubble Pit, 631-6G**

ADDENDUM 4.0 ADDITIONAL SOIL SAMPLING AND GROUNDWATER MONITORING WELL INSTALLATION

Addendum 4.0 is required to conduct additional sampling at the Central Shops Burning Rubble Pit 631-6G (CSBRP6G) RCRA/CERCLA Unit. This additional sampling is based on information obtained during unit characterization sampling conducted in March and April 1994 and observations in the historical aerial photography of the area.

SRS conducted a review of historical aerial photographs which indicates that the waste unit is not accurately marked in the field, and the location extends an additional 100 - 125 feet further east of the waste unit markers (orange balls). The photographs also showed that the pit was in operation from 1951 through 1955. In addition, the ditch immediately adjacent to the eastern most edge of the marked unit runs through the original waste unit and a portion of the waste unit is more than likely being used currently (1994) as a laydown yard.

The additional sampling will be conducted at a total of 12 soils locations (Figure 4-A1). Four locations are inside the estimated location of the waste unit, three locations are just outside the unit, and five background locations (not shown) will be selected. Specific background soil sample locations will be selected in cooperation with a soil taxonomist at the time the sampling is conducted. The soil taxonomist will select locations which are considered beyond the area that potentially may have been impacted from waste disposal activities at the unit. In addition, 6 surficial (0-1 foot) soil samples will be obtained within the ditch located along the railroad, south of the pit. Three of the samples will be selected within the ditch, upgradient and beyond the area of potential ash deposition. The remaining five samples will be collected within the ditch, downgradient from the pit. The total number of samples proposed for collection at each of the sampling locations is listed in Table 4-A1, including an additional 10 percent to be collected for quality assurance/quality control purposes. The proposed analyte list, identical to the analytical program used during the 1994 unit characterization sampling and outlined in section 4.3, is also detailed in Table 4-A1.

A minimum of five surface water and sediment samples will be obtained from the ephemeral stream, located approximately 200 feet southeast of the pit (Figure 4-A2). At the time the unit reconnaissance was made it appeared that the drain was hydrologically influenced solely by surface runoff. Selection of adequate background locations for surface water and sediment sampling does not appear to be possible, considering that the origin of the drain is located downgradient from the unit. Table 4-A2 provides the analyte list.

Preliminary results from the 1994 unit characterization indicate that contamination is present in the RFI/RI unit soils. A downgradient groundwater monitoring well will be installed in the water table aquifer, an action stipulated in the section 4.4, if contamination is detected in the unit soils. To help determine a permanent location for the monitoring well, three temporary well piezometers will be installed (as shown in Figure 4-A1) per WSRC 3Q5, one to the west, one to the south, and one to the southeast. Water level data from these wells will help determine the hydraulic gradient of the groundwater. Table 4-A3 provides a list of the temporary wells/piezometers and analyses required. One or more of the wells/piezometers will be chosen to be a permanent monitoring well. The remaining temporary wells/piezometers will be abandoned.

If preliminary characterization results (including results from this addendum) indicate the potential for notable ecological impact, then ecological sampling may be required.

All sampling, analytical activities, and groundwater monitoring well installations will follow the approach outlined in this RFI/RI Work Plan.

Figure 4-A2. Surface Water and Sediment Sample Locations

Table 4-A1
Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY	SAMPLE		SAMPLE	SAMPLE	SAMPLE	SAMPLE INT. *		ANALYTE
IDENTIFIER	PT	NUM	INSTRUMENT	TYPE	LOCATION	TOP	BOTTOM	CODE
CS6G	11	01	Hand Auger	Soil	Surface inside pit **	0.0	1.0	123
CS6G	11	02	Hand Auger	Soil	Inside pit	1.0	2.0	123
CS6G	11	03	Split-spoon	Soil	Inside pit	2.0	4.0 Δ	123
CS6G	11	04	Split-spoon	Soil	+1 to -1 ft BOP			123
CS6G	11	4A	Split-spoon	Duplicate	+1 to -1 ft BOP			123
CS6G	11	05	Split-spoon	Soil	-1 to -3 ft BOP			123
CS6G	11	06	Split-spoon	Soil	-3 to -5 ft BOP			123
CS6G	11	07	Split-spoon	Soil	-10 to -12 ft BOP			56
CS6G	11	08	Split-spoon	Soil	-15 to -17 ft BOP			56
CS6G	11	09	Split-spoon	Soil	-20 to -22 ft BOP			56
CS6G	11	10	Split-spoon	Soil	-25 to -27 ft BOP			56
CS6G	11	11	Split-spoon	Soil	-30 to -32 ft BOP			56
CS6G	11	12	Split-spoon	Soil	-35 to -37 ft BOP			56
CS6G	11	13	Split-spoon	Soil	-40 to -42 ft BOP			56
CS6G	11	14	Split-spoon	Soil	-45 to -47 ft BOP			56
CS6G	12	01	Hand Auger	Soil	Surface inside pit **	0.0	1.0	123
CS6G	12	02	Hand Auger	Soil	Inside pit	1.0	2.0	123
CS6G	12	03	Split-spoon	Soil	Inside pit	2.0	4.0 Δ	123
CS6G	12	04	Split-spoon	Soil	+1 to -1 ft BOP			123
CS6G	12	05	Split-spoon	Soil	-1 to -3 ft BOP			123
CS6G	12	06	Split-spoon	Soil	-3 to -5 ft BOP			123
CS6G	12	07	Split-spoon	Soil	-10 to -12 ft BOP			56
CS6G	12	08	Split-spoon	Soil	-15 to -17 ft BOP			56
CS6G	12	09	Split-spoon	Soil	-20 to -22 ft BOP			56
CS6G	12	9A	Split-spoon	Duplicate	-20 to -22 ft BOP			56
CS6G	12	10	Split-spoon	Soil	-25 to -27 ft BOP			56
CS6G	12	11	Split-spoon	Soil	-30 to -32 ft BOP			56
CS6G	12	12	Split-spoon	Soil	-35 to -37 ft BOP			56
CS6G	12	13	Split-spoon	Soil	-40 to -42 ft BOP			56
CS6G	12	14	Split-spoon	Soil	-45 to -47 ft BOP			56
CS6G	13	01	Hand Auger	Soil	Surface inside pit **	0.0	1.0	123
CS6G	13	02	Hand Auger	Soil	Inside pit	1.0	2.0	123
CS6G	13	03	Split-spoon	Soil	Inside pit	2.0	4.0 Δ	123
CS6G	13	04	Split-spoon	Soil	+1 to -1 ft BOP			123
CS6G	13	05	Split-spoon	Soil	-1 to -3 ft BOP			123
CS6G	13	06	Split-spoon	Soil	-3 to -5 ft BOP			123
CS6G	13	07	Split-spoon	Soil	-10 to -12 ft BOP			56
CS6G	13	08	Split-spoon	Soil	-15 to -17 ft BOP			56
CS6G	13	09	Split-spoon	Soil	-20 to -22 ft BOP			56
CS6G	13	10	Split-spoon	Soil	-25 to -27 ft BOP			56

Table 4-A1

Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY	SAMPLE	SAMPLE	SAMPLE	ANALYTE
IDENTIFIER	PT	NUM	INSTRUMENT	TYPE
LOCATION	TOP	BOTTOM	CODE	

CS6G	13	11	Split-spoon	Soil	-30 to -32 ft BOP				56
CS6G	13	11A	Split-spoon	Duplicate	-30 to -32 ft BOP				56
CS6G	13	12	Split-spoon	Soil	-35 to -37 ft BOP				56
CS6G	13	13	Split-spoon	Soil	-40 to -42 ft BOP				56
CS6G	13	14	Split-spoon	Soil	-45 to -47 ft BOP				56
CS6G	14	01	Hand Auger	Soil	Surface inside pit **	0.0	1.0		123
CS6G	14	02	Hand Auger	Soil	Inside pit	1.0	2.0		123
CS6G	14	03	Split-spoon	Soil	Inside pit	2.0	4.0 A		123
CS6G	14	04	Split-spoon	Soil	+1 to -1 ft BOP				123
CS6G	14	05	Split-spoon	Split	-1 to -3 ft BOP				123
CS6G	14	06	Split-spoon	Soil	-3 to -5 ft BOP				123
CS6G	14	07	Split-spoon	Soil	-10 to -12 ft BOP				56
CS6G	14	7A	Split-spoon	Duplicate	-10 to -12 ft BOP				56
CS6G	14	08	Split-spoon	Soil	-15 to -17 ft BOP				56
CS6G	14	09	Split-spoon	Soil	-20 to -22 ft BOP				56
CS6G	14	10	Split-spoon	Soil	-25 to -27 ft BOP				56
CS6G	14	11	Split-spoon	Soil	-30 to -32 ft BOP				56
CS6G	14	12	Split-spoon	Soil	-35 to -37 ft BOP				56
CS6G	14	13	Split-spoon	Soil	-40 to -42 ft BOP				56
CS6G	14	14	Split-spoon	Soil	-45 to -47 ft BOP				56
CS6G	15	01	Hand Auger	Soil	Surface outside pit #	0.0	1.0		123
CS6G	15	02	Hand Auger	Soil	Surface outside pit	1.0	2.0		123
CS6G	15	2A	Split-spoon	Duplicate	outside pit	1.0	2.0		123
CS6G	15	03	Split-spoon	Soil	outside pit	2.0	4.0		123
CS6G	15	04	Split-spoon	Soil	outside pit	5.0	7.0		123
CS6G	15	05	Split-spoon	Soil	outside pit	10.0	12.0		123
CS6G	15	06	Split-spoon	Soil	outside pit	15.0	17.0		56
CS6G	15	07	Split-spoon	Soil	outside pit	20.0	22.0		56
CS6G	15	08	Split-spoon	Soil	outside pit	25.0	27.0		56
CS6G	15	09	Split-spoon	Soil	outside pit	30.0	32.0		56
CS6G	15	10	Split-spoon	Soil	outside pit	35.0	37.0		56
CS6G	15	11	Split-spoon	Soil	outside pit	40.0	42.0		56
CS6G	15	11A	Split-spoon	Duplicate	outside pit	40.0	42.0		56
CS6G	15	12	Split-spoon	Soil	outside pit	45.0	47.0		56
CS6G	16	01	Hand Auger	Soil	Surface outside pit #	0.0	1.0		123
CS6G	16	02	Hand Auger	Soil	Surface outside pit	1.0	2.0		123
CS6G	16	03	Split-spoon	Soil	outside pit	2.0	4.0		123
CS6G	16	04	Split-spoon	Soil	outside pit	5.0	7.0		123
CS6G	16	05	Split-spoon	Soil	outside pit	10.0	12.0		123

Table 4-A1
Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY	SAMPLE		SAMPLE	SAMPLE	SAMPLE	SAMPLE INT. *		ANALYTE
IDENTIFIER	PT	NUM	INSTRUMENT	TYPE	LOCATION	TOP	BOTTOM	CODE
CS6G	16	06	Split-spoon	Soil	outside pit	15.0	17.0	56
CS6G	16	6A	Split-spoon	Duplicate	outside pit	15.0	17.0	56
CS6G	16	07	Split-spoon	Soil	outside pit	20.0	22.0	56
CS6G	16	08	Split-spoon	Soil	outside pit	25.0	27.0	56
CS6G	16	09	Split-spoon	Soil	outside pit	30.0	32.0	56
CS6G	16	10	Split-spoon	Soil	outside pit	35.0	37.0	56
CS6G	16	11	Split-spoon	Soil	outside pit	40.0	42.0	56
CS6G	16	12	Split-spoon	Soil	outside pit	45.0	47.0	56
CS6G	17	01	Hand Auger	Soil	Surface outside pit ≠	0.0	1.0	123
CS6G	17	02	Hand Auger	Soil	Surface outside pit	1.0	2.0	123
CS6G	17	03	Split-spoon	Soil	outside pit	2.0	4.0	123
CS6G	17	3A	Split-spoon	Duplicate	outside pit	2.0	4.0	123
CS6G	17	04	Split-spoon	Soil	outside pit	5.0	7.0	123
CS6G	17	05	Split-spoon	Soil	outside pit	10.0	12.0	123
CS6G	17	06	Split-spoon	Soil	outside pit	15.0	17.0	56
CS6G	17	07	Split-spoon	Soil	outside pit	20.0	22.0	56
CS6G	17	08	Split-spoon	Soil	outside pit	25.0	27.0	56
CS6G	17	09	Split-spoon	Soil	outside pit	30.0	32.0	56
CS6G	17	10	Split-spoon	Soil	outside pit	35.0	37.0	56
CS6G	17	11	Split-spoon	Soil	outside pit	40.0	42.0	56
CS6G	17	12	Split-spoon	Soil	outside pit	45.0	47.0	56
CS6G	17	12A	Split-spoon	Duplicate	outside pit	45.0	47.0	56
CS6G	18	01	Hand Auger	Soil	Background	0.0	1.0	123
CS6G	18	02	Hand Auger	Soil	Background	1.0	2.0	123
CS6G	18	03	Split-spoon	Soil	Background	2.0	4.0	123
CS6G	18	3A	Split-spoon	Duplicate	Background	2.0	4.0	123
CS6G	18	04	Split-spoon	Soil	Background	5.0	7.0	123
CS6G	18	05	Split-spoon	Soil	Background	10.0	12.0	123
CS6G	18	06	Split-spoon	Soil	Background	15.0	17.0	56
CS6G	18	07	Split-spoon	Soil	Background	20.0	22.0	56
CS6G	18	08	Split-spoon	Soil	Background	25.0	27.0	56
CS6G	18	09	Split-spoon	Soil	Background	30.0	32.0	56
CS6G	18	10	Split-spoon	Soil	Background	35.0	37.0	56
CS6G	18	11	Split-spoon	Soil	Background	40.0	42.0	56
CS6G	18	12	Split-spoon	Soil	Background	45.0	47.0	56
CS6G	18	12A	Split-spoon	Duplicate	Background	45.0	47.0	56
CS6G	19	01	Hand Auger	Soil	Background	0.0	1.0	123
CS6G	19	02	Hand Auger	Soil	Background	1.0	2.0	123
CS6G	19	03	Split-spoon	Soil	Background	2.0	4.0	123

Table 4-A1
Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY	SAMPLE		SAMPLE	SAMPLE	SAMPLE	SAMPLE INT.		ANALYTE
IDENTIFIER	PT	NUM	INSTRUMENT	TYPE	LOCATION	TOP	BOTTOM	CODE
CS6G	19	04	Split-spoon	Soil	Background	5.0	7.0	123
CS6G	19	04A	Split-spoon	Duplicate	Background	5.0	7.0	123
CS6G	19	05	Split-spoon	Soil	Background	10.0	12.0	123
CS6G	19	06	Split-spoon	Soil	Background	15.0	17.0	56
CS6G	19	07	Split-spoon	Soil	Background	20.0	22.0	56
CS6G	19	08	Split-spoon	Soil	Background	25.0	27.0	56
CS6G	19	09	Split-spoon	Soil	Background	30.0	32.0	56
CS6G	19	10	Split-spoon	Soil	Background	35.0	37.0	56
CS6G	19	11	Split-spoon	Soil	Background	40.0	42.0	56
CS6G	19	12	Split-spoon	Soil	Background	45.0	47.0	56
CS6G	20	01	Hand Auger	Soil	Background	0.0	1.0	123
CS6G	20	02	Hand Auger	Soil	Background	1.0	2.0	123
CS6G	20	03	Split-spoon	Soil	Background	2.0	4.0	123
CS6G	20	04	Split-spoon	Soil	Background	5.0	7.0	123
CS6G	20	05	Split-spoon	Soil	Background	10.0	12.0	123
CS6G	20	06	Split-spoon	Soil	Background	15.0	17.0	56
CS6G	20	07	Split-spoon	Soil	Background	20.0	22.0	56
CS6G	20	08	Split-spoon	Soil	Background	25.0	27.0	56
CS6G	20	09	Split-spoon	Soil	Background	30.0	32.0	56
CS6G	20	10	Split-spoon	Soil	Background	35.0	37.0	56
CS6G	20	11	Split-spoon	Soil	Background	40.0	42.0	56
CS6G	20	12	Split-spoon	Soil	Background	45.0	47.0	56
CS6G	21	01	Hand Auger	Soil	Background	0.0	1.0	123
CS6G	21	02	Hand Auger	Soil	Background	1.0	2.0	123
CS6G	21	03	Split-spoon	Soil	Background	2.0	4.0	123
CS6G	21	04	Split-spoon	Soil	Background	5.0	7.0	123
CS6G	21	05	Split-spoon	Soil	Background	10.0	12.0	123
CS6G	21	06	Split-spoon	Soil	Background	15.0	17.0	56
CS6G	21	6A	Split-spoon	Duplicate	Background	15.0	17.0	56
CS6G	21	07	Split-spoon	Soil	Background	20.0	22.0	56
CS6G	21	08	Split-spoon	Soil	Background	25.0	27.0	56
CS6G	21	09	Split-spoon	Soil	Background	30.0	32.0	56
CS6G	21	10	Split-spoon	Soil	Background	35.0	37.0	56
CS6G	21	11	Split-spoon	Soil	Background	40.0	42.0	56
CS6G	21	12	Split-spoon	Soil	Background	45.0	47.0	56
CS6G	22	01	Hand Auger	Soil	Background	0.0	1.0	123
CS6G	22	02	Hand Auger	Soil	Background	1.0	2.0	123
CS6G	22	03	Split-spoon	Soil	Background	2.0	4.0	123
CS6G	22	04	Split-spoon	Soil	Background	5.0	7.0	123

Table 4-A1
Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY IDENTIFIER	SAMPLE		SAMPLE INSTRUMENT	SAMPLE TYPE	SAMPLE LOCATION	SAMPLE INT. *		ANALYTE CODE
	PT	NUM				TOP	BOTTOM	
CS6G	22	04A	Split-spoon	Duplicate	Background	5.0	7.0	123
CS6G	22	05	Split-spoon	Soil	Background	10.0	12.0	123
CS6G	22	06	Split-spoon	Soil	Background	15.0	17.0	56
CS6G	22	07	Split-spoon	Soil	Background	20.0	22.0	56
CS6G	22	08	Split-spoon	Soil	Background	25.0	27.0	56
CS6G	22	09	Split-spoon	Soil	Background	30.0	32.0	56
CS6G	22	10	Split-spoon	Soil	Background	35.0	37.0	56
CS6G	22	11	Split-spoon	Soil	Background	40.0	42.0	56
CS6G	22	12	Split-spoon	Soil	Background	45.0	47.0	56
CS6G	23	01	Hand Auger	Soil	R.R. Ditch - Downgradient			123
CS6G	24	01	Hand Auger	Soil	R.R. Ditch - Downgradient			123
CS6G	25	01	Hand Auger	Soil	R.R. Ditch - Downgradient			123
CS6G	26	01	Hand Auger	Soil	R.R. Ditch - Upgradient			123
CS6G	27	01	Hand Auger	Soil	R.R. Ditch - Upgradient			123
CS6G	28	01	Hand Auger	Soil	R.R. Ditch - Upgradient			123
CS6G	28	01A	Hand Auger	Duplicate	R.R. Ditch - Upgradient			123
CS6G	TB	01		Trip Blank	Cooler 1			7
CS6G	TB	02		Trip Blank	Cooler 2			7
CS6G	TB	03		Trip Blank	Cooler 3			7
CS6G	TB	04		Trip Blank	Cooler 4			7
CS6G	TB	05		Trip Blank	Cooler 5			7
CS6G	TB	06		Trip Blank	Cooler 6			7
CS6G	TB	07		Trip Blank	Cooler 7			7
CS6G	FB	01		Field Blank	Day 1			123
CS6G	FB	02		Field Blank	Day 2			123
CS6G	FB	03		Field Blank	Day 3			123
CS6G	FB	04		Field Blank	Day 4			123
CS6G	FB	05		Field Blank	Day 5			123
CS6G	FB	06		Field Blank	Day 6			123
CS6G	FB	07		Field Blank	Day 7			123
CS6G	RA	01		Rinsate (A)	Day 1			123
CS6G	RB	01		Rinsate (S)	Day 1			123
CS6G	RA	02		Rinsate (A)	Day 2			123
CS6G	RB	02		Rinsate (S)	Day 2			123
CS6G	RA	03		Rinsate (A)	Day 3			123
CS6G	RB	03		Rinsate (S)	Day 3			123
CS6G	RA	04		Rinsate (A)	Day 4			123
CS6G	RB	04		Rinsate (S)	Day 4			123

Table 4-A1
Analytical Parameters for Soil and Surficial Sediment Samples

FACILITY	SAMPLE		SAMPLE	SAMPLE	SAMPLE	SAMPLE INT. *		ANALYTE
IDENTIFIER	PT	NUM	INSTRUMENT	TYPE	LOCATION	TOP	BOTTOM	CODE
CS6G	RA	05		Rinsate (A)	Day 5			123
CS6G	RB	05		Rinsate (S)	Day 5			123
CS6G	RA	06		Rinsate (A)	Day 6			123
CS6G	RB	06		Rinsate (S)	Day 6			123
CS6G	RA	07		Rinsate (A)	Day 7			123
CS6G	RA	07		Rinsate (S)	Day 7			123

Sample Pt Column

TB Trip Blank
FB Field Blank
RA Rinsate - Auger
RB Rinsate - Splitspoon

Sample Num Column

A Duplicate
B Split (10% splits will be added if necessary)

Analyte Codes

1 - TCL/TAL w/TIC 5 - GC/MS VOCs
2 - Dioxins/Furans 6 - RCRA Metals
3 - Rad Indicators 7 - TCL VOCs only

Notes

(A) = Auger
(S) = Splitspoon
BOP = Bottom of Pit
bls = Below Land Surface

- ** Sample interval (in ft bls) to be determined from BOP depth
- * Sampling will be terminated @ -5 ft BOP (inside pit) or 12 ft bls (outside pit) if VOC field screening indicates two consecutive samples with no contamination
- ≠ If the BOP is discovered, sampling will follow same intervals as inside pit
- Δ Samples will be collected in 5 ft intervals until BOP is found

Table 4-A2
Analytical Parameters for Surface Water and Sediment Samples

FACILITY	SAMPLE		SAMPLE	SAMPLE	ANALYTE
IDENTIFIER	PT	NUM	TYPE	LOCATION	CODE NUMBERS
CS6G	29	01	Surface Water	Ephemeral Stream	1,2,3,4,5,6,8,9
CS6G	29	02	Sediment	Ephemeral Stream	2,3,4,5,7
CS6G	30	01	Surface Water	Ephemeral Stream	1,2,3,4,5,6,8,9
CS6G	30	02	Sediment	Ephemeral Stream	2,3,4,5,7
CS6G	31	01	Surface Water	Ephemeral Stream	1,2,3,4,5,6,8,9
CS6G	31	1B	Split-Surface Water	Ephemeral Stream	2,3,4,5
CS6G	31	02	Sediment	Ephemeral Stream	2,3,4,5,7
CS6G	31	02B	Split-Sediment	Ephemeral Stream	2,3,4,5
CS6G	32	01	Surface Water	Ephemeral Stream	1,2,3,4,5,6,8,9
CS6G	32	02	Sediment	Ephemeral Stream	2,3,4,5,7
CS6G	33	01	Surface Water	Ephemeral Stream	1,2,3,4,5,6,8,9
CS6G	33	1A	Duplicate - Surface Water	Ephemeral Stream	2,3,4,5
CS6G	33	02	Sediment	Ephemeral Stream	2,3,4,5,7
CS6G	33	2A	Duplicate - Sediment	Ephemeral Stream	2,3,4,5
CS6G	TB	#	Trip Blank		4
CS6G	FC	01	Field Blank - Surface Water		4
CS6G	FD	01	Field Blank - Sediment		4
CS6G	RC	01	Rinsate - Surface Water		4,5
CS6G	RD	01	Rinsate - Sediment		4,5

Sample Point Column

TB Trip Blank
FC Field Blank - Surface Water
FD Field Blank - Sediment
RC Rinsate - Surface Water Equipment
RD Rinsate - Sediment Equipment

Sample Number Column

A Duplicate Blank
B Split Sample
Use next consecutive number
available from previous shipments

Analyte Codes are as follows

- 1 - Total organic halogens
- 2 - Metals (Ag, As, Ba, Cd, Cr, Cu, Pb, Mn, Hg, Ni, Se)
- 3 - Semi-volatile organic constituents, including polycyclic hydrocarbons (PAH)
- 4 - Volatile organic constituents [volatile organic analysis, gas chromatograph, mass spectrometer (VOA GC/MS)]
- 5 - Radionuclide indicators (gross-alpha, non-volatile beta, total radium) and tritium
- 6 - Surface water temperature, dissolved oxygen, pH, depth, flow (estimate)—field measurements
- 7 - Sediment pH, TOC
- 8 - Inorganics (Cl, F, SO₄, NO₃, Na, Fe)
- 9 - TOC, TSS, TDS

Table 4-A3
Analytical Parameters for Groundwater Samples

FACILITY	SAMPLE		SAMPLING	CONSTITUENTS	HYDROLOGIC
IDENTIFIER	PT	NUM	TYPE	FOR ANALYSIS	INTERVAL
CBR	T1	01	Groundwater	2	Water Table
CBR	T2	01	Groundwater	2	Water Table
CBR	T3	01	Groundwater	2	Water Table
CBR	T3	01A	Groundwater	2	Water Table
CBR	T3	01B	Groundwater	2	Water Table
CBR	TB	01	Trip Balnk	2	
CBR	FB	01	Field Blank	2	
CBR	RB	01	Rinsate Blank	2	

* temporary well/piezometers to be sampled once

Analyte Codes are as follows

2 - TCL/TAL w/TIC
3 - Tritium

Sample Point Column

TB Trip Blank
FB Field Blank
RB Rinsate Blank

Sample Number Column

A Duplicate
B Split

Appendix B

Daily Field Logs

KH $\approx$ 48°F CLEAR

11/2/94 - WET

NOTES BY: KELLY HUNTER - Kelly Hunter - KH

7:20 - @ WELL BUILDING - WAITING ON DRILL CREW
7:50 - SPOKE W/ Janelle Janson w/WERC - Janelle
CALLED THE DRILL CREW - THEY (THE DRILL CREW)
DID NOT KNOW OF THE PROJECT - IT WILL
TAKE $\approx$ 2 HOURS TO COLLECT THE TOOLS
AND SHOW UP ON SITE - TRIED TO CALL
DAVID CLARK TO LET HIM KNOW.

8:35 - DAVID CLARK AND RAY PLUNKETT @
WELL BUILDING - WE WENT OVER SCOPE
& PROJECT DETAILS

8:50 - DAVID CLARK & RAY PLUNKETT LEFT
SITE TO RETURN @ 10:00 W/ ETA
OF DRILL CREW. - 10:00 DRILL CREW @ WELL

10:45 - ON SITE - DAVID CLARK & RAY PLUNKETT
ON SITE ALSO DOE REPRESENTATIVE

11:05 - WENT OVER H&S PLAN W/ ALL WHO
WERE IN ATTENDANCE - A

11:10 - CHECKED OSHA TRAINING CERTIFICATES
FOR ALL DRILLING SUB EMPLOYEES
CHECKED - OK.

- MOVED TO CBR-6 LOCATION -
PLACED PLASTIC IN PROPOSED
LOCATION

11:22 - CALIBRATED HNU

11:22 - DRILLERS BEGIN SETUP FOR DRILLING

11:30 - DRILLERS LEFT SITE TO GET THE
WATER TRUCK FOR MUD ROTARY

11:30 - Janelle Janson ON SITE

12:00 - Janelle Janson LEFT SITE

12:05 - RAY PLUNKETT " "

12:15 - DAVE CLARK & I RECON ACCESS
TO CBR-6

12:38 - DRILLERS BACK ON SITE W/ WATER

13:15 TRUCK. DRILLERS DON'T HAVE
BARRIER ROPE - LEFT SITE TO RETRIEVE

13

13.

13

14:

14:

14:

14:

14.

15.

15.

15.

16

16.

16:

16:

16:

KH 11/2/94 LEAF $\approx 62^{\circ}\text{F}$

13:30 - DRILLER HELPERS SETTING UP RIG
- MEASUREMENTS

7 $\frac{7}{8}$ " MUD ROTARY BIT

BIT & TWO SUBS - 3.0'

MEASURED THREE RODS @ 20.00

13:47 - BEGAN DRILLING - CBR-06

- CHECKED NOISE LEVEL AROUND THE RIG
THE HIGHEST LEVEL WAS 87.7 dB.

13:55 - CHECKED BREATHING ZONE WITH HNU ϕ .MM

14:05 - MEASURED THREE RODS -

14:10 - DRILLER SLOWED BACK UP @ SITE

14:15 - HOOKED UP THE DESANDER & STARTED
UP - I CLASSIFIED SOIL TO BE A
COARSE-MED SILTY SAND

14:25 - ADDING A DRILL ROD - 20.00 BGS

14:37 - BEGAN DRILLING AGAIN

15:30 - PEA GRAVEL & CLAY CLOGGED UP DE-SANDER
PUMP - TRYING TO REMOVE OBSTRUCTION -

15:39 - REMOVED OBSTRUCTION -

15:42 - ADDING ON ANOTHER DRILL ROD

16:02 - BORING TERMINATED @ 61.0' BGS
3+20+20+18 $\Rightarrow$ 61.0' BGS

16:05 - CIRCULATING MUD TO CLEAN OUT
BORING - IT APPEARS TO BE IN
CLAY

16:05 - DAVID CLARK LEFT SITE

16:20 - DRILLERS & TRIP OUT RODS

16:30 - LEFT SITE FOR WELL BUILDING

11/3/94 KH CLEAR $\approx 78^{\circ}\text{F}$

4:00 - SCREEN USED 0.016" SLOTTED
(2) 10' SECTIONS - SEE WELL CONSTRUCTION/MATERIAL
INFORMATION FORMS FOR MEASUREMENTS OF MATL. ETC.

4:45 - FINISHED SETTING WELL - PREPARE FOR
MOBE TO CBR-04 LOCATION IN THE
MORNING

5:00 - LEFT SITE FOR WELL BUILDING

[Handwritten signature]

7:15

7:24 - E

7:40 - C

7:55 - T

8:10 - A

8:30 - I

8:30 -

9:30 -

10:00 -

10:40 - G

11:00 - M

11:15 - B

11:18 - C

M

LA

F

11:45 -

12:37 -

1:55 - F

2:05 - M

2:15 - I

2:30 -

2:45 -

3.

(2)

77

• • • • •

• • • • •

8:10

8:30

!

()

10:40 -

11:00 -

11:15-

11:18~

11:45

12:37

1:55

2:05

2:15

2:30

3:45

11/1/94 KH $\approx 80^\circ\text{E}$ YKH

3:

3:

1

(

2

YKH
Y

11/4/94 KH $\approx 80^{\circ}\text{F}$ CLEAR

3:00 - CONCRETE TRIMMER PIPE PUMPED REMAINDER OF 13.2 MCK

3:30 - MIXED ANOTHER GROUT MIX 13.4 lb/gal

GROUTED TO SURFACE

3:50 - LEFT SITE FOR WELL BUILDING

YKH
Y

YKH
Y

11:00

11:12

11:40

12:23

Handwritten notes along a diagonal line, possibly reading "Handwritten" or similar.

KH 11/7/94 CLEAR ~ 70°F

11:00 - ON SITE TO OVERSEE GROUTING OF CBR-4 -
MEASURED TOP OF BENLONITE @ 18.9' - TOLD DRILLERS
TO GET A SIDE DISCHARGE PIPE TO GROUT TO SURFACE -

11:12 - DRILLERS LEFT SITE TO GET SIDE DISCHARGE CONNECTION

11:40 - DRILLERS BACK ON SITE w/ SIDE DISCHARGE PIPE - BEGAN
MIXING GROUT - MIXED 13.4 lb/gal MIX - GROUTED
TO GROUND SURFACE.

12:23 - LEFT SITE

10:25 (3

11:30 - B

11:50 - C

SS

12:15 - F

B

12:30 - I

A

KE

HA

CH

BA

BRUC

12:35 (

12:40 - C

12:50 - J

13:00 - D

13:25 - C

13:45 - C

14:15 - C

14:50 - C

15:25 -

15:30 CITEC

BR6

BOA

SOIL

15:45 - F

L

SOIL

16:00 - Sa

16:20 - D

KH CLEAR ~ 70°F

11/14/94

(KELLY HUNTER RECORDING)

10:25 - BRUCE KRISTENSEN, RAY PLUNKETT ON SITE

11:30 - BEGAN SET UP & DECON SAMPLING EQUIPMENT

11:50 - COLLECTED RINSEATE SAMPLE W/ DROPPED SS - SPOON
SS - HAND AUGER & SS BOWL

12:15 - FILLED OUT CHAIN OF CUSTODY FOR TRIP
BLANK - DRILLERS ON SITE

12:30 - HEALTH & SAFETY PLAN MEETING

NAME	REPRESENTING	SIGNATURE
KELLY HUNTER	RUST E&T	Kelly Hunter
Harold Reed	Harold E. Reed	Harold E. Reed
CHARLES CRENSHAW	E&T	Charles Crenshaw
RAY PLUNKETT	WSRC	Ray Plunkett
BRUCE S. KRISTENSEN	RUST E&T	B. Kristensen

12:35 - CHECKED OSHA TRAINING RECORDS FOR DRILLER
& DRILLER'S HELPER - PAPER IN ORDER & UP
UP TO DATE

12:40 - CALIBRATED OVA

12:50 - DRILLERS BEGAN DECON FUMT

13:00 - DAVED CLARK ON SITE - BEGAN DRILLING CS6G-11

13:25 - COLLECTED SOIL SAMPLE FROM 0-1 FT BGS

13:45 - COLLECTED SOIL SAMPLE FROM 1-2' FT BGS

14:15 - COLLECTED SOIL SAMPLE FROM 2-4 FT BGS

14:50 - COLLECTED SOIL SAMPLE FROM 4-6 FT BGS

15:25 - " " " " 6-8 FT BGS

15:30 CHECKED SOIL SAMPLES W/ OVA & BREATHING ZONE

BREATHING ZONE @ ppm

BORHOLE @ ppm

SOIL SAMPLE FROM 4-6' BGS @ ppm

15:45 SOIL SAMPLE FROM 6-8 BGS 5 ppm

SOIL sample FROM THE BOTTOM OF 8' BGS @ ppm

SOIL sample FROM SAMPLE FROM 8-10' BGS @ ppm

16:00 - Sample FROM 8-10'

16:20 - Duplicate sample 8-10' BGS

16:25

17:10

Handwritten signature or scribble

KH CLEAR COOL $\approx 70^{\circ}\text{F}$ 11/14/94

16:25 - BORING TERMINATED @ 12' BGS

DID NOT DETECT THE BOTTOM OF THE
~~BRP~~
~~TRB~~ - RESIDUUM DETECTED @ 2' BGS

CONTINUED DRILLING PER THE WORK PLAN

17:10 - LEFT SITE - BK - TAKING SOIL SAMPLES TO
THE WELL BUILDING

[Handwritten signature]

11/15/94 KH CLEAR $\approx 60^{\circ}\text{F}$

- 7:05 - ON SITE - BSC & DRILLERS ALREADY ON SITE
- 7:10 - BEGAN MOVE OF DECON EQMT - DRILL RIG ETC TO BORING CS66-12
- 7:40 - CALIBRATED OVA -
- 8:00 - FILLED OUT TRIP BLANK COC & RED BOOK (SAMPLE BOOK)
- 8:30 - TOOK 1ST HAND AUGER 0-1
- 8:50 - TOOK 2ND HAND AUGER 1.0-1.5 - DARK ORGANIC MATERIAL PEAT & POSSIBLE BURN MATERIAL @ 1.5' BGS A SAND PALE IN COLOR. BEGINS STILL BELIEVED TO BE FILL HOWEVER NO SUSPECT BURN MATERIAL
- 9:15 - TOOK SAMPLE FROM 2-4 FT BGS
- 9:30 - " " " 4-6 FT BGS
- 9:45 - WSPC PERSONNEL ON SITE
- RESIDUUM OBSERVED @ 4' BGS - THEREFORE THE BOTTOM OF THE PET OBSERVED
- 10:00 - COLLECTED SOIL SAMPLE FROM 6-8' BGS
- 10:15 - TAKING OVA READINGS ON SAMPLES
DEPTH	OVA READING (ppm)
0-2	0
2-4	0
4-6	0
6-8	0
- 10:30 - SINCE THE BOTTOM OF THE PET WAS OBSERVED @ 3.5' BGS - TWO SAMPLES WERE COLLECTED BELOW THE BOTTOM OF THE PET WITH NON DETECT ON THE OVA. THEREFOR BORING WAS TERMINATED @ 6' BGS AND THE LAST SPLIT SPOON WAS FROM 6-8' BGS
- 10:35 - BEGAN MOVE TO CS66-13
- 11:00 - COLLECTED 2 RINSE BLANK
- 11:25 - COLLECTED 2 SAMPLE FROM 0-1.0' BGS WITH HAND AUGER
- 11:50 - RINSE BLANK COLLECTED

12:28

12:50 -

13:10 -

13:10 -

13:45 -

14:00 -

DE

0-

2-

4-

6-

14:00 -

B

S

E

14:20 -

B

15:00 -

15:30 -

16:00 -

11/15/94 KH CLEAR $\approx 75^{\circ}\text{F}$

- 12:28 - Collected sample from 1 to 2 ft BGS w/ HAND AUGER
12:50 - " " " 2 to 4 ft BGS w/ SPLIT SPOON
13:10 - " " " 4 to 6 ft BGS w/ SPLIT SPOON
13:10 - " " " 4 to 6 ft Duplicate
13:45 - " " " 6 to 8 ft BGS w/ SPLIT SPOON
14:00 - CHECKING SOIL SAMPLES w/ OVA

DEPTH	READINGS
0-2	0 ppm
2-4	0 ppm
4-6	0 ppm
6-8	0 ppm

- 14:00 - BASED ON THE OVA READINGS NO FURTHER SAMPLING REQUIRED - BORING TERMINATED @ 6' w/ LAST SAMPLE COLLECTED FROM 6'-8' BGS.

14:20 - BEGAN DECON. OF DRILLING EQUIPMENT

- 15:00 - CALLED IT A DAY - DID NOT WANT TO START DRILLING AND NOT BE ABLE TO FINISH THE BORING TODAY - DRILLERS LEFT SITE

15:30 - BK LEFT SITE

- I STAYED AND WORKING ON PAPER WORK
- LABELED BOTTLES FOR THE MORNING

16:00 - LEFT SITE

6:58

7:10

7:10

7:45

7:55

8:00

8:25

8:55

9:30

10:05

10:30

10:40

10:45

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

10:55

KH CLOUDY = 68°F 11/16/94

6:58 - ON SITE - DRILLERS ON SITE
7:10 - BK ON SITE - MOBE TO Q566-014
7:10 - SET UP FOR DAYS SAMPLING - CALIBRATED OVA
7:45 - TOOK SOIL SAMPLE FROM 0-1' BGS - HAND AUGER
7:55 - " " " " 1-2' BGS - HAND AUGER
8:00 - " " " " 2-4' BGS - SPLIT SPOON
8:25 - " " " " 4-6 BGS - SPLIT SPOON
8:55 - " " " " 6-8 BGS - SPLIT SPOON
9:30 - " " " " 8-10 BGS - " "
10:05 - " " " " 13-15 BGS - " "

10:30 TOOK OVA READINGS

SAMPLE INTERVAL	OVA READING (ppm)
0-1	15
1-2	20
2-4	3
4-6	10
6-8	12
8-10	0
13-15	0

10:40 - BORING TERMINATED @ 15' BGS
10:45 - WBRC PERSONNEL ON SITE
10:55 - MOBE TO DECON DRILLING EQUIPMENT
10:55 - MOBE TO Q566-15 & BEGAN GENERAL
SETUP

12:00 - LIGHT RAIN WELL WAIT UNTIL IT
BLOWS OVER

14:00 - NO RAIN HEAVY WELL SHUT DOWN FOR DAY

16:00 - LEFT SITE

Kelly

K

7:20 - U

7:20 - G

7:30 - C

8:25 - C

7:55 - C

8:40 -

8:55 -

7:45

B6

4

TO

coll

4

9:25 - Co

10:05 - Col

10:25 -

10:25 -

10:25 -

SAMI

0 -

1 -

2 -

4 - 6

10 - 1

10:35 - B.E.G.

EXAMPL

11:15 - COLLE

11:25 - Collec

11:40 - Collect

11:55 - Collect

12:30 - LI

12:45 - C.H.E.C.

0 - 1

1 -

2 -

4 - 6

10 - 12

KH 11/17/94 55°F CLOUDY

7:20 - ON SITE - DRILLERS & BK ON SITE

✓ UACN ARRIVAL -

7:20 - GENERAL SETUP CSG-15

7:30 - CALIBRATED OVA

8:25 - COLLECTED SOIL SAMPLE FROM 1.0 to 2.0 HAND AUGER

7:55 - COLLECTED " " " 0.0 to 1.0 " "

8:40 - " SOIL SAMPLE FROM 2.0 to 4.0 SPLIT SPOON

8:55 - " " " 4.0 to 6.0 " "

THIS sample 4 to 6 was proposed @ 5' to 7' BGS. However since fill ^{was} observed @ 2.5' BGS & RESIDUUM WAS OBSERVED @ 2.5' IT WAS DECIDED TO CHANGE THE SAMPLE DEPTH TO HAVE ON SAMPLE COLLECTED BENEATH THE FILL/RESIDUUM INTERFACE 4 to 6

9:25 - COLLECTED RINSE SAMPLE

10:05 - COLLECTED SOIL SAMPLE FROM 10'-12' BGS

10:25 - CHECKED SOIL SAMPLES WITH OVA

10:25 BORING TERMINATED @ 12' BGS

SAMPLE DEPTH	OVA READINGS (ppm)
0-1	0
1-2	0
2-4	0
4-6	0
10-12	0

10:35 - BEGAN DECON OF DRILLING EQMT & SOIL

✓ SAMPLE EQUIPMENT - MOVED TO CSG-16

11:15 - COLLECTED 1st SAMPLE 0-1 ft BGS w/ HAND AUGER

11:25 - Collected Sample 1-2 ft BGS " " "

11:40 - Collected Sample 2-4 ft " " SPLIT SPOON

11:55 - Collected Sample 4-6 ft " " " "

12:30 - " " 10-12 ft " " " "

12:45 - CHECKED SOIL SAMPLES w/ OVA

0-1 0 ppm

1-2 6 ppm

2-4 15 ppm

4-6 0 ppm

10-12 0 ppm

11

130

1330

1350

1400

1420

1440

1500

1520

1540

1560

1580

1600

1620

1640

1660

1680

1700

1720

1740

1760

1780

1800

1820

1840

1860

1880

1900

1920

1940

1960

1980

2000

2020

2040

2060

2080

2100

2120

2140

2160

2180

2200

2220

2240

2260

2280

2300

2320

2340

2360

2380

2400

2420

2440

2460

2480

2500

2520

2540

2560

2580

2600

2620

2640

2660

2680

2700

2720

2740

2760

2780

2800

2820

2840

2860

2880

2900

2920

2940

2960

2980

3000

3020

3040

3060

3080

3100

3120

3140

3160

3180

3200

3220

3240

3260

3280

3300

3320

3340

3360

3380

3400

3420

3440

3460

3480

3500

3520

3540

3560

3580

3600

3620

3640

3660

3680

3700

3720

3740

3760

3780

3800

3820

3840

3860

3880

3900

3920

3940

3960

3980

4000

4020

4040

4060

4080

4100

4120

4140

4160

4180

4200

4220

4240

4260

4280

4300

4320

4340

4360

4380

4400

4420

4440

4460

4480

4500

4520

4540

4560

4580

4600

4620

4640

4660

4680

4700

4720

4740

4760

4780

4800

4820

4840

4860

4880

4900

4920

4940

4960

4980

5000

5020

5040

5060

5080

5100

5120

5140

5160

5180

5200

5220

5240

5260

5280

5300

5320

5340

5360

5380

5400

5420

5440

5460

5480

5500

5520

5540

5560

5580

5600

5620

5640

5660

5680

5700

5720

5740

5760

5780

5800

5820

5840

5860

5880

5900

5920

5940

5960

5980

6000

6020

6040

6060

6080

6100

6120

6140

6160

6180

6200

6220

6240

6260

6280

6300

6320

6340

6360

6380

6400

6420

6440

6460

6480

6500

6520

6540

6560

6580

6600

6620

6640

6660

6680

6700

6720

6740

6760

6780

6800

6820

6840

6860

6880

6900

6920

6940

6960

6980

7000

7020

7040

7060

7080

7100

7120

7140

7160

7180

7200

7220

7240

7260

7280

7300

7320

7340

7360

7380

7400

7420

7440

7460

7480

7500

7520

7540

7560

7580

7600

7620

7640

7660

7680

7700

7720

7740

11/17/94 KH $\approx 50^{\circ}\text{F}$ CLOUDY

1300 - BOREING TERMINATED @ 12' BGS

1305 - BEGAN DECON OF DRILLING EQMT

1330 - MOVED TO CS66-17 LOCATION

1350 - TOOK 1st SOIL SAMPLE FROM 0-1' BGS

1405 - " 2nd " " " 1-2' BGS

1420 - " 3rd " " " 2-4' BGS

1420 - " DUPLICATE OF 3rd SAMPLE

1445 - " 4th " " " 5-7' BGS

1505 - " 5th " " " 10-12'

15:30 - BEGAN GENERAL SITE CLEANUP - DECON

15:20 - TOOK OVA READINGS

DEPTH	OVA READING (PPM)
0-1	0
1-2	3
2-4	6
5-7	0
10-12	0

16:00 - LEFT SITE

Handwritten signature/initials

7:00 - C.N

7:20 - M.C

7:45 - B.

8:00 - D.E

8:20 - C.O

8:30 -

8:45 -

9:15 -

9:15 -

10:15 -

10:30 -

11:00 -

11:00 -

11:30

11:50

12:15

12:30

12:45

12:45

13:00 - E

14:00 - C.I

DEPT

ALL

14:00 DRI

15:00 - B.I

11/18/90 KH ~ 55°F CLOUDY

7:00 - ON SITE - DRILLERS ON SITE UPON ARRIVAL

7:20 - MOBE TO CS6G-18 LOCATION

7:45 - Bruce Kristenson on SITE - DAVE CLARK - RAY PLUNKETT

8:00 - DECONED SAMPLING EQMT

8:20 - COLLECTED 1st Sample FROM 0-1 ft BGS - HAND AUGER

8:30 - " 2nd Sample FROM 1-2 " " " "

8:45 - " 3rd Sample FROM 2-4 " " SPLIT SPOON

9:15 - " 4th Sample " 5-7 " " " "

9:15 - " RENSATE w/ 4th Sample SPLIT SPOON

10:15 - " 5th Sample FROM 10-12 ft BGS SPLIT SPOON

10:30 - " 6th Sample FROM 15-17 " " "

11:00 - " 7th Sample " 20-22 " " "

11:00 - " 8th " " 20-22 - DUPLICATE

11:30 - " 9th " " 25-27 -

11:50 - " 10th " " 30-32

12:15 - " 11th " " 35-37

12:30 - " 12th " " 40-42

12:45 - " 13th " " 45-47

12:45 - " 14th " " 45-47 DUPLICATE

1:00 - BORING TERMINATED @ 45' BGS

12:00 - CHECKING SOIL SAMPLES w/ OVA

DEPTH	OVA READING (ppm)
-------	-------------------

ALL	Ø
-----	---

14:00 DRILLERS LEFT SITE

15:00 BK & I LEFT SITE

RA

9:10

A

10:00

D

ML

UP

BEL

10:30

CO

LOI

TH

10:35

DR

PR

10:35

BRUC

EQW

12:15

PR

EQW

12:30

LEI

Handwritten notes and a large diagonal line across the page.

Handwritten notes:
 11/21/94
 11/21/94
 11/21/94

RAIN KH $\approx 65^{\circ}\text{F}$ 11/21/94
 K. HUNTER RECORDING
 10:10 - AT WELL BUILDING WAITING ON DRILLERS
 10:00 - DRILLERS ARRIVE @ WELL BUILDING - WE
 MOVE TO CENTRAL SHOPS - PREPARE TO GRout
 UP BORING CS6h-18 - BECAUSE WE DRILLED
 BELOW THE WATER TABLE -
 10:30 - COULD NOT GET THE DRILL RIG TO CS6h-18
 LOCATION DUE TO RAID/MUD-WILL GRout LATER
 THIS WEEK (WED).
 10:55 - DRILLERS SERVING THE STEAM CLEANER - NOT WORKING
 PROPERLY
 10:35 - BRUCE KRSTIANSEN ON SITE - LOADED - ALL DECON
 EQUIPMENT - TABLES ETC TO CS6h-19 LOCATION.
 11:15 - DRILLERS STILL PERFORMING MAINTENANCE ON
 EDMT - WE ARE CALLED AT 4 DAY.
 11:30 - LEFT SITE

7:15

ON

7:20

SE

7:30

T

7:50

HAR

8:05

TOOK

8:30

"

8:55

"

9:40

"

10:10

"

10:40

"

11:10

"

11:40

"

12:10

"

12:40

"

12:50

"

1:30

DR

1:30

MO

2:45

DR

3:00

ABA

3:45

LEFT

Handwritten signature/initials

11/22/94 KH CLEAR $\approx 55^{\circ}\text{F}$

11:15 ON SITE - BRUCE KRISTENSEN & DRILLERS
ON SITE UPON ARRIVAL

11:20 SET UP FOR SOIL SAMPLING CS66-19

11:30 TOOK 1st SAMPLE FROM 0-1' BGS WITH
HAND AUGER -

11:50 TOOK 2nd Sample 1-2' BGS w/ HAND AUGER

12:05 " 3rd " 2-4' BGS " SPLIT SPOON

12:30 " 4th " 5-7' BGS " " "

" " DUPLICATE @ 5-7' BGS " "

12:55 " 5th Sample 10'-12' BGS @ #1 " "

1:10 " 6th " 15-17 BGS " "

1:10 " 7th " 20-22 BGS " "

1:40 " 8th " 25-27 BGS " "

1:10 " 9th " 30-32 BGS " "

1:40 " 10th " 35-37 BGS " "

1:40 " 11th " 40-42 BGS " "

12:40 " 12th " 45-47 BGS " " & DUPLICATE

12:50 BORING TERMINATED @ 45' BGS

1:30 DRILLERS LEFT SITE TO GET SUPPLES FOR GROUT

1:30 MOVED SAMPLE/DECON STATION TO CS66-20
LOCATION

2:45 DRILLERS BACK ON SITE

3:00 ABANDONED CS66-19 USED 6 BAGS PC
& 13.5 lb/gal BENT CEMENT GROUT

3:45 LEFT SITE

11/

7:00

7:10

MO

AB

8:30

CO

G

8:45

LE

Robert

11/23/94 KH CLEAR $\approx 45^{\circ}\text{F}$

1200 - ON SITE DRILLERS

1210 - MOVED TO CS66-18 LOCATION TO
ABANDON

1230 - COMPLETED BOREHOLE ABANDONMENT

6 BAGS PC, 13.5 lb/gal grout.

1245 - LEFT SITE

7/7/95

9:20

DRI

& R.

THEY

AND

CLEAR

CALL

10:00 - BEGA

10:30 - TOOK

11:00 - "

10:50 - TO

11:15 - COL

11:20 - BE

14:00 - LE

Handwritten signature

DRILLERS PUT ANTI-FREEZE IN THE STEAM CLEANER

4 RIG PUMP/GRout PUMP - Due to EXPECTED FREEZE

THEY DRAINED ALL ANTI-FREEZE FROM THE STEAM CLEANER

AND BLEW OUT RESIDUE WITH STEAM - RAN STEAM

CLEANER $\approx$ 5 min BEFORE STEAM CLEANING MACHINES. I

Called Janelle Janson & let her know.

BEGAN SET UP OF SAMPLING STATION.

TOOK 1ST SAMPLE w/ HAND AUGER

11. 2nd. " " " "

TOOK RINISATE BLANK HAND ALKAL

Collected soil sample from 2.4' BGS & split

BEHAN RAINING - STOPPED DRIVING

LEFT SITE CONTINUED TO RAIN

~~3/16/2007~~

10

11/29

7:15 - 0

7:45 - SK

8:20 - LE

11/29

11/29/94 KH CLOUDY LIGHT RAIN ~ 60°F.
KELLY HUNTER RECORDING

- 15 - ON SITE - WAITING ON DRILLERS
- 45 - BK & Drillers ON SITE - HEAVY RAIN
- 20 - LEFT SITE DUE TO RAIN

11/29/94

Kelly Hunter

St. Peter

11/30
UPON
7:10
7:45 - 101
8:10
8:40
8:45
9:00
9:35
10:15
10:45
11:00
11:00
12:15
12:15
12:30 BOE
12:45 CHECK
43.24
12:45 - B
12:40 - CHECK
14:40 CASINO
14:40 BATTLE
14:30 ABANDON
13:5 lb
14:40 CHECK
15:30 CASINO
15:30 BATTLE
16:00 - LEE

11/30/94 KIT CLOUDY $\approx 45^{\circ}\text{F}$

7:10 ON SITE - DRILLERS & BK ON SITE
UPON ARRIVAL

7:45 COLLECTED SAMPLE FROM 5'-7' BHS

8:10 " " " 10'-12' BGS

8:40 Collected Field Blank w/ DI H₂O

8:45 Collected sample FROM 15'-17' BGS

9:20 Collected SAMPLE " 20'-22' BGS

9:35 Collected SOIL SAMPLE FROM 25'-27' BGS

10:15 " " " " 30'-32' "

10:45 " " " " 35'-37' "

11:00 " " " " 40'-42' BHS

11:20 " ~~4th~~ ~~FEET~~ DUPLICATE 40'-42' BGS

12:15 " SPLIT FROM 45'-47' BHS

12:15 Collected SOIL SAMPLE FROM 45'-47' BGS

2:30 BORING TERMINATED

2:45 CHECKED FLUID LEVEL IN WELL CBR-05

43.24 FEET BELOW TOP OF CASING

2:55 BRUCE KRISTENSEN STARTED BAILING CBR-05 - & BAILED DRY

3:40 CHECKED FLUID LEVEL IN CBR-06 - 50.78' FROM TOP OF
CASING. & BEGAN BAILING

4:40 BAILED DRY

4:30 ABANDONED BORING w/ BENTONITE CEMENT GROUT

13.5 lb/gal. 5 BAGS PC

4:40 CHECKED H₂O LEVEL IN CBR-04 41.20' BELOW TOP OF
CASING

5:20 BAILED 3 WELL VOLUMES ≈ 10 gal H₂O

5:40 LEFT SITE

ANI

BK

I

CL

IA

IA

PO

WE

PE

LI

15:30 -

RENT

GI - 15:30

- 14:15

- 14:00

13:39

- 12:50

- 11:50

- 11:15

- 10:25

- 9:55

- 9:35

- 8:45

- 8:30

- 8:20

DEVI

- 7:50

- 12/1/15

Office

12/1/94 KH CLEAR $\approx$ 48°F

11:50 ON SITE BK & DRILLERS ON SITE UPON ARRIVAL

DRILLERS SETTING UP ON CS66-21 BORING

12:20 TOOK 1st SOIL SAMPLE WITH HAND AUGER 0-1'

12:30 " 2nd " " " " " 1-2'

12:45 " 3rd " " " " " " SPLIT SPOON & RINSATE 2-4'

12:55 " 4th " " " " " " 5-7' BGS

1:05 " 5th " " " " " " 10-12' BGS

1:20 " 6th " " " " " " 15-17 BGS & DUPLICATE

1:35 " 7th " " " " " " 20-22 BGS & SPLIT

1:50 " 8th " " " " " " 25-27 BGS

2:05 " 9th " " " " " " 30-32 BGS

2:30 " 10th " " " " " " 35-37 BGS

2:45 " 11th " " " " " " 40-42 BGS

3:05 " 12th " " " " " " 45-47 BGS

3:30 GROUTED CS66-21 BORING TO SURFACE 5.5 BAGS OF PC
BENTONITE CEMENT GROUT / WITH 13.5 lb/gal MIX

3:50 TOOK RINSATE SAMPLE FOR WELL CBR-T2

AFTER WE TOOK THE SAMPLE WE NOTICED THE
PROTECTIVE COVER WAS FRESHLY PAINTED $\approx$ 1 HOUR.

WE DECIDED NOT TO SAMPLE THE WELL DUE TO
POTENTIALLY CONTAMINATING THE SAMPLE & THE
INTEGRITY OF THE WELL - WILL TRY TO SAMPLE
IN THE MORNING OF 12/2/94. CALLED DAVID

CLARK AND NOTIFIED HIM OF THE SITUATION

WE SPOKE W/ DAVE CLARK (WSRC) AND TOLD HIM

BK & I WOULD BAIL THE WELLS ON SUNDAY

AND SAMPLE THEM MONDAY MORNING

12/4

10:00

ON

10:00 - BEG.

10:20 - BEI

11:00 - FIN

11:15 - BA

11:15 - BEI

12:00 - FI

12:15 - LE

July 1st

12/4/94 KH CLOUDY ~65°F

0800 - ON SITE TO PURGE WELLS FOR SAMPLING

ON 12/5/94.

0900 - BEGAN BAILING CBR-05 - BRUCE KRISTIANSON

1100 - BEGAN BAILING CBR-04 - KELLY HUNTER

1200 - FINISHED BAILING CBR-05 - DRY

1250 - BAILED 10 gal OF H₂O FROM CBR-04 - 3 WELL VOLUMES

0100 - BEGAN BAILING CBR-06 -

0130 - FINISHED BAILING CBR-06 - 7.5 gal H₂O - 3 WELL VOLUMES

0200 - LEFT SITE

12/5

6:50

7:25 - BRU

7:40 - DEC

8:00 - COLL

8:50 - COLLE

9:11 - CBR-

8:30 - COLL

8:40 - COLL

DU

9:45 - COLLE

10:00 - LEF

11:25 - AT

SOIL

12:15 - BACK

SAMP

12:30 - DECO

DRY

1:15 - O

AND

1:30 - COLLECT

1:45 - DECON

1:45 - COLLEC

1:55 - "

1:30 LEFT

WELL

12/5/94 KH PC $\approx$ 65°F

KELLY HUNTER RECORDING

ON SITE TO SAMPLE WELLS

BRUCE KRISTIANSON ON SITE

DECONED SAMPLING EQUIPMENT

COLLECTED FIELD BLANK

COLLECTED A GROUNDWATER SAMPLE FROM WELL

CBR-05 (CBR-T2)

COLLECTED GROUNDWATER SAMPLE FROM CBR-06 (CBR-T3)

COLLECTED GROUNDWATER SAMPLE FROM CBR-04 (CBR-T3)

DUPLICATE & SPLIT

COLLECTED GROUNDWATER SAMPLE FROM CBR-04 (CBR-T1)

LEFT SITE FOR SHIPPING

AT RUST LAB/TRAILER TO PREPARE FOR HAND AUGER
SOIL SAMPLESBACK ON SITE TO COLLECT HAND AUGER SOIL
SAMPLESDECONED SAMPLING EQUIPMENT - WAITING ON
DRYINGCOLLECTED SOIL SAMPLE CS66-28-01 FROM 0-1' BGS
AND ASSOCIATED DUPLICATE

COLLECTED SOIL SAMPLE CS66-27-01 FROM 0-1' BGS

DECONED SAMPLING EQUIPMENT

COLLECTED SOIL SAMPLE CS66-26-01 FROM 0-1' BGS

" " " CS66-24-01 FROM 0-1' BGS

LEFT SITE FOR TRAILER & DELIVERY SAMPLES TO
WELL BUILDING

8:55

9:00

DEU

9:40

CDL

9:55

Col

10:00

D.

10:15

F

10:30

I

11:05

-

11:45

- C

11:50

- C

12:20

- Q

12:45

A

12:50

A

12:30

- B1

12:45

DE.

13:00

STRI

13:30

- L

12:15

12/6/94 KH CLOUDY $\approx$ 65°F

KELLY HUNTER RECORDING

8:55 ON SITE

9:00 DECONED SAMPLING EQUIPMENT

9:40 COLLECTED SOIL SAMPLE CS66-25-01 0-1' BGS

10:55 COLLECTED " " CS66-23-01 0-1' BGS

11:00 DECONED SAMPLE EQUIPMENT

11:15 FILLING OUT SAMPLE FORMS

11:30 DEAN THOMAS ON SITE FOR INSPECTION

11:45 " " LEFT SITE

11:45 COLLECTED HAND AUGER SOIL SAMPLE FROM

CS66-22-01 FROM 0 to 1 ft BGS

11:50 COLLECTED SAMPLE CS66-22-02 1 to 2 ft BGS

12:00 COLLECTED SOIL SAMPLE 2 to 3.5 FT BGS

AUGER REFUSAL @ 3.5' BGS - DID NOT

AUGER THROUGH THE BURN MATERIAL

12:30 BRUCE KRISTIANSON ON SITE - HE HELPED

DECON / GENERAL SITE CLEANUP - IDENTIFIED
STREAM SAMPLE LOCATIONS

12:40 COLLECTED FIELD BLANK SAMPLE

13:30 LEFT SITE

Kelly Hunter

12/7

9:00

SAR

10:00

COLL

TEM

DO

pH

10:15

- C

11:00

- C

Loc

TE

D

P

12:00

- Co

TE

P

T

13:30

- C

T

P

T

14:00

- Col

14:30

- Co

TE

PI

D

15:00

- Col

15:15

- GE

15:20

- LCI

12/7/94 KH CLEAR $\approx 53^{\circ}\text{F}$

KELLY HUNTER RECORDING

ON SITE SETUP FOR SURFACE WATER & SEDIMENT SAMPLING

COLLECTED 1ST SW SAMPLE @ CS66-29 LOCATIONTEMP 13.4°C DO ~~0.785~~ ^{12/1/94} 7.85 mg/L

pH 10.51

COLLECTED SEDIMENT SAMPLE

COLLECTED SURFACE WATER SAMPLE @ CS66-30 LOCATION

TEMP -66°F DO ~~10.6~~ ^{12/1/94} 9.4 ^{12/1/94} 9.4 mg/L pH ~~7.85~~ ^{12/1/94} 10.5

COLLECTED SURFACE WATER SAMPLE & DUPLICATE @ CS66-31

TEMP -73° pH 9.68 DO -8.00 mg/L

COLLECTED SURFACE WATER SAMPLE @ CS66-32 location

Temp 15.8°C pH 9.22 DO 6.63

COLLECTED SEDIMENT SAMPLE @ CS66-32

COLLECTED SURFACE WATER SAMPLE @ CS66-33 & DUPLICATE

TEMP 16.0°C pH 6.61 DO 5.38 mg/L

COLLECTED SEDIMENT SAMPLE @ CS66-33

GENERAL SITE CLEANUP

LEFT SITE

1155 - ON

TEST

1155 - BEG

1155 - CB

1155 - FIA

SEN

1155 - FIA

Q

1215 - CC

12/20/94 KH Clear ~ 30°F

TRANSCRIBED ON 12/27/94 FROM NOTES
TAKEN 12/20/94 - KERRY HUNTER RECORDING

ON SITE w/ RAY PLUNKETT TO PERFORM SLUG

TEST ON CBR-4, CBR-5 & CBR-6

BEGAN PREPARATION OF SLUG TEST

CBR-5 - CBR-71

STATIC WATER LEVEL @ 50.85' BTHS Below TOC
12/20/94

USED A HERMIT AND DATA LOGGER

FALLING HEAD TEST RECORDED ON CHANNEL 0

RISING HEAD TEST RECORDED ON CHANNEL 1

FINISHED SLUG TEST FOR CBR-6 - MOBE AND

SETUP FOR SLUG TEST @ CBR-4 - CBR-13

STATIC H₂O LEVEL @ 41.37 Below TOC

FALLING HEAD TEST RECORDED ON CHANNEL 2

RISING " " " " " 3

FINISHED SLUG TEST @ CBR-4 MOBE & SETUP

CBR-5 - CBR-12

STATIC WATER LEVEL @ 43.13

FALLING HEAD TEST RECORDED ON CHANNEL 4

RISING " " " " " 5

COMPLETED SLUG TEST - LEFT SITE

12/1
1230 - DO
I w
CALCA
CBA
TO
TH
GA
1
BAC
BAC
MOBE
19
1110 - T
1115 - MOB
TOM
DE
1
T
1430 - BAC
1435 - MOBE
1500 - FINISH
1530 - LEFT

12/27/94 KH Clear $\approx$ 50°F

Key Hunter Recording

LOCATION SITE - SET UP DECON AREA

DO NOT HAVE WATER LEVEL PROBE HOWEVER

I WILL USE 12/20/94 WATER LEVELS TO

(CALCULATE AMOUNT OF WATER TO WITHHOLD)

CBR-6/CBR-T1 - 50.85' Below TC

TOTAL DEPTH OF WELL 60.40' B65

THEREFORE WITH 2.5' STICK UP (CASING) ABOVE

GROUND SURFACE - 12.05' OF WATER IN WELL

1.97 gal X 3 well volume = 5.89 gal

DR. BRUCE KRISTANSON ON SITE - BEGAN BAILING

Bailed 6 gal

MOBE TO CBR-T3 LOCATION

TOTAL DEPTH OF WELL 55.0' B65

DEPTH TO 43.13' Below TC

DEPTH TO 40.63' B65

19.11' KH

17.35' OF WATER

2.34 gal - Three well volumes

Bailed 10 gal

MOBE TO CBR-T2 LOCATION

TOTAL DEPTH - 55.0' B65

DEPTH TO WATER @ 43.13' ft Below TC

" " @ 40.63' B65

14.37' OF WATER IN WELL OR 2.34 gal

THREE well volumes 7.03 gal

Bailed 7 gal

MOBE TO CBR-T1 LOCATION TO DECON BATTERS

FINISHED BAIL DECON

LEFT SITE

[Handwritten signature]
[Handwritten signature]
12/28/94

12/28/94 JCH
KEI
0830 - ON
MONITOR
0845 - SAMPLE
0910 - MOBED
0920 - SETUP 1
0925 - Bruce
BLANK
0935 - Bruce
0930 - COLLECTE
DECONED
0940 - SETUP F
0950 - SAMPLED
1010 - MOBE 7
1015 - SETUP 1
1015 - THE S
WENT 3
1000 - DECONE
1040 - BEG
1105 - LOGED
1120 - GENERA
BATTER
TO WI

12/23/94 1CH CLEAR $\approx 35^{\circ}\text{F}$

KELLY HUNTER RECORDING

850 - ON SITE TO COLLECT GROUNDWATER SAMPLES FROM
MONITOR WELLS CBR-T1, CBR-T2, AND CBR-T3

855 - SAMPLED CBR-T1 - DECONED BAILER USED

855 - MOVED TO CBR-T2

855 - SETUP FOR RINSATE SAMPLE

855 - Bruce Kristerson ON SITE TO HELP W/ RINSATE
BLANK CBR-T2E

855 - Bruce Kristerson LEFT SITE

855 - COLLECTED RINSATE POURED DI H_2O THROUGH

DECONED BAILER INTO BOTTLES

855 - SETUP FOR SAMPLE CBR-T2

855 - SAMPLED CBR-T2

855 - MOVED TO CBR-T3

855 - SETUP FOR SAMPLING & BEGAN SAMPLING

855 - THE STRING TIED TO THE BAILER BROKE AND BAILER
WENT INSIDE WELL

855 - DECONED ANOTHER BAILER

855 - BEGAN SAMPLING CBR-T3

855 - LOGGED IN TRIP BLANK

855 - GENERAL SITE CLEANUP & LEFT SITE - WILL RETRIEVE

BAILER LATER IN DAY - DELIVERING SAMPLES & COL'S
TO WELL BUILDING FOR SHIPPING.

Appendix C

Field Reports for Groundwater Monitoring Wells

CBR-4

CBR-5

CBR-6

(

CBR-4

(

Project Name CENTRAL SHOPS Bldg				Project Manager (last name, first initial) RAY & LUNKETT				Department GO - ENVIRONMENTAL ENGINEERING					
Installation Purpose (Monitoring, Piezometer, etc.) TEMPORARY MONITORING				County Barnwell		Location Description CENTRAL SHOPS BURNING RUBBLE PIT				SRS North Grid Coordinate		SRS East Grid Coordinate	
				Latitude (decimal degrees)		Longitude (decimal degrees)		Ground Elev.		Top Casing Elev.		Liq. Level Pipe Elev.	

Drilling Start Date 11/4/94				Drilling Comp Date 11/4/94		Total Drilled Depth 62.0		Int. Static Water Level/Date NA		Total Borehole Deviation (angle/direction) NA	
Drilling/Sampling Method 7 7/8" mud rotary				Top Depth NA		Bot Depth NA		Diameter NA		Drilling/Sampling Method	
Drilling Company EMTC				Driller (last name, first initial) BARNES, G		Overight Company RUST E & F		Overight (last name, first initial) HUNTER, K		Drilling & Sampling Comments (drilling muds used, source of water, lost circulation zones, etc.)	

Date Logged				Logging Top Depth		Logging Bottom Depth		Logging Subcontractor		Logging Truck Operator	
Geophysical Logs											
☐ Caliper ☐ Gamma ☐ Natural Gamma ☐ Neutron Density ☐ Resistivity ☐ Single Pt. Resistivity ☐ L&S Normal Resistivity ☐ Spontaneous Potential ☐ Other Geophysical Logs (list)											
Backfill Top Depth		Backfill Bot Depth		Backfill Material (include type quantity and units)							

Elevations measured from height above MSL. Depths measured from ground surface to nearest 0.1 ft. * Enter an "X" if cuttings were taken.

MONITORING WELL INSTALLATION REPORT

Page 2 of 4

WELL NUMBER (AAA,NNN,AA)

CBR 04

WELL INSTALLATION (WELL MATERIALS)

Date Well Installed 11/4/94	Installed By EMTC	Overight RUST E & I	No. of Centralizers 2	Centralizer Type STAINLESS STEEL 2" φ	Sieve Analysis? ☐ Yes ☐ No	
CASING	Top Depth	Bot Depth	Material and Schedule	Diameter	Joint Type	
	2.5' ALS	40.08	PVC SCHEDULE 40	2"	FLUSH THREADED	
SCREEN	Top Depth	Bot Depth	Material	Diameter	Slot Size	Slot Type
	40.10	60.16	PVC	2"	0.016"	MACHINE SLOTTED
SUMP	Top Depth	Bot Depth	Material and Schedule	Diameter	Joint Type	
	NA	NA				
SUMP CAP	Top Depth	Bot Depth	Material and Schedule	Diameter	Cap Type	
	60.10	60.48	PVC SCHEDULE 40	2"	POINTED AND FLUSH THREADED	

WELL INSTALLATION (ANNULAR MATERIALS)

FILTER PACK	Top Depth	Bot Depth	Trade Name	Grain Size (mm)	Amount (sacks)	Sack Size (lbs)	Installation Method
	36.60	62.0	FX 50	0.45-0.55	8 (100 lb)	100	TRIMMIE - FLUSHED w/WATER
FINE SAND SEAL	Top Depth	Bot Depth	Trade Name	Grain Size (mm)	Amount (sacks)	Sack Size (lbs)	Installation Method
	NA	—	—	—	—	—	—
BENTONITE SEAL	Top Depth	Bot Depth	Hydration Time (hrs)	Amount	Units and Size (sacks, buckets, etc.)	Installation Method	
	11/10/94 28.9	36.60	48 hrs	2	BUCKETS	TRIMMIE	
GROUT	Top Depth	Bot Depth	Grout Mix	Amount (sacks)	Sack Size (lbs)	Grout Date	Installation Method
	0	18.9	13.4 lb/gal	3.5	90	11/7/94	PRESSURE GROUT

Report Prepared By

KELLY HUNTER

Date

11/10/94

Well Accepted By

Date

MONITORING WELL CONSTRUCTION DIAGRAM

DRILLING SUBCONTRACTOR EMTC

WELL NUMBER CBR-04

DR. ER G. BARNES

SRS COORDINATES _____

DATE OF WELL INSTALLATION 11/4/94

SANITARY SEAL ELEVATION _____

TECH. O.S./CO. NAME KELLY HUNTER / RUST ETI

NOTE: ALL MEASUREMENTS
ARE FROM GROUND
SURFACE AT START
OF BORING - MEASUREMENTS
TO NEAREST 0.1 FOOT.

1) Total Drilled Depth/Hole Diameter 62.0 / 7 7/8"

2) Casing/Screen Tally (Measured to Nearest 0.01 Foot)

(a) Sump & Plug Length 0.32

(b) Screen Length 20.08

(c) Casing Joint Lengths (Measured in Up-hole Sequence From Top of Screen) 10.06, 10.05, 10.05, 10.00, 2.74

(d) Depth to Top of Screen 40.08

3) Depths to Centralizers 19.0 & 39.0

4) Total Depth of Installed Well 60.48

5) Casing Stick Up (Standard 2.5' A.G.S.) 2.5

6) Depth to Top of Filter Pack 36.6

7) Depth to Top of Fine Sand Seal NA

8) Depth to Top of Bentonite Seal 18.9 - 48 hrs hydrated

9) Thickness of Grout 13.4 lb/gal

CLIENT WSRC

SUBJECT Well Construction

Prepared By Kelly Yantis Date 11/4/9.

PROJECT CENTRAL SHOPS BRP

Reviewed By Date

Approved By Date

CLIENT WSRC

SUBJECT Casing Tally

Prepared By Ante JAH Date 11/4/91

PROJECT CENTRAL SHOPS BRP

Reviewed By _____ Date _____

Approved By _____ Date _____

CBR-05

Casing Tally	Screen Zone	Materials List	Screen / Plug Tally
5.00	40.16 → 60.16	CASING - SCHEDULE 40 PVC 2" Ø	0.62
10.00			
10.05			
10.05		SCREEN - 0.016" SLOTTED 2" Ø PVC	
10.06			
45.16			
BORING TERMINATED @ 62.0' BGS			0.64
• SET WELL @ 60.48' BGS			0.62
• TOP OF SCREEN @ 40.16' BGS			
• TOP OF SAND @ 36.60			
• TOP OF BENTONITE @ 27.3'			
• GROUT TO SURFACE 13.4 lb/gal			
• 2 BUCKETS OF BENTONITE			0.62
2 (50 lb)			
• 8 (100 lbs) SAND			
• 3.5 BAGS PC			
		NA	SUMP
		PLUG	0.32

NOTE: PLACED SAND THROUGH TRIMMIE PIPE AND REMOVED 16' OF TRIMMIE PIPE AS APPROPRIATE TO ALLOW BENTONITE TO FALL TO THE TOP OF SAND. & IT APPEARS THERE IS A CLAY BALL

BETWEEN THE TOP OF THE SAND AND THE BOTTOM OF THE TRIMMIE PIPE, TOP OF THE BENTONITE WAS @ 27.5' BGS, THEREFORE LEAVING AN APPROXIMATE 5 FOOT SECTION ABOVE THE SAND PACK & BELOW THE BENTONITE SEAL WITHOUT A SEAL (VOID). BECAUSE THIS IS A PIEZOMETER AND OCCURED APPROXIMATELY 10 FEET ABOVE THE WATER TABLE WE ADDED AN ADDITIONAL BUCKET OF BENTONITE TO ENSURE AN ADEQUATE SEAL EXIST TO AVOID INTRUSION OF CEMENT GROUT, TOP OF BENTONITE @ 23.6' BGS.

CLIENT WSRC

 SUBJECT WELL CONSTRUCTION Prepared By KH Date 11/4/11

 PROJECT CENTRAL SHOPS BRP

Reviewed By _____ Date _____

Approved By _____ Date _____

CBR-04
Theoretical:
COARSE SAND

BOREHOLE DIAMETER - 7.875

BOREHOLE DEPTH - 62

SET WELL @ -60.48

TOP OF SAND (THEORETICAL) 38.48

 ONE BAG OF SAND (100 lb) = 1.2 ft³

$$V = \pi r^2 h$$

$$V = \pi \left(\frac{3.94}{12} \right)^2 (23.52) - \pi \left(\frac{1}{12} \right)^2 (22)$$

$$V = 7.48 \text{ ft}^3 \text{ OR } 6.23 \text{ BAGS OF SAND (100 lb)}$$

BENTONITE

$$V = \pi r^2 h = \pi \left(\frac{3.94}{12} \right)^2 (2) - \pi \left(\frac{1}{12} \right)^2 (2)$$

$$V = 0.6337 \text{ ft}^3$$

∴ - 1 Bucket BENTONITE

CBR-5

SRS MONITORING WELL INSTALLATION REPORT

Page 1 of 4

WELL NUMBER (AAA.N. A)

CBR 05

GENERAL

Project Name CENTRAL SHOPS BURNING RUBBLE PIT						
Project Manager (last name, first initial) TRAY PLUNKETT				Department GEO-ENVIRONMENTAL ENGINEERING		
Installation Purpose (Monitoring, Piezometer, etc.) TEMPORARY MONITORING		County BARNWELL		Location Description CENTRAL SHOPS BURNING RUBBLE PIT		
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)		Longitude (decimal degrees)	Ground Elev.	Top Casing Elev.
						Liq. Level Pipe Elev.

DRILLING & SAMPLING

Drilling Start Date 11/3/94		Drilling Comp Date 11/3/94		Total Drilled Depth 57		Init. Static Water Level/Date NA		Total Borehole Deviation (angle/direction) NA	
Drilling/Sampling Method	Top Depth	Bot Depth	Diameter	*	Drilling/Sampling Method	Top Depth	Bot Depth	Diameter	*
7 7/8" MUD ROTARY									
Drilling Company EMTC		Driller (last name, first initial) John SHOPE		Oversight Company RUST E & I			Oversight (last name, first initial) K. HUNTER		

Drilling & Sampling Comments (drilling muds used, source of water, lost circulation zones, etc.)

GEOPHYSICAL LOGGING

Date Logged	Logging Top Depth	Logging Bottom Depth	Logging Subcontractor	Logging Truck Operator
Geophysical Logs ☐ Caliper ☐ Gamma ☐ Natural Gamma ☐ Neutron Density ☐ Resistivity ☐ Single Pt. Resistivity ☐ L&S Normal Resistivity ☐ Spontaneous Potential Other Geophysical Logs (list)				
Backfill Top Depth	Backfill Bot Depth	Backfill Material (include type quantity and units)		

Elevations measured from height above MSL.

Depths measured from ground surface to nearest 0.1 ft.

* Enter an "X" if cuttings were taken.

50

WELL INSTALLATION (WELL MATERIALS)

Sieve Analysis?

FLUSH THE READER

MACHINE SLOTTED

Cap Type

7REMI - F1134

1

13.416/91

Report Prepared By

INTER

0180

11/01/17

Well Accepted By

Date _____

MONITORING WELL CONSTRUCTION DIAGRAM

DRILLING SUBCONTRACTOR EMTC

WELL NUMBER CBR-05

OPERATOR John Shope

SRS COORDINATES _____

DATE OF WELL INSTALLATION 11/3/94

SANITARY SEAL ELEVATION _____

TECH. O.S./CO. NAME Kelly Hunter/Rust E&I

NOTE: ALL MEASUREMENTS
ARE FROM GROUND
SURFACE AT START
OF BORING - MEASUREMENTS
TO NEAREST 0.1 FOOT.

1) Total Drilled Depth/Hole Diameter 57

2) Casing/Screen Tally (Measured to Nearest 0.01 Foot)

(a) Sump & Plug Length 0.20

(b) Screen Length 20.0

(c) Casing Joint Lengths (Measured in Up-hole Sequence From Top of Screen)

10.0, 10.0, 10.0, 5.0, 2.50

(d) Depth to Top of Screen 34.80

3) Depths to Centralizers 15.0 & 29.0

4) Total Depth of Installed Well 55.0

5) Casing Stick Up (Standard 2.5' A.G.S.) 2.5' A.G.S

6) Depth to Top of Filter Pack 32.95

7) Depth to Top of Fine Sand Seal NA

8) Depth to Top of Bentonite Seal 29.99

9) Thickness of Grout 13.4 16/21

CLIENT WSRC

SUBJECT Well Construction

Prepared By _____ ate _____

PROJECT _____

Reviewed By _____ Date _____

Approved By _____ Date _____

From
Bottom
Casing

CBR-05

From
Ground
Surface

+ 2.5

0

5.0

Gravel Pack

Theoretical

Coarse Sand - 6.5 BAGS

Fine Sand - NA

Bentonite - 1 BUCKET

Based on Practical

Application in the Field of

1 bag Coarse Sand = 1.2 ft³

1 bag Fine Sand =

1 bucket Bentonite = 0.7 ft³

Actual

Coarse Sand - 7 1/2 BAGS

Fine Sand -

Bentonite - 1 Bucket

35.0

55.0

57.0

BORING TERMINATED @ 57' BAGS

SET BOTTOM OF WELL / PLUG @ 55' BAGS

CLIENT WSRC

SUBJECT Casing Tally

PROJECT NO. _____

Prepared By Bill Date _____

PROJECT _____ Reviewed By _____ Date _____

Approved By _____ Date _____

Casing
Tally

Screen
Zone

Materials
List

Screen / Plug
Tally

5.00
2.50
10.00
10.00

TOP OF SCREEN 34.80

BOTTOM OF SCREEN 54.80

BOTTOM OF PLUG 55.00

TOP OF SAND @ 32.95

TOP OF BENT @ 29.99

0.05

10.00

*

0.20

0.05

10.00

0.20

NA
NA

SUM NA

0.20

PLUG

0.20

CLIENT WSRC

SUBJECT WELL CONSTRUCTION

Prepared By KH Date 11/4/04

PROJECT CENTRAL SHOPS BRP

Reviewed By _____ Date _____

Approved By _____ Date _____

CBR-05

Theoretical

COARSE SAND

BOREHOLE DIAMETER 7.875

DEPTH 57'

SET WELL 55'

TOP OF SAND (THEORETICAL) 32.8'

ONE BAG OF SAND (100 lb) = 1.2 ft³

$$V = \pi r^2 h$$

$$V = \pi \left(\frac{3.94}{12} \right)^2 (24.2) - \pi \left(\frac{1}{12} \right)^2 (22.2)$$

$$V = \pi (2.61) - \pi (0.154)$$

$$V = 7.71 \text{ ft}^3 \text{ OR } = 6.4 \text{ BAGS OF SAND}$$

(

CBR-6

(

1

GENERAL

Project Name

CENTRAL SHOPS BRP

Project Manager (last name, first initial)

RAY PLUNKETT

Installation Purpose (Monitoring, Piezometer, etc.)

TEMPORARY MONITORING

SRS North Grid Coordinate

SRS East Grid Coordinate

County

BARNWELL

Location Description

CENTRAL SHOPS BURNING RUBBLE PIT

Department

GO - ENVIRONMENTAL ENGINEERING

Longitude (decimal degrees)

Ground Elev.

Top Casing Elev.

Liq. Level Pipe Elev.

Drilling Start Date

11/3/94

Drilling Comp Date

11/3/94

Drilling Method

7 7/8" MUD ROTARY

Top Depth

Bot Depth

Diameter *

Total Drilled Depth

62.0

Init. Static Water Level/Date

NA

Total Borehole Deviation (angle/direction)

NA

Drilling/Sampling Method

Drilling/Sampling Method

Top Depth

Bot Depth

Diameter *

Driller (last name, initial)

SHOFF, J

Oversight Company

RUST E & F

Oversight (last name, initial)

HUNTER, K

Drilling & Sampling Comments (drilling muds used, source of water, lost circulation zones, etc.)

Date Logged

Logging Top Depth

Logging Bottom Depth

Logging Subcontractor

Logging Truck Operator

Geophysical Logs

☐ Caliper
☐ Gamma
☐ Natural Gamma
☐ Neutron Density
☐ Resistivity
☐ Single Pt. Resistivity
☐ L&S Normal Resistivity
☐ Spontaneous Potential

Other Geophysical Logs (list)

Backfill Top Depth

Backfill Bot Depth

Backfill Material (include type quantity and units)

Elevations measured from height above MSL. Depths measured from ground surface to nearest 0.1 ft. * Enter an "X" if cuttings were taken.

MONITORING WELL INSTALLATION REPORT

Page 2 of 4

WELL NUMBER (AAA,NNN,AA)

CBR

06

WELL INSTALLATION (WELL MATERIALS)

Date Well Installed	Installed By	Oversight	Had Centralizers	Centralizer Type	Sieve Analysis?	
11/3/94	EMTC	RUST E&F	2	2" STAINLESS STEEL	☐ Yes ☒ No	
CASING	Top Depth	Bot Depth	Material and Schedule	Diameter	Joint Type	
	2.2' AGH	40.2	SCHEDULE 40 PVC	2"	FLUSH THREADED	
SCREEN	Top Depth	Bot Depth	Material	Diameter	Slot Size	Slot Type
	40.2	60.2	PVC	2"	0.016	MACHINE SLOTTED
SUMP	Top Depth	Bot Depth	Material and Schedule	Diameter	Joint Type	
	NA					
SUMP CAP	Top Depth	Bot Depth	Material and Schedule	Diameter	Cap Type	
	0.20	60.4	PVC SCHEDULE 40	2"	FLUSH THREADED	

WELL INSTALLATION (ANNULAR MATERIALS)

FILTER PACK	Top Depth	Bot Depth	Trade Name	Grain Size (mm)	Amount (sacks)	Sack Size (lbs)	Installation Method
	2.0-35.90	62.0	FX 50	0.45-0.55	9.0	100	TRIMMIE - FLUSHED W/ WATER
FINE SAND SEAL	Top Depth	Bot Depth	Trade Name	Grain Size (mm)	Amount (sacks)	Sack Size (lbs)	Installation Method
	NA						
BENTONITE SEAL	Top Depth	Bot Depth	Hydration Time (hrs)	Amount	Units and Size (sacks, buckets, etc.)	Installation Method	
	32.50 35.90	35.90	30 hrs	1	BUCKET	TRIMMIE - FLUSHED W/ WATER	
GROUT	Top Depth	Bot Depth	Grout Mix	Amount (sacks)	Sack Size (lbs)	Grout Date	Installation Method
	32.50	32.50	13.2 lb/gal	5 BAGS	90	11/4/94	PRESSURE GROUTED W/ TRIMMIE

Report Prepared By

K. HUNTER

Date

11/10/94

Well Accepted By

Date

MONITORING WELL CONSTRUCTION DIAGRAM

DRILLING SUBCONTRACTOR EMTC

WELL NUMBER CBR-06

OWNER John Shope

SRS COORDINATES _____

DATE OF WELL INSTALLATION 11/3/94

SANITARY SEAL ELEVATION _____

TECH. O.S./CO. NAME K. Hunter

NOTE: ALL MEASUREMENTS
ARE FROM GROUND
SURFACE AT START
OF BORING - MEASUREMENTS
TO NEAREST 0.1 FOOT.

1) Total Drilled Depth/Hole Diameter 7 7/8"

2) Casing/Screen Tally (Measured to Nearest 0.01 Foot)

(a) Sump & Plug Length 0.20

(b) Screen Length 20

(c) Casing Joint Lengths (Measured in Up-hole Sequence From Top of Screen)

9.96, 10.00, 9.90, 9.95, 2.51

(d) Depth to Top of Screen 40.2

3) Depths to Centralizers 14-15 & 28-29

4) Total Depth of Installed Well 60.40

5) Casing Stick Up (Standard 2.5' A.G.S.) 2.2

6) Depth to Top of Filter Pack 35.90

7) Depth to Top of Fine Sand Seal NA

8) Depth to Top of Bentonite Seal 32.50

9) Thickness of Grout 32.50

Water Well Record

Prepared By K. HUNTER Date 11/3

Reviewed By _____ Date _____

Approved By _____ Date _____

CLIENT WSRC

SUBJECT Casing Tally

Prepared By Bill Date _____

PROJECT _____

Reviewed By _____ Date _____

Approved By _____ Date _____

CBR 06

Casing
Tally

Screen
Zone

Materials
List

Screen / Plug
Tally

SCREEN - 0.016" SCOTTED 2" Ø PVC

TOP OF SAND @ 35.9 0'

TOP OF BENTONITE @ 32.5'

BORING TERMINATED @ 62 ft BGS

SET WELL @ 60:40 w/ PLUG

9 (100 lb) BAGS OF SAND

GROUT MIX 13.2 lb/gal

5 BAGS PC (90 lb)

TOP OF SCREEN @ 60.2 → 40.2

CLIENT _____ SUBJECT _____ Prepared By _____ Date _____

PROJECT _____ Reviewed By _____ Date _____

_____ Approved By _____ Date _____

CBR-06

Theoretical:
COARSE SAND

BOREHOLE DIAMETER - 7.875

BOREHOLE DEPTH - 62.0

SET WELL @ - 60.40

TOP OF SAND @ - 35.90

 ONE BAG. OF SAND = 1.2 ft³
~~ONE BAG OF SAND~~

$$V = \pi r^2 h$$

$$V = \pi \left(\frac{3.94}{12} \right)^2 (26.10) - \pi \left(\frac{1}{12} \right)^2 (24.5)$$

$$V = 8.30 \text{ ft}^3 \text{ OR } 6.9 \text{ BAGS OF SAND}$$

Appendix D

Field Reports for Individual Boreholes

CS6G-11

CS6G-12

CS6G-13

CS6G-14

CS6G-15

CS6G-16

CS6G-17

CS6G-18

CS6G-19

CS6G-20

CS6G-21

CS6G-22

(

CS6G-11

(

SOIL BORING INSTALLATION REPORT

Boring Number (AAA,NNN,AAA)

C.S69

11

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	

SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation
---------------------------	--------------------------	----------------------------	-----------------------------	------------------

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 8 FT	Static Water Level NA	Drilling Start Date 11/14/94	Drilling Completion Date 11/14/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.) HP SCREENING OF COMPOSITE SAMPLES SCREENING WITH A ORGANIC VAPOR ANALYZER (OVA)
HAND AUGER	0-1			
" "	1-2			
SPLIT SPOON 3"	2-4			
" " "	4-6			
" " "	6-8			
" " "	8-10			

Drilling Company EET	Driller (last name, first initial) HOOD, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K
--------------------------------	--	--	--

Disposition of Samples GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment BACKFILLED WITH CUTTINGS	Materials Used in Abandonment NA
--	--

APPROVALS

Abandonment Verified By KELLY HUNTER	Date 11/14/94	Boring Installation Report Prepared By KELLY HUNTER	Date 11/29/94
--	-------------------------	---	-------------------------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL STOPS BRP		DATE	4/14/94	SHEET	1 of 1
WELL NO.		C566-11		REFERENCE DATUM	DRILLING CONTRACTOR E.E.I.		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER H. HOOD		
		COMPANY RUST E&I		DRILLING METHOD 3 1/4 ID HSA			

RUN NUMBER	DEPTH FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			CLAY, moderate yellowish brown (10Yr 4/2)	HAND AUGER
				med to fine sand, moist-wet,	0-1
				med plasticity (SC)	
2	1			Sandy CLAY, very pale orange (10Yr 8/2)	HAND AUGER
	2			TO DARK yellowish orange (10Yr 6/6),	1-2
				med-fine sand, med-plasticity stiff-HARD (SC)	
3	3			SANDY CLAY, Dark yellowish orange (10Yr 6/6)	SPLIT SPOON
				very pale orange (10Yr 8/2), med-fine grained	2-4
				rounded, med plasticity SC	
4	4				
	5			SANDY CLAY, Light brown (5Yr 5/6)	
				med-fine grained, low plasticity	N-10-14-14-30
				(SC) HARD	
	6				
5	7			SANDY CLAY, very pale orange (10Yr 8/2)	
	8			med-fine grained, rounded, high plasticity	
				SC	
6	9				
	0			DRILLING TERMINATED @ 8' BGS	
				TOOK A SPOON FROM 8'-10' BGS	
	1				
	2				
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-12

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, NNN, XXX)

CS6G | 12 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	

SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation
---------------------------	--------------------------	----------------------------	-----------------------------	------------------

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 6' BAS	Static Water Level NA	Drilling Start Date 11/15/94	Drilling Completion Date 11/15/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.) HP SCREENING OF COMPOSITE SAMPLES SCREENING WITH OVA
HAND AUGER	0-1			
" "	1-2			
SPLIT SPoon 3"	2-4			
" " 3"	4-6			
" " 3"	6-8			

Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company TRUST E & I	Oversight (last name, first initial) HUNTER, K
-------------------------	---	----------------------------------	---

Disposition of Samples GENERAL ENGINEERING LABORATORIES
--

ABANDONMENT

Method of Abandonment BACKFILL W/ SOIL CUTTINGS	Materials Used In Abandonment NATIVE SOIL
--	--

APPROVALS

Abandonment Verified By K. HUNTER	Date 11/15/94	Boring Installation Report Prepared By KELLY HUNTER	Date 11/29/94
--------------------------------------	------------------	--	------------------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BURNING RUBBLE PIT		DATE	11/15/94	SHEET	1 of 1
WELL NO.		CS6G-12		REFERENCE DATUM	DRILLING CONTRACTOR FEI		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER H. HOOD		
		COMPANY RUST E & I		DRILLING METHOD 3/4 ID HSA			

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			FILL: SAND silty, moderate yellowish brown (5% 5/4), fine grained sand, moist (5M) - cobble stones @ 1' BGS	HAND AUGER FROM 0-1 AND FROM 1-3
2	1			1.0-1.5 - SILT sandy, burn material, high organic	
3	2			Dusky blue (SPR 3/2) - 1.5-2.0 SAND, grayish orange (10% 7/4), fine-med grained	SPLIT SPOON SAMPLING THEREAFTER
3	3			2.0-2.5 SAND, silty, grayish orange (10% 7/4), fine-med	
4	4			2.5-3.5 - CLAY sandy, pale yellowish brown 10% 6/2, fine-medium medium plasticity (CL) - 3.5-4.0 CLAY sandy, marbled dark yellowish orange 10% 6/6 & pale yellowish brown 10% 6/2, low plasticity	
4	5			RESIDUUM: CLAY, sandy, marbled dark yellowish orange (10% 6/4) & pale yellowish brown (10% 6/2) Low plasticity (CL)	
5	6				
5	7			SAME AS ABOVE	
	8				
	9			BORING TERMINATED @ 6' BGS	
	0				
	1				
	2				
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-13

SOIL BORING INSTALLATION REPORT

Boring Number (AAA,NNN,AAA)

C.S69 | 13 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC	
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA		
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 6' BHS	Static Water Level NA	Drilling Start Date 11/15/94	Drilling Completion Date 11/15/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1			
"	1-2			
SPLIT SPOON	2-4			
"	4-6			
"	6-8			
Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K	

Disposition of Samples

GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment BACKFILL w/ SOIL CUTTINGS	Materials Used in Abandonment NA
--	-------------------------------------

APPROVALS

Abandonment Verified By K. HUNTER	Date 11/15/94	Boring Installation Report Prepared By KELLY HUNTER	Date 11/29/94
--------------------------------------	------------------	--	------------------

D-5

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BURNING RUBBLE PITS		DATE 11/15/94	SHEET 1 of 1
WELL NO. CS66-13		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
COMPANY RUST E & I		DRILLING METHOD 3 1/4 ID HSA	

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			Fill: Clay sandy, moderate yellowish brown (10Yr 3/4)	
2	1			Fine grained - 70.5 to 1.0 BURN MATERIAL, ASH BLACK WITH ORGANICS	HAND AUGER
3	2			SAME AS 0.5 to 1.0 WITH OLD NAILS, COPPER WIRE	
4	3			SAND, silty light olive gray (5GY 6/1) - fine grained, rounded	SPLIT SPOON
5	4			24" to 30" BURN MATERIAL AS DESCRIBED ABOVE	
	5			30" to 46" CLAY, sandy - light olive gray (5Y 9/1) rounded	
	6			Fine-med grained - 46" to 48" RESIDUUM: CLAY, sandy, very pale orange (10Yr 8/2), med-fine grained rounded low plasticity	
	7			SAME AS ABOVE 46" to 48"	
	8			SAME AS ABOVE	
	9			BORING TERMINATED @ 6'	
	10				
	11				
	12				
	13				
	14				
	15				
	16				
	17				
	18				
	19				
	20				
	21				
	22				
	23				
	24				
	25				
	26				
	27				
	28				
	29				
	30				

CS6G-14

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, NNN, AAA)

CS6G | 14 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC	
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA		
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 13	Static Water Level NA	Drilling Start Date 11/16/94	Drilling Completion Date 11/16/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1			
" "	1-2			
SPLIT SPOON	2-4			
" "	4-6			
" "	6-8			
" "	8-10			
" "	13-15			
Drilling Company EEI		Driller (last name, first initial) HOOB, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K

Disposition of Samples

ABANDONMENT

Method of Abandonment	Materials Used In Abandonment
-----------------------	-------------------------------

APPROVALS

Abandonment Verified By	Date	Boring Installation Report Prepared By	Date
-------------------------	------	--	------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BRP		DATE	11/16/94	SHEET	1 of 1
WELL NO.		CS67-14		REFERENCE DATUM	DRILLING CONTRACTOR E.E.I.		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER H. HOOD		
		COMPANY RUST E & I		DRILLING METHOD 3 1/4 ID HSA			

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			ELL: Silty SAND, Olive gray (5Y 4/1)	HAND AUGER
				fine grained, moist (SM)	0-1'
2	1			SAA EXCEPT LIGHT BROWN (5Y 6/4)	HAND AUGER
	2				1-2'
3	3			clayey SAND, Light Brown (5Y 6/4)	SPLIT SPOON
				fine grained, moist (CL)	2-4'
	4			FROM 4-5' (SAA) (SAME AS ABOVE)	
4	5			FROM 5-6 - BURN MATERIAL, BLACK	
	6	BURN MATERIAL		BURNED WOOD, GLASS FRAGMENTS, MISC. NATLS,	
				YELLOW PLASTIC, CONCRETE RUBBLE, WET	
5	7			6-7 - BURN MATERIAL AS DESCRIBED	
	8			ABOVE - 7-8' RESIDUUM Light Brown	
				(5Y 5/6) SANDY CLAY WITH Very Pale	
				orange (10YR 8/2) CLAY INTERBEDDED W/	
				Sand fine grained rounded, Dry (CL)	
				SAA FROM 7-8' BGS	
	9				
	10				
	11				
	12				
	13			PURCHED H ₂ O @ 12-13 BGS	
	14			13-15 - CLAY INTERBEDDED Very Pale	
				Orange (10YR 8/2) 2nd Light Brown	
				(5Y 5/6) - HIGH PLASTICITY, Saturated	
				(CH)	
	16				
	17			BORING TERMINATED @ 17 BGS	
	18				
	19				
	20				

CS6G-15

SRS SATURN RIVER SITE	SOIL BORING INSTALLATION REPORT		Boring Number (AAA,NNN,AAA)
			CS69 15

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	

SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 10	Static Water Level NA	Drilling Start Date 11/17/94	Drilling Completion Date 11/17/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0 - 1			
" "	1 - 2			
SPLIT SPOON	2 - 4			
" "	4 - 6			
" "	10 - 12			

Drilling Company E E I	Driller (last name, first initial) HOOD, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K
----------------------------------	--	--	--

Disposition of Samples GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment BACKFILL WITH SOIL CLINKERS	Materials Used in Abandonment NA
---	--

APPROVALS

Abandonment Verified By K. HUNTER	Date 11/17/94	Boring Installation Report Prepared By K. HUNTER	Date 11/29/94
---	-------------------------	--	-------------------------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BRP		DATE	11/19/94	SHEET	1 of 1
WELL NO.		CSGG-15		REFERENCE DATUM	DRILLING CONTRACTOR E.E.F.		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER H. HOOD		
				COMPANY	DRILLING METHOD 3/4 ID HSA		
RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION		DRILLING COMMENTS	
1	0			FILL: SILTY SAND, OLIVE GRAY (5Yr 4/1)			
				FINE GRAINED; MOIST (SM)			
2	1			1'-1.5' SAA - 1.5-2.0 SILTY SAND, DARK			
				YELLOWISH ORANGE, FINE GRAINED, MOIST (SM)			
3	2			SOME METAL SHAVINGS			
				2-2.5 SAA			
4	3			2.5-4.0 - RESIDUAL SILTY CLAY, VERY			
				PALE ORANGE (10Yr 8/2) INTERBEDDED			
				WITH LIGHT BROWN (5Yr 5/6) - FINE GRAINED			
				MOIST (CL)			
				SAA			
	6						
	7			NOT SAMPLED			
				BUT ASSUMED CLAY			
	8						
	9						
	10						
5	11			SAA			
	12						
	3			BORING TERMINATED @ 10'			
				BGS			
	4						
	5						
	6						
	7						
	8						
	9						
	0						

CS6G-16

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, NNN, AAA)

CS69 | 16 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC	
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA		
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 10 ft BGS	Static Water Level NA	Drilling Start Date 11/17/94	Drilling Completion Date 11/17/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1			
" "	1-2			
SPLIT SPIN 3"	2-4			
" " "	4-6			
" " "	10-12			
Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company RUST E&I	Oversight (last name, first initial) HUNTER, K	
Disposition of Samples GENERAL ENGINEERING LABORATORIES				
ABANDONMENT				
Method of Abandonment BACKFILL W/ NATIVE SOIL CUTTINGS	Materials Used In Abandonment NA			
APPROVALS				
Abandonment Verified By K. HUNTER	Date 11/17/94	Boring Installation Report Prepared By K. HUNTER	Date 11/29/94	

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/17/94	SHEET 1 OF 1
WELL NO. CS6G-16		REFERENCE DATUM	DRILLING CONTRACTOR EET
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HODD
COMPANY RUST E & I		DRILLING METHOD 3/4 ID HSA	

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			SAND silty, moderate yellowish brown 10 Yr (5/4), fine grained moist	0-1 HAND AUGER
2	1			1.0' to 1.5' SAME AS ABOVE	
3	2			1.5 to 2.0 SAND, silty, grayish black (N2) fine grained, moist (SM)	1-2 SPLIT SPOON
4	3			2.0 to 2.5 - SAME AS ABOVE - 2.5-3.5 SILT, grayish black (N2), wet	
	4			3.5 to 4.0 - SM CLAY sandy, medium light gray (N6), wet moist, fine grained (CL)	
	5			4.0 to 5.5 SAME AS ABOVE	
	6			5.5 to 6.0 CLAY, sandy pale yellowish brown (10 Yr 4/2), light brown (5 Yr 5/6), fine grained, HARD (CL)	
	7				
	8				
	9				
5	0			CLAY, sandy, w/ QUARTZ FRAGMENTS, med fine grained, very light gray, HARD, med plasticity, (CH)	
	1				
	2				
	3				
	4			BORING TERMINATED AT 10' BGS	
	5				
	6				
	7				
	8				
	9				
	0				

(

CS6G-17

(

(

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, BBB, AAA)

CS69 | 17

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC	
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA		
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 10	Static Water Level NA	Drilling Start Date 11/17/94	Drilling Completion Date 11/17/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1			
" "	1-2			
SPLIT SPOON 3"	2-4			
" "	5-7			
" "	10-12			
Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K	

Disposition of Samples

GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment BACKFILL W/ NATIVE SOIL CUTTINGS	Materials Used in Abandonment NA
---	-------------------------------------

APPROVALS

Abandonment Verified By HUNTER, K	Date 11/17/94	Boring Installation Report Prepared By HUNTER, K	Date 11/29/94
--------------------------------------	------------------	---	------------------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL STOPS BR		DATE	11/17/94	SHEET	1 OF 1
WELL NO.		CS66-17		REFERENCE DATUM	DRILLING CONTRACTOR		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER		
				COMPANY	RUST E&I		
				DRILLING METHOD	3 1/4 ID HSH		

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			0'-8" SAND, Grayish orange (10Yr 7/4), fine grained moist - 8"-12" sandy CLAY, LIGHT BROWN (5Yr 6/4) fine-med grained (CL) 8" →	RESIDUUM FROM
2	1			SAA FROM 8"-12"	
3	2			SAA	
	3				
	4				
4	5			RESIDUUM:	
	6			CLAY, INTERBEDDED, VERY PALE ORANGE (10Yr 8/2) and light brown (5Yr 6/4), med plasticity, moist, HARD (CH)	
	7				
	8				
	9				
	10			CLAY VERY PALE ORANGE (10Yr 8/2)	
5	11			HIGH PLASTICITY, moist, HARD-VERY HARD (CH)	
	12				
	3			BORING TERMINATED	
	4			10' BGS	
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-18

2018-2019

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, BBB, AAA)

CS69 | 18 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	

SRS North Grid Coordinate 45	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation
---------------------------------	--------------------------	----------------------------	-----------------------------	------------------

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 45	Static Water Level 43	Drilling Start Date 11/18/94	Drilling Completion Date 11/18/94	Drilling Method 3 1/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1	SPLIT SPOON	40-42	
"	1-2	"	43-47	
SPLIT SPOON	2-4			
"	5-7			
"	10-12			
"	15-17			
"	20-22			
"	25-27			
"	30-32			
"	35-37			

Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company RUST E & I	Oversight (last name, first initial) HUNTER, K
-------------------------	---	---------------------------------	---

Disposition of Samples GENERAL ENGINEERING LABORATORIES
--

ABANDONMENT

Method of Abandonment PRESSURE GROUT 13.5 lb/gal	Materials Used in Abandonment 6 BAGS OF PORTLAND CEMENT & BENT BOWDER
---	--

APPROVALS

Abandonment Verified By K. HUNTER	Date 11/23/94	Boring Installation Report Prepared By K. HUNTER	Date 11/29/94
--------------------------------------	------------------	---	------------------

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/18/94	SHEET 1 of 3
WELL NO. C569-18		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST E&I	DRILLING METHOD 3/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			Clayey SAND, Moderate brown (5Yr 4/4), 0-1' HAND AUGER fine-med grained, (CL) (MOIST)	
2	1			Sandy CLAY, Light brown (5Yr 5/6), fine grained, (CL)	1-2 HAND AUGER
3	2			SAA	SPLIT SPOON
	3				
	4				
4	5			Silty SAND, w/ QUARTZ FRAGMENTS, ^{fine} gravel, light brown (5Yr 5/6), HARD-VERY HARD, MOIST, med-coarse, rounded & angular (SP)	
	6				
	7				
	8				
	9				
5	10			Clayey SAND, w/ QUARTZ FRAGMENTS, fine-coarse gravel, Greenish red purple (5 RP 4/2), angular, (CL)	
	11				
	12				
	13				
	14				
6	15			SAA	
	16				
	17				
	18				
	19				
	20				

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/18/94	SHEET 2 of 2
WELL NO. CS66-18		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
COMPANY RUST E&I		DRILLING METHOD 3 1/4 ID HSA	

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
7	20			clayey SAND, SPECKLED moderate	SPLIT SADDON
	21			pink (SR 7/4), Grayish pink (SR 8/2),	
	22			light red (SR 6/2), Sand coarse rounded,	
8	23			gravel w/ QUARTZ FRAGMENTS, very hard	
	24			(CL)	
	25			SAA WITH HIGHER CLAY CONTENT	
9	26			LESS HARD, HARD	
	27				
	28			mm — PARCHED H ₂ O ZONE — mm	
10	29				
	30				
	31			CLAY, CLEAN NO SAND, GRAYISH red	
10	32			purple, moist (SRP 6/2), HIGH	
	33			PLASTICITY (CH) STIFF	
	34				
10	35			SAA	
	36				
	37				
10	38				
	39				
	40				

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BRP		DATE	11/18/94	SHEET	3 of 3
WELL NO.		CS66-18		REFERENCE DATUM			
LOGGED BY		K. HUNTER		SRP COORDINATES			
COMPANY		RUST E&I		DRILLING CONTRACTOR	EEI		
DRILLER		H. HOOD		DRILLING METHOD	3/4 ID HSA		

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
11	40				SPLIT SPOON
	41			SAA	
	42				
	43				
	44				
12	45				↓
	46			SAA w/ MICACEOUS - SATURATED LESS DENSE	
	47				
	48			BORING TERMINATED	
	49			@ 45' BGS	
	50				
	1				
	2				
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-19

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, BBB, CCC)

CS6G | 19 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PIT		Project Manager RAY PLUNKETT	Department WSRC
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)
			Ground Elevation

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 45	Static Water Level 42	Drilling Start Date 11/22/94	Drilling Completion Date 11/22/94	Drilling Method 3/4 ID HSA
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0-1	SPLIT SPOON	40-42	
"	1-2	"	45-47	
SPLIT SPOON	2-4			
"	5-7			
"	10-12			
"	15-17			
"	20-22			
"	25-27			
"	30-32			
"	35-37			
Drilling Company EEI	Driller (last name, first initial) HOOD, H	Oversight Company RUST E&I	Oversight (last name, first initial) HUNTER, K	

Disposition of Samples

GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment PRESSURE GROUT 13.5 LB/gal	Materials Used in Abandonment 6 BAGS OF PORTLAND CEMENT & BENTONITE POWDER
---	---

APPROVALS

Abandonment Verified By K. HUNTER	Date 11/22/94	Boring Installation Report Prepared By K. HUNTER	Date 11/29/94
--------------------------------------	------------------	---	------------------

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BRP		DATE	11/22/94	SHEET	1 of 3
WELL NO.		CS66-19		REFERENCE DATUM	DRILLING CONTRACTOR		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER		
COMPANY		RUST E&I		DRILLING METHOD		3 1/4 ID HSA	
RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION		DRILLING COMMENTS	
1	0			SAND, GRAYISH ORANGE 10Yr 7/4, fine grained, moist,		0-1 - HAND AUGER	
2	1			SAA TO 10" - SILTY SAND, GRAYISH ORANGE, (10Yr 7/4), fine grained, moist (SM)		1-2	
3	2			SANDY CLAY (SL), LIGHT BROWN (5Yr 5/6), pale yellowish brown (10Yr 6/2), fine-grained, moist, low plasticity (CL)		2-4 SPLIT SPOON	
	3						
	4						
	5			SANDY CLAY, light brown (5Yr 5/6), VERY PALE ORANGE (10Yr 8/2), fine-grained, moist, very hard (CL)			
4	6						
	7						
	8						
	9						
	10			CLAY, Grayish red purple (5RP 4/2), interbedded very pale orange (10Yr 8/2), very hard, low plasticity, (CL)			
5	11						
	12						
	13						
	14						
	15			CLAY, Grayish red purple (5RP 4/2) yellowish gray (5Y 8/1), very hard, moderate plasticity, (CL), micaceous			
6	16						
	17						
	18						
	19						
	20						

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/22/94	SHEET 2 of 3
WELL NO. CS66-19		REFERENCE DATUM	DRILLING CONTRACTOR
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST E&I	DRILLING METHOD 3/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
7	20				SPLIT SPOON
	21			Sandy CLAY, moderate red (SR 4/6), medium angular, moist, (CL)	
	22				
	23				
	24				
8	25			CLAY, Pale red purple (SR 6/2), high plasticity, moist (CH) (HARI)	
	26				
	27				
	28				
	29				
9	30			Sandy CLAY, moderate red (SR 4/6), low plasticity, moist, micaceous (CL)	
	31				
	32				
	33				
	34				
10	35			CLAY, Pale purple (SR 6/2), no sands, med plasticity, moist, micaceous, (CL)	
	36				
	37				
	38				
	39				
	40				

FIELD GEOLOGIC LOG

PROJECT		CENTRAL SHOPS BRP		DATE	11/22/94	SHEET	3 of 3
WELL NO.		CSGG -19		REFERENCE DATUM	DRILLING CONTRACTOR EEI		
LOGGED BY		K. HUNTER		SRP COORDINATES	DRILLER H. HOOD		
				COMPANY	RUST E&I		
					DRILLING METHOD 3 1/4 ID HSA		

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
11	40			Sandy CLAY, quartz fragments, pale purple (SP 1/2), (CL)	SPLIT SPOON
	41				
	42				
	43				
12	44			(5 R 3/4) Sand, moderate pink, fine-med, saturated rounded, some quartz fragments	↓
	45				
	46				
	47				
	8			BORING TERMINATED @ 45' BGS	
	9				
	0				
	1				
	2				
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-20

2000-01-01 to 2000-01-01

SOIL BORING INSTALLATION REPORT

Boring Number (AMN, HNT, AMY)

0567 20

GENERAL INFORMATION

Project Name CENTRAL SHOPS RUBBER PIT		Project Manager RAY PLUNKETT		Department USREC EIR	
Boring Purpose SOIL SAMPLING		County BARNWELL		Location Description CENTRAL SHOPS BRR	

SRS North Grid Coordinate		SRS East Grid Coordinate		Latitude (decimal degrees)		Longitude (decimal degrees)		Ground Elevation	
---------------------------	--	--------------------------	--	----------------------------	--	-----------------------------	--	------------------	--

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 45	Stallio Water Level NA	Drilling Start Date 12/28/94	Drilling Completion Date 12/30/94	Drilling Method 3 1/4 ID 1154
---------------------------	---------------------------	---------------------------------	--------------------------------------	----------------------------------

Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (include drilling muds used, source of water, lost circulation zones, etc.)
1-AND AUGER	0-1	SPLIT SPOON	40-42	
LC	1	1-2	45-47	
SPLIT SPOON	2-4			
LC	5-7			
11	10-12			
11	15-17			
11	20-22			
11	25-27			
11	30-32			
11	35-37			

Drilling Company EEI	Driller (last name, first initial) HOOD, H	Overight Company RUST E & I	Overight (last name, first initial) HUNTER, K
-------------------------	---	--------------------------------	--

Disposition of Samples

GENERAL ENGINEERING LABORATORIES

ABANDONMENT

Method of Abandonment PRESSURE GROUT w/ TRIMMITE	Materials Used in Abandonment PORTLAND CEMENT/BENTONITE SLURRY GROUT
---	---

APPROVALS

Abandonment Verified By K. Hunter	Date 11/30/94	Boring Installation Report Prepared By KELLY HUNTER	Date 12/5/94
--------------------------------------	------------------	--	-----------------

D-23

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS TRP		DATE 11/28/94	SHEET 1 of 3
WELL NO. CSOG-20		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST E&I	DRILLING METHOD 3/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
1	0			Clayey SAND, Dark yellowish orange (10 Yr 6/6), INNER-BEDED WITH p.p.	HAND AUGER
2	1			yellowish brown (10 Yr 6/2), fine grained	
	2			ROUNDED, MOIST (SC)	
3	3			Sandy CLAY, pale yellowish orange (10 Yr 8/6),	SPLIT SPOON
	4			fine grained, rounded moist (CL)	
	5				
4	6			Clayey SAND, Dark yellowish orange (10 Yr 6/6), fine grained, moist (CL)	
	7				
	8				
	9				
5	10			CLAY, Pale greenish yellow (10 Y 8/2)	
	11			moist, med plasticity (CL), Pale reddish brown (10 R 5/4)	
	12				
	13				
	14				
6	15			Sandy CLAY, Dark reddish brown (10 R 3/4), Very pale orange (10 Y 3/2), (CL)	
	16				
	17				
	18				
	19				
	20				

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/30/94	SHEET 2 of 3
WELL NO. CS67-20		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST E & I	DRILLING METHOD 3/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
7	20			CLAY, Very pale orange (10Yr 8/2), Grayish red purple (5RP 4/2), (CH) high plasticity (CH)	SPLIT SPOON
	21				
	22				
8	23				
	24				
	25				
9	26			SAA	
	27				
	28				
10	29				
	30				
	31				
	32				
	33				
	34				
	35				
	36				
	37				
	38			SAND, moderate orange pink (10R 7/4), fine grained	
	39				
	40				

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 11/30/94	SHEET 3 of 3
WELL NO. CS66-20		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST EEI	DRILLING METHOD 3 1/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT. RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
11	40			Sandy SILT, Very pale orange (10Yr 8/2), fine grained, STIFF (SM)	SPLIT SPOON
	41				
	42				
	43				
	44				
12	45			SAA	
	46				
	47				
	48				
	49				
	50				
	51				
	52				
	53				
	54				
	55				
	56				
	57				
	58				
	59				
	60				
	61				
	62				
	63				
	64				
	65				
	66				
	67				
	68				
	69				
	70				

BORING TERMINATED @ 45' BGS

CS6G-21

SRS SAVANNAH RIVER SITE	SOIL BORING INSTALLATION REPORT		Boring Number (AAA, NNN, AAA) CS69 21	

GENERAL INFORMATION

Project Name CENTRAL SHOPS BURNING RUBBLE PCT.		Project Manager RAY PLUNKETT	Department WSR ER
Boring Purpose SOIL SAMPLING	County BARNWELL	Location Description CENTRAL SHOPS AREA	
SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)
Ground Elevation			

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 45	Static Water Level NA	Drilling Start Date 12/1/94	Drilling Completion Date 12/1/94	Drilling Method 3 1/4 ID HSA
Sample Type HAND AUGER	Sampling Interval 0-1	Sample Type SPLIT SPOON	Sampling Interval 40-42	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
"	1-2	"	45-47	
SPLIT SPOON	2-4			
"	5-7			
"	10-12			
"	15-17			
"	20-22			
"	25-27			
"	30-32			
"	35-37			
Drilling Company L E I	Driller (last name, first initial) HOOD, H	Oversight Company TRUST E & I	Oversight (last name, first initial) HUNTER, K	

Disposition of Samples GENERAL ENGINEERING LABORATORIES
--

ABANDONMENT

Method of Abandonment PRESSURE GROUT - TRIMMITE	Materials Used in Abandonment PORTLAND CEMENT BENTONITE SLURRY GROUT
--	---

APPROVALS

Abandonment Verified By K. HUNTER	Date 12/1/94	Boring Installation Report Prepared By K. HUNTER	Date 12/5/94
--------------------------------------	-----------------	---	-----------------

D-27

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHAYS BRP		DATE 12/1/94	SHEET 1 of 3
WELL NO. CS66-21		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST EEI	DRILLING METHOD 3 1/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
	0			RESIDUUM:	
1				Sandy CLAY, Dark yellowish orange (10Yr 6/10), moderate red (5R 4/4); some peat, fine grained, moist (CL)	HAND AUGER
2	1			SAA, NO PEAT	
	2				
3	3			SAA, NO PEAT	SPLIT SPOON
	4				
	5			Sandy CLAY, Very pale orange (10Yr 8/2), Light Brown (5Yr 5/6), fine grained, DAMP, VERY HARD, (CL)	
4	6				
	7				
	8				
	9				
	10				
5	11			SAA	
	12				
	13				
	14				
	15			CLAY, Very pale orange (10Yr 8/2), Light Brown (5Yr 5/6), pale red purple (5R 4/2), VERY HARD, DAMP (CH)	
6	16			HIGH PLASTICITY	
	17				
	18				
	19				
	20				

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 12/1/94	SHEET 2 of 3
WELL NO. CS66-21		REFERENCE DATUM	DRILLING CONTRACTOR EEI
LOGGED BY K. HUNTER		SRP COORDINATES	DRILLER H. HOOD
		COMPANY RUST E&I	DRILLING METHOD 3/4 ID HSA

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
7	20			CLAY, Grayish red purple (SRP 4/2), HIGH PLASTICITY, DAMP, VERY HARD, (CH)	SPLIT SPOON
	21				
	22				
8	23				
	24				
	25				
	26				
	27				
9	28			CLAY, yellowish gray (SY 8/1), Grayish red purple (SRP 4/2), HIGH PLASTICITY DAMP, VERY HARD, (CH)	
	29				
	30				
	31				
	32				
10	33			CLAY, very pale orange (10YR 8/2), HIGH PLASTICITY, DAMP, VERY HARD (CH)	
	34				
	35				
	36				
	37				
	38			CLAYEY SAND, WHITE (N7), fine grained, DAMP, HARD (CL)	
	39				
	40				

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 12/1/94	SHEET 3 of 3
REFERENCE DATUM		DRILLING CONTRACTOR EEI	
WELL NO. CS66-21	SRP COORDINATES	DRILLER H. HOOD	
LOGGED BY K. HUNTER	COMPANY RUST E&I	DRILLING METHOD 3/4 ID HSA	

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
	40			SAA	SPOT SPOON
	41				
	42				
	43				
	44				
	45			SAA	
	46				
	47				
	-8			BORING TERMINATED	
	9			@ 45	
	0				
	1				
	2				
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	0				

CS6G-22

SOIL BORING INSTALLATION REPORT

Boring Number (AAA, XXX, AAA)

C566 | 22 |

GENERAL INFORMATION

Project Name CENTRAL SHOPS BRP		Project Manager RAY PLUNKETT	Department GO-ENVIRONMENTAL ENGINEERING
Boring Purpose SOIL BORING	County BARNWELL	Location Description CENTRAL SHOPS BURNING RUBBLE PIT	

SRS North Grid Coordinate	SRS East Grid Coordinate	Latitude (decimal degrees)	Longitude (decimal degrees)	Ground Elevation
---------------------------	--------------------------	----------------------------	-----------------------------	------------------

DRILLING & SAMPLING INFORMATION

Total Drilled Depth 3.5	Static Water Level NA	Drilling Start Date 12/6/94	Drilling Completion Date 12/6/94	Drilling Method HAND AUGER - STAINLESS STEEL
Sample Type	Sampling Interval	Sample Type	Sampling Interval	Drilling & Sampling Comments (Include drilling muds used, source of water, lost circulation zones, etc.)
HAND AUGER	0 - 1			
"	1 - 2			
"	2 - 3.5			

Drilling Company NA	Driller (last name, first initial) NA	Oversight Company RUST E&I	Oversight (last name, first initial) HUNTER, K
------------------------	--	-------------------------------	---

Disposition of Samples GENERAL ENGINEERING LABORATORIES
--

ABANDONMENT

Method of Abandonment BACKFILL WITH CUTTINGS	Materials Used in Abandonment SOIL CUTTINGS
---	--

APPROVALS

Abandonment Verified By K. J. [Signature]	Date 12/6/94	Boring Installation Report Prepared By	Date
--	-----------------	--	------

FIELD GEOLOGIC LOG

PROJECT CENTRAL SHOPS BRP		DATE 12/10/94		SHEET 1 of 1	
WELL NO. CS66-22		REFERENCE DATUM		DRILLING CONTRACTOR NA	
LOGGED BY K. HUNTER		SRP COORDINATES		DRILLER NA	
		COMPANY RUST E&I		DRILLING METHOD HAND AUGER	

RUN NUMBER	DEPTH, FEET	LITHOLOGY	PERCENT RECOVERY	SAMPLE DESCRIPTION	DRILLING COMMENTS
	0			FILL	HAND AUGER
1	0.5			Sandy CLAY, moderate reddish orange (10R 6/6), 2nd Pale Red (10R 6/2)	
2	1			S&A TO 18" - 18" - 24" BURN MATERIAL	
3	2			GRAVEL, SILTY SAND, MISC nails, wood particles & metal fragments; Black, Saturated	
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	10				
	11				
	12				
	13				
	14				
	15				
	16				
	17				
	18				
	19				
	20				
	21				
	22				
	23				
	24				
	25				
	26				
	27				
	28				
	29				
	30				
	31				
	32				
	33				
	34				
	35				
	36				
	37				
	38				
	39				
	40				
	41				
	42				
	43				
	44				
	45				
	46				
	47				
	48				
	49				
	50				
	51				
	52				
	53				
	54				
	55				
	56				
	57				
	58				
	59				
	60				
	61				
	62				
	63				
	64				
	65				
	66				
	67				
	68				
	69				
	70				
	71				
	72				
	73				
	74				
	75				
	76				
	77				
	78				
	79				
	80				
	81				
	82				
	83				
	84				
	85				
	86				
	87				
	88				
	89				
	90				
	91				
	92				
	93				
	94				
	95				
	96				
	97				
	98				
	99				
	100				

Appendix E

Daily Sign-In/Out Logs and Work Zone Entry/Exit Logs

Daily Sign-In/Out Logs

DAILY SIGN-IN/OUT LOG

PROJECT: 88351.000
PROJECT NO.: CENTRAL CHAPS BRP
SITE LOCATION:
HSO: K. HUNTER
DATE: 11/2/94
PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI

PROJECT LOCATION: Central Shops

PROJECT NO.: 12081 ADA 88351.000

SITE SAFETY OFFICER: K. HUNTER

DATE: 11/3/94

PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12084 RDH 98357.000
SITE SAFETY OFFICER: Kelly Hunter
DATE: 11/4/94
PAGE NO.: 1 of 1 =

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 NDH 84351.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/14/94
PAGE NO.: 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 N-DJ 00357.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/15/94
PAGE NO.: 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP. 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: ~~22081-98357.000~~
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/16/94
PAGE NO.: 1 =

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 ADA 958,357.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/17/94
PAGE NO.: 1 of 1 =

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 MDN 489,357.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/18/94
PAGE NO.: 1 OF 1 =

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 MPA 9.0351.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/22/94
PAGE NO.: 1 =

DAILY SIGN-IN/OUT LOG

PROJECT: Central Shops BRP, 631-6G RI
PROJECT LOCATION: Central Shops
PROJECT NO.: 12081 MDH - 052957.000
SITE SAFETY OFFICER: K. HUNTER
DATE: 11/28/94
PAGE NO.: 1 OF 1 =

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: CENTRAL SHOPS B2P
PROJECT NO.: 12681-MNH 99357.000
SITE LOCATION: CENTRAL SHOPS
HSO: K. LINTER
DATE: 12/1/94
PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: CENTRAL SHOPS
PROJECT NO.: 1208T MDN 000357.000
SITE LOCATION: CENTRAL SHOPS
HSO: K. HUNTER
DATE: 12/4/94
PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

DAILY SIGN-IN/OUT LOG

PROJECT: CENTRAL SHOPS BRP
PROJECT NO.: 12081-MDN 808357-80
SITE LOCATION: CENTRAL SHOPS
HSO: K. HUNTER
DATE: 12/6/94
PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all personnel working on the site.

Work Zone Entry/Exit Logs

WORK ZONE ENTRY AND EXIT LOG. (JOB EXPOSURE REPORT)

PROJECT: CS BAP
PROJECT NO.: 1208 / MDA 90057.000
SITE LOCATION: CENTRAL SHOPS
HSO: K. HUNTER
DATE: 11/17/94
PAGE NO.: 1 of 1

[illegible]

Note: This form is to be completed on a daily basis by all onsite personnel working within the controlled work zone.

WORK ZONE ENTRY AND EXIT LOG. (JOB EXPOSURE REPORT)

PROJECT: CENTRAL SHOPS BRP

PROJECT NO.: 88351.000

SITE LOCATION: _____

HSO: K. HUNTER

DATE: 11/2/94

PAGE NO.: / of / =

[illegible]

Note: This form is to be completed on a daily basis by all onsite personnel working within the controlled work zone.

WORK ZONE ENTRY AND EXIT LOG (JOB EXPOSURE REPORT)

PROJECT: CENTRAL SHOPS BRP
PROJECT NO.: 12081 -
SITE LOCATION: CENTRAL SHOPS
HSO: K. HUNTER
DATE: 11/3/94
PAGE NO.: 1 of 1 =

TIME

IN

OUT

NAME/FIRM
(Printed)

SIGNATURE

HNU/OVA
READINGS .
(IN BREATHING
ZONE)

LEVEL
PPE
(D/C/B)

[illegible]

Note: This form is to be completed on a daily basis by all onsite personnel working within the controlled work zone.

WORK ZONE ENTRY AND EXIT LOG (JOB EXPOSURE REPORT)

PROJECT: CS BRP
PROJECT NO.: 12081
SITE LOCATION: CENTRAL SHOPS
HSO: K. HUNTER
DATE: 11/14/94
PAGE NO.: 1 of 1 =

[illegible]

Note: This form is to be completed on a daily basis by all onsite personnel working within the controlled work zone.

Appendix F

Well Development Forms

CBR-4

CBR-5

CBR-6

CBR-4

DEVELOPMENT SHEET

WELL # CBR - T3

DEVELOPED BY Frank Cooper

DEVELOPMENT OVERSIGHT Rust

DATE STARTED 9 NOV 94

STARTING WATER LEVEL 29 ft

STARTING FLOW METER READING N/A

STARTING WELL YIELD (AFTER BAILING) A 35 Gal PH₂

DATE FINISHED 14 NOV 94

FINAL WATER LEVEL 41.5

FINAL FLOW METER READING N/A

TOTAL VOLUME OF WATER REMOVED 425

FINAL WELL YIELD 35

HOURS BAILED 4 1/2

HOURS PUMPED N/A

HOURS BLOWN 6 1/2

HOURS OTHER Swabbing 1

COMMENTS _____

FORM MUST BE TURNED IN THE FIRST WORKING DAY AFTER DEVELOPMENT IS COMPLETED
EVERY LINE MUST BE COMPLETED. PLACE NA (NOT APPLICABLE) IN EACH LINE THAT IS NOT
FILLED OUT WITH DATA

SAVANNAH RIVER PLANT WELL DEVELOPMENT REPORT

PROJECT PJ-4		DRILLING SUBCONTRACTOR EMTC	
WELL NO. CBR-T3	DRILLER Frank C.	S.G. CERTIFICATION NO. 969	DATE STARTED 9 NOV 94
DATE FINISHED 14 NOV 94		DEVELOPMENT METHODS Swabbing / AIR Lift / Bailing	
SAP COORDINATES J San	OVERSIGHT FIRM RUST	TOTAL DEVELOPMENT TIME 12	
SITE HYDROGEOLOGIST			

DATE/TIME	DISCHARGE RATE (GPM)	VOL. PURGED (GALLONS)	WATER TEMP. (°C)	pH	SPECIFIC CONDUCTANCE (µMHO/CM)	TOTAL DISSOLVED SOLIDS (PPM)	COLOR/TURBIDITY	SAND CONTENT (PER CENT)	REMARKS
9 NOV 94							Light		Water level 29 ft
7:30							BROWN		MURKY water
1100	30	110							Clear no w Bailer
							CLEAR BROWN		
10 NOV 94									
2:00	35								Added water
4:30	35	187.5							50 Gal water
									Truck
11 NOV 94									
7:15	35								Water level 38 ft
1100	35	320							Add approx 30 Gal of water & swabbed
14 NOV 94									
12:00	35								Water level 37.5 ft
2:50	35	425							Water level 41.5 ft
4 NOV 94		425	TOTAL						

WESTINGHOUSE SAVANNAH RIVER COMPANY
GROUNDWATER MONITORING WELL
INSTALLATION
SRS MONITORING WELL INSTALLATION REPORT

Manual: DPOI' 254
Chapter: 5 (Draft 1)
Page: 7 of 10
Effective Date: 8/1/89
Organization: Environmental
Protection Section

WELL DEVELOPMENT

Well number C.B.R. IT.3 Developed by Frank Cooper

Date started 9/11/94

Date completed 14 NOV 94

Oversight RUST

DEVELOPMENT METHOD:

	Hours	Results
Bailing	<u>1 1/2</u>	<u>110 Gall no sands</u>
Swabbing and surging	<u>1 1/2</u>	
Air lift	<u>3 3/4</u>	
Pumping	<u>0</u>	
Total hours	<u>1.2</u>	

Type and quantity of additives (including water) placed in well during development:

Approx 30 Gal of water did not seem
to help.

Estimated volume of water removed during development (gal) 425

	pH	Conductivity	Turbidity	Water Level
Start of development				<u>29 ft / 29 ft</u>
End of development				<u>41.5</u>
Well yield (gpm)	<u>Ap. 3/4</u>			

Well development comments water does not CLEAR UP.

Verified by _____
Date / /

Report prepared by _____
Date / /

"Experience makes the difference"

P.O. Box 750
Now Ellenton, SC 29809
(803) 652-2718

WELL DEVELOPMENT FORM

WELL: CBR T-3

DATE STARTED: 9 NOV 94

DATE FINISHED: 14 NOV 94

PAGE 1 OF 4

LOCATION: C Lay Lot

TIME STARTED: 7:30

TIME FINISHED: 15:00

TYPE OF DEVELOPMENT

WATER QUALITY

COMMENTS

DATE	TIME	BAILING	AIRLIFT	PUMPING	SWABBING	MUDDY	MILKY	SANDY	CLEAR	SANDFREE	COMMENTS
3 NOV 94	730	✓				✓					
10 NOV 94	1000 430		✓		✓		✓				DOES NOT CLEAR UP
1 NOV 94	715 1800		✓		✓						DOES NOT CLEAR UP
4 NOV 94	1250	✓			✓				✓		Clear brown
4 NOV 94	1430	✓			✓				✓		HAD TO ADD WATER during AIR LIFT

TOTAL NUMBER OF HOURS DEVELOPMENT 3 1/2

RIG USED 9

INSPECTOR'S SIGNATURE: _____

NAME OF DEVELOPER: Frank Cooper

CBR-5

DEVELOPMENT SHEET

WELL # CBR-T2

DEVELOPED BY Frank Cooper

DEVELOPMENT OVERSIGHT Rust

DATE STARTED 9 NOV 94

STARTING WATER LEVEL 41 ft

STARTING FLOW METER READING ^{Bailing} 1/2 Gal

STARTING WELL YIELD (AFTER BAILING) _____

DATE FINISHED 14 NOV 94

FINAL WATER LEVEL 30 ft

FINAL FLOW METER READING N/A

TOTAL VOLUME OF WATER REMOVED A 152 ~~155~~ Gal

FINAL WELL YIELD 1.30 GPH

HOURS BAILED 3 1/2

HOURS PUMPED N/A

HOURS BLOWN 2

SWABBING
HOURS OTHER 1

COMMENTS Had to Add water to well could
not air lift

FORM MUST BE TURNED IN THE FIRST WORKING DAY AFTER DEVELOPMENT IS COMPLETED.
EVERY LINE MUST BE COMPLETED. PLACE NA (NOT APPLICABLE) IN EACH LINE THAT IS NOT
FILLED OUT WITH DATA.

SAVANNAH RIVER PLANT WELL DEVELOPMENT REPORT

PROJECT PJ4				DRILLING SUBCONTRACTOR EMTC					
WELL NO. CBR-T2		DRILLER Frank C.		S.C. CERTIFICATION NO. 969		DATE STARTED 9 NOV 94		DATE FINISHED 14 NOV 94	
SRP COORDINATES J JANSEN			OVERSIGHT FIRM RUST			DEVELOPMENT METHODS Bailing Swab / Air Lift			
TOTAL DEVELOPMENT TIME 8			SITE HYDROGEOLOGIST						

DATE/TIME	DISCHARGE RATE (GPM)	VOL. PURGED (GALLONS)	WATER TEMP. (°C)	pH	SPECIFIC CONDUCTANCE (µMHOS/CM)	TOTAL DISSOLVED SOLIDS (PPM)	COLOR/TURBIDITY	SAND CONTENT (PER CENT)	REMARKS
9 NOV 94							Reddish		water level 41 ft
1:15	30	30							
3:00	30	60					Reddish		water level 48 ft
10 NOV		0							water level Air Lift
1100	0	0		unknown					want lift water
1200	0	0							adding water
11 NOV 94									
1:30	1	61							
3:30	1	62					Reddish		water level 44 ft
									filled well water
									don't help any
									swabbed Air Lift
14 NOV 94									water level 44 ft
900	30	92							Swabbing & Bailing
1200	30	122							water clearing up
	30	152							Bailed 10 more
									well is clean

152 TOTAL

WESTINGHOUSE SAVANNAH RIVER COMPANY

GROUNDWATER MONITORING WELL
INSTALLATION

SRS MONITORING WELL INSTALLATION REPORT

Manual:

Chapter:

Page:

Effective Date:

Organization:

DPSO: 254

5 (Draft 1)

7 of 10

8/1/89

Environmental
Protection SectionWELL DEVELOPMENTWell number C.B.R. 111 T12 Developed by Frank CooperDate started 9 NOV, 94Date completed 14 NOV, 94Oversight RUST

DEVELOPMENT METHOD:

	Hours	Results
Bailing	<u>3 1/2</u>	<u>PH 6.14</u>
Swabbing and surging	<u>1 1/2</u>	
Air lift	<u>3</u>	<u>NO water Calling water TRUCK</u>
Pumping		
Total hours	<u>8 HRS</u>	

Type and quantity of additives (including water) placed in well during development:

Water Aprdx 50 Gal totalEstimated volume of water removed during development (gal) 150 Gal

	pH	Conductivity	Turbidity	Water Level
Start of development	<u>6.14</u>			<u>41 ft</u> 54
End of development				<u>- 50 ft</u>
Well yield (gpm) <u>4</u>	<u>30 GPH</u>			

Well development comments could not air lift, bailed good
& cleaned

Verified by _____

Date / /

Report prepared by _____

Date / /

"Experience makes the difference"

P.O. Box 750
New Ellenton, SC 29809
(803) 652-2718

WELL DEVELOPMENT FORM

WELL: CBR-T2

DATE STARTED: 9 NOV 94

DATE FINISHED: 14 NOV 94

PAGE 1 OF 4

LOCATION: C

TIME STARTED: 115

TIME FINISHED: 1200

TYPE OF DEVELOPMENT

WATER QUALITY

COMMENTS

DATE	TIME	BAILING	AIRLIFT	PUMPING	SWABBING	MUDDY	MILKY	SANDY	CLEAR	SANDFREE	COMMENTS
NOV 94	115	✓						✓	Red		Water level 41 ft
NOV 94	305	✓									Water level 50 ft
NOV 94	1400		✓								Water level 48 ft
NOV 94	1200										Water level 44 ft
NOV 94	130										No water
NOV 94	350		✓								Wall CLEARED
NOV 94	900	✓			✓						Water level clear
NOV 94	1200	✓			✓						Water level 50 ft

TOTAL NUMBER OF HOURS DEVELOPMENT 6 1/2

RIG USED 9

INSPECTOR'S SIGNATURE: _____

NAME OF DEVELOPER: Frank Cooper

CBR-6

DEVELOPMENT SHEET

WELL # CBR - T1

DEVELOPED BY Frank Cooper

DEVELOPMENT OVERSIGHT RUST

DATE STARTED 9 NOV 94

STARTING WATER LEVEL 48ft

Bailing
STARTING FLOW METER READING 1/3 Gal

STARTING WELL YIELD (AFTER BAILING) 15

DATE FINISHED 14 NOV 94

FINAL WATER LEVEL 53.5

FINAL FLOW METER READING N/A

TOTAL VOLUME OF WATER REMOVED 202

FINAL WELL YIELD 35 GPH

HOURS BAILED 2 HR,

HOURS PUMPED N/A

HOURS BLOWN 3 1/2

HOURS OTHER Swabbed 1 HR,

COMMENTS Had to add water to well could
not air lift

FORM MUST BE TURNED IN THE FIRST WORKING DAY AFTER DEVELOPMENT IS COMPLETED.
EVERY LINE MUST BE COMPLETED. PLACE NA (NOT APPLICABLE) IN EACH LINE THAT IS NOT
FILLED OUT WITH DATA.

SAVANNAH RIVER PLANT WELL DEVELOPMENT REPORT

PROJECT PJ 4		DRILLING SUBCONTRACTOR EMTC	
WELL NO. CBR-T1	DRILLER Frank Cooper	S.G. CERTIFICATION NO. 969	DATE STARTED 9 NOV 94
DATE FINISHED 14 NOV 94		DEVELOPMENT METHODS BAILING / SWAB AIRLIFT	
SNP COORDINATES J JENSEN		OVERSIGHT FIRM RUST	
TOTAL DEVELOPMENT TIME 6 1/2		SITE HYDROGEOLOGIST	

[illegible]

WESTINGHOUSE SAVANNAH RIVER COMPANY

GROUNDWATER MONITORING WELL
INSTALLATION

SRS MONITORING WELL INSTALLATION REPORT

Manual: DPO: 254
 Chapter: 5 (Draft 1)
 Page: 7 of 10
 Effective Date: 8/1/89
 Organization: Environmental
 Protection Section

WELL DEVELOPMENTWell number C.B.R. 111 Developed by Frank CooperDate started 9 NOV, 94Date completed 14 NOV, 94Oversight RUS

DEVELOPMENT METHOD:

	Hours	Results
Bailing	<u>2</u>	<u>light sand</u>
Swabbing and surging	<u>1</u>	
Air lift	<u>3.5</u>	<u>no water / calling for water tank</u>
Pumping	<u>0</u>	
Total hours	<u>6.5</u>	

Type and quantity of additives (including water) placed in well during development:

NONE! Slow to Recharge, filled well w/
4 TIME approx 60 Gall. water

Estimated volume of water removed during development (gal) 20.2

	pH	Conductivity	Turbidity	Water Level
Start of development	<u>6.25</u>			<u>4.8 ft / 3</u>
End of development				<u>53.5</u>
Well yield (gpm)	<u>4 Gal Per HR</u>			

Well development comments Slow Recharge, water level
47 feet, filled well with water swabbed to
min no change

Verified by _____
 Date 1/1/

Report prepared by _____
 Date 1/1/

"Experience makes the difference"

P.O. Box 750
Now Ellenton, SC 29800
(803) 652-2718

WELL DEVELOPMENT FORM

WELL: C. B. R. T. 1

DATE STARTED: 9 NOV 94

DATE FINISHED: 14 NOV 94 PAGE 1 OF 4

LOCATION: C. AREA

TIME STARTED: 11:00 - 1:00

TIME FINISHED: 5:00

TYPE OF DEVELOPMENT

WATER QUALITY

COMMENTS

DATE	TIME	BAILING	AIRLIFT	PUMPING	SWABBING	MUDDY	MILKY	SANDY	CLEAR	SANDFREE	COMMENTS
NOV 94	11:00	✓				✓					water (eve) 48 ft
NOV 94	1:00	✓					✓				water (eve) 53 ft
NOV 94	4:00		✓								no water extracted
NOV 94	5:00		✓				✓				very little water
NOV 94	3:00	✓			✓						4 gal 1 hr
NOV 94	4:45	✓			✓						CLEANED up Good but not CLEAN

TOTAL NUMBER OF HOURS DEVELOPMENT 2 HRS

RIG USED 9

INSPECTORS SIGNATURE: _____

NAME OF DEVELOPER: Frank Cooper

11:00 - 1:00 2 HRS

Appendix G

Groundwater Sampling Information

Phase I (12/5/94)

CBR-4

CBR-5

CBR-6

Appendix G
Summary of Groundwater Sampling
Phase I (12/15/94)

Sample Location	Sample Number	Date Sampled	Sample ID Number	Analyte Code	Identifier
CBR-5	01	12/5/94	102519	2,3	Normal
CBR-5	01E	12/1/94	103798	2,3	Rinsate
CBR-5	01C	12/5/94	102520	2,3	Field Blank
CBR-4	01	12/5/94	102521	2,3	Normal
CBR-4	01A	12/5/94	102522	2,3	Duplicate
CBR-4	01D	12/5/94	102522	2,3	Split
CBR-6	01	12/5/94	103799	2,3	Normal

Analyte Codes for Groundwater Sampling:

2. TCL/TAL w/TIC
3. Tritium

QA/QC Sample Codes:

- A Duplicate sample
- C Field Blank
- D Split sample
- E Rinsate blank

Phase II (12/28/94)

CBR-4

CBR-5

CBR-6

Appendix G
Summary of Groundwater Sampling
Phase II (12/28/94)

Sample Location	Sample Number	Date Sampled	Sample ID Number	Analyte Code	Identifier
CBR-5	01	12/28/94	102560	2,3	Normal
CBR-5	01E	12/28/94	102561	2,3	Rinsate
CBR-4	01	12/28/94	102562	2,3	Normal
CBR-6	01	12/28/94	102559	2,3	Normal

Analyte Codes for Groundwater Sampling:

- 2. TCL/TAL w/TIC
- 3. Tritium

QA/QC Sample Codes:
E Rinsate blank

Appendix H

Field Permeability Testing

Falling and Rising Head Slug Tests For:

CBR-4

CBR-5

CBR-6

CBR-4

CBR-04 RISING HEAD TEST

DATA SET:

A14RISE.AQT

01/22/95

AQUIFER TYPE:

Unconfined

SOLUTION METHOD:

Bouwer-Rice

ESTIMATED PARAMETERS:

 $K = 3.1899E-06$ ft/sec $y_0 = 0.0251$ ft

TEST DATA:

 $R_0 = 1$ ft $r_0 = 0.0033$ ft $r_w = 0.3281$ ft $L = 20$ ft $b = 100$ ft $K = 21.61$ ft

CBR-5

CBR-05 FALLING HEAD TEST

DATA SET:

A:5FALL.AQT

01/22/95

AQUIFER TYPE:

Unconfined

SOLUTION METHOD:

Dowser-Rice

ESTIMATED PARAMETERS:

 $K = 3.1681 \times 10^{-6}$ ft/sec $y_0 = 0.3542$ ft

TEST DATA:

 $H_0 = 1$ ft $r_0 = 0.0833$ ft $r_w = 0.3281$ ft $L = 14.37$ ft $b = 100$ ft $K = 14.37$ ft

CBR-05 RISING HEAD TEST

DATA SET:

A:5RISE.AQT

01/22/98

AQUIFER TYPE:

Unconfined

SOLUTION METHOD:

Douglas-Rice

ESTIMATED PARAMETERS:

K = 1.3770E-05 ft/sec

Y0 = 0.9591 ft

TEST DATA:

H0 = 1. ft

ro = 0.0033 ft

rw = 0.3281 ft

L = 14.37 ft

b = 100. ft

K = 14.37 ft

(

CBR-6

(

(

CBR-06 FALLING HEAD TEST

DATA SET:

A: FALL.AQT

01/22/95

AQUIFER TYPE:

Unconfined

SOLUTION METHOD:

Bouwer-Rice

ESTIMATED PARAMETERS:

K = $9.6826E-07$ ft/sec

y0 = 0.6761 ft

TEST DATA:

H0 = 1. ft

ra = 0.0833 ft

rw = 0.3281 ft

L = 13.65 ft

b = 100. ft

H = 13.65 ft

CBR-06 RISING HEAD TEST

DATA SET:

A:GRIZL.AQT

01/22/95

AQUIFER TYPE:

Unconfined

SOLUTION METHOD:

Dowzer-Rice

ESTIMATED PARAMETERS:

 $K = 1.2597 \times 10^{-5}$ ft/sec $y_0 = 2.46$ ft

TEST DATA:

 $H_0 = 1$ ft $r_0 = 0.0033$ ft $r_w = 0.3281$ ft $L = 13.65$ ft $b = 100$ ft $K = 13.65$ ft

Appendix I

Surface Water/Sediment Sampling Information

Field Readings for Surface Water/Sediment Sampling
12/7/94

Sample Number	Surface Water Temperature	Dissolved Oxygen (mg/l)	pH
CS6G-29	13.4°C	7.85	10.51
CS6G-30	66°F	9.40	10.50
CS6G-31	73°F	8.00	9.68
CS6G-32	15.8°C	6.63	9.22
CS6G-33	16.0°C	5.38	6.61