**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1995

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

RICHLAND, WASHINGTON HANFORD ATOMIC PRODUCTS OPERATION

This document consists of
5 pages, No. 13 of
15 copies. Series A.

COPY 1 OF 1,

AUTHORIZATION FOR A PROCESS CHANGE - REVISION OF NUCLEAR
SAFETY RULES FOR TRANSPORTING PLUTONIUM COMPOUNDS BETWEEN
THE 231 AND 234-5 BUILDINGS

By

A. E. Smith

Z-Plant Process Technology Sub-Unit - Plant Processes Unit
Technical Section
ENGINEERING DEPARTMENT

June 9, 1954

HANFORD ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

Operated for the Atomic Energy Commission by the General Electric
Company under Contract # W-31-109-Eng.-52

This document contains restricted data
as defined by Atomic Energy Commission
regulations. It is to be controlled
in accordance with the provisions of an
order prohibiting its unauthorized
disclosure.

RECEIVED
MASTER

JUL 2 1954

300 AREA
CLASSIFIED FILES

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

at

A PRIME CONTRACTOR FOR THE U.S. ATOMIC ENERGY COMMISSION

COPY NO.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15

DISTRIBUTION

R.S. Bell
V.R. Cooper
O.H. Greager
T.W. Hauff
O.F. Hill
D.D. Lanning - R.P. Raftery
J.E. Maider - C.A. Priode
D. McDonald
L.M. Meeker - J.R. Cartmell, Jr.
W.N. Mobley
W.J. Ozeroff - G.M. Muller
E.G. Pierick
A.E. Smith
300 Files
Yellow Copy

DECLASSIFIED

By Authority of CH Henager

CG-PR-2, 12-2-91

by DK Harrison 3-19-99

Verified By DA Bunk 3-20-92

DECLASSIFIED

I. INTRODUCTION

Nuclear safety rules for transporting plutonium compounds between the 231 and 234-5 Buildings were established in Documents HW-30328⁽¹⁾ and HW-31465.⁽²⁾ Provisions for the co-transporting of loaded sample cans, filter boats and/or product samples were not included in the above documents. In the interest of economy and efficiency the rules have been reviewed and revised according to the provisions set forth in this document.

II. PRESENT TRANSPORTATION LIMITS

1. Transportation of Plutonium Nitrate in Sample Cans

A maximum of 12 sample cans each containing 169 to 400 grams of plutonium as plutonium nitrate solution processed from nominal 600 MWD/T plutonium⁽¹⁾, or a maximum of 12 sample cans containing up to 200 grams of plutonium as plutonium nitrate solution processed from nominal 200 MWD/T plutonium⁽²⁾, or a maximum of 10 sample cans containing 200 to 400 grams of plutonium as plutonium nitrate solution processed from nominal 200 MWD/T plutonium⁽²⁾; may be transported between the 231 and 234-5 Buildings at one time. The loaded cans are to be confined to a two dimensional array provided by twelve 10 inch by 20 inch compartments that are available on the transporting vehicle. Each compartment is limited to one loaded sample can and no other plutonium or plutonium compounds may be present on a vehicle transporting loaded sample cans.

2. Transportation of Plutonium Oxalate in Filter Boats

A maximum of 12 loaded filter boats each containing up to 1000 grams of plutonium as plutonium oxalate may be transported between the 231 and 234-5 Buildings at one time. The loaded boats must be in filter boat carriers and confined to a two dimensional array. No other plutonium or plutonium compounds may be present on a vehicle carrying loaded filter boats.⁽¹⁾

3. Transportation of Plutonium Samples

Provisions for transporting samples between the 231 and 234-5 Buildings have not been previously considered from a nuclear safety standpoint.

III. REVISED TRANSPORTATION LIMITS

The maximum allowable number of sample cans or filter boats containing plutonium compounds that may be transported between the 231 and 234-5 Building shall remain as defined in Documents HW-30328 and HW-31465 (outlined above). However, loaded sample cans and loaded filter boats may be transported at the same time on the same vehicle provided that a two dimensional array is maintained and the total number of items in such combinations does not exceed twelve (12), except that, whenever one or more sample cans contain (s) 200 to 400 grams of plutonium as plutonium nitrate solution processed from nominal 200 MWD/T plutonium the total

DECLASSIFIED

number of containers in such combinations shall not exceed ten (10). One filter boat or one sample can may be replaced by a maximum of 100 grams of plutonium or plutonium compounds of nondescript concentration in a suitable container or containers.

IV. BASIS

The nuclear safety rules for transporting plutonium nitrate, plutonium oxalate and plutonium samples have been reviewed and revised in the interest of efficiency. The transporting of mixed loads of plutonium compounds will decrease the number of trips required to transfer the various 231 Building products to the 234-5 Building.

The limits as established above are in keeping with the policy of preventing the accidental accumulation of unsafe masses of plutonium and shall be rigorously observed.

V. REFERENCES

1. HW-30328, Authorization for Process Change, Definitions and Changes in Batch Limits - Nuclear Safety - Buildings 231 and 234-5, A.E. Smith by R.E. Isaacson (3-11-54).
2. HW-31465, Addendum to HW-29691, Authorization for a Process Change - 231-Z Building - Loading, Identification, and Storage of Sample Cans Containing 400 Grams of Plutonium as Liquid Plutonium Nitrate Solution, A.E. Smith by R.E. Isaacson (4-14-54).

AES:RE Isaacson:pec

A.E. Smith
A.E. Smith

DECLASSIFIED

VI. APPROVALS

W.J. Ozeroff
W.J. Ozeroff

Head, Physics Unit
Applied Research Sub-Section

7/7/54 Date

O.F. Hill
O.F. Hill

Head, Plant Processes Unit
Separations Technology Sub-Section

7/2/54 Date

V.R. Cooper
V.R. Cooper

Manager
Separations Technology Sub-Section

7/14/54 Date

O.H. Greager
O.H. Greager

Manager
Technical Section
Engineering Department

_____ Date

ACCEPTED

J.E. Maider
J.E. Maider

Manager
Manufacturing Department

7-22-54 Date

Date Issued August 9, 1954

DECLASSIFIED