SEP 12 1996

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT 616570

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) Criticality and Shielding		4. Related EDT No.: 616570	
5. Proj./Prog./Dept./Div.: Spent Nuclear Fuel		6. Design Authority/ Design Agent/Cog. Engr.: F. Schmittroth		7. Purchase Order No.: NA	
8. Originator Remarks: Approval/Release				9. Equip./Component No.: NA	
				10. System/Bldg./Facility:	
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No				12. Major Assm. Dwg. No.: NA	
				13. Permit/Permit Application No.: NA	
				14. Required Response Date:	

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Design- ator	Reason for Trans- mittal	Origi- nator Dispo- sition	Receiv- er Dispo- sition
1	WHC-SD-SNF-ANAL-011		0	Comparison of Spent Fuel Databases for K Basin	NA	1		

16. KEY

Approval Designator (F)		Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-5, Sec.12.7)	1. Approval 2. Release 3. Information	4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)	1. Approved 2. Approved w/comment 3. Disapproved w/comment	4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged	

17. SIGNATURE/DISTRIBUTION
(See Approval Designator for required signatures)

(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
		Design Authority				1	1	W. L. Willis		9/14/96	R3-86
		Design Agent				1	1	W. D. Wittekind		8/13/96	H0-32
1	1	Cog.Eng. F. Schmittroth			H0-35						
1	1	Cog.Eng. K. D. Dobbin		8/13/96	H0-35						
1	1	Cog. Mgr. J. Greenborg		8/13/96	H0-35						
		QA									
		Safety									
		Env.									

18. F. Schmittroth See B1k. 17K 8/13/ Signature of EDT Originator Date 96		19. Authorized Representative Date for Receiving Organization		20. J. Greenborg Design Authority/ Cognizant Manager 8/13/96 Date		21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	
---	--	---	--	---	--	---	--

Comparison of Spent Fuel Databases for K Basin

F. Schmittroth, K. D. Dobbin

Westinghouse Hanford Company, Richland, WA 99352

U.S. Department of Energy Contract DE-AC06-87RL10930

EDT/ECN: 616570

UC: 510

Org Code: 8M730

Charge Code: LB012

B&R Code: EW3135040

Total Pages: 23

Key Words: Spent Fuel, Database, K Basin

Abstract: The SCATS and reconstructed SCATS databases representing spent fuel in the Hanford K basins are compared.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: WHC/BCS Document Control Services, P.O. Box 1970, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

Javis Bishop 9-12-96
Release Approval Date

Approved for Public Release

CONTENTS

1.0	INTRODUCTION	2
2.0	INITIAL COMPARISONS	2
2.1	DATABASE PROCESSING	2
2.2	PHYSICAL COMPARISON	3
3.0	BURNUP COMPARISON	4
4.0	RELATED WORK	4
4.1	BURNUP CONVERSION	5
4.2	DECAY HEAT CALCULATIONS (DKPRO)	5
4.2.1	Decay Codes	5
4.2.2	Decay Heat and Burnup	6
4.2.3	Unified Database	6
5.0	CONCLUSIONS	6
6.0	REFERENCES	7
APPENDICES		
A	RDSCATS, A Program to Read and Consolidate the SCATS and R-SCATS Databases	A-1
B	COMMENTS BY REVIEWER WARREN D. WITTEKIND	B-1

LIST OF FIGURES

Figure 1.	Comparison of the SCATS and R-SCATS databases as a function of burnup expressed in ^{240}Pu (%)	8
Figure 2.	Burnup conversion from ^{240}Pu (%) to MWd/short-ton based on least-squares fit	9

LIST OF TABLES

Table 1.	Comparison of the SCATS and R-SCATS Databases by Key Number	10
----------	--	----

COMPARISON OF SPENT FUEL DATABASES FOR K BASIN

1.0 INTRODUCTION

The standard database for spent nuclear fuel in the K basins is the Safeguards Control and Accountability Transaction System (SCATS) (Dasinger 1993). Two related databases include a reconstructed SCATS database (Wittekind 1994 and Schlosser 1992) (termed R-SCATS in this report), and an accountability database (Blehm 1990) (also called COLDMAC). The accountability database includes physical accountability of fuel pieces and amounts as well as average burnups. The SCATS and R-SCATS databases reflect improved burnup estimates that address the effects of a segregation campaign whereby low-burnup fuel elements were selectively removed for reprocessing.

A previous study (Wittekind 1994) found that decay heat values calculated from the R-SCATS database were significantly higher than values based on the accountability database. This result raises the question of how the SCATS database and the R-SCATS database compare for burnup-related values such as decay heat. Details of how burnups were assigned as a consequence of the segregation campaign are not readily available for both databases. The present work was therefore initiated to compare the standard SCATS database with the R-SCATS database as they are currently constituted.

Section 2.0 gives a direct physical comparison of the number of fuel pieces and amount of fuel followed by a burnup comparison in Section 3.0. Comparisons with related studies are given in Section 4.0 with conclusions given in Section 5.0.

2.0 INITIAL COMPARISONS

2.1 DATABASE PROCESSING

Electronic copies of the two databases, SCATS and R-SCATS, were obtained from their respective custodians, M. N. Serier and W. D. Wittekind, both of Westinghouse Hanford Company. Because of large differences in both content and format, a code RDSCATS was written to read both databases and consolidate them in a common format for comparison. The SCATS database is represented by a text-based comma-delimited file, KEYMOD1.TXT, with numerous records pertaining to a common fuel discharge key while R-SCATS is represented by a spreadsheet-based file, KEY-SUM1.WQ1, with a simpler record structure. (The KEYMOD1.TXT file is actually a text file dump extracted from the complete SCATS database.) The RDSCATS code is documented in Appendix A. The code was

written in C for its flexibility in parsing (i.e. splitting) complex records.

To process the R-SCATS spreadsheet file, KEY-SUM1.WQ1, it was first converted to a tab-delimited text file, KEY-SUM1.DAT. Adjoining tabs were separated by spaces to accommodate C parsing routines. Except for a similar separation of adjoining commas, the SCATS text file, KEYMOD1.TXT, renamed to KEYMOD1.DAT, was used intact.

Strategy

Both databases consist of records identified by "HAPO" key numbers that encode the discharged fuel date. The HAPO key numbers are defined as the number of days beyond 9/26/44. The SCATS database includes multiple lines corresponding to a given key, and the R-SCATS database includes fields that similarly identify distinct records belonging to a common key. In order to obtain a common basis for comparing the two databases, the multiple lines and subkeys were consolidated to composite records, each with one distinct key number. As implemented in the RDSCATS code, this strategy consists of simply adding all the records with a common key number. The addition included the number of pieces, the amount of uranium, and the amounts of total plutonium and ^{240}Pu .

2.2 PHYSICAL COMPARISON

The results of the physical comparison are given in Table 1 which shows the number of pieces and the uranium mass (percent ^{240}Pu is also shown). With minor exceptions, both the number of pieces and the uranium mass are in excellent agreement both globally and on a key-by-key comparison.

Three keys (21540, 22565, 22852) deserve special note. These are high burnup keys that are identified by the indicated key numbers in the SCATS database. They are also singled out as high-burnup subkeys in the R-SCATS database but with a corresponding key number whose leading digit is a 1 rather than a 2. To prevent the RDSCATS code from consolidating these keys with the corresponding keys, the leading 1 was edited to a 2 in the R-SCATS database, the same as for the SCATS database. Of course, this change impacts interpretation of the key number as a discharge date.

The largest discrepancy in the number of pieces, 27, occurs for the low HAPO key number 9623. Only two other, even smaller, discrepancies are found in Table 1. The 27 piece discrepancy is out of 207625 pieces and corresponds to 0.23 MTU. It accounts for nearly all of the negligibly small discrepancy, 0.015%, in the global uranium mass.

Although it does not affect the current comparison, it is noted that the Mark IV component of key 9621 (< 0.2 MTU) is represented in the R-SCATS database used here, but is missing in corresponding Table 1-2 of

Wittekind's report. Wittekind also remarks that this same key contains some single-pass reactor fuel listed as Mark 1A.

3.0 BURNUP COMPARISON

A small but non-negligible discrepancy in burnup is already apparent in Table 1. The average percent ^{240}Pu is about 4% higher (13.0 compared to 12.5) for the SCATS database. To manifest this difference, a graph displaying the distribution of discharged fuel as a function of burnup $^{240}\text{Pu}(\%)$ was made by binning the individual database records according to their burnup. A simple assignment of each record to a percent ^{240}Pu bin distorts the picture. The following simple prescription has the advantages of smoothing the graph and of rigorously conserving both the uranium mass and the total burnup.

The procedure is to split each database record into two $^{240}\text{Pu}(\%)$ bins labeled i and $i+1$ where i is the integer obtained by truncating the percent ^{240}Pu value denoted here by p . Next split the total uranium mass, m , for the record into a_i and a_{i+1} corresponding to the two bins. Conservation of uranium mass is assured by requiring

$$m = a_i + a_{i+1} .$$

Similarly, total burnup in $^{240}\text{Pu}(\%)$, is conserved by

$$p \cdot m = i a_i + (i+1) a_{i+1} .$$

These equations are readily solved for a_i and a_{i+1} :

$$\begin{aligned} a_{i+1} &= (p-i) m , \\ a_i &= m - a_{i+1} . \end{aligned}$$

Figure 1 shows the results of applying these equations to both databases. The slightly higher burnups for the SCATS database, noted previously in Table 1, is readily apparent in the shifted peak near a burnup of 14% ^{240}Pu . Both databases include a small amount of very high burnup fuel near 16% ^{240}Pu with some small differences. Finally the low burnup fuel component is nearly identical for both SCATS and R-SCATS.

4.0 RELATED WORK

While the primary scope of this work was a direct comparison of the SCATS and R-SCATS databases, a comparison with related work is worthwhile. Since part of the motivation of the present study was the decay heat discrepancy found by Wittekind between the R-SCATS database with the accountability database, a brief comparison with his results is made. The computation of decay heat requires an estimate of the activity of all significant radionuclides, mainly ^{90}Sr and ^{137}Cs and their respective daughters, ^{90}Y and ^{137}Ba . These values can be obtained from ORIGEN2 (Croff 1980) calculations decayed to a common time. Conversion of burnup expressed in $^{240}\text{Pu}(\%)$ to reactor-based units of MWd/MTU is also needed.

4.1 BURNUP CONVERSION

While ORIGEN2 calculations can be used to determine a conversion from $^{240}\text{Pu}(\%)$ to MWd/MTU, the conversion used here is based on older results developed when N reactor was still operating. To facilitate the conversion, regression coefficients $\{c_i\}$ were obtained relating the burnup, B , in MWd/MTU to the burnup, p , in $^{240}\text{Pu}(\%)$:
Two sets of coefficients were developed: one set $\{2.716, 143.1, 2.014,$

$$B = \sum_{i=0}^3 c_i p^i .$$

$0.227\}$ for Mark IV fuel and one set $\{0.787, 203.1, 0.015, 0.282\}$ for Mark 1A fuel. These were incorporated into the RDSCATS program as a procedure Calc MWd. Figure 2 compares values based on the regression analysis (shown by the curves) with representative values (shown by the points) used as the basis for the fit.

4.2 DECAY HEAT CALCULATIONS (DKPRO)

4.2.1 Decay Codes

The ORIGEN2 code can be used to calculate radionuclide production, decay, and decay properties such as decay heat. Because of the large number of distinct decay times and burnups, an alternative method of calculation is desirable. The study by Wittekind started with a basis set of ORIGEN2 calculations and then interpolated on both burnup and decay time to obtain the desired values. In this study, the DKPRO code (Schmittroth 1996), recently developed to support Hanford tank farm radionuclide inventories, was used. As in Wittekind's work, DKPRO interpolates on burnup between basis ORIGEN2 calculations. It differs in that it does not interpolate on decay time. Instead a full decay

calculation is made based on the same decay library used for the ORIGEN2 code.

In this context, the RADNUC code (Schwarz 1995) should also be noted. RADNUC is similar to DKPRO in that it carries out independent decay calculations; however, it uses approximate decay chain calculations and relies on its own independent internal decay library. Another difference is that the results of ORIGEN2 calculations are imbedded in RADNUC as part of the code, while DKPRO reads ORIGEN2 output files that can be included by the user as deemed necessary.

4.2.2 Decay Heat and Burnup

The RDSCATS program includes code to output two interface files, Hscats.dat and Hrscats.dat, suitable for input to the DKPRO program and corresponding to SCATS and R-SCATS respectively. The files include the HAPO number used for decay time calculations, fuel type, burnup, and uranium mass. DKPRO was run for each of the two files. The three altered key numbers discussed previously were edited back to a proper HAPO number to obtain correct decay-time calculations.

The two DKPRO calculations (decayed to the beginning of 1995) gave total decay heat values of 154 kW and 147 kW for SCATS and R-SCATS respectively. As expected, the slightly higher burnup for SCATS gives a correspondingly higher decay heat (5.3%). Eighty five percent of the decay heat arises from ⁹⁰Sr, ¹³⁷Cs and their daughters. The R-SCATS value is in good agreement with a value taken from Figure 1-1 of Wittekind's report. (Resolution of the figure is about 2 kW.)

Total burnups reported in the DKPRO calculations are 5.848×10^6 Mwd and 5.557×10^6 Mwd for SCATS and R-SCATS respectively. The R-SCATS value is very close (1.3% higher) to a value of 5.486×10^6 Mwd obtained from Wittekind.

The absolute accuracy of these burnups was not critically examined. It is known that the isotopic quantities in R-SCATS were calculated using uranium and plutonium isotopic tables that compared to PUREX measured isotopic quantities to less than one percent difference (see Attachment B). Since the scope of the current task only includes a direct comparison of SCATS and R-SCATS, details of these supplementary comparisons were not independently confirmed.

4.2.3 Unified Database

Another project related to the current task is development of a unified database for Hanford's defense waste. This project supports ongoing efforts to define the radionuclide content of the Hanford tank waste. It also includes records for the K basin; although it is not meant to supplant accountability records. The included K basin records are derived from a Schlosser file named SHIP_PX.DAT dated 1/11/93. A

DKPRO calculation was made using a preliminary version of the unified database. The total burnup is found to be 5.374×10^6 MWD or 3.4% below the value based on R-SCATS. The total uranium mass is 2090 MTU or 0.4% less than the R-SCATS value.

5.0 CONCLUSIONS

The SCATS and R-SCATS databases were compared on a physical basis and from a burnup perspective. With minor exceptions, the two databases were nearly identical in both the number of fuel pieces and the mass of uranium. The agreement holds on a key-by-key basis as well as globally.

Burnup for the SCATS database is about 4% to 5% higher than for the R-SCATS database. Decay heat calculations which are dominated by ^{90}Sr , ^{137}Cs , and their daughters show the same relationship.

6.0 REFERENCES

- Blehm, L. L., and A. R. Kelly, 1990, *Fuel Metal Accountability - 100 Areas*, WHC-IP-0069, Westinghouse Hanford Co., Richland, WA.
- Dasinger, J. R., 1993, *Nuclear Material Safeguards Systems User's Manual*, WHC-IP-0382/REV.1, Westinghouse Hanford Co., Richland, WA.
- Croff, A. G., 1980, *ORIGEN2- A Revised and Updated Version of the Oak Ridge Isotope Generation and Depletion Code*, ORNL-5621, Oak Ridge National Laboratory, Oak Ridge TN.
- Schlosser, J. E., 1992, *The FUELSEG Program, The Estimation of Isotopics of N Reactor Segregated Irradiated Fuels*, WHC-SD-NR-CSWD-049, Westinghouse Hanford Co., Richland, WA.
- Schmittroth, F., 1996, *DKPRO: A Radionuclide Decay and Reprocessing Code*, WHC-SD-XX-XXX, Westinghouse Hanford Co., Richland, WA.
- Schwarz, R. A., 1995, *Certification of RADNUC*, WHC-SD-HWV-SWD-001, Westinghouse Hanford Co., Richland, WA.
- Wittekind, W. D., 1994, *Consolidated Fuel Decay Heat Calculations*, WHC-SD-NR-ANAL-014, Westinghouse Hanford Co., Richland, WA.

Figure 1. Comparison of the SCATS and R-SCATS Databases as a Function of Burnup Expressed in ^{240}Pu (%).

Figure 2. Burnup conversion from $^{240}\text{Pu}(\%)$ to Mwd/short-ton based on least-squares fit.

Table 1. Comparison of the SCATS and R-SCATS Databases by Key Number

Key	No. of pieces		Uranium, MT		Percent Pu 240		Differences		
	Scats	R-scats	Scats	R-scats	Scats	R-scats	pieces	MTU	% Pu 240
9621	185	185	0.51	0.51	6.0	5.9	0	0.00	0.11
10001	95	95	1.04	1.04	13.2	9.8	0	0.00	3.49
10201	2000	2000	16.75	16.75	9.2	9.0	0	0.00	0.18
10259	2236	2236	23.30	23.30	10.4	10.2	0	0.00	0.18
10294	5620	5620	56.93	56.93	10.2	10.0	0	0.00	0.18
10350	2036	2036	16.31	16.31	10.6	10.3	0	0.00	0.31
10385	4084	4084	44.01	44.01	11.1	10.9	0	0.00	0.23
10456	4358	4358	42.92	42.92	11.3	11.0	0	0.00	0.27
10576	336	336	3.92	3.92	11.1	10.9	0	0.00	0.22
10602	4067	4067	41.16	41.16	13.0	12.6	0	0.00	0.38
10679	3725	3725	37.37	37.37	13.4	13.0	0	0.00	0.41
10742	2680	2680	27.17	27.17	13.9	13.4	0	0.00	0.45
10764	216	216	2.31	2.34	0.0	0.0	0	-0.03	0.00
10770	2708	2708	27.35	27.35	13.7	13.2	0	0.00	0.44
10832	6698	6698	69.42	69.42	13.5	13.1	0	0.00	0.42
10982	4324	4324	42.36	42.36	14.4	13.9	0	0.00	0.54
11036	2064	2064	20.57	20.57	14.1	13.6	0	0.00	0.49
11109	4077	4077	40.28	40.28	14.3	13.8	0	0.00	0.51
11183	5679	5679	61.07	61.06	14.3	13.8	0	0.01	0.50
11372	5172	5172	51.02	51.02	14.1	13.6	0	0.00	0.51
11449	4980	4980	49.17	49.17	13.9	13.4	0	0.00	0.51
11540	2688	2688	25.97	25.96	12.3	12.1	0	0.01	0.16
11733	56	56	0.64	0.64	12.1	11.8	0	0.00	0.31
11806	4844	4844	47.85	47.85	14.0	13.5	0	0.00	0.49
11897	5848	5848	56.38	56.38	14.9	14.3	0	0.00	0.59
11979	6576	6576	62.28	62.28	14.8	14.3	0	0.00	0.59
12127	4634	4634	46.23	46.22	14.6	14.0	0	0.01	0.56
12201	5036	5036	47.22	47.21	13.6	13.1	0	0.01	0.48
12240	8	8	0.09	0.09	13.6	13.1	0	0.00	0.42
12285	8004	8004	84.23	84.18	14.2	13.7	0	0.05	0.50
12480	7026	7026	73.46	73.46	14.2	13.7	0	0.00	0.51
12565	6409	6409	63.98	63.98	14.0	13.5	0	0.00	0.50
12639	6802	6802	69.25	69.25	13.6	13.1	0	0.00	0.45
12852	7636	7636	83.14	83.14	13.3	12.8	0	0.00	0.54
13015	4088	4088	45.04	45.04	13.2	12.7	0	0.00	0.51
13016	2534	2534	20.63	20.62	13.2	12.8	0	0.01	0.36
13371	618	618	5.01	5.01	12.9	12.5	0	0.00	0.42
13649	448	448	4.93	4.93	13.1	12.3	0	0.00	0.83
13685	224	224	2.61	2.61	13.3	12.7	0	0.00	0.63
14065	15	15	0.15	0.14	5.7	4.4	0	0.01	1.28
14355	840	840	9.70	9.70	12.3	12.0	0	0.00	0.36
14356	1319	1311	13.49	13.42	11.3	11.0	8	0.07	0.30
14722	6	6	0.07	0.07	5.1	5.4	0	0.00	-0.37
15204	8729	8729	97.37	97.37	6.0	5.9	0	0.00	0.12
15240	43	43	0.49	0.49	5.7	4.8	0	0.00	0.89
15316	1811	1811	19.52	19.52	6.1	5.8	0	0.00	0.32
15399	32	32	0.37	0.37	0.0	0.0	0	0.00	0.00
15444	28	28	0.31	0.31	4.7	4.7	0	0.00	-0.02
15451	856	856	8.89	8.89	6.5	6.5	0	0.00	0.06
15455	134	134	1.49	1.49	4.9	4.9	0	0.00	0.04
15457	36	36	0.37	0.37	4.1	4.1	0	0.00	0.02

Table 1 (continued)

Key	No. of pieces		Uranium, MT		Percent Pu 240		Differences		
	Scats	R-scats	Scats	R-scats	Scats	R-scats	pieces	MTU	% Pu 240
15458	11890	11890	132.29	132.29	4.3	4.2	0	0.00	0.03
15460	1944	1944	19.97	19.97	4.1	4.1	0	0.00	0.01
15461	1088	1088	12.73	12.73	1.6	1.6	0	0.00	0.00
9964	51	51	0.39	0.39	6.2	10.3	0	0.00	-4.07
9993	1062	1062	8.45	8.45	10.3	10.1	0	0.00	0.17
12823	952	952	7.83	7.83	13.2	12.7	0	0.00	0.48
12942	7084	7084	73.21	73.21	12.9	12.4	0	0.00	0.50
13017	2352	2352	26.89	26.85	11.4	11.0	0	0.04	0.38
13372	1814	1814	19.28	19.28	13.0	12.4	0	0.00	0.65
13524	3416	3416	37.58	37.58	13.1	12.6	0	0.00	0.59
13525	2184	2184	17.55	17.55	13.5	13.0	0	0.00	0.50
13648	4	4	0.03	0.03	11.7	7.2	0	0.00	4.50
13650	2100	2100	16.55	16.55	13.4	13.0	0	0.00	0.46
13686	2166	2166	17.86	17.86	12.4	12.0	0	0.00	0.38
13724	2	2	0.02	0.02	6.0	5.9	0	0.00	0.07
13858	4662	4665	52.74	52.78	12.0	11.6	-3	-0.04	0.46
13859	3616	3616	29.59	29.59	12.3	11.9	0	0.00	0.37
14055	28	28	0.33	0.33	2.4	6.4	0	0.00	-4.00
14448	1	1	0.01	0.01	6.0	6.1	0	0.00	-0.10
14883	2	2	0.02	0.02	5.7	5.8	0	0.00	-0.14
15244	46	46	0.36	0.36	5.8	10.4	0	0.00	-4.59
15347	19	19	0.14	0.14	6.2	10.4	0	0.00	-4.25
15445	242	242	1.97	1.97	5.2	5.3	0	0.00	-0.03
15448	5	5	0.03	0.03	4.5	10.4	0	0.00	-5.87
15459	4150	4150	33.92	33.92	4.1	4.0	0	0.00	0.03
15555	2	2	0.02	0.02	4.0	10.4	0	0.00	-6.41
21540	1003	1003	11.56	11.56	16.5	15.7	0	0.00	0.76
22565	588	588	6.83	6.83	16.7	15.9	0	0.00	0.79
22852	360	360	4.19	4.19	16.6	15.9	0	0.00	0.77
9623	27	0	0.23	0.00	12.0	0.0	27	0.23	12.00
Totals:	207528	207496	2098.67	2098.36	13.0	12.5	32	0.31	0.43

APPENDIX A

RDSCATS, A PROGRAM TO READ AND CONSOLIDATE
THE SCATS AND R-SCATS DATABASES

Prepared by:

Frank Schmittroth
Westinghouse Hanford Company
August 1996

APPENDIX A: RDSCATS, A Program to Read and Consolidate the SCATS and R-SCATS Databases.

The RDSCATS program was written specifically to read the diverse formats of the SCATS and R-SCATS database file. It performs the following functions:

1. Procedures Get scats and Get rscats read the records from each database. The built-in C routine strtok is then called to parse the record into fields.
2. The procedure Add key consolidates multiple records corresponding to the same key.
3. The routine Calc MWD, based on fitted regression coefficients is used to convert both Mark IV and Mark IA burnups given in $^{240}\text{Pu}(\%)$ to MWD/MTU.
4. The File out routine creates separate files Hscats.dat and Hrscats.dat representing the consolidated key data and in a format suitable as input to the DKPRO program.

FILE FORMATS

Both the SCATS and R-SCATS files have numerous fields that are not used in the present study. Only the fields explicitly used are described here. Field numbers start with 0 according to the C language convention.

SCATS

FieldNo.	Field name	Description
0	ItemID	Identification
3	NoPiec	No. of pieces
4	FormCd	"I" for Mark IA; "V" for Mark IV
23	OutEWt	Outer element weight (g)
25	InEWt	Inner element weight (g)
29	P4OU35	Percent ^{240}Pu or ^{235}U
36	MtCode	(10,20, or 81) for U; 50 for Pu

RSCATS

FieldNo.	Field name	Description
0	Basin	Basin location (not used)
1	Key	Key number
4	Material type	("MIV", "MIA", "NAT") for (Mark IV, Mark IA, Natural) resp.
5	Pieces	No. of pieces
6	Pu	Pu weight (g)
9	Pu240	^{240}Pu weight (g)
13	U	U weight (g)

RDSCATS Program Listing

```

/* rdscats is a program to read the SCATS and R-SCATS databases */
/* Subkeys are added together to create a common set of key */
/* records that can be compared */
/* F. Schmittroth, WHC (7/10/96) */

#include <stdio.h>
#include <string.h>
#include <stdlib.h>

#define NBUF 1024
#define NBIN 20

typedef struct ( /* structure for key data */
    int id;
    char type[20];
    double npieces;
    double u;
    double pu;
    double pu240;
    double pct240;
) key_typ;

typedef struct ( /* structure for complete database */
    int n;
    key_typ *data;
) dBase;

char buff[NBUF], fld[50][30];

/* Function prototype declarations */
void Add_key();
void GetId();
void Get_scats();
void Get_rscats();
void PreOut();
void LineOut();
void FileOut();
void Output();
void Tot_key();
void Clr_key();
void Calc_pct240();
double Calc_Mwd();
void Bin();

/*----- main program -----*/
main()
{
    dBase scats, rscats;

    Get_scats(&scats); /* read scats database */
    Get_rscats(&rscats); /* read r-scats database */

    Calc_pct240(&scats);
    Calc_pct240(&rscats);

    Output(&scats, &rscats);

    Bin(&scats, &rscats); /* put results into %Pu240 bins */

    return 0;
}

/*----- Get_scats (read SCATS database) -----*/
void Get_scats(scats)
    dBase *scats; /* Note that scats is a pointer unlike in main */
{

```



```

FILE *fin;
int nskey, nfld, uflag, npieces, nrcrd=0;
double ewt, inewt, outewt;
char *bp;
key_typ key, *s_keys;

nskey = 0;
s_keys = (key_typ *) malloc( 1000*sizeof(key_typ) );

fin = fopen("keymod1.dat", "r");

while( fgets(buff, NBUF, fin) !=NULL ) {
    nrcrd++;
    /* parse comma-delimited buffer into fields */
    nfld = 0;
    bp = strtok(buff, ",");
    while( bp != NULL ) {
        if(nrcrd==1) printf("%d: %s\n", nfld, bp);
        strcpy(fld[nfld++], bp);
        bp = strtok(NULL, ",");
    }
    if( nrcrd > 1 ) {
        GetId(&key.id, fld[0]);

        inewt = atof(fld[25]);
        outewt = atof(fld[23]);
        npieces = atof(fld[31]);
        ewt = npieces * (inewt + outewt);

        if( inewt*outewt > 0.0 )
            ewt = ewt/2.0;

        uflag = strstr(fld[36], "10") || /* Set uranium flag */
                strstr(fld[36], "20") ||
                strstr(fld[36], "81");

        Clr_key(&key);

        if( uflag ) { /* Is record U? */
            key.u = ewt;
            key.npieces = npieces;
            strcpy(key.type, fld[4]);
            Add_key(&nskey, s_keys, key); /* Add key to list */
        }

        if( strstr(fld[36], "50") ) { /* Is record Pu? */
            key.pu = ewt;
            key.pu240 = ewt * 0.01 * atof( fld[29] );
            Add_key(&nskey, s_keys, key);
        }
    }
    printf("nrcrd = %d\n", nrcrd);

    scats->n = nskey;
    scats->data = s_keys;

    return;
}

/*----- Get_rscats (read R-SCATS database) -----*/
void Get_rscats(rscats)
dbase *rscats; /* Note that scats is a pointer unlike in main */
{
    FILE *fin;
    int nrskey, nfld, nrcrd=0;
    char *bp;
    key_typ key, *rs_keys;

```

```

nrskey = 0;
rs_keys = (key_typ *) malloc( 1000*sizeof(key_typ) );

fin = fopen("KEY-SUM1.dat", "r");

while( fgets(buff, NBUF, fin) !=NULL ) {
    nrcrd++;
    /* parse buffer into fields */
    nfld = 0;
    bp = strtok(buff, "\\t");
    while( bp != NULL ) {
        if(nrcrd==1) printf("%d: %s\\n", nfld, bp);
        strcpy(fld[nfld++], bp);
        bp = strtok(NULL, "\\t");
    }
    if( nrcrd > 1 ) {
        key.id = atoi(fld[1]);
        strcpy(key.type, fld[4]);
        key.npieces = atoi(fld[5]);
        key.u = atof(fld[13]);
        key.pu = atof(fld[6]);
        key.pu240 = atof(fld[9]);

        Add_key(&nrskey, rs_keys, key); /* Add key to rs_keys list */
    }
    printf("nrcrd = %d\\n", nrcrd);

    rscats->n = nrskey;
    rscats->data = rs_keys;

    return;
}

/*----- utility routines -----*/
void PreOut(scats, rscats)
dbase *scats, *rscats;
{
    int k;

    printf("-----\\n");
    for(k=0; k<5; k++)
        printf("%12d: %15f %10.1f\\n", scats->data[k].id,
            scats->data[k].u, scats->data[k].npieces);

    printf("-----\\n");
    for(k=0; k<5; k++)
        printf("%12d: %15f %10.1f\\n", rscats->data[k].id,
            rscats->data[k].u, rscats->data[k].npieces);

    return;
}

/*----- Output results -----*/
void Output(scats, rscats)
dbase *scats, *rscats;
{
    int k, ks, kr, ns, nr;
    int match;
    key_typ skey, rkey, stot, rtot;
    char labl[10];
    FILE *sfile, *rfile;

    ns = scats->n;
    nr = rscats->n;

    sfile = fopen("Hscat.dat", "w"); /* Create scats file for Dkpro */
    rfile = fopen("Hrscat.dat", "w"); /* Create r-scats file for Dkpro */

```

```

Clr_key(&stot); Clr_key(&rtot);

for(ks=0; ks<ns; ks++) {           /* Loop thru scats database */
    skey = scats->data[ks];

    match = 0;
    for(kr=0; kr<nr; kr++) {
        rkey = rscats->data[kr];
        if( skey.id == rkey.id ) { /* Check r-scats for same record */
            match = 1;
            break;
        }
    }
    if( !match ) {
        Clr_key(&rkey);
        printf("- not found in rscats -\n");
    }

    /* print a line with both scats & rscats */
    sprintf(labl, "%d", skey.id);
    LineOut(labl, &skey, &rkey);
    FileOut(sfile, &skey); /* Save scats key */
    if( match )
        FileOut(rfile, &rkey); /* Save r-scats key */

    Tot_key(&stot, &skey);
    Tot_key(&rtot, &rkey);

} /* end of scats loop */

stot.pct240 = 100.0*(stot.pu240/stot.pu);
rtot.pct240 = 100.0*(rtot.pu240/rtot.pu);

LineOut("Totals:", &stot, &rtot); /* print totals */

return;
}

void Calc_pct240(db) /* Calculate % Pu 240 */
dbase *db;
{
    key_typ key;
    int k;

    for(k=0; k<db->n; k++) {
        key = db->data[k];
        db->data[k].pct240 = (key.pu > 0.0) ?
            100.0*(key.pu240/key.pu) : 0.0;
    }
    return;
}

void LineOut(labl, skey, rkey) /* Print a line of the table */
char *labl;
key_typ *skey, *rkey;
{
    printf("%8s ", labl);
    printf("(%5s,%5s) ", skey->type, rkey->type);
    printf("%7.0f %7.0f ", skey->npieces, rkey->npieces);
    printf("%8.2f %8.2f ", skey->u/1e6, rkey->u/1e6);
    printf("%8.2f %8.2f ", skey->pu/1e3, rkey->pu/1e3);
    printf("%8.2f %8.2f ", skey->pu240/1e3, rkey->pu240/1e3);
    printf("%7.2f %7.2f", skey->pct240, rkey->pct240);
    printf("\n");

    return;
}

void FileOut(fil, key) /* Output a key record to a DKPRO file */

```

```

FILE *fil;
key_type *key;

(
static char type[] [20] = {"MK-IV", "MK-1A", "NAT"};
int ityp;
double bu;

if( strstr(key->type, "V") )      /* MK-IV */
    ityp = 0;
else if( strstr(key->type, "I") ) /* MK-1A */
    ityp = 1;
else if( strstr(key->type, "N") ) /* NAT */
    ityp = 2;
else
    printf("**** Unrecognized type in FileOut ***\n");

if(ityp == 2)
    ityp = 0;      /* use MK-IV to calc. bu for NAT */

bu = Calc_MWd(ityp, key->pct240); /* convert from %Pu240 -> MWd/MTU */

fprintf(fil, "%5d %-8s%-8s%11.3e%11.3e\n",
        key->id, type[ityp], "KBASIN", bu, key->u/1e6);

return;
)

void Bin(scats, rscats) /* Bin the keys in %Pu240 bins for plotting */
dbase *scats, *rscats;
(
double smtu[NBIN], rmtu[NBIN];
double frac, mu;
int k, ks, kr, ns, nr, ibin;
key_type skey, rkey;

ns = scats->n;
nr = rscats->n;

for(k=0; k<NBIN; k++) (
    smtu[k] = 0.0;
    rmtu[k] = 0.0;
)

for(ks=0; ks<ns; ks++) ( /* bin the scats data */
    skey = scats->data[ks];
    ibin = skey.pct240;
    frac = skey.pct240 - ibin;
    mu = skey.u/1e6;
    smtu[ibin+1] += frac * mu;
    smtu[ibin] += (1.0-frac) * mu;
)

for(kr=1; kr<nr; kr++) ( /* bin the r-scats data */
    rkey = rscats->data[kr];
    ibin = rkey.pct240;
    frac = rkey.pct240 - ibin;
    mu = rkey.u/1e6;
    rmtu[ibin+1] += frac * mu;
    rmtu[ibin] += (1.0-frac) * mu;
)

for(k=0; k<NBIN; k++) (
    printf("%5d %8.2f %8.2f\n", k, smtu[k], rmtu[k] );
)

return;
)

void GetId(id1, id) /* extract key id from characters 3-7 and */
int *id1;          /* convert to an integer */

```

```

char *id;
{
    int k;

    for(k=3; k<8; k++)
        id[k-3] = id[k];
    id[5] = '\0';
    *id1= atoi(id);

    return;
}

void Add_key(nkey, keylist, key) /* Create a consolidated keylist */
int *nkey;
key_typ *keylist, key;
{
    int k;

    if( *nkey <=0 )
        *nkey = 0; /* 1st entry for new key */

    else {
        for(k=0; k<*nkey; k++) { /* prior keys saved */
            if( keylist[k].id == key.id ) { /* search for key */
                /* found it */
                keylist[k].u += key.u;
                keylist[k].npieces += key.npieces;
                keylist[k].pu += key.pu;
                keylist[k].pu240 += key.pu240;
                return;
            }
        }

        keylist[*nkey] = key; /* add new key */
        (*nkey)++;

        return;
    }

double Calc_Mwd(ityp, pct240) /* Calc. Mwd/MT from pct240 */
int ityp;
double pct240;
{
    int k;
    double pwr, sum;
    static double coef[2][4]= {
        {2.716, 143.1, 2.014, 0.227}, /* coefficients for MKIV fuel */
        {0.787, 203.1, 0.015, 0.282} /* coefficients for MKIA fuel */
    };

    if( ityp > 1)
        printf("**** Unrecognized type in Calc_Mwd ***: %d\n", ityp);

    sum = 0.0;
    pwr = 1.0;
    for (k=0; k<4; k++) {
        sum += coef[ityp][k] * pwr;
        pwr = pct240 * pwr;
    }

    return (1.1 * sum); /* correction from Mwd/ton to Mwd/MT */
}

void Tot_key(tot, key) /* Total key values */
key_typ *tot, *key;
{
    tot->u += key->u;

```

```

    tot->npieces += key->npieces;
    tot->pu += key->pu;
    tot->pu240 += key->pu240;

    return;
}

void Clr_key(key)      /* Clear key values */
    key_typ *key;
{
    key->u = 0.0;
    key->npieces = 0.0;
    key->type[0] = '\0';
    key->pu = 0.0;
    key->pu240 = 0.0;
    key->pct240 = 0.0;
    return;
}

```

APPENDIX B

COMMENTS BY REVIEWER
WARREN D. WITTEKIND

The R-SCATS isotopic database was maintained at a time when high accuracy of isotopic tables was very desirable. The isotopic tables previous to R-SCATS were based on DCODE computer code predictions (UNI-1937 ADD1 dated 11/11/1985). The isotopic table in R-SCATS was based on wet chemistry analyses. The isotopic tables in R-SCATS are: 1) isotopic production tables (referenced to N Reactor measured power levels), and 2) isotopic segregation tables (not referenced to N Reactor power level).

The isotopic segregation tables (UNI-2384 dated 2/1/84) were referred to neutron counts in fuel segregation detectors and N Reactor exposure measurements were lost. The neutron count standards were matched to chemically analyzed fuel elements. There was one isotopic segregation table adjustment (UNI-4008 dated 6/25/86) based on approximately eleven individual element analyses. This adjustment was meant to be applied retroactively.

The isotopic production tables were periodically adjusted to fit wet chemistry analysis (UNI-3332 dated 2/26/85, UNI-3771 dated 12/02/85, and WHC-0188 dated 2/11/88). These isotopic tables were not meant to be applied retroactively, but from their effective date onward. The reason for this was the resistance temperature devices (RTDs) were preferentially failing (defined as ± 8 °C from the mean of near neighbor RTDs) by measuring too low a temperature (80%) as compared to measuring too high a temperature (20%). The R-SCATS kept the previous isotopic calculations and applied these adjustments forward in time.

The R-SCATS compared to within 1% on plutonium quantity for the entire PUREX campaign November 1983 through December 1988.

I do not have knowledge of the SCATS data base. I believe there were changes in SCATS to incorporate some discrepancies between R-SCATS and SCATS. I also suspect that there was only one isotopic production table used, the most recent one and this would have been applied retroactively to all previous production. This retroactive application of the most recent isotopic production table would predict too high a Pu-240 composition for the same N Reactor MWD/T exposure, which is the observed difference between SCATS and R-SCATS for the same fuel quantity.

Warren D. Wittekind

DISTRIBUTION SHEET

To Distribution	From Criticality and Shielding	Page 1 of 1			
		Date August 1996			
Project Title/Work Order Comparison of Spent Fuel Databases for K Basin		EDT No. 616570			
		ECN No.			
Name	MSIN	Text With All Attach.	Text Only	Attach./ Appendix Only	EDT/ECN Only

R. G. Cowan	R3-86	X
C. Defigh-Price	X3-79	X
K. D. Dobbin	H0-35	X
D. R. Duncan	R3-86	X
J. R. Frederickson	R3-86	X
J. Greenborg	H0-35	X
A. L. Pajunen	R3-86	X
A. L. Ramble	A3-38	X
F. A. Schmittroth	H0-35	X
W. L. Willis	R3-86	X
W. D. Wittekind	H0-32	X
Central Files	A3-88	X