ornl

**OAK RIDGE
NATIONAL
LABORATORY**

LOCKHEED MARTIN

RECEIVED
JUN 08 1999
U S T I

**Neutronics Benchmarks for the
Utilization of Mixed-Oxide Fuel:
Joint U.S./Russian Progress Report
for Fiscal Year 1997**

**Volume 4, Part 7—Homogeneous
Mixtures of Polystyrene-Moderated
Plutonium and Uranium Oxides**

Fissile Materials Disposition Program

MANAGED AND OPERATED BY
LOCKHEED MARTIN ENERGY RESEARCH CORPORATION
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

ORNL-27 (3-96)

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

**NEUTRONICS BENCHMARKS FOR THE UTILIZATION
OF MIXED-OXIDE FUEL: JOINT U.S./RUSSIAN
PROGRESS REPORT FOR FISCAL YEAR 1997**

**Volume 4, Part 7—Homogeneous Mixtures of Polystyrene-Moderated
Plutonium and Uranium Oxides**

Musa Yavuz

Date Published: May 1999

Report Prepared by
LOCKHEED MARTIN ENERGY RESEARCH CORP.
P.O. Box 2008
Oak Ridge, Tennessee 37831-6363
Under
Subcontract Number 85B99398V

Funded by
Office of Fissile Materials Disposition
United States Department of Energy

Prepared for
Computational Physics and Engineering Division
Oak Ridge National Laboratory
Oak Ridge, Tennessee 37831
managed by
LOCKHEED MARTIN ENERGY RESEARCH CORP.
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-96OR22464

**HOMOGENEOUS MIXTURES OF POLYSTYRENE-MODERATED
PLUTONIUM AND URANIUM OXIDES**

Evaluator

**Musa Yavuz
Department of Mechanical Engineering
The University of Texas at Austin**

Internal Reviewer

**Naeem M. Abdurrahman
Department of Mechanical Engineering
The University of Texas at Austin**

External Reviewers

**M. E. Dunn
R. Trenton Primm III
Oak Ridge National Laboratory**

HOMOGENEOUS MIXTURES OF POLYSTYRENE-MODERATED PLUTONIUM AND URANIUM OXIDES¹

1. Detailed Description

1.1 Overview of Experiment

In the 1970s at the Battelle Pacific Northwest Laboratory (PNL), a series of critical experiments using a remotely operated Split-Table Machine was performed with homogeneous mixtures of (Pu-U)O₂-polystyrene fuels in the form of square compacts having different heights. With respect to Pu enrichments and moderation [H/(Pu+U) atomic] ratios (MR), four-different homogeneous (Pu-U)O₂-polystyrene mixtures were considered: Mixture 1) 7.6 wt% Pu with 19.5 MR, Mixture 2) 7.89 wt% Pu with 51.8 MR, Mixture 3) 14.62 wt% Pu with 30.6 MR, and Mixture 4) 30.0 wt% Pu with 47.4 MR. The Pu²⁴⁰ isotopic contents in Pu were 23 wt% for Mixture 1 and 8 wt% for Mixtures 2-4. In all mixtures, the uranium was depleted to about 0.151 wt% U²³⁵. The critical geometric dimensions for both fully Plexiglas^{TM} reflected and unreflected configurations were reported for Mixture 3 and 4 experiments. The dimensions for Mixture 1 and 2 experiments were given for fully-reflected assemblies.

This evaluation contains a total of 39 critical (fully reflected and bare) experimental configurations as well as 3 slab geometry critical dimensions.

1.2 Description of Experimental Configuration

A large glove box within a heavily shielded cell located at the PNL Critical Mass Laboratory (CML) was used for the experiments. The floor surface of CML was 1067 cm square, with 152-cm-thick side walls (except for a 91-cm-thick south wall) and a 61-cm-thick roof and floor [Smolen 1994]. A remotely operated Split-Table Machine (STM) shown in Fig. 1 was used for performing the experiments. Each half of the split table, one stationary and the other movable, had a steel frame. One of the table halves formed a surface of 76-cm wide and 61-cm long, and the other formed a surface of 76-cm wide and 46-cm long. The table surface was 51-cm above the floor level.

A 30-cm thick aluminum honeycomb material (effective Al density of 0.037 g/cm³) covered both table halves [Richey 1965]. For Mixture 1 [Lloyd 1974], the geometric dimensions of compacts, including the uncertainties in the measurements for fuel, clad and stacking void are given in Table 1. For Mixtures 2-4 [Bierman 1973], the length and width of solid fuel compacts were in the range of 5.08-5.09 cm, and the height having dimensions of 5.08, 5.09, 3.81 and 1.27 cm was variable. Each of the fuel compacts was clad with a 6-mil-thick #471 tape manufactured by Minnesota Mining and Manufacturing (3M) Company.

In Table 2, the experimentally corrected critical dimensions of the fuel assemblies are given for Mixture 1. For this mixture, Table 3 contains the number of compacts used in the experiments with the specified length, width, and height. The heights are given in number of compacts plus a compact of smaller size. Smaller size compacts should be treated as full layers of thinner fuel compacts having a thickness equal to the fractional layer "times" the thickness indicated for the compacts. The measured (corrected) critical

---

¹ Evaluator - Musa Yavuz, The University of Texas at Austin.

Internal Reviewer - Naeem M. Abdurrahman, The University of Texas at Austin.

External Reviewers - M. E. Dunn and R. Trenton Primm, III, Oak Ridge National Laboratory.

Keywords: critical experiment, mixed oxide fuel, Plexiglas-reflected, plutonium, polystyrene-moderated, Split-Table Machine.

dimensions and masses of fuel for Mixtures 2–4 experiments are given in Tables 4–6. In all experiments, the Plexiglas reflector had a thickness of 15 cm.

Table 1. Fuel compact dimensions for Mixture 1

Compacts	Length (cm)	Width (cm)	Height (cm)
Unclad	5.090 ± 0.005	5.090 ± 0.006	5.088 ± 0.018 1.279 ± 0.040
Clad	5.120 ± 0.005	5.120 ± 0.005	5.148 ± 0.018 1.339 ± 0.040
Stacked (clad + void)	5.153 ± 0.010	5.153 ± 0.010	5.172 ± 0.025 1.422 ± 0.043

Table 2. Critical dimensions for Mixture 1 [843 g (Pu+U)/liter]

Case	Critical dimensions (cm)		
	Length	Width	Height ^a
1	61.08 ± 0.06	66.17 ± 0.07	30.49 ± 0.15
2	61.08 ± 0.06	61.08 ± 0.06	31.80 ± 0.16
3	66.17 ± 0.07	66.17 ± 0.07	29.24 ± 0.16
4	61.08 ± 0.06	50.90 ± 0.05	35.61 ± 0.18
5	61.08 ± 0.06	55.99 ± 0.06	33.24 ± 0.16
6	50.90 ± 0.05	50.90 ± 0.05	40.76 ± 0.20
7 ^b	47.27 ± 0.20	47.27 ± 0.20	47.27 ± 0.20

^aExperimentally determined corrections (12.7% reduction in critical height) accounting for the reactivity of the cladding material and the stacking voids.

^bCube dimensions obtained by interpolation between critical assemblies.

Table 3. Critical dimensions in terms of number of compacts for Mixture 1

Case	Fuel length	Fuel width	Fuel height	
	5.09 cm	5.09 cm	5.088 cm	1.279 cm ^a
1	12	13	6	3.434 ± 0.012
2	12	12	7	0.632 ± 0.004
3	13	13	6	2.317 ± 0.020
4	12	10	8	0.068 ± 0.008
5	12	11	7	1.920 ± 0.016
6	10	10	9	0.703 ± 0.028

^aFractional layers should be treated as full layers having the fractional indicated thickness.

Table 4. Critical dimensions and masses for Mixture 2 [360 g (Pu+U)/liter]

Case	Critical dimensions (cm)			Critical mass (kg)	
	Length	Width	Height ^a	Pu	U
1	40.72±0.04	45.72±0.09	32.89±0.12	1.74±0.01	20.29±0.22
2	50.90±0.05	50.80±0.10	26.40±0.10	1.94±0.02	22.63±0.25
3	61.08±0.06	60.96±0.12	22.66±0.08	2.39±0.02	27.88±0.31
4	61.08±0.06	66.04±0.13	22.09±0.18	2.53±0.03	29.53±0.39
5	61.08±0.06	55.88±0.11	23.22±0.08	2.25±0.02	26.26±0.28
6	61.08±0.06	50.80±0.10	24.37±0.09	2.15±0.02	25.06±0.28
7	40.72±0.05	40.64±0.08	36.42±0.13	1.71±0.01	19.97±0.22
8 ^b	39.12±0.28	39.12±0.28	39.12±0.28	1.70±0.01	19.84±0.32
9 ^c	Infinite	Infinite	14.83±0.60	—	—

^aExperimentally determined corrections (~15% reduction in critical height) accounting for the reactivity of the cladding material and the stacking voids.

^bCube dimensions obtained by interpolation between critical assemblies.

^cInfinite slab thickness obtained by extrapolation of data.

Table 5. Critical dimensions and masses for Mixture 3 [580 g (Pu+U)/liter]

Case	Critical dimensions (cm)			Critical mass (kg)	
	Length	Width	Height ^a	Pu	U
1	30.54±0.03	40.72±0.04	29.81±0.15	3.14±0.04	18.35±0.35
2	40.72±0.04	40.72±0.04	23.84±0.10	3.35±0.04	19.57±0.37
3	45.81±0.04	50.90±0.05	19.82±0.11	3.92±0.05	22.89±0.44
4	50.90±0.04	50.90±0.05	18.92±0.09	4.16±0.05	24.28±0.46
5	61.08±0.06	50.90±0.05	17.72±0.09	4.67±0.06	27.28±0.52
6	61.08±0.06	61.08±0.06	16.53±0.09	5.26±0.06	30.73±0.59
7 ^b	33.30±0.17	33.30±0.17	33.30±0.17	3.13±0.05	18.28±0.40
8 ^c	Infinite	Infinite	11.56±0.09	—	—
9 ^d	40.72±0.04	40.76±0.17	52.39±0.07	7.37±0.05	43.06±0.82
10 ^d	40.72±0.04	45.86±0.19	45.10±0.06	7.14±0.08	41.70±0.79
11 ^d	50.90±0.05	45.86±0.19	36.99±0.05	7.32±0.08	42.75±0.81
12 ^d	43.78±0.07	43.78±0.07	43.78±0.07	7.12±0.08	41.55±0.80

^aExperimentally determined corrections (~4% reduction in critical height) accounting for the reactivity of the cladding material and the stacking voids.

^bCube dimensions obtained by interpolation between critical assemblies.

^cInfinite slab thickness obtained by extrapolation of data.

^dBare (unreflected) critical dimensions.

Table 6. Critical dimensions and masses for Mixture 4 [373 g (Pu+U)/liter]

Case	Critical dimensions (cm)			Critical mass (kg)	
	Length	Width	Height ^a	Pu	U
1	30.54±0.03	30.54±0.03	30.89±0.02	3.23±0.05	7.53±0.12
2	35.63±0.04	35.63±0.04	23.95±0.10	3.40±0.05	7.94±0.12
3	40.72±0.04	40.72±0.04	20.22±0.05	3.75±0.05	8.76±0.13
4	50.90±0.05	45.81±0.05	17.14±0.07	4.48±0.06	10.44±0.16
5	61.08±0.06	50.90±0.05	15.53±0.11	5.44±0.08	12.69±0.20
6	61.08±0.06	55.99±0.06	15.16±0.02	5.80±0.09	13.51±0.21
7	66.17±0.06	61.08±0.06	14.43±0.10	6.53±0.09	15.24±0.22
8	50.90±0.02	50.90±0.05	16.49±0.04	4.78±0.08	11.14±0.18
9 ^b	30.60±0.02	30.60±0.02	30.60±0.02	3.21±0.05	7.49±0.12
10 ^c	Infinite	Infinite	10.80±0.11	—	—
11 ^d	45.81±0.05	40.72±0.04	37.98±0.06	7.93±0.12	18.51±0.78
12 ^d	40.72±0.04	40.72±0.04	42.24±0.03	7.84±0.11	18.30±0.77
13 ^d	45.81±0.05	50.90±0.05	32.49±0.02	7.84±0.12	19.80±0.84
14 ^d	41.20±0.05	41.20±0.05	41.20±0.05	7.83±0.11	18.28±0.77

^a Experimentally determined corrections (~2% reduction in critical height) accounting for the reactivity of the cladding material and the stacking voids.

^b Cube dimensions obtained by interpolation between critical assemblies.

^c Infinite slab thickness obtained by extrapolation of data.

^d Bare (unreflected) critical dimensions.

1.3 Description of Material Data

The number densities of nuclides contained in fuel (MOX+polystyrene), clad (#471 3M tape) and reflector (methacrylate plastic or Plexiglas) are given in Table 7 for Mixtures 1–4. The ²³⁹Pu content in Pu was 68% for Mixture 1, and 91% for Mixtures 2–4.

Table 7. Composition of fuel, clad and reflector

Nuclide	Atomic density (E+24 atom/cm ³) ^a				Clad (3M tape)	Reflector (plexiglas)
	Mixture 1 [843 g (Pu+U)/liter]	Mixture 2 (408 g Oxide/liter)	Mixture 3 (660 g Oxide/liter)	Mixture 4 (426 g Oxide/liter)		
Am ²⁴¹	3.766E-07	1.741E-07	4.036E-07	3.511E-07		
Pu ²³⁸	9.535E-07	0.0	0.0	0.0		
Pu ²³⁹	1.092E-04	6.528E-05	1.954E-04	2.578E-04		
Pu ²⁴⁰	3.688E-05	5.941E-06	1.702E-05	2.257E-05		
Pu ²⁴¹	8.945E-06	3.481E-07	1.211E-06	1.756E-06		
Pu ²⁴²	4.689E-06	0.0	0.0	0.0		
U ²³⁵	2.897E-06	1.285E-06	1.904E-06	1.008E-06		
U ²³⁸	1.968E-03	8.376E-04	1.252E-03	6.604E-04		
O	4.348E-03	1.830E-03	3.023E-03	1.974E-03		1.428E-02
H	4.155E-02	4.719E-02	4.489E-02	4.468E-02	4.489E-02	5.712E-02
C	4.287E-02	4.540E-02	4.412E-02	4.537E-02	3.110E-02	3.570E-02
Cl	—	—	—	—	7.24E-03	—

^a Read E+24 as 10²⁴.

In Table 7, the number density for U^{235} of Mixture 4 is an order of magnitude lower than what was given in [Bierman 1973]. The reason for this is explained in Section 2 (Evaluation of Experimental Data). For Mixture 1, the cladding material per compact was 3.175 g and the cladding density was 1.12 g/cm^3 . Uranium density per compact was $0.779 \pm 0.006 \text{ g/cm}^3$, the plutonium density was $0.064 \pm 0.001 \text{ g/cm}^3$ and the total fuel density was $1.884 \pm 0.015 \text{ g/cm}^3$. For Mixtures 2-4, the cladding properties were not given because of the reported critical dimensions that account for the reactivity effect of the cladding and stacking void. The measured critical masses of plutonium and uranium are given in Tables 4-6. Particle size distributions which indicate the homogeneity are presented in Table 8 for Mixtures 1-4.

Table 8. Particle size distributions

Distribution (%)	Particle diameter (μm)			
	Mixture 1 $\text{PuO}_2\text{-UO}_2$	Mixtures 2-4		
		PuO_2	UO_2	Polystyrene
95	—	<20	<40	<225
90	<20	—	—	—
50	<5	<5	<9	<150
10	<0.8	—	—	—
5	—	<0.5	<3	<50

1.4 Supplemental Experimental Measurements

Inverse multiplication measurements to determine the critical dimensions were performed for both unreflected and fully Plexiglas-reflected configurations for Mixtures 3 and 4. Measurements for Mixtures 1 and 2 were only considered for fully reflected assemblies because of the large volume requirement for unreflected assemblies.

For Mixtures 2-4, critical dimensions in length, width, and experimentally corrected heights were reported. Also, experimentally corrected critical masses of solid fuel assemblies were presented. The corrections on the critical dimensions and masses were made to account for the reactivity effect of cladding and the presence of voids in the assembly of stacked compacts. These corrections were obtained by observing the change in critical mass due to varying the number of layers of cladding on the fuel compacts. For Mixture 1, the experimental assemblies were provided both in terms of fuel compacts and corrected critical dimensions of fuel only. For bare assemblies, an additional correction was also made to account for the reactivity effect of the structural material. The correction was an increase of 0.05% in the critical mass of each bare assembly.

Buckling measurements were performed for six bare critical assemblies. The extrapolation distances of 2.56 cm for Mixture 4 and 2.49 cm for Mixture 3 were calculated. The critical buckling values together with critical dimensions are shown in Table 9 for Mixtures 3 and 4.

Table 9. Critical buckling for Mixtures 3 and 4

Mixture 4 [373 g/(Pu+U)/liter]			
Critical dimensions (cm), $\lambda = 2.56 \pm 0.08$ cm*			
Width	Length	Height	B_g^2 (m ⁻²)
45.81 $\pm$ 0.05	40.72 $\pm$ 0.04	37.98 $\pm$ 0.06	138.16 $\pm$ 1.34
40.72 $\pm$ 0.04	40.72 $\pm$ 0.04	42.24 $\pm$ 0.03	137.94 $\pm$ 1.28
45.81 $\pm$ 0.05	50.90 $\pm$ 0.04	32.49 $\pm$ 0.03	139.27 $\pm$ 1.54
Average			138.46 $\pm$ 1.39
Mixture 3 [580 g/(Pu+U)/liter]			
Critical dimensions (cm), $\lambda = 2.49 \pm 0.07$ cm*			
Width	Length	Height	B_g^2 (m ⁻²)
40.76 $\pm$ 0.17	40.72 $\pm$ 0.04	52.39 $\pm$ 0.07	124.42 $\pm$ 1.47
45.86 $\pm$ 0.19	40.72 $\pm$ 0.04	45.10 $\pm$ 0.06	124.79 $\pm$ 1.36
45.86 $\pm$ 0.19	50.90 $\pm$ 0.05	36.99 $\pm$ 0.05	125.82 $\pm$ 1.43
Average			125.01 $\pm$ 1.43

*Extrapolation length.

2 Evaluation of Experimental Data

Material densities for fuel compacts (Mixtures 1–4) were documented in detail. However, the MR for Mixture 4 is not 47.4. Also, the U^{235} enrichment in U does not correspond to the reported 0.151 wt%. The number density for U^{235} given in [Bierman 1973] is an order of magnitude high. The corrected number density of $1.008 \leftrightarrow 10^{-6}$ is used in Table 7, rather than $1.008 \leftrightarrow 10^{-5}$. With this correction, the MR becomes 47.35 which is in agreement with the reported 47.4. Also, the enrichment of U^{235} becomes about 0.151 wt%. The rest of the material densities were correctly presented.

The geometric units of compacts were given in inches in [Bierman 1973], but the SI units were used in presenting the critical dimensions. In this evaluation, we use the SI units to be consistent with the critical dimensions.

Although the geometric (fuel-clad-void) compact data for Mixture 1 is well presented, this is not the case for Mixtures 2–4. Cladding compositions for Mixtures 2–4 compacts were not given although it is defined by #471 3M tape. The #471 3M tape composition [Bierman 1996] is the same as the Mixture 1 compacts. The stacking void per compact was not provided for these mixture experiments. Instead, the critical sizes and masses were given for solid assemblies of fuel only. Experimentally determined corrections were applied in each case to account for the reactivity effect of the cladding material and the presence of voids in the assembly of the stacked blocks.

The experimentally corrected dimensions of solid fuels were determined graphically. In these graphs, the critical height was plotted as a function of layers of cladding material. Using the data points in these plots, the critical height was extrapolated to zero cladding to determine the critical height of solid fuels only. These plots indicate that for Mixture 4 experiments, there were 3 data points (1, 2, and 3 layers of clad). However, for Mixtures 1–3, there were 2 data points in the reported figures (1 and 2 layers of clad). The fitted curve for Mixture 4 appears to be linear.

For bare assemblies, it is reported that there was only 0.05% increase in critical masses due to structural supports, but the descriptions of these were not given. Also, the exact location of the split table machine (STM) in the heavily shielded cell was not described. In addition, the critical dimensions were determined for slab by extrapolation of data and cube by interpolation between critical assemblies.

The critical dimensions reported in [Bierman 1973] for (Pu-U)O₂-polystyrene and (Pu²³⁹-U)O₂-water mixtures in spherical, cylindrical, and slab geometries are not included in this evaluation. These dimensions were calculated by extrapolating one, two or three experimental data points.

For Mixtures 2-4, the experimentally corrected dimensions of solid fuels were given. However, for Mixture 1, the critical dimensions were provided both in terms of number of compacts and the experimentally corrected dimensions of solid assemblies of fuel only. Thus, for Mixture 1:

- (a) the corrected dimensions in Table 2 can be calculated from those in Table 3, and
- (b) if the k_{eff} of the experiments both in terms of number of compacts and the experimentally corrected dimensions are within the statistical uncertainty, then the corrected dimensions can directly be used for simplifying the computational modeling.

To check "a", the corrected dimensions in Table 2 are calculated using Table 3 dimensions. (The length and the width dimensions of compacts agree each other as seen in Tables 2 and 3.) The corrected critical height given in Table 2 is a 12.7% reduction (accounting for the reactivity effect of the clad and the stacking voids) of the critical height given in Table 3. To verify this, for example, the total fuel height of Case 1 in Table 3 is $6 \leftrightarrow 5.088 + 3 \leftrightarrow 1.279 + (5.12/5.088)^2 \leftrightarrow 1.279 \leftrightarrow 0.434 = 34.927$ cm. Considering a 12.7% experimental reduction, the critical height is $(1.0 - 0.127) \leftrightarrow 34.927 = 30.491$ cm, which agrees with the Case 1 dimension of 30.49 cm given in Table 2. Also, all the other dimensions in Tables 2 and 3 agree each other in this manner.

To verify "b", MCNP calculations were performed. Polyethylene (poly.01t) thermal cross sections both in Fuel and Plexiglas was used. The calculated k_{eff} are 0.98210 ± 0.00154 for the Case 1 of Table 2 and 0.98264 ± 0.00094 for the Case 1 of Table 3. Also, the calculated k_{eff} are 0.98635 ± 0.00125 for the Case 2 of Table 2, and 0.98634 ± 0.00139 for the Case 2 of Table 3. Thus, k_{eff} s agree each other within the statistical uncertainty. This suggests that the experimentally corrected critical dimensions can directly be used in modeling the experiments. The input listings for these cases are given in Section 6. (Sample MCNP Input Listings.)

3 Benchmark Specifications

3.1 Description of Model

In the benchmark models, experimentally corrected solid fuel critical dimensions accounting for the reactivity effect of the cladding and the stacking voids are considered in calculating k_{eff} . Plexiglas surrounding the assemblies is used as reflector.

3.2 Dimensions

The corrected critical dimensions given in Tables 2, 4, 5, and 6 are used for Mixtures 1-4 experiments, respectively. In all assemblies, a 15-cm-thick Plexiglas reflector is used.

3.3 Material Data

The number densities of Mixtures 1-4 are given in Table 7.

3.4 Temperature Data

Because temperature data was not reported, a room temperature of 300K is assumed.

4 Results of Sample Calculations

The sample k_{eff} calculations were performed using the MCNP4A continuous cross section library based on the ENDF/B-VI data. Polyethylene thermal cross sections (poly.01t card) are used for both fuel mixtures and Plexiglas. In the calculations, 4000 particle histories, 100 active and 25 skipped generations were used. However, additional particle histories were made if k_{eff} had not attained a constant level after 400000 active particle histories. In Table 10, the calculated k_{eff} are listed for the critical dimensions given in Tables 2, and 4-6 for Mixtures 1-4, respectively.

Table 10. MCNP k_{eff} for cases in Tables 2, 4, 5, and 6

Case	Table 2	Table 4	Table 5	Table 6
1	0.98210 ± 0.00154	1.02956 ± 0.00140	1.01503 ± 0.00155	1.00690 ± 0.00155
2	0.98635 ± 0.00125	1.02315 ± 0.00136	1.01885 ± 0.00133	1.00819 ± 0.00134
3	0.98532 ± 0.00123	1.02144 ± 0.00124	1.01331 ± 0.00135	1.00699 ± 0.00145
4	0.98645 ± 0.00142	1.02099 ± 0.00212	1.01105 ± 0.00139	1.00310 ± 0.00148
5	0.98858 ± 0.00134	1.01867 ± 0.00122	1.01567 ± 0.00159	1.00470 ± 0.00148
6	0.99110 ± 0.00130	1.02351 ± 0.00137	1.01549 ± 0.00138	1.00243 ± 0.00154
7	0.99372 ± 0.00062	1.02940 ± 0.00125	1.02286 ± 0.00143	1.00846 ± 0.00131
8		1.02813 ± 0.00130	1.00208 ± 0.00126	1.00565 ± 0.00141
9		0.99725 ± 0.00116	1.01234 ± 0.00151	1.00539 ± 0.00137
10			1.01033 ± 0.00158	1.01431 ± 0.00122
11			1.00995 ± 0.00151	0.99572 ± 0.00177
12			1.01396 ± 0.00159	0.99302 ± 0.00183
13				0.99148 ± 0.00152
14				0.99545 ± 0.00155

5 References

- Bierman 1973. S. R. Bierman, E. D. Clayton, and L. E. Hansen, "Critical Experiments with Homogeneous Mixtures of Plutonium and Uranium Oxides Containing 8, 15, and 30 wt% Plutonium," *Nucl. Sci. Eng.*, **50**, 115-126 (1973).
- Lloyd 1974. R. C. Lloyd, S. R. Bierman, and E. D. Clayton, "Criticality of Plutonium-Uranium Mixtures Containing 5-8 wt% Plutonium," *Nucl. Sci. Eng.*, **55**, 51-57 (1974).
- Richey 1965. C. R. Richey, J. D. White, E. D. Clayton, and R. C. Lloyd, "Criticality of Homogeneous Plutonium Oxide-Plastic Compacts at H:Pu = 15," *Nucl. Sci. Eng.*, **23**, 150-158 (1965).
- Smolen 1994. G. R. Smolen, R. C. Lloyd, and H. Funabashi, "Critical Data and Validation Studies of Plutonium-Uranium Nitrate Solutions in Cylindrical and Slab Geometry," *Nuclear Technology*, **107**, 304 (1994).
- Bierman 1996. S. R. Bierman, *private communication*, December 1996.

2.10.6 Sample MCNP Input Listings

CASE 1 of TABLE 2: 7.6 wt% Pu; H:(U+Pu)=19.5 Moderation Ratio

C Cell Cards -Full Layer Compacts

1 1 0.0908999411 1 -2 3 -4 5 -6 imp:n=1 \$ Fuel

2 2 0.1071 7 -8 9 -10 11 -12

#1 imp:n=1 \$ Plexiglas

3 0 -7:8:-9:10:-11:12 imp:n=0 \$ outside of the assembly

C Surface Cards

C Full Size Fuel Compact Dimensions

1 pz -15.245

2 pz 15.245 \$ Fuel Height

3 px -30.54

4 px 30.54 \$ Fuel Length

5 py -33.085

6 py 33.085 \$ Fuel Width

C Plexiglas Reflector (15 cm-thick)

7 pz -30.245

8 pz 30.245

9 px -45.54

10 px 45.54

11 py -48.095

12 py 48.095

kcode 4000 1 25 125

ksrc 0. 0. 0.

print

m1 95241.60c 3.766e-7 94238.60c 9.535e-7 94239.60c 1.092e-4

94240.60c 3.688e-5 94241.60c 8.945e-6 94242.60c 4.689e-6

92235.60c 2.897e-6 92238.60c 1.968e-3 8016.60c 4.348e-3

1001.60c 4.155e-2 6000.60c 4.287e-2 \$ Fuel Composition

m2 1001.60c 5.712e-2 6000.60c 3.570e-2 8016.60c 1.428e-2

\$ Plexiglas Reflector

Composition

m1t poly.01t

m2t poly.01t

CASE 1 of Table 3: 7.6 wt% Pu; H:(U+Pu)=19.5 Moderation Ratio
C Cell Cards -Full Compacts (5.09 x 5.09 x 5.088)

1	1	0.0908999411	1	-2	3	-4	5	-6	u=1	imp:n=1	
									\$ (Pu+U)O ₂ -Polystyrene Mixture		
2	2	0.08323	7	-8	9	-10	11	-12			
			#1						u=1	imp:n=1	\$ 3M-Clad
3	0		#1 #2						u=1	imp:n=1	\$ Stacking Void

C 12x13x6 Fuel Blocks

4	0		13	-14	15	-16	17	-18	imp:n=1	lat=1	u=2
									fill=-5:0	-11:0	-12:0
									1	935R	\$12x13x6 Fuel Blocks
5	0	19	-20	21	-22	23	-24	fill=2	imp:n=1		

C -Smaller Compacts (5.09 x 5.09 x 1.279)

6	1	0.0908999411	27	-28	3	-4	5	-6	u=3	imp:n=1	
									\$ (Pu+U)O ₂ -Polystyrene Mixture		
7	2	0.08323	26	-29	9	-10	11	-12			
			#6						u=3	imp:n=1	\$ 3M-Clad
8	0		#6 #7						u=3	imp:n=1	\$ Stacking Void

C 12x13x3 Fuel Blocks

9	0		20	-30	15	-16	17	-18	imp:n=1	lat=1	u=4
									fill=-2:0	-11:0	-12:0
									3	467R	\$12x13x3 Fuel Blocks
10	0	31	-32	21	-22	23	-24	fill=4	imp:n=1		

C Fractional Layer

11	1	0.0908999411	32	-34	15	-22	17	-24	imp:n=1		
									\$ (Pu+U)O ₂ -Polystyrene Mixture		
12	3	0.1071	#5	#10	#11	38	-39	40	-41	42	-43
									imp:n=1	\$ Plexiglas Reflector	
13	0	-38:39:-40:41:-42:43							imp:n=0	\$ Outside of Critical Assembly	

C Surface Cards

C Full Size Fuel Compacts

1	pz	0.042	
2	pz	5.13	\$ Fuel Height
3	px	0.0315	
4	px	5.1215	\$ Fuel Length
5	py	0.0315	
6	py	5.1215	\$ Fuel Width

C Clad Compacts

7	pz	0.012
8	pz	5.16
9	px	0.0165
10	px	5.1365
11	py	0.0165
12	py	5.1365

C Stacked Compacts (Fuel+Clad+Void)

13	pz	0.0
14	pz	5.172
15	px	0.0
16	px	5.153
17	py	0.0
18	py	5.153

C Window Surfaces

19	pz	0.000001
20	pz	31.031999
21	px	0.000001
22	px	61.835999
23	py	0.000001
24	py	66.988999

C
C Smaller Fuel Compact having height of 1.279 cm

C
26 pz 31.0735
27 pz 31.1035
28 pz 32.3825
29 pz 32.4125
30 pz 32.454

C Window Surfaces

31 pz 31.032
32 pz 35.297999

C Fractional layer on top

34 pz 35.853086

C Reflector

38 pz -15.
39 pz 50.853086
40 px -15.
41 px 76.836
42 py -15.
43 py 81.989

kcode 4000 1 25 225

ksrc 31. 33.5 18.

c print

m1 95241.60c 3.766e-7 94238.60c 9.535e-7 94239.60c 1.092e-4
94240.60c 3.688e-5 94241.60c 8.945e-6 94242.60c 4.689e-6
92235.60c 2.897e-6 92238.60c 1.968e-3 8016.60c 4.348e-3
1001.60c 4.155e-2 6000.60c 4.287e-2 \$ Fuel Composition
m2 1001.60c 4.489e-2 6000.60c 3.110e-2 17000.60c 7.240e-3
\$ Clad Composition
m3 1001.60c 5.712e-2 6000.60c 3.570e-2 8016.60c 1.428e-2
\$ Plexiglas Reflector Composition
m1t poly.01t
m2t poly.01t
m3t poly.01t

CASE 2 of TABLE 2: 7.6 wt% Pu; H:(U+Pu)=19.5 Moderation Ratio

C Cell Cards -Full Layer Compacts

```
1      1 0.0908999411 1 -2 3 -4 5 -6  imp:n=1 $ Fuel
2      2 0.1071      7 -8 9 -10 11 -12
          #1
3      0      -7:8:-9:10:-11:12  imp:n=0 $ outside of the assembly
          imp:n=1 $ Plexiglas
```

C Surface Cards

C Full Size Fuel Compact Dimensions

```
1      pz -15.9
2      pz 15.9      $ Fuel Height
3      px -30.54
4      px 30.54      $ Fuel Length
5      py -30.54
6      py 30.54      $ Fuel Width
```

C Plexiglas Reflector (15 cm-thick)

```
7      pz -30.9
8      pz 30.9
9      px -45.54
10     px 45.54
11     py -45.54
12     py 45.54
```

kcode 4000 1 25 125

ksrc 0. 0. 0.

print

```
m1      95241.60c 3.766e-7 94238.60c 9.535e-7 94239.60c 1.092e-4
        94240.60c 3.688e-5 94241.60c 8.945e-6 94242.60c 4.689e-6
        92235.60c 2.897e-6 92238.60c 1.968e-3 8016.60c 4.348e-3
        1001.60c 4.155e-2 6000.60c 4.287e-2 $ Fuel Composition
m2      1001.60c 5.712e-2 6000.60c 3.570e-2 8016.60c 1.428e-2
        $ Plexiglas Reflector Composition
m1t     poly.01t
m2t     poly.01t
```

CASE 2 of TABLE 3: 7.6 wt% Pu; H:(U+Pu)=19.5 Moderation Ratio

C Cell Cards -Full Layer Compacts

```
1      1 0.0908999411 1 -2 3 -4 5 -6 u=1 imp:n=1
      $ (Pu+U)O2-Polystyrene Mixture
2      2 0.08323      7 -8 9 -10 11 -12
      #1 u=1 imp:n=1 $ 3M-Clad
3      0      #1 #2 u=1 imp:n=1 $ Stacking Void
C 12x12x7 Fuel Blocks
4      0      13 -14 15 -16 17 -18 imp:n=1 lat=1 u=2
      fill=-6:0 -11:0 -11:0 1 1007R $12x12x7 Fuel Blocks
5      0 19 -20 21 -22 23 -24 fill=2 imp:n=1
C Corrections
6      1 0.0908999411 20 -25 15 -22 17 -24 imp:n=1
      $ (Pu+U)O2-Polystyrene
7      3 0.1071 #5 #6 30 -31 32 -33 34 -35 imp:n=1
      $ Plexiglas Reflector
8      0 -30:31:-32:33:-34:35 imp:n=0 $ Outside of Critical Assembly
```

C Surface Cards

C Full Size Fuel Compact Dimensions

```
1      pz 0.042
2      pz 5.13      $ Fuel Height
3      px 0.0315
4      px 5.1215      $ Fuel Length
5      py 0.0315
6      py 5.1215      $ Fuel Width
```

C Clad Compacts

```
7      pz 0.012
8      pz 5.16
9      px 0.0165
10     px 5.1365
11     py 0.0165
12     py 5.1365
```

C Stacked Compacts (Fuel+Clad+Void)

```
13     pz 0.0
14     pz 5.172
15     px 0.0
16     px 5.153
17     py 0.0
18     py 5.153
```

C Window Surfaces

```
19     pz 0.000001
20     pz 36.203999
21     px 0.000001
22     px 61.835999
23     py 0.000001
24     py 61.835999
```

C Corrections

```
25     pz 37.012328
```

C Reflector

```
30     pz -15.0
31     pz 52.012328
32     px -15.0
33     px 76.836
34     py -15.0
35     py 76.836
```

```
kcode 4000 1 25 225
ksrc 31. 31. 18.5
c print
m1 95241.60c 3.766e-7 94238.60c 9.535e-7 94239.60c 1.092e-4
    94240.60c 3.688e-5 94241.60c 8.945e-6 94242.60c 4.689e-6
    92235.60c 2.897e-6 92238.60c 1.968e-3 8016.60c 4.348e-3
    1001.60c 4.155e-2 6000.60c 4.287e-2 $ Fuel Composition
m2 1001.60c 4.489e-2 6000.60c 3.110e-2 17000.60c 7.240e-3
    $ Clad Composition
m3 1001.60c 5.712e-2 6000.60c 3.570e-2 8016.60c 1.428e-2
    $ Plexiglas Reflector Composition
m1t poly.01t
m2t poly.01t
m3t poly.01t
```

Figure 1. Remote split table with faces separated.

INTERNAL DISTRIBUTION

1-5.	B. B. Bevard	20.	H. T. Kerr
6.	J. J. Carbajo	21.	M. A. Kuliasha
7.	E. D. Collins	22.	G. E. Michaels
8.	B. S. Cowell	23.	B. D. Murphy
9.	M. D. DeHart	24.	D. L. Moses
10.	F. C. Difilippo	25.	C. V. Parks
11.	R. J. Ellis	26-30.	R. T. Primm III
12-16.	J. C. Gehin	31.	C. C. Southmayd
17.	S. R. Greene	32.	Central Research Library
18.	T. W. Horning	33-34.	ORNL Laboratory Records (OSTI)
19.	D. T. Ingersoll	35.	ORNL Laboratory Records-RC

EXTERNAL DISTRIBUTION

36. N. Abdurrahman, College of Engineering, Dept. of Mechanical Engineering, University of Texas, Austin, Texas 78712
37. M. L. Adams, Department of Nuclear Engineering, Texas A&M University, Zachry 129, College Station, TX 77843
38. H. Akkurt, College of Engineering, Dept. of Mechanical Engineering, University of Texas, Austin, Texas 78712
39. D. Alberstein, Los Alamos National Laboratory, MS-E502, P.O. Box 1663, Los Alamos, NM 87545
40. J. Baker, Office of Fissile Materials Disposition, U. S. Department of Energy, MD-3, 1000 Independence Avenue SW, Washington, DC 20585
41. J. B. Briggs, Idaho National Environmental and Engineering Laboratory, P.O. Box 1625-3855, Idaho Falls, ID 83415-3855
42. L. Holgate, Office of Fissile Materials Disposition, U. S. Department of Energy, MD-1/2, 1000 Independence Avenue SW, Washington, DC 20585
43. A. Caponiti, Office of Fissile Materials Disposition, U. S. Department of Energy, MD-3, 1000 Independence Avenue SW, Washington, DC 20585
44. K. Chidester, Los Alamos National Laboratory, MS-E502, P.O. Box 1663, Los Alamos, NM 87545
45. W. Danker, U. S. Department of Energy, MD-3, 1000 Independence Avenue SW, Washington, DC 20585
46. T. Gould, Lawrence Livermore National Laboratory, P.O. Box 808, MS-L186, Livermore, CA 94551
47. L. Jardine, Lawrence Livermore National Laboratory, P.O. Box 808, MS-L166, Livermore, CA 94551
48. Dr. Alexander Kalashnikov, Institute of Physics and Power Engineering, 1 Bondarenko Square, Obninsk, Kaluga Region, Russia 249020
- 49-53. D. E. Klein, Associate Vice Chancellor for Special Engineering Programs, The University of Texas System, 210 West Sixth Street, Austin, TX 78701
54. J. O. Nulton, Office of Fissile Materials Disposition, U.S. Department of Energy, MD-3, 1000 Independence Avenue SW, Washington, DC 20585
55. S. L. Passman, Sandia National Laboratories, 1401 Wilson Blvd., Suite 1050, Arlington, VA 22209
- 56-60. Dr. Alexander Pavlovitch, Russian Research Center "Kurchatov Institute," Institute of Nuclear Reactors VVER Division, VVER Physics Department, 123182, Kurchatov Square, 1, Moscow, Russia
61. K. L. Peddicord, Associate Vice Chancellor, Texas A&M University, 120 Zachry, College Station, TX 77843-3133
62. G. Radulescu, Framatom Cogema Fuels, 1261 Town Center Drive, MS-423, Las Vegas, Nevada 89143
63. W. D. Reece, Texas A&M University, Department of Nuclear Engineering, Zachry 129, College Station, TX 77843-3133
64. P. T. Rhoads, Office of Fissile Materials Disposition, U.S. Department of Energy, MD-4, 1000 Independence Avenue SW, Washington, DC 20585
65. J. Thompson, Office of Fissile Materials Disposition, U.S. Department of Energy, MD-4, 1000 Independence Avenue SW, Washington, DC 20585
66. Fitz Trumble, Westinghouse Savannah River Company, Building 730R, Room 3402, WSRC, Aiken, SC 29808
67. M. Yavuz, 7201 Wood Hollow Drive, #475, Austin, TX 78731