12
**ULTRA-HIGH IMPLANT ACTIVATION EFFICIENCY IN GaN USING
NOVEL HIGH TEMPERATURE RTP SYSTEM**

MRS Spring
SAN098-0950C

SAND-98-0950C
CONF-980405--

X. A. Cao *, C. R. Abernathy *, R. K. Singh *, S. J. Pearton *, M. Fu **, V. Sarvepalli **, J. A. Sekhar **, J. C. Zolper ***, D. J. Rieger ****, J. Han ****, T. J. Drummond ****, R. J. Shul **** and R. G. Wilson *****

* Department of Materials Science and Engineering, University of Florida, Gainesville, FL 32611 USA

** Micropyrretics Heaters international, Inc. Cincinnati, OH 45212 USA

*** Office of Naval Research, Arlington, VA 22217 USA

**** Sandia National Laboratories, Albuquerque, NM 87185 USA

***** Consultant, Stevenson Ranch, CA 91381 USA

RECEIVED

APR 29 1998

OSTI

ABSTRACT

Si⁺ implant activation efficiencies above 90%, even at doses of $5 \times 10^{15} \text{ cm}^{-2}$, have been achieved in GaN by RTP at 1400-1500 °C for 10 secs. The annealing system utilizes with MoSi₂ heating elements capable of operation up to 1900 °C, producing high heating and cooling rates (up to $100 \text{ °C} \cdot \text{s}^{-1}$). Unencapsulated GaN show severe surface pitting at 1300 °C, and complete loss of the film by evaporation at 1400 °C. Dissociation of nitrogen from the surface is found to occur with an approximate activation energy of 3.8 eV for GaN (compared to 4.4 eV for AlN and 3.4 eV for InN). Encapsulation with either rf-magnetron reactively sputtered or MOMBE-grown AlN thin films provide protection against GaN surface degradation up to 1400 °C, where peak electron concentrations of $\sim 5 \times 10^{20} \text{ cm}^{-3}$ can be achieved in Si-implanted GaN. SIMS profiling showed little measurable redistribution of Si, suggesting $D_{\text{Si}} \leq 10^{-13} \text{ cm}^2 \cdot \text{s}^{-1}$ at 1400 °C. The implant activation efficiency decreases at higher temperatures, which may result from Si_{Ga} to Si_N site switching and resultant self-compensation.

Introduction

Ion implantation is an enabling technology for fabrication of GaN-based ultra-high power thrysistors, junction field-effect transistors (JFETs) and heterostructure field effect transistors (HFETs)⁽¹⁻¹⁰⁾. In particular selective area implantation can be used to reduce transistor access resistance by creating highly doped contact regions. Most published device characteristics show evidence of relatively high access resistances⁽¹¹⁻¹⁴⁾. To date GaN JFETs formed entirely by implantation into undoped material⁽²⁾ and GaN light emitting diodes (LEDs) formed by Mg⁺ implantation into n-type epi layers⁽¹⁵⁾ are the only devices fabricated using implant doping.

Past work has shown that in compound semiconductors the annealing temperature required for implant activation is a fairly high percentage of the melting temperature of the material, and is also a function of the implant dose^(16,17). In GaN it has been observed that low dose ($\leq 5 \times 10^{14} \text{ cm}^{-2}$) implants anneal poorly up to 1100 °C, leaving a coarse network of extended defects, while high dose ($\geq 2 \times 10^{15} \text{ cm}^{-2}$) implants may lead to amorphization. Amorphous layers recrystallize in the range 800-1000 °C to form defective polycrystalline material⁽¹⁸⁾. Quite good activation efficiencies have been obtained for n-type implanted dopants in spite of high residual damage⁽¹⁹⁻²¹⁾. It is also clear that annealing temperatures above 1300 °C are desirable for optimal electrical properties in the implanted layers^(19,20). The equilibrium N₂ pressure over GaN at 1400 °C is $> 1000 \text{ bar}$ ^(22,23), and at these temperatures only two methods have proven effective in preventing

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DTIC QUALITY INSPECTED 1

MASTER

19980528 012

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

surface decomposition. The first is use of high N_2 pressures (15 kbar)⁽²⁴⁾, and the second is deposition of AlN encapsulation layers⁽²⁵⁾ (at 1400 °C the equilibrium N_2 pressure above AlN is only 10^{-8} bar).

In this paper we report use of a new high-temperature rapid thermal processing system for annealing of implanted GaN at temperatures up to 1500 °C. When used in conjunction with AlN cap layers, very high activation efficiencies ($\geq 90\%$) can be obtained even for Si^+ ion doses of $5 \times 10^{15} \text{ cm}^{-2}$. This approach is attractive for processing of GaN devices in a conventional fabrication-line environment, without the need for specialized high-pressure furnaces.

Experimental

Undoped ($n \sim 1-8 \times 10^{16} \text{ cm}^{-3}$) GaN films 2-3 μm thick were grown on Al_2O_3 substrates at ~ 1040 °C by Metal Organic Chemical Vapor Deposition. Si^+ ions were implanted at 25 °C to a dose of $5 \times 10^{15} \text{ cm}^{-2}$ at an energy of 100 keV. This produces a maximum Si concentration at a projected range of 800 Å, according to a Transport-of-Ions-in-Matter calculation. The samples were deposited with AlN by reactive sputtering or by Metal Organic Molecular Beam Epitaxy, and were sealed in quartz ampoules under N_2 gas at 15 psi (the slight negative pressure was to prevent ampoule blow-out at elevated temperature). Annealing was performed in an MHI Zapper RTP furnace containing novel molybdenum intermetallic composite heating elements. These are maintained at constant temperature, and a motor driven actuator is used to achieve high ramp-up and ramp-down rates by inserting or removing the sample. Annealing was performed at 1100-1500 °C for dwell times of 10 secs. The samples were characterized by scanning electron microscopy, atomic force microscopy, Hall measurements (using alloyed 420 °C, 180 secs In-based contacts), and by Secondary Ion Mass Spectrometry (SIMS) using a cameca system and a Cs^+ ion beam.

Results and Discussion

A typical temperature-time profile for an annealing cycle is shown in Figure 1. Excellent temperature uniformity ($\leq \pm 4$ °C over a 9×6 " area at 1500 °C) and reproducibility was obtained. When unencapsulated samples were annealed, the GaN surface remained of reasonable quality at 1200 °C, at 1300 °C hexagonal pits at high density ($\sim 10^8 \text{ cm}^{-2}$) were observed with substantial loss of material, at 1400 °C only the AlN buffer layers remained, while at 1500 °C even this generally peeled away to leave only the Al_2O_3 substrate. By contrast, AlN-capped samples retained good quality surfaces to >1400 °C. Occasional localized cap failures were observed, and potential mechanisms for these are currently under investigation. One possibility is agglomeration of residual H_2 in the AlN to form bubbles which evolve from the material. From temperature-dependent studies we measured activation energies for N_2 loss of ~ 3.8 eV for GaN and 4.4 eV for AlN⁽²⁶⁾.

Electrical results for activated samples are shown in Figure 2. Note that in unencapsulated samples the sheet electron density increases with annealing temperature up to 1200 °C, but this was the highest temperature we could obtain data for due to loss of the film. By contrast, the AlN encapsulated samples showed a peak in the sheet electron density at 1400 °C, with a reduction at 1500 °C. Note that the 300 K electron mobility decreases at 1500 °C, indicating that the material is becoming more compensated. This behavior is fairly typical of Si implant activation in III-V materials, and is usually ascribed to self-compensation through Si site-switching, i.e. some of the Si_{Ga} donors move to Si_N sites, producing self-compensation. Note that with a peak Si activation efficiency of $\sim 90\%$, the corresponding peak electron concentration will be $\sim 5 \times 10^{20} \text{ cm}^{-3}$. This

very high doping level produces extremely good specific contact resistances for W and WSi_x metallization, with values $\leq 10^{-6} \Omega \cdot \text{cm}^2$ after annealing in the range 600-900 °C. This demonstrates the efficiency of the implantation approach for reducing contact resistances in GaN electronic devices.

Figure 1. Time-temperature profiles for RTP annealing of GaN at 1500 °C.

Figure 2. Sheet carrier density and electron mobility in Si implanted GaN after uncapped or AlN-capped annealing.

Figure 3 shows the calculated, as-implanted Si atomic profile, and the SIMS profiles of as-implanted and 1400 °C annealed samples. There are several obvious points in the data. First, the Profile Code algorithm does not produce a good match to the experimental profile, and some work will need to be done to obtain better stopping power data for the ions in GaN. Second, there is little redistribution of the Si at 1400 °C, with $D_{\text{Si}} \leq 10^{-13} \text{ cm}^2 \cdot \text{s}^{-1}$ at this temperature calculated from the change in width at half-maximum. This result emphasizes the extremely stable nature of dopants in GaN even at very high processing temperatures.

Figure 3. Calculated (from PCODE) and experimentally measured (by SIMS) profiles of implanted Si (100 keV, $5 \times 10^{15} \text{ cm}^{-2}$) in GaN.

SUMMARY AND CONCLUSIONS

To produce low specific contact resistances in selected area of GaN-based electronic devices, ion implantation is an attractive option. However, to achieve high doping levels, high implant doses and therefore high annealing temperatures are required. The major difficulty with processing GaN above $\sim 1150 \text{ }^{\circ}\text{C}$ is prevention of surface dissociation. The use of AlN encapsulation works well to temperatures of $\geq 1400 \text{ }^{\circ}\text{C}$, where Si implant activation efficiency is a maximum for high dose ($5 \times 10^{15} \text{ cm}^{-2}$) conditions. The activation efficiency decreases at higher temperatures, along with a decrease in electron mobility, which is consistent with Si self-compensation.

ACKNOWLEDGEMENTS

The work of UF is partially supported by grants from NSF-DMR (L. Hess), DARPA/EPRI (E. R. Brown/J. Melcher) and a sub-contract from MHI, who are supported by a BMDO SBIR grant (F19628-97-C-0092) monitored by Dr. Joe Lorenzo. R. G. Wilson is partially supported by a grant from ARO (Dr. J. M. Zavada). Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed-Martin company, for the US Department of Energy under contract No. DE-AC04-94AL85000.

References

1. S. C. Binari, L. B. Rowland, W. Kruppa, G. Kelner, K. Doverspike and D. K. Gaskill, *Electron. Lett.* **30** 1248 (1994).
2. J. C. Zolper, R. J. Shul, A. G. Baca, R. G. Wilson, S. J. Pearton and R. A. Stall, *Appl. Phys. Lett.* **68** 2273 (1996).
3. J. C. Zolper, in *GaN and Related Materials* (Gordon and Breach, NY 1997).
4. J. C. Zolper and R. J. Shul, *MRS Bulletin* **22** 36 (1997).
5. J. C. Zolper, M. H. Crawford, S. J. Pearton, C. R. Abernathy, C. B. Vartuli, C. Yuan and R. A. Stall, *J. Electron. Mater.* **25** 839 (1996).
6. J. C. Zolper, R. G. Wilson, S. J. Pearton and R. A. Stall, *Appl. Phys. Lett.* **68** 1945 (1996).
7. H. H. Tan, J. S. Williams, J. Zou, D. J. H. Cockayne, S. J. Pearton and R. A. Stall, *Appl. Phys. Lett.* **69** 2364 (1996).
8. J. C. Zolper, M. H. Crawford, H. H. Tan, J. S. Williams, J. Zou, D. J. H. Cockayne, S. J. Pearton and R. F. Karlicek, *Appl. Phys. Lett.* **70** 2729 (1997).
9. S. Strite, P. W. Epperlein, A. Dommen, A. Rockett and R. F. Broom, *Mat. Res. Soc. Symp. Proc.* **395** 795 (1996).
10. N. Parikh, A. Suvkhanov, M. Lioubtchenko, E. Carlson, M. Bremser, D. Bray, R. Davis and J. Hunn, *Nucl. Instr. Meth. B* **127/128** 463 (1997).
11. J. Burm, K. Chu, W. A. Davis, W. J. Schaff, L. F. Eastman and T. J. Eustis, *Appl. Phys. Lett.* **70** 464 (1997).
12. Q. Chen, M. A. Khan, J. W. Yang, C. J. Sun, M. S. Shur and H. Park, *Appl. Phys. Lett.* **69** 794 (1996).
13. Y. -F. Wu, B. P. Keller, S. Keller, D. Kapolnek, P. Kozodoy, S. P. DenBaars and U. K. Mishra, *Appl. Phys. Lett.* **69** 1438 (1996).
14. N. X. Nguyen, B. P. Keller, S. Keller, Y. F. Wu, M. Le, C. Nguyen, S. P. DenBaars, U. K. Mishra and D. Grider, *Electron. Lett.* **33** 334 (1997).
15. H. P. Maruska (private communication).
16. J. S. Williams, *Rep. Prog. Phys.* **49** 491 (1986).
17. S. J. Pearton, J. S. Williams, K. T. Short, S. T. Johnson, D. C. Jacobsen, J. M. Poate, J. M. Gibson and D. O. Boerma, *J. Appl. Phys.* **65** 1089 (1989).
18. H. H. Tan, J. S. Williams, J. Zou, D. J. H. Cockayne, S. J. Pearton, J. C. Zolper and R. A. Stall, *Appl. Phys. Lett.* **72** 1190 (1998).
19. J. C. Zolper, J. Han, R. M. Biefeld, S. B. Van Deusen, W. R. Wampler, S. J. Pearton, J. S. Williams, H. H. Tan, R. Karlicek and R. A. Stall, *Mat. Res. Soc. Symp.* **468** (1997).
20. J. C. Zolper, J. Han, R. M. Biefeld, S. B. Van Deusen, W. R. Wampler, D. J. Reiger, S. J. Pearton, J. S. Williams, H. H. Tan and R. Stall, *J. Electron. Mater.* (to be published).

21. S. J. Pearton, C. R. Abernathy, C. B. Vartuli, J. C. Zolper, C. Yuan and R. A. Stall, Appl. Phys. Lett. 67 1435 (1995).
22. S. Porowski and I. Grzegory, in GaN and Related Materials, ed. S. J. Pearton (Gordon and Breach, NY 1997).
23. N. Newman, In GaN Vol. I, ed. J. Reenkove and T. D. Moustakas (Academic Press, NY 1998).
24. J. C. Zolper, J. Han, S. B. Van Deusen, M. H. Crawford, R. M. Biefeld, J. Jun, T. Suski, J. M. Baranowski and S. J. Pearton, 1997 Fall MRS Meeting.
25. J. C. Zolper, D. J. Reiger, A. G. Baca, S. J. Pearton, J. W. Lee and R. A. Stall, Appl. Phys. Lett. 69 538 (1996).
26. J. Hong, J. W. Lee, J. D. MacKenzie, S. M. Donovan, C. R. Abernathy, S. J. Pearton and J. C. Zolper, Semicon. Sci. Technol. 12 1310 (1997).

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525

Publ. Date (11) 199804
Sponsor Code (18) DOE/CR, XF
UC Category (19) UC-900, DOE/ER

DOE