SEP 26 1996

20

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT

618182

2. To: (Receiving Organization) Packaging Engineering		3. From: (Originating Organization) Packaging Engineering		4. Related EDT No.: NA	
5. Proj./Prog./Dept./Div.: 84100		6. Design Authority/ Design Agent/Cog. Engr.: B. D. Flanagan		7. Purchase Order No.: NA	
8. Originator Remarks: Two boxes designed for the Plywood Box SEP will be used to transport a total of less than 10 A's from the 325 Building to the burial grounds. The attached SEP is being submitted for review, approval, and release.				9. Equip./Component No.: NA	
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No				10. System/Bldg./Facility: NA	
				12. Major Assem. Dwg. No.: NA	
				13. Permit/Permit Application No.: NA	
				14. Required Response Date: September 25, 1996	

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	WHC-SD-TP-SEP-052	NA	0	Safety Evaluation for Packaging for Two Plywood Boxes	SQ	1,2	1	

16. KEY					
Approval Designator (F)		Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-E, Sec.12.7)		1. Approval	4. Review	1. Approved	4. Reviewed no/comment
		2. Release	5. Post-Review	2. Approved w/comment	5. Reviewed w/comment
		3. Information	6. Dist. (Receipt Acknow. Required)	3. Disapproved w/comment	6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)											
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSN
4,1	4,1	Design Authority	WB Larson	9/24/96	28	4,1		JR Green	JR Green	9/26/96	G1-11
4,1	4,1	Design Agent	BD Flanagan	9/25/96	11	4,1		MJ Riess	MJ Riess	9/26/96	P7-75
4,1	4,1	Cog.Eng.	BD Flanagan	9/25/96	11						
4,1	1	Cog. Mgr.	JG Field	9/26/96	G1-11						
4,1	4,1	QA	CR Hoover	9/26/96	G1-11						
4,1	4,1	Safety	DW McNally	9/26/96	G1-119						
4,1	4,1	RL Clawson	RL Clawson	9/26/96	G1-13						

18. B-D Flanagan Signature of EDT Originator		19. J.G. Field Authorized Representative Date for Receiving Organization		20. J.G. Field Design Authority/ Consultant Manager		21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	

Safety Evaluation for Packaging for Two Plywood Boxes

B. D. Flanagan
Westinghouse Hanford Company, Richland, WA 99352
U.S. Department of Energy Contract DE-AC06-87RL10930

EDT/ECN: 618182 UC: 513
Org Code: 84100 Charge Code: BE0739
B&R Code: YN0100000 Total Pages: 16

Key Words: transport, A₂s, 325 Building, burial grounds

Abstract: This safety evaluation for packaging authorizes onsite transport of a total of less than 10 A₂s in two plywood boxes from the 325 Building in the 300 Area to the burial grounds in the 200 West Area.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: WMC/BCS Document Control Services, P.O. Box 1970, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

Jarvis Bishop 9-26-96
Release Approval Date

Release Stamp

Approved for Public Release

CONTENTS

PART A: DESCRIPTION AND OPERATIONS

1.0	INTRODUCTION	A-1
1.1	GENERAL INFORMATION	A-1
1.2	SYSTEM DESCRIPTION	A-1
2.0	PACKAGING SYSTEM	A-1
3.0	PACKAGE CONTENTS	A-2
3.1	GENERAL DESCRIPTION	A-2
4.0	TRANSPORT SYSTEM	A-2
5.0	ACCEPTANCE OF PACKAGE FOR USAGE	A-3
6.0	OPERATING REQUIREMENTS	A-3
7.0	QUALITY ASSURANCE PROGRAM	A-3
8.0	MAINTENANCE	A-3
9.0	REFERENCES	A-3

PART B: PACKAGE EVALUATION

1.0	INTRODUCTION	B-1
1.1	SAFETY EVALUATION METHODOLOGY	B-1
1.2	EVALUATION SUMMARY AND CONCLUSIONS	B-1
2.0	CONTENTS EVALUATION	B-1
2.1	CHARACTERIZATION	B-1
2.2	SIZE AND WEIGHT	B-1
3.0	RADIOLOGICAL RISK EVALUATION	B-2
3.1	INTRODUCTION	B-2
3.2	RISK ACCEPTANCE CRITERIA	B-2
3.3	ACCIDENT FREQUENCY ASSESSMENT	B-3
3.4	DOSE CONSEQUENCE ANALYSIS	B-3
3.5	RISK EVALUATION AND CONCLUSION	B-3
4.0	CONTAINMENT EVALUATION	B-4
4.1	CONTAINMENT SOURCE SPECIFICATION	B-4
4.2	NORMAL TRANSFER CONDITIONS	B-4
4.2.1	Containment Evaluation	B-5
4.3	ACCIDENT CONDITIONS	B-5

5.0	SHIELDING EVALUATION	B-5
6.0	STRUCTURAL EVALUATION	B-5
7.0	THERMAL EVALUATION	B-5
8.0	PRESSURE AND GAS GENERATION	B-5
9.0	PACKAGE TIEDOWN SYSTEM	B-6
10.0	REFERENCES	B-6
11.0	APPENDIX: SOLID WASTE STORAGE/DISPOSAL RECORDS	B-7

LIST OF TABLES

A-1	Nuclide Content	A-2
B-1	Nuclide Content	B-2
B-2	Total Effective Dose Equivalent Spreadsheet	B-4

SAFETY EVALUATION FOR PACKAGING FOR TWO PLYWOOD BOXES

PART A: DESCRIPTION AND OPERATIONS

1.0 INTRODUCTION

1.1 GENERAL INFORMATION

This safety evaluation for packaging evaluates and documents the ability of the plywood boxes listed below to meet the packaging requirements of WHC-CM-2-14, *Hazardous Material Packaging and Shipping*, for the onsite transfer of Type B radioactive material. Onsite transfer is the transport of hazardous materials on controlled routes confined to established limited areas and to portions of federally owned roadways to which public access is prohibited during transfer.

The plywood boxes being used for this transport are PIN number PNLD-95-322 and PNLD-95-385. The contents being transported are wood, plastic, piping, rubber, and gloves. The source term was determined by nondestructive analysis and obtained from the solid waste storage/disposal record.

Before the nondestructive analysis, the intention was to transport the boxes under WHC-SD-TP-SEP-020, *Safety Evaluation for Packaging (Onsite) Plywood Box* (WHC 1994), but Type B shipments are not included.

1.2 SYSTEM DESCRIPTION

The package system consists of a plywood box 1.22 m (4 ft) wide by 2.58 m (4 ft, 5.5 in.) high by 2.44 m (8 ft) long that is lined with one sheet of minimum 0.15-mm (6-mil) plastic and loaded with solid waste contaminated with Type B radioactive materials. A complete system description and figures are listed in WHC-SD-TP-SEP-020 (WHC 1994).

2.0 PACKAGING SYSTEM

A complete description of the packaging system is listed in WHC-SD-TP-SEP-020 (WHC 1994).

3.0 PACKAGE CONTENTS

3.1 GENERAL DESCRIPTION

The authorized contents of the two plywood boxes consist of fixed contamination on wood, plastic, piping, rubber, and gloves. The waste inventory sheet for each box is provided in Part B, Section 3.0, which lists the article description and weight for the entire contents. The contents follows Part A, Section 3.0, "Package Contents," of WHC-SD-TP-SEP-020 (WHC 1994) except for a Type A quantity.

Table A-1. Nuclide Content.

Nuclide	Curies	A ₂	No. of A ₂ s
PNNL Plywood Box PNLD-95-322			
⁹⁰ Sr	1.20 E-02	2.7	4.44 E-03
¹³⁷ Cs	9.50 E-03	13.5	7.04 E-04
¹⁵² Eu	1.50 E-04	24.3	
¹⁵⁴ Eu	7.00 E-04	13.5	5.19 E-05
²⁴¹ Am	3.28 E-02	5.41 E-03	6.60 E+00
Total A ₂ s			6.07
PNNL Plywood Box PNLD-95-385			
⁹⁰ Sr	4.10 E-03	2.7	1.52 E-03
¹³⁷ Cs	3.20 E-03	13.5	2.37 E-04
¹⁵⁴ Eu	8.30 E-04	13.5	6.15 E-05
²⁴¹ Am	8.50 E-03	5.41 E-03	1.57 E+00
Total A ₂ s			1.57

PNNL = Pacific Northwest National Laboratory.

4.0 TRANSPORT SYSTEM

Follow the transport system and tiedown system description of WHC-SD-TP-SEP-020 (WHC 1994). Note that since this is an onsite transfer the roads between the 325 Building and the Wye Barricade shall be closed until the transport vehicle reaches the Wye Barricade.

5.0 ACCEPTANCE OF PACKAGE FOR USAGE

Follow the packaging acceptance criteria of WHC-SD-TP-SEP-020 (WHC 1994).

6.0 OPERATING REQUIREMENTS

Follow the operating requirements of WHC-SD-TP-SEP-020 (WHC 1994).

7.0 QUALITY ASSURANCE PROGRAM

Follow the quality assurance program of WHC-SD-TP-SEP-020 (WHC 1994).

8.0 MAINTENANCE

Follow the maintenance requirements of WHC-SD-TP-SEP-020 (WHC 1994).

9.0 REFERENCES

WHC-CM-2-14, *Hazardous Material Packaging and Shipping*, Westinghouse Hanford Company, Richland, Washington.

WHC, 1994, *Safety Evaluation for Packaging (Onsite) Plywood Box*, WHC-SD-TP-SEP-020, Rev. 0-A, Westinghouse Hanford Company, Richland, Washington.

PART B: PACKAGE EVALUATION

1.0 INTRODUCTION

1.1 SAFETY EVALUATION METHODOLOGY

The plywood box package is evaluated in this part for normal onsite transport conditions and for compliance with the onsite transportation safety criteria found in WHC-CM-2-14. A radiological risk evaluation is included to show the package meets the accident acceptance criteria.

When possible, *Safety Evaluation for Packaging (Onsite) Plywood Box* (WHC 1994) is referenced to demonstrate integrity of the plywood box during normal conditions.

1.2 EVALUATION SUMMARY AND CONCLUSIONS

As shown by the following evaluations, the plywood boxes PNLD-95-322 and PNLD-95-385 will maintain containment of their contents through all normal handling and transport conditions. Maintaining containment is demonstrated by actual testing for normal transfer conditions and meeting the requirements. Comparison of the calculated accident frequency and the estimated dose consequence associated with this shipment determines that the shipment poses no unacceptable risk. Therefore, this evaluation demonstrates that the above plywood boxes are safe for this onsite transfer of the radioactive contents listed in Part A, Section 3.0.

2.0 CONTENTS EVALUATION

2.1 CHARACTERIZATION

The contents to be transferred in the plywood boxes PNLD-95-322 and PNLD-95-385 are 6.07 A₂s and 1.57 A₂s, respectively. A solid waste storage/disposal record for each box is supplied in the appendix, Section 10.0. The nuclide contents are shown in Table B-1.

2.2 SIZE AND WEIGHT

The weight of the contents for box PNLD-95-322 and PNLD-95-385 is 870 kg (1,914 lb) and 954.5 kg (2,104 lb), respectively. A waste inventory sheet documenting each item and its weight for each box is supplied in the following appendix. The gross weight limit for the plywood boxes is 2,268 kg (5,000 lb).

Table B-1. Nuclide Content.

Nuclide	Curies	A ₂	No. of A ₂ s
PNNL Plywood Box PNLD-95-322			
⁹⁰ Sr	1.20 E-02	2.7	4.44 E-03
¹³⁷ Cs	9.50 E-03	13.5	7.04 E-04
¹⁵² Eu	1.50 E-04	24.3	
¹⁵⁴ Eu	7.00 E-04	13.5	5.19 E-05
²⁴¹ Am	3.28 E-02	5.41 E-03	6.60 E+00
Total A ₂ s			6.07
PNNL Plywood Box PNLD-95-385			
⁹⁰ Sr	4.10 E-03	2.7	1.52 E-03
¹³⁷ Cs	3.20 E-03	13.5	2.37 E-04
¹⁵⁴ Eu	8.30 E-04	13.5	6.15 E-05
²⁴¹ Am	8.50 E-03	5.41 E-03	1.57 E+00
Total A ₂ s			1.57

PNNL = Pacific Northwest National Laboratory.

3.0 RADIOLOGICAL RISK EVALUATION

3.1 INTRODUCTION

Because this shipping campaign involves only two boxes in a single shipment with a combined payload of less than 10 A₂s, the potential dose consequence is limited, as is the probability of a transportation accident resulting in release.

3.2 RISK ACCEPTANCE CRITERIA

The acceptance criteria for this shipment are based on WHC-SD-TP-RPT-001 (Mercado 1994), which limits potential dose consequences to the onsite worker to 0.05 Sv (5 rem) and the offsite dose consequences to 5.0 mSv (500 mrem) if the calculated annual accident frequency is less than 1.0 E-03. The shipment is considered acceptable if the accident frequency can be shown to be less than 1.0 E-03 and the dose consequence is below the corresponding limits. Due to the minimal activity of the box contents, the potential dose consequences of the shipment are limited.

3.3 ACCIDENT FREQUENCY ASSESSMENT

The Hanford Site accident per mile rate of $2.0 \text{ E-}07$ from WHC-SD-TP-RPT-021 (Green et al. 1996) was used to calculate the total accident release frequency for this shipment. The distance from the 300 Area to the burial grounds in the 200 West Area is approximately 45 km (28 mi); when multiplied by the accident rate, it yields a total accident release frequency of $5.6 \text{ E-}06$.

3.4 DOSE CONSEQUENCE ANALYSIS

The material being shipped in the two boxes is similar in nature to the material analyzed for shipment in the *Safety Analysis Report for Packaging (Onsite) Flexible Material Packaging* (WHC 1996). That is, the material is contaminated equipment, rags, and debris, and no liquids or powders are allowed. Also, WHC (1996) covers shipments for any locations on the Hanford Site including the 300 Area. Accordingly, the dose consequence results in WHC (1996) can be used for the analysis of this material.

WHC (1996) develops tables of doses to the Hanford Site worker per curie of activity for a number of radionuclides. The tables are divided into beta dose, gamma dose, and inhalation dose. Using these tables and the total activity in the two boxes, the total effective dose equivalent to the onsite Hanford worker is calculated to be 0.53 mSv (53 mrem). The spreadsheet used to develop these values is shown in Table B-2. The public receptor dose at 100 m is found by dividing the total inhalation dose by 30, in keeping with the methodology used in finding the worker inhalation dose. The resulting public receptor dose is 0.017 mSv (1.7 mrem). The contribution from the europium isotopes is ignored in this analysis. Given the ratios of the radionuclides present in the two boxes, the gamma contribution from the europium isotopes will be small compared to the cesium dose, and the inhalation dose from the europium will be orders of magnitudes less than the americium contribution.

The dose consequence results show that the inventory contained within the two boxes fall well below the credible range upper limits. That is, the doses are much lower than the required 0.05 Sv (5 rem) to the onsite worker and 0.05 mSv (500 mrem) to the public receptor.

3.5 RISK EVALUATION AND CONCLUSION

Comparison of the calculated accident frequency and the estimated dose consequence associated with this shipment determines that the shipment poses no unacceptable risk.

Table B-2. Total Effective Dose Equivalent Spreadsheet.

	Total	Onsite		Onsite		Onsite	
	Inventory	Worker		Worker		Worker	
	Ci	photon dose		beta dose		inhalation	
		rad/Ci	rem	rem/Ci	rem	dose	rem
						rem/Ci	
Sr-90	1.61E-02	3.25E-03	5.23E-05	8.30E+00	1.34E-01	5.00E-04	8.05E-06
Cs-137	1.27E-02	8.80E-02	1.12E-03	2.20E-01	2.79E-03	7.90E-04	1.00E-05
Am-241	4.13E-02	2.40E-02	9.91E-04	0.00E+00	0.00E+00	1.20E+00	4.96E-02
Total			2.16E-03		1.36E-01		4.96E-02
						Onsite	Offsite
						Worker	Receptor
						Total	Total
						EDE	EDE
						rem	rem
							2.68E-07
							3.34E-07
							1.65E-03
				Total		5.31E-02	1.65E-03
Dose to activity values taken from Section 3.6.2 of the FMP SARP Table 1, 3, and 5.							

4.0 CONTAINMENT EVALUATION

4.1 CONTAINMENT SOURCE SPECIFICATION

The source term has been established to be no more than 6.07 A₂s as shown in Part B, Section 2.0. The radioactive material is fissile excepted (< 15 g).

4.2 NORMAL TRANSFER CONDITIONS

The packaging will prevent any loss or dispersal of the radioactive contents visually evident and will prevent any significant increase in the radiation levels at the external surfaces when exposed to the normal transfer conditions. Normal transfer conditions are defined as Hanford environmental conditions and the penetration, drop, compression, and lifting tests as discussed in WHC-SD-TP-SEP-020 (WHC 1994).

4.2.1 Containment Evaluation

The plywood box was subjected to testing for environmental conditions, penetration, drop, compression, and vibration analyses to assess the ability of the box to withstand the normal transfer conditions. With restrictions invoked by WHC-SD-TP-SEP-020 (WHC 1994) based on testing information, the plywood box containment for normal transfer conditions is acceptable. All appropriate restrictions invoked by WHC-SD-TP-SEP-020 (WHC 1994) have been followed by boxes PNLD-95-322 and PNLD-95-385.

4.3 ACCIDENT CONDITIONS

Accident conditions are evaluated Part B, Section 3.0, "Radiological Risk Evaluation." The accident release frequency is determined to be in the credible range at 5.6 E-06. The dose consequence results show that the doses are much lower than the required 0.05 Sv (5 rem) to the onsite worker and 0.05 mSv (500 mrem) to the public receptor. Therefore, the shipment poses no unacceptable risks due to accidents.

5.0 SHIELDING EVALUATION

The dose rates were measured for both boxes. The contact dose rate measurements are 100 mrem/h on the bottom, 12 mrem/h on the sides, and 1 mrem/h at 30 cm for box PNLD-95-322. For box PNLD-95-385, the maximum contact dose rate is 4 mrem/h and 1 mrem/h at 30 cm. These dose rates are below the U.S. Department of Transportation limits and are therefore acceptable.

6.0 STRUCTURAL EVALUATION

Follow the structural evaluation of WHC-SD-TP-SEP-020 (WHC 1994).

7.0 THERMAL EVALUATION

Follow the thermal evaluation of WHC-SD-TP-SEP-020 (WHC 1994).

8.0 PRESSURE AND GAS GENERATION

Follow the pressure and gas generation evaluation of WHC-SD-TP-SEP-020 (WHC 1994).

9.0 PACKAGE TIEDOWN SYSTEM

Follow the package tiedown system of WHC-SD-TP-SEP-020 (WHC 1994).

10.0 REFERENCES

- Green, J. R., B. D. Flanagan, and H. Harris, 1996, *Hanford Site Truck Accident Rate, 1990-1995*, WHC-SD-TP-RPT-021, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Mercado, J. E., 1994, *Report on Equivalent Safety for transportation and Packaging of Radioactive Materials*, WHC-SD-TP-RPT-001, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- WHC-CM-2-14, *Hazardous Material Packaging and Shipping*, Westinghouse Hanford Company, Richland, Washington.
- WHC, 1996, *Safety Analysis Report for Packaging (Onsite) Flexible Material Packaging*, WHC-SD-TP-SARP-007, Rev. 0-D, Westinghouse Hanford Company, Richland, Washington.
- WHC, 1994, *Safety Evaluation for Packaging (Onsite) Plywood Box*, WHC-SD-TP-SEP-020, Rev. 0-A, Westinghouse Hanford Company, Richland, Washington.

BEST AVAILABLE COPY

WASTE INVENTORY SHEET										Verify integrity of container	Signature	Page <u>1</u> of <u>1</u>											
Bldg. No.:	Room No.:	PIN:	Container type:	SOAR No.:	LLWSDA #:	Compatible/Yes No																	
3254	603	PKD-95-322	41418																				
Initial	Date	Article Description	Volume	Weight	Isotopes	Curie	Weight	I believe that the submitted information is true, accurate and complete and that this package does not contain hazardous or dangerous waste constituents as defined in WAC 173-303 and contains only materials compatible with compaction.															
CS	8/16	1-Bag 80% chalk 10% Rubber 5% Plastic 5% metal		50 lbs				Signature of Person Sealing Container Print Name: _____ Phone #: _____ Date: _____ Radiation Survey Information on Container Max Contact: [ ] <0.5 mrem/hr or _____ mrem/hr at 3'; [ ] 0.5 mrem/hr or _____ mR/hr Smearable Contamination: [ ] <2200 d/m/100 cm² BETA-GAMMA [ ] <220 d/m/100 cm² ALPHA Other: _____ Surveyed by: _____ Date: _____ VOLUME % COMPOSITION <table border="0"> <tr> <td>_____ % Paper</td> <td>_____ % Metal</td> </tr> <tr> <td>_____ % Rags</td> <td>_____ % Concrete</td> </tr> <tr> <td>_____ % Wood</td> <td>_____ % Glass</td> </tr> <tr> <td>_____ % Rubber</td> <td>_____ % Absorbent</td> </tr> <tr> <td>_____ % Plastic</td> <td>_____ % Animal</td> </tr> <tr> <td>_____ % _____</td> <td>_____ % Kortex</td> </tr> </table> (Specify)				_____ % Paper	_____ % Metal	_____ % Rags	_____ % Concrete	_____ % Wood	_____ % Glass	_____ % Rubber	_____ % Absorbent	_____ % Plastic	_____ % Animal	_____ % _____	_____ % Kortex
_____ % Paper	_____ % Metal																						
_____ % Rags	_____ % Concrete																						
_____ % Wood	_____ % Glass																						
_____ % Rubber	_____ % Absorbent																						
_____ % Plastic	_____ % Animal																						
_____ % _____	_____ % Kortex																						
CS	8/16	1-Bag 90% Plastic 10% chalk		50 lbs																			
CS	8/16	1-Bag 80% Rubber matching 10% Plastic		10 lbs																			
CS	8/16	1-Bag 70% Rubber cutting 30% Rubber 5% Plastic 5% metal		50 lbs																			
CS	8/16	2 bags Pz Filters		2 lbs																			
CS	8/16	4 bags angle iron, galvate		180 lbs																			
CS	8/16	5 bags rags and plastic		90 lbs																			
CS	8/16	2 bags metal hoses, pump		50 lbs																			
CS	8/16	4 bags tools		30 lbs																			
CS	8/16	2 bags soap pan scale		40 lbs																			
CS	8/16	6 bags Rags, Plastic, Rubber, glass, etc.		110 lbs																			
CS	8/16	2 bags Rags, Plastic, Rubber, etc.		90 lbs																			
CS	8/16	Misc. Cable, Conduct. Cable		10 lbs																			
CS	8/16	1-log of nut & bolts		2 lbs																			
CS	8/16	2 oil Resistor holders & tubing		8 lbs																			
CS	8/16	1 manip. boom		2 lbs																			
CS	8/16	3 - American & Misc. hardware		5 lbs																			
CS	8/16	4 BAGS CLOTH, PAST, CRABER, FIBERGLASS		220 lbs																			
CS	8/16	2 bags chalk, physical buffer		110 lbs																			
CS	8/16	1 BAG CLOTH PAST, RUBBER, ABSORBENT		20 lbs																			
TOTAL WEIGHT				1914																			

RECEIVED

SEP 09 1995

R.L. McDOWELL

Page 1 of 1

Total All Pages

MHC-SD-TP-SEP-052

Rev. 0

BEST AVAILABLE COPY

WASTE INVENTORY SHEET				Verify integrity of container		Signature		Page <u>1</u> of <u>1</u>	
Bldg. No.:	Room No.:	PIN:	Container type:	SOAR No.:	LLWSDR #:	Compatible Yes ☐ No ☐			
225A	603	PNC-95-385 15A	414X8						
Initial	Date	Article Description	Volume	Weight	Radioactive	Corrosive	Weight		
RA	9/4	1 BAG, GLOVES & PLASTIC		30					
		1 BAG, LIGHT RUBBER, SS METAL		20					
		RUBBER, WOOD		1					
		2 BAGS, CLOTH & PLASTIC		60					
		4 BAGS, RUBBER, PLASTIC, CLOTH		100					
DLB	9-16	5 BAGS plastic rubber cloth		100					
RA	9-9	4 BAGS PLASTIC RUBBER WITH METAL		150					
RA	9-15	2 BAGS Plastic, Rubber & Cloth & Knap Litter		65					
		1/2 SS Bull Valve, 3 Poly Lined Steel		5					
		Pump		45					
		2 bags 3 Absorbant		5					
CS	10-2	1 BAG, RUBBER, CLOTH, PLASTIC		15					
CS	10-6	Conduit, PANEL		100					
CS	10-6	TRANSPARENT-DRY		150					
CS	10-8	1 panel box, 1 panel cover		70					
CS	10-25	1 bag wire		20					
CS	10-25	Conduit pipes		10					
CS	10-30	Conduit pipes		40					
CS	10-30	Elect. panel, box, cover		100					
CS	10-30	8" half in vacuum valve, dial		5					
CS	10-30	1 bag nuts, fittings, rods		1					
RA	10-30	1 BAG TRASH, RAGS, GLOVES, SHIRTS		5					
RA	10-30	1/2" x 7/8" FMT		15					
RA	11-1	5 BAGS PLASTIC, CLOTH TAPE, RUBBER		100					
RA	11-2	3 BAGS MISC TRASH		200					
BC	11-6	4" wire strait plunger		15 lbs					
BC	11-6	Bag of 2nd hand electrical		5 lbs					
		Removed Wayne Pearson							

I believe that the submitted information is true, accurate and complete and that this package does not contain hazardous or dangerous waste constituents as defined in WAC 173-303 and contains only materials compatible with compaction.

Signature of Person Sealing Container _____

Print Name: _____
Phone #: _____
Date: _____

Radiation Survey Information on Container

Max Contact: [ ] <0.5 mrem/hr or _____ mrem/hr
at 3': [ ] 0.5 mrem/hr or _____ mR/hr

Seizable Contamination:
[ ] <2200 d/m/100 cm² BETA-GAMMA
[ ] <220 d/m/100 cm² ALPHA

Other: _____

Surveyed by: _____
Date: _____

VOLUME % COMPOSITION

15 % Paper	50 % Metal
15 % Rags	5 % Concrete
1 % Wood	1 % Glass
3 % Rubber	5 % Absorbent
25 % Plastic	5 % Animal
_____ % _____	_____ % Kotex
(Specify)	

Page Totals _____
Total All Pages _____

DISTRIBUTION SHEET

To	From	Page 1 of 1			
Distribution	Packaging Engineering	Date Sept. 25, 1996			
Project Title/Work Order		EDT No. 618182			
Safety Evaluation for Packaging for Two Plywood Boxes (WHC-SD-TP-SEP-052)		ECN No. N/A			
Name	MSIN	Text With All Attach.	Text Only	Attach./ Appendix Only	EDT/ECN Only
R. L. Clawson	G1-13	X			
B. D. Flanagan	G1-11	X			
J. G. Field	G1-11	X			
C. R. Hoover	G1-11	X			
W. B. Larson	P7-28	X			
D. W. McNally	G1-11	X			
M. J. Riess	P7-75	X			
Central Files	A3-88	X			
WHC-SD-TP-SEP-052 File	G1-11	X			