*Comparisons of Wilson-Fowler and Parametric
Cubic Splines with the Curve-Fitting
Algorithms of Several Computer-Aided
Design Systems*

Los Alamos
NATIONAL LABORATORY

*Los Alamos National Laboratory is operated by the University of California
for the United States Department of Energy under contract W-7405-ENG-36.*

Edited by Charmian Schaller, Weirich & Associates, for Group IM-1.

An Affirmative Action/Equal Opportunity Employer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither The Regents of the University of California, the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by The Regents of the University of California, the United States Government, or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of The Regents of the University of California, the United States Government, or any agency thereof. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

*Comparisons of Wilson-Fowler and Parametric
Cubic Splines with the Curve-Fitting
Algorithms of Several Computer-Aided
Design Systems*

*Wilbur D. Birchler
Scott A. Schilling*

Acknowledgements

The authors would like to express their thanks to all the individuals who contributed to this report. Some individuals provided data files, others contributed to the contents, and some provided moral support.

- ❑ Los Alamos National Laboratory, Los Alamos, New Mexico
 - Christopher J. Scully
 - Jacob S. Tafoya
 - Ronald M. Dolin
 - Richard M. Kieltyka
 - Stephen J. Levings
 - Bradley G. Baas
 - Scott D. Parkinson
 - Manuel A. Garcia
 - Edmund E. Kettering
 - Robert F. Montoya
 - Jody B. Niesen
 - Matthew L. Porter
 - Antonio R. Gonzales
 - Ronald V. Karpen
 - Bruce C. Trent
- ❑ Los Alamos National Laboratory, Los Alamos, New Mexico (Retired)
 - Donald Hall
- ❑ The Y-12 Plant, Oak Ridge, Tennessee
 - Bill D. Cain
- ❑ Rocky Flats Plant, Golden, Colorado (Retired)
 - Leroy Mellecker
- ❑ Atomic Weapons Establishment (AWE) Hunting-Brae
 - Andy Oughton, Reading, Berkshire, United Kingdom

Table of Contents

Acknowledgements	v
List of Figures	x
List of Tables	xi
Abstract.....	1
Summary.....	1
Conclusions.....	2
Introduction.....	2
Purpose of Study	2
Design, Inspection, and Fabrication Metrics.....	3
Splines.....	3
Wilson-Fowler Spline.....	3
Parametric Cubic Spline.....	5
Computer-Aided Design Systems.....	6
PTC CADD 5i.....	7
PTC Pro/E.....	7
PTC ICEM DDN.....	7
Evaluation Programs	8
Integrated Software Tools.....	8
Keyword Graphics Builder Program	8
Accuracy Study of Minimum-Distance Algorithms.....	9
Goals	9
Analytical Shapes: Circle, Ellipse, and Parabola.....	9
Spline Data.....	9
Analytical Circle Equations.....	10
Analytical Ellipse Equations	10
Analytical Parabolic Equations	10
Spline Data Set Parameters and Plots.....	11
Evaluation Data	14
Analytical Circle Equations.....	14
Analytical Ellipse Equations	14
Analytical Parabola Equations	15
Evaluation Data Set Parameters.....	15
Keyword Graphics Builder Program Command File.....	16
Analytical Circle.....	16
Deviation Plots.....	16
Maximum and Minimum Deviation Summary.....	24
Analytical Ellipse.....	25

Deviation Plots.....	25
Maximum and Minimum Deviations.....	32
Analytical Parabola.....	33
Deviation Plots.....	33
Maximum and Minimum Deviations.....	40
Conclusions.....	40
Deviations of Nonanalytical Shapes.....	41
Goals.....	41
Nonanalytical Shapes: Ellipse, Lampshade, and Weird Shape	41
Spline Data.....	41
Evaluation Data	44
Keyword Graphics Builder Program Command File.....	44
Nonanalytical Ellipse.....	44
Deviation Plots.....	44
Maximum and Minimum Deviations.....	52
Nonanalytical Lampshade.....	52
Deviation Plots.....	52
Maximum and Minimum Deviations.....	60
Nonanalytical Weird Shape.....	60
Deviation Plots.....	60
Maximum and Minimum Deviations.....	68
Conclusions.....	68
Effects of End Angles.....	69
Goal	69
Analytical Shapes, Circle, Ellipse, and Parabola.....	70
Spline Data.....	70
Evaluation Data Set Parameters.....	70
Keyword Graphics Builder Program Command File.....	70
Analytical Circle.....	71
Deviation Plots.....	71
Maximum and Minimum Deviations.....	76
Analytical Ellipse.....	76
Deviation Plots.....	76
Maximum and Minimum Deviations.....	82
Analytical Parabola.....	82
Deviation Plots.....	82
Maximum and Minimum Deviations.....	88
Conclusions.....	88
Summary and Conclusions.....	89
Appendix A—WFS Routines.....	91

Appendix B—PCS Routines	115
Appendix C—Minimum-Distance Routines.....	117
Appendix D—Analytical Spline-Point Data.....	123
Circle Spline-Point File.....	123
Ellipse Spline-Point File.....	124
Parabola Spline-Point File.....	124
Appendix E—Nonanalytical Spline-Point Data.....	127
Ellipse Spline-Point File.....	127
Lampshade Spline-Point File	128
Weird Shape Spline-Point File.....	128
Appendix F—Keyword Graphics Builder Program— Command Files	131
Analytical Shapes—Accuracy Study.....	131
Nonanalytical Shapes—Deviation Study	133
Analytical Shapes—End-Angle Effects.....	134
References.....	137

List of Figures

Figure 1.	Analytical Spline Data: Circle, Ellipse, and Parabola	13
Figure 2.	Analytical Circle: WFS, Deviations with 0.0000 mm Normal Offset.....	18
Figure 3.	Analytical Circle: PCS, Deviations with 0.0000 mm Normal Offset.....	19
Figure 4.	Analytical Circle: WFS, Deviations with +0.0254 mm Normal Offset.....	20
Figure 5.	Analytical Circle: PCS, Deviations with +0.0254 mm Normal Offset.....	21
Figure 6.	Analytical Circle: WFS, Deviations with -0.0254 mm Normal Offset.....	22
Figure 7.	Analytical Circle: PCS, Deviations with -0.0254 mm Normal Offset.....	23
Figure 8.	Analytical Ellipse: WFS, Deviations with 0.0000 mm Normal Offset.....	26
Figure 9.	Analytical Ellipse: PCS, Deviations with 0.0000 mm Normal Offset.....	27
Figure 10.	Analytical Ellipse: WFS, Deviations with +0.0254 mm Normal Offset.....	28
Figure 11.	Analytical Ellipse: PCS, Deviations with +0.0254 mm Normal Offset.....	29
Figure 12.	Analytical Ellipse: WFS, Deviations with -0.0254 mm Normal Offset.....	30
Figure 13.	Analytical Ellipse: PCS, Deviations with -0.0254 mm Normal Offset.....	31
Figure 14.	Analytical Parabola: WFS, Deviations with 0.0000 mm Normal Offset.....	34
Figure 15.	Analytical Parabola: PCS, Deviations with 0.0000 mm Normal Offset.....	35
Figure 16.	Analytical Parabola: WFS, Deviations with +0.0254 mm Normal Offset.....	36
Figure 17.	Analytical Parabola: PCS, Deviations with +0.0254 mm Normal Offset.....	37
Figure 18.	Analytical Parabola: WFS, Deviations with -0.0254 mm Normal Offset.....	38
Figure 19.	Analytical Parabola: PCS, Deviations with -0.0254 mm Normal Offset.....	39
Figure 20.	Nonanalytical Shapes: Ellipse, Lampshade, and Weird Shape.....	43
Figure 21.	Nonanalytical Ellipse: WFS, CADDs Deviations.....	46
Figure 22.	Nonanalytical Ellipse: PCS, CADDs Deviations.....	47
Figure 23.	Nonanalytical Ellipse: WFS, Pro/E Deviations.....	48
Figure 24.	Nonanalytical Ellipse: PCS, Pro/E Deviations.....	49
Figure 25.	Nonanalytical Ellipse: WFS, ICEM DDN Deviations.....	50
Figure 26.	Nonanalytical Ellipse: PCS, ICEM DDN Deviations.....	51
Figure 27.	Nonanalytical Lampshade: WFS, CADDs Deviations.....	54
Figure 28.	Nonanalytical Lampshade: PCS, CADDs Deviations.....	55
Figure 29.	Nonanalytical Lampshade: WFS, Pro/E Deviations.....	56
Figure 30.	Nonanalytical Lampshade: PCS, Pro/E Deviations.....	57
Figure 31.	Nonanalytical Lampshade: WFS, ICEM DDN Deviations.....	58
Figure 32.	Nonanalytical Lampshade: PCS, ICEM DDN Deviations.....	59
Figure 33.	Nonanalytical Weird Shape: WFS, CADDs Deviations.....	62
Figure 34.	Nonanalytical Weird Shape: PCS, CADDs Deviations.....	63
Figure 35.	Nonanalytical Weird Shape: WFS, Pro/E Deviations.....	64
Figure 36.	Nonanalytical Weird Shape: PCS, Pro/E Deviations.....	65
Figure 37.	Nonanalytical Weird Shape: WFS, ICEM DDN Deviations.....	66
Figure 38.	Nonanalytical Weird Shape: PCS, ICEM DDN Deviations.....	67
Figure 39.	Analytical Circle: WFS, Deviations with +0.25 Degree End Angles.....	72
Figure 40.	Analytical Circle: PCS, Deviations with +0.25 Degree End Angles.....	73
Figure 41.	Analytical Circle: WFS, Deviations with -0.25 Degree End Angles.....	74
Figure 42.	Analytical Circle: PCS, Deviations with -0.25 Degree End Angles.....	75
Figure 43.	Analytical Ellipse: WFS, Deviations with +0.25 Degree End Angles.....	78
Figure 44.	Analytical Ellipse: PCS, Deviations with +0.25 Degree End Angles.....	79
Figure 45.	Analytical Ellipse: WFS, Deviations with -0.25 Degree End Angles.....	80
Figure 46.	Analytical Ellipse: PCS, Deviations with -0.25 Degree End Angles.....	81
Figure 47.	Analytical Parabola: WFS, Deviations with +0.25 Degree End Angles.....	84
Figure 48.	Analytical Parabola: PCS, Deviations with +0.25 Degree End Angles.....	85
Figure 49.	Analytical Parabola: WFS, Deviations with -0.25 Degree End Angles.....	86
Figure 50.	Analytical Parabola: PCS, Deviations with -0.25 Degree End Angles.....	87

List of Tables

Table 1.	Analytical Shapes: Spline Data Set Parameters	11
Table 2.	Analytical Shapes: Evaluation Data Set Parameters.....	16
Table 3.	Analytical Circle: Summary of Deviations.....	24
Table 4.	Analytical Ellipse: Summary of Deviations.....	32
Table 5.	Analytical Parabola: Summary of Deviations.....	40
Table 6.	CAD System Spline Types and End-Angle Options	41
Table 7.	Nonanalytical Spline Parameters	42
Table 8.	Nonanalytical Shapes: Evaluation Data Parameters	44
Table 9.	Nonanalytical Ellipse: Summary of Deviations.....	52
Table 10.	Nonanalytical Lampshade: Summary of Deviations.....	60
Table 11.	Nonanalytical Weird Shape, Summary of Deviations.....	68
Table 12.	Analytical Spline Parameters	70
Table 13.	Evaluation Data Set Parameters.....	70
Table 14.	Analytical Circle: Deviations with Modified End Angles.....	76
Table 15.	Analytical Ellipse: Deviations with Modified End Angles	82
Table 16.	Analytical Parabola: Deviations with Modified End Angles	88

Comparisons of Wilson-Fowler and Parametric Cubic Splines with the Curve-Fitting Algorithms of Several Computer-Aided Design Systems

by

Wilbur D. Birchler

and

Scott A. Schilling

Abstract

Summary

The purpose of this report is to demonstrate that modern computer-aided design (CAD), computer-aided manufacturing (CAM), and computer-aided engineering (CAE) systems can be used in the Department of Energy (DOE) Nuclear Weapons Complex (NWC) to design new and remodel old products, fabricate old and new parts, and reproduce legacy data within the inspection uncertainty limits. In this study, two two-dimensional splines are compared with several modern CAD curve-fitting modeling algorithms. The first curve-fitting algorithm is called the Wilson-Fowler Spline (WFS), and the second is called a parametric cubic spline (PCS). Modern CAD systems usually utilize either parametric cubic and/or B-splines.

Three studies are presented in this report. The first study shows that the accuracy of the minimum-distance algorithm and the ability of both the WFS and PCS to represent analytical data sets (circle, ellipse, and parabola) are well within the inspection uncertainty. A ratio of the calculated deviation to the inspection uncertainty is the metric used in this report. If this ratio is less than one, then the models can be used to design, inspect, and fabricate the parts. Of the 18 numerical analyses presented, the largest ratio of calculated deviation to inspection uncertainty is 0.1489. This ratio is associated with the parabola and is located at the point of highest curvature. The signs of the deviations are shown to be correct. The conclusion from this study is that both the WFS and the PCS can be used to reproduce legacy data and to design new products and redesign old ones.

The second study evaluates three CAD systems—the Parametric Technology, Inc. (PTC) Pro/ENGINEER (Pro/E) system; the Control Data Corporation (CDC) Integrated Computer Engineering and Manufacturing Design, Drafting, and Numerical Control (ICEM DDN) system; and the Computervision Computer-Aided Design and Drafting System (CADDs). It demonstrates their capabilities to model DOE legacy data, and determines that they can be utilized to develop future models. Three nonanalytical shapes (ellipse, lampshade, and a weird shape) are evaluated with the three CAD systems. Of the 18 numerical analyses presented, the largest ratio of calculated deviation to inspection uncertainty is 0.6552. This ratio is associated with the weird-shape curve and is located at the point of high curvature.

This study indicates that all three CAD systems can be used to design, inspect, and fabricate parts from both legacy data and new solid-based models.

The third study establishes upper bounds on the variation of the end angles used to define the geometry of analytical shapes (circle, ellipse, and parabola) and still remain within the inspection uncertainty. When the end angles vary as much as 0.25 degree from the nominal values, the resultant deviations are still within the inspection uncertainty. End-angle effects are very local and damp out in the fourth or fifth segments of the spline data. The conclusion of this study is that if the end angles are within about 0.25 degree, the solid-based models still can be used to design, inspect, and fabricate parts.

Conclusions

The conclusion of this study is that any CAD system that supports either PCS or B-spline can be used to reproduce DOE legacy data and to design, inspect, and fabricate parts with confidence. The NWC should move on to these modern CAD systems, knowing that the legacy data generated by the WFS algorithm can be reproduced well within the inspection uncertainty limit.

Introduction

In the NWC, the models-based engineering (MBE) approach has been introduced to design, inspection, and fabrication operations. MBE is based upon a series of commercially available CAD, CAM, and CAE software packages. The DOE NWC selected the PTC Pro/E family of software packages as its de facto standard.

Many questions about the capabilities and accuracy of a software system must be addressed before it can be utilized in the design, inspection, and production environments. Following are some of the major issues associated with changing or introducing a new CAD system into a facility:

- ❑ How well do these CAD systems meet DOE's needs and requirements?
- ❑ How explicitly and precisely is geometry represented?
- ❑ How easily can geometry be extracted from the data bases?
- ❑ How tedious is the learning curve?
- ❑ What changes were made to the algorithms from previous versions?
- ❑ How well does the new product reproduce the results of past versions?
- ❑ What accuracy can be expected from the CAD system algorithms?
- ❑ How well do the CAD systems replicate the legacy data previously used in the DOE NWC?

The question addressed in this report is how well the CAD system replicates the legacy data previously used in the DOE NWC. Specifically, the interest is in the two-dimensional spline curve-fitting routines. DOE has utilized a curve-fitting routine referred to as the WFS for several years (late 1960 to 1998); whereas, the modern CAD systems usually use either parametric cubic and/or B-splines.

Purpose of Study

The purpose of this study is to establish whether the NWC-selected CAD system as delivered (PTC Pro/E) has the capability to replicate the DOE legacy data to the required accuracy. If the selected CAD system meets the accuracy requirements, then it can be used to reproduce legacy

data. In addition, it can be deployed with confidence to produce future models with at least the same fidelity as the legacy data. A numerical approach is utilized in this study to determine how well the CAD data replicate the legacy data.

Design, Inspection, and Fabrication Metrics

In order to evaluate the selected CAD system, we established metrics on the design uncertainty, inspection uncertainty, and the fabrication uncertainty. The definitions of these uncertainties are as follows:

❑ Design uncertainty	0.000254 mm (0.00001 in)
❑ Inspection uncertainty	0.00254 mm (0.0001 in)
❑ Fabrication uncertainty	0.0254 mm (0.001 in)

What is important is whether the differences in accuracy among the several CAD systems can be detected through the inspection processes. If the differences cannot be measured, then the models developed with the CAD systems are adequate. The results of numerical experiments presented in the following sections are compared to the inspection uncertainty. A ratio of the calculated deviation to the inspection uncertainty is the metric used in this report. If this ratio is less than one, then the models can be used to design, inspect, and fabricate the parts.

Splines

Splines are mathematical representations of a series of points. They are used to interpolate values at intermediate locations. There are many types of two-dimensional splines. They include the following:

- ❑ Linear splines
- ❑ Classic cubic splines
- ❑ Wilson-Fowler cubic splines
- ❑ Parametric cubic splines
- ❑ B-splines

Several restrictions are placed on the data sets, which are used to build the mathematical models. The points must be in increasing order, and the end slopes must be known. The bounds set on the formulation of the splines are that the mathematical representation must be continuous in position and smooth in slope. The model also must capture the input data points exactly.

In this study, historically used splines are compared with several modern CAD curve-fitting modeling algorithms. The first curve-fitting algorithm is called the WFS,¹ and the second is called a PCS.² These splines are presented in the next two sections.

Wilson-Fowler Spline

The WFS was developed at the DOE Oak Ridge Plant in Tennessee in the early 1960s. It is a cubic spline in the local two-dimensional u - v coordinate system with the chord length as the independent parameter, u . Additional references are available for this spline.^{3 and 4}

The mathematical representation of one segment of the WFS in local u - v space is summarized below. The nomenclature is very similar to that used in Ref. 3. Equation (1) defines the WFS in the local u - v space.

$$v(u) = C_1 u^3 + C_2 u^2 + C_3 u + C_4 \quad (1)$$

where $0 \leq u \leq L$,

$$C_1 = \frac{TA + TB}{L^2},$$

$$C_2 = \frac{-(2TA + TB)}{L},$$

$$C_3 = TA,$$

and $C_4 = 0$.

Also, TA = entry slope—measured from the chord,

TB = exit slope—measured from the chord,

and $L = \sqrt{(X_B - X_A)^2 + (Y_B - Y_A)^2}$, chord length.

The total spline consists of a series (number of spline points minus one) of these cubic segments. A curvature-matching technique is utilized to ensure that the spline is continuous in position, slope, and curvature. Both Ref. 1 and Ref. 3 describe the curvature-matching technique in great detail.

If the WFS is to be utilized in an efficient manner, it must be transformed in the global x - y coordinate system. The transformation equations are listed below. The nomenclature is very similar to that used in Ref. 3.

The global value of x as a function of the u is defined in Equation (2).

$$x(u) = A_x u^3 + B_x u^2 + C_x u + D_x \quad (2)$$

where $A_x = -C_1 \sin \gamma$,

$$B_x = C_2 \sin \gamma,$$

$$C_x = \cos \gamma - C_3 \sin \gamma,$$

and $D_x = X_A$.

The global value of y as a function of u is defined in Equation (3).

$$y(u) = A_y u^3 + B_y u^2 + C_y u + D_y \quad (3)$$

where $A_y = C_1 \cos \gamma$,

$$B_y = C_2 \cos \gamma,$$

$$C_y = C_3 \cos \gamma + \sin \gamma,$$

and $D_y = Y_A.$

The end points of the segment are defined below.

Where γ = chord angle—measured from the global x-axis,

$$\gamma = \tan^{-1} \frac{Y_B - Y_A}{X_B - X_A},$$

X_A, Y_A = beginning chord point,

and X_B, Y_B = ending chord point.

The total spline consists of a series (number of spline points minus one) of these cubic segment pairs.

A complete listing of the FORTRAN source code used to calculate the segment coefficients is given in Appendix A—WFS Routines.

Parametric Cubic Spline

The PCS presented here is smooth in the first derivative and continuous in the second derivative, both within the segment and at the spline points. Ref. 2 gives a complete derivation of the PCS.

The global value of x as a function of t (chord length) is defined in Equation (4).

$$x(t) = A_x t^3 + B_x t^2 + C_x t + D_x \quad (4)$$

where $0 \leq t \leq L,$

$$A_x = \frac{X''(L) - X''(0)}{6L},$$

$$B_x = \frac{X''(0)}{2},$$

$$C_x = \frac{X_B - X_A}{L} - \frac{L}{6}(2X''(0) + X''(L)),$$

and $D_x = X_A.$

Also, $X''(0)$ = value of the second derivative at the beginning of the segment,

and $X''(L)$ = value of the second derivative at the ending of the segment.

The global value of y as a function of t (chord length) is defined in Equation (5).

$$y(t) = A_y t^3 + B_y t^2 + C_y t + D_y \quad (5)$$

where $A_y = \frac{Y''(L) - Y''(0)}{6L},$

$$B_y = \frac{Y''(0)}{2},$$

$$C_y = \frac{Y_B - Y_A}{L} - \frac{L}{6}(2Y''(0) + Y''(L)),$$

and $D_y = Y_A.$

Also, $Y''(0)$ = value of the second derivative at the beginning of the segment,

and $Y''(L)$ = value of the second derivative at the ending of the segment.

The end points of the segment are defined below.

Where X_A, Y_A = beginning chord point,

X_B, Y_B = ending chord point,

and $L = \sqrt{(X_B - X_A)^2 + (Y_B - Y_A)^2}$, chord length.

The total spline consists of a series (number of spline points minus one) of these cubic segment pairs.

A complete listing of the FORTRAN source code used to calculate the segment coefficients is given in Appendix B—PCS Routines.

Computer-Aided Design Systems

The DOE national laboratories have been working with CAD, CAM, and CAE tools since the early 1980s. Many of the original CAD tools were designed using a kernel written by Patrick J. Hantatty.⁵ These tools were primarily electronic drafting boards. As the CAD systems matured, the next functionality developed was to integrate the manufacturing and machine control using CAM. CADDs was one of the early codes that went through this growth cycle. The tools and computers on which to run them were very expensive. Very few companies were able to afford them. The DOE national laboratories, Boeing, General Motors, and NASA were the type of organizations that purchased these early CAD/CAM tools. In the late 1980s and early 1990s, CAD companies started to develop three-dimensional modeling tools. A few new companies focusing on designing three-dimensional solid models were established. These tools were intended to be used by engineers to design and visualize the products in three dimensions. A solid model could be shaded and spun so that it was visible from any direction. Because the computer program could detect what was material and what was not, the mass properties of the three-dimensional components could be calculated very easily. Pro/E from Parametric Technology is one of these systems.

The nuclear weapons program in the United Kingdom uses Computervision CADDs as its CAD/CAM/CAE tool. The United States DOE NWC uses Pro/E as a de facto standard. Both tools are competitive in the global CAD/CAM/CAE market and are capable of doing all the design and

manufacturing work for complex design. One difference between the two companies is the way they compute complex curves and surfaces. Computervision CADD5 responded to a request from the NWC in the early 1980s and used the WFS algorithm that was derived by the DOE to define complex curves. Pro/E used industry-standard PCS and B-spline algorithms in its code. CDC's ICEM DDN system was also utilized in the NWC. This CAD system was used at the Rocky Flats Plant in the 1980s and early 1990s to manufacture many of the NWC parts.

Several CAD systems are and have been used in the DOE NWC. The three that are of interest in this study are the Computervision CADD5 system, the Pro/E system, and the ICEM DDN system. Below are introductory statements drawn from the CAD/CAM/CAE companies' web pages.

(The legacy data and manufacturing models of interest in this report were developed on earlier versions of these codes. In 1998, PTC purchased Computervision's CADD5 and CDC's ICEM DDN systems. For that reason the CAD systems listed below, taken from PTC's Web site, have different names.)

PTC CADD5 5i

CADD5 5i is the current release of the PTC product. It is a fully functional CAD/CAM/CAE system able to create complex geometry. The tool has integrated manufacturing and communication tools to allow many users to work on the same models. CADD5 software predated the parametric modeling concepts. This system is able to model without connecting dimensions and features. To alter designs, one must explicitly remodel the geometry. The system is also capable of modeling in parametric form such that one can modify a dimension and the part will redefine the geometry based on the new dimension. Because of the evolutionary changes of this CAD system, it can create wire-frame, surface, or solid-model geometry for the three-dimensional design of any component.

PTC Pro/E

Pro/E is a fully functional, parametric, three-dimensional, solid-modeling system. This CAD system started in the 1980s and was focused on parametric design with three-dimensional solid modeling from its inception. Pro/E is integrated with its manufacturing, inspection, and analysis packages. Information does not need to be transferred or translated to work in any of the packages. Pro/E uses parametric design for all geometry creation. When geometry is created, its dimensions parametrically drive the model. The documentation of the solid model is a two-dimensional drawing that is associated with the three-dimensional solid model. Dimensions can be modified in any location and will be updated in the model and drawing. The geometry of the model is also recalculated and redisplayed.

PTC ICEM DDN

CDC's ICEM, now a subsidiary of PTC, provides vital advanced styling and surfacing technology and expertise to major automotive- and consumer-product manufacturers. Established in the early 1980s, ICEM Technologies joined PTC in June 1998 as the ICEM Surfacing Center of Excellence. ICEM DDN is a fully functional CAD/CAM/CAE software. ICEM DDN started in the 1970s as a two-dimensional system to perform electronic drafting. This system, like Computervision, has evolved over the last 30 years, expanding from two-dimensional drafting into wire-frame, surface, and solid modeling. ICEM DDN has also developed the manufacturing tools to do CAM work. As in Pro/E, the design and manufacturing are integrated, and the users are able to work in either

package without transfer or translation of the data. The ICEM DDN system utilizes a version of the WFS algorithm.

Evaluation Programs

We used two analysis programs in this study—WX-Division Integrated Software Tools, and Keyword Graphics Builder Program. Descriptions of these programs are presented in the following sections.

Integrated Software Tools

This study began by using the WX-Division Integrated Software Tools⁶ (WIST) developed at Los Alamos National Laboratory (LANL). The WIST capabilities included the ability to rotate, mirror, and translate spline data; to calculate data normal to curves; to determine the minimum distance of data points from the spline representation of the data; and to calculate the WFS coefficients from the spline points. A graphics package was not available in WIST.

A peer review of WIST was performed. The WFS algorithms were reviewed. Minor changes were made to the source code. These changes were limited to making all the variables double precision, changing the convergence tolerances, and increasing the number of loops in the iteration algorithms. All the changes made to the source code were provided with comment blocks that started and ended with “Cwb” (which stands for “Comment by Wilbur Birchler”).

In addition, the minimum-distance algorithm was reviewed. A searching technique was utilized to determine which segment encompassed the data point. Problems arose when the data point was past the ends of the spline. No warnings were issued by the program. In addition, this technique would sometimes select the wrong segment. The approach used was very computationally intensive.

Because of the peer review and after evaluating many test cases, we concluded that only the coefficient generation part of the WIST software package should be used in this study. The FORTRAN source code is listed in Appendix A—WFS Routines.

Keyword Graphics Builder Program

After performing many analyses, going over the peer reviews, and determining that WIST had no graphics capabilities, we decided to use the Keyword Graphics Builder Program⁷ (KGB) to evaluate the CAD systems. KGB was developed at LANL, already had graphics options, and had many analysis capabilities. This software is written in several modules, and it is very easy to add new capabilities as needed. The program’s capabilities include standard mathematical operations such as adding, subtracting, multiplying, dividing, integrating, and differentiating two-dimensional data sets. Other data operations available are maximum/minimum value reporting, data chopping, data smoothing, data extrapolating, data merging, data scaling, data mirroring, and data translating. An excellent report-graphics package and presentation-quality graphics are major parts of this software.

KGB is a command-line-driven program. Commands can be entered interactively and/or from a command file. The Help File is on line and has several levels of detail. It utilizes an extensive Label File for graphics, for tracking units, for converting between units, and for assuring that all the operations are consistent. This software has excellent error-trapping and error-warning capabilities.

This program had a complete set of data-fitting algorithms before the WFS module (Appendix A—WFS Routines) from WIST was added. PCS capability was added to allow for direct comparisons with the WFS algorithms. The relevant FORTRAN software is listed in Appendix B—PCS Routines.

A new minimum-distance algorithm was developed and programmed. This new algorithm is an iterative solution based on the fact that the minimum distance of a point from a curve is normal to the curve. The FORTRAN software we used is listed in Appendix C—Minimum-Distance Routines.

Accuracy Study of Minimum-Distance Algorithms

The first step in evaluating CAD systems is to ensure that the selected evaluation (KGB, in this case) is accurate and correct. We took a numerical approach to this step, selecting and evaluating three analytical shapes. The results of this evaluation are presented in the following sections.

Goals

The goals of this study were to establish the accuracy of the minimum-distance software and to demonstrate that the directions of the deviations were correct.

Analytical Shapes: Circle, Ellipse, and Parabola

Three analytical shapes were utilized to determine how well the minimum-distance algorithm worked. These analytical shapes were a circle, an ellipse, and a parabola. The spline data and the evaluation data were generated with Mathcad.⁸ Equations were written for each shape. We generated spline data every two degrees from the x-axis to the y-axis. The spline data points are listed in Appendix D—Analytical Spline-Point Data. All data were rounded to six digits past the decimal point.

The procedure used to evaluate the minimum-distance algorithm was as follows:

- ❑ Generate the mathematical representations of the spline points for both WFS and PCS
- ❑ Generate three sets of evaluation data for each shape
- ❑ Develop Data Set 1—exact data on the curves
- ❑ Develop Data Set 2—exact data offset normal to the base curves by a positive value (increased radius)
- ❑ Develop Data Set 3—exact data offset normal to the base curves by a negative value (decreased radius)
- ❑ Calculate the minimum distances of the exact data from the mathematical representation results
- ❑ Summarize the results
- ❑ Compare the results

Spline Data

Three analytical shapes were utilized to establish the accuracy of the minimum-distance algorithm. These analytical shapes were a circle, an ellipse, and a parabola. The equations used to generate the spline data were programmed in Mathcad and are listed in the following three sections.

Analytical Circle Equations

The global x and y values as a function of θ are defined by Equation (6) and Equation (7), respectively.

$$x_k = R_0 \cos(\theta_k) \quad (6)$$

and

$$y_k = R_0 \sin(\theta_k) \quad (7)$$

$$\text{where} \quad \theta_k = \frac{\pi}{180.0} 2k,$$

$$k = 0, 1; 45,$$

$$\text{and} \quad R_0 = 100 \text{ mm.}$$

Analytical Ellipse Equations

The global x and y values as a function of β are defined by Equation (8) and Equation (9), respectively.

$$x_k = a_0 \cos(\beta_k) \quad (8)$$

and

$$y_k = b_0 \sin(\beta_k) \quad (9)$$

$$\text{Where} \quad \beta_k = \tan^{-1} \left[\frac{a_0 \sin(\theta_k)}{b_0 \cos(\theta_k)} \right],$$

$$\theta_k = \frac{\pi}{180.0} 2k,$$

$$k = 0, 1; 45,$$

$$a_0 = 100 \text{ mm},$$

$$\text{and} \quad b_0 = 80 \text{ mm.}$$

Analytical Parabolic Equations

The global x and y values as a function of θ are defined by Equation (10) and Equation (11), respectively.

$$x_k = \left[\frac{\cot(\theta_k) + \sqrt{\cot^2(\theta_k) - 4d}}{2c} \right] \cot(\theta_k) \quad (10)$$

and

$$y_k = \frac{\cot(\theta_k) + \sqrt{\cot^2(\theta_k) - 4d}}{2c} \quad (11)$$

where $\theta_k = \frac{\pi}{180.0} 2k,$

$$k = 0, 1, 45,$$

$$c = \frac{-x_p}{y_e^2},$$

$$d = x_p,$$

$$x_p = 100\text{mm},$$

and $y_e = 60\text{mm}.$

Spline Data Set Parameters and Plots

Table 1 lists the spline data set parameters of these analytical shapes. The number of points, point spacing, number of digits past the decimal point, and the end angles are summarized.

Table 1. Analytical Shapes: Spline Data Set Parameters

Analytical Spline	Number of Points	Spacing of Points (Degrees)	Digits Past Decimal Point	Beginning End-Angle (Degrees)	Ending End-Angle (Degrees)
Circle	46	2.0	6	90.0	180.0000
Ellipse	46	2.0	6	90.0	180.0000
Parabola	46	2.0	6	90.0	163.3008

These three analytical shapes are shown in Figure 1. The naming conventions for files are as follows:

- First field—shape
 - Circle
 - Ellipse
 - Parabola
- Second field—normal offset direction
 - _n—no normal offset
 - _p—plus normal offset (increasing radius)
 - _m—minus normal offset (decreasing radius)

- Third field—type of file
 - .spn—spline points
 - .pts—evaluation points

Figure 1 shows the three spline curves. The solid red curve is the analytical circle. The analytical ellipse is shown as the small-dash black curve. The large-dash green curve is the analytical parabola.

Figure 1. Analytical Spline Data: Circle, Ellipse, and Parabola

Evaluation Data

In order to evaluate the accuracy of the minimum-distance software, three “exact” data sets were generated for each of the analytical shapes. The first data set has a normal offset of 0.0000 mm. The second and third data sets have normal offsets of +0.0254 mm and −0.0254 mm. The equations used to generate the evaluation data are listed in the following three sections. Mathcad was used to generate all the evaluation points.

Analytical Circle Equations

The global x and y values as a function of θ are defined by Equation (12) and Equation (13), respectively.

$$x_j = (R_0 \pm \Delta) \cos(\theta_j) \quad (12)$$

and

$$y_j = (R_0 \pm \Delta) \sin(\theta_j) \quad (13)$$

$$\text{where} \quad \theta_j = \frac{\pi}{180.0} 0.25j,$$

$$j = 0, 1, 360,$$

$$R_0 = 100,$$

$$\text{and} \quad \Delta = 0.0254 \text{ mm}.$$

Analytical Ellipse Equations

The global x and y values as a function β are defined by Equation 14 and Equation 15, respectively.

$$x_j = a_o \cos(\beta_j) \pm \frac{\Delta \cos(\beta_j)}{\sqrt{(a_o \sin(\beta_j))^2 + (b_o \cos(\beta_j))^2}} \quad (14)$$

and

$$y_j = b_o \sin(\beta_j) \pm \frac{\Delta \sin(\beta_j)}{\sqrt{(a_o \sin(\beta_j))^2 + (b_o \cos(\beta_j))^2}} \quad (15)$$

$$\text{where} \quad \beta_j = \tan^{-1} \left[\frac{a_o \sin(\theta_j)}{b_o \cos(\theta_j)} \right],$$

$$\theta_j = \frac{\pi}{180.0} 0.25j,$$

$$j = 0,1;360,$$

$$a_o = 100\text{mm},$$

$$b_o = 80\text{mm},$$

$$\text{and} \quad \Delta = 0.0254\text{mm}.$$

Analytical Parabola Equations

The global x and y values as a function of θ are defined by Equation (16) and Equation (17), respectively.

$$x_j = \left[\frac{\cot(\theta_j) + \sqrt{\cot^2(\theta_j) - 4d}}{2c} \right] \cot(\theta_j) \pm \Delta \cos(\zeta_j) \quad (16)$$

and

$$y_j = \frac{\cot(\theta_j) + \sqrt{\cot^2(\theta_j) - 4d}}{2c} \pm \Delta \sin(\zeta_j) \quad (17)$$

$$\text{where} \quad \zeta_j = \frac{\pi}{2} - \tan^{-1} \left(\frac{-1}{\cot(\theta_j) + \sqrt{\cot^2(\theta_j) - 4d}} \right),$$

$$j = 0,1;360,$$

$$c = \frac{-x_p}{y_e^2},$$

$$d = x_p,$$

$$x_p = 100\text{mm},$$

$$y_e = 60\text{mm},$$

$$\text{and} \quad \Delta = 0.0254\text{mm}.$$

Evaluation Data Set Parameters

Table 2 lists the parameters of these analytical shapes. The number of points, point spacing, number of digits past the decimal point, and the normal offsets are summarized. Evaluation numbers were generated every 0.25 degree, using the equations listed in the above three sections.

Table 2. Analytical Shapes: Evaluation Data Set Parameters

Analytical Spline	Number of Points	Spacing of Points (Degree)	Digits Past Decimal Point	Normal Offset (mm)
Circle	361	0.25	6	0.0
Circle	361	0.25	6	+0.0254
Circle	361	0.25	6	-0.0254
Ellipse	361	0.25	6	0.0
Ellipse	361	0.25	6	+0.0254
Ellipse	361	0.25	6	-0.0254
Parabola	361	0.25	6	0.0
Parabola	361	0.25	6	+0.0254
Parabola	361	0.25	6	-0.0254

Keyword Graphics Builder Program Command File

The command files utilized to perform the following calculations are listed in Appendix F—Keyword Graphics Builder Program—Command files—Analytical Shapes—Accuracy Study.

Analytical Circle

The next six figures show the comparisons of WFS and PCS representations with the exact analytical circle data generated by Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the fabrication uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 1,000.

Deviation Plots

Figure 2 is a graph of the analytical circle modeled with the WFS algorithm. The normal offset is 0.0000 mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.0613\text{e-}6$ mm.

Figure 3 is a graph of the analytical circle modeled with the PCS algorithm. The normal offset is 0.0000 mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $1.3075\text{e-}6$ mm.

Figure 4 is a graph of the analytical circle modeled with the WFS algorithm. The normal offset is +0.0254 mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5401\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 5 is a graph of the analytical circle modeled with the PCS algorithm. The normal offset is $+0.0254$ mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5401\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 6 is a graph of the analytical circle modeled with the WFS algorithm. The normal offset is -0.0254 mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5402\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 7 is a graph of the analytical circle modeled with the PCS algorithm. The normal offset is -0.0254 mm. Mathcad was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5401\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 2. Analytical Circle: WFS, Deviations with 0.0000 mm Normal Offset

Figure 3. Analytical Circle: PCS, Deviations with 0.0000 mm Normal Offset

Figure 4. Analytical Circle: WFS, Deviations with +0.0254 mm Normal Offset

Figure 5. Analytical Circle: PCS, Deviations with +0.0254 mm Normal Offset

Figure 6. Analytical Circle: WFS, Deviations with -0.0254 mm Normal Offset

Figure 7. Analytical Circle: PCS, Deviations with -0.0254 mm Normal Offset

Maximum and Minimum Deviation Summary

Table 3 is a summary of the maximum and minimum deviations for the analytical circle. Column 1 lists the associated figure in this document that displays the results. The second column lists the type of evaluation spline. Columns 3 and 4 are the maximum and minimum deviations with the normal offset included. The fifth column gives the normal offset values. Columns 6 and 7 are the deviations with the normal offsets removed.

Table 3. Analytical Circle: Summary of Deviations

Figure	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)	Normal Offset (mm)	Maximum Deviation with Offset Removed (mm)	Minimum Deviation with Offset Removed (mm)
Figure 2	WFS	+5.980261e-7	-2.061326e-6	+0.0000	+5.980261e-7	-2.061326e-6
Figure 3	PCS	+1.307488e-6	-9.389013e-7	+0.0000	+1.307488e-6	-9.389013e-7
Figure 4	WFS	+2.540065e-2	+2.539813e-2	+0.0254	+6.500000e-7	-1.870000e-6
Figure 5	PCS	+2.540140e-2	+2.539915e-2	+0.0254	+1.400000e-6	-8.500000e-7
Figure 6	WFS	-2.539907e-2	-2.540206e-2	-0.0254	+9.300000e-7	-2.060000e-6
Figure 7	PCS	-2.539966e-2	-2.540083e-2	-0.0254	+3.400000e-7	-8.300000e-7

A review of columns 6 and 7 of Table 3 shows that the absolute largest deviation is associated with the WFS algorithm and has a value of 2.061326e-6 mm (Figure 2). The ratio of the calculated deviation to the inspection uncertainty is 8.115e-4.

In column 6 of Table 3, Maximum Deviation with Offset Removed, the WFS deviations range from +5.9++e-7 mm to +9.3++e-7 mm. Similarly, the PCS deviations range from +3.4++e-7 mm to +1.4++e-6 mm. The WFS model yields slightly better results than the PCS model for maximum deviations.

In column 7 of Table 3, Minimum Deviation with Offset Removed, the WFS deviations are almost identical and have values of -2.0++e-6 mm. Similarly, the PCS deviations are almost identical with values of -8.5++e-7 mm. The WFS model yields slightly poorer results than the PCS model for minimum deviations.

The results shown in columns 6 and 7 of Table 3 indicated that a minimum accuracy of about five and three-quarters digits past the decimal point could be expected for an analytical circle. In general, the accuracy of these splines is the number of digits past the decimal point minus one-quarter digit.

In column 6 of Table 3, Maximum Deviation with Offset Removed (mm), the WFS deviations are about an order of magnitude better than the PCS deviations. However, the deviations listed in column 7 of the same table, Minimum Deviation with Offset Removed (mm), show the opposite results.

The results of these analyses show that the WFS and PCS produce results that meet all of DOE's MBE requirements.

A review of the six figures listed in Table 3 shows that the minimum-distance algorithm produces the proper sign on the deviations.

Analytical Ellipse

The next six figures show the comparisons of WFS and PCS representations with the exact analytical ellipse data generated by Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the fabrication uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 1,000.

Deviation Plots

Figure 8 is a graph of the analytical ellipse modeled with the WFS algorithm. The normal offset is 0.0000 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $3.4457\text{e-}6$ mm.

Figure 9 is a graph of the analytical ellipse modeled with the PCS algorithm. The normal offset is 0.0000 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $4.4447\text{e-}6$ mm.

Figure 10 is a graph of the analytical ellipse modeled with the WFS algorithm. The normal offset is +0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5401\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 11 is a graph of the analytical ellipse modeled with the PCS algorithm. The normal offset is +0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5405\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 12 is a graph of the analytical ellipse modeled with the WFS algorithm. The normal offset is -0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5403\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 13 is a graph of the analytical ellipse modeled with the PCS algorithm. The normal offset is -0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5401\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 8. Analytical Ellipse: WFS, Deviations with 0.0000 mm Normal Offset

Figure 9. Analytical Ellipse: PCS, Deviations with 0.0000 mm Normal Offset

Figure 10. Analytical Ellipse: WFS, Deviations with +0.0254 mm Normal Offset

Figure 11. Analytical Ellipse: PCS, Deviations with +0.0254 mm Normal Offset

Figure 12. Analytical Ellipse: WFS, Deviations with -0.0254 mm Normal Offset

Figure 13. Analytical Ellipse: PCS, Deviations with -0.0254 mm Normal Offset

Maximum and Minimum Deviations

Table 4 is a summary of the maximum and minimum deviations for the analytical ellipse. Column 1 lists the associated figure that displays the results. The second column lists the type of evaluation spline. Columns 3 and 4 are the maximum and minimum deviations with the normal offset included. The fifth column gives the normal offset values. Columns 6 and 7 are the deviations with the offsets removed.

Table 4. Analytical Ellipse: Summary of Deviations

Figure	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)	Normal Offset (mm)	Maximum Deviation with Offset Removed (mm)	Minimum Deviation with Offset Removed (mm)
Figure 8	WFS	+4.916562e-7	-3.445712e-6	+0.0000	+4.916562e-7	-3.445712e-6
Figure 9	PCS	+4.444657e-6	-8.693426e-7	+0.0000	+4.444657e-6	-8.693426e-7
Figure 10	WFS	+2.540087e-2	+2.539657e-2	+0.0254	+8.700000e-7	-3.430000e-6
Figure 11	PCS	+2.540481e-2	+2.539896e-2	+0.0254	+4.810000e-6	-1.040000e-6
Figure 12	WFS	-2.539895e-2	-2.540339e-2	-0.0254	+1.050000e-6	-3.390000e-6
Figure 13	PCS	-2.539508e-2	-2.540121e-2	-0.0254	+4.920000e-6	-1.210000e-6

A review of columns 6 and 7 of Table 4 shows that the absolute largest deviation is associated with the PCS and has a value of 4.920000e-6 mm (Figure 13). The ratio to the calculated deviation and the inspection uncertainty is 1.937e-3.

In column 6 of Table 4, Maximum Deviation with Offset Removed, the WFS deviations range from +8.7++e-7 mm to +4.9++e-6 mm. However, the PCS deviations are almost identical with values of +4.++e-6 mm. The WFS model yields slightly better results than the PCS model for maximum deviations.

In column 7 of Table 4, Minimum Deviation with Offset Removed, the WFS deviations are almost identical and have values of -3.3++e-6 mm. However, the PCS deviations range from -8.6++e-7 mm to -1.2++e-6 mm. The WFS model yields slightly poorer results than the PCS model for minimum deviations.

The results of the analyses shown in columns 6 and 7 of Table 4, Maximum Deviation with Offset Removed (mm) and Minimum Deviation with Offset Removed (mm), reveal that the WFS and PCS models do equally well representing the data.

The results shown in columns 6 and 7 of Table 4 indicate that a minimum accuracy of about five and one-half digits past the decimal point could be expected for an analytical ellipse. In general, the accuracy of these splines is the number of digits past the decimal point minus one-half digit.

These analyses show that both the WFS model and the PCS model produce results that meet all of DOE's MBE requirements.

A review of the six figures listed in Table 4 also shows that the minimum-distance algorithm produces the proper sign on the deviations.

Analytical Parabola

The next six figures show the comparisons of WFS and PCS representations with the exact analytical parabola data generated by Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the fabrication uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 1,000.

Deviation Plots

Figure 14 is a graph of the analytical parabola modeled with the WFS algorithm. The normal offset is 0.0000 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model reproduces the exact results within $1.2481\text{e-}4$ mm.

Figure 15 is a graph of the analytical parabola modeled with the PCS algorithm. The normal offset is 0.0000 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $3.7820\text{e-}4$ mm.

Figure 16 is a graph of the analytical parabola modeled with the WFS algorithm. The normal offset is +0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5421\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 17 is a graph of the analytical parabola modeled with the PCS algorithm. The normal offset is +0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5778\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 18 is a graph of the analytical parabola modeled with the WFS algorithm. The normal offset is -0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the WFS algorithm reproduces the exact results within $2.5525\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

Figure 19 is a graph of the analytical parabola modeled with the PCS algorithm. The normal offset is -0.0254 mm. Mathcad was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their large magnitude, they show as a solid band on the plot. The analysis shows that the PCS algorithm reproduces the exact results within $2.5471\text{e-}2$ mm. Notice that this value includes the normal offset of $2.54\text{e-}2$ mm.

In all six of these figures, the inside normal offset curve has a small discontinuity at the pole. This condition is very pronounced in Figure 18 and Figure 19. The deviation curves overlap at the pole.

Figure 14. Analytical Parabola: WFS, Deviations with 0.0000 mm Normal Offset

Figure 15. Analytical Parabola: PCS, Deviations with 0.0000 mm Normal Offset

Figure 16. Analytical Parabola: WFS, Deviations with +0.0254 mm Normal Offset

Figure 17. Analytical Parabola: PCS, Deviations with +0.0254 mm Normal Offset

Figure 18. Analytical Parabola: WFS, Deviations with -0.0254 mm Normal Offset

Figure 19. Analytical Parabola: PCS, Deviations with -0.0254 mm Normal Offset

Maximum and Minimum Deviations

Table 5 is a summary of the maximum and minimum deviations for the analytical parabola. Column 1 lists the associated figure that displays the results. The second column lists the type of evaluation spline. Columns 3 and 4 are the maximum and minimum deviations with the normal offset included. The fifth column gives the normal offset values. Columns 6 and 7 are the deviations with the normal offsets removed.

Table 5. Analytical Parabola: Summary of Deviations

Figure	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)	Normal Offset (mm)	Maximum Deviation with Offset Removed (mm)	Minimum Deviation with Offset Removed (mm)
Figure 14	WFS	+2.035613e-5	-1.248098e-4	+0.0000	+2.035613e-5	-1.248098e-4
Figure 15	PCS	+3.782016e-4	-7.172041e-5	+0.0000	+3.782016e-4	-7.172041e-5
Figure 16	WFS	+2.542097e-2	+2.527537e-2	+0.0254	+2.097000e-5	-1.246300e-4
Figure 17	PCS	+2.577754e-2	+2.532846e-2	+0.0254	+3.775400e-4	-7.154000e-5
Figure 18	WFS	-2.537913e-2	-2.552455e-2	-0.0254	+2.087000e-5	-1.245500e-4
Figure 19	PCS	-2.502223e-2	-2.547146e-2	-0.0254	+3.777700e-4	-7.146000e-5

The absolute minimum and maximum deviations listed in Table 5 are 1.248098e-4 mm (Figure 14) and 3.782016e-4 mm (Figure 15), respectively. The ratios of the minimum and maximum deviations to the inspection uncertainty are 0.0491 and 0.1489, respectively.

In column 6 of Table 5, Maximum Deviation with Offset Removed, the WFS deviations are almost identical and have values of +2.0++e-5 mm. Similarly, the PCS deviations are almost identical with values of +3.7++e-4 mm. The WFS model yields slightly better results than the PCS model for maximum deviations.

In column 7 of Table 5, Minimum Deviation with Offset Removed, the WFS deviations are almost identical and have values of -1.2++e-4 mm. Similarly, the PCS deviations are almost identical with values of -7.1++e-5 mm. The WFS model yields slightly poorer results than the PCS model for minimum deviations.

The results shown in columns 6 and 7 of Table 5 indicate that a minimum accuracy of about three and three-quarters digits past the decimal point could be expected for an analytical parabola. In general, the accuracy of these splines is the number of digits past the decimal point minus two and one-quarter digits.

These analyses show that both the WFS and PCS produce results that meet all of DOE's MBE requirements.

A review of the six figures in Table 5 shows that the minimum-distance algorithm produces the proper sign on the deviations.

Conclusions

Of the 18 numerical analyses presented above, the largest ratio of calculated deviation to inspection uncertainty is 0.1489. This ratio is associated with the parabola and is located at a point of high

curvature. In addition, the signs of the deviations were shown to be correct. The conclusion from this study is that both the WFS and PCS algorithms can be used to model legacy data and to design new models.

Deviations of Nonanalytical Shapes

We had to know the accuracy of the minimum-distance software algorithms to evaluate the data generated by the different CAD systems (PTC/Pro/E, Computervision/CADDS, and CDC/ICEM DDN). The accuracy was established by the work shown in the section of this report entitled “Accuracy Study of Minimum-Distance Algorithms.” Because the mathematics actually used in the commercial CAD systems is not always known, such systems must be evaluated from the “outside.”

Each CAD system has its own method of representing the spline data points. Table 6 lists the type of two-dimensional, curve-fitting methods available in each CAD system, along with the end-angle options.

Table 6. CAD System Spline Types and End-Angle Options

CAD System	Spline Type	Default End-Angle Option	Specified End-Angle Option	Other End-Angle Option
Pro/E	PCS	Natural	Yes	–
CADDS	WFS	Circular	Yes	–
ICEM	WFS	Circular	Yes	Parabolic

Goals

The goals of this study are to establish and to compare the accuracy of these three CAD software systems.

Nonanalytical Shapes: Ellipse, Lampshade, and Weird Shape

Three nonanalytical shapes were utilized to determine how well the three CAD systems could model various shapes. These shapes were an ellipse, a lampshade, and a weird shape. The data for these analyses were obtained from Atomic Weapons Establishment (AWE) Hunting-Brae.⁹

The procedure used to evaluate the accuracy of the CAD systems was as follows:

- ☐ Generate the mathematical representations of the spline points for both WFS and PCS
- ☐ Generate a data set of evaluation points for each shape from each CAD system
- ☐ Calculate the minimum distances of the evaluation data from the mathematical representation results of both the WFS and PCS models
- ☐ Summarize the results
- ☐ Compare the results

Spline Data

Table 7 is a summary of the parameters used to characterize the three nonanalytical shapes. This table contains the number of points used to define the shape, the data-point spacing ranges, the

number of digits past the decimal point, and the beginning and ending angles. These data are used exactly as received (Ref. 9).

Notice in Table 7 that the spacing of the spline data points of the lampshade and weird shape vary from less than one degree to more than six degrees. Also, the number of points used to define these data is about half the customary number.

Table 7. Nonanalytical Spline Parameters

Non-analytical Splines	File Names	Number of Points	Spacing of Points (Degrees)	Digits Past Decimal Point	Beginning End Angle (Degrees)	Ending End Angle (Degrees)
Ellipse	c01762.spn	46	2.0	6	90.0000	180.0000
Lampshade	c01763.spn	28	0.92 – 6.94	6	99.2767	171.5234
Weird Shape	c01764.spn	24	0.78 – 5.04	6	174.6875	177.5217

Appendix E—Nonanalytical Spline-Point Data has a listing of the spline definitions. All data were rounded to six decimal points.

Figure 20 shows these three spline curves. The solid red curve is the nonanalytical ellipse. The lampshade is shown as the small-dash black curve. The large-dash green curve is the weird shape.

Figure 20. Nonanalytical Shapes: Ellipse, Lampshade, and Weird Shape

Evaluation Data

Three data sets of evaluation points were generated for each of the nonanalytical curves. Table 8 lists the file names, the number of points used in the evaluation, the approximate point spacing, and the accuracy of the data. The number was not identical in each of the evaluation data sets. All the data points were rounded to six digits past the decimal point.

Table 8. Nonanalytical Shapes: Evaluation Data Parameters

Nonanalytical Evaluation Data	File Name	Number of Points	Spacing of Points (Approximate)	Digits Past Decimal Point
Ellipse	c01762_CAD.pts	361	0.25	6
Ellipse	c01762_PRO.pts	351	0.25	6
Ellipse	c01762_ICM.pts	350	0.25	6
Lampshade	c01763_CAD.pts	361	0.25	6
Lampshade	c01763_PRO.pts	351	0.25	6
Lampshade	c01763_ICM.pts	350	0.25	6
Weird Shape	c01764_CAD.pts	339	0.25	6
Weird Shape	c01764_PRO.pts	351	0.25	6
Weird Shape	c01764_ICM.pts	350	0.25	6

Keyword Graphics Builder Program Command File

The command file used to perform the following calculations is listed in Appendix F—Keyword Graphics Builder Program—Command Files—Nonanalytical Shapes—Deviation Study.

Nonanalytical Ellipse

The next six figures show the comparisons of WFS and PCS representations of the nonanalytical ellipse curve with the evaluation data generated by the three different CAD systems. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 21 is a graph of the nonanalytical ellipse modeled with the WFS algorithm. CADDS was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model yields a maximum deviation of $1.1841\text{e-}5$ mm.

Figure 22 is a graph of the nonanalytical ellipse modeled with the PCS algorithm. CADDS was used to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur near the pole where the curvatures of the data are the largest. Note that the deviations damp out in about four segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $5.0234\text{e-}4$ mm.

Figure 23 is a graph of the nonanalytical ellipse modeled with the WFS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur near the pole where the curvatures of the data are the largest. Note that the deviations damp out in about four segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $4.9707\text{e-}4$ mm.

Figure 24 is a graph of the nonanalytical ellipse modeled with the PCS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS model yields a maximum deviation of $6.3625\text{e-}8$ mm.

Figure 25 is a graph of the nonanalytical ellipse modeled with the WFS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model yields a maximum deviation of $2.4593\text{e-}5$ mm.

Figure 26 is a graph of the nonanalytical ellipse modeled with the PCS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur near the pole where the curvatures of the data are the largest. Note that the deviations damp out in about four segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $5.1432\text{e-}4$ mm.

Figure 21. Nonanalytical Ellipse: WFS, CADDs Deviations

Figure 22. Nonanalytical Ellipse: PCS, CADDs Deviations

Figure 23. Nonanalytical Ellipse: WFS, Pro/E Deviations

Figure 24. Nonanalytical Ellipse: PCS, Pro/E Deviations

Figure 25. Nonanalytical Ellipse: WFS, ICEM DDN Deviations

Figure 26. Nonanalytical Ellipse: PCS, ICEM DDN Deviations

Maximum and Minimum Deviations

Table 9 is a summary of the maximum and minimum deviations for the nonanalytical ellipse. Column 1 lists the associated figure that displays the results. Column 2 is the CAD system used to generate the evaluation points. The third column gives the type of evaluation spline. Columns 4 and 5 are the maximum and minimum deviations.

Table 9. Nonanalytical Ellipse: Summary of Deviations

Figure	CAD System	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 21	CADDS	WFS	+9.934505e-7	-1.184080e-5
Figure 22	CADDS	PCS	+5.023381e-4	-9.812279e-6
Figure 23	Pro/E	WFS	+1.376314e-5	-4.970730e-4
Figure 24	Pro/E	PCS	+6.362479e-8	-5.822224e-8
Figure 25	ICEM	WFS	+1.620899e-5	-2.459316e-5
Figure 26	ICEM	PCS	+5.143201e-4	-1.657802e-5

The absolute minimum and maximum deviations listed in Table 9 are 4.970730e-4 (Figure 23) and 5.143201e-4 (Figure 26), respectively. The ratios of deviations to the inspection uncertainty are 0.1957 and 0.2025, respectively.

As was stated in the section of this document entitled “Computer-Aided Design Systems,” both CADDS and ICEM DDN have WFS modules, and Pro/E uses a PCS in its sketcher option. Figure 21 and Figure 25 reflect the existence of the WFS modules. Figure 24 verifies the use of a PCS in Pro/E. The other three figures show opposite results. In essence, like modules yield better results, and unlike modules yield poorer results. The deviations for Figure 22 and Figure 26 at their poles are opposite in direction and almost equal in magnitude to those shown in Figure 23.

A review of Table 9 reveals that the best combination of CAD system and spline model is Pro/E compared to the PCS model. The least desirable representations are Pro/E compared to the WFS model and ICEM DDN with the PCS model.

The results of these analyses show that both the WFS and PCS produce results that meet all of DOE’s MBE requirements.

Nonanalytical Lampshade

The next six figures show the comparisons of WFS and PCS representations of the nonanalytical lampshade curve with the evaluation data generated by the three different CAD systems. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 27 is a graph of the nonanalytical lampshade modeled with the WFS algorithm. CADDS was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model yields a maximum deviation of 7.3857e-5 mm.

Figure 28 is a graph of the nonanalytical lampshade modeled with the PCS algorithm. CADD5 was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvatures, the deviations damp out in about four to five segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $1.2690\text{e-}3$ mm.

Figure 29 is a graph of the nonanalytical lampshade modeled with the WFS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvature, the deviations damp out in about four to five segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $1.2734\text{e-}3$ mm.

Figure 30 is a graph of the nonanalytical lampshade modeled with the PCS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS model yields a maximum deviation of $6.5001\text{e-}8$ mm.

Figure 31 is a graph of the nonanalytical lampshade modeled with the WFS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model yields a maximum deviation of $5.9263\text{e-}5$ mm.

Figure 32 is a graph of the nonanalytical lampshade modeled with the PCS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvature, the deviations damp out in about four to five segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $1.2687\text{e-}3$ mm.

Notice that in all six of these figures, the inside normal offset curve has a large discontinuity in the region of high curvature.

Figure 27. Nonanalytical Lampshade: WFS, CADDs Deviations

Figure 28. Nonanalytical Lampshade, PCS, CADDs Deviations

Figure 29. Nonanalytical Lampshade: WFS, Pro/E Deviations

Figure 30. Nonanalytical Lampshade: PCS, Pro/E Deviations

Figure 31. Nonanalytical Lampshade: WFS, ICEM DDN Deviations

Figure 32. Nonanalytical Lampshade: PCS, ICEM DDN Deviations

Maximum and Minimum Deviations

Table 10 is a summary of the maximum and minimum deviations for the nonanalytical lampshade. Column 1 lists the associated figure that displays the results. Column 2 is the CAD system used to generate the evaluation points. The third column gives the type of evaluation spline. Columns 4 and 5 are the maximum and minimum deviations.

Table 10. Nonanalytical Lampshade: Summary of Deviations

Figure Number	CAD System	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 27	CADDS	WFS	+7.385725e-7	-3.636758e-5
Figure 28	CADDS	PCS	+1.269041e-3	-4.318652e-4
Figure 29	Pro/E	WFS	+4.393061e-4	-1.273383e-3
Figure 30	Pro/E	PCS	+5.684791e-8	-6.500090e-8
Figure 31	ICEM	WFS	+5.604529e-5	-5.926299e-5
Figure 32	ICEM	PCS	+1.268650e-3	-4.072064e-4

The absolute minimum and maximum deviations listed in Table 10 are 1.273383e-3 (Figure 29) and 1.269041e-3 (Figure 28), respectively. The ratios of deviations to the inspection uncertainty are 0.5013 and 0.4996, respectively.

A review of Table 10 reveals that the best combination of CAD system and spline model is Pro/E compared to the PCS model. The least desirable representations are CADDS compared to the PCS model and ICEM DDN with the PCS model.

As was stated in the section of this document entitled “Computer-Aided Design Systems,” both CADDS and ICEM DDN have WFS modules, and Pro/E uses a PCS in its sketcher option. Figure 27 and Figure 31 reflect the existence of these WFS modules. Figure 30 verifies the use of a PCS in Pro/E. The other three figures show opposite results. In essence, like modules yield better results, and unlike modules yield poorer results. The deviations for Figure 28 and Figure 32 at the equator and the region of high curvature are opposite in direction and almost equal in magnitude to those shown in Figure 29.

The results of these analyses show that the both the WFS and PCS produce results that meet all of DOE’s MBE requirements.

Nonanalytical Weird Shape

The next six figures show the comparisons of WFS and PCS representations for the nonanalytical weird shape curve with the evaluation data generated by the three different CAD systems. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 33 is a graph of the nonanalytical weird shape modeled with the WFS algorithm. CADDS was utilized to generate the evaluation data. The deviations of the evaluation data from the spline

model are plotted in red, and because of their small magnitude, they do not show on the plot. This analysis shows that the WFS model yields a maximum deviation of $1.3288\text{e-}4$ mm.

Figure 34 is a graph of the nonanalytical weird shape modeled with the PCS algorithm. CADD5 was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvature, the deviations do not damp out very well. This analysis shows that the PCS model yields a maximum deviation of $1.6642\text{e-}3$ mm.

Figure 35 is a graph of the nonanalytical weird shape modeled with the WFS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvature, the deviations do not damp out very well. The analysis shows that the WFS model yields a maximum deviation of $1.6099\text{e-}3$ mm.

Figure 36 is a graph of the nonanalytical weird shape modeled with the PCS algorithm. Pro/E was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the PCS model yields a maximum deviation of $2.3008\text{e-}5$ mm.

Figure 37 is a graph of the nonanalytical weird shape modeled with the WFS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red, and because of their small magnitude, they do not show on the plot. The analysis shows that the WFS model yields a maximum deviation of $1.0311\text{e-}4$ mm.

Figure 38 is a graph of the nonanalytical weird shape modeled with the PCS algorithm. ICEM DDN was utilized to generate the evaluation data. The deviations of the evaluation data from the spline model are plotted in red. The most deviations occur where the curvatures of the data are the largest. Note, in the regions of high curvature, the deviations do not damp out very well. The analysis shows that the PCS model yields a maximum deviation of $1.6128\text{e-}3$ mm.

Figure 33. Nonanalytical Weird Shape: WFS, CADDs Deviations

Figure 34. Nonanalytical Weird Shape: PCS, CADDs Deviations

Figure 35. Nonanalytical Weird Shape: WFS, Pro/E Deviations

Figure 36. Nonanalytical Weird Shape: PCS, Pro/E Deviations

Figure 37. Nonanalytical Weird Shape: WFS, ICEM DDN Deviations

Figure 38. Nonanalytical Weird Shape: PCS, ICEM DDN Deviations

Maximum and Minimum Deviations

Table 11 is a summary of the maximum and minimum deviations for the nonanalytical weird shape. Column 1 lists the associated figure that displays the results. Column 2 is the CAD system used to generate the evaluation points. The third column gives the type of evaluation spline. Columns 4 and 5 are the maximum and minimum deviations.

Table 11. Nonanalytical Weird Shape, Summary of Deviations

Figure Number	CAD System	Spline Type	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 33	CADDS	WFS	+6.153635e-5	-1.328788e-4
Figure 34	CADDS	PCS	+1.377073e-3	-1.664233e-3
Figure 35	Pro/E	WFS	+1.609922e-3	-1.343000e-3
Figure 36	Pro/E	PCS	+6.048408e-6	-2.300825e-5
Figure 37	ICEM	WFS	+1.031108e-4	-6.984389e-5
Figure 38	ICEM	PCS	+1.445499e-3	-1.612766e-3

The absolute minimum and maximum deviations listed in Table 11 are 1.664233e-3 (Figure 34) and 1.609922e-3 (Figure 35), respectively. The ratios of deviations to the inspection uncertainty are 0.6552 and 0.6338, respectively.

A review of Table 11 reveals that the best combination of CAD system and spline model is Pro/E compared to the PCS model. The least desirable representations are CADDS compared to the PCS model and ICEM DDN with the PCS model.

As was stated in this document in the section entitled “Computer-Aided Design Systems,” both CADDS and ICEM DDN have WFS modules, and Pro/E uses a PCS in its sketcher option. Figure 33 and Figure 37 reflect the existence of these WFS modules. Figure 36 verifies the use of a PCS in Pro/E. The other three figures show opposite results. In essence, like modules yield better results, and unlike modules yield poorer results. The deviations for Figure 34 and Figure 38 at the regions of high curvature are opposite in direction and almost equal in magnitude to those shown in Figure 35.

These analyses show that both the WFS and PCS produce results that meet all of DOE’s MBE requirements.

Conclusions

Of the 18 numerical analyses presented above, the largest ratio of calculated deviation to inspection uncertainty is 0.6552. This ratio is associated with the weird-shape curve and is located at a point of high curvature. This study shows that all three CAD systems can be used to design, inspect, and fabricate parts for both legacy data and new models.

Effects of End Angles

To assure that the three-dimensional solid models are independent of the CAD system, the end angles of the splines must be defined. All three CAD systems being evaluated have the option of specifying the end angles. One of the difficulties associated with building solid models from legacy data is that in a few cases, the end angles were not recorded. In these cases, estimates of the end angles must be made. The purpose of this study is to establish a bound on these angles such that the part definition will be within the inspection uncertainty.

Both the WFS and PCS formulations require that the end angles be defined. There are several methods of defining these angles, including the following approaches:

- ❑ Specified end angles
- ❑ Linear end angles
- ❑ Parabolic end angles
- ❑ Cubic end angles
- ❑ Circular end angles
- ❑ Natural end angles

All three CAD systems evaluated in this study have the capability of using the specified end angles. The designer determines the desired end angles and inputs the values in the system.

Linear end angles are defined by the slopes of linear lines passing through the first and last two points of the data set, respectively. None of the three CAD systems have this option.

Parabolic end angles are defined by the slopes of a parabolic curve passing through the first and last three points of the data set, respectively. None of the three CAD systems have this option. However, the ICEM DDN system does utilize a parabolic end-angle option. In the ICEM DDN WFS option, the parabolic end-angle conditions have very complex definitions. The first and last segments of the spline are forced to be parabolic (not cubic), and the angles at the first (last) and second (last minus one) are defined to be equal and opposite, respectively. These angles become part of the solution of the WFS cubic coefficients.

Cubic end angles are defined by the slopes of a cubic curve passing through the first and last three points of the data set, respectively. None of the three CAD systems have this option.

Circular end angles are defined by the slopes of a circular curve passing through the first and last three points of the data set, respectively. Many of the parts fabricated in the NWC from the 1980s to the early 1990s used a circle end-condition default definition. Both CADDs and ICEM DDN have this option.

Natural end angles are defined by setting the curvatures to zero at the ends. Table 6. CAD System Spline Types and End-Angle Options, shows that Pro/E uses natural end angles as its default.

Goal

The goal of this study is to establish upper bounds on how much the end angles may vary and still have inspection results within the inspection uncertainty.

Analytical Shapes, Circle, Ellipse, and Parabola

Three analytical shapes were utilized to establish the end-angle bounds such that the deviations were within the inspection uncertainty. These shapes were a circle, an ellipse, and a parabola. The spline data and the evaluation data were generated with Mathcad. The spline and evaluation data for this study are defined in the section of this document entitled “Accuracy Study of Minimum-Distance Algorithms.”

Spline Data

Table 12 is a summary of the parameters used to characterize the six analytical shapes. This table contains the number of points used to define the shape, the data-point-spacing ranges, and the beginning and ending end angles.

Table 12. Analytical Spline Parameters

Analytical Shape	Number of Points	Spacing of Points (Degrees)	Beginning End Angle (Degrees)	Ending End Angle (Degrees)
Circle-Plus	46	2.0	90.25	180.25
Circle-Minus	46	2.0	89.75	179.75
Ellipse-Plus	46	2.0	90.25	180.25
Ellipse-Minus	46	2.0	89.75	179.75
Parabola-Plus	46	2.0	90.25	163.5508
Parabola-Minus	46	2.0	89.75	163.0508

Evaluation Data Set Parameters

Table 13 lists the parameters of these analytical shapes. The number of points, point spacing, and number of digits past the decimal point are summarized. The evaluation figures were generated at every 0.25 degree using the equations listed in the section of this document entitled “Accuracy Study of Minimum-Distance Algorithms.”

Table 13. Evaluation Data Set Parameters

Analytical Spline	Number of Points	Spacing of Points (Degree)	Digits Past Decimal Point
Circle	361	0.25	6
Ellipse	361	0.25	6
Parabola	361	0.25	6

Keyword Graphics Builder Program Command File

The command files utilized to perform the following calculations are listed in Appendix F—Keyword Graphics Builder Program— Command Files—Analytical Shapes—End-Angle Effects.

Analytical Circle

The next four figures show the comparisons of WFS and PCS representations of the analytical circle with the evaluation data generated with Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 39 shows the results of the comparison of the WFS analytical circle model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $2.5917\text{e-}3$ mm.

Figure 40 shows the results of the comparison of the PCS analytical circle model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. This analysis shows that the PCS model yields a maximum deviation of $2.5904\text{e-}3$ mm.

Figure 41 shows the results of the comparison of the WFS analytical circle model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $2.5917\text{e-}3$ mm.

Figure 42 shows the results of the comparison of the PCS analytical circle model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. This analysis shows that the PCS model yields a maximum deviation of $2.5904\text{e-}3$ mm.

Figure 39. Analytical Circle: WFS, Deviations with +0.25 Degree End Angles

Figure 40. Analytical Circle: PCS, Deviations with +0.25 Degree End Angles

Figure 41. Analytical Circle: WFS, Deviations with -0.25 Degree End Angles

Figure 42. Analytical Circle: PCS, Deviations with -0.25 Degree End Angles

Maximum and Minimum Deviations

Table 14 is a summary of the maximum and minimum deviations for the analytical circle. Column 1 lists the associated figure that displays the results. Column 2 is the curve-fitting algorithm used to generate the evaluation points. The third column lists the end-angle changes. Columns 4 and 5 are the maximum and minimum deviations.

Table 14. Analytical Circle: Deviations with Modified End Angles

Figure	Spline Type	End Angles (Degree)	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 39	WFS	+0.25	+2.589556e-3	-2.591670e-3
Figure 40	PCS	+0.25	+2.590368e-3	-2.588462e-3
Figure 41	WFS	-0.25	+2.589556e-3	-2.591670e-3
Figure 42	PCS	-0.25	+2.590368e-3	-2.588462e-3

The absolute minimum and maximum deviations listed in Table 14 are 2.591670e-3 (Figure 41) and 2.590368e-3 (Figure 40), respectively. The ratios of deviations to the inspection uncertainty are 1.0203 and 1.0198, respectively. These calculations show that end angles may vary almost 0.25 degree and the deviations will still remain within the inspection uncertainty.

A review of the above four figures shows the effects of the end-angle changes on the deviations. Notice that at both ends of the spline, the deviations damp out between the third and fourth segments. This situation exists for both the WFS and PCS.

A review of Table 14 reveals that the deviations are antisymmetric about the ends for both spline representations. Also, the differences between the WFS algorithm and the PCS model are very small, and they are well within the accuracy of the calculations.

Analytical Ellipse

The next four figures show the comparisons of WFS and PCS representations of the analytical ellipse with the evaluation data generated by the Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 43 shows the results of the comparison of the WFS analytical ellipse model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. This analysis shows that the WFS model yields a maximum deviation of 2.5891e-3 mm.

Figure 44 shows the results of the comparison of the PCS analytical ellipse model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. This analysis shows that the PCS model yields a maximum deviation of 2.5933e-3 mm.

Figure 45 shows the results of the comparison of the WFS analytical ellipse model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $2.5941\text{e-}3$ mm.

Figure 46 shows the results of the comparison of the PCS analytical ellipse model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about four segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $2.5842\text{e-}3$ mm.

Figure 43. Analytical Ellipse: WFS, Deviations with +0.25 Degree End Angles

Figure 44. Analytical Ellipse: PCS, Deviations with +0.25 Degree End Angles

Figure 45. Analytical Ellipse: WFS, Deviations with -0.25 Degree End Angles

Figure 46. Analytical Ellipse: PCS, Deviations with -0.25 Degree End Angles

Maximum and Minimum Deviations

Table 15 is a summary of the maximum and minimum deviations for the analytical ellipse. Column 1 lists the associated figure that displays the results. Column 2 is the curve-fitting algorithm used to generate the evaluation points. The third column lists the end angle changes. Columns 4 and 5 are the maximum and minimum deviations.

Table 15. Analytical Ellipse: Deviations with Modified End Angles

Figure	Spline Type	End Angles (Degree)	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 43	WFS	+0.25	+2.589069e-3	-2.073179e-3
Figure 44	PCS	+0.25	+2.593280e-3	-2.072276e-3
Figure 45	WFS	-0.25	+2.071614e-3	-2.594148e-3
Figure 46	PCS	-0.25	+2.071708e-3	-2.584165e-3

The absolute minimum and maximum deviations listed in Table 15 are 2.594148e-3 (Figure 45) and 2.593280e-3 (Figure 44), respectively. The ratios of deviations to the inspection uncertainty are 1.0213 and 1.0210, respectively. These calculations show that end angles may vary almost 0.25 degree and still be within the inspection uncertainty.

A review of the above four figures shows the effects of the end-angle changes on the deviations. Notice that at both ends of the spline, the deviations damp out between the third and fourth segments. This situation exists for both the WFS and PCS.

A review of Table 15 reveals that the deviations are almost antisymmetric about the ends for both spline representations. Also, the differences between the WFS and PCS models are very small and are well within the accuracy of the calculations.

Analytical Parabola

The next four figures show the comparisons of WFS and PCS representations of the analytical parabola with the evaluation data generated with Mathcad. These plots show the spline curve (SPLN.PTS), the CAD points set (CADM.PTS), the deviation scale factor (SCALFATR), the maximum deviation (DISTANCE), and the inspection uncertainty bands (OFFSET). The SPLN.PTS are plotted to scale, and all the other curves are distorted by the scale factor of 5,000.

Deviation Plots

Figure 47 shows the results of the comparison of the WFS analytical parabola model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about five segments of the spline data. This analysis shows that the WFS model yields a maximum deviation of 2.6329e-3 mm.

Figure 48 shows the results of the comparison of the PCS analytical parabola model to the Mathcad data. The end angles are increased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about five segments of the spline data. This analysis shows that the PCS model yields a maximum deviation of 2.9093e-3 mm.

Figure 49 shows the results of the comparison of the WFS analytical parabola model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about five segments of the spline data. The analysis shows that the WFS model yields a maximum deviation of $2.6194\text{e-}3$ mm.

Figure 50 shows the results of the comparison of the PCS analytical parabola model to the Mathcad data. The end angles are decreased by 0.25 degree. The deviations of the evaluation data from the spline model are plotted in red. Note, at the ends of the spline, the deviations damp out in about five segments of the spline data. The analysis shows that the PCS model yields a maximum deviation of $2.2716\text{e-}3$ mm.

Figure 47. Analytical Parabola: WFS, Deviations with +0.25 Degree End Angles

Figure 48. Analytical Parabola: PCS, Deviations with +0.25 Degree End Angles

Figure 49. Analytical Parabola: WFS, Deviations with -0.25 Degree End Angles

Figure 50. Analytical Parabola: PCS, Deviations with -0.25 Degree End Angles

Maximum and Minimum Deviations

Table 16 is a summary of the maximum and minimum deviations for the analytical parabola. Column 1 lists the associated figure that displays the results. Column 2 is the curve-fitting algorithm used to generate the evaluation points. The third column lists the end-angle changes. Columns 4 and 5 are the maximum and minimum deviations.

Table 16. Analytical Parabola: Deviations with Modified End Angles

Figure	Spline Type	End Angles (Degree)	Maximum Deviation (mm)	Minimum Deviation (mm)
Figure 47	WFS	+0.25	+2.632867e-3	-1.605319e-3
Figure 48	PCS	+0.25	+2.909316e-3	-1.605285e-3
Figure 49	WFS	-0.25	+1.604538e-3	-2.619395e-3
Figure 50	PCS	-0.25	+1.604532e-3	-2.271586e-3

The absolute minimum and maximum deviations listed in Table 16 are 2.619395e-3 (Figure 49) and 2.909326e-3 (Figure 48), respectively. The ratios of deviations to the inspection uncertainty are 1.0313 and 1.1454, respectively. These calculations show that end angles may vary almost 0.25 degree and still be within the inspection uncertainty.

A review of the figures above shows the effects of the end-angle changes on the deviations. Notice that at both ends of the spline, the deviations damp out between the fifth and sixth segments. This situation exists for both the WFS and PCS.

A review of Table 16 reveals that the deviations are almost antisymmetric about the ends for both spline representations. Also, the differences between the WFS and PCS models are very small and are well within the accuracy of the calculations.

Conclusions

The above analyses show that the end angle may vary almost 0.25 degree and still be within the inspection uncertainty. End-angle effects are very local and damp out in the fourth or fifth segments. The conclusion of this study is that if the end angles are within about 0.25 degree, the solid-based models can be used to design, inspect, and fabricate parts.

Summary and Conclusions

Three studies are presented in this report. The first study shows that the accuracy of the minimum-distance algorithm and the ability of both the WFS and PCS to represent analytical data sets (circle, ellipse, and parabola) are well within the inspection uncertainty. Of the 18 numerical analyses presented, the largest ratio of calculated deviation to inspection uncertainty is 0.1489. This ratio is associated with the parabola and is located at the point of highest curvature. The signs of the deviations are shown to be correct. The conclusion from this study is that both the WFS and PCS can be used to reproduce legacy data and to design new products and redesign old ones.

The second study evaluates three CAD systems (Pro/E, ICEM DDN, and CADD5), demonstrates their capabilities to model DOE legacy data, and determines that they can be utilized to develop future models. Three nonanalytical shapes (ellipse, lampshade, and a weird shape) are evaluated with the three CAD systems. Of the 18 numerical analyses presented above, the largest ratio of calculated deviation to inspection uncertainty is 0.6552. This ratio is associated with the weird shape curve and is located at the point of high curvature. This study shows that all three CAD systems can be used to design, inspect, and fabricate parts for both legacy data and new models.

The third study sets upper bounds on the variation of the end angles used to define the geometry of analytical shapes (circle, ellipse, and parabola) and still remain within the inspection uncertainty. These analyses show that, when the end angles deviate almost 0.25 degree from the nominal values, the deviations are still within the inspection uncertainty. End-angle effects are very local and damp out in the fourth or fifth segments of the spline data. The conclusion of this study is that if the end angles are within about 0.25 degree, the solid-based models still can be used to design, inspect, and fabricate parts.

The conclusions of these studies are that any CAD system that supports either PCS or B-spline can be used with confidence to reproduce DOE legacy data or to design, inspect and fabricate old and new parts. The NWC should move on to these modern systems, knowing that the legacy data generated by the WFS algorithm can be reproduced well within the inspection limits.

Appendix A—WFS Routines

```

SUBROUTINE APTWF(NPTS,ANGIN,ANGOUT,IAFLG,WFSPL)
C-----
C      SUBROUTINE APTWF(WFSPL,NBLPTS)
C
C This subroutine controls the generation of the baseline APT Wilson-
C Fowler spline. The main features of this sub_routine are to put
C the IS standard data FORMAT into an APT FORMAT and to call two main
C APT routines (APT088 and APT089). The reason that we convert to the
C APT data FORMAT is because we decided to not make any changes to the
C original APT program, thus perserving our purest baseline assumptions.
C
C Routine APT088 takes the initial through point data, computes slope
C segment angles and segment lengths and load the TAB array in the
C proper FORMAT. After APT088 is done, routine APT089 can be called to
C the WF cubic coefficients. The spline fitting method is:
C
C 1. Approximate the slopes at each interior point by assigning each
C point the slope of a circle which passes through that point and the
C adjacent point on each side (3 point circle).
C 2. At each interior point calculate the difference in curvature
C between the cubic equation on one side of the point and the cubic
C equation on the other side of a point (i.e., delta curvature) in
C terms of the exterior angles.
C
C The final form of the data array is:
C   tab(1) - Record number of external canonical form.
C   tab(2-10) - Nine elements of 3x3 rotation matrix used to transform
C               tabulated points into u,v,w-coordinate system.
C   tab(11) - Total number of points, including the 2 extension
C             points.
C   tab(12) - 14.0
C   tab(13) - u-coordinate of extension point
C   tab(14) - v-coordinate of extension point
C   tab(15) - Coefficient of third degree cubic term for 1st interval
C   tab(16) - Coefficient of second degree cubic term for 1st interval
C   tab(17) - Length of 1st interval.
C   tab(18) - Maximum value of cubic in 1st interval.
C   tab(19) - Minimum value of cubic in 1st interval.
C   :
C   :
C   tab(13+m) - u-coordinate of mth point. m=1,...,n and n = # of through
C               pts
C   tab(14+m) - v-coordinate of mth point.
C   tab(15+m) - Coefficient of third degree cubic term for mth interval
C   tab(16+m) - Coefficient of second degree cubic term for mth interval
C   tab(17+m) - Length of mth interval.
C   tab(18+m) - Maximum value of cubic in mth interval.
C   tab(19+m) - Minimum value of cubic in mth interval.
C   :
C   :
C   tab(13+n) - u-coordinate of last extension point.
C   tab(14+n) - v-coordinate of last extension point.
C
C After the APT WF spline is computed, it is defined as a series of
C local(u,v) coordinate systems. Each local coordinate system is
C defined by the cubic:
C       v(u) = c1*u**3 + c2*u**2 + c3*u + c4
C
C By applying boundary conditions on the local interval
C       v(0) = 0, v(L) = 0
C       v'(0) = TA, v'(L) = TB,

```

```

c The local cubic reduces to
c      v(u) = c1*u**3 + c2*u**2 + c3*u,  where c3=TA
c
c since v(L) = 0, we get that c1*u**3 + c2*u**2 + c3*u = 0
c which implies:      c3 = -c1*u**2 - c2*u
c
c After the series of local cubics is defined, they will be transformed
c into global representation this will involve translation, rotation and
c a reparameterization. The new parameterization is w.r.t. the spline's
c cumulative choord length.
c
c See chapter 5 of the following report for more inFORMATION.
c
c Dolin, R. M., "The Wilson-Fowler Spline in a Global IGES Coordinate
c      Frame," Los Alamos National Laboratory Report Number
c      LA-11024-MS, September, 1987, Los Alamos, NM.
c
c-----
c
c
c      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
c      IMPLICIT INTEGER*4 (I-N)
C
Cwb  PARAMETER(NCOEF=13, MXKNOTS=201, DEGRAD=0.01745329)
      PARAMETER(NCOEF=13, MXKNOTS=201)
C
Cwb  DIMENSION TAB(20*MXKNOTS),COEF(8,MXKNOTS),WFSPL(NCOEF,MXKNOTS)
c
c Determine if end angles are to be specified or computed. KK and LL
c are end angle flags. When they =1, end angles exist and =0 no end
c angles exist. The KK flag is for the entry and the LL flag for exit
c of the spline. When end angles (slopes) are given, they should be in
c radians. APT defines the slope to be the tangent of the start or end
c angles. Hence, what we want to give the APT routines is the Tangent
c of the end angles.
Cwb
      PI=4.0D0*DATAN(1.0D0)
      DEGRAD=PI/180.0D0
Cwb
      DO 10 I = 1,18
          TAB(I) = 0.0D0
      10 CONTINUE
c
      IF (IAFLG .EQ. 1) THEN
          TAB(1) = DTAN(ANGIN)
          TAB(2) = DTAN(ANGOUT)
          KK = 1
          LL = 1
      ELSE
          TAB(1) = 0.0D0
          TAB(2) = 0.0D0
          KK = 0
          LL = 0
      END IF
      NN = NPTS*2 + 17
      J = 1
      DO 100 I = 18,NN,2
          TAB(I) = WFSPL(2,J)
          TAB(I+1) = WFSPL(6,J)
          J = J + 1
      100 CONTINUE
c
c Define the necessary APT parameters. MM is a coordinate definer, =3

```

```

c  => XY
c coordinate data.  JJ is a T&R flag, =0 => no data translation or
c rotation.
      MM      = 3
      JJ      = 0
cwb      RESULT = 0.D0
c
c Load the through points into the APT array and compute the initial
c set of local intervals
c
      CALL APT088 (MM, NPTS, KK, LL, JJ, TAB,ANGIN,ANGOUT)
c
c Compute the series of local cubics defined over each through point
c interval.
c
      CALL APT089(TAB)
c
c Convert the series of local cubics into a global spline definition
c with a cumulative choord length parameterization.  Begin by computing
c the linear term for each of the local cubic equations. The local cubic
c equation is
      v(u) = C1*u**3 + C2*u**2 + C3*u
c
c The two global cubic equations are given as:
c
      x(s) = Ax*s**3 + Bx*s**2 + Cx*s + Dx
      y(s) = Ay*s**3 + By*s**2 + Cy*s + Dy
c where
c      Ax = -C1*sin(gamma),      Ay =  C1*cos(gamma)
c      Bx = -C2*sin(gamma),      By =  C2*cos(gamma)
c      Cx =  C3*sin(gamma) + cos(gamma)  Cy = -C3*cos(gamma)+sin(gamma)
c      Dx =  u                      Dy =  v
c and
c      gamma = atan(Dv/Du)
c
c The coef array below is defined as Dx,Cx,Bx,Ax, Dy,Cy,By,Ay
c      i=1,2,...,8
      NSIZE = 20 + (NPTS-2)*7
      J      = 1
      DO 200 I = 20,NSIZE,7
        DXI  = TAB(I+7) - TAB(I)
        DYI  = TAB(I+8) - TAB(I+1)
        C1I  = TAB(I+2)
        C2I  = TAB(I+3)
        RLEN = TAB(I+4)
        C3I  = -C1I*RLEN*RLEN - C2I*RLEN
        GAMMA = F5ATAN(DYI,DXI)
        GAMMA = GAMMA * DEGRAD
        COSG  = DCOS(GAMMA)
        SING  = DSIN(GAMMA)
c
c COMPUTE THE GLOBAL X-COEFFICIENTS
      COEF(4,J) = -C1I*SING      ! THESE GLOBAL COEFFICIENTS
      COEF(3,J) = -C2I*SING      ! ARE THE RESULT OF ROTATING
      COEF(2,J) = -C3I*SING + COSG ! THE LOCAL CUBIC EQUATION
      COEF(1,J) = TAB(I)         ! INTO GLOBAL COORDINATES
c
c COMPUTE THE GLOBAL Y-COEFFICIENTS
      COEF(8,J) = C1I*COSG      ! [X Y] = [u v(u) 1] [R]
      COEF(7,J) = C2I*COSG      ! WHERE
      COEF(6,J) = C3I*COSG + SING ! -COSG -SING
      COEF(5,J) = TAB(I+1)       ! [R] = SING -COSG
      J          = J + 1         ! XT YT
200 CONTINUE

```

```

C
C LOAD X AND Y DATA POINTS OF LAST POINT INTO COEFFICIENT ARRAY
c Use the coordinates of the last point to define end interval
      COEF(1,J) = TAB(I)           ! THE NTH POINT HAS NO CUBIC
      COEF(5,J) = TAB(I+1)         ! BUT THE KNOT POINT WILL BE USED
C
c Define the WFSPL array w.r.t. the global coefficients
      DO 300 IG = 1,NPTS
        IF (IG .EQ. 1) THEN
          WFSPL(1,IG) = 0.0D0
        ELSE
          IT          = 24 + (IG-2)*7
          WFSPL(1,IG) = TAB(IT) + WFSPL(1,IG-1)
        END IF
C
        DO 350 JG = 1,8
          WFSPL(JG+1,IG) = COEF(JG,IG)
350    CONTINUE
300    CONTINUE
C
c Always compute the end angles after computing APT WF coefficients.
c Return angles in radians.
C      IF (IAFLG .EQ. 0) CALL GET_ANG(WFSPL,NPTS, ANGIN,ANGOUT)
C
c MAN O MAn O Man.....O man
C
      RETURN
      END
      SUBROUTINE APTWF(NPTS,ANGIN,ANGOUT,IAFLG,WFSPL)
C-----
C      SUBROUTINE APTWF(WFSPL,NBLPTS)
C
c This subroutine controls the generation of the baseline APT Wilson-
c Fowler spline. The main features of this sub_routine are to put
c the IS standard data FORMAT into an APT FORMAT and to call two main
c APT routines (APT088 and APT089). The reason that we convert to the
c APT data FORMAT is because we decided to not make any changes to the
c original APT program, thus perserving our purest baseline assumptions.
C
c Routine APT088 takes the initial through point data, computes slope
c segment angles and segment lengths and load the TAB array in the
c proper FORMAT. After APT088 is done, routine APT089 can be called to
c the WF cubic coefficients. The spline fitting method is:
C
c 1. Approximate the slopes at each interior point by assigning each
c point the slope of a circle which passes through that point and the
c adjacent point on each side (3 point circle).
c 2. At each interior point calculate the difference in curvature
c between the cubic equation on one side of the point and the cubic
c equation on the other side of a point (i.e., delta curvature) in
c terms of the exterior angles.
C
c The final form of the data array is:
c tab(1) - Record number of external canonical form.
c tab(2-10) - Nine elements of 3x3 rotation matrix used to transform
c tabulated points into u,v,w-coordinate system.
c tab(11) - Total number of points, including the 2 extension
c points.
c tab(12) - 14.0
c tab(13) - u-coordinate of extension point
c tab(14) - v-coordinate of extension point
c tab(15) - Coefficient of third degree cubic term for 1st interval
c tab(16) - Coefficient of second degree cubic term for 1st interval
c tab(17) - Length of 1st interval.

```

```

c  tab(18)  - Maximum value of cubic in 1st interval.
c  tab(19)  - Minimum value of cubic in 1st interval.
c      :
c      :
c  tab(13+m) - u-coordinate of mth point. m=1,...,n and n = # of through
c             pts
c  tab(14+m) - v-coordinate of mth point.
c  tab(15+m) - Coefficient of third degree cubic term for mth interval
c  tab(16+m) - Coefficient of second degree cubic term for mth interval
c  tab(17+m) - Length of mth interval.
c  tab(18+m) - Maximum value of cubic in mth interval.
c  tab(19+m) - Minimum value of cubic in mth interval.
c      :
c      :
c  tab(13+n) - u-coordinate of last extension point.
c  tab(14+n) - v-coordinate of last extension point.
c
c After the APT WF spline is computed, it is defined as a series of
c local(u,v) coordinate systems. Each local coordinate system is
c defined by the cubic:
c      v(u) = c1*u**3 + c2*u**2 + c3*u + c4
c
c By applying boundary conditions on the local interval
c      v(0) = 0,  v(L) = 0
c      v'(0) = TA, v'(L) = TB,
c The local cubic reduces to
c      v(u) = c1*u**3 + c2*u**2 + c3*u,  where c3=TA
c
c since v(L) = 0, we get that c1*u**3 + c2*u**2 + c3*u = 0
c which implies:  c3 = -c1*u**2 - c2*u
c
c After the series of local cubics is defined, they will be transformed
c into global representation this will involve translation, rotation and
c a reparameterization. The new parameterization is w.r.t. the spline's
c cumulative choord length.
c
c See chapter 5 of the following report for more inFORMATION.
c
c Dolin, R. M., "The Wilson-Fowler Spline in a Global IGES Coordinate
c      Frame," Los Alamos National Laboratory Report Number
c      LA-11024-MS, September, 1987, Los Alamos, NM.
c
c-----
c
c
c      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
c      IMPLICIT INTEGER*4 (I-N)
c
cwb  PARAMETER(NCOEF=13, MXKNOTS=201, DEGRAD=0.01745329)
c      PARAMETER(NCOEF=13, MXKNOTS=201)
c
cwb  DIMENSION TAB(20*MXKNOTS),COEF(8,MXKNOTS),WFSPL(NCOEF,MXKNOTS)
c
c Determine if end angles are to be specified or computed. KK and LL
c are end angle flags. When they =1, end angles exist and =0 no end
c angles exist. The KK flag is for the entry and the LL flag for exit
c of the spline. When end angles (slopes) are given, they should be in
c radians. APT defines the slope to be the tangent of the start or end
c angles. Hence, what we want to give the APT routines is the Tangent
c of the end angles.
cwb  PI=4.0D0*DATAN(1.0D0)
c      DEGRAD=PI/180.0D0

```

```

cwb      DO 10 I = 1,18
          TAB(I) = 0.0D0
10 CONTINUE
c
      IF (IAFLG .EQ. 1) THEN
          TAB(1) = DTAN(ANGIN)
          TAB(2) = DTAN(ANGOUT)
          KK      = 1
          LL      = 1
      ELSE
          TAB(1) = 0.0D0
          TAB(2) = 0.0D0
          KK      = 0
          LL      = 0
      END IF
      NN      = NPTS*2 + 17
      J       = 1
      DO 100 I = 18,NN,2
          TAB(I) = WFSPL(2,J)
          TAB(I+1) = WFSPL(6,J)
          J       = J + 1
100 CONTINUE
c
c Define the necessary APT parameters. MM is a coordinate definer, =3
c => XY
c coordinate data. JJ is a T&R flag, =0 => no data translation or
c rotation.
      MM      = 3
      JJ      = 0
cwb      RESULT = 0.D0
c
c Load the through points into the APT array and compute the initial
c set of local intervals
c
      CALL APT088 (MM, NPTS, KK, LL, JJ, TAB,ANGIN,ANGOUT)
c
c Compute the series of local cubics defined over each through point
c interval.
c
      CALL APT089(TAB)
c
c Convert the series of local cubics into a global spline definition
c with a cumulative choord length parameterization. Begin by computing
c the linear term for each of the local cubic equations. The local cubic
c equation is
c

$$v(u) = C1*u**3 + C2*u**2 + C3*u$$

c
c The two global cubic equations are given as:
c

$$x(s) = Ax*s**3 + Bx*s**2 + Cx*s + Dx$$


$$y(s) = Ay*s**3 + By*s**2 + Cy*s + Dy$$

c where
c

$$Ax = -C1*\sin(\gamma), \quad Ay = C1*\cos(\gamma)$$


$$Bx = -C2*\sin(\gamma), \quad By = C2*\cos(\gamma)$$


$$Cx = C3*\sin(\gamma) + \cos(\gamma) \quad Cy = -C3*\cos(\gamma) + \sin(\gamma)$$


$$Dx = u \quad Dy = v$$

c and
c

$$\gamma = \text{atan}(Dv/Du)$$

c
c The coef array below is defined as Dx,Cx,Bx,Ax, Dy,Cy,By,Ay
c
      i=1,2,...,8
      NSIZE = 20 + (NPTS-2)*7
      J      = 1

```



```

DO 200 I = 20,NSIZE,7
  DXI = TAB(I+7) - TAB(I)
  DYI = TAB(I+8) - TAB(I+1)
  C1I = TAB(I+2)
  C2I = TAB(I+3)
  RLEN = TAB(I+4)
  C3I = -C1I*RLEN*RLEN - C2I*RLEN
  GAMMA = F5ATAN(DYI,DXI)
  GAMMA = GAMMA * DEGRAD
  COSG = DCOS(GAMMA)
  SING = DSIN(GAMMA)
C
C COMPUTE THE GLOBAL X-COEFFICIENTS
  COEF(4,J) = -C1I*SING ! THESE GLOBAL COEFFICIENTS
  COEF(3,J) = -C2I*SING ! ARE THE RESULT OF ROTATING
  COEF(2,J) = -C3I*SING + COSG ! THE LOCAL CUBIC EQUATION
  COEF(1,J) = TAB(I) ! INTO GLOBAL COORDINATES
C
C COMPUTE THE GLOBAL Y-COEFFICIENTS ! [X Y] = [u v(u) 1] [R]
  COEF(8,J) = C1I*COSG ! WHERE
  COEF(7,J) = C2I*COSG ! -COSG -SING
  COEF(6,J) = C3I*COSG + SING ! [R] = SING -COSG
  COEF(5,J) = TAB(I+1) ! XT YT
  J = J + 1
200 CONTINUE
C
C LOAD X AND Y DATA POINTS OF LAST POINT INTO COEFFICIENT ARRAY
c Use the coordinates of the last point to define end interval
  COEF(1,J) = TAB(I) ! THE NTH POINT HAS NO CUBIC
  COEF(5,J) = TAB(I+1) ! BUT THE KNOT POINT WILL BE USED
C
c Define the WFSPL array w.r.t. the global coefficients
DO 300 IG = 1,NPTS
  IF (IG.EQ. 1) THEN
    WFSPL(1,IG) = 0.0D0
  ELSE
    IT = 24 + (IG-2)*7
    WFSPL(1,IG) = TAB(IT) + WFSPL(1,IG-1)
  END IF
C
DO 350 JG = 1,8
  WFSPL(JG+1,IG) = COEF(JG,IG)
350 CONTINUE
300 CONTINUE
C
c Always compute the end angles after computing APT WF coefficients.
c Return angles in radians.
C IF (IAFLG.EQ. 0) CALL GET_ANG(WFSPL,NPTS, ANGIN,ANGOUT)
C
c MAN O MAn O Man.....O man
C
RETURN
END
SUBROUTINE APT089(TAB)
crmd
crmd-----
c**** SOURCE FILE : M0002233.V12 ***
c*
C.....FORTRAN SUBROUTINE ....APT089 8/68 HG,RN
C.....FORTRAN SUBROUTINE APT089... 3/1/68 GK
C PART 2 OF APT088
C FORTRAN SUBROUTINE APT089
C
C PURPOSE TO GENERATE THE CANONICAL FORM OF A TABULATED

```

```

C          CYLINDER DEFINED BY THE POINTS THROUGH WHICH IT
C          MUST PASS BY THE FOLLOWING APT STATEMENT
C          TABCYL/*, V, TRFORM, MI, P1, **, K1, P2,
C          P3, ..., PN, ***, KN
C          * = NOX, NOY, NOZ, XYZ, RTHETA, OR THETAR
C          ** = SLOPE OR NORMAL
C          *** = SLOPE OR NORMAL
C
C LINKAGE      CALL APT089 (A)
C
C
C ARGUMENTS    A          ARRAY CONTAINING THE INFORMATION NECESSARY
C                  TO PLACE THE TABCYL CANONICAL FORM ON TAPE
C                  AND LATER RETRIEVE IT FROM TAPE
C
C SUBSIDIARIES TYPE          ENTRY
C          SUBROUTINE        APT040
C          SUBROUTINE        APT087
C          SUBROUTINE        APT094
C          REAL FUNCTION      ATAN
C          REAL FUNCTION      ATAN2
C          LOGICAL FUNCTION    CKDEF
C          REAL FUNCTION      COS
C          SUBROUTINE        DOTF
C          SUBROUTINE        ERROR
C          REAL FUNCTION      MINO
C          REAL FUNCTION      SIN
C          REAL FUNCTION      SQRT
C          SUBROUTINE        TABTAP
C          LOGICAL FUNCTION    ZVECT
C
C          ADDITIONS FOR PRINT /TABPRT,ON OR OFF
C          TABPRT FLAG IS CHECKED EACH TIME BEFORE PRINTING
C          FLAG IS SET IN PRINT ROUTINE AND INITIALIZED IN APT227
c input:
c   TAB          ARRAY CONTAINING THE INFORMATION NECESSARY TO
c               GENERATE THE TABCYL CANONICAL FORM
c   TAB(1)       - Number of data locations (i.e., size of TAB array)
c   TAB(2-10)    - Rotation matrix (set to [I] for IS applications).
c   TAB(11)      - Number of through points including extension points.
c   TAB(12)      - 14.0 Yes, its that simple
c   TAB(13-19)   - Space for first extension interval (zero initially)
c   TAB(20)      - u1
c   TAB(21)      - v1
c   TAB(22)      - Slope of first segment
c   TAB(23)      - Segment angle of first segment
c   TAB(24)      - Segment length of first segment
c   TAB(25)      - None
c   TAB(26)      - None
c   :           :
c   :           :
c   TAB(13+7i)   - ui
c   TAB(14+7i)   - vi
c   TAB(15+7i)   - Slope of first segment
c   TAB(16+7i)   - Segment angle of first segment
c   TAB(17+7i)   - Segment length of first segment
c   TAB(18+7i)   - None
c   TAB(19+7i)   - None
c
c Comment lines with an rmd or cd monicker where added by Ron Dolin and
c comment lines with an RJG CG monicker where added by Ralph Gladfelter.
crmd-----
c
crmd      SUBROUTINE APT089(A)

```

```

C96      SUBROUTINE APT089(TAB, ANGIN,ANGOUT)
C
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      IMPLICIT INTEGER*4 (I-N)
C
CG      INCLUDE 'BLANKCOM.INC'
C
C      UNLABELLED COMMON
C
C---      SIZE OF BLANK COMMON IS ALLOCATED RIGHT HERE.
C
crmd      INTEGER COMSIZ,SSIZ
crmd      PARAMETER (COMSIZ=36000)
crmd      PARAMETER (SSIZ=20000)
crmd      DOUBLE PRECISION COM
crmd      DIMENSION COM(COMSIZ)
C
crmd      COMMON COM
C
crmd      DOUBLE PRECISION CANON,SSCAN,BCANON,CAN
crmd      DIMENSION CANON(COMSIZ),SSCAN(SSIZ),BCANON(SSIZ),CAN(SSIZ)
CG      EQUIVALENCE (COM(1),CANON(1))
CG      EQUIVALENCE (COM(41),SSCAN(1))
CG      EQUIVALENCE (COM(41),BCANON(1))
CG      EQUIVALENCE (COM(41),CAN(1))
C
C      END OF BLANKCOM.INC
crmd      LOGICAL CKDEF,ZVECT
crmd      DOUBLE PRECISION TAB(SSIZ)
CG      EQUIVALENCE (COM(41),TAB(1))
crmd      DIMENSION A(2),VV(3),DD(12),ROTM(9),TABLE(8)
crmd      DIMENSION TEM(1000)
C ADD RJG
CG      INCLUDE 'DARRAY.INC'
C
C      *** 20. DARRAY BLOCK ***
C
C      PRINT BUFFER
C
CG      INTEGER CPL
CG      PARAMETER (CPL=120)
CG      CHARACTER DARRAY*(CPL)
C
CG      COMMON/DARRAY/DARRAY
C
C      END OF DARRAY.INC
crmd      DOUBLE PRECISION DY1,DY2
crmd      DOUBLE PRECISION A1,B1,A2,B2,SL1,SL2
C
CG      INCLUDE 'TOTAL.INC'
C
C      THE ORIGINAL COMMON-DIMENSION-EQUIVALENCE (CDE) PACKAGE TOTAL
C      HAS BEEN REPLACED BY INDIVIDUAL COMMON BLOCKS, AND EQUIVALENCE
C      STATEMENTS HAVE BEEN ELIMINATED AS FAR AS POSSIBLE.
C
CG      INCLUDE 'DSHAR6.INC'
C
C      *** 6. DSHARE BLOCK 6 ***
C
CG      DOUBLE PRECISION B,C,D(12),DX1,DX2,SB,TEM(3),TEMP,V(3),X2,Y2
C
CG      COMMON/DSHAR6/B,C,D,DX1,DX2,SB,TEM,TEMP,V,X2,Y2
C
CG      SAVE /DSHAR6/

```

```

C
CG   INCLUDE 'ZNUMBR.INC'
crmd -The IS program implementation's arrays and parameters
      PARAMETER( MXKNOTS=201)
      DIMENSION TAB(20*MXKNOTS), TEM(MXKNOTS)
      DIMENSION A(2)
crmd96 DIMENSION CANON(COMSIZ), SSCAN(SSIZ), BCANON(SSIZ), CAN(SSIZ),
crmd96 D(12)
crmd96 DIMENSION VV(3),          DD(12),          V(3),          ROTM(9),
crmd96 TABLE(8)
C
C   *** 10.  ZNUMBR BLOCK ***
C
C   REAL LITERALS
C
CG   DOUBLE PRECISION  Z0,      Z1,      Z2,      Z3,      Z5,
CG   1                  Z10,      Z90,      Z1E6, Z1E38, Z5EM1,
CG   2                  Z6EM1, Z9EM1,Z11EM1,Z12EM1, Z1EM2,
CG   3                  Z1EM3, Z1EM5, Z5EM6, Z1EM6, Z1EM7,
CG   4                  Z1EM9, Z1EM1,  ZM1,DEGRAD,  PI
C
CG   COMMON/ZNUMBR/     Z0,      Z1,      Z2,      Z3,      Z5,
CG   1                  Z10,      Z90,      Z1E6, Z1E38, Z5EM1,
CG   2                  Z6EM1, Z9EM1,Z11EM1,Z12EM1, Z1EM2,
CG   3                  Z1EM3, Z1EM5, Z5EM6, Z1EM6, Z1EM7,
CG   4                  Z1EM9, Z1EM1,  ZM1,DEGRAD,  PI
C
CG   INCLUDE 'LDEF.INC'
      PARAMETER (Z1EM9 = 1.0D-9)
C
C   *** 11.  LDEF BLOCK ***
C
C   LOGICAL VARIABLES WHICH MUST REMAIN INVIOLEATE
C
CG   LOGICAL JCS,PRNTON,REFFLG,SUBFLG,UNFLAG,ZFLAG,JDS,
CG   1          BOUNDF,PCHLST,CANFLG,BNDERR,TABPRT,REFMOT,ALTMLT
C
CG   COMMON/LDEF/JCS,PRNTON,REFFLG,SUBFLG,UNFLAG,ZFLAG,JDS,
CG   1          BOUNDF,PCHLST,CANFLG,BNDERR,TABPRT,REFMOT,ALTMLT
C
CG   INCLUDE 'ISHR17.INC'
C
C   *** 17.  ISHARE17 BLOCK ***
C
C   TABCYL SHARED INTEGER VARIABLES
C   SOME OF THESE MAY BE ONLY USED AS LOCAL VARIABLES
C
      INTEGER      I,INC,I1,J,J1,K,L,LIM,L1,M,N,NM1
      COMMON/ISHR17/I,INC,I1,J,J1,K,L,LIM,L1,M,N,NM1
C
CG   SAVE /ISHR17/
C
CG   INCLUDE 'KNUMBR.INC'
C
C   *** 19.  KNUMBR BLOCK ***
C
C   INTEGER LITERALS
C
CG   INTEGER      K0,      K1,      K2,      K3,      K4,      K5,      K6,      K7,
CG   1            K8,      K9,      K10,     K12,     K13,     K15,     K16,     K18,
CG   2            K19,     K23,     K24,     K25,     K26,     K27,     K29,     K30,
CG   3            K31,     K32,     K33,     K34,     K44,     K45,     K46,     K47,
CG   4            K48,     K50,     K51,     K52,K1013, K1E4, K1E6, KM1
C

```

```

CG      COMMON/KNUMBR/   K0,   K1,   K2,   K3,   K4,   K5,   K6,   K7,
CG  1      K8,   K9,  K10,  K12,  K13,  K15,  K16,  K18,
CG  2      K19, K23, K24, K25, K26, K27, K29, K30,
CG  3      K31, K32, K33, K34, K44, K45, K46, K47,
CG  4      K48, K50, K51, K52,K1013, K1E4, K1E6, KM1
C
C
      DOUBLE PRECISION A1, B1, A2,B2,SL1,SL2

crmd
crmd -The following two data statements were added to define the numbers
crmd used by this sub_routine.
crmd
      DATA K1,   K4,   K7, K15
1      /1,      4,      7, 15/

crmd
      DATA Z0,      Z1,      Z2,
1      ZM1 , Z1EM3 , Z1EM7
2      /0.D0, 1.D0, 2.D0,
3      1.0D-1, 1.0D-3, 1.0D-7/
cwb 1      Z1EM3, Z1EM7, ZM1,   DEGRAD,   PI
cwb 3      1.0E-3, 1.0E-7, 1.0E-1, 0.01745329, 3.141592653589793/
crmd96
c96      DATA K0,   K1,   K2,   K3,   K4,   K5,   K6,   K7,
c96  1      K8,   K9,  K10,  K12,  K13,  K15,  K16,  K18,
c96  2      K19, K23, K24, K25, K26, K27, K29, K30,
c96  3      K31, K32, K33, K34, K44, K45, K46, K47,
c96  4      K48, K50, K51, K52,K1013, K1E4, K1E6, KM1
c96  5      /0,1,2,3,4,5,6,7,8,9,10,12,13,15,16,18,19,23,24,25,26,
c96  6      27,29,30,31,32,33,34,44,45,46,47,48,50,51,52,
c96  7      1013,1E4,1E6,-1 /

crmd
c96      DATA Z0,      Z1,      Z2,      Z3,      Z5,
c96  1      Z10, Z90, Z1E6, Z1E38, Z5EM1,
c96  2      Z6EM1, Z9EM1,Z11EM1, Z12EM1, Z1EM2,
c96  3      Z1EM3, Z1EM5, Z5EM6, Z1EM6, Z1EM7,
c96  4      Z1EM9, Z1EM1, ZM1,   DEGRAD, PI
c96  5      /0.D0, 1.D0, 2.D0, 3.D0, 5.D0, 10.D0, 90.D0, 1.0E6,
c96  6      1.0E38, 5.0E-1, 6.0E-1, 9.0E-1,
c96  7      11.0E-1, 12.0E-1, 1.0E-2, 1.0E-3,
c96  8      1.0E-5, 5.0E-6, 1.0E-6, 1.0E-7,
c96  9      1.0E-9, 1.0E-1, -1.0, 0.01745329,
c96 &      3.141592653589793/

crmd
CG      INCLUDE 'XUNITS.INC'
C
CG      DOUBLE PRECISION TABEXT,SSEXT
CG      INTEGER IOLD
CG      CHARACTER*6 OLDMOD
C
CG      COMMON/XUNITS/TABEXT,SSEXT,IOLD
CG      COMMON/XUNITC/OLDMOD
C
C      END OF XUNITS.INC
C
CG      EQUIVALENCE (TAB(2),ROTM(1))
C
CG      CHARACTER FORM1*112,FORM2*92,FORM3*120,FORM4*28
CG      CHARACTER FORM5*4,FORM7*16,FORM9*100
C
CG      DATA FORM1/
CG  1' NUM      THETA      RADIUS      X-CORD      Y-CORD
CG  2      SEG LENGTH      SEG ANGLE      EXT ANGLE' /
CG      DATA FORM2/
CG  1' NUM      SLOPE      NORMAL      ALPHA      TANGENT A      TANGENT B

```

```

CG 2 CURVA DELTA CURV '/'
CG DATA FORM3/
CG 1' CURVATURE .+.....+.
CG 2...+.....+.
CG DATA FORM4/' EXTENSION INTERSECTION U= '/'
CG DATA FORM5/' V= '/'
CG DATA FORM7/' ROTATION MATRIX'/
CG DATA FORM9/
CG 1'0 U V A B L
CG 2'ENGTH MAX MIN '/'
crmd
crmd - Need these two data statements for IS applications
crmd96 DATA TABLE /0.05D0, 0.1D0, 0.2D0, 0.5D0, 1.D0, 2.D0, 5.D0, 10.D0/
crmd
crmd
crmd - Let the games begin. The first section defines local functions
crmd that are used by this sub_routine. They represent equations from
crmd the original Fowler and Wilson report.
C ARITHMETIC STATEMENT FUNCTIONS
c
c96 DOUBLE PRECISION DX1, DX2, DY1,DY2
crmd96 DATA ZLIT2, ZLIT3, ZLIT4, ZLIT6 /1.D10, 50.D0, 52.5001D0, 5.D-5/
DATA ZLIT2 /1.0D10/
C
crmd96 DATA K21, K14, ZLIT1 /21, 14, .707D0/
crmd
crmd - This function returns the smaller of either the input number or
crmd 1e-9.
crmd The reason for this function is to insure that we never get into a
crmd numerical divide by zero situation.
crmd
SMAL(Z1)=DSIGN(DMAX1(DABS(Z1),Z1EM9),Z1)
c
crmd - The following functions compute the slope, tangent and curvature
crmd of the input variables. The function assumes knowledge of the
crmd delta X's and Y's for the interval represented by Z1 and Z2.
CRJG - THE EQUATION USED BY THIS FUNCTION IS EQUIVALENT TO EQUATION 9 OF
CRJG THE Y-1400 "CUBIC SPLINE, A CURVE FITTING ROUTINE REPORT BY FOWLER
CRJG AND WILSON"
c
C96 These following functions were moved into their own function
C96 statements outside of this subroutine. This subroutine can then
c96 call them.
C96 SLOP(Z1) = (DY2+DY1*Z1) / SMAL(DX2+DX1*Z1)
C96 TAN(Z1) = DSIN(Z1) / SMAL(DCOS(Z1))
C96 CRVA(Z1,Z2,Z3)=- (4.*TAN(Z1)+2.*TAN(Z2))*DABS(DCOS(Z1))**3 /Z3
C
crmd -The following function computes the difference in curvature at a
crmd given through point. There are two measures of curvature at each
crmd through point, the interval to the left and the interval to the
crmd right both have curvatures that need to be compared so that they
crmd can be checked for convergence. It calls function CRVA from
crmd above.
CRJG -THE FOLLOWING EQUATION IS EQUIVALENT TO EQUATION 18 OF THE Y-1400
CRJG CUBIC SPLINE, A CURVE FITTING ROUTINE REPORT BY FOWLER AND WILSON
C
CURV(SL1,SL2) = CRVA(A2,B2,SL2) + CRVA(B1,A1,SL1)
c
crmd -A majority of the sub_routine is not necessary for the partical
crmd application of the APT WF-spline representation that we have and
crmd is therefore commented out. The only functionality that we really
crmd need, the data manipulation and initial data calculation necessary
crmd to run the WF algorithm.
crmd We decided not to move lines around, so read carefully to see what

```

```

crmd has been commented out and what has not. The next hundred or so
crmd lines have executable lines intermixed.
Cwb
    PI=4.0D0*DATAN(1.0D0)
    DEGRAD=PI/180.0D0
Cwb
    L1=0
    560 DCMAX =Z0
crmd
crmd -Find the maximum value of the delta curvature at each of the 2nd to
crmd n-1 through point intervals.
crmd
    DO 570 I1=14,NM1,7
    IF (DABS(TAB(I1+18)).LT.DCMAX) GO TO 570
    DCMAX = DABS(TAB(I1+18))
    J1=I1
    570 CONTINUE
crmd
crmd -If all the interval delta curvatures where less than 1e-3, we can
crmd skip the curvature minimization stuff. However, if even one
crmd through point interval did not have continous curvatuue, we must
crmd minimize it. If several intervals had discontinous curvatures,
crmd minimize the interval that was the most outta whack.
crmd
C MINIMIZE MAXIMUM CURVATURE, USING NEWTON'S METHOD
cwb IF (DCMAX.LE.Z1EM3 .OR. L1.GE.K4*I) GO TO 640
IF (DCMAX.LE.Z1EM9 .OR. L1.GE.K4*I) GO TO 640
    A1 = TAB(J1+8) - TAB(J1+9)
    A2 = TAB(J1+15) - TAB(J1+16)
    B2 = TAB(J1+22) - TAB(J1+16)
    DCP = -4.D0*(TAB(J1+10)+TAB(J1+17)) / TAB(J1+10)/TAB(J1+17)
cwb DCP = -4.*(TAB(J1+10)+TAB(J1+17)) / TAB(J1+10)/TAB(J1+17)
crmd
C OBTAIN NEW APPROXIMATION FOR SLOPE AT P(J1), and a NEW CURVATURE
cwb DO 580 I1 = 1,4
DO 580 I1 = 1,25
    A2=DATAN(TANGENT(A2)-TAB(J1+18)/DCP)
    TAB(J1+15) = A2 +TAB(J1+16)
    B1 = TAB(J1+15) - TAB(J1+9)
    TAB(J1+18) = CURV(TAB(J1+10),TAB(J1+17))
    IF (DABS(TAB(J1+18)) .LE. Z1EM9) GO TO 590
    580 CONTINUE
crmd
crmd -Changes to the slope and curvature at the ith interval impacts the
crmd computed slope and curvature at the i-1st and i+1st intervals,
crmd which in turn impacts their j-1st and j+1st intervals. In other
crmd words, changing the slope and curvature in one interval can impact
crmd all others.
C CHANGE IN A2 - CHANGE IN CURVATURE AT P(J1-1), P(J1+1)
C AT START OR END OF TABCYL, REFLECT ANGLE
    590 X2 = A2
    Y2 = B2
    L1 = L1 + K1
crmd
crmd -The first computed goto directs work depending on whether the
crmd start angle has been specified (e.g., 610 => no start angle). The
crmd second computed goto directs flow depending on whether the end
crmd angle has been specified.
    IF (J1+K-K15)620,630,600
    600 IF(J1+L-NM1) 610,601,630
    601 B2 = PI - A2
    TAB(I-6) = TAB(I-12) + B2
    TAB(I-10) = CURV(TAB(I-18),TAB(I-11))
    610 A2 = A1

```

```

        B2          = B1
        A1          = TAB(J1+1) - TAB(J1+2)
        B1          = TAB(J1+8) - TAB(J1+2)
        TAB(J1+11) = CURV(TAB(J1+3),TAB(J1+10))
        GO TO 630
crmd
620 A1          = PI - B1
    TAB(22) = TAB(23) + A1
    TAB(32) = CURV(TAB(24),TAB(31))
crmd
630 IF (J1 .EQ. NM1) GO TO 560
    A1          = X2
    B1          = Y2
    A2          = TAB(J1+22)-TAB(J1+23)
    B2          = TAB(J1+29)-TAB(J1+23)
    TAB(J1+25) = CURV(TAB(J1+17),TAB(J1+24))
    GO TO 560
crmd
C SAVE END SLOPES AND WRITE OUT DATA --- not!!
640 IF(L .NE. 0) GO TO 642
    A1          =TAB(I-20) -TAB(I-19)
    B1          =TAB(I-13) -TAB(I-19)
    A2          =TAB(I-13) -TAB(I-12)
    B2          = PI - A2
    TAB(I-6)    = TAB(I-12) + B2
    TAB(I-10)   = CURV(TAB(I-18),TAB(I-11))
crmd
crmd -We are now done computing the WF spline wrt a series of peicewise
crmd local cubics. The task before us now is compute the cubic equation
crmd that can define the spline.
crmd Since end angles exist, use them. SB is the entry splope and SE2
crmd is the exit slope.
    642 SB      = TANGENT(TAB(22))
        SE2    = TANGENT(TAB(I-6))
crmd      ANGIN = SB
crmd      ANGOUT= SE2
crmd
C CHECK TABPRT FLAG
CG      IF(TABPRT) GO TO 643
C...      CALL PRINT TO OUTPUT ISN AND TABCYL IDENTIFICATION INFORMATION
CG      CALL PRINT(15,A,1)
C
CG      CALL CFORM(FORM1,DARRAY,1,112)
CG      CALL CPRINT(DARRAY)
crmd
crmd The following do-loop computes the polar coordinates of each set of
crmd through points. Perform the conversion because the polar angle is
crmd used in the next set of executables
C96 The below call used to be "CALL APT0897(TEM,TAB(J1+13))"
    643 DO 672 I1=1,N
        J1 = K7 * I1
        CALL APT087(TEM(1),TAB(J1+13))
        TAB(J1+19) = TEM(2)
crmd
C CHECK TABPRT FLAG
CG      IF(TABPRT) GO TO 672
C GA IS SEGMENT ANGLE, XA EXTERIOR ANGLE
crmd      GA1 = GA
crmd      IF (I1 .EQ. N) GO TO 650
crmd      GA = TAB(J1+16) / DEGRAD
crmd      IF (I1 .EQ. K1) GO TO 660
crmd      XA = GA - GA1
crmd      IF(DABS(XA) .GT. Z2*Z90) XA = XA - DSIGN(360.0D0,XA)
CG      GO TO 670

```



```

C NO SEGMENT ANGLE FOR LAST POINT
crmd 650 GA = Z0
crmd 660 XA = Z0
CR670 CALL ICONV(I1,DARRAY,1,4)
CG CALL FCONV(TEM(2),DARRAY,5,15,4)
CG CALL FCONV(TEM(1),DARRAY,20,15,6)
CG CALL FCONV(TAB(J1+13),DARRAY,35,15,6)
CG CALL FCONV(TAB(J1+14),DARRAY,50,15,6)
CG CALL FCONV(TAB(J1+17),DARRAY,65,15,6)
CG CALL FCONV(GA,DARRAY,80,15,4)
CG CALL FCONV(XA,DARRAY,95,15,4)
CG CALL CPRINT(DARRAY)
672 CONTINUE
crmd
crmd -Next set of instructions. Find the maximum and minimum curvatures
C WRITE MATCHED CURVATURES
C CHECK TABPRT FLAG
CG IF(TABPRT) GO TO 674
CG CALL CFORM('0',DARRAY,1,1)
CG CALL CFORM(FORM2,DARRAY,2,92)
CG CALL CPRINT(DARRAY)
crmd
674 CMIN = ZLIT2
CMAX = -ZLIT2
DO 690 I1=1,N
J1 = K7*I1
IF (I1 .EQ. N) GO TO 675
TA = TAB(J1+15) - TAB(J1+16)
TB = TAB(J1+22) - TAB(J1+16)
TEM(2) = CRVA(TA,TB,TAB(J1+17))
GO TO 680
675 TA = Z0
TB = Z0
TAB(25) = Z0
TEM(2) = 0.0D0
680 TA = TANGENT(TA)
TB = TANGENT(TB)
TAB(J1+15) = TANGENT(TAB(J1+15))
PHI = DATAN(ZM1/SMAL(TAB(J1+15))) / DEGRAD
AL = PHI -TAB(J1+19)
TAB(J1+19) = TEM(2)
C CHECK TABPRT FLAG
CG IF(TABPRT) GO TO 685
CG CALL ICONV(I1,DARRAY,1,4)
CG CALL FCONV(TAB(J1+15),DARRAY,5,12,5)
CG CALL FCONV(PHI,DARRAY,17,12,4)
CG CALL FCONV(AL,DARRAY,29,12,4)
CG CALL FCONV(TA,DARRAY,41,12,7)
CG CALL FCONV(TB,DARRAY,53,12,7)
CG CALL FCONV(TAB(J1+19),DARRAY,65,10,4)
CG CALL FCONV(TAB(J1+18),DARRAY,75,13,4)
CG CALL CPRINT(DARRAY)
C PLOT CURVATURES
685 TAB(J1+15) = TA
TAB(J1+16) = TB
CMIN = DMIN1(CMIN,TAB(J1+19))
690 CMAX = DMAX1(CMAX,TAB(J1+19))
crmd
crmd -Next set of instructions.
crmd CEN2 = (CMAX-CMIN) / Z2
crmd DO 700 J1=1,7
crmd I1 = J1
crmd IF (CEN2 .LE. TABLE(J1)) GO TO 710
crmd 700 CONTINUE

```

```

crmd      I1      = 8
crmd 710 CURVRG = TABLE(I1)
crmd      CEN1    = 50.0 / CURVRG
crmd      CENTER  = CEN2 + CMIN
crmd      IDUMY   = CENTER*CEN1 + DSIGN(Z5EM1,CENTER)
crmd      CENTER  = IDUMY
crmd      CENTER  = CENTER / CEN1
crmd      CURTI1  = CENTER -CURVRG
crmd      CURTI2  = CENTER - Z5EM1*CURVRG
crmd      TEMP    = CENTER + Z5EM1*CURVRG
crmd      TEM(1)  = CENTER + CURVRG
C CHECK TABPRT FLAG
CG      IF(TABPRT) GO TO 732
CG      CALL CFORM('0',DARRAY,1,1)
CG      CALL FCONV(CURTI1,DARRAY,17,7,4)
CG      CALL FCONV(CURTI2,DARRAY,42,7,4)
CG      CALL FCONV(CENTER,DARRAY,67,7,4)
CG      CALL FCONV(TEMP,DARRAY,92,7,4)
CG      CALL FCONV(TEM(1),DARRAY,113,7,4)
CG      CALL CPRINT(DARRAY)
C
CG      CALL CFORM(FORM3,DARRAY,1,119)
CG      CALL CPRINT(DARRAY)
crmd      KP=K7*N
CG      DO 730 I1=7,KP,7
CG      CALL CFORM('.',DARRAY,18,1)
CG      CALL CFORM('.',DARRAY,119,1)
CG      J1=ZLIT4-ZLIT3*CENTER/CURVRG
CG      J1=MIN0(MAX0(J1,2),102)+17
CG      CALL CFORM('.',DARRAY,J1,1)
CG      J1=ZLIT3*(TAB(I1+19)-CENTER)/CURVRG+ZLIT4
CG      J1=MIN0(MAX0(J1,2),102)+17
CG      CALL CFORM('*',DARRAY,J1,1)
CG      L1=I1/7
CG      CALL ICONV(L1,DARRAY,1,3)
CG      CALL FCONV(TAB(I1+19),DARRAY,4,12,6)
CG 730 CALL CPRINT(DARRAY)
CG      CALL CFORM(FORM3(17:),DARRAY,17,103)
CG      CALL CPRINT(DARRAY)
crmd
C FIT CUBICS TO GIVEN SLOPES - TRANSLATE AND ROTATE TO ELIMINATE
C CONSTANT TERM
732 DO 771 I1 = 7,NM1,7
      TLENGT = TAB(I1+17)
      S1      = TAB(I1+15)
      T1      = TAB(I1+16)
C COMPUTE COEFFICIENTS OF CUBIC, STORE IN TAB ARRAY, A, B, and C
      TAB(I1+15) = (T1+S1) / TAB(I1+17)**2
      TAB(I1+16) = (-Z2*S1-T1) / TAB(I1+17)
      TAB(I1+17) = S1
C COMPUTE MAXIMUM AND MINIMUM VALUES ON EACH CURVE
      IF (DABS(TAB(I1+15)) .GT. Z1EM9) GO TO 750
      TAB(I1+19) = Z0
      TAB(I1+15) = Z0
      IF(DABS(TAB(I1+16)) .GT. Z1EM9) GO TO 740
C EQUATION IS LINEAR - MUST BE Y = 0
      TAB(I1+16) = Z0
      TAB(I1+17) = Z0
      TAB(I1+18) = Z0
      GO TO 770
C EQUATION IS QUADRATIC - EXTREMUM AT -C/2B
740 TAB(I1+18) = -TAB(I1+17)**2 / (4.0D0*TAB(I1+16))
cwb740 TAB(I1+18) = -TAB(I1+17)**2 / (4.*TAB(I1+16))
      GO TO 760

```

```

C EQUATION IS CUBIC - SOLVE FOR FIRST DERIVATIVE ZERO
750  TEMP = TAB(I1+16)**2
      TEM1 = 3.0D0 * TAB(I1+15) * S1
cwb  TEM3 = (TEMP-TEM1)* DSQRT(TEMP-TEM1) * 2.0
      TEM3 = (TEMP-TEM1)* DSQRT(TEMP-TEM1) * 2.0D0
      TEM2 = TAB(I1+16) * (2.0D0*TEMP-3.0D0*TEM1)
cwb  TEM2 = TAB(I1+16) * (2.*TEMP-3.*TEM1)
      TEM4 = TEM2 + DSIGN(TEM3,TEM2)
      TEM3 = S1**2 * ((4.D0/3.D0)*TEM1-TEMP)
cwb  TEM3 = S1**2 * (1.3333333*TEM1-TEMP)
      TEMP = TEM4 / ((TAB(I1+15)**2)*27.0D0)
cwb  TEMP = TEM4 / ((TAB(I1+15)**2)*27.)
      IF(Z1) 760,760,755
755  CONTINUE
      TEM1 = TEM3 / TEM4
      TAB(I1+18) = TEMP
      TAB(I1+19) = TEM1
C TEST FOR MAX GREATER THAN MIN
760  IF(TAB(I1+18) .GE. TAB(I1+19)) GO TO 769
      TEMP = TAB(I1+18)
      TAB(I1+18) = TAB(I1+19)
      TAB(I1+19) = TEMP
C MAX OR MIN MUST BE WITHIN INTERVAL
769  IF(S1.LE.Z0 .AND. T1.GE.Z0) TAB(I1+18) = Z0
      IF (S1.GE.Z0 .AND. T1.LE.Z0) TAB(I1+19) = Z0
770  TAB(I1+18) = TAB(I1+18) / TLENGT
      TAB(I1+19) = TAB(I1+19) / TLENGT
      TAB(I1+17) = TLENGT
771 CONTINUE
crmd
C COMPUTE EXTENSION INTERVALS
C EXTENSION EQUIVALENT TO 10 INCH. REGARDLESS OF UNITS
crmd  DST = TABEXT
crmd  DELTA = DST / DSQRT(Z1+SB**2)
crmd  IF ((TAB(21)-TAB(28))*SB+TAB(20)-TAB(27).LT.Z0) DELTA = -DELTA
crmd  TAB(13) = TAB(20) + DELTA
crmd  TAB(14) = TAB(21) + DELTA*SB
crmd  DELTA = DST / DSQRT(Z1+SE2**2)
crmd  IF ((TAB(I-7)-TAB(I-14))*SE2+TAB(I-8)-TAB(I-15).LT.Z0)DELTA=-crmd DELTA
crmd  TAB(I-1) = TAB(I-8) + DELTA
crmd  TAB(I) = TAB(I-7) + DELTA*SE2
crmd  DO 780 I1=15,19
crmd  TAB(I1) = Z0
crmd  J1 = K7*N + I1
crmd 780 TAB(J1) = Z0
C REDUCE EXTENSION IF NECESSARY
crmd  IF (DABS(SB-SE2) .LT. ZLIT6) GO TO 790
crmd  X = (TAB(I-7)-TAB(14)+SB*TAB(13)-SE2*TAB(I-8)) / (SB-SE2)
crmd  A1 = X - TAB(13)
crmd  B1 = SB * A1
crmd  IF ( A1**2+B1**2 .GT. DST**2 ) GO TO 790
crmd  Y = B1 + TAB(14)
crmd  IF ( (X-TAB(I-8))**2+(Y-TAB(I-7))**2.GT.DST**2 ) GO TO 790
crmd  IF ((X-TAB(20))*(TAB(27)-TAB(20))
crmd 1 + (Y-TAB(21))*(TAB(28)-TAB(21)).GT.Z0) GO TO 790
crmd  IF ((X-TAB(I-8))*(TAB(I-15)-TAB(I-8))
crmd 1 + (Y-TAB(I-7))*(TAB(I-14)-TAB(I-7)).GT.Z0) GO TO 790
crmd  TAB(13) = X-Z1EM2 * (X-TAB(20))
crmd  TAB(14) = Y-Z1EM2 * (Y-TAB(21))
crmd  TAB(I-1) = X-Z1EM2 * (X-TAB(I-8))
crmd  TAB(I) = Y -Z1EM2* (Y-TAB(I-7))
CG  CALL CFORM(FORM4,DARRAY,1,26)
CG  CALL FCONV(X,DARRAY,27,15,8)
CG  CALL CFORM(FORM5,DARRAY,46,3)

```

```

CG      CALL FCONV(Y,DARRAY,49,15,8)
CG      CALL CPRINT(DARRAY)
crmd 790 TAB(17) = DSQRT((TAB(20)-TAB(13))**2 + (TAB(21)-TAB(14))**2)
crmd     TAB(I-4) = DSQRT((TAB(I)-TAB(I-7))**2 + (TAB(I-1)-TAB(I-8))**2)
C CHECK TABPRT FLAG
CG      IF(TABPRT) GO TO 796
CG      CALL CFORM(FORM7,DARRAY,1,16)
CG      CALL CPRINT(DARRAY)
crmd     L=1
CG      DO 791 I1=2,10
CG      CALL FCONV(TAB(I1),DARRAY,L,13,6)
CG 791 L=L+13
CG      CALL CPRINT(DARRAY)
CG      CALL CFORM(FORM9,DARRAY,1,100)
CG      CALL CPRINT(DARRAY)
CG      DO 9095 I1=13,I,7
CG      L=1
CG      DO 9096 J1=1,7
CG      L1=I1+J1-1
CG      IF(L1.GT.I) GO TO 9094
CG      CALL FCONV(TAB(L1),DARRAY,L,15,8)
C 9096 L=L+15
CG 9094 CALL CPRINT(DARRAY)
9095 CONTINUE
796 A(2)=TAB(1)
CG      CALL APT094(1,A(1),TAB(1))
      RETURN
      END
      LOGICAL FUNCTION CKDEF(ARG)

C
C*****
C*** SOURCE FILE : CKDEF000.V01 ***
C
C
C * CKDEF *
C
C LOGICAL FUNCTION CKDEF
C
C PURPOSE TO DETERMINE THAT THE ARGUMENT IS PROPERLY DEFINED
C          THE VALUE .FALSE. IS RETURNED IF DEFINED,.TRUE. OTHERWISE
C
C
C Modified for FORTRAN 90 by Ron Dolin on 12/96.....goal was to not
C change source code or programming at all.
C*****
C
CG      INCLUDE 'SDP.INC'
C
      INTEGER*4 ARG(2),STR,DTR,ASH,I3,I2
      LOGICAL FIRST
      SAVE STR,DTR,ASH,FIRST

C
      DATA FIRST/.TRUE./
      DATA NBCHAR /0/

C
      IF (FIRST) THEN
        I3=3*NCHAR
        I2=2*NCHAR
        STR=ISHFT(ICHAR('*'),I3)+ISHFT(ICHAR('T'),NBCHAR)+ICHAR('R')
        DTR=ISHFT(ICHAR('$'),I3)+ISHFT(ICHAR('T'),NBCHAR)+ICHAR('R')
        ASH=ISHFT(ICHAR('A'),I3)+ISHFT(ICHAR('S'),I2)
      +   +ISHFT(ICHAR('H'),NBCHAR)
        FIRST=.FALSE.
      ENDIF

```

```

C      IF ((ARG(1).EQ.STR).AND.(ARG(2).EQ.ASH)) THEN
C          CKDEF=.TRUE.
CG      CALL ERROR(1,'CKDEF  ')
C      ELSE IF ((ARG(1).EQ.DTR).AND.(ARG(2).EQ.ASH)) THEN
C          CKDEF=.TRUE.
C      ELSE
C          CKDEF=.FALSE.
C      END IF
C      RETURN
C      END
C      SUBROUTINE DOTF (RESULT,ARG1,ARG2)

C
C-----
C*** SOURCE FILE : M0002836.V02    ***
C
C.....FORTRAN SUBROUTINE          DOTF.....          5/1/68    GK
C          THE FIRST INPUT VECTOR
C          ARG2    ARRAY CONTAINING THE CANONICAL FORM OF
C          THE SECOND INPUT VECTOR
C
C SUBSIDIARIES TYPE          ENTRY
C          LOGICAL FUNCTION    CKDEF
C          SUBROUTINE          ERROR
C-----
C
C
C      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
C      IMPLICIT INTEGER*4 (I-N)
C
C      DIMENSION ARG1(3),ARG2(3),DS(6),IARG1(2),IARG2(2)
cwb  DOUBLE PRECISION DS
C      LOGICAL CKDEF
C
CG      INCLUDE 'TOTAL.INC'
CG      INCLUDE 'ZNUMBR.INC'
CG      INCLUDE 'KNUMBR.INC'
C
C
C96  Need to have the input variable for CKDEF to be an integer so
C96  convert...
C      IARG1(1) = ARG1(1)
C      IARG1(2) = ARG1(2)
C      IARG2(1) = ARG2(1)
C      IARG2(2) = ARG2(2)
C      IF (CKDEF(IARG1).OR.CKDEF(IARG2)) GO TO 20
C
C...    MOVE ARGUMENTS TO DOUBLE PRECISION SCRATCH LOCATIONS
C
C      DO 10 I=1,3
C          DS(I) = ARG1(I)
C          DS(I+3)= ARG2(I)
C10  CONTINUE
C
C...    COMPUTE DOT PRODUCT
C
C      RESULT = DS(1)*DS(4) +DS(2)*DS(5) +DS(3)*DS(6)
C      GO TO 9
C
C...    ISSUE DIAGNOSTIC, INPUT UNDEFINED, RESULT=0
C
CG 20 CALL ERROR (10,'DOTF  ')
C20 CONTINUE
C      RESULT = 0.0D0

```

```

C
  9 RETURN
    END
    FUNCTION SMAL(Z1)
C
C96-----
C96 FUNCTION SMAL(Z1) - This function returns the smaller of either the
C96 input number or 1e-9. The reason for this function is to insure
C96 that we never get into a numerical divide by zero situation.
C96
C96 Yanked out of the main software body and put into its own function
C96 by Ron Dolin as part of the FORTRAN 90 upgrade on 12/9/96
C96 This was not a full logic upgrade, just enough to get the program
C96 running.
C96-----
C
    IMPLICIT DOUBLE PRECISION (A-H,O-Z)
    PARAMETER (Z1EM9 = 1.0D-9)
CWB    PARAMETER (Z1EM9 = 1.0E-9)
C
    SMAL = DSIGN(DMAX1(DABS(Z1),Z1EM9),Z1)
C
    RETURN
    END
    FUNCTION SLOP088(Z1,Z2,DX1,DX2,DY1,DY2)
C
C96-----
C96 FUNCTION SLOP088 (Z1,Z2,DX1,DX2,DY1,DY2) - This function computes
C96 the slope of the Z1 interval. The DX and DY variables are local
C96 coord lengths on either side of the interval being evaluated. This
C96 is the slope function that is used in subroutine APT088.
C96
C96 Created by Ron Dolin as part of the FORTRAN 90 upgrade on 12/9/96
C96 This was not a full logic upgrade, just enough to get the program
C96 running.
C96-----
C
    IMPLICIT DOUBLE PRECISION (A-H,O-Z)
C
    SLOP088 = (Z1*DY2+Z2*DY1) / SMAL(Z1*DX2+Z2*DX1)
C
    RETURN
    END
    FUNCTION TANGENT(Z1)
C
C96-----
C96 FUNCTION TANGENT (Z1) - This function computes the tangent of
C96 the Z1 interval. The function was renamed from TAN to TANGENT
C96 because the new compiler did not like overwriting a preexisting
C96 function name.
C96
C96 Created by Ron Dolin as part of the FORTRAN 90 upgrade on 12/9/96
C96 This was not a full logic upgrade, just enough to get the program
C96 running.
C96-----
C
    IMPLICIT DOUBLE PRECISION (A-H,O-Z)
C
    TANGENT = DSIN(Z1) / SMAL(DCOS(Z1))
C
    RETURN
    END
    FUNCTION CRVA(Z1,Z2,Z3)
C

```

```

C96-----
C96  FUNCTION CRVA (Z1,Z2,Z3) - This function computes the curvature of
C96  and interval.
C96
C96  Created by Ron Dolin as part of the FORTRAN 90 upgrade on 12/9/96
C96  This was not a full logic upgrade, just enough to get the program
C96  running.
C96-----
C
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
C
      CRVA= -(4.D0*TANGENT(Z1)+2.D0*TANGENT(Z2))*DABS(DCOS(Z1))**3 /Z3
cwb  CRVA = -(4.*TANGENT(Z1)+2.*TANGENT(Z2))*DABS(DCOS(Z1))**3 /Z3
C
      RETURN
      END
      SUBROUTINE GET_SPLPT(SPLINE,IKNOT,S,X,Y)
C-----
C      GET_SPLPT(SPLINE,IKNOT,S, X,Y) - Computes the coordinates for an
c input spline. The variables are:
C
c INPUT:  SPLINE - Spline from which parametric definition is specified
c          IKNOT  - Knot point interval that computed point lies in.
c          S      - Parametric distance from start of interval that pt
c                  lies.
c OUTPUT: X      - X-coordinate of computed point.
c          Y      - Y-coordainte of computed point.
C
c Written by Ron Dolin begining 7/21/92
C-----
C
      IMPLICIT DOUBLE PRECISION (A-H, O-Z)
      IMPLICIT INTEGER*4 (I-N)
      PARAMETER (NCOEF=13, MXKNOTS=201)
C
cwb
      COMMON /WSPNRLT/ XOUT,YOUT,DXTNVT,DYTNVT,CRDLNG
      DOUBLE PRECISION XOUT,YOUT,DXTNVT,DYTNVT,CRDLNG
C
      COMMON /WSPNFSD/ DX,DY,DDX,DDY
      DOUBLE PRECISION DX,DY,DDX,DDY
cwb
      DIMENSION SPLINE(NCOEF,MXKNOTS)
C
C Compute the coordinates of a point in the IKNOTth interval.
C
      X = SPLINE(2,IKNOT) + S*SPLINE(3,IKNOT)
      &      + S*S*SPLINE(4,IKNOT)
      &      + S*S*S*SPLINE(5,IKNOT)
C
      Y = SPLINE(6,IKNOT) + S*SPLINE(7,IKNOT)
      &      + S*S*SPLINE(8,IKNOT)
      &      + S*S*S*SPLINE(9,IKNOT)
CWB
      DX = SPLINE(3,IKNOT)
      &      +2.0D0*S*SPLINE(4,IKNOT)
      &      +3.0D0*S*S*SPLINE(5,IKNOT)
C
      DY = SPLINE(7,IKNOT)
      &      +2.0D0*S*SPLINE(8,IKNOT)
      &      +3.0D0*S*S*SPLINE(9,IKNOT)
C
      DDX= 2.0D0*SPLINE(4,IKNOT)+6.0D0*S*SPLINE(5,IKNOT)
C

```

```

        DDY= 2.0D0*SPLINE(8,IKNOT)+6.0D0*S*SPLINE(9,IKNOT)
CWB
        SGMLNG=SPLINE(1,IKNOT)+S
C
        XOUT=X
        YOUT=Y
        DXTNVT=DX/DSQRT(DX**2+DY**2)
        DYTNTV=DY/DSQRT(DX**2+DY**2)
        CRDLNG=SGMLNG
C
C We be done
C
        RETURN
        END
        SUBROUTINE HORNERS(A,OLDS, S)
C
C-----
C        HORNERS(A,OLDS, S)
C        Computes the roots of a cubic equation given an initial value for the
C        cubic's parameter (OLDS). The root will be returned in the variable
C        'S'. Horner's method can be used to solve for the roots of nth
C        ordered polynomials but it is coded here for strictly cubics.
C        Horner's method is a variation of Newton's method.
C
C        The equation for the cubic is:
C                 $P(S) = A(1)*S**3 + A(2)*S**2 + A(3)*S + A(4)$ 
C        The equation for the derivative of the cubic is:
C                 $P'(S) = 3*A(1)*S**2 + 2*A(2)*S + A(3)$ 
C        For an initial parameter (OLDS) the root of the cubic is found by:
C                 $s = OLDS - [P(olds) / P'(olds)]$ 
C
C        Written by Ron Dolin begining on 8/20/92
C-----
C
        IMPLICIT DOUBLE PRECISION (A-H,O-Z)
        IMPLICIT INTEGER*4 (I-N)
        DIMENSION A(4)
C
C        The cubic equation to be solved is of the form:
C                 $P = A(1)*S**3 + A(2)*S**2 + A(3)*S + A(4)$ 
C        The derivative of the cubic equation is:
C                 $DP = 3*A(1)*S**2 + 2*A(2)*S + A(3)$ 
C        The first time we compute a root may not render the best value. We
C        will therefore iterate potentially ten times. Since this method is a
C        variation of Newton's method, it follows the Newton method's for
C        convergence.
C                S = OLDS
C                DS = 0.0D0
C                DO 100 I = 1,50
CWB        DO 100 I = 1,10
C                P = ( ( A(1)*S + A(2) ) *S + A(3) ) *S + A(4)
C                DP = ( 3.0D0*A(1)*S + 2.0D0*A(2) ) *S + A(3)
C                IF (DP .EQ. 0.0D0) RETURN
C                S = OLDS - ( P / DP)
C                DS = DABS(S - OLDS)
C                OLDS = S
C                IF (DS .LT. 1.0D-9) RETURN
CWB        IF (DS .LT. 1E-7) RETURN
C        100 CONTINUE
C
        RETURN
        END
        SUBROUTINE APT087 (DRESULT,RECT)
C

```



```

C-----
C.....FORTRAN SUBROUTINE          APT087...          5/1/68   GK
C
C          FORTRAN SUBROUTINE APT087
C
C PURPOSE      TO GENERATE THE POLAR COORDINATES OF A GIVEN
C              POINT.
C
C LINKAGE      CALL APT087 (RESULT, RECT)
C
C ARGUMENTS    RESULT (1)          DISTANCE FROM ORIGIN TO INPUT POINT
C              RESULT (2)          ANGLE IN DEGREES BETWEEN INPUT POINT
C                                  AND POSITIVE X-AXIS
C              RECT                ARRAY CONTAINING THE CANONICAL FORM
C                                  OF INPUT POINT IN RECTANGULAR
C                                  COORDINATES
C
C This subroutine is so short and focused on the simple task of
c computing
c the polar coordinates of a rectangular coordinate system that the
c original APT sub_routine has been dramatically edited. The executable
c statements have not been altered but the unnecessary baggage has been
c removed..... By order of Ron Dolin on 10/15/92
C-----
C
c
c      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
c      IMPLICIT INTEGER*4 (I-N)
cwb  PARAMETER (DEGRAD = 0.017453293)
C
c      DIMENSION DRESULT(2), RECT(2)
c      DIMENSION SC(2)
C
C CHANGE RECTANGULAR COORDINATES TO POLAR -  DRESULT(1) = RAD,
C                                           DRESULT(2) = ANGLE
Cwb
c      PI=4.0D0*DATAN(1.0D0)
c      DEGRAD=PI/180.0D0
Cwb
c      SC(1) = RECT(1)
c      SC(2) = RECT(2)
c      Z0    = 0.0D0
c
c      UNFLAG = CKDEF(SC)
c
c      DRESULT(1) = DSQRT(SC(1)**2 + SC(2)**2)
c      DRESULT(2) = Z0
C
c      IF (DRESULT(1) .NE. Z0) DRESULT(2) = DATAN2(SC(2),SC(1))/DEGRAD
C
c      RETURN
c      END
c      FUNCTION F5ATAN(AY,AX)
C
c -----
c      F5ATAN(AY,AX)
c Computes the arctangent of AY / AX. The function takes care of
c infinite
c arctangent problems. It also takes care of improper quadrant problems
c that can arise when using various compilers. The value of the
c arctangent is returned in degrees. This is a double precision version
c of the original IDEAL library function.
c
c Written by Rob Oakes or Dwight Jaeger in the 1980's

```

```

c Modified for SE module by Ron Dolin begining on 8/25/92
c -----
c
c
c      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
c      IMPLICIT INTEGER*4 (I-N)
cwb
c      PI=4.0D0*DATAN(1.0D0)
c      RADDEG=180.0D0/PI
cwb
c
cwb  ENTRY ATANDL(AY,AX)
c      X =DABS(AX)
c      Y =DABS(AY)
cwb  X = ABS(AX)
cwb  Y = ABS(AY)
c      IF(Y .GT. X) GO TO 1050
c      IF(X. EQ. 0.0D0) THEN
c          F5ATAN = 45.0D0
c          RETURN
c      END IF
c
cwb
c      F5ATAN =RADDEG*DATAN(Y/X)
c      GO TO 1075
c      1050 F5ATAN = 90.0D0 - RADDEG*DATAN(X/Y)
c
cwb  F5ATAN = 57.2957795131D0 * ATAN(Y/X)
cwb  GO TO 1075
c      1050 F5ATAN = 90.D0 - 57.2957795131D0*ATAN(X/Y)
c
c      1075 IF(AX .LT. 0.0D0) F5ATAN = 180.0D0 - F5ATAN
c          IF(AY .LT. 0.0D0) F5ATAN = 360.0D0 - F5ATAN
c
c We're just a couple of happy campers lost in the proper quadrant
c      RETURN
c      END

```

Appendix B—PCS Routines

```

      subroutine NRFCs (npt1,angin,angout,iaflg,wfspl)
c
c      Wilbur D. Birchler, Ph.D.
c      Engineering Analysis
c      Los Alamos National Laboratory
c      Los Alamos, New Mexico
c      (505) 667-9361
c
c      implicit none
c
c      Begin WILSON-FOWLER Information Block
c
c      PARAMETER (ncoef=13, mxknots=201, mxpts=1000, ndim=3)
c
c      double precision wfspl
c      dimension wfspl(ncoef,mxknots)
c
c      E n d WILSON-FOWLER Information Block
c
c      integer*4 i, j, npt1, iaflg, ncoef, mxknots, mxpts, ndim, one
c
c      double precision t, x, y, dxt2, dyt2, angin, angout
c      double precision anginx, angoutx, anginy, angouty, pi
c      dimension t(mxpts), x(mxpts), y(mxpts), dxt2(mxpts), dyt2(mxpts)
c
c      pi=4.0d0*datan(1.0d0)
c      one=1
c
c      x(1)=wfspl(2,1)
c      y(1)=wfspl(6,1)
c      t(1)=0.0d0
c      wfspl(1,1)=0.0d0
c
c      do 10 i=2,npt1
c      x(i)=wfspl(2,i)
c      y(i)=wfspl(6,i)
c      t(i)=t(i-1)+dsqrt((x(i)-x(i-1))**2+(y(i)-y(i-1))**2)
c      wfspl(1,i)=t(i)
10 continue
c
c      values of end slopes
c
c      anginx=dcos(angin)
c      anginy=dsin(angin)
c      angoutx=dcos(angout)
c      angouty=dsin(angout)
c
c      call spline (t,x,npt1,one,anginx,one,angoutx,dxt2)
c      call spline (t,y,npt1,one,anginy,one,angouty,dyt2)
c
c      do 20 i=1,npt1-1
c      wfspl(5,i)=(dxt2(i+1)-dxt2(i))/(6.0d0*(t(i+1)-t(i)))
c      wfspl(9,i)=(dyt2(i+1)-dyt2(i))/(6.0d0*(t(i+1)-t(i)))
c      wfspl(4,i)=dxt2(i)/2.0d0
c      wfspl(8,i)=dyt2(i)/2.0d0
c      wfspl(3,i)=(x(i+1)-x(i))/(t(i+1)-t(i))-(t(i+1)-t(i))*(dxt2(i)/3.d0
1 +dxt2(i+1)/6.0d0)
c      wfspl(7,i)=(y(i+1)-y(i))/(t(i+1)-t(i))-(t(i+1)-t(i))*(dyt2(i)/3.d0
1 +dyt2(i+1)/6.0d0)
20 continue
c

```

```

do 30 i=3,5
  wfspl(i,npt1)=0.0d0
  wfspl(i+4,npt1)=0.0d0
30 continue
c
  return
end
subroutine spline (x,y,n,iflg1,yp1,iflgn,ypn,y2)
c
  Wilbur D. Birchler, Ph.D.
  Engineering Analysis
  Los Alamos National Laboratory
  Los Alamos, New Mexico
  (505) 667-9361
c
  implicit none
c
  integer*4 n, iflg1, iflgn, ncoef, mxknots, mxpts, ndim
  PARAMETER (ncoef=13, mxknots=201, mxpts=1000, ndim=3)
  double precision yp1, ypn, x, y, y2, u
  dimension x(mxpts), y(mxpts), y2(mxpts), u(mxpts)
c
  iflg1 = end condition for end 1
  = 0 - natural boundary
  = 1 - specified end angle
  iflgn = end condition for end 1
  = 0 - natural boundary
  = 1 - specified end angle
c
  integer*4 i, k
  double precision p, qn, sig, un
c
  if (iflg1.eq.0) then
    y2(1)=0.0d0
    u(1)=0.0d0
  else
    y2(1)=-0.5d0
    u(1)=(3.0d0/(x(2)-x(1)))*((y(2)-y(1))/(x(2)-x(1))-yp1)
  endif
c
  do 10 i=2,n-1
    sig=(x(i)-x(i-1))/(x(i+1)-x(i-1))
    p=sig*y2(i-1)+2.0d0
    y2(i)=(sig-1.0d0)/p
    u(i)=(6.0d0*((y(i+1)-y(i))/(x(i+1)-x(i))-(y(i)-y(i-1))/(x(i)-x(i-1)
1  )))/(x(i+1)-x(i-1))-sig*u(i-1))/p
10 continue
c
  if (iflgn.eq.0) then
    qn=0.0d0
    un=0.0d0
  else
    qn=0.5d0
    un=(3.0d0/(x(n)-x(n-1)))*(ypn-(y(n)-y(n-1))/(x(n)-x(n-1)))
  endif
c
  y2(n)=(un-qn*u(n-1))/(qn*y2(n-1)+1.0d0)
c
  do 20 k=n-1,1,-1
    y2(k)=y2(k)*y2(k+1)+u(k)
20 continue
c
  return
end

```

Appendix C—Minimum-Distance Routines

```

subroutine analyze_datawb (bl_spl,nblpts,spltyp,pt_data,ndpts
1 ,pt_data1)
c
c      Wilbur D. Birchler, Ph.D.
c      Engineering Analysis
c      Los Alamos National Laboratory
c      Los Alamos, New Mexico
c      (505) 667-9361
c
c      implicit double precision (a-h,o-z)
c      implicit integer*4 (i-n)
c
c      parameter (ncoef=13, mxknots=201, mxpts=1000, ndim=3)
c      parameter (tolz=1.0d-20, tols=1.0d-10)
c
c      character*10 spltyp
c      dimension bl_spl(ncoef,mxknots), pt_data(3,mxpts)
c      dimension sbgnd(2,2*mxknots), jbgnd(2*mxknots)
c
c      common /wbspnrlt/ xout, yout, dxtnvt, dytnvt, crdlnq
c      double precision xout, yout, dxtnvt, dytnvt, crdlnq
c
c      dimension pt_data1(5,mxpts)
c
c      Build Subsegments - Inflection Points
c
c      nsbsgm=0
c
c      do 10 i=1,nblpts-1
c      nsbsgm=nsbsgm+1
c      sbgnd(1,nsbsgm)=0.0d0
c      jbgnd(nsbsgm)=i
c      a=6.0d0*(bl_spl(4,i)*bl_spl(9,i)-bl_spl(8,i)*bl_spl(5,i))
c      b=6.0d0*(bl_spl(3,i)*bl_spl(9,i)-bl_spl(7,i)*bl_spl(5,i))
c      c=2.0d0*(bl_spl(3,i)*bl_spl(8,i)-bl_spl(7,i)*bl_spl(4,i))
c
c      sl=0.0d0
c      sh=bl_spl(1,i+1)-bl_spl(1,i)
c      call gdsqrt (a,b,c,sl,sh,n,sl,s2)
c
c      if (n.eq.0) then
c      sbgnd(2,nsbsgm)=bl_spl(1,i+1)-bl_spl(1,i)
c      go to 10
c      endif
c
c      if (n.eq.1) then
c      sbgnd(2,nsbsgm)=s1
c      nsbsgm=nsbsgm+1
c      jbgnd(nsbsgm)=i
c      sbgnd(1,nsbsgm)=s1
c      sbgnd(2,nsbsgm)=bl_spl(1,i+1)-bl_spl(1,i)
c      go to 10
c      endif
c
c      if (n.eq.2) then
c      sbgnd(2,nsbsgm)=s1
c      nsbsgm=nsbsgm+1
c      jbgnd(nsbsgm)=i
c      sbgnd(1,nsbsgm)=s1
c      sbgnd(2,nsbsgm)=s2
c      nsbsgm=nsbsgm+1

```

```

        jbgnd(nsbsgm)=i
        sbgnd(1,nsbsgm)=s2
        sbgnd(2,nsbsgm)=bl_spl(1,i+1)-bl_spl(1,i)
        go to 10
    endif
c
10 continue
c
    do 70 i=1,ndpts
c
        x1=pt_data(1,i)
        y1=pt_data(2,i)
c
        jseg=0
        dmin=1.0d30
        smin=1.0d30
c
        do 20 j=1,nsbsgm
            indx=jbgnd(j)
            ss=sbgnd(1,j)
            call GET_SPLPT (bl_spl,indx,ss,xs,ys)
            dist=(x1-xs)**2+(y1-ys)**2
            if (dist.lt.dmin) then
                dmin=dist
                jseg=j
                smin=ss
c
                if (dmin.lt.tolz) then
                    indx=jbgnd(jseg)
                    go to 50
                endif
c
            endif
            ss=(sbgnd(1,j)+sbgnd(2,j))*0.1d0
            call GET_SPLPT (bl_spl,indx,ss,xs,ys)
            dist=(x1-xs)**2+(y1-ys)**2
            if (dist.lt.dmin) then
                dmin=dist
                jseg=j
                smin=ss
c
                if (dmin.lt.tolz) then
                    indx=jbgnd(jseg)
                    go to 50
                endif
c
            endif
            ss=(sbgnd(1,j)+sbgnd(2,j))*0.5d0
            call GET_SPLPT (bl_spl,indx,ss,xs,ys)
            dist=(x1-xs)**2+(y1-ys)**2
            if (dist.lt.dmin) then
                dmin=dist
                jseg=j
                smin=ss
c
                if (dmin.lt.tolz) then
                    indx=jbgnd(jseg)
                    go to 50
                endif
c
            endif
            ss=(sbgnd(1,j)+sbgnd(2,j))*0.9d0
            call GET_SPLPT (bl_spl,indx,ss,xs,ys)
            dist=(x1-xs)**2+(y1-ys)**2

```

```

        if (dist.lt.dmin) then
            dmin=dist
            jseg=j
            smin=ss
c
            if (dmin.lt.tolz) then
                indx=jbgnd(jseg)
                go to 50
            endif
c
        endif
        ss=sbgnd(2,j)
        call GET_SPLPT (bl_spl,indx,ss,xs,ys)
        dist=(x1-xs)**2+(y1-ys)**2
        if (dist.lt.dmin) then
            dmin=dist
            jseg=j
            smin=ss
c
            if (dmin.lt.tolz) then
                indx=jbgnd(jseg)
                go to 50
            endif
c
        endif
c
        20 continue
c
        30 continue
c
        if (jseg.gt.nsbsgm) then
            jseg=nsbsgm-1
            ss=sbgnd(2,jseg)
        endif
        if (jseg.le.0) then
            jseg=1
            ss=sbgnd(1,jseg)
        endif
c
        indx=jbgnd(jseg)
c
        40 continue
        call GET_SPLPT (bl_spl,indx,ss,xs,ys)
        ds=(x1-xs)*dxtnvt+(y1-ys)*dytnvt
        ss=ss+ds
        if (dabs(ds).lt.tols) go to 50
        go to 40
c
        50 continue
c
        if (jseg.eq.1.and.ss.lt.0.0d0) then
            write (6,80)
            write (9,80)
            write (6,90) i,x1,y1
            write (9,90) i,x1,y1
            ss=0.0d0
            indx=1
            go to 60
        endif
c
        if (jseg.eq.nsbsgm.and.ss.gt.sbgnd(2,nsbsgm)) then
            write (6,80)
            write (9,80)
            write (6,90) i,x1,y1

```

```

        write (9,90) i,x1,y1
        ss=sbgnd(2,nsbsgm)
        indx=nblpts-1
        go to 60
    endif
c
    if (ss.lt.sbgnd(1,jseg)) then
        ss=sbgnd(1,jseg)+ss
        jseg=jseg-1
        go to 30
    endif
c
    if (ss.gt.sbgnd(2,jseg)) then
        ss=ss-sbgnd(2,jseg)
        jseg=jseg+1
        go to 30
    endif
c
60 continue
c
    call GET_SPLPT (bl_spl,indx,ss,xs,ys)
c
    pt_data1(1,i)=xout
    pt_data1(2,i)=yout
    pt_data1(3,i)=dxtnvt
    pt_data1(4,i)=dytnvt
    pt_data1(5,i)=crdlng
c
70 continue
c
    return
c
80 format ('*',')
90 format ('Warning...Point ',i3,' is off Spline ',' x= ',f12.6,' y=
1',f12.6,'.....PLTSPLN')
end
subroutine gdsqrt (a,b,c,s1,sh,n,s1,s2)
c
c    Wilbur D. Birchler, Ph.D.
c    Engineering Analysis
c    Los Alamos National Laboratory
c    Los Alamos, New Mexico
c    (505) 667-9361
c
implicit none
c
real*8 a, b, c, s1, s2, s3, rdl, tolz, sl, sh
integer*4 n
c
data tolz /1.0d-30/
c
if (dabs(a).lt.tolz) then
    if (dabs(b).lt.tolz) then
        s1=0.0d0
        s2=0.0d0
        n=0
        return
    else
        s1=-c/b
        n=1
        s2=0.0d0
        if (s1.le.s1) then
            s1=0.0d0
            n=0

```



```

        return
    endif
    if (s1.ge.sh) then
        s1=0.0d0
        n=0
        return
    endif
    return
endif
endif
else
    rdl=b**2-4.0d0*a*c
    if (rdl.eq.0.0d0) then
        s1=-b/(2.0d0*a)
        s2=0.0d0
        n=1
        if (s1.le.s1) then
            s1=0.0d0
            n=0
            return
        endif
        if (s1.ge.sh) then
            s1=0.0d0
            n=0
            return
        endif
        return
    endif
    if (rdl.lt.0.0d0) then
        s1=0.0d0
        s2=0.0d0
        n=0
        return
    endif
    if (rdl.gt.0.0d0) then
        s1=(-b-dsqrt(rdl))/(2.0d0*a)
        s2=(-b+dsqrt(rdl))/(2.0d0*a)
        n=2
        s3=s1
        if (s1.gt.s2) then
            s1=s2
            s2=s3
        endif
        if (s1.le.s1) then
            s1=0.0d0
            n=n-1
            go to 10
        endif
        if (s1.ge.sh) then
            s1=0.0d0
            n=n-1
            go to 10
        endif
        continue
    10    if (s2.le.s1) then
            s2=0.0d0
            n=n-1
            go to 20
        endif
        if (s2.ge.sh) then
            s2=0.0d0
            n=n-1
            go to 20
        endif
    20    continue

```

```
        if (n.eq.1.and.s1.eq.0.0d0) then
            s1=s2
            s2=0.0d0
        endif
        return
    endif
endif
c
return
end
```

Appendix D—Analytical Spline-Point Data

The three analytical spline data-point files are listed in this appendix.

Circle Spline-Point File

```
!
!   WF Start Angle (Deg)  ..  90.00
!   WF End Angle (Deg)   .... 180.00
!
!   Number of Points ... 46
!
      0          100          100          0
      2          100    99.939083      3.48995
      4          100    99.756405      6.975647
      6          100     99.45219     10.452846
      8          100    99.026807     13.91731
     10          100    98.480775     17.364818
     12          100     97.81476     20.791169
     14          100    97.029573     24.19219
     16          100     96.12617     27.563736
     18          100    95.105652     30.901699
     20          100    93.969262     34.202014
     22          100    92.718385     37.460659
     24          100    91.354546     40.673664
     26          100    89.879405     43.837115
     28          100    88.294759     46.947156
     30          100     86.60254      50
     32          100     84.80481     52.991926
     34          100    82.903757     55.91929
     36          100    80.901699     58.778525
     38          100    78.801075     61.566148
     40          100    76.604444     64.278761
     42          100    74.314483     66.913061
     44          100     71.93398     69.465837
     46          100    69.465837     71.93398
     48          100    66.913061     74.314483
     50          100    64.278761     76.604444
     52          100    61.566148     78.801075
     54          100    58.778525     80.901699
     56          100     55.91929     82.903757
     58          100    52.991926     84.80481
     60          100      50      86.60254
     62          100    46.947156     88.294759
     64          100    43.837115     89.879405
     66          100    40.673664     91.354546
     68          100    37.460659     92.718385
     70          100    34.202014     93.969262
     72          100    30.901699     95.105652
     74          100    27.563736     96.12617
     76          100     24.19219     97.029573
     78          100    20.791169     97.81476
     80          100    17.364818     98.480775
     82          100     13.91731     99.026807
     84          100    10.452846     99.45219
     86          100     6.975647     99.756405
     88          100      3.48995     99.939083
     90          100      0      100
```

Ellipse Spline-Point File

```

!
!   WF Start Angle (Deg)  ..  90.00
!   WF End Angle (Deg)   .... 180.00
!
!   Number of Points ... 46
!
!
!      0      100      100      0
!      2  99.965762  99.904866  3.488755
!      4  99.863425  99.620163  6.96612
!      6  99.69411  99.147975 10.420872
!      8  99.459654  98.491719 13.842108
!     10  99.162566  97.656063 17.219399
!     12  98.805964  96.646817 20.542915
!     14  98.393509  95.470801 23.803544
!     16  97.929315   94.1357 26.992978
!     18  97.41787   92.6499 30.103777
!     20  96.863943  91.022332 33.12942
!     22  96.272494  89.262302 36.064311
!     24  95.648594  87.379339 38.903788
!     26  94.997344  85.383047 41.644094
!     28   94.3238  83.282972 44.282342
!     30  93.632918  81.088485 46.816459
!     32  92.929494  78.808681 49.245129
!     34  92.218128  76.452293 51.567723
!     36  91.503182   74.02763 53.784221
!     38  90.788764  71.542523 55.895145
!     40  90.078706  69.004292 57.901476
!     42  89.376556  66.419725 59.804589
!     44  88.685578  63.795066 61.606179
!     46  88.008752  61.136017 63.308198
!     48  87.348784  58.447744 64.912796
!     50  86.708111  55.734899 66.422266
!     52  86.088921  53.001632 67.838995
!     54  85.493164  50.251621 69.165423
!     56  84.922571  47.488099 70.404002
!     58  84.378666  44.71388  71.557167
!     60  83.862787  41.931393 72.627304
!     62  83.376103  39.14271  73.61673
!     64  82.919629  36.349573 74.527669
!     66  82.494241  33.553431 75.362239
!     68  82.100691  30.75546  76.122435
!     70  81.739621  27.956597 76.810119
!     72  81.411578  25.157561 77.427012
!     74  81.117021  22.358881 77.974685
!     76  80.856333  19.560917 78.454555
!     78  80.629833  16.763885 78.867878
!     80  80.437781  13.967874 79.21575
!     82  80.280383  11.17287  79.4991
!     84  80.157803  8.378772  79.71869
!     86  80.070162  5.585412  79.875115
!     88  80.017545  2.792572  79.9688
!     90      80      0      80

```

Parabola Spline-Point File

```

!
!   WF Start Angle (Deg)  ..  90.0000
!   WF End Angle (Deg)   .... 163.3008
!
!   Number of Points ... 46
!
!
!      0      100      100      0

```

2	99.724286	99.663537	3.480327
4	98.918384	98.677424	6.900198
6	97.64132	97.106431	10.206297
8	95.977836	95.043786	13.357533
10	94.02365	92.59522	16.327036
12	91.872561	89.864925	19.101379
14	89.607846	86.94611	21.6781
16	87.298161	83.916379	24.062634
18	84.996849	80.836807	26.265471
20	82.743289	77.753258	28.299871
22	80.565148	74.698705	30.180236
24	78.480811	71.695788	31.921022
26	76.501597	68.75918	33.536093
28	74.633627	65.897582	35.038366
30	72.879303	63.115328	36.439651
32	71.238442	60.413625	37.750623
34	69.709126	57.791485	38.980849
36	68.288327	55.246417	40.138871
38	66.972353	52.774934	41.232298
40	65.757172	50.372917	42.267896
42	64.638637	48.035869	43.25169
44	63.612639	45.759103	44.189052
46	62.675213	43.537862	45.084775
48	61.822613	41.367403	45.943155
50	61.051349	39.243051	46.768047
52	60.358217	37.160229	47.562924
54	59.740316	35.114476	48.330931
56	59.195049	33.101451	49.07492
58	58.720131	31.116929	49.797496
60	58.313583	29.156792	50.501045
62	57.97373	27.217018	51.187766
64	57.699199	25.293664	51.859696
66	57.488912	23.382847	52.518735
68	57.342091	21.480726	53.166661
70	57.258252	19.583475	53.805157
72	57.237206	17.687269	54.435818
74	57.27907	15.788251	55.060176
76	57.384264	13.88251	55.679706
78	57.553528	11.966051	56.295845
80	57.78793	10.034769	56.910002
82	58.088888	8.084411	57.523571
84	58.458183	6.110544	58.137943
86	58.897991	4.108516	58.754518
88	59.41091	2.073411	59.374719
90	60	0	60

Appendix E—Nonanalytical Spline-Point Data

The three nonanalytical spline data-point files are listed in this appendix.

Ellipse Spline-Point File

```
!
! CAD Start slope (Deg) .. -90.0000
! CAD End slope (Deg) .... -0.0000
!
! WF Start Angle (Deg) .. 90.0000
! WF End Angle (Deg) ... 180.0000
!
! Number of Points ... 46
!
0.0000 93.500000 93.500000 0.000000
2.0000 93.198700 93.141926 3.252588
4.0000 92.313400 92.088529 6.439457
6.0000 90.896800 90.398858 9.501303
8.0000 89.027700 88.161289 12.390261
10.0000 86.799900 85.481214 15.072644
12.0000 84.311000 82.468602 17.529243
14.0000 81.653700 79.228236 19.753818
16.0000 78.909500 75.852680 21.750406
18.0000 76.145600 72.418769 23.530284
20.0000 73.414900 68.987440 25.109375
22.0000 70.756400 65.604192 26.505814
24.0000 68.197700 62.301699 27.738504
26.0000 65.756500 59.101551 28.825752
28.0000 63.443100 56.016932 29.784731
30.0000 61.262500 53.054881 30.631250
32.0000 59.215200 50.217338 31.379275
34.0000 57.299100 47.503107 32.041250
36.0000 55.510300 44.908776 32.628136
38.0000 53.843400 42.429178 33.149307
40.0000 52.292500 40.058379 33.612971
42.0000 50.851400 37.789955 34.026228
44.0000 49.513900 35.617319 34.395245
46.0000 48.273700 33.533730 34.725194
48.0000 47.124900 31.532713 35.020626
50.0000 46.062100 29.608147 35.285616
52.0000 45.079800 27.753896 35.523367
54.0000 44.173200 25.964356 35.736869
56.0000 43.337900 24.234246 35.928747
58.0000 42.569600 22.558451 36.101068
60.0000 41.864600 20.932300 36.255807
62.0000 41.219400 19.351336 36.394570
64.0000 40.630900 17.811414 36.518811
66.0000 40.096300 16.308634 36.629793
68.0000 39.613000 14.839291 36.728534
70.0000 39.178800 13.399939 36.816029
72.0000 38.791600 11.987264 36.893004
74.0000 38.449700 10.598174 36.960224
76.0000 38.151600 9.229707 37.018334
78.0000 37.895800 7.878980 37.067686
80.0000 37.681300 6.543289 37.108836
```

82.0000	37.507000	5.219965	37.141984
84.0000	37.372200	3.906459	37.167471
86.0000	37.276400	2.600270	37.185597
88.0000	37.219100	1.298928	37.196427
90.0000	37.200000	0.000000	37.200000

Lampshade Spline-Point File

```

!
! CAD Start slope (Deg) .. -80.7233
! CAD End slope (Deg) .... -8.4766
!
! WF Start Angle (Deg) .. 180.0000 - 80.7233 = 99.2767
! WF End Angle (Deg) .... 180.0000 - 8.4766 = 171.5234
!
! Number of Point ... 28
!
0.0000 56.700000 56.700000 0.000000
3.5700 56.196049 56.087000 3.499200
6.5780 55.882886 55.515000 6.401700
9.9364 55.677563 54.842400 9.607400
12.9638 55.650525 54.232100 12.484400
16.4533 55.851777 53.564700 15.819100
19.4683 56.250573 53.034500 18.747500
22.2533 56.694383 52.471700 21.470300
24.0755 56.822700 51.879600 23.180300
25.6628 56.598902 51.015900 24.511500
27.0216 55.956783 49.848300 25.422600
27.9623 55.115696 48.681300 25.843200
28.9510 53.848536 47.119300 26.066000
30.0986 52.337354 45.280400 26.246600
31.6816 50.765148 43.200100 26.661800
33.2417 49.620034 41.500500 27.200300
34.8287 48.667661 39.949500 27.795300
40.1855 46.174994 35.275800 29.795100
45.9210 44.140762 30.706500 31.709900
51.1727 42.567917 26.689000 33.162100
57.5074 40.972975 22.010300 34.559100
64.4569 39.813978 17.167400 35.922600
70.8328 39.650009 13.018100 37.452000
76.2420 40.473634 9.625500 39.312400
80.0399 41.727403 7.217300 41.098500
83.3522 43.121427 4.992000 42.831500
86.6486 44.340431 2.592100 44.264600
90.0000 45.000000 0.000000 45.000000

```

Weird Shape Spline-Point File

```

!
! CAD Start slope (Deg) .. -5.3125
! CAD End slope (Deg) .... -2.4783
!
! WF Start Angle (Deg) .. 180.0000 - 5.3125 = 174.6875
! WF End Angle (Deg) .... 180.0000 - 2.4783 = 177.5217
!
! Number of Points ... 24
!
10.6325 107.297800 105.455588 19.797396

```

11.4126	102.431700	100.406388	20.268458
12.3071	97.399100	95.160788	20.760760
13.5209	91.686100	89.144992	21.436214
14.9906	85.836300	82.915143	22.202466
16.2770	81.302000	78.043244	22.787438
17.7706	76.781800	73.118243	23.434320
20.5084	70.726300	66.243726	24.778584
24.3245	65.636600	59.809857	27.035981
29.3600	62.194400	54.205922	30.493629
34.1821	61.005100	50.466843	34.274188
39.6041	61.441800	47.338918	39.167865
44.1534	62.945900	45.162260	43.846968
48.5757	65.118700	43.084482	48.827989
53.8197	68.143900	40.227264	55.003257
58.6382	70.973000	36.937219	60.603701
63.7764	73.585800	32.515754	66.012087
67.6314	74.981100	28.535080	69.339127
72.0364	75.792000	23.375217	72.097340
77.7110	75.784000	16.130079	74.047520
83.0883	75.288700	9.060209	74.741561
87.9188	75.014500	2.724212	74.965018
91.2798	75.133600	-1.678099	75.114858
94.7630	75.560400	-6.274106	75.299466

Appendix F—Keyword Graphics Builder Program— Command Files

The three Keyword Graphics Builder Program command files, which were used to calculate and plot the deviation results, are listed in this appendix.

Analytical Shapes—Accuracy Study

```
*, Analytical Shapes - Offset Study
*,
*, Circle Data
splndata,Circle_n.spn,132,132,Circle_n.spn,3,4,d,90.,d,180.
proedata,Circle_n.pts,132,132,Circle_n.pts,3,4
proedata,Circle_p.pts,132,132,Circle_p.pts,3,4
proedata,Circle_m.pts,132,132,Circle_m.pts,3,4
*, Ellipse Data
splndata,Ellipse_n.spn,132,132,Ellipse_n.spn,3,4,d,90.,d,180.
proedata,Ellipse_n.pts,132,132,Ellipse_n.pts,3,4
proedata,Ellipse_p.pts,132,132,Ellipse_p.pts,3,4
proedata,Ellipse_m.pts,132,132,Ellipse_m.pts,3,4
*, Parabola Data
splndata,Parabola_n.spn,132,132,Parabola_n.spn,3,4,d,90.,d,163.3008
proedata,Parabola_n.pts,132,132,Parabola_n.pts,3,4
proedata,Parabola_p.pts,132,132,Parabola_p.pts,3,4
proedata,Parabola_m.pts,132,132,Parabola_m.pts,3,4
*,
on,tek,p,.9
on,grid
on,geom
*,
*, Open plot file
open,Circle.wf.ps,p
*,
*, Plot Analytical shapes - Spline Data
plot,,Circle_n.spn,Ellipse_n.spn,Parabola_n.spn,
*,
*, Circle - Calculate and plot deviation results - Wilson-Fowler
pltptwf,Circle_n_wf,Circle_n.spn,Circle_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Circle_p_wf,Circle_n.spn,Circle_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Circle_m_wf,Circle_n.spn,Circle_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*,
*, Circle - Calculate maximum/minum deviations - Wilson-Fowler
maxmin,Circle_n_wf.lg
maxmin,Circle_p_wf.lg
maxmin,Circle_m_wf.lg
*,
close
*,
*, Open plot file
open,Ellipse.wf.ps,p
*,
*, Ellipse - Calculate and plot deviation results - Wilson-Fowler
pltptwf,Ellipse_n_wf,Ellipse_n.spn,Ellipse_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Ellipse_p_wf,Ellipse_n.spn,Ellipse_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Ellipse_m_wf,Ellipse_n.spn,Ellipse_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*,
*, Ellipse - Calculate maximum/minum deviations - Wilson-Fowler
maxmin,Ellipse_n_wf.lg
maxmin,Ellipse_p_wf.lg
maxmin,Ellipse_m_wf.lg
```

```

*,
close
*,
*, Open plot file
open,Parabola.wf.ps,p
*,
*, Parabola - Calculate and plot deviation results - Wilson-Fowler
pltptwf,Parabola_n_wf,Parabola_n.spn,Parabola_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Parabola_p_wf,Parabola_n.spn,Parabola_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptwf,Parabola_m_wf,Parabola_n.spn,Parabola_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*, Parabola - Calculate maximum/minum deviations - Wilson-Fowler
maxmin,Parabola_n_wf.lg
maxmin,Parabola_p_wf.lg
maxmin,Parabola_m_wf.lg
*,
close
*,
*, Open plot file
open,Circle.cs.ps,p
*,
*, Circle - Calculate maximum/minum deviations - Parametric Cubic
pltptcs,Circle_n_cs,Circle_n.spn,Circle_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Circle_p_cs,Circle_n.spn,Circle_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Circle_m_cs,Circle_n.spn,Circle_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*,
*, Circle - Calculate maximum/minum deviations - Parametric Cubic
maxmin,Circle_n_cs.lg
maxmin,Circle_p_cs.lg
maxmin,Circle_m_cs.lg
*,
close
*,
*, Open plot file
open,Ellipse.cs.ps,p
*,
*, Ellipse - Calculate maximum/minum deviations - Parametric Cubic
pltptcs,Ellipse_n_cs,Ellipse_n.spn,Ellipse_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Ellipse_p_cs,Ellipse_n.spn,Ellipse_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Ellipse_m_cs,Ellipse_n.spn,Ellipse_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*,
*, Ellipse - Calculate maximum/minum deviations - Parametric Cubic
maxmin,Ellipse_n_cs.lg
maxmin,Ellipse_p_cs.lg
maxmin,Ellipse_m_cs.lg
off,geom
*
close
*, Open plot file
open,Parabola.cs.ps,p
*,
*, Parabola - Calculate maximum/minum deviations - Parametric Cubic
pltptcs,Parabola_n_cs,Parabola_n.spn,Parabola_n.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Parabola_p_cs,Parabola_n.spn,Parabola_p.pts,132,132,ur,1,1000.,.0254,.00254,.0254
pltptcs,Parabola_m_cs,Parabola_n.spn,Parabola_m.pts,132,132,ur,1,1000.,.0254,.00254,.0254
*,
*, Parabola - Calculate maximum/minum deviations - Parametric Cubic
maxmin,Parabola_n_cs.lg
maxmin,Parabola_p_cs.lg
maxmin,Parabola_m_cs.lg
*,
close
tty

```

Nonanalytical Shapes—Deviation Study

```
*, Non-Analytical Shapes CAD Systems Evaluations
*, Spline data
splndata,c01762.spn,132,132,c01762.spn,3,4,d, 90.0000,d,180.0000
splndata,c01763.spn,132,132,c01763.spn,3,4,d, 99.2767,d,171.5234
splndata,c01764.spn,132,132,c01764.spn,3,4,d,174.6875,d,177.5217
*,
*, Evaluation data
proedata,c01762_CAD.pts,132,132,c01762_CAD.pts,3,4
proedata,c01763_CAD.pts,132,132,c01763_CAD.pts,3,4
proedata,c01764_CAD.pts,132,132,c01764_CAD.pts,3,4
proedata,c01762_PRO.pts,132,132,c01762_PRO.pts,1,2
proedata,c01763_PRO.pts,132,132,c01763_PRO.pts,1,2
proedata,c01764_PRO.pts,132,132,c01764_PRO.pts,1,2
proedata,c01762_ICM.pts,132,132,c01762_ICM.pts,4,5
proedata,c01763_ICM.pts,132,132,c01763_ICM.pts,4,5
proedata,c01764_ICM.pts,132,132,c01764_ICM.pts,4,5
*,
on,tek,p,.9
on,grid
on,geom
*,
  Open plot file
open,AWE.wf.ps,p
*,
*, Plot Non-Analytical Shapes - Spline Data
*,
plot,,,c01762.spn,c01763.spn,c01764.spn
*,
*, Calculate and plot deviation results - Wilson-Fowler
pltptwf,c01762_CAD,c01762.spn,c01762_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_CAD.lg
pltptwf,c01763_CAD,c01763.spn,c01763_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_CAD.lg
pltptwf,c01764_CAD,c01764.spn,c01764_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_CAD.lg
pltptwf,c01762_PRO,c01762.spn,c01762_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_PRO.lg
pltptwf,c01763_PRO,c01763.spn,c01763_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_PRO.lg
pltptwf,c01764_PRO,c01764.spn,c01764_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_PRO.lg
pltptwf,c01762_ICM,c01762.spn,c01762_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_ICM.lg
pltptwf,c01763_ICM,c01763.spn,c01763_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_ICM.lg
pltptwf,c01764_ICM,c01764.spn,c01764_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_ICM.lg
*,
close
*,
*, Open plot file
open,AWE.cs.ps,p
*,
*, Calculate and plot deviation results - Parametric Cubic
pltptcs,c01762_CAD,c01762.spn,c01762_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_CAD.lg
pltptcs,c01763_CAD,c01763.spn,c01763_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_CAD.lg
pltptcs,c01764_CAD,c01764.spn,c01764_CAD.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_CAD.lg
pltptcs,c01762_PRO,c01762.spn,c01762_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_PRO.lg
```

```

pltptcs,c01763_PRO,c01763.spn,c01763_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_PRO.lg
pltptcs,c01764_PRO,c01764.spn,c01764_PRO.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_PRO.lg
pltptcs,c01762_ICM,c01762.spn,c01762_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01762_ICM.lg
pltptcs,c01763_ICM,c01763.spn,c01763_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01763_ICM.lg
pltptcs,c01764_ICM,c01764.spn,c01764_ICM.pts,132,132,ur,1,5000.,.00254,.00254
maxmin,c01764_ICM.lg
*,
close
tty

```

Analytical Shapes—End-Angle Effects

```

*, Analytical Shapes - End Angle Study
*,
*, Circle - Spline and evaluation data
splndata,Circle_n.spn,132,132,Circle_n_spn,3,4,d,90.00,d,180.00
splndata,Circle_p.spn,132,132,Circle_n_spn,3,4,d,90.25,d,180.25
splndata,Circle_m.spn,132,132,Circle_n_spn,3,4,d,89.75,d,179.75
proedata,Circle_n.pts,132,132,Circle_n_pts,3,4
*,
*, Ellipse - Spline and evaluation data
splndata,Ellipse_n.spn,132,132,Ellipse_n_spn,3,4,d,90.00,d,180.00
splndata,Ellipse_p.spn,132,132,Ellipse_n_spn,3,4,d,90.25,d,180.25
splndata,Ellipse_m.spn,132,132,Ellipse_n_spn,3,4,d,89.75,d,179.75
proedata,Ellipse_n.pts,132,132,Ellipse_n_pts,3,4
*,
*, Parabola - Spline and evaluation data
splndata,Parabola_n.spn,132,132,Parabola_n_spn,3,4,d,90.00,d,163.3008
splndata,Parabola_p.spn,132,132,Parabola_n_spn,3,4,d,90.25,d,163.5508
splndata,Parabola_m.spn,132,132,Parabola_n_spn,3,4,d,89.75,d,163.0508
proedata,Parabola_n.pts,132,132,Parabola_n_pts,3,4
*,
on,tek,p,.9
on,geom
*, Ope plt file
open,Circle.end.ps,p
*,
*, Circle - Calculate and plot deviations - Wilson-Fowler
pltptwf,Circle_p_wf,Circle_p.spn,Circle_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptwf,Circle_m_wf,Circle_m.spn,Circle_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Circle_p_wf.lg
maxmin,Circle_m_wf.lg
*,
*, Circle - Calculate and plot deviations - Parametric Cubic
pltptcs,Circle_p_cs,Circle_p.spn,Circle_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptcs,Circle_m_cs,Circle_m.spn,Circle_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Circle_p_cs.lg
maxmin,Circle_m_cs.lg
*,
close
*,
*, Open plot file
open,Ellipse.end.ps,p
*,
*, Ellipse - Calculate and plot deviations - Wilson-Fowler
pltptwf,Ellipse_p_wf,Ellipse_p.spn,Ellipse_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptwf,Ellipse_m_wf,Ellipse_m.spn,Ellipse_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Ellipse_p_wf.lg
maxmin,Ellipse_m_wf.lg
*,

```

```

*, Ellipse - Calculate and plot deviations - Parametric Cubic
pltptcs,Ellipse_p_cs,Ellipse_p.spn,Ellipse_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptcs,Ellipse_m_cs,Ellipse_m.spn,Ellipse_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Ellipse_p_cs.lg
maxmin,Ellipse_m_cs.lg
*,
close
*,
*, Open plot file
open,Parabola.end.ps,p
*,
*, Parabola - Calculate and plot deviations - Wilson-Fowler
pltptwf,Parabola_p_wf,Parabola_p.spn,Parabola_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptwf,Parabola_m_wf,Parabola_m.spn,Parabola_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Parabola_p_wf.lg
maxmin,Parabola_m_wf.lg
*,
*, Parabola - Calculate and plot deviations - Parametric Cubic
pltptcs,Parabola_p_cs,Parabola_p.spn,Parabola_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
pltptcs,Parabola_m_cs,Parabola_m.spn,Parabola_n.pts,132,132,ur,1,5000.,.00254,.00254,.0254
maxmin,Parabola_p_cs.lg
maxmin,Parabola_m_cs.lg
*,
close
tty

```

References

1. A.H. Fowler and C.W. Wilson, "Cubic Spline, A Curve Fitting Routine," Union Carbide Nuclear Company report (September 1962).
2. William H. Press, Saul A. Teukolsky, William T. Vetterling, and Brian P. Flannery, *Numerical Recipes in FORTRAN, The Art of Scientific Computing*, second ed. (Cambridge University Press, New York, 1992), pp. 107-110.
3. Ronald M. Dolin, "The Wilson-Fowler Spline in a Global IGES Coordinate Frame," Los Alamos National Laboratory report LA-11024-MS (September 1987).
4. W.R. Melvin, "Error Analysis and Uniqueness Properties of the Wilson-Fowler Spline," Los Alamos National Laboratory report LA-9178 (August 1982).
5. "The CAD/CAM Hall of Fame," *Machine Design*, October 1998, p. 104.
6. Ronald M. Dolin and The WX-Division Integrated Software Tools Team (Jose Arellano, Ralph Gladfelter, John Hopkins, Robert Montoya, Kent Musgrave, Scott Parkinson, Bob Reinhart, Mike Smith, Royce Tyler), "Interchangeable Spline Reference Guide," Los Alamos National Laboratory report LA-12746-M (May 1994).
7. Billie M. Wheat and Wilbur D. Birchler, "TDAP User's Guide," Los Alamos National Laboratory WX-4 Technical Engineering Support Group internal manual (April 1984).
8. *Mathcad, User's Guide, Mathcad Plus 6, Macintosh Version*, professional ed. (MathSoft, Inc., Cambridge, Massachusetts, 1996) pp. 1-630.
9. Andy Oughton, computer-aided design manager, AWE Hunting-Brae, Aldermaston, Reading, Berkshire, United Kingdom, personal communication, November 1999.

This report has been reproduced directly from the best available copy. It is available electronically on the Web (<http://www.doe.gov/bridge>).

Copies are available for sale to U.S. Department of Energy employees and contractors from—

Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
(423) 576-8401

Copies are available for sale to the public from—

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22616
(800) 553-6847