RECEIVED

OCT 16 2000

OSTI

Earth Sciences Division
Annual Report
1 9 9 7

Ernest Orlando Lawrence
Berkeley National Laboratory
University of California
Berkeley, California 94720

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Table of Contents

Relevance and Excellence: A Perspective from the Division Director	1
<i>Sally M. Benson, Earth Sciences Division Director</i>	
Subsurface Geosciences Department	5
<i>Ernest L. Majer, Subsurface Geosciences Department Head</i>	
Crosswell Seismic Tomography in Basalt Flows at the INEEL TAN Site	7
<i>T.M. Daley, J.E. Peterson, and E. L. Majer</i>	
GPR-Assisted Saturation and Permeability Estimation in Bimodal Systems	9
<i>S. Hubbard, Y. Rubin, and E. L. Majer</i>	
Hydrogeological Parameter Spatial Correlation Structure Inference Using Geophysical Data	11
<i>S. Hubbard, Y. Rubin, and E. L. Majer</i>	
Acoustic Visibility of Immiscible Liquids in Poorly Consolidated Sand	13
<i>M. B. Kowalsky, J.T. Geller, P.K. Seifert, K.T. Nihel, and L. R. Myer</i>	
3D Boundary-Domain Finite Element Method for Electromagnetic Modeling	15
<i>G. Xie, J. Li, and G. Moridis</i>	
Numerical Investigation of Fracture Channel Waves	17
<i>W.Yi, S. Nakagawa, K. T. Nihel, J.W. Rector, L. R. Myer, and N. G.W. Cook</i>	
Molecular-Scale Simulation of Clay Mineral Surface Geochemistry	19
<i>G. Sposito, J.A. Greathouse, S.-H. Park, and R. Sutton</i>	
Fast Flow of Water Along Surfaces of Unsaturated Fractured Rock	21
<i>T. K. Tokunaga and J. Wan</i>	
Micro-XANES Spectroscopy of Selenium Reactive Transport at the Water-Sediment Boundary	23
<i>T. K. Tokunaga, S. R. Sutton, S. Bajt, and G. Shea-McCarthy</i>	
Colloid Transport in Unsaturated Porous Media	25
<i>J. Wan and T. K. Tokunaga</i>	
Center for Isotope Geochemistry	27
<i>Donald J. DePaolo, Center for Isotope Geochemistry Head</i>	
Isotopic Assessment of Intrinsic Bioremediation of Petroleum Hydrocarbons	29
<i>M. E. Conrad</i>	
An Integrated Isotopic Study of Groundwater Flow and Contaminant Migration	31
<i>M. E. Conrad and D.J. DePaolo</i>	

Reaction Rates and Flow Velocities in Fluid-Rock Systems Measured with Sr Isotopes	33
<i>D.J. DePaolo</i>	
An Isotopic Approach to Determining the Industrial Contribution to Atmospheric Methyl Bromide	35
<i>A. H. Goldstein and S. E. McCauley</i>	
Models for Global Atmospheric Moisture Transport and Implications for Isotopic Paleotemperature Records in Ice Cores	37
<i>M. B. Hendricks and D.J. DePaolo</i>	
Air-Xe Enrichments in Oil Field Gases and the Influence of Water During Oil Migration and Storage	39
<i>B. M. Kennedy and T. Torgersen</i>	
Mantle Fluids in the San Andreas Fault System, California	41
<i>B. M. Kennedy and Y. K. Kharaka</i>	
Regional Climate System Modeling and Applications	43
<i>N. L. Miller and J. Kim</i>	
Measurements of Cosmogenic Nuclides in Extraterrestrial and Terrestrial Materials	45
<i>K. Nishiizumi, R. C. Finkel, M. W. Caffee, W. E. Dietrich, and A. M. Heimsath</i>	
Nuclear Waste Department	47
<i>Gudmundur S. Bodvarsson, Nuclear Waste Department Head</i>	
Center for International Collaboration in Nuclear Waste Management Programs	49
<i>A. Simmons</i>	
Seismic Imaging of the Paleozoic Basement at Yucca Mountain, Nevada	51
<i>M. A. Feighner, T. M. Daley, R. Gritto, and E. L. Majer</i>	
Seismic Reflectivity of Layered Volcanic Tuffs at Yucca Mountain, Nevada	53
<i>T. M. Daley, M. A. Feighner, and E. L. Majer</i>	
Characterization of Fracture Flow Structure Using Cross-Hole Air Permeability	55
<i>P. J. Cook and J. S. Wang</i>	
Measurements of Water Potential at the Exploratory Studies Facility, Yucca Mountain, Nevada	57
<i>R. Salve and J. S. Y. Wang</i>	
Hydrologic Monitoring in Unsaturated Fractured Tuff Boreholes	69
<i>R. Salve, T. Tokunaga, J. S. Y. Wang, R. Solbau, and J. Clyde</i>	
Numerical Modeling of Water Migration in Fracture-Matrix Systems	61
<i>S. Finsterle, A. L. James, and J. S. Y. Wang</i>	
Modeling of Seepage into Drifts	63
<i>J. Birkholzer, G. Li, C.-F. Tsang, and Y. Tsang</i>	
Simultaneous Inversion of Air-Injection Tests in Fractured Unsaturated Tuff at Yucca Mountain, Nevada	65
<i>K. Huang, Y. W. Tsang, and G. S. Bodvarsson</i>	
Thermohydrological Laboratory Tests: Visualizing Flow Processes with Boiling in Fractures	67
<i>T. J. Kneafsey and K. Pruess</i>	
Lessons Learned from the Single Heater Test at Yucca Mountain, Nevada	69
<i>Y. W. Tsang, J. T. Birkholzer, and B. Freifeld</i>	
UZ Flow and Transport Model for Yucca Mountain, Nevada	71
<i>Y.-S. Wu, G. S. Bodvarsson, C. F. Ahlers, A. C. Ritcey, and C. Haukwa</i>	

Calibration of the UZ Flow and Transport Model for Yucca Mountain, Nevada	73
<i>C. F. Ahlers, T. M. Bandurraga, Y. S. Wu, A. C. Ritcey, and G. S. Bodvarsson</i>	
Water Seepage Through Unsaturated Fractured Rock	75
<i>K. Pruess</i>	
Geochemical Constraints on Flow Processes at Yucca Mountain, Nevada	77
<i>E. L. Sonnenthal and G. S. Bodvarsson</i>	
Summary of S ⁴ Z: Sub-Site-Scale Saturated Zone Model for Yucca Mountain, Nevada	79
<i>A. J. B. Cohen, C. M. Oldenburg, A. M. Simmons, A. K. Mishra, and J. Hinds</i>	

Energy Resources Department81

Larry R. Myer, Energy Resources Department Head

Electro-Osmosis Used to Consolidate Well Casings	83
<i>G. A. Cooper and R. C. Wrixon</i>	
Marine Magnetotellurics for Base Salt Mapping: Gulf of Mexico Field Test at the Gemini Structure	85
<i>G. M. Hoversten, S. Constable, and H. F. Morrison</i>	
Electromagnetic Imaging in Steel-Cased Wells	87
<i>K. H. Lee, H. J. Kim, and Y. Song</i>	
Continuity Testing Using Guided Waves	89
<i>V. Korneev, L. Myer, and K. Nibel</i>	
High-Resolution Reservoir Structure from Dynamic Data	91
<i>D. W. Vasco and A. Datta-Gupta</i>	
Prediction of Transport Properties for Reservoir Rock Using the Pore-Level Network Model	93
<i>P. Huang and L. Myer</i>	
Detection and Characterization of Hydraulic Fractures in Oil Reservoirs	95
<i>T. W. Patzek and A. De</i>	
Control of Fluid Injection into a Low-Permeability Rock	97
<i>T. W. Patzek and D. B. Silin</i>	
Oral Bioavailability of PAHs from Solid Environmental Matrix	99
<i>H.-Y. N. Holman, Y. Mao, and R. Goth-Goldstein</i>	
Selenium Cycling in Intertidal Wetlands in the San Francisco Estuary	101
<i>P. T. Zawislanski, H. S. Mountford, E. Gabet, S. Chau, and H. W. Wong</i>	
Response of Liquid-Dominated Geothermal Systems to Exploitation	103
<i>A. Truesdell and M. Lippmann</i>	
Advances in Numerical Simulation of Flow and Transport in Multiphase, Multicomponent Systems	105
<i>K. Pruess, C. Oldenburg, G. Moridis, and Y. S. Wu</i>	
Sharp Front Simulation for TOUGH2 Through Total Variation Diminishing Schemes	107
<i>C. M. Oldenburg and K. Pruess</i>	
Gas Flow in Porous Media with Klinkenberg Effects	109
<i>Y. S. Wu, K. Pruess, and P. Persoff</i>	

Environmental Remediation Technology Department	111
<i>Terry C. Hazen, Environmental Remediation Technology Department Head</i>	
Hydrogeologic Characterization Using the Iterated Function System (IFS) Inverse Method	113
<i>C. Doughty, J. Najita, T. M. Johnson, and D. Saboo</i>	
Conceptual Model of Geometry and Physics of Liquid Flow in Fractured Basalt	115
<i>B. Faybishenko, C. Doughty, M. Steiger, J. C. S. Long, and J. Jacobsen</i>	
Near Surface Wetting of a Ponded Basalt Surface: Observations Using Time Domain Reflectometry	117
<i>R. Salve</i>	
Numerical Method for Simulating Non-Newtonian Fluid Flow in Porous Media	119
<i>Y.S. Wu and K. Pruess</i>	
Design and Evaluation of Instrumentation for Infiltration Tests in Fractured Rock	121
<i>B. Faybishenko, C. Doughty, R. Salve, M. Steiger, P. Zawislanski, and J. Peterson</i>	
Uncertainty Propagation from Subsurface Transport to Exposure Modeling	123
<i>A. L. James, C. M. Oldenburg, D. H. Bennett, and T. E. McKone</i>	
Ferrofluids for Subsurface Flow Control and Imaging	125
<i>G. Moridis</i>	
VZMS: Vadose Zone Monitoring System for McClellan Air Force Base	127
<i>C. M. Oldenburg and P. T. Zawislanski</i>	
Chemical Compatibility of Colloidal Silica Grout	129
<i>P. Persoff, J. Apps, and G. Moridis</i>	
Geophysical Verification of Subsurface Containment Structures	131
<i>L. Pellerin, F. Gilbert, S. Hubbard, and J. Peterson</i>	
Measuring Partition Coefficients of Colloids at Gas-Liquid Interfaces	133
<i>J. M. Wan and T. K. Tokunaga</i>	
Compliance Monitoring and Selenium Load Management in the Grasslands Basin	135
<i>N. W. T. Quinn</i>	
Preliminary Investigations of a Wetting Front Migration at Yucca Mountain, Nevada	137
<i>R. Salve and J. S. Wang</i>	
Center for Environmental Biotechnology	139
<i>Jennie C. Hunter-Cevera, Center for Environmental Biotechnology Head</i>	
Biotransformation of VOCs in Fractured Rock Vadose Zones	141
<i>H.-Y. N. Holman, J. T. Geller, M. Conrad, K. Pruess, and J. C. Hunter-Cevera</i>	
Infrared Microspectroscopy — A Probe for Bacteria Localization in Geologic Materials	143
<i>H.-Y. N. Holman, D. L. Perry, M. C. Martin, W. R. McKinney, and J. C. Hunter-Cevera</i>	
Publications	145
Earth Sciences Division Personnel	167

Relevance and Excellence

A Perspective from the Division Director

The U.S. Department of Energy's (DOE) national laboratories fill a unique role in the scientific community. We are asked to perform research that is relevant to addressing the important responsibilities of DOE, and at the same time we are required to maintain a standard of excellence set by our peers in the scientific community.

The earth and environmental sciences play a central role in many of the most challenging issues addressed by the DOE:

- Safe disposal of radioactive wastes
- Reliable, environmentally sound, and affordable energy supplies
- Cost-effective remediation of soils and groundwater at the Department of Energy's facilities
- Understanding how burning fossil fuels influences climate change
- Expanding the fundamental knowledge needed to address these and future issues
- Education of our future scientists and engineers

The Earth Sciences Division is engaged in all of these important areas — striving to achieve both relevance and excellence in the scientific research we perform. In this annual report we present examples of our research projects in the context of national problems that we are seeking to address. While it is not a complete accounting, it is representative of the nature and breadth of our research program.

One of our most significant accomplishments over the past several years is development of a new level of understanding of water transport in deep, fractured vadose zones. Our efforts are driven largely by the DOE's Yucca Mountain Project, which seeks to evaluate Yucca Mountain, Nevada, a potential geologic repository that can

safely store nuclear wastes over tens to hundreds of thousands of years. Key scientific challenges include evaluating how much and how quickly water moves from the potential repository to groundwater supplies down gradient of the site, predicting how much water will come in contact with the waste canisters, and how these factors are influenced by the heat generation of waste-filled canisters. Answering these questions requires a multi-faceted approach, combining large-scale three-dimensional modeling with smaller scale process models and experiments that include effects of individual features such as drifts, fractures, and canisters. Through the collective efforts of hydrologists, geologists, geochemists, and geophysicists, a whole new level of confidence and understanding has been achieved. New insights into the role of fracture and matrix heterogeneity have been developed. We now understand how the complex interaction between fractures and the rock matrix impacts water seep-

Robert Trautz taking samples from the water collection system at Yucca Mountain, Nevada.

age into drifts. What's more, our ability to predict how the complex interplay of thermal, capillary, and gravitational forces influences liquid water and vapor water transport has been refined and tested. These accomplishments strengthen the scientific foundation upon which important decisions are made about how nuclear waste will be managed, not only in the United States, but internationally.

We have also made significant advances in our ability to image subsurface structures and processes. Oil and gas production in mature fields or fields with low permeability requires high-resolution images of structures and processes to guide and control production strategies. We have developed a new way of mapping the permeability structure of oil fields that uses water-cut data from producing wells, combined with ray-path inversion methods borrowed from seismic imaging. Since water-cut data are available from almost every oil field, this approach provides a powerful new tool for permeability mapping in developed fields. Producing oil from low-permeability oil fields such as the diatomite formations in the Central Valley of California is a big challenge. This is because production rates are too low to be economical if hydraulic fracturing in combination with injection of water or steam is not used to drive the oil out of the pore spaces in the rock. However, injection can lead to fracture extension that, if not immediately detected and properly controlled, can quickly break through to the overburden

or producing wells. Once this happens, much of the oil is left behind and cannot be removed from the rock. We have developed an approach, using optimal control theory, to detect fracture extensions and control them through modulating injection rates. Through close working relationships with the oil and gas industry, these and other technologies are already being employed to enhance the productivity and lower the cost of domestic oil and gas production.

We are also making important inroads into understanding how biogeochemical interactions with contaminants influence their fate, transport, and bioavailability. Cost-effective and permanent remediation of soils and groundwater requires a fundamental understanding of the behavior of contaminants in subsurface environments. We have developed new synchrotron-based methods for probing these interactions on the scale at which it is possible to directly observe the interaction between individual microbial communities and contaminants. One such study demonstrates the simultaneous growth of a microbial community, reduction of chromium(VI) to chromium(III), and degradation of toluene. Experiments such as this are made possible by the Advanced Light Source, which provides a combination of infrared spectro-microscopy and micro-x-ray absorption spectroscopy. Another study shows how diffusive transport combined with microbial reduction at a sediment/pond interface quickly reduces selenium to insoluble forms within less than 1 cm of the soil surfaces. Fundamental studies such these provide the foundation for evaluating the effectiveness of both natural and accelerated

Jiamin Wan and Tetsu Tokunaga with glass micromodel they developed. *Pseudomonas putida* mt-2 biofilms are grown in this partially water-saturated porous network, with toluene as the sole carbon source.

Berkeley Lab has developed cryogenic drilling, a technique used for drilling environmental monitoring and remediation wells in unstable soils and rock by freezing the borehole wall with nitrogen.

bioremediation. In addition to understanding these processes, the ability to diagnose and monitor them is also essential. Scientists in our Center for Environmental Biotechnology, together with our Center for Isotope Geochemistry, have developed new methods for combining stable and unstable isotopes of carbon to monitor degradation rates of organic contaminants in subsurface environments. These are just a few of the scientific investigations and technology development projects that are aimed at expanding the set of tools available for remediating DOE's contaminated soils and sediments.

Over the past year we have also begun to focus our attention on the important problem of climate variability and climate change. Together with the University of California at Berkeley, we have established a Center for Atmospheric Sciences. Three new projects are described in this report that launch this effort. Over the coming years we expect this program to grow in size and impact to become an important part of our program — striving to achieve the standard of relevance and excellence that we have set for ourselves in the Earth Sciences Division.

ORGANIZATION OF THIS REPORT

This report is divided into six sections, which correspond to the major research programs in the Division:

- Subsurface Geosciences
- Center for Isotope Geochemistry

- Nuclear Waste
- Energy Resources
- Environmental Remediation Technology
- Center for Environmental Biotechnology

ACKNOWLEDGMENTS

The Earth Sciences Division consists of over 170 scientists and engineers. All of us would like to acknowledge the support of our sponsors in the U.S. Department of Energy. We gratefully appreciate the variety of assistance they provide to us, including financial and intellectual, and sometimes just a pat on the back. We also appreciate the support we receive from other federal agencies, including the U.S. Bureau of Reclamation, Department of Defense, and the Environmental Protection Agency. These activities support and enrich our programs by broadening the range of applications of our research. We also appreciate support from our industrial collaborators and colleagues, both financial and through partnerships. These relationships bring us ideas, data, and experience.

Sally M. Benson
Earth Sciences Division Director

Jil Geller is monitoring water seepage through a natural rock fracture covered by a transparent replica of the top half of the fracture. This rock fracture was inoculated with microorganisms cultured from an undisturbed core taken from Idaho National Engineering and Environmental Laboratory.

[HTTP://WWW-ESD.LBL.GOV](http://www-esd.lbl.gov)

Subsurface Geosciences Department

Ernest L. Majer,
Subsurface Geosciences
Department Head

The mission of the Subsurface Geosciences Department is to provide a fundamental base of knowledge in the earth sciences to support the Earth Sciences Division's and DOE's programmatic goals in energy resources, nuclear waste disposal, environmental remediation, global climate change, and fundamental investigation of the subsurface. Our approach is to maintain and draw upon our core areas of expertise in vadose zone and fracture hydrology, reservoir engineering, seismic and electrical geophysics, isotope geochemistry and rock/soil physics.

The principal issues driving the research are centered around scaling from the molecular level to the field, adequate prediction and inclusion of complex effects such as anisotropy and heterogeneity, and dealing with coupled processes.

The research within the Department is divided into two groups and two centers.

- Subsurface processes and processes monitoring
- Subsurface imaging
- Center for Computational Seismology
- Geosciences Measurement Center

As a whole, the research involves theoretical, laboratory, field, and interpretational work, addressing coupled processes and heterogeneity at a variety of scales. Much of the research also uses Berkeley Lab research facilities such

as the Advanced Light Source (ALS) and the National Energy Research Supercomputing Center (NERSC).

SUBSURFACE PROCESSES AND PROCESS MONITORING

This group's research has concentrated on multiphase fluid flow and processes in earth materials. A large focus has been on rock-fluid interactions in fractured media, issues closely associated with nuclear waste disposal and geothermal energy production. This group is also involved in research to understand the fundamental behavior of surface chemistry under a variety of conditions. The goal of this work is a better knowledge base of complex interactions in the subsurface, which is necessary for the prediction of a variety of dynamic earth processes.

SUBSURFACE IMAGING

The Subsurface Imaging group uses electrical and seismic methods to image both static and dynamic properties of the earth. The scale ranges from the core scale (10s of cm) to the whole earth. A primary focus has been to combine geophysical methods for directly imaging properties controlling fluid flow and transport. In addition, the work in subsurface imaging is a well-balanced effort in the numerical modeling and theory of wave propagation (both elastic and electromagnetic), field validation and experimentation, and data processing and interpretation. This provides a broad development base that balances theory with practice.

CENTER FOR COMPUTATIONAL SEISMOLOGY

The Center for Computational Seismology focuses on developing and applying seismic imaging and earthquake source mechanism theory to improve the ability to understand static and dynamic properties of the subsurface. Projects range from whole-earth imaging methodology to fine-scale tomographic imaging of cores. The Center also provides a computational facility and base of support that integrates and leverages many different seismic and geophysical projects.

GEOSCIENCES MEASUREMENT CENTER

This effort involves the development, fabrication, planning, and execution of a variety of laboratory and field experiments. The focus of the Geosciences Measurement Center is to provide a base of expertise to support unique field and laboratory experiments developed throughout the entire Earth Sciences Division. It is a mix

of technical, engineering, and scientific expertise brought together to address a variety of field and laboratory experiments in fluid flow and transport, microbial behavior, and geophysical imaging.

FUNDING

Most of the funding for the Subsurface Geosciences Department's work is drawn from the Office of Basic Energy Research, Division of Engineering and Geosciences, and the Office of Biological and Environmental Research. However, a significant amount of funding is also drawn from other government funding programs involving basic research. Examples are the U.S. Environmental Protection Agency and the U.S. Geological Survey.

Crosswell Seismic Tomography in Basalt Flows at the INEEL TAN Site

T. M. Daley, J. E. Peterson,
and E. L. Majer

RESEARCH OBJECTIVES

The TAN (Test Area North) site at Idaho National Engineering and Environmental Laboratory (INEEL) is a mixed waste site currently undergoing clean-up activities. In 1996 we began seismic crosswell studies designed to study the heterogeneity of the basalt flows containing the aquifer beneath the TAN site. This research is part of an integrated physical (geophysical and hydrologic) and microbial study program using innovative geophysical imaging and microbial characterization methods to identify key scales of physical heterogeneities that affect the biodynamics of natural subsurface environments. Data from controlled laboratory and *in-situ* microbial experiments are being used in conjunction with our seismic imaging to determine the dominant physical characteristics (lithologic, structural, and hydrologic) that can be imaged *in situ* and correlated with microbial properties. A goal of the seismic imaging at this site is to identify fundamental scales of variation of physical parameters that control transport behavior relative to predicting subsurface microbial dynamics.

APPROACH

High-resolution seismic measurements were used to obtain information on location of fractures, layer continuity, layer thickness, and other structural and lithologic features so that improved predictive models of flow and transport can be developed and applied to microbial behavior and distribution. The TAN site basalt flows have fluid flow controlled by both sedimentary lens interbeds and fracture zones. In this application, geophysical measurements were made between holes to assess the continuity and homogeneity of the intervening material.

The geophysics concentrated on obtaining crosswell seismic data at the sub-meter resolution scale at several wells in the TAN area. In the initial field session, tomographic imaging was carried out for 10 crosswell pairs using 9 different wells. The seismic data were acquired with Berkeley Lab's high-frequency crosswell system. Data were recorded at frequencies over 3,000 Hz using 0.5 m source/sensor spacing. Large variations in attenuation were observed, limiting our imaging ability in some regions. Seismic velocity

inversions (tomograms) were produced for 5 well pairs. An example is the T-GRW/TAN-9 well pair, which produces a complete velocity tomogram (Figure 1) over the depths surveyed (approximately 65 to 100 m). The ray coverage was good from 64 to 94 m, and the inversion showed little effect of any deviations of the wells.

RESULTS

The tomographic results show three low-velocity zones: one about 2-m thick between depths of 66 and 68 m, which corresponds to a high flow zone; a thicker one at a depth of 74 to 78 m, which corresponds to a sedimentary lens; and one at a depth of 85 to 87 m, which corresponds to a low-velocity zone seen in the other well pairs. The middle low-velocity zone is the thickest and contains the lowest velocities, well below 3 km/s, indicative of sedimentary materials. In addition to velocity tomography, which utilizes one piece of information from the recorded seismograms (i.e., the first arrival time), we use relative amplitude and spectral content. Figure 2 shows seismograms and spectra with true relative amplitude as a function of depth for the T-GRW/TAN-9 well pair. We see low amplitude regions from 72.5 to 77 m and 84 to 85 m, which correspond to sedimentary interbeds in the basalt flows. The high-amplitude, high-frequency zones such as 69 m and 90 m are interpreted as low-permeability, minimally fractured material. Figure 2 also shows the submeter resolution obtainable for variations in material properties when quality high-frequency seismic crosswell data can be obtained.

From the seismic imaging several results are evident. The geology of the surveyed area is quite varied, with large changes in seismic velocity and attenuation with depth. From our experience in other fractured environments, this indicates extreme variability in fracture/rock properties and also indicates fracture permeability. The scale of heterogeneity is equal to the 0.5 m sampling interval and seismic wavelengths used in this survey.

From the seismic imaging several results are evident. The geology of the surveyed area is quite varied, with large changes in seismic velocity and attenuation with depth. From our experience in other fractured environments, this indicates extreme variability in fracture/rock properties and also indicates fracture permeability. The scale of heterogeneity is equal to the 0.5 m sampling interval and seismic wavelengths used in this survey.

SIGNIFICANCE OF FINDINGS

Crosswell seismic data utilizing high-frequency sources can obtain submeter

Figure 1. Seismic velocity tomogram between wells T-GRW and TAN-9.

Figure 2. Zero-offset (i.e., equal source/receiver depth) seismograms (top), and spectra (bottom) in true relative amplitude, as a function of depth, for wells T-GRW and TAN-9.

resolution of heterogeneity in the complex environment of fractured basalt flows with interbedded sedimentary lenses. The heterogeneity imaged with seismic techniques can be correlated with flow properties in the saturated zone of the basalt flow.

RELATED PUBLICATION

Majer, E. L., J. E. Peterson, T. Daley, B. Kaelin, L. Myer, J. Queen, P. D'Onfro, and W. Rizer, Fracture detection using crosswell and single well surveys, *Geophysics*, 62, 495-504, 1997.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Environmental Science Management Program; and by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

GPR-Assisted Saturation and Permeability Estimation in Bimodal Systems

S. Hubbard, Y. Rubin, and E. L. Majer

RESEARCH OBJECTIVES

Much of the problem and initial cost of subsurface remediation comes from field site characterization. Three-dimensional information about the heterogeneous subsurface is needed in order to identify the key controls on the flow and contaminant transport processes. Recent studies have recognized that natural heterogeneity and the large spatial variability of permeability predominantly control the flow field and hence the transport. Moreover, natural heterogeneity exhibits variability over a wide range of scales and therefore is difficult to characterize due to scarcity of data and costliness of conventional field sampling techniques such as drilling. With poor site characterization, remediation schemes are unnecessarily expensive because costly over-design may be required to compensate for uncertainty. Incorporation of two- and three-dimensional densely sampled geophysical data with conventional hydrological data increases the amount of data available for characterization. This incorporation has the potential to significantly improve the hydraulic estimates over those obtained from borehole data alone.

The purpose of this paper is to explore the use of ground penetrating radar (GPR) data for estimating saturation and permeability in bimodal systems. In these systems, the petrophysical relationships used to transfer the geophysical measureables into hydrological parameters are often nonunique. Therefore, it is difficult to obtain a single estimate of permeability or saturation given a geophysical measurement at a particular location. In this paper, we propose a methodology for addressing this estimation problem.

APPROACH

We performed numerical experiments to investigate the general utility of ground penetrating radar (GPR) data for saturation

and permeability estimation under a range of hydrogeological conditions (Hubbard et al., 1997). GPR is a noninvasive, high-resolution geophysical method. When acquired in the

common-midpoint or crosshole tomographic acquisition modes, estimates of dielectric constants can be obtained from the recorded radar electromagnetic wave travel times. Petrophysical relations can then be used to transfer these dielectric constants into saturation or permeability estimates.

We performed several case studies on synthetic bimodal geologic systems, where each system was composed

of a sand facies together with another facies having a larger clay volume fraction, and where each facies had a characteristic permeability. The geologic domains were constructed using indicator simulation routines. Model saturation fields were obtained by numerically simulating two-dimensional water flow through the synthetic domains for a limited time period, at which time radar data acquisition and processing were simulated. The resulting synthetic two-dimensional dielectric constant fields represented geophysical field data potentially available for estimation of saturation and permeability. Figure 1(a) illustrates an example of a dielectric constant field obtained from collecting synthetic radar data through an unsaturated bimodal system composed of a sand and a clay facies. Expected saturation values, shown in Figure 1(b), were obtained by ordinary kriging of saturation measurements taken from four wellbores whose locations are annotated above the figure. The petrophysical curves that illustrate the relationships between the facies (and corresponding permeability) for this sand-clay system are shown in Figure 1(c) (reduced from Knoll et al., 1995). These curves illustrate that nonuniqueness exists when trying to map a geophysical attribute (dielectric constant obtained from radar data)

Figure 1. (a) Dielectric field cross section potentially available from radar data. (b) Expected value of saturation obtained from kriging borehole saturation measurements. (c) Petrophysical curves illustrating the relations between dielectric constant and fractional water saturation for a sand-clay system (reduced from Knoll et al., 1995). (d) Saturation estimates obtained using information displayed in Figures 1(a)–(c) in a maximum likelihood formalism. Sw is water saturation.

into a hydrological estimate (saturation or permeability). For each dielectric constant value obtained from the radar data in a bimodal system, there are two possibilities of saturation (S_1 and S_2), depending on whether the facies at that subsurface location is a clay (with associated permeability k_1), or a sand (with associated permeability k_2).

We now want to estimate the most likely value of saturation at each subsurface location, given the options presented from the radar data and petrophysical curves. To do this, we define saturation as random function described by a binomial pdf. If S_1 is the saturation value associated with the clay facies and S_2 is the saturation value associated with the sand facies, the pdf for saturation (S) can be expressed as:

$$f(S) = P\delta(S - S_1) + (1 - P)\delta(S - S_2), \quad (1)$$

where δ is the Dirac delta and P is the probability such that

$$S = \begin{cases} S_1 & \text{prob} = P \\ S_2 & \text{prob} = 1 - P \end{cases} \quad (2)$$

From Eqs. (1) and (2) we obtain the relation between P and $\langle S \rangle$, where $\langle \rangle$ denotes the expected value operator:

$$P = \frac{\langle S \rangle - S_2}{S_1 - S_2} \quad (3)$$

In Eq. (3), $\langle S \rangle$ can be estimated using borehole measurements [Figure 1(b)], and S_1 and S_2 can be obtained using the dielectric constants from radar data [Figure 1(a)] together with the petrophysical relationship [Figure 1(c)]. The value of P can be estimated for each subsurface location; this value indicates which saturation estimate (S_1 or S_2) is closest to the expected value at that location. The value of P can then be used in a maximum likelihood (ML) formalism to choose which saturation option is optimal for each subsurface location. Figure 1(d) displays the saturation estimates obtained using the information shown in Figures 1(a)–(c) with this ML technique. When compared to the model saturation field, these estimates were correct 97.8% of the time.

Permeability can also be defined as a random function and described by a binomial pdf. The methodology presented above can be used to choose the optimal permeability value at each subsurface location given the two options presented from the radar data and petrophysical relationships. Using this ML technique, the corresponding permeability estimates obtained [for the same system and using the dielectric data shown in Figure 1(a)] yielded permeability estimates that were correct 93% of the time when compared to the model permeability field.

RESULTS

Numerical case studies were repeated using this methodology on geologic domains composed of different facies combinations and with radar data corrupted with different levels of noise. Case study results suggest:

- Saturation estimates are improved over those estimates obtained from borehole information.
- Saturation estimates are optimal when the system is most homogeneous.
- Intrinsic permeability estimation is improved using GPR over those estimates obtained using wellbore data alone when the system is heterogeneous. As the system becomes homogeneous, the method loses the capability to distinguish between the components of the system.

SIGNIFICANCE OF FINDINGS

This study suggests that GPR data are potentially useful for providing saturation and permeability estimates. The proposed technique extends the time domain reflectometry (TDR) concept of using electromagnetic signal travel times to estimate a one-dimensional profile of water content, to using GPR travel times to estimate two-dimensional cross sections of both saturation and intrinsic permeability. This method should be especially advantageous in areas favorable for GPR data acquisition where detailed resolution is required but drilling of numerous boreholes is prohibited owing to the time and cost incurred as well as specific site limitations.

RELATED PUBLICATION

Hubbard, S. S., Y. Rubin, and E. Majer, Ground-penetrating-radar-assisted saturation and permeability estimation in bimodal systems. *Water Resour. Res.* 33(5), 971–990, 1997.

REFERENCE

Knoll, M., R. Knight, and E. Brown, Can accurate estimates of permeability be obtained from measurement of dielectric properties?, *SEGEEEP Annual Meeting Extended Abstracts*, Environ. and Eng. Geophys. Soc., Englewood, Colo., 1995.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Environmental Science Management Program; and by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U. S. Department of Energy under Contract No. DE-AC03-76SF00098.

Hydrogeological Parameter Spatial Correlation Structure Inference Using Geophysical Data

S. Hubbard, Y. Rubin, and E. L. Majer

RESEARCH OBJECTIVES

Flow and transport modeling requires as input a regular grid of hydraulic conductivity values. Because exhaustive permeability measurements are not obtainable, stochastic simulation methods are often used to produce these regular grids, given spatial correlation information. Wellbore data are sometimes useful for obtaining information about the correlation structure in the vertical direction, but the measurements are rarely dense enough in the horizontal direction to provide information about the horizontal spatial correlation structure. Further exacerbating the quest for correlation structure information, different measuring devices sample the subsurface with different support scales, and experimental studies indicate that the correlation scale is a function of the scale of the observation relative to the scale of the heterogeneity.

We have investigated use of radar and seismic tomographic data to supplement hydrogeological measurements in the spatial correlation structure inference procedure. Although we find that high-resolution geophysical data are useful for obtaining estimates of hydrological parameters, in practice the geophysical data often sample only a portion of the aquifer under investigation. At the tomographic profile locations, permeability estimates obtained from these data can be used to describe that portion of the study volume. For the remainder of the study volume, stochastic simulation techniques are commonly used to generate hydrogeological values. These techniques require as input information about the parameter's spatial covariance structure. This paper focuses on using high-resolution tomographic data together with limited borehole data to infer the log-permeability spatial correlation structure.

APPROACH

We performed three numerical case studies where scales of geophysical data measurements were varied relative to scales of heterogeneity. Data assumed available for all case

studies included permeability measurements from core samples and tomographic geophysical data. Our inference procedure was performed in the spectral domain, where analysis of data having different support scales and spatial sampling ranges was facilitated. In this domain, the spectral density curve is the analog to the experimental variogram. Dense wellbore data may measure the high frequency, or, when working with spatial information, high wavenumber variations of the measured property, while geophysical data may measure variations occurring at the lower end of the wavenumber spectrum. As data with different support scale and sampling ranges occupy different areas in the wavenumber domain, the ability to estimate the spatial statistical structure from the spectral density curves varies as a function of the measurement data support scale relative to the scale of heterogeneity.

Here we present a *single case study* designed to investigate the usefulness of high-resolution crosshole seismic data as an aid to statistical structure inference when the resolution obtainable from the geophysical data is less than the scale of the heterogeneity. For this study, we simulated a model permeability field with an exponential log-permeability covariance function using a sequential simulation routine. This field was transformed into a core-scale velocity field using a velocity-permeability petrophysical relationship developed by Rubin et al. (1992). Forward geophysical modeling was performed through this field using seismic data acquisition parameters common for detailed characterization projects. Ten percent random noise was added to the raw geophysical data, and these "corrupted data" were inverted to yield the 2D velocity field shown in Figure 1(a). This figure represents field geophysical data potentially available to us for spatial correlation inference. We assumed for this study that dense permeability measurements were available to us from a few half-meter core sections extracted from the single borehole annotated above Figure 1(a).

Seismic and core information was transformed into the wavenum-

Figure 1. (a) Synthetic tomographic velocity data. (b) Spectral density curves obtained from analysis of core (top left) and seismic (top right) information in the vertical direction.

ber domain using fast Fourier transforms. Spectral density curves were calculated in vertical direction for the core data [Figure 1(b) upper left] and in the vertical and horizontal directions for the seismic data. Using the petrophysical relationships, the seismic velocity spectra were transformed into an estimated log-permeability spectrum. The spectral curves obtained from analysis of seismic data in the vertical direction are shown in the upper right corner of Figure 1(b). These spectral density curves can be fit using automatic procedures to solve for the hydrological parameters of interest; e.g., the integral scale in the vertical direction can be estimated by fitting the upper curves in Figure 1(b) with the 1D spectral expression corresponding to an exponential covariance:

$$S(k) = \frac{\sigma^2 I}{\pi(1 + k^2 I^2)}, \quad (1)$$

where S is spectral density, k is wavenumber, I is the integral scale, and σ^2 is the variance of the log-permeability. The spectrum represents distribution of variance over wavenumber; hence variance can be estimated from the spectral density curve itself and then used within Equation (1) to solve for the integral scale. Using this approach, the core spectral density curve [Figure 1(b), top left] was fit with Eq. (1) to yield a vertical integral scale estimate of 5.8 cm. Similar analysis of the geophysically obtained spectra shown in Figure 1(b) (top right) was performed to yield a vertical integral scale of 14.8 cm. Analysis of the model permeability field revealed that the actual vertical integral scale is 13.3 cm [Figure 1(b), bottom right]. Thus, the true heterogeneity is not accounted for using information from limited core sections or geophysical data alone. We investigated the usefulness of combining data to yield a better vertical integral scale estimate. Spectral curves obtained from seismic and core data were combined [Figure 1(b), bottom left] to yield a complete spectrum, with information from seismic data covering the lower wavenumber portion of the domain, and information from core data covering the higher wavenumber portion. When this combined spectrum was fit using Eq. (1), a value of 13.4 cm was obtained for the vertical integral scale, which is more similar to the model permeability vertical integral scale of 13.3 cm [Figure 1(b), bottom right] than those estimates obtained using either geophysical or hydrological measurements alone.

RESULTS

Although we discussed only one case study in detail, the results of all three studies suggest the following. Geophysical data alone can be used successfully to infer the spatial correlation structure of an aquifer when geophysical resolution is high compared to the scale of

the heterogeneity. If geophysical data resolution is low compared to the scale of the heterogeneity, measurements with a smaller support scale such as core measurements must be incorporated with the data to accurately infer spatial correlation structure. Geophysical data are capable of yielding critical information about the correlation structure in the horizontal direction. This information is very difficult to obtain using conventional borehole data. In hierarchical geological environments, or in systems where there is more than one level of variability, geophysical data can be used to estimate the spatial correlation structure of the level of heterogeneity that shares a similar support scale as the geophysical data measurements. An example of a hierarchical system is an aquifer composed of several geologic facies (i.e., sand, silt, and clay facies) where there is a large-scale spatial variability associated with the geometry of the facies packages and a smaller scale heterogeneity associated with the intra-facies variability. If the resolution of the geophysical data is low compared to the within-facies variability, but is on the same order as the variability of the facies geometry, it may be possible to extract information about the larger scale of heterogeneity using the geophysical data.

SIGNIFICANCE OF FINDINGS

These results suggest collection of a few cross-hole profiles and interpretation of these tomographic profiles along with limited wellbore data can yield spatial correlation structure information traditionally only obtainable by performing extensive and intrusive hydrological sampling. Geophysical data may provide critical spatial correlation information at a lower cost, more efficiently, and less invasively than conventional characterization techniques.

RELATED PUBLICATIONS

- Hubbard, S. S., Y. Rubin, and E. Majer, Estimation of hydrological model parameters from spectral analysis of high-resolution geophysical data, *EOS*, 78(48), 1997.
- Rubin, Y., Mavko, G., and Harris, J., Mapping permeability in heterogeneous aquifers using hydrological and seismic data, *Wat. Resour. Res.*, 28(7), 1809-1816, 1992.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Environmental Science Management Program; and by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098..

Acoustic Visibility of Immiscible Liquids in Poorly Consolidated Sand

RESEARCH OBJECTIVES

Detection and characterization of nonaqueous phase liquids (NAPLs) in poorly consolidated, water-saturated sands are of great importance in petroleum and environmental engineering. Prohibitively expensive drilling procedures as well as the potential for accidental liquid mobilization during drilling procedures make noninvasive testing optimal for subsurface characterization of contaminated or oil-bearing sites.

In poorly consolidated sand with weak intergranular cementation and low effective stresses, acoustic waves are sensitive to pore fluid properties. Therefore, with sufficient contrast between pore liquids, their distributions can be visualized using tomographic inversion techniques (e.g., velocity contrast for travel time tomography, attenuation contrast for amplitude tomography, or impedance contrast for diffraction tomography). The success of these methods in practice is likely to depend on the fluid properties and the volumetrics and geometry of the target fluid. While the work by Geller and Myer (1995) and Seifert et al. (1997, 1998) indicates strong sensitivity of seismic wave propagation to the presence of immiscible liquids in sand packs, these experiments were conducted in one-dimensional, 5-cm-long columns at ultrasonic frequencies, and could therefore not address upscaling issues. The main objectives of the current research are to detect and visualize three-dimensional distributions of NAPLs using lower-frequency (~60 kHz) acoustic waves.

APPROACH

To investigate the acoustic visibility of nonaqueous phase liquids in poorly consolidated sands, laboratory experiments were conducted in a 0.6-m-diameter confining cell with water-saturated sand. A radial confining pressure of 20 psi was applied to the cell to simulate consolidation conditions typically encountered in the shallow subsurface. Cross-hole data sets were then collected before and after dodecane, a lighter than water nonaqueous phase

M. B. Kowalsky, J. T. Geller, P. K. Seifert,
K. T. Nihei, and L. R. Myer

liquid (LNAPL), was injected into the bottom of the cell. Measurements were taken for 40 source positions and 40 receiver positions at 1-cm spacing (Figure 1) using a source excited by a 60 kHz single cycle sine wave.

Dodecane was chosen as the injection liquid because of its chemical and acoustic properties as a target fluid in water (specific gravity of 0.745, acoustic velocity of 1,290 m/s, which is 14% lower than the velocity in water, and viscosity of 1.278 kPa-s). By injecting from the bottom of the tank, buoyancy forces were expected to cause the LNAPL to finger upward, leaving residual LNAPL segments along the flow paths. This transport mechanism is analogous to the downward migration of denser than water NAPL (DNAPL) contaminants in groundwater aquifers. Also, the dodecane was dyed red to aid in identifying its distribution during the tank excavation conducted after the acoustic measurements.

RESULTS

The zero-offset waveforms, taken while the source and receiver are diametrically opposed and at equal depths, are shown in Figure 2 for the baseline and post-injection surveys. The baseline data show nearly constant velocities (± 0.4 m/s), but variable trough-to-peak amplitudes ($\pm 20\%$) without systematic trend. After dodecane injection, the recorded waveforms differed dramatically from the reference waveforms: the

largest velocity decrease of about 2% occurred at around a 50 to 60 cm depth. The amplitude decreased by about 35% at around 40 cm, and by as much as 65% at the same elevation where the velocity decrease was observed. The measured waveforms also contain reflections from the tank walls (immediately behind the first P-wave arrival and at near 440 μ s). Careful observation also reveals the arrival of scattered waves, occurring at oblique angles and originating from the peripheries of the low amplitude/low velocity

Figure 1. Experimental set-up used for acoustic scanning of dodecane injection.

zones and from the top and bottom of the tank.

Following the LNAPL injection and crosswell imaging, the tank was excavated by pressing a rigid-walled grid with $5 \times 5 \times 10$ cm-deep cells into the sand and then collecting and measuring the volume of the sand/water/dodecane mixture from each cell. The excavation indicated a distribution of residual dodecane throughout the depth of the tank. The depth of maximum concentration and lateral distribution of the LNAPL agreed well with the depth where the maximum attenuation and velocity decrease were observed.

Straight ray amplitude and velocity tomography was also performed on the collected waveforms using waveform first arrivals. While the velocity difference tomography worked reasonably well in locating the dodecane zone at a depth of 50–60 cm, the smaller dodecane features were not resolved that were apparent from amplitude variation in the raw waveforms. In amplitude difference tomography, regions of large attenuation corresponded to the low-velocity regions in the velocity difference tomogram, but again, small features were not visible. Both the speculated diffraction patterns observed in the zero-offset waveforms and the analysis by Seifert et al. (1998) indicate that wave scattering, and not intrinsic attenuation, may be the most significant attenuation mechanism in the NAPL/water/sand mixture. Imaging methods that utilize amplitudes of the direct and scattered waves are likely to enhance the detection and delineation of LNAPLs.

Figure 2. Density plot of waveforms taken before and after injection of dodecane, an LNAPL, shows after injection a maximum decrease in velocity and amplitude from 50 to 60 cm depth (although significant attenuation is observed throughout the entire depth).

SIGNIFICANCE OF FINDINGS

These experiments show promise for the imaging of immiscible liquids in porous media at increased scales and lower frequencies. Though P-wave velocity changes in the presence of immiscible liquids, for the small NAPL volume and scale of this experiment, these changes are small (on the order of several percent). Amplitude differences in the first arrival, presumably due to scattering, are much larger (up to 65%) and may enable higher resolution imaging of the

LNAPL. Thus, while it may be possible to locate LNAPL fingers in saturated sediment with acoustic velocities, the use of direct and scattered wave amplitudes may lead to improved acoustic visibility.

RELATED PUBLICATIONS

- Geller, J. T., and L. R. Myer, Ultrasonic imaging of organic liquid contaminants in unconsolidated porous media, *J. of Contam. Hydrol.*, 19, 85–104, 1995.
- Seifert, P. K., J. T. Geller, and L. R. Johnson, Effect of P-wave scattering on velocity and attenuation in unconsolidated sand saturated with immiscible liquids, *Geophysics*, 63(1) 161–170, 1998.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract DE-AC03-76SF00098; and by the Director, Air Force Office of Scientific Research under Contract AFOSR-960010, through the U.S. Department of Energy under Contract DEF60293ER14391. We would like to acknowledge and thank Roland Gritto and John E. Peterson, Jr., for their contributions on the tomography.

3D Boundary-Domain Finite Element Method for Electromagnetic Modeling

G. Xie, J. Li, and G. Moridis

RESEARCH OBJECTIVES

Three-dimensional electromagnetic (EM) forward modeling and inversion algorithms play an important role in geophysical exploration, oil reservoir management, and environmental site characterization. The new Global Integral and Local Differential (GILD) parallel modeling and nonlinear inversion algorithm is designed to overcome the limitations of conventional inversion. The advantages of this algorithm are as follows. (1) GILD uses a new exact global boundary integral equation and local differential equation in the domain that reduces the numerical boundary noises and improves accuracy of the modeling and inversion. (2) It uses a new global integral and local differential decomposition in inversion that decomposes the ill-posed full matrix into 4^n small sparse matrices and a smaller full matrix, which greatly improves the ill-posed condition and reduces computation time and storage requirements. (3) GILD is a high-performance parallel multiple hierarchy algorithm with parallel efficiency of 96%. (4) It minimizes data communication between processors that is suitable for the architecture of the massively parallel computer T3E with distribution memory. (5) The GILD parallel algorithm can be very useful in solving elliptic, parabolic, and hyperbolic modeling and inversion in the T3E that can benefit it by expanding the T3E's applications in sciences and engineering. (6) The new volume integral equation and boundary integral equation for magnetic field are created and employed in the GILD modeling and inversion. In this report, we discuss the development of a 3D boundary-domain finite element method for EM modeling using a new boundary EM integral-differential equation. The algorithm and software are important components of the new GILD modeling and inversion for new coupled GEO-HYDRO high-resolution imaging. The new high-resolution imaging software will be an essential tool for the oil, gas, coal, and geothermal energy geophysical exploration and environmental restoration of contaminated sites and nuclear waste.

APPROACH

New GILD Nonlinear Inversion. The new GILD inversion method consists of the following five parts. (1) The domain is decomposed into subdomain SI and subdomain SII. (2) A new global boundary magnetic or seismic integral equation on the boundary and local magnetic or seismic differential equations in the domain will be used together to obtain EM field or seismic wave in the modeling step. (3) The new global magnetic or seismic Jacobian volume integral equation in SI and the local magnetic or seismic Jacobian differential equations in SII will be used together to update the electric

conductivity and permittivity, and seismic velocity from the magnetic field data and seismic wave data in the inversion step. (4) The subdomain SII can naturally be decomposed into 4^n smaller sub-cubic-domains; the sparse matrix in each sub-cubic-domain can be

inverted separately, in parallel. (5) A new parallel multiple hierarchy substructure direct algorithm, a new parallel multiple hierarchy preconditioned conjugate gradient, or Lanczos iteration will be used to solve the smaller 2×2 block matrices in SI from domain to the boundary, recursively and in parallel.

A New 3D Volume Integral Equation for Magnetic Field.

$$H(r) = H_b(r) - \int_V \frac{(\sigma - \sigma_b) + i\omega(\epsilon - \epsilon_b)}{\sigma + i\omega\epsilon} \nabla_r \cdot g(r, r') \times (\nabla_{r'} \times H - J) dr' + \int_V \frac{(\sigma - \sigma_b) + i\omega(\epsilon - \epsilon_b)}{\sigma + i\omega\epsilon} \nabla_r \times G_b(r, r') (\nabla_{r'} \times H - J) dr' \quad (1)$$

A New 3D Boundary Integral Equation for the Magnetic Field. The new boundary integral-differential equation for the magnetic field is

$$MH(r) = H_b(r) + \frac{1}{i\omega\mu} \oint_{\partial\Omega} \left[\left(\frac{1}{\sigma + i\omega\epsilon} \nabla_{r'} \times G_b(r', r) \right) \times H(r') \right] \cdot ds - \frac{1}{i\omega\mu} \oint_{\partial\Omega} \left[\left(\frac{1}{\sigma + i\omega\epsilon} \nabla_{r'} \times H(r') \right) \times G_b(r', r) \right] \cdot ds, \quad (2)$$

New GILD Modeling. The collocation finite element method (FEM) was used to discretize the new EM boundary integral-differential equation, and the Galerkin FEM to discretize the internal domain EM differential equation (BDFEM). The differential term in the boundary integral-differential equation can be naturally discretized into the FEM terms. The boundary FEM equations and the domain FEM equations are coupled into the completed BDFEM equation system. A new parallel decomposition and multi-level algorithm from the internal domain to the boundary can be used to solve the BDFEM equation.

Parallel Multilevel Algorithm. A parallel Boundary-Domain Finite Element Method algorithm is presented as follows. (1) The domain is decomposed into the two parts, SI and SII (Figure 1). SI is a set elements of the nodes on the boundary, SII is a set of the nodes in the internal domain. The finite element matrix equation in the internal domain SII is sparse. The SII is decomposed into 4^n sub-domains SII(l), for example, $l=1, 2, \dots, 4^3$. (2) The 4^n parallel elements (PEs) in the T3E-type MPP computer will be used to solve 4^n submatrix equations, in parallel. (3) The modeling is reduced into the matrix equation on a new mesh domain

(Figure 3). The internal mesh of the new domain is reorganized into 4^{n-1} groups. The 4^n PEs are divided into 4^{n-1} groups, with 4 PES in each group. The 4^{n-1} groups of PES are used to solve the 4^{n-1} group sub-matrix equation, in parallel. This processor is called a parallel multiple hierarchy substructure algorithm (Xie and Li, 1998). (4) Finally, a complete finite element matrix equation on the boundary is obtained. A parallel LU decomposition is used to solve the boundary matrix equation, and the magnetic field on the boundary will be obtained. By backward processing, the magnetic field in the internal domain can be obtained. The boundary integral representation can be used to calculate the magnetic field in the out-of-domain in parallel. The boundary integral representation is similar to step (1) but with $M=I$, r in the out-of-domain, and r' on the boundary.

In steps (1)-(3), we used LU decomposition to solve sparse or semi-sparse sub-matrix in parallel. The parallel LU decomposition or preconditioned biconjugate gradient iteration can be used to solve the boundary full matrix equation in step (4).

RESULTS

The boundary element EM modeling program was implemented on the T3D/T3E massively parallel computer. A layer-like model was used to test this algorithm. The mesh is $30 \times 30 \times 30$, total nodes are 27,000. The 64 PEs are used to run the model. The wall time is 480 s. The relative error of the magnetic field between this algorithm and EM1D is less than 10^{-4} . Another simulation model is presented as follows: the source is a plane wave, a resistive block is imbedded in a half space. In the background of the Earth, the electric resistivity $\rho = 10$ ohm-m, and the electric permittivity $\epsilon = 10 \epsilon_0$. In the block, the electric resistivity $\rho = 10^5$ ohm-m, and the electric permittivity $\epsilon = 2 \epsilon_0$. The frequencies are from 10^7 - 10^8 Hz. The cubic domain is $[-1, -1, -1; 1, 1, 1]$. The mesh is $26 \times 26 \times 26$, total nodes are 17,576. The 64 PEs are used to run the model. The wall time is 288 s. Using the algorithm on T3E, the magnetic field response $H_y/H_{y,b}$ (Figure 5) and the electric field response $E_y/E_{y,b}$ (Figure 6) are

Figure 1. Domain decomposition. Figure 2. Parallel local FEM in SII. Figure 3. Parallel group algorithm. Figure 4. Two boundary layer equation. Figure 5. Magnetic field (top), and; Figure 6. Electric field (bottom).

presented on a $z = -0.05$ level with a 10^7 Hz frequency. The field imaging in Figures 5 and 6 is very good in the domain; it is particularly clear on the neighborhood of the boundary. The 3D FEM modeling based on the volume magnetic integral equation was used to run the same model. The relative error of results between the BDFEM and GILD is less than 10^{-4} - 10^{-5} .

SIGNIFICANCE OF FINDINGS

The tests show the boundary finite element EM modeling is accurate, fast, and highly adaptive to the parallel processing environment. The algorithm is suitable for any frequency $\omega \geq \omega_0 > 0$ and high contrast media. Boundary reflection error is reduced to a minimum (Figures 5 and 6). The BDFEM EM modeling and GILD nonlinear inversion will be used to construct 3D EM high-resolution

imaging. The parallel modeling and inversion algorithm will be a tool for large scope coupled inversion.

RELATED PUBLICATIONS

- Xie, G. J. Li, and K. H. Lee, New 3D nonlinear EM inversion, in *Proceedings of Int. Symposium on 3D EM*, pp. 405-414, SDR, 1995.
- Xie, G., and J. Li, A new 3D parallel high resolution EM nonlinear inversion based on a new global magnetic integral and local differential decomposition (GILD), LBNL-40265, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Xie, G., and J. Li, New 3D Parallel GILD electromagnetic modeling and inversion using global magnetic integral and local differential equation position, LBNL-42105, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Numerical Investigation of Fracture Channel Waves

W. Yi, S. Nakagawa, K. T. Nihei,
J. W. Rector, L. R. Myer,
and N. G. W. Cook

RESEARCH OBJECTIVES

In recent years, fractures in tight reservoir rocks have been recognized as major conduits for oil and gas production. Optimal well placement and production require a knowledge of characteristics such as fracture dimensions, aperture, and compliance. A basic challenge is to determine these geometrical and physical properties from seismic measurements. This research examines the characteristics of channel wave propagation in a waveguide formed by two parallel fractures using two-dimensional elastic finite difference simulations and mode analysis.

Thin, compliant features such as fractures are known to possess an acoustic impedance, $I_{frac} = \kappa/\omega$, which is different from the host rock, $I_{host} = \rho c$, where κ is the fracture stiffness [stress/length], ω is the angular frequency of the wave, and ρ and c are the density and velocity of the host rock. The impedance contrast between the fracture and host rock determines the seismic visibility of the fracture: $I_{host}/I_{frac} = (\rho c \omega)/\kappa$. This relation shows that the seismic visibility of the fracture is dependent on both its stiffness and the frequency of the wave, the effect being largest when the fracture stiffness is low compared to the product of the acoustic impedance of the host rock times the frequency of the wave.

Because fractures possess a frequency-dependent acoustic impedance, a variety of interesting elastic wave phenomena have been demonstrated to exist for wave propagation across and along single fractures. These effects include frequency-dependent transmission and reflection, including wave conversions, and dispersive fracture interface wave propagation. Since fractures typically appear as sets of nearly parallel planar features, it is important to determine the seismic response of waves traveling between fractures. The results of this research demonstrate that parallel fractures form an elastic waveguide that supports a family of channel waves that can be viewed as generalized Rayleigh-Lamb plate waves for the case when a plate is sandwiched between two half-spaces through normal and tangential springs. In addition, several interesting properties of fracture channel waves that differ from conventional Rayleigh channel waves supported by a low-velocity layer are shown for the first two lowest order symmetric modes.

APPROACH

Numerical simulations of elastic wave propagation in a medium with two parallel fractures were performed using a two-dimensional, elastic, staggered grid finite difference code, which uses fourth-order differencing in space and

second-order differencing in time. Fractures can be integrated into the finite difference code either as cells with anisotropic properties chosen to exactly replicate the normal and tangential fracture stiffnesses or by explicitly applying the *displacement-discontinuity* boundary conditions across neighboring grid cells. For fractures that are aligned with the finite difference grid, the latter approach is the simplest and is the approach used here.

For a planar fracture located in the x - y plane, the displacement-discontinuity boundary conditions for a fracture are:

$$u_x^+ - u_x^- = \frac{\tau_{zx}}{\kappa_{zx}}, \quad u_z^+ - u_z^- = \frac{\tau_{zz}}{\kappa_{zz}} \quad (1)$$

$$\tau_{zz}^+ = \tau_{zz}^-, \quad \tau_{zx}^+ = \tau_{zx}^- \quad (2)$$

where u is the particle displacement, τ is the stress, κ is the fracture stiffness in units of [Pa/m], and the superscripts $+$ and $-$ refer to opposite sides of the fracture. The displacement-discontinuity boundary conditions are generalized to the boundary condition for a welded interface as $\kappa \rightarrow \infty$ and for a free-surface as $\kappa \rightarrow 0$. Several researchers have demonstrated that this model provides a good description of the dynamic behavior of a fracture using laboratory ultrasonic measurements of wave transmission across a single fracture and fracture interface wave propagation along a single fracture.

RESULTS

A snapshot for the vertical component of the wavefield in a fracture waveguide taken at $t = 62$ ms for a P-wave transmission coefficient of 0.6 case is shown in Figure 1. The source is a broadband explosion source with a central frequency of 374 Hz and is located at the center of the waveguide.

The wavefield around the fracture waveguide is also characterized by strong head waves. These head waves are generated as a result of interaction between the propagating P-wave wavefront inside and outside of the waveguide. For the velocity-contrast waveguide, no significant head waves were generated.

The snapshot also shows strong high-frequency reverberations near the source. This results from multiple reflections of high-frequency waves by the fractures. The velocity-contrast waveguide, on the other hand, did not show such reverberations.

Figure 1. Finite difference snapshots taken at $t = 62$ ms for waves in a fracture waveguide. The P-wave transmission coefficients across the fractures are $T = 0.6$. Location of the explosion source is indicated by a star.

The channel waves in the fracture waveguide consist of multiple modes with different velocities. By examining the dispersion relations in a measured seismogram, the modal structure of the wave can be determined. For this purpose, an array of receivers was located along the center of the waveguides, 12 wavelengths from the source. By applying f-k (frequency-wavenumber) analysis to the seismograms measured at different horizontal offsets, the velocity dispersion of the wave was computed. An f-k plot for the fracture waveguide is shown in Figure 2 for the 0.6 transmission coefficient case (for normally incident P waves). In the f-k plots, the slope of each curve represents the velocity dispersion of the various channel wave modes. The modal structure of wave for the fracture waveguide can be seen clearly. A comparison with the corresponding f-k plot for a velocity-contrast waveguide did not show distinct individual modes (not shown). It was also observed that the fracture channel waves contain more high frequencies than the low velocity channel waves.

The computed phase velocities for the lowest-order symmetric fracture channel mode showed good agreement with the velocities obtained from mode analysis. Mode analysis of the fractured waveguide has shown that the fracture channel wave is a generalized Rayleigh-Lamb plate wave (Nihei et al., 1998). The current simulation confirms that such waves can be generated by a simple point explosion source, as should be expected.

To examine the characteristics of the wavefield of the fracture waveguide near the source, the receiver array was moved to four wavelengths from the source. The f-k analysis of the wavefield revealed the existence of leaky modes that result from multiple reflected waves. The phase velocities of these leaky modes were seen to be extensions of the true normal modes above the shear wave velocity. Because of the finite offset between source and receiver, it was not possible to see the continuation of these waves to near vertical inci-

Figure 2. f-k plot for a receiver array located in the center of the fracture waveguide 12 wavelengths from the source.

dence, as present in the snapshot in Figure 1. The complexity of the wavefield near the source in the fracture waveguide results from the frequency-dependent reflectivity of multiple parallel fractures.

SIGNIFICANCE OF FINDINGS

Significantly different velocity-frequency behavior for the various modes was observed for a waveguide formed by two parallel fractures. In addition, the fracture waveguide shows high-frequency thickness resonances near the source. These wave phenomena indicate that rock containing multiple sets of aligned fractures may serve as elastic conduits for channel wave propagation, and that these characteristics are different from those observed in classic low-velocity waveguides. Research is continuing to evaluate the properties of these waves and their potential for characterizing the properties of fractured rock.

RELATED PUBLICATION

Nihei, K. T., M. Schoenberg, W. Yi, L. R. Myer, and N. G. W. Cook, Fracture channel waves, *J. Geophys. Res.*, in press, 1998.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Molecular-Scale Simulation of Clay Mineral Surface Geochemistry

G. Sposito, J. A. Greathouse,
S.-H. Park, and R. Sutton

RESEARCH OBJECTIVES

This project involves basic research directed toward an accurate model of molecular structure at the surface of hydrated 2:1 clay minerals (smectites). These minerals, which are isostructural with micas (e.g., muscovite or biotite), are of great importance in petroleum production, nuclear waste containment, and contaminant attenuation by designed clay liners. The objective to be addressed is Monte Carlo (MC) and molecular dynamics (MD) simulations of interfacial molecular structure on smectite minerals adsorbing water and cations (counterions). The results obtained will provide a significantly improved quantitative understanding of clay-clay, clay-water, and cation-clay interactions that will be used to test existing experimental data and, if necessary, improve the potential function models used in the simulations.

APPROACH

Computational algorithms for the MC and MD simulations, based on the codes MONTE and MOLDY, have been developed by our collaborators, Dr. N. T. Skipper and Dr. K. Refson. These codes are fully optimized and

running well on the Cray J90 and T3E supercomputers at the National Energy Research Scientific Computing Center (NERSC).

RESULTS

Monte Carlo and molecular dynamics (200 ps) simulations were performed to elucidate interlayer structure in hydrated lithium-hectorite (which is isostructural with biotite and has interlayer Li^+ counterions) at low water content ($\text{H}_2\text{O}/\text{Li} = 3$). Numerous spectroscopic studies of these stable clay mineral hydrates have led to an interlayer structural model based on a postulated inner-sphere surface complex comprising Li^+ bound directly to the hectorite surface while surmounted by exactly three solvating water molecules that execute hindered rotational motions around their symmetry axes (Figure 1). Our simulation results, based on tested water-water, Li^+ -water, water-clay mineral, and Li^+ -clay mineral potential functions, showed that outer-sphere surface complexes formed

Figure 1. Spectroscopic model of a postulated trihydrate inner-sphere surface complex in $\text{Li}(\text{H}_2\text{O})_3$ -hectorite. Stipled circles denote water oxygens, open circles are hectorite surface oxygens, and the crosshatched circle is Li^+ . The transition dipole moment vectors for IR-active symmetric and asymmetric stretching vibrations of the water molecule are denoted M_s and M_{as} , respectively. Upper view (a) is in the (z,x) plane and lower view (b) in the (y,x) plane. The angle of 35° between the dipole moment vector M_s and the horizontal line is confirmed by our MC simulations.

Figure 2. Monte Carlo "snapshot" of the interlayer molecular configuration in $\text{Li}(\text{H}_2\text{O})_3$ -hectorite as seen in projection onto the (y,x) plane. Orange spheres denote surface oxygen ions; yellow spheres are structural Si^{4+} cations. Note that only two water molecules solvate each Li^+ (red O and white H), while the third (one is at the center of the figure) is keyed into a hexagonal cavity in the surface, evidently attracted to a hectorite structural proton (black sphere).

Figure 3. Molecular dynamics simulation of the time dependence of the x -coordinates (denoted in either red or blue) of a pair of protons in a water molecule that has keyed into a hexagonal cavity of the hectorite surface (see Figure 2). Note the sporadic exchange of x -coordinates, indicating that rotations of the H-H line of centers are occurring (on the picosecond time scale of the MD simulation).

instead on Li-hectorite, with water molecules interposed between Li^+ and the hectorite surface (Figure 2). The number of water molecules solvating each Li^+ in the clay hydrate was two, not three, and rotational motions of these water molecules did not occur. Instead, rotations around the symmetry axis occurred (Figure 3) only for water molecules attracted to protons inside the hexagonal cavities in the oxygen surface (Figure 2), thus strongly contradicting the spectroscopic model depicted in Figure 1.

Our MC simulation results for $\text{Li}(\text{H}_2\text{O})_3$ -hectorite were, however, in general agreement with the interpretation of both infrared (IR) and nuclear magnetic resonance (NMR) spectral data insofar as the average orientation of solvating water molecules is concerned (e.g., the 35° angle in Figure 1). Also, the Li^+ oscillations inferred from quasielastic neutron scattering (QNS) spectra were confirmed by our MD simulations (Figure 4).

SIGNIFICANCE OF FINDINGS

The MC and MD simulations indicated clearly that the inner-sphere trihydrate surface complex proposed for $\text{Li}(\text{H}_2\text{O})_3$ -hectorite on the basis of IR, QNS, and NMR spectroscopic data (Figure 1) was an oversimplification in several respects. First, outer-sphere surface complexes formed with the Li^+ solvation number are equal to two. Second, rotational motions in these surface complexes (at least over the 200-ps simulation time

Figure 4. Molecular dynamics simulation of the cumulative trajectories (over 200 ps) of Li^+ (black) and three hydrating water molecules (gray) as seen in projection onto the (z,x) plane in the hectorite interlayer region. For reference, the oxygen ions in the hectorite surface are centered on the lines defined by $z = \pm 1.88 \text{ \AA}$. This trajectory plot reveals vertical oscillatory motions of Li^+ (and its solvation shell) along an axis normal to the hectorite surface, in agreement with QNS spectral data. Lateral cation hopping between adjacent sites on the hectorite surface also is apparent.

scale) were absent. Water molecules in $\text{Li}(\text{H}_2\text{O})_3$ -hectorite that are not in surface complexes with Li^+ did show rotation around their symmetry axes, however (Figures 2 and 3). These major structural differences should be resolvable by developing new spectroscopic models guided by the results from this project and then comparing them with extant or new spectral data.

RELATED PUBLICATIONS

Greathouse, J., and G. Sposito, Monte Carlo and molecular dynamics studies of interlayer structure in $\text{Li}(\text{H}_2\text{O})_3$ -smectites, *J. Phys. Chem. B*, 102, 2406-2414, 1998.
Chang, E.-R.C., N. T. Skipper, and G. Sposito, Monte Carlo and molecular dynamics simulations of electrical double layer structure in potassium-montmorillonite hydrates, *Langmuir*, 14, 1201-1207, 1998.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Fast Flow of Water Along Surfaces of Unsaturated Fractured Rock

RESEARCH OBJECTIVES

Although fractures in rock are well-recognized as pathways for fast percolation of water, the possibility that fast flow could occur along unsaturated fracture pathways has not previously been recognized. Rapid migration of solutes through some portions of deep vadose zones has recently been reported by others. Such findings clearly show preferential water flow along a fraction of potentially conductive pathways, and disequilibrium between fractures and the rock matrix. Most conceptual models for flow and transport in unsaturated fractured rock require high fracture saturations in order to permit flow through fractures. Such models envision small regions of fractures as being either fully saturated or desaturated, with the condition for local fracture saturation essentially based on aperture-capillarity considerations. In such conceptualizations, local segments within a fracture are either saturated (conductive) or dry (non-conductive), such that continuous saturated pathways within fractures are required to sustain fast flow. However, observations of rapid transport through unsaturated fractured rock often are not associated with evidence for such continuous, saturated flow pathways. Until recently, transient pulses of locally highly saturated fracture flow during episodic, high-intensity rainfall events provided the only explanation for fast flow through fractured vadose zones. In this study, two mechanisms for fast flow along unsaturated fractures were experimentally tested. The first involves water film flow along fracture surfaces. The second involves flow along high-permeability fracture surface zones.

Film flow has been recently identified, and shown to depend on fracture surface roughness and the matric potential (Tokunaga and Wan, 1997). Water film thickness can build up along fracture surfaces when the matric potential is high enough to sustain effectively saturated conditions in the immediately underlying matrix. As matric potentials increase (towards zero), water film thicknesses expand along fracture surfaces by first filling finer scale roughness features, and progressively filling coarser roughness features. The transmissivity (volumetric flux per unit length transverse to flow, under a hydraulic head gradient of unity) of such films increases with film thickness, and supports fast gravity-driven flow. In our earlier study, the influence of surface roughness on flow was only qualitatively identified through comparing the very rapid advance of a dye tracer down a natural rough fracture surface relative to its insignificant movement down an adjacent polished flat surface.

A second condition that could support fast flow along unsaturated fractures occurs in fracture coatings and fracture surface zones that have undergone permeability-

enhancing alterations. When the permeability of the fracture surface region is significantly greater than that of the underlying matrix, water will flow preferentially along the fracture

surface. Although some previous research has been directed at measuring the hydraulic characteristics of fracture coatings, the focus of those studies was on water flow into the rock matrix, rather than along fracture surface regions.

APPROACH

In order to more quantitatively examine the effects of surface roughness on film flow, experiments were conducted on water-saturated ceramic blocks with simple V-channel corrugations. Use of systems with such simple geometries for examining flow along rough surfaces follows from the long history of conceptual and physical models of flow in porous media that are based upon bundles of capillary tubes. Individual ceramic blocks were prepared with (i) flat, polished surfaces, (ii) V-channels aligned with the downwards flow direction, (iii) V-channels aligned transverse to the flow direction, and (iv) V-channels both parallel and transverse to the flow direction. The effective hydraulic conductivity versus matric potential relations for these ceramic blocks were determined by adjusting flow rates and boundary potentials to establish unit hydraulic head gradients at specific values of the matric potential, in the manner described previously. We define the effective hydraulic conductivity as the flux through both the matrix and along surfaces under a unit hydraulic head gradient, per unit horizontal cross-sectional area normal to flow.

The significance of surface zone fast flow was quantitatively evaluated through measuring trends in cumulative water uptake in another sample of the welded tuff, through its fracture coating and then into its matrix. In homogeneous porous media, the short-term volumetric water uptake rate per unit area follows diffusion-like behavior. Thus, the cumulative imbibition of water is linear with respect to the square root of time, with the proportionality factor referred to as the sorptivity. When such an experiment is done on a coating-matrix composite sample with the surface coating placed in contact with a free water reservoir, and imbibition into the low-permeability matrix occurring via the coating, sorptivities in both layers can be deduced.

RESULTS

Comparisons of measured effective hydraulic conductivities for the flat surface ceramic and the ceramic with V-channels aligned with the flow direction showed very large differences at matric potentials very close to zero.

T. K. Tokunaga and J. Wan

The effective hydraulic conductivity of the flat-surface ceramic remains constant, and equal to the hydraulic conductivity of the matrix over nearly the full range of matric potentials tested, with relatively small increases at matric potentials very close to zero. The effective hydraulic conductivity of the V-channel ceramic shows increases of up to 4 orders of magnitude in the near-zero matric potential range. The transmissivity of this V-channel sample becomes as large as $10^{-5} \text{ m}^2 \text{ s}^{-1}$, corresponding to average velocities up to 3 km d^{-1} within channels. Differences between these laboratory measurements and a linear combination of the saturated matrix hydraulic conductivity and predicted V-channel fluxes based on an approximate solution by Romero and Yost are within 100 Pa of matric potential and an order of magnitude in effective hydraulic conductivity. The effective hydraulic conductivity function of the ceramic with channels transverse to flow was similar to that of the flat surface, despite the fact that pendular water thicknesses built up to nearly fill the 1.0-mm-deep channels at near-zero matric potentials. This result demonstrates the very high hydraulic resistance encountered for flow transverse to ridge features. Finally, experiments on the ceramic block with channels in both transverse and parallel orientations yielded results that were very similar to those on the block with only channels aligned with the flow direction. This last result indicates that film flow on surfaces of natural, rough fracture can be represented by sets of effectively parallel paths.

Square-root-of-time plots for water entry through the Topopah Spring tuff fracture coating, then into the welded tuff matrix, reveal that the sorptivity of the fracture coating is 5.5 times greater than that of the underlying matrix. Since permeabilities are very well correlated with sorptivities raised to the fourth power (shown by Kao and Hunt), the permeability of the Topopah Spring Tuff fracture coating is about 900 times greater than that of the matrix rock. Thus, gravity-driven flow within this fracture coating can proceed with a velocity about 900 times greater than in the immediately underlying matrix rock. Such extremely high contrasts in permeabilities are especially important during episodic rainfall events since much of the infiltrating water percolates along fractures.

SIGNIFICANCE OF FINDINGS

These results show that rock fracture surfaces and fracture surface zones can serve as fast flow pathways along essentially unsaturated fractures. Thus, explanations of unsaturated flow in fractured rock based upon conceptual models that consider only aperture distributions and average rock matrix properties are generally incomplete. The low sorptivity of partially saturated, very low permeability rock can sustain near-zero matric potentials along fracture surfaces associated with preferential flow paths. The roughness of natural fracture surfaces permits film flow under such near-zero matric potentials. Alterations to fracture surface zones of very low permeability rock are most likely to be permeability enhancing. For these reasons, film flow and surface zone flow can be especially important in understanding flow through unsaturated, fractured, low-permeability rock. Although this study has identified two mechanisms contributing to fast flow, it remains very important to quantify how fluxes are distributed with respect to flow velocities since this distribution determines the overall contribution of fast flow. Flux distributions need to be determined at the appropriate field-scale since heterogeneous distributions of hydraulic properties along flow paths need to be included.

RELATED PUBLICATION

Tokunaga, T. K., and J. Wan, Water film flow along fracture surfaces of porous rock. *Water Resour. Res.*, 33 (6), 1287-1295, 1997.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Micro-XANES Spectroscopy of Selenium Reactive Transport at the Water-Sediment Boundary

RESEARCH OBJECTIVES

An important step in cycling many trace elements in the environment is transport across boundaries between surface waters and underlying sediments. This macroscopic interface between two environmental compartments is often chemically and biologically stratified because of steep gradients in dissolved oxygen and other major redox-controlling species. Anoxic conditions that often occur at very shallow sediment depths promote reduction of redox-sensitive trace elements that move into this boundary region. For many elements dissolved in natural and contaminated waters, redox transformation results in adsorption or precipitation, often at depths of only a few mm from sediment surface. Selenium (Se) is an environmentally important trace element, both as an essential nutrient and as a toxin, that undergoes such redox changes. Selenium transport and transformations in wetlands have received considerable attention since identification of Se poisoning in wildlife deaths and deformities at Kesterson Reservoir, CA. Soluble Se(VI) is stable in oxidizing waters, and was the dominant Se species in agricultural drain waters discharged at Kesterson Reservoir. Under reducing conditions, this mobile form adsorbs as [Se(IV)] and precipitates [as Se(IV) and Se(0)]. Variations in Se solubility and sorption characteristics among its different forms require Se speciation be understood to predict transport.

To test models of time-dependent trace element partitioning in surface-water/sediment environments, experimental methods with appropriate spatial and temporal resolution are required. Determination of concentration profiles with adequate spatial resolution is critical. This is the basis on which mass transfer calculations are performed. Sampling of sediments or pore waters necessary for various conventional laboratory analytical methods locally perturbs the system under study. The synchrotron x-ray fluorescence microprobe (SXRFM) permits nondestructive, 2D mapping of many elements under realistic environmental conditions. When major reactions of concern involve oxidation-reduction of an element, the synchrotron-based technique of x-ray absorption near-edge structure (XANES) spectroscopy permits direct determination of valence. By combining monochromatic synchrotron radiation with the SXRFM, scanning micro-XANES spectroscopy can be performed within very small regions (about 10 μm). By scanning a sample in front of a monochromatic microbeam, micro-XANES can be used to obtain maps of spatial distributions of trace elements, including information on distributions among oxidation state. This study utilized micro-XANES to

T. K. Tokunaga, S. R. Sutton,
S. Bajt, and G. Shea-McCarthy

obtain spatially and temporally resolved information so as to better understand diffusion and redox influences on Se transport across the water-sediment boundary. Experiments were conducted in small, ponded sediment columns, with and

without a large excess of NO_3^- to inhibit and permit Se reduction, respectively.

APPROACH

Small soil columns were designed to permit real-time, *in-situ* SXRFM and micro-XANES measurements of vertical profiles of Se, across ponded water-sediment boundaries. In each of 2 columns, rectangular 31 $\times$ 10 $\times$ 5 mm (height, width, and depth, respectively) cavities were milled into the middle of an acrylic plastic frame. The back side of each cell was embedded with an array of platinum electrodes (spaced at 2-to-5-mm depth intervals) to measure redox potential. The soil used (Albic Natraqualf) was collected from Kesterson National Wildlife Refuge, in an area with no previous history of exposure to seleniferous waters. In the first ponded sediment system, denoted as +N, soil was saturated with a 240 mM NaNO_3 solution to maintain oxidizing conditions. In the second system, denoted as -N, organic matter in the form of air-dried and pulverized grass (*Bromus mollis*) tissue was added uniformly into the soil to promote development of reducing conditions. The -N sediment was saturated with a 120 mM Na_2SO_4 solution. The appropriate preconditioning solution was added to the air-dry soil, which was mixed, compressed into a pellet, and compacted into the lower 20-mm portion of the acrylic frame. Mylar tape sealed the front surface of each cell. Upon sealing, each column was oriented vertically, and ponded with the same solution used to presaturate its sediment. The columns were maintained in vertical orientation, and incubated in a room temperature water reservoir. Following incubation, the ponded solution was removed from each column with a syringe, and immediately replaced with a solution containing Se(VI). This solution contained SeO_4^{2-} at a concentration of 4.8 mM, with the background electrolyte composition similar to that of the preconditioning solutions. The sediment columns were monitored using the SXRFM in monochromatic mode. Micro-XANES measurements were made at the National Synchrotron Light Source (beamline X26A). A large spot size of about 200 μm was used to average over many grains. Selenium, iron, and zinc were detected in fluorescence mode. The normalized Fe and Zn fluorescence permitted location of the pool-sediment boundary. Concentrations and speciation were determined through calibration with model compounds in water and sediment standards. About ten depth

profile scans were obtained on each column, with intervening times between profiling used to obtain XANES of standard samples and micro-XANES of selected locations within columns. The ponding experiments ran for total elapsed times of about 62 h. Micro-XANES spectra of selected locations within columns provided local Se speciation. Interpretation of oxidation state distributions within specific locations in the ponded sediment systems was based on comparing their micro-XANES with that of model Se compounds.

RESULTS

Total Se concentration profiles from the two systems showed removal of Se from ponded waters and accumulation within shallow sediment. Total Se concentrations obtained with the SXRFM in the NO_3^- rich (+N) system exhibited a series of profiles that indicate Se(VI) diffused freely into the sediment from the pool, without significant reduction to adsorbed or precipitated species. Micro-XANES analyses at various locations in the +N system showed that Se remained in the Se(VI) state throughout this experiment. The measurements of Se depth profiles in the +N system compare well with explicit finite difference model predictions based solely on diffusion. The calculated profiles were obtained using measured diffusivities in water ($D_w = 3.6 \text{ mm}^2 \text{ h}^{-1}$), a fitted effective diffusivity in sediments ($D_s = 0.65 \text{ mm}^2 \text{ h}^{-1}$), and a harmonic mean diffusivity at the water-sediment interface. The effective diffusivity of Se(VI) in sediments was obtained by simultaneously fitting to all of the +N depth profiles. The overall evolution of the total Se distribution within the sediments without NO_3^- provided indirect evidence that reactions strongly influenced mass transfer. The rates of pool-sediment transfer of Se were more rapid into the NO_3^- free, organic-matter-amended sediment, especially at later times. Reduction of Se(VI) within shallow sediments led to increases in its concentration gradient at the pool-sediment boundary, thereby enhancing diffusive Se removal from pool waters. Local Se concentration maxima grew within the -N sediment profiles, indicating diffusion of soluble species to local regions of active Se sorption and/or precipitation. Micro-XANES spectra collected at various depths within the -N sediment revealed combinations of Se(0) and aqueous Se(VI) as dominant Se species. It is interesting to note that accumulation of the intermediate oxidation state, Se(IV), was typically less than 5% of the total local concentration. Average behavior of this system with respect to pool Se removal can be modeled with an overall apparent first-order Se(VI) reduction rate constant, k_p , of 0.015 h^{-1} applied to the deeper than 1-mm sediments in the

diffusion simulations. The micro-XANES results showed that local rates of reduction to Se(0) varied in a heterogeneous manner, and that reduction rates were up to 10 times greater in the more rapidly reducing zones, which were separated by distances of about 5 mm.

SIGNIFICANCE OF FINDINGS

This real-time, *in-situ* study illustrates how diffusion and reduction rates regulate Se mass transfer across static pond-sediment interfaces, and the use of micro-XANES in investigating reactive transport across sharp environmental boundaries. Conventional methods cannot provide the resolution to characterize transient reactive transport in regions with steep redox gradients. These results directly show reduction of Se(VI) to Se(0) can occur within very shallow depths in reducing sediments. The necessary environmental condition for generation of such heterogeneity is a sharp gradient in redox status, provided in the water-sediment boundary region. Coarse volume-averaging across such heterogeneity prevents observation of small-scale processes that can control transport and overall reaction progress. Results from the two columns demonstrate how the balance between rates of diffusion and reduction determine evolution of total Se profiles in hydrostatic, ponded sediments. Slower reduction rates permit Se(VI) diffusion deeper into sediments, more effective dissipation of concentration gradients, and therefore slower depletion from ponded waters. More rapid reduction rates prevent deep advances of the diffusion front, accumulation of reduced species at shallow depths, sustained high concentration gradients, and more rapid depletion of Se(VI) from ponded waters. Model results consistent with measurements in Kesterson Reservoir sediment cores are obtained by combining our average apparent first-order Se(VI) reduction rate with appropriate advection and dispersion terms.

RELATED PUBLICATION

Tokunaga, T. K., S. R. Sutton, S. Bajt, P. Nuessle, and G. Shea-McCarthy, Selenium diffusion and reduction at the water-sediment boundary: Micro-XANES spectroscopy of reactive transport, *Environ. Sci. Technol.*, 32, 1092-1098, 1998.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract Nos. DE-AC03-76SF00098, DE-FG02-92BR14244, and DE-AC2-76CH00016.

Colloid Transport in Unsaturated Porous Media

J. Wan and T. K. Tokunaga

RESEARCH OBJECTIVES

Transport of colloids in subsurface environments has received considerable attention in recent years, primarily because suspended colloids (inorganic, organic, and microbial) can be contaminants themselves and can serve as carriers of sorbed contaminants. Current conceptual and predictive models for colloid transport in soils and groundwaters have relied heavily on filtration theory, developed for single fluid phase systems. However, this does not account for the effect of unsaturation. Despite the importance of colloid-facilitated chemical transport in the vadose zone, a physically based model for transport of colloids in unsaturated soils has not previously been available. In this research, we propose that the gas phase can physically constrain colloid movement through regions of thin water films. We call the mechanistic basis of this process "film-straining."

APPROACHES AND RESULTS

Conceptual Model. In partially saturated porous media, water is retained by capillarity and adsorption, with both effects included in the matric potential, ψ (energy per unit volume, Pa). Water retained by capillarity exists as pendular rings around grain-grain contacts, and water retained by adsorption appears as thin films along grain surfaces. We define the saturation at which pendular rings become discontinuous as the critical saturation, S_c , and its corresponding matric potential at this point as critical matric potential, ψ_c . We propose that film-straining occurs only when pendular rings become disconnected. In this state, colloids must move through adsorbed thin water films in their traverse through the porous medium. We also propose that in the adsorbed film region when the thickness of an adsorbed water film, w , is greater than the diameter of a sphere colloid particle, d , film-straining of hydrophilic colloids remains ineffective [Figure 1(b)]. However, when w is similar or smaller than d , retardation of colloid transport is expected since surface tension forces hydrophilic colloids against grain surfaces [Figure 1(a)]. Therefore, pendular ring discontinuity and the ratio of colloid size to film thickness are clearly important factors controlling unsaturated colloid transport. Retardation of ideal, nonsorbing colloids can occur at two locations: trapped within individual pendular rings due to exclusion from entry into surrounding thin films, and within films which are too thin to effectively move the colloids.

Predictive Model. In order to develop a predictive model, we began with a system with simple geometry, a close packing of uniform spherical grains of radius, with menisci at their critical matric potential. The critical matric potential under these conditions can be described with the Laplace-Young equation. We approximate the

probability of pendular ring discontinuity by an integral normal probability function. We modified Langmuir's approach for expressions of water film thickness w . We developed an

approximate model [Equation (1)] that accounts for the local rate at which suspended colloids are strained by thin water films in unsaturated porous media (Wan and Tokunaga, 1997).

$$\left. \frac{\partial C}{\partial t} \right|_{\text{straining}} = -N \left\{ \frac{1}{p\sqrt{2\pi}} \int_0^{\psi} \exp \left[-\frac{(\psi - \psi_c)^2}{2p^2} \right] d\psi \right\} \left[\frac{d}{L} \left(\frac{2\gamma}{R} - \psi \right)^{0.5} \right]^{\beta} v^{(1+\beta)} C, \quad (1)$$

For a suspension of hydrophilic colloids, film-straining is not efficient unless $\psi \leq \psi_c = -B\gamma/R$. For $\psi \leq \psi_c$, film-straining becomes important as w decreases relative to d , with the ψ -dependence of w estimated from the Langmuir film equation. The local rate of film-straining is due to the combined effects of capillary discontinuity of pendular rings, diminished mobilizing drag on colloids within thin films, and velocity influences. The local cumulative concentration of strained colloids is obtainable by substituting the solution of the advection-dispersion equation into Equation (2) and integrating with respect to time. The total suspended-plus-strained, colloid concentration at any location and time is then

$$\frac{C_s(z,t)}{C_o} = \frac{C(z,t)}{C_o} + \frac{\mu}{C_o} \int_0^t C(z,t') dt'. \quad (2)$$

Experimental Testing. To test the film-straining model, a method of infiltrating colloid suspensions into packed sand columns was used. Well-rounded quartz sand was size-fractionated to specific ranges. Solution ionic strength was kept low (1.0 mM NaCl, pH 5.5) in all the experiments. Hydrophilic and negatively charged (carboxylate modified) polystyrene latex microspheres were used as colloids. Three variables were tested: matric potential (and corresponding saturation), sand grain size (150–212, 212–425, and 425–500 μm), and colloid size (0.97, 0.28, 0.093, and 0.014 μm). The columns were 0.34-m long and 19-mm ID, assembled from 17 sections of 20-mm-long acrylic tube. Each transport experiment was conducted by injecting a colloid suspension (at $C = C_o$) into the top of an initially dry column at a constant rate. Five different flow rates were tested, ranging from the Darcy velocity equal to the measured effectively saturated hydraulic conductivity (K_s) down to $10^{-4} K_s$, by reducing the rate one order of magnitude between each test. Water contents and colloid concentrations were measured for each section. Mass balances of water and colloids were calculated for each run. Figure 1(c) shows an example of experimen-

Film Straining of Colloids in Unsaturated Porous Media: Conceptual Model and Experimental Testing

Figure 1. (a) and (b) Conceptual model of unsaturated straining, when $d \geq w$ film-straining occurs, and when $d \leq w$ film-straining is inefficient. (c) Comparison of mathematics model and experimental data of film-straining.

tal data and the model predictions. Effective penetration of hydrophilic colloids through unsaturated porous media is predicted when a system is above the critical saturation value. For colloids smaller than the thickness of adsorbed thin water films, the model predicts that colloids can still be efficiently transported, even when the system matric potential and saturation are lower than their critical values. The conceptual basis of this model is supported by good agreement between the wide range of experiments and model predictions using only two adjustable parameters.

SIGNIFICANCE OF FINDINGS

This work introduced a new theory of film-straining, and provided a quantitative, mechanistic model for colloid transport in unsaturated porous media. By using this model as a bridge, applications of the filtration theory can be extended to unsaturated porous media.

RELATED PUBLICATION

Wan, J., and T. K. Tokunaga, Film-straining of colloids in unsaturated porous media: conceptual model and experimental testing, *Environ. Sci. Technol.*, 31(8), 2413-2420, 1997.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Center for Isotope Geochemistry

Donald J. DePaolo, Center for Isotope Geochemistry Head

The Center for Isotope Geochemistry was established in 1988 and has three major goals. The first is to maintain a state-of-the-art analytical facility for the measurement of the concentrations and isotopic compositions of elements in rocks, minerals, fluids, and gases in the earth's crust, oceans, and atmosphere. The second objective is to develop new ways of using isotope ratio measurements to study earth processes. This involves improvements in analytical techniques, as well as exploration of the natural isotopic variations of key elements and development of conceptual models relating isotopic variations to earth processes. The third objective is to apply well-known isotopic approaches to specific energy and environmental problems, such as groundwater contamination and remediation, geothermal resource development, nuclear waste isolation, and global climate change.

Most of the analytical facilities of the Center are located at Berkeley Lab, but facilities on the U.C. Berkeley campus are also used. The Berkeley Lab facilities include a stable isotope laboratory supervised by Mark Conrad; a noble gas laboratory supervised by B. Mack Kennedy; a cosmogenic isotope preparation laboratory supervised by Kuni Nishiizumi; and an analytical chemistry laboratory supervised by Scott Mountford. On the campus is a thermal ionization mass spectrometry laboratory supervised

by Don DePaolo and maintained by Tom Owens. In the near future the Center will obtain a multiple-collector, magnetic sector mass spectrometer with a plasma source, which will greatly expand its analytical capabilities.

Two of the projects represented in this annual report apply isotopes to problems of groundwater contamination. Both are examples of what we refer to as "isotopic diagnostics." Isotope ratio measurements made on samples of groundwater or soil gas are used to decipher what chemical or biochemical reactions are proceeding in the subsurface and at what rates. In the case of the Alameda Naval Air Station, Mark Conrad is using carbon isotopes to detect evidence of natural biodegradation of petroleum hydrocarbons in the shallow subsurface. At the Test Area North Site of the Idaho National Engineering and Environmental Laboratory, we use carbon, oxygen, hydrogen, and strontium isotopes for a similar purpose. These estimates of natural attenuation of the groundwater contaminants are essential for predicting the future environmental and health impacts of the contaminated water, and therefore for determining what type of remediation strategy is appropriate.

In a somewhat different type of study, strontium (Sr) isotopes in groundwaters are being used to estimate the rate at which natural mineral weathering reactions are tak-

ing place. The somewhat surprising finding here is that the derived rate of Sr exchange is almost independent of groundwater flow velocity in fractured basalt, which implies that Sr isotopes can be used as a flow velocimeter for groundwater in basalt-hosted aquifers.

Two projects are aimed at understanding global scale atmospheric issues. Allen Goldstein and Sean McCauley are attempting to use carbon isotope measurements to determine how much of the methyl bromide in the earth's atmosphere is attributable to the use of this compound as an agricultural insecticide. This answer is important since the use of MBr is currently being restricted because of its effect on stratospheric ozone depletion. Melissa Hendricks and Donald DePaolo are addressing a central issue in global climate change — the interpretation of water isotope data from polar ice cores. Transport models are used to understand the relationship between the isotopic composition of snow precipitated in Antarctic and the mean annual Antarctic surface temperature. The conclusion is that it was in fact much colder in Antarctica during the last ice age than was previously thought.

Kennedy has been using the isotopes of the noble gases helium, neon, argon, and krypton to study the origin and behavior of gases in the earth's crust. In a study published in *Science* in 1998, he and others show that gases emanating from springs along the San Andreas Fault in California have a significant component of helium that has come all the way from the earth's mantle, more than 30 km below the surface. They suggest that fluids are entering the fault zone from the mantle and acting to lubricate the fault, which would explain the well-known dearth of friction on the San Andreas Fault. In a study with Thomas Torgerson, it is shown that noble gas contents of brines indicate the oil/water ratios of petroleum reservoirs, and that this information can be useful for understanding the process of petroleum migration.

In early 1998, the Earth Sciences Division began to assemble a team of atmospheric scientists to develop a program in global climate change science. Norman Miller and Jinwon Kim are the vanguard of this effort, and were included with the Center for Isotope Geochemistry to take advantage of the overlap in research interests. Drs. Miller and Kim are using regional climate system models for a variety of purposes. One effort is to understand how to downscale global model information for use in regional models. Another effort is to make predictions of the regional effects of global climate change over decade-to-century timescales, with emphasis placed on the effects in the southwestern U.S. and eastern Asia. A third effort is aimed at making predictions of local streamflow intensity during winter storms, where warnings 6 to 24 hours in advance of floods can be critical. Yet another aim of

the regional studies is to make seasonal precipitation predictions for use in water resource planning. The research shows that the modeling approach has promise for eventually delivering reliable predictions, but that continuing model development is needed to reach that goal.

Kunihiko Nishiizumi is a Senior Fellow at the U.C. Space Sciences Laboratory and a member of the Center for Isotope Geochemistry. His research involves measurements of cosmogenic nuclide isotope abundances in rocks and minerals. Dr. Nishiizumi collaborates closely with members of the Center for Accelerator Mass Spectrometry (CAMS) at Lawrence Livermore National Laboratory. Sample preparation for his studies is done in the labs in Berkeley Lab's Building 70A and the mass spectrometry is carried out at the CAMS facility. Dr. Nishiizumi's measurements, which reflect the effects of galactic cosmic rays (GCR) in rocks, allow him to study earth processes such as landscape erosion rates, as well as prehistoric sunspot intensity. He and his collaborators have been able to directly measure terrestrial erosion rates, and his measurements in polar ice cores are serving to refine the ability to date ancient climate events. His research also extends to other planetary bodies: cosmogenic nuclides have been used to better understand how meteorites derived from Mars and the Moon have been excavated and transported to Earth.

The Environmental Measurements Laboratory (EML), which is overseen and operated by Scott Mountford, represents a consolidation of the chemical analytical facilities of the Earth Sciences Division. The EML is called upon by many researchers and projects within the Division to provide chemical characterization of soil, rock, mineral, and fluid samples. The EML is equipped with modern instrumentation, including ICPMS, Atomic Absorption spectrometry, various types of gas chromatographs, and GC/MS, HPLC, and facilities for standard wet chemical analysis.

FUNDING

The research of the Center for Isotope Geochemistry has been supported by the Director, Office of Basic Energy Sciences, Materials Sciences and Engineering and Geosciences Divisions; and the Environmental Science Management Program of the U.S. Department of Energy. Center research has also been supported by the U.S. Navy; the Office of Space Science of the National Aeronautics and Space Administration; the Office of Polar Programs of the National Science Foundation; and LBNL Laboratory Directed Research and Development grants.

Isotopic Assessment of Intrinsic Bioremediation of Petroleum Hydrocarbons

M. E. Conrad

RESEARCH OBJECTIVES

Within the last few years, there has been increasing acceptance by regulatory agencies and the general public of *in-situ* microbiological methods for remediating sites contaminated with petroleum hydrocarbons. These techniques provide rapid, cost-effective methods of cleaning sites while minimizing site disturbance and possible human exposure to the contaminants. However, there are significant problems associated with demonstrating that these processes are actually occurring in the field and that they are effectively eliminating potential health and environmental risks.

One technique for monitoring bioremediation of petroleum hydrocarbons is to measure concentrations of byproducts of microbial metabolism such as soil gas CO_2 and CH_4 or groundwater-dissolved inorganic carbon compounds (DIC). There are, however, other potential sources and sinks for these compounds. Isotopic analyses of these metabolic byproducts is one promising method of differentiating the source of compounds.

APPROACH

The stable carbon isotope ratios ($^{13}\text{C}/^{12}\text{C}$) of petroleum hydrocarbons tend to be lower than most other sources of carbon in the environment. These differences are reflected in the $^{13}\text{C}/^{12}\text{C}$ ratios of metabolic byproducts of hydrocarbon degradation. In some cases, however, there can be overlap with plant material in the soils. In addition, the $^{13}\text{C}/^{12}\text{C}$ ratios can be significantly shifted by some microbial metabolic processes that commonly occur at sites contaminated with petroleum hydrocarbons (e.g., methanogenesis, methane oxidation). To resolve these issues, we also measure the ^{14}C contents of the metabolic byproducts. The ^{14}C content of natural organic

matter in near surface environments is usually near modern levels, whereas fossil fuels have no measurable ^{14}C . Further, at the level of precision that radiocarbon measurements can be

made, the effects of isotopic fractionation are insignificant. When coupled together, measurements of both stable carbon isotope ratios and radiocarbon can provide unequivocal information on the extent of biodegradation and the biochemical pathways involved. Field data from several sites at the former Naval Air Station at Alameda, California, are presented to demonstrate potential uses of isotope monitoring of bioremediation of petroleum hydrocarbons.

RESULTS

Migration of VOCs into Buildings. Soil gas and groundwater samples were collected from beneath a building situated over a shallow plume of gasoline contamination. At about 60 cm beneath the building, the levels of gasoline-range volatile organic carbon compounds (VOCs) in soil gas dropped from 50,000 ppm to less than 50 ppm. Low ^{14}C contents coupled with large negative shifts in $^{13}\text{C}/^{12}\text{C}$ ratios of CO_2 across interval demonstrated that aerobic conversion of contaminants within the layer was limiting vertical transport of the contaminants into the building.

Biological Controls on Plume Movement. The isotopic compositions of potential metabolic byproducts of petroleum hydrocarbon biodegradation in soil gas and groundwater samples from a shallow plume of aviation gas (AVGAS) were analyzed. VOC concentrations in soil gas samples from the original source area were low (<1,000 ppm), but were in excess of 100,000 ppm under an

Figure 1. The top graph contains rainfall data collected at Jack London Square in Oakland, CA. The bottom graphs contain data on the concentrations and carbon isotopic compositions of soil gas samples collected from a 60-cm depth at the site of a former oil refinery at Alameda Point, CA.

adjacent, asphalt-covered parking lot. Soil gas CH_4 exceeded 20% in the central part of the plume and correlated well with VOC concentrations. The ^{14}C contents of the CH_4 , associated soil gas CO_2 , and dissolved inorganic carbon compounds (DIC) in the groundwater were all less than 0.1 times modern levels, indicating that they were primarily formed from degradation of the AVGAS. The $^{13}\text{C}/^{12}\text{C}$ ratios of CO_2 and DIC in the central part of the plume were relatively high, suggesting that a large fraction of the CO_2 in that area was also produced as a byproduct of methanogenic activity. At the down-gradient edges of the plume, CH_4 levels dropped to zero and the $\delta^{13}\text{C}$ values of CO_2 were much lower (-26‰), indicating that aerobic degradation of the AVGAS was dominant in this area. Beyond the edges of the plume, the ^{14}C contents of both groundwater DIC and soil gas CO_2 were significantly below modern levels, implying that most of the carbon there was derived from hydrocarbons and had migrated beyond the edge of the plume. These data show that although methanogenic activity in the central part of the plume was degrading the AVGAS slowly, aerobic activity at the edges of the plume was effectively limiting migration of the hydrocarbons.

Biological Mechanisms for Degradation of Aged Refinery Wastes. Vertical profiles of soil gas samples above 90-plus-year-old refinery wastes were collected for isotopic analyses. Soil gas at the surface of the water table contained greater than 80% CH_4 with ^{14}C contents of less than 0.1 times modern levels, indicating that the CH_4 was predominantly derived from the refinery wastes. With decreasing depth, CH_4 levels dropped to zero and O_2 increased. In addition, the $^{13}\text{C}/^{12}\text{C}$ ratios and ^{14}C contents of CO_2 in the profile decreased sharply as the CH_4 disappeared, implying a significant input of CO_2 produced by microbial oxidation of the CH_4 in the aerobic soils above the contaminants.

Seasonal Changes in Microbial Activity. The isotopic compositions of soil gas CO_2 and CH_4 were tracked over a one year period to evaluate the effects of changing seasonal conditions on *in-situ* microbial activity (Figure 1). The first samples were taken about two weeks after the end of the first rainy season and contained elevated CH_4 levels, but within 2 months the CH_4 had disappeared. Fol-

lowing the subsequent rainy season (which ended earlier than in the previous year), soil gas CH_4 levels were initially high and dropped off again. Throughout these cycles, the ^{14}C contents of the CH_4 remained low, indicating that the CH_4 was derived from degradation of hydrocarbon contaminants. The $^{13}\text{C}/^{12}\text{C}$ ratios of the CH_4 started low and increased as the amount decreased, signifying that the CH_4 was being oxidized. These data indicate that flooding during the winter stimulates increased methanogenic activity in the soils, which in turn leads to elevated levels of methane oxidation after the soils dry out.

SIGNIFICANCE OF FINDINGS

The results of this work demonstrate that combined measurements of the stable $^{13}\text{C}/^{12}\text{C}$ ratios and ^{14}C contents of metabolic byproducts of biodegradation of petroleum hydrocarbons provide a powerful technique for monitoring intrinsic biologic activity. For a diverse set of conditions, the data clearly delineate zones of methanogenesis, methane oxidation, and aerobic activity. They also indicate that although residual contamination may remain for extended periods of time, intrinsic bioremediation can effectively limit the spread of petroleum hydrocarbons in the environment.

RELATED PUBLICATIONS

- Conrad, M. E., P. F. Daley, M. F. Fischer, B. B. Buchanan, T. Leighton, and M. Kashgarian, Combined ^{14}C and $\delta^{13}\text{C}$ monitoring of *in situ* biodegradation of petroleum hydrocarbons, *Environ. Sci. Technol.*, 31(5), 1463-1469, 1997.
- Conrad, M. E., A. S. Templeton, P. F. Daley, and L. Alvarez-Cohen, Isotopic evidence for biological controls on migration of petroleum hydrocarbons, *Org. Geochem.*, in press.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

An Integrated Isotopic Study of Groundwater Flow and Contaminant Migration

RESEARCH OBJECTIVES

An extensive array of isotopic methods is available for monitoring subsurface geologic processes. The purpose of this project is to combine these techniques into an integrated study of important hydrologic parameters affecting the fate and transport of environmental contaminants.

The Test Area North (TAN) site at the Idaho National Engineering and Environmental Laboratory (INEEL) was chosen for this study. Between 1955 and 1972, a wide variety of waste materials, including low-level radioactive isotopes, sewage and chlorinated solvents were disposed of in a 310-ft-deep (94.5 m) well below the water table at the TAN site. The result of this activity is a 2-km plume that is currently expanding at a rate of approximately 100 m/yr.

The primary contaminant of concern at the TAN site is trichloroethylene (TCE). The regulatory goals for the site are to eliminate the source of contamination, defined as the 5000 $\mu\text{g/l}$ concentration isograd for TCE, and to decrease the remaining contamination to below 5 $\mu\text{g/l}$. The present remediation technique being utilized at the site is pump-and-treat. However, because of the low solubility of TCE, the rate of removal is slow.

APPROACH

Samples of groundwater from monitoring wells at the TAN site were collected for isotopic analyses. The δD and $\delta^{18}\text{O}$ values of the water were measured to determine the sources of the groundwater and delineate flow paths within the aquifer. The $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of groundwater strontium were measured to help further distinguish different components in the groundwater and to examine interaction between the groundwater and the rocks. The $\delta^{13}\text{C}$ and ^{14}C values of dissolved inorganic carbon (DIC) in the water were analyzed to evaluate the potential for natural attenuation of TCE at the site.

RESULTS

Source of Groundwater. A relatively large range of δD and $\delta^{18}\text{O}$ values were measured for the groundwater from the TAN site. On a plot of δD versus $\delta^{18}\text{O}$ (Figure 1), the data form a straight line, originating on the global meteoric water line and extending out with a slope of approximately 5. This is typical of evaporated water and indicates that the groundwater at the TAN site contains a major component of evaporated water. The source of this evaporated water is to the west of the plume and appears to be an artifact of a playa lake that existed at the site until the early part of the 20th century. After that time, the primary input to the playa lake (the Big Lost River drainage)

was diverted for agricultural purposes and the lake disappeared.

The strontium isotope data for the TAN waters also provide evidence of several different origins for the groundwater. The

plume of contaminated groundwater at the site appears to be confined to the upper 60 m of the aquifer. Infiltration beneath that depth is limited by a low-permeability sedimentary interbed (the "Q-R" interbed). The $^{87}\text{Sr}/^{86}\text{Sr}$ ratio of a groundwater sample from beneath the Q-R interbed is significantly higher than the $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of samples from above the interbed, indicating that this water is from a different source and that the Q-R is an effective barrier to groundwater mixing. The δD and $\delta^{18}\text{O}$ values of the deep sample further support this conclusion.

Water/Rock Interaction. The $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of groundwater in the TAN area are out of equilibrium with the rocks in the aquifer. Interaction between the water and the rocks should cause the $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of the water to shift towards the $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of the rock. The $^{87}\text{Sr}/^{86}\text{Sr}$ ratios of the groundwater samples measured do change along the axis of the plume. However, the rate of change is similar to regional variations in $^{87}\text{Sr}/^{86}\text{Sr}$ ratios observed in the Snake River aquifer. This implies that the chemistry of the plume is not causing the rates of dissolution of silicate minerals in the rock to be significantly altered.

Biodegradation of Contaminants. The ability of subsurface microorganisms to degrade TCE is one of the key issues at the TAN site. Groundwater DIC is one potential byproduct of microbial metabolism of TCE. However, there are a number of other possible sources for groundwater DIC, including dissolution of carbonate minerals, exchange with atmospheric CO_2 , and degradation of natural organic matter. Measurements of the $\delta^{13}\text{C}$ and ^{14}C values of DIC provide one possible method of identifying contributions resulting from biodegradation of TCE.

The DIC in the TAN waters does have a significant range of $\delta^{13}\text{C}$ values. The primary factor producing these variations appears to be differences between the water sources. The lowest values measured are for the more evaporated (playa lake?) waters. To a lesser extent, however, there are also vertical variations in the $\delta^{13}\text{C}$ values of the DIC, especially in the vicinity of the injection well. Where samples were collected at different depths in the plume, those from near the top of the water table tend to have lower $\delta^{13}\text{C}$ values relative to those from the base of the plume. The contaminants have much lower $\delta^{13}\text{C}$ values than the natural background, and it is possible that the vertical variations indicate that higher levels of biodegradation of contaminants are occurring near the surface of the water table.

Figure 1. $\delta^{18}\text{O}$ and δD data for water samples collected from monitoring wells at the TAN site of the Idaho National Engineering and Environmental Laboratory. Also shown are the global meteoric water line and a best fit line through the data (which is a typical trend for data observed for evaporated waters).

Measurements were also made of the ^{14}C contents of DIC in a limited number of the TAN samples. Outside of the plume, there is a good correlation between higher ^{14}C and the lower $\delta^{13}\text{C}$ DIC in more evaporated samples. This probably means that the evaporated water is younger than the other water. Within the plume ($>100 \mu\text{g/l}$ TCE), the ^{14}C contents of DIC are elevated above modern levels, indicating there was ^{14}C -enriched material in the injected waste. This suggests that the ^{14}C of DIC may be a very sensitive tracer of contaminant transport in the plume.

SIGNIFICANCE OF FINDINGS

This work has identified several geochemically distinct sources of groundwater at the TAN site. The isotopic measurements provide natural tracers that furnish information that would not be available from any standard hydrologic tests. This information will be very useful in defining

hydrologic characteristics of the TAN system such as fluid pathways, flow rates, and mixing zones. In addition, there is evidence that biologic activity within the contaminant plume may be vertically stratified, with higher contaminant degradation rates near the surface of the water table. A major focus of future work on this project will be measuring other isotopic ratios (e.g., $\delta^{13}\text{C}$, $\delta^{37}\text{Cl}$ of TCE, $\delta^{37}\text{Cl}$ of groundwater chloride) that might be useful for determining the extent of biologic activity that is occurring.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Environmental Science Management Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Reaction Rates and Flow Velocities in Fluid-Rock Systems Measured with Sr Isotopes

D. J. DePaolo

RESEARCH OBJECTIVES

The number of variables present in water-rock systems, combined with spatial heterogeneity on many scales, makes it extremely difficult to use laboratory measurements to make successful predictions about the transport properties of fluid-rock systems that have dimensions in the hundreds of meters to hundreds of kilometers. Laboratory mineral-fluid reaction rates are typically far from the observed values in most water-rock systems, and there is much debate about what causes the differences. There are potential contributions from armoring of already-reacted mineral grains, poisoning of reactive surfaces by adsorbed trace metals, or channelization of flow to reduce the effective mineral-fluid reactive surface area.

Observations of natural water-rock systems using the isotopic compositions of the fluids and rocks can be used to address this problem to a large degree. The primary observable property of natural fluid-rock systems is the "reaction length," which is the distance a fluid travels (or the distance an element can diffuse in a fluid) in the time it takes the fluid to react sufficiently with the rock matrix to approach isotopic equilibrium. Thus, observations made using isotopic ratios measure the ratio between fluid transport rates and water-rock reaction rates. Based on data we are now accumulating, effective reaction rates in many natural water-rock systems do not vary over a

very large range, as might be predicted from laboratory studies, but instead are confined to a small range that has some dependence on rock type and temperature. This implies that isotopic data can be used to estimate flow velocities within this

uncertainty. Such information is extremely useful because flow velocities are typically difficult to determine.

APPROACH

Using strontium (Sr) isotopes as an example, the shift of the $^{87}\text{Sr}/^{86}\text{Sr}$ ratio in the fluid phase in a one-dimensional groundwater-rock system with one dissolving solid phase (the simplest case) can be described in terms of a single parameter, which we call the reaction length:

$$L_e = \frac{v}{R_d M W_d c_s / c_f} \quad (1)$$

where v is the average groundwater pore velocity ($v\phi$ is the Darcy velocity), c_f and c_d are the concentrations of the element (Sr) in the fluid and the dissolving phase, respectively, R_d is the rate of the dissolution, expressed as the fractional mass dissolved per unit time, and W_d is the mass fraction of the dissolving phase in the total solid. M is the mass of solid per unit volume of fluid, which is dependent mainly on the porosity. The value of L_e is large when flow is fast in comparison to reactions, and it is small when there is rapid reaction. In the limit $L_e \rightarrow \infty$,

Figure 1. Apparent reaction rates for Sr (and O in one case) isotopes in basalts plotted versus water flow velocity. Rates are given in reciprocal million years. Data are also shown for carbonate from deep sea ooze and chalk (Richter and DePaolo, 1988). The deep sea oozes exhibit an aging effect; after 10 m.y. their reaction rates are as low as those in the basalts and several orders of magnitude lower than laboratory measurements. ODP: Ocean Drilling Project; HSDP: Hawaii Scientific Drilling Project; SRP: Snake River Plain Aquifer.

the element is a "conservative" tracer and its isotopic ratio is dependent only on the fluid "source." In the limit $L_e \rightarrow 0$, there is "local equilibrium" and the isotopic composition of the fluid reflects only that of the local rock matrix and gives no information about the fluid source. For virtually all situations, L_e is finite and nonzero. In situations where L_e is approximately the same as the scale of observation, the data are a sensitive measure of v/R_d .

Our objective is to measure L_e in natural water-rock systems where other parameters are reasonably well constrained, and thereby to determine empirically the value of R_d . Because there are so few other constraints on the magnitude of R_d , even fairly crude estimates derived from observations of natural fluids can be useful. In the examples described, it is assumed that the dissolving phase is bulk rock, which is reasonable for fine-grained volcanic rocks, and that the overall porosity is between 5% and 10%. Concentrations and isotopic ratios are measured directly on samples of fluid and rock.

RESULTS

We have been able to get a good estimate of R_d in a low-temperature system hosted by basalt from the Hawaii Scientific Drilling Project pilot corehole in Hilo. In the middle and lower parts of the well (500–800 m below sea level), the formation water is seawater that has circulated into the basalt pile. The chemistry of the fluid is almost identical to seawater, and the temperature (about 8°C) is slightly higher than the temperature of ocean water offshore at comparable depth. The water can be dated by radiocarbon, and we know that the seawater started out with an $^{87}\text{Sr}/^{86}\text{Sr}$ value of 0.70918 ± 1 . The values of $^{87}\text{Sr}/^{86}\text{Sr}$ measured in the well water (0.7088), combined with the travel distance of 12 km gives $L_e = 190 \pm 35$ km. The radiocarbon age (6,000 yr) yields a flow velocity of 2 m/yr and the derived value of R_d is $6 \pm 3 \times 10^{-9} \text{ yr}^{-1}$.

We also have been able to get a rough estimate of effective reaction rate in the basalt-hosted Snake River Plain Aquifer, which is about $4 \pm 2 \times 10^{-9} \text{ yr}^{-1}$ based on gradients in the $^{87}\text{Sr}/^{86}\text{Sr}$ ratio ($L_e \approx 150$ km). A third estimate of basalt reaction rate was derived by Schrag et al. (1992) for ocean floor basalt buried beneath Cenozoic deep sea carbonate. This estimate is based on gradients in $\delta^{18}\text{O}$ in pore fluids and is about $10 \pm 5 \times 10^{-9} \text{ yr}^{-1}$, slightly higher but also corresponding to a higher temperature of about 50–70°C.

The primary result is that the effective value of the reaction rate in Equation (1) does not vary by a large amount in natural groundwater systems, whereas the flow velocity varies by several orders of magnitude. This statement only applies strictly to fractured rock systems hosted by basaltic rocks, and to fluids with near-neutral pH. It is likely, however, that it may also be applicable to other types of rocks based on the observation that deep sea carbonate ooze yields similar values of R_d .

SIGNIFICANCE OF FINDINGS

Because it may be possible to estimate R_d empirically, it may be possible to infer groundwater velocity directly from observations of natural isotopic variations. This approach avoids the necessity of adding tracers, and may be particularly useful where groundwater velocities are too slow to allow tracer experiments to be used effectively. Application of this approach to flow in the Yucca Mountain vadose zone has yielded infiltration fluxes that are close to those obtained by other means. The approach has also been applied to groundwater at the Berkeley Lab site (Johnson and DePaolo, 1997), which flows very slowly because of the low permeability rock units.

RELATED PUBLICATIONS

- DePaolo, D. J., E. M. Stolper, and D. M. Thomas, The Hawaii scientific drilling project: summary of preliminary results, *GSA Today*, 6(8), 1–8, 1996.
- Johnson, T. M., and D. J. DePaolo, Rapid exchange effects on isotope ratios in groundwater systems, 2. Flow investigation using Sr isotope ratios, *Water Resour. Res.*, 33(1), 197–205, 1997.
- Richter, F. M., and D. J. DePaolo, Diagenesis and Sr isotopic evolution of seawater using data from DSDP 590B and 575, *Earth Planet. Sci. Lett.*, 90, 382–394, 1988.
- Schrag, D. P., D. J. DePaolo, and F. M. Richter, Oxygen isotope exchange in a two-layer model of oceanic crust, *Earth Planet. Sci. Lett.*, 111, 305–317, 1992.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Divisions of Engineering and Geosciences and of Materials Sciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

An Isotopic Approach to Determining the Industrial Contribution to Atmospheric Methyl Bromide

A. H. Goldstein and S. E. McCauley

RESEARCH OBJECTIVES

Methyl bromide (CH_3Br) is a trace gas that constitutes the primary source of stratospheric bromine. The role of bromine in stratospheric ozone loss has been well documented, but the CH_3Br budget of the troposphere has major uncertainties. Because CH_3Br is produced by both industrial and nonindustrial processes, there are large uncertainties in estimating the industrial contribution. The fraction of tropospheric CH_3Br contributed by industrial production could be as low as 10% or as high as 50%. Measurements of the carbon isotopic composition ($\delta^{13}\text{C}$) of industrial CH_3Br suggest that the $\delta^{13}\text{C}$ values of industrial and nonindustrial CH_3Br sources are different by about 30‰, and therefore that the $\delta^{13}\text{C}$ of atmospheric CH_3Br should allow accurate estimation of the industrial contribution. Our objectives are to confirm the isotopic composition of industrially produced CH_3Br and then to measure the value in the atmosphere at selected sites. This should allow us to determine with much greater accuracy the fraction of the atmospheric budget contributed by industry.

APPROACH

Samples of CH_3Br were obtained from the four largest manufacturers (Albemarle, Ameribrom, Dead Sea Bromine, Great Lakes Chemical Co.) for isotopic analysis. These companies manufacture approximately 80% of the world total CH_3Br used as a fumigant. Aliquots of each sample tank were measured by Gas Chromatography/Infrared Mass Spectrometry (GC/IRMS) at Berkeley Lab; GC-IRMS allows separation of CH_3Br from other gas species, combustion, and carbon isotope analysis in a continuous flow mode, and dramatically reduces sample-size requirements (by a factor of 10^3 – 10^4) compared to dual inlet mass spectrometry. Even with this increased sensitivity, measuring the $\delta^{13}\text{C}$ of CH_3Br from non-industrial sources and the ambient atmosphere will require significant cryogenic preconcentration.

RESULTS

Results obtained from GC/IRMS analysis are essentially identical to those obtained by sealed tube combustion and analysis on a dual inlet VG Prism mass spectrometer. The standard error of repeat $\delta^{13}\text{C}$ measurements is ca. 0.25‰ for each tank. The measured $\delta^{13}\text{C}$ values of industrially produced CH_3Br are all low (the value for atmospheric CO_2 is about -9 for comparison), but there is significant variability between manufacturers. The lowest value is ca. -68‰ and the highest is -48‰. The CH_3Br from the largest of the manufacturers (Ameribrom) has the highest $\delta^{13}\text{C}$ value. The industrial CH_3Br source is iso-

topically light, probably because thermogenic methane is used as a carbon source for methanol, which in turn is the feedstock for manufacturing CH_3Br . The average $\delta^{13}\text{C}$ of the industrial CH_3Br source, weighted by production values, is about -56‰.

The $\delta^{13}\text{C}$ values of natural CH_3Br sources have not been directly measured, but we predict they will be isotopically heavy relative to the industrial source. Most combustion-produced hydrocarbons, including CH_4 , have $\delta^{13}\text{C}$ values that reflect the source biomass $\delta^{13}\text{C}$, which is approximately -27‰ for forests. Marine algae also produce CH_3Br and have a $\delta^{13}\text{C}$ value of around -20‰. Barring significant fractionation during either formation process, we believe that these two sources will have a mean signature of approximately -25‰. Testing this prediction will be an important step.

SIGNIFICANCE OF FINDINGS

The $\delta^{13}\text{C}$ of atmospheric CH_3Br should primarily reflect mixing between biomass burning, marine algae and industrial sources. It is possible, however, that the $\delta^{13}\text{C}$ of atmospheric CH_3Br will also be influenced by the sink mechanisms that remove it from the atmosphere. For CH_4 , the primary sink mechanism is oxidation by the OH radical; this sink fractionation has been measured to be about +5‰. The sink fractionation for $\text{OH} + \text{CH}_3\text{Br}$ should be smaller because of the high mass of Br. Other sink fractionations associated with degradation in seawater and in soils are also possible, but are also likely to be small (order of 5‰ or less) compared to the difference in source signatures. These fractionations must be determined experimentally before a full analysis of the CH_3Br budget can be completed.

An intensive sampling campaign could probably resolve the industrial source signature to ± 2 ‰, the non-industrial combined source to ± 5 ‰, and the atmospheric value for a given air mass to better than 1‰, making it possible to resolve the industrial fraction of atmospheric CH_3Br to ± 10 %. Variations in $\delta^{13}\text{C}$ of atmospheric CH_3Br with time and latitude should provide additional information about the factors controlling the interhemispheric gradient of CH_3Br .

Isotopic measurements of the main CH_3Br sources and the atmospheric reservoir should greatly improve our understanding of the CH_3Br budget, and of the biogeochemical processes controlling atmospheric CH_3Br . This approach would also provide an independent tool for assessing the effectiveness of recent amendments to the Montreal Protocol that call for the complete phaseout of CH_3Br by 2005 in industrialized nations.

Figure 1. Comparison of estimated values of $\delta^{13}\text{C}$ in natural sources of CH_3Br and the values measured at Berkeley Lab for industrial CH_3Br (McCauley et al., 1998). The average values are different by about 30 permil; analytical uncertainty is expected to be 1 permil for air samples.

RELATED PUBLICATIONS

- Goldstein, A. H., B. C. Duabe, J. W. Munger, and S. C. Wofsy, Automated in-situ monitoring of atmospheric non-methane hydrocarbon concentrations and gradients, *J. of Atmos. Chem.*, 21, 43-59, 1995.
- Goldstein, A. H., S. C. Wofsy, and C.M. Spivakovsky, Seasonal variations of nonmethane hydrocarbons in rural New England: Constraints on OH concentrations in northern midlatitudes, *J. of Geophys. Res.*, 100(D10), 21023-21033, 1995.

McCauley, S. E., and D. J. DePaolo, The Marine $^{87}\text{Sr}/^{86}\text{Sr}$ and $\delta^{18}\text{O}$ records, Himalayan alkalinity fluxes, and Cenozoic climate models, in *Tectonic Uplift and Climate Change*, edited by W. F. Ruddiman, pp. 427-467, Plenum Press, New York, N.Y., 1997.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Models for Global Atmospheric Moisture Transport and Implications for Isotopic Paleotemperature Records in Ice Cores

M. B. Hendricks and D. J. DePaolo

RESEARCH OBJECTIVES

Much of current knowledge about how extensive global climate change can be and how rapidly it can occur is based on paleotemperature records retrieved from glacial ice in Antarctica and Greenland. The paleotemperature estimates are based on measurements of the isotopic composition of oxygen and hydrogen (normally expressed as $\delta^{18}\text{O}$ and δD) in ice. The glacial ice represents snow precipitated and accumulated over the past 200 to 300 thousand years. The conversion of water isotope ratios to mean annual temperature is uncertain. Current estimates are based on the modern-day observed relationship between the $\delta^{18}\text{O}$ isotopic composition of snow and mean annual temperature, but this may not apply to earlier times, when the climate was very different. The objective of this research is to (1) develop a relatively simple model of meridional moisture transport and use it to evaluate the controls on $\delta^{18}\text{O}$ and δD of precipitation, and (2) re-evaluate the isotopic data from polar ice cores in terms of paleotemperatures.

Oxygen and hydrogen isotopic ratios in precipitation differ from the isotopic ratios in ocean water due to isotopic fractionation that occurs with every evaporation and condensation step in the hydrologic cycle. The heavy isotopes, ^{18}O and ^2H (D), systematically decrease in abundance in precipitation, falling in regions of decreasing mean annual surface temperature. The heavy isotopes are most depleted in Antarctic precipitation, in which there is also a nearly linear relationship between $\delta^{18}\text{O}$ and surface temperature. The linear relationship is typically attributed to Rayleigh distillation, which is a simple conceptual model that neglects all complexities of atmospheric water vapor transport. General circulation models (GCMs) produce reasonably good fits to the modern $\delta^{18}\text{O}$ -temperature relationship, but are too complex to clearly elucidate the controlling mechanisms.

APPROACH

We start with a relatively simple conservation statement describing the essential transport processes that affect

isotopic fractionation in atmospheric water vapor. The total column water vapor in the atmosphere, w , is described by:

$$\frac{\partial w}{\partial t} = D\nabla^2 w - v\nabla w + E - P \quad (1)$$

The first term on the right-hand side is transport due to eddy processes, which is described here as diffusion. The second term is transport due to advection, and the third and fourth are source/sink terms: evaporation from the ocean and land surface (E) and precipitation (P), respectively. The first two terms effectively represent horizontal moisture transport in the atmosphere. They are separated into eddy-diffusive and advective components because the two types of transport have different effects on isotopic fractionation. By treating isotopes as different species, with slightly different values for E and P , an analogous conservation equation for the transport of isotopic ratios can be derived.

Isotopic fractionation ultimately is caused by the fact that cold air holds much less water than warm air. As moisture is transported from warm to cold areas, precipitation must exceed evaporation and the net "rainout" of atmospheric moisture causes isotopic fractionation. Consequently, isotopic gradients in precipitation follow temperature gradients. The primary isotopic variations globally are a function of latitude; the $\delta^{18}\text{O}$ values of precipitation are high near the equator and very low at the poles. The simplest description of the earth, therefore, is a one-dimensional version of Equation 1 in spherical polar coordinates, with the single spatial variable being latitude. We also use the steady-state approximation ($\partial w/\partial t = 0$), and assume that relative humidity is uniform.

Equation (1) implies that isotopic ratios in precipitation are controlled by three processes: evaporation from the ocean surface, eddy-diffusive transport, and advective transport. Transport by diffusion causes more horizontal mixing between air masses, decreasing the rate at which the isotopes are fractionated relative to that caused by pure advection. Isotopic fractionation therefore depends on

Figure 1. The dimensionless parameter relating the importance of evaporative recharge to diffusional transport in determining isotopic ratios in precipitation. The parameter L is the length scale for rainout, which is a function of the surface temperature gradient. Evaporation dominates at low latitudes and diffusive transport is most significant at high latitudes.

two dimensionless parameters — one that relates the rate of evaporation to the amount of diffusive transport (see Figure 1), and one that describes the relative amount of diffusive versus advective transport.

RESULTS

Based on the known (but still somewhat uncertain) values of E and P as a function of latitude, and accepted values for large scale eddy diffusivities, the Earth can be divided into three regions (Fig-

ure 1). Between approximately 75°N and 45°S, evaporation is the dominant control on the value of $\delta^{18}\text{O}$ and δD in precipitation. In this region, the exchange rate between the ocean and the atmosphere, via evaporation and precipitation, is so high that $\delta^{18}\text{O}$ and δD are nearly constant and only very weakly dependent on surface temperature.

Outside of the broad equatorial zone, evaporation rates drop significantly and the isotopic composition of precipitation is more strongly controlled by the rate at which air must lose moisture poleward due to decreasing temperature. The type of transport determines the rate of decrease in $\delta^{18}\text{O}$ and δD with temperature decrease. Other climatic changes, such as changes in the evaporation source, decrease in sea surface temperature, and variations in precipitation levels, do not have a large effect on the values of $\delta^{18}\text{O}$ and δD , but do affect the tightly constrained relationship between $\delta^{18}\text{O}$ and δD in precipitation.

Our model is effective in simulating isotopic ratios in precipitation without the complexity of GCMs. The relative significance of advection and eddy-diffusion in the transport of water vapor from the tropics to the polar regions is very important and evaporation from the ocean surface into air masses cannot be neglected. The results of sensitivity studies reveal that isotopic composition of precipitation in polar regions is most dependent on the amount of water vapor in the air column over the conti-

Figure 2. The change in $\delta^{18}\text{O}$ for a colder climate, such as that of the last glacial period. The red line represents the model-predicted change in $\delta^{18}\text{O}$ for transport by eddy-diffusion only. The blue line is the predicted change in $\delta^{18}\text{O}$ for transport by advection only. The heavy green line is the relationship in modern precipitation, which has been used to interpret the ice core record, but probably does not apply.

ment and the magnitude of change in that parameter between the coast and the interior of the continent, which contains an effect due to elevation as well as temperature. Water vapor content of the atmosphere above Antarctica is not well known and needs to be investigated further. If good water vapor data were available, the isotopic data would tightly constrain the ratio of diffusive to advective transport over Antarctica.

SIGNIFICANCE OF FINDINGS

When applied to precipitation that fell in Antarctica during the last maximum glacial period, about 20,000 years ago, the model predicts a larger change in past global temperatures than has been inferred from the modern $\delta^{18}\text{O}$ -temperature relationship (Figure 2). The model results suggest that actual temperatures 20,000 years ago were colder by 6°C to 10°C than has been previously estimated. This further emphasizes the idea that global temperature can change by very large amounts in relatively short time periods.

The isotopic compositions of paleoprecipitation in both mid-latitude and high-latitude regions may be useful for monitoring past and future global temperature changes, but they can be interpreted properly only in the context of appropriate models for atmospheric moisture transport.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098..

Air-Xe Enrichments in Oil Field Gases and the Influence of Water During Oil Migration and Storage

B. M. Kennedy and T. Torgersen*

*University of Connecticut

RESEARCH OBJECTIVES

Water or brines are often co-produced with hydrocarbons, yet their role in hydrocarbon formation, migration, and accumulation is not well understood. Groundwaters (fresh or connate) tend to be saturated in atmospheric noble gases that can be readily identified by their elemental and isotopic compositions. In general, noble gases associated with hydrocarbons have relative abundances and isotopic compositions, suggesting that air-saturated formation waters play an important role in hydrocarbon systems. Typically, however, the amount of air-derived krypton (Kr) and xenon (Xe) is in excess of that predicted by their solubilities in water or oil. Kr and Xe are ~1.5–4 times more soluble in oil and water than Ar, yet $^{132}\text{Xe}/^{36}\text{Ar}$ argon (Ar) ratios of ~10–20 times the ratio in air or air-saturated water are not uncommon. It is important to identify the source or cause of the heavy noble gas enrichments in order to understand the role of water in hydrocarbon systems.

In one model, the Kr and Xe enrichments reflect fractionation driven by equilibrium solubility partitioning between water, natural gas, and oil (Bosch and Mazor, 1988). The model assumes that the entire air noble gas budget in hydrocarbon fluids originated in air-saturated water. A second model suggests that the excess heavy noble gases associated with hydrocarbons were originally trapped in the carbon-rich petroleum source rocks and are, therefore, somehow related to hydrocarbon formation and expulsion (Hiyagon and Kennedy, 1992). The basis of this model is the observation that carbon-rich sediments (e.g., shales) are strongly enriched in air-derived heavy noble gases relative to their proportions in air or air saturated water (Podosek et al., 1980).

APPROACH

In this study, we determined the elemental and isotopic compositions of noble gases associated with

oil and gas from the southern San Joaquin Valley, California. Samples were obtained from production wells in three oil fields: Elk Hills, operated by Bechtel Petroleum Operations (DOE operator for NPR#1); Cymric-McKittrick, operated by Chevron; and North Coles Levee, operated by Arco.

RESULTS

We found the produced gases to be strongly enriched in Kr and Xe relative to the other air-derived noble gases (Figure 1). The average $^{132}\text{Xe}/^{36}\text{Ar}$ enrichment factors are ~30 times the air ratio and in some cases are as high as 576 times the ratio in air. These represent the highest $^{132}\text{Xe}/^{36}\text{Ar}$ ratios measured to date in terrestrial fluids and fall well outside the range predicted by the solubility partitioning model (Bosch and Mazor, 1988). The large magnitude of the enrichments combined with an inverse correlation between the degree of Kr/Xe-enrichment and ^{36}Ar concentration (Figure 2) suggests mixing between noble gases derived from air-saturated water and a heavy noble gas enriched component indigenous to the hydrocarbons.

We propose a model in which Kr-Xe-enriched hydrocarbon phases become diluted with noble gases

extracted from air saturated groundwater during hydrocarbon migration and storage. The concentrations of noble gas per gram of carbon in the initial expelled hydrocarbon phase can be reasonably estimated from the measured concentrations in carbon-rich rocks. These estimates are shown in Figure 2 as a range of values depicted by the shaded region. The solid lines are dilution trajectories depicting the addition of noble gases extracted from groundwater. The numbers along each trajectory are the water/carbon mass ratios. In general, the composition of the production fluids conforms to the simple model and suggests that during hydrocarbon

Figure 1. Relative Kr and Xe abundances in production fluids from southern San Joaquin oil fields: solid circles, Elk Hills and North Coles Levee fields; open circles, Cymric McKittrick field. $F(i)$ values are the $i/^{36}\text{Ar}$ ratio in the production fluid normalized to the same ratio in air. ASW (air-saturated water) is the composition of water in equilibrium with air at 10 °C. The linear trend indicates mixing between a Kr-Xe-enriched component and either air-saturated water and/or air.

Figure 2. Oil-water mixing model. Symbols are the same as in Figure 1. The shaded region reflects the range in noble gas compositions of carbon-rich sedimentary rocks (Podosek, et al., 1980). The solid lines are mixing trajectories between the hydrocarbon end member and air-saturated water. The tick marks along the trajectories are water/carbon mass ratios in the mixture.

expulsion, migration, and storage each gram of carbon has equilibrated with only ~10–100 g of air-saturated water.

SIGNIFICANCE OF FINDINGS

An aqueous solution of methane and/or oil has had a limited role in the generation, migration and accumulation of oil in the southern San Joaquin fields. The very low water/oil ratios provide geochemical support for oil migration by solution in a supercritical methane phase and indicate that low water/oil environments can produce large hydrocarbon accumulations; the Elk Hills field alone has produced over 2 billion barrels of oil. It is interesting to note that the water/methane ratio of the Alberta gas fields is of the order of 200–1,000 g-water/g-carbon and that these gases occur with no accompanying oil phase. We cannot, therefore, rule out aqueous phase migration of methane in the Alberta system. However, the noble gas estimated water/methane ratio of the Alberta field becomes a test for models describing basin scale hydrologic flow (Garven, 1989) by requiring 200–1,000 passes of water through the field over the lifetime of the reservoir.

RELATED PUBLICATION

Hiyagon, H., and B. M. Kennedy, Noble gases in CH₄-rich gas fields, Alberta, Canada, *Geochim. Cosmochim. Acta.*, 56, 1569–1589, 1992.

REFERENCES

- Bosch, A., and E. Mazor, Natural gas association with water and oil as depicted by atmospheric noble gases: case studies from southeastern Mediterranean Coastal Plain, *Earth Planet. Sci. Lett.*, 87, 338–346, 1988.
- Garven, G., A hydrologic model for the formation of the giant oil sand deposits of the western Canada sedimentary basin, *Am. J. Sci.*, 289, 105–166, 1989.
- Podosek, F. A., M. Honda, and M. Ozima, Sedimentary noble gases, *Geochim. Cosmochim. Acta.*, 44, 1875–1884, 1980.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Mantle Fluids in the San Andreas Fault System, California

B. M. Kennedy and Y. K. Kharaka*

*United States Geological Survey

RESEARCH OBJECTIVES

The San Andreas Fault (SAF) is known to be a weak fault, and explanations for its weakness include either low friction fault zone materials or superhydrostatic fluid pressures within the fault zone (Hickman, 1991; Hickman et al., 1995). Models of fault weakening by elevated fluid pressures call on different fluid origins. Crustal fluids, connate or meteoric, may be drawn into the fault zone in response to fault rupture and become trapped by mineral reactions; high fluid pressures required to weaken the fault are re-established by compaction of the sealed fault zone materials (Byerlee, 1990; Byerlee, 1993; Sleep and Blanpied, 1992). In this model, the base of the seismogenic zone, defined by the brittle-ductile transition, is treated as an impermeable boundary. In an alternative model, fault weakening fluid pressures are generated by a high flux of deep crustal or mantle fluids that are continually supplied to the seismogenic zone from the ductile lower crust at superhydrostatic pressures (Rice, 1992).

APPROACH

To investigate fluid source and influence on SAF dynamics, we conducted a chemical and helium isotopic study of selected springs, seeps, and wells associated with the SAF and companion faults. Elevated discharge temperatures or salinity, unusual solute chemistry, high gas or water flow rates, or other indications of deep circulation or extensive water-rock interaction were used to select sampling sites.

RESULTS

The fluids can be divided into four categories based on geochemistry (Figure 1), which is controlled by local crustal provenance lithologies, and into meteoric or evolved connate based on water isotopes (Figure 2). The helium isotopic compositions varied from 0.12 to 4.0 Ra (Ra is the $^3\text{He}/^4\text{He}$ ratio in air) and indicate that fluids from the

SAF system contain mantle He contributions of ~1 to ~50% (Figure 3). The high $^3\text{He}/^4\text{He}$ ratios represent an influx of mantle fluids, and the hydrodynamics thus require that (i) the

brittle-ductile transition is a permeable boundary, and (ii) mantle fluids crossing this boundary and entering the seismogenic zone must be at or near lithostatic pressure.

As mantle fluids flow up through the fault zone, the $^3\text{He}/^4\text{He}$ ratios will become diluted with radiogenic ^4He that is produced locally in the crust, generating a vertical gradient in the fault zone helium isotopic composition that depends on the vertical rate of fluid flow. Calculated flow rates vary from ~1–10 mm yr⁻¹ (Figure 3). A flow of ~3 mm yr⁻¹ corresponds to a ^3He flux through the SAF of ~2 × 10⁻¹⁵ mole cm⁻² yr⁻¹, which integrated over the entire San Andreas system implies a total flux of ~6 mole ^3He yr⁻¹. One can assume that the mantle ^3He is associated with other more abundant mantle volatiles, certainly CO₂ and perhaps water. Using the upper mantle CO₂/ ^3He ratio of ~10¹⁰ implies a mantle CO₂ flux of ~10¹¹ mole yr⁻¹.

The pore pressure induced by the CO₂ flux will depend on crustal permeability. If the permeability is constant with depth, then the ^3He calculated CO₂ flux implies a permeability of ~10⁻²¹ m² to maintain high pore pressures through the ductile region and into the seismogenic zone. Alternatively, if permeability decreases exponentially with depth at a rate scaled to a linear increase in stress, then at the base of the seismogenic zone superhydrostatic pressures imply fault zone permeability of ~10⁻¹⁸ m² (Rice, 1992). In this context, fault weakening by mantle fluid inflow at the rate implied by the ^3He flux seems plausible.

SIGNIFICANCE OF FINDINGS

The flux of mantle He through the San Andreas system requires a brittle-ductile boundary that is permeable and supports the fault weakening model

Figure 1. Ternary plot of major anion concentrations in deep fault zone fluids from the San Andreas system. Co-variations delineate four chemically distinct fluids: chloride-rich (yellow), sulfate-rich (red), bicarbonate-rich (blue), and bicarbonate- and chloride-rich (green). Symbol shapes refer to sample groups defined by location: San Andreas Group (SAG, squares), western Transverse Ranges (SYG, triangles), and the southern Coast Ranges (CRG, diamonds).

Figure 2. Isotopic composition of fault zone waters (symbols as in Figure 1). Dashed line labeled MWL (Meteoric Water Line) depicts expected variations in the isotopic composition of meteoric waters. Box defines the range in isotopic compositions of oil field waters from the San Joaquin Valley, Ca.

Figure 3. The helium isotopic composition, percent mantle helium, and fluid flow rate plotted as a function of the approximate distance from the main strike of the SAF (symbols as in Figure 1; MHS: Merced Hot Spring, MM: Middle Mountain Oil Well, VP: Varian-Philips Well, SC: Stone Canyon Well).

calling for high fault zone fluid pressures driven by a mantle source (Rice, 1992). If we have sampled fluids directly from fault zones, then the observation that mantle helium is mixed with fluids from the adjacent crust implies that elements of both models (Byerlee, 1990; Byerlee, 1993; Rice, 1992; Sleep and Blanpied, 1992) are important. Because weakness of the fault system is generated by high fluid pressures in the fault zone relative to the surrounding crust, infiltration of crustal fluids into the fault zone requires episodic reversals of the fluid pressure gradient. Local increases in fault zone porosity induced by fault failure may temporarily lower the fluid pressure, permitting infiltration of crustal fluids. The regional distribution of high $^3\text{He}/^4\text{He}$ ratios will place constraints on models for the lithospheric structure of the San Andreas system.

RELATED PUBLICATION

Kennedy, B. M., Y. K. Kharaka, W. C. Evans, A. Ellwood, D. J. DePaolo, J. Thordsen, G. Ambats, and R.H. Mariner, Mantle Fluids in the San Andreas Fault System, California, *Science*, 278, 1278–1281, 1997.

REFERENCES

- Byerlee, J. D., Friction, overpressure and fault normal compression, *Geophys. Res. Lett.* 17, 2109–2112, 1990.
- Byerlee, J. D., A model for episodic flow of high pressure water in fault zones before earthquakes, *Geology*, 21, 303–306, 1993.
- Hickman, S., Stress in the lithosphere and the strength of active faults, *Rev. Geophys.* 29, 759–775, 1991.
- Hickman, S., R. Sibson, and R. Bruhn, Introduction to special section: Mechanical involvement of fluids in faulting, *J. Geophys. Res.*, 100, 12,831–12,840, 1995.
- Rice, J. R., Fault stress states, pore pressure distributions, and the weakness of the San Andreas fault, in *Fault Mechanics and Transport Properties of Rocks*, edited by B. Evans and T. F. Wong, pp. 475–503, Academic Press, San Diego, Calif., 1992.
- Sleep, N. H., and M. L. Blanpied, Creep, compaction, and the weak rheology of major faults, *Nature*, 359, 687–692, 1992.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Regional Climate System Modeling and Applications

N. L. Miller and J. Kim

RESEARCH OBJECTIVES

Understanding the impacts of global climate change at regional scales has become an important emerging international concern. The Regional Climate System Model (RCSM) Team has been participating in a number of activities to better understand the past, present, and future climates of the southwestern United States, east Asia, and northeast Australia. The goals of our research are to produce regional short-term (2-3 day) hydroclimate, seasonal hydroclimate, and long-term climate change simulations. The results from these simulations will provide water resources managers, policy decision makers, and the general public with important information on the state of our water resources.

APPROACH

The Regional Climate System Model (RCSM) produces high-resolution (10-20 km) information for impact assessments by downscaling large-scale data. Its products include regional hydroclimate simulations (precipitation, snow budget, soil moisture, streamflow, temperature, wind, surface energy and water budgets) for short-term forecasts, seasonal-scale predictions, and long-term climate scenarios. Downscaled hydroclimate data are used to drive a variety of assessment models for water resources, agricultural productivity, forest productivity, and ecosystem response. The flexible structure of the RCSM allows us to include additional assessment components with relative ease. The RCSM is an integrated modeling system for regional hydroclimate modeling and impact assessments. It consists of a pre-processor to prepare input data from GCM simulations, global analysis, land surface geographical information, satellite and other remotely sensed data; physically based process models for atmospheric, land-surface, and river flow modeling; and a post-processor for output data analysis and impact assessments (Figure 1).

RESULTS

The RCSM has been successfully employed for experimental weather and basin-scale quantitative precipitation and streamflow predictions, seasonal-scale predictions, and hydroclimate and water

resource assessments for the southwestern U.S. since 1994 (Miller and Kim, 1998). U.S. National Weather Service offices and River Forecast centers in

the southwestern U.S. have been using and evaluating our weather and streamflow forecasts as a part of their operational forecasts. The RCSM and its components are being used for hydroclimate downscaling, regional climate variability, water resources, agro-ecosystem response, and sustainability studies for east Asia and northeast Australia.

During the 1997-1998 wet season, we automated 48-hr precipitation and streamflow predictions. Streamflow predictions are produced at 6-hr time steps for two sub-basins of the Russian River at the northern California Coastal Range. Streamflow forecasts showed good skill during periods of continuous precipitation when uncertainties in the antecedent soil moisture conditions were small (Figure 2).

Streamflow forecast skill was fair to poor during dry periods, when base flow is a dominant source of streamflow. As a result, this coupled streamflow prediction technique was especially useful in predicting the timing and amount of flow during heavy precipitation events that are important for flood forecasting and reservoir operations.

A seasonal hindcast experiment utilized the initial fields of the National Oceanographic and Atmospheric Administration's (NOAA) National Center for Environmental Predictions (NCEP) aviation forecast to run the RCSM. The main purpose of this experiment is an evaluation of the RCSM and a water resources assessment. We have obtained good agreement between the simulated and observed streamflow over the two sub-basins, the Upland and the Healdsburg basins, of the Russian River, with correlation values of 0.61 and 0.81, respectively

[Figures 3(a) and (b)].

A seasonal hydroclimate prediction experiment took place for the period November 1, 1997, to March 31, 1998, as a collaboration between the University of California and the NCEP. The large-scale forcing data were produced by the UCLA General Circulation Model driven by the Sea Surface Temperature forecast from NOAA. The main focus of this experiment

Figure 1. The Regional Climate System Model.

is to establish a seasonal prediction system for the western United States, examine the performance of the system, and develop a method for simulating and producing information useful for water resources management and long-term planning. The strong ENSO during the 1997–1998 winter season made this study more important. The predicted streamflow characteristics (e.g., frequency and duration of high flow events, monthly discharge volume) at the two basins described above showed promising results. As expected, a daily time series generated from the GCM-driven seasonal forecast is not useful at this early stage.

SIGNIFICANCE OF FINDINGS

The Regional Climate System Model is an important new Earth Sciences Division capability. It is being used as the simulation tool for a projected doubled carbon dioxide atmosphere ($2 \times \text{CO}_2$) in California as part of the U.S. National Assessment on Climate Variability and Climate Change. RCSM 48-hour forecasts are used by the National Weather Service during the rainy season to augment local watches and warnings. It is contributing toward the pioneered resrach to produce physically based seasonal forecasts.

RELATED PUBLICATIONS

Kim, J. N. L. Miller, A. K. Guetter, and K. P. Georgakakos, River flow response to precipitation and snow budget in California during the 1994–1995 winter, *J. Climate*, in press, 1998.

Miller, N. L., and J. Kim, The regional climate system model, in *Mission Earth: Modeling and Simulation for a Sustainable Global System*, edited by M. C. Clymer and C. R. Mechoso, pp. 43–52, Pub. Soc. Comp. Sim., 1997.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098; by the Administrator of the National Aeronautics and Space Administration, NASA Mission to Planet Earth Project; and by the University of California Campus–Laboratory Collaboration Hydrology Project.

Figure 2. Forecasted 48 hour precipitation and streamflow Hopland Basin, Russian River, California.

Figure 3. Hydroclimate seasonal simulation (Nov. 1, 1997–Mar. 31, 1998) AVN/MAS/Top Model: (Top) Russian River at Healdsburg, (Bottom) Russian River at Hopland.

Measurements of Cosmogenic Nuclides in Extraterrestrial and Terrestrial Materials

K. Nishiizumi, R. C. Finkel,
M. W. Caffee, W. E. Dietrich,*
and A. M. Heimsath*

*University of California, Berkeley

RESEARCH OBJECTIVES

Our goal is to use cosmogenic nuclide measurements to help us understand fundamental processes affecting the history of extraterrestrial materials such as lunar and meteoritic samples. We have developed techniques to measure nuclides with half lives ranging from 1.0×10^5 yr, ^{41}Ca , to 1.57×10^7 yr, ^{129}I . In addition to the histories of meteorites and lunar surface materials, we also are studying the history of the Sun (solar cosmic rays: SCR) and of the galactic cosmic rays (GCR). We have extended our cosmogenic nuclide studies to include the paleoclimate record in polar ice and terrestrial surface processes.

We continue to investigate cosmogenic ^{10}Be and ^{36}Cl in a Greenland ice core (GISP2). The objective is a continuous profile of cosmogenic nuclide concentrations from the surface to the bottom of the core. The resulting time series of nuclide concentrations will be applied to three main problem areas: the historical intensity of solar activity, historical variations in the geomagnetic field, and obtaining integrated ages for sections of the ice core. In addition, we use cosmogenic radionuclide concentrations to study climatic history through the effects of atmospheric circulation and atmospheric chemistry on nuclide deposition.

APPROACH

We study the nature and evolution of solar system materials, including cosmic rays over the time period from near 10^8 yr to the present to study the nature and evolution of solar system materials including cosmic rays. These studies involve measurements of long-lived cosmogenic radionuclides (^{10}Be , ^{26}Al , ^{36}Cl , ^{41}Ca , and ^{129}I) using accelerator mass spectrometry (AMS), measurement of ^{53}Mn using neutron activation, and, with collaborators, measurement of stable cosmogenic nuclides (e.g., ^3He and ^{21}Ne).

The advent of AMS dramatically increased the measurement sensitivity and accuracy of long-lived nuclides (detection limits are a few times 10^5 atoms for ^{10}Be , ^{26}Al , and ^{36}Cl with ratios of 10^{-14} – 10^{-15} to stable isotopes). We have measured these nuclides at the Lawrence Livermore National Laboratory's AMS facility (CAMS).

Most lunar meteorites have complex cosmic ray exposure histories, having been exposed both at some depth on the Moon (2π irradiation) before their ejection and as small bodies in space (4π irradiation) during transport from the Moon to the Earth. Once captured by the Earth, there follows a long terrestrial residence time. Measurements of cosmogenic radio- and stable nuclides can

unravel the complex histories of these objects if at least four nuclides can be measured. The concentrations of cosmogenic nuclides also constrain the depth of the sample at the time of ejection from the Moon. These exposure durations can then be used to model impact and ejection mechanisms.

RESULTS AND SIGNIFICANCE OF FINDINGS

Extraterrestrial Materials

Lunar Meteorites. We measured ^{10}Be , ^{26}Al , ^{36}Cl , and ^{41}Ca in lunar meteorites QUE93069 and QUE94269. The chemical compositions and cosmogenic radionuclide concentrations in QUE93069 and QUE94269 are identical and suggest that they are a pair. The ^{36}Cl concentrations in surface samples are slightly lower than the interior samples due to evaporative loss during atmospheric entry. The ^{26}Al values in both exterior samples of the QUE93069 and QUE94269 pair were 7–9% higher than interior samples, which indicates SCR bombardment during the short transition time from the Moon to the Earth. Based on the ^{14}C concentration in QUE93069, the terrestrial age of the meteorite is 12 ky. After the terrestrial age correction, the patterns of the three cosmogenic nuclide concentrations were compared with those of the Apollo 16 cores, and we conclude that the paired lunar meteorites were ejected from 65–80 g/cm² below the surface of the Moon, had a short 4π exposure of 20–50 ky, and a 12 ky terrestrial age. This is the first case where it has been possible to obtain definite durations for both the 2π and 4π exposure ages as well as the terrestrial age of a lunar meteorite (Nishiizumi et al., 1996).

Martian meteorites. Some meteorites found on the Earth (SNC meteorites) have been shown to come from Mars. Using cosmic-ray-produced nuclide exposure histories, the timing and conditions of ejection from the hypothesized Martian parent body can be determined. We measured ^{10}Be , ^{26}Al , and ^{36}Cl concentrations in a new Antarctic shergottite, Yamato 793605 (Y793605). The ^{36}Cl terrestrial age is <70 ky. The ^{10}Be concentration in Y793605 is similar to those of LEW88516 and ALH77005. However, this ^{10}Be concentration differs significantly from those of other basaltic shergottites such as Shergotty, Zagami, and QUE94201. The ^{10}Be exposure age of Y793605 is 4.0 My or longer and consistent with the noble gas exposure age of ~5.4 My. The exposure ages of all the shergottites seemingly require at least four ejection events (0.6, 2.4, 3.0–4.0, and ~5.4 My) from their parent body. Even among those shergottites having similar cosmic ray exposure ages, the different terrestrial ages indicate that

each shergottite was ejected as an individual object from the parent body.

At least 8 out of the 12 lunar meteorites we have studied were ejected from shallow depths in the Moon. In contrast, none of the Martian meteorites studied to date show evidence of a 2π bombardment on their hypothesized Martian surface. Evidently, all Martian meteorites were ejected from a much deeper depth than were most lunar meteorites. More than half of the lunar meteorites reached the Earth within 100 ky of their ejection. In contrast, Martian meteorites have much longer transit times.

Terrestrial Materials. We have developed techniques for studying the rates of geomorphological processes such as erosion, glacier movement, and meteorite impact events using the *in-situ* produced cosmogenic nuclides ^{10}Be and ^{26}Al in quartz. Numerical modeling of the evolution of soil depth on an eroding landscape suggests that local soils quickly reach a time-independent thickness on divergent hillslopes (ridges). We applied two independent experimental methods that allowed the validity of the hypothesized dependence of soil production rate on soil thickness to be tested for the first time. One of the methods directly determines soil production rates by measuring the concentration of cosmogenic radionuclides in exposed bedrock and in bedrock at the base of the soil column. We have applied the methods at six field sites—three in California, one in Oregon, and two in Australia.

Polar Ice Cores. We have determined cosmogenic nuclide profiles from 334 m to the bottom (3,053 m) of the GISP2 ice core. The ^{10}Be and ^{36}Cl concentrations show significant variations on several time scales. Some of these variations are correlated with the climate swings that occurred at the end of the last glacial period. Others seem to be independent of climate and to be more directly related to changes in the production rates of cosmogenic nuclides in the atmosphere. Much of this variability in the 1,300–12,000-yr time range most likely results from variation in the helio-magnetic modulation of the GCR flux. A good correlation is observed between the ^{10}Be concentration in ice, on the GISP2 time scale, and $\Delta^{14}\text{C}$ values in wood. Over the length of our Holocene record, an approximately 100-yr lag for the tree ring

record must be invoked to bring the $\Delta^{14}\text{C}$ into registration with the ^{10}Be . One possible explanation for this offset is that the time scales may be in error. Secondly, it is also possible that carbon transfer with quickly exchanging reservoirs such as the biosphere or the surface ocean can contribute some (but probably not all) of the lag in $\Delta^{14}\text{C}$ peaks relative to those of ^{10}Be . In addition to the constant 100-yr offset, it appears that an additional gap of about 150 yr is required somewhere between 9.5 ky BP and 10.9 ky BP to keep the ^{10}Be and $\Delta^{14}\text{C}$ records in registration. This gap occurs in the part of the $\Delta^{14}\text{C}$ record where there are still uncertainties in tying the German Oak ^{14}C chronology to the German Pine ^{14}C chronology. The ^{10}Be and ^{36}Cl record in ice may, therefore, prove useful in improving the reliability of the ^{14}C time scale during this period. This figure gives strong evidence that at GISP2 the effects of extended periods of low solar activity, such as that observed during the Maunder minimum, are reliably detectable. This offers the exciting possibility of studying solar variations well beyond the tree ring limit by using ^{10}Be (Finkel and Nishiizumi, 1997).

RELATED PUBLICATIONS

Finkel, R. C., and K. Nishiizumi, Beryllium 10 concentrations in the Greenland Ice Sheet Project 2 ice core from 3–40 ka, *J. Geophys. Res.*, 102, 26,699–26,706, 1997.

Nishiizumi, K., M. W. Caffee, A. J. T. Jull, and R. C. Reedy, Exposure history of lunar meteorites Queen Alexandra Range 93069 and 94269, *Meteorit. Planet. Sci.*, 31, 893–896, 1996.

FUNDING

This work has been supported by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098; the Administrator of the National Aeronautics and Space Administration, Office of Space Science; the Director of the National Science Foundation, Office of Polar Programs.

Nuclear Waste Department

Gudmundur S. Bodvarsson,
Nuclear Waste Department
Head

The Nuclear Waste Department assists the Department of Energy and the United States, as well as other countries, to solve the problem of how to safely dispose of nuclear waste through high-quality scientific analyses and technology development. The primary work of the Department involves investigating the feasibility and potential of the Yucca Mountain Site in Nevada for permanent storage of high-level nuclear waste. The Nuclear Waste Department also does collaborative work with other countries on nuclear waste disposal issues, including Japan, Switzerland, and Sweden. It has established the Center for International Radioactive Waste Studies, the main purpose of which is to foster relationships with other countries to promote the exchange of ideas and research results.

The Yucca Mountain Site is located about 120 km northwest of Las Vegas in a semi-arid region. The potential repository will be located about 350 m below the surface within a thick unsaturated zone (UZ). The subsurface rocks at Yucca Mountain consist primarily of fractured volcanic tuffs that vary in degree of welding. To date, a total of 60 deep surface boreholes have been drilled in the area. In addition, an 8-km-long underground tunnel, the Exploratory Studies Facility (ESF), was completed in 1996 at Yucca Mountain.

Berkeley Lab's work at Yucca Mountain consists of solving many ground-breaking problems related to mul-

tiphase, nonisothermal flow and transport through the UZ. Some of the key questions Laboratory scientists are addressing include:

- How much water percolates through the UZ to the repository horizon at Yucca Mountain?
- What fraction of water flows in fractures and how much flows through the matrix blocks?
- How much of this water will seep into the waste canister emplacement drifts?
- How will water containing radionuclides migrate from the repository to the water table?
- Where are the main source areas for water containing radionuclides that recharge into the underlying saturated zone?

Three main groups within the Department — Ambient Testing, Thermal Testing, and Modeling — are addressing these questions, with support from geophysical studies.

AMBIENT TESTING GROUP

The Ambient Testing group investigates how water flows through the mountain and how much of this water will seep into the emplacement drifts. The group is currently performing various tests within the ESF, including

the fracture/matrix interaction test, the drift-to-drift test, the Paint Brush Unit test (PTn test), and the niche testing. The fracture/matrix interaction test is a relatively small-scale (a few meters) test that focuses on the components of water flow in fractures and matrix blocks and the interaction between the two continua. The drift-to-drift test addresses the same issues, but on a much larger and spatial scale (10–20 m). The test in the Paint Brush Unit, an unwelded tuff unit, addresses issues of episodic flow, effects of faults and large-scale features, and lateral continuity of flow and transport. This unit, being above the potential repository, is key to dispersing fracture flow from the above fractured units and buffering the transient behavior of episodic flow. The niche studies address perhaps the most crucial problem of Yucca Mountain, i.e., determining the fraction of water that will flow into the emplacement drifts. This fraction is critical as it affects the rate of dissolution of the waste, the thermodynamic conditions near the waste, and thus the corrosion rates of waste packages and rate of transport out of the waste emplacement drifts. The niche studies are carried out by introducing water into boreholes above the opening and measuring what fraction actually seeps into the opening. Results to date suggest that a small fraction of the prevailing percolation flux will enter the drifts; these results have been verified by comprehensive modeling studies.

THERMAL TESTING GROUP

The Thermal Testing group works in collaboration with other national laboratories to evaluate the effects of heat on thermodynamic conditions, fluid flow and transport, and permanent property changes at and near the emplacement drifts. The Yucca Mountain Project has completed the first large-scale heater test, called the Single Heater Test. The project is now conducting a larger-scale heater test in a drift over 80-m long. This second heater test is intended to resemble the actual in-place conditions when the high-level radionuclide waste is placed in the emplacement drifts. Berkeley Lab's role in the heater tests is to characterize the heater test area prior to testing; monitor potential changes in fracture and matrix saturations through air injections, tracer testing, and ground-penetrating radar measurements; and perform predictive thermo-hydrological and thermo-hydrochemical calculations. The initial characterizations of the heater test areas were performed with air-injection tests that yield the 3-D permeability structure of the fracture network. Continued air-injection testing during the heating and cooling phases of the heater test yielded changes that can be attributed to changes in fracture saturations or mechanical effects. Cross-hole radar tomography has also yielded very promising results regarding change in global saturations of the system due to heaters. Detailed 3-D

thermo-hydrologic and thermo-hydrochemical calculations were used to predict the behavior of the test. These will be refined to better fit observations as the test progresses. Finally, Laboratory scientists are involved with measurements of the isotopic compositions of condensate water that have seeped into the boreholes.

MODELING GROUP

Berkeley Lab has the primary responsibility for the development of the UZ flow and transport model. This is a very comprehensive 3D, dual-permeability, numerical model that represents the entire UZ at and near Yucca Mountain. The model is intended to integrate in a single computational framework all of the relevant geological, hydrological, geochemical, and other observations that have been made at the surface, in boreholes, and in tunnels at Yucca Mountain. The model is calibrated against pneumatic moisture tension, matrix potential, temperature, geochemical, perched water, and other data from the UZ. The model is then used to predict all of these variables in new boreholes and new drifts to be drilled. The degree of agreement between the model predictions and the subsequent observations give a measure of the reliability of the model, and direction to which additional data need to be collected and incorporated. A very important sub-model of the UZ model is the drift-scale model, which is on a tens-of-meters scale, versus the UZ model's hundreds-of-thousands-of-meters scale. The drift-scale model, in a similar fashion as in the UZ model, predicts the results of the niche tests, and then is modified to match the actual observations. As the *in-situ* testing seepage can only be achieved at much higher rates than the current estimated percolation flux rates, the drift-scale model must be relied upon to accurately calculated seepage into drifts under those different conditions. In addition, the drift-scale model forms the basis for sensitivity studies of the impact on seepage rates from various important fracture and matrix parameters. Both the UZ and the drift-scale models are key process models for Total System Performance Assessment (TSPA), and performance of the potential repository is only as reliable as these two key models.

FUNDING

The Nuclear Waste Department's Yucca Mountain Project research is supported by the Director, Office of Civilian Radioactive Waste Management (through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project), of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Center for International Collaboration in Nuclear Waste Management Programs

RESEARCH OBJECTIVES

The objective of the Berkeley Lab International Center is to provide unique support to DOE's Office of Civilian Radioactive Waste

Management initiatives in high-level waste disposal by bringing to bear knowledge gained by programs in other countries toward problems faced at Yucca Mountain. The primary goals of sustained international collaboration are to respond to national technical needs in radioactive waste disposal, to share information and maintain communication, and to affect technology transfer and advancement.

APPROACH

The Berkeley Lab International Center provides one means of preserving communication between the U.S. and the international radioactive waste management community. Through its library and database, the Center provides updated information on radioactive waste programs and research in other countries. This can serve to link American scientists in the nuclear waste community with those abroad who have common interests and may serve as a springboard for future collaborative activities. The International Center provides an annual update of developments in radioactive waste management around the world (Simmons, 1998) and produces timely fact sheets on particular subjects at the request of DOE. The International Center has also brought speakers and visiting scholars from Russia, France, and Japan to work with Berkeley Lab scientists on problems related to radioactive waste management and associated environmental issues.

RESULTS

A survey performed by the Berkeley Lab International Center has shown that, since 1995, a number of changes have occurred in radioactive waste management programs around the world (Simmons, 1998). Countries with no previously established programs have now drawn up a framework for high-level waste disposal, either because they plan to continue to rely on nuclear energy as a source of electricity (e.g., Taiwan, Indonesia, India) or because, in the case of former Soviet Bloc countries, they

can no longer rely on Russia to reprocess and dispose of spent nuclear fuel. Figure 1 shows countries having radioactive waste management programs.

A. Simmons

Nuclear waste disposal programs have common elements in many countries. However, common to all countries are the following: (1) a policy of ultimate deep geologic disposal as the safest means for ensuring adequate waste isolation; (2) a reliance on both natural and engineered barriers; (3) a recognition of the need for research and development of disposal technologies as well as rigorous screening and characterization of potential disposal sites; (4) recognition of long-term safety as the primary goal of waste isolation and pursuit of a performance assessment approach in demonstrating safety; and (5) regulation of the nuclear waste management program by an independent authority. Most countries plan to store waste for a period of up to fifty years prior to disposal in order to cool it to temperatures below 100°C. Most countries are also examining a number of sites for characterization and will select from among those the site that has the best overall favorable natural features, meets socioeconomic and other criteria, and is accepted by the populace. A number of countries elect to reprocess spent fuel prior to disposal; these include France, Japan, Russia, Germany, and the U.K.

Some high-level waste management programs are more mature than others, with Sweden, Canada, and Switzerland having conducted research in underground laboratories (URLs) for more than a decade. These facilities have afforded the opportunity for multinational collaborative experiments and have allowed countries without a URL of their own to conduct *in-situ* tests. International collaboration provides increased program leverage for small nations that would otherwise not be able to support some activities. Collaboration

also provides the scientific confidence gained by collective buy-in and review. Collaboration occurs through bilateral agreements or under the auspices of multinational organizations such as the Commission of European Communities (CEC), International Atomic Energy Agency (IAEA), and Organization for Economic Cooperation and Development/Nuclear Energy Agency (OECD/NEA).

Figure 1. Map showing countries (shaded) with radioactive waste management programs.

Country	Rock Type	Natural Versus Engineered Barrier Relative Emphasis	Underground Research Laboratory (URL)	Site Selection Status of HLW Repository	HLW Repository Operation Start Date
Belgium	clay	natural barrier; impermeability of clay	in Boom clay at Mol	rock type selected; Mol studied as candidate	2030 or later
Canada	crystalline	multiple barrier	at Whiteshell — in crystalline rock	concept has been reviewed through EIS	No date established
Finland	granite	engineered barrier	research tunnel	four sites being characterized for suitability	2020
France	granite, clay	natural barrier	three sites being considered for URL	only rock types have been selected	2020–2025
Germany	salt; granite as back-up	natural barrier	Asse II Salt Mine; Gorleben Salt dome	Gorleben, 6 other domes as alternatives, also granite	2008 (unlikely)
Japan	granite, sedimentary rocks	multi-barrier	Kamaishi mine; Iono mine; Mizunami City (planned)	rock types selected - area screening to be done	2030–2045
Russia	salt, granite, clay, basalt	multi-barrier	none	planning stages for site selection criteria	indeterminate
Spain	granite, salt, clay	multi-barrier	none	rock types selected - area screening to be done	2020 or after
Sweden	granite	engineered barrier	Aspo Hard Rock Lab	feasibility review of 5 volunteer sites	2010–2020
Switzerland	granite or clay	engineered barrier	Grimseil Pass	potential sites for characterization selected in 1994	after 2020
United States	welded fractured tuff	multi-barrier approach	Yucca Mountain, Nevada	Viability Assessment for potential repository at Yucca Mountain (1998)	2010
United Kingdom	assumed granite	multi-barrier containment system assumed — with total system performance	planning stage at Sellafield was stopped	no active HLW program; program is for LLW	2080–2100 assumed by nuclear industry

Table 1. Status of Radioactive Waste Geologic Disposal Efforts in the U.S. and eleven other countries.

Compared to the eleven countries with mature programs (see Table 1), the U.S. is unique in a number of ways. It is the only country that has a legislatively mandated date for the acceptance and disposal of waste, it has the largest program, it is the only country that is focusing all characterization efforts on a single site (Yucca Mountain, Nevada), and it is the only country with a potential repository in the unsaturated zone. With the exception of the unlikely opening date of 2008 for a German repository, the U.S. starting date for full repository operations is the earliest, by at least a decade. (Sweden plans to open a demonstration repository only in 2008.) Most other nations plan to begin repository operations around 2020, except for the U.K., which does not plan to open a repository for another 60 to 80 years.

SIGNIFICANCE OF FINDINGS

According to the LBNL International Center survey and supporting literature, it is generally accepted that the ability of a country to site a high-level nuclear waste repository will not be entirely based on a well-executed technical program and safe repository design, but instead will be based strongly on societal acceptance. Public opposition to the concept of a permanent repository for radioactive waste is strong in most nations. It has meant the inability to site a low-level waste repository in Switzerland and the United Kingdom and has led Spain to postpone plans for constructing a URL. The degree of opposition has stimulated analyses of the reasons for opposition and a rethinking of approaches in many programs. The role and importance of public information and public participation in developing waste management and disposal strategies and facilities

are recognized and are receiving an increased emphasis, partly because of public opposition and partly due to the fact that where successes have occurred, the public has played a strong role in the process and has endorsed its outcome (e.g., Sweden's low-level waste repository). In many of the countries surveyed by the LBNL International Center, more effort than in the past has been devoted over the last three years to screening sites and providing extensive documentation as to how sites meet favorable criteria prior to conducting actual site characterization. The LBNL International Center will continue to gather and share information as radioactive waste management programs evolve and countries attempt to find common solutions to this global problem.

RELATED PUBLICATIONS

- Simmons, A.M., *Status of International High-Level Radioactive Waste Management Programs*, U.S. Dept. of Energy, Washington, D.C., 1998.
- Witherspoon, P. A. (ed.), *Geological Problems in Radioactive Waste Isolation: Second Worldwide Review*, LBNL-38915, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

FUNDING

This is supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Seismic Imaging of the Paleozoic Basement at Yucca Mountain, Nevada

RESEARCH OBJECTIVES

The structure and depth of the Paleozoic (Pz) basement at Yucca Mountain have important implications for the modeling of fluid flow in the saturated zone, earthquake hazard assessment, and the tectonic history of the region. However, the depth to basement is poorly known since only one borehole, P#1, penetrates the Pz. This well is located about 2,000 ft east of the main drift on a basement high and encounters the basement at a depth of 4,080 ft in the well. In November 1997, a Vertical Seismic Profile (VSP) experiment was carried out at borehole P#1, with the purpose of identifying seismic reflection energy from the top of the Pz interface and imaging it for local structure and faulting around the well. A second objective was to correlate, if possible, the results from the VSP with a previously recorded surface seismic line, REG-3, which extends several thousand feet west-northwest and south-southeast of the well. Such a correlation with a surface seismic line would allow for a more regional interpretation of the Pz.

APPROACH

A standard VSP setup was used with 40-ft spacing of sensors in the well and a Vibroseis surface source. Four different source locations were recorded from 500 to 2,800 ft. Considerable variations in the strength of the Pz reflections were encountered at each site. The best results were obtained at Site 4, located 1,600 ft WNW of the well, and are shown in Figure 1(a) (left). The processed data show a strong reflection at the depth of the Pz in the well (blue is positive amplitude, red is negative amplitude, and the Pz pick is in yellow). The Pz appears nearly flat lying and continuous for nearly 600 ft WNW of the well. The velocity structure obtained from the first arrival times showed a marked increase in seismic velocity at this level, which agrees with the expected velocities of limestones and dolomites that comprise the Pz in this region.

The surface seismic line, REG-3, was recorded along the Site 4 to P#1 azimuth and allowed for a direct comparison to the VSP data. The data from REG-3 were provided as Common Depth Point (CDP) gathers from the U.S. Geological Survey; these traces were binned into gathers that reflect from a common depth location. An examination of the gathers showed the presence of a strong reflection at the correct two-way travel time as seen in the VSP data. To increase the signal-to-noise ratio, only traces with offsets greater than 2,500 ft were used in the stack, since the near-offset traces contained weak incoherent reflected energy. Figure 1(a) (right) shows the stack of these CDP gathers and the resulting reflectors. Again, the Pz can be seen as a strong reflector and appears to have a slight

M. A. Feighner, T. M. Daley, R. Gritto, and
E. L. Majer

westward dip. These results show that the Pz appears as a reflector in both the VSP and surface seismic data and that their locations at depth correlate very well. Next, we extend our interpretation of the Pz away from the well.

RESULTS

The CDP gathers within 2,000 ft of the well were stacked and migrated and are shown in Figure 1(b). The location and dip of faults from the most recent geologic model are shown in green, and the interpreted Pz surface is shown in yellow. From geologic considerations, the Paintbrush Canyon Fault was thought to intersect the well at the depth of the Pz, but the offset was unknown. Our interpretation suggests an offset estimated between 100 and 200 ft. Additionally, the Pz appears to be broken to the ESE with offsets generally within the 200-to-400-ft range. However, west of the Midway Valley Fault, the Pz was difficult to pick up because of possible large offsets of the interface (two possible interpretations are shown as dashed lines). If offsets become greater than one wavelength of the reflection signal (about 750 ft), it is impossible to uniquely identify the Pz without additional well control.

SIGNIFICANCE OF FINDINGS

The major conclusions of this study are:

- (a) Of the four VSP datasets collected at P#1, Site 4 provided one of the best Pz reflections and revealed the Pz to be nearly flat lying and continuous for 600 ft WNW of the well.
- (b) Near vertical reflections of P-wave energy revealed few coherent amplitudes, in both the VSP and surface reflection data.
- (c) The VSP Pz reflection data were matched to the REG-3 seismic line CDP data. The REG-3 data showed a strong coherent reflector at the Pz, but with greater westward dip than the VSP data. The migrated REG-3 data show a possible fault of the Pz at P#1 with a small offset of about 100 to 200 ft. The Pz was traced within 2,000 ft of the well and revealed numerous offsets in the surface with generally westward dipping interfaces. However, interpretation beyond this range proved difficult due to possible large offsets in the Pz interface.
- (d) There is no indication that a large offset exists in the Paleozoic at P#1 (as originally believed, based on the geologic model). A better model for the

Figure 1. (a) Comparison of VSP and surface seismic data at P#1; (b) Interpretation of Pz away from the well (based purely on surface seismic data), with mapped faults from the most recent geologic model.

top of the Pz basement near P#1 is a continuous, slightly westward dipping interface with a slight step across the Paintbrush Canyon Fault at P#1.

RELATED PUBLICATION

Feighner, M. A., T. M. Daley, R. Gritto, and E. L. Majer, Results of VSP analysis in P#1, Yucca Mountain Project Milestone, SP3B6AM4, LBNL-41799, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, Through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Seismic Reflectivity of Layered Volcanic Tuffs at Yucca Mountain, Nevada

T. M. Daley, M. A. Feighner,
and E. L. Majer

RESEARCH OBJECTIVES

Yucca Mountain is the site currently being studied for potential use as a high-level nuclear waste repository. The Yucca Mountain area is typical of many volcanic regions in that it is very heterogeneous and structurally complex. The general nature of the volcanics (alternating flow properties in vertical and horizontal directions) causes many geophysical anomalies. Faulting complicates the geophysical signature within the thick section of partially saturated tuff overlying the area. Geophysical techniques such as seismic reflection profiling offer the prospect of imaging the heterogeneities that are important to fluid flow in the unsaturated tuffs of Yucca Mountain.

APPROACH

In August of 1993 a relatively small program was initiated by Berkeley Lab at the direction of the Department of Energy/Yucca Mountain Site Characterization Project Office (DOE/YMSCO) to evaluate the use of high-resolution geophysics for the detection and mapping of lithology, structure, faults, and fractures in the potential repository area at Yucca Mountain, Nevada. This initial work involved two Vertical Seismic Profiles (VSP), and the recording of three surface reflection lines. This was also the first attempt at using modern seismic imaging techniques to determine geologic features within the massive tuff flows

of Yucca Mountain. In late 1994, Berkeley Lab embarked on a more ambitious program of utilizing high-resolution seismic imaging using surface reflection and VSP, gravity, electrical (MT), and magnetic methods. This report will feature the results

from the seismic work related to identification of reflecting horizons within the tuff flows of the Tiva Canyon, Topopah Spring, Calico Hills, and Prow Pass formations. The seismic reflection lines sample a variety of geologic conditions and features of interest to the project. Lines YMP-1, 2, 3, 4, 5, and 6 were designed to look at structure, faulting, and lithology in or near the repository block over this depth range. This report will focus on seismic line YMP-5, which is on Yucca Ridge.

RESULTS

The seismic lines were interpreted for four "marker horizons" based on the reflectivity identified in VSP surveys. Figure 1 shows line YMP-5 (a migrated depth section) interpreted for these four reflective horizons.

We believe the pink-colored reflection is associated mainly with the Tptrv, the vitrophyre near the top of the Topopah Spring Tuff. It also may include reflectivity associated with the Tpcpv (the vitric zone near the base of the Tiva Canyon Tuff) and with the thin bedded tuffs between the Tiva Canyon Tuff and the Topopah Spring Tuff. Since we believe the pink marker is associated with the Tpcpv

Figure 1. Seismic line YMP-5 with interpreted marker boundaries and current geologic cross section. The seismic section is a migrated depth section at 1:1 scale. Compared porosity log (if available) for all wells within 1,000 ft. of seismic line is plotted on the geologic cross section.

to Tptrv lithologic section, we also feel it can be a marker for the thermal/mechanical unit PTn. Variation in the reflectivity of the pink horizon may indicate variations in the physical properties of the PTn.

The blue-colored reflection is associated with the lithophysal zones of the Topopah Spring Tuff. There is reflectivity from the upper lithophysal zone (Tptpul), the lower lithophysal zone (Tptpll), and the middle nonlithophysal zone (Tptpmn). We believe that changes in matrix properties, such as number of lithophysae and distribution of lithophysae size, as well as changes in water saturation and total porosity, will cause changes in seismic reflectivity. On some lines, such as YMP-5 and YMP-6, we have interpreted at least two major reflectors within the lithophysal zone and colored them blue.

The orange-colored reflection is associated with the vitrophyre at the base of the Topopah Spring Tuff (Tptpv). This is usually a single coherent reflector. It is identifiable on nearly every seismic line. This is an important reflector since, taken together with the pink marker (the Tptrv), we believe it defines the apparent seismic thickness of the Topopah Spring Tuff. Additionally, the Tptrv to Tptpv section defines the thermal/mechanical units TSw1 and TSw2. Therefore, variation in the reflectivity of this section may be indicating variation in physical properties of the TSw1 and TSw2.

The yellow-colored reflection is the deepest reflector identified, and we believe it is associated with the central portion of Prow Pass. This reflector often appears in a pair with the orange marker.

Using these marker horizons as an interpretive framework, we can now discuss the reflectivity of YMP-5. We display the current 3D geologic model of the repository region along with the interpreted seismic sections (top, Figure 1). It is immediately obvious that the seismic sections look quite different from the geologic model. The seismic data image a very heterogeneous subsurface based on rock properties, while the geologic model is based on laterally continuous lithologic boundaries derived from well information and surface mapping.

The overall seismic character of YMP-5 is one of relatively good reflectivity on the southern and northern ends, with poor reflectivity in the center section (CDPs 540 to 740). The Tptrv (pink) is most reflective on the southern end from CDPs 320 to 560 with a gap from CDP 440 to 480. The lithophysal reflectivity (blue) is fairly strong but typically occurs in short segments. The appearance of two reflectors within the lithophysal zone is seen on other lines and implies reflectivity above and below

the Tptpmn. The Tptpv (orange) and Tcp (yellow) are good reflectors on the southern end from CDPs 240 to 460. Both Tptpv and Tcp have reflectivity on the northern end of line YMP-5 from CDPs 730 to 920 with a maximum continuity of about 40 CDPs (240 m). As on other lines, these two horizons seem to have spatially coincident reflectivity.

In general, the geophysical results indicate that the proposed repository volume at Yucca Mountain is made up of a complex overlapping structure of tuffs that vary in physical properties throughout the repository region on a scale not captured in the current geologic model. We believe this variation in seismic reflectivity is, in large part, due to variation in rock properties. We know that porosity can be a controlling factor for seismic velocity and reflectivity in the rock units being studied. Other properties, such as fracture density and fracture stiffness, lithophysal size and distribution, and degree of welding in vitric zones, may be important factors in seismic reflectivity.

SIGNIFICANCE OF FINDINGS

We have used VSP results from three wells, together with general geologic information, to identify four marker horizons that serve as an interpretive framework of seismic profiling at Yucca Mountain. These marker horizons may be caused by variable thickness zones rather than distinct lithologic boundaries, such as in the lithophysal zones of the Topopah Spring tuff and in the Tpcpv-Tptrv transition.

We have developed an understanding of which lithologic horizons within the Yucca Mountain tuff flows can be imaged and their reflection characteristics. These lithologic horizons are important for bounding the thermo-mechanical units (PTn, and TSw 1 and 2). It follows that if the geophysical data are reflecting material property variations, then they are also imaging heterogeneity in the thermo-mechanical units.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Characterization of Fracture Flow Structure Using Cross-Hole Air Permeability

P. J. Cook and J. S. Wang

RESEARCH OBJECTIVES

As part of the ambient testing program for the Yucca Mountain Project, the unsaturated zone is under investigation to examine the fluid flow and transport characteristics of the fractured tuff. Flow is believed to be confined to the fractures, which means that an understanding of how fracture systems transport fluids is essential to determining how fast and in what quantities fluids will travel through the rock. A combination of size and number of connections between fractures affects the flow. Flow can travel in networks of fractures. A way to determine potential flow paths in a fracture system is to perform air-permeability tests in boreholes drilled into the rock.

APPROACH

Sets of multiple holes intersect the permeable fractures and allow air to be injected into the rock. To allow injection into a specified location along a borehole and monitoring in other boreholes at particular locations, rubber packers are used to isolate sections of the boreholes. A flow controller directs flow into a section. Pressures in the injected location and at all observed locations are measured with pressure transducers. Air flow can be controlled accurately from 0.5 standard liters per minute (SLPM) to 500 SLPM. Pressure transducers usually have a 0–200 kPa range, absolute, with a 0.5 kPa resolution. Typically, a packer system is capable of isolating up to twenty 0.3048-m zones in each borehole at one time. Each zone is isolated from an adjacent one by a 0.3048-m section of

inflatable rubber gland that seals against the borehole wall. To map the entire length of each hole, the packers are moved to new locations once all available isolated sections have been

tested for a given configuration. To enable pressures from all possible flow paths to be monitored, the sealed sections of the boreholes are tested and previously tested zones are sealed by moving the packers 0.3048 m and retesting. A group of up to seven 10-m boreholes is used for each investigation. For each investigation, the boreholes are drilled parallel to each other into the rock, 1 to 2 m apart. Three such investigations have been performed to date in the Exploratory Test Facility of the Yucca Mountain Project.

RESULTS

An immediately usable result from air-permeability testing is a measure of the permeability at each location in the injected borehole. This permeability is calculated using a formula obtained from LeCain, 1995:

$$k = \frac{P_{sc} Q_{sc} \mu \ln\left(\frac{L}{r_w}\right) T_f}{\pi L (P_2^2 - P_1^2) T_{sc}} \quad (1)$$

where k is the permeability, P_{sc} is standard pressure, Q_{sc} is the flow rate, T_{sc} is standard temperature, μ is the dynamic viscosity of air, L is the length of zone, and r_w is the radius of the bore. T_f is the temperature of formation, P_2 is the steady-state pressure, and P_1 is the initial pressure.

Figure 1. Comparison of pre-excitation and post-excitation air permeability from one nearby borehole.

Equation (1) assumes that the air behaves as an ideal gas and is derived for a homogeneous porous medium. The geometry is assumed to be that of a line source in an infinite medium with a zone of influence equal to the zone length. While the fractured tuff under investigation is not a homogeneous or infinite medium, the equation provides a consistent method of obtaining a permeability value for an equivalent homogeneous case and enables comparison of the various test results. A comparison of the different zones and locations is the focus of these tests.

Measurements of the single-hole permeability provide an insight into the permeability structure of the section of rock being examined. Single-hole permeability data from boreholes can be used for planning tests, such as dye-emplacment (Wang et al., 1997), to investigate the flow of liquids in the unsaturated zone. In addition, if the investigated section of rock is to be mined out, the permeability from the single-hole data can be correlated with observed fractures. Tests can be carried out after nearby mining to determine the effect on permeability of stress relief and newly exposed surfaces. Cross-hole data from pressures observed in response zones yield directional information about connections between boreholes due to fractures.

SIGNIFICANCE OF FINDINGS

Figure 1 shows a bar graph comparing pre- and post-mining air permeability from a nearby borehole. The effect of mining on the values can be seen. A calculation incorporating the altered boundary conditions will tell how much of the change is due to stress relief of fractures. Figure 2 shows pressure curves from injection and response zones. Each column of graphs corre-

Figure 2. Injection and response plots for many zones in a cluster of boreholes. The injected zone is marked with a line. The range on the red plot is 70 kPa, and the range on the others is 1.38 kPa.

sponds to a borehole, and each graph represents a monitored or injected zone. The injected zone is marked as such. The pressure responses in some zones are exceptionally large compared to the rest, indicating the existence of discrete flow connections in the rock.

RELATED PUBLICATIONS

Tsang, Y. W., and P. Cook, Ambient characterization of the ESF Drift Scale Test Area by field air permeability measurements, Yucca Mountain Project Level 4 Milestone SP9512M4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

Wang, J., P. Cook, and R. Trautz, Flow tests to quantify seepage into drifts, Presented at the American Geophysical Union, Washington, D.C., 1997.

REFERENCE

LeCain, G. D., Pneumatic testing in 45-degree-inclined boreholes in ash-flow tuff near Superior, Arizona, U.S. Geol. Surv. Water Resour. Invest. Rep. 95-4073, U.S. Geological Survey, Denver, Colo., 1995.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Measurements of Water Potential at the Exploratory Studies Facility, Yucca Mountain, Nevada

R. Salve and J. S. Y. Wang

RESEARCH OBJECTIVES

Borehole clusters and niches provide a framework for studies investigating drift-scale seepage and testing in the Exploratory Studies Facility (ESF) at Yucca Mountain. These studies have been designed to measure *in-situ* permeability and other hydrologic parameters of repository level rock, while attempting to identify drift-scale seepage processes. Typically, a cluster of boreholes installed along the right rib of the main drift of the ESF is monitored to determine water potentials and content. This is followed by a series of tests in which air and water permeabilities are determined at various locations within the cluster of boreholes. A niche is then excavated into which a second cluster of boreholes is cored into the niche wall (Figure 1). *In-situ* measurements of water content and potential in these new boreholes are followed by measurements of air permeability.

The primary objective of this effort was to determine the water potential at various points within three niche sites. To meet this objective a common method to measure water potential, the use of psychrometers, was adapted for borehole application.

APPROACH

Water potential measurements were made with Wescor, Inc., psychrometers (model PST-55) connected to a Campbell Scientific data logger (model CR7). Using the multiplexing capabilities of the data logger, hourly measurements of up to 20 psychrometers were automated. Water potentials were measured either along the length, or at the ends of 3 in. diameter boreholes. Three different types of housing units were used to locate psychrometers in the boreholes. The main feature of the housings was the creation of a small air chamber, which allowed for quick equilibration, and measurements of humidity close to the borehole wall.

RESULTS

Water potential measurements obtained from the three niches are summarized in Table 1.

Niche 1 (Pre-excavation). The water potentials mea-

sured at the ends of the three pre-excavation boreholes (U, B, and M) in Niche 1 were close to saturation values, indicating that the formation is relatively wet approximately 10 m from the main drift in the ESF. Of the three, the end of the middle

borehole appeared to be wettest, with water potentials between 0 and -1 bar. Measurements made along the profile of the upper borehole (between 3.7 and 7.9 m from the collar) ranged between -3.7 and -6.9 bars.

Niche 1 (Post-excavation). In the excavated niche cavity, water potentials were monitored in five boreholes. The monitored locations in borehole A were selected to be 6.25 and 6.75 m from the collar following observations of high neutron counts (suggesting a moist zone). The high water potentials measured at these points (i.e., -0.2 and -3.0 bars, respectively) support these observations. In three of the remaining boreholes (B, D, and E) water potentials measured at depths of 6.0 m varied significantly between boreholes. Here borehole D (-2.5 bars) was wettest followed by B (-4.2 bars), and then E (-7.7 bars). These observations appear to be consistent with those made in the pre-excavation holes that indicated the formation tended to get wetter with increasing distance from the main drift. Measurements made close to the collar in borehole C suggest that there was significant dry-out in the rock surrounding the niches up to a depth of at least 0.15 m, extending possibly to 2.6 m.

Niche 2. Measurements were made at the ends of three 10-m-long boreholes before and after a series of air-permeability tests. Pretest water potential values ranged between -2.4 and -3.8 bars. However, following the test, water potentials in one hole (BR) dropped to between -4.7 and -5.7 bars, while in another hole (BL) the measurements did not show significant changes. Closer

to the borehole collar, readings made between 0.6 and 1.2 m indicate a relatively dry zone, with water potentials between -12.5 and -13.7 bars.

Niche 3. The three sets of observations made in Niche 3 show significant variability within the boreholes in the niche.

Measurements made at the ends of boreholes UL (-1.5 bars) and UM (-8.2 bars) indicate that at a depth of 10 m within a horizontal distance of 1 m there is a steep hydraulic gradient.

Further, observations within borehole UM indicate that there is a prominent dry-out zone associated with the main drift of the ESF.

SIGNIFICANCE OF FINDINGS

These measurements suggest that there is significant variability in water potentials between and within the three niches. One source of the variability can be attributed to the possible drying out of the matrix resulting from ventilation effects along the main drift of the ESF. This is evident from multiple measurements made close to the borehole collars that show increasing water potentials with increasing distances from the collar. A similar dry-out observed close to the collar in borehole C in the Niche 1 cavity indicates ventilation effects are also prominent in enclaves along the main drift. Our data suggest that the extent to which ventilation effects may have penetrated the matrix are possibly greater than 3.0 m.

The second source of variability are formation heterogeneities, which allow zones with high moisture content to develop (i.e., fast flow paths). Our data point to two possible zones that have significantly high water potentials. The first was observed at the end of the middle bore-

hole in Niche 1 (pre-excavation) while the second was detected 6.25 m along borehole A in Niche 1 (post-excavation).

When looked at beyond the ventilation effects of the ESF (i.e., at 10-m depths), Niche 1 appears to be wetter than Niche 2. The data from Niche 3 are too limited to draw any such conclusions. The two measurements made in Niche 3 suggest that there is large variability (-1.5 and -8.5 bars) in the short distance (0.75 m) between the two boreholes.

Our preliminary observations of variability in water potentials between and within niches raise questions on the extent and rate of dry-out associated with ventilation along the main drift, the spatial gradients in water potentials associated with features such as faults, and the effect of air-permeability tests in redistributing moisture within the formation being investigated.

WATER POTENTIAL MEASUREMENTS IN NICHE 1				
Borehole ID	Dist. from collar (m)	Duration of measurement	Temp.	Pressure (bars)
U	10.0	5/9-16/97	23.3	-1.3
U	10.0	5/9-16/97	23.3	-1.3
M	10.0	5/9-16/97	23.3	-0.7
M	10.0	5/9-16/97	23.3	0.0
B	10.0	5/9-16/97	23.2	-1.2
U	6.1	7/8-14/97	24.8	-4.9
U	5.5	7/8-14/97	25.3	-4.6
U	5.5	7/8-14/97	24.9	-3.4
U	4.9	7/8-14/97	25.0	-4.6
U	4.3	7/8-14/97	25.3	-6.8
U	3.7	7/8-14/97	25.5	-6.2
U	7.9	9/16-24/97	24.3	-4.9
U	7.3	9/16-24/97	24.5	-4.6
U	6.7	9/16-24/97	25.3	-7.1
U	6.1	9/16-24/97	24.8	-6.7
U	5.5	9/16-24/97	24.9	-3.6
A	6.25	18/18-21/97	22.9	-0.2
A	6.75	18/18-21/97	23.0	-3.0
B	6.00	18/18-21/97	22.7	-4.3
C	0.15	18/18-21/97	25.8	-13.2
C	0.76	18/18-21/97	25.1	-3.3
C	1.98	18/18-21/97	24.1	-2.2
C	1.98	18/18-21/97	24.1	-4.7
C	1.37	18/18-21/97	24.5	-4.0
C	2.60	18/18-21/97	23.8	-5.7
D	6.00	18/18-21/97	23.9	-2.2
D	6.00	18/18-21/97	23.8	-3.2
E	6.00	18/18-21/97	28.9	-7.5
E	6.00	18/18-21/97	28.9	-8.1
WATER POTENTIAL MEASUREMENTS IN NICHE 2				
UM	1.2	7/1-8/97	26.5	-12.7
UM	0.6	7/1-8/97	26.9	-13.9
UM	0.6	7/1-8/97	26.9	-16.5
BR	10.0	7/1-8/97	23.2	-3.7
BR	10.0	7/1-8/97	23.2	-3.9
BR	10.0	7/1-8/97	23.2	-3.2
BL	10.0	7/1-8/97	23.2	-2.4
BL	10.0	7/1-8/97	23.2	-3.6
ML	10.0	7/1-8/97	23.2	-0.1
ML	10.0	7/24-28/97	23.3	-2.9
ML	10.0	7/24-28/97	23.3	-3.8
ML	10.0	7/24-28/97	23.3	-3.9
BR	10.0	7/24-28/97	23.3	-5.8
BR	10.0	7/24-28/97	23.3	-4.9
BR	10.0	7/24-28/97	23.3	-4.8
BL	10.0	7/24-28/97	23.3	-2.1
BL	10.0	7/24-28/97	23.3	-1.5
BL	10.0	7/24-28/97	23.3	-2.8
WATER POTENTIAL MEASUREMENTS IN NICHE 3				
UM	0.5	12/22/97-1/8/98	22.3	-27.3
UM	1.1	12/22/97-1/8/98	24.3	-15.4
UM	1.7	12/22/97-1/8/98	24.9	-8.3
UM	2.9	12/22/97-1/8/98	25.7	-2.8
UL	10.0	12/22/97-1/8/98	25.7	-1.5
ML	10.0	12/22/97-1/8/98	23.7	-8.4

Table 1. Water potential measurements in niche 1.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Hydrologic Monitoring in Unsaturated Fractured Tuff Boreholes

R. Salve, T. Tokunaga, J. S. Y. Wang,
R. Solbau, and J. Clyde

RESEARCH OBJECTIVES

Hydrologic investigations in fractured rock environments can be significantly enhanced if boreholes installed for pneumatic tests and other site characterization purposes are also used to obtain hydraulic measurements. However, the traditional method of using backfill material (like silica sand) in placing instruments in boreholes can severely disturb the natural system. Further, backfilling often results in permanent installation of sensors that cannot then be removed for periodic calibrations. Therefore, while boreholes provide access into the formation, there is a need for instrumentation procedures that eliminate the need for backfilling, while allowing relative ease in locating and removing sensors.

The primary object of this effort was to develop tools for monitoring water potential and content in boreholes. Here the main design concerns were: (i) reduction of uncertainties arising from the use of backfill material, and (ii) installation techniques that allowed for convenient retrieval of sensors for recalibration and relocation.

APPROACH

To meet our objectives we chose two common methods of measuring water potential, i.e., tensiometers and psychrometers, and adapted them for borehole applications. We also fabricated a simple sensor to detect the wetting and drying of the borehole wall in response to a migrating wetting front. To permit efficient sensor installation, we considered the use of several housing and packer designs.

RESULTS

Tensiometers. To address limitations associated with conventional tensiometers (i.e., contact geometry, backfill, etc.) we redesigned the conven-

tional tensiometer such that the porous tip follows the shape of the borehole wall and contacts the wall directly, thereby greatly increasing the sensing area without increasing the storage volume. This design eliminates the need for fill material, allowing

the sensor to directly equilibrate with the environment along the boreholes oriented at any angle. To obtain good hydraulic contact between the tensiometers and the borehole wall, the tensiometers are pushed against the borehole walls with air-inflatable bladders (Figure 1). To relocate the unit, the bladders and packers are deflated such that tensiometer surfaces are pulled away from borehole walls.

Psychrometer Housing. We designed three housing units for psychrometers. The main feature in these units was a small air chamber that allowed for quick equilibration and measurements of humidity close to the borehole wall. Each unit was developed to serve a specific application.

i. Single Packer Assembly.

This design is used to measure potentials at the end of a borehole. The unit is comprised of a single rubber packer through which conduits carry wires for multiple psychrometers [Figure 2(a)].

ii. Multiple Packer Assembly.

This design is used to measure potentials simultaneously in multiple locations within a single borehole. It is comprised of six 0.3-m-long packers, each enclosing five 0.3-m cavities [Figure 2(b)].

iii. The Borehole Tensiometer-Psychrometer Assembly (BTPA). The BTPA was developed for applications where there is enough uncertainty on matrix saturation such that preliminary information is required on whether potentials along borehole walls are within the range of tensiometers (i.e., > -0.8 bars) or psychrometers. It

Figure 1

Figure 2

Figure 1. Borehole tensiometers. Figure 2. (A) Single packer assembly, (B) multiple packer assembly, and (C) borehole tensiometer-psychrometer assembly.

consists of two tensiometers and two psychrometers housed in a packer unit [Figure 2(c)].

SIGNIFICANCE OF FINDINGS

We have explored the use of various sensor designs for instrumenting boreholes to obtain hydraulic measurements in the ESF at Yucca Mountain. We have exploited the simple geometry of boreholes to accommodate modifications to various conventional tools used to monitor the migration of a wetting front along borehole walls. Further, we have designed a system that permits quick installation and removal of sensors, thereby making multiple measure-

ments with the same array of instruments convenient, while reducing measurement errors associated with back-fill and infrequent calibrations.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Numerical Modeling of Water Migration in Fracture-Matrix Systems

S. Finsterle, A. L. James,
and J. S. Y. Wang

RESEARCH OBJECTIVES

Modeling flow of water in fractured, unsaturated tuffs at Yucca Mountain, Nevada, is essential for assessing the performance of the proposed high-level nuclear waste repository. Of particular interest is the prediction of water seepage into underground openings, because the seepage rate is a key factor determining waste mobilization and migration from the repository emplacement drifts.

A 5-m-diameter drift is currently being excavated at Yucca Mountain for enhanced characterization of the repository block. A plume of water used during the construction of this Cross Drift is expected to migrate through the fractured tuffs, potentially seeping into the Exploratory Studies Facility (ESF) beneath it at the cross-over point of the two tunnels. Predicting and monitoring the migration of a construction-water plume may provide information on flow of water in an unsaturated fracture network. Amount of water released, permeability of the fractured formation, continuity of the fracture network, and imbibition into the matrix blocks are all expected to be sensitive parameters, affecting penetration depth, migration velocity, and flow patterns of the construction-water plume.

The objective of this modeling study is to qualitatively understand construction-water migration in a densely fractured porous medium and the interaction between fractures and adjacent matrix blocks. Furthermore, we would like to predict seepage into the ESF, taking into account capillary barrier and ventilation effects.

APPROACH

In order to gain confidence in predictive modeling of plume migration,

numerical simulations were compared to tracer concentration data from cores showing evidence of construction water in the matrix at depths below the ESF. A two-dimensional, vertical model with the invert of the ESF at the upper boundary was

developed, and multiple interacting continua were specified to appropriately resolve the pressure and saturation gradients between the fractures and the matrix. A random permeability field was imposed on the fracture continuum, representing spatial heterogeneities such as asperities, fracture network discontinuities, and high-permeability flow channels. A pulse of water was released at the top of the model, and saturation changes in both the fracture and matrix continua were calculated using the ITOUGH2 model (Finsterle, 1997).

In a second series of simulations, construction-water losses from the Cross Drift were modeled. The model contained two hydrogeologic layers of different fracture frequencies, as well as the ESF Main Drift 17.5 m below the Cross Drift. Furthermore, the dry-out zone, developed around the ESF as a result of drift ventilation, was

taken into account, along with the capillary barrier effects, which divert parts of the construction-water plume around the opening.

RESULTS

A pulse of water released from a drift migrates quickly through the fractures to great depths, assuming that the fracture network is continuous. The amount of water imbibing into the matrix, providing the construction-water signals observed in the data, depends on fracture density, but is generally limited due to low matrix permeabilities and the relatively fast bypassing of the plume. Increased matrix saturations are

Figure 1. Simulated saturation changes in fracture and matrix continuum 10 days after construction-water release.

Figure 2. Saturation distribution in fracture continuum, illustrating construction-water migration from the Cross Drift to the ESF.

related to low-permeability obstacles in the fracture continuum, which increase the residence time, allowing water to imbibe into the matrix. Figure 1 shows the change in fracture (left) and matrix (right) saturation 10 days after construction-water release. The pattern seen in the matrix continuum is qualitatively comparable to observed tracer profiles.

Figure 2 shows the simulation results of the drift-to-drift construction-water migration. The saturation distribution in the fracture continuum reflects the fast travel times, the impact of the contact between higher and lower permeability layers, as well as the ventilation and capillary barrier effects in the vicinity of the ESF. Seepage into the ESF was determined to strongly depend on construction-water release rates, fracture permeability, and fracture capillarity. Imbibition into the matrix only becomes important if fracture permeabilities are relatively low. The simulation results are discussed in more detail in Finsterle et al. (1998).

SIGNIFICANCE OF FINDINGS

The simulations show that relatively large pulses of water may migrate fast and to great depths within a porous medium that exhibits a continuous fracture network of moderate to high density. The actual penetration depth of construction water released from a drift is poorly reflected in tracer data obtained from the matrix. Moreover, the latter seem to reflect heterogeneities in the fracture continuum rather than the matrix.

The timing and amount of seepage into an underground opening are difficult to predict under transient flow conditions. They depend on geometrical and hydrogeological properties that are complex and hard to characterize. Monitoring seepage in the ESF as the Cross Drift passes provides a unique opportunity to improve our understanding of unsaturated flow in a fractured system.

RELATED PUBLICATIONS

- Finsterle, S., ITOUGH2 command reference, Version 3.1, LBNL-40041, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Finsterle, S., A. L. James, J. S. Y. Wang, J. T. Fabryka-Martin, L. E. Wolfsberg, A. Flint, and W. R. Guertel, Model prediction of local plume migration from the Cross Drift, Yucca Mountain Project Milestone, SP33S3M4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Modeling of Seepage into Drifts

RESEARCH OBJECTIVES

Crucial for the performance of underground nuclear waste repositories is the amount of water seeping into the waste emplacement drifts. Water contacting the waste canisters can significantly enhance their corrosion rate. The objective of this study is to predict the rate of water flowing into drifts at the potential repository site at Yucca Mountain, Nevada, as a basis for assessing the long-term performance of the repository. This undertaking is particularly complicated as the designated site is located in thick, partially saturated, fractured tuff formations approximately 200 m above the water table. The emplacement drifts will act as capillary barriers for the unsaturated flow, ideally diverting water around them, if the capillary forces are stronger than gravity and viscous forces. Seepage of water into the drifts will only be possible if the hydraulic pressure in the rock close to the drift walls increases to positive values; i.e., the flow field becomes locally saturated.

APPROACH

A numerical methodology was developed and applied to study the potential rate of seepage into underground cavities that are embedded in variably saturated heterogeneous fractured rock. The fractured rock mass is modeled as a stochastic continuum where the fracture permeability varies by several orders of magnitude. Three different realizations of random fracture permeability fields are generated, with the random permeability structure based on extensive fracture mapping, borehole video analysis, and *in-situ* air-injection tests. A three-dimensional model is used to represent the heterogeneous steady-state flow field around the drift, with the drift geometry explicitly accounted for within the numerical discretization grid. A variety of flow scenarios are considered, assuming present-day and possible future climate conditions at Yucca Mountain.

J. Birkholzer, G. Li,
C.-F. Tsang, and Y. Tsang

RESULTS

For the conditions at Yucca Mountain, the heterogeneity of the flow domain is a key factor controlling the rate of seepage into drifts. Figure 1 shows a typical flow field in the vicinity of the drift, presenting saturation contours in three horizontal slices of the 3D model domain. A future climate scenario is assumed where the percolation flux through the mountain (i.e., the amount of water flowing with gravity from the ground surface through the vadose zone to the deep water table) is approximately 200 mm/yr. In the horizontal plane just above the drift (middle horizontal slice), liquid accumulates at the drift crown as the vertical gravity-driven flow is diverted around it, while in the horizontal plane below the drift a low-saturation shadow develops. In addition to this flow perturbation effect, the saturation contours reflect the heterogeneity of the model area, showing several locations where "channelized" flow accumulates, creating high saturation values dependent on local permeability contrasts. In fact, at some of these locations, the saturation reaches unity, representing a local ponding condition. Obviously, the probability for local ponding is highest near the stagnation point at the drift crown. Eventually, seepage into the drift occurs when a local ponding condition is encountered in a grid element adjacent to the drift wall.

Various flow scenarios have been analyzed, with percolation fluxes ranging from 5 mm/yr to 1,000 mm/yr. Figure 2 summarizes the results of these simulation runs for the three realizations considered. It gives the total seepage flux into the drift as a function of the inflow at the top boundary of the model. The seepage flux is expressed as a percentage of the percolation flux over an area corresponding to the vertical shadow of the drift. Our simulation results indicate that water drips into the drifts are likely to occur when steady-state percolation fluxes through the unsaturated zone at Yucca Mountain are higher than

Figure 1. Saturation contours for a percolation flux of 200 mm/yr.

Figure 2. Relative seepage rate for three realizations of random permeability fields. Only those simulation runs are presented where seepage into the drift occurs.

approximately 20 mm/yr. Thus, for future climate conditions with higher infiltration than the present state, drifts at Yucca Mountain will be vulnerable for water to enter. In comparison to results obtained for a homogeneous flow field, the seepage threshold fluxes are about an order of magnitude smaller, indicating the important effect of heterogeneity giving rise to local saturation variations. The rate of seepage is correlated to the assumed percolation scenario, i.e., the higher the percolation flux, the more significant will be the amount of water dripping into the opening. Other important factors are the degree of heterogeneity, the formation properties, and the size and shape of the drifts.

Note that the probability of seepage is strongly dependent on details of the local heterogeneity around the drift walls. Therefore, the variation between different realizations of stochastic fields can be significant. Particularly for small percolation fluxes where seepage locations along the drifts are sparsely distributed, the model domain size might not be sufficient to guarantee a large enough statistical sample. Ultimately, an analytical stochastic relationship would be very useful to estimate the potential rate of seepage as a function of different key parameters.

SIGNIFICANCE OF FINDINGS

The seepage rates derived in our numerical study are an important parameter for evaluating the long-term performance of the potential nuclear waste repository at Yucca Mountain. For example, the future corrosion rate of the waste canisters cannot be calculated without reasonable estimates for the amount and location of water contacting them. The conceptual framework developed here can also be useful in a variety of other hydrogeologic and engineering applications.

RELATED PUBLICATION

Birkholzer, J., G. Li, C.-F. Tsang, and Y. T. Tsang, Modeling studies and analysis of seepage into drifts at Yucca Mountain, *J. Contam. Hydrol.*, accepted.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Simultaneous Inversion of Air-Injection Tests in Fractured Unsaturated Tuff at Yucca Mountain, Nevada

K. Huang, Y. W. Tsang,
and G. S. Bodvarsson

RESEARCH OBJECTIVES

Fluid flow in fractured rocks is often very complex and focuses in a few fractures. The complexity of fluid flow in fractured rocks is mainly due to the complex geometry of fault patterns where superimposed structures of fractures on different scales may all contribute to the overall flow. If the density of fractures is large enough for the rock to be approximated as a continuum, then the subsurface heterogeneity is usually represented by spatially variable permeability distribution.

This paper presents numerical simulations of pressure responses to 21 air-injection tests in a rock block situated within the highly fractured welded tuff formation at Yucca Mountain, Nevada. Local permeabilities were estimated by simultaneously fitting the numerical solutions with the measured data of pressure changes from all 21 tests. Hence, our objective is to arrive at a detailed three-dimensional permeability distribution for the test block.

APPROACH

The test block, $13 \times 21.5 \times 18 \text{ m}^3$, resides in the densely fractured nonlithophysal stratigraphic unit. The test block is bounded by drifts at the north, south, and west sides, which are 5-m high, and form the open boundaries. There are 30 boreholes in this block, horizontal or angled, originating from the three drift walls, ranging in length from 5 to 8 m, and all being 7.4 cm in diameter. Rock outcrops on the walls of drifts show that some areas have dense fracture distribution, while other areas remain intact. Borehole videos also indicate differing degrees of fracturing in localized zones within each borehole. Therefore, it can be expected that the local permeability is highly spatially variable.

The test block is the site of an *in-situ* thermal test. A large number of air-injection tests have been carried out in packed-off boreholes in this test block as preheat characterization for the fracture permeability. A typical test consists of injecting air at a constant flow rate in one

chosen borehole, while the pressure response in this and all other boreholes is monitored. After the system has been completely recovered, a new test is started at another borehole. In total, 21 injection tests have been conducted at different boreholes. Since pressure responses in all boreholes were monitored, there were 30 sets of pressure data for each injection test. We intend to simultaneously fit the observed pressure changes for all 21 tests with numerically simulated results and consequently obtain a permeability structure of the test block.

The solution domain is discretized into $34 \times 26 \times 24$ hexahedral elements, with spacing from 0.25 to 1.00 m. Numerical modeling for flow and transport induced by slug test or injection test in boreholes often neglects the borehole volume. Because the ratio of the borehole volume to the volume of some rock elements is about 1/5 to 1/3 (which is significant), in this study each borehole is explicitly discretized into several elements, and a large permeability has been assigned to the borehole elements.

There are a number of alternative modeling concepts proposed to characterize the flow and transport in fractured media. A densely fractured medium with well connected fractures may be treated as a porous continuum, with higher permeabilities for the fracture zones and lower ones for the matrix. That a continuum approach is appropriate for this study can be shown by two facts: (1) fracture mapping of the test block and borehole video indicate that the fractures in this tuff block are relatively

Figure 1. Simulated and measured pressure changes at the injection boreholes.

Figure 2. Estimated 3D permeability distribution of the test block.

densely distributed; (2) interference pressure response is observed in all monitored zones for each air-injection test, which indicates that the fractures are well connected. The numerical code TOUGH2 was applied to simulate the pressure responses of the air injection tests.

RESULTS

Through extensive trial-and-error efforts to adjust the local permeability values, the "best" simulated results were obtained. Figure 1 shows the comparison of the simulated pressure changes with measured data for the injection boreholes. It can be seen that simulated results and the observed data agree very well for all the injection tests. The excellent match between the calculated and measured pressures applies to both magnitudes and the transient time evolution. For a closer view, we have also examined the simulated results for some individual injection tests and compared the calculated pressure increases in the observation boreholes with the measured data. In all 21 tests, the measured and simulated pressure changes agree well for most observation boreholes. In general, pressure change in the injection hole quickly reaches steady state with minimal well storage effect under the constant rate injection. Interference pressure response in the observation boreholes is also rapid, suggesting a good connecting among the boreholes through the fractures. These facts also may affirm the validity of a continuum conceptualization of the fractures.

A set of local permeabilities was obtained after a best-fitting between the calculated and simulated pressure changes. Although an inversion problem is intrinsically nonunique, the quantity of data provides a tight constraint on the inversion. The 3D permeability distribution map (Figure 2) shows that the test block is highly heterogeneous, with the permeability varying from 10^{-15} to

10^{-10} m^2 . The permeability structure is such that the lower part of the block is generally more permeable than the upper part. The south side of the block is relatively more permeable than the north side. The center part is perhaps the most permeable in this block.

SIGNIFICANCE OF FINDINGS

Results from this experimental and numerical study suggest that: (1) pressure data from air injection test boreholes are very useful for estimating rock permeability and determining the connectivity of fractured rocks; (2) for densely fractured rock, the continuum model may be adequate to simulate the flow and transport without needing to take into account channeling of flow through discrete fractures.

RELATED PUBLICATIONS

Tsang, Y. W., C.-F. Tsang, F. V. Hale, and B. Dverstorp, Tracer transport in a stochastic continuum model of fractured media, *Water Resour. Res.*, 32(10), 3077-3092, 1996.

Tsang, Y. W., and J. T. Birkholzer, Multi-phase thermalhydrological processes in the single heater tests at Yucca Mountain, *J. Contaminant Hydrol.*, accepted.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through memorandum purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Thermohydrological Laboratory

RESEARCH OBJECTIVES

Understanding fluid flow behavior in fractured rock is important for the disposal of radioactive waste. High-level nuclear wastes are hot and will continue to generate heat for some time. This heat will boil water present in the pores in the rock (even in the arid Nevada desert, rock pore spaces may be 90% water filled), generating water vapor that will move primarily in the fractures to cooler rock, where it will condense. The condensate will flow downwards, and if it flows back through the fracture network towards the emplaced waste, it may ultimately provide a pathway for radionuclides to the environment.

Our objective is to visually observe flow phenomena in fractures in the vicinity of boiling-temperature regions and to evaluate the importance of these phenomena for nuclear waste disposal.

APPROACH

Fluid flow in fractures can be directly observed in fracture analog models made with at least one transparent side. In this work, a variety of fracture analog models were fabricated using sandblasted glass, epoxy casts of natural rock fractures, and a rock fracture face that was mated to its corresponding epoxy replica face. Heat was applied to the fractures in various ways, such as partially submerging sealed models in a controlled temperature bath, or applying heated water to disks mounted to the glass fracture walls. In the rock-replica experiment, the rock was heated prior to placing the replica face. Pentane, a volatile organic liquid at room temperature, was chosen as the working fluid because it wets glass, epoxy, and rock in the same way that water wets rock, and it boils at about 36.1°C, making the experimental setup much easier. Pentane has a lower viscosity and enthalpy of vaporization than water, which allows for upward scaling of results. Pentane was introduced into the apertures under appropriate thermal conditions and observations were made. To gain additional

Tests: Visualizing Flow Processes with Boiling in Fractures

T. J. Kneafsey and K. Pruess

insights, an infrared camera was used in some experiments to monitor the temperature distribution in the exposed part of the fracture models.

RESULTS

Upon introduction into the models, pentane seeped downward, influenced by gravity, viscosity, and capillarity. When the liquid reached the warmed region, near or above the boiling point, enhanced evaporation occurred, and vapor condensed in the cooler region forming a condensation halo. In the condensation halo, pentane traveled downward in films along the fracture wall and towards saturated islands (Figure 1) where liquid saturated (spanned) the aperture. When additional liquid was added to liquid islands, either by flow or condensation, destabilizing gravitational forces exceeded the stabilizing capillary forces, resulting in intermittent downflow. These events often contacted and destabilized other saturated islands, adding volume to the flow and causing deeper finger penetration into the heated region.

Fingers and films penetrated into regions hotter than the liquid boiling point, with the depth of penetration decreasing as heat transfer increased. Liquid flowed in films along the fracture walls when the flow rate was low or the aperture large. At larger flow rates, liquid flowed in continuous or intermittent rivulets. Very narrow apertures inhibited flow so that only short fingers could penetrate into the warmed region. Flow focused by capillary or emplaced barriers divided seepage through the models, resulting in longer fingers at the outlet of the barriers.

In some fingers in the boiling region, liquid became superheated and then evaporated spontaneously and rapidly. These somewhat violent rapid evaporation events (REEs) were frequently observed in the experiments, expelling liquid droplets and generating large volumes of vapor that temporarily disturbed liquid flow paths in the warmed region and condensation halo.

In many cases, temperature monitoring with the infrared

Figure 1. Fracture model partially submerged in warm bath at 42°C.

camera showed low temperature gradients, indicative of heat-pipe conditions (liquid-vapor counterflow). Heat pipes developed when areally extensive boiling and condensation regions were available, when liquid flowed into the boiling region at an adequate rate, and when apertures were large enough to permit liquid and vapor to flow past each other.

SIGNIFICANCE OF FINDINGS

Continuous rivulet flow, intermittent rivulet (and drop) flow, thread forming and snapping, fingering, and film flow were observed in the fracture models. Liquid is not excluded from regions that are heated above the nominal boiling point. Fingers resulting from intermittent and continuous rivulets penetrated deeper into the heated region than films did, and thus may be of more significance for waste isolation. Film flow on rough surfaces occurred when the aperture was large. Film flow may be the slowest of the three mechanisms observed, but may dominate under low flow conditions.

Heat pipes may be accompanied by enhanced rock dissolution within the condensation halo and enhanced precipitation within the boiling region. These two effects may modify liquid flow paths.

Rapid evaporation events may alter nearby water flow paths. This may cause dripping that would not occur

under stable conditions. Rapid evaporation events in fractures intersecting a cavity where waste is stored may disperse liquid droplets and dissolved salts, which may impact corrosion of the protective waste package containers.

RELATED PUBLICATIONS

Kneafsey, T. J., and K. Pruess, Laboratory experiments on heat-driven two-phase flows in natural and artificial rock fractures, *Water Resour. Res.*, accepted.

Kneafsey, T. J., and K. Pruess, Preferential flow paths and heat pipes: results from laboratory experiments on heat-driven flow in natural and artificial rock fractures, LBNL-40467, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Lessons Learned from the Single Heater Test at Yucca Mountain, Nevada

Y. W. Tsang, J. T. Birkholzer,
and B. Freifeld

RESEARCH OBJECTIVES

The Single Heater Test (SHT) is one of two *in-situ* thermal tests included in the site characterization program for the proposed underground nuclear waste repository at Yucca Mountain. The thermal tests are being carried out in the Topopah Springs welded tuff formation in the Exploratory Studies Facility (ESF) at Yucca Mountain. The primary objective of the thermal tests is to develop a better understanding of the coupled thermal, mechanical, hydrological, and chemical processes likely to exist in the unsaturated fractured rock mass surrounding the repository.

APPROACH

The Single Heater Test (SHT) consists of a 5-m-long, nominal 4 kW heating element, horizontally emplaced among 30 instrumental boreholes, which span a rock block of approximately 13 m $\times$ 10 m $\times$ 13 m in a side alcove in the ESF. Temperature, gas pressure, humidity, and mechanical displacement of the rock are monitored on at least an hourly basis by 530 sensors installed in numerous instrumental boreholes. Figure 1 shows schematically the layout of boreholes grouped according to their different functions. The heater hole is collared on the "Thermomechanical Alcove" wall, oriented W-E (y axis) at 2 m above the drift floor. While many boreholes housing thermal and mechanical sensors are drilled parallel to the heater hole, the hydrological holes are all orthogonal to the heater hole. These holes are designed to probe the moisture redistribution in the SHT block by neutron logging, electrical resistivity tomography, cross-hole radar tomography, and air-permeability tests. This active testing was carried out periodically throughout the SHT, both during the heating phase from August 26, 1996, to May 28, 1997; and during the cooling phase from May 28, 1997, to January 1998. This document summarizes the understanding of the thermohydrological response of the SHT on the basis of simulations

and comparison to measured data.

Modeling of the SHT (Birkholzer and Tsang, 1996; Tsang and Birkholzer, 1997) was carried out using the numerical simulator TOUGH2 for simulating multidimensional coupled

transport of water, vapor, air, and heat in heterogeneous porous and fractured media. The welded tuff in which the SHT was conducted is conceptualized as a dual continuum, composed of a matrix continuum with low permeability, and a fracture continuum with permeability several orders of magnitude higher. Fracture permeability values were assigned based on pretest air-permeability tests in the SHT block. Property values for the matrix continuum — including grain density, matrix liquid saturation, thermal conductivity, thermal expansion coefficient, and heat capacity — were determined from laboratory measurements of cores from the SHT block. Where matrix data specific to the SHT block were not available, measured values for cores from the same stratigraphic unit were used. The 3D computational domain is partitioned into about 30,000 gridblocks, and the alcove geometry is explicitly modeled. Fine gridding and radial symmetry are used around the heater hole to account for the heater geometry, and sharp gradients of temperature, saturation, and pressure. The grid is then converted gradually to Cartesian symmetry in order to better represent the boundaries of the drift and alcove walls.

RESULTS

The key processes involved in the thermal-hydrological response of the unsaturated fractured tuff to heat are as follows. As formation temperature approaches 100°C around the heater, matrix pore water boils and vaporizes. Most of the vapor generated moves into the fractures, where it becomes highly mobile and is driven with gas pressure gradient away from the heat source. When the vapor encounters cooler rock, it condenses, and the local fracture saturation builds up.

Figure 1. Schematic of borehole configuration of the Single Heater Test. The heater is collared on the Thermomechanical Alcove pointing W-E.

Part of the condensate may then imbibe into the matrix, where it is subject to a very strong capillary gradient towards the heat source, giving rise to a reflux of liquid to the dry-out areas. Some fraction of the condensate in the fractures may also flow back towards the boiling zone; however, as capillary forces are relatively weak in the fractures, a substantial amount of liquid may drain by gravity. If the return of moisture back to the heater in liquid phase is less than the outflow of moisture in

vapor phase, the volume near the heat source will become dry. The counterflow of vapor/condensation fluxes is reflected in the "heat-pipe" signature in the temperature data (namely, a small temperature gradient), and with time, the temperature remains at the nominal boiling point.

Temperature monitoring data have been continuously collected in multiple locations, which allows the display of data either as a snapshot or as time evolution at a particular spatial location. Figure 2 shows a snapshot after 3 months of heating. Temperature data from all the boreholes having temperature sensors at the mid-plane of the heater are displayed as a function of radial distance from the heater. The matrix and fracture temperatures from the simulations, represented by solid and dotted line, respectively, are also plotted. The simulated matrix and fracture temperatures are similar except near the nominal boiling point, where the fracture temperature slope shows a plateau. This is indicative of the presence of a region of liquid and vapor counterflow, i.e., the heat pipe effect.

Simulations also show that the drying region centers around 0.8 m from the heater at 3 months of heating, and moves out to about 1.2 m at the end of 9 months of heating. Beyond the drying region is the condensation zone, where the liquid saturation increases from preheat values. The redistribution of the moisture content described by the numerical model is consistent with data from active testing by neutron logging, electrical resistivity tomography, cross-hole radar tomography and air-permeability tests. While most of the liquid resides in the matrix and is monitored by the first three types of active

Figure 2. Measured and simulated temperature at 3 months. Temperatures shown are those in the center plane of the SHT block at $y = 4.5$ m.

testing, air-permeability tests target the liquid saturation in the fractures. Periodic air-permeability tests indicate an increase in the fracture liquid saturation in the "condensation zones" during the SHT heating phase, and a return to preheat values when the heat is turned off.

SIGNIFICANCE OF FINDINGS

The agreement between the data and simulated results indicates that the thermal-hydrological responses of the SHT are well represented by the coupled thermal-hydrological numerical

model. While heat conduction accounts for most of the temperature rise, thermohydrological coupling contributes to the heat transfer by convection, resulting in better agreement between simulations and temperature data. The thermohydrological coupling also accounts for the moisture redistribution seen by the active testing data.

RELATED PUBLICATIONS

Birkholzer, J. T., and Y. W. Tsang, Forecast of thermal-hydrological conditions and air injection test results of the Single Heater Test at Yucca Mountain, LBNL-39789, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

Tsang, Y. W., and J. T. Birkholzer, Interpreting the thermal-hydrological response of the ESF Single Heater Test, Yucca Mountain Site Characterization Project Report Level 4 Milestone SP9267M4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

UZ Flow and Transport Model for Yucca Mountain, Nevada

RESEARCH OBJECTIVES

The U.S. Department of Energy (DOE) is currently investigating the feasibility of using the unsaturated zone (UZ) at Yucca Mountain, Nevada, as a permanent storage facility for the geologic disposal of high-level nuclear waste. As part of the site characterization studies, a 3D site-scale UZ flow and transport model of Yucca Mountain has been developed at Berkeley Lab. The primary objectives of this model are to simulate and investigate the existing natural state of the mountain's hydrogeological system, and to predict possible future system responses in support of the Yucca Mountain Project. The UZ flow and transport model has been constructed to (a) integrate all relevant, available data from the unsaturated zone into a single, comprehensive, 3D model; (b) quantify the flow of moisture, heat, and gas through the unsaturated zone; (c) evaluate the effects of repository thermal loading on moisture, gas, and heat flow within the mountain; and (d) provide a defensible and credible model that describes all relevant unsaturated-zone flow and transport processes at Yucca Mountain. This model does not include radionuclide transport.

APPROACH

The modeling approach is based on a mathematical formulation of coupled multiphase, multicomponent fluid and heat flow through porous and fractured rock, using the TOUGH2 code. Fracture and matrix flow is treated using the dual-permeability modeling approach. The model domain covers a total area of approximately 43 km², and uses the land surface and the water table as its top and bottom boundaries, respectively. In addition, site-specific data, representative surface infiltration, and geothermal conditions are incorporated into the model. The model development consists of the following major steps (Bodvarsson et al., 1997):

- Development of a conceptual hydro-

Y.-S. Wu, G. S. Bodvarsson,
C. F. Ahlers, A. C. Ritcey,
and C. Haukwa

geological model for moisture, gas, and heat flow, and chemical transport processes in the UZ system

- Integration and incorporation of all available field and laboratory data

- Model calibration and sensitivity studies, including both inverse and direct modeling efforts
- Model applications, including predictive studies

Figure 1 presents a summary of the important data collected at Yucca Mountain and various aspects of the conceptual model.

RESULTS

Our understanding of the Yucca Mountain system has improved significantly in recent years through a combination of field studies and modeling efforts conducted using the UZ flow and transport model (Bodvarsson et al., 1997). Data incorporated into the model include liquid saturations for the various geological layers, *in-situ* and core-sample water potentials, saturated hydraulic conductivities and desaturation curves, core-sample bulk property measurements, pneumatic monitoring observations, temperature data, perched water data, air-permeability test results, and geochemical analyses. Data from the Exploratory Studies Facility (ESF) include fracture mapping data, environmental isotopes and hydrochemical data, fracture coating data, and bulk properties from *in-situ* and core-sample measurements.

Incorporation of field data and continued model calibration and verification studies have led to a comprehensive and complex UZ model that represents the important, known flow processes in Yucca Mountain's UZ system. These processes include 3D moisture flow and distribution, capillary effects, fracture/matrix flow and interactions, gas flow, development of perched water zones, lateral flow effects, convective and conductive heat transfer, evaporation and condensation, groundwater/gas travel times, and

Figure 1. Schematic cross section through Yucca Mountain showing various conceptual model data and processes.

transport of conservative and reactive species/tracers.

The UZ model provides the Yucca Mountain project with estimates of important parameters for the total system performance assessment (TSPA) and viability assessment (VA). These parameters include (1) predicted spatial and temporal values of percolation flux in the UZ system; (2) estimated components of fracture and matrix flow at and below the potential repository horizon; and (3) probable flow paths from the land surface to the repository and water table. In addition, the rock properties estimated for the UZ model are used as basic sets of fracture/matrix parameters for other site characterization study activities and repository designs.

TSPA is currently utilizing the full 3D UZ flow model in the 1998 TSPA-VA analyses (Wu et al, 1998) without further abstraction. This step represents significant progress by the project in assessing repository performance, since the results from current modeling efforts with the UZ model provide more realistic representations of the 3D nature of flow within the unsaturated zone and of the relevant processes occurring at Yucca Mountain. In addition, the UZ flow model is used to provide input data/parameters for various other models, such as ambient and thermal drift-scale models, the mountain-scale thermohydrological model, and the UZ transport model used for TSPA-VA.

Other UZ model applications include prediction of ambient conditions at various boreholes and proposed drift locations at the site. These predictions develop scientific confidence in the UZ model, aid in test and construction design, and test model calibration. Percolation fluxes and steady-state initial conditions from the UZ site-scale model are also used by smaller scale modeling studies at Yucca Mountain, such as studies of seepage into waste-emplacement drifts and movement of construction water.

SIGNIFICANCE OF FINDINGS

The UZ flow and transport model developed at Berkeley Lab is a key process model of the UZ system at Yucca Mountain. The model is currently used to characterize the UZ system for TSPA-VA, and it will play a more crucial role for the Yucca Mountain Project as it approaches License Application (LA). The major contributions of the UZ model are summarized as:

- Developing a representative and comprehensive 3D hydrogeological conceptual model for flow and transport processes in the unsaturated zone of Yucca Mountain
- Developing a number of basic parameter sets of fluid flow in fracture, matrix, and faults for the project
- Integrating and incorporating available field data into a single model

- Completing extensive model calibration and sensitivity studies that make the model results consistent with field observations
- Obtaining various understandings of flow and transport processes in the UZ system regarding moisture, gas, and heat flow; tracer transport; fracture-matrix interactions; perched water phenomena; lateral flow and its effects; effects of major faults; estimated percolation flux and fracture-matrix flow components
- Providing TSPA-VA with estimated flow fields under current and future climatic conditions

One key area for future UZ model development is to reduce the uncertainties associated with UZ flow and transport analyses. It is necessary to continue the UZ model calibration efforts to incorporate all the updated field data. As the Yucca Mountain Project moves towards LA, continuous improvements and enhancements to the UZ flow model will be necessary as more new data become available from ongoing field studies at Yucca Mountain, along with the latest results of laboratory analyses of rock and water samples. These new data should enhance the detailed characterization of hydrogeologic formations and may significantly improve our conceptual understanding of how the mountain system works. Furthermore, numerical modeling techniques need to be continuously improved for better model representation of the unsaturated zone, with increasing numerical accuracy, computational efficiency, and reliability.

RELATED PUBLICATIONS

Bodvarsson, G. S., T. M. Bandurraga and Y. S. Wu (eds.), *The Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada, for the Viability Assessment*, Yucca Mountain Site Characterization Project Milestone SP24UFM4, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

Wu, Y. S., A. C. Ritcey, C. F. Ahlers, J. J. Hinds, A. K. Mishra, C. Haukwa, T. M. Bandurraga, H.H. Liu, E. L. Sonnenthal, and G. S. Bodvarsson, 3D UZ site-scale model for abstraction in TSPA-VA, Yucca Mountain Site Characterization Project Milestone SLX01LB3 Report, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Calibration of the UZ Flow and Transport Model for Yucca Mountain, Nevada

RESEARCH OBJECTIVES

The U.S. Department of Energy (DOE) is currently investigating the feasibility of using the unsaturated zone (UZ) at Yucca Mountain, Nevada, as a permanent storage facility for the geologic disposal of high-level nuclear waste. As part of the site characterization studies, a 3D site-scale UZ flow and transport model has been developed at Berkeley Lab (Bodvarsson et al., 1997). The primary objectives of the UZ model are to simulate and investigate the existing natural state of the mountain's hydrogeological system and predict possible future system responses in support of the Yucca Mountain Project. In order to do this, it is critical to incorporate all relevant, available data into the UZ flow and transport model. Data inversion and model calibration ensure that the model accurately represents the existing natural state so that predictions of future system responses can be made with confidence. This model does not include radionuclide transport.

APPROACH

The UZ flow and transport model uses the TOUGH2 (Transport of Unsaturated Groundwater and Heat) code to simulate multiphase, multicomponent fluid and heat flow through the porous and fractured rock of Yucca Mountain. A companion code, ITOUGH2 (Inverse TOUGH2), is used for automated data inversion. Data inversion uses a set of measured data (e.g., permeability, saturation, and capillary pressure) to predict (or calibrate) model parameters. ITOUGH2 automatically calibrates a specified set of model parameters in order to provide the best match between the model and the available data. Because of the large number of forward simulations required by ITOUGH2 to calibrate the UZ flow and transport model, submodels of the full 3D model are used for automated data inversion. Several submodels, representing the hydrogeology at boreholes where the data are collected, are used simultaneously to estimate layer-averaged model parameters.

The automated data inversion using ITOUGH2 allows the simultaneous

C. F. Ahlers, T. M. Bandurraga, Y. S. Wu,
A. C. Ritcey, and G. S. Bodvarsson

consideration of several types of data, including rock matrix saturation and water potential. Air pressure vs. time measured at several depths is also considered (air pressure in the subsurface changes due to barometric pumping). The conceptual

model of Yucca Mountain assumes that the liquid system is at a steady-state condition, and that saturation and water potential measurements from the rock matrix reflect this. However, barometric pumping of the subsurface is a transient phenomenon. The simulations must therefore first calculate the steady-state conditions of the system in order to match the saturation and water potential measurements and then simulate the transient barometric pumping of the system in order to match the air pressure vs. time measurements.

Several of the model parameters being calibrated also have measured values from field data. Fracture and rock matrix hydraulic permeability measurements are available as well as fitting coefficients for saturation vs. water potential relationships that describe unsaturated flow in the rock matrix. In addition to the mean data values, the automated inversion considers the uncertainty, or variance, associated with each of the measurements. Where there is more certainty (low variance) associated with data, the automated inversion attempts to more closely match the model to the data.

In order to improve the accuracy of the automated model calibration using the submodels, trial-and-error calibration of the full 3D model is performed using a limited number of simulations. These simulations are used to predict flow and transport

phenomena that are dependent on the 3-D geometry of the full UZ model. Small changes in predicted saturation and water potential are expected because of lateral flow. Other changes, such as prediction of the occurrence of perched water, are very dependent on the 3D geometry of the model.

RESULTS

Data from five boreholes are used for automated inversion. Saturation and water potential data are available

Figure 1. Example of calibrated match between simulated and observed air pressure vs. time at three depths in one borehole.

for all five boreholes, but air pressure vs. time data are available for only three of the boreholes.

Using these data, seven parameters for each of 22 layers in the site-scale model are estimated by ITOUGH2. Permeability and two unsaturated flow parameters (α and m for the van Genuchten relationships) are estimated for the fractures and rock matrix in each layer. One additional parameter for each layer describes the amount of interaction between fluid in the fractures and in the rock matrix. Figures 1 and 2 show examples of the match between the calibrated simulations and the observed data. Bodvarsson et al. (1997) describe the full calibration procedure.

One particular problem is the question of whether the set of model parameters estimated is unique. Due to the large number of model parameters being estimated, it is probable that many combinations of parameters would provide an equally good solution to the problem.

In order to understand the sensitivity of the solution to variations in key model parameters and to different conceptual models, Wu et al. (1997) produced several calibrated parameter sets that were then given to the Total System Performance Assessment (TSPA) group of the Yucca Mountain Characterization Project for use in preparing a Viability Assessment report. Each of 13 parameter sets underwent the same type of calibration procedure as was carried out for the first parameter set, although fewer parameters were estimated for each of these sets. Sensitivity of the solution to variations of infiltration, fracture permeability, and the α parameter for the fractures were explored. Conceptual models were explored of fracture-dominated flow throughout the mountain and flow that switches between fractures and rock matrix (depending on which layer it is crossing).

SIGNIFICANCE OF FINDINGS

The calibrated parameter set produced by Bodvarsson et al. (1997) is currently being used as the project-wide, base-case parameter set for numerical modeling. However,

Figure 2. Example of match between simulated and observed saturation and water potential in one borehole.

with ongoing data collection at Yucca Mountain, the evolution of the conceptual models of flow at the mountain, and the question of how to apply those concepts to numerical models, the 1997 base-case parameter set will soon be supplanted by a 1998 base-case parameter set for the UZ flow and transport model. The 13 parameter sets calibrated for TSPA were used to generate mountain-scale flow fields. TSPA then used these flow fields to evaluate the probability of transport of radionuclides

away from the proposed repository toward the accessible environment within the time that the radionuclides remain dangerous.

RELATED PUBLICATIONS

- Bodvarsson, G. S., T. M. Bandurraga, and Y. S. Wu (eds.), *The Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada, for the Viability Assessment*, Yucca Mountain Site Characterization Project Report, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Wu, Y. S., A. C. Ritcey, C. F. Ahlers, A. K. Mishra, J. J. Hinds, and G. S. Bodvarsson, Providing base-case flow fields for TSPA-VA: evaluation of uncertainty of present-day infiltration rates using DKM/Base-Case and DKM/Weeps parameter sets, Yucca Mountain Site Characterization Project, Level 4 Milestone SLX01LB2, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Water Seepage Through Unsaturated Fractured Rock

K. Pruess

RESEARCH OBJECTIVES

Evidence from a number of field sites suggests that water seepage through fractured unsaturated zones may proceed, in part, by means of fast preferential flow paths. Examples include Yucca Mountain, Nevada, where analyses of water and rock samples from the unsaturated zone have shown that environmental tracers have migrated to a depth of several hundred meters in a matter of decades. At nearby Rainier Mesa, persistent highly localized flow of water from fractures into drifts located above the water table was observed at depths of several hundred meters beneath the land surface. At a field site in the Negev Desert, Israel, man-made tracers migrated rapidly across a thick unsaturated zone of fractured chalk. All these observations indicate that in semi-arid environments water is able to migrate downward rather rapidly along localized preferential flow paths through fracture networks in partially saturated rocks, without being imbibed into the rock matrix. Localized preferential flow of water in nonhorizontal fractures has also been observed in laboratory experiments.

The objective of our research is to contribute to an understanding of water seepage behavior in unsaturated fractured rocks through development of conceptual and numerical models. We are especially interested in conditions and mechanisms for fast preferential flow. In addition to seepage under ambient conditions, we also consider the strongly heat-driven flow regimes that would develop near high-level nuclear waste packages, and in geothermal injection operations where cold water would be introduced into hot rock fractures.

APPROACH

Natural rock fractures are expected to encompass a large variety of aperture distributions. The present work focuses on "small-aperture" fractures in hard rocks, such as tuffs, basalts, granites, or graywackes. Aspects of fracture aperture distribution that are believed to be essential for replicating natural features include (a) the presence of asperity contacts, where the fracture walls touch; (b) a more or less gradual change

towards larger apertures away from the asperities; (c) small-scale fracture wall roughness; and (d) finite-sized spatial correlation length among apertures.

We conceptualize fractures as two-dimensional heterogeneous porous media, and use geostatistical techniques to generate synthetic permeability distributions in the fracture plane. Water flow in high-angle fractures is simulated numerically, taking into account the combined action of gravity, capillary, and pressure forces. For water seepage through hot fractured rock we use a semianalytical method to model conductive heat transfer from the wall rocks, which gives rise to strong vaporization effects. All flow simulations were carried out with our general-purpose simulator, TOUGH2.

RESULTS

In the flow simulations, water is injected over different portions of the top boundary of a synthetic heterogeneous fracture. An example of simulated seepage behavior is shown in Figure 1. It is seen that seepage proceeds in dendritic patterns along localized pathways. Asperity contacts promote local ponding in some regions, while other

regions are bypassed by the percolating water. Simulations not shown here indicate that subhorizontal barriers or obstacles of low permeability, as may be provided by fracture intersections and terminations, are effective in funneling distributed seepage into preferential pathways. Flow funneling becomes stronger, and seeps advance downward more rapidly, when laterally more extensive obstacles are present. Average vertical permeability becomes smaller for longer subhorizontal obstacles in a fracture, so that we have the seemingly paradoxical result that water seepage, and solute transport, may proceed faster in media of lower average permeability.

Seepage behavior in heterogeneous fractures may be different on different space and time scales. An analysis of the governing equations for unsaturated water flow suggested that an approximate scaling invariance should hold when simultaneously all horizontal dimensions and the water flow rate are increased by a

Figure 1. Liquid seeps shown at the time of breakthrough at a depth of -19.5 m. Water is injected at a constant rate of 10^{-3} kg/s over a 1-m interval at the top of a heterogeneous fracture. The injection interval is centered at different distances from the left boundary, namely, 8.5 m (top), and 10.5 m (bottom). Reference permeability is 10^{-9} m².

factor λ , while all vertical dimensions and time are simultaneously increased by a factor λ^2 . Through numerical simulation experiments, we were able to confirm this theoretical result.

Our numerical simulations of water injection into unsaturated rock fractures at above-boiling temperatures revealed complex fluid flow and heat transfer processes. An example of a boiling injection plume in a heterogeneous fracture is shown in Figure 2. As water descends from the injection point, it is heated by conduction from the wall rocks. Boiling commences when water reaches the saturated vapor temperature at prevailing (nearly ambient) pressures. Water continues to vaporize as it migrates downward, with latent heat of vaporization supplied by the wall rocks. The rocks are cooled locally by the vaporization process. Quantitative details depend strongly on water seepage rates, rock temperature, and heterogeneity structure of the fractures. Fractures with volume-averaged homogeneous permeability structure tend to give a very poor approximation of vaporization behavior and water migration pattern.

SIGNIFICANCE OF FINDINGS

Recent advances in numerical simulation capabilities have made possible fully transient simulations of two- and three-dimensional unsaturated flow in heterogeneous rock fractures, with detailed resolution of small-scale heterogeneity, and including highly nonlinear transitions between partially and fully saturated conditions locally. Numerical experiments on water seepage in synthetic heterogeneous fractures with realistic heterogeneity have shown many of the features observed at field sites, including fast preferential flow, flow fingering, bypassing, and ponding. Scaling relationships were proposed and confirmed that enable laboratory-scale observations of fracture flow to be applied to field-scale phenomena.

Water flow and solute transport behavior in unsaturated rock fractures may be very different from what is seen in homogeneous media and in fully saturated condi-

Figure 2. Water saturations (top) and temperatures (bottom) after 11.63 h of water injection at a rate of 11.4 kg/h into a heterogeneous vertical fracture with reference permeability of 10^{-10} m² and a temperature of 110°C.

tions. For example, water seepage may proceed faster in unsaturated fractures of lower average permeability.

Water seepage through fractured rock at above-boiling temperatures is of interest for nuclear waste repository design and performance, and for water injection schemes aimed at enhancing energy recovery from geothermal fields. We have demonstrated numerical simulation techniques that can describe the complex interplay between fluid flow and heat transfer processes. Our results indicate that liquid water can migrate considerable distances through fractured rock that is at above-boiling temperatures and be only partially vaporized. Put differently, heating fractured rock to temperatures above the nominal boiling point does not preclude water seepage and solute transport through the fractures.

RELATED PUBLICATIONS

- Pruess, K., On vaporizing water flow in hot sub-vertical rock fractures, *Trans. Porous Media*, 28, 335-372, 1997.
- Pruess, K., On water seepage and fast preferential flow in heterogeneous, unsaturated rock fractures, *J. Contam. Hydr.*, 30, 333-362, 1998.

FUNDING

This work has been supported by the Assistant Secretary of the Office of Energy Efficiency and Renewable Energy, Office of Geothermal Technologies; and Director, Office of Civilian Radioactive Waste Management, Yucca Mountain Site Characterization Project (through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory), of the U. S. Department of Energy, Contract No. DE-AC03-76SF00098,

Geochemical Constraints on Flow Processes at Yucca Mountain, Nevada

RESEARCH OBJECTIVES

Placing bounds on the percolation fluxes at the repository level in Yucca Mountain is important for the evaluation of the site as a potential repository of high-level nuclear waste and in the designing of waste packages and their emplacement. The spatial distribution of the percolation flux and the effects of possible climate changes are also important. Our objectives were to develop and apply methods based on the geochemical behavior of chloride and strontium (Cl) and (Sr) coupled to the site-scale model of the unsaturated zone to bound the percolation fluxes and subsurface flow pathways for the modern climate (precipitation and infiltration) and the estimated climate at the peak of the last glacial period (approximately 21,000 years ago).

APPROACH

The 3D unsaturated zone (UZ) site-scale model for Yucca Mountain was used to model the surface Cl fluxes and the subsurface spatial distribution for two precipitation (i.e., climate) and infiltration conditions, provided by the U.S. Geological Survey (USGS). Because the climate has varied considerably over the past 20,000 years, the transient effects of decreased infiltration in the Holocene on the subsurface Cl distribution is also simulated.

Fluxes of Cl and Sr to the subsurface are primarily dependent on the chloride concentration in precipitation and the spatial distribution of precipitation, with a lesser source from wind-blown dust. Therefore, evaporation is the controlling factor for concentration differences. Combining the windblown dust component and that dissolved in precipitation, an effective concentration ($C_{Cl,p}$) in precipitation has been estimated by researchers at Los Alamos National Laboratory. A good assumption for the Cl ion is that it is not incorporated into minerals, and

therefore the surface chloride flux (J_{Cl}) is given by:

$$J_{Cl} = C_{Cl,p} J_p \quad (1)$$

where J_p is the precipitation flux of water. The surface concentration is then related to the infiltration flux — higher infiltration results in lower concentrations and vice-versa.

Modeling was performed using the T2R3D module of TOUGH2 for simulating advective and diffusive tracer transport, simultaneously with the water-air system, using the surface boundary Cl fluxes described by Equation (1) and the estimated concentrations of Cl and Sr in precipitation.

RESULTS

Simulations were performed using the calculated modern infiltration and precipitation fluxes at Yucca Mountain (mean ~ 5 mm/yr over the model domain), and fluxes for the last glacial maximum (mean ~ 28 mm/yr). A case was performed to evaluate the climate change that occurred approximately 10,000 years ago. The spatial distribution of Cl concentrations obtained by using the chloride flux given by Equation (1) with the infiltration fluxes from the

USGS generally shows a pattern of high concentrations under alluvial channels, with much lower concentrations at ridge tops, where both precipitation and infiltration are higher (Figure 1).

An east-west cross section (Figure 2) from the 3D site-scale model shows the Cl distribution for the climate-change case. Flow is generally vertical above the zeolitic units (~900 m) with up to about 100 m lateral flow in the shallow bedded tuffs (nonwelded volcanic units, termed the PTn). At greater depths there is significant mixing due to lateral flow on top of the low permeability Calico Hills zeolitic tuffs (CHn) and greater downdip flow of lower chloride waters from higher infiltration regions near the crest of Yucca Mountain.

Figure 1. Surface concentrations of chloride calculated from the model precipitation and infiltration rates and the estimated concentration of chloride in precipitation.

Figure 2. East-west Cross section through 3D model, showing chloride concentrations for the 10,000 yr infiltration case (glacial maximum climate followed by 10,000 yr of the modern climate). Large areas below regions of low infiltration retain waters from the last glacial period.

Comparison of model results to Cl measurements from pore waters in boreholes at shallow levels (i.e., in the PTn), indicates that the calculated mean infiltration rate at the site is unlikely to be higher than 5 mm/yr, and could be as low as 1 mm/yr. Chloride concentrations in pore waters measured in the Exploratory Studies Facility tunnel by Los Alamos National Laboratory are roughly matched by the near-vertical flow directly below alluvial channels and small ridges, with a better correlation in the southern part of the Main Drift.

In the basal vitrophyre of the Topopah Spring unit and in the underlying Calico Hills unit, the predicted present infiltration results in steady-state concentrations significantly higher than the observed perched water concentrations and in many of the pore waters. The perched water concentrations are closer to those predicted by the infiltration pattern calculated for the previous glacial maximum. Thus, the evidence suggests that the perched water has a significant component of older waters from a period of higher precipitation, possibly the late Pleistocene or early Holocene. Strontium concentrations in the unsaturated zone and in perched waters are also fairly well matched, considering evaporation as the controlling factor for waters entering the subsurface, with water-rock interaction as the major factor where waters have contacted zeolite-rich rocks in the CHn at depth (Figure 3).

SIGNIFICANCE OF FINDINGS

Modeling of the Cl and Sr concentrations at Yucca Mountain indicates that the present-day mean percolation flux at the site is not likely to be more than 5 mm/yr. This work has also shown that perched waters may have a large fraction of water remaining from a period of higher precipitation, possibly the late Pleistocene, and were not formed by recent flow of dilute waters directly from the surface. This is supported by independent studies on ^{36}Cl and ^{14}C by researchers at Lawrence

Sr Concentrations From 3-D Model and Perched Water Analyses

Figure 3. Concentrations of Sr in the unsaturated zone and in perched waters from the USGS compared to 3D model results. The strong drop in Sr concentrations at depth is a result of Sr exchange with zeolite-rich volcanic tuffs.

Livermore National Laboratory (LLNL). These results provide important bounds for constraining both the current percolation fluxes at the potential nuclear waste repository and for the possible variations due to future climate changes.

RELATED PUBLICATIONS

Sonnenthal, E. L., and G. S. Bodvarsson, Modeling the chloride geochemistry in the unsaturated zone, in, *The Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada, for the Viability Assessment*, edited by G. S. Bodvarsson, T. M. Bandurraga, and Y. S. Wu, Yucca Mountain Site Characterization Project Milestone, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

Sonnenthal, E. L., and G. S. Bodvarsson, Percolation flux estimates from geochemical and thermal modeling, in *Proc. Eighth International Conference on High-Level Radioactive Waste Management*, pp. 130-132, American Nuclear Society, La Grange Park, Ill., 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Summary of S⁴Z: Sub-Site-Scale Saturated Zone Model for Yucca Mountain, Nevada

A. J. B. Cohen, C. M. Oldenburg,
A. M. Simmons, A. K. Mishra,
and J. Hinds

RESEARCH OBJECTIVES

The proposed site for a U.S. Civilian radioactive waste repository is Yucca Mountain, Nevada. The proposed repository is to be built in the unsaturated zone, approximately 200 to 300 m above the water table. The long-term isolation of wastes relies in part on the flow and transport characteristics beneath the water table because the saturated zone will be the final transport pathway between the potential repository and the regions down-gradient from the site. The geologic structure beneath Yucca Mountain is comprised of dipping volcanic rock layers of variable thickness, which are fractured and offset by faults. The layers have variable flow properties, and the effects of faults on flow are generally unknown. The resulting complex hydrogeologic structure is one of the primary factors that controls the directions, speed, and pathways of saturated zone flow. In addition, there are relatively few data collected beneath the water table, and the uncertainty of flow and transport predictions is, therefore, significant. The need to make predictions of how potential radionuclides from the repository will mix and spread in the saturated zone is the primary motivation for studying the saturated zone.

Some of the primary uncertainties regarding the saturated zone and its transport characteristics include the velocity of groundwater flow, the effects of complex geologic structures on saturated zone flow and transport, the hydrologic properties of faults, and the role of potential upwelling from a deep carbonate aquifer.

The objective of this study is to develop a computer model of the saturated zone that can be used as a tool to test current hypotheses of saturated zone flow, and to identify and plan hydrologic tests needed to improve our understanding of the system.

APPROACH

We have developed the S⁴Z Model¹, a 3D numerical model of the saturated zone at Yucca Mountain (S⁴Z is a pseudo-acronym for "Sub-Site-Scale Saturated Zone"). One of the primary objectives in the development of S⁴Z was the inclusion of realistic geologic structure.

Figure 1 shows the model in plan view. The model covers an area of ~100 km². The figure shows the gridblock discretization, the locations of saturated zone boreholes (red), the water table contours (blue), and the surface traces of the dominant normal faults (black). The proposed repository area is located within the rectangular gridblocks on the western side. The top of the model represents the water table, and the bottom represents the base of a low-permeability geologic layer, approximately 1 km beneath the water table. The gridblock discretization is designed to replicate the continuity of the faults and to enable simulation of hydraulic and tracer tests conducted in the clustered area of boreholes located near the model's center. These simulations require a finer gridblock discretization, as shown.

The model has 23 layers that replicate the geometry and lateral continuity of strata as defined in a 3D geologic model of the site. Faults act to displace geologic layers, which can create obstructions or fast pathways for fluid flow. The displacement is also replicated. The model is developed for use with TOUGH2, the same computer code used by Berkeley Lab scientists who simulate flow in the unsaturated zone at Yucca Mountain. This code simulates fluid and heat transport in fractured rocks.

RESULTS

The model was calibrated to water table elevations, and simulation of and calibration to pumping tests were performed. Numerous experimental simulations were also performed.

Figure 1. Plan view of the S⁴Z Model.

Figure 2. (a) S⁴Z Model cross section along A-A' (Figure 1). (b) Passive tracer concentration distribution from source at water table beneath the repository along cross-section A-A' (Figure 1). Log X = log (tracer mass fraction).

These simulations illustrated the effects of different fault types on saturated zone flow, and the effects of infiltration source locations on the fate of down-gradient transport characteristics. A dual-permeability model was also developed. One simulation is described below. Fault zones that are comprised of fractured permeable rock could be high-permeability features, and this simulation considers fault zones with a constant permeability of 10^{-11} m^2 . This is the same value assigned to the high-permeability Bullfrog Tuff unit. The manner in which repository-source water infiltrates the water table and is transported down gradient is illustrated using a passive tracer under steady-state flow conditions along a 2D cross section of the model. Figure 2(a) shows the model profile along cross-section A-A' (Figure 1). Figure 2(b) shows the simulation results along this cross section. In this figure, the tracer plume is primarily transported within the Bullfrog unit, and the high-permeability faults act to hydraulically connect this unit, even where it is displaced against lower-permeability units at faults. The general result is that vertical mixing is inhibited, and water infiltrating to the water table beneath the repository could migrate several kilometers down gradient from the site within units that are hundreds of meters beneath the water table. Simulations that consider low-permeability fault zones, or faults with no altered zone, show that upwelling of deep waters to the water table occurs. Hence, mechanisms other than those previously considered could create upwelling. Simulations that consider faults with no internal zone and with displacement only show that repository-source

plumes can be channeled into narrower regions down gradient. This behavior is not predicted using traditional dispersion models, nor was it anticipated.

SIGNIFICANCE OF FINDINGS

Simulation results reveal potential flow characteristics and their effects on transport that are fundamentally different than those considered in current conceptual models of the saturated zone. They therefore illustrate the weaknesses in our understanding of the saturated zone, and point to the need for further field testing.

RELATED PUBLICATION

Cohen, A. J. B., C. M. Oldenburg, A. M. Simmons, A. K. Mishra, and J. Hinds, S⁴Z: Sub-site-scale saturated zone model for Yucca Mountain, Yucca Mountain Site Characterization Project Milestone SP25UM4, LBNL-41773, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Energy Resources Department

Larry R. Myer, Energy Resources
Department Head

The Energy Resources Department is responsible for two major program areas: (1) Oil and Gas Exploration and Development, and (2) Geothermal Energy Development.

OIL AND GAS EXPLORATION AND DEVELOPMENT

Multidisciplinary research is being conducted in reservoir characterization and monitoring, optimization of reservoir performance, and environmental protection. Using basic research studies as a source of innovative concepts, the Energy Resources Department researchers seek to transform these concepts into tangible products of use to the industry within a time frame consistent with today's rapid growth in technology. Reservoir characterization and monitoring involve development of new seismic and electromagnetic techniques focused at the inter-well scale. Optimization of reservoir performances involves application of reservoir engineering and geomechanics principles to enhance production. The next major step in research will focus on methods to optimize performance through integration of monitored geophysical data, production data, and reservoir simulation.

Principal research activities include:

- Applications of seismic methods for characterization of fractured reservoirs
- Use of converted waves in cross-well applications
- Development of magnetotellurics for marine applications
- Development of mid-frequency electromagnetic techniques with a focus on imaging through casing
- Improved inversion methods for reservoir characterization, with a focus on combining production and geophysical data
- Pore-to-laboratory-scale study of physical properties and processes, with a focus on controlling phase mobility, predicting multiphase flow properties, and drilling efficiency
- Development of reservoir process control methods
- Development of new methods to mitigate environmental efforts of petroleum refining and use
- Development of single-well seismic technology, including instrumentations, acquisition, and processing

Since 1994, the major part of the Oil and Gas Exploration and Development program has been funded through the Natural Gas and Oil Technology Partnership Program. Begun in 1989, the Partnership was expanded in 1994 and again in 1995 to include all nine DOE multiprogram laboratories, and has grown over the years to become an important part of the DOE Oil and Gas Technologies program for the national laboratories. Partnership goals are to develop and transfer to the domestic oil industry the new

technologies needed to produce more oil and gas from the nation's aging, mature domestic oil fields, while safeguarding the environment.

Partnership technology areas are:

- Oil and Gas Recovery Technology
- Diagnostics and Imaging Technology
- Drilling, Completion, and Stimulation

Projects are typically multiyear, are reviewed and re-prioritized annually by industry panels, and are collaborations between national laboratories and industry.

GEOTHERMAL ENERGY DEVELOPMENT

The main objective of ERD's geothermal energy development program is to reduce uncertainties associated with finding, characterizing, and evaluating geothermal resources. The ultimate purpose is to lower the cost of geothermal energy for electrical generation or direct uses (e.g., agricultural and industrial applications, aquaculture, balneology, etc.). With these goals in mind, existing tools and methodologies are upgraded and new techniques and instrumentations are developed for use in the areas of geology, geophysics, geochemistry, and reservoir engineering.

The program encompasses theoretical, laboratory, and field studies, with an emphasis on a multidisciplinary approach to solving the problems at hand. Cooperative work with industry, universities, and government agencies draws from Berkeley Lab's 25 years of experience in the area of geothermal research and development.

In recent years, the DOE geothermal program has become more industry-driven, and a significant part of the Berkeley Lab effort has been directed toward industry assistance, especially in the area of technology transfer and in understanding the nature and dynamics of The Gey-

sers geothermal field in northern California, which has begun to show the effects of overexploitation.

At present, the main research activities of the program include:

- Development and enhancement of computer codes for modeling heat and mass transfer in porous and fractured rocks.
- Laboratory investigations of the hydraulic and thermal properties of fractured and intact reservoir rocks.
- Isotopic and noble gas studies to characterize geothermal fluids; and to identify their sources, their potential migration paths, and the connectivity within the geothermal reservoir.
- Documentation of the behavior of geothermal fluids under commercial production and injection operations (e.g., field case studies), with specific emphasis on The Geysers field.

FUNDING

The Oil and Gas Exploration and Development program receives funding from the Assistant Secretary for Fossil Energy, Natural Gas and Oil Technology Partnership Program; and Director, Office of Energy Research, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. Support is also provided by the Gas Research Institute (GRI) and direct industry contributions. Industrial collaboration is an important component of the DOE Fossil Energy and GRI programs.

The Geothermal Energy Development program receives support from the Assistant Secretary of the Office of Energy Efficiency and Renewable Energy, Office of Geothermal Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Electro-Osmosis Used to Consolidate Well Casings

RESEARCH OBJECTIVES

The objective of this research is to improve the bearing capacity of offshore oil well casings in order to prevent collapse and loss of the well.

APPROACH

Oil wells are made by drilling down to a certain depth and then placing a tubular steel casing to protect the hole drilled so far. The hole is then deepened by drilling with a smaller diameter bit inside this casing, and setting a second casing. This process is repeated until the desired target depth is reached. Often four or five nested casings are employed, starting at 30 in. diameter and finishing at 6 or 8 in. diameter at the bottom of a 15,000-ft-deep well.

Offshore, the first casing is typically 30 or 36 in. in diameter, and may be 200–300 ft deep. Marine sediments to these depths below the sea floor are often very soft and have little capacity to support the casing (and the weight of the next casing to be placed inside it, until firm rock is reached), and many wells are lost because of the collapse of the casing. Such an accident typically costs three million dollars to recover.

Our approach has been to use electro-osmosis to strengthen the soil surrounding the casing and thereby improve its stability. The work has grown out of a broader investigation of the use of electrokinetic effects in clay-containing soils, *inter alia*, to reduce the amount of clay sticking to drilling equipment, tool wear, and the coefficient of friction between soils and metal objects.

G. A. Cooper and R. C. Wrixon

Electro-osmosis is the process whereby, if a clay is subjected to an electric field, water migrates toward the negative electrode. Here it may be used

as a lubricant to reduce friction and wear. At the anode, on the other hand, water is removed, so the clay becomes dryer and stiffer, and hence has a great bearing capacity. A related phenomenon, electrophoresis, is the movement of clay particles suspended in water towards the anode. Electrophoresis, followed by electro-osmosis (using a well casing as an anode), is the basis of drying the soil around the casing and improving its bearing capacity.

We have carried out laboratory experiments to investigate the voltage, current, and time required to achieve significant improvements in clay bearing strength. Early experiments were run on the pure clays montmorillonite and kaolinite, and subsequent work was done using real marine sediments from San Francisco Bay, the Gulf of Mexico, and the North Sea. Metal rods were immersed in wet clay samples and subjected to treatments for various times, voltages, and currents. They were then pulled out of the clay and the pull-out force measured.

RESULTS

We found that in all cases, the pull-out force was increased. The response varied with clay type and operating parameters, with bearing capacity increased up to ten times in some circumstances (Figure 1). In typical cases, using real marine sediments, improvements of 50 to 300% were achieved. Interestingly, there is an optimum level of

Figure 1. Calculations showing the bearing capacity of a 300-ft-long by 36-in.-diameter casing based on laboratory pull-out tests of steel rods embedded in 75 wt % kaolinite-water mixtures. A typical casing of this type may weigh 90,000 lb, and may need to support an additional 250,000 lb when the next casing is being placed. Note that the untreated clay supports only 40,000 lb.

Figure 2. Pull-out shear strength as a function of applied voltage for six-hour consolidation tests in a Gulf of Mexico sediment from 25 to 40 ft below mud line. Note the different responses obtained with different anode materials.

treatment beyond which the pull-out resistance decreases again. This is associated with the clay surrounding the "casing" becoming so dry that it cracks. It is not clear if this will occur in a full-scale experiment, however, since in our lab work the clay was contained in a beaker and was therefore unable to shrink in towards the anode. In the field, the soil would be free to move in to accommodate any shrinkage.

Another interesting discovery was that the material of the anode affects the rate and degree of consolidation. This is because, at the anode, the metal of the electrode dissolves and metal ions diffuse into the soil, where they react with the clay particles. Figure 2 shows the effect in a sediment from the Gulf of Mexico where steel, copper, and aluminum anodes were used. The aluminum shows a rapid result, but a correspondingly early level of "overtreatment." The steel electrode shows a slower response, but with a higher peak, while the copper electrode shows the slowest response, but also the greatest strength, and no over treatment, at least by the end of the experiment.

SIGNIFICANCE OF FINDINGS

These results indicate that clay soils may be strengthened substantially by electro-osmotic treatment. Extrapolating the lab data to field conditions indicates that a 200-ft-long by 36-in.-diameter casing, placed in a typical marine sediment may be treated by applying 1,750 A

at 90 V for 10 hr. The increase in bearing capacity would depend on the soil surrounding the casing, but it is expected to lie in the range of 50 to 300% mentioned above. Such increases are well worth having, and may make the difference between a successful and a failed well. The cost of the electricity required (1,500 kW h, at perhaps \$200) is negligible, and the extra equipment, i.e., cables and a counter electrode to connect to an existing DC welding set, is small by comparison with regular rig operating expenses, which are typically \$100,000/day).

RELATED PUBLICATIONS

Wrixon, R., and G. A. Cooper, Theoretical and practical guidelines for using electrokinetics to improve casing support in soft marine sediments, (presented at the 1998 SPE/IADC Drilling Conference, Dallas Tex., March 3-6, 1998), SPE/IADC 39299, Society of Petroleum Engineers, Dallas, Tex., 1998.

Wrixon, R., and G. A. Cooper, *In situ* casing consolidation by electrokinetic and electrochemical methods, *J. Pet. Technol.*, 50(2), 51-53, 1998.

FUNDING

This work has been supported by the Assistant Secretary for Fossil Energy, Natural Gas and Oil Technology Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Marine Magnetotellurics for Base Salt Mapping: Gulf of Mexico Field Test at the Gemini Structure

G. M. Hoversten, S. Constable,*
and H. F. Morrison

**Scripps Institution of Oceanography*

RESEARCH OBJECTIVES

Sponsored by a consortium of major oil companies and the DOE, a collaborative effort of the Scripps Institution of Oceanography (SIO), University of California at Berkeley, and Berkeley Lab has developed equipment, algorithms, software, and field techniques that have together made the application of Marine Magnetotellurics (MMT) to petroleum exploration possible. In June 1997, a demonstration survey was run over the Gemini prospect in the Gulf of Mexico. The Gemini salt structure is a complex 3D salt body with a subsalt oil and gas discovery by a Chevron Texaco partnership. This is the first successful MMT survey conducted in the Gulf for petroleum exploration.

APPROACH

The state-of-the-art SIO seafloor electromagnetic recorder (Figure 1) is based on two decades of SIO development. It incorporates an acoustic navigation and release system, a modern digital data logger, custom electric field preamplifiers, low-noise electrodes designed for seafloor use, and commercial broad-band magnetic sensors in underwater pressure cases. The seafloor instrument weighs approximately 150 kg and with its electrode arms detached is easily transportable. It can be deployed with or without magnetic field sensors. This allows considerable flexibility in possible survey configurations. The instrument (Figure 1) is configured as a complete magnetotelluric (MT) site with orthogonal E and H measurement capability. The 5-m electrode arms detach for shipping and onboard handling of the system, described in detail by Constable et al. (in press). To test relative performance of algorithms and provide enhanced confidence in information content of the data, we use four different 2D MT inversion algorithms: (1) Smith and Booker (1988); (2) a non-linear conjugate gradient algorithm, (Mackie, 1997); (3) Occam2D algorithm, (deGroot-Hedlin et al., 1990); and (4) Sharp Boundary Inversion (SBI) algorithm (Smith et al., 1997).

RESULTS

The first three algorithms find models that are smooth both verti-

cally and horizontally. They are all started from a 0.7 ohm-m half space with no a priori information as constraints. All 3 smooth inversions provide very consistent models in the following respects. First, all show presence of resistive ($\sim 1\Omega\text{-m}$) material just below the seafloor.

Second, all have a sharp increase in resistivity corresponding with top salt as picked from the 3D seismic. Third, all show a zone just above salt with lower resistivity than seawater. Fourth, all give a similar picture of base salt down to a depth of about 5 km. It is reassuring that the three different algorithms all give very similar pictures and indicate the presence of a confined salt body in the correct location. However, the smooth inversions provide a fuzzy base salt picture that must be interpreted with the aid of inversion tests on numerical model data. To improve resolution of the base salt we use some of the constraining features possible with the Occam2D algorithm (Figure 2) and in additional inversions use the SBI algorithm.

The 2D SBI inversion is parameterized to accommodate sharp contrasts in resistivity across boundaries and thus eliminate some of the ambiguity in interpreting smooth inverse models. Rather than parameterizing the model in terms of blocks for which resistivity is solved, the SBI parameterizes the model in terms of vertical node locations of boundaries between layers and resistivities of the layers. Resistivities are defined laterally at node locations and are constant vertically within each layer. They vary linearly between nodes in the horizontal direction within each layer. To stabilize the inversion a smoothing constraint is placed on vertical node locations and on the horizontal variation of resistivity. At each iteration layer resistivities are projected onto an underlying finite element mesh for MT calculations.

Because the SBI is parameterized by layer boundaries a starting model with the appropriate number of layers is required. In this case, the results from the smooth inversions are used as a guide in building the SBI starting model. In particular, a near-surface resistive layer is indicated. The presence of a deeper resistive layer was both indicated in the smooth

Figure 1. SIO seafloor MT data logger over side of survey ship in the Mediterranean.

Figure 2. Occam2D TM mode inversion. Starting model was 0.5 Ω -m half space. Black line shows salt outline as interpreted from 3D prestack depth migrated data. No smoothing across blocks at top salt.

inversions and in the apparent resistivity curves at lower frequencies. Starting location of the base salt is deep enough to encompass the high resistive zone shown on all smooth inversions. The SBI has placed a base salt interface within a few percent of the 3D seismic pick down to a 5-km depth (Figure 3). Below 5 km, where the salt is thinnest, the SBI has thinned the salt from the starting model until no more changes in the MT response occur. The resulting salt model at the southeast end of the line beneath sites 5 and 6 represents minimum salt thickness at this depth that produces any MT response. In addition to the base salt, the inversions of the data indicate the presence of a deep resistive zone that could correspond to cretaceous sediments. The experiment is not designed to acquire the accurate low-frequency data to accurately position this deep resistor. Longer recording times are needed to improve data quality below 0.001 Hz, where information about the deeper structure is contained.

SIGNIFICANCE OF FINDINGS

The 1997 Gulf of Mexico MMT survey is the first successful one of its kind, both in terms of high-quality seafloor MT data acquisition and successful interpretation of resulting data. Inverse models, which fit observed data, are of sufficient fidelity to answer significant exploration questions about shape and location of base salt structures. In particular, smooth 2D inversions of field data show the confined nature of the Gemini salt body and sharp boundary 2D inversions resolve the base of the salt to within a few percent of its depth down to a 5-km depth. In addition, models at Gemini could provide information of deeper Gulf structure. The technology is moving into commercialization. The consortium is planning two additional test surveys in 1998: in the North Sea to image the base of basalt structures; and in the Gulf of Mexico.

Figure 3. SBI inversion of Gemini data. Top of salt boundary location was fixed. White line is salt outline from 3D seismic.

RELATED PUBLICATIONS

- Constable, S., A. Orange, G. M. Hoversten, and H. F. Morrison, Marine magnetotellurics for petroleum exploration 1. A seafloor equipment system, *Geophysics*, 63(3), 816-825, 1998.
- deGroot-Hedlin, C., S. Constable, Occam's inversion to generate smooth, two-dimensional models from magnetotelluric data: *Geophysics*, 55, 1613-1624.
- Hoversten, G. M., S. Constable, and H. F. Morrison, Marine magnetotellurics for petroleum exploration 2. Numerical analysis of subsalt resolution, *Geophysics*, 63(3), 826-840, 1998.
- Smith, J. T., G. M. Hoversten, H. F. Morrison, and E. Gasperikova, Sharp boundary inversion of 2-D magnetotelluric data, in *Extended Abstracts of the 1997 Ann'l Meeting of European Assoc. of Geophysicist & Engineers, Geneva, Switzerland*, 1(F023), 1997.

REFERENCES

- Mackie, R. L., D. W. Livelybrooks, T. R. Madden, and J. C. Larsen, A magnetotelluric investigation of the San Andreas fault at Carrizo Plain, California, *Geophys. Res. Lettrs.*, 24, 1847-1850, 1997.
- Smith, J. T., and J. R. Booker, Rapid Inversion of Two- and Three-Dimensional Magnetotelluric Data, *J. Geophys. Res.*, 96, 3905-3922, 1998.

FUNDING

This work has been supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Laboratory Technology Research Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Electromagnetic Imaging in Steel-Cased Wells

RESEARCH OBJECTIVES

Borehole electromagnetic (EM) measurements, using fiber-glass-cased boreholes, have proven useful in oil field reservoir characterization and process monitoring (Wilt et al., 1995). It has been presumed that these measurements would be difficult in metal-cased wells due to the very large EM attenuation and phase shifts. Recent laboratory and field studies have indicated that detection of EM signals through metal casing should be possible at low frequencies, and that these data may provide a conductivity image at a useful scale. Furthermore, using numerical analysis Becker et al. (1997) showed that if the casing properties are independently known, then the formation signal can be accurately recovered.

Three properties of the casing are particularly important in evaluating and analyzing EM field behavior — electrical conductivity, magnetic permeability, and thickness of casing wall. The objective of our research is to develop an EM methodology for evaluating these parameters using single-hole measurements.

APPROACH

An innovative EM method has been developed for characterizing a steel casing in terms of its electrical conductivity, magnetic permeability, and thickness. The method is based on the accurate measurement of the magnetic fields near a transmitting loop in a steel-cased borehole, and the least-squares inversion of the data. The need to make measurements close to the source stems from two related considerations. First, by making measurements close to the transmitter we can minimize the formation response. In evaluating the casing parameters, formation response is merely noise. The second consideration concerns the practicalities of fabricating a borehole tool. The measurement accuracy in terms of ppm of the

primary field can best be achieved when the transmitter and receiver are close to each other.

It is assumed that the casing is uniform, infinite in length, and lies in a uniform whole space. A single loop is used as both the transmitter and the receiver. The transmitter and receiver are coaxial and separated vertically by a distance of 10 cm. The radius of the loop source is 2.54 cm (1 in.) and the inner casing radius is 6.36 cm (2.5 in.). A one-ampere current is used in the loop with its effective magnetic moment of 2.03×10^{-3} ampere-m². The conductivity of well fluid, steel, and formation are 0, 0.5×10^7 , and 0.01 S/m, respectively. The relative magnetic permeability of the casing is 125, while for the other media it is that of free space.

Data used for reconstructing the model parameters are H_z fields, sampled logarithmically at seven frequencies ranging from 1.25 to 80 Hz. We have used the Marquardt-Levenberg least-squares (LS) method to invert the H_z field. Once H_z fields for a theoretical model have been calculated, the following rms error, objective function, is used in the LS inversion as the objective function to be minimized,

$$E(\mathbf{m}) = \sqrt{\frac{1}{N} \sum_i \sum_j \left(\frac{f_{i,j}^o - f_{i,j}^c(\mathbf{m})}{f_{i,j}^o} \right)^2}, \quad (1)$$

where f^o is the observed H_z field, f^c is the H_z fields calculated for model $\mathbf{m}$, subscript $i = 1$ to 2 indicates the real and imaginary parts of the fields, subscript $j = 1$ to 7 indicates the sampling frequencies, and $N = 2 \times 7$ is the number of data. In the LS inversion, we have solved the system of resulting data misfit equations directly using Householder transformation without forming the normal equation.

Parameter	Given	Initial	Inversion		
			6 digits	5 digits	4 digits
σ (S/m)	0.5×10^7	1.0×10^7	0.5001×10^7	0.4997×10^7	0.4836×10^7
μ_r	125	100	125.0	124.9	120.9
d (cm)	0.62	1.0	0.6199	0.6202	0.6401
$(\sigma\mu)^{1/2}d$	0.1738	0.3545	0.1738	0.1737	0.1735
RMS error		0.7641×10^{-2}	0.2339×10^{-6}	0.1967×10^{-5}	0.1827×10^{-4}

Table 1. Inversion for casing parameters. Vertical magnetic fields are sampled at frequencies between 1.25 and 80 Hz. Transmitter-receiver separation is 10 cm. Three data sets with varying accuracy have been used for the inversion.

RESULTS

In analyzing synthetic data for inversion purposes, we assume that the number of digits chosen to represent the data reflects the accuracy of the data in terms of ppm. Table 1 shows inversion results corresponding to the three different data sets with different accuracy. It appears that individual parameters can be resolved almost exactly if data quality is better than 10 ppm. If data quality is better than 100 ppm (4-digit accuracy), all parameters can be accurately resolved to 0.1%. The resolving power is greatly reduced with data worse than 100-ppm accuracy, resulting in an overall accuracy of 3% for individual parameters. Note that while the resolution of individual casing parameters is low, the lumped parameter $(\sigma\mu_r)^{1/2}d$ can be accurately evaluated (0.2%) within the noise level.

SIGNIFICANCE OF FINDINGS

We have shown that, using accurate measurements and common inversion techniques, steel casing parameters can be accurately resolved to within 0.1%. As demonstrated by Wilt et al. (1995), we can then easily extract the formation response, an essential piece of information for properly evaluating reservoirs in producing fields. The study results have led us to investigate borehole EM tools for accurate measurements in cased borehole environments. The specifications of EM tools and operational principles have been presented by Lee et al. (1998).

RELATED PUBLICATIONS

- Becker, A., B. Wang, K. H. Lee, and M. Wilt, Subsurface electromagnetic measurement through steel casing, in *Expanded Abstracts of the 67th Ann. Internat. Mtg., Soc. Expl. Geophys.*, pp. 1965-1968, 1997.
- Lee, K. H., H. J. Kim, and Y. Song, Electromagnetic method for analyzing the property of steel casing, LBNL-41525, Lawrence Berkeley National Laboratory Report, Berkeley, Calif. 1998.
- Wilt, M., K. H. Lee, D. Alumbaugh, H. F. Morrison, A. Becker, A., H.-W. Tseng, and C. Torres-Verdin, Cross-hole electromagnetic tomography: A new technology for oil field characterization, *The Leading Edge*, 14, 173-177, 1995.

FUNDING

This work has been supported by the Assistant Secretary for Fossil Energy, Office of Natural Gas and Petroleum Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. The research has been driven by the LBNL/UCB EM consortium, whose membership includes the Chevron USA Production Company, Japan National Oil Corporation, Western Atlas Logging Services, Halliburton Energy Services, Electromagnetic Instruments, Inc., U.S. Environmental Protection Agency, and OYO Corporation..

Continuity Testing Using Guided Waves

RESEARCH OBJECTIVES

Some geological structures are capable of trapping and transporting a wave energy very long distances without significant attenuation. The trapped waves, which are usually called guided waves, have an interference nature and propagate in the form of different types of compact wave disturbances (modes) with frequency-dependent velocities of propagation. Excitation of modes is rather sensitive to frequency content of the source, its positioning inside the waveguide, and velocity contrast between waveguide and heterogeneity within the waveguide. For seismic waves one of the most important examples of a waveguide structure is a continuous low-velocity layer. So far, the most explored case of seismic waveguide energy belongs to coal seam exploration because of its very high contrast and relatively easy access. At the same time, low-velocity layers can be found in the sedimentary sequences common to most gas and oil exploration sites. Testing of the continuity of such layers is important because it allows us to define parameters for reservoir characterization. The use of regular body waves for this purpose is restricted since they tend to propagate inside of high-velocity structures and are highly dissipative. Therefore, rather dense and expensive drilling is required in order to get a good signal.

The Gas Research Institute has funded research to develop forward numerical models to predict the full

V. Korneev, L. Myer, and K. Nihei

waveform response of guided waves excited in a geological waveguide. As part of this research, we intend to find answers to the following ques-

tions: Do different typical geological disturbances reveal distinctive patterns in guided waves signatures? How can guided waves be used to detect a presence of disturbance in a waveguide? Can guided waves be used to characterize the continuity of low-velocity reservoirs at the distances exceeding typical interwell distances for gas wells in gas and oil production regions? These and related problems have been the research subject of our work on reservoir continuity testing using guided waves.

APPROACH

We used a numerical approach to investigate characteristics of elastic wave propagation in a variety of complex media representing different typical cases of geological waveguide disturbance. A new elastic 2D finite-difference code was developed as a research testing tool for wave field simulation. Computed synthetic results were analyzed in both time and spectral domains. One of the analysis approaches used was backward propagation migration. Numerical propagation of the recorded data is done in reverse time, simulating a "rewind" procedure for wave propagation process.

Another approach accounts for both particle motion and wave symmetry in recorded data. Waveguide distur-

Figure 1. (a) Wave field distribution and (b) a WDDM processing result for the undisturbed waveguide.

Figure 2. (a) Wave field distribution and (b) a WDDM processing result for the waveguide disturbance of the tectonic fault type.

bances are detected using symmetry properties of the modal structure of normal and leaky modes in a waveguide. A source located in the center of a low-velocity layer of constant thickness will generate a guided wave that is either purely symmetric or antisymmetric with respect to the centerline of the layer. However, if a geologic disturbance such as a fault, pinchout, or washout interrupts the waveguide, the symmetry of the propagating wave motion will be disturbed. Berkeley Lab has developed a patented processing algorithm called a waveguide disturbance detection method (WDDM) to characterize the symmetry of a guided wave. To utilize a modal structure of the guided waves, WDDM separates low-index spatial harmonics of a wavefield that correspond to the most stable normal modes. These are recorded on an array of receivers. The presence of large low-order wavenumber peaks in tall symmetric and antisymmetric components is a direct indication that the waveguide contains a discontinuity.

RESULTS

To date, we have used finite difference simulations of wave propagation in continuous, disturbed, and discontinuous waveguides. Figure 1 is an example of such a simulation. The upper part of the figure illustrates a wavefield produced by a single point source located in the center of a 15-m-thick, continuous, horizontal, low-velocity layer. There is a 20% velocity contrast between the layer and surrounding rock. The line of the symmetry is the centerline of the waveguide. The lower part of the figure graphically illustrates the results of WDDM processing for an undisturbed low-velocity layer. The results show how the total propagation energy is partitioned among the symmetric and antisymmetric components of both the x and z particle motion components and pressure. The propagation energy available in each of these symmetry components is then further subdivided to reveal how energy is distributed among the first four normal propagation modes. In this example of a continuous waveguide, most of the energy is contained in the symmetric x and pressure components; whereas the antisymmetric z component contains a relatively small amount of energy.

Figure 2 shows a simulated waveguide that is offset by the fault. The WDDM results at the bottom of the figure illustrate the value of this processing technique. Although guided wave propagation energy propagates across the fault, the total propagation energy is distributed very differently from that expected in a continuous waveguide. This example shows that energy is more evenly distributed among symmetric and antisymmetric modes in all of the components: x, z, and pressure.

A variety of similar models have been used to characterize other geologic features such as lenses, pinchouts, splits, thickening and thinning, and

dipping beds. WDDM analysis of each of these models has shown that each type of geologic disturbance yields a characteristic symmetry component and mode signature. A backward propagation migration procedure was applied for a number of models simulating a channel washout disturbance. The final image gave good quality indication of the channel position and depth.

Field tests scheduled to take place in mid 1998 will be performed at Union Pacific Resources Stratton Field in South Texas, which is known to host low-velocity waveguides. These tests are also designed to test and verify the theoretical ability of guided waves to propagate at distances substantially exceeding those proven to be practical for regular body waves. If successfully detected, the guided waves will be the only seismic waves providing information on stratified geological structures. In preparation for the field data processing, a number of numerical tests were computed for the models representing real velocity logs. The results reveal an important property of real waveguides — low-frequency leakage due to the presence of finite thickness high-velocity layers in the waveguide bounding halfspaces. This effect is related to the “tunnel” effect in quantum mechanics, which describes a penetration of low-energy particles through a potential barrier. However, the elastic case is more complicated because of the presence of two types of waves (p- and s-) in a medium.

SIGNIFICANCE OF FINDINGS

Research results revealed distinctive patterns in different types of waveguide disturbance signatures. The ability to predict the characteristics of guided wave signals is a necessary precursor for inverse signal analysis techniques required to understand crosswell seismic data acquired in the field. Polarization WDDM analysis provides a tool for fast waveguide testing in real time and can be easily incorporated into field data processing packages. Low frequency leakage phenomena must be investigated to provide an understanding of field data. It is anticipated that the test results will demonstrate that continuity logging can become an important and commercial tool for reservoir characterization.

RELATED PUBLICATION

Parra J. O., L. R. Myer, K. T. Nihei, V. A. Korneev, and A. W. Gorody, Guided seismic waves for reservoir characterization, *GasTIPS*, 3(3), 11-18, 1997.

FUNDING

This work has been supported by the Gas Research Institute.

High-Resolution Reservoir Structure from Dynamic Data

RESEARCH OBJECTIVES

Understanding the nature of flow within a reservoir is key to optimizing oil extraction. Controlling factors for flow are the permeability and porosity distributions within the reservoir. Unfortunately, very little of the data gathered at oil and gas fields is directly related to reservoir flow. One useful data type gathered systematically in all fields is the components of the fluids produced at a well: the ratios of oil, water, gas, etc. The ratio of water to oil and water, the water-cut, is one such ratio routinely gathered in oil fields undergoing water flood. It is this ratio that determines if the well is economical and should be maintained or shut down. However, the relationship between water-cut and the porosity and permeability structure of a reservoir is highly nonlinear, governed by the equations of multiphase flow, and is only now being used to infer permeability variations between producing wells. The inversion of multiphase flow data is difficult and computationally intensive.

Inferring reservoir structure from dynamic data, such as the water-cut, generally requires an order of magnitude more of calculations than does forward modeling. By forward modeling we mean simulation: one is given a model of reservoir structure with the task of predicting what would be observed during production. As an illustration, consider the problem of estimating the distribution of permeability in a reservoir based upon water-cut observations. During water flooding a flow field is set up between producers and injectors. At the producing wells the proportions of water and oil are measured. Calculating the water-cut at the production wells can be done using finite difference, finite element, or streamline approaches. Depending on the sophistication and assumptions, the calculations can be substantial. The inverse problem of using the water-cut data to estimate the spatial distribution of reservoir permeability requires the repeated solution of the forward problem of reservoir simulation. For example, most formulations of the inverse problem require computation of the sensitivity of water-cut concentration to changes in model parameters. That is, we must compute the change in the water-cut at an observation point induced by a deviation in subsurface hydrologic properties, such as porosity and permeability. Currently, there are three main approaches for estimating sensitivities: perturbation methods, direct algorithms, and adjoint state methods. Each approach has distinct advantages and drawbacks, but all require either extensive computation and/or significant code development. In geophysical imaging there are equivalents to these three techniques for calculating sensitivities. For example, the adjoint state method has been coupled with numerical methods for electromagnetic and seismic wave propagation. As in the

D. W. Vasco and A. Datta-Gupta*

*Texas A&M University, College Station, TX

inversion of water-cut, the numerical approaches can require either substantial code development or intense computational burden, particularly for three-dimensional applications.

Thus, a large investment is required to conduct field-scale inversions for each data type. As shown below, the asymptotic approach described here leads to an extremely efficient formalism for subsurface imaging, applicable to three-dimensional problems. Asymptotic methods are effective in such fields as electromagnetics and optics, seismology, and fluid mechanics. For example, asymptotic approaches are now used in seismology to solve very large problems involving millions of arrival time data and hundreds of thousands of unknowns. The key point is that the sensitivities needed for solving the inverse or imaging problem result from a single forward run. Thus, the approach is orders of magnitude faster than current techniques, which typically require a large number of forward runs. Using the formalism, large-scale three-dimensional imaging problems may be solved in hours on a workstation, rather than days.

APPROACH

The phenomena of interest in reservoir modeling are described by a governing set of partial differential equations. A basis for the formulation of the reservoir imaging problem is an asymptotic expansion of solutions to these governing equations. In essence, an asymptotic representation emphasizes the rapidly varying spatial and temporal attributes of the solution. Distinct scalar equations governing arrival times and amplitudes are produced. In this section, we outline how the asymptotic approach is applied to the inversion of multiphase reservoir data to map variations in permeability over an oil field under water-flood conditions.

We begin with the equation governing the saturation of the wetting phase — a quasi-linear parabolic to hyperbolic partial differential equation. We are interested in the properties of a rapid variation in saturation, as might occur during the passage of a front of injected water. To this end, in the next section we shall consider a form of the solution in which the time scale of the saturation variation is explicit. The advantage of this representation is that the initial terms of the series represent rapidly varying (high-frequency) solutions, and successive terms are associated with lower frequency behavior. The propagation of a sharp front is best described by the initial terms of the sum.

In order to infer reservoir properties from dynamic data, we need to know how the data are changed if reservoir properties are perturbed slightly. That is, we would like to know how water-cut, for example, varies as reser-

voir permeabilities and porosities are perturbed. The equations describing the propagation of the water front, the streamlines, and the saturation amplitudes may be used to derive sensitivities. Using perturbation theory, we can compute the changes in water-cut due to deviation in reservoir structure.

RESULTS

In an actual application to over 40 tracer breakthrough curves at Hill AFB (Vasco and Datta-Gupta, 1998), the asymptotic algorithm has performed well, and we deem this approach to inversion a success. The technique proved to be extremely efficient: an inversion for porosity, permeability, and pressure gradient magnitude variations in 1,540 grid blocks took less than 1 hr on a standard workstation. In comparison with our previous work on the Hill AFB tracer data, the two-step linearized inversion out-performed a nonlinear conjugate gradient routine (Vasco et al., 1997), which found a local minimum and matched secondary peaks rather than the actual concentration peaks. A simulated annealing algorithm produced a somewhat better match than our asymptotic approach, but required orders of magnitude more computation (50,000 forward simulation runs).

SIGNIFICANCE OF FINDINGS

A reservoir model derived from static data such as geologic, well, and seismic data will result in fluid flow predictions that do not necessarily match the observed production history. Thus, the model needs to be improved further by integrating dynamic data such as multiphase production history, an untapped wealth of information on reservoir flow properties. Conditioning reservoir models with dynamic data typically requires the solution of an inverse problem. This can be computationally prohibitive, and has never been done for fine-scale reservoir descriptions consisting of several million grid cells. Our approach relies on a new technique for the inversion of dynamic data for reservoir permeability and porosity structure that requires the same order of computation as does the forward problem. Our forward model is a very general and fully three-dimensional streamline simulator that has been shown to be orders of magnitude faster than conventional numerical simulators. We compute parameter sensitivities (the change in the observed production data given a change in reservoir structure) using an asymptotic approach that exploits an analogy between the streamline modeling and ray tracing. In particular, the sensitivities are line integrals of simple functions along the streamlines. The sensitivities are an essential component of the inver-

sion procedure, and their computation can require N forward simulations, where N is the number of grid blocks representing the reservoir structure, usually in the range of 10,000 to 1,000,000. Our new asymptotic approach only requires one forward simulation to obtain the sensitivities for all N grid blocks. Thus, in one forward simulation we obtain all that we need to infer reservoir permeabilities from the production history. The resulting algorithm has reduced the time required to invert tracer data for three-dimensional reservoir structure from days to less than 1 hour (Vasco and Datta-Gupta, 1998).

The asymptotic approach is applicable under very common water-flood conditions for several reasons. First, the method of characteristics that is strongly tied to the asymptotic approach has been successfully applied to multiphase and shock front propagation problems. Secondly, streamlines and trajectories may be defined for a propagating water front and are found to be relatively unperturbed by the passage of the front. Finally, one-dimensional solutions along the streamlines, the Buckley-Leverett equation, are known. These one-dimensional solutions may be efficiently solved along streamlines in three-dimensions. The asymptotic approach can unite all of these methods and tie them to related approaches in electromagnetic and seismic wave propagation. The result is an efficient approach for imaging reservoir structure using oil field data.

RELATED PUBLICATIONS

- Vasco, D. W., and A. Datta-Gupta, Asymptotic solutions for solute transport: A formalism for tracer tomography, *Water Resour. Res.*, in press.
- Vasco, D. W., A. Datta-Gupta, and J. C. S. Long, Resolution and uncertainty in hydrologic characterization, *Water Resour. Res.*, 33, 379-397, 1997.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program; by the Associate Director of the Office of Basic Energy Sciences, Division of Engineering and Geosciences; and by the Assistant Secretary for Fossil Energy, Office of Oil Gas and Shale Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. All computations were carried out at the Center for Computational Seismology and the National Energy Research Scientific Computing (NERSC) Center of Berkeley Lab.

Prediction of Transport Properties for Reservoir Rock Using the Pore-Level Network Model

P. Huang and L. Myer

RESEARCH OBJECTIVES

The purpose of this research is to develop a method to determine the relative permeability of reservoir rocks from their microscale pore structure. The pore structure of rock is characterized by stochastic parameters such as the porosity, pore-size distribution, spatial correlation in pore sizes, and geometric parameters such as pore geometry, connectivity, and throat geometry. These parameters are determined from images of pore-scale microstructure. The rock specimen used for the analysis can be a drill core or even drill cuttings that are continuously produced during a drilling operation. In the latter case, if the permeability of the rock is determined by examining the pore structure of drill cuttings, on-site real-time decisions can be made from drill cutting analysis.

Measured pore structure parameters are used to construct a regular cubic network model, where a pore is represented by a sphere, and channels that connect neighboring pores are represented by variable cross-sectional tubes. Results of the numerical simulations for models with measured pore structure parameters have been compared with experimental results for relative and absolute permeability and capillary pressure. These comparisons demonstrate applicability of the numerical technique to predict the transport properties of porous rock from pore-level information.

APPROACH

A stochastic model is chosen to represent the distribution of pore sizes measured from thin section images of rocks. Using the stochastic model, pore diameters that follow specific distributions (normal distribution, log-normal distribution, and exponential distribution) are generated for the network. The size of the pores can be spatially correlated by applying the spectral representation theory to the stochastic generation of the pore diameters. The diameter of a throat is assumed to be some fraction of the diameter of the smaller of the two pores connected to each throat.

Flow in a single circular tube is assumed to be laminar and to follow the Poiseuille law. Fluid flow in the network is analogous to electrical current in a circuit. Kirchhoff's current law and voltage law are applied to the mass balance for each node (pore) and pressure balance for each loop in the network. Permeability of the network can be derived from Darcy's law as long as the relationship between pressure drop and flow rate are obtained.

Partial saturation in the network is accomplished by simulating a nonwetting invasion process. The network is initially fully saturated with the wetting phase, and the capillary pressure is increased from a low initial value in small increments. If the radius of a given tube, which is connected to the invading phase, is larger than the critical radius r_c , given by the Young-Laplace equation, it will

Figure 1. Comparison of simulated relative permeability with experiments performed by Maloney (1993).

immediately be invaded. If a tube (representing a throat) is occupied by a nonwetting phase, the two pores at each end are always invaded immediately by the nonwetting phase. Trapping is simulated. However, a wetting film is assumed to exist along all internal surfaces of the porous medium, so the residual wetting phase saturation at the end of invasion simulations is zero.

RESULTS

Initial simulations used mercury injection data to extract the mean diameter of the pore throats instead of thin section information, which was not yet available. Absolute permeability simulation was done for eight different rocks representing a range of five orders of magnitude in intrinsic permeability. The simulations used a cubic network of 32 pores in each direction. The overall porosity of the network was not equal to the porosity measured in the laboratory. Simulated results are very close to those obtained from experimental data.

Relative permeability simulation was done for Fontainebleu sandstone using a sample of 8% porosity and measured intrinsic permeability of 65mD. For this sample, thin section images were analyzed, yielding an exponential pore size distribution.

Simulation results are found to be in good agreement with the experimental results given by Maloney (1993), as shown in Figure 1.

SIGNIFICANCE OF FINDINGS

The network model is able to predict the flow properties based on the pore-level information. It has been validated by comparison with measurements of oil/brine relative permeability and intrinsic permeability. Precise pore-level data are the key factor for successful prediction of the flow properties of reservoir rock.

RELATED PUBLICATIONS

Huang, P., L. R. Myer, Study of the effects of pore structure on flow properties of porous media by using pore-level network model, in *Proc. of the AGU 1997 Fall Meeting, San Francisco, California, December 8-12, 1997*, American Geophysical Union, Washington, D.C., 1998.

Huang, P., G. Yang, L. R. Myer, and N. Cook, Simulation of capillary hysteresis in drainage and imbibition process, *Int. J. Rock Mech. & Min. Sci.*, 34, (3-4), paper 135, 1997.

REFERENCE

Maloney, D., Reservoir-condition special core analyses and relative permeability measurements on Almond Formation and Fontainebleu Sandstone rocks, NIPER-712, National Institute for Petroleum and Energy Research, Bartlesville, Okla., 1993.

FUNDING

This work has been supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Laboratory Technology Research Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Detection and Characterization of Hydraulic Fractures in Oil Reservoirs

T. W. Patzek and A. De

RESEARCH OBJECTIVES

An optimal water injector delivers the highest possible rate without causing uncontrolled or excessive fracturing of the reservoir. Over

time, constant injection rate at constant pressure causes, albeit inadvertently, hydrofracture extension and reservoir damage. To understand the response of a fractured reservoir to fluid injection, we must measure the dynamics of hydrofracture growth. As we have demonstrated in this project, only then can we operate the injection wells successfully, and prevent catastrophic hydrofracture extension, reservoir damage, and well failure.

As we have shown elsewhere, optimal control of injection pressure for smooth and unsupervised well operation requires continuous estimation of the state of hydrofracture as well as the history of hydrofracture growth. Since we cannot characterize the hydrofracture directly, a model-based "observer" must be designed to feed the optimal controller. The optimal controller will make it possible to grow injection hydrofractures from small initial sizes and, hence, significantly lower the cost of initial fracturing jobs. It may also control casing deformation. Impulse response of a dynamic system is routinely used to build mathematical models based on the observed system data. Once a mathematical model is available, the impulse system response can be used to determine the model parameters. In the eighties, Holzhausen et al. used impedance analysis to determine the hydrofracture closure pressure and its dimensions under shut-in conditions. In their analysis, the fractures were modeled as *lumped* capacitance and resistance in series. We doubt that such a simplified representation of the hydrofracture is sufficient for optimal injector control. Hence, we will use a *distributed* model.

APPROACH

In accordance with objectives, the research has proceeded in two broad areas. First, we have developed a model-based observer for the dynamic characterization of hydrofractures. The proposed observer will detect and characterize hydraulic fractures. We expect that a "smart" controller with a model-based observer will lead to increased efficiency of injection, reduced operator intervention, and lower well failure rate.

Second, we have analyzed injection and production data to characterize the oil field in general, and establish the growth history of hydrofractures in particular. An interactive reservoir analyzer has been developed, which allows us to investigate the injector-producer interactions and relates the injection and the production data to the evolution of hydrofractures.

Model-Based Observer of Hydraulic Fractures. The first step in the development of the observer is to construct a model of the hydrofractured well that captures its geometry and the

physical properties of the fluids. Our research has shown that an injection well and its associated fractures can be modeled as a lossy transmission line network to incorporate the viscous losses in the wellbore tubing, perforations, and fractures. The model parameters for the well are determined completely by the well geometry and the fluid properties. Therefore, the only unknown parameters are those for the hydrofractures. The fracture characteristics can then be determined by matching the measured hydraulic impedance test response of a well with the simulated response. Alternatively, the well could be characterized through a model-based inversion of the transient response data.

Interactive Reservoir Analyzer. An interactive reservoir analyzer has been developed using a Matlab® environment. The analyzer lets us examine interactively the production and injection history of producers and injectors, respectively; the productivity and injectivity contours; and injector-producer interactions.

RESULTS

We have access to published and proprietary experimental data on the transient responses of several wells, with depths ranging from 600 to 9,000 ft. These experimental data were used to validate our model. Transmission-line network models were constructed for each of these wells. The transient responses of the networks were simulated using SIMetrix®, a commercial simulator of electronic circuits, in particular, transient, lossy transmission lines. The simulation results demonstrated that the transmission line network model captures the dynamics of the well-hydrofracture systems quite accurately (Patzek and De, 1998). We present here the results of two hydraulic impedance tests performed on an injection well in the South Belridge Diatomite, where the fracture was known to have grown twofold in the intervening period between the two tests. Figure 1 shows the two transient responses, along with the corresponding fracture sizes. We observe that the larger fracture causes a lower rate of attenuation of the pressure pulse, which implies that the dynamic characterization of the fracture is indeed possible through periodic impulse testing of the well-hydrofracture system.

We have developed an Interactive Waterflood Analyzer software that allows one to evaluate the performance of injectors and producers on a well-by-well basis or of the

Figure 1. The influence of fracture size on the impulse response of well-hydrofracture system.

reservoir as a whole. Figures 2 and 3 illustrate two software features. Figure 2 shows the response of oil production to waterflood. Figure 3 depicts the domain of influence of each producer in a field project.

SIGNIFICANCE OF FINDINGS

We have established that hydraulic impedance testing is a viable technique for the dynamic characterization of hydraulic fractures. We have also shown that a lossy transmission line network model sufficiently captures the dynamics of a wellbore-hydrofracture system. We are currently developing algorithms based on neural network and fuzzy logic for the reconstruction of the fracture growth history from the injection-production data.

Figure 2. Oil response to water injection.

Figure 3. Domain of influence of producers.

Together, these two techniques will provide information about the state of the hydrofractures, a crucial input to an optimal injection controller. Optimal control of injectors will lead to increased efficiency of injection, reduced operator intervention, and lower well failure rate.

RELATED PUBLICATION

Patzek, T. W., and A. De, Lossy transmission line model of hydrofractured well dynamics (presented at the SPE 1998 Western Regional Meeting, Bakersfield, Calif., May 10-13, 1998), SPE 46195, Society of Petroleum Engineers, Dallas, Tex., 1998.

FUNDING

This work has been supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Laboratory Technology Research Partnership Program; and by the Assistant Secretary for Fossil Energy, Natural Gas and Oil Technology Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Control of Fluid Injection into a Low-Permeability Rock

T. W. Patzek and D. B. Silin

RESEARCH OBJECTIVES

The purpose of this project is to design and implement a "smart" controller of water, steam, or CO₂ injection into a low-permeability fractured reservoir rock. Hydrofractured wells are normally used to inject fluids into such rock. These wells are equipped with automatic controllers of injection rate and pressure. The existing controllers fail during accidental hydrofracture extension and may exacerbate reservoir damage. In contrast, our smart controller "understands" the dynamics of fluid injection and remains stable even during catastrophic hydrofracture extension.

The need for such a controller comes from an observation that about one-third of the world's crude oil and a comparable fraction of oil reserves in the U.S. are locked in low-permeability reservoirs. The low-permeability fractured oil reservoirs such as the Austin Chalk, the West Texas Carbonates, or the California Diatomites hold tens of billions of barrels of oil. The Diatomites represent the biggest oil resource in California and are essential to the survival of the oil industry in the state. Estimates of original oil in place are 10 billion barrels with typical primary recovery after 10 yr from 2.5 to 6%. Primary production leads to reservoir compaction and well damage that must be mitigated. In contrast, steam injection may increase ultimate oil recovery eightfold. Neither steam nor water can be injected into the low-permeability fractured diatomite without careful control.

APPROACH

We use mass-balance considerations in order to develop a model of fluid injection into a low-permeability rock. It turns out that an important term has been omitted in the model originally published in 1957 and attributed to Carter. This model has been widely used since then. By fixing this flaw and analyzing the impact of variable injection pressure, we were able to obtain another formulation of hydrofracture growth model. Our model is simpler, has a clear physical interpretation, and allows one to draw important conclusions, some of which are listed below.

The objective of the controller is to specify the injection pressure that forces the injection rate to keep to the desired target level. Therefore, the input to the controller consists of the results of fracture area measurements and the records of injection history. On output, the controller produces the injection pressure to be applied to the well.

For the controller design, we apply control theory and regularization methods. We characterize the control objectives by a quadratic criterion that consists of two terms. The main term estimates the deviation of the true injection rate from the reference. An additional term has

been introduced to improve controller stability. In order to construct an optimal control, three modes of admissible controls have been considered, reflecting the trade-off between system performance, stability of the solution, and simplicity of the resulting control.

RESULTS

A mass-balance model of hydrofracture growth during fluid injection, attributed to Carter, has been corrected, extended to the case of variable injection pressure, and presented in an equivalent simplified form. The growth of fracture area at constant injection rate is expressed in terms of two easily measured field parameters, the early "injection slope" in linear transient flow, and the average injection rate.

We show that fluid injection above a reasonable minimum rate must lead to hydrofracture extension. Ultimately, fracture growth is inevitable, regardless of the mechanical design of injection wells and injection strategy. We also show that water injection leads to less severe formation damage and fracture extension than steam. By analyzing the thermal and pore stresses, we demonstrate that steam injection may lead to the creation of horizontal fractures, vertical fracture extension, and reservoir damage.

Using control theory methods, we have designed and analyzed three modes of injection control. A distinctive feature of the controller proposed here is that the value of the injection pressure it produces is computed through a model of the injection process. It automatically takes into account the fracture area changes and decrease of the pressure gradient at the older parts of the fracture caused by the saturation of the surrounding formation with the injected liquid.

The convoluted nature of the processes does not allow one to obtain the optimal solution as a genuine feedback control and to design the controller as a standard closed-loop system. At each time, we have had to account for the data over the entire history of injection. However, the feedback mode may be imitated by designing the control on a relatively short time interval, which slides with time. When an unexpected event happens, e.g., when we observe an abrupt fracture extension, a new sliding interval is generated and the controller is promptly refreshed. An example of controller simulation is shown in Figures 1-3. In spite of the large fracture extension shown in Figure 1, the target cumulative injection and the actual cumulative injection are not distinguishable in Figure 2. The optimal injection pressure produced by the controller is shown in Figure 3.

Figure 1. Fracture area versus time.

Figure 2. The target cumulative injection is followed exactly by controller-enforced injection.

Figure 3. Reaction of the optimal injection pressure to a fracture extension.

SIGNIFICANCE OF FINDINGS

The fractured, low-permeability Diatomites represent a vast oil resource, with some 10 billion barrels of oil in place. This resource is being developed using secondary and enhanced oil recovery techniques. An improper injection strategy may result in irreversible reservoir damage caused by an overpressure or a wrong reaction to unexpected fracture failure.

A "smart" controller has been designed to stabilize fluid injection automatically, even in the case of catastrophic fracture extension. Therefore, implementation of the controller will help to protect hundreds of millions of dollars in hardware investments and will serve to protect the environment. The most important conclusion is that one cannot base one's strategy only on the current measurements. Instead, one has to take into account the whole history of fluid injection in order to make the right decisions.

FUNDING

This work has been supported by the Assistant Secretary for Fossil Energy, Natural Gas and Oil Technology Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Oral Bioavailability of PAHs from Solid Environmental Matrix

RESEARCH OBJECTIVES

Ingestion is a major pathway of mammalian exposure to residual polycyclic aromatic hydrocarbons (PAHs) in surface soils near petroleum-contaminated sites. Risk assessment of this type of contaminant exposure has traditionally been greatly simplified by assuming that all contaminants in ingested soil are completely absorbed into the bloodstream, i.e., are 100% bioavailable. This simplified assumption has been used conservatively to assure the protection of public health, particularly for those who have been involuntarily exposed to the contaminants. However, for sites that were contaminated years ago, the assumption of 100% bioavailability could overestimate the ecological risk and increase remediation expenses substantially with negligible reduction of risk. Field and laboratory studies have demonstrated that the bioavailability of contaminants from soil to microorganisms and small animals can be significantly less than 100%. Furthermore, contaminant bioavailability and toxicity to these ecological receptors can diminish as the contaminants are weathered.

The question addressed in this study is, can one transfer the above observations of diminishing bioavailability to the exposure to other mammalian receptors? This question cannot be readily answered because of the lack of data and assessment protocols. To overcome these difficulties, Berkeley Lab is participating in a research program on gastrointestinal (GI) uptake of weathered petroleum

H.-Y. N. Holman, Y. Mao,
and R. Goth-Goldstein

hydrocarbons, which is jointly initiated by the U.S. Department of Energy and the Petroleum Environmental Research Forum (DOE/PERF). Our goal is to develop a physiologically based

in-vitro extraction method that can be used to (1) quantify the bioavailability of organic hydrocarbons in the mammalian gastrointestinal (GI) tract; and (2) address the above issue on the diminishing bioavailability of weathered organic contaminants to mammal receptors.

APPROACH

To achieve this goal, we have selected humans as our mammalian model. Bioavailability of ingested contaminants refers to the fraction of contaminants that could enter the systemic circulation in an unaltered form (i.e., parent form). Although many organic contaminants may be metabolized at the wall of the gastrointestinal tract and liver before they enter the systemic circulation, these metabolites in the systemic circulation will not be included here.

A three-component, physiologically based *in-vitro* human model (Figure 1) was developed and calibrated according to existing *in-vitro* methods from areas of nutrition and pharmacology. It was employed to estimate the oral bioavailability under typical physiological conditions of soil-bound PAHs from 10 different petroleum-contaminated sites. The soil texture ranged from sand to silty clay (Figure 2); the petroleum

Figure 1. A schematic diagram of the three-component GI extraction protocol.

Figure 2. Range of soil texture.

hydrocarbons ranged from jet fuel to crude oil; and the total recoverable petroleum hydrocarbons ranged from 5.3 ppm to 81,000 ppm. Oral bioavailability estimated *in vitro* and PAHs sorption-desorption parameters measured in batch experiments, together with data obtained from the characterization of contaminant mixtures and properties of soil samples, were integrated, analyzed, and interpreted. Relations among these measurements, together with knowledge from pharmacokinetics and soil chemistry, were used to identify the critical mechanisms that control the uptake of ingested residual PAHs into mammalian circulation.

RESULTS

Oral availability to humans depends on the composition of the GI fluids. Under typical physiological conditions after a fat-rich diet, oral availability of soil-bound PAHs increases almost linearly with the percentage of silt and clay (Figure 3). The influence of soil mineralogy and soil organic carbons is not obvious.

The fraction of the orally available PAHs that crosses the human intestinal cells and enters the human systemic circulation decreases with increasing PAH lipophilicity.

Percentage of Ingested Soil-Bound PAHs that are Available to Epithelial Cells of the Human Small Intestine as a Function of Soil Texture

Figure 3. PAH oral bioavailability as a function of soil texture.

SIGNIFICANCE OF FINDING

We have developed and calibrated the first *in-vitro* physiologically based extraction protocol that can realistically and practically estimate human oral exposure to PAHs in surface soils at petroleum-contaminated sites. Our *in-vitro* measurements provided the first evidence that, under normal physiological conditions, PAHs in ingested soils are not completely absorbed into the bloodstream. This observation implies that the prevailing practice of complete bioavailability in exposure and risk assessment may overestimate the ecological risk and increase remediation expenses substantially with negligible reduction of exposure and risk to humans.

RELATED PUBLICATION

Holman, H.-Y. N., Y. Mao, and R. Goth-Goldstein, Bioavailability of organic compounds from solid environmental matrices, in *Proc. of the 18th SETAC Symp., Bridging the Global Environment: Technology, Communication, and Education*, 335, Soc. Environ. Toxicology and Chemistry, Pensacola, Fla., 1997.

FUNDING

This work has been supported by the Assistant Secretary for Fossil Energy, Natural Gas and Oil Technology Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Selenium Cycling in Intertidal Wetlands in the San Francisco Estuary

P. T. Zawislanski, H. S. Mountford,
E. Gabet, S. Chau, and H. W. Wong

RESEARCH OBJECTIVES

Since 1994, we have been investigating selenium (Se) geochemistry in the tidal wetlands of the Carquinez Strait. This is in response to concerns about elevated selenium Se concentrations in water, sediments, and biota of the San Francisco estuary. Oil refineries in the northern part of the estuary contribute approximately 60% of the total Se input to the Estuary waters, with most of the remainder coming from the San Joaquin River. Research to date in Berkeley Lab's Earth Sciences Division has covered such issues as Se deposition, distribution, and fractionation in wetlands sediments; uptake by plants; adsorption onto plant litter; uptake by clams; and isotopic fractionation. Processes by which selenium is introduced into and potentially released from the sediment system and the characterization and quantification of Se fluxes have been the focus of the research program in 1997. The need to measure Se fluxes into and out of intertidal marsh sediments is related to the fact that intertidal wetlands support a wide diversity of birds, some of them threatened or endangered, which feed at the sediment-water-air interface. Therefore, the uptake of contaminants by these birds, whether directly via ingestion of water, or indirectly via the consumption of benthic organisms, is determined by dissolved and adsorbed concentrations at the sediment-water-air interface. Two intertidal systems were selected, one in Martinez Regional Park and another in Benicia State Park, both downstream of major oil refinery effluent discharge points. Both sites were chosen because of the presence of a relatively undisturbed intertidal zone, complete with a *Distichlis spicata*/*Salicornia* sp. dominated marsh plain, a *Scirpus* sp./*Typha latifolia*/*Spartina foliosa* lower marsh, and an extensive mudflat.

APPROACH

Selenium fluxes into the intertidal system include deposition with settling particulates, immobilization of dissolved Se onto both sediments and plant matter via reduc-

tion and/or adsorption, uptake by benthic organisms via filtration of particulates, and uptake by algae. Selenium fluxes out of the sediment include sediment resuspension and diffusion into overlying waters, and plant and microbial volatilization. Deposi-

tion and resuspension of Se with particulates were studied using a set of sediment traps that were used to both measure sedimentation rate and collect samples for analysis to determine the Se mass flux. Immobilization of Se due to reduction of dissolved Se was studied under laboratory conditions. Adsorption of Se onto plant matter, specifically plant litter, was investigated in the field using a set of mesh bags containing harvested samples of the major wetland plant species. Diffusion of Se out of the sediment was estimated based on dissolved Se concentration gradients in pore water and surface water.

ACCOMPLISHMENTS

Sediment deposition was found to provide the largest flux of selenium into the wetlands. The distribution of Se on the settling particles was found to be very close to that observed in cored sediment samples, although it was lower in the topographically highest and organically richest part of the marsh, suggesting that an additional Se flux, likely a combination of adsorption and reduction of dissolved Se, was contributing Se to that part of the system (Figure 1). Mean Se concentrations on suspended particulates are around 1 mg kg^{-1} , indicating that a size separation of particles is occurring in the marsh-mudflat system. The peak in Se in the lower marsh (Figure 1) is due to a

large influx of plant litter, further enriched with Se due to adsorption. Pore-water concentrations of Se were about one order of magnitude higher than those observed in the overlying tidal water, suggesting a net flux of Se out of the sediments. Litter bag studies have shown conclusively that Se, and heavy metals, adsorb onto plant litter, with a net tenfold increase in Se concentrations. Selenium loss

Figure 1. Selenium on trapped sediments and surface sediments sampled in the Martinez wetlands.

Se fluxes (mg Se m ⁻² yr ⁻¹)					
	particulate deposition	particulate resuspension	plant litter adsorption	dissolved Se diffusion	Net Flux
marsh	1.5 to 3	0	0.05 to 0.5	≈(-0.5)	1.05 to 3
mudflat	0 to 15	0 to (-15)	0	≈(-0.5)	(-15.5) to 14.5

Table 1. Fluxes of Se into and out of marsh and mudflat sediment. Effluxes shown as negative numbers.

via sediment resuspension is more difficult to measure, although it can be said that this process need only be considered in the mudflats and not in any part of the marsh. Laboratory experiments showed that Se reduction and immobilization occurs only under stagnant water conditions, such as may be observed after high tide on the marsh plain. This flux will be greatest in topographic depressions and therefore is highly spatially variable. A summary of measured ranges of Se fluxes is shown in Table 1.

SIGNIFICANCE OF FINDINGS

All of the data support a model in which the accumulation of selenium in estuarine wetlands is influenced primarily by Se on suspended particulates and sedimentation dynamics. The ecological significance of such a cycle is considerable, given that sediments provide the primary exposure pathway to benthic organisms. Sediment Se concentrations are fairly uniform with depth, and given the amount of sediment recycling and redistribution, it is unlikely that reduction of Se levels in Carquinez Strait waters would result in a noticeable decrease in sedimentary Se in estuarine wetlands. Furthermore, Se concentrations at the ecologically sensitive sediment-water-air interface are going to be much higher than in the ambient water, a fact that will not, in the short term, be moderated by reductions of Se in refinery effluent. The results of these studies underline the need to intensify monitoring of the sediment-water-air boundary.

RELATED PUBLICATIONS

Zawislanski, P. T., and A. E. McGrath, Selenium cycling in estuarine wetlands: overview and new results from the San Francisco Bay, in *Environmental Chemistry of Selenium*, edited by W. T. Frankenberger and R. A. Engberg, Marcel Dekker, New York, N.Y., 1998.

Zawislanski, P. T., and A. B. Crawley, Selenium cycling study in the San Francisco Bay: partnership involving federal and state government and industry (presented at the SPE/EPA 1997 Exploration and Production Environmental Conference, Dallas, Tex., 1997), SPE 37885, Society of Petroleum Engineers, Dallas, Tex., 1997.

FUNDING

This work has been supported by the Assistant Secretary for Fossil Energy, the Natural Gas and Oil Technology Partnership Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098; and by the San Francisco Bay Regional Water Quality Control Board.

Response of Liquid-Dominated Geothermal Systems to Exploitation

A. Truesdell and M. Lippmann

RESEARCH OBJECTIVES

Documentation of the behavior of geothermal reservoirs under production is vital to efficient exploitation. On the basis of these field case studies, reservoir management procedures that might extend the commercial lifetime of a field and optimize the extraction of the heat stored in the subsurface could thus be developed. Cerro Prieto, in Mexico, is an ideal system for this purpose. The field has been under production since 1973, and its developer, the Comisión Federal de Electricidad, has been cooperating with LBNL/DOE in the area of geothermal energy since the late 1970s.

Cerro Prieto, the largest liquid-dominated geothermal field presently under exploitation worldwide, is about 30 km south of the California U.S. border. It is a hot (320–350°C) system with a total capacity of at least 780–800 MWe; which is hosted in sedimentary and metasedimentary rocks.

Electrical power generation began in 1973 with 75 MWe; by July 1981 the installed capacity was 180 MWe. In 1986–87, four 110 MWe units were put on line to bring the total capacity to 620 MWe, where it remains at present.

Over the last 25 years, large amount of geothermal fluids have been produced from the field (about 12,000 metric tons per hour during 1997) to supply steam to the power plants. This has resulted in a reduction of pressures and changes in reservoir processes, such as local boiling, phase segregation, steam condensation, fluid mixing, and dilution. In order to support reservoir pressures, injection of brine from the evaporation pond located west of the wellfield began in 1989. In recent years, the injection rates have been equivalent to about 20% of total production.

In spite of the large rate of mass (and heat) extraction, wells, continue to produce enough steam to satisfy the requirements of the power plants. This is largely due to the system's generally open boundaries that allow the natural recharge of the reservoir. The inflow of cooler and less saline

groundwaters does not occur everywhere. Recharge along the N–NW boundary of the present wellfield seems to be minor, but the lateral influx through the western and southern edges of the field, as well as vertical through two normal faults, is significant.

APPROACH

Initially, a multidisciplinary study approach was used to identify the main geological structures controlling the flow of fluid through the subsurface and to determine the physical and geochemical properties of the rocks and fluids of the geothermal system. Later on, as the activities of the field focused on the production of fluids and generation of electrical power, data collection was mainly restricted to the study of information obtained from new wells and in monitoring the physical and chemical characteristics of the produced (and injected) fluids. As a result, there is a large volume of wellhead information available (pressures, flow rates, enthalpies, and chemistry of liquids and gases), including isotopic data, that can be used to follow the history of individual wells, as well as that of the two main geothermal aquifers (the Alpha and Beta reservoirs).

RESULTS

The analyses of the well data indicate that the reservoir pressure drawdown caused by the exploitation of the field resulted in an almost immediate inflow of groundwaters into the western, shallower Alpha Reservoir. This is evident from changes in the chloride and silica content and isotopic characteristics of the produced fluids. It was shown that the waters invaded the Alpha Reservoir horizontally from the west and vertically down the normal, east-dipping Fault L.

In the 1980s the development of the field proceeded towards the east, where the deeper and much larger Beta Reservoir was encountered. Initially, groundwater recharge to this aquifer was believed to be only lateral, along the edges of the system, except perhaps to the north where there is an

Figure 1 Chloride concentrations in the Cerro Prieto Alpha Reservoir in 1982 (in ppm). Groundwaters enter down Fault L, reducing chloride in the center of the reservoir.

impermeable boundary. More recent chloride and isotope data, however, clearly indicate that the major recharge to the Beta Reservoir is by groundwater flowing down the normal, SE-dipping Fault H.

Geothermal fluids in the Alpha reservoir mixed with cooler waters even before commercial-scale fluid production began. This mixing was not uniform, as shown by the chloride content of fluids produced by different wells. In response to reservoir drawdown caused by exploitation, only local boiling occurs near most Alpha wells (i.e., no extended steam zone is formed). This is due to the lateral and vertical groundwater recharge that provides significant pressure support (essentially the reservoir responds as having a constant-pressure boundary).

The behavior of wells open in the Beta Reservoir is quite different and varies over the system. Until about 1985, before the new units came on line, production from this deeper reservoir was relatively small. However, because temperatures are higher and fluid recharge is more restricted than in the Alpha Reservoir, an extended boiling zone began to form very early. After 1986, some wells showed adiabatic steam condensation, others produced fluid enriched in chlorides due to boiling. Other wells in the Beta Reservoir present clear indications of the effects of horizontal and vertical groundwater recharge. Still others show mixing with the waters being injected along the western edges of the system.

Recently, on the basis of the chloride content in the produced fluids, the amount of fluid recharge at Cerro Prieto was estimated on a yearly basis. After 1983, more than half of the total Alpha Reservoir production was from groundwater recharging the system.

In the Beta wells the fraction of total production due to groundwater is much smaller than in the Alpha Reservoir. Initially, the results fluctuated from a thirtieth to a quarter of the total, but after 1985 the relative amount has been stable at between a fourth and a

Figure 2. Chloride concentrations in the deeper Beta Reservoir (in ppm). As in the Alpha Reservoir, groundwaters enter down a fault (Fault H, shaded) in the upper right of the figure. There is also a high-chloride anomaly in the bottom center from injection of evaporated reservoir water.

fifth of the total production. On the other hand, the amounts injected are about the same or somewhat less than the groundwater recharge into both reservoirs.

SIGNIFICANCE OF FINDINGS

The Cerro Prieto field case study confirmed that leaky reservoir boundaries help sustain production and extend the commercial lifetime of a geothermal field, but since recharge is mainly from cooler groundwater and injectate, the temperature of the reservoir rocks and fluids must progressively decrease. Thus, power plant design should allow for the use of

lower separation pressures as the exploitation of a geothermal field proceeds.

RELATED PUBLICATIONS

- Truesdell, A. H., and M. J. Lippmann, Effects of pressure drawdown and recovery on the Cerro Prieto Beta Reservoir in the CP-III Area, in *Proc. Twenty-Third Workshop on Geothermal Reservoir Engineering, Stanford University, 26-28 January, 1998*, 23, pp. 90-99, Stanford Univ., Stanford, Calif., 1998.
- Truesdell, A. H., M. J. Lippmann, H. Gutiérrez Puente, H. and V. J. de León, The importance of natural fluid recharge to the sustainability of the Cerro Prieto Resource, *Geotherm. Resour. Coun. Trans.*, 22, in press.

FUNDING

This work has been supported by the Assistant Secretary of Energy Efficiency and Renewable Energy, Office of Geothermal Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Advances in Numerical Simulation of Flow and Transport in Multiphase, Multicomponent Systems

K. Pruess, C. Oldenburg,
G. Moridis, and Y. S. Wu

RESEARCH OBJECTIVES

Numerical simulation of multiphase fluid and heat flow is a mature technology that is now routinely used in geothermal reservoir engineering, nuclear waste isolation studies, and environmental contamination problems. The general-purpose simulator TOUGH2 developed at Berkeley Lab is presently in use in more than 150 organizations in over 25 countries. Our continuing research aims at improving the description of flow and transport processes, enhancing the numerical efficiency for solving large problems on small computers, and generally increasing the utility of reservoir simulators as practical engineering tools.

APPROACH

Our enhancements of numerical simulation capabilities are primarily driven by application needs in different programmatic areas. Literature data have been used to develop more comprehensive descriptions of thermophysical properties of fluid mixtures. There is an increasing emphasis on modeling mass transport associated with fluid flows. We are currently in the process of assembling and documenting a series of program modules for the TOUGH2 code that will be released as a new Version 2.0 after suitable beta-testing by users inside and outside Berkeley Lab.

RESULTS

New process simulation capabilities include multiphase diffusion and dispersion, coupling between flow in reservoirs and wellbores, and precipitation and dissolution of solid phases. Here we highlight some of the major developments that are included in the new Version 2.0 of TOUGH2.

New Fluid Property Modules. The original TOUGH2, released in 1991, provided five different fluid property or "EOS" (equation-of-state) modules. Labeled "EOS1"–"EOS5," these included the main modules for geothermal and nuclear waste applications. The new Version 2.0 release of TOUGH2 includes improved versions of these five EOS modules, as well as several new fluid property modules (Table 1).

As an illustration of new process simulation capabilities available through these modules, we present results for production from a geothermal reservoir in which the reservoir fluid is a highly saline brine with dissolved CO_2 (see Figure 1). In response to production, the reservoir fluid boils, which increases the concentration of dissolved NaCl until its solubility limit is exceeded and precipitation starts. This reduces both reservoir porosity and permeabil-

ity. For the one-dimensional radial flow system simulated here, a similarity property should hold, according to which thermodynamic conditions in the reservoir depend on radial distance R and time t only through the similarity variable $x = R^2/t$. Comparison between results at different times plotted

in Figure 1 shows that this is indeed the case.

Module	Capabilities
EOS7	water, brine, air
EOS7R	water, brine, air, parent-daughter radionuclides
EOS8	water, "dead" oil, noncondensable gas
EOS9	variably saturated flow according to Richards' equation
EWASG	water, salt (NaCl), noncondensable gas (includes precipitation and dissolution, with porosity and permeability change)

Table 1. New fluid property modules for TOUGH2.

Coupled Wellbore Flow. Geothermal production wells typically operate at (nearly) constant wellhead pressures. As flow rate and flowing enthalpy change with time, wellbore pressure gradients and flowing bottomhole pressures will also change. From a conceptual point of view, the most straightforward way to describe production from geothermal wells is to set up and solve equations for flow in the reservoir and flow in the wellbore in a fully coupled manner. From a practical viewpoint, an alternative approach may be preferable in which the wellbore and reservoir simulations are performed separately. Flowing wellbore pressures may be represented by tables that can be generated through repeated running of a wellbore simulator ahead of the reservoir simulation. Such a tabular interpolation approach has been incorporated into TOUGH2. An example application to a coupled reservoir-wellbore system with boiling flow in the reservoir is shown in Figure 2. Production with constant downhole pressure predicts only a modest rise in enthalpy and a strong decline in well flow rate. The coupled calculation gives a much stronger rise in enthalpy, and shows that high production rates can be sustained throughout a 30-yr time period.

Improved Linear Equation Solvers. Most of the computational work in the numerical simulation of fluid and heat flow arises in the solution of large systems of lin-

Figure 1. Simulated thermodynamic conditions for 1D radial flow problem with salinity and noncondensable gas, plotted as a function of the similarity variable $x = R^2/t$. Results at 2×10^6 s are shown as lines, while the data at $t = 5 \times 10^6$ s are given as symbols.

Figure 2. Simulated flow rate (q), flowing enthalpy (h), flowing bottomhole pressure (P_{wb}), reservoir pressure in well grid block (P_{res}) for production from a boiling geothermal reservoir. Results obtained for constant bottom-hole pressure of $P_{wb} = 57.37$ bars, labeled q_c , h_c , and $P_{res,c}$, also shown.

ear equations. We have developed a new solver package called "T2SOLV," which adds the BiCGSTAB method and a banded direct solver to the previously available solution algorithms. T2SOLV also features a choice of different preconditioners for poorly conditioned matrices, such as matrices with mostly zeros in the main diagonal. Test calculations have shown that the new preconditioners can handle difficult flow problems for which the previous solver package failed.

SIGNIFICANCE OF FINDINGS

Recent advances enhance the scope, flexibility, and accuracy of modeling flow and transport in multiphase, multicomponent fluid systems. This allows better and more accurate solutions to many engineering problems, as well as novel applications in the geosciences.

We have established a homepage for the TOUGH family of codes (<http://www-esd.lbl.gov/TOUGH2/>), which provides information for established and prospective users on items such as code availability, new releases, applications, and workshops.

RELATED PUBLICATIONS

- Battistelli, A., C. Calore, and K. Pruess, The simulator TOUGH2/EWASG for modeling geothermal reservoirs with brines and non-condensable gas, *Geothermics*, 26(4) 437-464, 1997.
- Moridis, G., and K. Pruess, T2SOLV: an enhanced package of solvers for the TOUGH2 family of reservoir simulation codes, *Geothermics*, in press, 1998.
- Pruess, K., TOUGH2—An Update, in *Proceedings, 19th New Zealand Geothermal Workshop, Auckland, New Zealand, 1997*, pp. 211-216, New Zealand Geothermal Assoc., Auckland, New Zealand, 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Sharp Front Simulation for TOUGH2 Through Total Variation Diminishing Schemes

C. M. Oldenburg and K. Pruess

RESEARCH OBJECTIVES

Geothermal fluid production and reinjection cause strong advective flow in geothermal systems. The accuracy of simulated phase, concentration, and thermal fronts in strongly advective flow systems is degraded by numerical dispersion. Numerical dispersion tends to artificially smooth sharp fronts and leads to inaccurate predictions of the movement of boiling fronts and tracers. Numerical dispersion is particularly serious in strongly coupled problems where temperature controls boiling, which then strongly affects the flow. Inaccurate flow simulations can lead to poor decision making by the reservoir engineer.

In this research, we investigate the use of higher-order total variation diminishing (TVD) schemes for reducing numerical dispersion and improving the simulation of front propagation in geothermal reservoirs. Literature on the subject shows that TVD schemes reduce numerical dispersion for explicit finite difference methods in single-phase, isothermal, and mostly one-dimensional flow situations. The objective of this study is to incorporate TVD schemes into the implicit reservoir simulator TOUGH2 and investigate the potential of TVD schemes for reducing numerical dispersion for multiphase, nonisothermal, multicomponent, and two-dimensional flow situations such as those that arise in geothermal reservoir engineering.

APPROACH

The accurate approximation of quantities such as phase saturation, concentration, and temperature at the interfaces between gridblocks is essential for diminishing numerical dispersion in the integral finite difference method. Standard practice assigns interface values equal to the values at the upstream gridblock, a method known as full upstream weighting. Full upstream weighting generally overestimates the value at the interface thereby leading to numerical dispersion. A more accurate approximation of the interface values can be obtained

by considering two upstream gridblocks to make a higher-order approximation of the interface value. However, such higher-order schemes are known to produce spurious

oscillations in certain situations. To prevent spurious oscillations, flux limiters are applied in the form of a function that weights the interface value toward either the upstream value or the downstream value, depending on the ratio of the gradients between the upstream and downstream gridblocks. The criterion for limiting flux is based on the requirement that the overall differences in the values of saturation, concentration, or temperature due to advection should diminish with time, a criterion known as total variation diminishing, or TVD.

We have incorporated several higher-order schemes into TOUGH2 (two-point upstream, Van Leer, and Leonard) with flux limiters to make them TVD. We currently restrict grids to be either one- or two-dimensional with rectangular gridblocks. Within a TOUGH2 simulation, using higher-order TVD schemes entails finding the upstream gridblock, assuming locally one-dimensional flow, calculating the ratio of upstream to downstream gradient, applying the flux limiters, and approximating interface values of phase saturation, concentration, or temperature accordingly. Verification of the methods implemented through TOUGH2/EOS7R was presented in Oldenburg and Pruess (1997). The Leonard scheme (LTVD) has proven robust and accurate (Oldenburg and Pruess, 1998) and we present an example LTVD result below.

RESULTS

We demonstrate application of the LTVD scheme in TOUGH2/EOS7R to a test case involving injection and production from a two-dimensional subhorizontal fracture zone initially in single-phase liquid conditions ($T = 300^\circ\text{C}$, $P = 85.93$ bar). Production and injection wells are arranged in a five-spot pattern with 400-m well spacing. Cold water ($T \approx 30^\circ\text{C}$) is

Figure 1. Results at six months calculated using full upstream weighting.

injected at a rate of 16 kg/s (full-well basis), and production occurs at the same rate. Four kg of tracer are injected over a period of 10 days. One quarter of the five-spot pattern was discretized into 400 square gridblocks (20 x 20) of 10-m length per side.

Results after 6 months computed using full upstream weighting for phase saturations, component mass fractions, and thermal energy are shown in Figure 1. The temperature field shows the effects of

cold injection fluid entering the system, the tracer mass fraction field being advanced relative to the thermal field due to thermal retardation. The saturation field shows the development of a two-phase region due to lower pressure at the production well. The final plot gives breakthrough curves of temperature and tracer mass fraction at the production well. Initial tracer breakthrough occurs at about 6 months.

Results after 6 months computed using the LTVD scheme for phase saturations, component mass fractions, and thermal energy are presented in Figure 2. Comparing the two figures, we see generally similar results. However, note the relatively sharper fronts for temperature and especially for tracer mass fraction in Figure 2. The phase saturation front has evolved differently using LTVD and is not as far advanced. This is because the thermal front remains sharper in the LTVD calculation. The breakthrough curves highlight the differences in the schemes. Note first that more time steps are required using LTVD, thus increasing the cost of calculation. But further note the higher maximum and steeper limbs of the tracer breakthrough curve in Figure 2. Tracer would first be detected at significant concentrations after about 9 months. This sharper tracer breakthrough curve would allow a more accurate prediction of the arrival of the thermal front than the result computed using upstream weighting.

Figure 2. Results at six months calculated using the LTVD scheme.

SIGNIFICANCE OF FINDINGS

We find the higher-order TVD schemes to work well in the implicit TOUGH2 framework for one- and two-dimensional flow problems. Significantly sharper profiles of temperature and mass fraction were obtained relative to upstream weighting. Breakthrough curves for the reinjection problem show the improvement in accuracy that can be obtained by using the LTVD scheme.

RELATED PUBLICATIONS

- Oldenburg, C. M., and K. Pruess, Higher-order differencing for geothermal reservoir engineering, in *Proc. of the Twenty-Second Workshop on Geothermal Reservoir Engineering*, Jan. 27-29, 1997, pp. 303-308, SGP-TR-155, Stanford University, Palo Alto, Calif., 1997.
- Oldenburg, C. M., and K. Pruess, Higher-order differencing for phase-front propagation in geothermal systems, in *Proc. of the Twenty-Third Workshop on Geothermal Reservoir Engineering*, Jan. 26-28, 1998, pp. 127-134, SGP-TR-158, Stanford University, Palo Alto, Calif., 1998.

FUNDING

This work has been supported by the Assistant Secretary for Energy Efficiency and Renewable Energy, Geothermal Division, U.S. Department of Energy, under Contract No. DE-AC03-76SF00098.

Gas Flow in Porous Media with Klinkenberg Effects

RESEARCH OBJECTIVES

The objective of this work is to present a methodology to analyze steady-state and transient gas flow through porous media with Klinkenberg effects. Gas flow in porous media differs from liquid flow because of the large gas compressibility and pressure-dependent effective permeability. The latter, pressure-dependent permeability, may have significant impact on gas flow behavior, especially in low-permeability media, but it has been ignored in most of the previous studies because of the mathematical difficulty in handling the additional nonlinear term in the gas flow equation. This work provides a set of new analytical solutions developed for analyzing steady-state and transient gas flow through porous media including Klinkenberg effects. The analytical solutions are obtained using a new form of gas flow governing equation that incorporates the Klinkenberg effects. As application examples, the new analytical solutions have been used to verify numerical solutions, and to design new laboratory and field testing techniques to determine the Klinkenberg parameters. The proposed laboratory analysis method is also used to analyze data from steady-state flow tests of three core plugs from the Geysers geothermal field.

APPROACH

Physically, Klinkenberg effects are significant whenever the mean free path of gas molecules in porous media approaches the pore dimension, i.e., when most molecular collisions are with the pore wall rather than with other gas molecules. Gas permeability is then enhanced by "slip flow." Therefore, the Klinkenberg effect is expected to be greatest in fine-grained, lower permeability porous media with small pores.

If a subsurface system is isothermal, the ideal gas law applies, and gravity effects are negligible, then gas flow in porous media is described by a mass balance equation (Wu et al., 1996).

$$\nabla \cdot (\nabla P_b^2) = \frac{1}{\alpha} \frac{\partial P_b^2}{\partial t} \quad (1)$$

In Equation (1) we use a new variable, a pressure function

$$P_b = P + b \quad (2)$$

Y. S. Wu, K. Pruess, and P. Persoff

where b is the Klinkenberg factor, which is dependent on the pore structure of the medium and the temperature for a given gas. In Equation (1), α is a gas

diffusivity, defined as a function of gas pressure, P ,

$$\alpha = \frac{k_{\infty} P_b}{\phi \mu} \quad (3)$$

where k_{∞} is the absolute, gas-phase permeability under very large gas-phase pressure at which conditions the Klinkenberg effects are negligible, ϕ is porosity of the rock, and μ is gas viscosity.

The gas flow equation (1) is a nonlinear partial differential equation with respect to P_b^2 because of the diffusivity term α , (3), which is a function of pressure. In general, the gas flow governing equation (1) must be solved by a numerical method. However, it is possible to obtain certain analytical solutions, as proven in the following flow conditions. Under steady-state flow conditions, Equation (1) becomes linear and many analytical solutions can be directly derived. For the case of transient flow, Equation (2) may be linearized using the conventional approach for transient gas flow analysis, i.e., set

$$\alpha = \frac{k_{\infty} P_b}{\phi \mu} \approx \frac{k_{\infty} \bar{P}_b}{\phi \mu} \quad (4)$$

where $\bar{P}_b$ depends on the average gas pressure and is treated as a constant. Using the approximation of (4), Equation (1) becomes linear with respect to P_b^2 , and many analytical solutions can be obtained by analogy with heat conduction problems or slightly compressible flow problems, as demonstrated below.

RESULTS

For one-dimensional, linear, horizontal, and steady-state flow, the boundary conditions are: at the inlet ($x = 0$), a constant mass injection rate q_m per unit cross-sectional area is imposed, and at the outlet ($x = L$), the gas pressure, P_L , is kept constant. Then, a steady-state solution can be derived and is (Wu et al., 1998),

Figure 1. Exact Klinkenberg analysis plot for the three test samples.

	Traditional		Exact	
sample	$k_{\infty} (m^2)$	b(Pa)	$k_{\infty}(m^2)$	b(Pa)
36	1.66E-20	1.81E+06	1.61E-20	1.88E+06
9a	3.15E-20	1.23E+06	2.75E-20	1.43E+06
9b	4.38E-20	9.75E+05	4.02E-20	1.08E+06

Table 1. Analysis results of the laboratory tests.

$$P(x) = -b + \sqrt{b^2 + P_L^2 + 2bP_L + 2q_m\mu(L-x)/k_{\infty}\beta} \quad (5)$$

For horizontal radial transient flow towards a well, approximated as a line source/sink, with the gas flow Equation (1) and the linearization to the diffusivity α , (4), the problem is identical to the Theis solution in terms of P_b . The solution can therefore be written directly as

$$P_b^2(r, t) = P_{bi}^2 - \frac{\mu Q_m}{2\pi k_{\infty} h \beta} Ei\left(-\frac{r^2}{4\alpha t}\right) \quad (6)$$

where Q_m is the well mass pumping or injection rate of gas, and $P_{bi}^2 = (P_i + b)^2$, with P_i being the initial gas pressure.

The new analytical solutions can be used to (1) validate a numerical simulator of gas flow, (2) determine Klinkenberg coefficients from laboratory tests, and (3) analyze transient well tests. For example, an approach for determining both k_{∞} and β from laboratory tests can be derived using solution (5),

$$\frac{q_m \mu L}{\beta(P_o - P_L)} = bk_{\infty} + k_{\infty} \left(\frac{P_o + P_L}{2} \right) \quad (7)$$

To evaluate k_{∞} and β experimentally, a series of measurements are made in which the outlet pressure P_L is held constant while P_o inlet pressure is varied and the mass injection rate, q_m , is measured. Then $Y = q_m \mu L / \beta(P_o - P_L)$ is plotted against $X = (P_o + P_L)/2$, and k_{∞} and β are evaluated from the slope and intercept of the plot of Y against X . One example of the steady-state gas flow experiments conducted to test this approach to evaluate k_{∞} and β is as follows. Three rock core samples were obtained from a well in The Geysers geothermal field. The laboratory test data were interpreted according to the traditional Klinkenberg method and the new model (7), referred to as exact Klinkenberg analysis. The traditional method assumes the exact Klinkenberg analysis $X = (P_o + P_L)/2$ and $Y = q_m \mu L / \beta(P_o - P_L)$ are plotted in Figure 1 for the three samples. Table 1 summarizes the anal-

ysis results using the two methods. The results from these tests indicate the values obtained by the two methods are close.

SIGNIFICANCE OF FINDINGS

A general gas flow governing equation that considers the Klinkenberg effect has been derived by introducing a new pressure variable. Based on this new form of the gas flow governing equation, a set of new analytical solutions has been developed for analyzing steady-state and transient gas flow through porous media with Klinkenberg effects. As an extension of this work, additional analytical solutions for 1D, 2D, and 3D gas flow with the Klinkenberg effects can be readily derived. These analytical solutions will find applications in analyzing gas flow and determining soil flow properties in the unsaturated zone or in laboratory tests where Klinkenberg effects cannot be ignored. In order to demonstrate their applications, we have used the new analytical solutions to verify the numerical solutions of gas flow that include the Klinkenberg effect. Several new laboratory and field testing techniques are derived based on the analytical solutions for determining the Klinkenberg parameters of porous medium gas flow. These new laboratory and field test analysis methods are very easy to implement and more accurate to use.

RELATED PUBLICATION

Wu, Y. S., K. Pruess, and P. Persoff, Steady and transient analytical solutions for gas flow in porous media with Klinkenberg effects, LBNL-39499, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

FUNDING

This work has been supported by the Assistant Secretary of Energy Efficiency and Renewable Energy, Office of Geothermal Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Environmental Remediation Technology Department

Terry C. Hazen, Environmental Remediation Technology Department Head

The Environmental Remediation Technology Department is conducting multidisciplinary environmental cleanup research on characterization, monitoring, modeling, and remediation technologies. These projects are basic and applied, and include everything from molecular studies to full-scale field deployments. Generally, this year's work has fallen into three areas: (1) modeling, simulation, and instrumentation studies of hydrogeological processes; (2) subsurface contaminant barriers; and (3) watershed management and monitoring of metals.

HYDROGEOLOGICAL PROCESSES

Hydrogeological research has focused on studies modeling subsurface heterogeneity via the Iterated Function Systems (IFS) inverse method. The IFS inverse method does not impose the structure of an aquifer a priori, and yet there are few unknown parameters in the inversion. This allows a hierarchical structure for each trial hydrologic property that mimics the multiple scales of heterogeneity often seen in natural geological media. This work will allow better characterization of subsurface heterogeneity, thereby allowing better, faster, cheaper groundwater and vadose zone remediation.

Other studies have focused on conceptual models of liquid flow in fractured basalt. Characterization, monitor-

ing, risk, and ultimately remediation are dependent upon knowing how to predict water and contaminant flow in fractured rock. Many DOE waste sites are in fractured rock. Berkeley Lab cooperative research with Idaho National Engineering and Environmental Laboratory (INEEL) and Stanford University at the DOE Idaho Box Canyon site has demonstrated that conducting fractures dominate subsurface flow, along with lateral movement of water and solutes. This work will have a major effect on how DOE remediates and manages fractured rock waste sites.

Berkeley Lab and INEEL joint research at the DOE Idaho Box Canyon site on instrumentation for monitoring water flow and chemical transport in fractured rocks has led to the creation of new techniques for detecting underground barriers and leaks from underground tanks, ponds, landfills, and cribs. These new creations include a new borehole sealing technology, an acrylic casing that improves neutron logging, a TDR wave pad, miniature electrical resistivity probes, tensiometer tip placement method, new suction lysimeter installation techniques, and new thermistor installation techniques. These new instruments and installation techniques have greatly improved performance and shown that several types of measurements at different scales are necessary to monitor water and contaminant flow in fractured basalt.

Berkeley Lab has continued to develop the SELECT code for modeling subsurface contamination at hazardous waste sites. The most recent research in this area has demonstrated propagation of uncertainty from complex subsurface contaminant transport simulation through a sophisticated human exposure model, resulting in a stochastic description of human health risk. This will allow site risk assessment to be carried out so as to account for the uncertainty of the particular case under study. This also will allow a better overall risk assessment.

Field tests at McClellan Air Force Base for the Department of Defense have shown that Vadose Zone Monitoring Systems (VZMS) — instrument packages consisting of tensiometers, suction lysimeters, gas samplers, pressure transducers, and thermistors — permanently installed at multiple levels provide better monitoring of contaminants at waste sites. Indeed, the field tests at McClellan AFB have allowed identification of shallow sources of contamination that were very significant.

New research on partition coefficients of colloids at gas-liquid interfaces has shown very promising results that will permit quantification of surface excesses of the wide range of inorganic, organic, and microbial colloids, as well as molecular species complexed onto colloids. New techniques being tested in this research will allow quantification of colloid K values, which will provide understanding of a wide variety of natural and engineered systems.

SUBSURFACE CONTAINMENT BARRIERS

Berkeley Lab research on ferrofluids has shown that they have potential to effectively guide reactants and barrier liquids to contaminated target zones in the subsurface using electromagnetic forces. Ferrofluids also allow the use of geophysical methods to trace the movement and position of liquids injected into the subsurface. This research, combined with earlier work on viscous barriers for containment (patent pending), provides a great opportunity for containing, controlling, and predicting solvent, metal, and radionuclide contamination at waste sites, DOE's greatest environmental cleanup problem.

Berkeley Lab has also shown that electrical resistivity tomography is the method of choice in visualizing subsurface barriers but has been unable to show the quality of the wall due to the lack of electrical contrast between the grout and the clay in the sediment. Cross-hole seismic tomography was also found to be inappropriate due to injection of air during injection of the subsurface barrier.

WATERSHED MANAGEMENT AND MONITORING OF METALS

The Environmental Remediation Technology Department has researched selenium transport in the Grassland Water District for many years. Recent research has focused on better methods for compliance monitoring and management. The U.S. Bureau of Reclamation has sponsored this work in an effort to better manage selenium loading in the San Luis Drain. Microbial studies this year have shown that selenium in-transit losses occur and that the fate of this selenium is bed sediments. Manipulation of the microbial ecology of the Drain may stimulate the bioremediation of selenium from the water, thereby reducing the mass loading of selenium into the San Joaquin River.

PARTNERS AND FUNDING

The Department receives support from DOE programs in the Office of Energy Research, Offices of Biological and Environmental Research (OBER) and Environmental Management (EM). OBER supports the Natural and Accelerated Bioremediation Research program. EM programs include the Environmental Management Science Program (14 projects); the Subsurface Contaminant Focus Area (2 projects); and the Characterization, Monitoring, and Sensor Technology Crosscutting Program (2 projects). Support is also received from Department of Defense (Air Force Office of Scientific Research and McClellan AFB), California Environmental Protection Agency, and the U.S. Bureau of Land Management. Partners include the University of California at Berkeley, Stanford University, Westinghouse Savannah River Company, Idaho National Engineering and Environmental Laboratory, Lawrence Livermore National Laboratory, the University of Nevada, and the University of Illinois.

Hydrogeologic Characterization Using the Iterated Function System (IFS) Inverse Method

C. Doughty, J. Najita,
T. M. Johnson,* and D. Sahoo*

*University of Illinois, Urbana-Champaign

RESEARCH OBJECTIVES

There is a critical need to adequately characterize subsurface heterogeneity before attempting to implement groundwater or vadose-zone remediation activities. Our objective is to continue development of an inverse method for hydrogeological characterization based on Iterated Function Systems (IFS). The original version of the IFS inverse method (Doughty, 1995) analyzed pressure-transient data collected during interference pump tests. It may now be applied to spatial distributions of concentration data, which may arise from controlled tracer tests or naturally occurring geochemical tracers.

APPROACH

Geologic media are highly heterogeneous on many scales, making it difficult to infer field-scale properties from core or outcrop samples. A variety of idealized conceptual models are available for up-scaling, ranging from the assumption of stationarity and ergodicity at some scale, above which a stochastic treatment may be used, to the assumption of a fractal geometry in which variability repeats itself at all scales. Rather than relying on such idealizations, an alternative approach is to use hydrologic inversion to attempt to determine effective properties at the scale of interest in the first place, and eliminate any need to scale up. This approach requires that the scale at which parameter identification is done be chosen specifically for the application at hand. For example, for the cleanup of a contaminant plume in a groundwater aquifer, inverting interference-test or tracer-test data using wells in the vicinity of the plume would make sense. For understanding regional variability of a water-supply aquifer, an inversion of regional hydraulic head data or naturally occurring geochemical tracer data would be appropriate.

The inversion procedure typically consists of numerically simulating an interference test or tracer test using a mathematical model of the subsurface, assuming some distribution of hydrological properties (the parameters of the model), then comparing the calculated and observed pressure responses or breakthrough curves, and based on this comparison, modifying the parameters of the model and repeating the simulation. This procedure continues until a satisfactory match between the observed and calculated data is obtained, and the corresponding model parameters are accepted as providing a possible representation of the hydrological property distribution.

Three traditional methods for aquifer characterization are zone-based inversion, unstructured inversion, and geo-statistical analysis. In a zone-based inverse method, the flow domain is divided into zones by the modeler, and the

inverse method searches for the flow properties within each zone. This has the advantage of there being relatively few unknown parameters, but has the disadvantage of imposing the structure a priori, rather than letting it come out of the data. This makes the zone-based

method poorly suited for strongly heterogeneous systems in which the locations of heterogeneous features are unknown a priori. In an unstructured inverse method such as lattice annealing, the transmissivity of each grid element is allowed to vary independently. This has the advantage of not imposing any structure a priori, but leads to a huge number of unknowns, which decreases the efficiency and robustness of the inverse method. In the geo-statistical approach, one uses small-scale measurements (such as permeabilities measured from core samples) to define variograms that condition the spatial variability of a random field that represents the permeability distribution at the aquifer scale. Again, there are relatively few unknown parameters in this approach, but it is possible that the behavior measured at the core scale is irrelevant for characterizing flow at the aquifer scale.

The IFS inverse method is designed to make use of the best features of these approaches. It uses relatively few unknown parameters, but allows the structure to be determined as part of the inversion process; it focuses on behavior at the largest scale first, refining it to consider smaller scales of variability as necessary.

The key features of the IFS inverse method are illustrated in Figure 1. An IFS is a mathematical operation that acts recursively to construct an attractor, a set of points with a fractal geometry (first panel). Only a few parameters are required to describe an attractor created with an IFS, because the fractal geometry means that simple patterns, when repeated at multiple scales, can result in rather complex shapes. After an attractor is created, it is mapped onto the grid on which the flow equation is solved numerically (second panel). The user specifies a rule governing the action of each point of the attractor. In Figure 1, red points decrease transmissivity and blue points increase transmissivity, as illustrated by thinner or thicker grid lines (second panel), and by the color-coded transmissivity distribution (third panel).

During the inversion, the parameters of the IFS are varied, which results in different shaped attractors, which in turn results in different trial transmissivity distributions. Each trial transmissivity distribution is used to simulate the well test or tracer test with minimization of the overall mismatch between observed and calculated drawdowns or concentrations used to guide the choice of parameters of the IFS.

RESULTS

The flow and transport simulator used in the current version of the IFS inverse method is the finite element model TRINET, which calculates transient or steady-state fluid flow and solute transport on a lattice composed of one-dimensional finite elements. Although TRINET was originally developed to study flow and transport in fracture networks, the primary interest here is in applying it to simulate transport in a porous medium or a fractured medium being treated as an effective continuum. This requires developing expressions to relate TRINET parameters, which describe the hydrologic properties of the fracture network, to equivalent parameters that describe flow and transport in porous media. These expressions are then verified by comparing TRINET results to analytical solutions for flow and transport in porous media.

The IFS inverse method is currently being applied to a natural gradient tracer experiment conducted at the Columbus Air Force Base in Mississippi. Hydraulic conductivity at the site ranges over several orders of magnitude. Tracer is injected for 48 hr and the data consist of concentration distributions observed in an extensive array of multilevel monitoring wells extending 350 m down-gradient from the injection well, taken over the course of the experiment (approximately 440 days). The task of modeling the experiment is simplified by simulating transport in a 2D vertical section along the middle of the aquifer. Preliminary results suggest that the highly heterogeneous nature of the aquifer can be captured by the IFS inverse method.

An application of the IFS inverse method at a much larger scale is currently underway for the Snake River Plain Aquifer in Idaho. We are analyzing the spatial distribution of naturally occurring strontium isotope ratios in groundwater, which are indicative of

Figure 1. Key features of the Iterated Function System (IFS) inverse method.

water residence time in the aquifer. In this way, fast flow paths through the aquifer can be characterized, and in particular fast flow paths leading away from contaminated zones can be identified. For this application a flow and transport model that includes rock-water chemical reactions is needed. A version of the IFS inverse method incorporating the numerical simulator SUTRA, which considers the necessary processes, is being developed.

SIGNIFICANCE OF FINDINGS

Adequate hydrogeological characterization is critical for the success of subsurface remediation activities. The strengths of the IFS inverse method are that the structure of the aquifer is not imposed a priori, and yet there are few unknown parameters in the inversion. Restricting the search of hydrologic property distributions to those constructed with IFS's also has an advantage in that each trial hydrologic property distribution has a hierarchical structure, which mimics the multiple scales of heterogeneity often seen in natural geological media.

RELATED PUBLICATION

Doughty, C., Estimation of hydrologic properties of heterogeneous geologic media with an inverse method based on iterated function systems, Ph.D. thesis, Dept. of Material Sciences and Mineral Engineering, University of California, Berkeley, Calif., 1995.

FUNDING

This work has been supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098; and by the U.S. Air Force Office of Scientific Research.

Conceptual Model of Geometry and Physics of Liquid Flow in Fractured Basalt

RESEARCH OBJECTIVES

A key issue in environmental remediation of contaminated sites is the development of an appropriate conceptual model that describes the geometry and physics of fluid flow and contaminant transport. Many existing conceptual models have lead to significant errors in predictions and planning of remediation efforts because the numerical models used to predict flow and transport behavior and to design the remediation system were based upon incorrect conceptual models. The purpose of this investigation is to develop a conceptual model for fractured basalt based on the results of lithological studies and field tests conducted at a fractured basalt site near the Idaho National Engineering and Environmental Laboratory (INEEL) in Idaho. The conceptual model is especially important and difficult to develop because it must incorporate variably saturated fractured rocks of the vadose zone with discrete zones of perched groundwater with extreme contrasts in permeability between rubble zones, fractures, and matrix.

APPROACH

The primary approach of this project was to independently evaluate the geometry and physics of flow, and then combine these data into a conceptual model of flow and transport in fractured basalt. Investigations were centered on a detailed site characterization and a series of ponded infiltration tests conducted at an experimental site at Box Canyon in the Eastern Snake River Plain near INEEL. Site characterization consisted of various borehole logging techniques along with fracture mapping of a nearby cliff face. A series of infiltration tests with a potassium bromide tracer were conducted in a 7×8 m pond, including a 2-week test from August 27 to September 9, 1996, and a series of four pulsed infiltration tests from

September 11 to November 3, 1997.

RESULTS

The geometrical model of flow in basalt is based on borehole data and a fracture map inferred from observations on the Box Canyon cliff face. Borehole data provided information

about the types of fractures, the depth of soil infill in the fractures, the existence of a central fracture zone within the upper basalt flow, and the location of a rubble zone at the base of the upper basalt flow. The fracture map provided an illustration of the fracture spatial distribution, persistence, as well as the size and shape of fracture-bounded blocks. A map of the fracture pattern in the upper basalt flow as it is exposed on the side of the cliff at Box Canyon is shown in Figure 1. As can be seen from this map, the basalt flow is divided into an upper and lower zone of distinctly different fracturing, which is probably due to different cooling rates and temperature gradients during their formation.

With the results of the infiltration tests, we determined that the infiltration rate from the land surface was primarily affected by hydraulic properties of the topsoil layer, the interface between the topsoil layer and fractured basalt, and the near-surface soil-filled fractures. The cumulative infiltration volume for each test was described by a Horton type exponential function. Initial flow rates varied from 4.2 cm/day to 17.2 cm/day between tests, but rates converged to a range of 2.1 cm/day to 2.9 cm/day after 2 days (Figure 2). We hypothesized that due to the redistribution of water between fractures and matrix, some fractures, which became saturated at the beginning of the tests, became desaturated thereafter, suggesting that steady state was not reached (Figure 2). Lateral movement of water was observed within the central fracture zone and the rubble zone with ER measurements. Potassium

Map prepared by J. Lore (Stanford University)

Figure 1. A map of the fracture pattern in the upper basalt flow as it is exposed on the side of the cliff at Box Canyon (after J. Lore).

Figure 2. A typical example of changes in water pressure measured with tensiometers at three depths (1, 5, and 10 ft). Daily averaged values are shown.

bromide tracer added to the pond water was also detected in the rubble zone. A multicomponent model describing the saturation-desaturation behavior of rocks is proposed. According to this model, column-bounding fractures are the primary pathways for fast infiltration from the surface toward the rubble zone. Following the rapid saturation of rocks through conducting fractures, a gradual saturation of the basalt columns occurs.

The data from the infiltration tests conducted at Box Canyon show that it is impossible to identify a priori which fractures will transmit water during an infiltration event. As a result, water and tracer are not detected in much of the installed equipment, and the resulting information from the infiltration test alone is not enough to develop an adequate model of flow and transport in fractured basalt. Instead, our approach to the development of a conceptual model of flow and transport employed in this investigation is to combine the site characterization data with the results of the infiltration tests. It appears that the conventional term, "water front," commonly used to characterize infiltration in sedimentary material, is irrelevant for infiltration in fractured rocks, meaning that lateral movement of water and solutes is a dominant flow characteristic and could have important implications for contaminant accumulation.

SIGNIFICANCE OF FINDINGS

Our results provide a new conceptual model that can significantly improve the results of prediction of water flow and chemical transport in fractured rocks. This may provide an entirely new approach for environ-

mental management of contaminated fractured rock sites. DOE faces the remediation of several such sites where chemical and radioactive wastes released from shallow ponds and deep wells have traveled downward sporadically through narrow fracture pathways.

RELATED PUBLICATION

Faybishaenko, B., R. Salve, P. Zawislanski, K. H. Lee, P. Cook, B. Freifeld, J. Jacobsen, B. Sisson, J. Hubbell, K. Dooley, Ponded infiltration test at the Box Canyon Site. Data report and preliminary analysis, LBNL-40183, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Office of Science and Technology, Characterization, Monitoring, and Sensor Technology Crosscutting Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. Field investigations were conducted jointly with B. Sisson, K. Dooley, T. Wood and others from INEEL and the geological investigations were conducted jointly with A. Aydin and J. Lore from Stanford University.

Near Surface Wetting of a Ponded Basalt Surface: Observations Using Time Domain Reflectometry

R. Salve

RESEARCH OBJECTIVES

Given the limitations imposed by rocks on traditional methods for estimating moisture content, an appropriate method would exploit a physical property that is a function primarily of water content and that can be measured directly and reliably. One promising technology is Time Domain Reflectometry (TDR). TDR has the potential to provide rapid, reliable, and routine techniques for determining moisture content and perhaps electrical conductivity in rocks.

Here we present results from an infiltration experiment conducted on a fractured surface along the Snake River Plain in southeastern Idaho. Our objective was to determine the spatial and temporal variability in the wetting of a fractured basalt formation close to the surface (i.e., up to a depth of 0.80 m) in response to a ponded event using existing TDR technology. This effort was part of a larger investigation that sought to understand flow through fractured basalt. It was motivated by the presence of a large number of contaminated sites along the Snake River Plain and the absence of a clear understanding of fluid flow and transport processes through heterogeneous geologic media.

APPROACH

Field investigations were conducted at Box Canyon located on the Snake River Plain near the town of Arco, in southeastern Idaho. The experiment involved monitoring changes in dielectric (K_a) values in response to a plug of water introduced into a fracture basalt formation under ponded boundary conditions. To achieve this, an impermeable berm, approximately 0.5-m high, was constructed

along the perimeter of a 7 × 8 m plot using sand bags injected with polyurethane sealant. On the first day of the experiment, the bermed area was filled with water, which was maintained at an average height of 0.23 m.

After eleven days of ponding,

water supply to the pond was stopped and the water level in the pond gradually dropped due to infiltration and evaporation. On the thirteenth day of the experiment, the remaining water was pumped out of the pond.

Sixteen TDR probes (0.2-m long with a diameter of 0.002 m) were installed vertically, in or close to the bermed plot, with their tops located 0 to 0.6 m below the surface. Twelve probes were located within the pond. Eleven probes were installed in boreholes, three in fractures visible at the surface, and two in the rock matrix.

Temperature measurements were made at depths at which the TDR probes were installed before, during, and after the infiltration test. In addition, the temperatures of ambient air and ponded water were continuously recorded.

RESULTS

The results of this experiment can be divided into three broad periods with reference to the wetting of the basalt surface: pre-ponding, ponding and post-ponding. Additional information is provided by the response of the near-surface formation to a post-ponding rainfall event. Figure 1 (a-c) illustrates the changes in K_a observed during the experiment for six locations (A-F). Table 1 summarizes observations of wetting and drying in response to both the ponding and rainfall events at all the monitored locations.

Figure 1. Changes in K_a observed at six locations during the infiltration experiment.

Probe	PONDING ¹		DRYING AFTER PONDING ²		RAINFALL ³			
	Time to first response ⁴	Time to max. wetting	K _a at max. wetting	Time to first response	Time to first response	Time to maximum response	Time to pre-rain K _a	Time at maximum drying ⁵
A	13 27	17 57	26	7 04	2 04	14 04	132 30	23/9/96 22 04
B	0 08	Continuous ⁶	17 3	58 04	11 04	47 04	81 30	21/9/96 19 04
C	1 30	Continuous	17 8	28 06	2 06	14 06	81 32	21/9/96 13 06
D	0 30	Continuous	4 9	No drying	none		None	K _a increasing
E	5 31	134:30	6 5	Before L	3 07	Continuous	123 33	29/9/96 1 19
F	14 31	Continuous	7 7	13 07	8 07	57 07	129 33	K _a dropping
G	0 01	1 21	26 2	70 08	2 08	44 08	216 46	K _a dropping
H			-	-	-	-	-	-
I	0 57	Continuous	12 6	4 04	2 04	11 04	45 30	9/17/96 13 04
J	0 28	22 39	15 7	396 00	5 04	41 04	63 30	K _a dropping
K	0 08	Continuous	20 1	4 04	11 05	11 05	57 31	K _a dropping
L	1 38	Continuous	6 8	37 07	11 05	35 05	273 43	K _a dropping
M	4 39	Continuous	13 8	79 05	8 05	32 05	204 43	K _a dropping
N	0 29	11 09	4 3	No drying	none	Continuous	None	K _a increasing
O	1 19	Continuous	15 3	109 06	5 06	11 06	111 32	K _a dropping
P	0 08	0 10	59 2	31 06	2 06	14 06	111 32	K _a dropping

¹ Here t₀ is time at which pond was filled (8/27/96 12:50 pm)

² Here t₀ is time at which pond was completely drained (9/9/96 1:00 pm)

³ Rainfall occurred between 9/16/96 and 9/18/96

⁴ All time is presented in hours:minutes

⁵ 'Continuous' indicates that K_a values continued to rise

⁶ Data collection stopped on 10/10/96

Table 1. Summary of response of TDR probes during infiltration experiment.

There were four distinct patterns to the changes in K_a during ponding [Figure 1(b)]: an abrupt rise followed by constant values (e.g., probe A), an abrupt rise followed by a slight continuous rise (e.g., probes B and C), a steady continuous rise (e.g., probes D, E, and F), and an abrupt rise followed by a continuous drop (e.g., probe G).

Similar to the response to ponding, all monitored locations responded to the cessation of ponding within one day. There were three distinct patterns to the change in dielectric constants immediately after the pond had been drained [Figure 1(c)]: an abrupt drop followed by a constant value (e.g., probe C), an abrupt drop followed by a slight continuous drop (e.g., probe O), and a steady continuous drop (e.g., probe A). Locations that exhibited a particular pattern on wetting showed a mirrored response to drying. A clear exception was the fracture outside the pond (probe A), where there was an abrupt rise following ponding and a slow gradual decrease after the pond had been drained.

A prominent feature in the response of all TDR measurements was a diurnal fluctuation in dielectric values that coincided with temperature changes. The amplitude of these fluctuations was directly correlated with K_a measurements (for instance, a larger K_a experienced a larger amplitude fluctuation).

SIGNIFICANCE OF FINDINGS

The changes in dielectric values in response to ponding suggest that wetting and drying of the near-surface is extremely variable. This variability is introduced by features in the near-surface formation such as fractures, soil infilling, and the formation matrix. Early in the experiment it was apparent that the soil-filled near-surface fractures act as fast flow paths. Changes in K_a at locations outside the pond suggest that there is a lateral component to flow in the subsurface. The variability in response time to both wetting and drying suggests that close to the surface there are significant heterogeneities that influence travel time.

The performance of the TDR system suggests that, while quantitative deductions on the absolute saturation status at any location are difficult, useful qualitative information can be gleaned from the real-time automated measurements of dielectric made before, during, and after the ponding event.

FUNDING

This work has been supported by the Assistant Secretary for Environmental Management, Offices of Environmental Restoration, Waste Management, and Science and Technology, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Numerical Method for Simulating Non-Newtonian Fluid Flow in Porous Media

Y. S. Wu and K. Pruess

RESEARCH OBJECTIVES

Flow and displacement of non-Newtonian fluids in porous media occur in many subsurface systems, related to underground natural resource recovery and storage projects, as well as environmental remediation schemes. A thorough understanding of non-Newtonian fluid flow through porous media is of fundamental importance in these engineering applications. In the past few decades, considerable progress has been made in our understanding of single-phase porous flow behavior of non-Newtonian fluids through many quantitative and experimental studies. However, little research is found in the literature on multiphase non-Newtonian fluid flow or numerical modeling approaches for such analyses. For non-Newtonian fluid flow through porous media, the governing equations become nonlinear, even under single-phase flow conditions, because effective viscosity for the non-Newtonian fluid is a highly nonlinear function of the shear rate, or the pore velocity. The solution for such problems can in general only be obtained by numerical methods.

The objective of this work is to develop a numerical method for modeling non-Newtonian fluid flow in porous media. We have developed a 3D, fully implicit, integral finite difference simulator for single- and multiphase flow of non-Newtonian fluids in porous/fractured media. Several rheological models for Power-law and Bingham non-Newtonian fluids have been incorporated into the model. In addition, model predictions of single- and multiphase flow for power-law and Bingham fluids have been verified against the available analytical solutions, and in all the cases, numerical simulations are in good agreement with analytical solutions.

APPROACH

The multiphase system is assumed to be isothermal and composed of three mass components, air, water and a nonaqueous phase liquid (NAPL). These components are assumed to be present only in their associated phases; i.e., mass transfer between phases is ignored. Therefore, the present formulation is similar to the "dead oil" immiscible flow model. Two of the liquids,

water and NAPL, can be considered as non-Newtonian fluids, while the gas phase is always treated as a Newtonian fluid. In an isothermal system containing three mass components, three mass balance equations

are needed to fully describe the system. The balance equations for component or phase β ($\beta = w$ -water, a -air, and n -NAPL) are written in integral form for an arbitrary flow region V_n with surface area Γ_n as follows,

$$\frac{d}{dt} \int_{V_n} M^\kappa dV_n = \int_{\Gamma_n} \mathbf{F}^\kappa \cdot \mathbf{n} d\Gamma_n + \int_{V_n} q_\beta^\kappa dV_n \quad (1)$$

Here, M_β is the mass of component β ($\beta = w, a, n$) per unit porous medium volume; $\mathbf{F}_\beta$ is the mass flux of component β into V_n , $\mathbf{n}$ is the inward unit normal vector; and q_β is the rate of mass generation of component β per unit volume.

The mass accumulation terms for water, air and NAPL ($\beta = w, a, n$) in (1) are defined as:

$$M^\kappa = \phi \sum_\beta S_\beta \rho_\beta X_\beta^\kappa \quad (2)$$

Here, ϕ is the porosity; S_β is the saturation of phase β ; and ρ_β is the β phase density.

The mass flux terms are given by a multiphase extension of Darcy's law,

$$\mathbf{F}_\beta = -k \frac{k_{r\beta} \rho_\beta}{\mu_\beta} (\nabla P_\beta - \rho_\beta \mathbf{g}) \quad (3)$$

Here, k is the absolute permeability; $k_{r\beta}$ is the relative permeability to phase β ; μ_β is the β phase dynamic viscosity, which for non-

Newtonian fluids will be a generally nonlinear function of flow rate; P_β is the fluid pressure in phase β ; and $\mathbf{g}$ is the gravitational acceleration vector.

The mass transport governing Equation (1) needs to be supplemented with constitutive equations, which express all the parameters as functions of a set of primary thermodynamic variables of interest (P_β, S_β). These correlations are similar to those used for black-oil models. Except for viscosity for a non-Newtonian fluid (phase $\beta = n$ or

Figure 1. Comparison of the power-law fluid saturation profiles from the numerical and analytical solutions at time = 10 hours.

w), the apparent viscosity may be expressed as a function of saturation and potential gradient (Wu and Pruess, 1996),

$$\mu_{\beta} = \mu_{\beta}(S_{\beta}, \nabla \Phi_{\beta}) \quad (4)$$

where $\nabla \Phi_{\beta} = P_{\beta} - \rho_{\beta} \mathbf{g}$, a potential gradient.

The numerical scheme implementation is based on the "MULKOM/TOUGH2" family of multiphase, multicomponent codes. The mass balance equations for each phase are expressed in terms of the integral finite difference equations, which are fully implicit to provide stability and time step tolerance in highly nonlinear problems. Thermodynamic properties are represented by averages over explicitly defined finite subdomains, while fluxes of mass across surface segments are evaluated by finite difference approximations. All mass balance difference equations are solved simultaneously, using the Newton/Raphson iteration procedure.

The capillary pressures and relative permeabilities are treated as functions of saturation, and can be specified differently for different flow regions. The rheological properties for non-Newtonian viscosity need special treatments and depend on the rheological models used. Several common viscosity functions have been implemented in the code, such as the power-law and Bingham models.

RESULTS

One example (Wu and Pruess, 1998) is given in this section to provide verification of the model numerical schemes. This example is a one-dimensional immiscible flow problem of two incompressible fluids, one Newtonian and one non-Newtonian fluid, in a semi-infinite, horizontal, homogeneous, and isotropic porous medium with a unit cross-sectional area. Capillary effects are assumed to be negligible. Under such conditions, an analytical solution is available (Wu and Pruess, 1996). A power-law fluid is injected as a displacing agent to drive an initially saturated Newtonian liquid in a porous medium, and a comparison of the saturation profiles from the numerical and analytical solution after 10 hr of non-Newtonian fluid injection is shown in Figure 1. The figure illustrates that the numerical results are in excellent agreement with the analytical solution, although some smearing occurs at the sharp front as normally seen for a Buckley-Leverett problem.

SIGNIFICANCE OF FINDINGS

The objective of the present work was to develop a numerical method to investigate transport phenomena of non-Newtonian fluids through porous media. Whenever non-Newtonian fluids are involved in porous media, the flow problem will become highly nonlinear because of the dependence of the apparent viscosity used in the Darcy equation on shear rate. In general, a numerical method is needed to analyze non-Newtonian fluid flow in porous media. This work focuses on developing a methodology for power-law and Bingham plastic fluids, the most commonly encountered fluids in reservoirs. The proposed method should also be useful in analyzing flow problems with other types of non-Newtonian fluids.

A fully implicit, three-dimensional, integral finite difference model has been developed by modifying the general numerical codes, "MULKOM/TOUGH2," to consider the effects of non-Newtonian viscosity. This new simulator is capable of modeling both single and multiple phase non-Newtonian fluid flow through porous or fractured media. The numerical model can account for all the important factors that affect the flow behavior of non-Newtonian and Newtonian fluids, such as capillary pressure, complicated flow domains in homogeneous porous and fractured media, and various well operation conditions. Several commonly used non-Newtonian rheological models have been incorporated in the code. The validity of the numerical method has been confirmed by comparing the numerical results with analytical solutions.

RELATED PUBLICATIONS

- Wu, Y. S., and K. Pruess, Flow of non-Newtonian fluids in porous media, *Adv. Porous Media*, 3, 87-179, 1996.
- Wu, Y. S., and K. Pruess. A numerical method for simulating non-Newtonian fluid flow and displacement in porous media, *Adv. Water Resour.*, 21, 351-362, 1998.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, Yucca Mountain Site Characterization Project, of the U. S. Department of Energy, Contract No. DE-AC03-76SF00098, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory.

Design and Evaluation of Instrumentation for Infiltration Tests in Fractured Rock

B. Faybishenko, C. Doughty,
R. Salve, M. Steiger,
P. Zawislanski, and J. Peterson

RESEARCH OBJECTIVES

Many subsurface remediation efforts at contaminated sites have yielded disappointing results because of a lack of understanding of fluid flow and transport processes through heterogeneous geologic media, and in particular in fractured rocks. Fractures represent an extreme heterogeneity that can cause orders of magnitude differences in water flow and contaminant transport in both the vadose and groundwater zones. In order to predict the fate of contaminants under both natural and remediation conditions, an effective field monitoring system must be designed. Therefore, the objective of this study, conducted jointly with the Idaho National Engineering and Environmental Laboratory (INEEL), is to develop a suite of reliable tools to be used for characterizing liquid- and gas-phase flow and contaminant transport in a fractured basalt vadose zone, and evaluate the performance of these tools during ponded infiltration tests.

APPROACH

Twenty years of hydrogeological investigations of contaminated sites worldwide, well drilling and instrumentation in fractured basalt at INEEL, and joint LBNL/INEEL research at the Box Canyon site near INEEL have revealed four critical problems related to the monitoring of water flow and chemical transport in fractured rocks:

- Identifying where to place subsurface instrumentation so it intercepts highly localized flow and transport pathways. This requires developing a good conceptual model of flow and transport, which is described in Faybishenko et al., page 115, this report.
- Installation of the subsurface instrumentation so that probes can be in contact with the main geological components of fractured basalt that affect water and contaminant transport, including column bounding

fractures, column-normal fractures, vesicular basalt, etc.

- Sealing of borehole to preserve natural pathways of water movement in fractured rocks.
- Using a sealing material that will not affect readings of geophysical techniques (i.e., radar and neutron logging, electrical

resistivity.)

A new design of borehole sealing technology is described below, followed by the main characteristics of the probes installed in the boreholes. Then, an evaluation of this design using the results of the ponded infiltration test is presented.

1. New borehole sealing technology. It is common practice to install an array of single monitoring probes in boreholes at different depths within sand layers separated by impermeable bentonite or cement layers. Figure 1 illustrates that if a fracture intersects the well near a layer of sand, there is no outlet for the water, and the result is perched water on top of the bentonite seal. Therefore, we designed a method of instrument installation and sealing technology that eliminates the problems associated with conventional instrumentation. We used a polyurethane sealant to inflate packers. We attached probes to the outside of these packers, and then backfilled the rest of the borehole between the packers. This material shows great promise for enabling the rapid, cost-effective installation of sensors and probes in fractured rocks.

2. Neutron logging access boreholes. Neutron logging is commonly done in metal-cased boreholes. However, the metal interferes with electromagnetic logging and was therefore not an option for our studies. Acrylic casing was found to be the most viable material. Laboratory investigations found that a 2 to 4 mm-thick-wall of acrylic pipe is virtually "invisible" to neutrons.

3. TDR wave guides. Two types of Time Domain Reflectometry (TDR) probes

Figure 1. A schematic of installation of single probes (tensiometers, suction lysimeters, electrical resistivity probes, thermistors) in fractured rocks: (a) a schematic of conventional technology. Probes are located in fine-texture sandy layers, which are separated by low permeable bentonite grout; (b) a schematic of a new installation method for fractured rocks. The probes are located on the outside surface of plastic bags (packers) attached to a PVC access pipe.

were installed at the Box Canyon Site. The first was a rigid-wave-guide probe, used to determine the changes in the moisture content of soils and rocks from the surface to a 0.6-m depth. The second type was a flexible wave-guide probe, installed in direct contact with the rocks along the borehole walls. To accomplish this task, a special TDR pad consisting of flexible wave guides bonded to polyethylene closed cell foam was designed and tested.

4. Miniature Electrical Resistivity (ER) probes. A new type of miniature four-electrode probe of the Wenner configuration was designed and fabricated for real-time monitoring of changes in the electrical resistivity during the infiltration tests. The four electrodes were spaced at 1-cm intervals and held in place with an epoxy. The probes were installed in boreholes using the new borehole sealing technology, and were also used to monitor changes in resistivity of the pond water by submerging the probes below the pond surface.

5. Tensiometers. Two types of tensiometers were installed, with the porous tip in contact with the rocks, using the new borehole sealing technology. Deep tensiometers were installed at depths greater than 3.3 m. Conventional air-pocket-type tensiometers were used at depths above 3.3 m. To maintain a better contact with rocks, the ceramic tips were placed in bags of fine sand.

6. Suction lysimeters. Two types of conventional suction lysimeters were installed in boreholes using the new borehole sealing technology. Deep suction lysimeters were used to collect water below 3.3 m, and shallow suction lysimeters above this depth.

7. Thermistors. Conventional thermistors were installed in boreholes using the new borehole sealing technology.

8. Ground Penetrating Radar (GPR). In cross-borehole GPR, we sent and received radar signals using antennae located at equally spaced depths in a pair of boreholes. Signal amplitude versus time was recorded and travel time between points determined, enabling construction of tomographic images of the dielectric constant in the plane between the boreholes. We used GPR to characterize the subsurface moisture distribution before, during, and after the ponded infiltration tests.

RESULTS

Measurements during a series of five ponded infiltration tests (one 2-week test in 1996 and four 2–4 day tests in 1997), including tracer injections, provided information at three different scales:

Tensiometers, TDR probes, electrical resistivity probes, and thermistors installed at different depths in boreholes provided point measurements in the near vicinity of the sensor without perturbing the sys-

tem. These measurements were effective in the upper 3-m near-surface zone, which consisted of vesicular basalt intersected by numerous fractures, and provided information about water arrival that suggested lateral flow was occurring during infiltration.

Neutron logging and suction lysimeters provided approximately 20–30 cm around the borehole. During the infiltration test in 1996, 62% of the suction lysimeters produced water that was collected for analysis. Neutron logging confirmed that flow occurred through localized fracture zones.

GPR provided information about a plane between boreholes without perturbing the system by furnishing a two-dimensional image of subsurface response to the ponded infiltration tests. Although the tomographic image is of low resolution, it provided insights into the system response not obtainable from point measurements alone, and aided interpretation of point measurement responses.

Performance evaluation of the instrumentation and interpretation of the experimental results support the use of several types of measurements at different spatial scales to study water infiltration in fractured basalt.

SIGNIFICANCE OF FINDINGS

Based on these results, we have further refined a conceptual model of the geometry and physics of liquid flow in fractured basalt (this report, Faybishaenko et al., page 115). The borehole sealing technology and a combination of point-type, near-borehole, and cross-borehole monitoring techniques are recommended for short- and long-term monitoring and for controlling the remediation efforts at DOE contaminated sites. In particular, we suggest using the new techniques to provide information needed to control the integrity of underground barriers, and to detect leaks from surface and underground tanks, ponds, landfill sites, and cribs.

RELATED PUBLICATION

Zawislanski, P. T., and B. Faybishaenko, New casing and backfill design for neutron logging access boreholes. *Ground Water J.*, in press.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Office of Science and Technology, Characterization, Monitoring, and Sensor Technology Crosscutting Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. This has been a joint LBNL/INEEL project.

Uncertainty Propagation from Subsurface Transport to Exposure Modeling

RESEARCH OBJECTIVES

Among the environmental problems currently foremost in public awareness are hazardous waste sites with subsurface contamination. These waste sites are being assessed using site-specific models that predict the fate and transport of subsurface contamination and the subsequent potential for long-term human health risk. Currently, predictions of contaminant transport and the resulting human health risk are most often performed independently. Ranges of contaminant concentrations derived from either data or from simulations typically are not used in human exposure and health risk evaluations. Instead, risk assessments rely on upper-bound static concentrations derived from either limited site data or from simple models that use conservative assumptions about contaminant distributions. An improved methodology uses ranges of values to reflect the inherent uncertainties introduced in both modeling efforts. Ideally, an integrated uncertainty analysis should be used in the assessment of contaminated sites, such that information is passed from subsurface transport modeling to exposure and risk calculations. Here we demonstrate model integration, including uncertainty propagation, by investigating the sources of outcome uncertainty in an integrated subsurface contaminant transport and human health risk model for a particular case study.

APPROACH

The approach described here is part of a risk-based remediation analysis framework called SELECT being developed at Berkeley Lab. In the SELECT framework, hazardous-waste site remediation scenarios are assessed in terms of health risk and cost. The SELECT framework combines state-of-the-art subsurface contaminant transport (T2VOC) and human health risk (CalTOX) models, thus making it possible to treat the uncertainty of the integrated analysis. Figure 1 illustrates the framework for uncertainty analysis

A. L. James, C. M. Oldenburg,
D. H. Bennett, and T. E. McKone

for T2VOC and CalTOX in SELECT. T2VOC models transport in the subsurface environment, while CalTOX models exposure in the shallow soil and indoors in the residential environment.

Based on a case study with information from an actual site contaminated with trichloroethylene (TCE), we investigated the propagation of variance in the simulation of risk using a complex subsurface contaminant transport simulation model integrated with a multipathway human health risk model. Ranges of subsurface contaminant concentrations are calculated with the subsurface transport simulator T2VOC (using the associated code ITOUGH2 for uncertainty analysis) for a three-dimensional system in which TCE migrates in both the vadose and saturated zones over extended distances and time scales. The subsurface TCE concentration distributions are passed to CalTOX, which is used to calculate risk through multiple exposure pathways based on inhalation, ingestion, and dermal contact. Monte Carlo and linear methods are used to propagate uncertainty due to parameter variance. We used rank correlation to evaluate contributions to overall uncertainty from each model system

RESULTS

Figure 2 illustrates the contribution of selected T2VOC and CalTOX parameters to total risk variance calculated by rank correlation. In this TCE case study, we find that total human health risk is most sensitive to horizontal permeability, the parameter that controls the speed with which TCE is transported laterally through the subsurface towards the residential area. This parameter accounts for roughly 60% of variance in total risk. For this case study, subsurface transport uncertainties are dominant in their contribution to uncertainty in the total risk. Uncertainty originating from the exposure modeling, however, was significant enough to make its evaluation important.

Figure 1. Schematic of framework for uncertainty analysis for T2VOC and CalTOX in SELECT. T2VOC models transport in the subsurface environment while CalTOX models exposure in the shallow soil and indoors in the residential exposure environment.

Figure 2. Determination of regression correlation coefficient for individual T2VOC and CalTOX parameters. Note that the percentage of risk variance attributed to the parameter horizontal permeability extends to a value of roughly 60%.

SIGNIFICANCE OF FINDINGS

We have demonstrated the propagation of uncertainty from a complex subsurface contaminant transport simulation through a sophisticated human exposure model, resulting in a stochastic description of human health risk. This initial attempt at integrating uncertainty analyses between two models has also enabled the evaluation of which parameters from both models (T2VOC and CalTOX) exert the greatest influence on final risk variance for a particular case study. It is important to remark that the influence of individual parameters and models will always be site specific and that by developing the methodology and framework with which to perform the propagation of uncertainty as we do in SELECT, site risk assessment can be carried out accounting for uncertainty.

RELATED PUBLICATIONS

Bennett, D. H., A. L. James, T. E. McKone, and C. M. Oldenburg, On uncertainty in remediation analysis: variance propagation from subsurface transport to exposure modeling, *Reliability Engineering and System Safety*, in press.

James, A. L., and C. M. Oldenburg, Linear and Monte Carlo uncertainty analysis for subsurface contaminant transport simulation. *Water Resour. Res.* 33(11), 2495-2508, 1997.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098; and by the State of California to the University of California at Berkeley through the Cal-EPA Department of Toxic Substances Control (DTSC) Contract Agreement 95-T1050.

Ferrofluids for Subsurface Flow Control and Imaging

RESEARCH OBJECTIVES

The objectives of this project are to investigate the potential of ferrofluids (stable suspensions of colloidal ferromagnetic particles in a carrier liquid):

1. To accurately and effectively guide (i) reactants (for *in-situ* treatment) or (ii) barrier liquids (low-viscosity permeation grouts) to contaminated target zones in the subsurface using electromagnetic forces
2. Using geophysical methods, to trace the movement and position of liquids injected in the subsurface

APPROACH

Ferrofluids are stable colloidal suspensions of magnetic particles in various carriers with saturation magnetizations as high as 1000 Gauss, low viscosities (<5 cp, allowing easy injection into the subsurface), and a small particle size (3.5–15 nm, minimizing potential filtration problems). The solid, magnetic, single-domain particles are covered with a molecular layer of dispersant. Thermal agitation (Brownian motion) keeps the particles suspended, while the dispersant coating prevents the particles from agglomeration. Ferrofluids are superparamagnetic and move as a homogeneous single-phase fluid under the influence of a magnetic field. This attribute is responsible for the unique property of ferrofluids that they can be manipulated in virtually any fashion, defying gravitational or viscous forces in response to external magnetic fields.

We investigated the use of Ferrofluid for Guiding liquids (FGs) to enhance the efficiency of *in-situ* treatment and waste containment through (a) accurate guidance and delivery of reagent liquids to the desired subsurface contamination targets; and/or (b) effective sweeping of the contaminated zone as FGs move from the application point to an attracting magnet/collection point. FGs can be manufactured with the appropriate carrier liquids (e.g., reactants for *in-situ* treatment or barrier liquids).

Current delivery and emplacement practices for *in-situ* remediation or

G. Moridis

containment consist entirely of injection, and suffer from the adverse effects of heterogeneity, which may cause the treatment effort to be short circuited by

preferential flow. Magnetic fields are easier to manipulate than pressure fields, and the soil magnetic properties are quite homogeneous. Magnetically controlled emplacement is thus expected to be more accurate and effective by allowing liquids to be focused and guided to the desired locations. FGs offer the unique advantage of a predictable and symmetric final distribution of the liquid regardless of the flow pathway (Figure 1).

RESULTS

Starting from first principles, the partial differential equation of FG flow in porous media was derived. The appropriate multiphase and/or solute transport equations governing the flow of subsurface liquids in the presence of FGs were identified. The corresponding equations of induction and magnetic field (Maxwell equations) were determined. Analytical 1D solutions were developed for an FG moving in an FG-saturated medium in response to a magnetic field, and were verified against laboratory data (Moridis and Oldenburg, 1998).

Hele-Shaw experiments (Figure 2) demonstrated the ability to guide FGs in response to external magnetic fields, and indicated that FGs remain stable and do not disperse during magnetic flow despite their complete water miscibility. As the fluid approached the magnet, its velocity increased due to the increasing magnetic field strength and gradient. An important observation was that the FGs accumulate against the magnet in a symmetric predictable distribution, which is controlled only by the attributes of the magnetic field.

Experiments of magnetically induced FG flow in porous media in 2D sand beds confirmed the ability to guide FGs in response to fields from Nd-Fe-B magnets (Borglin and Moridis, 1998). The FG flow pattern toward the magnet was very similar to that observed in the Hele-Shaw experiment. Practically identical observations have been made with (a) different initial FG distributions, (b) different sand

Figure 1. Horizontal flow of EMG 805™ ferrofluid through sand, and accumulation against a permanent magnet. The final ferrofluid distribution is uniform, predictable regardless of the flow pathway, unaffected by the hydraulic properties, and depends only on the magnetic field.

tray sizes, and (c) variable distances between the initial FG position and the magnet. The importance of these observations lies in the realization that the final FG distribution is unaffected by heterogeneities in the properties of the porous media and flow patterns, and is controlled only by the magnetic field.

Practical FG applications involve the solution of coupled, strongly nonlinear equations of flow and magnetic field that are tractable only through numerical simulation. Using the TOUGH2 general simulator of flow and transport through porous media (Pruess, 1991), the new module EOS7M (describing the behavior and flow of ferrofluids in the presence of a magnetic field) was developed, verified against analytical solutions, and validated against laboratory data (Oldenburg et al., 1998). The EOS7M module accounts for the effects of the magnetic field on the ferrofluid, as well as the coupled effects of water-miscibility on the ferrofluid properties and its flow and transport characteristics.

The high saturation magnetization in the FGs provides a signature sufficiently strong for magnetic detection methods at low loading volumes (i.e., 1–5%). We investigated the possibility of exploiting this property to develop a method for monitoring and imaging liquid movement and position during injection using electromagnetic methods. We demonstrated the feasibility of using conventional magnetometry to detect subsurface zones of injected Ferrofluid for Tracing liquids (FTs) (Borglin et al., 1998). Several geometric shapes were considered, and the detection depths of FTs were calculated using magnetometry principles. Laboratory experiments showed a very good agreement between predictions and measurements.

SIGNIFICANCE OF FINDINGS

1. The movement and accumulation of ferrofluids in the subsurface can be effectively controlled by magnetic fields. As the final ferrofluid distribution depends only on the magnetic field and is unaffected by the heterogeneity of the hydraulic properties, effective remediation and containment technologies (based on the target-

Figure 2. Movement of EMG 805™ ferrofluid in a water-filled horizontal Hele-Shaw cell in response to a Nd-Fe-B magnet.

ing capabilities of ferrofluids with appropriate carrier liquids) are possible.

2. Ferrofluids appear to be promising tracers for the detection and imaging of the movement and position of liquids in the subsurface.

RELATED PUBLICATIONS

Borglin, S., and G. J. Moridis, Experimental investigation of magnetically-driven flow of ferrofluids through porous media, LBNL-40126 Lawrence Berkeley National Laboratory, Berkeley, Calif.,

1998.

Borglin, S., G. J. Moridis, and A. Becker, Magnetic detection of ferrofluid injection zones, LBNL-40127, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

Moridis, G. J., and C. M. Oldenburg, Principles of ferrofluid flow in porous media, LBNL-40167, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

Moridis, G. J., S. E. Borglin, C. M. Oldenburg, and A. Becker, Theoretical and experimental investigations in the use of ferrofluids to guide and detect liquids in the subsurface, LBNL-41069, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

Oldenburg, C. M., Borglin, S. E., and G. J. Moridis, On modeling flow and transport of magnetic fluids in porous media, LBNL-40146, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

Pruess, K., TOUGH2 — A general-purpose numerical simulator for multiphase fluid and heat flow, LBNL-29400, Lawrence Berkeley Laboratory, Berkeley, Calif., 1991.

FUNDING

This work has been supported by the Director of the Office of Laboratory Policy, Laboratory Directed Research and Development Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

VZMS:

RESEARCH OBJECTIVES

Because of the large number (258) of contaminated sites at McClellan Air Force Base (AFB), only the most highly contaminated sites have been characterized sufficiently to design and implement remedial actions. The remaining majority of sites likely pose much smaller risks due to lower contaminant concentrations and smaller total masses of contaminants. Nevertheless, in order to prioritize remediation efforts, it is necessary to determine whether the many enigmatic sites contribute to the degradation of groundwater in the aquifer 100 ft below the ground surface. The objectives of this research are to (1) develop and install a Vadose Zone Monitoring System (VZMS) consisting of multiple levels of permanently installed tensiometers, suction lysimeters, gas samplers, pressure transducers, and thermistors; (2) monitor these instruments over one or more years; (3) complement the monitoring data with physical properties determined from samples collected during drilling; and (4) carefully analyze all of the VZMS data in an integrated manner to determine the behavior of the vadose zone and its contaminants at this location. The field data and conceptual understanding we develop at this site can be used to provide constraints on vadose zone processes and modeling at other sites at McClellan AFB.

APPROACH

The VZMS is an array of instruments deployed in a borehole to monitor soil hydraulic potential, gas-phase pressure, contaminant concentrations in both liquid and gas phases, and temperature. The instruments include tensiometers, pressure transducers, liquid and gas samplers, and thermistors. A single cluster of the instruments designed to be installed permanently in a borehole is shown in Figure 1. The cluster includes a stainless-steel, spring-loaded mechanism that, when triggered, pushes the instruments against the borehole wall in order to enhance contact between the sensor and the formation. Those instruments, which rely on the exchange of fluids

Vadose Zone Monitoring System
for McClellan Air Force Base

C. M. Oldenburg and P. T. Zawislanski

made of stainless steel. Each level of instrumentation is backfilled with sand and then separated from underlying and overlying levels with a layer of bentonite. Thirteen levels of these instrument clusters were installed over approximately 100 ft. of alluvial sands and silts between the surface and the water table in each of two boreholes (VZMS-A and VZMS-B) 10 ft. apart at site S-7 in Investigative Cluster-34 (IC-34) at McClellan AFB. The many tubes and wires connected to the various instruments are enclosed in a vault at the surface, with connections to a data acquisition system installed in a portable building at the site. Two nearby boreholes for neutron logging were also constructed to monitor moisture content. Gas and liquid samples are brought to the Berkeley Lab Environmental Measurements Laboratory for chemical analyses.

In order for the VZMS to provide information on moisture movement, gas-phase flow due to barometric pumping, and contaminant fluxes in gas and liquid phases, a considerable data analysis effort is required. Our approach for enhanced data analysis is to use all of the data for the site, including VZMS temporal data, to build a plausible conceptual model that will be developed and studied using the multiphase simulator T2VOC along with ITOUGH2 for inverse modeling, and uncertainty and sensitivity analyses. Below we present initial observations from the VZMS that will be used to constrain the conceptual model.

RESULTS

The primary contaminants found at the site include TCE, cis 1,2-DCE, and Freon 123a. Shown in Figure 2 are soil gas TCE concentrations measured by the EPA TO14 method from VZMS-A for four sampling events. The data show two fundamental features: (1) gas-phase TCE concentrations are highest at the top of the vadose zone and decrease with depth until near the water table, where there is a small increase; and (2)

Figure 1. Sketch of VZMS instrument cluster.

the shallowest TCE concentrations are increasing with time. These data suggest that there is a shallow (<6-ft. depth) source of TCE as well as contaminated groundwater at the water table. Both the source and the contaminated groundwater appear to be contributing TCE to the vadose zone. We see in Figure 2 that over the period of our observations, the shallow soil gas concentrations are increasing. The increase in shallow TCE soil gas concentrations may be indicative of the

infiltration of surface runoff that is contaminated by TCE in the shallow soils. Surface runoff includes water that moves through the coarse subgrade gravels of the concrete pad. This is being investigated further by direct sampling and analyses of subgrade water that appears in the VZMS vault immediately following rainfall. The frequent occurrence of barometric pressure changes in the 1997–1998 rainy season and the continuous automated recording of pressure at all levels of the VZMS have also produced an excellent record of barometric pumping, which can be used to constrain permeability in the profile.

Despite the evidence of rainfall events in the VZMS data, the vadose zone at the VZMS site has turned out to be considerably drier than anticipated. As a result, tensiometry and liquid sample extraction have proven difficult since the moisture potential at many levels is more negative than the porous cups of the tensiometers and suction lysimeters. Nevertheless, we have been able to collect liquid samples from some levels, and gas sampling is possible at all levels. Comparisons of gas and liquid volatile organic chemical (VOC) concentrations from levels where we have both kinds of samples show the gas and aqueous phases to be in equilibrium with Henry's Law partitioning governing VOC concentrations. Thus, Henry's Law can be

Figure 2. Depth distribution of TCE in soil gas for four sampling events at VZMS-A

used with some level of certainty to predict liquid-phase concentrations from gas-phase concentrations for VZMS levels where suction lysimetry is not possible.

SIGNIFICANCE OF FINDINGS

The installation and monitoring of the VZMS at S-7 in IC-34 at McClellan AFB has allowed the collection of data that identified a shallow source of VOC contamination. Furthermore, the shallow TCE concentrations are increasing with

time, suggesting downward movement of TCE through the vadose zone. Integrating all of the data from the VZMS will allow the development of a conceptual model for numerical simulations that permits enhanced data analysis and predictions that may have implications for other sites at McClellan AFB. The VZMS methodology is applicable to contaminated sites throughout the DOE, DOD, and Industry, where vadose zone contamination is important.

RELATED PUBLICATION

Zawislanski, P., B. Faybishenko, A. James, B. Freifeld, and R. Salve, Vadose zone monitoring system installation report for McClellan AFB, LBNL-39525, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

FUNDING

This work has been supported by the Secretary of the U.S. Department of Defense under Military Interdepartmental Purchase Request FD2040-96-74020EM to Ernest Orlando Lawrence Berkeley National Laboratory, managed for the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Chemical Compatibility of Colloidal Silica Grout

RESEARCH OBJECTIVES

Subsurface containment of contaminants by *in-situ* barriers can be a practical alternative to other options, such as excavation and disposal of contaminated soils, or pumping and treating. Barrier containment minimizes exposure of workers or the public to contaminants, and after formation of an *in-situ* barrier, more intensive remediation technologies, such as soil washing or alcohol flooding, can be applied without the risk of spreading the mobilized contaminants beyond the contained region. Formation of subsurface barriers by permeation grouting is known as Viscous Liquid Barrier (VLB) technology. Low-viscosity liquids are injected through multiple injection points in the subsurface. The injected plumes intersect and merge to completely surround and isolate the contaminant source and plume. Once in place, they gel to form a nearly impermeable barrier. VLB is the only technology currently capable of providing horizontal barriers (bottoms) in containment systems.

Colloidal Silica (CS), a stable aqueous suspension (colloid) of silica microparticles, has a low viscosity (typically 5 to 8 cP) and can be made to gel with a controlled gel time by adding brine. These properties make it suitable for VLB application. The principal advantages of CS over other injectable grouts are its low viscosity and nontoxicity. Unlike microfine cements, the particles cannot be filtered out by the soil. Detailed discussions of CS properties and their use in VLB technology can be found in Persoff et al. (1998a,b) and Moridis et al. (1998).

In 1997 Brookhaven National Laboratory was the site of a demonstration of VLB formed by injection of CS (Moridis, 1998). The purpose was to test whether a VLB formed by injecting CS could meet regulatory requirements for low permeability, and withstand the effects of contaminants.

APPROACH

Two-by-four-inch cylindrical samples of grouted sand were made by pouring sand into liquid CS grout in molds. This method of sample preparation was used because it guarantees good reproducibility among samples and guarantees full saturation of the pore space by the grout (a condition not necessarily achieved in the field). The hydraulic conductivity and unconfined compressive strength of samples were

P. Persoff, J. Apps, and G. Moridis

measured by ASTM methods D-5084 and C-39, respectively.

Three variables were examined:

(1) silica concentration ranging from 5 to 27 wt%; (2) inclusion

of dense, nonaqueous phase liquid (DNAPL) contaminants; and (3) immersion of samples for up to one year in DNAPL contaminants and in water saturated with DNAPL contaminants. In tests (2) and (3), uncontaminated water was also tested as a control. The DNAPLs tested were C_2Cl_4 (perchloroethylene, PCE), CCl_4 (carbon tetrachloride), and $C_6H_5NH_2$ (aniline). The CS used in this work was DuPont Ludox SM, with a 2-hr-gel, time-produced NaCl addition (0.1 to 0.3 molar, depending upon the silica concentration).

RESULTS

The compressive strength and hydraulic conductivity of Monterey sand grouted with CS are shown in Figure 1. The line fitting the strength data is a least-squares fit, not forced through the origin. As the silica content of the grout was reduced by dilution, the unconfined compressive strength of the sample decreased and the hydraulic conductivity increased. The Monterey sand itself is not cohesive, and any unconfined compressive strength results from the cementing effect of the grout, which increases linearly with the amount of silica in the grout.

The hydraulic conductivity of the grouted samples is the principal property of interest. A value of 10^{-7} cm/s is generally accepted as the requirement for barrier material. The data in Figure 1 show that this criterion was met by all the samples made with a silica content exceeding 7.4 wt%. The sand grains themselves are effectively impermeable and the measured hydraulic conductivity can be understood to represent the hydraulic conductivity of the gelled Ludox SM itself, multiplied by a factor of approximately 0.38, representing the volume fraction of the sample occupied by gelled grout.

The relationship between silica concentration and hydraulic conductivity can be explained, at least qualitatively, by considering the structure of the gelled CS. The gelled CS has a high water content, and constitutes a second, microporous medium that fills the macropores of the sand. Gelled CS consists of a network of particle chains. Within the CS, the space between the gelled chains of silica particles constitutes a

Figure 1. Compressive strength and hydraulic conductivity of samples of Monterey sand grouted with various dilutions of Ludox SM.

Figure 2. Compressive strength of Monterey sand grouted with two dilutions of Ludox SM, after immersion for up to one year in various liquids. In each graph, the lower set of curves shows data for 7.4 wt% silica, while the upper set of curves are for 19.7 wt% silica. (a) Water, pure chlorinated organics, and water saturated with chlorinated organics. (b) Water, pure aniline, and water saturated with aniline.

network of micropores through which water can flow. The size of these micropores depends upon the silica concentration: at 27.0 wt% silica the grout is 90% water by volume, and at 7.4 wt% it is 97% water. Considered as a porous medium, the grout with 7.4 wt% silica therefore has only 8% more pore space than grout with 27.0 wt% silica, but its hydraulic conductivity is 30 times as great. Flow resistance results from viscous drag on water as it flows through a tangle of chains of gelled particles. The low value of hydraulic conductivity results from a highly divided flow path with many small pores. Decreasing the silica concentration by a factor of 3.67 increases the space between chains. This is similar in effect to increasing the pore diameter, which can account for the observed increase in permeability.

Aniline was the only one of the DNAPLs tested that adversely affected the strength of samples. This was observed both when aniline was included in the sample and when uncontaminated samples were immersed in aniline. Figure 2 shows that samples gained strength during the immersion, except for samples immersed in aniline and water saturated with aniline. In that sense, immersion in aniline weakened the samples.

SIGNIFICANCE OF FINDINGS

These results indicate that gelled colloidal silica (CS) has a low permeability and is unaffected by PCE and CCl_4 . Therefore, CS would be a good candidate for VLB formation by permeation grouting to control these contaminants. Aniline, however, prevents gelled CS from reaching its full strength and may degrade the grout in the long term.

Two conditions must be satisfied to achieve low permeability in a VLB: the permeability of the grout itself must be low, and the grout must nearly completely saturate the pore space (sweep efficiency). The results shown in Figure 1 indicate that significant dilution of CS is possible without unacceptably high permeability. In designing a VLB, this property allows for grout dilution by groundwater, or can justify reducing material costs by diluting CS. However, even a completely impermeable grout will not form a good barrier if ungrouted holes remain after injection. The optimum design may use dilution not to save cost but to increase the injected volume to better ensure complete grouting.

RELATED PUBLICATIONS

- Moridis, G., Evaluation of alternative designs for an injectable barrier at the Brookhaven National Laboratory Site, Long Island, NY, LBNL-41763, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Persoff, P., J. Apps, G. Moridis, and J. M. Whang, Effect of dilution and contaminants on sand grouted with colloidal silica, LBNL-40854R1, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998a.
- Persoff, P., G. Moridis, J. Apps, and K. Pruess, Evaluation tests for colloidal silica to be used for grouting applications, *Geotech. Testing J.*, 21(3), 264-269, 1998b.

FUNDING

This work has been supported by the E. I. DuPont de Nemours Co. under Contract No. BG-94211 through an agreement with the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Geophysical Verification of Subsurface Containment Structures

L. Pellerin, F. Gilbert,
S. Hubbard, and J. Peterson

RESEARCH OBJECTIVES

Subsurface barriers are under investigation as a remediation option for contaminant isolation. The success of the containment is dependent on the placement and integrity of the subsurface barriers, and hence the verification of its integrity, extent, and bulk hydraulic conductivity. A robust methodology for verification and monitoring of the subsurface containment barrier is under development. Geophysical (GP) surveys are used to determine the areal extent and continuity of the barrier. Information obtained from GP measurements can be combined with the hydraulic and gaseous tracer results to produce a comprehensive understanding of the quality and performance of the barrier.

The methodology was tested at two different types of subsurface barriers. Thin-diaphragm walls were created by simultaneously jetting a cement-bentonite grout at approximately 5,800 psi in two opposing directions without rotating the drill string during the injection process. Two barriers, constructed by keying thin-diaphragm walls into clay layers, were emplaced during the summer of 1997 at the Dover National Test Site (DNTS) to demonstrate both emplacement and verification technologies in

both the vadose and the saturated zones. The GP verification methodology is described with respect to the DNTS barriers. A viscous liquid barrier, emplaced in the vadose zone, using a low-energy permeation grouting technique at the Brookhaven

National Laboratory (BNL), was also successfully verified using the geophysical methodology discussed below.

APPROACH

The GP verification methodology under development included: site characterization to determine *in-situ* host properties; laboratory analysis of soil and grout mixtures to estimate physical properties for modeling and survey design; and data acquisition, reduction, and interpretation. Four GP methods were investigated: electromagnetics (EM), ground penetrating radar (GPR), electrical resistivity (ER), and borehole seismic.

Site characterization of the DNTS with surface GP methods defined important features, such as the location of the watertable and clay lenses, in addition to estimating important physical properties of the host media. Laboratory measurements of grout mixtures gave estimates of the physical properties to be used with the

Figure 1. Crosshole GPR data presented as an amplitude spectrum of the first arrival before and after injection and the differenced data, and the difference in travel time for the same borehole pair.

host parameter estimates for numerical modeling of the system. Numerical models were used in a sensitivity study to address which GP techniques would be optimal for the thin-diaphragm wall barrier system at DNTS. All of the geophysical instruments were deployed from boreholes or permanently emplaced vertical electrode arrays (VEAs). To increase resolution, data were acquired prior to and after the grout injection and then differenced. For leak detection, ER was used to monitor a salt water flood of a cell of one of the barriers.

RESULTS

The primary purpose for the EM induction logging was to quantify the changes in the electrical properties of the borehole completion materials and soils over the period of time that the barriers were injected. The EM measurement proved to be easy to make and required very little time and/or effort. The data provided information on the changes in the formation electrical properties during the course of the project, which were useful for interpretation of the borehole GPR and ER data. For both barriers, responses at the holes outside of the cell showed a decrease in conductivity that would be consistent with the curing of the grout used to complete the boreholes. The holes inside the barriers showed an increase in conductivity, indicating that there was a response to the presence of the barrier and/or the increase of moisture content within the cells. The sensitivity analysis indicated that a single-hole, multifrequency, multiseparation EM tool would be useful in delineating the barrier.

The cross-borehole GPR data were acquired in both a zero offset profiling (ZOP) mode and a multiple offset profiling (MOP) mode from borehole pairs located across the walls of the barriers. The ZOP data were rapid to collect, and straightforward to interpret in transmission mode. The multiple offset data, which are time-consuming to collect, were needed to construct tomograms of the barrier walls. The GPR data are presented in Figure 1 as an amplitude spectrum of the first arrival before and after injection and the differenced data. The before injection data show an attenuating region in blue at 4–5 m, corresponding to the clay layer. After injection, the section from 1–5 m attenuated the signal, indicating the presence of the barrier. It is interesting to note that after injection there was still a hint of the structure of the stratigraphy. The colors

are reversed in the difference data, clearly showing no change in blue. A velocity analysis is also shown as the difference in travel time before and after injection as a function of depth for the same borehole pair. The difference in travel time was roughly 3 ns, as predicted in the sensitivity study, indicating a slowing of the wave as it propagated through the relatively wet barrier.

The contrast between the electrical properties of the host and the grout made the ER method, with fixed electrodes, a natural selection. Cross-borehole ER data were acquired with the Lawrence Livermore National Laboratory Electrical Resistivity Tomography (ERT) system. No data were taken before injection of the barriers, so differencing was not possible and only images after injection were made. The high contrast of the grout to the host allowed for direct imaging of the barrier. Unfortunately, the electrical contrast between the grout and the clay was insufficient to determine the quality of a wall keyed to a floor.

The cross-hole seismic method was demonstrated, but without success because of the problems of propagating acoustic energy in the vadose zone and the severe scattering of energy due to the injection of air into the subsurface during injection of the barrier.

SIGNIFICANCE OF FINDINGS

A robust methodology that accounts for the various components of the system — host environment, grout, etc. — was successfully demonstrated on two very different types of subsurface barrier. The verification design was successful, because the proper methods were chosen on a proper scientific basis, not on availability or the user's familiarity with a technique. The methodology outlined and demonstrated provides the best chance that the verification survey will be successful. In addition, a database, including laboratory measurements and numerical simulations, is being developed on which to base regulations.

FUNDING

This work has been supported by the Director, Office of Science and Technology, Subsurface Contaminants Focus Area, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Measuring Partition Coefficients of Colloids at Gas-Liquid Interfaces

J. M. Wan and T. K. Tokunaga

RESEARCH OBJECTIVES

Colloidal particles include many different organic, inorganic, and microbial substances. Their very small sizes (nm to μm) give them high specific surface areas, and often high surface charge densities. These characteristics make suspended particles efficient carriers of otherwise immobile, strongly sorbing metal ions. In addition to their well-known mobility in water, particles are also found to favorably accumulate at air-water interfaces in many natural environments and engineered systems. Enrichment of particle-associated heavy metals and organic compounds has been found at ocean and lake surfaces. For instance, the concentrations of lead, iron, nickel, copper, fatty acids, hydrocarbons, and chlorinated hydrocarbons were found to be 1.5 to 50 times higher in the surface layer (approximately 150- μm thick) of Narragansett Bay relative to the bulk water, with most of the enrichment in particulate and organic fractions. Clays, humic acids, and microorganisms have been found to accumulate at water-gas interfaces in unsaturated soils. Engineered systems such as flotation-based mineral separation methods also take advantage of particle partitioning at air-water interfaces. These examples suggest that colloidal partitioning at air-water interfaces can be significant in a wide variety of natural and engineered systems. For surface active molecules, changes in surface tension along with changes in solution concentration determine their surface excesses through the Gibbs equation. However, for suspensions of particles, surface tension changes are often not measurable. In this study a simple dynamic method was developed to quantify particle surface excesses at air-water interfaces.

APPROACH AND RESULTS

We developed a method using a bubble column device to quantify colloidal surface excesses. In the bubble column system (Figure 1), gas is bubbled through a vertical column containing the dilute aqueous suspension (solution) of the colloids (solute). The rising bubbles sorb and carry the surface-active species upwards, then release them back to the solution at the free surface where the bubbles burst. At steady state, a concentration profile is established along the column length that reflects the balance

between upward transport by partitioning onto rising bubbles and downward transport by eddy dispersion. By predetermining the column eddy dispersion coefficient D for given conditions (column dimensions, air-flow rate, and bubble size) and measuring the steady-state concentration profile, partitioning between bulk and surface regions can be determined. In a bubble fractionation column at steady state, the local mass balance for a surface active compound requires that upward and downward transport rates be equal. This condition is represented by

$$af\Gamma = AD \frac{dC}{dz}, \quad (1)$$

where a is the surface area per bubble, f is the bubble generation rate, Γ is the surface excess, A is the column cross-sectional area, C is the concentration in solution (suspension), and z is the vertical coordinate. For dilute solutions (suspensions) in which partitioning at the water-gas interface is linear with respect to concentration, surface excess is given by

$$\Gamma = KC \quad (2)$$

For surface-active molecules, K is the linear adsorption isotherm coefficient. In extending this approach to particulate systems, we define K as the particle partition coefficient, relating particle surface excesses to their bulk suspension concentrations. The extension of Equation (2) to linear partitioning of particles is intended to apply in dilute suspensions, when K is relatively constant. The solution to Equations (1) and (2) is an exponential profile, and the ratio of concentrations at elevation z versus at the bottom of the column at steady state is

$$\frac{C(z)}{C_b} = \exp\left(\frac{afKz}{AD}\right). \quad (3)$$

Thus, when A , a , f , and D have been independently determined, measurement of $C(z)$ at steady state permits determination of K . In our present work, D was directly determined through measuring transient salt concentration profiles following step inputs of salt tracers in bubble columns (Wan and Tokunaga, 1998). The analytical solution of the

Figure 1. The bubble column device.

dispersion equation was then fitted to these results by adjusting D . To test the uniqueness of the bubble column results, adsorption isotherm constants obtained with this method can be compared with values obtained by surface tension measurements. For a dilute surfactant solution, combining the Gibbs absorption equation with Equation 2 gives

$$K = \frac{-1}{RT} \frac{d\gamma}{dC}, \quad (4)$$

where R is the gas constant and T is the Kelvin temperature. Thus, whether surface excesses measured by bubble fraction columns and surface tension measurements are equivalent can be tested in simple surfactant solutions through comparing K values obtained using Equation (3) versus Equation (4). Separate experiments were conducted in the bubble column at $22.8 \pm 0.5^\circ\text{C}$ for solutions (suspensions) of sodium dodecyl benzene sulfate (SDBS), kaolinite clay, and soil humic acid (HA). SDBS was selected as the test surfactant. At steady state, samples (1.5 ml each) were withdrawn through the sampling ports using syringes. Concentrations of all samples were measured with a spectrophotometer. The absolute particle numbers of clay colloids were determined using a particle analyzer. The measured concentration profiles were used with the model [Equation (3)] to obtain surfactant adsorption isotherm constants and colloid partition coefficients. The K value of $64 \pm 4 \mu\text{m}$ for the SDBS resulting from the bubble column profile is in good agreement with the K ($64 \pm 12 \mu\text{m}$) obtained from surface tension measurements. This agreement validated the bubble column technique as a method to determine partitioning of surface-active components at air-water interfaces. The reproducible measurements of HA concentration profiles resulted in a K value of $18 \mu\text{m}$. Given the poorly defined nature of humic acid molecular weights and the extremely wide range of reported values for this quantity, our measured K permits determination of HA surface excesses in terms of mass per interfacial area. The measured relative concentration profiles of kaolinite and the best average-fit model profile are shown in Figure 2. The well-developed

Figure 2. Steady-state relative concentration profiles of kaolinite clay particles in the bubble column. Data points are from column experiments conducted at the three indicated initial particle concentrations.

concentration gradients for kaolinite in the bubble column demonstrated that, under the given solution chemistry, this clay partitions favorably at air-water interfaces. Over a two order of magnitude range in concentrations, the clay suspensions gave a reasonable linear partitioning relation. A K value of $23 \pm 5 \mu\text{m}$ accounted for kaolinite partitioning over this range of suspension concentrations. When clay suspension concentrations are expressed in terms of mass per unit volume, surface excesses of clays are identified in terms of mass per interfacial area.

SIGNIFICANCE OF FINDINGS

This study provided the first measured partition coefficients of clay and humic colloids at the air-water interface. By extension, this method will permit quantification of surface excesses of the wide range of inorganic, organic, and microbial colloids, as well as molecular species complexed onto colloids. The bubble column technique can provide quantification of colloid K values, useful in understanding a wide variety of natural systems (ocean and lake surfaces, and soils) and engineered systems (separation processes).

RELATED PUBLICATION

Wan, J., and T. K. Tokunaga, Measuring partition coefficients of colloids at air-water interfaces, *Environ. Sci. Technol.*, Nov., 1998.

FUNDING

This work has been supported by the Assistant Secretary of Environmental Management, Environmental Management Science Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Compliance Monitoring and Selenium Load Management in the Grasslands Basin

RESEARCH OBJECTIVES

Berkeley Lab's Earth Sciences Division (ESD) has been involved in the Grassland Bypass Project (GBP) from its inception. The project diverts agricultural drainage water from Grassland Water District (GWD) channels into the San Luis Drain. The GWD contains a 40,000 hectare tract of some of the most important wetland habitat on the Pacific Flyway. Through this unique project, the Grasslands Basin agricultural water districts agreed to limit annual selenium exports to the San Joaquin River to 3000 kg/yr. They also agreed to reduce their selenium discharges by an additional 5%/yr in the 3rd, 4th, and 5th years of the project and pay fines of up to \$500,000 per year for excesses in annual selenium load limits. ESD provided technical assistance and developed an environmental assessment of possible impacts of the proposed project. This 1991 report showed only minor impacts to the San Joaquin River. ESD was further involved in the development of a monitoring plan, a version of which was published as an LBNL topical report (Quinn, 1995). The monitoring plan and agreement for use of the San Luis Drain were finalized after negotiation between the responsible parties.

An unresolved research issue first recognized during completion of the environmental documentation was the ability of the natural system to bioremediate selenium. Before the GBP, this agricultural drainage passed through approximately 160 km of wetland channels in transit to the San Joaquin River. Mass balance analyses performed for this system of channels indicated a 25% and 35% reduction in the dissolved selenium load between the northern boundary of the agricultural water districts and the San Joaquin River. This loss had implications for the capability of the agricultural water districts to meet selenium load targets since it was unknown whether some of the same in-transit losses that occurred in the GWD conveyance system would be replicated in the Drain. Hence, a primary research objective during the first year of the GBP was to quantify the selenium load loss in the 45-km reach of the

San Luis Drain and develop a clearer understanding of the mechanisms responsible for attenuating selenium loads.

N. W. T. Quinn

APPROACH

Flow and water quality monitoring stations were selected approximately 3 km north of the Drain inlet and 2 km south of the Drain outlet, providing a 40-km section for study. The upstream flow and water quality monitoring site was located at an existing check structure. The water stage above the weir boards was used to calculate discharge using a weir discharge rating curve. A conductivity sensor and datalogger recorded electrical conductivity and water temperature every 15 min, and a 24-bottle autosampler was used to obtain a composite weekly water quality sample for selenium analysis. A solar panel provided the site's DC power. A footbridge and cantilevered bridge were constructed at the downstream flow and water quality monitoring site as a platform to attach acoustic doppler velocity sensors, stage, and electrical conductivity sensors. Discharge was measured every 15 min at the site. A cellular phone, modem, and datalogger allowed real-time acquisition of data. A 24-bottle autosampler collected water samples for selenium analysis 6 times per day. Flow and selenium concentration data were combined to estimate monthly selenium loads and load target compliance.

A cooperative study with students in the Bioremediation Education, Science and Technology Program and the UCB Leighton laboratory developed a microbial profile of (a) the ecology of the quiescent San Luis Drain before onset of drainage diversions; and (b) the flowing San Luis Drain during operation of the GBP. Of particular interest was the capability of the natural bacterial populations in

the Drain to remove selenium from the water column. Water samples were taken at five locations along the 45-km Drain alignment in the quiescent system, each location having a unique combination of water depth, water chemistry, and carbon availability. Shallow water depths lead to high algal productivity during the summer; reaches adjacent to agricul-

Figure 1. Comparison of measured selenium loads at inlet and outlet to San Luis Drain

(Note: Se loads at inlet from flow weighted concentrations sampled weekly).

Figure 1. Comparison of measured selenium loads at inlet and outlet to San Luis Drain.

tural areas receive agricultural fertilizer and pesticide inputs; reaches with large quantities of rotting wind-blown vegetation provide a microbial energy source. Microbial ecology of the Drain was compared via water samples from the Drain outlet in both quiescent and flowing systems. Selenium uptake experiments were performed in the laboratory with isolates in pure culture to compare their ability to reduce selenate and selenite to the inert elemental form.

RESULTS

Figure 1 shows the results of a mass balance performed on samples taken at each end of the San Luis Drain for the first year of the GBP. There was a net in-transit loss of 6% in dissolved selenium loads determined by combining flow and water column selenium concentration measurements. Errors in these estimates are mostly associated with water quality sampling, which was performed weekly at the inlet and 6 times a day at the outlet in 1997. Sampling at the inlet has been performed daily since April 1998. Although in-transit losses of selenium occurred in the winter months between inlet and outlet, there appeared to be a net increase in selenium load for March through June 1997. Winter is associated with rainfall runoff from agricultural fields, some of which is directly discharged into the subsurface drainage conveyance system. Sediment deposition in the Drain during these months may help remove some water column selenium. There is no easy explanation for the selenium load increase. This is a challenge for ongoing research and monitoring activities. Drain microbial profiles showed the majority of bacterial strains isolated, when grown in the laboratory with adequate nutrients, could remove 95% of the selenium in a 1 mMolar selenite solution within 24 hr. A few strains were capable of reducing about 10% of 1 mMolar selenate solution to elemental selenium in the same time period. This is significant as approximately 95% of selenium in

Figure 2. Selenium detoxification experiment.

agricultural drainage water is selenate. Figures 2(a) and 2(b) show the results of one of these selenium detoxification experiments with a bacterial strain later identified as *Pseudomonas putida*.

SIGNIFICANCE OF FINDINGS

There is evidence that selenium in-transit losses occur in the San Luis Drain. The fate of this selenium is most likely bed sediments into which water column selenium can diffuse and which can accumulate dead algal

and bacterial cells. Sampling during the past 12 months shows a small, though not statistically significant, net increase in sediment concentration. The San Luis Drain is equivalent to a large reactor with a residence time of 3–5 days, depending on flow conditions. Future manipulation of Drain microbial ecology might be possible through additives or by diverting part of the flow into a flow-through wetland system to stimulate the natural biomediation potential of the existing system, reducing the mass loading of selenium to the San Joaquin River. This would have a significant impact on the future viability of agriculture in the western San Joaquin Valley and provide a significant benefit to the environment.

RELATED PUBLICATIONS

Quinn, N. W. T., J. McGahan, and M. Delamore, Innovative drainage management techniques to meet monthly and annual selenium load targets, *California Agriculture*, in press.

Quinn N. W. T., Compliance monitoring program for use and operation of the Grasslands Bypass to remove agricultural drainage from Grassland Water District channels, LBNL-39052, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

FUNDING

This work has been supported by the U.S. Bureau of Reclamation, Sacramento, California, through the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Preliminary Investigations of a Wetting Front Migration at Yucca Mountain, Nevada

R. Salve and J. S. Wang

RESEARCH OBJECTIVES

Migrating water plumes in the unsaturated fractured tuffs within Yucca Mountain can originate as water used for construction activities associated with the boring of the Exploratory Studies Facility (ESF) and the East-West Cross Drift (EWCD), or as water introduced as infiltration (rainfall or artificial ponding) at the surface. Monitoring the migration of these plumes may provide information on parameters defining flow of water in this site which has been proposed for the storing of nuclear waste. In this report we summarize some preliminary results of our efforts. These results, when coupled with those of the U.S. Geological Survey (USGS), are part of a larger investigation in which the main objectives are to: determine the seepage response to water infiltrating the surface at high rates that mimic expected El Nino related rainfall events; and monitor the migration of a water plume resulting from tunneling activities in the EWCD.

APPROACH

We chose an alcove located relatively close to the surface of Yucca Mountain (37 m) to measure spatial and temporal connections between rapid infiltration through the alluvial cover into the bedrock near the surface, and percolation fluxes at the potential repository level. Here the alcove ceiling and rib were instrumented by the USGS with sensors (heat dissipation probes, TDR probes and tensiometers) to detect changes in rock saturation, while water was injected at the surface immediately above the alcove.

To supplement the monitoring effort by the USGS, we installed additional sensors (electrical resistance probes) in two nearly horizontal boreholes stemming from the alcove wall. These sensors were located in four 10-ft-long packers, with sensors at 6 in. intervals. Three of these

packers were installed in one of the boreholes, at distances of 0-10 ft, 30-40 ft, and 60-70 ft from the borehole collar. The fourth packer was installed in the second borehole 0-10 ft from the collar. Electrical resistance

measurements began in mid-December, 1997, while the infiltration at the surface was initiated in early March 1998.

To monitor the migration of a water plume resulting from construction of the EWCD, a 30-m-long borehole was constructed at an angle of 30° (from the horizontal), along the proposed path of the EWCD tunnel. The borehole originated at the end of a starter tunnel, which was the launching pad for the tunnel boring machine (TBM) being used to excavate the EWCD. Changes in water saturation and potential were monitored along the entire 30-m length of the borehole using psychrometers and electrical resistivity probes, as the TBM inched through the formation above.

RESULTS

In Alcove 1, water began to seep into the alcove 58 days after the infiltration experiment began. This seepage was not picked up by any of the sensors, but was observed as drips in localized portions of the ceiling. The pattern of electrical resistance changes observed along portions of the two boreholes is summarized in Figure 1. Our data suggest that along the borehole walls there were significant changes (both spatial and temporal) in the moisture status during the 4-month monitoring period. The periodic wetting and drying cycles indicate that the formation was responding to disturbances independent of the surface infiltration event. Further, the uniform response pattern of most sensors suggests that there is substantial communication among various locations within the formation.

Figure 1. Changes in electrical resistance measured in borehole in Alcove 1 27-37 ft from collar.

Figure 2. Changes in moisture status along EWCD borehole during construction of tunnel.

Data obtained from the EWCD borehole are summarized in Figure 2, and include changes in electrical resistance and water potentials along the 30-m-long borehole prior to, during, and after the TBM passed over the monitoring zone. The data suggest that prior to the actual boring of the ECRB, there were changes in water potentials up to a depth of 25-m from the borehole collar. Continuous changes in water potential and electrical resistance were observed at depths of less than 20 m. An interesting anomaly in the data are the periodic fluctuations in water potentials and resistance, the amplitudes of which were largest for sensors closer to the borehole collar. These fluctuations are superimposed on a general wetting trend captured along the entire borehole.

SIGNIFICANCE OF FINDINGS

Preliminary analysis of data obtained from Alcove 1 suggests that flow in the fractured tuffs is possibly feature related, with a small number of fractures conveying large

amounts of flow. Further, it appears that the formation is well ventilated, with efficient air communications even at distances greater than 30 m. Our data from the EWCD tunneling activities indicate that at distances of more than 20 m from the borehole collar, there were significant changes in the formation moisture status. Ongoing investigations are directed towards determining possible causes of these changes.

FUNDING

This work has been supported by the Director, Office of Civilian Radioactive Waste Management, through Memorandum Purchase Order EA9013MC5X between TRW Environmental Safety Systems, Inc., and Ernest Orlando Lawrence Berkeley National Laboratory for the Yucca Mountain Site Characterization Project, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Center for Environmental Biotechnology

Jennie C. Hunter-Cevera, Center for Environmental Biotechnology Head

The Center for Environmental Biotechnology (CEB) was established four years ago as a multidivisional center for integrated interdisciplinary research in three main focus areas:

- Biogeochemical Transformations
- Environmental Diagnostics
- Environmental Health Risk Assessment Based on Bioavailability

The Center is a joint effort linking Berkeley Lab and the University of California at Berkeley (UCB). The Center's administrative home is Berkeley Lab's Earth Sciences Division. Its extended staff represent four major divisions: Earth Sciences, Life Sciences, Environmental Energy Technology, and Engineering. In addition, the Center has collaborating scientists from Information and Computational Sciences, Accelerated Fusion Research, Nuclear Physics, the Advanced Light Source, and Materials Sciences. UCB faculty that collaborate with CEB are members of the Plant and Microbial Biology, Environmental Engineering, Molecular and Cell Biology, Chemistry, and Physics Departments. CEB's vision and goal are to facilitate programs and coordinate and provide multidisciplinary research teams that address specific environmental problems at DOE and DOD sites and within the State of California. CEB also manages the Army Corps of Engineers Bioremediation Education, Science, and Technology (BEST) Program and Berkeley Lab's efforts in biological nonproliferation and antibiotic discovery and diagnostics.

BIOGEOCHEMICAL TRANSFORMATIONS

Microbe-Rock Interactions. Our main objective in examining biogeochemical transformations is to simulate "real world" conditions in "real time." An example is the current work jointly being carried out by CEB and the Advanced Light Source in using nonintrusive synchrotron infrared spectromicroscopy to spatially map the presence of TCE-biodegrading and chromium-biotransforming microorganisms in subsurface basalt core samples from

the Idaho National Engineering Laboratory TAN site. Results of this work indicate that the biotransformation of chromium(VI) occurs simultaneously with the biodegradation of toluene. At the same time, our geochemists and modelers are examining flow rate and preferential flow pattern of water and DNAPLs in the fractured basalt where these microorganisms grow as a biofilm. Kinetic activity is monitored over time in geocosms by use of ICP-MS and detection of TCE pathway intermediates using the synchrotron infrared spectromicroscopy. We are also examining the structure of biofilms using soft x-ray imaging.

Biodegradation of Fuel Additives. This project looks at the biodegradation of methyl tertiary butyl ether (MTBE), a gasoline additive that is a potential carcinogen. By designing a bioreactor that simulates the actual "process reactor," we have isolated indigenous microorganisms that are attached to carbon material and have the capability of biodegrading this gasoline additive. These microorganisms are currently being identified and appear to be members of the *Actinomycetales* family. A pilot plant is being constructed in Southern California for treatability studies.

Biodegradation of Mixed Wastes. We are also working on the biosorption of actinides in the presence of organics and chelating agents and assessing the fate and transport of actinides. This combination of actinides and organics represents the actual mixtures found at the Hanford site near Richland, WA. Results indicate that the fate and transport of actinides are very different in a mixture versus pure actinides and that certain bacteria are capable of absorbing actinides at high levels. In another study we are investigating microorganism-heavy metal interactions with the specific goal of using ubiquitous soil bacteria to biosorb the contaminants. This project allows us to study the molecular mechanisms involved in biosorption of metals and elucidate any occurring preferential binding in mixtures of contaminating metals.

Panoche Algal-Bacterial Selenium Treatment. A selenium and nitrate treatment system has been operated on agricultural land within the Panoche Water District for the past two years. Two side-by-side systems consisting of a shallow high-rate algal pond, a deep reduction pond, a sedimentation unit, and a filter bed were constructed close to the tile sump draining a 1,000-acre field. Removal rates vary from 40–80%, depending on the system's configuration. Ongoing research focuses on increasing the removal efficiency and throughput of these systems under a variety of environmental conditions. The ultimate objective is to develop a low-cost, easy-to-implement technology farmers can use to reduce selenium loads exported to the San Joaquin River and San Francisco Bay-Delta.

ENVIRONMENTAL DIAGNOSTICS

Polyphasic Characterization of Microbial Communities in Damaged Environments. This project characterizes microbial communities in damaged environments such as closed defense bases or agricultural water and sediment runoffs with high levels of heavy metals, and from an *ex-situ* bioreactor that remediates methyl ethyl ketone. We have isolated and characterized some hundred environmental strains. Ecology-based isolation and cultivation techniques enabled us to grow a large number of microorganisms. To characterize them, we employed molecular-level methods such as small subunit rRNA gene sequencing and phospholipid fatty acid methyl ester profile analysis, and the BIOLOG identification system.

Stable isotope monitoring. CEB in collaboration with the Center for Isotope Geochemistry has been employing stable isotope monitoring to validate bioremediation activities in field sites. The isotopic ratios of soil gas and groundwater compounds are monitored to distinguish byproducts of biodegradation of petroleum hydrocarbons (e.g., CO₂, CH₄) from other potential sources. Further, distinctive shifts in the isotopic compositions of the contaminants and metabolic byproducts have been used to differentiate between specific metabolic pathways used by the microorganisms to degrade the contaminants. More recently, we have concentrated on using isotopic measurements to detect *in-situ* biodegradation of more recalcitrant contaminants such as chlorinated solvents and gasoline oxygenates.

Detection of environmentally important genes with mass spectrometry. One way to assess the importance of bioremediation is to confirm that organisms in an environmental sample carry the genes for pollutant-degrading enzymes. A general assay has been devel-

oped to hybridize peptide nucleic acid probes to PCR amplified DNA and use Matrix-Assisted-Laser-Desorption-Ionization Time-of-Flight Mass Spectrometry to score the test. A specific procedure targets the catechol-2,3-dioxygenase gene, an intermediate in the degradation of several aromatic compounds, including naphthalene, benzene, toluene and nitrobenzene. The advantages of this diagnostic approach are high throughput and the high level of confidence associated with a measurement of ion mass.

Colorimetric Detection of DNA Hybridization. The rapid detection of DNA hybridization between a synthetic oligodeoxynucleotide (ODN) of known sequence and its complement provides a powerful tool for diagnostics and nucleic acid sequencing. In collaboration with the Materials Sciences Division, our research is directed towards development of a colorimetric sensor for specific detection of DNA hybridization via nucleic acid molecular recognition of a single stranded sample ODN (ss-s-ODN) with a single stranded probe ODN (ss-p-ODN), which is covalently attached to the surface of highly colored polydiacetylene (PDA) thin films and liposomes. Such a recognition and binding event induces a blue-to-red color transition of the PDA liposome absorbance.

ENVIRONMENTAL HEALTH RISK ASSESSMENT BASED ON BIOAVAILABILITY

Assessing environmental risk based on bioavailability is a challenge for CEB. There is much data in the literature on high dose exposure rates or single dose, single compound exposure rates to animals. CEB is examining the weathered material as it exists in nature and exposing human cell lines to this material over time. In many instances our cell line models consist of co-culturing two different types of cell lines on thin membranes. We can measure bioavailability, contaminant metabolism, and DNA damage and repair using specific molecular biomarker assays developed by our cell biologists. With this model we are investigating the uptake of a mixture of metals and their biotransformation rates and using analytical methods and the Advanced Light Source's synchrotron capabilities.

PARTNERS AND FUNDING

CEB research is funded by the U.S. Department of Energy, U.S. Department of Defense, U.S. Navy Office of Naval Research, and the petroleum industries. Current collaborators come from the DOE national laboratories, the Army Corps of Engineers, University of California at Berkeley, Cal/EPA, institutes in the former Soviet Union, and the biotechnology and bioremediation industry.

Biotransformation of VOCs in Fractured Rock Vadose Zones

RESEARCH OBJECTIVES

Volatile organic compounds (VOCs) are common organic contaminants detected in polluted subsurface soil and fractured rock vadose zones. The possibility of using intrinsic microorganisms to biologically transform VOCs to less harmful compounds has stimulated many investigations of this detoxification process in subsurface soils, but little of this work has involved fractured rock vadose zones.

The goal of this project is to investigate the possibility of using intrinsic endolithic (rock-inhabiting) bacteria to transform VOCs. Specifically, the project objectives are: (1) to evaluate the presence of endolithic bacteria and their long-term survival potential; (2) to characterize the mechanisms and pathways used by the intrinsic endolithic bacteria to transform VOCs at the bacteria-mineral interface; and (3) to optimize the desirable transformation kinetics with respect to the range of critical environmental factors. In addition, we also validate the use of stable isotopes to monitor the biotransformation processes.

APPROACH

Toluene and trichloroethylene (TCE) represented VOCs. Toluene was used to model biotransformation driven by the primary substrate utilization mechanism. TCE was used to model biotransformation of a secondary substrate. Rock cores were collected aseptically from a VOC-contaminated subsurface fractured rock vadose zone at a depth of 66-70 m at a site within the extensive Columbia basalt flow in southeastern Idaho. Sampling technique, sample handling, and sectioning at the drilling site were conducted according to the aseptic protocol developed under DOE's Subsurface Science Program. All collected rock samples were fine-grained silicate-containing vesicular basalts, with calcic plagioclase feldspar $[(\text{Na,Ca})(\text{AlSi})_4\text{O}_4]$, pyroxene $[(\text{Ca,Na,Mg,Fe})(\text{Al,Si})\text{O}_3]$, and olivine $[\text{Mg}_{1.8}\text{Fe}_{0.2}\text{SiO}_4]$ being the essential minerals. About 10-25% of the matrix consisted of vesicles of various sizes. Some vesicles were partly infilled with individual or mixtures of minerals.

H-Y. N. Holman, J. T. Geller, M. Conrad, K. Pruess, and J. C. Hunter-Cevera

Thin-sections of the rock specimens were prepared from the cores by using our newly developed low-speed diamond-wire-cutting protocol. We have proven that the protocol would not produce significant disturbance of the existing microbial arrangement inside rock samples. Printing-off cultivation experiments as well as surface-enhanced infrared absorption-reflection (SEIRA) microspectroscopy analysis (Holman et al., this report, page 143) were conducted to evaluate the presence of microorganisms in the thin-sectioned rock specimens.

Culturable microorganisms from the printing-off cultivation experiments were identified by their colony and cellular morphology and by BIOLOG and fatty acid methyl ester (FAME) analyses. Their VOC-biotransformation potentials with respect to a range of critical environmental factors were monitored using the infrared microspectroscopy Beamline 1.4.3 at Berkeley Lab's Advanced Light Source. This infrared microprobe uses a synchrotron

source that has a much higher brightness than a conventional thermal IR source. The experimental spot size of the unmasked synchrotron beam focused through an infrared microscope is 10 μm , one-hundred-fold smaller than is possible with an internal thermal source. This experimental procedure is nondestructive to the biological materials being studied.

Column and geocosm experiments are conducted to study mass transfer limitations to the microbial transformation of VOCs. The limitations arise from heterogeneous distributions of minerals, VOCs, moisture, and microorganisms.

RESULTS

This is an ongoing project. The following are our preliminary results. Comparative analysis of results from the printing-off experiment suggests that at the mesoscale level, there is a significant heterogeneity in the distribution and diversity of cultivatable microbial consortia inside the vesicular basalt. As shown in Figure 1, our endolithic microorganisms lived in pore space with or without direct connection with the surface. Spatial analysis of the SEIRA microspectra

Figure 1. Photographs of colony growth on agar disk that received inoculation from surface of thin section of vesicular basalt.

indicates that the micron-scale localization around the pore space was controlled by the mineral heterogeneity (see Holman et al., this report, page 143).

Results from the BIOLOG and FAME analyses indicate that the culturable bacteria belong to 11 genera, 15 species, and over 80 strains. Most of the bacteria are gram-positive.

Temporal analysis of infrared spectra for the culturable bacteria indicates that gram-positive and gram-negative microorganisms responded very differently to the changes of critical environmental factors. Most gram-positive isolates did not show signs of stress after being incubated in low humidity (20% RH) for weeks.

The synchrotron-based infrared microspectra show that toluene-bacteria interactions on the mineral surfaces were highly localized at the micron scale. Five days after the initial exposure to the toluene vapor, we observed that at the location of the bacteria peak, there is a depletion of toluene (Figure 2).

SIGNIFICANCE OF FINDINGS

This study provides evidence that our intrinsic endolithic microorganisms in the vesicular basalt did not show signs of stress in a low-humidity environment. We also demonstrated, for the first time, the application of synchrotron-based infrared microspectroscopy to monitor

the progress of VOC biotransformation as the transformation took place on geologic materials.

RELATED PUBLICATIONS

Holman, H.-Y. N., D. L. Perry, M. C. Martin, and W. R. McKinney, Applications of synchrotron infrared microspectroscopy to the study of inorganic-organic interactions at the bacterial-mineral interface, *Application of Synchrotron Radiation Techniques to Materials Sciences, MRS Symp. Series, 54*, in press, 1998a.

Holman, H.-Y. N., D. L. Perry, and J. C. Hunter-Cevera, Surface-enhanced infrared absorption-reflectance (SEIRA) microspectroscopy — a chemical/biological probe for

bacteria localization in geologic materials, *J. Microbiol. Methods*, accepted, 1998b.

FUNDING

This work is supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Division of Materials Sciences; and Office of Biological and Environmental Research, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Figure 2. *Arthrobacter oxydans* bacteria, isolated from a contaminated DOE site in Idaho, attached themselves to magnetite mineral surfaces. We locate the bacteria via their spectral signature, and locate a depletion of toluene near the peak location of the bacteria.

Infrared Microspectroscopy — A Probe for Bacteria Localization in Geologic Materials

H.-Y. N. Holman, D. L. Perry,
M. C. Martin, W. R. McKinney,
and J. C. Hunter-Cevera

RESEARCH OBJECTIVES

Pollution of subsurface geologic zones and the possibility of using intrinsic endolithic (rock/mineral-inhabiting) bacteria to detoxify or immobilize pollutants have stimulated new interest in the exploration of endolithic bacteria and their long-term survival in the geologic environment. The location of bacteria within rocks and minerals dictates the type and intensity of environmental stresses bacteria are exposed to and thus affects their long-term survival potential. Various approaches have addressed the microbial localization in rocks. Except for microscopy techniques that visually enumerate the distribution of endolithic microorganisms on an intact environmental sample, most methods use molecular and/or metabolic probes to identify the presence of microorganisms in crushed rocks and conventional techniques to identify physical and geochemical properties of the rock materials. This project's purpose was to develop and demonstrate the applicability of surface-enhanced infrared absorption-reflection (SEIRA) microspectroscopy as a complement to existing methods, to quickly study with minimum sample preparation *in-situ* relationships between the microbial localization and the microscopic physiochemical structures of geologic materials. Unlike traditional microscopy approaches, SEIRA microspectroscopy can simultaneously provide researchers biological, geochemical, and physical characteristics of the intact environmental samples.

APPROACH

Specimens (40–100- μm thick) were prepared aseptically from fine-grained silicate-containing vesicular basalt rock samples collected from a subsurface rock vadose zone 66–70-m deep within the Columbia basalt flow in southeastern Idaho. Their main composition is calcic-plagioclase feldspar $[(\text{Na},\text{Ca})(\text{AlSi})_4\text{O}_4]$; pyroxene $[(\text{Ca},\text{Na},\text{Mg},\text{Fe})(\text{Al},\text{Si})\text{O}_3]$, and olivine $[\text{Mg}_{1.8}\text{Fe}_{0.2}\text{SiO}_4]$. About 10–25% of the matrix consisted of vesicles of various sizes. Some vesicles were partly infilled with individual or mixtures of minerals. *In-situ* relationships between the microbial localization and the microscopic physiochemical structures of geologic materials were studied

by means of SEIRA microspectroscopy with a metal-overlayer configuration. SEIRA microspectroscopy combines traditional light-reflecting microscopy with the more recent but well-documented SEIRA spectroscopy technique. The working procedure involved using visible light

and reflecting optics to view a magnified image of a material surface and select a microscopic surface area on the sample for infrared reflection-absorption spectroscopic analysis. The selection was relatively subjective and relied on geometry, color, crystallographic properties, and other material-specific features of the sample surface. Once the sample area was selected, it was noted and the specimen coated with a thin film of gold. Molecular information of the selected surface area was recorded *in situ* spectroscopically in the infrared spectral region.

Spatial distributions of indigenous bacteria relative to other surface characteristics were measured by space-resolved SEIRA microspectroscopy. Space-resolved microspectra of the surface were recorded on the Fourier transform infrared (FTIR) spectrometer-IR-Plan microscope system, which was equipped with a computer-controlled x-y mapping stage. With the automatic step-by-step collection of microspectra, maps that showed the absorption peak height of a functional group of molecules vs. the physical location on the sample surface were obtained. For each measurement at a given location, 128 spectra were co-added at a spectral resolution of 4 cm^{-1} .

RESULTS

Analysis of infrared spectra for materials in the system indicates the following distinct infrared absorption bands be used to detect spatial distribution of bacteria microcolonies within the basalt specimen: the C=O ester peak near $1,741\text{ cm}^{-1}$, C=O Amide I peaks (within the Amide I envelope) near $1,650\text{ cm}^{-1}$, and C=O Amide II peaks near $1,550\text{ cm}^{-1}$. The broad features of reflectance spectra for constituent minerals of basalts in the region between $1,300$ and 800 cm^{-1} were used to identify the distribution of vesicles in the basalt specimens. Detailed changes in spectral features in the $1,300$ and 800 cm^{-1} regions were used as markers to identify changes in constituent minerals.

Figure 1. Microphotography of the $400 \times 500\text{ }\mu\text{m}$ study area. Axis BB' is the sampling path. The 2 prominent dark areas are 2 vesicles in basalt specimen.

SEIRA microspectroscopic mapping experiments (Holman et al., 1998b) were conducted on a selected specimen (Figure 1) to evaluate potential applicability of SEIRA microspectroscopy as a chemical/biological probe to relate the localization of living endolithic bacteria to physical and geochemical characteristics of the rock surface. In one experiment, SEIRA microspectroscopy was applied to the study of the relation of the localization of intrinsic endolithic bacteria and the location of vesicles within the basalt specimen. The study area covered 400–500 μm , and was irradiated with a 100- μm diameter infrared beam. The step width in both x and y directions was 50 μm . Figure 2 shows the resulting four contour plots of the area. The first contour [Figure 2(a)] is based on infrared reflectance arising from the mineral silicate functional groups (fundamental asymmetric Si-O-Si and Si-O-Al stretching vibrations in the 1,300–800 cm^{-1} infrared region). The remaining three plots are based on infrared absorption arising from the C=O functional group of biomolecules: stretching vibrations near 1741 cm^{-1} of C=O ester of peptides and proteins [Figure 2(b)], stretching vibrations near 1,650 cm^{-1} of Amide I C=O weakly coupled to the N-H stretching mode [Figure 2(c)], and bending vibrations near 1,550 cm^{-1} of Amide II C=O coupled to the N-H stretching mode [Figure 2(d)]. Figure 2(a), shows two areas of low reflectance intensity in the infrared reflectance from the Si-O-Si and Si-O-Al stretching vibrations. In Figures 2(b–d), each contour map has two areas, at a similar spatial location, of higher intensity in the corresponding infrared functional group image from different C=O vibrational modes of biomolecules. These areas of high absorption intensity from different C=O vibrational modes of biomolecules, however, seem to be at locations near the edge of the two areas of the low reflectance intensity due to the presence of vesicles and extended almost uni-directionally into the basalt matrix. This implies that, similar to endolithic microorganisms in the surface terrestrial environment, subsurface bacteria within vadose vesicular basalts tend to bore into the basalt matrix beneath the vesicle surface.

Figure 2. Contour plots of study area based on absorption intensity from (a) silicate-containing minerals in basalt in 1,300–800 cm^{-1} region, (b) phospholipids in outer membrane of gram-negative bacteria at 1741 cm^{-1} , (c) bacterial protein Amide I at 1,650 cm^{-1} , (d) Amide II at 1,550 cm^{-1} . (Aperture = 50 $\times$ 50 μm .)

SIGNIFICANCE OF FINDINGS

This study demonstrates that SEIRA microspectroscopy using a metal-overlayer is a promising, simple, and analytical tool for studying *in-situ* localization of bacteria within geologic materials such as rocks. The enhanced ester carbonyl peak near 1,740 cm^{-1} of the phospholipids of the bacterial membranes and other absorption bands for bacterial protein Amides I and II in the region between 1,700 and 1,500 cm^{-1} were ideal markers for detecting spatial changes in microbial distribution. The intense features of enhanced reflectance spectra for constituent minerals of basalts in the region between 1,300 and 800 cm^{-1} were ideal marker bands for distribution of minerals and vesicles (gas-bubble cavities) in the basalt specimens. Comparative analyses of space-resolved SEIRA microspectra measurements suggested that bacteria in

the vadose vesicular basalts not only lived on the vesicle surface but also penetrated and lived beneath this surface.

RELATED PUBLICATIONS

- Holman, H.-Y. N., D. L. Perry, M. C. Martin, and W. R. McKinney, Applications of synchrotron infrared microspectroscopy to the study of inorganic-organic interactions at the bacterial-mineral interface, *Application of Synchrotron Radiation Techniques to Materials Sciences, MRS Symp. Series*, in press, 1998a.
- Holman, H.-Y.N., D. L. Perry, and J. C. Hunter-Cevera, Surface-enhanced infrared absorption-reflectance (SEIRA) microspectroscopy — a chemical/biological probe for bacteria localization in geologic materials, *J. Microbiol. Methods*, accepted, 1998b.

FUNDING

This work is supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Division of Materials Sciences; and Office of Biological and Environmental Research, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Publications 1996-1998

- Ahlers, C. F., S. Finsterle, and G. S. Bodvarsson, Characterization and prediction of subsurface pneumatic response at Yucca Mountain, Nevada. *J. Contam. Hydrol.*, accepted.
- Al Mahamid, I., C. F. Novak, K. A. Becraft, S. A. Carpenter, and N. Hakem, Solubility of Np(V) in K-Cl-CO₃ solutions to high concentrations: measurements and thermodynamic model predictions, *Radiochimica Acta*, 222, 1-9, 1997.
- Al Mahamid, I., and B. M. Smith, Literature search on the use of resins for treatment of radioactive wastes, LBNL-40939, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Antolik, M., R. M. Nadeau, R. C. Aster, and T. V. McEvilly, Differential analysis of coda Q using similar microearthquakes in seismic gaps, Part 2: Application to seismograms recorded by the Parkfield High Resolution Seismic Network, *Bull. Seismol. Soc. Am.*, 86(3), 890-910, 1996.
- Apps, J. A., and C.-F. Tsang (eds.), *Scientific and Engineering Aspects of Deep Injection Disposal of Hazardous and Industrial Wastes*, Academic Press, Inc., San Diego, Calif., 1996.
- Bandurraga, T. M., and G. S. Bodvarsson, Calibrating hydrogeological properties for the 3-D site-scale unsaturated zone model of Yucca Mountain, Nevada. *J. Contam. Hydrol.*, accepted.
- Battistelli, A., C. Calore, and K. Pruess, The simulator TOUGH2/EWASG for modeling geothermal reservoirs with brines and non-condensable gas, *Geothermics*, 26, 437-464, 1997.
- Becker, A., B. Wang, K. H. Lee, and M. Wilt, Subsurface electromagnetic measurement through steel casing, in *Expanded Abstracts of the 67th Annual Int'l Meeting, Soc. Exploration Geophysics*, pp. 1965-1968, 1997.
- Bennett, D. H., A. L. James, T. E. McKone, and C. M. Oldenburg, On uncertainty in remediation analysis: variance propagation from subsurface transport to exposure modeling, *Reliability Engineering and System Safety*, 62, 117-129, 1998.
- Benson, S. M., Capturing and sequestering carbon by enhancing the natural carbon cycle: preliminary identification of basic science needs and opportunities, LBNL-40813, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Benson, S. M., Influence of nitrate on the mobility and reduction kinetics of selenium in groundwater systems, *Environ. Chem. Selenium*, 22, 437-457, 1997.
- Birkholzer, J. T., and K. Karasaki, A new Eulerian-Lagrangian finite element simulator for solute transport in discrete fracture-matrix systems, in *Proc. XI Int'l Conference on Computational Methods in Water Resources, Cancun, Mexico, July 22-26, 1996, I*, pp. 263-270, 1996.
- Birkholzer, J. T., and K. Karasaki, FMGN, RENUMN, POLY, TRIPOLY: Suite of programs for calculating flow and transport in fracture networks embedded in porous matrix blocks; theory, design, user's manual and sample applications, LBNL-39387, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.

- Birkholzer, J. T., G. Li, C.-F. Tsang, and Y. W. Tsang, Numerical experiments on the probability of seepage into underground openings in heterogeneous fractured rock, LBNL-41685, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Birkholzer, J. T., Li, G., C.-F. Tsang, and Y. W. Tsang, Modeling Studies and Analysis of Seepage into Drifts at Yucca Mountain, *J. Contam. Hydrol.*, accepted.
- Birkholzer, J., G. Li, C.-F. Tsang, and Y. Tsang, Numerical experiments on the probability of seepage into underground openings at Yucca Mountain, in *Proc. XII International Conference on Computational Methods in Water Resources, Crete, Greece, June, 1998*, Computational Mechanics Publications, Boston, Mass., 1998.
- Birkholzer, J. T., and C.-F. Tsang, Flow channeling in unsaturated heterogeneous soils, in *Proc. XI Int'l Conference on Computational Methods in Water Resources, Cancun, Mexico, July 22-26, 1996, 1*, 647-654, 1996.
- Birkholzer, J. T., and C.-F. Tsang, Solute channeling in unsaturated heterogeneous porous media, *Water Resour. Res.*, 33(10), 2221-2238, 1997.
- Birkholzer, J. T., and Y. Tsang, Forecast of thermal-hydrological conditions and air injection test results of the single heater test at Yucca Mountain, LBNL-39789, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Bodvarsson, G. S., T. M. Bandurraga, and Y. S. Wu (eds.), *Development and Calibration of the Three-Dimensional Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada*, Yucca Mountain Project Level 4 Milestone SP24UFM4, LBNL-39315, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Bodvarsson, G. S., T. M. Bandurraga, and Y. S. Wu (eds.), *The Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada, for the Viability Assessment*, Yucca Mountain Site Characterization Project Milestone SP24UFM4, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Bodvarsson, G. S., W. Boyle, R. Patterson, and D. Williams, Overview of scientific investigations at Yucca Mountain — the potential site for high-level nuclear waste disposal, *J. Contam. Hydrol.*, accepted.
- Bodvarsson, G. S., E. Kwicklis, C. Shan, A. Ritcey, Y. S. Wu, Analysis of temperature data to yield percolation flux at Yucca Mountain, *J. Contam. Hydrol.*, accepted.
- Boitnott, G. N., and A. Kirkpatrick, Interpretation of field seismic tomography at the Geysers Geothermal Field, California, in *Proc. 22nd Workshop on Geothermal Reservoir Engineering, Stanford, CA, SGP-TR-155*, pp. 391-398, Stanford Univ., Stanford, Calif., 1997.
- Borglin, S., and G. J. Moridis, Experimental studies of magnetically driven flow of ferrofluids through porous media, LBNL-40126, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Borglin, S., G. J. Moridis, and A. Becker, Magnetic detection of ferrofluid injection zones, LBNL-40127, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Borglin, S., G. J. Moridis, and C. M. Oldenburg, On magnetic fluid emplacement: laboratory experiments of ferrofluid flow, LBNL-42203, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Chang, F.-R. C., N. T. Skipper, and G. Sposito, Monte Carlo and molecular dynamics simulations of interfacial structure in lithium-montmorillonite hydrates, *Langmuir*, 13(7), 2074-2082, 1997.
- Chang, F.-R. C., N. T. Skipper, and G. Sposito, Monte Carlo and molecular dynamics simulations of electrical double layer structure in potassium-montmorillonite hydrates, *Langmuir*, 14, 1201-1207, 1998.
- Chen, H., G. G. Touchard, and C. J. Radke, A linearized corrosion double-layer model for laminar flow electrification of hydrocarbon liquids in metal pipes, *Indus. Eng. Chem. Res.*, 35(9), 3195-3202, 1996.
- Cohen, A. J. B., Analysis of pressure disturbances in unsaturated rock from installation of new boreholes in Alcove 4, ESF, LBNL-41484, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Cohen, A. J. B., Simulation of pumping tests to characterize faults at Yucca Mountain, Nevada, LBNL-42084, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Cohen, A. J. B., K. Karasaki, B. Friefeld, P. Benito, P. Cook, J. Clyde, K. Grossenbacher, J. Peterson, R. Solbau, B. Thapa, D. Vasco, and P.T. Zawislanski, *Hydrogeologic Characterization of Fractured Rock Formations: A Guide for Groundwater Remediators*, Summary EPA Project EPA/600/S96/001, U.S. Environmental Protection Agency, Washington, D.C., 1996.
- Cohen, A. J. B., J. Najita, K. Karasaki, and A. Simmons, Conceptual model development of saturated zone flow in the vicinity of C-holes, Yucca Mountain, Nevada, Yucca Mountain Project Milestone OBO3M, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Cohen, A. J. B., and C. M. Oldenburg, Effects of faulted stratigraphy on saturated zone flow beneath Yucca Mountain, in *Proc. TOUGH Workshop 1998, Lawrence Berkeley National Laboratory, Berkeley, Calif., May 4-6, 1998*, pp. 95-100, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Cohen, A. J. B., C. M. Oldenburg, A. M. Simmons, A. K. Mishra, and J. Hinds, S^4Z : Sub-site-scale saturated zone model for Yucca Mountain, in *Proc. Int'l High-Level Waste Management Conference and Exposition, Las Vegas, NV, May 11-14, 1998*, LBNL-41773, 1998.
- Cohen, A. J. B., and A. M. Simmons, Development of the sub-site-scale three-dimensional saturated zone flow model: evaluation of flow processes, Yucca Mountain Site Characterization Project Milestone SP33SM4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Cohen, D., T. W. Patzek, and C. J. Radke, Two-dimensional network simulation of diffusion-driven coarsening of foam inside a porous medium, *J. Colloid Interface Sci.*, 179, 357-373, 1996.
- Cohen, D., T. W. Patzek, and C. J. Radke, Onset of mobilization and the fraction of trapped foam in porous media, *Trans. Porous Media*, 28, 253-284, 1997.
- Cohen, R. R., and C. J. Radke, Ionic surface diffusion coefficients using an electrostatic patchy charge model, *J. Electroanal. Chem.*, 405, 23-32, 1996.
- Conrad, M. E., P. F. Daley, M. L. Fischer, B. B. Buchanan, T. Leighton, and M. Kashgarian, Combined ^{14}C and $\delta^{13}C$ monitoring of in situ biodegradation of petroleum hydrocarbons, *Environ. Sci. Tech.*, 31(5), 1463-1469, 1997.
- Conrad, M. E., A. S. Templeton, P. F. Daley, and L. Alvarez-Cohen, Isotopic evidence for biological controls on migration of petroleum hydrocarbons, *Org. Geochem.*, in press.
- Conrad, M., D. Thomas, S. Flexer, and T. Vennemann, Fluid flow and water-rock interaction in the East Rift Zone of Kilauea Volcano, Hawaii, *J. Geophys. Res.*, 102(B7), 15021-15035, 1997.
- Conradson, S. D., I. Al Mahamid, D. L. Clark, N. J. Hess, E. A. Hudson, M. P. Neu, P. D. Palmer, W. H. Runde, and C. D. Tait, Oxidation state determination of plutonium aquo ions using x-ray absorption spectroscopy, *Polyhedron*, 17(4), 599-602, 1998.
- Constable, S., A. Orange, G. M. Hoversten, and H. F. Morrison, Marine magnetotellurics for petroleum exploration, Part 1: A sea-floor equipment system, *Geophysics*, 63(3), 816-825, 1998.
- Cox, B. L., A. Sweet, and E. L. Majer, Application of electrical methods to measure microbial activity in soils: preliminary microcosm results, LBNL-41047, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- DeFlaun, M. E., C. J. Murray, W. Holben, T. Scheibe, A. Mills, T. Ginn, T. Griffin, E. L. Majer, and J. L. Wilson, Preliminary observations on bacterial transport in a coastal plain aquifer, *FEMS Microbiol. Rev.*, 20, 473-487, 1997.
- deGroot-Hedlin, C., and S. Constable, Occam's inversion to generate smooth, two-dimensional models from magnetotelluric data, *Geophysics*, 55, 1613-1624.
- DePaolo, D. J., E. M. Stolper, and D. M. Thomas, The Hawaii scientific drilling project: summary of preliminary results, *GSA Today*, 6(8), 1-8, 1996.
- Dickens, G., and B. M. Kennedy, Noble gases in hydrate from the Black Ridge, in *Proc. Ocean Drilling Program, Scientific Results*, 164, in press.

- Dodson, A., B. M. Kennedy, and D. J. DePaolo, Helium and neon isotopes in the Innaha Basalt, Columbia River Basalt Group: evidence for a Yellowstone plume source, *Earth Planet. Sci. Lett.*, 150, 443-451, 1997.
- Doner, H. E., and M. Zavarin, The role of soil carbonates in trace and minor element chemistry, *Adv. GeoEcology*, 30, 407-422, 1996.
- Dong, Q., and J. W. Rector, Bi-domain modeling of bore-hole wave propagation, in *Expanded Abstracts with Author's Biographies, Society of Exploration Geophysicists Int'l Exposition and 67th Annual Meeting, November 2-7, 1997, Dallas, Tex.*, pp. 262-265, Society of Exploration Geophysicists, Tulsa, Okla., 1998.
- Doughty, C., Investigation of conceptual and numerical approaches for evaluating moisture, gas, chemical, and heat transport in fractured unsaturated rock, *J. Contam. Hydrol.*, accepted.
- Doughty, C., Numerical modeling of field tests in unsaturated fractured basalt at the Box Canyon site, in *Proc. TOUGH Workshop 1998, Berkeley, Calif., May 4-6, 1998*, pp. 210-215, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Drozhko, E. G., Y. U. Glagolenko, Y. G. Mokrov, I. A. Ivanov, G. A. Postovalova, L. M. Samsonova, A. V. Glagolev, S. A. Ter-Saakian, M. L. Glinsky, N. A. Vasil'kova, A. V. Skokov, K. Stevenson, W. Lowder, H. Wollenberg, C.-F. Tsang, W. Frangos, and R. Solbau, Joint Russian-American hydrogeological-geochemical studies on the Karachai-Mishelyak system, South Urals, Russia, *J. Environ. Geol.*, 29(3-4), 216-227, 1996.
- Evans, W. C., M. L. Sorey, R. L. Michel, B. M. Kennedy, and L. J. Hainsworth, Gas-water interaction at Mammoth Mountain, California, USA, in *Proc. 9th Int. Symposium on Water-Rock Interaction — WRI-9, Taupo, New Zealand*, pp. 443-446, 1998.
- Faulques, E., J. D. Zubkowski, and D. L. Perry, Infrared and raman spectra of lead(II)-thiourea lead(II) chloride, *Spectroscopy Lett.*, 29, 1275, 1996.
- Faybishenko, B., Comparison of laboratory and field methods for determination of unsaturated hydraulic conductivity of soils (to be published in *Proc. International Conference Characterization and Measurement of the Hydraulic Properties of Unsaturated Porous Media*) LBNL Report-42022, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Faybishenko, B., C. Doughty, J. C. S. Long, T. Wood, J. Lore, and J. Jacobsen, Conceptual model of geometry and physics of liquid flow in unsaturated fractured basalt at Box Canyon Site, in *Proc. 1997 Fall Meeting of AGU, San Francisco, CA*, American Geophysical Union, Washington, D.C., 1998.
- Faybishenko, B., C. Doughty, J. Geller, S. Borglin, L. Cox, J. Peterson, Jr., M. Steiger, K. Williams, T. Wood, R. Podgorney, T. Stoops, S. Wheatcraft, M. Dragila, and J. Long, A chaotic-dynamical conceptual model to describe fluid flow and contaminant transport in a fractured vadose zone, 1997 progress report, LBNL-41223, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Faybishenko, B., P. Jordan, and M. Mesa, Lithological data report: Box Canyon site 1995-1997 data, LBNL-40182, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Faybishenko, B., J. C. S. Long, J. B. Sisson, C. Doughty, R. Salve, K. Williams, P. Zawislanski, and J. Jacobsen, Field ponded infiltration test in fractured basalt at Box Canyon Analog Site in Idaho: Summary of Preliminary Results, in *Proc. 1996 GSA Annual Conference, Denver, Colo.*, 1996.
- Faybishenko, B., R. Salve, P. T. Zawislanski, K. H. Lee, P. Cook, B. Freifeld, J. Jacobsen, B. Sisson, J. Hubbell, and K. Dooley, Ponded infiltration test at the Box Canyon Site: Data report and preliminary analysis, LBNL-40183, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Faybishenko, B., T. R. Wood, T. M. Stoops, C. Doughty, and J. Jacobsen, A conceptual model of tracer transport in fractured basalt: large scale infiltration test revisited, in *Proc. 1997 GSA Annual Conference, Salt Lake City, Utah*, 1997.

- Feighner, M. A., T. M. Daley, and E. L. Majer, Results of vertical seismic profiling at Well 46-28, Rye Patch geothermal field, Pershing County, Nevada, LBNL-41800, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Feighner, M. A., T. M. Daley, R. Gritto, and E. L. Majer, Report on CDP reflection image and subsurface structure along lines B and C: UZ-16 VSP, Yucca Mountain Project Report, LBNL-40926, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Feighner, M. A., T. M. Daley, R. Gritto, and E. L. Majer, results of VSP analysis in P#1, Yucca Mountain Project Level-4 Milestone, SP3B6AM4, LBNL-41799, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Finkel, R. C., and K. Nishiizumi, Beryllium 10 concentrations in the Greenland Ice Sheet project 2 ice core from 3-40 ka, *J. Geophys. Res.*, 102, 26,699-26,706, 1997.
- Finsterle, S., and B. Faybishenko, Design and analysis of an experiment to determine hydraulic parameters of variably saturated porous media, *Adv. Water Resour.*, in press.
- Finsterle, S., and B. Faybishenko, What does a tensiometer measure in fractured rock?, in *Proc. Int'l Workshop on Characterization and Measurement of the Hydraulic Properties of Unsaturated Porous Media, Riverside, CA, October 22-24, 1997*, in press.
- Finsterle, S., A. L. James, J. S. Y. Wang, J. T. Fabryka-Martin, L. E. Wolfsberg, A. Flint, and W. R. Guertal, Model prediction of local plume migration from the cross drift, Yucca Mountain Project Milestone SP3S3M4, Lawrence Berkeley National Laboratory, Calif., 1998.
- Finsterle, S., ITOUGH2 command reference, Version 3-1, LBNL-40041, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Finsterle, S., ITOUGH2 sample problems, LBNL-40042, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Finsterle, S., Multiphase inverse modeling: an overview, in *Proc. Geothermal Program Review XVI, Berkeley, Calif., April 1-2, 1998*, LBNL-41638, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Finsterle, S., Parallelization of ITOUGH2 using PVM, LBNL-42261, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Finsterle, S., and J. Najita, Robust estimation of hydrogeologic model parameters, *Water Resour. Res.*, in press.
- Finsterle, S., C. M. Oldenburg, A. L. James, K. Pruess, and G. J. Moridis, Mathematical modeling of permeation grouting and subsurface barrier performance, in *Proc. 1997 Int'l Containment Technology Conference and Exhibition, St. Petersburg, FL, February 9-12, 1997*, pp. 438-444, Florida State University, Tallahassee, Fla., 1997.
- Finsterle, S., and P. Persoff, Determining permeability of tight rock samples using inverse modeling, *Water Resour. Res.*, 33(8), 1803-1811, 1996.
- Finsterle, S., and K. Pruess, Design and analysis of a well test for determining two-phase hydraulic properties, LBNL-39620, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Finsterle, S., and K. Pruess, Development of inverse modeling techniques for geothermal applications, in *Proc. DOE Geothermal Program Review 15, San Francisco, CA, March 24-26, 1997*, DOE/EE-0139, pp. 2-47 to 2-54, U.S. Dept. of Energy, Washington, D.C., 1997.
- Finsterle, S., K. Pruess, D. P. Bullivant, and M. J. O'Sullivan, Applications of inverse modeling to geothermal reservoir simulation, in *Proc. 22nd Workshop on Geothermal Reservoir Engineering, Stanford, CA*, pp. 309-316, SGP-TR-155, Stanford Univ., Stanford, Calif., 1997.
- Finsterle, S., C. Satik, and M. Guerrero, Analysis of boiling experiment using inverse modeling, in *Proc. TOUGH Workshop 1998, Berkeley, Calif., May 4-6, 1998*, pp. 281-287, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Finsterle, S., T. O. Sonnenborg, and B. Faybishenko, Inverse modeling of a multistep outflow experiment for determining hysteretic hydraulic properties, in *Proc. TOUGH Workshop 1998, May 4-6*, pp. 250-256, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Fitzgerald, S. D., C. T. Wang, and K. Pruess, Laboratory and theoretical studies of injection into horizontal fractures, in *Proc. 18th New Zealand Geothermal Workshop, Auckland, NZ*, pp. 267-273, New Zealand Geothermal Assoc., Auckland, New Zealand, 1996.
- Frangos, W., and S. Ter-Saakian, Resistivity and induced polarization survey at a Russian nuclear waste site, *Geophysics*, in press.
- Freifeld, B., L. Myer, G. Moridis, P. Cook, A. James, L. Pellerin, and K. Pruess, Lance water injection tests adjacent to the 281-3H retention basin at the Savannah River Site, Aiken, South Carolina, LBNL-39028, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Fung, P., H. Chen, G. G. Touchard, and C. J. Radke, A nonlinear corrosion double-layer model for laminar flow electrification of hydrocarbon liquids in long metal pipes, *J. Electrostatics*, 40-41, 445-53, 1997.
- Garg, A., M. Nikravesh, A. R. Kovscek, L. M. Castanier, and T. W. Patzek, CT scan and neural network technology for construction of detailed distribution of residual oil saturation during waterflooding, in *Proc. the 66th Western Regional Meeting, Alaska, USA, May 15-18, 1996*, SPE 35737, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Garg, A., E. Zwahlen, and T. W. Patzek, Experimental and numerical studies of one-dimensional imbibition in Berea Sandstone, in *Proc. Sixteenth Annual American Geophysical Union Hydrology Days, Denver, CO, April 15-18, 1996*, pp. 171-183, American Geophysical Union, Washington, D.C., 1996.
- Geller, J. T., Laboratory studies of groundwater degassing in replicas of natural fractured rock for linear flow geometry, LBNL-41386, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Geller, J. T., G. Su, H.-Y. Holman, M. Conrad, T.-S. Loiu, K. Pruess, and J. C. Hunter-Cevera, Processes controlling the migration and biodegradation of non-aqueous phase liquids (NAPLs) within fractured rocks in the vadose zone, FY97 annual report, LBNL-41387, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Geller, J. T., G. Su, H.-Y. Holman, M. Conrad, K. Pruess, and J. C. Hunter-Cevera, Processes controlling the migration and biodegradation of non-aqueous phase liquids (NAPLs) within fractured rocks in the vadose zone, FY96 annual report, LBNL-39996, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Geller, J., G. Su, and K. Pruess, Preliminary studies of water seepage through rough-walled fractures, LBNL-38810, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Gittleman, C. S., A. T. Bell, and C. J. Radke, The role of alkali cations in zeolite synthesis from silicate solutions containing N, N, N-trimethyl-1-adamantammonium cations, *Catalysis Lett.*, 38, 1-9, 1996.
- Goldstein, A. H., B. C. Duabe, J. W. Munger, and S. C. Wofsy, Automated in-situ monitoring of atmospheric non-methane hydrocarbon concentrations and gradients, *J. Atmos. Chem.*, 21, 43-59, 1995.
- Goldstein, A. H., S. C. Wofsy, and C. M. Spivakovsky, Seasonal variations of nonmethane hydrocarbons in rural New England: constraints on OH concentrations in northern midlatitudes, *J. of Geophys. Res.*, 100(D10), 21023-21033, 1995.
- Greathouse, J., and G. Sposito, Monte Carlo and molecular dynamics studies of interlayer structure in $\text{Li}(\text{H}_2\text{O})_3$ -smectites, *J. Phys. Chem.*, B102, 2406-2414, 1998.
- Gritto, R., V. A. Korneev, and L. R. Johnson, Location of underground cavities using scattered elastic waves, *EOS Trans.*, 77, 497, American Geophysical Union, Washington, D.C., 1996.
- Gritto, R., V. A. Korneev, and J. E. Peterson, The effect of source and receiver coupling on travel time and amplitude inversion results, *EOS Trans.*, 78(46), 462, 1997.
- Grossenbacher, K., K. Karasaki, and D. Bahat, Curved scanline theory, *Math. Geol.*, 29(5), 629-651, 1997.
- Gu, B., K. T. Nihei, and L. R. Myer, Numerical investigation of fracture interface waves, *J. Acoust. Soc.*, 102(1), 120-127, 1997.
- Gu, B., K. Nihei, and L. Myer, Numerical simulation of elastic wave propagation in fracture rock with the boundary integral equation method, *J. Geophys. Res.*, 101(B7), 15,933-15,943, 1996.

- Gu, B., K. T. Nihei, L. R. Myer, and L. J. Pyrak-Nolte, Fracture interface waves, *J. Geophys. Res.*, 101(B1), 827-835, 1996.
- Gu, B., R. Suarez-Rivera, K. Nihei, and L. Myer, Incidence of plane waves upon a fracture, *J. Geophys. Res.*, 101(B11), 25,337-25,346, 1996.
- Hakem, N., I. Al Mahamid, J. Apps, and G. Moridis, Sorption of cesium and strontium on Savannah River soils impregnated with colloidal silica (presented at the 1997 International Containment Technology Conference & Exhibition, St. Petersburg, Florida, February 9-12, 1997), LBNL-39498, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Haukwa, C., Wu, Y. S., and G. S. Bodvarsson, Thermal loading studies using the UZ model, *J. Contam. Hydrol.*, accepted.
- Hildenbrand, K., and T. N. Narasimhan, Aquifer characterization by passive monitoring: a case study, LBNL-41086, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Holman, H.-Y., and I. Javandel, Evaluation of transient dissolution of slightly water-soluble compounds from a light nonaqueous phase liquid pool, *Water Resour. Res.*, 32(4), 915-923, 1996.
- Holman, H.-Y. N., Y. Mao, and R. Goth-Goldstein, Bioavailability of organic compounds from solid environmental matrices, in *Proc. 18th SETAC Symposium, Bridging the Global Environment: Technology, Communication, and Education*, 335, Society of Environmental Toxicology and Chemistry, Pensacola, Fla., 1997.
- Holman, H.-Y. N., D. L. Perry, and J. C. Hunter-Cevera, Surface-enhanced infrared absorption-reflectance (SEIRA) microspectroscopy — a chemical/biological probe for bacteria localization in geologic materials, *J. Microbio. Methods*, accepted.
- Holman, H.-Y. N., D. L. Perry, M. C. Martin, and W. R. McKinney, Applications of synchrotron infrared microspectroscopy to the study of inorganic-organic interactions at the bacterial-mineral interface, *Application of Synchrotron Radiation Techniques to Materials Sciences, MRS Symp. Series*, 54, in press.
- Hoversten, G. M., H. F. Morrison, and S. Constable, Marine magnetotellurics for petroleum exploration, Part 2: Numerical analysis of subsalt resolution, *Geophysics*, 63(3), 826-840, 1998.
- Huang, P., and L. R. Myer, Study of the effects of pore structure on flow properties of porous media by using pore-level network model, in *Proc. of the AGU 1997 Fall Meeting, San Francisco, California, December 8-12, 1997*, American Geophysical Union, Washington, D.C., 1998.
- Huang, P., G. Yang, L. R. Myer, and N. Cook, Simulation of capillary hysteresis in drainage and imbibition process, *Int. J. Rock Mech. & Min. Sci.*, 34(3-4), 135, 1997.
- Hubbard, S. S., E. Majer, J. Geller, J. Peterson, and B. Parsons, Permeability estimation using geophysical data, *EOS Trans.*, 77(46), F220, American Geophysical Union, Washington, D.C., 1996.
- Hubbard, S. S., J. E. Peterson, E. L. Majer, P. T. Zawislanski, J. Roberts, and K. Williams, Estimation of permeable pathways and water content using tomographic radar data, *The Leading Edge*, 16(11), 1623-1628, 1997.
- Hubbard, S. S., Y. Rubin, and E. Majer, Estimation of hydrogeological parameters and their spatial correlation structure using geophysical methods, in *Groundwater Quality: Remediation and Protection*, edited by E. M. Herveret and K. Kovar, IAHS Publication 250, IAHS Press, Wallingford, UK, 1998.
- Hubbard, S. S., Y. Rubin, and E. Majer, Estimation of hydrological model parameters from spectral analysis of high-resolution geophysical data, *EOS Trans.*, 78(48), American Geophysical Union, Washington, D.C., 1997.
- Hubbard, S. S., Y. Rubin, and E. L. Majer, Ground-penetrating-radar-assisted saturation and permeability estimation in bimodal systems, *Water Resour. Res.*, 33(5), 971-990, 1997.
- Huyakorn, P. S., Y. S. Wu, and N. S. Park, A multiphase approach to the numerical solution of a sharp interface saltwater intrusion problem, *Water Resour. Res.*, 32(1), 93-102, 1996.

- Ilderton, D., T. W. Patzek, J. W. Rector, and H. J. Vinegar, passive imaging of hydrofractures in the South Belridge Diatomite, *SPE Formation Evaluation J.*, 46-54, March 1996.
- Ingram, B. L., J. C. Ingle, and M. E. Conrad, Stable isotope record of late holocene salinity and river discharge in San Francisco Bay, California, *Earth Planet. Sci. Lett.*, 141, 237-247, 1996.
- James, A. L., and C. M. Oldenburg, Enhanced data analysis for the VZMS: conceptual model design and initial application for the vadose zone monitoring system (VZMS), McClellan AFB: 1998 semi-annual report, LBNL-41909, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- James, A. L., and C. M. Oldenburg, Linear and Monte Carlo uncertainty analysis for subsurface contaminant transport simulation, *Water Resour. Res.*, 33(11), 2495-2508, 1997.
- Johnson, T. M., and D. J. DePaolo, Rapid exchange effects on isotope ratios in groundwater systems, 1. Development of a transport-dissolution-exchange model, *Water Resour. Res.*, 33(1), 187-195, 1996.
- Johnson, T. M., and D. J. DePaolo, Rapid exchange effects on isotope ratios in groundwater systems, 2. Flow investigation using Sr isotope ratios at Lawrence Berkeley National Laboratory, Berkeley, Calif., *Water Resour. Res.*, 33(1), 197-209, 1996.
- Johnson, T. M., and D. J. DePaolo, Reaction-transport models for radio carbon in groundwater: the effects of dispersive transport and the use of Sr isotope ratios to correct for water-rock interaction, *Water Resour. Res.*, 32(7), 2203-2212, 1996.
- Kaelin, B., and L. R. Johnson, Dynamic composite elastic medium theory. Part I. One-dimensional media, *J. Appl. Phys.*, in press.
- Kaelin, B., and L. R. Johnson, Dynamic composite elastic medium theory. Part II. Three-dimensional media, *J. Appl. Phys.*, in press.
- Kaelin, B., and L. R. Johnson, Using seismic crosswell surveys to determine the aperture of partially water saturated fractures, *Geophysics*, accepted, 1998.
- Kaelin, B., Seismic imaging of the shallow subsurface with high frequency seismic measurements, Ph.D. Thesis, LBNL-42058, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Kalinin, V. V., and C. J. Radke, An ion-binding model for ionic surfactant adsorption at aqueous-fluid interfaces, *Colloids and Surfaces A: Physicochem. & Eng. Aspects*, 114, 337-350, 1996.
- Karageorgi, E., T. V. McEvilly, and R. Clymer, Seismological studies at Parkfield IV: variations in controlled-source waveform parameters and their correlation with fault-zone activity, 1987 to 1995, *Bull. Seismol. Soc. Am.*, 87, 39-49, 1996.
- Kennedy, B. M., D. Benoit, and A. H. Truesdell, A preliminary survey of noble gases at Dixie Valley, Nevada, in *Proc. Geothermal Resources Council 1996 Meeting, Portland, OR, September 29-October 2, 1996*, 20, pp. 815-820, Geothermal Resources Council, Davis, Calif., 1996.
- Kennedy, B. M., A. Ellwood, D. M. DePaolo, Y. K. Kharaka, W. C. Evans, and J. Thordsen, Isotopic evidence for mantle fluids in the San Andreas fault, *EOS Trans.*, 79, S223, American Geophysical Union, Washington, D.C., 1998.
- Kennedy, B. M., and D. J. DePaolo, Isotopic and noble gas geochemistry in geothermal research, in *Proc. DOE Geothermal Review 15, March 25-26, 1997, San Francisco, CA, DOE/EE-0139*, pp. 2-7 to 2-13, U.S. Dept. of Energy, Washington, D.C., 1997.
- Kennedy, B. M., Y. K. Kharaka, W. C. Evans, A. Ellwood, D. J. DePaolo, J. Thordsen, G. Ambats, R. H. Mariner, Mantle fluids in the San Andreas fault system, California, *Science*, 278, 1278-1281, 1997.
- Kennedy, B. M., and T. Torgersen, Chemical and isotopic study of fluids from San Joaquin Basin oil fields, *EOS Trans.*, 77, F236-237, American Geophysical Union, Washington, D.C., 1996.
- Kennedy, B. M., and A. H. Truesdell, The Northwest Geysers high-temperature reservoir: evidence for active magmatic degassing and implications for the origin of The Geysers geothermal field, *Geothermics*, 25, 365-387, 1996.

- Kharaka, Y., B. M. Kennedy, J. J. Thordsen, and W. C. Evans, Role of fluids in the dynamics of the San Andreas fault system, California, USA, in *Proc. Int'l Conference on Fluid Evaluation, Migration, and Interaction with Rocks, Geofluids Belfast, N. Ireland, 1997*, pp. 107-110, 1997.
- Kharaka, Y. K., J. J. Thordsen, W. C. Evans, and B. M. Kennedy, Fluids and faults: the chemistry, origin and interactions of fluids associated with the San Andreas fault system, California, USA, in *Proc. 9th Int. Symposium on Water-Rock Interaction — WRI-9, Taupo, New Zealand*, pp. 781-784, 1998.
- Kim, H. J., N. L. Miller, A. K. Guetter, and K. P. Georgakakos, River flow response to precipitation and snow budget in California during the 1994-1995 winter, *J. Climate*, in press.
- Kim, H. J., Y. Song, and K. H. Lee, High-frequency electromagnetic inversion for a dispersive layered earth, *Geomagnetism and Geoelectricity*, 49, 1439-1450, 1997.
- Kirkpatrick, A., J. Peterson, and E. Majer, Source mechanisms of microearthquakes at the Southeast Geysers Geothermal Field, California, in *Proc. 21st Workshop on Geothermal Reservoir Engineering, Stanford, CA*, SGP-TR-151, pp. 359-366, Stanford Univ., Stanford, Calif., 1996.
- Kirkpatrick, A., J. E. Peterson, Jr., and E. L. Majer, Three-dimensional compressional and shear-wave seismic velocity models for the Southeast Geysers, in *Proc. Twenty-Second Workshop on Geothermal Reservoir Engineering, Stanford University, Stanford, CA, January 27-29, 1997*, SGP-TR-155, pp. 399-410, Stanford University, Stanford, Calif. 1997.
- Kirkpatrick, A., A. Romero, Jr., J. Peterson, Jr., L. Johnson, and E. Majer, Microearthquake source mechanism studies at the geysers geothermal field, in *Proc. DOE Geothermal Program Review XIV, April 8-10, 1996, Berkeley, Calif.*, pp. 161-173, DOE/EE-0106, U.S. Dept. of Energy, Washington, D.C., 1996.
- Kneafsey, T., and K. Pruess, Experimental studies of vaporizing flows in unsaturated fractures, *EOS Trans.*, 78(46), F308 (supplement), American Geophysical Union, Washington, D.C., 1997.
- Kneafsey, T., and K. Pruess, Laboratory experiments on heat-driven two-phase flows in natural and artificial rock fractures, *Water Resour. Res.*, accepted.
- Kneafsey, T., and K. Pruess, Preferential flow paths and heat pipes: results from laboratory experiments on heat-driven flow in natural and artificial rock fractures, LBNL-40467, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Kneafsey, T., and K. Pruess, Thermohydrological laboratory tests — insights into processes and behavior, in *Proc. Int'l High-Level Radioactive Waste Management Conference, Las Vegas, Nevada*, pp. 261-263, American Nuclear Society, La Grange Park, Ill., 1997.
- Korneev, V. A., K. T. Nihei, and L. R. Myer, Nonlinear interaction of plane elastic waves, LBNL-41914, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Kovscek, A. R., T. W. Patzek, and M. Johnston, Evaluation of rock/fracture interactions during steam injection through vertical hydrofractures, *SPE Production and Facilities*, 100-105, May 1997.
- Kovscek, A. R., R. M. Johnston, and T. W. Patzek, Analysis of hydrofracture geometry and matrix/fracture interactions during steam injection, in *Proc. 1996 SPE/DOE Tenth Symposium on Improved Oil Recovery, Tulsa, OK, April 21-24*, SPE 35396, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Kovscek, A. R., R. M. Johnston, and T. W. Patzek, Interpretation of hydrofracture geometry using temperature transients II: Asymmetric hydrofractures, *In Situ*, 20(3), 251-289, 1996.
- Kovscek, A. R., T. W. Patzek, and C. J. Radke, Mechanistic foam flow simulation in heterogeneous and multidimensional media, SPE 39102, *SPEJ*, 2(4) 511-526, 1997.
- Kovscek, A. R., and C. J. Radke, Gas bubble snap-off under pressure-driven flow in constricted noncircular capillaries, *Colloids and Surfaces A: Physicochem. & Eng.*, 117, 55-76, 1996.
- Lee, K. H., H. J. Kim, and Y. H. Song, Electromagnetic method for analyzing the property of steel casing, LBNL-41525, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Lippmann, M. J., and E. U. Antunez, Information systems and technology transfer programs on geothermal energy and other renewable sources of energy, in *Proc. 21st Workshop on Geothermal Reservoir Engineering, Stanford, CA, January 22-24, 1996*, SGP-TR-151, pp. 9-19, Stanford Univ., Stanford, Calif., 1996.
- Lippmann, M. J., A. H. Truesdell, and H. Gutierrez Puente, What will a 6 km deep well at Cerro Prieto find?, in *Proc. 22nd Workshop on Geothermal Reservoir Engineering, Stanford, CA, January 27-29, 1997*, SGP-TR-155, pp. 19-28, Stanford Univ., Stanford, Calif., 1997.
- Liu, H. H., C. Doughty, and G. S. Bodvarsson, An active fracture model for unsaturated flow and transport in fractured rocks, *Water Resour. Res.*, **34**, 2633-2646, 1998.
- Majer, E. L., A. Datta-Gupta, J. E. Peterson, D. W. Vasco, L. R. Myer, T. M. Daly, B. Kaelin, J. Queen, P. S. D'Onfro, W. D. Rizer, D. Cox, and J. Sinton, Utilizing crosswell, single well and pressure transient test for characterizing fractured gas reservoirs, *The Leading Edge*, **15**, 951-956, 1996.
- Majer, E. L., M. Feighner, L. Johnson, T. Daley, E. Karageorgi, K. H. Lee, B. Kaelin, K. Williams, and T. McEvelly, Synthesis of borehole and surface geophysical studies at Yucca Mountain, Nevada and vicinity, Volume I: Surface geophysics, LBNL-39319, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Majer, E. L., M. Feighner, L. Johnson, T. Daley, K. Williams, E. Karageorgi, and T. V. McEvelly, Results and interpretation of multiple geophysical surveys at Yucca Mountain, Nevada, LBL-38200, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Majer, E. L., M. Feighner, L. Johnson, K. H. Lee, T. Daley, E. Karageorgi, P. Parker, T. Smith, K. Williams, A. Romero, T. McEvelly, D. Ponce, and V. Langeheim, Results of multiple high-resolution geophysical surveys at Yucca Mountain, in *Proc. IHLRWM Conference, American Nuclear Society, Las Vegas, Nevada, CA, April 29-May 3, 1996*, American Nuclear Society, La Grange Park, Ill., 1996.
- Majer, E. L., J. E. Peterson, T. Daley, B. Kaelin, L. R. Myer, J. Queen, P. D'Onfro, and W. Rizer, Fracture detection using crosswell and single well surveys, *Geophysics*, **62**(2), 495-504, 1996.
- McCauley, S. E., and D. J. DePaolo, The marine $^{87}\text{Sr}/^{86}\text{Sr}$ and $\delta^{18}\text{O}$ records, Himalayan alkalinity fluxes, and Cenozoic climate models, in *Tectonic Uplift and Climate Change*, edited by W.F. Ruddiman, pp. 427-467, Plenum Press, New York, N.Y., 1997.
- Miller, N. L., and J. Kim, The regional climate system model, in *Mission Earth: Modeling and Simulation for a Sustainable Global System*, edited by M. C. Clymer and C. R. Mechoso, pp. 43-52, Pub. Soc. Comp. Sim., 1997.
- Moore, J. N., D. I. Norman, B. M. Kennedy, and M. C. Adams, Origin and chemical evolution of The Geysers, California hydrothermal fluids: implications from fluid inclusion gas compositions, *Geothermal Resour. Counc. Trans.*, **21**, 635-641, 1997.
- Moridis, G. J., Evaluation of alternative designs for an injectable barrier at the Brookhaven National Laboratory Site, Long Island, New York, LBNL-41763, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Moridis, G. J., Semi-analytical solutions for parameter estimation in diffusion cell experiments, LBNL-41857, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Moridis, G. J., TOUGH90: A FORTRAN90 implementation of TOUGH2, in *Proc. TOUGH Workshop 1998, Berkeley, Calif., May 4-6, 1998*, pp. 300-306, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Moridis, G. J., J. Apps, P. Persoff, L. Myer, S. Muller, P. Yen, and K. Pruess, A field test of a waste containment technology using a new generation of injectable barrier liquids, in *Proc. Spectrum 1996, Seattle, WA, August 18-23, 1996*.
- Moridis, G. J., S. Borglin, C. M. Oldenburg, and A. Becker, Theoretical and experimental investigations of ferrofluids for guiding and detecting liquids in the subsurface, FY 1997 annual report, LBNL-41069, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Moridis, G. J., A. James, and C. M. Oldenburg, Development of a design package for a viscous barrier at The Savannah River Site, in *Proc. 1997 Int'l Containment Technology Conference and Exhibition, St. Petersburg, Florida, February 9-12, 1997*, pp. 452-458, 1997.
- Moridis, G. J., and C. M. Oldenburg, Principles of ferrofluid flow in porous media, LBNL-40167, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Moridis, G. J., P. Persoff, J. Apps, A. James, C. M. Oldenburg, A. McGrath, L. Myer, L. Pellerin, and K. Pruess, A design study for the isolation of the 281-3H retention basin at the Savannah River site using the viscous barrier technology, LBNL-38920, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Moridis, G. J., and K. Pruess, T2SOLV: An enhanced package of solvers for the TOUGH2 family of codes, in *Proc. 22nd Workshop on Geothermal Reservoir Engineering, Stanford, CA, January 27-29, 1997*, SGP-TR-155, pp. 295-301, Stanford Univ., Stanford, Calif., 1997.
- Moridis, G., and K. Pruess, T2SOLV: an enhanced package of solvers for the TOUGH2 family of reservoir simulation codes, *Geothermics*, in press.
- Moridis, G. J., P. Yen, P. Persoff, S. Finsterle, P. Williams, L. Myer, and K. Pruess, A design study for a medium-scale field demonstration of the viscous barrier technology, LBNL-38916, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Mountford, H. S., Onshore oil spill impact: data assessment, physical processes, and preliminary recommendations, LBNL-39256, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Myer, L., J. Jacobsen, J. Horsman, J. T. Fredrich, W. R. Wawersik, J. G. Arguello, M. Bruno, and H. Qian, Use of visualization techniques in analysis of well failures in diatomite reservoirs, *The Leading Edge*, 15, 185-189, 1996.
- Myneni, S. C. B., T. K. Tokunaga, and G. E. Brown, Abiotic selenium redox transformations in the presence of Fe (II, III) oxides, *Science*, 278, 1106-1109, 1997.
- Nadeau, R. M., and L. R. Johnson, Seismological studies at Parkfield VI: moment release rates and estimates of source parameters from small repeating earthquakes, *Bull. Seismol. Soc. Am.*, 88(3), 790-814, 1998.
- Nadeau, R. M., and T. V. McEvilly, Seismological studies at Parkfield V: characteristic microearthquake sequences as fault-zone drilling targets, *Bull. Seismol. Soc. Am.*, 87(6), 1463-1472, 1997.
- Najita, J., and C. Doughty, Using TRINET for simulating flow and transport in porous media, LBNL-42158, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Nakao, S., J. Najita, and K. Karasaki, Sensitivity study on hydraulic well testing inversion using simulated annealing, LBNL-41131, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Narasimhan, T. N., Basic postulates of groundwater occurrence and movement, LBNL-41235, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Narasimhan, T. N., Fourier's heat conduction equation: history, influence, and connections, LBNL-41798, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Narasimhan, T. N., Hydraulic characterization of aquifers, reservoir rocks and soils: a history of ideas, *Water Resour. Res.*, 34(1), 33-46, 1997.
- Narasimhan, T. N., A note on setting up the diffusion equation, LBNL-41234, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Narasimhan, T. N., and N. W. T. Quinn, Agriculture, irrigation and drainage on the west side of the San Joaquin Valley, California: unified perspective on hydrogeology, geochemistry and management, LBNL-38498, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Neue, G., C. A. Dybowski, M. L. Smith, M. A. Hepp, and D. L. Perry, Determination of $^{207}\text{Pb}^{2+}$ chemical shift tensors from precise powder lineshape analysis, *Sol. State Nucl. Mag. Resonance*, 6, 241, 1996.

- Nikravesh, M., Dynamic neural network control of nonlinear-time varying systems: stability analysis, optimal network structure, and on-line adaptation, in *Proc. NAFIPS '96 Biennial Conference of the No. Am. Fuzzy Info. Processing Society, Berkeley, Calif., June 19-22, 1996*, pp. 1128-133, 1996.
- Nikravesh, M., A. Garg, A. R. Kavscek, L. M. Castanier, and T. W. Patzek, Neural network and its application to CT scanning, in *Proc. Workshop on High Resolution X-Ray Computed Microtomography, LBNL, Berkeley, Calif., Aug. 12-13, 1996*, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Nikravesh, M., A. Garg, and T. W. Patzek, Neural network-based reconstruction of CT scan images (presented at the 32nd Western Regional Meeting and 35th Pacific Conference on Chemical and Spectroscopy, San Francisco, Calif., October 30-November 2, 1996), SPE 35737, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Nikravesh, M., A. R. Kavscek, R. M. Johnston, and T. W. Patzek, Prediction of formation damage during fluid injection into fractured, low permeability reservoirs via neural networks, in *Proc. SPE Formation Damage Symposium Lafayette, LA, February 14-15, 1996*, SPE 31103, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Nikravesh, M., A. R. Kavscek, A. R. Murer, and T. W. Patzek, Field-wise waterflood management using neural networks, in *Proc. the 66th Western Regional Meeting, Alaska, USA, May 15-18, 1996*, SPE 35721, Society of Petroleum Engineering, Dallas, Tex., 1996.
- Nikravesh, M., A. R. Kavscek, A. S. Murer, and T. W. Patzek, Neural networks for field-wise waterflood management in low permeability, fractured oil reservoirs (presented at the 66th SPE Western Regional Meeting, Anchorage, AK, May 22-24, 1996), SPE 35721, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Nikravesh, M., A. R. Kavscek, and T. W. Patzek, Dividing oil fields into regions with similar characteristic behavior using neural network and fuzzy logic approaches, in *Proc. NAFIPS 1996 Biennial Conference of the N. A. Fuzzy Info. Proc. Society, Berkeley, Calif., June 19-22, 1996*, pp. 164-169, 1996.
- Nikravesh, M., A. R. Kavscek, and T. W. Patzek, Identification and control of industrial-scale processes via neural networks, in *Proc. Fifth Int'l Conference on Chemical Process Control, CPCV Conference, Tahoe City, CA, January 5-12, 1996*, pp. 284-287, 1996.
- Nikravesh, M., and M. Soroush, Theoretical methodology for prediction of gas-condensate flow behavior (presented at the SPE Annual Technical Conference and Exhibition, Denver, Colorado, October 6-9, 1996), SPE 36704, Society of Petroleum Engineers, Dallas, Tex., 1996.
- Nikravesh, M., M. Soroush, M. Johnston, and T. W. Patzek, Design of smart wellhead controllers for optimal fluid injection policy and producibility in petroleum reservoirs: neuro-geometric approach (presented at the International Thermal Operations and Heavy Oil Symposium, February 10-12, 1997, Bakersfield, Calif.), SPE 37557, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Nikravesh, M., M. Soroush, M. Johnston, and T. W. Patzek, Design of smart wellhead controllers for optimal fluid injection policy and producibility in petroleum reservoirs: a neural network-model predictive approach (presented at the SPE Production Operations Symposium, Oklahoma City, OK, March 9-11, 1997), SPE 37445, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Nishiizumi, K., M. W. Caffee, A. J. T. Jull, and R. C. Reedy, Exposure history of lunar meteorites Queen Alexandra Range 93069 and 94269, *Meteorit. Planet. Sci.*, **31**, 893-896, 1996.
- Noorishad, J., and C.-F. Tsang, Coupled thermohydroelasticity phenomena in variably saturated fractured porous rocks — formulation and numerical solution, in *Coupled Thermo-Hydro-Mechanical Processes in Fractured Media*, edited by O. Stephansson, L. Jung, and C.-F. Tsang, pp. 93-134, Elsevier Sci., New York, N.Y., 1996.
- Novak, C. F., I. Al Mahamid, K. A. Becraft, S. A. Carpenter, N. Haken, and T. Prussin, Measurement and thermodynamic modeling of Np(V) solubility in aqueous K₂CO₃ solutions to high concentrations, *J. Solution Chem.*, **26**(7), 681, 1997.

- Novikov, A. P., F. I. Pavlotskaya, E. M. Korobova, T. A. Goryachenkova, I. E. Kazinskaya, E. M. Kuzovkina, and B. F. Myasoedov, Distribution, speciation, and computational migration model of selected radioactive nuclides in some ecosystems from the Mayak Region, LBNL-39168, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Oldenburg, C. M., Comparison of scale analysis and numerical simulation for saturated zone convective mixing processes, LBNL-40365, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Oldenburg, C. M., S. E. Borglin, and G. J. Moridis, Numerical simulation of ferrofluid flow for subsurface environmental engineering applications, LBNL-40146, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Oldenburg, C. M., S. E. Borglin, and G. J. Moridis, On modeling flow and transport of magnetic fluids in porous media, LBNL-40146, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Oldenburg, C. M., J. C. S. Long, J. S. Jacobsen, A. L. James, A. R. Kovscek, H. S. Mountford, Onshore oil spill impact: data assessment, physical processes, and preliminary recommendations, LBNL-39256, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Oldenburg, C. M., and G. J. Moridis, Ferrofluid flow for TOUGH2, in *Proc. TOUGH Workshop 1998*, pp. 263-268, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Oldenburg, C. M., and K. Pruess, Application of TOUGH2/ EOS7R to modeling of radionuclide release from a low/intermediate level repository under two-phase conditions, LBNL-38837, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Oldenburg, C. M., and K. Pruess, Higher-order differencing for front propagation in geothermal systems, in *Proc. TOUGH Workshop 1998*, pp. 13-18, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Oldenburg, C. M., and K. Pruess, Higher-order differencing for geothermal reservoir simulation, in *Proc. 22nd Workshop on Geothermal Reservoir Engineering, Stanford, CA, January 27-29, 1997*, SGP-TR-155, pp. 303-308, Stanford Univ., Stanford, Calif., 1997.
- Oldenburg, C. M., and K. Pruess, Higher-order differencing for phase-front propagation in geothermal systems, in *Proc. Twenty-Third Workshop on Geothermal Reservoir Engineering, Stanford, CA, January 26-28, 1998*, pp. 127-134, SGP-TR-158, Stanford Univ., Stanford, Calif., 1998.
- Oldenburg, C. M., and K. Pruess, Layered thermohaline convection in hypersaline geothermal systems, *Trans. Porous Media*, in press.
- Oldenburg, C. M., and K. Pruess, Mixing with first-order decay in variable velocity porous media flow, *Trans. Porous Media*, 22, 161-180, 1996.
- Oldenburg, C. M., K. Pruess, and B. J. Travis, Reply to comment on "Dispersive transport dynamics in a strongly coupled groundwater-brine flow system," *Water Resour. Res.*, 32(11), 3411-3412, 1996.
- Parra, J. O., L. R. Myer, K. T. Nihei, V. A. Korneev, and A. W. Gorody, Guided seismic waves for reservoir characterization, *GasTIPS*, 3(3), 11-18, 1997.
- Parsons, B. S., D. J. P. Swift, A. C. Muller, and S. S. Hubbard, Reconciling facies architecture with sequence concepts in a Quaternary barrier spit complex, *EOS Trans.*, 77(46), F328, American Geophysical Union, Washington, D.C., 1996.
- Patzek, T. W., Field applications of foam for mobility improvement and profile control, SPE Distinguished Lecture Paper, SPE 29612-P, *SPE Reservoir Engineering*, Society of Petroleum Engineering, Dallas, Tex., 1996.
- Patzek, T. W., Fluid Injection into low permeability reservoirs, DOE OPA Review, Reston, VA, January 19, 1997, U.S. Dept. of Energy, Washington, D.C., 1997.
- Patzek, T. W., Optimal fluid injection policy and producibility in fractured flow permeability reservoirs, in *Proc. Petroleum Technology Transfer Council Meeting, University of Southern California, Los Angeles, CA, May 15, 1997*, 1997.
- Patzek, T. W., Problems and opportunities in the development of hydrocarbon resources in the diatomites, in *Proc. West Coast Petroleum Technology Transfer Center, Bakersfield, CA, Nov. 10, 1996*, 1997.

- Patzek, T. W., Statistical characterization of metal-contaminated fills (presented at the SPE Western Regional Meeting, Long Beach, Calif., June 26, 1997), SPE 38307, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Patzek, T. W., and A. De, Lossy transmission line model of hydrofractured well dynamics (presented at the SPE 1998 Western Regional Meeting, Bakersfield, Calif., May 10-13, 1998), SPE 46195, Society of Petroleum Engineers, Dallas, Tex., 1998.
- Patzek, T. W., A. R. Kovscek, and P. J. Sullivan, Inferring aqueous contaminant history with an inverse model, in *Proc. Seventh Annual West Coast Conference on Contaminated Soils and Groundwater, Oxnard, CA, March 10-13, 1997*, 1997.
- Patzek, T. W., and D. M. Silin, Control of fluid injection into a low-permeability rock. 1. Hydrofracture growth (presented at the SPE/DOE Improved Oil Recovery Symposium, Tulsa, Oklahoma, 19-22 April 1998), SPE 39698, Society of Petroleum Engineering, Dallas, Tex., 1998.
- Patzek, T. W., and P. J. Sullivan, Statistical characterization of metal-contaminated fills (presented at the SPE Western Regional Meeting, Long Beach, Calif., June 25-27, 1997), SPE 38307, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Pellerin, L., V. F. Labson, and M. C. Pfeifer, VETEM — A very early time electromagnetic system: year two, in *Proc. Symposium of the Application of Geophysics to Engineering and Environmental Problems, April 29, 1996, Keystone, CO*, pp. 91-100, 1996.
- Persoff, P., and J. B. Hulen, Hydrologic characterization of four cores from the geysers coring project, in *Proc. 21st Workshop on Geothermal Reservoir Engineering, Stanford University, Stanford, CA, January 22-24, 1996*, Stanford Univ., Stanford, Calif., 1996.
- Persoff, P., and G. J. Moridis, Laboratory study of closure cap repair techniques, LBNL-39420, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Persoff, P., G. J. Moridis, D. M. Tuck, and M. A. Phifer, Laboratory testing of closure cap repair techniques, in *Proc. Int'l Containment Technology Conference and Exhibition, St. Petersburg, Fla., February 9-12, 1997*, pp. 319-326, 1997.
- Persoff, P., G. J. Moridis, J. Apps, and K. Pruess, Effect of dilution and contaminants on strength and hydraulic conductivity of sand grouted with colloidal silica gel, in *Proc. Int'l Containment Technology Conference and Exhibition, St. Petersburg, Fla., February 9-12 1997*, pp. 578-584, 1997.
- Persoff, P., G. J. Moridis, J. Apps, and K. Pruess, Evaluation tests for colloidal silica for use in grouting applications, *Geotech. Testing J.*, 21(3), 264-269, 1998.
- Peterson, J. E., S. Hubbard, K. H. Williams, E. L. Majer, and P. T. Zawislanski, Moisture content estimation using crosshole radar measurement, *EOS Trans.*, 78(17), S166, American Geophysical Union, Washington, D.C., 1997.
- Peterson, Jr., J. E., and K. Williams, Ground penetrating radar results at the Box Canyon Site: 1996 survey as part of infiltration test, LBNL-40915, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Pili, E., B. M. Kennedy, M. S. Conrad, and J. P. Gratier, Isotope constraints on the involvement of fluids in the San Andreas fault, *EOS Trans.*, 79, S229, American Geophysical Union, Washington, D.C., 1998.
- Pollard, M. L., and C. J. Radke, Effective viscosities in thin iron micellar liquid films, *AIChE J.*, 42(7), 2005-2013, 1996.
- Pozdniakov, S. P., C.-F. Tsang, and V. A. Korneev, Flow and tracer transport of a doublet well system in an aquifer with a circular inclusion, LBNL-38260, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Pruess, K., Injection plume behavior in fractured, vapor-dominated reservoirs, in *Proc. 21st Workshop Geothermal Reservoir Engineering, Stanford University, Stanford, CA, January 22-24, 1996*, SGP-TR-151, Stanford University, Stanford, Calif., 1996.
- Pruess, K., On vaporizing water flow in hot sub-vertical rock fractures, *Trans. Porous Media*, 28, 335-372, 1997.
- Pruess, K., On water seepage and fast preferential flow in heterogeneous, unsaturated rock fractures, *J. Contam. Hydrol.*, 30, 333-362, 1998.
- Pruess, K. (ed.), *Proc. TOUGH Workshop 1998*, LBNL-41995, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Pruess, K., TOUGH2 — An update, in *Proc. 19th New Zealand Geothermal Workshop, Auckland, NZ November 1997*, pp. 211-216, New Zealand Geothermal Assoc., Auckland, New Zealand, 1998.
- Pruess, K., B. Faybishenko, and G. S. Bodvarsson, Alternative concepts and approaches for modeling flow and transport in thick unsaturated zones of fractured rocks, *J. Contam. Hydrol.*, accepted.
- Pruess, K., S. Finsterle, G. Moridis, C. Oldenburg, E. Antúñez, and Y. S. Wu, Advances in the TOUGH2 family of general-purpose reservoir simulators, in *Proc. Geothermal Program Review XIV, Berkeley, Calif., April 8-10, 1996*.
- Pruess, K., S. Finsterle, G. Moridis, C. Oldenburg, and Y. S. Wu, General-purpose reservoir simulators: the TOUGH2 family, *CRC Bulletin*, 26(2), 53-57, 1997.
- Pruess, K., C. Oldenburg, G. Moridis, and S. Finsterle, Water injection into vapor- and liquid-dominated reservoirs: modeling of heat transfer and mass transport, in *Proc. DOE Geothermal Program Review 15, San Francisco, Calif., March 25-26, 1997*, pp. 2-55 to 2-62, DOE/EE-0139, U.S. Dept. of Energy, Washington, D.C., 1997.
- Pruess, K., A. Simmons, Y. S. Wu, and G. Moridis, TOUGH2 software qualification, LBNL-38383, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Quinn, N. W. T., Bay-delta modeling forum, LBNL-39641, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Quinn, N. W. T., A compliance monitoring program for use and operation of the Grasslands Bypass for drainage conveyance in the Western San Joaquin Valley, LBNL-39052, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Quinn, N., and J. Karkoski, Prospects for real-time management of water quality in the San Joaquin Basin, California, *J. Am. Water Resour. Assoc.*, accepted.
- Quinn, N. W. T., J. McGahan, and M. Delamore, Innovative drainage management techniques to meet monthly and annual selenium load targets, *Calif. Agriculture*, in press.
- Ritcey, A. C., Y. S. Wu, and G. S. Bodvarsson, Modeling analysis of the effect of future climate change on the distribution and movement of moisture in the unsaturated zone at Yucca Mountain, Nevada, *J. Contam. Hydrol.*, accepted.
- Romero, Jr., A., E. M. McEvilly, E. L. Majer, Three-dimensional attenuation tomography at the Northwest Geysers Geothermal Region, California, *Geophysics*, 62, 149-167, 1997.
- Rubin, H., D. Dvayrin, J. T. Birkholzer, and G. Rouve, Advection and dispersion of contaminant in a permeable medium embedding fractures in which advection velocity is comparatively slow, *J. Hydrology*, 179, 135-162, 1997.
- Rubin, Y., S. Hubbard, and S. Ezzedine, Conjunctive use of geophysical or tracer data with hydrogeological testing for enhanced site characterization (presented at the ASCE IAHR Conference, San Francisco, CA), #260, 1997.
- Rubin, Y., S. S. Hubbard, A. Wilson, and M. A. Cushey, Aquifer characterization, in *The Handbook of Groundwater Engineering*, Chapter 10, pp. 10.1-10.68, edited by J. W. Delleur, CRC Press, New York, N.Y., 1998.
- Rubin, H., A. M. Soliman, J. T. Birkholzer, and G. Rouve, Transport of a tracer slug in a fractured permeable formation, *J. Hydrology*, 176, 153-180, 1997.
- Rutqvist, J., J. Noorishad, C.-F. Tsang, and O. Stephansson, Determination of fracture storativity in hard rocks using high pressure injection testing, *Water Resour. Res.*, 34(10), 2551-2560, 1998.
- Rutqvist, J., O. Stephansson and C.-F. Tsang, Hydraulic field measurements of incompletely closed fractures in granite, *Int'l J. Rock Mech. Mining Sci.*, 34(3-4), 1997.
- Rutqvist, J., C.-F. Tsang, D. Ekman and O. Stephansson, Evaluation of in situ Hydromechanical Properties of Rock Fractures at Laxemar in Sweden, in *Proc. First Asian Rock Mechanics Symposium: ARMS '97, Seoul, Korea*, pp. 619-624, A. A. Balkema Publishers, Rotterdam, The Netherlands, 1997.
- Salve, R., Near-surface wetting of a ponded basalt surface: observations using time domain reflectometry, *J. Hydrology*, 208 (3-4), 249-261, 1998.

- Salve, R., T. Tokunaga, J. S. Wang, R. Solbau, and J. Clyde, Hydrologic monitoring in unsaturated fractured tuff boreholes, *EOS Trans.*, 78 (supplement), American Geophysical Union, Washington, D.C., 1997.
- Schlueter, E. M., R. W. Zimmerman, P. A. Witherspoon, and N. G. W. Cook, The fractal dimension of pores in sedimentary rocks and its influence on permeability, *Eng. Geol.*, 48(3-4), 199-215, 1997.
- Seifert, P. K., Effects of pore fluids in the subsurface on ultrasonic wave propagation, Ph.D. Thesis, LBNL-41781, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Seifert, P. K., J. T. Geller, and L. R. Johnson, Effect of P-wave scattering on velocity and attenuation in unconsolidated sand saturated with immiscible liquids, *Geophysics*, 63(1), 161-170, 1998.
- Shan, C., H.-Y. Holman, and I. Javandel, A pitfall and its solution in monitoring and cleaning up groundwater contamination by petroleum products, *EOS Trans.*, 78 (supplement), American Geophysical Union, Washington, D.C., 1997.
- Shan, C., and I. Javandel, Analytical solutions for solute transport in a vertical aquifer section, *J. Contam. Hydrol.*, 27(1-2), 63-82, 1996.
- Simmons, A. (ed.), Environmental management science program awards: fiscal year 1997 annual progress report, LBNL-41192, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Sisson, J. B., and B. Faybishenko, Box Canyon hot air injection study and vadose zone instrument development result, INEL-95/0597, Idaho National Engineering and Environmental Laboratory, Idaho Falls, Idaho, 1997.
- Solodov, I. N., V. I. Velichkin, and N. P. Laverov, Safe geological disposal of liquid wastes: isolating geochemical properties of the injection zone rocks as a factor for retardation and "self-destruction" of liquid radioactive wastes, LBNL-39167, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Solodov, I. N., A. V. Zotov, A. D. Khoteev, A. P. Mukhamet-Galeev, B. R. Tagirov, and J. Apps, Geochemistry of natural and contaminated subsurface waters in fissured bed rocks of the Lake Karachai area, southern Urals, Russia, *App. Geochem.*, accepted.
- Sonnenthal, E. L., and G. S. Bodvarsson, Modeling of geochemistry in the unsaturated zone, *J. Contam. Hydrol.*, accepted.
- Sonnenthal, E. L., and G. S. Bodvarsson, Modeling strontium geochemistry and isotopic ratio in the unsaturated zone, in *The site-scale unsaturated zone model of Yucca Mountain, Nevada, for the viability assessment*, edited by G. S. Bodvarsson, T. M. Bandurraga, and Y. S. Wu, Yucca Mountain Site Characterization Project Milestone, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Sonnenthal, E. L., and G. S. Bodvarsson, Modeling the chloride geochemistry in the unsaturated zone, in *The Site-Scale Unsaturated Zone Model of Yucca Mountain, Nevada, for the Viability Assessment*, edited by G. S. Bodvarsson, T. M. Bandurraga, and Y. S. Wu, Yucca Mountain Site Characterization Project Milestone, LBNL-40376, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Sonnenthal, E. L., and G. S. Bodvarsson, Percolation flux estimates from geochemical and thermal modeling, in *Proc. Eighth International Conference on High-Level Radioactive Waste Management*, pp. 130-132, American Nuclear Society, La Grange Park, Ill., 1998.
- Sonnenthal, E. L., D. DePaolo, and G. S. Bodvarsson, Modeling the strontium geochemistry and isotopic ratio in the unsaturated zone at Yucca Mountain, Nevada, *EOS Trans.*, 78 (supplement), American Geophysical Union, Washington, D.C., 1997.
- Sorey, M. L., W. C. Evans, B. M. Kennedy, C. D. Farrar, L. J. Hainsworth, and B. Hausback, Carbon dioxide and helium emissions from a reservoir of magmatic gas beneath Mammoth Mountain, California, *J. Geophys. Res.*, 103(15), 15,303-15,323, 1998.
- Sorey, M. L., W. C. Evans, C. D. Farrar, M. B. Kennedy, and L. Hainsworth, Carbon dioxide and helium emissions from a reservoir of magmatic gas beneath Mammoth Mountain, California, *EOS Trans.*, 77, American Geophysical Union, Washington, D.C., 1996.

- Soroush, M., and M. Nikraves, Shortest-prediction-horizon nonlinear model predictive control, in *Proc. 13th World Congress Int'l Federation of Automatic Control-IFAC San Francisco, CA, June 30-July 5, 1996*, 1996.
- Stephansson, O., L. Jung, and C.-F. Tsang (eds.), *Coupled Thermo-Hydro-Mechanical Processes in Fractured Media*, Elsevier Sci., New York, N.Y., 1996.
- Thapa, B. B., and K. Karasaki, Observations of joint persistence and connectivity across boreholes, in *Proc. 2nd North American Rock Mechanics Symposium, Montreal, Quebec, Canada, June 19-21, 1996*, 1996.
- Tokunaga, T. K., A tensiometer for measuring hydraulic potentials on surfaces of porous rock, *Water Resour. Res.*, 33(6), 1509-1513, 1996.
- Tokunaga, T. K., G. E. Brown, Jr., I. J. Pickering, S. R. Sutton, and S. Bajt, Selenium redox reactions and transport between ponded waters and sediments, *Environ. Sci. Tech.*, 31(5), 1419-1425, 1996.
- Tokunaga, T. K., S. R. Sutton, and S. Bajt, Mapping of selenium concentrations in soil aggregates with synchrotron x-ray fluorescence microprobe, *Soil Sci.*, 158(6), 421-434, 1997.
- Tokunaga, T. K., S. R. Sutton, S. Bajt, P. Nuessle, and G. Shea-McCarthy, Selenium diffusion and reduction at the water-sediment boundary: MicroXANES spectroscopy of reactive transport, *Environ. Sci. Tech.*, 32, 1092-1098, 1998.
- Tokunaga, T. K., and J. Wan, Water film flow along fracture surfaces of porous rock, *Water Resour. Res.*, 33(6), 1287-1295, 1996.
- Touchard, G. G., T. W. Patzek, and C. J. Radke, A physico-chemical explanation for flow electrification in low conductivity liquids, *IEEE Trans. Indus. Appl.*, 32(5), 1051-1057, 1996.
- Truesdell, A. H., and M. J. Lippmann, Effects of pressure drawdown and recovery on the Cerro Prieto Beta Reservoir in the CP-111 Area, in *Proc. Twenty-Third Workshop on Geothermal Reservoir Engineering, Stanford University, Stanford, CA, January 26-28, 1998*, 23, pp. 90-98, SGP-TR-158, Stanford Univ., Stanford, Calif., 1998.
- Truesdell, A. H., M. J. Lippmann, and H. Gutierrez Puente, Evolution of the Cerro Prieto reservoirs under exploitation, in *Proc. 1997 Annual Meeting of the Geothermal Resources Council, Burlingame, CA, October 12-15, 1997*, 21, pp. 263-270, Geothermal Resources Council, Davis, Calif., 1997.
- Truesdell, A. H., M. J. Lippmann, H. Gutierrez Puente, and V. J. de Leon, The importance of natural fluid recharge to the sustainability of the Cerro Prieto Resource, *Geotherm. Resour. Coun. Trans.*, 22, 529-536, 1998.
- Tsang, C.-F., A discussion of scientific issues in hydrogeology of low permeability strata, in *Proc. of 30th International Geological Congress*, 22, pp. 224-228, 1997.
- Tsang, C.-F., From processes to systems: a discussion of predictive modeling of flow and transport in geologic systems, in *Groundwater and Subsurface Remediation*, edited by H. Kobus, B. Barczewski and H. Koschitzky, pp. 207-218, Springer Verlag Publishers, New York, N.Y., 1996.
- Tsang, C.-F., Linking thermal, hydrological and mechanical processes in fractured rocks, in *Annual Review of Earth and Planetary Sciences*, 27, in press.
- Tsang, C.-F., Some hydrologic factors affecting the safety of deep injection disposal of liquid wastes, in *Scientific and Engineering Aspects of Deep Injection Disposal of Hazardous and Industrial Wastes*, edited by J. A. Apps and C.-F. Tsang, pp. 35-45, Academic Press Inc., San Diego, Calif., 1996.
- Tsang, C.-F., and I. Neretnieks, Flow channeling in heterogeneous fractured rocks, *Rev. Geophys.*, 36(2), 275-298, 1998.
- Tsang, C.-F., and J. Rutqvist, Progress in coupled analysis of a thermo-hydro-mechanical experiment in fractured rock, in *Computer Methods and Advances in Geomechanics*, edited by J.-X. Yuan, A. A. Balkema Publishers, Rotterdam, The Netherlands, 1997.
- Tsang, C.-F., and O. Stephansson, A conceptual introduction to coupled thermo-hydro-mechanical processes in fractured rocks, in *Coupled Thermo-Hydro-Mechanical Processes in Fractured Media*, edited by O. Stephansson, L. Jung, and C.-F. Tsang, pp. 1-24, Elsevier Sci., New York, N.Y., 1996.

- Tsang, C.-F., and Y. Tsang, Research directions in hydrogeology, *Earth Sci. Frontiers*, 3(1), 43-48, 1996.
- Tsang, C.-F., and Y. W. Tsang, Some impressions and comments on hydrogeology and environmental sciences in China, *Bulletin of National Natural Science Foundation of China*, 10(2), 116-120, 1996.
- Tsang, Y. W., and J. T. Birkholzer, Interpreting the thermal-hydrological response of the ESF Single Heater Test, Yucca Mountain Site Characterization Project Level 4 Milestone SP9267M4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Tsang, Y. W., and J. T. Birkholzer, Multi-phase thermal-hydrological processes in the Single Heater tests at Yucca Mountain, *J. Contam. Hydrol.*, accepted.
- Tsang, Y. W., and J. T. Birkholzer, Predictions and observations of thermohydrologic conditions in the single heater test, *J. Contam. Hydrol.*, accepted.
- Tsang, Y., and J. Birkholzer, Thermohydrological response of the Yucca Mountain single heater test, in *Proc. 8th International High-Level Nuclear Waste Conf., May 1998, Las Vegas, Nev.*, pp. 140-142, American Nuclear Society, La Grange Park, Ill, 1998.
- Tsang, Y. W., and P. Cook, Ambient characterization of the ESF Drift Scale Test Area by field air permeability measurements, Yucca Mountain Project Level 4 Milestone SP9512M4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Tsang, Y. W., C.-F. Tsang, F. V. Hale, and B. Dverstorp, Tracer transport in a stochastic continuum model of fractured media, *Water Resour. Res.*, 32(10), 3077-3092, 1996.
- Vasco, D. W., A. Datta-Gupta, and J. C. Long, Integrating field production history in stochastic reservoir characterization (presented at the SPE Annual Technical Conference and Exhibition Denver, CO, Sept., 1997), SPE 36567, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Vasco, D. W., Groups, algebras and the nonlinearity of geophysical inverse problems, *Geophys. J. Int.*, 131, 9-23, 1997.
- Vasco, D. W., and A. Datta-Gupta, Asymptotic solutions for solute transport: a formalism for tracer tomography, *Water Resour. Res.*, in press.
- Vasco, D. W., A. Datta-Gupta, and J. C. Long, Resolution and uncertainty in hydrologic characterization, *Water Resour. Res.*, 33(3), 379-397, 1996.
- Vasco, D. W., K. Karasaki, and L. Myer, Monitoring of fluid injection and soil consolidation using surface tilt measurements, *J. Geotech. Geoenviron. Eng.*, 124(1), 29-37, 1997.
- Vasco, D. W., J. E. Peterson, and K. H. Lee, Ground-penetrating radar velocity tomography in heterogeneous and anisotropic media, *Geophysics*, 62(6), 1758-1773, 1997.
- Vasco, D. W., J. E. Peterson, and E. L. Majer, Resolving seismic anisotropy: sparse matrix methods for geophysical inverse problems, *Geophysics*, 63(3), 970-983, 1997.
- Velichkin, V. I., A. A. Asadulin, N. N. Tavasov, V. V. Poluektov, V. A. Petro, and V. I. Myskin, Geology and geochemical features of the "Mayak" area bedrock (Chelyabinsk, S. Urals, Russia), LBNL-39165, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Wahl, C., and S. M. Benson, Update to modeling soil selenium concentrations in the shallow soil profile at Kesterson Reservoir, Merced County, California 1988-1993, LBNL-39215, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Wan, J., and T. K. Tokunaga, Film straining of colloids in unsaturated porous media: conceptual model and experimental testing, *Environ. Sci. Tech.*, 31(8), 2413-2420, 1997.
- Wan, J., and T. K. Tokunaga, Measuring partition coefficients of colloids at air-water interfaces, *Environ. Sci. Tech.*, Nov., 1998.
- Wang, J. S. Y., Trautz, R. C., Cook, P. J., Finsterle, S., James, A. L., Birkholzer, J. T. 1998. Field Testing and Analysis of Seepage into Drifts at Yucca Mountain, *J. Contam. Hydrol.*, accepted.
- Wilt, M., P. Kasameyer, S. Takasugi, K. H. Lee, and M. Lippmann, Fracture mapping in geothermal fields with long-offset induction logging, in *Proc. Twenty-Second Workshop on Geothermal Reservoir Engineering, Stanford, CA*, SGP-TR-155, pp. 229-232, Stanford Univ., Stanford, Calif., 1997.

- Witherspoon, P. (ed.), *Geological Problems in Radioactive Waste Isolation: Second Worldwide Review*, LBNL-38915, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Wong, H., I. Fatt, and C. J. Radke, Deposition and thinning of the human tear film, *J. Colloid Interface Sci.*, 184, 44-51, 1996.
- Wrixon, R. C., and G. A. Cooper, In-situ casing consolidation by electrokinetic and electrochemical methods (presented at the 1997 SPE Annual Technical Conference, Drilling and Completion Section, San Antonio, Tex.), SPE 38586, Society of Petroleum Engineering, Dallas, Tex., 1997.
- Wrixon, R., and G. A. Cooper, Theoretical and practical guidelines for using electrokinetics to improve casing support in soft marine sediments (presented at the 1998 SPE/IAD.C, Drilling Conference, Dallas, Tex., March 3-6, 1998), SPE/IAD.C. 39299, Society of Petroleum Engineering, Dallas, Tex., 1998.
- Wrixon, R.C., and G. A. Cooper, In-situ casing consolidation by electrokinetic methods, *J. Pet. Tech.*, 50(2), 51-53, 1998.
- Wu, Y. S., R. Ahlers, P. Fraser, and A. Simmons, Software qualification of selected TOUGH2 modules, LBNL-39490, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Wu, Y. S., and A. K. Mishra, Modifications and additions to selected TOUGH2 modules, LBNL-41870, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Wu, Y. S., and K. Pruess, A numerical method for simulating non-Newtonian fluid flow and displacement in porous media, *Adv. Water Resour.*, 21, 351-362, 1998.
- Wu, Y. S., and K. Pruess, Flow of non-Newtonian fluids in porous media, *Adv. Porous Med.*, 3, 87-184, 1996.
- Wu, Y. S., K. Pruess, and P. Persoff, Gas flow in porous media with Klinkenberg effects, *Trans. Porous Media*, 32, 117-137, 1998.
- Wu, Y. S., Haukwa, C., and G. S. Bodvarsson, A site-scale model for modeling fluid and heat flow in the unsaturated zone of Yucca Mountain, Nevada, *J. Contam. Hydrol.*, accepted.
- Wu, Y. S., Ritcey, A. C., and G. S. Bodvarsson, A modeling study of perched water phenomena in the unsaturated zone, *J. Contam. Hydrol.*, accepted.
- Wu, Y. S., A. C. Ritcey, C. F. Ahlers, J. J. Hinds, A. K. Mishra, C. Haukwa, T. M. Bandurraga, H. H. Liu, E. L. Sonnenthal, and G. S. Bodvarsson, 3-D UZ site-scale model for abstraction in TSPA-VA, Yucca Mountain Site Characterization Project Milestone SLX01LB3 Report, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Wu, Y. S., A. C. Ritcey, C. F. Ahlers, A. K. Mishra, J. J. Hinds, and G. S. Bodvarsson, Providing base-case flow fields for TSPA-VA: evaluation of uncertainty of present-day infiltration rates using DKM/Base-Case and DKM/Weeps parameter sets, Yucca Mountain Site Characterization Project Report, YMP Level 4 Milestone SLX01LB2, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Wu, Y. S., Ritcey, A. C., Sonnenthal, E. L., Bandurraga, T. M., Haukwa, C., Fairley, J. P., Chen, G., Li, J. H., and Bodvarsson, G. S., Incorporation of perched water data into the UZ site-scale model, Yucca Mountain Project Level 4 Milestone SP24UCM4, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Xie, G., and J. Li, A new 3D parallel high resolution electromagnetic nonlinear inversion based on new global magnetic integral and local differential decomposition (GILD), LBNL-40265, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Xie, G., J. Li, and K. H. Lee, New 3D Nonlinear electromagnetic Inversion, LBNL-39019, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Xie, G., J. Li, and E. L. Majer, New 3D Parallel SGILD modeling and inversion, in *Proc. 18th Annual International Conference, "Predictability Quantifying Uncertainty in Models of Complex Phenomena," May 11-15, 1998, Los Alamos, NM, 1998*, LBNL-42252, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Xie, G., J. Li, E. Majer, and D. Zuo, New 3D parallel GILD electromagnetic modeling and nonlinear inversion using global magnetic integral and local differential equation, LBNL-42105, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Xu, T., F. Gerard, K. Pruess, and G. Brimhall, Modeling non-isothermal multiphase multi-species reactive chemical transport, LBNL-40504, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Xu, T., and K. Pruess, Coupled modeling of non-isothermal multi-phase flow, solute transport and reactive chemistry in porous and fractured media: 1. Model development and validation, LBNL-42050, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Xu, T., E. Sonnenthal, N. Spycher, K. Pruess, and G. Brimhall, Coupled modeling of non-isothermal multi-phase flow, solute transport and reactive chemistry in porous and fractured media: 2. Model applications, LBNL-42051, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Xu, T., S. P. White, and K. Pruess, Pyrite oxidation in saturated and unsaturated porous media flow: a comparison of alternative mathematical modeling approaches, LBNL-42049, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.
- Zawislanski, P. T., and A. B. Crawley, Selenium cycling study in the San Francisco Bay: A partnership involving federal and state government and industry (presented at the SPE/EPA 1997 Exploration and Production Environmental Conference, Dallas, Tex.), SPE 37885, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Zawislanski, P. T., S. Benson, A. Brownfield, E. Gabet, A. Haxo, T. Johnson, D. King, A. McGrath, H. Mountford, S. Myneni, J. Oldfather, T. Sears, and H.-W. C. Wong, Selenium fractionation and cycling in the intertidal zone of the Carquinez Strait: quarterly progress report, January through March 1996, LBNL-39616, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, P. T., S. Benson, A. Brownfield, S. Chau, E. Gabet, T. Johnson, D. King, A. McGrath, H. Mountford, S. Myneni, J. Oldfather, T. Sears, and H.-W. C. Wong, Selenium fractionation and cycling in the intertidal zone of the Carquinez Strait: quarterly progress report, April through June 1996, LBNL-39617, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, P. T., and B. Faybishenko, New casing and backfill design for neutron logging access boreholes, *Groundwater J.*, in press.
- Zawislanski, P. T., B. Faybishenko, A. James, B. Freifeld and R. Salve, Vadose zone monitoring system installation report for McClellan AFB, LBNL-39525, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, P. T., G. R. Jayaweera, J. W. Biggar, W. T. Frankenberger, and L. Wu, The Pond 2 selenium volatilization study: a synthesis of five years of experimental results, 1990-1995, LBNL-39516, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, P. T., and A. E. McGrath, Selenium cycling in estuarine wetlands: Overview and new results from the San Francisco Bay, in *Environmental Chemistry of Selenium*, edited by W. T. Frankenberger and R. A. Engberg, Marcel Dekker, New York, N.Y., 1998.
- Zawislanski, P. T., A. E. McGrath, S. M. Benson, H. S. Mountford, T. M. Johnson, E. Gavet, S. C. B. Myneni, T. K. Tokunaga, S. Chau, and H. Wong, Selenium fractionation and cycling in the intertidal zone of the Carquinez Strait: annual report, October 1, 1995-December 31, 1996, LBNL-40993, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Zawislanski, P. T., A. McGrath, S. Benson, H. S. Mountford, T. Johnson, E. Gabet, S. Myneni, T. Tokunaga, T. K. Chau, and H. Wong, Selenium fractionation and cycling in the intertidal zone of the Carquinez Strait: annual report, October 1, 1995-December 31, 1996, LBNL-40993, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, P. T., A. E. McGrath, H. S. Mountford, T. M. Johnson, S. C. B. Myneni, E. Cornet, T. C. Sears, A. A. Brownfield, S. Chau, H. W. C. Wong, and D. King, Selenium geochemistry in marshes affected by refinery outfall, Carquinez Strait, Calif.: influence of redox conditions, sedimentation dynamics, and plant environment, LBNL-39514, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1996.
- Zawislanski, H. S. Mountford, R. Dahlquist, S. J. Rodriguez, and R. Salve, Monitoring and data analysis for the vadose zone monitoring system (VZMS), McClellan AFB: quarterly status report, August 15, 1997-November 15, 1997, LBNL-41147, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Zawislanski, P. T., and C. M. Oldenburg, Data analysis for preliminary conceptual model design, vadose zone monitoring system (VZMS), McClellan AFB: 1997 annual report, LBNL-41262, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1998.

- Zawislanski, P. T., R. Salve, B. Freifeld, H. S. Mountford, R. Dahlquist, A. James, S. Rodriguez and B. Faybishenko, Monitoring and data analysis for the vadose zone monitoring system (VZMS), McClellan AFB quarterly status report, LBNL-40377, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Zawislanski, P. T., R. Salve, B. M. Freifeld, H. S. Mountford, R. Dahlquist, S. J. Rodriguez, and B. Faybishenko, Monitoring and data analysis for the vadose zone monitoring system (VZMS), McClellan AFB: quarterly status report, May 15, 1997-August 15, 1997, LBNL-41009, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Zawislanski, P. T., T. K. Tokunaga, S. M. Benson, H. S. Mountford, T. C. Sears, H. Wong, D. King, and J. Oldfather, Hydrological and geochemical investigations of selenium behavior at Kesterson Reservoir: progress report, October 1, 1994-September 30, 1996, LBNL-41027, Lawrence Berkeley National Laboratory, Berkeley, Calif., 1997.
- Zawislanski, P. T., and M. Zavarin, Nature and rates of selenium transformations: a laboratory study of Kesterson Reservoir soils, *Soil Sci. Soc. Am. J.*, 60(3), 791-800, 1996.
- Zimmerman, R. W., Effective conductivity of a 2-dimensional medium containing elliptic inhomogeneities, in *Proc. Royal Society of London Series A-Mathematical Physical and Engineering Sciences*, 452(1950), pp. 1713-1727, 1996.
- Zimmerman, R. W., and G. S. Bodvarsson, Effective transmissivity of 2-dimensional fracture networks, *Int'l J. Rock Mechanics and Mining Sciences and Geomechanics Abstracts*, 33(4), 433-438, 1996.
- Zimmerman, R. W., and G. S. Bodvarsson, Hydraulic conductivity of rock fractures, *Trans. Porous Media*, 23(1), 1-30, 1996.
- Zimmerman, R. W., T. Hadgu, G. S. Bodvarsson, A new lumped-parameter model for flow in unsaturated dual-porosity media, *Adv. Water Resour.*, 19(5), 317-327, 1996.
- Zwahlen, E. D., and T. W. Patzek, A comparison of mapping schemes for reservoir characterization (presented at the SPE Western Regional Meeting, Long Beach, Calif. June 25-27, 1997), SPE 38264, Society of Petroleum Engineers, Dallas, Tex., 1997.
- Zwahlen, E. D., and T. W. Patzek, Linear transient flow solution for primary oil recovery with infill and conversion to water injection, *In Situ*, 21(4), 1997.

[HTTP://WWW-ESD.LBL.GOV](http://www-esd.lbl.gov)

Earth Sciences Division Personnel

STAFF SCIENTISTS AND ENGINEERS

Al Mahamid, Ilham
Birkholzer, Jens T.
Bishop, James
Bodvarsson, Gudmundur S.
Conrad, Mark S.
Dodson, Jr., John A.
Doughty, Christine A.
Faybishenko, Boris A.
Feighner, Mark A.
Finsterle, Stefan A.
Freifeld, Barry M.
Geller, Jil T.
Goldstein, Norman E.
Gonzalez, Jr., Emilio
Hazen, Terry C.
Hestir, Kevin F.
Holman, Hoi-Ying
Hoversten, Gary M.
Huang, Kangle
Hubbard, Susan S.
Hunter-Cevera, Jennie C.
Jacobsen, Janet S.
Javandel, Iraj
Karasaki, Kenzi
Kennedy, Burton M.
Kim, Jinwon
Korneev, Valeri A.
Lamble, Geraldine M.
Lee, Ki H.
Li, Guomin
Li, Jianhua
Lippmann, Marcelo J.
Liu, Hui-Hai
Majer, Ernest L.
McEvilly, Thomas V.
Miller, Norman L.
Moriadis, George J.

Mukhopadhyay, Sumit
Myer, Larry R.
Myneni, Satish
Nihei, Kurt T.
Oldenburg, Curtis M.
Pan, Lehua
Perry, Dale L.
Persoff, Peter
Peterson, John E.
Pruess, Karsten
Quinn, Nigel
Shan, Chao
Silin, Dmitriy
Sonnenthal, Eric
Spycher, Nicolas
Stringfellow, William T.
Tokunaga, Tetsu K.
Tomutsa, Liviu
Torn, Margaret S.
Tsang, Chin-Fu
Tsang, Yvonne T.
Vasco, Donald W.
Wan, Jiamin
Wang, Joseph S.
Waychunas, Glenn A.
Wu, Yu-Shu
Xie, Ganquan
Zawislanski, Peter T.
Zimmerman, Robert W.

FACULTY

Becker, Alex
Boering, Kristie A.
Brimhall, George
Buchanan, Bob B.
Cooper, George A.
DePaolo, Donald J.

Doner, Harvey E.
 Doyle, Fiona M.
 Fung, Inez
 Glaser, Steven
 Ingram, B. Lynn
 Johnson, Lane R.
 Leighton, Terrance J.
 Morrison, H. Frank
 Narasimhan, T. N.
 Patzek, Tadeusz W.
 Radke, Clayton J.
 Rector, James W.
 Rubin, Yoram.
 Shen, Hsieh W.
 Sposito, Garrison
 Witherspoon, Paul A.

RESEARCH ASSOCIATES, SPECIALISTS, AND TECHNICIANS

Ahlers, C. Fredrik
 Alusi, Thana
 Bandurraga, T. Mark
 Carpenter, Scott A.
 Castro, Grace M.
 Clyde, John R.
 Cohen, Andrew J.
 Cook, Paul J.
 Dahlquist, Richard
 Daley, Thomas M.
 Dougherty, James R.
 Hedegaard, Randall F.
 Hinds, Jennifer
 James, April L.
 Jordan, Preston D.
 Kirkpatrick, Elizabeth A.
 Liebert, Ilana
 Link, Suzanne M.
 Menendez-Barreto, Melani
 Mountford, H. Scott
 Najita, Julie S.
 Olson, Keith R.
 Owens, Thomas L.
 Ritcey, Anne C.
 Salve, Rohit
 Shuster, David
 Steiger, Michael
 Stover, Richard C.
 TerBerg, Robert
 Trautz, Robert C.
 Williams, Kenneth H.
 Zhang, Winnie W.

POST DOCTORATES

Borglin, Sharon E.
 Davis, Simon
 De, Asoke
 Gabelle, Frederic
 Gritto, Roland
 Haukwa, Charles
 Hesler, Galen J.
 Hu, Qinhong
 Kaelin, Bruno
 Kneafsey, Timothy J.
 Lin, Jo Chiu Fang
 McCauley, Sean
 Mishra, Anil
 Nakagawa, Seiji
 Park, Sung-Ho
 Rutqvist, Jonny
 Veerapaneni, Srinivas
 Xu, Tianfu

STAFF

Aden-Gleason, Nancy
 Bell, Andre R.
 Bradley, Rachel Maren
 Cushey, Mark
 Fink, Maria
 Fissekidou, Vassiliki A.
 Hodge, Sheryl A.
 Kaszuba, David
 Kramer, Bridget R.
 Lau, Peter K.
 Lippert, Donald R.
 Lucido, Nina
 Mangold, Donald C.
 McClung, Ivelina
 McCullough, Julie
 Miller, Grace A.
 Quarrie, Avril
 Robitaille, Daniel
 Seybold, Sherry A.
 Simmons, Ardyth M.
 Taliaferro, Carol L.
 Villavert, Maryann
 Wuy, Linda D.

DESIGNER AND PRODUCER

Maria Fink

EDITOR

Julie McCullough