KENO3D Visualization Tool for KENO V.a and KENO-VI Geometry Models

Prepared by
J. E. Horwedel and S. M. Bowman, ORNL

Oak Ridge National Laboratory

U.S. Nuclear Regulatory Commission
Office of Nuclear Regulatory Research
Washington, DC 20555-0001

AVAILABILITY NOTICE

Availability of Reference Materials Cited in NRC Publications

NRC publications in the NUREG series, NRC regulations, and *Title 10, Energy*, of the *Code of Federal Regulations*, may be purchased from one of the following sources:

1. The Superintendent of Documents
U.S. Government Printing Office
PO. Box 37082
Washington, DC 20402-9328
<http://www.access.gpo.gov/su_docs>
202-512-1800
2. The National Technical Information Service
Springfield, VA 22161-0002
<<http://www.ntis.gov/ordernow>>
703-487-4650

The NUREG series comprises (1) brochures (NUREG/BR-XXXX), (2) proceedings of conferences (NUREG/CP-XXXX), (3) reports resulting from international agreements (NUREG/IA-XXXX), (4) technical and administrative reports and books [(NUREG-XXXX) or (NUREG/CR-XXXX)], and (5) compilations of legal decisions and orders of the Commission and Atomic and Safety Licensing Boards and of Office Directors' decisions under Section 2.206 of NRC's regulations (NUREG-XXXX).

A single copy of each NRC draft report is available free, to the extent of supply, upon written request as follows:

Address: Office of the Chief Information Officer
Reproduction and Distribution
Services Section
U.S. Nuclear Regulatory Commission
Washington, DC 20555-0001

E-mail: <DISTRIBUTION@nrc.gov>
Facsimile: 301-415-2289

A portion of NRC regulatory and technical information is available at NRC's World Wide Web site:

<<http://www.nrc.gov>>

All NRC documents released to the public are available for inspection or copying for a fee, in paper, microfiche, or, in some cases, diskette, from the Public Document Room (PDR):

NRC Public Document Room
2120 L Street, N.W., Lower Level
Washington, DC 20555-0001
<<http://www.nrc.gov/NRC/PDR/pdr1.htm>>
1-800-397-4209 or locally 202-634-3273

Microfiche of most NRC documents made publicly available since January 1981 may be found in the Local Public Document Rooms (LPDRs) located in the vicinity of nuclear power plants. The locations of the LPDRs may be obtained from the PDR (see previous paragraph) or through:

<<http://www.nrc.gov/NRC/NUREGS/SR1350/V9/lpdr.html>>

Publicly released documents include, to name a few, NUREG-series reports; *Federal Register* notices; applicant, licensee, and vendor documents and correspondence; NRC correspondence and internal memoranda; bulletins and information notices; inspection and investigation reports; licensee event reports; and Commission papers and their attachments.

Documents available from public and special technical libraries include all open literature items, such as books, journal articles, and transactions, *Federal Register* notices, Federal and State legislation, and congressional reports. Such documents as theses, dissertations, foreign reports and translations, and non-NRC conference proceedings may be purchased from their sponsoring organization.

Copies of industry codes and standards used in a substantive manner in the NRC regulatory process are maintained at the NRC Library, Two White Flint North, 11545 Rockville Pike, Rockville, MD 20852-2738. These standards are available in the library for reference use by the public. Codes and standards are usually copyrighted and may be purchased from the originating organization or, if they are American National Standards, from—

American National Standards Institute
11 West 42nd Street
New York, NY 10036-8002
<<http://www.ansi.org>>
212-642-4900

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for

any third party's use, or the results of such use, of any information, apparatus, product, or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

KENO3D Visualization Tool for KENO V.a and KENO-VI Geometry Models

Manuscript Completed: March 2000
Date Published:

Prepared by
J. E. Horwedel and S. M. Bowman, ORNL

Oak Ridge National Laboratory
Managed by Lockheed Martin Energy Research Corporation
Oak Ridge, TN 37831-6370

H. D. Felsher, NRC Project Manager

**Prepared for
Office of Nuclear Regulatory Research
U.S. Nuclear Regulatory Commission
NRC Job Code B0304**

ABSTRACT

Criticality safety analyses often require detailed modeling of complex geometries. Effective visualization tools can enhance checking the accuracy of these models. This report describes the KENO3D visualization tool developed at the Oak Ridge National Laboratory (ORNL) to provide visualization of KENO V.a and KENO-VI criticality safety models. The development of KENO3D is part of the current efforts to enhance the SCALE (Standardized Computer Analyses for Licensing Evaluations) computer software system.

CONTENTS

	<u>Page</u>
ABSTRACT	iii
LIST OF FIGURES	vii
ACKNOWLEDGMENTS	ix
1 INTRODUCTION	1
2 KENO3D OVERVIEW.....	3
3 TOOLBARS	5
3.1 STANDARD TOOLBARS	5
3.2 VIEWS TOOLBAR	6
3.3 ZOOM TOOLBAR	6
3.4 CAMERA TOOLBAR	7
3.5 ROTATE VIEW AROUND AXIS	8
3.6 DISPLAY PROPERTIES/HIDE OBJECTS TOOLBAR	8
3.7 DISPLAY OPTIONS TOOLBAR	9
3.8 LEGEND AND AXIS OPTION TOOLBAR	9
3.9 CUTAWAY VIEWS TOOLBAR	10
4 THE MENUS	11
4.1 FILE MENU	11
4.2 VIEW MENU	11
4.3 WINDOW MENU	13
4.4 SETUP MENU	13
4.5 EDIT MENU	13
4.6 HELP MENU	13
5 SMALL MODEL EXAMPLE	15
6 LARGE MODEL EXAMPLE	17
7 SUMMARY	19
8 REFERENCES	21

LIST OF FIGURES

Figure		Page
1	KENO3D sample LWR shipping container	4
2	Simple KENO V.a example	15
3	A zoomed-in slice of a large KENO V.a model with water and void hidden from view	18

ACKNOWLEDGMENTS

The authors gratefully acknowledge the sponsors of the KENO3D development, the U.S. Nuclear Regulatory Commission (NRC) Fuel Cycle Safety and Safeguards Division (Harry Felsher, Technical Monitor), and the U.S. Department of Energy (DOE) EM-5 Package Approval and Safety Program (Mike Wangler, Program Manager).

1 INTRODUCTION

The SCALE (Standardized Computer Analyses for Licensing Evaluations) computer software system¹ developed at Oak Ridge National Laboratory (ORNL) is widely used and accepted around the world for criticality safety analyses. SCALE includes the well-known KENO V.a and KENO-VI three-dimensional (3-D) Monte Carlo criticality computer codes. Criticality safety analyses often require detailed modeling of complex geometries. Effective visualization tools can enhance checking the accuracy of these models. To address this need, ORNL has recently developed a powerful state-of-the-art visualization tool called KENO3D. The purpose of this report is to describe the KENO3D visualization tool.

2 KENO3D OVERVIEW

KENO3D enables KENO V.a and KENO-VI users to interactively display their three-dimensional geometry models. The interactive options include:

- Shaded or wireframe images
- Standard views, such as top view, side view, front view, and isometric (3-D) view
- Rotating the model
- Zooming in on selected locations
- Selecting parts of the model to display
- Editing colors and displaying legends
- Displaying properties of any unit in the model
- Creating cutaway views
- Removing units from the model
- Printing image or saving image to common graphics formats

KENO3D reads CSAS, KENO V.a, and KENO-VI input files. It attempts to verify that the KENO geometry input is “legal” (i.e., it conforms to the code input guidelines). KENO3D prints a warning message for illegal geometry input, and if possible, it displays the illegal KENO geometry to facilitate debugging of the input. Problems with more than 300,000 KENO V.a bodies* have been successfully tested and displayed.

KENO3D has the look and feel of a typical PC Windows application. Toolbar buttons are included for all major menu options. A setup dialog allows the user to specify toolbars that should be displayed. KENO3D has a fully integrated help system to aid beginning, as well as advanced users.

KENO3D has several unique options that provide users with increased flexibility in visualizing portions of a model in greater detail or for visualizing parts of larger models that may be too big to provide a useful image when viewed in their entirety. These options include:

- **“Load slice”** option allows the user to define a three-dimensional (3-D) slice to display prior to loading the model. The slice can be specified by defining the corners of a bounding box or by restricting the portion of an array in the model.
- A variety of **cutting tools** allows the user to remove sections from the model to view the internal structure. A “remove section” option allows the user to remove a block or pie shaped section from the model. Another cut-tool is an interactive block eraser. The user drags the eraser to the desired location by holding down the left mouse button, and then double clicks the left mouse button to remove the part of the model under the eraser. A sample KENO3D model visualization using the cutting tools is shown in Figure 1.

* In general, a body in KENO3D is equivalent to a geometry region in KENO.

- Using the “**rebuild in window**” option, the user can draw a window around a portion of the model in the view. KENO3D will then reload the model, displaying only the portion that is in the window. This option is useful when displaying smaller parts of a complicated model.
- The user may use **nesting level control** to reduce the amount of detail in the model by setting the nesting level for arrays and holes to a small value such as zero or 1, depending on the model. With a nesting level of zero, no holes or arrays are filled. If nesting level is 1, only the first level of arrays and holes are filled, etc. A recommended strategy is to load the model with a nesting level of zero, make cuts, adjust the view to desired zoom level and orientation, change the nesting level, and then reload the model. Though for a large model the execution time can be significant, the majority of interactive steps occur in the first few seconds. With care, the reloaded model requires little or no interactive changes.

Figure 1 KENO3D sample LWR shipping container

3 TOOLBARS

There are eight toolbars by default at startup. All toolbars can be docked (the default), moved to any location on the screen, or hidden from view. On exit, KENO3D saves the present configuration in an initialization file. Toolbar positions and other settings will be restored from the initialization file the next time KENO3D is executed. The toolbars and their functionality are described below.

3.1 STANDARD TOOLBAR

The standard toolbar contains seven buttons. Five of the toolbar buttons are related to loading the model.

Open File. This button is the same as the “Open” option under the File menu. The active folder will be opened, and a file dialog box will allow the user to select the appropriate input file to display. For very large problems or problems that the user is not familiar with, simply opening the file can result in excessive execution time. “Preloading” may be safer when dealing with large problems.

Preload File. This button is the same as the “Preload” option under the File menu. The user may select a file to “Preload.” The file will be opened and the input read without displaying the model. After preloading, the user may display information about the model, select a unit to load, mark mixtures for hiding, or load a model slice. This method is the preferred way to open large input files or input files for new models.

Reload Active File From Disk. The file in the active window will be reloaded by rereading the input file. Reload rereads the model input from disk. For example, the user may select this option if the input file has changed, or if the user wishes to reset everything to the initial state.

Custom Reload From KENO3D Memory. A list of KENO units in the active file is presented. The user may select any unit from this list to display. The file on disk is not reread. The user may change the nesting level. This option may be used after a “Preload File.” For example, the user may use this option to “load” a model at a low nesting level (e.g., 0), then make several cuts. Once the model has had sections removed, the user may select to reload the model at a higher nesting level.

Load Slice. A list of KENO units in the active file is presented. The user may select any unit from this list to display. The user may define a “slice” of the model to display by specifying model bounds or array bounds. The dialog presented allows the user to mark mixtures to hide. With the “bound model” option, the user may also specify a portion of the model to be removed (e.g., front quarter, pie slice, etc.) The user may change the nesting level. The file on disk is not reread.

Print File. A print file dialog is started. The display of the active file may be printed.

Copy Screen to Clipboard. Clicking this button causes the image in the active KENO3D window to be copied to the clipboard. The contents of the clipboard may be pasted into other applications (e.g., Word, Paint, WordPerfect, etc.)

3.2 VIEWS TOOLBAR

The Views Toolbar contains four buttons.

Isometric (3D) View. The active model is displayed in an isometric or 3-dimensional view.

Top View. The active model is displayed from the top.

Right View. The active model is displayed from the right.

Front View. The active model is displayed from the front.

3.3 ZOOM TOOLBAR

The Zoom Toolbar contains five buttons.

Zoom All. The active model is zoomed to fill the window.

Zoom Window. The user draws a window around a portion of the model by dragging the mouse while holding the left button down. The window is complete when the user releases the left button. Clicking the left button again will cause that portion of the model that is contained in the window to be zoomed into full view.

Zoom Using Mouse. The active model can be zoomed in or out by holding down the left mouse button, and dragging the mouse up or down.

Zoom-in. The active model is zoomed in to approximately 200% of its present size.

Zoom-out. The active model is zoomed out to approximately 50% of its present size.

3.4 CAMERA TOOLBAR

The Camera Toolbar contains three buttons.

Orbit Camera. The “camera or view position” can be orbited around the active model by holding down the left mouse button and dragging the mouse.

Pan Camera. The view position for the active model can be panned left or right by holding down the left mouse button while dragging the mouse.

Rotate View. This menu button causes the **Rotate View Around Axis** Toolbar to pop up.

3.5 ROTATE VIEW AROUND AXIS

The Rotate View Around Axis Toolbar **does not show up by default**; however, the user may choose to leave this toolbar active. This toolbar becomes active by clicking the Rotate View button on the Camera Toolbar. This toolbar may also be docked.

Rotate View Around X-Axis. The view position for the active model can be rotated around the x-axis by holding down the left mouse button while dragging the mouse.

Rotate View Around Y-Axis. The view position for the active model can be rotated around the y-axis by holding down the left mouse button while dragging the mouse.

Rotate View Around Z-Axis. The view position for the active model can be rotated around the z-axis by holding down the left mouse button while dragging the mouse.

Step. The STEP button allows the user to set the size for incremental rotations. The view position can be rotated incrementally by selecting one of the “rotate view” buttons, holding down the control key or shift key, and clicking the left mouse button.

3.6 DISPLAY PROPERTIES/HIDE OBJECTS TOOLBAR

The Display Properties/Hide Objects Toolbar contains three buttons.

Display Properties. The user may click on selected model parts using the left mouse button to display information about the selected part (e.g., mixture, unit, composition, etc.). The dialog will allow the user to hide the selected entity, mixture, or unit items.

Erase Mixture. Clicking this button will display a list of mixtures in the active model. The user may select a mixture to hide from the view.

Display Model Properties. A click on this button will display information about the model presently in the active view.

3.7 DISPLAY OPTIONS TOOLBAR

The Display Options Toolbar contains four buttons.

Shaded Image. The active model is displayed as a shaded image.

Wireframe Image. The active model is displayed as a wireframe.

Highlight Edges. The active model is displayed as a shaded image with edges highlighted. Clicking this button will toggle edge highlighting on or off.

Refresh Wireframe. Clicking this button will cause the wireframe to be reconstructed at the present zoom level. For example, a very small image of a cylinder might actually be displayed as a hexagon. After zooming, refreshing will cause KENO3D to recalculate the vertices, possibly displaying a smoother wireframe image.

3.8 LEGEND AND AXIS OPTIONS TOOLBAR

The Legend and Axis Options Toolbar contains three buttons.

Color Legend. The user is presented a dialog box showing the various color legend options. A color legend may be presented in the active view or in a separate view. If the user wishes to edit colors, the legend must be in a separate view.

Light Intensity. By clicking this button, a light-intensity dialog box is presented that allows the user to adjust the intensity of eye, distant, and ambient light sources.

Display-axes. This button will toggle the axes on/off. If the axes are not showing in the active view, the user is presented a dialog box showing the various axes options. If the axes are active, clicking this button will remove the axes from the active view.

3.9 CUTAWAY VIEWS TOOLBAR

The Cutaway Views Toolbar contains three buttons.

Interactive Eraser. The model is switched to wireframe. A red, rectangular eraser is shown in the view. The user may drag this eraser to any position. Double clicking the mouse will remove the portion of the model inside the red wireframe. The user may change views during this operation. When satisfied with the position of the eraser, double clicking the mouse will invoke the removal operation. The operation may be cancelled by reclicking the Interactive Eraser button.

Remove Section. The user is presented a dialog box showing the various “slicing” options. Slicing options that specify the shape and location of the section to be hidden from view include pie, quarter, top, right, front, left, back, and bottom.

Rebuild In Window. The user defines a plane, such as an x-y plane. The third plane is considered infinite. The user draws a rectangle around a region of the model by depressing the left mouse button and dragging the mouse. The rectangle is complete when the left mouse button is released. Clicking the left mouse button again will cause KENO3D to reload the model from the file and build only the portion that falls within the window. The user may cancel this operation by reclicking the “Rebuild In Window” button any time prior to the final mouse click.

4 THE MENUS

Six pull-down menus are below the title bar of the main window, with corresponding toolbar buttons for most of the menu options. Prior to loading a model, only three menus are shown (e.g., File, Setup, and Help).

4.1 FILE MENU

- **Open**
- **Close**
- **Preload File**
- **Reload File**
- **Save As Picture**
- **Print, Print Setup**
- **Print Preview**
- **Recent Files**
- **Exit**

Most of these are self-explanatory. **Save As Picture** allows saving the screen image in a Windows Metafile Format for import to other applications such as Word, WordPerfect, etc. **Preload** allows a file to be opened and the input read without displaying the model. After preloading, the user may display information about the model, select a unit to load, mark mixtures for hiding, or load a model slice.

4.2 VIEW MENU

• Standard Views - Isometric (3-D)- Top- Right- Front- Bottom- Back- Left• Select - Unit From Memory- Display Properties- Erase Mixture- Pick Body To Erase	• Camera - Orbit- Rotate- Pan- Zoom Window- Zoom All- Zoom Mouse- Zoom In- Zoom Out• Cutouts - Remove Section- Interactive Eraser- Rebuild In Window

The View Menu also contains the following selections:

- **Set Lights.** By clicking this option, a light-intensity dialog box is presented that allows the user to adjust the intensity of eye, distant, and ambient light sources.
- **Shade.** The active model is displayed as a shaded image.
- **Highlight Entities.** The active model is displayed as a shaded image with edges highlighted. Selecting this option will toggle edge highlighting on or off.
- **Wireframe.** The active model is displayed as a wireframe.
- **Refresh.** Selecting this option will cause the wireframe to be reconstructed at the present zoom level. For example, a very small image of a cylinder might actually be displayed as a hexagon. After zooming, refreshing will cause KENO3D to recalculate the vertices, possibly displaying a smoother wireframe image.
- **Add Legend.** The user is presented a dialog box showing the various color legend options.
- **Show Axes.** This option will toggle the axes on/off. If the axes are not shown in the active view, the user is presented a dialog box showing the various axes options. If the axes are displayed, clicking this option will remove the axes from the active view.
- **Display Properties.** The user may click on selected model parts using the left mouse button to display information about the selected part (e.g., mixture, unit, composition, etc.). The dialog will allow the user to hide the selected entity, mixture, or unit items.
- **Hide Mixture.** The user is presented a list of mixtures in the active model. The user may select a mixture to hide from the view.
- **Display Model Properties.** Information is displayed about the model presently in the active view.
- **Custom Reload.** A list of KENO units in the active file is presented. The user may select any unit from this list to display. The file on disk is not reread. The user may change the nesting level.
- **Load Slice.** A list of KENO units in the active file is presented. The user may select any unit from this list to display. The user may define a “slice” of the model to display by specifying model bounds or array bounds. The dialog presented allows the user to mark mixtures to hide. With the “bound model” option, the user may also specify a portion of the model to be removed (e.g., front quarter, pie slice, etc.) The user may change the nesting level. The file on disk is not reread.

4.3 WINDOW MENU

- **New Window** makes a copy of the active window, which can allow the user to have multiple views of the active model. For example, the view can be changed from isometric to top view in the active window. However, any changes to the active model, such as a cutaway or reload, will be reflected in all windows showing the active model.
- **Cascade** presents all model windows in a hierarchical order.
- **Tile** “tiles” all model windows.

4.4 SETUP MENU

The Setup Menu allows the user to change background color, toolbar settings, optimization level, interactive options, and CSAS options. Changes can be made permanent or temporary. A “Reset Defaults” button will reset all setup options to the original installation settings.

4.5 EDIT MENU

The Edit Menu contains three options.

- **Copy to Clipboard** option copies the active window to the clipboard for importing to other applications, such as commercial word processing and graphics software programs. After selecting this option, and changing to another application, the paste command in the other application can be used to copy the image of the active window into that application.
- **Edit File** opens the CSAS or KENO input file for editing with a user-specified text editor.
- **Editor Setup** provides a dialog that allows the user to specify their preferred text editor.

4.6 HELP MENU

The help menu provides online guidance in the use of KENO3D. Two options are available:

- **Help Topics** starts the fully integrated KENO3D help system. KENO3D help is an embedded HTML Help application with a table of contents, index, and search capabilities.
- **About KENO3D** displays the version number of the software and copyright information.

5 SMALL MODEL EXAMPLE

Using KENO3D to visualize models with less than 400 bodies is relatively easy to do with the default settings. The example demonstrated comes from the KENO V.a user manual and is included in the KENO3D distribution package as “keno12.inp.” To run this problem with KENO3D:

1. Start KENO3D
2. Click the file menu
3. Click Open
4. Move to the folder that contains the KENO V.a examples (i.e., C:\KENO3D\Examples), and select the file (i.e., keno12.inp).
5. Click the Open push button.
6. Use the “Erase Mixture” option to remove mixture zero.
7. Click on “Remove Section” followed by “OK” to get the resulting image shown in Figure 2.

Figure 2 Simple KENO V.a example

6 LARGE MODEL EXAMPLE

Though it is possible to load models with many thousands of bodies, the resulting image may be of limited usefulness. Often the amount of detail is far greater than the resolution of the screen. Also, due to the number of bodies in the image, the interactive behavior of KENO3D may be very sluggish. Depending on the characteristics of a model, the user may choose a variety of ways to load a view of the model. Loading a very large model may take 20 to 30 minutes of execution time, or more, using the “Open File” button. Getting a slice of the same model, with some mixtures removed, might be achieved in 20 to 30 seconds using “Preload File” followed by “Load Slice” **Warning:** when a model slice intersects a majority of the objects in the model, loading a slice can also be very resource intensive (i.e., memory and time). To work effectively the user should try to specify a slice that significantly reduces the number of objects that will ultimately be displayed. Some of the alternatives that may be useful in reducing the number of objects in the KENO3D display when working with larger models are the following:

1. Use “Preload” to read the model input, then load selected units other than the global unit.
2. Use “Preload” to read the model input, then use “Load slice” to reduce the number of bodies to be displayed.
3. Reduce the model detail by setting the nesting level for holes and arrays to 1 or zero. With a nesting level of zero, units referenced in holes or arrays in the global unit are represented by a single body. With a nesting level of 1, units referenced in holes or arrays in the global unit are displayed; however, units referenced in holes or arrays in those units are represented by a single body.

The example demonstrated has more than 280,000 bodies when modeled in full detail. The array in the global unit has 314 levels in the Z direction. This example is included in the KENO3D distribution package as “GA4-TruckCask.inp.” To achieve the image shown in Figure 3:

1. Load the model input using the “preload” option.
2. Use “Load slice” to restrict the image displayed to be the array slice at the 76th Z level.
3. Mark mixtures zero (void) and water to be hidden from view.
4. Use “zoom window” to zoom in on a selected portion of the slice.

Figure 3 A zoomed-in slice of a large KENO V.a model with water and void hidden from view

7 SUMMARY

The primary objective in the development and ongoing enhancements to KENO3D is to provide an easy-to-use visualization tool that allows criticality safety specialists to interactively display their KENO V.a and KENO-VI geometry models. A production version of KENO3D for KENO V.a geometry models was released in 1999. KENO3D with enhancements to allow modeling of KENO-VI geometry models is to be released in 2000.

8 REFERENCES

1. *SCALE: A Modular Code System for Performing Standardized Computer Analyses of Licensing Evaluation*, NUREG/CR-0200, Rev. 6 (ORNL/NUREG/CSD-2R6), Vols. I, II, and III, in press. Available from Radiation Safety Information Computational Center at Oak Ridge National Laboratory as CCC-545.

NRC FORM 335 (2-89) NRCM 1102 3201, 3202		U.S. NUCLEAR REGULATORY COMMISSION BIBLIOGRAPHIC DATA SHEET <i>(See instructions on the reverse)</i>		1. REPORT NUMBER (Assigned by NRC, Add Vol., Supp., Rev., and Addendum Numbers, if any.) NUREG/CR-6662 ORNL/TM-1999/284	
2. TITLE AND SUBTITLE KENO3D Visualization Tool for KENO V.a and KENO-VI Geometry Models				3. DATE REPORT PUBLISHED	
				MONTH March	YEAR 2000
				4. FIN OR GRANT NUMBER	
5. AUTHOR(S) J. E. Horwedel and S. M. Bowman				6. TYPE OF REPORT Technical	
				7. PERIOD COVERED <i>(Inclusive Dates)</i>	
8. PERFORMING ORGANIZATION — NAME AND ADDRESS <i>(If NRC, provide Division, Office or Region, U.S. Nuclear Regulatory Commission, and mailing address; if contractor, provide name and mailing address.)</i> Oak Ridge National Laboratory Post Office Box 2008 Oak Ridge, Tennessee 37831-6370					
9. SPONSORING ORGANIZATION — NAME AND ADDRESS <i>(If NRC, type "Same as above"; if contractor, provide NRC Division, Office or Region, U.S. Regulatory Commission, and mailing address.)</i> Fuel Cycle Safety and Safeguards Office of Nuclear Material Safety and Safeguards U.S. Nuclear Regulatory Commission Washington, DC 20555-0001					
10. SUPPLEMENTARY NOTES H. D. Felsher, NRC Program Manager					
11. ABSTRACT <i>(200 words or less)</i> <p>The SCALE (<u>S</u>tandardized <u>C</u>omputer <u>A</u>nalyses for <u>L</u>icensing <u>E</u>valuations) computer software system developed at Oak Ridge National Ridge National Laboratory (ORNL) is widely used and accepted around the world for criticality safety analyses. SCALE includes the well-known KENO V.a and KENO VI three-dimensional (3-D) Monte Carlo criticality computer codes.</p> <p>Criticality safety analyses often require detailed modeling of complex geometries. Checking the accuracy of these models can be enhanced by effective visualization tools. To address this need, ORNL has recently developed a powerful state-of-the-art visualization tool called KENO3D. KENO3D enables KENO V.a and KENO VI users to interactively display their three-dimensional geometry models. The interactive options include: Shaded or wireframe images; Standard views, such as top view, side view, front view, and isometric (3-D) view; Rotating the model; Zooming in on selected locations; Selecting parts of the model to display; Editing colors and displaying legends; Displaying properties of any unit in the model; Creating cut-away views; Removing units from the model; Printing image or saving image to common graphics formats</p>					
12. KEY WORDS/DESCRIPTORS <i>(List words or phrases that will assist researchers in locating the report.)</i> SCALE, criticality safety, graphics , KENO, 3-D, visualization				13. AVAILABILITY STATEMENT unlimited	
				14. SECURITY CLASSIFICATION <i>(This Page)</i> unclassified	
				<i>(This Report)</i> unclassified	
				15. NUMBER OF PAGES	
				16. PRICE	

INTERNAL DISTRIBUTION

1. D. L. Barnett	30. B. L. Kirk
2-5. S. M. Bowman (4)	31. M. A. Kuliasha
6. B. L. Broadhead	32. J. B. Manneschildt
7. K. J. Carroll	33. B. D. Murphy
8-11. W. C. Carter (4)	34-36. C. V. Parks (3)
12. R. L. Childs	37. L. M. Petrie
13. M. D. DeHart	38. R. T. Primm
14. M. E. Dunn	39. C. E. Pugh
15. K. R. Elam	40. B. T. Rearden
16. R. J. Ellis	41. J. P. Renier
17. M. B. Emmett	42. R. C. Robinson
18. P. B. Fox	43. R. W. Roussin
19. I. C. Gauld	44. C. H. Shappert
20. J. C. Gehin	45. R. G. Taylor
21. G. R. Handley	46. T. E. Valentine
22. O. W. Hermann	47. J. C. Wagner
23. D. F. Hollenbach	48. R. M. Westfall
24. C. M. Hopper	49. Central Research Library
25-28. J. E. Horwedel (4)	50. ORNL Laboratory Records-RC
29. D. T. Ingersoll	

EXTERNAL DISTRIBUTION

51. F. M. Alcorn, BWX Technologies, Inc., Naval Nuclear Fuel, 212 Windsor Rd., Lynchburg, VA 24502
52. R. E. Anderson, Los Alamos National Laboratory, P.O. Box 1663, NIS-6, MS J562, Los Alamos, NM 87545
53. W. L. Andrews, Defense Nuclear Facilities Safety Board, 625 Indiana Ave., Washington, DC 20004
54. C. Apperson, Westinghouse Savannah River Company, Savannah River Site, Bldg. 773-11A, Aiken, SC 29808-0001
55. M. G. Bailey, Office of Nuclear Material Safety & Safeguards, U.S. Nuclear

- Regulatory Commission, MS O13 D13, Washington, DC 20555
56. A. B. Barto, Office of Nuclear Material Safety & Safeguards, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, DC 20555
 57. L. Berg, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 58. R. N. Blomquist, Argonne National Laboratory, RA/208, 9700 S. Case Ave., Argonne, IL 60439-4842
 59. C. Boman, BWX Technologies, Inc., Naval Nuclear Fuel, P.O. Box 785, Lynchburg, VA 24505
 60. J. B. Briggs, INEEL, P.O. Box 1625, MS-3855, Idaho Falls, ID 83402
 61. T. Burns, Defense Nuclear Facilities Safety Board, 625 Indiana Ave., Washington, DC 20004
 62. S. A. Burrows, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, DC 20555-0001
 63. R. D. Busch, University of New Mexico, Chemical and Nuclear Engineering Department, FEC 209, Albuquerque, NM 87131-1341
 64. D. E. Carlson, NMSS/SFPO/STRD, U.S. Nuclear Regulatory Commission, MS O13 D3, Washington, D.C. 20555-0001
 65. G. Comfort, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 66. P. Cousinou, Institute of Protection and Nuclear Safety, B. P. 6 - 92265 Fontenay-Aux-Roses, Cedex, France
 67. D. R. Damon, NMSS/FCSS/FLIB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 68. J. R. Davis, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555
 69. H. L. Dodds, University of Tennessee, Nuclear Engineering Dept., 214 Pasqua Engineering Bldg., Knoxville, TN 37922
 70. T. W. Doering, Framatome Cogema Fuels, 1261 Town Center Drive, Las Vegas, NV 89124
 71. D. D. Ebert, RES/DSARE/SMSAB, U.S. Nuclear Regulatory Commission, MS T10 K8, Washington, D.C. 20555-0001
 72. C. W. Emeigh, NMSS/FCSS/FLIB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 73. H. D. Felsher, NMSS/FCSS/FLIB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 74. P. Felsher, Rocky Flats Environment Technology Site, Bldg. T886B, P.O. Box 464, Golden, CO 80402-0464
 75. J. R. Felty, Science Applications Int'l Corp., 2418 N. Dickerson St., Arlington, VA 22207
 76. I. E. Fergus, U.S. Department of Energy, EH-22, 20300 Century Blvd., Germantown, MD 20874
 77. R. Frost, Navarro Research and Engineering, Inc., 659 Emory Valley Road Oak Ridge, TN 37831

78. E. K. Fujita, Argonne National Laboratory, 9700 South Cass Avenue, RA/208, Argonne, IL 60439-4842
79. M. A. Galloway, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
80. A. S. Garcia, U.S. Department of Energy, Idaho Operations Office, 850 Energy Dr., MS 1154, Idaho Falls, ID 83401-1563
81. F. Gee, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
82. A.S. Giantelli, NMSS/SFPO/TRD, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
83. J. Gulliford, Winfrith Technology Centre, 306/A32, AEA Technology PLC, Winfrith, Dorchester, Dorset DT2 8DH
84. S. T. Huang, Lawrence Livermore National Laboratory, MS L-128, P.O. Box 808, Livermore, CA 94551
85. J. C. Ingram, Bechtel Jacobs Company LLC, P. O. Box 4699, Bldg. K-1320, MS-7592, Oak Ridge, TN 37831-7592
86. S. Keeton, Lawrence Livermore National Laboratory, P.O. Box 808, MS L-634 Livermore, CA 94551-0808
87. E. F. Kendall, U.S. Department of Energy, Oak Ridge Operations Office, YSO, P.O. Box 2001, Oak Ridge, TN 37831
88. K. D. Kimball, NISYS Corporation, 6055 Atlantic Blvd., Suite G-2, Norcross, GA 30071
89. R. Knief, XE Corporation (XEC), P.O. Box 90818, Albuquerque, NM 87199-0818
90. L. I. Kopp, NRR/DSSA/SRXB, U.S. Nuclear Regulatory Commission, MS O10 B3, Washington, D.C. 20555-0001
91. J. Kovacic, NMSS/SFPO/STRD, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
92. M. N. Leach, NMSS/FCAA, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, DC 20555-0001
93. M. A. Lee, U.S. Department of Energy, Livermore Operations, 7000 East St., P.O. Box 808, L-293, Livermore, CA 94551-0808
94. L. J. Lessler, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
95. R. J. Lewis, NMSS/SFPO/SLID, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
96. J. R. Liaw, Argonne National Laboratory, Bldg. 208, 9700 S. Cass Avenue Argonne, IL 60439
97. R. Libby, Pacific Northwest National Laboratory, P.O. Box 999, M/S K7-74, Richland, WA 99352
98. J. J. Lichtenwalter, Navarro Research and Engineering, 659 Emory Valley Road, Oak Ridge, TN 37831
99. R. C. Little, Los Alamos National Laboratory, MS F663, P.O. Box 1663, Los Alamos, NM 87545
100. Y. Y. Liu, Argonne National Laboratory, 9700 South Cass Avenue, 308/D108

- Argonne, IL 60439
101. C. D. Manning, Siemens Power Corporation, 2101 Horn Rapids Road, P.O. Box 130, Richland, WA 99352-0130
 102. R. McBroom, U.S. Department of Energy, Oak Ridge Operations Office, YSO, P.O. Box 2001, Oak Ridge, TN 37831
 103. J. McKamy, U.S. Department of Energy, EH-34, 19901 Germantown Road, Germantown, MD 20874-1290
 104. R. D. McKnight, Argonne National Laboratory, 9700 S. Cass Ave., Argonne, IL 60439-4842
 105. T. P. McLaughlin, Los Alamos National Laboratory, P.O. Box 1663, Los Alamos, NM 87545
 106. D. E. I. Mennerdal, E M Systems, Starvägen 12, Täby, SWEDEN S-18357
 107. R. D. Montgomery, Nuclear Fuel Services, Inc., 1205 Banner Hill Rd., Erwin, TN 37650
 108. L. Montierth, Lockheed Martin Idaho Tech. Co., P.O. Box 1625, MS 3458, Idaho Falls, ID 83415-3458
 109. D. C. Morey, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
 110. R. D. Mosteller, Los Alamos National Laboratory, MS J562, Los Alamos, NM 87545
 111. J. A. Myers, NMSS/SFPO, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
 112. W. D. Newmyer, Westinghouse CNFD, Drawer R, Columbia, SC 29250
 113. K. A. Niemer, Duke Engineering & Services, 400 S. Tryon St., WC26B, P.O. Box 1004, Charlotte, NC 28201-1004
 114. C. W. Nilsen, RES/DSARE/SMSAB, U.S. Nuclear Regulatory Commission, MS T9 F31, Washington, D.C. 20555-0001
 - 115-116. Office of Scientific and Technical Information, U.S. Department of Energy, P.O.Box 62, Oak Ridge, TN 37831
 117. H. Okuno, Japan Atomic Energy Research Institute, 2-4 Shirakara-shirane, Tokaimura, Ibaraki-ken, JAPAN 319-1195
 118. S. A. Parra, Lawrence Livermore National Laboratory, P.O. Box 808, MS L-128, Livermore, CA 94551
 119. L. E. Paulson, Manager, Nuclear Safety, GE Nuclear Energy, P.O. Box 780, Castle Hayne Road, Wilmington, NC 28405
 120. S. Payne, U.S. DOE/AL/SASD, P.O. Box 5400, Albuquerque, NM 87185-5400
 121. V. A. Perin, NMSS/DWM/HLWB, U.S. Nuclear Regulatory Commission, MS T7 F3, Washington, D.C. 20555-0001
 122. R. E. Pevey, University of Tennessee, Nuclear Engineering Dept., 214 Pasqua Engineering Bldg., Knoxville, TN 37922
 123. J. Philbin, Sandia National Laboratory, P.O. Box 5800, Albuquerque, NM 87185-1143
 124. R. C. Pierson, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001

125. A. W. Prichard, Pacific Northwest National Laboratory, P.O. Box 999, MSIN: K8-34, Richland, WA 99352
126. M. Brady Raap, Battelle Pacific Northwest National Lab, P.O. Box 999 / MS K8-34 Richland, WA 99352
127. M. Rahimi, NMSS/DWM/HLWB, U.S. Nuclear Regulatory Commission, MS T7 F3, Washington, D.C. 20555-0001
128. T. A. Reilly, Westinghouse Safety Management Solutions, 1993 South Centennial Dr., Aiken, SC 29803
129. C. Rogers, Duke Engineering Services, 10503 W. Williams Road, Benton City, WA 99320
130. C. T. Rombough, CTR Technical Services, Inc., 950 Sugarloaf Rd., Manitou Springs, CO 80829
131. B. Rothleder, U.S. Department of Energy, EH-31, 19901 Germantown Rd., Germantown, MD 20874-1290
132. W. S. Schwink, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
133. M. K. Sheaffer, Lawrence Livermore National Laboratory, P.O. Box 808, L-634, Livermore, CA 94550
134. T. S. Sherr, NMSS/FCSS/FLIB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
135. J. A. Smith, NMSS/FCSS, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
136. T. Taylor, Lockheed Martin Idaho Tech. Co., P.O. Box 1625, MS 3458, Idaho Falls, ID 83415-3458
137. D. A. Thomas, Framatome Cogema Fuels, 1261 Town Center Drive, Las Vegas, NV 89124
138. J. A. Thornton, Duke Engineering & Services, 400 S. Tryon St., WC26B, P.O. Box 1004, Charlotte, NC 28201-1004
139. P. Ting, NMSS/FCSS/FCOB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
140. W. W. Tippl, Siemens AG, Power Generation Group (KWU) , Dept. NDM3 Postfach 10 10 63, Berliner Strasse 295-303, D-63010 Offenbach am Main /Germany
141. H. Toffer, Fluor Daniel Northwest, Inc., P.O. Box 1050, MSIN B4-44, 1100 Jadwin Ave., Richland, WA 99352-1050
142. C. Tripp, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
143. E. F. Trumble, Westinghouse Safety Management Solutions, P.O. Box 5388, 1993 South Centennial Dr., Aiken, SC 29803
144. M. Wangler, Office of Site Operations, EM-5/CLV-1059, U.S. Department of Energy, 19901 Germantown Road, Germantown, MD 20874-1290
145. M. D. Waters, NMSS/SFPO/SLID, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001

146. M. F. Weber, NMSS/FCSS, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001
147. R. M. Weller, NMSS/DWM/URLL, U.S. Nuclear Regulatory Commission, MS T7 J8, Washington, D.C. 20555-0001
148. L. Wetzel, BWX Technologies, Inc., Naval Nuclear Fuel, P.O. Box 785, Lynchburg, VA 24505
149. S. A. Whaley, NMSS/SFPO/STRD, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
150. B. H. White, NMSS/SFPO/STRD, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
151. D. W. Williams, Westinghouse Electric Corporation, 5801 Bluff Rd MS#15, Columbia, SC 29209
152. R. E. Wilson, Safe Sites of Colorado, P.O. Box 464, Golden, CO 80402-0464
153. C. J. Withee, NMSS/SFPO/STRD, U.S. Nuclear Regulatory Commission, MS O13 D13, Washington, D.C. 20555-0001
154. A. Wong, NMSS/FCSS/FSPB, U.S. Nuclear Regulatory Commission, MS T8 A33, Washington, D.C. 20555-0001