Linker

LA-13829-PR
Progress Report

Approved for public release;
distribution is unlimited.

Los Alamos National Laboratory is
operated by the University of California
for the US Department of Energy
under contract W-7405-ENG-36.

Los Alamos
NATIONAL LABORATORY
Los Alamos, New Mexico 87545

LDRD

**LABORATORY DIRECTED
RESEARCH & DEVELOPMENT
2000
ANNUAL PROGRESS REPORT**

LDRD

LABORATORY DIRECTED RESEARCH & DEVELOPMENT

Published by Los Alamos National Laboratory

Laboratory Director: John C. Browne

Director for Science and Technology Base Program: Allen Hartford

Program Manager for Laboratory Directed Research and Development:
David E. Watkins

Scientific Editor: Rita Spencer and David E. Watkins

LDRD Office Support: Lennett Rendon, Leonard Salazar, Aurelia Sisneros,
and Victoria DeVargas

Managing Editor: Denise Sessions (*Communication Arts & Services, IM-1*)

Editors: Nikki Goldman, Faith Harp, Marty DeLanoy, Sheila Molony,
Linda K. Wood, Marian Goad, Cynthia Phillips, Eileen Patterson,
Jennifer Graham, Amy Reeves, Betty Katz, Pat Wing, Judy Prono,
Denise Sessions, and Meredith Coonley (*IM-1*)

Designer: Gail Flower (*IM-1*)

Layout, Composition, and Production: Julie Medina (*IM-1*)

Printing Coordination: Guadalupe D. Archuleta (*Imaging Services, IM-4*)

The four most recent reports in this unclassified series are **LA-13278-PR, LA-13433-PR,
LA-13595-PR, and LA-13730-PR.**

This report is available electronically on the Web (<http://www.doe.gov/bridge>).

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither The Regents of the University of California, the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by The Regents of the University of California, the United States Government, or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of The Regents of the University of California, the United States Government, or any agency thereof. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Contents

1 LDRD Overview

Directed Research Projects

Atomic, Molecular, Optical, and Plasma Physics, Fluids, and Beams

10	Applications of Quantum Technologies	16	Ultrafast Time-Resolved Atomic Probes of Strategic Materials
12	High Power Microwave Science and Technology	18	SDSS Photometry and Controls
13	Next-Generation Sophistication in Defense and High-Energy-Density Physics Exploratory Research		

Bioscience

19	Bioremediation Science to Meet National Challenges	26	Host-Pathogen Interactions
20	Optical Biosensors	29	Molecular Foundations of the Host-Pathogen Interface
21	Pathogen Detection in the Real World	30	Sensitive and Rapid Detection of Diagnostically Important Proteins
24	Functional Genomics		
25	The Identification of Proteins That Bind to Novel DNA Sequences/ Structures		

Chemistry

31	A New Paradigm in Separations: Molecular Recognition Membranes	37	Synergistic Effects in Actinide Molecular Science
33	Condensed Phase Kinetics and Reduced Reaction Mechanisms of Energetic Materials	39	Structural Biology Applied to DNA Damage and Repair
35	Cradle-to-Grave Carbon Management	40	Chemical Reactions at Actinide Surfaces: Implications for Nuclear Material Aging and Safety

Computer Science and Software Engineering

42	Foundations of Simulation Science

Directed Research Projects (cont.)

Engineering Science

- 44 Hard and Deeply Buried Target Defeat
- 46 Nuclear Materials Management Systems for Proliferation Resistance, Environmental Protection, and Sustainability

Geoscience, Space Science, and Astrophysics

47 Coupled Environmental Modeling 49 Space Science and Exploration 51 Dynamic Processes of the Earth	53 Integrated Ocean and Atmospheric Science and Modeling 57 Earth's Plasma and Radiation Environment

Instrumentation and Diagnostics

- 60 Advanced Nuclear Measurement Science
- 61 Spall/Ejecta Studies with Proton Radiography

Materials Science

63 Investigation of Spin, Charge, and Lattice Degrees of Freedom in Magnetoresistive Materials 64 Self-Assembling Organic Electronic Materials 66 Coordinated Synthesis, Characterization, and Modeling of Materials 67 Development of Semiconducting Polymeric Films with High Concentrations of Boron 70 Neutron and Accelerator-Based Science	73 Static and Dynamic Electronic Response of Actinide Single Crystals in Magnetic Fields 74 Understanding and Predicting Behavior of Polymeric Materials with Time 78 A Scaleable Silicon-Based Nuclear Spin Quantum Computer 79 Organizing Principles across Classes of Complex Electronic Materials

Directed Research Projects (cont.)

Mathematics, Simulation, and Modeling

81	Discrete Simulation of Nonlinear Systems	89	Management of Nuclear Warhead and Infrastructure Reduction
83	Probabilistic and Combinatorial Analysis for Biological Systems	90	Strategic Computing Applications
84	Nonlinear Complex Phenomena	91	Theoretical Quantum Computation
87	Quantifying and Reducing Uncertainty in Predictions of Complex Phenomena	92	Advanced 3-D Modeling and Simulation
		93	ElectriSims

Nuclear and Particle Physics

95	Nonequilibrium Science: Assessment, Control, and Prediction
96	Ultracold Neutron Science
98	Neutrino Physics Experiments

Exploratory Research Projects

Atomic, Molecular, Optical, and Plasma Physics, Fluids, and Beams

100 Artificial Atoms Probed by Femtosecond Pulses: Evolution of Optical Properties during the Bulk-Atomic Transformation 103 Laser-Plasma Interactions in Diffraction-Limited Beams 104 Stochastic Resonance in Arrays with Tunable Nonlinearity and Coupling 105 Create and Study Quantum Degenerate Systems 106 Dynamical Stability and Quantum Chaos of Ions in a Linear Trap 107 Quantum Coherence and Decoherence: Trapping a Schrödinger Cat 108 Quantum Feedback Control: Methods and Applications	109 Direct Observation of Individual, Optical Energy-Transfer Events 110 Optical Investigations of Quantum Information 112 Cold Atom Fermion Coherence 113 Ultrafast Dynamics of Laser-Plasma Interactions in Solids 114 Reconnection Scaling Experiment Transition from Resistive Magnetohydrodynamics to Collisionless Reconnection 115 Three-Body Atomic Recombination in Bose-Einstein Condensates 116 Macroscopic Quantum and Statistical Science

Bioscience

117 Noninvasive Techniques for Genetic Analysis 118 Rapid Genotyping Assay for Beryllium Disease Susceptibility 119 Next Generation of Molecular Dynamics: Implicit Solvent/Langevin Models for Folding of Peptides and Proteins 120 Fundamental Process in Polymer Light-Emitting Electrochemical Cells 121 Computational Studies of the Role of Water Fluctuations in Protein Dynamics and Folding 122 The Molecular Aging Clock 123 Hyperthermophile Biocatalysis: The Molecular Basis of Enzyme Stability and Activity 124 New Approaches to High-Throughput DNA Sequence Validation 125 Development of a Superconducting Quantum Interference Device (SQUID) Microscope for Imaging Cortical Neuronal Columns	126 Rapidly Photocleavable Caged Proteins 127 Universal Scaling Laws in Biology: Aerobic Metabolism, Energy Use, and Longevity 128 Third-Generation Oligonucleic Acid Analogs 130 Coordination of Carbon and Nitrogen Metabolism 131 DNA Repair and Molecular Assembly Involved in Chromosome Condensation 132 Characterization of Exceptional Chromosomal Regions by DNA Sequencing 133 Studying the Spread of HIV Using Genetic Sequences 134 Single Protein Spectroscopy with Native Fluorescence 135 Sensitive Mass Spectroscopic Analysis of Biomolecules in the Megadalton Range 136 Novel Mass Tagging with Stable Isotopes in Postgenomic Studies

Exploratory Research Projects (cont.)

Chemistry

137	Unraveling Heterogeneous Surface Reaction Kinetics	148	Plutonium-Mediated Catalysis
138	Soluble Polymers for Enhancing Biocatalysis	149	Understanding and Controlling Micelles in Supercritical Carbon Dioxide
139	Alkane Chemistry of Ligated (Allyl)Iridium Moieties on Metal Oxide Supports and Multilayer Hydrogen Transport Membranes	150	Synthesis and Characterization of High-Performance Propellants
141	Novel Surfactants and Micellar Chemistry for Enhanced Reactivity and Separations	152	Anomalous Isotope Effects in Ozone Formation
144	Supported Technetium Chemistry	153	Electron Transfer on the Vibrational Time Scale in Mixed Valence Systems
145	Nonadiabatic Processes in Chemical Reactions	154	Advanced Membrane Architectures for Separation of Actinide and Toxic Metal Ions
147	Description of Complex Adsorption from a Simple Equation of State	155	Redox Chemistry of Os (VI)-Nitrado Complexes

Computer Science and Software Engineering

156	Data Structures and Computer Arithmetic for Quantifying Uncertainty	165	Adaptive Superscalar Microprocessor Architecture
157	Extremal Optimization	166	High-Performance TCP over the Next-Generation Internet
160	Machine Learning	167	Computing with Networks of Spiking Neurons: Application to Real-Time Segmentation of Natural Scenes
161	Combinatorial Optimization in Biology		
163	A Computational Framework for Multiscale Shape Characterization and Recognition		

Exploratory Research Projects (cont.)

Engineering Science

168	Use of Metallic Glasses in Ceramic-Metal Joining	181	Next-Generation High-Power Microwave Source
169	Development and Engineering of the Ion-Cut and Low-Temperature Direct-Bonding Process	183	Improvement of Wear Resistance in Quenched and Tempered Steels by Cryogenic Treatment
170	Pulse Shaping in Explosive-Pulsed-Power Systems	184	Engineering of Plastic Artificial Muscles
171	Acoustic-Network Refrigerators	187	Adaptive Femtosecond Pulse Delivery
172	Use of Directed-Light Fabrication for Fabricating Functionally Gradient Materials	188	A New Method for Cooling High-Frequency Conductors
175	Composite Films Made with Metallic Carbon Nanotubes	189	Effect of Solid-Solid Phase Transformations on Elastic Constitutive Relations
178	Highly Constrained Bandwidth Combinational Algorithm for Transmission of Speech (HC-BATS)	190	Study of the Secondary Flows in Thermoacoustic-Stirling Hybrid Heat Engines
179	Hydrogen Storage in Intermetallic Alloys	191	Engineered Triple-Phase Boundary Gas Sensors

Geoscience, Space Science, and Astrophysics

192	Lightning in the Atmosphere and in the Solar Nebula	206	Multiscale Physics of Multiphase Flow in Porous Media
193	High Pressure Crystal Chemistry of Hydrated Minerals	207	Antarctic Circumpolar Wave and El Niño
196	New Windows on Gamma-Ray Bursts	208	Low-Energy Neutral Atom Imaging: Watching Magnetospheric Dynamics
198	Advanced Computational Analysis of Disordered Materials and Clay Minerals	211	Galaxies and Large-Scale Structure in a Universe with a Cosmological Constant
200	Tsunami from Asteroid and Comet Impacts	212	Nonlinear Dynamical Processes Involved in Earthquake-Induced Strong Ground Motion
201	A Large-Aperture, Wide-Angle Air Cerenkov Telescope	213	Heat Flux Dissipation in Collisionless Space and Astrophysical Plasmas
202	A New Method for Modeling Wave Propagation in Strongly Heterogeneous Media: Applications to Seismic Wave Propagation in the Earth	214	Analysis of Large-Scale Structure in the Sloan Digital Sky Survey
203	The Genesis and Evolution of Basalt on the Moon	216	Observing High-Energy Transients with Milagro
204	Sky Patrol Analysis with the Robotic Optical Transient Search Experiment	217	Optical and Chemical Studies of Sulfate Aerosols to Predict the Recovery of the Ozone Layer and Constrain the Earth's Radiation Budget
205	Galactic Magnetic Fields: Their Origin and Manifestation in Accretion Disks around Supermassive Black Holes	218	Tracer Tomography in Unsaturated Fractured Rock
		219	Optical Refrigeration

Exploratory Research Projects (cont.)

Instrumentation and Diagnostics

- 220 An Integrated Solid-State Optical Device with High-Speed Scanning, Variable Focusing, and Frequency-Doubling Capabilities
- 221 Cryptographic Key Generation using Long-Baseline Radio Interferometry
- 222 X-Ray Refractive Optics for Astrophysics and Nonproliferation
- 224 Time-Resolved Photon Migration Tomography and Spectroscopy
- 227 Integrated Optical Biosensor
- 228 High-Quantum-Efficiency, Silicon-Integrated, Tunable-Band-Gap Infrared-Detection Devices Based on Rhenium Molybdenum Silicide
- 230 Electron Tunneling Spectroscopy of Buried Interfaces
- 231 The Nonlinear Elasticity Project
- 232 Direct Probing of Cloud Radiative Properties Using a Daytime Wide-Angle Imaging Lidar
- 235 Cumulative On-Orbit Magnetic Pointing and Attribution of Spread Signals
- 236 Remote Sensing of Volcanoes
- 237 Fundamental Underpinnings for Predictive Modeling of Complex Systems

Materials Science

- 238 Unusual Metal Behavior in Taylor Microwires
- 239 Bulk Ferromagnetic Metallic Glasses
- 242 Unconventional Superconductivity and Violation of Time-Reversal Invariance
- 245 New Vortex Phases in Irradiated High-Temperature Superconductors
- 246 Novel Approaches to Low-Temperature Thin-Film Materials Chemistry: Kinetic Energy Activated Molecular Beam Epitaxy
- 248 Bulk Rapid Solidification
- 251 Intrinsic Local Modes in Low-Dimensional Materials
- 252 Organic Electronic Materials under Intense Electrical Injection
- 253 Investigation of Experimental Defect Interactions in Materials by Integrating Experimental Techniques with Large-Scale Simulations
- 255 Synthesis and Characterization of Superhard Materials
- 257 From Artificial Atoms to Artificial Solids: Soft-Matter Nanotechnology
- 260 Direct Observations of Individual Relaxation Modes in Polymers
- 261 Time-Resolved Study of Martensitic Phase Transformations
- 262 In Situ Characterization and Failure Prediction of Composites
- 263 Modeling Complex Processes in Hard and Soft Materials
- 266 Complex Behavior in Novel Correlated Electron Materials
- 267 Time-Resolved Fluorescence Emission from Biological and Electronic Materials
- 268 Investigations of Complex Deformation Behavior in Materials
- 271 In Situ Synthesis of Organic/Inorganic Nanocomposites
- 272 Understanding Complex Instrumentation Issues Involving Polarized Neutron Beams and High Magnetic Fields

Exploratory Research Projects (cont.)

Mathematics, Simulation, and Modeling

273 Efficient Multilevel Iterative Methods for Nonlinear PDEs 274 Extending the Theory of Resonant Perturbations to Partial Differential Equations, with Applications to Nonlinear Optics 275 Invariant Discretizations for Computational Gas Dynamics 276 Unitary Symmetry, Discrete Mathematics, and Combinatorics 277 Statics and Dynamics of Granular Media	280 Quantum Physics Algorithms 281 New Dispersive Models of Fluid Turbulence 282 New Perspectives in Mathematical Modeling of High-Bit-Rate Optical-Fiber Telecommunications 285 Effective Arbitrary Lagrangian-Eulerian Strategies 286 Direct Numerical Simulation and Stochastic Modeling in Ocean Dynamics 287 Rayleigh-Ritz Computation of Multitime Statistics 288 PREDICT

Nuclear and Particle Physics

289 Exploring and Testing the Standard Model and Beyond 290 Determination of the Neutron Lifetime and Ultracold-Neutron Source Development 291 Parity Nonconservation in the Reaction $n + p = d + \gamma$ 292 A Search for Superradiant Emission in a Nuclear Isomer Crystal 293 High-Energy Cosmic Transients 294 Weak Interactions at Low Energy 295 Weak Interaction in Nuclei 296 Exact Solutions of Quantum Gauge Theories from String Solitons 297 Development of Detectors and Electronics for the Study of the Beta Decay of Polarized Neutrons at LANSCE	298 The Search for Dark Matter 299 Improved Matching of Lattice and Continuum QCD 300 Fundamental Symmetries with Trapped Atoms 302 CP Violation in Kaon Decays: Epsilon and ϵ'/ϵ 303 Test of Big Bang Nucleosynthesis Models by Precision Measurement of the $n + {}^1\text{H} \rightarrow {}^2\text{D} + \gamma$ Cross Section 305 Precision Analysis of Parity-Nonconserving Weak Coupling Constants 306 SQUIDs as Sensors to Measure the Neutron Electric Dipole Moment 307 Low-Energy Solar Neutrino Spectroscopy

308 Table of Projects

317 Index of Principal Investigators

Overview

Abstract

This is the FY00 Annual Progress report for the Laboratory Directed Research and Development (LDRD) Program at Los Alamos National Laboratory. It gives an overview of the LDRD Program, summarizes progress on each project conducted during FY00, characterizes the projects according to their relevance to major funding sources, and provides an index to principal investigators. Project summaries are grouped by LDRD component: Directed Research and Exploratory Research. Within each component, they are further grouped into the ten technical categories: (1) atomic, molecular, optical, and plasma physics, fluids, and beams, (2) bioscience, (3) chemistry, (4) computer science and software engineering, (5) engineering science, (6) geoscience, space science, and astrophysics, (7) instrumentation and diagnostics, (8) materials science, (9) mathematics, simulation, and modeling, and (10) nuclear and particle physics.

LDRD Program Overview—FY2000

David Watkins and Rita Spencer

The Laboratory Directed Research and Development (LDRD) program is seen by the Los Alamos National Laboratory (LANL) Director, Dr. John C. Browne, as a key strategic tool to ensure the future vitality of the science and technology at the Laboratory. In a statement to the Military Procurement Subcommittee of the Committee on Armed Services,¹ Dr. Browne described his view of LDRD as follows:

The DOE's Laboratory Directed Research and Development program has been a primary vehicle for the national laboratories to support the exploratory and innovative research any scientific institution must have to keep it vital and effective.

The research and development projects initiated through LDRD, embryonic and leading-edge in nature, remain commensurate with our mission and directed toward support of the nation's scientific needs in the long term.

Los Alamos is first and foremost a national security laboratory, and the scientific work conducted in the LDRD program supports the long-term DOE national security mission. In order to maintain the broad range of multidisciplinary capabilities required for the national security mission, the Laboratory receives funding from a variety of sources including various offices in DOE. To determine the level of support LDRD provides for the national security mission, we examine each year the extent to which LDRD projects support the three DOE national security program areas outlined in the National Defense Authorization Act for FY97.² These areas are identified in the Act as:

- Section 3101, Weapons Activities—stockpile stewardship and stockpile management
- Section 3102, Environmental Restoration and Waste Management—environmental restoration, waste management, nuclear materials and facilities stabilization, technology development, and environmental science
- Section 3104, Other Defense Activities—verification and control technology, nuclear safeguards and security, and fissile materials disposition

To reflect more accurately the national security activity conducted at the Laboratory, we added a fourth area to those outlined in the three referenced sections, namely the Department of Defense (DoD) component of the reimbursable programs funded by the Work for Others (WFO) Program. Taken together, these four sections form the basis for the national security activities at Los Alamos.

Each project is examined to determine its relevance to these categories. The data resulting from this analysis is found in the Table of Projects at the end of this document. This analysis demonstrates that over 90% of the LDRD funding goes to projects relevant to national security missions. This figure substantially exceeds the fraction of LANL's budget that is derived from national security programs (about 65%).

Authorization and Funding

LDRD was instituted by the National Defense Authorization Act, 1991,³ as a means for the DOE laboratories to conduct work of a more fundamental and creative nature than the more developed scientific approaches normally selected for programmatic focus. Recognizing that sustained excellence in mission execution requires that Laboratory capabilities be continually reinvigorated, Congress acknowledged that the ability to direct resources to such work is often the difference between institutional excellence and mediocrity. The LDRD program drives the creation of powerful scientific and technological capabilities that are applied to national problems for which science can provide a solution. It is key to ensuring a high return on the nation's investment in the Laboratory.

In the same National Defense Authorization Act, Congress set a funding limit for each DOE laboratory's program of 6% of that laboratory's total operating and capital equipment budget. LDRD budgets for each laboratory consist of both operating and capital equipment funds that are generated through the application of a uniform assessment to direct-funded programs including all DOE and reimbursable WFO programs.

This year proved to be particularly trying for the LANL LDRD program. After the program plan had defined which continuing projects and new proposals would be funded, the FY00 Energy and Water Development Appropriations Act⁴ reduced available funding by stating,

Of the funds in this Act provided to government-owned contractor-operated laboratories, not to exceed four percent shall be available to be used for Laboratory Directed Research and Development: Provided, that none of the funds in the Environmental Management programs are available for Laboratory Directed Research and Development.

Not only was the funding formula reduced, but the assessment was not to be collected from programs funded by the DOE Environmental Management Program, thus reducing the Laboratory LDRD budget by 37% relative to the LDRD program plan submitted in August 1999. As well as eliminating and reducing much of the Laboratory's most essential science, this turn of events affected the morale of the staff and adversely affected retention and recruiting of new talent. For example, the number of postdoctoral employees at LANL was down substantially in FY00. Postdoctoral employees supported by the LDRD program dropped by 38% relative to the number in FY99. Attracting and retaining the highly capable personnel needed to meet our mission in the future is a major issue for the Laboratory. The pool of postdoctoral employees is an essential resource for providing the brightest and best scientists and engineers for the stockpile stewardship effort. Fortunately, the Energy and Water Appropriations Act for FY01 has restored the funding to 6%, and the number of postdoctoral employees at LANL is expected to gradually return to a more beneficial level.

Because of the funding cut, it became necessary to reduce the number of LDRD projects and the funding allocated to ongoing and newly planned projects after the start of FY00. In general, funding for basic science and highly innovative, entrepreneurial projects at national laboratories has been declining. From a strategic perspective, sustaining funding for projects in LANL's LDRD Exploratory Research (ER) component is essential to prevent further erosion of support for basic science at the core of DOE's missions. As a consequence, the reduction in overall LDRD funding at LANL was balanced in favor of the LDRD ER component, at some additional expense to the LDRD Directed Research (DR) component. This strategy is reflected in the change in the relative proportion of the funds in the two components between FY99 and FY00, as illustrated in Fig. 1 a and b.

Fig. 1. These two pie charts are shown together to compare the distribution of (a) FY00 funding with (b) FY99 funding among the two LDRD program components—Exploratory Research and Directed Research.

A breakdown of the LDRD program's projected and actual costs for the years from FY99 to FY03 is shown in Table 1. In FY99, the DOE-approved assessment rate was 6% and the actual Laboratory operating costs were \$1,258 million. In FY00, the assessment rate was 4% of all but Environmental Management Programs funding, and actual laboratory costs were \$1,348 million. A breakdown of the Laboratory's FY00 funding by major program sponsor is shown in Fig. 2.

Table 1. Projected Funding for LDRD (\$M)

Funding Area	Actual Cost	Actual Cost ¹	Projected Cost		
	FY99	FY00	FY01	FY02	FY03
Operating	71.1	47.0	82.0	82.0	82.0
Capital Equipment	2.9	1.3	1.5	1.5	1.5
Total	73.0	48.3	83.5	83.5	83.5

¹Projected amounts for FY02 and beyond are subject to approval in accordance with DOE Order 413.2.

LDRD Program Structure for FY00

The LDRD program structure followed the pattern of the previous year. The program consists of two components with distinct institutional objectives: Directed Research (DR) and Exploratory Research (ER).

The DR component makes long-range investments in moderately large multidisciplinary scientific projects in key competency or technology development areas seen as vital to our long-term ability to execute the Laboratory's missions. This component is directly tied to management's strategic vision for the Laboratory. The formulation of the science and technology strategies for the Laboratory is led and monitored by the Deputy Laboratory Director for Science, Technology, and Programs (DLDSTP) working in close coordination with the three Associate Laboratory Directors (ALDs). The DLDSTP is also responsible for oversight and strategic management of the LDRD program. This makes it easier to align investment of the LDRD resources with the goals and needs outlined in the Laboratory Strategic Plan.

The ER component consists of generally smaller projects with a few investigators. These projects primarily explore highly innovative ideas, often fundamental, in those science and technology disciplines underpinning the Laboratory's programs. The stress is on competency of the Laboratory in key strategic scientific disciplines. For this year, process support and review for these ER projects was available in ten technical categories:

- atomic, molecular, optical, and plasma physics, fluids, and beams;
- bioscience;
- chemistry;
- computer science and software engineering;
- engineering science;
- geoscience, space science, and astrophysics;
- instrumentation and diagnostics;
- materials science;
- mathematics, simulation, and modeling; and
- nuclear and particle physics.

The LDRD program employs a formal management process that imposes accountability in the selection, execution, and documentation of projects. All projects were selected through competitive review by peers and/or scientific management. Innovation and scientific excellence are key selection criteria. All projects were required to be in science and technology areas that support the Laboratory's mission. Decisions on project funding are ultimately the responsibility of the Laboratory Director.

The annual LDRD proposal cycle began in February with a formal call for new proposals for LDRD projects. In the call for new proposals, we provided detailed guidance for each LDRD component. The guidance included estimates of component funding for planning purposes and background on the research and development areas that will be supported. Successful proposals must include an annual statement of work.

New ER proposals were reviewed by one of the ten LDRD technical category teams. Proposals were evaluated and ranked based on scientific and technical merit, creativity and originality of proposed effort, and capability of the team to succeed within the budgetary constraints. Continuing ER proposals were subject to scientific management review and annual review by the relevant ER technical category team. Funding was extended into a subsequent fiscal year if the projects were previously approved for multiyear funding and if adequate progress towards stated objectives was made.

Fig. 2. The percentage breakdown of FY00 funding for major programs at Los Alamos National Laboratory.

The DR component solicited proposals in two phases. The first phase consisted of a broad call for three-page preproposals identifying strategic LDRD investment opportunities that support the Laboratory Strategic Plan. A strategy team chaired by DLDSTP assessed the preproposals. Based on the information submitted in the preproposals, the strategy team recommended to the DLDSTP and the three ALDs the science and technology thrusts for a directed call for full proposals. The DLDSTP and the ALDs made the final decision on the directed call for full proposals. This call was targeted at specific authors and scientific activities and provided a budget target for each proposal. Once the full proposals were received, they were reviewed by the strategy team and ranked on the basis of scientific and strategic merit. The DLDSTP and ALDs used this rank to determine the portfolio of proposals to be funded as DR projects.

Each year the composition of the LDRD portfolio is reviewed and adjustments are made to ensure the best match possible to institutional needs. In addition, as part of the evaluation of the program, we conduct a rather detailed review to evaluate current projects. This year, as a consequence of the Cerro Grande fire and the closure of the Laboratory, the approval process conducted in FY00 for the FY01 portfolio was delayed. As a consequence of the fire, the review schedule was delayed and adapted to an abbreviated schedule.

The Success of LDRD

Los Alamos National Laboratory's core mission is to enhance global security by ensuring safety and confidence in the U.S. nuclear weapons stockpile, developing technical solutions to reduce the threat of weapons of mass destruction, and improving the environmental and nuclear materials legacies of the cold war. LDRD is a vital tool supporting the Laboratory's missions.

The most important contribution that LDRD makes is to develop and apply innovative scientific and technological solutions to the scientific challenges underpinning our mission. LDRD projects tend to be at the leading edge of research at the Laboratory and in the scientific community at large. This preeminence is essential to sustaining LANL as a world-class scientific institution, and hence to sustaining the nuclear deterrent at the core of our missions. This is especially important in this era when testing of nuclear weapons has been suspended, as the LDRD program helps provide clear evidence that LANL retains the necessary scientific and technical expertise to maintain the stockpile.

The success of LDRD in accomplishing this is illustrated by the program output. With only 4% of the Laboratory funding for FY00, LDRD produced a disproportionately high proportion of all refereed Laboratory publications. Through these publications, LDRD creates a strong Los Alamos presence and scientific reputation in the broader scientific community. That visibility and reputation in turn make Los Alamos science and scientists magnets to attract and retain the best talent needed to execute our ongoing mission. The combination of increasing the competency of our people while achieving a deeper understanding of our science and technology clearly will prepare us to execute our core mission better.

The following LDRD successes illustrate just a few of the significant contributions to fundamental science and technology in a range of national security areas.

Fluid Dynamics and Turbulence

Fluid flows in nuclear weapons, ocean circulation, and other real-life applications have features such as transient forcing, strong anisotropy and inhomogeneity, multiphase flow, and coherent structures that make traditional turbulence modeling ineffective. Researchers have developed a new analytical approach, the Navier-Stokes alpha model, for both numerical algorithm development and physical modeling that can naturally incorporate these additional features. By combining a high level of expertise in both theoretical mathematics and physical sciences, the researchers derived results in a nonlinear dispersive system of flow equations to produce this model. The Navier-Stokes alpha model shows promise as a subgrid model for turbulent fluid flows, capturing the important large-scale turbulence features without having to explicitly model or resolve the smaller scales.

In direct numerical simulations, they found that the length scale, designated as alpha, truncates the turbulent cascade without interfering with the fluid motion on scales that are larger than alpha. Thus, the constant parameter alpha in the model defines the boundary between resolved scales and subgrid scales. By comparing direct numerical simulations of fluid turbulence using several values of the parameter alpha (including when alpha equals zero, which is where the original Navier-Stokes equations are recovered), they found that the large-scale features, including statistics and structures, are preserved by the alpha models, even at coarser resolutions. Thus, their model provides an accurate coarse-grained description of the fluid motion at the resolved scales and truncates the subgrid scales.

They also discovered an intriguing connection between the Navier-Stokes alpha model and large-eddy simulation (LES) codes. These LES codes are based on nonoscillatory algorithms and turbulence estimation methods. Such codes have already proved effective at modeling turbulence (e.g., in planetary boundary layers). The truncation analysis of these nonoscillatory algorithms reveals terms that are nearly identical to the nonlinear dispersion terms in the Navier-Stokes alpha model.

This work has a potentially enormous impact on programmatic efforts in modeling turbulence for stockpile stewardship.

Plutonium-Mediated Catalysis

Understanding the chemistry of actinide elements, especially plutonium, is essential to managing weapons processes and to environmental remediation. Plutonium has been observed to degrade organic compounds that it contacts. These organic compounds include processing chemicals, biological molecules, and combustible wastes. The degradation has often been attributed to radiolysis. However, radiation is not kinetically competent to induce all of the changes observed. Literature reports and some preliminary evidence indicate that plutonium may chemically and catalytically induce these degradation reactions. Researchers are working, therefore, to determine which reactions actually occur, how to stop them when they are unwanted, and how to take advantage of them when appropriate.

Recently, through this research, it has been determined that simple plutonium alkoxide compounds are excellent Lewis acid catalysts. Using the Meerwein (MPV) reduction reaction as a test case, researchers determined that Plutonium (III) exceeds the lanthanides in its catalytic ability. Plutonium (IV) does not, however, catalyze the MPV reaction. Neither neptunium (III) or uranium (III) catalyze the MPV reaction either, and their failure mechanisms demonstrate their oxidation potentials. The test reactions validate the concept that the product analysis of simple reactions can provide additional physical information. The MPV reaction is also known to degrade cellulosic materials, so these results are particularly relevant to plutonium-bearing wastes.

As a precursor to extending the work to actinides, the scientists are producing reactions with lanthanide surrogates to test the catalytic efficiency of insoluble metal halide salts. Several lanthanide chlorides have proved to be very active catalysts, thus validating the extra effort required to do similar experiments with actinides.

Quantifying Radiation-Case Performance Measurement

When the primary pit of a thermonuclear weapon is compressed to supercriticality, the radiation that is produced is channeled to the secondary via the radiation case. The radiation-case dynamics affect the radiation transport, and must be known to correctly predict the total device performance. Historically, semiquantitative measurements and qualitative features have been deduced from flash x-ray “case radiographs” of mock nuclear weapons (where the fissile material is replaced with nonfissile material). Research has been directed toward the quantitative inference of the case performance from case radiographs, quantification of the uncertainties on those inferences, and improvement of the experimental design for future case radiographic experiments.

A tool called the Bayes Inference Engine (BIE) was used to make inferences of geometry and mass distribution of the primary pit material for “cavity radiographs.” This research was a first attempt to analyze a case radiograph with the BIE. The BIE combines a number of innovative techniques into a powerful, user-friendly analysis tool.

The BIE allows an analyst to graphically build complex parametrized models of the geometry and mass distribution of all the components of a hydrodynamically driven mock nuclear weapon. This “object model” is then propagated through a radiographic chain model, also graphically constructed by the analyst. The radiographic chain model predicts the noiseless radiograph that would be observed given the parameter values of the object model. The likelihood of getting the real radiographic data, given that the radiograph predicted by the object and radiographic chain models is true, is computed and iteratively maximized over the parameter values of the object and/or radiographic chain models. Ultimately, the parameter values that yield the maximum likelihood of the real radiographic data are obtained through this process. *A priori* information about the object or radiograph chain can also be included in the analysis. The probabilistic framework used by the BIE allows the analyst to generate *a posteriori* credible intervals on the estimated parameter values, or even to choose one model over another by computing the evidence for the competing models. The BIE has been used in classified analyses of cavity radiographs to produce results with unprecedented resolution recovery and noise suppression due to the fact that the degrading effects of the radiographic chain are included in the forward model, and can therefore be eliminated (to some extent) from the estimates of geometry and mass distribution.

Unfortunately, radiographic data can suffer from a number of systematic uncertainties, including an unknown photon source spectrum, spot size and intensity profile, detector resolution, background, and sensitivity, and from scattered radiation background. The approach to quantifying the uncertainty in the analysis of the dynamic radiographic data was to analyze a static radiograph of the mock nuclear device taken shortly before the dynamic radiograph was taken, where the object geometry and mass distribution are perfectly known. The errors in analyzing this dataset, using the same radiographic chain model as for the analysis of the dynamic radiographic data, was then be used to determine errors in the analysis of the dynamic data.

This research enables us to quantify and limit the uncertainties we face in one component of a weapons system. Such research is typical of the activities that are important during a time when actual testing is not permitted.

¹Prepared statement submitted to the Military Procurement Subcommittee of the Committee on Armed Services
United States House of Representatives, March 21, 2000

²Public Law 104–201

³Public Law 101–510

⁴Section 308 (Public Law 106–60)

LDRD

Directed Research Projects
2000

Atomic, Molecular, Optical, and Plasma Physics, Fluids, and Beams

Applications of Quantum Technologies

99505

David J. Vieira

The main goal of this project is to apply the latest technologies in laser and trapping to control, manipulate, and detect the quantum states of atomic and photonic systems. Recent advances have made it possible to (1) produce nonclassical two-photon states; (2) use lasers to cool atoms or ions to their quantum mechanical ground states; (3) detect selected species at extremely low levels; and (4) optically manipulate and detect the quantum states of these selected species. These breakthrough technologies have opened up a wide range of cutting-edge research important to the Laboratory in three main areas: basic science; quantum information and information assurance; and nonproliferation and international security. Due to the brevity of this summary, we highlight only two of the seven areas that we are working on under this project.

A part of our research involves the development of a robust source of entangled photons that may then be used as a tool for producing and relaying quantum information. Previously, we have demonstrated a novel method of producing pairs of polarization-entangled photons using the down conversion of laser light passing through two adjacent nonlinear crystals. This source has been used to study quantum cryptography, quantum tomography, and entanglement distillation. During these investigations, we discovered a previously unknown effect involving the coupling of phase to emission direction. This effect arises from the complex dependence of birefringence on propagation direction in a birefringent crystal. This results in an angularly varying phase $[\phi(\theta)]$ between the terms of horizontal-horizontal (HH) and vertical-vertical (VV) polarization constructing the entangled state, leading to $|HH\rangle + e^{i\phi(\theta)}|VV\rangle$. Using large collection irises causes an averaging over phase that degrades the observed entanglement.

As part of this project, we investigated one method of eliminating this undesirable phase averaging. Specifically, using an appropriate compensating crystal (similar to the

crystals used in the source itself), we demonstrated an order of magnitude reduction in the variation of phase with emission angle. This in turn allows us to use significantly larger collection irises, and hence implies a substantially higher production rate of entangled photon pairs (see Fig. 1). If one could completely compensate the phase for *all* pairs of emitted photons, the resulting source would be more than 100 times brighter than the current one, which is already 10 times brighter than the best previous source of polarization-entangled photons.

The second part of our project on which we report is our research using optical traps. The capabilities of optical traps include many features desirable for ultrasensitive detection. These include the optical trap's high selectivity, high sensitivity, and large dynamic range. Building on the work that we have already done in the trapping of rubidium-82, we have recently demonstrated the first reported magneto-optical trapping of cesium-135 (half-life = 2 Myr) and cesium-137 (half-life = 30 yr), which are of interest to nonproliferation and environmental concerns. Moreover, by measuring cesium-135 and cesium-137 in sequence, we have been able to perform the first isotopic ratio measurement of cesium atoms in an optical trap. By averaging five measurements involving a trapped cloud of $\sim 20,000$ atoms for each species, we have determined the isotopic ratio to an accuracy of 30%. More recently we have extended these measurements down to the 1,000-atom level and proven that this new method is linear over more than two orders of magnitude (see Fig. 2). At the 1,000-atom level this corresponds to a sample size of $\sim 10^7$ atoms, which is an order of magnitude better than existing techniques. Further improvement should allow us to extend this method down to 10^6 atoms per sample level.

Publications

Crane, S.G., et al., "Parity Violation Observed in the Beta Decay of Magnetically Trapped ^{82}Rb Atoms" (to be published in *Phys. Rev. Lett.*).

Crane, S.G., et al., "Trapping an Isotopic Mixture of Fermionic ^{84}Rb and Bosonic ^{87}Rb Atoms," *Phys. Rev. A* **62**, 011402(R) (2000).

Vieira, D.J., et al., "Trapping Radioactive Atoms for Basic and Applied Research," *Hyperfine Inter.* **127**, 387 (2000).

Fig. 1. Results showing the benefit of including a compensation crystal after the down-conversion source. Without compensation, the visibility (and hence the purity of the collected state) degrades as the collection irises are opened; with compensation, the purity remains high.

Fig. 2. Linearity test using a magneto-optical trap (MOT) for the detection of cesium-135 (blue circles) and cesium-137 (red circles). Vertical axis is the number of cesium atoms determined from the MOT fluorescence signal; horizontal axis is the number of cesium ions implanted into the accumulation (source) foil as determined from an integrated-current measurement. The solid line indicates a linear fit with a forced zero intercept; the dash line is a linear with a fitted (free) intercept.

High Power Microwave Science and Technology

99522

Michael V. Fazio

This project responds to the ever-increasing susceptibility of military and civilian electronics to disruption and destruction by high power microwaves (HPM) as a result of their increasing sophistication, miniaturization, and exponential proliferation. HPM weapons function by coupling electromagnetic energy down to the electronic component level of the target systems, causing burnout or upset. HPM weapon technology is needed for the functional kill of hostile weapons platforms, for the defeat of hard and deeply buried targets, for disruption and denial of adversaries' command and control systems, and for self-protection of our own weapon platforms.

The goal of the project is to design and experimentally test an advanced HPM source, the annular beam klystron (ABK), at the 1 gigawatt and 1 kilojoule per pulse output level which is high enough to be operationally interesting for DoD applications and is more than a factor of ten beyond anything commercially available today. This year's tasks are: high power electron gun design, RF circuit design and modeling, and mechanical design and fabrication of the beamstick assembly that includes the electron gun, two RF cavities, and beam collector. The Banshee pulsed power modulator needed to power the ABK is being upgraded to a 5-Hz pulse repetition frequency and single pulse testing is underway.

This thermionic electron gun, at 800,000 volts and 4,000 amperes is a factor of ten higher in power than conventional thermionic gun technology. The novel electron gun and beamstick (see the figure) has been designed, components procured, and fabrication is underway.

The RF circuit design has focused on writing a specialized particle-in-cell code for klystron modeling needed to model the bunching of the intense electron beam through the ABK. This code is complete and we are using it to perform the RF design. The DOE high-energy physics accelerator community has already requested this code for designing linear collider high power RF sources.

If we are even moderately successful with the ABK we should have a major impact on the progress being made by the DoD HPM community. We will have validated a major paradigm shift in the design of gigawatt-class HPM sources.

Publications

Fazio, M., et al., "Design for a One-Gigawatt, Annular Beam Klystron" (*Proc. XX International Linear Accelerator Conference*, Monterey, CA, August 2000).

The annular beam klystron beamstick assembly includes the high power thermionic electron gun, two RF cavities to initiate electron beam bunching, a section of drift tube (that in the complete ABK will include several more RF cavities for higher gain and the output cavity), and the beam collector.

Next-Generation Sophistication in Defense and High-Energy-Density Physics Exploratory Research

99524

Carter Munson

The major goal of this project is to help address well defined physics and data needs of the Nuclear Weapons program through the development of advanced experimental measurement capabilities, experimental measurements of dynamic materials properties, and associated theoretical and computational designs intended to maximize the physics return of the Atlas facility. Focus areas include the development of capabilities for conducting strongly-coupled plasma (SCP) hydrodynamics experiments and the characterization of phase transitions in a dynamic environment. The program encompasses the development of an SCP target, laser-driven, shock-based measurement of the equation of state (EOS) properties of an SCP, the comparison of experimental data with currently proposed SCP theories, the utilization of dynamic melt diagnostic techniques which have been developed for probing material surfaces, and the evaluation of other advanced diagnostic techniques, such as neutron resonance and photoelectron spectroscopy, for application to dynamic experiments.

During the past year, we have performed extensive optical measurements of the dynamic melting characteristics of metals. By observing the temporal response of the dielectric constant and second harmonic generation to ultrashort laser pulses incident on metallic surfaces, we have monitored heat-induced structural deformations and phase transitions. Dielectric constant measurements indicate that the heat-induced structural deformations and phase transitions in metals are tied to electronic disorder and band structure collapse, whereas fundamental/second harmonic measurements indicate a disordered lattice due to electronic heating, and suggest that a nonthermal component exists in the heat-induced structural deformation and phase transition in gold. This work has resulted in a number of publications and in a significant increase in our understanding of the detailed physics of phase transitions in metals.

In the SCP EOS, we have obtained initial images of the SCP plume using the x-ray microscope (which is necessary to obtain the required spatial resolution for determining shock propagation velocities and, hence, SCP EOS information). We are currently optimizing the x-ray microscope for optical throughput, and we are repairing portions of the shock generation and x-ray backlighter laser systems.

We have performed initial SCP target preparation experiments using a cylindrical target geometry in the Colt facility, and we are analyzing data from these experiments. In addition, we have continued evaluation and construction work on the CHAMP system as a possible relatively compact, intense source of pulsed neutrons for neutron resonance spectroscopic measurements in dynamic experiments.

Publications

Guo, C., et al., "Direct Observation of Ultrafast Thermalization Dynamics in Metals," (submitted to *Phys. Rev. Lett.*).

Guo, C., et al., "Structural Phase Transition of Aluminum Induced by Electronic Excitation," *Phys. Rev. Lett.* **84**, 4493 (2000).

Guo, C., and A.J. Taylor, "Breaking Metals Using Ultrafast Optical Excitation," *Opt. & Photonics News* (in press, December 2000).

Guo, C., and A.J. Taylor, "Nonthermal Component in Heat-Induced Structural Deformation and Phase Transition in Gold," *Phys. Rev. B* **62**, 921 (2000).

Guo, C., and A.J. Taylor, "Ultrafast Dynamics of Thermal and Nonthermal Structural Changes in Metals," *Int. J. of Modern Physics* **14** (in press, 2000).

Guo, C., and A.J. Taylor, "Ultrafast Electronic Disorder in Heat-Induced Structural Deformations and Phase Transitions in Metals," *Phys. Rev. B.* **62**, 5382 (2000).

Fig. 1. Real and imaginary components of the dielectric constant of silver as a function of laser intensity at time delays of 0.2 ps and 5 ps after the pump pulse. Results indicate that heat-induced structural deformations and phase transitions in metals are tied to electronic disorder and band-structure collapse.

Fig. 2. Time-resolved fundamental and surface second harmonic generation (SHG) signals for Au. At early (<0.2 ps) and late (>1 ps) times, theoretical models fit both fundamental and SHG (Sipe, et al., 1987). In this treatment the SHG fit considers only the Fresnel factors.

Ultrafast Time-Resolved Atomic Probes of Strategic Materials

2000512

Antoinette J. Taylor

Controlling functionality in electronic materials is essential to address strategic national needs for materials. The key to controlling material functionality is understanding structure-function relationships in complex materials on atomic length and time scales. Such spatially and temporally local probes do not currently exist. The objective of this project is to develop complementary probes (optical, electronic, magnetic) by combining ultrafast optical techniques with microscopies, and to use these probes to study electronic processes with fs temporal and nm spatial resolution. Combining these approaches will result in a unique capability at the frontiers of materials science, to simultaneously probe at ultrashort length and time scales across a range of hard-soft strategic materials (organic, inorganic, and biological). This work will strengthen the Laboratory's core competencies in complex experimentation, as well as in nuclear and advanced materials.

In the area of probes development we characterized our fs scanning tunneling microscope (STM) in a polarization-gating geometry with a low-temperature-grown gallium arsenide (GaAs) tip, demonstrating simultaneous 2-ps and 20-nm resolution. Dynamical studies following photoexcitation in InGaAs/GaAs quantum dots using the fs-STM reveal a slower relaxation time within the dots than on the substrate because of confinement effects.

A terahertz (THz) imaging capability has been designed and is being assembled. We have recorded the THz spectra of mock explosive materials. We are also developing a fs near-field scanning optical microscope capability by combining a commercially available atomic force microscope and inverted optical microscope that will provide sub-10-nm spatial resolution.

Portable confocal optical microscopy instrumentation that can be easily interfaced with ultrafast lasers is being developed. Far-field fs optical Kerr pump/probe instrumentation is being set up as the first step toward studying local magnetization dynamics in materials.

We are also developing the theoretical framework to calculate from first principles the dynamical processes studied in ultrafast pump-probe experiments. We are investigating how the kinetic energy given optically to an electron is transferred to the phonon subsystem. We have calculated how a bare electron interacts with phonons by integrating the time-dependent, many-body Schrödinger equation in real space and time.

Publications

Averitt, R.D., et al., "Conductivity Artifacts in Optical-Pump THz Probe Measurements in $\text{YBa}_2\text{Cu}_3\text{O}_7$," *J. Opt. Soc. Am. B* **17**, 327 (2000).

Averitt, R.D., et al., "Ultrafast Conductivity Dynamics in Colossal Magnetoresistance Manganites" (submitted to *Phys. Rev. Lett.*).

Bonca, J., and S.A. Trugman, "Frolich Bipolaron" (submitted to *Phys. Rev. Lett.*).

Bonca, J., and S.A. Trugman, "Mobile Bipolaron—Strong Coupling Approach," *J. Supercond.* **13**, 999 (2000).

Bonca, J., et al., "The Mobile Bipolaron," *Phys. Rev. Lett.* **84**, 3153 (2000).

Donati, G.P., et al., "Ultrafast Dynamically Imaged Surfaces Using a Scanning Tunneling Microscope with a Photoexcited, Low-Temperature-Grown GaAs Tip," *J. Opt. Soc. Am. B* **17**, 1077 (2000).

Klimov, V., "Optical Nonlinearities and Ultrafast Carrier Dynamics in Semiconductor Nanocrystals," *J. Chem. Phys. B* **104**, 6112 (2000).

Klimov, V., et al., "Optical Gain and Stimulated Emission in Nanocrystal Quantum Dots," *Science* **290**, 314 (2000).

Klimov, V., et al., "Mechanisms for Intraband Energy Relaxation in Semiconductor Quantum Dots: The Role of Electron-Hole Interactions," *Phys. Rev. B* **61**, R13349 (2000).

Klimov, V., et al., "Quantization of Multi-Particle Auger Rates in Semiconductor Quantum Dots," *Science* **287**, 1011 (2000).

Kraabel, B., et al., "Ultrafast Dynamical Holography in Nanocrystal Solids" (*Appl. Phys. Lett.*, in press).

Kraabel, B., et al., "A Unified Picture of the Photoexcitations in Phenyl-Based Conjugated Polymers: Universal Spectral and Dynamical Features in Subpicosecond Transient Absorption," *Phys. Rev. B* **61**, 8501 (2000).

Lobad, A.I., and A.J. Taylor, "On the Coherent Control of Photo-Induced Phonons in Solids" (submitted to *Phys. Rev. B*).

Mikhailovsky, A., et al., "Femtosecond Intraband Reexcitation Spectroscopy" (submitted to *Opt. Lett.*).

Raghavan, S., et al., "Dynamic Localization in Spin Systems," *Phys. Rev. B* **61**, 5864 (2000).

Thorsmolle, V.K., et al., "C-axis Josephson Plasma Resonance Observed in $\text{Ti}_2\text{Ba}_2\text{CaCu}_2\text{O}_8$ Superconducting Thin Films Using Terahertz Time-Domain Spectroscopy" (*Opt. Lett.*, in press).

Tretiak, S., et al., "CEO/Semiempirical Calculations of Static Nonlinear Polarizabilities in Conjugated Molecules" (*J. Chem. Phys.*, in press).

Tretiak, S., et al., "CEO/Semiempirical Calculations of UV-Vis Spectra in Conjugated Molecules," *Chem. Phys. Lett.* **331**, 561 (2000).

Tretiak, S., et al., "Interchain Electronic Excitations in Poly-Phenylenevinylene Aggregates," *J. Phys. Chem. B* **104**, 7029 (2000).

Van Patten, P.G., et al., "Structural and Photophysical Properties of a Water-Soluble Porphyrin Associated with Polycations in Solution and Electrostatically-Assembled Ultrathin Films," *J. Phys. Chem. B* **104**, 5986 (2000).

Weisse, A., et al., "Optimized Phonon Approach for the Diagonalization of Electron-Phonon Problems," *Phys. Rev. B: Rapid Commun. B* **62**, R747 (2000).

Xu, S., et al., "Femtosecond Transient Absorption Study of Oriented poly(9,9-Dioctylfluorene) Films: Hot Excitons, Thermalized Excitons and Charge Transfer Species" (*Phys. Rev. B* , in press).

Yarotsky, D., et al., "Picosecond Carrier Dynamics In Self-Assembled InGaAs/GaAs Quantum Dots" (submitted to *J. Opt. Soc. Am. B*).

SDSS Photometry and Controls

2000601

Bryan E. Laubscher

The Sloan Digital Sky Survey (SDSS) endeavors to map one quarter of the sky (the North Galactic Cap) to a depth not previously achieved. A number of research institutions are collaborating on this ambitious project at Apache Point Observatory, near Sunspot, New Mexico. For this project Los Alamos researchers are informally collaborating with SDSS on engineering and observational research to support the survey data acquisition and on astronomical research using that acquired data.

This year the primary achievement of the SDSS was the commencement of survey operations. We contributed to this effort in several ways. We built the SDSS standard star system through observation with the photometry telescope and engineered the photometry telescope for improved data quality. We also assisted with the data reduction process to ensure that proper standard star processing procedures would be used. Finally, we executed imaging and spectroscopic observations with the 2.5-meter telescope and developed the Telescope Performance Monitor, a software program that provides observers with necessary diagnostic information about the telescope's performance.

Using the SDSS data, we have begun conducting astronomical research on topics that include T Tauri stars, galaxy clustering properties and evolution, extremely red stars, and transient phenomena in astronomy.

Bioscience

Bioremediation Science to Meet National Challenges

99500

James R. Brainard

Because of its ability to remediate, dilute, and diffuse inaccessible contaminants cost effectively, in situ bioremediation offers the potential of solving the most difficult of environmental legacies of the Cold War—the remediation of contaminated aquifers. However, the persistence of many contaminants in the environment is evidence that microorganisms are not naturally adapted to degrade these contaminants either at the rates required or to the extents required. Numerous and diverse microorganisms contain enzymes that have limited abilities to transform pollutants, but the affinity of these enzymes for many of the most dangerous pollutants is poor, the turnover rates are slow, and many of the enzymes are product inhibited. These suboptimal catalytic properties are directly responsible for the most serious and fundamental limitation of bioremediation: difficulties in meeting the desired regulatory levels.

In addition, as various bioremediation approaches have been applied at field scale, it has become apparent that knowledge about bioremediation derived from laboratory studies does not always apply. One of the largest contributors to this problem is the fact that most (estimates range from 90% to >99%) of the microorganisms present in the environment have thus far resisted attempts to culture them in the laboratory. Consequently, present bioremediation strategies are based on understanding derived from an infinitesimal fraction of the total microbial population.

Our first goal was to build and demonstrate competency in bioremediation science by understanding the catalytic mechanisms that some important dehalogenase enzymes use, thus enabling protein engineering of those enzymes for improved catalytic properties. The second goal was to develop and apply molecularly based tools for assessing microbial communities in natural environments.

Last year we solved the structure of a *Rhodococcus* dehalogenase and performed kinetic studies comparing the functional properties of the *Rhodococcus* dehalogenase with those of an homologous enzyme from *Xanthobacter*. This year we have introduced several site-specific mutations into the *Xanthobacter* enzyme designed to combine the desirable lack of halide product inhibition of the *Rhodococcus* enzyme with the desirable substrate specificity and activity of the *Xanthobacter* enzyme.

Publications

Chang, C.H., et al., "In vivo Screening of Haloalkane dehalogenase Mutants," *Bioorg. Med. Chem.* **7**(10), 2175 (1999).

Dunbar, J., et al., "Assessment of Microbial Diversity in Four Southwestern United States Soils by 16S rRNA Gene Terminal Restriction Fragment Analysis," *Appl. Environ. Microbiol.* **66**(7), 2943 (2000).

Dunbar, J., et al., "Levels of Bacterial Community Diversity in Four Arid Soils compared by Cultivation and 16S rRNA Gene Cloning," *Appl. Environ. Microbiol.* **65**(4), 1662 (1999).

Dunbar, J., et al., "Phylogenetic Specificity and Reproducibility and New Method for Analysis of Terminal Restriction Fragment Profiles of 16S rRNA Genes from Bacterial Communities," *Appl. Environ. Microbiol.* **67**(1), 190 (2001).

Franzen, S., et al., "Resonance Raman Studies of Heme Axial Ligation in H93G Myoglobin," *J. Phys. Chem. B* **104**(44), 10359 (2000).

Newman, J., et al., "Haloalkane dehalogenases: Structure of a *Rhodococcus* Enzyme," *Biochem.* **38**, 16105 (1999).

Optical Biosensors

99506

Basil I. Swanson

The objective of this project is to develop a biosensor platform that is based on lessons from nature and that can be used for the environmental detection of protein toxins. The heart of the sensor is the target of protein toxins—receptor molecules that decorate a cell membrane surface. We mimic cell signaling in nature by directly coupling recognition between receptors and protein toxins with amplified signal transduction to give high sensitivity and specificity. Our research is aimed at developing an in-depth understanding of the underlying science of optical sensors based on protein-receptor binding, cell membrane mimics, and receptor aggregation that is triggered by protein-receptor recognition.

This work contributes to the Laboratory and DOE mission to reduce the threat of biological agents by laying the foundation for the development of a rugged, “miniaturizable” sensor system that can be used for the early detection of terrorist use of protein toxins. Although the primary objective is a hand-held sensor that can be used in the field for detecting toxins, the same platform could be adapted for use in a doctor’s office to aid in rapidly diagnosing infection.

Our approach is to integrate research in (1) preparing and characterizing biomimetic materials, (2) synthesizing natural receptor molecules, (3) measuring proximity-based fluorescence changes used in signal transduction, and (4) modeling the kinetics of binding to optimize the sensor platform for detecting protein toxins. We have characterized the transport, binding, and aggregation of cholera toxin with its receptor; developed a fluorescence recovery after photobleaching (FRAP) experiment to characterize the lateral mobility in membranes; and developed an experiment to image biomimetic membranes on waveguide substrates.

In the past year we also modeled the sensitivity of our biosensor and compared the theory to experimental results and to laboratory-based sandwich assays. To study the energy transfer process induced by multivalent protein binding, we used time-resolved techniques. We also adapted the optical biosensor platform to flow cytometry and optimized several parameters of the system for cholera toxin detection. To minimize background fluorescence, we developed a two-tiered energy transfer scheme. We also synthesized a generic linker molecule based on lysine to

anchor receptor molecules to fluid biomimetic membranes, synthesized receptor molecules for the detection of ricin, and used scanning probe microscopy to image the aggregation of cholera in a fluid biomimetic membrane upon binding.

Publications

Bardeau, J.F., et al., “Phase Transition Based Transduction in a Biosensor,” *Synth. Met.* **102** (1–3), 1452 (1999).

Clark, T. Jr., et al., “A New Application of UV-Ozone Treatment in the Preparation of Substrate-Supported Mesoporous Thin Films,” *Chem. Mater.* **12** (12), 3879 (2000).

Kelly, D., et al., “Integrated Optical Biosensor for Detection of Multivalent Proteins,” *Opt. Lett.* **24**(23), 1723 (1999).

Nyquist, R.M., et al., “Characterization of Self-Assembled Monolayers for Biosensor Applications,” *Langmuir* **16**(4), 1793 (2000).

Song, X., et al., “Detection of Multivalent Interactions Through Two-Tiered Energy Transfer” (*Anal. Biochem.*, in press).

Song, X., et al., “Flow Cytometry-Based Biosensor for the Detection of Multivalent Proteins,” *Anal. Biochem.* **284**, 35 (2000).

Wang, R., et al., “Non-Equilibrium Pattern Formation in Langmuir Assisted Assembly of Alkylsiloxane Monolayers,” *Phys. Chem. B.* **103**(46), 10149 (1999).

Pathogen Detection in the Real World

99516

Babetta Marrone

The purpose of this project is to develop an inline sample concentrator for biological particles to be used in conjunction with detection analyzers such as flow cytometers.

Flow cytometry, pioneered at Los Alamos, rapidly analyzes biological particles. Biological particles (bacteria, blood cells, and chromosomes, for example) are detected and measured one at a time as they flow through a fluid-filled sensing chamber. We have focused on developing an acoustic sample concentrator, which can concentrate samples up to several orders of magnitude. Such a device can significantly increase the sample throughput rate and subsequently the data collection rate. The acoustic concentrator will enhance the throughput rate for any flow cytometer that is analyzing low-concentration samples. For example, higher sample throughput will allow earlier detection of low concentrations of biological agents. This innovation will find immediate use in the national security arena, enhancing early warning of a biological attack by existing U.S. Army battlefield-based flow cytometers.

We have primarily addressed the development of a simple device for concentrating and transporting small particles in a fluid stream. Over the course of the project, we built and tested several acoustic concentration devices for decreasing sizes and concentrations of particles.

Figure 1 displays the interior of the acoustic chamber of one of the devices. As the acoustic pressure within the cavity is increased, particles migrate toward the center of the cavity. Figure 2 displays the same chamber shortly after the acoustic disturbance in the chamber has reached a resonance condition. The particles have migrated toward a line in the chamber and are concentrated into a fine stream on the order of 30 μm in diam. In this example the particle concentration is 50 times greater than when the acoustic power is turned off.

In summary we have constructed and tested a system for concentrating a flowing suspension of particles into an axial-focused sample stream using acoustic pressure forces that are orthogonal to the flow direction. While the developmental testing of the concentrator used polystyrene microspheres, we have also demonstrated the acoustic focusing of bacteria.

Fig. 1. A host of 10- μ m-diam polystyrene microspheres is seen flowing in random locations in the acoustic chamber with the power off. This image shows a 270- μ m-wide central view of the 1.5-mm-wide flow channel. The flow is from top to bottom. The average flow velocity for this experiment is approximately 1.0 cm/min.

Fig. 2. The same sample of microspheres and flow conditions as in Fig. 2, but with the acoustic power on. The particles have migrated to the center of the chamber, forming a stream that is approximately 30 μm wide.

Functional Genomics

99518

Michael Altherr

This project integrates technology development and research to advance the fields of functional and structural genomics into the next millennium. In this context, functional genomics is a collection of activities, procedures, and processes to rapidly produce information and resources for the characterization of unknown genetic elements. Emphasis is phased to take advantage of technologies that will translate DNA sequence data into biologically relevant data without regard to species of origin; this data will serve needs ranging from bioterrorism threat reduction to understanding the cellular effects of low-dose ionizing radiation.

This year we have established an experimental infrastructure for global gene expression studies, and we participated in the establishment of a mass spectrometry resource. We developed the capability for sequencing full-length cDNAs. We have established a broad cross disciplinary computational sciences group that has created a major data resource for global gene expression data and has created novel algorithm applications for the analysis of these data. We established collaborations with external data generators and have provided the infrastructure to take advantage of externally generated data.

This project has facilitated the expansion of computational biology to the high-performance computers at the Laboratory. We established a number of external collaborations based on the recognition of the quality of our schema for the global gene expression database and our emerging “in-silico” analytical capabilities. We will continue to lead in the development of the gene expression database to facilitate our in-house efforts and to attract additional external data streams; these capabilities will enable the Laboratory to warehouse enormous amounts of gene expression data from multiple locations for a variety of different experimental models. Furthermore, we will continue to work on developing novel and robust analytical tools to identify trends and significant biological features in these complex data sets. Computer scientists at the Laboratory with experience in modeling complex phenomenon can use this data repository to conduct higher level “meta” analyses on these distinctly generated, apparently disparate, data sets.

The Identification of Proteins That Bind to Novel DNA Sequences/Structures

99529

E. M. Bradbury

We are studying the analysis by mass spectrometry (MS) of chromosomal proteins involved in the cell's response to low-dose ionizing radiation (IR).

Over this past year, the Bioscience Division has spent much effort to set up an MS capability. The PE Biosystems Voyager™ MALDI TOF and Finnegan Electrospray mass spectrometers have been installed. The facility is currently being expanded to include a Genomics Solutions data workstation and software for the analysis of two-dimensional (2-D) protein gels from polyacrylamide gel electrophoresis (PAGE) of proteins and a Genomics Solutions™ Investigator™ ProPic™ robot for excising protein spots that change in response to low-dose IR.

In parallel with these studies, other funded efforts are directed to incorporating stable isotopes in proteins to mass-tag proteolytic peptides for use in database searches to identify both chemically modified proteins and differentially expressed proteins. We have irradiated yeast (*Saccharomyces cerevisiae*) and are irradiating human skin fibroblasts. We have confirmed that low-dose IR phosphorylates an unusual chromosomal protein histone, H2AX, within 1 min of the induction of DNA double-strand breaks.

A major question arising from this observation is the identification of other histones and chromosomal proteins that form complexes with H2AX. We will use antibodies specific for H2AX and for phosphorylated H2 to immunoprecipitate H2AX protein complexes and phosphorylated H2AX protein complexes. We will separate these protein complexes by 2-D PAGE, excise protein spots, and proteolyse the protein for analysis by MS.

A longer-term objective of this project is to isolate functional subcomponents or chromosomes to determine whether particular gene families are associated with specific chromosomal proteins and/or chemically modified proteins; i.e., we will perform a functional genomics study of eukaryotic chromosomes.

Publications

Chen, Xian, et al., "Site-Specific Mass Tagging with Stable Isotopes in Proteins for Accurate and Efficient Protein Identification," *Anal. Chem.* **72**, 1134 (2000).

Host-Pathogen Interactions

2000516

Goutam Gupta

Bacterial and viral pathogens pose an increasing threat in our world today. With the emergence of recently discovered vancomycin-resistant strains of *Staphylococcus*, we are beginning to witness a new era of emerging pathogens. In addition, the looming threat of biowarfare development from rogue countries and terrorist organizations further exacerbates the problem of evolving pathogens. Therefore, in the area of biological research, a primary mission is to accurately elucidate the pathogenic machinery conferring virulence to these organisms. Only by way of a thorough understanding of pathogenic mechanisms will we be able to (1) design robust biosensors for early detection of pathogens (our first line of defense) and (2) develop mechanistically based pathogen countermeasures.

Once a target cell is encountered, a pathogen can cause permanent damage to the host through both direct and indirect multistep processes. A pathogen, for example, can first bind to a given type of host cell through specific receptors on the cell surface. It then enters the host cell and proliferates at the expense of the host machinery. On the other hand, some pathogens release toxic proteins that kill host cells by disrupting critical metabolic and immunogenic pathways.

This year we primarily focused our research on two classes of bacterial toxins: (1) *Staphylococcus enterotoxin* (SE) superantigens such as SEA, SEB, etc., and (2) the protective antigen (PA) from *Bacillus anthracis*. Toxins released from bacteria are primary causative agents or mediators of many bacterial pathogenesis. For both SE and PA, the binding of the toxin to specific receptors on the surface of the host immune cells defines the first step in pathogenesis. We first analyzed the structural components involved in the toxin-receptor interactions. Based upon this knowledge, we designed, by a structure-based approach, a new class of protein ligands, called the bi-specific ligands, that bind to two different surface epitopes on SE or PA. Synergistic binding of these ligands to two different sites of the toxin produces high affinity and high specificity. Figure 1 illustrates the design of a human DR α -linker-TCRV β chimera. Figure 2 illustrates the creation of a bi-specific ligand targeted against PA.

Biological assays reveal that the bi-specific protein ligands do, indeed, block SE- or PA-induced pathogenesis of human immune cells by preventing the binding of toxins to their receptors. This nonantibody-based pathogen countermeasure strategy can easily be extended to any toxins (such as *Botulinum* toxin, *Cholera* toxin, etc.) that pose threat to human health and safety.

Publications

Lehnert, N.M., et al; "Structure-Based Design Of A Bi-Specific Receptor Mimic That Inhibits T Cell Responses to a Superantigen" (*Biochem.*, in press).

Fig. 1. Structure-based design of a bi-specific chimera, DRA-linker-TCRVb, that blocks the pathogenesis of Staphylococcus enterotoxin B (SEB) superantigen. We have adopted (GSTAPPA)₂ as the linker sequence because it supports synergistic binding of DRA and TCRVb to SEB and thereby makes DRA-(GSTAPPA)₂-TCRVb as effective an SEB-binder as the native MHC class II-T cell receptor complex. Finally, we show that DRA-(GSTAPPA)₂-TCRVb inhibits SEB-induced IL-2 release and T cell proliferation at nanomolar concentrations. Here, a representative low-energy model of the DRA-(GSTAPPA)₂-TCRVb is shown. Different structural elements are color coded: DRA=cyan, TCRVb=blue, Linker=red, and SEB=green and magenta. DRA and TCRVb make contacts on the same side of SEB but with different surface epitopes (shown in magenta).

Fig. 2. Design of a bi-specific ligand targeted against PA. Two single-chain antibodies (scFv1 and scFv4) are joined by the linker sequence GSTAPPAGSTAPPA (shown in red with a black arrow). ScFv4 binds to the cell binding epitope on PA, whereas scFv1 binds to a different epitope on PA (shown in green with two epitopes as red loops).

Molecular Foundations of the Host-Pathogen Interface

2000517

Michael Altherr

These studies are directed at reducing the threat from biological agents by addressing one of the major biological challenges of our time, the host-pathogen interface. Our objective is to create novel databases and integrated computational tools to support functional genomic investigations of interaction between pathogens and human cells. Several key technologies have emerged that allow the analysis of the entire transcriptional component (the transcriptome) and the translational component (the proteome) of a cell. The knowledge gained from these studies is being used to disrupt key events in pathogenesis, in order to ameliorate the consequences of exposure to pathogenic organisms and to aid in the development of effective vaccines and small molecule therapeutics.

Work on this project is divided into four focused areas. These are host cell biology, informatics, pathogen biology, and host/pathogen proteomics.

In the area of pathogen biology, we have employed ORF (open reading frame) prediction algorithms to identify putative genes in the genome of *Bacillus anthracis*. With this information we generated array target elements for interrogation with RNA derived from strains of *B. anthracis*. We have successfully isolated mRNA from the *B. anthracis* Sterne strain (an attenuated variant).

In host cell biology, we have successfully cultured human macrophages (the *B. anthracis* host cell model).

In our proteomics group, we have initiated capillary electrophoresis studies as a “front-end” to high-throughput mass spectrometry.

Finally, our greatest accomplishments in this first year were in the information technology arena. We have established a laboratory information management system (LIMS) for two process areas: (1) primer generation for *B. anthracis* genomic DNA, and (2) PCR (polymerase chain reaction) amplification of microarray targets. In addition, we have worked to interface the LIMS with a completed prototype of the Gene Expression Database (Xbase). We have also developed singular value decomposition (SVD) and support vector machine methods for clustering and classification of gene expression data.

Sensitive and Rapid Detection of Diagnostically Important Proteins

2000518

Andrew P. Shreve

The goal of this one-year project was to demonstrate how techniques previously developed at Los Alamos for the sensitive and rapid detection of protein toxins can be extended to more general protein detection problems. The approach has been to develop an artificial membrane-bound receptor, which links three independent chemical entities: a hydrophobic membrane anchor, a fluorescent dye molecule, and a variable recognition unit. The recognition unit can be either an antibody or a small organic ligand. This synthetic receptor molecule will be adaptable to any protein detection problem for which either multiple epitope antibodies or multiply bound molecular ligands are available, and is designed to replace the natural glycolipid receptors that are used in the previously developed protein toxin detector. The demonstration of how to extend existing current sensor capabilities and open up new targets for sensitive and rapid detection is expected to provide significant new programmatic opportunities related to the early diagnosis of diseases and to the assessment of treatment efficacy.

We developed and isolated antibodies that recognize and bind to different epitopes of selected target proteins. To allow coupling of any recognition molecule, including single-chain antibody units, to a membrane anchor and a fluorescent tag, we synthesized a generalized trifunctional receptor molecule. We also performed the initial characterization of the membrane-forming capacity and solubilities of the generalized receptor molecule.

These results of our work have (1) placed us in a position to demonstrate sensing capability for wide ranges of target proteins using transduction methods based on fluorescence resonance energy transfer and (2) laid the groundwork for both the National Institutes of Health and DOE proposals that we are preparing.

Chemistry

A New Paradigm in Separations: Molecular Recognition Membranes

98602

Gordon D. Jarvinen

We had two project goals: (1) understand, on the molecular level, mechanisms that govern ion and molecule transport through a semipermeable membrane and (2) develop robust molecular recognition membranes. A membrane is a permeable structure that separates two fluid phases and can operate as an active or passive barrier to transporting matter between the phases. The membrane can discriminate between components of the phases because of differences in properties such as size, shape, electrical charge, solubility, and diffusion rate.

Control of selective transport opens many membrane-separation possibilities. Molecular recognition membranes that accomplish precise separations based on chemical properties could lower costs for numerous industries where separations are an important part of operating cost, such as petrochemical and gas production, chemical process

industries, pharmaceutical production, and energy generation. Such membranes could also help meet separation challenges faced by the DOE, such as production and processing of nuclear materials, treating legacy wastes from past nuclear operations, remediating contaminated environmental sites, and sustaining energy generation.

This year our work focused on membranes for selective transport of metal ions from a feed solution to a receiving solution. We performed transport studies of various metal cations through modified and unmodified Anodisc™ alumina membranes. These membranes contain straight nonintersecting pores with average pore diameters of 20 nm and 100 nm.

We applied 30- to 100-nm-thick gold coatings to the membranes, then treated the membranes with alkylthiols that form a self-assembled monolayer on the gold and create a hydrophobic barrier (Fig. 1). This hydrophobic barrier is key to achieving selective transport between aqueous feed and receiving phases.

Fig.1. Alumina disks 25 mm in diameter and coated with 70 nm of gold. The gold layer was reacted with a thiol compound to form a self-assembled monolayer of the thiol on the gold surface. The left disk was treated with a thiol compound terminating with a carboxylic acid group, and the right disk was treated with a thiol terminating with an alkyl chain. The carboxylic acid group generates a more hydrophilic surface, as indicated by the low contact angle of the water drop on the left compared with the water drop on the relatively hydrophobic surface on the right.

We achieved quantitative transport of uranyl nitrate and 2,4,6-trichlorophenol with very high fluxes, indicative of a very thin selective layer of 50–100 nm. The uranium transport required the presence of a complexing agent, such as tributyl phosphate, in the membrane. The phenol diffused through the hydrophobic thiol layer that had been treated with dodecane to seal “holes” in the layer.

Other accomplishments include developing membrane characterization methods and performing both macroscopic and molecular-level modeling to clarify the experimental transport results. Future work will build on these results and lead to important new separation technology.

Publications

Bluhm, E.A., et al., “Surface Effects on Metal Ion Transport across Porous Alumina Membranes. 2. Trivalent Cations: Am, Tb, Eu, and Fe,” *Langmuir* **16**, 7056 (2000).

Pesiri, D.R., et al., “The Characterization of Asymmetric Alumina Membranes by Rutherford Backscattering Spectrometry,” *J. Membr. Sci.* **176**, 209 (2000).

Condensed Phase Kinetics and Reduced Reaction Mechanisms of Energetic Materials

98603

S. F. Son

High explosives (HE) science and modeling lie at the heart of the Laboratory's responsibilities in nuclear weapons applications. The HE component of a nuclear weapon furnishes the initial conditions for all other processes. However, our current HE models contain the least fundamental modeling of any component in a weapon. Our objective has been to develop a competency to predict reaction processes in energetic materials, in particular octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazocine (HMX), using detailed and reduced chemical kinetics schemes. We performed detailed chemistry experiments and calculations to contribute to the ultimate aim of developing simple, yet rigorous, models. Our project has four interacting components: (1) fundamental decomposition measurements, (2) detailed and reduced kinetic schemes, (3) modeling—coupling of transport with kinetics, and (4) integrated chemical and transport experiments.

This year we pursued our studies of selected chemical kinetic pathways. We also explored reduction methods; we applied Intrinsic Low-Dimensional Manifold methods to HMX chemistry for the first time, and the results show significant computational savings. We are comparing these reduced models to other simplified models. We used a detailed chemistry code to simulate the burning of HMX and compared the results to ignition data. These calculations are the only unsteady detailed chemistry calculations currently being performed on energetic materials. We developed further a novel nonlinear optical technique to study the kinetics of a solid-solid phase transition that occurs in heated HMX and triaminotrinitrobenzene (TATB). We incorporated the kinetics obtained into new reduced reaction schemes. We continued our study of the role of these crystalline changes. We looked at the effect of the HMX phase change in possible cook-off scenarios and compared it with newly available data. In addition, we performed and analyzed millisecond timescale experiments (laser ignition) of the HMX (thermally activated) polymorph change. Finally, we performed novel experiments on the combustion in "cracks" and actual damaged (thermal and mechanical) explosives.

Publications

- Ali, A.N., et al., "Laser Ignition of High Explosives," *Proceedings JANNAF 18th Propulsion Systems Hazards Subcommittee Meeting 692* (Chemical Propulsion Information Agency Publication, Johns Hopkins University, Columbia, MD, 1999), Vol. 1, pp. 51–67.
- Berghout, H.L., et al., "Convective Burning in Gaps of PBX 9501," *Proceedings JANNAF 18th Propulsion Systems Hazards Subcommittee Meeting 692* (Chemical Propulsion Information Agency Publication, Johns Hopkins University, Columbia, MD, 1999), Vol. 1, pp. 113–122.
- Berghout, H.L., et al., "Convective Burning in Gaps of PBX 9501" (Twenty-Eighth International Symposium on Combustion, Edinburgh, Scotland, July 30–August 4, 2000).
- Berghout, H.L., et al., "The Utility of High-Nitrogen Compounds in Explosive, Pyrotechnic and Propellant Applications" (Life Cycles of Energetic Materials, Hotel Royal Plaza, Orlando, FL, September 26–29, 1999).
- Bolme, C.A. et al., "Burn Rates of Energetic Materials" (Life Cycles of Energetic Materials, Hotel Royal Plaza, Walt Disney World, Orlando, FL, Sept. 25–29, 1999).
- Brewster, M.Q., et al., "Simplified Combustion Modeling of Double Base Propellant: Gas Phase Chain Reaction vs. Thermal Decomposition," *Combust. Sci. Technol.* **154**, 1 (2000).
- DeCroix, M.E., et al., "Dynamic Observations of Polymorph Changes in Explosives using Second Harmonic Generation," *Proceedings JANNAF 18th Propulsion Systems Hazards Subcommittee Meeting 692* (Chemical Propulsion Information Agency Publication, Johns Hopkins University, Columbia, MD, 1999), Vol. 1, pp. 23–31.
- De Croix, M.E., et al., "Temporally Resolved Measurements of a Structure Change in High Explosives During Rapid Heating" (submitted to *J. Phys. Chem. B*).
- Gonthier, K.A., and J.M. Powers, "A High Resolution Numerical Method for a Two-Phase Model of Deflagration-to-Detonation Transition," *J. Comp. Phys.* **163**, 376 (2000).
- Gonthier, K.A. et al., "Modeling Compaction-Induced Energy Dissipation of Granular HMX" (Eleventh International Detonation Symposium, Snowmass Village, CO, August 30–September 4, 1998).
- Louwens, J., et al., "Steady-State Hydrazinium Nitroformate (HNF) Combustion Modeling," *Journal of Propulsion and Power* **15**(6), 772 (1999).

- Lyman, J.L., and Y.C. Lyman, "Numerical Analysis of Laser Induced Ignition of Nitramine Propellants" (8th International Conference on Numerical Combustion, SIAM/INRIA, Amelia Island, FL, March 5–8, 2000).
- Lyman, J.L., et al., "Thermalchemical Functions for Gas-Phase, 1, 3, 5, 7-Tetranitro-1, 3,5,7-Tetraazacyclooctaine (HMX), and its Condensed Phases, and its Larger Reaction" (submitted to *Combust. and Flame*).
- Paolucci, S., and J.M. Powers, "Wavelet/ILDM Modeling of Combustion" (8th International Conference on Numerical Combustion, SIAM/INRIA, Amelia Island, FL, March 5–8, 2000).
- Powers, J.M., et al., "Application of Intrinsic Low Dimensional Manifolds to Nitramine Combustion" (8th International Conference on Numerical Combustion, SIAM/INRIA, Amelia Island, FL, March 5–8, 2000).
- Powers, J.M., et al., "A Wavelet/ILDM Method for Computational Combustion," *Bulletin of the American Physical Society* **44**, 54 (1999).
- Powers, J.M., "Thermal Explosion Theory for Shear Localizing Energetic Solids," *Combustion Theory and Modeling* **3**, 103 (1999).
- Rastigejev, Y., et al., "Novel Modeling of Hydrogen/Oxygen Detonation" (38th AIAA Aerospace Sciences Meeting, Reno, NV, January 10–13, 2000).
- Singh, S., et al., "Viscous Detonation in H₂/O₂/Ar Using Intrinsic Low Dimensional Manifolds and Wavelet Adaptive Multilevel Representation" (accepted in *Combustion Theory and Modeling*).
- Son, S.F., "Combustion of Energetic Materials" (IMA High-Speed Combustion in Gaseous and Condensed-Phase Energetic Materials Workshop, Minneapolis, MN, November 8–12, 1999).
- Son, S.F., "Overview of Energetic Materials Combustion" (Eighth International Conference on Numerical Combustion, Amelia Plantation, Amelia Island, FL, March 5–8, 2000).
- Son, S.F., et al., "Burn Rate Measurements of HMX, PBX 9501, TATB, PBX 9502, DHT, DAAF, and BTATz" *Proceedings JANNAF 18th Propulsion Systems Hazards Subcommittee Meeting 692* (Chemical Propulsion Information Agency Publication, Johns Hopkins University, Columbia, MD, 1999), p. 101.
- Son, S.F., et al., "Burn Rate Measurements of HMX, TATB, DHT, DAAF and BTATz" (Twenty-Eighth International Symposium on Combustion, Edinburgh, Scotland, July 30–August 4, 2000).
- Son, S.F., et al., "Combustion of Damaged Explosives" (submitted to *Thermochimica Acta*).
- Son, S.F., et al., "Dynamic Observation of a Thermally Activated Structure Change in 1,3,5-Triamino-2,4,6-trinitrobenzene (TATB) by Second Harmonic Generation," *J. of Phys. Chem. B*, **103**(26), 5434 (1999).

Cradle-to-Grave Carbon Management

99523

Hans Ziock

The stability of the U.S. and world economies is dependent on abundant low-cost energy, which is the basis of modern society and our wealth. As the world's population grows and strives to reach the affluence of the U.S., the world's already huge energy consumption will grow rapidly, as will its environmental impacts. Fossil fuels are currently the energy source of choice, as shown by their dominance of the world's energy supply. Their convenience, general public acceptance, huge associated infrastructure investment, and low cost explain this dominance. Growing world energy demand, coupled with the lack of a realistic replacement in the foreseeable future, means that the environmental issues associated with the use of fossil fuels must be dealt with.

We are addressing the key issues involved with achieving fossil fuel use with zero CO₂ emissions. Simultaneously, we are working to eliminate all other smokestack emissions associated with fossil fuel use: SO_x, NO_x, mercury, particulates, etc. Our thrust is threefold: separating the energy from the carbon, reducing smokestack emissions to zero, and permanently disposing of the resultant CO₂ through mineral carbonation. This work is directly relevant to DOE's Vision 21 program and offers a route for achieving the Vision 21 program goals.

The zero emission coal (ZEC) concept developed as part of this project is shown schematically in Fig. 1. During this year we filed a patent claim for the ZEC process. We actively sought industry evaluation and participation in developing this concept, and we established the Zero Emission Coal Alliance, ZECA, whose members include major utilities, coal companies, and research and government members from both Canada and the U.S. Through the work carried out under this project, the ZEC process is being refined and improved. We are also continuing to work on the development of high-temperature hydrogen-separation membranes, which would allow the process to produce clean hydrogen in addition to clean electricity. The combined theoretical and experimental work on the hydrogen-separation membranes has resulted in a second patent application. A third patent application involves geothermal energy production associated with underground CO₂ sequestration.

Publications

Walters, R.P., et al., "Carbonation: A Viable Method for CO₂ Sequestration," 25th International Technical Conference on Coal Utilization and Fuel Systems, Clearwater, FL, March 6–9, 2000.

Ziock, H.-J., and K.S. Lackner, "Zero Emission Coal" (Fifth International Conference on Greenhouse Gas Control Technologies, Cairns, Australia, August 13–16, 2000).

Ziock, H.-J., et al., "Zero Emission Coal" (GlobeEx Energex 2000 Conference, Las Vegas, NV, July 23–28, 2000).

Fig. 1. A schematic representation of the ZEC process. Coal is reacted with water to produce hydrogen through the use of CaO , which supplies missing energy and captures the generated CO_2 . The hydrogen is used to fuel solid-oxide fuel cells to generate electricity. The fuel cells' waste heat is captured to regenerate the CaO while generating a disposal-ready stream of pure CO_2 . This stream is reacted with magnesium or calcium minerals in an above-ground or below-ground process to form stable mineral carbonates (rocks), thereby guaranteeing permanent, safe disposal of the CO_2 .

Synergistic Effects in Actinide Molecular Science

2000501

David L. Clark

The project goal is to develop a fundamental understanding of the factors that influence chemical synergism in actinide chemistry. Synergistic effects occur when different metal ions or ligands are used to impart dramatic changes in solution chemical properties. For example, using two different ligands can dramatically enhance chemical separation efficiencies. Moreover, combining multiple metal ions can dramatically enhance (or decrease) chemical solubilities. We believe the observed chemical property changes are driven by fundamental changes in the molecular electronic structure. We can now test this idea with a multidisciplinary approach integrating synthesis, spectroscopy, theory, and modeling. The results of this work will have far-reaching implications for the behavior of actinides in waste and spent-fuel repository environments and for the design of high-efficiency recovery processes.

Synergistic effects may arise from the ability of actinide 5f electrons to communicate between metal atoms through the agency of bridging ligands and changing the diffuse swarm of solvent molecules in the outer sphere of a molecular complex in solution. As a test, we developed a strategy to prepare molecular systems with actinide metal centers containing different numbers of valence 5f electrons in the same molecule. This year, we targeted mixed-metal [U(VI)-Np(VI)] or mixed-valent [U(VI)-U(V)] molecules to vary the nature of 5f-5f electron interactions between metal centers. We have successfully prepared and structurally characterized several new target molecules with different numbers of valence 5f electrons on each actinide center. So far, new mixed-valent 5f complexes have shown “nonclassical” electronic spectra: the f-f electronic transitions have moved from their expected energy regions. In a similar fashion, new mixed-valent 5f complexes reveal extremely slow electron transfer kinetics for adding or removing an electron from a mixed-valent complex. In parallel, we have successfully developed the theoretical foundation to calculate both the electronic structure and the spectroscopic properties of actinide molecules containing more than one metal center. In our theoretical efforts, we applied hybrid density functional theory calculations to model systems containing two metal atoms with different numbers of 5f electrons.

Publications

Berg, J.M., and D.K. Veirs, “Speciation of Pu(IV) Complexes with Weak Ligands from Electronic Spectra” (accepted in *Proceedings of the OECD/NEA Workshop on Speciation Technology*).

Berg, J.M., et al., “Speciation Model Selection by Monte Carlo Analysis of Optical Absorption Spectra: Plutonium(IV) Nitrate Complexes,” *Appl. Spectrosc.* **54**, 812 (2000).

Burns, C.J., et al., “A Trigonal Bipyramidal Uranyl Complex: Synthesis and X-Ray Crystal Structure of [Na(THF)₂]-[UO₂(N(SiMe₃)₂)₃],” *Inorg. Chem.* **39**, 5464 (2000).

Burns, C.J., et al., “Non-Aqueous Chemistry of Uranyl Complexes with Tripodal Ligands,” in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 397.

Burns, C.J., et al., “Structural Preferences and Reactivity of Uranyl Alkoxide Complexes Prepared in Non-Protic Media,” in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 377.

Chisholm-Brause, C.J., et al., “Uranium(VI) Sorption Complexes on Montmorillonite as a Function of Solution Chemistry” (accepted in *J. Colloid Interface Sci.*).

Clark, D.L., “The Chemical Complexities of Plutonium,” *Los Alamos Science* **26**, 310 (2000).

Conradson, S.D., et al., “Characterizing the Plutonium Aquo Ions by XAFS Spectroscopy,” *Los Alamos Science* **26**, 364 (2000).

Danis, J.A., et al., “Coordination Trends in Alkali Metal Crown Ether Uranyl Halide Complexes: The Series [A(crown)]₂[UO₂X₄] where A = Li, Na, K and X=Cl, Br” (submitted to *Inorg. Chem.*).

Duff, M.C., et al., “Spectroscopic Characterization of Uranium in Evaporation Basin Sediments,” *Geochim. Cosmochim. Acta.* **64**, 1535 (2000).

Hay, P.J., and R.L. Martin, “Computational Studies of Actinide Chemistry,” *Los Alamos Science* **26**, 328 (2000).

Hay, P.J., et al., “Theoretical Studies of the Properties and Solution Chemistry of AnO₂²⁺ and AnO₂⁺ Aquo Complexes for An = U, Np and Pu,” *J. Phys. Chem. A* **104**, 6259 (2000).

Hopkins, T.A., et al., “Spectroscopy of UO₂Cl₄²⁻ in Basic Aluminum Chloride-1-Ethyl-3-methylimidazolium Chloride” (accepted in *Inorg. Chem.*).

- Hopkins, T.A., et al., "Spectroscopy of UO_2Cl_2 in Basic Aluminum Chloride: 1-Ethyl-3-methylimidazolium Chloride," in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 309.
- Martin, R.L., et al., "Theoretical Studies of Actinide Crown Ether Inclusion Complexes," in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 392.
- Morris, D.E., et al., "Steric vs Electronic Effects in Binary Uranyl Alkoxides: A Spectroscopic Perspective," in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 371.
- Oldham, S.M., et al., "Lewis Base Binding Affinities and Redox Properties of Plutonium Complexes," in *AIP Conf. Proc.* 532, (Springer-Verlag, New York, 2000), p. 230.
- Reeder, R.J., et al., "Uranyl Incorporation into Calcite and Aragonite: XAFS and Luminescence Studies," *Environ. Sci. Technol.* **34**, 638 (2000).
- Runde, W., "The Chemical Interactions of Actinides in the Environment," *Los Alamos Science* **26**, 338 (2000).
- Runde, W., et al., "Single Crystal and Solution Complex Structure of $\text{Nd}(\text{CO}_3)_4^{5-}$. The First Characterization of a Mononuclear Lanthanide(III) Carbonato Complex," *Inorg. Chem.* **39**, 1050 (2000).
- Runde, W., et al., "Spectroscopic Characterization of Trivalent f-Element (Eu, Am) Solid Carbonates," *J. Alloys Compd.* **303/304**, 182 (2000).
- Schreckenbach, G., "Mixed Uranium Chloride Fluorides $\text{UF}_{6-n}\text{Cl}_n$ and Methoxyuranium Fluorides $\text{UF}_{6-n}(\text{OCH}_3)_n$: A Theoretical Study of Equilibrium Geometries, Vibrational Frequencies and the Role of the f Orbitals," *Inorg. Chem.* **39**, 1265 (2000).
- Schreckenbach, G., et al., "NMR Shielding Calculations across the Periodic Table: Diamagnetic Uranium Compounds. 1. Methods and Issues," *J. Phys. Chem. A* **104**, 8244 (2000).
- Warner, B.P., et al., "Plutonium(III)-Catalyzed Meerwein-Ponndorf-Verley Reactions" (accepted in *Inorg. Chim. Acta*).
- Wilkerson, M.P., et al., "Bis[Uranyl Chloride) bis (Tetrahydrofuran)]" (submitted to *Inorg. Synth.*).
- Wilkerson, M.P., et al., "Synthesis and Structure of Tetrakis (2,6-Dichlorophenoxide)bis(tetrahydrofuran)uranium(IV)," *J. Chem. Crystallogr.* **30**, 7 (2000).
- Wilkerson, M.P., et al., "The Basicity of the Uranyl Ion under Electron-Donor Coordination Environments," *Inorg. Chem.* **39**, 5277 (2000).

Structural Biology Applied to DNA Damage and Repair

2000502

Joel Berendzen

We are studying the structure and function of proteins, focusing on scientific issues that take advantage of the Laboratory's expertise in genomics, molecular biology, and biomolecular structure, dynamics, and function. Our goal is to further develop capabilities in x-ray crystallography, nuclear magnetic resonance, infrared absorbance and Raman spectroscopy, x-ray and neutron scattering, theory and modeling, and protein production and purification. Our major emphasis is on studying the structures and function of proteins from extreme thermophiles—proteins that thrive at high temperatures. Studying the structure and dynamics of these proteins will help explain the basis for protein thermostability in general.

This year we used spectroscopic and modeling techniques to identify pathways taken by proteins to fold from disordered chains into compact structures. We developed molecular models for protein shapes determined from x-ray and neutron scattering and developed three-dimensional structures of proteins determined by x-ray crystallography. We also developed protein engineering and production capabilities. During the remainder of the project period, we plan to automate these capabilities, determine the three-dimensional structures of proteins involved in intracellular signaling, and analyze the dynamics and flexibility of biomolecules.

Publications

Brunori, M.B., et al., "The Role of Cavities in Protein Dynamics: Crystal Structure of a Photolytic Intermediate of a Mutant Myoglobin," *Proc. Natl. Acad. Sci. U.S.A.* **97**, 2058 (2000).

Chu, K., et al., "Crystal Structure of Photorelaxed Horse-Heart Myoglobin CO Complex," *Nature* **403**, 921 (2000).

Hernandez, G., et al., "Millisecond Time Scale Conformational Flexibility in a Hyperthermophile Protein at Ambient Temperature," *Proc. Natl. Acad. Sci. U.S.A.* **97** (7), 3166 (2000).

Sass, H.J., et al., "Structural Alterations for Proton Translocation in the M State of Wild-Type Bacteriorhodopsin," *Nature* **406**, 649 (2000).

Terwilliger, T.C., "Maximum-Likelihood Density Modification," *Acta Crystallogr.* **D55**, 1863 (2000).

Terwilliger, T.C., "Structural Genomics in N. America," *Nat. Struct. Biol.* **7**, 935 (2000).

Yang, J., et al., "A Comprehensive Approach for Accurate Measurement of Proton-Proton Coupling Constants in the Sugar Ring of DNA," *J. Magn. Reson.* **146**, 260 (2000).

Chemical Reactions at Actinide Surfaces: Implications for Nuclear Material Aging and Safety

2000514

Joseph Baiardo

The scientific goal is to increase our fundamental understanding of the role that surface defects, catalysis, radiolysis, and 5f electronic structure have on the molecular and atomic scale processes that control chemical reactivity of actinide metal and oxide surfaces. Actinide metal surfaces and their respective oxides are highly reactive, undergoing complex reactions in ambient environments. Extrinsic reactions of these actinide surfaces ultimately compromise the long-term stability of these materials regardless of their disposition environment. We are addressing this issue through the establishment of a multidisciplinary, cross-divisional fundamental research capability in actinide interfacial surface science that includes experimentation and theoretical modeling.

This year we obtained temperature-dependent studies of both α - and δ -Pu that delineate sharp features in the valence band spectra near the Fermi level. The temperature-dependent photoemission has led us to the conclusion that plutonium metal forms narrow, f-conduction hybridized bands at the Fermi level. We also initiated H_2 -adsorption studies (see Fig. 1). We successfully designed, built, and acquired data using a unique hydrogen atom source that emulates chemical transformations arising from bond cleavage reactions (such as homolytic bond scission from water). We examined the reactivity of H(D) atoms at UO_2 surfaces, and the reaction of C1 oxygenates following H(D) atom impingement (see Fig. 2). We have observed that the surface chemical state of plutonium oxide following exposure to air containing water vapor is highly variable and dependent on the magnitude of the radiation field at the oxide surface. A high-radiation field reduces the absolute amount of surface hydroxide, similar to a 400°C thermal treatment, thus keeping active sites (for subsequent water reaction) open on the surface. It appears that radiolytically initiated chemistry can also play a key role at the surfaces of plutonium oxide.

Fig. 1. This figure shows LPLS results of the first H_2 adsorption experiment on δ -Pu. Significant changes in the density-of-states throughout the valence band may indicate that H_2 reacted with the Pu even at 77 K.

Hydrogen on δ -Pu - Photoemission

Fig. 2. This figure shows the H/D atom doser and UPS spectra of smooth and sputter-damaged UO_2 surfaces before and after D atom exposure. The weak OD feature in both cases indicates that D atoms do not easily chemisorb on either surface. However, the increased OD intensity seen in damaged (i.e., oxygen vacancies) relative to smooth oxide surfaces indicates that the former are more reactive.

We are also evaluating novel “hybrid” functionals to obtain reliable theoretical treatments of the surface chemistry of actinide oxides using density functional theory (DFT). Traditional DFT approaches often incorrectly predict metallic character with essentially no bandgap for transition metal (NiO) and actinide oxides (UO_2). We have performed hybrid DFT calculations using cluster models to represent the (111) surface of UO_2 and PuO_2 to address the utility of such models for describing the structure and energies of hydrogen adsorbed on these surfaces.

Publications

Arko, A.J., et al., “Electronic Structure of α - and δ -Pu from Photoelectron Spectroscopy,” *Phys. Rev. B* **62**, 1773 (2000).

Arko, A.J., et al., “Electronic Structure of α - and δ -Plutonium Theory vs. Experiment,” *Los Alamos Science* **26**, 104 (2000).

Arko, A.J., et al., “Photoelectron Spectroscopy of α - and δ -Plutonium,” *Los Alamos Science* **26**, 120 (2000).

Boettger, J.C., “Approximate Two-Electron Spin-Orbit Coupling Term for Density Functional Theory Calculations Using the Douglas-Kroll-Hess Transformation,” *Phys. Rev. B* **62**, 7809 (2000).

Boettger, J.C., and A.K. Ray, “All Electron Density Functional Theory Calculations of the Zero-Pressure Properties of Plutonium Dioxide,” in *Plutonium Futures - The Science*, AIP Conf. Proc. **532**, (Springer-Verlag, NY, 2000), p. 422.

Boettger, J.C., and A.K. Ray, “All-Electron LCGTO Calculations for Uranium Dioxide,” *Int. J. Quant. Chem.* **80**, 824 (2000).

Joyce, J.J., and A.J. Arko, “Laser Plasma Light Source Design and Operation,” *Los Alamos Science* **26**, 138 (2000).

Ray, K., and J.C. Boettger, “An All-Electron LCGTO Study of Square and Hexagonal Plutonium Monolayers” (submitted to *J. Phys. Condes. Matter*).

Voss, M., et al., “Surface Characterization and Theoretical Studies of UO_2 Surfaces Following Atomic H Exposure” (submitted to *J. Nuc. Mater.*).

Computer Science and Software Engineering

Foundations of Simulation Science

2000515

Christopher L. Barrett

This project develops a comprehensive formal basis for simulation of large heterogeneous complex systems. We addressed the following areas: the mathematical foundations of simulation, issues in implementing and computing large-scale simulations, and extending the statistical sciences for simulation-based reasoning. To illustrate the theoretical research, we implemented a simulator for large mobile packet-switched data communication systems. This application is inherently related to theory (complex packet sequence and network rebroadcast dynamics can be viewed in terms of our theoretical constructs). This very current research topic is strategically and programmatically important; attempts to provide capability that is beyond the state of the art; and relates directly to core competencies in high-performance computing, modeling, and simulation and in complex system analysis.

We have made substantial progress in this project. We have produced important fundamental mathematical developments in Sequential Dynamical Systems (SDS) and surprising connections to computer science, especially relationships to algorithm theory and computational complexity. A SDS-based design led to a prototype packet-switched, data-communication networks simulator with unprecedented levels of performance. The project has created opportunities for recruiting and collaboration in computer science and mathematics critical skills. The theoretical and demonstration results of this project have already provided the conceptual basis for two externally funded application-oriented projects. Progress in this theoretical simulation science area will undoubtedly continue to underwrite the scientific quality of such successful spin-off applications.

This year we established the basis for dynamical SDS isomorphy class concepts and the foundations of a computational complexity and algorithmic theory of SDS. We produced a prototype for highly scalable, efficient simulation of mobile communication and computation systems.

Our research provided a conceptual and theoretical basis for potential applications development that enabled a spin-off project to be funded.

Publications

Barrett, C., et al., “Computational Aspects of Sequential Dynamical Systems: I” (IEEE Conference on Computational Complexity, Florence, Italy, July 4–7, 2000).

Barrett, C., et al., “Elements of a Theory of Simulation II: Sequential Dynamical Systems,” *Appl. Math. and Comput.*, **107/2-3**, 121 (2000).

Barrett, C., et al., “Elements of a Theory of Simulation III: Sequential Dynamical Systems” (accepted in *Appl. Math. and Comput.*).

Barrett, C., et al., “Elements of a Theory of Simulation IV: Sequential Dynamical Systems” (accepted in *Appl. Math. and Comput.*).

Barrett, C., et al., “Formal Language Constrained Path Problems” (accepted in *SIAM J. Computing*).

Barrett, C., et al., “Sequential Dynamical Systems and Applications” (33rd Annual Simulation Symposium, Washington DC, April 16–20, 2000).

Barrett, C.L., et al., “Actuated Signals in TRANSIMS” (79th Annual Transportation Research Board Meeting, Washington, DC, January 12, 2000).

Carr, R., et al., “On the Red-Blue Set Cover Problem” (Association for Computing Machinery-Society for Industrial and Applied Mathematics [ACM-SIAM] Symposium on Discrete Algorithms, San Francisco, CA, January 9–11, 2000).

Czabarka, E., et al., “Algorithms for Optimizing Production DNA Sequencing” (Association for Computing Machinery-Society for Industrial and Applied Mathematics [ACM-SIAM] Symposium on Discrete Algorithms, San Francisco, CA, January 9–11, 2000).

Doddi, S., et al., “Approximation Algorithms for Clustering to Minimize the Sum of Diameters” (Seventh Scandinavian Workshop on Algorithm Theory, Bergen, Norway, July 5–7, 2000).

Doddi, S., et al., “Point Set Labeling with Specified Positions” (Association for Computing Machinery Symposium on Computational Geometry, Hong Kong, China, June 12–14, 2000).

Hunt III, H.B., et al., “On the Efficient Approximability of ‘HARD’ Problems: A Survey,” in *Proc. Approximation and Complexity in Numerical Optimization: Continuous and Discrete Problems*, P.M. Pardalos, Ed. (Kluwer Academic Publishers, Holland, 2000).

Hunt III, H.B., et al., “Parallel Approximation Schemes for a Class of Planar and Near Planar Combinatorial Problems” (accepted in *Information and Computation*).

Jacob, R., et al., “A Computational Study of Routing Algorithms for Realistic Transportation Networks,” *ACM J. Experimental Algorithmics*, **4**, 6 (1999).

Konjevod, G., et al., “Budget Constrained Minimum Cost Connected Medians” (26th International Workshop on Graph Theoretic Concepts in Computer Science, Konstanz, Germany, June 15–17, 2000).

Kopp, S., and C. Reidys, “Neural Networks – A Combinatorial Perspective” (accepted in *Applied Math and Computation*).

Krumke, S.O., et al., “Approximation Algorithms for Broadcast Scheduling in Radio Networks” (accepted in *Telecommunication Journal*).

Marathe, M.V., et al., “Experimental Analysis of a Simple Distributed Edge Coloring Algorithm” (12th ACM Symposium on Parallel Algorithms and Architectures, Bar Harbor, ME, July 9–13, 2000).

Mortveit, H.S., and C.M. Reidys, “Discrete Sequential Dynamical Systems,” (accepted in *Discrete Mathematics*).

Ravi, R., et al., “Approximation Algorithms for Degree Constrained Minimum Cost Network Design Problems” (accepted in *Algorithmica*).

Reidys, C.M., “Acyclic Orientations and Sequential Dynamical Systems” (accepted in *Advances in Applied Mathematics*).

Reidys, C.M., “Random Induced Subgraphs of Cayley Graphs,” *European Journal of Combinatorics*, **21** (8), 1057 (2000).

Rosenkrantz, D.J., et al., “Efficient Construction of Minimum Makespan Schedules for Tasks with a Fixed Number of Distinct Execution Times” (accepted in *Algorithmica*).

Engineering Science

Hard and Deeply Buried Target Defeat

99510

Wendee M. Brunish

The goal of this project is developing technology to improve the nation's capability to find and characterize underground facilities and, as a byproduct, limit the proliferation of weapons of mass destruction. Our plan is to emphasize risky and novel approaches that leverage national test facilities to maximize our progress.

The technical components of the project are information tools, information integration, weapons phenomenology modeling, signal propagation and signature development (including infrared, long-range seismic detection, active seismic imaging, radio frequency [RF] and infrasound), and novel sensors.

We have made significant progress in improving our understanding of signatures from underground facilities and of technologies for finding and characterizing them. This year, we incorporated our underground facility signature data into the DIGS software system; we can now apply more sophisticated network analysis methods to integrate and interpret diverse data types to better comprehend a single problem. To predict how geology will impact the effects of weapons on buried structures, as shown in Fig. 1, we studied the effects of three-dimensional features, such as buried fault scarps, on stress wave propagation with weapons phenomenology calculations. We developed seismo-acoustic signatures using a combination of multiphenomenology data collection exercises, analysis tools, modeling of tunnel resonances, and scale-model lab analyses. We analyzed long-range seismic detection using local array data to improve error estimation techniques; this improvement will help us separate signal from noise and better understand multipath effects. We modeled infrared signatures from underground facilities to maximize the effectiveness of this technique, taking diurnal and seasonal temperature variations into account. We recorded RF signatures from a variety of relevant sources and refined recording systems and analysis techniques (see example of signature in Fig. 2). We modified and applied the DETECT

code to the problem of propagation along an external cable shield to the ground interface and added further complexities such as tunnel fill, cable bundle, and lead pipe to the two-dimensional finite-volume time-domain method.

Publications

Doll, C.G., et al., "Analysis of Tunnel Boring Machine Seismic Signal Attenuation," *Seis. Res. Lett.*, **71**, 220 (2000).

Greaves, R.J., et al., "Seismic Characterization of Tunnel Boring Machine Activity near Boston, MA, USA" (American Geophysical Union 1999 Fall Meeting, San Francisco, December 15–19, 1999).

Fig. 1. The stress field surrounding an explosion at 200 milliseconds illustrates the effect of a fault scarp on the amount of damage an attack causes to an underground facility. To determine which targets we can hold at risk, we need this kind of three-dimensional geologic modeling capability.

Fig. 2. We can identify the type, location, and activity of vehicles associated with underground facilities using RF signals. This figure shows the signal associated with a vehicle starting up in an underground facility at the Nevada Test Site.

Nuclear Materials Management Systems for Proliferation Resistance, Environmental Protection, and Sustainability

99521

Edward Arthur

This project developed a first-of-its-kind Nuclear Materials Management System computer program to model various material/process combinations in the nuclear fuel cycle. Doing so allows determination of how best to implement them according to criteria of economics, proliferation risk, and environmental impacts. The resulting fuel cycles (flow of materials between different materials and processes) can provide options for future developers of nuclear technology as well as policy makers.

We completed the project this year. We report progress in the following areas. (1) The optimization code FCOPT (Fuel Cycle Optimization) was completed to allow analysis of generalized fuel cycles. (2) Optimization methods based on minimizing economic or proliferation risks were implemented into FCOPT. (3) Underlying models for proliferation and environmental risks were created (in initial form). (4) A laptop-based graphical interface was developed to allow a user to interrogate and display results from hundreds of fuel cycle component combinations analysis runs. (5) A number of test cases were run to demonstrate model capabilities in which nuclear fuel cycle combinations were optimized using either cost or proliferation risk minimization. We also demonstrated the extensive capabilities of this model to potential users and identified steps for improvement that could result given future programmatic funding.

Geoscience, Space Science, and Astrophysics

Coupled Environmental Modeling

98604

Larry Winter

This project has developed high-resolution computer models of coupled environmental systems. Coupled systems consist of discrete physical domains that interact nonlinearly and operate at different time and space scales. The study of coupled systems has led to a new generation of modeling tools we can use to predict the evolution of environmental phenomena. These tools will enable us to address a large variety of future environmental security issues—from global challenges such as CO₂ and water cycles to regional problems such as fresh water supply and agriculture to local threats such as wildfire and flooding. Furthermore, because coupled environmental systems are natural analogs of weapons systems, which are also composed of diverse physical elements evolving at different rates and over different volumes, interdomain coupling is highly relevant to the stewardship of weapons systems.

This year the project concentrated on modeling the water cycle of the upper Rio Grande Basin for the 1992–1993 water year and implementing the three-dimensional fire model. We completed initial simulations of linked atmosphere-land surface processes on the Nirvana Blue computer for soil moisture in the San Luis Valley at resolutions of 100m. This work required novel representations of cloud microphysics and the movement of water tables as free surface in heterogeneous media, as well as fine-grained parallelized versions of atmospheric and land surface processes linked as communicating processes through the Laboratory's Parallel Applications Workspace. We implemented the three-dimensional model on idealized and realistic wildfire situations to both debug the model and learn more about wildfire behavior. The variety of idealized scenarios tested various complex aspects of wildfire behavior. We analyzed the results of large wildfires we simulated in Southern California and near the Laboratory's S-site. In conjunction with the National Center for Atmospheric Research in Boulder, Colorado, we implemented fire image processing algorithms for infrared video, and this method should result in a validation tool in the near future. We also implemented an improved diffusion-based radiation scheme.

Publications

Assouline, S., and D.M. Tartakovsky, "Unsaturated Hydraulic Conductivity Function based on a Fragmentation Process" (accepted in *Water Resour. Res.*).

Costigan, K.R., et al., "Atmospheric/Hydrologic Models for the Rio Grande Basin: Simulations of Precipitation Variability," *Global and Planetary Change* **25**, 83 (2000).

Costigan, K.R., et al., "Model Sensitivities Affecting Long-Term Simulation of Precipitation" (9th Conference on Mountain Meteorology, Snowmass Village, CO, August 7–11, 2000).

Costigan, K.R., et al., "Simulations of Precipitation over the Upper Rio Grande Basin" (15th Conference on Hydrology, Long Beach, CA, January 9–14, 2000).

Lu, Z., et al., "Conditional Moment Analysis of Steady State Unsaturated Flow in Bounded, Randomly Heterogeneous Soils based on Kirchhoff Transformation: 1. Recursive Finite Element Formulation" (submitted to *Water Resour. Res.*).

Reisner, J.M., et al., "Coupled Atmospheric-Fire Modeling Employing the Method of Averages," *Mon. Wea. Rev.* **128**, 3683 (2000).

Stalker, J.R., and K.R. Knupp, "A Method to Identify Convective Cells within Multi-Cell Thunderstorms from Multiple Doppler-Radar Data" (submitted to *Mon. Wea. Rev.*).

Stalker, J.R., et al., "Use of Cumulus Parameterization and Explicit Microphysics for Climate Studies over the Rio Grande Basin" (15th Conference on Hydrology, AMS, Long Beach, CA, January 9–14, 2000).

Tartakovsky, D.M., and C.L. Winter, "Dynamics of Free Surfaces in Random Porous Media" (accepted in *SIAM J. Appl. Math.*).

Tartakovsky, D.M., et al., "Equivalent Transmissivity Tensor for Bounded Randomly Heterogeneous Aquifers" (submitted to *Transport in Porous Media*).

Winter, C.L., et al., “Moment Equations for Flow in Highly Heterogeneous Porous Media” (accepted in *Surveys in Geophysics*).

Winter, C.L., et al., “Numerical Solutions of Moment Equations for Flow in Heterogeneous Composite Aquifers” (submitted to *Water Resour. Res.*).

Winter, C.L., and D.M. Tartakovsky, “Groundwater Flow in Heterogeneous Composite Aquifers” (submitted to *Water Resour. Res.*).

Winter, C.L., and D.M. Tartakovsky, “Mean Flow in Composite Porous Media,” *Geophysical Research Letters* **27**(12), 1759 (2000).

Space Science and Exploration

99511

Deborah Bennett

The goal of our project is to enhance the Laboratory's space science capabilities in activities that are synergistic between the Laboratory and the nation's space programs. We are enhancing a variety of Laboratory technologies that are also valuable to sponsors such as NASA, the National Science Foundation space program, and other government agencies, as well as to industry.

A great deal of technical progress has been made this year. The following are examples of this year's successes. (1) It was discovered that x-ray photoelectron spectroscopy reveals the chemical state of elements in million-year-old mineralized rock samples, enabling the possible identification of life forms. (2) Planetary core samples less than a millimeter in diameter were extracted using carbon-based microdrills. These samples can be analyzed in Chemin, a small, portable x-ray diffraction/x-ray fluorescence instrument designed for use on space missions. (3) High-quality Raman spectra of minerals were obtained using a compact laser and detection system. By combining laser-induced breakdown spectroscopy (LIBS) and Raman spectroscopy, we can now obtain complete geochemical and mineralogical analyses of a sample using the same instrument—an exciting breakthrough. (4) Structures etched with the photo-lithographic technique LIGA (a German acronym) were shown to possess sufficient internal channel smoothness to allow limited focusing of soft x-rays. This is the first time any x-ray focusing has been achieved with etched lobster-eye optics. (5) The astrophysics soft-x-ray/reflectometry laboratory is now fully functioning. This laboratory will enable the development of several new instrument technologies, which will provide new measurement and experimental capabilities. (6) The heat-pipe power system core was successfully tested to 1200 K using resistance heaters at NASA's Marshall Space Flight Center (see Fig. 1). This test verified the geometric and structural adequacy of the core. The heat-pipe power system is a fission power reactor intended to provide electric power and/or propulsion for deep-space and manned missions. The resistance heaters simulate the heat from fission reactions without the expense and safety issues associated with using fissile fuel.

Publications

Bedau, M., et al., "Open Problems in Artificial Life," in *Artificial Life* (MIT Press, Cambridge, MA, in press).

Burde, S., et al., "Direct Detection of DNA in Microfossils" (submitted to *Nature*).

Mayer, B., and S. Rasmussen, "Dynamics and Simulation of Micellar Self-Reproduction," *International Journal of Modern Physics, C* **11** (4), 809 (2000).

Nilsson, M., et al., "Constructive Molecular Dynamics (MD) Lattice Gases: 3-D Molecular Self-Assembly," in *New Constructions in Cellular Automata*, D. Griffeath and C. Moore, Eds. (Oxford University Press, Oxford, U.K., 2000) p. 157.

Peele, A.G., et al., "LIGA for Lobster: First Observation of Lobster-Eye Focusing from Lithographically Produced Optics" (submitted to *Rev. Sci. Instrum.*).

Rasmussen, S., et al., "Ansatz for Dynamical Hierarchies," in *Artificial Life* (MIT Press, Cambridge, MA, in press).

Ritzau, S., et al., "Solid State Detection of Low Energy (1–20 keV) Ions and Electrons for Constellation Missions," in *Science Closure and Enabling Technologies for Constellation Class Missions*, V. Angelopoulos and P. Panetta, Eds. (University of California Printing Services, Berkeley, CA) p. 131.

Snyder, H.R., et al., "Fluidized Bed Plasma Imaging and Possible Strong Coupling," *Appl. Phys. Lett.* **76** (18), 251 (2000).

Wiens, R., et. al., "Development of a Prototype Laser-Induced Breakdown Spectroscopy (LIBS) Instrument with Stand-Off Raman Capabilities as Part of the Mars Instrument Development Program," in *Proceedings of the 31st Lunar and Planetary Science Conference* (Lunar and Planetary Institute, Houston, TX, 2000) p. 1468.

Fig 1. Heat-pipe power system core being tested with resistance heaters, which simulate a fission energy source. The heat-pipe power system was designed to provide electricity from fission for deep-space and manned missions.

Dynamic Processes of the Earth

2000507

Kristin Bennett

Investigation of the Earth's materials, lithospheric properties, and planetary interior is essential for understanding and interpreting the dynamics and composition of the solid earth. The objective of our project is to improve fundamental understanding of solid earth dynamics and apply that knowledge to significant issues related to defense programs.

We expect our project to impact several strategic interests of the Laboratory, including characterizing materials at high pressures and temperatures, monitoring and predicting constitutive responses of nuclear stockpile materials, and predicting strong ground motion for earthquake hazard analysis and nuclear nonproliferation assessment. We approach our study of materials with numerous tools, including texture analysis, neutron scattering, high-pressure research, nuclear-based analysis, high-precision isotopic analysis, Mossbauer spectroscopy, and seismic and geochemical measurements. We are also modeling joint tomographic inversion, fluid flow and transport, and polycrystal plasticity theory.

This year we focused on computational simulations and how they compare with observed data. We used molecular dynamic and Monte Carlo simulations with measurements from inelastic and quasielastic neutron-scattering data to study the vibrations and diffusive motions of water molecules through geological materials.

We began studying the development of strain and seismic anisotropy in the oceanic upper mantle by combining three-dimensional, time-dependent flow models with real textural data of oceanic olivine. The goal is to interpret seismic data. Using an advanced three-dimensional convection code that includes components for rigid plates and a low-viscosity zone just beneath, we demonstrated how motions of relatively fixed plates emerge from the Earth's convective style.

To study the dipole component of the Earth's magnetic field, we used computational geodynamo models. Our results suggest that different heat flux conditions at the core-mantle boundary produce statistically very different magnetic field models, supporting the hypothesis of preferred transitional bands.

Finally, we used fully coupled multiphase modeling of heat and mass transport to simulate the flow of heat, water, and air in ash-flow tuff at a field site in southern Nevada where there has been volcanic activity (see Fig. 1).

Publications

Aurnou, J., and P. Olson, "Control of Inner Core Rotation by Electromagnetic, Gravitational and Mechanical Torques," *Phys. Earth Planet. Inter.* **117**, 111 (2000).

Buffett, B.A., and G.A. Glatzmaier, "Gravitational Braking of Inner-Core Rotation in Geodynamo Simulations," *Geophys. Res. Lett.* **27**, 3125 (2000).

Coe, R.S., et al., "An Examination of Simulated Geomagnetic Reversals from a Paleomagnetic Perspective," *Philos. Trans. R. Soc. London, Ser. A* **358**, 1141 (2000).

Cooper, K.M., et al., "Crystal and Magma Residence at Kilauea Volcano, Hawaii: $^{230}\text{Th}/^{226}\text{Ra}$ Dating of the 1955 East Rift Eruption" (submitted to *Science*).

Glatzmaier, G.A., and T. Clune, "Computational Aspects of Geodynamo Simulations, *Comput. Sci. Eng.* **2**, 61 (2000).

McMillan, D.G., et al., "A Statistical Appraisal of Magnetic Fields of Geodynamo Models" (submitted to *Geochemistry, Geophysics, Geosystems*).

Megnin, C., and B. Romanowicz, "A Comparison between Tomographic and Geodynamic Models of the Mantle," in *History and Dynamics of Global Plate Motions, AGU Monograph Series* (American Geophysical Union, Washington, D.C., 2000), Vol. 121, p. 257.

Megnin, C., and B. Romanowicz, "A Model of Shear Velocity in the Mantle from the Inversion of Waveforms of Body, Surface, and Higher Mode Waveforms" (accepted in *Geophysical Journal International*).

Pari, G., and W.R. Peltier, "Subcontinental Mantle Dynamics: A Further Analysis Based upon the Joint Constraints of Dynamic Surface Topography and Free-Air Gravity," *Journal of Geophysical Research* **105**, 5635 (2000).

Richards, M.A., et al., "Mantle Convection and Plate Motion History: Toward General Circulation Models," *History and Dynamics of Global Plate Motions, AGU Monograph Series* (American Geophysical Union, Washington, D.C., 2000), Vol. 121, p. 289.

Richards, M.A., et al., "The Role of a Low Viscosity Zone in Stabilizing Plate Tectonics: Implications for Comparative Terrestrial Planetology" (submitted to *Science*).

Roberts, P.H., and G.A. Glatzmaier, "Geodynamo Theory and Simulations" (accepted in *Reviews of Modern Physics*).

Roberts, P.H., and G.A. Glatzmaier, "A Test of the Frozen Flux Approximation Using a New Geodynamo Model," *Philos. Trans. R. Soc. London, Ser. A* **358**, 1109 (2000).

Stegman, D.R., et al., "Models of Mantle Mixing Associated with Plate-Scale Flow (submitted to *Journal of Geophysical Research*).

100 years

Fig. 1. Cross-section view of a magma intrusion into older volcanic rock. The model results shown are for the base-case simulation at 100 years after intrusion. The boundary of the intrusion is represented by the black line overlay. (A) Temperature. The zone of boiling in the host rock extends to the ground surface above the intrusion and outward about 100 to 150 m. (B) Saturation. The dry-out zone extends about 50 m into the host rock, and the outer edge of the condensation zone is located about 150 m from the contact. (C) Temperature and saturation profiles along the transect represented by a wide V-shaped line across the upper part of the intrusion in A and B. (D) Gas pressure and vapor movement. Vapor flow is dominantly away from the vapor-pressure highs located above and below the intrusion. The maximum flow rate of the vapor is on the order of 5 mm/s.

Integrated Ocean and Atmospheric Science and Modeling

2000508

C. F. Keller

This research is designed to enhance competency in large-scale modeling by developing and applying capabilities to interactive global climate models. The aim is to understand and predict climate change and associated phenomena and become a major player in the new, multiagency Advanced Climate Prediction Initiative.

This research will also support the Laboratory's new efforts in understanding water resources, both Lidar water vapor measurements as well as the larger computer modeling. The numerical methods development supported by this project focuses on developing new algorithms for geophysical flows, and in particular for the dynamics of oceans and atmospheres, and on testing them in realistic simulations. The issues include representing subgrid scale effects while preserving flow variability, efficient treatment of multiple time scales, preservation of asymptotic balances, and ensuring nonoscillatory behavior (closely related to enforcing the second law of thermodynamics locally).

Advances in general circulation modeling will benefit certain aspects of treaty verification and counter-terrorism work. Finally, the study of biogeochemical cycles in the global oceans will support initiatives to evaluate environmental impacts of expected pollution from East Asian industrialization.

Despite new security regulations that delayed progress, we have now succeeded in coupling the University of California at Los Angeles's global climate model (grid point model) with the Los Alamos Global Ocean (POP) code. This coupled model will be used to study variability in the eastern Pacific Ocean and its influence on precipitation in western North America. The HIGRAD code was used to simulate Lidar observations of evaporation in the equatorial Pacific Ocean (Fig. 1). The SPLASH code, which models the fate of localized precipitation (evapotranspiration, runoff, and subsurface infiltration), was used to further study groundwater recharge in semi-arid areas, and to evaluate runoff at the Laboratory and surrounding area in the aftermath of the Cerro Grande Fire (Fig. 2). A substantial improvement was made in the global ocean-phytoplankton modeling effort. In addition to shifting to the highest resolution ocean simulations ($1/6^\circ$ grid cell), the iron budget was introduced, which resulted in much more realistic simulations of the latitudinal and seasonal growth and decay of phytoplankton. Comparisons with the new satellite, SEAWIFS, which senses chlorophyll, show much improved agreement (Fig. 3).

The numerical methods development supported by this project have been targeted toward geophysical flows in the ocean and atmosphere. We developed a method of averages to treat (in a computationally efficient manner) the multiple timescale processes associated with oceanic flows and wildfire propagation. We have conducted numerical studies of a new turbulence model based on a dispersive closure, and have validated the effects of this model in homogenizing potential vorticity in an idealized ocean basin simulation. We have made new theoretical connections of this turbulence model to the modified equations of modern nonoscillatory forward time fluid algorithms.

Publications

Brekke, L., et al., "Validation of a Lidar Wind-Field Algorithm for Flux Estimates" (submitted to *Geophys. Res. Lett.*).

Chu, S., and S. Elliott, "Latitude versus Depth Simulation of Ecodynamics and Dissolved Gas Chemistry Relationships in the Central Pacific" (submitted to *J. Atmos. Chem.*).

Cooper, D.I., "Spatial and Temporal Properties of Water Vapor and Flux Over a Riparian Canopy," *Agric. & Forest Meteorol.* (December 1999).

Eichinger, W.E., et al., "Estimation of Spatially Distributed Latent Heat Flux Over Complex Terrain from a Raman Lidar," *Agric. & Forest Meteorol.* (December 1999).

Kao, C.-Y.J., et al., "Probing Atmospheric Turbulence with High-Resolution Lidar and Models" (submitted to *J. Geophys. Res.*).

Kao, C.-Y. J., et al., "High Resolution Modeling of Lidar Data: Mechanisms Governing Surface Water Vapor During SALSA," *Agric. & Forest Meteorol.* (December 1999).

Li, H., et al., "Rossby Wave Instability of Thin Accretion Disks—III Nonlinear Simulations" (to be published in *Astrophys. J.*).

Nadiga, B., and L. Margolin, "Dispersive Eddy Parameterization in a Barotropic Model" (to be published in *J. Phys. Oceanography*).

Reisner, J., et al., "Coupled Atmospheric-Fire Modeling Employing the Method of Averages," *Mon. Wea. Rev.* **128**, 3683.

Smolarkiewicz, P.K., et al., "A Class of Nonhydrostatic Global Models," *J. Atmos. Sci.* **58**, 349.

Sun, C., et al., "Data Assimilation for a Coupled Ocean-Atmosphere Model. Part I: Sequential State Estimation" (submitted to *Mon. Wea. Rev.*).

Fig. 1. High resolution computer simulations of water vapor over the equatorial Pacific Ocean done to compare with those observed by the Los Alamos Raman Lidar. Fig. 1a is a simulation of the Lidar vertical scan; Fig. 1b is a simulation of Lidar horizontal scan 10 m above the ocean. Agreement with Lidar observations is extremely good, but has led to reassessment of how fast Lidar scans should be made.

Fig. 2. Computer simulations of runoff from the Cerro Grande fire: Top: Pre- and post-fire distributions of runoff (yellow areas have highest runoff). Bottom: Difference in runoff between pre- and post-fire (blue areas have greatest difference).

Fig. 3. Phytoplankton in the Pacific Ocean simulated with Los Alamos Ocean Code, POP, during La Niña, Dec. 1996 (3a) and during El Niño, Dec. 1997 (3b). Clearly seen is the difference between upwelling-fertilized “La Niña” plankton, and no upwelling-unfertilized “El Niño” lack of plankton, which agrees well with observations.

Earth's Plasma and Radiation Environment

2000509

J. Birn

Earth's atmosphere, ionosphere, and magnetosphere, where programmatic and scientific satellites reside, are strongly affected by bursts of particles and waves. This project constitutes a comprehensive effort to investigate the sources and mechanisms that cause and affect such bursts. One part focuses on sources and mechanisms causing x-ray and gamma-ray bursts. The other part concerns the study of plasma and field processes involved in solar-terrestrial interaction.

Using Los Alamos interplanetary plasma measurements and theory, we have explored the processes that govern the electron-to-proton temperature ratio in the solar wind. We found a critical limiting condition, which was supported by observations indicating the existence of the whistler heat flux instability. We have also developed an analytical approach and numerical codes to investigate the acceleration and heating of the ions in the solar wind plasma.

Through multipoint analysis and modeling, we have studied the structure of an interplanetary magnetic cloud or "coronal mass ejection" and identified orientation and scales. The observations at different sites do not fit a single cylindrical flux rope model (Fig. 1), indicating a more complicated structure.

Fig. 1. Simultaneous observations of an interplanetary magnetic cloud with the structure of a magnetic flux rope. Simple models fitted to the observations at "Pioneer Venus Orbiter" and "ISEE-3" indicate different orientations and sizes at the two sites or a more complicated structure.

We have studied the process by which magnetospheric electrons are accelerated to relativistic energies. As a step toward an extended data analysis, we have developed a method to renormalize the data from geosynchronous orbit to a reference location.

To study effects of time variation and turbulence, we have further examined particle motion in the Earth's nightside magnetotail. We found that the observed inverse velocity dispersion can be explained by particle motion near an explosively evolving site where magnetic fields merge or "reconnect" and that the approximate location of this site can be determined from the observed velocity dispersion.

We have worked with colleagues at Berkeley to adapt software developed for supernova searches for finding astrophysical transients measured with the *Robotic Optical Transient Search Experiment* (ROTSE) at Los Alamos. The primary goal is to improve gamma-ray burst identification. The newly developed ROTSE software was verified by a blind test on real data. The software successfully identified the known transient XTE J1118+480 (see Fig. 2).

Fig. 2. Blind test of the transient detection software. By comparing two ROTSE images containing the known transient XTEJ1118+480, the new software successfully located the variable source. The insert in the upper left is a blowup of the small box in the ROTSE field. The software compared this image with an earlier one (blowup on the upper right) and produced the subtraction (lower right) that clearly shows the transient near the center of the field.

Publications

Galinsky, V.L., and V.I. Shevchenko, “Nonlinear Cyclotron Resonant Wave-Particle Interaction in a Nonuniform Magnetic Field,” *Phys. Rev. Lett.* **85**, 90 (2000).

Gao, Y.F., et al., “Sino-Magnetic Array at Low Latitudes (SMALL) including Initial Results from the Sister Sites in the United States” (submitted to *Adv. Space Res.*).

Gary, S.P., et al., “Alpha/Proton Magnetosonic Instability in the Solar Wind,” *J. Geophys. Res.* **105**, 20989 (2000b).

Gary, S.P., et al., “Electromagnetic Alpha/Proton Instabilities in the Solar Wind,” *Geophys. Res. Lett.* **27**, 1355 (2000a).

Gosling, J.T., et al., “Coronal Mass Ejections,” in *Summary-Rapporteur Volume of the International Cosmic Ray Conference*, B. Dingus, Ed., in *AIP Conference Proceedings* (American Institute of Physics, Woodbury, NY, in press).

Hull, A.J., et al., “Electron Temperature and de Hoffmann-Teller Potential Change across the Earth’s Bow Shock: New Results from ISEE1,” *J. Geophys. Res.* **105**, 20957 (2000).

Kawano, H., et al., “Correlation between the Solar Wind Dynamic and Static Pressures,” *J. Geophys. Res.* **105**, 7583 (2000).

Lindsay, G.M., et al., “Predictability of Dst Index based upon Solar Wind Conditions Monitored Inside 1 AU,” *J. Geophys. Res.* **104**, 10335 (1999).

Lindsay, G.M., et al., “Relationships between CME Speeds from Coronagraph Images and Interplanetary Characteristics of Associated ICMEs,” *J. Geophys. Res.* **104**, 12515 (1999).

Mulligan, T., et al., “Flux Rope Modeling of an Interplanetary Coronal Mass Ejection Observed at WIND and NEAR,” in *Solar Wind Nine*, S.R. Habbal, R. Esser, J.V. Hollweg, and P.A. Isenberg, Eds. (AIP Conference Proceedings 689, Woodbury, NY, 1999).

Mulligan, T., et al., “Intercomparison of NEAR and WIND ICME Observations,” *J. Geophys. Res.* **104**, 28217 (1999).

Mulligan, T., et al., “Interplanetary Magnetic Clouds: Statistical Patterns and Radial Variations,” *Adv. Space Res.* **26(5)**, 801 (2000).

Mulligan, T., et al., “On Interplanetary Coronal Mass Ejection Identification at 1 AU,” in *Solar Wind Nine*, S.R. Habbal, R. Esser, J.V. Hollweg, and P.A. Isenberg, Eds. AIP Conference Proceedings 693, Woodbury, NY, 1999).

Mulligan, T., and C.T. Russell, “Multi-Spacecraft Modeling of the Flux Rope Structure of Interplanetary Coronal Mass Ejections: Cylindrically Symmetric versus Non-Symmetric Topologies” (submitted to *J. Geophys. Res.*).

Mulligan, T., “Inversion Studies of Magnetic Cloud Structure at 0.7 AU: Solar Cycle Variation” (submitted to *Geophys. Res. Lett.*).

Newbury, J.A., and S.P. Gary, “Whistler Instabilities in the Solar Wind: Magnetic Fluctuations and Anisotropy Constraints” (submitted to *J. Geophys. Res.*).

Peromian, V., et al., “Intrinsic Self-Adjustment and Variability of the Magnetotail,” in *Proc. of the Fifth International Conference on Substorms* (St. Petersburg, Russia, in press).

Russell, C.T., et al., “Comparison of Three Techniques of Determining the Resonant Frequency of Geomagnetic Pulsations” (submitted to *J. Atmosph. Solar Terr. Phys.*).

Instrumentation and Diagnostics

Advanced Nuclear Measurement Science

98601

Victor Gavron

Future systems for nuclear materials measurement must be capable of assaying nuclear materials that are highly impure, contaminated, heterogeneous, and encased in highly shielding matrices. In this project, we developed the advanced infrastructure of fundamentally new measurement methods and data fusion that will provide these capabilities.

We developed and tested a new scintillator/optical fiber sensor and incorporated it into the newest nuclear safeguards tool for neutron coincidence counting. The new sensor retains the high detection efficiency achieved with previous counters but reduces the dead-time by more than an order of magnitude.

We have also devised computer tools to evaluate neutron tomography as a portable waste assay system. To rapidly solve the forward neutron transport for a large number of trial material distributions within the scanned container, we wrote a versatile neutron transport subroutine in FORTRAN, and benchmarked it against MCNP (Monte Carlo Neutron-Photon transport code).

Our research produced a method to perform nondestructive analysis to determine the material mass of highly enriched uranium (HEU) in heavily shielded systems. This new method uses delayed neutrons from fission products distributed throughout the HEU sample as a source of interrogating neutrons. The fission products are from fission events produced by an external radiation probe of pulsed 14-MeV neutrons.

Working with industrial partners, we designed and produced detectors with record-breaking energy resolution and counting throughput. This work is the foundation of current scientific research on CdZnTe materials and devices that will lead directly to improvements in the design and manufacturing of the next generation of detectors.

We developed data fusion involving the application and development of novel statistical approaches to combining data in order to improve assay methods. Approaches included pattern recognition, multivariate response modeling, methods to reduce bias due to errors in predictors, and a new cross-validation-based method of choosing parameters in biased regression.

We have continued analysis, quantification, and characterization of inventories of fissile materials, in both the military and commercial fuel cycles. This characterization includes weapons-related fissile material waste streams and fissile material of potential weapons use from commercial production.

Publications

Burr, T.L., et al., "Shielding-Related Assay Challenges and Experimental Results in Nuclear Safeguards," *Trans. Am. Nucl. Soc.* **81**, 240 (1999).

Dreicer, J.S., "How Much Plutonium Could Have Been Produced In The DPRK IRT Research Reactor?" *Science and Global Security* **8** (3), 273 (2000).

Hollas, C.L., et al., "Subcritical Neutron Multiplication Measurements of HEU Using Delayed Neutrons as the Driving Source" (Sixth International Conference on Nuclear Criticality Safety, Versailles, France, September 20–24, 1999).

Spall/Ejecta Studies with Proton Radiography

2000520

Mary Hockaday

Characterization of spall development under shock conditions is critical to the development of physics-based weapons performance models for stockpile stewardship. Spall is fracture along a surface when tension from colliding rarefactions (release waves) exceeds the material strength, effectively ripping the material apart. We designed a high-explosive (HE) -driven package to investigate spall in aluminum using proton radiography. Proton radiography is a new technique for investigating material dynamics, and the goal of this project was to study, conduct a demonstration experiment, and analyze the data to determine if proton radiography could be an effective quantitative tool for studying spall. This research provides challenging experimental tests to fundamental models of the processes involved and will help to enrich and sustain Laboratory core competencies in shock-wave physics, high-explosive science, and weapons diagnostics and design.

Before a high-explosive experiment can be fielded at the Los Alamos Neutron Science Center (LANSCE), a high-fidelity explosive test must be performed at a Laboratory Dynamic Experiments (DX) Division firing site. The Cerro Grande fire closed the DX firing sites, preventing us from testing several different spall packages. Therefore, we conducted only one dynamic experiment at LANSCE this year. The HE package tested consisted of a 10.2-cm-diameter by 40-mm-thick “hockey puck” of 9502 HE with a 1.02-cm-thick 6061-T6 aluminum flyer plate attached directly to it.

Traditionally, the diagnostic standard for characterizing spall-layer formation has been the Velocity Interferometer System for Any Reflector (VISAR) technique. We integrated a VISAR system into the proton radiography facility and fielded it on the specially designed HE package. The VISAR worked as anticipated, and the oscillating VISAR data in Fig. 1 shows surface motion characteristic of a spall layer at the fast moving surface. We observed the spall layer itself in the radiographs (see Fig. 2). The unstructured surface velocity and the thickness of the spall layer determined from the multiframe radiographs matched that of the VISAR data. We also performed work towards developing a linear hydrogen ion chamber to track material motion crossing a one-dimensional “slit.” We tested a prototype but did not make a material motion measurement.

Fig. 1. VISAR velocity data. A sine wave of period 0.387 msec can be matched to the oscillations in the VISAR velocity data. Because the sound speed of aluminum is 5.4 mm/msec, this corresponds to a shock wave reflecting back and forth in a 1.1-mm-thick aluminum layer.

Fig. 2. Volume-density proton radiography data from the spall experiment. The upper righthand image is a static taken before detonation. Time increases from the lower left to the right and then up. Time spacing between images is 1.073 msec. The spall layer is visible in all images starting with the third.

Materials Science

Investigation of Spin, Charge, and Lattice Degrees of Freedom in Magnetoresistive Materials

98817

Robert H. Heffner

The ground states of transition metal oxides (TMOs) are extraordinarily interesting, encompassing superconducting, magnetic, insulating, and metallic behaviors. We are studying TMOs exhibiting colossal magnetoresistance (CMR)—a large decrease of electrical resistance on application of an external magnetic field—for two principal reasons. First, the materials are of fundamental scientific interest because conventional theories of magnetic ordering and charge transport do not apply to these materials, which have unusually strong coupling (on the nanometer-length scale) between their lattice, spin, and charge degrees of freedom. Second, a predictive understanding of these systems may enable us to use these materials for applications like magnetic field sensors and data storage. Our goal is to understand the microscopic mechanisms responsible for the macroscopic CMR phenomena by studying the lattice and spin properties of CMR materials primarily using neutron scattering and muon-spin relaxation (μ SR).

This year, we completed a systematic μ SR study of the system $\text{La}_{1-x}\text{Ca}_x\text{MnO}_3$, $x = 0.0, 0.06, 0.18, 0.33, 0.67$, and 1.0 , which spans antiferromagnetic, ferromagnetic, charge-ordered, metallic, and insulating systems. All of the doped manganites except CaMnO display anomalously slow, spatially inhomogeneous manganese spin fluctuation rates below their magnetic ordering temperatures. In particular, for the insulating ferromagnet (FM) $\text{La}_{0.82}\text{Ca}_{0.18}\text{MnO}_3$ and conducting FM $\text{La}_{0.67}\text{Ca}_{0.33}\text{MnO}_3$, we showed that a bimodal distribution of manganese fluctuation rates λ_1 and λ_2 exists in addition to the ordinary spin waves found in homogeneous materials. We hypothesized that the λ_1 Mn rates are due to overdamped spin waves characteristic of a disordered FM and that the λ_2 Mn relaxation rates come from distinct, relatively insulating regions in the sample. We also carried out a series of neutron scattering experiments demonstrating that the intrinsic inhomogeneity of these materials exists on a nanometer-length scale.

Traditionally, solids are treated, to a good approximation, as homogeneous, three-dimensional materials with near-perfect, long-range crystallographic order and linear response. In magnetic materials, this view leads to magnetic order characterized only by long-range collective excitations such as spin waves. The complexity we found in these materials arises from the strong interplay between intrinsic structure on the mesoscale (a few lattice constants) and the charge, spin, and lattice degrees of freedom. This complexity can occur even in nominal single crystals and demands a radical rethinking of conventional approaches to understanding basic materials properties.

Publications

Booth, C.H., et al., “Local Lattice Disorder in the Geometrically Frustrated Spin Glass $\text{Y}_2\text{Mo}_2\text{O}_7$,” *Phys. Rev. B* **62**, R755 (2000).

Gardner, J.S., et al., “Neutron Scattering Studies of the Glass-like Pyrochlore $\text{Y}_2\text{Mo}_2\text{O}_7$ ” (International Conference on Magnetism, Recife, Brazil, August 6–11, 2000).

Heffner, R.H., et al., “Evidence for a Distributed Ferromagnetic Transition in $(\text{La}, \text{Ca})\text{MnO}_3$,” *Physica B* **289–290**, 61 (2000).

Heffner, R.H., et al., “Muon Spin Relaxation Study of $(\text{La}, \text{Ca})\text{MnO}_3$ ” (accepted for publication in *Phys. Rev. B*).

Heffner, R.H., et al., “Observation of Two Time Scales in the Ferromagnetic Manganite $\text{La}_{1-x}\text{Ca}_x\text{MnO}_3$, $x \approx 0.3$,” *Phys. Rev. Lett.* **85**, 3285 (2000).

Self-Assembling Organic Electronic Materials

99503

Alan R. Bishop

A central scientific endeavor of this new century will be understanding the physical principles that govern the relationships between (1) molecular level (microscopic) interactions and self-assembly mesoscopic structures and (2) mesoscopic structure and (macroscopic) electronic functionality in organic electronic and biomolecular materials. These relationships are important for many physical systems, and understanding their governing principles will have important implications in many areas of science and technology.

The goal of our project is to elucidate, control, and exploit these relationships for complex organic materials by understanding (1) the self-assembly processes in macromolecular organic structures and the relationship between mesoscopic structure and electronic functionality, and (2) using this understanding, along with and application of novel molecular synthesis and mesoscale fabrication techniques, to design and build new organic electronic materials. Our project focuses on three critical cross-cutting scientific issues: the fundamental mechanisms of organic self-assembly, the electronic structure and transport properties of organic interfaces, and the dipole alignment in multilayer organic films.

This year we have made progress toward each of our research targets. We have integrated synthesis-characterization modeling teams around classes of organic self-assembling materials, focusing on (a) controlling two- and three-dimensional self-assembly, (b) understanding and using the electronic structure and transport properties of organic heterojunctions, and (c) self-assembly and characterization of photoactive multilayered polar organic superlattices. In particular, we have developed a new theoretical description of charge transport in amorphous organic materials together with the effects of polarons on their optical properties, and provided a quantitative description of organic solid film properties based on molecular level details.

We have also modeled the nonlinear optics of donor/acceptor-substituted conjugated molecules and oligomers. Additionally, we have established new synthetic methods for three-dimensionally assembled organic-inorganic hybrid materials and characterized them with a variety of spectroscopic and thermodynamic methods. Finally, we have patterned surfactant templated silicate thin films via selective UV/ozone exposure.

Publications

Bardeau, J.F., et al., "Spectroscopic Evidence of Bilayer-Micellar Phase Transition in Layered Silver(n-alkane) thiolates," *J. Phys. Chem.*, **104**, 627 (2000).

Bronold, F., et al., "Dynamics of a Single Electron in the Ordered and Disordered Holstein Model" (*Phys. Rev. B*, in press).

Campbell, I.H., et al., "Charge Carrier Effects on the Optical Properties of Poly (p-phenylene vinylene) (submitted to *Phys. Rev. B*).

Campbell, I.H., et al., "Optical Properties of Single Carrier Polymer Diodes under High Electrical Injection" (to be published in *Appl. Phys. Lett.*).

Clark, T. Jr., et al., "A New Application of UV-Ozone Treatment in the Preparation of Substrate-Supported, Mesoporous Thin Films," *Chemistry of Materials* **12**, 3879 (2000).

Crone, B.K., et al., "Device Model Investigation of Bilayer Organic Light Emitting Diodes," *J. App. Phys.* **87**, 1974 (2000).

Kirova, N., et al., "Excitations and Optical Properties of Phenylene-Based Polymers," *Synthetic Materials* **100**, 29 (1999).

Kladko, K., et al., "Universal Scaling of Wave Propagation Failure in Arrays of Coupled Nonlinear Cells," *Phys. Rev. Lett.* **84**, 4505 (2000).

Martin, R.L., et al., "Molecular and Solid-state Properties of tris-(8-hydroxyquinolate)-aluminum," *Phys. Rev. B* **61**, 15804 (2000).

Saxena, A., et al., "CEO/Semiempirical Calculations of Static Nonlinear Polarizabilities in Donor/Acceptor Substituted Molecules" (submitted to *J. Phys. Chem. B*).

Saxena, A., et al., "Optical Nonlinearities in Polyenes: Role of Intrinsic Localized Modes," *Synth. Met.* **116** (2000).

Teber, S., et al., "Solitons and Stripes in Degenerate Broken-Symmetry Ground State Materials" (*J. Phys.: Condens. Matter*, in press).

Tretiak, S., et al., "CEO/Semiempirical Calculations of UV-Visible Spectra in Conjugated Molecules," *Chem. Phys. Lett.* **331**, 561 (2000).

Tretiak, S., et al., "CEO/Semiempirical Electronic Excitations in Poly-phenylenevinylene (PPV)," *Chem. Phys. Lett.* **331**, 561 (2000).

Tretiak, S., et al., "Interchain Electronic Excitations in Poly-Phenylenevinylene Aggregates," *J. Phys. Chem. B* **104**, 7029 (2000).

Wang, W.Z., et al., "Effects of Nonadiabaticity and Disorder on nonlinear Optical Susceptibilities," *Phys. Rev. B* **59**, 1697 (1999).

Weisse, A., et al., "Optimized Phonon Approach for the Diagonalization of Electron-Phonon Problems," *Phys. Rev. B* **62**, R747 (2000).

Yu, Z.G., et al., "Dynamics of Electronic Transport in Metal/Organic/Metal Structures," *J. Phys. Cond. Matt.* **11**, L7 (1999).

Yu, Z.G., et al., "Molecular Geometry Fluctuations and Field-Dependent Mobility in Conjugated Polymers" (*Phys. Rev. B*, in press).

Yu, Z.G., et al., "Molecular Geometry Fluctuation Model for the Mobility of Conjugated Polymers," *Phys. Rev. Lett.* **84**, 721 (2000).

Zhao, S., et al., "Phase Transitions in Self Assembling Monolayers: Constrained Rigid Rods and Symmetry Breaking" (submitted to *Phys. Rev. Lett.*).

Coordinated Synthesis, Characterization, and Modeling of Materials

99507

Don M. Parkin

This project develops both existing and new competencies in materials science through a collaboration between Laboratory staff and external materials scientists that explores new techniques in a variety of areas related to the synthesis, characterization, and modeling of materials. New applications and development of materials synthesis and characterization techniques form the basis for increasing our broad technical capabilities for applying to programmatic activities.

This year the project focused on materials deformation modeling and experimental studies of spall fracture. We created computer-generated models to study the nature of the atomic arrangements in grain boundaries, the transition region between two crystals of the same phase. We also used these models to explore the sliding resistance of grain boundaries. We found that the sliding resistance of grain boundaries is very high but that grain boundary dislocations are responsible for sliding at low stress levels. In addition, some boundaries acquire various configurations. The existence of multiple-grain boundary states has important implications for strength and the temperature dependence of grain boundary properties.

Experiments with the Laser-Driven Miniflyer concentrated on studies of spall fracture in model materials. We completed tests on high-purity cold-rolled copper foil 100 microns thick and annealed high-purity copper targets in thicknesses of 100, 200, or 400 microns. Damage in the two copper alloys was very different. In the cold-rolled copper, voids formed abundantly and were located homogeneously throughout the highly stressed region in the middle of the target thickness. In the annealed copper, void formation was much less frequent, and the voids tended to be larger than those in the cold-rolled material were. No metallurgical features were associated with the location of the void formation.

We conducted additional work with high-purity (99.999%) single crystal copper. Targets 100 microns thick, oriented in the $\langle 100 \rangle$, $\langle 110 \rangle$, or $\langle 111 \rangle$ directions, were impacted with 50-micron-thick cold-rolled copper flyers. Preliminary results have shown that much greater flyer velocities are needed to achieve spall fracture in the single crystal copper, as compared with the polycrystalline annealed or cold-rolled copper materials. The spall strengths of the single crystal material (about 5 GPa) are much greater than those of the polycrystalline materials.

Publications

Alexander, D.J., et al., "Spall Studies in Copper Foils using the Laser-Driven Miniflyer" (EXPLOMET 2000, International Conference on Fundamental Issues and Applications of Shock-Wave and High-Strain-Rate Phenomena, Albuquerque, NM, June 19–23, 2000).

Hoagland, R.G., et al., "On the Strengthening Effects of Interfaces in Multilayer FCC-Metallic Composites" (submitted to *Philos. Mag.*).

Kurtz, R.J., et al., "Computer Simulation of Misfit Dislocation Mobility in Cu/Ni and Cu/Ag Interfaces" (MRS symposium on Structure and Mechanical Properties of Nanophase Materials, Boston, MA, November 27–December 1, 2000).

Misra, A., et al., "Dislocation Models for Strengthening in Nanostructured Metallic Multilayers," in *MRS 2000 Fall Meeting Proceedings* **634**, D. Farkas, et al., Eds. (available online <http://www.mrs.org/publications/epubs/proceedings/fall2000/b/>, 2000).

Mitchell, T.E., et al., "Stacking Fault Energy and Yield Stress Asymmetry Associated with $1/2\langle 331 \rangle$ Dislocations in MoSi₂" (accepted in *Philos. Mag.*).

Mitchell, T.E., et al., "Yield Stress Anomalies, Yield Stress Asymmetry and Dislocation Core structures in Molybdenum Disilicide" (accepted in *Proceedings of International Symposium on Structural Intermetallics*).

Tonks, D.L., et al., "Spallation Strength of Single Crystal and Polycrystalline Copper," *Journal de Physique IV* **10**, Pr9-787 (2000).

Development of Semiconducting Polymeric Films with High Concentrations of Boron

99509

Quanxi Jia

Technology for neutron detection is important and will play an increasing role in the Laboratory's core mission of "reducing the global nuclear danger." Current detection mechanisms rely on neutron-absorbing, gas-filled detectors such as the three helium gas detectors used at LANSCE. Other neutron detection technologies include scintillators (ZnS) and pyroelectric detectors [Pb(Zr,Ti)O₃]. The drawbacks of current technologies are slow response time, sensitivity to radiation, and difficulties encountered in fabrication of large area detectors. In this project, we aimed at developing a new class of neutron detectors based on conductive polymeric films doped with boron compounds. Upon interacting with neutrons, energetic lithium-7 and alpha particles will be created from boron-10 and will yield an induced signal in the form of current or charge accumulation.

To construct such composite films, we prepared optical-quality semiconductive polymer films on oxide substrates (ITO [indium-tin oxide]) with homogenous boron distribution. The composite films have optimized electron/hole transport properties and must be protected with an inert layer of polyvinyl alcohol. The Kelvin probe is an analytical instrument that uses a vibrating capacitor to measure the difference of work functions or the contact potential

difference (CPD) between two surfaces made of metals, semiconductors, or liquid interfaces (see Fig. 1). It is an effective tool for detecting changes in charge properties or surface potential difference at the polymer/ITO interface.

We monitored and measured charge accumulation on surfaces/interfaces of our composite films in situ resulting from neutron radiation. Upon exposure to neutrons, preliminary results show that there is an induced charge accumulation or a change of surface potential (see Figs. 2–3). This response, which can be used as a neutron detector, depends on the level and degree of interaction between neutron and boron in the conductive polymers. We also found that titanium oxide films inserted between boron-doped polymeric layers and conductive substrates enhanced the neutron-induced charge accumulation effects.

We will continue to use the Kelvin probe technique to evaluate materials interfaces for electric properties resulting from neutron radiation or photo-induced effects. In particular, we are interested in response time and sensitivity to the radiation or photo-induced effects.

Publications

Li, A.D.Q., et al., "Structure and Property of Macromolecular Self-Assembly on Oxide Surfaces" (accepted in *Polymeric Materials: Science and Engineering*).

Li, L.S., et al., "Surface Electronic Properties of Self-Assembled, Oppositely Charged Macrocyclic and Polymer Multilayers on Conductive Oxides" (accepted in *J. Phys. Chem.*).

Fig. 1. Schematic of Kelvin probe setup used for neutron detection. The sample is a composite boron-containing thin film, and the probe is made of stainless steel.

Fig. 2. Photo-induced charge separation in a TiO_2/ITO device, measured by Kelvin probe. The characteristics of this device indicate that it is possible to use such structures for photonic detection; therefore, one can tailor such devices for neutron detection.

Fig. 3. Neutron-induced charge accumulation in a device consisting of a multilayered structure of PVA/conducting boron-doped polymer/TiO₂/ITO. Note that charge accumulation or surface potential increases when neutron is turned on and surface potential remains constant while neutron is turned off.

Neutron and Accelerator-Based Science

99519

Daniel Strottman

Our goal is to support critical technology innovations essential to the success of the Laboratory's efforts in neutron science and to the Los Alamos Neutron Science Center (LANSCE). The project has two primary thrusts: The development of the Device for Advanced Neutron Capture Experiments (DANCE), and the development of the IN500 spallation source for cold neutron spectroscopy.

During the second year of this project, we made progress in each of the thrust areas of the proposal; progress was significantly less than anticipated because of the reduction by two in the funding.

We continued design work for the inelastic scattering instrument. Conceptual designs have been presented for a repetition rate multiplying chopper system and for much improved methods of beam extraction and beam delivery. We have produced simulations for the chopper system and the beam delivery system.

Work on DANCE has progressed rapidly. For the proposed array, we completed very extensive simulations of the background resulting from neutron scattering off the shielding and frame. These simulations required a new design using larger crystals than originally envisaged. We completed the construction of the frame with these larger crystals (see Figs. 1 and 2). We also purchased prototype BaF_2 crystals and tested them for signal response and timing. After choosing the supplier, we began negotiating for delivery of the crystals. We then purchased all required photomultiplier tubes. Design of the shielding on the new flight path is complete, and we have ordered prototypes for suitability testing. We have installed a shutter on flight path 14, paving the way for testing during the coming year.

In the past year we also developed an analysis technique that allows us to determine phonon dispersion relations from powder diffraction data. This technique relies on a sophisticated modeling of the lattice dynamics. We have extended our previous work, which was restricted to one-phonon processes only, to include all multiphonon processes in the quasi-harmonic approximation. We investigated the role of powder averaging in detail, with the surprising result that the common assumption of Gaussian peaks in a pair density function is wrong.

Publications

Mezei, F., and M. Russina, "Neutron Beam Extraction and Delivery at Spallation Neutron Sources" (*Physica B*, in press).

Mezei, F., and M. Russina, "Novel TOF Chopper System Design Concept Based on a Filtering Principle," in *Hercules Conference Proceedings* (Grenoble, April 2000, to be published).

Mezei, F., et al., "The Multiwavelength Cold Neutron Time-of-Flight Spectrometer Project IN500," *Physica B* **276**, 128 (2000).

Russina, M., et al., "Experimental Evidence for Fast Heterogeneous Relaxation in a Supercooled Liquid," *Phys. Rev. Lett.* **86**, 3630 (2000).

Fig. 1. The completed DANCE ball and supporting frame. Each of the 162 holes will ultimately house a BaF_2 crystal and photomultiplier tube.

Fig. 2. A close-up of the stainless steel DANCE ball showing the interconnecting parts that allow easy disassembly for maintenance or replacement of crystals.

Static and Dynamic Electronic Response of Actinide Single Crystals in Magnetic Fields

2000503

Antoinette J. Taylor

In this project, complementary experimental and theoretical approaches probe the response of 5f-electrons in magnetic fields. Two experimental techniques use the pulsed fields of the National High Magnetic Field Laboratory (NHMFL), focusing on the Fermi surface parameters as well as the effective electron masses of actinides. We build on techniques pioneered in a previous thrust and focus now primarily on transuranics. We also use femtosecond dynamics to gain insight into the nature of the electron-electron correlations that may cause significant deviations from the single particle approach. Our ultimate goal is determining and understanding the electronic structure of δ -Pu because the band structure is a significant starting point in the determination of the equation of state. Toward this end, one theoretical approach focuses on the traditional band calculations, whereas a second approach attempts to understand additional terms not included in band structure.

This year we have grown single crystals of PuIn_3 , PuSn_3 , and PuGa_3 . They are the first single crystals of Pu intermetallic compounds grown at Los Alamos in over 20 years. These crystals have already been employed in photoemission measurements using the Los Alamos Laser Plasma Light Source and de Haas van Alphen (dHvA) measurements here at the NHMFL. Unfortunately, the dHvA measurements were unsuccessful because of excess sample aging that occurred as a result of the Cerro Grande fire. However, we were able to demonstrate that our sample transportation and encapsulation methods were adequate for these measurements. We also performed dHvA measurements on CeRhIn_5 , a new heavy fermion compound, and we performed detailed comparisons with band structure calculations. Future dHvA measurements on Pu compounds will enable such comparisons.

In the area of femtosecond dynamism, we performed the first transient reflection measurements on a series of heavy fermion UX_3 compounds; we observed an initial ultrafast cooling of the hot carriers followed by renormalization of the hot carriers into the intermediate-valence state. We have also performed the first ultrafast carrier dynamics measurements in colossal magnetoresistance manganites, where we measured a temperature-dependent spin-lattice relaxation time of 10–100 ps in these materials and a thermal to magnetic energy scaling factor of 13.

Publications

Averitt, R.D., et al., “Nonequilibrium Superconductivity and Quasiparticle Dynamics in $\text{YBa}_2\text{Cu}_3\text{O}_{7-d}$ ” (accepted in *Phys. Rev. B Rapid Comm.*).

Averitt, R.D., et al., “Ultrafast THz Conductivity Dynamics: Spin-Lattice Relaxation in Colossal Magnetoresistive Oxides,” in *Ultrafast Phenomena VII*, T. Elsaesser, et al., Eds. (Springer-Verlag, Berlin, 2000), p. 434.

Cornelius, A.L., et al., “Anisotropic Electronic and Magnetic Properties of the Quasi-Two-Dimensional Heavy-Fermion Antiferromagnet CeRhIn_5 ,” *Phys. Rev. B* **62**, 14181 (2000).

Jaime, M., et al., “Heat Capacity Measured up to 60 T in $\text{Ce}_3\text{Bi}_4\text{Pt}_3$ Kondo Insulator,” *Physica B* **280**, 563 (2000).

Lobad, A.I., et al., “Laser-Induced Dynamic Spectral Weight Transfer in $\text{La}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$,” *Chem. Phys.* **251**, 227 (2000).

Lobad, A.I., et al., “Spin-Lattice Interaction in Colossal Magneto-Resistance Manganites,” *Appl. Phys. Lett.* **77**, 4025 (2000).

Lobad, A.I., et al., “Ultrafast Dynamics of the Heavy State in UX_3 Compounds” (*Quantum Electronics and Laser Science Conference 2000*, San Francisco, CA, May 7–12, 2000).

Lobad, A.I., et al., “Ultrafast Dynamics of the Spin-Lattice Relaxation in $\text{La}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$: Magnetic Field Dependence” (accepted in *Phys. Rev. B Rapid Comm.*).

Siders, J.L., et al., “Terahertz Emission from $\text{YBa}_2\text{Cu}_3\text{O}_{7-d}$ Thin Films via Bulk Electric Quadrupole/Magnetic Dipole Optical Rectification,” *Phys. Rev. B* **61**, 13633 (2000).

Thorsmolle, V.K., et al., “Observation of the Josephson Plasma Resonance in $\text{Tl}_2\text{Ba}_2\text{CaCu}_2\text{O}_8$ using THz Spectroscopy,” in *Ultrafast Phenomena VII*, T. Elsaesser, et al., Eds. (Springer-Verlag, Berlin, 2000) p. 431.

Understanding and Predicting Behavior of Polymeric Materials with Time

2000504

Edward M. Kober

Polymer-based materials are widely used throughout DOE, DoD, and industry. Two particular applications in nuclear weapons are as the binders for high explosives and as cushions. Such materials are particularly susceptible to chemical and physical aging processes, and this could lead to a degradation of system performance. The goal of this program is to develop physically-based models for these materials, where aging and time-dependent behavior are explicitly and accurately described. One aspect of this project is to develop and apply novel experimental techniques that can quantify time-dependent changes in properties and composition. Another aspect is to develop multiscale modeling techniques that explain these changes and develop continuum level models from them.

The first class of materials being studied is a polyester-polyurethane segmented block copolymer system. These are thermoplastic materials that undergo a time-dependent microphase separation that controls their structural properties. We have synthesized members of this class with controlled (and varied) composition and molecular weight, and these have also been hydrolytically degraded. The dependence of mechanical properties upon each of these factors has been measured. With surface force microscopy (SFM), we have demonstrated that the morphology of the phase-separation process is highly dependent upon sample preparation, and this accounts for many discrepancies in earlier analyses (see Fig. 1). Time-dependent infrared (IR) and small angle neutron scattering (SANS) have been used to quantify the rate and extent of the phase separation process, and to relate this to the change in strength properties. A mean-field model for diblock copolymer systems has been extended to these segmented systems, and verified by comparison with more intensive, explicit simulations (see Fig. 2). A first-pass continuum model has been developed that includes this information about the phase-separation process.

A second class of materials being studied is cross-linked polydimethylsiloxanes that contain a silica filler. We have demonstrated that solid-state nuclear magnetic resonance and IR measurements can measure time-dependent changes in the silica-polymer system. We have developed both explicit simulations and mean-field approaches to characterize the polymer-surface interaction. A preliminary continuum model based on homogenization techniques has been developed that can fit the measured strength properties.

Publications

Chitanvis, S.M., "Elementary Approach to Self-Assembly in Random Copolymers," *Mat. Res. Soc. Symp. Proc.* **661**, 2000 (to be published).

Chitanvis, S.M., "Physics of Polymer Melts" (submitted to *Phys. Rev. E*).

Cooke, D.W., et al., "X-Ray-Induced Thermally Stimulated Luminescence and Electronic Processes in a Segmented Poly(Ester Urethane)," *Radiat. Phys. Chem.* **58**, 29 (2000).

Graff, D.K., et al., "Static and Dynamic FT-IR Linear Dichroism Studies of Plasticization Effects in a Polyurethane Elastomer," *Macromolecules* **32**, 7147 (1999).

Hanson, D.E., "A Mesoscale Strength Model for Silica-Filled Polydimethylsiloxane Based on Atomistic Forces Obtained from Molecular Dynamics Simulations," *J. Chem. Phys.* **113**, 7656 (2000).

Hawley, M.E., et al., "Comprehensive Structural Study of Pre- and Post-Heat Treated Compression Molded Polyurethane Samples of Varying Composition Studied by Scanning Probe Techniques," *Mat. Res. Soc. Symp. Proc.* **661**, 2000 (to be published).

Johnson, J.N., and J.J. Dick, "Spallation Studies in Estane," in *Shock Compression of Condensed Matter*, M.D. Furnish, L.C. Chhabildas, and R.S. Hixson, Eds. (AIP, Woodbury, NY, 2000), p. 543.

Ponomarev, A.L., et al., "Adsorption of Isolated, Flexible Polymers onto a Strongly Attracting Surface," *Macromolecules* **33**, 2662 (2000).

Ponomarev, A.L., et al., "Surface Diffusion and Relaxation of Partially Adsorbed Polymers," *J. Polym. Sci. Part B: Polym. Phys.* **38**, 1146 (2000).

Rasmussen, K.O., et al., "Mean Field and Monte Carlo Modeling of Multiblock Copolymers," *Mat. Res. Soc. Symp. Proc.* **661**, 2000 (to be published).

Schoonover, J.R., et al., “A Polymer Degradation Study by Factor Analysis of GPC-FTIR Data” (to be published in *Appl. Spectrosc.*).

Schoonover, J.R., et al., “Static and Dynamic Infrared Linear Dichroism Study of Changes in Tensile Properties of a Hydrolyzed Poly(Ester Urethane)” (submitted to *Polym. Degrad. Stab.*).

Wang, H., et al., “DMA-FTIR Creep-Recovery Study of a Poly(Ester Urethane) Elastomer with Molecular-Level Viscoelastic Modeling” (submitted to *Macromolecules*).

Wang, H., et al., “Temperature Dependent Dynamic Mechanical Analysis-Fourier Transform Infrared Study of a Poly(Ester Urethane) Copolymer” (submitted to *Appl. Spectrosc.*).

Fig. 1. Surface Force Microscopy images ($2.5\text{ mm} \times 2.5\text{ mm}$) of poly(ester urethane) samples before (column 1) and after (column 2) a thermal treatment. Samples had different amounts of urethane: (a) 57%, (b) 36%, and (c) 30%. The white regions are pure urethane regions whose distribution is highly dependent on composition and treatment.

Fig. 2. Comparison of calculated scattering functions, $S(q)$, from an approximate mean-field approach and an explicit bond fluctuation simulation for multiblock copolymer systems of the type $[A_m B_n]_p$ showing very good agreement. Dotted lines $p=1$ (diblock); dashed $p=3$; dash-dot $p=5$; solid $p=6$. This verifies and quantifies parameters used in the mean-field treatment.

A Scaleable Silicon-Based Nuclear Spin Quantum Computer

2000510

P.C. Hammel

For certain problems in which quantum superposition can result in massive parallelism, a quantum computer (QC) is much more powerful than any conventional computer. A colleague recently presented a realistic and well-thought-out proposal for a silicon-based QC with a highly scaleable architecture. To test this proposal, we are using our established quantum computing and nanofabrication expertise to build a two-qubit QC.

The exceptional computational capabilities of a two-qubit QC would be crucial to national security because of the ability of such a computer to factor large numbers. Los Alamos leads in the field of quantum computation; our research will allow us to play a major role in the next century's revolution in computation.

We are addressing the experimental challenges this project presents, including the ability to fabricate the phosphorus array with atomic-precision on the surface of silicon, using a monohydride layer as a mask that is patterned by applying a current from a scanning tunneling microscope (STM) tip. Another challenge is to create a quantum bit readout by means of a single-spin magnetic resonance force microscope (MRFM).

Through extensive collaboration with our Australian partners, we have developed techniques for silicon surface preparation and monohydride deposition. A variable-temperature, ultrahigh-vacuum STM has been installed and commissioned at Los Alamos. Our MRFM capabilities have been enhanced through (1) the development of hardware employing unique magnetic probe tips and microwave sources for the excitation of electron paramagnetic resonance and (2) the acquisition of electron paramagnetic resonance signals from phosphorus-doped silicon. Theoretical exploration of single-spin detection and alternative computation schemes are under way.

Publications

Berman, G.P., and V.I. Tsifrinovich, "Modified Approach to Single-Spin Detection Using Magnetic Resonance Force Microscopy," *Phys. Rev. B: Condens. Matter* **61**, 3524 (2000).

Berman, G.P., et al., "A Magnetic Resonance Force Microscopy Quantum Computer with Tellurium Donors in Silicon" (submitted to *Phys. Rev. Lett.*).

Berman, G.P., et al., "Dynamics of Nuclear Spin Measurement in a Mesoscopic Solid-State Quantum Computer," *J. Phys.: Condens. Matter* **12**, 2945 (2000).

Berman, G.P., et al., "Solid-State Nuclear-Spin Quantum Computer Based on Magnetic Resonance Force Microscopy," *Phys. Rev. B: Condens. Matter* **61**, 14694 (2000).

Berman, G.P., et al., "Solid-State Quantum Computation—A New Direction for Nanotechnology," *Superlattices Microstruct.* **27**, 89 (2000).

Berman, G.P., et al., "The Static Stern-Gerlach Effect in Magnetic Force Microscopy" (submitted to *Phys. Rev. Lett.*).

Kwiat, P.G., et al., "Demonstration of Entanglement Distillation and Purification" (submitted to *Nature*).

Kwiat, P.G., et al., "Experimental Verification of Decoherence-Free Subspaces," *Science* **290**, 498 (2000).

Organizing Principles across Classes of Complex Electronic Materials

2000511

Joe D. Thompson

Apparently diverse classes of complex electronic materials exhibit common physical properties that cannot be described by conventional concepts in condensed matter physics. In each of these classes, competing interactions produce intrinsic electronic and structural inhomogeneities that might be expected if these materials are close to a zero-temperature phase transition, that is, a quantum-critical point.

Using a closely coupled synthesis, characterization, and modeling strategy, our goal is to establish the essential new physics underlying the common behaviors of these materials. This research will provide a scientific basis to predictively control properties of these complex electronic materials for future civilian and defense technologies.

This year we have made several important discoveries among which the most notable are the following. (1) We have discovered a new family of dimensionally tunable materials that hold substantial promise for bridging our understanding of behaviors common to three-, two-, and one-dimensional complex electronic materials near a quantum-critical point. This has been an extremely exciting development that has received much of our attention this year and will continue to do so for the coming year. (2) We have developed a quite general theoretical model of competing electronic interactions out of which naturally comes intrinsic electronic and structural inhomogeneity and the existence of a quantum-critical point. (3) We have provided unequivocal evidence for intrinsic spin-charge-lattice inhomogeneity in two-dimensional copper-oxide materials. (4) We have established a theoretical basis and additional strong experimental evidence for an empirical relationship between magnetic discommensuration and the superconducting transition temperature in classes of cuprate superconductors. This relationship commonly has been used to argue for the intimate role of inhomogeneity in high-temperature superconductivity.

Publications

Balatsky, A.V., "Superconductivity: from Obscurity to Impurity," *Nature* **403**, 635 (2000).

Balatsky, A.V., et al., "Collective Mode in Unconventional Superconductors" (to be published in *Proceedings of the International Conference on Materials and Mechanisms of Superconductivity—IV* (Houston, 2000)).

Bao, W., et al., "Incommensurate Magnetic Structure of CeRhIn_5 " (to be published in *Phys. Rev. B*).

Chakravarty, S., et al., "Hidden Order in the Cuprates" (submitted to *Phys. Rev. B*).

Cornelius, A.L., et al., "Anisotropic Electronic and Magnetic Properties of the Quasi-Two-Dimensional Heavy-Fermion Antiferromagnet CeRhIn_5 " (to be published in *Phys. Rev. B*).

Curro, N.J., et al., "Evidence for Spiral Magnetic Order in the Heavy Fermion Material CeRhIn_5 ," *Phys. Rev. B* **62**, R6100 (2000).

Eroles, J., et al., "Microscopic Scenario for Striped Superconductors" (to be published in *Physica C*).

Graf, M.J., and A.V. Balatsky, "Identifying the Pairing Symmetry in the Sr_2RuO_4 Superconductor," *Phys. Rev. B* **62**, 9697 (2000).

Graf, M.J., and D.W. Hess, "Antiferromagnetic Domains and Superconductivity in UPt_3 " (submitted to *Phys. Rev. B*).

Graf, M.J., et al., "Identification of the Orbital Pairing Symmetry in UPt_3 " (submitted to *Phys. Rev. B*).

Martin, I., and A.V. Balatsky, "Visualizing the Particle-Hole Dualism in High-Temperature Superconductors" (submitted to *Nature*).

Martin, I., et al., "Striped superconductors in the extended Hubbard model" (submitted to *Nature*).

Morr, D.K., "Spin-Lattice Relaxation in the Mixed State of the High- T_c Cuprates: Electronic Spin-Flip Scattering versus Spin-Fluctuations" (submitted to *Phys. Rev. B*).

Morr, D.K., and A.V. Balatsky, "Proximity Effects and Quantum Dissipation in the Chains of $\text{YBa}_2\text{Cu}_3\text{O}_{6+x}$ " (submitted to *Phys. Rev. Lett.*).

Morr, D.K., and D. Pines, "Magnetic Coherence as a Universal Feature of Cuprate Superconductors" (submitted to *Phys. Rev. B*).

Pagliuso, P.G., et al., “Crystal-Field Induced Magnetic Frustration in Nd-based Antiferromagnets” (to be published in *Phys. Rev. B*).

Petrovic, C., et al., “A New Heavy-Fermion Superconducting Prototype CeIrIn₅: Relative of the Cuprates?” (submitted to *Europhys. Lett.*)

Thompson, J.D., et al., “Superconductivity and Magnetism in a New Class of Heavy-Fermion Materials,” (*J. Magn. Magn. Mater.* in press).

Westfahl, H., Jr., and D.K. Morr, “Theory for the Spin-Susceptibility in the Pseudo-Gap Regime of the Underdoped Cuprates: Effect of Phase Fluctuations,” *Phys. Rev. B* **62**, 5891 (2000).

Mathematics, Simulation, and Modeling

Discrete Simulation of Nonlinear Systems

98805

Shiyi Chen

The goal of our project was to develop discrete numerical methods for modeling multiscale physical phenomena in nonlinear systems. The underlying techniques included the kinetic lattice-Boltzmann method, dissipative particle dynamics, and molecular dynamics. These discrete particle methods were applied to problems in complex fluids, soft condensed matter (granular materials, vesicles, colloids, nanotribology), and multiphase fluid flows in porous media. The simulation results were compared with theoretical predictions from cycle expansions and renormalized perturbation schemes. We expect that the numerical tools we are developing will provide insight into physics from the microscopic to macroscopic scale.

To simulate granular materials, we used the C++ programming language to develop a two-dimensional, event-driven, hard-sphere molecular dynamics code to simulate dissipative particle dynamics. By studying collapsing dynamics with the code, we found that two-dimensional energy decay in a granular medium can be accurately described by the two-dimensional Burgers equation, similar to our previous work in a one-dimensional granular medium. We also observed the high-density regions we predicted for two-dimensional granular media simulations. (See Fig. 1).

We made considerable progress in understanding how to model the spread of infectious diseases and estimate the impact that control measures can have on their spread. Modeling can reduce the uncertainty of the estimates of disease propagation and help us better understand the mechanisms of diseases and epidemics. Our results will help researchers estimate the benefits and costs of projected interventions and project the requirements that an epidemic will place on the health care system.

We modified our nonlinear systems model to include additional terms, such as third-order dispersion and Raman scattering, to describe femtosecond pulse propagation in optical fibers. By implementing and using this new model, we observed the oscillation of the full width at half maximum and the frequency shift of the pulse with respect to the energy. We found excellent agreement when comparing the numerical results with experiments carried out at Los Alamos.

We also developed a new lattice-Boltzmann method to model cavity flows in micro-electro-mechanical devices. We found that the velocity, vorticity, and pressure distributions strongly depart from the classic results as the Knudsen number increases.

Fig. 1. A two-dimensional simulation showing many high-density regions that we predicted for granular media. This snapshot shows the clustering effects for 250,000 particles after 30,000 time steps.

Probabilistic and Combinatorial Analysis for Biological Systems

98806

David C. Torney

Mathematical methods are becoming increasingly important in several biological arenas such as genomics research and countermeasures for biological warfare, particularly in light of the plethora of molecular-biological data. The combinatorial aspects of genetics and biological sequences mandate the development of new mathematical methods.

We developed methods for combinatorial and probabilistic modeling of HIV strain development. After HIV infection, the amount of virus in a person's blood peaks; then, within a few months, it settles down to a constant level (set point) that is maintained for many years. What determines the set-point level of the virus is unknown. This year, we have been exploring the possibility that CD8+ T cells control the amount of virus that infected cells produce—and hence the set point. In SIV-infected monkeys, we have been able to deplete CD8+ T cells and show that the amount of virus then rises between 10- and 1000-fold. To explain the kinetics of this increase, we have developed models indicating some of the increase may be due to a soluble factor CD8+ T cells secrete that may directly block virus production. In addition, because CD8+ T cells are able to kill virus-producing cells, the lifespans of these cells are shortened and the amount of virus they produce is reduced.

Turning to biologically motivated combinatorics, we investigated some systems of linear algebraic equations whose solutions comprise combinatorial designs of classical types. Although these systems are conceptually straightforward, they are difficult to solve because, asymptotically, they involve too many unknowns. Steiner systems, for instance, involve one (0,1)-binary unknown for each of the k -subsets of the ground set (unknowns designating the design's blocks). Thus, we developed other algebraic systems yielding the same classes of designs; systems of quadratic equations, with a modest number of unknowns, were shown to yield these designs. We derived equivalent linear systems, following Wengrzik, to facilitate the solution of these systems. These systems involve equalities and inequalities and comprise only a modest number of (0,1)-binary unknowns.

Also, motivated by the Bayesian analysis of biological sequences, we have enumerated the nonisomorphic Euler multigraphs with small numbers of edges and no loops. For one to ten edges, these numbers are 0, 1, 1, 4, 4, 15, 22, 68, 131, and 376 respectively.

Publications

Chen, W. Y.-C., and D.C. Torney, "On Equivalence Classes of Matchings and Constructed Designs" (submitted to *Discr. Appl. Math.*).

Detours, V., and A.S. Perelson, "The Paradox of Alloreactivity and Self MHC Restriction: Quantitative Analysis and Statistics," *Proc. Natl. Acad. Sci. USA* **97**, 8479 (2000).

Detours, V., et al., "A Quantitative Theory of Affinity-Driven T Cell Repertoire Selection," *J. Theoret. Biol.* **200**, 389 (1999).

Detours, V., et al., "Deriving Quantitative Constraints on T Cell Selection from Data on the Mature T Cell Repertoire," *J. Immunol.* **164**, 121 (2000).

D'yachkov, A.G., and D.C. Torney, "On Similarity Codes," *IEEE Transactions on Information Theory* **46**, 1558 (2000).

Erdos, P.L., et al., "A Finite Word Poset" (accepted in *Elec. J. of Combinatorics*).

Metzner, K.J., et al., "Effects of in vivo CD8+ T Cell Depletion on Virus Replication in Rhesus Macaques Immunized with a Live, Attenuated Simian Immunodeficiency Virus Vaccine," *J. Exp. Med.* **191**, 1921 (2000).

Torney, D.C., "Bayesian Analysis of Binary Sequences" (submitted to *Adv. Appl. Math.*).

Torney, D.C., "Binary Cumulants," *Adv. Appl. Math.* **25**, 34 (2000).

Torney, D.C., and J. Wang, "Systems of Linear Congruences with Individual Moduli," *Linear Algebra and its Applications* **318**, 195 (2000).

Nonlinear Complex Phenomena

99508

Hans Frauenfelder

Work under this project has been proceeding in four areas with a common theme of nonlinear complexity: (1) nonlinear and stochastic dynamics; (2) nonequilibrium statistical physics; (3) energy landscape, dynamics, and function of proteins; and (4) multiscale phenomena in electronic and structural materials.

In nonlinear and stochastic dynamics, we have developed a new modeling scheme for turbulence called the Navier-Stokes-alpha (NS-alpha) model that captures the large-scale features of turbulence without having to compute the ever-smaller scales produced in a turbulent cascade. The solutions of the NS-alpha model describe the Eulerian mean turbulent motion. Its steady-state solutions agree well with experimental data for the mean velocity profile, even at the highest available Reynolds numbers for turbulent pipe flows.

In nonequilibrium statistical physics, we showed that, for a coupled lattice-map-model nonequilibrium system, we could recover statistical descriptions of the dynamics consistent with equilibrium statistical mechanics through a coarse graining approach. Second, we computed the chaotic dynamics of a real physical experiment and determined the mechanism for the chaotic dynamics. This idea has applicability in powerful new approaches to weather prediction by taking into account the spatial sensitivity of a chaotic system. Finally, we investigated vertically vibrated granular chains, which act like long-chain polymers. The diffusion of knots on a chain proved amenable to experimental characterization and theoretical analysis.

We discovered the myoglobin protein may actually be the prototype of a multifunction protein involved in protein networks crucial for understanding proteomics. Nearly all protein research has been directed towards understanding the function of individual proteins. Recently, it has become clear that proteins cooperate in protein networks, and it is important to understand the effect of protein-protein interactions on the function of individual proteins.

We used a combination of nonlinear and nonequilibrium analytical and numerical methods to probe the origins, signatures, and consequences of multiscale structure and dynamics in complex materials. In particular, we have studied models of complex electronic, optical, magnetic, and structural materials. Our studies emphasized (1)

competitions of short- and long-range interactions in hard and soft, organic, inorganic, and biological materials; (2) materials deformation and failure mechanisms, including friction and elasticity; and (3) nonlinear mechanisms for energy and charge localization and transport in discrete, polarizable matter.

This work proceeds rapidly through the synergism of these efforts—all of them involve similar aspects of fundamental physics in the analysis of complex, nonlinear systems.

Publications

Allen, J.S., et al., "Toward an Extended-Geostrophic Euler-Poincaré Model for Mesoscale Oceanographic Flow" (accepted in the Proceedings of the Issac Newton Institute Programme on the Mathematics of Atmospheric and Ocean Dynamics, Cambridge University Press).

Berman, G., et al., "Dynamical Stability of an Ion in a Linear Trap as a Solid-State Problem of Electron Localization" (accepted in *Phys. Rev. A*).

Bloch, A.M., et al., "An Optimal Control Formulation for Inviscid, Incompressible, Ideal Fluid Flow" (39th IEEE Conference on Decision and Control, Sydney, Australia, December 12–15, 2000).

Chu, K., et al., "Structure of a Ligand-Binding Intermediate in Wild-Type Carbonmonoxy Myoglobin," *Nature* **403**, 921 (2000).

Daruka I., et al., "Molecular Dynamics Simulations of the Surface Stress Distribution in Stacked Quantum Dot Systems," *Phys. Rev. B* **60**, R2150 (1999).

Domaradzki, J.A., and D.D. Holm, "Navier-Stokes-alpha Model: LES Equations with Nonlinear Dispersion" (accepted in Special LES volume of ERCOFTAC Bulletin).

Egolf, D.A., "Equilibrium Regained: From Nonequilibrium Chaos to Statistical Mechanics," *Science* **287**, 101 (2000).

Egolf, D.A., et al., "Mechanisms of Extensive Spatiotemporal Chaos in Rayleigh-Bernard Convection," *Nature* **404**, 733 (2000).

Fehske, H., and A. Bishop, "Local Mode Behavior in Quasi-One-Dimensional Charge-Density-Wave Systems," *Physica B* **281**, 673 (2000).

Foias, C., et al., "The Navier-Stokes-alpha Model of Fluid Turbulence" (accepted in *Physica D*).

Frauenfelder, H., and B.H. McMahon, "Energy Landscape and Fluctuations in Proteins," *Annalen der Physik* **9**, 655 (2000).

- Frauenfelder, H., and H.J. Borschberg, "Towards a New Synthetic Entry into the Iboga-Alkaloid Family," *Helvetica Chimica ACTA* **83**, 1753 (2000).
- Fringer, O., and D.D. Holm, "Integrable vs Nonintegrable Geodesic Soliton Behavior" (accepted in *Physica D*).
- Gaididei, Y., et al., "Energy and Charge Localization in Pumped Systems" (accepted in *Phys. Rev. B*).
- Gaididei, Y., et al., "Switching Between Different Vortex States in 2-Dimensional Easy-Plane Magnets due to an ac-Magnetic Field," *Phys. Rev. B* **61**, 9449 (2000).
- Holm, D.D., et al., "Euler-Poincaré Equations in Geophysical Fluid Dynamics" (accepted in the Proceedings of the Isaac Newton Institute Programme on the Mathematics of Atmospheric and Ocean Dynamics, Cambridge University Press).
- Kawabata, C., et al., "Critical Temperature and Critical Current of 3D Anisotropic Josephson Junction Arrays," *J. Phys. Soc. Jpn* **69**, 194 (2000).
- Kevrekides, P., et al., "Localized Excitations and Their Thresholds," *Phys. Rev. E* **61**, 4652 (2000).
- Kevrekides, P., et al., "Parametric Quantum Resonances in Bose-Einstein Condensates," *J. Low Temp. Phys.* **120**, 205 (2000).
- Kevrekides, P., et al., "Propagation Failure, Universal Scalings, and Goldstone Modes" (accepted in *Phys. Lett. A*).
- Kevrekides, P., et al., "Twisted Localized Modes" (accepted in *Phys. Rev. E*).
- Kevrekidis, P., et al., "Two-Dimensional Discrete Breathers: Construction, Stability, and Bifurcations," *Phys. Rev. E* **61**, 2006 (2000).
- Kladko, K., et al., "Intrinsic Localized Modes in the Charge-Transfer Solid PtCl₁," *J. Phys. Condensed Matt.* **11**, L415 (1999).
- Kladko, K., et al., "Universal Scaling of Wave Propagation Failure in Arrays of Coupled Nonlinear Cells," *Phys. Rev. Lett.* **84**, 4505 (2000).
- Lookman, T., et al., "Signatures of Long-Range Elastic Interaction in Textured Materials," *Phys. Rev. B* **82**, 5265 (2000).
- McMahon, B.H., et al., "Density Functional Theory Calculation of Barrier to Ligand Binding in Myoglobin," *Biophys. J.* **76**, A23 (1999).
- McMahon, B.H., et al., "Microscopic Model of Carbon Monoxide Binding to Myoglobin," *J. Chem. Phys.* **113**, 6831 (2000).
- McMahon, B.H., et al., "Structure/Dynamics/Function Relationship in Myoglobin," *Biophys. J.* **78**, P1671 (2000).
- Mitkov, I., et al., "Localized Structures in Nonlinear Lattices with Diffusive Coupling and External Driving," *Phys. Rev. E* **61**, 1106 (1999).
- Muller, J.D., et al., "Connection Between the Taxonomic Substates and Protonation of Histidines 64 and 97 in Carbonmonoxy Myoglobin," *Biophys. J.* **77**, 1036 (1999).
- Raghavan, S., et al., "Dynamic Localization in Spin Systems," *Phys. Rev. B* **61**, 5864 (2000).
- Roeder, J., et al., "Locked-to Running Transition in the 2-Dimensional Underdamped Driven Frenkel-Kontorova Model" (accepted in *Phys. Rev. E*).
- Sanchez, A., et al., "Roughening and Superroughening in the Ordered and Random Two-Dimensional Sine-Gordon Models," *Phys. Rev. E* **62**, 3219 (2000).
- Schnitzer, H.J., et al., "A Collective-Variable Theory for Nonlinear Coherent Excitations in Classical Hamiltonian Systems," *Physica D* **141**, 261 (2000).
- Stojkovic, B., et al., "Charge Ordering and Long-Range Interactions in Layered Transition Metal Oxides: A Quasiclassical Continuum Study," *Phys. Rev. B* **62**, 4353 (2000).
- Tretiak, S., et al., "CEO/Semiempirical Calculations of UV-Visible Spectra in Conjugated Molecules," *Chem. Phys. Lett.* **331**, 561 (2000).
- Tretiak, S., et al., "CEO/Semiempirical Calculations of Static Nonlinear Polarizabilities in Conjugated Molecules" (accepted in *J. Chem. Phys.*).
- Tretiak, S., et al., "Interchain Electronic Excitations in Poly-Phenylenevinylene Aggregates," *Phys. Chem. B* **104**, 7029 (2000).
- Tsironis, G., et al., "Dependence of Thermal Conductivity on Discrete Breathers in Lattices," *Phys. Rev. E* **60**, 6610 (1999).
- Tsironis, G., et al., "Soliton-Breather Reaction Pathways," *Phys. Rev. E* **60**, 7618 (1999).
- Vanossi, A., et al., "Spontaneous Pattern Formation in Driven Nonlinear Lattices," *Phys. Rev. E* **62**, 7353 (2000).
- Voulgarakis, N., et al., "Multiquanta Breather Model for PtCL" [accepted in *Phys. Rev. B (Rapid Comm.)*].
- Weisse, A., et al., "Optimized Phonon Approach for the Diagonalization of Electron-Phonon Problems," *Phys. Rev. B* **62**, R747 (2000).

Fig. 1. A cross section through myoglobin with a heme group and its central iron atom, where small molecules such as O₂, CO, and NO can bind. Also shown are four cavities, denoted by Xe1 to Xe4. These cavities appear not to be random dislocations, but custom-made entities. Twenty-five years of previous work suggests that Mb is not only a storage system but a miniature chemical reactor. The heme iron is the reaction center where one reactant can be bound, the Xe1 cavity the place where the second reactant can be stored. The heme can act as a controlling gate, and the reaction occurs in the heme cavity.

Quantifying and Reducing Uncertainty in Predictions of Complex Phenomena

99512

David H. Sharp

Current and future DOE missions will increasingly rely on large-scale simulations for scientific input to high-impact decisions about stockpile stewardship, global climate change, energy, environmental remediation, and similar complex problems. Because the cost of mistakes can be very high, decision-makers will insist that simulations come with rigorous estimates of levels of accuracy, limits of applicability, and other measures that ensure the integrity and reliability of the answer. Our objective is to develop and validate methods for reaching these goals. In addressing this problem in a real-world weapons physics context, we are conducting a high-risk, high-payoff project that requires the highest level of science of which the Laboratory is capable.

Uncertainties affecting simulations arise from incomplete or insufficiently accurate models, errors in input data, and errors that result from the limited accuracy of solutions of the governing equations. Our overall approach is to create the science base for estimating the uncertainty from each source. We report progress in several areas. We developed a new high-fidelity model of energy transport in a specific stockpile system that gives an improved basis for quantifying uncertainty caused by changes to the stockpile. New radiography methods utilizing the Dual Axis Radiographic Hydrotest facility (DAHRT) and improved diagnostics have been developed that will further reduce uncertainties in the energy-transport model. We have initiated an integrated analysis and testing program to develop a probability-based structural analysis that is being applied to the overall performance of the stockpile system under study. A portion of the project that characterizes variability in the materials properties for input to engineering analysis codes has provided materials science support for this aspect of the study. Dramatic improvements in statistical and data analysis methods have supported project efforts across the board.

The analysis of complex natural or engineering systems can require input from any scientific discipline. What then brings the various components in the analysis of a complex system together, bringing coherence to the overall effort, is a common application. It is this factor that has lead to a project that is truly multidisciplinary and interdivisional, with each component of the project supporting, enhancing, and benefiting from the work of other components.

Publications

Adams, P.J., et al., "Quantification of Uncertainty and Stockpile Confidence (U)" (Nuclear Explosive Design Physics Conference XII, Los Alamos National Laboratory, Los Alamos, NM, October 25–29, 1999).

Dolin, R.M., et al., "Reliability Predictions Based On Probabilistic Structural Analysis And Monte Carlo Simulation" (Joint Working Group 31 annual meeting, Reading, England, October 10–11, 2000).

Dolin, R.M., et al., "As-built/As-is Assessment of Geometric and Material Properties for One-Hundred Manufactured Products" (Third Biennial Tri-Laboratory Engineering Conference on Modeling and Simulation, Livermore National Laboratory, Livermore, CA., November 2–3, 1999).

Dolin, R.M., et al., "As-Built/As-Is Engineering Modeling, Analysis, and Manufacturing" (Joint Working Group 31 annual meeting, Reading, England, October 10–11, 2000).

Dolin, R.M., et al., "Model Parameter Updating Using An As-Built/As-Is Philosophy And Bayesian Belief Networks" (7th ISPE International Conference On Concurrent Engineering, Lyon, France, July 17–20, 2000).

Dolin, R.M., et al., "Quantifying Uncertainty In Simulation Predictions Using A Bayesian Framework" (16th IMACS World Congress 2000 on Scientific Computation, Applied Mathematics, and Simulation, Lausanne, Switzerland, August 21–25, 2000).

Dolin, R.M., et al., "Validating Analysis Predictions Using Bayesian Methods, Decision Analysis, and As-built/As-is Philosophy" (Joint Working Group 39 annual meeting, Reading, England, July 6, 1999).

Dolin, R.M., and C.L. Faust, "Assessing System Reliability Using Logical Models And Simulation" (Joint Working Group 31 annual meeting, Reading, England, October 10–11, 2000).

Dolin, R.M., and E. Rodriguez, "Bayesian Inference Techniques In A Decision Analysis Framework To Determine Valve Reliability" (Third Biennial Tri-Laboratory Engineering Conference on Modeling and Simulation, Livermore National Laboratory, Livermore, CA, November 2–3, 1999).

French, S., et al., "Critique of and Limitations on the Use of Expert Judgments in Accident Consequence Uncertainty Analysis" (accepted in *Radiation Protection Dosimetry*).

Glimm, J., and D.H. Sharp, “Prediction and the Quantification of Uncertainty,” in *Predictability: Quantifying Uncertainty in Models of Complex Phenomena*, S.-Y. Chen, et al., Eds. (North-Holland, Amsterdam, 1999), p. 152.

Mason, T.A., and P.J. Maudlin, “Effects of Higher-Order Anisotropic Elasticity Using Textured Polycrystals in Three-Dimensional Wave Propagation Problems,” *Mech. Materials* **31**, 861 (1999).

Maudlin, P.J., et al., “High-rate material modelling and validation using the Taylor cylinder impact test,” *Phil. Trans. Royal Soc. London, Series A* **357**, 1707 (1999).

Maudlin, P.J., et al., “On the modeling of the Taylor cylinder impact test for orthotropic textured materials: experiments and simulations,” *Int. J. Plasticity* **15**, 139 (1999).

McKay, M.D., “Statistical Theory & Methods for Computer Experiments: Quantifying Prediction Uncertainty for a Computer Model” (United Kingdom Engineering and Physical Sciences Research Council Workshop “Statistical Analysis of Computer Code Outputs,” Gregynog, Wales, UK, April 10–14, 2000).

McKay, M.D., et al., “Sample size considerations when using R2 to measure uncertainty importance” (European Safety and Reliability Conference, Garching-Munich, Germany, September 13–17, 1999).

Ross, T., and S. Donald, “A New Method for the Development of Empirical Possibility Distributions” (World Automation Congress, Maui, HI, June 11–16, 2000).

Treml, C., et al., “Using Bayesian Belief Networks and an As-Built/As-Is Assessment for Quantifying and Reducing Uncertainty in Prediction of Buckling Characteristics of Spherical Shells” (8th ASCE Joint Speciality Conference on Probabilistic Mechanics and Structural Reliability, University of Notre Dame, South Bend, IN, July 23–26, 2000).

Zocher, M.A., et al., “An Evaluation of Several Hardening Models Using Taylor Cylinder Impact Data” (European Congress on Computational Methods in Applied Sciences and Engineering, Barcelona, Spain, September 11–14, 2000).

Zweig, G., and B. Wohlberg, “Age-related changes in Pu deduced from EXAFS data with a new super-resolution fast Fourier transform” (Nuclear Explosive Design Physics Conference XII, Los Alamos National Laboratory, Los Alamos, NM, October 25–29, 1999).

Management of Nuclear Warhead and Infrastructure Reduction

99513

James E. Doyle

The goal of this project is to provide a scientific basis for next-generation measures applicable to verifying deep reductions in the numbers of nuclear weapons and assessing the impact of these reductions on a range of national security issues. We addressed the challenges of safely and securely reducing nuclear weapons, materials, and infrastructure at the levels of the global system, national facilities, and critical nuclear items, taking account of the interrelationships among these levels. Our three major research areas are (1) developing novel computer-based assessment and visualization tools by adapting leading-edge software; (2) developing new methodologies, capabilities, and metrics with strategic dynamics and evaluation analyses to solve problems in strategic stability and associated risks to U.S. national security; and (3) focussing on nuclear archaeology and warhead transparency and monitoring measurements.

This year the project has developed several powerful analytic tools, prototype technologies, and an integrated research structure that help meet the challenges of safely and securely reducing excess nuclear weapons and infrastructure. Integrating optimization and game theoretic algorithms to solve the dependent hierarchical optimization and multipolar stability problems in the Multiple Engagement of Strategic Arsenals with Stability Metrics Assessment Model advanced the state-of-the-art in the operations research community. The Applied Monitoring and Transparency Lab demonstrates the potential application of comprehensive monitoring technologies for bilateral (U.S.-Russian) treaties and for future multilateral or global treaties. We developed the Integrated Facility Monitoring System and the Magazine Transparency System using unique combinations of technology and procedures to provide high confidence that nuclear warheads have been dismantled in accordance with a potential treaty. The U.S. Nuclear Weapon Disassembly Visualization Model demonstrated an innovative application of commercially available three-dimensional visualization and simulation hardware and software. These capabilities enable conducting quantitative assessments of operational facility delays caused when foreign nationals are present in nuclear weapon dismantlement facilities or when it is necessary to redirect sensitive activities to bypass observable areas.

Publications

Doyle, J.E., "Tracking Warheads from Dismantlement to Storage," *Dateline: Los Alamos*, Los Alamos National Laboratory publication, March 2000, p. 9.

Strategic Computing Applications

99515

Andrew White

The objective of this project is to explore the capabilities of terascale computing for applications other than the Accelerated Strategic Computing Initiative, thereby improving the Laboratory's computational capabilities. This year the project has had two distinct components: (1) Global Climate Modeling: The Role of the Thermohaline Circulation in Climate and (2) Epidemiology Modeling: Molecular Causes to Macroscopic Consequences.

Each of these components represents a significant scientific challenge, complements the stockpile stewardship program, draws on unique Los Alamos capabilities, and addresses an area of intense societal concern. The scientific objective of the first component is to determine the dependence of the global thermohaline circulation system on key physical processes. This circulation system has a major influence on world climate. The objective of the second component is to illuminate the fundamental mechanisms of disease and provide insight into the protection against unnatural pathogens.

We have made progress this year in simulating the global ocean with 0.1° resolution and 40 vertical levels. In addition, we have compared our two ocean models and validated them against observational data. Our progress also includes an evaluation of the model's abilities to simulate the observed thermohaline circulation and its sensitivity to various physical processes.

In epidemiological modeling, we have developed an agent-based, computer simulation model of the antibody response to influenza vaccination and live influenza virus. This model incorporates the concept of antibody cross-reactivity, so that an antibody raised to one vaccine will react not only with that vaccine but also with nearby vaccines or live viruses. To estimate the timing of the last common ancestor of the viral strains that have caused the HIV pandemic, we have applied phylogenetic analysis to HIV sequences.

Publications

Korber, B., et al., "Timing the Ancestor of the HIV-1 Pandemic Strains," *Science* **288**, 1789 (2000).

Lapedes, A., and R. Farber, "The Geometry of Immunological Shape Space: Application to Influenza" (submitted to *J. Theor. Biol.*).

Theoretical Quantum Computation

2000513

Emanuel Knill

Advances in computing and computer technology are revolutionizing our world economically and scientifically. Quantum computers offer great improvements in efficiency for solving combinatorial problems, securing communication, and simulating quantum physics. These computers make obsolete the most commonly used encryption protocols; enable novel encryption strategies (quantum cryptography without distance limits); and solve economically important combinatorial searching problems (scheduling, for example).

Implementing quantum computers is hampered by the fragility of quantum states, which is caused by decoherence. Decoherence destroys a quantum computer's ability to act as an interferometer and implement the quantum parallelism required by the above-mentioned applications. Our goal is to develop and implement the tools needed for physically realizable, scalable, and fault-tolerant quantum computers. We focus on techniques and results that apply to all conceivable physical realizations of quantum computation, while using available technology such as nuclear magnetic resonance (NMR) to test our results.

So far, we have developed and published a theory of quantum error correction for general noise, showing that protected subsystems exist. We defined a new class of quantum codes based on alphabets of size larger than 2. We found a quantum operation that universally reverses quantum noise processes near-optimally for transmitting both classical and quantum information.

In collaboration with the Massachusetts Institute of Technology (MIT), we analyzed in detail the behavior of error-correcting codes both theoretically and experimentally using NMR. Finally, we established the record for number of quantum bits (qubits) quantumly controlled, using liquid state NMR to control the nuclear spins of labeled crotonic acid. To do so required establishing quantum benchmark methodologies and new methods for applying NMR pulses. We are nearing completion of the synthesis for a 10-qubit molecule.

Publications

Ashikhmin, A., and E. Knill, "Non-Binary Quantum Stabilizer Codes" (submitted to *IEEE Trans. Inf. Theory*).

Barnum, H., and E. Knill, "Reversing Quantum Dynamics with Near-Optimal Quantum and Classical Fidelity" (submitted to *Phys. Rev. Lett.*).

Knill, E., et al., "An Algorithmic Benchmark for Quantum Information Processing," *Nature* **404**, 368 (2000).

Knill, E., et al., "Theory of Quantum Error Correction for General Noise," *Phys. Rev. Lett.* **84**, 2525 (2000).

Advanced 3-D Modeling and Simulation

2000519

David C. Cartwright

The goal of this project is to develop advanced three-dimensional (3-D) simulation tools for Los Alamos' defense mission and the DOE's microelectronics mission of hardened microelectronics for the nation's defense. While enhancing Los Alamos capabilities, the project will also help the U.S. semiconductor industry develop advanced modeling and simulation tools for the 0.05- to 0.1- μm (50- to 100-nm) technology, which the Semiconductor Industry Association (SIA) forecasts to be introduced into manufacturing in 2007.

This project was a specific component in the DOE Cooperative Research and Development Agreement (CRADA) to develop advanced simulation methods for nonlinear material and electromagnetic systems and to create the technology base for nanometer-scale integrated circuit components. These extremely small-scale components will be the foundation of future-generation supercomputers and will provide the computing performance essential for the DOE's mission-related simulations. This research at the nanometer-scale is directly related to the new National Nanoscale Initiative and to quantum computing.

Under the terms of the CRADA, Los Alamos and Sandia are working with several universities (Massachusetts Institute of Technology, Dartmouth, University of Texas – Austin, and North Carolina State University) supported by the Semiconductor Research Corp. to develop advanced models and simulators. Several companies (Motorola, Intel, LSI Logic, and Lucent) provide the experimental validation. This three-way collaboration has resulted in substantially improved abilities to model semiconductor materials and devices and to simulate certain systems and manufacturing processes.

We made major progress in materials deposition, where we investigated the chemistry of etching silicon surfaces with highly reactive chlorine ions that may be generated in plasma-etching reactors. We also studied the effects of the sputtering process, especially for depositing copper onto metal surfaces. We further developed a simulation software, TopoSim-3D, to describe both the chemical and physical processes involved in the formation of thin films.

We have implemented into the Los Alamos-developed computer code Grain3D a fully 3-D surface front-tracking method for calculating evolutionary grain growth in materials. Grain3D now is capable of finite element calculations for the evolution of the grain boundary surfaces on large systems. Calculations involve 1,000 or more grains (more than one million computational cells). Grain growth ordering is determined by examining the kinetics of a large cube of grains as a function of time. Although calculations are dependent on the evolution of the surface grid, Grain3D contains an internal volumetric grid, which is necessary for the calculation of diffusion and stress properties.

This project also incorporated 3-D grid generation capability, developed at Los Alamos, into an adaptive 3-D Poisson equation solver that uses a variational principle to determine the optimum electric field for a given geometry and material composition. This capability is essential for determining the optimum spacing of quantum dots, the voltages applied to each dot, and the parameters (e.g., spacing and voltages) for the gates linking the quantum dots.

ElectriSims

2000600

Doug Roberts

The goal of this project is to further develop the capability to model electrical-system infrastructures. This capability could be applied to the entire national, or even continental, power structure. Both the market and physical systems involved are dynamic, and together generate a complexity that drives the need for simulation. This year we made significant progress. We developed an algorithm to solve a linear electrical power flow code that runs and scales nicely on the Rockhopper Linux Cluster. Our distributed algorithm solved the power flow equations for a grid of 100,000 nodes and 150,000 links in 0.49 sec. We extended our electrical infrastructure simulation design to model the Western Systems Coordinating Council (WSCC) region of the United States under several market rule sets. Working with our collaborator, the California Independent Systems Operator (CAL-ISO), we ran two example simulation scenarios that illustrated the unique capabilities of the ElectriSims simulation (see fig. 1).

Our approach is a bottom-up aggregation that includes the lowest-level simulation agents. Therefore, all electrical busses and transmission lines are represented as software objects in the simulation, as are the market entities (ISOs, consumers, generators, power brokers). By carefully capturing and encapsulating the behavior of the simulation agents, the system behavior emerges as the agents interact.

To take advantage of the distributed memory architecture of the Linux cluster, we used a diakoptics approach to solving the power flow equations. This approach is related to the inverse of the sum of two matrices and is an alternative to Gauss-Jordon and Krylov methods. Diakoptics offers several advantages, including scalability for parallel computing. Using diakoptics, a matrix equation is solved by separating the matrix into a number of submatrices that are individually easier to solve, and composing their solutions to produce the solution of the original system. The practical applicability of the diakoptics method depends on the existence of a graph composed of sparsely interconnected subgraph clusters. This structure is characteristic of many physical systems under study. The method is even more efficient when the subgraph clusters are themselves sparsely connected.

Publications

Dowell, L.J., “Simulating Earthquake Damage to the Electric-Power Infrastructure: A Case Study for Urban Planning and Policy Development” (submitted to *Computers and Operations Research*).

Dowell, L.J., et al., “On Solving Nearly-Singular, Sparse Systems of Linear Equations: Diakoptics Techniques for Parallel Computing” (submitted to *Applied Computing Review*).

Loose, V.W., and L.J. Dowell, “Economic and Engineering Constraints on the Restructuring of the Electric-Power Industry: A Consideration of Reactive-Power Ancillary Services” (INFORMS Spring 2000 Meeting, Salt Lake City, UT, May 7–10, 2000).

Fig. 1. This figure shows the location and quantity of undispatched power in WSCC for a light summer load case under PJM-style market rules.

Nuclear and Particle Physics

Nonequilibrium Science: Assessment, Control, and Prediction

98605

Emil Mottola

The goal of this project is to create an integrated, interdisciplinary approach to the complex real-time dynamics of nonequilibrium phase transformations and to develop new quantitatively controllable computational strategies for averaging over the finest spatiotemporal scales and predicting macroscopic behavior. The reliable modeling of nonequilibrium systems is critical to a variety of Laboratory programs. For example, knowing how material responds in the presence of propagating shock fronts is essential to predicting weapons yields and aging characteristics, pressing problems in the absence of full-scale testing.

Extracting information about large-scale nonlinear coherent structures and significant physical variables from the microphysical theory without consuming inordinate amounts of computer resources limits the predictive power and uncertainty assessment in these settings. Predicting macroscopic properties and assessing uncertainty require control of the noise intrinsically generated at each level of coarse graining. The Laboratory's large-scale computational capabilities, the breadth of its multidisciplinary scientific expertise, and its mission of studying complex phenomena under extreme nonequilibrium conditions are uniquely suited to this effort.

This year, we made significant progress in calculating transport coefficients, such as electrical conductivity and hydrodynamical limits, from microscopic theory. We found experimental signatures of phase transitions in high-energy nuclear collisions. We also looked at the thermodynamics of shock-driven phase transformations in titanium; we developed and applied molecular dynamics codes for the titanium and other materials. We produced Ginzburg-Landau models of strain and elasticity in solids and coupled these models to existing hydrodynamic codes. We developed adaptive mesh refinement techniques in numerical simulations and invented a new accelerated Langevin molecular dynamics approach to numerical simulations.

Publications

Chodos, A., et al., "A Two-Dimensional Model with Chiral Condensates and Cooper Pairs Having QCD-like Phase Structure," *Phys. Rev. D* **61**, 045011 (2000).

Habib, S., and G. Lythe, "Dynamics of Kinks: Nucleation, Diffusion, and Annihilation," *Phys. Rev. Lett.* **84**, 1070 (2000).

Mihaila, B., et al., "Exact and Approximate Dynamics of the Quantum Mechanical $O(N)$ Model," *Phys. Rev. D* **62**(12), 5015 (2000).

Sanati, M., et al., "BCC to HCP Reconstructive Phase Transformation in Early Transition Metals" (accepted in *Phys. Rev. B*).

Sasik, R., et al., "Thermal Vortex Dynamics in a Two-Dimensional Condensate," *Phys. Rev. B* **62**(2), 1238 (2000).

Saxena, A., et al., "Domain Walls in BCC to HCP Reconstructive Phase Transformation," *Mater. Sci. Eng. A* **273–275**, 226 (1999).

Ultracold Neutron Science

98606

Susan J. Seestrom

We are continuing our efforts aimed at establishing Los Alamos as the world leader in fundamental physics using ultracold neutrons (UCNs). Fundamental physics performed using UCNs includes determination of neutron lifetime and decay parameters that can provide sensitive tests of the standard model of electro-weak interactions. We have demonstrated UCN production from a cryogenic sample of deuterium irradiated by cold neutrons. In the previous year of this project, we built and tested a prototype spallation UCN source.

The major focus this year has been to elucidate the physics behind the very short lifetime observed for UCNs in solid deuterium. Research concentrated on the effect of the deuterium molecular state—that is, whether the deuterium is in the ortho or para state. Our calculations have indicated that para deuterium could cause a large upscattering rate and hence a short lifetime. We prepared a device to convert deuterium to the ground state by cooling in the presence of a catalyst. We also prepared a test cell in which we used the

differing thermal conductivity of ortho and para deuterium to determine the relative amount achieved of the two states. We also measured the ortho/para ratio off-line using a Raman scattering spectrometer developed for this purpose. This spectrometer also allowed us to measure the contamination from H_2 molecules, which provide another source of UCN losses. With this system, we accurately measured the ortho/para ratio.

We performed experiments to measure the dependence of the UCN rate and lifetime in the deuterium on the ortho/para ratio and on the deuterium temperature. Figures 1 and 2 show the results of these measurements. The data clearly shows a dramatic increase in the number of UCN produced and stored as the para-deuterium fraction is reduced. Measurements made with small amounts of para deuterium show the expected temperature dependence. The data obtained confirms the hypothesis that the upscattering from para-deuterium impurities caused the short lifetime we previously observed.

We made measurements aimed at using the highest number of protons that could be used in Line B. This number corresponded to a maximum of about 100 mA protons delivered for 1 sec, or about 100 m Coul of protons. Figure 3 shows the number of UCN stored as a function of the number of protons. It has a maximum UCN density of nearly 100 UCN/cc—more than twice the previous world record for UCN density.

Fig. 1. Data and constrained exponential fits (solid lines) to lifetime data taken at different para-deuterium fractions.

Fig. 2. Data points are fitted solid deuterium lifetimes as a function of temperature, para-fraction, and volume. Solid lines show the predicted temperature and para-fraction dependence to the lifetimes. The dashed line is the predicted effect of departure from the solid lifetime model to upscatter from the gas in the guide at higher temperatures.

Fig. 3. Data for UCN production as a function of protons delivered to the UCN production target.

Neutrino Physics Experiments

99514

William Louis

This project explores some advanced technology areas that might significantly enhance and broaden the performance of the Booster Neutrino Experiment (BooNE) at Fermilab and the Sudbury Solar Neutrino Observatory (SNO) experiments. These experiments are well poised to resolve the Liquid Scintillator Neutrino Detector (LSND) and solar neutrino anomalies and are capable of proving that neutrino oscillations occur and of making precision measurements of the neutrino oscillation parameters.

We have made much progress this year on MiniBooNE. Improved event reconstruction and particle identification have made possible the reconstruction of the π^0 mass and have resulted in a lower background. Also, we improved and finalized the phototube mounting design, and construction of the phototube mounting plates has begun. Finally, we have also started to implement an array of computer PCs running LINUX—instead of a single multiprocessor computer—for performing the data acquisition.

The SNO detector is fully operational, and the collaboration has been accumulating physics data since October 1999. This year, qualitative results were presented in June at the Neutrino 2000 Conference. We worked on developing optimal techniques for the use of sources to understand the background wall, on the necessary analysis tools to characterize the detector backgrounds, and on a detailed comparison of the three neutral current (NC) detection schemes. Also, we are studying the issues involved in recovering the ratio of Charged Current (CC) and NC /CC shape in the pure D₂O versus dissolved salt options.

On the theoretical side, we have combined LSND with other data to make it possible to resolve the tritium beta decay anomaly and the supposed conflicts between neutrino oscillation data sets in terms of pseudo-Dirac neutrinos. The result is “natural” in the technical sense and correlates long baseline oscillations with particle-antiparticle transitions versus flavor-changing oscillations on shorter baselines. In addition, we computed neutrino cross sections within a large-basis shell-model framework and found them to be consistent with experiment data within statistical uncertainties. Overall, this year’s work has led to improvements in the quality of the MiniBooNE and SNO experiments and in the theoretical understanding of neutrino oscillations.

LDRD

Exploratory Research Projects

2000

Atomic, Molecular, Optical, and Plasma Physics, Fluids, and Beams

Artificial Atoms Probed by Femtosecond Pulses: Evolution of Optical Properties during the Bulk-Atomic Transformation

98001

Victor Klimov

Our understanding of electronic interactions in naturally occurring molecules and crystalline solids has greatly advanced during the past century. Recently, a new challenge has emerged with the development of a class of artificial materials consisting of small crystalline particles with physical dimensions smaller than 10 nm. This nanoscale range corresponds to a transitional regime between molecules and conventional solids in this range, the electronic energies, and hence the electronic and optical properties, exhibit a strong dependence on the material's dimensions.

Geometrical (quantum) confinement drastically modifies the electronic interactions that control many important processes (e.g., energy relaxation, carrier branching between nonradiative and radiative decay channels, carrier transport, and materials ionization). The goal of this project was to study modifications in fundamental electronic interactions during a gradual transition from molecular, to nanoscale, and finally to bulk crystalline regimes. In our studies, we used series of nearly monodispersed nanoparticles — colloidal quantum dots (QDs) — whose sizes can be tuned accurately from 1 to 20 nm, spanning the range between molecules and bulk crystalline solids.

This year we concentrated on studies of size-dependent, multiparticle interactions, namely Auger recombination and Auger-type electron-hole energy transfer. Auger recombination is a nonradiative process in which the electron-hole recombination energy is not emitted as a photon but instead is transferred to an electron or a hole. To study the effect of quantum confinement on Auger rates, we used a femtosecond transient absorption experiment applied to CdSe quantum dots of different sizes.

For the first time we were able to resolve single exponential dynamics of the 2-, 3-, and 4-electron-hole pair QD states (see Fig. 1) and to accurately measure quantized Auger rates. Furthermore, we observed that in quantum confined systems, the Auger constant is not a “constant” anymore but is a QD size-dependent quantity that scales as the QD radius cubed.

We also studied the role of Auger-type electron-hole energy transfer in carrier intraband relaxation. In these studies we used CdSe QDs capped with hole-accepting molecules. By re-exciting an electron within the conduction band at different stages of hole transfer and monitoring its relaxation back to the ground state, we observed a more than 10-fold increase in the electron relaxation time (from 250 fs to 3 ps) after the completion of the hole transfer to the capping molecule (see Fig. 2). This increase strongly indicates that electron relaxation in QDs is dominated by Auger-type electron-hole interactions but not by phonon emission as in bulk materials.

Publications

Klimov, V.I., et al., “Mechanisms for Intraband Energy Relaxation in Semiconductor Quantum Dots: The Role of Electron-Hole Interactions,” *Phys. Rev. B* **61**, R13349 (2000).

Klimov, V.I., et al., “Quantization of Multiparticle Auger Rates in Semiconductor Quantum Dots,” *Science* **287**, 1011 (2000).

Fig. 1. (a) Normalized dynamics of QD average populations and (b) dynamics of 1-, 2-, 3-, and 4-pair states extracted from the transient absorption data (QD radius is 1.7 nm).

Fig. 2. (a) Schematic of relaxation/transfer processes in QDs capped with hole-accepting molecules (pyridine) and (b) dynamics of electron relaxation back to the ground state after the infrared re-excitations. Dynamics are taken at different stages of hole transfer to a capping group (Δt_{IR} is the delay between the visible pulse creating the electron-hole pair and the infrared pulse that re-excites an electron). A pronounced increase in the relaxation time with increasing Δt_{IR} is a clear indication of the relaxation mechanism involving electron-hole interactions.

Laser-Plasma Interactions in Diffraction-Limited Beams

98002

David S. Montgomery

Propagation of an intense laser beam through large, dense plasmas is extremely important to laser-driven inertial confinement fusion (ICF) because effects such as stimulated Raman scattering (SRS), stimulated Brillouin scattering (SBS), and self-focusing not only degrade the performance of ICF targets but also place restrictive limits on the design of ignition targets. Experimental studies in large ignition-scale plasmas cannot be modeled from first principles because the large interaction volume is beyond the reach of current computational tools. Experimental studies using a diffraction-limited laser can, however, be directly modeled from first principles and are an essential step toward quantitative understanding of laser-plasma instabilities. These first-principles models can then guide the development of reduced description models for simulating the entire interaction volume in large-scale plasmas.

This year we measured flow-induced beam steering, a branch of the forward SBS instability, in plasmas with supersonic transverse flow under conditions where the growth of other instabilities was insignificant. The experiment measured the transmitted beam angular distribution and spectrum for various laser intensities and transverse flow. We compared the experimental results to a three-dimensional (3-D) first-principles model, which was the first ever direct numerical simulation of a laser-plasma instability. The simulation was in good quantitative agreement with measurements of the deflection angle and in good qualitative agreement with measurements of the angular distribution and spectra.

We also performed experimental studies of SRS. SRS is the decay of the intense laser wave into a scattered light wave and an electron plasma wave. This instability is important to ICF because it can scatter a significant fraction of laser energy (~50%) and because it produces fast electrons that can reduce the ICF implosion efficiency. Although the measurements were performed under conditions where SRS is stable according to linear theory, we observed significant SRS (~10%) that is orders of magnitude above linear theory predictions. We performed kinetic one-dimensional simulations that show electron trapping causing significant SRS to develop in these conditions. We will eventually develop a reduced 3-D model to compare to the experiments.

Publications

Fernández, J., et al., “Recent Los Alamos Experiments on Laser-Plasma Instabilities,” in *Inertial Fusion Sciences and Applications 99*, C. Labaune, et al., Eds., (Elsevier Press, Paris, 2000), p. 318.

Montgomery, D.S., et al., “Flow-Induced Beam Steering in a Single Laser Hot Spot,” *Phys. Rev. Lett.* **84**, 678 (2000).

Rose, H.A., “A Self Consistent Trapping Model of Driven Electron Plasma Waves at Low Density and Limits on Stimulated Raman Scatter” (submitted to *Phy. Plasmas*).

Stochastic Resonance in Arrays with Tunable Nonlinearity and Coupling

98003

Alp T. Findikoglu

Stochastic resonance (SR), a phenomenon in which random noise plays a constructive role by enhancing a nonlinear system's response to a deterministic signal, has been observed in a wide range of physical and biological systems. Our project combines a novel experimental technique with extensive numerical and theoretical analysis to investigate threshold-free SR. Our joint experimental/theoretical team includes the expertise of groups in materials science, high-frequency experimentation, and mathematical modeling.

The theory of nonequilibrium, nonlinear dynamics and the numerics and analysis of stochastic partial differential equations necessary for modeling and prediction have been developing rapidly in the last couple of years, while quantitative comparison with experiment has been largely lacking. The SR devices we have used in this project are ideally suited to provide such an experimental test. Further, demonstration of noise-induced enhancements in nonlinear response of dielectric media could lead to the development of practical high-frequency devices such as ultralow-noise broadband amplifiers and ultrasensitive detectors.

To study the effect of noise on nonlinear response, we used the 8-cm-long coplanar waveguides designed and fabricated by our team as generic distributed nonlinear resonators (essentially, building blocks for arrays) and characterized their response as functions of various noise, bias, and signal inputs. In parallel with this experimental effort, we constructed a theoretical model based on a set of coupled partial differential equations in a nonlinear medium with two boundaries. We used the experimental results to provide parameters for the model, which was in turn used to predict the deterministic aspects of our device. The model accurately predicted the bias and frequency dependence of the nonlinear response, including generation of harmonics and intermodulation products.

This year we refined the numerical and theoretical analysis. Also, we experimentally investigated noise-induced effects on the mixed signal output of stochastic resonators for up-conversion and down-conversion. Numerical and experimental results indicate that, under certain conditions, the mixed output power of the stochastic resonator increases linearly with band-limited input noise power, whereas the output of a conventional mixer would remain unchanged with input noise. The signal-to-noise ratio in the vicinity of the mixed output signal frequency for the stochastic resonator remained, to first order, inversely proportional to the input noise power, similar to the expected behavior for a conventional mixer operated in the small-signal limit. These effects we have observed hold promise for the design of mixers and amplifiers with improved performance in noisy environments.

Publications

Findikoglu, A.T., et al., "Nonlinear Dielectric Response and Stochastic Effects in Strontium Titanate" (submitted to *Appl. Phys. Lett.*).

Create and Study Quantum Degenerate Systems

99001

David J. Vieira

The main objective of this project is to sympathetically cool a Fermi gas of rubidium-84 (half-life = 33 d) atoms down to the Fermi degenerate regime via atomic collisions with a rubidium-87 Bose-Einstein condensate (BEC). In this state we can investigate novel and interesting quantum mechanical effects of such ultracold, degenerate matter. In particular, we are exploring fermion-fermion and fermion-boson collisions and their thermodynamic properties at temperatures approaching absolute 0 K (~10–100 nK). At these low temperatures fermions may also form Cooper pairs and go through a phase transition similar to that observed in superfluid helium-3. This work is also expected to open future possibilities in the areas of coherent states generation of atomic ensembles, pulsed/continuous wave atom lasers, and atom interferometers. Potential technical spinoffs from this work are in the areas of quantum information/control and the development of ultrasensitive inertial sensors.

In previous work we demonstrated the trapping of rubidium-84 atoms for the first time and investigated the simultaneous trapping of rubidium-84 and rubidium-87 atoms in overlapping magneto-optical traps (MOT). In the rubidium-84/87 simultaneous trapping experiment we investigated light-assisted collisional losses that could have limited the sympathetic cooling experiment; however, we found a suitable trapping condition that effectively eliminates this potential problem.

This year we have demonstrated the transfer of two rubidium isotopes (rubidium-82 and rubidium-87) from one MOT to another MOT with the subsequent loading of these two species into a pure magnetic trap called a time-orbiting-potential (TOP) trap. We obtained a 50% TOP loading efficiency and TOP trap lifetime of ~60 s. Additional studies indicated that the temperature of the atomic cloud limited the lifetime. To enable a better optimization of the “optical molasses” cooling step in the TOP trap loading sequence, we have installed an intensified charge-coupled device camera to image the expansion of the cloud upon release from the trap. By taking multiple-shot images at different delay times relative to when the atoms are released, we can determine the average velocity of the atoms and consequently the temperature of the ensemble. With this new tool, we are now quantitatively measuring the temperature and density of the atomic cloud and optimizing the TOP trap loading sequence.

To produce the densities needed for efficient sympathetic cooling, we are building a new MOT – TOP trap system that has much stronger magnetic fields for tighter confinement. All of the components, including new TOP coils, trapping cell, drive electronics, and laser system, have been built or purchased, and we are currently putting this new trapping system together. The first goal of this system is to produce a rubidium-87 BEC. Once the BEC is built, we will overlap a cloud of rubidium-84 atoms with the rubidium-87 BEC and attempt the sympathetic cooling of rubidium-84 via atomic collisions of rubidium-84 and rubidium-87. Continuous radio-frequency evaporation will keep the rubidium-87 BEC cold. In this way we hope to produce and investigate the quantum mechanical properties of a weakly interacting Fermi degenerate gas of rubidium-84.

Publications

Crane, S.G., et al., “Trapping an Isotopic Mixture of Fermionic ^{84}Rb and Bosonic ^{87}Rb Atoms,” *Phys. Rev. A* **62**, 011402(R) (2000).

Vieira, D.J., et al., “Trapping Radioactive Atoms for Basic and Applied Research,” *Hyperfine Inter.* **127**, 387 (2000).

Dynamical Stability and Quantum Chaos of Ions in a Linear Trap

99002

Daniel F. V. James

As an important new area of science and technology, quantum computation has great relevance to national security, specifically to the theory, modeling, and high-performance computing mission of the Laboratory. A major initiative is currently underway at Los Alamos to investigate the use of trapped ions to build a quantum computer. One main obstacle to the realization of such a device is the presence of fundamentally quantum dynamical instabilities that can occur in such systems, including quantum chaos. We are studying these instabilities and will identify the correct operational parameters to avoid them. In particular, we will develop theoretical models for a wide class of dynamical quantum instabilities and will, in close collaboration with experimental efforts, study the impact of these instabilities on the dynamics of trapped ions. We have completed the following two important studies for this project.

Using a novel method devised to aid experiments, we have developed a new approach to the resonant classical and quantum dynamics of harmonically driven trapped ions. We have also showed that in the quantum system, one can analyze the dynamics by using quantum resonance cells, which are similar to the resonance cells in the classical phase space. This analysis gives the average quantum probability in each cell. Also, this technique will make it possible to simplify the measurement of the probability distribution, because in this case it is not necessary to measure the probability at a fixed oscillator state.

We have also investigated analytically and numerically the stability of the classical and quantum ground states of trapped ions under the influence of resonant lasers. This study is of direct importance to quantum computation, which relies on the maintenance of the trapped ions in their collective ground states.

Publications

Berman, G.P., et al., "Dynamical Stability of an Ion in a Linear Trap as a Solid-State Problem of Electron Localization," (submitted to *Phys. Rev. A*).

Berman, G.P., et al., "Dynamical Stability and Quantum Chaos of Ions in a Linear Trap," *Phys. Rev. A* **61**, 023403 (2000).

Berman, G.P., et al., "Quantum Chaos of an Ion Confined in a Linear Ion Trap Interacting with Laser Fields," *CHAOS* **10**, 371 (2000).

Berman, G.P., et al., "Stability of the Ground State of a Harmonic Oscillator Perturbed by a Monochromatic Wave" (submitted to *CHAOS*).

Berman, G.P., et al., "Symmetry of Quantum Phase Space in a Degenerate Hamiltonian System," *CHAOS* **10**, 670 (2000).

James, D.F.V., "Quantum Computation with Hot and Cold Ions: An Assessment of Proposed Schemes," *Fortschritte der Physik* **48**, 823 (2000).

James, D.F.V., "Quantum Computation with Trapped Ions and the 'Heating Problem,' " in *Quantum Computing III: Proceedings of the International Society of Optical Engineering*, E. Donkor and A.R. Pirich, Eds. (SPIE, Bellingham, WA, 2000), **4047**, 60.

Kamenev, D.I., and G.P. Berman, *Quantum Chaos: A Harmonic Oscillator in a Monochromatic Wave* (Rinton Press, Inc., Princeton, 2000).

Quantum Coherence and Decoherence: Trapping a Schrödinger Cat

99003

Wojciech H. Zurek

The purpose of the project is to investigate decoherence in the context of atom and ion trap experiments. Ion traps are a promising implementation of quantum computers. They also offer a possibility to carry out experiments that will shed a new light on the process of decoherence, which is responsible for the transition from quantum to classical. Atomic traps were recently used to observe Bose-Einstein condensation, a symmetry-breaking phenomenon, which involves basic quantum considerations at a fundamental level. In both settings, Schrödinger cat states—flagrantly nonclassical and very quantum superposition—will be implemented. We are investigating loss of quantum coherence analytically in situations relevant for the forthcoming experiments. This project has long-term implications for national security and aims to expand the Laboratory's high-performance computing capability.

This year we have attacked several related problems in the area of decoherence. In particular, we have studied the relevance of chaos in the environment for the effectiveness of decoherence and concluded that chaotic environments will indeed be more effective than regular environments. We are now investigating schemes for testing our theoretical prediction in ion traps and other settings that offer experimentally feasible implementations of chaotic dynamics. Moreover, we have studied the structure of the Wigner function and arrived at the limit on the smallest scales it can accommodate (structure saturation). We have also discussed the effect these scales have on the decoherence rate. Finally, we have studied Bose-Einstein condensation and derived a formula for the decoherence rate of Schrödinger cat states in this setting. All of these advances will help with the implementations of quantum information processing.

Publications

Anglin, J.R., and W.H. Zurek, "Vortices in the Wake of a Rapid Bose-Einstein Condensation," *Phys. Rev. Lett.* **83**, 1707 (1999).

Dalvit, D.A.R., and P.A. Maia Neto, "Decoherence via the Dynamical Casimir Effect," *Phys. Rev. Lett.* **84**, 798 (2000).

Kielpinski, D., et al, "Sympathetic Cooling of Trapped Ions for Quantum Logic," *Phys. Rev. A* **61**, 032310 (2000).

Paz, J.P., and W.H. Zurek, "Quantum Limit of Decoherence: Environment Induced Superselection of Energy Eigenstates," *Phys. Rev. Lett.* **82**, 5181 (1999).

Quantum Feedback Control: Methods and Applications

99004

Salman Habib

The fateful inception of quantum mechanics during the early part of the last century provoked a radical shift in our fundamental beliefs about physics. Above all else, we learned to embrace the idea that events in the microworld transpire according to laws and physical principles that directly contradict those governing the macroworld of human experience. However strange such notions may seem, their validity has been confirmed time and again by numerous experiments performed over the last fifty years: Active manipulation and control of quantum states is now becoming possible in a number of experimental contexts. Several exciting applications have been identified and substantial effort is now being expended to develop these technologies. The aim of this project is to develop a theoretical and computational framework for the design and analysis of quantum feedback control systems. The development of quantum feedback control as an engineering discipline will play an essential role in promoting technological applications of mesoscale quantum systems which operate at the interface of classical and quantum mechanics.

Very substantial progress was made in the past year. We elucidated the precise relationship between classical and quantum feedback control. This will enable the application of the extensive body of knowledge already developed in classical control theory to the quantum domain, as well as sharply delineate the differences between the classical and quantum regimes. Feedback schemes for laser-driven active single-atom cooling and atom switching in a double-well potential were developed. In these schemes the use of suboptimal estimation was found to be critical for practical applications.

Ideas in quantum information theory motivated by questions in feedback control were investigated. Not only does feedback control suggest new definitions of quantum information and disturbance, the trade-off between them is an important issue for the design of optimal feedback algorithms. Model reduction strategies (based on a control-theoretic input-output view of systems) were applied successfully to quantum dynamics and possible applications to quantum statistical mechanics are being investigated.

Publications

Bhattacharya, T., et al., “Continuous Quantum Measurement and the Emergence of Classical Chaos” (*Phys. Rev. Lett.*, in press).

Doherty, A., et al., “Information, Disturbance and Hamiltonian Quantum Feedback Control” (submitted to *Phys. Rev. A*.)

Doherty, A., et al., “Quantum Feedback Control and Classical Control Theory,” *Phys. Rev. A* **62**, 012105 (2000).

Doherty, A., et al., “Robust Control in the Quantum Domain: Entanglement, Feedback and Measurement Backaction” (IEEE Control and Decision Conference, Sydney, Australia, December 2000).

Habib, S., et al., “The Quantum-Classical Transition in Nonlinear Dynamical Systems” (submitted to *Phys. Rev. Lett.*).

Direct Observation of Individual, Optical Energy-Transfer Events

99005

William Patrick Ambrose

Optical energy transfer data is used to provide information on changes in orientation of molecules and changes in distance between 1 and 10 nm. Extracting donor-acceptor distances often requires assumptions about the underlying distributions of dipole orientations, vector displacements, and assumes a dipole-dipole coupling approximation. Our goal is to observe experimentally the interactions between individual pairs of molecules at optical energies, free from ensemble averaging. Individual molecules will be scanned relative to one another using fine-positioning techniques. The results of this process will allow us to test directly the approximations used in energy-transfer theories. Evaluating and refining the approximations through experimentation will lead to a capability for producing optical images with a resolution better than $(\text{wavelength})/100 = 5 \text{ nm}$, far below the diffraction limit $(\text{wavelength}/2)$. This capability will be used to guide the design of surface-based sensors with molecules embedded in thin films, such as those needed for the Chem-Bio Nonproliferation Program.

To expand on our previous success in detecting single molecules on surfaces, we needed to find an atomically smooth surface for this work. We demonstrated optical detection of single fluorescent molecules on an atomically smooth surface (mica) using confocal laser scanning microscopy. Next, we demonstrated probe-sample scanning with 1 nm probe oscillation amplitude and 1 nm height noise in an apparatus with a resemblance to tapping mode atomic force microscopy. The height noise needs to be reduced another order of magnitude. Hence, we assembled an experimental isolation chamber incorporating acoustic and electrical isolation and two stages of vibration isolation from the floor. The chamber reduces the through-air acoustic noise by a factor of 100 for sound frequencies between 100 to 5000 Hz. To improve probe-sample height feedback, we will employ the principles that 1) a probe oscillating on resonance with low self damping provides high sensitivity to sample proximity, and 2) detection of probe-frequency modulation by the sample does not limit the probe-height control-loop bandwidth (as with amplitude modulation detection). In other words, the loop bandwidth and noise can be controlled by other elements of the control loop. We have designed and built probe-oscillator electronics with automatic gain (amplitude) control, and

will soon complete frequency demodulation and feedback electronics. With these improvements in our scanning system, we will then have the position control necessary to spatially resolve energy transfer efficiencies with sub-nanometer precision.

Optical Investigations of Quantum Information

2000001

Paul G. Kwiat

Optical systems at the photon level are optimal for experimentally investigating basic issues in quantum information science because they possess well-understood and controllable properties. Specifically, entangled states of two or more systems lie at the heart of quantum mechanics (Erwin Schroedinger called them “the characteristic trait”), play a crucial role in the transition to the classical realm, and are central to quantum communication and computation. As such, studies of optical entanglement are of fundamental importance to the Laboratory’s work in high-performance computing, enabling a range of future applications in basic science, advanced computation, and national security, with capabilities exceeding conventional techniques. This project is aimed at developing techniques for the creation, characterization, and utilization of entangled states, as embodied in quantum mechanically correlated photons.

At Los Alamos we have developed a novel source of polarization-entangled pairs of photons (see Fig. 1). This source, in addition to being much brighter than all others, has the added feature of being tunable, allowing us to explore previously inaccessible topics in quantum information. In this project we have developed methods of introducing “controlled decoherence” to our correlated photons, enabling the generation of quantum states with an adjustable degree of “mixture” (i.e., how classically random they are), as well as an adjustable degree of entanglement (i.e.,

how nonclassical they are). Ours is the only system in the world to permit controlled generation of these sorts of two-photon states. We have used these to implement the first experimental realization of entanglement “distillation.” In this procedure, special measurements are used to recover completely entangled (“clean”) states from partially entangled and/or partially mixed (“noisy”) states (see Fig. 2). In one of these experiments, we observed the phenomenon of “hidden nonlocality”: before distillation, the states appear classical, whereas afterwards, they display the definite nonclassical feature of nonlocality.

Finally, we have used the correlated photons to implement a quantum cryptography protocol—the nonlocal correlations of the photons allow a sender and receiver to generate a shared, random, secret key, which is then used to encrypt messages. Because the information is carried in the fragile quantum states of single photons, any attempt at eavesdropping is readily detectable (see Fig. 3). We are now working on an advanced scheme, in which the visibility of an eavesdropper is further enhanced by 33%.

Publications

Kwiat, P.G., et al., “Experimental Entanglement Distillation and Revealing Hidden Nonlocality” (to be published in *Nature*).

Kwiat, P.G., et al., “Experimental Verification of Decoherence-Free Subspaces,” *Science* **290**, 498 (2000).

Naik, D.S., et al., “Entangled State Quantum Cryptography: Eavesdropping on the Ekert Protocol,” *Phys. Rev. Lett.* **84**, 4733 (2000).

White, A.G., et al., “Exploring Hilbert Space: Synthesizing a Range of Quantum States” (submitted to *Nature*).

Fig. 1. When ultraviolet photons polarized at 45° are incident on the two adjacent nonlinear crystals (shown here as #1 and #2), they have an equal probability of being converted into two horizontally (vertically) polarized red photons in the first (second) crystal. An entangled-polarization state results from the quantum mechanical indistinguishability of these two possibilities.

Fig. 2. Using new techniques of “quantum state tomography,” we are able to take “pictures” of the quantum mechanical states. At left is an imperfectly entangled state. At right is the same state after “entanglement distillation”; it is then perfectly entangled—all the peaks have the same height. (H = horizontal polarization, V = vertical polarization)

Fig. 3. In the absence of an eavesdropper (bottom line), the sender and receiver in a quantum cryptography protocol have only a 3% bit error rate (BER). With an eavesdropper measuring the photons going to the receiver (top line), the error rate is increased to at least 25% (depending on the polarization angle of the eavesdropper's attack—Eve's polarizer angle). The increased error rate allows detection of the intrusion.

Cold Atom Fermion Coherence

2000002

P.W. Milonni

As ultra-low-temperature laboratories, neutral atom traps provide a range of flexibilities that is unprecedented in traditional low-temperature physics. Until recently, attention has focused on trapping atoms of integer spin (bosons) and cooling them to create Bose-Einstein condensates (BECs). The demonstrations of BEC superfluidity, a state of matter that is characterized by the quantum property of matter-wave coherence on a macroscopic scale, illustrate further the potential of atom traps for novel techniques and possible generalizations of superfluidity. Similarly, several experimental efforts aim at reaching the predicted superfluid state of mutually attracting atoms of half-integer spin (fermions) in atom traps.

During the first year of this project we reviewed the issues and experimental achievements in detecting and studying the superfluid behavior of atom-trap BECs. One of these techniques, the excitation and observation of so-called scissor modes, appears to be a particularly promising candidate for observing fermion superfluidity.

We also suggested and analyzed the possibility of creating a new state of matter consisting of mutually coherent fermionic and bosonic superfluids. The low-energy Feshbach resonance was believed to simply alter the interatomic interaction. In an external magnetic field, the effective interaction of two distinguishable fermions can be strongly attractive, thereby increasing the critical temperature for Cooper pairing (superfluidity) to experimentally achievable values. Our studies have revealed that the resulting system consists of a fermion-paired superfluid of atoms that is mutually coherent with a boson superfluid of the molecules that are created in the intermediate state of the binary-atom Feshbach resonance. This process is, in fact, a new fermion pairing mechanism that was originally suggested in high- T_c superconductivity (a hypothesis that has been challenged in that context by experimental observations). We predicted atom-molecule population oscillations in response to a sudden change of the magnetic field. These oscillations can serve as a signature of the Fermi/Bose superfluid state of matter.

Thirdly, we uncovered a new fermion-specific heating mechanism that will play an important role in fermion cooling. Because of the Pauli principle, the particles in a low-temperature, weakly interacting fermion system occupy the lowest-energy single-particle states. We pointed out that the removal of such particles in the loss processes, unavoidable in the ultracold gas systems, leads to an effective heating of the system that is particularly significant in the ultralow temperatures necessary to reach fermion superfluidity.

Publications

Timmermans, E., “Superfluids and Superfluid Mixtures in Atom Traps” (to be published in *Contemp. Phys.*).

Timmermans, E., et al., “Prospect of Creating a Composite Fermi/Bose Superfluid” (submitted to *Phys. Rev. Lett.*).

Ultrafast Dynamics of Laser-Plasma Interactions in Solids

2000004

George Rodriguez

Advances in ultrafast laser technology have opened a field of science in which it is now possible to study intense-laser/solid interactions on time scales on the order of 10^{-14} seconds, a time regime that was previously inaccessible. The electric field of an intense, ultrashort laser pulse exerts a force on particles that can exceed the forces binding electrons or atoms in solids. Indeed, very nonequilibrium thermodynamic conditions can be produced that make it technically challenging to diagnose and understand the heating mechanisms involved when an intense, short-pulse laser ablates a material.

Our project is a joint experimental/theoretical effort to understand the physics of the primary-event, laser-induced breakdown and properties (multiphoton and collisional ionization, dense plasma formation, nonequilibrium thermal conduction, and hydrodynamic expansion) of hot, dense plasma transport in solids. Our goal is to perform the first time-resolved experiments that will completely characterize radiation-driven hydrodynamic mechanisms responsible for ultrafast ($t < 100$ fs) optical breakdown in solids. We are using a rigorous hydrodynamic computer model with an optical-field wave solver to calculate the interaction of the plasma with the laser. This project integrates and utilizes the Laboratory's scientific leadership in plasma science, laser-beam technology, and hydrodynamic modeling.

During our first year of work, we have checked the multipulse, interferometric frequency-resolved optical-gating diagnostic (MI-FROG) by performing ultrafast, time-resolved optical-field ionization studies with gas targets at near-atmospheric pressures. We used a one-dimensional, plasma-fluid computer model to describe the dynamics of the plasma-ionization front traveling through the approximately 100-fs optical pump pulse. We also used comparisons with tunnel-ionization-rate models to calculate the optical-field interaction with the gas for optical intensities approaching 2×10^{14} W/cm². When the femtosecond, time-resolved ionization dynamics of the noble gases (He, Ne, Ar, Kr, and Xe) and molecular homonuclear diatomics (H₂, N₂, and O₂) are measured by MI-FROG, the results agree with the ionization rates as calculated from our model.

We have finished constructing the experimental target chamber and integrating an ultrashort-pulse ($t \sim 50$ fs) laser system. An evacuated target chamber is required to prevent undesired nonlinear optical mechanisms from interfering with an intense laser pulse (approximately 10^{16} W/cm²) before it reaches the solid target. We have also completed an extremely position-sensitive diagnostic device based on a microscope-coupled Michelson stellar interferometer and are using it to measure the hydrodynamic motion of a femtosecond laser-heated aluminum target. Surface-motion measurements and comparisons with hydrodynamic computer code predictions will allow the study of hydro and material models in an important regime that is difficult to access by other means. Experiments on aluminum targets are in progress.

Publications

Rodriguez, G., et al., "Coherent Ultrafast MI-FROG Spectroscopy of Optical Field Ionization in Molecular Gases: H₂, N₂ and O₂" (submitted to *IEEE J. Select. Topics Quantum Electron.*).

Siders, C.W., et al., "Measurement of Ultrafast Ionization Dynamics of Gases by Multi-Pulse Interferometric Frequency Resolved Optical Gating" (submitted to *Phys. Rev. Lett.*).

Reconnection Scaling Experiment Transition from Resistive Magnetohydrodynamics to Collisionless Reconnection

2000005

Tom Intrator

We are investigating magnetic reconnection in a laboratory astrophysics experiment on earth. Magnetic reconnection is a major unsolved issue in magnetohydrodynamics (MHD) and plays a fundamental role in many astrophysical and laboratory plasmas that change magnetic field topology. Magnetic flux annihilates and transforms into plasma kinetic energy—a process beyond the scope of ideal MHD, where magnetic fields are “frozen-in” to the plasma fluid frame. The Reconnection Scaling Experiment (RSX) is a simple and unique physics experiment that will have a large impact on our understanding of magnetic reconnection. This physics is ubiquitous in stellar atmospheres, planetary magnetospheres, astrophysical plasmas, satellite communications, fusion plasma research, dynamo self-generation of magnetic fields, and the large-scale structure of the universe. Many astrophysicists typically invoke fluid dynamics to model a universe that is 99.5% plasma, shortchanging the significance of Maxwell’s equations in plasma flows. Many papers and invited talks at recent physics meetings testify to an explosion of interest in these issues.

RSX can scale between collisional and collisionless reconnection, and we model this with three-dimensional (3-D) fluid simulations of the reconnection region using the NIMROD code. This code simulates nonlinear electromagnetic phenomena that fundamentally alter the magnetic confinement of fusion-grade plasmas. NIMROD can handle the stiff mathematical equations that describe hot magnetized plasmas, where time and spatial scales vary by many orders of magnitude, making comparisons with nonfusion experiments straightforward.

We will generate 3-D movies of magnetic reconnection with unique information at the electron skin-depth length scales from many repetitive shots as the reconnection region sweeps down a 4-m plasma column. The RSX experiment is unique in the world, premised upon a linear (not toroidal), gun-driven (not tokamak-like equilibria) device with identically repetitive shots achieving Lundquist numbers in the range of 200–1000. We can address the key physics questions with many experimental knobs that are decoupled from the plasma formation and equilibrium issues.

This year, we have assembled the mechanical infrastructure for this experiment, including vacuum vessels, vacuum pumping systems, magnet solenoid, electrolytic capacitor bank for the magnet coils, plasma guns, and data acquisition equipment. First plasma is scheduled for December 2000. Our students have made major contributions to the design and assembly of the experiment.

Three-Body Atomic Recombination in Bose-Einstein Condensates

2000006

Russell T Pack

The recent development of the ability to cause atomic gases in cold traps to form Bose-Einstein condensates (BECs) has caused enormous, worldwide excitement in atomic and molecular physics. Three-body atomic recombination causes atoms to be lost from the traps, and, because of the strong dependence of the recombination rate on the atomic density, it is the loss mechanism that limits the maximum density achievable in many condensates. Hence, three-body recombination needs to be well understood.

In this project, we are extending our three-body hyperspherical scattering methods and codes to do exact quantum-mechanical calculations of three-body recombination rates of alkali atoms at the ultralow temperatures of BECs. The results will help researchers at Los Alamos and worldwide achieve a detailed understanding of recombination and better control of BECs and will thus open the way to new applications of BECs. This research will similarly help those studying ultracold fermionic systems. This work contributes to understanding new physics and to the Laboratory's capabilities in theory, modeling, and high-performance computing.

Our three-body code in Delves' hyperspherical coordinates is now running and giving what we believe are correct results. Because they are new, first-ever such results, we are checking them carefully before publishing them. The results so far converge slowly with respect to both the number of coupled differential equations solved and the largest distance (hyperradius) to which the equations are integrated. To speed convergence, we are implementing the new slow/smooth variable discretization (SVD) method. In its original form, the SVD method is computationally very expensive for alkali atom systems, but we have now discovered that it can be neatly combined with the renormalized Numerov method. We are implementing this approach, which we expect to speed both convergence and computation time markedly and enable us to generate the reaction probabilities, cross sections, and rates needed. Debugging of the SVD code is nearly complete.

Macroscopic Quantum and Statistical Science

2000061

Raymond Laflamme

Nuclear magnetic resonance (NMR) provides an experimental setting in which to explore physical implementations of quantum coherence. Ideas and instrumentation from liquid-state NMR spectroscopy have already been used to experiment with small quantum systems. This approach has carried the field to a complexity of about 10 fully coherent spins, a small number for quantum computation but large enough for observing and better understanding the complexity of the quantum world. Liquid-state NMR is the only present-day technology about to reach this size. However, further increases in complexity will require new methods. We investigated and laid the groundwork toward a scalable quantum system using spin-1/2 particles. The next step is achieving a solid-state NMR capable of reaching 10–30 spins with full coherent control. This work complements other LDRD and DOE projects on theoretical and experimental quantum information processing. This work investigates how macroscopic quantum coherence can be created and observed in a matrix of organic molecules.

We have identified four ways in which solid-state NMR can be used to increase our understanding of quantum coherence. First, the system can be highly polarized, thereby increasing the sensitivity necessary to measure the effect of coherent spins. Second, the decoherence rates can be made slower. Third, in comparison with liquid-state NMR, couplings between spins are higher, thereby permitting both faster and more accurate operations, so that manipulations of much greater complexity can be implemented. Finally, there are mechanisms that can be used for dynamically resetting the quantum bits (called qubits), thus making it possible to remove information from a system and to efficiently implement error-correction.

From the standpoint of spectroscopy, the main differences between liquid- and solid-state NMR are that, for solid-state NMR, the dipolar couplings are resolved; spin diffusion contributes significantly to the dynamics; the chemical shift needs to be described by a tensor; the spin lattice relaxation times are typically very long; the transverse (phase) decoherence time is dominated by spin-spin interactions, which can be refocused by special-purpose radio frequency (RF) pulse sequences; and there are methods for creating very high nonthermal polarizations.

By enabling us to manipulate quantum systems with a reasonable degree of reliability, NMR offers a useful testbed for quantum information processing. We have demonstrated many of the elements essential for quantum control. NMR also allows us to move from theoretical understanding to the laboratory benchtop and helps us understand the difficulties of harnessing the power of quantum mechanics. NMR techniques have been developed in the spectroscopy community to deal with a wide range of coherent errors, and although the best quantum technologies might not resemble what we can imagine today, the set of techniques being developed is essential to making progress. We have investigated these differences and concluded that solid-state NMR is a promising quantum technology.

Publications

Cory, D.G., et al., “NMR Based Quantum Information Processing: Achievements and Prospects,” in *Fortschritte der Physik* (special issue: *Experimental Proposals for Quantum Computation*) **48**, 875 (2000).

Cory, D.G., and R. Laflamme, “Computing with Quantum Physics: Quantum Computing Offers Great Promise for Very Powerful Systems,” in *Dr Dobbs's Journal*, (*Supplement on Software in the 21st Century*) 29 (2000).

Bioscience

Noninvasive Techniques for Genetic Analysis

98005

Jonathan Longmire

In this project we used molecular genetic approaches to study the Mexican spotted owl (*Strix occidentalis lucida*) population that resides in the Jemez Mountains of northern New Mexico. Our aim was to identify genetic markers that could be used to study spotted owl populations and to develop methods that would allow us to isolate the owl DNA from molted feathers.

We developed the genetic markers by constructing a genomic DNA library for the spotted owl (the first ever produced) and screening the library for clones that contained highly polymorphic, repeated sequences. We then analyzed these repeated sequences in DNA samples isolated from molted spotted owl feathers (see Fig. 1). We used the resulting data to examine genetic variation present within the owl population. The Jemez population can now be compared genetically to spotted owls from other geographic areas.

Because we used molted feathers collected at nest sites as a DNA source, we did not have to trap and handle the owls. Thus, our genetic study was noninvasive and of minimal disturbance to the wild population of this threatened species. Our data will provide valuable insights into several aspects of spotted owl biology and ecology, such as turnover rates at nest sites, survival rates, possible multiple paternity, dispersal patterns, and levels of genetic diversity and genetic uniqueness of the Jemez population. This project contributes to our understanding threatened and endangered species, an environmental issue of local and national importance.

Fig. 1. Spotted owl DNA polymorphisms analyzed on an automated DNA sequencing machine. We developed primers that allowed us to amplify and analyze, through a polymerase chain reaction, a repeat of four nucleotides that make up a common polymorphism in spotted owl DNA. The blue bands are the highly polymorphic alleles (fluorescently labeled) present within the genomic DNA of an individual owl. The red bands are DNA fragments of a defined length, to serve as a size standard. The variation seen between owls can be used for population analyses, including measuring genetic diversity.

Rapid Genotyping Assay for Beryllium Disease Susceptibility

98006

John Nolan

With the unraveling of the human genome, biomedical researchers have discovered many millions of single-nucleotide polymorphisms (SNPs), which are specific points in the genome where a single nucleotide varies between individuals or between two paired chromosomes of an individual. The goal of our project was to use flow cytometry to analyze SNPs. The method we developed has significant advantages in speed and sensitivity over existing methods for detecting and analyzing SNPs, providing a powerful genomics tool for exploring genetic diversity and disease.

To analyze and count the bases at polymorphic sites, we developed a novel microsphere-based method that employs fluorescently labeled oligonucleotides. The labeled oligonucleotides allow us to differentiate the constituent bases of SNPs on genomic DNA in solution. We designed an unlabeled oligonucleotide primer that anneals immediately adjacent to the SNP site and a fluorescent oligonucleotide reporter that anneals opposite the SNP site. We add ligase to covalently attach the reporter to the primer. After heating a sample to dissociate template and unannealed reporter, we capture the primer-reporter complex on microspheres and use flow cytometry to measure the microsphere fluorescence.

We can multiplex this oligonucleotide ligation assay by using different sized or different colored beads to capture different primers. Thus, we simultaneously measure the SNP frequency at multiple sites in a single individual or pool of individuals. We tested these methods on sequences with known polymorphic features and on samples from patients with beryllium sensitivity, a condition associated with a specific polymorphism.

In the first year of the project, we demonstrated the feasibility of a microsphere-based, flow-cytometric oligonucleotide ligation assay for the glu69 variant of HLA DPB1 (a gene that codes for a cell-surface protein) exonII that is associated with chronic beryllium disease. In the second year, we optimized our microsphere-based assay in several respects. First, we determined the optimum concentration of reagents (primers, template, and enzyme) and reaction conditions (temperature, number and duration of thermal cycles) required for accurate determination of

the SNP identity. This allowed us to perform an assay that is both rapid and cost effective. Second, we began to develop conditions for the multiplexed analysis of SNPs, allowing multiple genetic variants to be screened simultaneously and enhancing the predictive power of our screening assay. We also developed methods for the covalent conjugation of synthetic oligonucleotides to microspheres, an essential step in providing assay kits that are both robust and have extended shelf lives.

This year we developed methods for detecting multiple nucleotide bases at multiple sites simultaneously and optimized conditions for analyzing several SNPs simultaneously. Our method offers the most efficient means available for screening diagnostic SNPs. We have now extended the basic method we developed in this project to new, funded applications in bacterial pathogen detection, viral genotyping, and other areas related to human health.

Publications

Cai, H., et al., "Flow Cytometry Based Minisequencing: A New Platform for High Throughput Single Nucleotide Polymorphism Analysis," *Genomics* **66**, 135 (2000).

Nolan, J.P., et al., "SNP Scoring for Drug Discovery Applications," in *Integrated Drug Discovery Technologies*, H.-Y. Mei and A. Czarnik, Eds. (Marcel Dekker, New York, in press).

Next Generation of Molecular Dynamics: Implicit Solvent/Langevin Models for Folding of Peptides and Proteins

98008

Gerhard Hummer

How do proteins fold and what are the mechanisms and forces underlying protein stability and complex formation? How can small changes in the amino acid sequence result in disease-causing conformational variability and aggregation? What role do large-scale motions play in enzyme activity? These questions are central to structural biology. A unique theoretical method could, in principle, help to address them: molecular dynamics (MD) simulation. However, typical simulations extend only into the nanosecond range, 2 to 4 orders of magnitude short of folding and aggregation phenomena. We developed the tools needed for constrained Langevin dynamics simulations with effective, solvent-averaged potentials instead of conventional Newtonian dynamics with vacuum interactions. We studied, through these theoretical means, the initial phases in peptide and protein folding.

MD simulations are widely used in structural biology, with applications to experimental protein-structure refinement and theoretical studies of protein dynamics and function. MD studies of proteins are computationally demanding because of the explicit treatment of solvent water and the short time steps imposed by fast bond vibrations. To overcome these limitations, we have developed effective, solvent-averaged potentials, thus eliminating explicit water, and a stochastic Langevin dynamic with constrained bonds and bond angles. With these improvements, we expect a third-order-of-magnitude gain over conventional MD simulations, which will allow us to study microsecond dynamics of peptides and proteins.

Extensive molecular dynamics simulations of alanine- and glycine-based peptides allowed us to develop a detailed understanding of molecular mechanisms involved in α -helix formation. We showed that the unfolding kinetics for these short peptides is a thermally activated process. Folding, on the other hand, was shown to be controlled by diffusion in conformation space for a fast-folding peptide. For a peptide with sequence-induced folding traps (that is, enthalpically stabilized conformations competing with the helical folded state), thermal activation controls escape from the intermediate states, followed by conformational diffusion.

We could also quantify the many-body effects in hydrophobic interactions, which form a major bottleneck in the development of accurate solvent-averaged potentials. Hydrophobic interactions are a major stabilizing factor for folded proteins. Their strong, many-body character is frequently approximated by surface-area models. However, surface-area descriptions are ill suited to dynamics calculations and lack the molecular detail required for accurate energetics. We developed an alternative force-field description with a surprisingly simple quantification of many-body terms. This force field proved accurate for structural variations at both small- and intermediate-length scales, such as forming a model of a protein hydrophobic core. We also obtained promising results using this force-field model for characterizing protein surfaces as targets in drug development.

Publications

Garcia, A.E., et al., "Solvent Effects on Protein Folding/Unfolding," *Prog. Theor. Phys.* **138**, 282 (2000).

Hillson, N., et al., "Pressure-Induced Protein Folding/Unfolding Kinetics," *Proc. Natl. Acad. Sci. U.S.A.* **96**, 14848 (1999).

Hummer, G., et al., "Conformational Diffusion and Helix Formation Kinetics," *Phys. Rev. Lett.* **85**, 2637 (2000).

Onuchic, J.N., et al., "The Energy Landscape Theory of Protein Folding Mechanisms and Scenarios," *Adv. Protein Chem.* **53**, 87 (2000).

Fundamental Process in Polymer Light-Emitting Electrochemical Cells

98011

Darryl L. Smith

In this project, we described experimental and device model results for the properties of a new class of light-emitting polymer devices, polymer light-emitting electrochemical cells (LECs). The devices consist of a polymer, both luminescent and ionically conductive, into which an ionic salt is dissolved. The resulting film is contacted by two electrodes, and when a sufficiently large voltage bias is applied, ions from the dissolved salt are spatially separated. The ions dope the polymer, making it electrically conductive. An electrical junction forms between the *p*-type doped material near the positively biased contact and the *n*-type material near the negatively biased contact. Electrons injected from the *n*-type side of the junction recombine with holes injected from the *p*-type side of the junction, emitting light.

These devices have five species of interest: electrons, holes, anions, cations, and associated salt molecules. The contacts are ohmic for electrons and holes, so that the current flow is limited by the bulk of the device and not by the contacts, and they are blocking to anions and cations, so that the ions are not exchanged with the contacts. Because the contacts are blocking to the ions, there is no ionic current flow at steady state. Ionic conductivity is necessary to establish the steady-state conditions, and the ionic mobilities play an important role in the time response of the device, but they do not influence its steady-state properties. When a small steady-state voltage bias is applied to the LEC, the voltage drop across the contact double layers simply adjusts, and the center of the device remains charge neutral and field free.

Polymer LECs offer a number of potential advantages over organic light-emitting diodes, including insensitivity to variations in device thickness and to the type of metal used to form the contacts. Thus, LECs could provide highly energy-efficient solid-state lighting and display technologies. Our research in this area supports the DOE mission in energy conservation.

Publications

Crone, B.K., et al. "Device Model Investigation of Bilayer Organic Light Emitting Diodes," *J. Appl. Phys.* **87**, 1974 (2000).

Crone, B. K., et al., "Device Physics of Single Layer Organic Light-Emitting Diodes," *J. Appl. Phys.* **86**, 5767 (1999).

Computational Studies of the Role of Water Fluctuations in Protein Dynamics and Folding

99006

Angel Garcia

The purpose of this project is to elucidate the role of water dynamics in mediating large-scale fluctuations, ligand binding, and unfolding/folding transitions of proteins. We study the stability, dynamic fluctuations, and early unfolding events in proteins by performing extensive molecular dynamics simulations. We are developing an atomic-level description of hydrogen exchange that describes hydrogen protection factors, taking into account protein dynamical fluctuations, hydration structure, and water relaxation. We study the kinetics of water penetration into the hydrophobic core of proteins under various conditions to understand the mechanism of small ligand binding to the protein interior. We are testing the recently postulated hypothesis that pressure-induced protein denaturation occurs via water penetration into the protein hydrophobic core. This work supports Los Alamos' program in genomics by elucidating genetic control mechanisms for cellular function.

We have studied the rate of water penetration in cyt c, an electron transport protein involved in metabolism. We found that water extensively penetrates the protein hydrophobic interior. The entropy of water in the protein interior is the same as in bulk water. Water molecules penetrate in pairs, thus reducing the energetic cost. Large motions of water in the protein result in a negligible entropy upon penetration. Extensive molecular dynamics simulations on Snase, a DNA binding protein, show that water also penetrates the protein hydrophobic core, consistent with high resolution x-ray data obtained by our collaborator at Johns Hopkins University. We found that water occupies regions in the protein interior that can support mutations of nonpolar groups to charged and polar groups. This finding suggests that interior water molecules are responsible to the larger dielectric constant (a measure of the ability to screen electrostatic fields) measured in the protein interior.

We plan to study the role of hydrostatic pressure in inducing protein unfolding. Proteins unfold when subject to hydrostatic pressures of 2–5 Kbar, suggesting that the volume of the unfolded protein is reduced upon unfolding. Theoretical models we developed suggest that this unfolding is driven by water penetration into the protein hydrophobic interior that reduces the total volume of the protein-solvent system. To study this unfolding transition,

we are developing a hybrid molecular Dynamics/Monte Carlo approach to efficiently simulate the equilibrium number of interior water molecules as a function of pressure. This approach allows the exchange of water molecules from the bulk water phase to the protein interior by insertion attempts, without following the water penetration trajectories. We will employ enhanced sampling techniques to accelerate the system equilibration at various temperatures. We are conducting simulations of protein unfolding on Snase, which has been extensively studied by nuclear magnetic resonance and optical spectroscopy and by neutron scattering.

Publications

Garcia, A.E., et al., "Solvent Effects on Protein Folding/Unfolding," *Prog. Theor. Phys. Supp.* **138**, 282 (2000).

Garcia, A.E., et al., "Theoretical and Computational Methods of Biomolecular Hydration," in *Hydration at Interfaces*, M. Morra, Ed. (John Wiley & Sons, London), in press.

Hummer, G., et al., "Conformational Diffusion and Helix Formation Kinetics," *Phys. Rev. Lett.* **85**, 2637 (2000).

Hummer, G., et al., "New Perspectives on Hydrophobic Effects," *Chem. Phys.* **258**, 349 (2000).

Onuchic, J.N., et al., "The Energy Landscape Theory of Protein Folding Mechanisms and Scenarios," *Adv. Prot. Chem.* **53**, 87 (2000).

Sanbonmatsu, K.Y., and A.E. Garcia, "Structure of Met-enkephalin in Explicit Solvent Using Replica Exchange Molecular Dynamics" (submitted to *Proteins: Struct., Funct., Genet.*).

Vigil, D., et al., "Functional Dynamics of the Hydrophobic Cleft in the N Domain of Calmodulin" (to be published in *Biophys. J.*).

The Molecular Aging Clock

99007

Teresa Ruscetti

We hypothesize that control of the DNA repair processes in ribosomal DNA (rDNA) is critical during the aging process. We are currently investigating other age-related genes to understand how recombinational repair in rDNA is controlled during the aging process.

In *Saccharomyces cerevisiae*, the aging process is linked to the formation and accumulation of extrachromosomal circles of DNA. These circles are derived primarily from the rDNA array, which is a linear array of 9.1-kbp repeats (160–200 copies) important in ribosome biogenesis. The senescent phenotype may be the result of accumulation of these rDNA circles, which sequester key enzymes in the replicative and ribosome biosynthetic pathways. Formation of rDNA circles must arise as an excision/deletion event following recombination, perhaps because of a double strand break (DSB).

This year, we developed an assay system that allows us to measure recombinational repair in the rDNA array. We integrated a recombination substrate consisting of direct repeats in which a DSB can be introduced into the rDNA array on chromosome XII and at a non-rDNA locus on chromosome V. In rDNA, the frequency of recombination was six-fold lower than the non-rDNA site (2.5% versus 15%). Most (70%) recombination on chromosome V yielded a deletion event, but we did not detect deletion events in rDNA (<0.0002%). The assay system allowed characterization of recombination tract lengths and direction. The average tract length in rDNA was short (96 bp), and all tracts were unidirectional, extending only 5 ft to the DSB. Outside rDNA, average tract length was considerably longer (362 bp), and 44% of tracts were bidirectional. Because Sir2p is known to function in rDNA silencing and lifespan, we also examined the effect of *sir2* mutation on rDNA-specific recombination. We found that *sir2* increased both the frequency of recombination (two-fold) and the average tract length (176 bp). However, the *sir2* mutant had no effect on deletion or tract direction. These results indicate that DSB repair in rDNA is strictly regulated to minimize deletion of rDNA repeats and that this regulation is largely independent of Sir2p function.

Publications

Ruscetti, T., et al., “Ionizing Radiation Induces Immediate Relocalization of PARP and DNA-PKcs” (submitted to *Radiation Research*).

Ruscetti, T., “Repair in Ribosomal DNA and Aging” (Workshop on Aging, National Institute on Aging, Washington, D.C., November 16–17, 2000).

Hyperthermophile Biocatalysis: The Molecular Basis of Enzyme Stability and Activity

99008

R. Brian Dyer

Hyperthermophile enzymes offer enormous potential as biocatalysts for industrial synthesis, biomass conversion, and bioremediation. This potential is one of the principal drivers for the many DOE-sponsored genome-sequencing efforts recently completed or still underway on hyperthermophilic organisms. Realizing this potential requires a more complete understanding of the molecular basis of the thermal stability and activity of hyperthermophile enzymes. The complex interplay between enzyme stability and activity has led to contradictory hypotheses regarding the coupling of the two, with important implications for the design of enhanced catalysts. Recent advances in the structural determination and genetic manipulation of these enzymes combined with new laser spectroscopic methods for probing functional dynamics developed in our laboratories offer the unique opportunity to resolve these issues. We have chosen the enzyme lactate dehydrogenase (LDH) as a model system in which to determine the relationships among stability, dynamics, and catalytic activity. We are studying the effects of thermal stability in a homologous series of enzymes from mesophiles (human, pig), thermophiles (*Bacillus stearothermophilus*), and hyperthermophiles (*Thermotoga maritima*).

We are exploring the role of K_m versus k_{cat} (how k_{cat} differs between mesophiles and hyperthermophiles) and the coupling of the maximum catalytic rate to the temperature of thermal denaturation for LDH. Our unique approach employs structure-specific spectroscopic probes, including vibrational and fluorescence spectroscopies combined with time-resolved techniques and laser methods for rapid reaction initiation, including T-jump and pH-jump. We have demonstrated that the key catalytic activation step in LDH is the polarization of the carbonyl bond of pyruvate, most likely because of a hydrogen bond between the CO and the protonated His-195. This interaction is reflected in the IR spectrum as a 35-cm^{-1} shift of the CO stretch, corresponding to a 14–17 kcal/mole stabilization of the reaction coordinate. We have also measured the rate of hydride transfer ($2 \times 10^5 \text{ s}^{-1}$), the T-R transition (flap closure, 750 s^{-1}), and the bimolecular ligand association ($4 \times 10^7 \text{ M}^{-1}\text{s}^{-1}$) for the human enzyme. These measurements provide the first glimpse of the details of this reaction and of the coupling of protein dynamics to the substrate binding and activation.

Publications

Dyer, R.B., et al., “The Rate of Hydride Transfer from NADH to Pyruvate in Lactate Dehydrogenase” (submitted to *Biochemistry*).

Gulotta, M., et al., “Difference FTIR Studies of Pyruvate Activation in Lactate Dehydrogenase” (submitted to *J. Am. Chem. Soc.*).

New Approaches to High-Throughput DNA Sequence Validation

99009

P. Scott White

An important component of sequencing DNA for any genome project is quality control. Natural genetic variation should be distinguished from errors in the reporting sequence. We are developing flow cytometry assays to discriminate between errors and natural variation. This discrimination is important to anyone using public DNA databases.

To be cost-effective, assays must be run simultaneously. The primary focus of this project is to develop sets of DNA tags that can be used to perform many assays simultaneously for the cost of a single assay. The tags are designed from mathematical algorithms (codes) used in information theory and promise high levels of multiplexing with minimal additional assay design and development. Once developed, the code-designed DNA tags can be applied to a wide variety of assays, with applications in biothreat reduction, environmental microbiology, comparative genomics, gene mapping, and DNA sequence validation.

We have developed two approaches to generating DNA tags. One uses error-correcting codes; the other is random. Randomly generated DNA tags currently show the most promise for use in our flow cytometry assays. One hundred such tags have been chemically synthesized, and several of them have been successfully assayed. An earlier set of 16 DNA tags generated with the error-correcting codes is also being used. All sequences are being tested with a commercially available 100-bead array (microsphere set). The overall percentage of DNA tags that are predicted to be useful has improved dramatically as a function of improvements in the algorithms.

Once successful with a 100-bead array, we will apply our mathematical algorithms to resequencing clone DNA for sequence validation. This resequencing will be performed directly from bacterial artificial chromosome (BAC) clone DNA instead of from polymerase chain reaction products, and the sensitivity will be optimized in order to successfully perform assays. The resequencing will draw from our expertise in BAC end-sequencing for the Center for Human Genome Studies here at Los Alamos.

Publications

Cai, H., et al., "Flow Cytometry-Based Minisequencing: A New Platform for High Throughput Single Nucleotide Polymorphism Analysis," *Genomics* **66** (2), 135 (2000).

Nolan, J.P., et al., "SNP Scoring for Drug Discovery Applications," in *Integrated Drug Discovery Technologies*, H.-Y. Mei and A. Czarnik, Eds. (Marcel Dekker, New York, in press).

Development of a Superconducting Quantum Interference Device (SQUID) Microscope for Imaging Cortical Neuronal Columns

99010

Robert H. Kraus, Jr.

This project is designed to develop a unique magnetic-field microscope to image cortical and brain stem activity and function with high spatial and temporal resolution. The microscope uses a Superconducting Quantum Interference Device (SQUID) sensor array and a superconducting image-surface (SIS) concept patented by the Laboratory. The SIS both produces a gradiometric field at the sensor array for nearby sources and shields the array from ambient background fields. The system was to be optimized to obtain spatial resolution better than 300 μm and temporal resolution better than 0.5 ms for in vivo measurements of neuronal columns. Imaging the activity of individual neuronal columns with high temporal resolution will provide a new level of understanding of the connectivity and communication between individual columns and the propagation of signals and information within the brain.

We made good progress this year, despite the drastic cut in funding. We obtained four linear SQUID arrays from a spin-off company in Jena, Germany, closely coupled with the collaborating laboratory there. Each unique high-critical-temperature SQUID array consists of 11 SQUID sensors on a single substrate and represents the only devices of their kind in the world. We have completed extensive testing of cross talk between the sensors, one of the most critical parameters, with exceptional results. Measured cross talk for all channels is now below 90dB, a result in most cases limited by our capability to measure the cross talk. The noise performance of these SQUIDs is better than 500 fT/sqrt(Hz), well within our requirements and extremely encouraging for this effort.

In addition, we have completed resolution measurements with single arrays to determine sensitivity and found that our ability to discriminate between neighboring sources is better than 120 microns at a sensor-source separation of 1 millimeter. This limitation is based on the source spacing of our phantom (~120 microns). We have fabricated and completed initial tests on a new SQUID microscope dewar, based on technology developed for and lessons learned

from the system built for the Enhanced Surveillance Program. The dewar employs a unique stainless design with extremely thin integrated windows near the SQUID arrays to minimize Johnson noise from the metal. We have measured the Johnson noise contribution and found it to be at least an order of magnitude below the array sensor noise floor. We are currently designing a dewar insert for mounting the SQUID arrays. In summary, we have completed approximately half of the goals outlined in the original LDRD proposal, an effort greater than the relative level of funding received for the effort.

Rapidly Photocleavable Caged Proteins

99011

Charlie Strauss

The mechanics of protein folding is one of the outstanding unsolved problems in structural biology. The central experimental limitation is the inadequacy of biophysical methods for probing protein molecules in the act of folding. Our goal is to develop an experimentally friendly and universal approach to photo-protective caging and photo-reversible unfolding of protein domains and then to benchmark these techniques by measuring folding kinetics. Our work could be useful in numerous applications, including biosensors, photodegradable materials, and biochemical radiation detectors.

The key distinction between our approach to protein denaturation and all existing denaturation techniques is that we are not disrupting the fundamental chemical process that drives protein folding and protein dynamics. By using a large chemical cage attached to a specific amino acid in a protein, we destabilize the native state without appreciably affecting the unfolded state. In contrast, conventional guanidine and thermal denaturation work by weakening the dominant interatomic forces between protein residues.

This year we focused on the critical bottlenecks of protein solubility, cage solubility, and absorption wavelength. We worked with a collaborator from the University of Kansas, who provided three new photo-protective groups: acetylphenol, mono-methoxy acetylphenol, and dimethoxy acetylphenol. In the photo-release spectrum, these compounds showed peaks well away from the tryptophan absorption and no complicating fluorescence. However, the compounds had the undesirable properties of limited water solubility and solvent-dependent wavelengths. We have now designed an electron transfer photo-protective cage that tethers chromophore, an electron acceptor, to aminopinol, an electron donor, thus separating chemical activity and chromophore wavelength. The sulfate group and the extremely large steric bulk make us confident that these soluble cages will destabilize any protein domain.

Exposed hydrophobic regions of unfolded caged proteins promoted aggregation. Based on alanine scanning mutagenesis, we selected hydrophobic residues that did not appreciably affect the folding kinetics. We mutated these to less hydrophobic residues, which we expressed and purified.

Universal Scaling Laws in Biology: Aerobic Metabolism, Energy Use, and Longevity

2000007

Geoffrey West

A major thrust of this project is to explore and elaborate on a newly proposed set of universal principles governing energy transport in biological systems complementary to the genetic code and the principle of evolution. All life functions by transforming energy from physical or chemical sources into organic molecules that are metabolized to do the work of building, maintaining, and reproducing complex, highly organized structures and processes. Over the immense spectrum of biological size, ranging over 21 orders of magnitude in mass from the smallest microbe to the largest whale, organisms use basically the same chemical constituents and reactions to create an amazing variety of forms, functions, and dynamical behaviors. These universal principles are critical to understanding, manipulating, and managing biological systems in such diverse contexts as medicine, agriculture, and natural resource management.

Despite their amazing diversity and complexity, biological systems in almost all aspects obey remarkably simple and systematic empirical scaling power laws; for example, metabolic rate scales as the $3/4$ power of mass. Recently, we developed a general model that explains the origin of these scaling laws. It is based on the observation that all biological phenomena are constrained, and ultimately limited, by the rate at which essential resources can be supplied. Because the model provides a quantitative, testable framework for understanding these allometric relationships, it offers the opportunity of addressing many important problems, both basic and applied. Two of these that this project will look at are the cellular and molecular extension and foundation of the model and its possible relationship to the origins of aging and mortality by aerobic damage and the central role of size in biodiversity and its relationship to size and energy distributions in ecosystems. The potential benefits and applications of this work are clear: a fundamental theory of aging and mortality is central to issues of health, whereas a theory of ecosystems has potentially important implications for environmental issues such as agricultural production and carbon sequestration.

The model is based on four general principles: (1) life at all scales is sustained by hierarchical fractal-like branching network systems that are (2) space-filling; (3) the terminal branch of the network is a size-invariant unit (e.g., mitochondria); and (4) organisms have evolved so that the energy required to distribute resources is minimized. We have recently shown how the $3/4$ power scaling continues down through cells and mitochondria to the very molecules of the respiratory complex. We have calculated numbers and densities of mitochondria in cells in excellent agreement with data. The model thus strongly suggests the existence of as-yet-unidentified intracellular networks that have the properties required by the model and established for the transport networks of higher organisms. It is a key objective to test whether these networks exist, and, if so, how they are manifested in cellular structure and function. We have conjectured that the dissipative forces in the network from oxidative damage are the basic origin of aging and ultimately mortality. At the other end of the spectrum, we have recently derived the size distribution of trees in forests including their population densities and energy usage, also in excellent agreement with data.

Publications

West, G.B., et al., "A General Allometric Model of Growth" (submitted to *Nature*).

West, G.B., et al., "Allometric Scaling of Metabolism from Molecules and Mitochondria to Cells and Mammal" (submitted to *Nature*).

Third-Generation Oligonucleic Acid Analogs

2000008

Louis “Pete” Silks

The central theme of “antisense” technology is using synthetic pieces of DNA to interrupt gene function. The classical antisense approach is to create tiny bits of so-called antisense DNA that bind to and therefore interfere with the messenger RNA (mRNA) gene product implicated in a disease.

In this project we take a new approach to the development of oligomeric analogs to nucleic acids that uses a novel molecular core called a piperazine (see Fig. 1). The expected advantages of these oligonucleic acid analogs (ONAAAs) are improved binding to complementary strands (relative to their natural counterpart) and increased resistance to biodegradation. Furthermore, we expect the uncharged analogs in this new class of ONAAAs to exhibit improved bioavailability, including cellular uptake. Monomers of these types of molecules are attractive candidates for drug development, particularly for fighting viral infections such as HIV and herpes simplex.

Our analogs are designed to be similar to natural DNA and RNA in the way that they encode genetic information and interact with their natural counterparts. These oligomeric analogs can potentially be used as biomolecular tools for antisense and antigene applications. Current examples for applications of similar ONAAAs in the literature include blocking genomic information in medical applications, such as blocking a disease gene, or identifying the function of gene sequences.

Our project directly relates to the functional genomics project at Los Alamos and DOE. In addition, it supports the following scientific thrust areas of the Laboratory’s Bioscience Division: threat reduction, structural genomics, functional genomics, biomedical sensors, and natural and engineered biochemical diversity.

We have established a general synthetic route to both ketopiperazines and piperazines. We have synthesized the thymidine analog and are currently using these monomers on a standard solid-phase DNA synthesizer. Our nuclear magnetic resonance (NMR) investigation of this advanced monomer confirmed essential structural elements of our initial molecular modeling studies. Next year we will develop assays to evaluate binding and hybridization of oligonucleotide analog strands to their natural DNA and RNA complements, mismatch tolerance, and self-binding.

In addition, we will use two-dimensional NMR methods and restrained molecular dynamics to determine the solution structures of piperazine oligonucleotides and their DNA and RNA hybrids.

We are working to protect the Laboratory’s intellectual property on the monomers and applications of the oligomers, and the Laboratory has approved submitting a patent application. When the application has been sent to Utah for processing, we can begin to publish our research.

Thymidine ONAA

Fig. 1. Molecular components of a thymidine monomer suitably protected for solid phase syntheses.

Coordination of Carbon and Nitrogen Metabolism

2000009

Pat J. Unkefer

Biotechnologies based on controlling plant growth are attractive options for increasing the sequestration of atmospheric carbon and thus reducing the environmental impact of burning fossil fuels. Developing biotechnologies to control the growth of plants and all other photosynthetic organisms requires understanding the organisms' regulatory system coordinating their assimilation of carbon and nitrogen. We combined two innovative tools to investigate the complex regulation of carbon and nitrogen metabolism: metabolic control and DNA microarray analysis. We have recently discovered a metabolite that sharply increases the rates of carbon fixation, nitrogen assimilation, and overall plant growth. DNA microarray analysis allows us to survey the genome to identify changes in gene expression that the metabolite induces. We are identifying enzymes whose gene expression is altered, measuring their activities, and then correlating metabolic changes with observed changes in gene expression. With this information, we will develop a comprehensive model of coordinating carbon and nitrogen metabolism.

This year we determined that the activation state of the carbon dioxide-fixing enzyme, ribulose biphosphate carboxylase, is sharply increased in metabolite-treated plants. This finding is an important key linking increased carbon metabolism with changes in gene expression because the activity that changes the activation state is controlled completely by changes in gene expression. We showed that the enzyme phosphoenol pyruvate carboxylase is also increased. We identified, isolated, and sequenced the gene encoding for the enzyme synthesizing the metabolite. This information will allow us to probe for any changes in the expression of this enzyme, an activity essential to formulating an accurate model of the coordination of carbon and nitrogen metabolism. We have now inserted the gene into transformation vectors for both bacteria and for plants; the transformations have been accomplished. We are screening the transformed plants for the expression transgene. Allowing the transformed plants to mature will enable us to test in plants derived from seeds so that we can avoid the impacts of the regeneration of the plants from single cells. We carried out a time course of the effects of treatment and determined the relative order for the effects on amino acid biosynthesis, carbon dioxide fixation, nitrogen uptake and storage, and nitrate reduction.

Publications

Knight, T.J., and P.J. Unkefer, "Impacts of Altered Roles of Leaves and Roots for Nitrogen Assimilation: Effects on Carbon Metabolism" (to be submitted to *Plant Physiol.*).

Knight, T.J., and P.J. Unkefer, "Impacts of Altered Roles of Leaves and Roots for Nitrogen Assimilation: Effects on Nitrogen Metabolism" (to be submitted to *Plant Physiol.*).

Knight, T.J., and P.J. Unkefer, "Selective Inactivation of Glutamine Synthetase: Utility of this System to Study Plant Metabolism" (to be submitted to *Plant Physiol.*).

DNA Repair and Molecular Assembly Involved in Chromosome Condensation

2000010

Robert Cary

We have identified a physical interaction between a DNA double-strand break (DSB) repair protein and a member of the structural maintenance of chromosomes (SMC) protein superfamily. SMC proteins have been implicated in nonhomologous DNA repair, recombination repair, and mitotic chromosome condensation, but this is the first link between the DSB repair complex and a protein involved in the structural modulation of chromatin in mammalian cells. The interaction we identified thus represents a critical and previously unknown link between higher-order genetic organization and the cellular response to radiation-induced damage of our genetic material.

Our goal is to characterize the large multiprotein complex that includes DSB repair and SMC proteins and reveal the complex's role in the cellular response to ionizing-radiation-induced DNA damage. This work contributes directly to a mechanistic molecular understanding of the biological response to radiation damage of DNA in humans and is, therefore, of significant relevance to both Laboratory and DOE missions.

In this first year of the project, we obtained data that suggests a subset of centromere binding proteins may play an important role in DNA damage repair. To understand the role of these centromere binding proteins in DNA repair, we have determined the subcellular location and co-localization of four proteins critical to our work. Moreover, to facilitate the detailed characterization of the proteins, we generated a stable transgenic cell line expressing a key member of the complex under study. This cell line will be used to purify the multiprotein complex.

In addition, we have identified a novel protein: a new member of a family of centromere binding proteins that interacts with XRCC4, a small protein required for DSB repair. We have generated antibodies to this protein and another member of the complex and are using these antibodies to confirm the physical interactions between members of the complex. We have already confirmed that the SMC protein component of the complex is a protein required for higher-order chromosome structure. Using a

reverse transcriptase-polymerase chain reaction, we have obtained data on the expression level of the centromere protein in different tissues and have cloned a full-length cDNA encoding this protein.

Publications

Stewart, P.L., et al., "Digitally Collected Cryo-Electron Micrographs for Single Particle Reconstruction," *Microsc. Res. Tech.* **49**, 224 (2000).

Yannone, S.M., et al., "PARP Stimulates Ligation by Human DNA Ligase IV" (submitted *J. Biol. Chem.*).

Characterization of Exceptional Chromosomal Regions by DNA Sequencing

2000011

Michael Altherr

Only recently, a draft sequence of the human genome was announced. To date, the bulk of research has focused on segments associated with protein coding sequences. However, estimates suggest that as much as 90 percent of the genome of vertebrates does not encode mRNAs, the precursor to protein. Much of this exceptional noncoding genomic sequence is composed of a variety of repeat sequences. Repeat structures complicate sequencing efforts as they result in cloning artifacts and significantly complicate assembly algorithms. However, their importance in biological processes cannot be underestimated.

Our goal is to understand the function and structure of the exceptional noncoding chromosomal segments. The success of this project is dependent on three distinct components: (1) isolating exceptional chromosomal segments through molecular cloning, (2) rendering the exceptional chromosomal segment “sequenceable” while maintaining its overall structural integrity, and (3) sequencing, assembly, and analysis of the segment.

We have chosen to model this effort on the exceptional genomic segment contained in the D4Z4 locus located on human chromosome 4. The D4Z4 locus contains an approximately 150-kbp EcoRI restriction fragment composed of nearly identical 3.3 kbp repeats. We are isolating the D4Z4 locus by preparative pulsed field gel electrophoresis in advance of cloning in a bacterial artificial cloning system (BACs). Following cloning in BACs, we will use Transposon Bombing to tag the intact locus. In this way, we will maintain the structural integrity of the D4Z4 locus while placing sequencing primer sites along its length. We can then map the tagged clones with the goal of developing an overlapping set of sequenceable substrates.

Part of the motivation for sequencing these exceptional regions is our hypothesis that the homogenous nature of these repetitive segments is maintained evolutionarily by some functional necessity. We know from some limited sequencing of individual repeat units that these elements share over 99% sequence identity. Consequently, it is necessary to have a high degree of sequence accuracy to take advantage of sequence analysis tools, particularly in the areas where real differences occur. These features will ultimately be examined for their biological function.

Studying the Spread of HIV Using Genetic Sequences

2000054

Tanmoy Bhattacharya

Understanding how AIDS spreads is important to global security because large-scale pandemics destabilize entire regions of the world. Well-defined subepidemics are emerging in several Asian countries, and research could show whether these subepidemics are self-contained diversifications from a single or small number of founder cases, or whether the epidemics in various parts of the world are continually feeding each other.

Our goal is to analyze the genetic sequence of HIV from diverse geographical regions. No systematic study of the geographical patterning of epidemics of HIV subtypes existed, so we launched such a study using the supercomputers in the Advanced Computing Laboratory and the large number of HIV sequences available in the Laboratory's HIV database.

In this one-year project, we studied two sets of sequences from viruses of HIV subtype C; each with two sets of outgroups. Outgroups are used to determine the direction of the phylogenetic tree, i.e., which are the "parents" and which are the "offspring." The choice of the outgroup has a major impact on the results of the analysis. One of our data sets had a smaller number (36) of fairly long (1,417 bases) sequences, whereas the other had a larger number (47) of much shorter (1,047 bases) fragments. We used the general reversible (REV) model of point mutations with site-dependent rate of evolution.

We estimated the equilibrium frequencies, the REV matrix parameters, and the site-dependent rates using a maximum likelihood method. These estimates were then fed back to generate the most likely tree, and the answer was checked by jumbling the input order of sequences.

In all cases, we found that the sequences collected in different geographical regions clustered together, indicating that these subepidemics were started by a small number of founders. This discovery partially answered one of our questions. Our research also indicates that a larger study incorporating requisite data collection can, in principle, time the transmission events.

Single Protein Spectroscopy with Native Fluorescence

2000063

Richard A. Keller

The goal of this project is to detect and study single protein molecules by native fluorescence. Tryptophan, a natural amino acid, fluoresces when excited with ultraviolet radiation. These studies focus on proteins containing one or more tryptophan molecules. The great advantage of single molecule studies issues from the complete removal of ensemble averaging, enabling a detailed understanding of systems that would be difficult or impossible with bulk measurements. Ultrasensitive detection of proteins usually relies upon tagging the protein with a fluorescent label; this labeling can interfere with the reactivity of proteins, making detection with native fluorescence desirable. This research will extend the capabilities in single molecule studies to analyses of biomolecular structure and function.

We will use a confocal, epi-illuminated setup for ultraviolet excitation of protein fluorescence. We have focused this first year on generating the necessary ultraviolet radiation and setting up the confocal apparatus and detection electronics. We obtained 15 mW of pulsed, 280-nm light by frequency tripling the output of a titanium:sapphire laser. The fundamental output of the Ti:sapphire (~840 nm) is first frequency doubled with a lithium triborate (LBO) crystal. We separate the doubled output from the fundamental with a dichroic beam splitter. The polarization of the second harmonic is rotated 90° and is recombined with the fundamental, which has been suitably delayed, and focused into a β -barium borate (BBO) crystal. We separate the resulting 280-nm radiation from the fundamental and second harmonic with a dispersing prism. The ultraviolet radiation passes through a dichroic beam splitter and is focused by a quartz microscope objective (NA 1.25, 40 $\times$) to a diffraction-limited spot (~0.3 μ m) in the sample droplet. Fluorescence from the sample is collected by the same objective, reflected by the dichroic beam splitter, and focused onto a pinhole located in the image plane of the objective. We filter the fluorescence transmitted through the pinhole to discriminate against scattered excitation light and then detect it with a photomultiplier tube. We will use pulsed excitation and time-correlated, single-photon counting for further discrimination against scattered excitation light.

Sensitive Mass Spectroscopic Analysis of Biomolecules in the Megadalton Range

2000066

Vahid Majidi

Currently, only a limited number of technologies (gel electrophoresis and flow cytometry) are routinely used for detecting large biomolecules. Mass spectrometry (MS) potentially offers extremely high sensitivities and unmatched resolving power. However, its limited instrumental mass range (several hundred kilodaltons) seriously hinders its routine application for evaluating biomolecular complexes. The importance of megadalton biopolymer detection is illustrated in the following example: An easy method to identify bacteria (for example, *E. coli*) is to use specific enzymes to digest the DNA into a certain number of fragments (about a dozen), and then to evaluate the size (or mass) of each fragment. The fragments have a typical size of 64 kbp (~40 megadalton), which is beyond the range of current mass spectrometric instrumentation. Our approach, to extend the analytical mass range, will pave the way for rapid and sensitive ultrahigh-molecular-weight detection of biomolecules, ultimately facilitating direct mass-spectrometric detection of protein/DNA and protein/protein complexes. These tools can be used for rapid and high throughput identification of pathogens.

In the past several months, we evaluated an ion gun and electron gun for larger molecule dissociation. We put an ion lens into the flight path to focus the ion beam into a small cross-section beam (3 mm in diameter). A phosphor screen was used to observe beam cross-section and alignment. During cesium ion gun experiments, we did not observe significant signal intensity change from the micro channel plate (MCP) detector.

Next, we mounted a Faraday Cup opposite to the cesium/electron gun, where the variation of primary beam could be monitored. Experiments showed that the current variation from Faraday Cup is more sensitive to large molecules, most likely because of the large cross-section of large biomolecules. More interestingly, some large M/Z ions that are not obvious in the MCP spectrum were clearly observed in the signal from Faraday Cup.

Novel Mass Tagging with Stable Isotopes in Postgenomic Studies

2000071

Xian Chen

In parallel with the DNA sequencing projects of the US DOE Joint Genome Institute, there is an urgent need to establish a genome-based biological analysis and diagnostic capability. This effort would be directed toward an understanding of the sequence–function relationships associated with chromosome functions, genetic diseases, and human susceptibility to radiation- and chemical-induced diseases. New technologies applied in postgenomic studies need to handle an estimated 60,000 genes in the human genome. The current limitation of dealing with only one gene at a time makes it difficult to come to an overall understanding of the secret of human life. Consequently, because of its speed, accuracy, and sensitivity, mass spectrometry (MS) is the most promising tool for analyzing human genes and their products on a large scale. Our novel use of stable isotopes to signature biological molecules in a sequence-specific way will dramatically enhance the specificity, accuracy, sensitivity, and throughput of MS-based technology in the context of functional genomics.

For example, we have successfully demonstrated proof-in-principle that site-specific mass tags can be used as internal markers in the identification of *E. coli* protein mixtures. In addition, our observations have suggested that the concept of mass tagging is generally applicable to eukaryotic cells. We have also shown that site-specific mass tags can be used as internal markers in protein sequencing and that this process is readily applicable to facilitate the sequencing of selected DNA fragments by MS.

Publications

Chen, X., et al., “Site-Specific Mass Tagging with Stable Isotopes in Proteins for Accurate and Efficient Protein Identification,” *Anal. Chem.* **72**, 1134 (2000).

Chemistry

Unraveling Heterogeneous Surface Reaction Kinetics

98012

William Patrick Ambrose

For this work we proposed to observe and study the nature of the interactions between individual immobilized and individual solvated molecules. Our specific aims were to (1) develop wide-field fluorescence microscopy with a capability to observe individual fluorescent molecules binding to molecules immobilized on the wall of a flow channel; (2) develop a flow system to allow reproducible and quantitative delivery of reagents to molecules bound on a surface; (3) use these enhanced capabilities to measure the single molecule behavior of a variety of model systems including receptor-ligand binding and enzymatic activity. We accomplished the first and second goals during the first two years of the project.

In this final year, funding for the project was reduced. With our limited funds, we attempted binding and enzyme activity studies of a fluorescently labeled DNA template to immobilized human immunodeficiency virus reverse transcriptase (HIV-RT).

A collaborator from the University of New Mexico in Albuquerque provided the biological materials and sample preparation protocols. The DNA was linked to a fluorescent label. We immobilized the HIV reverse transcriptase on the wall of a perfusion chamber. We flowed labeled DNA through the perfusion chamber and observed binding of the DNA to the wall at the single DNA molecule level. A characteristic signal related to the enzyme activity of the DNA-RT complex that we expected to see was not observed. Determining whether the expected characteristics of our hypothesized transcription signal are correct or if we need to change sample protocols would require additional work.

Soluble Polymers for Enhancing Biocatalysis

98013

Nancy N. Sauer

Natural and synthetic soluble polymers have been known to enhance enzymatic activity and stability, but there has been limited information correlating functional changes in enzymes with specific polymer-enzyme interactions. In this project, we enhanced understanding of the molecular interactions between synthetic soluble polymers and enzymes. Such interactions affect biocatalysis. Our results could increase the utility of biocatalysts for synthetic applications such as sensors, waste treatment, and decontamination.

This year we focused on the impact of the polymers on enzyme activity. We studied the effect of polymer structure on enzyme stability and the stabilization of enzymes in organic media. In contrast to 12- to 450-fold enhancements of enzyme stability in the presence of polymers, the effects of polymers on subtilisin steady-state kinetics were subtle. We found that K_m , which is a measure of the affinity of an enzyme for a substrate, varied about 30% between the polymers, the monomer surrogates, and the buffer. We also found that K_{cat} , which measures how quickly an enzyme converts a substrate, decreased modestly from its value in the buffer, decreasing roughly 10% in polyacrylic acid to roughly 37% in polyethyleamine (PEI), a commercially available cationic polyamine PEI-SO₃, a PEI derivative. Notably, the K_{cat}/K_m values for polymeric species do not differ greatly from those measured for the monomer salts.

This data indicates that the effects of the polymers on the subtilisin-catalyzed hydrolysis of a substrate are much less significant than their effects on subtilisin inactivation. This observation is consistent with the model that simple surface interactions between the polymers and enzymes are responsible for enzyme stabilization.

For the enzyme yeast alcohol dehydrogenase (YADH), PEI affects activity substantially. The maximum velocity for YADH activity is increased by approximately 30% in the presence of PEI. This increase in activity may result from a combination of factors; however, one way that amine polymers could increase measured YADH activity is by limiting the back reaction of the aldehyde product. Amine functions undergo a Schiff's base condensation with aldehydes to give amides. We studied YADH kinetics in the presence of semicarbazide to prevent the reverse reaction

from contributing to the measured oxidation rates. We tested our theory by experiment and concluded that the measured increase in YADH activity with amine polymers like PEI and PEI-SO₃ likely resulted from inhibition of the conversion of aldehyde back to alcohol in the reverse reaction.

We also evaluated the effect of polymer structure on enzyme stabilization. We determined the enzyme kinetics of YADH under several conditions for three amine polymers: PEI (branched), polyvinyl amine (linear), and a commercial starburst dendrimer (spherical). While PEI consistently stabilized alcohol dehydrogenase to deactivation, polyvinyl amine showed little stabilization over standard buffer solutions. In contrast, the starburst dendrimer had a highly negative effect on enzyme stabilization.

These results suggest that multiple polymer-enzyme surface interactions are important in stabilization. To assess this possibility, we studied enzyme stabilization in organic solvents. Unlike stabilization of enzymes in aqueous solution, where all polymer systems stabilized activity for both enzymes, stabilization of enzymes in organic solvents such as alcohols was very system dependent—that is, dependent upon which enzyme and polymer were present.

Publications

Foreman, T.M., et al., "Effects of Water-Soluble Polymers on the Stabilization and Activity of Yeast Alcohol Dehydrogenase and Subtilisin Carlsberg" (submitted to *Biotechnol. Bioeng.*).

Alkane Chemistry of Ligated (Allyl)Iridium Moieties on Metal Oxide Supports and Multilayer Hydrogen Transport Membranes

99012

R. Tom Baker

Many industrial chemicals are derived from alpha-olefins that are in turn derived from the high-temperature “cracking” of petroleum feedstocks. The cracking process results in the formation of undesirable products, including H_2 , that require many separation and purification steps. Large energy savings plus waste reduction would be realized if alpha-olefins could be obtained directly from low-temperature dehydrogenation of the alkanes in natural gas.

Recent reports of new low-temperature iridium complex catalysts developed by university researchers Jensen and Goldman prompted us to pursue the combination of alkane dehydrogenation processes with a novel multilayer hydrogen membrane. Our objective is to construct a catalytic membrane reactor to convert alkanes to high-purity alpha-olefins and hydrogen.

Our initial approach was to generate a new class of low-temperature iridium catalysts that were bonded to the oxygen atoms of a metal oxide coating on the palladium surface of a multilayer (Pd/V/Pd) hydrogen membrane (Fig. 1). We studied the ligand chemistry of tris(allyl)iridium and found that the carbon monoxide product is sufficiently reactive with alcohols (such as triphenylsilanol) to be a suitable precursor for bonding the iridium complex to the metal oxide surface. Furthermore, we have performed hybrid density functional theory (DFT) calculations on tris(allyl)iridium and related complexes to gain a better understanding of the reactivity of iridium complexes with solid supports.

Concurrent with these studies, we prepared patterned membranes (Fig. 2), in which we could attach the iridium complex to islands of vanadium oxide in order to get better hydrogen transport from the catalyst to the membrane surface. We also prepared a graftable version of the Jensen/Goldman iridium dehydrogenation catalyst (Fig. 3) so that we can begin testing these newly patterned membranes with an established catalyst.

Publications

John, K.D., et al., “Molecular and Electronic Structure and Molecular Dynamics of $M(allyl)_3$ ($M = Rh, Ir$)” (submitted to *J. Am. Chem. Soc.*).

Fig. 1. Proposed catalytic membrane reactor for low-temperature alkane dehydrogenation.

Fig. 2. Patterned Pd/V/Pd composite hydrogen membrane.

Fig. 3. Jensen/Goldman iridium dehydrogenation catalyst modified with a siloxy group for grafting to the vanadium oxide surface.

Novel Surfactants and Micellar Chemistry for Enhanced Reactivity and Separations

99013

William Tumas

Our project goal is to develop new concepts for “biphasic” or phase-separable catalysis using dense-phase (supercritical or liquid) CO_2 when catalysts are immobilized in one phase and the reactants and/or products reside largely in a distinct liquid phase. We seek to combine the molecular design advantages of homogeneous catalysis with the separability of heterogeneous systems. Using dense-phase CO_2 allows for unprecedented control of phase behavior, solubility (of catalysts, ligands, and polymeric supports), and mass transfer through simple changes in reaction conditions (i.e., pressure, temperature).

We developed three new approaches to biphasic catalysis that enable the two phases to interact significantly during reaction and overcome longstanding mass-transfer problems. These approaches use water (H_2O)/ CO_2 emulsions, CO_2 -expandable polymer supports, and CO_2 /ionic liquid systems. Our approaches should be applicable to a wide range of reactions and should lead to enhanced separations, reactivity, and, in some cases, selectivity, over conventional organic solvents.

Our work centers on catalysis in emulsions that use only water and environmentally benign supercritical CO_2 along with water-soluble catalysts and emulsion-forming surfactants that are active at the $\text{H}_2\text{O}/\text{CO}_2$ interface. Carbon dioxide is unique because emulsions can be broken at lower pressures, allowing for efficient phase separation and catalyst recycle (Fig. 1).

Activity for even highly hydrophobic substrates is significantly higher than for conventional aqueous biphasic systems, as we observed in the hydrogenation of styrene by water-soluble rhodium catalysts (Fig. 2). We measured the turnover frequency for 1-octene as 140 h^{-1} , 1-decene as 110 h^{-1} , and 1-eicosene as 30 h^{-1} , suggesting that the reaction occurs at the $\text{H}_2\text{O}/\text{CO}_2$ interface.

The key advantages of our approaches are (1) low interfacial tension, (2) high interfacial surface area, (3) miscibility of gaseous reactants, and (4) ability to break emulsions by decreasing pressure.

In collaboration with the University of North Carolina, we developed new fluorinated copolymers that are uniform-sized beads. These beads are porous or expandable in CO_2 and can be modified with transition metal catalysts (Fig. 3). We showed that these polymers are effective recoverable catalysts for hydrogenation and hydroboration reactions.

Fig. 1. An $\text{H}_2\text{O}/\text{CO}_2$ emulsion formed from 1 wt % poly(butylene oxide)-*b*-poly(ethylene oxide) surfactant (40°C , 4000 psi). Fig. 1a. shows that after pressure is decreased (1000 psi), the system phase separates. Fig. 1b. shows the separation into a lower aqueous phase that contains the catalyst and the surfactant and an upper CO_2 phase that contains the product.

Publications

Carter, C.A.G., et al., "Enhanced Regioselectivity of Rhodium-Catalyzed Alkene Hydroboration in Supercritical Carbon Dioxide," *Chem. Commun.* **2000**, 347 (2000).

DeSimone, J., and W. Tumas, Eds., *Green Chemistry Approaches Using Liquid and Supercritical Carbon Dioxide*, in Green Chemistry Series (Oxford University Press, New York, in press).

Liu, F., et al., "Phase-Separable Catalysis Using Room-Temperature Ionic Liquids and Supercritical Carbon Dioxide" (submitted to *Chem. Commun.*).

Tumas, W., "Homogeneous and Biphasic Catalysis in Dense-Phase Carbon Dioxide," *Proceedings of the 5th International Symposium on Supercritical Fluids (ISSF)*, Atlanta, Georgia, 2000).

Tumas, W., et al., "Homogeneous, Heterogeneous, and Biphasic Catalysis in Dense-Phase Carbon Dioxide," in *Green Chemistry Approaches Using Liquid and Supercritical Carbon Dioxide*, J. DeSimone and W. Tumas, Eds. (Oxford University Press, New York, in press).

Fig. 2. Turnover frequencies (h^{-1}) at 50% conversion for hydrogenation of styrene in biphasic H_2O /toluene, biphasic H_2O/CO_2 , and H_2O/CO_2 emulsions. Reaction conditions are as follows: 50/50 wt % H_2O/CO_2 , 80 mM styrene, 1 mol % $RhCl(tppds)_3$ as catalyst where *tppds* is tris(3,5-disulfonato-phenyl)phosphine, rhodium/ligand ratio is 1/6, T is 40°C, P_{H_2} is 300 psi, P_{total} is 4000 psi.

Fig. 3. (Top) Synthetic scheme for porous or expandable polymers that incorporate transition metal catalysts (upper equation); (lower left) solid-state ³¹P nuclear magnetic resonance spectrum of polymer-supported catalyst showing bound and free phosphine; and (lower right) micrograph of polymer/catalyst beads.

Supported Technetium Chemistry

99014

Carol J. Burns

Our goal is to exploit solid-phase synthesis techniques in order to investigate the coordination chemistry of technetium when the element is appended to polymeric supports. The application of solid-phase synthesis or related heterogenization techniques could change our overall approach to experimental work involving radionuclides in providing the means to control contamination associated with mobile (volatile) radionuclides. These studies are undertaken principally to evaluate the differences and similarities in the homogeneous and supported chemistry of technetium, and determine whether the reactivity of polymer-bound systems can be used fairly to predict solution behavior. The ultimate goal is to provide the knowledge base for pursuing high-throughput synthesis approaches to problem solving in diverse applications such as waste treatment and high-yield substrate labeling in nuclear medicine applications.

This year we examined (a) the binding of higher-valent technetium species (RTcO_3) as analogs for the removal of pertechnetate from waste streams and (b) the subsequent stability of the polymer-bound species. We have demonstrated the efficient capture of high-valent rhenium and technetium oxo complexes on amine- and isocyanate-functionalized polymers and confirmed the basic mechanism of attachment of the metal through covalent bonding (Fig. 1). Results have shown that solid-supported chemistry can differ significantly from its solution counterpart. In contrast to known homogeneous chemistry of rhenium, covalent binding of certain rhenium(VII) oxo complexes at polymer supports by means of the generation of metal-imido linkages in condensation reactions results in reduction of the metal (as determined by x-ray absorption spectroscopy). Reactivity studies have shown that this covalent binding is relatively robust, however. For example, treatment of Re(V) -containing polymers with strong oxidants such as hydrogen peroxide leads to oxidation of the metal center, but without leaching from the support.

Most recently, work has focused on the functionalization of soluble polymers to create comparable metal binding sites. Studying soluble polymers will enable us to use a broader range of characterization tools to study the fate of the metal.

Fig. 1. Extended x-ray absorption fine structure on polymer-bound technetium species. Both experimental data and calculated fit are shown. The data are best fit by a model in which the metal is bound by three oxo/imido groups and one siloxide oxygen, consistent with the expected product of a condensation reaction between $(\text{Me}_3\text{SiO})\text{TcO}_3$ and a pendant isocyanate ($-\text{NCO}$) group.

Nonadiabatic Processes in Chemical Reactions

99015

Brian K. Kendrick

In the past, most theoretical methods for treating chemical reactions were based on the simplifying adiabatic approximation that ignores nonadiabatic processes. In recent years, it has become clear that the discrepancies between experiments and theoretical treatments of reactions as simple as $\text{H} + \text{D}_2 \rightarrow \text{HD} + \text{D}$ may be the result of theoretical treatments that ignore these nonadiabatic processes. Treating these processes properly from a theoretical standpoint has been very difficult and computationally challenging, but we have developed some novel methods that may allow for an accurate treatment of these processes for the first time. We expect to develop new techniques that will help to resolve the current discrepancy that exists between recent experimental results and previous theoretical treatments for the above reaction at high energies. This work contributes to the fundamental understanding of chemistry and to the Laboratory's core competency in theory, modeling, and high-performance computing.

This year we published our results for the $\text{H} + \text{D}_2 \rightarrow \text{HD} + \text{D}$ reaction for all total angular momentum $J = 0-5$ and extended these calculations to include all $J = 0-29$. This number of J values is sufficient to obtain adequate convergence, and our results are in very good agreement with recent high-resolution experiments. This agreement confirms our preliminary findings from last year: the effects of low-energy, nonadiabatic processes cancel out when the contributions from even and odd values of J are added together. We also made an unexpected discovery: resonances (bumps) appeared in both the integral and differential cross sections. Figure 1 shows an example of this resonance structure. Bumps similar to this one were recently observed experimentally. This work has been cited as an "important advance in the field of chemical reaction dynamics" in the June 2, 2000, issue of *Science*. We also completed the development of a more accurate potential energy surface for $\text{Na}_3(\text{X})$. This new surface will allow us to compute more accurate rovibrational energy levels and accurately assess the nonadiabatic effects in molecular spectra.

Fig. 1. Integral cross section for the $\text{H} + \text{D}_2(v = 1, j = 0) \rightarrow \text{HD}(v' = 1, j' = 0) + \text{D}$ reaction as a function of collision energy. A large resonance (bump) is clearly visible at about 0.41 eV. The different curves correspond to different J_{max} (the number of total angular momentum J included). The top and bottom curves correspond to $J_{\text{max}} = 29$ and $J_{\text{max}} = 0$, respectively.

Publications

Kendrick, B.K., "Geometric Phase Effects in the $\text{H} + \text{D}_2 \rightarrow \text{HD} + \text{D}$ Reaction," *The J. of Chem. Phys.* **112**, 5679 (2000).

Kendrick, B.K., "How to Observe Resonance Structure in the Integral Cross Sections of the $\text{H} + \text{D}_2 \rightarrow \text{HD} + \text{D}$ Reaction," submitted to the *J. of Chem. Phys.*

Kendrick, B.K., et al., "Observation of Predicted Resonance Structure in the $\text{H} + \text{D}_2 \rightarrow \text{HD}(v' = 0, j' = 7) + \text{D}$ Reaction at a Collision Energy of 0.49 eV," *Phys. Rev. Lett.* **84**, 4325 (2000).

Kendrick, B.K., et al., "On the Nonexistence of Strictly Diabatic Molecular Electronic Bases," *Chem. Phys. Lett.* **330**, 629 (2000).

Description of Complex Adsorption from a Simple Equation of State

99016

Bryan F. Henson

We are developing new equations of state to describe the adsorption and interfacial thermodynamics of solid atmospheric aerosols, such as dust or ice particulate. We have developed a nonlinear light-scattering technique to measure the surface thermodynamic state of an aerosol under the unique, high-pressure conditions necessary for the stability of these systems and with this technique have begun to determine the equations of state for a number of important environmental systems. Significant emphasis will be placed on calculating the stability and volume of surface liquid phases, a poorly understood phenomena that is very important in understanding how aerosols modify atmospheric chemical composition. The theoretical and experimental work will illuminate the important role of aerosols on global change, atmospheric chemistry (ozone depletion), and the transport of pollutants and chemical and biological warfare agents.

This year we have explored the ramifications of our new theory of the interfacial liquid phase of H_2O and worked toward its acceptance and publication. The central impact of the theory is the implication that the free energy of the interfacial liquid phase is equivalent to that of normal water and that the term quasi liquid is a misnomer. The fact that the interfacial liquids are liquids indistinguishable from their bulk counterparts means that subsequent theoretical work on a theory of true multicomponent interfacial solutions may build upon classic, bulk thermodynamics. We have begun calculations on the volume of liquid represented by such interfacial liquids under atmospheric conditions. Others have shown that a significant amount of trace gas is taken up in the Arctic snow pack. We calculate that the amount of water expected in snow as interfacial liquid is considerable and is a possible reservoir for such uptake.

Plutonium-Mediated Catalysis

2000012

Benjamin Warner

Plutonium degrades the organic compounds that it contacts. These organic compounds include processing chemicals, biological molecules, and combustible wastes. This degradation has often been attributed to radiolysis. However, radiation is not kinetically competent to induce all of the changes observed. From the literature and some preliminary evidence, we believe that plutonium may chemically and catalytically induce these degradation reactions. In this project, we aim to determine which reactions occur, how to stop them when they are unwanted, and how to take advantage of them when appropriate. The value of this project is that it supports Los Alamos and DOE missions in plutonium processing and waste stabilization. The knowledge gained will allow more-stable processes to be developed and will minimize mixed TRU waste.

During this year, we determined that simple plutonium alkoxide compounds are excellent Lewis acid catalysts. We used the Meerwein (MPV) reduction reaction as a test case. Plutonium(III) exceeds the lanthanides in its catalytic ability. Plutonium(IV) does not, however, catalyze the MPV reaction. Neither neptunium(III) nor uranium(III) catalyze the MPV reaction either, and their failure mechanisms demonstrate their oxidation potentials. This test reaction therefore validates the concept of this project that the product analysis of simple reactions can provide physical information. The MPV reaction is also known to degrade cellulosic materials, so it is directly relevant to plutonium-bearing wastes. This work has resulted in one accepted manuscript, and an invitation to write a review paper.

Also during this year, we performed reactions with lanthanide surrogates to test the catalytic efficiency of insoluble metal halide salts. Several lanthanide chlorides were very active catalysts, and this work will be extended to the actinides. This part of the project resulted in two published papers.

Publications

Fang, X.-G., et al., "Ytterbium Trichloride-Catalyzed Diels-Alder Reactions of Unactivated Dienes," *Synth. Commun.* **30**, 2669 (2000).

Fang, X.-G., et al., "Ytterbium Trichloride-Catalyzed Allylation of Aldehydes with Allyltrimethylsilane," *Tetrahedron Lett.* **41**, 447 (2000).

Warner, B.P., et al., "Plutonium(III)-Catalyzed Meerwein-Ponndorf-Verley Reactions," (to be published in *Inorg. Chim. Acta*).

Understanding and Controlling Micelles in Supercritical Carbon Dioxide

2000013

T. Mark McCleskey

This project is concerned with the understanding and control of water in CO₂ microemulsions. These nano-sized droplets of water dispersed in CO₂ have potential as an environmentally benign medium for cleaning heterogeneous waste contaminated with radioactive or hazardous metals.

The microemulsions offer two significant advantages over traditional methods that involve washing the waste with bulk water. One advantage is that small amounts of water can be used for large volumes of waste that have small amounts of metal distributed throughout the waste. When bulk water is used, the amount of water is generally proportional to the volume of material to be remediated, but with the microemulsion the amount of water is only proportional to the amount of radioactive or hazardous metal. This means that grams of waste can be cleaned with microliters of water. The second advantage is that the nanodroplets of water can penetrate spaces in porous materials, such as wood, that bulk water cannot access.

We are investigating the stability of these microemulsions, their ability to bind metals, and the nature of the water within the microemulsion. We have examined the water pool, sequestered within three different surfactant or surfactant-cosurfactant assemblies, and investigated how the pool affects luminescence probes differently, depending upon surfactant head-group charge and nanodroplet size (i.e., w_0 , molar ratio of water to surfactant). We have investigated the influence of intramolecular water on the photophysical characteristics of two probes ([Ru(bpy)₃]²⁺ and 1-aminonaphthalene, AN). The steady-state and fluorescence lifetime results of AN suggest that while a continuum of different types of water exists within the micelle, the water pool does not resemble bulk water in terms of polarity (dielectric constant). The results from spectroscopic measurements of [Ru(bpy)₃]²⁺ strongly suggest that it is localized at the water/surfactant interface when the surfactant contains a negatively charged head group. In addition, we have demonstrated that these micelles can extract copper and europium from a variety of substrates, including wood and filter paper.

Synthesis and Characterization of High-Performance Propellants

2000014

Michael A. Hiskey

High-nitrogen energetic materials may be the key to meeting the advanced performance objectives of next-generation solid propellants. Those most familiar with this technology recognize that current solid-propulsion systems have reached their performance limits. The high-nitrogen materials form a unique class of energetic materials deriving most of their energy from their high positive heats of formation rather than from oxidation of the carbon backbone, as with traditional energetic materials. Compounds of high nitrogen content typically have high densities, and the reduced amounts of hydrogen and carbon atoms in the molecular framework allow a desirable oxygen balance to be achieved more easily. Oxygen balance is a measure of the oxygen/fuel ratio in a chemical explosive (e.g., TNT) or a mixture (e.g., ammonium nitrate and fuel oil). High-nitrogen compounds also burn more quickly and cleanly and are therefore especially suitable as low-signature propellant ingredients.

This year, we successfully prepared two high-nitrogen energetic materials in sufficient quantities to allow small-scale motor firings. The first of these molecules, 3,6-bis(1*H*-1,2,3,4-tetrazol-5-ylamino)-1,2,4,5-tetrazine, or BTATz (Fig. 1), is 79 wt % nitrogen and has a measured heat of formation two orders of magnitude higher than those of traditional energetic materials. BTATz also has a very fast burn rate (8 cm/s at 1470 psi). Also, our burn-rate measurements showed that BTATz can depress the pressure exponent in certain propellant formulations. The pressure exponent describes the effect of pressure on increasing propellant burn rate. A low pressure exponent is necessary for rocket motor stability, particularly when the working motor pressure is pushed to higher limits.

A second high-nitrogen compound, 3,3'-azobis(6-amino-1,2,4,5-tetrazine), or DAAT (Fig. 2), has the highest recorded density (1.78 g/cm³) of any compound containing only carbon, hydrogen, and nitrogen atoms. We are currently working on oxidizing DAAT to improve the oxygen balance and increase the burn rate. Finally, we have constructed a small rocket motor and a thrust stand, which will allow us to characterize our high-nitrogen propellants and study the exhaust plumes.

Publications

Chavez, D.E., et al., "3,3'-Azobis(6-amino-1,2,4,5-tetrazine): A Novel High-Nitrogen Energetic Material," *Angew. Chem., Int. Ed. Engl.* **39**, 1791 (2000).

Fig. 1. The compound 3,6-bis(1*H*-1,2,3,4-tetrazol-5-ylamino)-1,2,4,5-tetrazine, or BTATz, is 79% nitrogen by weight.

Heat of Formation = +206 Kcal/mol

Fig. 2. The compound 3,3'-azobis(6-amino-1,2,4,5-tetrazine), or DAAT, is 76% nitrogen by weight.

Anomalous Isotope Effects in Ozone Formation

2000015

Russell T Pack

Researchers have known for 20 years that stratospheric ozone (O_3) shows large (40%), “mass-independent” enrichments of the heavy oxygen isotopes (oxygen-17 and oxygen-18) relative to the oxygen (O_2) present, which is composed mostly of oxygen-16 atoms. This effect has been intensively studied experimentally and traced to the ozone formation reaction, $O + O_2 + M \rightarrow O_3 + M$, where M is N_2 , O_2 , or Ar. The measured rates of this reaction show similarly anomalous variations (by 50%) for different isotopic combinations. Many theoretical explanations have been offered, but none agree with all the experiments even qualitatively, and the cause remains unexplained.

Our objective is to find a full explanation by doing detailed quantum theoretical calculations of the rates of the isotopic variants of this reaction. Our results would give a clear understanding of the mechanism responsible for such large isotope effects. Successful completion of the work will produce a new capability for accurately modeling the kinetics of complicated reactions with symmetry effects. In addition, it will allow the isotopic composition of ozone to be used as an atmospheric probe and will enhance Los Alamos programs in atmospheric chemistry and global climate change.

Although reduced funding slowed the project drastically, we made some useful progress. We examined the effect of symmetry on the equations of our quantum trajectory method and found that it has a significant effect that will cause the method to give different results for different symmetries. That result is encouraging and indicates that the method should explain the effects seen experimentally. In addition, we carried out vibrational rotational infinite order sudden (VRIOS) approximation calculations on several isotopic combinations of the model recombination reaction, $Ne + Ne + H \rightarrow Ne_2 + H$, and found that the resulting rates display anomalous isotope effects of the size and type needed to solve the ozone problem. We have begun to write up these model results for publication; they show clearly how the new pathways that arise when the symmetry is broken speed up the reaction.

Electron Transfer on the Vibrational Time Scale in Mixed Valence Systems

2000016

William Woodruff

The basic processes at the heart of thermally activated chemical reactivity involve the excitation of molecular vibrations. The question of how excitation occurs in a complex condensed-phase environment is the key to understanding chemical reactivity, which could greatly impact the synthesis of novel substances or the design of catalysts.

Until now it hasn't been possible to examine this issue directly, but our collaborators at the University of California (UC) at San Diego have recently identified a class of mixed-valence complexes in which electron transfer appears to occur on the vibrational time scale, similar to the way that chemical dynamics often occur on the nuclear-magnetic-resonance time scale. These complexes offer the opportunity to use time-resolved vibrational and vibronic spectroscopies to directly characterize the coupling of molecular vibrations to the reaction coordinate.

We expect that our studies will offer insight into the coupling of molecular vibrations to chemical reactivity, and thereby point to guiding principles for the rational control of reactivity via molecular vibrations, either by synthetic design, catalytic strategies, or spectroscopic manipulation of vibrational states.

Our target systems consist of two Ru_3O clusters bridged by an organic ligand such as pyrazine. In these complexes, electron transfer on the vibrational time scale is suggested by coalescence of infrared peaks as a result of varying intervalence transfer (IT) rates. This inference needs to be verified by direct observation of both IT rates and vibrational dynamics.

We characterized the vibrational and electronic spectroscopy of the unbridged Ru_3O clusters. With our UC collaborators, we constructed an electrochemical cell for preparing the dimeric mixed-valent complexes for the study of redox-state-dependent electron transfer reactions. We have expanded our collaborations through the participation of a researcher from the University of Calgary.

Advanced Membrane Architectures for Separation of Actinide and Toxic Metal Ions

2000065

Nancy N. Sauer

The requirements of stockpile stewardship necessitate the development of advanced, low-cost, reprocessing techniques that have an absolute minimum impact on the environment. New membranes that selectively transport actinides could greatly simplify reprocessing waste streams. To address this need, we have developed versatile membrane systems based on inorganic supports with well-defined pore structures. Modifying the membrane surface with hydrophobic layers or selective receptors allows us to build structures or chemical gates that enable separation of a wide range of species. The resulting thin membrane layer allows for high transport rates, whereas the selective receptors allow for transport of specific target ions. The goal of this work is to develop selective, stable membrane systems for the facilitated transport of molecules and metals such as uranium.

Our approach relies on commercially available alumina membranes coated with a thin layer of gold to control the thickness of the active membrane layer. Treating the gold-coated membranes with thiols gives self-assembled monolayers with the target high stability and chemical selectivity. We characterized the resultant membranes using a wide range of spectroscopic techniques including grazing-angle reflectance absorbance and fluorescence spectroscopies.

This year we developed techniques for the preparation of stable membrane systems and tested membrane transport properties using simple molecules such as phenol. We prepared membranes with simple alkyl thiols and checked them for stability and the ability to transport phenol. We adjusted solution pH in the receive side of the transport cell to facilitate phenol transport. We have demonstrated quantitative transport of several phenolic compounds through our membranes. The membrane techniques optimized with these systems enabled the development of stable membrane systems for the separation of uranium and lanthanides. For separation of uranium, we synthesized and chemically bound thiols modified with various phosphorous oxyacids, which have been used extensively as extractants for actinides, to the membrane surface. After

evaluating membrane stability, we examined several systems for uranium transport. Using the fixed-site carrier $\text{HS}(\text{CH}_2)_{11}\text{P}(\text{O})(\text{OCH}_2\text{CH}_3)_2$ attached to the gold coated surface, we obtained membranes with rapid, quantitative, and selective transfer of uranium.

Redox Chemistry of Os(VI)-Nitrido Complexes

2000068

David E. Morris

A remarkably diverse redox chemistry has been uncovered by researchers at Los Alamos and the University of North Carolina for osmium(VI)-nitrido complexes, a class of transition-metal complexes with strong chemical bonding between the metal and nitrogen atoms. Understanding how the chemistry works will impact research in modeling advanced catalytic schemes for “green” chemistry, in modeling protein-based systems for small molecule activation for bioscience and biotechnology, and in developing environmental remediation technologies for the degradation and destruction of organic contaminants. Our project also will foster interdivisional collaboration and rejuvenate Los Alamos research capabilities in transition-metal coordination chemistry and photophysics.

These new nitrogen-based oxidants — $[\text{OsVI}(\text{Cl})_2(\text{N})(\text{L}_3)]_+$, where $\text{L}_3 = 2,2',2''\text{-terpyridine (tpy)}$, $\text{tris-(1-pyrazolyl)methane (tpm)}$, and $\text{tris-(1-pyrazolyl)borate (Tp)}$ — are of significant interest for their potential use in effecting catalytic redox transformations in both organic and inorganic substrates. These complexes have unique chemical and spectral properties that can be exploited to study an array of chemical reactions. It appears that, in comparison with the corresponding oxo complexes, they exhibit selectivity and efficiency in such areas as atom-transfer reactions and synthesis of novel heteroatom organic compounds.

Discovery of these complexes also provides a new means to probe important reactions such as proton-coupled electron transfer and nitrido-amine interconversion related to the terminal stage in the biological reduction of NO_2 to N_2 to NH_3 . We have expanded this redox chemistry by synthesizing and characterizing the new nitrogen-based osmium complexes that incorporate hydrazido, sulfilimido, and phosphoraniminato ligands and by investigating electron-transfer reactions of these complexes.

This year we studied the redox chemistry of osmium-phosphoraniminato containing tpm and Tp ligands. These complexes, which are accessed from the corresponding electron-rich osmium(VI)-nitrido complexes, exhibit redox reactivity toward atom and electron transfers. For example, the phosphoraniminato ligand from the osmium(V) center is easily transferred to different tertiary phosphine com-

pounds to form a series of asymmetrical bis(phosphoranylidene) PF_6 compounds. This atom transfer reaction is being extended to sulfur and nitrogen compounds.

We also studied the proton-coupled electron transfer reaction in the protonated osmium(IV)-sulfilimido. We observed a large kinetic isotope effect (31.1) and are investigating this mechanism. Upon oxygen atom transfer, osmium(IV)-sulfoximido chemistry is established. Most recently, we observed a reaction between a cyanide compound and osmium(VI)-nitrido. Our preliminary results show a promising redox chemistry for this osmium(IV)-cyanamido complex.

Publications

Huynh, M.H.V., and T.J. Meyer, “Preparation of Heteroatom Arrays by Stepwise Atom/Group Transfer in *cis*- and *trans*- $[\text{Os}^{\text{IV}}(\text{tpy})(\text{Cl})_2(\text{N})]^{+}$ ” (submitted to *J. Am. Chem. Soc.*).

Huynh, M.H.V., et al., “Formation and O-atom Reactivity of the Os(IV)-Sulfilimido and Os(IV)-Sulfoximido Complexes, *cis*-/ *trans*- $[\text{Os}^{\text{IV}}(\text{tpy})(\text{Cl})_2(\text{NSC}_6\text{H}_3\text{Me}_2)]$ and *cis*-/ *trans*- $[\text{Os}^{\text{IV}}(\text{tpy})(\text{Cl})_2(\text{NS}(\text{O})\text{C}_6\text{H}_3\text{Me}_2)]$ ” (to be published in *J. Am. Chem. Soc.*).

Huynh, M.H.V., et al., “Formation and Reactivity of Os(IV) Cyanoimido Complex, $\text{NEt}_4[\text{Os}^{\text{IV}}(\text{bpy})(\text{Cl})_3(\text{NCN})]$ ” (submitted to *J. Am. Chem. Soc.*).

Huynh, M.H.V., et al., “Proton-Coupled Electron Transfer from Sulfur. An S-H/S-D Kinetic Isotope Effect of ≥ 31.1 ,” *Angew. Chem., Int. Ed.* **39** (22), 4101 (2000).

Huynh, M.H.V., et al., “Redox Chemistry of Morpholine-based Os(VI)-hydrazido Complexes: *trans*- $[\text{Os}^{\text{VI}}(\text{tpy})(\text{Cl})_2(\text{NN}(\text{CH}_2)_4\text{O})]^{2+}$ ” (submitted to *Inorg. Chem.*).

Computer Science and Software Engineering

Data Structures and Computer Arithmetic for Quantifying Uncertainty

2000017

James M. Hyman

In most numerical calculations, computational uncertainties are unavoidable. Truncation errors are introduced when a computable discrete model replaces a mathematical continuous one. Round-off errors, caused by the finite precision of the computer, are generated during the computation. Some of the most serious uncertainties are the propagation and creation of uncertainties in the initial conditions, the data, and the constants in a mathematical model describing a physical process. These inherent uncertainties cannot be made arbitrarily small by performing additional computation, using higher-order formulas, or carrying more significant digits in the arithmetic. We propose to develop a new interval arithmetic, which we call significance arithmetic, that can account for the creation and propagation of uncertainties in a computer program due to uncertainties in the data.

In this first year, we developed a new arithmetic for computer simulations that uses a probability distribution variable (PDV) as the basic data type. We have verified the effectiveness of the PDV arithmetic rules by extending FORTRAN to account for the creation and propagation of uncertainties in a computer program due to uncertainties in the data. To compute reasonable and accurate bounds on these uncertainties, many of the functional dependencies developing between the variables during execution are monitored automatically and used by the PDV arithmetic algorithms. We found that the final uncertainty bounds are much smaller than they would have been had the dependencies been ignored. These dependencies are also a measure of the sensitivity of the output of a program as a function of the uncertainty in the data.

Extremal Optimization

2000018

Madhav Marathe

Computer scientists have observed that the most difficult of computational problems lie near phase transitions—points that divide parameter space into regimes of distinct behavior. Some of the most widely used heuristic tools for such problems, inspired by equilibrium statistical mechanics, fail near these phase transitions (Fig. 1). Curiously, however, we have found that heuristic algorithms inspired by nonequilibrium phenomena do not suffer from these difficulties. We are therefore developing a nonequilibrium method, called extremal optimization, which is expected to lead to the next generation of general-purpose optimization algorithms (Figs. 2 and 3). Our goal is to analyze nonequilibrium approaches: to understand the behavior of such methods near phase transitions and the reason they do not necessarily suffer from the same complexity issues as do exact algorithms and equilibrium-based heuristics. Ultimately, we expect to gain a deeper and more applied understanding of algorithmic complexity, by gaining new insights into the role that phase transitions play in computational problems. The resulting opportunity to develop

revolutionary computing tools for combinatorial problems—resource allocation is a prime example—directly addresses the Laboratory's Strategic Plan and DOE's emphasis on high-performance computing.

The first and the more fundamental aspect of this project involves the development of the theory of extremal optimization. Over the past year, we have conducted a numerical study of the behavior of order parameters in computationally hard problems, in the region around phase transitions. In addition, we have conducted a theoretical study of phase transitions in graph-based problems and explored algorithmic local-search capabilities in the simulational context of sequential dynamical systems. These investigations have led to further insights as to the specific link between phase transitions and algorithmic performance. They have also suggested appropriate means to refine present notions of computational complexity, indicating where average-case performance is a more relevant measure than worst-case performance.

The second major part of the project is the elaboration of a test bed documenting the performance of the extremal optimization algorithm over different computationally hard problems. We have applied the algorithm to several new problems, including satisfiability, graph coloring, and spin glasses. In all cases, we have confirmed that our results are strong exactly where predicted, that is, around phase transitions.

Fig. 1. In graph bipartitioning, we must split the points into two sets of equal size (dark and light points here), with a minimum of lines connecting points from opposite sets (white lines). This arrangement has many applications in computational resource allocation. The instance shown is near the phase transition, where the problem is hardest to solve.

Publications

Boettcher, S., “Extremal Optimization: Heuristics via Co-Evolutionary Avalanches,” *Comput. Sci. Eng.* **2** (6), 75 (2000).

Boettcher, S., and A.G. Percus, “Combining Local Search with Co-Evolution in a Remarkably Simple Way,” in *Proceedings of the 2000 Congress on Evolutionary Computation* (IEEE, New York, 2000), p. 1578.

Boettcher, S., and A.G. Percus, “Extremal Optimization” (submitted to *Phys. Rev. Lett.*).

Boettcher, S., and A.G. Percus, “Nature’s Way of Optimizing,” *Artif. Intell.* **119**, 275 (2000).

Boettcher, S., et al., “Optimizing through Co-Evolutionary Avalanches,” *Lect. Notes Comput. Sci.* **1917**, 447 (2000).

Boettcher, S., et al., “Phase Transitions and Algorithmic Complexity” (submitted to *Nature*).

Istrate, G., “Algorithmic Implications of Phase Transitions,” 15th Annual Conference on Computational Complexity, Florence, Italy, July 4–7, 2000).

Istrate, G., “Dimension-Dependent Behavior in the Satisfiability of Random K-Horn Formulae” (submitted to *SIAM J. Comput.*).

Fig. 2. Run of equilibrium-based simulated annealing compared with nonequilibrium extremal optimization, on graph bipartitioning. The cut size is the number of lines connecting points from opposite sets. Simulated annealing slowly converges; extremal optimization rapidly decreases and fluctuations continue, allowing it to keep searching for better solutions.

Fig. 3. Extremal optimization run on the Fig. 1 example. Shaded areas denote the cut sizes that were explored using logarithmic time bins. The best cut size found drops exponentially, then continues to drop more slowly. The correct minimum cut size is 2, found after approximately 100,000 update steps, which is less than the number of points (500) squared.

Machine Learning

2000019

Don Hush

The use of empirical observations to augment first-principle knowledge in the development of a scientific model is referred to as *learning*. The complexity of many learning problems of national importance extends far beyond the capabilities of current scientific methodology. Specifically, researchers are often unable to compute acceptable solutions and simultaneously assess their accuracy. Without doing so, proposed solutions may generate disastrous consequences.

In this project, we study a formal mathematical framework, probably approximately correct (PAC), that directly addresses these issues by facilitating the development of efficient computational solutions while simultaneously assessing their accuracy. In recent years, this framework has revolutionized the solution of classic problems in classification, prediction, and regression and has become the preferred scientific framework in which to attack these problems.

Several important application domains at the Laboratory, including computer security and discrete simulation-based decision-making for infrastructure analysis, require a resolution of learning issues. Our goal is to advance the understanding of the PAC framework through its application to classification and prediction problems at Los Alamos. We will accomplish this through studying methods such as bagging, boosting, and support vector machines (SVM).

This year, activities focused primarily on SVMs. We provided the first proof of Vapnik's result related to performance bound; this result provides the primary motivation for SVMs. Our proof has been accepted for publication. In addition, we studied learning algorithms for SVMs and provided the first proof of convergence for a general class of methods called *decomposition algorithms*. These are the most common approach for training SVMs. Our analysis revealed flaws in the common implementation of these algorithms. By correcting these flaws, we were able to prove convergence and to provide the first (polynomial) bound on the rate of convergence.

Finally, we applied 12 prediction methods to the computer network intrusion-detection problem, using data provided by the 1998 Intrusion Detection Evaluation Program of the Defense Advanced Research Projects Agency. This study suggests that SVMs and boosting are very effective in computer network intrusion detection.

Publications

Hush, D., and C. Scovel, "Extension of a Theorem of Boucheron, Lugosi, and Massart" (submitted to *Ann. Probab.*).

Hush, D., and C. Scovel, "On the VC Dimension of Bounded Margin Classifiers" (accepted in *Mach. Learn.*).

Hush, D., and C. Scovel, "Polynomial-Time Decomposition Algorithms for Support Vector Machines" (submitted to *Mach. Learn.*).

Fig. 2: Sequencing coverage “profile” on DNA clone—total height of columns represents number of times sequenced. Darker shadings represent shotgun sequencing and lighter shading represents walking. Reliability standards require that each region be sequenced at least three separate times (column height at least three). In this demonstration, we performed only half of the usual shotgun sequencing. Nevertheless, with efficient algorithms, very few regions remain to be walked.

Publications

Cai, H., et al., “Flow Cytometry-Based Minisequencing: A New Platform for High-Throughput Single-Nucleotide Polymorphism Scoring,” *Genomics* **66**, 135 (2000).

Czabarka, E., et al., “Algorithms for Optimizing Production DNA Sequencing,” in *Proceedings of the 11th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA ’00)*, (ACM-SIAM, New York, 2000), p. 399.

Erdos, P.L., et al., “A Finite-Word Poset” (accepted in *Elec. J. Combinatorics*).

A Computational Framework for Multiscale Shape Characterization and Recognition

2000021

Lakshman Prasad

The objective of this project is to develop a computational framework for multiscale characterization, analysis, and recognition of irregular polygonal shapes. The framework will enable the development of a comprehensive, connected body of mathematical methods and algorithms based on the topological, metrical, and morphological properties of shapes. The framework will develop a geometric filtering scheme for extracting semantically salient shape features. This effort creates a paradigm for solving shape-related problems in pattern recognition, computer vision, and image understanding, in a conceptually cohesive and algorithmically amenable manner.

The project develops an advanced image analysis capability at Los Alamos for solving a wide range of problems in automated facility surveillance, nuclear materials monitoring, treaty verification, industrial safety, robotics, and remote sensing. The project will provide the scientific underpinnings that will enable us to collaborate in building smart surveillance cameras, with a direct practical impact on the Laboratory's capabilities in domestic and international safeguards and security.

We formulated an invertible transform called the chordal axis transform (CAT), for polygonal shapes, which yields a feature-based representation of a shape from its contour-based representation. This capability enables the efficient filtering, manipulation, and understanding of shapes in terms of their features.

To concisely represent and understand complex shapes in terms of their salient features, we developed an efficient geometric pruning technique that operates on the CAT of a shape to filter noisy and insignificant shape features. This technique facilitates the multiscale analysis of shapes in terms of the morphological significance of their features.

To capture the semantics of shapes for purposes of recognition and understanding, we developed a feature-based algebraic language for syntactically expressing shapes as strings in this language. Each element (feature) of a string (shape) has a metric vector that captures the physical characteristics of that feature (Fig. 1). This language of shapes establishes a multiscale syntactic shape-description

paradigm, wherein shape syntax may be *telescoped* to yield a progressive coarse-to-fine characterization, based on feature metrics, for hierarchical shape comparison and matching. This paradigm paves the way for the development of complex shape databases and recognition algorithms to automate object shape understanding in images.

Publications

Prasad, L., and R.L. Rao, "A Geometric Transform for Shape Feature Extraction," *Proc. SPIE, Vision Geom. IX* **4117**, 222 (2000).

Prasad, L., and R.L. Rao, "Multiscale Discretization of Shape Contours," *Proc. SPIE, Vision Geom. IX* **4117**, 202 (2000).

Prasad, L., et al., "Feature-Based Syntactic and Metric Shape Recognition," *Proc. SPIE, Vision Geom. IX* **4117**, 234 (2000).

Schlei, B.R., et al., "Geometric Morphology of Granular Materials," *Proc. SPIE, Vision Geom. IX* **4117**, 196 (2000).

The Grammar G:

$G = (\{ S, L, H \}, \{ l_o, h_o, l, h, (,) \}, S, R)$

The Production Rule Set R:

$S \rightarrow l_o$	Sting & Loop
$S \rightarrow h_o$	Generators
$L \rightarrow l$	Terminators
$H \rightarrow h$	
$S \rightarrow LLL$	Shape Initiators
$S \rightarrow LH$	
$S \rightarrow HH$	
$L \rightarrow LL$	Stem, Limb & Handle
$L \rightarrow (L)$	Generators
$L \rightarrow (H)$	
$H \rightarrow HH$	
$H \rightarrow HLH$	

Human shape

$\Pi((\Pi)l)$

Feature	a	l	w
i	202.312	20.524	9.857
i	286.204	41.111	6.962
(	49.714	4.590	21.664
(	165.397	20.480	16.152
i	366.757	50.986	7.193
i	333.293	45.503	7.325
)	165.397	20.480	16.152
i	274.325	39.921	6.872
)	49.714	4.590	21.664

a = Area of the feature primitive

l = Length of feature primitive

w = Area of the feature primitive

Fig. 1. Linguistic representation of a human shape and the corresponding metrical attributes of the shape's feature elements. The string $\Pi((\Pi)l)$, which is a sequential listing of the feature elements encountered along the shape contour, represents the shape at a coarse resolution. The grammar provides rules for generating and recognizing shapes.

Adaptive Superscalar Microprocessor Architecture

2000022

Maya Gokhale

The purpose of this project is to develop an instruction-level, adaptive microprocessor architecture, with the goal of improving processor efficiency for scientific computing applications by 10% to 50%. Currently, microprocessor efficiency rates of less than 20% of peak are not uncommon, even for optimized, cache-friendly codes. A major source of this low efficiency is a mismatch between the number and type of function units required by the dynamic instruction stream and the number and type of available fixed function units. This mismatch prevents the microprocessor from executing the instructions at its maximum execution rate, because some functional units are always underused, whereas other units might be overloaded, causing a central-processing-unit stall. Improvement of processor efficiency will afford a corresponding speedup in execution of large, dynamic scientific codes such as those being developed in the Accelerated Strategic Computing Initiative (ASCI) stockpile stewardship program.

Our proposed solution is to design a new processor architecture with adaptive, reconfigurable functional units. In the first year, this architecture has been simulated in software. We built a detailed instruction-level simulator to study the effects of proposed adaptive features; sketched hardware mechanisms to implement the adaptive features; quantified hardware costs for proposed hardware extensions; and developed a benchmark suite to help us quantify the proposed architecture.

Our primary approach was to adapt the R10000 processor by making a floating-point (FP) unit capable of executing either FP or integer operations, thus adaptively varying the number of available integer and FP units based on the dynamic mix of integer and FP instructions in the instruction stream. Simulations showed a speedup of 8.3% to 14.3% on integer applications with a small increase in hardware and no impact on clock frequency. We further studied the impact of the above adaptation on future processor architectures, such as those that issue more instructions in parallel and processor-in-memory architectures. The greatest performance increase was found for processor-in-memory architectures. Using results from this year's simulations, we plan to construct adaptive portions of the processor in configurable hardware.

Publications

Lavenier, D., et al., "Integer/Floating Point Reconfigurable ALU" (6th Symposium on New Machine Architectures [SympA'6], Besancon, France, June 19–22, 2000).

High-Performance TCP over the Next-Generation Internet

2000023

Wu-chun Feng

With emerging high-bandwidth applications requiring gigabit-per-second speeds over the wide-area network (WAN), applications such as those in the DOE Accelerated Strategic Computing Initiative (ASCI) program, our project team has found that simply increasing the network-link speeds is not enough to achieve sustained gigabit-per-second performance between applications distributed over the WAN. Also, over the past decade, researchers have failed to understand the fundamental causes of self-similar (fractal) traffic—traffic that is a major reason for performance degradation in the Internet, and therefore, ASCI's distributed computational environment.

In fact, our network tests between Sandia National Laboratories/New Mexico and Los Alamos over a 155-Mbit/s WAN resulted in less than 2-Mbit/s delivered bandwidth per flow between applications, or two orders of magnitude slower than what is needed for ASCI applications over the WAN. This problem is due to the lack of understanding of how the Transmission Control Protocol, or TCP, (a ubiquitous protocol that supports applications requiring reliable network transport, e.g., the World Wide Web and remote scientific visualization) adversely affects network traffic and its associated performance between applications.

Because of this lack of understanding, the goal of this project is a more rigorous study, analysis, and characterization of network traffic to guide the development of a high-performance TCP to support today's and tomorrow's ASCI distributed- and distance-computing environments, as well as the next-generation Internet. We spent this year measuring and monitoring live network traffic for analysis and characterization purposes. As we expected, our preliminary analysis found that TCP was a primary source of self-similarity (and hence, performance degradation); this finding refutes the conclusions made by several seminal papers over the past five years.

Publications

Feng, W., and P. Tinnakornsriruphap, "The Adverse Impact of the TCP Congestion-Control Mechanism in Heterogeneous Computing Systems" (International Conference on Parallel Processing [ICPP 2000], Toronto, Canada, August 21–24, 2000).

Tinnakornsriruphap, P., et al., "On the Burstiness of the TCP Congestion-Control Mechanism in a Distributed Computing System" (20th IEEE International Conference on Distributed Computing Systems [ICDCS 2000], Taipei, Taiwan, April 10–13, 2000).

Computing with Networks of Spiking Neurons: Application to Real-Time Segmentation of Natural Scenes

2000070

Melanie Mitchell

The ultimate goal of this project was to develop neural network models of the mammalian retina and visual cortex. We used machine-learning techniques (beginning with genetic algorithms) to discover parameters and connection topologies that optimize the ability of these networks to segment visual scenes. The segmentation results from the synchronization of neural spike trains among cells stimulated by the same objects or visual features. During the three months of funding for this project we made the following progress.

We ported a general neural simulator from an interpreted language, the Matlab programming environment, to the compiled language, C. As a result, the algorithms that we investigate should execute an order of magnitude faster. In order to evolve network parameters using a genetic algorithm, we will need to execute a great many simulations, each comprising many individual neural networks across multiple generations. A reduced execution time is therefore critical to the feasibility of the project.

We wrote a genetic algorithm (GA) to evolve the parameters and connection topologies for neural networks. This required the careful design and implementation of a representation for these parameters and topologies so that they can be effectively evolved. We also developed a user interface for the genetic algorithm that allows users to easily specify particular selection and variation methods as well as numerical parameters, such as mutation and crossover probabilities. We are also working on an idea to create a convolution kernel for the neural system model, to help sharpen up the output response. Finally, we plan to couple the neural simulator to a gradient-based inverse engine. This coupled package could be used to crosscheck the GA system for simple test cases and to provide an alternative search strategy.

We also set up a concurrent versions system source code repository for the project so that members of the team can easily share code related to the project. We developed input/output routines to perform and analyze experiments—multiple runs of the genetic algorithm on neural networks—and to manage data collected from these experiments.

We developed an interface that allows the new neural network simulator to communicate with both the genetic algorithm and the fitness-computing routine. We are at present attempting to complete our first full-scale run, in which a genetic algorithm will evolve a network consisting of both spiking and nonspiking neurons in order to maximize a fitness function. Currently, the fitness function uses very simple criteria for evaluating any given network: specifically, we require only that the output be proportional to the input. We are developing a more complex fitness function for selecting networks that encode stimulus properties in the collective firing activity of neural ensembles.

We have developed routines to create input images to be segmented by the candidate neural networks. Images are bars of various shapes, sizes, orientations, and illuminations that are randomly or regularly spaced in an input field. We adapted these routines from a neural simulator that was written in FORTRAN and converted into C++. We are currently working on transferring additional features from the FORTRAN simulator, such as disks, annuli, gratings, checkerboards, and motion.

Publications

Kenyon, G.T., et al., “Segmentation and Intensity Coding via Synchronous Firing of Retinal Ganglion Cells: A Computer Model” (submitted to *Nature Neuroscience*).

Engineering Science

Use of Metallic Glasses in Ceramic-Metal Joining

98014

Rajendra Vaidya

The objective of our project was to demonstrate the feasibility of using metallic glasses in joining ceramics to metals. Residual stresses due to mismatch in thermal expansion properties in ceramic-metal joints can lead to failure at the interface or within the brittle ceramic. Low-temperature brazing techniques coupled with ductile interlayers can alleviate this problem. However, the use of precious-metal-based brazes and the incorporation of the interlayer add to the complexity and cost of the joining process.

To overcome these problems, we investigated the use of metallic glass brazes, which eliminate the need for separate interlayers in ceramic-metal joining. The use of metallic glass brazes could affect how problematic joints are formed, such as the joining of molybdenum disilicide to stainless steel. Such joints are required in a number of industries, including the glass-melting industry and the electronics industry.

Our main focus this year was on evaluating the residual stresses in successfully joined samples and making process recommendations. The joints were produced by high-temperature brazing with a cobalt-based metallic glass (METGLAS™ 2714A). Joining was completed in one of two ways: by feeding excess braze into the braze gap upon heating, or by constraining the molybdenum disilicide/stainless steel assembly with an alumina fixture during the heating cycle. Applying one of these techniques was necessary to ensure the production of a high-quality void-free joint.

We evaluated the residual stresses in the molybdenum disilicide/stainless steel 316-L joints using x-ray diffraction and instrumented indentation techniques. We used two different techniques because of their limitations. The indentation technique was unsuitable for the ceramic because it caused cracking, and the x-ray diffraction technique was unsuitable for the metal because of the effect of the surface treatment.

Our results were mixed. When compared with the joint formed with extra braze but no external constraint, the constrained joint had higher residual tensile stresses in the stainless steel but lower residual compressive stresses in the molybdenum disilicide.

This lack of residual-stress balance indicates that (1) the stress state in the braze is significantly different under the two conditions of joining and (2) the volume of the braze plays an important role in the development of the residual stresses. We also performed push-out tests on both joints. The joints created without an external constraint were stronger than those formed with a constraint.

Our results have important implications for selecting an appropriate joining process: adding extra braze or constraining the joint. An external constraint is certainly easier to apply in an industrial setting but results in higher residual tensile stresses, which may compromise the strength of the joint. On the other hand, use of excess braze is more difficult to implement in an industrial setting but results in a favorable residual-stress state. The choice of technique will depend on the application and the manufacturing equipment used.

Publications

Vaidya, R.U., et al., “Residual Stresses and Interface Strengths in MoSi₂/Stainless Steel 316-L Joints Produced by Metallic-Glass Brazing” (accepted in *Metall. Mater. Trans. A*).

Development and Engineering of the Ion-Cut and Low-Temperature Direct-Bonding Process

98015

Michael Nastasi

In this research, we propose to develop a new and innovative integrated circuit (IC) engineering technology that will allow for the development of effective and economical Silicon on Insulator (SOI) materials technology. The ability to produce SOI materials is critical to the production of (a) high-performance, radiation-hardened, ICs, (b) ICs that can operate at low power, and (c) three-dimensional IC chips 250 to 500 times denser than conventional chips. Our goals include studying the fundamental materials physics of the ion-stimulated cleaving process with traditional ion implantation and developing a plasma-source ion implantation chamber to implant hydrogen into single-crystal silicon. Our approach will benefit from recent technological breakthroughs in the areas of plasma processing, ion-beam-stimulated cleaving of single-crystal silicon, and plasma-stimulated low-temperature direct bonding of silicon to SiO_2 .

This past year, we continued our study of the basic mechanism of hydrogen-induced surface cleaving in silicon. In one critical experiment, a $\langle 100 \rangle$ oriented silicon wafer was implanted with 175-keV protons to a dose of $5 \times 10^{16} \text{ cm}^{-2}$. The implanted wafer was bonded to a silicon oxide capped $\langle 100 \rangle$ silicon wafer and then heated to an elevated temperature of 600°C to produce exfoliation. We analyzed the hydrogen-implanted sample in the as-implanted state as well as after the cleavage of the silicon wafer. We monitored the depth distribution of the implantation damage with Rutherford backscattering spectrometry (RBS) in channeling condition and cross-sectional transmission electron microscopy imaging. Elastic recoil detection analysis and secondary ion mass spectroscopy were performed to examine the hydrogen depth distribution. We measured the thickness of the exfoliated layer after cleavage with cross section scanning electron microscopy and RBS channeling. A comparison of the results from these methods showed conclusively that the cleavage of the silicon wafer takes place near the implantation damage peak rather than at the hydrogen concentration peak. This observation suggests that the stress and strain field in the proton-implantation-induced damage region of the silicon crystal is in part responsible for the hydrogen-induced cleavage of the silicon crystal. We can then hypothesize

that methods other than ion implantation providing defect engineering, strain production, and hydrogen introduction into the lattice will result in crystal slicing in silicon and possibly other materials.

Publications

Breese, M.B.H., et al., "Analysis of the Crystalline Quality of Exfoliated Surfaces in Hydrogen Implanted Silicon," *Appl. Phys. Lett.* **77**, 268 (2000).

Hoechbauer, T., et al., "Hydrogen Blister Depth in B+Hydrogen Co-implanted N-type Silicon," *Appl. Phys. Lett.* **75**, 3938 (1999).

Höchbauer, T., et al., "Hydrogen-implant induced silicon surface layer exfoliation" (accepted in *Phil. Mag.*).

Zheng, Y., et al., "Orientation Dependence of Blistering in H-Implanted Si" (accepted in *J. Appl. Phys.*).

Zheng, Y., et al., "Transfer of n-type GaSb onto GaAs substrate by Hydrogen Implantation and Wafer Bonding," *Journal of Electronic Materials* **29**, 916 (2000).

Pulse Shaping in Explosive-Pulsed-Power Systems

98016

Michael V. Fazio

In this project we have developed pulse-shaping hardware to allow compact explosive-power systems to properly drive loads such as high-power microwave tubes. Explosive-pulsed-power systems have milliohm source impedances with exponentially rising waveforms. High-power microwave tubes and other loads of interest require fast-rising, square-pulse outputs of several hundred kilovolts and impedances of a few ohms to a few hundred ohms. With pulse-shaping systems, explosive-pulsed power will have many more applications in both high-energy density physics and many Department of Defense programs.

During this project, we developed two types of pulse-shaping systems: a high-voltage air-core transformer and an explosively formed fuse. This year we finished designing and built a system to power a 1.3 GHz reltron, a type of high-power microwave tube. The system consists of an explosively driven “flat-plate” flux compression generator and a high-voltage transformer. It is designed to generate approximately 200 J of radio frequency energy at a 1.3 GHz frequency and could allow compact, high-power sources of microwaves to be deployed as microwave weapons.

We tested the completed explosive-pulsed-power system and verified that the explosive generator part of the circuit will perform as designed. Although we planned to test the system by using it to power the reltron high-power microwave tube, the reltron tube was not ready for testing as expected. We hope that although this particular project has ended, the final experiment can be conducted sometime in the near future. However, we completed the explosive-pulsed-power system, the goal of our efforts.

Acoustic-Network Refrigerators

98017

William Ward

The acoustic-network refrigerator shares the thermoacoustic refrigerator's simplicity, but it utilizes acoustic-network design to create a Stirling cycle heat pump, thereby boosting the inherent efficiency but eliminating the complexity of a displacer piston. The adaptation also allows the Stirling cycle, which is generally better suited to cryocoolers, to be efficient in more ubiquitous low-temperature-difference cooling. The working fluid is helium, which means that a CFC (chlorofluorocarbon)-free refrigerator can become competitive in a broad range of domestic, industrial, and military cooling uses where it can have the most significant impact on economics and energy utilization. These advanced methods for improving energy efficiency and utilization will lessen the impact of national defense activities on ecological systems when CFC-coolant systems, such as chillers on naval vessels, can be replaced with improved models.

The project was a combined experimental and theoretical effort to design a candidate refrigerator and use it to identify and mitigate sources of inefficiency. We built a flexible laboratory-scale refrigerator that is capable of several hundred watts of cooling at a modest temperature difference. A high-efficiency linear electric motor that drives a reciprocating piston powers the device.

Several effects limit the overall efficiency of the cycle. Mean flow across the regenerator (or Gedeon streaming) convects heat across the closely spaced cold and warm portions of the refrigerator, causing a substantial loss if not countered. In our current device, a pair of continuously adjustable miniature DC fans supplies the appropriate amount of suppression flow. We also found that we could reduce energy losses along the acoustic path if we used distributed instead of lumped impedance tuning elements in this application. During this final year, we found a way to counter the large heat loss that results from simple longitudinal conduction in the narrow regenerators appropriate to this system. By using alternating layers of metal and polymer screens, we can decrease this effect while avoiding any performance anomaly resulting from cross-sectional temperature nonuniformity.

The Los Alamos thermoacoustic design code, DeltaE, evolved significantly over the course of this effort. This year it incorporates new calculation models that are more suitable and accurate for this type of apparatus. Still, the computer models are a linear approximation and overpredict performance at high amplitudes. If the device efficiency nears these theoretical levels, we expect a substantial external interest in further development of the technology.

Use of Directed-Light Fabrication for Fabricating Functionally Graded Materials

99017

Partha Rangaswamy

Directed-Light Fabrication (DLF) is a one-step process in which we deposit metal powder to the focal zone of a laser beam in order to fabricate functionally placed or compositionally graded metal parts. In powder form, the metal part flows into the moving spot of an intense laser beam, producing a continuous molten pool that solidifies rapidly into dense metal after the beam passes. A key advantage of DLF is that the entire fabrication process can be represented in a computer model that incorporates material properties and component geometry. This model then drives the DLF equipment and controls the laser beam's motion to produce a part in a single step, allowing simplification of design and fabrication (see Fig. 1). This capability will reduce the cost of fabricating nuclear weapons parts by eliminating multiple processing steps and the need for joining multiple products.

This year we have enhanced the process versatility by integrating finite-element design analysis with DLF's solid model, motion path, and process parameter controls. As a result, a design engineer can now combine or change materials in specific areas of a part to improve localized material properties, such as wear or strain resistance. Last year we demonstrated the capability to use the DLF process to place materials and alter material chemical composition according to predesigned specifications for a metal part.

In direct-laser metal deposition technologies such as DLF, it is important to understand and control thermal behavior during fabrication. During the DLF process, large thermal gradients in the vicinity of the growth plane leave the completed component in a state of residual stress, as evidenced by the warping of some of our components upon their extraction from the base substrate. To characterize residual stresses, we used a holographic-hole-drilling technique to determine stresses in simple-shaped materials of stainless steel (SS316L), inconel (IN718) and tool steel (H13) (see Fig. 2). These samples and experimental data were provided by Sandia National Laboratories through the Laser Engineering Net Shaping (LENS)-DLF consortia. In addition to the holographic-hole-drilling technique, we will

Fig. 1. The motion path developed from a solid model defining both the part geometry and material placement boundaries controls four feeders that deliver metal powder to the focal zone of a laser beam. We formed compositional gradients by ramping two or more feeders, we formed sharp boundaries by changing from one feeder to the other, and we formed alloys and composites by simultaneously feeding two or more feeders.

perform neutron diffraction (ND) techniques (available at the Los Alamos Neutron Science Center and Chalk River Laboratories in Canada) to evaluate the residual stresses in these materials and on functionally graded and sharp interface deposits (see Fig. 3). We have elected to use ND because it can nondestructively measure strains within the bulk of the material.

Publications

Lewis, G.K., et al., "Fabrication of Functionally Graded Metal Deposits," (International Conference on Powder Metallurgy and Particulate Materials, Vancouver, Canada, June 20–24, 1999).

Fig. 2. A laser holographic-hole-drilling technique shows the residual stress distribution in three solid samples of SS316L, IN718, and H13 materials across the growth direction along the fabrication plan (the x-direction) and the through-layer condition (the z-direction). We used a weighted polynomial function to obtain the fit to the data.

Fig. 3. (a) We fabricated a sharp nickel-200/Monel K500 interface in a bar by stopping one feeder and starting a second one on command from the motion path program. The copper composition data and hardness data showed very little gradient present. (b) We fabricated a graded interface comprising nickel-200 and Monel K500 material by linearly ramping down the nickel-200 powder feed and linearly ramping up the Monel K500 powder feed.

Composite Films Made with Metallic Carbon Nanotubes

99018

Brian Fishbine

By suspending metallic carbon nanotubes in insulating matrix material, such as plastic, we have made new types of “artificial dielectric” composites. The nanotubes’ high aspect ratios (length/radius) and metallic conductivity enhance the dielectric properties of the matrix. Fig. 1 shows some nanotube “ropes,” produced by the laser-ablation process, that we have used to make artificial dielectrics. Our main goal is to make lightweight films—about 1 mm thick—that absorb radar, thereby reducing the radar cross sections of military aircraft, ships, ground vehicles, or other structures. In addition to absorbing electromagnetic radiation, these films also shield it. An important military application is to shield electronic equipment from the intense electromagnetic pulse produced by a nuclear burst. The films can also shield cell phones, laptop computers, and other devices from electromagnetic interference. Our secondary goal is to make composites for the high-energy-density capacitors used in detonators and other weapons systems requiring lightweight, compact, pulsed-power sources.

This year we have measured the complex dielectric constants of composites made with several types of carbon nanotubes at several concentrations. These measurements have allowed us to calculate the composites’ insertion and reflection losses. Insertion loss shows how well a film shields electromagnetic radiation; reflection loss shows how well the film absorbs radar. We find that when suspended in a 2-mm-thick film, carbon nanotubes made by the laser-ablation process can provide high reflection loss at radar frequencies (see Fig. 2).

Computer modeling has also helped us explore the potential of carbon nanotube composites for high-energy-density capacitors (see Fig. 3). To test our code predictions of enhanced dielectric constant, our university collaborators have provided small zeolite crystals with carbon nanotubes grown in the crystal pores. We have just begun measuring the low-frequency dielectric constants of hundreds of these crystals in a “powder” occupying about 0.1 ml.

Publications

Fishbine, B.H., et al., “Dielectric Composites Made with Carbon Nanotubes” (submitted to *IEEE Trans. Antennas Propag.*).

Fig. 1. A scanning electron micrograph of the nanotubes used to obtain the results shown in Fig. 2. These tubular structures consist of thousands of individual, single-wall carbon nanotubes tightly bound by van der Waals forces into nanotube “ropes.” Higher magnification reveals 100–200 single-wall carbon nanotubes in each rope cross section.

Fig. 2. The reflection loss of a nanotube composite film 2 mm thick backed by a perfect reflector, such as an aircraft wing. We have calculated these results from our measurements of the complex dielectric constants of five concentrations of nanotubes suspended in toluene. A film with a reflection loss of -20 dB will reduce the radar cross section of a flat metal sheet to 1% of its physical area.

Fig. 3. The calculated relative complex dielectric constant κ of zeolite crystals with carbon nanotubes grown in the crystal pores. When $\kappa''/\kappa' \leq 0.01$, the material can be used to make capacitors. These results assume the nanotubes are aligned with the axes of the zeolite pores, which is the case for our crystals.

Highly Constrained Bandwidth Combinational Algorithm for Transmission of Speech (HC-BATS)

99019

John Hogden

The goal of this project is to combine a Los Alamos-developed speech processing algorithm with state-of-the-art data compression algorithms to reduce the number of bits needed to transmit data, and in particular, speech data. This research contributes to the Laboratory's mission to support the intelligence community (which has a need for increasingly compressed speech). The new technique, MALCOM, also has potential applications in fields such as speech recognition, text analysis, and video analysis.

Our method requires estimating parameters of Gaussian probability density functions (PDFs). However, our first version of the software required all the PDFs to be circularly symmetric and required different PDFs to have identical covariance matrices. This implementation required 26% more bits than state-of-the-art approaches. When the PDFs were allowed to have different covariance matrices (but were still circularly symmetric), we still required 9% more bits than the most current approaches. Incorporating some standard bit-reduction algorithms allowed our implementation to use the same number of bits as the state-of-the-art approaches. We are still testing our most recent version of the software, but initial results on a simulated data set show a 15% reduction in bits compared to our previous results when the PDFs are not constrained to be circularly symmetric. These results suggest that the approach may eventually succeed at improving state-of-the-art speech transmission.

Hydrogen Storage in Intermetallic Alloys

99020

Dan J. Thoma

Methodologies for designing complex intermetallic alloys with hydrogen storage applications do not currently exist, and the commonly used trial-and-error approach hampers efforts to achieve lightweight materials with large hydrogen-to-metal atom ratios. Therefore, our project goal is to develop such a methodology that uses (1) geometric models to define hydrogen sites and (2) electronic structure calculations to determine the available electronic state occupancy for the Laves phase class of intermetallic phases.

The proposed research addresses the fundamental and unresolved question of which *a priori* methods should be used to predict the hydrogen storage capacity of an engineering product. Our strategy is to develop new models (whose simpler forms are known to have an influence on hydrogen storage capacity) that enable us to design chemical species (samples, materials, etc.) without conducting numerous experimental evaluations. This design strategy for hydrogen storage will have an impact on various aspects of nuclear weapons science and technology.

Our major progress this past year has been in the development of our model. We can now actually predict the enthalpy of hydride formation in intermetallics. In the 1970s, George Campbell predicted that a class of metallic compounds known as Laves phases follows systematic thermodynamic trends as a function of atom size ratios. With first-principles calculations, we can simulate this effect. Based upon the combination of geometric size rules with the electronic structure calculations, we postulated similar trends for hydride formation. The results in Fig. 1 are based upon our own measurements and literature data. The figure shows that the data points fall on the lines and that, therefore, our *a priori* model works. No other model exists for predicting these types of results, and the model has significant implications for battery, fuel cells, and other technologies that rely on hydrogen storage.

The essence of the model is quite simple conceptually. The cohesive forces that hold the atoms together dictate atom bond lengths. We can use the bond lengths to predict the site occupancy of hydrogen atoms (where the hydrogen atoms sit within the crystal lattice). To prove this theory, we have successfully demonstrated this concept for disordered alloys. Our models have the unique advantage of allowing us to normalize these trends for all classes of materials.

Publications

Teter, D.F., and D.J. Thoma, "The Prediction of the Hydriding Thermodynamics of Pd-Rh-Co Ternary Alloys," *Metall. and Mater. Trans. B*, **30B** 667 (2000).

Thoma, D.J., "Laves Phase Intermetallics" (accepted in *Encyclopedia of Materials*, January 2000).

Fig. 1. The heat of hydride formation for binary Laves phases follows a trend similar to that found by Campbell for the heat of formation of the binary Laves phase compounds.

Next-Generation High-Power Microwave Source

99021

Clifford Fortgang

We propose to design, build, and test, a 17-GHz, 100-MW class microwave-source. The mechanism is the same one that a free-electron laser uses but in a new regime with a reversed-axial guide magnetic field in addition to the usual wiggler magnetic field. Such a microwave device has two important and distinct applications: first, as a radio-frequency (RF) source for the future-generation electron-positron particle-beam accelerator; second, as a design for an RF weapon to attack vulnerable solid-state electronic packages. Our goal is to produce a working prototype microwave-source.

This year we have concentrated our efforts on experiments involving the electron gun. We completely characterized the thermal-mechanical properties of the cathode and its support. The cathode operates at a temperature of 1050°C, so thermal management is an important issue. Figure 1 shows a thermal image of the cathode with temperature variations of 25°. Uneven heating at the entry and exit of the heater filament leads causes the cool spot at the top of the cathode. This effect is larger than desired, and we are working with the cathode manufacturer to improve the thermal uniformity by redesigning the filament subassembly. In addition to thermal measurements, we began characterizing the cathode-beam current emission. Figure 2 shows a unique diagnostic that we designed and built to measure beam current emission as a function of space over the entire 215-cm²-area cathode. Because the cathode is so large compared to other cathodes of the same type, quality control is an issue. Our measurements indicate that in fact the cathode performs as expected. We've investigated two regimes of operation (the space-charge-limited regime and the temperature-limited regime), and the data is remarkably close to what is expected by theory and design. These results are good news because they mean that this electron gun will produce a high-quality electron beam.

Publications

Simmons, D.F., and C.M. Fortgang, "Using Multispectral Imaging to Measure Temperature Profiles and Emissivity of Large Thermionic Dispenser Cathodes" (to be submitted to *Rev. Sci. Instrum.*).

Fig. 1. Thermal image of 6.5-in. cathode showing thermal uniformity to $\sim 25^{\circ}\text{C}$.

Fig. 2. Multiple Faraday cup diagnostic used to measure cathode current emission uniformity.

Improvement of Wear Resistance in Quenched and Tempered Steels by Cryogenic Treatment

2000024

Yuntian T. Zhu

Cryogenic treatment has been found to increase the wear resistance of quenched and tempered steels by several times. However, the mechanism for this phenomenological improvement in wear resistance is unknown, hindering cryogenic treatment's development from art to science-based technology. The objective of this project is (1) to investigate the mechanisms of cryogenic treatment and (2) to study the effect of microstructure, toughness, strength, and hardness on wear resistance.

This project will contribute to the overall Laboratory mission and required capabilities, especially in materials science. Martensitic phase transformation, which we will study in this project, also occurs in plutonium and its surrogate materials. The scientific knowledge obtained in this study can provide useful information about the phase transformations in plutonium. In addition, it may also help the future development of long-lived tools for machining radioactive materials. By remaining in service longer, such tools will reduce radioactive waste.

In the first year of the project, we conducted in situ cryogenic transmission electron microscopy (TEM) on 4140 and M2 steels. We first examined the samples at room temperature, then cooled them in situ with liquid nitrogen for about three hours and reexamined them to look for carbon-atom clustering around the dislocations or any changes in dislocation density. In both steels, the dislocation density in the martensite phase is so high that we have not been able to detect small, subtle changes upon cooling.

A commercial laboratory has tested the wear resistance of cryogenically treated drills made of M1 steel and has found no significant difference between the wear resistance of cryogenically treated and untreated drills. Cryogenic treatment may work with some alloys but not with others, partly because the same parameters are used for the cryogenic treatment of all alloys.

Cryogenically treated steels are annealed after treatment, and this has been done at various temperatures. Cryogenic treatment could affect the microstructures of alloys during the subsequent annealing, changing the mechanical properties of the alloys. To learn about these changes, we are currently conducting TEM and x-ray analyses that will allow us to check the change of lattice parameter and the precipitation of new phases.

Engineering of Plastic Artificial Muscles

2000025

Hsing-Lin Wang

Our objective is to engineer the next generation of light-weight, solid-state conducting polymer artificial muscles (actuators) with great mechanical strength, fast response time and long life cycles. This technology may have wide application in such DOE mission areas as environmental remediation and enhanced surveillance and in national security applications for covert operations. Our project focuses on using novel light-weight materials (conducting polymers) to fabricate highly efficient actuators.

We measured the mechanical strength of porous membranes. Initially, our concern is that the Young's modulus, the number of merit for measuring the mechanical strength of these porous engineering articles, can translate into the maximum work force that this device can generate. Typically, we performed three tests on each membrane. The values reported here are the average of these three trials. Fig. 1 shows an example of such measurement. The mechanical strength (Young's modulus) of these membranes varies from 400 MPa (51 μ m) to 250 MPa (160 μ m), represented by the slopes of these stress-strain curves. Elongation of these membranes ranges from 2% to 5%. Their mechanical strength decreases as their thickness increases. This result is consistent with what we previously observed: that mechanical strength of fibers spun from highly concentrated polyaniline, emeraldine base solution decreases as the fiber diameter increases. The strength of these membranes is also greater than we expected (10 to 100 MPa). They are stronger than the natural muscle, which has a tensile strength of approximately 0.01 MPa, by several orders of magnitude.

In addition, we studied the effects of processing conditions on the mechanical properties of polyaniline fibers. On the basis of this study, we optimized the conditions for fabricating other polyaniline engineering articles with much greater strength. Then we used the enhanced membranes to study their feasibility as chemical actuators. We discovered that the overall thickness of these membranes has a dramatic impact on their response time (see Fig. 2). The greater the thickness, the more slowly they respond to the changes of chemical stimuli. Membrane made from 2-mil wet film bends 120 degrees in a minute. All the above discoveries pave the way for the future success of this project.

Publications

Wang, H.L., "Conducting Polymer Actuators Based on Asymmetric Membranes" (submitted to *Adv. Mater.*).

Wang, H.L., et al., "Effect of Processing Conditions on the Properties of High Molecular Weight Conductive Polyaniline Fiber," *J. Polym. Sci., Part B: Polym. Phys.* **38** (1), 194 (2000).

Fig. 1. Stress-strain curves for the polyaniline asymmetric membranes with various thicknesses.

Fig. 2. Response time of the chemical actuators based on asymmetric membranes with various thicknesses.

Adaptive Femtosecond Pulse Delivery

2000026

Antoinette J. Taylor

Ultrafast optics has had a significant impact on science and technology over the last three decades. The objective of this project is to develop an adaptive system for remote delivery of ultrafast pulses operating over a wide range of initial pulse parameters and environmental conditions. To achieve this goal, we will combine femtosecond (fs) laser sources, fs temporal and spatial pulse shaping, fiber-optic propagation, and feedback control based on evolutionary algorithms to optimize high-bandwidth, short-pulse propagation in optical fibers.

Demonstration of this method will represent a landmark advance in the field of guided pulse propagation and will furnish a solid basis for the extension of ultrafast adaptive pulse shaping to a wide class of techniques and applications. The development of an adaptive system for remote delivery of ultrafast pulses will provide the Laboratory with a tool of extreme practical utility, in areas such as remote sensing, diagnostics for the weapons program, and high-speed communications and computation.

We have demonstrated adaptive pulse delivery of a 200-fs optical pulse, propagating in the nonlinear regime, through a 10-m optical fiber. Our experimental approach is as follows: a computer-controlled spatial light modulator temporally shapes 200-fs pulses at a wavelength of 1.55 μm and then inputs them into an optical fiber. After propagation, the output pulse is sent to a second-harmonic crystal; light generated at the second harmonic in the crystal is used as a control parameter for the adaptive feedback loop, because a shorter pulse yields a larger second-harmonic signal. A computer algorithm modifies the controls for the spatial light modulator until a maximum value for the second-harmonic signal is found, which indicates that the output pulse width is minimized. The feedback loop uses a genetic algorithm for this optimization process.

For the input intensity used in this experiment, an unshaped pulse that propagates through the fiber broadens by 75% and is visibly distorted. With the feedback loop engaged, the output pulse broadens by only 5% and much of the nonlinear distortion is defeated, notably in the wings of the pulse. The peak intensity of the optimized output exceeds that of the unoptimized output pulse by a factor of 2. An analysis of the phase of the optimized shaped pulse reveals that cubic and quartic nonlinearities are the dominant pulse-distortion mechanisms, in agreement with simulations of the propagation performed using the nonlinear Schrödinger equation.

Publications

Kane, D.J., et al., "Convergence Test for Inversion of Frequency-Resolved Optical Gating Spectrograms," *Opt. Lett.* **25**, 1216 (2000).

Nicholson, J.W., et al., "Full-Field Characterization of Femtosecond Pulses by Spectrum and Cross-Correlation Measurements," *Opt. Lett.* **24**, 1774 (1999).

Omenetto, F.G., et al., "Adaptive Control of Nonlinear Femtosecond Pulse Propagation in Optical Fibers" (submitted to *Opt. Lett.*).

Omenetto, F.G., et al., "Femtosecond Pulse Propagation in Optical Fibers," in *Ultrafast Phenomena VII*, T. Elsaesser, et al., Eds. (Springer-Verlag, New York, in press).

Omenetto, F.G., et al., "Observation of Chirped Soliton Dynamics at $\lambda = 1.55 \mu\text{m}$ in a Single Mode Optical Fiber with Frequency-Resolved Optical Gating," *Opt. Lett.* **24**, 1392 (1999).

Omenetto, F.G., et al., "Second-Harmonic Generation Frequency-Resolved Optical Gating Analysis of Low-Intensity Shaped Femtosecond Pulses at 1.55 μm ," *Opt. Lett.* **24**, 1780 (1999).

Omenetto, F.G., et al., "Shaping, Propagation, and Characterization of Ultrafast Pulses in Optical Fibers," *Appl. Phys. B* **70**, S143 (2000).

Omenetto, F.G., et al., "Ultrafast Soliton Dynamics," *Opt. Photonics News* **10**, 47 (1999).

Siders, C.W., et al., "Multi-pulse Interferometric FROG," in *Frequency Resolved Optical Gating* (Springer-Verlag, New York, in press).

A New Method for Cooling High-Frequency Conductors

2000027

Curt Ammerman

The goal of this project is to develop a powerful method for cooling high-frequency, alternating current (AC) conductors. This method of cooling involves boiling a dielectric, Fluorinert refrigerant that is in contact with electrical conductors. We will examine litz wire conductors in this effort. This technology could improve the power density of transformer windings, electrical machine windings, and AC magnet coils by a factor of 10, or for a given volume, reduce losses by a factor of 10. Thus, the size and weight of power conversion equipment in vehicles could be decreased and the electrical efficiency of stationary power conversion devices could be increased. Repetitively pulsed, high-field research magnets could be made to reach higher field strengths with greater duty cycles and to consume less power. AC “rastering” and “kicker” magnets for particle-beam accelerators could be made more efficient, compact, and reliable through the elimination of separate water cooling systems.

During this year, we successfully completed the fundamental pool boiling experiments on all litz wire specimens. In order to perform these tests, we designed and constructed a pool boiling experimental facility. Next, we wrote and refined the data-acquisition and control software that was used to operate this facility. To ensure that the test apparatus would give meaningful results, we analyzed the experimental uncertainty in detail. In the experiments themselves, we measured boiling heat-transfer values for six different litz wire configurations. For each specimen, natural convection, nucleate boiling, and critical heat flux data were obtained. In addition, we took high-speed photographs of the boiling phenomena to aid in characterizing the heat-transfer performance of the litz wires. The fundamental boiling heat-transfer data from these tests are very promising and show that the braided nature of the litz wires provided an enhanced heat-transfer surface.

Effect of Solid-Solid Phase Transformations on Elastic Constitutive Relations

2000028

Todd O. Williams

The purpose of this project is to consider the influence of solid-solid phase transformations (SSPTs) that occur at the single-crystal level on the overall/effective behavior of polycrystalline metals. SSPTs occur in many metals (such as actinides, steels, and shape memory alloys) and result in changed crystalline structures (e.g., different crystal symmetries) from that of the parent phase. The resulting changes in the crystalline structures of the single crystals subsequently result in complex changes in the overall/bulk thermomechanical response of transforming polycrystalline materials.

SSPT processes proceed as a nontrivial function of the bulk temperature, bulk stress, and time. To correctly predict the response of structures composed of materials undergoing SSPTs requires having appropriate constitutive descriptions at the macroscopic level. We are developing these constitutive relations (obtained as an explicit function of the evolving microstructure) in our work.

During this year, the project team has developed a unique extended version of the two-dimensional (2-D) Ginzburg-Landau (GL) theory for modeling the evolution of the SSPTs in single crystals. Our GL theory now incorporates thermomechanical coupling and thermal dilatational effects. This extension was necessary in order to obtain complete constitutive relations for both the single crystal and for the polycrystal. We addressed a broad range of issues during the development of our 2-D GL theory, including methods for bridging multiple length scales, appropriate incorporation of combined transformation and thermomechanical effects, and numerical implementation.

First, we obtained initial estimates of the necessary material parameters for our GL model using existing experimental data and microscopic calculations such as molecular dynamics and electronic structure calculations. Next, we carried out preliminary comparisons of our proposed theory with existing theories. Currently, we are implementing our 2-D GL theory into a computer code for the analysis of single-crystal behavior as well as combining it with a homogenization theory for the analysis of polycrystalline metals. The resulting framework represents a multi-length-scale theory bridging the responses from the atomistic to the macroscopic length scales.

Publications

Lookman, T., et al., “Effect of Solid-Solid Phase Transformations on Elastic Constitutive Relations” (accepted in *J. Phys. IV*).

Study of the Secondary Flows in Thermoacoustic-Stirling Hybrid Heat Engines

2000056

Greg Swift

Thermoacoustic-Stirling hybrid heat engines and refrigerators, which are based primarily on oscillating flow, have recently shown great promise, with efficiencies approaching those of mature technologies such as the internal combustion engine. However, quantitative predictive knowledge about secondary fluid flow effects is lacking. Without such knowledge, these engines and refrigerators cannot reach their full potential, because the secondary flows convect heat, reducing the efficiency. In this project, we have begun an experimental and computational study of the secondary flows and power dissipation caused by oscillating viscous flow through asymmetrical orifices and other sudden expansions. This work will ultimately enable higher efficiencies in thermoacoustic systems, supporting Los Alamos activities in two ongoing CRADAs (cooperative research and development agreements), which are funded by the DOE Offices of Basic Energy Sciences and Fossil Energy, and helping build the foundation of an important new energy-conversion technology.

This year, we built a test facility in which flow visualization and measurements of secondary-flow velocity and associated small pressure effects can be performed, in a geometry and with flow conditions correctly scaled up from relevant thermoacoustic systems. The facility is complete, with the oscillating-flow source, the schlieren optics, and the hot-wire anemometer velocity sensors debugged and with the pressure sensors partially debugged. For our first experiment, we undertook a scaling study of high-speed oscillating flow through an asymmetrical orifice, with the outflow forming a jet while the return flow is more broadly distributed in space. Each oscillation of this flow launches a vortex ring, much like a smoke ring, that initially surrounds the outflowing jet and soon merges with it. Our measurements show that, far enough from the orifice, the jet formed by the oscillating flow mimics a steady-flow jet with the same time-averaged fluid momentum.

To complement the experiments, we also began computational studies, but with disappointing results. Today's versatile fluid-dynamics codes are not equal to the task of accurately predicting the behavior of turbulent oscillating compressible flow. We quickly abandoned the computational thrust.

Engineered Triple-Phase Boundary Gas Sensors

2000060

Fernando Garzon

The objective of this project is to explore novel approaches to optimizing the performance of solid-state electrochemical sensors. Gas sensing using mixed-potential devices has been widely investigated over the last twenty years. The literature describes mixed-potential sensors of various electrode materials and solid electrolytes that detect gases that react catalytically with oxygen. While many prototype devices have been fabricated, commercially available devices have not yet emerged. The prototype devices display many desirable characteristics in terms of size, cost and sensitivity, but many do not meet long-term response stability and reproducibility requirements.

Our recent research using electrochemical characterization methods and gas chromatography has clarified the fundamental response mechanisms of mixed-potential sensors for simple gases such as hydrogen and carbon monoxide. We have shown that the interplay between heterogeneous oxidation kinetics and oxygen electroreduction kinetics at the triple-phase interface controls the response behavior of mixed-potential sensors. We have developed new analytical models to describe the response behavior of these devices. These models predict that, by careful engineering of the triple-phase interfaces, we may develop new classes of sensors that will exceed the performance of past designs, that will reliably detect chemical warfare agents, and that will be valuable in monitoring and efficiently controlling combustion processes involving such equipment as internal combustion engines and utility boilers.

We have successfully fabricated electrochemical sensors with controlled triple-phase interfaces that offer greatly improved response characteristics than first-generation devices. A patent application has been submitted on the new sensor design.

We prepared the sensors with gold and platinum electrodes and yttria-stabilized-zirconia and gadolium-doped-ceria solid electrolytes. We also prepared platinum/gold electrode sensors on sapphire substrates using photolithographic methods. The sensor response times appear to be controlled by the diffusion rate of oxygen vacancies in the solid electrolyte. The sensors respond to ppm levels of CO in less than 5 seconds. The sensor output is stable and reproducible for long test periods. The device-to-device response reproducibility is also excellent. We have further refined electrokinetic models, specifically a mixed-potential model, for the response behavior of these devices.

Publications

Garzon, F.H., et al., "Mixed Potential Sensors: Theory, Experiments and Challenges," *Solid State Ionics* **136**, 663 (2000).

Mukundan, R., et. al., "A Mixed Potential Sensor Based on a $\text{Ce}_{0.8}\text{Gd}_{0.2}\text{O}_{1.9}$ Electrolyte and Platinum and Gold Electrodes," *Journal of the Electrochemical Society* **147**, 1583 (2000).

Geoscience, Space Science, and Astrophysics

Lightning in the Atmosphere and in the Solar Nebula

98018

Joseph E. Borovsky

Lightning is a phenomenon that is not well understood. On Earth, lightning causes forest fires and produces chemical changes in the atmosphere that may lead to global warming. In the solar nebula, lightning may be the catalyst for chemical and physical changes that have unknown effects. Our goal was to develop a model for lightning leaders in Earth's atmosphere and a methodology to scale this model to the conditions of the solar nebula to estimate the energy deposition into the gas. The model is based on the dynamics of charge flow on the lightning channel near the leader tip and uses recent theoretical results about the electrodynamic properties of lightning channels.

We uncovered a surprising dilemma: nonlinear lightning pulses were found either to propagate at the velocity of light or not to propagate. We attempted to resolve this dilemma by making a systematic variation of the parameters of lightning channels (initial radius and temperature), plus trying various schemes for radiative cooling of the lightning channel. Unfortunately, the model did not produce propagation velocities that match observations, i.e., long-distance propagation at a small fraction of the velocity of light.

We have concluded that our model, which appeared to be a promising description of the physics of the propagation of lightning, is lacking some element. There are several possible reasons for the disagreement. First, we may have overlooked a physical effect that plays a key role in heat transport out of the lightning channel; i.e., an anomalous heat conduction in air under high electric fields. Second, we may have overlooked a physical effect that alters the heat capacity of the channel; i.e., a spreading of the electrical current of the lightning outside of the channel. Third, we may have incorrectly derived the nonlinear terms of the equations describing the time development of the electromagnetic fields around the channel and charge movement along the channel; i.e., carried incorrect nonlinear terms in the mathematics.

High Pressure Crystal Chemistry of Hydrous Minerals

98019

Yusheng Zhao

Hydrogen has long been appreciated for its role in geological processes, but it has recently figured in new concepts of how the Earth works. We now believe that most of our planet's hydrogen may be locked up in high-pressure phases of hydrous silicate minerals within the Earth's mantle. This rocky interior (approximately 7/8 of Earth's volume) is conjectured to contain 1–2 orders of magnitude more water than the more obvious oceans (the “hydrosphere”) and atmosphere. Our goal is to use the capability of neutron scattering from hydrogen to study the crystal chemistry and stability of hydrogen-bearing minerals at high pressures and temperatures (P-T). At the most basic level this is a study of the hydrogen bond itself: varying pressure and temperature provide a means to study bond lengths and vibrational features (displacement vectors).

Next is the question of the crystallographic structure of hydrous minerals at extreme conditions. Which structures are stable, and what is the range of their abilities to retain hydrogen? We will perform the first direct probe of the crystal structure and thermal vibration of atoms for the hydrous minerals at simultaneous high P-T. Studying high P-T crystal chemistry of hydrous minerals will help to improve our understanding of the composition and dynamics of Earth's deep interior.

We have worked on the deuterated hydrous mineral phase-A $\text{Mg}_7^{IV}\text{Si}_2\text{O}_8(\text{OD})_6$ synthesized at high P-T conditions of $P=10\text{ GPa}$ and $T=1000^\circ\text{C}$, with the mixture of 3 parts of brucite MgOD (deuterated sample) and 2 parts of forsterite Mg_2SiO_4 (end-member olivine). The time-of-flight neutron diffraction data were collected at LANSCE/HIPD with high resolution (151° bank) and moderate resolution (90° bank). Shown in Fig. 1 are neutron diffraction patterns in observed, calculated, and difference forms. The crystal structure of the deuterated sample was refined using the Rietveld technique, and the atomic position and thermal vibrations were determined accordingly. With the wide range of d-spacing from $0.5\text{\AA}$ to $3.0\text{\AA}$, we can accurately determine the crystal structure.

We compared our refinement results with experimental results previously obtained by Kurt Lenerweber (Arizona State University) and John Parise (State University of New York at Stony Brook) and got very good agreement. Neutron diffraction is sensitive to the hydrogen (deuterium) positions that allow us to study the details of the crystal structure of hydrous minerals. The in situ high P-T neutron diffraction experiment will reveal the structure response to the P-T conditions and the details of the dehydration process.

Publications

Zhao, Y., “The New Development of High P-T Neutron Diffraction Techniques at LANSCE” (The 2nd HIPPO Neutron Diffractometer User Workshop for Materials and Earth Sciences, Santa Fe, NM, February 28–March 2, 2001).

Hydrous Mineral Phase_A $\text{Mg}_7\text{Si}_2\text{O}_8(\text{OD})_6$

Phase A

Hist 1

Bank 1,2-Theta 150.0, I-S cycle 361 Obsd. and Diff. Profiles

Phase A

Hist 3

Bank 3,2-Theta 90.0, I-S cycle 361 Obsd. and Diff. Profiles

Fig. 1. The Rietveld refinement for the time-of-flight powder neutron diffraction pattern of deuterated phase-A $\text{Mg}_7^{\text{IV}}\text{Si}_2\text{O}_8(\text{OD})_6$. Observed data are indicated by a cross “+”; the calculated pattern is drawn as a continuous red line; and the difference between calculated and observed patterns is shown at the bottom. The Bragg reflection positions are shown by short vertical bars marked below the diffraction pattern.

Space group $p6_3$
 Laue symmetry $6/m$
 acentric primitive
 hexagonal lattice

Hydrous Mineral Phase_A $\text{Mg}_7\text{Si}_2\text{O}_8(\text{OD})_6$

Lattice parameters:

a	b	c
7.833995	7.833995	9.545873
alpha	beta	gamma
90.00000	90.00000	120.00000

Atom	X	Y	Z
Mg	.3750	.4524	.3748
Mg	.2238	.2422	.1042
Mg	.3333	.6667	.1214
Si	.6667	.3333	.1709
Si	.0000	.0000	.3922
O	.2125	.0344	-.0258
O	.4637	.0894	.4802
O	.4523	.2929	.2385
O	.1681	.4452	.2361
O	.6667	.3333	.0039
O	.0000	.0000	.2413
D	.0387	.3664	.2369
D	.1672	.7106	.9235

Fig. 2. Crystal structure of phase-A $\text{Mg}_7\text{Si}_2\text{O}_8(\text{OD})_6$ shown from different angles. The magnesium-centered octahedra and the silicon-centered tetrahedra are the major building blocks of the structure, and the hydrogen (blue ball, deuterium in the current case) atoms are tangled with the oxygen atoms (green ball). Large voids are present in the crystal structure, which are expected to collapse at higher pressures. The refined lattice parameters and structure parameters are listed on the diagrams.

New Windows on Gamma-Ray Bursts

98020

E.E. Fenimore

Gamma-ray bursts are the largest explosions in the universe, outshining supernova by at least a factor of 1000 while they literally flood the entire universe with gamma rays. Since their discovery at Los Alamos in 1973, the key uncertainty has been their distance from Earth. They never repeat so it has been difficult to study individual bursts long enough to get an accurate location. A key defining property of the bursts are rapid fluctuations in the rate of energy production. We investigated these fluctuations to understand the characteristics of the underlying process, which is capable of converting nearly the mass of the sun directly into energy.

Recently, a handful of bursts have been accurately located, revealing that they originate in faraway galaxies. Those few bursts give us our first well-calibrated estimates of the distance to the events, and therefore the total energy produced by the bursts. We have used these events to find a characteristic of the bursts that is correlated with the total energy produced. We found that the spikiness associated with the rapid fluctuations correlates with the absolute energy production: more rapid variations are correlated with more energy production.

We established a quantitative relationship between the spikiness and the total energy production that allows calculation of the distance to an event based only on the observed total flux and the time variation in the gamma rays. We applied the relationship to 220 well-observed bursts, establishing estimates of the distance to each burst. From this, we can determine the number of events as a function of the distance; that is, the burst formation rate as a function of the “redshift,” a measure of the distance in terms of how much the expansion since the Big Bang has stretched, or reddened, light. There is a growing consensus that gamma-ray bursts are the result of the collapse of massive stars into black holes. Since massive stars die almost as soon as they are born (a few million years), we can determine the formation rate of stars by measuring the death rate of massive stars through the rate of gamma-ray bursts.

The figure shows the burst formation rate from our analysis and the star formation rate estimated from supernova observations. The star formation rate is a crucial diagnostic of the evolution of the universe, and most supernova observations indicate that the rate of new star production leveled out at about a redshift of 2.5. However, the supernova observations are substantially hampered by dust. Our burst formation rate is unaffected by dust and indicates that star formation occurred at a much higher rate much earlier in the universe than previously thought.

Publications

Fenimore, E.E., and E. Ramirez-Ruiz, “Redshifts For 220 BATSE Gamma-Ray Bursts Determined by Variability and the Cosmological Consequences” (submitted to *Astrophys. J.*).

Ramirez-Ruiz, E., and E.E. Fenimore, “Implications of Pulse Width Evolution in Gamma-Ray Bursts,” *Astrophys. J.* **539**, 712 (2000).

Walker, K.C., et al., “Gamma-ray Bursts Have Millisecond Variability,” *Astrophys. J.* **537**, 264 (2000).

Wu, B., and E.E. Fenimore, “Spectral Lags of Gamma-Ray Bursts from Ginga and Batse,” *Astrophys. J. Lett.* **535**, L29 (2000).

The rate of formation of gamma-ray bursts (histogram) and stars (dotted line) as a function of the distance in the universe as measured by the redshift, z . The star formation is based on supernova observations, which have substantial uncertainty due to the interference of dust. The gamma-ray burst observations are unaffected by dust and indicate a much higher rate of production early in the universe.

Advanced Computational Analysis of Disordered Materials and Clay Minerals

98021

David L. Bish

X-ray and neutron diffraction are the most powerful methods for studying the structures of crystalline solids, including many materials of interest to nuclear weapons and environmental programs. Crystallographically disordered solids are some of the most technologically useful materials due to their inherent disorder and high surface areas. Unfortunately, existing crystallographic methods are largely restricted to ordered materials (Fig. 1a), and disordered materials (Fig. 1b) cannot be accurately characterized or modeled. We have developed a new method for diffraction analysis of the structural details of disordered materials. The method combines Rietveld refinement methods with a new treatment of disorder that completely describes scattering over all parts of reciprocal space sampled in a diffraction experiment. This approach will allow researchers to quantitatively analyze disordered materials, such as zeolite and clay catalysts, superconductors, and nanocomposites, representing a major breakthrough in our abilities to understand the structures of polycrystalline disordered materials.

We developed crystallographic models to describe disordered layered materials, including: crystallite size in three dimensions; crystallite-size distribution for both ordered and disordered portions of the crystal; a variety of specific rotations of individual layers; and variations in structural vacancies. We modeled clay minerals first, as they make up the most important group of natural disordered materials relevant to DOE environmental management programs.

Disorder in the mica/smectite minerals was modeled well with existing disorder theories, but kaolin minerals, one of the technologically most important clay minerals, required development of new theories. Our model simulates the effects of fixed shifts between adjacent layers, and it allows only very specific stacking of layers to avoid energetically unfavorable interactions. We also incorporated the effects of random displacements in the *X-Y* plane to account for the existence of broad energy minima across interlayer interfaces. Application of the new model produced realistic diffraction patterns, but no combination of the model parameters matched all observed data for all materials. Therefore, we will continue to pursue additional theories.

We have also coded derivatives for all disorder parameters to allow *determination* of these parameters in a Rietveld refinement, rather than simply modeling their effects.

Although we have targeted the area of clay mineralogy for the initial application of this methodology, the new code will be equally applicable wherever disordered materials are important, such as with zeolite catalysts, nanocomposites, C-based intercalation compounds, high- T_c superconductors, $\text{FeF}_2/\text{ZnF}_2$ and GaAs/AlAs superlattices, and multilayer crystals. No such code is presently available, and this development will be a major milestone in diffraction studies. We believe the new combined method represents a breakthrough in our abilities to analyze the structures of polycrystalline disordered materials, a breakthrough that could well be similar in magnitude to that represented by the standard Rietveld method.

Publications

Bish, D.L., et al., "Three-Dimensional Interstratification of Structural Units in Silicate Minerals: The Structure of Opal-CT," *Geological Society of America Abstracts with Programs* **32** (2000).

Guthrie Jr., G.D., et al., "An Integrated Model for Interstratified Illite/Smectite," *Geological Society of America Abstracts with Programs* **32** (2000).

Johnston, C.T., "Vibrational Spectroscopic Study of the 1.03 and 0.95 nm Kaolinite-Hydrazine Intercalation Complexes," *J. Phys. Chem. B* **104**, 8080 (2000).

Johnston, C.T., et al., "Distribution of Dickite- and Nacrite-like Stacking Sequences in Kaolin," in *Proceedings of the 37th Annual Clay Minerals Society Meeting* (Clay Minerals Society, Boulder, CO, 2000), p. 69.

Reynolds Jr., R.C., and D.L. Bish, "The Effects of Grinding on the Structure of a Low-Defect Kaolinite," in *Proceedings of the 37th Annual Clay Minerals Society Meeting* (Clay Minerals Society, Boulder, CO, 2000), p. 97.

Fig. 1. X-ray powder diffraction patterns of ordered (a) and disordered (b) kaolinite, one of the most common clay minerals on the Earth's surface. These patterns illustrate the tremendous difference between ordered and disordered materials. Note that the diffraction pattern of the disordered material (b) cannot be simulated by simply broadening the pattern of the ordered material (a).

Tsunami from Asteroid and Comet Impacts

98022

Jack G. Hills

Asteroid and comet impacts are the single greatest known threat to the survival of humanity and even life on Earth. One serious consequence of such an impact is tsunami, if the impact occurs in the ocean. We have used Los Alamos computer capabilities and professional expertise to model the tsunami run-ups expected from such encounters. We were motivated to reduce the threat from asteroid impacts in two ways: (1) by providing a risk assessment of the amount of damage expected from such an impact, which will determine the appropriate amount to spend on efforts to prevent or mitigate such disasters; and (2) by identifying coastal areas that are particularly vulnerable to such impacts. We used simulations of large asteroid impacts in mid-ocean to identify coastal areas that are most vulnerable. We expected to find the range of damage in these vulnerable areas over a span of time by doing Monte Carlo simulations of impacts in the ocean over the asteroid sizes that are expected to impact the ocean over that time.

Only a small fraction of the work expected to be done during this third year of the project was completed because of a significant reduction in funding. We made progress in modeling the effect of wave dispersion on the propagation of short-wavelength tsunami waves produced by the impacts of smaller asteroids. This study is important in finding how far the waves can travel from the impact point without suffering significant reduction in wave height. The tsunami produced by large impactors, which were studied during the first two years of this project, are not significantly affected by wave dispersion.

The funding reduction this year prevented us from improving the model of the initial series of tsunami waves coming out of the impact point. We were planning to port the shallow water model to a parallel computer to allow it to run with much improved resolution. Results would have provided much more detailed flooding models of specific bays, harbors, and other high-value assets.

Finally, we were to use Monte Carlo simulation to find the range of damage to some highly vulnerable areas such as Long Island that would result from the impacts of both large and small impactors. The small impactors are far more frequent than the large ones that we studied earlier, but each one produces much less damage unless it hits near the coast. We were planning to find the relative importance of the small versus large impactors.

Publications

Hills, J.G., and M.P. Goda, "Damage from Comet-Asteroids Impacts with Earth," *Physica D* **133**, 189 (1999).

Hills, J.G., and M.P. Goda, "The Asteroid Tsunami Project at Los Alamos National Laboratory," *Science of Tsunami Hazard* **19**, 55 (2001).

A Large-Aperture, Wide-Angle Air Cerenkov Telescope

98023

Constantine Sinnis

Hess first discovered cosmic rays in 1912. Since then, researchers have learned much about the nature of cosmic ray particles, but the details of their origin and mechanisms for acceleration and propagation still remain a topic at the forefront of scientific research. One of the most intriguing aspects of cosmic-ray research is determining the mass composition of the cosmic radiation at energies around 3×10^{15} eV, often referred to as the “knee” in the cosmic-ray spectrum. At this energy, the slope of the all-particle spectrum exhibits a break. Understanding the physics behind the observed break will answer many questions about the life cycle and origin of cosmic rays. Our goal is to extend the measurement of the cosmic-ray composition down into an energy regime where it has been directly measured by balloon-borne instruments and, with the same instrument, measure the composition above the knee.

When a high-energy cosmic ray enters the earth’s atmosphere, an extensive air shower (EAS) is generated. An EAS consists of thousands of relativistic particles traveling in a pancake. The proposed Wide-Angle Cerenkov Telescope will measure the lateral distribution of the Cerenkov light that the EAS generates. Researchers established the use of the Cerenkov lateral distribution to measure the mass composition of cosmic rays with Cerenkov telescopes within the CYGNUS array (the CACTI detector).

During this year, we have completed the construction of the six telescopes and the necessary infrastructure (buildings and cable plant). The 150 photomultiplier tubes have been tested, and the high-current bases have been designed and built. The design of the focal plane light cones is complete, and manufacturing has begun. Engineering data from two of the telescopes indicates that our performance will substantially exceed our design goal; an energy threshold about five times lower than the design goal will be easily achievable. This level of performance will allow for greater overlap with direct measurements. This winter, we will begin regular physics runs.

A New Method for Modeling Wave Propagation in Strongly Heterogeneous Media: Applications to Seismic Wave Propagation in the Earth

98024

Michael Fehler

Modeling seismic wave propagation in the heterogeneous anelastic earth is an important aspect of fossil energy exploration and nonproliferation detection—both important Laboratory missions. Such modeling can be accomplished using a variety of analytic and numerical methods. Analytic methods give reliable results even when media contrasts are strong, but solutions are not available for many media of interest. Numerical methods give reliable results for only weakly heterogeneous media, and most cannot account for the variations in surface topography of real-Earth features such as mountains and canyons. Strong heterogeneities and surface topography can have significant influences on seismic wavefields, but we had no reliable means to model their influences. We had developed a novel microscopic approach, termed phononic lattice solid by interpolation (PLSI), for modeling wave propagation in strongly heterogeneous media, including those with irregular surface topography. The goals of this project were to further develop this method and investigate its reliability.

This year, to extend the approaches we had developed in the previous two years to three-dimensional (3-D) problems, we developed a more efficient method to model particle interactions at each lattice node. (The PLSI approach has rather complicated interaction rules in two dimensions that become even more complex in 3-D.) We investigated a new set of particle interaction rules, called Lattice BGK, which require fewer computations per interaction step. These rules will be more tractable in 3-D. We performed a suite of computational tests on this method and investigated the anelastic attenuation of wave energy that happens in this approach. This attenuation occurs as part of the numerical calculation and can be considered as a beneficial byproduct because attenuation also occurs during elastic wave propagation in the Earth. Most numerical schemes for modeling elastic wave propagation have difficulty in modeling realistic attenuation scenarios. We have investigated approaches for determining the amount of attenuation this method models and explored how to make this attenuation model applicable to the Earth.

Although this project is ended, a great deal of work remains in the testing of these methods. We hope to obtain funding at some future date to continue this research.

Publications

Huang, L.-J., et al., “Absorbing Boundary and Free Surface Conditions in the Phononic Lattice Solid by Interpolation,” *Geophys. J. Int.* **140**, 147 (2000).

The Genesis and Evolution of Basalt on the Moon

99022

William C. Feldman

We are investigating the origin and evolution of basalt on the Moon with data measured by our Lunar Prospector neutron and gamma-ray spectrometers. These data and their analysis provide a first demonstration of the utility of neutron spectroscopy for remote sensing of planetary surfaces, which supports our ability to meet our DOE programmatic activities in the area of nuclear treaty verification.

So far we have developed the first global map of thorium on the Moon. The distribution of thorium suggests that the Moon has a single hot spot near the surface that faces the Earth. This hotspot implies a global redistribution of all radioactive elements that have contributed to heating the Moon and hence the observed distribution of lunar volcanism, which preferentially occurred on the near side of the Moon. We have also created a map of this volcanism as evidenced by enhanced deposits of iron using the Lunar Prospector gamma-ray data.

We have found that the hydrogen content of permanently shaded craters near the south pole of the Moon is enhanced by a factor of about 30 relative to the hydrogen content contained in soils at equatorial latitudes. This ratio is sufficiently high that it is most likely explained in terms of water-ice deposits. However, this year our detailed study of the emplacement and retention of these deposits near both poles shows that a significant fraction of the enhanced hydrogen must be in the form of water molecules.

We have delineated and quantified the chemistry of the different lunar terranes using measurements of fast-neutron fluxes and the ratio of thermal/epithermal neutron fluxes, respectively. It turns out that both data sets provide useful indices that discriminate between basaltic (mafic) compositions normally found in the lunar maria and anorthositic compositions normally found in the lunar highlands. An analysis of their global distribution shows that what ever generated Oceanus Procellarum must also have configured the surface composition of the Moon. We have found further that the fast neutron flux provides a faithful measure of the average atomic mass of lunar soils.

We have also studied the distribution of gadolinium and samarium by combining our thermal neutron data with measurements of the abundances of iron and titanium. These measurements were derived from the UV/VIS spectral-reflectance data gathered by a camera aboard the Clementine mission. The distribution of gadolinium and samarium closely matches that of thorium as measured by our Lunar Prospector gamma-ray spectrometer. These same data have also provided strong constraints on the abundance of TiO_2 of lunar soils. These constraints are about a factor of two below the TiO_2 abundances inferred from analyses of spectral reflectance data.

Publications

Elphic, R.C., et al., "Determination of Lunar Global Rare Earth Element Abundances Using Lunar Prospector Neutron Spectrometer Observations" (accepted in *J. Geophys. Res.*).

Elphic, R.C., et al., "Lunar Prospector Neutron Spectrometer Constraints on TiO_2 " (submitted to *J. Geophys. Res. -Planets*).

Feldman, W.C., et al., "Global Distribution of Lunar Composition: New Results from Lunar Prospector and Clementine" (submitted to *J. Geophys. Res. -Planets*).

Feldman, W.C., et al., "Polar Hydrogen Deposits on the Moon," *J. Geophys. Res.* **105**, 4175 (2000).

Feldman, W.C., et al., "The Chemical Information Content of Lunar Thermal and Epithermal Neutrons" (accepted in *J. Geophys. Res. -Planets*).

Gasnault, O.M., et al., "Combined Analysis of Thorium and Fast Neutron Data at the Lunar Surface" (submitted to *J. Geophys. Res. -Planets*).

Gasnault, O.M., et al., "The Interpretation of Planetary Fast Neutron Leakage Flux and its Application to the Moon" (submitted to *Geophys. Res. Letters*).

Lawrence, D.J., et al., "High-Resolution Measurements of Absolute Thorium Abundances on the Lunar Surface from the Lunar Prospector Gamma-Ray Spectrometer," *Geophys. Res. Lett.* **26**, 2681 (1999).

Lawrence, D.J., et al., "Iron Abundances on the Lunar Surface as Measured by Lunar Prospector" (to be submitted to *J. Geophys. Res. -Planets*).

Lawrence, D.J., et al., "Thorium Abundances on the Lunar Surface" (accepted in *J. Geophys. Res. -Planets*).

Maurice, S., et al., "High-Energy Neutrons from the Moon" (accepted in *J. Geophys. Res. -Planets*).

Sky Patrol Analysis with the Robotic Optical Transient Search Experiment

99023

W. Thomas Vestrand

The Robotic Optical Transient Search Experiment (ROTSE) is a system of optical telescopes designed to respond quickly and automatically to alerts from high-energy satellites that detect gamma-ray bursts. The telescopes turn to focus on the area of the sky where gamma-ray bursts have been detected.

The ROTSE telescopes also perform nightly automatic surveys of the entire sky—to ensure readiness, monitor data quality, and provide baselines. The data from these surveys (or “sky patrols”) is what we use for our project, to search for transient and variable objects of fundamental interest in astronomy. These objects include flare stars (stars that have brief bursts of energy), variable stars (stars that have changes in intensity), active galactic nuclei, meteors, asteroids, and comets. The sky patrol data is archived at Los Alamos and amounts to 2 Tbytes per year. Our project takes advantage of this otherwise minimally used archive of ROTSE data.

Our project supports the Laboratory’s fundamental science mission and enhances the Laboratory’s competence in handling large data files, such as those used in the weapons and threat reduction programs. ROTSE itself is a collaboration between Los Alamos, the University of Michigan, and Lawrence Livermore National Laboratory.

This year has been an exciting one for the ROTSE data project. We completed the pipeline for analysis of ROTSE sky patrol data, and the search for variable and transient sources began in earnest. The utility of the ROTSE sky patrol data was demonstrated this year when a new transient x-ray source, XTE J1118+480, was discovered by the Rossi X-Ray Timing Explorer satellite. While this remarkable black-hole candidate was studied by an armada of major ground-based and satellite observatories, our sky patrol data provided unique predisccovery observations that capture the entire development of the optical outburst, which began before the x-ray outburst. These observations place important constraints on models of the binary-star system.

The richness of our sky patrol data was also demonstrated by our publication of a catalog of 1,781 variable stars we detected in just the 5% of the sky visible to ROTSE. Nearly 90% of these variable stars were previously unknown. It is clear that mining the ROTSE database will have a significant impact on studies that use variables to study galactic structure as well as studies of the physics of variable stars.

Galactic Magnetic Fields: Their Origin and Manifestation in Accretion Disks around Supermassive Black Holes

99024

Warner Miller

This project is concerned with understanding the magnetic fields that accretion disks around supermassive black holes produce. The gravitational binding energy released in the formation of the central black hole powers the quasar-Active Galactic Nuclei (AGN), the brightest objects in the universe, during galaxy formation. These objects also release still more energy in the form of magnetic fields. This magnetic energy is released in the form of giant magnetic lobes, radio lobes, that fill the space between galaxies. These magnetic fields represent the largest accessible or free energy in the universe. (Other energies like rest mass, lambda, and the black body background radiation are not accessible.) These fields are generated in the giant dynamo of the accretion disk forming every galactic black hole. They affect the structure of galaxy spacing in the universe and produce the extra galactic and ultrahigh-energy cosmic rays.

In the course of the project, we have discovered and presented the first understanding of the origin of large-scale cosmic magnetic fields. We also understood and calculated the nonlinear behavior of the Rossby wave instability in accretion disks, the first time a hydrodynamic instability has been shown to transport angular momentum in accretion disks. We simulated the alpha omega dynamo in the sodium experiment and in the black hole accretion disk and in stars with a three-dimensional kinematic dynamo code. We demonstrated in theory and experiment how plumes rotate in a rotating frame, thereby explaining the origin of the critical alpha helicity in the dynamos within accretion disks and in stars.

Publications

Beckley, H.F., et al., "The Flow Field for a Liquid Sodium alpha - \Omega Dynamo Experiment" (submitted to *Phys. Fluids*).

Chacon, L., et al., "An Implicit, Nonlinear Reduced Resistive MHD Solver" (submitted to *J. Comput. Phys.*).

Colgate, S.A., and H. Li, "The Magnetic Fields of the Universe and Their Origin" (Highly Energetic Physical Processes and Mechanisms for Emissions from Astrophysical Plasmas, International Astronomical Union Symposium 195, Bozeman, MT, July 6–10, 1999).

Colgate, S.A., and R.J. Buchler, "Coherent Transport of Angular Momentum: The Ranque-Hilsch Tube as a Paradigm" (14th Florida Workshop in Nonlinear Astronomy Gainesville, FL, February 18–21, 1999).

Gary, S.P., and H. Li, "Whistler Heat Flux Instability at High Beta," *Astrophys. J.* **529**, 1131 (2000).

Gary, S.P., et al., "Simulations of Electron/Electron Instabilities: Electromagnetic Fluctuations," *Phys. Plasmas* **7**(#2), 448 (2000).

Kazimura, Y., et al., "Electromagnetic Fluctuations near the Electron Plasma Frequency from an Electron/Electron Instability," *J. Geophys. Res. - Space Physics* **105**, 10537 (2000).

Kusunose, M., et al., "Temporal and Spectral Variabilities of High-Energy Emission from Blazars using Synchrotron Self-Compton Models," *Astrophys. J.* **536**, 299 (2000).

Li, H., and M. Kusunose, "Temporal and Spectral Variabilities of High-Energy Emission from Blazars using Synchrotron Self-Compton Models," *Astrophys. J.* **536**, 729 (2000).

Li, H., et al., "On the Particle Heating and Acceleration in Black Hole Accretion Systems," *Astronomical Society of the Pacific Conference Series* **161**, 349 (1999).

Li, H., et al., "Rossby Wave Instability of Thin Accretion Disk-II. Detailed Linear Theory," *Astrophys. J.* **533**, 1023 (2000).

Li, H., et al., "Rossby Wave Instability of Thin Accretion Disk-III. Nonlinear Simulations" (accepted in *Astrophys. J.*)

Michel, F.C., and H. Li, "Electrodynamics of Neutron Stars," *Phys. Rep.-Review Section of Physics Letters* **318**(#6), 228 (2000).

Multiscale Physics of Multiphase Flow in Porous Media

99025

Dongxiao Zhang

Physical observations and theoretical treatments of multiphase flow in porous media are usually associated with three different length scales: pore (microscopic), local (lab or macroscopic), and field. Dominant processes and governing equations may vary with scales. Extending from one scale to another requires upscaling or downscaling, which allows the essence of physical processes at one level to be summarized at the coarser or finer level.

We plan to systematically investigate fundamental issues of multiphase flow at the microscopic and macroscopic scales and to develop upscaling methods for predicting macroscopic quantities and characteristic relationships based on some statistical parameters of microscopic quantities. A successful approach to upscaling would lead to greatly increased efficiency and accuracy in simulating multiphase flows in porous media at the lab and field scales. This project addresses some important issues of multiscale science, which is a key component for many of the Laboratory's core competencies.

This year, we continued using an enhanced lattice Boltzmann permeameter (LBP) to study single- and two-phase flows through pore-scale geometries, which are obtained with high-resolution computed microtomography (CMT) of rock cores. The LBP is capable of realistically capturing the detail of the porous-medium geometry and all the relevant physical and chemical processes. In addition, it can provide necessary data at the microscopic and macroscopic scales.

With this computational tool, we were able to investigate some fundamental issues of single-phase flow in porous media, such as the existence of representative elementary volume (REV), the scale dependence of porosity, specific surface area and permeability, and the relationship among these three quantities. We found that REV may not be well defined in a deterministic sense but that it does exist statistically. The concept of statistical REV is weaker than the deterministic REV but is more useful in applications. In addition, we found that the size of REV may be different for different quantities.

We have also investigated fundamental issues of multiphase flow on the basis of the same pore geometries and examined computationally multiphase constitutive relations such as the capillary-saturation relation and the relative permeability-saturation relation, which are required to model multiphase flow at a macroscopic scale. For the remainder of the project, we will continue to investigate fundamental issues of multiphase flow and develop upscaling methodology from microscopic to macroscopic scale.

Publications

Zhang, D., et al., "Pore Scale Study of Flow in Porous Media: Scale Dependency, REV, and Statistical REV," *Geophys. Res. Lett.* **27**, 1195, 2000.

Antarctic Circumpolar Wave and El Niño

99026

Chung-Chieng A. Lai

The main objective of this research is to expand our knowledge of the El Niño phenomenon on a global scale, and in particular, its links to the Antarctic Circumpolar Wave (ACW). This work will provide valuable information toward the ultimate goal of being able to forecast El Niño and related climate variability. These results can provide information for assessment of climate-related energy policies for the core DOE national energy security mission. Our work adds creative concepts and the new findings of climate variabilities, which will enhance our climate system modeling capability and put Los Alamos at the forefront of global climate research.

We have used two approaches to study the oceanic and atmospheric processes involved in El Niño, the ACW, and their possible connection. Climate data analysis is our first approach. The second methodology is to model a hypothesis using a simulation and then study the results.

One of the difficulties in predicting El Niño-related climate variation is the irregularity of the El Niño cycle. There are variations in the amplitude of the warm/cold phases of the cycle as well as in the evolution of El Niño events. What is the reason for the irregularity in the El Niño cycle? Our main approach to finding this answer is to examine the decadal climate variabilities that may modulate the behaviors of the El Niño variations on an interannual time scale. During this project year, we have examined the climate variabilities revealed from simulation of the Community Climate System Model of the National Center for Atmospheric Research. We verified the link between sea surface temperatures (SST) in the tropical El Niño region and in regions along the Antarctic Circumpolar Wave.

We have focused on observational evidences of monthly mean SST during the past century and found a variety of El Niño patterns on a global scale. In particular, we identified a typical El Niño evolution whose SST anomaly pattern can be directly traced back to the Antarctic Circumpolar Wave. We have further looked into the variability in the entire Pacific Ocean and found interesting evolutions of a decadal oscillation pattern that may partially explain the characteristics of El Niño variability.

Publications

Huang, Z., and C.-C. Lai, “2000a: An Examination of ENSO Signal in Antarctic Circumpolar Current Region Revealed by NCAR Climate System Model Simulations,” in *Proceedings of the Sixth International Conference on Southern Hemisphere Meteorology and Oceanography* (American Meteorological Society, Boston, MA, 2000), p. 215.

Huang, Z., and C.-C. Lai, “2000b: A New Look of the Pacific Decadal Oscillation,” in *Proceedings of the American Geophysical Union 2000 Fall Meeting*, special edition of *EOS: Transactions*, v. 81, No. 48, Nov. 28, 2000, article no. A62B-06.

Low-Energy Neutral Atom Imaging: Watching Magnetospheric Dynamics

99027

Michelle F. Thomsen

Energetic neutral atoms (ENAs) are generated when energetic ions in the magnetosphere are neutralized by charge exchange with cold geocoronal neutrals. Imaging these ENAs is a powerful method to remotely view the structure and dynamics of Earth's magnetosphere. ENA imaging has profound implications for global monitoring of the near-Earth space environment, especially in regard to the safety of satellite systems during times of high magnetospheric activity.

Our project involves the analysis and interpretation of data from the Low Energy Neutral Atom Prototype (LENA-P) imager that was built by Los Alamos in collaboration with the Southwest Research Institute and The Aerospace Corporation. LENA-P was launched in the winter of 1997 and was the first instrument to image ENA emission from the bulk of the magnetospheric ion population. Our work focuses on identifying temporal transients, correlating them with geomagnetic activity, and mapping the spatial extent and spectral content of structures.

We have received and processed 37 months of LENA-P observations. Our effort during the first year of the project was aimed primarily at devising data-handling and archiving procedures and appropriate summary data displays (see Fig. 1), as well as examining short-time-scale enhancements and possible relationships between LENA fluxes and viewing.

During this year we conducted extensive statistical analyses of the observations with respect to satellite location, time from launch, and geomagnetic activity. We found very little statistical association between the LENA fluxes and magnetic activity. However, there was a strong association with the local time of the measurements. Orbit-averaged fluxes were much higher when the spacecraft local time was between noon and dusk than at other local times, and this dependence was repeated in the second year of observations as well (see Fig. 2).

Analysis of the LENA-P data has provided valuable insights to guide our operations and data analysis for our Medium-Energy Neutral Atom (MENA) imager aboard the Imager for Magnetopause-to-Aurora Global Exploration (IMAGE) satellite, launched last in the spring of 2000. We are comparing these two data sets to try to extract additional information about the performance of each instrument, as well as possible stereoscopic viewing of magnetospheric phenomena.

Fig. 1. LENA-P count rates from one orbit on July 9, 1999, as a function of energy, viewing direction, and time. The regions of intense fluxes at the left- and right-hand sides are produced by charged particles local to the satellite as it moves through the ion-trapping region near Earth. The weaker fluxes in the center correspond to ENAs observed from high latitudes.

Fig. 2. Daily averaged LENA-P count rate versus time for the first year and a half of the mission. The peaks early in 1998 and 1999 correspond to intervals when the satellite orbit was located in the afternoon region of the magnetosphere.

Galaxies and Large-Scale Structure in a Universe with a Cosmological Constant

99028

Wojciech H. Zurek

This project investigates the formation of galaxies and clusters of galaxies in the presence of gravity and expansion, as well as the less well understood cosmological constant that modifies the expansion of the universe. We are studying the possible origin of these forces and their impact on the formation of large-scale structures in the universe.

This year, we focused on the study of phase transformations in the nonequilibrium setting. Such phase transitions are expected to occur in the early history of the universe. One of the implications of the phase transitions is the possible emergence of topological defects, which may directly influence the evolution of the universe on all scales. We studied the behavior of the fields in the vicinity of the critical temperature, where fluctuations may be important (so-called Ginzburg regime). We concluded that the fluctuations are quite ineffective in erasing the memory of the order parameter (field) on scales relevant for the formation of defects. Our studies aid understanding the dynamics of the cosmological phase transformations by analogy with the much more accessible transition in the laboratory.

Nonlinear Dynamical Processes Involved in Earthquake-Induced Strong Ground Motion

2000029

Paul A. Johnson

Our primary objective in this project is to test the hypothesis that seismic wave mixing effects significantly influence strong ground motion (SGM), the most damaging aspect of a large earthquake. By “mixing,” we mean that new frequencies are created near the ground surface, where layers can ring like a bell that has been struck by a hammer. The mixing results from nonlinear behavior of the near-surface layers. Our second objective is to study what causes the nonlinear behavior in order to suggest measures to mitigate the shaking resulting from SGM.

In the distant past, large earthquakes occurred where Los Alamos is located. Our work will directly benefit planning and building design. This project reflects the goal of DOE to use the huge supercomputing power of the national laboratories to solve complex national problems.

We will accomplish our objectives by conducting (1) dynamic resonance wave experiments on sedimentary materials to determine the influence of fluids on the nonlinear response of the near-surface layers, (2) laboratory experiments to determine the origin of, and possible influences on, the nonlinear behavior, and (3) a partial analysis of worldwide larger-wave-amplitude earthquake data sets in order to test our hypothesis regarding model importance.

We have applied different numerical models to SGM and determined that the successful model must incorporate the basic element of “hysteretic” nonlinearity in the upper layers of the Earth. From laboratory studies we have discovered that, at low strain amplitudes, the scale of the nonlinear mechanism is atomic. This was a significant surprise because we had assumed that the scale was closer to the grain-size scale, and the observation influences our modeling and general understanding of the basic nonlinear mechanisms leading to nonlinear wave behavior in surface sediments. We expect that other mechanisms, such as grain-to-grain sliding, also become active and contribute to the overall nonlinear wave behavior at higher wave amplitudes. We have also discovered that moisture content has a very large effect on nonlinear behavior, especially at low water saturations: in wetter climates or in places where the groundwater is near the surface, both nonlinear wave damping and resonance modal shifts are significantly larger than under very arid conditions.

Publications

Ostrovsky, L., and P. Johnson, “Dynamic Nonlinear Elasticity in Geomaterials,” (accepted in *Rivista del Nuovo Cimento* of the Italian Physics Society).

Van Den Abeele, K., et al., “The Influence of Water Saturation on the Nonlinear Mesoscopic Response of Earth Materials, and the Implications to the Mechanism of Nonlinearity,” (accepted in *J. Geophys. Res.*).

Heat Flux Dissipation in Collisionless Space and Astrophysical Plasmas

2000030

S. Peter Gary

The transport of thermal energy by electrons is a fundamental process in all hot plasmas. We are using particle-in-cell computer simulations to attack the unsolved problem of thermal transport in collisionless plasmas such as the solar wind. In particular, we are seeking to verify the hypothesis that wave-particle scattering from instabilities acts to impose an upper bound on the heat flux. We are using observations from Los Alamos instruments on solar wind missions both to provide a starting point for the simulations and to confirm (or disprove) the conclusions derived from those simulations. The results of this project will enhance the Laboratory's capabilities in space, astrophysics, and fusion plasmas and, if successful, will have application to the hot, dense plasmas of weapons program interest.

This year, we used magnetic field electron observations from the Ulysses spacecraft to seek correlations between whistler-like magnetic fluctuation amplitudes and electron anisotropies. We found no clear correlation between magnetic fluctuations and the dimensionless electron heat flux, but we found a good correlation between such fluctuations and the electron core temperature anisotropy. This result provides evidence that a whistler instability constrains that anisotropy in the solar wind.

Publications

Li, H., et al., "On the Dissipation of Magnetic Fluctuations in the Solar Wind" (submitted to *Geophys. Res. Lett.*).

Newbury, J.A., and S.P. Gary, "Whistler Instabilities in the Solar Wind: Magnetic Fluctuations and Anisotropy Constraints" (submitted to *J. Geophys. Res.*).

Stawicki, O., et al., "Solar Wind Magnetic Fluctuation Spectra: Dispersion Versus Damping" (submitted to *J. Geophys. Res.*).

Analysis of Large-Scale Structure in the Sloan Digital Sky Survey

2000031

Michael S. Warren

The Sloan Digital Sky Survey will probably be directly responsible for the most important contributions to cosmology during the first decade of the 21st century. The Sloan 2.5-m wide-field telescope at Apache Point Observatory, near Cloudcroft, New Mexico, will map the positions and redshifts of nearly 1 million galaxies.

This project will analyze the data provided by the Sloan survey in order to obtain a theoretical understanding of the large-scale structure in the universe. The fundamental parameters of the universe are contained in the statistical measures of galaxy clustering, such as the two-point correlation function. Los Alamos has unique expertise in accelerating the calculation of galaxy correlation functions and similar statistics through the use of hierarchical tree code algorithms. Additionally, we can deduce the origin of cosmic structure by numerically modeling the formation of galaxies and comparing the model to the observations.

We developed initial versions of codes to efficiently determine the two-point correlation function, power spectrum, and small-scale velocity dispersion of Sloan-scale catalogs. We also refined our code, which generates initial conditions without first going to Fourier space, allowing us to generate initial conditions in a hierarchical manner. This way, we can make the mass resolution of the particles change as a function of radius in order to best reproduce the characteristics of the survey. We converted some of our previous simulation results into a synthetic catalog of galaxies and are able to place observers within the synthetic catalog to determine sources of systematic error that would not be apparent with any other approach.

Our recent work has focused on improving the fidelity of massively parallel N -body simulations at small length scales in order to provide more relevant synthetic data. Figure 1 demonstrates the galaxy halos formed from dark matter in a simulation containing about 5 million particles but using a unique set of initial conditions that preliminary results indicate has increased the maximum density in the final halos by a factor of 30.

Publications

Frenk, C.S., et al., “The Santa Barbara Cluster Comparison Project: A Test of Cosmological Hydrodynamics Codes,” *Astrophys. J.* **525**, 554 (1999).

Fig. 1. The image shows a region of space about 150 million light years across, in which we have simulated the formation of galaxy halos formed from dark matter. The simulation starts about 13 billion years before the present day and contains about 5 million gravitationally interacting particles.

Observing High-Energy Transients with Milagro

2000032

Todd Haines

Particle acceleration in the cosmos is not well understood. Nowhere is this more evident than in the various high-energy transient phenomena that are known to occur, from those in our own neighborhood in the form of flares from the sun, to those on the other side of the universe in the form of gamma-ray bursts. These known sources of high energy are generally transient, varying in length from fractions of a second to days.

The Milagro gamma-ray observatory at Los Alamos has the world's only wide-aperture, high-duty particle detector capable of detecting cosmic rays and gamma rays in the teraelectronvolt energy regime. Because it can detect bursts of such high energy, Milagro is uniquely suited for the study of transient sources. This year, Milagro operated about 90% of the time, with high reliability.

In this first year of our Milagro project, a great deal was accomplished. We made some progress on two of our main goals: (1) developing very fast online analysis of the signals Milagro detects so that we can search for transients in nearly real time; and (2) finding ways to lower Milagro's energy threshold to make it more sensitive to transients.

To make Milagro more sensitive, we want to lower its energy threshold without greatly increasing the trigger rate from cosmic rays. The methods we have tried so far make Milagro very sensitive to single large-angle cosmic-ray muons, making Milagro less effective at detecting transients. To search for transients in the data from Milagro's more sensitive threshold, we wrote a straightforward algorithm based on previously developed ideas. The algorithm is effective but not as powerful as one would eventually like to make it.

We also developed a new technique for rejecting cosmic-ray background—a significant advance. Cosmic rays come in from all directions and produce air showers that are very similar to gamma-ray air showers. Without some method to reject these background events, one must search for gamma-ray sources on top of this very “bright” background. Doing so is much like trying to see the moon during the day—the moon is only slightly brighter than the daytime sky, so it is difficult to find. Rejecting the background makes the problem much more like finding the moon at night—the moon is then very bright and much easier to see.

Our background rejection method is based on the signals observed in the lower part of Milagro—the so-called muon layer. We look for a “hot spot” in this bottom layer. The hot spot is due either to a penetrating muon or a high-energy particle in a cosmic-ray shower, both of which are not often present in gamma-ray showers. With a collaborator from the University of California at Irvine, we developed a simple algorithm that works well for filtering out cosmic-ray background in typical events. The one weakness of our method is that it classifies gamma-ray showers whose core lands on Milagro as cosmic-ray background events. This classification is not desirable because these showers are the best, most easily reconstructed events that Milagro observes. Clearly, we will need to improve this weakness in the algorithm.

Optical and Chemical Studies of Sulfate Aerosols to Predict the Recovery of the Ozone Layer and Constrain the Earth's Radiation Budget

2000033

John R. Stephens

Human activities are causing two global environmental problems: ozone depletion and climate change. As a result of international agreements, atmospheric levels of chlorofluorocarbons are now declining, and the resultant ozone losses should gradually disappear. However, atmospheric concentrations of greenhouse gases, including carbon dioxide, continue to rise. Greenhouse gases warm the lower atmosphere but cool the stratosphere by enhancing radiative heat loss to space. Increases in greenhouse gases will delay until the next century the recovery of stratospheric ozone. Sulfate aerosols play important roles in both ozone loss and climate change by affecting stratospheric chemistry and radiative transfer, respectively. We are measuring the physical, optical, and chemical properties of simulated stratospheric sulfate aerosols suspended in gases using a single particle balance. Our work will provide improved data for global climate models and improve the understanding of ozone depletion.

During the year, we have modified our particle balance to allow measurements of single particle absorption using a photoacoustic method in which the particle is illuminated by modulated laser light and the resultant pressure modulation of the gas in the particle trap is measured. We developed a new method to inject particles into the balance, incorporated a fiber-coupled laser, and added a photoacoustic detector to the system. We also measured the acoustic characteristics of the trap. The acoustic noise in the laboratory generally increases with frequency and shows a broad peak about 2 kHz. In contrast, acoustic resonances occur in the trap near 300, 500, and 900 Hz. By operating at one of the resonant modes of the trap, we maximize the signal to noise of the photoacoustic signal caused by particle absorption. The work to date has shown the feasibility of measuring the absorption of particles within the balance. During the next year, we will begin injecting sulfate and mineral particles into the balance and measuring their size and absorption properties. We will then move to more stratospherically relevant particles of mixed sulfate and mineral compositions and measure their absorption and albedo.

Publications

Dubey, M.K., and J.R. Stephens, "Towards Measurements of Optical Absorption by Single Atmospheric Aerosols in an Electrodynamical Balance" (American Geophysical Union Conference, Washington, DC, May 30–June 2, 2000).

Tracer Tomography in Unsaturated Fractured Rock

2000034

H. J. Turin

Understanding the processes that control the flow of water and transport of solutes down from the ground surface through the vadose zone to the water table is a major challenge facing the scientific community today. The flow processes determine aquifer recharge rates, which in turn limit the ultimate sustainable yield of groundwater resources, the subject of DOE's global sustainability focus. Transport rates determine the environmental risks posed by present or future radioactive and other hazardous waste sites, which occur at many DOE facilities including Los Alamos and Yucca Mountain. Studying present-day distributions of global-fallout radionuclides in the vadose zone can provide important insight into the nature and rates of these processes. By simultaneously considering different radionuclides with different physical and chemical processes "tomographically," we can learn far more than we could by looking at a single species. To enable low-cost, large-volume sampling of vadose-zone water, we are taking advantage of the access into the vadose zone afforded by deep cave systems.

This year we successfully mounted three sampling expeditions to Carlsbad Caverns National Park in southeastern New Mexico. We sampled 26 pools from Lechuguilla Cave and Carlsbad Cavern and also collected one local precipitation sample and samples from two local surface springs. These samples were analyzed for major ions and trace elements at the Laboratory, for stable isotopes at New Mexico Institute of Mining and Technology, and for low-level tritium (radioactive hydrogen) at the University of Miami. Silver chloride accelerator targets were prepared at New Mexico Institute of Mining and Technology and analyzed for radiochlorine at Purdue University and at Lawrence Livermore National Laboratory. A subset of the samples were analyzed for stable carbon isotopes and radiocarbon at the University of Arizona.

Unequivocal identification of global-fallout levels of tritium and radiochlorine in some, but not all, of the samples has confirmed the validity of cave pools as vadose-zone sampling sites. Preliminary interpretation of the Lechuguilla Cave data show that although in most areas transport velocities are about 1–2 meters per year, in a few cases preferential pathways have accelerated that rate by a factor of approximately four. These pathways may be associated with surface topography and structural features. Furthermore, a tomographic comparison of tritium and radiochlorine distributions suggests that vapor-phase transport plays a significant role in subsurface redistribution of water vapor.

Publications

Turin, H.J., and M.A. Plummer, "Lechuguilla Cave Pool Chemistry, 1986–1999," *J. Caves Karst Stud.* **62** (2), 135 (2000).

Turin, H.J., et al., "Chlorine-36 and Tritium Profiles in Deep Caves of Southeastern New Mexico," *Abstr. Geol. Soc. Am.* **32** (7), A-481 (2000).

Optical Refrigeration

2000035

Timothy Gosnell

We have discovered a method by which solid materials can be cooled directly with laser light. Our objective is to construct a completely solid-state device that will support a thermal load of 1 mW and operate continuously at 150 K upon descent from room temperature. The potential applications for cooling with laser light include threat reduction and use on space missions.

We are applying three techniques in developing a suitable cooling element for optical refrigeration: (1) absorption and fluorescence spectroscopy, (2) photothermal deflection spectroscopy, and (3) laser cooling in a vacuum. We are using conventional absorption and fluorescence spectroscopy to detect and identify trace parasitic impurities that reduce the cooling efficiency of a material.

Photothermal deflection spectroscopy allows us to study the cooling potential of candidate materials in great detail without the need to isolate the sample in a vacuum and measure temperature changes directly. Rather, a pump laser is focused into the sample, and the temperature gradient thus generated yields a “deflection” of a counterpropagating probe beam (usually HeNe). The effect is exactly analogous to a mirage: a thermal gradient above a hot landscape deflects light from a blue sky to make it appear as though the light emanates from the land, yielding the appearance of a lake. We are able to study both the pump-wavelength dependence of the photothermal deflection and the time dependence of the deflection. Both types of data are especially useful in diagnosing the presence of contaminants, radiation trapping, and other effects that might degrade performance of the cooling element.

Our experiments with laser cooling in a vacuum are the proof of the pudding. After a suitable candidate material (host + Yb³⁺ doping level) is selected, a small sample is isolated in a vacuum chamber and optically pumped at a wavelength that optimizes the cooling power. The temperature is measured conveniently through the use of the sample's fluorescence spectrum, which is strongly temperature dependent. A precision of 1 K is readily achieved with this technique; previous experiments have exhibited temperature changes of 65 K with respect to room temperature.

This year we performed extensive absorption and fluorescence measurements in the visible and near-infrared spectral regions on ZrF₄-BaF₂-LaF₃-AlF₃-NaF (ZBLAN) glass samples intentionally and individually doped with all trivalent rare-earth ions. For the first time, we identified parasitic impurities present in ZBLAN:Yb³⁺ cooling samples and measured their concentrations.

However, we shifted directions when we discovered laser cooling in Yb³⁺-doped *crystalline* solids. Specifically, photothermal deflection measurements of Yb³⁺-doped KY(WO₄)₂ exhibited a cooling signal whose magnitude suggested that a factor-of-5 increase in cooling power could be obtained with the use of this host material.

Unfortunately, the monoclinic crystal structure of KY(WO₄)₂ makes detailed interpretation of photothermal deflection data extremely challenging. We undertook a systematic improvement of the photothermal deflection apparatus, including calibrating the induced temperature gradient, in order to offer much more quantitative information. In the process, we discovered some anomalous photothermal deflection signals in both ZBLAN and KY(WO₄)₂ samples, suggesting that new physics is being exposed in the measurements. We have investigated numerous hypotheses for the anomalous signals and have rejected each one. At this time, the signals remain a mystery.

Instrumentation and Diagnostics

An Integrated Solid-State Optical Device with High-Speed Scanning, Variable Focusing, and Frequency-Doubling Capabilities

98027

Quanxi Jia

Control of the position and spot size of a high-speed laser beam is useful for many applications including optical data storage, laser printing, and display technology. These data storage, laser printing, and display technology functions have traditionally been performed using separate elements for focusing and scanning, which require multistep manufacturing processes and sometimes necessitate difficult alignment procedures.

Because of the rich range of linear and nonlinear optical properties exhibited by ferroelectrics, we have been able to integrate electro-optic lenses and scanners on a ferroelectric crystal wafer. This integration greatly reduces the cost of producing such devices and improves their reliability. Our project goal was to develop a new generation of multifunctional, integrated, solid-state optical devices.

This year we successfully integrated an independently controlled high-power electro-optic lens and a large-angle scanner on a single-crystal lithium tantalate wafer. The lens is capable of collimating light leaving from waveguides that range in diameter from 4–40 μm . The collimated light is then deflected over an angular range of nearly 20° by an independently controlled deflector. This scan range is almost 5 times greater than any range previously reported for a continuous-scanning electro-optic deflector. Consequently, for some applications this device we are fabricating may provide a faster, more mechanically robust alternative to galvanometer-type and other mechanical-scanning systems.

For the first time, we have also designed and fabricated a horn-shaped electro-optic scanner on a ferroelectric lithium tantalate wafer. The horn-shaped scanner design offers greater scanning angles compared with a similar rectangular scanner. Our scanner can scan 632.8 nm of light by an unprecedented 14.6° angle that corresponds to a measured voltage dependence-of-deflection angle of $1.845^\circ/\text{kV}$. This angle is one of the largest scan angles so far reported for this technology.

Publications

Gahagan, K.T., “Integrated High-Power Electro-Optic Lens and Large-Angle Deflector” (submitted to *Appl. Opt.*).

Gahagan, K.T., “Integrated High-Power Electro-Optic Lens/Scanner for Space-Based Platforms” (submitted to *Proceedings of SPIE*, 45th Annual Meeting of the International Society for Optical Engineering, San Diego, California, July 30–August 4, 2000).

Gopalan, V., “In Situ Video Observation of 180° Domain Kinetics in Congruent LiNbO_3 Crystals,” *Appl. Phys. Lett.* **75**, 2482 (1999).

Gopalan, V., et al., “Integration of Electro-Optic Lenses and Scanners on Ferroelectric LiTaO_3 ,” *Integrated Ferroelect.* **25**, 371 (1999).

Scrymgeour, D. A., “A Large-Angle Electro-Optic Scanner on LiTaO_3 Fabricated by In Situ Monitoring of Ferroelectric Domain Microengineering” (submitted to *Appl. Opt.*).

Cryptographic Key Generation using Long-Baseline Radio Interferometry

98028

Richard J. Hughes

We have been developing a cryptographic key generation system based on observing radio noise from distant astronomical objects. The basic idea is that Alice and Bob, two parties who want to remotely generate a shared key that is unknown to a third party observer, can do so by correlating, through radio interferometry, the noise from a radio star in the 1- to 2-Gigahertz range. We aimed to construct a demonstration system and develop the public discussion protocols required for a practical system and to demonstrate such a system's ultimate security.

During the first two years of this project, we constructed coherent radio receivers using 6-foot parabolic dish antennas; the antennas can be independently dynamically pointed at any area of the sky to follow an object of interest. The antenna signal is extracted with cylindrical waveguides coupled to preamplifiers that contribute only 0.5 decibels of noise to the expected thermal noise in the amplifiers' 50-ohm input resistance. With these antenna systems, we can obtain a signal correlation of 0.9 in a few microseconds when observing the sun; the same correlation can be obtained from Cassiopea A in 20 milliseconds of averaging.

During this year, we have made an intensive investigation of the practical and theoretical issues of implementing a cryptographic system. We had a technical breakthrough when we realized that if Bob records both phases of the noise signal, he can adjust his local oscillator phase to be coherent with Alice. This discovery greatly relaxes the receiver phase stability requirements and decreases the problems with calculating the phase delay at distinct points on the earth. We developed a communication protocol to allow Alice and Bob to extract the correlation from the noise signal. Briefly, Alice multiplies her noise signal, recorded over some period of time (such that the correlation is over 0.9), by $A = +1$ or -1 and sends it to Bob, keeping the value of A secret. Bob multiplies his signal by Alice's and then can determine A with probability of 0.9 (assuming the correlation is 0.9). Bob can set his phase, as described before, if Alice agrees to send $A = +1$. We have also investigated the efficiency of various protocols that Alice and Bob can use to correct the errors expected for correlations in the range of 0.9 to 0.99.

X-Ray Refractive Optics for Astrophysics and Nonproliferation

99029

Don Casperson

This project encompasses a theoretical and experimental investigation into refractive x-ray optics, or the use of lenses for focusing beams of x-rays. Applications include the focusing of synchrotron beams to small focal spots with high intensity and high angular-resolution imaging of astrophysical x-ray sources from satellite platforms.

The x-ray energies of interest span a few kiloelectronvolts to several tens of kiloelectronvolts, where a series of submillimeter-diameter lenses termed compound refractive lenses (CRLs) can generate a focal spot typically 1 m to 2 m distant. Refractive optics may offer an alternative to grazing-incidence reflective optics that are frequently used over this energy range but that are more difficult to manufacture and to align.

X-ray absorption in the lens material is an important design consideration. Low-atomic-number materials and thin-lens designs contribute to higher transmission efficiencies. We constructed CRLs from polystyrene and a low-atomic-number epoxy material. In this second year of the project, we made our first attempt at characterizing the focusing properties of a polystyrene CRL at the X8A beam line of the Brookhaven National Synchrotron Light Source. At this facility we installed an x-ray charge-coupled-device camera 1.2 m downstream of the CRL assembly, for diagnosing the x-ray spot size. The monochromatic nature of a CRL permits us to look at focusing properties by scanning the x-ray energy at a fixed focal length. Fig. 1 is a photomicrograph of a millimeter-diameter planoconcave parabolic lens; the CRL tested contained six of these lenses in a series. In spite of some CRL alignment problems, we found evidence of focusing as we scanned over the energy range of 5.0 to 5.7 keV. All focal spots showed narrowing relative to the unfocused beam size. The best focus occurred at 5.5 keV near the optical design program prediction. Fig. 2 plots two-dimensional histograms of focal spot intensities from 5.0 to 5.7 keV, in 0.1 keV steps.

Fig. 1. A polystyrene planoconcave lens for focusing soft x-rays. The lens is 1.6 mm in length; the parabolic portion of the lens is 0.6 mm in diameter.

Fig. 2. Two-dimensional histograms of focal-spot distributions as a function of synchrotron x-ray energy over the range of 5.0 to 5.7 keV. The narrowest distribution at 5.5 keV is near the predicted best focus in the ZEMAX optical design code. Each histogram element represents 0.024 mm of width.

Time-Resolved Photon Migration Tomography and Spectroscopy

99030

John George

We are developing a system for time-resolved photon migration tomography and spectroscopy. This system is based on the remote ultralow-light-level imaging (RULLI) detector—a novel photon counting imager developed at Los Alamos. As pulsed laser light is delivered to the surface of biological tissue, the RULLI detector measures the time history and amplitude of light that subsequently emerges from the tissue surface. We use the time-resolved data to reconstruct absorption and scattering properties of the tissue (see Fig. 1).

We are applying this advanced optical technology to biomedical problems. Time-resolved optical methods offer the prospect of tomographic imaging and localized spectroscopy that are sensitive to biochemistry and physiology. Our system can be used to characterize intracranial bleeding or stroke, to map optical changes associated with neural activation, and to explore the feasibility of optical screening procedures for mammography. Photon migration tomography and spectroscopy techniques also have value for the characterization of highly scattering media, from high explosives to liquid wastes to suspended aerosols.

This year we completed portions of the high-performance data acquisition system we have been developing. The system is intended to allow tissue images to be processed in real time. We are working toward incorporating a new

Fig. 1. Time-resolved optical tomography. (a) Fiber optics in an array over the head surface are used as sources and detectors. Time-resolved illumination and detection methods allow tomographic reconstruction. (b) A segmented MRI image is used to simulate the transport of photons through neural tissue in a realistic geometry. (c) An optical tomographic reconstruction (using simulated time-resolved optical data based on the MRI image) captures the major features of the simulated tissue.

tube into the detector itself, one sensitive in the near infrared. We also constructed a limited fiber detector and source array, which moves light from the surface of the tissue to the light sensor detector. We submitted an NIH Bioengineering Research Partnership grant application for resources to develop an MRI-compatible integrated sensor array incorporating optical tomography.

We performed charge-coupled-device direct imaging experiments in animals. These experiments allowed us to characterize optical-neurophysiological and blood-flow responses to brain activation (see Fig. 2). We imaged several physical phantoms, to characterize resolution and detection limits of time-resolved optical tomography (see Fig. 3). We are developing models of photon transport and have explored the use of existing optimization codes to reconstruct phantom data.

Publications

Barros, K.M., et al., “Virtual Pinhole Confocal Microscope,” in *Proceedings of the Inter-Institute Workshop on In Vivo Optical Imaging at the NIH* (Optical Society of America, Washington, D.C, in press).

George, J.S., et al., “Time Resolved Photon Migration Tomography with a Novel Remote Ultra Low Light Imager (RULLI),” in *Proceedings of the Inter-Institute Workshop on In Vivo Optical Imaging at the NIH* (Optical Society of America, Washington, D.C, in press).

Rector, D.M., and J.S. George, “Continuous Image and Electrophysiological Recording with Real Time Processing and Control,” in *Methods*, D. Krieger, Ed. (Academic Press, San Diego, CA, in press).

Rector, D.M., et al., “A Focusing Image Probe for Assessing Neural Activity In Vivo,” *J. Neurosci. Methods* **91**, 135 (1999).

Rector, D.M., et al., “High Speed Imaging of Scattered Light Signals that Track the Neural Electrical Response,” in *Proceedings of the Inter-Institute Workshop on In Vivo Optical Imaging at the NIH* (Optical Society of America, Washington, D.C, in press).

Rector, D.M., et al., “Rapid Evoked Optical Responses Imaged from the Rat Dorsal Brainstem In Vivo (submitted to *Neuroimage*).

Fig. 2. Video imaging of the fast optical response from rat brainstem, during stimulation of the vagus nerve. A sequence of video frames (10 ms) appears across the top; specific regions of tissue are marked A, B, and C. The graphs labeled A, B, and C show how each region responded to stimulation, recorded optically. The EVP graph shows how the tissue responded, measured with an electrode on the surface of the tissue. The optically recorded response and the electrically recorded response correspond, a phenomenon not previously demonstrated.

Fig. 3. RULLI data from a phantom, a plexiglass box containing a dense lipid suspension and a wire. The wire, positioned 2 cm behind the front surface of the box, is not visible to the eye. The graph (top) shows the time history of photon detection in response to a 50-ps laser pulse. An image of the phantom (bottom) constructed from early photons discloses the embedded wire.

Integrated Optical Biosensor

99031

Karen M. Grace

A compelling need exists for field-portable biological detection systems that are rapid, sensitive, reliable, and easy to use. The ultimate goal of this project is to develop the science and technology for an entirely new sensor systems approach for mitigating natural and man-made biological threats. In our device, we produce a molecular architecture that mimics a cell membrane surface by placing a phospholipid bilayer containing fluorescently labeled receptors on a planar optical waveguide where it is probed with evanescent field techniques. Multivalent binding of the targeted analyte produces receptor aggregation and triggers proximity-based fluorescence resonance energy transfer (FRET), providing highly selective signal transduction. The multiple cycling of the fluorescent species leads to an enormous amplification of the signal, which we can detect by measuring changes in the fluorescence emission spectrum. Successful development of this approach will offer the combined advantages of sensitivity, specificity, simplicity, and rapid response time in a compact, low-power device.

This year, we focused on increasing the sensitivity, response time, and repeatability of our sensor approach. To reduce consumption of relatively costly bioactive materials, we designed and fabricated new sensor fluid cells and sample delivery systems that allow us to decrease sample cell volumes by two orders of magnitude. In addition, this decreased sample cell volume significantly reduces diffusion time within the cell, resulting in rapid sensor response times. We have developed fluorescence imaging and analysis techniques to study and optimize critical sensor parameters including bioactive membrane uniformity and lateral mobility on different types of waveguide surfaces. We have also developed and are currently testing higher-index, sol-gel waveguide structures to increase evanescent field intensity within the bioactive membranes for greater sensor sensitivity. Using our bench top system, we have successfully demonstrated subnanomolar sensitivities to cholera toxin. Currently, we are transitioning our bench top system to a compact, low-power detection system.

Publications

Kelly, D., et al., "Integrated Optical Toxin Sensor," *SPIE Proc. of Advanced Materials and Optical Systems for Chemical and Biological Detection* 3858 (SPIE Press, Boston, MA, 1999), p. 54.

Kelly, D., et al., "Integrated Optical Biosensor for Detection of Multivalent Proteins," *Opt. Lett.* **24**, 1723 (1999).

High-Quantum-Efficiency, Silicon-Integrated, Tunable-Band-Gap Infrared-Detection Devices Based on Rhenium Molybdenum Silicide

99032

Terence E. Mitchell

Infrared sensors are used in detection and imaging systems for numerous defense applications (such as surveillance, night operations, detection of underground missile sites, etc.), as well as for industrial, medical, and astronomical applications. All currently used infrared-detector materials have major drawbacks; e.g., mercury cadmium telluride suffers from a lack of integration with silicon signal-processing circuitry, and platinum silicide-based Schottky detectors have poor quantum efficiency. Hence, there is an ongoing demand for the development of novel infrared-detector materials. We are investigating the relationship between processing, structure, and infrared response in a new class of semiconducting, rhenium disilicide-based infrared-detector materials. These infrared sensors will be silicon integrated and have higher quantum efficiency than platinum silicide. The band-gap energy of rhenium disilicide can be tuned by doping with molybdenum to match the infrared wavelength to be detected. This study is developing processing methods and provides a fundamental understanding of the defect structures and infrared response of these disilicides.

During this year's work on silicon integration, we completed a transmission electron microscopy study of a cross section of rhenium disilicide thin film grown by the traditional reactive-deposition epitaxy techniques. That study revealed a high concentration of voids at the film-substrate interface (Fig. 1). As a result, we developed a synthesis route for producing void-free interfaces using codeposition of rhenium and silicon and solid-state epitaxy. In addressing infrared response, we inferred high absorption coefficients (~ 30000 per cm at ~ 0.2 eV infrared energy) through the optical-transmission measurements we conducted on rhenium molybdenum silicide films with indirect band gaps that are typically less than ~ 0.15 eV.

Also during this year, we studied the phase equilibrium between molybdenum and rhenium disilicides and found that molybdenum can be substituted for up to about a third of the rhenium without changing the crystal structure; good epitaxy is maintained for all compositions. The band gap can thus be tailored by adjusting the rhenium-to-molybdenum ratio in the disilicide in the 8- to 12-micron wavelength range, the range in which the atmosphere transmits infrared.

In the future we will adjust processing parameters to improve the quality of epitaxy (as inferred from ion channeling and transmission electron microscopy) and correlate with the photoresponse measurements. We will perform optical transmission measurements as a function of the rhenium-to-molybdenum ratio to determine the absorption coefficients and band gaps. We will also fabricate simple heterojunction- and photoconductor-type devices and evaluate the photoresponse of those devices as a function of infrared wavelength in order to determine the quantum efficiency and cut-off wavelengths.

Publications

Misra, A., and T.E. Mitchell, "Twinning in Incommensurate and Commensurate Structures of ReSi_{2-x} Alloys," in *Advances in Twinning*, S. Ankem and C.S. Pande, Eds. (Minerals, Metals, and Materials Society, Warrendale, PA, 1999), p. 253.

Misra, A., et al., "Characterization of Epitaxial Growth of Semiconducting Rhenium 'Disilicide' Films," in *Nucleation and Growth Processes in Materials*, A. Gonis, P. Turchi, and A. Ardell, Eds. (Materials Research Society, Warrendale, PA, in press).

Misra, A., et al., "Defect Structures in Semiconducting ReSi_{2-x} Thin Films," *Microsc. Microanal.* **5**, Suppl. 2, 726 (1999).

Misra, A., et al., "Incommensuration and Other Structural Anomalies in Rhenium Disilicide," *Philos. Mag. A.*, **79**, 1411 (1999).

Mitchell, T.E., and A. Misra, "Structure and Mechanical Properties of $(\text{Mo}, \text{Re})\text{Si}_2$ Alloys," *Mater. Sci. Eng. A.* **261**, 106 (1999).

Mitchell, T.E., et al., "Unusual Incommensurate, Modulated and Disordered Structures in Refractory Metal Disilicides," in *Electron Microscopy and Analysis 1999*, Institute of Physics Conference Series Number 161, C.J. Kiely, Ed. (Institute of Physics, Bristol, England, 2000) p. 23.

Fig. 1. (a) Transmission electron microscopy image showing a cross section through a rhenium disilicide thin film on a silicon substrate with a chromium protective cap. Note the elongated void at the interface formed during the reaction between silicon and rhenium at $\sim 600^\circ\text{C}$. (b) Diffraction pattern showing the epitaxy between the silicon and silicide. The two orientations of the silicide are shown by the square and rectangle. (c) High-resolution atomic image of the silicide/silicon interface from a region with no voids. Note the epitaxy at the interface and the high density of vertical planar defects in the silicide (also visible in Figure 1a).

Electron Tunneling Spectroscopy of Buried Interfaces

99033

Ian H. Campbell

Developing a new, spatially resolved experimental spectroscopy to measure the fundamental electrical properties of an emerging class of electronic materials is a pressing need. In this project we have used scanning tunneling microscopy techniques to inject these emerging materials, which have strong electron-lattice coupling, with electrons that have a well-defined and adjustable energy. These techniques are allowing us to learn more about charge injection into and transport through the electronic states of the material.

Two examples of these materials are transition metal perovskite oxides like LaMnO_3 , which have magnetoresistive properties, and conjugated organic materials, which are becoming important for optoelectronic applications. Our poor understanding of charge injection and transport in these materials is impeding our ability to apply them technologically. Our new spectroscopy technique is building a foundation, however, for the technological development of this important emerging class of electronic and magnetic materials.

We have developed and built a derivative spectroscopy system in which the bias voltage between a scanning tunneling microscope tip and the material to be investigated is modulated at a frequency f . The current in the material is measured at frequencies f and $2f$, with phase-sensitive techniques to enhance the effective sensitivity and energy resolution of the spectroscopy.

We have initiated a study of tunneling in these materials with strong electron-lattice coupling, the results of which imply that the electron-lattice coupling can lead to significantly enhanced tunneling for electrons with energies in the energy gap of an insulator. Developing our understanding of electron-lattice coupling in these systems is essential for a science-based design strategy for electronic and magnetic devices based on these materials.

Publications

Campbell, I.H., and D.L. Smith, "Physics of Organic Electronic Devices," in *Solid State Physics*, H. Ehrenreich and F. Spaepen, Eds. (Academic Press, New York, 2000), Vol. 55, p. 1.

Kozhevnikov, M., et al., "Ordering-Induced Band Structure Effects in GaInP_2 Studied by Ballistic Electron Emission Spectroscopy," *Appl. Phys. Lett.* **75**, 1128 (1999).

Martin, R.L., et al., "Molecular and Solid State Properties of Tris-(8-hydroxyquinolate)-aluminum," *Phys. Rev. B* **61**, 15804 (2000).

Smith, D.L., et al., "Scattering Theory of Ballistic Electron Emission Microscopy at Nonepitaxial Interfaces," *Phys. Rev. B* **61**, 13914 (2000).

Yu, Z.G., et al., "Molecular Geometry Fluctuations and Field Dependent Mobility in Conjugated Polymers" (to be published in *Phys. Rev.*).

The Nonlinear Elasticity Project

2000036

Paul A. Johnson

Our primary objective is to develop, based on the nonlinear response of a damaged material, the experimental and theoretical tools necessary to measure, characterize, predict, quantify, and locate damage. Our focus is on assembly-line-manufactured materials, composites, earth materials, metals, concrete, etc. The work will be relevant to diagnosis of damage in materials, to issues in stockpile stewardship, to materials science and solid-state physics, and to the physical characterization of an aging stockpile. We will develop the means to nondestructively understand the mechanism(s) of nonlinear response. This new understanding will enable us to quantitatively correlate nonlinear response to damage; to locate damage; to apply our method to assembly-line inspection of aircraft and spacecraft delaminations and drill core concrete strength and durability; and to monitor damage to the infrastructure and in the stockpile.

We have made significant progress in developing nonlinear elastic wave spectroscopy (NEWS) and applying it to nondestructive testing of materials. We have developed a theoretical approach to locating damage and a prototype to monitor the linear and nonlinear properties of curing concrete. We have also worked on an ultrasensitive, nonlinear, nondestructive testing method for detecting damage in machined components (one that is ten times more sensitive than any existing nonlinear method and hundreds of times more sensitive than any other nondestructive testing method we are aware of). We are improving the quantitative understanding of the mechanism of nonlinear response (it is nanoscale phenomenon) that will lead us to quantitatively relating the nonlinear response to the quantity of damage.

Further, we have established that damaged materials (metals, ceramics, composites with cracks, and/or delaminations, concrete, and more) are part of a large class of materials, based on their nonlinear behavior. We believe that this is a new universality class, and we are currently looking for the scaling relation that links these materials together to form this class.

Publications

Johnson, P., "The New Wave in Acoustic Testing," *Materials World, the J. Inst. Materials* **7**, 544 (1999).

TenCate, J.N., et al., "Universal Slow Dynamics in Granular Solids," *Phys. Rev. Lett.* **85**, 1020 (2000).

Van Den Abeele, K., et al., "Nonlinear Elastic Wave Spectroscopy (NEWS) Techniques to Discern Material Damage. Part I: Nonlinear Wave Modulation Spectroscopy (NWMS)," *Research on Nondestructive Evaluation* **12**, 17 (2000).

Van Den Abeele, K., et al., "Nonlinear Elastic Wave Spectroscopy (NEWS) Techniques to Discern Material Damage. Part II: Single Mode Nonlinear Resonance Acoustic Spectroscopy," *Research on Nondestructive Evaluation* **12**, 31 (2000).

Direct Probing of Cloud Radiative Properties Using a Daytime Wide-Angle Imaging Lidar

2000037

Steven P. Love

The aim of this project is to build a daytime-capable version of our powerful new instrument, the wide-angle imaging lidar (WAIL). Using a unique Los Alamos-developed, high-speed imaging technology, WAIL produces, in effect, wide-field, high-speed “movies” of light propagation in clouds, directly measuring the clouds’ complex multiple scattering properties. Such information, for daytime clouds in particular, is of critical importance for understanding the role of clouds in the global climate. In more general terms, characterizing radiation redistribution by clouds aids DOE and Laboratory remote-sensing efforts, both active and passive, by clarifying the distorting effects of clouds on short optical pulses and aiding development of better satellite retrieval algorithms.

We have already demonstrated nighttime WAIL, using a doubled Nd:YAG laser transmitter, 60-degree field-of-view imaging optics, and interference filters to reject background light. The key to daylight operation is rejection of the much larger background. To accomplish this, we theoretically modeled, designed, and built a wide-angle Faraday magnetooptic atomic line filter based on sodium vapor. This filter produces an ultranarrow band-pass precisely coincident with the strong Fraunhofer absorption at 589 nm, where sunlight is 20 times dimmer than at other visible wavelengths. In this filter, a sodium vapor cell sits in a strong magnetic field that splits the sodium absorption lines (Zeeman splitting) and produces a 90-degree rotation of the plane of polarization only for wavelengths near the original absorption line center (Faraday rotation). Placed between crossed polarizers, this configuration produces a very narrow, angle-insensitive transmission band. Our filter design (Fig. 1) uses samarium-cobalt permanent magnets and internal optics to provide a 65-degree field of view, while limiting the range of angles within the sodium cell to 20 degrees. Fig. 2 shows its calculated transmittance. A Nd:YAG-pumped dye laser, tuned and stabilized at 589 nm, will be the transmitter for the daytime WAIL. This laser is currently under construction.

Fig. 1. Wide-angle Faraday magnetooptic sodium atomic line filter. The schematic is a cross section of the Los Alamos design, showing the sodium vapor cell at center, SmCo permanent magnets for generating the 2700-gauss magnetic field, crossed polarizers, and the 65-degree field-of-view lens system. The photo shows the assembled filter, with one of the eight SmCo magnets partially withdrawn.

Fig. 2. Predicted transmission of the Los Alamos–design atomic line filter, based on a detailed atomic physics model of sodium vapor. The central peak is 0.0034 nm wide. The effective transmission bandwidth, including the shoulder regions, is approximately 0.009 nm.

We continue to use nighttime WAIL experiments to obtain scientific data, test our theory, and refine the daylight design. Fig. 3 shows results demonstrating new optics for separately measuring the central and wide-angle portions of the scattered returns.

Fig. 3. Nighttime results, obtained August 31, 2000, from the wide-angle imaging lidar (WAIL). The frames (60 degrees across) are from two WAIL “movies,” illustrating the use of an occulting disk (bottom sequence) to emphasize the large-angle returns. The combined data sets yield improved linearity and dynamic range. Sequences proceed from the initial laser impact on the cloud through high-order multiple scattering. The vertical black bar is a shadow band used to block the near-field laser beam.

Publications

Davis, A.B., “Radiative Transfer in the Time-Domain, or What Laser Pulses and Lightning Flashes Can Tell Us about Solar Fluxes in the Cloudy Atmosphere” (10th Atmospheric Radiation Measurement Program Science Team Meeting, San Antonio, TX, March 13–17, 2000).

Davis, A.B., and A. Marshak, “Multiple Scattering in Clouds: Insights from Three-Dimensional Diffusion Theory” (accepted in *Nucl. Sci. Eng.*).

Davis, A.B., and C.A. Rohde, “Monte Carlo Ray-Tracing in Stratified Atmospheres over Complex Terrain, with Applications to Active and Passive Remote Sensing from Space” (SPIE Regional Meeting on Optoelectronics, Photonics, and Imaging, Optical Sciences Conference, Albuquerque, NM, April 10–11, 2000).

Davis, A.B., et al., “Cloud-Property Retrievals from Off-Beam/Multiple-Scattering Lidar Data Collected in Space and from the Ground,” in *Proceedings of the 20th International Conference on Light Radar*, J. Pelon, Ed. (Springer-Verlag, New York, in press).

Davis, A.B., et al., “Lite Returns from Marine Stratocumulus: An Information-Content Analysis Using Photon Diffusion Theory” (11th International Workshop on Multiple Scattering in Lidar Experiments, Williamsburg, VA, November 1–3, 2000).

Love, S.P., et al., “Remote Sensing of Cloud Liquid Water Content with Off-Beam Lidar,” in *Proceedings of 13th International Conference on Clouds and Precipitation* (Desert Research Institute, Reno, 2000), p. 349.

Love, S.P., et al., “Wide-Angle Imaging Lidar (WAIL): Progress towards a Deployable System with Full Diurnal Cycle Monitoring of Clouds from the Ground” (11th International Workshop on Multiple Scattering in Lidar Experiments, Williamsburg, VA, November 1–3, 2000).

Marshak, A., et al., “Cloud-Vegetation Interaction: Use of Normalized Difference Cloud Index for Estimation of Cloud Optical Thickness,” *Geophys. Res. Lett.* **27**, 1695 (2000).

Rohde, C.A., and A.B. Davis, “Efficient Ray-Tracing in Highly Complex Terrain under a Stratified Atmosphere, Application to Fine Laser Altimetry from Space” (11th International Workshop on Multiple Scattering in Lidar Experiments, Williamsburg, VA, November 1–3, 2000).

Cumulative On-Orbit Magnetic Pointing and Attribution of Spread Signals

2000038

Abram R. Jacobson

In this work, we explore and establish the technical basis for a radically new way of locating the sources of radio-frequency (RF) signals emitted on Earth and observed from a satellite. The approach will address diverse problems in intelligence gathering, beacon location, arms-control verification, and atmospheric electrification/storm meteorology.

Many anthropogenic signals of intelligence interest, as well as most very high frequency (VHF) signatures of lightning, occur repetitively. During such a series of signal repetitions from the same location, the LEO satellite, which has an approximately 100-minute orbital period, moves relative to the source. The RF line-of-sight at each instant in the orbit passes from the source, through the Earth's ionosphere, to the satellite. The RF signal is dispersed in the ionospheric plasma, and the dispersed signal is further split into "magneto-ionic" modes of radio propagation by plasma's anisotropic refractivity. The instantaneous frequency-splitting of the two modes (at any given time in the received waveform) is $2f_{ce} \cos\theta$, where f_{ce} is the electron-cyclotron frequency, proportional to magnetic field (2.80 MHz per gauss), and θ is the angle between the field $\mathbf{B}$ and the RF wavevector $\mathbf{k}$. This information forms the basis for cumulative inference of the source location: as the satellite receives subsequent repetitions of signal from the same source but at different orbital positions, the observable mode-splitting $2f_{ce} \cos\theta$ changes in a predictable way that depends on source and satellite locations. The latter is known, and the former can be uniquely retrieved.

This year, we succeeded in demonstrating the basic validity of this approach to geolocation. We tested the method by using several-hundred illuminations of the FORTE satellite with broadband VHF pulses from the LAPP pulser facility at Los Alamos. We were able to demonstrate geolocation accuracies of <100 km on the ground. The principal sources of uncertainty appear to be related to ionospheric raybending. We are going to see how best to correct for that phenomenon during FY2001.

Publications

Jacobson, A.R., and X.-M. Shao, "Using Geomagnetic Birefringence to Locate Sources of Impulsive, Terrestrial VHF Signals Detected by Satellites on Orbit" (submitted to *Radio Science*).

Remote Sensing of Volcanoes

2000069

Fraser Goff

The goal of this project is to analyze the data from measurements of volcanic gases collected remotely using a relatively new Fourier Transform Infrared (FTIR) device. Because volcanic plumes are reasonable surrogates for clandestine proliferators, they provide us with a means to develop remote gas measuring capabilities in the field for nonproliferation applications.

Earlier projects recorded measurements for two to three weeks at a time. Because no US volcanoes have been particularly active, we have worked overseas with in-country collaborators. Data from the FTIR has proven accurate after comparison with the conventional Correlation Spectrometer (COSPEC) that determines SO_2 concentration, and by conventional direct gas sampling and chemical analysis.

In this one year of data analysis, the most interesting result was that we quantitatively determined the concentration and flux of CO_2 (and other gases) in the volcanic plume of Popocatépetl in Mexico (see figure). We found large, short-duration bursts of CO_2 (rates up to 140,000 tons/day) that would last for 0.5 to 2 hours. We believe that much of this excess CO_2 comes from digestion of limestone (natural CaCO_3) that occurs in a 1-km-thick section of Cretaceous rocks underlying the volcano.

Publications

Goff, F., et al., "Passive Infrared Remote Sensing Evidence for Large, Intermittent CO_2 Emissions at Popocatépetl Volcano, Mexico" (to be published in *Chemical Geology*).

Love, S.P., et al., "Passive Infrared Spectroscopic Remote Sensing of Volcanic Gases: Ground-based Studies at White Island and Ruapehu, New Zealand, and Popocatépetl, Mexico," in *Remote Sensing of Active Volcanism, American Geophysical Union, Monograph 116*, 117 (2000).

Dale Counce (left) and Steve Love of Los Alamos run COSPEC and FTIR, respectively, during a small explosion of Popocatépetl volcano. COSPEC measures SO_2 concentration whereas the FTIR measures CO_2/SO_2 , HCl/SO_2 , HF/SO_2 , and SiF_4/SO_2 . When combined with windspeed and plume cross-section (from maps and laser binoculars), the discharge rates of volcanic gases are calculated.

Fundamental Underpinnings for Predictive Modeling of Complex Systems

2000072

Ronnie Mainieri

Many natural and manmade systems display complex behavior that comes from the interaction of their many components. Examples include insect societies, the cell, ecological systems, and the flow of parts in a factory. These systems are not amenable to traditional modeling techniques but can be simulated by “agent-based” models in which each individual agent in the system follows a set of simple rules. In traffic modeling, for example, each vehicle is an agent.

One of the main difficulties in dealing with agent-based models is making sense of their rich behavior. The simulations may be as complex as real life, and there is a need to develop tools and techniques to understand them. We have shown how nonequilibrium statistical mechanics and other theoretical tools can be used to understand these complex simulations. Much of the DOE’s work is concerned with predicting the behavior of large systems in extreme conditions. Traditionally these systems have been modeled by methods constructed without theoretical underpinnings, making it difficult to establish their ranges of applicability and reliability. We felt that it was necessary to initiate theoretical research in agent-based systems. In the near future this may result in expertise that is directly applicable to core problems of the Laboratory, increasing the efficiency and reliability of simulations.

This was a one-year project, but in that period, we achieved some respectable results. We proved that, when examined closely, the behavior of agents in some complex systems can be described by solutions to partial differential equations. We developed an understanding of how queuing models work and under what circumstances they fail. We found new phase transitions in epidemiology models. We added latency effects to HIV epidemic models. We found a new system of coupled ordinary differential equations that approximates the output of TRANSIMS (Transportation Analysis Simulation System), a set of forecasting procedures developed at the Laboratory to model transportation and traffic. And last, we derived new macroscopic equations from the microdynamics of agent-based models.

Publications

Klein, W., et al., “Clusters and Fluctuations at Mean-Field Critical Points and Spinodals,” *Phys. Rev. Lett.* **85** (6), 1270 (2000).

Korber, B., et al., “Timing the Ancestor of the HIV-1 Pandemic Strains,” *Science* **288** (5472), 1789 (2000).

Krapivsky, P.L., et al., “Stochastic Aggregation: Rate Equations Approach,” *J. Phys. A: Math. Gen.* **33** (31), 5465 (2000).

Materials Science

Unusual Metal Behavior in Taylor Microwires

98034

John J. Petrovic

This research was designed to develop the Taylor microwire approach and employ it for fundamental studies of both ultra-fine-scale and nonequilibrium structures in selected metal and other materials. The Taylor microwire approach is an elegantly simple, experimentally convenient technique that combines both rapid solidification and deformation. In this technique, material is melted inside a glass tube and the softened glass with the molten material core is then drawn out into a fine microwire. Key requirements are that the working temperature of the glass be higher than the melting point of the material, and that the material not be reactive with the glass.

Possible applications include high-strength/high-conductivity materials, new electronic and optical fibers, biological electrodes/sensors, and advanced sensors for enhanced surveillance of weapons systems.

We produced copper/silver microwires 10 μm in diameter by the Taylor microwire technique. Because of the rapid solidification occurring during the process, these microwires had a metastable single-phase microstructure, with an extremely small 10-nm grain size. We expect these copper/silver microwires to have an important combination of both high strength and high electrical conductivity.

We also synthesized pure silicon microwires 10 μm in diameter using this technique. This is the first time such silicon microwires have ever been produced. We made the silicon microwires by adding silicon chunks to the inside of a Vycor glass tube, then pulling the microwire at a temperature of approximately 1900°C. We fabricated a 46-cm length of continuous silicon microwire during the course of the project. No technical barriers exist for the production of significantly longer lengths. Silicon microwires may have important applications in the electronics industry.

Bulk Ferromagnetic Metallic Glasses

98035

Ricardo Schwarz

Currently, about 1% of the total electrical energy produced in this country is lost as heat dissipated by distribution transformers and motors. These losses can be substantially decreased—to roughly one third of current heat loss—by the use of more efficient transformers and motors that use ferromagnetic cores made from amorphous (glassy) or nanocrystalline alloys. The optimum implementation requires the cores be prepared from ferromagnetic laminas at least 0.3 mm thick. Existing ferromagnetic foils prepared by rapid quenching are at most 30 μm thick. Our project addressed the science needed to develop new synthesis routes for bulk ferromagnetic metallic glasses. We explored various novel techniques for the synthesis and consolidation of ferromagnetic powders.

During this last year of the project, we studied the synthesis and consolidation of soft ferromagnetic amorphous and nanocrystalline powders, both of which can have very low losses under cyclic magnetic excitation. We worked on two synthesis routes, described below.

First, we used mechanical alloying, a high-energy ball milling technique, to produce ultra-fine-microstructure, ferromagnetic, $\text{Fe}_{80}\text{Cu}_{20}$ (in at. %) powders. This powder has very low magnetic losses under cyclic excitation (see Fig. 1). Because of their fine microstructure, these powders are hard and cannot be cold-pressed into fully dense and flexible compacts, as needed for engineering applications. The powders cannot be hot-pressed because this would coarsen the microstructure and destroy the good magnetic properties. We investigated several novel cold consolidation methods, including a novel equal-channel angular extrusion technique we developed in collaboration with researchers at the Idaho National Engineering and Environmental Laboratory.

Fig. 1. Cyclic magnetization curve for mechanically alloyed $\text{Fe}_{80}\text{Cu}_{20}$ powder measured in a superconducting quantum-interference device. The saturation magnetization is 175 emu/g. The inset shows the powder has very small magnetic hysteresis, approximately 0.4 Oe.

Second, we designed and built an electro-discharging machine for preparing soft, ferromagnetic, amorphous, iron-based alloy powders. The technique is based on discharging a capacitor between vibrating crystalline rods of $\text{Fe}_{67}\text{Cr}_4\text{Mo}_4\text{Ga}_4\text{P}_{11}\text{B}_5\text{C}_5$ (in at. %) inside a dodecane bath. Sparks produced by the electrical discharge melt small amounts of material inside the dodecane. The melt droplets then solidify into spherical particles of various sizes (see Fig. 2). Because the droplets are small (less than $200\text{ }\mu\text{m}$ in diameter), they solidify quickly and have no time to crystallize. Instead, they undercool and solidify in the amorphous (glassy) state, as evidenced by their x-ray diffraction pattern (see Fig. 3). Differential-scanning

calorimetry confirmed that the powder is amorphous and showed that the crystallization temperature is about 40°C higher than the glass-transition temperature. When the powder is heated to the glass-transition temperature, it becomes soft. Because the alloy remains amorphous until the temperature is further raised to the crystallization temperature, we were able to consolidate the amorphous powder into fully dense ferromagnetic parts.

Fig. 2. Amorphous $\text{Fe}_{67}\text{Cr}_4\text{Mo}_4\text{Ga}_4\text{P}_{11}\text{B}_5\text{C}_5$ powder prepared by electro-discharge in a dodecane bath.

Fig. 3. X-ray diffraction pattern of $\text{Fe}_{67}\text{Cr}_4\text{Mo}_4\text{Ga}_4\text{P}_{11}\text{B}_5\text{C}_5$ powder prepared by electro-discharge. The broad maxima indicate that the powder is amorphous.

Unconventional Superconductivity and Violation of Time-Reversal Invariance

98036

Roman Movshovich

We have discovered that when nickel impurities are doped in high-temperature superconductor (HTS) Bi-2212, thermal conductivity displays a sharp drop at a temperature of 200 mK. We interpret this anomaly as complete opening of the superconducting gap, with a brand new symmetry of the superconducting order parameter. Such state violates time-reversal invariance, with spontaneous appearance of superconducting currents.

We have extended thermal conductivity experiments to measurements of an insulating analogue $\text{Bi}_{12}\text{Sr}_2(\text{Y}_x\text{Ca}_{1-x})\text{Cu}_2\text{O}_8$, where substitution of yttrium for calcium drives the sample from superconducting to insulating ground state. This change allowed us to show that the 200-mK anomaly is indeed of electronic origin. We also have performed additional higher temperature thermal conductivity studies on insulating $\text{Bi}_{12}\text{Sr}_2(\text{Y}_x\text{Ca}_{1-x})\text{Cu}_2\text{O}_8$, which proved the high quality of the samples compared to those investigated and reported by other researchers.

Recently, we performed preliminary thermal conductivity measurements on a pure superconducting Bi-2212 sample in a magnetic field (H) applied parallel to the CuO_2 layers responsible for high-temperature superconductivity. In this orientation, only the magnetic spin of superconducting electrons couple to magnetic field, since the magnetic vortices penetrating the sample lie between the superconducting planes and do not lead to additional supercurrent. We observed the linear dependence of the increased thermal conductivity on the magnetic field, contrary to the predicted H^2 dependence. To resolve this anomalous observation, we have acquired a precision rotator, which will be installed in a dilution refrigerator capable of achieving a temperature of 20 mK. A superconducting magnet will provide a magnetic field of up to 9 T at the rotator. The detailed study of the field dependence of thermal conductivity on the angle between the field and the CuO planes will provide additional tests of the two-dimensionality of HTS.

We used thermal conductivity techniques developed within the course of this project to study a new family of ambient pressure superconductors: heavy fermion CeIrIn_5 ($T_c = 0.4$ K) and CeCoIn_5 ($T_c = 2.3$ K). We were able to observe the predicted universal thermal conductivity limit (as $T \rightarrow 0$ K) (where thermal conductivity is independent of the amount of impurities present in the sample) in CeIrIn_5 (Fig. 1). Such behavior is only expected in unconventional superconductors with lines of nodes in the energy gap, as in two-dimensional, d-wave, high-temperature superconductors. Thermal conductivity in CeCoIn_5 displays a kink and a sharp rise as the sample becomes superconducting at $T_c = 2.3$ K (Fig. 2). This behavior closely parallels that observed in a number of HTS. It is generally attributed to the strongly reduced scattering of the electrons in the superconducting state, due to decrease in antiferromagnetic fluctuations. Observed behavior in CeCoIn_5 hints at the importance of magnetic fluctuations for unconventional superconductivity in heavy fermion compounds. In addition, we observed that thermal conductivity of CeCoIn_5 varies with temperature as T^3 at very low temperatures of $T/T_c < 0.043$. Such behavior is expected in the clean limit of unconventional superconductors with lines of nodes in the energy gap.

To confirm this picture, we performed low-temperature specific heat C measurements of both CeIrIn_5 and CeCoIn_5 . Both compounds show the presence of linear-in- T and T^2 terms in C , indicating the presence of nodes in the energy gap, in accord with thermal conductivity measurements.

Publications

Movshovich, R., et al., “Low Temperature Thermal Transport in High Temperature Superconducting $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$ via Y-doped Insulating Analogue” (submitted to *Phys. Rev. B [Rapid Communications]*).

Movshovich, R., et al., “Unconventional Superconductivity in CeIrIn_5 and CeCoIn_5 : Specific Heat and Thermal Conductivity Studies” (submitted to *Phys. Rev. Lett.*).

Fig. 1. Thermal conductivity of CeIrIn_5 . Solid line is a linear fit to the data for $T < 0.2 \text{ K} = T_c/2$. Dotted line is an upper limit estimate for the phonon thermal conductivity.

Fig. 2. Thermal conductivity of CeCoIn_5 . Solid line is a power law fit for $T < 100 \text{ mK} < T_c/20$. Dotted line is an upper limit estimate of phonon thermal conductivity. Dashed line is electronic thermal conductivity for $T > T_c$. Inset: thermal conductivity over temperature vs T^2 for $T < 0.1 \text{ K}$.

New Vortex Phases in Irradiated High-Temperature Superconductors

98037

L.N. Boulaevskii

This project investigated the appearance of quantized vortices when nanometer-sized amorphous columnar structures are introduced into anisotropic high-temperature superconductors by irradiation with energetic heavy ions. Vortex structure and dynamics affect losses in the superconducting state, so this research was important for all high-temperature superconductor applications.

We calculated the magnetic field dependence of plasma-resonance frequency in pristine and irradiated $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$ (Bi-2212) crystals near the critical temperature for the superconducting transition, T_c . At low magnetic fields, we found that the linear in-field plasma frequency corrections are related to the average distance between pancake-shaped vortices (meandering length) in neighboring layers. Near T_c , average meandering length approaches the London penetration depth. We also found evidence of the existence of the line liquid phase at low fields. Specifically, in a small melting field, the meandering length does not change much at the melting transition. Finally, we found that the pinning effect of columnar defects affects the field dependence of the plasma resonance frequency weakly near T_c .

For magnetic fields parallel to the c-axis ($\mathbf{H} \parallel \mathbf{c}$), the effect of vortices on quasiparticle conductivity (σ_0) is accounted for by a semiclassical (Doppler shift) approach. When pancake vortices are weakly correlated in adjacent layers (as in the Bi-2212 superconductor above 0.05 T), σ_0 increases sharply with H at low temperatures and then reaches an extended region of slow linear growth.

In Bi-2212 the c-axis resistivity, $\rho_c(H)$, was measured in quasistatic magnetic fields up to 60 T. We found that at high fields (a) quasiparticle tunneling conductivity increases linearly with the field, and (b) $\rho_c(T)$ tends to saturate to nonzero value as T tends to zero. Both features are consistent with the model of a d-wave superconductor with coherent interlayer tunneling.

From measurements of the c-axis I-V characteristics of intrinsic Josephson junctions in Bi-2212 mesas, we obtained the field dependence ($\mathbf{H} \parallel \mathbf{c}$) of the quasiparticle (QP) conductivity. The observed dependence is explained by the dual effect of supercurrents around vortices: they enhance the QP density of states, leading to an increase of

conductivity at low H , and they enhance the scattering rate for coherent tunneling as pancakes become disordered along the c-axis at higher H , leading to a plateau at moderate H .

We calculated the field dependence of the critical current and Josephson plasma resonance (JPR) frequency in a macroscopically uniform vortex glass phase in highly anisotropic layered superconductors. Results are in agreement with experimental data for JPR frequency measured in Bi-2212 superconductor in the field cooling regime in fields below 1 T.

Publications

Bulaevskii, L.N., et al., "Critical Current and Josephson Plasma Resonance in the Vortex Glass Phase of $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$ " (accepted in *Phys. Rev. B*).

Koshelev, A.E., and L.N. Bulaevskii, "Josephson Coupling and Plasma Resonance in Vortex Crystal," *Physica C* **341-348**, 1503 (2000).

Koshelev, A.E., et al., "Josephson Coupling, Phase Correlations, and Josephson Plasma Resonance in Vortex Liquid," *Phys. Rev. B* **62**, 14403 (2000).

Latyshev, Yu.I., et al., "Interlayer Tunneling of Quasiparticles and Cooper Pairs in Bi-2212 Single Crystal Whiskers," *Physica C* **341-348**, 1499 (2000).

Morozov, N., et al., "C-axis Tunneling in $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$ in the Magnetic Field Up to 60 T," *Physica C* **341-348**, 1511 (2000).

Morozov, N., et al., "High-Field Quasiparticle Tunneling in $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$: Negative Magnetoresistance in the Superconducting State," *Phys. Rev. Lett.* **84**, 1784 (2000).

Morozov, N., et al., "Quasiparticle and Cooper Pair Tunneling in the Vortex State of $\text{Bi}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$," *Phys. Rev. B* **62**, R14681 (2000).

Thorsmølle, V.K., et al., "C-axis Josephson Plasma Resonance Observed in $\text{Ti}_2\text{Sr}_2\text{CaCu}_2\text{O}_8$ Superconducting Thin Films Using Terahertz Time-Domain Spectroscopy" (submitted to *Optics Letters*).

Vekhter, I.B., et al., "Interlayer Quasiparticle Transport in the Vortex State of Josephson Coupled Superconductors," *Phys. Rev. Lett.* **84**, 1296 (2000).

Novel Approaches to Low-Temperature Thin-Film Materials Chemistry: Kinetic Energy Activated Molecular Beam Epitaxy

99040

Mark Hoffbauer

Our project uses energetic atomic species to grow and process thin-film materials. This is an innovative technology that will be critical for developing new materials with improved properties, particularly at the nanoscale.

We use reactive atoms with high kinetic energies (a few electron volts) to activate thin-film growth at much lower temperatures than possible with other techniques. Our goal is to grow very high quality nitride and oxide thin films, develop new thin-film processing techniques, and produce prototype electronic and/or optical devices. The results of this project are important to the Laboratory and DOE for the development of smaller and faster computers, enhanced optical communications devices, improved sensors, and high-performance microelectronics.

Kinetic Energy Activated Molecular Beam Epitaxy (KEAMBE) is depicted schematically in Fig. 1. To date, we have concentrated on directly exposing substrates maintained at low temperatures to energetic atoms to form oxide or nitride films. We have had considerable success in growing device-quality gate oxides on silicon, novel oxides on gallium arsenide and germanium substrates, and nitride films on a wide variety of substrates, and in passivating CdZnTe radiation detector surfaces. We have made major improvements in our energetic atom source and how we handle samples, and we are installing new deposition sources to further broaden our capabilities.

Our emphasis is on growing oxide and nitride films using co-deposition—a metal is evaporated onto a substrate that is simultaneously exposed to either energetic nitrogen or oxygen atoms (Fig. 1, left). We optimize growth conditions to produce stoichiometric films with good crystallinity, uniformity, and purity by varying substrate temperature, incident atom energy, and flux. We then examine thin-film physical properties, surface and interface reactivity, nucleation, and diffusion using a variety of interfacial probes and characterization techniques.

We are pursuing the growth of aluminum, gallium, and indium nitride films, with emphasis on exploring selected area growth of nitride and oxide films and their applications in the emerging nanoscale device arena. We are investigating the etching of polymers (Fig. 1, right) with sub-100-nm features and very high aspect ratios. Film growth and polymer etching are critical for the fabrication of nanoscale devices. Overall, our goal is to understand the scientific basis for KEAMBE while simultaneously producing device-quality thin-film materials.

Fig. 1. In KEAMBE, a substrate is exposed to an energetic atom beam. (Left) A thin film is created when energetic atoms either react directly with the substrate, or in co-deposition, react with a metal being evaporated onto the substrate, producing a nitride or oxide metal compound. Materials can also be grown in selected areas or etched away with KEAMBE by using a suitably chosen mask. (Right) For example, a polymer layer and patterned mask can be laid down on the substrate. When the collimated atoms impinge upon unmasked areas of the polymer layer, material is removed, leaving only those areas of the polymer layer protected by the mask.

Bulk Rapid Solidification

99041

Dan J. Thoma

Directed light fabrication (DLF) is a one-step process in which we fuse gas-delivered metal powders in the focal zone of a laser beam in order to produce fully dense, near-net-shaped, three-dimensional (3-D) metal components from a computer-generated solid model. Because we can control and vary the lasers' power distributions, we have been able to process a variety of materials ranging from aluminum alloys to tungsten, including intermetallics such as Mo_5Si_3 and NiAl . The features of the resulting microstructures are significantly more refined than those generated by any other conventional solidification process. Theoretically and experimentally, secondary dendrite arm spacing indicates the cooling rate during solidification. From this information, we have preliminary indications that the cooling rates are in the regime classified as rapid solidification ($>10^4$ K/s). Our purpose in this project is (1) to experimentally and theoretically define the solidification behavior, and (2) to realize the unique advantages associated with rapidly solidified bulk product. In short, we hope to materialize the "Holy Grail" of a 30-year international research effort.

A substantial funding level decrease following the cut in the LDRD program adversely affected our progress this year and caused us to lose the postdoctoral researcher working on our project. Nonetheless, we made significant advances in three areas. We extended last year's progress in the development of iron-based materials having strengths greater than wrought product. After conducting detailed microstructure investigations, we were able to attribute the great strength of the as-processed material to a high proportion of dislocation networks in the material (see Figs. 1 and 2). During deposition, the residual stresses were apparently past yield, offering a new processing route to form in situ strengthening mechanisms. In fact, this fabrication route produces stronger and more ductile steels than does any other method. This has direct potential implications for certain aspects of the nuclear weapons program.

In addition, we have made substantial progress in making new iron-based amorphous alloys produced by melt-spinning and direct-casting bulk amorphous magnesium alloys.

Publications

Hawley, M.E., et al., "Magnetic Force Microscopy Study of New Nanocrystalline Soft Magnetic Ribbons," *Mat. Res. Soc. Symp. Proc.*, **577** 531 (1999).

Stalder, M., et al., "Retransformation ($\alpha \rightarrow \gamma$) Kinetics of Strain-Induced Martensite in 304 Stainless Steel," *Mater. Sci. Eng. A*, **280** (2), 270 (2000).

Fig. 1. Transmission electron microscope image of an as-deposited, iron-based alloy. The structure displays a high proportion of dislocation networks, illustrating why the strength of the alloy is so high.

**Fe-25Ni D.J. F Tensile Specimen
Gage Section
312993-1**

1μm

Fig. 2. Transmission electron microscope image of an as-deposited iron-based alloy that has been mechanically tested under tension. Again, the high-dislocation-density network elucidates why the material is as strong as wrought alloys.

Intrinsic Local Modes in Low-Dimensional Materials

99042

Andrew P. Shreve

Localization of vibrational energy to form intrinsically localized modes (ILMs) has long intrigued scientists in fields ranging from biology to condensed matter physics because of its deep implications for energy focusing and transduction, nucleation, transport processes, and local reactivity in many general classes of materials, including biological, electronic, and energetic. However, poor understanding about how to create and study ILMs experimentally has largely stalled progress in this field. This project is aimed at developing and using optical spectroscopic techniques for this purpose. This work requires strong collaboration between experiment and theory. Fully nonlinear and nonadiabatic models are necessary to interpret results and guide new experimental design, while conversely, experimental results, including measurements of dynamics, are needed to benchmark further model development.

Our initial focus has been on mixed-valence materials, which allow for chemically tunable control of nonlinearities. This year, we synthesized a series of defect-free materials with nonlinearities ranging from very strong to very weak. With steady-state Raman spectroscopy, we characterized the appearance of intrinsic localization phenomena in the very strongly nonlinear materials and the transition into delocalized states in the weakly nonlinear materials. We also measured and modeled Raman excitation profiles in both strongly and weakly nonlinear materials. We used advanced numerical diagonalization techniques (Jacobi-Davidson algorithm) to study ground states and ILMs in fully quantum-mechanical linear chains with up to 12 sites, including electron-electron interactions and infrared and Raman phonon modes in a Peierls-Hubbard model. Our calculation of Raman overtone shifts was in good agreement with the experiment. In addition, we have calculated the optical response caused by ILMs, demonstrating multi-time scale features resulting from internal “shape” oscillations of coupled electronic-lattice degrees-of-freedom.

Based on these results, we plan to extend our studies into other important classes of materials in the remainder of the project, as well as to compare intrinsic localization phenomena with extrinsic localization introduced by the presence of defects.

Publications

Buschmann, W.E., et al., “Synthetic Control of Defect Content in $[\text{Pt}(\text{en})_2\text{Cl}_2][\text{Pt}(\text{en})_2](\text{ClO}_4)_4$ ” (submitted to *J. Am. Chem. Soc.*).

Buschmann, W.E., et al., “Synthetic Control of Defect Content in $[\text{Pt}(\text{en})_2\text{Cl}_2][\text{Pt}(\text{en})_2](\text{ClO}_4)_4$,” *Abs. Papers Am. Chem. Soc.* **219(1)**, 57-INOR (2000).

Dexheimer, S.L., et al., “Femtosecond Vibrational Dynamics of Self-Trapping in a Quasi-One-Dimensional System,” *Phys. Rev. Lett.* **84**, 4425 (2000).

Fehske, H. et al., “Local Mode Behavior in Quasi-1D CDW Systems,” *Physica B* **281**, 673 (2000).

Kladko, K., et al., “Intrinsic Localized Modes in the Charge-Transfer Solid PtCl ,” *J. Phys. Condensed Matter* **11**, L415 (1999).

Organic Electronic Materials under Intense Electrical Injection

99043

Darryl L. Smith

Our objective in this project is to understand the properties of organic electronic materials under intense electrical injection, using a tightly coupled synthesis-characterization-modeling approach. An extremely interesting new physics arises in these materials under such conditions; numerous charge carriers are present, and the interaction between the resulting carriers leads to changes in the energetics, dynamics, optical response, and transport properties of the injected excitations.

Organic electronic materials are becoming interesting from both a scientific and a technological point of view. Light-emitting diodes, an important application of organic electronic materials, are entering production, and organic electrical injection lasers have just been demonstrated. Understanding the fundamental physics of intense electrical injection in organic electronic materials is essential to the development of these new devices.

We are investigating two principal classes of structures: vertical injection and multilayer charge accumulation. Vertical injection structures consist of one or more layers of conjugated organic materials with electrically injecting metal contacts on each side. Multilayer charge accumulation structures consist of a conjugated organic material film with a metal contact on one side and an insulator on the other. To date these structures have been used to (1) determine the influence of the high-excitation density that is injected into an organic electronic material on the optical response of the material and (2) study the injection process at the metal/organic interface at high-voltage bias, where the injected current density is large. These results are important for designing organic light-emitting diodes that would be useful for displays and solid-state lighting.

Publications

Crone, B.K., et al., "Device Model Investigation of Bilayer Organic Light-Emitting Diodes," *J. Appl. Phys.* **87**, 1974 (2000).

Yu, Z.G., et al., "Molecular Geometry Fluctuation Model for the Mobility of Conjugated Polymers," *Phys. Rev. Lett.* **84**, 721 (2000).

Investigation of Experimental Defect Interactions in Materials by Integrating Experimental Techniques with Large-Scale Simulations

99044

Peter Lomdahl

This project experimentally and theoretically investigates the detailed physics of dislocation interactions in face-centered cubic (FCC) materials. We use large-scale molecular dynamics simulations and high-resolution transmission electron microscopy (TEM) techniques to reveal details of dislocation interactions. Our goal, which is directly relevant to the Laboratory's materials science core competency, is to apply these techniques in an integrated, coherent fashion so that we can better understand the basic processes of materials deformation.

To experimentally determine the optimum geometry for in situ deformation in the transmission electron microscope, we have tested three types of films: (1) conventionally electropolished specimens prepared from bulk copper, (2) evaporated thin films prepared by ion sputtering onto rock salt, and (3) nanocrystalline films prepared by inert gas condensation. Each type of film has advantages and disadvantages, but with all types there is dislocation motion and intersection (see Fig. 1).

When we used electropolished specimens, we could control dislocation motion well. However, because of the varying thickness of each specimen, the dislocation often concentrated in areas away from the observed area. In using evaporated thin films, we have found that we can produce films >200 nm that yield fairly robust in-situ test specimens. However, to achieve good image quality under weak-beam conditions, we must use samples that are thinner than ~100 nm. Because pure copper films thicken under island growth conditions, the resulting samples are not continuous and tend to tear. The nanocrystalline thin films are suitably thin and continuous, but dislocation activity occurs in the larger grains (~250 nm in diameter), and the grains overlap. In addition, the grain boundaries are porous, and intergranular fracture occurs. Accordingly, we have concentrated on the first two types of specimens.

We have used large-scale molecular dynamics simulations to study defect interactions in FCC materials. In a series of simulations, we have shown how shock-induced dislocation patterns can account for the macroscopic plastic deformation of FCC materials. We have a good understanding of the dependence of these dislocation patterns as a function of crystal orientation and shock strength. We will perform further large-scale molecular dynamics simulations on copper to investigate the sensitivity of grain boundaries on dislocation patterns. We have initiated preliminary studies of the x-ray signatures of these patterns in collaboration with an experimental group at the University of Oxford in England.

Publications

Germann, T.C., et al., "Orientation Dependence in Molecular Dynamics Simulations of Shocked Single Crystals," *Phys. Rev. Lett.*, **84**, 5351 (2000).

Fig. 1. TEM micrograph of a dislocation intersection in copper.

Synthesis and Characterization of Superhard Materials

2000039

Yusheng Zhao

To discover materials harder than diamonds has long been a dream of mankind. Novel superhard materials now exist. Manmade diamonds and cubic boron nitride have been successfully synthesized, and computations from the first-principles theory can aid in the design of other new superhard materials.

The intrinsically strong and short covalent bonds of the light elements can form very tight, three-dimensional networks with extreme resistance to external forces—“superhard” materials. In addition to their extreme hardness, these materials possess other unique properties such as high thermal conductivity, intrinsic abrasive strength, a high degree of chemical inertness, and wide energy-band gaps. These properties make superhard materials highly desirable in industrial applications—for example, as superabrasives for tooling and as heat sinks for semiconductors.

Our goal is to synthesize superhard materials using high-pressure technology. We will then conduct a comprehensive study of these synthesized materials, characterizing a wide range of their properties and modeling them. The success of this study will have important implications for materials science, condensed-matter physics, and geological science.

We have used a Paris-Edinburgh cell to reach pressures of 10 GPa and temperatures of 1500 K. A new press, TAP-98, and sintered diamond anvils will allow us to push the pressure-temperature range up to 30 GPa and 2000 K.

We have improved pressure-temperature synthesis conditions by introducing a metallic reinforcement ring to the ceramic gasket. We are able to adjust pressure efficiency, maintain the sample shape, and, at the same time, retain the electric/thermal insulation. The new arrangement of the thermal couple, which goes through the back of the toroidal anvil with an easily removed metallic cone, guarantees successful temperature measurement. We have prepared samples with the B-C-N-O system and have selected a $\text{B}_2\text{O}_3 + 4\text{B} = \text{B}_2\text{O}$ mixture as our starting material. We have applied a ball-milling technique to increase the chance that the material will bond. Our initial x-ray diffraction data show that diffraction patterns of the starting material have been altered by the ball-milling process.

We also performed our first computer simulation on the bulk modulus of the B-O system. Using the *ab initio* pseudopotential electronic structure method and density-functional theory, we have performed extensive calculations on the bonding properties of a series of boron oxides: B_2O_3 , BO, B_2O , B_3O , and B_6O . We calculated the equilibrium lattice constant, atomic position, bulk modulus, and cohesive energy of each boron oxide. We have verified the controversial structure of B_2O and proposed possible stable structures for BO and B_3O .

One of our interesting findings is that the bulk modulus, thus the hardness, of boron oxides (B_xO) increases with the boron concentration, i.e., increases with x (see Fig. 1). This trend does not depend on the strength of the individual interatomic chemical bonds but mainly on the rigidity of the different bonding networks that build the crystal.

Publications

Xie, J., et al., “First-Principles Study of Bonding Properties of Boron Oxides” (submitted to *Phys. Rev. B*).

Fig. 1. Variation of the bulk modulus of boron oxides plotted as a function of boron concentration. The bulk modulus, and so the hardness, of boron oxides increases with the boron concentration. [The bulk modulus of B_2O_3 is the average value of $B_2O_3(I)$ and $B_2O_3(II)$, whose individual values are shown with triangles. The bulk modulus of B_{12} is shown for comparison.]

From Artificial Atoms to Artificial Solids: Soft-Matter Nanotechnology

2000040

Victor Klimov

Our goal is to develop and study novel classes of tunable materials built from semiconductor nanoparticles known also as colloidal quantum dots (QDs). In QDs, the bulk band structure collapses into discrete atomic-like levels; therefore, QDs are often viewed as artificial “tunable” atoms with electronic energies that are controlled by dimensions. Colloidal QDs can be chemically manipulated like large molecules and, in particular, can be assembled into ordered and disordered arrays (QD solids). QD solids possess great technological potential, associated with the tunability of their properties through combined control of energy structures in the individual nanoparticles and of the particles’ collective interactions in the solid.

This project focuses on development of semiconductor QD solids with properties that are optimized for light-emitting and nonlinear optical applications. Such solids are of interest in several DOE program areas, including energy and renewable energy, basic energy science, and nonproliferation and national security, and are directly related to the Laboratory’s capabilities in nuclear and advanced materials.

During this first year, we developed procedures for building close-packed arrays of nanoparticles and have applied these procedures to fabricating solid-state films of CdSe QDs. These films were characterized using optical and electron microscopy and linear and nonlinear optical spectroscopic techniques. The films showed optical gain at the position of the emitting transitions, and this gain developed at pump levels between one and three electron-hole pairs per dot. The gain band was spectrally tunable by changing the dot size, as expected from quantum confinement effects (see Fig. 1).

The optical gain decayed with picosecond time constants that exhibited strong dependence on QD sizes. The observed time scales were consistent with carrier recombination dominated by nonradiative Auger effects that “turned on” when two or more electron-hole pairs per dot were excited. Despite highly efficient Auger recombination, the optical gain was high enough to allow development of stimulated emission that was observed in photoluminescence spectra as a sharp peak with a clear gain threshold (see Fig. 2). The emission color was tunable by tuning the size of the dots used to fabricate the solids [compare Figs. 2(a) and (b)]. Our results unambiguously demonstrate the feasibility of optical amplifiers and lasers based on colloidal nanoparticles.

Publications

Jacoby, M., “Quantum Dot Lasers Coming Soon,” *Chem. Engineering News* **78** (43), 78 (2000).

Klimov, V.I., “Optical Nonlinearities and Ultrafast Carrier Dynamics in Semiconductor Nanocrystals,” *J. Phys. Chem. B* **104**, 6112 (2000).

Klimov, V.I., et al., “Optical Gain and Stimulated Emission in Nanocrystal Quantum Dots,” *Science* **290**, 314 (2000).

Klimov, V.I., et al., “Quantization of Multiparticle Auger Rates in Semiconductor Quantum Dots,” *Science* **287**, 1011 (2000).

Fig.1. Tunable gain spectra of three films fabricated from CdSe QDs with radii of 1.3, 1.7, and 2.1 nm.

Fig. 2. Development of a sharp stimulated emission band as a function of pump intensity in the photoluminescence spectra of films fabricated from CdSe QDs with radii of 2.1 nm (a) and 1.35 nm (b). Insets: Superlinear intensity dependence of the stimulated emission (circles) showing a clear threshold compared with the sublinear dependence of the photoluminescence intensity outside the sharp stimulated emission peak (squares).

Direct Observations of Individual Relaxation Modes in Polymers

2000041

William Patrick Ambrose

The scientific objective of this work is to observe the low-frequency responses of individual relaxation modes in optically transparent amorphous systems. We are separately observing individual subchain and whole-chain responses to electric fields and mechanical stress for the same individual polymer chains. By removing the masking effects of ensemble averaging, we are testing whether individual relaxation modes have physical equivalence with respect to electric fields and mechanical stress. Understanding and predicting the complex flow and aging behavior of polymers is important in industry (for example in the extrusion molding of structural components) and for defense applications, such as understanding the aging of binders in explosives. Any insight that we can gain into the microscopic structural behavior of polymer systems will be beneficial. The results may be useful for guiding the refinement of constitutive models and hydrocodes used in modeling explosives components.

We built an apparatus for wide-field imaging the positions and emission polarizations of individual fluorescent molecules. To test the apparatus' ability to detect single fluorescent molecules, we demonstrated position imaging and polarization analysis of the emission from individual Rhodamine 6G molecules on a transparent surface. To observe motion, we collected sequences of polarization-split images (movies) of individual fluorescent dye molecules deposited on silica. We developed computer programs to analyze sequences of polarization-split images to extract the orientations of individual dipole (single-molecule) emitters. We observed individual molecules occasionally undergoing orientation fluctuations under low-humidity conditions and exhibiting increased reorientation and diffusional translation under high-humidity conditions.

We are preparing a manuscript showing that we are able to follow the motion of single fluorescent molecules and obtain information on the local dynamics of the condensed matter (in this case, water) surrounding the probe molecule. Recently, we prepared polymer samples [poly(methyl methacrylate)] with low concentrations of fluorescent impurity molecules, and we have imaged these with wide-field polarization-split imaging at the single-molecule level.

Time-Resolved Study of Martensitic Phase Transformations

2000042

Dan J. Thoma

In this project, we are developing a new experimental method—the application of laser-based materials measurements (such as transient x-ray diffraction) to a problem of fundamental scientific interest: martensitic transformations in solids. We developed a new technique before this project started. We wanted to apply this new technique, which has extraordinary resolution, to study a problem on a timescale that has never before been achieved. Martensite reactions are a type of solid-state phase transformation that occurs as the result of a shear distortion of a crystal lattice. Our research addresses a fundamental and unresolved question in materials science: What are the nucleation mechanisms and kinetics in the martensitic (displacive) transformation? We will use the Los Alamos Trident laser to produce ultrafast tensile pulses with laser-generated shocks in order to probe the material on a time-and-stress scale not heretofore accessible by other experimental methods. Many nuclear weapons materials incorporate martensitic structures. Uranium alloys, plutonium alloys, and steels all exist with martensitic structures, whose formation dictates the properties, performance, and aging of the metals. The increased understanding resulting from this project will benefit work in stockpile stewardship, advanced characterization of materials, and complex experimentation and measurement.

In the first year of the project, we initiated activities on a shape memory alloy, NiTi. We used various compositions with different phase-transformation start temperatures. First, we conducted thermal analysis and microstructural investigations to characterize the material. Next, we investigated the elastic properties. Finally, we used the Trident laser to shock load the five compositions of samples under various loading conditions. We are focusing current activities on postmortem investigations of the transformed microstructures. Overall, our progress has been steady and enlightening, with no major setbacks in our timetables. We have even had the opportunity to investigate a new type of martensitic reaction, and we have almost finalized the results. A workshop that we held on martensitic reactions generated outstanding ideas, and remnants of new topical areas will be the focus of future studies.

We performed some background work on AuZn, which we are planning to pulse load next year. The results on this alloy were extraordinary. This background work was a major achievement.

Publications

Darling, T.W., et al., “Elastic and Thermodynamic Properties of the Shape-Memory Alloy AuZn” (submitted to *Phys. Rev. Lett.*).

In Situ Characterization and Failure Prediction of Composites

2000043

Irene J. Beyerlein

The goal of our project is to develop realistic and reliable failure simulations of composite materials. Our research integrates up-to-date neutron and x-ray diffraction techniques with micromechanical modeling. We are supporting the Laboratory's mission by combining computational modeling and materials characterization, which is carried out at Los Alamos Neutron Science Center (LANSCE) and other DOE facilities.

In this first of year of the project, we worked on designing and fabricating composite specimens that are (1) suitable for mechanical testing during x-ray and neutron diffraction measurements and (2) consistent with the geometry and shape of the specimens represented in our current micromechanical models—allowing us to test our models. We also designed the geometry of the specimens to correspond to the limitations and requirements of each diffraction technique.

We overcame numerous obstacles before identifying the most suitable aluminum alloy (A356) and fixing the processing conditions for an alumina fiber/aluminum matrix. Time devoted at this stage was worthwhile because comparing the results from neutron diffraction and x-ray diffraction enabled us to exploit advantages unique to each diffraction technique. In turn, improved measurements will help us validate and refine our models of the mechanical behavior of fiber composites.

Once the neutron beam at LANCE was operating, we were able to perform neutron-diffraction residual strain and mechanical loading experiments on single alumina fiber/aluminum matrix specimens, both pristine and prenotched. We are currently analyzing the data we gathered and identifying the appropriate model to apply.

We will conduct future neutron diffraction experiments using the new spectrometer for materials research at temperature and stress (SMARTS) instrument, which will provide much better spatial and temporal resolution than was previously available. We also plan to use x-ray or neutron radiography to effectively find the notches and voids in the specimens.

We also initiated x-ray diffraction studies at synchrotron radiation facilities on Ti-SiC multifiber composites, made by 3M. These composites are consistent in geometry and material response with the micromechanical models we have developed. We collected x-ray diffraction data on Ti-SiC residual strain at Los Alamos, and at the National Synchrotron Light Source at Brookhaven National Laboratory and the Argonne Photo Source at Argonne National Laboratory. The techniques we used provided superb spatial resolution ($\sim 2 \mu\text{m}$) for strain data, which will allow us to check our micromechanical models. We are currently analyzing the data sets we collected.

Publications

Hanan, J.C., et al., "In Situ Characterization of Matrix Response to Fiber Fractures" (Tenth Annual International Conference on Fracture, Honolulu, HI, December 2001).

Hanan, J.C., et al., "Residual Strains in a Ti-SiC Composite," *Adv. X-Ray Anal.* **44** (2000).

Modeling Complex Processes in Hard and Soft Materials

2000055

Gerardo Ortiz

Our goal is to understand the organizing principles behind complex behavior in matter. These principles stand at a frontier of the science of materials—a frontier that explicitly recognizes the role of intrinsic nonlinearity and feedback in producing large-scale sensitivities to small perturbations. Understanding, controlling, and utilizing these features requires research on the complex, multiscale structure and dynamics resulting from competing interactions and from coupled spin, charge, and lattice degrees-of-freedom. These features pave the road to qualitatively new science and new materials at the Laboratory.

We developed a microscopic model that captures the magnetic and superconducting properties of high- T_c cuprate materials. In particular, we showed that appropriate inhomogeneous interactions that break magnetic symmetries are essential to induce substantial pair-binding of holes. Moreover, building upon the phenomenology of our microscopic model, we developed a mean-field (“Josephson spaghetti”) model that provides a scenario for the macroscopic superconductivity (see Fig. 1). Our model will further our understanding of why anisotropies are relevant to substantial pair-hole binding and whether the stripes themselves have important superconducting fluctuations.

The simplest representation of a stripe is realized by a t - J_z chain model. We have analytically determined the exact quantum phase diagram of this model and its generalizations to any spin and sign of the magnetic exchange interaction and particle statistics. We have also developed a new spin-particle mapping, for arbitrary spin S generating the $SU(2)$ group algebra, that constitutes a natural generalization of the Jordan-Wigner transformation for $S = 1/2$. This last problem remained open for 72 years.

Finally, we have presented a minimal model of a doped Mott insulator that simultaneously supports antiferromagnetic stripes and d -wave superconductivity. At the unrestricted mean-field level, the various phases of the cuprates, including weak and strong pseudogap phases, and two different types of superconductivity in the underdoped and the overdoped regimes, find a natural interpretation. We argue that on the underdoped side, the superconductor is intrinsically inhomogeneous—striped coexistence of superconductivity and magnetism—and global phase

coherence is achieved through Josephson-like coupling of the superconducting stripes. On the overdoped side, the state is homogeneous overall and the superconductivity is of the classical Bardeen-Cooper-Schrieffer type (see Fig. 2).

Publications

Batista, C.D., and G. Ortiz, “Generalized Jordan-Wigner Transformations,” *Phys. Rev. Lett.* **86**, 1082 (2001).

Batista, C.D., and G. Ortiz, “Quantum Phase Diagram of the t - J_z Chain Model,” *Phys. Rev. Lett.* **85**, 4755 (2000).

Batista, C.D., et al., “Common Magnetic Origin of the Resonance Peak and Incommensuration in High T_c Superconductors” (submitted to *Phys. Rev. Lett.*).

Eroles, J., et al., “Pairing in Inhomogeneous Superconductors,” in *Recent Progress in Many-Body Theories* (World Scientific, Singapore, 2000), p. 327.

Eroles, J., et al., “Inhomogeneity-Induced Superconductivity?,” *Europhys. Lett.* **50**, 540 (2000).

Eroles, J., et al., “Microscopic Scenario for Striped Superconductors,” in *Physica C* (in press).

Eroles, J., et al., “Photoemission Spectroscopy of Cuprates from Inhomogeneous Models” (submitted to *Phys. Rev. Lett.*).

Martin, I., et al., “A Minimal Model of Striped Superconductors” (submitted to *Nature*).

Martin, I., et al., “Competing Quantum Orderings in Cuprate Superconductors: A Minimal Model,” in *International Symposium on Physics in Local Lattice Distortions* (AIP Conf. Proc., 2000).

Martin, I., et al., “Competing Quantum Orderings in Cuprate Superconductors: A Minimal Model,” *Int. J. of Modern Phys. B* **14**, 3567 (2000).

Martin, I., et al., “The Physics of Inhomogeneous Striped Superconductors,” in *J. Magn. Magn. Mater.* (in press).

Ortiz, G., and A.A. Aligia, “How Localized is an Extended Quantum System?” *Phys. Status Solidi* **220**, 737 (2000).

Fig. 1. Schematic representation of the superconducting ground state. Antiferromagnetic (AF) zones between stripe segments are colored in blue. Red spins near the stripes represent easy-axis Ising-like links. Gray ellipses characterizes the bound pairs (holes in red).

Fig. 2. Schematic phase diagram obtained by superimposing the AF/stripped (ICAF) and the d -wave superconducting (SC) phase diagrams. In the intersection region we distinguish the subregions of Josephson-coupled striped superconductor (SSC), and nonsuperconducting “strange metal” (SM), which is neither a superconductor nor a simple insulator.

Complex Behavior in Novel Correlated Electron Materials

2000057

Alexander Balatsky

We are studying fundamental issues of superconductivity in novel correlated electron materials using a coordinated measurement and theoretical approach. The discovery of new materials and the large number of unanswered fundamental physics questions drive the science of novel correlated electron materials. A new family of tetragonal derivatives of CeIn_3 (e.g., CeCoIn_5 , CeIrIn_5 , et al.) has been synthesized that promises to substantially modify our understanding of the interaction of magnetism and superconductivity in heavy Fermions. These materials, like the cuprates, can exhibit unconventional superconductivity with broken symmetries in addition to broken gauge symmetry, leading to quite unusual behavior of the thermodynamic and transport properties. For example, when magnetic insulator cuprates are doped, the added charges lead to spatially modulated structure called “stripes.” A greater understanding of such phenomena will support the Laboratory’s program in superconductivity and our core competency in materials science.

We studied the effect of local charge/spin correlations or stripes on superconductivity and normal state properties of the cuprates with nuclear magnetic resonance (NMR). We have found a strong peak in the ^{139}La spin-lattice relaxation rate in a single crystal $\text{La}_{1.67}\text{Eu}_{0.2}\text{Sr}_{0.13}\text{CuO}_4$ in which magnetic neutron scattering indicates the presence of static charge-stripes. We established that these data reflect a distribution of activated energies centered near 50 K and with a width comparable to 50 K, indicating strongly inhomogeneous magnetic properties. To understand whether this inhomogeneity arises from disorder introduced by substitutional dopants, we have applied this analysis to several systems: $\text{La}_2\text{Cu}_{1-x}\text{Li}_x\text{O}_4$ and $\text{La}_{2-x-y}\text{Eu}_y\text{Sr}_x\text{CuO}_4$, with 0.01×0.15 . Remarkably, the character of the inhomogeneity is essentially unchanged in all these cases, suggesting that it is intrinsic rather than arising from impurity disorder. These inhomogeneities that slow spin fluctuations also enhance the Cu spin-relaxation rate and directly explain the wipeout of Cu NMR intensity.

We constructed a model unifying nanoscale inhomogeneities (stripes) and superconductivity in high-temperature copper oxide superconductors. We also proposed impurity states in the pseudogap regime as a probe to distinguish between the superconducting and nonsuperconducting origin of the pseudogap.

This year we have studied the dynamics of polaron formation on a one-dimensional Holstein chain. Our results are relevant to time-resolved optics experiments on manganites and metal-dielectric interfaces and to time-resolved STM experiments.

Time-Resolved Fluorescence Emission from Biological and Electronic Materials

2000058

Andrew P. Shreve

The measurement of time-resolved fluorescence emission on the subnanosecond time scale from both biological samples and electronic materials provides an important probe of structure, function, and dynamics. We have used this ultrafast laser technique to examine fluorescence decay dynamics associated with energy-transfer processes induced by protein binding to membrane-bound ligands.

If each protein binds to multiple fluorescently labeled ligands, the resulting ligand-protein complex leads to a resonant energy transfer between bound ligands. We have recently shown that this transfer provides a sensitive and selective signal transduction method for detecting protein toxins at very low concentrations. Our measurements have provided the first direct time-resolved studies of the energy transfer process upon which this signal transduction process relies. This research will generate valuable information for modeling protein-ligand interactions and optimizing the sensor transduction approach.

In a second area, time-resolved fluorescence techniques are useful in examining the dynamics of both intrinsic and defect-mediated electronic energy localization in nonlinear electronic materials. Such localization is an essential part of the electronic responses of many complex materials of commercial importance including organic conductors and semiconductor nanoclusters. The ability to directly resolve the dynamics and how they are influenced by structure is providing extremely valuable information to help benchmark models and simulations of responses.

Our work during this short-term project has focused on three areas: (1) development of existing Los Alamos instrumentation for ultrafast time-resolved fluorescence measurements, (2) measurement of the dynamics of fluorescent resonant-energy transfer processes associated with protein-binding-induced energy transfer between fluorescently labeled ligands, and (3) measurement of the influence of synthetically controlled chemical defects on fluorescence dynamics in quasi-one-dimensional electronic materials.

Based on our results, we have also been able to incorporate time-resolved fluorescence studies directly into other research involving the development of coupled time-resolved and spatial imaging techniques for characterizing complex interfacial systems.

Investigations of Complex Deformation Behavior in Materials

2000059

Terence E. Mitchell

We are studying complex deformation behavior in two classes of material: metals with grains in the nanometer range and unusual intermetallics. Nanostructured materials are the subject of a major new DOE initiative. Intermetallics have potential applications as high-temperature structural materials, for improving energy efficiency. We are conducting experiments on the mechanical properties of both nanostructured metals and unusual intermetallics, observing dislocations and defects at the atomistic scale with transmission electron microscopy.

Nanocrystalline materials deviate from the Hall-Petch relationship, suggesting that they deform by mechanisms other than bulk dislocations. Atomistic models suggest that at a certain grain size, grain-boundary sliding becomes dominant. To gain insight into this change in deformation behavior, we tensile-tested samples of nanocrystalline copper in a transmission electron microscope (TEM). We prepared these samples using inert gas condensation and an optimized sequence of powder outgassing and compaction at 69°C. The resulting specimens were approximately 98% dense. We cut the TEM specimens, electropolished them in a solution of 30% HPO_4 /70% H_2O , and mounted them in a straining stage.

The resulting microstructure contained grains ranging from 25 to 300 nm. Interestingly, the microstructure had well-defined regions, with each region exhibiting a narrow grain-size distribution. Fig. 1 shows an area of a specimen, after straining, which contains a region of 25-nm grains adjacent to a region of 300-nm grains.

Fig 1. Results of tensile testing nanocrystalline copper. After being subjected to stress, the sample had clearly delineated regions defined by grain size. The area to the left has an average grain size of ~300 nm, while the area to the right has a grain size of ~25 nm.

During deformation, we observed dislocation pileups in grains as small as 50 nm, while single dislocations were observed in grains as small as 30 nm. Figure 2 shows pileups in a 100-nm and 50-nm grain. In addition, we found no strong evidence of grain-boundary sliding. However, grains larger than ~100 nm appeared to account for most of the deformation, indicating a need for specimens with a much narrower grain-size distribution. Next, we will concentrate on thin films with higher densities and narrower grain-size distributions.

In our investigation of unusual intermetallics, we studied the effects of alloying polycrystalline molybdenum disilicide with aluminum, niobium, and rhenium. We evaluated the mechanical properties of the alloys with microhardness and compression tests over a range of temperatures, up to 1600°C. We found that adding rhenium to molybdenum disilicide potentially hardened the solid solution, whereas alloying molybdenum disilicide with aluminum or niobium softened the solid solution at room temperature.

Compared with molybdenum disilicide, the quaternary $(\text{Mo, Re})(\text{Al, Si})_2$ alloy exhibited higher compressive strength at 1600°C and enhanced compressive plasticity at room temperature. We hypothesize that the softening at low temperatures may result from the reduction in Peierls stress, caused by solutes that lower the stacking fault energy. The high hardening rate from rhenium additions cannot be explained by classical substitutional solution-hardening theories for binary alloys based on atomic size misfit and elastic modulus misfit. Since rhenium “disilicide” is semiconducting and has a silicon-deficient stoichiometry of $\text{ReSi}_{1.75}$, the addition of rhenium to molybdenum disilicide may lead to the formation of constitutional vacancies, which can pair with rhenium substitutionals to form point defect complexes. To interpret the rapid hardening that rhenium causes in molybdenum disilicide, we developed a model that describes the elliptical strain field around these complexes.

Fig. 2. Dislocation pileups formed during deformation of nanocrystalline copper. The larger arrow indicates a pileup in a 100-nm grain, while the smaller arrow indicates a pileup in a 50-nm grain. Several other pileups are evident.

Publications

Hugo, R.C., et al., “In Situ TEM Observation of Nanocrystalline Copper during Straining” (Rio Grande Regional Symposium on Advanced Materials, Albuquerque, NM, Oct. 2000).

Hugo, R.C., et al., “TEM Observation of Nanocrystalline Copper during Deformation” (Materials Research Society Meeting, Boston, MA, Dec. 2000).

Keast, V.J., et al., “Compositional Mapping of Nanoscale Metallic Multilayers: A Comparison of Techniques,” in *Electron Microscopy and Analysis 1999*, C.J. Kiely, Ed. (Institute of Physics, Bristol, U.K., 2000) Conf. Ser. 161, p. 211.

Kung, H., et al., “Grain Boundaries and Interfaces in Nanostructured Materials” (Julia R. Weertman Symposium, The Minerals, Metals and Materials Society Meeting, Cincinnati, OH, 1999).

Misra, A., et al., “Rapid Solution Hardening at Elevated Temperatures by Substitutional Re Alloying in MoSi_2 ,” *Acta Mater.* **48**, 925 (2000).

Mitchell, T.E., “A Dislocation Tetrahedron for MoSi_2 ,” *Acta Mater.* **48**, 2713 (2000).

Mitchell, T.E., et al., “Unusual Incommensurate, Modulated and Disordered Structures in Refractory Metal Disilicides,” in *Electron Microscopy and Analysis 1999*, C.J. Kiely, Ed. (Institute of Physics, Bristol, U.K., 2000) Conf. Ser. 161, p. 23.

Sharif, A.A., et al., “Dislocation Motion in Erbium Single Crystals,” *Mater. Sci. Eng., A* **290**, 164 (2000).

Sharif, A.A., et al., “Elastic Constants of Erbium Single Crystals,” *J. Am. Ceram. Soc.* **83**, 2246 (2000).

Sharif, A.A., et al., “Slip Systems in Erbium Single Crystals,” *Key Eng. Mater.* **171**, 801 (2000).

Youngdahl, C.J., et al., “Deformation Behavior in Nanocrystalline Copper” (submitted to *Scr. Mater.*).

Youngdahl, C.J., et al., “TEM Observation of Nanocrystalline Copper during Deformation” (submitted to *MRS Bull.*).

In Situ Synthesis of Organic/ Inorganic Nanocomposites

2000064

Mark Smith

The focus of this project is synthesizing polymer composites with inorganic fillers of nanometer-scale particle size. Using inorganic silicates allows in situ formation of this novel class of materials because the lamellar planes of silicates naturally exist at the nanoscale. We directly add small organic molecules to the filler material and subsequently polymerize these organics into polymer chains.

This research directly supports the National Nanoscience Initiative by developing novel synthetic methods for new nanocomposite materials. Of particular interest is the ability to perform polymerization of monomeric materials with filler particles that self-divide into nanoscale dimensions during polymerization. In addition, this project builds on the strong history of achievements by Los Alamos in the fields of materials, chemistry, and polymer sciences. Advances in the field of nanocomposites will have tremendous impact on the nation's future with cost effective routes to producing functional materials.

To enable the in situ formation of the nanocomposites, we first subject the filler to molecular-scale grafting. We accomplish this by converting the chemical functionality of the silicate surface to an alcohol. Subsequent treatment with metal catalysts allows direct bonding of the organic monomer to the reinforcing surfaces. Adding the monomer then allows polymer molecules to form between the silicate layers.

The proof of concept for in situ synthesis of organic/inorganic nanocomposites is a success. We developed methods in materials chemistry, polymer synthesis, and solution processing that enable us to produce self-forming nanocomposites. We controlled the composition of the silicate surface and produced preliminary material samples for property evaluation. We made the selection of the polymeric material to allow for a crystalline polymer matrix, as opposed to an amorphous polymer matrix, and evaluated the effect of surface grafting.

Understanding Complex Instrumentation Issues Involving Polarized Neutron Beams and High Magnetic Fields

2000067

Michael Fitzsimmons

Developing neutron spin and sample excitation correlation techniques will be essential for understanding a wide range of magnetic and related electron transport problems in the emerging class of complex materials including, for example, nanostructured-engineering and adaptive materials. To achieve a detailed understanding of complex materials, future studies will use neutron beams to characterize the exotic magnetic and atomic structures of these materials in combination with never-before-realized conditions of high magnetic field, high pressure, and very low temperatures.

Our objective is to understand the complex instrumentation issues involving extraction from a pulsed neutron source of a polarized neutron beam and propagation of the polarized neutron beam through huge magnetic field gradients that depend upon space and time. We are aiming, through this project, to develop a solution to the polarization problems, e.g., beam splitting (the Stern-Gerlach effect), associated with interactions between (polarized) neutron beams and the equipment (in this case the high field magnets) that produces a variety of extreme environments simultaneously. Solution of this problem will enable unique studies of complex materials described previously.

During the short duration of the project this year, we developed the equipment required to extract a polarized beam of cold neutrons from the Lujan Center spallation target. The centerpiece of this project is the polarization cavity that is composed of a nickel-coated neutron guide filled with polarizing supermirrors. Unlike conventional approaches, the polarization cavity is designed to produce a beam of neutrons optimally polarized for neutrons of all wavelengths. First tests of the new approach suggest that we obtained neutron beam polarization exceeding 90%.

Mathematics, Simulation, and Modeling

Efficient Multilevel Iterative Methods for Nonlinear PDEs

98029

Dana Knoll

The objective of this project was to develop a new, robust, multilevel methodology for the efficient solution of systems of nonlinear multiple time-scale, multiple length-scale (i.e. stiff) partial differential equations (PDEs). We have developed an innovative methodology that has Newton-like nonlinear convergence properties, multigrid-like efficiency, and Krylov-like dependability, while not requiring the explicit formation or storage of the Jacobian. The foundation of our algorithm uses simple multigrid/multilevel methods as preconditioners for the Jacobian-Free Newton-Krylov (JFNK) method. We do not require rigorous multigrid methods to see great benefit. Furthermore, we have established the concept of physics-based preconditioning.

We have clearly demonstrated that low-complexity multigrid ideas can produce excellent preconditioners of the JFNK method. This year, we codified the ideas of physics-based preconditioning of JFNK using the Navier-Stokes equations and the equations of radiation diffusion. This new work is already being referenced by researchers at other DOE labs, NASA, and academia. In this approach, existing time-split (segregated) integration methods can be used as efficient preconditioners for the accurate JFNK-based (coupled) integrator. We have begun to extend these ideas from radiation diffusion to atmospheric flows and magneto-hydrodynamics (MHD). The atmospheric flow problems we considered presented a new challenge because they coupled a stiff wave term with phase change of fast chemical reactions. The MHD problems we addressed presented a new challenge because they contained multiple stiff waves with anisotropic propagation.

Based on the overwhelming interest in this research, we believe we are filling a void at Los Alamos. There continues to be a realization that the combination of JFNK and multigrid ideas provides a workable algorithm for removing splitting-based numerical errors that are inherent in most existing large-scale simulation codes, including those relevant to stockpile stewardship.

Example application areas include general computational fluid dynamics, MHD, solidifying flows, radiation hydrodynamics, Fokker-Planck simulation of plasmas, atmospheric flows, and granular flows. This project has led to programmatic funding of related research by the ASCI program.

Publications

Bates, J.W., et al., “On Consistent Time-integration Methods for Radiation Hydrodynamics in the Equilibrium Diffusion Limit: Low Energy Density Regime” (accepted in *J. Comput. Phys.*).

Brackbill, J.U., and D.A. Knoll, “Transient Magnetic Reconnection and Unstable Shear Layers” (accepted in *Phys. Rev. Lett.*).

Chacon, L., et al., “A Bounce Averaged Fokker-Planck Code for Penning Fusion Devices” (accepted in *Comput. Phys. Comm.*).

Chacon, L., et al., “An Implicit Nonlinear Reduced Resistive MHD Solver” (submitted to *J. Comput. Phys.*).

Knoll, D.A., and V.A. Mousseau, “On Newton-Krylov Multigrid Methods for the Incompressible Navier-Stokes Equations,” *J. Comput. Phys.* **163**, 262 (2000).

Knoll, D.A., et al., “Nonlinear Convergence, Accuracy, and Time Step Control in Non-Equilibrium Radiation Diffusion” (accepted in *J. Quant. Spectrosc. Radiat. Transfer*).

Mousseau, V.A., et al., “Physics-based Preconditioning and the Newton-Krylov Method for Non-Equilibrium Radiation Diffusion,” *J. Comput. Phys.* **160**, 743 (2000).

Reisner, J., et al., “Application of the Newton-Krylov Method to Geophysical Flows” (accepted in *Mon. Wea. Rev.*).

Extending the Theory of Resonant Perturbations to Partial Differential Equations, with Applications to Nonlinear Optics

98030

Roberto Camassa

The exponential growth of the Internet has created intense pressure for new higher capacity fiber-optic communication lines. The most promising designs for the next generation of communication systems presently use soliton pulses as bit carriers.

In order to increase system capacity, it is necessary to use a regime with multiple soliton channels (operating at different wavelengths) in a single fiber. Experiments show that this approach, although feasible, is adversely affected by two types of resonance effects: resonant interactions between channels and resonances with periodic amplification. A transmission technique that uses strong periodic variation of dispersion with distance—"dispersion management"—shows great promise in being able to stabilize soliton pulses against the deteriorating influences of these resonance effects. Optimizing the dispersion management technique will affect the performance of real world fiber-optic systems, pushing the limits to faster bit rates. A thorough theoretical understanding of the mechanisms responsible for stabilizing the pulses is crucial for these advances.

Our project centered around mathematical averaging and partial differential evolution equations, the theoretical tools needed to understand dispersion management. We developed a concrete example as a vehicle for working on averaging theory. The work we completed provides a detailed base for future generalization of the mathematical theory of averaging and opens the path to optimizing dispersion management in fiber-optic applications.

This last year of the project, we concentrated on two aspects of modeling electromagnetic field propagation in optical media. With an eye on developing analytical and numerical methods for future generation devices that utilize ultrashort pulses, we have studied propagation of the fundamental carrying electric field in a nonlinear superconducting waveguide. We have included in our models the effects induced by noise, which is a widespread feature of long-distance fiber-optic communication lines.

Large-bandwidth, high-speed telecommunication is a key component of information technology. Its numerous roles are of immediate interest to DOE and the Laboratory—from connecting supercomputers to transferring very large quantities of data from experimental devices that are monitoring hazardous experiments. Moreover, as the Internet becomes one of the defining elements of the modern world, it is imperative that the United States maintain a position of leadership in this area. Such a goal can only be achieved by looking several years ahead of the current technological state of the art, which requires addressing fundamental scientific questions such as those we are investigating.

Publications

Findikoglu, A.T., et al., "Nonlinear Dielectric Response and Stochastic Effects in Strontium Titanate" (submitted to *Appl. Phys. Lett.*).

Lushnikov, P.M., "On the Boundary of the Dispersion-Managed Soliton Existence," *JETP Lett.* **72** (3), 163 (2000).

Zoldi, S.M., et al., "Parallel Implementation of the Split-Step Fourier Method for Solving Nonlinear Schrodinger Systems," *SIAM News* **32** (1), 8 (1999).

Invariant Discretizations for Computational Gas Dynamics

98031

Mikhail Shashkov

The primary goal of this project was to formulate finite-difference methods that do not contain vector and tensor components that are related to some fixed coordinate system. In addition, the coefficients must depend only on the coordinate invariant characteristics of the computational grid, such as edge length, face area, cell volume, and angles between edges.

Algorithms based on mathematical principles that correspond to basic physical principles produce accurate and robust numerical methods. One such principle is symmetry. Our new finite-difference methods are invariant and therefore better able to reproduce the structure of the solution. The new methods require far fewer mesh points in obtaining the same quality as existing methods do. Consequently, the new methods allow us to (1) solve problems when preservation of symmetry is important and (2) remove uncertainty about whether a nonsymmetric result is caused by numerical errors or by physical design.

We developed and implemented a “modified gradient” approach for three dimensional gas dynamics calculations in which forces are locally modified according to the expected symmetry in the flow. We used numerical experiments to illustrate the robustness of this new method.

We showed the advantages of our new methods for solving spherical Rayleigh-Taylor instability problems. In traditional methods small departures from discrete-error-caused spherical symmetry can lead to unacceptably large errors in the system with large convergence ratios. In addition, the uncertainty about whether a nonsymmetric result is caused by numerical errors or by physical design severely limits predicting capabilities and understanding dynamical behavior of such systems. Our new methods have no such errors.

Publications

Caramana, E., et al., “A Compatible, Energy- and Symmetry-Preserving Lagrangian Hydrodynamics Algorithm in Three-Dimensional Cartesian Geometry,” *J. Comput. Phys.* **157**, 89 (2000).

Margolin, L., et al., “Symmetry-Preserving Discretizations for Lagrangian Gas Dynamics,” in *Proceedings of the Third European Conference on Numerical Mathematics and Advanced Applications*, P. Neittaanmaki, et al., Eds. (World Scientific, Singapore, 2000), p. 725.

Margolin, L., and M. Shashkov, “Using a Curvilinear Grid to Construct Symmetry-Preserving Discretizations for Lagrangian Gas Dynamic,” *J. Comput. Phys.* **149**, 389 (1999).

Unitary Symmetry, Discrete Mathematics, and Combinatorics

98032

William Y.C. Chen

The purpose of this research was to simplify the complex physics and chemistry in material science and other disciplines by applying a branch of mathematics called combinatorics to well-identified areas of physics and chemistry. Combinatorics has recently found wide applications across physical and informational problems.

We have developed the relationship between combinatorics and physics in two prominent areas: (1) the theory of group representations, which is used to explain the spectra of many-particle quantum systems; and (2) the theory of maps of the interval, which is used to model and explain the behavior of discrete dynamical systems.

Progress in the theory of group representations is based on two discoveries that we made early in this project. We discovered that a classical combinatorial result known as MacMahon's Master Theorem unifies the theory of binary recoupling coefficients, which recur throughout physical applications in many-particle physics. We also found that the multiplication law of group representations is far more general than the structure of groups and Lie algebras. The law depends solely on a combinatorial identity among multinomial coefficients. This finding, in turn, allows the extension of group representations to polynomials defined over arbitrary commuting variables. In fact, it also allows the extension to noncommuting variables, as well as to the first comprehensive theory of tensor operators, which are the basis of all interactions in physical systems.

Progress in the theory of maps of the interval is due to an increased understanding of the combinatorial properties of certain sequences of integers that label the inverse graphs naturally. We have shown that the combinatorial property of parity of sequences dictates the birth of bifurcation and cycle points, which are properties that govern the behavior of dynamical systems modeled by maps of the interval.

This project clearly demonstrates the rich relationship between combinatorics and physics and has led to new results for each discipline.

Publications

Chen, W.Y.C., et al., "Adjacency and Parity Relations of Words in Discrete Dynamical Systems," *J. Comb. Theory A* **91**, 476 (2000).

Chen, W.Y.C., et al., "The Flagged Double Schur Function" (accepted in *J. Algebraic Combin.*).

Louck, J.D., "New Perspectives on the Unitary Group and its Tensor Operators," in *Proceedings of the Sixth Conference on Symmetry and Structural Properties of Condensed Matter*, T. Lulek et al., Eds. (World Scientific, Singapore, 2001).

Louck, J.D., "Unitary Group Theory and the Discovery of the Factorial Schur Functions," *Ann. Combin.* **4**, 413 (2000).

Louck, J.D., and M.L. Stein, "Relations Between Words and Maps of the Interval" (Renaissance of Combinatorics Conference, Tianjin, China, October 1999).

Louck, J.D., et al., "Angular Momentum, Umbral Calculus, and Combinatorics" (accepted in *Internat. J. Comp. Math.*).

Statics and Dynamics of Granular Media

99034

Eli Ben-Naim

The mathematical description of granular materials such as powders, grains, and explosives—ensembles of macroscopically sized particles—is incomplete. To remedy that deficiency, we are using statistical investigations of the dynamics of granular flow and the statics of granular packing to develop appropriate continuum equations and improved numerical modeling techniques. Our numerical studies involve large-scale parallel computations and thus employ the Laboratory's high-performance computing capabilities. This project enhances the Laboratory's core competencies in the areas of advanced computing, modeling, and simulation, as well as the Laboratory's mission in materials science. Better mathematical and statistical descriptions of granular packing and granular flow will also translate into improved geophysical and earth sciences models. Granular materials are characterized by two unique

features: strong dissipative interactions and macroscopic particles. This project focuses on how these characteristics influence freely evolving granular gases and excited granular matter.

This year we developed a new numerical simulation method, a relaxation technique that allows us to simulate shocks arising in granular flows as a result of strong energy dissipation. Combined with efficient collision-driven molecular-dynamics simulations (Fig. 1), we used this method to verify predictions of a continuum theory proposed by our previous work in two spatial dimensions. In particular, we showed that the velocity distributions approach a scaling form and that the corresponding energy scale is independent of the degree of dissipation.

To address the role of energy dissipation, we obtained an exact analytic solution for the time-dependent and steady-state behavior of the kinetic theory of granular gases with a constant collision kernel. We found that moments of the velocity distribution exhibit multiscaling asymptotic behavior. In addition, we found generalized fluctuation-dissipation relations, as the corresponding hierarchy of relaxation time scales is related to the cumulants of the steady-state distribution in the presence of a balancing energy source.

Fig. 1. Density inhomogeneities and shock formation in granular media. Shown is a subset of an event-driven molecular dynamics simulation.

The macroscopic particle size was the basis of our study of excited granular polymers. We developed a diffusion theory that describes statistical properties of the relaxation times of topological constraints such as knots in vertically vibrated granular polymers (Fig. 2). Characteristics of the opening time distribution, including fluctuations and coefficients underlying extremal statistics, agree to within a few percent with the measured experimental values (Fig. 3).

Publications

Ben-Naim, E., and P.L. Krapivsky, “Stochastic Aggregation: Scaling Properties,” *J. Phys. A*, **33**, 5477 (2000).

Ben-Naim, E., et al., “Knots and Random Walks in Vibrated Granular Chains” (to be published in *Phys. Rev. Lett.*).

Chen, S., et al., “Clustering Kinetics of Granular Media in Three Dimensions,” *Phys. Lett. A*, **269**, 218 (2000).

Krapivsky, P.L., and E. Ben-Naim, “Stochastic Aggregation: Rate Equations Approach,” *J. Phys. A*, **33**, 5465 (2000).

Nie, X., et al., “Dynamics of Vibrated Granular Monolayers,” *Europhys. Lett.* **51**, 679 (2000).

Fig. 2. Relaxation of knots in vertically vibrated granular chains. Shown are snapshots of the unknotting process taken at equally spaced time intervals.

Fig. 3. Diffusion theory versus experimental data. Shown is the survival probability $F(z)$ versus the opening time z (measured in units of the average opening time) of a simple knot in a vibrated granular polymer.

Quantum Physics Algorithms

99035

Emanuel Knill

The discovery of interesting quantum algorithms that would be much faster than their classical counterparts, the implementation of individual quantum gates, and the discovery of quantum error-correcting codes have revealed the enormous practical potential that exists in the field of quantum computation. Quantum computing may one day revolutionize computer science, affect issues of national security, and impact the economy. Simulations produced in quantum systems using a modest number (<40) of quantum bits, known as qubits, exceed the capabilities of even the biggest present-day classical computers. The goal of this project is to advance the state of the art in quantum physics algorithms.

Previously in this project, we introduced a new model of quantum computing called “one-bit quantum computing” (QC1), which is intermediate in power between classical and quantum computing. The model describes ideal nuclear magnetic resonance (NMR) quantum computing at high temperature and establishes the intrinsic nonclassicality of this computational system. The discussion of what accounts for the power of quantum computing is now significantly enriched, and previous explanations are seen to be incomplete. We showed also that spectral density estimation can be implemented using QC1. This work was crucial to our recent discovery of a new type of problem that can be solved efficiently by using quantum computers. This problem is characterized by a family of combinatorial sums called “quadratic weight enumerators” (QWGTs, pronounced “queue-widgets”). QWGTs extend the power of quantum computing by providing families of natural problems that can be seen to be more powerful than quantum computers, equivalent to quantum computers, or equivalent to one-bit quantum computers, respectively.

This year we also established algorithms for simulating harmonic oscillators with an NMR-based spin system. We then implemented those algorithms at MIT and published the theory and experiments.

Publications

Knill, E., and R. Laflamme, “Quantum Computation and Quadratically Signed Weight Enumerator” (to be published in *Inf. Proc. Lett.*).

Tseng, C.-H., et al., “Quantum Simulation of a Three-body Interaction Hamiltonian on an NMR Quantum Computer,” *Phys. Rev. A* **61**, 012302/1-6 (2000).

Tseng, C.-H., et al., “Quantum Simulation with Natural Decoherence,” *Phys. Rev. A* **62**, 032309/1-9 (2000).

New Dispersive Models of Fluid Turbulence

99037

Darryl D. Holm

Flows in nuclear weapons, ocean circulation, and other real-life applications have features that make traditional turbulence modeling inappropriate. These features include transient forcing, strong anisotropy and inhomogeneity, multiphases, and coherent structures. Our work combines new elements of theory, numerical simulation, and modeling that can naturally incorporate these features. Our objective is to produce predictive models for use in several major programs at the Laboratory.

We are harnessing a new analytical approach for both numerical algorithm development and physical modeling. This approach results in a nonlinear dispersive system of flow equations we call the Navier-Stokes alpha model. The Navier-Stokes alpha model shows great promise as a subgrid model for turbulent fluid flows and has an intriguing relation to nonoscillatory algorithms for numerical simulation of turbulence.

This year we showed that the solutions of the Navier-Stokes alpha model do indeed describe the Euler-averaged motion of a turbulent fluid. We also showed that strong solutions of the Navier-Stokes alpha model exist globally, that they are unique, and that they possess a global attractor whose fractal dimension is finite.

The Navier-Stokes alpha model equations generalize the scale-similarity class of large-eddy simulation (LES) models and improve them by restoring their Kelvin circulation theorem, which is fundamental to all fluid dynamics. For this class of LES models, the Kelvin theorem states that upon applying a certain approximate inverse of the LES spatial filtering, the circulation velocity of the defiltered fluid in these LES models is preserved for every fluid loop that moves with the filtered velocity. The subgrid-scale forces in the Navier-Stokes alpha model (recast as an LES scale-similarity model) transform properly—that is, covariantly—both under Galilean transformations and under a change to a uniformly rotating reference frame.

These results show that the Navier-Stokes alpha model equations extend the LES scale-similarity models in a way that is consistent with fundamental physics.

Publications

Domaradzki, J.A., and D.D. Holm, “Navier-Stokes Alpha Model: LES Equations with Nonlinear Dispersion” (accepted in special LES volume of *ERCOTAC Bull.*).

Foias, C., et al., “The Navier-Stokes Alpha Model of Fluid Turbulence” (accepted in *Physica D*).

New Perspectives in Mathematical Modeling of High-Bit-Rate Optical-Fiber Telecommunications

99038

Ildar Gabitov

To keep up with the exponentially growing demand for optical-fiber system capacity, U.S. industry must develop ever-faster means of communication (at least in the terabit-per-second regime). In recognition of this demand, a multiagency effort is underway to develop significantly better bandwidth solutions. Indeed, no existing network and fiber technology is even close to being sufficiently robust and affordable to link DOE's supercomputing sites.

The aim of our project is to contribute to the theoretical background of modern optical-fiber telecommunications and develop new principles of data transmission in optical-fiber links. Applications include networks for next-generation supercomputers, which would be of great value to the Laboratory and DOE.

We are exploiting methods of modern mathematics to describe the optical pulse dynamics in optical-fiber links. This year, we investigated several aspects of these pulse dynamics with dispersion management and random variation of fiber parameters.

Short-range-correlated uniform noise in the dispersion coefficient broadens and eventually destroys all initially compact pulses. However, when the integral of the random component of the dispersion coefficient is set to zero (pinned) periodically or quasi-periodically along the fiber, the nature of the pulse propagation changes dramatically. If randomness is added to the constant positive dispersion, pinning significantly reduces pulse broadening (see Figs. 1 and 2). If the randomness is added to the piecewise constant periodic dispersion, pinning may even provide probability distributions of pulse parameters that are numerically indistinguishable from the statistically steady case.

We developed a Lie-transform approach and obtained an equation that describes the slow dynamics of an optical pulse and takes into account higher-order corrections. We proved the existence of dispersion-managed solitons in the case of zero/negative average dispersion; we demonstrated that a dispersion-managed soliton can exist only if the modulus of average dispersion is small enough to allow nonlinear compensation of pulse broadening—because of the dispersion variation over one period. We presented an

asymptotic description of the fine-tail structure of the dispersion-managed solitons and showed the dependence of this structure on the central part of the pulse, which carries the main part of the soliton energy.

We also studied three-dimensional space-time collapse in nonlinear optical cavities pumped by an external train of pulses. We demonstrated that collapse is an effective mechanism for generating ultrashort pulses from initially smooth wave packets and obtained the criteria for collapse of an optical cavity. These criteria for optical-cavity collapse can be used to design an ultrashort-pulse generator of a new type.

Publications

Chertkov, M., et al., "Pulse Confinement in Optical Fibers with Random Dispersion" (submitted to *Science*).

Gabitov, I., et al., "Lie-Transform Averaging in Nonlinear Systems with Strong and Rapid Periodic Dispersion Variations," *Phys. Lett. A* **265**, 274 (2000).

Lushnikov, P.M. "Dispersion-Managed Soliton in Optical Fibers with Zero Average Dispersion," *Opt. Lett.* **25**, 1144 (2000).

Lushnikov, P.M., "On the Boundary of the Dispersion-Managed Soliton Existence," *J. Exp. Theor. Phys. Lett.* **72**, 111 (2000).

Lushnikov, P.M., and A.V. Mamaev, "Spontaneous Hexagon Formation in Photorefractive Crystal with a Single Pump Wave," *Opt. Lett.* **24**, 1511 (1999).

Lushnikov, P.M., and M. Saffman, "Collapse in a Forced Three-Dimensional Nonlinear Schroedinger Equation," *Phys. Rev. E* **62**, 5793 (2000).

Lvov, Yu, and I. Gabitov, "Dispersion Management in Optical Fiber Links: Integrability in Leading Nonlinear Order" (submitted to *Phys. Lett. A*).

Shaulov, G., et al., "Pulse Dynamics in Absorber Dominated Optical Cavities," *Opt. Commun.* **164**, 39 (1999).

Fig. 1. Evolution of the conventional soliton amplitude with distance. All units are normalized to dispersion length. The different colors represent different periods of pinning (I). For example, the black curve describes soliton degradation in the fiber with no pinning. The upper curves correspond to the pinning period $I = 0.5$ (solid pink line) and to the case in which the pinning point is randomly distributed over $I = 0.5 \pm 0.25$ (broken pink line). The value of the dispersion variation is 0.1. The pinning method dramatically reduces the rate of soliton degradation.

Fig. 2. Evolution of the dispersion-managed soliton amplitude with distance. The different colors represent different periods of pinning (l). All units are normalized to dispersion length, and the value of the dispersion variation is 0.1. The dispersion-managed solitons do not degrade noticeably.

Effective Arbitrary Lagrangian-Eulerian Strategies

2000045

Mikhail Shashkov

Our goal in this research project is to develop new algorithms and improved analysis tools that will effectively use the power of current and future generations of scalable parallel supercomputers. In particular, we are concentrating on improving the explicit Lagrangian update and rezone/remap phase in arbitrary Lagrangian-Eulerian (ALE) simulations. In numerically solving multidimensional problems in fluid dynamics, an important consideration is the relationship between the fluid motion and the computational grid. Traditionally, there have been two viewpoints: Lagrangian and Eulerian. In the Lagrangian framework, the mesh moves with local fluid velocity, whereas in the Eulerian framework, the fluid flows through a fixed grid. Each framework has its own advantages and difficulties. The essence of the ALE methodology is that it allows us to choose the mesh motion arbitrarily, to suit the situation, thus allowing us the flexibility to combine the individual strengths of the two approaches.

During the last year we have developed an automatic rezone strategy for use in ALE simulations. Our methodology is based on the minimization of a nonlinear functional that measures the deviation of the local Jacobian matrix from a reference Jacobian matrix. The resulting grid motion is as nearly Lagrangian as possible while minimizing grid distortion. The local Jacobian is constructed from the geometry of an individual cell, but the reference Jacobian includes the geometry of the surrounding cells. The difference between these two Jacobians quantifies the smoothness of the mesh.

Two key features of our new method are a variable weighting scheme that takes into account the Lagrangian velocity field and a barrier that prevents mesh folding. We can easily extend this method to three-dimensional applications and to cases with unstructured grids. In addition, we have developed a new high-order, conservative interpolation procedure, with which we can significantly improve the accuracy of the remap phase. We have demonstrated the robustness and the effectiveness of our method on several test examples.

Publications

Knupp, P., et al., “Optimizing Mesh Quality for Rezoning in ALE Methods,” *Proceedings of 2000 SIAM Annual Meeting*, (Society for Industrial and Applied Mathematics, Philadelphia, PA, 2000).

Knupp, P., et al., “New Rezone Strategy for ALE Methods,” *Proceedings of First SIAM Conference on Computational Science and Engineering* (Society for Industrial and Applied Mathematics, Philadelphia, PA, 2000).

Direct Numerical Simulation and Stochastic Modeling in Ocean Dynamics

2000046

Darryl D. Holm

This project focuses on the physics and mathematics of three-dimensional modeling of ocean turbulence. The principal application of this work is to ocean circulation modeling, which will eventually benefit DOE's climate prediction program by significantly improving the accuracy of modeling thermohaline circulation. However, our work can also be applied to all branches of turbulence modeling, including stockpile stewardship. Our main goal is to derive self-consistent equations for the effects of fluctuations on mean flow by combining direct numerical simulations (DNS) and new ideas regarding nonlinear dynamics and stochastic partial differential equations (PDEs).

Toward that goal, we have developed a derivation of Lagrangian and Eulerian mean equations that describes the coupled equations for the mean and the variance of ocean circulation dynamics. As a basis for our equations, we have determined appropriate averages for the decomposition of fluid parcel trajectories and velocities into their mean and stochastic parts. We used DNS to model these approximate equations in the double-gyre problem of ocean circulation. We then compared these solutions to the DNS of the unapproximated equations to assess the statistical properties of the fluctuations. Finally, we applied the theory of stochastic PDEs to model the rapid fluctuations around the slow-time dynamics.

Initial analyses of the data have shown that our new model equations significantly improve the variability and energetics as compared to standard methods. We have found that the alpha effect suppresses instability growth rates at small scales while preserving the large-scale variability necessary for modeling ocean circulation. The alpha model allowed an exceptionally long time step without becoming unstable. We are investigating the detailed mechanism for this important property of the alpha models in a variety of other test problems.

Publications

Duan, J., et al., "Variational Methods and Nonlinear Quasigeostrophic Waves," *Phys. Fluids* **11**, 875 (1999).

Holm, D.D., "Fluctuation Effects on 3D Lagrangian Mean and Eulerian Mean Fluid Motion," *Physica D* **133**, 215 (1999).

Rayleigh-Ritz Computation of Multitime Statistics

2000047

Francis J. Alexander

Researchers in weapons design, climate modeling, computer science, and environmental management programs must be able to predict the behavior of complex systems. These systems include underground reservoirs, the global climate, turbulent flows, and large computing and communications networks. To predict the systems' behaviors, we must accurately and efficiently compute temporal correlations, optimal histories, and other multitime statistics. This is an extremely difficult proposition given the strongly fluctuating, nonequilibrium, and, in particular, multiscale nature of the systems. Our novel statistical mechanics approach directly addresses these complexities. We use physical intuition and empirical evidence that describe the dynamics of the system, together with a Rayleigh-Ritz approximation scheme, in a quantitative computation. In this way, a drastic mode reduction can be achieved, sidestepping the difficulty of a direct numerical calculation.

This year we have focused our work on a hydrological transport application: estimating the past history of transport of chemicals or radioactive materials that were involved in spills. Our goal was to trace the contaminant plumes to their sources. Generally, scientists have access to the measurements of the pollutant concentration at a few points in space and time and must work backward to determine the most likely time and location that the spill occurred. In addition to a method for calculating the most likely, or mean, location of the source, we have developed numerical methods by which we can make an a priori assessment of the degree of uncertainty regarding the spill's location.

We calculate these statistics using a variational cost function called the effective action. In our theoretical work we have shown that we obtain conditional averages by minimizing this action, using the measurements as constraints. We calculate the effective action itself by the Rayleigh-Ritz method, employing a simple Ansatz for the statistics and a guess of the relevant dynamical variables. By making well-motivated, physically inspired guesses we can radically minimize the number of degrees of freedom that we need for the calculation. Thus, estimation problems that were intractable by direct calculational methods become feasible when we use the variational method. We have also developed a Monte Carlo method for optimal estimation that circumvents many computational problems.

Publications

Eyink, G.L., "A Variational Formulation of Nonlinear Estimation" (submitted to *Method. and Comput. in Appl. Prob.*).

PREDICT

2000062

Mary Meyer

Information Integration Technology (IIT) is a combination of processes, methods, and tools for collecting, organizing, and analyzing diverse information and for utilizing that information to guide prudent decision making. PREDICT (Performance and Reliability Evaluation with Diverse Information Combination and Tracking) is a highly successful IIT tool we developed that has been applied here at Los Alamos and at Delphi Automotive Systems, formerly the systems/components divisions of General Motors.

Specifically, the PREDICT tool is a formal, multi-disciplinary process we developed for estimating the performance of a product when test data may be sparse or nonexistent. PREDICT combines all available information: expert knowledge, historical information, experience with similar products, and computer model outputs. PREDICT's calculations can help guide product development from the concept stage through prototyping and production. PREDICT can then be used to document the product's performance through its lifetime.

PREDICT won an R&D 100 award in 1999. This project was funded for one year to allow us take advantage of the momentum we gained by winning a national award. Through this project, we have strengthened the theoretical foundations of IIT and have continued to evolve the methodology for eliciting and representing all kinds of information, with a focus on the weapons community and the auto industry. Delphi Automotive Systems has used PREDICT for designing systems within engines, such as fuel systems. Los Alamos uses the IIT methodology to estimate the reliability of its aging nuclear weapons, which cannot be tested but whose reliability must be certified to Congress. Each of these applications has different requirements for combining and using information, and each has different problem areas in handling uncertainties.

In developing IIT and the tool PREDICT, we have drawn on numerous approaches, including statistical analysis, uncertainty analysis, reliability analysis, subjective probability, fuzzy set theory, Bayesian methods, knowledge modeling, cultural anthropology, and expert judgment techniques.

Publications

Bement, T.R., et al., "Testing the Untestable: Reliability in the 21st Century" (accepted in *IEEE Trans. Reliab.*).

Booker, J.M., et al., "PREDICT: A New Approach to Product Development and Lifetime Assessment Using Information Integration Technology," in *Handbook of Statistics: Statistics in Industry* (Elsevier, Amsterdam, in press).

Meyer, M.A., and R. C. Paton, "Interpreting, Representing, and Integrating Scientific Knowledge from Interdisciplinary Projects" (accepted in *Theoria et Historia Scientiarum*).

Perl, M.L., and M.A. Meyer, "The Practice of Experimental Physics: Recollections, Reflections, and Interpretations" (accepted in *Theoria et Historia Scientiarum*).

Nuclear and Particle Physics

Exploring and Testing the Standard Model and Beyond

98038

Geoffrey West

The goal of this project is to extend and develop predictions and consequences of the standard model of elementary particle physics in several different directions. These include various aspects of the strong nuclear force as described by Quantum Chromodynamics (QCD), the unified electroweak theory, and the gravitational interaction.

We improved the method developed last year to relate the lattice QCD output of light quark masses to those used in phenomenology, and quantified its errors. This led to improved confidence in the results. We also performed preliminary investigation of the possibility of evaluating the CP-violating parameter ϵ'/ϵ directly on the lattice.

We extended the improved fixed point action to include fermions. The ease with which this development was carried out demonstrated the power of the higher symmetry that is preserved in this new action. This extension now paves the way for the method to be used in practical simulations with reduced errors.

We studied further the perturbative expansion in QCD, and provided a heuristic proof of its divergent behavior. Studying the behavior of its low order terms we gained a qualitative understanding of precocious scaling.

Building upon our earlier work on periodic instanton solutions of the SU(2) Yang-Mills-Higgs system (the standard electroweak model with no fermions), we studied the new class of complex instanton solutions analytically at low energies and numerically at high energies, and found bifurcation points as the temperature and energy were varied.

We extended our previous study of the infrared properties of gravity by showing that the low energy effective action, can be derived by dimensional regularization and has a cohomological interpretation as closed but nonexact one-forms of the local Weyl group. The distinguishing feature of this effective action is that it is logarithmically sensitive to global Weyl rescalings and therefore a marginal operator

in the Wilson sense, which does not decouple in the low energy effective action of 4-dimensional gravity. In addition, we showed that the infrared effects of a massless scalar field in de Sitter space also includes the low energy effective action, by examining the late time attractor behavior of the energy-momentum tensor, which is independent of the initial state.

We have also been analyzing systematics that might be the cause of the anomalous acceleration seen in the orbit of Pioneers 10 and 11. One by one, we have been eliminating these as potential causes, the largest of them being reaction from beacon beam towards the earth, reaction due to thermal radiation from the radioisotope thermoelectric generators, and gas leaks from attitude-control thrusters. The reported annual signal is now understood as being due to imprecise determination of the velocity cosine of the craft off the plane of the ecliptic. Although we feel that the Pioneer effect is most likely due to an undiscovered systematic effect, an explanation is yet to be found.

Publications

Turyshchev, S.G., "The Apparent Anomalous, Weak, Long-range Acceleration of Pioneer 10 and 11, in Gravitational Waves and Experimental Gravity," in *Proceedings of the XVIIIth Moriond Workshop of the Rencontres de Moriond*, edited by J. Dumarchez and J. Tran Thanh Van (World Pub., Hanoi, 2000) p. 481.

West, G.B., "Asymptotic Series and Precocious Scaling," *Foundations of Physics* **30**, 695 (2000).

Determination of the Neutron Lifetime and Ultracold-Neutron Source Development

98039

Steve K. Lamoreaux

Ultracold neutrons (UCNs) are neutrons with kinetic energy so low (less than 200 neV, corresponding to a velocity of 5 m/s) that they can be trapped by magnetic fields and reflected from material surfaces. UCNs can be used for measuring fundamental properties of the neutron; these properties can shed new light on the nature of the interaction between elementary particles.

Our goals are to measure the neutron beta-decay lifetime with an order-of-magnitude improvement, and to develop a new UCN source that offers a 100-fold increase in density compared with existing sources. This work supports the DOE mission in the thrust area of fundamental nuclear science.

We finally succeeded in producing, storing, and detecting UCNs in a superfluid helium-4 magnetic trap. Our main effort this year has been on improving these preliminary results but was limited by neutron activation, which contaminates the extraction of the neutron lifetime. Basically, the technique relies on producing UCNs by the so-called superthermal process (inelastic scattering of neutrons in superfluid helium-4 to near-zero energy). A UCN so produced remains in the superfluid bath (which, at low temperature, appears as a perfect mechanical vacuum to the UCN) until it is lost to beta decay. UCNs that decay in the superfluid bath produce scintillation light.

We now believe that all loss mechanisms can be controlled so that there is no systematic error at the level of accuracy sought. The primary problem remaining to be solved is elimination of stray light resulting from activation when the UCNs are initially produced caused by neutrons that are elastically scattered and then absorbed into the trapping system. The subsequent decay of the induced radioactivity also produces scintillation light. Our plan to eliminate this light involves use of an incident neutron velocity filter (only a small energy band is useful for UCN production) and a larger trapping volume.

The second area of effort involves the identification and testing of materials to serve as a new type of UCN source, in particular, solid deuterium. Much of this work has merged with that of the Ultracold Neutron Science project. We recently produced a world-record UCN density with a new source. The design for this new source was produced under our project.

The success of the new source is due to the identification of a UCN loss mechanism in the solid deuterium; we had seen evidence of such a loss in our 1998 measurements in Berlin. Briefly, the loss is due to the paramolecular state of the deuterium molecule that remains on freezing the gas from room temperature. This year, we produced a theoretical analysis of this problem, built a cryogenic catalytic converter to eliminate the paramolecular state, and constructed apparatus to evaluate the conversion efficiency. We are now well-poised to construct the world's most powerful UCN user source.

Publications

Hill, R.E., et al., "Performance of a Prototype Solid Deuterium UCN Source," *Nucl. Instrum. Methods Phys. Res., Sect. A* **440**, 522 (2000).

Huffman, P.R., et al., "Magnetically Stabilized Luminescence in Hexagonal Boron Nitride" (accepted in *J. Lumin.*).

Huffman, P.R., et al., "Magnetic Trapping of Neutrons," *Nature* **403**, 62 (2000).

Huffman, P.R., et al., "Progress Toward Magnetic Trapping of Neutrons," *Nucl. Instrum. Methods Phys. Res., Sect. A* **440**, 422 (2000).

Liu, C.-Y., et al., "Ultracold Neutron Upscattering in a Solid Deuterium Crystal," *Phys. Rev. B* **62**, R3581 (2000).

Parity Nonconservation in the Reaction $n + p = d + \gamma$

98040

J. David Bowman

We proposed to design and begin an experiment to measure the Parity NonConserving (PNC) directional asymmetry, A , in the capture of polarized neutrons on hydrogen $n + p \rightarrow d + \gamma$ at the Los Alamos Neutron Science Center (LANSCE). We proposed to measure the PNC asymmetry, A , of the direction of emission of the gamma ray with respect to the neutron spin with an error of $5 \cdot 10^{-9}$. This asymmetry can be unambiguously related to the weak isovector pion-nucleon-nucleon coupling, H_π . The value of this coupling had been previously determined from two different measurements in complex nuclei. The two determinations disagree—most likely because of uncertainties in the calculation of the nuclear matrix elements needed to relate measured quantities to the weak meson couplings. The present measurement does not suffer from nuclear structure uncertainty. Our measurement of the asymmetry should determine H_π to 10% of its expected value, 10^{-6} . At the present time, none of the six weak meson-nucleon-nucleon couplings were known. This measurement will provide the first unambiguous determination for one of the weak meson-nucleon-nucleon coupling constants. The above statistical error can be obtained in one year at LANSCE. We showed that systematic errors are negligible. The experiment made use of the large flux of cold neutrons available at LANSCE and controlled systematic errors with the pulsed structure of the neutron flux. We had in place for the project a highly qualified collaboration of scientists from within Los Alamos and from universities and national laboratories in the United States, Russia, and Japan.

This year we conducted a test run. Our goal for the run was to test a 10% model of the final hydrogen $n + p \rightarrow d + \gamma$ apparatus. We measured neutron flux to benchmark the LANSCE Monte Carlo prediction of the flux from the liquid-hydrogen moderator. The measured flux was 20% higher than predicted, which is good for the experiment. We established that beam intensity and position fluctuations would not degrade the experiment. We produced a polarized neutron beam by transmission through a polarized helium-3 cell. We measured the spin flipper efficiency vs. energy and position of a radio frequency spin flipper. We determined that the reversal efficiency for the experiment will be greater than 96%. The totally absorbing neutron transmission monitor we used will also be part of

the final experimental setup. We compared the performance of 3-in. and 5-in. vacuum photodiodes and chose the cheaper 3-in. photodiode. We used four prototype CsI detectors and low-noise preamps to measure PV gamma asymmetries in chlorine-35, lanthanum-139, and cadmium-113 to $\pm 2.5 \cdot 10^{-6}$ (stat) and $\pm \text{few } 10^{-7}$ (syst) in 8 hours/target. We exercised a full data-acquisition system. These tests show that there are no technical obstacles to carrying out the full-blown experiment, which has been accepted for programmatic funding.

A Search for Superradiant Emission in a Nuclear Isomer Crystal

98041

Robert S. Rundberg

Nuclear superradiance is a possible means of releasing the nuclear energy stored in nuclear isomers. The energy density of nuclear isomers is greater than that of conventional explosives but is orders of magnitude less than nuclear explosives. The release of this energy as electromagnetic energy would have unique applications of considerable interest. Superradiance, as it has been termed, describes the photon emission properties of high-cooperation-number quantum states in ensembles of atoms. A cooperation number is the eigenvalue of the photon emission operator analogous to spin.

Superradiance can be achieved by producing highly enriched nuclear isomers. The high-cooperation-number state can be reached either by adsorbing photons into an ensemble of ground state nuclei or by allowing an ensemble of fully excited isomers to decay. The single photon case has been demonstrated in a series of elegant experiments using synchrotron radiation to excite iron-57 Mössbauer crystals. From a fully excited crystal, the photon intensity will increase until a maximum is achieved when the number of excited nuclei equals the number of ground state nuclei. At this point, the radiation rate is proportional to the square of the number of nuclei. In a few cases, such as molybdenum-93, a radioactive nuclide decays preferentially to the nuclear isomer, niobium-93m. These systems can be generators of highly enriched nuclear isomers.

We have developed chemical separation procedures to isolate niobium from the Los Alamos Neutron Scattering Center (LANSCE) isotope production targets. We estimate, based on analyses of samples, that a kilogram of molybdenum produces 30 milligrams of niobium. This material has 10% niobium-93m. The isotopes niobium-93g, niobium-94, niobium-91, and niobium-92 make up the rest of the niobium. The process we used to isolate the niobium produced from spallation reactions will also purify the molybdenum for use as a niobium-93m generator. Molybdenum is adsorbed as a sulfato complex onto Dowex-ag1 anion exchange resin. We collect and concentrate the niobium-93m and other radioactive products by evaporation. We then scavenge the niobium from the acid solution by co-precipitation with iron hydroxide. Although the procedure is manpower intensive and limited to 10-gram

batches of molybdate, it does not generate mixed waste and retains the purified molybdenum. We have processed 200 grams of the available 1500 grams of molybdate thus far at a rate of about 10 to 20 grams per week.

We have also developed a procedure for growing thin films of lithium niobate on single crystals using the sol-gel method. We developed chemical procedures for manufacturing the necessary reagents using a Schlenk line with stable niobium at the milligram level.

We have, to date, isolated niobium fractions from target material containing the isotopes listed in the table below. The stable niobium-93 and long-lived niobium-92 are not listed; the masses are about 35 micrograms and 60 micrograms, respectively. The amounts of niobium isotopes represent 13 percent of the quantity available from the 1500-gram stock of molybdate. The final quantity we will have available when the processing is completed will be 7.5 times greater; the final stock will contain 300 micrograms or 85 Curies of niobium-93m, which will undoubtedly be the largest source of niobium-93m ever produced.

Table 1. Radioisotopic composition of niobium from LANSCE targets.

Isotope	Number of Atoms	Approx. mass
94Nb	3.60×10^{17}	56 micrograms
93mNb	1.26×10^{17}	20 micrograms
91Nb (680y isomer)	1.66×10^{18}	250 micrograms
91Nb (62d isomer)	$<4 \times 10^{17}$	

Separating niobium from LANSCE targets has taken much longer than we anticipated because of budget cutbacks, difficulties in radioactive handling, and the Cerro Grande fire. The separation and preparation of nuclear isomer crystals of niobium-93m will continue after the end of this project with other funding.

High-Energy Cosmic Transients

98042

Todd Haines

Milagro is the world's first water-Cherenkov air-shower detector. As such, it has unique properties for the observation of transient events from the cosmos—a very wide field of view and low energy threshold. The subject of this project was research on these transients with data from Milagrito, a prototype phase of the experiment that had somewhat reduced capabilities compared with Milagro.

We had two major achievements on the project this year. Milagrito had observed two high-energy cosmic transients. The first was a signal from gamma-ray burst (GRB) 970417a. GRBs have not been observed at energies above about 10 GeV. Thus, establishing a lower limit on the energy of these events is of utmost importance. We have shown that these events were indeed new world-records in energy, with the lowest energy being above 300 GeV and several of them in the 700–800 GeV region. Such high-energy events will be difficult for models of GRBs to predict.

The second accomplishment was an analysis searching for “untriggered” bursts from anywhere in the sky. Because the BATSE gamma-ray burst detector observed only approximately one-half of the sky at any time, many GRBs went undetected. Moreover, it is possible for a new type of source to produce a burst of $\sim$ TeV gamma rays, with little or no emission at lower energies. The search looks for a short-lived signal above the cosmic-ray background from any place in the sky at any time and of duration from $\sim$ seconds to hours. We observed no other (besides 970417a) statistically significant signal.

Publications

Leonor, I., et al., “Searching for High-Energy Emission from Gamma-Ray Bursts” (accepted in *Astrophys. J.*).

Weak Interactions at Low Energy

99045

Jim Friar

Weak interactions are one of the four fundamental forces in nature (e.g. they cause beta decay). Over the past several years, a number of nonnegligible but still marginal inconsistencies have developed between weak-interaction experimental results and theoretical expectations derived from the Standard Model (SM). The SM describes all of our current understanding of elementary particles. Our goal is to examine these inconsistencies for corrections and explanations within the SM and for implications for additional interactions beyond the SM.

We are attacking in five areas where there may be some inconsistency or where significant experimental progress is expected in the near future. These involve radiative corrections to super-allowed beta decay, tritium beta decay, T(time-reversal)-even observables in neutron and nuclear beta decay sensitive to non-SM interactions, parity-violating nucleon-nucleon scattering, and CP- and T-violation. The first three areas are very closely related, as the new interactions may be the source of the unitarity violation. The fourth relates to a more general test of the overall scheme, while the fifth depends on the details of any non-SM interactions.

We have investigated the electric dipole moment of the electron and of the neutron in the unconstrained minimal supersymmetric standard model. We have shown that one-loop contributions from the R-parity-violating interactions are absent without the participation of either sneutrino-antisneutrino mixing or of Majorana-neutrino mass terms.

We developed a pseudo-Dirac neutrino mass matrix based on a combination of theory (quark-lepton symmetry) and phenomenology that is consistent with all current neutrino mass and oscillation experiments. We predict shorter baselines for flavor oscillations such as found by the Liquid Scintillator Neutrino Detector experiment, but longer baselines for oscillations into sterile neutrinos, such as may be occurring for neutrinos from the Sun.

We successfully performed a critical test of the theory of super-allowed beta-decay nuclear corrections by guaranteeing that physical results are independent of the way the calculations are organized (gauge-invariance constraint). The form of this constraint also allows us to separate cleanly the radiative corrections into individual nucleon and nuclear corrections, the latter being new results.

During the past year, we have developed new computational algorithms to treat quantum low-energy scattering and applied them to the weak-interaction parity violation in polarized neutrons propagating in helium. Results show 30% differences from simple model extractions of parity-violating nucleon-nucleon coupling constants. We have initiated calculations to analyze all the few-nucleon parity-violating data to place the tightest possible constraints on the parity-violating nucleon-nucleon interaction.

Publications

Goldman, T., et al., "Implications of Quark-Lepton Symmetry for Neutrino Masses and Oscillations," *Mod. Phys. Lett. A* **15**, 439 (2000).

Herczeg, P., "CP-Violating Effects in the R-Parity Violating Minimal Supersymmetric Standard Model," in *Proceedings of the Second International Conference—Beyond the Desert—99: Accelerator, Non-Accelerator and Space Approaches into the Next Millennium* (Institute of Physics Publishing, Bristol, 2000), p. 125.

Herczeg, P., "P, T-Violating Electron-Nucleon Interactions in the R-Parity Violating Minimal Supersymmetric Standard Model," *Phys. Rev. D* **61**, 095010 (2000).

Stephenson Jr., G.J., et al., "Tritium Beta Decay, Neutrino Mass Matrices, and Interactions Beyond the Standard Model" (accepted in *Phys. Rev. D*).

Weak Interaction in Nuclei

99046

Anna C. Hayes

The main objective of this project is to improve understanding of weak interactions in nuclei by investigating and improving models for (1) fundamental parity and time-reversal symmetry violation in the nucleus and (2) neutrino-nuclear scattering.

If parity and time-reversal (PT) symmetry is violated in the nucleus, it would be manifested through a nuclear Schiff moment. A Schiff moment can occur when an opposite parity level is admixed into the nuclear ground state by a PT-violating nucleon-nucleon interaction. We investigated the nuclear structure required for enhancing the nuclear Schiff moment and have shown that, contrary to naive expectations, the giant dipole resonance makes almost no contribution. We found strong correlation between states with large octupole strength and states with large Schiff strength. Thus, most of the strength determining Schiff moments in the nucleus lies at low excitation energy. The largest enhancement of Schiff moments is expected for octupole-deformed nuclei. However, we have shown that strong octupole vibrations also enhance Schiff moments. Thus, we expect plutonium-239, for example, to be enhanced to within a factor of 10 of the octupole-deformed nucleus of radium-225.

As the core of a massive star collapses to form a neutron star, neutrinos of all flavors are produced, with a significant flux up to energies of 100 MeV. Synthesis of the light elements lithium, beryllium, and boron in a supernova involves spallation of these neutrinos, primarily from carbon. Determining the key neutrino cross sections involved in neutrino spallation requires a detailed understanding of the underlying nuclear physics reactions; therefore, we examined the nuclear structure issues involved in all neutrino reactions measured to date.

The cross sections we analyzed include (a) those involved in solar neutrino detectors; (b) those involved in accelerator-based neutrino oscillation searches at the Liquid Scintillator Neutrino detector (LSND) and in the United Kingdom; and (c) those determining the interaction of atmospheric neutrinos with oxygen in the Kamiokande neutrino detector in Japan. We found the neutrino-carbon cross section from decay-in-flight neutrinos at LSND to be the most sensitive to the nuclear physics model used. The neutrino energies involved in supernova neutrino nucleosynthesis are similar to, though lower than, the neutrino energies at LSND.

Publications

Engel J., et al., "Nuclear Octupole Correlations and the Enhancement of Atomic Time-Reversal Violation," *Phys. Rev. C* **61**, 35502 (2000).

Hayes, A.C., and I.S. Towner, "Shell Model Calculations of Neutrino Scattering from 12-C," *Phys. Rev. C* **61**, 044603 (2000).

Hayes, A.C., and L. Zanini, "Systematic Studies of P-violation in (n, γ) Reactions on Compound Nuclear Systems," in *Capture-Ray Spectroscopy and Related Topics*, Stephen Wender, Ed., AIP Conf. Proc. **529**, 555 (2000).

Tomsovic, S., et al., "Statistical Theory of Parity Nonconservation in Compound Nuclei," *Phys. Rev. C* **62**, 054607 (2000).

Exact Solutions of Quantum Gauge Theories from String Solitons

99047

Michael Mattis

This project was intended to uncover the relationship between the collective dynamics of extended solitons in string theory and supersymmetric gauge theories. We found a far-reaching relationship between semiclassical effects in field theory, which fall under the heading of instanton physics, and effects in string theory involving extended solitons, or branes. Our work with instantons has provided a convincing piece of evidence in favor of Maldacena's Conjecture. We have shown how the rather unusual construction of instantons known as the Atiyah-Drinfeld-Hitchin-Manin (ADHM) construction arises very naturally from the dynamics of branes. Along the way, we overcame most of the technical difficulties encountered with the ADHM construction—namely, the resolution of the nonlinear constraints and the construction of a volume form.

The most important development in field theory in many years is the representation of gauge theories (the theories that describe the interactions of quarks and gluons) in terms of a string theory. The idea is that in regions of parameter space where conventional calculational techniques, for instance Feynman diagrams, are found wanting, there is a new and apparently very different, tractable way to formulate the theory. To represent a certain class of supersymmetric gauge theories in terms of string theory requires a ten-dimensional string theory defined on a particular background: the product of five-dimensional anti-de Sitter space and a five sphere. This duality is known as the anti-de Sitter conformal field theory (AdS/CFT). The original goal of our project, to investigate various links between the dynamics of solitons in string theory and semiclassical methods in field theory, has been fulfilled in the context of the AdS/CFT correspondence. It has been acknowledged among the leaders of this field/string theory revolution that our innovative calculations have provided some of the best evidence for the AdS/CFT correspondence.

Previous to our work, there had been little or no use of the ADHM construction of instantons in physics. We wanted to make use of this important calculus that has had no application because of its inherent difficulties. We recognized that the rather arcane ADHM instanton calculus can be naturally described in the language of string theory solitons—a major achievement. The mysterious parameters

of the ADHM constructions are then nothing more than the collective coordinates of string theory solitons, so-called D-instantons, moving in a background of D3-branes. We developed instanton calculus to a level where we can exactly calculate effects with arbitrary numbers of instantons. We can now capture effects of instanton configurations that cannot be thought of as a dilute gas of single instantons. Although developed for supersymmetric theories, this calculus can also be applied to quantum chromodynamics.

Publications

Davies, N.M., et al., "Gluino Condensate and Magnetic Monopoles in Supersymmetric Gluodynamics," *Nucl. Phys. B* **559**, 123 (1999).

Hollowood, T.J., "Instantons, Finite $N = 2$ $Sp(N)$ Theories and the AdS/CFT Correspondence," *Journal of High Energy Physics* (available online, <http://jhep.cern.ch>, 1999).

Hollowood, T.J., and V.V. Khoze, "ADHM and D-Instantons in Orbifold AdS/CFT Duality," *Nucl. Phys. B* **575**, 78 (2000).

Hollowood, T.J., et al., "Breakdown of Cluster Decomposition in Instanton Calculations of the Gluino Condensate," *Nucl. Phys. B* **570**, 241 (2000).

Hollowood, T.J., et al., "Instantons in $N = 4$ $Sp(N)$ and $SO(N)$ Theories and the AdS/CFT Correspondence" (accepted in *Adv. Theor. Math. Phys.*).

Hollowood, T.J., et al., "Summing the Instanton Series in $N = 2$ Superconformal Large- N QCD," *Journal of High Energy Physics* (available online, <http://jhep.cern.ch>, 1999).

Development of Detectors and Electronics for the Study of the Beta Decay of Polarized Neutrons at LANSCE

99048

W. Scott Wilburn

Precise measurements of the neutron beta-decay correlations (A, B, a, and b) provide important tests of the standard model of electroweak interactions. At the Los Alamos Neutron Science Center (LANSCE), we are designing an experiment to measure all four correlations with a level of accuracy an order of magnitude better than that of existing measurements.

Previous experiments were limited by systematic effects associated with neutron polarization measurement, backgrounds, and detector efficiencies. However, our experimental design relies on three technological advances: pulsed cold-neutron beams, helium-3 neutron polarizers, and large-area silicon detectors with very thin dead layers. LANSCE provides the only pulsed cold-neutron beam dedicated to nuclear physics. The pulsed nature of the LANSCE beam combined with a helium-3 neutron polarizer (developed at the Laboratory) makes it possible to determine the neutron polarization with unprecedented accuracy. Large-area silicon detectors promise a number of improvements that include almost-perfect efficiency, high uniformity, good energy resolution, position information, and the ability to detect the electron and the proton from neutron decay.

Very thin dead-layer silicon detectors capable of detecting the low-energy protons are available commercially. We have constructed an apparatus for measuring detector dead layers, using 3.2-MeV alpha particles. With this apparatus, we have measured the dead layers of sample detectors and have obtained a value of 56 ± 13 nm. This dead layer corresponds to losing only 5 keV for 30-keV incident protons. These detectors, however, have intrinsically high-contact resistances, which cause long signal rise times and make it impossible to achieve a timing resolution of a few nanoseconds. We have worked with the manufacturer on two new designs (with lower distributed resistance) that will solve this problem and have tested sample detectors. Applying a thin (<25 nm) layer of aluminum over the silicon appears to solve the resistance problem.

With this project, we are proving the feasibility of using silicon detectors to measure the neutron beta-decay correlations. The key characteristics of the detector include a large area, a very thin dead layer, fast timing, and position resolution. Once a detector with these properties is developed, we will be ready to design and construct the full experiment. This experiment will contribute to maintaining the Laboratory's core competency in nuclear science.

Publications

Wilburn, W.S., et al., "A New Approach to Measuring the Neutron Decay Correlations with Cold Neutrons at LANSCE," in *Proceedings of the 2000 Conference on Physics with Pulsed Neutron Beams* (World Scientific, River Edge, NJ, in press).

The Search for Dark Matter

99049

Salman Habib

There is strong indirect evidence that mass in the universe is dominated by a component which, apart from its gravitational effects, does not interact with ordinary matter. This unidentified component is referred to as “dark matter.” This project is a joint experimental and theoretical effort exploring possibilities for the detection of one type of dark matter in the solar system, the weakly interacting massive particles (WIMPs).

There are three components to the project: direct detection using silicon(lithium) [Si(Li)] detectors at the Waste Isolation Pilot Plant (WIPP), indirect detection with the MILAGRO Gamma-Ray Observatory, and related theoretical support. Direct detection of WIMPs is possible by observing their elastic scattering from nuclei; indirect detection efforts look for high-energy photons produced when two WIMPs annihilate. Theoretical efforts include calculation of relevant interaction cross sections and the distribution of WIMPs in the solar system. Our work has two goals: to characterize backgrounds at WIPP as a possible location for a large dark matter experiment and to measure both the external and internal backgrounds in large Si(Li) detectors with the idea of installing an array of them as a dark matter detector at WIPP.

The direct detection effort has achieved stated goals up to this time, including the outfitting of the counting room at WIPP and characterization of background signals. Work continues on controlling the identified problem with high-voltage surface discharge in the detectors. We have made differential shielding measurements with both a hyperpure germanium detector and Si(Li) detectors. These results allowed us to characterize the gamma ray and fast neutron backgrounds at WIPP.

We have also made substantial progress on the indirect detection effort. MILAGRO is taking data, and the initial sensitivity study has been completed. Work on detailed input from the theory component regarding structure in the WIMP distribution near the Sun is in progress. Theoretical work is continuing, with focus on developing an appropriate Monte Carlo method for calculation of the WIMP distribution in the solar system. We have written and tested a high-resolution galactic dynamics code that will be used for modeling the dark matter distribution in the solar neighborhood.

Improved Matching of Lattice and Continuum QCD

99051

Tanmoy Bhattacharya

Quantum chromodynamics (QCD), the theory of strong interactions, provides a first-principles way of nonperturbatively determining the properties of hadrons by calculating the matrix elements of various operators between hadronic states. Precise estimates of these matrix elements are essential to interpreting the experiments being conducted at such DOE experimental facilities as the Fermi National Accelerator Laboratory, the Brookhaven National Laboratory, and the Stanford Linear Accelerator Center. However, the large size of the coupling constant involved makes QCD at the hadronic scale not amenable to perturbative analysis. Consequently, nonperturbative methods like lattice simulations are essential.

In this project we are developing techniques to reduce the discretization errors inherent in such lattice simulations and also to determine the renormalization constants necessary to convert from the lattice results to the continuum. In particular, we are determining the improvement and renormalization constants for the Wilson fermion bilinear operators by using two different methods: (1) applying chiral Ward identities, and (2) using quark states in a fixed-gauge background. Finally, we are studying short-distance, two-point functions and their suitability for providing yet another determination of these constants.

This year, using the Ward identity method, we completed the calculation of the scale invariant renormalization and improvement constants for the fermion bilinears at $\beta=6.2$. We compared this calculation to previous results as well as to perturbation theory. This project is the first complete study of the improvement constants and their scale dependence. Our main results show that perturbation theory typically underestimates the renormalization and improvement constants, thereby indicating large, two-loop corrections and higher-order discretization effects. Perturbation theory seems especially ineffective for the ratio of pseudoscalar to scalar renormalization constants, but the Ward identity method can not determine whether it fails for the scalar, the pseudoscalar, or for both the renormalization constants.

In addition, we have begun to analyze the efficacy of the Ward identity method by using external quark states in a fixed gauge. The advantage of this method is that it makes possible the calculation of scale-dependent quantities, such as the scalar and pseudoscalar renormalization constants, separately.

Publications

Bhattacharya, T., et al., “Order a Improved Renormalization Constants” (accepted in *Phys. Rev. D*).

Bhattacharya, T., et al., “Renormalization Constants Using Quark States in Fixed Gauge,” (in *Proceedings of the XVIII International Symposium on Lattice Field Theory* (Elsevier Science Publishing Co., Inc., New York, in press)).

Fundamental Symmetries with Trapped Atoms

99052

Andrew Hime

We are working to exploit magnetically trapped rubidium-82 in a new generation of fundamental symmetry experiments. Rubidium-82, a pure and allowed Gamov-Teller (GT) beta-decay nucleus, has the appropriate atomic structure and lifetime to be manipulated and confined in magnetic and optical traps. We are mounting a prototype experiment to measure the positron-spin correlation coefficient from polarized rubidium-82 in a magnetic time-orbiting-potential (TOP) trap. In this case, an essentially massless source of polarized species is confined to a highly localized cloud. We can exploit the pointlike geometry of such a source, together with a “rotating” nuclear polarization vector, to measure the positron-spin correlation as a continuous function of positron energy and emission angle in a single and fixed positron detector. This program exploits a number of unique opportunities at Los Alamos to study fundamental symmetries of the weak interaction at a new level of precision.

This year our experiment has met with enormous success. We have demonstrated trapping of some millions of rubidium-82 atoms in a magneto-optical trap and the efficient transfer of these atoms to a TOP trap. We have measured, for the first time, the positron-nuclear spin correlation function continuously, and on an event-by-event basis, in terms of the positron energy and direction relative to the nuclear orientation (see Fig. 1). The differential energy spectrum and angular distribution are as expected for a pure and allowed GT decay and demonstrate the feasibility for pushing the experiment into a new frontier of precision to study further the origins of parity violation in the weak interaction.

Publications

Crane, S.G., et al., “Parity Violation Observed in the Beta Decay of Magnetically Trapped ^{82}Rb Atoms” (accepted in *Phys. Rev. Lett.*).

Fig. 1. ^{82}Rb beta decay data accumulated over a period of six hours. (a) The angular distribution obtained after binning the events as a function of positron-nuclear spin angle and integrated over positron kinetic energy above a threshold of 800 keV. The solid curve results from a cosine fit to the distribution, whereas the nonzero amplitude results from parity-violation and indicates the successful confinement and polarization of ^{82}Rb atoms in the TOP trap. (b) The differential positron kinetic energy spectrum obtained after integrating out the angular degree of freedom. The solid curve results from detailed Monte Carlo simulations that account for the full decay scheme for ^{82}Rb decay and the details of the positron detection optics. The spectrum departs from a pure positron signal at low energy because of Compton scattering of 776-keV gamma rays from the 2^+ state of the ^{82}Kr daughter nucleus.

CP Violation in Kaon Decays: Epsilon and Epsilon'/Epsilon

2000048

Rajan Gupta

Charge conjugation and parity (CP) violation is a subtle feature of the Standard Model. It implies that particles and antiparticles behave differently in their interactions with matter. In 1964 Cronin and Fitch discovered CP violation in the neutral kaon system; they showed that a tiny fraction of the time the long-lived state (K-long) decayed into two pions, which are characteristic of the K-short state. This CP violation could be explained by an interaction solely between the K^0 particle and its antiparticle ($\bar{K}^0$). Recently, however, the Kaons at the Tevatron collaboration at Fermi National Accelerator Laboratory confirmed direct CP violation in the kaon decays: ϵ'/ϵ is nonzero and much larger than the theoretical predictions of the Standard Model. The largest theoretical uncertainty comes from the estimate of the strange quark mass and quantum chromodynamic (QCD) corrections to weak-matrix elements. The most promising method for significantly reducing these uncertainties is lattice QCD. Our goal is to develop the remaining numerical and theoretical techniques and carry out the numerical simulations that will yield these quantities.

We made significant progress this year in the theoretical calculations of the renormalization constants needed to define the quantum operators and in code development for implementing the simulations as described below. The calculation of ϵ' requires using a lattice discretization of the Dirac action that respects chiral symmetry. Staggered fermions are one such scheme. However, it was shown some years ago that the simplest transcription of the effective Hamiltonian describing weak interactions has very large perturbative corrections and that the associated calculations were unreliable. We have developed improved operators that have smaller corrections; we are completing the one-loop perturbative calculations of the matrix that specifies the mixing between them.

On the numerical side, we had to find computing resources outside the Laboratory for the calculations. Toward this end, we entered into the Lattice QCD collaboration at Columbia University and will use their special-purpose computer, which has a unique operating system and communication protocols. We learned to use the machine and developed the software for the calculation. In addition, we finished developing code for calculating the two-point correlation function (from which the spectrum can be extracted) and the simpler four-fermion matrix elements. We anticipate completing all the code development and the necessary theoretical calculations by the end of the fiscal year.

Test of Big Bang Nucleosynthesis Models by Precision Measurement of the $n+^1\text{H}\rightarrow^2\text{D}+\gamma$ Cross Section

2000049

Stephen Wender

Scientists are continually refining ways to more accurately predict the abundance of the light elements believed to have been formed at the beginning of the universe — during the big bang. By studying collisions of subatomic particles, we can better understand what happened in the initial explosion.

The goal of our project is to test the consistency of big bang nucleosynthesis models by measuring the cross section for the reaction $n+^1\text{H}\rightarrow^2\text{D}+\gamma$ (neutron capture on hydrogen forming deuterium and a gamma ray) more precisely than has been done before. The primordial abundance of deuterium has recently been measured with an accuracy of 7%. The major uncertainty in the determination of the baryon density in the early universe is the cross section for the formation of ^2D . Our measurement, which will have an uncertainty of 3%, will make the uncertainty in big bang nucleosynthesis due to the $n+^1\text{H}\rightarrow^2\text{D}+\gamma$ cross section negligible.

We studied the reaction by placing a polyethylene target containing both hydrogen and carbon in the pulsed neutron beam at the Los Alamos Neutron Science Center's Weapons Neutron Research facility. The emitted gamma rays were observed with a high-purity germanium detector. We used the $^{12}\text{C}(n,n')^{12}\text{C}$ (inelastic neutron scattering) reaction as a reference.

Because of the high background radiation, it is difficult for us to extract data on the reaction we're studying. To reduce the problem, we experimented with the shielding around the germanium detector and by using an active shield that will reduce background counts under the peak of interest. We also changed the proton beam characteristics to maximize the neutron capture reaction on hydrogen.

So far, we have been unable to extract a cross section for the reaction, but we have been able to extract a relative cross section for the $^{12}\text{C}(n,n')^{12}\text{C}$ reference reaction. Our results are shown in Fig. 1, compared with a previous measurement. The reference reaction is approximately 5,000 times more intense than the $n+^1\text{H}\rightarrow^2\text{D}+\gamma$ reaction. With more data, we should be able to obtain a result for the reaction of interest. We are purchasing a more efficient detector capable of handling a very high count rate. We are also getting an active shield for the new detector and changing the experimental arrangement to minimize the background radiation.

Publications

Seabury, E.H., et al., "Precision Measurement of the $n+p\rightarrow d+\gamma$ Cross Section for Testing Big-Bang Nucleosynthesis Models," Los Alamos National Laboratory report LA-UR-00-3022 (to be published in *Proceedings of the International Conference on the Applications of Accelerators in Science and Industry CAARI 2000*).

Fig. 1. The current measurement of the $^{12}\text{C} (n,n')^{12}\text{C}$ reaction cross section compared with a previous measurement.

Precision Analysis of Parity-Nonconserving Weak Coupling Constants

2000050

Benjamin Gibson

Parity nonconservation (PNC) in the nuclear force can be described in terms of meson-exchange weak coupling constants. Values extracted from nuclear PNC experiments appear inconsistent with current expectations arising from fundamental knowledge of weak interactions. Our goals are (a) to develop improved nuclear PNC models and examine unexplored nuclear medium effects and (b) to test limits of model dependence of the weak pion-exchange coupling constant extracted from the photon asymmetry in PNC polarized neutron radiative capture by a proton and in fluorine-18 PNC gamma transitions. Model dependence in moving from the two-nucleon system to many-body systems is a key issue. The Los Alamos effort to measure such neutron-proton radiative capture and the Laboratory's computational resources play key roles. Theoretical analysis is also crucial, making the Laboratory the appropriate institution to undertake this investigation. If successful, the research will advance understanding of weak interactions and high-performance computing in nuclear science.

The small, weak PNC coupling constants extracted from $A \approx 18$ nuclei are difficult to account for in either quark-based models or chiral Lagrangian-based models. This leads us (a) to calculate the effects of charge dependence in many-body matrix elements on the photon asymmetry and circular polarization in the γ decays of parity-mixed levels in fluorine-18 and (b) to calculate one-meson-exchange contributions to the $\bar{n} + p$ radiative capture process to explore limits upon the theoretical uncertainty in the calculated photon asymmetry. To facilitate calculation (a), we have developed the first statistical shell model to explore the root-mean-square value of the parity-nonconserving interaction matrix elements in heavy nuclei. We have also demonstrated that the parity-violating weak pion-coupling constant extracted from measurements on fluorine-18 is considerably more model dependent than previously thought. To facilitate calculation (b), we developed a working code to calculate radiative transitions in the neutron-proton continuum (np bremsstrahlung) at energies above the threshold for np radiative capture; developed a working code to calculate parity-

nonconserving amplitudes, which are due to the weak interaction, in the neutron-proton continuum at energies above the np radiative capture threshold; and initiated development of a code to calculate the deuteron wave function, including parity-nonconserving amplitudes that are due to the weak force in the nuclear Hamiltonian.

Publications

Hayes, A.C., and Luca Zanini, "Systematic Studies of P-Violation in (n,γ) Reactions on Compound Nuclear Systems," *Capture Gamma-Ray Spectroscopy and Related Topics*, Stephen Wender, Ed., *AIP Conf. Proc.* **529**, 555 (2000).

Tomsovic, S., et al., "Statistical Theory of Parity Nonconservation in Compound Nuclei," *Phys. Rev. C* **62**, 054607 (2000).

SQUIDs as Sensors to Measure the Neutron Electric Dipole Moment

2000052

Michelle A. Espy

Our project provides research for a novel experiment that will measure the neutron electric dipole moment (nEDM) with sensitivity 250 times greater than current experimental limits, within reach of the big bang theory of the matter/antimatter asymmetry in the universe and predictions from grand-unified supersymmetric theories. Key to the experimental design is understanding whether or not superconducting quantum interference device (SQUID) sensors can detect the precession frequency of the helium-3 used as polarizer, spin analyzer, and detector for the neutrons. SQUIDs would dramatically reduce the dominant source of experimental systematic error. The experiment requires a novel use of SQUIDs. In this project we are evaluating the required aspects of their performance. Preliminary work has already demonstrated required noise performance. The nEDM measurement brings an experiment of recognized scientific importance to Los Alamos. In addition, the scientific impact of the SQUID work benefits the larger SQUID community and the biological and weapons projects at the Laboratory.

Our approach is to test the SQUIDs under the same conditions found in the final experiment, including noise tests as a function of temperature from 0.3 K to 10 K. Insights into the behavior of SQUIDs with temperature will benefit all our SQUID projects. We are conducting studies of experimental noise sources in the superconducting vessel. These studies include tests of materials, induction coil design, and the effects of leakage current. When beam is available, we will place SQUIDs in the experimental area to study the environmental noise and radiation. We will then incorporate the SQUIDs into the existing cryostat. In addition, we will study the SQUIDs' capability for detecting the helium-3 precession.

We have located a cryostat to perform the tests of SQUID noise as a function of temperature. A probe to couple to this system is currently being fabricated. We have the required temperature sensors and SQUIDs, and we are collaborating with others involved in the experiment to identify and resolve design issues affecting the SQUIDs. At present, we are participating in neutron tomography at the Manuel Lujan Jr. Neutron Scattering Center to test the experimental cryostat and the distribution of helium-3 in the target.

Publications

Espy, M.A., et al., "Superconducting Quantum Interference Devices (SQUIDs) as Detectors in a New Experiment to Measure the Neutron Electric Dipole Moment," *IEEE Trans. Appl. Supercond.* **9** (2), 3696 (1999).

Low-Energy Solar Neutrino Spectroscopy

2000053

Thomas Bowles

Despite the extensive efforts of the past thirty years, the number of solar neutrinos observed falls significantly short of that predicted by the Standard Solar Models. A direct measurement of the dominant p-p low-energy solar neutrinos is crucial to resolve this problem. Low-Energy Solar Neutrino Spectroscopy (LENS) appears to be the only technique likely to yield this measurement.

For the LENS experiment to be successful, we must be able to observe the initial neutrino interaction in a ytterbium-loaded scintillator followed by a delayed-coincidence 72-keV gamma ray with a half-life of 50 nanoseconds. It is essential that the scintillator produce the highest-possible light output in a time that is short relative to 50 ns. In addition, the detector must collect as much light as possible. Finally, we must develop the pulse-fitting techniques that allow us to search for and separate delayed-coincidence signals.

To study these issues, we constructed a test cell and an electronics system to measure scintillator samples. We record the entire pulse waveform of the signals from the scintillator, which allows us to see if the shape is consistent with delayed coincidence. We have taken data with different scintillators and are analyzing it to select the best one. We have also modeled the optical performance of two possible configurations for LENS: an array of scintillator modules that are 50 cm $\times$ 50 cm $\times$ 400 cm long and a single sphere of scintillator modules. In general, we concluded that we prefer a spherical design if the scintillator is highly transparent to the scintillation light. At present, the attenuation length in various scintillator samples is only approximately 2 meters, thus indicating that the detector will need to have a modular design. The LENS project is working to improve the scintillator's transparency, and we will fix the detector design after we determine the maximum transparency that we can achieve.

LDRD Project Data for FY 2000

Legend to Program Authorization Area

Code	Program Authorization Area
WA	Weapons Activities
ODA	Other Defense Activities
ER&WM	Environmental Restoration and Waste Management
WFO/DoD	Work-for-Others from the Department of Defense
Other	Department missions other than national security

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER & WM	WFO/DoD	Other
98001	100	Artificial Atoms Probed by Femtosecond Pulses: Evolution of Optical Properties during the Bulk-Atomic Transformation	X				
98002	103	Laser-Plasma Interactions in Diffraction-Limited Beams	X	X	X	X	X
98003	104	Stochastic Resonance in Arrays with Tunable Nonlinearity and Coupling		X		X	X
98005	117	Noninvasive Techniques for Genetic Analysis					X
98006	118	Rapid Genotyping Assay for Beryllium Disease Susceptibility					X
98008	119	Next Generation of Molecular Dynamics: Implicit Solvent/Langevin Models for Folding of Peptides and Proteins					X
98011	120	Fundamental Processes in Polymer Light-Emitting Electrochemical Cells	X	X	X	X	X
98012	137	Unraveling Heterogeneous Surface Reaction Kinetics	X	X	X		X
98013	138	Soluble Polymers for Enhancing Biocatalysis			X	X	X
98014	168	Use of Metallic Glasses in Ceramic-Metal Joining	X		X		X
98015	169	Development and Engineering of the Ion-Cut and Low-Temperature Direct-Bonding Process	X	X	X		X
98016	170	Pulse Shaping in Explosive-Pulsed-Power Systems	X	X		X	X
98017	171	Acoustic-Network Refrigerators					X
98018	192	Lightning in the Atmosphere and in the Solar Nebula		X			X
98019	193	High Pressure Crystal Chemistry of Hydrated Minerals	X		X	X	X
98020	196	New Windows on Gamma-Ray Bursts	X	X			X
98021	198	Advanced Computational Analysis of Disordered Materials and Clay Minerals			X		X
98022	200	Tsunami from Asteroid and Comet Impacts		X			X
98023	201	A Large-Aperture, Wide-Angle Air Cerenkov Telescope				X	X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
98024	202	A New Method for Modeling Wave Propagation in Strongly Heterogeneous Media: Applications to Seismic Wave Propagation in the Earth		X	X		X
98027	220	An Integrated Solid-State Optical Device with High Speed Scanning, Variable Focusing, and Frequency Doubling Capabilities	X	X	X		X
98028	221	Cryptographic Key Generation Using Long-Baseline Radio Interferometry	X	X		X	X
98029	273	Efficient Multilevel Iterative Methods for Nonlinear PDEs	X	X			X
98030	274	Extending the Theory of Resonant Perturbations to Partial Differential Equations, with Applications to Nonlinear Optics	X	X		X	X
98031	275	Invariant Discretization for Computational Gas Dynamics	X	X			X
98032	276	Unitary Symmetry, Discrete Mathematics and Combinatorics	X	X			X
98034	238	Unusual Metal Behavior in Taylor Microwires	X	X	X	X	X
98035	239	Bulk Ferromagnetic Metallic Glasses	X	X		X	X
98036	242	Unconventional Superconductivity and Violation of Time-Reversal Invariance	X	X	X	X	X
98037	245	New Vortex Phases in Irradiated High-Temperature Superconductors	X	X	X	X	X
98038	289	Exploring and Testing the Standard Model and Beyond	X				X
98039	290	Determination of the Neutron Lifetime and Ultracold-Neutron Source Development	X	X			X
98040	291	Parity Nonconservation in the Reaction $n + p = d + \gamma$	X	X			X
98041	292	A Search for Superradiant Emission in a Nuclear Isomer Crystal					X
98042	293	High-Energy Cosmic Transients					X
98601	60	Advanced Nuclear Measurements Science		X	X		X
98602	31	A New Paradigm in Separations: Molecular Recognition Membranes			X		X
98603	33	Condensed Phase Kinetics and Reduced Reaction Mechanisms of Energetic Materials	X			X	X
98604	47	Coupled Environmental Modeling		X	X		X
98605	95	Nonequilibrium Science: Assessment, Control, and Prediction	X		X	X	X
98606	96	Ultracold Neutron Science	X	X			X
98805	81	Discrete Simulation of Nonlinear Systems	X	X	X	X	X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
98806	83	Probabilistic and Combinatorial Analysis for Biological Systems					X
98817	63	Investigation of Spin, Charge, and Lattice Degrees of Freedom in Magnetoresistive Materials	X	X	X	X	X
99001	105	Create and Study Quantum Degenerate Systems		X			X
99002	106	Dynamical Stability and Quantum Chaos of Ions in a Linear Trap		X			X
99003	107	Quantum Coherence and Decoherence: Trapping a Schrödinger Cat	X	X		X	X
99004	108	Quantum Feedback Control: Methods and Applications		X		X	X
99005	109	Direct Observation of Individual, Optical Energy-Transfer Events	X	X		X	X
99006	121	Computational Studies of the Role of Water Fluctuations in Protein Dynamics and Folding		X			X
99007	122	The Molecular Aging Clock		X			X
99008	123	Hyperthermophile Biocatalysis: The Molecular Basis of Enzyme Stability and Activity	X		X		X
99009	124	New Approaches to High-Throughput DNA Sequence Validation	X	X		X	X
99010	125	Development of a Superconducting Quantum Interference Device (SQUID) Microscope for Imaging Cortical Neuronal Columns	X	X		X	X
99011	126	Rapidly Photocleavable Caged Proteins	X	X			X
99012	139	Alkane Chemistry of Ligated (Allyl)Iridium Moieties on Metal Oxide Supports and Multilayer Hydrogen Transport Membranes	X		X	X	X
99013	141	Novel Surfactants and Micellar Chemistry for Enhanced Reactivity and Separations			X		X
99014	144	Supported Technetium Chemistry	X	X	X		X
99015	145	Nonadiabatic Processes in Chemical Reactions			X		X
99016	147	Description of Complex Adsorption from a Simple Equation of State	X	X	X		X
99017	172	Use of Directed-Light Fabrication for Fabricating Functionally Gradient Materials	X	X	X	X	X
99018	175	Composite Films Made with Metallic Carbon Nanotubes	X			X	X
99019	178	Highly Constrained Bandwidth Combinational Algorithm for Transmission of Speech (HC-BATS)	X	X		X	X
99020	179	Hydrogen Storage in Intermetallic Alloys	X	X	X	X	X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
99021	181	Next-Generation High-Power Microwave Source				X	X
99022	203	The Genesis and Evolution of Basalt on the Moon		X			X
99023	204	Sky Patrol Analysis with Robotic Optical Transient Search Experiment	X	X			X
99024	205	Galactic Magnetic Fields: Their Origin and Manifestation in Accretion Disks Around Supermassive Black Holes	X	X			X
99025	206	Multiscale Physics of Multiphase Flow in Porous Media	X	X	X	X	X
99026	207	Antarctic Circumpolar Wave and El Niño			X		X
99027	208	Low-Energy Neutral Atom Imaging: Watching Magnetospheric Dynamics	X	X			X
99028	211	Galaxies and Large-Scale Structure in a Universe with a Cosmological Constant	X				X
99029	222	X-ray Refractive Optics for Astrophysics and Nonproliferation	X	X			X
99030	224	Time-Resolved Photon Migration Tomography and Spectroscopy	X	X	X	X	X
99031	227	Integrated Optical Biosensor	X	X		X	X
99032	228	High Quantum Efficiency, Silicon-Integrated, Tunable-Band-Gap Infrared-Detection Devices Based on Rhenium Molybdenum Silicide	X	X	X	X	X
99033	230	Electron Tunneling Spectroscopy of Buried Interfaces	X	X	X	X	X
99034	277	Statics and Dynamics of Granular Media	X	X	X	X	X
99035	280	Quantum Physics Algorithms	X	X			X
99037	281	New Dispersive Models of Fluid Turbulence	X			X	X
99038	282	New Perspectives in Mathematical Modeling of High Bit-Rate Optical-Fiber Telecommunications	X			X	X
99040	246	Novel Approaches to Low-Temperature Thin-Film Materials Chemistry: Kinetic Energy Activated Molecular Beam Epitaxy	X	X	X	X	X
99041	248	Bulk Rapid Solidification	X	X	X	X	X
99042	251	Intrinsic Nonlinear Local Modes in Low-Dimensional Materials	X				X
99043	252	Organic Electronic Materials Under Intense Electrical Injection	X	X	X	X	X
99044	253	Investigation of Experimental Defect Interactions in Materials by Integrating Experimental Techniques with Large-Scale Simulations	X	X		X	X
99045	294	Weak Interactions at Low Energy	X				X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
99046	295	Weak Interactions in Nuclei	X	X			X
99047	296	Exact Solutions of Quantum Gauge Theories from String Solitons	X				
99048	297	Development of Detectors and Electronics for the Study of the Beta Decay of Polarized Neutrons at LANSCE	X				X
99049	298	The Search for Dark Matter	X				X
99051	299	Improved Matching of Lattice and Continuum QCD	X				X
99052	300	Fundamental Symmetries with Trapped Atoms		X			X
99500	19	Bioremediation Science to Meet National Challenges			X	X	X
99503	64	Self-Assembling Organic Electronic Materials	X	X		X	X
99505	10	Applications of Quantum Technologies		X		X	X
99506	20	Optical Biosensors		X		X	X
99507	66	Coordinated Synthesis, Characterization, and Modeling of Materials	X	X	X	X	X
99508	84	Nonlinear Complex Phenomena	X	X	X		X
99509	67	Development of Semiconducting Polymeric Films with High Concentrations of Boron	X	X	X	X	X
99510	44	Hard and Deeply Buried Target Defeat		X		X	
99511	49	Space Science and Exploration	X	X	X	X	X
99512	87	Quantifying and Reducing Uncertainty in Predictions of Complex Phenomena	X	X		X	X
99513	89	Management of Nuclear Warhead and Infrastructure Reduction	X	X		X	X
99514	98	Neutrino Physics Experiments	X				X
99515	90	Strategic Computing Applications	X	X	X	X	X
99516	21	Pathogen Detection in the Real World		X		X	X
99518	24	Functional Genomics		X		X	X
99519	70	Neutron and Accelerator-Based Science	X	X	X		X
99521	46	Nuclear Materials Management Systems for Proliferation Resistance, Environmental Protection, and Sustainability		X	X		
99522	12	High Power Microwave Science and Technology	X	X		X	X
99523	35	Cradle-to-Grave Carbon Management		X	X		X
99524	13	Next-Generation Sophistication in Defense and High Energy-Density Physics Exploratory Research	X	X	X	X	X
99529	25	The Identification of Proteins That Bind to Novel DNA Sequences/Structures		X			X
2000001	110	Optical Investigations of Quantum Information	X	X		X	X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
2000002	112	Cold Atom Fermion Interference	X	X	X		X
2000004	113	Ultrafast Dynamics of Laser-Plasma Interactions in Solids	X		X	X	X
2000005	114	Reconnection Scaling Experiment Transition from Resistive Magnetohydrodynamics to Collisionless Reconnection			X		X
2000006	115	Three-Body Atomic Recombination in Bose-Einstein Condensates					X
2000007	127	Universal Scaling Laws in Biology: Aerobic Metabolism, Energy Use and Longevity					X
2000008	128	Third-Generation Oligonucleic Acids	X	X			X
2000009	130	Coordination of Carbon and Nitrogen Metabolism			X		X
2000010	131	DNA Repair and Molecular Assembly Involved in Chromosome Condensation	X	X	X		X
2000011	132	Characterization of Exceptional Chromosomal Regions by DNA Sequencing					X
2000012	148	Plutonium Mediated Catalysis	X	X			X
2000013	149	Understanding and Controlling Micelles in Supercritical Carbon Dioxide	X	X	X	X	X
2000014	150	Synthesis and Characterization of High-Performance Propellants	X	X		X	
2000015	152	Anomalous Isotope Effects in Ozone Formation					X
2000016	153	Electron Transfer on the Vibrational Time Scale in Mixed Valence Systems			X		X
2000017	156	Data Structure and Computer Arithmetic for Quantifying Uncertainty	X	X	X	X	X
2000018	157	Extremal Optimization	X	X			X
2000019	160	Machine Learning	X	X		X	X
2000020	161	Combinatorial Optimization in Biology	X	X			X
2000021	163	A Computational Framework for Multiscale Shape Characterization and Recognition	X	X		X	X
2000022	165	Adaptive Superscalar Microprocessor Architecture	X	X	X		X
2000023	166	High-Performance TCP over the Next-Generation Internet	X	X	X	X	X
2000024	183	Improvement of Wear Resistance in Quenched and Tempered Steels by Cryogenic Treatment	X	X	X	X	X
2000025	184	Engineering of Plastic Artificial Muscles	X	X	X	X	X
2000026	187	Adaptive Femtosecond Pulse Delivery	X	X	X	X	X
2000027	188	A New Method for Cooling High-Frequency Conductors		X	X		X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
2000029	212	Nonlinear Dynamical Processes Involved in Earthquake-Induced Strong Ground Motion	X		X	X	X
2000030	213	Heat Flux Dissipation in Collisionless Space and Astrophysical Plasmas		X	X		X
2000031	214	Analysis of Large-Scale Structure in the Sloan Digital Sky Survey	X	X			X
2000032	216	Observing High-Energy Transients with Milagro	X	X			X
2000033	217	Optical and Chemical Studies of Sulfate Aerosols to Predict the Recovery of the Ozone Layer and Constrain the Earth's Radiation Budget			X		X
2000034	218	Tracer Tomography in Unsaturated Fractured Rock				X	X
2000035	219	Optical Refrigeration		X		X	X
2000036	231	The Nonlinear Elasticity Project	X	X		X	X
2000037	232	Direct Probing of Cloud Radiative Properties Using a Daytime Wide-Angle Imaging Lidar	X	X		X	X
2000038	235	Cumulative On-Orbit Magnetic Pointing and Attribution of Spread Signals	X	X		X	
2000039	255	Synthesis and Characterization of Superhard Materials	X	X	X	X	X
2000040	257	From Artificial Atoms to Artificial Solids: Soft-Matter Nanotechnology	X	X	X	X	X
2000041	260	Direct Observations of Individual Relaxation Modes in Polymers	X	X		X	X
2000042	261	Time Resolved Study of Martensitic Phase Transformations	X	X	X	X	X
2000043	262	In Situ Characterization and Failure Prediction of Composites	X			X	X
2000045	285	Effective Arbitrary Lagrangian-Eulerian Strategies			X		X
2000046	286	Direct Numerical Simulations and Stochastic Modeling in Ocean Dynamics	X		X		X
2000047	287	Rayleigh-Ritz Computation of Multitime Statistics	X	X		X	X
2000048	302	CP Violation in Kaon Decays: Epsilon and Epsilon'/Epsilon					X
2000049	303	Test of Big Bang Nucleosynthesis Models by Precision Measurement of the $n+^1\text{H}\rightarrow^2\text{D}+\gamma$ Cross Section	X				X
2000052	306	SQUIDS as Sensors to Measure the Neutron Electric Dipole Moment	X	X			X
2000053	307	Low-Energy Solar Neutrino Spectroscopy					X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
2000054	133	Studying the Spread of HIV Using Genetic Sequences		X		X	X
2000055	263	Modeling Complex Processes in Hard and Soft Materials	X		X		X
2000056	190	Study of the Secondary Flows in Thermoacoustic-Stirling Hybrid Heat Engines					X
2000057	266	Complex Behavior in Novel Correlated Electron Materials	X				X
2000058	267	Time-Resolved Fluorescence Emission from Biological and Electronic Materials		X		X	X
2000059	268	Investigations of Complex Deformation Behavior in Materials	X			X	X
2000060	191	Engineered Triple-Phase Boundary Gas Sensors	X		X	X	X
2000061	116	Macroscopic Quantum and Statistical Science		X			X
2000062	288	PREDICT	X	X	X	X	X
2000063	134	Single Protein Spectroscopy with Native Fluorescence		X		X	X
2000064	271	In Situ Synthesis of Organic/Inorganic Nanocomposites	X				X
2000065	154	Advanced Membrane Architectures for Separation of Actinide and Toxic Metal Ions	X		X	X	X
2000066	135	Sensitive Mass Spectroscopic Analysis of Biomolecules in the Megadalton Range		X		X	X
2000067	272	Understanding Complex Instrumentation Issues Involving Polarized Neutron Beams and High Magnetic Fields	X				X
2000068	155	Redox Chemistry of Os (VI)-Nitrido Complexes					X
2000069	236	Remote Sensing of Volcanic Gases		X	X	X	X
2000070	167	Computing with Networks of Spiking Neurons: Application to Real-Time Segmentation of Natural Scenes		X		X	X
2000071	136	Novel Mass Tagging with Stable Isotopes in Post-Genomic Studies					X
2000072	237	Fundamental Underpinnings for Predictive Modeling of Complex Systems	X	X	X	X	X
2000501	37	Synergistic Effects in Actinide Molecular Science	X	X	X		X
2000502	39	Structural Biology Applied to DNA Damage and Repair	X	X	X		X
2000503	73	Static and Dynamic Electronic Response of Actinide Single Crystals in Magnetic Fields	X	X	X		X
2000504	74	Understanding and Predicting Behavior of Polymeric Materials with Time	X		X	X	X
2000507	51	Dynamic Processes of the Earth	X	X	X		X
2000508	53	Integrated Ocean and Atmospheric Science and Modeling	X				X
2000509	57	Earth's Plasma and Radiation Environment	X	X	X		X

Los Alamos National Laboratory FY 00 LDRD Project Listing and Characterization							
Project Number	Page Number	Project Title	WA	ODA	ER& WM	WFO/ DoD	Other
2000510	78	A Scaleable Silicon-based Nuclear Spin Quantum Computer	X	X			X
2000511	79	Organizing Principles across Classes of Complex Electronic Materials	X			X	X
2000512	16	Ultrafast Time-Resolved Atomic Probes of Strategic Materials	X	X	X	X	X
2000513	91	Theoretical Quantum Computation		X			X
2000514	40	Chemical Reactions at Actinide Surfaces: Implications for Nuclear Material Aging and Safety	X	X	X		X
2000515	42	Foundations of Simulation Science	X	X	X	X	X
2000516	26	Host-Pathogen Interactions				X	
2000517	29	Molecular Foundations of the Host-Pathogen Interface	X	X		X	X
2000518	30	Sensitive and Rapid Detection of Diagnostically Important Proteins		X		X	X
2000519	92	Advanced 3-D Modeling and Simulation	X	X		X	X
2000520	61	Spall/Ejecta Studies with Proton Radiography	X				
2000600	93	ElectriSims	X	X	X	X	X
2000601	18	SDSS Photometry and Controls		X			X

Los Alamos National Laboratory FY 2000 Totals

Total Program Funding (\$M) = \$46.98M

Total Number of Projects = 203

Index of Principal Investigators

A

Alexander, F.J. [287](#)
 Altherr, M. [24](#), [29](#), [132](#)
 Ambrose, W.P. [109](#), [137](#), [260](#)
 Ammerman, C. [188](#)
 Arthur, E. [46](#)

B

Baiardo, J. [40](#)
 Baker, R.T. [139](#)
 Balatsky, A. [266](#)
 Barrett, C.L. [42](#)
 Ben-Naim, E. [277](#)
 Bennett, D. [49](#)
 Bennett, K. [51](#)
 Berendzen, J. [39](#)
 Beyerlein, I.J. [262](#)
 Bhattacharya, T. [133](#), [299](#)
 Birn, J. [57](#)
 Bish, D.L. [198](#)
 Bishop, A.R. [64](#)
 Borovsky, J.E. [192](#)
 Boulaevskii, L.N. [245](#)
 Bowles, T. [307](#)
 Bowman, J.D. [291](#)
 Bradbury, E.M. [25](#)
 Brainard, J.R. [19](#)
 Brunish, W.M. [44](#)
 Burns, C.J. [144](#)

C

Camassa, R. [274](#)
 Campbell, I.H. [230](#)
 Cartwright, D.C. [92](#)
 Cary, R. [131](#)
 Casperson, D. [222](#)
 Chen, S. [81](#)
 Chen, W.Y.C. [276](#)
 Chen, X. [136](#)
 Clark, D.L. [37](#)

D

Doyle, J.E. [89](#)
 Dyer, R.B. [123](#)

E

Espy, M.A. [306](#)

F

Fazio, M.V. [12](#), [170](#)
 Fehler, M. [202](#)
 Feldman, W.C. [203](#)
 Feng, W. [166](#)
 Fenimore, E.E. [196](#)
 Findikoglu, A.T. [104](#)
 Fishbine, B. [175](#)
 Fitzsimmons, M. [272](#)
 Fortgang, C. [181](#)
 Frauenfelder, H. [84](#)
 Friar, J. [294](#)

G

Gabitov, I. [282](#)
 Garcia, A. [121](#)
 Gary, S.P. [213](#)
 Garzon, F. [191](#)
 Gavron, V. [60](#)
 George, J. [224](#)
 Gibson, B. [305](#)
 Goff, F. [236](#)
 Gokhale, M. [165](#)
 Gosnell, T. [219](#)
 Grace, K.M. [227](#)
 Gupta, G. [26](#)
 Gupta, R. [302](#)

H

Habib, S. [108](#), [298](#)
 Haines, T. [216](#), [293](#)
 Hammel, P.C. [78](#)
 Hayes, A.C. [295](#)
 Heffner, R.H. [63](#)
 Henson, B.F. [147](#)
 Hills, J.G. [200](#)
 Hime, A. [300](#)
 Hiskey, M.A. [150](#)
 Hockaday, M. [61](#)
 Hoffbauer, M. [246](#)
 Hogden, J. [178](#)
 Holm, D.D. [281](#), [286](#)
 Hughes, R.J. [221](#)
 Hummer, G. [119](#)
 Hush, D. [160](#)
 Hyman, J.M. [156](#)

I

Intrator, T. 114

J

Jacobson, A.R. 235
 James, D.F.V. 106
 Jarvinen, G.D. 31
 Jia, Q. 67, 220
 Johnson, P.A. 212, 231

K

Keller, C.F. 53
 Keller, R.A. 134
 Kendrick, B.K. 145
 Klimov, V. 100, 257
 Knill, E. 91, 280
 Knoll, D. 273
 Kober, E.M. 74
 Kraus, R.H. 125
 Kwiat, P.G. 110

L

Laflamme, R. 116
 Lai, C.-C.A. 207
 Lamoreaux, S.K. 290
 Laubscher, B.E. 18
 Lomdahl, P. 253
 Longmire, J. 117
 Louis, W. 98
 Love, S.P. 232

M

Mainieri, R. 237
 Majidi, V. 135
 Marathe, M. 157, 161
 Marrone, B. 21
 Mattis, M. 296
 McCleskey, T.M. 149
 Meyer, M. 288
 Miller, W. 205
 Milonni, P.W. 112
 Mitchell, M. 167
 Mitchell, T.E. 228, 268
 Montgomery, D.S. 103
 Morris, D.E. 155
 Mottola, E. 95
 Movshovich, R. 242
 Munson, C. 13

N

Nastasi, M. 169
 Nolan, J. 118

O

Ortiz, G. 263

P

Pack, R.T. 115, 152
 Parkin, D.M. 66
 Petrovic, J.J. 238
 Prasad, L. 163

R

Rangaswamy, P. 172
 Roberts, D. 93
 Rodriguez, G. 113
 Rundberg, R.S. 292
 Ruscetti, T. 122

S

Sauer, N.N. 138, 154
 Schwarz, R. 239
 Seestrom, S.J. 96
 Sharp, D.H. 87
 Shashkov, M. 275, 285
 Shreve, A.P. 30, 251, 267
 Silks, L.P. 128
 Sinnis, C. 201
 Smith, D.L. 120, 252
 Smith, M. 271
 Son, S.F. 33
 Stephens, J.R. 217
 Strauss, C. 126
 Strottman, D. 70
 Swanson, B.I. 20
 Swift, G. 190

T

Taylor, A.J. 16, 73, 187
 Thoma, D.J. 179, 248, 261
 Thompson, J.D. 79
 Thomsen, M.F. 208
 Torney, D.C. 83
 Tumas, W. 141
 Turin, H.J. 218

U

Unkefer, P.J. [130](#)

V

Vaidya, R. [168](#)

Vestrand, W.T. [204](#)

Vieira, D.J. [10](#), [105](#)

W

Wang, H. [184](#)

Ward, W. [171](#)

Warner, B. [148](#)

Warren, M.S. [214](#)

Wender, S. [303](#)

West, G. [127](#), [289](#)

White, A. [90](#)

White, P.S. [124](#)

Wilburn, W.S. [297](#)

Williams, T.O. [189](#)

Winter, L. [47](#)

Woodruff, W. [153](#)

Z

Zhang, D. [206](#)

Zhao, Y. [193](#), [255](#)

Zhu, Y.T. [183](#)

Ziock, H. [35](#)

Zurek, W.H. [107](#), [211](#)