APR 13 1999

4

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT 623368

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) Characterization Engineering		4. Related EDT No.: N/A	
5. Proj./Prog./Dept./Div.: Characterization Project		6. Design Authority/Design Agent/Cog. Engr.: G.P. Janicek		7. Purchase Order No.: N/A	
8. Originator Remarks: The attached test plan/report is submitted for release.				9. Equip./Component No.: N/A	
				10. System/Bldg./Facility: 200 General	
				12. Major Assm. Dwg. No.: N/A	
11. Receiver Remarks:		11A. Design Baseline Document? ☐ Yes ☒ No		13. Permit/Permit Application No.: N/A	
				14. Required Response Date: April 15, 1999	
15. DATA TRANSMITTED					
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	(F) Approval Designator
1	HNF-4292	N/A	0	Test Plan and Report for	SQ
				MAXIDRILL Model 3030	2
				Footclamp	1
16. KEY					
Approval Designator (F)		Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D OR N/A (See WHC-CM-3-5, Sec. 12.7)		1. Approval 2. Release 3. Information		4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged	
		4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)		1. Approved 2. Approved w/comment 3. Disapproved w/comment	
17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)					
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
1	/	Design Authority GP Janicek	<i>[Signature]</i>	4/1/99	S7-03
		Design Agent	<i>[Signature]</i>	4/1/99	S7-12
1	/	Cog. Eng. <i>T.R. Fain</i>	<i>[Signature]</i>	4-1-99	S7-12
1	/	Cog. Mgr. JS Schofield	<i>[Signature]</i>	4-8-99	S7-12
1	/	QA DC Board	<i>[Signature]</i>	5-7-07	
1	/	Safety JA Ranschau	<i>[Signature]</i>	4/5/99	
		Env.			
18. <i>[Signature]</i> 4/1/99 HF Shumake Jr Signature of EDT Originator		19. <i>[Signature]</i> 4/8/99 JS Schofield Authorized Representative for Receiving Organization		20. <i>[Signature]</i> 4/6/99 GP Janicek Design Authority/ Cognizant Manager	
				21. DOE APPROVAL (if required) Ctrl No. N/A ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	

TEST PLAN AND REPORT FOR MAXIDRILL MODEL 3030 FOOTCLAMP

R. M. Boger

Prepared by Lockheed Martin Hanford Corporation
Richland, WA 99352
U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 623368

UC: 2070

Org Code: 74900

Charge Code: 102250EI00

B&R Code: EW3120074

Total Pages: 12

Key Words: footclamp, RMCS, RMCST, waste sampling, characterization

Abstract:

This test plan and report defines the testing performed to determine whether the MAXIDRILL Model 3030 Footclamp meets the needs of RMCS operations. This document reports the outcome of the test performed. The new footclamp will enhance the safety of RMCS operations.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

4/13/99
Release Approval Date

Release Stamp

Approved For Public Release

**TEST PLAN AND REPORT FOR
MAXIDRILL MODEL 3030
FOOTCLAMP**

Prepared for
Characterization Engineering
Lockheed Martin Hanford Corporation
Richland, Washington

by
H. F. Shumake Jr.

March 1999

TABLE OF CONTENTS

1.0 Scope	1
2.0 Footclamp Description	1
3.0 Objective.....	1
3.1 Acceptance Criteria	1
4.0 Test Plan	2
4.1 Close Rate Test	2
4.2 Jaw Engagement Measurement.....	3
4.3 Failure Mode.....	3
4.4 Load/Slip Test	3
4.5 Excessive Deformation Test	4
5.0 Close Rate Adjustment Procedure	4
5.1 Parker® SP25 Speed Control.....	4
6.0 Results	5
7.0 Conclusion	6
APPENDIX A—Results Tables	7

1.0 SCOPE

This document is both a test plan and a test report. Its purpose is to document the findings, adjustment procedures, and test plan to determine whether a MAXIDRILL Model 3030 Footclamp meets the needs of the Rotary Mode Core Sampling (RMCS) operations in tank farms. The test is to be conducted by H. F. Shumake Jr. with the assistance of D. L. Powell Jr. at the Engineering Testing Lab (ETL).

On June 18, 1998, a problem occurred while core sampling operations were being conducted. Approximately 28 ft. of drill string was inadvertently dropped into tank 241-SX-102. The root cause of this occurrence was determined to be inadequate or defective design of the footclamp being used. The footclamp in use during this occurrence relied on a wedge-type design that gripped the drill string tighter as the weight of the drill string was increased. The MAXIDRILL Model 3030 Footclamp does not rely on a wedge effect to hold the drill string; it uses spring force to engage the jaws with the drill string. The use of the MAXIDRILL Model 3030 Footclamp should eliminate any further problems of this nature and allow corrective action 2 in section 26 of the related occurrence report (RL—PHMC-TANKFARM-1998-0064) to be completed.

2.0 FOOTCLAMP DESCRIPTION

The MAXIDRILL Model 3030 Footclamp is an assembly composed of a pair of machined steel jaws, a pair of pneumatic actuators, and a base that supports it. The base consists of several pieces that are assembled to mount the actuators, guide the jaws, and support the assembly as well as the drill string that it is holding. The pneumatic actuators are essentially the same as those found on an air brake system on a commercial truck; they operate by means of a spring force. The pneumatic force is used to overcome the spring force to disengage the actuator. Therefore, the actuator fails in the engaged, or closed, position. One of the actuators is fit with a tee, the second actuator is plumbed to the tee via a flexible hose, and the third port of the tee is fit with a three-way ball valve. The three-way ball valve is used to control the engagement and disengagement of the actuators. When the ball valve is in the closed position the springs in the actuators force the jaws to engage the drill string. The rate of closure is controlled by a Parker Speed Control, which is attached to the exhaust port of the three-way ball valve.

3.0 OBJECTIVE

The purpose of conducting these tests is to determine whether a MAXIDRILL Model 3030 Footclamp suits the needs of the RMCS operations.

3.1 ACCEPTANCE CRITERIA

- 3.1.1 The jaws of the footclamp need to close at a rate that does not exceed one foot per second—a close time of approximately one second is desired to reduce the

likelihood of deformation of the drill string by gradually applying the full force of the jaws to the drill string rather than allowing the jaws to “slam shut.”

- 3.1.2 The distance between the engaged jaws is less than 2 ¼ in. The outside diameter of the smallest piece of drill string is 2 ¼ in. To ensure that the footclamp will securely hold a piece of drill string of this size the distance between the engaged, or closed, jaws must be less than 2 ¼ in.
- 3.1.3 The footclamp must fail in the closed position. In the event that the supply air is lost to the footclamp, the footclamp must fail closed to prevent the drill string from dropping into the waste tank.
- 3.1.4 The footclamp must restrain a vertical load of at least 1000 lbf. on a piece of drill string (fluted and non-fluted) when engaged by the jaws. The weight of the longest section of drill string to be deployed into a waste tank is approximately 250 lbf. A factor of safety of four was chosen to ensure that the footclamp would sufficiently restrain the drill string.
- 3.1.5 The footclamp must not deform the drill string to the point that the sampling apparatus will not pass through it. The drill string is used as a conduit to allow the sampling apparatus to reach its destination in the waste. A “GO GAGE” has been fabricated to test whether the drill string is deformed to the point that the sampler won’t pass through the drill string. The dimensions of the “GO GAGE” are 1.895 inches in diameter by 12 inches long. The “GO GAGE” must pass through the drill string to ensure that the internal diameter of the drill string has not been distorted to the point of not allowing the sampler to pass through it.

4.0 TEST PLAN

4.1 CLOSE RATE TEST

- 4.1.1 Prior to airline attachment, measure and record the distance from the “mating” edges of the jaws relative to the pneumatic actuator mount plate.
- 4.1.2 Ensure that the 3-way ball valve is in the closed position.
- 4.1.3 Attach an airline to the quick-connect air fitting that is mounted on the footclamp.
- 4.1.4 Regulate the air pressure to 100 psig, or maximum supply pressure, whichever is less. Record the air pressure.
- 4.1.5 Disengage the footclamp by reversing the position of the valve. Measure and record the distance from the “mating” edges of the jaws relative to the pneumatic actuator mount plate.
- 4.1.6 Record the stroke. The stroke is the difference between the measurements taken in step 4.1.1 and 4.1.5.
- 4.1.7 Engage the footclamp by reversing the position of the valve while timing with a stopwatch how long it takes for the jaws to touch. Record the time.
- 4.1.8 Disengage the footclamp by reversing the position of the valve while timing with a stopwatch how long it takes for the jaws to retract. Record the time.

- 4.1.9 Divide the stroke found in 4.1.6 by the closure time found in 4.1.7. This is the rate of closure. Record the rate of closure.
- 4.1.10 Divide the stroke found in 4.1.6 by the retraction time found in 4.1.8. This is the rate of retraction. Record the rate of retraction.

NOTE: If the footclamp engages too rapidly or slowly then the speed control will have to be adjusted. Adjust the speed control as required to achieve a closure time of 1 ± 0.1 seconds with supply pressure of 100 psig or the maximum supply air pressure, whichever is less. See 5.0 for the close rate adjustment procedure.

- 4.1.11 Repeat steps 4.1.7 and 4.1.8 five times.
- 4.1.12 Repeat steps 4.1.7 and 4.1.8 five times for air pressures of 80 psig and 60 psig to determine the close rate at these operating pressures.

4.2 JAW ENGAGEMENT MEASUREMENT

- 4.2.1 With the jaws in the engaged, or closed, position measure the distance between the surfaces of the jaws that contact the drill string. Record the measurement.

4.3 FAILURE MODE

- 4.3.1 With the jaws in the disengaged, or open, position disconnect the air supply hose from the fitting. Record the outcome.

4.4 LOAD/SLIP TEST

The SATEC machine located in the Engineering Testing Laboratory (305 building) will be used to apply and measure the load.

Figure 1: SATEC "Press" with footclamp mounted and SATEC "Control Panel"

- 4.4.1 Ensure that the speed control on the footclamp has been adjusted appropriately (see Section 5.0).
- 4.4.2 Mount the footclamp in the SATEC test apparatus.
- 4.4.3 Connect supply air to the footclamp via the quick-connect fitting.
- 4.4.4 Disengage, or open, the footclamp and insert a piece of clean, dry, 2-¼ inch drill string.

NOTE: The excessive deformation test, step 4.5.1 should be performed prior to insertion of the drill string in the footclamp.

- 4.4.5 Engage the footclamp by turning the 3-way ball valve handle 180°.
- 4.4.6 Load the drill string with the SATEC press until slip occurs.

NOTE: In the context of this document, slip will be defined as when the drill string moves a distance greater than 3/16 of an inch or the maximum load is recorded, whichever occurs first.

- 4.4.7 Record the load indicated on the SATEC load cell.
- 4.4.8 Reposition the drill string and repeat the test for a total of 5 times.
- 4.4.9 Repeat steps 4.4.4 through 4.4.8 with a piece of drill string lubricated with LA-CO® (Brand Name) T-O-T (Product Name) anti-seize joint compound.
- 4.4.10 Repeat steps 4.4.4 through 4.4.9 with 2-½ inch fluted drill string.

4.5 EXCESSIVE DEFORMATION TEST

- 4.5.1 Test the drill string specimen that will be used in the hold force test prior to being placed into the footclamp by passing the “GO GAGE” through the drill string specimen. If the “GO GAGE” passes through the drill string then the drill string is acceptable for use in the hold force test.
- 4.5.2 Test the drill string specimen after the drill string has been clamped in and removed from the footclamp by attempting to pass the “GO GAGE” through the drill string specimen. If the “GO GAGE” passes through the drill string specimen then the drill string was not excessively deformed.

5.0 CLOSE RATE ADJUSTMENT PROCEDURE

5.1 PARKER® SP25 SPEED CONTROL

- 5.1.1 Loosen the lock nut on the adjustment (needle valve) screw.
- 5.1.2 Rotate the adjustment screw clockwise to slow the jaws down or counter-clockwise to speed them up.
Initially, ¼ of a turn will be enough to determine the magnitude of the rate change.

NOTE: To avoid damage to the needle and seat in the speed control do not force the needle into the seat by turning the adjustment (needle valve) screw too far clockwise. When resistance is felt, STOP.

- 5.1.3 Repeat steps 4.1.7 through 4.1.10 to determine the new close rate.
- 5.1.4 When the desired close rate is achieved, secure the lock nut on the adjustment (needle valve) screw while preventing the adjustment (needle valve) screw from rotating.

6.0 RESULTS

The testing of the MAXIDRILL Model 3030 Footclamp went well. However, two unplanned events occurred during the testing. The maximum supply air pressure that was available in the ETL was 93 psig. The plan was to test the footclamp with a maximum air supply pressure of 100 psig. The plan was to test footclamp with minimum of 65 psig but the footclamp required 68 psig to open. These events did not create a problem with the test, and should not create a problem with the use of the footclamp.

Data sheets for the rate and hold force tests can be found in Appendix A. The fundamental data from the rate and hold force tests are located in Table 1 and Table 2 below.

The jaw engagement measurement was zero inches. The footclamp fails in the closed position when the supply air is lost. The inner diameter of the drill string was not distorted to the point of not allowing the sampler to pass through it.

Table 1: Rate Test Results			
Rate Test (fps)			
Close Rate	Supply Air Pressure (psig)		
	93	80	68
Maximum	0.12	0.13	0.16
Minimum	0.10	0.11	0.13
Average	0.11	0.12	0.15

Table 2: Hold Force Test Results (Minimum Value for Each Configuration)		
Hold Force (lbf)		
Drill String Type	Non-lubricated	Lubricated
2 ¼-inch Diameter Non-Fluted	3264	3157
2 ½-inch Diameter Fluted	3197	2672

7.0 CONCLUSION

The MAXIDRILL Model 3030 Footclamp passed the defined criteria to be able to satisfy the needs of RMCS operations in tank farms.

The original intention of this test was to evaluate the footclamp with a supply air pressure approximately equal to that available on the RMCS trucks, 100 psig. As indicated in Section 6.0, only 93 psig was available at the ETL. This does not invalidate the test results. However, it will require that the close rate test and adjustments be made prior to use of the footclamp in the field with the "normal" operating pressure of approximately 100 psig.

The footclamp tested would not open, or disengage, with an air supply of less than 68 psig. The footclamp was supposed to open with a supply pressure of 65 psig. This should not pose a problem with the use of the footclamp during RMCS because the air pressure available on the RMCS trucks is approximately 100 psig.

The tests performed indicate that the MAXIDRILL Model 3030 Footclamp is acceptable for use during, and will enhance the safety of, RMCS operations.

APPENDIX A—RESULTS TABLES

RATE TEST DATA TABLE-MAXIDRILL Model 3030 Footclamp						
Date: 3/23/99		Test Performed by: H.F. Shumake Jr.				
		Test Assisted by: D.L. Powell Jr.				
		Test Location: 305 Lab				
A	DISTANCE FROM MATING EDGE OF JAWS TO ACTUATOR MOUNT PLATE (ENGAGED) =					4.1875 INCHES
B	DISTANCE FROM MATING EDGE OF JAWS TO ACTUATOR MOUNT PLATE (DISENGAGED) =					2.8750 INCHES
C	STROKE = DIFFERENCE BETWEEN VALUES IN ROWS A & B (A - B) =					1.3125 INCHES
D	93 psig (max pressure of shop air in 305 lab)					
	TRIAL 1	time for jaws to CLOSE =	0.95 seconds	RATE =	0.12	fps
	TRIAL 2	time for jaws to CLOSE =	1.00 seconds	RATE =	0.11	fps
	TRIAL 3	time for jaws to CLOSE =	1.02 seconds	RATE =	0.11	fps
	TRIAL 4	time for jaws to CLOSE =	0.97 seconds	RATE =	0.11	fps
	TRIAL 5	time for jaws to CLOSE =	1.08 seconds	RATE =	0.10	fps
	TRIAL 1	time for jaws to OPEN =	0.97 seconds	RATE =	0.11	fps
	TRIAL 2	time for jaws to OPEN =	1.09 seconds	RATE =	0.10	fps
	TRIAL 3	time for jaws to OPEN =	1.09 seconds	RATE =	0.10	fps
	TRIAL 4	time for jaws to OPEN =	1.11 seconds	RATE =	0.10	fps
	TRIAL 5	time for jaws to OPEN =	1.10 seconds	RATE =	0.10	fps
E	80 psig					
	TRIAL 1	time for jaws to CLOSE =	0.93 seconds	RATE =	0.12	fps
	TRIAL 2	time for jaws to CLOSE =	0.86 seconds	RATE =	0.13	fps
	TRIAL 3	time for jaws to CLOSE =	0.96 seconds	RATE =	0.11	fps
	TRIAL 4	time for jaws to CLOSE =	0.89 seconds	RATE =	0.12	fps
	TRIAL 5	time for jaws to CLOSE =	0.82 seconds	RATE =	0.13	fps
	TRIAL 1	time for jaws to OPEN =	1.23 seconds	RATE =	0.09	fps
	TRIAL 2	time for jaws to OPEN =	1.54 seconds	RATE =	0.07	fps
	TRIAL 3	time for jaws to OPEN =	1.49 seconds	RATE =	0.07	fps
	TRIAL 4	time for jaws to OPEN =	1.58 seconds	RATE =	0.07	fps
	TRIAL 5	time for jaws to OPEN =	1.51 seconds	RATE =	0.07	fps
F	68 psig (min air pressure that would open jaws)					
	TRIAL 1	time for jaws to CLOSE =	0.68 seconds	RATE =	0.16	fps
	TRIAL 2	time for jaws to CLOSE =	0.82 seconds	RATE =	0.13	fps
	TRIAL 3	time for jaws to CLOSE =	0.73 seconds	RATE =	0.15	fps
	TRIAL 4	time for jaws to CLOSE =	0.74 seconds	RATE =	0.15	fps
	TRIAL 5	time for jaws to CLOSE =	0.76 seconds	RATE =	0.14	fps
	TRIAL 1	time for jaws to OPEN =	3.50 seconds	RATE =	0.03	fps
	TRIAL 2	time for jaws to OPEN =	3.01 seconds	RATE =	0.04	fps
	TRIAL 3	time for jaws to OPEN =	3.52 seconds	RATE =	0.03	fps
	TRIAL 4	time for jaws to OPEN =	3.32 seconds	RATE =	0.03	fps
	TRIAL 5	time for jaws to OPEN =	3.27 seconds	RATE =	0.03	fps
Comments: The maximum air pressure available in the 305 lab March 23, 1999 is 93 psi.						
Footclamp will not open fully with less than 68 psig supply air. At 68 psig the jaws fully open but the last 1/4-1/2" takes approximately 0.75 seconds.						

Load/Slip Test Data Table--MAXIDRILL Model 3030 Footclamp			
Date: 3/23/99		Test Performed by: H.F. Shumake Jr.	
		Test Assisted by: D.L. Powell Jr.	
		Test Location: 305 Lab	
2 1/4-inch Diameter Non-Fluted Drill String (Non-lubricated)		2 1/4-inch Diameter Non-Fluted Drill String (Lubricated)	
Trial #	Hold Force (lbf)	Trial #	Hold Force (lbf)
1	3264	1	3157
2	3422	2	3690
3	3772	3	4036
4	3841	4	4136
5	3479	5	3620
2 1/2-inch Diameter Fluted Drill String (Non-lubricated)		2 1/2-inch Diameter Fluted Drill String (Lubricated)	
Trial #	Hold Force (lbf)	Trial #	Hold Force (lbf)
1	3197	1	3688
2	4371	2	4015
3	5144	3	2672
4	3595	4	3189
5	4415	5	4525
Comments: The 2 1/2-inch fluted drill string displayed a larger range of hold force values because of the variance of the "gripped" surface of the drill string due to the flutes.			