Report Title: Technical Progress on Project Entitled: “24-Channel Geophone Array for Horizontal or Vertical Boreholes”

Type of Report: Quarterly Technical Report

Reporting Period Start Date: December 10, 2000

Reporting Period End Date: March 31, 2001

Principal Author: Erik C. Westman

Date Report was Issued: July 2002

DOE Award Number: DE-FC26-01NT41063

Name and Address of Submitting Organization:

Virginia Polytechnic Institute and State University
Office of Sponsored Programs
Collegiate Square
460 Turner Street, Suite 306
Blacksburg, VA 24060

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility of the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Abstract

This report describes the technical progress on a project to design and construct a multi-channel geophone array that improves tomographic imaging capabilities in both surface and underground mines. Especially important in the design of the array is sensor placement. One issue related to sensor placement is addressed in this report: the development of simple, robust, MSHA-acceptable clamping unit. Improved imaging capabilities will produce energy, environmental, and economic benefits by increasing exploration accuracy and reducing operating costs.

Table of Contents

Disclaimer	i
Abstract	ii
Table of Contents	iii
Introduction.....	1
Experimental.....	2
Results and Discussion	2
Conclusion	3
References	3

Introduction

The ability to accurately image conditions within a rockmass permits superior resource characterization resulting in more efficient extraction. This ability relates directly to industry goals to:

- 1) sense, visualize, and predict geological anomalies in front of mining equipment,
- 2) reduce operational downtime,
- 3) detect difficult mining conditions,
- 4) minimize waste, and
- 5) precisely characterize ore bodies.

Achieving these goals will have the benefits of reducing the amount of energy consumed by mining operations and minimizing the environmental impact of extraction.

Seismic tomography has been used successfully to monitor and evaluate geologic conditions ahead of a mining face. A review of the history and theory of tomographic imaging itself will be presented to properly illustrate the advances introduced by the multi-channel borehole geophone array.

Seismic tomography produces a map of an object's internal properties in a non-invasive fashion (Radon, 1917). By measuring the travel times of a seismic wave between source and receiver points around a rock mass, it is possible to calculate a map of the distribution of physical properties influencing seismic wave velocity within a rock mass. Tomography was first adapted to the field of medicine (Hounsfield, 1973; Cormack, 1973) and subsequently to the geosciences (Dines and Lytle, 1979). For at least 20 years, tomography has been used in the mining industry to create images of geologic features as well as stress-related features (Buchanan et al., 1981, Mason 1981, Kormendi et al., 1986). A more recent mining-specific application of tomography is an adaptation which can image stress concentrations ahead of the longwall face by using the longwall shearer itself as the seismic source (Westman et al., 1996).

Velocity tomography creates a velocity map from signal time-travel data. In this specific type of tomography, the raypath and the velocity variations along the raypath are unknown variables. By representing the medium as a grid, a forward velocity model is constructed to estimate the travel-time and the refraction path of each ray. Refraction paths are estimated by back-projection across the grid from each receiver to the source. By propagating a finite difference wavefront across the grid from a known source location, the travel-times can be estimated. Differences between the estimates and the measured travel times are used to iteratively update the velocity grid from each receiver to the source. The process is repeated a specific number of times, or until no noticeable changes occur.

Tomographic methods usually involve some sort of iterative algorithm to invert the traveltimes (Dines and Lytle, 1979; Peterson et al., 1985). A problem with these techniques is a tradeoff between resolution and stability of the solution. At some point, as one attempts to see smaller features, the inversion becomes unstable and velocity

artifacts appear. Velocity artifacts are seen as fluctuations of values between adjacent points and the smearing of anomalous zones. Therefore, too few iterations will produce an image which lacks detail, and too many will overfit the data, and produce an image with an abundance of artifacts. A cross-validation method can determine the number of iterations needed (Peterson and Davey, 1990). Also, this method can give a way to determine several solutions to a non-unique problem, which can be then averaged to produce an image that may be an improvement over a single solution obtained using all the data at once.

To complete a tomographic survey, a seismic source must be selected. Several factors must be considered, including cooperation with mining operations, regularity of signal and amount of energy. Sources, including mining-induced seismic activity (Young, 1992), mining equipment and manually input energy (Westman and Haramy, 1996) are all possible considerations. For surveys at a quarry, a drill excavating blast holes can be used as the source. The longwall shearer has been used as the source for underground coal as it provides a relatively high amplitude signal.

A primary limitation to existing seismic tomography, however, is the placement of sensors. The goal of this ongoing project is to develop an array of 24 seismic sensors capable of being mounted in either a vertical or horizontal borehole. This array will significantly improve the ability of seismic tomography to accurately image conditions within a rock mass.

Experimental

Initial construction of the geophone housing has been focused on a rugged, low-cost prototype, capable of withstanding the harsh environment of a borehole. The housing and locking-arm have been fabricated from poly-vinyl chloride (PVC) for low-cost and durability.

More time has been spent on the design of the clamping unit during the first quarter of the project than on any other issue. The proposal called for an electric motor within the geophone housing to press an arm out and lock against the borehole wall. However, because a specific objective of the project is to develop an array that will be used in methane drainage boreholes, for safety reasons it was decided to consider non-electric alternatives for clamping.

Results and Discussion

The initial alternative design was to use an inflatable bladder that would act between the array housing and a hinged arm. A prototype was constructed and tested in vertical blastholes at a local quarry. The design was found to be clumsy to place and the air pressure bled out of the system, resulting in poor coupling with the borehole.

Conclusion

Seismic tomography is a promising technique for imaging conditions ahead of surface or underground mining, thereby increasing efficiency and reducing energy consumption during the mining operation. A principle difficulty in using seismic tomography is the placement of multiple sensors around the mining face. Progress during the first calendar quarter of the project (December 10, 2000 through March 31, 2001) focused on development of a rugged housing unit and a non-electrical clamping mechanism greatly increasing the usefulness of the tool in methane-drainage boreholes.

References

- Buchanan, D.J., R. Davis, P.J. Jackson, and P.M. Taylor, 1981, "Fault Location by Channel Wave Seismology in United Kingdom Coal Seams," *Geophysics*, Vol. 46, pp. 994-1002.
- Cormack, A.M., 1973, "Reconstruction of Densities from their Projections, with Applications in Radiological Physics," *Phys. Med. Biol*, vol. 18, no. 2, pp. 195-207.
- Dines, K.A., and J.R. Lytle, 1979, "Computerized geophysical tomography," *Proc. IEEE*, vol. 67, no. 7, pp. 1065-1073.
- Hounsfield, G.N., 1973, "Computerized transverse axial scanning (tomography). 1. description of system," *Br. J. Radiol.*, vol.46, no. 552, pp. 1016-1022.
- Kormendi, A., T. Bodoky, L. Hermann, L. Dianisda, and T. Kalman, 1986, "Seismic Measurements for Safety in Mines," *Geophysical Prospecting*, Vol. 34, pp. 1022-1037.
- Mason, I.M, 1981, "Algebraic Reconstruction of a Two-Dimensional Velocity Inhomogeneity in the High Hazles Seam at Thoresby Colliery," *Geophysics*, Vol. 46, pp. 298-308.
- Peterson, J.E. Jr, B.N.P. Paulsson, and T.V. McEvelly, 1985, "Applications of Algebraic Reconstruction Techniques to Crosshole Seismic Data," *Geophysics*, Vol 50, No. 10, pp. 1566-1580.
- Peterson, J.E. Jr. and A. Davey, 1991, "Crossvalidation Method for Crosswell Seismic Tomography," *Geophysics*, Vol 56, No. 3, pp. 385-389.
- Radon, J., 1917, "Über die bestimmung von functionen durch ihre integralwere lange gewisser mannigfaltigkeiten," *Ber. Verh. Saechs. Akad. Wiss.*, vol. 69, pp. 262-267.
- Westman, E.C. and K.Y. Haramy, 1996, "Seismic tomography to map hazards ahead of the longwall face," *Mining Engineering*, Vol. 48, No. 11, pp. 73-79.

Westman, E.C., K.Y. Harny, and A.D. Rock, 1996, "Seismic tomography for longwall stress analysis," Proceedings of 2nd North American Rock Mechanics Symposium (Montreal, Quebec, June 19-21), ed. By M. Aubertin, F. Hassani, and H. Mitri, A.A. Balkema, pp. 397-403.

Young, R.P., 1992, "Invited Paper: Correlation between seismic velocity and induced seismicity in underground mines," Proceedings of 33rd U.S. Symposium on Rock Mechanics (Santa Fe, New Mexico, June 3-5), ed. by J.R. Tillerson and W.R. Wawersik, A.A. Balkema, pp. 1113-1122.