S

ENGINEERING CHANGE NOTICE

Page 1 of 21. ECN **663397**Proj.
ECN

2. ECN Category (mark one) Supplemental ☐ Direct Revision ☒ Change ECN ☐ Temporary ☐ Standby ☐ Supersedure ☐ Cancel/Void ☐	3. Originator's Name, Organization, MSIN, and Telephone No. A. Artzer, CVDF, X3-78, 372-2785 6. Project Title/No./Work Order No. SNF/W-441, Spent Nuclear Fuel Cold Vacuum Drying 9. Document Numbers Changed by this ECN (includes sheet no. and rev.) SNF-3933, Rev. 4	4. USQ Required? ☒ Yes ☐ No 7. Bldg./Sys./Fac. No. CVDF 142K 10. Related ECN No(s). N/A	5. Date 10/07/00 8. Approval Designator S ^N Q 11. Related PO No. N/A
12a. Modification Work ☐ Yes (fill out Blk. 12b) ☒ No (NA Blks. 12b, 12c, 12d)	12b. Work Package No. N/A	12c. Modification Work Complete N/A Design Authority/Cog. Engineer Signature & Date	12d. Restored to Original Condition (Temp. or Standby ECN only) N/A Design Authority/Cog. Engineer Signature & Date
13a. Description of Change HOOD Incorporated changes from Rev. 4a, removed internal pressure 150 psig and vacuum, increased sample size to 100% for cracking pressure and for reseal pressure due to failure in sample lot, changed bubble tight standards...to No Continuous Bubble Formation. USQ Approval: <u>CVD-00-2047</u>			
14a. Justification (mark one) Criteria Change ☐ Design Improvement ☒ Environmental ☐ Facility Deactivation ☐ As-Found ☐ Facilitate Const ☐ Const. Error/Omission ☐ Design Error/Omission ☐		14b. Justification Details Revision is necessary because of failures in the reduced sample size. Other changes are necessary to clarify intent of the document. The design verification method for SC/SS components is by independent review in accordance with EN-6-027-01. Documentation of this review is accomplished by the independent review approval signature provided on page 2 of this ECN.	
15. Distribution (include name, MSIN, and no. of copies) See distribution sheet.			RELEASE STAMP

ENGINEERING CHANGE NOTICE				Page 2 of 2	1. ECN (use no. from pg. 1) 663397												
16. Design Verification Required [X] Yes [] No		17. Cost Impact <table><thead><tr><th colspan="2">ENGINEERING</th><th colspan="2">CONSTRUCTION</th></tr><tr><th>Additional</th><th>[N/A] \$</th><th>Additional</th><th>[N/A] \$</th></tr></thead><tbody><tr><td>Savings</td><td>[N/A] \$</td><td>Savings</td><td>[N/A] \$</td></tr></tbody></table>			ENGINEERING		CONSTRUCTION		Additional	[N/A] \$	Additional	[N/A] \$	Savings	[N/A] \$	Savings	[N/A] \$	18. Schedule Impact (days) Improve ment [N/A] Delay [N/A]
ENGINEERING		CONSTRUCTION															
Additional	[N/A] \$	Additional	[N/A] \$														
Savings	[N/A] \$	Savings	[N/A] \$														
19. Change Impact Review: Indicate the related documents (other than the engineering documents identified on Side 1) that will be affected by the change described in Block 13. Enter the affected document number in Block 20.																	
SDD/DD	[]	Seismic/Stress Analysis	[]	Tank Calibration Manual	[]												
Functional Design Criteria	[]	Stress/Design Report	[]	Health Physics Procedure	[]												
Operating Specification	[]	Interface Control Drawing	[]	Spares Multiple Unit Listing	[]												
Criticality Specification	[]	Calibration Procedure	[]	Test Procedures/Specification	[]												
Conceptual Design Report	[]	Installation Procedure	[]	Component Index	[]												
Equipment Spec.	[]	Maintenance Procedure	[]	ASME Coded Item	[]												
Const. Spec.	[]	Engineering Procedure	[]	Human Factor Consideration	[]												
Procurement Spec.	[]	Operating Instruction	[]	Computer Software	[]												
Vendor Information	[]	Operating Procedure	[]	Electric Circuit Schedule	[]												
OM Manual	[]	Operational Safety Requirement	[]	ICRS Procedure	[]												
FSAR/SAR	[]	IEFD Drawing	[]	Process Control Manual/Plan	[]												
Safety Equipment List	[]	Cell Arrangement Drawing	[]	Process Flow Chart	[]												
Radiation Work Permit	[]	Essential Material Specification	[]	Purchase Requisition	[]												
Environmental Impact Statement	[]	Fac. Proc. Samp. Schedule	[]	Tickler File	[]												
Environmental Report	[]	Inspection Plan	[]	N/A	[]												
Environmental Permit	[]	Inventory Adjustment Request	[]		[]												
20. Other Affected Documents: (NOTE: Documents listed below will not be revised by this ECN.) Signatures below indicate that the signing organization has been notified of other affected documents listed below.																	
Document Number/Revision		Document Number/Revision		Document Number/Revision													
N/A																	
21. Approvals																	
Signature		Date		Signature													
Design Authority C. Miska		10-7-00		Design Agent													
Cog. Eng. C. Van Katwijk		10/9/00		PE													
Cog. Mgr. C. Haller		10/9/2000		QA													
QA R. K. Ramsgate		10/9/00		Safety													
Safety J. R. Brehm		10/9/00		Design													
Environ.				Environ.													
Other				Other													
Independent Review		10/9/2000															
DEPARTMENT OF ENERGY																	
Signature or a Control Number that tracks the Approval Signature																	
ADDITIONAL																	

DISTRIBUTION SHEET

To Distribution	From SNF-CVD	Page 1 of 1
Project Title/Work Order W-441, CGI Package		Date 10/7/00 10/10/00
		EDT No. N/A
		ECN No. 663398 663397

[illegible]

NUPRO Process Vent/MCO Check/Relief Valve - Prevent Backflow From Process Vent Into MCO

Prepared for the U.S. Department of Energy
Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the
U.S. Department of Energy under Contract DE-AC06-96RL13200

Fluor Hanford
P.O. Box 1000
Richland, Washington

SNF-3933
Revision 5

ECN 663397

NUPRO Process Vent/MCO Check/Relief Valve - Prevent Backflow From Process Vent Into MCO

Project No: W-441

Division: SNF

C. R. Miska
Fluor Hanford

Date Published
October 2000

Prepared for the U.S. Department of Energy
Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the
U.S. Department of Energy under Contract DE-AC06-96RL13200

Fluor Hanford

P.O. Box 1000
Richland, Washington

Chris Bradon
Release Approval

10/10/00
Date

Release Stamp

TRADEMARK DISCLAIMER

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy. Available in paper copy and microfiche.

Available electronically at <http://www.doe.gov/bridge>. Available for a processing fee to the U.S. Department of Energy and its contractors, in paper, from:
U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
phone: 865-576-8401
fax: 865-576-5728
email: reports@adonis.osti.gov(423) 576-8401

Available for sale to the public, in paper, from:
U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
phone: 800-553-6847
fax: 703-605-6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>

Printed in the United States of America

Total Pages: 15

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA**

CGI No. **CGI-SNF-D-07-P4-040**

Page 1 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

Section 1 Part Information

Item No.: **NA**

Manufacturer:

Supplier:

Mfg. Part/Model No.:

Supplier's P/N:

Part Description:

End Use Description:

Section 2a Component Information

Equipment No.: **VPS -
CKV-112**

Specification No.:
**SNF-5303
(W-441-P4)**

Manufacturer: **Nupro
Valve Mfg. Company**

Past P.O. No.: **NA**

Procurement and/or Model
No.: **SS-RL4M8F8**

Equipment Supplier (if different from manufacturer): **TBD**

Equip. Supplier's Part No.:
NA

Component Description: **This valve is a 1/2 inch check / relief valve located between the MCO pressure safety element and the process vent. The valve limits release volumes to the local exhaust duct.**

Section 2b Qualified Vendor/Supplier Survey

1. Is the Item available from a catalogue of a qualified NQA1 supplier? (coordinate with project CGI interface Engineer or BTR)

☐ YES (go to #2 below)

☒ NO (go to procedure step 5.3.2, proceed to dedicate Item.)

If not available from a qualified NQA1 supplier, is it available from an ISO 9000 supplier? (coordinate with project CGI interface Engineer or BTR)

☐ YES (go to #2 below, then go to procedure step 5.3.2, proceed to dedicate Item)

☒ NO (go to procedure step 5.3.2, proceed to dedicate Item.)

2. List of Candidate qualified suppliers or ISO 9000 suppliers

company name and type

contact name

phone

NA

3. Recommended Procurement Strategy (coordinate with project CGI interface Engineer or BTR):

NA

Section 2c CGI Determination

1. Question #1: Is the Item subject to design or specification requirements that are unique to nuclear facilities or activities?

☐ YES (the Item is not commercial grade)

☒ NO (continue)

2. Question #2: Is the Item used in applications other than nuclear facilities or activities?

☐ NO (the item is not commercial grade)

☒ YES (continue)

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA**

CGI No. **CGI-SNF-D-07-P4-040**

Page 2 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

3. Question #3: Is the Item ordered from manufacturer/supplier on the basis or specifications set forth in the Published product information (e.g., manufacturers catalog)?

☐ NO (the Item is not commercial grade)

☒ YES (continue)

☒ **All three criteria have been satisfied. The Item meets the definition of commercial grade.**

Section 2d Reason for Dedication

The above described Item is being Dedicated for use in the application cited for the following reason(s):

☒ Item is being purchased from a non ESL manufacturer supplier as commercial grade to be used in a Safety Class application.

☐ Item is being purchased from a non ELS manufacturer supplier as commercial grade to be used in a Safety Significant application.

☐ Item was purchased from a non ESL manufacturer supplier as commercial grade to be used in a Safety Class application.

☐ Item was purchased from a non ESL manufacturer supplier as commercial grade to be used in a Safety Significant application.

☐ Other ('like-for-like', similar, substitution, replacement evaluation)

Section 3 Failure Effects Evaluation

A. Part/Component Safety Function:

1. **Check valve relief range limits release of hydrogen to the local exhaust duct.**

2. **Check valve relief range limits release of radioactive material from the MCO.**

3. **Check valve opens when required to provide overpressure relief path.**

4. **Maintain critical function before and after Seismic event.**

B. Part/Component Functional Mode:

Safety Function #1:

☒ Active – Mechanical or Electrical change of state is required to occur for the component to perform its safety function

☐ Passive – Change of state is not required for the component to perform its safety function

Safety Function #2:

☒ Active – Mechanical or Electrical change of state is required to occur for the component to perform its safety function.

☐ Passive – Change of state is not required for the component to perform its safety function

Safety Function #3:

☒ Active – Mechanical or Electrical change of state is required to occur for the component to perform its safety function.

☐ Passive – Change of state is not required for the component to perform its safety function

Safety Function #4:

☐ Active – Mechanical or Electrical change of state is required to occur for the component to perform its safety function.

☒ Passive – Change of state is not required for the component to perform its safety function

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA**CGI No. **CGI-SNF-D-07-P4-040**

Page 3 of 12

**Title: NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**C. Host Component Safety Function (if applicable): **NA**

1.

D. Failure Mechanisms(s) and the effects on component or system safety function (see worksheet 1):

1. **Seizure – failure of the check valve to close as required, resulting in greater release volumes to the local exhaust duct.**
2. **Fracture of the valve body or piping attachment, resulting in greater release volumes to the local exhaust duct.**
3. **Seizure -- failure of the check/relief valve to open as required, resulting in functional impairment of the pressure safety element, VPS-PSE-1*33.**

Section 4 Environmental & Natural Phenomena Hazard Design

Environmental Qualification Required:

Yes []

No [**X**]**Environmental Condition B**

If yes: Environmental Qualification Requirements

Limiting Environmental Conditions:

Required Safety Functions:

Qualification Period:

Natural Phenomena Hazard (NPH) Design Required:

Yes [**X**]

No []

HNF-PRO-97**SNF-5303**

If yes: NPH Design Requirements

Performance Category: **PC-3**NPH Design Req'ts.: **Seismic Condition A****Required Safety Functions: Check Valve Closure to Provide Isolation Between the Process Vent and the MCO; Confinement; open when required to provide overpressure relief path.****Section 5 Component Functional Classification**[**X**] Safety Class (SC)

[] General Service

[] Safety Significant (SS)

If part/component classification is different from host component/system, document basis.

Section 6 [reserved]**Section 7 [reserved]****Section 8 References (for Functional Classification)**

National Codes/Standards:

ASME B31.3

Safety Analysis Report (SAR):

HNF-3553, Annex B

Drawings:

H-1-82161; HNF-SD-SNF-SEL-002, +ECN 652269Vendor Manuals/Manufacturer/Supplier Information: **Nupro Company - "RL4" Series Low Pressure Proportional Relief Valves.**

Other:

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA** CGI No. **CGI-SNF-D-07-P4-040**

Page 4 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

Section 9 Critical Characteristics				
Critical Characteristics Verification Document: Vendor Specifications, HNF-SD-SNF-SEL-002, ECN 652269	Acceptance Criteria/Tolerances	Acceptance Method	ID	Function
1. Item Identification Critical Characteristics (necessary for reasonable assurance that the Item delivered is the Item specified)				
Nameplate - Manufacturer	NUPRO Valve Mfg. Company	1,IN	X	
Component Number- Procurement and/or Model Number	SS-RL4M8F8 , (Per SNF-5303, Section H, Design Data Sheet)	1,IN	X	
Process Connection, Inlet/outlet	1/2" Male NPT X 1/2" FNPT	1,IN	X	
2. Physical Critical Characteristics (necessary for reasonable assurance that the Item delivered is the Item specified)				
Material, Body	Stainless Steel (Note 4)	1, IN, 1,T	X	
Material, Process Connection	Stainless Steel (Note 4)	1, IN, 1,T	X	
"A" Dimension	Maximum 5.43 inch	1, IN	X	
3. Performance Critical Characteristics (necessary & sufficient for reasonable assurance that the Item will perform its intended safety function(s))				
Confinement	No leakage at test pressure of 165 psig. Note 3.	1,T		X
Cracking Pressure Setting	≤34 ± 0.5 psig. Lockwire to be in place to maintain pressure relief setting after test.	1,T		X
Reseal Pressure	Reseal must occur ≥21 ±0.5 psig.	1,T		X
Seat Leakage, Reverse Flow After Cracking	Pressure test to design pressure (150 psig) (No continuous bubble formation,)	1,T		X
Environmental	Note 1			
Seismic Condition A	Note 2	1,T		X
Flow Rate	N/A			

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA**

CGI No. **CGI-SNF-D-07-P4-040**

Page 5 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

4. Notes and Legend:

1. The check / relief valve bonnet seal, stem seal, and bonded poppet seal (VITON) is not subject to degradation at ambient conditions of 40°F and 60% RH or 115°F and 22% RH and is suitable for Environmental Condition B application.
2. Maintain critical function before and after Seismic event. SNF-5303, Appendix L, page L-18 provides a seismic testing plan for this safety class, Seismic Condition A component at a Seismic Spectra SNF-4896. Equipment that has been shaker-table tested should not be installed in a plant (Ref. IEEE Standard 344-1984, Section 7). Consequently, the seismic test constitutes a destructive test. The industry sampling practice for destructive test is to test only one item.
3. Pressure test at 110% of design accident condition pressure of 150 psig.
4. Material verification acceptance method may be by either inspection or test.

Rev. 2: Updated reference documentation.

Rev. 3: Removed requirement for valve flow testing per RFI HO-183.

Rev. 4 Changed cracking pressure from nominal 30 psig to $\leq 34 \pm 0.5$ psig, changed reseal pressure from >20 psig to $\geq 21 \pm 0.5$ psig per ECN 663394.

Rev. 4a Changed Vendor Manual reference from HL4 series to RL4 series, changed "A" dimension height from Nominal to Maximum per ECN 663395.

Rev. 5 Incorporated changes from Rev. 4a, Removed Internal Pressure 150 psig and Vacuum, Increased sample size to 100 % for cracking pressure and for reseal pressure due to failure in sample lot, Changed bubble tight standards...to No Continuous Bubble Formation.

Acceptance Method:

1. Special Test and Inspection
1,IN for Inspection
1,T for Test
2. Commercial Grade Survey
3. Source Verification
4. Vendor/Item History

Section 10 Initial Reviews and Approvals

Approvals:

Designated Engineer: *ana per telecom for*
Carl Van Katwyke 10/9/00

Design Authority: *[Signature] 10-7-00*

QA Engineer: *[Signature] 10/9/00*

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA** CGI No. **CGI-SNF-D-07-P4-040**

Page 6 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

WORKSHEET 1 DETERMINATION OF FAILURE MECHANISMS/MODES

SECTION 1

Typical Failure Mechanisms	Definition	Applicable to Component under Evaluation	
Fracture	Separation of a solid accompanied by little or no macroscopic plastic deformation.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Corrosion	The gradual deterioration of a material due to chemical or electrochemical reactions, such as oxidation, between the material and its environment.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Erosion	Destruction of materials by the abrasive action of moving fluids, usually accelerated by the presence of solid particles carried with the fluid.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Open Circuit	An electrical circuit that is unintentionally broken so that there is no complete path for current flow.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Short Circuit	An abnormal connection by which an electrical current is connected to ground, or to some conducting body, resulting in excessive current flow.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Blockage	Clogging of a filtering medium resulting in the inability to perform its purification function or blockage of flow.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Seizure	Binding of a normally moving item through excessive pressure, temperature, friction, jamming.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Unacceptable Vibration	Mechanical oscillations produced are beyond the defined permissible limits due to unbalancing, poor support, or rotation at critical speeds.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Loss of Properties	A loss of mechanical and physical properties of a material due to exposure to high temperatures, radiation exposure.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Excess Strain	Under the action of excessive external forces the material of the part has been deformed or distorted.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Mechanical Creep	From prolonged exposure to high temperature and stress, the object will show a slow change in its physical (shape and dimension) and mechanical characteristics.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____
Ductile Fracture	Fracture characterized by tearing of metal accompanied by appreciable gross plastic deformation.	Yes [] Mode. _____	No [X]; If Yes, indicate failure Mode. _____

Section 2 Additional Failure Modes Applicable to the Component Under Evaluation

- Failure of check valve to seat and prevent reverse flow/failure of check valve to open and provide flow path for pressure safety element VPS -PSE-1*33.**
- Process connection/body break.**

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA** CGI No. **CGI-SNF-D-07-P4-040**

Page 7 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

CHECKLIST 1

ACCEPTANCE METHOD 1

SPECIAL TEST/INSPECTION VERIFICATION

SECTION 1			
Item Description: Nupro Process Vent/MCO Check / Relief Valve		Equip #: VPS-CKV-*112	
System #: 07		Procurement and/or Model #: SS-RL4M8F8	
Manufacturer (Address/Phone): Nupro Valve Mfg. Company		Supplier (Address/Phone):	
P.O. #			
SECTION 2 CRITICAL CHARACTERISTICS TO BE VERIFIED BY METHOD 1.			
Insp	Test	Post-Test	
☒	☐	☐	1. Nameplate - Manufacturer
☒	☐	☐	2. Component Number-Procurement and/or Model Number
☒	☐	☐	3. Process Connection
☒	☐	☐	4. "A" Dimension
☒	☒	☐	5. Material, Body (Verification may be by either inspection or test)
☒	☒	☐	6. Material, Process Connection (Verification may be by either inspection or test)
☐	☒	☐	7. Confinement
☐	☒	☐	8. Cracking Pressure Setting
☐	☒	☐	9. Reseal Pressure
☐	☒	☐	10. Seat Leakage, Reverse Flow After Cracking
☐	☒	☐	11. Seismic Condition A
☐	☐	☐	12.
SECTION 3 VERIFY BY INSPECTION			
* See Appendix D, Table D-1 of Administrative Procedure EN-6-035-01 for Sampling Size			
Characteristic: Nameplate - Manufacturer			
Sample Size*: All Items			
Acceptance Criteria: NUPRO Company			
Receipt Inspection Plan / Report #: _____			
References (see Section 7): _____			

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA** CGI No. **CGI-SNF-D-07-P4-040**

Page 8 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE --
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

Characteristic: **Component Number-Procurement and/or Model Number**

Sample Size*: **All Items**

Acceptance Criteria: **SS-RL4M8F8 , (Per SNF-5303, Section H, Design Data Sheet)**

Receipt Inspection Plan / Report #: _____

References (see Section 7): **Nupro Company - "RL4" Series Low pressure Proportional Relief Valves.**

Characteristic: **Process Connection, Inlet / Outlet**

Sample Size*: **All Items**

Acceptance Criteria: **1/2" Male NPT X 1/2" FNPT**

Receipt Inspection Plan / Report #: _____

References (see Section 7): _____

Characteristic: **Material, Body**

Sample Size*: **Normal Sample Size**

Acceptance Criteria: **Stainless Steel**

Receipt Inspection Plan / Report #: _____

References (see Section 7): _____

Characteristic: **Material, Process Connection**

Sample Size*: **Normal Sample Size**

Acceptance Criteria: **Stainless Steel**

Receipt Inspection Plan / Report #: _____

References (see Section 7): _____

Characteristic: **"A" Dimension**

Sample Size*: **Normal Sample Size**

Acceptance Criteria: **Maximum 5.43 inch**

Receipt Inspection Plan / Report #: _____

References (see Section 7): _____

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. **NA** CGI No. **CGI-SNF-D-07-P4-040**

Page 9 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

SECTION 4 VERIFY BY SPECIAL TEST

* See Appendix D, Table D-1 of Administrative procedure EN-6-035-01 for Sampling Size

Test To Be Performed by:

☐ Purchaser

☐ Supplier/Manufacturer**

☐ Other

Number of Items to be Tested:

Test/Inspection Location:

Characteristic for Test: **Confinement**

Acceptance Criteria: **No Leakage at Test Pressure of 165 psig**

Sample Size*: **Normal Sampling Size**

Actual Test Value:

Test Plan and Report #: _____ References (see Section 7): _____

Characteristic for Test: **Cracking Pressure Setting**

Acceptance Criteria: **$\leq 34 \pm 0.5$ psig. Lockwire to be in place to maintain pressure relief setting after test.**

Sample Size*: **100% due to failure of item in Sample lot.**

Actual Test Value:

Test Plan and Report #: _____ References (see Section 7): _____

Characteristic for Test: **Reseal Pressure**

Acceptance Criteria: **Reseal must occur $\geq 21 \pm 0.5$ psig.**

Sample Size*: **100% due to failure of item in Sample lot.**

Actual Test Value:

Test Plan and Report #: _____ References (see Section 7): _____

Characteristic for Test: **Seat Leakage, Reverse Flow After Cracking**

Acceptance Criteria: **Pressure test to design pressure (150 psig) (No continuous bubble formation.)**

Sample Size*: **Normal Sampling Size**

Actual Test Value:

Test Plan and Report #: _____ References (see Section 7): _____

Characteristic for Test: **Seismic Condition A**

Acceptance Criteria: **Maintain Critical Function Before and After Seismic Event**

Sample Size*: **Destructively Test Only One Item**

Actual Test Value:

Test Plan and Report #: _____ References (see Section 7): _____

**If Supplier/Manufacturer or Other, Refer to CGI Checklist-2 for Support Information

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. NA CGI No. CGI-SNF-D-07-P4-040

Page 10 of 12

Title: NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE -
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO

SECTION 5 TEST / INSPECTION SUMMARY (Acceptance Method 1)

1. SUMMARY OF VERIFIED CRITICAL CHARACTERISTICS, THEIR VERIFICATION METHODS, AND RESULTS

ITEM DESCRIPTION:

Critical Characteristics				Verification Results							
Critical Characteristics	Acceptance Criteria/Tolerances	ID	Function	Method T/IN	Procedure or RR#	Check- list ID	Number Tested	Number Failed	Verifying Organization	Printed Name Signature	Date
Nameplate - Manufacturer	Nupro Valve Mfg. Company	X		1,IN							
Component Number- Procurement and/or Model Number	SS-RL4M8F8, (Per SNF- 5303, Section H, Design Data Sheet)	X		1,IN							
Process Connection	1/2 inch MNPT X 1/2 inch FNPT	X		1, IN							
"A" Dimension	Maximum 5.43 inch	X		1, IN							
Material, Body	Stainless Steel	X		1,IN							
Material, Process Connection	Stainless Steel	X		1,IN							
Confinement	No Leakage at Test Pressure of 165 psig (No Bubbles)		X	1,T							

2. DISPOSITION OF UNVERIFIED OR FAILED CRITICAL CHARACTERISTICS

Critical Characteristic	Disposition

3. SIGNATURE INDICATES ALL CRITICAL CHARACTERISTICS VERIFIED SATISFACTORY OR ACCEPTABLY DISPOSITIONED AND COMMERCIAL GRADE DEDICATION IS SATISFACTORY AND COMPLETE.

BUYER VERIFICATION	
Testing Agency Approval: _____ Date _____	Design Authority: _____ Date _____
Testing Agency QA Engineer: _____ Date _____	QA Engineer: _____ Date _____

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. NA CGI No. CGI-SNF-D-07-P4-040

Page 11 of 12

Title: NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE -
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO

1. SUMMARY OF VERIFIED CRITICAL CHARACTERISTICS, THEIR VERIFICATION METHODS, AND RESULTS

ITEM DESCRIPTION: 2

Critical Characteristics				Verification Results							
Critical Characteristics	Acceptance Criteria/Tolerances	ID	Function	Method T/IN	Procedure or RR#	Check- list ID	Number Tested	Number Failed	Verifying Organization	Printed Name Signature	Date
Cracking Pressure Setting	≤34 ± 0.5 psig. Lockwire to be in place to maintain pressure relief setting after test.		X	1, T							
Reseal Pressure	Reseal must occur ≥21 ±0.5 psig.		X	1, T							
Seat Leakage, Reverse Flow After Cracking	Pressure test to design pressure (150 psig) (No continuous bubble formation)		X	1, T							
Seismic Condition A	Maintain Critical Function Before and After Seismic event.		X	1, T							

2. DISPOSITION OF UNVERIFIED OR FAILED CRITICAL CHARACTERISTICS

Critical Characteristic	Disposition

3. SIGNATURE INDICATES ALL CRITICAL CHARACTERISTICS VERIFIED SATISFACTORY OR ACCEPTABLY DISPOSITIONED AND COMMERCIAL GRADE DEDICATION IS SATISFACTORY AND COMPLETE.

Testing Agency Approval: _____	Design Authority: _____	BUYER VERIFICATION
Testing Agency QA Engineer: _____	QA Engineer: _____	
	Date _____	Date _____
	Date _____	Date _____

Commercial Grade Item Upgrade Dedication Form

SNF-3933, Rev. 5

ECN No. NA CGI No. CGI-SNF-D-07-P4-040

Page 12 of 12

Title: **NUPRO PROCESS VENT/MCO CHECK / RELIEF VALVE –
PREVENT BACK FLOW FROM PROCESS VENT INTO MCO**

SECTION 6 CONTACTS/PHONE NUMBERS

Name	Phone
Design Authority	()
QA	()
QC	()
Cog - Engineer	()
CGI Engineer	()
Procurement Engineer	()
Other	()

SECTION 7 SUPPORTING DOCUMENTATION FOR THIS CHECKLIST

Initial Procurement Documents	For Critical Characteristics
☐ Drawings:	
☐ Manuals (specify type & number):	
☐ Design Calculations	
☐ Installation Instructions	
☐ Operation Instructions	
☐ Calibration Instructions	
☐ Manufacturer's Recommended Spare Parts List	
☐ Other:	
Procurement Documents	
☐ Certificate of Conformance/Compliance	
☐ Seismic Qualification Certificate	
☐ Environmental Qualification Certificate	
☐ Test Report (s):	
☐ Inspection Report (s):	
☐ CMTRs for ASME Pressure Retaining Materials	
☐ Valve Seat Leakage Report	
☐ Weld Records	
☐ Material Traceability Record	
☐ Other:	