Evaluation of Roof Bolting Requirements Based on In-Mine Roof Bolter Drilling

(Contract No. DE-FC26-01NT41056)

Project Duration: Dec. 18, 2000 – Dec. 17, 2003

Quarterly Technical Progress Report

Report Period

July 1, 2002 – Sept. 30, 2002

Syd S. Peng (Principal Investigator)

*Department of Mining Engineering
West Virginia University
Morgantown, WV 26506-6070
Tel: 304-293-7680 ext. 3301
E-mail: sspeng@mail.wvu.edu*

October 15, 2002

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

Additional field tests have been performed in this quarter. The development of the data interpretation methodology and other related tasks are still continuing.

TABLE OF CONTENTS

Disclaimer

Abstract

Research Objectives

Experimental

Results and Discussion

1. Characterizing the Rock Strata
2. Exploring the Roof Bolting Mechanisms
3. Development of On-Board Data Visualization and Database Program

Conclusions

Reference

Research Objectives

Roof bolting is the most popular method for underground openings in the mining industry, especially in the bedded deposits such as coal, potash, salt etc. In fact, all U.S. underground coal mine entries are roof-bolted as required by law.

However, roof falls still occur frequently in the roof bolted entries. The two possible reasons are: the lack of knowledge of and technology to detect the roof geological conditions in advance of mining, and lack of roof bolting design criteria for modern roof bolting systems.

This research is to develop a method for predicting the roof geology and stability condition in real time during roof bolting operation. Based on such information, roof bolting design criteria for modern roof bolting systems will be developed for implementation in real time.

For the prediction of roof geology and stability condition in real time, a micro-processor will be used and a program (ROOFSTAB) developed to monitor the drilling parameters. These parameters include thrust, penetration rate, rotation torque, rotation rate, drill position, and vacuum condition. At the same time, rock cores will be obtained a borehole drilled immediate next to bolt hole for the determination of the mechanical properties and structure of the rock strata within the bolting horizon. A relationship or relationships will be established between these drilling parameters and the mechanical and structural data of the roof strata. A roof bolter control system will be developed to monitor these drill parameters. For the development of ROOFSTAB drilling parameters will be obtained from four different coal seams in four mine sites. With this information, a computer program will be developed for use in conjunction with the roof bolter for real-time prediction of strata mechanical properties and structures in roof strata within the bolting horizon.

For the development of roof bolting design criteria, numerical simulations will be performed to investigate the mechanisms of modern roof bolting systems including both the tension and non-tensioned (or fully grouted) bolts. Parameters to be studied are: bolt size/strength, bolt length, bolt spacing, grout annulus and length, and roof geology (massive strata, fractured, and laminated or thinly-bedded). The results of these experiments will be analyzed to develop a roof bolting criterion or criteria program (ROOFBOLT) that will be combined with the ROOFSTAB for use in conjunction with roof bolt installation.

The following main tasks are to be performed for achieving the proposed research objectives:

- A.** Development of Operator Control Technology for Monitoring Roof Bolter Drill Operations Parameters.
- B.** Laboratory and Underground Testing.
- C.** Drill Parameters Data Analysis and Correlation with Roof Stability Conditions Software Development for Mapping of Roof Geological Conditions
- D.** Laboratory Tests to Investigate the Mechanisms of Roof Bolting Using Simulated Materials
- E.** Development of Roof Bolting Design Criteria for Implementation in Primary Roof Bolting Cycle

EXPERIMENTAL

Additional field tests have been conducted at a Peabody coal mine in southern West Virginia.

RESULTS AND DISCUSSION

The objective of this research project is to develop the methodology for evaluating the geology and stability condition of the roof strata of underground openings in real-time during roof bolting operation. Based on such information, bolting requirements for modern roof bolting systems will be developed for implementation in real time. The following main items of works performed in this reporting period are listed:

1. Characterizing the Rock Strata

Development of the systematic and mechanics-based approach for interpreting the drilling parameters is still continuing. One technical paper detailing the development of the data interpretation methodology has been presented at the 21st International Conference on Ground Control in Mining to be held at Morgantown, Aug. 7- 9, 2002 and published in its proceedings.

2. Exploring the Roof Bolting Mechanisms

In studying the mechanisms involved in roof bolting, three-dimensional finite element models for simulating the tensioned bolt have been developed and refined. Two-dimensional finite element models for simulating the fully grouted resin bolts have also been developed and refined. The effects of sliding and separation of bedding planes have been considered in these models. Based on the numerical modeling results, the design criteria for tensioned and fully grouted resin bolts are being developed. The yielding zone developed over the entry can be used to determine the bolt length, the magnitude of plastic strain can be used to judge the roof local stability, and the stress distribution around the entry and bolt load are also used to check roof stability.

Two technical papers reporting the findings of this numerical modeling have been presented at the 21st International Conference on Ground Control in Mining to be held at Morgantown, Aug. 7- 9, 2002 and published in its proceedings.

3. Development of On-Board Data Visualization and Database Program

The development of a computer program to display the original and derived drilling parameters, the identified rock types and geological structures in the bolting horizon in 2-D and 3-D is continuing in this quarter.

Evaluation of Roof Bolting Requirements Based on In-Mine Roof Bolter Drilling

- **Funding:** \$1,352,338
- **Sponsor:** US DOE IOF – Mining
- **Research Partners:**
 - West Virginia University
 - J.H. Fletcher and Company
 - Consol Energy
 - Peabody Energy
 - Marrowbone Development Corp.
- **Project Duration:** 3 Years
- **Status:** 2nd Year
- **Research Objectives:**
 - Develop a computerized method to evaluate the roof geology using the drilling parameters during bolting operation in real-time
 - Develop roof bolt system design requirements based on the real time evaluation of roof geology and stability conditions.
 - Develop a computer program that will work with the bolter for real time production of the mechanical properties, structures of roof strata and design requirements for roof bolt systems

Sandstone
Crack
Laminated Shale
Shale

Underground Testing

Drill Control Unit

Progress on Planned Tasks

Tasks Planned in the Proposal	Progress
A. Development of Operator Control Technology for Monitoring Roof Bolter Drill Operation Parameters	As detailed in item No. 1
B. Laboratory and Underground Testing	As detailed in item No. 1
C. Drill Parameter Data Analysis and Correlation with Roof Stability Conditions	As detailed in item No. 1
D. Software Development for Mapping of Roof Geological Conditions	As detailed in item No. 3
E. Computer Modeling to Investigate the Mechanisms of Roof Bolting	As detailed in item No. 2
F. Development of Roof Bolting Design Requirements for Implementation in the Primary Roof Bolting Cycle	As detailed in item No. 2

CONCLUSIONS

Additional field tests have been performed. The development of the data interpretation methodology is still continuing.

REFERENCE

- Luo, Y. S.S. Peng, B. Mirabile, G. Finfinger and G. Wilson, 2002, "Estimating Rock Strengths Using Drilling Parameters During Roof Bolting Operations – Progress Report," *Proc. 21st Int'l Conference on Ground Control in Mining*, Ed. S.S. Peng, C. Mark and A.W. Khair, pp. 288-293.
- Yassien, A., Y.Q. Zhang, J.S. Han and S.S. Peng, 2002, "Comparison of Some Aspects of Bolting Mechanisms Between Fully-Grouted Resin and Tensioned Bolts in Underground Mine Entries," *Proc. 21st Int'l Conference on Ground Control in Mining*, Ed. S.S. Peng, C. Mark and A.W. Khair, pp. 114-125.
- Zhang, Y.Q. and S.S. Peng, 2002, "Design Considerations for Tensioned Bolts," *Proc. 21st Int'l Conference on Ground Control in Mining*, Ed. S.S. Peng, C. Mark and A.W. Khair, pp. 131-140.