AUG 07 2000 (24) S

Station 4

ENGINEERING DATA TRANSMITTAL

Page 1 of 4
1. EDT 629049

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) Process Engineering		4. Related EDT No.:							
5. Proj./Prog./Dept./Div.: Spent Nuclear Fuel Project		6. Design Authority/ Design Agent/Cog. Engr.: R. A. Sexton		7. Purchase Order No.: N/A							
8. Originator Remarks: For release				9. Equip./Component No.: N/A							
				10. System/Bldg./Facility: N/A							
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No				12. Major Assm. Dwg. No.: N/A							
				13. Permit/Permit Application No.: N/A							
				14. Required Response Date: N/A							
15. DATA TRANSMITTED											
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	(F) Approval Design- ator	(G) Reason for Trans- mittal	(H) Origina- tor Dispo- sition	(I) Receiv- er Dispo- sition			
1	HNF-3635	N/A	0	Spent Nuclear Fuel Removal Campaign Plan	S ^N , Q, E	1	1	1			
16. KEY											
Approval Designator (F)		Reason for Transmittal (G)			Disposition (H) & (I)						
E, S, Q, D or N/A (see WHC-CM-3-5, Sec. 12.7)		1. Approval 2. Release 3. Information 4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)			1. Approved 2. Approved w/comment 3. Disapproved w/comment 4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged						
17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)											
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
1	1	Design Authority	L. H. Goldmann	6/21/00	R3-86	1	1	J. D. Mathews	6/21/00	X3-65	
		Design Agent	N/A			1	1	K. R. Morris	6/21/00	X3-74	
1	1	Cog. Eng.	R. A. Sexton	6-2-00	R3-86	1	1	A. L. Pajunen	6/21/00	R3-86	
1	1	Cog. Mgr.	J. R. Frederickson	6/21/00	R3-86	1	1	T. J. Ruane	7/25/00	X3-61	
1	1	QA	S. S. Moss	6-5-2000	R3-11	1	1	J. R. Gregory	7/21/00	X3-78	
1	1	Safety	R. L. Gensch	8/1/00	R3-20	1	1	C. D. Lucas	7-19-00	X3-74	
1	1	Env.	D. J. Watson	7/27/00	X3-	1	1	O. M. Serrano	000007	S2-44	
18. R. A. Sexton Signature of EDT Originator Date 6-2-00		19. J. R. Frederickson Authorized Representative Date 8/7/00		20. J. R. Frederickson Design Authority/ Cognizant Manager Date 8/7/00		21. DOE APPROVAL (if required) Ctrl. No. N/A ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments					

Spent Nuclear Fuel Removal Campaign Plan

Prepared for the U.S. Department of Energy
Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the
U.S. Department of Energy under Contract DE-AC06-96RL13200

Fluor Hanford

P.O. Box 1000

Richland, Washington

Spent Nuclear Fuel Removal Campaign Plan

A. L. Pajunen
Fluor Hanford

R. A. Sexton
Technical Resources International, Inc.

Date Published
June 2000

Prepared for the U.S. Department of Energy
Assistant Secretary for Environmental Management

Project Hanford Management Contractor for the
U.S. Department of Energy under Contract DE-AC06-96RL13200

Fluor Hanford
P.O. Box 1000
Richland, Washington

Release Approval

8/7/00
Date

Release Stamp

TRADEMARK DISCLAIMER

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy. Available in paper copy and microfiche.

Available electronically at <http://www.doe.gov/bridge>. Available for a processing fee to the U.S. Department of Energy and its contractors, in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
phone: 865-576-8401
fax: 865-576-5728
email: reports@adonis.osti.gov(423) 576-8401

Printed in the United States of America

Total Pages: 51

SPENT NUCLEAR FUEL REMOVAL CAMPAIGN PLAN

Table of Contents

1.0 Introduction.....	1
2.0 Fuel Removal Campaigns (Fuel Selection)	3
2.1 K West Basin Campaigns	3
2.1.1 K West Mk 1A Fuel Removal	4
2.1.2 K West Mk IV Fuel Removal	4
2.1.3 Single Pass Reactor Fuel Removal	7
2.2 K East Basin Campaigns.....	7
2.2.1 K East Mk IV Fuel Removal.....	10
2.2.2 Single Pass Reactor Fuel Removal	11
2.3 Projected K Basin MCO Characteristics.....	11
2.3.1 K West Basin MCOs.....	11
2.3.2 K East Basin MCOs	15
3.0 Process Validation	18
4.0 Canister Storage Building.....	20
4.1 Startup MCO Positions	20
4.2 MCO Monitoring	20
5.0 Fuel Removal Closeout.....	21
6.0 References.....	22
Appendix A. K West Basin Fuel Canister Descriptions	A-1
Appendix B. K West Basin MCO Descriptions.....	B-1
Appendix C. K East Basin MCO Descriptions.....	C-1

SPENT NUCLEAR FUEL REMOVAL CAMPAIGN PLAN

1.0 Introduction

The overall operation of the Spent Nuclear Fuel Project will include fuel removal, sludge removal, debris removal, and deactivation transition activities. Figure 1-1 provides an overview of the current baseline operating schedule for project sub-systems, indicating that a majority of fuel removal activities are performed over an approximately three-and-one-half year time period. The purpose of this document is to describe the strategy for operating the fuel removal process systems.

The campaign plan scope includes:

- identifying a fuel selection sequence during fuel removal activities,
- identifying MCOs that are subjected to extra testing (process validation) and monitoring, and
- discussion of initial MCO loading and monitoring in the Canister Storage Building (CSB).

The campaign plan is intended to integrate fuel selection requirements for handling special groups of fuel within the basin (e.g., single pass reactor fuel), process validation activities identified for process systems, and monitoring activities during storage.

Figure 1-1. Spent Nuclear Fuel Baseline Operating Schedule

2.0 Fuel Removal Campaigns (Fuel Selection)

The K Basin fuel inventory is grouped into campaigns based on processing fuel with common handling characteristics. Separate groups of campaigns are defined for each basin which can generally be performed independent from one another (Single Pass Reactor fuel is the only exception to this generalization). This independence is necessary since the planned operating schedule, shown in Figure 1-1, anticipates K West fuel removal being nearly completed before K East fuel removal startup. No routine N Reactor fuel transfers between basins are currently planned to support fuel removal activities. Therefore, physical location represents the initial attribute for defining different fuel removal campaigns.

The project accountability strategy is developed in Morris, 1998. The analysis in Morris, 1998 identifies fuel keys stored in each basin that must be blended to limit the plutonium inventory within constraints used for designating the attractiveness category of MCOs. This strategy requires that canisters in high plutonium keys be combined with lower plutonium material to ensure each MCO contains less than 15.5 kg Pu. Some key blending will be required during fuel removal from each basin.

Fuel selection is described in this report by projecting the MCO characteristics that result from an idealized implementation of the strategy. These MCO characteristics are developed from a matrix describing the available information on canisters in each position in the basins. The canister data are a union of safeguards inventory data, computer predictions, and characterization program data.

Safeguards inventory data are used for the canister position, piece count, key number, plutonium inventory, ^{240}Pu isotopic content, and uranium inventory. In most cases, the fuel key number indicates the fuel discharge date (key number 001 $\equiv$ September 26, 1944). Computer predictions are used to estimate the fuel heat load decayed to a common fuel removal startup date of November 30, 2000 in each canister. The heat load is based on fuel key number and ^{240}Pu isotopic content (see Pajunen, 1998 and Packer, 1998 for radionuclide and heat load calculations for each key in the K West and K East basins, respectively). The characterization program data consist of visual observations indicating the condition of fuel in most K East and a few K West canisters. In addition, any notes on fuel condition from prior segregation campaigns and canister gas/liquid sample results (K West basin specific) are included from characterization program notes.

2.1 K West Basin Campaigns

The K West Basin contains Mk IV N Reactor fuel, Mk 1A N Reactor fuel, and Single Pass Reactor (SPR) fuel. Different fuel and scrap basket designs have been developed for Mk IV and Mk 1A N Reactor fuel based on criticality control criteria. The design differences result in a system where Mk 1A fuel must be placed in baskets of the proper design. The only exception to this is one canister (canister lid #7939) which contains 12 E length Mk 1A fuel assemblies that are the same length as the longest Mk IV fuel assemblies. Criticality analyses were completed (Kessler, 2000) to allow loading this single canister of Mk 1A fuel in Mk IV fuel baskets and a Mk IV MCO. While it is possible to place Mk IV fuel in either basket and satisfy criticality

constraints, most Mk IV fuel is longer than the Mk 1A fuel basket and will not fit in the alternate basket design. This plan includes, for information purposes, plans for processing of SPR fuel. However, current versions of the Safety Analysis does not include SPR fuel. It has been left for a future revision of the SAR. Current plans are based on development of Mk 1A fuel basket hex tube assembly inserts for loading SPR fuel. The importance of controlling the basket design used during fuel removal forms the basis for working on one fuel type at a time.

Figure 2-1 describes the development of fuel selection, which forms the basis for K West basin campaigns. Fuel type is the first basis for fuel selection to control matching fuel and basket type, as described above. A further subdivision is made based on plutonium blending requirements.

The FRS process validation is planned during the Phased Startup Initiative (PSI), Phase IV. This will demonstrate that selected cleaning machine operating parameters provide acceptable confidence of satisfying the cleaning criteria. Once process validation is complete, production can be performed without inspecting each fuel element.

2.1.1 K West Mk 1A Fuel Removal

Mk 1A fuel will be removed first because the schedule for fabrication of Mark 1A baskets precedes that of Mark IV baskets. A great deal of flexibility is available in selecting Mk 1A fuel during this campaign. Potential goals to be achieved include minimizing the number of open keys for simplification of accountability records and emphasizing removal of fuel around the fuel retrieval equipment. While the MCO characteristics described in Section 2.3.1 are based on a sequence of canister processing, the only fuel selection requirement for this part of the Mk 1A fuel processing campaign is to complete removal of all Mk 1A fuel.

After about 2 MCOs have been processed, about 20 empty rack positions will be created near the front of the channel to the dummy elevator pit, to provide an empty canister staging area.

2.1.2 K West Mk IV Fuel Removal

The Mk IV fuel inventory in the K West basin contains three keys, identified in Morris, 1998, that need to be blended with other fuel keys to stay within the MCO plutonium inventory constraint. Therefore, the Mk IV fuel inventory is sub-divided into a plutonium blending campaign and other Mk IV fuel campaign.

Figure 2-1. K West Basin Fuel Selection Description

2.1.2.1 K West Plutonium Blending

Morris, 1998 identifies that Mk IV fuel in keys 21540, 22565, and 22852 would exceed the plutonium inventory limit established from safeguard considerations if loaded into MCOs without blending (See Tables B-1 and B-2 of reference). Based on this definition, these three keys, containing 70 canisters, are called "high Pu keys" and must be blended with fuel from other keys of lower plutonium content. Based on accountability data, the plutonium content of high Pu keys is bounded by the E length assemblies in key 22852, which contain approximately 67.2 g Pu/assembly.

Fuel key 13017 was selected for blending with the high Pu keys because it contains the lowest specific plutonium content available in the K West basin Mk IV material. This key contains approximately 39.2 g Pu/assembly. Maximum MCO loading flexibility during blending is maintained if the Pu content limit is maintained on a basket basis ($15,500/5 = 3,100$ g). This allows any basket produced during the blending campaign to be loaded in a MCO with any other basket produced during the campaign and still meets the MCO plutonium constraint. Criticality controls on fuel mass loaded in Mk IV scrap baskets limit loadings to 39 equivalent assemblies (975 kg). Therefore, the plutonium content of scrap baskets can not exceed 2,621 g (67.2×39), which is less than the plutonium constraint, even if all scrap comes from the high Pu key. An allowable inventory of high and low blend keys in each fuel basket can be estimated from the following inequalities.

$$67.2x + 39.2y \leq 3,100$$

$$x + y \leq 54$$

where: x = number of high Pu assemblies
 y = number of low Pu assemblies

The inequalities are satisfied when $x \leq 35$ assemblies, or less than 65% of the assemblies are from the high Pu key. This can be conservatively implemented by ensuring 50% of the assemblies are from the low Pu key and 50% of the assemblies are from the high Pu key. Adequate control of the basket plutonium inventory should be achieved by alternately retrieving a canister of fuel from the high and low Pu blend key. However, the number of assemblies from high Pu keys loaded in each fuel basket must be counted during basket loading. After it is verified that the number of high Pu assemblies loaded in a fuel basket is less than or equal to 35 (average of 27 expected) and baskets are moved to the basket queue, MCOs from plutonium blending will satisfy the plutonium inventory limit, independent of which stored fuel and scrap baskets are combined in a MCO.

2.1.2.2 Other Mk IV Fuel

Once the plutonium blending campaign is complete, a great deal of flexibility is available in selecting the remaining Mk IV fuel. Potential goals to be achieved include minimizing the number of open keys for simplification of accountability records and emphasizing removal of fuel around the fuel retrieval equipment. While the MCO characteristics described in Section 2.3.1 are based on a sequence of canister processing, the only fuel selection requirement for this part of the Mk IV fuel processing campaign is to complete removal of all Mk IV fuel.

The canister currently located in cubical 144 (canister lid #7939) is unique to the K West basin.

This canister contains 12 E length Mk 1A fuel assemblies that are the same length as the longest Mk IV fuel assemblies. Due to the small number of these assemblies, the Mk 1A fuel basket was designed for shorter fuel assemblies to improve MCO loading efficiency. Criticality analyses were completed (Kessler, 2000) to allow loading this single canister of Mk 1A fuel in Mk IV fuel baskets and a Mk IV MCO. Since this represents a unique situation, loading of this Mk 1A canister into a Mk IV fuel basket will be performed after all other Mk 1A fuel has been loaded in baskets. Kessler, 2000, specifies that any scrap generated during cleaning of this fuel must be placed in a Mk 1A scrap basket. For this reason, the E length Mk 1A canister will need to be processed before Mk IV canisters, and while a Mk 1A scrap basket is still available.

2.1.3 K West Single Pass Reactor Fuel Removal

Processing of SPR fuel must be included in a future revision of the SAR, but the strategy for processing it is discussed here for information purposes.

The strategy for handling SPR fuel is based on combining the 133 SPR assemblies stored in the K East basin with 833 SPR assemblies stored in the K West basin. This approach requires that SPR fuel removal from the two basins be integrated. Therefore, the schedule window for SPR fuel removal ranges from the start of K East fuel removal to the completion of K West fuel removal. In the current schedule, this window is only about 1 month long. An alternate strategy would be to process an SPR MCO for each basin. SPR fuel may not be mixed with N Reactor fuel.

The current concept for SPR fuel removes fuel from the basins using Mk 1A fuel and scrap baskets, adapted for SPR fuel loading. SPR fuel is first loaded into a MCO at the K East basin. It is expected that the MCO will need to contain a complete complement (6) of full and empty baskets while being transferred from the K East to K West basin to comply with MCO design analyses. Therefore, a MCO containing fuel must be received and opened at the K West basin and some of the baskets removed. The baskets are then loaded with SPR fuel and returned to the MCO.

The operations of receiving a MCO containing fuel, opening the MCO, handling a potentially contaminated shield plug, and removing baskets are all non-routine activities that must be performed at the K West basin in support of SPR fuel removal. Each of these activities has the potential for contaminating the K West water, or operating areas, which could result in a suspension of operations. Therefore, the timing of SPR fuel loadout is planned to be first fuel processed from the K East basin and the last MCO loaded in the K West basin, after completing the N Reactor fuel campaigns. This approach minimizes the impact that potential contamination delays would have on completing K West fuel removal.

2.2 K East Basin Campaigns

The K East basin contains Mk IV and SPR fuel. There is also a small quantity of Mk 1A fuel that was returned from the 300 Area after use for characterization. A single Mk 1A MCO will be processed in K East, containing the Mk 1A fuel and Mk IV elements that are short enough to fit in the Mk 1A basket. Figure 2-2 describes the development of fuel selection in the K East basin. Fuel type continues to be the first basis for fuel selection, but the selection must only

discriminate between SPR and N Reactor fuel. A further subdivision is made based on plutonium blending requirements.

Figure 2-2. K East Basin Fuel Selection Description

2.2.1 K East Mk IV Fuel Removal

Mk IV fuel is the dominant inventory of fuel in the K East. Multiple fuel keys are identified in Morris, 1998 that need to be blended with other fuel keys to stay within the MCO plutonium inventory constraint. Therefore, the Mk IV fuel inventory is sub-divided into a plutonium blending campaign and other Mk IV fuel campaign.

2.2.1.1 K East Plutonium Blending

The plutonium blending strategy described in Section 2.1.1.2 for K West basin was modified for K East basin because there are more high Pu keys and the fuel generally contains less plutonium per assembly. Morris, 1998 identifies 12 keys that are considered to be high Pu keys, requiring blending (see Table B-3 of reference). The high Pu keys are as follows:

10742	11183	11979
10982	11372	12127
11036	11449	12285
11109	11897	12480

Morris, 1998 also indicates these keys must be mixed with lower plutonium content keys at a 40:60 ratio (40% high plutonium, 60% lower plutonium content) in a MCO. However, the following discussion is used as a basis for simplifying the loading during plutonium blending at the K East basin.

As described in Section 2.1.2.1, a basket plutonium limit of 3,100 g is used as a basis for developing a loading plan. Of the high Pu keys, key 11897 contains the highest specific Pu content and is bounded by 60.71 g Pu/assembly (from canister location 4757). Based on this maximum plutonium content, the scrap basket inventory can not exceed 2,368 g Pu (39×60.71).

A large number of low Pu blend keys are available from the group of key numbers greater than 15000 (fuel discharged after October 1985). A sort of keys above 15000 indicates that the maximum specific Pu content of fuel in this group is 26.89 g Pu/assembly (see key 15240, canister location 1840). The allowable inventory of high and low blend keys in each fuel basket can be estimated from the following inequalities.

$$60.71x + 26.89y \leq 3,100$$

$$x + y \leq 54$$

where: x = number of high Pu assemblies
 y = number of low Pu assemblies

The inequalities are satisfied when $x \leq 48$ assemblies. This can be interpreted to imply that each fuel basket will comply with the plutonium inventory limit if each fuel basket contains at least 6 assemblies from key numbers greater than 15000. This approach can then be conservatively applied by loading at least one full canister of fuel (14 assemblies) with key number greater than 15000 in each fuel basket during the retrieval of the high Pu keys listed above. After proper

loading of the fuel baskets, MCOs from plutonium blending will satisfy the plutonium inventory limit, independent of which stored fuel and scrap baskets are combined in a MCO.

2.2.1.2 K East Other Mk IV Fuel

Once the plutonium blending campaign is complete, a great deal of flexibility is available in selecting the remaining Mk IV fuel. Potential goals to be achieved include minimizing the number of open keys for simplification of accountability records and emphasizing removal of fuel around the fuel retrieval equipment. While the MCO characteristics described in Section 2.3.2 are based on a sequence of canister processing, the only fuel selection requirement for this part of the Mk IV fuel processing campaign is to complete removal of all Mk IV fuel.

2.2.2 K East Single Pass Reactor Fuel Removal

The SPR fuel removal campaign is expected to start with fuel loading in the K East basin. The current plan is based on performing SPR fuel removal at the end of the K West basin operations (See Section 2.1.3).

2.3 Projected K Basin MCO Characteristics

The characteristics of MCOs produced by the above fuel selection plan were developed to provide an indication of expected MCO properties. The projected MCO characteristics are considered realistic approximations of actual MCO loading. However, it should be recognized that a great deal of fuel selection flexibility has been retained in the loading plan for most canisters. This flexibility is considered essential to allow operations to efficiently respond to canister condition uncertainties.

2.3.1 K West Basin MCOs

Figures 2-3 and 2-4 describe the plutonium and uranium inventory of MCOs from the K West basin assuming an idealized loading scheme that implements the above strategy. Overall, 203 MCOs containing N Reactor fuel are projected to be loaded assuming an average of one scrap basket per MCO (146 Mk 1A MCOs and 57 Mk IV MCOs). This projection is consistent with prior nominal estimates for the number of MCOs produced at the K West basin (Pajunen, 1997).

The actual scrap generation rate will impact the loadings actually observed in MCOs. The constraints on MCO Pu inventory were confirmed first for each campaign (Mk 1A, Mk IV Pu blending, and Other Mk IV). The canister selection basis was then arranged to minimize the number of keys open at any given time. When no other constraint defined fuel selection, the early removal of fuel from areas near the fuel retrieval system was emphasized.

Figure 2-3 indicates that MCOs generated during Mk IV high plutonium key blending will result in the highest plutonium inventory. It is not possible for the Mk 1A MCOs to approach the plutonium inventory constraint of 15,500 g Pu. Figure 2-4 indicates the anticipated difference in uranium loadings between Mk IV and Mk 1A MCOs. Based on the idealized loading, Mk IV MCOs are expected to contain around 6,000 kg U and Mk 1A MCOs are expected to contain approximately 4,200 kg U. One partial MCO load is currently predicted at the end of each N Reactor fuel type.

Figure 2-5 indicates the predicted heat load of MCOs from the K West basin assuming a decay date of November 30, 2000 (K West fuel removal startup date) and the canister loading strategy described above. The idealized loading scheme indicates that The MCOs produced from Mk 1A fuel are projected to range from approximately 200 to 400 W and will be the first MCOs loaded in the Canister Storage Building. Mk IV MCO heat loads can be expected to range from approximately 400 to 550 W. The plutonium inventory, uranium inventory, and heat load of the SPR MCO is bounded by the N Reactor fuel MCOs.

Figure 2-6 predicts the aluminum hydroxide inventory of MCOs from the K West basin assuming a nominal coating thickness of 1.1 mils is present, after cleaning, on all fuel assemblies stored in aluminum canisters (Jensen, 1998). The prediction indicates that Mk IV fuel is primarily stored within aluminum canisters, while Mk 1A fuel is primarily stored in stainless steel canisters.

Figure 2-3. Projected K West Basin MCO Plutonium Inventory

Figure 2-4. Projected K West Basin MCO Uranium Inventory

Figure 2-5. Projected K West Basin MCO Heat Load

Figure 2-6. Projected K West Basin MCO Aluminum Hydroxide Inventory

2.3.2 K East Basin MCOs

Figures 2-7 and 2-8 describe the plutonium and uranium inventory of MCOs from the K East basin assuming an idealized loading scheme that implements the above strategy. Overall, 202 MCOs containing Mk IV N Reactor fuel are projected to be loaded assuming an average of one scrap basket per MCO. This projection is consistent with prior nominal estimates for the number of MCOs produced at the K East basin (Pajunen, 1997). The actual scrap generation rate will impact the loadings actually observed in MCOs. The constraints on MCO Pu inventory were confirmed first for each campaign (Mk IV Pu blending, and Other Mk IV). The canister selection basis was then arranged to minimize the number of keys open at any given time. When no other constraint defined fuel selection, the early removal of fuel from areas near the fuel retrieval system was emphasized.

Figure 2-7 indicates that MCOs from other Mk IV fuel removal will result in the highest plutonium inventory. The other Mk IV MCOs contain more Pu than the blended MCOs because of the conservative algorithm used to define the number of high Pu assemblies in a fuel basket. All MCOs loaded are within the plutonium inventory constraint of 15,500 g Pu. Figure 2-8 indicates the anticipated uranium loading of MCOs, which is approximately constant at 6,000 kg U for all MCOs from K East basin. While not predicted by the idealized loading, a single partial MCO load is likely to be observed at the end of N Reactor fuel removal from K East basin.

Figure 2-9 indicates the predicted heat load of MCOs from the K East basin assuming a decay date of November 30, 2000 (K West fuel removal startup date) and the canister loading strategy described above. The idealized loading scheme indicates that MCO heat loads can be expected to range from 0 to 600 W.

Aluminum hydroxide coatings have not been observed on K East fuel, which is stored in open canisters. Therefore, there is no graph for aluminum hydroxide for K East corresponding to the one for K West.

Figure 2-7. Projected K East Basin MCO Plutonium Inventory

Figure 2-8. Projected K East Basin MCO Uranium Inventory

Figure 2-9. Projected K East Basin MCO Heat Load

3.0 Process Validation

A series of tests focused on confirming process performance predictions are described in Sexton, 2000. Some testing is done for fuel retrieval activities during the PSI. Testing that will be done for complete MCOs include:

- performing a detailed visual examination of fuel loaded in a particular MCO, which is used to develop estimates of reaction rate parameters,
- measuring the scrap generation ratio, which is used to update projections of the required number of MCOs and scrap baskets,
- measuring temperatures and radiation levels during basket loading to confirm design calculations predicting operator exposure,
- measuring gas temperature, pressure, and composition for comparison with design predictions of variations during cask transfers,
- performing detailed radiation surveys before and after cask transfers to the CVD to confirm estimates used to predict operator exposure,
- measuring radiation levels, in the vicinity of the cask and piping, before and after bulk water removal at the CVD to confirm operator exposure estimates,
- measuring the corrosion power of MCOs to confirm estimates of the expected reacting surface area contained in a MCO,
- measuring gas generation rates for comparison with thermal modeling predictions, and
- performing detailed radiation surveys before and after transfer to the CSB to confirm estimates used to predict operator exposure.

The number of MCOs used in each test is varied, depending on the potential for measurements to vary from MCO to MCO. Table 3-1 summarizes the MCOs used in each test. Final selection of the MCO involved in a particular test is, in some cases, limited to identifying that a number of MCOs must be selected during production from a specified group. For example, three MCOs would be used to assess scrap density (the MCOs must contain a scrap basket to support this measurement).

Table 3-1. Selection of Multi-Canister Overpacks for Process Validation Tests

MCOs	Process Validation Tests										MCO Monitoring in CSB (See Section 4.2)	
	Fuel Retrieval		Basket Loading and MCO Closure		Cask Transfer			Cold Vacuum Drying – Bulk Water Removal		Cold Vacuum Drying – Gas Generation Rate		Cask Transport to CSB – Radiation Levels
Visual Exam	Scrap Generation Ratio	Loading Temperature	Radiation Levels	Temperature and Pressure Rise	Gas Sample	Radiation Level	Radiation Level	Corrosion Power Test				
MCOs Removed from K West Basin												
Mk1A	(2)	(3)	(1)	(3)	(3)	(3)	(3)	(3)	(2)	(2)	(3)	(2)
Pu Blend	(1)								(1)	(1)		(1)
Other MkIV	(1)								(1)	(1)		(1)
SPR	(1)								(1)	(1)		(1)
MCOs Removed from K East Basin												
Pu Blend	(1)								(1)	(1)		(1)
Other MkIV	(1)								(1)	(1)		(1)
SPR	**								**	**		**

Notes: (#) — Process validation test is performed on the indicated number of MCOs selected from this group of MCOs.

** - SPR MCO transferred from K East Basin to K West Basin to complete loading. Visual examination of K East SPR fuel should be performed during loading at K East Basin.

4.0 Canister Storage Building

4.1 Startup MCO Positions

Evaluation of the CSB tube positions used for startup is not completely defined at this time. Initial recommendations, based on two-dimensional heat transfer models, indicate that startup loadings should be placed in tubes near the exhaust stack (Jones, et al., 1998). Three-dimensional modeling is proposed to provide a basis for specifying the actual tube pattern used during startup and determine the relationship of vault heat rejection to the tube loading pattern.

4.2 MCO Monitoring

The proposed MCO monitoring approach during dry storage at the CSB (Sexton, 1998) is based on evaluating 4 to 6 N Reactor fuel MCOs for up to two years. The concept described in the activity description intends to identify MCOs with the following target characteristics:

- (1) One MCO with minimal exposed fuel surface area and no aluminum hydroxide.
- (2) One MCO with minimal exposed fuel surface area, but high in aluminum hydroxide.
- (3) One MCO from KW high in exposed fuel surface area and scrap.
- (4) One MCO from KE high in exposed fuel surface area and scrap.

One or two additional MCOs could be included in the monitoring activity if there are loadings of special interest.

The fuel campaign descriptions in Section 2 provide additional bases for defining 6 N Reactor fuel MCOs for monitoring during dry storage. One MCO can be selected from each fuel grouping used to describe campaigns. This results in selecting a MCO for monitoring from:

- The K West basin Mk 1A fuel campaign (Two MCOs potentially satisfies (1) and (3) above)
- The K West basin plutonium blending Mk IV campaign
- The K West basin other Mk IV fuel campaign (potentially satisfies (2) above)
- The K East basin plutonium blending Mk IV campaign (potentially satisfies (4) above)
- The K East basin other Mk IV fuel campaign.

The MCO containing SPR fuel is also expected to require monitoring, for a total of up to seven MCOs in the monitoring program.

The actual MCOs used for monitoring will not be specified, beyond the above general guidance, prior to the start of operations. At that time, the MCOs monitored will be selected based on recommendations of process engineering personnel. Table 3-1 indicates the process validation tests that will be performed to support evaluation the MCOs monitored in the CSB.

5.0 Fuel Removal Closeout

Sludge retrieval from basin floors is planned after fuel removal from K West basin and during and after K East basin. Based on past experience, the potential exists for finding a small number of fuel elements, or pieces, during these basin cleanout activities. The capability to load, transfer, dry, and weld a MCO must be retained until activities that may discover additional fuel elements are complete. This may result in the production of a single MCO, containing a small quantity of fuel, after the majority of fuel removal activities are completed (see Figure 1-1).

6.0 References

- Bergmann, D. W., 1998, *K West Basin Color-coded Maps*, Interoffice Correspondence to J. R. Frederickson, 98-SNF/DWB-005, dated December 7, 1998.
- Jensen, L., 1998, *Statistical Analysis of Aluminum Trihydroxide Thickness Data*, HNF-3247, Rev 0, Lockheed Martin Hanford Corp, Richland, Washington.
- Jones, J. H., A. R. Walsh, and G.J. Banken, 1998, *Preliminary Thermal Analysis of MCO Loading during Canister Storage Building Startup, E014N-KBASIN.010, Rev 0*, EDT 625800, prepared for DE&S Hanford by Q-Metrics, Inc., Woodinville, Washington.
- Kessler, S. F., 2000, *Criticality Safety Evaluation Report for Storage and Removal of Spent Nuclear Fuel from K Basin*, HNF-SD-SNF-CSER-010, Rev. 1B, Fluor Hanford, Richland, WA
- Morris, K. R., 1998, *Special Nuclear Material Accountability Strategy for the Spent Nuclear Fuel Project*, HNF-2297, Rev 0, DE&S Hanford, Richland, Washington.
- Packer, M. J., 1998, *Radionuclide Content of K East Basin Keys Decayed to November 30, 2000*, EDT 625799, DE&S Hanford, Richland, Washington.
- Pajunen, A. L., 1997, *Estimated Fuel Inventory Loaded in Fuel and Scrap Baskets*, HNF-SD-SNF-CN-012, Rev 0, SGN Eurisys Services Corporation, Richland, Washington.
- Pajunen, A. L., 1998, *Radionuclide Content of K West Basin Keys Decayed to November 30, 2000*, EDT 625777, DE&S Hanford, Richland, Washington.
- Sexton, R. A., 1998, *MCO Monitoring Activity Description*, HNF-3312, Rev 1, DE&S Hanford, Richland, Washington.
- Sexton, R. A., 2000, *Spent Nuclear Fuel Process Validation Technical Support Plan*, SNF-4909, Rev. 1, Fluor Hanford, Richland, WA
- Shen, E. J., et al., 1999, *Fuel Retrieval System Process Validation Plan*, SNF-3896, Rev 0, DE&S Hanford, Richland, Washington.
- Welsh, T. L., and A. L. Pitner, *Statistical Analysis of the K West Fuel Element Visual Examination Results*, HNF-2314, Rev. 0, DE&SH Hanford, Richland, WA

Appendix A. K West Basin Fuel Canister Descriptions

Canister description data for the K West Basin were developed to support campaign planning from a combination of safeguards accountability records, calculations projecting radionuclide heat generation, and characterization data. Figures A-1 through A-5 summarize selected parameters describing the basin canisters by location maps in the basin fuel storage grid (Bergmann, 1998).

The complete information for each K West canister is summarized as follows:

- Canister location – based on storage rack cubicle grid numbers (based on location as of October 1998)
- Canister lid number
- Fuel key number
- Wt% ^{240}Pu - average ^{240}Pu content of plutonium in canister
- Fuel type – Mk IV, Mk 1A, or SPR
- Number of inner elements, outer elements, and total assemblies contained in the canister
- Mass of plutonium in canister
- Mass of uranium in canister
- Heat load of fuel in canister decayed to November 30, 2000 (K West Basin startup date)
- Wt% ^{235}U – average ^{235}U content of uranium in canister
- Fuel grade – grade assigned to fuel during segregation activities (not applicable to all canisters)
- Fuel model indication – indicates fuel element length
- Canister type – based on June 1998 video data (Mk I A1, Mk I SS, or Mk II)
- Indication of fuel damage based on 1995/1996 visual examinations (not applicable to all canisters)
- Observation notes from encapsulation activities (not applicable to all canisters)

Figure A-1 indicates the location of different fuel types in the KW Basin. Generally, Mk IV fuel is located near the west end of the basin (near the fuel retrieval system). However, some Mk IV canisters can be found in each bay.

Figure A-2 shows the plutonium content of canisters. This figure indicates the distribution of canisters containing plutonium that must be blended to control the plutonium inventory of K West basin MCOs. Figure A-3 shows the distribution of canister heat load. Generally, the high heat load canisters in K West also must be blended to control the MCO plutonium inventory. This has the effect of reducing the peak MCO heat load produced by fuel removal activities.

Figure A-4 indicates the position of K West basin canisters that have been evaluated as part of characterization activities. Since the canisters in K West basin canisters have lids, actual data observations of K West fuel originates from a limited number of canisters. Figure A-5 indicates the types of canisters in each location. Comparison of Figure A-5 with Figure A-1 indicates that

most aluminum canisters contain Mk IV fuel. Review of the data listing shows that 10 aluminum canisters contain Mk 1A fuel, with the remaining aluminum canisters containing Mk IV fuel.

Figure A-1. K West Basin Fuel Type Map

(2D) II Print II 02 Nov 1998 II kwcan3.plt II parameters of KW fuel/canisters

KW BASIN FUEL TYPE BY CANISTER

FUEL TYPE
 empty
 *** SPR
 *** MARK IV
 *** MARK I

Figure A-2. K West Basin Canister Plutonium Inventory Map

(2D) II Print II 02 Nov 1998 II kwcan5.plt II parameters of KW fuel/canisters

Figure A-3. K West Basin Canister Heat Generation Map

(2D) || Print || 02 Nov 1998 || kwcan5.plt || parameters of KW fuel/canisters

Figure A-4. Characterization Test Data Locations

(2D) II Print II 03 Dec 1998 II kwcan9.plt II parameters of KW fuel/canisters

KW BASIN: SHOWING CANISTERS WITH CHARACTERIZATION TESTS

Figure A-5. K West Basin Canister Type Map

(2D) || Print || 04 Nov 1998 || kwcan3.plt || parameters of KW fuel/canisters

KW BASIN CANISTER TYPE
BASED ON UNDERWATER VISUAL SURVEY
(SUMMER 1998)

CANISTER TYPE

*** MARKIAL
 *** MARKISS
 *** MARKIIS

Appendix B. K West Basin MCO Descriptions

The following tables summarize the characteristics of MCOs plotted in Figures 2-3 through 2-6. Detailed listings of the canisters loaded in each MCO to produce the characteristics listed in Table B-2 are shown in Table B-4 as fuel selection for plutonium blending is less flexible than the remainder of fuel processing.

The projected MCO characteristics are considered realistic approximations of actual MCO loading. However, it should be recognized that a great deal of fuel selection flexibility has been retained in the loading plan for most canisters. This flexibility is considered essential to allow operations to efficiently respond to canister condition uncertainties.

Table B-1. K West Basin Mk 1A MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
1	20	270	6857	4287	216.3	9964, 9993
2	19	265	6954	4229	222.9	9993
3	19	266	6509	4382	201.8	9993, 10201
4	19	264	6506	4406	201.3	10201
5	20	269	6126	4149	189.6	10201
6	20	268	6563	4115	210.3	10201, 10259
7	19	266	6916	4385	219.3	10259, 10294
8	19	266	6897	4385	218.3	10294
9	19	264	6845	4352	216.7	10294
10	19	266	6890	4381	218.1	10294
11	19	265	7138	4332	232.4	10294, 10350
12	19	266	7467	4383	247.8	10350
13	19	266	7439	4367	246.8	10350
14	19	266	6662	3912	221.1	10350
15	19	264	7090	4242	233.4	10350, 10385
16	19	266	7277	4371	239.3	10385
17	19	266	7926	4382	274.0	10385, 10456
18	19	266	7880	4338	273.1	10456
19	19	266	7922	4361	274.6	10456
20	19	266	7934	4383	274.7	10456, 10602
21	19	266	7712	4344	265.8	10602
22	19	266	7790	4388	268.5	10602
23	19	265	7781	4383	268.2	10602
24	19	266	7942	4265	284.0	10602, 10679
25	19	266	7915	4212	284.9	10679
26	19	266	8300	4359	301.2	10679, 10742
27	19	266	8600	4223	325.2	10742
28	20	267	8832	4278	337.8	10742, 10770
29	19	266	9103	4339	350.8	10770
30	19	266	8801	4250	337.5	10770, 10832
31	19	266	8935	4340	341.8	10832
32	19	266	8935	4340	341.8	10832
33	19	265	8852	4299	338.7	10832
34	19	261	9156	4237	362.9	10832, 10982
35	19	266	9557	4374	381.7	10982
36	19	266	9555	4372	381.6	10982
37	19	264	9485	4340	378.8	10982
38	19	266	9429	4344	376.0	10982, 11036
39	19	266	9487	4374	378.4	11036, 11109
40	19	264	9479	4346	380.4	11109
41	19	266	9538	4374	382.9	11109
42	19	266	9538	4374	382.9	11109
43	20	270	9123	4255	362.0	11109, 11183
44	19	266	9249	4355	364.7	11183
45	19	265	8754	4090	348.0	11183, 11372
46	19	266	8932	4065	364.2	11372
47	19	266	9567	4353	390.1	11372
48	19	266	9614	4374	392.0	11372
49	19	266	9614	4374	392.0	11372
50	19	266	9400	4335	380.5	11372, 11449
51	19	266	9405	4384	378.7	11449

Table B-1. K West Basin Mk 1A MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
52	19	266	9405	4384	378.7	11449
53	19	266	9405	4384	378.7	11449
54	19	266	9219	4297	371.1	11449
55	19	266	9291	4384	372.4	11540
56	19	266	9291	4384	372.4	11540
57	19	266	9357	4384	377.6	11540, 11806
58	19	266	9709	4383	405.5	11806
59	19	266	9701	4380	405.2	11806
60	19	266	9709	4383	405.5	11806
61	19	264	9631	4348	402.2	11806
62	20	270	9291	4113	395.0	11806, 11897
63	19	266	10037	4367	432.2	11897
64	19	266	9927	4319	427.4	11897
65	19	265	10032	4365	432.0	11897
66	19	265	9123	3969	392.8	11897
67	19	265	9018	3952	386.9	11897, 11979
68	19	266	9810	4301	420.6	11979
69	19	266	9860	4323	422.8	11979
70	19	266	9694	4249	415.6	11979
71	19	266	9688	4247	415.4	11979
72	19	265	8923	3913	382.7	11979
73	19	266	9181	4037	395.8	11979, 12127
74	19	266	9517	4186	410.7	12127
75	19	265	9602	4224	414.4	12127
76	19	259	9422	4160	405.7	12127, 12201
77	19	266	9310	4383	383.8	12201
78	19	266	8881	4181	366.1	12201
79	19	266	9310	4383	383.8	12201
80	19	266	9310	4383	383.8	12201
81	19	266	9310	4383	383.8	12201
82	19	266	9085	4285	371.8	12201, 12285
83	19	266	9272	4394	371.8	12285
84	19	266	9272	4394	371.8	12285
85	19	266	9272	4394	371.8	12285
86	19	265	9237	4378	370.4	12285
87	19	265	9368	4286	395.8	12285, 12480
88	19	266	9709	4392	416.7	12480
89	19	266	9709	4392	416.7	12480
90	19	266	9709	4392	416.7	12480
91	19	265	9678	4387	415.4	12480, 12565
92	19	266	9652	4393	414.2	12565
93	19	266	9652	4393	414.2	12565
94	19	266	9652	4393	414.2	12565
95	19	266	9652	4393	414.2	12565
96	19	266	9652	4393	414.2	12565
97	19	265	9387	4388	396.6	12565, 12639
98	19	266	9215	4394	384.8	12639
99	19	266	9215	4394	384.8	12639
100	19	264	9181	4378	383.3	12639
101	19	266	9215	4394	384.8	12639
102	19	266	9239	4396	386.8	12639, 12823
103	19	266	9277	4377	392.3	12823
104	19	266	9188	4362	388.2	12823, 12852
105	19	266	9086	4346	383.1	12852

Table B-1. K West Basin Mk 1A MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
106	19	266	8957	4284	377.7	12852
107	19	266	9206	4401	389.0	12852, 12942
108	19	266	9033	4307	383.4	12942
109	19	266	8905	4246	378.0	12942
110	19	266	8832	4211	374.8	12942
111	19	266	9234	4402	391.8	12942
112	19	266	9087	4281	385.0	12942, 13016
113	19	266	9299	4333	393.5	13016
114	19	266	9310	4338	393.9	13016
115	19	258	9096	4247	384.7	13016
116	19	266	9270	4320	392.2	13016
117	19	266	9060	4310	388.6	13016, 13371
118	19	265	9345	4368	410.5	13371, 13525
119	19	266	8705	3997	387.3	13525
120	19	266	9356	4296	416.4	13525
121	19	266	9576	4398	426.2	13525
122	19	266	9293	4279	413.6	13525, 13650
123	19	266	9056	4184	403.1	13650
124	19	266	9141	4223	406.8	13650
125	19	266	8979	4147	399.5	13650
126	19	266	9003	4331	393.0	13650, 13686
127	19	266	8797	4392	376.8	13686
128	19	266	8797	4392	376.8	13686
129	20	271	8962	4475	383.9	13686
130	20	268	8785	4404	377.2	13686, 13859
131	19	266	8557	4311	368.6	13859
132	19	266	8685	4375	374.1	13859
133	19	266	8721	4392	375.6	13859
134	19	266	8686	4376	374.2	13859
135	19	266	8657	4360	372.9	13859
136	19	266	8592	4327	370.0	13859
137	29	266	5020	4340	207.7	13859, 15244, 15347, 15445, 15448, 15451, 15457
138	20	269	2638	4389	104.6	15459
139	19	266	2615	4349	103.7	15459
140	19	266	2616	4351	103.7	15459
141	19	266	2604	4331	103.2	15459
142	19	266	2637	4386	104.5	15459
143	19	266	2641	4392	104.7	15459
144	19	266	2573	4277	102.0	15459
145	19	266	2535	4378	100.3	15459, 15460
146	6	71	591	1184	23.2	15460, 15555
Mk 1A Total	2780	38620	1235168	627201	49946.1	

Table B-2. K West Basin Plutonium Blending MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
1B	18	250	12971	5649	544.8	22852, 13017
2B	18	252	13229	5767	554.9	22852, 13017, 22565
3B	18	252	13356	5857	558.9	22565, 13017
4B	18	250	13235	5831	550.1	22565, 13017, 21540
5B	18	252	13099	5848	530.6	21540, 13017
6B	18	252	13116	5852	531.2	21540, 13017
7B	18	252	12894	5730	522.6	21540, 13017
8B	19	252	12342	5842	494.9	21540, 13017
9B	19	253	10385	5696	416.1	13017, 15244, 12852
High Pu Blend MCO Total	164	2264	114627	52073	4704.0	

See Table B-4 for detailed canister listing loaded in each MCO to produce MCOs with the characteristics listed above.

Table B-3. K West Basin Other Mk IV MCO Descriptions						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
1	18	252	9811	5441	403.2	13858
2	18	252	10690	5738	436.5	13858
3	18	252	10618	5761	433.4	13858
4	18	252	10608	5881	436.0	13858, 10001
5	18	252	10466	5866	431.1	13858, 10001
6	18	252	10494	5882	432.3	13858, 19623
7	18	252	10494	5882	432.3	13858, 10001
8	18	252	9985	5595	411.2	13858, 10001
9	18	252	9742	5458	401.2	13858, 19623, 14065, 14055, 10001
10	18	251	10270	5755	423.0	12852
11	19	260	10282	5676	422.1	12852
12	18	252	11163	5872	454.0	12852
13	18	252	11069	5822	450.1	12852
14	19	266	11727	6171	476.7	12852
15	19	266	11750	6181	477.8	12852
16	19	266	11757	6185	478.1	12852
17	19	266	11744	6178	477.6	12852
18	19	266	11799	6206	479.8	12852
19	18	251	11686	5861	488.7	12852
20	18	252	11718	5877	488.7	12852
21	18	252	11670	5854	486.7	12942
22	18	252	11718	5877	488.7	12942
23	18	252	11718	5877	488.7	12942
24	18	252	11718	5877	488.7	12942
25	18	252	11718	5877	488.7	12942
26	18	252	11718	5877	488.7	12942
27	18	252	11718	5877	488.7	12942
28	18	252	11718	5877	488.7	12942
29	18	248	11686	5861	487.4	12942
30	18	252	11624	5865	477.5	12942, 13015
31	18	251	10740	5420	441.3	13015
32	18	252	11176	5639	459.1	13015
33	18	252	11011	5587	454.8	13015
34	18	252	9487	4789	389.9	13015
35	18	249	10837	5470	445.3	13015
36	18	252	11458	5782	470.7	13015
37	18	252	11622	5877	477.9	13015
38	18	252	9717	5024	407.5	13372
39	18	252	10489	5426	440.1	13372
40	18	248	10776	5574	452.1	13372
41	18	243	10047	5171	423.7	13372, 13524
42	18	252	10034	5136	425.7	13524
43	18	252	10729	5493	455.3	13524
44	18	252	11162	5712	473.4	13524
45	18	252	11229	5746	476.3	13524
46	18	252	10991	5626	466.2	13524
47	18	252	11082	5672	470.1	13524
48	26	192	6334	4043	230.7	13524, 10764, 9964
Total	878	12091	523800	273200	21666.1	

Table B-4. K West Basin Plutonium Blending Canister Loading Details

[illegible]

Table B-4. K West Basin Plutonium Blending Canister Loading Details

[illegible]

Table B-4. K West Basin Plutonium Blending Canister Loading Details

[illegible]

[illegible]

Table B-4. K West Basin Plutonium Blending Canister Loading Details								
MCO Number	Basin Storage Cubicle Number	Canister Lid Number	Fuel Key Number	Wt% ²⁴⁰ Pu	Assembly Total	Canister Plutonium Inventory, g Pu	Canister Uranium Inventory, Kg U	Canister Heat Load, W
9B	2228	1616	13017	11.39	14	549	327	21.1
	2227	1575	13017	11.39	14	549	327	21.1
	1609	1681	13017	11.39	14	549	327	21.1
	1608	1677	13017	11.39	14	390	232	15.0
	1607	1676	13017	11.39	14	533	317	20.5
	1606	1623	13017	11.39	14	549	327	21.1
	1605	1617	13017	11.39	14	533	317	20.5
	1604	1619	13017	11.39	14	549	327	21.1
	113	1620	13017	11.39	14	417	248	16.0
	112	1568	13017	11.39	14	545	324	20.9
	2073	8153	15244	13.58	0.5	14	7	0.7
	6271	1865	12852	13.43	14	651	327	27.2
	6270	1886	12852	13.43	14	651	327	27.2
	6269	953	12852	13.43	14	651	327	27.2
	6268	950	12852	13.43	14	651	327	27.2
	6267	1741	12852	13.43	14	651	327	27.2
	6266	1745	12852	13.43	14	651	327	27.2
	6265	1856	12852	13.43	14	651	327	27.2
	6264	1889	12852	13.43	14	651	327	27.2
9B	Cans =	19			253	10385	5696	416.1

Appendix C. K East Basin MCO Descriptions

The following tables summarize the characteristics of MCOs plotted in Figures 2-7 through 2-9.

The projected MCO characteristics are considered realistic approximations of actual MCO loading. However, it should be recognized that a great deal of fuel selection flexibility has been retained in the loading plan for most canisters. This flexibility is considered essential to allow operations to efficiently respond to canister condition uncertainties.

Table C-1. K East Basin Plutonium Blending MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
1	18	250	10636	5424.9	404.08	10742, 15204
2	18	252	11307	5641.39	432.37	10742, 15204
3	18	252	11615	5817.11	445.22	10742, 15204
4	18	252	10704	5482.29	405.65	10742, 15204
5	18	250	10964	5587.03	417.41	10742, 15204
6	18	250	11851	5825.31	478.99	10742, 10982, 15204
7	18	252	11541	5677.25	466.81	10982, 15204
8	18	250	11379	5643.61	456.82	10982, 15204
9	18	250	11716	5775.93	474.39	10982, 15204
10	18	252	11418	5696.72	458.13	10982, 15204
11	18	252	11369	5673.58	456.3	10982, 15204
12	18	248	10615	5457.13	416.17	10982, 11036, 15204
13	18	250	11342	5741.62	445.36	11036, 15204
14	18	252	11481	5709.43	451.15	11036, 15204
15	18	252	11452	5752.35	454.15	11036, 11109, 15204
16	18	252	11756	5859.86	470.54	11109, 15204
17	18	250	11432	5741.17	456.56	11109, 15204
18	18	252	11586	5801.63	462.78	11109, 15204
19	18	244	11001	5566.81	438.85	11109, 15204
20	18	252	11288	5682.35	449.61	11109, 15204
21	18	250	11174	5485.38	443.69	11109, 11183, 15204
22	18	252	11510	5680.07	455.95	11183, 15204
23	19	253.5	11649	5711.93	461.74	11183, 15204
24	18	251	11615	5730.88	460.35	11183, 15204
25	18	252	11627	5738.03	461	11183, 15204
26	18	251.5	11742	5844.31	465.45	11183, 15204
27	18	252	11715	5799.09	464.41	11183, 15204
28	18	252	11515	5722.59	456.47	11183, 15204
29	18	252	11698	5827.58	463.73	11183, 15204
30	18	248	11691	5768.93	463.44	11183, 15204
31	18	252	11475	5661.67	454.3	11183, 15204
32	18	251.5	11549	5714.07	457.5	11183, 15204
33	19	250.5	11542	5789.89	459.12	11183, 11372, 15204
34	18	252	11512	5841.53	460.64	11372, 15204
35	18	249.5	11271	5727.6	450.89	11372, 15204
36	18	247.5	10935	5426.03	439.74	11372, 15204
37	19	253	11948	5781.97	482.48	11372, 15204
38	18	251	11277	5728.66	452.31	11372, 15204
39	18	252	11526	5845.14	461.16	11372, 15204

Table C-1. K East Basin Plutonium Blending MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
40	18	252	11194	5701.79	448.03	11372,15204
41	18	252	11293	5710.76	452.44	11372,11449, 15204
42	18	252	11461	5762.02	462.23	11449,15204
43	18	252	11380	5797.37	456.67	11449,15204
44	18	252	11300	5739.42	454.03	11449,15204
45	18	250	11136	5710.05	443.56	11449,15204
46	18	252	10932	5638.04	431.13	11449,15204
47	18	252	11315	5796.98	452.31	11449,15204
48	18	252	10962	5371.61	454.12	11449,11897, 15204
49	18	252	12155	5760.14	510.16	11897,15204
50	18	252	11751	5666.7	492.75	11897,15204
51	18	242	10949	5205.81	455.35	11897,15204
52	18	252	10719	5361.67	441.6	11897,15204
53	18	252	11572	5530.96	484.37	11897,15204
54	18	252	10699	5351.21	441.34	11897,15204
55	18	251.5	11397	5497.55	476.13	11897,15204
56	18	252	12134	5575.23	513.36	11897,15204
57	18	252	11956	5726.17	511.86	11897,11979, 15204
58	18	252	11565	5441.25	497.53	11979,15204
59	18	252	11913	5692.32	512.9	11979,15204
60	18	252	11690	5613.94	501.87	11979,15204
61	18	252	11241	5496.33	478.88	11979,15204
62	18	245.5	11439	5462.51	482.76	11979,15204, 15240, 15316
63	18	251.5	11219	5431.5	479.23	11979, 15316
64	18	252	11588	5587.5	497.15	11979, 15316
65	18	252	11358	5461.81	490.06	11979, 15316
66	18	252	11900	5705.88	504.05	11979, 12127, 15316
67	18	252	11826	5728.72	493.25	12127, 15316
68	18	247.5	11544	5494.18	481.49	12127, 15316
69	18	252	11918	5819.64	497.03	12127, 15316
70	18	252	11849	5721.93	494.37	12127, 15316
71	18	252	11585	5638.44	483.03	12127, 15316
72	18	252	11528	5585.29	480.73	12127, 15316
73	18	252	11658	5695.62	486.18	12127, 12285, 15316
74	18	252	11522	5657.69	479.72	12285, 15316
75	18	252	11582	5717.6	482.29	12285,15316, 15399, 15444
76	19	254	11833	5831.91	494.28	12285, 15451
77	18	244.5	11647	5555.62	482.94	12285, 15451
78	18	251.5	11778	5714.08	488.49	12285, 15451
79	18	252	11741	5685.14	487.06	12285, 15451

Table C-1. K East Basin Plutonium Blending MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
80	18	252	11743	5674.17	485.76	12285, 15451
81	19	253	12196	5724.7	506.14	12285, 15451, 15455
82	18	252	11350	5663.38	473.65	12285, 15455, 15457
83	19	251	11165	5544.75	466.79	12285, 15457, 15458
84	18	252	11095	5759.14	466.58	12285, 15458
85	18	252	11152	5813.65	469.5	12285, 15458
86	18	252	10774	5658.6	452.6	12285, 15458
87	18	252	11134	5771.53	468.54	12285, 15458
88	18	252	11163	5757.96	469.4	12285, 15458
89	18	252	11064	5785.65	463.68	12285, 12480, 15458
90	18	252	11016	5724.24	462.42	12480, 15458
91	18	252	11123	5766.72	465.87	12480, 15458
92	18	252	10911	5685.97	457.28	12480, 15458
93	18	252	11164	5856.21	467.91	12480, 15458
94	18	252	11149	5865.42	467.38	12480, 15458
95	18	252	11147	5836.22	467.09	12480, 15458
96	18	252	10788	5662.7	455.18	12480, 15458
97	18	252	11139	5814.24	466.66	12480, 15458
98	18	252	11142	5800.37	466.72	12480, 15458
99	18	252	11023	5754.23	462.03	12480, 15458
100	18	252	11001	5758.27	461.08	12480, 15458
101	18	252	8570	5712.28	362.59	12480, 15458
High Pu Blend MCO Total	1824	25381	1148662	573415.56	46997.28	

Table C-2. K East Basin Other Mk IV MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
1	18	252	13952	5858	583.8	12565
2	18	252	13612	5714	569.5	12565
3	18	250	13693	5764	573.0	12565
4	18	252	13800	5793	577.3	12565
5	18	252	13970	5866	584.7	12565
6	18	252	13986	5873	585.4	12565
7	18	252	11003	5844	457.5	12565, 15204
8	21	251.5	9186	5404.95	270.5	10001, 10201, 10259
9	18	252	10408	5756.85	312.12	10259
10	18	248	9783	5412.61	293.46	10259
11	18	252	9537	5278.53	286.19	10259
12	18	252	10470	5804.33	316.05	10259, 10294
13	18	250	10299	5713.62	311.51	10294
14	18	249.5	10153	5632	307.04	10294
15	18	250	10366	5755.49	313.5	10294
16	18	248	10296	5716.71	311.38	10294
17	18	248	10235	5674.98	309.35	10294
18	18	246	10112	5637.19	305.44	10294, 10350, 10385
19	18	250	11159	5743.49	352.28	10385
20	18	249.5	11225	5771.32	354.77	10385
21	18	249	11311	5810.95	357.67	10385
22	18	250	11357	5834.28	359.1	10385
23	18	248	11257	5782.92	355.9	10385
24	18	252	11448	5880.96	361.98	10385
25	18	250	11179	5833.72	360.64	10385, 10456
26	18	246	10787	5638	348.72	10456
27	18	245	10731	5608.2	346.87	10456
28	18	248	10343	5404.8	334.27	10456
29	18	249.5	10455	5468.57	337.37	10456, 10576
30	20	251	12316	5845.05	428.58	10576, 10602
31	18	245.5	13085	5658.16	485.52	10602
32	18	250	13500	5828.22	500.53	10602
33	18	248	13332	5755.22	494.25	10602
34	18	244.5	12918	5605.09	480.21	10602
35	19	255	13681	5851.55	518.27	10602, 10679
36	18	244	12070	5276.51	451.7	10679
37	19	251.5	13052	5570.34	496.39	10679
38	18	242	13292	5640.35	507.53	10679
39	19	246	10536	5533.33	400.72	10679, 10764
40	21	254	11223	5793.41	426.98	10764, 10770
41	18	252	13286	5735.3	505.36	10770
42	18	248	12974	5596.76	493.42	10770
43	18	250	12771	5579.57	478.07	10770, 10832

Table C-2. K East Basin Other Mk IV MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
44	18	252	13536	5874.84	504.54	10832
45	18	250	13393	5812.5	499.19	10832
46	18	250	13325	5782.61	496.61	10832
47	18	250	13073	5673.24	487.22	10832
48	18	252	13088	5678.78	487.69	10832
49	18	250	12850	5575.33	478.81	10832
50	18	250	12701	5510.01	473.21	10832
51	18	250	12713	5517.28	473.82	10832
52	18	246	12628	5626.06	464.8	10832, 11540
53	20	254	11444	5878.56	390.06	11540
54	19	251.5	11380	5853.6	387.7	11540
55	18	252	13075	5766.92	514.53	11540, 11733, 11806
56	18	252	13615	5765.21	557.11	11806
57	18	252	13709	5844.63	555.02	11806
58	18	252	13799	5857.86	562.24	11806
59	18	252	13841	5872.16	564.58	11806
60	18	252	13105	5654.94	534.57	11806, 12201
61	18	252	13258	5706.27	541.58	12201
62	18	252	13345	5698.63	546.18	12201
63	21	254	13634	5828.25	558.3	12201, 12240, 12639
64	18	252	13561	5777.06	555.43	12639
65	18	252	13776	5870.25	564.42	12639
66	18	252	13744	5856.12	563.06	12639
67	18	252	13597	5794.02	557.05	12639
68	18	251.5	13739	5854.32	562.87	12639
69	18	252	13685	5830.72	560.6	12639
70	18	252	13583	5786.96	556.36	12639
71	18	247.5	12840	5774.11	518.15	12639, 12852
72	18	252	10602	5469.54	485	12852, 13015, 13649
73	19	243.5	11187	5664.96	521.52	13649, 13685, 14065, 14355
74	18	252	11727	5862	506.29	14355
75	23	245	9020	5018.25	419.71	14355, 14356
76	20	250	8191	5203.33	400.05	14356
77	22	250	8203	5219.66	400.83	14356
78	18	244.5	3347	5497.79	152.63	14356, 14722, 15458
79	18	252	3012	5468.29	136.9	15458
80	18	247	3066	5617.34	140.59	15458
81	18	252	3045	5525.78	138.33	15458
82	18	252	3131	5679.81	142.18	15458
83	18	252	3074	5582.43	139.73	15458
84	18	252	3102	5632.13	140.99	15458
85	18	252	3152	5724.61	143.31	15458

Table C-2. K East Basin Other Mk IV MCO Description						
MCO Number	Canister Total	Assembly Total	MCO Plutonium Inventory, g Pu	MCO Uranium Inventory, kg U	MCO Heat Load, W	Key(s)
86	18	252	3061	5559.57	139.15	15458
87	18	252	3128	5684.24	142.27	15458
88	18	252	3109	5645.1	141.32	15458
89	18	252	3040	5523.38	138.24	15458
90	18	252	3036	5510.13	137.94	15458
91	18	252	3088	5611.1	140.46	15458
92	18	252	2989	5430.68	135.96	15458
93	18	252	3049	5533.9	138.54	15458
94	18	252	3072	5577.91	139.63	15458
95	18	252	3096	5621.11	140.72	15458
96	18	252.5	3188	5504.74	135.8	15458, 15460
97	18	244	3056	5164.17	122.3	15460
98	18	252	3222	5303.37	127.81	15460
99	18	252	2927	5399.4	118.1	15460, 15461
100	18	250	1143	5849.1	53.58	15461
101	19	266	1216	6223.45	57	15461
Other Mk IV Total	1848	25296.5	1003465	572174.88	38197.33	

DISTRIBUTION SHEET

To	From	Page 1 of 1
Distribution	Process Engineering	Date
Project Title/Work Order		EDT No. 629049
Spent Nuclear Fuel Removal Campaign Plan		ECN No. N/A

Name	MSIN	Text With All Attach.	Text Only	Attach./ Appendix Only	EDT/ECN Only
------	------	-----------------------------	--------------	------------------------------	-----------------

Spent Nuclear Fuel Project

J. R. Frederickson	R3-86	X		
L. H. Goldmann	R3-86	X		
J. R. Gregory	X3-78	X		
J. J. Irwin	R3-86	X		
M. J. Langevin	X4-01	X		
J. D. Mathews	X3-65	X		
W. C. Miller	R3-11	X		
C. R. Miska	R3-86	X		
F. W. Moore	R3-86	X		
K. R. Morris	X3-74	X		
J. W. Neskas	R3-86	X		
A. L. Pajunen	R3-86	X		
O. M. Serrano	S2-44	X		
R. A. Sexton	R3-86	X		
K. E. Smith	L6-58	X		
G. E. Stegen	X4-01	X		
J. A. Swenson	R3-11	X		
J. E. Truax	X3-71	X		
J. H. Wicks	X3-71	X		
SNF Project Files	R3-11	X		
SNF Project Procedures	X3-86			X
SNF Project Training	S2-45			X