ANNOUNCEMENT

PART I: STI PRODUCT DESCRIPTION (To be completed by Recipient/Contractor)

A. STI Product Identifiers

1. REPORT/PRODUCT NUMBER(s)

None

2. DOE AWARD/CONTRACT NUMBER(s)

DE FC36-98GO10291

3. OTHER IDENTIFYING NUMBER(s)

Energetics 3347

B. Recipient/Contractor

Energetics, Incorporated, Washington DC

C. STI Product Title

Technical Assessments, Analyses and Technology
Characterizations of Hydrogen Energy Technologies

D. Author(s)

Skolnik, Edward G., Energetics, Inc.

E-mail Address(es):

eskolnik@energeticsinc.com

E. STI Product Issue Date/Date of Publication

07/31/2000

(mm/dd/yyyy)

F. STI Product Type (Select only one)

☒ 1. TECHNICAL REPORT

☒ Final ☐ Other (specify) _____

☐ 2. CONFERENCE PAPER/PROCEEDINGS

Conference Information (title, location, dates)

☐ 3. JOURNAL ARTICLE

a. TYPE: ☐ Announcement Citation Only

☐ Preprint ☐ Postprint

b. JOURNAL NAME

c. VOLUME _____ d. ISSUE _____

e. SERIAL IDENTIFIER (e.g. ISSN or CODEN)

☐ OTHER, SPECIFY

G. STI Product Reporting Period (mm/dd/yyyy)

05/01/1998

Thru

07/01/2000

H. Sponsoring DOE Program Office

EERE/Golden Field Office

I. Subject Categories (list primary one first)

Hydrogen

Keywords **Hydrogen** Evaluations Analyses

J. Description/Abstract

See attached

K. Intellectual Property/Distribution Limitations

(must select at least one; if uncertain contact your
Contracting Officer (CO))

☒ 1. UNLIMITED ANNOUNCEMENT (available to
U.S. and non-U.S. public; the Government
assumes no liability for disclosure of such data)

☐ 2. COPYRIGHTED MATERIAL: Are there any
restrictions based on copyright? ☐ Yes ☐ No
If yes, list the restrictions as retained in your contract

☐ 3. PATENTABLE MATERIAL: THERE IS
PATENTABLE MATERIAL IN THE DOCUMENT
INVENTION DISCLOSURE SUBMITTED TO DOE:
DOE Docket Number: S-
(Sections are marked as restricted distribution
pursuant to 35 USC 205)

☐ 4. PROTECTED DATA: ☐ CRADA ☐ Other
If other, specify

Release date (mm/dd/yyyy)

☐ 5. SMALL BUSINESS INNOVATION RESEARCH
(SBIR) DATA

Release date (Required,

No more than 4 years from date listed in part 1.E above)

☐ 6. SMALL BUSINESS TRANSFER (STTR) DATA
Release date (Required,

No more than 4 years from date listed in part 1.E above)

☐ 7. OFFICE OF NUCLEAR ENERGY APPLIED
TECHNOLOGY

L. Recipient/Contractor Point of Contact Contact

for additional information (contact or organization name to be
included in published citations and who would receive any
external questions about the content of the STI Product or the
research contained therein)

Name and/or Position

Edward G. Skolnik, Program Manager/Senior Scientist

E-mail eskolnik@energeticsinc.com

Phone 202 406-4125

Organization Energetics, Inc.

UNITED STATES DEPARTMENT OF ENERGY (DOE)
Scientific and Technical Information (STI) For Financial
Assistance Recipients and Non-M&O/M&I Contractors

ANNOUNCEMENT

PART II: STI PRODUCT MEDIA/FORMAT and LOCATION/TRANSMISSION

(To be completed by Recipient/Contractor)

A. Media/Format Information:

1. MEDIUM OF STI PRODUCT IS:
☒ Electronic Document ☐ Computer medium
☐ Audiovisual material ☒ Paper ☐ No full-text
2. SIZE OF STI PRODUCT 167 Pages
3. SPECIFY FILE FORMAT OF ELECTRONIC
DOCUMENT BEING TRANSMITTED, INDICATE:
☐ SGML ☐ HTML ☐ XML ☒ PDF Normal ☐ PDF Image
☐ WP-Indicate Version (5.0 or greater) _____
Platform/operating system _____
- ☐ MS-Indicate Version (5.0 or greater) _____
Platform/operating system _____
- ☐ Postscript _____
4. IF COMPUTER MEDIUM OR AUDIOVISUAL
 - a. Quantity/type (specify) _____
 - b. Machine compatibility (specify) _____
 - c. Other information about product format a user
needs to know: _____

B. Transmission Information:

STI PRODUCT IS BEING TRANSMITTED:

- ☐ 1. Electronic via Elink
- ☒ 2. Via mail or shipment to address indicated
in award document (*Paper products,
CD-ROM, diskettes, videocassettes, et.*)
- _____
- ☐ 2a. Information product file name
(of transmitted electronic format)
- _____

PART III: STI PRODUCT REVIEW/RELEASE INFORMATION

(To be completed by DOE)

A. STI Product Reporting Requirement Review:

- ☐ 1. THIS DELIVERABLE COMPLETES ALL
REQUIRED DELIVERABLES FOR THIS AWARD
- ☐ 2. THIS DELIVERABLE FULFILLS A
TECHNICAL REPORTING REQUIREMENT,
BUT SHOULD NOT BE DISSEMINATED
BEYOND DOE.

B. DOE Releasing Official

- ☐ 1. I VERIFY THAT ALL NECESSARY
REVIEWS HAVE BEEN COMPLETED AS
DESCRIBED IN DOE G 241.1-1A, PART II,
SECTION 3.0 AND THAT THE STI
PRODUCT SHOULD BE RELEASED IN
ACCORDANCE WITH THE INTELLECTUAL
PROPERTY/DISTRIBUTION LIMITATION
ABOVE.

Released by (name) _____

Date _____
(mm/dd/yyyy)

E-mail _____

Phone _____

Abstract:

This report includes thirteen site-visit-based analyses or assessments of hydrogen R&D projects as well as four analyses of hydrogen process scenarios. The latter include the use of hydrogen/bromine electricity storage, hydrogen as a bus fuel, low-rank coal as thermal source to regenerate hydrides, and sodium hydride on-board storage.

Final Report

**Technical Assessments, Analyses and Technology Characterizations
of Hydrogen Energy Technologies**

Submitted to

**The U.S. Department of Energy – Golden Field Office
In Partial Fulfillment of
Cooperative Agreement No. DE-FC36-98GO10291**

Submitted By

Energetics, Incorporated

July 2000

**Technical Assessments, Analyses and Technology Characterizations of
Hydrogen Energy Technologies
Final Report**

Submitted to

**The U.S. Department of Energy – Golden Field Office
In Partial Fulfillment of
Cooperative Agreement No. DE-FC36-98GO10291**

During the period of this Cooperative Agreement, Energetics completed a total of thirteen on-site analyses of Hydrogen Program R&D projects as well as a series of detailed engineering/economic analyses and technology characterizations of transportation and remote power-based hydrogen technologies.

The Cooperative Agreement was originally supposed to include some additional analyses as well as a series of seminars, but was never funded to the initially intended level, and was also cut short of its initial 3-year duration.

The identity of the projects and the locations of the thirteen on-site analyses are shown in Table 1. A report on each of the projects visited is included in this Final Report.

A listing of the detailed analyses also undertaken as part of this Cooperative Agreement are shown in Table 2. All of the reports containing the detailed analyses are also included in this Final Report.

Table 1. Identity of Thirteen Site-visit Analyses Undertaken as Part of this Cooperative Agreement

Project	Performing Laboratory	Date of Visit
Storage and Purification of Hydrogen Using Ni-coated Mg	Arthur D. Little, Inc.	June 1998
Hydrogen Transmission and Storage with a Metal Hydride Organic Slurry	Thermo Power, Inc.	June 1998
Thermal Management Technology for Hydrogen Storage	Oak Ridge National Laboratory & Materials and Environmental Research, Inc.	August 1998
Improved Metal Hydride Technology	Energy Conversion Devices, Inc.	August 1998
Hydride Development for Hydrogen Storage	Sandia National Laboratories (CA)	September 1998
Biomass to Hydrogen via Fast Pyrolysis and Catalytic Steam Reforming	National Renewable Energy Laboratory	December 1998
Hydrogen Separation Membrane Development	Savannah River Technology Center	March 1999
Hydrogen Production by Photosynthetic Water Splitting	Oak Ridge National Laboratory	March 1999
Bioreactor Project	University of Hawaii	July 1999
Insulated Pressure Vessels for Cryogenic Hydrogen Storage	Lawrence Livermore National Laboratory	September 1999
PEM Fuel Cell Stacks for Power Generation	Los Alamos National Laboratory	January 2000
Hydrogen from Biomass in Supercritical Water	University of Hawaii	March 2000
Hydrogen Storage Tank Liners	Lawrence Livermore National Laboratory	March 2000

Table 2. List of Detailed Analyses.

Hydrogen Bromine-based Electricity Storage
Hydrogen-fueled Buses
Feasibility of Using Low-rank Western Coal as a Carbon Source for Hydride Regeneration
Analysis of the Sodium Hydride-based Hydrogen Storage System being developed by PowerBall Technologies, LLC

Site-Visit Analyses

Technical Evaluation Report

Project: High Efficiency Stationary Hydrogen Storage

Company: Arthur D. Little, Inc. (ADL), Cambridge, MA

P.I.: Dr. Scott Hynek

Date of Visit: June 8, 1998

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The work being carried out at Arthur D. Little (ADL) was originally based on the development of tailored phase change material (PCM) systems. There were touted for use as temperature controllers for the hydriding and dehydriding of magnesium for stationary hydrogen storage. It then evolved to the investigation of nickel coatings to enhance the hydriding kinetics, and then evolved further to the study of thin coatings that could be selectively penetrated by hydrogen. The application for this work has now become support of on-board hydrocarbon reforming. It appears that the driver behind this progression is ADL's thrust in on-board reforming. Apparently, ADL wants this research to support that thrust.

The PCM project seems to have more-or-less become a coatings study on its own. It appears, however, that the attempt to use magnesium nitride coatings (Mg_3N_2) as the hydrogen "filter" has not been successful, and that, if research continues, it will involve looking for a new coating candidate. Thus the direction of the research is going toward on-board reforming of liquid fuels, not toward the storage of hydrogen.

II Introduction and Background:

I met with **Dr. Scott Hynek** of ADL at their facility in Cambridge, MA. The purpose of the meeting was to learn about the hydrogen storage activities that are currently taking place at ADL and to determine how these activities were progressing. Emphasis was placed on determining how they had evolved from ADL's work of the past few years. I had previously sent Dr. Hynek a list of questions that I wished to discuss as part of our meeting, and asked for a demonstration as well.

Dr. Hynek's current project involves the identification/development of surface coatings for magnesium that will selectively admit hydrogen from a mixture of hydrocarbon reformer product. Thus, the coated magnesium serves as both a purifier and storage (as hydride) medium for hydrogen. Dr. Hynek suggested that the system was being developed to enable on-board reforming. Recall that, earlier, Dr. Hynek had been looking at stationary storage systems, where a PCM made up of a mixture of metallic salts was used to control the hydriding and dehydriding of a magnesium-based storage system.

During the meeting, we discussed the project(s) at length and covered all of the questions. A copy of the questions is attached, but the answers are included in their appropriate places in the following discussion. I also saw the system used for hydriding the

magnesium, although I was not given an actual demonstration. The discussion topics are characterized below.

III Questions and Answers:

Prior to our meeting, I forwarded a series of questions to Dr. Hynek. The questions and discussion based on them are shown here.

The PCM Project:

- 1. What is the status of the phase change material project that you were involved with earlier? Were any data generated confirming the theory; how many cycles were possible?**

Dr. Hynek stated that the PCM project was successfully completed and that he had submitted a final report. According to Dr. Hynek, a phase change reactor was made that works. The system was very heavy however, and only applicable for stationary systems. *(Interestingly, it was for stationary systems that the project was geared in the first place.)* In addition, the PCM system chosen was very corrosive, especially at the temperatures needed to hydride magnesium. Therefore, it was necessary to use stainless steel vessels.

According to Dr. Hynek, however, the system was tested successfully, and run for a “few cycles”. At this point, they ran out of funding, and the reactor was decommissioned. Due to this, they “never gave it the opportunity to break down.” *I always had my doubts as to how many cycles a rather delicate balance could have been maintained for the relative concentrations of a three-component system that relied on fairly small temperature differences to drive the hydriding/dehydriding sequence.*

Nickel Coated Magnesium Powder:

The original PCM project evolved to focus on coatings of the hydride material. This was due to protect the magnesium, and to increase the kinetics of the hydriding reaction. Thus, the current project was supposedly “Stationary Storage and Purification of Hydrogen using Nickel Coated Magnesium Powder”. Indeed, that was how the project started. While nickel coating did improve the kinetics, it was not impervious to impurities, and broke down.

- 2. What would the magnesium hydride system weigh on a per kg H₂ basis? Is this compatible with on-board storage?**

When working with the nickel coated magnesium powder (NCMP), the ADL group was able to obtain about six percent hydrogen on a hydride-only basis. Dr. Hynek indicated that in addition to the container, the only additional system weight would be some tubing and a check-valve. Dr. Hynek indicated that he thought this system was too heavy for conventional, primary storage, but it might be compatible with buffer storage. *(See discussion below on their current surface work.)*

3. How effective were NCMPs in storing/regenerating already purified hydrogen, simulating electrolyzer-produced hydrogen?

The dehydriding temperature of the system is 300-350°C. Thus, NCMP was very effective in storing and regenerating already purified hydrogen, and even worked well with commercial grade hydrogen. It just doesn't work with reformat, and that right now is the ADL direction of choice.

4. During your recent annual review presentation, you spoke of magnesium nitride coatings. Are these in place of NCMPs or are you still looking at the nickel coatings also?

The work on NCMP is not being pursued. The title of the annual review presentation addresses NCMP only because this was the original title of the project. The only work currently going on involves thin coatings for selective penetration by hydrogen.

The Current Surface Treatment Project:

The project that is currently being undertaken by ADL involves the use of Mg_3N_2 as a coating for magnesium particles. The goal was to develop or identify surface materials that would selectively pass hydrogen. This would allow the use of on-board hydrocarbon reformers to be used, and result in sufficiently pure hydrogen being passed to the fuel cell.

The thinking was that if any coating can be made thin enough, it will selectively pass hydrogen. Magnesium nitride was chosen because, since it is a salt of magnesium, it would more likely adhere to magnesium. In addition, the nitride can be made in an inexpensive process by reacting magnesium with ammonia. At the right temperature, the reaction is self-limiting, so the coating will be thin.

5. When being used on-board in conjunction with an on-board reformer, is the intention for the system to be used only during the period of time that the reformer is warming up?

Dr. Hynek believes that a potential application may be to use the coated hydride to provide buffer storage, i.e. use the hydride to provide hydrogen to the fuel cell until the reformer is hot enough to begin producing its own hydrogen. Additionally, it could be used to provide peaking power for hill climbing. It could be a fairly simple system, utilizing a pressure regulator and a check valve.

6. Do you envision NCMP as a purification system, a storage system or both? Is it exclusively an on-board system, or would it have an application for, say, a replacement for PSA or membrane purification systems on a stationary reformer?

It could conceivably take the place of a PSA system. It might also reduce a pre-compression step. The temperatures would be about right for this type of an application.

7. You have spoken of the “temperatures of interest” for the hydride system to be 300-400°C. The DOE program is looking for hydride storage systems operating in the 150°C range to be more compatible with PEM fuel cells. How does this particular system fit in?

The 300-400°C “temperatures of interest” is not compatible with either the operating conditions of the PEM fuel cell, nor is it near the DOE storage temperature goal. There are two answers: first, a cooling system will be needed anyway to handle the reformat. Secondly, since this will be a buffer system, rather than a primary storage system, the issue is not as important. *While it is true that a buffer system is not going to have the capacity of a primary storage system, the question remains: why have the cooling problem at all? Why not look at a lower temperature system? The answer is, I think, that they are committed totally to the on-board reformer concept – a concept that is much more compatible with the higher temperature storage system.*

Dr. Hynek indicated that the magnesium nitride coating was not as robust as expected, and only lasted a couple of months. He believes, however, that recoating can easily be accomplished. Perhaps also, ammonia can be left in the vapor phase above the hydride for continuous regeneration. *Recoating every couple of months seems excessive. An ammonia atmosphere permanently set over the hydride seems like it would lead to a complex separation process. Would you need a second infrastructure to keep an ammonia supply available?*

8. Are there any plans to address coatings for hydriding materials other than magnesium?

Nickel is not a candidate coating for a reformat purification process, although during our conversation, Dr. Hynek came upon the thought that a Ni/Mg nitride might be a good coating candidate. It might be better kinetically than the straight magnesium nitride. The nitride coating is not as good kinetically as was the NCMPs. With the nitride system, Dr. Hynek has been using platinum as a dissociation catalyst, and concedes that he may need a platinum washcoat.

Dr. Hynek believes, however, that the answer lies with a different coating material, and that’s the direction in which he’d like to see the research go. He indicated that they have a couple more coatings to look at. Their identity is proprietary, however.

IV Tour:

The hydride facility is a stand-alone 6 x 15-foot structure. A bank of six hydrogen tanks attached to a manifold stand outside the building. Inside the building, the reactor consists of six test vessels each containing coated hydrides. Each vessel has its separate heating system, and is equipped with thermocouples and pressure transducers. A data logger

records pressure and temperature for each vessel. Current hydriding conditions are two hours at 300 to 350°C.

Using a new gas manifold, each test vessel can be filled with a variety of gas mixtures (to simulate reformat feeds) consisting of hydrogen, CO, CO₂, and steam. Previously, the same vessels were used to apply the coating to the magnesium powder. Chemical vapor deposition (CVD) was used to form the nitride coating from ammonia:

This reaction is self-limiting, with the formation of a thin, complete coat. Dr. Hynek indicated that the new, proprietary coatings might require a “fancier” mode of application.

In the previous work, NCMP were produced by a CVD process using a nickel carbonyl [Ni(CO)₅] precursor. This was not a pleasant material to work with.

V Additional Issues:

ADL is looking at on board reforming as a major thrust. They would “not be happy” with a project that emphasized on-board hydrogen storage. Therefore, Dr. Hynek is looking at options that will support on-board reforming. ADL does not see hydride storage upon a vehicle as practical because it is too heavy.

The ADL view is somewhat infrastructure based. The thought is that if a refueling station is built, it should mirror the on-board system. If the on-board system is metal hydride, there should be stationary metal hydrides in the refueling station. If you have a liquid infrastructure, the on-board hydrogen source should also be liquid.

Right now, there are no plans to investigate non-magnesium storage systems. Magnesium was chosen for its low cost, and high storage capacity. (Recall that the original application for the PCM-based system was stationary storage, and that the current thrust is on-board reforming. The magnesium system is more compatible with both applications than it is with on-board hydrogen storage for PEM fuel cells.) Dr. Hynek did concede that maybe it would be worthwhile to look at other, lower temperature hydrides even if their capacity is not as great, especially if you are just looking at a small buffer system.

Technical Evaluation Report

Project: Hydrogen Storage in Metal Hydride Slurries

Company: Thermo Power Corporation, Waltham, MA

P.I: Dr. Ron Brault

Date of Visit: June 9, 1998

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

Thermo Power Corporation (TPC) is working on two projects for the DOE Hydrogen Program. They involve the use of metal hydrides in slurry form to transport and store hydrogen for both on-board and stationary storage applications. The methodology being studied is somewhat unique within the portfolio of hydride storage being investigated by the DOE program.

In all, the TPC project so far contains much to be impressed with. Slurry work is going well, proceeding toward a light-weight, high energy-density system, and hydrogen generation tests appear to be proceeding acceptably as well. The concept set forth for on-board systems appears sound, but needs to be demonstrated. Stationary storage systems, the original concept appears neglected for the time being, but also appears to be a viable concept. The overall regeneration process is the biggest problem right now. It needs to be the focus of future work.

Project Strengths:

- They have identified a hydride carrier (light mineral oil) that is a good medium for this type of slurry, and that also protects the particle surface from premature or a too rapid reaction.
- They are concentrating on materials that have the potential to give a high hydrogen loading, especially lithium hydride (LiH), which produces 2 grams of hydrogen for each 8 grams of hydride; and calcium hydride (CaH₂), which produces 4 grams of hydrogen for each 42 grams of hydride:

Sodium would only provide two grams of hydrogen per 24 grams of hydride:

- They are making slurries that have solids loadings that are up to 90% by weight, that are pourable and appear easy to handle.

Issues that should be Addressed:

- They have not yet addressed the quite complex regeneration (of hydride) sequence. This could be a real show stopper because:
 - The thermodynamics and efficiency of the proposed reaction sequence may not be sufficient to make the process economical.
 - Maintaining water/hydride management (not allowing contact when it's not wanted) needs to be demonstrated.
 - The regenerated hydride will likely not be easily slurried. Perhaps the reconstituted slurry will be as costly to make as the original one.
 - The regeneration reaction scheme generates CO₂. This weakness is shared by many of the Program projects.
- The overall on-board system including the presence of spent hydroxide, the amount of water needed to augment fuel cell-generated water, and the overall refueling system must be addressed in much greater detail than has occurred to this point. For instance, the calculation for the percentage hydrogen in the on-board system needs to include the hydroxide. Slurry stability in a moving vehicle has been inadequately addressed, as have pumping tests.

II Introduction and Background:

TPC (formerly Tecogen), located in Waltham, MA, is currently involved in two projects for the DOE Hydrogen Program. One is in the R&D portfolio, and is involved with the use of a hydride slurry to produce and store hydrogen. The second is a validation project that is concerned with an on-board storage system for hydrogen again utilizing slurry technology. The two projects are closely tied together, with much that is to be accomplished in the first project (slurry technology, regeneration of the hydride) being used in the second. I visited TPC on June 9, and met with **Dr. Ron Brault**, who is the Principal Investigator on both projects. He made a semi-formal presentation that covered a composite of the two projects. He and his coworkers showed me several slurries and ran a hydrogenation demonstration, and he also provided answers to the questions that I had sent him prior to my visit. We divide the following discussion into matters relating to slurries, hydrogen generation, on-board activities, and hydride regeneration. The questions are included at the beginning of each section.

III Questions and Answers:

Slurry Materials and Processing Considerations:

1. **TPC's report indicated that a 38% NaH slurry had a viscosity of 250 to 300 cps. What viscosities did the LiH and CaH₂ slurries have? What type of viscometer was used in the measurements? Are the slurries Newtonian or are they affected by shear rate? Do the added dispersants affect slurry rheology?**

2. **Is the aluminum powder premixed with the slurry or the water? What role does the aluminum take in the hydrogen release reaction? Does it eventually form $\text{Al}(\text{OH})_3$? Will it then be an additional problem during the later separation step?**
3. **Were fluid CaH_2 slurries ever made, and if so, what were their properties?** *At the time of my sending the questions to Dr. Brault, all of his reports were indicating that no pourable slurry had been made to date with calcium hydride.*
4. **Is there any effort to tailor the particle size distribution (PSD) of the hydrides to increase the slurry solids loading? What is the modality of the PSD?**

After working with preliminary systems that featured sodium hydrides in various carriers (notably acetone), TPC is now concentrating on lithium and calcium hydrides, and has settled on mineral oil as the liquid medium. In choosing lithium and calcium, TPC has chosen probably the best two choices for hydrides based on weight percentage potential. *The selection, of mineral oil, I would consider to be in the nature of a mini breakthrough.* Mineral oil serves as both a carrier and a reaction controller. Its hydrophobic nature prevents premature or too rapid dehydriding of the solid. Mineral oils also have a low vapor pressure. The particular mineral oils used by TPC have been acid-scrubbed, so they are inert. *One caveat might be the fact that “mineral oil” is a generic term. Product consistency could be a problem unless TPC takes steps to better identify the material and determine its batch-to-batch consistency.*

When TPC began their work, they first looked at sodium-based slurries. This was because sodium hydride was readily available, and is not extremely reactive. When they began to make the slurries and generate hydrogen from them, they found that the production reaction appeared to be pH limited. That is, as water was added, hydrogen was being generated, and NaOH was being formed, raising the pH of the mixture. At a pH of about 13.6, the reaction stopped. As a result, TPC tried adding powdered aluminum to the slurry as a means of scavenging the NaOH. (Aluminum will dissolve in base to give the aluminate ion, AlO_2^- .) While this approach was successful in controlling the reaction rate for the sodium system, TPC meanwhile moved on to Li and Ca systems to increase potential storage capacity. Since LiOH and $\text{Ca}(\text{OH})_2$ are much less soluble than is NaOH, the base limitation never occurred. Therefore, the need for aluminum no longer exists, and this potential bottleneck is no longer an issue.

TPC has considered lithium and sodium borohydrides as well; these materials are not as reactive as the straight hydrides, and therefore hydrogen generation might be more controllable. However, the boron acts as a buffer, which limits hydrogen generation. In addition, the regeneration of these more complex materials would also be more complex.

Note: Despite the presence of four hydrogen atoms in each borohydride molecule, these materials are only slightly more efficient a hydrogen producer than the straight hydride on a weight basis when one looks at the whole system:

For instance, comparing LiBH_4 with LiH : 22 grams of LiBH_4 produces 8 grams of hydrogen, but also produces 24 grams of LiOH and 62 grams of B(OH)_3 (8.5% hydrogen). In reaction [1], 8 grams of LiH produces 2 grams of hydrogen, and 24 grams of LiOH (7.7% hydrogen.)

TPC is making laboratory slurries in small jar mills (about one quart size) using ceramic cylinders as the grinding medium. They have demonstrated slurries that are above 90% by weight. Proprietary dispersants are used - one percent by weight for lithium and two percent for calcium. *These dispersants could become a cost issue, but we have no information.*

Lithium hydride slurries are very easy to mill. (They mill wet.) Calcium hydrides are somewhat more difficult, but they are making good progress on both, being in the over 90% by weight range. One interesting phenomenon: Lithium hydride is less dense than mineral oil. When separation occurs, the hydride floats to the top. *This would make remixing easier in a scenario where the slurry would be shipped in barrels.*

A photomicrograph is used to determine particle size distribution, and a Zahn cup measures viscosity. They measure stability using paint industry standards. Slurry particle size distribution is more or less monomodal and in the 5-10 micron range. No attempt has yet been made to tailor the particle size distribution. Viscosities are in the 100-300 centipoise (cps) range at low shear rate. Dr. Brault mentioned that the slurries appear to be Bingham plastics, having a yield point. *There is not a lot of attention being paid to slurry properties at this point. There is no attempt to raise the solids loading or increase the stability by particle size adjustment, or to address the non-Newtonian rheology that appears to exist. Pumping tests will have to be addressed soon if TPC wishes to pump their slurries over any distance; slurry pumping problems could cause a drastic reformulation of these slurries. On the positive side, this team is quite knowledgeable about slurries, and these issues will be addressed.*

Hydrogen Generation:

5. **One of the monthly reports indicated that LiH only released about 41% of the expected hydrogen and that more experiments were planned. Were they ever completed? Success with LiH appears to be of extra importance due to its higher weight percentage of hydrogen, all else being equal.**
6. **Many of the reported tests are indicating that the hydrogen generation reaction does not go to completion due to pH and pressure effects. This implies that some of the hydride remains unreacted. Will this pose a problem later when the mixture is removed from the reaction chamber and the pressure is released? In other words, can it lead to hydrogen generation occurring downstream?**

TPC has now demonstrated 95 percent hydrogen recovery from their hydride slurries. They believe that when they build an engineered reaction chamber, they will do even better.

LiH generates hydrogen somewhat faster than does CaH_2 , but they are more or less in the same range.

Dr. Brault and his associates provided a demonstration of hydrogen generation from CaH_2 . They mixed the hydride and water in a 1 to 2 molar ratio in a reaction tube, producing hydrogen in what appears to be a controlled reaction. The heat of reaction drove the temperature up to about 300°F (lithium hydride gives off less heat; the temperature is generally around 200°F.) The reaction appears to be pressure limited. Dr. Brault indicated that reaction during the recycling process could indeed be a problem if hydrogen generation was not complete when intended. One of the goals is to make a slurry with a lot of fines so that there is a high surface area. This will cause an accelerated reaction rate early in the process, and help ensure reaction completeness. *However, it might prevent the slurry from being optimized for solids loading and, therefore, energy density.* Dr. Brault pointed out that they need to get away from their current bench-scale batch process for hydrogen generation, and begin some flow tests for the hydrogen generation data to be realistic. *I agree about the need for flow tests to authenticate the data. Reaction completeness may be a problem in a practical setting, however. We discuss this more in the On-Board section.*

Dr. Brault mentioned another application for a batch hydrogen generation system: If you run the pressure-limited reaction in a canister, you can stall the reaction until you release the pressure. This could have military applications.

On-Board Considerations:

- 7. In determining the storage capacity of the on-board hydrogen system, is the amount of water being carried taken into account?**
- 8. In incorporating a hydride slurry for on-board applications and transporting of hydrogen as well, what sorts of tests have been performed or are planned to ensure slurry stability?**

Dr. Brault spoke of using water produced by the fuel cell as reaction water to generate hydrogen. He stated that they would need about a one-liter start-up water tank to generate sufficient hydrogen to get the system going. *One liter of water weighs one kilogram, and equals 55.6 moles of water. This will produce 55.6 moles of hydrogen either from LiH or CaH_2 , which in turn is equal to about 0.11 kg of hydrogen. At 93 miles/kg of hydrogen, this would allow about a ten-mile range in addition to the fuel cell water.*

The numbers reported by TPC do not include the extra liter of water. *Complete analysis would have to include it, as well as the weight of the hydroxide formed. The simplest way to do this is merely calculate the hydrogen produced as a fraction of all the reactants (as*

opposed to just the hydride). For instance, for the lithium system in equation [1], two grams of hydrogen are formed from eight grams of lithium hydride and eighteen grams of water. This amounts to about four percent hydrogen, but this is provided without adding heat.

Dr. Brault indicated that on start up, a small battery would run the slurry pump to move slurry into the reaction chamber. Water from the reserve would be added, and hydrogen is generated for the fuel cell. The water reserve would also come in to play for peaking operations such as hill climbing.

TPC sees that the methodology of refueling of a vehicle should mimic the existing infrastructure as much as possible. Thus, they would consider a slurry system as mimicking the existing gasoline infrastructure. One difference would be that you would need to pump spent hydroxide out of the vehicle while you pumped new hydride slurry in to the vehicle. Dr. Brault envisions a bladder tank to separate the spent from the unspent fuel. *This immediately brings two problems to mind. First, it would mean either requiring one hundred percent conversion of hydride to hydroxide prior to removing the spent fuel. If this was not done, we would both suffer an efficiency loss (dumping good fuel) and be exposing the recovery system to further hydrogen generation, as both unused hydride and water would be present in the mix. Second, handling of the spent material would be a problem. It is unlikely that the spent material would still be in the form of easily handleable, pumpable slurry. Perhaps these problems could be solved by 1) multiple fuel tanks in the vehicle, so that one could be totally exhausted of hydrogen and the second would be in use when refueling the first, and 2) using a make-up carrier; perhaps more mineral oil to re-slurry the spent material. Note that these are solutions to two problems (not an either/or situation), and both could probably be quite costly as well as inconvenient. I don't believe refueling will be easy with this kind of system.*

The hydrogen generation process is exothermic. Dr. Brault sees simply employing a radiator on board to dissipate the extra heat. In a stationary application, combined heat and power could be an option. *Theoretically, it would be beneficial if the heat could somehow be used in the regeneration of hydride, but I guess that could not be done on board.*

In an attempt to simulate vehicular motion, TPC runs tests on shaker tables. This, according to Dr. Brault, duplicates the “sloshing” motion in a vehicle. *I believe that real vehicle tests are needed. Realistic motion in a real on-board tank cannot be simulated by a jar on a shaker table.*

Recycling/Regeneration:

- 9. Does the overall process involve the pumping of a hydroxide slurry? If so, is there any evidence that the slurry will be pumpable without additional processing?**

10. Have any laboratory scale tests on the reaction scheme that regenerates the hydride been carried out yet?

Dr. Brault envisions that spent slurry will be pipelined back to a central location for regeneration, and that a centrifuging method would be used to remove the mineral oil from the hydroxide before regeneration. Dr. Brault also mentioned that the particle size distribution of the spent slurry is not that much different from that of the hydride slurry, but that the viscosity is different. This, says Dr. Brault, may be a function of the stoichiometry. He believes that they may have to add water to make the slurry pumpable. *I am surprised by the fact that the particle size distribution did not change. I would think that the size and the shape of the particles would be affected greatly by the chemical reaction. Perhaps it didn't show up clearly in the photomicrographs. We have already mentioned that pipelining a slurry that has not been properly formulated will be difficult to handle at high loadings. Substituting a hydroxide in a slurry tailored for a hydride will likely be difficult. It will be further complicated by the solubility of the hydroxide in the excess water. While this will help reduce the solids loading and viscosity, it will further complicate the regenerative process. The centrifuging process may be inadequate. An evaporation step may be necessary. This part of the process needs to be investigated as a priority; it will dictate the available options for regeneration.*

TPC have not yet approached the regeneration process experimentally, but plan to address it in the fall. They will first perform static experiments in the furnace, and then proceed to small flow tests. The reaction scheme for regeneration can be expressed by the following (using the Ca system as the example):

TPC is considering electric arc heating for regeneration, but hope to be able to get a large portion of the needed heat from the exothermic reactions. There is a sizable efficiency penalty for using electric heating.

Dr. Brault thinks that they will probably be driven toward the lithium system, primarily due to its requiring less heat during the regenerating process than does calcium. (As mentioned before, lithium hydride has a higher energy density as well.)

It may be too early for us to assess this aspect of the process since TCP hasn't begun the testing yet. It seems that they have devoted a lot of time to the thermodynamics of the process, finding an overall essentially thermally-neutral reaction scheme. It is a very complex system, however, and I'm not sure how the kinetics will all play out, or if they can make a viable reaction process that will indeed be basically self-sustaining. They

won't find out until they go to the flow tests. It's a good overall process; it's too bad that they're making CO₂, however.

IV Final Thoughts:

TPC's closest analog is the unfunded Power Ball concept, and I believe, the TPC process is superior. I prefer the slurry as a mode of transport, and also feel that the LiH system, providing more hydrogen per unit hydride, is a better storage system.

Technical Evaluation Report

Project: The Use of Fullerenes to Store Hydrogen

Company: Oak Ridge National Laboratory (ORNL), Oak Ridge, TN

P.I.: Dr. Fang Chen

and

Company: Material and Electrochemical Research Corporation (MER), Tucson, AZ

P.I.: Dr. Raouf Loutfy

Dates of Visits: February 25, 1998 (Dr. Chen in Washington, DC)

August 14, 1998 (Dr. Loutfy in Tucson, AZ)

Evaluation by: Edward G. Skolnik, Energetics Inc.

A Meeting with Dr. Chen

I Introduction:

The use of fullerenes, primarily C₆₀ structures, as a means to store hydrogen is being studied by a team from Oak Ridge National Laboratory (ORNL) and Material and Electrochemical Research Corporation (MER). On February 25, I met in Washington with **Dr. Fang Chen**, the ORNL Principal Investigator, and spent about an hour with him discussing this project. During this February meeting, we held a preliminary discussion and I saw some small samples of fullerene powders and pellets, both with and without associated hydrogen. We also planned for a more formal meeting at MER later in the year.

II Fullerene and Hydrogenated Fullerene Appearance/Description:

Dr. Chen carried with him, fullerenes as a bulk powder, as a pellet, and deposited in a thin film on aluminum foil. He is especially excited about the thin film version, as he envisions a lightweight heat-transfer system. Although no cost of fullerene production has been offered, Dr. Chen indicated that MER believes that it can be made "inexpensively" in volume in an arc furnace. (They use a process similar to what Dr. Smalley of Rice University uses.) The bulk density of fullerene powders is about 1 gram/cc.

Hydrogenated fullerenes take on distinctive coloration, said to be as a result of light scattering. Dr. Chen had samples of stable hydrogenated fullerenes in powder form. A sample that was approximately 3 percent by weight hydrogen had an orange color, while a 4 percent hydrogen sample was an olive green. This phenomenon, its reproducibility, and possible uses is something that we will need to discuss with MER.

III Discussion:

Hydrogenation and Dehydrogenation Process:

The hydrogenate is relatively easy to make, and is quite stable. Without a catalyst it requires about 400°C or more, and 4,000-5,000 psi to produce. It is stabilized by cooling

and depressurizing. Using a catalyst reduces the required temperature and pressure considerably. Dr. Chen indicated that pressures would be in the 500 psi region and temperatures would vary depending on the catalyst, but would probably be closer to 200°C.

The need for catalysis for dehydrogenation is greater, as the uncatalyzed dehydrogenation reaction requires 160 kJ/mole, as opposed to 100 kJ/mole for the hydrogenation reaction. The currently ongoing work involves the finding/developing of the proper catalyst. The research team has been looking at solid, liquid and solution catalysts. This would be yet another subject of discussion during the visit to MER.

Theoretical Hydrogenation Limits:

The limiting factor as to what amount of hydrogen can be associated with a quantity of fullerene is unclear. If one hydrogen were chemically associated with each carbon, that is, C₆₀H₆₀, the theoretical limit would be 7.7 percent by weight hydrogen. However, it is unclear, according to Dr. Chen, whether the association between the carbon and hydrogen is chemical or physical.

I believe that a clue as to the answer to this may come from the kinetic expression that is associated with the dehydrogenation step. According to Dr. Chen, the rate of dehydrogenation of the uncatalyzed, hydrogenated fullerene obeys the equation:

$$\text{Rate} = A (C/C_{\max}) e^{-E/\kappa T} \quad (1)$$

where C is the hydrogen concentration in the fullerene and C_{max} is its maximum concentration, A is the Arrhenius pre-exponential factor, E is the activation energy, κ is the molecular gas constant, and T is temperature. Since the rate of a chemical reaction, (dr/dt) is a function of the reactant concentrations and a rate constant, the rate of a reaction

can be expressed as:

$$(dr/dt) = \text{Rate} = k [C_A]^a [C_B]^b \dots [C_N]^n \quad (3)$$

where k is the rate constant and C represents the concentration of the species in question.

The Arrhenius expression for the rate constant, k, can be expressed as a function of temperature by:

$$k = A e^{-E/\kappa T} \quad (4)$$

Therefore, the expression for the dehydrogenation process can be expressed as:

$$\text{Rate} = k (C/C_{\max}) \quad (5)$$

This is the form of a first-order reaction, dependent only on the concentration of C, in this case, the concentration of hydrogen. This would indicate that since the reaction rate is not dependent on the rate of concentration of the fullerene hydrogenate, that the fullerene hydrogenate is not a chemical species, but that the hydrogen is physically held within the fullerene structure. At least, it indicates that the rate-determining step is the physical removal of hydrogen from the matrix. This means that the theoretical chemical limit to the degree of hydrogenation may not be the actual limit.

IV Interim Conclusion:

The project appears viable at this stage, especially if 6-7 percent hydrogen is a reality. I hope to learn a lot more later on when I visit MER (see below). While I developed an understanding of the thermal management calculations involved, I think that I will learn more as to what is going on chemically at MER. I'll also get a better feel for the degree of difficulty of making fullerenes in these forms.

The path that ORNL/MER is taking now – getting a catalyst that will lower dehydrogenation temperature seems sound. Their initial efforts indicating that liquid or solution catalysis is preferred, again makes sense from the approach of addressing reactant/catalyst contact.

B Trip to MER

I Summary:

Of the three projects that are referred to as “carbon structure” storage projects, the one being conducted by the team of Oak Ridge National Laboratory (ORNL) and Materials and Electrochemicals Research Corporation (MER) is by far the furthest along. They are at least at the several kilogram level in producing their storage material, fullerenes, and have demonstrated close to theoretical hydrogen take-up levels. On the other hand, theirs is the only carbon structure that definitely requires both heat and pressure to “move” hydrogen. Because of this, the ORNL/MER team has added a new element to their project. They are now looking at not only fullerenes but at “organic hydrocarbon” hydrogen storage as well.

This group is probably closer to a “real” system that meets DOE goals than any other with the exception possibly of U Hawaii’s work. It provides higher storage loadings than the metal hydrides, and is farther along in terms of scale-up than the other carbon structure work.

Project Strengths:

- The thermal management approach appears to be very sound. Much of what ORNL predicted when running the thermodynamics and kinetics of the fullerene processes appears to have been proven in experiment.

- MER, as an expert in carbon structures appears a good choice as a CRADA partner.
- The already achieved storage numbers of over six percent by weight hydrogen (non-system base) and over 90 kg/m³ on a volumetric basis (based on a stated material bulk density of 1.5 g/cc for pelletized fullerene) meets the DOE goal.
- The group may not have much farther to go in reducing the temperature, especially if higher temperature PEM fuel cells become available.

Issues that should be Addressed:

- The effort is now being split to include a very different system. Can both the fullerene system and the new organic hydrocarbon system be pursued to the necessary level without diluting the effort?
- In what way does the hydrocarbon system differ from work being done elsewhere? (such as the University of Hawaii). MER's expertise is in fullerenes. This is not a fullerene system.
- What will the effective degree of hydrogenation be for either the fullerene system or the new system? If each hydrogen atom comes out progressively more slowly, it may be too difficult or too costly to get sufficient hydrogen out. System thermodynamics/kinetics need to be matched up with the needs of a practical system.
- The practical system needs to be mapped out. (Actually two systems, the fullerene and the organic hydride) How would it look on a vehicle?
- There was, initially, some misconception as to the state of hydrogen in the storage system. ORNL reported several times that the rate of the uncatalyzed dehydrogenation process was proportional to the "concentration of hydrogen in the fullerene." I interpreted that to mean that hydrogen was entrapped in the fullerene by a physical process, and was told at first, that the storage could very well be physical. In actuality, the storage is chemical, and the relationship is with the number of hydrogen atoms in the molecule C₆₀H_x. In the meeting at MER, it was made definitively clear that the species was chemical; there was no question.

II Introduction and Background:

I met with **Dr. Raouf Loutfy**, the President of MER, on August 14th at his facility in Tucson, AZ. Also present at the meeting were **Rick Murphy** and **Jim Wang** of Dr. Chen's staff at ORNL

MER has a CRADA with ORNL in which MER is responsible for the production and hydrogenation of fullerenes, while ORNL is responsible for the thermal management activities. Thus, ORNL determines and tests the conditions under which fullerenes can

best be hydrogenated and dehydrogenated, while MER produces the materials and runs the experiments.

MER, established in 1985, has historically been involved with fullerenes due to its proximity to the University of Arizona. Although fullerene production methodology was invented by Professor Smalley of Rice University, it was the University of Arizona that brought fullerene production into practice; they have the license. MER is the world leader in fullerene production. Among its other interests are carbon/carbon composites, and fuel cells.

III Discussion-Fullerenes:

Production of Fullerenes:

MER basically uses the Smalley method to produce fullerenes; that is, they use an arc furnace to vaporize carbon rods. Their bench-scale facility can produce about 0.5 kg/day of fullerenes by this method. Production of fullerenes includes the usage of thin carbon rods as the anodes for the arc discharge. The thinness of these rods and their lack of bulk lend them to vaporization and fullerene production. Thicker carbon electrodes would transfer too much of the arc-derived heat away from the surface, and make the process inefficient.

In the development of the methodology for scale up of this process, one must consider the fact that using bigger, thicker rods would lead to inefficiency. MER, however, has developed a proprietary process by which they maintain high efficiency. Dr. Loutfy estimates that the cost of producing fullerenes in the bench scale process is about \$12,000/kg. Using the scaled up (lab-scale/PDU) process that could produce up to 30 kg/day of fullerenes the cost would drop by a factor of about 100, to \$120/kg. This is still an intolerably high cost, but keep in mind, we are still talking about a PDU.

Dr. Loutfy feels that to justify a scale-up to, say, pilot plant size, they probably need two or three applications for the fullerenes. Hydrogen storage would be one of the applications. MER revealed that there is another currently proprietary application being spearheaded by a Japanese chemical company. Consequently, they have sold a license to this company to promote this unnamed product in Japan. (MER would retain the rights in the U.S. and Europe.) About another order of magnitude decrease in the cost of fullerene production is needed to make the material competitive. Dr. Loutfy stated that a breakthrough will be needed for this to happen, and is looking for the Japanese to lead the way initially.

Physical vs. Chemical Sorption of Hydrogen:

In the earlier report, we discussed the possibility that the hydrogen take-up by fullerenes may be physical rather than chemical. We had brought this hypothesis forth based on an ORNL report that the dehydrogenation process rate expression obeyed the relationship:

$$\text{Rate} = A (C/C_{\max}) e^{-E/kT} \quad (1)$$

In which “The dimensionless factor ($C/C_{\max}$) is intended to capture the trend that at a given time, the hydrogen escape rate is proportional to the amount of hydrogen present in the sample.” Since the rate of a reaction cannot be dependent on its products, but only on its reactants, I concluded that the hydrogen/fullerene association must be physical, and the dehydration rate controlled by the diffusion of hydrogen out of the fullerenes. Dr. Loutfy now informs me that the factor ($C/C_{\max}$) actually refers not to the hydrogen concentration, but to the value of “x” in the chemical species $C_{60}H_x$ – the fullerene hydride. In other words, the species is indeed chemical, and the rate of dehydrogenation is based on the concentration of the reactant in the reaction:

As the value of “x” decreases, the reaction slows. Thus, complete dehydrogenation is difficult. This may be the most serious consequence of the process. The ORNL/MER project is already hampered by hydrogenation/dehydrogenation temperature and pressure conditions. One would not wish to resort to yet higher temperature to squeeze out more hydrogen. At the same time, if you can’t get the hydrogen out, it doesn’t count.

Physical adsorption of hydrogen by fullerenes, in fact, according to Dr. Loutfy is limited to about 0.2% by weight. It takes about 2.5 electron volts (60 kcal) to penetrate the fullerene cage; Dr. Loutfy says that this is less than the energy of C-H bond formation. (Bond energy tables show the C-H bond energy to be 80 kcal.) Regardless, since the kinetics follow reaction #2, it has to be chemical. Thus, the species is chemical, and therefore, an organic hydride. Thus, the chemical saturation of $C_{60}H_{60}$ is valid, and the theoretical hydrogen concentration (exclusive of system) is 7.7% by weight.

Fullerene Hydride Make-up and Appearance:

As we mentioned above when reporting on our conversation with Dr. Chen, fullerene hydrides can be pelletized without any loss of structure. At that time, Dr. Chen reported a bulk density of about 1.0 g/cc. Dr. Loutfy now reports that they have achieved bulk densities of up to 1.5 g/cc. We also noted that fullerene hydrides take on various colors, depending on the hydrogen concentration. This has been explained as having to do with the fact that as the amount of hydrogen in the fullerene increases, the material becomes more paraffin-like in nature. $C_{60}H_{60}$ as a cage structure would be a paraffin – no double bonds, saturated in hydrogen. The typical high molecular weight paraffin is white in color, and as the fullerene hydride adds hydrogen, it becomes lighter in color. A reasonable argument, and one that also would have been good to have earlier when we were considering the system to be a physical adsorption system.

Hydrogenation and Dehydrogenation of a Fullerene:

The major problem facing this project is the fact that currently it still takes too much heat and too much pressure to hydrogenate and dehydrogenate a fullerene. As reported earlier,

without a catalyst it takes about 4000-5000 psi at 400°C to hydrogenate fullerene, but one can essentially reduce the pressure by an order of magnitude, and reduce the temperature into the 200°C range by using a catalyst. A key factor with using a catalyst for hydrogenation and especially dehydrogenation is in the degree of contact between the fullerene and the catalyst. Most early-on results involving catalysts involved solid catalysts and solid-solid contact. Later, MER dissolved the catalyst in a proprietary solvent to promote better contact. This provided a medium in which hydrogen atoms can better be transported, thus reducing the activation energy for the process.

IV Discussion-Liquid Systems:

The success that ORNL/MER has had with the concept of improved contact has led them to investigate new all-liquid systems. In other words, these are systems that no longer contain fullerene(!) Using a proprietary material that they simply refer to as Organic Hydride #1 (or OrgHyd1) and a new, proprietary liquid catalyst system, MER is currently achieving up to 7% by weight hydrogen under 350-400 psi at 180°C. Dr. Loutfy indicated that they could currently recover up to 75% of the hydrogen. The activation energy for the dehydration step with this system is only half of what it was for the fullerene system (84 kJ/mole vs. 160 kJ/mole). Dr. Loutfy described OrgHyd1 as a “very low cost feedstock,” and one that would require a system volume only about ten percent more than gasoline.

The new system has the thermal advantage over fullerenes, but may suffer in other respects. For instance, how easy is it to separate hydrogen from the liquid system. Two problems; i) is hydrogen at all soluble in the organic material and ii) how easy is it to separate the gaseous hydrogen from the organic vapor? Of course, these two problems are also potential problems with the solvent systems for the fullerene catalysts.

V Other Topics:

Nanotubes:

On a different topic, Dr. Loutfy mentioned that MER has made some nanotubes for Mike Heben (NREL) using the carbon arc-discharge method. In a two-hour period, they made about 30 grams of material of which about 20 percent was single-walled nanotubes (SWNT). They performed hydrogen adsorption tests with the material, and found that they were getting about 2.5% by weight hydrogen adsorption on a total material basis. Interestingly, they found that if they milled the material, breaking up the nanotubes, they actually somewhat increased the amount of hydrogen adsorption.

Still on the subject of nanotubes, Dr. Loutfy brought up the name of Mayya Papan. He is a theoretician at NASA Ames who has run some calculations on the use of SWNTs as storage media. He believes that SWNTs may close if heated. This may also be the case for the spacings between graphitic plates of nanofibers. Thus, this may become an issue for both the NREL and Northeastern nanostructure projects, especially, if one or both

projects evolves into something that requires some heat to speed up the hydriding or dehydriding process.

Fuel Cells:

Among MER's other interests is the fuel cell business. Their expertise in carbon/carbon composites has led to their making bipolar plates of this material for PEM fuel cells. They are currently making 50-watt stacks under an Army contract for use by foot soldiers. The fuel cells have an energy density of 150 watts/kg. In addition, MER has a contract with DOE for fuel cells for buildings.

Technical Evaluation Report

Project: Improved Metal Hydride Technology

Company: ECD Corporation, Troy, MI

P.I.: Dr. Krishna Sapru

Date of Visit: August 21, 1998

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The hydrogen storage group at Energy Conversion Devices, Inc. (ECD), have an excellent understanding of metal hydrides, how to make them, and how to use them. In addition, they have available to them an abundance of diagnostic equipment, making the obtaining of timely data in house possible. This makes ECD a very good place for the undertaking of applied R&D leading to commercial products. **Dr. Krishna Sapru** and her team seem to have approaches toward developing a hydrogen storage system that is well thought out, and multifaceted. The metal hydride R&D, however, seems to be pointing toward a conclusion that one cannot have both a high weight percent hydride (over three percent on a H/(M+H) basis) and a low dehydriding temperature material (below about 100° C).

ECD does not appear concerned with <3% H/(M+H), which works out to about 2% system weight. They say that Ron Sims of Ford finds this level quite “adequate”, and that Ford “loves metal hydrides.” *There are many niche markets where 2 weight percent system weight is reasonable, but I would think, this would not include mainstream applications, that is, for use on board light-duty vehicles.*

The magnesium work does not appear to be progressing sufficiently. Its use may be likely limited to niche market applications. ECD has not investigated the transition metal hydrides in nearly as great a degree; low temperature systems will most likely be achievable, but their theoretical hydride loading is limited greatly by the high atomic weights of the metals in question. ECD is currently concentrating on market identification for their magnesium and transition metal hydride systems. There is still a possibility, however, that ECD will achieve a more widely useful system. They have recently produced some ultra-fine (under 100 nm) size alloys that may lend themselves better to hydriding/dehydriding kinetics. This in turn could lead to a lower temperature system for a given composition.

II Introduction and Background:

On the above date, I visited Dr. Krishna Sapru and her team at Energy Conversion Devices, Inc. (ECD), in Troy, MI. I was given a tour of their United Solar unit and their Ovonics Batteries unit as well as a tour/demo of their metal hydride work. There were also several hours of discussion with Dr. Sapru and five members of her staff. I also met briefly with ECD President Stan Ovshinsky, mainly a courtesy visit, and even got a ride in an EV.

ECD and its subsidiaries are about 400 people strong. Their United Solar (PV) and Ovonics (Nickel Metal-Hydride Batteries) divisions, including their General Motors-Ovonics Joint Venture, seem to be going full speed ahead. (United Solar is owned jointly by ECD and by Canon of Japan.) They also have an “information” division that looks at materials that store information by undergoing physical and/or chemical changes.

ECD got into the hydrogen business in 1980 through a contract with ARCO when the oil company was investigating alternative fuel options during the energy crisis. At that time, they investigated aspects of hydrogen production, storage, and utilization. This respectively involved alkaline electrolysis (developed thin film electrodes), disordered materials (sputtered thin films), and alkaline fuel cells. Although this was only a three-year project, it provided the knowledge that ECD used to develop their nickel metal hydride (NMH) battery business. NMH technology was first investigated by Daimler-Benz, but it was ECD that led the way to commercialization. Nearly every battery manufacturer in the world has licensed some part of ECD’s NMH technology. Their current NMH activities concentrate on batteries for vehicles.

III Questions and Answers:

I had provided Dr. Sapru with a list of questions and discussion topics prior to my visit. She and her staff compiled answers to these questions prior to my arrival, and these answers formed the basis for our extensive discussion. These questions and answers are discussed below:

Materials:

1. Do you plan to look only at magnesium based alloys or will you look at other materials as well?

ECD is and will continue to look at Mg systems, but is also approaching the goal of high-capacity low-temperature storage from the other direction by investigating low-temperature transition metal hydrides (e.g., Ti-V-Zr). They combine elements by examining pressure vs. temperature profiles. Currently, they are beginning to achieve hydride weights of about 1.5% at room temperature, and indicate that these levels are applicable for certain niche markets.

ECD believes that the “current goal”, stated as 3 wt% hydride 2 wt% system is achievable, and are the type of systems that have many applications. ECD has spoken to Ford’s Ron Sims, who believes that 2 wt% system is perfectly adequate and is a desirable system due to its high safety. Dr. Sapru also pointed out that these 2 wt% systems have applicability in context with small, stationary fuel cells. ECD admits that improvements to the magnesium hydride systems present a challenge, but feel they are making “slow but steady progress.”

It appears to me that ECD considers these magnesium hydrides as being of limited value. They are talking about niche markets and special cases. Their work with the transition metal hydrides may work out better, but these are weight percent-limited by the weight of the metals.

2. What role does Mo play in the Mg/Ni/Mo alloys?

Molybdenum, acting more like a dopant than an alloy, serves as a catalyst for both hydrogen dissociation and for the absorption/desorption process. It forms oxides that are more conductive than resistive. Levels of 1 wt% Mo are sufficient. The use of Mo for this purpose arises from ECD's work in the early '80s. At that time, ECD showed that the addition of Mo to Mg-Ni electrodes improved the hydrogen evolution reaction by reducing cell overvoltage.

3. Are any data available for systems in which you use the four-part alloys that you have spoken about? This refers to Dr. Sapru's presentation at the 1998 Annual Peer Review, where she alluded to Mg-Ni-Mo-C alloys.

In fact, most of the data presented during 1998 involve these kinds of systems. Results for these four part systems are quite reproducible. Recently, ECD has even been working with five and six part systems in order to lower the desorption temperature.

Alloy preparation:

4. In particle size experiments, what characteristics are you looking for to optimize a system? (For example, narrow or wide or multimodal distribution, high surface area, regular/irregular shape, introduction of eccentricities, etc.)

Kinetics are improved by the use of high surface areas, that is, a high percentage of fines. Thus, the goal is a narrow particle size distribution with most particles between 1 and 10 microns in diameter. When measurements are made, the powders are sieved first, and measurements are made on only the <45-micron fraction. In addition, measurements are rarely taken prior to about five hydriding/dehydriding cycles. These cycles act to break particles (hydrogen embrittlement) and improve the kinetics. The system is stabilized after 5-10 cycles.

Particle shape is not controlled; particles are generally spherical. Mechanical alloying introduces stresses into the particles, which lead to disorders. These disorders are preferred for improved storage properties.

The need for several hydriding cycles, or a "breaking in" process will, of course, need to be accounted for in any demonstration/commercial venture, or simulation.

5. How reproducible by chemical structure are materials that are made by a mechanical alloying process, and how reproducible are their properties?

Chemical composition is “generally reproducible,” while properties, especially kinetics can vary in some cases. Dr. Sapru cited Mg-Ni-Mo-C as a very reproducible system both in composition and in properties, while Mg-Ni-Cu-Fe-Mn-Si-C has reproducible composition, but varies from run to run in properties, especially kinetics.

6. When you refer to “yield” following a grinding process, what exactly does that mean? Is it yield of a particular alloy ... or any alloying? When the yield is less than 100%, and especially when the yield is very low, what are the other materials present?

Yield is simply percentage of powder recovered after milling. Some of the material sticks to the walls of the mill or to the grinding media. Dr. Sapru indicated that these fractions are recoverable. *Aside from the efficiency/cost considerations of low yields, there is the additional R&D concern that testing done on low yield fractions are not representative of the system as a whole.*

7. When grinding is done with a lubricant, how is it proposed to separate the lubricant from the alloy?

Lubricants used are graphitic carbon and/or heptane. Heptane evaporates during processing, while the carbon becomes part of the alloy. It is also believed that the carbon acts as a catalyst and a kinetic aid for the hydriding/dehydriding cycle.

8. How does a large number of catalytic hydriding sites lead to a high tolerance against surface poisoning?

Dr. Sapru states that sites due to such phenomena as dangling bonds, unfilled orbitals, and surface dislocations act as catalytic sites. As more sites are available, losing a few (i.e., poisoning) does not significantly reduce the material’s activity.

9. Did you ever look at a dispersant to reduce agglomeration of fines?

Heptane (see Question 7, above) acts as a dispersant and reduces agglomeration. However, its use requires that the materials undergo a longer grinding time.

It may be advisable to investigate the use of dispersants to increase yields, that is, getting the materials off the mill walls.

10. Would you expect that a high grinding speed at a shorter time is more efficient from a power consumption point of view as well as a time saver, or doesn’t it matter?

Dr. Sapru pointed out that mechanical alloying is basically a low cost process. With the R&D batch mixes, time and speed are basically interchangeable. ECD believes that in a practical process, the higher speed/shorter time scenario would lead to a more economic process, but efficiency evaluations have not yet been performed on this aspect.

ECD is not yet sure what the process will be, but they do not believe that scale-up will be difficult, and they feel that if they get good yields, the process will not be expensive.

Hydriding and De-hydriding:

11. What do you project as the “ultimate” hydrogen concentration you could achieve at temperatures compatible with PEM fuel cells?

For the magnesium system, MgH_2 is 7.8% theoretically. Dr. Sapru stated that a Mg based alloy operating at less than 100°C would have a capacity of no more than half that (3.8%). *Based on the overall conversation, 3.8% would seem optimistic.*

The theoretical maximum weight percent for a transition metal based system, say VH_2 , is a little under 4 percent. The concept of high weight percent at low temperature with a transition metal is a “new problem” for ECD. They have never worked in the direction of high weight percentage before. They want to increase state-of-the-art transition metal systems from 1% to 2% in the short term, and think that they can get to close to 3% eventually.

12. Your papers at the NHA meeting spoke of using hydrogen as a heat source to dehydride your storage materials. I don’t recall any reference to this either during the annual review or during the World Hydrogen Energy Congress. Are you still considering this as an option?

That particular work was not DOE funded, but was done under a now completed SBIR supported by DARPA. That work involved the construction of a laboratory prototype metal hydride hydrogen storage unit. Dr. Sapru indicated that she would not be opposed to receiving DOE funding to optimize this prototype.

13. I have heard/read at various times that melt spinning produces a more homogeneous material that increases the level of hydriding. However, I also heard that hydriding is improved by disorders in the matrix. Please explain.

The homogeneity is on a more macroscopic level. It does not effect the matrix disordering level. ECD has not done a great deal of melt spinning trials. They have found, however, that rapid quenching (based on wheel speed) leads to a highly disordered system. The limited use of the melt spinner is due to the fact that it is the property of their battery people, and there is concern about poisoning the equipment.

14. Do the same alloy/particle properties that favorably effect desorption kinetics also favorably effect hydriding rate?

The activation energies are the same in both directions, and the rates are mutually effected the same way by material parameter changes.

I am surprised that this would be the case universally, unless diffusion rate were the rate determining step, which Dr. Sapru says is not the case.

IV Tours:

Tour of Hydrogen Storage Technologies Area:

ECD's mechanical alloying studies are performed in attritor mills, using twenty-gram samples for research. They generally mill in an argon atmosphere, although they have also looked at 5% hydrogen in argon. They classify the ground material using sieves in a glove box, and then use the -325 mesh (<45 micron) material for hydriding tests.

While the "conventional" Mg systems are made by the mechanical alloying method, the non-magnesium transition metal systems are generally made by induction melting. Processing is done with a 15 kW induction heating system, with the materials in graphite crucibles.

I was also briefly shown a system in which transition metal mixtures are subjected to plasma discharge, producing particles that are under 100 nm via gas-phase condensation. Dr. Sapru is quite excited about this material, which can lead to much more favorable kinetics. (I'm not sure that it would lead to any increased loading; probably not. Perhaps with the Mg systems, it may make lower temperatures more practical, however.)

Testing of metal alloys and metal hydrides include kinetic measurements and pressure-composition-temperature (PCT) measurements. Testing is performed on 1-2 gram samples. Typically, a magnesium-based sample is heated to 300°C, and then soaked in 500 psi hydrogen for two hours before the pressure is relieved. The pressure is cycled four times before any measurements are taken. The reason for this is that the first couple of hydriding cycles results in an overall decrease in the particle size of the alloy, resulting in a change (improvement) of kinetic properties.

Tour of Other ECD Areas:

The tour of the United Solar facility consisted primarily of a showcasing of their PV panel production PDU. This unit produces triple-junction amorphous silica PV panels that will produce in excess of 2 volts, making them capable of splitting water. The nine layers (pin,pin,pin) of this material, some less than a micron thick, are formed by plasma arc-induced chemical vapor deposition upon the substrate. This is accomplished by robotically-controlled operations forming the various layers at different stations. (Very impressive!) The unit runs continuously, producing one-half mile long rolls of PV panel. Five MW of panel can be produced annually. ECD estimates that when scaled to an annual production of 75 MW, the cost for these panels will be under \$1/watt.

At the Ovonic NMH development facility, I was walked through the process of making NMH batteries. An ingot consisting of an alloy of nickel, vanadium, titanium, zirconium and chromium is produced in the furnace, and is then broken into fine powder by using

hydrogen to embrittle the material. It is then melted into the substrate to form a negative electrode plate. The positive electrode plate is made of nickel foam with a paste of nickel hydroxide and other materials painted on. The plates are alternated with foam separators between them, and inserted into a metal can.

Similar processes are carried out on a larger, partially automated scale at the GM Ovonic facility. Overall, 800,000 linear feet of electrode material per month are made by this and other GM Ovonic plants.

ECD also has quite extensive analytical capabilities, and runs these as a separate section within the organization. Since much of their work involves surface conditions of their materials, one of their most important analytical tools is a system that provides thin film surface analysis. It is a four-function system that incorporates Auger Spectroscopy, Electron Spectroscopy for Chemical Analysis (ESCA), Auger Sputtering, and Secondary Ion Mass Spectroscopy (SIMS). With these techniques, surface thickness, composition, and impurity identification and depth can be determined.

Among its other analytical equipment (not including the tools discussed in the tour of the hydrogen storage area) are a scanning electron microscope, and an inductive coupled plasma spectrometer. The latter system is used to obtain detailed composition measurements of metal alloys, down to the parts per billion range in cases. The ingot is dissolved in acid, diluted, and subjected to plasma discharge, to obtain emission spectra.

As mentioned above, ECD also has an “information” division, but this area was not toured.

Technical Evaluation Report
Project: Hydrogen Storage Development
Company: Sandia National Laboratories, Livermore, CA
P.I.: Dr. George Thomas
Date of Visit: September 17, 1998
Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

Sandia National Laboratories (SNL) in Livermore, CA is probably the premiere metal hydride laboratory for the DOE Hydrogen Program. The expertise of **Dr. George Thomas** and his staff, the extensive diagnostic equipment resource, and the tie-in with the combustion and systems side of the house (led by **Dr. Jay Keller**) presents a formidable package for the Program. Dr. Thomas is leading a hydride storage effort that covers development and evaluation of metal hydride materials, development of hydride container systems (hydride beds), and integration of hydride storage into systems. The metal hydride materials effort has primarily been based on magnesium systems, but has recently grown to include alanates (materials of the form $X(AlH_4)_y$) and similar systems. A series of six modular hydride beds have been produced. They were originally intended for use on the Palm Desert vehicles, but when those plans changed, they remained at SNL, and are awaiting a home. In the systems integration area, SNL leans on systems engineering as a means to make hydrides an integral part of a process. Thus, hydride materials, beds and operating labor are all part of an equation. SNL is also heavily involved in the coordination of the Remote Application Power Program (RAPP).

The work being performed by Dr. Thomas' group is mainstream to the program. Key strengths include Dr. Thomas' overall knowledge of hydride chemistry, the vertical nature of the SNL approach (hydride materials, hydride beds, systems), the interaction of Dr. Thomas with Dr. Keller, and the understanding of what the limits are with a hydride system.

It appears to me that Dr. Thomas, similarly to the group at ECD, has basically written off magnesium systems for wide scope usage. It appears that the combination of low temperature and high energy density will not be reachable with these systems.

The collaboration with Craig Jensen in Hawaii on alanate systems likely will (and should) take up a large part of the SNL research effort. While some magnesium work will continue, it likely will be strongly geared toward applications. Dr. Thomas states that there is much to be done with storage systems rather than hydride chemistry.

II Introduction and Background:

On the above date, I visited Dr. Thomas at his laboratory at SNL. The purpose of the meeting was, as usual to gather information through discussions and a tour, that would help in my assessment of the technology in question. In addition, given Dr. Thomas'

overall expertise in storage technologies, a discussion on the overall package of hydrogen storage activities was held. **Steve Guthrie**, who is on Dr. Thomas' team, and Jay Keller who acts as Program Manager for the SNL hydrogen work, and who also leads SNL's remote power and combustion efforts in hydrogen, were also present for large fractions of the day.

During the day, we primarily discussed the magnesium hydride systems, the collaboration with the University of Hawaii on the relatively new alanate storage systems, and the status of the hydride bed modules that SNL constructed earlier. We also spent some time discussing SNL's role in RAPP. I also was given a tour of many of the facilities of the Materials and Engineering Science Center, focusing primarily on surface analytical capabilities. Finally, I was able to pulse Dr. Thomas on his opinion of various storage technologies and the associated ongoing projects.

Dr. Thomas' laboratory was exceedingly active on the day of my visit. Representatives from Plug Power and the University of Alaska, Fairbanks were present, setting up for some quick-turn-around reformer/fuel cell assembly and testing that needed to be completed by the end of the fiscal year as part of RAPP.

III Discussion:

Magnesium-based Systems:

Dr. Thomas' team have been working on magnesium based hydride storage systems for the past several years. Dr. Thomas feels at this time that these type of systems will probably not exceed about 3.5% by weight hydrogen (material weight) at any temperature approaching PEM applicability. Maybe 120°C can be achieved at this weight percentage. For this reason, the SNL team is quite excited about their relatively new undertaking in conjunction with Craig Jensen's laboratory at U Hawaii on alanates and related substances.

As to the magnesium systems themselves, Dr. Thomas is specifically addressing Mg/Zn/Al systems. He is using a new ball mill/melt process to get higher plateau pressures. You need a higher pressure at a particular temperature. Dr. Thomas' goal is to be able to produce the so-called "R" phase of the Mg/Zn/Al system with consistency. The R phase has a higher hydrogen capacity than the alternative configurations.

Aluminum-based (and Analogous) Systems:

Alanates [*a rather strange name in my opinion; it implies the presence of oxygen*] and similar compounds provide an opportunity for reasonably high hydrogen loading. The base compound, NaAlH₄, contains 7.4% hydrogen by weight; the analog LiAlH₄, contains 9.8% hydrogen. The collaboration with Jensen's group originated with the finding by Bogdanovic that alanates can be hydrided reversibly in the presence of appropriate catalysts:

“X” can be Na, Li, Mg or Zr. Zirconium particularly may be interesting as the reaction may occur at or near room temperature. Dr. Thomas stated that the analogous boronate (using the same type of nomenclature) systems, which would provide the potential for higher hydrogen loadings (boron has an atomic weight of 11 versus 28 for aluminum) are probably not reversible. Depending on the level of use, NaAlH₄ could either be purchased, or produced from Na/Al mixtures in a hydrogen atmosphere. If X were something other than Na, it would probably be difficult to purchase.

Reaction [1] is actually composed of two steps. Using NaAlH₄ as an example:

Reaction [2] might require high pressure to recycle the hydride – perhaps about 1500 psi, but Reaction [3] would appear to lend itself to low pressure low temperature operation.

Current work is focused on determining optimum catalytic systems for the hydriding/dehydriding cycle. These materials do not appear to degrade during recycling. The key to these systems, according to Dr. Thomas, is fabrication and synthesis.

Storage Modules, RAPP, and Other Projects:

SNL is sensitive to “useless demonstrations”. Thus, they are holding on to their six hydride bed modules for the time being. They were, at one time going to be used on the Palm Desert project, but now they believe that other storage systems may have better applicability for Palm Desert. Thus, the modules (or 5 of the 6, at least) are sitting on a test stand in one of the laboratories, waiting for an application. Dr. Thomas mentioned wheelchairs as possibly being appropriate if the right scenario could be found.

Dr. Thomas is sensitive about an apparent misconception as to the speed of filling hydride systems. He mentioned that he believes that DOE has been stating that metal systems are hydrided slowly, making this one of the disadvantages of this type of storage system. The existing modules can be filled in six minutes by adding hydrogen in short bursts and using a cooling line.

As previously mentioned, my visit coincided with a rush of activity concerning SNL’s role in the RAPP Program. As my visit occurred about two weeks before the end of the fiscal year, SNL was busy trying to test/demonstrate operational fuel cells by the end of the month. The plan is for three competitive 3.5-5 kW reformer/ PEM fuel cell systems, probably with hydride storage. The concept being addressed is: home-level distributed power generation, with, perhaps, the reformer built oversized to provide heat as well. The fuel of choice (or more accurately, of necessity) is diesel.

The hydrogen people at SNL are interested in systems. All that they do with hydrides must ultimately lead to making storage devices that are part of an integrated system. Their approach is thus tied strongly to systems engineering analysis. Dr. Thomas believes that it is on storage systems, rather than hydride chemistry, that the work must focus. For instance, successful hydride storage systems must use inexpensive hydride materials, inexpensive hydride bed materials, and low manufacturing costs.

IV Tour:

SNL, as one would expect, has a vast array of analytical tools at their disposal. I was given a tour of some of the facilities within the Materials and Engineering Science Center, focusing on the equipment that is applicable for hydride work. The Center has several scanning and transmission electron microscopes (SEMs and TEMs) including a hot filament SEM, a field emission SEM and a field emission TEM. (Field emission systems produce very high electric fields resulting in high resolution micrographs), and an electron microprobe. The group is thus able to obtain both morphological and elemental compositions. Other techniques used by Dr. Thomas' team includes: Inductively Coupled Plasma Mass Spectrometry (ICP-MS) x-ray tomography, laser ablation and x-ray diffraction (to identify phase).

Standard hydriding tests are performed with a pressure/composition/temperature (PCT) manifold in the hydride R&D lab. Kinetics experiments done on the system tie in with microstructure analysis. Since much of the understanding of hydride systems is surface-oriented, SNL also employs x-ray photoelectron spectroscopy (XPS) and Auger Spectroscopy to characterize the chemistry of the material surfaces for both the hydriding and dehydriding processes.

During the tour, I was also shown and allowed to operate a model remote-controlled car, which was powered by an H-Power provided fuel cell and included hydride storage.

V The Overall Hydrogen Storage Program:

Following the "formal" part of the meeting, Dr. Thomas and I reviewed the overall hydrogen storage component of the DOE hydrogen program. Given the importance of hydrogen storage in the overall program, Dr. Thomas feels first and foremost that there is not nearly enough money being spent to enable the necessary ventures into new research. The program, however, needs to ensure that the projects being supported are enabling technologies. Specifically, Dr. Thomas feels that there is not enough being done in the area of non-vehicular storage. The increase in prominence of distributed utilities make them a good candidate for stationary hydride storage systems.

There is a key need to lower the costs of metal hydride systems. Currently, the "AB" hydride systems (e.g., Mg_2Ni) cost about \$20/kg. This needs to be lowered to the \$5/kg range.

One interesting comment made by Dr. Thomas is that he does not consider projects where hydrides are reacted with water such as the Thermo Power Corp (TPC) process to be a storage process because the hydriding is not reversible. He believes it should be moved to the production side. *This is not a trivial argument, since the Program weighs production dollars vs. storage dollars. I agree that the TPC project does not represent classical, reversible hydride technology. However, it includes (if successful) a remote regeneration process. More important is the fact that its purpose is to provide an on-board source of hydrogen. It provides a material on-board that undergoes a chemical reaction to ultimately power a vehicle. In this manner, it is much like a tank of gasoline. Thus, I believe that the storage section is appropriate for the TPC project.*

Technical Evaluation Report

Project: Biomass-to-Hydrogen

Company: National Renewable Energy Laboratory (NREL), Golden, CO

P.I.: Dr. Esteban Chornet

Date of Visit: December 22-23, 1998

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

NREL is developing a process in which they are looking to convert biomass waste into hydrogen by means (usually) of a two step process. In the first step, the waste is converted into one or more products by means of a fast pyrolysis reaction. This product, a "pyrolysis oil," can then be separated using water, into an aqueous and non-aqueous fraction. In the second step, the aqueous fraction (or possibly the whole pyrolysis oil) is subjected to steam reforming to produce hydrogen. The potential success of the project is tied heavily to both technical and economic issues, in a fairly complex and feedstock-sensitive manner. An important part of the project is the plan to offset process and feedstock costs by making a salable co-product of the non-aqueous, or pyrolytic lignin, fraction. To date, the co-product of choice has been an adhesive that could take the place of a phenolic resin used to join layers of plywood or particleboard. They are also investigating fuel additives as co-products. The major technical challenges at this time are the charring that occurs during the reforming process, causing fouling of the catalyst, and issues dealing with the robustness of the system to differing feedstock.

Exhibit 1 shows a schematic of the overall fast pyrolysis/reforming process.

Project Strengths:

The major strengths (and potential weaknesses) of the project all lie in the robustness of the concept and the systems. The project has been thought out in much detail, and is strong in chemistry, engineering and economic analysis. The researchers have a mind toward multiple products, usage of multiple waste materials, and both niche and large markets. The project has a real conservation, "use everything" ring to it. Even the char that is formed during the fast pyrolysis step is combusted to provide heat for the reactor.

One key strength may be the concept of being able to transport liquid, pumpable, pyrolysis oils, the intermediate product, rather than biomass or hydrogen. This is likely the least expensive way to go, lacking a hydrogen infrastructure.

Unlike some other projects, this one is approaching the coking problem during the second step, in what I believe to be the correct manner – a fluid-bed catalyst system.

Issues that should be Addressed:

A potential drawback is that there is so much going on, so many potential feeds, products, and co-products, that it would be easy to lose sight of the fact that this is a hydrogen project. There are many scenarios under which this project can become a real winner: inexpensive or free feedstock to the pyrolysis system, co-products that will reduce the cost of hydrogen to a competitive level, inexpensive or free feeds to the reformer system, small localized pyrolysis reactors, etc. All of these scenarios, however, have a sub-scenario where hydrogen production becomes unneeded or unwanted. I do not believe that this is happening, but it is something for which we should keep our eyes open. For instance, a focus on a lucrative pyrolysis co-product could lead to the wrong optimization parameters for hydrogen. In another example, the scenario discussed below in which the aqueous fraction or the whole oil is reformed at a refinery in conjunction with natural gas or naphtha does not lead to hydrogen as an energy carrier.

In all, (the potential for the project to veer to a non-Program goal aside) this is, in my opinion, one of the strongest projects in the Program, with the greatest potential for inexpensive, renewable hydrogen.

II Introduction and Background:

On the above dates, I visited **Dr. Esteban Chornet** and **Dr. Stefan Czernik** at their laboratory in the Field Test Laboratory Building (FTLB) at NREL. On the afternoon of December 22, Dr. Czernik gave me a tour of the fast pyrolysis and reformer facilities. Dr. Czernik and I also spent some time with **Maggie Mann**, discussing the life-cycle aspects of some of my questions. On the morning of December 23, I met with both Dr. Chornet and Dr. Czernik, and we discussed the project in detail. I had previously sent Dr. Chornet a list of questions to be discussed during our meeting, and these formed the basis for much of our discussion.

The NREL project by which fast pyrolysis is used to turn biomass into materials that can be processed has been around in one form or another since the early '80s. The goal was to make liquid hydrocarbons. This particular project, to make hydrogen, started in 1994.

The objective of this project is to use fast pyrolysis as a means to convert various biomass waste materials into handleable oils (as opposed to tars) and to reform some of these oils into hydrogen. In order to help offset the cost of hydrogen, other pyrolysis products are tailored to be sold in other markets.

III Tour:

Dr. Czernik walked me through the entire pyrolysis/reforming setup. The fast pyrolysis system occupies much of a large multi-leveled laboratory [I would really call it a Process Development Unit (PDU)] within the FTLB. It is a multifunctional system, used for some gasification studies (with a different reactor) as well as the present work. The fixed- and

fluid-bed reforming systems are located in an area on the upper level of the laboratory. These systems are considerably smaller.

Fast Pyrolysis Process:

The fast pyrolysis reaction occurs by means of an ablative process in a vortex reactor. The cylindrical, stainless steel reactor is 26 cm in diameter, and is capable of a heating rate of about 2000°C/sec. The feedstock, generally 2-5 mm in diameter, is dry, but possibly containing up to about 10% moisture, is introduced tangentially. Either steam or nitrogen is used as the carrier gas, which is preheated. The residence time for one pass through the reactor is about 0.5-0.8 seconds. The temperature at the reactor walls is nominally 650°C, while the gases in the center are about 500°C. The particles do not totally react with one pass-through but are recycled some 10-20 times through the reactor. Unreacted particles are separated from product gases by centrifugal force for recycling. Byproduct char will eventually fall out of the reactor along with the product gases. The products contain about 10-15% by weight char (note that it is a char and not a pure carbon), which is then separated from the product using two cyclones and a baghouse, the latter for small (< 5 micron particles). The baghouse is held at 400-420°C. This provides for a balance between purity and yield; at a higher temperature, they would get a lower yield. As it is, they probably lose about 10% of product for the sake of purity. The pyrolysis system can operate in this manner for about 9-10 hours before the baghouse becomes clogged, if periodic back-flushes are used to clean the flexible ceramic or sintered baghouse filter.

The product gases then go to a condensation train. Two scrubbers and coalescing filters are used to collect the product. Scrubbing is a difficult process, probably due to the aerosol nature of the product.

The overall pyrolysis system can also be run in a gasification mode. In that case, a second Inconel reactor is used, and the reactor temperature is nominally 800°C. This is not part of the current project, but shows the versatility of the system.

Reforming Process:

The feed for the reformer can be either the aqueous fraction of the pyrolysis product, or the entire pyrolysis oil. Alternately, the group is looking at feeds from other sources – primarily waste streams that would provide an economic benefit.

The initial reformer reactor for this project (still set up) utilized a fixed-bed configuration. The reactor used generally standard nickel catalysts in packed tubes. Superheated steam (600°C) and the biomass feed was introduced co-currently. The furnace area itself was three-zoned; the top (inlet) zone had a temperature of no less than 600°C, the middle zone 750°C, and the bottom zone 700°C, but the temperatures could be varied. Shifting as well as reforming took place in the reactor, but the system was not efficient for converting all the CO to CO₂.

The fixed-bed reactor worked well for model compounds, but was less successful for actual pyrolysis oils. When the oils were vaporized (to allow better contact with the catalyst bed) to feed into the reactor, they tended to form a char material especially in the pre-catalyst portion of the tube furnace, where it would clog the reactor. The char could be removed by reaction with CO, but the regeneration cycle was unacceptably long. Feeding the pyrolysis oil as a fine mist reduced the charring problem, but made the oil/catalyst contact less efficient.

The group therefore has recently moved to a fluid-bed reactor. Again, there is a three-zone furnace around the Inconel reactor, but the catalyst particles have to be ground (300-500 microns) in order to be mobile. Superheated steam is used as the fluidizing gas. The reactor can be operated up to 800°C. The feed is sprayed into the fluid bed in liquid form through a 0.2 mm nozzle immersed in the bed. The system products are hydrogen, CO, CO₂, and a few ppm of methane. As the catalyst deactivates, methane concentration increases to, perhaps, 0.01%. The system is all computer-monitored, and the product gas is analyzed every five minutes. One problem with the current configuration is that some of the catalyst fines winds up in the steam condensate system.

Presently, about 90% of the carbon goes to product, with the remainder ending up as coke on the catalyst. Overall, a 95% mass balance closure is being achieved.

IV Initial Discussion:

The success of the project on a large scale is tied to the diversity of feedstocks that can be used and the cost to acquire and use these feedstocks. To date, much of the work has involved either model compounds or poplar. Currently, the group is beginning to investigate peanut shells (from a collaborator in Georgia, consisting of a municipality and a utility), southern pine, and bagasse (sugar cane stems), as inexpensive – or free – feedstock. They have estimated that the cost of hydrogen from feedstock such as these, with the assumption that the feedstock is free, is \$7-12 /GJ hydrogen. This does not include any revenue that might be generated from a co-product. They want to be more than niche market suppliers.

The co-product is made by the addition of water. (A higher quality material can be made by using ethyl acetate extraction rather than water, but this would be more expensive). This creates an aqueous fraction, which is reformed to make hydrogen, and a non-aqueous fraction that can be tailored to be a substitute for a phenolic adhesive that is used to bind plywood or particle board. If this adhesive material is mixed 50/50 with a real phenolic adhesive, there is no decrease in physical properties for bonding plywood or particleboard. No long term repeatability or aging data is available yet. Maggie Mann estimates that this “biophenol” would cost about half as much as phenol. This would lower the net cost of hydrogen to about \$5/GJ. There is one major drawback to this product, however. According to the researchers, people who use it complain about the smell; therefore, industry has lost interest (perhaps only temporarily) in this material. This is part of the reason that the Chornet group is also looking at alternative products –

primarily fuel additives that will boost the octane rating. The group is also receiving funding from the Ethanol Program to investigate this type of gasoline additive.

A strategy being investigated would be to locate the fast pyrolysis system at the feedstock site, and then transport the pyrolysis oil. The reforming step would be performed at either the hydrogen use site, or where a hydrogen infrastructure existed. This would be a less expensive alternative to having to transport either biomass feedstock or hydrogen – at least without a hydrogen infrastructure. Dr. Czernik pointed out that this type of strategy is not an option for a biomass gasification project where either feedstock or hydrogen would have to be shipped.

Dr. Chornet envisions a scenario where fast pyrolysis could be performed in a local region, like, for instance, an agricultural community. Such a community could buy a fast pyrolysis system to process their communal agricultural waste, and sell the pyrolysis oils.

Fast pyrolysis is a low-dollar investment technology. If you have a co-product, the cost decreases even more. If you team with a refinery to reform the aqueous fraction, the infrastructure already exists.

The Chornet group is expecting to announce an agreement on fast pyrolysis of peanut shells with the aforementioned Georgia group, sometime within the next few months. Since Georgia also has a plywood industry, this may be an especially good match. At this point, however, no names are being disclosed.

Although the vortex reactor works well at the size (PDU?) being used at NREL, it may not scale well. A circulating or bubbling fluid bed may be needed for commercial fast pyrolysis units.

Another issue is the effect of the biomass on the nickel catalyst. Since the biomass material contains considerable oxygen, it can attack the nickel catalyst, forming nickel oxide. Dr. Chornet's group is trying to work with ICI and with United Catalysts to develop a new catalyst that would be more suited to the oxygen-containing biomass.

V Questions and Answers:

A major part of our discussion centered on the questions that I had sent to Dr. Chornet prior to our meeting.

- 1. Have there been any attempts at non-oxidative methods of removing coke materials after fast pyrolysis, and thus reduce/eliminate CO₂ emissions during this step? Alternately, have there been any attempts to alter the system configuration to limit coking of the catalyst in the first place?**

The fast pyrolysis process does not produce a coke; it produces a char. This is considerably more oxygenated than coke. There is no attempt to remove the char at all during fast pyrolysis. It is an integral part of the balanced system. The char is burned to

provide some of the heat for the pyrolysis process. In fact, the process is tailored to produce the right amount of char.

2. How are the biomass feedstocks to the pyrolysis process prepared for handling?

You need a fairly dry material as a feed; you don't want to use the fast pyrolysis system as a drier. Ideally, the feed will be 10-15% water. You could use char combustion as a means of drying the feedstock. You would have to balance the need of drying with the need of char combustion to provide heat for the fast pyrolysis. Alternately, an agricultural commercial drier could be used. The feedstock is then ground or milled. In the case of lightweight materials, such as peanut shells, it may be advantageous to pelletize the particles as well. You generally want about 2 mm particles.

3. What is the chemical composition of the coke that is evolved during the pyrolysis and reforming process? Is it close to pure carbon for any natural feedstocks?

The fast pyrolysis char contains 15-20% oxygen, 1-2% hydrogen, about 10% "ash", and the rest carbon. Dr. Chornet indicated that some of the ash might be amorphous silica, which may be salable to the semiconductor or tire industries.

The material formed during reforming, is indeed coke. It is nearly all carbon, and creates a problem for the catalyst.

4. Are the pyrolysis oils generally handleable and pumpable at room temperature, or do they have to be heated?

The oils have viscosities of about 50-100 cps at room temperature; the pour point is below the freezing point of water. The pyrolysis oils are pumpable and easily handleable.

5. How does the reforming process compare to conventional (refinery-based) steam methane reforming or catalytic naphtha reforming? What reforming temperatures are used? Do the processes involve conventional shift and purification steps?

The process is very similar to conventional reforming methods. In fact, one concept was that the process could actually be performed in the refinery one day, perhaps co-reforming the pyrolysis oil with natural gas or naphtha. The group's goals include compatibility with present industry and infrastructure.

Here is one example of where the project's goals could be incompatible with that of the Hydrogen Program.

6. You showed a Figure in your 1998 annual review paper that indicated that the aqueous bio-oil fraction is either directly steam reformed, or goes through a "thermal depolymerization and/or stabilization" step prior to steam reforming. What is the advantage of the additional step?

The pulp and paper industry has a refuse stream that is similar to the aqueous fraction of pyrolysis oils, and may be a good candidate for reforming. However, it is quite polymeric. The reformer handles monomers easier than polymers. Thus, the thermal depolymerization may be needed to utilize this type of material. The aqueous fraction of the “standard” pyrolysis oil produced by fast pyrolysis has little polymeric content.

7. During the reforming process, how does coking vary with the different partial or whole oil feedstocks?

If there is no aqueous separation step, meaning that the whole oil is reformed, there is a higher tendency to coke. This is due to the higher oligomeric content of the whole oil. The hemicellulose (non-aqueous) fraction is highly oligomeric.

The need to remove coke from the reforming system was recognized as a problem early in the project. One of the first things that was done was to demonstrate the ability to regenerate the catalyst by removing coke with steam or CO.

This is admittedly a tedious process, and should not be the final answer. It does appear that it will be the final answer, as the rate of catalyst contamination should decrease dramatically with the use of the fluid-bed catalyst system.

8. Have there been any attempts to tailor a process for minimal CO₂ emissions (resulting in net negative CO₂ when including the growing of the biomass)?

In order to best consider CO₂ emissions, one must look at the entire life of the carbon materials – a life cycle analysis (LCA). The net CO₂ emissions are near zero. The only time that the net CO₂ becomes negative is when the carbon can be tied up in a non-combustion mode. For instance, if a co-product is made from the fast pyrolysis process, and that product is the adhesive material, the carbon is tied up. This scenario would result in a net-negative CO₂. If the co-product is a fuel additive, the carbon is soon combusted. The only other source of non CO₂ carbon as determined by LCA is what is sequestered in the soil during the biomass growing period.

Basically, the amount of overall CO₂ emissions is not sensitive to starting material.

9. What are the net overall CO₂ emissions in the “standard” pyrolysis/reforming process?

As stated above, negative net CO₂ emissions are realized if the co-product is used in a non-combustion mode. Barring this, the net result is a slight positive CO₂ emission.

The reformer system in a commercial process would use pressure swing adsorption (PSA) to separate the hydrogen and concentrate the CO₂. As with any other system, concentrated CO₂ is superior to combustion-formed diffuse CO₂ for sequestration or for possible use. [Dr. Chornet also mentioned the potential to use CO₂ with ammonia to

make urea for fertilizer. Urea is $(\text{NH}_2)_2\text{CO}$.]

The low net CO₂ emissions is a strong positive attribute of the process.

10. Are there any results yet available for the reforming of whole pyrolysis oils with a fluidized bed configuration?

There are now some recent results. Charts are attached for a reforming run that was performed on a whole bio-oil using a steam to carbon (S/C) molar ratio of 1.6. The hydrogen yield compared to the stoichiometric yield (Exhibit 2), and overall gas composition (Exhibit 3) are shown. Hydrogen yield can be seen to be dropping off from a maximum of a little under 80% after about one hour. In this case, regeneration of the catalyst was not included. About 10% coke was obtained, and the drop-off was attributed to this. In addition, the S/C is not ideal; it should be higher – perhaps 3 to 5. Dr. Chornet believes that under these conditions, the drop off should not occur until, say, 50 hours.

As a first run, the results are not bad, although I am not sure as to why they used such a low S/C to begin with. I'll be interested to see what they get when they improve the ratio.

11. How do the costs of using purchased pyrolysis oils compare with those of pyrolyzing biomass, and using these oils?

When doing an economic analysis on a “bought oil”, Maggie Mann uses a price of \$80/ton. Information that Dr. Chornet received from a Canadian company indicates that pyrolysis oil will be available for something between \$70 and \$200/ton, but the product is not yet marketable.

The assumed cost for a dry feedstock is \$40/ton. At an energy density of 16 GJ/ton, this works out to \$2.50/GJ – about the same as natural gas. Even if the feedstock is free, you have to transport it – maybe \$20/ton. That is why the co-product concept is important, as is the need for an environmental driver.

This shows why the concept of localized fast pyrolysis and shipment of a liquid intermediate is attractive.

12. Have you looked at all at the feasibility of using waste biomass as a feedstock?

Sludges are not good feedstocks for this kind of process. They generally contain too much moisture (75-80%) and are too expensive to dry, unless a special case exists where waste heat can be used. Forest wastes (i.e., sawdust, etc.) containing 50-60% water may be able to be dried economically.

Exhibit 1 Hydrogen from Biomass Schematic

Exhibit 2. Hydrogen Yield from Bio-oil Reforming

Exhibit 3. Overall Gas Composition from Bio-oil Reforming

Technical Evaluation Report

Project: Membrane Separation Technology

Company: Savannah River Technology Center, Aiken, SC

P.I.: Dr. Myung Lee

Date of Visit: March 23, 1999.

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The membrane separation project being carried out at the Savannah River Technology Center (SRTC) is headed by **Dr. Myung Lee**. The project basically involves the development of a sol-gel processed glass that has a tailored porosity that will selectively pass hydrogen. The material, applied by a dipping and drying process, appears as a two-micron thick coating either on a porous inert substrate such as Vycore, or on a reactive metal hydride. The fact that two quite different systems (with very different separation mechanisms) are being studied with the two different substrates is not extremely clear from Dr. Lee's various reports and submittals. Regardless of the substrate, however, the properties of the coating have been the focus of much of the project to date. The goal is a coating with a very narrow pore-size distribution, with an average measurable pore diameter of about 40 Angstroms.

Over the past couple of years, Dr. Lee and his group have examined sol-gel materials, mixing methods, and drying times and temperatures in order to optimize coating properties. They have demonstrated that they can selectively collect hydrogen through the membrane, and have measured some take-up rates as a function of pressure.

What has not been done yet is to create a robust system that can be recycled repeatedly – except if a metal hydride substrate is used (more on this later.) They do not yet have hydrogen collection efficiencies and purities measured as a function of their input parameters. Consequently, they do not have material and energy balances for their system(s), nor are there any rough cost estimates available.

Project Strengths:

- The addition of membrane separation technology to the portfolio of available hydrogen technologies is important in that it provides the potential for less expensive and more efficient recovery of high purity hydrogen compared to pressure swing adsorption. It specifically provides a better system for removal of CO from hydrogen, decreasing the likelihood of fuel cell catalyst poisoning. Although a few years ago, several laboratories were slated to begin R&D on various metal or ceramic membranes for hydrogen separation, all but the SRTC project was cancelled. The Hydrogen Program currently funds only the SRTC project as a separation technique.
- The concept and methodology of this project is credible, once one can dig down and determine what it actually is.

Issues that should be Addressed:

- The amount of progress made so far is not great. The accumulated data to date is heavily weighed toward pore size distribution. There is little in the way of hydrogen take-up data, and nothing in the way of hydrogen purity and recovery percentage.
- This project should begin to generate “practical” data. Their metal hydride system is ready for this now. (They have built a bench-scale reactor that has the versatility to provide rate, purity, and efficiency data for both types of membranes.)
- Getting 1 or 2 more membrane projects in the portfolio would be beneficial.

II Introduction and Background:

I visited Dr. Myung Lee at SRTC to discuss his project involving the development of membrane systems that selectively filter hydrogen. His project is one of several under the SRTC hydrogen umbrella, which is more or less spearheaded by the SRTC tritium work, mostly funded by DOD. Among the DOE/EE funded projects, Dr. Lee lists only his own project and the Westinghouse Bus Project.

III Tour:

I was given a tour of the three laboratories in which Dr. Lee prepares his membranes, dries them, and tests them for hydrogen permeability.

The key element of Dr. Lee's membrane is a polymeric ringed silica material having alternating silicon and oxygen atoms, with the average ring containing 6-7 silicon atoms. In a typical mix, Dr. Lee combines a solution of tetraethylorthosilicate (TEOS) in ethanol with a separate water-ethanol mixture that has been adjusted to a pH of 1.6 by hydrochloric acid addition. The proton provided by the acid prevents premature agglomeration of the polymer.

As the mixture just begins to form a gel, the substrate is dipped into it and allowed to partially dry about four times. This results in a two micron-thick coating. The coating is allowed to dry under ambient conditions for about two days, and then subjected to oven drying at various temperatures. Dr. Lee stated the drying temperature as being 200-600°C. The ambient, slow dry tends to narrow the pore size distribution, while the high temperature finish removes the large pore size “tail” from the distribution. The finishing temperature range is very wide. I was not able to get a good answer from Dr. Lee as to why this range has not been narrowed as yet. Recently, Dr. Lee has recently begun testing the effect of microwave drying as opposed to oven drying. No conclusions have yet been made from this – it's very new.

There are two different systems being developed here. The sol-gel material is coated on the substrate. The first involves a passive substrate such as Vycore (a porous silica-glass),

or a stainless steel frit. In this case, hydrogen would pass through the sol-gel and the substrate to a collection point, while other gases would not pass through the sol-gel coating and be pumped away. The second case involves a metal hydride substrate such as LaNi (V), the current material of choice. Here, again the hydrogen selectively passes the sol-gel coating, but it reacts with the substrate forming a metal hydride. Other gases do not pass through the coating and are pumped away. The hydrogen is later recovered by a pressure/temperature operation. SRTC is currently using the composite metal $\text{LaNi}_{4.7}\text{Al}_{0.3}$ because it “is available”. It will typically store about one percent by weight hydrogen. Dr. Lee offered that the identity of the metal could be changed if desired, to accommodate some of the higher temperature, higher storage capacity hydrides.

One advantage of the metal hydride substrate is its self-sealing ability. If a defect (i.e., large pore) occurs in the sol-gel coating at a particular site, allowing CO passage. The reaction of the CO with the metal poisons and seals that site. Thus, the coating localizes and minimizes metal hydride contamination. Dr. Lee states that mixtures with as much as 10% CO have been used without contaminating the hydride. In addition, the coating extends the cycling life of the membrane, preventing breakdown due to contamination. On the other hand, a large pore defect (i.e., hole) present with a passive substrate renders the membrane ineffective.

Dr. Lee has built a bench scale reactor system that will handle both the passive (Vycore) and active (metal hydride) substrate systems. He provided me with a schematic of the system, a copy of which is attached as Exhibit 2.

There is nothing special or unique about the reactor design. It appears to be a reasonable system with which to gather hydrogen separation effectiveness and efficiencies. Hopefully, SRTC will start to collect meaningful hydrogen data.

IV Questions and Answers:

Prior to my visit, I sent Dr. Lee a series of discussion questions. These questions and answers are included in the general discussion below, in the appropriate section.

1. What is the desired pore size distribution? How do pore size results vary with temperature?

One cannot measure pore sizes any smaller than about 15 Angstroms, while hydrogen separates from other small gas molecules (e.g., CO) at about 3-4 Angstroms. Dr. Lee believes that the pores have “bottlenecks” within their structure. Measurable 20 Angstrom pores, he believes will contain the 3-4 Angstrom bottlenecks through which hydrogen will pass, but CO will not. *This is somewhat roundabout, and not conclusive in itself, but Dr. Lee has shown correlations between 20-Angstrom average pore size and selective hydrogen take-up.*

Dr. Lee believes that pore size distribution should be narrow. This can generally be accomplished by a slow room temperature dry, followed by the 200-600°C bake.

2. How is the pore size measured? How reproducible is the pore size distribution?

Pore sizes in the gel are measured using the B.E.T. (Bruner, Emmett, Teller) adsorption method. Dr. Lee has much data showing pore size as a function of mixture parameters. Data show very good reproducibility for a given mix.

3. Does the evaporation process effect pore size?

Yes, as does the drying time and temperature. Exhibit 1 shows the effect of drying temperature on pore size distribution.

4. How is the thin layer thickness controlled? How uniform is it? How reproducible is it?

Thickness is controlled by the number of times the substrate is dipped in the gelling material. Four dips produce a two-micron coating. Uniformity is often a function of the uniformity of the substrate. *In other words, uniformity and reproducibility is somewhat limited. The correlation between performance and thickness properties is unknown.*

5. Metal hydrides are generally a long term storage medium for hydrogen. What is the role they will play in the separation process? If they are actually capturing hydrogen, it seems that a complex temperature/pressure cycle would be needed to keep the purification going on a continuous basis. – or is it a batch process?

The use of a passive (e.g., Vycore) substrate would result in a continuous process mode, while the metal hydride process is by nature a batch process. For the latter, Dr. Lee envisions having two membrane systems, one collecting hydrogen in the metal hydride while the other recovers the hydrogen, thus creating a pseudo-continuous process.

The fact that there are two far different types of substrates and two quite different processes is something that should have been revealed long ago. It's probably a communication fault.

Currently, typical runs using the Vycore substrate involves putting hydrogen into a calibrated volume at a fixed pressure and then exposing it to the inside of a Vycore tube which has a sol-gel outer coating. The tube is simply set in a hood and the hydrogen is allowed to pass through the tube walls and vent through the hood. Rate of hydrogen take-up is measured by monitoring the pressure decrease in the calibrated volume.

For the metal hydride substrate, the hydrogen is generally pulled into the metal by a vacuum. Hydrogen can later be reclaimed by heating the system; the hydrogen recovery pressure is a function of temperature at the time of release.

6. Are there any data showing selectivity of the filter to hydrogen? What concentration of CO passes through the filter?

Dr. Lee states that with the metal hydride system, no CO passes through the sol gel coating, and if an imperfection exists, the flaw is quickly sealed, as stated above. A perfect Vycore system is also impervious to CO. However, this system appears to be much less robust. (See next question).

Other than one piece of data that showed that with the best sol-gel (noted as “Mix E” by Dr. Lee), a 90/10 H₂/CO mixture had a “100% hydrogen capacity” no selectivity data is given. In addition, Dr. Lee shows concern that if hydrogen sulfide is present, it may corrupt the system.

I think we can say that no real separation efficiency/effectiveness data exist.

7. Do any recycling data exist? Does any degradation of the system occur?

Dr. Lee’s group has recycled the metal hydride system through “hundreds of cycles” without any apparent degradation of the system. No long term aging data are available, however. The Vycore system is not nearly as robust. After exposure to hydrogen, many membranes begin to grow cracks. Dr. Lee believes that the cracks are forming in the substrate and then propagating into the coating as well. He also thought that moisture might be involved in the process. At any rate, this is a serious problem for the non-metal hydride system, and is one that Dr. Lee is currently concentrating on solving. The Vycore type system is expected to be a much lower cost system than would be the metal hydride system. One thing that Dr. Lee is considering is the use of an alumina substrate instead of Vycore. It is obviously a serious problem.

Although, cracking is a serious problem, hopefully not a great effort will be spent on trying to solve it if this means putting off getting the efficiency/effectiveness data. These data can and should be obtained for the metal hydride system now. They can also work with the Vycore system, getting the data on the first cycle or two, prior to cracking. The material is not expensive, at least at the small scale, and a large number of membranes could be made for this purpose. We need to see if the system is worthwhile to begin with, before we try to fix the cracking problem.

8. In the written report for the 1998 Annual Review, a Figure is presented as indicating flow rate for hydrogen as a function of feed pressure. How does purity compare with the Pd/Ag membrane? What is the hydrogen regeneration rate?

No measures for purity comparisons or hydrogen regeneration rate are available.

9. What is the identity and concentration of metal hydride in the ceramic membrane? How is it dispersed?

My question presents a good example of the communication problem. Dr. Lee’s reports are not clear on the two systems. It appeared from some of his writing that metal hydride particles were dispersed throughout a sol-gel ceramic matrix. As is obvious now, the

metal hydride is a substrate in one of two basic membrane configurations. SRTC has submitted a patent application on the coated metal hydride design.

10. What temperature range do you anticipate using to run the filtration process?

It depends on the process. You could use the membrane on a reformer output, running at 400-500°C, or you could run at room temperature. With a metal hydride system, you could run at room temperature to collect the hydride (remember this is a LaNi system) and then use heat off the reformer to later recover the hydrogen at a high pressure.

11. Your contribution to the 1999 Annual Operating Plan (AOP) shows that you plan to construct a “large filter”. How large? Is it expected that most of the membrane material issues will be settled prior to construction?

SRTC has used 1 cm² and 20 cm² filters for their tests. For scaling up to the “large” filter, they will just use several of the 20 cm² filters. Membrane issues have not been settled for the Vycore system, and will be addressed in parallel.

This is obviously not a production scale filter about which SRTC is talking. It is to be used in the bench scale reactor. Hopefully, good metal hydride membrane data will be developed now, and Vycore membrane data will follow soon thereafter.

12. The AOP also shows a rather ambitious schedule involving the construction and testing of a reactor. What size is this expected to be? Is its construction on schedule?

The reactor in question, is of course, the bench scale system that we have already discussed. It has already been built and vacuum-tested.

13. Do any projected mass/heat balances and system costs exist?

Not yet. They have to get the data first.

VI Additional Discussion:

Dr. Lee has found that if he takes two metal hydride substrates, coats only one of them, and exposes both of them to hydrogen, the coated substrate will adsorb twice as much hydrogen as the uncoated one. (About 2% by weight as opposed to 1%.) The take-up rates are not affected by the coating. Dr. Lee does not understand what is actually occurring here, but thinks that some hydrogen might actually become trapped within the sol-gel coating itself.

Dr. Lee believes that the membrane would be “much less expensive” than pressure swing adsorption (PSA) if the single step (Vycore) membrane is used. If the metal hydride system is used, and a heat source exists off which the membrane could tap, the system would also be cheaper than PSA. If no “piggyback” source exists, the cost would be

about equivalent to PSA. *I do not believe that these statements are based on any real calculations, and are just rough estimates.*

The cost and simplicity of system are the reasons that SRTC is pushing for the single-step membrane. – But they will have to solve the cracking problem.

Dr. Lee is expecting a group from Mississippi Chemical Company to visit his laboratory in the near future. They make ammonia, and are apparently very interested in the SRTC process. *Dr. Lee is quite excited about this prospect, as it represents the first industrial interest in his project.*

Exhibit 1. Effect of Drying Temperature on Pore Size Distribution

Exhibit 2. Bench Scale Reactor System

Technical Evaluation Report
Project: Photosynthetic Water Splitting
Company: Oak Ridge National Laboratory, Oak Ridge, TN
P.I.: Dr. Elias Greenbaum
Date of Visit: March 30, 1999
Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

At the 1998 Hydrogen Program Peer Review, the Photosynthetic Water Splitting project being headed by **Dr. Elias Greenbaum** at Oak Ridge National Laboratory (ORNL) received some criticism from the reviewers. This criticism was based on the alleged failure of the project to concentrate on the proper avenues to lead to efficient hydrogen production, while addressing issues relating to the possibility of the existence of algae mutants that operate in a single photosystem process. In the past several months, however, Dr. Greenbaum has changed the course of this research to emphasize the development of algae that can produce hydrogen from water at a rate and pressure that would be commercially attractive. He is also addressing the decrease of the ratio of chlorophyll antennae to photosynthesis reaction sites thereby increasing the efficiency of the photobiological reaction. *Dr. Greenbaum is therefore showing himself to be both responsive to the reviewers' concerns, and, I believe, is on the right track.* We must, however, keep in mind that this type of research is long-term; we should not expect a precommercial-scale reactor based on these systems within, say, the next decade or two..

Project Strengths:

- Dr. Greenbaum was quite concerned about last year's review, and has been as responsive as anyone I have ever seen in this position. His shift of focus back to hydrogen production seems both sincere, and to date, effective. He is now looking at an alga that can produce hydrogen against a 1 atm. hydrogen head pressure, and is also now addressing antenna size. The fact that the research is refocused was clear to me during my visit, and is also, I believe, further proof that the Annual Review system works!
- In the past year, however, Dr. Greenbaum has moved his effort toward the alga *Scenedesmus* D₃, which, he has found, can produce hydrogen against at least a one-atmosphere hydrogen head pressure. This is more in line with following a path that could lead to usable hydrogen production.

Issues that should be Addressed:

- There is no doubt that Dr. Greenbaum is still interested in the "one vs. two photosystem" work that he had been immersed in over the last couple of years. He still plans to pursue it, only not for the Hydrogen Program. Care should be taken that this is not part of the Program Work.

II Introduction and Background:

I visited Dr. Elias Greenbaum at his laboratory at ORNL, Dr. Greenbaum's work is based on the development of algal systems that can synthesize hydrogenase. Certain algae can synthesize hydrogenase in an anaerobic atmosphere. No larger organism can do this. The hydrogenase enzyme is reversible; it can produce or consume hydrogen, and its reactivity is not inhibited by the presence of nitrogen (as the enzyme nitrogenase is). Some of the problems that incur with the use of the hydrogenase enzyme to produce hydrogen include:

- Hydrogenase will lose its ability to function in the presence of oxygen, generally at levels of 100-1000 ppm.
- The corresponding oxidation reaction is inhibited by the presence of hydrogen
- In the presence of CO₂, the photosynthesis reaction prevails.

Another problem is that the rate of photon excitation is uncontrollable. The excitation sets electrons in motion at a kinetically limited rate of about 100 electrons/second. Since there are a multitude of receptor sites for the photons (i.e., antennae), there is an imbalance between photon excitation and electron motion. It is thus necessary to reduce the antennae size, limiting the number of receptors, and thus "controlling" photon excitation.

Dr. Greenbaum, for the past several years has been conducting research on defining/creating algae that will make hydrogen (and oxygen) from water. His research, up until last year had focused on the alga *Chlamydomonas*. This was largely based on the fact that Dr. Greenbaum had some results indicating that the system required only one light reaction rather than the normal two to make hydrogen. This single photosystem mechanism (requiring only one photon) offered the possibility that the conversion of light energy to hydrogen for *Chlamydomonas* could be twice as efficient as that for other algae systems. In addition, *Chlamydomonas* is quite suitable for genetic manipulations that could decrease the antenna size.

The number of photosystems involved in the mechanism of water splitting by *Chlamydomonas*-produced enzymes then became a matter of some controversy, and the ORNL group devoted a great deal of effort trying to prove their one photosystem theory. The jury is still out on the answer to that, but it appears that the mechanism consists of at least partially the more common two-photosystem variety. Dr. Greenbaum believes that the one-photosystem mechanism is still partially correct too, however.

The bigger problem as far as the DOE Hydrogen Program was concerned, however, was that this debate was slowing progress toward a robust, efficient hydrogen-producing system that could eventually lead to a commercial product. This year's effort, however, has seen more of a hydrogen focus. Dr. Greenbaum has found that the alga *Scenedesmus* D₃ may be the "production hydrogen" alga needed. It can produce hydrogen against a one-atmosphere head pressure.

Much of our discussion, delineated below, centered on the *Scenedesmus* D₃ vs. *Chlamydomonas* options.

III Questions and Answers:

I provided Dr. Greenbaum with a series of discussion questions prior to my visit, and these formed a major part of our talk:

- 1. How does *Scenedesmus* D₃ compare to *Chlamydomonas* as a hydrogen producer? Your note says that *Scenedesmus* D₃ may be an “industrial grade” hydrogen producer. What were the factors that had you emphasizing *Chlamydomonas* up until this year? What technical factors caused you to change your emphasis to *Scenedesmus* D₃?**

Scenedesmus D₃ was the alga that was actually the one with which hydrogen production was originally discovered in 1942. The production rates of hydrogen from *Scenedesmus* D₃ and from *Chlamydomonas* are similar, but the former can produce hydrogen against a one-atmosphere hydrogen head pressure, thus making it more suitable for higher pressure hydrogen production. Up until now, the concentration was on *Chlamydomonas* because it was a better understood system. It was attractive from a genetic engineering perspective. That is, it was a good alga to work with in the task of reducing antenna size.

If ones goal is high pressure “industrial” hydrogen production, one would think that this would be a criterion from day 1, and that algae screening and development would have included this test, thereby identifying Scenedesmus D₃ earlier. This obviously did not happen. Dr. Greenbaum was caught up in the Chlamydomonas phenomenon of a single photosystem mechanism. This could have led to a higher conversion efficiency, and was obviously of importance for this reason. The fact that the hydrogen production reaction for Chlamydomonas was inhibited by hydrogen was not given enough importance at the time. This was probably a mistake, but maybe understandable in the light (no pun intended) of the single photosystem phenomenon. At any rate, the fact that Dr. Greenbaum has refocused his work toward Scenedesmus D₃ is more important.

- 2. How would you envision a commercial process in which *Scenedesmus* D₃ (or some other alga) would produce large quantities of hydrogen? What would you consider the biggest challenges to this effort?**

The process would be based, of course on solar-driven biotechnology. The reactors would be glass tubes, and the algae would generate hydrogen at relatively high positive pressures. Design features would address issues such as gas separation and oxygen-induced reaction inhibition.

The “designer alga” would have small antennae (perhaps 1/10 size), would be oxygen insensitive (this would be based on NREL’s contribution), and would be thermodynamically driven.

The biggest challenge, according to Dr. Greenbaum is obtaining adequate funding to complete the research phase and move the process out of the laboratory and into the marketplace. The important problems that must be solved include:

- the development of the high-pressure hydrogen producing system
- linearization of the light saturation curve of photosynthesis (*it reaches a plateau*)
- development of an oxygen tolerant hydrogenase enzyme

3. Your FY 1999 AOP submittal indicated that you were also doing some testing with *Chlorella*. How does this compare as a hydrogen producer?

Chlorella is yet to be tested. It is the third of the “rugged alga” that produce hydrogen along with *Scenedesmus* D₃ and *Chlamydomonas*.

4. You also indicate that you intend (or already have) to check the indirect measurement of hydrogen formation via oxygen concentration measurements by seeding the hydrogen atmosphere with 350 ppm CO₂. I assume that this will lead to the production of oxygen via photosynthesis. How will this serve as a check on the thermodynamically driven reaction? I assume that the formation of oxygen via photosynthesis will result in inhibition of subsequent hydrogen formation. However, you can’t measure hydrogen formation in a hydrogen atmosphere, so are you looking for a reduction in overall oxygen concentration? How does the oxygen concentration from the hydrogenase-catalyzed hydrogen evolution reaction compare with that from photosynthesis in the presence of 350 ppm CO₂?

The rates of oxygen evolution coupled to hydrogen production are typically 5 to 10 percent of the rate of oxygen evolution coupled to CO₂ reduction. This is because of the photosystem II requirement of CO₂/HCO₃⁻ for optimum oxygen evolution activity. The bicarbonate effect is one of the limiting aspects of biohydrogen production. (Light saturation is another).

You can simply measure the concentrations of CO₂, oxygen, and hydrogen.

5. What is ORNL’s role(s) in working with Melis’ group?

Both laboratories are part of the DOE biohydrogen production team. Dr. Greenbaum stated that ORNL is the leader in systems designed and constructed for measuring simultaneously photoproduction of hydrogen and oxygen, and CO₂ assimilation. Aside from the quantitative measurements, Drs. Greenbaum and Melis hold interactive critical dialogues on antenna sizes and sulfur issues. Sulfur deprivation could reduce the oxygen sensitivity of the hydrogenase enzyme.

6. What are the limiting factors as to the amounts and types of solutes and contaminants allowable in the water being split?

These algae are quite forgiving as far as water conditions are concerned. The basic rule of thumb is: if the algae can grow in the water, they can split the water.

7. If CO₂ inhibits hydrogen generation, what is the maximum amount of CO₂ allowable in the system? How would a practical system be purged of CO₂?

The degree of inhibition of hydrogen generation by CO₂ is dependent on temperature and light intensity. It is a good idea to keep the CO₂ levels below 10 ppm, by pumping on the system.

IV Additional Discussion:

Dr. Greenbaum believes that there is a 10-20 year “grace period” in developing a method of splitting water. He feels that the requisite research will take about that long. *I don't know about a grace period being available other than in the context of it probably taking that long to develop something of a realistic hydrogen infrastructure. Nevertheless, the time needed to develop the photosynthetic water splitting technology is probably accurate. Dr. Greenbaum contends that the time can be shortened by infusion of funds, and while this may be the case, the major message may be to keep the core research alive. It's probably the most important part of the Program.*

One aspect of the mechanism for hydrogen production that I was previously unaware of is the fact that if no CO₂ is present (i.e., no normal photosynthesis can take place), the photolysis results in the dehydrogenation of some of the starches within the alga's carbohydrate structure. In fact, 80% of the evolved hydrogen comes from the water being split, and the other 20% comes from the starch. *I would think that this would be a limiting factor, reducing the activity of the algae, unless the starch is rehydrogenated at some point.*

Dr. Greenbaum defines process efficiency as the Gibbs Free Energy of the produced hydrogen divided by the energy of the input light, and multiplied by 0.47 to account for the fact that only about 47% of the light energy is in the visible (and therefore useful) range. Input light energy is measured simply by focusing on algae on a known area of filter paper, and using photodetectors.

Dr. Greenbaum mentioned that Dr. Laurie Metz at the University of Chicago is investigating genetically reducing antenna size.

Technical Evaluation Report

Project: Bioreactor

Company: University of Hawaii, Honolulu, HI

P.I.: Dr. Rick Rocheleau (**Acting**)

Date of Visit: July 8, 1999

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The bioreactor project at the University of Hawaii is at a critical point of its existence. The project has a fairly large (200 liter) working bioreactor, an organism that produces hydrogen under anaerobic conditions and is fairly easy to work with, a competent program manager who has recently taken the program under his wing, and several biologists and bioengineers associated with the program to varying degrees. On the other hand, the project's principal investigator (PI) resigned several months ago, and no new PI has been identified. In addition, the identified cyanobacteria, *Arthrospira*, while it produces hydrogen readily in the dark, does not produce hydrogen in the light (photolytically). The anaerobic hydrogen evolves from the carbohydrate matter itself, resulting in partial (note: not total) dehydrogenation of the cyanobacteria. It leaves a partially dehydrogenated biomass waste material. This is not the anticipated process, and seems less efficient and inferior to other biohydrogen systems. The identification of a light induced reaction process with this or another organism resulting in hydrogen from water would be preferable.

Project Strengths:

- The most valuable commodity associated with this project is the bioreactor. The reactor should be made available for collaborative efforts. The identification of a good, water-splitting, hydrogen-producing organism either from the Mitsui collection or elsewhere would be a bonus.
- The Mitsui collection itself is a very valuable asset.

Issues that should be Addressed:

- The continued use of *Arthrospira* as only a low-level, anaerobic hydrogen producer should be discouraged unless one can demonstrate the regeneration of the byproduct, resulting in a steady-state biomass concentration.
- A suitable PI needs to be identified.

II Introduction and Background:

I visited **Dr. Rick Rocheleau** and his team at the University of Hawaii's Hawaii Natural Energy Institute (HENI) on July 8, 1999. Dr. Rocheleau is currently managing the bioreactor project, and is acting as principal investigator at least until a new PI can be put into place. This is a result of the resignation of Dr. Oskar Zaborsky, the previous PI, from the project several months ago. Currently Dr. Rocheleau's team includes biologist **Dr. Yasuyuki Nemoto**, bioengineer **Dr. Scott Turin**, and visiting biologist **Dr. Youji Wachii**. Drs. Nemoto and Wachii were present at our meeting; Dr. Turin was away on travel. I also met **Dr. JoAnn Radway** who formerly was Dr. Zaborsky's primary hands-on researcher. Dr. Radway is still performing research at UHawaii through the university's Marine Bioproduct Engineering Center (MarBEC). Dr. Radway recently resigned from the biohydrogen project. Through MarBEC, she is still actively involved with the bioreactor, and also is responsible for the maintenance of the Matsui Collection.

During my visit, I spent several hours with Drs. Rocheleau, Nemoto and Wachii, during which time I was given an interactive presentation on the history of and the planned future of the Hawaii biohydrogen project. Included in this presentation was a discussion of the set of questions that I had sent to Dr. Rocheleau about two weeks prior to the meeting. Following the presentation/discussion, I was shown the outdoor bioreactor and the laboratory facilities as well as the Matsui Collection.

III Tour:

I was given a tour of the biohydrogen facilities by Dr. Radway and her staff. Most impressive was, of course, the bioreactor. Its dimensions and capacity are discussed below in the "Initial Discussion" section. While I was there, the reactor was being calibrated for flow characteristics. A concern was the fact that regardless of how the system had been configured, all the small (high surface area) bubbles were coalescing into large bubbles with low surface to volume ratios while flowing up the tubes. This was hindering transfer properties. It appeared (at least at the time) that the problem would not be solved mechanically, but a chemical solution might be needed. Dr. Radway and her group were conducting the flow tests. Dr. Rocheleau did indicate to me that the two groups would share the data.

I also was taken through the laboratories, which contained a good assortment of smaller reactors, diagnostic equipment, and the Matsui collection of organisms. All of this is being maintained by Dr. Radway and her people. In fact, one of Dr. Radway's technicians probably spends about four hours each day just tending to the Mitsui collection.

IV Overview and Initial Discussion:

The goal of the HENI Bioreactor Project is to develop a sustainable bioreactor for hydrogen production. The process consists of two major stages: growth of the cells, and production of hydrogen. HENI plans to use a marine organism for this work. This is

because marine organisms are more abundant, are easier to grow due to ease of nutrient uptake, and hold a much more dominant position in U Hawaii's photobiological history. *Surprisingly*, however, the current organism of choice is *Arthrospira sp.*, a fresh water organism. The organism is equivalent to *Spirulina sp.*, a cyanobacteria that is being used by a company called Cyanotech as a source of beta-carotene extraction. The HENI team is trying to identify a marine organism with properties similar to *Arthrospira sp.* The organism physically is long and stringy in structure, being one cell wide, but about 1 mm in length. These dimensions make *Arthrospira* easy to work with as material can be concentrated easily by sieving. In addition, *Arthrospira* grows well under alkaline conditions (an unusual situation) and is not very susceptible to contamination.

The FY 1999 proposal which had been put into place by former P.I. Oskar Zaborsky was comprised of a mechanism in which the cells grew under light conditions (photosynthesis) in stage one, and then produces hydrogen in a three-step second stage that was comprised of:

- concentrating the cells and adapting them to hydrogen production under anaerobic, dark conditions;
- producing hydrogen under light conditions; and
- recycling the cells to regrowth (stage 1)

Although literature data indicated that this scheme had worked with some types of green algae, it did not work here. The anaerobic "adaptation" step actually resulted in the production of hydrogen. Hydrogen was formed by metabolizing the cells' own carbohydrate. Hydrogen was not produced in the light; the photosynthesis process of Stage 1 proved dominant in this step.

Perhaps the most significant feature of the project to date is the utilization of the outdoor bioreactor to grow the organism. The bioreactor (*which was being used to determine flow mechanisms on the day that I visited*) consists of eight tubes, each twenty meters in length and 4 cm in diameter. This provides for a total volume of 200 liters and a total surface area of 6.4 square meters.

The growth of *Arthrospira* in the bioreactor was measured at 0.43 g/liter/day. (86 g/day for the 200 liter reactor.) The *Arthrospira* concentration in the reactor is typically 3000-5000 mg (dry)/liter.

Hydrogen was produced in the dark at a rate of about 22.4 ml in 12 hours for each gram of *Arthrospira*. If the reactor produces 86 g /day biomass, this works out to a total of about 2 liters of hydrogen produced in 12 hours. No hydrogen was subsequently produced in the light. *The actual data shown never actually reaches the 22.4 ml per 12 hours bioreactor time. Under various conditions, the graph I was shown indicated production rates of 50 to 80 percent of that amount.*

Dr. Rocheleau and his team propose for 2000 that the "Old Hawaii" process be modified to reflect what was actually happening: hydrogen production in the dark followed by recycling of the biomass. They claim that concentrating the *Arthrospira* to go from an

aerobic to an anaerobic environment would be easily accomplished by screening the long, thin *Arthrospira* material. They need to engineer the process, however, to make it continuous. The Cyanotech process would be a good model for this. The group may also try to look at light catalyzed hydrogen again if they can find a proper alga to work with. One of their goals might be to find a green alga that would produce hydrogen in the light, but would be easy to concentrate like *Arthrospira*.

The direction that the research appears to be going is questionable. A light-catalyzed hydrogen production process with an easy to concentrate biomass (as Arthrospira appears to be) would have been preferable. It would have (similarly to other projects) likely resulted in hydrogen from water splitting rather than biomass depletion. What we appear to have here is a project where a small amount of hydrogen is stripped off of a large molecule leaving a large amount of questionable byproduct. I have my doubts if the direction that the project is taking is therefore the right one. An attempt to use the bioreactor with materials that could produce light-catalyzed hydrogen might be preferable.

V Questions and Answers:

A significant period of time was used to go over the series of questions that I sent to Dr. Rocheleau prior to our meeting. These questions and responses are discussed here:

1. What properties of *Arthrospira* make it superior to other bacteria strains in hydrogen generation? Have other systems been looked at? For example, how well did *Chlamydomonas* perform?

As stated earlier, *Arthrospira* is filamentous, making it easy to concentrate by screening. The concentrating step is important in that it makes it easier to achieve the anaerobic conditions needed for dark hydrogen production. *Chlamydomonas* produces hydrogen in the dark at about the same rate as *Arthrospira*, but when it is moved into the light, it starts producing oxygen (photosynthesis), inhibiting further hydrogen production. The main problem with *Chlamydomonas* is that it is difficult to concentrate.

Since we know that Chlamydomonas will produce photolytic hydrogen in the absence of CO₂ and with small antennae, it seems to me that it would be advantageous to examine the possibility of improving the ability to concentrate the alga so as to use it in conjunction with the bioreactor. Either that, or find a marine organism that will work. It's the bioreactor that is HENI's strength, not the Arthrospira.

2. Does hydrogen actually get produced during the “dark step”, or what is meant by “turning on the biochemical machinery?”

“Turning on the biochemical machinery” means creating physiological changes inside the cells that will make it possible to produce hydrogen by reversible hydrogenase activity. As we have seen, hydrogen is produced during the dark step, although this wasn't the original intent.

What I see as the problem is that the mechanism for dark hydrogen production is not really water splitting, it's biomass degradation.

3. If *Arthrospira* has an activity of 1 micromole hydrogen per mg of dry cell under dark conditions, what production rate would be expected in the light-dependent step (step 3)?

As stated, no hydrogen is produced; photosynthesis prevails. HENI has indicated that they plan to look for an organism that has an oxygen-tolerant hydrogenase system that would allow photolytic hydrogen production to occur.

If HENI is going to do anything other than provide the bioreactor, the oxygen tolerant organism approach would be a good idea. Concentrating on a marine organism would be a good idea also. Alternatively, HENI could simply provide the bioreactor for systems being developed in other laboratories.

4. Explain the “exogenous electron carrier”.

This is an artificial electron donor that is used to measure enzymatic activities of materials such as hydrogenase.

5. It appears that U Hawaii has addressed steps 1-2 (growth of cyanobacteria and dark activation) of the four step process. Have steps 3 and 4 (hydrogen production in the light, and recycling) been evaluated? Is this going to be folded in to the new fiscal year task of making a sustainable bioreactor?

The plan has been modified to allow for dark hydrogen production, as already stated.

6. Eli Greenbaum at ORNL has been evaluating systems that he believes can produce hydrogen against a one-atm. hydrogen head pressure. In other words it has the potential of producing hydrogen in usable concentration under real world, industrial conditions. What is the potential for the *Arthrospira* system under real-world conditions?

They have no experimental data on this. They stated, however, that since they are concentrating the cyanobacteria and forcing anaerobic conditions, they would have very little headspace.

7. In what manner does the culture collection maintenance play into the bioreactor work? Is the collection being co-funded by other sources as well?

HENI plans to look to the collection to find other filamentous species and check them for hydrogen production activity. They will also look for Hawaiian marine filamentous cyanobacteria strains.

The collection is being co-funded by MarBEC. This is being accomplished by having Dr., Radway, who is being funded by MarBEC, maintain the collection.

I am not sure that “filamentous” should be the key screening parameter. Although concentrating potential is important, I believe that the ability to produce hydrogen photolytically is more important. This should be a key criterion for selecting new species.

8. At what production rate/ reactor size was the preliminary production cost of \$15/MMBtu established?

This number was apparently an “old John Benneman number.” Dr. Rocheleau was unsure of its history, but planned to get back to us on this. (*Dr. Benneman formerly collaborated with Dr. Zaborsky on this project.*)

9. What efforts are being made to interact with the other Hydrogen Program photobiological P.I.s? What are (will be) the contributions of other labs to the U Hawaii Project? What are (will be) the contributions of U Hawaii to projects in other labs?

Other labs would contribute to the Hawaii project by providing better strains or species for hydrogen production. These would likely be engineered to contain oxygen-tolerant hydrogenase. Hawaii would contribute to other projects by testing these strains in a “real-world bioreactor,” providing hydrogen production information.

For some of this work, Dr. Rocheleau and his staff believe that the bioreactor is too large. They would want to use a smaller reactor to test other organisms and engineering parameters.

None of this type of interaction is happening as yet. I would think that this could be the most important contribution that the Hawaii biohydrogen project could make to the Hydrogen Program.

10. How would you envision a commercial process in which a bioreactor system would produce large quantities of hydrogen? What would you consider the biggest challenges to this effort?

The HENI group identified many technical challenges:

- The need to find a more suitable marine organism
- Addressing the recycling step so that essential nutrients can be reused
- The need for an automated “anaerobification” step that will allow the cells to be concentrated and put into a closed chamber with very little head space, where the cells can quickly consume all the remaining oxygen. This will provide for anaerobic conditions where hydrogen can be produced in the “dark” reaction.

This did not really address commercialization. I am also concerned about too large an effort on dark hydrogen. That process does not seem very efficient.

11. What are the plans as to restaff the bioreactor project?

The current plan is to allow Drs. Nemoto, Wachii, and Turin to run the project. A new post-doctoral fellow will also be hired to run the experiments on the “New Hawaii Process”.

I am not sure that this is the entire answer. A single strong PI needs to be identified either from within the project or elsewhere. If Dr. Rocheleau can spend more time directing the project (which he probably does not have time to do) this would help. I’m not sure this issue has been completely thought out yet.

VI Final Thoughts:

The presence at the University of Hawaii of the bioreactor, which will likely be of great value to the overall biohydrogen segment of the Program, is by far the project’s major asset. I do not believe that the project is headed in the right direction by concentrating on “dark” hydrogen production. The lack of a permanent PI is another serious problem. There is also the question as to what equipment belongs to the Hydrogen Program and what is the property of the MarBEC project and what is jointly owned and shared. Given his track record in other UHawaii projects, Dr. Rick Rocheleau should be given a chance to straighten these problems out.

The project should also move in the direction of providing bioreactor testing for the organisms of other laboratories, and looking for a marine organism that will produce photolytic hydrogen.

The need to efficiently produce hydrogen needs to be stressed. Interaction with other labs needs to be stressed. The role of Dr. Radway needs to be defined.

If the Hawaii biohydrogen project is to succeed, it has to be centered on the bioreactor.

Technical Evaluation Report

Project: Vehicular Hydrogen Storage Using Cryogenic Hydrogen
Company: Lawrence Livermore National Laboratory, Livermore, CA

P.I.: Dr. Salvador Aceves

Date of Visit: September 22, 1999

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The pressurized cryogenic hydrogen storage tank project being carried out by Lawrence Livermore National Laboratory (LLNL) under the direction of **Dr. Salvador Aceves** is one of the group of storage projects that is of great importance to the eventual utilization of on-board hydrogen as a fuel cell feedstock. It provides the potential of a relatively inexpensive, long-range storage option. Nevertheless many technical, safety (both real and perceived) economic, and logistical hurdles need to be addressed.

The concept, briefly, involves the development of an on-board hydrogen storage tank that is strong enough to hold over 3,000 psi of compressed hydrogen, and is also sufficiently insulated to hold liquid hydrogen with only minimal evaporation. In this way, if one is traveling short distances, one can use the less expensive compressed hydrogen. However, if one requires a longer range, one can switch to the more costly, but more compact liquid hydrogen.

The LLNL group has conducted extensive techno-economic analyses on the concept, identified tank and insulation materials, constructed prototype tanks, and cycled (pressure and temperature) and burst-tested the tanks. Pressure cycling is performed with pressures up to 3,500 psi. Helium is used as the cycling gas. Most of the temperature testing has been done at liquid nitrogen temperatures (77°K) due to safety considerations in using liquid hydrogen. At the time of my visit, Dr. Aceves and his team had recently completed their first cycling test with liquid hydrogen. In order to perform this test, the participants had to go to a remote testing area, far removed from the laboratory, and had to spend 2 or 3 days virtually locked in a bunker.

Project Strengths:

- An effort to make a single system that can be both a low cost hydrogen storage strategy for a “commuter” vehicle and a high capacity hydrogen storage strategy for long trips is technically a good one.
- The group is making significant progress using virtually “off-the-shelf” technology.
- Much of the testing that has been performed to date (temperature cycling, pressure cycling, burst testing) has been successful.

- The tank has been shown to never totally lose its supply of liquid hydrogen as a conventional liquid hydrogen tank would. Due to its insulation, there will always be hydrogen present on which to run the vehicle.

Issues that should be Addressed:

- There needs to be more thought put to scenarios where a user of a vehicle equipped with one of these tanks would switch back and forth between gaseous and liquid hydrogen.
- Testing with hydrogen has just started, and is apparently difficult to do at LLNL from a permitting standpoint. If the difficulty persists it could unduly stretch out the project. In addition, it leads to a public perception that hydrogen is a uniquely dangerous material.
- Since hydrogen testing is just now starting, much of the designing to date has been based on extrapolation from liquid nitrogen temperatures. While the colder temperature of liquid hydrogen points to only a slight contraction of the case material, and less off-gassing of the fibers, testing under real conditions are needed.
- A better dissemination of information is needed. For instance, referring to the insulation overwrap as “multi-layer vacuum super insulation” without any further explanation, is insufficient at best.
- Better bond data (or a better bond) is apparently necessary for the fiber/epoxy composite. We were told that it “fails somewhat” within the composite – not at the composite to aluminum interface. We were also told that the internal pressure presses everything together.

Overall, I think that this is a good project, but it needs a better understanding of what the potential market actually will be. Using two fuels (gaseous and liquid hydrogen) for two ranges sounds good in theory, but how applicable is it on a large scale? Some real world scenarios need to be addressed.

II Introduction and Background:

I met with Dr. Salvador Aceves at his laboratory at Lawrence Livermore National Laboratory to discuss his project. Dr. Aceves made a presentation that was updated from his Annual Review Presentation. We discussed the project in detail including a series of questions that I had forwarded to Dr. Aceves prior to my visit. Dr. Aceves also showed me the facilities, samples of tank materials, and prototype tanks.

The project has been going on for several years, initially as an analytic study of methods to provide low-cost, long-range hydrogen storage. The current design emerged as the most promising. It couples the lightweight of pressure vessels with the smaller overall volume/higher storage density of cryogenic vessels. The storage system is based on the

premise that a personal vehicle can serve two purposes: it can be a short-range commuter vehicle, and it can be a vehicle used for long distance travel. Thus, the storage system is designed to hold either high-pressure (3,500 psi) gaseous hydrogen for commutes, or liquid hydrogen for long distance travel. Since gaseous hydrogen is used only for short-range driving, the tank can be relatively small (alternatively, the extra design for an ultra-high pressure tank is avoided). Since expensive liquid hydrogen is only used when necessary for long range driving, the cost is relatively low. In addition, the “super insulation” keeps evaporation low.

LLNL is partnered with Standard Composites Industries (SCI) of Pamona, CA. SCI is performing testing at no cost. Dr. Aceves mentioned that they are planning a demonstration of the tank in FY 2001. A possible site is Palm Desert.

III Tour:

The tour of the facilities was more-or-less routine. I saw prototype tanks, bare and insulated; I saw joints and fittings designed to facilitate the filling and emptying of the tank; I saw pressure test facilities and assemblies. I did not see the area where actual hydrogen testing was (had been) going on. This site was several miles away from the laboratory, and was not easily accessible.

I was shown a roll of (and given a small piece of) the “multi layer vacuum superinsulation.” It more-or-less-resembles a papery aluminum foil. This is discussed below.

IV Questions and Answers:

I sent Dr. Aceves a set of discussion questions prior to my arrival. He responded in writing and we also discussed the questions and answers in detail.

- 1. Please describe in terms of pressure and temperature cycles, the conditions under which the vessel would operate between “fill-ups.” Consider situations in which the vehicle i) would make several short trips (maybe 20-30 km a day, back and forth to work) ii) would make a single long trip.**

“See [...Exhibit 1 ...] with the results of the run. Also see [...Exhibit 2...] with a plot of the temperature and pressure shown on a property diagram for hydrogen.”

Exhibit 1 shows the appropriate pressure and temperature cycles and Exhibit 2 shows a plot of the state and density of hydrogen as a function of time for the same process. The data show a 95 liter cryotank filled with 5 kg of liquid hydrogen, driven 20 km per day. Each day’s consumption is about 0.15 kg.

A couple of interesting points emerge. First of all, only the first part of the question was answered. Note that my question did not specify whether the hydrogen was gaseous or liquid. All of the previous reports on the system indicated that the tank would be filled with compressed, gaseous hydrogen for short daily commutes and with liquid hydrogen

for long trips. Yet in a scheme that would seem to clearly call for gaseous hydrogen, Dr. Aceves modeled liquid hydrogen. This goes along with his many comments indicating that the system may be best run on liquid hydrogen only.

Second, the curve shows that after about a week, the remaining hydrogen is all vapor. As the hydrogen continues to be depleted and the temperature rises, the maximum pressure in the vessel, which is a little above 1,000 psi, is reached after about two weeks.

2. How does refueling a vehicle that uses the insulated pressure vessel differ from refueling a liquid hydrogen vehicle?

“Ideally, an insulated pressure vessel would be fueled with compressed hydrogen for most of the time, and it would be fueled with liquid hydrogen only when this is needed for long range. When fueled with liquid hydrogen, the fueling of an insulated pressure vessel would be different than the fueling of a liquid hydrogen tank because the insulated pressure vessel may have its contents under pressure. Ideally, the tank would be filled with liquid hydrogen at high pressure to avoid losing the gaseous hydrogen contained in the vessel. If this is not practical or economical, then the high pressure hydrogen would have to be vented before filling it with liquid hydrogen.”

The insulated pressure vehicle would be filled with liquid hydrogen at high pressure to avoid losing the gaseous hydrogen already contained in the vessel. This is based on the assumption that the tank already most likely contains some pressurized gaseous hydrogen as a result of its primary day-to-day use. If the high-pressure fill is not economical or practical, the gaseous hydrogen would have to be vented prior to the liquid hydrogen fill up.

The need to vent gaseous hydrogen in order to fill up with liquid hydrogen is an item that came up quite a bit during the day. It appears that this may be one of the major drawbacks of the system. It raises costs, increases safety concerns, and may turn the system into one with limited appeal. It also reduces the likelihood of a conceptual home filling system.

3. If a cryogenic hydrogen vessel were to fail – say in a collision with another automobile, how would the consequences compare to those that might be suffered by a compressed hydrogen tank or by a liquid hydrogen tank?

“This depends on the state of the hydrogen at the moment of the failure. If the stored hydrogen is in a gaseous state, then the consequences would be similar to having compressed hydrogen tank fail. If the tank contains liquid hydrogen, then the accident would be similar to having a liquid hydrogen tank fail. In either case the failure would be quite benign, since hydrogen evaporates and diffuses so quickly. Failure of pressure vessels is in general unlikely to occur, as can be derived from the good safety record that exists for natural gas tanks.”

If the tank were filled with gaseous hydrogen, the consequences would be similar to the failure of a standard compressed hydrogen tank. If it were filled with liquid hydrogen, results would be similar to those for a standard liquid hydrogen tank. Dr. Aceves stressed the benefits of quick evaporation and rapid diffusion of hydrogen as limiting the negative effects of a tank failure.

What Dr. Aceves says is certainly true, although I would hesitate to agree with his use of the word “benign” when discussing a potential failure.

4. What plans are there to address potential seal failures?

“Seals are a big problem when high-pressure hydrogen has to be contained, especially considering that in this case we have to keep a vacuum space around the pressure vessel for the insulation. For this reason, we decided to only use welded joints in all the ducts that contain hydrogen. We also use an explosion-bonded part between the aluminum tank and the stainless steel shell. Seals between the vacuum space and the environment are much easier to handle and regular vacuum seals are used.”

Dr. Aceves believes that seals are a very important consideration, especially in light of the fact that the insulation surrounding the case needs to contain vacuum space. Thus, LLNL is using only welded joints for all ducts that contain hydrogen. The seal between the aluminum tank liner and the stainless steel shell is an explosion-bonded aluminum/stainless steel joint. (Explosion bonding is produced by setting off an explosive charge next to adjacent plates of the two metals to be bonded. The explosion “pushes the two plates into each other.”) Seals that do not come in contact with hydrogen (such as those within the vacuum insulation) are not a problem; “regular” seals are used.

This question was prompted by some of the concerns of the Peer Review Panel at the Annual Review. Dr. Aceves indicated that a bimetallic joint did indeed show leakage, and had to be replaced. This will bear careful watching. One question that arises is whether the intricate welding process that may be necessary to make a sound joint can be cost-effective.

LLNL appears to be well aware of reviewers’ concerns. They are performing extensive cycling and leak checking. These need to be done with hydrogen, however.

5. What are the materials that make up the multi-layer insulation (If this is proprietary, please just provide whatever generic information that you can.)

“The multi-layer insulation is made of aluminized mylar with a layer of very thin gauze in between the layers to reduce conduction heat transfer. This is a commercial product. We only cut it into pieces that fit around the vessel.”

The insulation is a commercial product, made up of layers of aluminized Mylar separated by thin layers of gauze. The gauze reduces thermal conductivity, while the shiny aluminum surface provides the reflectivity that cuts down on radiative heating. LLNL only cuts the insulation to shape.

The only objection I have here is the use of the term “multilayer vacuum superinsulation” together with its acronym “MLVSI” and without much in the way of description, if any, in many of Dr. Aceves’ publications it becomes confusing.

6. The vessel itself has been described as a kevlar/aluminum or carbon fiber/aluminum vessel, and has been depicted as having an aluminum base with

a fiber overwrap. Is there a binder (resin) component to the fiber? What temperatures is the fiber wrap exposed to? Has the wrap material been exposed to mechanical properties testing as a function of temperature, and if so what were the results?

"Yes, the tanks have a Kevlar/epoxy overwrap. The fiber overwrap will be exposed to liquid hydrogen temperature (20 K). The individual fibers and the resins have been tested (not by us) down to liquid helium temperature (4 K). The results indicate that the fiber stiffens as the temperature drops. We have made a table of properties for the fibers and the resins and these will be used in a detailed finite element analysis of the tanks."

The overwrap is kevlar or carbon with an epoxy binder. This overwrap will see temperatures as low as 20°K (liquid hydrogen temperatures.) Testing has been done (not by LLNL) on the fibers and the epoxies (*apparently separately*) using liquid helium (4°K). The fibers stiffen as the temperature drops. LLNL has compiled a table of fiber and resin properties and is using these data in a finite element analysis.

Failure testing at low temperatures would be of value.

7. Has there been, or are there any plans to perform aging tests on the vessel or its components?

"Aging is always an issue when an accelerated cyclic test is conducted (as we are doing). Kevlar is indeed known to age, and for this reason, the safety factor for Kevlar vessels (3.25) is bigger than the value used for carbon fiber vessels (2.5). However, this appears to be the only effect of aging. Once this effect is taken into account (by increasing the safety factor), an accelerated test should be able to reflect the material behavior during regular use. Pressure vessels fail suddenly when a high pressure is applied. There is no evidence that the pressure vessel will fail by creep under a sustained load."

LLNL is conducting accelerated cycling tests, but apparently not aging tests. The Kevlar issue "appears to be the only effect of aging." With this being controlled by the increased safety factor, the accelerated cycling tests should accurately reflect real material behavior.

I would think that some accelerated aging tests would be of value to supplement the Kevlar aging database. Aging properties of epoxy, bond interfaces, and any material coming into direct contact with hydrogen should be evaluated thoroughly.

8. When vessels were burst-tested, what were the failure modes?

"The vessels failed by hoop mid cylinder separation. This is the preferred mode of failure. See [Exhibits 3 and 4..]."

The burst testing was performed after a cycling series; the vessel burst at 13,657 psig. This number was better than (but not outside the statistical range of) other similar vessels that had been burst tested.

9. Are you still considering the microsphere option at all?

“No. Multilayer insulation is inexpensive enough and easy enough to install that we are planning to continue using it in the future. We have proven to ourselves that we can keep a high vacuum in the insulation space by generating an initial vacuum with a vacuum pump. The vacuum is then improved as the vessel is filled with liquid hydrogen due to cryopumping (adsorption into the fiber that occurs when the vessel is cooled down).”

10. At what temperature (approximately) is the interface between the exterior of the fiber wrap and the innermost layer of the insulation?

“Most of the thermal resistance in the insulated pressure vessel is in the multilayer insulation. Therefore, the outer surface of the fiber overwrap reaches a temperature that is very close to the temperature of the interior of the vessel. This was verified in our recent experiments where it reached the temperature of the cryogenic fluid to within 10 K.”

The exterior of the fiber wrap (and thus, the innermost layer of insulation) is very close in temperature to the internal temperature of the vessel. That is, with liquid hydrogen inside the vessel, about 20°K.

Note: This question was asked due to my mistaken notion that the insulation is bonded to the composite case (which would raise the question of bond strength at cryotemperature) As the MLVSI is physically wrapped around the case, but is not bonded, this is not an issue. I do believe that the LLNL researchers need to be a little more careful in how they describe their system, so that misconceptions are not generated.

V Additional Discussion:

Extensive testing has taken place on the inner vessel, but not much yet on the insulated vessel. They have tested a small (1 kg H₂) insulated pressure vessel with liquid hydrogen. They held it for two days without any problems seen.

At low temperatures, the fiber wrap will be less tough (less resistant to impact) but would burst at a higher pressure. A ten-meter drop test is being scheduled for a tank filled with liquid nitrogen.

Good test, but liquid hydrogen is colder, and would likely decrease tank strain capabilities.

All the testing and cycling that has been done on the tanks is performance-based. The problem is that no one is certifying these types of tanks. LLNL is looking for a way to make this happen.

The vessel does emit a considerable amount of gas. This is not composite-based hydrocarbons, but primarily water (70%) and nitrogen (30%). At cryogenic temperatures, the vessel actually absorbs gas.

The insulation appears to be working well. Conventional liquid hydrogen systems start losing hydrogen at about two days, and have lost all hydrogen after about ten days. According to Dr. Aceves, this insulated cryohydrogen system loses hydrogen only very gradually, and actually reaches what appears to be equilibrium. Some hydrogen (3.5 kg in a tank designed for 5 kg) remains, and will be around for “years”.

VI Final Thoughts:

A tank that can either hold pressurized, gaseous hydrogen or liquid hydrogen allows both relatively inexpensive daily commutes (on gaseous hydrogen) and long-range (400 miles) travel (on liquid hydrogen). Say that you are commuting to work every day, so you fill up with compressed hydrogen. Then on the weekend, you plan to drive a few hundred miles to another city, so you fill up with liquid hydrogen. But how can you, when you haven't used up all of the gaseous hydrogen from the previous fill-up? What do you do? Do you vent the excess hydrogen? Sell it back to the hydrogen dealer? Have two tanks? All of these options increase safety concerns and/or system cost.

Dr. Aceves mentioned that perhaps if you are planning to use your vehicle for long trips you fill it with liquid hydrogen all the time. This is a more costly option. Dr. Aceves likened the situation to owning an SUV. You pay for the “status” associated with owning the vehicle even though you don't utilize its intended advantages. I'm not sure that I agree. Also, if you are going to do this, the tank will simply serve as an insulated liquid hydrogen tank. Why give the tank an excess of high-pressure capability? The curve that Dr. Aceves presented to us shows that the pressure goes a little above 1000 psi.

It appears that an analysis is warranted in which the methodology and cost of using the system with only liquid hydrogen is considered.

Exhibit 1. Table of Temperature and Pressure Cycles

results obtained from cryotank program for a car driven 20 km daily
the car is an 80 mpg car
tank volume is 95 liters

		mass	temperatu	pressure	gas	density	density	temperatu
		in tank, kg	re K	Pa	fraction	kg/m3	lb/ft3	re R
initial		5	20			52.63158	3.278793	36
after	drive	4.844624	19.20549	73418.63	5.80E-03	50.99604	3.176904	34.56988
after	parking	4.844624	22.62738	192384.8	1.22E-02	50.99604	3.176904	40.72928
after	drive	4.689248	21.96175	161961.2	1.21E-02	49.36051	3.075014	39.53115
after	parking	4.689248	24.9602	326240.7	2.02E-02	49.36051	3.075014	44.92836
after	drive	4.533872	24.35707	287509.9	2.12E-02	47.72497	2.973125	43.84273
after	parking	4.533872	27.05083	494176.3	3.05E-02	47.72497	2.973125	48.69149
after	drive	4.378496	26.49614	446086.3	3.32E-02	46.08943	2.871236	47.69305
after	parking	4.378496	28.93521	690628.1	4.25E-02	46.08943	2.871236	52.08338
after	drive	4.22312	28.45396	637440	4.86E-02	44.45389	2.769347	51.21713
after	parking	4.22312	30.6446	912872.4	5.29E-02	44.45389	2.769347	55.16028
after	drive	4.067744	30.25553	858434.9	6.67E-02	42.81836	2.667458	54.45995
after	parking	4.067744	32.11022	1139337	2.67E-02	42.81836	2.667458	57.7984
after	drive	3.912368	31.91335	1106310	7.42E-02	41.18282	2.565569	57.44403
after	parking	3.912368	37.58789	2845801	0.00E+00	41.18282	2.565569	67.6582
after	drive	3.756992	36.5918	2543262	0.00E+00	39.54728	2.46368	65.86524
after	parking	3.756992	40.43945	3241895	0.00E+00	39.54728	2.46368	72.79101
after	drive	3.601616	39.36523	2958301	0.00E+00	37.91175	2.36179	70.85741
after	parking	3.601616	45.06836	4356738	0.00E+00	37.91175	2.36179	81.12305
after	drive	3.44624	42.72461	3537207	0.00E+00	36.27621	2.259901	76.9043
after	parking	3.44624	50.84961	5765528	0.00E+00	36.27621	2.259901	91.5293
after	drive	3.290864	48.70117	4961817	0.00E+00	34.64067	2.158012	87.66211
after	parking	3.290864	54.6582	6215137	0.00E+00	34.64067	2.158012	98.38476
after	drive	3.135489	52.72461	5563184	0.00E+00	33.00515	2.056124	94.9043
after	parking	3.135489	59.01367	6795411	0.00E+00	33.00515	2.056124	106.2246
after	drive	2.980113	56.41602	5898731	0.00E+00	31.36961	1.954235	101.5488
after	parking	2.980113	63.56445	7400293	0.00E+00	31.36961	1.954235	114.416
after	drive	2.824737	60.5957	6353223	0.00E+00	29.73407	1.852345	109.0723
after	parking	2.824737	67.93945	7881348	0.00E+00	29.73407	1.852345	122.291
after	drive	2.669361	64.75586	6756153	0.00E+00	28.09854	1.750456	116.5605
after	parking	2.669361	72.02148	8157519	0.00E+00	28.09854	1.750456	129.6387
after	drive	2.513985	68.7793	7058887	0.00E+00	26.463	1.648567	123.8027
after	parking	2.513985	75.24414	7788379	0.00E+00	26.463	1.648567	135.4395
after	drive	2.358609	72.68555	7211231	0.00E+00	24.82746	1.546678	130.834
after	parking	2.358609	79.0918	7759082	0.00E+00	24.82746	1.546678	142.3652
after	drive	2.203233	75.81055	6799707	0.00E+00	23.19193	1.444789	136.459
after	parking	2.203233	82.86133	7675879	0.00E+00	23.19193	1.444789	149.1504
after	drive	2.047857	79.46289	6695997	0.00E+00	21.55639	1.3429	143.0332
after	parking	2.047857	86.65039	7546582	0.00E+00	21.55639	1.3429	155.9707
after	drive	1.892481	82.99805	6537793	0.00E+00	19.92085	1.241011	149.3965
after	parking	1.892481	90.32227	7350098	0.00E+00	19.92085	1.241011	162.5801
after	drive	1.737105	86.5332	6334668	0.00E+00	18.28532	1.139121	155.7598
after	parking	1.737105	93.93555	7089942	0.00E+00	18.28532	1.139121	169.084
after	drive	1.581729	89.93164	6069824	0.00E+00	16.64978	1.037232	161.877

Exhibit 1 continued

after	parking	1.581729	97.37305	6592286	0.00E+00	16.64978	1.037232	175.2715
after	drive	1.426353	93.34961	5754590	0.00E+00	15.01424	0.935343	168.0293
after	parking	1.426353	101.0059	6210254	0.00E+00	15.01424	0.935343	181.8106
after	drive	1.270977	96.72852	5379004	0.00E+00	13.37871	0.833454	174.1113
after	parking	1.270977	104.6387	5775098	0.00E+00	13.37871	0.833454	188.3497
after	drive	1.115601	99.89258	4791699	0.00E+00	11.74317	0.731565	179.8066
after	parking	1.115601	108.3105	5283887	0.00E+00	11.74317	0.731565	194.9589
after	drive	0.960225	103.1152	4267090	0.00E+00	10.10763	0.629676	185.6074
after	parking	0.960225	111.9434	4702637	0.00E+00	10.10763	0.629676	201.4981
after	drive	0.804849	106.3184	3692871	0.00E+00	8.472095	0.527787	191.3731
after	parking	0.804849	115.752	4075684	0.00E+00	8.472095	0.527787	208.3536
after	drive	0.649473	109.502	3075293	0.00E+00	6.836558	0.425897	197.1036
after	parking	0.649473	119.7559	3403613	0.00E+00	6.836558	0.425897	215.5606
after	drive	0.494097	112.6465	2436231	0.00E+00	5.201021	0.324008	202.7637
after	parking	0.494097	123.9746	2720215	0.00E+00	5.201021	0.324008	223.1543
after	drive	0.338721	115.5957	1713770	0.00E+00	3.565484	0.222119	208.0723
after	parking	0.338721	128.3496	1944238	0.00E+00	3.565484	0.222119	231.0293
after	drive	0.183345	118.3301	934277.4	0.00E+00	1.929947	0.12023	212.9942
after	parking	0.183345	132.998	1071387	0.00E+00	1.929947	0.12023	239.3964

Exhibit 2. Plot of Temperature/Pressure

FIGURE 3-15 Density (P vs T)

Exhibit 3. Burst-tested Kevlar/Aluminum Pressure Vessel

Exhibit 4. Details of burst-tested vessel

Technical Evaluation Report
Project: PEM Fuel Cell Stack Project
Company: Los Alamos National Laboratory, Los Alamos, NM
P.I.: Dr. Mahlon Wilson
Date of Visit: January 26, 2000
Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

This R&D project at Los Alamos National Laboratory (LANL) deals with the development of components for small (3-5 kW) PEM fuel cells for home use. The components of interest are the bipolar plates, CO resistant anodes, and humidification devices. Much of what is being done on this project is in conjunction with LANL's CRADA partner, Plug Power.

The bipolar plates work appears to be the centerpiece at this time. It is a two-pronged effort that involves looking at both molded composite plates and plates based on metal alloy foils as alternatives to expensive, machined graphite plates.

The humidification work also seems to be progressing well, centered on the use of wicking threads to get water to the membrane. The status of the CO tolerant anode is less clear.

Project Strengths:

- The identification of PEMFC needs is very sound. The cost of the bipolar plates has long been considered to be a major obstacle to inexpensive fuel cells. Anode tolerance to CO is essential for hydrocarbon-based feedstock. An efficient humidification process is necessary to optimize membrane performance, especially at low pressure.
- Working with a respected CRADA partner lends credibility to the process. Plug Power provides that aspect. (A similar situation exists with LANL's other project, the fuel cell "battery", where the CRADA partner is DCH Technologies.)
- The entire bipolar plates effort seems well thought out, and covers sufficient options to maximize chances of success. A coated aluminum option seems particularly interesting. The humidification/near-ambient operation effort also addresses real system issues, and appears to be headed in the right direction.
- Materials handling and testing facilities and capabilities appear to be first-rate.

Issues that should be Addressed:

- There needs to be more of an understanding as to what the operating pH of the system will be under a variety of conditions, feedstocks, membrane types, etc. If metal alloy foils or coatings are going to be used for the bipolar plates, their corrosion testing conditions should be based on well understood, real-world scenarios. For instance, we would not want to see a potential inexpensive, effective alloy be eliminated because it showed poor corrosion conditions at a pH that a system would never see.
- The state of the CO tolerant anode work (or at least the manner in which it was presented to me) is somewhat uncertain. There is a plan to look at both anodes that will work with an air-bleed (lower tolerance) and without an air-bleed (higher tolerance necessary). It is not at all clear, however, as to what has actually been done, and what needs to be done.

Overall, the pluses far outweigh the minuses. This is a good project, headway is being made, and it looks like significant improvements to the PEM fuel cell will be realized.

II Introduction and Background:

I visited LANL on January 26, 2000 to assess the small PEM Fuel Cell Stack project. LANL is also working on a small PEM fuel cell “battery” for portable devices. I met with **Dr. Mahlon Wilson**, the team leader for the two Hydrogen Program projects at LANL, and with **Ms. Christine Zawodzinski**, who is a technician on the project. (LANL considers any technical person without a Ph.D., a “technician”. Ms. Zawodzinski possesses a Master’s degree in chemistry.) We spent nearly an entire day discussing the project and touring the Group’s facilities.

The CRADA that LANL has with Plug Power has just recently been signed. The tasks were written two years ago, however, and LANL is trying to “push” Plug toward steam methane reforming and membrane separation as opposed to partial oxidation (as was indicated in the initial task statements). They are currently in dialog.

Project Components:

Bipolar Plates

Bipolar plates are viewed as one of the most expensive fuel cell components. This is largely true because standard bipolar plates are made of intricately machined graphite. The machining is particularly cost intensive due to the incorporation of flow fields (paths for the reaction gases) in the graphite. LANL’s work on bipolar plates includes development of both composite and metal alloy replacements for the machined graphite plates.

Composite plates generally involve a thermoset or thermoplastic material with graphite filler to provide the conductive element. The thermoplastic version is more expensive,

primarily because processing includes cooling in the mold under pressure to avoid void formation. The material of choice is polyvinyl difluoride (PVDF), a very good barrier plastic that tends to be stable right up to its melt temperature. LANL is no longer working in this area, having handed the work off to a producer, SGL. Plug power's work with composite bipolar plates at this time, largely involves PVDF.

Thermosets that have been evaluated have been based on epoxies or vinyl esters. Epoxies are cheaper, but have poor elongation properties and need incorporation of plasticizers to improve this parameter. Vinyl esters, while having about the same tensile strength as epoxies, have inherent elongation capabilities of about ten percent. The vinyl ester plates also show greater tensile strength than thermoplastic plates. The thermoplastic plates are likely to break if they are dropped; the vinyl esters won't break.

The composite bipolar plate is about 1/8 inch thick, and weighs about 200 grams. Since the cost of raw material is a few dollars per pound, LANL has been looking for an alternative type of plate as well. They are focusing on a plate made of a thin metal alloy foil mounted on an inert polycarbonate backing. The foil, being only about two thousandths of an inch thick, adds little to the raw material cost of the plate.

LANL metal alloy work currently uses thicker samples, just to make it easier. Once a material is identified, they will look at having foils made. One method of getting foils that they are looking into is through a company called "Metal Samples." This company procures, processes, and provides samples of other companies' metals. Eventually, the plan would be to simply stamp flow-fields into the foil. For 2-mil thick foils, this should be quite easy to do. The real question may be whether the foils can stand up to clamping pressures of 700 psi. (The polycarbonate backing should help sustain the pressure.)

The alloy of choice for LANL right now is Ebrite 26-1 – an iron/chromium/molybdenum alloy that is showing very low corrosion amounts. The company that makes it, Allegheny Ludlum does not make it in foil form yet.

LANL is also looking at another metal option – coatings. For example, one could coat cast-aluminum with a bipolar coating. Dr. Wilson is excited about this idea, but recognizes several potential problems such as pinhole formation, adhesion, and conductivity anomalies. LANL is working with a company that develops these types of coatings, but wishes to keep the information proprietary at this time.

Coated cast-aluminum could ultimately be cheaper than (or at least as cheap as) foil with backing. Since aluminum would be more thermally conductive, this type of design might be good for stacks that require better temperature control. Better electrical conductivity would also be likely; this could lead to higher efficiency or more power. Finally, this type of design would eliminate the clamping pressure concerns of foils.

CO Tolerant Anodes

A major issue with all PEM fuel cells is the effect of carbon monoxide on the anode (hydrogen side) of the cell. CO presence lowers fuel cell performance and reduces the lifetime of the anode. Since much of LANL's work, especially with Plug Power, involves using mixed-fuel streams as well as hydrogen formed via partial oxidation processes, a high content of CO in the product stream is likely. There are three ways of dealing with this problem. One involves using a pre oxidation (PROX) step to reduce the CO content prior to feeding the mixture into the fuel cell. A shift reactor should reduce CO down to at least 1%. This product is fed into the PROX reactor, mixed with air, and run over a precious metal (such as platinum) catalyst bed. This process will bring the CO level down to less than 100 ppm, but reduces the overall efficiency of the process.

The second approach involves the use of an air bleed into the hydrogen stream. This reduces the effect of CO on the anode. It also causes a reduction in overall efficiency (about one percent efficiency reduction for each percent of air bled in) and also increases the safety risk should the hydrogen ignition limits be accidentally reached.

The third approach is the development of the CO tolerant anodes. The tolerance level is variable, based on whether the system has an air bleed or not. One CO tolerant anode system that LANL is looking at, which is proprietary, is to be used in a non-air-bleeding mode. While the system will work on up to 100 ppm CO, there are some aging problems with the anode alloy catalysts. At this time, they only have lifetimes of hundreds of hours.

If on the other hand air bleeds are allowed, you can get by without using a PROX reactor. Under these conditions, you would want an anode that could handle thousands of ppms of CO. Dr. Wilson does not believe that this can be done easily, but he says that LANL does have some catalysts that can handle 1000 ppm of CO for hundreds of hours.

The overall CO tolerant anode work is being performed in Dr. Tom Zawodzinski's "shop". There are three task leaders within this fuel cell group, one is Mahlon Wilson, a second is Tom Zawodzinski, and the third is Dr. Shimshon Gottesfeld. Dr. Gottesfeld is concentrating on direct methanol fuel cells these days.

Unfortunately, I was unable to meet with Dr. Zawodzinski for any length of time, and did not get a good feeling for the CO work.

Humidification

It is necessary to keep the membrane wet to ensure good membrane performance. The standard process is reactive humidification, that is, letting some of the water formed in the fuel cell recycle into the fuel feed stream. But this water is in vapor form, and the membrane's uptake of water vapor is limited. To get enough water vapor from the reaction to the membrane would mean running at a very high current density. LANL therefore believes that there are advantages to using liquid water to hydrate the membrane.

The LANL process involves distributing the water over the entire anode side of the plate, and then using porous, hollow wicks to transport the water to the membrane. This type of approach also allows for near ambient operation of the fuel cell, which results in a lower cost system, and one that is more efficient (fewer parasitic losses.)

III Tour:

Dr. Wilson and Ms. Zawodzinski took me on a tour of their facility. Most of their equipment is in one laboratory that they call the “Stack Lab”. The equipment in the lab includes:

- A computer-controlled positioning table/milling machine
An interesting little story here: They were not authorized to buy a “real” milling machine. But they could buy a positioning table, and mounted a hand-held mill on it.
- A computer-controlled embroidering machine. Accurate to 0.1 mm; used to incorporate the wicking threads.
- A 50-ton parallel plate press
- Three fuel cell test stations. A test station controls fuel cell temperature, supplies reactants to the cell, and monitors voltage and current. It contains two humidification bottles, pressure regulators, rotometers, cartridge heaters, and an HP 6060 load box. You enter a voltage, and the load box maintains it. You can measure cell resistance under load; you measure voltage and current to calculate resistance. You can tell if a cell is drying out.
- Two smaller stations (maximum of 60 amps and 300 watts) are currently being used for corrosion testing. One large station is used for large cells or stacks (up to 8 kW and “several hundred” amps). One can use this station to measure overall stack resistance.
- Several complete and partial fuel cells and stacks.
- A few small (10-50 W) fuel cell “battery” systems (the other LANL hydrogen project) for which they have a CRADA with DCH Technologies. One of the small cells was powering a radio.

I also saw the CO tolerance lab briefly. There were several fuel cell test stations here, perhaps six, but I saw no ongoing work. Dr. Wilson did mention that the ambient pressure work had not yet started.

The set-up for the direct methanol fuel cell laboratory is very similar to that of the “Stack Lab”.

The diagnostic equipment for the group is quite impressive. Among other equipment I saw an X-ray Fluorometer, SEM/EDAX, X-ray Diffraction system, sputtering chambers, an Instron tensile tester, FTIR, UV/Vis spectrophotometer, environmental chamber, GC/MS and an Atomic Force Microscope.

IV Questions and Answers:

I sent Dr. Wilson a set of questions that then became the basis for a major part of our discussion. These are shown, and discussed, below:

- 1. Is there any thought being given to direct hydrogen systems, where hydrogen is made from non-hydrocarbon sources? How would the LANL system be modified under those conditions? In what ways could the system be simplified? What, if any, additional problems might be incurred?**

Dr. Wilson repeated often that direct hydrogen is his preferred method of operation. It's "easier", he said. All of his work except the anode task is based on neat hydrogen. His ideal system uses steam reforming and membrane separation prior to use in a fuel cell (ala Northwest Power). He prefers the higher efficiency of this process to the Plug Power method of partial oxidation and stream clean up. *Despite LANL's alliance with Plug.* Dr. Wilson does not particularly like processes that are going to result in more CO formation, and require a higher air-bleed to preserve the anode. These processes result in higher parasitic losses and lower efficiency.

Interestingly, Dr. Wilson did not even consider "non-hydrocarbon sources" as the question stated. He looks at reforming as the clean system. The discussion continued, however.

Processing other species that contained a sulfur compound would likely be a problem (sulfuric acid would form, lowering the pH and potentially corroding the bipolar plates). Trying to make hydrogen from ammonia would create a special problem. The proton, rather than reaching the membrane, would react with ammonia, forming the ammonium ion:

The ammonium ion would clog the membrane, but it would eventually unclog, according to Dr. Wilson.

The concept of the membrane clogging, but eventually unclogging came up several times, especially in conversations about metal bipolar plates. I don't believe that an answer that the membrane will eventually unclog is a good answer. It likely won't unclog if it is in constant service, and periodic cycling means either down time, or increased material cost.

2. Roughly, what are the comparative costs associated with bipolar plates made from machined graphite vs. 316 Stainless Steel vs. “metal alloys more noble than 316SS,” both from an absolute dollars and a life cycle standpoint?

Overall, one could consider the cost of metal plates to be about 50 cents each. If the alloy were high in Ni, Mo or Ti, it would be a “little higher.” Composite plates would cost about \$1-2 each, with thermosetting vinyl ester-based composites being less expensive, and thermoplastic PVDF plates being more expensive. Machined graphite plates are 1-2 orders of magnitude more expensive than PVDF plates.

Graphite plates would last the longest, but the composite plates have considerably long lives as well. Graphite plates would be virtually unaffected by the fuel cell process. The only concern would be that a “dirty” graphite could reduce membrane lifetime.

With composite plates, the major concern would be the effect of water. Quite a lot of water could permeate the plates over ten or 20 thousand hours. The question is what effect will it have on the tensile properties of the plates? LANL is addressing that issue via a series of accelerated wetting tests. These tests are being done with methanol rather than water. Methanol wets out the plates quicker than water does, so one would expect to see any adverse effect sooner. Plates have been tested with methanol for 1000 hours to date, and no tensile changes could be seen. Testing continues.

Metal plates have not been tested in fuel cells to any great degree as yet. It is known, however, that they last for “years” in similar electrochemical environments. The membrane’s life, however, is somewhat compromised by the presence of metal ions from the metal plates. Life of the membrane can be extended if it is flushed, but some stagnant areas will remain clogged.

3. How long a lifetime would you expect for a membrane exposed to 316SS bipolar plates?

Dr. Wilson and Ms. Zawodzinski feel that a membrane exposed to 316 SS would be fine for a transportation application, where total usage would likely be under 2000 hours, but that it probably would not survive a 20,000 hour stationary power supply application. Other alloys such as the aforementioned E-Brite 26-1 looks particularly promising. Membranes exposed to this alloy have been tested for 1000 hours at 0.5 volts and 1000 hours open circuit, and appear to be still clean.

Dr. Wilson estimates a goal for the FC system to be 40,000 hours, but Plug Power touts 15 years as possible. Aside from contamination from metal bipolar plates (or “dirty” graphite plates, for that matter) a serious contamination source could be humidification water. The presence of calcium is the chief concern. Calcium could clog membrane functional sites at, perhaps, one percent per year.

4. If a membrane retains metal ions, can it be “recharged”, or does it need to be permanently replaced?

Theoretically, a membrane could be recharged by pumping nitric acid through it, and ion-exchanging out the clogging metals. The nitric acid, however, would likely passivate the metal bipolar plate surface. The LANL group is not seriously considering recharging of membranes.

5. You say that the 316SS plates are essentially corrosion free, yet the membrane picks up metal ions. Are you looking at corrosion in a “macro” sense as opposed to a micro (metal ions) sense, or could the ions be coming from another source?

Yes, it is a macro vs. micro situation. Corrosion effects reduce plate thickness by less than ½ micron per year (and thus the plate is visibly corrosion-free) but metal ions can be seen in the membrane using x-ray fluorescence.

Seeing that the presence of metallic ions in the membrane is the key parameter, it is probably misleading to emphasize the visible condition of the plate.

6. Is there any correlation between metal ions in the membrane and the source of hydrogen?

There may be a correlation if the reformat stream contained a large amount of CO₂, say 30%. This could result in the formation of carbonic acid, which would lower the pH and thus contribute to an increase in corrosion. Dr. Wilson feels that a pH of 4 would be enough to cause a problem. It is pH that causes corrosion problems far more than the nature of the input gas.

No effect on corrosion was seen on SS 316 when exposed to the chloride ion.

LANL are also aware of potential problems with exposure to hydrogen itself. They have found that nickel alloys resist corrosion from exposure to hydrogen better than stainless steel alloys, while the latter do better on exposure to air.

Dr. Wilson thinks that he may want to look at different foils for the anode and cathode sides, – say SS 316 for the cathode (air) side, and E-Brite 26-1 for the anode (hydrogen) side.

(As I write, I wonder why he said E-Brite 26-1. This is an iron-based non-nickel alloy (see equation 7). As such, based on the above comment, I would think it would be more subject to attack from hydrogen.

7. In Table 1 of your FY1999 Annual Review Report, can we assume that the balance of material for E-Brite 26-1 is Fe – that is, no Ni?

The sum of the elements presented for this material only added up to 27% -- 26% Cr and 1 % Mo. All other materials listed in the table showed complete compositions.

Correct. The balance is iron; there is no nickel present in E-Brite 26-1.

Minor point: I realize that LANL simply reported the assay as provided by Allegheny-Ludlum, the manufacturer, but an effort should have been made to identify the remaining elements and report it in the paper.

8. Is the pH range of 2-6 what is to be expected as the typical operating parameters of the fuel cell?

LANL has not ever seen pH=2 water coming out of their own stacks, but have seen reports that others observed these conditions. Dr. Wilson speculates that the acidic pH may stem from the presence of sulfuric acid-based species in the effluent. Under normal conditions, however, the pH shouldn't be any lower than about 6.

One exception may be found when Gore membranes (as opposed to DuPont membranes are used in the PEMFC. Gore impregnates their Gore-Tex membranes with liquid Nafion (which they buy from DuPont), and the liquid could leach out of the membrane and lower the pH. If the water is stagnant in spots, localized areas could see higher Nafion concentrations, and conceivably a pH of 2. *If this is the case, a better question might be: why use Gore membranes?*

Based on these reports and theories, LANL feels that pH=2 is one logical point at which to test.

I think that it is important not to overstate the likelihood of an acidic environment. While testing at pH=2 should continue in order to bracket likely conditions, it should not be used as a basis for eliminating alloy candidates that are "winners" under all other conditions.

9. You refer to the use of composite bipolar plates (in conjunction with Plug Power) as being a short-term solution. Why are they only a short-term solution? How do they compare cost-wise with the metal plates?

The composite hardware task is winding down simply because it has gone as far as LANL can take it. The "compounders" (two Midwestern companies -- "Premix" and "Bulk Molding Compounds" [BMC]) are working the problem now. Plug Power likes the composite option, but presently they are using machined graphite plates. The composite option is considered short-term because composites, while the price will come down when mass-produced, will never be as cheap as metal foil plates.

This assumes that metal foil plates will give the type of lifetime needed for stationary fuel cells.

10. How would composite bipolar plates “age”? Are there plans to do any testing in this area following the identification of a system?

A number of polymer systems would be affected by long-term exposure to water. If hydrolysis took place, tensile properties could be affected. Actually, this may not be a serious problem *per se*. The plates must have good tensile properties during assembly, but compression strength is the key during long-term operation. However, if hydrolysis causes the plates to start leaking, this is a serious problem.

LANL is currently running accelerated aging tests. Since methanol wets out the polymeric binder more quickly than does water, and the hydrolysis mechanism is similar, they can get a more rapid approximation of the effect of long-term exposure to water. They are also running tests at pH=2 to test the effect under these conditions.

11. What is your goal for CO tolerant anodes?

The goal is constantly moving because fuel processing is improving. It is probably better to consider two goals – one if air is being bled into the hydrogen, and one if it is not. It is desirable not to use an air bleed. Using an air bleed causes a decrease in overall efficiency by about one percent for each percent of air added, and also presents a potential safety issue if too much air is injected, the upper ignition limit is reached, and an explosive mixture leaks out. In addition, an air-handling system increases the overall system cost.

Fuel processing is getting more sophisticated. Using a Prox process, fuel cell feedstock gas can be supplied with an average CO content of about 20 ppm, with spikes up to 100 ppm. Thus, the goal is to have an anode that is tolerant to 100 ppm of CO without the need of an air bleed.

Recall that I did not talk to Dr. Zawodzinski at any length. Based on the conversation with Dr. Wilson, however, it seems that the major effort is to go away from an air bleed. This apparently will lock them into a Prox reactor mode. Dr. Wilson does not hold out much hope for the alternative system (no Prox with an air bleed).

12. Please explain the reconfigured anode. What is it made of? How is it reconfigured?

The reconfigured anode includes a backing – a gas diffusion layer. This modification improves CO tolerance, but its nature is proprietary. Dr. Wilson mentioned that this is a “very competitive” topic.

13. What partial pressure of hydrogen is necessary to achieve acceptable anode performance? – Or is the parameter that needs to be monitored the ratio of hydrogen to CO partial pressures?

Dr. Wilson gave the answer based on stoichiometry rather than partial pressure. With about 40% hydrogen in the feed stream (not including water), you want a 1.1-1.2

hydrogen to oxygen stoichiometry. If you have a lower hydrogen content, you would have to flow much faster, that is, use a much higher stoichiometry. The higher stoichiometry improves performance. You need the extra hydrogen to “push the inerts out of the way.” But the extra hydrogen could then be used for some other process. *Or presumably, recycled.*

If you had neat hydrogen (membrane separation or hydrogen from water) you wouldn't have these problems. Dr. Wilson is a proponent of membrane separation even though his project does not practice it. He mentioned Northwest Power's diesel reforming project as something that would benefit from membrane separation.

H₂/CO ratios do not affect performance. It's the actual amount of CO that is important.

14. What alternatives to the wicking method for hydrating the membrane were considered?

LANL also considered using tubes molded into the membrane and pumping the water through. The ability to keep the tubes open at high pressure, however, was the chief concern.

LANL is also considering running the water through the hydrogen flow channels on the anode-side plate (rather than over the entire plate), and then wicking over to the membrane.

I am not sure what advantage this last option would have. It appears to me that it would be more difficult to supply sufficient water and would be harder to control.

15. What material is the wicking thread made of?

The thread is a polyester material, specifically “Coolmax.” The fiber in the threads have a convoluted geometry that allow more efficient wicking. The thread is 50-denier multifilament and is wound with a thicker co-thread of cotton-polyester.

VI Additional Discussion:

- One of the LANL/Plug tasks is the systems-based humidification effort. Plug, however, seems to be backing away from this task, and apparently is moving toward their own proprietary humidification process.
- During our discussion on using ammonia as a source of hydrogen (see Question 1), Dr. Wilson wondered about the possibility of using ammonia as the fuel, and NH₄⁺ as the actual transport ion (an ammonium exchange membrane fuel cell).

Technical Evaluation Report

Project: Hydrogen from High Moisture Biomass in Supercritical Water

Company: University of Hawaii, Honolulu, HI

P.I.: Dr. Michael Antal

Date of Visit: March 9, 2000

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

The group of researchers at the University of Hawaii who are developing a method of gasifying biomass in supercritical water to produce hydrogen are led by **Dr. Michael Antal**. The project is several years old, and to date, Dr. Antal's group has developed a working reactor that is capable of accepting carbohydrate-based biomass and converting it to a syngas which is primarily CO₂ and hydrogen with some methane and a small amount of CO by reacting it with pressurized (4000-5000 psi) water at temperatures between 700 and 800°C in the presence of inexpensive carbon catalysts. They have found that they can produce the gas with very little coking, and have developed a process by which the coke and biomass-based ash can be removed from the reactor walls. The reactor is made of cast-alloy, a nickel/molybdenum based material that can withstand the high reactor pressure.

Dr. Antal's group have demonstrated that they can handle dry biomass such as sawdust by suspending it in starch gel, and can handle wet biomass such as potato processing wastes directly. They have shown that while the gasification process works well on cellulose and sugar-based carbohydrates, it does not work on other types of biomass such as sewage sludge. In fact, Dr. Antal questions whether sewage sludge can be classified as a biomass at all.

Presently, Dr. Antal is trying to obtain funding to further develop the process using potato wastes. A potato processing company in Richland, Washington, Lamb-Weston Corp., is interested in a way to get rid of their processing waste, and view the supercritical gasification process as a means to eliminate waste disposal costs and produce a usable, combustible gas as a bonus. The improved process would use a different composition reactor tube (likely zirconia, titania, or alumina) that would allow a somewhat higher temperature (and therefore higher hydrogen concentration) environment with less likelihood of corrosion than the nickel alloy. Since the proposed reactor materials will not adequately resist 4000-psi pressure, Dr. Antal proposes to encase the tube (or perhaps several tubes) in a carbon-steel pressure vessel. Dr. Antal claims that both the pressure vessel and reactor tubes are "off-the-shelf" items. *Dr. Antal, stating the above claims of off-the-shelf technology, took exception to analyses performed at NREL that indicated that the pressure reactor system would be prohibitively expensive. (I am not sure about the off-the-shelf feature. The pressure vessel itself may be off-the-shelf, but Dr. Antal has not either down-selected to a reactor tube type or even started testing choices.)*

Project Strengths:

- Dr. Antal is a dedicated, well-organized researcher. He has built systems that work. He has learned how to process slurry feedstock in a more or less generic manner so that they can be fed efficiently into the reactor; he has built, and proposes to build progressively more efficient reactor systems.
- Dr. Antal has the proper facilities for carrying out his objectives. His laboratory is a model of efficient use of space.
- The supercritical water experiment provides a medium that produces a minimum of unwanted byproducts such as coke. Furthermore, Dr. Antal has developed a process that will oxidize away the little bit of coke that does form without harm to the production gases or the catalyst. The other unwanted byproduct, ash, such as the alkali oxides that form upon gasification of potato wastes can be removed by brushing them out of the reactor (they are not fused to the reactor walls.) Dr. Antal has successfully demonstrated this process in small scale.
- The catalyst is simply carbon, not even necessarily activated. Charcoal works fine. Replacement of the catalyst bed is an inexpensive, easy process.

Issues that should be Addressed:

- First and foremost, the project has evolved in such a manner that I would no longer consider it a hydrogen project. Dr. Antal's arrangement with Lamb-Weston involves producing syngas from potato wastes, and then burning the syngas. Lamb-Weston is mainly interested in getting rid of the wastes. Getting a combustible material is a bonus. The syngas contains about 30 mole percent of hydrogen (presently, although the new design should increase this), but this does not make it a hydrogen project. It's a biomass project. Dr. Antal has asked Lamb-Weston to come up with ways that they could use actual hydrogen. Apparently there is a nearby refinery to which they could sell hydrogen, but this appears a bit of a stretch. There is no talk of how they would separate out the hydrogen. Maximizing (which is being proposed by Dr. Antal) and purifying hydrogen should be a major concern of any future work. Besides, Lamb-Weston is "perfectly happy" to burn the syngas.
- The coke and ash removal process, while effective at small scale, could become unwieldy in a larger, multiple reactor tube operation. Temperature control could be difficult.

This is, in my opinion, a good project; it's just not going down the road that parallels what the Hydrogen Program is looking for. A company such as Lamb-Weston will likely solve a major problem by employing Dr. Antal's reactor. There are very likely scores of other food processing companies, agricultural industry segments, and others who could benefit from this system.

Biomass contains a relatively small amount of hydrogen. As such, it is difficult to justify a project such as this if its primary goal is producing hydrogen. This particular program has evolved into one where hydrogen has become the afterthought. The entire Lamb-Weston concept is not a hydrogen-based concept.

II Introduction:

I visited Dr. Michael Antal and two of his co-workers, **Stephen Allen** (Junior Researcher and Member of the U Hawaii Faculty) and **Deborah Schulman** (Research Associate) on March 9, 2000, spending a full day with them, discussing the project and getting a tour of their laboratory including a dry run on each biomass reaction system present.

III Tour/Demonstration:

I was not given a demonstration of the supercritical gasifier in operation. Dr. Antal told me that it would take nearly a week to get it up and running at this point, and there was no funding to do so. *I'm sure he was trying to make a point, but it's a point well taken, and the meeting did not suffer greatly from the lack of the active demonstration. The dry run-through served nearly as well.*

The laboratory is very compact, and well set up. Half of the lab is set up for computers, analysis equipment, storage, and chemistry related tools. The other half of the laboratory contains four reactor systems.

The analysis equipment includes a Gas Sorption Analyzer that provides BET porosity measurements. This is rarely used for the hydrogen work; it is primarily for activated carbon studies. In addition, there is a GC/Mass Spectrometer and another gas chromatograph. There is also an HPLC that is used primarily for Dr. Antal's ethanol work.

The series of reactors include:

1. Their "old" reactor that operated at less than 1000 psi and at about 250°C. It is currently being refurbished to be used in the making of activated charcoal from the reaction of biomass in hot water.

In its original use, the reactor was used to make ethanol from sugar cane bagasse (stems), sugar cane leaves, corn fiber, southern pine, pine bark, or aspen wood chips. The batch reactor is about two inches in diameter; biomass (10 – 30 grams) is placed in a cage, and lowered into the hot water. Product can either be emptied from the reactor bottom, or pumped into a tank.

This reactor was the precursor to reactor #3 (below).

2. A reactor that is used to make charcoal from biomass. It operates at about 300°C and 150 psi (but can be used at pressures up to about 1000 psi). It includes a power boiler

and power reactor, built to code. This reactor produces theoretical yields of charcoal – about twice what industry gets.

3. A reactor that is used for the ethanol work. This work is being funded by the National Science Foundation (NSF), the Consortium for Plant Biotechnology (CPBR), and BC International (BCI). The work is being performed by U Hawaii, and Dartmouth College. Dr. Antal's group does the biomass pretreatment work in this reactor, and Dartmouth does the fermentation.

The premise here is that if the temperature and pressure is high enough, you can use water alone to run the pretreatment step. Dr. Antal's group runs the reactor at 210-220°C and 335 psi, immersing the biomass in the water for one or two minutes. This dissolves (but does not react) all of the hemicellulose and about half of the lignin. This pretreatment product is then sent to Dartmouth for fermentation.

This reactor was built to have the features of a commercial process. Instead of a hot water tank, a full-scale boiler is used. (All safety issues are met.) Steam from the boiler preheats the 8-inch diameter reactor. The feed can be up to 2 kg in weight (wet), but is generally run with about ½ kg.

One kg of dry bagasse will eventually produce about 400g ethanol.

Both the charcoal reactor and ethanol reactor are run in semi batch mode to make the feed process easier.

4. The “present” hydrogen reactor. It is based on a design by Modell at MIT who used this type of reactor to burn Department of Defense generated waste in supercritical water. Dr. Antal states that in the U Hawaii case, they are using the reactor to “synthesize, not destroy.” Originally, Dr. Antal used the reactor to convert ethanol to ethylene for the National Science Foundation. During that study, Dr. Antal discovered that the supercritical water dissolved biomass without char formation. Thus started the wet biomass project.

The system does not use a boiler – just a high-pressure reactor (a ¼-inch tube), so no permitting is needed (the boiler people are not interested – there is not enough material here to constitute a safety concern).

The feed system is simply an open cylinder. A piston is placed into the chamber, and a combination of sawdust and starch gel (or potato waste without the starch gel) is placed into the upper chamber. Water is pumped into the lower chamber, or for ease of handling at this scale, the cylinder is flipped over, and the water is filled from the top. The overall feedstock is 15% solids – 10% sawdust and 5% starch gel.

The cast-alloy reactor is heated by a three-zone furnace to about 700°C. Additional heaters are used at the entrance and exit of the reactor tube to get a quick temperature rise, and to minimize heat loss. Fifteen computer-monitored thermocouples are

mounted on the outside of the reactor. The catalyst bed extends about ten cm into the reactor on the aft end, with air also entering through an aft end annulus.

The feeder is pressurized to 4000 psi with water, as is the reactor. The process starts by just running the pressurized water through the reactor until the temperature profile is stable. At this point, the water is turned off, and the feeder is opened.

A sixteen-port gas-sampling valve provides gas samples to a gas chromatograph (they monitor CO₂, CO, hydrogen, CH₄, and light hydrocarbons. They also monitor CO₂, CO and CH₄ by infrared detection.

A typical feed cycle is 1-2 hours, and is finished by switching off the feed, and back to water to react the residual feed, and then bring the pressure down, still holding the temperature at 700°C. They then burn out carbon deposits with low-pressure air, monitoring the CO₂ concentration. When that value is down to about 0.2%, they insert a brush manually to break up ash deposits, then blow air through the system again.

They have made runs lasting up to about eight hours (6-7 cycles) and were still going strong when they stopped. There was no evidence of catalyst degradation. Gas yield does not decrease between the cycles, but does decrease within a cycle probably because the deposits on the reactor walls reduce heat transfer.

IV Questions and Answers:

A large portion of our discussion time was spent going over a series of questions that I had sent Dr. Antal prior to our meeting. Dr. Antal sent back a series of answers prior to my trip. These are shown below, as is the additional discussion we had on each of them.

1. With a much-varied set of biomass raw materials being proposed, what differences do you see rising as potential technical problems? How do the differences in type, availability, and cost (positive or negative) of biomass mesh with potential markets.

“Our proposal only concerns the gasification of potato wastes. We are interested in other food processing wastes, other wet biomass, and biomass in general (e.g. wood sawdust), but our focus for the next few years is the gasification of potato wastes”.

Dr. Antal at first was looking for a representative biomass, and thought of wood sawdust as being representative of a biomass that would be difficult to work with. How do you feed dry sawdust into a reactor at 4000-5000 psi? Dr. Antal also pointed out that sawdust has large markets already such as the particle board market and the charcoal market. There are not a lot of people trying to find a way to get rid of sawdust. *Then why pick sawdust? I suppose if you find that you can feed sawdust, you can feed anything with a little preprocessing. So it's probably a good technical choice, albeit a poor economic one.*

In trying to find something that people are trying to get rid of, Dr. Antal's group then focused on sewage sludge. This is a good economic choice, but turned out to be a bad technical one. Sewage sludge (and most non cellulose-based materials) does not gasify by the supercritical water process. Therefore, the group turned to vegetable food wastes. They are carbohydrates, and people usually need a way of disposing of them. They settled on potato wastes, mainly because they had a customer – Lamb-Weston.

2. What are transportation costs of wet biomass? Do you foresee a centralized gasification plant or dedicated distributed plants?

"Potato wastes are available in Lamb-Weston's factories. We foresee a gasifier located in each factory. There is no transportation."

It is expensive to move biomass, especially very wet biomass such as the potato wastes. This is why Lamb-Weston cannot sell potato wastes to hog farmers, for instance. It costs too much to ship.

3. Starch gel – does this produce hydrogen as well? How much? If you are using a feedstock that is 10-20% solids, doesn't much of the hydrogen come from the carrier?

"The gasification of starch gels is thoroughly described in our paper. Our proposal does not concern the gasification of starch gels."

Of course I knew that starch gels would produce hydrogen. I was trying to get Dr. Antal to tell me that a significant portion of his hydrogen is from starch gel. When he has to use starch gel, such as with sawdust, his feed is nominally 10% sawdust, 5% starch gel, and the rest water. If he tries a higher solids loading, he cannot pump the material, and he cokes the reactor as well.

Of course, Dr. Antal's present (and proposed future) work concerns potato wastes which don't require an additive.

Dr. Antal considers the applicability of starch gel for biomass suspension as somewhat of a "miracle". Oily additives such as coconut oil do not gasify.

Dr. Antal also commented that there is no plan to use starch gels in the future. It was just part of a proof of concept experiment with sawdust. It's not an economically viable option.

So what is it, a miracle or a curiosity?

4. Does the starch gel basically serve as the only additive you need for most biomass systems? How generic is the processing of the feedstock?

"No additives are needed for potato wastes. Starch gels are needed to deliver sawdust to the reactor."

If you do need an additive, starch gel appears to be more or less generic. No additional additive is needed. The only stipulation for successfully using starch gel is that the feed must have an essentially neutral pH.

- 5. You indicate that you can perform steam reforming using this process at temperatures below 800°C, but state that the process will produce more hydrogen at temperatures above 750°C. – Would they produce even more hydrogen at temperatures above 800°C? – or is the process maximized at some temperature between 750 and 800?**

“Thermochemical equilibrium calculations indicate that higher temperatures improve hydrogen yields. The reactor described in our proposal can easily be run at temperatures above 800°C to determine how much improvement is realized at higher temperatures.”

The problem is that their cast-alloy reactor cannot withstand the higher temperatures. It loses its strength and “balloons” as well as corrodes more rapidly. Dr. Antal’s new proposed reactor tubes will not corrode at the higher temperatures, but cannot withstand the 4000-5000 psi pressure. Thus, the carbon steel pressure vessel to maintain the tube integrity is needed.

- 6. Releasing the air into the region in front of the carbon bed so that it oxidizes char at reactor entrance rather than oxidizing the bed – how close to 100% is this? Is any catalyst lost?**

“We are unable to measure any loss of bed carbon. The gas in the bed is stagnant. Little oxygen should be delivered to the bed by the airflow. In any case, in a practical reactor the catalyst would be charcoal, which is very cheap.”

The material that is being formed is coke (from condensed reaction gases), not char. It burns off very easily. Dr. Antal does not know, however, if the process is practical. This is something he hopes to learn from the Lamb-Weston work.

Both the coke and the ash form near the reactor entrance because it is a somewhat cooler region. The gases condense to coke at the lower temperatures, and the ash precipitates out of the steam, being less soluble at these temperatures. If it did happen to carry down to the catalyst, it’s not a big problem. Charcoal is inexpensive.

- 7. How will the carbon deposit and ash removal described for the reactor translate to real world sizes and situations? Do you visualize a modified batch mode process using a bank of reactors where a reactor is shut down and cleaned every few hours on a staggered basis?**

“This is the most important issue that we face. Potato waste is about 10% ash (dry basis). If we feed 100 lb. of potato waste (on a dry basis) to the reactor, we will accumulate 10 lb. of ash. So we must remove this ash from the reactor. Our idea is exactly what you describe. Several reactors will operate in parallel within one large pressure vessel. When one reactor plugs, it will

be shut down, cleaned, and restarted while the others continue to operate. This cleaning will be done in a sequential manner.

"I understand that the panel of reviewers was skeptical of this approach. In response, I emphasize that life could have been tougher. We were delighted to discover that the carbon (coke) accumulation in the entrance of the reactor is extremely reactive and burns quickly and easily in flowing air. If the carbon accumulation had not burned easily, I would have abandoned this work! Likewise, we were delighted to discover that the ash is trivially removed from the reactor by a light brushing, followed by a burst of air. If the ash had fused to the side of the reactor, I would have abandoned this work! In summary, we could hardly have hoped for a better situation."

This is indeed a batch process that would be made pseudo-continuous by having multiple reactor tubes (about one inch in diameter each) located parallel to one another inside the one foot diameter, 30 foot long pressure vessel. It may be necessary to water-cool the pressure vessel if it is affected by the heat of many reactor tubes, but the resultant hot water would perhaps be usable. Dr. Antal visualizes a situation where one (or more) tube(s) can be in a burn-out or brush-out phase while the other tube (or tubes) is in reaction mode.

The one-inch diameter reactor tubes is probably a limiting factor. Any larger, and they are no longer off-the-shelf. In addition, larger tubes would probably be less efficient from a heat-transfer standpoint. Heat transfer time is proportional to the square of the radius of the reactor. If you heat the biomass too slowly, you'll make charcoal.

I am not too confident of being able to manage such an unwieldy system, especially with a manual "brush out" component. I think temperature control may be a nightmare.

8. One of the key "hooks" of this project is the minimization of char and tar formation in the presence of superheated water. Yet char cleanup still appears to be a major issue. Where is the gain?

"The gain is carbon gasification efficiencies that approach 100%. The formation of "tar" and "char" is very small relative to any other gasifier. This point is discussed at greater length in our paper."

Dr. Antal also pointed out that since ash will be formed, a clean-out step is necessary anyway.

9. Explain change in catalyst BET and packing density after run. If you assume that the loss in surface area occurs throughout the run, you would expect hydrogen yield to decrease correspondingly. Yet hydrogen yield per cycle does not change even though you would expect a much lower BET for, say, cycle 5 than cycle 1. Please explain.

"As emphasized in all our papers, the surface area of the carbon is inconsequential. Biomass charcoal is a better catalyst than activated carbon. The outer surface area of the charcoal (which has virtually no pores) is more than adequate to catalyze the tar gasification reactions. We only

use activated carbon because it is convenient: it is homogeneous, and already ground to a convenient size for us.”

Then, I guess, it's not really necessary to measure BET or other surface measurements.

10. If the catalyst surface and density characteristics change so much after one eight-hour run, how will this be dealt with on a practical level? Change out the catalyst for each run? Recharge it?

“As mentioned above, the change in surface area of the carbon is inconsequential. If our proposal is funded, we will test the life of charcoal catalysts with potato waste feed. In any case, charcoal is cheap, and can be burned for disposal and energy recovery. If it is necessary to clean the reactor of ash every few hours, it will not be difficult to replace the charcoal catalyst once a day (for example).”

This is a little out of phase with Dr. Antal's statement that he couldn't show me an active system, because it would take a week to get it running. Perhaps it would be a bit harder to clean the reactor ash and to change the charcoal than anticipated.

11. What percentage of hydrogen present in the waste material do you expect to recover from the new reactor both before and after consideration of recycled hydrogen to provide heat to the system?

“We estimate that about 30% of the combustible gas products must be burned to run the gasifier. Thus, about 70% of the energy content of the feed will be available. It is possible that none of the hydrogen will be burned. If a gas separation system is employed at the exit of the reactor, combustion of the methane product may be enough to fuel the gasifier.”

This is the only mention of gas separation. If we are going to deal with hydrogen instead of syngas, we need a separation system.

12. I understand that in some of your earlier work, there was a controversy regarding some sampling and storage techniques. While it appeared that the storage techniques were not compromising the results, I am not as sure as to the sampling techniques. I recall seeing several data tables indicating that air might have been leaking into the system during sampling. If this were occurring at high temperature, there is the possibility of additional oxidation occurring. Was any attempt made to quench any reaction in the sampler and/or has the system or technique been modified so that air no longer leaks into the sampling system?

“The gas sampling has always been done at room temperature. Air is not a problem at room temperature. If our proposal is funded, we will be using a 36 port sampling valve to take gas samples at room temperature. Air will not leak into this valve.”

This puts to rest the only concern I had with leakage.

VI Additional Discussion:

- We have been talking about materials that can be successfully gasified by the supercritical water process as being carbohydrates. Dr. Antal likes to consider successful materials as those that can be fermented to ethanol, that is, it contains sugars. *This ties in well with one of Dr. Antal's other projects which we talked about earlier – his preparation of fermentation precursors.*
- The FY 1999 Peer Review Team stated about this project, even if it were fully successful “it still would run up against the same 5% hydrogen from biomass barrier.” That’s life; dry biomass contains nominally 5% hydrogen by weight. Dr. Antal reports his yields in grams of gas produced per gram of dry biomass solid, and in mole fractions of the product gases. He has reported total gas yield of up to about 1.3 g of gas per gram of feed solid, and shows nominal relative product mole fractions of 0.3, 0.02, 0.44, and 0.23 respectively for hydrogen, CO, CO₂, and methane. (*Mole fractions always make hydrogen look better!*) If we perform the calculation to convert to grams of hydrogen, we find that Dr. Antal is recovering about 0.032 grams of hydrogen for each gram of biomass feedstock, or about 65% of the hydrogen present. I have attached an appendix with the details of this calculation. If Dr. Antal can produce hydrogen at a higher temperature using his corrosion resistant reactor encased in his pressure jacket, he could recover more of the biomass hydrogen, and perhaps actually pull some of the hydrogen off the water (with the proper catalyst).
- Dr. Antal mentioned that the Codes and Standards (C&S) situation in Hawaii is rather unusual. For boiler-related work (and some of the reactors have boiler components) only boiler inspectors are allowed to have the C&S books. It is difficult for his group to maintain a proper collection of C&S literature.
- Potato waste is one of the more difficult materials to work with because of the amount/type of ash – it’s high in alkali content.
- Dr. Antal is concerned about the NREL process analysis that was based on a commercial plant, and did not consider the fact that a cast-alloy reactor is low-cost.

VII Final Thoughts:

Using typical values supplied by Dr. Antal in some of his reports, we calculated approximate efficiency of converting biomass to hydrogen.

1.3 grams of gas evolved from 1.0 grams biomass solid.

Mole fractions of gases evolved:

H_2 :	0.3
CO:	0.02
CO_2 :	0.44
CH_4 :	0.23

A total of one mole of gases would mean:

H_2 :	$0.3 \text{ moles} \times 2 \text{ g/mole} = 0.6 \text{ g}$
CO:	$0.02 \text{ moles} \times 28 \text{ g/mole} = 0.56 \text{ g}$
CO_2 :	$0.44 \text{ moles} \times 44 \text{ g/mole} = 19.36 \text{ g}$
CH_4 :	$0.23 \text{ moles} \times 16 \text{ g/mole} = 3.68 \text{ g}$

Total weight of one mole of gas would be 24.20 g

So 1.3 g of gas is equal to a composite $1.3/24.20 = 0.054$ moles of gas, of which 30% is hydrogen. Thus, $0.054 \times .3 = .0162$ moles of hydrogen. At 2g/ mole of hydrogen, this equals 0.324 g of hydrogen produced for each gram of biomass processed. If the biomass composition includes 5 % hydrogen, the hydrogen production efficiency is about 65%.

Technical Evaluation Report

Project: Hydrogen Storage Using Lightweight Tanks

Company: Lawrence Livermore National Laboratory, Livermore, CA

P.I.: Dr. Fred Mitlitsky

Date of Visit: March 21, 2000

Evaluation by: Edward G. Skolnik, Energetics Inc.

I Summary:

Dr. Fred Mitlitsky is responsible for two somewhat related projects at Lawrence Livermore National Laboratory (LLNL) – one involving the development of regenerative fuel cells (RFC), and the other involving the development of lightweight tanks for hydrogen storage. In the tank area, the emphasis is on liner development for vehicular hydrogen storage, and it is in this area that we focused our visit. The liners serve as barriers to hydrogen permeation and also as mandrels on which to wrap composite tanks.

Quite a lot of work has been done in the liner area over the past few years. Dr. Mitlitsky's group has tested and/or characterized some fifty material candidates as to hydrogen permeability, and has assessed leading candidates for strain, toughness, corrosion resistance and processability as well. A high density polyethylene has emerged as the leading candidate to this point. LLNL, is trying to improve the system by adding a coating (polymeric or metallic) to the inside surface of the liner. This would decrease hydrogen permeability and would allow for a thinner overall liner system.

This is an important project. Advanced compressed hydrogen tanks are very likely to be the near to mid term (*at least*) answer for on-board hydrogen storage.

Project Strengths:

- Dr. Mitlitsky and his group appear to have correctly identified the goals of high pressure storage, and are attacking them in a proper, well thought out manner.
- The team appears to be a good one.
- The focus on lightweight liners is the right direction for this overall effort.

Issues that should be Addressed:

- To date, the results appear to indicate that no single polymeric system will meet permeability requirements and be easy to process. Dr. Mitlitsky has indicated that there are a lot of potential alternatives (metal coatings, "paint-on" polymers, use of dicyclopentadiene). They need to be developed and assessed.
- Results are presented in far too complex a manner; they need to be simplified.

- An overall cost-benefit comparative analysis is needed at a stated safety level.
- More material aging studies are needed. These really need to be done in a hydrogen atmosphere.

II Introduction and Background:

I visited Dr. Mitlitsky and two of his co-workers, **Dr. Andrew Weisberg** and **Dr. Blake Myers** on March 21, 2000, spending the better part of a day with them, discussing the project and getting a tour of their laboratory.

The major emphasis of our meeting was the discussion of liner materials and systems that are being identified/developed at LLNL. Dr. Mitlitsky states that they can achieve a 12% hydrogen loading using a polyethylene-lined composite-wrapped tank. It can hold 5000 psi hydrogen, and has a 2.25 safety factor.

The key parameter, however, is permeability. Permeability units are derived from a gas transmission rate (e.g., moles per square meter per second), for a given material thickness and a given pressure.

In determining what the permeability rate should be, a comparison was made to a natural gas vehicle (NGV) specification. This spec stated that for natural gas at 3600 psi, the permeability should be no more than 0.25 standard cc per hour per liter of tankage. At this rate, natural gas leaking into a stagnant, closed standard garage would take three years to reach the lower flammability limit (5%). Based on this, LLNL believes that their goal for a 5000 psi hydrogen tank should be 1 cc per liter of tankage.

III Tour:

- The laboratory possesses a RFC test rig, on which “all kinds of” RFCs can be tested. Hydrogen can either be produced from water (in the electrolyzer mode) or can be bottled hydrogen. One can add impurities either to the hydrogen (cathode) or oxygen (anode) gases if desired in the test. The rig is currently not operational; safety features are being repaired. In addition, the RFC work is not funded during the current (1999-2000) fiscal year. (Dr. Mitlitsky is trying to obtain RFC funding from the Defense Advanced Research Projects Agency (DARPA).)
- Dr. Mitlitsky showed me a small RFC that produced hydrogen in the electrolysis mode (he demonstrated burning the hydrogen) and produced electricity (turned a propeller) in the galvanic mode.
- There were also assorted liners, cases, and parts of both in various states of completion throughout the laboratory.

IV Questions and Answers:

A large portion of our discussion time was spent going over a series of questions that I had sent Dr. Mitlitsky prior to our meeting. Dr. Mitlitsky had prepared a set of written responses, and these were referred to often during our discussion. The written responses are included in this section:

For questions directly related to the FY 1999 Annual Review Report prepared by Dr. Mitlitsky, the reader is referenced to <http://www.eren.doe.gov/hydrogen/pdfs/26938ll.pdf>

1. Please explain the philosophy as to why a storage system that is more likely to be vehicular, and the regenerative fuel cell, that is more likely to be stationary are considered as a unit.

“Regenerative fuel cells (RFCs) have vehicular applications as well as stationary applications. In fact, this line of research (RFC systems with lightweight tankage) began as a result of starting with a clean sheet of paper and determining which high cycle life energy storage system would be optimal (from mass considerations) for vehicles. Vehicles designed around RFC systems with lightweight tankage have comparable cost to vehicles designed around primary fuel cell powered systems. Unlike primary fuel cell powered systems, vehicles with RFC systems carry their infrastructure onboard the vehicle. Therefore, RFCs do not require an extensive hydrogen infrastructure for initial market penetration. RFCs can be electrically recharged or rapidly refueled.

“Many classes of vehicles would benefit from closed cycle energy storage (e.g., indoor service vehicles, mining vehicles, high altitude aircraft, spacecraft, some boats, some offroad vehicles, some construction vehicles). This is similar to the niche for secondary batteries, which primary batteries cannot replace in many applications due to cost and logistics. To build closed cycle energy storage for vehicles requires the highest performance storage systems, without a superior storage system these options fail.”

This may be, but I don't believe that the RFC project (at least at first) had anything to do with vehicles.

2. Is the cryogenic tank that Salvador Aceves is working on simply a totally different concept, or are there any overlaps with the lightweight liner/tank project?

“There is only modest overlap between Salvador's cryogenic tank project and the lightweight liner/tank project. Although the components for the pressure vessel inside Salvador's storage approach have the same names as the components of a lightweight tank, they face much more stringent operating specification. Due to huge technical risks, Salvador has not been able to innovate on these components, having found a relatively heavy option already in production. Instead his research activity must focus on heat loss and insulating systems outside the pressure vessel, in contrast to our effort focuses on weight and hydrogen permeation.”

Dr. Aceves could conceivably use some of the same materials to make a plastic-lined tank. Dr. Mitlitsky thought that dicyclopentadiene might be applicable for the cryotank. This might decrease overall tank weight.

You can compare hydrogen losses from a compressed gas tank, to liquid hydrogen boil-off. Dr. Mitlitsky believes that if his liner is 0.15 inches thick, his tank will have a half-life of 6 months. Hydrogen in a cryotank would not last as long.

There appears to be very little overlap. It seems to be two storage projects that happen to be at the same laboratory.

3. You stated in your FY 1999 Report that metal liner options will “poison RFC systems.” How will this happen?

“The statement from the FY 1999 Report is “Without extreme caution concerning the management of residual moisture, the available metal liner options can poison RFC systems.” This statement is relevant to hydrogen sources which may have more than negligible amounts of water contained (e.g., electrolytic hydrogen production which does not have adequate drying of the gas stream). Moisture in the gas stream can react with some metal liners (e.g., aluminum or some grades of steel) and leach metal ions into the gas stream. These metals can poison PEM fuel cells and reduce lifetimes or performance.

“The term ‘poison’ refers to the inactivation of catalysts, although in the case of PEM, it can also refer to the occupation of sites responsible for proton transport. Industry experience has failed to confirm the irreversibility of poisoning, although it has compiled a large laundry list of ions incompatible with the intrinsically long service life of PEMs.

“If care is taken to use tank liner materials that are compatible with PEM fuel cell plumbing, or if water is prohibited from collecting in the hydrogen storage tanks (e.g., by assuring that only dry hydrogen is stored) and if water is prevented from forming in the hydrogen container (e.g., by preventing low levels of air or oxygen from entering the hydrogen tank), then liner material choice does not need to be constrained by compatibility with water and/or fuel cell plumbing.”

Dr. Mitlitsky believes that it is better to use liner material that is not affected by moisture than to worry about poisoning. I would agree.

4. Why is your data normalized to MDPE for hydrogen and HDPE for oxygen? Since MDPE data appears to be available throughout, why not use it as a baseline for everything?

“The data presented in the FY 1999 Report “Table 3. Literature Survey of Some Polymers Considered for Tank Liners” was generated primarily by comparing to reference data in “Modern Plastics 1991 (Mid-October 1990 Issue Vol 67 (11), pp. 592-6 for Film & Sheet (supplemented with pp. 480-528 for Resins & Compounds)”. This reference did not have both hydrogen and oxygen permeation data for HDPE, which is a marginally superior permeation barrier compared with MDPE (note that oxygen permeation is ~35% greater in MDPE compared with HDPE). In fact, HDPE was chosen as a baseline material for liner development, so it is the relevant data for comparison within this program which is focused on developing hydrogen tankage. Oxygen data is presented because it was readily available, and well-funded RFC programs might be interested in storing oxygen. At present, nobody is paying for oxygen permeability data collection (except proprietary data in the food wrap industry), so there isn’t much published on materials (e.g., polyethylene variants) that might be more suitable for tank liners. Although I agree in principle that a good choice for a baseline should be the same for both gases, for this program HDPE is the relevant baseline.”

The Table is shown in Exhibit 1. For the liner program, we should just concentrate on HDPE. This has become the baseline material at any rate. Anything that has shown lower permeability has failed on other grounds.

5. We need to discuss the permeation testing methodology shown in Figure 8 of your FY 1999 Annual Report. (The figure is hard to follow.)

“Figure 8 - Schematic and Photos of Permeability Test Fixture at SRI shows a permeability test fixture at SRI which is capable of screening a wide variety of liner candidates for permeation as a function of delta-P up to 5 ksi (34.5 MPa). Tests can be performed at various temperatures, induced biaxial strains, and using several different gases, including hydrogen. These tests are effectively a modified version of the ASTM gas transmission test using a Dow gas transmission cell (ASTM Designation: D 1434-82, section 9.1, 1982, Philadelphia, PA). The ASTM test is strictly defined at low delta-P (~30 psi). However, some materials exhibit unexpected permeation characteristics at high delta-P (~5 ksi), which is more representative of the design point for hydrogen tanks.

“In addition, permeation tends to be exponential with temperature, so elevated temperatures can be more indicative of worst-case design points for hydrogen tanks. Some materials also exhibit increased permeation as a function of strain cycles (that result from pressure cycles and temperature cycles to a lesser extent). A rather large database of hydrogen permeation data has been collected on this apparatus for various materials as a function of temperature, delta-pressure, and biaxial strain.”

The Figure is reproduced here as Exhibit 2.

6. Figure 9 in your 1999 Annual Report seems to indicate that permeability is actually decreasing with increasing pressure for several materials. Please explain.

“Figure 9 - Measured Hydrogen Permeability of Several Candidate Liner Materials, does show that permeability decreases with increasing delta-pressure for several materials, most notably HDPE. This phenomenon is not completely understood, has been seen by other groups, and might be due in part to the increased compressibility of some materials at higher delta-P. One possible explanation is that the increased compressibility could reduce the size of more permeable micropores within the material and thus reduce the induced permeability at higher delta-P. Note that even in cases where the permeability of the material decreases with pressure, the actual permeation (or gas transmission rate) still increases with pressure.”

The Figure is shown in Exhibit 3.

It's best to track both permeability and permeation.

7. The same report indicates that some life cycle tests are being conducted. Have any real time or accelerated aging tests been conducted (or planned) that look at mechanical properties and permeability?

“Three different tests have been performed to study mechanical properties and permeability as the tank ages:

“Accelerated stress rupture, as defined by NGV2 (hold a tank at 125% of service pressure for 1,000 hours at 65 °C).

Leak test, ambient pressure cycle test, and repeated leak test. Mechanical tensile tests at temperature and various strain rates. This data will allow us to calculate the fatigue properties of

the liner material. Can also predict creep and life expectancy of materials. A separate program was undertaken to predict the time effect of the compression set of Nitrile O-rings.

“Direct testing of cycle life issues has only taken place on integrated vessels. These tests were performed in house at Thiokol as part of a risk reduction effort to make sure this line of development could pass NGV2. When may experimental tanks with nylon liners failed cycle life tests, an in-house research program was funded at Thiokol to calibrate and predict cycle life. That program acquired strain cycles to failure on ‘dogbone’ test specimens, produced one excellent retrodiction (prediction of an experimental result already in hand) of nylon tank cycle life, and was abandoned due to lack of specifically useful predictions for the cluster of HDPE liner materials now used as a baseline.”

I think the tests that are lacking are ones that need to be done in a hydrogen atmosphere, or after materials have been aged in a hydrogen atmosphere.

8. Have physical property tests been carried out as a function of temperature?

“Permeability and tensile properties have been obtained at -40 °F, room temperature, and +180 °F. These results are limited to the best candidate materials, while the room temperature results have been accumulated for a much wider range of plastics in order to find the best candidates.”

9. What are the goals for the properties being tested?

“Obtain permeation, mechanical characterization, and life cycle data for design and analyses. Obtain more data as necessary to design a tank liner which serves as an adequate barrier with minimal weight. Numerous materials property issues have arisen in the development process that required the extension of this testing program, and future developments of even thinner liners might require additional measurements that we cannot currently justify (financially) at this time.”

Goals of 2×10^{-16} moles per square meter per second for permeability at room temperature and 5000 psi will allow a reduction in liner thickness below the 0.3 inch baseline value. Trying to get better than this would likely compromise other considerations such as processing ease, temperature dependence, etc.

Strain goals are 1% for thousands of cycles.

To meet natural gas vehicle goals (NGV2), they need to show the ability to cycle 15,000 times. LLNL has the capability of performing 10 cycles per minute. They use water as a recycling fluid, as it is much safer than gas.

10. Has any down-selection been performed as to liner material? If so, to what material(s)? What are the relative strong and weak points of these materials?

“Cross-linked high-density polyethylene (XLPE) is our baseline material at this time. No other polymeric material has shown better permeability that can be fabricated into a lightweight high cycle life tank. Other polymer material with lower permeability are brittle and/or require extra processing or protection methods. High cycle life tanks using metal liners tend to be heavier and more expensive than tanks with polymer liners.”

Other than polyethylene, the only material that looks somewhat promising at this point is dicyclopentadiene (DCPD). It has many superior properties (toughness, corrosion resistance, wider temperature range, ease of processing), but is not as good a barrier as polyethylene. LLNL is currently looking at “treated” versions of DCPD to reduce permeability.

11. Your FY 2000 AOP submission indicates some planned work with permeation inhibition coatings. Have materials been identified? What type of testing has been done, or is planned?

“Yes, candidate materials have been identified. These include “paint on” layers of low permeability polymers onto molded polymers. We are also examining plated metal coatings onto molded polymers. Samples have been prepared with one paint-on and two plated coatings. Another batch of perhaps two coating approaches will also be assembled shortly. All of these specimens are headed for the SRI permeation testing apparatus. Plans are underway at Thiokol, under an existing (small) DOE-funded contract, to permeation and burst test an integrated 12” vessel with plated liner.”

This work, I believe, is critical to the success of the project. It does not appear that polyethylene alone (or perhaps any polymeric material alone) will be satisfactory for meeting goals.

12. Is the liner chemically bonded to the composite tank? If so, what bond tests are being performed?

“No. There may be a chemical bond formed during processing between liner and composite overwrap, but there is no realistic way to test this bond. It is clear that this bond fails during the first few cryogenic temperature cycles applied to Salvador’s tanks, without harming their performance. With lightweight liners, the failure of this bond may not be so forgiving, one such failure having lead to a leak path in a prototype (thick XLPE liner, conformable) Thiokol tank. That tank’s failure locus does not occur in cylindrical tanks, and no direct effort is anticipated to improve this bond which has worked well on over a dozen gH₂ and NG tanks.”

At one time, LLNL did make an attempt to bond liner to case, but the debonding created more problems than no bond at all.

13. What material (if it’s not proprietary) is being used as the binder material for the carbon fibers in the composite tank?

“TCR® resin UF3325-93 (resin system in prepreg 93% part B - commercial cure = short cure - an 8 hr cure, low part B, therefore more flow, process is proprietary, can store at room temperature for up to ~1 year, 270 °F cure, 2 hour ramp, hold for 4 hr, 2 hour cooldown = commercial cure). Although the epoxies used as matrix materials for advanced composites are not proprietary or exotic, their handling is. Even process recipe duplication may not suffice to duplicate matrix performance. The resin just mentioned was formulated for its (proprietary) handling characteristics, and results in tanks which are tough enough to pass the “bullet test” (part of NGV2) easily.”

The resin is a Thiokol product. One of its best properties is its long shelf-life in the uncured (prepreg) state.

14. In the FY 1999 report, in the “Barriers” section, nothing is indicated as a problem in the tank liner area. Do you believe that standard R&D procedures with materials already identified will lead to meeting your objectives?

“Yes.”

Our discussions on metal coatings might lead me to believe that they are not there yet. Polyethylene is the liner of choice, but it will either be too thick, or will need an as yet untested metal coating.

V Additional Discussion:

Liner Material and Processing

- Currently, the LLNL group uses rotomolding (a spin-melt molding process) to produce liners. For small numbers of liners, this is the economical way to go, as the tooling costs under \$20K. 1-4 parts can be made per hour. For mass produced parts, they would look at injection molding. The tooling is much more expensive (up to \$250K), but several parts can be produced per minute. Dr. Mitlitsky is also considering blow-molding. This would produce parts even more quickly, and could also produce thinner parts.
- Dr. Mitlitsky’s suggested that their liner technology could go in one of several directions: Crosslinked polyethylene liner is considered the baseline. From a technical standpoint, polyethylene will likely provide an adequate permeation barrier. However, for safety reasons “the way the rules are written.” it would likely have to be made too thick. Other options are to use a different liner (along with its associated problems), or coat the polyethylene with something (outside, inside or both). Many liner candidates are too expensive and/or are difficult to process. They may be difficult to rotomold or need to be processed in an inert atmosphere, for instance. One suggestion is to bond a metal coating onto the outside of the polyethylene liner material. The metal acts as a secondary permeation barrier. Injection molding may prove a cheap alternative for rotomolding, but LLNL needs someone else to do this. *The likely problem is that they can’t afford the tooling. This appears to be a good indication of the fact that LLNL is not nearly “there yet”. They have both material and processing issues.*
- So far, only polyethylene has qualified as a single-material candidate. LLNL has found that if they use ¼ inch polyethylene inside a composite, they can achieve a leakage of 1 cc/hr per liter of tankage at 5000 psi. This is barely acceptable. *(or may not even be acceptable. My understanding is that DOE wants 0.25 cc)* If you use a metal coating, you should do better by an order of magnitude. This doesn’t include high temperature usage or cycling, however.

- As far as coatings go, one potential candidate is vinylidene – basically, Seran Wrap. The material can be painted on the polyethylene, and exhibits good permeation inhibition – perhaps two orders of magnitude better than polyethylene itself. Metals are even better permeation barriers, but they have lower strain-to-failure values.
- Another option is a liner that is only metal. However, the metal will fatigue and fail before the composite, so the metal cannot be too thin. So you are increasing weight and cost.
- Strains of about 1 percent are needed for tank liners.
- In Dr. Mitlitsky's words, polyethylene "turns to butter" at 7000 psi. The use of a different material at high pressures may be warranted. *I would be concerned at 5000 psi under these conditions.*
- Some polymers including polyethylene, if heated back to the cure temperature, will perform a one time shrinkage of 6-8 percent. This fact needs to be considered when coating the liner.

It would seem to me that the initial cure cycle is not sufficient to totally crosslink the polymer, and the recycle is finishing the process. The cure cycle should probably be changed to end this problem.

Composites

- An epoxy binder "looks great" until it is pressurized for the first time, then it starts to develop microcracks; that is why you need a liner.
- DCPD is another candidate for composite binder. It is 1-2 orders of magnitude tougher than polyethylene, is less subject to corrosion, and is easier to work with than is epoxy. LLNL thinks they can manufacture a part that won't crack and may work well.
- The tanks they currently can produce can hold 5% hydrogen. They know that they can go higher, but manufacturers think it may be too expensive. For example, they could use T-700 carbon fiber tanks, which costs about \$17/pound, they may be able to accommodate 9-10 percent hydrogen.
- T-1000 carbon fiber tanks will get you to 12% hydrogen, but the fiber is \$70/lb – a real problem. Perhaps the cost will come down with large volume purchases.
- LLNL has built a prototype tank (with T-1000 fibers), but have not yet burst-tested it. Thiokol, however, did successfully perform an armor-piercing bullet test on a tank at 5000 psi.

- LLNL does not do much large-scale testing on-site. They let Thiokol do it, or hire a contractor.

Regenerative Fuel Cells

This was not the topic of interest for this visit (recall that RFC R&D is not currently being funded at LLNL), but Dr. Blake Myers has a contract to look at safety issues with regard to the SRT/National Power halogen RFC project, and wanted to spend a few minutes discussing the project.

As we know, hydrogen/halogen RFCs can operate at higher efficiencies than their hydrogen/oxygen counterparts. For example, according to Dr. Myers, at 300 amps per square foot, the water system has a round trip efficiency of around 40-50%, while the HBr system is about 64%. *I think the HBr numbers are a little high.* The halogen systems, however, present many additional safety issues. For instance, Dr. Myers recommends complete body coverage in the operating area, and a “clothespin” respirator.

Dr. Myers believes that National Power, with their halogen electrolyzer experience in Europe, is a “great partner for SRT.”

Dr. Myers does not see a problem with bromine supply, citing Great Lakes and Albermarle in the U.S. and Dead Sea Bromine in Israel as the three leading bromine suppliers, each capable of supplying over 300 million pounds of bromine per year. *These three companies account for roughly 80% of the world's output.* All of these companies have good safety records.

Exhibit 1. From Mitlitsky FY 1999 Report (Table 1)

Figure of Merit = $1 / (\text{Gas Permeability} * \text{Density})$, normalized with HDPE = 1

Data are from Modern Plastics 1991 (Mid-October 1990 Issue Vol 67 (11), pp592-6 for Film & Sheet (supplemented with pp480-528 for Resins & Compounds) unless noted
 Permeability to gases data (property #15) is given in units of [cc - mil / 100 in² - 24 hr - atm] @ 25 °C (multiply by 3.886 to convert to [cc - 100 micron / m² - 24 hr - bar])
 Figure Of Merit (FOM) is defined as $1 / (\text{Gas Permeability} * \text{Density})$ and is normalized to HDPE (or MDPE if no HDPE data)

Boldface if H₂ FOM is >5 (5 times better than MDPE) or if unknown and O₂ FOM >5 (5 times better than HDPE)

Boldface and Red if H₂ FOM is >25 (25 times better than MDPE) or if unknown and O₂ FOM >25 (25 times better than HDPE)

Material	Lo H ₂ Perm	Hi H ₂ Perm	Lo O ₂ Perm	Hi O ₂ Perm	Lo Density g/cc	Hi Density g/cc	H ₂ FOM (MDPE=1) 1 / (Lo H ₂ Perm * Lo Density)	O ₂ FOM (HDPE=1) 1 / (Lo O ₂ Perm * Lo Density)	Lo Usable Temp °C [1]	Hi Usable Temp °C [1]	Lo Melt Temp °C [1]	Hi Melt Temp °C [1]
ABS (acronitrile butadiene styrene)				50	70	1.04	---	3.35				
Acrylonitrile methyl acrylate copolymer, rubberized	240		0.5	0.8	1.15		6.84	302.76			135	
Cellulose acetate	835		117	150	1.28	1.31	1.69	1.16			230	
Cellulose triacetate			150		1.28	1.31		0.91				
Cellulose acetate butyrate			600	1000	1.19	1.23		0.24			140	
Ethyl cellulose			2000		1.15			0.08			135	
Regenerated cellulose (Cellophane)	1.2	2.2	0.5	0.8	1.4	1.4	1074.82	248.69				
ECTFE (ethylene chlorotetrafluoroethylene copolymer) e.g. Halar [4]			25	36	1.66	1.7		4.19	-160	150	236	246
ETFE (ethylene tetrafluoroethylene copolymer) e.g. Tefzel [4]			100	184	1.7	1.75		1.02	-190	150	265	278
FEP (fluorinated ethylene propylene copolymer) e.g. Teflon FEP [4]	2200		715	750	2.15		0.38	0.11	-190	200	260	290
PFA (perfluoroalkoxy) e.g. Teflon PFA [3,4]			296	1142	2.15			0.27	-200	250	300	310
PCTFE (polychlorotrifluoroethylene copolymer) e.g. Aclar	220	330	7	15	2.08	2.15	3.95	11.96	-200	180	183	204
PTFE (polytetrafluoroethylene) e.g. Teflon [1]			386	998	2.1	2.2		0.21	-200	260	320	340
PVF (polyvinyl fluoride) e.g. Tedlar [4]	58		3	7.8	1.38	1.57	22.56	42.05	-70	100	185	190
PVDF (polyvinylidene fluoride) e.g. Kynar [2,4]			3.4	14	1.76	1.78		29.09	-30	135	168	172
Nylon 6 (polyamide) extruded	90	110	2.6		1.13		17.76	59.25			210	220
Nylon 6 (polyamide) biaxially oriented			1.2	2.3	1.16			125.06				
Nylon 6/6 (polyamide) molding compound					1.13	1.18					255	265
Nylon 11	323		34	92	1.02		5.48	5.02			191	194
Nylon 12	323		34	92	1.04		5.38	4.92			160	209
Polycarbonate	1600		300		1.2			0.94				
PET (polyester or polyethylene terephthalate)	100		3	6	1.38	1.41	13.08	42.05			245	265
Polyetherimide			37		1.27			3.70				
LDPE (low density polyethylene)	1950		500		0.91	0.925	1.02	0.38			98	124
MDPE (medium density polyethylene)	1950		250	535	0.926	0.94	1.00	0.75			98	124
HDPE (high density polyethylene)			185		0.941	0.965		1.00			130	137
UHMWPE (ultrahigh molecular weight polyethylene)					0.94						125	135
BVA (ethylene vinyl acetate copolymer)			840		0.924	0.94		0.22			103	108
Polyimide (e.g. Kapton)	250		25		1.42		5.09	4.90				
PMMA (polymethyl methacrylate)					1.14	1.26						
Polypropylene extrusion cast	1700		150	240	0.885	0.905	1.20	1.31			160	175
Polypropylene biaxially oriented			100	160	0.902	0.907		1.93				
Polystyrene			250	350	1.05	1.06		0.66			74	110
Polyurethane elastomer			75	327	1.11	1.24		2.09			75	137
PVC (polyvinyl chloride) nonplasticized	3	10	4	30	1.2	1.5	501.58	36.27				
PVC (polyvinyl chloride) plasticized			100	1400	1.2	1.4		1.45				
Poly sulfone			90	230	1.24	1.37		1.56				
TFE/TFP/VIDA terpolymer e.g. THV [4,5]			225		1.97	2.03		0.30			115	180
Vinyl chloride acetate copolymer nonplasticized			15	20	1.3	1.4		8.93				
Vinyl chloride acetate copolymer plasticized			20	150	1.2	1.35		7.28				
Vinylidene chloride vinyl chloride copolymer	4	55	0.08	1.1	1.59	1.71	283.92	1368.59				
Vinyl nitrile rubber alloy			50	65	1.1	1.3		3.17				

[1] Permeability & temp data from H. Fitz, "Fluorocarbon films-present situation & future outlook", Kunststoffe with German Plastics, vol 70(1) English trans. pp.11-16, Jan(1980).

[2] Lo O₂ permeability data from [1].

[3] Use permeability data for air (O₂ data not available) from [1].

[4] Use additional permeability data from Allied Signs Data Sheet "Fluoropolymer Barrier Properties", 12/4/95

[5] 3M Product Specifications including Form 33754-A-PWO December 13, 1993

Exhibit 2. Permeability Test Fixture From Mitlitsky FY 1999 Report (Figure 8)

Exhibit 3. Measured Hydrogen Permeability From Mitlitsky FY 1999 Report (Figure 9)

Detailed Analyses

Hydrogen Bromine-based Electricity Storage

The hydrogen bromine electrochemical cycle, shown in reaction { 1 } below, has been previously recommended as a means of storing electricity because, unlike the water cycle, it is highly reversible with demonstrated electric-to-electric efficiencies of 80% or higher (Fritts and Savinell 1983, Balko and McElroy 1980). The HBr-based electricity storage system is best suited for 6-10 hour peak shaving applications and is envisioned as a part of a distributed generation system.

Figure 1 is a schematic of the proposed HBr-based electricity storage system. The heart of the system is the reversible PEM cell, which can be operated in either electrolysis or galvanic mode. Because the HBr reaction is highly reversible, the electrode catalysts for electrolysis and galvanic operation are not highly specialized, making it less challenging to fabricate a reversible cell that is efficient in both directions.

The process operation is as follows. HBr is electrolyzed during periods of low electricity demand, forming bromine liquid and hydrogen gas which are stored. Hydrogen gas and bromine are recombined in the cell during peak demand hours to produce electricity. A power electronics component rectifies/inverts electricity in and out of the electrochemical cell and manages the voltage difference between the stack and the load.

This HBr technology is being developed by SRT Group and National Power, who have developed solar-based HBr energy systems and sodium bromide electrochemical energy storage systems, respectively. The hydrogen bromine electricity storage is in the pre-commercial stage and faces the following technical challenges:

Previous laboratory scale demonstrations of HBr cell efficiencies were conducted at low current density (i.e., less than 200 Amps/ft²). High efficiency must be demonstrated at a current density above 500 Amps/ft².

Because hydrobromic acid is electrically conductive, shunt currents limit the number of cells that can be stacked in a bipolar configuration. Modular stack output potential is limited to 10-20 volts. Such low voltage will create high resistive losses and increase the cost of power electronics equipment, which is generally current-limited. Several stacks could be externally wired in series, but this increases the cost of the system as well. An optimal system that considers stack voltage limitation must be developed.

The field life of the membrane electrode assemblies (MEAs) must be demonstrated. Because of the toxicity of the reactants, changing out the MEAs could be expensive compared to a water system. We project that an MEA life of 5-7 years is required for an economic system.

The cost of the hydrogen compressor is based on the assumption that the gas outlet pressure from the PEM stack is 1,000 psi. In theory, a high hydrogen gas outlet pressure

is achievable at low cost by pressuring the water inlet. If only a 200 psi outlet pressure is achievable, the cost of the hydrogen compressor would double.

Table 1 shows a capital cost estimate for a 300 kW 8 hour HBr-based electricity storage system. The estimate is based on a 72% AC/AC round-trip efficiency, a reversible PEM stack cost of 350 \$/kW, and a power electronics cost of roughly 175 \$/kW. All these estimates were provided by SRT Group and National Power and inherently rely on the resolution of the above technical issues.

A financial analysis of the system was conducted based on a hypothetical commercial or industrial facility that faces a time-of-use electric rate structure and buys an HBr system to reduce its electric bill. The HBr system would be operated 8 hours per day, 250 days per year. A pro forma cash flow analysis model was used to determine the energy rate for peak electricity required to yield a 15% after-tax internal rate of return based on an off-peak electric rate of 2 cent/kWh and a demand charge of 8 \$/kW/month (financial analysis assumptions include 20 year system life, 50% debt/equity, 7.5% interest on debt, 10 year ACRS depreciation schedule and 28% marginal tax rate). The base case peak electricity cost is 7.9 cents/kWh. Figure 2 shows that the required cost of peak electricity varies between 6 and 12 cents/kWh based on changes in several key assumptions.

Table 1. Capital Cost Estimate for a 300 kW, 8 hour Hydrogen Bromine -based Electricity Storage System

Component	Cost
PEM stack (300 kW, 350 \$/kW)	105,000
Power electronics (inverter 125 \$/kW, rectifier 50 \$/kW)	55,000
Hydrogen Compressor (10 kW, 12.6 kg H ₂ per hr)	26,300
Hydrogen gas storage (84 kg, 400 \$/kg)	33,800
Acid storage tank (Kynar, 10.7 m ³ , 6,000 \$/m ³ installed)	64,000
Piping and controls	30,000
Assembly and installation	30,000
Total capital cost	\$ 344,100
Size of equipment based on a 72% round trip efficiency	

As a comparison, a diesel generator (12 kWh/gallon efficiency, 1 \$/gallon fuel cost, 1 cent/kWh O&M) operated 8 hrs/day 250 days per year requires an electricity rate of 5.4 cents/kWh to yield a 15% IRR. On the other hand, the 1996 average rate for electricity for industrial customers in

New England was 7.92 cents/kWh (both peak and off-peak, *Electric Power Annual 1996 Volume II*, 1997). Our assessment is that the HBr-based electricity storage system has the potential to be commercially viable if the developers achieve their cost and efficiency goals.

A proposed area of future work is to evaluate the HBr system as an addition to wind/diesel hybrid systems in remote applications. The HBr system would manage the interface among the wind turbine generators, the diesel generators, and the load. It would enable the diesel generators to run at a more level rate increasing the fuel efficiency and extending their useful life. Lead acid batteries have been proposed to serve the same function. The HBr system offers the benefit that longer duration storage is less costly. A deeper storage system can capture a significant amount of excess turbine energy and allow a higher capacity wind turbine system for a given size load.

References

Electric Power Annual 1996 Volume II. 1997. DOE/EIA-0348(96)/2 Table 7. Energy Information Administration

Fritts, S.D. and R.F. Savinell. 1983. "Simulation of a Rechargeable Hydrogen-Bromine SPE Fuel Cell." *AIChE Symposium Series, Electrochemical Applications*, No. 254. Vol. 83

Figure 1. Schematic of the HBr-based Electricity Storage System

Figure 2. Financial Analysis of a 300 kW, 8 hour HBr-based Electricity Storage System

Hydrogen-fueled Buses

Table 1 shows significant recent industrial activity aimed at developing hybrid electric power systems for vehicles. A hybrid electric vehicle (HEV) offers improved fuel efficiency, reduced pollutant emissions, and reduced wear and tear on the mechanical components over vehicles powered by a conventional internal combustion engine (ICE). For transit bus applications, hybrid electric vehicles offer adequate range where all-electric vehicles fall short. Most commercial efforts are focused on diesel, gasoline, or natural gas-fueled systems. Energetics has analyzed the feasibility of using hydrogen fuel for hybrid electric power systems and the incremental cost compared to diesel, gasoline, or natural gas-fueled systems. The objective of the analysis is to build on the Hydrogen Program's experience with the Savannah River Bus and explore the impact of more advanced hydrogen storage and hydrogen-fueled electricity generation components. A full report will be published later this year. The analysis and preliminary results are summarized below.

Table 1. Hybrid Electric Vehicle Development Activities

Market	Company /Model	Fuel and power system	StatusStatus
Passenger Vehicle	Toyota Prius	Gasoline ICE HEV	Began sales in Japan Dec 10, 1997, has delivered 700 and has 3700 on back order. Monthly production of this car has gone from 1000 to 2000 per month to meet demand. The car travels 66 miles per gallon
	GM Modified EV1	Diesel ICE, Natural gas ICE, and PEM HEV	Experimenting with hybrid electric power systems in the EV1 platform
	Chrysler Intrepid ESX	Diesel ICE HEV	Built a series hybrid electric four door car in 1996, working on a parallel hybrid electric.
	Mitsubishi Space Wagon/Chariot	Diesel ICE HEV	Mitsubishi is expected to introduce these two cars over the next two years. They have also developed an all-electric Miata.
Transit & School Bus	Bluebird Bus	Diesel, natural gas and H2 ICE HEV	Involved in the hydrogen bus project. Have experimented with natural gas and diesel hybrid electric systems as range extenders for their electric school bus.
	Lockheed-Orion	Natural Gas ICE HEV	Recently won a competitive award to supply 4 diesel hybrid electric buses to New Jersey Transit and 10 diesel hybrid electric buses to New York Transit Authority. Units will be delivered in 1998. Future plans will depend on the performance of these units in the field.
	APS Systems	Propane ICE HEV	Plan to put one prototype bus into service in California in 1998. Nickel cadmium batteries, propane rotary engine.
	Advanced Vehicle Systems	Natural Gas ICE HEV	Built two natural gas hybrid electric buses to be used in Chattanooga, Tennessee.
Military	TDM	Diesel ICE HEV	Won an award to build 10-15 hybrid electric service vehicles for the US Army.

	Unique mobility HE hummer	Diesel ICE HEV	Developed a hybrid electric hummer for the U.S. Army. Offers improved performance over conventionally-powered hummer. Also, can run in “Stealth mode,” running only on the electric motor.
--	---------------------------	----------------	--

Table 2 shows the curb weights of several diesel, natural gas, and hydrogen-fueled transit buses. Notice that the curb weight of the diesel hybrid electric vehicle is 4,430 pounds higher than the conventional diesel ICE, mostly due to the weight of the batteries. The gross vehicle weight for a diesel hybrid is increased to 38,000 pounds giving a net reduction in people-carrying capacity of 1,430 pounds, or nearly 20%. The natural gas and hydrogen options are heavier still because of the increase in on-board fuel storage and ICE weight compared to diesel. This incremental weight directly displaces people-carrying capacity because the two-axle bus gross vehicle weight is limited to 38,000 pounds by the weight-bearing capacity of the roads.

The data in Table 2 indicate that reductions in the weights of the batteries and power systems are important to developing hybrid electric buses. In reduced range applications or smaller size transit buses the weight limitations may not be as severe.

Table 2. Weights of Conventional and HEV buses

	Diesel		Natural Gas	Hydrogen	
Bus Component	ICE	Hybrid	Hybrid	Pressure Vessel	Mg Hydride
Batteries	0	4,000	4,000	4,000	4,000
Fuel Storage ¹	200	130	170	650	1,900
ICE ²	2,000	1,400	2,100	2,800	2,800
Motor/ Generator ³	0	600	600	600	600
Balance	24,800	25,300	25,300	25,300	25,300
Vehicle Curb Weight	27,000	31,430	32,170	33,350	34,600
Gross vehicle weight limitation	36,000	38,000	38,000	38,000	38,000
Passenger weight capacity	8,000	6,570	5,830	4,650	3,400

¹ Based on a 200 mile range

² Diesel engine weight based on 275 hp Navistar Engine; 30% power reduction for HEV; multipliers of 1.5 and 2.0 used for natural gas and hydrogen ICE's respectively

³ Estimates of advanced systems from Solectria and Fisher Electric Technology

A transit bus will be driven anywhere from 20,000 to 40,000 miles per year, and fuel cost is an important part of the overall bus cost. Figure 1 shows the fuel cost for diesel, natural gas, and hydrogen buses over a range of hydrogen fuel costs. A first-of-a-kind natural gas reformer sized to fuel 40 buses could deliver compressed hydrogen at a cost of 5 \$/kg (Thomas, C.E., et al, 1997). Clearly, low-cost hydrogen is needed to enable commercialization of hydrogen fueled buses.

The success of the hybrid electric platform hinges largely on the development of a peaking battery. If an acceptable peaking battery is developed and the hybrid electric platform proves commercially viable, on-board natural gas combustion is a strong competitor to hydrogen. Diesel emits relatively large amounts of nitrous oxides and particulate matter and not readily comparable to hydrogen. Natural gas exhibits full life-cycle pollutant and greenhouse gas emissions comparable to hydrogen. It is less expensive than hydrogen on a delivered-energy basis, and the efficiency differential between a hydrogen-fed PEM fuel cell and a natural gas ICE are reduced in a hybrid electric platform. (This is driven by the fact that the level operation of the ICE in a hybrid electric platform greatly increases its efficiency, and the parallel hybrid, a new development in hybrid electric vehicles that offers increased fuel efficiency, is not amenable to a fuel cell. A parallel hybrid is a hybrid in which mechanical torque from the ICE can be transferred directly to the wheels when it is optimal to do so. Since a fuel cell does not generate torque, it cannot utilize a parallel hybrid configuration.)

The question then is how can a hydrogen bus be differentiated from a natural gas bus to become preferable? One possible differentiating characteristic is carbon dioxide emissions and global climate change. Because a vehicle with on-board hydrogen storage is carbon-free, it is potentially carbon dioxide emission-free. However, the development of renewable-based hydrogen production technologies and/or carbon dioxide sequestration systems are required to realize zero full life-cycle carbon dioxide emissions. Another potential motivation characteristic is robustness of pollutant emissions. Natural gas ICE systems rely on tailpipe clean-up to achieve low emissions and the performance of the clean-up device may degrade over time and during transient conditions.

Advanced hydrogen storage options being developed by the Hydrogen Program can also differentiate hydrogen from natural gas. These are low-pressure systems that do not require a high-pressure gas compressor and have markedly different vehicle safety characteristics. Hydride and fullerene near- to mid-term options require heat at 120 to 250 °C to release hydrogen and so require an on-board heat balance. This is difficult to

achieve with a PEM fuel cell that rejects heat at 60-80 °C. Internal combustion engines operate at 300-400 °C and are a better heat match with advanced hydrogen storage options.

Reference

Thomas, C.E. 1997. *Hydrogen Infrastructure Study prepared for the Ford Motor Company*, Arlington, VA: Directed Technologies, Inc. Page 15, Praxair unit

Figure 1. Fuel Cost For Transit Buses

Based on 40,000 miles per year, diesel cost 1 \$/gallon,
NG cost 2 cents/kWh, conventional diesel eff 3 mpg

Feasibility of Using Low-rank Western Coal as a Carbon Source for Hydride Regeneration

Introduction and Background

One of the storage systems that is being considered for hydrogen, both on-board and in stationary applications is a system being proposed by Thermo Power Corporation. In this system, a reactive metal hydride such as LiH or CaH₂ is transported in slurry form, using mineral oil as the carrier fluid, to its point of use. After the hydrogen is recovered by reacting with water, the spent material is in the form of an hydroxide. For example:

or:

Thermal Power then proposes to take the hydroxide and reconvert it to the hydride through the following series of steps:

Or for the lithium analog:

Considering reactions [1] and [8] for the calcium system, and reactions [2] and [12] for the lithium system, it can be seen that in both cases, one mole of carbon leads to one mole of hydrogen.

Thermo Power, has proposed that they can obtain a “char” which has a heating value of about 14,000 Btu/lb. Thermo Power further states that the char can be obtained on site in a regeneration

plant located on the East Coast for no more than \$1.67/MMBtu (Breault *et al*, 1999). It has been proposed that an alternative low cost process might be to use a low-rank Western coal as a carbon source. The purpose of this analysis is to consider this option and determine under what conditions, if any, such a process would be feasible.

If one were to use a low-rank coal as a carbon source, and the hydrogen is being used in the eastern part of the country, the options open are:

- Move the spent hydroxide west
- Move the low-rank coal east

The cost of these transportation processes as compared with the on-site use of the char is then considered. Note that the cost of regenerating the hydride from the hydroxide is not part of this analysis, as this process would have to take place regardless of the location or carbon source. However, the *efficiency* of this process is needed in order to estimate the amount of coal or char that needs to be transported.

The coal that was chosen for this exercise is Wyodak sub-bituminous coal from Campbell County, Wyoming. The coal was picked to coincide with that being used by another project involving low-rank Western Coals that is being co-funded by DOE/EE and DOE/FE, and is being performed at the National Renewable Energy Laboratory (Golden, CO) and the Federal Energy Technology Center (Pittsburgh, PA). The proximate and ultimate analyses for Wyodak coal are shown in Table 1.

Table 1: Proximate and Ultimate Analyses of Wyodak Coal (As received)

Proximate Analysis (%)	
Moisture	26.6
Volatile Matter	33.2
Fixed Carbon	34.4
Ash	5.8
Ultimate Analysis (%)	
Sulfur	0.6
Hydrogen	6.5
Carbon	50.0
Nitrogen	0.9
Oxygen	36.2
Heating Value (Btu/lb)	8630

Since Thermo Power at this point is considering Massachusetts (the site of their laboratory) as the potential site for hydride dispensing, the calculation will include: 1) the cost of moving Wyodak coal from Wyoming to Massachusetts, 2) alternatively, the cost of moving spent hydroxide in slurry form, from Massachusetts to Wyoming (where the regeneration process would occur) and then moving the hydride slurry back to Massachusetts, and 3) a comparison with the cost of using Thermo Power's char.

Cost for Transporting Western Coal to Massachusetts

In order to estimate the cost of transporting coal from the western U.S. to Massachusetts it is important to understand that western coal is not currently used in Massachusetts electric power plants. Therefore, no real data exists with organizations such as FERC for what it would actually cost to transport Western coal to Massachusetts by rail. A methodology has been developed that estimates the hypothetical cost of transporting western coal to Massachusetts. This is a preliminary estimate only to be used for comparing different scenarios and it should not be used for detailed engineering assessments of these options.

Wyodak is the most productive coal bed in Wyoming, with Campbell County being the largest coal producing region in Wyoming (Energy Information Administration, Dec. 1998). However, since no Wyoming coal is shipped to Massachusetts, in order to calculate the transportation cost of sending coal by rail from Wyoming to Massachusetts the following methodology is used:

The average mine-mouth price of coal in Wyoming (nominal dollars, 1997) = \$6.00/short ton (Energy Information Administration, May 1998, p. 154, Table 80). The delivered cost of coal is defined as the mine-mouth price + transportation + taxes + commissions + insurance + equipment lease costs. Since we only have data on mine-mouth price and delivered price of coal, our definition of aggregate transportation cost includes transportation, taxes, commissions, insurance and equipment lease costs. Table 2 shows delivered and aggregate transportation cost for coals from Wyoming for 1997. Table 2 also shows approximate distances for each state from Wyoming. Figure 1 plots the aggregate transportation cost as a function of distance from Wyoming.

Table 2 Aggregate Transportation Cost of Wyoming Coal, 1997

Destination state	Delivered cost (\$/ton)	Distance from WY (miles)	Transportation cost (\$/ton)
AL	19.49	1,080	13.49
AZ	18.99	690	12.99
AR	28.56	860	22.56
CO	14.95	300	8.95
FL	24.59	1,630	18.59
GA	26.29	1,160	20.29
IL	30.70	790	24.70

IN	19.89	900	13.89
IA	15.31	580	9.31
KS	16.69	580	10.69
KY	21.60	1,010	15.60
LA	25.82	1,120	19.82
MI	18.59	960	12.59
MN	19.04	540	13.04
MS	23.22	1,020	17.22
MO	15.56	780	9.56
MT	9.24	240	3.24
NB	10.06	500	4.06
NV	18.79	620	12.79
NC	31.80	1,290	25.80
ND	11.02	420	5.02
OH	21.63	1,040	15.63
OK	15.80	670	9.80
OR	19.95	630	13.95
TN	15.67	1,090	9.67
TX	26.18	1,010	20.18
UT	22.68	320	16.68
WI	16.64	780	10.64
WY	14.16	210	8.16

Sources:

Mine-mouth cost = \$6.00/ton (Source: Energy Information Administration, May 1998, p. 154, Table 80)

Delivered cost: Source: Energy Information Administration, 1995, p. 35 – 38, Table 23.

Distance = Measured roughly from Wyoming to major urban center of each state.

Transportation cost = Delivered cost – mine mouth cost

Figure 1. Aggregate Transportation Cost of Wyoming Coal

As can be seen from Figure 1, while there is an upward trend with increasing distance, there is also considerable scatter in the data. This is due to the fact that what is being plotted here is not the real transportation cost only but an aggregate transportation cost which includes the rail cost and other factors such as taxes, commissions, insurance and equipment lease costs.

Nonetheless, using the best-fit regression equation in Figure 1, the cost of transporting the coal from Wyoming to Massachusetts can be calculated. Assuming the distance from Wyoming to Massachusetts to be 1,490 miles (approximate distance from Campbell County, Wyoming to Boston, Massachusetts) the aggregate transportation cost from Wyoming to Massachusetts would be: $0.167(1490)^{0.657} = \$20.30/\text{ton}$. **Delivered cost for coal from Wyoming to Massachusetts would be: $\$20.30 + \$6.00 = \$26.30/\text{ton}$ (aggregate transportation cost + mine-mouth cost).** It should be pointed out that the transportation cost assumes that the coal cars would be returned empty to the mine. In some cases it is possible that a second product could be identified for the return trip. This would act as a credit, and reduce the cost of coal transportation.

According to the ultimate and proximate analyses as indicated in Table 3, the Wyodak coal has a carbon content of 50% on an as-received basis. Thus, the cost of delivered carbon is $\$26.30/0.5 = \52.60 per ton. Even more important is the fact that the useful carbon – that which would be used in the regeneration process shown in equations [8] and [12] would likely be the fixed carbon. This as shown in Table 3, makes up 34.4% of the coal by weight. The cost of delivered fixed carbon is $\$26.30/0.344 = \76.45 per ton. Right now, due to the state of development of the Thermo Power process, no data is available on what percent of the fixed carbon can be utilized by the regeneration reactions (equations [8] and [12]). Clearly, the process economics would

depend significantly on the level of carbon conversion that could be achieved and further data in this area (on the basis of pilot plant tests for example) is essential to deriving meaningful conclusions from this analysis.

The delivered cost of coal on a Btu basis can be calculated simply from the as-received heating value and the delivered cost per ton:

$$\text{\$26.30/ton} / (8630 \text{ Btu/lb} \times 2000 \text{ lb/ton}) = \text{\$ 1.52/MMBtu}$$

On a fixed carbon basis, this is equivalent to:

$$\text{\$ 1.52/MMBtu} / 0.344 = \text{\$4.43 /MMBtu}$$

compared with the reported cost of the delivered char, \$1.67/MMBtu, without even considering the cost of converting the coal to char.

Remembering that one mole of carbon produces one mole of hydrogen (or 12 pounds of carbon produces 2 pounds of hydrogen), and that hydrogen has a heating value of 61,000 Btu/lb, the cost of delivered Wyodak-based fixed carbon to produce one million Btu of hydrogen can be calculated:

$$(\text{\$76.45/ ton C} / 2000 \text{ lb C/ton C}) \times (12 \text{ lb C} / 2 \text{ lb H}_2) \times (1 \text{ lb H}_2 / 0.061 \text{MM Btu H}_2) \\ = \text{\$3.76/MMBtu.}$$

The cost of delivered char to produce the same amount of hydrogen is calculated by:

$$(\text{\$1.67/MMBtu C} \times 0.014 \text{ MMBtu C/lb} \times (12 \text{ lb C} / 2 \text{ lb H}_2) \times (1 \text{ lb H}_2 / 0.061 \text{MM Btu H}_2) = \\ \text{\$2.30/MMBtu.}$$

Cost for Transporting Hydroxide from Massachusetts to Wyoming, and Hydride from Wyoming to Massachusetts

Next, the alternative path of transporting the hydroxides to the mine mouth is considered. First, the weight of hydroxide that must be moved as a function of the hydrogen energy that it will eventually become is calculated. The hydroxide will be converted back to a hydride by reactions [8] or [12], and then used to make hydrogen by reactions [1] or [2], respectively. One mole of LiOH leads to one mole of hydrogen; one mole of Ca(OH)₂ leads to two moles of hydrogen. If 61,000 Btu is used as the energy content of one pound of hydrogen, one pound of LiOH leads to 5080 Btu of hydrogen, and one pound of Ca(OH)₂ leads to 3297 Btu of hydrogen.

Next, the state of the hydroxide as it is collected from a storage area in Massachusetts is considered. Thermo Power is considering using water to wash the spent hydroxide out of the reaction chambers (where hydrogen is made), and then turning the mix into a manageable slurry with more water. R. Breault has indicated that a 60-65 weight % slurry could be made from LiOH and water, and a 70 weight % slurry could be made from Ca(OH)₂ and water (Breault,

1999). The following assumptions to obtain a best-case scenario for this preliminary assessment will be made:

- The degree of difficulty of shipping will not be increased by a lack of slurriability of the hydroxide. That is, we will assume that the slurry is mixable, stable, and pumpable under the loadings designated above.
- There is no residual, unreacted hydride in the hydroxide material (this would react with the water upon slurrying).
- The hydroxide will not need grinding or further processing to make it slurriable.
- The surfactant's cost and concentration will not be included at this time.

The densities for LiOH and Ca(OH)_2 respectively are 1.46 and 2.24 grams/cc. About 11% by weight LiOH is soluble in water, while Ca(OH)_2 is virtually insoluble (less than 0.2%). Using these values, the relationships between the volume of hydroxide/water slurries and MMBtu of hydrogen are shown in Figure 2 for 25-95% by-weight hydroxide slurries. The analogous weight relationships are shown in Figure 3. These data show, for example, that 30.75 gallons of a 60% by-weight LiOH slurry would need to be regenerated to eventually produce 1 MMBtu of hydrogen. This amount of slurry would weigh 329 pounds. For a Ca(OH)_2 slurry, a 70% slurry would require 31.9 gallons, and would weigh 434 pounds.

Figure 2. Hydroxide Slurry Volume Resulting in 1MMBtu Hydrogen

Figure 3. Weight of Hydroxide Slurry Representing 1MMBtu Hydrogen

If it is then assumed that the hydrides are regenerated by the aforementioned processes in Wyoming, and then slurried in mineral oil and shipped back to Massachusetts, analogous calculations can be performed on these hydrides. The densities of LiH and CaH₂ are 0.82 and 1.7 grams/cc, respectively. The hydrides are slurried in mineral oil, having a density of 0.82 (Breault, 1999). The hydrides are, of course, insoluble in the mineral oil. The volume and weight relationships between the hydride/mineral oil slurries and MMBtu of hydrogen are shown respectively in Figures 4 and 5. These data show, for example, that 16.03 gallons of a 60% by-weight LiH slurry would need to be regenerated to eventually produce 1 MMBtu of hydrogen. This amount of slurry would weigh 110 pounds. For a CaH₂ slurry, a 70% slurry would require 23 gallons, and would weigh 247 pounds.

Figure 4. Hydride Slurry Volume Resulting in 1 MMBtu Hydrogen

In considering the cost of transporting the hydroxide and hydride slurries, an assumption will be made that the cost of transporting slurry is the same as transporting coal. This represents a lower limit of the cost. This is because coal transportation is assumed to occur on open rail cars with no cover, the rail cars are not lined with any material to protect them from corrosion, and there is no pre-treatment of the coal to reduce dust or exposure along the way. Transporting the slurries would presumably have to involve some protection of the rail-cars from the slurry and may necessitate other types of controls such as covers or sealed vessels to minimize exposure to the elements. Thermo Power has suggested (Breault, 1999) that the slurries could be carried in a tarp-covered rail car. The equivalency of the coal cost to the slurry transportation cost allows us

to evaluate the economics of this option under highly optimistic conditions. If the economics under these favorable conditions do not turn out to be attractive then it is difficult to see how the cost could be improved to make this option competitive with the cost of transporting the coal from west to east.

Figure 5. Weight of Hydride Slurry Representing 1 MMBtu Hydrogen

Recall that the cost of shipping coal from Wyoming to Massachusetts was \$20.30 per ton (not including the cost of the coal at the mine mouth). So this number, \$20.30 per ton, can serve as the lower limit of the shipping cost of the slurries. It has been estimated (Breault, 1999) that the relative slurriabilities of the hydrides and hydroxides are about the same; LiH will produce a slurry with about the same ease as LiOH, etc. Using this, the weight of the hydroxide slurry can be added to that of the hydride slurry at any particular loading to get an estimate for the round-trip weight requirement per Btu of hydrogen. The curves relating slurry loading to the equivalent hydrogen cost are presented in Figure 6. Again, looking at the base cases, the 60% lithium slurries would incur a transportation cost of \$4.45/MMBtu hydrogen, and the 70% calcium slurries would incur a transportation cost of \$6.91/MMBtu.

Comparison of Costs/Conclusions

Finally, comparisons can be made of moving slurries back and forth to Wyoming from Massachusetts with the options of moving the Wyodak coal east, and using the “char” that

Thermo Power initially proposed. Recall, that if all the fixed carbon in the coal is converted to hydrogen, the cost of moving the coal east is \$3.76/MMBtu hydrogen. This would then be less expensive than the cost of either the 60% lithium slurry or the 70% calcium slurry. The \$2.30/MMBtu hydrogen cost for the char is cheaper yet. However, if the conversion rates of the carbons are less than 100%, the slurry transportation option becomes more feasible. This is because a slurry transportation cost is not a function of carbon conversion.

Figure 6. Cost of Round Trip Transport of Lithium and Calcium Slurries

Figure 7 presents the sensitivity to carbon-conversion efficiency of the equivalent transportation costs of Wyodak coal and “char” as compared to 50, 60, and 70% lithium and calcium slurries. As can be seen, transport of 60% lithium slurries become the less expensive option for conversion efficiencies of less than 85% of the Wyodak fixed carbon, and for less than 55% of the char. For the 70% calcium slurries to become the less expensive option, the conversion efficiency of the Wyodak fixed carbon would have to be less than 57%, and the char conversion would have to be less than 35%.

If the carbon-conversion level is low, the process is likely not economical. Thus it would be less likely that shipping slurries is a good option. This is especially true when one considers the fact that this analysis does not consider any additional transportation-related costs involving making the slurries or shipping them under optimal conditions. If these factors are added, the slurry lines

in Figure 7 move upward, making the intersections occur at even lower values of carbon conversion.

It would seem then, that using the char would be the least expensive option. Recall, however, that we are only dealing with transportation costs or equivalent transportation costs. Further analysis would include information on the conversion processes. For instance, if a high conversion percentage were possible for the Wyodak coal at the mine mouth, and this conversion – presumably a pyrolysis process – also produced salable hydrogen (or another salable product), the net cost of transporting the slurries including the hydrogen “credit” may be lower.

Figure 7. Comparison of Transport Cost as a Function of Carbon Conversion

It should also be noted that this analysis only deals with long-range transportation cost: 1490 miles. Since delivered coal prices are so dependent on transportation, shorter distances will likely present a different picture.

Acknowledgements

Discussions with Ron Breault of Thermo Power are gratefully acknowledged. This work was performed under DOE contract DE-FC36-98GO90291.

References

Breault, R., Thermo Power, Personal Communication, 1999

Breault, R.W. J. Rolfe, and A. McClaine, March 1999, "Hydrogen for the Hydrogen Economy", in the *Proceedings of the 24th International Technical Conference on Coal Utilization and Fuel Systems*, pp 723-734, Clearwater FL, Published by The Coal and Slurry Technology Association

Energy Information Administration, February, 1995, *Coal Data, A Reference*, DOE/EIA-0664(93).

Energy Information Administration, December 1998, *Coal Industry Annual, 1997*, DOE/EIA-0584(97).

Energy Information Administration, May 1998, *Cost and Quality of Fuels for Electric Utility Plants 1997, Tables*, DOE/EIA.

Analysis of the

Sodium Hydride-based Hydrogen Storage System

being developed by

PowerBall Technologies, LLC

Prepared for

The US Department of Energy
Office of Power Technologies
Hydrogen Program

Prepared by

J. Philip DiPietro
and
Edward G. Skolnik,
Energetics, Incorporated

October 29, 1999

Analysis of the Sodium Hydride Based Hydrogen Storage System

We considered the viability of a system for storing hydrogen on-board a vehicle in the form of plastic-encapsulated sodium hydride (NaH) pellets. Hydrogen is produced when the pellets are cut and immersed in water. The exposed NaH surface reacts with water, releasing hydrogen and forming sodium hydroxide (NaOH) as a byproduct. Later, in an off-board activity, the hydroxide is recycled to hydride via a multi-step regeneration process that relies on methane as both a fuel and a reactant. This is a preliminary analysis that required the development of conceptual designs for several of the process steps and the need to make several assumptions in order to complete the overall systems analysis. The analysis was peer reviewed by several members of their hydrogen community, and their comments were taken into account in the preparation of this document.

Executive Summary

The reaction of sodium hydride with water to form hydrogen and sodium hydroxide can be utilized onboard a vehicle to deliver hydrogen to an onboard power system. PowerBall Technologies, LLC has developed a novel means of controlling the reaction: they encapsulate small amounts of sodium hydride in plastic balls. These balls are sliced open one at a time onboard the vehicle to deliver hydrogen as needed. We estimate a sodium hydride-based storage system can achieve a hydrogen storage density of 4.3 wt% and 47 kg/m³, including all ancillary equipment. PowerBall Technologies, LLC is also developing a novel method of manufacturing the sodium hydride material. Instead of the traditional electrochemical process, they propose to form sodium metal by reacting natural gas and sodium hydroxide. A preliminary assessment indicates the cost of hydrogen delivered to a vehicle is about \$5.3/kg (\$39.4/MMBtu) using the sodium hydride system being developed by PowerBall Technologies, LLC. The implementation of cost reduction steps, based primarily on an alternative source of NaOH, results in a decrease of the cost of hydrogen to about \$4.1/kg (\$30.5/MMBtu).

One large component of the cost of the process is the energy requirements, with the key factor being the cost of regenerating the sodium hydride from sodium hydroxide. The full life-cycle energy consumption of the base case sodium hydride process is 4.0 kWh of energy per kWh of hydrogen delivered to the vehicle compared to 2.2 and 1.7 for liquid hydrogen and compressed hydrogen gas, respectively.

A comparison of the cost of delivered hydrogen from the PowerBall process with compressed hydrogen and liquid hydrogen is \$5.3/kg for the base case PowerBall process, \$4.1/kg for the lower cost PowerBall option, \$ 1.4/kg for compressed hydrogen, and \$2.8/kg for liquid hydrogen. When one includes the estimated cost of the respective on-board systems, however, the numbers become somewhat closer. The onboard equipment for the PowerBall process is estimated at about \$0.46/ kg H₂ compared to the capital cost of a pressure vessel, \$750, which equals about \$0.88/kg of hydrogen stored over the life of a vehicle. The overall costs are then about \$5.76/kg for the base-case PowerBall system, \$4.56/kg for the lower cost PowerBall system, \$2.28/kg for compressed hydrogen, and \$3.30/kg for the liquid hydrogen system.

A comparison can also be made between the cost of hydrogen from the PowerBall system, and the cost of gasoline. Using the comparative values of 31.4 miles/gallon gasoline for a standard AIV (Aluminum

Intensive Vehicle) Sable, and 82.3 miles per gallon-equivalent for a fuel cell vehicle¹, a hydrogen cost of \$5.30/kg is roughly equivalent to a gasoline cost of \$2.02 per gallon, not including taxes. (An on-board hydrogen fuel cell vehicle will be more fuel-efficient than a gasoline ICE vehicle). A hydrogen cost of \$4.10/kg is roughly equivalent to \$1.56 per gallon (untaxed).

Aside from the relatively low cost of the on-board PowerBall operating system, another “plus” is the fact that the encapsulated ball system is amenable to the initial situation of a small number of vehicles in a geographic area.

It should also be pointed out that the application of the PowerBall technology in the chemical industry represents an attractive option. The estimated plant gate manufacturing cost of sodium metal via PowerBall Industries’ thermochemical process could be as much as ten times less than the current commodity price for sodium produced via electrolysis. Also, the encapsulation concept could greatly lower the cost of transporting sodium and/or sodium hydride. PowerBall might consider pursuing applications for its technologies within the chemical industry in the near term, with a plan to expand into energy systems in the future.

Recently, PowerBall unveiled a modified recycling process. In this process, the syngas ($CO + H_2$) which is formed during the first step of the recycling process is in part combusted to produce heat to raise the reaction temperature, and in part reacted to produce more methane feedstock. As an addendum to this report, we have addressed this modification in the form of a very preliminary analysis.

PowerBall has indicated that the overall modified process is superior in that it produces more hydrogen per unit methane, and that the overall reaction is exothermic. Our preliminary analysis indicates that while

- *The amount of hydrogen produced per unit methane has indeed increased, and*
- *The overall reaction is exothermic,*

The following mitigating factors need to be considered as well:

- *The exothermicity of the overall reaction is in part due to the inclusion of a step (the hydriding of sodium) which is done separately, and from which the heat likely could not be used in the integrated process. Without this step, the overall reaction is endothermic.*
- *The benefit incurred by the decrease in the amount of methane feedstock needed is likely more than offset by the need for multiple separations, multiple reactors, and the added cost of oxygen to burn the syngas.*

¹ “Integrated Analysis of Hydrogen Passenger Vehicle Transportation Pathways”, C.E. Thomas et al, Directed Technologies, Inc., Report to the National Renewable Energy Laboratory, Subcontract AXE-6-16685, March 1998.

Background

The PEM fuel cell has potential to be the next-generation vehicle power system, but delivering pure hydrogen fuel to the PEM stack, either through onboard storage of neat hydrogen or the processing of fossil fuels on-board, remains a barrier on the basis of cost, weight, and/or volume. The two commercially available options for onboard storage of hydrogen, compressed gas or liquid, are energy-intensive and would require significant investment in distribution infrastructure.

The Department of Energy's Hydrogen Program seeks to improve the commercial viability of hydrogen-based energy systems, and the Program is funding R&D into advanced hydrogen storage technologies, including chemical hydrides and carbon absorbents. Another approach being explored by PowerBall Technologies, LLC is to react a metal hydride with water to produce hydrogen gas and the corresponding metal hydroxide. Potential reactants include sodium, sodium hydride, calcium, and lithium. PowerBall Technologies, LLC has focused its efforts on sodium hydride because, compared to the others, it offers adequate weight and volume density, fast kinetics, and a clear recycle loop as will be discussed below.

The sodium hydride / water reaction {1} is strongly exothermic and proceeds vigorously upon contact of the reactants. In order to control the reaction for use as an onboard hydrogen source, PowerBall Technologies, LLC proposes that the sodium hydride be encapsulated in plastic-coated pellets (nominally 1.5 inches in diameter with a coating of polyethylene 0.020 inches thick). The pellets are stored onboard a vehicle, sliced open one at a time, and contacted with water to produce hydrogen as needed.

The objective of this analysis is to characterize the sodium hydride-based hydrogen storage system and compare it to compressed gas and liquid hydrogen storage systems. The criteria for evaluation are:

1. Cost of hydrogen delivered to the vehicle
2. Weight and volume density of the onboard hydrogen storage system

Cost of Hydrogen Delivered to the Vehicle

The cost and fuel efficiency of the sodium hydride system is determined by an assessment of the production and delivery of sodium hydride balls to the vehicle. Sodium hydride is available as a specialty chemical, however its cost is prohibitive for use as a hydrogen carrier. The conventional process for sodium hydride manufacture, electrolyzing sodium chloride and then sparging hydrogen gas through a bath of the molten sodium metal, is too expensive for use as a hydrogen carrier. We can estimate the cost of the NaCl electrolysis process by considering the cost of product sodium. DuPont's list price for sodium metal is \$3.3/kg for bulk shipments (36,000 kg or more, <http://www.dupont.com/sodium/price.mtml>). Assuming it costs 20 cents/kg to produce sodium hydride from sodium metal by the sparging process, the estimated cost of sodium hydride is \$3.5/kg. Based on reaction {1}, twelve kg of NaH are required to deliver 1 kg of hydrogen gas. Thus \$3.5 /kg of NaH

converts to \$42/kg (\$300/MMBtu) of hydrogen delivered to the vehicle. Estimates of the cost of pressurized gas or liquid hydrogen delivered to a vehicle ranged from \$1.4-2.8/kg. Clearly, the conventional process is too expensive.

The high cost of sodium hydride from the conventional production pathway is due to high-energy consumption. According to DuPont, the electrolysis of sodium chloride consumes 9.7 kWh of electricity per kg of sodium, which, based on reaction {1}, works out to 3.4 kWh electricity per kWh hydrogen delivered to a vehicle. When one considers that most U.S. electricity generation is fossil-based with an efficiency of 30% to 60%, the full life-cycle energy consumption of the sodium hydride system is even higher.

To achieve lower cost, PowerBall Technologies, LLC is developing a process for manufacturing sodium hydride from sodium hydroxide. Figure 1 is a schematic of the vehicle fueling system, in which vehicles consume sodium hydride balls and generate sodium hydroxide solution. At refueling stations, the sodium hydroxide solution is drained from the vehicles and replaced with a fresh load of sodium hydride balls. The hydroxide is stored at the vehicle refueling station and transported to a central facility where it is used as feedstock in the manufacture of new sodium hydride balls. The balls are then shipped out to the refueling stations to replenish their inventories.

Figure 2 is a block diagram of the process being developed by PowerBall Technologies, LLC for converting sodium hydroxide to sodium hydride. The process flow is as follows: 30 wt% sodium hydroxide is charged to a first stage concentrator where roughly 80% of the water is boiled off. Effluent sodium hydroxide solution (70 wt%) is charged to a second stage concentrator where the remaining water is boiled off, leaving molten sodium hydroxide (melting point of sodium hydroxide is 318 C). The molten sodium hydroxide is mixed with methane and charged to the sodium reactor, which is a molten bath of sodium carbonate (Na_2CO_3). The sodium carbonate serves to disperse the reactants and raise their temperature to roughly 980C. The following overall reaction occurs

The reactant products are gases and escape from the top of the reactor. The reaction is strongly endothermic, and heat must be supplied to the reactor by circulating a portion of the sodium carbonate bath through a heater vessel. The sodium carbonate is heated by burning a fuel and injecting the combustion exhaust into the bottom of the bath. The exhaust gases bubble up through the molten sodium carbonate bath, transferring heat. The transfer of sodium carbonate between the reactor and heater vessels is driven by the density difference of the hot and cold material. The sodium reactor heater fuel is preheated with exhaust gas effluent, and it is assumed that a 500C inlet temperature is achieved.

The effluent from the sodium reactor, CO, H_2 , and Na at 980C, is quenched with Dowtherm or mineral oil, condensing the sodium at 880C at atmospheric pressure. The quench fluid is cooled by an air cooler.

Forty percent of the hydrogen contained in the quench overhead stream is recovered via a membrane or pressure swing absorber. The hydrogen is then bubbled up through the molten sodium product to produce sodium hydride. The carbon monoxide and hydrogen from the quench overheads (minus the hydrogen recovered for NaH production) is burned as fuel in the sodium reactor heater.

The concept is not entirely novel, as a United States patent was awarded to C. Netto of Germany in 1891 for the production of sodium from sodium hydroxide and carbon (patent number 460,985). In a patent filed in 1955 (patent number 2,930,689), McGriff moved the technology further. Among other ideas, he patented the concept of the sodium carbonate reactor.

Figure 2 contains a mass balance on the process based on 100 weight units of sodium hydroxide solution charged to the first stage concentrator (nominally kg/h). Also presented is the estimated duty of the heaters and coolers. The material balance is based on a process in which natural gas is used as both the carbon source for the sodium reactor and also to meet the process heating requirements.

Figure 3 shows a financial analysis of the NaH manufacturing process. We use a pro-forma cash flow model with capital, feedstock, and O&M costs as inputs. We then adjust the plant gate cost of sodium hydride to achieve an internal rate of return of 10% based on the after-tax cash flow.

The primary inputs into the financial analysis model are as follows:

PowerBall Technologies, LLC estimates it will cost \$1 million to build a pilot plant with a capacity of 45 kg/hr of sodium hydride production (unit cost \$22,000/kg/hr). Energetics has reviewed the cost estimate based on the results of the heat and material balance. The pilot plant makes enough sodium hydride per year to supply power balls to roughly 250 passenger vehicles. Our financial analysis is based on a commercial unit that produces 450 kg/hr of sodium hydride with a unit cost of \$10,000/kg/hr of NaH production capacity.

The O&M cost is estimated to be 6% of capital. This rather high estimate is based on the corrosive nature of the materials involved leading to frequent parts replacement, and the high labor cost associated with ensuring safe operation.

The natural gas consumption is 1.0 kg per kg of NaH production based on the material balance shown in Figure 2. The cost of natural gas is assumed to be \$.42 /MMBtu (\$.115 /kg, Annual Energy Outlook 1997 for industrial customers in the year 2000).

We estimate that the sodium hydride balls will need to be transported via truck an average of 50 miles from the sodium hydride production plant to the dispensing stations. Also, the sodium hydroxide will be transported from the dispensing stations back to the sodium hydride production facility. We estimate the cost of truck transportation to be 10 cents per kg of hydrogen delivered to the vehicle.

The base case analysis gives a sodium hydride plant gate cost of \$.44/kg which is substantially less than

the cost derived from sodium chloride electrolysis of \$3.8/kg. An NaH cost of \$0.44 /kg translates to a delivered hydrogen cost of \$5.3/kg. Table 1 shows that the natural gas feedstock represents 27% of the total sodium hydride manufacturing cost. As we have shown, the full life-cycle energy consumption of the base case sodium hydride process is high: 4.0 kWh of energy per kWh of hydrogen delivered to the vehicle (see addendum), compared to 2.2 and 1.7 for liquid hydrogen and compressed hydrogen gas, respectively. Notice that the truck transportation cost is a significant portion of the total cost.

Table 1. Cost break-down for NaH production		
	cost \$/kg NaH	percent of total cost
Natural gas (\$2.4/MMBtu)	0.12	27%
O&M (6% of capital)	0.08	17%
Capital recovery (10% IRR)	0.15	33%
Truck transportation	0.10	23%
Total	0.44	

Methods for Further Reducing the Sodium Hydride Production Cost

Figure 4 shows an alternative system in which spent sodium hydroxide from the vehicles is sold as a chemical feedstock and the sodium hydride manufacturing process is fed spent sodium hydroxide solution from industry. This process is considered feasible because 1) the spent sodium hydroxide from the vehicles should be relatively pure, and 2) the NaH production process being developed by PowerBall Technologies, LLC should be relatively tolerant of impurities and able to accept low-value spent sodium hydroxide solution. The system in Figure 4 will generate additional revenue due to the price differential between the caustic solution sold as a commodity chemical and the spent caustic taken from industry. The market price for sodium hydroxide solution ranges from 20 to 100 cents per kg. The developers would need to identify a spent industrial caustic that did not coke up the sodium hydroxide drying process. Also significant cost would be incurred in additional storage systems and in handling, marketing, and distributing the sodium hydroxide product. We estimate the net profits from such a system could equal 10 cents per kg of NaH (\$1.20/kg of hydrogen).

Another method of reducing the natural gas cost would be to utilize by-product heat where possible. Table 2 shows the natural gas consumption broken out by its use in the process. Notice that the fuel credit from the syngas in stream 14 largely offsets the fuel required to provide the heat of reaction. By-product heat could be used instead of natural gas to concentrate the NaOH solution.

Table 2. Natural gas consumption in the NaH production process			
Stream number (from Figure 2)	Process use	Natural gas use	
		(kg CH ₄ / kg NaH)	percent of total
10	Fuel for concentrating the NaOH solution	0.32	21%
11	Reagent in the sodium reactor	0.64	42%
12	Fuel to provide heat of reaction	0.57	37%
	Subtotal	1.53	
14	Fuel credit from the by-product CO and H ₂	-0.53	-35%
Total		1.0	

Another strategy for reducing costs is to substitute another hydrocarbon for natural gas. Because the natural gas charged to the sodium reactor is a carbon source for reaction {2}, the key criterion for displacing reactor feedstock is the cost per carbon atom. Table 3 shows the cost per carbon of several hydrocarbon feedstocks. No. 6 oil represents a 20% reduction compared to natural gas. Coal represents a 65% reduction in feedstock costs but would require increased capital for drying and solids handling equipment. Interestingly, diesel is more expensive per weight of carbon than natural gas.

Table 3. Hydrocarbon cost, \$/kg of carbon		
Hydrocarbon	Cost	
	\$/MMBtu*	\$/kg carbon
Natural gas	2.42	0.154
Diesel	4.40	0.198
No. 6 Oil	2.55	0.114
Coal	1.48	0.050
* Annual Energy Outlook 1997, Industrial users 2000		

Alternately, if a less expensive source of natural gas can be found, this also would lower the overall process cost. Personnel from PowerBall Technologies, LLC, have stated that stranded natural gas

assets can be obtained for as little as \$0.68/MMBtu, which is equivalent to \$.043/kg carbon. This would lower the cost of NaH production from \$0.44/kg NaH to \$0.36/kg NaH. However, while this may open up applications in some areas, it is unlikely that this cost of natural gas could be maintained on a large-scale basis.

Table 4 compares the cost of liquid and compressed gaseous hydrogen estimated by Air Products and Chemicals in a study conducted with Directed Technologies for Ford Motor Company. The table shows that even under the aggressive low-cost scenario the sodium hydride system is more than twice as expensive as compressed hydrogen gas from a gas-station-sized steam methane reformer.

Table 4. Cost of delivered hydrogen from several onboard storage technologies		
	Cost of delivered hydrogen \$/kg	Minimum number of vehicles served
Liquid hydrogen	2.8	400,000
Compressed gaseous hydrogen from a gas-station-sized steam methane reformer (100 factory built units)	1.4	1,000 per station, 100,000 total
Sodium hydride balls, base case	5.3	2,500
Sodium hydride balls, low cost case based on treatment of spent sodium hydroxide	4.1	2,500

The results from Table 4 should not discount the sodium hydride option. The liquid hydrogen cost is for a relatively large system. Small quantities of merchant, liquid hydrogen can be much more expensive, in the \$5-7/kg range. With respect to gaseous hydrogen, in order to perform a comprehensive comparison, one must consider the cost of the onboard storage system. Table 5 shows the estimates for the cost of the onboard storage system for compressed gas, liquid hydrogen, and NaH systems. The sodium hydride system is inherently low-cost, and Table 5 shows that when levelized over the life of the vehicle, the cost of the onboard storage system per kg of hydrogen delivered to the power system is significant. This narrows the gap on the overall cost of using sodium hydride storage instead of compressed hydrogen: \$4.76/kg for the NaH-based process (including profit from sale of NaOH) and \$2.3/kg for compressed hydrogen. The cost for the liquid hydrogen system based on the same analysis is \$3.3/kg.

Table 5. Onboard storage system cost analysis (systems with a storage capacity of 4 kg hydrogen)			
	Unit cost \$/kg	Total cost \$	Levelized cost \$/kg H ₂ *
Compressed gas	190	760	0.88
Liquid hydrogen	100	400	0.46
Sodium hydride	100	400	0.46
*The capital recovery factor for the onboard hydrogen storage system equals 5.75 (based on an 8 year life and 8% interest rate). The levelized cost of the onboard storage system equals the annualized cost (initial cost / capital recovery factor) divided by the kg consumed by the vehicle per year. We assume a vehicle consumes 150 kg of hydrogen per year (80 miles per kg, 12,000 miles per year).			

Energy Consumption in the Sodium Hydride-based Hydrogen Storage System

There are four sources of energy consumption associated with the sodium hydride system: 1) drying the sodium hydroxide, 2) raising the temperature of the system to 980C, 3) regenerating the hydride from the hydroxide, and 4) producing hydrogen from the hydride on-board. Table 6 below shows the various energy sinks in the sodium hydride-based hydrogen energy pathway.

By far the largest source of energy loss is in the conversion of sodium hydroxide to sodium hydride. Equation {2} below shows the primary conversion reaction.

The energy consumed by the conversion equals the heat value of the methane charge minus the heat value of the by-product carbon monoxide and hydrogen, plus the heat required to drive the reaction.

Energy required to convert NaOH to NAH	=	Heat value of stoichiometric methane	-	Heat value of by- product CO and H ₂	+	Heat of Reaction, 93.4 kcal/mole
--	---	--	---	---	---	-------------------------------------

Table 6. Energy losses in the sodium hydride-based hydrogen energy pathway

Process stage	Heat lost, Btu of thermal energy per Btu of hydrogen energy delivered to the vehicle	Notes
Drying the sodium hydroxide solution*	0.44	Assume a two stage drying process; the first stage takes the solution from 50% to 75%, and the second takes it from 75% to 100%. Assume the steam from the second stage is re-condensed in the first stage.
Raising the temperature of the reactants to 980C	0.22	Assume 50% of the duty is achieved via heat integration
Conversion of sodium hydroxide to sodium hydride	2.81	Assume by-product CO and H2 are burned for heat value in an 80% efficient burner. Heat consumption includes the heat value of the methane consumed.
Conversion of sodium hydride to hydrogen fuel onboard	0.55	Exothermic reaction with water produces heat onboard the vehicle, which is dissipated.
Total	4.02	
Note that for this analysis we have assumed a 50 wt % solution as opposed to 30 wt % in the base case analysis contained in the report. This reduces the amount of water that must be boiled off per unit of sodium by a factor of 2, although the impact on the overall energy consumption is small.		

One mole of methane is consumed per each mole of sodium hydroxide reacted. Based on the heat of combustion of the natural gas consumed, 191.8 unit of heat energy are consumed per mole of sodium hydroxide reacted.

$$\begin{array}{rcl}
 \frac{1 \text{ mole CH}_4}{1 \text{ mole Na}} & * & \frac{191.8 \text{ kcal}}{\text{mole CH}_4} \\
 & & = 191.8 \text{ kcal heat / kcal NaOH reacted}
 \end{array}$$

The heating value of by-product hydrogen and carbon monoxide is calculated as follows:

$$\begin{array}{rcl}
 \text{Hydrogen} & \frac{2 \text{ mole H}_2}{\text{mole NaOH}} * & \frac{28,700 \text{ kcal}}{\text{kg H}_2} * \frac{0.002 \text{ kg H}_2}{\text{mole H}_2} = 114.8 \text{ kcal / mole NaOH}
 \end{array}$$

$$\begin{array}{rcl}
 \text{Carbon Monoxide} & \frac{1.0 \text{ mole H}_2}{\text{mole NaOH}} * & \frac{2,415 \text{ kcal}}{\text{kg CO}} * \frac{0.028 \text{ kg CO}}{\text{mole CO}} = 67.6 \text{ kcal / mole NaOH}
 \end{array}$$

Note that the amount of hydrogen is reduced from 2.5 moles to 2.0 moles to account for the hydrogen consumed in making NaH from Na:

To calculate the net energy requirement from the reactor we assume that the hydrogen and CO burner is 80% efficient, and also that the transfer of heat into the reactor vessel is 80% efficient. The energy consumed is thus:

$$191.8 + 93.4 / 0.8 - 0.8 * (114.8 + 67.6) = 162.6 \text{ kcal/mole NaOH reacted}$$

For each mole of sodium hydroxide, one mole of hydrogen is provided to the vehicle power system. Each mole of Na is converted to NaH using a portion of the byproduct hydrogen as shown in reaction {3}. Since the heat from this exothermic reaction is non-recoverable, it is not included in this calculation.

Next, the 162.6 kcal/mole NaOH must be expressed in a hydrogen-equivalent manner. Each mole of NaH provides one mole of hydrogen to the vehicle power system upon reaction with water as shown in reaction {1}.

Based on a lower heating value of hydrogen of 57.8 kcal/mole, energy consumption is as follows.

$$\frac{162.6 \text{ kcal}}{\text{mole NaOH}} * \frac{1 \text{ mole NaOH}}{1 \text{ mole H}_2} * \frac{1 \text{ mole H}_2}{57.8 \text{ kcal}} = 2.81 \text{ kcal energy / kcal hydrogen}$$

The total energy consumed by the sodium hydride pathway, 4.02 kcal of energy per unit of hydrogen energy delivered, is high compared to liquid and pressurized gaseous storage (2.2 and 1.7 Btu energy per Btu of hydrogen delivered respectively). The estimate is credible when one considers that the overall steam methane reforming reaction as shown below produces four hydrogen molecules per methane molecule compared to only one hydrogen molecule per methane in the sodium hydride process.

Weight and volume density of the onboard hydrogen storage system

Weight density is defined as the kg of hydrogen fuel delivered to the on-board power system divided by the total weight of the hydrogen storage system, including ancillary equipment. Similarly, volume density is defined as the kg of hydrogen delivered to the vehicle per cubic meter of space that the hydrogen

storage system takes up.

In order to develop a weight and volume density estimate, we characterized a sodium hydride-based hydrogen storage system designed to deliver 4.09 kg of hydrogen (a vehicle range requirement of 380 miles and a fuel efficiency of 93 miles per kg of hydrogen). Twelve kg of sodium hydride are required for each kg of hydrogen delivered to the PEM fuel cell, giving a total sodium hydride requirement of 49 kg.

PowerBall claims that they are able to compact NaH to a density of 1.1 g/cc. Thus, a 1.5-inch diameter ball would hold 0.0319 kg of NaH; 1,540 balls would be required to hold a total of 49 kg of NaH. At the peak rate of hydrogen consumption by the PEM fuel cell, the ball slicer will be cutting NaH balls at the rate of fourteen per minute to maintain hydrogen supply.

The onboard hydrogen storage system is shown in Figure 5 and works as follows: As the PEM fuel cell is operated it draws hydrogen gas from the storage system. A ball-slicing device retrieves a plastic-coated sodium hydride ball from the inventory and slices it open so that the sodium hydride is contacted with the water, producing hydrogen gas. The rate of ball slicing is controlled to maintain the pressure in the tank between 120 and 150 psi.

The ball slicing device developed by PowerBall Technologies, LLC works as follows. A ball is corralled into a cartridge tube. The cartridge is then closed and a burst of high-pressure hydrogen gas accelerates the ball through a blade assembly and into a water reservoir where the sodium hydride reacts to form hydrogen gas. The high-pressure hydrogen gas is produced by a small intensifier that takes 120 psi hydrogen gas from the main containment vessel and divides it into a high-pressure stream (250 psi) and a low-pressure stream (30 psi). The high-pressure stream is used by the ball slicer, and the low-pressure stream is discharged to a small buffer tank that feeds the PEM fuel cell. This is a somewhat complex system compared to an electric motor slicer, but it has the advantage that it does not represent a parasitic load and actually helps dissipate some of the thermal energy from the sodium hydride reaction.

Because the PEM fuel cell produces water as a by-product (the overall electrochemical reaction is shown below), it can supply the water required for the sodium hydride reaction, thus lowering the required weight of the system.

Inspection of reactions {1} and {5} indicates that the fuel cell could provide all the water required by the sodium hydride system. However, practical considerations require extra water: 1) some of the water produced in the PEM fuel cell escapes in the wet exit gas; 2) a water inventory is needed for start-up; and 3) it is possible that sodium hydroxide, being hygroscopic, may become associated with reactant water, making some of the water unavailable for reaction (this issue requires further investigation; it could increase the system water requirement and/or necessitate on-board dehydration and segregation of the sodium hydroxide product). Thus, we assume the initial water inventory equals 50% of the

stoichiometric requirement.

Because the reaction {1} is strongly exothermic, the storage system will likely heat up during vehicle operation. We estimate the sodium hydride storage system will increase the onboard cooling duty by 100% and increase the weight of the radiator system by 75%.

The containment vessel will consist of a plastic liner for corrosion resistance and a stainless steel or carbon/glass fiber shell to provide strength. If stainless steel is used, the weight of the vessel could be 30 kg. We have lowered the estimate of the containment vessel to 20 kg assuming advanced materials are used.

Table 7 shows the weight and volume of the components of the sodium hydride hydrogen storage system. The sodium hydride balls are the primary component, representing 56% of the weight and 51% of the volume. This indicates that significant weight and cost reductions below the estimates presented are unlikely to be achieved in real systems.

Table 7. Estimated size and weight of a Power Ball system designed to deliver 4.1 kg of hydrogen to a vehicle power system		
Component	Weight (kg)	Volume (m ³)
Sodium hydride balls	49	.0445
Water	18.4	.0184
Vapor space	Negligible	.0249
Container	20	negligible
Incremental radiator requirement	7	negligible
Ball slicer	3	negligible
Total	97.4	0.0879
Weight density	4.2%	
Volume density	46.6 kg/m ³	

Interestingly, the storage system gets heavier as hydrogen is consumed. This is because water from the PEM fuel cell that would otherwise be discharged from the vehicle is reacted with sodium hydride and the oxygen atom is captured in the sodium hydroxide product. Assuming that 10% of the water content remains with the depleted system, we estimate the weight of a fully depleted tank to be 113.6 kg. This is an equivalent weight density of 3.6%.

Figure 6 shows that the sodium hydride system weighs more than compressed hydrogen gas and liquid hydrogen, but is more compact. That trade-off is similar to the one presented by magnesium hydride systems. The primary performance difference between the magnesium hydride systems and the sodium

hydride/water system is that the magnesium system's hydrogen release reaction is endothermic (it uses waste heat from the onboard power system and/or burns a portion of the hydrogen parasitically), whereas the sodium hydride system generates a large amount of heat when it releases hydrogen. This means that the sodium hydride is simpler in that it does not have to be heat integrated with the on-board power system. On the other hand, because the heat generated onboard is lost, the sodium hydride system is inherently less energy-efficient.

The density analysis above assumes that the reaction of the cut sodium hydride pellets and water will be essentially stoichiometric. In fact, in the absence of mixing, the reaction will become diffusion limited, and consequently less efficient on a kinetic basis. As a result, excess water will need to be used to increase the reaction rate. At a reasonable value of 1.5 times stoichiometric for the amount of water needed, the weight density of the system is reduced to 3.8 % (3.3% based on a depleted tank), and the volume density is about 42.2 kg/m³.

Other Concerns

Materials Concerns

Sodium hydride is regarded as an extremely reactive material and any system using it will come under close scrutiny for safety. Of concern is the potential for a chain reaction, in which the coating of one of the balls in the ball storage tank breaks for whatever reason (perhaps in a car crash) and reacts with water. The heat from this reaction then melts the coating of another balls and so on. A full safety analysis of the proposed on-board storage system is needed.

The density of NaH as claimed by PowerBall is 1.1 g/cc. This is the value we used above to calculate weight and volume system densities. Literature values for NaH, however, indicate that the density is actually 0.92 g/cc. With this lower density, the volume required for the PowerBalls would be about 16 % higher (including air space, 27% higher) than shown in Table 7.

Sodium hydroxide, though commonly used, is a caustic material and is hazardous. Siting of NaOH storage tanks in commercial areas where vehicle service stations are typically sited could cause resistance from local authorities. Also, onboard storage of sodium hydroxide solution will require Department of Transportation approval.

Above 30 wt%, aqueous solutions of sodium hydroxide freeze above 0 degrees Celsius. The NaH system must be designed to either avoid high concentration of sodium hydroxide to manage frozen reactant products.

Engineering/Processing Concerns

The storage system cost estimate may be low in that it does not include extensive coolant systems, buffer tanks, and interconnectivity. Nor is a method included for removal of the spent hydroxide liquid and refilling the tanks with water and PowerBalls. It has been hypothesized that the hydrogen-liberating

reaction can be run stoichiometrically, leaving a dry hydroxide product, which would be easy to remove. Such a system would likely be difficult to control, especially due to the hygroscopic nature of NaOH.

The upcoming operation of the PowerBall Technologies, LLC pilot plant will be very instructive regarding the feasibility of sodium hydroxide-fed sodium hydride production. Anticipated issues include: corrosion of the submerged heater, coking in the sodium hydroxide dryer, temperature controls in the reactor, recovering heat from the sodium reactor heater, and recovering hydrogen from the reactor off-gas. A more detailed process cost estimate should be completed after the benefits of the pilot plant operation are available.

If the operating pressure of the onboard storage system were raised, it would be possible to power the PEM fuel cell air compressor via a hydrogen-fed expansion turbine. In addition to reducing the parasitic electric load of the air compressor, the expander would reduce the cooling requirements. This concept has been investigated for pressure vessel systems. It was largely abandoned because of cost and also because the pressure is gradually reducing as the tank is emptied. In the sodium hydride system, the pressure can be controlled over the full storage cycle by varying the rate of ball slicing. However, a high-pressure system would require a heavier containment tank. The trade-offs associated with this concept should be investigated in more detail.

Garnering additional revenues by supplying the sodium hydride production process with spent industrial caustic solution can substantially reduce the cost of sodium hydride. In many cases spent industrial caustic solutions fall under environmental regulations. Such regulations could affect handling requirements of the feedstock and the solids from the bottom of the sodium reactor and heater. Such regulations, if applicable, could diminish the economic incentives. A set of environmental case studies could be useful to assess the feasibility of this concept.

Environmental Concerns

Aside from the environmental concerns voiced above, dealing with the handling of NaOH, there is the question of CO₂ emissions. The regeneration reaction (reaction (2)) is powered by burning methane, CO and hydrogen, resulting in the formation of CO₂. The amount of CO₂ produced is likely greater than current gasoline engines given the 4 to 1 energy requirement to deliver hydrogen. On the other hand, CO₂ production in the PowerBall case would be centralized, and therefore amenable to sequestration options. Overall CO₂ to the atmosphere would therefore likely be less. At any rate, if the PowerBall option is to be viable, greenhouse gas effects need to be given a closer look.

Conclusions

The base case cost of the sodium hydride system corresponds to a cost of hydrogen delivered to the vehicle power system of \$5.30/kg. A low-cost scenario reduces this cost to \$4.10/kg. The low-cost case is twice as expensive than costs predicted for compressed hydrogen gas systems. However, the fact that the sodium hydride system is amenable to geographically dispersed hydrogen vehicles, and that it promises a relatively low-cost on-board storage system, may make it attractive. Including the on-

board equipment, the low-cost case of the PowerBall system is a little over \$1/kg more expensive than a comparable liquid hydrogen system, and a little over \$2/kg H₂ more expensive than a compressed hydrogen system. The safety features and ease of transportation of the encapsulated NaH pellets increases the attractiveness of the system, making it of interest at least to niche markets.

An onboard hydrogen storage system using plastic-coated balls of sodium hydride may achieve a hydrogen storage density of 4.3 wt% and 47 kg/m³ including all ancillary equipment. This is heavier, but more compact than compressed gas and liquid hydrogen systems.

Figure 1. Schematic Of The Sodium Hydride-based Hydrogen Storage And Delivery System

Figure 2
Block Diagram and Mass Balance of the
Power Ball Na/NaH Production System

Flow Rates in kg/h

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
NaOH	30		30		30	30									
Na							17.25		17.25						
NaH															18.75
C															
CO							21.0	21.0						21.0	
H ₂ O	70	57	13	13											
CH ₄						12				5.9	12	0.6			
H ₂							3.75	3.75					1.5	2.25	
Total	100	57	43	13	30	42	42	24.75	17.25	4.9	12	0.6	1.5	23.25	18.75
Temp °C	20	120	120	320	320	320	980	500	500	20	20	20	300	300	

Figure 3. Analysis of PowerBall's Sodium-Based Hydrogen Storage Concept, Cash Flow from NaH Production

[illegible]

Figure 4. Potentially Higher Value System that also Provides Management of Spent Sodium Hydroxide Solution from Industry

Figure 5. Schematic of a PEM Fuel Cell/Power Ball
Hydrogen Storage On-board Power System

Figure 6. Hydrogen Storage Density*

* Based On Systems That Store 4.1 Kg Of Hydrogen

Addendum: Addressing A Change to the PowerBall Process

Note: To avoid confusion, we are continuing with the equation numbering scheme that was used in the main report.

PowerBall, Inc. has recently proposed a change to their overall schematic for producing and recycling their sodium hydride pellets. In their new scenario, they indicate that the overall reaction for the recycling process will be:

If this is combined with the on-board hydrogen-generation reaction:

the result is:

So that in effect one mole of methane is being used to produce two moles of hydrogen.

PowerBall has indicated that a key factor in determining the viability of the recycling process that is being discussed here is the question of whether reaction {6} is exothermic. Reaction {6} is indeed exothermic, releasing 15.8 kcal/mole of methane.

However, some discussion is necessary as to the importance of this exothermicity. Reaction {6} is the result of a series of reactions and processes that involve the transfer of heat and mass, and thus any rational analysis must be based on a calculation that takes each of the individual component reactions into account. According to information supplied by PowerBall, the reaction would be carried out by first reacting methane with sodium hydroxide as in the previous scheme:

½ mole of hydrogen would still react with the sodium:

This leaves 2 moles of hydrogen and one mole of CO – a “syngas” mixture.

PowerBall then claims that about one half of the syngas can be combusted to provide the heat to run reaction {2}.

In order to provide the correct stoichiometry, we will use half of the CO, but only 0.5 mole of hydrogen:

The remainder of the syngas, ½ mole of CO and 3/2 mole of hydrogen could then produce methane and water in the “reverse reforming” mode:

The methane product of reaction {8} can then be recycled to reaction {2}, etc. Thus, each subsequent recycling reclaims 1/2, 1/4, 1/8, 1/16, etc. moles of CH₄ for further reaction.

As the recycling continues, the theoretical limits to equations {2}, {3}, {7}, and {8} become:

which combine to produce:

Thus, stoichiometrically, it is true as PowerBall has contended, that one mole (16 grams) of methane will produce two moles (48 grams) of sodium hydride, which will in turn lead to the on-board production of two moles (4 grams) of hydrogen:

However, the overall exothermicity of equation {6} of -15.8 kcal, includes reaction {3'} as one of its components. This reaction occurs separately from the main recycling system, and its released heat cannot be used to aid in the recycle process. The reaction is exothermic by 28 kcal. Thus, the recycle process, which is composed of reactions {2}, {7'}, and {8'} combine as follows:

is actually endothermic by 12.2 kcal in total, or by 12.2/2 = 6.1 kcal/mole of NaOH reacted

Even more important is the fact that in order to follow the recycling process scheme as described by PowerBall, and shown here by reactions {2}, {3}, {7}, and {8}, the reaction {2} products must be followed by separation into 4 product streams:

with the first and second streams reacted to regenerate the sodium hydride by reaction {3}, the third stream reacted to liberate energy for recycling in the system by reaction {7}, and the fourth stream reacted to form methane by reaction {8}.

It should be further pointed out that yet another separation is then necessary – the methane produced in reaction {8} must be separated from the water before being reintroduced into reaction {2}.

Reaction {2} must be run a high temperature to produce the desired products. This is evident from Figure A, which shows the major species that occur in equilibrium between an equimolar mixture of liquid NaOH and CH₄. To form sodium, the reaction is best run at a temperature greater than 1200 K (927 C) and preferably closer to 1300 K (1027 C). In order to separate sodium from this mixture, the gases must be irreversibly quenched to a low temperature, thus freezing the high temperature mixture composition. The quenching of the products has some energy loss associated with it. In addition, although the conversion of sodium is high, it is not 100%, and thus there will be some loss of sodium in this process.

Figure A. Equilibrium composition of an equimolar mixture of methane and sodium hydroxide (CH₄ + NaOH_(L))

Another form of loss that will occur is the energy expenditure and less than unity conversion efficiency from each of the 5 separation processes described above.

We can now repeat the analysis for energy consumption that was presented in the main body of the report, modified based on the new set of equations:

We note that the energy consumed by the conversion now equals the heat value of the methane charge plus the heat required to drive the reaction. The heating value of the syngas is now incorporated into the equation (equation {9}). Note, however, that there is now more Na produced per unit methane.

One mole of methane is consumed for every two moles of sodium hydroxide reacted. Based on the heat of combustion of the natural gas consumed, 191.8 unit of heat energy are consumed for every two moles of sodium hydroxide reacted.

$$\frac{1 \text{ mole CH}_4}{2 \text{ mole Na}} \times \frac{191.8 \text{ kcal}}{\text{mole CH}_4} = 95.9 \text{ kcal heat / kcal NaOH reacted}$$

This is the heating value of stoichiometric methane, and is added to the heat of reaction {9}, 6.1 kcal/kcal NaOH reacted:

= 102.0 kcal/mole NaOH reacted. This is substantially lower than the energy requirement (162.6 kcal) for the original process.

On a hydrogen basis, as before, the energy requirement on a per hydrogen unit energy basis is calculated using the lower heating value of hydrogen:

$$\frac{102.0 \text{ kcal}}{\text{mole NaOH}} \times \frac{1 \text{ mole NaOH}}{1 \text{ mole H}_2} \times \frac{1 \text{ mole H}_2}{57.8 \text{ kcal}} = 1.76 \text{ kcal energy input / kcal hydrogen.}$$

We could also consider using the heat generated during the hydride production process,

-14 kcal/mole Na, as a drying source for NaOH. Recall that Table 6 showed the need of 0.44 energy units per energy unit of hydrogen produced to dry the hydroxide. Since each mole of Na eventually converts to one mole of hydrogen, the production of 57.8 kcal of hydrogen is preceded by the production of 14 kcal of heat during the hydriding step. Thus, there is a gain of $14/57.8 = 0.24$ energy units/energy units of hydrogen produced due to the hydriding step. If we assume an 80% heat transfer, this is still 0.19 units. This reduces the need of fuel to $0.44 - 0.19 = 0.25$ units for this step.

We can then modify Table 6 to incorporate these changes.

Table 6'. Energy losses in the sodium hydride-based hydrogen energy pathway		
Process stage	Heat lost, Btu of thermal energy per Btu of hydrogen energy delivered to the vehicle	Notes
Drying the sodium hydroxide solution*	0.25	Assume a two stage drying process; the first stage takes the solution from 50% to 75%, and the second takes it from 75% to 100%. Assume the steam from the second stage is re-condensed in the first stage.
Raising the temperature of the reactants to 980C	0.22	Assume 50% of the duty is achieved via heat integration
Conversion of sodium hydroxide to sodium hydride	1.76	Includes the heating value of the methane used
Conversion of sodium hydride to hydrogen fuel onboard	0.55	Exothermic reaction with water produces heat on-board the vehicle, which is dissipated.
Total	2.78	
Note that for this analysis we have assumed a 50 wt % solution as opposed to 30 wt % in the base case analysis contained in the report. This reduces the amount of water that must be boiled off per unit of sodium by a factor of 2, although the impact on the overall energy consumption is small.		

In trying to look at the cost of the revised process, we must consider the fact that we have dropped the sodium carbonate heater and added what might be at first considered a more direct heating mechanism. However, due to the batch nature of the process, we are actually dealing with a different indirect heater – the walls of the reactor. We are also faced with the need either for a larger reactor to accommodate air as an oxygen supply, or to purchase reactant oxygen. Finally, we need a separate reactor to perform the reverse reforming reaction.

In addition, as already pointed out, the new process requires an increase in the number of separations necessary to provide reaction materials. In addition to the separation of sodium (already a factor in the original scheme) the separation of reaction {2} syngas components into three fractions would also be required. This would be manifested as 1) one-fifth of the H₂ for hydriding the sodium (as in the original system), 2) one-fifth of the H₂ and half of the CO to be combusted to provide heat, and 3) three-fifths of the H₂ and the other half of the CO to convert to methane. The separation of product methane from

water represents yet another process. Membrane systems and pressure regulators could likely be set up to approximate this type of separation, but performing this inexpensively and efficiently represents a challenge to the project.

The improved utilization of methane as depicted by this revised process is offset by the additional expenses that are likely to be incurred by:

- The need for a separation process to provide the proper stoichiometry for the syngas combustion and the methane regenerating reactions,
- Either the need for a bigger reactor to accommodate air to oxidize the syngas, or the increased operating expenses that will be incurred to supply oxygen for the same process,
- The greater losses of efficiencies that come with more complex processes,
- The additional reactor needed to regenerate methane.

Disclaimers

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government, or any agency thereof.

This research report was prepared by Energetics, Incorporated as an account of work sponsored by the United States Department of Energy, Office of Energy Efficiency and Renewable Energy Under Cooperative Agreement Number DE-FC36-98GO10291. Because of the nature of the work performed, neither Energetics, Incorporated nor any of its employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by Energetics, Incorporated.