SAND REPORT

SAND2002-3131

Unlimited Release

Printed October 2002

Development of a Risk-Based Probabilistic Performance-Assessment Method for Long- Term Cover Systems—2nd Edition

Clifford K. Ho, Bill W. Arnold, John R. Cochran, and Randal Y. Taira

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation,
a Lockheed Martin Company, for the United States Department of
Energy under Contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.

Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865)576-8401
Facsimile: (865)576-5728
E-Mail: reports@adonis.osti.gov
Online ordering: <http://www.doe.gov/bridge>

Available to the public from

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Rd
Springfield, VA 22161

Telephone: (800)553-6847
Facsimile: (703)605-6900
E-Mail: orders@ntis.fedworld.gov
Online order: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>

SAND2002-3131
Unlimited Release
Printed October 2002

Development of a Risk-Based Probabilistic Performance-Assessment Method for Long-Term Cover Systems—2nd Edition

Clifford K. Ho, Bill W. Arnold, and John R. Cochran
Sandia National Laboratories
P.O. Box 5800
Albuquerque, New Mexico 87185
Contact: ckho@sandia.gov
(505) 844-2384

Randal Y. Taira
Pacific Northwest National Laboratory
4500 Sand Point Way NE, Suite 100
Seattle, WA 98105

Abstract

A probabilistic, risk-based performance-assessment methodology has been developed to assist designers, regulators, and stakeholders in the selection, design, and monitoring of long-term covers for contaminated subsurface sites. This report describes the method, the software tools that were developed, and an example that illustrates the probabilistic performance-assessment method using a repository site in Monticello, Utah. At the Monticello site, a long-term cover system is being used to isolate long-lived uranium mill tailings from the biosphere. Computer models were developed to simulate relevant features, events, and processes that include water flux through the cover, source-term release, vadose-zone transport, saturated-zone transport, gas transport, and exposure pathways. The component models were then integrated into a total-system performance-assessment model, and uncertainty distributions of important input parameters were constructed and sampled in a stochastic Monte Carlo analysis. Multiple realizations were simulated using the integrated model to produce cumulative distribution functions of the performance metrics, which were used to assess cover performance for both present- and long-term future conditions. Performance metrics for this study included the water percolation reaching the uranium mill tailings, radon gas flux at the surface, groundwater concentrations, and dose. Results from uncertainty analyses, sensitivity analyses, and alternative design comparisons are presented for each of the performance metrics. The benefits from this methodology include a quantification of uncertainty, the identification of parameters most important to performance (to prioritize site characterization and monitoring activities), and the ability to compare alternative designs using probabilistic evaluations of performance (for cost savings).

Acknowledgments

This work was funded by the U.S. Department of Energy EM-50 Technical Task Plan AL21SS22 “Risk-Based Performance Assessment of Long-Term Cover Designs for Waste Isolation and Disposal at DOE Facilities.” Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy under Contract DE-AC04-94AL85000.

Preface to the 2nd Edition

This report provides a comprehensive summary of the work conducted between 2000-2002 for the U.S. Department of Energy EM-50 Technical Task Plan AL21SS22 “Risk-Based Performance Assessment of Long-Term Cover Designs for Waste Isolation and Disposal at DOE Facilities.”. It supersedes an earlier report (SAND2001-3032) published after the first year of the project titled, “Development of a Risk-Based Performance-Assessment Method for Long-Term Cover Systems—Application to the Monticello Mill Tailings Repository,” by Ho et al. (2001). Additional information and results have been produced during the second year of the project and are included in this report. For completeness and convenience, all of the information presented in the first report is contained in this report as well. Additional information reported in this second edition includes the following:

- *Evaluation of an alternative evapo-transpiration (ET) cover design (Sections 4.3.1 and 4.5)* with simulation of all four performance metrics (water percolation through the cover, radon gas flux through the cover, groundwater concentration, and peak cumulative dose).
- *Additional uncertainty quantification for the base-case-composite and alternative-ET cover designs (Section 4.5)*—illustrates how probabilistic results can be used to estimate probability of exceeding regulatory or performance metrics.
- *Comparison between alternative designs for each scenario and performance metric (Section 4.5)*—illustrates how alternative designs can be compared to minimize cost while ensuring adherence to relevant regulatory requirements and performance metrics.
- *Additional results and descriptions of sensitivity analyses for each scenario, design, and performance metric (Section 4.6)*—demonstrates how parameters important to long-term performance can be identified for prioritizing characterization and monitoring studies.
- *Description of computer modules that were added to FRAMES for stochastic analyses (Appendix A)*. These include the radon-gas-transport code, RAECOM, and the water-balance code, HELP.

Contents

1. Introduction.....	13
2. Description of Probabilistic Performance-Assessment Process.....	14
3. Description of Monticello Mill Tailings Repository Site	16
3.1 Background	17
3.2 Regulatory Requirements and Performance Metrics.....	19
3.2.1 Regulatory History.....	19
3.2.2 Records of Decision.....	20
3.2.3 Identification of Landfill-Design Regulations	21
3.2.4 Summary of Performance Metrics for the Monticello Repository	23
4. Performance Assessment of the Monticello Mill Tailings Repository	25
4.1 Scenario Development and Screening of FEPs.....	25
4.2 Total-System Framework Model.....	30
4.3 Process-Model Development and Parameter Distributions.....	32
4.3.1 Water Percolation through the Cover	32
4.3.2 Radon Gas Transport through the Cover	36
4.3.3 Source-Term Release	40
4.3.4 Vadose-Zone Transport	42
4.3.5 Saturated-Zone Transport	44
4.3.6 Human Exposure.....	46
4.4 Results and Discussion of Base-Case Composite Design	48
4.4.1 Percolation through the Composite Cover	48
4.4.2 Radon Gas Flux at the Surface.....	49
4.4.3 Groundwater Concentration and Exposure Assessment for the Shallow Alluvial Aquifer	51
4.4.4 Groundwater Concentration and Exposure Assessment for the Burro Canyon Aquifer.....	53
4.5 Results and Discussion of Alternative Designs and Scenarios	55
4.5.1 Percolation through the ET Cover	55
4.5.2 Radon Gas Flux at the Surface.....	57
4.5.3 Groundwater Concentration and Exposure Assessment for the Shallow Alluvial Aquifer	59
4.5.4 Groundwater Concentration and Exposure Assessment for the Burro Canyon Aquifer.....	61
4.5.5 Removal of the Liner Beneath the Mill Tailings	62

4.6 Sensitivity Analyses	64
4.6.1 Percolation through the Cover	65
4.6.2 Radon Gas Flux at the Surface.....	66
4.6.3 Groundwater Dose from the Shallow Aquifer	68
4.6.4 Groundwater Dose from the Burro Canyon Aquifer	70
4.6.5 Hypothetical Example and Application of Sensitivity Analyses	72
5. Summary and Conclusions	72
6. References.....	75
Appendix A: Development of Additional Modules for FRAMES.....	79
A.1. Integration of HELP with FRAMES.....	79
A.2. Integration of RAECOM with FRAMES.....	94
Appendix B: Parameter Values and Distributions for Material Properties of the Monticello Cover	99
Uncertainty Distributions for Layer 1	100
Uncertainty Distributions for Layers 2 and 4	102
Appendix C: Stepwise Linear-Regression Method of Sensitivity Analysis	105

List of Figures

Figure 1. Integration between performance-assessment task and other primary tasks in the long-term capping strategy.	16
Figure 2. Map of the Monticello Mill Tailings site and vicinity.	17
Figure 3. Aerial view of the double composite-liner system at the base of the repository.	18
Figure 4. Illustration of the landfill cover and geology.	19
Figure 5. Conceptual model for water percolation (scenarios 1 and 2) and gas transport (scenarios 3 and 4) through a composite (base-case) cover design for present and future conditions. A 3% slope is assumed for the drainage layer. An alternative evapotranspiration (ET) cover design that only consists of Layer 1 is also considered in Section 4.5.	28
Figure 6. Conceptual model for radionuclide transport from the mill tailings to the shallow alluvial aquifer and location of receptor well for present (scenario 5) and future (scenario 6) conditions.	29
Figure 7. Conceptual model for radionuclide transport from the mill tailings to the deep Burro Canyon aquifer and location of receptor well for present (scenario 7) and future (scenario 8) conditions.	29
Figure 8. Screen capture of FRAMES graphical user interface for scenario 5.	31
Figure 9. Cumulative probability distribution of water percolation reaching the mill tailings for present and future conditions (scenarios 1 and 2).	49
Figure 10. Cumulative probability distribution of simulated radon flux at the land surface for present and future conditions (scenarios 3 and 4).	49
Figure 11. Cumulative probability distribution for peak Ra-226 concentration in the shallow alluvial aquifer for present and future conditions (scenarios 5-6). Note: concentration values of 0 are not plotted on the log scale.	52
Figure 12. Cumulative probability distribution for peak cumulative dose for Ra-226 and its progeny from the shallow alluvial aquifer for present and future conditions (scenarios 5-6). Note: dose values of 0 are not plotted on the log scale.	53
Figure 13. Cumulative probability distribution for peak cumulative dose for Ra-226 and its progeny from the Burro Canyon aquifer for future conditions (scenario 8). Note: dose values of 0 are not plotted on the log scale.	55

Figure 14. Cumulative probability distribution of water percolation reaching the mill tailings for present and future conditions (scenarios 1 and 2) and for the evapotranspiration cover.	57
Figure 15. Cumulative probability distribution of radon-222 flux at the landfill cover for present and future conditions (scenarios 3 and 4) and for the evapotranspiration cover.	58
Figure 16. Cumulative probability distribution of Ra-226 concentration in the shallow alluvial aquifer for present and future conditions (scenarios 5 and 6) and for the evapotranspiration cover.....	59
Figure 17. Cumulative probability distribution of peak cumulative dose for Ra-226 and its progeny in the shallow alluvial aquifer for present and future conditions (scenarios 5 and 6) and for the evapotranspiration cover.	60
Figure 18. Cumulative probability distribution of peak cumulative dose for Ra-226 and its progeny in the Burro Canyon aquifer for present and future conditions (scenario 8) and for the evapotranspiration cover.	61
Figure 19. Peak Ra-226 concentration in the shallow aquifer during present-day conditions using the evapotranspiration cover with and without a double composite-liner system beneath the mill tailings.	63

List of Tables

Table 1. Summary of performance objectives applicable to the Monticello Mill Tailings Repository.	24
Table 2. List of features, events, and processes relevant to the Monticello Mill Tailings Repository.	25
Table 3. Summary of scenarios and performance objectives evaluated in this study.....	27
Table 4. Uncertainty distributions for stochastic parameters in the percolation model (see Figure 5 for layer names and descriptions).	34
Table 5. Correlation coefficients between parameters in the percolation model.....	36
Table 6. Parameter values for radon flux model (present conditions).	37
Table 7. Parameter values for radon flux model (future conditions).	38
Table 8. Parameter values for source-term model.	41
Table 9. Parameter values for double composite-liner system in vadose-zone model.	43
Table 10. Parameter values for vadose-zone layer for two aquifers.	44
Table 11. Parameter values for saturated-zone model.	45
Table 12. Parameter values for chronic exposure module.	47
Table 13. Parameter values for receptor intake module.	47
Table 14. Parameter values for human health impact module.	47
Table 15. Summary of parameters important to simulated water percolation through the cover based on stepwise linear-regression analysis (composite cover).	65
Table 16. Summary of parameters important to simulated water percolation through the cover based on stepwise linear-regression analysis (ET Cover).	66
Table 17. Summary of parameters important to simulated radon flux through the cover based on stepwise linear-regression analysis (composite cover).	67
Table 18. Summary of parameters important to simulated radon flux through the cover based on stepwise linear-regression analysis (ET Cover).	67
Table 19. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (composite cover, Shallow Aquifer)	69

Table 20. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (ET cover, Shallow Aquifer).....	70
Table 21. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (composite cover, Burro Canyon Aquifer).	71
Table 22. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (ET cover, Burro Canyon Aquifer).....	71

Intentionally Left Blank

1. Introduction

Long-term cover systems are needed at U.S. Department of Energy (DOE) complexes to assist in isolating contaminants and waste that have migrated into the subsurface near landfills, waste-disposal sites, and high-level waste tanks. The long-term covers are considered to be a vital remedial option for DOE's 2006 Accelerated Cleanup Plan (DOE/EM-0362), which intends to clean up more than 90 percent of the contaminated sites in DOE's Environmental Management Program. In addition, DOE Order 435.1 states that performance assessments are to be conducted for low-level waste disposed after September 26, 1988, and that performance objectives should be evaluated for a 1,000-year period to determine potential risk impacts to the public and environment. However, current landfill-cover design guidelines, such as those stated in the Resource Conservation and Recovery Act, are not risk-based and do not consider long-term site-specific influences such as climate, vegetation, and soils. These design guidelines may not address important long-term features, events, and processes at the site that may contribute to the long-term risk of groundwater contamination and human exposure. In addition, traditional design guidelines for covers often rely on deterministic models of flow and transport processes that neglect uncertainty inherent in actual contaminant transport.

As a result, a probabilistic, risk-based performance-assessment methodology has been developed to assist designers, regulators, and involved stakeholders in the selection, design, and monitoring of long-term covers. This approach considers regulatory requirements, site-specific parameters, engineering-design parameters, and long-term verification and monitoring requirements. Because many of the contaminants are long-lived, this methodology also considers changes in the environmental setting (e.g., precipitation, temperature) and cover components (e.g., liner integrity) for long time periods (>100 years). Uncertainty and variability in important site-specific parameters are also incorporated through stochastic simulations in this method.

Additional benefits of a risk-based performance-assessment method include potential savings in cost, increased public confidence, and useful guidance for associated studies in engineering design, environmental setting, and long-term monitoring. The design and implementation of long-term covers can be very costly, especially if prototypes are designed and implemented without meaningful criteria, leading to poor performance that may violate exposure limits set by regulatory requirements. The inclusion of uncertainty distributions for important input parameters (e.g., material properties, precipitation) addresses the performance of long-term covers under more realistic (and uncertain) conditions and ensures more defensible calculations of long-term performance.

Using performance metrics such as water percolation through the waste, groundwater concentrations, and dose also provides a more concrete metric against which alternative designs can be compared for performance and cost. In addition, the integrated approach of the performance-assessment model ensures a comprehensive, defensible, and traceable process that demonstrates the design selection process in a systematic fashion to regulators and stakeholders, reducing the likelihood of providing costly re-evaluations and demonstrations to address features, events, or processes that were not considered initially. Finally, sensitivity analyses can be used by associated studies in engineering design, environmental setting, and long-term performance to identify parameters that are most important to long-term performance. These

parameters may require additional characterization and monitoring by these groups to reduce the uncertainty in the calculations and to improve the confidence in the models.

The overall objective of this study was to provide these methods and tools to DOE and to document the results in a report that would be available to end-users. In this report, we first define a performance assessment and describe the systematic process to conduct a performance assessment for long-term covers. This method is then illustrated using the Monticello Mill Tailings Repository Site in Monticello, Utah. A general description of the site is provided, and four primary performance objectives based on regulatory requirements are presented. A performance assessment of the repository at the Monticello Mill Tailings Site is then detailed, starting with a description of the conceptual site model and scenarios to be considered. A framework tool for conducting a stochastic analysis is briefly described, followed by a detailed description of each feature, event, and process that is modeled and integrated into the framework tool. Results of alternative designs and sensitivity analyses are then presented and compared to the performance metrics. Conclusions are drawn regarding the performance of the existing cover at Monticello, and comments and recommendations regarding the proposed performance-assessment method for long-term covers are presented.

2. Description of Probabilistic Performance-Assessment Process

As defined by DOE M 435.1-1, a performance assessment is “An analysis of a radioactive waste disposal facility conducted to demonstrate there is a reasonable expectation that performance objectives established for the long-term protection of the public and the environment will not be exceeded following closure of the facility.” In addition, DOE M 435.1-1 also states that the method used for the performance assessment must include uncertainty analyses. A method that addresses these requirements has been used for the Waste Isolation Pilot Plant (DOE, 1996) and Yucca Mountain Project (DOE, 1998) to assess the long-term performance of nuclear waste repositories. Uncertainty analyses and probabilistic approaches have also been used for decommissioning of contaminated sites (Meyer and Gee, 1999; Meyer and Taira, 2001). A similar systematic approach is proposed here to conduct performance assessments for long-term covers. The approach is outlined as follows:

1. Develop and screen scenarios based on regulatory requirements (performance objectives) and relevant features, events, and processes
2. Develop models of relevant features, events, and processes
3. Develop values and/or uncertainty distributions for input parameters
4. Perform calculations and sensitivity/uncertainty analyses
5. Document results and provide feedback to previous steps and associated areas to improve calculations, as needed

In step 1, a scenario is identified as a well-defined sequence of features, events and processes that describes possible future conditions at the disposal site. An example of a scenario is the

release of radionuclides from a landfill via the vadose zone to the aquifer, where water is pumped from a well and ingested by an individual. Another scenario might be the inadvertent intrusion of a person digging for natural resources, which disrupts the repository and causes a direct release of radionuclides to the surface. The decision to evaluate or not evaluate various scenarios depends, in part, on relevant performance objectives set forth by regulatory requirements. In addition, scenarios should be chosen that represent features, events, and processes that are relevant to the specific site being evaluated. More information regarding features, events, and processes that are modeled in this study is provided in Section 4.1.

Step 2 develops the models that are necessary to simulate the chosen scenarios in the performance assessment. The models that are used vary in complexity, and a hierarchy of models can exist. An overarching conceptual model of each scenario is developed to guide the development of more detailed mechanistic models of individual features, events, and processes that comprise the scenario. These detailed models are then integrated into a total-system model of the entire scenario. The integration of the more detailed models may include the models themselves or a simplified abstraction of the model results. An example of this model development is provided in Sections 4.2 and 4.3.

After the models are developed, values must be assigned to the parameters required by the model (step 3). If the parameter is well characterized, a single deterministic value may be assigned. However, uncertainty and/or variability in the parameter may require the use of distributions (e.g., log-normal, uniform, etc.) to define the values. Experimental data, literature sources, and professional judgment are often used to determine these distributions. The development of uncertainty distributions for parameters used in this study are described in Section 4.3.

In step 4, calculations are performed using the integrated total-system model. Because stochastic parameters are used, a Monte Carlo approach is taken to create an ensemble of simulations that use different combinations of the input parameters. For each run (realization), a value for each input parameter is sampled from the uncertainty distribution, and the simulation is performed. The results of each realization are equally probable, and the collection of simulation results yields an uncertainty distribution that can be compared to performance objectives to assess the risk of exceeding those performance objectives or metrics. Sensitivity analyses can also be performed to determine which parameters the performance metrics are most sensitive to.

The last step (step 5) is to document the findings, typically as cumulative distribution functions that present the probability (or risk) of exceeding a performance objective. These findings may be used to evaluate alternative designs, where performance objectives, cost, and schedule comprise some of the criteria in choosing the most suitable cover for a site.

Figure 1. Integration between performance-assessment task and other primary tasks in the long-term capping strategy.

Finally, within this long-term capping strategy, an integrated effort must occur among several major components to accomplish a performance assessment (see Figure 1). The performance assessment relies on information from the Environmental Setting Task (e.g., climate change, vegetation change, etc.) and Engineering Design Task (e.g., material properties, configuration, etc.). In return, results from the performance assessment will identify parameters that are most important to long-term performance. More data can then be obtained on these parameters to reduce uncertainty. In addition, the parameters that are most important to performance can be used by the Long-Term Monitoring Task to assess methods to monitor these parameters important to long-term performance. Therefore, a performance assessment can be an iterative process, where each iteration builds upon previous information to continually improve the confidence in the calculations.

3. Description of Monticello Mill Tailings Repository Site

To illustrate the application of the performance-assessment method for long-term covers, an example is provided using the uranium mill tailings repository at the Monticello Mill Tailings Site in Monticello, Utah. A brief overview of the site is provided in this section, along with the performance objectives for this site. The performance-assessment method for this site is then detailed in Section 4.

3.1 Background

The Monticello Mill Tailings Site is located in southeastern Utah, south of the town of Monticello (see Figure 2). The present climate at Monticello is “sub-humid,” with an average annual precipitation of ~38 cm (15 inches) and an average annual temperature of 7.8 °C (46 °F).

In 1941, the Monticello mill was constructed and used to process nearly a billion kilograms of ore. By 1960, when operations were terminated, approximately 2 million cubic meters of low-level radioactive uranium mill tailings had been left behind from the operations. These mill tailings are sand-like material that remains after uranium has been extracted from the ore, and the tailings contain radioactive materials that can produce radon gas and gamma radiation.

Figure 2. Map of the Monticello Mill Tailings site and vicinity.

To contain the mill tailings, DOE began construction of a repository south of the original mill site in 1995, and in 1996 the construction of a composite double-liner system at the base of the repository was completed (see Figure 3). Trucks were used to transport the tailings from the mill site to the repository beginning in 1997, and placement of the tailings was completed in 1999. Construction of the cover began during the placement of the tailings, and, although the majority of the cover is complete, re-vegetation of the entire cover is being finalized. The cover was designed to mitigate the release of radon gas to the surface and to minimize water infiltration to the mill tailings per 40 CFR Part 264.301 (RCRA Subtitle ‘C’ design per EPA, 1991). It consists of a thick topsoil layer with vegetation that can store precipitation and allow evaporation and transpiration via the vegetation. This top layer overlies a coarse sand layer that acts as a capillary barrier and is intended to drain any infiltrating water laterally above a high-density polyethylene geomembrane. Beneath the geomembrane is a compacted clay layer that serves as

a barrier to radon gas transport and water infiltration. The clay layer rests directly on top of the mill tailings. At the base of the repository beneath the mill tailings is a double composite-liner system composed of sand, two geomembrane liners, two geosynthetic clay-liners, and a transmissive leachate collection system. The entire repository is surrounded by Quaternary deposits consisting of sandy loam, clay, and pediment gravels.

Figure 3. Aerial view of the double composite-liner system at the base of the repository.

Beneath the repository, two groundwater-bearing units (aquifers) exist. The upper unit is called the alluvial aquifer, which is a perched aquifer located as close as several meters below the bottom of the repository. This alluvial aquifer discharges to Montezuma Creek in several areas east of the millsite, and it had been contaminated by mill tailings prior to construction of the repository. The contaminants of concern include uranium, as well as its radioactive decay products (thorium-230, radium-226, radon-222), and heavy metals such as vanadium, lead-210, and arsenic. The lower regional aquifer beneath the alluvial aquifer is called the Burro Canyon aquifer and has not been contaminated. Between the alluvial aquifer and the Burro Canyon aquifer are unsaturated layers of shale and sandstone. The water from the upper alluvial aquifer is used for irrigation purposes, but all drinking-water wells are located in the lower Burro Canyon aquifer. An illustration of the repository site and the geologic formations beneath it are shown in Figure 4.

Figure 4. Illustration of the landfill cover and geology.

3.2 *Regulatory Requirements and Performance Metrics*

Waste-disposal sites are designed to be protective of human health and the environment. The phrase “protective of human health and the environment” expresses a clear intent, but the phrase does not have a universally accepted meaning. For example, should protective measures be designed to be effective for a few generations (~ 100 years) or so long as the waste could present a hazard? For illustrative purposes, this section identifies the quantitative performance objectives set by regulations applicable to the landfill being built as part of the closure of the Monticello Mill Tailing Site. Insight for this regulatory analysis was provided by DOE (1995) and MACTEC (2000).

Long-lived contaminants will remain at many of the DOE closure sites, including the Monticello landfill. To address the long-term management of these closure sites, the DOE has created a “stewardship” program, which is discussed after the identification of the quantitative performance objectives.

3.2.1 *Regulatory History*

Congress found that active and inactive uranium- and thorium-mill operations might pose a potential and significant health hazard to the public, and in 1978 Congress passed the Uranium Mill Tailings Radiation Control Act (UMTRCA) to assess and remediate hazards at 24 privately owned mill sites. Title I of UMTRCA authorizes the DOE to clean up these 24 sites to meet 40 CFR 192 standards set by the U.S. Environmental Protection Agency (EPA), with the concurrence of the U.S. Nuclear Regulatory Commission.

UMTRCA did not address the Monticello Mill Tailings Site because the site is not privately owned; the DOE owns the site. In 1980 the DOE accepted the Monticello Mill Tailings Site under DOE’s Surplus Facilities Management Program. In 1988, the DOE, EPA, and the State of

Utah entered into a Federal Facilities Agreement. EPA included the site on the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) National Priorities List (NPL) in 1989. Studies undertaken in 1989 identified on-site and off-site contamination of groundwater and stream sediments. Contaminates of concern include arsenic, chromium, lead, molybdenum, selenium, and vanadium, and the radioactive materials included radium-226, radon, and uranium.

Three operable units were defined. Operable Unit 1 addresses the mill tailings and other contaminated materials at the old millsite. Operable Unit 2 addresses remediation of other, peripheral properties that were contaminated by radioactive materials from the millsite. Operable Unit 3 addresses contaminated groundwater and surface water down gradient of the millsite.

3.2.2 Records of Decision

Remedial actions were selected through two Records of Decisions (RODs). To address threats to human health from Operable Units 1 and 2, the first ROD was issued in 1990. (EPA/ROD/R08-90/034). The second ROD was issued in 1998 and addressed threats posed by Operable Unit 3.

The first ROD requires consolidation of contaminated materials from the millsite and the peripheral properties in a new repository that is being built ~2 km south of the old millsite. The ROD requires:

- Removal of tailings, ore, and process-related material from their Millsite location
- De-watering contaminated materials to bring moisture content to 0.26 or less
- Placement of the contaminated materials in a landfill that is being constructed ~2 km south of the millsite
- Design of the landfill to meet requirements of the UMTRCA and 40 CFR 192 technical standards. To meet these requirements, the landfill will be:
 - Capped to protect the groundwater, to isolate the waste from the environment, and to control the escape of radon gas
 - Constructed with features to control and treat surface-water runoff
 - Revegetated
- Long-term surveillance and environmental monitoring will be implemented to ensure the effectiveness of the remedial action and compliance with groundwater and surface-water standards
- Approximately two million cubic meters of contaminated materials will be consolidated in the ~32 square kilometer (80 acre) landfill

In addition, there are numerous federal regulations, state regulations, and guidance documents that can be applied to the design of the landfill that receives the mill tailings and associated wastes. The next section discusses the identification of those regulations.

3.2.3 Identification of Landfill-Design Regulations

As required by CERCLA, the protection levels achieved by the landfill system must be at least equal to those specified by *applicable or relevant and appropriate requirements* (ARARs). The primary ARARs for the new landfill are:

- (A) EPA's 40 CFR 192, "Health and Environmental Protection Standards for Uranium and Thorium Mill Tailings;" these are the Federal regulations implementing UMTRCA
- (B) EPA's 40 CFR 141 and 40 CFR 143, "Safe Drinking Water Act National Primary and Secondary Drinking Water Standards"
- (C) "Administrative Rules for Ground Water Quality Protection" (UAC R317-6), the State regulations implementing parts of the Utah Water Quality Act (Title 19, Chapter 5, Utah Code Annotated)
- (D) "Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities" (R315-8, Utah Administrative Code), the State regulations implementing parts of the Utah Solid and Hazardous Waste Act (Title 19, Chapter 6, Part 1, Utah Code Annotated)
- (E) DOE Order 435.1, Radioactive Waste Management

Each of these primary ARARs is discussed below.

(A) Landfill Requirements from the EPA's 40 CFR 192

The EPA's 40 CFR 192 sets two specific standards for radon releases from landfills containing mill tailings. It states that the control of residual radioactive materials and their listed constituents shall be designed to:

- (1) Be effective for up to one thousand years, to the extent reasonably achievable, and, in any case, for at least 200 years
- (2) Provide reasonable assurance that releases of radon-222 from residual radioactive material to the atmosphere will not:
 - (i) Exceed an average release rate of 20 picocuries per square meter per second
 - (ii) Increase the annual average concentration of radon-222 in air at or above any location outside the disposal site by more than one-half picocurie per liter (40 CFR 192.02)

40 CFR 192.02 also sets groundwater protection standards for uranium mill tailings that are similar to RCRA regulations concerning hazardous waste. The mill tailings standards include Maximum Contaminant Levels (MCLs) for a number of contaminants, including arsenic, lead, radium, uranium, and gross alpha-particle activity (excluding radon and uranium). Under 40 CFR 192, the point of compliance (POC) for groundwater protection is the intersection of a vertical plane with the uppermost aquifer underlying the site, located at the hydraulically downgradient limit of the disposal area plus the area taken up by any liner, dike, or other barrier designed to contain the residual radioactive material (40 CFR 192.02(c)(4)).

(B) Federal Safe Drinking Water Act

The EPA's 40 CFR 141 and 40 CFR 143 set health-based standards (maximum contaminant levels or MCLs) for community water-supply systems. For contaminants present at the Mill Tailings Site, the Safe Drinking Water Act MCLs are all equal to, or higher than, the groundwater protection standards set in 40 CFR 192.

For example, the Safe Drinking Water Act (SDWA) MCL for selenium is 0.05 milligrams per liter (mg/L), and the groundwater protection standard set in 40 CFR 192 is 0.01 mg/L; therefore, use of the 40 CFR 192 standards provides equal or greater protection than that provided by the SDWA. The only exception is that the SDWA sets an MCL of 4 millirem per year (mrem/yr) for beta particles and photon radiation from man-made radionuclides, and 40 CFR 192 has no standard for beta particles.

(C) Landfill Requirements from the Utah Water Quality Act

The administrative Rules for Ground Water Quality Protection (UAC R317-6) implement a State environmental law that has no Federal counterpart. Because many of its provisions are more stringent than those in other ARARs, UAC R317-6 governs most aspects of groundwater protection. UAC R317-6 applies to all groundwater in the State and defines groundwater as "subsurface water in the zone of saturation including perched groundwater."

This extends the protectiveness of the rule beyond that of the RCRA and UMTRCA regulations, which apply only to aquifers that can yield significant quantities of water to wells or springs. The Utah definition of contaminant is not restricted to hazardous substances. Instead, a contaminant is "any physical, chemical, biological, or radiological substance or matter in water" (UAC R317-6-1.11). This definition encompasses virtually anything that could be discharged from the landfill.

Protection levels for these contaminants must be met at a compliance monitoring point. Point of discharge "means the area within outermost location at which effluent or leachate has been stored, applied, disposed of, or discharged; for diked facilities, the outermost edge of the dikes" (UAC R317-6-1.28). The point of discharge, therefore, is similar in concept to the point of compliance defined in 40 CFR 192.

UAC 317-6 protection levels vary with the classification of the groundwater, which varies according to water quality and potential use. At the Monticello landfill site, the shallow groundwater contains Class II groundwater. *Such groundwater could be used for drinking or similar uses after conventional water treatment.*

(D) Landfill Requirements from the Utah Solid and Hazardous Waste Act

UAC R315-8 implements a Utah law that applies the provisions of RCRA at the State level. Because UAC R315-8 is at least equal to, and potentially more stringent than, the comparable RCRA regulations in 40 CFR 264, the Utah rule is considered the governing standard.

UAC R315-8 is most important as the source of design requirements for the landfill liner and cover. UAC R315-8-14.2 requires that the entire landfill cell must have a liner system, that the system must include two liners with a leachate collection and removal system above each liner, and that the lower liner must be a composite of a geomembrane and a clay layer. It also requires that the permeability of the clay layer be less than or equal to 1×10^{-7} cm/s (same value specified in RCRA regulations 40 CFR 264.301), which will be used in this study as a performance metric. The rule also provides for alternate design or operating practices if the owner or operator demonstrates functional equivalency (UAC R315-8-14.2(d)). UAC R315-8-14.3 sets requirements for monitoring and inspection of liner systems, both during and after construction.

(E) DOE Orders

Although not listed as an ARAR, the DOE, through a DOE “Order,” sets standards for maximum doses to a member of the public from all routine DOE operations, including remedial actions.

3.2.4 Summary of Performance Metrics for the Monticello Repository

Each of the regulations discussed above was reviewed for quantitative performance objectives that govern the long-term performance of the mill tailings landfill/repository at Monticello. Table 1 summarizes these metrics. When two or more regulations set the same standard, only the standard set by 40 CFR 192 is presented in Table 1.

Of the metrics summarized in Table 1, only a few are used in this study as performance objectives for the selected scenarios (Section 4.1). In addition, the amount of percolation reaching the mill tailings is used as a performance objective based on the requirements in RCRA 40 CFR 264.301 and UAC R315-8-14.2. The performance objectives used in this study are summarized as follows:

- (1) Percolation of water reaching mill tailings shall be less than 1×10^{-7} cm/s. This is based on the prescribed maximum conductivity of the clay liner in 40 CFR 264.301 and UAC R315-8-14.2, where a unit-gradient flow is assumed to equate percolation to conductivity.
- (2) Average flux of radon-222 gas shall be less than 20 pCi/m²/s at the surface of the repository cover (40 CFR 192.02(a) and 40 CFR 192(b)(1)).
- (3) Combined radium-226 and radium-228 concentrations in groundwater shall be less than 5 pCi/L (only radium-226 is evaluated in this study) (40 CFR 192.02(a) and 40 CFR 192.02(c)(4) and Table 1 to Subpart A of 40 CFR 192).
- (4) The effective dose to a member of the public from all pathways shall be less than 100 mrem/year (only radium-226 is evaluated in this study) (DOE Order 5400.5 II 1. a).

Table 1. Summary of performance objectives applicable to the Monticello Mill Tailings Repository.

Media	Standard	Point of Compliance	Period of Compliance	Regulation
All Pathways	< 100 mrem/year Effective Dose Equivalent from all routine DOE activities	to a member of the public	not defined	DOE Order 5400.5 II 1. a.
Atmosphere	< 10 mrem/year Effective Dose Equivalent, excluding Rn	to a member of the public	not defined	40 CFR 61.92
Atmosphere	Average flux of Rn-222 < 20 pCi/m ² /s or (see next row)	In air above landfill, averaged over entire landfill	1,000 years if reasonably achievable, and, in any case, for at least 200 years	40 CFR 192.02(a) and 40 CFR 192(b)(1)
Atmosphere	annual average concentration of Rn-222 in air < 0.5 pCi/L	At or above any location outside the landfill	1,000 years if reasonably achievable, and, in any case, for at least 200 years	40 CFR 192.02(a) and 40 CFR 192(b)(2)
Groundwater	Arsenic < 0.05 mg/L ^{1, 2}	Intersection of vertical plane with uppermost aquifer at downgradient limit of disposal area plus area taken by dike or other waste barrier	1,000 years if reasonably achievable, and, in any case, for at least 200 years	40 CFR 192.02(a) and 40 CFR 192.02(c)(4) and Table 1 to Subpart A of 40 CFR 192
	Chromium < 0.05 mg/L ^{1, 2}			
	Lead < 0.05 mg/L ^{1, 2}			
	Molybdenum < 0.1 mg/L ^{1, 2}			
	Selenium < 0.01 mg/L ^{1, 2}			
	Combined Ra-226 & Ra-228 < 5 pCi/L ^{1, 2}			
	Combined U-234 & U-238 < 30 pCi/L ^{1, 2, 3}			
	Gross alpha-particle activity, excluding Rn and U < 15 pCi/L ^{1, 2}			
Groundwater	Beta particles, and photons from man-made radionuclides < 4 mrem/yr	In community water supply systems	not defined	40 CFR 141.16
Compacted soil layer in cover	Water percolation ⁴ < 1x10 ⁻⁷ cm/s	Hydraulic conductivity of compacted soil layer in cover	not defined	40 CFR 264.301

¹ If background is below this level; ² An alternative concentration limit may be established under 40 CFR 192.02 (c)(ii)(A); ³ Where secular equilibrium obtains, this criterion will be satisfied by a concentration of 0.044 milligrams per liter (0.044 mg/l). For conditions of other than secular equilibrium, a corresponding value may be derived and applied, based on the measured site-specific ratio of the two isotopes of uranium. ⁴ A unit-gradient flow is assumed to equate percolation to hydraulic conductivity

4. Performance Assessment of the Monticello Mill Tailings Repository

This section presents an illustration of the risk-based performance-assessment method (as defined in Section 2) for the Monticello Mill Tailings Repository Site. Scenarios are first developed based on relevant performance objectives (Section 3.2.4) and applicable features, events, and processes at the site. A total-system framework is then developed to integrate the more detailed “process models” in each scenario. Descriptions of each process model are provided along with the parameter distributions, and a discussion of the results of the simulated performance metrics is presented.

4.1 Scenario Development and Screening of FEPs

The first step in the performance assessment is to develop relevant scenarios based on performance objectives and applicable features, events, and processes at the site. The performance objectives have been summarized in Section 3.2.4, and a list of relevant features, events, and processes at the Monticello site are listed in Table 2 along with their treatment in this study. Rigorous methods have been developed by Cranwell et al. (1982) to identify and screen FEPs. However, the scoping nature of this assessment did not allow for a full implementation of the FEPs process. Therefore, only a subset of all possible FEPs were identified in Table 2 based on best professional judgment. In addition, only radium-226 (and its daughter products) was chosen as the aqueous contaminant of interest for transport via the groundwater, and radon-222 was chosen as the gas-phase contaminant of interest for gas transport to the surface of the cover. The inclusion of additional radionuclides may increase the peak concentrations and doses simulated in this assessment. A total of eight scenarios were chosen based on the relevant FEPs and performance objectives. Table 3 provides a summary and explanation of these scenarios.

Table 2. List of features, events, and processes relevant to the Monticello Mill Tailings Repository.

Title	Description	Treatment
Environmental Conditions		
Future climates	Future climates may yield different temperatures and precipitation rates than present conditions.	Included in HELP (Hydrologic Evaluation of Landfill Performance) model. ¹
Future vegetation	Vegetation on covers may change with future climates.	Included in HELP model. ¹
Erosion	Wind and flooding can cause erosion of soils, which may impact infiltration.	Not included. Uncertain impact.
Percolation to Waste		
Run-on/Run-off	Precipitation can run-on and run-off surfaces above the repository.	Included in HELP model. ¹
Evapo-transpiration	Precipitation can be evaporated and transpired by plants.	Included in HELP model. ¹
Storage	Infiltration can be stored in soils.	Included in HELP model. ¹
Capillary barriers/lateral diversion	Percolation can be diverted by capillary barriers.	Included in HELP model. ¹
Membrane leakage	Membranes and liners can leak if defects are present.	Included in HELP model. ¹
Membrane deterioration	Membranes and liners can deteriorate over	Included in HELP model using increased

Title	Description	Treatment
	time.	defects for future conditions. ¹
Fast flow paths (e.g., root holes)	Heterogeneities in the cover may cause fast flow paths.	Not included. May have large impact.
Spatial and temporal variability in infiltration	Episodic infiltration and spatial variability may increase the infiltration in locations	Not included. May have large impact.
Source-Term Release and Transport through Cover		
Leaching	Radionuclides can leach into percolating pore water	Included in MEPAS source-term model. ³
Radon gas flux	Radon gas can transport through the cover to the surface	Included in RAECOM model. ²
Barometric pumping	Barometric pressure variations may cause advection of radon gas to the surface	Not included. May have large impact.
Subsidence of waste	Waste could subside and change shape of repository	Not included. Not expected to have a large impact.
Vadose-Zone Transport		
Advection	Radionuclides can transport in percolating pore water.	Included in MEPAS vadose-zone model. ⁴
Diffusion/Dispersion	Radionuclides can transport by molecular and mechanical diffusion/dispersion.	Included in MEPAS vadose-zone model. ⁴
Sorption	Radionuclides can adsorb onto solid surfaces.	Included in MEPAS vadose-zone model. ⁴
Fast transport paths	Heterogeneities and colloids may facilitate faster transport	Not included. May have a large impact.
Water-table rise	Future wetter climates may cause the water table to rise, decreasing the vadose-zone transport distance	Not included. May have a large impact.
Saturated-Zone Transport		
Advection	Radionuclides can transport in groundwater.	Included in MEPAS saturated-zone model. ⁴
Diffusion/Dispersion	Radionuclides can transport by molecular and mechanical diffusion/dispersion in groundwater.	Included in MEPAS saturated-zone model. ⁴
Sorption	Radionuclides can adsorb onto solid surfaces.	Included in MEPAS saturated-zone model. ⁴
Fast transport paths	Heterogeneities and colloids may facilitate faster transport	Not included. May have a large impact.
Human Exposure		
Shallow alluvial aquifer	Humans can use water from the shallow alluvial aquifer for agriculture	Included in MEPAS exposure, intake, and health-impact models. ⁵
Deep Burro Canyon aquifer	Humans can use water from the deep aquifer for agriculture and consumption.	Included in MEPAS exposure, intake, and health-impact models. ⁵
Inhalation	Humans can inhale radon gas and contaminated particulates.	Not included. Not expected to have a large impact.
Direct contact	Humans can experience dermal contact through bathing, swimming, etc.	Not included. Not expected to have a large impact.
Disruptive Events		
Earthquakes, tornadoes, human intrusion, bio-intrusion	These events could disrupt the repository site and cause changes to transport processes and pathways	Not included. May have a large impact.

¹Schroeder et al. (1994a,b); ²Rogers et al. (1984); ³Streile et al. (1996); ⁴Whelan et al. (1996); ⁵Strenge and Chamberlain (1995)

Table 3. Summary of scenarios and performance objectives evaluated in this study.

Scenario	Description	Climate	Performance Objective Addressed
1	Infiltration percolates through the cover and reaches the mill tailings.	Present	<ul style="list-style-type: none"> Percolation of water reaching mill tailings shall be less than 1×10^{-7} cm/s.
2	Infiltration percolates through the cover and reaches the mill tailings.	Future	<ul style="list-style-type: none"> Percolation of water reaching mill tailings shall be less than 1×10^{-7} cm/s.
3	Radon-222 gas diffuses from the mill tailings to the surface.	Present	<ul style="list-style-type: none"> Average flux of radon-222 gas shall be less than 20 pCi/m²/s at the surface of the repository cover.
4	Radon-222 gas diffuses from the mill tailings to the surface.	Future	<ul style="list-style-type: none"> Average flux of radon-222 gas shall be less than 20 pCi/m²/s at the surface of the repository cover.
5	Radium-226 leaches from the mill tailings and transports through the composite liner, the vadose zone, and into the shallow alluvial aquifer where water is used for agricultural purposes.	Present	<ul style="list-style-type: none"> Radium-226 concentration in groundwater shall be less than 5 pCi/L. The effective dose to a member of the public from all pathways shall be less than 100 mrem/year.
6	Radium-226 leaches from the mill tailings and transports through the composite liner, the vadose zone, and into the shallow alluvial aquifer where water is used for agricultural purposes.	Future	<ul style="list-style-type: none"> Radium-226 concentration in groundwater shall be less than 5 pCi/L. The effective dose to a member of the public from all pathways shall be less than 100 mrem/year.
7	Radium-226 leaches from the mill tailings and transports through the composite liner, the vadose zone, and into the deep Burro Canyon aquifer where water is used for agricultural purposes and drinking.	Present	<ul style="list-style-type: none"> Radium-226 concentration in groundwater shall be less than 5 pCi/L. The effective dose to a member of the public from all pathways shall be less than 100 mrem/year.
8	Radium-226 leaches from the mill tailings and transports through the composite liner, the vadose zone, and into the deep Burro Canyon aquifer where water is used for agricultural purposes and drinking.	Future	<ul style="list-style-type: none"> Radium-226 concentration in groundwater shall be less than 5 pCi/L. The effective dose to a member of the public from all pathways shall be less than 100 mrem/year.

Once the scenarios were developed, conceptual models of the features, events, and processes for each scenario could be formulated. The conceptualizations involve simplifications of the complex nature of the site, but they capture the salient features to be modeled. The conceptual models include contaminant source and release information (as applicable), a description of transport mechanisms and pathways, and a definition of modeling endpoints. Figure 5, Figure 6, and Figure 7 illustrate the conceptual models of the various scenarios (see Table 3). From a computational standpoint, each scenario is simulated stochastically and independently to yield distributions of the corresponding performance metrics in Table 3. Fault trees or other analysis

methods could be used to assign probabilities to each scenario and combine these distributions, but for this example, each scenario is treated independently.

Figure 5 illustrates the conceptualization for scenarios 1-4 for water and gas transport through the landfill cover for both present and future conditions. Under future conditions, additional uncertainty is added to parameters such as precipitation and liner quality to reflect potentially wetter conditions and deteriorated materials. Figure 6 illustrates scenarios 5 and 6, where radium-226 (and its daughter products Rn-222, Pb-210, Bi-210, and Po-210) leach from the mill tailings and transport to the shallow alluvial aquifer under present and future conditions. Figure 7 illustrates scenarios 7 and 8, which are similar to scenarios 5 and 6 except the aquifer is thicker and located more deeply in the Burro Canyon. In addition, the water from the Burro Canyon aquifer is used for both drinking and agriculture, whereas the water from the shallow alluvial aquifer is used only for agriculture. Transport to both the shallow alluvial aquifer and the Burro Canyon aquifer could not be simulated simultaneously because of limitations in the FRAMES model, but because the transport the Burro Canyon aquifer is much longer, the combined peak concentration and dose are not expected to be significantly different than the results from the shallow alluvial aquifer. More details regarding the various conceptual and process models used in the simulations are provided in Section 4.3.

Figure 5. Conceptual model for water percolation (scenarios 1 and 2) and gas transport (scenarios 3 and 4) through a composite (base-case) cover design for present and future conditions. A 3% slope is assumed for the drainage layer. An alternative evapotranspiration (ET) cover design that only consists of Layer 1 is also considered in Section 4.5.

Figure 6. Conceptual model for radionuclide transport from the mill tailings to the shallow alluvial aquifer and location of receptor well for present (scenario 5) and future (scenario 6) conditions.

Figure 7. Conceptual model for radionuclide transport from the mill tailings to the deep Burro Canyon aquifer and location of receptor well for present (scenario 7) and future (scenario 8) conditions.

4.2 Total-System Framework Model

Each scenario contains a combination of models that represent processes in different media (e.g., transport in the vadose zone, saturated zone, air, etc.). Often, these models do not originate from the same numerical code, and a framework is required to seamlessly integrate individual codes into a multimedia assessment. The system used for this study was the Framework for Risk Analysis in Multimedia Environmental Systems (FRAMES). FRAMES was developed by Pacific Northwest National Laboratory (PNNL) with funding from DOE and EPA. The FRAMES system allows for a holistic approach to modeling in which models of different type (i.e., source, fate and transport, exposure, health impact), resolution (i.e., analytical, semi-analytical, and numerical), and operating platforms can be combined as part of the overall assessment of contaminant fate and transport in the environment. The FRAMES system provides a user-friendly platform for integrating medium specific computer models, an extensive and editable contaminant database, a powerful and flexible sensitivity/uncertainty module, and textual and graphical viewers for presenting modeling outputs. The FRAMES system employs a graphical user interface (GUI) that aids a user in setting up and simulating each conceptual site model. Screen captures from the GUI can also be very helpful as a tool to communicate the assessment approach to others. Figure 8 presents a screen capture of the FRAMES GUI depicting scenario 5 in this study. Similar cases were set up in FRAMES for the other scenarios in this study; however, scenarios 1 and 2 were simulated separately using HELP v. 3.07 as a stand-alone code (Schroeder et al., 1994a,b). As part of this project, HELP was integrated into FRAMES so that stochastic HELP simulations could be performed from within the FRAMES architecture.

The module icons displayed in Figure 8 represent detailed process models that can be accessed by clicking on the icon. Existing models in FRAMES include those derived from the Multimedia Environmental Pollutant Assessment System (MEPAS) (Whelan et al., 1992). MEPAS is a physics-based environmental analysis code that integrates source-term, transport, and exposure models for endpoints such as concentration, dose, or risk. As its name suggests, MEPAS is capable of computing contaminant fluxes for multiple routes, which include leaching to groundwater, overland runoff, volatilization, suspension, radioactive decay, constituent degradation, and source/sink terms. The radioactive-decay loss route is always utilized for radionuclides; it cannot be turned off. The model also requires the user to select from three different source medias: surface soil, surface water/pond, and contaminated aquifer. Another module was created in FRAMES to integrate the radon-gas-transport code RAECOM (Rogers et al., 1984) so that stochastic simulations of radon-gas transport from the waste to the surface could be simulated from within FRAMES (see Appendix A). Section 4.3 provides more detailed discussion of each process model used in the scenarios.

In Figure 8, the arrows on the screen linking the icons from the Monticello Landfill icon to the Health Impacts icon indicate the direction of data flow through the system. Additional arrows originating from the FRAMES contaminant database (con1) indicate that all modules are receiving contaminant data. Finally, arrows linking module icons to the Sensitivity Model icon indicate those modules that contain stochastic parameters.

Figure 8. Screen capture of FRAMES graphical user interface for scenario 5.

In most modeling exercises there are uncertainties associated with each input parameter. Uncertainty analyses are performed in an effort to try to capture the effect of parameter uncertainty and variability on the simulated results. Invariably, certain parameters impact modeling results more than others when their values are changed. However, in most cases, this type of behavior is difficult to predict when a modeling scenario includes multiple models and multiple uncertain input parameters. For this reason, FRAMES allows parameters to be varied stochastically, and it records the sampled parameter values for each realization so that they can be used in subsequent sensitivity analyses. The sensitivity/uncertainty module in FRAMES is called the Sensitivity Uncertainty in Multimedia Modeling Module (SUMMM). The SUMMM module can be attached to any model that has been integrated into FRAMES and allows the user to stochastically vary any input parameter that is identified in the process models. Input parameters can be stochastically varied by a distribution, correlation coefficient, an equation, or any combination of these three options. Four distributions are currently available: (1) uniform, (2) log uniform, (3) normal, and (4) log normal. SUMMM utilizes the Latin Hypercube Sampling (Wyss and Jorgensen, 1998) technique to minimize the number of modeling runs that must be performed to accurately represent distributions selected by the user.

The stochastic parameters that were varied in each scenario are detailed in Section 4.3. One hundred realizations were simulated in each scenario (except for scenarios 1 and 2) using FRAMES with the SUMMM module. In scenarios 1 and 2, only 50 realizations were simulated because the HELP code was not integrated with FRAMES and had to be run manually for each realization (see Appendix A for a description of a newly integrated version of FRAMES and HELP). The results of each simulation that were recorded correspond to the performance metrics listed in Table 1.

4.3 Process-Model Development and Parameter Distributions

This section presents the detailed process models that were integrated in the total-system model FRAMES. An overview of the model is provided along with the necessary input parameter distributions for the following process models: (1) water percolation through the cover; (2) radon gas transport through the cover; (3) source-term release; (4) vadose-zone transport; (5) saturated-zone transport; and (6) human exposure.

4.3.1 Water Percolation through the Cover

Water percolation through the cover to the waste is affected by numerous factors including the weather, plant behavior, and the properties of the cover systems and their variability. The HELP v. 3.07 code (Schroeder et al., 1994a,b) considers the above variables for landfill cover systems. The processes modeled in HELP include weather, snowmelt, runoff, infiltration, evapotranspiration, vegetative growth, soil moisture storage, lateral subsurface drainage, leachate recirculation, unsaturated vertical drainage, and leakage through soil, geomembrane or composite liners. HELP is widely used due to its ease of use compared to other numerical codes and its acceptance within the regulatory community. Convenient default parameters are included for soils, geosynthetic materials, evapotranspiration processes, and weather parameters. Thus, the user-input parameters can be minimal. However, it uses a simplified water routing technique to evaluate the distribution of water in the landfill covers, and flow due to capillary pressure gradients, which may be important in semi-arid and arid environments, is neglected. As a result, the HELP model of flow through the cover does not account for capillary barriers (i.e., between layers 1 and 2 in Figure 5), but it does allow for lateral drainage in layer 2, which is assumed to have a 3% slope. This simplification can lead to overprediction of percolation/leakage in semi-arid and arid conditions (Fleenor and King, 1995; Webb et al., 1997).

A number of other codes include more mechanistic models for unsaturated flow; however, other features important to landfill covers are not included. For example, TOUGH2 (Pruess et al., 1991) has a much more comprehensive model for unsaturated flow including local heterogeneity as demonstrated by Ho and Webb (1998) for capillary barriers, but the effect of weather and plants is not included. UNSAT-H (Fayer, 2000) is another candidate code. While it does include some weather and plant features, it is restricted to one-dimensional geometry. In the interest of trying to include the relevant features, events and processes, the HELP code was chosen for the present scenario analysis. However, future model development in this area might be needed in order to adequately capture all the necessary physics.

Parameter values for the HELP model of percolation through the landfill cover at the Monticello site were assigned based on site-specific data, where available, and on general information about soil characteristics in other cases. Sensitivity analyses were conducted with the HELP model to provide information on parameter sensitivity and to determine which parameters should be included as stochastic parameters in the performance-assessment analyses. Uncertainties in key parameters and correlations were quantitatively evaluated and uncertainty distributions were assigned.

Sensitivity analyses with the HELP model of the landfill cover were conducted using the expected values of model parameters (Abraham and Waugh, 1995) and varying individual parameters within reasonable ranges for present conditions (see Appendix B for details). Average monthly precipitation and temperature data for Monticello, Utah, were used in the model (Owenby and Ezell, 1992). The dependent variable in sensitivity analyses was the average annual percolation through the landfill cover. Analysis of environmental factors indicated moderate sensitivity to total precipitation, evaporative zone depth, and maximum leaf-area index. Results also indicated moderate to high sensitivity to the saturated hydraulic conductivity, wilting point, and field capacity in layer 1 and moderate sensitivity to the saturated hydraulic conductivity, wilting point, and field capacity in layer 2 (see Figure 5 for layer configuration). Results for the geomembrane (layer 3) indicated moderate sensitivity to defect density and placement quality. Moderate sensitivity to saturated hydraulic conductivity was observed for layer 4. Note that the definitions for these parameters can be found in Schroeder et al. (1994a,b). The results of the sensitivity analyses were used as a semi-quantitative basis for choosing the parameters to be treated stochastically in the analyses of percolation with the HELP model. Distributions for uncertain parameters are summarized in Table 4 for present (scenario 1) and future (scenario 2) climatic conditions, and brief descriptions of the distributions are provided below.

The upper bound of the evaporative-zone-depth parameter for layer 1 is the total thickness of the layer and the lower bound is specified as 0.81 m (32 in) based on professional judgment. A uniform distribution is specified for the evaporative-zone-depth parameter, based on the lack of specific information on the relative probability of the value. The maximum leaf-area index is assigned a uniform uncertainty distribution with a lower bound of 0.0 (corresponding to no vegetation) and an upper bound of 1.6 for present climatic conditions and 2.0 for future climatic conditions (Waugh, personal communication, 2001).

Uncertainty in the hydraulic parameters for layer 1 in the landfill cover was analyzed based on data from the site (Daniel B. Stephens and Associates, 1993). Soil drainage data were fit using the van Genuchten model for soil characteristics for eight samples. Results were converted to the field capacity and wilting point of the Brooks-Corey model for input to the HELP code. Statistical analysis indicated an approximate log-normal distribution of saturated hydraulic conductivity, when a single outlier in the data set was discarded. The distributions of field capacity and wilting point are approximately uniform and the lowest and highest observed values of these parameters were taken as bounds to uniform distributions. See Appendix B for more details.

Uncertainty in the hydraulic parameters for layers 2 and 4 was evaluated based on a compilation of data for sand and clay, respectively (Carsel and Parrish, 1988). This approach was taken

because site-specific data were not available for these materials. The uncertainty distributions given for saturated hydraulic conductivity and the van Genuchten soil characteristic parameters in Table 4 were back-transformed from the distributions provided in Carsel and Parrish (1988). The van Genuchten parameters were converted to the Brooks-Corey parameters of field capacity and wilting point for use in the HELP model. See Appendix B for more details.

Stochastic parameters related to the geomembrane (layer 3) are the defect density and the placement quality. For present conditions, the uncertainty distribution for the defect density was designated as a normal distribution with a mean of 0.0012 defects/m² (5 defects/acre) and the standard deviation was set at 3.7x10⁻⁴ defects/m² (1.5 defects/acre) to give an approximate variation from 0 to 0.0025 defects/m² (0 to 10 defects/acre), based on professional judgment. Degradation of the geomembrane was incorporated into the probabilistic analyses by varying the defect density for future conditions in a uniform distribution between 0 defects/m² (0 defects/acre) and 1.2 defects/m² (5000 defects/acre), corresponding to essentially complete degradation of the plastic geomembrane. A uniform distribution in the placement quality from 1 to 6 (perfect placement to worst-case placement) was assigned, given the lack of site-specific information on placement quality (see Shroeder et al., 1994a,b for details).

Uncertainty in precipitation and temperature for future climatic conditions was incorporated in the analyses by defining parameters for the precipitation multiplier and temperature adjustment relative to present conditions. The precipitation multiplier is the ratio of the average annual precipitation for future conditions to the present annual average. The precipitation multiplier was assigned a uniform distribution with 1.0, corresponding to present conditions, as a lower bound. The upper bound of 2.04 was specified to correspond to the ratio of estimated glacial climatic precipitation of 80 cm/year (Waugh and Petersen, 1994) to present average annual precipitation of 39.3 cm/year (Owenby and Ezell, 1992). The precipitation multiplier was applied to the individual monthly average precipitation values used in the HELP model for the simulations of future conditions. A uniform uncertainty distribution for the average temperature adjustment was specified with a lower bound of -6.0 °C and an upper bound of 0.0 °C. The lower bound corresponds to the estimated average annual temperature for cooler, glacial climatic conditions (Waugh and Petersen, 1994). The value of the temperature adjustment was added to the average monthly temperature values (present conditions) used in the HELP model for simulations of future conditions (Owenby and Ezell, 1992).

Table 4. Uncertainty distributions for stochastic parameters in the percolation model (see Figure 5 for layer names and descriptions).

Layer	Parameter	Uncertainty Distribution (Present Conditions)	Uncertainty Distribution (Future Conditions)
1	Evaporative Zone Depth (m)	Uniform Distribution Lower Bound: 0.81 Upper Bound: 1.8	Uniform Distribution Lower Bound: 0.81 Upper Bound: 1.8
1	Maximum Leaf Area Index	Uniform Distribution Lower Bound: 0.0 Upper Bound: 1.6	Uniform Distribution Lower Bound: 0.0 Upper Bound: 2.0
1	Effective Saturated Hydraulic Conductivity (cm/s)	Log Normal Distribution Geometric Mean: 3.0x10 ⁻⁴ Geometric S.D.: 8.9	Log Normal Distribution Geometric Mean: 3.0x10 ⁻⁴ Geometric S.D.: 8.9
1	Field Capacity	Uniform Distribution	Uniform Distribution

Layer	Parameter	Uncertainty Distribution (Present Conditions)	Uncertainty Distribution (Future Conditions)
		Lower Bound: 0.22 Upper Bound: 0.38	Lower Bound: 0.22 Upper Bound: 0.38
1	Wilting Point	Uniform Distribution Lower Bound: 0.08 Upper Bound: 0.21	Uniform Distribution Lower Bound: 0.08 Upper Bound: 0.21
2	Effective Saturated Hydraulic Conductivity (cm/s) ¹	Log Ratio Normal Distribution Mean: -0.394 S.D.: 1.15	Log Ratio Normal Distribution Mean: -0.394 S.D.: 1.15
2	Van Genuchten Alpha (1/cm) ¹	Log Ratio Normal Distribution Mean: 0.378 S.D.: 0.439	Log Ratio Normal Distribution Mean: 0.378 S.D.: 0.439
2	Van Genuchten N ¹	Log Normal Distribution Mean: 0.978 S.D.: 0.100	Log Normal Distribution Mean: 0.978 S.D.: 0.100
3	Defect Density (1/m ²)	Normal Distribution Mean: 0.0012 S.D.: 3.7x10 ⁻⁴	Uniform Distribution Lower Bound: 0 Upper Bound: 1.2
3	Placement Quality	Uniform Distribution Lower Bound: 1 Upper Bound: 6	Uniform Distribution Lower Bound: 1 Upper Bound: 6
4	Effective Saturated Hydraulic Conductivity (cm/s) ²	Log Ratio Normal Distribution Mean: -5.75 S.D.: 2.33	Log Ratio Normal Distribution Mean: -5.75 S.D.: 2.33
4	Van Genuchten Alpha (1/cm) ²	Log Ratio Normal Distribution Mean: -4.145 S.D.: 1.293 Lower Bound: -5.01 Upper Bound: 0.912	Log Ratio Normal Distribution Mean: -4.145 S.D.: 1.293 Lower Bound: -5.01 Upper Bound: 0.912
4	Van Genuchten N ²	Log Normal Distribution Mean: 0.0002 S.D.: 0.118 Lower Bound: 0.0 Upper Bound: 0.315	Log Normal Distribution Mean: 0.0002 S.D.: 0.118 Lower Bound: 0.0 Upper Bound: 0.315
N/A	Precipitation Multiplier	N/A	Uniform Distribution Lower Bound: 1 Upper Bound: 2.04
N/A	Average Temperature Adjustment (°C)	N/A	Uniform Distribution Lower Bound: -6.0 Upper Bound: 0.0

¹see Carsel and Parrish (1988) parameter distributions for sand.; ²see Carsel and Parrish (1988) parameter distributions for clay; N/A: Not Applicable; S.D.: Standard Deviation

Important correlations exist between several of the uncertain parameters in the HELP model for percolation at the Monticello site. The correlation coefficients (R-values) for these correlations are summarized in Table 5. The correlation between evaporative-zone depth and maximum leaf-area index was based on professional judgment that higher plant density would correspond to deeper rooting depth. The correlations between the hydraulic parameters in layer 1 were based on statistical analysis of site-specific data (Daniel B. Stephens and Associates, 1993). The values of the correlation coefficients for the hydraulic parameters in layers 2 and 4 were taken from Carsel and Parrish (1988). The moderate positive correlation between maximum leaf-area index and the precipitation multiplier for future conditions was based on professional judgment that wetter climatic conditions would generally correspond to higher plant density. The moderate negative correlation between the precipitation-multiplier parameter and the average temperature adjustment was based on professional judgment that wetter climatic conditions would generally correspond to lower average temperatures.

Table 5. Correlation coefficients between parameters in the percolation model.

Parameter 1	Parameter 2	Correlation Coefficient (Present Conditions)	Correlation Coefficient (Future Conditions)
Evaporative Zone Depth (inches)	Maximum Leaf-Area Index	0.60	0.60
Effective Saturated Hydraulic Conductivity (cm/s) (layer 1)	Field Capacity (layer 1)	-0.66	-0.66
Field Capacity (layer 1)	Wilting Point (layer 1)	0.88	0.88
Effective Saturated Hydraulic Conductivity (cm/s) (layer 2)	Van Genuchten Alpha ¹ (1/cm) (layer 2)	0.743	0.743
Effective Saturated Hydraulic Conductivity (cm/s) (layer 2)	Van Genuchten N ¹ (layer 2)	0.843	0.843
Van Genuchten Alpha ¹ (1/cm) (layer 2)	Van Genuchten N (layer 2)	0.298	0.298
Effective Saturated Hydraulic Conductivity (cm/s) (layer 4)	Van Genuchten Alpha (1/cm) (layer 4) ¹	0.948	0.948
Effective Saturated Hydraulic Conductivity (cm/s) (layer 4)	Van Genuchten N ¹ (layer 4)	0.908	0.908
Van Genuchten Alpha ¹ (1/cm) (layer 4)	Van Genuchten N ¹ (layer 4)	0.910	0.910
Maximum Leaf-Area Index	Precipitation Multiplier	N/A	0.60
Precipitation Multiplier	Average Temperature Adjustment (°C)	N/A	-0.60

¹Van Genuchten parameters were transformed to wilting point and field capacity for use in HELP (assumes wilting point and field capacity occur at 15.3 m (15 bars) and 3.37 m (0.33 bars) of head at 20°C, respectively); N/A: Not Applicable

Multiple realizations of the uncertain parameter values were generated using the Latin Hypercube sampling method for input to the HELP percolation model. The Latin Hypercube stratified sampling algorithm provides an efficient method of sampling for uncertainty assessment that preserves the correlations specified among parameters. The uncertainty distributions and correlation coefficients given in Table 4 and Table 5 were specified in the input to the Latin Hypercube sampling. The LHS computer code (Wyss and Jorgensen, 1998) was used to produce 50 realizations of uncertain parameter values for present conditions (scenario 1) and 50 realizations for future conditions (scenario 2).

4.3.2 Radon Gas Transport through the Cover

One objective of the cover design is attenuation of the radon emanation from the mill tailings to the atmosphere at the Monticello site. The landfill cover acts as a gas diffusion barrier, allowing time for the decay of the relatively short-lived Rn-222 gas (half-life = 3.8 days) during migration through the pore spaces of the cover soil. In particular, the compacted clay layer of the cover design serves as a barrier to radon migration due to its relatively low diffusion coefficient.

Regulatory requirements limit the allowable flux of Rn-222 from the waste to the land surface to 20 pCi/m²·s.

The conceptual model of radon migration through the landfill cover is one-dimensional upward transport driven by the difference in concentration in the tailings and the atmosphere. The processes affecting transport are molecular diffusion and radioactive decay. The boundary conditions for the problem are defined by a specified production rate of radon in the mill tailings and the assumption of zero radon concentration in the air at the land surface. Steady-state conditions, with regard to the radon concentration profile and flux, are also assumed to exist. Formulation of the radon gas transport model for present (scenario 3) and future (scenario 4) climatic conditions are presented below.

The mathematical model for steady-state one-dimensional transport of radon is expressed in the following equation:

$$D \frac{d^2 C}{dx^2} - \lambda C + \frac{R \rho \lambda E}{\phi} = 0 \quad (1)$$

where D is the effective diffusion coefficient for radon, C is the radon concentration in the pore space, λ is the decay constant of Rn-222, R is the specific activity of ²²⁶Ra in the soil, ρ is the dry bulk density of the soil, E is the radon emanation coefficient, and ϕ is the total porosity of the soil.

The RAECOM computer code (Rogers et al., 1984) is used to solve this equation for the radon flux at the land surface. This program provides a solution for radon transport through a multi-layer landfill cover in which the material properties vary among the layers. The relevant properties for the materials in the cover are the thickness of the layer, the effective diffusion coefficient, porosity, moisture content, and radon emanation rate. Comparison between the RAECOM computer code and the RADON computer code (NRC, 1989) for an identical sample problem presented in the documentation of both codes indicates that the same solution is obtained from both codes.

Parameter values for the materials in the landfill cover at the Monticello site are assigned a representative value in some cases and are treated as stochastic parameters for those parameters exhibiting significant variability and sensitivity. Parameter values and uncertainty distributions used in the performance assessment of the landfill cover are summarized in Table 6 for present conditions and in Table 7 for future conditions. Deterministic parameters are those for which a single value is presented in the tables. Values defining the uncertainty distributions for stochastic parameters are presented in the tables for those parameters.

Table 6. Parameter values for radon flux model (present conditions).

Layer # ¹	Layer Thickness (cm)	Diffusion Coefficient (cm ² /s)	Porosity	Moisture Content (weight %)	Radon Emanation (pCi/cm ³ ·s)
5 (mill tailings)	1500.	Geometric Mean 1.49E-2 S.D. log 0.25	.43	Mean 4.8 S.D. 0.91	Mean 1.72E-3 S.D. 2.86E-4

Layer # ¹	Layer Thickness (cm)	Diffusion Coefficient (cm ² /s)	Porosity	Moisture Content (weight %)	Radon Emanation (pCi/cm ³ -s)
4	61.	Geometric Mean 2.05E-3 S.D. log 0.25	.35	Mean 10.1 S.D. 0.91	0.
3	0.15	Mean 2.72E-5 S.D. 8.15E-6	.01	1.0	0.
2	30.	Geometric Mean 2.20E-2 S.D. log 0.25	.37	Mean 10.0 S.D. 0.91	0.
1	168.	Geometric Mean 1.08E-2 S.D. log 0.25	.43	Mean 10.1 S.D. 0.91	0.

¹See Figure 5 for layer configuration.

Table 7. Parameter values for radon flux model (future conditions).

Layer # ¹	Layer Thickness (cm)	Diffusion Coefficient (cm ² /s)	Porosity	Moisture Content (%)	Radon Emanation (pCi/cm ³ -s)
5 (mill tailings)	1500.	Geometric Mean 1.49E-2 S.D. log 0.25	.43	Mean 7.0 S.D. 2.10	Mean 1.72E-3 S.D. 2.86E-4
4	61.	Geometric Mean 2.05E-3 S.D. log 0.25	.35	Mean 10.1 S.D. 2.10	0.
3	0.15	Lower Bound 5.44E-6 Upper Bound 2.20E-2	.01	1.0	0.
2	30.	Geometric Mean 2.20E-2 S.D. log 0.25	.37	Mean 10.0 S.D. 2.10	0.
1	168.	Geometric Mean 1.08E-2 S.D. log 0.25	.43	Mean 10.1 S.D. 2.10	0.

¹See Figure 5 for layer configuration.

The radon transport model consists of five layers, in which layer 5 consists of the uranium mill tailings. The other layers correspond to the layers in the landfill cover design used as the basis for the performance assessment analyses (see Figure 5). The thickness of each layer is fixed for this analysis of radon release to the atmosphere and is based on the cover design. The thickness of the tailings is based on an engineering estimate from the repository geometry (DOE, 1995). The porosity of each layer is the expected value of total porosity, as utilized in the analysis of groundwater percolation to the waste and from DOE (1995) for the tailings. The radon source term for layers above the tailings is set to zero because the regulatory limits placed on radon flux apply only to the tailings as a source and not to the background radon emanations from native materials at the site.

A log-normal uncertainty distribution is assigned to the diffusion coefficient in layers 1, 2, 4 and 5 (where layer 5 is the mill tailings). The geometric mean for the diffusion coefficient is taken

from DOE (1995). The standard deviation of the log diffusion coefficient of 0.25 is based on the observation that measured values of the diffusion coefficient exhibit about one order of magnitude variability at intermediate values of moisture content (Rogers et al., 1984). The geometric mean plus or minus two standard deviations of 0.25 results in an approximate variability of one order of magnitude for the diffusion coefficients in the realizations.

The distribution of the effective diffusion coefficient in the geomembrane (layer 3) is based on the following approximation. It is assumed that the diffusion coefficient for the intact high-density polyethylene is essentially zero. The uncertainty distribution for the defect density is the same as that used for the groundwater percolation analysis (i.e., normal distribution with a mean of 1.2×10^{-3} defects/m² (5 defects/acre) and a standard deviation of 3.7×10^{-4} defects/m² (1.5 defects/acre) for present conditions and a uniform distribution from 2.4×10^{-4} defects/m² (1 defect/acre) to 1.2 defects/m² (5000 defects/acre) for future conditions. It is assumed that each defect in the geomembrane is 1 cm² and will have a diffusion coefficient equal to the expected value for the overlying sand layer. In addition, each defect represents an effective area for diffusion of 1 m² through the geomembrane to account for multidimensional focusing of diffusion through the defect. The effective diffusion coefficient of the entire geomembrane is the area-weighted average diffusion coefficient, taking into account the total number of defects/m². This approach results in a normal distribution of the effective diffusion coefficient under present conditions (scenario 3). For future conditions (scenario 4), a uniform uncertainty distribution results, in which the diffusion coefficient varies from a very low value to a value that corresponds to essentially complete degradation of the geomembrane.

The uncertainty in the moisture content of the layers in the model is based on the analysis of percolation flux through the cover. The steady-state groundwater flux in the vadose zone, assuming a unit hydraulic gradient, is related to the moisture content by the following relationship in the van Genuchten model:

$$\frac{K(\theta)}{K_s} = \left(\frac{\theta - \theta_r}{\phi - \theta_r} \right)^{\frac{1}{2}} \left\{ 1 - \left[1 - \left(\frac{\theta - \theta_r}{\phi - \theta_r} \right)^{\frac{1}{m}} \right]^m \right\}^2 \quad (2)$$

where $K(\theta)$ is the unsaturated hydraulic conductivity (equal to the flux for a unit gradient), K_s is the saturated hydraulic conductivity, θ is the volumetric moisture content, θ_r is the residual moisture content, ϕ is the porosity, and m is equal to $(n-1)/n$, where n is the van Genuchten fitting parameter. This expression was used to determine the corresponding value of moisture content in the tailings for each realization of percolation flux in the analysis (see Section 4.3.1), based on representative values of saturated hydraulic conductivity, residual moisture content, porosity, and van Genuchten n (Morrison et al., 1995). The resulting distribution of volumetric moisture content in the tailings for present conditions (scenario 3) has a mean of 7.2% and a standard deviation of 1.36%. The corresponding distribution for future conditions (scenario 4) has a mean of 10.5% and a standard deviation of 3.15%. These values of volumetric moisture content must be converted to weight % for input to the RAECOM program. Volumetric moisture content is converted to weight % moisture content by multiplying by the ratio of the density of water to the

dry bulk density. Using a value of 1.50 g/cm^3 for bulk density results in the values shown in Table 6 and Table 7 for the uncertainty distributions for layer 5 (mill tailings).

The uncertainty in moisture content in the layers above the tailings cannot be directly derived in a similar manner because the average percolation flux in these layers was not calculated in HELP. It is assumed for these layers that the means of the distributions for moisture content are equal to the expected values for those layers and the standard deviation is the same as that derived for the tailings.

Measurements of effective diffusion coefficient at different levels of moisture saturation indicate a negative correlation between diffusion coefficient and moisture content (Rogers et al., 1984). For the analysis of radon gas transport in this study, a correlation coefficient of -0.7 was assumed between diffusion coefficient and moisture content for each layer (except the geomembrane). This correlation is qualitatively consistent with data presented for medium to medium-low values of moisture saturation (Rogers et al., 1984).

The radon source term from the tailings is a stochastic parameter with a mean value of $0.00172 \text{ pCi/cm}^3\text{-s}$. This value corresponds to the average concentration of ^{226}Ra in all tailings piles of 669 pCi/g (DOE, 1990). It is calculated from the third term on the left side of Eq. (1), assuming a bulk density of 1.50 g/cm^3 , radon emanation coefficient of 0.35 , and porosity of 0.43 (DOE, 1995). The uncertainty distribution for the radon emanation rate in the tailings is based on data indicating that the radon emanation coefficient for Monticello acid and Monticell alkaline mill tailings differs by a factor of approximately 2 (Rogers et al., 1984). The standard deviation assigned to the radon source term corresponds to a value that varies by a factor of 2 between the mean minus two standard deviations and the mean plus two standard deviations.

4.3.3 Source-Term Release

The source-term model used in the groundwater-transport simulations was the MEPAS Computed Source Term Release Model (Streile et al., 1996). The source is conceptualized as a constantly-stirred tank reactor in which the contaminant inventory is homogeneously spread throughout the source volume. During each time step, constituent fluxes to each loss route selected by the user are computed, and then mass is subtracted from the available inventory. After each time step, the remaining inventory is again distributed evenly throughout the source area. The model keeps a mass balance for each constituent and stops releasing mass when the constituent inventory has been depleted. This source-term model is used to calculate radium-226 release rates from the mill tailings for both present and future climatic conditions in scenarios 5-8.

The input data required by the model varies with the source media and loss routes selected by the user. In this assessment, the conceptual-site model for the source consisted of “surface” soils contaminated with Ra-226 and leaching to the groundwater as the loss route. The input parameter values are listed in Table 8. Note that several parameters were varied stochastically. The distribution data for these parameters are listed along with prescribed point values that were used when distributions were deemed unnecessary.

Table 8. Parameter values for source-term model.

Parameter	Point Value	Distribution Type	Min.	Max.	Source
Time Step	1 yr	none	N/A	N/A	1
Source Length	N/A	uniform	0.91 m (3 ft)	550 m (1,800 ft)	2
Source Width	N/A	uniform	0.91 m (3 ft)	260 m (850 ft)	2
Source Thickness	12.5 m (41 ft)	none	N/A	N/A	1,2
Bulk Density	1.54 g/cm ³	none	N/A	N/A	1
Total Porosity	0.43	none	N/A	N/A	2
Moisture Content ⁴	0.26	none	N/A	N/A	2
Ra-226 K _d	N/A	uniform	50 ml/g	200 ml/g	1
Ra-226 Water Solubility Limit	4.0x10 ⁻⁸ mg/L (40 pCi/L)	none	N/A	N/A	1,2
Ra-226 Inventory	2,290 Ci	none	N/A	N/A	1, 2
Ra-226 Half-Life	1,599 yr	none	N/A	N/A	3
Darcy Percolation Rate (present)	N/A	log uniform	3.6x10 ⁻¹³ cm/s	3.8x10 ⁻⁹ cm/s	see Section 4.4.1
Darcy Percolation Rate (future)	N/A	log uniform	1.1x10 ⁻¹¹ cm/s	3.4x10 ⁻⁷ cm/s	see Section 4.4.1

¹ Assumed or derived; ² DOE (1995); ³ CRC (1990); ⁴ moisture content is assumed constant in MEPAS; N/A: Not Applicable

The parameters with uncertainty distributions were selected because their values varied significantly and because the Ra-226 leaching flux out of the source was highly sensitive to these parameters. Brief descriptions for each of the stochastic parameters and how their distribution parameters were derived are provided below.

Source Length and Width—The area of the source is conceptualized as a rectangle having a length and width. Source length is oriented along the predominant groundwater flow direction in the aquifer. Source width is oriented perpendicular to the predominant groundwater flow direction in the aquifer. In the MEPAS model, constituent fluxes are assumed to leave the bottom of the source homogeneously throughout the entire source area. However, in this case, a liner is placed under the entire source area, and leaks in the liner contribute to the actual downward percolation from the source term. For this reason, the source area was varied in an effort to simulate the leak areas and minimize artificial dilution. The source area was varied by independently varying the source length and source width. Although length and width were varied independently, they were correlated by a correlation coefficient of 0.75 to the effective conductivity of the liner. The source length was varied from 550 m (1,800 ft) down to 0.91 m (3 ft) using a uniform distribution. The source width was varied from 260 m (850 ft) down to 0.91 m (3 ft) using a uniform distribution. The maximum values corresponded to the actual dimensions of the repository, and the minimum dimensions corresponded to the assumed minimum dimensions of the effective leak area beneath the repository.

Ra-226 K_d—The partition coefficient, K_d, is a parameter that describes a constituent's tendency to sorb onto soil solids. It is defined as the ratio of a constituent's particulate concentration (g-contaminant/g-soil) to a constituent's dissolved concentration (g-contaminant/ml-water). The

higher a constituent's K_d value, the higher the constituent's tendency to sorb onto soil solids. A constituent's K_d affects its availability in soil water and has the effect of retarding its transport through the groundwater pathway. Site-specific K_d values for Ra-226 were not available; therefore, the Ra-226 K_d was conservatively estimated at 100 ml/g. It should be noted that estimates for sorption-coefficient values in the literature ranged 500 ml/g for sandy soil to 9100 ml/g for clay (Thibault et al., 1990). Because this value is an estimate and can greatly impact Ra-226 transport, it was treated as a stochastic parameter. It was varied with an assumed uniform distribution between 50 and 200 ml/g. The inventory [Ci], repository volume [m^3], bulk density [g/cm^3], and K_d [ml/g] in Table 8 were used to calculate the concentration of Ra-226 [pCi/ml] in the pore water. If this value was less than the solubility in Table 8, it was multiplied by the product of the Darcy percolation rate and cross-sectional area to calculate the rate of release of Ra-226; otherwise, the solubility was used as the maximum concentration in the pore water.

Darcy Percolation Rate (present and future)—The Darcy percolation rate describes the rate at which water is entering the source zone. The percolation values used in this assessment were derived using the HELP computer model as described in Section 4.3.1. Results of the HELP model indicated that under current conditions, the Darcy percolation could range from a high of 3.8×10^{-9} cm/s to a low of 3.55×10^{-13} cm/s with a log-uniform distribution. Under future conditions, the HELP model indicated that the percolation rate could range from a high of 3.39×10^{-7} cm/s to a low of 1.05×10^{-11} cm/s with a log-uniform distribution. These distributions were used by MEPAS to independently simulate present and future climatic source term releases for scenarios 5-8.

4.3.4 Vadose-Zone Transport

The vadose-zone transport model used for scenarios 5-8 was the MEPAS vadose-zone transport model (Whelan et al., 1996). The vadose-zone model employs a semi-analytical solution to the advective-dispersive equation for solute transport. Solute transport is described by one-dimensional advection vertically downward with longitudinal dispersion. The model assumes that the vadose zone has the same areal extent as the source zone above it and has a uniform thickness that is defined by the user. The soil within the vadose zone is assumed to be homogeneous and isotropic; therefore, separate vadose-zone models must be created and connected in series to simulate a soil profile that has more than one distinct layer.

The conceptual site model for the vadose zone in this assessment (scenarios 5-8) consisted of two distinct elements: (1) a double composite-liner system beneath the repository composed of sand, two geomembrane liners, two geosynthetic clay-liners, and a transmissive leachate collection system; and (2) the undisturbed vadose zone between the liner and the water table (see Figure 6 and Figure 7). Because the sand layer (30 cm thick) and the leachate collection region of the composite-liner system are highly transmissive, only the geomembrane and geosynthetic clay-liner materials were modeled. The parameter values and distributions used for the effective composite-liner system are listed in Table 9.

Two parameters were varied stochastically for the composite liner system based on their range and impact on Ra-226 transport. The Ra-226 partitioning coefficient, K_d , and its distribution

were described in Section 4.3.3, and the identical distribution is used for the vadose-zone models. The distribution for effective saturated hydraulic conductivity of the composite-liner system is more complex and described below.

Table 9. Parameter values for double composite-liner system in vadose-zone model.

Parameter	Point Value	Distribution Type	Min.	Max.	Source
Total Porosity	0.50	none	N/A	N/A	1
Field Capacity	0.40	none	N/A	N/A	2
Saturated Hydraulic Conductivity	N/A	log uniform	1.0×10^{-9} cm/sec	1.0×10^{-4} cm/sec	2
Thickness of composite liner	1.5 cm (0.6 in)	none	N/A	N/A	3
Longitudinal Dispersivity ⁴	0.015 cm (0.006 inches)	none	N/A	N/A	2 (1% of thickness)
Bulk Density	1.33 g/cm ³	none	N/A	N/A	2 (= (1-total porosity)*2.65)
Ra-226 K _d	N/A	uniform	50 ml/g	200 ml/g	2

¹Freeze and Cherry (1979); ²Assumed or derived; ³DOE (1995); ⁴for vadose zone (Burck et al., 1995); N/A: Not Applicable

The saturated hydraulic conductivity describes the maximum rate at which water can flow through a medium. If the rate of water entering the composite liner system from the medium above (i.e., mill tailings in the source-term model) exceeds the conductivity of the effective composite liner, then the water flux is capped at the saturated hydraulic conductivity value of the effective liner. The liner system, as modeled, consisted of two layers of a 0.15-cm thick geomembrane liner above a ~0.6-cm thick geosynthetic clay liner. The intrinsic values for the saturated conductivities of the two materials (1×10^{-9} cm/s for the geosynthetic clay liner and 2×10^{-13} cm/s for the geomembrane liner) were assumed based on literature values (DOE, 1995). We assumed that a distribution of defects could occur in both the geomembrane liner (1 cm² holes; see Section 4.3.2 for defect distribution) and the geosynthetic clay liner (1 cm² “rolls” or creases caused by overlapping the liner sheets). Estimates revealed that with just one defect hole in the geomembrane liner, the geosynthetic clay liner would provide the limiting conductivity. Assuming a distribution of creases in the clay liner led to an effective conductivity distribution for the composite liner system as shown in Table 9. It should be noted that this effective conductivity is used only if the sampled percolation rate in the source-term model (see Table 8) is greater than the effective liner conductivity. In nearly all cases during present climate conditions, the percolation rate is less than the lowest value of the effective conductivity of the liner, so the effective conductivity of the liner is not limiting. However, for future conditions, the percolation rate will exceed the minimum effective conductivity of the liner in about half the sampled realizations.

The effective conductivity of the liner layer was correlated to source length and width by a moderately positive correlation coefficient of 0.75. This was done to reduce the artificial dilution associated with a simulated large source area having only a few defects in the composite liner system through which contaminant could transport. If the sampled effective conductivity of

the liner were small, this would indicate few defects and a smaller area through which transport could occur. On the other hand, if the sampled effective conductivity were large, this would indicate a larger number of defects and a larger area through which transport could occur (see Section 4.3.3 for more details).

Another vadose-zone “layer” was used to represent the undisturbed soil layer beneath the composite liner system. Two different thicknesses were used in the vadose-zone model to represent vadose-zone transport to the two different aquifers: (1) the shallow alluvial aquifer (scenarios 5-6) and (2) the deeper Burro Canyon aquifer (scenarios 7-8). The transport to each aquifer was modeled in separate runs. The input parameter values and distributions used for the undisturbed soil layer in the vadose-zone model are listed below in Table 10.

Table 10. Parameter values for vadose-zone layer for two aquifers.

Parameter	Point Value	Distribution Type	Min.	Max.	Source
Total Porosity	0.41	none	N/A	N/A	1
Field Capacity	0.18	none	N/A	N/A	1
Hydraulic Conductivity	1.0 cm/sec	none	N/A	N/A	2,3
Thickness of Vadose Zone (Shallow Alluvial Aquifer)	4.6 m (15.0 ft)	none	N/A	N/A	4
Longitudinal Dispersivity ⁵ (Shallow Alluvial Aquifer)	4.6 cm (0.15 ft)	none	N/A	N/A	2 (1% of thickness)
Thickness of Vadose Zone (Deep Burro Canyon Aquifer)	30 m (100 ft)	none	N/A	N/A	2,4
Longitudinal Dispersivity ⁵ (Deep Burro Canyon Aquifer)	0.3 m (1.0 ft)	none	N/A	N/A	2 (1% of thickness)
Bulk Density	1.5 g/cm ³	none	N/A	N/A	2
Ra-226 K _d	N/A	uniform	50 ml/g	200 ml/g	2

¹Morrison et al. (1995); ²Assumed or derived; ³Freeze and Cherry (1979); ⁴DOE (1995); ⁵for vadose zone (Buck et al., 1995); N/A: Not Applicable

4.3.5 Saturated-Zone Transport

Groundwater transport for scenarios 5-8 was simulated using the MEPAS saturated-zone transport model (Whelan et al., 1996). The saturated-zone transport model employs a semi-analytical solution to the advective-dispersive equation for solute transport. Solute transport is described by one-dimensional advection in the predominant groundwater flow direction with three-dimensional dispersion (i.e., longitudinal, lateral, and vertical dispersivities). The model assumes that the saturated-zone layer has an unbounded areal extent and has a uniform thickness that is defined by the user. The soil within the saturated zone is assumed to be homogeneous and isotropic. The peak concentration of contaminants in the groundwater can be determined in the saturated-zone transport model by specifying a location for a receptor well. The model will determine the time varying concentrations at this location and SUMMM records the peak concentration and time of peak concentration for each realization of a stochastic simulation.

Two aquifers were modeled separately with the saturated-zone transport model: (1) the shallow alluvial aquifer (scenarios 5-6) and (2) the deep Burro Canyon aquifer (scenarios 7-8). The input parameter values used for both aquifers are listed in Table 11. Note that several of the parameters were varied stochastically, and several parameters (dispersivity values) were computed during run-time by the sensitivity/uncertainty module SUMMM. The equations are described in the footnotes to the table. Several important parameters are also discussed in more detail below.

Table 11. Parameter values for saturated-zone model.

Parameter	Value	Distribution Type	Min.	Max.	Source
Total Porosity ^a	N/A	uniform	0.35	0.50	1,2
Darcy Velocity	N/A	log uniform	3.0E-07 cm/sec	3.0E-05 cm/sec	3
Thickness of Aquifer (Burro Canyon aquifer)	30 m (100 ft)	none	N/A	N/A	4
Thickness of Aquifer (alluvial aquifer)	1.2 m (4 ft)	none	N/A	N/A	4
Bulk Density	1.5 g/cm ³	none	N/A	N/A	1,4
Longitudinal Travel Distance to Well Intake ^b	N/A	uniform	0.76 m (2.5 ft)	274 m (901 ft)	4
Horizontal Distance off Plume Center Line to Well Intake	0 m	none	N/A	N/A	1
Vertical Distance Below Water Table To Well Intake	0 m	none	N/A	N/A	1
Longitudinal Dispersivity ^c	N/A	uniform	0.076 m (0.25 ft)	27.4 m (90.1 ft)	1
Lateral Dispersivity ^d	N/A	uniform	0.025 m (0.0825 ft)	9.0 m (29.7 ft)	1
Vertical Dispersivity ^e	N/A	uniform	1.9x10 ⁻⁴ m (6.3x10 ⁻⁴ ft)	0.069 m (0.23 ft)	1
Ra-226 K _d	N/A	uniform	50 ml/g	200 ml/g	1

^a Effective porosity set equal to total porosity; ^b Travel distance = ((1/2)*source length) + 1; ^c Longitudinal dispersivity = 0.1*travel distance; ^d Lateral dispersivity = 0.033*travel distance; ^e Vertical dispersivity = 0.00025*travel distance (from Buck et al., 1995)

¹ Assumed or derived; ² Freeze and Cherry (1979); ³ Smith (2001); ⁴ DOE (1995)

The total porosity describes the total fraction of void spaces in the aquifer. All void spaces in the aquifer are assumed to be filled with water; however, not all of the water is necessarily contributing to the flow. The effective porosity describes the fraction of the voids that contain flowing water. In this assessment, the effective porosity was set equal to the total porosity because site-specific soil characteristics were not known. The effective porosity affects the velocity of the pore water traveling through the aquifer and, subsequently, the rate at which the contaminant is traveling. A uniform distribution was assumed as shown in Table 11. The range was based on literature values for a sandy soil, which closely matched the composition of the alluvium aquifer.

The Darcy velocity of the groundwater describes the volumetric flux of water through the aquifer. The Darcy velocity is converted to pore-water velocity by dividing Darcy velocity by the effective porosity. The pore-water velocity represents the actual velocity of the groundwater, which is greater than the Darcy velocity due to the reduced area available for flow in the soil pores (the velocity must increase as the cross-sectional area of flow is reduced to maintain conservation of mass). Finally, the solid-water partitioning coefficient, K_d , for Ra-226 assumes the same distribution as those described in the source-term and vadose-zone models.

4.3.6 Human Exposure

Three modules in MEPAS (Streng and Chamberlain, 1996) were used to evaluate human exposure in this assessment. In the MEPAS system, chronic human health impacts are computed based on contaminant concentrations in the environment. The process of computing the health impacts from environmental concentrations is broken down into three components or modules: the Chronic Exposure module, the Receptor Intake module, and the Human Health Impact module. The Chronic Exposure module receives as its input time-varying contaminant concentrations in the various exposure media (e.g., ground water, surface water, surface soil, and air) and computes time-averaged concentrations for each exposure pathway selected by the user. The time frame for averaging is specified by the user. Exposure pathways available to the user depend on the exposure medium. Some examples of exposure pathways are drinking water, fish ingestion, meat ingestion, milk ingestion, vegetable ingestion, soil dermal contact, and indoor air inhalation. The Receptor Intake module receives time-averaged concentrations by exposure pathway and computes the time-averaged contaminant intakes and doses by exposure pathway. The model requires the user to specify receptor parameters such as body weight, length of exposure, water intake rates, and air inhalation rates. The Human Health Impact module receives the time-averaged intake and doses by exposure pathway and computes time-averaged human-health effects by exposure pathway as selected by the user. Some examples of health effects available to select are hazard quotient, cancer incidence, cancer fatalities, and dose.

Equations and methodologies used in all three modules are typical of those recommended by the EPA and various state agencies. Default values for many of the equation parameters are provided in MEPAS and are also based on EPA and various agency recommendations; however, the user also has the option of editing each input parameter value through the MEPAS user interfaces. While most parameters have default values provided, certain parameters such as duration of exposure, exposure pathways, intake rates, etc. must be input by the user. Selected input parameter values for each of the three modules are listed below in Table 12, Table 13, and Table 14 for scenarios 5-8 of this assessment. None of the parameters were varied stochastically for this assessment.

As noted in Section 4.1, there are two aquifers (shallow alluvium and Burro Canyon) associated with the site. The water usage for each aquifer was assumed to be different as shown in Table 12. It was assumed that the shallow alluvial aquifer was used for agricultural purposes only and that the deeper Burro Canyon aquifer was used for both agricultural purposes and drinking water.

Table 12. Parameter values for chronic exposure module.

Parameter	Value
Time to start exposure computation (alluvial aquifer) ¹	10,000 years
End time for exposure computation (alluvial aquifer) ¹	20,000 years
Number of evaluation points (alluvial aquifer) ²	334
Time to start exposure computation (Burro Canyon aquifer) ¹	12,000 years
End time for exposure computation (Burro Canyon aquifer) ¹	27,000 years
Number of evaluation points (Burro Canyon aquifer) ²	500
Exposure duration	30.0 years
Exposure pathways selected (alluvial aquifer)	leafy vegetable ingestion, other vegetable ingestion, meat ingestion, milk ingestion
Agricultural water usage (alluvial aquifer)	crop irrigation, animal drinking, and irrigation of animal feed
Fraction of the year that groundwater is used for irrigation (alluvial aquifer)	1.0
Irrigation rate (alluvial aquifer) ³	100 L/m ² /month
Exposure pathways selected (Burro Canyon aquifer)	drinking water, leafy vegetable ingestion, other vegetable ingestion, meat ingestion, milk ingestion
Agricultural water usage (Burro Canyon aquifer)	crop irrigation, animal drinking, and irrigation of animal feed
Fraction of the year that groundwater is used for irrigation (Burro Canyon aquifer)	1.0
Irrigation rate (Burro Canyon aquifer)	100 L/m ² /month

¹The start and end times for the exposure computation are estimated based on the calculated times for peak concentration in the saturated-zone transport model

²The number of evaluation points was chosen to yield an exposure duration of 30 years.

³Default value in MEPAS (Streng and Chamberlin, 1995)

Table 13. Parameter values for receptor intake module.

Parameter	Value ¹
Body weight of individual	70 kg
Exposure duration	30.0 yr
Ingestion rate of leafy vegetables	0.021 kg/d
Ingestion rate of other vegetables	0.13 kg/d
Ingestion rate of meat	0.065 kg/d
Ingestion rate of milk	0.075 L/d
Ingestion rate of water	2 L/d

¹Default values used in MEPAS (Streng and Chamberlin, 1995)

Table 14. Parameter values for human health impact module.

Parameter	Value
Health metric	radiation dose commitment

4.4 Results and Discussion of Base-Case Composite Design

The results of the stochastic simulation using the base-case composite cover design (Figure 5) are presented in the following sections for scenarios 1-8 (see Table 3). The results of scenarios 1 and 2 (water percolation through the cover) are presented in Section 4.4.1; the results of scenarios 3 and 4 (radon gas transport through the cover) are presented in Section 4.4.2; the results of scenarios 5 and 6 (radium transport to the shallow alluvial aquifer) are presented in Section 4.4.3; and the results of scenarios 7 and 8 (radium transport to the deep Burro Canyon aquifer) are presented in Section 4.4.4.

4.4.1 Percolation through the Composite Cover

As discussed in Section 4.3.1, the code HELP was used to simulate the range of percolation fluxes through the composite cover at Monticello. Results of the Monte Carlo simulations using the HELP code are presented as a cumulative probability in Figure 9 for both present-day (scenario 1) and future conditions (scenario 2). The simulations for future conditions included additional uncertainty in input parameters such as precipitation, temperature, and integrity of the geomembrane liner. Results show that the uncertainty in the input parameters cause a large range in the percolation through the cover (5-6 orders of magnitude). The performance of the cover under future conditions is seen to be worse (higher percolation through the cover) because of the potential for increased precipitation and a degraded geomembrane liner. However, the cumulative distributions of water percolation for both present-day and future conditions are generally below the equivalent maximum hydraulic conductivity value of 1×10^{-7} cm/s as prescribed in 40 CFR 264.301. The probabilistic results shown in Figure 9 indicate that there is no risk under present-day conditions that the percolation through the cover will exceed the regulatory requirement for maximum hydraulic conductivity, but this probability increases to approximately 5% for future conditions (we assume a unit gradient, making the percolation flux and hydraulic conductivity equivalent).

Figure 9. Cumulative probability distribution of water percolation reaching the mill tailings for present and future conditions (scenarios 1 and 2).

4.4.2 Radon Gas Flux at the Surface

Probabilistic analyses of radon gas transport for the landfill cover performance assessment were performed using the FRAMES computer program. The RAECON computer code was coupled into the FRAMES code as an alternative model in the source module. The RAECON model in the source module was linked to the sensitivity module in FRAMES and 100 realizations of the system were simulated for present conditions and for future conditions (scenarios 3-4).

The results of these simulations are shown in **Error! Reference source not found..** For present climatic conditions and essentially undegraded geomembrane performance, the simulated Rn-222 flux at the land surface spans approximately three orders of magnitude with a maximum value of about 1 pCi/m²-s. The median value among the 100 realizations of cover performance is about 0.16 pCi/m²-s for present conditions. For future conditions (>100 years), the simulated Rn-222 flux at the land surface spans approximately three orders of magnitude with a maximum value of about 2.9 pCi/m²-s. It should be noted that the uncertainty reflected in the results for future conditions is significantly broader than the uncertainty for present conditions in absolute (linear) terms. The median value among the 100 realizations of cover performance is about 3.4 pCi/m²-s for future conditions.

Figure 10. Cumulative probability distribution of simulated radon flux at the land surface for present and future conditions (scenarios 3 and 4).

Most of the variability among realizations for both the present and future conditions is attributable to uncertainty in the values of the effective diffusion coefficient in the tailings and cover layers. Uncertainty in the radon source term and the values of moisture content contribute to overall uncertainty in the system performance to a lesser extent.

The difference between the results for present conditions and future conditions is due primarily to potentially degraded performance of the geomembrane as a diffusion barrier in the future. Uncertainty exists with regard to the impact of numerous degradation processes for high-density polyethylene geomembranes and estimates suggest a lifetime of several hundred years (Koerner et al., 1991; Hsuan and Koerner, 1998). It should be noted that in the model the geomembrane layer functions as a significant barrier to diffusion only at relatively low values of defect density, primarily due to the relative thinness of the layer. In addition, the somewhat higher values of moisture content in the tailings for future, wetter climatic conditions lead to enhanced radon diffusion due to the reduced volume of the air phase in the medium.

The results for both the present and future conditions are influenced by a competing interaction between two parameters in the model for radon transport. Transport of radon gas by diffusion is enhanced at higher moisture content because of the reduced air-phase volume in the soil under these conditions. This enhancement is due to the relatively higher radon concentration in the air phase (same radon mass in a smaller volume of air) and the resulting larger concentration gradient between the mill tailings and the atmosphere at land surface. In a competing manner, higher moisture content results in a lower effective diffusion coefficient for radon gas. This relationship is represented by the negative correlation between moisture content and effective diffusion coefficient in this study. The aggregate impact of this competing interaction between moisture content and effective diffusion coefficient on the probabilistic analyses conducted for this study is not clear, but is probably dominated by variability in the diffusion coefficient.

Overall, these results indicate a high degree of confidence (nearly 100%) that the landfill cover design at Monticello meets the performance objective of 20 pCi/m²-s of Rn-222 flux from the tailings at the land surface for present conditions. The simulation results for future conditions indicate relatively high confidence (approximately 97%) that the Rn-222 flux from the tailings at the land surface will be less than the regulatory limit. The expected performance of the landfill cover design for future conditions, as represented by the median (3.4 pCi/m²-s) or the mean (5.0 pCi/m²-s) is significantly lower than the regulatory limit.

It should be noted, however, that the analyses of radon gas transport for this study are based on nominal behavior of the landfill cover system. The thickness of each layer in the design is fixed in this performance assessment. Consequently, these analyses do not address scenarios that could impact the thickness of the cover (e.g., erosion or subsidence). In addition, some processes and features that could potentially compromise performance of the cover system as a diffusion barrier (e.g., animal burrowing and desiccation cracking) were not explicitly evaluated.

4.4.3 Groundwater Concentration and Exposure Assessment for the Shallow Alluvial Aquifer

In this section (and the next), two performance metrics were recorded during the FRAMES groundwater transport simulations: 1) the peak Ra-226 concentration in the water crossing the down-gradient boundary of the repository and 2) the peak total dose for Ra-226 and its progeny for specified exposure pathways associated with the consumption of groundwater from a well at the down-gradient boundary of the waste site.

The peak groundwater concentrations for Ra-226 [pCi/L] were recorded in FRAMES for 100 realizations of pore-water transport from the mill tailings to the shallow alluvial aquifer (scenarios 5-6). Cumulative probabilities of the peak concentration are plotted in Figure 11 for both present and future conditions. These results can be used to determine the probability of exceeding the maximum contaminant level (MCL) or risk-based concentration; the MCL for Ra-226 is 5 pCi/L (40 CFR 192.02(a) and 40 CFR 192(b)(2)).

Results indicate that the simulated maximum Ra-226 concentration in the groundwater is approximately 0.2 pCi/L, which is less than the MCL. The low peak concentrations are attributable mainly to the low percolation rates through the source, high K_d values for Ra-226, and a relatively short half-life for Ra-226. The percolation rate range computed by the HELP model for current conditions was $3.55\text{E-}13$ cm/s to $3.80\text{E-}09$ cm/s. The percolation rate computed by the HELP model for future conditions was $1.05\text{E-}11$ cm/s to $3.39\text{E-}07$ cm/s. These low percolation rates coupled with high K_d values that ranged from 50 ml/g to 200 ml/g resulted in long travel times to the receptor well. In all modeling runs, the times of peak concentrations were between 7,000 and 15,000 years. These long travel times coupled with a half-life for Ra-226 of 1,599 years resulted in the low peak concentrations at the receptor well location. Therefore, the stochastic modeling in this assessment indicates that for both current and future conditions there is no risk of exceeding the MCL. However, it should be emphasized that a number of assumptions (albeit conservative) were made in the development of this model, and only a limited number of features, events, and processes were considered.

Figure 11 also shows that the concentrations for future conditions are greater than the concentrations for present conditions by 2-3 orders of magnitude. The primary reason is the increased infiltration rate during future conditions caused by greater precipitation and more degradation of the cover and liner materials. It should also be noted that the simulations for both present and future conditions result in a large range of concentrations due to the large range of stochastic parameter distributions that were used in the models. Future simulations will attempt to provide a sensitivity analysis and reduce the uncertainty in these parameters with more refined data.

Figure 11. Cumulative probability distribution for peak Ra-226 concentration in the shallow alluvial aquifer for present and future conditions (scenarios 5-6). Note: concentration values of 0 are not plotted on the log scale.

The cumulative probability distribution for dose (millirem per year) resulting from the shallow alluvial aquifer simulations were plotted for both present and future conditions. In MEPAS, the cumulative dose was recorded over a moving 30-year period, and the dose rate in millirem per year was calculated by dividing the peak cumulative dose by 30 years. The maximum effective dose equivalent for all radionuclides and all routine DOE exposure pathways is 100 mrem/year (DOE Order 5400.5 II 1.a).

For both the current and future conditions, the peak cumulative dose from Ra-226 and its decay products for all pathways is 0.78 mrem/year, which is considerably less than the maximum effective dose equivalent. However, only Ra-226 and its progeny were considered in this assessment, and only the groundwater pathway was evaluated. In addition, the low peak cumulative doses are attributable to the low percolation rates through the source, high K_d values for Ra-226, and a relatively short half-life for Ra-226. In all modeling runs, the times of peak cumulative doses were between 10,000 and 17,000 years. These long travel times coupled with a half-life for Ra-226 of 1,599 years resulted in the low peak cumulative doses for the exposures associated with water usage from the receptor well location. Also it should be noted that the time of peak cumulative dose may vary from the time of peak Ra-226 concentration at the groundwater well. The cumulative dose incorporates the doses due to progeny as well, and

progeny may peak at different times than the parent constituent (different half-lives and different K_d values; the K_d values for the progeny were assumed to be 1000 ml/g).

Figure 12. Cumulative probability distribution for peak cumulative dose for Ra-226 and its progeny from the shallow alluvial aquifer for present and future conditions (scenarios 5-6).
Note: dose values of 0 are not plotted on the log scale.

Similar to the cumulative distribution for concentration, the dose results in Figure 12 show that there is a large spread in the results. In addition, the future conditions yield doses that are 2-3 orders of magnitude larger than the doses for present-day conditions. Future analyses will consider sensitivity analyses and the reduction of uncertainty in the input parameters.

4.4.4 Groundwater Concentration and Exposure Assessment for the Burro Canyon Aquifer

The results presented in this section are similar to the results presented in the preceding section. The only difference in the conceptual models is that the groundwater concentration and exposure assessment are performed for the deeper Burro Canyon aquifer (scenarios 7 and 8) as opposed to the shallow alluvial aquifer (scenarios 5 and 6).

Simulations of Ra-226 transport from the mill tailings to the Burro Canyon aquifer resulted in undetectable (zero) concentrations in the groundwater during the simulation period for nearly all

conditions. The simulations with present climatic conditions resulted in zero groundwater concentrations for all realizations in the Burro Canyon aquifer. The value for the peak Ra-226 concentration in the groundwater under future conditions was 5×10^{-11} pCi/L, which is well below the MCL of 5 pCi/L. The extremely low (or zero) concentrations are due to the low percolation rates through the source, high K_d values for Ra-226, and a relatively short half-life for Ra-226 that resulted in long travel times to the receptor well in the aquifer (the two non-zero concentrations simulated under future conditions occurred at 8,000 and 14,000 years). The concentrations predicted for the Burro Canyon aquifer are significantly lower than those for the shallow alluvial aquifer due to the difference in thickness of the vadose zones. The vadose-zone depth to the alluvial aquifer is 4.6 m (15 ft), while the vadose-zone depth to the Burro Canyon aquifer is 30 m (100 ft). The added depth leads to longer travel times and greater decay of Ra-226.

Figure 13 shows the simulated cumulative distribution for peak dose resulting from transport of Ra-226 to the Burro Canyon aquifer. Only the results for the future infiltration scenario are presented in the figure because the results for the present conditions resulted in doses that were zero for all realizations. The models simulating future conditions resulted in a peak cumulative dose of 8.62×10^{-10} mrem/year, which is well below the regulatory limit. The peak cumulative doses occurred between 12,000 and 18,000 years in all the simulations, which are longer than the times of peak doses for the shallow alluvial aquifer. The doses predicted for the Burro Canyon aquifer are significantly lower than those for the alluvial aquifer due to the difference in thickness of the vadose zones. The added depth leads to longer travel times and thus more time for the Ra-226 to decay. Also it should be noted that the time of peak cumulative dose may vary from the time of peak Ra-226 concentration at the groundwater well. The cumulative dose incorporates the doses due to progeny, and progeny may peak at different times than the parent constituent.

Figure 13. Cumulative probability distribution for peak cumulative dose for Ra-226 and its progeny from the Burro Canyon aquifer for future conditions (scenario 8). Note: dose values of 0 are not plotted on the log scale.

4.5 Results and Discussion of Alternative Designs and Scenarios

An alternative cover design was also evaluated for the Monticello disposal site using probabilistic calculations. The performance of an evapotranspiration (ET) cover (Dwyer, 2000) was evaluated using the same probabilistic methods described for the existing design. The ET cover consists of a simplified design consisting of only the top layer (layer 1) shown in Figure 5. The ET cover concept makes use of the natural moisture storage capacity of this upper layer of soil and the relatively high efficiency of natural vegetation for the removal of moisture via evapotranspiration. An assessment of landfill-cover cost versus performance can be made based on these results. This example illustrates the use of probabilistic simulations and risk-based performance metrics to evaluate alternative designs for long-term covers.

4.5.1 Percolation through the ET Cover

Simulated percolation flux through the landfill cover in the HELP code is significantly higher for the ET cover than for the composite cover, as shown in the cumulative distribution plots in

Figure 14. For present conditions, the 50th percentile of percolation is almost three orders of magnitude higher for the ET cover than for the composite cover. For future conditions, the 50th percentile is more than one order of magnitude higher for the ET cover compared to the composite cover. There is significantly greater difference in simulated percolation for present versus future conditions for the composite cover relative to the ET cover.

Although the ET cover does not perform as well as the composite design with regard to percolation flux, the majority of the realizations for future conditions yield percolation flux values that are less than the regulatory limit. All of the realizations for present conditions simulate a value of percolation flux less than the regulatory limit. The expected behavior of the ET cover for future conditions is percolation lower than the regulatory limit. In addition, the ET cover is much cheaper to construct than similar designs such as the one at Monticello (Dwyer, 2000).

Uncertainty in simulated percolation flux is considerably greater for the composite cover than for the ET cover under both present and future conditions. This is due to the greater number of components in the composite cover design in comparison to the ET cover. Uncertainty in the properties and behavior of individual layers in the composite design result in greater aggregate uncertainty in overall performance. One advantage of a simplified design, such as the ET cover, is a lower level of uncertainty in the performance of the landfill cover design. However, this lower level of uncertainty comes at the expense of significantly greater expected value of percolation flux through the system in the case of the ET cover. It is also interesting to note that the worst simulated performance with regard to percolation flux (i.e., the 99th percentiles of the cumulative distribution functions) for the composite cover and the ET cover are very similar. This implies that we cannot state with a very high degree of confidence that the composite cover will have a lower percolation flux than the ET cover, even though the expected percolation through the composite cover is significantly less than for the ET cover.

Figure 14. Cumulative probability distribution of water percolation reaching the mill tailings for present and future conditions (scenarios 1 and 2) and for the evapotranspiration cover.

4.5.2 Radon Gas Flux at the Surface

Simulated Rn-222 flux through the surface of the landfill cover is significantly higher for the ET cover relative to the composite cover, for both present and future conditions, as shown in the cumulative distribution plots in Figure 15. The radon flux in the ET cover is somewhat greater than two orders of magnitude higher than in the composite cover for present conditions and somewhat greater than one order of magnitude higher for future conditions. This significant degradation in simulated performance for the ET cover is due to the important roles of the geomembrane and clay layer as barriers to radon diffusion in the composite design.

Uncertainty in the Rn-222 flux for the ET cover is significantly greater than the uncertainty for the composite cover in absolute (linear) terms. However, examination of Figure 15 indicates that uncertainty in radon flux is approximately log-normally distributed for both the ET and the composite cover, with a similar degree of uncertainty in the log-transformed values of simulated radon flux.

There are only small differences in the distributions of simulated radon flux for present and future conditions with the ET cover, as shown in Figure 15. These differences are due to differences in the uncertainty of the moisture content of the ET layer under present and future climatic conditions and are generally not significant.

A majority of the realizations of the ET cover exceed the performance objective of 20 pCi/m²-s, for both present and future conditions. The 50th percentile values of the simulated Rn-222 flux are about 25 pCi/m²-s and 30 pCi/m²-s for present and future conditions, respectively. This result indicates an apparent violation of the regulatory limits for radon flux with the ET cover design. Thus, the ET cover design may be simplified, cheaper, and adequate for the performance metrics of percolation flux, groundwater concentrations, and cumulative dose, but inadequate to meet the radon flux standards. It should be noted, however, that the model for radon diffusion used in this study made the simplifying assumption that mill tailings with the higher Ra-226 concentrations were uniformly distributed within the waste layer of the landfill. In actuality, an effort was made to place the highest activity mill tailings deeper in the waste cell and cover these with relatively less contaminated soils. This stratification of contaminants within the relatively thick waste layer would result in significant attenuation of radon flux through the overlying cover.

Figure 15. Cumulative probability distribution of radon-222 flux at the landfill cover for present and future conditions (scenarios 3 and 4) and for the evapotranspiration cover.

4.5.3 Groundwater Concentration and Exposure Assessment for the Shallow Alluvial Aquifer

The distributions of simulated Ra-226 concentrations in the shallow alluvial aquifer for the ET cover are significantly higher than for the composite cover for both present and future conditions, as shown in the cumulative probability distribution plots in Figure 16. The simulated concentrations of Ra-226 are about four to five orders of magnitude higher for the ET cover design at the 50th percentile levels for the present and future conditions. However, the maximum simulated Ra-226 concentrations for the ET cover are still significantly lower than the MCL for Ra-226 of 5 pCi/L. The range of uncertainty in the Ra-226 concentration is very high for both the ET cover and the composite cover, spanning over 20 orders of magnitude. It should be noted that the simulated concentrations for most realizations are extremely small and are essentially zero in any real terms.

Figure 16. Cumulative probability distribution of Ra-226 concentration in the shallow alluvial aquifer for present and future conditions (scenarios 5 and 6) and for the evapotranspiration cover.

The distributions of simulated peak cumulative dose from Ra-226 and its progeny in the shallow alluvial aquifer for the ET cover are significantly higher than for the composite cover for both present and future conditions, as shown in the cumulative probability distribution plots in Figure 17. The simulated values of peak cumulative dose are about three to four orders of magnitude higher for the ET cover design at the 50th percentile levels for the present and future conditions. The maximum simulated values of peak cumulative dose are still significantly lower than the regulatory limit of 100 mrem/year for both the ET cover and the composite cover for present and future conditions. It should be noted that the simulated doses for most realizations are extremely small and are essentially zero in any real terms.

Figure 17. Cumulative probability distribution of peak cumulative dose for Ra-226 and its progeny in the shallow alluvial aquifer for present and future conditions (scenarios 5 and 6) and for the evapotranspiration cover.

4.5.4 Groundwater Concentration and Exposure Assessment for the Burro Canyon Aquifer

The distributions of simulated peak cumulative dose for the deeper Burro Canyon aquifer for the ET cover and the composite cover are shown in Figure 18. The simulated doses for the ET cover are somewhat smaller than those for the composite cover for future conditions (all simulated doses with the composite cover for present conditions are zero). This result is unexpected, given the generally higher percolation flux through the mill tailings with the ET cover than with the composite cover for future conditions. It should be noted, however, that magnitudes of the simulated doses in the deeper Burro Canyon aquifer are very small and essentially equivalent to zero.

Figure 18. Cumulative probability distribution of peak cumulative dose for Ra-226 and its progeny in the Burro Canyon aquifer for present and future conditions (scenario 8) and for the evapotranspiration cover.

4.5.5 Removal of the Liner Beneath the Mill Tailings

Another alternative design was considered that consisted of the ET cover without the double composite-liner system beneath the mill tailings (see Section 4.3.4). In FRAMES, the “vadose-zone” model representing the double composite-liner system was simply removed from the model. Results of stochastic simulations for the present-day, shallow-aquifer scenario show that the peak groundwater concentrations are the same with and without the liner Figure 19. A likely explanation is that the simulated percolation flux through the waste during present-day conditions was less than the effective hydraulic conductivity of the liner system; therefore, the liner did not inhibit the simulated flux. However, for future-climate conditions, or during adverse conditions such as snowmelt or rapid water percolation through animal burrows (which were not modeled), the amount of percolation would exceed the effective hydraulic conductivity of the liner, and the liner would provide an additional barrier to contaminant transport to the aquifer. Hypothetically, if the percolation flux through the waste and the effective hydraulic conductivity of the liner were well characterized, then results such as those shown in Figure 19 would indicate that a great deal of cost savings may be achieved by omitting the bottom liner since the performance would not be impacted by the omission of this design feature.

Figure 19. Peak Ra-226 concentration in the shallow aquifer during present-day conditions using the evapotranspiration cover with and without a double composite-liner system beneath the mill tailings.

4.6 Sensitivity Analyses

A sensitivity analysis of the probabilistic assessment results can provide valuable information regarding which components of the landfill cover system and which parameters are most important to the simulated performance metric(s). This information provides understanding about the relationship between uncertainty in individual input parameters and the uncertainty in the performance of the system. In addition, knowledge of the parameters having the greatest influence on future performance can be used to help prioritize site characterization activities, to help optimize landfill cover design, and to assist in the design of monitoring systems.. Using a sensitivity analysis provides the quantitative information necessary to ensure that resources are directed to those aspects of the cover system that “drive” performance and not on those aspects of cover design that have little significance.

A variety of methods are available for sensitivity analysis of this type. One simple method is to examine discrete cases in which a single uncertain parameter is varied to its extreme values (e.g., 5th and 95th percentiles) while the remaining uncertain parameters are held constant at their expected values. This method may be very useful in developing understanding of the system and/or model, but requires that specific model runs be conducted for each discrete case. Alternatively, the sensitivity of the performance-assessment model can be determined in a global sense from the Monte Carlo probabilistic realizations using regression analysis. Multiple regression analysis involves construction of a linear regression model of the output with all of the independent variables using a least squares procedure. Stepwise linear regression is a modified version of multiple regression that selectively adds input parameters to the regression model in successive steps (Helton and Davis, 2000). In this method, a sequence of regression models is constructed in which the first model contains the most important independent variable; the second model contains the two most important variables, etc. Additional information on the stepwise linear regression method is provided in Appendix C of this report.

Parameter sensitivity in sampling-based probabilistic modeling is a function of both the physical relationship of that parameter within the mathematical model and the amount of uncertainty in that parameter. In some cases, an input parameter is highly important to the model output because it has a direct or disproportionately great impact on the physical processes being simulated. In other cases, an input parameter with moderate physical significance to the model output may be highly important because of a relatively high degree of uncertainty in that parameter.

Sensitivity analyses quantify the relative contribution of uncertainty in individual parameter values to uncertainty in the adopted performance measure; there are, however, some limitations. A sensitivity analysis compares the relative contribution of *uncertainty in individual parameter values* to uncertainty in the performance measure. A sensitivity analysis cannot identify the importance of those parameters that are modeled as fixed values. Also, a sensitivity analysis cannot assess the importance of processes that are not modeled. For example, potential degradation of the cap by deep-rooted juniper trees will not be identified as being important if this process of root intrusion is not included in the model of the system.

4.6.1 Percolation through the Cover

Sensitivity analysis of simulated percolation through the cover using the stepwise regression method with rank-transformed input and output variables is summarized in Table 15. The most important parameters to uncertainty in percolation for both present and future conditions are placement quality of the geomembrane liner (see Schroeder et al., 1994a,b), the saturated hydraulic conductivity of the topsoil layer, and the wilting point of the clay layer. For future climatic conditions, the uncertainty in precipitation and temperature contribute to uncertainty in the percolation to a significant, but lesser extent.

Uncertainty in the placement quality of the geomembrane is the most important factor with regard to percolation in the HELP model, accounting for about 44% of the variability in simulated percolation, based on the ΔR^2 value in the stepwise regression (see Table 15). This is understandable, given the key role the geomembrane liner plays in preventing downward percolation and in the lateral diversion of infiltration in the overlying drainage layer. It should be noted that a broad, uniform uncertainty distribution was assigned to the placement quality, given the lack of site-specific information on this parameter.

Table 15. Summary of parameters important to simulated water percolation through the cover based on stepwise linear-regression analysis (composite cover).

Step	Variable	R^2	ΔR^2
Present Climate			
1	placement quality	0.4382	0.4382
2	Ksat-layer 1	0.6132	0.1750
3	wilting point – layer 4	0.6600	0.0468
4	wilting point – layer 2	0.6733	0.0133
5	evaporative zone depth	0.6824	0.0091
Future Climate			
1	placement quality	0.4513	0.4513
2	Ksat – layer 1	0.6096	0.1583
3	wilting point – layer 4	0.7213	0.1117
4	precipitation multiplier	0.7869	0.0656
5	temperature adjustment	0.7957	0.0088
6	maximum leaf-area index	0.8044	0.0087

A similar sensitivity analysis for percolation through the cover using stepwise regression was performed for the alternative ET cover design, with the results shown in Table 16. For the ET cover, there is poor correlation between the uncertain input parameters to the HELP model and the simulated average annual percolation flux. There is a significant, but small impact of uncertainty in the maximum leaf area index for present conditions. Evaporative zone depth is a somewhat more important parameter for future conditions and the precipitation multiplier has a small influence on uncertainty in percolation also for future conditions.

This lack of correlation between the parameters defining the characteristics of the ET cover and the uncertainty in percolation is an interesting observation and can be explained as follows. The HELP model includes a stochastic precipitation generator that results in significant variations in the simulated daily precipitation values. This stochastic precipitation simulator can result in significant variability in the average annual percolation through the ET cover system, even when averaged over the 100-year simulation time of the HELP runs. For the ET cover design, this variability apparently dominates over the variability in simulated percolation resulting from uncertainty in the other input parameters. For the composite cover design, the variability associated with stochastic fluctuations in the synthetic precipitation record tend to be damped by the cover system and the importance of the input parameters associated with the cover characteristics is greater.

Table 16. Summary of parameters important to simulated water percolation through the cover based on stepwise linear-regression analysis (ET Cover).

Step	Variable	R ²	ΔR ²
Present Climate			
1	maximum leaf-area index	0.0361	0.0361
Future Climate			
1	evaporative zone depth	0.1025	0.1025
2	precipitation multiplier	0.1419	0.0394

4.6.2 Radon Gas Flux at the Surface

Results of the stepwise regression of the rank-transformed input parameters and the radon flux at the surface of the landfill cover, as simulated by the radon diffusion model are summarized in Table 17. Note that variables are deemed to be statistically significant and included in the stepwise linear regression model only for a p-level of less than 0.05. The two most important parameters controlling the simulated radon flux in both the present-climate and future-climate models are the effective diffusion coefficients in the evapotranspiration layer (layer 1) and the clay diffusion-barrier layer (layer 4). These two parameters together account for about 60% and 87% of the variability in the simulated radon flux at the surface for present and future conditions, respectively. For present climatic conditions the diffusion coefficient in the mill tailings and the moisture content in the evapotranspiration layer are also significant parameters. For future climatic conditions the radon emanation rate from the mill tailings and the effective diffusion coefficient in the (degraded) geomembrane layer are also significant parameters in the model.

It is understandable that the diffusion coefficients in layer 1 and layer 4 are the most important parameters in the analysis of radon gas transport, given the relatively greater thickness of layer 1 and the diffusion-barrier nature of layer 4. It is interesting to note that the uncertainty in the diffusion coefficient in layer 1 is of greater importance than the diffusion coefficient in the

diffusion barrier of layer 4 under present conditions and is of almost equal importance for future conditions.

Table 17. Summary of parameters important to simulated radon flux through the cover based on stepwise linear-regression analysis (composite cover).

Step	Variable	R ²	ΔR ²
Present Climate			
1	Diffusion Coefficient – layer 1	0.3879	0.3879
2	Diffusion Coefficient – layer 4	0.5989	0.2110
3	Diffusion Coefficient – layer 5	0.6986	0.0997
4	Moisture Content – layer 1	0.7166	0.0180
Future Climate			
1	Diffusion Coefficient – layer 4	0.4571	0.4571
2	Diffusion Coefficient – layer 1	0.8728	0.4156
3	Radon Emanation Rate	0.8931	0.0203
4	Diffusion Coefficient – layer 3	0.8994	0.0063

A similar sensitivity analysis using stepwise regression was performed for the alternative ET cover design, with the results shown in Table 18. For the ET cover, the uncertainty in simulated radon flux is strongly dominated by uncertainty in the diffusion coefficient in the evapotranspiration layer (layer 1), accounting for about 76% and 95% of the variability in radon flux under present and future conditions, respectively. Moisture content in layer 1 and the radon emanation rate from the mill tailings play a significant, but relatively minor role in the output of the radon diffusion model. This result is expected, given the simplified nature of the ET cover design in which layer 1 is the only layer in the system.

Table 18. Summary of parameters important to simulated radon flux through the cover based on stepwise linear-regression analysis (ET Cover).

Step	Variable	R ²	ΔR ²
Present Climate			
1	Diffusion Coefficient – layer 1	0.7629	0.7629
2	Moisture Content – layer 1	0.7940	0.0311
3	Radon Emanation Rate	0.8002	0.0062
Future Climate			

Step	Variable	R ²	ΔR ²
1	Diffusion Coefficient – layer 1	0.9485	0.9485
2	Moisture Content – layer 1	0.9765	0.0280
3	Radon Emanation Rate	0.9773	0.0008

4.6.3 Groundwater Dose from the Shallow Aquifer

A stepwise linear regression was performed between the rank-transformed input parameters and the simulated dose from the FRAMES model of Ra-226 transport from the Monticello mill tailing repository. The stepwise regression analysis was conducted for simulation results in the shallow aquifer for present and future climatic conditions and in the deep aquifer for future climatic conditions. Results of the stepwise regression for the shallow aquifer are summarized in Table 19. Note that variables are deemed to be statistically significant and included in the stepwise linear regression model only for a p-level of less than 0.05.

Analyses of cumulative groundwater dose and peak groundwater concentration were conducted with the FRAMES model. Examination of the results for these two performance metrics indicates that they are very highly correlated, on a realization-by-realization basis. This indicates that sensitivity analysis on these two performance metrics will yield very similar results. Consequently, only sensitivity analyses for groundwater dose are presented here; conclusions regarding sensitivity to peak groundwater concentration are expected to be very similar.

Several of the stochastic input parameters used in the model are directly correlated (as equal or scaled values) and consequently cannot be distinguished in the regression analysis. For example, the travel distance to the well is directly proportional to the longitudinal dispersivity, transverse dispersivity, and the length of the waste zone. So where “travel distance to well” appears as the variable in Table 19, the variable of significance to the results may be travel distance to the well or any of the directly correlated parameters.

The results shown in Table 19 indicate that the uncertainty in simulated dose from the shallow aquifer for present climatic conditions is strongly dominated by uncertainty in the sorption coefficient for radium in the vadose zone. Uncertainty in the radium K_d in the vadose zone accounts for approximately 92% of the variability in the simulated dose. Darcy percolation rate through the landfill cover, Darcy velocity in the shallow aquifer, and travel distance to the well are also significant, but much less important parameters, under present conditions.

This is an excellent example of the type of valuable information provided by a sensitivity analysis. Intuitively, variability in doses would be driven by variability in the water flux through the waste because water dissolves the radium, water carries the radium to the receptor, and the water flux varies over one and two orders of magnitude. However, the sensitivity analysis demonstrates that approximately 92% of the variability in the dose is associated with variability in the sorption coefficient of radium and only 2% of the variability is driven by variability in the water flux.

For future conditions, the simulated dose in the shallow aquifer is still primarily a function of uncertainty in the radium K_d in the vadose zone, but the Darcy percolation flux through the landfill cover is also an important uncertainty in the behavior of the system. Travel distance to the well and saturated hydraulic conductivity of the landfill liner are also significant parameters, under future conditions. For exactly the same disposal system, subjected to a wetter climatic, the uncertainty in the radium sorption coefficient is now less important (56 %) and the variability in the water flux has a much greater influence (27%) on the variability in the dose. Sensitivity analyses provides this insight.

The dominant importance of the sorption coefficient for radium in the vadose zone, with regard to simulated dose in the shallow aquifer, is understandable because of the potential retardation caused by the sorption process in relation to the half-life of Ra-226 of 1600 years. The greater importance of the Darcy percolation rate through the cover under future conditions, relative to present conditions, is due to the generally higher percolation flux under future climatic conditions.

Table 19. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (composite cover, Shallow Aquifer)

Step	Variable	R ²	ΔR ²
Present Climate, Shallow Aquifer			
1	Radium Sorption Coefficient – Vadose Zone	0.9259	0.9259
2	Darcy Percolation Rate	0.9435	0.0175
3	Darcy Velocity – Shallow Aquifer	0.9489	0.0054
4	Travel Distance to Well	0.9540	0.0051
Future Climate, Shallow Aquifer			
1	Radium Sorption Coefficient – Vadose Zone	0.5624	0.5624
2	Darcy Percolation Rate	0.8278	0.2654
3	Travel Distance to Well	0.8342	0.0064
4	Saturated Hydraulic Conductivity – Landfill Liner	0.8440	0.0098

A similar sensitivity analysis of simulated dose using stepwise regression was performed for the alternative ET cover design, with the results shown in Table 20. The results of the sensitivity analysis for the ET cover are similar to the results for the composite cover design, with uncertainty in the simulated dose being dominated by uncertainty in the radium K_d in the vadose zone. The relative importance of the Darcy percolation rate through the landfill cover is greater for the ET cover than for the composite cover design, under both present and future conditions. This result is consistent with the generally greater magnitude of percolation flux for the ET cover, relative to the composite cover design.

Table 20. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (ET cover, Shallow Aquifer).

Step	Variable	R ²	ΔR ²
Present Climate, Shallow Aquifer			
1	Radium Sorption Coefficient – Vadose Zone	0.8939	0.8939
2	Darcy Percolation Rate	0.9605	0.0666
3	Darcy Velocity – Shallow Aquifer	0.9629	0.0024
4	Travel Distance to Well	0.9638	0.0009
Future Climate, Shallow Aquifer			
1	Radium Sorption Coefficient – Vadose Zone	0.4351	0.4351
2	Darcy Percolation Rate	0.7325	0.2974
3	Saturated Hydraulic Conductivity – Landfill Liner	0.7845	0.0520
4	Darcy Velocity – Shallow Aquifer	0.7900	0.0055
5	Total Porosity – Shallow Aquifer	0.7949	0.0049

4.6.4 Groundwater Dose from the Burro Canyon Aquifer

Sensitivity analysis of the groundwater dose from the deeper Burro Canyon aquifer using stepwise regression was also performed. All of the realizations of the FRAMES model for groundwater dose from the deeper aquifer resulted in values of zero. Consequently, no sensitivity analysis for present conditions was possible. The analysis of the deep aquifer for future climate is limited by the fact that a large number of realizations (44 %) result in a zero value of simulated dose. It should also be noted that the values of simulated dose for the Burro Canyon aquifer are very small (see Figure 18).

The results of the sensitivity analysis for the Burro Canyon aquifer are given in Table 21. The uncertainty in the simulated dose from the deep aquifer for future climatic conditions is primarily a function of the uncertainty in the travel distance to the well (and/or uncertainty in dispersivity and length of the waste zone) and the Darcy velocity in the deep aquifer. Together, uncertainty in these two parameters account for about 59% of the variability in the simulated groundwater dose. The importance of the distance to the well and the Darcy velocity in the deep aquifer is due to the direct impact these parameters have on the transport time of Ra-226 and its progeny to

the receptor. Darcy percolation rate through the landfill cover and the width of the waste zone are also significant parameters with regard to simulated dose.

Table 21. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (composite cover, Burro Canyon Aquifer).

Step	Variable	R ²	ΔR ²
Future Climate, Deep Aquifer			
1	Travel Distance to Well	0.3373	0.3373
2	Darcy Velocity – Deep Aquifer	0.5859	0.2486
3	Darcy Percolation Rate	0.6526	0.0667
4	Width of Waste Zone	0.6761	0.0235

A similar sensitivity analysis of simulated dose using stepwise regression was performed for the alternative ET cover design, with the results shown in Table 22. The results of the sensitivity analysis for the ET cover are similar to the results for the nominal cover design, with uncertainty in the simulated dose being dominated by uncertainty in the travel distance to the well and the Darcy velocity in the deep aquifer, under both present and future conditions. Other significant, but minor input parameters are width of the waste zone, total porosity in the deep aquifer, radium K_d in the landfill liner, and saturated hydraulic conductivity of the landfill liner.

Table 22. Summary of parameters important to simulated cumulative dose based on stepwise linear-regression analysis (ET cover, Burro Canyon Aquifer).

Step	Variable	R ²	ΔR ²
Present Climate, Deep Aquifer			
1	Travel Distance to Well	0.3920	0.3920
2	Darcy Velocity – Deep Aquifer	0.6897	0.2977
3	Width of Waste Zone	0.7221	0.0324
4	Total Porosity – Deep Aquifer	0.7310	0.0089
5	Radium Sorption Coefficient – Landfill Liner	0.7376	0.0066
Future Climate, Deep Aquifer			
1	Travel Distance to Well	0.4360	0.4360
2	Darcy Velocity – Deep Aquifer	0.6838	0.2478
3	Width of Waste Zone	0.7118	0.0280
4	Total Porosity – Deep Aquifer	0.7266	0.0148

Step	Variable	R ²	ΔR ²
5	Saturated Hydraulic Conductivity – Landfill Liner	0.7359	0.0093

4.6.5 Hypothetical Example and Application of Sensitivity Analyses

All of the simulated doses to the receptor meet the performance objective. However, as a hypothetical example, assume that 15% of the realizations of dose to the receptor under the shallow-aquifer, current-climate scenario were above the performance objective. Further assume that it is determined to be unacceptable to have 15% of the possible doses above the performance objective. This alone does not mean that disposal system performance is unacceptable. The analyst could reexamine the treatment of uncertainty to determine if there is a *defensible* means of reduce the uncertainty and the doses. The sources of uncertainty include: numerical model uncertainty, conceptual model uncertainty, uncertainty in the future state of the system, and input parameter uncertainty. For this simple example, assume that numerical model uncertainty, conceptual model uncertainty, and uncertainty in the future state of the system have been properly addressed, and uncertainty in the input parameters still exists.

Input parameter uncertainty may exist because of a lack of knowledge, or because of natural variability or because of both. Input parameter uncertainty is quantitatively addressed in this analysis, using a range of equally likely parameter values and Monte Carlo simulations. For the shallow aquifer, current climate scenario, 16 parameters are uncertain because of a lack of knowledge, or natural variability or both. Uncertainty is inherent in real systems, assessed over long time frames, and this uncertainty should be truthfully carried into the analysis.

Utilizing the sensitivity analysis, variability in the K_d for radium accounts for 92% of the variability in the dose to the receptor. Based on current knowledge, the variability in the radium K_d could be as low as 50 ml/g and it could be as high as 200 ml/g. Knowing the importance of the radium sorption coefficient, the analyst could then ask several qualitative questions. First, what is the likelihood that laboratory studies or other analysis would *defensibly* narrow or shift the range in the sorption values? Second, what is the cost of these additional studies? If it is believed that the range of K_d values can be defensibly narrow or shifted to the higher values, at a reasonable cost, then field or laboratory studies of radium K_d values are justified.

Based on the insight provided by a sensitivity analysis, the analyst can select the best option for future activities. Importantly, designing a better cap that further reduces the water flux to the waste is probably not the best option for reducing the dose to the receptor, as variability in the flux of water through the cap only accounts for 2% of the variability of the dose.

5. Summary and Conclusions

This report has presented a method for conducting probabilistic performance-assessment analyses for long-term cover systems. The systematic approach consists of five basic steps:

1. Develop and screen scenarios based on regulatory requirements (performance objectives) and relevant features, events, and processes
2. Develop models of relevant features, events, and processes
3. Develop values and/or uncertainty distributions for input parameters
4. Perform calculations and sensitivity/uncertainty analyses
5. Document results and provide feedback to previous steps and associated areas to improve calculations as needed

This method was illustrated with a performance assessment of the uranium mill-tailings repository at Monticello, Utah. A number of scenarios were considered in the assessment that evaluated several key performance metrics: (1) water percolation through the cover; (2) radon gas transport through the cover; (3) concentration of radium-226 in the groundwater; and (4) human exposure to radium-226. A summary of the scenarios considered and their respective performance objectives are summarized in Table 3. Representative features, events, and processes (FEPs) were identified for each scenario, but not all FEPs (e.g., human intrusion) were considered in this assessment.

The software FRAMES was used to integrate various components into a total-system model. FRAMES employs a drag-and-drop icon-based architecture that allows models of different processes and different media to be linked to one another. Component models that were used in FRAMES included several MEPAS modules: source-term model, vadose-zone transport model, saturated-zone transport model, and human-exposure models. In addition, a radon-gas transport code, RAECOM, was integrated into FRAMES as part of this study. The code HELP was used independently of FRAMES to determine the amount of water that could percolate through the cover to the waste, but we have recently integrated HELP with FRAMES (see Appendix A). In each model, and in the total-system model, uncertainty analyses were performed using distributions of stochastic parameters that were determined to have a large range and/or a significant impact on the simulated performance metric. Values and ranges for input parameter distributions were obtained using existing data, literature, and professional judgment.

Monte Carlo simulations were performed to obtain a distribution of results that could be compared to the desired performance objective for each scenario. Present and future climatic conditions were considered independently in the scenarios. For future conditions, additional uncertainty was added to parameters such as precipitation and geomembrane degradation in the cover. In nearly all the simulations, the simulated results were well below the desired performance objectives for both present and future conditions.

The model of water percolation through the base-case composite cover resulted in just a few realizations (all during future climatic conditions) that produced percolation fluxes exceeding 10^{-7} cm/s. A curve fit was applied to the results to create a log-normal distribution of percolation fluxes that was used in the source-term model in FRAMES. In addition, a stepwise linear regression revealed that the most important parameters for water percolation through the cover were geomembrane placement quality, hydraulic conductivity of the topsoil layer, and wilting point of the clay layer. Evaluation of an alternative evapotranspiration (ET) cover design

revealed that the inclusion of just the topsoil layer was sufficient to produce simulated percolation fluxes that were generally below the performance metric. The uncertainty in the results of the ET cover were significantly less than the composite cover, and sensitivity studies showed little correlation between the simulated percolation and stochastic input parameters for the ET cover.

The radon-gas transport analysis revealed that nearly all of the realizations yielded surface Ra-222 fluxes that were below the regulatory limit of 20 pCi/m²-s. Sensitivity analyses revealed that important parameters in this model were the effective diffusion coefficient and moisture content in the different layers of the cover. The moisture content was found to have an interesting impact on the diffusive flux of radon gas from the mill tailings to the surface of the cover. An increase in moisture content decreased the effective diffusion coefficient due to the reduced area for diffusion. However, an increased moisture content also increased the concentration gradient through the cover by reducing the available pore space for radon gas to occupy. In addition, simulation of radon-gas transport through an alternative ET cover design resulted in nearly 80% of the realizations in which the Ra-222 gas fluxes exceeded the regulatory metric. Although the ET cover design was simulated to provide adequate performance relative to water percolation through the cover, the ET cover failed to provide adequate performance relative to the simulated radon-gas-flux metric in the model. This illustrates that while some alternative designs may be cheaper to construct and implement, they should be compared against all relevant performance metrics to ensure (with a sufficient degree of confidence) that they will not exceed the regulatory metrics.

Transport of radium-226 from the mill tailings to two different aquifers was also evaluated under present and future conditions. Transport to both a shallow alluvial aquifer and a deeper regional (Burro Canyon) aquifer was simulated independently. Groundwater concentrations and dose to a human were used as the performance metrics in these simulations. In all simulations, the simulated groundwater concentration and dose were less than the desired performance objectives (5 pCi/L and 100 mrem/yr). The sensitivity of dose and radium concentrations to variability in the uncertain input parameters, for a number of scenarios, was summarized in Sections 4.6.3 and 4.6.4. For all of the shallow groundwater scenarios, variability in the sorption coefficient for radium drove the variability in the dose and radium concentration metrics. Counter to intuition, variability in water percolation to the waste was not the most critical component of system performance for the modeled system. For the deep groundwater scenarios, where travel time became a dominant consideration, variability in the dose and radium concentration metrics was driven by the distance to the receptor well and the Darcy velocity in the deep aquifer. Insights provided by these sensitivity analyses could be used to optimize cover design or to identify key parameters for future site monitoring.

Overall the results of this performance assessment illustrated how probabilistic analyses could be used to evaluate long-term performance of covers against regulatory metrics. The performance metrics can be risk-based, such as groundwater concentration or dose, or they can be prescriptive metrics such as conductivity for a particular layer of the cover. In both cases, probabilistic performance assessments can provide uncertainty and sensitivity analyses that identify the parameters that are most important to long-term performance. These parameters may be important for engineering design, environmental studies, and long-term monitoring efforts to assist in prioritizing their efforts. In addition, alternative designs for long-term covers can be

evaluated using risk-based performance metrics that are intended to protect human health and the environment. These comparisons provide a more quantitative means to compare the performance of cover designs while factoring in additional issues such as cost and schedule.

Long-lived contaminants will remain in the Monticello landfill and many other closure sites being managed by DOE. To address the long-term management of these closure sites, the DOE has created a “stewardship” program. This DOE stewardship program encompasses the activities required to maintain an adequate level of protection of human health and the environment posed by wastes and residual contamination after cleanup is complete (DOE, 1999).

DOE’s commitment to provide long-term environmental stewardship may require DOE to consider performance objectives more stringent than those set by applicable regulations. As an example, a regulation may require that performance be assessed for 30 years, even when addressing long-lived contaminants. From a risk-based perspective, DOE is best served by considering features, events, and processes at the site that may contribute to the long-term risk of groundwater contamination and human exposure. Analysis of performance over long time periods provides the opportunity to examine the impacts of a range of geologic conditions on the ability of the engineered and natural barriers to limit releases to the biosphere. Therefore it may be in DOE’s best interest to consider the long-term performance of a closure system, even if the regulations only address the near-term performance.

6. References

Abraham, J.D. and W.J. Waugh, 1995, Cover drainage and leakage rate estimation using the help 3.1 code, Calc. No. E0267102, Rust Geotech Inc., Grand Junction, CO.

Buck, J. W., G. Whelan, J. G. Droppo, Jr., D. L. Streng, K. J. Castleton, J. P. McDonald, C. Sato, and G. P. Streile, 1995, Multimedia environmental pollutant assessment system (MEPAS): application guidance -- guidelines for evaluating MEPAS input parameters for version 3.1, PNL-10395, Pacific Northwest Laboratory, Richland, Washington.

Carsel, R.F. and R.S. Parrish, 1988, Developing joint probability distributions of soil water retention characteristics, Water Resources Research, vol. 24, no. 5, pp. 755-769.

Cranwell, R.M., R.V. Guzowski, J.E. Campbell, and N.R. Ortiz, 1982, Risk methodology for geologic disposal of radioactive waste: scenario selection procedure, NUREG/CR-1667 (SAND80-1429), U.S. Nuclear Regulatory Commission, Washington DC.

CRC (Chemical Rubber Company), 1990, Handbook of chemistry and physics, 71st ed., CRC Press, Boca Raton, FL.

Daniel B. Stephens and Associates, Inc., 1993, Laboratory analysis of soil hydraulic properties of Monticello remedial action project samples, Albuquerque, New Mexico.

DOE (U.S. Department of Energy), 1990, Final remedial investigation/feasibility study—environmental assessment for the Monticello, Utah, Uranium Mill Tailings Site, DOE/ID/12584-21, U.S. Department of Energy, Washington, D.C.

DOE, 1995, Monticello remedial action project operable unit i millsite remediation pre-final design, MR-E-95-04, Engineering Document Number E01425AD, U.S. Department of Energy, Washington, D.C.

DOE, 1996, Title 40 CFR 191 compliance certification application for the Waste Isolation Pilot Plant, 21 vols. DOE/CAO-1996-2184. U.S. Department of Energy, Carlsbad Area Office, Carlsbad, NM.

DOE, 1998, Viability assessment of a repository at Yucca Mountain. DOW/RW-0508. U.S. Department of Energy, Office of Civilian Radioactive Waste Management, Washington, D.C.

DOE/EM-0362, 1998, Accelerating Cleanup: paths to closure, June 1998.

DOE, 1999, From Cleanup to stewardship, Appendix D, DOE/EM-0466.

DOE Order 5400.5, 1993, Radiation Protection of the Public and the Environment.

DOE M 435.1-1, 1999, Radioactive waste management manual, p. IV-11, approved 7/9/99.

Dwyer, S. F., B. R. Reavis, and G. Newman, 2000, Alternative landfill cover demonstration, FY2000 annual data report, SAND2000-2427, Sandia National Laboratories, Albuquerque, New Mexico.

EPA (U.S. Environmental Protection Agency), 40 CFR 61, National Emissions standards for hazardous air pollutants.

EPA, 40 CFR 141, National primary drinking water regulations.

EPA, 40 CFR 192, Health and Environmental protection standards for uranium and thorium mill tailings.

EPA, 40 CFR 264, Standards for owners and operators of hazardous waste treatment, storage, and disposal facilities.

EPA, 1991, Seminar Publication: Design and Construction of RCRA./CERCLA Final Covers, EPA/625/4-91/025.

Fayer, M.J., 2000, UNSAT-H Version 3.0: Unsaturated Soil Water and Heat Flow Model - Theory, User Manual, and Examples," PNNL-13249, Pacific Northwest National Laboratory, Richland, WA.

Fleenor, W.E., and I.P. King, 1995, Identifying limitations on use of the help model, Landfill Closures - Environmental Protection and Land Resources, Geotechnical Special Publication No. 53, Dunn and Singh, eds., ASCE.

Freeze, R.A., and J.A. Cherry, 1979, *Groundwater*, Prentice-Hall Inc., Englewood Cliffs, N.J.

Helton, J.C. and F.J. Davis, 2000, *Sampling-Based Methods for Uncertainty and Sensitivity Analysis*, SAND99-2240, Sandia National Laboratories, Albuquerque, NM.

Ho, C.K. and S.W. Webb, 1998, Capillary Barrier performance in heterogeneous porous media, *Water Resources Research*, Vol. 34, No. 4, pp. 603-609.

Hsuan, Y.G. and R.M. Koerner, 1998, Antioxidant depletion lifetime in high density polyethylene geomembranes, *Journal of Geotechnical and Geoenvironmental Engineering*, vol. 124, no. 6, pp. 532-541.

Koerner, R.M., Y. Halse-Hsuan, and A.E. Lord, 1991, Long-term durability of geomembranes, *Civil Engineering*, April, 1991, pp. 56-58.

MACTEC, 2000, Monticello Mill Tailings Site Operable unit III, Interim remedial action progress report, Prepared for the DOE, Grand Junction Office, Machtech ER, Grand Junction Colorado, Q00197AA.

Meyer, P. D. and G. W. Gee, 1999, Information on hydrologic conceptual models, parameters, uncertainty analysis, and data sources for dose assessments at decommissioning sites, NUREG/CR-6656, U.S. Nuclear Regulatory Commission, Washington, D.C.

Meyer, P. D. and R. Y. Taira., 2001, Hydrologic uncertainty assessment for decommissioning sites: hypothetical test case applications, NUREG/CR-6695, U.S. Nuclear Regulatory Commission, Washington, D.C.

Morrison, S.J., V.S. Tripathi, and R.R. Spangler, 1995, Coupled reaction/transport modeling of a chemical barrier for controlling uranium(VI) contamination in groundwater, *Journal of Contaminant Hydrology*, vol. 17, pp. 347-363.

NRC (U.S. Nuclear Regulatory Commission), 1989, Calculation of Radon flux attenuation by earthen uranium mill tailings covers, Regulatory Guide 3.64, U.S. Nuclear Regulatory Commission, Washington, D.C.

Owenby, J. R. and D. S. Ezell, 1992, Monthly station normals of temperature, precipitation, and heating and cooling degree days 1961-90 Utah, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, Asheville, NC.

Pruess, K., 1991, TOUGH2—A general-purpose numerical simulator for multiphase fluid and heat flow, *LBL-29400*, Lawrence Berkeley Laboratory, Berkeley, CA.

Rogers, V.C., K.K. Nielson, and D.R. Kalkwarf, 1984, Radon attenuation handbook for uranium mill tailings cover design, NUREG/CR-3533, U.S. Nuclear Regulatory Commission, Washington, D.C.

Schroeder, P. R., Aziz, N. M., Lloyd, C. M. and Zappi, P. A., 1994a, The hydrologic evaluation of landfill performance (HELP) model: User's Guide for Version 3, EPA/600/R-94/168a,

September 1994, U.S. Environmental Protection Agency Office of Research and Development, Washington, DC.

Schroeder, P. R., Dozier, T.S., Zappi, P. A., McEnroe, B. M., Sjostrom, J. W., and Peyton, R. L., 1994b, The hydrologic evaluation of landfill performance (HELP) model: engineering documentation for version 3, EPA/600/R-94/168b, September 1994, U.S. Environmental Protection Agency Office of Research and Development, Washington, DC.

Smith, G., 2001, personal communication in e-mail dated 5/23/2001.

Streile, G.P., Shields K.D., Stroh J.L., Bagaasen L.M., Whelan G., McDonald J.P., Droppo J.G., and Buck J.W., 1996, The multimedia environmental pollutant assessment system (MEPAS): source-term release formulations. PNNL-11248, Pacific Northwest National Laboratory, Richland, WA..

Streng, D.L. and P.J. Chamberlin, 1995, Multimedia environmental pollutant assessment system (MEPAS): exposure pathway and human health impact assessment models. PNNL-10523, Pacific Northwest National Laboratory, Richland, WA..

Thibault, D.H., M.I. Sheppard, and P.A. Smith, 1990, A critical compilation and review of default soil solid/liquid partition coefficients, K_d , for use in environmental assessments, AECL-10125, Atomic Energy of Canada Limited Research Company.

van Genuchten, M. Th., F. J. Leij, and S. R. Yates, 1991, The RETC code for quantifying the hydraulic functions of unsaturated soils, Version 1.0. EPA Report 600/2-91/065, U.S. Salinity Laboratory, USDA, ARS, Riverside, California.

Waugh, W.J., 2001, personal communication in e-mail dated 2/20/2001.

Waugh, W. J. and K. L. Petersen, 1994, Paleoclimatic data application: long-term performance of uranium mill tailings repositories, in Proceedings of "Climate Change in the Four Corners and Adjacent Regions: Implications for Environmental Restoration and Land-Use Planning," CONF-9409325, Grand Junction, CO, September 12-14, 1994.

Whelan, G, J.W. Buck, D.L. Streng, J.G. Droppo, B.L. Hoopes, R.J. Aiken, 1992, Overview of the multimedia environmental-pollutant assessment system (MEPAS), Hazardous Waste & Hazardous Materials, 9(2), pp. 191-208.

Whelan G, McDonald JP, and Sato C., 1996, The multimedia environmental pollutant assessment system (MEPAS): groundwater pathway formulations. PNNL-10907, Pacific Northwest National Laboratory, Richland, WA.

Wyss, G.D. and K.H. Jorgensen, 1998, A user's guide to LHS: Sandia's Latin Hypercube Sampling Software, SAND98-0210, Sandia National Laboratories, Albuquerque, NM.

Appendix A: Development of Additional Modules for FRAMES

A.1. Integration of HELP with FRAMES

A.1.1. Introduction

The Hydrologic Evaluation of Landfill Performance (HELP) Model, which was developed by the Department of Defense's Waterways Experiment Station (WES), was used to provide infiltration estimates for a hypothetical cap at the Monticello Mill Tailings Repository. The model runs in a deterministic mode. In order to capture the effects of variations in input parameter values (i.e., landfill design parameter values), the model must be run multiple times. In each run, input parameter values are varied and the output results are stored and compiled with the results of other runs such that summary statistics (e.g., max, min, mean, standard deviation, etc...) can be computed.

In the Monte Carlo simulations for water percolation, one hundred realizations were simulated to develop summary statistics for the HELP output. Changing input values and running the model this many times is time consuming and increases the opportunities for errors in the input and in selecting outputs. The purpose of this task was to automate this procedure.

A.1.2. Method Used to Automate Stochastic HELP Modeling Runs

The method chosen to automate the stochastic HELP modeling runs was to integrate the model into the Framework for Risk Analysis in Multimedia Environmental Systems (FRAMES). FRAMES allows for a holistic approach to modeling in which models of different type (i.e., source, fate and transport, exposure, health impact), resolution (i.e., analytical, semi-analytical, and numerical), and operating platforms can be combined as part of the overall assessment of contaminant fate and transport in the environment. FRAMES includes sensitivity/uncertainty module that can be applied to any model that is integrated into the system. The sensitivity/uncertainty module is called the Sensitivity Uncertainty in Multimedia Modeling Module (SUM3) and it allows the modeler to run a model or a set of models in an entire modeling scenario in a stochastic mode. SUM3 uses the Latin Hypercube sampling technique and enables a user to select from a list of 4 statistical distributions. It also gives the user the ability to correlate variables or describe an equation relating two or more variables.

The process of integrating HELP into FRAMES was partially completed by WES for a separate project. This made the completion of the integration project much easier. Portions of the project completed by WES will be noted as each of the process steps is described. The process of incorporating HELP into FRAMES involved creating a description (DES) file; writing a processor that reads a HELP input file and writes to the FRAMES input file; writing a processor that reads a FRAMES input file and writes to HELP input files; and writing a processor that

reads the HELP output file, selects specific output results of interest, and writes them to a file. Each of these steps will be described briefly below:

1. Create a DES file – A DES file is a file that is required by the FRAMES system for every model. The file tells the system the name of the model, what type of model it is, what type of models it can connect to, the name and location of its executable, and other pertinent model information. The file also contains a list of the model input parameters that the model developer has listed as stochastic (i.e., the parameters available to be changed in a stochastic analysis). Along with stochastic parameter names, the parameters internal name, units, min and max range, and format are listed. The HELP model DES file was created by WES, however, it required modifications in order to get the model operating correctly in the system. The DES file name is 'HLP307S.DES' and it is listed below:

HELP Model DES file: HLP307S.DES

mf,Version 2.1

"Model:Source:Src","HELP 3.07 (source zone)","h307_uiS.bat","h307runS.bat"

"HELP 3.07 (source zone) Hydrologic Evaluation of Landfill Performance Module.

The HELP Module simulates hydrology for a confined disposal facility (CDF). HELP computes site specific hydraulics and hydrology.

Some Key Assumptions:

1. Equilibrium between solid and aqueous phases.
2. Dredged material will not change porosity.
3. Segment size is one-tenth of a soil layer.
4. The time step is one month.
5. A maximum of 20 layers of soil or geosynthetic material.

A more complete list of key assumptions and the associated discussion of them can be found in the following technical notes and documents.

Technical Notes:

Aziz, N. M., and Schroeder, P. R.(1998).
'Application of the HELPPQ module for ADDAMS:
Hydrologic Evaluation of leachate production and
quality in confined disposal facilities,'
Technical Note EEPD-xx-xx, U.S. Army Engineer
Waterways Experiment Station, Vicksburg, MS.

Aziz, N. M., and Schroeder, P. R.(1998).
'Documentation of the HELPPQ module for ADDAMS:
Hydrologic Evaluation of leachate production and

quality in confined disposal facilities,'
Technical Note EEPD-xx-xx, U.S. Army Engineer
Waterways Experiment Station, Vicksburg, MS.

Technical Document:

Schroeder, P. R., Dozier, T. S., Zappi, P. A.,
McEnroe, B. M., Sjostrom, J. W., and Peyton, R. L.
(1994). 'The Hydrologic Evaluation of Landfill
Performance (HELP) Model: Engineering Documentation
for Version 3,' EPA/600/R-94/168b, September 1994,
U.S. Environmental Protection Agency Office of
Research and Development, Washington, DC.

REQUIREMENTS

DOS.
IBM-compatible 8088, 80286, 80386, or 80486-based CPU
with an 8087, 80287, 80387 or 80486 math co-processor.
Monitor (preferably color EGA or better).
A 3.5- or 5.25-inch floppy disk drive.
A hard disk with 6 MB of available storage.
Minimum 400k bytes of available low level RAM.
A printer is needed if a hard copy is desired.

Point of Contact:

U.S. Army Engineer Waterways Experiment Station
Paul R. Schroeder
3909 Halls Ferry Rd
Vicksburg, MS 39180-6199

Phone: (601)-634-3709
EMail: schroep@ex1.wes.army.mil
URL Address: <http://www.wes.army.mil/el/elmodels/index.html>

1,Read
1,CON,,1,1,
5,Write
AFF,Air Emission Rates
WFF,Infiltration
WFF,Aquifer Flux
WFF,Runoff
SCF,
14,"Variables"
"HelpETLai","Continuous","n/a","Min",0,"Max",10,"Maximum Leaf Area Index",0,"%2.1f"

"HelpETevDepth","Continuous","in","Min",0.001,"Max",80.0,"Evaporative Zone
 Depth",0,"%4.1f"
 "HelpETWind","Continuous","mph","Min",0.0,"Max",100.0,"Wind Speed",0,"%5.1f"
 "HelpD10Moist","Continuous","in","Min",0.0,"Max",100.0,"Precipitation Moisture",0,"%4.0f"
 "HelpD10Snow","Continuous","in","Min",0.0,"Max",100.0,"Precipitation Snow",0,"%4.1f"
 "HelpD10Percent","Continuous","percent","Min",0.0,"Max",100.0,"Percent Area of Possible
 Runoff",0,"%5.1f"
 "HelpD10Slope","Continuous","percent","Min",1.0,"Max",50.0,"Slope",0,"%4.1f"
 "HelpD10Slength","Continuous","ft","Min",50.0,"Max",2000.0,"Slope Length",0,"%6.1f"
 "HelpD10Prop5","Continuous","n/a","Min",0.0,"Max",1.0,"Field Capacity",1,"%4.2f"
 "Label","Layer #",Index3
 "HelpD10Prop6","Continuous","n/a","Min",0.0,"Max",1.0,"Wilting Point",1,"%2f"
 "Label","Layer #",Index3
 "HelpD10Prop8","Continuous","cm/sec","Min",0.0,"Max",1.0,"Sat. Hyd. Conductivity",1
 "Label","Layer #",Index3
 "HelpD10Prop14","Continuous","#/acre","Min",0.0,"Max",1.0,"Geomembrane Pinhole Density",1,"%3f"
 "Label","Layer #",Index3
 "HelpD10Prop15","Continuous","#/acre","Min",0.0,"Max",1.0,"Geomembrane Instal. Defects",1,"%1f"
 "Label","Layer #",Index3
 "HelpD10Prop16","Continuous","n/a","Min",0.0,"Max",6.01,"Geomembrane Placement
 Quality",1,"%0f"
 "Label","Layer #",Index3

2. Writing a processor that reads a HELP input file and writes to the FRAMES input file – This step was completed by WES and is self explanatory. In order to work in FRAMES, it is necessary to read a model's input parameter values and write them to the FRAMES scenario input file. It is through this file that SUM3 substitutes input values for the model as part of a stochastic analysis.
3. Writing a processor that reads a FRAMES input file and writes to HELP input files - This step was completed by WES and is self-explanatory. In order to work in FRAMES, it is necessary to read a model's input parameter values from the FRAMES scenario input file and re-write them to the model's specific input files. SUM3 substitutes input values for the model through the FRAMES scenario input file, but substituted values must be transferred to the model's input file for the changes to affect the modeling runs.
4. Writing a processor that reads the HELP output file, selects specific output results of interest, and writes them to a file – This step was completed entirely through this task. The way that SUM3 works is that it prompts the user for the parameters to be varied in the stochastic assessment, it prompts the user for the parameters of the distribution for each parameter along with any correlation relationships and equations that will be used to vary the parameter values, and prompts the user for the number of iterations to run and to select the outputs to monitor. In the case of the HELP model, the outputs to monitor are predefined and no selections need to be made. SUM3 then creates a list of parameter values for each parameter selected by the user. For each iteration SUM3 copies input

parameter values from its list into the FRAMES scenario input file. As described previously, the input values are transferred to the model input file and then the model is run. After each run, an output file is generated. This file is searched for the output results of interest and those results are written to a separate results file. This process is repeated for each iteration up to the number specified by the user.

A.1.3. How To Use HELP Stochastically Within FRAMES

This section will provide a step by step description of how to run HELP within FRAMES. In order to follow these instructions, FRAMES and HELP and its associated files must be loaded onto the user's computer.

1. Start up the FRAMES system.
2. Use the 'File' menu in the upper left corner to select 'New'.
3. When prompted for a file name, enter any name you want to use. The name has to be 8 characters or less with no spaces though. For this case, enter the name 'SNL2.GID'.
4. When the 'Create New Site' window appears, click 'Ok'.
5. You will next add three icons from the list on the left to the work space window on the right. Add a 'Contaminant' icon, a 'Source' icon, and a 'Sensitivity' icon by double clicking on one of each. The icons should automatically be added to the window on the right.
6. You will next add the model connections. You will need to connect the 'Contaminant' icon to the 'Source' icon and the 'Source' icon to the 'Sensitivity' icon. To connect the 'Contaminant' icon to the 'Source' icon, hold the 'Shift' key down and click on the 'Contaminant' icon. Then drag a line from the 'Contaminant' icon to the 'Source' icon. A line should appear with an arrow pointing to the 'Source' icon. To connect the 'Source' icon to the 'Sensitivity' icon, hold the 'Shift' key down and click on the 'Source' icon. Then drag a line from the 'Source' icon to the 'Sensitivity' icon. A line should appear with an arrow pointing to the 'Sensitivity' icon.
7. Arrange the icons so they look like Figure A-1 below.
8. You will next pick a contaminant model. Right click on the 'Contaminant' icon and select 'General Info'. A window entitled 'Object General Information' should appear. In the window on the left, click on 'FRAMES Default Chemical Database Selection' to select the FRAMES default chemical database. Once it is selected, click on the 'Ok' button on the lower right corner of the window. The main FRAMES window should reappear.
9. You will next pick the constituent to be modeled. Right click on the 'Constituent' icon and select 'User Input'. A window entitled 'FRAMES Constituent Database Editor' should appear. The actual constituent selected does not matter in this case because HELP is being run to predict hydrologic and not contaminant transport. Select 'Benzene' from the list on the left and add it by double clicking on it. Benzene should appear in the list to the right. Use the File menu in the upper left corner to exit and save changes.

Figure A-1. Screen capture of FRAMES icon setup

10. You will next pick a source model. Right click on the 'Source' icon and select 'General Info'. A window entitled 'Object General Information' should appear. In the window on the left, click on 'HELP 3.07 (source zone)' to select the HELP model. Once it is selected, click on the 'Ok' button on the lower right corner of the window. The main FRAMES window should reappear.
11. You will next enter the input data to the HELP model. Right click on the 'Source' icon and select 'User Input'. A DOS window should appear. Press any key to get to the next screen. Repeat this to get through the disclaimer and preface screens. The main menu screen should then appear and will look like the screen capture in Figure A-2 below.

Figure A-2. Screen capture of HELP input data main menu

12. Use the arrow keys to get to 'Enter/Edit Weather Data' and press 'return'. The weather data entry window should appear. You will need to enter a data file for precipitation, temperature, solar radiation, and evapotranspiration. To add the precipitation data file, use the arrow keys to get to the precipitation row and hit the 'F4' key. Highlight the 'Data4' file and hit 'return'. The 'Data4' file that contains the precipitation data for the run has now been added. Repeat this process to add the temperature (Data7), solar

radiation (Data13), and evapotranspiration (Data11) files. Then hit the 'Page Down' key.

13. The data entered can be viewed in the following screens. To exit the Weather data section, hit the 'F10' key. Hit the 'F10' key again to exit. You will be asked whether or not you would like to overwrite the data files with the current data. No changes have been made so select 'yes' for all four files.
14. The main menu will then reappear. Use the arrow keys to get to 'Enter/Edit Soil and Design Data' and press 'return'. The soil and design data window should appear. You will again need to add a file. Hit the 'F4' key, highlight the 'Data10' file and hit 'return'. The 'Data10' file that contains the soil and design data for the run has now been added. You can hit the 'page down' button to page through the input values entered. When you are done, hit the 'F10' key to exit. When the next window appears, select 'Save Soil and Design Data'. Hit 'F10' again to exit. You will be asked whether or not you would like to overwrite the data file with the current data. No changes have been made so select 'yes'.
15. Use the arrow keys to select 'Quit'. The DOS window should disappear and a new window entitled 'HELP Model Post-Processing UI' should appear. It will look like the screen capture below if Figure A-3. Click on the 'Ok' button on the bottom of the screen. The window should disappear and the main FRAMES screen should reappear.
16. You will next run the HELP model. Right click on the 'Source' icon and select 'Run Model'. The model should then run. A green light will appear on the 'Source' icon to indicate that the model was run successfully.

Figure A-3. Screen capture of HELP post-processing UI

17. You will next pick a sensitivity/uncertainty model. Right click on the 'Sensitivity' icon and select 'General Info'. A window entitled 'Object General Information' should appear. In the window on the left, click on 'MEPAS Sensitivity/Uncertainty' to select the SUM3 model. Once it is selected, click on the 'Ok' button on the lower right corner of the window. The main FRAMES window should reappear.
18. You will next enter the input data to the SUM3 model. Right click on the 'Sensitivity' icon and select 'User Input'. The user interface for SUM3 should appear.
19. You will next select the parameters that will be varied stochastically in the assessment. Each parameter to be varied is required to have an alias, which is an abbreviated name for the parameter. The alias name must be 8 characters or less and contain no spaces.
20. Scroll through the list and find the variable description 'Maximum Leaf Area Index from HELP (src2)'. Click on it and the cursor will appear in the 'Alias' window near the top of the tab. Type in 'maxleaf' and click the 'Add' button. The alias should be added to the window below.
21. Next you will repeat the process by finding the variable descriptions listed in Table A-1. and adding the associated alias also listed in the table.

22. After all parameters have been selected and given aliases, click on the check box in the lower left of the screen. When this box is checked, only the aliased variables will be listed. The screen should now look like the screen capture in Figure A-4.

Table A-1. Stochastic Parameters and Aliases

Variable Description	Alias
Maximum Leaf Area Index from HELP (src2)	maxleaf
Evaporative Zone Depth from HELP (src2)	EvDepth
Field Capacity, Layer #1 from HELP (src2)	FCap1
Wilting Point, Layer #1 from HELP (src2)	Wilt1
Sat. Hyd. Conductivity, Layer #1 from HELP (src2)	Sat1
Sat. Hyd. Conductivity, Layer #2 from HELP (src2)	Sat2
Sat. Hyd. Conductivity, Layer #4 from HELP (src2)	Sat4
Geomembrane Pinhole Density, Layer #3 from HELP (src2)	PinDen3
Geomembrane Placement Quality, Layer #3 from HELP (src2)	PlaceQ3

Figure A-4. Screen capture of SUM3 UI – Variable Selection

23. You will next enter the parameter information. Click on the 'Parameters' tab near the top of the screen. The user interface will now display the 'Parameters' tab. A screen capture of this screen is shown in Figure A-5. Note that all aliased parameters are listed on the left of the screen.

24. You will next add the distribution information associated with each of the parameters. Select ‘maxleaf’ by clicking on it in the list. Go to the ‘Distribution’ tab to the right to select a distribution type. Currently only four types are available and they are normal, log-normal, uniform, and log-uniform. In order to simulate other distribution types, the equation editor must be used. A description of its use will not be included here.
25. For the parameter ‘maxleaf’ select the ‘uniform’ distribution type. For the upper bound type in ‘8.0’ and for the lower bound type in ‘2.0’.

Figure A-5. Screen capture of SUM3 UI – Parameter tab

26. Repeat this process for the other parameters. Use the contents of Table A-2 to obtain distribution type and distribution information for each of the parameters.

Table A-2. Parameter Distribution Information

Parameter Alias	Distribution Type	Max	Min	Mean	Standard Deviation
maxleaf	uniform	8.0	2.0	N/A	N/A
EvDepth	uniform	35.0	25.0	N/A	N/A
FCap1	normal	0.4	0.3	0.36	0.05
Wilt1	uniform	0.2	0.01	N/A	N/A
Sat1	normal	3.0	0.01	1.0	0.05
Sat2	normal	0.03	0.001	0.01	0.005

Parameter Alias	Distribution Type	Max	Min	Mean	Standard Deviation
Sat4	normal	1.0E-6	1.0E-8	1.0E-7	2.0E-8
PinDen3	uniform	2.0	0.5	N/A	N/A
PlaceQ3	uniform	5.0	1.0	N/A	N/A

27. After all of the parameter information has been entered, click on the 'Outputs' tab. On this tab, type in a random seed value of 1 and for 'Number of iterations' type in '10'. This is the tab where a user would normally specify the output parameters of interest but as previously stated, the HELP output parameters of interest have previously been selected so no choices need to be made here.
28. Use the 'File' menu in the upper left corner to save and exit the SUM3 user interface.
29. The HELP model is now ready to be run in a stochastic mode. Right click on the 'Sensitivity' icon and select 'Run Model'. The HELP model should be fired off ten times. A green light on the 'Sensitivity icon will indicate that all ten runs were completed successfully.

A.1.4. How To Evaluate Results

This section will provide a step-by-step description of how to evaluate the HELP outputs from the stochastic modeling runs. In order to follow these instructions, M.S. Excel or some other spreadsheet program that can import comma separated files must be loaded onto the user's computer.

The output from the sensitivity/uncertainty runs will be written to two separate files. Both files are written in a comma-separated format so they can easily be imported into a spreadsheet program for viewing and analysis. The first file is the standard FRAMES SUM3 output file, which is always labeled with the input file name and has the file extension '.SUF'. The '.SUF' extension names stands for Sensitivity Uncertainty File. In this case, the file name is 'SNL2.SUF'. The second file is a special file designed to report selected HELP output values. The name for this file will be the name of the output file specified by the user through the HELP model user interface appended with a '.SUF' at the end. In this case, the file name is 'SNL2.OUT.SUF'.

The following are the steps to follow to evaluate the results from the stochastic HELP run:

1. Start up M.S. Excel or another spreadsheet program.
2. Click on the file menu and select 'Open'.
3. Locate the file 'SNL2.SUF' on your computer and click on the 'Open' button. It will be located in the same folder as your FRAMES input file (i.e., SNL2.GID) unless you have specified otherwise.
4. The Text Import Wizard screen will appear. For the original data type, select 'Delimited'. Then click on the 'Next' button. For the 'Delimiters' check the 'Comma' box and uncheck the 'Tab' box. Then click on the 'Finish' button. The file should come up in a readable format. It will look like Figure A-6.

5. This file lists the input parameters that were varied in the modeling runs along with the values used in each specific run. As can be seen, the upper part of the file lists the aliases and parameter descriptions. The lower part lists data used in each realization. The parameter values used in each iteration are listed by row. In this case, ten iterations were run so there are ten rows.
6. To view the output results of each iteration, a second file must be opened.
7. Click on the file menu and select 'Open'.
8. Locate the file 'SNL2.OUT.SUF' on your computer and click on the 'Open' button. It will be located in the same folder as your FRAMES input file (i.e., SNL2.GID) unless you have specified otherwise.
9. The Text Import Wizard screen will appear. For the original data type, select 'Delimited'. Then click on the 'Next' button. For the 'Delimiters' check the 'Comma' box and uncheck the 'Tab' box. Then click on the 'Finish' button. The file should come up in a readable format. It will look like Figure A-7. The file is very large (47 columns) so only a portion of it is actually shown in the figure.
10. This file lists the selected outputs of each modeling run. The format is similar to the 'SNL2.GID' file in that the results for each iteration are listed in a single row. In this case, ten iterations were run so there are ten rows.
11. The easiest way to evaluate the results is to keep the inputs and outputs of each iteration in the same row in the same spreadsheet. The data for each iteration is listed by rows in both files so this makes integrating the results from both files very easy. To do this just take the data from either one of the files, paste it into the other file, and adjust the rows so that they line up correctly. An example of this is shown in Figure A-8. Again only a portion of the file is shown because the file size is very large.

sen5	25								
2									
Sensitivity/Uncertainty Module for FRAMES									
Beta Test version									
9	0								
maxleaf	Maximum Leaf Area Index from src2								
EvDepth	Evaporative Zone Depth from src2								
FCap1	Field Capacity, Layer # 1 from src2								
wilt1	Wilting Point, Layer # 1 from src2								
Sat1	Sat. Hyd. Conductivity, Layer # 1 from src2								
Sat2	Sat. Hyd. Conductivity, Layer # 2 from src2								
Sat4	Sat. Hyd. Conductivity, Layer # 4 from src2								
PinDen3	Geomembrane Pinhole Density, Layer # 3 from src2								
PlaceQ3	Geomembrane Placement Quality, Layer # 3 from src2								
10									
realizations	maxleaf	EvDepth	FCap1	wilt1	Sat1	Sat2	Sat4	PinDen3	PlaceQ3
1	2.2	27.3	0.32	0.14	1.02E+00	1.31E-02	8.42E-08	1.648	2
2	3.7	31.6	0.39	0.11	9.44E-01	9.77E-03	1.02E-07	1.793	4
3	7	29.7	0.37	0.14	9.01E-01	8.88E-03	7.30E-08	1.344	3
4	4.4	34.4	0.38	0.08	9.81E-01	7.12E-03	1.11E-07	0.794	2
5	5.3	34	0.36	0.2	1.04E+00	5.87E-03	8.05E-08	1.97	1
6	3.8	28	0.31	0.1	9.64E-01	1.58E-02	1.21E-07	0.98	5

7	2.9	25.9	0.35	0.05	1.01E+00	1.69E-02	1.43E-07	0.57	4
8	6	30.3	0.39	0.04	9.95E-01	4.32E-03	9.69E-08	1.419	2
9	6.2	26.8	0.33	0.18	1.08E+00	1.17E-02	9.33E-08	0.819	5
10	7.4	32.8	0.34	0.02	1.05E+00	1.13E-02	1.08E-07	1.148	3

Figure A-6. Contents of the SNL2.SUF File

Label	(in.)	Std Dev(in.)	(ft^3)	(%)	Label	(in.)	Std Dev(in.)	(ft^3)	(%)
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.056	0.057	203.76	0.688
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.055	0.0563	201.21	0.679
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.056	0.0566	201.96	0.682
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.055	0.0559	200.3	0.676
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.056	0.0569	203.17	0.686
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.056	0.0567	202.55	0.684
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.056	0.0564	201.51	0.68
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.055	0.056	200.39	0.676
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.057	0.0583	206.45	0.697
PRECIPITATION	8.16	1.32	29628.1	100	RUNOFF	0.055	0.0558	199.96	0.675

Figure A-7. Partial Contents of the SNL2.OUT.SUF File

sen5	25											
2												
Sensitivity/Uncertainty Module for FRAMES												
Beta Test version												
9	0											
maxleaf	Maximum Leaf Area Index from src2											
EvDepth	Evaporative Zone Depth from src2											
FCap1	Field Capacity, Layer # 1 from src2											
wilt1	Wilting Point, Layer # 1 from src2											
Sat1	Sat. Hyd. Conductivity, Layer # 1 from src2											
Sat2	Sat. Hyd. Conductivity, Layer # 2 from src2											
Sat4	Sat. Hyd. Conductivity, Layer # 4 from src2											
PinDen3	Geomembrane Pinhole Density, Layer # 3 from src2											
PlaceQ3	Geomembrane Placement Quality, Layer # 3 from src2											
10												
realizations	maxleaf	EvDepth	FCap1	wilt1	Sat1	Sat2	Sat4	PinDen3	PlaceQ3	Label	(in.)	Std Dev(in.)
1	2.2	27.3	0.32	0.14	1.02E+00	1.31E-02	8.42E-08	1.648	2	PRECIPITATION	8.16	1.32
2	3.7	31.6	0.39	0.11	9.44E-01	9.77E-03	1.02E-07	1.793	4	PRECIPITATION	8.16	1.32
3	7	29.7	0.37	0.14	9.01E-01	8.88E-03	7.30E-08	1.344	3	PRECIPITATION	8.16	1.32
4	4.4	34.4	0.38	0.08	9.81E-01	7.12E-03	1.11E-07	0.794	2	PRECIPITATION	8.16	1.32
5	5.3	34	0.36	0.2	1.04E+00	5.87E-03	8.05E-08	1.97	1	PRECIPITATION	8.16	1.32
6	3.8	28	0.31	0.1	9.64E-01	1.58E-02	1.21E-07	0.98	5	PRECIPITATION	8.16	1.32
7	2.9	25.9	0.35	0.05	1.01E+00	1.69E-02	1.43E-07	0.57	4	PRECIPITATION	8.16	1.32
8	6	30.3	0.39	0.04	9.95E-01	4.32E-03	9.69E-08	1.419	2	PRECIPITATION	8.16	1.32
9	6.2	26.8	0.33	0.18	1.08E+00	1.17E-02	9.33E-08	0.819	5	PRECIPITATION	8.16	1.32
10	7.4	32.8	0.34	0.02	1.05E+00	1.13E-02	1.08E-07	1.148	3	PRECIPITATION	8.16	1.32

Figure A-7. Partial Contents of the Combined Output From SNL2.SUF and SNL2.OUT.SUF Files

12. Once the output from both files is combined in this way, the user can perform statistical analyses on the results such as correlating input parameter values to results.

A.1.5. Verification of HELP Stochastic Runs

SUM3 works by creating a list of sampled values for each parameter selected by the user based on the distribution parameters entered by the user. It then substitutes the parameter values into the input file for the model, runs the model, and collects outputs for the run. This process is repeated until the number of iterations specified by the user have been completed.

The process used to verify that the system was working properly was pretty straightforward. HELP was run stochastically using SUM3 for ten iterations. After the runs were completed, the inputs and outputs for each run were available to view. The test involved entering the values for each run and running HELP deterministically to see if the results matched the results saved for that iteration by SUM3. The concept being that the HELP model results should be the same whether the input parameter values are input by hand or if they are input by SUM3. Several of the ten realizations were checked and each time the results matched the results saved by SUM3.

A.2. Integration of RAECOM with FRAMES

The RAECOM computer code (Rogers et al., 1984) was integrated into the FRAMES modeling system in order to evaluate the uncertainty in simulated radon flux through the landfill cover at the Monticello mill tailings disposal unit. The RAECOM code was originally written to deterministically simulate the radon flux for a given cover design and set of parameter values (or to determine the minimum thickness of a particular layer to meet regulatory criteria). Coupling of the RAECOM code with the FRAMES code allows automated evaluation of the uncertainty and sensitivity of simulated radon flux via the SUM3 module in FRAMES. The SUM3 module uses the Latin Hypercube sampling technique to efficiently sample the ranges of uncertainty in input parameters and allows the user to run the model in a stochastic mode.

The integration of RAECOM into FRAMES involves producing a set of files and codes that allow communication of the RAECOM program with FRAMES during execution of the FRAMES code. The .DES file contains information on the sub-program being called (RAECOM in this case) and a list of stochastic and output parameters to be passed between the sub-program and FRAMES. A pre-processor program is required to write stochastic parameter values into a properly formatted input file for the RAECOM code. A post-processor program is needed to write the output of the RAECOM code into a file that is properly formatted for the FRAMES code. In addition, a batch file is needed to call the pre-processor program, the RAECOM executable, and the post-processor sequentially. The files and codes that were developed to integrate RAECOM into FRAMES are specific to the landfill cover design at Monticello and to the stochastic parameters in this study used to evaluate uncertainty. These

files and codes can be modified to accommodate alternative analyses. Fully generalizing the integration of RAECOM into FRAMES would, however, require significant additional code development.

The .DES file for the RAECOM code is *RAECOM2.DES*. The .DES file tells the FRAMES system the name of the model, the type of model it is, which modules in FRAMES it can connect to, the name and location of the executable, and a list of the stochastic parameters in the model. The .DES file also contains annotation information about the model. The *RAECOM2.DES* file is listed below:

```
"mf","Version 2.1"
"Model:source:src","RAECOM 2.0 Radon Flux Model","RadonMod2.bat
","raecom2.bat ","c:\frames\src.ico"
"
MODULE VERSION
1.2

MODULE DESCRIPTION
Radon flux through landfill cover

MODULE REFERENCES
RAECOM software code
Rogers, V.C., K.K. Nielson, and D.R. Kalkwarf, 1984, Radon attenuation
handbook
for uranium mill tailings cover design, NUREG/CR-3533, U.S. Nuclear
Regulatory
Commission, Washington, D.C.

VALID CONNECTIONS
Valid Input Reads

Valid Output Writes
    wff aquifer flux

SYSTEM REQUIREMENTS
Operating System:    WIN 95 / NT
Processor:           486
RAM Memory:          32 Mb
Disk Space:          1 Mb

POINT OF CONTACT
Company Name:        Sandia National Laboratories
Contact Name:        Bill Arnold
Mailing Address:     P.O. Box 5800
City:                Albuquerque
State:               NM
Zip Code:            87110
Country:             USA
Telephone Number:    (505) 284-4603
Fax Number:          (505) 284-4001
Email Address:       bwarnol@sandia.gov
URL Address:         unknown
```

```

"
0,"Read"
1,"Write"
"wff","aquifer flux"
10,"Variables"
"Q1","Continuous","N/A","Min",0,"Max",10,"radon emanation rate from
tailings",0
"D1","Continuous","N/A","Min",0,"Max",10,"diffusion coefficient layer
1",0
"D2","Continuous","N/A","Min",0,"Max",10,"diffusion coefficient layer
2",0
"D3","Continuous","N/A","Min",0,"Max",10,"diffusion coefficient layer
3",0
"D4","Continuous","N/A","Min",0,"Max",10,"diffusion coefficient layer
4",0
"D5","Continuous","N/A","Min",0,"Max",10,"diffusion coefficient layer
5",0
"P1","Continuous","N/A","Min",0,"Max",10,"moisture content percent
layer 1",0
"P2","Continuous","N/A","Min",0,"Max",10,"moisture content percent
layer 2",0
"P4","Continuous","N/A","Min",0,"Max",10,"moisture content percent
layer 4",0
"P5","Continuous","N/A","Min",0,"Max",10,"moisture content percent
layer 5",0

```

Note that there are 10 variables passed between FRAMES and RAECOM, as designated in the file *RAECOM2.DES*. These are the 10 stochastic input parameters to the radon flux model.

The pre-processor code (*raecom-pre2.exe*) is a relatively simple FORTRAN program that reads in a template input file for the RAECOM code, inserts the values of the stochastic variables for that realization, and writes the input file to be read by RAECOM. The template input file is named *rc_tmplt.dat* and is specific to the Monticello landfill cover analysis. The values of the stochastic parameters for the current realization are read from the file *radon_s2.gid*, which is rewritten during each iteration of the SUM3 module of the FRAMES code. The output of the pre-processor code is the input file for the RAECOM executable with the file name *rcinput.dat*. The file *rc_tmplt.dat* is shown below as an example of the input for the RAECOM code (see Rogers et al., 1984 for explanation):

```

RAECOM CALCULATION OF MONTICELLO LANDFILL COVER
5, 0., 0., 3, 20., .001
1500., .0149, .43, .00215, 13.1
61., .00205, .35, .0, 15.2
0.15, .0002, .01, .0, 1.0
30., .022, .37, .0, 15.0
168., .0108, .43, .0, 15.2

```

The post-processor code (*raecom-post.exe*) is a simple FORTRAN program that reads in the simulated radon flux from the RAECOM program, reads in a template for the .wff file to pass the results to FRAMES, and writes the results of that realization to the temporary .wff file. The

simulated radon flux through the upper layer of the landfill cover is read from the file *rcoutput.dat*. The template file for communicating the results to FRAMES is named *rc_tmplt.wff*. The simulated radon flux at the surface of the landfill cover is written to the file *~radon34.wff*. An example output file *rcoutput.dat* is shown below:

RAECOM CALCULATION OF MONTICELLO LANDFILL COVER

***** I N P U T P A R A M E T E R S *****

NUMBER OF LAYERS : 5
 RADON FLUX INTO LAYER 1 : 0.000 pCi/m2/sec
 SURFACE RADON CONCENTRATION : 0.000 pCi/liter

 LAYER 3 ADJUSTED TO MEET Jcrit : 0.000 +/- 20.0
 pCi/m2/sec

LAYER 3 EXCEEDS SATURATION. MOISTURE CHANGED FROM 0.010 TO 0.004

BARE SOURCE FLUX (Jo) FROM LAYER 1 : 1173. pCi/m2/sec

LAYER	THICKNESS (cm)	DIFF COEFF (cm2/sec)	POROSITY	SOURCE (pCi/cm3/sec)
1	1500.00	0.3651E-01	0.4300	0.2070E-02
2.49	0.00	0.4828E-02	0.3500	0.0000E+00
8.85	0.00	0.1139E-01	0.0100	0.0000E+00
0.37	0.00	0.4131E-01	0.3700	0.0000E+00
7.07	168.00	0.7788E-02	0.4300	0.0000E+00
9.05				

***** RESULTS OF RADON DIFFUSION CALCULATION *****

LAYER	THICKNESS (cm)	EXIT FLUX (pCi/m2/sec)	EXIT CONC. (pCi/liter)	MIC
1	1500.00	3.2245E+02	7.1460E+05	0.9340
2	0.00	3.2245E+02	5.1389E+05	0.6716

3	0.00	3.2245E+02	2.0459E+05	0.2674
4	0.00	3.2245E+02	5.8098E+05	0.7593
5	168.00	4.0707E+01	0.0000E+00	0.7602

In this example output file from the RAECOM code, the simulated radon flux at the surface is the exit flux from the upper layer of the landfill cover (layer 5) and is equal to 40.7 pCi/m² s.

The DOS batch file controlling the sequential execution of the pre-processor, RAECOM code, and post-processor is named *raecom2.bat*. The *raecom2.bat* file is shown below:

```
copy %1.gid radon_s2.gid
raecom-pre2.exe
raecom2.exe
raecom-post.exe
copy ~radon34.wff %2.wff
```

Appendix B: Parameter Values and Distributions for Material Properties of the Monticello Cover

This Appendix details the base-case parameters and the derivation of uncertainty distributions for various layers in the Monticello cover. The base-case parameters used in the HELP calculations are shown in Tables B-1 and B-2:

Table B-1. Base-Case Input Parameters for Cover Layers

Input Parameter		Value	Source
Layer 1 Vertical Percolation Layer	Thickness (in)	66.0	(1)
	Porosity	0.456	(1)
	Field Capacity	0.380	(1)
	Wilting Point	0.180	(1)
	Initial Water Content	0.300	(1)
	K _{sat} (cm/sec)	10 ⁻⁴	see Section 4.3.1
Layer 2 Lateral Drainage Layer	Thickness	12.0	(1)
	Porosity	0.375	(1)
	Field Capacity	0.150	(1)
	Wilting Point	0.040	(1)
	Initial Soil Water Content	0.080	(1)
	K _{sat} (cm/sec)	10 ⁻²	(1)
	Slope (%)	3	(1)
	Drainage Length (ft)	1800.	(1)
Layer 3 Flexible membrane Liner	Thickness (in)	0.060	(1)
	K _{sat} (cm/sec)	2.0 x 10 ⁻¹³	(1)
	Pinhole Density (Holes/Acre)	1.0	(1)
	Installation defects (holes/acre)	1.0	(1)
	Placement Quality	"Good"	(1)
Layer 4 Radon Barrier	Thickness (in)	24.0	(1)
	Porosity	0.343	(1)
	Field Capacity	0.200	(1)
	Wilting Point	0.150	(1)
	Initial Soil Water Content	0.310	(1)
	K _{sat} (cm/sec)	10 ⁻⁷	(1)

(1) Abraham and Waugh (1995)

Table B-2. HELP Base-Case General Input Parameters

Input Parameter		Value	Source
Cover Slope (%)		3.0	(1)
Cover Length (ft)		1800.	(1)
SCS Runoff Curve Number		92	(1)
Evaporative Zone Depth (in)*		66.0	(1)
Maximum Leaf-Area Index*		1.0	(1)
Growing Season	Start - DOY*	74	(1)
	End - DOY*	319	
Average Wind Speed (mph)*		7.50	(1)
Average RH*	1 st Quarter	58.5%	(1)
	2 nd Quarter	30.7%	
	3 rd Quarter	32.8%	
	4 th Quarter	50.8%	
Precipitation*		Monthly Variation	(2)
Temperature (min and max)*		Monthly Variation	(2)
Solar Radiation*		Based on Latitude of 37.52 Degrees	(2)

* Parameter Varied

(1) Abraham and Waugh (1995)

(2) Owenby and Ezell (1992)

Uncertainty Distributions for Layer 1

The RETC Program (van Genuchten, et al., 1991) has been used to fit the initial drainage curve data for the Monticello soils (Daniel B. Stephens & Associates, 1993). The resulting fitting parameters, as well as the porosity, field capacity, and wilting point have been derived from these fits. Initially, the Brooks and Corey option was selected in RETC because Brooks and Corey is used in HELP, but the fits did not make sense. The van Genuchten/Mualem option ($m=1-1/n$) was selected next, and the fits were much better. The saturation as a function of head for van Genuchten is

$$S_e = \left(1 + (\alpha h)^n\right)^{-m}$$

where $m = 1 - 1/n$ for the Mualem option, and

$$S_e = \frac{\theta - \theta_r}{\theta_s - \theta_r}$$

where α , n , θ_s and θ_r were fit by the program. The results are tabulated below as well as the field capacity (θ_{FC}) ($h=0.33$ bars = 330 cm) and wilting point (θ_{WP}) ($h=15$ bars = 15,000 cm) derived from the fit. The porosity was calculated from the curve fit and is different from the porosity listed in the report.

Table B-3. Constitutive parameters for soil samples of layer 1.

Sample Number	Porosity $\phi=\theta_s$	α (cm^{-1})	n	θ_r	θ_{FC}	θ_{WP}	R^2
358-128	0.474	0.0412	1.142	0.	0.326	0.191	0.972
358-144	0.427	0.0032	1.183	0.	0.381	0.209	0.979
358-172	0.373	0.00026	1.249	0.	0.370	0.257	0.993
351-128	0.468	0.0616	1.146	0.	0.301	0.173	0.972
351-144	0.398	0.0033	1.188	0.	0.354	0.192	0.968
351-172	0.356	0.00027	1.267	0.	0.353	0.237	0.996
354-128	0.462	0.0410	1.295	0.0153	0.221	0.082	0.998
354-144	0.466	0.0144	1.337	0.0236	0.278	0.096	0.991
354-188	0.332	0.0048	1.217	0.	0.278	0.132	0.964
361-128	0.391	0.0606	1.155	0.	0.245	0.136	0.985
361-144	0.408	0.0341	1.156	0.	0.277	0.154	0.980
361-177	0.330	0.00072	1.230	0.	0.321	0.189	0.984

The R^2 values are generally good for all the fits. However, because the data are limited (8 points per curve for pressure heads ranging from 0 to over 100,000 cm), the fidelity of the curve fits may be low. The fits show a wide range of values, especially for the α parameter, which ranges over two orders of magnitude. The porosity values from the curve fits are generally much lower than the porosity values listed in the report. The values from the curve fit tend towards the measured moisture content at zero head. Even with the wide variation in the α parameter, the calculated values of the field capacity (θ_{FC}) and wilting point (θ_{WP}) are reasonably consistent except for a couple of values.

A statistical analysis of the parameters in Table B-3 was performed to estimate the uncertainty distributions and potential correlations among saturated hydraulic conductivity, field capacity, and wilting point. The probability plot of log-transformed K_{sat} indicates an approximately log-normal distribution for this parameter, with the exception of one outlier sample, as shown in Figure B-1 below. The mean value of log K_{sat} is -3.52 with a standard deviation of approximately 0.95.

The linear correlation between log K_{sat} and field capacity gives a negative correlation with an R-squared value of 0.44. The linear correlation between field capacity and wilting point yields a positive correlation with an R-squared value of 0.78. Both field capacity and wilting point appear to be approximately uniformly distributed.

Results indicate that K_{sat} should be sampled from a log-normal distribution with a log-transformed mean of -3.52 and standard deviation of 0.95. Field capacity should be sampled from a uniform distribution with a lower bound of 0.22 and upper bound of 0.38. Wilting point should be sampled from a uniform distribution with a lower bound of 0.08 and an upper bound of 0.21. A correlation coefficient of negative 0.44 should be specified for log K_{sat} and field capacity. A correlation coefficient of 0.78 should be specified for field capacity and wilting point.

Figure B-1. Cumulative probability of log-transformed hydraulic conductivity for soil samples of layer 1.

Uncertainty Distributions for Layers 2 and 4

The section describes steps to develop stochastic parameter distributions for the saturated hydraulic conductivity (K_{sat}), wilting point (θ_{wp}), and field capacity (θ_{FC}). Uncertainty distributions for these parameters are developed for layers 2 (sand) and 4 (clay) of the HELP percolation model for the Monticello disposal site using data and joint probability distributions reported in Carsel and Parrish (1988).

1. Input statistics (mean and standard deviation) for normal (transformed) distributions of K_{sat} , α , and N for the sand and clay layers in Carsel and Parrish (1988, Table 6) into LHS. Ensure physical limits of parameters by transforming lower and upper bounds (A and B) for lognormal and hyperbolic arcsine transforms (do not need limits on log ratio transform). The only parameters that need to have physical limits applied are the N -parameters for both sand and clay layers (lognormal transforms).
2. Input correlation coefficients into LHS for K_{sat} , α , and N using the lower triangular portion of the matrices shown in Table 7 of Carsel and Parrish (1988). This lower triangular portion contains the “Pearson product-moment correlations,” which is the same as the correlation coefficient, R , used in LHS.
3. After LHS has calculated the distribution of parameters, the parameters need to be post-processed and back-transformed into real space. In addition, the wilting point and field

capacity need to be determined from the van Genuchten parameters (α and N). First, we need to transform the LHS parameter so that its mean is the same as the mean used in the Monticello calculation. We convert the normalized LHS parameter, Y , to a standard normal deviate (say Z) and then convert the standard normal deviate to a value with a new mean assuming that the standard deviation in Carsel and Parrish (1988, Table 6) is the same as the Monticello data:

$$y = Y + \mu_2 - \mu_1$$

where y is the deviate in transformed space with the Monticello mean, Y is the transformed deviate sampled by LHS from the original distribution, μ_1 is the mean from Carsel and Parrish (1988, Table 6), and μ_2 is the Monticello mean. Note that μ_2 is the mean in the transformed space. For a log-ratio transform, there is no analytical way to transform the mean value reported for Monticello to the log-ratio mean in transformed space (we would need the actual data; we only have site data for Layer 1 (soil), not layers 2 and 4). Therefore, we iterate on the transformed mean for the parameters that require a log-ratio transform in Carsel and Parrish (1988) (i.e., K_{sat} and α). This is done in a spreadsheet for all values in the distribution, and the transformed mean is varied until the desired mean is achieved for the distribution in real space. Because K_{sat} is generally lognormally distributed, we assumed that the point values for K_{sat} used in the Monticello model were median values instead of mean values.

The van Genuchten N parameter for sand and clay uses a log-normal transformation in Carsel and Parrish (1988), so its transformed mean can be exactly specified from a mean value in real space (using the standard deviation from Carsel and Parrish). The mean N -parameter is obtained from the reported wilting point and field capacity in the Monticello calculation using the van Genuchten equation for soil moisture retention. The wilting point and field capacity values provide two equations for two unknowns, α and N . The wilting point and field capacity give the moisture content at capillary pressures of 0.33 and 15 bars, respectively. These equations can be solved implicitly, say, in Mathcad.

4. Backtransform the deviate from normal space (y) to real space (X) using the appropriate back-transformation (Eqs 15-17 in Carsel and Parrish, 1988).
5. Calculate wilting point by using a rearranged form of the van Genuchten equation. The following equation is taken from Equation 1 in Carsel and Parrish (1988), but the residual moisture content, θ_r , is replaced by the Equation (6) in the HELP Engineering Manual. In addition, the saturated moisture content is replaced by the porosity.

$$\theta_{wp} = \frac{a(\gamma - 1) + \phi}{\gamma + b(1 - \gamma)} \quad (B1)$$

$$\text{where } \gamma = \left[1 + (\alpha h_{wp})^N \right]^M \quad (B2)$$

$$\text{and } a = 0.014, b = 0.25 \text{ if } \theta_{wp} \geq 0.04 \quad (B3)$$

$$a = 0, b = 0.6 \text{ if } \theta_{wp} < 0.04 \quad (B4)$$

where ϕ is the porosity of the material (not sampled), h_{wp} is the wilting point head (cm) associated with the wilting point pressure prescribed by HELP (p. 15 of the Engineering Manual) to be 15 bar (= 1.53×10^4 cm at 20°C, and $M = 1 - 1/N$). Note that the resulting wilting point in (B1) must be compared to the conditions for the wilting point prescribed Equations (B3) and (B4). If the values are contradictory, then Equation (B1) must be solved again using the other values (either from Equation (B3) or Equation (B4)) for parameters a and b .

6. Once the wilting point is determined, the field capacity can be found using the Equation (B1) from Carsel and Parrish (1988):

$$\theta_{fc} = \theta_r + \frac{\phi - \theta_r}{\left[1 + (\alpha h_{fc})^N\right]^M} \quad (B5)$$

$$\text{where } \theta_r = 0.014 + 0.25\theta_{wp} \text{ if } \theta_{wp} \geq 0.04 \quad (B6)$$

$$\theta_r = 0.6\theta_{wp} \text{ if } \theta_{wp} < 0.04 \quad (B7)$$

where h_{fc} is the field-capacity head (cm) associated with the field-capacity pressure prescribed by HELP (p. 15 of the Engineering Manual, Schroeder et al., 1994b) to be 0.33 bar (= 337 cm at 20°C). This method assumes that the field capacity and the wilting point are perfectly correlated, and that they are calculated from the sampled van Genuchten parameters.

Appendix C: Stepwise Linear-Regression Method of Sensitivity Analysis

When sampling-based uncertainty/sensitivity analysis is performed on a model with many uncertain parameters, standard multiple regression may not be appropriate. Typically, only a small number of uncertain parameters have a significant impact on the uncertainty in the model output. Overfitting of the model can occur when variables are arbitrarily forced into the regression relationship. Consequently, it is desirable to construct a multiple regression model that is based on only those input parameters that have a significant impact on the output.

Stepwise linear regression is a modified version of multiple regression that selectively adds input parameters to the regression model in successive steps (Helton and Davis, 2000). In this method a sequence of regression models is constructed in which the first model contains the most important independent variable, the second model contains the two most important variables, etc. The stepwise process continues until no more variables with a significant effect on the output are found. The stepwise construction is halted when addition of more parameters will not meaningfully contribute to the regression model for the dependent variable.

The stepwise linear regression method provides insights into model sensitivity in several ways. The order of parameter selection for incorporation into the regression model gives an indication of their relative importance. The parameters added in the steps are successively less important to the model output. The change in the coefficient of determination (ΔR^2) for a given step indicates the fraction of the variance in the model output explained by the input parameter added in that step. The sign of the standardized regression coefficient indicates the “direction” of influence for that parameter.

Linear regression analysis, including stepwise regression, performs poorly for non-linear relationships. Rank transformation of independent and dependent variables is a straightforward method that often improves regression analysis and is generally used to compensate for potential non-linear relationships in the stepwise linear regression method for complex model results. Rank transformation consists of assigning integer rankings to the variables, where the smallest value of a given variable is assigned a value of 1, the next higher value is assigned a value of 2, etc. Averaged rank values are assigned to equal values for a particular parameter. Rank transformation essentially develops regression on the strength of the monotonic relationship, instead of the strength of the linear relationship between independent and dependent variables.

Correlations between input parameters can complicate regression sensitivity analysis, producing unstable regression coefficients. One possible strategy is to eliminate from the analysis one of the input parameters in a highly correlated pair. Rarely, non-monotonic relationships between dependent and independent variables may lead to very poor performance of the stepwise regression method that cannot generally be corrected with rank transformation. Scatter plots and understanding of physical relationships can be used to identify non-monotonic behavior.

Stepwise linear regression is one of the most powerful and commonly used methods of sensitivity analysis in sampling-based uncertainty analyses. This method facilitates a global understanding of the relationships between uncertainty in input parameters and the uncertainty in modeling results for complex probabilistic models. In addition, stepwise regression provides a quantitative basis for prioritizing the importance of parameters and components of the landfill cover system with regard to system performance.

Distribution

<p>1 Missy Klem
Department of Energy
P.O. Box 5400
Building 384-3
Albuquerque, NM 87185</p>	<p>Savannah River Operations Office
Road 1A, Building 703-A
Aiken, SC 29801</p>
<p>1 Pam Saxman
Department of Energy
P.O. Box 5400
Building 384-3
Albuquerque, NM 87185</p>	<p>1 Skip Chamberlain
Department of Energy, Headquarters
Germantown
19901 Germantown Road, Room 2218
Germantown, MD 20874-1290</p>
<p>1 Michael Fayer
Battelle, Pacific Northwest National Laboratory
P.O. Box 999 / MS K9-33
Richland, WA 99352</p>	<p>1 James Wright
U.S. Department of Energy
Savannah River Operations Office
Road 1A, Building 703-A
Aiken, SC 29801</p>
<p>5 Randal Taira
Battelle Seattle Research Center
4500 Sand Point Way NE
Suite 100
Seattle, WA 98105-3949</p>	<p>1 Calvin C. Chien
DuPont Company
Barley Mill Plaza 27/2128
4417 Lancaster Pike
Wilmington, DE 19805</p>
<p>1 Gene Whelan
Battelle, Pacific Northwest National Laboratory
P.O. Box 999 / MS K9-36
Richland, WA 99352</p>	<p>1 Craig H. Benson
Department of Civil & Env. Engr.
University of Wisconsin-Madison
2214 Engineering Hall
1415 Engineering Dr.
Madison, WI 53706</p>
<p>1 Glendon Gee
Battelle, Pacific Northwest National Laboratory
P.O. Box 999 / MS K9-33
Richland, WA 99352</p>	<p>1 Lorne G. Everett
Lakehead University
3700 State St., Suite 350
Santa Barbara, CA 93105-3100</p>
<p>1 John Heiser
Brookhaven National Laboratory
P.O. Box 5000 , Building 830
Upton, NY 11973-5000</p>	<p>1 Hillary I. Inyang
University of North Carolina-Charlotte
CARC Bldg, Rm 238
9201 University City Blvd.
Charlotte, NC 28223-0001</p>
<p>1 Jody Waugh
U.S. Department of Energy
Grand Junction Office
2597 B3/4 Road
Grand Junction, CO 81503</p>	<p>1 Beth A. Moore
U.S. DOE
1000 Independence Ave. SW
Forrestal Bldg., Rm 3E066
Washington, DC 20585</p>
<p>1 Mike Serrato
Savannah River Technology Center
Building 773-42A-217
Aiken, SC 29808</p>	<p>1 Greg P. Newman
Geo-Slope International Ltd.
1400 633 6th Ave SW
Calgary, AB T2P 2Y5
Canada</p>
<p>1 Scott McMullin
U.S. Department of Energy</p>	

- 1 Jack C. Parker
Oak Ridge National Laboratory
Bldg. 1505, Rm 264
Oak Ridge, TN 37831
- 1 Steven J. Piet
INEEL
P.O. Box 1625, MS-3605
Idaho Falls, ID 83415-3605
- 1 Robert P. Breckenridge
INEEL
P.O. Box 1625
Idaho Falls, ID 83415-2213
- 1 Andrew D. Paterson
2149 N. Street NW
Washington, DC 20037
- 1 Charles D. Shackelford
Department of Civil Engineering
Colorado State University
Fort Collins, CO 80523-1372
- 1 Caroline B. Purdy
U.S. DOE
Cloverleaf Bldg., EM-54
19901 Germantown Rd
Germantown, MD 20874
- 1 Bruce A. Robinson
LANL
MS T003
Los Alamos, NM 87545
- 1 Ralph Smiecinski
P.O. Box 98518
Las Vegas, NM 89193-8518

1	MS-0701	P. Davies, 6100
1	MS-0701	W. Cieslak, 6100
1	MS-0706	R. Finley, 6113
5	MS-0735	J. Cochran, 6115
10	MS-0735	C. Ho, 6115
1	MS-0735	E. Webb, 6115
1	MS-0750	M. Walck, 6116
1	MS-0750	D. Borns, 6116
1	MS-0751	L. Costin, 6117
1	MS-0750	H. Westrich, 6118
1	MS-0719	W. Cox, 6131
1	MS-0719	S. Dwyer, 6131
1	MS-0719	C. Heise, 6131
1	MS-0719	S. Howarth, 6131
1	MS-0719	E. Lindgren, 6131
1	MS-1087	F. Nimick, 6132
1	MS-1087	D. Stockham, 6133
1	MS-1088	D. Miller, 6134
1	MS-1089	D. Fate, 6135
1	MS-1395	K. Knowles, 6821
1	MS-0779	R. Anderson, 6849
1	MS-0778	P. Swift, 6851
5	MS-0776	B. Arnold, 6852
1	MS-0776	H. Jow, 6852
1	MS-9018	Central Technical Files, 8945-1
2	MS-0899	Technical Library, 9616
1	MS-0612	Review & Approval Desk, 9612 For DOE/OSTI