LABORATORY DIRECTED RESEARCH AND DEVELOPMENT

Science
and Technology
Mission Technologies
Grand Challenges

A Department of Energy
National Laboratory

“The Next Revolution”

Cover (Above)

By supporting critical research, Sandia’s LDRD researchers are making exciting advances in micro- and nanotechnologies. Microsystems are highly miniaturized systems that integrate a number of devices (each on the order of 1 μm to 1 mm in size) representing a range of capabilities (e.g., electronics, mechanics, and optics, among others) onto a single silicon chip. These microsystems represent *the next revolution* in silicon technology that will lead to new products with combined actuation, sensing, and communication capabilities.

Sandia’s nanosciences LDRD investigations advance the underpinning capabilities that will lead to improved microsystem performance. Nanosciences discoveries enable scientifically tailored materials and lead to revolutionary advances in technology—by building things atom-by-atom or molecule-by-molecule, the production of virtually every human-made product will be revolutionized.

Sandia’s LDRD research enhances the Laboratories’ proficiency in many technical fields in support of its Department of Energy mission to serve extensive national security applications. By understanding and controlling phenomena at multiple levels, researchers are learning to design materials and systems with vastly different sets of properties. As one Sandia scientist put it, “...*design possibilities are limited only by one’s imagination.*”

Cover photos (top right, going clockwise): (1) examining nanoscale behavior, (2) creating the world’s smallest robots, (3) advancing ultrasensitive detection systems, (4) developing novel microfabrication techniques, (5) architecting novel nanomaterials, (6) inventing intelligent microsystems, and (7) investigating nanoclustered catalysts.

Abstract

This report summarizes progress from the Laboratory Directed Research and Development (LDRD) program during fiscal year 2001. In addition to a programmatic and financial overview, the report includes progress reports from 295 individual R&D projects in 14 categories.

This work was supported by the United States Department of Energy under Contract DE-AC04-94-AL85000.

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy.

SAND 2002-0812
March 2002

LDRD Annual Report Staff:

Chuck Meyers
Cynthia Harvey
Donna Chavez
Bryon Cloer

Carol Whiddon
Katharine Beebe
Donna Drayer
Douglas Prout

Table of Contents

- 13 “... exceptional service in the national interest.”
 - 14 Supporting National Security Through Science and Technology
 - 17 Laboratory Directed Research and Development (LDRD) Program Overview
-

Advanced Concepts

- 35 Solutions to National and Global Security Issues Based on Limited Freshwater Resources
 - 37 Understanding and Managing Threats to the Social Fabric of the United States
 - 40 Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles
 - 42 Micromachined Patch-Clamp Array
 - 44 Microscale Techniques for the Study of Cell Signaling
 - 47 Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling
 - 49 Training Software Agents to Reason in the Absence of Data
 - 51 Nonlinear Modeling and Simulation of Pulsed Electromagnetic Stimulation and Response of Selected Excitable Biological Structures
 - 54 MyLink
-

Advanced Manufacturing

- 57 Microdiagnostic MEMS Lab-on-a-Chip
 - 61 Thin-Film Deposition Processes Incorporating *In Situ* Monitoring Capabilities
 - 63 Volumetric Displacement Control (VDC) of Manufacturing Tools
-

- 66 Process-Based Quality Tools to Verify Cleaning and Surface Preparation
 - 69 Fabrication of Three-Dimensional Microstructures Using Soft Lithography
 - 72 Automatic Design of Practical Fixtures
 - 75 Microreplication: Precision Metal Parts from Electroformed Master Molds
 - 78 IMEMS Packaging and Interconnection Technology
 - 81 Assembly of LIGA Using Electric Fields
 - 83 Computer Numerically Controlled Micro-machines
 - 85 Electromicrofluidic Packaging
 - 87 Mesoscale Wide-Bandwidth Linear Magnetic Actuators
 - 90 Levitated Three-Axis Microaccelerometer
 - 92 Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques
 - 94 Resolving Fundamental Limits of Adhesive Bonding in Microfabrication
-

Biotechnology

- 97 Predicting Function of Biological Macro-molecules
- 100 Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes
- 103 Molecular-Scale Studies of Single-Channel Membrane Pores
- 105 Efficient Massively Parallel Techniques for Protein Structure Generation

Table of Contents

- 107 Mapping Membrane Protein Interactions in Cell Signaling Systems
- 109 High-Throughput Instruments, Methods, and Informatics for Systems Biology
- 111 Nanolaser Flowchip for Real-Time Cell and Tumor Biology

Computational & Information Sciences

- 114 Heterogeneous Simulation
- 116 Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions
- 118 Hybrid Sparse-Dense Incomplete Factorization Preconditioners
- 121 Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry
- 124 Molecular Simulation of Reacting Systems
- 126 Massively Parallel Global Climate Model for Paleoclimate Applications
- 129 Algorithmic Advances in Computational Structural Biology
- 132 Large-Scale Nonlinear Optimization Arising from PDE Models
- 134 Parallel Methods for Coupling Circuit- and Device-Scale Simulations
- 136 A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems
- 139 Parallel Atomistic Computing for Failure Analysis of Micromachines
- 141 Implementation of Fault Tolerance in Scientific Simulation Application Software

- 143 Smart Sensor Technology for Joint Test Assembly Flights
- 145 Multilevel Methods for Nonlinear Structural Mechanics
- 147 Algorithmic Support for Commodity-Based Parallel Computing Systems
- 149 Parallel Repartitioning for Optimal Solver Performance
- 152 Numerical Methods Applied to High-Energy Physics
- 155 Self-Organizing Network Intelligent Algorithm (SONIA)

Electronics & Photonics

- 158 Silicon Three-Dimensional Photonic Crystal and Its Applications
- 160 Monolithic Micromachined Variable Tuners for Rapid Prototyping and Optimization of Microwave Circuits
- 163 Quantum Tunneling Transistors for Practical Application
- 165 Development of Magnetically Excited Flexural Plate-Wave Devices for Implementation as Physical, Chemical, and Acoustic Sensors, and as Integrated Micropumps for Sensored Systems
- 168 Stress-Free Amorphous Diamond for High-Sensitivity Microsensors with Integrated Microstructures
- 172 Radiation-Induced Prompt Photocurrents in Microelectronics: Physics
- 175 SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications

Table of Contents

178	Defining the Frontiers of Vertical, External-Cavity, Surface-Emitting Lasers	Emerging Threats
181	Growth and Characterization of Quantum Dots and Quantum Dot Devices	217 Surface Decontamination of Bacterial Protein Toxins by RF Power
184	Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	219 Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures
187	Miniature Sensors for BW Agents Using Fatty-Acid Profiles	221 HPM Vulnerability Assessment and Tests
189	Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	223 Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay
192	High-Al-Content AlGaInN Devices for Next-Generation Electronic and Optoelectronic Applications	226 Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments
194	Microfabrication of Electromagnetic Devices	229 Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays
196	GaAs MOEMS Technology	232 Miniature UV Fluorescence-Based Biological Agent Sensor
198	Integrated Microsensors for Autonomous Microrobots	235 Proton Beam Directed-Energy Weapon
201	Silicon-Integrated Planar Microbatteries	237 Micro-High-G Acceleration Recorder
203	High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS	239 Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation
205	II-V-Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	241 Distributed Reconfigurable Homogeneous Microrobotic Systems
207	The Integration of Advanced Photonics and MEMS	243 Robust Planning for Autonomous Navigation of Mobile Robots in Unstructured, Dynamic Environments
209	Aging Mechanisms in Dormant MEMS Structures	246 Intense Directed-Energy Theory Initiative
211	MEMS in μ Fluid Channels	248 Fuzzy Data Mining
213	Dispersive Photonics for Next-Generation Sensors and Microsystems	251 Air Sterilization and Decontamination

Table of Contents

253	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	289	Obstacle Detection for Autonomous Navigation
255	Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents	291	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications
258	Advanced Unattended Ground Sensor Technology	293	Atmospheric Plasma Applications
261	The Endowment of Simulator Agents with Human-Like Episodic Memory	295	Feasibility Study on Fire-Suppression Properties of the Sandia Decon Foam
264	Automated Combat Course of Action (COA) Development	297	Feasibility Study for Improved Less-Lethal Weapons
266	An Advanced Learning Model for Agent Behavior	300	Feasibility Study for 5x Enhanced Energetic Materials
268	Threat-Assessment Study for Short-Pulse Laser Technologies in Directed-Energy and Countersensor Applications	302	Ultrahigh-Temperature Ceramic Material Research
270	Algorithms for Improved Performance in Cryptographic Protocols	304	Modeling Building Air Flow for Autonomous Robotic Agents
273	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	305	Investigation of Advanced Digital-Video Compression for the Control of Robotic Platforms
275	Triggered Isomer Research	307	Microfuze
277	A Scientific Basis for Robotic Ground-Vehicle Design	310	Intelligent Projectile Development
278	Adaptive and Mobile Ground Sensors	312	Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat
281	Algorithm Development for Prognostic Health Monitoring and Maintenance		Energy & Critical Infrastructure
283	New Mechanism for Upset of Electronics	315	Solid-State Ballistic Chemical Sensors
285	Flexible Robotic Maintenance Facility	317	Varying QoS for Fixed and Mobile Networks
287	Distributed Autonomous Navigation	319	High-Surety SCADA for the Critical Energy Infrastructures
		321	Agent-Based Mediation and Cooperative Information Systems

Table of Contents

324	Dynamically Self-Configurable Network Protocol	363	Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures
327	Hybrid Processing of Measurable and Subjective Information in Surety Analysis	365	Very High Temperature Gas-Cooled Reactor
329	Production Surety and Disruption Vulnerability Analysis	368	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations
332	Source Code Assurance Tool	370	A Model of Infrastructure Interdependency Using Communication Agents
335	A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	373	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants
338	A Micro-GC-Based Controller for Energy-Intensive Processes	376	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management
341	A MEMS Microelectric Generator	378	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles
343	Nanostructured Silicon Surfaces for Cost-Effective Photovoltaic Efficiency Improvements	381	Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion
346	Network Intrusion Detection Using Adaptive Critic Neural Networks	383	Specific Anion Nanoengineered Sorbents for Water Purification
348	Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry	385	Active Management Systems for Water-Quality Monitoring
350	Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	388	Low-Work-Function Material Development for the Microminiature Thermionic Converter
353	Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	391	Autonomous Microexplosive Subsurface Tracing System
356	Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	394	Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar
358	Use of Apatite and Substituted Apatites for <i>In Situ</i> Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water	396	Security Models of Agent-Based Coalitions
360	Information-Sharing Security Module Research and Development	399	Vulnerability Assessment of National Power Grid

Table of Contents

Engineering Sciences

- 402 Structural Simulations Using Multiresolution Material Models
- 405 Mechanisms of Adiabatic Shear Failure
- 407 Crack Nucleation and Growth: Combining Validated Atomistic and Continuum Modeling
- 410 Applied Microfluidic Physics
- 413 Innovative Measurement Diagnostics for Fluid/Solid and Fluid/Fluid Interactions in Rotating Flowfields
- 416 Energetic-Material Burn and Detonation at the Mesoscale
- 419 Small-Scale Multiaxial Deformation Experiments on Solder for High-Fidelity Model Development
- 422 Uncertainty Propagation in Models of Thermo-fluid Systems
- 425 Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements
- 428 A Physically Based Approach to Modeling Ductile Fracture
- 430 Radiation Aging of Stockpile and Space-Based Microelectronics
- 432 Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach
- 435 Effect of Dielectric Photoelectric Effect on Surface Breakdown

Grand Challenges

- 438 Information Collection
 - 439 Molecular Integrated Microsystems (MIMS)
 - 443 A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting
 - 447 Interfacial Bioscience Grand Challenge (IBIG)
-

Materials Science & Technology

- 450 Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films
- 453 Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments
- 456 Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS
- 458 Linking Atomistic Computations with Phase-Field Modeling
- 460 A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms
- 462 Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth
- 464 Wetting and Spreading Dynamics of Solder and Braze Alloys
- 467 Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms
- 471 Microscale Shock-Wave Physics Using Photonic Driver Techniques
- 474 Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis

Table of Contents

477	Physical Basis for Interfacial Traction-Separation Models	518	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation
480	Diagnostics for Joining Solidification/Microstructural Simulations	520	Mechanics and Tribology of MEMS Materials
483	Effects of Microstructural Variables on the Shock-Wave Response of PZT 95/5	523	Dynamics of Metal/Ceramic Interfaces
486	Mechanisms of Dislocation-Grain Boundary Interaction	524	<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth
488	Functional Materials for Electrochemo-mechanical Actuation of Microvalves and Micropumps	527	Determination of Critical-Length Scales for Corrosion Processes Using Microelectro-analytical Techniques
491	Making the Connection Between Microstructure and Mechanics	530	Nanoscale Mechanics in an Instrumented Transmission Electron Microscope
494	Switchable Hydrophobic-Hydrophilic Surfaces	532	LIGA Microsystems Aging: Evaluation and Mitigation
497	Nanostructured Materials Integrated in Micro-fabricated Optical Devices	534	Science-Based Processing of Field-Structured Composites
499	All-Ceramic Battery	536	Exploration of New Multivariate Spectral Calibration Algorithms
502	Magnetic-Field Effects on Vacuum-Arc Plasmas		
504	Microstructural and Continuum Evolution Modeling of Sintering		Microsystems & Engineering Sciences Applications (MESA)
507	Assuring Ultraclean Environments in Micro-system Packages: Irreversible and Reversible Getters	540	New Architectures for Micro-Total-Analytical Systems
509	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	543	Interconnection Technology for Next Generation of Integrated Microsystems
511	Nanoclusters for Supercapacitors		
513	First-Principles Determination of Dislocation Properties		Nonproliferation & Materials Control
516	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	546	A Real-Time Decision-Support Framework to Guide Facility Response to Abnormal Events
		549	Physical Model-Based Fusion of Sensor Array Data
		551	Controlling Information: Its Flow, Fusion, and Coordination

Table of Contents

552	Characterization of Underground Facilities in an Urban Environment	589	Extensibility of Knowledge-Based Human Agent Simulation
554	Nanosat	592	Secure Authenticated Sensor Packs
560	High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	595	Remote Monitoring of Difficult, Real-Time Targets Using Video SAR Technique
562	Induced Molecular Markers for Pathogen Detection: Microincubators for Rapid Toxin Expression	597	Adaptive Computer Intrusion Detection
564	Self-Assembled, Tamper-Detection Seals	599	Link Analysis Using High-Performance Computing
566	Techniques for Improving and Exploiting MTI Imagery	602	Coating Chemical Preconcentrators to Improve Chemical Agent Collection
568	Risk-Informed Proliferation Analysis Development	604	Ultralow-Power Spread-Spectrum Transceivers for Microtags to Improve Security During Critical Operations
571	Development of a Microoptic Gyroscope	607	Detection and Exploitation of Spread-Spectrum Waveforms
573	Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation	609	Small Power Direct-Conversion Microfluid Systems Using Logistical Fuels
575	New Glass Technology for Enhanced Architectural Surety	612	High-Bandwidth Optical Data Interconnects for Satellite Applications
578	Compact UV Laser Source for Chemical and Biological Sensing	615	Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources
580	Advanced Digital Detectors for Neutron Imaging	618	Deployable Large-Aperture Optics System for Remote-Sensing Applications
582	Microfabricated Acoustic Spectrum Analyzer	622	MicroChemLab Technologies for Early Detection of Pathogen Exposure
585	Enabling Analytical and Modeling Tools for Enhanced Disease Surveillance	625	Intelligent Tracking of the Telepresent Rapid-Aiming Platform
587	Microtransceiver for Tag, Beacon, and Data-Exfiltration Applications	627	Engineering Biomicrodevice Interfaces: New Microfuel Cells for Harvesting Energy from Biological Systems

Table of Contents

630	Embedded Self-Powered Microsensors for Monitoring the Surety of Critical Buildings and Infrastructures
632	Photonic Lattice Coatings
633	Applicability of a Self-Referencing Shearing Interferometric Vibration Detector
635	Small-Scale High-Performance Optics
638	Terahertz Radiation Technology for MASINT
640	Radar Tag for the Remote Monitoring of Restricted Equipment
643	Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System
644	Conceptual Design of Self-Adjusting Inertial Inmate Restraints
646	Miniaturized Sensor Technologies for Drug Detection
649	The Development of Polymer-Based Antitamper Systems
651	Network-Enabled Firmware
652	Indications and Warnings in the Cyber Domain
653	Cognition-Driven Augmented Analyst

Pulsed Power Sciences

655	Use of Intense Ion Beams for Surface Modification and Creation of New Materials
657	Low-Intensity Laser Triggering of Spark Gaps
659	Enhanced Impulse Experimentation Capability
661	Z-Pinch Power-Plant System Development

664	Recyclable Transmission Line Concept for Z-Pinch IFE
665	Suppression of Electron Emission from Conductors
667	Solid-State Switch for Advanced Pulsed Power
669	Isentropic Compression Experiments on the Saturn Accelerator

Corporate Objectives

672	An Optically Triggered Semiconductor Switch for Firing Systems
674	Information Extraction from Hyperspectral Images Obtained from Satellites
676	Capillary Elastohydrodynamics in Manufacturing Processes
678	Ultraminiaturization of RF Circuitry
681	An Actuator Based on an Electrokinetic Pump
684	Laser-Assisted Microgas Metal Arc Welding
687	Ultrahigh-Resolution Radiography for Detailed Inspection of Weapon Components and Systems
689	Surface-Micromachined Mechanical Timer
692	Pseudostationary Separation Materials for Highly Parallel Microseparations
695	Novel Coatings for Microelectromechanical (MEM) Devices
699	DNA Microarray Technology
701	Shock Response of Diamond Crystals
703	Investigation of Nanoscience Technologies

Table of Contents

704	Magnetic Polysilicon MEMS Devices	738	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture
707	Theoretical Study of Sb as a Surfactant in Epitaxy of III–V Materials	740	Microcontact Printing of Nanoparticle Arrays
709	Single-Wire Explosion Experiments	742	Mathematical Analysis of Deception
712	Scattering from Nanostructured Materials	743	A System Dynamics Approach to Modeling Water Demand
715	The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	745	Controlling Contamination in Precision Mirrors by Surface-Capping Modifications
716	A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	748	Chip-Based Optical-Cell Manipulation
718	Magnetically Insulated Power Flow Experiment	750	Advanced Particle Control for Electric-Discharge Light Sources
720	Molecular Self-Assembly	752	Wireless Infrastructure Data-Transmission System
722	Molecular Simulations of MEMS Coatings	754	MEMS–Based Electromechanical Acoustic Energy Harvester
723	Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches		
725	Fundamental Studies of Water-Surface Interactions	755	Appendix A Project Number/Title Index
728	Biomimetic Chloroplasts: An Integrated Micro-device Power Source	767	Appendix B Awards/Recognition List
730	Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves	768	Appendix C Project Performance Measures
732	Scanning Tunneling Microscopy of Silicon-Based Nanostructures	783	Appendix D DOE Critical Technologies
733	Self-Assembly of Polymers in Confined Geometries	800	Appendix E Major National Programs
735	Building Conscious Machines Based on the Primate Brain	818	Appendix F Dual-Benefit Areas and Single-Area Categories

“... exceptional service in the national interest.”

Science and technology are the heart of the United States industrial competitiveness, national security, energy resources, environmental quality, and leadership in fundamental and applied science.

At Sandia, the Laboratory Directed Research and Development Program provides the knowledge that drives our future. We initiate research and development that spawn the knowledge that revolutionized technology. Areas of emphasis center on our core technical competencies and the major strategic thrusts of Sandia's Institutional Plan. Leading-edge experiments that validate our work are constructed and operated on schedule, within budget, and in a safe and environmentally responsible manner.

Our work continues to produce many scientific and technological breakthroughs that lead to new technologies, markets, and businesses for the nation.

To all those who have contributed so generously of their time and talent, thanks and congratulations for a job well done.

Supporting National Security Through Science and Technology

Ambassador C. Paul Robinson

President

Sandia National Laboratories

*Sandia National Laboratories FY 2002 LDRD Program Review
July 12, 2001*

At a recent budget hearing for the Senate Armed Services Committee (SASC), Senator Reed of Rhode Island asked, “I keep hearing a lot about LDRD, that it’s been very much a source of contention. What’s all the fuss about?” The three Department of Energy (DOE) National Nuclear Security Administration (NNSA) laboratory directors in attendance (Bruce Tarter [Lawrence Livermore National Laboratory], John Browne [Los Alamos National Laboratory], and myself, C. Paul Robinson [Sandia National Laboratories]) talked extensively about LDRD as being “...the lifeblood of the Laboratory.”

The history of LDRD goes back to the Manhattan Project period when the decision was made to establish what are now the DOE NNSA labs. The question was, “What can we do, now that we’ve assembled the top scientists, to make sure that the defense of this nation will always remain in the hands of scientists who are at the top of their game?” The answer was to give creative people some freedom to have ideas, to think new thoughts, and to create the leading edge perpetually. Those decision-makers believed that such opportunities would keep the researchers at the top of their game and, along with that, increased national security would be the result.

When LDRD was first incarnated as the Weapons Supporting Research Program, funding levels were authorized up to one-third of the Lab budget—one-third was controlled at the discretion of the laboratory. However, by the time I arrived at Los Alamos National Laboratory (LANL) in 1967, discretionary funding was down to twenty percent.

When compared to the various industries that invest in research and development (R&D), the DOE LDRD Program funding level ranks quite low. For example, the highest discretionary R&D budgets are around thirty-five percent and are typically found in the software industry. Many electronics firms’ R&D budgets are at the twenty percent level. Dr. Al MacLachlan, who was at the DOE briefly and was also the former Chief Technology Officer at DuPont, makes the point

The history of LDRD goes back to the Manhattan Project period The question was, “What can we do, now that we’ve assembled the top scientists, to make sure that the defense of this nation will always remain in the hands of scientists who are at the top of their game?” The answer was to give creative people some freedom to have ideas, to think new thoughts, and to create the leading edge perpetually.

that at DuPont Research Laboratory, discretionary R&D funds remain at twenty percent. At the lower range of R&D investment, cement aggregates and bulk materials organizations may fund R&D at the two percent level. These percentages help illustrate that the fiscal year 2000 (FY 2000) reduction in the LDRD Program (from six percent to four percent) was a real problem for maintaining the world-class R&D at the DOE labs.

When I arrived at Los Alamos, one of the favorite phrases left over from Enrico Fermi's time at Los Alamos was, "...it's not worthy of being called an experiment unless it's got at least a fifty-percent chance of failing." Failure is how you move most quickly through the scientific method. R&D is trial and error, and that's what we are about.

I made a pitch to the senators on the SASC for what I think could improve government funding in general. I explained that no one today would dare fund a project that only has a fifty percent chance of succeeding. In fact, you hardly hear anybody talk about experiments. I can say that, fortunately, the DOE NNSA organization is a delightful exception. This is in stark contrast to many organizations that focus almost entirely on demonstration projects. In today's environment, that's what people want to fund—something that's a sure success. You can get that kind of short-term success, but you take tiny, tiny baby steps, and you don't move to the dramatic stretches of the science, the stretches of the mind, to do something new.

We held interesting sessions with Dr. Millie Dresselhaus at last December's Science Day at Sandia. Dr. Dresselhaus conducted focus groups with a cross-section of the Labs' technical staff, including fresh graduates who've just come to the Lab, post-docs, as well as some mid-career people. The purpose of the focus groups was to get feedback on the scientific health of our institution. We were praised for the attitude about LDRD; however, the participants said that the process is bureaucratic.

The LDRD process is bureaucratic, but it does provide some sense to a process that, at its heart, is impossible. If you look at the history of LDRD at Sandia, the potential requests for proposals would outspend the monies available by a factor of fifteen. So one of the first things we did was put an extra step into the process to say, "Please don't waste a lot of time writing big proposals." This pre-proposal stage encourages people to submit a short précis of what's proposed—this helps us determine what new ideas are the best of the best. Of

These percentages help illustrate that the fiscal year 2000 (FY 2000) reduction in the LDRD Program (from six percent to four percent) was a real problem for maintaining the world-class R&D at the DOE labs.

course, the “losers” in the process are unhappy, but at least we’re more efficient with the time spent in the proposal process without sacrificing the quality of proposed research.

In addition, we added another component that has certainly complicated and put more bureaucracy into the process. I claim, however, that this component of our LDRD Program is an enormous success—the Grand Challenge projects. Grand Challenges are about team research, about multidisciplinary research, about doing something that no individual researcher could accomplish alone. Universities have the problem of how to teach students to work effectively in teams. Our Grand Challenges incentivize people to get together to take on things that are much bigger than they could ever attempt on their own. Blending large ideas together with a lot of specialties is important for us and, I believe, important for the country.

In order to be considered as a Grand Challenge, a proposal must meet two essential tests (among others):

- The proposal must engage multidisciplinary teams across the Labs.
- The proposal must address technical areas that are vital to the core purpose of the Labs.

It is not a question of “If you succeed, will the results be used?” The results (of Sandia’s research) will be used and they will revolutionize the nation’s national security.

Grand Challenges are about team research, about multidisciplinary research, about doing something that no individual researcher could accomplish alone. ... Our Grand Challenges incentivize people to get together to take on things that are much bigger than they could ever attempt on their own. Blending large ideas together with a lot of specialties is important for us and, I believe, important for the country.

An Overview of Sandia's FY 2001 Laboratory Directed Research and Development (LDRD) Program

B. K. Cloer

"It is not a question of 'If you succeed, will the results be used?' The results (of Sandia's LDRD research) will be used and they will revolutionize the nation's national security."

*Ambassador C. Paul Robinson
President, Sandia National Laboratories
Sandia National Laboratories LDRD FY 2002 Program
Review, July 2001*

"Some of the most fundamental research that we have at Sandia, research that has an incredible payoff for the missions of the Labs, derives from the seeds sown in the LDRD Program."

*A. D. Romig, Jr.
Chief Technology Officer
Vice President for Science & Technology and Partnerships
Sandia National Laboratories LDRD FY 2002 Program
Review, July 2001*

Program Strategy

Sandia National Laboratories is a national resource that provides world-class science, technology, and engineering. The Laboratories' capabilities must remain on the cutting edge since the safety, security, and reliability of the U.S. nuclear weapons stockpile depend directly on them.

Sandia's LDRD Program supports the DOE's missions through Sandia's four primary strategic objectives: nuclear weapons, nonproliferation and materials control, energy and critical infrastructure, and emerging national security threats. To meet these objectives, LDRD promotes creative and innovative research and development that Labs' Director

FY 2001 Funding Levels (\$M)

FY 2001 Selected Statistics

Full-time Staff	304
Smallest Project (\$K)	4.5
Average Project (\$K)	244
Average Project (FTE)	1.03
Largest Project (\$M)	2.85
1st Year Projects	161
2nd Year Projects	79
3rd Year Projects	54
4th Year Projects	1

Ambassador C. Paul Robinson says "...has significantly strengthened Sandia's ability to fulfill its mission for the DOE."

Sandia's LDRD Program provides the flexibility to invest in long-term, high-risk research activities that attract the best research talent from across the Laboratories. LDRD research provides an opportunity for this talent to explore innovative scientific and technological opportunities that hold high potential for payoff in future applications. As a result, LDRD advances strengthen Sandia's science and technology base and provide considerable support to DOE and the Laboratories' mission needs.

Authorized by federal law and implemented under DOE under DOE Order 413.2A, LDRD is Sandia's sole source of discretionary research funds. In FY 2001, over 95 percent of Sandia's LDRD projects provided benefits in basic and applied research to meet national security challenges.

Program Performance

The FY 2001 LDRD Program funded 295 projects (selected from 1351 possibilities, including ideas and continuations) with a program allocation of \$70 million. The program was divided into five major investment categories (including subdivisions):

- **Science and Technology** (Advanced Manufacturing, Biotechnology, Computational and Information Sciences, Electronics and Photonics, Engineering Sciences, Materials Science and Technologies, Pulsed Power Sciences)
- **Mission Technologies** (Energy and Critical Infrastructure, Emerging Threats, Nonproliferation and Materials Control)
- **Grand Challenges**
- **Advanced Concepts**
- **Corporate Objectives**

Sandia's LDRD Program utilizes several types of measures to identify research performance, including

- Quality of science, technology, and engineering
- Relevance to national needs and agency missions
- Quality of research management.

Quality of science is indicated by expert advisory committees, peer reviews, sustained progress, and recognition

by the scientific community. Relevance is indicated by sustained advancement of fundamental science and advances in support of missions. The quality of LDRD research management is indicated by well-developed research processes, established project goals and milestones, and effective decision making in managing and redirecting projects.

Sandia LDRD received significant scientific recognition from industry, government, and professional societies in FY 2000 (the latest year for complete results). In FY 2000, two of the six DOE Office of Basic Energy Sciences (BES) Awards were awarded to two Sandia LDRD-related activities: “Nanocluster Catalyst” (FY 1996 project number 3539.270) and “Direct Fabrication of Multifunctional Nanocomposites Via Supramolecular Self-Assembly” (FY 2000 project number 10406). In addition, citation analysis provides a measure for the impact of LDRD research advancement. In 2000, Sandia LDRD journal articles across all fields represented 18 percent of all Sandia articles, and over the past five years, Sandia LDRD journal articles outranked overall-Sandia articles in terms of relative impact: 1.57 to 1.29 (as measured by the ISI’s [Institute for Scientific Information] Science Citation Impact database).

Each foundational LDRD investment area maintains external review boards to provide feedback on research quality. As an example, LDRD Electronics and Photonics research results were externally peer-reviewed by the Microelectronics and Photonics External Review Panel on October 1–3, 2000. An excerpt from the Panel’s report is

- “...The panel reviewed...photonic crystals, gallium nitride (GaN) science, chemical and biological sensors, radiation-hard microelectronics for weapons and satellite applications and facilities operations. The presentations established a compelling basis for an outstanding rating...”

External reviews also provide important perspective and recommendations on the relevance of LDRD research. As an example of relevance, the Microelectronics and Photonics External Review Panel highlighted the support of LDRD research to the Labs’ missions:

- “...In summary, the Microelectronics and Photonics capabilities at Sandia provide the opportunity to deliver exceptional service to the nation in broad areas and in changing times...”

FY 2001 Performance

Refereed Publications	267
Other Communications	197
Patent Disclosures	98
Patent Applications	59
Patents	7
Copyrights	10

... two of the six DOE Office of Basic Energy Sciences (BES) Awards were awarded to two Sandia LDRD-related activities: Nanocluster Catalyst and Direct Fabrication of Multifunctional Nanocomposites Via Supramolecular Self-Assembly.

The Sandia LDRD Program has developed a process that encourages Labwide participation (i.e., involves executive leadership, program directors, and research staff throughout the Labs) to produce new knowledge with long-term benefits. Because research outcomes are frequently unpredictable, targeted levels of research performance and milestones cannot be 100 percent specified beforehand. However, research goals and milestones are established for each project to inspire extraordinary levels of innovation from the research teams and staff. As such, each project team is encouraged to create a deliberate mismatch between the group's research aspirations and its present knowledge and resources.

The Sandia LDRD Program has been tracking the number of completed milestones and the number of goals met since the early 1990s. Project milestones are determined for every \$300K of funding and identify specific accomplishments in the progression of research. Goals refer to certain capabilities that are desired within the overall framework of a project's research activities. In scientific inquiry, meeting all of the intended goals indicates that the research challenges have been set too low.

From FY 1996 through FY 2000, LDRD projects maintained a risk balance that resulted in a 69 percent average completion rate for milestones and a 51 percent average rate for goals met. In addition, the percentage of research goals met has declined over the past four years. This provides an indication of the high level of "stretch" anticipated by LDRD participants in their research activities.

FY	Completed Milestones	Goals Met
FY96	72%	69%
FY97	72%	50%
FY98	69%	45%
FY99	66%	40%
FY00	67%	50%

Additional Reading

A comprehensive discussion of DOE and Sandia's LDRD Program management and funding sources may be found in the "Sandia National Laboratories FY 2001–2006 Institutional Plan," dated December 2000.

The Sandia LDRD Program has developed a process that encourages Labwide participation (i.e., involves executive leadership, program directors, and research staff throughout the Labs) to produce new knowledge with long-term benefits. ... research goals and milestones are established for each project to inspire extraordinary levels of innovation from the research teams and staff. As such, each project team is encouraged to create a deliberate mismatch between the group's research aspirations and its present knowledge and resources. ... In scientific inquiry, meeting all of the intended goals indicates that the research challenges have been set too low.

The LDRD Program's Impact on Sandia's Science and Technology

*A. D. Romig, Jr.
Chief Technology Officer
Vice President for Science & Technology and Partnerships
Sandia National Laboratories
Sandia National Laboratories FY 2002 LDRD Program Review
July 12, 2001*

Some of the most fundamental research that we have at Sandia, research that has an incredible payoff for the missions of the Labs, derives from the seeds sown in the LDRD Program. Investments made ten and fifteen years ago in the LDRD Program are having a direct impact on the weapons program today. At the time when those investments were made, you would not have been able to make the connection between research activity and future programmatic application. But, it is now clear that those investments have developed the technical base for the Laboratories today and will continue to meet the needs of the nation as we go forward into the future.

Funding Research Priorities for a National Security Laboratory

Sandia is a national security laboratory. Our nuclear weapons mission accounts for over half of the work at the Labs and truly defines our being. All other program areas draw from, as well as contribute to, the weapons work at the Labs. Similarly, Sandia's LDRD Program investment priorities reflect our strong emphasis of support to the weapons mission of the Labs. The Science and Technology (S&T) investment areas (IAs) identify research with a strong coupling to the nuclear weapons program and account for nearly half (i.e., 46.1 percent in FY 2002) of the LDRD annual budget. The Mission Technologies IAs (i.e., Energy and Critical Infrastructure, Nonproliferation and Materials Control, Emerging Threats, Differentiating Technologies) support the other national security business areas of the Labs and account for a little more than one-third (i.e., 36.3 percent in FY 2002) of annual LDRD funding commitments.

The research portfolio for the S&T IAs of the LDRD Program emphasizes S&T innovation that supports the nuclear weapons stockpile. For example, investments are determined

Some of the most fundamental research that we have at Sandia, research that has an incredible payoff for the missions of the Labs, derives from the seeds sown in the LDRD Program. Investments made ten and fifteen years ago in the LDRD Program are having a direct impact on the weapons program today. ...

Our nuclear weapons mission accounts for over half of the work at the Labs and truly defines our being. All other program areas draw from, as well as contribute to, the weapons work at the Labs.

for very basic research in disciplines, including materials, engineering sciences, and nanotechnology, among several other areas. For some research investments, the path from science to mission can be very long—perhaps a twenty-year timeframe to useful adoption. And, of course, there are many ideas that initially seem to have a lot of promise but do not survive the trip to eventual application.

In general, however, the basic research efforts produce results with times to useful adoption of nominally five to ten years. Results stemming from basic research are often integrated to develop technology with shorter times to useful adoption—approximately two to five years. As a result, we are continually evaluating research efforts to cultivate, nurture, and mature results to the point where they may be identified for the insertion path into weapons and other national security applications.

In addition, we make an effort to identify some crosscutting research efforts between technical disciplines (such as our research efforts with integrated microtechnologies) to advance our Microsystems and Engineering Sciences Applications (MESA) capabilities. We believe that the high functionality of integrated microsystems will enable new capabilities and applications that will revolutionize the capabilities of the nuclear stockpile while increasing its safety, security, and reliability.

These very small, highly integrated, and low-power microtechnologies are created using integrated circuit fabrication technology that allows the combination of diverse functions on a single chip. Integrated microsystems may include combinations of sensors, miniature communications, microelectronics for on-board processing, and microelectromechanical systems (MEMS) that integrate gears and action elements fabricated from silicon compounds. In the future, integrated microsystems will streamline the number of weapon components, reduce production and maintenance costs, and minimize the number of fault points in the weapons system.

Grand Challenges (GCs) investments are a key element of Sandia's LDRD Program strategy. These investments enable us to assemble multidiscipline project teams to focus on solutions to significant national-level problems and capabilities. The GC investments receive about ten percent of the program funding and are Sandia's largest LDRD projects. Competition among potential GC proposals is very high. The Labs' Mission Council collaborates each year to make the

... the basic research efforts produce results with times to useful adoption of nominally five to ten years. Results stemming from basic research are often integrated to develop technology with shorter times to useful adoption—approximately two to five years. ...

In addition, we make an effort to identify some crosscutting research efforts between technical disciplines (such as our research efforts with integrated microtechnologies) to advance our Microsystems and Engineering Sciences Applications (MESA) capabilities. ...

Grand Challenges (GCs) investments are a key element of Sandia's LDRD Program strategy. These investments enable us to assemble multidiscipline project teams to focus on solutions to significant national-level problems and capabilities.

recommendations for the forthcoming fiscal year's GC projects. Their recommendations assess the high-risk, high-payoff proposals based on their potential for impacting a Sandia mission or national needs area. Sandia's μ ChemLab™ is an example of a successful former GC project that has progressed the full cycle from research to applications.

Two LDRD Program IAs that receive small funding amounts are the Advanced Concepts and the University Collaborations IAs. Advanced Concepts investments consider technical approaches to counter threats that the world and the nation will face over the next decade or two. These very out-of-the-box research activities are unique not only due to the kinds of problems being addressed but also because, in some cases, there are not yet established any programmatic frameworks in which to address the problems. For example, how do we prepare for threats before there is an awareness of their damage potential or before there is an organizational structure tasked to address it? This is an important focus of the Advanced Concepts IA.

Currently, there is no governmental organization tasked with creating technologies as a way to solve water problems and to mitigate conflict. You might ask, "Why do we want to worry about water?" Many political scientists point out that over the next ten to fifteen years, water is as likely (perhaps even more likely) to drive conflict and warfare than are oil or energy. The Advanced Concepts IA is a tool for the Labs to address such threats by capturing them within an overall scientific and technological construct.

With the great explosion of scientific and technologic advances in recent years, we realize that a lot of our research activities cannot be accomplished alone. The University Collaborations IA has been created to explore science and technology areas through collaborations with cooperating universities. Sandia recognizes that much expertise in emerging sciences and technologies presently lies with universities and industrial organizations. Thus, University Collaborations research activities provide access to world-class, external resources that Sandia requires in order to develop critically needed research and technical capabilities for the future.

Sandia's μ ChemLab™ is an example of a successful former GC project that has progressed the full cycle from research to applications. ...

With the great explosion of scientific and technologic advances in recent years, we realize that a lot of our research activities cannot be accomplished alone.

The Future of LDRD

What is the future of LDRD? Before commenting on the future, perhaps it would be helpful to briefly review the recent past. Looking back to the late 1960s, Sandia was making decisions about where it thought the future was going to go. It was clear then that microelectronics would have a key role in how weapon systems would evolve. As a result, Sandia made investments in various microtechnologies that laid the foundation for our expertise in radiation effects in solids (i.e., that led to the development of rad-hard microelectronics), microoptics, MEMS, sensors, etc. In fact, today we believe that all of these and other similar advances are going to create continued advancements and lead to entirely new ways of meeting the needs of the stockpile and other national security missions through MESA capabilities.

Consistent with the past research strategies, we believe that the LDRD Program is critical for determining current investments that the Labs will be able to capitalize on in the future. We are investing now in the emerging fields of biotechnology, nanotechnology, and information technology, and especially in the interface of how these disciplines come together. As an example, self-assembly processes (which have been a focus of LDRD investments since the mid-1980s) are very much related to fundamental chemical and biological mechanisms and provide powerful methods for fabricating nanoscale devices with great precision. Our evolving knowledge of self-assembly processes will lead to the creation of new generations of miniature devices and systems. In the future, I believe that self-assembly techniques will be used in stockpile rebuilds and in the development of other national security systems. In fact, our μ ChemLab™ technology already uses self-assembly techniques to construct materials and devices to specific requirements.

We are often asked, “How will biotechnology impact the weapons program.” One current example is the extension of massively parallel computing architectures used in weapons modeling and simulation activities (i.e., based on research that began in LDRD) into various biotech investigations. Other than the nuclear weapons program, the big computational challenges today are being addressed in the genomics and proteomics biotech areas. Leveraging the investments and innovations in these bio areas can support the computational technology required by our weapons program. In fact, our investigations into computational technology recently led to

We are investing now in the emerging fields of biotechnology, nanotechnology, and information technology, and especially in the interface of how these disciplines come together. As an example, self-assembly processes (which have been a focus of LDRD investments since the mid-1980s) are very much related to fundamental chemical and biological mechanisms and provide powerful methods for fabricating nanoscale devices with great precision. ... Our evolving knowledge of self-assembly processes will lead to the creation of new generations of miniature devices and systems.

the Cooperative Research and Development Agreement (CRADA) between Celera, Compaq Computer, and Sandia. This collaboration will produce a scalable computer architecture that will yield the world's fastest general-purpose supercomputing design: 10 teraflops by 2002, 100 teraflops by 2004, and ultimately, one petaflop.

As another example, a new Sandia Grand Challenge project for FY 2002 will investigate the application of biotechnology to develop small power sources and fuel cells for portable applications. Today's warfighter carries around approximately sixty pounds of batteries to power his equipment. Imagine the benefits to the warfighter if we could reduce the weight of those batteries by supplementing or replacing them with biological microfuel cells for powering the equipment. Such fuel cells would utilize body fluids (i.e., glucose) to support power generation. To make this work, however, we are going to need incredible advancements in membrane technology. Eventually, fuel cells might be a better choice for the stockpile than lithium batteries, but we cannot prove that without the right kind of membrane technology—and that technology may first be developed in the biotechnology arena.

*The LDRD Program
investments prioritize research
to serve the nuclear weapons
mission while building
competencies for anticipated
future national security needs.*

The LDRD Program Is Critical to the Future of the Labs

Other than technology, the crucial benefit of our LDRD Program is people—I do not want us to lose sight of this. Two young staff members recently told me that the LDRD Program is one of the reasons they stay at the Labs. While other research organizations have attempted to lure them away, they stay partly because they like the people and the facilities here. But most importantly, they told me, through the LDRD Program they get to do the kind of research they want to do, and the results of this research impact the future of the nation. The work we do at Sandia, and especially in the LDRD Program, attracts talented people like these young staff members that fuel the capabilities of the Labs.

Without a doubt, the LDRD research activities are absolutely critical to the future of the Laboratories. Through LDRD investments, we conduct research to ensure that the right S&T are available and provide the differentiating strengths to meet Sandia's mission needs. The LDRD Program investments prioritize research to serve the nuclear weapons mission while building competencies for anticipated future national security needs.

An Overview of the Electronics and Photonics (E&P) Investment Area

Marion Scott

Deputy, Microsystems Science, Technology and Components Center

Sandia National Laboratories

Sandia National Laboratories FY 2002 LDRD Program Review

July 13, 2001

The Electronics and Photonics (E&P) LDRD investment area (IA) prioritizes research that expands the Labs' capabilities for creating next-generation, integrated microdevices and microsystems. These research activities draw upon the Labs' differentiating strengths and will enable the Labs to develop future advanced systems for achieving its national security missions. In particular, E&P research advances will help us to continue to ensure the safety, security, and reliability of the nation's nuclear weapons stockpile.

The future of microsystems points to an even higher degree of integration to create systems that are very small, require less power consumption, and are very low cost to manufacture. These new systems will ultimately contain sensing, processing, mechanical actuation, and communications on a single chip. Because of their low cost and high functionality, these integrated microsystems will help us realize entirely new systems and applications.

The Integrated Solutions thrust of the E&P IA addresses innovative approaches to achieving higher levels of integration as well as mixed technology integration. We encourage research ideas that address advanced packaging, thermal management of microsystems, micro-integrated power supplies, and integrated photonic systems. Approaches to radiation hardening and other requirements to ensure rugged performance of integrated microsystems in abnormal environments are also sought. An example of a success of this research thrust is our photonics crystal research that improves optical waveguides for communications applications.

Our other E&P research thrust, Microdevices, invests in technologies with the potential to impact the Labs' strategic businesses' and weapons' needs in a three- to five-year timeframe. We seek new concepts with the potential to advance microelectronics, photonics, mechanical actuation, and sensing capabilities. A specific focus area within the Microdevices thrust is on concepts that couple functional

The Electronics and Photonics (E&P) LDRD investment area (IA) prioritizes research that expands the Labs' capabilities for creating next-generation, integrated microdevices and microsystems. These research activities draw upon the Labs' differentiating strengths and will enable the Labs to develop future advanced systems for achieving its national security missions.

materials, nanotechnology, and microscale fabrication to develop revolutionary new microsystem architectures and functions. An example of a success is our investments in strained-layer superlattice devices, and new materials-based components have led to the creation of new laser devices composed of indium gallium arsenide nitride. In addition, we are beginning to research silicon-on-insulator (SOI)-based microelectromechanical systems (MEMS) devices.

Often, the results of our E&P research have had multiple applications. As an example, we originally developed chemiresistor technology for weapons' applications. Recently, we explored the use of this technology to examine subsurface water quality. In addition, chemiresistor technology was integrated into the world's smallest autonomous robot to enable onboard chemical sensing. These microrobots are useful for mobile, distributed sensing applications and can go where human beings either cannot or do not want to go.

Another example of LDRD innovation that has multiple potential applications is our research in optical switching MEMS devices. Microoptical switches have exciting potential in commercial communications applications as well as for various applications aligned with the Labs' business areas. Optical switches are an enabling element for future optically controlled synthetic-aperture radars as well as for nanosatellite communications.

Sandia's LDRD Program provides the opportunity to fund the initial research efforts in a number of promising technology areas. The results of the research have produced numerous electronics device and system concepts and have supported a number of applications consistent with the Labs' business areas. These research investments are helping us develop our microsystems capabilities to address the critical national security issues of the twenty-first century.

Microoptical switches have exciting potential in commercial communications applications as well as for various applications aligned with the Labs' business areas.

Optical switches are an enabling element for future optically controlled synthetic-aperture radars as well as for nanosatellite communications.

An Overview of the Engineering Sciences Investment Area

Thomas C. Bickel

Director, Engineering Sciences Center

Sandia National Laboratories

Sandia National Laboratories FY 2002 LDRD Program Review

July 13, 2001

I want to provide a threefold introduction to Sandia's Engineering Sciences Research Foundation (ESRF) efforts by way of a philosophical overview, a description for the research portfolio (which includes an external review process), and a perspective for what research activities we envision for the future. The ESRF efforts are guided by research plans across multiple technical disciplines. An important aspect of addressing the goals of these plans is cooperation with other organizations, both internal to and external to Sandia. It has been our experience that the increase in funding in other technical areas, especially the health sciences, has led to a rapid decline in the interest of graduate students to work in the physical sciences. As a result, collaborations with the National Science Foundation (NSF) and other organizations have helped maintain our conduit of highly skilled and motivated young scientists and engineers.

Engineering Sciences is one of Sandia's core competencies that provide critical technical underpinnings to support our missions. The ESRF research activities are conducted through two programs: the Engineering Sciences (ES) LDRD investment area (IA) research explorations, and the DOE Defense Programs (DP) technology base work. A fundamental difference between these two activities is the time scale for useful adoption of the research results. The LDRD investments address more fundamental research efforts that have the potential to produce results applicable to product development within a three- to five-year timeframe. The LDRD results roll into the more focused work of the DP tech base efforts and are ultimately incorporated into our missions' base.

The Engineering Sciences LDRD investment thrusts include (1) advances in scientific theory, (2) advances in material/constitutive models, (3) advances in numerical algorithms and methods, (4) explorations in experimental discovery, and (5) experimental diagnostics development. As examples of emphasis for these thrusts: in the novel numerical

*Engineering Sciences is one of
Sandia's core competencies
that provide critical technical
underpinnings to support our
missions.*

algorithmic thrust, we are exploring large-deformation solid-fluid interactions via a level-set approach and structural simulations using multiresolution material models. In our advancing diagnostics techniques thrust, we are investigating filtered Rayleigh-scattering diagnostics for multiparameter thermal/fluids measurements.

We have had fifty years to understand continuum engineering mechanics and science. In FY 2002 and in the future, ES LDRD investments will concentrate on new investigations at the micro- and nanoscales to address the area of noncontinuum mechanics. These investigations will draw on past research results and understanding but will now be extended by fundamental discoveries to the micro- and mesoscales. Past knowledge will be coupled with new knowledge to support our mission space. For example, we still seek to better understand what fire is (i.e., a multimeter phenomenon), but we will now also seek to understand it down to the microscale.

New starts for FY 2002 ES investments will also include investigations into creating high-fidelity friction models for MEMS (microelectromechanical systems). We will examine the broad concept of how stiction in MEMS devices affects performance. We will also develop microscale models to improve prediction of thermal transport across open or slightly open joints in MEMS devices. This research will have an important impact on the future deployment of MEMS devices in a number of mission-related areas.

One ES research success that is having an impact on a Labs mission area is illustrated by an example addressing the need for protecting weapons in a fire. To be able to understand an abnormal environment (e.g., fire), we have to understand the fundamentals of the environment. In a recent LDRD research effort, we investigated a number of novel diagnostic techniques that had the potential to address the radiosity of soot development in a fire scenario. We transitioned one discovery of this LDRD effort, a bench-scale laser-based technique, into a DOE Defense Program research effort that was eventually used in an actual JP4 jet-fuel fire scenario. The fundamental technique originally developed in LDRD has been further refined and incorporated into the MAVEN (Model Accreditation Via Experimental Sciences for Nuclear Weapons) Program to address data validation applications.

It is important to emphasize that the ESRF management team is managing ES research and development throughout the entire R&D spectrum. We annually present the R-D-A

We will also develop microscale models to improve prediction of thermal transport across open or slightly open joints in MEMS devices. ... ES LDRD investments will concentrate on new investigations at the micro- and nanoscales to address the area of noncontinuum mechanics. These investigations will draw on past research results and understanding but will now be extended by fundamental discoveries to the micro- and mesoscales. Past knowledge will be coupled with new knowledge to support our mission space ... One ES research success that is having an impact on a Labs mission area is illustrated by an example addressing the need for protecting weapons in a fire.

(research to development to application) spectrum of our ES activities for review by an external panel of experts. We earned excellent grades from the panel in the most recent review of our ES research and Accelerated Strategic Computing Initiative (ASCI) programmatic efforts. In the future, we plan to host panels every six months and to alternate between the ASCI and ESRF topics.

One of the principle challenges we face with ES research is to keep pace with the tremendous advances that are being made in computational speed. Faster computational hardware is outstripping our fundamental understanding of the ES. At Sandia, we are now producing simulations of between 50 and 100 million three-dimensional high-fidelity finite elements. To put that in perspective, ten years ago we were doing two-dimensional simulations on 10,000 finite elements. As we go forward, the very fundamental underpinnings of our mission-related systems (e.g., numerical algorithms, phenomenological science) are being investigated and expanded by Sandia's LDRD research efforts.

... we are now producing simulations of between 50 and 100 million three-dimensional high-fidelity finite elements. To put that in perspective, ten years ago we were doing two-dimensional simulations on 10,000 finite elements.

An Overview of the Materials Science & Technology (MS&T) Investment Area

Julia Phillips

Director, Physical and Chemical Sciences Center

Sandia National Laboratories

Sandia National Laboratories FY 2002 LDRD Program Review

July 12, 2001

Due in large part to the impressive advances made in techniques and technology since 1990, the future is very bright for materials science and technology—at Sandia, the LDRD Program has had a lot to do with those advances. As examples, the sensitivity of analytical tools (in terms of resolution and the size of signal) has increased by a factor of 10^3 . Computational power has increased by 10^6 and enables us to address materials problems that we could not approach before. That is why some of Sandia's most exciting LDRD projects are in the materials modeling and simulation areas.

The Materials Science & Technology (MS&T) investment area (IA) of Sandia's LDRD Program prioritizes research by three core thrusts, including

- Aging and reliability of materials
- Materials processing
- Scientifically tailored materials.

Two additional crosscutting research themes have become increasingly important in the last few years, including nanoscale science and technology (S&T) for microsystems, and materials and process modeling.

The objective of the materials aging and reliability research thrust is to advance our capabilities for predicting materials properties as a function of time and operating conditions. Predicting materials properties, in turn, helps us to examine the future performance and reliability of high-consequence components and systems. Essential to this understanding are our investigations of bulk materials degradation, information extraction and analysis, and advanced analytical technique development. Similarly, we seek advances in understanding surface and interface science, the science of localized corrosion, and nanotribology. Further, investigations in materials performance, interface reliability, and materials aging improve our materials modeling capabilities.

... the future is very bright for materials science and technology—at Sandia, the LDRD Program has had a lot to do with those advances. As examples, the sensitivity of analytical tools (in terms of resolution and the size of signal) has increased by a factor of 10^3 . Computational power has increased by 10^6 and enables us to address materials problems that we could not approach before.

The objective of the materials processing research thrust is to improve the characterization and modeling of materials processing across all relevant length scales with the ultimate goal of process control, optimization, and true process-based quality. Processes of research interest include liquid metal processing, joining, thermal and cold spray, ceramics, and polymeric encapsulation. Process innovation supports our capabilities for modeling ceramics, welding, and solidification.

Our objectives in scientifically tailored materials research include drawing upon our scientific expertise to develop materials with unique properties that may be tailored for a broad range of applications. These research investments are high risk and high payoff and are generally focused on fundamental areas beyond current programmatic needs. For example, we are investigating the aging and reliability for MEMS lubricants, reactive wetting in solders and brazes, and copper segregation and aluminum grain boundaries and the interaction between grain boundaries and dislocations.

The crosscutting nano- and microscale research themes address

- Design principles for nanoscale assembly,
- Nano- and microscale materials and processes for microsystems, and
- Nanoscale diagnostics.

Design principles for nanoscale assembly has the goal of understanding new nanoscale assembly principles to enable synthesis and processing of functional nanomaterials with unique structures and revolutionary performance enhancements over existing materials. We are investigating materials of different functionalities (e.g., photochromic, switchable surface properties) as well as new approaches to nanoscale assembly—particularly, colloidal systems and templating. In addition, we are looking at fundamental issues, such as the structure of water near surfaces.

Our goal in nano- and microscale materials and processes research is to develop scientific understanding of novel classes of materials, structures, and processing techniques as enablers for microsystems. For example, we are studying amorphous diamonds, LIGA (the German term *Lithographie, Galvanoformung, und Abformung*, for lithography, electroforming, and molding) processing, and low-temperature cofired ceramic packaging. In addition, we are investigating

Our objectives in scientifically tailored materials research include drawing upon our scientific expertise to develop materials with unique properties that may be tailored for a broad range of applications.

the aging and reliability of materials in microsystems and how these materials behave when they are dormant for years or decades.

In our nanoscale diagnostics research, our goal is to develop and apply diagnostic tools for measuring physical, chemical, structural, and biological properties of materials and material systems at the nanoscale.

Overall, the MS&T research investment themes improve the capabilities required to support the missions of Sandia and the DOE NNSA (National Nuclear Security Administration). For example, the aging and reliability investigations develop our capabilities to support war reserve (WR) surveillance; materials processing research activities expand our tech base to support WR production and design efforts; and scientifically tailored materials increase our capabilities to support WR design. The crosscuts of nanoscale and materials and process modeling research develop the S&T base exploited by MESA (Microsystems and Engineering Sciences Applications) and ASCI (Accelerated Strategic Computing Initiative) applications.

In addition to DOE NNSA, MS&T research also develops our materials technical base to support a variety of DOE missions, including (among others):

- Aging research supports the Office of Power Technology investigations.
- Materials processing supports the Office of Industrial Technology explorations.
- Scientifically tailored materials expand our capabilities to address the Offices of Science (particularly Basic Energy Sciences [BES]) and Transportation Technologies investigations.

In our nanoscale diagnostics research, our goal is to develop and apply diagnostic tools for measuring physical, chemical, structural, and biological properties of materials and material systems at the nanoscale.

Advanced Concepts

The Advanced Concepts investment area is looking at how the United States might better “wage peace” by addressing global resource issues. At first glance, food production and water resources may appear to be outside Sandia’s scope; however, as world population grows and as global interdependence increases, the national security of the United States may well depend on reducing conflicts over resources. Sandia has skills and assets that can contribute technology-based system solutions to global resource problems.

The “Understanding and Managing Threats to the Social Fabric of the United States” project examines a subtle form of terrorism based on creating an acute, undesirable sentiment among major segments of U.S. citizens. This type of terrorism has the potential to have profound effects and could essentially cause the United States to be unable to provide for the common good of its citizens. The project will develop an understanding of the meaning of undermining the social fabric of our society, the potential threats, the warning signals, and the viable countermeasures. A panel of

experts discussed terrorist groups and identified the motivations, goals, likelihood of conflict, and timeframe for executing an event. A simulation model was developed during the meeting, capturing the essence of the various panelists’ discussions, arguments, and counterarguments.

21554

Solutions to National and Global Security Issues Based on Limited Freshwater Resources

M. E. Tadros, J. E. Miller, D. Y. Sasaki, R. W. Bradshaw

Systems-level solutions are needed to ease freshwater shortages in many regions throughout the world that could lead to conflicts and increased tension. The Department of Energy's (DOE's) Environmental Quality R&D Portfolio FY 1999–2001 states that one of the three primary areas of responsibility of the environmental-quality business line is to provide the technologies and institutions to solve domestic and international environmental problems. Scarce and contaminated water resources are a major environmental problem both in many parts of the U.S. and in areas of the world that are central to U.S. national security concerns such as the Middle East, Mexico, and China. The DOE is one of the lead agencies with responsibility to help create and maintain the scientific and technological infrastructure that supports the nation's security and environmental integrity. This project is focused on the development of two new methods for water desalination: a method for water-evaporation suppression from reservoirs and a method for improving protected agriculture to reduce water consumption.

We developed a conceptual design for a novel, high-efficiency desalination process that provides process heat based on distillation by direct-contact heat exchange between a saline water stream and a nonvolatile liquid. The heat-transfer coefficients for direct-contact boiling are much larger than comparable tube-wall heat-transfer coefficients. This method enables the dissolved solids in the saline water source to be collected by the working fluid, preventing the discharge of a concentrated brine stream. Since the cost of the sweeping gas alone is enough to make the economics questionable, we recommend that future work in this area focus on vacuum operation.

We carried out controlled experiments with two tomato plants grown in a conventional glass greenhouse and a greenhouse treated with the infrared reflective film, and collected data on the crop yield, energy consumption, temperature, humidity, and water consumption. The results are

We developed a conceptual design for a novel, high-efficiency desalination process that provides process heat based on distillation by direct-contact heat exchange between a saline water stream and a nonvolatile liquid.

very encouraging and support our design concept. We submitted a technology advancement disclosure.

We carried out laboratory and field (i.e., swimming pool) experiments to develop new surfactant composition for suppression of the evaporation of water. We found a mixture of fatty alcohols of various chain lengths to be superior to a mixture reported by others, particularly under conditions of wind and wave action. The new monolayer films exhibited high surface pressures, film recovery, and self-healing characteristics.

We analyzed the impact of technologies supporting sustainable development for the border region between the United States and Mexico. We evaluated and improved upon a solar water-distiller/water-purification technology and an early warning system for infectious disease outbreaks.

We analyzed the impact of technologies supporting sustainable development for the border region between the United States and Mexico. We evaluated and improved upon a solar water-distiller/water-purification technology and an early warning system for infectious disease outbreaks.

22126

Understanding and Managing Threats to the Social Fabric of the United States

J. Espinoza, J. G. Turnley, T. D. Moy

Terrorism is the use of force or violence against persons or property in violation of the criminal laws of the U.S. for purposes of intimidation, coercion, or ransom. One way governments attempt to reduce our vulnerability to terrorist incidents is by increasing security at airports and other public facilities. However, little attention seems to be given to a more subtle, yet potentially far more consequential, form of terrorism than bombing facilities and airlines—a form of terrorism based on creating an acute invidious sentiment among major segments of the citizenry of the United States. This has the potential to have far-reaching, profound effects and, if properly orchestrated, could essentially cause the United States to be unable to provide for the common good of its citizens.

This project will develop an understanding of the meaning of undermining the social fabric of our society, the potential threats, the warning signals, and the viable countermeasures. It should be emphasized that this proposed work is distinct from, but complementary to, Sandia's critical infrastructures surety activities. The focus will not be on what a malevolent agent might do to our infrastructures, but rather upon what might be done to cause major segments of the citizenry of the United States to violently interact with each other.

The innovative features of this work are (1) the synthesis of an integrated picture of the potential threats to our society as seen from myriad historically disparate perspectives, (2) the development of a dynamic simulation that can provide valuable insights into the complex phenomena that serve as the glue for our social fabric, and (3) the analysis of urban race riots of the sixties and seventies profiled via an artificial neural network (ANN) classifier that supports the development of the dynamic model and promotes the understanding of deliberate and planned attacks to break down the social fabric of our nation.

This project will develop an understanding of the meaning of undermining the social fabric of our society, the potential threats, the warning signals, and the viable countermeasures.

Sandia met several significant milestones in the development of this project:

- *Vital Issues Process II meeting.* Sandia hosted a panel discussion in Washington, DC, on 28 February 2001. The panel comprised a mix of national security experts, economists, social scientists, journalists, experts on aspects of the U.S. physical and communications infrastructure, and others aware of and/or sensitive to pressure or weak points in our social fabric, and how those weak points could be or have been manipulated. The panel discussed the potential for complete social infrastructure breakdown through the use of asymmetric warfare (IBAW).

The panel was divided into three groups, each of which was tasked with developing scenarios detailing the infrastructure breakdown of the United States according to the following categories:

- (1) Identification of infrastructure vulnerabilities
- (2) Development of scenarios for attacking vulnerabilities
- (3) Presentation of the scenarios
- (4) Critique of the scenarios in terms of feasibility and likelihood.

We produced a textual report documenting the discussions and outcomes of the VIP II meeting and summarizing the discussion, the themes that arose, and the IBAW scenarios. In view of the sensitivity of the issues, the report of the panel discussion is currently not available for public release or distribution.

We also developed a dynamic model in real time that reflected the panel discussion. PowerSim Constructor, a simulation model, was developed during the meeting to capture the gist of the various panelists' discussions, arguments, and counterarguments. We have since updated the model and modified it to properly reflect the outcome of the VIP II meeting.

- *Urban riot computer model (ANN classifier and predictor).* We are developing an urban riot computer model as a tool for policy- and decision-makers to assist them in identifying conditions that have historically been conducive to urban rioting. The software model will use socioeconomic, environmental, and public opinion conditions to classify the likely severity of an impending riot, thereby helping decision-makers countermand or prevent riots in their communities. The Advanced Concepts Group based the development of the riot-prevention computer model on an analysis of historical

The panel comprised a mix of national security experts, economists, social scientists, journalists, experts on aspects of the U.S. physical and communications infrastructure, and others aware of and/or sensitive to pressure or weak points in our social fabric, and how those weak points could be or have been manipulated.

data from the 500-plus race riots of the sixties and seventies. The Kerner Commission, established by President Johnson after a summer of violence and destruction in American cities, conducted the most thorough and reliable study of the 1960s urban rioting to date. We relied heavily on the findings of the Commission, which were published in April 1968 as “The Report of the National Advisory Commission on Civil Disorders.” The relevant riot parameters are being defined by the use of an ANN classifier that will filter conditions from hundreds of potential variables such as socioeconomic, environmental, and public opinion. An ANN predictor will be trained using the filtered data derived from the ANN classifier and tested against more recent riot events, such as the Los Angeles riots (1992) and the Cincinnati riots (2001).

The Kerner Commission, established by President Johnson after a summer of violence and destruction in American cities, conducted the most thorough and reliable study of the 1960s urban rioting to date.

Other Communications

Advanced Concepts Group, Sandia National Laboratories. 2001. “Infrastructure Breakdown Through the Use of Asymmetric Warfare.” Panel discussion consisting of national security experts, economists, social scientists, journalists, and experts on aspects of the U.S. physical and communications infrastructure, hosted by Sandia National Laboratories, Washington, DC, 28 February.

Moy, T. D., and A. L. Scott. 2001. “The Urban Riot Modeling Project.” Internal memorandum, Sandia National Laboratories, Albuquerque, NM.

32159

Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles

P. Van Blarigan, N. J. Paradiso, Jr.

Sandia has worked on transportation projects involving alternative fuels and new engine designs. We leveraged this experience to study the performance of several advanced power plants in a single-occupancy vehicle (SOV) for application in urban-transportation driving cycles. In parallel to this analytical study, we performed combustion experiments to assess the thermal-efficiency performance of a homogeneous-charge free-piston electrical generator of greatly reduced size. These experiments are necessary to assess the scaling effects necessitated by utilization in an SOV in comparison to a full-size automobile.

Sandia's accomplishments cover modeling and free-piston combustion performance.

Modeling. We used the Sparrow SOV as a baseline for application of various prime movers: electric, gasoline, diesel and methanol operation of conventional four-stroke engines, fuel cells operating on hydrogen and methanol, microturbines operating on natural gas, and free-piston electrical generators operating on methanol, gasoline, and natural gas.

We modeled each prime mover, when appropriate, with a conventional series hybrid and parallel hybrid drivetrain, with various power-plant sizes as an additional variable. We modeled each combination of engine and drivetrain on both urban- and highway-driving cycles.

The results indicate a large variation in performance, but clearly superior operation by hybrid drivetrains relative to the conventional baseline case. Small power plants (3 kW–7 kW) clearly have the advantage over the larger baseline unit (30 kW). The top performers were the diesel and free-piston motors.

Free-piston combustion performance. The approximately 1 kW output combustion experiment was intended to evaluate the performance of a free-piston generator at low-end size for an SOV. Sandia's current experience is with a 30 kW experiment; thus, confident interpolation between these two cases will be possible. We fabricated a combustion cylinder of 12 mm bore and 64 mm

... we performed combustion experiments to assess the thermal-efficiency performance of a homogeneous-charge free-piston electrical generator of greatly reduced size. These experiments are necessary to assess the scaling effects necessitated by utilization in a single-occupancy vehicle in comparison to a full-size automobile.

stroke. We instrumented the device with cylinder pressure and piston-displacement diagnostics, in addition to the support equipment necessary to measure fuel-to-mechanical-work efficiency. The device is a single-stroke experiment, similar to a 75 mm bore existing experiment.

Initial results indicate a 20 percent reduction (44 percent indicated thermal efficiency) from the 30 kW case. This reduction is thought to be due principally to an increased surface-to-volume ratio and larger crevice-volume fraction. The results, however, show that even at 1 kW, the concept is superior to other electrical-power generators.

The device is a single-stroke experiment, similar to a 75 mm bore existing experiment. ... The results, however, show that even at 1 kW, the concept is superior to other electrical-power generators.

32161

Micromachined Patch-Clamp Array

M. Okandan, S. M. Brozik, P. C. Galambos

A micromachined patch-clamp array that would enable real-time measurements and manipulation of cells has been described as the “dream” of a neurobiologist. This project will study the feasibility of realizing that dream. The completion of the Human Genome Project has set the stage to begin the hard part of the work—understanding the amazingly complex machinery of cellular processes and cellular signaling. The genome preserves and propagates the code for this machinery, but the code alone does not give us the complete insight into the details. To work out these details, and thus to learn about the origin and cure of diseases, disorders, and even aging, the biomedical community needs new tools such as the one investigated here. Such a tool will leverage the large investment that has been made in microsystems at Sandia over the last decade and provide the opportunity for establishing an entry point for utilizing the microsystems technology in the biological and medical sciences. Current techniques require extensive manual operation, and a repeatable, standardized setup for doing the measurements will enable a large set of new, fundamental, and exciting studies on cellular processes and cellular signaling.

We completed the first-round design of the micromachined patch-clamp array. These designs incorporate several different concepts: patch clamp or extracellular measurements, conductivity measurements, optical excitation/measurements, cell localization, and chemical delivery/extraction.

The cell localization area is the central focus of the designs. We placed polysilicon (poly-Si) electrodes below this region for the electrical/fluid-flow measurements. We routed other microfluidic channels to the backside of the wafer for connection to the mesoscale fittings and placed these microfluidic channels around the backside of the wafer to facilitate delivery and extraction of fluids/chemicals. We fabricated several different designs with poly-Si layers and are currently readying them for initial characterization. Designs using silicon nitride (SiN)—which allows electrical isolation of electrodes and optical access into the testing region—are being fabricated and will be tested as we finish processing.

3-D model of a design with five microfluidic channels (inset shows the close-up view).

The cell localization area is the central focus of the designs. We placed polysilicon (poly-Si) electrodes below this region for the electrical/fluid-flow measurements. We routed other microfluidic channels to the backside of the wafer for connection to the mesoscale fittings and placed these microfluidic channels around the backside of the wafer to facilitate delivery and extraction of fluids/chemicals.

Initial testing using bovine red blood-cells have been carried out in other bio-MEMS (microelectromechanical systems) devices, and the same protocol will be used in preliminary testing of these devices.

32163

Microscale Techniques for the Study of Cell Signaling

V. A. Vandernoot, J. S. Schoeniger, S. A. Pizarro

We will adapt microanalytical technologies developed at Sandia to address important problems in cell signaling that would improve the speed, throughput, or sensitivity for monitoring a cell-signaling pathway. Cell signaling is central to biological processes of critical importance in national security contexts and also to many biomedical problems, such as the immune response to pathogens. In collaboration with researchers from the Alliance for Cellular Signaling (AFCS) at the University of Texas, Southwestern, we will exploit developments supported through μ ChemLab™ technologies and apply them to a problem of importance to cellular signaling. The project consists of the selective collection and concentration of cell-signaling proteins by immunoaffinity chromatography and the application of sensitive bioanalytical and microanalytical tools (Fourier transform [FT] ion cyclotron mass spectrometry [MS], capillary electrophoretic techniques), to determine phosphoprotein signatures of B-cells (B lymphocytes). We will then compare the response of these phosphoprotein signatures to signatures obtained from cells after exposure to one of a variety of agonists (hormones). The goal of this work is to significantly advance the state-of-the-art tools to aid in the understanding of cellular-signaling pathways and how the various pathways interconnect (e.g., redundancies, synergistic responses, or additive or subtractive effects).

Cell lines and sample preparation. We received samples of two different cell lines that are being evaluated by the AFCS. These were primary cell lines of both the B-cells originally proposed for this project and the cardiac myocytes. We evaluated several different approaches for sample preparation to optimize the yield of proteins, including four different lysis buffers and three different precipitation options for each cell type. We based our selection criteria both on the amount of total protein in the received sample and on the size and number of distinct proteins that were observed by electrophoretic separation and detection.

We will adapt microanalytical technologies developed at Sandia to address important problems in cell signaling that would improve the speed, throughput, or sensitivity for monitoring a cell-signaling pathway. Cell signaling is central to biological processes of critical importance in national security contexts and also to many biomedical problems, such as the immune response to pathogens. In collaboration with researchers from the Alliance for Cellular Signaling at the University of Texas, Southwestern, we will exploit developments supported through μ ChemLab™ technologies and apply them to a problem of importance to cellular signaling.

We evaluated the effect of protein precipitation as a means of preconcentration and sample cleanup to eliminate potential interferences from the lysis buffers. We used either acetone or ammonium sulfate to precipitate the proteins.

Ultimately, neither precipitation protocol was deemed ideal. The acetone precipitation caused difficulty in redissolving the proteins, while the ammonium sulfate treatment resulted in a recurring spurious peak in laser-induced fluorescence (LiF) traces.

We selectively collected phosphoproteins from B-cells and myocytes by two different methods: immobilized metal-affinity chromatography (IMAC) and immunoaffinity chromatography.

Capillary electrophoresis with LiF detection. We found capillary electrophoretic separations with LiF detection to be effective, sensitive microseparation and analysis tools for the cell extracts. Proteins from myocytes or B-cells were labeled with fluorescamine (a fast-reacting fluorogenic dye that reacts with primary amines in the millisecond timeframe) and separated by either capillary-zone electrophoresis (CZE) or capillary-gel electrophoresis (CGE).

CGE analysis of phosphorylation signatures upon stimulation. The goal of this project is to examine how phosphorylation signatures change in response to a variety of agonists (stimuli). The AFCS identified a large group of agonists of interest (including epinephrine, interleukin, and others) and supplied B-cell and myocyte samples stimulated (for 5 minutes) with appropriate stimuli. We observed differences in resting- and activated-cell lysates by both CZE and CGE. The phosphoprotein-signature differences were apparent in samples obtained by both phospho-enrichment techniques evaluated (antibody-based and immobilized metal-ion-affinity techniques), suggesting that significant changes occurred in not only the levels of phosphotyrosine-containing proteins, but also in phosphoserine- and phosphothreonine-containing proteins.

Comparison to conventional techniques. Our progress shows proof-of-concept for the ability to assay the differences in phosphoprotein signatures associated with cell stimulation and signaling. The approach proposed here for the use of microscale separation techniques coupled with LiF detection represents a significant improvement in terms of the time required to generate data (less than 1 hour compared with 8 to 10 hours for slab-gel/Western blot). This approach has additional advantages in terms of good sensitivity (nanomolar

The goal of this project is to examine how phosphorylation signatures change in response to a variety of agonists (stimuli). ...

Our progress shows proof-of-concept for the ability to assay the differences in phosphoprotein signatures associated with cell stimulation and signaling.

sensitivity) and direct quantitation (compared to subsequent densitometry or electroelution of an excised-gel spot from a slab-gel approach followed by mass spectrometry or some other quantitation method). Certainly, the slab-gel approach currently isolates a larger number of species; this is because of a 2-D separation mode.

32166

Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling

M. D. Rintoul, S. J. Plimpton, P. T. Boggs, M. P. Sears, J. F. Shepherd, S. A. Means

The fundamental unit to all life on earth is the cell. Despite the enormous differences between the cells of different organisms (and the differences between different types of cells within a single organism), all cells share the same ability to not only grow but to also respond to many widely varying external stimuli. Ultimately, the different responses that the cell generates are the result of many highly interdependent physical and chemical processes.

Understanding the cell has tended to be a reductionist effort, with an attempt to study all of the different processes of the cell in finer and finer detail until a complete understanding was reached. However, it has become clearer that most important cell processes involve a large number of simultaneous smaller processes, and these cannot be studied independently.

Sandia seeks to provide a computational framework in which the cell, or at least significant parts of it, can be modeled as a whole. Many of the smaller details of cell processes have been described through careful experiments, but it is difficult to experimentally study these processes as a whole. Sandia's researchers who specialize in modeling large-scale physical systems that consist of many strongly interacting parts are uniquely poised to provide a means of putting all of the pieces together to help solve the puzzle as a whole.

After providing a framework, we will demonstrate the proof of our concept by applying our model to an outstanding problem in cell modeling. The model will be that of chemotaxis, in which a cell such as a lymphocyte is able to hunt down and possibly destroy an unwanted cell (which is also in motion) by following a chemical trail. This work could have the ability to identify and respond to bioweapon threats and disease vectors.

The primary accomplishment this year was confirmation of a new mathematical model for the distribution of calcium-releasing proteins that are vital in the process of cell fertilization.

The egg is represented as a 500 mm radius sphere. Illustrated above on the left is how the spherical region is meshed: radially symmetric partitions toward the outer region and the surface, with a cube of rectangular elements at the center. This resulted in 371,200 elements and 376,185 nodes. The mesh was partitioned into 512 subregions for solution on 512 processors. The partitioning is illustrated above on the right (surface view).

This work could have the ability to identify and respond to bioweapon threats and disease vectors.

The model came from a group at the University of Connecticut Health Sciences Center and was being developed to help explain the complex calcium wavefront that was seen very clearly in experiment during the fertilization process. Unfortunately, this new model was too complex for the university simulation capabilities to verify in a fully 3-D context.

We used techniques in meshing, solving partial differential equations (PDEs), and massively parallel (MP) computing. (These techniques were developed for our stockpile stewardship work.) We performed this simulation and verified that the new model did fit the experimental data almost perfectly. This work was performed in a few hours on hundreds of processors and is thought to be among the largest whole-cell simulations ever performed anywhere in the world.

We used the same techniques to model intracellular neuronal concentrations in an attempt to explore the possible impact of intracellular sodium on intracellular calcium and the indirect affect on neurotransmitter release. Experimental work shows that sodium plays a mysterious role in modulating neurotransmitter release with regard to long-term (approximately 100 sec) responses to chronic stimulations and may have implications for short-term learning. Our simulations indicate that the sodium-calcium exchanger (posited by some experimentalists as a possible vector for the influence that sodium exerts) has relatively insignificant impact on neurotransmitter release.

We performed this simulation and verified that the new model did fit the experimental data almost perfectly. This work was performed in a few hours on hundreds of processors and is thought to be among the largest whole-cell simulations ever performed anywhere in the world.

Refereed

Means, S. A. 2001. "Impact of Sodium on Intracellular Calcium and Its Implications in Neurotransmitter Release." Master's Thesis, Department of Applied Mathematics, University of New Mexico, Albuquerque, NM (August).

Rintoul, M. D., J. N. Shadid, A. G. Salinger, J. Schaff, B. Slepchenko, J. Wagner, L. Loew, S. A. Means, and P. Embid. 2001. "Preliminary Parallel Finite-Element Simulations of Diffusion/Reaction Systems in Cellular Modeling." Paper presented to the 1st International Symposium on Computational Cell Biology, Lenox, MA, 4-6 March.

33317

Training Software Agents to Reason in the Absence of Data

E. M. Raybourn, M. E. Senglaub, D. L. Harris

Automated reasoning is a technology that approximates the complex functions of human decision making. Automated-reasoning systems are becoming more and more complex and are operating at significantly increased conceptual levels and tempos. As reasoning technology evolves, the ability to put human controllers in charge could put these systems and their interactions with a human population at risk.

Sandia proposes re-examining some fundamental questions concerning reasoning. We are exploring these questions in an issues context, which we can apply as a validation tool for any reasoning model. The issues include the absence of information, the absence of expected cues, as well as the identification of cues, learning collaboratively through the clustering or grouping of information, and the ability to creatively connect information from diverse knowledge domains. Identification of a theoretical foundation for reasoning will enable us to develop automated-reasoning agents that can be used to populate complex high-consequence control systems. Within a Defense Programs (DP) context, we envision these controllers installed in operational systems that can decide, for example, if a fuzing option will result in undesirable collateral damage—or determine if actions taken by maintenance and logistics support personnel constitute an insider threat—and then the controllers can respond accordingly. The key to these capabilities is that these agents can respond to situations with far less data than would be required by “pattern matching”-type reasoning methodologies, which are statistically based.

Sandia discovered the impact of Charles Sanders Peirce’s work (philosophy of scientific inquiry and semiotics) on cognition-based decision making in simulated environments. These notions have been implemented successfully in contexts such as data fusion, systems engineering, and the design of information operations systems. Peirce’s theory focuses on formal logic that can achieve the best possible conclusions based on available information. Complex adaptive systems use such logic not only to process

Sandia proposes re-examining some fundamental questions concerning reasoning. We are exploring these questions in an issues context, which we can apply as a validation tool for any reasoning model. The issues include the absence of information, the absence of expected cues, as well as the identification of cues, learning collaboratively through the clustering or grouping of information, and the ability to creatively connect information from diverse knowledge domains. Identification of a theoretical foundation for reasoning will enable us to develop automated-reasoning agents that can be used to populate complex high-consequence control systems.

information, but also to build a constantly evolving base of knowledge from which to hypothesize, predict, test, plan, and implement action. Because his work aims to identify formal logical systems, Peirce's work creates an opportunity to articulate a variety of modes of reasoning that human beings or other complex systems might use.

Identification of a theoretical foundation for reasoning will enable us to develop automated-reasoning agents that can be used to populate complex high-consequence control systems. These systems can be used in power stations, in medical-emergency rooms, in combat environments that are dominated by autonomous fighting systems, in the classroom, and in the strategic stockpile.

One characteristic of complex systems is that design engineers probably will not be able to anticipate all operational scenarios and build contingencies into the control algorithms. Populating these control systems with reasoning agents provides a mechanism for dealing with these unknown and unanticipated situations; the agents will be able to assimilate and generate solutions faster than their human counterparts.

We designed a functional model of cognition that addresses (1) abduction and analogic, which deals with postulating solutions to a broad spectrum of well- or ill-defined problems, (2) deduction, which identifies high-probability solutions, and (3) induction, which is an approach to validation and learning.

Also, we identified a natural coupling to the work of Lefebvre, Apter, and others working in the areas of the social dynamic impacts on reasoning and included this work in our functional representations of cognition.

As a final part of our effort, we began to define the technologies that can be used to support the different functions of our cognition model. JSM (John Stuart Mills) offers an example of one technology that we have begun to explore for applications in areas of abduction and possibly induction.

We designed a functional model of cognition that addresses (1) abduction and analogic, which deals with postulating solutions to a broad spectrum of well- or ill-defined problems, (2) deduction, which identifies high-probability solutions, and (3) induction, which is an approach to validation and learning.

34713

Nonlinear Modeling and Simulation of Pulsed Electromagnetic Stimulation and Response of Selected Excitable Biological Structures

R. C. Pate, R. B. Asher, P. E. Patterson, M. E. Tadros

This project begins the implementation of an appropriate modeling framework to allow for the simulation of fundamental “effects level” interaction of electromagnetic (EM) fields with biological systems. Sandia began by considering linear resistor-capacitor (RC) network modeling of excitable biological membrane structures (i.e., elongated muscle or nerve cells) as a reasonable starting point for exploring EM coupling and effects in biological systems. Linear modeling, however, is of limited utility. Nonlinear mechanisms must also be introduced to more realistically simulate observed excitation effects and threshold behavior associated with cellular membrane system responses to applied electrical stimuli. We specifically limited nonlinear mechanisms considered for this project to those associated with the voltage-controlled flow of various species of ions through channels or pores in the membranes of excitable biological cell structures. Several models describing the macroscopic behavior of various types of animal nerve and muscle tissue have been derived empirically over the past half-century. Well-known examples include the Hodgkin-Huxley neural model (unmyelinated nerve); the Frankenhaeuser-Huxley neural model (myelinated nerve); the model for striated muscle fiber developed and later improved by Adrian, Chandler, Hodgkin, and Peachey; the original Noble and the improved McAllister-Noble-Tsien model for the cardiac Purkinje fiber; the Beeler-Reuter model of ventricular myocardial fiber, and others. The Hodgkin-Huxley model, in particular, was groundbreaking work in this field that led to a Nobel Prize in physiology. Among the more interesting and pressing reasons to pursue this line of investigation is to better understand and characterize macroscopic nonlinear excitation responses and thresholds, at the active membrane level, in living animals exposed to the near-field or far-field coupling of EM pulses from external sources.

The problem of bioelectromagnetic (BEM) interactions and effects must be addressed at several levels. As an overall modeling framework, we consider three major levels of

We specifically limited nonlinear mechanisms considered for this project to those associated with the voltage-controlled flow of various species of ions through channels or pores in the membranes of excitable biological cell structures. Several models describing the macroscopic behavior of various types of animal nerve and muscle tissue have been derived empirically over the past half-century.

system interaction and response. The first stage of interaction involves determining the macroscopic coupling and detailed distribution of EM fields within the interior of the heterogeneous biological system. The second stage involves determining the field interaction and response mechanism(s) at the microscopic subsystem (e.g., sensory, nerve, or muscle cells/tissue, etc.) and submicroscopic feature/process (e.g., active biological membrane, ionic channel dynamics, etc.) levels. The third stage involves determining the physiological and higher-level perceptual and/or behavioral effects induced within the system by the interaction/response mechanisms identified in the second stage. Modeling and simulation improvements are needed in the first stage, but the greatest challenges remain in addressing the second and third stages outlined above. The project work was active to a limited degree in addressing all three levels of interaction, but greatest emphasis was placed on cell membrane-level model development.

We made progress toward establishing an initial modeling framework incorporating basic bioelectrical mechanisms that underlie the response of biological systems to electrical and EM stimuli. The mechanisms considered thus far are localized at the cell membrane level. Ionic channels (also referred to as “macromolecular pores”) are believed to be the elementary excitable elements in cell membranes. Active membranes produce and transduce electrical signals in living cells, tissues, specialized structures, and higher-level systems. They can be activated (“excited”) by a host of stimuli, depending on the specialized nature of the cells, tissue, or higher-level system being considered. Of particular initial interest for this project has been the response of biological cells with electrically active membrane (e.g., nerve or muscle) to currents induced by electrical excitation due to the coupling of EM fields.

We identified passive cable modeling of microscopic biological membrane structures as the most useful and insightful approach to the initial investigation of bioelectrical interactions and response at the microscopic cellular membrane level. After beginning at this level, we pursued improved modeling of excitable cells by extending the passive RC-network modeling with the circuit analogs for empirically derived nonlinear models of active biological membrane. We placed initial emphasis on the implementation of the Hodgkin-Huxley model for unmyelinated nerve. The resulting system of differential equations is quite stiff, requiring care in the

We made progress toward establishing an initial modeling framework incorporating basic bioelectrical mechanisms that underlie the response of biological systems to electrical and EM stimuli. The mechanisms considered thus far are localized at the cell membrane level. Ionic channels (also referred to as “macromolecular pores”) are believed to be the elementary excitable elements in cell membranes.

numerical implementation. We are pursuing several alternative approaches for comparison and check. We also initiated the exploration of available techniques for conducting the migration of high-resolution time or frequency-domain field-coupling calculations from the macroscopic scale to the microscopic membrane-level scale in complex, heterogeneous, biological material structures. Similarly, we also initiated work to explore the eventual migration of theoretical ion-channel modeling at the nanoscale level of molecular dynamics and electrodiffusion to the macroscopic membrane level described empirically by Hodgkin-Huxley and other similar experimentally derived nonlinear modeling constructs.

*We are pursuing several
alternative approaches for
comparison and check.*

35510

MyLink

R. L. Craft, N. M. Berry, D. E. Rhodes, C. M. Pancerella, R. M. Arms, R. J. Garcia

Without question, the Internet and its associated technologies are changing every aspect of our lives. As computers continue to increase in power and drop in price, we have opportunities to place “intelligence” where it has never existed before. Similarly, the explosion of pervasive digital communications has given us the ability to instantly move vast quantities of information to wherever we want it. At the same time, for as much as these technologies have already reshaped our world, they are only the vanguard of what is to come—the foundation on which the future digital superstructure will be built. Without a doubt, our greatest opportunities to exploit the power of information technology still lie ahead.

Of these opportunities, one of the most exciting is the potential to use computers and networks to overcome our human limitations. With this technology, we can tear down many of the barriers imposed on us by the realities of time and space and by the finiteness of our individual minds. A range of current national problems, such as helping war fighters make sound decisions in the fast-paced, data-saturated battlefield of the future or helping our seniors maintain their ability to live independently, even in the face of debilitating events, beg for the kinds of solutions that information technology has the power to provide. To this end, this project will produce a prototype system that demonstrates key elements that we believe need to be available if we are to ultimately realize this human/computer collaboration in this future digital world.

The team developed initial outlines and storyboarded concepts for the software. In the middle of the project, we refocused work to allow us to tailor the concepts for use in a real-world setting. This would allow a natural test-bed for our concepts and software without the need to provide our own human-study environment.

We engaged the engineering staff at the Intel Architecture Labs regarding our concepts for a technical architecture to support next-generation approaches to delivering care. We participated in a two-day event at the Architecture Labs focused on the question of where care delivery is heading in the future, and laid the groundwork for

*... this project will produce a
prototype system that
demonstrates key elements that
we believe need to be available
if we are to ultimately realize
this human/computer
collaboration in this future
digital world.*

future collaborations with some of the key players in smart homes and technology to assist the disabled.

Our programmers produced a simple program to illustrate the concepts being advanced by the project. The goal of the software was to create a software tool that would interact with individuals to help them track their daily levels of activity and to encourage them to work toward activity-level goals.

We also collaborated with a related project in California that used students to produce a related demonstration with a military focus.

The goal of the software was to create a software tool that would interact with individuals to help them track their daily levels of activity and to encourage them to work toward activity-level goals.

Advanced Manufacturing

The objective of the Advanced Manufacturing investment area is to support manufacturing technology advances with an emphasis on process-based quality. Process-based quality is a systematic approach to generate superior manufactured goods (i.e., nuclear weapon components and subsystems) with little or no product inspection or testing. Research priorities in this investment area support the miniaturization and cost- and time-reduction requirements for future nuclear weapon manufacturing needs. Manufactured products, particularly microdevices, have the potential to reduce defects and costs.

The cost of designing and manufacturing fixtures has driven significant research in automatic design. Nonetheless, automated fixture design systems are not widely used due to lack of adequate analysis tools. The “Automatic Design of Practical Fixtures” project will develop new fixture design techniques based on recent advances developed by Sandia and a new idea for mitigating the effects of dimensional errors. The new results allow more general analysis of stability, realistic simulation of fixture loading, including sliding and rolling, and sticking contacts. This

approach can be broadly classified as simulation-based design and, as such, will require the simulation of multiple scenarios, each corresponding to possible unknown loading conditions and manufacturing errors.

10347

Microdiagnostic MEMS Lab-on-a-Chip*M. P. de Boer, M. B. Sinclair, E. J. Pryputniewicz, N. D. Masters, N. F. Smith, F. Bitsie*

Although mechanical properties of microelectro-mechanical systems (MEMS) structural materials are critical to product design and performance, there exists no infrastructure for their routine measurement. Furthermore, when measurements are presently made on an interferometric microprobing station, resolution is very high, but accuracy is not well known. Sandia will overcome these deficiencies by developing a self-validating suite of small area test structures for automated measurement. Statistical quality control can then become the basis for MEMS design, process improvement, and reliability. Because MEMS are radiation hard and demonstrate promise for nuclear weapons surety, this work will directly benefit the nuclear weapons program.

Our approach for developing microdiagnostic MEMS devices is modeled after parametric devices in microelectronics. We believe a similar avenue is feasible and is indeed the best approach for MEMS. Relevant mechanical properties include residual stress, stress gradient, adhesion, friction, and fracture strength. Our project will have two main thrusts. The first is to optimize test structures, in conjunction with a determination of the accuracy of the mechanical tests from optoelectrical probing techniques. To validate test results, we will use measured device parameters to predict performance of a composite test structure. Predictions will then be compared to actual performance. The second thrust is to implement the procedures on an automated prober.

The development of a standard suite of diagnostic device designs with properly validated measurement and analysis specifications will enable first-run success of designs and facilitate the production and reliability of MEMS, both in Sandia nuclear weapons surety applications and in the commercial world.

(1) We incorporated appropriate important property measurement structures into fully automatic testing. Full automation is an aggressive goal; therefore, we separated this objective into two tasks. First, we constructed a manual interferometer equipped with our new software for production lots to enable at least an important subset of the properties to be measured. Some 30 lots were characterized in

Because MEMS are radiation hard and demonstrate promise for nuclear weapons surety, this work will directly benefit the nuclear weapons program.

Our approach for developing microdiagnostic MEMS devices is modeled after parametric devices in microelectronics.

semiautomatic fashion. Second, we continued to make progress on our full-scale test system. Where before, two weeks were required to obtain data on a column of a wafer, this task can now be accomplished in two days. We continued to make considerable progress toward full-scale automation, including (a) combining our image analysis software and deflection analysis software into one package, (b) developing algorithms to reduce required user input into deflection analysis, and (c) continued debugging and improving analysis software.

(2) We wrote design rules based on materials property data. We created control charts for properties that have been tested many times.

(3) We determined accuracy for important properties yet to be incorporated. We developed general techniques to assess the accuracy of our methods.

(4) We fully checked algorithms for residual stress, adhesion, fracture, and friction. For residual stress, we developed two methodologies to measure residual stress, which resulted in a journal submission. We now have a fully

... we continued to make progress on our full-scale test system. Where before, two weeks were required to obtain data on a column of a wafer, this task can now be accomplished in two days.

μ Diagnostic Lab on a Chip LDRD program

We developed test structures, mechanics, and metrologies to automatically determine material and surface properties for microelectromechanical systems.

checked algorithm for this property. We also have a journal submission for our adhesion measurement procedure that allows adhesion to be measured along the full length of a cantilever test structure. We designed new fracture and friction devices. The friction device resulted in an invited paper to the Society for Photooptical Instrumentation Engineers (SPIE) Conference. We completed fabrication of the fracture device and will test it soon. Based on our fracture device design, we are also working on a metal test structure to test stress/strain curves of thin-metal films as well as fatigue and creep properties. This resulted in an unexpected invited presentation at the Fall 2001 Materials Research Society (MRS) Conference based on our abstract.

(5) We optimized designs for all types of test structures. Our new support post designs did solve the initial offset-angle problem. The status of the friction and fracture devices is discussed above.

We completed fabrication of the fracture device and will test it soon. Based on our fracture device design, we are also working on a metal test structure to test stress/strain curves of thin-metal films as well as fatigue and creep properties.

Refereed

Baker, M. S., M. P. de Boer, N. F. Smith, and M. B. Sinclair. 2001. "Determination of Residual Stress in Fixed-Fixed Microbeams to ± 0.5 Megapascal Accuracy." *J. Microelectromechanical Systems*, submitted.

Baker, M. S., M. P. de Boer, N. F. Smith, and M. B. Sinclair. 2001. "Measurement of Residual Stress in MEMS to Submegapascal Accuracy." *Proc. Society for Experimental Mechanics Annual Conference and Exposition* (Portland, OR, May).

de Boer, M. P., and T. M. Mayer. 2001. "Tribology of MEMS." *MRS Bulletin* **26**(4) (April): 302–304.

de Boer, M. P., D. L. Luck, J. A. Walraven, and J. M. Redmond. 2001. "Characterization of an Inchworm Actuator Fabricated by Polysilicon Surface Micromachining." *Proc. SPIE* **4558**, in press.

de Boer, M. P., J. A. Knapp, and P. J. Clews. 2001. "Effect of Nanotexturing on Interfacial Adhesion in MEMS." *Proc. International Conference on Fracture* (ICF10) (Honolulu, HI, December).

de Boer, M. P., N. F. Smith, N. D. Masters, M. B. Sinclair, and E. J. Pryputniewicz. 2001. "Integrated Platform for Testing MEMS Mechanical Properties at the Wafer Scale by the IMaP Methodology." *Mechanical Properties of Structural Thin Films, Special Technical Publication (STP) 1413* (ASTM, West Conshohocken, PA, 2002); S. B. Brown and C. L. Muhlstein, eds., accepted.

Jensen, B. D., M. P. de Boer, N. D. Masters, F. Bitsie, and D. A. LaVan. 2001. "Interferometry of Actuated Cantilevers to Determine Material Properties and Test Structure Nonidealities in MEMS." *J. Microelectromechanical Systems* **10**(3) (September): 336–346.

Knapp, J. A., and M. P. de Boer. 2001. "Mechanics of Microcantilever Beams Subject to Combined Electrostatic and Adhesive Forces." *J. Microelectromechanical Systems* (September).

Masters, N. D., M. P. de Boer, B. D. Jensen, M. S. Baker, and D. Koester. 2001. "Side-by-Side Comparison of Passive MEMS Strain Test Structures Under Residual Compression." *Mechanical Properties of Structural Thin Films, Special Technical Publication (STP) 1413* (ASTM, West Conshohocken, PA, 2002); S. B. Brown and C. L. Muhlstein, eds., accepted.

Other Communications

de Boer, M. P. 2001. "Effect of Nanotexturing on Interfacial Adhesion in MEMS." Keynote address, ASME Mechanics and Materials Summer Conference, San Diego, CA, June.

de Boer, M. P. 2001. "Evaluating MEMS Reliability Using Optimized Test Structures." Keynote address, CAMPmode Meeting, University of Colorado at Boulder, Boulder, CO, May.

de Boer, M. P. 2001. "Mechanics and Materials Science at the Micron Scale: Taking Advantage of MEMS." (Invited) Presentation to the Johns Hopkins University Mechanical Engineering Department Seminar, Baltimore, MD, May.

de Boer, M. P. 2001. "Studying Adhesion and Friction in MEMS: Test Structure, Metrology, and Lubrication Choices." NIST Presentation, Gaithersburg, MD, May.

de Boer, M. P. 2001. "Studying Friction in MEMS: Test Structure, Metrology, and Lubrication Choices." (Invited) Paper presented to the International Conference on Metallurgical Coatings and Thin Films, San Diego, CA, April.

10349

Thin-Film Deposition Processes Incorporating *In Situ* Monitoring Capabilities

D. P. Adams, J. A. Floro, N. R. Moody, R. S. Goeke, J. A. Romero

This project researches alternative thin-film deposition techniques that allow control of residual stress. Processes that allow tailoring of residual stress may enable engineers to directly affect film properties such as adhesion and performance. In particular, Sandia is focusing on two reactive-deposition techniques for growing various metal hydrides, evaporation, and ion-beam sputtering. There is interest in metal hydride layers for miniature fuel cells.

Understanding the origin of stress during all stages of fabrication is a key aspect of this work. Achieving this understanding is challenging, considering that stress is impacted by many factors, including grain structure, defect density, composition, epitaxy, and mismatch of substrate/film thermomechanical properties. In addition, stress may be directly influenced by deposition parameters.

We are researching reactive-deposition techniques because we anticipate that simultaneous deposition of both species will be found to generate a stress that is small compared with two-step processes that first deposit metal and then react the metal with a second species such as hydrogen (H).

We are researching both evaporation and sputtering, which potentially result in different residual stresses. During evaporation, metal atoms arrive at the film surface with low kinetic energy that may lead to a zero or tensile stress due to a low-density microstructure. During reactive sputtering, metal atoms and sputter-gas atoms can strike a growing film with high energy. However, sputter parameters can be modified to alter the energy imparted to a film. Potentially, this would allow the user to control film stress.

In addition to research and development of alternative deposition techniques, this project aims to develop a stress diagnostic tool suitable for a manufacturing environment. This diagnostic instrument must allow for in situ investigation of stress during all stages of fabrication, including deposition, rotation, heating, and cool-down. Potentially, the diagnostic instrument may be used for feedback control of a process.

... Sandia is focusing on two reactive-deposition techniques for growing various metal hydrides, evaporation, and ion-beam sputtering. Metal hydride films are of interest for nuclear weapon (NW) applications. In addition, there is interest in metal hydride layers for miniature fuel cells. ... In addition to research and development of alternative deposition techniques, this project aims to develop a stress diagnostic tool suitable for a manufacturing environment.

We demonstrated the ability to tailor film stress. Completion of this goal required a thorough investigation of the effects of deposition parameters on film microstructure, composition, and phase. The laser-based sensor provided rapid feedback to evaluate stress.

A long-term goal of our work is to demonstrate processes that lock in a particular stress, including tensile, compressive, and zero stress. We recognize that each stress “type” may be desirable for different applications, particularly those that cycle or remove H over time. It is apparent that the mechanical properties of metal hydride films are important to long-term reliability. Therefore, we evaluated all reactively deposited films. Our evaluation included tests of interfacial bond strength (adhesion) for different substrates and moduli.

Refereed

Adams, D. P., J. A. Romero, J. A. Floro, M. Rodriguez, and P. Kotula. 2001. “Microstructure and Stress of Sputter-Deposited Erbium Hydride Thin Films.” *J. Appl. Physics*, in press.

We demonstrated the ability to tailor film stress. Completion of this goal required a thorough investigation of the effects of deposition parameters on film microstructure, composition, and phase. The laser-based sensor provided rapid feedback to evaluate stress.

10721

Volumetric Displacement Control (VDC) of Manufacturing Tools

L. F. Bieg, B. Jokiel, Jr., M. T. Ensz

Sandia's desire to eliminate or minimize independent product inspection must result in better process control. Statistical process control (SPC) has been exercised in the past by influencing the process based on trends. This method may be applied to high-volume manufacturing at low manufacturing tolerances. Enhancements in material/fabrication processes are driven by reducing cost and cycle time and by minimizing fabrication defects at increased accuracy and speed. In-process inspection has forced the requirement of periodically certifying the manufacturing process. Historically, methods defined under American National Standard ASME B5.54 are applied to determine the performance of computer numerically controlled (CNC) systems. Trained experts have to apply a multitude of expensive and sensitive equipment to evaluate performance.

We conceptualized a volumetric displacement control (VDC). The VDC can perform volumetric three-dimensional (3-D) analysis of a workspace at a high degree of accuracy in real time. The application of the VDC is simple and requires little time and skill since the actual processing equipment is guiding the VDC through all workspace extremities. Today, feedback during the manufacturing process is limited to displacement (motion) sensing of the equipment, at great distances away from the actual point of operation. In most cases, rotating motion produced by a motor is translated into linear motion through the pitch or lead of a screw. External and self-induced thermal influences as well as geometric errors while in motion have never been detected and applied to control the process. Industry and university publications assign an 80 percent contribution of errors based on thermal and geometric issues. Our approach will measure and correct in real time process-induced errors on manufacturing tools of motion. The VDC system will provide total process control (TPC) to the fabrication floor.

Our team evaluated, analyzed, calibrated, and corrected the VDC system prototype. We designed and implemented data-acquisition software that provides the capability to perform pertinent studies and corrections. We

Today, feedback during the manufacturing process is limited to displacement (motion) sensing of the equipment, at great distances away from the actual point of operation. In most cases, rotating motion produced by a motor is translated into linear motion through the pitch or lead of a screw. External and self-induced thermal influences as well as geometric errors while in motion have never been detected and applied to control the process. Industry and university publications assign an 80 percent contribution of errors based on thermal and geometric issues. Our approach will measure and correct in real time process-induced errors on manufacturing tools of motion.

evaluated the Sandia-designed joint feedback system and calibrated it to provide accurate angular resolution in the count domain of three counts per arc second for joints 1 and 2, and five counts per arc second for joint 3. We performed a long-term drift study. This study included different altitudes within a 2-cubic-foot working volume and resulted in a one-count drift stability within a 24-hour period. Joint 3, the farthest away from the baseplate kinematic mount, was analyzed to be most sensitive to drift.

Sandia's negotiations with New River Kinematics, Inc., and Brunsen Instruments resulted in the purchase of Spatial Analyzer, a commercially available metrology software. This software module allowed the VDC team to evaluate the performance of a Zeiss coordinate measuring machine (CMM) with a Laser Trucker, and compare both these devices with the VDC system. Commercial metrology software is driving the inspection performance of the VDC system. It allows for the evaluation of every known geometrical element.

We provided a real-time graphical representation of the VDC system in software for a state-of-the-art graphical user interface (GUI). The VDC system is applied for in-process inspection by the operator/machinist as needed, to define datum features, part orientation, maximum material condition, out-of-tolerance conditions, or for final feature inspection after part manufacturing.

We designed and fabricated an artifact to serve the function of on-machine certification and calibration of the VDC system. Conversely, displacement performance of the manufacturing tool can be evaluated against the artifact. Multiple ANSI B5.54 circle diamond square test parts were fabricated by our machining test-bed, and the VDC system will inspect it on the machine. Subsequent post-manufacturing inspection on a CMM will determine and document process improvement levels. Application mode 1 is defined as in-process inspection; application mode 2 addresses the use of the VDC system as a 3-D ball bar and allows for dynamic evaluation of motion in the entire workspace of production equipment.

We finalized two independent patent applications of the VDC system and filed them with the U.S. Patent and Licensing Office. Two unrelated private companies have expressed interest in licensing the VDC system.

We provided a real-time graphical representation of the VDC system in software for a state-of-the-art graphical user interface (GUI). The VDC system is applied for in-process inspection by the operator/machinist as needed, to define datum features, part orientation, maximum material condition, out-of-tolerance conditions, or for final feature inspection after part manufacturing.

Conceptual picture of a measuring device installed on a small milling machine.

Refereed

Jokiel, B., Jr., L. F. X. Bieg, and M. Ens. 2000.

“Development of an Independent Real-Time Position Feedback Device for CNC Machining Operations.”

Proc. ASPE Fall 2000 Conference **1** (Scottsdale, AZ, October): 4.

10722

Process-Based Quality Tools to Verify Cleaning and Surface Preparation

J. A. Emerson, P. A. Lemke, N. R. Moody, E. D. Reedy, Jr., D. P. Adams

Specifying material choices and the method for processing does not always ensure the long-term durability of an adhesive bond. Manufacturing quality and control are crucial, and one must be able to fully characterize and certify the entire fabrication process. From a recently completed cleaning study, Sandia learned of the need to develop and move to the factory floor a tool to identify surface preparation requirements and guarantee their effectiveness. This tool would utilize a method for measuring adhesion of small areas in conjunction with combinatoric testing. The development of a small plate containing many masked-off regions follows combinatorial techniques. By processing this plate through a production line, a new region is exposed during each step of the fabrication process. Now, the plate contains the combined effects of all the processing steps as well as any contamination added during storage and transit. This combinatoric process characterization plate (PCP) is interrogated to determine if the desired adhesion level exists when the fabrication process is complete.

The unique goal of this project is to develop and move to the factory floor a combinatorial PCP to identify surface preparation requirements and guarantee their effectiveness. No other tests or inspection would be necessary to guarantee the final product acceptance. Although this is a new concept for certifying war reserve parts, the core idea of maintaining process control is critical to modern manufacturing. Not only will this tool represent an existing part in terms of the combined effects of all the processing steps and any contamination added during storage and transit; it will also carry the history of sequential surface preparation and subsequent processes.

We are developing a method based on nanoindentation and contact mechanics testing to interrogate the PCP. This method shows great promise. For example, a thin layer of the adhesive is cast over the plate, followed by a stressed overlayer. The radius of the blister generated during indentation is directly related to interfacial fracture toughness. The ultimate goal is a tool that can be used on the

The unique goal of this project is to develop and move to the factory floor a combinatorial PCP to identify surface preparation requirements and guarantee their effectiveness. No other tests or inspection would be necessary to guarantee the final product acceptance. Although this is a new concept for certifying war reserve parts, the core idea of maintaining process control is critical to modern manufacturing. Not only will this tool represent an existing part in terms of the combined effects of all the processing steps and any contamination added during storage and transit; it will also carry the history of sequential surface preparation and subsequent processes.

factory floor for small-lot and rarely used processes. We are taking full advantage of current collaborative work with Honeywell/Federal Manufacturing and Technology (FM&T) process engineers to further our effort.

In previous work, we focused on developing small-area adhesion tests that are accurate, convenient, and scalable from conventional adhesion tests. We placed stressed layers on a polymer film to induce delamination. We completed studies for developing known and adjustable stress overlayers with Ta₂N-superlayer stressed thin films under various vacuum deposition pressures. However, these stressed superlayers trigger delamination in weakly bonded films but not in strong-adhering films.

Following this initial work, which was a combination of background pressure and deposition rates, tungsten overlayers were repeatedly deposited with stresses ranging from 1 GPa tension to 4 GPa compression. When combined with controlled thickness, the total stored energy can be tailored to induce fracture in each film. Moreover, we can deposit overlayers in such a way that the stresses do not overdrive or underpower crack growth. We showed with the nanoindentation of thin epoxy films on aluminized glass that delamination occurs readily along the film-metal interface. To measure the interfacial toughness for 0.2 μm –1 μm thick epoxy films, we found that a critical indenter displacement is required to create stresses that drive interfacial crack growth.

We continued work on measuring the surface adhesion, using contact mechanics and nanoindentation techniques for one polymer film system. We demonstrated the use of JKR (Johnson, Kendall, and Roberts theory) contact mechanics for detecting trace amounts of surface contamination. This approach capitalizes on the difference in surface energy between the epoxy probe and organic contaminant. In particular, we developed a method by which surface cleanliness can be estimated quantitatively by computing the adhesion hysteresis parameter, H .

We employed a tensile brazil nut (TBN) sandwich specimen to measure the interfacial fracture toughness of a millimeter-scale epoxy bond constrained by metal adherends. The specimen consists of two semicircular aluminum disks bonded together by a thin epoxy layer. A 12.7 mm long interfacial crack (or weakly bonded region) is introduced along one end of the epoxy bond during specimen fabrication.

When combined with controlled thickness, the total stored energy can be tailored to induce fracture in each film.

Moreover, we can deposit overlayers in such a way that the stresses do not overdrive or underpower crack growth. ...

This approach capitalizes on the difference in surface energy between the epoxy probe and organic contaminant.

The specimen is loaded via pins inserted through one of the sets of the opposing holes that circle the outside edge. We vary the applied mode mixity by using a different set of loading holes, and an 80° variation in applied crack-tip mode mixity is possible. The ability to easily adjust the applied mode mixity over a wide range of potential values is a substantial advantage over other common types of interfacial fracture specimens. Failure load is the only measured quantity in a TBN sandwich test. A calibration function, which depends on failure load, initial crack length, and the position of the loading points, is used to determine interfacial toughness and the associated crack-tip mode mixity. We performed more than 40 detailed finite-element analyses to establish the required TBN sandwich specimen calibration. The principle challenge that we encountered while developing the TBN sandwich specimen was finding a reliable method for inserting an initially sharp interface crack of known size. This is a crucial step since an initially blunt crack invalidates the measurement. Methods using self-assembled monolayer (SAM) coatings have met with success, and we continue to refine our fabrication processes.

We performed more than 40 detailed finite-element analyses to establish the required TBN sandwich specimen calibration. The principle challenge that we encountered while developing the TBN sandwich specimen was finding a reliable method for inserting an initially sharp interface crack of known size. This is a crucial step since an initially blunt crack invalidates the measurement.

Refereed

Moody, N. R., D. F. Bahr, M. S. Kent, J. A. Emerson, and E. D. Reedy, Jr. 2001. "Adhesive Failure of a Thin Epoxy Film on an Aluminized Substrate." *Proc. Materials Research Society: Fundamentals of Nanoindentation and Nanotribology II* **649** (April) (Boston, MA, 27 November 2000): Q6.3.

Moody, N. R., D. F. Bahr, M. S. Kent, J. A. Emerson, and E. D. Reedy, Jr. 2001. "Thickness Effects on Adhesion of Epoxy Films." *Proc. 24th Annual Adhesion Society Meeting* **24** (Williamsburg, VA, February): 309–311.

Nesbitt, S. L., J. A. Emerson, and J. P. Bell. 2000. "Evaluation of β -Diketone-Containing Polymeric Coupling Agents for Enhancing the Adhesion of Epoxy to Aluminum." *J. Adhesion* **72**: 245–268.

Woerdeman, D. L., J. A. Emerson, and R. K. Giunta. 2001. "Epoxy/Aluminum Adhesion as Measured by Contact Mechanics (JKR) in the Presence of an Organic Contaminant." *Proc. Materials Research Society: Fundamentals of Nanoindentation and Nanotribology II* **649** (April) (Boston, MA, 27 November 2000): Q6.4.

Woerdeman, D. L., J. A. Emerson, and R. K. Giunta. 2001. "JKR Contact Mechanics as a Practical Tool for Detecting Organic Contamination on Aluminum." *Proc. 24th Annual Adhesion Society Meeting* **24** (Williamsburg, VA, February): 29–31.

10723

Fabrication of Three-Dimensional Microstructures Using Soft Lithography

R. L. Myers, D. P. Adams, A. D. Oliver, J. A. Emerson

Microstructures are becoming increasingly important in technological advances in many fields including the upgrade and maintenance of the nuclear weapons stockpile. Microstructures are fabricated primarily by photolithography, a process that produces two-dimensional (2-D) parts. However, photolithography has intrinsic limitations in making 3-D structures. The LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) process requires x-ray radiation, making it costly and not readily accessible. The ability to fabricate 3-D microstructures of a wide range of materials using a soft lithography technique (e.g., microcontact printing) makes it possible to achieve unprecedented levels of system functionality for microelectromechanical systems (MEMS), microsensors, and microoptical devices at a much lower cost. Soft lithography techniques use a patterned elastomeric stamp or mask.

Sandia is investigating the fabrication of 3-D microstructures using microcontact printing. This process could be used to create MEMS devices. Microcontact printing is a soft lithography technique in which a self-assembled monolayer (SAM) is patterned by transfer printing. A macroscopic analogy is linoleum block printing, which offers low-cost, high-precision replication. The thin-patterned layer can be an etch resist or a foundation upon which to build new types of microstructures. Since an elastomeric stamp is flexible, it can be used to transfer a pattern to 2-D or 3-D substrates. For example, metallized glass capillaries can be patterned by microcontact printing, then selectively etched in an aqueous etchant to form microstructures such as microcoils.

Current university research demonstrates that microcontact printing can achieve nanometer-level resolution on planar substrates. Our particular application requires a much larger feature size that should be easier to pattern with this technique. We propose the fabrication of 3-D microstructures with feature sizes in the tens of microns.

Our particular application requires a much larger feature size that should be easier to pattern with this technique. We propose the fabrication of 3-D microstructures with feature sizes in the tens of microns.

We transferred a variety of patterns to 2-D substrates by microcontact printing using process improvements from our previous research results. In our earlier process-improvement study, we learned how to make a stamp with a minimum number of defects. We also learned how best to apply the hexadecanethiol “ink” to the stamp to get full coverage of the SAM on the surface of the stamp. We are now able to get numerous repeatable pattern transfers with the same stamp, and up to five pattern transfers with one application of the hexadecanethiol ink.

We made an elastomeric stamp of the microchain pattern from the master that we fabricated earlier. We transferred the pattern to 2-D substrates of silver (Ag) and gold (Au) by microcontact printing, followed by selective wet etching in an aqueous etchant. We developed our procedure for selective wet etching using flat substrates initially to become skilled in the process. We are now able to selectively etch 3-D substrates such as metallized glass capillaries, which are more difficult to process. We established a procedure for selective wet etching of Au using an aqueous cyanide bath, and of Ag using an aqueous ferricyanide bath. We successfully produced the microchain pattern on 3-D metallized glass capillaries of Au and Ag using microcontact printing followed by selective wet etching.

The next step in our microfabrication operation is electroplating. While electroplating a substrate patterned in Au, we discovered that our original microchain design needed modifications to accommodate the electroplating process. We made a new master using the improved design and are currently making a stamp from this master. Once the stamp is made, we can transfer the new microchain pattern to metallized glass capillaries using microcontact printing followed by selective wet etching. Then we will do the subsequent processing necessary to make a microchain, resulting in our first 3-D part. By transferring the microchain pattern to two metallized glass capillaries and then adjoining them, interlocking links can be formed through electroplating. This electrochemically welds the two halves of each link together and builds up the thickness of the links to make them more robust. We completed the fabrication of the master for the microcoil pattern and made an elastomeric stamp for this pattern.

In our earlier process-improvement study, we learned how to make a stamp with a minimum number of defects. We also learned how best to apply the hexadecanethiol “ink” to the stamp to get full coverage of the SAM on the surface of the stamp. We are now able to get numerous repeatable pattern transfers with the same stamp, and up to five pattern transfers with one application of the hexadecanethiol ink.

Other Communications

Myers, R. L., D. P. Adams, R. K. Giunta, J. A.

Emerson, M. J. Vasile, and Y. Picard. 2001.

“Microcontact Printing Using Stamps with Curvilinear Cross-Sections.” Poster presentation to the Materials Research Society 2001 Spring Meeting, San Francisco, CA, April.

10751

Automatic Design of Practical Fixtures

J. C. Trinkle, R. J. Gross, E. J. Gottlieb

The cost of designing and manufacturing fixtures has driven significant research in the automatic design of fixtures at Sandia (e.g., Holdfast), in academia, and in industry. However, automated fixture design systems are not widely used. The two primary problems are (1) lack of generality (i.e., arbitrary three-dimensional [3-D] parts and fixturing element geometries cannot be handled), and (2) inability to accurately predict important performance criteria (i.e., tolerance stack-up, loading difficulty, and thermal expansion mismatches). These problems lead to failures. In the Neutron Generator Facility, for example, fixture failures cause significant costs and delays.

Fixture design systems have fallen short because there have been no underlying theory or analysis tools to efficiently predict loading difficulty and problems associated with dimensional errors and changes in parts and fixtures. Sandia proposes to develop a new fixture design technique based on recent results that researchers have developed, and a new idea for mitigating the effects of dimensional errors. The new results allow more general analysis of stability; realistic simulation of fixture loading, including sliding and rolling; and sticking contacts. Our work will yield a principled way to include unstructured and systematic dimensional variations in the design process.

The proposed approach can be broadly classified as simulation-based design. As such, it will require the simulation of multiple scenarios (each corresponding to possible unknown loading conditions and manufacturing errors). To maximize the effectiveness of this approach, variants of bundle methods will be applied to minimize the number of scenarios to be analyzed, and yet still guaranteeing the achievement of fixture design specifications and ongoing experiments to validate our simulations. Also, since the approach is simulation-based, any phenomenon that can be simulated can be included without changing our approach.

We implemented a new method for the simulation of systems of rigid bodies in unilateral contact with dry friction in the simulation tool, UMBRA. This capability is not

Fixture design systems have fallen short because there have been no underlying theory or analysis tools to efficiently predict loading difficulty and problems associated with dimensional errors and changes in parts and fixtures. Sandia proposes to develop a new fixture design technique based on recent results that researchers have developed, and a new idea for mitigating the effects of dimensional errors.

available in any of Sandia's numerical codes, including PRONTO, even though the capability is discussed in PRONTO's manual.

(1) *Designed objective function for tolerance stack-up problem; tested on two-dimensional (2-D) examples.* The worst-case position errors due to machining errors of points on a fixtured part (or set of parts) is affected by the locations of the contact points between the part and the fixture. We can now design optimal fixture points that minimize the worst-case positioning errors of designated key points.

(2) *Tested loading-strategy design method on 3-D deterministic parts. Developed new unexpected results while waiting for key piece of code to be developed.* We implemented the most difficult part of this milestone—rigid-body dynamic simulation—and have a solid mathematical foundation in place to begin the design of strategies that ensure complete mating of a part with its intended fixture. We still have not completed one important part of this simulation capability—contact-point identification between concave bodies. Once we have contact-point identification, we will be able to complete this milestone readily. However, while awaiting this accomplishment, we developed some very useful simulation-free insertion design techniques. Our results have been submitted for publication.

(3) *Obtained thermal data via finite-element analysis.* We tested deterministic, 3-D thermal design and successfully solved some test problems with the SIERRA code for coupled thermal/structural problems (Calagio). We are currently running problems with known solutions to verify Calagio for our application.

We implemented the most difficult part of this milestone—rigid-body dynamic simulation—and have a solid mathematical foundation in place to begin the design of strategies that ensure complete mating of a part with its intended fixture.

Refereed

Balkcom, D., E. J. Gottlieb, and J. C. Trinkle. 2001. "A Sensorless Insertion Strategy for Rigid Planar Parts." Paper submitted to the IEEE International Conference on Robotics and Automation, Washington, DC, May 2002.

Han, L., J. C. Trinkle, and Z. Li. 2000. "Grasp Analysis and Linear Matrix Inequality Problems." *IEEE Transactions on Robotics and Automation* **16**(6) (November): 663–674.

Pang, J. S., and J. C. Trinkle. 2000. "Stability Characterizations of Fixtured Rigid Bodies with Coulomb Friction." *Zeitschrift für Angewandte Mathematik und Mechanik* **80**(10) (October): 643–663.

Trinkle, J. C., D. Balkcom, and E. J. Gottlieb. 2001. "Computing Wrench Cones for Planar Contact Tasks." Paper submitted to the IEEE International Conference on Robotics and Automation, Washington, DC, May 2002.

Trinkle, J. C., J. Tzitzouris, and J. S. Pang. 2001. "Dynamic Multi-Rigid-Body Systems with Concurrent Distributed Contacts: Theory and Examples." *Philosophical Transactions of the Royal Society on Mathematical, Physical, and Engineering Sciences*, accepted.

Other Communications

Trinkle, J. C. 2001. "Motion Planning for Systems with Mechanical Constraints." (Invited) Paper presented to the Department of Computer Science, Rennselaer Polytechnic Institute, Troy, NY, November.

Trinkle, J. C., D. Balkcom, and E. J. Gottlieb. 2001. "Designing Fixture Loading Strategies." Paper presented to the International Conference on Scientific Computation and Differential Equations, Vancouver, British Columbia, Canada, July.

10755

Microreplication: Precision Metal Parts from Electroformed Master Molds

R. P. Janek, J. T. Hachman, Jr., N. Y. C. Yang, J. J. Kelly

Batch fabrication of weapons-related microsystems has been successfully demonstrated using deep x-ray lithography and subsequent electroforming through plastic molds (LIGA [acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding]). While this process is well characterized and well understood, low cost and quick turnaround of precision microscale parts has not yet been realized due primarily to the high cost of x-ray exposure and the inherent single-use nature of the LIGA-generated plastic mold. Replication of metal microcomponents from an electroformed, multiple-use metal master mold would represent a significant technological breakthrough and would enable a production process that delivers metal parts with unparalleled precision, reproducibility, and reliability at a much lower cost than currently possible.

Replication is accomplished through a sequence of processing steps. The metal master mold is first fabricated using standard LIGA techniques. A conformal dielectric film (e.g., polystyrene) is then electrochemically deposited over the surface of the master, followed by selective etching of the dielectric at the base of each molded feature. A conductive layer of amorphous carbon is sputtered over the master, creating electroactive sites at the base of each molded feature. Metal parts are then electrodeposited through the mold onto the conductive seed layer. The insulating sidewalls of the master ensure high-fidelity replication of the part as the metal fills the molded features. Metal parts are released from the mold by simultaneous thermal decomposition of the sacrificial dielectric and carbon seed layers. The master mold is then cleaned and reused.

This project utilizes existing Sandia expertise in LIGA, electrodeposition, and electro-initiated polymerization that can be applied directly to fabrication of integrated microsystems for Defense Program (DP) applications. In addition to DP needs, low-cost and time-saving replication of metal microparts would impact many commercial

Replication is accomplished through a sequence of processing steps. The metal master mold is first fabricated using standard LIGA techniques. A conformal dielectric film (e.g., polystyrene) is then electrochemically deposited over the surface of the master, followed by selective etching of the dielectric at the base of each molded feature.

applications, including manufacture of microelectronics, telecommunication devices, and precision automotive and aerospace components.

Our novel method of through-mask electrodeposition on substrates with conducting sidewalls was valuable in attempting to use metal master or plastic sacrificial ("lost") molds. Since the electrodeposition process is modified to account for film growth from the sidewalls, no special processing steps are necessary to render the sidewalls insulating. This simplifies the process flow.

For our experiments with the conductive polymethylmethacrylate (PMMA), we drilled holes into the top of a test sample, but, in principle, one may emboss this material with a stamp (made by the LIGA process) for rapid replication. The plated parts were mechanically separated from the substrate in the case of a metal substrate, while for the conductive PMMA, the substrate itself was dissolved. We carried out electrodeposition experiments on the two types of substrates to assess the ease with which the parts were obtained, as well as the feature-filling capabilities of various electrodeposition processes.

The experiments done with the metal master mold had features 150 μ deep and 100 μ –200 μ wide. Since the aspect ratios were not too challenging, we investigated only direct current. Before deposition, we treated the surface with an oxidizing agent to facilitate subsequent demolding. Although we also tried additional lubricants such as molybdenum disulfide and tungsten disulfide, the demolding step was particularly difficult, causing significant damage to the plated parts when viewed in cross section via scanning electron microscopy (SEM). Consequently, we focused our subsequent efforts using conductive PMMA, which can be dissolved with acetone to free the plated parts. One interesting observation of the experiments on metal with active sidewalls was that even direct current, which we expected to have the worst feature-filling performance, filled most of the features except for a thin void at their centers. Most probably, this is attributable to the low thickness and aspect ratio of the features.

We drilled holes with a diameter of approximately 150 μ and a depth of 1.1 mm (aspect ratio about 7) into conducting PMMA, yielding an aggressive aspect ratio feature for the testing of the various electrodeposition schemes outlined above. We found that the direct current and the pulse-reverse plating methods (where the deposit is partially

Our novel method of through-mask electrodeposition on substrates with conducting sidewalls was valuable in attempting to use metal master or plastic sacrificial ("lost") molds. ...

For our experiments with the conductive polymethylmethacrylate (PMMA), we drilled holes into the top of a test sample, but, in principle, one may emboss this material with a stamp (made by the LIGA process) for rapid replication.

stripped off during deposition) provided the least satisfactory results. When direct current was employed, the metal did not penetrate significantly down into the feature. Pulse reverse-plating deposited metal about a third of the way into the feature, but the film has a noticeable roughness; the bottom two-thirds of the feature was empty. Pulse plating penetrated all the way down into the feature, but the feature was pinched off about a quarter of the way into the feature, resulting in voiding. Direct current deposition with the leveling agent coumarin led to a smooth metal film throughout the feature depth, but in some cases voiding occurred. This variation may be due to the lack of well-defined hydrodynamics during the experiments, since the leveling effect is sensitive to mass transfer.

We concluded that (1) it is possible to plate on conductive PMMA with active sidewalls, (2) these substrates are preferable to metal ones, since they avoid mechanical demolding and potential damage, (3) features having an aspect ratio of about 1 to 2 are not too difficult to fill, even with direct current, and (4) pulse plating and leveling agents (or perhaps a combination of these two methods) hold the most promise for filling higher-aspect-ratio features (greater than about 6).

Direct current deposition with the leveling agent coumarin led to a smooth metal film throughout the feature depth, but in some cases voiding occurred.

10770

IMEMS Packaging and Interconnection Technology

K. A. Peterson, C. A. Reber

Microelectromechanical systems (MEMS) offer the opportunity to miniaturize key components in military and commercial applications at low cost. Many advantages from this miniaturization are subsequently sacrificed, however, in packaging MEMS structures with the present understanding of conventional microelectronic packaging processes. The resulting low yields in MEMS packaging are a “show-stopper” for the eventual success of MEMS.

This Sandia project will resolve multiple micropackaging issues to efficiently and reliably take advanced MEMS structures from functionality in a laboratory setting to fielded applications. We will practice concurrent engineering to develop the interconnection, micropackaging, postprocessing and, ultimately, wafer-scale packaging concepts that will make consistent, process-based quality a reality.

We will study and improve packaging materials and processes so that they don't “kill” released, functional MEMS. We will further investigate a new processing sequence utilizing high-capacity commercial polymer encapsulation to afford complete protection to conventional wirebonds and die-attach prior to the release of the MEMS devices. We will further investigate a new approach for ruggedizing released and treated functional MEMS wafers through the use of encapsulation in a vacuum-deposited, carbon-based material.

This approach protects MEMS devices through some potentially damaging micropackaging processes, such as backside preparation, die-separation, handling, die-attach, interconnection, and possibly even transfer molding. Packaging innovations that reduce the number and complexity of processing steps will be instituted in a package design with an integral, optical-quality window. Ultimately, we will investigate wafer-scale packaging techniques that make the device into its own package.

This project will complete these evaluations with the goal of ensuring advanced manufacturing at higher yield. The success of this project will be a major step in the advanced manufacturing of reliable MEMS structures and will make them more available to Sandia weapon applications.

This project will complete these evaluations with the goal of ensuring advanced manufacturing at higher yield. The success of this project will be a major step in the advanced manufacturing of reliable MEMS structures and will make them more available to Sandia weapon applications.

We are continuing to work in a multidepartmental team, and we are increasing our interactions internally and externally, obtaining more buy-in and expertise from key experts in MEMS. We are interacting with projects with more knowledge as a result of evaluations performed in this work (i.e., wirebonding on the Product Emulator).

We furthered the combination of conventional packaging and new ideas for packaging and came up with several promising approaches (including seven Disclosure of Technical Advance submissions). We are prototyping test devices in the plastic encapsulation arena with the services of an outside vendor. We prototyped the coating technique for prereleased MEMS devices and characterized the behavior of several devices with limited success. We prototyped the flip-chip mounting of the MEMS test die to test polysilicon substrates and demonstrated high attachment strengths. We completed a patent application for a gold-based MEMS interconnection technique that negates the requirement for metal on MEMS bond pads. We pursued release etch-resistant material solutions that enable the “package now, release later” concepts that we continue to develop. These include work on several common solders that look quite promising. We significantly explored eutectic die-attach as a technique enabling prerelease packaging and demonstrated the compatibility of this approach using conventional commercial high-temperature, co-fired ceramic (HTCC) packages. We obtained two significant device types and numerous test die from recent reticle sets for a demonstration of these ideas. This work will exercise microengines, micromirror arrays, and test structures, all of which are in need of packaging solutions. We prepared these wafer segments, coated them with appropriate backside metallization, and diced them to size. We demonstrated for the first time the direct electroplating of polysilicon with metal and continue to refine this and related abilities, including electroless techniques.

We interacted with projects involving microfluidics and developed several new ideas in this area. We prototyped a microfluidic plastic package that can readily be fabricated by a commercial vendor at the low cost of \$9 per part. We also made progress on a microfluidic channel fabrication technique for plastic packaging. We prototyped the package that allows soldered next-level connection of packages to microfluidic boards with a technique that is readily applicable to plastic encapsulated MEMS in general.

We demonstrated for the first time the direct electroplating of polysilicon with metal and continue to refine this and related abilities, including electroless techniques.

We devoted considerable effort to expanding the realm of “package now, release later” concepts and procured and prepared a number of materials, processes, and devices that we expect to result in several successful demonstrations of high-yield MEMS packaging techniques.

Other Communications

Peterson, K. A., S. E. Garrett, and C. A. Reber. 2000. “Approaches to MEMS Packaging.” Paper presented to the Packaging and Integration of MEMS and Related Microsystems Advanced Technology Workshop, Orlando, FL, 10–12 November.

10773

Assembly of LIGA Using Electric Fields

J. T. Feddema, T. M. Weber, L. K. Warne, D. L. Armour, W. A. Johnson, A. J. Ogden, G. E. Vernon

The goal of this project is to develop a device that uses electric fields to grasp and possibly levitate LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) parts. This noncontact form of grasping would solve many of the problems associated with grasping parts that are only a few microns in dimensions. Scaling laws show that for parts of this size, electrostatic and electromagnetic (EM) forces are dominant over gravitational forces. This is why microparts often stick to mechanical tweezers. If these forces can be controlled under feedback control, the parts could be levitated and could even be rotated in air. In this project, we used capacitive-sensing techniques to track the part, and feedback control to regulate the applied field of an array of electrodes. The eventual use of this tool will be to assemble metal and nonmetal LIGA parts for weapons surety devices.

Our accomplishments include the following:

- (1) Built a symmetric gripper with both attractive electrostatic pads and repulsive EM coils.
- (2) Performed extensive experimental tests with this gripper to evaluate the reliability of picking up and releasing a 4 mm diameter, 100 μ thick copper part.
- (3) Modified the gripper design to include a 0.5 μ thick coating of polymethylmethacrylate (PMMA) to act as an insulator between the gripper and the part.
- (4) Designed and built an addressable array-based gripper for picking up nonsymmetric parts.
- (5) Modified the Sandia-developed EIGER'S electrostatic boundary element code so that it would run on a parallel computer cluster.
- (6) Simulated the electrostatic effects of the gripper designs using the modified EIGER'S code.
- (7) Analyzed the lateral stability problem associated with the current gripper designs.

The experimental results show that we can reliably pick up the 4 mm diameter, 100 μ thick part when the gripper is within 80 μ of the part and a 120 V potential is applied to the electrostatic pads. Unfortunately, there is 40 percent probability that the part will stick to the gripper when the volt

Combined electrostatic/electromagnetic gripper used to pick up 4 mm diameter LIGA part. The electrostatic force of attraction is created by applying up to 150 volts to the four inner pads. The electromagnetic force of repulsion is created by applying up to 1 amp at 10 MHz to the coils surrounding the inner pads. The center circle is used to sense the stand-off distance between the part and the gripper.

Experimental setup used to test the new gripper designs. Gripper is inside the DIP package on the robotic positioning system. The 4 mm diameter part is on the pedestal below the package.

is released. We believe this to be caused by residual electrostatic effects, van der Waal forces, and surface tension forces. To eliminate this sticking problem, we added the EM coils to the gripper design. Driving the coils with a 1 Å, 10 MHz sine wave reduces the probability of sticking to 6 percent. Other tests show that simply heating the surface by applying direct current (DC) through the coils reduces the probability of sticking to 15 percent.

Experimental tests and the lateral stability analysis also show that it is difficult to stably levitate a part with the current planar gripper designs. Any small lateral disturbance or initial displacement can cause the part to jump out of the electrostatic/EM fields. Further research is needed to design a true levitation device. However, the current designs are still a possible solution for reliably picking up and releasing metal LIGA parts that are less than 1 m³ in size.

To eliminate this sticking problem, we added the EM coils to the gripper design. Driving the coils with a 1 Å, 10 MHz sine wave reduces the probability of sticking to 6 percent. Other tests show that simply heating the surface by applying direct current (DC) through the coils reduces the probability of sticking to 15 percent.

Refereed

Feddema, J. T., L. K. Warne, W. A. Johnson, and A. J. Ogden. 2001. "Electrostatic/Electromagnetic Grippers for Microassembly." *Proc. World Automation Congress 2002, ISORA 9th International Symposium on Robotics and Applications* 1 (Orlando, FL, 9 June 2002).

10793

Computer Numerically Controlled Micromachines

G. L. Benavides, C. W. Dyck, B. Jokiel, Jr., D. P. Adams, L. F. Bieg

Historically, microelectromechanical systems (MEMS)-type micromachines are designed to function in a two-dimensional (2-D) workspace. In this project, Sandia will design, manufacture, package, and apply computer numerically controlled (CNC) silicon (Si) micromachines. These multiple degree-of-freedom (DOF) machines (including 3-D) will serve as the basic building block for a variety of applications. We are contemplating applications in micromilling, microcoordinate measuring, microalignment, optical switching, laser pointing, rastering, and a device that performs surgery on living cells. A micromilling machine capable of machining nanosized features can be built by employing a high-speed motor holding a cutting tool, all on one chip.

Some of the innovative technologies that are needed to enable CNC micromachines are:

- (1) A parallel mechanism, the only method of fabricating a microstage on a chip since serial mechanisms require the stacking of actuators.*
- (2) Sputtering or chemical vapor deposition (CVD), to apply nonsilicon material to a polysilicon (poly-Si) part.*
- (3) A focused ion beam (FIB), to fabricate micro-sized cutting tools.*
- (4) A micromachine stepper motor, to provide open-loop positional control.*
- (5) Nonsilicon-based microfabrication, to provide packaging of Si micromachines.*

CNC micromachines will have War Reserve and commercial applications. CNC micromachines can be used to machine or inspect nonplanar parts to previously unheard of dimensions. A mirrored platform can couple optical energy to multiple sensors or detonators. Medical applications include micromanipulation of biological specimens using a dexterous CNC manipulator.

We fabricated the amplifiers necessary to drive the microstage and purchased the waveform card for the personal computer (PC). The amplifier, the waveform card, the PC, and the Sandia-developed controller software all go together to

These multiple degree-of-freedom (DOF) machines (including 3-D) will serve as the basic building block for a variety of applications. We are contemplating applications in micromilling, microcoordinate measuring, microalignment, optical switching, laser pointing, rastering, and a device that performs surgery on living cells.

make up the controller/driver for the microstage. We successfully beta-tested a similar controller/driver to drive the linear stepper motors on the microstage.

We tested a controller/driver to test the newly fabricated planar microstages. We successfully actuated the Si-based linear stepper motors and showed them to both drive and kinematically validate the microstage. This test was probably the first demonstration of a controllable actuator driving a Si-based parallel kinematic mechanism. We also tested an alternative actuation scheme, but our tests showed it to be problematic. The alternative to the linear stepper motors is the large displacement shuffle motors. The controller/driver performs the major functions of the computer-aided design/computer-aided manufacturing (CAD/CAM) interface.

We exceeded our expectations regarding the task of designing erectable microstages. We completed the mask designs for three different erectable microstages and they are now in fabrication. Patent applications are in process for these three innovative devices, which have different motion-specific attributes that appeal to different applications and represent a significant leap in Si-based MEMS technology. We improved the linear stepper motors, and they should provide steady, reliable motion. We used the working model to validate the kinematics of the erectable microstage. We performed a DOF analysis to determine whether the newly designed erectable parallel kinematic mechanisms were properly constrained.

We successfully actuated the Si-based linear stepper motors and showed them to both drive and kinematically validate the microstage. This test was probably the first demonstration of a controllable actuator driving a Si-based parallel kinematic mechanism.

10794

Electromicrofluidic Packaging

G. L. Benavides, D. Gutierrez, P. C. Galambos, K. A. Peterson, C. A. Reber

Microfluidics is experiencing explosive growth in new product development. The number of surface-micromachined (SMM) microfluidic devices is likely to increase as issues of manufacturing efficiency and integration of microfluidics with electronics become important. SMM microfluidic devices are manufactured with the same tools as integrated circuits (ICs), and their fabrication can be incorporated into the IC fabrication process.

To realize applications for SMM microfluidic devices, an efficient method for getting fluid into these devices must be developed. This project focuses on packaging for electromicrofluidic devices, and specifically on an efficient method for delivering fluids of interest to SMM microfluidic channels that are integrated with electronics. Sandia will develop an electromicrofluidic dual in-line package (EMDIP, formerly called MMP [microfluidic/microelectronic package]) that allows for electrical connections using standard techniques and microfluidic connection from either a substrate or a test fixture.

Using the SUMMiT™ (Sandia Ultraplanar Multilevel MEMS Technology) process, we will manufacture SMM microfluidic channels that will require both electrical and fluidic connection. The fluid will be introduced into the microfluidic devices from the back of the wafer through Bosch-etched vias. These vias will align with passages in the EMDIP, allowing fluid delivery to each individual channel in the wafer.

We will also investigate the next level of packaging that takes the fluid from the EMDIP to standard connectors. In production devices, the next level of packaging will probably be a fluidic printed wiring board (FPWB) with embedded fluid channels. For fluidic IC testing, the intermediate packaging level will consist of a test fixture, allowing connection of fluidic devices for pressure and flow-rate measurements. The EMDIP, test fixture, and FPWB will require mesoscale fabrication in nonsilicon materials. Our investigation will primarily focus on the fabrication and packaging of an EMDIP made from either ceramic or plastic material.

Exploded view of the electromicrofluidic dual in-line package.

Using the SUMMiT™ (Sandia Ultraplanar Multilevel MEMS Technology) process, we will manufacture SMM microfluidic channels that will require both electrical and fluidic connection.

- We modified the design of the EMDIP. The modified design should be more manufacturable and easier to assemble. The lead frame was designed to be initially flat, provide bondpads, and leave a large footprint for one or more electromicrofluidic ICs.

- We designed and fabricated a mold that we then used to fabricate the EMDIP. We fabricated five EMDIPs in clear silicone and five EMDIPs in a hard opaque epoxy.

- We fabricated several manifolds (fan-out) in PEEK (polyether ether ketone). We envision that these manifolds will be injection-molded; however, these manifolds were precision-mesomachined due to the limited quantity.

- We assembled EMDIP. The assembly includes the manifold and the electromicrofluidic IC. We used 3M adhesive tape to bond the surfaces. We performed a leak test to test the integrity of the adhesive tape. The results of the leak test indicate this is a viable process.

- We filed two patent applications on electromicrofluidic packaging and are currently participating in a market study to estimate commercial potential of this packaging concept.

- We designed the FPWB.

We filed two patent applications on electromicrofluidic packaging and are currently participating in a market study to estimate commercial potential of this packaging concept.

Refereed

Galambos, P. C., and G. L. Benavides. 2000. "Electrical and Fluidic Packaging for Surface-Micromachined Electromicrofluidic Devices." *Proc. Society of Photo-Optical Instrumentation Engineers (SPIE)* (Santa Clara, CA, September).

Galambos, P. C., G. L. Benavides, M. Okandan, M. W. Jenkins, and D. Hetherington. 2001. "Precision Alignment Packaging for Microsystems with Multiple Fluid Connections." *Proc. 2001 ASME, International Mechanical Engineering Congress and Exposition* (New York, NY, November).

26508

Mesoscale Wide-Bandwidth Linear Magnetic Actuators

L. A. Jones

The purpose of this project is to develop and integrate the technologies to efficiently manufacture mesoscale wide-bandwidth linear magnetic actuators. Sandia defines mesoscale actuators as actuators that have linear travel beyond that which can be achieved using electrostatic, piezoelectric, or magnetostrictive technologies, but that are small enough in overall size that mesomachining and micromachining methods are required to fabricate them. Our work leverages on the results of recently completed as well as ongoing projects at Sandia concerning the fabrication of mesoscale magnets and windings. Our project seeks to supply mesoscale magnetic actuator technology to a host of applications at Sandia.

A mesoscale moving-magnet linear actuator has been designed using magnetic computation software. Linear Halbach magnet arrays are suspended in the stator, using magnetic bearings. The tubular actuator has a square cross-section with four orthogonal planar stator windings batch-fabricated using stacks of copper (Cu) structures electroplated into lithographic resist masks and then diffusion-bonded together. The differential magnetic pressure between opposite pairs of stator windings provides the magnetic bearing.

Applications of this technology include pointing actuation as required by optical switches, lithography, telescopes, and radars, control and propulsion surfaces, wide-bandwidth valve modulation, active vibration damping, and micromaterials testers.

We are developing and integrating the technologies necessary to efficiently manufacture mesoscale wide-bandwidth linear magnetic actuators. We define mesoscale linear actuation as at least 1 mm peak to peak, which is beyond the range that can be obtained using piezoelectric, magnetostrictive, or silicon-micromachined devices. We define a wide-bandwidth actuator as one that can be served from a no-motion position direct current (DC) up through its first resonant frequency. The technologies that we are developing and integrating for such actuators include the fabrication and assembly of mesoscale linear permanent-

The purpose of this project is to develop and integrate the technologies to efficiently manufacture mesoscale wide-bandwidth linear magnetic actuators. ...

Our work leverages on the results of recently completed as well as ongoing projects at Sandia concerning the fabrication of mesoscale magnets and windings. Our project seeks to supply mesoscale magnetic actuator technology to a host of applications at Sandia.

magnet arrays; the batch fabrication of mesoscale stator windings; the optimization of mesoscale magnetic flux paths; the development of low-friction, low-wear, long-throw linear suspensions; the development of compact and rugged absolute actuator position sensing schemes; and the development of the control electronics and advanced feedback-control algorithms necessary for micron-level position control.

To focus our efforts, we are developing a prototype wide-bandwidth mesoscale linear actuator that utilizes moving permanent magnets. State-of-the-art mesoscale linear actuators utilize variable-reluctance structures, thereby avoiding the difficult problem of fabricating mesoscale arrays of permanent magnets. A moving permanent-magnet actuator will have substantially higher performance than a variable-reluctance actuator.

We envision numerous applications for mesoscale wide-bandwidth linear magnetic actuators including (1) pointing applications such as optical switches, lithography, telescopes, and radars, (2) control surface actuation for microUAVs (unmanned airborne vehicles), (3) wide-bandwidth valve modulation for high-speed flow processes, (4) active vibration-damping applications, and (5) micromaterials testers.

As work proceeded on this project, we decided to implement an integrated linear magnetic bearing. This approach is technically more aggressive and will yield significant benefits if successful. Choosing magnetic bearings leads to the development of maximum precision actuators rather than maximum force actuators. Maximum force actuators utilize high-permeability materials to capture as much flux as possible from the magnets and the windings. The presence of this high-permeability material inevitably leads to variable reluctance cogging forces. Maximum precision actuators, on the other hand, benefit greatly from magnetic bearings and are typically implemented without any high-permeability materials. (In the macroscale world, they are often called *ironless motors*.) Accordingly, we are implementing maximum precision actuators with no high-permeability materials. Similar conclusions were arrived at in the literature for magnetically levitated platens developed for nanometer-scale lithography.

We designed a linear actuator to take advantage of planar batch-fabrication technologies. We developed our design using magnetic field computation software. It is a tubular structure with a square cross-section. The four sides of

... we are developing a prototype wide-bandwidth mesoscale linear actuator that utilizes moving permanent magnets. State-of-the-art mesoscale linear actuators utilize variable-reluctance structures, thereby avoiding the difficult problem of fabricating mesoscale arrays of permanent magnets. A moving permanent-magnet actuator will have substantially higher performance than a variable-reluctance actuator.

the square stator are assembled from planar coils, batch-fabricated using stacks of Cu structures electroplated into lithographic resist masks, and then diffusion-bonded together. The planar coils implement three-phase, two-layer, two-thirds pitch windings axially along each of the four sides of the stator. On the slider is a four-sided Halbach array oriented in the axial direction. The rotation of the magnetization vector in the array is such that the magnetic field is confined to the outside of the structure.

The stator windings on opposite sides of the slider are series-connected, yielding two orthogonal pairs of windings that can be controlled to resist transverse translational forces acting on the slider. In addition, independently controlled windings are implemented at each of the four corners of each planar winding in order to provide pitch, roll, and yaw control of the slider.

Construction of a singled-sided stator and slider (only one side of the four-sided actuator) is under way to verify the efficacy of the design.

Construction of a singled-sided stator and slider (only one side of the four-sided actuator) is under way to verify the efficacy of the design.

26509

Levitated Three-Axis Microaccelerometer*F. J. Peter, S. H. Kravitz, R. C. Givler, J. C. Gilkey, L. K. Warne, R. D. Kinney*

A quantum leap in performance improvement and cost reduction of accelerometer design for tactical-grade applications will require a new approach rather than incremental improvements to existing concepts. Sandia's objective is to significantly advance the state of the art with a novel three-axis, closed-loop accelerometer implemented as a hybrid micromachine. This hybrid approach provides an enormous increase in available design space and frees the designer from the limitations of the monolithic process while preserving the precision, small size, low-cost, and low-power benefits of monolithic microelectromechanical system (MEMS) fabrication. The design can be tailored to meet the dynamic range, resolution, bandwidth, and environmental requirements of the application. Design goals are 100-micro-G bias stability and \$200 cost.

We developed a sound design concept, created approximate performance models, and ensured concurrency with hybrid MEMS fabrication.

- *Design concept.* We defined the operating principle, the nominal rotor and stator size and geometry, operating voltages, and materials for a proof-of-principle prototype.

- *Detailed design.* We specified the detailed rotor and stator geometry.

- *Capacitance model.* We (1) modeled rotor/stator capacitance for sensing and actuation, and (2) defined the geometrical design rules that maximize usable capacitance, minimize parasitic capacitance, mitigate high-voltage breakdown, and minimize the chance of short circuits caused by conductive particles.

- *Fluid-damping model.* We modeled translational and rotational damping for both air- and water-filled cases. Air damping alone provides substantial squeeze-film damping. Liquid damping would provide unsurpassed shock survivability (and 81 times the existing capacitance), but we still need to investigate the impact on control-system bandwidth.

This hybrid approach provides an enormous increase in available design space and frees the designer from the limitations of the monolithic process while preserving the precision, small size, low-cost, and low-power benefits of monolithic microelectromechanical system (MEMS) fabrication. The design can be tailored to meet the dynamic range, resolution, bandwidth, and environmental requirements of the application.

- *Control-system model.* We developed a 5-degree-of-freedom, closed-loop control algorithm, position-sensor capacitance models, and force-to-voltage conversion equations for the actuators.

- *Performance prediction.* We calculated performance based on actual closed-loop operation of a test structure developed for the rotating microgyro, 2 milli-G at 100 Hz bandwidth. This gyro test structure was geometrically suboptimal relative to the prototype accelerometer that is yet to be built, which was extremely encouraging news. Given the improvements that we have designed into the first prototype, predicted bias stability is 250 micro-Gs for the air-filled case and 3 micro-Gs for the water-filled case.

- *Fabrication.* We ensured concurrency between design and hybrid MEMS fabrication: gold on glass, wafer-to-wafer alignment and bonding, conductive vias, flip-chip bonding, and fluid fill port. A wafer-level assembly approach provides the cost benefit and tolerances required to meet performance objectives. We have yet to determine if we can reliably inject and maintain the liquid in the rotor cavity. This determination awaits fabrication of prototype hardware.

A wafer-level assembly approach provides the cost benefit and tolerances required to meet performance objectives.

26510

Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques

D. P. Adams, T. M. Mayer, M. J. Vasile, V. C. Hodges

This project researches new techniques for fabricating complexly shaped micro- and mesoscale devices. Currently, there is a need for numerous small devices having nonplanar features. This need extends to miniature components critical to nuclear weapons and emerging threats. It includes microactuators, microsolenoids, micropumps, and microsensors. Devices built from nonplanar substrates are also desired for biomedical (e.g., endoscopes and catheters) and pharmaceutical applications.

Sandia's goal is to research innovative techniques for fabricating curvilinear, micron-sized features of various materials onto planar and nonplanar substrates (e.g., cylinders and spheres). Development of novel microfabrication techniques is required, since current processes are limited in either dimensionality, material complexity, or microstructure control.

In this work, we use focused ion beam (FIB) sputtering to define features. This may involve direct ion sputtering, nanoscale direct-write growth processes, or sputter-fabrication of microcutting tools and subsequent ultra-precision machining.

For the first time, mechanically based Damascene processes are being investigated for making nonplanar microcoils. Coils having micron-size features are difficult to make using conventional wire-wrapping techniques. We target film materials other than those used in conventional silicon (Si) microelectromechanical systems (MEMS). This work starts with single-element metals such as copper (Cu), gold (Au), and silver (Ag) but will include metal alloys. For example, titanium nickel (TiNi) shape-memory alloy coils for fiber deflectors and zero magnetic susceptibility multilayer coils for nuclear magnetic resonance (NMR) spectrometers are feasible. To our knowledge, heterolayer thin-film microcoils have not been attempted at micron-length scales. In addition, FIB chemical vapor deposition (FIB-CVD) is being researched as a direct-write technique for controlling curved

This project researches new techniques for fabricating complexly shaped micro- and mesoscale devices. Currently, there is a need for numerous small devices having nonplanar features. This need extends to miniature components critical to nuclear weapons and emerging threats.

shapes in deposits at length scales below 25 μ . We are collaborating with Louisiana Tech University to develop these capabilities.

Our work made several achievements:

- (1) We developed a process for physical vapor deposition and electroplating onto cylindrical substrates.
- (2) We researched a process for chemical-mechanical polishing films on cylindrical substrates.
- (3) We demonstrated single-layer thin-film bound microcoil (wire width less than 25 μ).
- (4) We developed process of wire bonding to bound microcoil.
- (5) We researched kinetics, structure, and phase of ion beam-induced, chemical vapor-deposited thin films.

We have begun to work toward our next milestones. As a first step toward incorporating a CVD system onto the FIB apparatus, we designed and installed a retractable gas-jet nozzle with control valve, pressure gauge, and positioning stage. Initially, this gas-jet assembly will be dedicated to chemically amplified ion sputtering, a process that will increase the rate of shaping tungsten carbide (WC), diamond, and high-speed steel microlathe tools by 10 times or more. We are now working toward incorporating CVD processes onto this same gas-jet assembly.

As a first step toward incorporating a CVD system onto the FIB apparatus, we designed and installed a retractable gas-jet nozzle with control valve, pressure gauge, and positioning stage.

Refereed

Adams, D. P., and M. J. Vasile. 2000. "Microfabrication Via Focused Ion-Beam Sputtering." Presentation to the Rio Grande Symposium (joint meeting of the New Mexico Chapters of the MRS, ASM, and ACerS), Albuquerque, NM, November.

Adams, D. P., M. J. Vasile, and Y. N. Picard. 2000. "Focused Ion-Beam-Shaped Microcutting Tools for Fabricating Curvilinear Features." *Proc. American Society Precision Engineering* **22** (Scottsdale, AZ, October): 176–179.

26511

Resolving Fundamental Limits of Adhesive Bonding in Microfabrication

R. K. Giunta, D. R. Adkins, J. A. Emerson, M. S. Kent

Sandia is developing microsystems for the Nuclear Weapons Strategic Business Unit (SBU), including a Sandia Ultraplanar Multilevel MEMS Technology (SUMMiT)-based microsystem component. (MEMS stands for microelectro-mechanical systems.) As electronic and optical components reach the micro- and nanoscales, efficient assembly and packaging require the use of adhesive bonds. This work focuses on resolving several fundamental issues in the transition from macro- to micro- to nanobonding. A primary issue is monitoring surface properties of parts to be bonded. At submillimeter scales, traditional means of evaluating surface energy cannot be applied. We are using contact mechanics to evaluate surface properties of micron-scale parts. Another issue is that, as bondline thicknesses decrease, knowledge of the stability and dewetting dynamics of thin adhesive films is important to obtain robust, void-free adhesive bonds. Our investigations into the dewetting dynamics of thin adhesive films have already had an impact on manufacturing processes. We continue to investigate the fundamental limitations of current adhesive-bonding technology and how these size limitations can be overcome. The areas of contact mechanics, capillary fluid flow, surface energetics, and wetting have all been investigated. The focus areas that we selected—evaluating the surface properties of micron-scale parts and minimizing adhesive bondlines without sacrificing bond quality—will result in development of techniques and models for the next generation of micron-scale devices. By resolving these adhesive bonding issues, we are allowing significantly smaller devices to be designed and fabricated. Simultaneously, we are increasing the manufacturability and reliability of these devices.

(1) Select an elastomer to use as a probe for the contact-mechanics technique. We chose two epoxy elastomers to use as a probe, basing our choice on contact-mechanics experiments. We found these elastomers to be sensitive to the differing surface properties of clean versus contaminated surfaces.

This work focuses on resolving several fundamental issues in the transition from macro- to micro- to nanobonding. A primary issue is monitoring surface properties of parts to be bonded. At submillimeter scales, traditional means of evaluating surface energy cannot be applied. We are using contact mechanics to evaluate surface properties of micron-scale parts.

(2) Measure down to 1μ the capillary flow of a liquid adhesive flowing into gaps. We measured capillary flow in gaps down to 10μ and are developing a test method to hold parallelism in gaps down to 1μ . Larger-scale equipment, which is necessary to achieve parallelism to about 0.1μ , is currently being built to achieve this goal.

(3) Analyze morphology of thin films of one adhesive on one substrate for three film thicknesses as a function of time and temperature to determine if films are dewetting. We analyzed the dewetting behavior of two adhesive systems on clean silicon (Si) surfaces and found that thin films of one system dewet from the surface, while those from the other system do not, regardless of film thickness and temperature. In the dewetting case, an 8–10 Å film of epoxy remains on the Si after the bulk of the liquid has dewetted. The film consists of a combination of the epoxy resin and crosslinker. The rate at which the epoxy dewets from the substrate is significantly affected by ambient humidity, with increased humidity significantly increasing the rate of dewetting.

(4) Build a system that can write adhesive coatings on millimeter-scale surfaces. We developed a computer-guided dispensing system that can deliver nanoliter quantities of adhesive to sample surfaces. An epoxy was dispensed in a line that is about 3 mm long and 400μ wide.

We analyzed the dewetting behavior of two adhesive systems on clean silicon (Si) surfaces and found that thin films of one system dewet from the surface, while those from the other system do not, regardless of film thickness and temperature.

Other Communications

Giunta, R. K., D. R. Adkins, R. L. Myers, D. P. Adams, and J. A. Emerson. 2001. "Fabrication and Testing of Patterned Microfluidic Devices for Measuring the Flow Properties of Viscous Liquids." Paper presented to the Materials Research Society Spring Meeting, San Francisco, CA, 16–20 April.

Giunta, R. K., M. S. Kent, J. S. Hall, D. R. Tallant, M. J. Garcia, and J. A. Emerson. 2001. "Wetting and Dewetting Behavior of Thin Epoxy Films on Silicon." *Proc. 24th Annual Meeting of the Adhesion Society* **24** (Williamsburg, VA, February): 122–124.

Giunta, R. K., M. S. Kent, J. S. Hall, J. A. Emerson, and D. L. Woerdeman. 2001. "Methods to Fabricate Strong Micron-Thick Bondlines for Microsystems." *Proc. 46th International SAMPE Symposium and Exhibition Science of Advanced Materials and Process Engineering Series* **46** (Long Beach, CA, 6–10 May): 1498–1504.

Biotechnology

The Biotechnology investment area enables Sandia research efforts that develop targeted biotechnology capabilities in support of national security missions. Biotechnology will integrate Sandia's core capabilities in the physical, informational, and engineering sciences, and augment them with new biotechnical capabilities at the cellular/molecular level. The focus will be on tools and capabilities to build informational and physically based systems. These models will facilitate improved toxin-detector systems and improved microinstrumentation.

The “Nanostructured Materials Integrated in Microfabricated Optical Devices” project draws upon the emerging strength of nanocomposite materials capabilities at Sandia with the recognized expertise and processing capabilities involving microfabricated optical-device structures. The project involves design, development, and characterization of microscale structures to achieve the desired material and device function. Microsensor arrays and unique tunable microoptical devices will be developed. Multiple materials and optics issues must be addressed to successfully merge these disparate

search areas. Results from this work will make great strides in creating new micron-scale sensing arrays for biopathogens and will facilitate new approaches to materials and drug discovery.

10746

Predicting Function of Biological Macromolecules

L. J. D. Frink, H. P. Hjalmarson, M. P. Sears, A. G. Salinger, P. S. Crozier, M. J. Stevens, M. G. Martin

While sequencing technology has been a major thrust in computational biology for the last decade, there is now considerable interest in predicting protein structures from their amino acid sequences, understanding the interactions and functions of proteins in their native environments, and understanding cellular response to stimuli. This increased understanding is expected to lead to a revolution in medicine in the next century.

Sandia developed and demonstrated the applicability of a variety of computational tools to biophysical problems. Our work applies and extends massively parallel (MP) molecular simulation, molecular theory, and engineering codes to model a diverse set of problems, including DNA (deoxyribonucleic acid) condensation, DNA interactions, protein-protein interactions, drug docking, ion channel protein-mediated transport across membranes, electroporation, effect of intracellular calcium and sodium in neurotransmitter release, and studies of xenopus oocyte fertilization. This project involved developing code needed for biology applications and applying codes to the problems noted above.

We placed particular emphasis on development of a new, faster Fourier-space-based approach for molecular theory calculations, solving engineering models of cells using the MPSalsa code, completing work on comparative studies of bioforce fields, and completing work on DNA condensation.

We accomplished a significant amount of work in code development and the application of those codes to biological problems. The project successfully converted codes designed for materials modeling applications into tools suitable for biological applications.

In our work to date, code development efforts have involved both modification of existing code to perform calculations on biological systems and the development and implementation of novel algorithms. We completed studies on biological forcefields (AMBER, CHARMM, CoMPASS, GROMOS, and OPLS [optimized potentials for liquid

We placed particular emphasis on development of a new, faster Fourier-space-based approach for molecular theory calculations, solving engineering models of cells using the MPSalsa code, completing work on comparative studies of bioforce fields, and completing work on DNA condensation. ...

We accomplished a significant amount of work in code development and the application of those codes to biological problems. The project successfully converted codes designed for materials modeling applications into tools suitable for biological applications.

simulations]) using the TOWHEE code. These studies identified CHARMM as the most robust forcefields for further computational work and provided the groundwork knowledge necessary for Sandia's molecular modeling team to enter the arena of biology. Further developments of the TOWHEE code included development of a variety of Monte Carlo moves (e.g., collective moves and fixed endpoint configuration-bias moves). These moves are currently being implemented to improve performance in molecular simulation of biological macromolecules and large cyclic ligands. In the arena of solvated systems, we added new physics models for polarization and transport to the TRAMONTO code, and made a large number of modifications to efficiently handle $O(1000)$ atom systems common to biology. Finally, we implemented an entirely new Fourier-space-based, matrix-free solution method (code FasTram) for solving the molecular theory equations that underpin the TRAMONTO code.

In the arena of applications, we began a variety of new studies as well as completed some begun earlier. We identified structural motifs for the DNA condensation with molecular dynamics simulations and published the results. Application of molecular theory code to calculating fluxes in gramicidin ion channels is under way. We completed initial investigations of electroporation, which led to acceptance of the manuscript "Self-Consistent Simulations of Electroporation Dynamics in Biological Cells Subjected to Ultrashort Electrical Pulses." Investigation of cyclic 9-mer polypeptides (nine peptide units linked together to form a ring) that are potential cancer drugs are under way with both the TRAMONTO and TOWHEE codes.

In the cellular modeling arena, we performed calculations of the interplay of intracellular sodium and calcium in neurotransmitter cells. We studied calcium waves in xenopus oocyte fertilization and found them to compare favorably with experimental observations. We noted that the cell modeling effort is tied to the molecular studies of ion channels in that the behavior of the neurotransmitter cells is largely dictated by channel behavior at the boundary of the cells. Molecular insight may add to the understanding of how those boundary conditions should be implemented.

We noted that the cell modeling effort is tied to the molecular studies of ion channels in that the behavior of the neurotransmitter cells is largely dictated by channel behavior at the boundary of the cells. Molecular insight may add to the understanding of how those boundary conditions should be implemented.

Refereed

Bright, J. N., J. Hoh, M. J. Stevens, and T. B. Woolf. 2001. "Characterizing the Function of Unstructured Proteins: Simulations of Charged Polymers Under Confinement." *J. Chem. Phys.* **115**: 4909.

Joshi, R. P., Q. Hu, R. Aly, K. H. Schoenbach, and H. P. Hjalmarson. 2001. "Self-Consistent Simulations of Electroporation Dynamics in Biological Cells Subjected to Ultrashort Electrical Pulses." *Physical Review* **64**: 11913.

Stevens, M. J. 2001. "Simple Simulations on DNA Condensation." *Biophysical Journal* **80**: 130.

10774

Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes

R. C. Hughes, S. M. Brozik, D. Y. Sasaki

Impedance-based, planar chemical microsensors are the easiest sensors to integrate with electronics. Sandia's goal is a several-order-of-magnitude increase in the sensitivity of this sensor type. We recently developed novel chemical sensors based on planar interdigitated microelectrodes coated with thin films of polyelectrolytes. The ion conductivity of ions doped into these films is sensitive to a wide range of volatile organic compounds (VOCs), including nerve agent simulants. We believe that the mechanism of detection involves reversible plasticization of the polymer chains, allowing faster ion motion that is detected by simple alternating current (AC) impedance at low frequencies (10 to 15 Hz). We have achieved parts-per-million-level sensitivities with these new devices, but to achieve an orders-of-magnitude increase in sensitivity, we are exploring ion motion (impedance) in very thin lipid bilayer capacitor membranes that are chemically tethered to our planar electrodes.

The basic idea is to mimic biological-chemical sensors that rely on changes in ion transport across very thin organic membranes for the sensing. The large increase in sensitivity over polyelectrolytes will come from molecular recognition elements like antibodies that bind the analyte molecule. We can tie the molecular recognition sites to the lipid bilayer capacitor membrane, and we can use a number of mechanisms to modulate the impedance of the lipid bilayers. These mechanisms include coupled ion channels, pore modification, and double-layer capacitance modification by the analyte molecule.

We succeeded in forming stable bilayers over templated sol-gel scaffolds and also over octadecyltri-chlorosilane (OTS) layers bonded to the platinum (Pt) surface. In both cases, we showed that gramicidin ion channels could be made to function and discriminate between cesium (Cs) ions and other ions.

We successfully satisfied our most important milestones by fabricating two kinds of supported lipid bilayers on our lipid chip electrode arrays, and by measuring their

We have achieved parts-per-million-level sensitivities with these new devices, but to achieve an orders-of-magnitude increase in sensitivity, we are exploring ion motion (impedance) in very thin lipid bilayer capacitor membranes that are chemically tethered to our planar electrodes.

properties by impedance spectroscopy. In addition, we fabricated biosensors with these bilayers by using selective ion channels that modulate the impedance of the bilayer with the concentrations of specific ions. The first kind of supported bilayer uses a thin film of templated sol-gel on the electrode to act as a scaffold for the bilayer. We formed lipid bilayers on the sol-gel by vesicle fusion and obtained electrical information about the bilayer. The electrical information comes from impedance spectroscopy taken over seven to eight decades in frequency. We can extract the capacitance of the bilayer and find, in most cases, the correct capacitance for a single bilayer. Every bilayer membrane has some ionic leakage. By looking in the right frequency range, we can also extract this membrane impedance, which tells us something about how many defects there are in the deposited bilayer and about the ionic seal around the edges of the electrode.

We have steadily improved our high-resistance values by perfecting the techniques for deposition. We also incorporated gramicidin ion channels in the bilayer membrane and showed selective chemical detection of Cs ions. The second kind of supported bilayer was composed of OTS and 1-palmitoyl-2-oleoyl-sn-glycero-3-phosphocholine. OTS was covalently attached to the substrate and acted as the lower leaf of the bilayer. We also showed gramicidin ion channels to function in this bilayer, which was rugged enough to still be functional after eight days. We demonstrated chemical selectivity of Cs ions over calcium (Ca) ions. The Cs ion transport gives a signal that tells us whether the gramicidin membrane protein is lined up with its partner in the lower leaf (or OTS layer, in the case of the hybrid).

To make a sensor for almost any molecule, we attach an antibody to that molecule to the gramicidins in the upper leaf, and when the target molecule binds, we should get a decreasing current due to the disruption of the aligned channels. To demonstrate this effect, we are developing the chemical methods to attach the antibody to the gramicidin. We biotinylated one-micron spheres and the antibody to biotin to show how a microbe (or large toxin molecule) could be captured by the labeled gramicidin and detected electrically. We expect results soon.

We have steadily improved our high-resistance values by perfecting the techniques for deposition. We also incorporated gramicidin ion channels in the bilayer membrane and showed selective chemical detection of Cs ions.

Other Communications

Branch, D. W., S. M. Brozik, and R. C. Hughes. 2001. "Detection of Biological Agents Using an Impedance-Based Biosensor." Paper presented to BioMEMS and Biomedical Nanotechnology, Columbus, OH, 22–25 September.

26581

Molecular-Scale Studies of Single-Channel Membrane Pores

A. R. Burns, T. A. Michalske, J. G. Fleming, D. Y. Sasaki, B. S. Swartzentruber, K. O. Evans, G. D. Bachand

Translocation of large biomolecules (e.g., proteins, deoxyribonucleic acid [DNA]) through single-ion-channel protein pores in membranes is an emerging technology that promises new rapid detection and sequencing approaches. However, experts cannot fully interpret the modulated ionic-current signals yet because too little is known about the molecular-level details of translocation.

Sandia will introduce a new experimental approach, based on proximal scanning-probe microscopy (SPM), to study the molecular-level structure and energetics and kinetics of biomolecule interactions with membrane pores during translocation. By implementing the proximal probes, we will supplement the existing macroscopic-ion current-detection approach and be able to (1) characterize the size and shape of a selected pore, (2) correlate local molecular interactions with ion currents, (3) directly measure the forces on translocating molecules, and (4) monitor atomic-scale movement of transmembrane pore proteins during translocation. This project will provide important new insights for molecular translocation through membranes. These insights, together with molecular simulations, are critical for emerging biotechnologies. We also plan to apply our approach to robust solid-state nanopores, created with silicon (Si)-micromachining techniques.

Based on designs supplied by our collaborators at Harvard University, we built a variable-temperature apparatus for measuring ionic current through single-ion channels in planar lipid bilayers. The apparatus comprises two reservoirs between which a small Teflon aperture can be positioned. We developed a technique to form 25 μ m apertures in a Teflon tube interconnecting the two reservoirs and inserted bilayer lipid membranes (e.g., diphytanoylphosphatidylcholine [DPPC]) across the aperture. We also acquired the necessary (patch-clamp) test and electronic equipment for measuring picoampere ionic currents. Solid-state pores less than 10 nm in diameter were created in Si by an innovative technique of overlapping trenches. We completed our instrument that

Sandia will introduce a new experimental approach, based on proximal scanning-probe microscopy (SPM), to study the molecular-level structure and energetics and kinetics of biomolecule interactions with membrane pores during translocation... This project will provide important new insights for molecular translocation through membranes. These insights, together with molecular simulations, are critical for emerging biotechnologies.

combines an inverted optical microscope with an atomic force microscope (AFM). We expect to demonstrate single-molecule force measurements. Transparent samples (in air or in a liquid cell) can be examined with high-numerical-aperture objectives for fluorescence collection and simultaneously imaged with the AFM for structural topography or force profiles. AFM imaging can be accomplished in two ways: (1) with a tube scanner that moves the probe tip over a stationary sample, or (2) with a flat scanner that moves the sample between the objective and the (stationary) probe tip. The first method is expected to yield the highest topographic resolution, but precise optical alignment with the objective focus is lost in large (greater than 500 nm) scans. The optical alignment is maintained in the second approach at the sacrifice of high-topographic resolution. We designed the microscope to take advantage of fluorescent labeling of biomolecules. Labeling the translocating biomolecule and/or labeling the protein pores will greatly complement force measurements, since fluorescence-resonance-energy transfer is very sensitive to unfolding and molecular-scale movements.

*We expect to demonstrate
single-molecule force
measurements.*

26582

Efficient Massively Parallel Techniques for Protein Structure Generation

M. D. Rintoul, M. G. Martin, M. P. Sears, A. Slepoy

Sandia is developing an enumeration technique that generates folded proteins matching distance constraints provided by cross-linking, multidimensional mass-spectrometry (MS) and nuclear magnetic resonance (NMR) experiments. While the protein folding problem has been shown to be nondeterministic polynomial (NP)-hard both on and off lattice, distance-geometry techniques can retrieve n -residue protein structures in quadratic time when $n(n-1)/2$ distance constraints are provided. Recent results demonstrate that on lattices, protein structures can be determined in linear time with only n distance constraints. Furthermore, current studies indicate that more than half of the n distance constraints can be acquired directly from the sequence data (i.e., secondary structure assignments). These findings represent a substantial gain from the state-of-the-art methods by drastically reducing the experimental effort required to compile distance information.

Sandia will extend the above results by developing an off-lattice technique that enumerates folded proteins from MS and NMR data. This technique includes a validation-and-refinement scheme that uses a hierarchy of high-fidelity objective functions ranging from bonded hard spheres in a vacuum to fully atomistic Lennard-Jones and coulombic sites in water. Both the enumeration and the molecular-physics techniques have been successfully adapted to massively parallel (MP) architectures in the past, and we expect to implement them in this fashion for this work.

We started our theoretical work on incorporating distance-constraint information by using a Hamiltonian-path model of a protein on a lattice. In this model, which is essential to a compact self-avoiding walk, we demonstrated that, unlike the general lattice model where n distance constraints were required to describe an n -residue protein, only approximately $n/2$ distances were required to completely describe the protein structure. More importantly, we then performed our simulations off-lattice to begin a truly realistic construction of a protein from real-space distance constraints. We devised an algorithm to compute which additional inter-

These findings represent a substantial gain from the state-of-the-art methods by drastically reducing the experimental effort required to compile distance information.

peptide distances were to describe a partially constrained protein structure and developed an additional algorithm to count the number of possible structures described by a set of constraints that did not rigorously fix a protein's structures. Using simulation, we showed that in general, short topological constraints (distances between peptides that were topologically close in the protein sequence) were the most useful kind of constraint. This is a very relevant practical result because secondary-structure identification can supply much information. Finally, we studied the effect of uncertainties on the distance constraints. The results were robust until the uncertainties began to approach 0.1 Å, and then the quality of the reconstruction decreased rapidly.

On the molecular-physics part of the simulation, we did much work in converting the TOWHEE Monte Carlo simulation code to prepare it to handle proteins. First, we extended periodic boundary conditions to include intramolecular interactions. Second, we added a single-atom translation move to augment the coupled-decoupled configurational bias move. This is useful for sampling conformations internal to the protein. Finally, we developed a program that automates the construction of the molecule configuration input file to allow simple simulation setup.

Using simulation, we showed that in general, short topological constraints (distances between peptides that were topologically close in the protein sequence) were the most useful kind of constraint. This is a very relevant practical result because secondary-structure identification can supply much information.

Refereed

Faulon, J. L., M. D. Rintoul, and M. M. Young. 2001. "Deterministic Inverse Imaging." Paper presented to the ACS National Meeting, Designing Focused Libraries for Drug Discovery Symposium, San Diego, CA, April.

26583

Mapping Membrane Protein Interactions in Cell Signaling Systems

M. M. Young, J. M. Faulon, J. S. Schoeniger, R. Behrens, Jr., C. B. Troup, R. B. Jacobsen, S. A. Datwyler

Sandia will apply the MS3D technique to determine the structure of the rhodopsin-transducin membrane-protein complex (RTC). We made progress in adapting the MS3D approach for characterizing membrane-protein systems and made computational progress in experimental design, data analysis, and protein-structure modeling. Preliminary experimental data—on a proof-of-concept membrane protein structurally homologous to rhodopsin, bacteriorhodopsin (BR)—shows that MS3D can be successfully modified to address membrane-protein systems. Theoretical calculations show that, given sufficient experimentally derived constraints, determining the structure of a membrane protein to low resolution is possible. Future work will focus on the application of the validated experimental and computational methods to the RTC structure determination.

Preliminary experimental data on a proof-of-concept membrane protein structurally homologous to rhodopsin, BR, shows that MS3D can be successfully modified to address membrane-protein systems. Sandia is working to develop the MS3D experimental protocol. We completed a series of control experiments with uncross-linked BR. These experiments demonstrate that all steps in the MS3D protocol (except the initial cross-linking step) can be performed with BR—namely, the separation, solubilization, and digestion of the monomeric fraction, and the acquisition of mass-spectrometry (MS) data on the proteolytic digest. Work is ongoing to characterize BR cross-linked with a series of cross-linking reagents.

Progress on the rhodopsin-transducin system is summarized as follows: We purified the components of the rhodopsin-transducin system—namely, rhodopsin from the rod outer membrane and all three components of the transducin heterotrimer. We developed a functional assay to ascertain whether we are cross-linking the RTC in a biologically significant state. We also designed methods to proteolyze both rhodopsin and transducin-alpha and to

Sandia is working to develop the MS3D experimental protocol. We completed a series of control experiments with uncross-linked BR. These experiments demonstrate that all steps in the MS3D protocol (except the initial cross-linking step) can be performed with BR—namely, the separation, solubilization, and digestion of the monomeric fraction, and the acquisition of mass-spectrometry (MS) data on the proteolytic digest. Work is ongoing to characterize BR cross-linked with a series of cross-linking reagents.

characterize the resultant peptide fractions using liquid chromatography (LC)/MS.

Computational progress is in the areas of experimental design, data analysis, and protein-structure modeling. We developed a prototype tool, MSDesign, to assist experimentalists with protease selection. The tool calculates the theoretical libraries of peptides and cross-linked peptides for a user-defined set of proteases. Also, this tool produces statistics on the total number of overlapping species, the number of overlapping cross-linked species, and the peptide coverage of the resolvable cross-linked species over a given parts-per-million error range. A new version of the spectrum-assignment program, ASAP, was developed to support flexible amino-acid modification and protease-specificity definitions, fully combinatoric-theoretical library generation, control-spectrum subtraction, and N14 and N15 peptide assignments. A modified form of this program supporting the assignment of protein-protein cross-linking data is near completion. We performed theoretical calculations both on- and off-lattice to enumerate the number of constraints required to uniquely determine a protein structure and to map the size of the solution space as a function of the number of provided constraints. Last, we performed distance-geometry calculations that show, given sufficient experimentally derived constraints (approximately 20), that determining the transmembrane-domain structure of a membrane protein is possible to low resolution.

We performed theoretical calculations both on- and off-lattice to enumerate the number of constraints required to uniquely determine a protein structure and to map the size of the solution space as a function of the number of provided constraints.

Refereed

Faulon, J., M. D. Rintoul, and M. M. Young. 2001. "Constrained Walks and Self-Avoiding Walks: Implication for Protein-Structure Determination." *J. Computational Biology*, submitted.

Young, M. M., C. B. White, S. Datwyler, R. Behrens, and J. Schoeniger. 2001. "The Solution of Integral Membrane-Protein Structures Using Chemical Cross-linking and High-Resolution Mass Spectrometry Methods." Poster presentation at the American Society for Mass Spectrometry (ASMS), Santa Fe, NM, May.

32574

High-Throughput Instruments, Methods, and Informatics for Systems Biology

D. M. Haaland, B. N. Wylie, K. W. Boyack, W. C. Sweatt, J. L. Rienstra, J. A. Timlin, M. B. Sinclair, C. M. Boney, S. M. Gentry, C. M. Wehlburg

Cell scientists, medical researchers, and security organizations working on biothreat assessments need much better instruments, together with better informatics and knowledge-management tools. These needs are especially critical in new high-throughput technologies, including gene- and protein-expression arrays. This project researches techniques, instrumentation, and algorithms that directly address improved data collection and new analysis techniques for dealing with large datasets; the project also addresses tools for integration with other Web-accessible resources. Current microarray technology allows only binary comparisons between the expression levels in control and treated cells in each experiment. Also, quantitative comparisons between microarray experiments are poor, thus limiting the information that can be gleaned from complex events.

Sandia designed and is building a new hyperspectral-imaging (HSI) microarray scanner to greatly improve the current microarray technology by using Sandia's multivariate-chemometric expertise and HSI capabilities. This technology will allow the comparison of up to 20 different cellular responses on a single microarray by simultaneously monitoring multiple fluorophores. The scanner is expected to improve the quantitative accuracy of gene expression and to improve speed; the University of New Mexico (UNM) will provide the biological expertise needed to understand the complex genetic response of cells to bioagents. With the new scanner and the collaborative-analysis tools that we are developing, we will be able to investigate a variety of opportunities such as the development of new biologically based biosensors for bioagents, protein detection, and understanding the genetic basis of cancer and its treatment.

We converted the information-efficient spectral imaging system (ISIS) from a telescopic passive-remote sensor to a microscopic HSI scanner with laser excitation. We upgraded ISIS hardware, rewrote control and data-analysis

Sandia designed and is building a new hyperspectral-imaging (HSI) microarray scanner to greatly improve the current microarray technology by using Sandia's multivariate-chemometric expertise and HSI capabilities. This technology will allow the comparison of up to 20 different cellular responses on a single microarray by simultaneously monitoring multiple fluorophores.

software and recalibrated ISIS for improved wavelength and intensity accuracy. We tested the modified system using inexpensive fluorophores, and fluorescence results from these studies compare favorably with independent fluorimeter measurements. Examination of ISIS data from binary mixtures of fluorophores with line focusing confirms the separation and quantitative profiling of the dyes using Sandia-developed multivariate-analysis methods. Early data indicate that in the current configuration, ISIS will be inadequate for monitoring low gene-expression levels. Therefore, we tested a second charge-coupled device (CCD) detector spectrometer system with higher sensitivity for low-fluorescence levels required to quantify large numbers of spectrally overlapping fluorophores. We obtained tagged deoxyribonucleic acid (DNA) microarray samples and initiated statistically designed studies to identify the parameters that limit the quantitation of gene expression on microarrays.

We investigated the use of robust measures of correlation and found that for large datasets the added computational cost is not warranted, but for smaller sets, the tool is useful. We worked with UNM and the National Center for Genomic Resources (NCGR) to complete two tasks. First, the NCGR GeneX database and upload tool were installed at UNM. Second, we demonstrated that V_xInsight™ (Visual Explanation and Insight, a tool for exploring data collections) can be served remotely using HTTP (Hypertext Transfer Protocol) and Web-based interfaces. We have made significant progress in making the tools more robust.

We worked with UNM and the National Center for Genomic Resources (NCGR) to complete two tasks. First, the NCGR GeneX database and upload tool were installed at UNM. Second, we demonstrated that V_xInsight™ (Visual Explanation and Insight, a tool for exploring data collections) can be served remotely using HTTP (Hypertext Transfer Protocol) and Web-based interfaces. We have made significant progress in making the tools more robust.

Refereed

Kim, S. K., J. Lund, M. Kiraly, K. Duke, M. Jiang, J. M. Stuart, A. Eizinger, B. N. Wylie, and G. S. Davidson. 2001. "A Gene Expression Map for *Caenorhabditis Elegans*." *Science* **293** (14 September): 2093–2098.

34491

Nanolaser Flowchip for Real-Time Cell and Tumor Biology

P. L. Gourley

Growing interest in biomicroelectromechanical systems (bio-MEMS) devices has brought attention to new issues involving interfacial phenomena of biological materials with semiconductor surfaces. One such device is the biocavity laser in which flowing cells interact with semiconductor surfaces. A technical problem is that the cells adhere to the surface and prevent fluid flow after a period of time. Sandia investigated the binding interactions of cells and proteins to the semiconductor surfaces used in these microcavity lasers. The study sought to determine how adhesion and biofouling can be attenuated using readily prepared coatings of thin organic films.

We deposited hydrophobic (alkane) and hydrophilic (oligoethylene glycol) coatings onto oxidized silicon (Si) and gallium arsenide (GaAs) by various techniques: self-assembled monolayers (SAMs), Langmuir-Blodgett (LB), and spin-casting. We exposed coated and bare surfaces to media containing cells (astrocytes, glioblastomas) and proteins (serum albumin) in flowing and static experiments to evaluate kinetic- and thermodynamic-adhesion phenomena. We used atomic-force microscopy (AFM) and optical microscopy to characterize the coatings and subsequent biofilm formation to evaluate materials for biocompatibility.

We flowed cells through a microfabricated structure composed of glass and semiconductor materials that formed an array of microchannels. If surface adhesion is strong, biofouling of the microchannels will occur, resulting in reduced fluid-flow rates. In addition to the measurement of flow rates, we conducted post-mortem analyses of the glass and semiconductor surfaces with optical microscopy to determine binding patterns that lead to biofouling. The results show that surfaces coated with hydrophilic SAM layers are much more resistant to biofouling than similar surfaces coated with hydrophobic layers.

We showed cell adhesion and biofouling to be dependent not only on surface functionality, but also on kinetic interactions of the biomaterial to the surface. Under flow

In addition to the measurement of flow rates, we conducted post-mortem analyses of the glass and semiconductor surfaces with optical microscopy to determine binding patterns that lead to biofouling.

conditions, astrocytes and glioblastomas exhibited little biofouling behavior on the hydrophilic Tapping-Mode Etched-Silicon Probe (TESP) surface, but strong channel clogging with the hydrophobic surface. These studies suggest future investigations of cellular adhesion on composite surfaces of hydrophilic and hydrophobic domains as well as complex functionality to further understand cell and protein adhesion.

Creating a smooth flow of biological cells through a microscopic channel in an optical device is far from simple. The problem is one encountered whenever scientists try to merge biological materials with microfabricated structures. These materials are poorly suited for each other. Proteins are large, sticky molecules that tend to adhere to glass, metal, and semiconductor surfaces, forming biofilms that foul the devices and quickly compromise their performance. Our device quickly demonstrated this problem. When we flowed the astrocytes and glioblastoma cells through our channels, they stuck on the downstream side of the channels. Within a few minutes, the device was severely clogged. Surfaces coated with hydrophilic SAM layers help to minimize this problem and are preferred over hydrophobic coatings. These layers increased fluid velocity and minimized cell sticking. We do not, however, consider the problem solved. Even with the surface treatments, the operation time of our biocavity laser is extended by only a factor of 3.

These studies suggest future investigations of cellular adhesion on composite surfaces of hydrophilic and hydrophobic domains as well as complex functionality to further understand cell and protein adhesion.

Refereed

Gourley, P. L., and D. Y. Sasaki. 2001. "1. Biocavity Lasers." (Invited review) *American Scientist* **89** (April/May): 152–159.

Computational and Information Sciences

The goal of the Computational and Information Sciences investment area is to develop next-generation computing and information systems capabilities that will provide a strategic benefit to the nuclear weapons program and other important Sandia business areas. Recent advances in massively parallel computing technology are greatly expanding the usefulness of computer simulations. Computational and information sciences proposals focus on system software for computer clusters, emergent behavior, adaptive software, and parallel input/output (I/O) visualization. A theme of these efforts is manipulating and interacting with large datasets. Another important aspect of this work is creating technologies that make high-performance computers easier to use and thus broaden the impact of such computing on Sandia's programs.

The "Large-Scale Nonlinear Optimization Arising from PDE Models" project has made significant progress toward the implementation of successive quadratic programming algorithms, which will significantly reduce the computational requirements for large-scale applications. The parallel optimization methods that are being developed will solve high-fidelity, coupled-physics problems that are too expensive to solve with existing

optimization capabilities. Collaboration with academia was developed through the Computer Systems Research Institute (CSRI) to study large-scale transient PDE (partial differential equation)-constrained simulation. Two patent applications have been filed as a result of this effort.

10313

Heterogeneous Simulation

F. J. Oppel, III, E. J. Gottlieb, P. G. Xavier

A recent Department of Energy study, "Roadmap for Robotics and Intelligent Machines," addressed the need for building intelligent machines as an integrated system of heterogeneous perception, reasoning, and action components. No generalized simulation framework exists to enable modeling behaviors of intelligent machines that depend on physical environments. Such a framework would require a heterogeneous simulation environment to model these intelligent machines operating in a real world containing different environments.

This project is developing a framework for building and testing heterogeneous simulations. Sandia's research enables the integration of several models residing on different platforms that often contain varying model fidelity. The framework will interface with existing simulation packages through either online access or offline data access. The framework will incorporate diverse simulation environments ranging from continuous simulations (modeling physics such as dynamics, radiation, and plumes) to event-based simulations (e.g., modeling agent behaviors, state machines).

We developed a simulation framework (UMBRA) to enable building simulation environments to examine the behaviors of intelligent agents/machines in complex heterogeneous environments. Our final accomplishments built on our previous achievements (i.e., basic UMBRA framework design, multimodel methodology, and online connector module) to include the offline connector method and the fidelity-switching scheme. We demonstrated these capabilities in a simulation of autonomous intelligent agents executing a complex collective behavior.

The design of the "offline" connector enables precomputed data from an external simulation program to flow from an UMBRA module into the heterogeneous run-time environment. This allows interfacing to central processing unit (CPU)-intensive simulation programs, such as route planners for intelligent agents, to include the data results into the run-time environment. In addition, the "offline" connector interface can interrogate the external simulation during runtime to update the dataset as required.

This project is developing a framework for building and testing heterogeneous simulations. Sandia's research enables the integration of several models residing on different platforms that often contain varying model fidelity. The framework will interface with existing simulation packages through either online access or offline data access.

The fidelity-switching scheme allows the heterogeneous simulation environment to model and switch between different levels of fidelity during runtime. For example, an object within a simulation may contain different levels of dynamic state such as a nonconstrained dynamic motion, a constrained contact dynamic motion, and a stationary condition. A rigid-body contact simulation demonstrated modeling an object that could detect its state and reconfigure the UMBRA modules to provide the appropriate fidelity. This enables the heterogeneous simulation environment to improve its computational efficiency, since the simulation will execute the CPU-intensive algorithms (contact dynamics) when required, or switch to less-intensive algorithms (static condition). Another example demonstrated switching different behaviors of a controller module for an intelligent agent, depending on the environment surroundings.

During the final year of this project, we demonstrated this heterogeneous modeling capability in an event-based, modular, distributed simulation environment. We selected the high-level architecture (HLA) as an evaluation environment to provide a distributed simulation interface. To incorporate the HLA interface environment, we utilized the multimodel methodology to provide an HLA UMBRA world module. This world module utilized the UMBRA Module Factory to create UMBRA HLA interface modules to connect to UMBRA computational modules. We selected as a test case a previous heterogeneous simulation of a swarm of intelligent agents communicating and searching for a plume in a building. This simulation initially contained several UMBRA computational modules: a behavior, controller, sensors, and physics modules. We added an additional UMBRA HLA module per agent to communicate the agent state information to another UMBRA HLA module executing in a stealth simulation on another computer. The stealth simulation only required the UMBRA HLA module and UMBRA geometry module to track the position and state of the corresponding objects in the publishing simulation.

The accomplishments of this project are providing significant impacts on several Sandia projects and HLA military simulations. This project sets the foundation to perform heterogeneous system analysis of intelligent agents (combination of machines with humans) for security or military operations in urban environments and/or Homeland Defense operations.

The accomplishments of this project are providing significant impacts on several Sandia projects and HLA military simulations. This project sets the foundation to perform heterogeneous system analysis of intelligent agents (combination of machines with humans) for security or military operations in urban environments and/or Homeland Defense operations.

10314

Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions

D. E. Small, J. P. Luck, J. J. Carlson

This project will develop sensing, parallel-processing, and geometric-reasoning algorithms to enable unobtrusive human-computer interactions. Our approach is to leverage two unique Sandia capabilities: volumetric video motion detection (VVMD) and large-scale computing. Unprecedented human-machine interactions will be demonstrated through dramatic advances to the VVMD. By developing new parallel-processing algorithms and a new personal computer (PC)-cluster deployment architecture, we will extend the resolution of the current VVMD platform to its attainable limits. We will move from platforms that make video-rate constructions of several hundred volume elements (voxels) to platforms that update millions of voxels in real time. We will also develop robust geometric-reasoning algorithms to interpret the constructions.

We will demonstrate two scales of human-computer interaction. On a small scale, the VVMD will monitor a small volume (several cubic feet) directly in front of a computer monitor. A person will interact with the computer through a combination of gestures and voice commands. This system could replace or augment a keyboard and mouse. On a larger scale, the VVMD will monitor the position and orientation of one or more humans in a room-sized volume. Differentiating itself from other position/orientation sensors, the VVMD allows participants to maneuver untethered, thus allowing more natural human-machine interactions. By combining a VVMD at this scale with a state-of-the-art video wall and visualization platform, participants could use simple gestures to browse through high-fidelity simulation results and to collaborate with remote participants. Another application at this scale is a robotic work cell, where an operator can point at an object and gesture to cause the robot to move the object to a new position.

We achieved the following goals:

- The software can fit a fully articulated 3-D human model to the volumetric data. This includes 22 degrees of freedom.

A person will interact with the computer through a combination of gestures and voice commands. This system could replace or augment a keyboard and mouse. On a larger scale, the VVMD will monitor the position and orientation of one or more humans in a room-sized volume. Differentiating itself from other position/orientation sensors, the VVMD allows participants to maneuver untethered, thus allowing more natural human-machine interactions.

- We optimized the 3-D fitting algorithms so they can run in real time on modern computer architectures.
- We can drive an articulated human avatar in real time and use it to interact with another person from a remote location. This enables a “3-D conference call” between users. As a part of this work, we can generate novel synthetic views of the 3-D data using advanced texture-mapping techniques.
- We developed new and innovative color image-processing techniques for motion detection and integrated them into the sensor.
- We continued development of voice-gesture-interaction techniques for high-fidelity simulations.

We also addressed the following issues, which experts in the field have identified as major problems in markerless motion tracking:

- (1) The majority of previous work assumes the 3-D model is known *a priori*.
- (2) Most systems cannot handle significant occlusion and do not have mechanisms to stop and restart tracking of individual body parts.
- (3) Few body models have incorporated articulation constraints or collision constraints.
- (4) No systems have compared their results to ground truth.
- (5) Few systems have used 3-D data as direct input to their tracking system. Using 3-D data relieves the problems associated with retrieving 3-D information from a 2-D view.

A system must also perform tracking in real time to be useful for most applications. Calibration of the data-acquisition device must be simple and fast.

We can drive an articulated human avatar in real time and use it to interact with another person from a remote location.

This enables a “3-D conference call” between users.

Refereed

Luck, J. P., and D. E. Small. 2001. “Real-Time Tracking of Articulated Human Models Using a 3-D Shape-from-Silhouette Method.” *Lecture Notes in Computer Science 1998* 1 (Robot Vision 2001, Auckland, New Zealand, February): 19–26.

10315

Hybrid Sparse-Dense Incomplete Factorization Preconditioners

M. A. Heroux, J. N. Shadid, R. R. Rao, P. R. Schunk

Development of robust scalable linear equation solvers persists as one of the most important and elusive goals in large-scale scientific and engineering computing. With continued progress in parallel applications development and steady advances in availability of parallel computers, the lack of robust scalable solvers increasingly becomes a critical roadblock to progress in the use of numerical simulation for engineering and scientific disciplines. In the past few years, many key Sandia applications have been ported to parallel computers, a large number of them requiring a linear solver. With few exceptions, these codes face the difficult task of finding a robust parallel solver. Since preconditioned iterative solvers are the methods of choice, and because basic iterative methods have reached a high level of maturity, the real heart of the challenge is the need for robust parallel preconditioners.

This project will develop a set of preconditioners in the TRILINOS/AZTEC framework that directly addresses the problems of robustness and scalability for key applications on current and future parallel computers. This work is unique in that it brings together the strengths of existing sparse solver technology into a single preconditioner framework that can be tuned to match the needs of the most challenging problems of today. By imposing a block partitioning on the linear operator (or a recursive set of such partitionings) that matches the underlying physics of the application and then developing block preconditioners based on this partitioning, we open up the ability to have a full spectrum of robustness and scalability. In addition, within this framework we can exploit in a very natural way the memory hierarchies of parallel computers like Computational Plant (CPlant) and can simultaneously leverage the past investment in both distributed- and shared-memory parallel-programming techniques.

In the final year of this project, we made significant progress in putting the algorithmic advances from our previous work into use with production users. We refined the diagonal perturbation methods that we developed previously,

This work is unique in that it brings together the strengths of existing sparse solver technology into a single preconditioner framework that can be tuned to match the needs of the most challenging problems of today. By imposing a block partitioning on the linear operator (or a recursive set of such partitionings) that matches the underlying physics of the application and then developing block preconditioners based on this partitioning, we open up the ability to have a full spectrum of robustness and scalability.

and we worked with GOMA code users to learn the most effective strategies for using these methods. The diagonally perturbed incomplete lower/upper with threshold (ILUT) factorization preconditioners with adaptive perturbations has become the preconditioner of choice for most difficult GOMA problems. With some exceptions, we are able to solve problems of interest; however, for the most difficult problems, the cost of the preconditioner and the required expertise of the user are still too high.

We documented our progress on several test problems of practical and academic importance. Most notably, we can solve each problem initially identified as an important test case at project start-up. We also can solve the viscoelastic models that we started with, a deformable roller-nip problem, and a brazing problem, each of which was intractable when we started this project.

As part of this and other projects, we produced several general-purpose software packages that are used with GOMA and across an increasing list of other applications. In particular, the TRILINOS solver framework was initially developed for use with GOMA, as was IFPACK, the C++ incomplete factorization package. The PETRA distributed matrix and vector services package also was partly developed. TRILINOS, IFPACK, and PETRA are all copyrighted and are going through the process for public release under the Lesser Gnu Public License.

The final area of importance was getting GOMA to run well on CPlant parallel computers. During earlier work on this project, we ported GOMA to CPlant. Now, we have seen that port become an important vehicle for GOMA users. CPlant is an excellent platform for GOMA and is becoming a preferred platform for users who have large GOMA problems. Execution of GOMA in parallel on CPlant is excellent when compared to use of SOLARIS platforms, both in single-node performance and in speedup on multiple processors for sufficiently large problems.

*... we produced several
general-purpose software
packages that are used with
GOMA and across an
increasing list of other
applications.*

Other Communications

Heroux, M. A. 2001. "Dynamic Parallel Data Redistribution for Preconditioned Iterative Solvers." Paper presented to the SIAM Parallel Processing Conference, Norfolk, VA, March.

Heroux, M. A. 2001. "Object-Oriented Design Issues in the TRILINOS Project." Presentation to Workshop on Object-Oriented Software for Scientific Computing, Livermore, CA, July.

Heroux, M. A., and K. W. Kampshoff. 2001. "Observations on the Use of Heterogeneous Parallel Clusters for Scientific Computing." Paper presented to the SIAM Parallel Processing Conference, Norfolk, VA, March.

Kampshoff, K. W. 2001. "Parallel Sparse Matrix Computations on Beowulf Clusters." Senior Thesis, Department of Computer Science, St. John's University, Collegeville, MN (May).

Schunk, P. R., and M. A. Heroux. 2001. "Iterative Solver Preconditioners for Finite Element Formulations of Multiphysics Problems Including Incompressible Fluid and Solid Mechanics." *Proc. International Conference on Computational Engineering* **1** (Puerto Vallarta, Mexico, August).

10316

Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry

R. C. Schmidt, T. E. Voth, P. E. Desjardin, T. M. Smith, A. R. Kerstein

In this project, Sandia aims to advance the algorithms and methods for large-eddy simulation (LES) for unstructured grids, irregular geometry, and coupled physics. The current emphasis is on developing and demonstrating an LES subgrid closure strategy based on the one-dimensional turbulence (ODT) model. The goal of our research is to demonstrate a new approach for LES, high-Reynolds-number, wall-bounded flows that avoid the overwhelming computational expense of finely resolved three-dimensional (3-D) mesh near walls, and that are applicable to coupled multiphysics flows. Until now, accurate LES of turbulent wall-bounded flows required extremely fine meshes that are unaffordable for most engineering problems. Approximate near-wall models presently used are unreliable and incapable of treating complex flows and multiphysics environments.

ODT is a stochastic simulation method representing the time evolution of a turbulent profile along a notational line of sight, which in this application is taken to be the wall-normal direction. In the near-wall region, finely resolved ODT lines are embedded within a coarse LES mesh, and the ODT evolution equations capture the fine-scale temporal and spatial variations (in one direction) of the three-component velocity field.

We present details of the new near-wall closure model and perform calculations for turbulent channel flow at Reynolds numbers based on friction velocity ranging from 395 to 10,000. In addition, we give a mathematical description of a generally applicable ODT-based subgrid closure model for LES that is valid for any region of flow (i.e., not only near the wall). We also describe and discuss a separate LES-related task that involved LES calculations of isotropic turbulence decay in a box comparing lumped mass projection (LMP) and reproducing kernel particle method (RKPM) filtering for dynamic models on irregular (randomized) LES meshes.

Until now, accurate LES of turbulent wall-bounded flows required extremely fine meshes that are unaffordable for

We present details of the new near-wall closure model and perform calculations for turbulent channel flow at Reynolds numbers based on friction velocity ranging from 395 to 10,000.

most engineering problems of interest. Approximate near-wall models presently used are unreliable and incapable of treating complex flows and multiphysics environments. Our major accomplishment in our most recent work was the continued development, implementation, and testing of a new near-wall subgrid model based on the ODT modeling approach (Kerstein).

The development of ODT as a subgrid model required significant revisions to the stand-alone ODT model and numerous innovations to couple the LES and ODT approaches. Key issues addressed included (1) revising the ODT evolution equations to properly account for advection effects, (2) relating ODT variables to LES variables and providing proper ODT/LES interface boundary conditions, (3) determining how to address continuity constraints on the 3-D control volumes associated with the one-dimensional (1-D) ODT domains, (4) developing a method for triplet-mapping into the LES domain, and (5) devising a revised fractional-step (projection), time-integration scheme that allows for the two-way coupling between ODT (which evolves at direct numerical simulation [DNS]-like time steps) and the global LES solution.

The base LES code used for testing the near-wall ODT subgrid model was a structured grid, second-order, finite-difference code specifically designed for doing channel flow. We obtained the code from Stanford University through our collaboration with the Center for Turbulence Research. ODT/LES coupling is bidirectional and occurs both through the direct calculation of the subgrid turbulent stress by temporally and spatially filtering the ODT-resolved momentum fluxes (upscale coupling), and through the LES-resolved mean pressure and velocities impacting the ODT behavior (downscale coupling). In the approach developed here, the equations simulating the turbulent flow are distinct in each of the three flow regions, which we refer to as (1) the ODT inner region, (2) the LES/ODT overlap region, and (3) the LES core-flow region.

To demonstrate the performance of ODT as a subgrid model for LES, we performed calculations for turbulent channel flow at Reynolds numbers based on friction velocities ranging from 395 to 10,000. We compared these results to DNS and experimental data and found that remarkably good results were obtained over the entire Reynolds-number range. Although computational cost was not quantitatively addressed, all results were obtained on single-processor workstations,

Our major accomplishment in our most recent work was the continued development, implementation, and testing of a new near-wall subgrid model based on the ODT modeling approach (Kerstein).

with runtimes varying from several hours for the lower Reynolds-number flows to several days for the highest Reynolds-number flows. These results demonstrated the cost effectiveness of the approach and provided data for determining how the approach will scale to extremely large problems.

Other accomplishments included:

(1) The development and mathematical description of a generally applicable ODT-based subgrid closure model for LES that is valid for any region of flow (i.e., not only near the wall); and

(2) Calculations of isotropic turbulence decay in a box comparing LMP and RKPM filtering for dynamic models on irregular (randomized) LES meshes.

These results demonstrated the cost effectiveness of the approach and provided data for determining how the approach will scale to extremely large problems.

Refereed

Schmidt, R. C., A. R. Kerstein, S. Wunsch, and V. Nilsen. 2001. "Near-Wall LES Closure Based on One-Dimensional Turbulence Modeling." *J. Computational Physics*, submitted.

Other Communications

Desjardin, P. E., T. M. Smith, and C. J. Roy. 2001. "Numerical Simulations of a Methanol Pool Fire." *Proc. 39th AIAA Aerospace Sciences Meeting and Exhibit, AIAA Paper 2001-0636* (Reno, NV, 8–11 January).

Kerstein, A. 2001. "High-Fidelity Subgrid Closure of Turbulent Flow Simulations Using a One-Dimensional Stochastic Method." Invited feature article prepared for *Computer Physics Communications*.

10317

Molecular Simulation of Reacting Systems

A. P. Thompson, F. B. Van Swol

Reacting systems are critical in a wide variety of materials problems central to Sandia's missions, including polymer oxidation, epoxy curing (encapsulation), corrosion, reactive spreading and wetting (solder), and reactive equilibria in hazardous waste. In many cases, significant resources were focused on molecular simulation of equilibrium and transport properties of materials in which chemical reactions play an important role, but the reaction events have been either completely ignored or greatly simplified. For example, in polymer aging it is likely that on some short-length scale, the oxygen-reaction and -diffusion processes are linked. Any truly predictive model of the chemical and physical processes underlying aging must include this reactive/diffusive linkage.

The primary focus of this project is to introduce chemical reaction models into existing materials simulation models. Two different classes of model were targeted: continuous forcefield molecular dynamics (MD) and hard-sphere MD. We continued two major efforts to incorporate reaction models into these existing molecular simulation codes. For continuous forcefield MD, we extended the Monte Carlo (MC) reaction capability to include bond-breaking. To do this within the spatial decomposition parallel-processing framework of the Large-Scale Atomic/Molecular Massively Parallel Simulator (LAMMPS) code, we implemented a general checkerboarding procedure for avoiding conflicts between reactions on neighboring processors. We used the code to examine a model hydrocarbon system in which the molecular weight can grow by linear growth and decrease by random chain scission. We are currently developing a capability to simulate chemical aging of organic polymers by auto-oxidation.

For the discontinuous forcefield MD (tethered hard-sphere-based polymers), we have implemented the polymerization reaction capability for both forming and breaking bonds. Two options exist for the reaction criterion. One is stochastically based, while the other is more firmly based on reaction kinetics using the energy and angles of collisions. The latter approach exploits the event-driven

We continued two major efforts to incorporate reaction models into these existing molecular simulation codes. For continuous forcefield MD, we extended the Monte Carlo (MC) reaction capability to include bond-breaking. To do this within the spatial decomposition parallel-processing framework of the Large-Scale Atomic/Molecular Massively Parallel Simulator (LAMMPS) code, we implemented a general checkerboarding procedure for avoiding conflicts between reactions on neighboring processors.

algorithm that underlies hard-sphere dynamics. The tethered chains can now account for bond-angle potentials through the use of nonadditive diameters.

For continuous forcefield MD, we implemented both the MC bond-breaking and bond-making capabilities. We accomplished this using a general parallel algorithm, which enables us to simulate large systems without any conflicts between reactions on different processors. So far, the code has been used to study two different reacting systems:

(1) *Linear polymer growth.* We observed that trapping the reactive end inhibits the polymerization rate in two dimensions but not in three dimensions.

(2) *Hydrocarbon cracking/reforming.* We find that at low scission/addition ratios, the average molecular weight passes through a maximum before reaching a stable dynamic equilibrium.

We are currently adding the capability to simulate chemical aging of organic polymers by auto-oxidation.

In the case of the hard-sphere MD, we introduced bond-making events to simulate linear polymer growth. Two options exist for the reaction criterion. One is stochastically based, and the other is more firmly based on reaction kinetics using the energy and angles of collisions. The latter approach exploits the event-driven algorithm that underlies hard-sphere dynamics. The tethered chains can now account for bond-angle potentials through the use of nonadditive diameters. We used the code to study polymer wall interfaces focusing on both melts and solutions.

The results of this study have appeared in three publications and will be used to look at reactions at interfaces.

... we implemented both the MC bond-breaking and bond-making capabilities. We accomplished this using a general parallel algorithm, which enables us to simulate large systems without any conflicts between reactions on different processors.

10318

Massively Parallel Global Climate Model for Paleoclimate Applications

M. B. E. Boslough, T. R. Guilinger

Global climate has recently become recognized as a national security issue and has been identified by the Department of Energy's Office of Energy Research as important to decision making on many issues relating to stewardship of the planet. The potential economic costs associated with climate change are enormous, but so are the costs of policies designed to avoid or minimize climate change. Predictive climate models must be developed, but the time scales of global climate change preclude validation before the damage is done. Thus, there will always be an element of uncertainty as to how good the models are and whether or not they should be trusted.

One of the most notable successes in recent years was the ability of climate modelers to accurately hindcast the time-dependence of global temperature changes in the twentieth century. This breakthrough resulted from the addition to the radiative transport model of the opacity of sulfate aerosol pollution and boosted the credibility of climate modeling in general. Another validation strategy is to take advantage of the Earth's geologic history to test the predictability of climate models in hindcast mode using paleoclimatic data.

We believe that successful paleoclimate models will lead to further gains in climate-modeling credibility. The purpose of this project is to parallelize a widely used paleoclimate code to take advantage of the massively parallel environments that are becoming available. We expect this project to form a climate-modeling nucleus at Sandia that can grow as the role of the national labs in climate modeling increases, with Sandia in the leadership position in paleoclimate modeling.

We successfully ported the paleoclimate workhorse code GENESIS to the Computational Plant (CPlant) and converted its parallelism from shared memory to distributed memory using message-passing interface (MPI). This accomplishment required a fundamental change in the parallel decomposition so that they are all over latitude strip domains, instead of the various types of decomposition used in the shared-memory version. With over 99 percent of the code

Global climate has recently become recognized as a national security issue and has been identified by the Department of Energy's Office of Energy Research as important to decision making on many issues relating to stewardship of the planet.

parallelized (in terms of runtime of the serial version), we achieved a speedup of four times that of the shared-memory parallel version at R15 resolution. T106 (1° -by- 1°) resolution runs 20 times faster than the National Center for Atmospheric Research (NCAR) serial version on 20 nodes of the CPlant.

We continued the performance enhancements of our distributed-memory parallel version of GENESIS, reaching a speedup comparable to that of PCCM (parallel community climate model) for some resolutions and configurations. We identified further areas for significant improvements to be made in the current parallel code in terms of file I/O (input/output) and memory management. We continued our impact-induced climate change research in collaboration with the University of New Mexico.

We made significant improvements in the speedup of the parallel version, reaching 21 times the speed of the serial version, and 4 times the speed of the shared-memory version. On the CPlant, we can now achieve nearly 14 model years per CPU (central processing unit) day at T31 (spectral truncation limit) resolution. Typical paleoclimate model runs of 20 to 30 years can now be performed in a couple of days. This compares to 3 model years per day with the old version of GENESIS for the PMESH Cray SV1 at Penn State and gives us a version with which we can do production runs. We further sped up the code by parallelizing over spectral coefficient and performing sums as MPI reduction operations during the spectral domain portion of the computation, thus reducing the communication required every time step.

We also identified areas for future improvements, including the redimensioning of all global arrays so that only memory that is used is actually allocated. This redimensioning will decrease latency time for communication as well as pipelining during loops. We can also speed up the communication associated with the spectral transform by another factor of two. If higher-resolution simulations are needed by the paleoclimate community, we can do our parallel decomposition over longitude in addition to latitude. Our latest parallel version of GENESIS now has the option of running at T63 and T106 resolutions, for which our distributed-memory parallelism has the greatest speedup, due to the higher computation/communication ratio.

We made significant improvements in the speedup of the parallel version, reaching 21 times the speed of the serial version, and 4 times the speed of the shared-memory version. On the CPlant, we can now achieve nearly 14 model years per CPU (central processing unit) day at T31 (spectral truncation limit) resolution.

Refereed

Boslough, M. B. E. 2001. "Impact-Induced Climate Change Due to an Orbiting Debris Ring." *Proc. 20th Annual International Space Development Conference (ISDC) 2001* 1 (Albuquerque, NM, 24–28 May): 9.

Fawcett, P. J., and M. B. E. Boslough. 2001. "Climatic Effects of an Impact-Induced Equatorial Debris Ring." *J. Geophysical Research: Atmospheres*, in review.

10728

Algorithmic Advances in Computational Structural Biology

R. D. Carr, W. E. Hart, M. J. Collins, S. J. Plimpton, A. M. Johnston

The protein database (PDB) contains data on the folding structures of thousands of proteins and is likely to grow considerably. An appropriate analysis of these data may produce a biologically relevant clustering of the PDB proteins, which would be useful in predicting protein function and for other aspects of biology and genomics. Sandia has the resources and expertise to become a leader in this effort.

The research for this project attempts to make a clustering of proteins based on making pairwise computations of the similarities in protein structure by using a numerical combinatorial optimization measure. We formulated and solved or approximated instances of the combinatorial optimization problem maximum contact map overlap (max CMO) and made preliminary checks of its biological validity.

Max CMO gained acceptance in the computational biology community as an important measure of protein structure similarity. But the intractability of this NP (nondeterministic polynomial) hard-to-calculate measure has discouraged its use. However, for clustering purposes, finding a good approximation to the numerical similarity score between two proteins indicated by an optimal solution to max CMO is sufficient. Upper bounds to this score can be obtained efficiently by linear programming (LP) methods. Lower bounds can be obtained by using genetic algorithms (GAs) and local search. Lower bounds (and exact solutions) can also be obtained through branch-and-cut using our Parallel Integer and Combinatorial Optimization (PICO) software. When the difference between upper and lower bounds is small, the scores that our methods obtained are validated in their accuracy. Most major stumbling blocks to performing these computations efficiently and accurately are being overcome; hence, we plan to calculate these upper and lower bounds soon, in parallel on Computational Plant (CPlant).

(1) We successfully cast pairwise protein structure comparison as a combinatorial optimization problem (max CMO). Specifically, we seek the largest common subgraph of two contact maps that preserves the amino acid ordering on

An appropriate analysis of these data may produce a biologically relevant clustering of the PDB proteins, which would be useful in predicting protein function and for other aspects of biology and genomics. Sandia has the resources and expertise to become a leader in this effort.

each backbone. A contact map for a protein is a graph containing information about how that protein is folded.

(2) We devised a linear integer model for max CMO, which uses bipartite matchings both between vertices and between edges of two contact maps.

(3) We determined max CMO to be a variation of maximum independent set (MIS) involving perfect graphs. We showed that for problems similar to max CMO, the integrality gap (showing how closely the linear model approximates the integer answer) is no worse than $\log(n)$. For MIS, the integrality gap is as bad as $\sqrt{n}$.

(4) Using the independent set structure, we found strong clique cutting planes that tighten our linear formulation.

(5) There is a polynomial characterization of the cliques of a perfect graph. Using this structure of perfect graphs, we found efficient separation algorithms for these cutting planes; i.e., based on our current optimal fractional solution (which is infeasible for the combinatorial problem), we can determine which cutting planes to add to eliminate this solution from our current linear model.

(6) We found polynomial size linear formulations of our separation algorithms.

(7) We found a way of incorporating all the above cutting planes into one bigger but polynomial size linear formulation in a higher dimensional space. To do this, we used the dual of the formulation in accomplishment 6, above.

(8) We strengthened the correspondence in our linear model between the bipartite matching between vertices (x -variables) and that matching between edges (y -variables). Our objective function has only y -variables, but a stronger correspondence makes cutting planes in the x -variables have an effect on these y -variables.

(9) We broke up max CMO problem instances into smaller pieces using novel methods, making solving our linear formulation manageable in terms of both time and memory.

(10) We developed GAs with flexible input parameters. We found values for the input parameters that enabled us to find solutions close to our LP bound in many cases.

We strengthened the correspondence in our linear model between the bipartite matching between vertices (x -variables) and that matching between edges (y -variables). Our objective function has only y -variables, but a stronger correspondence makes cutting planes in the x -variables have an effect on these y -variables.

Refereed

Carr, R., and G. Lancia. 2001. "Compact Versus Exponential Size Relaxations." *Operations Research Letters*, accepted.

Carr, R., G. Lancia, B. Walenz, and S. Istrail. 2001. "101 Optimal PDB Structure Alignments: A Branch-and-Cut Algorithm for the Maximum Contact Map Overlap Problem." *Recomb. Proc.* **5** (Montreal, Canada, 22 April): 100–110.

Other Communications

Carr, R., G. Lancia, and S. Istrail. 2000. "Branch-and-Cut Algorithms for Independent Set Problems: Integrality Gap and an Application to Protein Structure Alignment." Sandia Technical Report SAND2000-2171, Sandia National Laboratories, Albuquerque, NM (September).

10757

Large-Scale Nonlinear Optimization Arising from PDE Models

B. G. van Bloeman Waanders, A. G. Salinger, M. S. Eldred, P. T. Boggs, K. R. Long, R. A. Bartlett

The research of large-scale partial-differential equations (PDE)–constrained optimization methods has enabled significant progress toward developing methods, tools, and general algorithms. Researchers have, however, identified difficult interfacing issues and complex characteristics associated with large-scale multiphysics simulation codes, forcing additional research directions.

One of the key outcomes of Sandia's development and testing of sequential quadratic programming (SQP) methods has been the realization of the many complicating characteristics related to the Sandia simulation environment. In particular, transients, multiphysics, and heterogeneous computing are common to many Sandia codes, causing complicating issues such as inexactness of the state Jacobian, nonsmooth behavior, local residuals, and inefficient computing environments. We addressed many of these issues through our developments, but some require further investigation.

Previously, we developed and tested effective tools on real production problems. Our remaining goals are to complete large optimization problems on Computational Plant (CPlant) and to find ways to package our tools in a practical and accessible manner under general frameworks, such as DAKOTA, SIERRA, and IDEA. The impact of this work will be realized not only through development of methods, tools, and algorithms, but also through creating powerful design environments so that the momentum of using optimization tools continues to grow.

The large-scale PDE–constrained optimization project has made significant progress in the area of software development, application testing, refinement of research directions, publications, presentations, and collaborations. We selected an object-oriented framework as our primary reduced-space SQP (rSQP++) development framework and added new algorithms to provide a flexible PDE simulation interface and to improve the stability associated with inexact Jacobians. Although rSQP++ runs in parallel on a small number of processors, in its current form the algorithms will

One of the key outcomes of Sandia's development and testing of sequential quadratic programming (SQP) methods has been the realization of the many complicating characteristics related to the Sandia simulation environment. In particular, transients, multiphysics, and heterogeneous computing are common to many Sandia codes, causing complicating issues such as inexactness of the state Jacobian, nonsmooth behavior, local residuals, and inefficient computing environments. We addressed many of these issues through our developments, but some require further investigation.

not scale. We designed and implemented new classes of transformation and reduction operators so that state vectors can be decomposed and communicated efficiently in large-scale optimization problems. A significant amount of work remains to propagate these new classes throughout the code. Testing of a chemical vapor deposition (CVD) reactor problem demonstrated an order-of-magnitude improvement in compute cost over a black-box approach.

Limited memory capabilities were added to O3D to effectively solve large-scale PDE-constrained problems using a full-space solution technique. Development of a symbolic simulator (Sundance) continues and has proven to be a very useful prototyping and testing vehicle. We developed a special proxy vector method to manage heterogeneous computing environments. This critical capability allows the investigators to manage the complexity of remote heterogeneous compute environments, and also to manage the many different components needed to solve a large-scale PDE-constrained optimization problem.

Our academic collaborations have grown significantly as a result of this research and development work.

Testing of a chemical vapor deposition (CVD) reactor problem demonstrated an order-of-magnitude improvement in compute cost over a black-box approach.

Refereed

Kearsley, A. J., J. W. Tolle, and P. T. Boggs. 2001. "Hierarchical Control of a Linear Diffusion Equation." *Springer Verlag Lecture Notes in Computational Science and Engineering*, accepted.

Long, K. R. 2001. "A Rapid-Prototyping Tool for Parallel PDE-Constrained Optimization." *Springer Verlag Lecture Notes in Computational Science and Engineering*, accepted.

Salinger, A. G., R. P. Pawloski, J. N. Shadid, B. G. van Bloemen Waanders, R. A. Bartlett, G. C. Itle, and L. T. Biegler. 2001. "rSQP Optimization of Large-Scale Reacting-Flow Applications with MPSalsa." *Springer Verlag Lecture Notes in Computational Science and Engineering*, accepted.

Other Communications

Van Bloemen Waanders, B. G., A. G. Salinger, R. P. Pawloski, L. T. Biegler, and R. A. Bartlett. 2001. "Simultaneous Analysis and Design Optimization of Massively Parallel Simulation Codes Using an Object-Oriented Framework." Paper presented to the 10th SIAM Conference on Parallel Processing for Scientific Computing, Norfolk, VA, 12 March.

10777

Parallel Methods for Coupling Circuit- and Device-Scale Simulations

S. A. Hutchinson, E. R. Keiter

The focus of this project is to research parallel coupling schemes between semiconductor device-level simulation and circuit-level simulation. The motivation for this research is multifold. Device-level simulation, which is based on solving a set of partial differential equations (PDEs) on a discrete spatial mesh, is generally too demanding for application to an entire circuit. However, many device problems of interest are only meaningful in the context of a complete circuit. A coupled approach can be a good compromise. Much of the progress on this project has been dependent on the maturation of the XYCE analog circuit simulator.

We completed the 1-D PDE diode model begun earlier and have added enhanced physics. Also, we implemented the initial two-dimensional (2-D) PDE device infrastructure and added several key infrastructure capabilities, including support for dynamically sized devices (e.g., PDE grids), dynamic parallel problem partitioning, and associated data migration. This key capability allows for efficient parallel performance of heterogeneous problems such as the mixed-mode circuit/device problems of the project. The parallel infrastructure required to perform these runs is in place, and we have completed initial runs in parallel.

We implemented many algorithmic enhancements for the solution phase, including the addition of improved time integration methods, nonlinear solution strategies, and line search algorithms. These improvements are essential to the eventual solution of the mixed-mode simulations and the associated stiffness of such problems.

We also implemented the initial device/circuit coupling (one level). In this mode of operation, the PDE-based Jacobian elements are used in the same fully coupled Jacobian matrices, as are the circuit-based elements.

Thus, we met stated tasks with the exception of the design and implementation of the two-level coupling. We switched the ordering of some tasks to provide better alignment with the XYCE (the implementation circuit code) development schedule, which resulted in our being ahead of

We implemented many algorithmic enhancements for the solution phase, including the addition of improved time integration methods, nonlinear solution strategies, and line search algorithms. These improvements are essential to the eventual solution of the mixed-mode simulations and the associated stiffness of such problems.

schedule with parallel implementation but behind on two-level coupling. However, our progress demonstrates the continuing feasibility of our approach and puts us on track to meet current milestones for an implicit finite-volume device simulator prototype running within a parallel-circuit simulation environment.

10778

A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems

D. R. Gardner, J. P. Castro, G. L. Hennigan, M. F. Young, M. A. Gonzales

Significant effort has been invested in developing high-fidelity models for parts of nuclear weapons (e.g., the neutron generator). However, comparatively little effort has been invested in developing computer modeling tools to examine interactions among weapon subsystems. Computer tools for modeling complex subsystem interactions in a nuclear weapon in varied environments and over a wide range of time scales (from nanoseconds to years) at multiple levels of fidelity can enable designers and safety analysts to perform their jobs faster, better, and cheaper.

The goal of this project is to develop methods to couple vastly different subsystems and physical models. Sandia will encapsulate these methods within a framework accessed by a JAVA-based interface. At the end of the project, users will be able to select modules from a library, modify them, and connect them into a system, using models of various fidelities. Each module will allow a range of thermal phenomena to be modeled within it, and users will be able to couple modules with differing spatial dimensionalities. In addition, users will be able to loosely couple electrical circuit and thermal models. For example, a user will be able to couple temperatures from a three-dimensional (3-D), finite-element model (FEM) of the arming, fuzing, and firing system (AF&F) to lumped parameter models for the remainder of the weapon and to model electrical circuit functions in the AF&F.

The technical challenges that Sandia is addressing in this project include how to couple models of different spatial dimensionalities. The methods developed will be broadly applicable to systems ranging from nuclear weapons to power plants. In particular, this work will provide an enhanced capability to model systems of nuclear weapons modules in normal and abnormal environments. We call the tool the “Entero system engineering code package.”

We implemented and assessed an algorithm for linking a lumped-parameter system model to a 3-D FEM of a component for thermal radiation. We compared three systems: a full lumped-parameter system model, a mixed-fidelity

The technical challenges that Sandia is addressing in this project include how to couple models of different spatial dimensionalities. The methods developed will be broadly applicable to systems ranging from nuclear weapons to power plants.

system model, and a full 3-D model. The mixed-fidelity model consisted of 0-D (lumped-parameter) models for all the system components except the AF&F system, which was represented by a 3-D FEM. Temperatures for the FEMs were computed by the COYOTE code.

In the mixed-fidelity system model, we coupled the FEM to the 0-D system model by an average temperature. We considered both the surface node-averaged temperature and the volume-averaged temperature of the FEM. Average temperatures predicted by the mixed-fidelity system model compared well with the average temperatures predicted by the 3-D model. Using the surface node-averaged temperature for coupling in the mixed-fidelity system model produced slightly better temperature predictions than using the volume-averaged temperature for coupling. In addition, the mixed-fidelity system model produced results in approximately one-quarter of the execution time of the 3-D model.

We coupled both the SPICE 3f5 and the ChileSPICE circuit simulation codes to the lumped-parameter, and the mixed-fidelity models through a construct denoted a thermal pin, which allows a circuit to be attached to a location in a component. We performed a coupled electrical/thermal simulation for the LM-185 circuit to demonstrate this capability.

We extended the mixed-fidelity algorithm to conduction heat transfer. The algorithm uses a simplified 1-D conduction model to connect components. We are testing and refining the algorithm.

We developed a method for mixed-fidelity system modeling and documented it in a Disclosure of Technical Advance. In this method, a simulation is controlled by a system model in which each physical component is represented by a software object that contains a 0-D model of the physical component. The software objects are connected by objects called *ports* that identify and manage the information exchange between objects. The 0-D model of a component may be augmented by an alternate, possibly higher-fidelity model by connecting it to the alternate model with a special port that transforms the 0-D state variables of the 0-D model to those used by the alternate model. As an example, consider a system of two components that are interacting via thermal radiation. The 0-D temperature of each component is an average temperature. Suppose that the temperature of one of the components is modeled with a 3-D FE model. The port connecting the FE model to the 0-D

In the mixed-fidelity system model, we coupled the FEM to the 0-D system model by an average temperature. We considered both the surface node-averaged temperature and the volume-averaged temperature of the FEM.

Average temperatures predicted by the mixed-fidelity system model compared well with the average temperatures predicted by the 3-D model.

model computes an average temperature from the former model for use by the latter model and provides the temperature from the 0-D model as boundary conditions for the FE model.

We enhanced the engineering interface to enable a user to specify a 3-D COYOTE heat-transfer model for the AF&F in place of the 0-D model. We also enhanced the interface to allow users to easily place an electrical circuit in the 3-D AF&F. We added a view-factor calculator for occluding conical frustums to the interface to enable users to calculate view factors for lower-fidelity system models.

We enhanced the engineering interface to enable a user to specify a 3-D COYOTE heat-transfer model for the AF&F in place of the 0-D model.

Other Communications

Demmie, P. N. 2001. "Optimal Design of Complex Systems Using the Entero Code System." *Advances in Computational Engineering & Sciences 2001, Proc. International Conference on Computational Engineering and Sciences (ICES '01)* 1 (Puerto Vallarta, Mexico, August).

Gardner, D. R., J. P. Castro, P. N. Demmie, M. A. Gonzales, G. L. Hennigan, M. F. Young, and S. S. Dosanjh. 2001. "Developing a Flexible System-Modeling Environment for Engineers." *Proc. 35th Hawaii International Conference on Systems Sciences*, accepted.

26512

Parallel Atomistic Computing for Failure Analysis of Micromachines

P. M. Gullett, S. J. Plimpton, M. G. Martin

To quantify microstructure-property relations related to weapon engineering designs of micromachines, Sandia will develop atomistic algorithms for parallel computers that compute continuum quantities. With these and other serial computing tools, we will perform atomistic simulations of various sizes, geometries, materials, and boundary conditions (BCs). Currently, no capability exists that can handle the different-size-scale effects required to predict failure. Nonlocal continuum models have been proposed to address this problem; however, they are phenomenological in nature and are difficult to validate for microscale components. Our goal is to separately quantify damage nucleation, growth, and coalescence mechanisms to provide a basis for macroscale continuum models that will be used for micromachine design. Because microcomponent experiments are difficult, a systematic computational study that employs Monte Carlo (MC) methods, molecular statics, and molecular dynamics (MD) simulations to compute continuum quantities will provide mechanism-property relations associated with the following parameters: specimen size, number of grains, crystal orientation, strain rate, temperature, defect nearest-neighbor distance, void/crack size, chemical state, and stress state. This will be the first foundational study to quantify size-scale effects from nanometers to microns in terms of damage progression and thus potentially allow for optimized micromachine designs that are more reliable and have higher fidelity in terms of strength.

We determined and evaluated continuum quantities including stress, strain (deformation gradient), and misorientation tensor. The definitions of these continuum quantities had not previously been defined. We are publishing this work.

(1) We determined and evaluated continuum quantities including stress, strain (deformation gradient), and misorientation tensor. The definitions of these continuum quantities had not previously been defined. We are publishing this work.

(2) We developed a preprocessor called *PREWARP* that defines realistic microstructures, geometries, and defects/pores with appropriate grain sizes, orientations, and more. Although methods exist to perform preprocessing of atom positions, our method is user-friendly and can be used in a general sense.

(3) We analyzed BCs/multiaxial-stress states to evaluate comparisons with finite-element (FE) methods. Previously, the relationship between BCs for atomistic representations versus those for FE analysis has been unclear. We quantified various types and can give definitive recommendations for matching FE simulations.

(4) We determined void growth determination. We employed an algebraic expression to determine the void growth from the atomic positions. We showed that results can fall within 1 percent of error estimates.

(5) We started modified embedded atom method (MEAM) parallelization. To obtain correct local stress and strain measures, MEAM must be used as opposed to embedded atom method (EAM) potentials. The MEAM potential allows for asymmetric stress that occurs around defects that admit anisotropy. We have started the parallelization of MEAM.

We employed an algebraic expression to determine the void growth from the atomic positions. We showed that results can fall within 1 percent of error estimates.

Other Communications

Gullett, P. M., M. F. Horstemeyer, M. I. Baskes, and D. J. Bammann. 2001. "Nanoscale Evaluation of Stress States in the Presence of Defects." Paper presented to the International Congress of Engineering Sciences, Puerto Vallarta, Mexico, August.

Horstemeyer M. F., P. M. Gullett, S. J. Plimpton, and M. I. Baskes. 2001. "Atomistic Simulations and Experiments of Large Deformation Processes." Paper presented to the 6th U.S. National Congress on Computational Mechanics, Detroit, MI, August.

Horstemeyer, M. F., P. M. Gullett, D. J. Bammann, and M. I. Baskes. 2001. "Atomistic Damage Modeling." Paper presented to the ASME Summer Meeting, San Diego, CA, June.

26513

Implementation of Fault Tolerance in Scientific Simulation Application Software

R. R. Drake, R. M. Summers

Sandia is working to study, implement, and test various fault-tolerance mechanisms controlled at the simulation-code level. That is, underlying software layers will detect errors and failures and communicate them to the application by using a convenient interface; the simulation code itself will act on the errors. Targeted faults include corrupt communication messages, processor-node dropouts, and an unacceptable slowdown of service from processing nodes. We are considering recovery techniques such as resending communication messages and the dynamic reallocation of failing processor nodes.

Sandia recognizes that scientific simulation software must be able to detect and recover from errors and failures of supporting hardware and software layers. Computing must evolve from the current large, specialized multimillion dollar Accelerated Strategic Computing Initiative (ASCI) platforms to smaller, less-expensive interconnected machines consisting of off-the-shelf hardware. As the Computational Plant (CPlant, a super computer system) has shown, fault tolerance can be necessary even on such a homogeneous system and may also prove useful in the next generation of ASCI platforms.

The goal is to determine a practical solution to such faults and the ability to retrofit existing simulation codes. We will consider (visible) communication layers and use the message-passing interface (MPI) to allow detection and adjustment of catastrophic failures such as a node dropout. The local-area multicomputer (LAM) implementation of MPI is an example, providing dynamic process spawning, some level of fault tolerance, and standard support for many platforms and operating systems. A robust fault-detection and delivery-signal-handling interface will complement the MPI implementation. The fault-detection and signal-handling interface will enable the application to recognize and act on platform errors.

We are studying the ability of a computer simulation to recover from the loss of a computer node. Two important aspects that we examined are (1) the ability of the MPI

Sandia recognizes that scientific simulation software must be able to detect and recover from errors and failures of supporting hardware and software layers. ... As the Computational Plant (CPlant, a super computer system) has shown, fault tolerance can be necessary even on such a homogeneous system and may also prove useful in the next generation of ASCI platforms.

implementation and lower layers to recover from a computer-node dropout, and (2) how the application will be notified of an error and synchronized to a reasonable location in the code. Both aspects are necessary if the simulation is to recover. The first requires software that is not under our control and is only currently being developed. The second is an interface issue that may have multiple solutions and may depend on the MPI and communication interface.

To solve the MPI issue, we made progress in two ways. First, we established a dialog with another Sandia research group consisting of CPlant operating-system (OS) developers. The dialog resulted in some fault-recovery considerations in their project. Second, we created a collaboration with the LAM/MPI developers at Indiana University. We enhanced the fault-tolerance coding in the LAM/MPI implementation and wrote a general-requirements document describing a fault-tolerance interface at the MPI/application-programming interface (API) level, which, if implemented in any given MPI, could be used to recover an application should a fault occur. This is significant because an application code, which is written to handle faults in one MPI implementation, will run successfully on any other MPI that implements the fault-tolerance interface.

At the application level, we encapsulated in a C++ object a mechanism to prepare for and catch errors and timeouts. The application code is protected from the details and can use the object to jump back to a location in the code to begin an error-recovery procedure or to try the troubled code again.

... we created a collaboration with the LAM/MPI developers at Indiana University. We enhanced the fault-tolerance coding in the LAM/MPI implementation and wrote a general-requirements document describing a fault-tolerance interface at the MPI/application-programming interface (API) level, which, if implemented in any given MPI, could be used to recover an application should a fault occur. This is significant because an application code, which is written to handle faults in one MPI implementation, will run successfully on any other MPI that implements the fault-tolerance interface.

26514

Smart Sensor Technology for Joint Test Assembly Flights

K. D. Marx, R. C. Armstrong, D. E. Rhodes, C. M. Pancerella, D. A. Sheaffer, Jr., N. M. Berry

Sandia is performing many expensive tests using sensor arrays. The world relies on sensors to perform a variety of tasks from the mundane to sophisticated. Currently, processors associated with these sensors are sufficient only to handle rudimentary logic tasks. Although multiple sensors are often present in such devices, insufficient processing power exists for situational understanding. Until recently, no processors that met the electrical power constraints for embedded systems were powerful enough to perform sophisticated computations.

Improving the efficacy, reliability, and information content resulting from these sensor arrays is of critical importance. With the advent of powerful commodity processors for embedded use, a new opportunity to improve efficacy arises.

Sandia intends to bring the software and expertise gained from our work in artificial intelligence (AI) and high-performance simulations to the general field of sensor technology and sensor arrays. As a result of the proposed work, sensor-array tests of practical importance to Sandia will increase the amount of usable information derived from those tests by an order of magnitude, while improving the believability of the data. Although this work is applicable to the emerging vision of ubiquitous computing generally, we propose to focus on a system of importance to Sandia: joint test assembly (JTA) for intercontinental ballistic missile (ICBM) warheads. The goal of this work is to, in effect, put the brain of the analyst on the test flight. High-fidelity simulations can be used to train advanced neural networks and incorporate them into sensors capable of recognizing real situations. Because the networks are trained by simulations, networks can learn to recognize situations that are too expensive or too dangerous to recreate experimentally.

(1) To assess project feasibility, we reviewed available and anticipated computer-processor and wireless-communication hardware.

Sandia intends to bring the software and expertise gained from our work in artificial intelligence (AI) and high-performance simulations to the general field of sensor technology and sensor arrays. As a result of the proposed work, sensor-array tests of practical importance to Sandia will increase the amount of usable information derived from those tests by an order of magnitude, while improving the believability of the data.

(2) We designed a simple electromechanical system to capture many of the features of hardware existing in JTA flights. The design includes the sensor implementation to provide data on the system performance and on the thermal environment in which the system operates.

(3) We developed a computer model of this system; the model implements the PSpice electrical simulation software.

(4) We built an oscillator circuit with a temperature sensor to emulate two of the signals anticipated from the electromechanical prototype.

(5) We set up a PC104 processor running the LINUX operating system as an initial central processing unit (CPU) test-bed. It was connected to a data-acquisition (DAQ) board to implement analog/digital (A/D) conversion of signal data.

(6) We wrote DAQ software. The software resides on the processor to do the A/D data sampling and to provide an interface with AI software by using the JAVA Native Interface.

(7) We connected the oscillator circuit and temperature sensor to the DAQ board and used it to exercise the data-conversion and data-conditioning capabilities of the processor and software.

(8) We developed and ran a model of the oscillator circuit to demonstrate the potential for supplying the AI modules with comparative information to be used in decision-making processes.

(9) We devised a flexible and decentralized agent-based architecture for the project. This will admit the AI and Artificial Life (Alife) applications envisioned, as noted above, to bring the brain of the analyst on board the JTA flights. We created prototypes to determine that the agents are capable of running in the JAVA environment with the embedded processors that are identified for the project.

This work spawned two new initiatives:

(1) *The Embedded Reasoning Institute.* This is a summer research project for advanced undergraduates and beginning graduate students; the project involves computer science, computer engineering, and electrical engineering.

(2) *The placement of a LINUX sensor on an instrumentation-development flight.* This will involve real-time DAQ concurrent with the numerical processing of images.

We devised a flexible and decentralized agent-based architecture for the project. This will admit the AI and Artificial Life (Alife) applications envisioned, as noted above, to bring the brain of the analyst on board the JTA flights. We created prototypes to determine that the agents are capable of running in the JAVA environment with the embedded processors that are identified for the project.

26515

Multilevel Methods for Nonlinear Structural Mechanics

C. R. Dohrmann, M. W. Heinstein

Robust and scalable parallel algorithms for solving nonlinear partial differential equations (PDEs) are essential for modeling and simulation to have a significant impact on weapons programs at Sandia. Computational models with millions of unknowns are becoming commonplace in the engineering sciences. A major challenge associated with these models is obtaining solutions in reasonable amounts of time. For example, the critical time step used in explicit transient dynamics decreases with mesh refinement and can increase runtimes significantly. Implicit dynamic formulations are not constrained by a critical time step, but do require the solution of large systems of nonlinear equations.

We will investigate a variety of multilevel methods to solve algebraic equations arising from finite-element (FE) discretizations of nonlinear PDEs. The application focus is for nonlinear structural mechanics codes with emphasis on implicit dynamics and quasi-statics. The existing multilevel framework within the quasi-statics code JAS will serve as a starting point for our efforts, but all development will acknowledge the importance of inclusion in SIERRA.

Two candidate multilevel methods are entirely new and based on uniform strain and eigenmode characteristics of subdomains. Both methods require only a single FE mesh and would replace the coarse mesh currently required in JAS. In addition, collaborations between staff in the engineering and computational sciences would enable further development and evaluation of existing approaches such as smoothed aggregation.

(1) We reviewed literature on two-level and multilevel algorithms for structural mechanics. We decided to focus on a new two-level interface preconditioner for substructuring. This effort will be extended to multiple levels. Also, we developed a theoretical basis for this preconditioner and began programming for implementation in an FE code.

(2) We developed an effective partition of unity for domain decomposition methods. The partition is based on solutions of problems local to each subdomain of an FE mesh decomposition. We developed a coarse subspace and interface

We decided to focus on a new two-level interface preconditioner for substructuring. This effort will be extended to multiple levels.

Also, we developed a theoretical basis for this preconditioner and began programming for implementation in an FE code.

preconditioner from this partition. The new coarse subspace will replace the exiting coarse grid (constraint mesh) in JAS.

(3) We explored different alternatives for coarse-grid subspaces. These included zero-energy modes, energy-minimizing uniform-strain modes, and modes based on low-order polynomial functions of nodal coordinates. The partition of unity that we developed enables us to use these subspaces to construct a coarse-grid problem.

(4) We devised new preconditioners for mixed FE formulations. Both overlapping Schwarz and interface preconditioners were conceived. The preconditioners are applicable to nearly incompressible materials (e.g., metal plasticity) and will provide an alternative to the current method of accommodating such materials.

(5) We developed methods for treating essential boundary conditions (BCs) and contact in a multilevel framework. These methods remove multilevel constraints from nodes with existing kinematic or contact BCs.

We developed methods for treating essential boundary conditions (BCs) and contact in a multilevel framework.

These methods remove multilevel constraints from nodes with existing kinematic or contact BCs.

26516

Algorithmic Support for Commodity-Based Parallel Computing Systems

V. J. Leung, C. A. Phillips, D. P. Bunde, N. W. Dauchy, L. A. Fisk, J. R. Johnston, R. E. Riesen, R. L. Rubin

Sandia is developing efficient algorithms for managing resources in parallel computers. This work focuses on scheduling for processor allocation. Effective scheduling on commodity-based supercomputers, such as Computational Plant (CPlant), must account for central processing unit (CPU) heterogeneity, bandwidth limitations, irregular interconnection topology, and reduced hardware reliability. These factors have not had significant impact on Sandia's Accelerated Strategic Computing Initiative (ASCI) Red machine.

Existing schedulers make strong assumptions about the uniformity of network connectivity and resource availability (e.g., node memory). Consequently, these tools will not perform as well on more heterogeneous computing platforms.

This work will have direct impact on CPlant utility by improving batch and interactive schedulers. Additionally, our work will characterize jobs that are run on CPlant and Janus (e.g., communication load/pattern of network congestion) to enable smart decisions for scheduling.

We will evaluate the performance characteristics of jobs running on CPlant and evaluate the throughput of the CPlant scheduler. Given this analysis, we will develop new schedulers for CPlant to improve the throughput of this machine. In particular, we will develop schedulers that exploit users' guidance to tailor the schedule to problem characteristics.

We began by experimenting with job placement on Siberia, the CPlant machine for which the most documentation is available. The results should apply generally to Antarctica. To gather experimental data, we developed the CPlant kernel data-gathering facility and augmented schedule and yod log-file output.

We found that contiguous-node allocation with low-aspect ratio resulted in the best performance for communication-intensive jobs. Given this result, the routes and job sizes on CPlant become critical to node assignment. Shortest-path routes should give the best communication

This work will have direct impact on CPlant utility by improving batch and interactive schedulers. Additionally, our work will characterize jobs that are run on CPlant and Janus (e.g., communication load/pattern of network congestion) to enable smart decisions for scheduling.

performance when CPlant nodes are allocated contiguously. In particular, they minimize inter-job-message contention because most messages for a job are routed completely within the piece of the machine allocated to that job. However, shortest-path routes are only guaranteed on Siberia between processors that are at most three switch hops apart. Thus, only jobs using up to 48 contiguous nodes are guaranteed shortest-path routes. After a thorough analysis of routing on CPlant, we developed general shortest-path routes for Siberia. Since Siberia was decommissioned, these shortest-path routes were generalized to Antarctica.

The new routes will (1) immediately improve Antarctica's performance, even with the current noncontiguous allocation scheme, and (2) make message-routing behavior more intuitive and predictable. The job-placement problem becomes easier to approximate, both theoretically (for an automated scheduler) and in practice, when users are allowed to choose processor allocation by hand. We then implemented several one-dimensional packing heuristics for CPlant, including First Fit, Best Fit, and Sum of Squares. These implementations have been tested by simulation and on Iceberg and Alaska during system time. When completely tested, these heuristics can be combined with space-filling curves to approximate multidimensional packing. It is not clear otherwise how some of these heuristics can be generalized to multiple dimensions. We also implemented backfill in the scheduler.

On the theoretical side, we have shown several lower bounds on the best that any algorithm can achieve under certain circumstances.

After a thorough analysis of routing on CPlant, we developed general shortest-path routes for Siberia. Since Siberia was decommissioned, these shortest-path routes were generalized to Antarctica. The new routes will (1) immediately improve Antarctica's performance, even with the current noncontiguous allocation scheme, and (2) make message-routing behavior more intuitive and predictable.

26517

Parallel Repartitioning for Optimal Solver Performance

K. D. Devine, M. A. Heroux, B. A. Hendrickson, E. G. Boman, R. Heaphy, R. J. Hoekstra

Sandia is making strides in parallel repartitioning to improve solver performance. The partitioning of data and work for distributed-memory solver packages is typically established by the application that calls the solver. Often the best data distribution for the application is not best for the solver.

Overlapping Schwarz preconditioners are frequently required to keep iteration counts down as more processors are added. However, the overlapping Schwarz preconditioners may have very unbalanced workloads, even if the data distribution is balanced for other phases of the solver computation.

By combining the parallel data-redistribution tools in ZOLTAN with the state-of-the-art preconditioning and linear-solver technology in TRILINOS, we are beginning to address the problems surrounding partitioning and data and workload distribution. (ZOLTAN is a general-purpose library for parallel partitioning and dynamic load balancing in parallel applications. TRILINOS is a library of state-of-the-art, robust, scalable solvers with an object-oriented application-programmer interface [API].)

We propose the following:

- (1) Incorporate ZOLTAN into the TRILINOS framework.*
- (2) Develop meaningful cost functions that give good parallel-data redistribution for solvers.*
- (3) Using the graph of the sparse matrix, develop the algorithmic theory and implementation that allow us to determine the data distribution. When the graph is extended for overlapping Schwarz, the data and work distribution should still be balanced.*

We completed and tested an initial implementation of ZOLTAN in TRILINOS. Step 3 is, to our knowledge, a new research area. To address Step 3, we developed a general strategy based on iterative improvement. We tested this strategy, which proved promising in a serial implementation.

Sandia is making strides in parallel repartitioning to improve solver performance. The partitioning of data and work for distributed-memory solver packages is typically established by the application that calls the solver. Often the best data distribution for the application is not best for the solver.

- *Coupling TRILINOS and ZOLTAN.* A key component of this work is to incorporate the ZOLTAN dynamic load-balancing library into the TRILINOS solver project. We made significant progress incorporating ZOLTAN into TRILINOS. Within TRILINOS, import and export classes have been implemented; these classes are used for communication and for data movement to establish new decompositions. We implemented ZOLTAN call-back functions into TRILINOS to return the graph of a matrix. Having these tools in place enables us to use ZOLTAN to compute new decompositions in TRILINOS and move matrix data to new processors.

Several improvements were made in ZOLTAN to improve the performance of data movement in TRILINOS. Within the ZOLTAN communication package and data-migration tools, we added the capability to move objects of variable sizes. In addition, we made improvements to the ZOLTAN design to modularize common functionality and to enable greater code reuse.

The combined TRILINOS and ZOLTAN package was tested in Sandia's XYCE Parallel Electronic Simulator. (XYCE is a massively parallel [MP] analog-circuit simulator that Accelerated Strategic Computing Initiative [ASCI] designers use for arming, fuzing, and firing [AF&F] simulations.) XYCE has two phases requiring very different partitions: a load phase and a linear-solve phase. In the load phase, devices must be distributed among processors so total processor-load times are equal and network connections between processors are minimized. ZOLTAN directly computes partitions with respect to load times, which can vary by up to two-orders-of-magnitude variation among devices. The linear-solve phase requires a partition with respect to the graph of the matrix. In this partition, all nodes and edges of the matrix graph are weighted equally. For a fixed-size problem involving a simple network, the ZOLTAN-TRILINOS coupling allows XYCE solutions with up to 80 percent efficiency on 32 processors.

- *Partitioning for overlapping preconditioners.*

Overlapping Schwarz preconditioners may have very unbalanced workloads, even if the data distribution is balanced for other phases of the solver computation. In typical data decompositions, only the work and communication within a processor subdomain is considered in computing new partitions. However, for overlapping preconditioners, the work and communication required for the overlap regions can be significant and must also be accounted for in computing new

Several improvements were made in ZOLTAN to improve the performance of data movement in TRILINOS.

Within the ZOLTAN communication package and data-migration tools, we added the capability to move objects of variable sizes. In addition, we made improvements to the ZOLTAN design to modularize common functionality and to enable greater code reuse.

partitions. Moreover, the amount of work in the overlap region is a function of the subdomains in the decomposition. This interdependence between the overlap workloads and the decomposition drives requires an iterative approach to repartitioning for overlapping preconditioners.

We developed a general partitioning approach for overlapping preconditioners. An initial partition is generated using a standard partitioning tool. A cost function that reflects both subdomain and overlap-region costs is then computed. Using a diffusion-type algorithm, work shifts from heavily loaded (with respect to this new cost function) processors to less-loaded neighboring processors; the costs are updated to reflect new processor assignments. We evaluate the new partition and repeat the diffusion stage until workloads reach an acceptable balance.

We tested this strategy using the serial partitioning algorithms in CHACO (a graph partitioning package) for the initial partition, along with a serial diffusion algorithm for the iterative improvement. A variety of matrices coming from partial differential equation (PDE)–based applications were used to test the method. We applied the iterative-improvement balancing scheme to each matrix with one level of overlap.

For nearly all problems, the maximum processor load is significantly reduced; load reduction should result in improved performance. Given these results, we feel this method should be further pursued with a parallel implementation in ZOLTAN and testing in TRILINOS.

We tested this strategy using the serial partitioning algorithms in CHACO (a graph partitioning package) for the initial partition, along with a serial diffusion algorithm for the iterative improvement.

Refereed

Devine, K., E. Boman, B. Hendrickson, W. Mitchell, and C. Vaughan. 2001. "Applications of Dynamic Load Balancing." *U.S. National Congress on Computational Mechanics* (Detroit, MI, August): 419.

Heroux, M., and K. Kampshoff. 2001. "Observations on the Use of Heterogeneous Clusters for Scientific Computations." *Proc. 10th SIAM Conference on Parallel Processing for Scientific Computing* **10** (Portsmouth, VA, March).

Kampshoff, K. 2001. "Observations on the Use of Heterogeneous Clusters for Scientific Computations." Senior Thesis, Department of Computer Science, St. John's University, Minnesota (May).

Other Communications

Devine, K. 2001. "The Zoltan Dynamic Load-Balancing Library." Invited talk to Sandia's Combustion Research Facility, Livermore, CA, April.

Devine, K., E. Boman, B. Hendrickson, C. Vaughan, and W. Mitchell. 2001. "Data Management for Scientific Computations." Paper presented to the Workshop on Object-Oriented and Component Technology for Scientific Computing, Livermore, CA, July.

33319

Numerical Methods Applied to High-Energy Physics

J. S. Wagner, P. C. Gray

The concept of mass is a bedrock of our understanding of the physical world. Along with the concept of mass, the interpretation of space has posed lasting challenges to the human intellect. The two prevailing theoretical paradigms that independently explicate mass and space, the Standard Model of Particle Physics and the Big Bang Cosmology, are demonstratively contradicted by respective experimental findings concerning the anomalous g -value of the muon and precision measurements of the cosmic microwave background (CMB).

Significantly, both theoretical pictures are also deeply troubled by the appearance of unphysical divergent quantities. Two further enduring theoretical riddles are likewise mysterious, the surprising effectiveness of mathematical descriptions of physical phenomena, discussed by Wigner, and the significance of large numbers, considered initially by Dirac.

This letter introduces a cryptographic synthesis that (1) creates a unified archetype by fusing the concepts of mass and space through the definition of a new physical entity, the "inverse state," (2) yields an interlocking concordance of quantitative results involving (a) the ν_e , ν_μ , and ν_τ masses, (b) the Higgs mass through the formulation of a seesaw relation, (c) the value of the gravitational constant G , (d) the magnitudes of the fine-structure constant α , and the unified strong-electroweak coupling constant α^ , and (e) the group structure of particle states, and (3) provides responses to the philosophical questions voiced by Wigner and Dirac.*

The principal conclusions are (1) the barrier to theoretical progress has been the arbitrary disjunction of the concepts of mass and space, and (2) there exists a universal optimized organizing principle relating the cosmic and microscales possessing a precision of one part in $\sim 10^{121}$.

Sandia conjectures that the corresponding regulatory architecture plays a fundamental role in a broad range of complex phenomena including the biological realm. The exceptional level of theoretical exactitude expresses an epistemological limit of a new form.

Sandia conjectures that the corresponding regulatory architecture plays a fundamental role in a broad range of complex phenomena including the biological realm.

The exceptional level of theoretical exactitude expresses an epistemological limit of a new form.

We conducted fundamental research in the nature of matter and in cosmological principles. Arithmetic conditions relating particle masses can be defined on the basis of (1) the supersymmetric conservation of congruence and (2) the observed characteristics of particle reactions and stabilities. Stated in the form of common divisors of the particle-mass parameters, these relations can be interpreted as expressions of genetic elements that represent particle characteristics.

To illustrate this concept, it has been shown that the pion triplet ($\pi^\pm, \pi^0$) can be associated with the existence of a greatest common divisor $d_{o\pm}$ in a way that can account for both the highly similar physical properties of these particles and the observed $\pi^\pm/\pi^0$ mass splitting. Classification of the respective physical states is achieved by association of the common divisors (genes) with corresponding residue class designations in a finite field $\mathbb{F}$ (typ.). Further, the existence of the finite field $\mathbb{A}$ and the corresponding group of units $\mathbb{F}^*$ (typ.) leads immediately to the definition of a new physical entity, the inverse state, a concept that allows supersymmetry to be directly expressed in terms of hierarchical relationships between odd and even order subgroups of $\mathbb{A}^*$. The invention of the inverse state further enables (1) the formulation of the cosmic seesaw congruence, the statement that fuses the concepts of mass and space, (2) the creation of a new definition of particle elementarity, and (3) the computation of the Higgs mass.

The structure established by the use of these mathematical procedures transforms the theoretical organization of the particle-mass scale into a cryptographic analysis. It has been shown that the law of quadratic reciprocity arranges the group structure of physical particle states by powerfully constraining the subgroup relationships in $\mathbb{A}^*$. A profound consequence of the subgroup ordering is the doubling of the genetic function of the divisors and their classification with the residue classes of $\mathbb{A}$. On the basis of the pattern found, the genetic divisor interpretation can be applied to both (1) the designation of subgroup orders and (2) the specification of the masses and intrinsic attributes of individual particle systems. It was generally concluded that the constraint on the group relationships expressed jointly by quadratic reciprocity and the seesaw congruence creates a universal optimized structure that plays a fundamental regulatory role in a large array of complex phenomena.

The invention of the inverse state further enables (1) the formulation of the cosmic seesaw congruence, the statement that fuses the concepts of mass and space, (2) the creation of a new definition of particle elementarity, and (3) the computation of the Higgs mass.

Refereed

Yang, D., A. B. Borisov, J. W. Longworth, K. Boyer, and C. K. Rhodes. 2002. "Cryptographic Unification of Mass and Space Links Neutrino Flavour (ne/nm) Transformations with the Cosmological Constant L ." *Nature*.

Other Communications

Yang, D., A. B. Borisov, K. Boyer, and C. K. Rhodes. 2001. "Determination of Supersymmetric Particle Masses and Attributes with Genetic Divisors." Sandia Technical Report SAND2001-1608, Sandia National Laboratories, Albuquerque, NM.

39420

Self-Organizing Network Intelligent Algorithm (SONIA)

J. S. Wagner, D. L. Harris, N. G. Brannon, G. M. Pollock

This project will explore the possibility that distributed, perhaps biomimetic, intelligence could emerge either inadvertently or deliberately on very large scale computational networks. This project will also attempt to analyze such systems in terms of potential performance bounds, detectable signature characteristics, and possible mitigation strategies. Currently, there are about 10^8 computers on the Internet with a total processing capability of more than 10^{16} operations per second, which is arguably comparable to about 500 human consciousnesses if the Internet were highly connected. If a self-executing algorithm evolved or were created for whatever reason, then this vast number of computers could be a fertile breeding ground for genetic algorithms. Specific questions to be investigated include: Is it possible to develop either accidentally or by design some sort of distributed intelligence from a system with these capabilities? Would such a distributed intelligence be a threat, a nuisance, or a benefit?

We reached agreement on the initial questions outlined in the project proposal as well as some follow-on questions. We also identified key issues and questions that need to be addressed for monitoring and assessing distributed systems aspects related to this research. Further, we completed an extensive bibliography, notes, and an outline for a report detailing important aspects of this research.

For this investigation we focused our research activities on three major aspects: (1) the correspondence between a characterization of levels of human intelligence and potential levels of intelligent cyber agents to allow categorization and assessment of intelligent cyber agents, (2) an understanding of human consciousness and how this could be related to cyber agents and the potential for their evolution or emergence as conscious entities, and (3) an investigation of computer technologies that could directly support or inhibit the evolution or emergence of biomimetic intelligence. These areas are directly related to the set of specific questions that we attempted to answer.

Currently, there are about 10^8 computers on the Internet with a total processing capability of more than 10^{16} operations per second, which is arguably comparable to about 500 human consciousnesses if the Internet were highly connected. If a self-executing algorithm evolved or were created for whatever reason, then this vast number of computers could be a fertile breeding ground for genetic algorithms. Specific questions to be investigated include: Is it possible to develop either accidentally or by design some sort of distributed intelligence from a system with these capabilities? Would such a distributed intelligence be a threat, a nuisance, or a benefit?

It is possible to develop either accidentally or by design some sort of distributed intelligence; elementary distributed denial-of-service attacks are a prelude to more sophisticated distributed intelligence. Distributed intelligence could provide both significant beneficial and detrimental effects, depending on the agent circumstances and characteristics. It is currently not possible to prove whether any entities with biomimetic intelligence exist today; however, this indeterminacy primarily was dependent on the definition and level of intelligence. Given lower intelligence thresholds and the absence of any agent self-consciousness, we agreed that lesser agents do currently exist. It would not be possible to prove that a conscious biomimetic intelligence entity is impossible. Distinctions exist between accidental and deliberate scenarios; one example is the greater amount of time and computing resources that an agent would require to accidentally evolve versus one deliberately designed to a given level of intelligence. Consequently, we agreed that accidental evolution of conscious biomimetic intelligences is highly unlikely in the near term, but potentially plausible emulations of conscious agents with deliberate design could occur at any time.

From this research there was a clear conclusion that continued research into measurements of agent intelligence and agent consciousness is required to more adequately categorize cyber agents into the legal framework. The detection of agent behavior that potentially could emerge into an advanced intelligence is also required.

From this research there was a clear conclusion that continued research into measurements of agent intelligence and agent consciousness is required to more adequately categorize cyber agents into the legal framework. The detection of agent behavior that potentially could emerge into an advanced intelligence is also required.

Electronics and Photonics

The Electronics and Photonics investment area explores innovative solutions to national problems that build on Sandia's existing strengths. Advances in the realization of small, low-power, highly integrated electronics packages (i.e., integrated microsystems) support the mission needs of Sandia. Research focus areas have included microdevice concepts that enable advances in microelectronics, photonics, microelectromechanical systems (MEMS), and sensors. Other important research includes biological interfaces, mechanical actuation, photonics concepts, chemical sensing, and optical recognition; new approaches to integration, packaging, and micropower systems are being investigated.

The goals of the "Silicon Three-Dimensional Photonic Crystal and Its Applications" project are to advance Sandia's recent technology breakthrough in creating silicon photonic crystals and to demonstrate these engineered materials' unique potential for various national security applications. Potential military applications include infrared image control (thermal stealth), target identification, and signature recognition. Potential commercial applications targeted at the wavelength used for optical communications will lead to a totally new generation of devices that are

integratable with current microelectronics, MEMS, and sensors. This will enable full microsystems on a chip. Examples of discrete silicon photonic devices are high-performance low-cost lasers, light-emitting diodes, mirrors, waveguides, and optical filters. This work received an R&D 100 Award and has one patent application pending.

10328

Silicon Three-Dimensional Photonic Crystal and Its Applications

S. Y. Lin, S. K. Lyo, J. G. Fleming

The goal of this project is to advance Sandia's recent technological breakthrough in creating high-temperature metallic silicon (Si) three-dimensional (3-D) photonic crystals (PhC). We are examining the new 3-D crystal structures and will demonstrate their unique applications in military and commercial photonics. Military applications in the infrared (IR) include using bandpass filters for thermal image control, target identification, and signature recognition. Commercial applications targeted at the wavelengths used for optical communications at 1 μm to 2 μm wavelengths will lead to a totally new generation of Si photonic devices that can be integrated with current Si microelectronics. Examples are high-performance mirrors, waveguides, and optical filters. With a typical device size of 5 μm to 10 μm , the PhC device is truly miniature in size and will pave the way for integrated optical circuits. Sandia researchers will also investigate the crystals for future energy applications.

(1) Physics of an all-metallic 3-D PhC. We built a 3-D PhC with tungsten (W) metal for the first time and showed it to operate in the IR wavelength of 4 μm to 25 μm . The photonic structure has an absolute 3-D photonic bandgap (PBG) and can sustain high-temperature (high-T) operation at T greater than 1000°C. This new metallic structure has many superior optical properties, including an extraordinarily large PBG (8 μm to greater than 25 μm) and the strongest attenuation constant (30 dB per unit cell) ever reported in any PH. The large bandgap means that as few as four layers are sufficient for optical waveguiding and light confinement. This accomplishment opens up a new dimension in PBG engineering and in lightguiding and bending and will pave the way for a broad-bandwidth optical interconnect.

(2) First realization of absolute PBG using a simple cubic PhC at IR wavelength. Conventionally, it is believed that a simple cubic structure does not possess a complete PBG, due to its inherent dispersion anisotropy. Yet this structure may be the most ideal for constructing a 3-D optical interconnect since it exhibits x-y-z rotational symmetry.

The goal of this project is to advance Sandia's recent technological breakthrough in creating high-temperature metallic silicon (Si) three-dimensional (3-D) photonic crystals (PhC). We are examining the new 3-D crystal structures and will demonstrate their unique applications in military and commercial photonics. ... We built a 3-D PhC with tungsten (W) metal for the first time and showed it to operate in the IR wavelength of 4 μm to 25 μm This accomplishment opens up a new dimension in PBG engineering and in lightguiding and bending and will pave the way for a broad-bandwidth optical interconnect.

Through extensive computational design and fabrication, we show that it is possible to have a complete bandgap in a 3-D simple cubic PhC.

(3) Three-dimensional control of light using a quasi-3-D photonic slab structure. A conventional 2-D PhC confines light only in the 2-D plane and, thus, is less useful than a 3-D PhC, although a 2-D structure is easier to fabricate and in some cases is sufficient for integrated photonic applications. We recently realized a quasi-3-D structure, which confines light in the 2-D plane by PBG effect and in the third direction by a strong index guiding. This accomplishment may find important application in ultrafast optical switching.

(4) Direct absorptance measurement and observation of an order-of-magnitude absorption enhancement. A new absorptance measurement system has been set up and is fully operational. A recent absorptance measurement on a 3-D metallic PhC reveals an interesting and potentially important phenomenon: Despite the strong metallic reflection, a structured metallic PhC exhibits strong anisotropy at the photonic band-edge. This strong absorption may be utilized to enhance photonic voltaic conversion efficiency and even incandescent lamp efficiency. A fundamental discovery like this can quickly create a disruptive technological impact on energy and communication applications.

This strong absorption may be utilized to enhance photonic voltaic conversion efficiency and even incandescent lamp efficiency. A fundamental discovery like this can quickly create a disruptive technological impact on energy and communication applications.

Refereed

Lin, S. Y. 2000. "Three-Dimensional Control of Light in a Two-Dimensional Photonic Crystal Slab." *Nature* **407**: 983-986.

Lin, S. Y. and E. Chow. 2001. "Quantitative Analysis of Ending Efficiency in Photonic Crystal Waveguide Bends at 1.55-Millimeter Wavelengths." *Optics Letters* **26**: 286-288.

Lin, S. Y., and J. G. Fleming. 2001. "A Complete Three-Dimensional Photonic Bandgap in a Simple Cubic Structure." *J. Opt. Soc. Amer. B* **18**: 32.

Lin, S. Y., J. G. Fleming, and E. Chow. 2001. "Two-Dimensional and Three-Dimensional Photonic Crystals Built with VLSI Tools." *MRS Bulletin* **26** (August): 627.

10329

Monolithic Micromachined Variable Tuners for Rapid Prototyping and Optimization of Microwave Circuits

C. W. Dyck, C. P. Tigges, S. Hietala, L. R. Sloan, T. R. Christenson, T. A. Plut

Microwave tuners measure and optimize the performance of microwave devices by varying the impedance presented to the device. Once the optimal impedance for a performance parameter (e.g., noise, power, efficiency, and gain) is known, a circuit is synthesized to present the proper impedance to the device and to translate that impedance to the system environment (usually 50 ohms). Present tuners are greater than 20 cubic inches with coaxial connectors as an interface. Loss incurred in the interface between the tuner and the device diminishes the impedance range of the tuner.

Sandia is developing miniature integratable precision-machined (MIPM) tuners that can be assembled in a hybrid fashion or monolithically integrated with microwave active devices. This development would minimize interface losses, increase the tuning range, reduce design cycle times and cost, reduce size and weight of microwave circuitry, allow for frequency agility in circuit design, and improve microwave circuit performance.

A key element in the realization of an MIPM tuner is a small, low-loss switch. We demonstrated functional micromechanical switches on gallium arsenide (GaAs) substrates. Open-state was less than 0.3 dB, and return loss was greater than 25 dB (0.1 to 20.1 GHz). Off-state isolation was greater than 25 dB.

We continued to focus on improving the MIPM switch. This effort resulted in two new process approaches and the start of contact metallurgy studies. For the first process, we used gold (Au) as the mechanical material and photosensitive benzocyclobutene (BCB) as the electrically insulating material. Based on process issues, we adopted a second approach using nickel (Ni) as the mechanical material and SiON as the electrically insulating material. The latter approach is still in development and shows promise in accomplishing our goals of increased manufacturability, yield, and performance, based on results from a number of process iterations.

We continued to focus on improving the MIPM switch. This effort resulted in two new process approaches and the start of contact metallurgy studies. For the first process, we used gold (Au) as the mechanical material and photosensitive benzocyclobutene (BCB) as the electrically insulating material. Based on process issues, we adopted a second approach using nickel (Ni) as the mechanical material and SiON as the electrically insulating material. The latter approach is still in development and shows promise in accomplishing our goals of increased manufacturability, yield, and performance, based on results from a number of process iterations.

We changed the initial process and initiated contact studies to improve the radio-frequency (RF) switch fabrication yield and device functionality. Early results showed limited switch lifetime caused by metal fatigue and by the devices sticking after a few actuation cycles. The previous process also used an organic film as the anchor layer. Organic layers were found to be inappropriate for this application, as they absorb moisture and are too compliant. The switch process was first changed to a gold (Au)-BCB process, then to a Ni-SiON process to address the metal fatigue and organic anchor layer issues. We initiated contact studies to decrease sticking and improve the switch lifetime.

The first process consisted of Au coplanar microstrips as the base metal layer deposited on top of GaAs substrates. We used polymethylglutarimide (PMGI) as the sacrificial layer. Au was electroplated above the sacrificial layer to act as the mechanical spring and the electrical contact. We deposited photosensitive BCB and patterned it to insulate the electrical contact from the mechanical spring. The structures were released with O₂ plasma. This process eliminated the need for organic anchors and did not have any thin trenches where metal thinning and fatigue could occur. O₂ plasma release was used instead of a wet release because it deposited less residual contaminants and required fewer steps.

We encountered two process issues. First, the electroplated Au films had large stress gradients. This caused the singly clamped RF switches to curl out of plane, making them unusable. The residual stress gradient was also difficult to predict because it varied from run to run. The result is that we purchased a dedicated Au electroplating bath and are installing it to run controlled studies of the film. Second, the BCB films had large residual compressive stress (greater than 30 MPa). The BCB films were tensile as deposited; however, they rapidly absorbed N-methyl-pyrrolidone (NMP) during the PMGI wet release. The resulting compressive stress buckled the doubly clamped RF switches. Acetone was tried as an alternative release chemistry, but it attacked the BCB layer.

We modified this process by replacing the electroplated Au layer with electroplated Ni, and by replacing the photosensitive BCB with low-stress SiON. The base metal coplanar microstrip layer and the sacrificial PMGI layers were unchanged. The O₂ plasma release process was also still used. We used electroplated Ni because it has low residual stress gradients. This process has been well characterized at Sandia.

This process eliminated the need for organic anchors and did not have any thin trenches where metal thinning and fatigue could occur. O₂ plasma release was used instead of a wet release because it deposited less residual contaminants and required fewer steps.

Ni is also a better mechanical material than Au because it is stiffer and more resistant to fatigue. Its disadvantages are higher resistivity and relative permeability. Our plan is to use the Ni as a mechanical material (for the springs), and substitute Au back into the process as the contact material once the residual strain gradients are well controlled. For now, Ni will be used for both the mechanical and electrical portions to continue the switch development.

Current issues include residual tensile stress in the Ni film. Residual tensile stress is better than compressive stress; however, when this is imposed on our current switch topography, the result is that the switch will pull down to the substrate after release. Increasing the sacrificial layer thickness has largely mitigated this effect. Design changes will also improve the device performance. A second issue is the stress mismatch between the SiON layer and the Ni film. Although both films have low residual stress, the mismatch between the two is enough to cause curling on structures that have large overlap areas. We will fix this problem by making minor design improvements. A third issue is the nonuniformity of SiON. It deposits unequally over different materials. We are now investigating this nonuniformity.

We have begun contact metallurgy studies and have ordered test structure masks and test equipment to test a variety of sputtered contact metals. We will measure contact resistance for the different metals as a function of applied force and the number of actuation cycles.

We have begun contact metallurgy studies and have ordered test structure masks and test equipment to test a variety of sputtered contact metals. We will measure contact resistance for the different metals as a function of applied force and the number of actuation cycles.

10330

Quantum Tunneling Transistors for Practical Application

J. A. Simmons, J. L. Reno, S. K. Lyo, J. R. Wendt, W. E. Baca, M. P. Lilly

Sandia recently demonstrated the Double Electron Layer Tunneling Transistor (DELTT), a three-terminal quantum transistor with excellent electrical isolation between input and output. This is the first three-terminal quantum device that does not depend on lateral size confinement, but rather is planar, allowing reliable fabrication. In the past year, we demonstrated DELTTs with excellent behavior at 77 K and verified models predicting the maximum operating temperature. In addition, we demonstrated circuits (bistable memories and digital logic gates) using the multifunctionality of the DELTT at 77 K.

Because the DELTT is quantum, it should be capable of extremely high speeds. In conjunction with its multifunctionality, this would make it particularly suited for such high-end applications as ultrahigh-speed analog-to-digital (A/D) converters for use in radar imaging and high-speed transistors for communications. Before the DELTT can fully live up to its exceptional promise, however, a number of engineering obstacles must be overcome. The most important of these are (1) modification of the growth structure to achieve room-temperature operation, and (2) engineering of the device geometry to reduce parasitics and thus achieve high speed.

In this project, we will engineer further improvements in the DELTT to achieve room-temperature operation, increase the operating speed, and assess the ultimate speed limitations. We will pursue two different major thrusts. These are (1) the use of different material systems with larger conduction band offsets than aluminum gallium arsenide/gallium arsenide (AlGaAs/GaAs) to achieve deeper quantum wells (QWs) and larger tunneling barriers for higher temperatures, and (2) the design of DELTTs with very short low-capacitance gates, low-resistance channels, and various other optimized features designed to reduce parasitics and enable high speed.

Our investigations of the three-layer DELTT structure continued. We verified that our conceptual model of its principle of operation is valid. We grew, fabricated, and

... we demonstrated DELTTs with excellent behavior at 77 K and verified models predicting the maximum operating temperature. ... we demonstrated circuits (bistable memories and digital logic gates) using the multifunctionality of the DELTT at 77 K.

measured numerous three-layer DELTT structures having different thicknesses of the first (emitter) tunneling barrier. We showed that the peak tunneling current decreased exponentially with the thickness of the emitter tunnel barrier, and also that the peak tunneling current varied linearly with the density in the emitter layer. Our model predicts that it should be possible to achieve three-layer DELTTs with current densities as high as 10^4 A/cm^2 .

We grew these DELTTs from the AlGaAs-GaAs material system. We generally measured them at a temperature of 77 K. We showed them to exhibit gate-controlled negative differential resistance up to a temperature of 273 K, or roughly 0°C . We also grew DELTTs from the indium aluminum arsenide (InAlAs)-indium gallium arsenide (InGaAs) material system, which we expected would exhibit operation at room temperature. However, difficulties with fabrication prevented us from completing measurements on these devices.

We also showed that the source-drain voltage at which the resonant tunneling current peak occurs can be predicted by a simple lever-arm model. A self-consistent solution of Schrodinger's and Poisson's equations for the DELTT structure yields the positions of the energy subbands for the various layers in the structure. The validity of the calculation was verified by photoluminescence measurements. The resonant peak occurs when the emitter and resonant layer subbands align. The observed peak voltage values were within 10 percent of the calculated values and showed that the model is correct.

Our model predicts that it should be possible to achieve three-layer DELTTs with current densities as high as 10^4 A/cm^2 .

10331

Development of Magnetically Excited Flexural Plate-Wave Devices for Implementation as Physical, Chemical, and Acoustic Sensors, and as Integrated Micropumps for Sensored Systems

W. K. Schubert, D. R. Adkins, J. L. Dohner, R. J. Shul, M. A. Mitchell, W. C. Ginn, M. A. Butler, L. F. Anderson, D. C. Graf, J. P. Lucero

The magnetically excited flexural plate-wave (mag-FPW) device has great promise as a versatile sensor platform. FPWs can have better sensitivity at lower operating frequencies than the more common surface acoustic-wave (SAW) device. Lower operating frequency (< 1 MHz for the FPW versus several hundred megahertz to a few gigahertz for the SAW device) simplifies the control electronics and makes integration of sensor with electronics easier. Magnetic rather than piezoelectric excitation of the FPW greatly simplifies the device structure and processing by eliminating the need for piezoelectric thin films, also simplifying integration issues. Furthermore, unlike the SAW device, the FPW can operate in both gas- and liquid-phase ambients, greatly increasing the number of potential applications. The versatile mag-FPW resonator structure can be configured to fulfill a number of critical functions in an autonomous sensed system. As a physical sensor, the device can be extremely sensitive to temperature, fluid flow, strain, acceleration, and vibration. By coating the membrane with self-assembled monolayers (SAMs), or polymer films with selective absorption properties (originally developed for SAW sensors), the mass sensitivity of the FPW allows it to be used as biological or chemical sensors. Yet another critical need in autonomous sensor systems is the ability to pump fluid. Mag-FPW structures can be configured as micropumps, using controlled acoustic streaming to move the fluid. In this project, Sandia will enhance the acoustic streaming by inducing wave interference through active control of the phase relationship of multiple sources. Successful development of mag-FPW devices as physical and chemical sensors, and as micropumps for both liquid- and gas-phase analytes, would enable the development of a completely new integrated sensing platform.

Successful development of mag-FPW devices as physical and chemical sensors, and as micropumps for both liquid- and gas-phase analytes, would enable the development of a completely new integrated sensing platform.

- *Fabrication, characterization, and modeling.* We designed, fabricated, and tested accelerometer chips. We attached a dual-membrane FPW device to a plastic manifold for gas-flow sensing. To heat the membrane above ambient temperature, we added direct current (DC) on top of the alternating current (AC) drive signal to the input port. Gas flowing over the membrane cooled the membrane, increasing the tension and the resonant frequency. Increased heating power improved the sensitivity. Reasonable sensitivity was achievable with careful compensation for drift in ambient conditions. We demonstrated better than 0.5 milli-g sensitivity. Greater sensitivity could be obtained with larger proof mass or a thinner cantilever beam.

We fabricated and tested acoustic streaming test structures. We observed rapid motion of tiny spheres suspended in water on the back surface of the FPW membrane; however, we were not able to drive the spheres in any preferred direction. These tests were done without a lid to confine the fluid near the membrane.

We used an improved FPW finite-element model (FEM) to explore the effects of fabrication flaws, packaging loads, and drive approaches on FPW operating characteristics. Packaging-induced stress loading on the FPW frame can result in operation anomalies. Loading interacted with the driven transducer leg (TL) configuration to increase or decrease the signal strength and even to alter which mode was most strongly excited. Modeling also showed that making the FPW membranes slightly wider (about one-eighth wavelength) than an exact number of wavelengths can compensate for misaligned TLs and improve performance, in agreement with our experimental observations.

- *Polyimide FPW devices.* Having made unsuccessful prior attempts to fabricate polymer membrane FPW devices in silicon, we pursued an alternative approach with Hutchinson Technologies Incorporated (HTI). HTI fabricated several FPW designs in their copper-polyimide flex-circuit material. We investigated several designs by FEM and selected seven designs for testing. HTI produced a few hundred of these devices on their standard 12-inch-by-27-inch sheet stock.

- *Single-port FPW drive electronics.* The microprocessor-based detector circuit tracked the impedance peak that occurred at the FPW resonance point. These new drive electronics allowed us to pursue simpler and more compact FPW designs and made it easier to integrate FPWs into complete sensor systems.

The picture shows several versions of polyimide flexible circuit board FPW devices mounted in a single ceramic package. The frequency response for one of the devices is shown in the graph at right. This type of FPW device could prove much cheaper to fabricate than our traditional Si-based version.

The sensing membrane of a flexural plate-wave accelerometer chip is centered in a thinned cantilever beam with a large, full-thickness proof mass at one end. The device is fabricated from a silicon wafer using a multiple-step deep reactive ion etching technique. Acceleration perpendicular to the plane of the chip causes the beam to flex, affecting the tension in the sensor membrane, and thus the resonance frequency of the device. The reference membrane is used to account for drift in ambient conditions (pressure and temperature).

Refereed

Schubert, W. K., and D. R. Adkins. 2001. "Mode Imaging and Finite-Element Modeling of Flexural Plate-Wave Resonators." Paper presented to the 198th Meeting of the Electrochemical Society, Phoenix, AZ, October.

Other Communications

Adkins, D. R., W. K. Schubert, and L. F. Anderson. 2001. "Magnetically Excited Flexural Plate-Wave Devices for Sensor Applications." *Proc. Sensors Expo* **1** (Chicago, IL, June): 317–322.

10334

Stress-Free Amorphous Diamond for High-Sensitivity Microsensors with Integrated Microstructures

J. P. Sullivan, R. J. Hohlfelder, T. A. Friedmann, R. J. Shul, M. P. de Boer, D. A. LaVan, W. K. Schubert, C. I. H. Ashby, T. M. Alam

In this project, Sandia's patented stress-free amorphous diamond (a-D) films were used to create high-sensitivity microsensors and rugged microelectromechanical systems (MEMS). A-D possesses a suite of properties unique to any other microstructural or microsensor material, including the ability to easily tailor film stress from compressive through zero to slightly tensile, hardness and stiffness 90 percent that of diamond, very high wear resistance, surfaces that are intrinsically hydrophobic, extreme chemical inertness, chemical compatibility with silicon (Si) processing, room-temperature deposition, the ability to control the film conductivity from insulating to conducting, and biocompatibility. We used ultrathin to thin (0.1 μ to 2 μ thick) a-D freestanding membranes in the fabrication of flexural plate-wave (FPW) chemical sensors. We used the chemical sensors to detect the presence of volatile organic compounds (VOCs) with ethyl cellulose as the detection layer.

We developed a number of a-D MEMS structures and new MEMS fabrication technologies to evaluate the properties of a-D and the performance of a-D MEMS structures. These structures included friction-and-wear test structures, new tensile test and fracture toughness structures, two-level structures, and grayscale lithography for sloped sidewalls in MEMS. The MEMS structures fabricated from a-D are particularly important because they offer one possible solution for addressing stiction in polysilicon (poly-Si) MEMS, and they also offer a possible technology leading to wear-resistant, long-lifetime MEMS. The MEMS structures also permit measurement of the mechanical properties of films of a-D. These measurements are not possible using conventional techniques developed for bulk material.

We also conceived new sensor and MEMS-device structures that offer new capabilities for Sandia's programs, including acoustic sensors, radio-frequency (RF)-processing structures based on submicron mechanical oscillators, hybrid a-D/poly-Si MEMS, and bio-MEMS.

We developed a number of a-D MEMS structures and new MEMS fabrication technologies to evaluate the properties of a-D and the performance of a-D MEMS structures. These structures included friction-and-wear test structures, new tensile test and fracture toughness structures, two-level structures, and grayscale lithography for sloped sidewalls in MEMS.

Project goals are to create new high-performance chemical sensors and MEMS, based on a stress-free a-D material invented at Sandia, and then to use these structures to gain understanding about the unique structure and properties of this material. We met these goals.

We fabricated FPW chemical sensors using thin membranes of a-D. We designed these sensors to detect the presence of VOCs, such as perchloroethylene, chloroform, and xylene, using ethyl cellulose as the sensing agent. (The sensor can be used to detect other chemical agents by applying a different sensing agent to the sensor surface.) The fabricated sensors showed good sensitivity to the volatile organics down to the two-parts-per-million level, with a net sensitivity a few times better than a comparable nitride-based sensor. Even further sensitivity improvement is expected by reducing the a-D membrane thickness from 0.37μ to a thickness less than 0.1μ .

We recently created and tested several new a-D MEMS test structures, including (1) a friction-and-wear test structure, (2) new tensile-test and fracture-toughness structures, (3) grayscale lithography test structures, and (4) a-D multilevel test structures. The friction-and-wear test structure consisted of coupled, orthogonally oriented comb-drive actuators designed to have a single contact surface with adjustable contact pressures and shear rates. (A portion of this design was featured on the April 2001 cover of the *MRS Bulletin*.) The new tensile test structures included large (greater than 1 mm) bowtie-like structures that were actuated using tensile test machines, as well as smaller pull-tab structures (gauge widths down to 10μ) that are actuated with a nanoindenter. These latter structures were used to determine the fracture toughness of a-D, an important materials property that determines the maximum tensile strain that a structural member could endure. We determined that the fracture toughness of a-D is about $8\text{ MPa}/\text{m}^2$, which is a high value for a ceramic material (it is about eight times higher than that of poly-Si). We developed the grayscale lithography test structures to create a new MEMS processing technology that allows three-dimensional (3-D) shaping of 2-D-deposited a-D films. These test structures successfully showed the viability of this approach and opened the possibility for the creation of all-a-D captured hub and pin-joint designs. We also developed the first multilevel a-D MEMS designs with a hybrid structure. These structures consist of patterned poly-Si combined with a-D structural elements (spring-supported

We developed the grayscale lithography test structures to create a new MEMS processing technology that allows three-dimensional (3-D) shaping of 2-D-deposited a-D films. These test structures successfully showed the viability of this approach and opened the possibility for the creation of all-a-D captured hub and pin-joint designs. We also developed the first multilevel a-D MEMS designs with a hybrid structure.

An amorphous diamond MEMS structure that is designed to measure the force generated by an electrostatically actuated comb drive is shown. The inset shows a close-up of the comb fingers of the comb drive.

resonating plates) and were developed to enable acoustic sensing using small MEMS structures. We successfully fabricated and tested these structures.

We also achieved a new understanding of the surface chemistry of a-D and the compatibility of a-D with biological materials. Water-contact-angle studies revealed that the as-fabricated a-D MEMS surface is nearly hydrophobic (advancing contact angle of 84°), and that annealing at temperatures greater than 1100 K yields a true hydrophobic surface (contact angle of 94°). We believe that the increase in contact with annealing is due to desorption of oxygen from the carbon surface, which leaves a mostly hydrogen-terminated surface. The intrinsic high-contact angles found for this material are especially useful for reducing stiction (contact adhesion) in MEMS structures, and this has been reflected in the ability to release the a-D MEMS structures without the use of applied hydrophobic coatings or supercritical drying.

We performed biocompatibility testing of the a-D material to evaluate the viability of a-D bio-MEMS structures. We grew endothelial capillary cells on uncoated and fibronectin-coated a-D surfaces and observed that there was abundant cell growth and adhesion on the fibronectin-coated surface but little adhesion to the uncoated surface. This result indicates that a-D MEMS would be especially valuable as bio-MEMS, which could be important for future Sandia programs.

We also achieved a new understanding of the surface chemistry of a-D and the compatibility of a-D with biological materials. Water-contact-angle studies revealed that the as-fabricated a-D MEMS surface is nearly hydrophobic (advancing contact angle of 84°), and that annealing at temperatures greater than 1100 K yields a true hydrophobic surface (contact angle of 94°).

Refereed

Alam, T. M., T. A. Friedmann, and A. Jurewicz. 2001. "Solid-State ^{13}C NMR Investigations of Amorphous Carbon Thin Films-Structural Changes During Annealing." *Proc. American Chemical Society*, accepted.

Alam, T. M., T. A. Friedmann, P. A. Schultz, and A. Jurewicz. 2001. "Investigation of Structure in Diamond Thin Films Using ^{13}C MAS and 2-D Exchange MAS NMR Spectroscopy." Paper presented to the National Meeting of the American Chemical Society, San Diego, CA, April.

Chen, X., J. M. Gibson, J. P. Sullivan, T. A. Friedmann, and P. Volyes. 2001. "Fluctuation Microscopy Studies of Medium-Range Order Structures in Amorphous Tetrahedral Semiconductors." *Proc. Fall 2000 Materials Research Society Meeting* **638** (Boston, MA, November–December): F14.40.1.

Friedmann, T. A., D. A. LaVan, T. M. Alam, P. G. Kotula, J. P. Sullivan, R. G. Hohlfelder, M. P. de Boer, C. I. H. Ashby, and M. Mitchell. 2001. "Comparison of Yield Strength of Amorphous Diamond Films Measured by Tensile Testing and Nanoindentation." Paper presented to the Spring 2001 Meeting of the Materials Research Society, San Francisco, CA, April.

Friedmann, T. A., J. P. Sullivan, R. J. Hohlfelder, D. A. LaVan, M. P. de Boer, M. T. Dugger, C. I. H. Ashby, and M. Mitchell. 2001. "Amorphous Diamond MEMS." Paper presented to the International Conference on Metallurgical Coatings and Thin Films ICMCTF 20, San Diego, CA, April–May.

Friedmann, T. A., R. J. Hohlfelder, J. P. Sullivan, D. A. LaVan, M. P. de Boer, P. G. Kotula, T. M. Alam, M. T. Dugger, C. I. H. Ashby, and M. Mitchell. 2001. "Micromechanical Structures Made from Hard Stress-Free Amorphous Diamond Thin Films." *Proc. Materials Research Society Fall 2000 Meeting* (Boston, MA, November–December).

Sullivan, J. P., T. A. Friedmann, and K. Hjort. 2001. "Diamond and Amorphous Carbon MEMS." *MRS Bulletin* **26** (April): 309–311.

Sullivan, J. P., T. A. Friedmann, M. P. de Boer, D. A. LaVan, R. J. Hohlfelder, C. I. H. Ashby, M. T. Dugger, M. Mitchell, R. G. Dunn, and A. J. Magerkurth. 2001. "Developing a New Material for MEMS: Amorphous Diamond." *Proc. Materials Research Society Fall 2000 Meeting* **657** (Boston, MA, November–December): EE7.1.1.

Sullivan, J. P., T. A. Friedmann, R. J. Hohlfelder, M. P. de Boer, M. T. Dugger, W. K. Schubert, C. I. H. Ashby, M. Mitchell, and R. G. Dunn. 2001. "Tetrahedral Amorphous Carbon (Amorphous Diamond) Mechanical Devices." Paper presented to the Spring 2001 Materials Research Society Meeting, San Francisco, CA, April.

Other Communications

LaVan, D. R., K. Jackson, S. J. Glass, T. A. Friedmann, J. P. Sullivan, and T. E. Buchheit. 2001. "Direct Tension and Fracture Testing Using the Lateral Force Capabilities of a Nanomechanical Test System." Published in book, *Mechanical Properties of Structural Films*, ASTM STP 1413 (West Conshohocken, PA): C. Muhlstein and S. B. Brown, eds.

10719

Radiation-Induced Prompt Photocurrents in Microelectronics: Physics

P. E. Dodd, W. Beezhold, B. L. Doyle, D. L. Buller, R. S. Flores, D. S. Walsh, G. Vizkelethy, M. R. Shaneyfelt, J. R. Schwank

The effects of photocurrents in nuclear weapons induced by proximal nuclear detonations are well known and remain a serious hostile environment threat for the U.S. stockpile. The focus of this project is to study the physical phenomena underlying prompt photocurrents in microelectronic devices and circuits. Sandia's goal is to obtain an improved understanding of these phenomena and to incorporate improved models of photocurrent effects into simulation codes to assist designers in meeting hostile radiation requirements with minimum build and test cycles.

Analytical photocurrent models have been successfully applied for low-level transients. At higher radiation dose rates, effects such as the variation of lifetime and carrier mobility with injection level, internal electric field distortions, and Auger recombination become important. These effects are typically ignored in analytical models. Numerical device simulators such as the Da VINCI three-dimensional (3-D) code work at a fundamental physical level and inherently handle phenomena such as electric field distortions and high-injection conditions. However, Da VINCI, which is used at Sandia primarily for cosmic-ray upset analysis, has neither been rigorously applied nor validated for the study of x-ray and gamma-ray photocurrents.

A newly developed capability on Sandia's ion microbeam accelerator is the ability to supply ionizing radiation in selected microregions of a device. Achievable dose rates should approach those possible with conventional large-scale simulators such as HERMES III and Saturn. It is, therefore, possible to test the physics and models in Da VINCI at the device or subcircuit level in ways not previously possible. This project will benefit weapon-based integrated circuit (IC) development by ensuring that they are insensitive to hostile threats.

This project met all milestones to study hostile-threat photocurrent effects in weapon electronics using transient radiation microscopy (TRM). We continued the experimental tests and simulations and found no "show-stoppers" from

A newly developed capability on Sandia's ion microbeam accelerator is the ability to supply ionizing radiation in selected microregions of a device. Achievable dose rates should approach those possible with conventional large-scale simulators such as HERMES III and Saturn. It is, therefore, possible to test the physics and models in Da VINCI at the device or subcircuit level in ways not previously possible. This project will benefit weapon-based integrated circuit (IC) development by ensuring that they are insensitive to hostile threats.

either the experiments or simulations. We successfully set up and used the second, improved version of the TRM. Improvements include more precise and reproducible positioning of the device under test (less than 100 nm), more precise current measurement, significant noise reduction, and shorter ion-beam pulse length. During the experiments, we used dose rates up to 200 Grad(Si) per second and a pulse length of 100 ns.

To further investigate the extended storage time effect that we discovered in our previous work, we performed a large number of experiments on a commercial positive-intrinsic-negative (PIN) diode with a wide range of dose rates and ion-beam pulse lengths. The Da VINCI simulations predicted the extended storage time very well for all dose rates. The agreement is quite remarkable for both high dose rates when the photocurrent exists several times longer than the ion-beam pulse, and for low dose rates where the diode response mirrors the beam pulse.

To complement the TRM measurement, we studied the transient response further, using electron linear accelerators (LINACs). No enhanced storage time was found, as had been previously predicted by Da VINCI simulations. Da VINCI simulations are in excellent agreement with both TRM and LINAC data taken over many orders of magnitude in dose rate.

We improved the TRM system still further to meet Mark III specifications. We performed experiments with this significantly improved system, and, using a new method to control the ion-beam pulse, we achieved ion-beam pulses shorter than 10 ns at a dose rate of 100 Grad(Si) per second. We performed experiments on extremely thin PIN diodes and partially confirmed simulation predictions that extended storage times would disappear. We are conducting further work to fully understand these results.

We performed TRM experiments on 2N2907 bipolar junction transistors, as well as experiments on discrete CMOS6r (bulk complementary metallic oxide semiconductor [CMOS]) and CMOS7 (silicon-on-insulator [SOI]) transistors fabricated in Sandia's Microelectronics Development Laboratory. These transistors form the building blocks for all CMOS ICs fabricated at Sandia for use in weapons and satellite systems. Data on the Sandia parts indicate that the beam dose rate may vary slightly from pulse to pulse,

We improved the TRM system still further to meet Mark III specifications. We performed experiments with this significantly improved system, and, using a new method to control the ion-beam pulse, we achieved ion-beam pulses shorter than 10 ns at a dose rate of 100 Grad(Si) per second. We performed experiments on extremely thin PIN diodes and partially confirmed simulation predictions that extended storage times would disappear. We are conducting further work to fully understand these results.

requiring further development of the system. To measure the very small currents induced in SOI devices, we fabricated and successfully tested special parallel transistor-array test structures.

Refereed

Dodd, P. E., G. Vizkelethy, W. Beezhold, D. S. Walsh, M. R. Shaneyfelt, J. R. Schwank, and B. L. Doyle. 2001. "Device-Level Studies of Dose Rate Response Using Numerical Simulations and Transient Radiation Microscopy." *J. Radiation Effects, Research and Engineering*, accepted.

Dodd, P. E., G. Vizkelethy, W. Beezhold, D. S. Walsh, M. R. Shaneyfelt, J. R. Schwank, and B. L. Doyle. 2001. "Device-Level Studies of Dose Rate Response Using Numerical Simulations and Transient Radiation Microscopy." Paper presented to the 19th Hardened Electronics and Radiation Technology Conference, San Antonio, TX, March.

10733

SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications

R. J. Shul, C. T. Sullivan, C. P. Tigges, M. A. Polosky, T. R. Christenson, S. Montague

Nearly all microactuator types rely on elastic suspension for reliable and effective operation. The exceptionally high yield strength and linear mechanical response possessed by single-crystal silicon (Si) renders it an appropriate material for the fabrication of springs, particularly if they may be patterned into arbitrary prismatic geometry. Using a deep reactive-ion etch (DRIE) process and silicon-on-insulator (SOI) wafers, Sandia will fabricate released, movable single-crystal Si structures 10 μm –100 μm thick with lateral dimensions less than 5 μm . The integration of these structures with surface-machined microelectro-mechanical systems (MEMS) or LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) enables a considerable design leverage in diverse applications such as clasps, sensors, inertial resonators, microengines, and position actuators.

The attraction of high-aspect-ratio Si is that the parts can have relatively high longitudinal (out-of-plane) stiffness and mass. With this technology, we anticipate the fabrication of thick actuators with increased force and comparable throw as compared to surface-micromachined (SMM) MEMS. Additionally, we will develop a two-mask lithographic process to form thick comb drives and stators (providing high force) with thin springs (low spring constants) on a single device to achieve low voltage actuation, a very desirable goal. Also enabled is the fabrication of high-mass structures with micron resolution for accelerometers or gyros, in addition to extremely rigid, lightweight, high-strength structural components for systems applications. The development of this technology will also allow fabrication of a simple and robust discriminator/optical redirect design. The simplicity is a direct consequence of the use of thick Si, which reduces the number of required levels for the device structure and permits a simpler configuration of the optical redirect elements and interconnect.

The attraction of high-aspect-ratio Si is that the parts can have relatively high longitudinal (out-of-plane) stiffness and mass. With this technology, we anticipate the fabrication of thick actuators with increased force and comparable throw as compared to surface-micromachined (SMM) MEMS. Additionally, we will develop a two-mask lithographic process to form thick comb drives and stators (providing high force) with thin springs (low spring constants) on a single device to achieve low voltage actuation, a very desirable goal.

We developed a DRIE process for multilevel SOI structures. The advantage of a multilevel DRIE process in bulk machining is the ability to trade off lateral and longitudinal structural stiffness for various applications. This capability is particularly useful for actuated suspension-bearing systems, since the overall depth of the device can be dictated by process or actuation force requirements while the suspension geometries are dictated by stiffness requirements. Since longitudinal versus lateral stiffness ratio is proportional to the square of the thickness, multilevel structures give a wide margin in suspension-system design.

The process requires two-level lithography and high-accuracy alignment. A hard mask that defines the actuator fingers and anchors is initially applied. To minimize topography issues, this mask is typically less than 2 μm and is inert to solvent rinses. The second-level mask is then patterned using conventional photoresist. The second-level mask contains the actuator fingers and anchors as well as the springs, and requires high-accuracy alignment. The sample is then exposed to the DRIE process for the first etch step. In this step, all features are etched to a specific depth. The second-level resist is then stripped in acetone, leaving the first-level resist intact. The sample is then DRIE-etched to the underlying oxide layer. The actuator fingers and anchors are protected by the first-level mask while the springs are exposed to the etch. The thickness of the springs is therefore less than that of the protected features. The springs, which are protected only during the first etch, are about 10 μm thick, while the anchors and actuators, which are protected during both etch steps, are about 25 μm thick. Although the multilevel SOI process has been demonstrated, the process needs to be optimized. Due to the high alignment tolerance necessary, we redesigned the mask. Using more sophisticated alignment marks, we expect alignment errors to be less than 0.5 μm . We completed preliminary fabrication of two-level structures on bulk Si wafers, and these show promise.

A cantilever beam 1 x 2 optical switch with a 5 μm thick top Si layer was successfully etched using the smooth sidewall DRIE process developed for optical microoptoelectromechanical systems (MOEMS) structures with small critical dimensions. A polymeric optical waveguide stack has been developed using perfluorocyclobutane (PFCB) and benzocyclobutene (BCB), with the high-index BCB as the core layer sandwiched between two layers of PFCB cladding. The waveguide stack is post-processed on top of the SOI

We developed a DRIE process for multilevel SOI structures. The advantage of a multilevel DRIE process in bulk machining is the ability to trade off lateral and longitudinal structural stiffness for various applications. This capability is particularly useful for actuated suspension-bearing systems, since the overall depth of the device can be dictated by process or actuation force requirements while the suspension geometries are dictated by stiffness requirements.

mechanical structure. We successfully fabricated and tested this structure and are optimizing the design, process steps, and integration to improve yield and operation.

We demonstrated further development of multiwafer integration and device location with SOI structures. A spring device was fabricated in 50 μm thick SOI to position small optical lenses. We believe this technology can be used to accurately position hybrid components to tolerances in the micron range and can also be used for wafer-to-wafer integration. It is also possible to envision using such structures to locate and align fiber optics for optical switching applications.

Recent success with the DRIE processing of SOI material stimulated interest in the fabrication of electromagnetic (EM) SOI devices. With a four-mask integrated SOI and DRIE process, EM devices were laid out and will be fabricated with isolated copper (Cu) coils and embedded rare-earth permanent magnets. The process uses double-sided DRIE, silicon (Si) oxidation, Cu electroplating, permanent magnet application, and oxide etch-release steps. The device is an eddy current-damped accelerometer that will use a generalized microactuator that operates as a shutter or valve.

We demonstrated further development of multiwafer integration and device location with SOI structures. A spring device was fabricated in 50 μm thick SOI to position small optical lenses. We believe this technology can be used to accurately position hybrid components to tolerances in the micron range and can also be used for wafer-to-wafer integration.

10744

Defining the Frontiers of Vertical, External-Cavity, Surface-Emitting Lasers

A. V. Smith, A. A. Allerman, R. E. Allman, K. M. Geib, A. J. Fischer, P. Esherick, D. K. Serkland

New sources based on diode laser technology are needed to improve wavelength coverage and beam quality for applications in remote sensing, local sensing, displays, and data storage. Vertical external-cavity surface-emitting lasers (VECSELs) provide significant flexibility in output wavelength and power over vertical-cavity surface-emitting lasers (VCSELs) and yet maintain the good beam quality inherent in VCSELs. The external cavity permits single transverse mode operation with large-diameter beams and also provides space for nonlinear optical elements within the laser cavity that can shift the output wavelength of near-infrared (IR) lasers into the visible, ultraviolet (UV), or mid-IR. Sandia continues to establish itself as a leader in VECSEL research and development by demonstrating record IR output powers, and compact blue and IR sources.

Sandia will advance the understanding and capabilities of VECSELs in three important areas:

- (1) Optically pumped, wavelength-converted VECSELs,*
- (2) Optically pumped, high-power (greater than 1 W) VECSELs, and*
- (3) Electrically pumped VECSELs.*

The utility and compactness of optical pumping of VECSELs has been demonstrated and continues to be the quickest route to advanced VECSEL devices. Wavelength-converted VECSELs shift the output wavelength of near-IR lasers into the visible and UV with frequency doubling. Mid-IR wavelengths can be produced by insertion of an optical parametric oscillator into the VECSEL cavity. High-power VECSELs have required optimized quantum-well (QW) gain regions and innovative thermal management, and we expect further improvements. Direct electrical pumping of VECSELs is a technically formidable problem but certainly presents the largest payoffs if realized. Our approach to electrically pumped VECSELs has changed to a bottom-emitting geometry that shows great promise. Sandia's excellence in the areas of compound semiconductor growth, photonic devices,

Sandia continues to establish itself as a leader in VECSEL research and development by demonstrating record IR output powers, and compact blue and IR sources. ... Sandia's excellence in the areas of compound semiconductor growth, photonic devices, and nonlinear optics provides us with an exciting opportunity to solidify our leadership position in this emerging technology.

and nonlinear optics provides us with an exciting opportunity to solidify our leadership position in this emerging technology.

• *Optically pumped VECSEL.* One path to higher power in VECSELS is increasing the pump diameter while keeping the pump power density near its optimum value. Unfortunately, this results in high temperatures in the active region, which reduces efficiency. In our previous work, we reported increased efficiency using an optically contacted sapphire window to remove heat from the active region. We now have further characterized VECSEL performance with the intracavity sapphire window. Using a pump beam diameter of 500μ , we achieved 1.5 W of continuous-wave (CW) output at 980 nm. We demonstrated good beam quality by transmitting 1 W through a single-mode fiber, starting with 1.5 W launched with simple lenses. Pulsed operation (66 percent duty cycle) produced a maximum average power of 2 W and a maximum peak power of 4.4 W. The optical efficiency remained only about half of that obtained with a small pump beam diameter, suggesting that further gains in efficiency and output power are obtainable with improved thermal management.

We made progress in understanding the so-called *blue mode* of operation of our broadband intracavity-doubled VECSEL. We suspected that this might be a mode-locked laser, but recent modeling of broadband frequency-doubling (with our state-of-the-art models) suggested that the VECSEL is, instead, frequency-modulated. This blue mode of operation shows stable blue-output amplitude with many modes simultaneously lasing and has milliwatts of output power in a compact diode-pumped setup, making it a desirable source for many blue-light applications.

• *Electrically pumped VECSEL.* We completely redesigned our electrically pumped VECSEL structures to address problems in achieving uniform current injection with our earlier designs. Our new approach utilizes a bottom-emitting structure that allows a central top contact to inject current uniformly where needed and also allows more efficient heat sinking. We fabricated devices that demonstrated much greater electroluminescence uniformity, as intended. We constructed a new probe station for rapid wafer-level characterization of the new device structure in both CW and pulsed modes. We obtained lasing in pulsed operation for oxide-confined devices in an external cavity with 5 percent output coupling with peak intensities in the milliwatt range.

In our previous work, we reported increased efficiency using an optically contacted sapphire window to remove heat from the active region. We now have further characterized VECSEL performance with the intracavity sapphire window. Using a pump beam diameter of 500μ , we achieved 1.5 W of continuous-wave (CW) output at 980 nm. We demonstrated good beam quality by transmitting 1 W through a single-mode fiber, starting with 1.5 W launched with simple lenses. Pulsed operation (66 percent duty cycle) produced a maximum average power of 2 W and a maximum peak power of 4.4 W.

We identified thermal issues due to the lack of heat sinking and substrate absorption as the key issues that need to be addressed.

Refereed

Alford, W. J., T. D. Raymond, and A. A. Allerman.
2001. "High Power and Good Beam Quality at 980
Nanometers from a Vertical External-Cavity Surface-
Emitting Laser." *J. Optical Society of America B*,
accepted.

10749

Growth and Characterization of Quantum Dots and Quantum Dot Devices

R. M. Biefeld, J. G. Cederberg, M. J. Hafich, S. R. Kurtz, J. F. Klem, K. M. Geib, J. R. Wendt, G. A. Vawter, E. D. Jones, S. K. Lyo, A. J. Fischer, W. W. Chow, H. C. Schneider

A clear systems need exists for the development of alternative short wavelength (ultraviolet [UV]) as well as 1.3 μm infrared (IR) lasers on gallium arsenide (GaAs) for use in vertical-cavity surface-emitting lasers (VCSELs). To meet this need, Sandia will develop efficient self-assembled quantum dot (QD) emitters. Confinement in three dimensions (3-D) will minimize the degradation of output power with increasing temperature and improve overall efficiency. Enhanced 3-D confinement should aid in the development of shorter-wavelength UV-visible (UV-vis) VCSELs as well as produce ultralow-threshold currents. The 3-D carrier confinement will decrease lateral carrier diffusion, thereby increasing the internal quantum efficiency (IQE). Additional benefits of QDs within VCSELs include polarization control and the ability to tailor the emission wavelength by accessing material compositions with greater strain than permitted in quantum wells (QWs).

Our project objectives include the following:

- To develop a microscopic theory that combines photonic and quantum kinetic aspects so that optical properties of the QD/extended-QW system can be predicted and compared to the observed characteristics for maximized device performance.
- To examine the effects of surface orientation and strain on the size and position distribution of self-assembled QDs using metal-organic chemical vapor deposition (MOCVD) and molecular beam epitaxy (MBE). We will use a combination of surface orientation, strain effects, and substrate or mask patterning with electron-beam lithography to grow QDs with controlled size, shape, and spatial distribution.
- To explore development of stable QD formation by argon (Ar) ion-beam etching of various substrates for an additional preparation technique.
- To prepare QD light-emitting diodes (LEDs) and lasers using the techniques developed in this investigation.

... we will develop efficient self-assembled quantum dot emitters. Confinement in three dimensions (3-D) will minimize the degradation of output power with increasing temperature and improve overall efficiency. Enhanced 3-D confinement should aid in the development of shorter-wavelength UV-visible (UV-vis) VCSELs as well as produce ultralow-threshold currents. The 3-D carrier confinement will decrease lateral carrier diffusion, thereby increasing the internal quantum efficiency (IQE).

We used MOCVD and MBE to grow indium arsenide (InAs), indium gallium arsenide (InGaAs), indium arsenide antimony (InAsSb), and GaAsSb QDs on GaAs. The QDs are uniform in size, varying from 15 to 30 nm in height and 50 to 100 nm in width, with densities of 0.5–2 times 10^{10} cm⁻². The size and position uniformity vary with the growth technique and conditions.

Specifics of our progress follow:

- We determined that the introduction of Sb during QD formation reduces the 2-D to 3-D critical thickness by reducing the surface energy. The photoluminescence (PL) intensity and linewidth are also dependent on growth technique and conditions, including temperature and growth rate. We observed PL intensity at both low temperature (4 K) and room temperature.

- We began investigating the interactions of the strain field of GaSb QDs with GaAs/AlGaAs QWs.

- We performed investigations of the substrate miscut. Results indicate the importance of step-density for dot formation.

- We began GaSb/InGaSb heterostructure growth and characterization to investigate Ar-milled nanostructures.

- We initiated our investigation into the dynamics of excitation-energy (e.g., exciton) transport in multidot-well structures.

- We have theoretically shown that the two dominant mechanisms by which an exciton hops between widely separated states are dipole-dipole and photon-exchange coupling.

- We found that for dot-to-dot coupling, the photon-exchange interaction can compete with the dipole-dipole coupling only for long-distance (greater than 400 nm) transfer.

- We are currently formulating multiphonon-assisted hopping transfer rates between dots.

- We computed gain spectra using a theory developed for QD lasers, using a self-consistent treatment of the coupled QD/QW system, including many-body Coulomb effects. Our approach involves adapting the semiconductor Bloch equations in the screened Hartree-Fock approximation to describe a shallow QD surrounded by a QW region. This picture describes both strain-induced dots and dot-in-a-well structures. The solution of the semiconductor Bloch equations gives the optical spectra.

We have theoretically shown that the two dominant mechanisms by which an exciton hops between widely separated states are dipole-dipole and photon-exchange coupling. We found that for dot-to-dot coupling, the photon-exchange interaction can compete with the dipole-dipole coupling only for long-distance (greater than 400 nm) transfer. We are currently formulating multiphonon-assisted hopping transfer rates between dots.

Refereed

Cederberg, J. G., R. M. Biefeld, A. A. Allerman, E. D. Jones, and S. R. Kurtz. 2001. "Growth of InAs and InAsSb Quantum Dots by Metal-Organic Chemical Vapor Deposition." Paper presented to the 43rd Electronic Materials Conference, Notre Dame, IN, 27–29 June.

Schneider, H. C., and W. W. Chow. 2001. "Highly Excited Quantum Dots." Paper presented to the IEEE-LEOS Semiconductor Laser Workshop, Baltimore, MD.

Schneider, H. C., and W. W. Chow. 2001. "Theory of Carrier-Induced Refractive Index Change and the Alpha Factor in Quantum Dot Lasers." *Applied Physics Letters*, submitted.

Schneider, H. C., W. W. Chow, and S. W. Koch. 2001. "Many-Body Effects in the Gain Spectra of Highly Excited Quantum Dot Lasers." *Physical Review B* **64** (5 September): 115315–115322.

Schneider, H. C., W. W. Chow, and S. W. Koch. 2001. "Theory of Population Dynamics in Quantum Dot Lasers." Paper presented to the Ultrafast Phenomena in Semiconductors V, Photonics West, San Jose, CA.

10766

Heterogeneous Integration of Optoelectronic Arrays and Microelectronics

K. M. Geib, A. A. Allerman, V. M. Hietala, D. K. Serkland

Integrated microsystems provide the benefits of small size, low power consumption, robustness, and potentially inexpensive manufacture. However, multifunctional advanced microsystems often require a combination of microelectronic and photonic technologies. For example, high-density two-dimensional (2-D) integrated optoelectronic arrays are the basic components necessary to construct real-time electrooptical signal-processing and analog information-processing microsystems. In corresponding applications such as digital and neural computing, data mining, and data communication switching, there is a critical need to provide local electronic processing in each optoelectronic pixel. Moreover, to achieve the required functionality in these systems, highly sophisticated devices, often with state-of-the-art performance, are necessary. Thus, combinations of dense numbers of high-performance devices originating from disparate technologies are needed to achieve the next generation of information-processing, interconnect, and intelligent sensing microsystems.

As the integration density increases, heat dissipation becomes a critical issue. Thus, tailoring the properties of the substrate material independently from the epitaxial material is desirable. The applique technique that we demonstrated allows this independence by transferring only the epitaxial material and eliminating the substrate material.

Advanced integration of electronics and photonics will require the development of techniques for bringing both technologies onto the same substrate.

In corresponding applications such as digital and neural computing, data mining, and data communication switching, there is a critical need to provide local electronic processing in each optoelectronic pixel.

An 8 x 8 VCSEL array with four 16-channel GTL drivers integrated into a single 84-pin grid array package. The plot is the measured input/output characteristic of one channel of the package device.

Integration of microoptics with light sources for communications is quite challenging. An alternative approach that minimizes alignment tolerances is to capture the light from several lasers using an imaging fiber bundle. The preliminary investigation of this technique looks promising.

- We demonstrated a hybrid package with high-speed drivers wire-bonded to vertical-cavity surface-emitting lasers (VCSEL) arrays. We fabricated a number of hybrid packages consisting of an 8 x 8 VCSEL array and four 16-channel high-speed drivers, with 100 percent operability reported by our industrial partner. The drivers convert gunning transceiver logic (GTL) digital logic levels into the current levels required by the lasers.

- We demonstrated functional 2-D VCSEL arrays flip-chipped onto driver circuitry. We demonstrated flip-chip integration of VCSELs with high-speed gallium arsenide (GaAs) electronics. We designed and fabricated a 64-element integrated VCSEL driver. We are fabricating VCSELs, which will be flip-chip-bonded to the driver die once the VCSEL fabrication is complete. We bonded 850 nm VCSELs to test coupons with 100 percent functionality.

- We designed and fabricated GaAs amplifier receiver circuitry. We designed, fabricated, and tested a 64-element receiver array. Each receiver element consists of a metal semiconductor metal (MSM) photodetector, an amplifier, a level discriminator, and a GTL output stage.

- We developed applique bonding of VCSELs to unique substrates. We demonstrated applique bonding of dissimilar materials by transferring VCSEL epitaxial material less than 10 μ thick after substrate removal onto a silicon wafer, using an electroplated indium interlayer.

- We developed a technique to provide collimation of the VCSEL array output in the integrated package. Collimation of the light from a VCSEL array requires

We developed a technique to provide collimation of the VCSEL array output in the integrated package.

Collimation of the light from a VCSEL array requires sophisticated optics and small alignment tolerances.

(a) Numerical aperture dependence of coupling efficiency (ratio of light coupled into the fiber to VCSEL light output) and coupling error (ratio of maximum to minimum coupling for a change in lateral position). (b) LED illumination of a small portion of the fiber bundle consisting of 15,379 individual fibers.

sophisticated optics and small alignment tolerances. We developed a more straightforward approach using a flexible imaging fiber bundle light guide with a 1.8 mm hexagonal cross-section consisting of 15,379 fibers, each with a 9.1μ core and a 2μ thick cladding on a 13.5μ pitch to transmit the VCSEL light to the detector without the use of collimating optics. This technology is insensitive to VCSEL/fiber alignment, making it ideally suited for light transmission over short distances (several meters).

This technology is insensitive to VCSEL/fiber alignment, making it ideally suited for light transmission over short distances (several meters).

Refereed

Hietala, V. M., C. Chun, J. Laskar, K. D. Choquette, K. M. Geib, A. A. Allerman, and J. J. Hindi. 2001. "Two-Dimensional 8 x 8 Photoreceiver Array and VCSEL Drivers for High-Throughput Optical Data Links." *IEEE J. Solid-State Circuits* **36** (September): 1297–1302.

Mukherjee, S. D., K. D. Choquette, K. M. Geib, G. R. Hadley, T. R. Carter, A. J. Fischer, C. T. Sullivan, M. Robinson, and K. Tatah. 2001. "Crosstalk Versus Positional Tolerance Trade-off in Parallel Datalink Packaging Using VCSEL Arrays and Fiber Image Guides." Paper presented to the ASME International Electronic Packaging Technical Conference, Kauai, HI, 8–13 July.

10775

Miniature Sensors for BW Agents Using Fatty-Acid Profiles

G. C. Frye-Mason, K. Wally, C. H. Morgan, P. R. Lewis, C. D. Mowry, R. P. Manginell

Sandia is developing a microfabricated sensor for the rapid identification of bioorganisms. When fully developed, this device will provide a unique miniaturized capability for biological warfare (BW) agent detection, an important national security mission that is especially key to nonproliferation and materials control (NP&MC). Tailored toward detection of pathogens and other BW agents such as anthrax, the device will also have significant spin-off applications.

The miniature BW agent detector relies on an established technique of identification based on fatty-acid (FA) profiles. These biomarkers are used to distinguish bacteria at the gram-type, genera, and even species levels. Current commercial methods extract bacterial samples and chemically derivatize them to produce fatty-acid methyl esters (FAMES). These methods are lengthy (over one hour) and labor-intensive, but have been used to differentiate BW agents, plant pathogens, food-borne pathogens, and other microorganisms. More recent work demonstrates that FAMES can be obtained from whole bacterial cells in an in situ single-step pyrolysis/methylation/mass spectrometry analysis. Derivatization and detection occur rapidly, with little sample preparation. Bacteria have been differentiated. This method can also detect the causal agent of anthrax, amino acids, and oligopeptides.

We used microfabricated pyrolyzers to demonstrate the in situ pyrolysis of whole-cell bacteria to produce volatile FAME derivatives, and demonstrated FAME detection using surface acoustic-wave (SAW) devices.

The intended goal of a miniature BW agent detector will require progress in the area of micropyrolysis, microfabricated gas chromatography (GC) separations, and detection of FAME products. We made progress in each of these areas, including the following recent accomplishments:

Sandia is developing a microfabricated sensor for the rapid identification of bioorganisms. When fully developed, this device will provide a unique miniaturized capability for biological warfare agent detection, an important national security mission that is especially key to nonproliferation and materials control.

(1) Demonstrated microfabricated GC separations of FAME molecules, using air carrier (previously only nitrogen had been used). This achievement is important since a portable system would have to use air.

(2) Redesigned and fabricated a new test fixture for micropyrolysis tests. This test fixture worked as designed, enabling important bacterial pyrolysis experiments.

(3) Developed a reproducible procedure for capturing and analyzing the products of micropyrolyzer tests. This procedure also demonstrated that micropyrolysis devices could be reused many times, a key issue for the final system.

(4) Demonstrated a coating technique used to keep the sample contained in the “hot” zone of the micropyrolysis device.

(5) Demonstrated that the micropyrolysis/methylation technique, using FAs, does indeed give a linear response versus quantity of material.

(6) Demonstrated SAW detection of FAME molecules. Two-coated SAW devices detected vapor-phase FAMES rapidly and reversibly. These characteristics demonstrate that SAW detection could be viable for the portable device envisioned in this project.

(7) Demonstrated micropyrolysis of two bacterial samples, *Bacillus subtilis* and *Pseudomonas fluorescens*. We produced several FAME molecules from each bacterium. Our original milestone was detection of FAMES from three bacteria.

(8) Generated intellectual property for Sandia in the form of a technical advance.

We redesigned and fabricated a new test fixture for micropyrolysis tests. This test fixture worked as designed, enabling important bacterial pyrolysis experiments.

Other Communications

Morgan, C. H., C. D. Mowry, R. P. Manginell, G. C. Frye-Mason, R. J. Kottenstette, and P. R. Lewis. 2000. “Rapid Identification of Bacteria with Miniaturized Pyrolysis/GC Analysis.” *Proc. Society of Photooptical Instrumentation Engineers: Advanced Environmental and Chemical Sensing Technology* **4205** (Boston, MA, October): 199–206.

10776

Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays

S. M. Brozik, D. W. Branch, D. Y. Sasaki, G. D. Meyer, R. W. Cernosek

This project continues with the development of enhanced-sensitivity biosensors utilizing acoustic platforms with biorecognition layers. The resulting sensors will be capable of detecting both chemical and biological agents in aqueous media, and have application in nonproliferation, military scenarios, environmental monitoring, intelligence, law enforcement, medical diagnostics, and food processing.

This project is evaluating two acoustic sensor platforms for detection of biological warfare (BW) agents: the quartz crystal microbalance (QCM) and the shear-horizontal surface acoustic-wave (SH-SAW) device. These acoustic devices probe both the mass and the viscoelastic properties (film rigidity) of a surface layer. The oscillating surface of the device causes displacement and deformation of the layer. Mechanical compliance of surface receptor layers, bound organisms, and the surrounding fluid media all contribute to the viscoelasticity. By exploring the microdevice-biomaterials interface, we can optimize these sensors to achieve the desired sensitivity required by the nonproliferation and military communities.

- *Investigation of nonspecific binding of immobilized antibody layers.* To minimize nonspecific attachment of antigens, we applied thin films of polyethylene glycol (PEG) to the gold (Au) surface of the reference sensors. This process has proved satisfactory for preliminary investigations.

- *QCM sensor.* We investigated several covalent immobilization techniques that are designed to be compatible with QCM resonators and SH-SAW acoustic sensors. One such scheme uses an alkanethiol and streptavidin film to tether antibodies to a Au surface. The Au electrode surface is first bioactivated with mercaptohexadecanoic acid (MHDA), which mediates conjugation of streptavidin to biotinylated antibodies. The antibodies were biotinylated at a substitution level to minimize steric hindrances and, therefore, optimize their natural affinity to their target analytes. We achieved typical substitution amounts that range from 5 to 18 moles of biotin per mole of immunoglobulin G (IgG). The

This project is evaluating two acoustic sensor platforms for detection of biological warfare (BW) agents: the quartz crystal microbalance (QCM) and the shear-horizontal surface acoustic-wave (SH-SAW) device. These acoustic devices probe both the mass and the viscoelastic properties (film rigidity) of a surface layer.

bioconjugation scheme permits the surface chemistry to be renewed by biotinylating the antibodies with iminobiotin, where binding is dependent on the local pH.

We used the above scheme to capture anthrax spore simulants (e.g., *Bacillus thuringiensis*) on the surface of a QCM resonator operating in liquid. The University of Alabama at Birmingham (UA) provided antibodies that were raised against *Bacillus anthracis*. These antibodies were biotinylated and then bound to the surface of a 5 MHz QCM resonator. We passed buffer containing a specific concentration of spores across the surface of the QCM and monitored frequency shift (Δf). The frequency was resolved to 0.5 Hz, and we extrapolated a detection limit of 24.2 ng cm⁻². This translates to around 32,000 spores that can be detected using a 5 MHz QCM sensor.

- *SH-SAW sensor.* Critical to the mass sensitivity of the SH-SAW device is applying the appropriate polymer thickness to simultaneously optimize the following parameters: E-field screening from the liquid, insulation of the interdigitated electrodes (IDTs) from liquid, and the mass sensitivity. We evaluated the static capacitance of the double-electrode, split-finger IDTs in air ($\epsilon_r = 1$) and in water ($\epsilon_r = 78.5$) using different polyimide ($\epsilon_r = 2.9$) thicknesses on the LiTaO₃ ($\epsilon_r = 47$). We found effective screening to occur when the polyimide thickness was around 1.2 μ m.

We demonstrated a detection of spores generically by using biotinylated polystyrene beads ($r = 0.5 \mu$ m). We applied PEG molecular weight (MW) 5000 to the Au surface of the reference to prevent nonspecific binding while antibodies were attached to the working line. Measuring the phase shifts, we detected the amount of mass. The amount of beads injected was 10⁵ beads per milliliter. We found the net phase shift post injection to be about 1.1°, corresponding to bound mass of about 0.1 μ g. At this time, further optimization of the polyimide film is necessary to improve mass sensitivity.

- *Characterization of flexural plate-wave (FPW) devices for response in low-viscosity liquid environments.* Sandia is developing magnetic FPW devices in a separate project. Although that project has not yet demonstrated a fully functional FPW device in a liquid environment, significant progress has been made toward that goal.

- *Collaboration efforts.* We continue to receive anti-anthraxis antibodies and test spores from UA. In addition, small peptide units (SPUs) are being developed as alternative

We used the above scheme to capture anthrax spore simulants (e.g., Bacillus thuringiensis) on the surface of a QCM resonator operating in liquid. The University of Alabama at Birmingham (UA) provided antibodies that were raised against Bacillus anthracis.

receptors for anthrax. These patented SPUs should provide robust bioreceptor layers capable of being tailored for array elements.

Ongoing work in collaboration with Auburn University (AU) will focus on food pathogen detection. In addition to laboratory and modeling collaborations, AU has supplied Sandia with antibodies raised against Salmonella so we can conduct parallel studies using the SH-SAW device.

Ongoing work in collaboration with Auburn University (AU) will focus on food pathogen detection.

Refereed

Cernosek, R. W., B. A. Chin, J. M. Barbaree, V. Vodyanoy, D. E. Conner, and Y. P. Hsieh. 2001. "A Rapid Biosensing System for Detecting Food-Borne Pathogens." *Proc. Sensors Expo* (Chicago, IL, 5–7 June): 113–116.

Hillman, A. R., R. W. Cernosek, and S. J. Martin. 2001. "Interpretation of Viscoelastic Phenomena on Thickness Shear Mode Resonators." *Analytical Chemistry*, submitted.

Josse, F., F. Bender, and R. W. Cernosek. 2001. "Guided SH-SAW Sensors for Chemical and Biochemical Detection in Liquids." *Analytical Chemistry*, accepted.

Josse, F., K. Zinszer, F. Bender, and R. W. Cernosek. 2001. "Guided SH-SAW Sensors for Liquid-Phase Detection." *Proc. IEEE International Frequency Control Symposium* (Seattle, WA, 6–8 June).

Lucklum, R., P. Hauptmann, and R. W. Cernosek. 2001. "Thin-Film Material Properties Analysis with Quartz Crystal Resonators." *Proc. IEEE/EIA International Frequency Control Symposium* (Seattle, WA, 6–8 June).

Other Communications

Cernosek, R. W. 2001. "Surface Acoustic-Wave (Bio)Chemical Sensors." (Invited) Paper presented to the 4th Annual Army Force Health Protection Conference, Albuquerque, NM.

Cernosek, R. W., C. A. Bailey, B. A. Chin, A. N. Rumpf, and S. J. Martin. 2001. "The Effects of Liquid-Solid Suspensions on TSM Resonator Response: Consequences for Biosensing Using Shear Mode Acoustic Devices." Presentation to the Acoustic Wave Sensor Workshop, Taos, NM.

Cernosek, R. W., S. M. Wentworth, Y. Shen, C. Ellis, C. S. Yamarthy, H. Yang, T. Lishok, and F. Smith. 2001. "Love-Wave Sensors for Food Safety." Poster session at the Auburn University Detection and Food Safety Center Technology Conference, Auburn, AL.

10782

High-Al-Content AlGaInN Devices for Next-Generation Electronic and Optoelectronic Applications

A. G. Baca, C. I. H. Ashby, S. R. Lee, J. Han, R. J. Shul, M. H. Crawford, A. F. Wright, A. J. Fischer, C. C. Mitchell

Tremendous recent breakthroughs in the technology of gallium arsenide (GaN) and related aluminum gallium indium nitride (AlGaInN) materials synthesis and device demonstrations have sparked world-wide interest in these materials for lighting and other applications. By adding Al and In to GaN, the energy bandgap can be tuned from the visible (2.0 eV) to the ultraviolet (UV, 6.1 eV). These advances will drive the development of multicolor light-emitting diode (LED) displays and white-light sources with high reliability (> 10 years' lifetime) and low power consumption (~ 10 W). The large-bandgap (2.0–6.1 eV), high-breakdown field ($\sim 5 \times 10^6$ V/cm) and saturation drift velocity (2.7×10^7 cm/sec) and chemical inertness will enable a new generation of high-temperature and high-power electronics critical for many commercial and defense applications.

Realizing efficient solid-state white-light illumination and high-power electronics will depend on further improvements in high-Al-content AlGaInN materials and devices. Over the last several years, Sandia has made substantial strides toward the development of AlGaInN materials and devices; the world's shortest-wavelength (355 nm) LED was recently demonstrated by Sandia researchers. This project seeks to achieve these necessary improvements through a partnership with GELCORE (joint venture between EMCORE and GE Lighting) to develop "High-Efficiency GaN-LED-Based White-Light Sources," and through forefront research in AlGaIn-based high-electron-mobility transistor (HEMT) electronics technology. In addition, the development of cantilever epitaxy will provide lower-defect substrates for these applications. The GELCORE partnership is synergistic, with internal missions to develop short-wavelength illumination sources for chemical-biological sensing, while the development of high-power electronics will lead to new business opportunities in portable (military) and satellite communications.

... the world's shortest-wavelength (355 nm) LED was recently demonstrated by Sandia researchers. This project seeks to achieve these necessary improvements through a partnership with GELCORE (joint venture between EMCORE and GE Lighting) to develop "High-Efficiency GaN-LED-Based White-Light Sources," and through forefront research in AlGaIn-based high-electron-mobility transistor (HEMT) electronics technology.

We realized low-dislocation-density GaN growth in our work by a method that both is simpler and offers more benefits than other approaches. The method is termed *cantilever epitaxy*, a new type of epitaxial lateral overgrowth. We showed cantilever epitaxy to reduce dislocation density by about three orders of magnitude. Our efforts in *p*-doping were successful and improved the processing of LEDs. Our growth efforts in high-Al-content AlGa_N by metal-organic chemical vapor deposition (MOCVD) also were successful and resulted in high GaN, HEMTs with a breakdown voltage in excess of 100 V. These transistors also achieved high power levels of 1.67 W/mm at 10 GHz.

(1) We achieved LED power levels of greater than 1 mW at 380 nm (our goal was 2 mW).

(2) We improved *p*-contacts by optimizing the anneal temperature.

(3) We developed cantilever epitaxy process with dislocation densities three orders of magnitude lower than conventional growth methods.

(4) We developed processes for growing high-Al-content films without cracking.

(5) We developed GaN HEMT with greater than 100 V breakdown. The transistor achieved power levels of 1.67 W/mm at 10 GHz.

We realized low-dislocation-density GaN growth in our work by a method that is both simpler and offers more benefits than other approaches. The method is termed cantilever epitaxy, a new type of epitaxial lateral overgrowth.

Refereed

Ashby, C. I. H., C. C. Mitchell, J. Han, N. A. Missert, P. P. Provencio, D. M. Follstaedt, G. M. Peake, and L. Griego. 2000. "Low-Dislocation Density GaN from a Single Growth on a Textured Substrate." *Applied Physics Letters* 77: 3233–3235.

Other Communications

Baca, A. G., R. D. Briggs, J. W. Johnson, C. Monier, A. A. Allerman, C. C. Mitchell, J. R. Wendt, R. J. Shul, F. Ren, and M. G. Armendariz. 2001. "High-Performance GaN/AlGa_N HEMTs." *Proc. 200th Electrochemical Society Meeting, State-of-the-Art-Program on Compound Semiconductors PV2001-20* (San Francisco, CA, 2–9 September): 41–46.

10783

Microfabrication of Electromagnetic Devices*T. R. Christenson, C. P. Tigges, W. G. Yelton, P. G. Clem, D. T. Schmale*

High-performance microfabricated electromagnetic (EM) devices remain an integration challenge due to lack of understanding about depositing high-quality ferromagnetic materials and inability to co-fabricate high-quality factor and high-density EM coils. Sandia expects that the solution to these processing issues will enable batch microfabrication of a large class of EM devices. These devices include millimeter-scale actuators with several-hundred-micron actuation strokes at well above millinewton output forces. Performance is facilitated with soft ferromagnetic materials that possess high-saturation magnetic flux density and additive or molding-based high-aspect-ratio batch-processing techniques. The resulting generic magnetic microactuator platform technology is well suited for applications involving microrobotic propulsion, high reliability, and relatively high-power handling optical and radio-frequency (RF) switching, low-leakage gas and liquid valves, gas- and liquid-flow regulators, precision microoptical positioning stages, and microgenerators. These devices also will also benefit from permanent magnets, which possess exceptional efficiency at a small scale.

Due to the low driving point impedance of electromagnets and the low temperatures involved with this type of fabrication, we anticipate that ultimately, co-integration with bipolar drive and control microcircuitry will enable integrated sensing, data taking, and closed-loop operation.

We devised two processing techniques to realize a batch-fabricated air core coil and a coil with a soft ferromagnetic material core. Both schemes rely on a batch diffusion-bonding and wafer-transfer approach that we found to yield exceptionally low interface resistance between electroplated copper layers. We identified preferred diffusion-bonding conditions for Cu as 425°C at a pressure of 5 ksi for 1 to 2 hours. We found titanium (Ti) to serve as a suitable sacrificial metal that maintains etch properties subsequent to Cu diffusion-bonding sequences.

One approach to coil fabrication involving multiple-angled deep x-ray exposures was tested for the first time using

High-performance microfabricated electromagnetic (EM) devices remain an integration challenge due to lack of understanding about depositing high-quality ferromagnetic materials and inability to co-fabricate high-quality factor and high-density EM coils. Sandia expects that the solution to these processing issues will enable batch microfabrication of a large class of EM devices. These devices include millimeter-scale actuators with several-hundred-micron actuation strokes at well above millinewton output forces.

an improved custom-fabricated two-axis tilting stage. Results revealed a considerably more powerful technique for the definition of reentrant photoresist geometry. We investigated electrochemistry for an alloy of nickel-iron-cobalt and determined operating conditions for a family of low-coercivity (less than 1 Oersted), high-saturation flux density (greater than 1.7 Tesla) materials. We determined that a fluoroborate-based chemistry provided significantly greater bath stability than sulfamate- or sulfate-based chemistry.

The identification of electroplating conditions that facilitate the compositions necessary for kovar and SuperInvar low thermal-expansion alloys was an additional benefit of this work. We laid out a new test mask to evaluate magnetic and mechanical properties of these electrodeposits, including structures for internal strain measurement, stress-strain response, bulk modulus, thermal-expansion coefficient, and magnetic hysteresis response.

We filed for two patents on our concern-batch coil microfabrication and multiple-angle x-ray exposures.

The identification of electroplating conditions that facilitate the compositions necessary for kovar and SuperInvar low thermal-expansion alloys was an additional benefit of this work.

Refereed

Christenson, T. R., and W. C. Sweatt. 2001. "Microoptomechanical Uses of Deep X-Ray Lithography (X-Optics)." Paper presented to HARMST '01, Baden-Baden, Germany, 17 June.

10784

GaAs MOEMS Technology

*O. B. Spahn, C. P. Tigges, J. L. Reno, E. J. Garcia, M. A. Polosky,
G. D. Grossetete, J. F. Klem, J. J. Lean*

Many microelectromechanical systems (MEMS)–based components require optical monitoring techniques that use optoelectronic devices to convert mechanical position information into useful electronic signals. While the constituent piece-parts of such hybrid opto-MEMS components can be optimized separately, the resulting component performance, size, ruggedness, and cost are compromised substantially by assembly and packaging limitations.

Gallium arsenide (GaAs) microoptoelectromechanical systems (MOEMS) offers the possibility of monolithically integrating high-performance optoelectronics with simple mechanical structures built in very low stress epitaxial layers, with a resulting component performance that is determined only by GaAs microfabrication technology. For example, submicron features can be etched into GaAs structures, allowing for the sensing of submicron alignment and displacements by a variety of approaches. This capability provides dramatically improved sensitivity and eliminates packaging and alignment problems. More importantly, GaAs MOEMS implicitly integrates the capability for radiation-hardened optical communications into the MEMS sensor or actuator component, a vital step toward rugged, integrated, autonomous microsystems that sense, act, and communicate.

We continued to focus on microfabrication issues to control stiction, the limiting mechanism in the operation of our devices. We developed novel switch designs that do not rely on mechanical stops (and therefore physical contact) to limit the motion of the cantilever, a novel and radical approach that not only circumvents the processing roadblocks but also offers superior performance. We consider our new approach to be highly promising not only in terms of our objective, but also as a general concept in MEMS drive and sensor technology. We are filing technical advances on this subject.

We also designed a novel mechanically latched switch structure that is useful for mechanical memory applications. Concurrent with our process development and design activities, we obtained data on dynamic performance of the

We continued to focus on microfabrication issues to control stiction, the limiting mechanism in the operation of our devices. We developed novel switch designs that do not rely on mechanical stops (and therefore physical contact) to limit the motion of the cantilever, a novel and radical approach that not only circumvents the processing roadblocks but also offers superior performance. We consider our new approach to be highly promising not only in terms of our objective, but also as a general concept in MEMS drive and sensor technology.

standard 1-by-2 switches, and we compared that data with predicted values. In addition to its inherent value, the data will be used in the implementation of a physically based control approach that will mitigate the presence of stiction with an appropriate drive signal and allow high-frequency operation.

We made progress in fabrication of high-reflectivity (tilting) micromirrors (HiRTM) devices and changes in the device structure implemented for the second-generation design. We also designed distributed Bragg reflector (DBR) Fabry-Perot filters for sensor applications and optical components for the communications industry. These types of devices constitute basic building blocks of tunable active structures such as vertical-cavity surface-emitting lasers (VCSELs) and resonant-cavity detectors.

We made progress in fabrication of high-reflectivity (tilting) micromirrors. ... We also designed distributed Bragg reflector Fabry-Perot filters for sensor applications and optical components for the communications industry.

Refereed

Spahn, O. B., C. T. Sullivan, T. Bakke, A. A. Allerman, J. L. Reno, G. D. Grossetete, J. J. Lean, and C. Fuller. 2001. "Promise and Progress of GaAs MEMS and MOEMS." *Proc. GaAs MANTECH 2001* (Las Vegas, NV, May).

Other Communications

Spahn, O. B., C. T. Sullivan, J. Burkhart, C. P. Tigges, and E. J. Garcia. 2000. "GaAs-Based Microelectromechanical Wave-Guide Switch." *Proc. 2000 IEEE/LEOS International Conference on Optical MEMS* (Kauai, HI, 21–24 August): 41–42.

10785

Integrated Microsensors for Autonomous Microrobots

E. J. Heller, D. R. Adkins, S. A. Casalnuovo, R. H. Byrne, R. C. Hughes

The goal of this project is to develop a suite of new low-power integrated microsensor systems that will enable the development of networks of 0.25 in.³ autonomous microrobots.

The focus of Sandia's work is on two primary sensor classes. The first class consists of microsensors that can be used as navigational and communication aids. Several possible devices in this class include microglobal positioning systems (GPS), magnetometers, ultrasonic or optical detector systems (for proximity detection), and single-chip radio-frequency (RF) transceivers. Although we will consider a number of possibilities in this class, only those deemed most suitable to the microrobot application will undergo further development. The second group of sensors consists of microsensors for environmental trace-chemical detection. There are a number of possible sensors to consider in this class, but microsensor systems based on chemiresistors and surface acoustic-wave (SAW) devices have already undergone the most substantial development and will be given priority. The primary emphasis is to develop microsensors that can take advantage of modern semiconductor manufacturing techniques to efficiently produce large numbers of essentially disposable microsensor systems. As devices are completed, they will be incorporated into microrobots that others are constructing. We will use these microsensors to enable networks of autonomous microrobots. We will consider several methods of network organization, but the primary focus is expected to be on "marsupial" systems. These systems use a larger mother robot to deploy and support a large group of networked autonomous microrobots.

Our tracked microrobot is capable of climbing over nickels, dimes, and quarters and can easily move on short-pile carpeting. In addition, the microrobot contains some of the features of much larger robots, including a PIC (programmable interface controller) 16C77 central processing unit (CPU), batteries, a thermistor temperature sensor, and status-indicator light-emitting diodes (LEDs). However, the microrobot's functions are currently preprogrammed. Future

A photograph of the microrobot showing the control electronics, drive motors, and tracks.

The focus of Sandia's work is on two primary sensor classes.

The first class consists of microsensors that can be used as navigational and communication aids. The second group of sensors consists of microsensors for environmental trace-chemical detection.

versions of the microrobot will allow for sensing environmental properties and responding according to programmed instructions.

Two versions of the microrobot and associated software are available. The initial version of the microrobot and software allows the microrobot to move forward and backward only. The most recent version allows the robot to make 90° right and left turns under program control. This feature is an initial step toward giving the microrobot obstacle-detection capabilities. The microrobot can run for 15 to 20 minutes on a single set of batteries and travel about 90 inches. The control electronics for the microrobot are composed of a combination of devices in die form and commercially available passive surface-mount components, and are built in the form of a simple multichip module fabricated on a glass substrate. The control electronics are mounted on the front of the microrobot and are easily accessible for *in situ* programming of the onboard PIC microprocessor.

We are pursuing several new developments to improve the capabilities of the microrobot. We made improvements to the mechanical capabilities of the microrobot platform itself, including new wheels that prevent the silicone tracks from falling off and new Smoovy motors with 25:1 gear reduction that will allow the robot to move about five times faster than the previous microrobots that used motors with 125:1 gear reduction. We are also investigating direct current (DC) permanent magnet motors that use less power and run faster than the present motors.

Among the most significant improvements is the addition of an RF communications link to allow both remote control of the microrobot and data from onboard sensors to be transmitted from the microrobot. The RF communications link is being implemented using the RF Monolithics TR1000 hybrid transceiver. This module is contained in a 10 x 7 x 2 mm³ shielded enclosure and requires a minimum of external passive components. The complete radio is located on a 15 x 13 mm² two-sided conventional FR-4 printed wiring board, with surface-mount components on both sides. This radio module has been used successfully for other robotics applications, but for the current project we had to write new code to interface with the MicroChip PIC microcontroller. The radio operates at 916.5 MHz and has a maximum data transmission rate of 115.2 kb/sec using amplitude-shift keyed modulation, making it suitable for voice transmission. In

A photograph of the microrobot crawling over coins.

Two versions of the microrobot and associated software are available. The initial version of the microrobot and software allows the microrobot to move forward and backward only. The most recent version allows the robot to make 90° right and left turns under program control. This feature is an initial step toward giving the microrobot obstacle-detection capabilities.

upcoming work, we expect to implement simple commands to give the user remote control capability and readout of temperature sensor data.

10786

Silicon-Integrated Planar Microbatteries

S. H. Kravitz, N. S. Bell, D. Ingersoll

Sandia seeks a new microbattery concept that will be integrated into silicon (Si). By combining Si-micromachining with new cathode and anode materials, this concept will permit batteries to be built directly into integrated circuit (IC) or microelectromechanical systems (MEMS) devices. The concept is to micromachine interdigitated reservoirs on a Si wafer, which will serve as containers for the battery materials. The reservoirs will be interconnected by microchannels, which provide a means to pass electrolyte between the interdigitated reservoirs without allowing particles through. We will electrically isolate the reservoirs from each other by using a thermally grown oxide. A conductive liner will then be added to the reservoirs.

We will achieve dispensing of the electroactive material into the reservoirs using MicroPen, a computer-aided design (CAD)-driven system consisting of a high-precision fluid-dispensing unit coupled with an X-Y table. To prevent clogging or migration between reservoirs, spherical monodisperse powders with a narrow size distribution will be prepared by co-precipitation of alkoxides or by flame pyrolysis of atomized chemical precursors.

We will design this device in two different ways. As a series-connected battery, it will supply 100 V to MEMS devices. In parallel connection, it will be a high-capacity/high-power 3 V battery capable of supplying high current needs for communication or mechanical motion. With some battery chemistries, it will be possible to recharge, using photovoltaic (PV) cells. The approach of making an integrated and co-packaged planar power source on a Si chip will reduce the size and cost of a battery-powered system.

We made progress in three areas: (1) the redesign and fabrication of the microbattery structure, (2) the formulating and dispensing of pastes of appropriate rheology and particle size to fill the cavities of the battery, and (3) the development of the appropriate filling procedure for the compartments. We accomplished the following tasks:

- Developed new Bosch-etch procedures to allow etching of the three different etch depths required in this design, with special emphasis on perfecting the etch to create 2 μm or 3 μm posts 100 μm deep.

We made progress in the redesign and fabrication of the microbattery structure, the formulating and dispensing of pastes of appropriate rheology and particle size to fill the cavities of the battery, and the development of the appropriate filling procedure for the compartments.

- Developed a buried electrode procedure for the electrical contact/lid assembly to allow complete sealing.
- Established anodic bonding parameters for Si, with 1000 Å of insulating oxide.
- Developed a new mask to allow accurate alignment of the electrical contact/lid assembly to the Si compartments.

We sealed the first devices. The yield on these sealed devices was not high because space around the hundreds of devices on the wafer was insufficient to form a good anodic bond. We have since redesigned the layout to provide more room around the devices. These devices are filled with anode and cathode materials, which are separated by the 2 µm to 3 µm posts/spaces between the two compartments. The battery materials must have no particles smaller than the size of the spaces or an electrical short will occur between the two compartments. The materials are dispensed as pastes using the MicroPen. We made anode (graphite powder) and cathode (lithium cobalt oxide [LCO]) pastes using a tri-block copolymer and solvents. We measured these pastes for particle size and viscosity. If a solvent wash was used to pre-wet the battery compartment, we successfully filled the batteries by using plastic nozzles that sealed the fill hole in the lid of the battery.

The cathode component is LCO. When Sandia initially synthesized this material, it was discarded on characterization of the particle size because particle size was smaller than the post spacing. We subsequently purchased commercial LCO and characterized it for particle size. The mean particle size was 20 µm. We synthesized a conductive tri-block copolymer (pBAAc) and mixed it with the LCO to act as a thickener, binder, and particle dispersant. We measured the viscosity of this mixture. We made a dispensable paste by dissolution in n-methylpyrrolidone (NMP) and polymethylmethacrylate (PMMA). The anode component is graphite in the form of acetylene black. This was also mixed with the pBAAc and NMP.

We initially attempted paste injection with a steel tip into the lightly oxidized Si cavities. This attempt resulted only in wetting the glass lid; the paste flowed out of the cavity without filling it. We changed the pen tip to plastic and enlarged it to seal the cavity opening, and we pre-wetted the Si cavity with NMP. The paste then was extruded into the cavity until it flowed out of the exit hole. The devices are awaiting electrolyte fill and testing.

If a solvent wash was used to pre-wet the battery compartment, we successfully filled the batteries by using plastic nozzles that sealed the fill hole in the lid of the battery.

10796

High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS

J. G. Fleming, S. Y. Lin, M. A. Polosky, S. S. Mani

Optical microelectromechanical systems (MEMS) are emerging as a key element of MEMS technology. However, despite the great interest in this area, the actual optical components employed are primitive: mirrors, simple lenses, and waveguides. In this project, Sandia is seeking to make a revolutionary advance in both MEMS and photonics through a combination of surface MEMS and the newly emerging field of photonic lattices.

Photonic lattices are the photonic analogues of semiconductors, in which the photonic bandgap (PBG) arises as the result of a periodic array of regions of high- and low-refractive index. As a general rule, the pitch of the lattice corresponds to roughly half the wavelength of light at midgap. The properties of these engineered materials rely only on the index of refraction of the materials and their arrangement. These engineered materials have a number of novel properties: they can act as extremely efficient mirrors, and they can be “doped” to form very high-Q optical cavities and highly efficient 90-degree-bend waveguides.

In many ways, it is natural to try to combine surface MEMS with photonic lattices. Silicon (Si), the basic structural material of MEMS, can also be used to form the lattice. Since the lattice properties rely on the repeat unit, which is small, small changes in dimension can result in large changes in optical properties of the lattice. Such small, well-defined displacements are readily obtained using MEMS processing. Potential applications include high-reflectivity mirrors, switching mirror arrays, waveguide switches, scanning spectrometers, and hollow waveguides.

We have continued to make considerable progress on this project. We fabricated and tested one-dimensional (1-D) switching structures and fabricated the first iteration of large dielectric stack mirrors integrated with surface MEMS. In both cases, we identified the major fabrication problem to be residual stress in the mirror stacks. We obtained useful switching cavity data; however, the large integrated mirror structure required a redesign. The redesign involves the

Sandia is seeking to make a revolutionary advance in both MEMS and photonics through a combination of surface MEMS and the newly emerging field of photonic lattices.

addition of a drumlike stiffening rim around the mirror, combined with a series of stiff springs between the rim and the mirror, which can deform to relax the mirror stress. This lot is complete, and we are evaluating it.

In the area of waveguiding in photonic lattice structures, we demonstrated efficient waveguiding in 2-D photonic lattice structures and are the first to demonstrate waveguiding in 3-D photonic lattices. Much of this work is summarized in the August 2001 *MRS Bulletin*. The 3-D waveguide appears on the front cover of the publication.

Although it was not in our original proposal, we fabricated hollow waveguides in which the 1-D mirror confines light in a hollow tube. These structures have been proposed sporadically by various groups since the sixties; however, they are difficult to fabricate, especially on a small scale. These devices can be thought of as one-photonic lattice mirrors (Bragg reflectors) that are formed into a tube. We successfully fabricated such structures, and the initial results indicate reasonable propagation losses and low coupling losses. These structures are structurally very similar to the channels being developed for bio-MEMS/microfluidics. There may be significant value to having a single platform, which can be used to channel both light and fluids.

In the area of waveguiding in photonic lattice structures, we demonstrated efficient waveguiding in 2-D photonic lattice structures and are the first to demonstrate waveguiding in 3-D photonic lattices.

Refereed

Fleming, J. G., and S. Y. Lin. 2001. "Waveguiding in MEMS-Compatible Three-Dimensional Silicon Photonic Lattices." *Proc. Transducers '01 EuroSensors XV* **2** (Munich, Germany, June): 1344–1347.

Lin, S. Y., J. G. Fleming, and E. Chow. 2001. "Two- and Three-Dimensional Photonic Crystals Built with VLSI Tools." *MRS Bulletin* **26**(8) (August): 627–631.

26518

II-V: Boron-Based Semiconductors for Optoelectronic Materials and Device Studies

J. F. Klem, E. D. Jones, N. A. Modine, K. Leung, S. R. Kurtz

We are continuing Sandia's award-winning work on vertical-cavity surface-emitting lasers (VCSELs). VCSELs offer high efficiency, excellent beam quality, and manufacturability. A VCSEL operating at 1.3 μm to 1.55 μm would revolutionize communication technology. Current promising materials are based on indium gallium/arsenic nitride (InGa/AsN) or gallium arsenic antimonide (GaAsSb), both grown on gallium arsenide (GaAs) substrates where the superior thermal conductivity and index contrast of aluminum gallium arsenide (AlGaAs) distributed-Bragg-reflector (DBR) mirrors can be employed. However, because of poor valence or conduction band alignments, these systems do not satisfy the needed temperature stability. We believe the gallium arsenic antimony nitride (GaAsSbN) material system is a superior candidate for the 1.3 μm to 1.55 μm semiconductor-laser system because GaAsSbN offers fewer difficulties with strain-layer growth and can span a range of bandgaps from 0.8 eV to 1.2 eV (1.55 μm to 1 μm). However, lack of basic information on this alloy restricts its use in semiconductor devices. Therefore, we will thoroughly investigate the GaAsSbN alloy system. The growth of this material for laser applications is completely new and has not been investigated. The material properties of this alloy are poorly characterized, and the material affords an excellent opportunity for Sandia's world-class expertise in growth and characterization of novel semiconductors. This investigation will also enable us to expand the understanding of dilute-nitride alloys beyond our existing world-class efforts in InGaAsN. For this project, we assembled a research team that has demonstrated leadership in the research and device community through publications, invited presentations, and record device performance in developing new semiconductor alloys.

Sandia is using local-density approximation (LDA) first-principles calculations to show that replacing 6.3 percent of the As atoms in GaAs with Sb decreases the bandgap of the artificially ordered alloy by 0.10 eV, while increasing the lattice constant by 0.5 percent. Similar calculations for indium gallium arsenide (InGaAs) with 6.3 percent In indicate that the

We are continuing Sandia's award-winning work on vertical-cavity surface-emitting lasers (VCSELs). VCSELs offer high efficiency, excellent beam quality, and manufacturability. A VCSEL operating at 1.3 μm to 1.55 μm would revolutionize communication technology. Current promising materials are based on indium gallium/arsenic nitride (InGa/AsN) or gallium arsenic antimonide (GaAsSb), both grown on gallium arsenide (GaAs) substrates where the superior thermal conductivity and index contrast of aluminum gallium arsenide (AlGaAs) distributed-Bragg-reflector (DBR) mirrors can be employed.

bandgap is reduced by 0.08 eV, while the lattice constant is increased by 0.4 percent. This confirmed that Sb should be an effective alternative to In as an additive to GaAsN used to further lower the bandgap while matching to the GaAs lattice constant.

We surpassed our theory milestone by theoretically studying clustering effects in gallium boron arsenide (GaBAs) and GaAsSb. The main conclusion of these calculations is that boron (B) atoms interact more strongly than Sb atoms, and as such, the B clustering causes a greater spread in the bandgap than for possible Sb clustering. This suggests that carrier localization due to clustering and/or composition fluctuations may be less of a problem in GaAsSb than in GaBAs.

We performed a study of growth conditions that led to nitrogen (N) incorporation into GaAsSb. Using x-ray diffraction (XRD) in conjunction with photoluminescence (PL), we found that use of TMSb (tri-methyl-antimonide) enabled us to incorporate N when DMHy (di-methyl-hydride) was added, while, if TESb (tri-ethyl-antimonide) were used as the Sb precursor, subsequent addition of DMHy produced no incorporation of N.

We experimentally studied the optical and electrical properties of XGaAsN (X=In, Sb, B) materials as a function of growth technique. To determine whether some of the properties of InGaAsN were caused by metal-organic chemical-vapor deposition (MOCVD)-related impurities (hydrogen, carbon, oxygen, and others) or growth conditions, (e.g., deficient group V flux), we performed comparative studies on InGaAsN grown by molecular-beam epitaxy (MBE) using a radio-frequency (RF) plasma, N source. Summarizing, we find that annealed MBE material quality is comparable to that of annealed, MOCVD-grown InGaAsN.

We surpassed our theory milestone by theoretically studying clustering effects in gallium boron arsenide (GaBAs) and GaAsSb. The main conclusion of these calculations is that boron (B) atoms interact more strongly than Sb atoms, and as such, the B clustering causes a greater spread in the bandgap than for possible Sb clustering. This suggests that carrier localization due to clustering and/or composition fluctuations may be less of a problem in GaAsSb than in GaBAs.

Refereed

Wixom, R. R., G. B. Stringfellow, and N. A. Modine. 2001. "Theory of Antimony-Induced Triple Period Ordering in GaInP." *Physical Review B, Rapid Communications*, accepted.

Other Communications

Klem, J. F., D. K. Serkland, and K. M. Geib. 2001. "High-Performance 1.3-Micron InGaAsN VCSELs." *Proc. IEEE Lasers and Electro-Optics Society 2001 Annual Meeting*, accepted.

Modine, N. A., E. D. Jones, A. A. Allerman, and S. R. Kurtz. 2001. "Understanding the GaAsN-Dilute Alloy." Paper presented to the Annual March Meeting of the American Physical Society, Seattle, WA, March.

26519

The Integration of Advanced Photonics and MEMS

J. G. Fleming, S. Y. Lin, C. T. Sullivan

Sandia is continuing to research microelectro-mechanical systems (MEMS). In spite of considerable interest, optical MEMS devices typically do not apply the range of possibilities associated with the wave nature of light. Optical MEMS devices usually consist of conceptually simple, but structurally complex, mechanical systems—really just movable mirrors. One interesting research area is that of ring resonators and waveguide couplers. Physically, ring resonators and waveguide couplers are relatively simple structures, but could act as narrow, high-efficiency band filters/drops and couplers. Difficulties in fabrication and switching have hindered research. Applying MEMS might resolve both difficulties. Moreover, the size scale of ring resonators and waveguide couplers is almost ideal for MEMS; small displacements give rise to large changes in optical properties.

Perhaps because of relatively recent rapid progress in fields that traditionally have not overlapped, the opportunity exists to combine elements of the two fields—advanced photonics and MEMS—to make significant technological advances. To advanced photonics, MEMS can offer a simple, manufacturable switch. On the other hand, advanced photonics offers the ability, not just to reflect light in free space, but also to confine light within waveguides where the light can be efficiently manipulated, switched, and filtered.

Existing MEMS technology does not realize this added functionality. With possibly the world's premier surface-MEMS capability, Sandia is in an excellent position to integrate advanced photonics and MEMS research. Sandia has world experts on advanced photonics as well as advanced sensor groups; the latter are one of the potential beneficiaries of MEMS advances. Furthermore, the devices of interest are relatively easy to fabricate, so we could expect significant and rapid progress with relatively little resource expenditure.

We made considerable progress on this project. We designed two-level test structures with waveguides and also devised resonator and coupler switches. We designed the structures to work with a parallel plate-type switch. The

With possibly the world's premier surface-MEMS capability, Sandia is in an excellent position to integrate advanced photonics and MEMS research. Sandia has world experts on advanced photonics as well as advanced sensor groups; the latter are one of the potential beneficiaries of MEMS advances.

narrow portion of the waveguide, in which the light couples to the resonator or coupler, is supported by a thicker strut. To aid coupling of light into the waveguide, the waveguide tapers out in stages from the 0.2μ wide active area to 6μ at the input side. The actuator and electrode portions are designed to have a gradient in fill factor to allow for chemical-mechanical-polishing (CMP) dishing to create a thin—approximately 0.5μ high—active region while retaining a thicker—approximately 1.5μ thick—input-coupling region. Silicon-nitride (SiN) posts support resonator rings off the substrate. We tested the design and process flow first in polysilicon (poly-Si), which is readily available and inexpensive. Using these test lots, we demonstrated the SiN-pillar formation, narrowing down the active portion of the waveguide, CMP dishing, polishing of end facets, release of the parts by supercritical carbon dioxide (CO_2) drying and electrical actuation. Parts using existing silicon-on-insulator (SOI) material have now been fabricated. We know single-crystalline Si has better optical properties than poly-Si; therefore, we will perform optical testing on these structures and not on the poly-Si structures. We have completed initial tests and observed wavelength dropping.

We tested the design and process flow first in polysilicon (poly-Si), which is readily available and inexpensive.

Using these test lots, we demonstrated the SiN-pillar formation, narrowing down the active portion of the waveguide, CMP dishing, polishing of end facets, release of the parts by supercritical carbon dioxide (CO_2) drying and electrical actuation.

32913

Aging Mechanisms in Dormant MEMS Structures

T. M. Mayer, B. C. Bunker, H. I. Kim, J. G. Kushmerick, D. R. Jennison

Thin-polymer films can render microelectromechanical systems (MEMS) surfaces hydrophobic, eliminating the catastrophic effects of capillary-driven interfacial adhesion. However, even treated surfaces can demonstrate strong adhesion and stiction after long-term environmental exposures resulting from aging and restructuring within the antistiction films. The physics and chemistry of interactions between micromachine components is poorly understood. Consequently, micromachine performance as a function of time and storage conditions (dormancy) cannot yet be predicted.

This project will elucidate the mechanisms of property evolution in hydrocarbon and fluorocarbon coatings with an emphasis on self-assembled monolayers (SAMs). Sandia will employ a suite of in situ experimental probes to determine (1) how the molecular structures and compositions of MEMS surfaces change with time and environmental exposure, (2) how these molecular changes influence the interfacial adhesion between well-defined, nanometer-scale, single-asperity contacts, and (3) whether models based on molecular and nanoscale experiments can be used to predict the evolving interactions between rough surfaces in model micromachine components. The result of this project will be the development of physical/chemical models for dormancy in MEMS that spans molecular-, nanometer-, and micron-length scales. The model will provide a framework to evaluate MEMS environmental and packaging requirements and to develop more robust MEMS designs and antistiction coatings. This project will provide experimental input to and validation of simulated interfacial phenomena for both molecular-scale dynamics of contacting surfaces and mechanical modeling of realistic MEMS structures.

We made significant progress in evaluating the stability of fluorinated alkylsilane films in humid environments. We measured adhesion and friction properties of a number of films as a function of humidity, defined long-term testing protocols for initial screening and detailed

The result of this project will be the development of physical/chemical models for dormancy in MEMS that spans molecular-, nanometer-, and micron-length scales. The model will provide a framework to evaluate MEMS environmental and packaging requirements and to develop more robust MEMS designs and antistiction coatings.

accelerated test conditions, and assembled the experimental and theoretical tools necessary to carry out the remainder of the first-year milestones. We concentrated on interactions of water vapor with monolayer organosilane films. We observed the degradation and sensitivity to water adsorption of films formed by vapor deposition from fluorinated octyltrichlorosilane (FOTS) and octyldimethylaminosilane (FOAS). We found that as-deposited FOTS films are unstable in humid environments and restructure to form small globules on the surface. This is accompanied by significant adsorption of water vapor and an irreversible increase in the frictional properties of the film. This behavior is caused by poor binding of the film to the substrate and can be mitigated by annealing to drive condensation reactions with surface hydroxyl groups.

Films formed from FOAS, however, are strongly bound to the surface after deposition at room temperature and show no evidence of degradation from humidity at room temperature. Statistical screening measurements of film degradation at more extreme exposure conditions are under way. We have also initiated computational models of silicon dioxide (SiO_2) surfaces and interaction of film head groups with this surface.

We concentrated on interactions of water vapor with monolayer organosilane films. We observed the degradation and sensitivity to water adsorption of films formed by vapor deposition from fluorinated octyltrichlorosilane (FOTS) and octyldimethylaminosilane (FOAS). We found that as-deposited FOTS films are unstable in humid environments and restructure to form small globules on the surface.

32923

MEMS in μ Fluid Channels

C. I. H. Ashby, M. P. de Boer, E. F. Hasselbrink, C. M. Matzke, D. Y. Sasaki, G. D. Bachand, M. Okandan

Microelectromechanical systems (MEMS) comprise a new class of devices that include various forms of sensors and actuators. Recent studies show that high-sensitivity MEMS-cantilever structures—appropriately functionalized with chemically sensitive films or biological receptors—are able to detect a wide range of chemicals, biomolecules, or even single bacterial cells. In this approach, cantilever deflection replaces optical-fluorescence detection, thereby eliminating complex chemical-tagging steps that are difficult to achieve with chip-based architectures. A key challenge to utilizing this new detection scheme is the incorporation of functionalized-MEMS structures within complex microfluid (μ fluid)-channel architectures. Achieving this integration is currently limited by the processing approaches used to seal lids on pre-etched μ fluid channels.

This project will combine Sandia's leading capabilities in MEMS processing with our newly developed low-temperature photolithographic method for fabricating μ fluid channels to construct MEMS-instrumented μ fluidic chips. Sandia will initially apply this approach to immunospecific detection of bacterial cells in collaboration with Cornell University. We will also explore in situ cantilevers as a new approach to directly monitor fluid transport within microchannels. Cantilever-based detectors offer aN (10^{-18})-force sensitivity that can be used to detect local flow rates and pressure gradients within μ fluidic channels. (Localized pressure and flow instruments are currently not available but are critical to optimizing μ fluidic architectures.) Initial work will focus on passive MEMS structures; later in the project we will extend this new integrated approach to incorporate actuated MEMS that can be used to direct or otherwise modify μ fluidic-flow environments.

A key challenge in this project is to fabricate leak-proof microchannels that can be loaded with liquid samples to undergo pressure-driven or electroosmotically driven flow past cantilevers. We successfully fabricated leak-proof microchannels over cantilevers. Our new dielectric microchannel-formation process employs continuous sequential deposition of layers of high-density-plasma

On-axis microcantilever encased in photoresist in preparation for microchannel formation by plasma deposition of dielectric films.

This project will combine Sandia's leading capabilities in MEMS processing with our newly developed low-temperature photolithographic method for fabricating μ fluid channels to construct MEMS-instrumented μ fluidic chips. Sandia will initially apply this approach to immunospecific detection of bacterial cells in collaboration with Cornell University. We will also explore in situ cantilevers as a new approach to directly monitor fluid transport within microchannels.

(HDP)–deposited silicon oxide (SiO_x) and silicon oxynitride (SiO_xN_y). The HDP SiO is similar to thermal silicon dioxide (SiO_2) and serves as an inner-channel surface that is inert toward the aqueous solutions that have been tested to date. The SiO_xN_y comprises the bulk of the electron cyclotron resonance (ECR) film because of its mechanical resiliency. The trilayer structure displays low stress (12 MPa) and is mechanically robust. The composite trilayer film ($\text{SiO}_x/\text{SiO}_x\text{N}_y/\text{SiO}_x$) is deposited over patterned photoresist that covers the cantilevers. The photoresist is removed by dissolution in acetone after the deposition, and Fourier-transform infrared (FTIR) analysis shows no photoresist residue after dissolution. We assembled a leak-proof interconnect for introducing fluids into the microchannel using capillary tubes attached to the open ends of the microchannels. We also successfully investigated Si rubber as a material for fabricating microchannels. We constructed microchannels over arrays of cantilevers fabricated at Sandia in the Materials Development Lab and over individual cantilevers fabricated at Cornell University that were positioned both parallel and perpendicular to the microchannel axis.

We monitored local flow rates and pressure gradients optically by incorporating cantilevers into the flow stream. Additionally, we monitored the response of protein-coated beads flowing past nanoporous media. Fluid flow across the cantilevers caused bending because of shear surface-stress on the top and sides of the cantilevers. Differential deflection of the microfabricated cantilevers allowed them to act as novel pressure-sensor devices for microfluidics. The microchannels also allowed for the behavior of protein-coated beads to be measured using pressure-based flow and electroosmotic flow. Using pressure-based flow, the beads flowed past the nanosized pores, “ignoring” their presence. In contrast, the proteins sought out the pores and became immobilized in them under electroosmosis, revealing that electric fields strongly influence protein-pore interaction.

We monitored local flow rates and pressure gradients optically by incorporating cantilevers into the flow stream. Additionally, we monitored the response of protein-coated beads flowing past nanoporous media.

Other Communications

Halle, K. J. 2001. “Biomolecule Detection and Separation Devices Based on Integrated Microfluidic Systems.” Paper presented to Symposium 2001, Albuquerque, NM, 9 August.

33602

Dispersive Photonics for Next-Generation Sensors and Microsystems

G. A. Vawter, M. J. Hafich, G. R. Hadley, S. Y. Lin, W. J. Zubrzycki, C. R. Alford, J. R. Wendt, D. W. Peters

Artificially structured photonic-bandgap (PBG) materials are commonly investigated for their unique ability to block and guide light. However, an exciting aspect of PBGs that has received little attention is the extremely high refractive-index distortion near the edge of the bandgap but within the range of frequencies capable of propagating within the PBG material. In fact, a recent suggestion is that a negative-refractive index may be realized with the correct PBG configuration.

Sandia proposes to investigate, both numerically and experimentally, the design and performance of such PBG materials intended to optimize the “distortion” of refractive index to realize new classes of photonic devices. For example, stripes of positive and negative refractive index form a planar “lens train” capable of guiding light much like a sequence of spherical lenses guides a Gaussian beam. Quadrants of positive and negative index will form a resonant optical cavity without mirrors or waveguides of any kind.

These optical properties of PBGs are expected to yield new and unexpected applications as understanding and fabrication technology develop in the next few years. Guided light might be focused to extremely high intensity and used to probe micro- or nanocavities filled with organic material in a chemical- or biological-sensor role, such as cytology. Or the refractive index of a fluid could be monitored with a very sensitive threshold wherein the strong index distortion effect would dramatically alter the optical properties of a waveguide or resonant cavity.

Sandia has created a new numerical model to compute the out-of-plane losses for a general class of photonic-crystal (PhC) waveguides formed by the superposition of a two-dimensional (2-D) PhC onto a slab-confinement structure. We use this model to calculate the propagation loss of a single-row-defect waveguide composed of hexagonal air holes etched into two different slab structures. We interpreted the results in terms of a simple coupled-mode-theory picture where loss results from coupling by the waveguide

Sandia has created a new numerical model to compute the out-of-plane losses for a general class of photonic-crystal (PhC) waveguides formed by the superposition of a two-dimensional (2-D) PhC onto a slab-confinement structure. We use this model to calculate the propagation loss of a single-row-defect waveguide composed of hexagonal air holes etched into two different slab structures.

corrugation between the fundamental mode and certain radiative slab modes. This picture in turn suggests that low-loss PhC waveguides should be possible through carefully engineering the radiation modes of the slab waveguide.

Planar PhC waveguides are of interest because of ease of fabrication and potential for highly dispersive behavior. Unfortunately, these waveguides are not without loss because of possible radiation out of the epitaxial plane. To be of interest in lightwave circuits, the losses must be demonstrated to be of an acceptable magnitude. Such devices have been fabricated and demonstrated to guide light, but accurate quantitative measurements of waveguide loss have rarely been reported. When such measurements are reported, the measurements are usually in the range of 15 to 100 cm^{-1} . Therefore, determining whether such waveguides can be designed and fabricated with significantly lower losses, (e.g., below 5 cm^{-1}) is of great importance.

In our method, the 3-D Helmholtz equation is solved by finite-difference (FD) techniques for the complex propagation constant of such a PhC waveguide. The results show significant detail of light propagation and sensitivity to the slab geometry. Results suggest both a simple coupled-mode-theory picture of the loss mechanism and possible low-loss designs.

For the present study, circles of 0.264 μm diameter arrayed in a hexagonal pattern with lattice constant $\lambda = 0.44 \mu\text{m}$ were assumed to be etched about 2 μm into two different common slab geometries using either aluminum oxide (Al_2O_3) or aluminum gallium arsenide (AlGaAs) lower-slab layers. The resulting computed power loss as a function of the normalized wavelength for both slab geometries shows a series of high-loss resonance peaks separated by lower-loss regions. The calculated *best* loss for the Al_2O_3 structure is 10 cm^{-1} over a 130 nm wavelength range and, for the AlGaAs structure, 40 cm^{-1} over a 70 nm wavelength range. Thus, the predicted propagation loss for the Al_2O_3 slab geometry is already close to being in an acceptable range for general utility and is considerably below measured values reported to date.

... the predicted propagation loss for the Al_2O_3 slab geometry is already close to being in an acceptable range for general utility and is considerably below measured values reported to date.

We were also successful in setting up frequency-domain models of PhC band structure. We use these models to calculate the direction of propagation of light within a 2-D or 3-D PhC as a function of the wavelength of light. Unlike common optical materials, only specific wavelengths of light will propagate across a PhC in any given direction. This characteristic is key to our interest in exploiting the dispersive nature of PhC for new and useful optical devices. With this model in place, we can now design PhCs in both frequency and spatial domains.

*We were also successful
in setting up frequency-domain
models of PhC band structure.*

Refereed

Hadley, G. R. 2001. "Out-of-Plane Losses of Line-Defect Photonic Crystal Waveguides." *IEEE Photonics Technology Letters*, accepted.

Emerging Threats

The Emerging Threats investment area addresses Sandia's national security mission by developing and applying high-impact responses to emerging security threats. Focus areas for research include the development of new national security capabilities for focused logistics, difficult targets, modeling and simulation, minimally manned warfare, and protection of the homeland. The research concentrates on innovations that enable the development of new system concepts and architectures projected for future operations in these areas. This goal is accomplished primarily through partnerships to broaden the application base for Sandia's mission-driven technologies.

The project "Surface Decontamination of Bacterial Protein Toxins by RF Power" is based on a radio-frequency electromagnetic (nonionizing radiation) method of decontamination. This method of decontamination requires no water, no drying, and no cleanup, and offers very fast inactivation of bacterial protein toxins. Further, it penetrates joints, bearings, and other difficult-to-reach surfaces. The photon energy is so low that photocurrents and electrostatic discharge effects are not produced so that sensitive equipment is not at risk. This method

operates by irreversible alteration of the conformation of biomacromolecules. It is energy efficient, leaves no residue, and may be applied either by scanning or all at once in a multimode cavity. One patent disclosure has been filed by this project.

10368

Surface Decontamination of Bacterial Protein Toxins by RF Power

R. P. Toth

This pilot project is investigating the feasibility of using radio-frequency (RF) power to decontaminate bacterial protein toxins dried onto various surfaces that mimic the surfaces found on vehicles, including surfaces coated with radar-absorbing material (RAM) and the thin, three-dimensional webs that simulate fabrics. In previous work, Sandia focused on developing RF equipment: a W-band extended interaction oscillator; a near-field-focused elliptical antenna; and a rectilinear scanner; and on using that equipment to inactivate a toxin surrogate, the neurotransmitter enzyme acetyl choline esterase. This year we continued to work with the procedures and assay methods previously developed, with the goal of successfully inactivating Kanagawa hemolysin toxin.

This year we applied RF equipment and developed process and analytical methodologies for toxin surrogates in previous work. We accomplished the following tasks:

- *Selection of the toxin.* Selection of the toxin was driven by considerations of safety, relevance to threat toxins, thermostability, and ease of use. The last point devolves to avoiding toxins on the Centers for Disease Control's (CDC's) Select Agent list and suitability of spectrophotometric assay. The other considerations are self-evident, with the possible exception of a requirement for thermostability. Thermostability is desirable because it provides a control for simple thermal denaturation while under RF exposure. The toxin selected for these studies was a hemolytic toxin from *Vibrio parahaemolyticus* that is named for the prefecture in Japan where it was characterized following episodes of food poisoning from fish. This bacterial protein toxin has a molecular weight of 42,000 and is composed of a dimer. It is thermostable (i.e., not inactivated by heating to 80°C to 90°C for 10 minutes); it is directly hemolytic; and it consists of 165 amino acid residues with a single disulfide bond. It is encoded by nine genes, only one of which is on a plasmid. It is a pore-forming toxin with a receptor that is Ca^{++} independent. In human erythrocytes, the hole produced in the cell membrane is about 2 nm. Injected intraperitoneally in microgram doses, it is toxic to mice due to cardiotoxicity.

This ... project is investigating the feasibility of using radio-frequency (RF) power to decontaminate bacterial protein toxins dried onto various surfaces that mimic the surfaces found on vehicles, including surfaces coated with radar-absorbing material (RAM) and the thin, three-dimensional webs that simulate fabrics.

- *Spectrophotometric assay of toxin activity/inactivation.* The assay method selected was based on spectrophotometric detection of hemoglobin (HGb) released through the pores formed in ovine erythrocyte suspensions. HGb standards (15, 30, 45 mg/l) were used to calibrate the spectrophotometer. The basic reactions employed were conversion of HGb to met-hemoglobin by ferricyanide, with further conversion via cyanide (Drabkin's Reagent) to form cyanmet-hemoglobin with a strong absorption peak at 530 to 550 nm.

- *Toxin application and recovery methods on a variety of surfaces.* The toxin was tested before and after drying on the target surface, as well as before and after RF exposure. Controls for autolysis of the erythrocyte suspension were performed before and after runs.

- *Estimation of drying and rehydration cycle effects.* As in the toxin surrogate studies in our previous work, drying did not produce the expected 2 log inactivation. On the contrary, drying of reconstituted Kanagawa hemolysin toxin produced less than 10 percent inactivation.

- *RF exposure effect on the primary activity of the selected bacterial protein toxin.* RF exposure inactivated the toxin. Standing-wave exposure of thin three-dimensional targets reduced the activity by about 40 percent. Tests on RAM materials produced half of that inactivation. We speculate that the reduced effect is due to the difficulty of establishing a standing-wave field on such a lossy material. The total RF power produced at W-band is only 60 W. It was coupled to the surface, to be decontaminated by a Cassegrain feed, elliptical reflector with a roughly 60 to 65 percent aperture efficiency. The antenna was about 20 inches in diameter and produced a diffraction-limited spot size (half-power, full-width) of 7 mm to 8 mm. The spot was scanned over the surface with a dwell time of about 100 μ sec. We tested both traveling-wave and standing-wave exposures.

These pilot-level results suggest that full-scale tests are warranted. These results also indicate how an operational system would be configured: (1) higher power (not the 60 W used here), (2) multilateral exposure with a high-Q (high-quality) chamber (not the scanned spot used here), and (3) dwell times in the order of a minute (not the one-tenth second used here). This sort of design would be useful to decontaminate reconnaissance vehicles such as remotely piloted vehicles flown through a toxin cloud.

These ... results suggest that full-scale tests are warranted. These results also indicate how an operational system would be configured: (1) higher power (not the 60 W used here), (2) multilateral exposure with a high-Q (high-quality) chamber (not the scanned spot used here), and (3) dwell times in the order of a minute (not the one-tenth second used here). This sort of design would be useful to decontaminate reconnaissance vehicles such as remotely piloted vehicles flown through a toxin cloud.

10369

Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures

S. M. Cameron, T. S. Luk, A. C. Bernstein

Recent experimental observations of stable, self-guided light propagation of gigawatt peak power femtosecond optical pulses through the atmosphere over long distances (about 100 m) without diffraction divergence has important ramifications for laser-beam transport, directed-energy (DE) weapons, and optical remote sensing. Stabilization of the laser channel is attributed to a dynamic balance between the Kerr self-focusing nonlinearity in air and the combined effects of normal diffraction and refractive defocusing from the induced ionization column. Conical white-light emission associated with the propagating light channel can be used for multispectral remote sensing over long distances. By using spatial adaptive control, temporal pulse shaping, and dispersion compensation to manipulate onset and stability of the self-focused beam-forming process, optical energy can be concentrated in a prescribed focal volume at predetermined range for remote sensing at high field intensity.

In previous work, Sandia characterized spectral brightness, spatial distribution, and angular divergence of conical white-light emission produced by nonlinear propagation of 800 nm femtosecond pulses in air. We also measured parametric studies of how laser energy and initial chirp condition affect the spectral brightness of the conical emission. We identified optical processes responsible to key spectral features in the white-light spectral distribution and also made spectral brightness and angular divergence comparisons with the white-light generation produced in water. The spectral brightness measurements covered the spectral ranges from 0.4 μm to 1.6 μm . We made similar measurements on the continuum generation produced by nonlinear propagation in air, using 400 nm femtosecond pulses. By comparing the characteristics of these two wavelengths, we determined key mechanisms responsible for the white-light continuum generation. To determine fundamental nonlinear parameters and limitations in our numerical model, we developed our numerical simulation

... Sandia characterized spectral brightness, spatial distribution, and angular divergence of conical white-light emission produced by nonlinear propagation of 800 nm femtosecond pulses in air. We also measured parametric studies of how laser energy and initial chirp condition affect the spectral brightness of the conical emission. We identified optical processes responsible to key spectral features in the white-light spectral distribution and also made spectral brightness and angular divergence comparisons with the white-light generation produced in water.

effort and compared the experimental data on the spatial and temporal collapse of the femtosecond pulses. Combining the nonlinear propagation model and experimental result allowed us to develop an accurate model to predict the achievable intensity at range.

10370

HPM Vulnerability Assessment and Tests*L. D. Bacon, G. J. Denison*

High-power microwave (HPM) technology has matured to the point where practical electromagnetic (EM) weapons are becoming technically feasible. One opportunity for this type of directed energy (DE) is a terrorist attack on our infrastructure. This project concentrates on only one type of system—hand-held radios.

The major initial challenges are modeling and simulation, and the development of a source designed for close-range, in-chamber effects research on target electronics. Sandia is also assessing electronic system susceptibilities to HPM attacks causing system upset for one specific system, with the view that this process can be applied to other more complex systems and scenarios. We are examining (1) possible entry path(s) of EM energy into a critical system, and (2) interactions with electronic circuits that may cause upset or latchup leading to damage and the EM parameter set (frequency, power level, pulsewidth, repetition rate, etc.) that exacerbates these tendencies.

To better understand an HPM system's vulnerability at the component level, we tested specific circuit elements for damage. Once we determine HPM system requirements, we will carry out validation tests and work on critical components of an HPM system. Our work consists of three aspects: (1) vulnerability assessment to determine HPM transmitter parameters, (2) development of an HPM system, and (3) modeling and simulation.

Our goals are to

- Determine specific target systems and perform a vulnerability assessment.
- Build a nonfrequency-tunable HPM transmitter.
- Design a frequency-tunable HPM system.
- Conduct HPM tests of the radio.
- Do tests aimed at a comparison of the vulnerability assessment and actual effects.

Two major efforts—computer modeling and simulation of effects, and an experimental effort that included testing targets for effects—were required to meet current objectives. We added new systems to our test matrix, which now includes a variety of radio types. Our specific tasks were to

To better understand an HPM system's vulnerability at the component level, we tested specific circuit elements for damage. Once we determine HPM system requirements, we will carry out validation tests and work on critical components of an HPM system. Our work consists of three aspects: (1) vulnerability assessment to determine HPM transmitter parameters, (2) development of an HPM system, and (3) modeling and simulation.

(1) Complete HPM tests and compare those results with code results. The tests were carried out in different frequency bands for two different types of assets in transmit or receive. We tested a variety of radios in a test-cell chamber and a mode-stirred chamber.

(2) Model and simulate effects at 1 GHz and higher frequencies (narrowband). The modeling was extended to include chaotic/nonlinear effects.

*We tested a variety of radios in
a test-cell chamber and a
mode-stirred chamber.*

10377

Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay

C. J. Brinker, C. S. Ashley, B. G. Hance, J. S. Schoeniger, A. K. Singh

Trace chemical sensing of nitroaromatic explosives in soil can provide useful information for the detection of buried landmines or other unexploded ordnance, especially when combined with complementary information from physical detection methods. Environmental fate and transport studies of explosives in soil indicate that 2,4,6-trinitrotoluene (TNT) and similar products such as dinitrotoluene (DNT) are major contributors to the trace chemical signature emanating from buried landmines. Chemical analysis methods under development have great potential to detect landmines or to rapidly classify electromagnetically detected anomalies as landmines versus landmine-like objects. However, these chemical methods are currently confined to point sensors.

Sandia produced prototype granular sensor particles that are designed both to preconcentrate signature chemicals from the environment and to provide easily detectable changes in visible fluorescence when exposed to nitroaromatic explosives. In contrast to existing chemical methods confined to point sensors, Sandia's method can remotely determine the presence of nitroaromatic explosives in surface soil, utilizing a novel distributed granular sensor approach in combination with ultraviolet visible (UV-vis) fluorescence light detection and ranging (LIDAR) technology. We produced prototype sensor particles that combine sample preconcentration, explosives sensing, signal amplification, and optical signal output functions. These particles can be sprayed onto soil areas that are suspected of explosives contamination. Using these sensor particles in conjunction with our fluorescence LIDAR spectrometer system, we demonstrated the detection of 1 part per million TNT in soil from 2-inch-diameter natural soil targets at a standoff range of 0.5 km. In addition, we used a laboratory fluorescence imaging system to demonstrate spatially resolved detection of TNT in soil. While our prototype tests primarily have used TNT, we demonstrated the fluorescent polymer used in formulation of our sensor particles to be sensitive to 2,4-DNT as well. This is an

Sandia produced prototype granular sensor particles that are designed both to preconcentrate signature chemicals from the environment and to provide easily detectable changes in visible fluorescence when exposed to nitroaromatic explosives.

important signature compound for trace chemical detection of buried landmines.

Sensor particles are made by depositing appropriate fluorescent materials from solvent solution into carrier particles. The fluorescent optical response of the particles to TNT and DNT is provided by doping the particles with a small amount of a fluorescent polymer (C14 polymer, supplied by Nomadics, Inc.). By design, the fluorescence emission spectrum of the distributed particles is strongly affected by absorption of nitroaromatic explosives from the surrounding environment.

C14 exhibits a very sensitive amplified response to nitroaromatic explosives due to oxidative quenching of the highly delocalized excited state of the polymer. C14 exhibits an absorption maximum at about 430 nm, with emission maximum at about 460 nm. A second fluorescent polymer, p-bis(o-methylstyryl)-benzene (MSB), which absorbs at about 360 nm, exhibits multiple emissions at 400 to 420 nm (near the absorption maximum for C14), and has no response to nitroaromatic compounds, was included in the particles to serve both as an internal standard and as an optical pump for C14. We prepared TNT- and DNT-doped soil samples by sieving and drying natural soil. We used analytical-grade DNT or recrystallized military-grade TNT to prepare samples doped to a concentration of 10 mg/kg or 100 mg/kg, respectively. We prepared lower concentrations by dilution with clean soil. We prepared hockey puck samples containing 10 g of soil sprinkled with about 1 mg/cm² particles and covered with a quartz window.

We used a laboratory fluorescence spectrometer or remotely used a portable LIDAR laboratory to obtain spectral measurements. Using about 1 mg/cm² coverage of the sensor particles on natural soil, we observed significant spectral changes due to TNT concentrations in the parts-per-million range (a milligram TNT per gram of soil) on 2-inch-diameter targets at a standoff distance of 0.5 km. We also used these field measurements to validate calculations of fluorescent signal/noise for the granular sensor particles, as a function of several variables, including particle and receiver characteristics, standoff range, pump laser characteristics, and particle coverage.

We used a laboratory fluorescence spectrometer or remotely used a portable LIDAR laboratory to obtain spectral measurements. Using about 1 mg/cm² coverage of the sensor particles on natural soil, we observed significant spectral changes due to TNT concentrations in the parts-per-million range (a milligram TNT per gram of soil) on 2-inch-diameter targets at a standoff distance of 0.5 km.

Refereed

Simonson, R. J., B. G. Hance, R. I. Schmitt, M. S. Johnson, and P. J. Hargis. 2001. "Remote Detection of Nitroaromatic Explosives in Soil Using Distributed Sensor Particles." *Detection and Remediation Technologies for Mines and Mine-like Targets VI, Proc. Society of Photooptical Instrumentation Engineers* **4394** (Bellingham, WA): 104–114.

10379

Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments

P. C. Bennett, T. S. Gladwell, M. J. McDonald

Sandia has developed the science and technology base required to revolutionize the remote manipulation of hazardous materials in difficult, unstructured environments. Dexterous remote manipulation is required by the Department of Energy (DOE) and other organizations to safely and quickly respond to increasing numbers of encounters with unexploded ordnance (UXO), such as munitions, mines, and improvised devices left by terrorists. The science base created at Sandia includes advances in geometric reasoning, sensor fusion and model-building, automated planning, and task-based reasoning. These advances are motivated by the need to reduce risk to explosive ordnance disposal (EOD) and other field technicians, who are frustrated by the slow, unsafe, primitive remote manipulation capabilities available on the market today.

The engineering motivations for constructing such systems are the need to determine how laboratory technologies such as sensing and control perform when actually fielded, and how they are best integrated. The first motivation advances the science of component technologies by establishing limits on their practical use and identifying flaws in accepted problem definitions. The second motivation also establishes limits on component technologies and allows them to successfully coexist with one another. This knowledge increases successful transition of technologies to the field.

The system that Sandia built was originally envisioned as teleoperated, but now includes significant autonomy to lessen operator burden. Autonomy will be in the form of automatic planning of manipulator motions required to manipulate objects or perform operations at locations designated by the operator. Autonomy requires high-bandwidth force control responses that enable safe contact operations. With the manipulator mounted on a mobile vehicle, the system is capable of performing tasks such as opening unlocked doors and going through them, deploying inspection devices, and unscrewing fuses autonomously under task-level direction of an operator.

Sandia has developed the science and technology base required to revolutionize the remote manipulation of hazardous materials in difficult, unstructured environments.

The system that Sandia built was originally envisioned as teleoperated, but now includes significant autonomy to lessen operator burden.

Increased use of computer-based motion planning and sensor-based control allowed us to integrate advanced capabilities that we had not originally planned. We were able to move from teleoperation to assisted (telerobotic) and automated operations, which substantially reduced operator burden during task execution. Examples of this include automated stowage and deployment of manipulators regardless of starting point, replay and rewind of the last movements, automated camera tracking of the tool tip, and visual targeting implementation.

Visual targeting enabled the operator to draw on a camera view, designate points and lines, and command robot actions based on the designated items. The operator could designate objects such as a pipe bomb, provide position, orientation, and length information, and then with a push of a button, command the system to pick up the pipe or to properly align a weapon to destroy it. We incorporated work from others to enable the interface, and we developed automated path-planning algorithms to enable the button command.

We implemented automated camera tracking of the remote system tool tip after observing that up to 40 percent of the time required to execute an operation was spent adjusting camera views. Operators can now select this option by pushing a graphical user interface (GUI) button that initiates a kinematic tracking of the tool tip and automatic aiming of the camera's pan-tilt unit.

We implemented a reachability check on the system to determine if an operator-selected action could be executed on the designated object. Predicated on the kinematic knowledge of the robot's capabilities and the input available from visual targeting, the system could determine if the robot could reach the object with the required orientation; if not, robot motion would not execute, and the operator would be notified of the issue.

We implemented visual three-dimensional feedback for preview and augmented view of operations, which eliminated the need for frequent camera adjustments to reascertain the current manipulator configuration. In addition, individual joints in the graphical representation turned red when joint limits were reached, thus communicating to the operator the reason the robot had ceased movement even though a command to move was still being sent.

The operator could designate objects such as a pipe bomb, provide position, orientation, and length information, and then with a push of a button, command the system to pick up the pipe or to properly align a weapon to destroy it. We incorporated work from others to enable the interface, and we developed automated path-planning algorithms to enable the button command.

Successful demonstrations based on user-community interactions included the following:

- We recovered improvised explosive devices from building and car situations and placed them in mock containment vessels for removal from the vicinity.
- We aligned disruption weapons with target devices, and users verified proper placement.
- We emplaced x-ray equipment, made x-ray recordings, and recovered the recordings in approximately 4 minutes without direct human intervention, which is approximately five times faster than baseline capability.
- We opened car and building doors to access devices placed in indoor and outdoor scenarios, then conducted confined space searches, including access to glove boxes.
- We accomplished computer-assisted key insertion and turning to gain access to car trunks and doors.
- We consistently carried out automated and computer-assisted tool changing in the course of all demonstrations.

Interactions with the user community were extensive during the development and implementation of the above technologies. Community participants included DOE/National Nuclear Security Administration (NNSA) emergency response personnel, the interagency counterterrorism Technical Support Working Group, Albuquerque Police Department Bomb Squad, international counterterrorist operators, and the U.S. Armed Forces.

Other Communications

Harrigan, R. W., and P. C. Bennett. 2001. "Making Remote Manipulators Easy to Use." *AeroSense 2001: Unmanned Ground Systems III* 4364 (Orlando, FL, April).

We recovered improvised explosive devices from building and car situations and placed them in mock containment vessels for removal from the vicinity.

10380

Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays

M. B. E. Boslough, L. C. Marron, R. J. Pryor

Among the greatest practical challenges to the realization of robotic swarms is the relative lack of rapid mobility and the limited power supply associated with currently available autonomous devices. Unmanned airborne vehicles (UAVs) are particularly constrained because they must consume significant power just to stay aloft. This constraint limits the potential application of UAV swarms unless the individual vehicles can derive locomotive energy from the local environment. It is, however, theoretically possible (as has been demonstrated with support from flight data collected in this project) for a robotic glider to remain aloft and navigate by dynamic soaring in the shear boundary layer near the Earth's surface, or in separation flow on the leeward side of a topographic high.

*Dynamic soaring was first described in the nineteenth century. It is the means by which many species of albatross cover vast distances of the ocean without flapping their wings. Moreover, the flight cycle required to derive energy from the wind velocity gradient is a circuitous pattern of climbing upwind, turning and diving downwind, and turning back upwind. This cycle allows vast areas of the sea to be scanned with no net expenditure of flight energy. The Wandering Albatross, *Diomedea exulans*, has been observed to follow ships for several days in a row.*

The same method that optimizes foraging for seabirds can be applied to search, tracking, sentry, and monitoring problems. With communication links, a collective intelligence can be designed that improves on nature.

We modified our goals significantly from our original proposal to focus on software development and flight simulations at the expense of hardware and actual flight tests. We developed a generalized genetic programming tool called YGP and fully integrated it with a flight behavior simulation tool called Birdbox. We also developed a version of FlightGear with which we can reproduce and display flight test data as well as display evolved behaviors.

- YGP is a generalized version of a genetic programming tool. In YGP, the data structure of the tree that

We developed a generalized genetic programming tool called YGP and fully integrated it with a flight behavior simulation tool called Birdbox. We also developed a version of FlightGear with which we can reproduce and display flight test data as well as display evolved behaviors. ... With communication links, a collective intelligence can be designed that improves on nature.

contains the flight-control algorithm consists of multiple arrays that keep track of state variables (for flight simulation), calculated variables (for high-level situational awareness and decisions), calculated integers (for policy table flags), registers (genetically calculated values), and pointers (for multiple decision trees that depend on policy flags). Array dimensions are determined at compile time and depend on the evaluation function, the number of degrees of freedom (DOFs) of the flight vehicle, and whether the flight space is discrete or continuous. By generalizing the genetic programming, behaviors for any environmental rules can be developed with the same code, from the most basic (4 DOFs, discrete space, simple flight rules, fixed lift zone) to the most advanced (6 DOFs, continuous space, full aerodynamics, turbulent boundary layer). We used the most basic example as a benchmark because it runs much faster than a realistic simulation. YGP demonstrated the fastest convergence that approaches the best solution we have ever found for the benchmark problem. We also developed a method of storing behaviors so that they can be written and read across various computational platforms. These trees are compact, with about a one-kilobyte storage requirement per behavior. Finally, YGP also has a generalized capability for communication among vehicles, so that collective behavior and swarming can be developed.

- Birdbox is a cross-platform flight simulator that we developed primarily as a research tool. We used OpenGL, Open GL Utility Toolkit (GLUT), and Open GL User Interface (GLUI) libraries so that the simulator can be run in non-Windows computer environments. Birdbox allows a researcher to visually observe simulated gliders exhibiting flight behaviors evolved with YGP. The user can modify the following elements: camera rotation, camera translation, number of birds, size of birds, texture mapping, water animation, and screen update rate. GUI buttons provide the underlying functionality by allowing the user to load a new behavior file and switch to other environments. The data window displays time and instantaneous information about the bird state, such as distance, altitude, and current register. Birds are rendered as paper airplanes, each with its own color and shadow on the ground to locate the bird in the XY plane. The same evaluation function subroutines that are used in YGP are used in Birdbox, along with the same data structure and traversal function for the decision trees that are evolved with YGP.

We used the most basic example as a benchmark because it runs much faster than a realistic simulation. YGP demonstrated the fastest convergence that approaches the best solution we have ever found for the benchmark problem.

- We adapted FlightGear as a flight visualization tool for demonstrations. FlightGear is an open-source flight simulator that incorporates LaRCsim, a NASA Langley Research Center product that provides a full 6 DOF flight model. We developed a new flight model inherited from existing flight model C++ objects. The new model, FDMAIbaltross, enables the user to display flight paths developed by any function capable of returning positions in a Cartesian space, thereby allowing any evolved flight trajectory to be displayed. FlightGear also holds promise as a full aerodynamics simulation tool that can be combined with YGP. Most major geographic features such as bodies of water, mountain ranges, and valleys can be displayed using FlightGear, giving researchers the ability to visualize the performance of a particular flight behavior in various locations.

We adapted FlightGear as a flight visualization tool for demonstrations. FlightGear is an open-source flight simulator that incorporates LaRCsim, a NASA Langley Research Center product that provides a full 6 DOF flight model.

10381

Miniature UV Fluorescence–Based Biological Agent Sensor

K. L. Schroder, R. M. Biefeld, J. Han, P. J. Hargis, Jr., R. F. McCoy, Jr., A. J. Fischer

To date, efforts in developing nitride-based emitters have focused mostly on visible (blue and green) light emission using indium gallium nitride (InGaN) as the active region. Ultraviolet (UV) applications using gallium nitride (GaN) and aluminum gallium nitride (AlGaN) have remained relatively unexplored. Sandia aims to fabricate a UV light-emitting diode (LED) in a recently established metal-organic chemical vapor deposition (MOCVD) facility that has demonstrated the growth of GaN materials with structural, optical, and electrical quality comparable to the best reported thus far.

This project will develop a miniaturized UV fluorescence biosensor based on UV LED and miniature spectrometer technologies that Sandia is currently developing. Sandia will evaluate the performance of an LED operating at 360 nm in biofluorescence measurements. The LED is based on the AlGaN family, which has direct optical bandgaps from 364 nm GaN to 200 nm (aluminum nitride [AlN]). The wide wavelength range of these materials makes them attractive as compact UV light sources.

Our specific goals are (1) to develop novel UV LED light sources, (2) to demonstrate their usefulness for the detection of biomaterials, (3) to develop a miniature spectrometer for biofluorescence measurements, and (4) to culminate in the design for a prototype instrument that can be used for demonstration measurements.

• **LED development.** Considerable work has been done on the growth and processing of GaN–based UV LEDs. Initial studies focused on the internal structure of the LED active region (e.g., quantum-well [QW] width, barrier width, doping levels), but did not result in a significant increase in LED performance. Improvements in the low-temperature buffer layer, where the GaN film initially nucleates on the sapphire substrate, have dramatically reduced the number of threading dislocations in our GaN material. Threading dislocations are known to be nonradiative recombination centers for GaN grown on sapphire substrates and to reduce the overall efficiency of LEDs. These improvements in the GaN

This project will develop a miniaturized UV fluorescence biosensor based on UV LED and miniature spectrometer technologies that Sandia is currently developing. Sandia will evaluate the performance of an LED operating at 360 nm in biofluorescence measurements.

nucleation layer resulted in a 15 times increase in LED performance, with output powers as high as 1.3 mW at 20 mA for devices operating at 390 nm. Similar improvements can be expected as for LEDs grown with GaN/AlGaIn QWs for emission at 350 nm.

LEDs have also been grown on low-defect-density cantilever epitaxy (CE). CE is a lateral overgrowth technique pioneered at Sandia that has been shown to significantly reduce the number of threading dislocations and, hence, to improve the optical efficiency of light emitters grown on GaN. Our first LED wafer grown on CE substrates resulted in 1.3 mW of output power at 20 mA for a device operating at 390 nm. This result is very encouraging since we know that our CE wafers are not optimized. We observed certain areas across one LED device to be extremely bright, while other areas did not emit light. Therefore, with improvements in our CE substrates, we expect to produce LEDs that are much brighter than those possible on planar sapphire substrates. CE substrates will be particularly important for shorter-wavelength LEDs where reductions in threading dislocation density have been shown to dramatically improve device efficiency.

- *Spectrometer and detector development.* Our efforts focused on fiber coupling of gateable detector arrays suitable to commercially available miniature spectrometers. We acquired several miniature spectrometers for evaluation. None of these commercial units is available off-the-shelf with detectors suitable for temporally gated biofluorescence measurements. We selected two types of gateable detectors for evaluation. The first is an array of individual miniature photomultiplier tubes, and the second is an avalanche photodiode array. Eventually, between 16 and 32 detector elements would be required to spectrally resolve the fluorescence signatures. For evaluation purposes, we acquired four element arrays. We designed a fiber-coupling scheme for coupling of the spectrometer output to the detectors and fabricated fiber-coupling hardware.

- *Prototype sensor system design and biofluorescence measurements.* We created a design for a prototype sensor using a UV LED and miniature spectrometer. For this design, a sample of bioorganisms in solution is placed into a cuvette that is then placed in the prototype sensor. The sample is illuminated by the LED, and fluorescence is detected by the spectrometer. The current configuration uses a Zeiss miniature monolithic spectrometer with a charge-coupled device (CCD)

LEDs have also been grown on low-defect-density cantilever epitaxy (CE). CE is a lateral overgrowth technique pioneered at Sandia that has been shown to significantly reduce the number of threading dislocations and, hence, to improve the optical efficiency of light emitters grown on GaN. Our first LED wafer grown on CE substrates resulted in 1.3 mW of output power at 20 mA for a device operating at 390 nm.

detector, but the new spectrometer and fiber-coupled detectors can be readily incorporated. New biofluorescence measurements have not yet been conducted with the prototype.

10720

Proton Beam Directed-Energy Weapon

M. G. Mazarakis, T. J. Renk

One of the most pressing U.S. emerging threats is the MACH 2 sea-skimming missiles that are expected to be widely available to opposing naval and shore offensive forces. The time available from detection to destruction is only 10–20 sec. A rapid-response, total-lethality, flexible-aiming and -firing defensive system is essential for continued protection of the U.S. naval fleets, and carrier battle groups, in particular. Sandia is developing a concept design of a new type of directed-energy (DE) weapon based on high-energy particle beams. Not only could it be capable of destroying the missile, but also of neutralizing any biological or chemical agent before destruction. Partial beams, propagating with velocities close to the speed of light, could deliver onto the target lethal energy. Multiple pulses could easily destroy a target at a required distance. The first application for evaluation is that of terminal defense for naval vessels such as the aircraft carrier. A longer-term, longer-range possibility is for theater missile and ballistic missile defense, which is also being evaluated in the simulation and modeling work.

This project successfully addressed atmospheric propagation and target lethality. We defined the technical parameters for system performance expectations and did not identify any “show-stoppers.” We delineated accelerator requirements and compared them with various accelerator concepts. We developed a roadmap for future technology development.

Our study focused on several key issues and technical parameters for this weapons concept, with the following conclusions:

(1) A speed-of-light interceptor could give dramatic improvement in targeting response time, rapid redirection, and retargeting for defense against a high-velocity sea-skimming missile.

(2) This weapon would provide a unique and cost-effective defense capability for protection of U.S. Navy

This project successfully addressed atmospheric propagation and target lethality. We defined the technical parameters for system performance expectations and did not identify any “show-stoppers.” We delineated accelerator requirements and compared them with various accelerator concepts. We developed a roadmap for future technology development.

carriers against present and future high-speed (MACH 2) antimissile attack.

(3) The proposed proton-beam weapon has good penetration and lethality potential against the typical components and systems carried in the nose of an anti-ship missile.

(4) Further development of intense beam-accelerator technology is needed to address these challenging but feasible requirements.

10727

Micro-High-G Acceleration Recorder

D. A. Hoke, R. G. Lundgren, V. I. Bateman, R. R. Lockhart, E. A. Henry, J. J. Allen, F. J. Peter, J. W. Lantz

All recent attempts to collect projectile acceleration data at impact velocities greater than 3500 feet/sec have failed. These data are becoming increasingly important to the hard and deeply buried target community in order to determine high-velocity penetration dynamics, multilayered target characteristics, and survivability of the fuze, explosives, and penetrator. This project will develop, either internally at Sandia or using a commercial supplier, a suitable acceleration transducer plus the associated miniaturized electronics to process and store the acceleration data.

This project initially was to use Sandia's integrated microelectromechanical systems (IMEMS); however, that fabrication process was dropped. Our current approach is to develop a transducer separate from the signal-processing electronics. Important transducer attributes are small size, low power consumption, and good cross-axis signal rejection. Power consumption correlates strongly with overall electronics volume because a larger energy-storage device must be used. We will evaluate the transducer developed both in laboratory tests and as part of a complete acceleration recorder used to instrument an earth-penetrator test.

We analyzed the capacitance processing electronic device needed to translate the MEMS-based accelerometer output and obtained results that indicated that the device could not provide adequate dynamic range and that its power consumption would exceed our goals. This discovery effectively eliminates the current MEMS accelerometer design.

We conducted a fundamental review of all potential physical phenomena that we could use to create an accelerometer with the characteristics needed, without limiting the transducer to a MEMS component. The most likely device would be piezoelectric, piezoresistive, or capacitive. We identified manufacturers of each transducer type, but none was producing components with the needed characteristics. We have begun scheduling visits to these manufacturers to discuss modifications that would make their devices meet our needs. In parallel, we have begun design considerations for a revised MEMS device to be produced at Sandia. The technology to be

All recent attempts to collect projectile acceleration data at impact velocities greater than 3500 feet/sec have failed.

These data are becoming increasingly important to the hard and deeply buried target community in order to determine high-velocity penetration dynamics, multilayered target characteristics, and survivability of the fuze, explosives, and penetrator.

developed, silicon (Si) on glass (SOG), shows promise because of the relative ease of connecting the sense mass (etched bulk Si) to the electronics.

We developed preliminary electronic schematics for an integrated acceleration recorder with an assumed diameter of about 1 cm. Completion of the recorder will be held until an accelerometer is chosen. We also designed a preliminary mechanical design for the acceleration recorder housing. We began work on a testing equipment configuration for the acceleration recorder electronics to test functionality and calibrate the recorder.

We also designed a preliminary mechanical design for the acceleration recorder housing.

10736

Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation

C. L. Smithpeter, D. V. Campbell, J. T. Feddema, S. K. Dunlap, R. O. Nellums, T. M. Gurrieri, A. D. Niese, K. O. Wessendorf

In autonomous navigation, needs exist for sensing position, generating a terrain map, and obstacle assessment/avoidance from a moving platform. The three-dimensional (3-D) image data from a conventional laser radar (LADAR) is a possible solution for the sensing need; however, current LADAR sensors are limited by cost, complexity, required laser power, and sensitivity to motion. Other 3-D image data applications such as precision munitions guidance, physical security, target surveillance, and docking of spacecraft have similar concerns with respect to current LADAR technology.

Sandia aims to address the limitations of LADAR sensors by developing a miniature LADAR architecture that is insensitive to platform or image scene motion. The ultimate objective is to reduce the LADAR receiver to a focal plane array similar to a charge-coupled device (CCD) camera. In addition, we are seeking innovative techniques to reduce the required laser illumination power, which currently dominates system cost and power requirements. Our primary focus is on designing the integrated circuitry (IC) in each pixel of the array to sense laser time-of-flight (TOF) range with nanosecond accuracy. Additional circuit design objectives are to reject solar background and electronic gating on a 100 ns timescale. We are fabricating two versions of the IC array for laboratory testing.

We completed the design of an 8 x 16 flash range array and submitted it for fabrication. The components of the pixel include a low-noise pre-amplifier, differential modulator, and time gating. Previous research and our analysis predict that amplifying the signal as close to the photodiode as possible will achieve optimal sensitivity. The noise of this pre-amplifier typically dominates signal to noise and the corresponding sensitivity. Improving sensitivity reduces the required laser energy per image. Based on this analysis, we designed an integrating charge amplifier with 20 times gain and low-noise characteristics.

Sandia aims to address the limitations of LADAR sensors by developing a miniature LADAR architecture that is insensitive to platform or image scene motion. The ultimate objective is to reduce the LADAR receiver to a focal plane array similar to a charge-coupled device (CCD) camera. In addition, we are seeking innovative techniques to reduce the required laser illumination power, which currently dominates system cost and power requirements. Our primary focus is on designing the integrated circuitry (IC) in each pixel of the array to sense laser time-of-flight (TOF) range with nanosecond accuracy.

Our analysis found the second source of excess noise is bias (steady-state) current running through the modulator amplifier. This current also limits the dynamic range of the sensor. We developed a differential modulator to eliminate the bias currents, thereby reducing noise and improving dynamic range.

LADARs typically use time gating on the 100 ns scale to reject unwanted light. Switching the analog circuitry of the pixel in the 100 ns time scale is a challenge. The gating issues are induced noise, signal loss, and unpredictable bias currents. Our solution is to use a balanced or differential switching to reduce the effect of gating on the range measurement.

We developed a differential modulator to eliminate the bias currents, thereby reducing noise and improving dynamic range.

10752

Distributed Reconfigurable Homogeneous Microrobotic Systems

D. M. Hensinger, J. T. Feddema, S. E. Eskridge

A distributed reconfigurable microrobotic system is a collection of unlimited numbers of distributed small, homogeneous robots designed to autonomously organize and reorganize to achieve mission-specified geometric shapes and functions. The concept of a homogeneous system, which is similar to the cell structure of biological organisms, has fundamental applications and advantages (mass-producible/low-cost, fault tolerant, self-maintainable/repairable) in the design of multimodal, complex artifacts. Such systems can evolve into many different shapes (e.g., manipulators, antennas, buildings, and even animals) and perform a variety of functions (e.g., crawl, walk, and swim). If some part of the system malfunctions, it can still maintain total function through automatic reconfiguration. For example, a system could piggyback into space on the space shuttle in some contorted form to maximize the shuttle's payload. Upon arrival, it could reconfigure itself from its traveling position and form a tether for shuttle docking, reconfigure itself again and form a lasso to rope a damaged satellite, and then reconfigure once again to form a satellite-repair tool. Even better would be to build the satellite from a collection of homogeneous reconfigurable robots and have it repair itself. For difficult terrain maneuverability, a homogeneous system could become snakelike for narrow passages, grow legs for walking or climbing, or roll down a slope as a ball. Conceptual designs for both two-dimensional (2-D) and 3-D reconfigurable homogeneous robots exist.

Sandia will investigate design, control, and planning issues for self-configuring and self-organizing for both systems. Our ultimate goals are (1) the building and testing of a suite of miniature, homogeneous robots designed for self-reconfiguration systems, (2) the development of control electronics that will guide and dock multiple robots that form a larger robot, and (3) the development of planning algorithms to achieve selected shapes and of motion-planning algorithms to move the resulting shapes.

Top: Picture of 2-D reconfigurable Gemini showing active articulation of connecting joint in a "middle up" state.

Below: A "Gemini" system consisting of two modules demonstrates its superior mobility. These modules can connect to and disconnect from each other autonomously. The active coupling between the modules allows control of their relative positions. System configuration can be optimized for varying terrain and mission requirements.

- *2-D system.* Sandia's research on the 2-D system focused on control system integration, testing, and demonstration. Research on the 3-D systems focused on formalizing and publishing the configuration planning method. We completed the integration of the active joint mechanism for coupling and manipulation of two Gemini robotic platforms. The coupled Gemini platform is able to adopt six distinct configurations. The configurations have unique implications for the mobility and mission effectiveness of the coupled system. We identified configurations that improve the range and mobility of the coupled system over that of the uncoupled system. Decoupling the components and allowing them to function autonomously can obviate any degradation of the performance of the coupled system. We developed an automated docking system that relies on ultrasonic range detection to align the individual robotic modules prior to coupling. We redesigned the coupling mechanism to improve its strength in response to dynamic loading.

- *3-D system.* Sandia is designing and fabricating the 3-D systems in collaboration with Dartmouth University. We successfully completed all milestones with the exception of the design, fabrication, and demonstration of 3-D interconnects. Work on the 3-D system focused on documenting and publishing the configuration planning algorithm implementation and resulted in a paper that we submitted to IROS2000. We built a self-reconfiguring robot system of four identical modules. Each module connects to its neighbors with rotating actuators. Each individual module can move in three dimensions relative to its neighbors. We are currently modifying this system to allow global locomotion and manipulation experiments.

We completed the integration of the active joint mechanism for coupling and manipulation of two Gemini robotic platforms. The coupled Gemini platform is able to adopt six distinct configurations. The configurations have unique implications for the mobility and mission effectiveness of the coupled system. ...

Sandia is designing and fabricating the 3-D systems in collaboration with Dartmouth University.

10753

Robust Planning for Autonomous Navigation of Mobile Robots in Unstructured, Dynamic Environments

G. R. Eisler, C. L. Lewis

Emerging battlefield doctrines envision “sensor-to-shooter” battlefield grids that will bring an instant firepower response on critical targets via assessment from human “recon” teams and unattended ground devices comprising the grid. However, training enough soldiers to do reconnaissance tasks is expensive; and maintaining extended-term human surveillance posts can be problematic. Teleoperating robotic assets does not maintain covertness, nor is it feasible for more than a few robots.

Collections of autonomous mobile robots have the advantages of stealth, compactness, redundancy, and long-duration operation. They can provide effective communication networks, manifest collective intelligence via distributed algorithms, and carry a variety of sensors.

This project takes the first step toward this goal by developing a single vehicle characterized by an algorithmic-driven, multispectral approach to point-to-point navigation. By the third year, the vehicle will contain on-board trajectory planning; global positioning system (GPS) satellite position fixes with inertial measurement backup; a mix of sensors to determine obstacle size, configuration, and density; the ability to replan a path in the face of impenetrable terrain; and Internet communication for receipt of mission objectives.

Sandia will use a phased approach for long-range path planning incorporating digital maps. The mission terrain will be characterized from various standpoints: slope, obstacle density, covertness, line-of-sight (LOS), etc. We developed planning algorithms to “grid” the terrain and weight of each gridpoint according to the aforementioned metrics. Short-range planning will center on obstacle/hazard avoidance and modifying steering to be fuel- and time-efficient. Obstacle sensor development to date has shown that optical devices have the best potential for long-range obstacle alerts, allowing time for a planned path over the remaining point-to-point terrain versus reactive obstacle avoidance at short range.

We developed the baseline 1 m vehicle on the RATLER (Robotic All-Terrain Lunar Exploration Vehicle) design. The

Sandia will use a phased approach for long-range path planning incorporating digital maps. The mission terrain will be characterized from various standpoints: slope, obstacle density, covertness, line-of-sight (LOS), etc. We developed planning algorithms to “grid” the terrain and weight of each gridpoint according to the aforementioned metrics. Short-range planning will center on obstacle/hazard avoidance and modifying steering to be fuel- and time-efficient.

vehicle provides excellent mobility, simplified mounting and access structures for sensor attachment, and electrical component shielding.

We developed a three-dimensional (3-D) route planner for navigation over changing elevation; integrated the use of mapped data into the planning environment; provided an active-imaging sensor system for short-to-medium-range scene analysis; provided an inertial measurement unit to complement GPS usage; and provided radio-frequency (RF) Ethernet communication to the EON system, the Sandia external network.

- *Path planning.* The path-planning environment allows the user to interactively visualize a 3-D terrain model and to plan minimum-cost paths across the terrain based on metrics of mission requirements or goals. The underlying planning algorithm uses a weighted graph approach via either a uniform grid or a nonuniform “quadtree” representation overlaid on digital terrain elevation data (DTED) maps. Edge weights or relative costs between variables for the robot to traverse a grid edge are provided for a selection of variables including travel distance, time, vehicle attitude in roll and pitch, radio communications, coactness, and path width (to provide a safety margin against getting blocked or stuck). Choosing time provides a dynamical element to the search by biasing downhill traverses more. Each weight or importance factor specifies a given variable influence on the overall edge cost. Large changes in relative weights can produce very different choices in traversals. Dijkstra’s algorithm and the A* method are standard minimum-cost algorithms in the artificial intelligence (AI) literature and are provided. A* uses a predictive measure of estimating cost to the goal that can help focus the direction of the search, but may fail for the erratic, nonmathematically smooth nature of natural terrain. In cases where dynamic replanning is necessary due to unexpected obstacles during path traversal, the D* algorithm is provided. The D* algorithm relies on a nonuniform grid to provide a localized “escape” solution. Terrain models are used to evaluate the graph edge weights (e.g., pitch, LOS radio communications).

Supported terrain models include the U.S. Geological Survey (USGS) digital elevation models (DEMs), synthetic-aperture radar (SAR), and a variety of custom data formats. High-resolution aerial photographs (e.g., black and white, color, infrared) may be “texture-mapped” to the terrain

The path-planning environment allows the user to interactively visualize a 3-D terrain model and to plan minimum-cost paths across the terrain based on metrics of mission requirements or goals.

elevation model to aid in distinguishing vegetation type and density as well as cultural features such as roads, trails, and buildings. The current path-planning environment allows the user to interactively view the 3-D terrain models and any planned path(s). Regions of radio, vehicle, or location LOS visibility can be generated to aid in analysis of the terrain and to do mission planning. In addition, manual designation of avoidance regions can also be implemented and recognized by the planning algorithms.

- *Inertial navigation measurements.* We are applying Sandia technology for missile and bomb navigation to this land navigation problem through the use of a SANDAC flight computer, NovAtel GPS receiver, and a Litton LN200 inertial measurement unit. This combination provides a baseline in measurement acquisition and position estimation. This stage will be the precursor for replacing these components with less-expensive units and compensating for the loss of accuracy through improved modeling of the accumulated errors and sensor fusion via Kalman filtering.

- *Obstacle sensing.* The obstacle detection system has progressed from the previous two-device prototype to a bank of sixteen ultrasonic Massa M-5000 Smart Sensors providing panoramic coverage of the vehicle. The coverage extends 4 feet radially from the edge of the vehicle. To detect obstacles around the robot, all of the sensors are triggered at the same instant and the data from each sensor are read through a common serial port. As the vehicle (located in the center) moves, it continues to image a body-fixed “occupancy grid.” The blue 8° beam angle cones indicate the detection zones from the M-5000 sensors. Obstacles are color-coded based on the strengths of reflected returns (in increments of 25 percent of full scale), which prioritize the obstacle avoidance steering needed.

We added bumper switches to the vehicle as a last line of defense to prevent catastrophic contact with obstacles (e.g., encoders, compass, vehicle tilt sensors).

We are applying Sandia technology for missile and bomb navigation to this land navigation problem through the use of a SANDAC flight computer, NovAtel GPS receiver, and a Litton LN200 inertial measurement unit. This combination provides a baseline in measurement acquisition and position estimation.

10772

Intense Directed-Energy Theory Initiative*J. S. Wagner, M. G. Mazarakis, P. C. Gray, M. W. Trahan, S. Tucker, E. P. Parker*

As part of the Strategic Defense Initiative (SDI) era, Sandia achieved national recognition for leadership in end-to-end design, modeling, and simulation of directed-energy (DE) systems, including charged particle beams (CPB), high-power radio frequency (RF) and high-power microwaves (HPM), and hybrid laser-assisted CPB systems. This project is advancing and leveraging these never-superseded simulation tools and techniques to enable Sandia to tackle new national security applications. Applications under investigation include both exoatmospheric and endoatmospheric applications as well as laboratory end-to-end accelerator designs supporting many related fusion plasma and DE applications.

Sandia's nearly abandoned DE simulation legacy includes a full suite of multidimensional simulation codes with a variety of physics-based approximations. These range from simple macroscopic envelope models of beams to fully self-consistent microscopic electrostatic, magnetostatic, electromagnetic (EM), and neutral gas dynamic particle-in-cell (PIC) codes.

We reconstituted and modernized for future applications a suite of simulation codes originating from SDI legacies. We constructed EM, electrostatic, and magnetostatic (Buckshot) codes in one dimension, two dimensions, and three dimensions. We built a unique neutral gas particle code to study neutral gas dynamics in both space and atmospheric environments. We constructed a genetic algorithm that can operate a PIC code (Buckshot) that will enable the automated use of PIC codes as design tools.

We rebuilt several new simulation and modeling codes using historical Sandia-developed physics packages to demonstrate the breadth and depth of Sandia's CPB modeling and simulation (M&S) capability. We met all of our current milestones. We added new features to prior programs and conducted new demonstration applications to show depth and breadth of capability. We reconstructed the ion-beam superconducting super collider (SSC) version of Buckshot and the EM code and conducted representative particle beam demo simulations. We enabled the SSC helical electrostatic quadrupole model as an example of using Buckshot as an ion-

... Sandia achieved national recognition for leadership in end-to-end design, modeling, and simulation of directed-energy (DE) systems, including charged particle beams (CPB), high-power radio frequency (RF) and high-power microwaves (HPM), and hybrid laser-assisted CPB systems. ... This project is advancing and leveraging these never-superseded simulation tools and techniques to enable Sandia to tackle new national security applications. Applications under investigation include both exoatmospheric and endoatmospheric applications as well as laboratory end-to-end accelerator designs supporting many related fusion plasma and DE applications.

beam accelerator design tool. We built the NGP code for endoatmospheric beam heating issues. We implemented the EM code for a shaped-charge detonation signature demo, as an example of signatures that might be an indication of space-based difficult targets.

We rebuilt the Air Propagation Code (APC) and conducted preliminary studies to guide experimental design to address unresolved issues in air chemistry models. We validated the rebuilt code by recreating the experimental results first reported for unpropagated radial-pulse-line accelerator (RADLAC) high-current relativistic electron beams. Although our final report does not take advantage of all of the code's capabilities, the APC has the ability to study effects related to beam propagation such as nose (radial) expansion, erosion, or instability growth.

We validated the rebuilt code by recreating the experimental results first reported for unpropagated radial-pulse-line accelerator (RADLAC) high-current relativistic electron beams.

10791

Fuzzy Data Mining*S. M. Deland, L. A. Kennicott, C. L. Jenkin, J. M. Britanik, G. N. Conrad*

This project focuses on techniques for pattern discovery in discrete-event time-series data. The researchers' original motivation for the project was based on observed challenges in analyzing data from network-based, sensor-driven monitoring systems. Examples of such systems include the unattended monitoring systems used in nuclear material safeguards and transparency applications, and network intrusion-detection systems (NIDS) used to monitor computer network communication traffic and user sessions. Analysis of data from such systems requires extracting and classifying patterns in the sensor data and interpreting them in terms of expected or allowed activities.

A key issue from an operational perspective is that it is not feasible to have a human perform all of the analysis. A simple approach to automating the analysis is to identify patterns, classify the patterns as normal (or allowed, or expected, or other classification) and abnormal (or suspicious, or unauthorized, or other classification), and use pattern-matching algorithms to identify and classify observed behavior. However, pattern-detection tools generally cannot discover new, unknown patterns in the data. New tools are needed that are capable of pattern discovery, i.e., the identification of new patterns in the data, whether those patterns represent normal activity or whether they are indicative of unauthorized, anomalous activities.

In this project, Sandia explored two different aspects of the pattern-matching/-discovery problem. The first aspect studied was the use of dynamic time-warping (DTW) for pattern-matching in continuous data. In essence, DTW is a technique for aligning time series along the time axis to optimize the similarity measure. The second aspect studied was techniques for discovering patterns in discrete-event data. We developed a pattern-discovery tool based on adaptations of the a priori and generalized sequential pattern (GSP) mining algorithms. We then used the tool on three different application areas: unattended monitoring system data from a storage magazine, NID, and analysis of robot training data.

The basic approach to sequential pattern discovery is to tokenize the event data, representing the events as symbols

This project focuses on techniques for pattern discovery in discrete-event time-series data...Examples of such systems include the unattended monitoring systems used in nuclear material safeguards and transparency applications, and network intrusion-detection systems (NIDS) used to monitor computer network communication traffic and user sessions.

in a sequence. Initially, patterns are “discovered” in the data by exhaustively searching the symbol sequences for repeating subsequences. Two problems are associated with this approach to pattern discovery. First is the intensive nature of the exhaustive search that is exponential to the size of the sequence. The *a priori* and GSP algorithms are computationally efficient methods for addressing this problem. Second is the matter of deciding what subsequences or patterns are significant to consider for investigation or to ignore in further analysis. Occurrence frequency and other statistical measures can be computed to help a user decide which patterns are significant. A final interesting problem with discrete-event data from multiple sensors is that events from simultaneous activities can be intermingled, effectively disrupting the patterns or making them “noisy.” To handle this problem, we investigated the use of regular expressions and likeness measures to identify similar patterns. After exploring a number of different likeness measures, we defined a token sequence weighted metric that allows a domain expert to provide appropriate significance to tokens and metric components. Each token can be weighted to provide a penalty relative to noise, absence, and sequence position. Additionally, the individual components of the metric, noise, absence, and sequence position can be weighted to exhibit their relative importance during analysis.

We incorporated the sequential pattern-discovery algorithms into a prototype sequential pattern-discovery tool. We applied the sequence pattern-discovery tool to three different problem domains: (1) data from an unattended monitoring system used to monitor activity at a simulated storage facility, (2) Transmission Control Protocol/Internet Protocol (TCP/IP) packet data for an NID application, and (3) robot state data. In each application, we used the tool to find interesting patterns in the data. In the case of the storage facility data, a number of the patterns represented simple event combinations (e.g., pairing of open- and closed-door events, triggering of image capture) known to occur in the data. This analysis helped validate the pattern-discovery approach. The robot data represented a complex state vector and was thus an excellent test of the ability of the pattern detector to discover patterns in a sequence of arbitrary object representations.

The concepts behind the tool certainly exhibit promise, and there are a number of enhancements suggested by individuals who have seen demonstrations of the tool, as well

We applied the sequence pattern-discovery tool to three different problem domains: (1) data from an unattended monitoring system used to monitor activity at a simulated storage facility, (2) Transmission Control Protocol/Internet Protocol (TCP/IP) packet data for an NID application, and (3) robot state data.

as possible uses. The tool shows promise in analyzing network-intrusion data, bunker sensor data, and state sequences from robot test runs. Other possibilities may include nontemporal data such as textual patterns or genome sequences.

Other Communications

Conrad, G. N., J. M. Britanik, S. M. DeLand, and C. L. Jenkin. 2001. "Pattern Discovery in Time-Ordered Data." Sandia Technical Report, Sandia National Laboratories, Albuquerque, NM, in review.

26531

Air Sterilization and Decontamination

R. P. Toth, G. C. Hauser, P. C. Gray

This project will further develop and test a novel method of air sterilization/decontamination to protect vehicles and buildings from attack with biological or chemical weapons. Conventional methods of protection from biological agents is by HEPA (high-efficiency particulate aerosol) filtration (mechanical sterilization). To a knowledgeable adversary, HEPA filters are easily defeated because of their spatial bandpass characteristics. In view of the loads likely to be used in a bioattack and of vulnerability to certain recognized threat agents, occupants will not be protected.

Sandia has developed a new technology based on a radio-frequency (RF)–driven, atmospheric-pressure plasma reactor. It is low cost and capable of quickly sterilizing air (agent half-life in the tens of microseconds) at realistic loads and air flows.

A knowledgeable adversary can defeat HEPA filters because of the spatial bandpass characteristics that (HEPA) filters have. Regarding the likely loads used in a bioattack and vulnerability to certain recognized threat agents, occupants will not be protected. Also, due to shadowing, UV is not useful for the heavy loads expected in a biological warfare (BW) attack. Furthermore, UV damage to DNA (deoxyribonucleic acid) is reversible. Sandia has investigated a new technology for thermal inactivation based on an RF–driven, atmospheric-pressure plasma reactor.

We produced an atmospheric-pressure plasma of at least 1000°C with a laboratory-prototype RF system comprising a power oscillator, its associated high-voltage power supply (HVPS), RF-power control circuitry, RF diagnostics, protective circuitry, and a coaxial applicator for plasma generation. The RF-power oscillator launched 2450 MHz waves into transverse electric (TE)–dominant-mode waveguide and a three-port circulator. We used fixed tuning to match the RF source into the applicator through a WR 284 waveguide. The three-port circulator protects the RF power source while sparkgap initiates the plasma. As RF heats a seed gas (such as argon, nitrogen, or nitrous oxide), the plasma temperature increases and the fixed match takes over control of reflected power. Estimates of temperature by infrared (IR)

We produced an atmospheric-pressure plasma of at least 1000°C with a laboratory-prototype RF system comprising a power oscillator, its associated high-voltage power supply (HVPS), RF-power control circuitry, RF diagnostics, protective circuitry, and a coaxial applicator for plasma generation.

radiometry and frangible coupons within the coupling region of the plasma were 1200°C to 1700°C. We completed a design for heating, ventilation, and air conditioning (HVAC) ducts and ordered RF components.

Beginning with the 1.5-inch coaxial applicator, we used computational-flow dynamics (CFD) studies to determine that this simple reactor had insufficient dwell time for the target flow-rate of 100 cfh and 109 spores cc. CFD studies suggested that a swirl design would combine the target flow and load with dwell times needed for supernumary kill. A number of 1.5-inch-diameter models swirl-chamber designs were built in Delrin and tested on a flow bench. After several iterations, we met specifications in a design for WR 284. Concurrently, we manufactured the best design in 6-inch Delrin for use in HVAC ducts at several hundred cubic feet per minute. The final design will become a mandrel for a ceramic mold that will be tested in the future.

We established a culture system for *Bacillus thuriensis* and *Serratia marcescens*. We completed dispersion tests for the 1.5-inch applicator in axial flow. We injected spores as hydrosols from multiple nebulizers pressurized with argon gas. We recovered spores first by filter paper and later by a six-stage Anderson impactor. Initial dispersion-loss measurements were just under 0.6 logarithm.

After several iterations, we met specifications in a design for WR 284. Concurrently, we manufactured the best design in 6-inch Delrin for use in HVAC ducts at several hundred cubic feet per minute. The final design will become a mandrel for a ceramic mold that will be tested in the future.

26532

Data Fusion and Visualization of MASINT Results for Underground Facility Characterization

M. D. Ladd, M. L. Yee, J. M. Brabson, R. W. Simons, M. W. Koch, D. C. Craft, A. A. Yee, D. C. Carlson, M. E. Bukaty

There has been a long-standing requirement for technologies and architectures to link and integrate dispersed-information assets into a coherent system, particularly systems that address national security threats. Two broad categories of dissimilar types of data can be used to characterize underground facilities (UGFs). One category consists of map-based or image-based data, such as multispectral or hyperspectral images, or synthetic-aperture radar (SAR) images. The second category consists of time-sequence data, such as seismic, acoustic, or electromagnetic (EM) data, which record measured energy over time at a given location. Because of the dissimilar nature of these two categories of data (image versus time-sequence), sensor-level fusion is not feasible in this case and presents unique challenges. Fusion of processed data is required. In this work, Sandia will analytically combine information at the feature level, where raw data from each sensor are preprocessed to generate selected useful features. While feature-level fusion is not new, Sandia believes that this work represents the first time that such fusion is applied to these dissimilar types of data for UGF characterization. The work will help determine what new information for UGF characterization can be obtained. The project will deliver a suite of prototype algorithms that perform the feature extraction, fuse the data, and then present the results with imagery in a meaningful, visual way to the human analyst. Results will be derived from data obtained from experiments performed at the Nevada Test Site (NTS). The development of such algorithms and display tools will provide meaningful and important capabilities that do not currently exist for characterizing a UGF.

We collected more than 1000 Ka-band SAR images. We developed programs to read information from the newly redesigned header and made histograms of the sensor-collection parameters. We also obtained script-tables that describe events of the desired target versus time. Using these script tables, we identified approximately 200 SAR images

... Sandia will analytically combine information at the feature level, where raw data from each sensor are preprocessed to generate selected useful features. While feature-level fusion is not new, Sandia believes that this work represents the first time that such fusion is applied to these dissimilar types of data for UGF characterization.

that intersect the scripts. We also extracted a collection of more than 20 acoustic and seismic datasets that Sandia collected from the same test scenarios as the SAR data. We also obtained multispectral imagery collected by the Remote Sensing Lab (RSL).

We have begun developing an algorithm to extract generic features from possible SAR targets. These features will support the target-related queries. We also prepared software tools to generate feature/identification information from acoustic and seismic data that also will support the target queries. We also began discussions with RSL personnel for possible collaboration on approaches for extracting features from the spectral data. We identified two different types of feature sets for acoustic/seismic data. One of the feature sets consists of the relative weighting of harmonic line sets extracted from the acoustic energy emitted by a vehicle. The other signature uses spectral-eigenvalue-decomposition analysis to identify equipment running in steady state.

We started developing processing modules needed to extract features and the initial statistical analysis and began developing the fusion module that is based on the sequential probability-ratio test technique. We have also begun work on the visualization tools, including discussions with potential customer groups.

We have begun developing an algorithm to extract generic features from possible SAR targets. These features will support the target-related queries. We also prepared software tools to generate feature/identification information from acoustic and seismic data that also will support the target queries.

26533

Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents

C. I. H. Ashby, R. Kottenstette, W. G. Yelton, J. R. Wendt, T. J. Shepodd

Accurate identification of chemicals and biochemicals that can be used as chemical/biological weapons (CW/BW) is essential at nanomolar levels with short analysis times (less than 5 minutes). Vibrational spectra can serve as chemical fingerprints for positive identification of CW/BW molecules. The required speed and sensitivity might be achieved with surface-enhanced Raman spectroscopy (SERS) using nanotextured metal surfaces. Although ordinary SERS produces sensitivity enhancements on the order of 10^6 versus normal Raman spectroscopy, a properly nanotextured metal surface can increase sensitivity up to 10^{14} -fold. Under partially optimized conditions, a single hemoglobin molecule yielded a spectrum with signal-to-noise (S/N) greater than 20 in 200 sec, and low-noise spectra were demonstrated for nanomolar concentrations with less than 1 sec data collection. However, systematic and reproducible methods for preparing metallic surfaces that maximize sensitivity have not been developed.

Sandia proposes developing chemical-fingerprint identification of CW/BW molecules using SERS as the detector for conventional chromatographs and integrating SERS-based detection in the chip-scale microseparation columns developed under μ ChemLab™. We propose developing methods to form high-efficiency metallic nanostructures that can be integrated with either gas- or liquid-phase chem-lab-on-a-chip separation columns to provide a highly sensitive, highly selective microanalytical system to detect current and future chemical/biological agents. The innovative aspects of this project include the design and fabrication of metallic nanostructures that (1) reliably provide the sensitivity for rapid nanomolar detection and identification and that (2) can be incorporated into lab-on-a-chip architectures or used as add-on detectors for other chromatographs. In addition to speed and sensitivity, chemical fingerprinting by SERS will enable rapid identification of new, nonstandard CW/BW agents that might be introduced to avoid detection by established sensor systems.

Sandia proposes developing chemical-fingerprint identification of CW/BW molecules using SERS as the detector for conventional chromatographs and integrating SERS-based detection in the chip-scale microseparation columns developed under μ ChemLab™.

We employed several different methods to achieve a high density of surface-enhanced Raman “hot spots.” These include direct evaporation of metal onto rough surfaces, electrochemical deposition of nanoporous structures, and formation of nanometer-scale metallic columns using electron-beam lithography and lift-off. Preliminary measurements on liquid samples show SERS enhancements for the evaporated gold (Au) structures and for an initial nanoporous Au structure that are characteristic of those reported for Au in the literature (up to 10^6) and are not as high as desired for optimum sensitivity.

A new fabrication approach is being developed to produce structures that closely mimic those predicted by recent theoretical work to produce the highest purely electromagnetic (EM) enhancements ($> 10^{11}$). This approach is based on using an oxidized-aluminum (Al) nanochannel template to control electrochemical deposition of a dense array of capped metallic nanowires with nanometer spacing.

We conducted studies to establish the processing protocols to control nanopore diameter and nanopore spacing. Pore diameters between 2 nm and 100 nm can be controllably produced.

We studied the roles of the grain size and alignment in the Al before oxidation, as well as the effect of preoxidation annealing. We found pore spacing to be generally unaffected by the crystal morphology of the starting Al, which will facilitate the ultimate incorporation of oxidized-Al templates into chip-scale microchannels.

Under development are metallization protocols to form several different metallic nanostructures in these templates that approximate the theoretically predicted optimum shape to produce the desired EM enhancements.

We designed and will fabricate a fixture to integrate metallized test structures with the output of a gas chromatograph to accommodate the preferred metallization as determined by these studies.

We developed acrylate-based polymer monoliths as reverse-phase chromatography media for efficient and reproducible protein separations under both low pH and high pH conditions. These materials employ both the electrophoretic migration of analytes and the differential portioning of analytes in stationary and mobile phases to achieve excellent separations.

This approach is based on using an oxidized-aluminum (Al) nanochannel template to control electrochemical deposition of a dense array of capped metallic nanowires with nanometer spacing. We conducted studies to establish the processing protocols to control nanopore diameter and nanopore spacing. Pore diameters between 2 nm and 100 nm can be controllably produced.

We demonstrated the electrochromatographic separation of neutral and charged amino acids and of bioactive peptides in capillaries using microchip columns with three bioactive peptides separated on-chip in an 8 cm microcolumn. These studies have efficiently separated test compounds closely related to eventual target molecules. We established chromatographic protocols and demonstrated the longevity and reproducibility of our techniques. The separations are independent of concentration so future SERS results could be confirmed, even where analyte concentrations are below our current chromatographic detection limits. Our work in peptides complements our previous work in small molecules yielding a breadth of chromatographic media/conditions for target analytes.

*We established
chromatographic protocols
and demonstrated the
longevity and reproducibility
of our techniques.*

Refereed

Yelton, W. G., K. B. Pfeifer, and A. W. Staton. 2001.
“Porous Al₂O₃ Nanogeometry Sensor Films: Growth
and Analysis.” *J. Electrochemical Society*, accepted.

26534

Advanced Unattended Ground Sensor Technology

D. E. Gallegos, D. L. Faucett, J. W. Giron, M. R. Heying, M. E. Bukaty

During recent years, unattended ground sensors (UGSs) have proved very useful for detecting, identifying, and characterizing difficult targets. However, current UGS technology places severe restrictions on real-world deployment. Specifically, the excessive bulk and inability of UGS to covertly intercommunicate in clusters and to off-load data make this technology difficult to deploy in denied territories. In addition, redeveloping a distinct, custom UGS for each set of varying mission requirements is often prohibitive in time and cost.

To address the bulk, weight, and development challenges, Sandia proposes a novel architecture, referred to as scalable digital signal processing (SDSP), based on the incorporation of a coherent interconnection fabric (ICF). This architecture could lead to small, modular, reconfigurable sensors that could be rapidly inserted into a wide range of deployment mechanisms, such as a microglider, projectile, or robot, or by hand. Our goal is to achieve a significant decrease in power consumption, thereby dramatically reducing the battery payload—the physical “fat” in UGS. Our plug-together architectural approach would enable the use of sophisticated power management, dynamically variable clock-rate devices, and UGS-optimized signal processing to automatically optimize the watts-per-MIPS (million instructions per second) arrangement for a given task. Similarly, we plan to address the data-communications challenges.

This project would design, develop, and demonstrate a prototype miniature ground sensor based on the novel SDSP and other architectures. This architecture will be modular in nature and will enable rapid response to new data-collection needs.

This project would design, develop, and demonstrate a prototype miniature ground sensor based on the novel SDSP and other architectures.

This architecture will be modular in nature and will enable rapid response to new data-collection needs.

(1) Generalized power-modeling tool for next-generation unattended ground sensors (NG-UGS) system. The modular elements of the preliminary power-model tool have been expressed on Excel worksheets. The investigation used the as-built tactical UGS (TUGS) sensor and a developmental

project, Rooster, as examples for system composition and mission complexities. We are reworking the TUGS power elements, are collecting the power estimates for the components of the NG-UGS lab demo system, and entering them for comparison and use during the lab-bench exercises.

The power numbers for the state-of-the-art components in the NG-UGS unit are either unavailable or not reliable. Especially critical is the power draw of the TI 'C55 processor module under different operational conditions. We terminated an attempt to partially populate a previously developed 'C55 circuit board from another project to conduct power measurements when a fatal design flaw was revealed in the design of the board. As a result, we accelerated design and development of the NG-UGS demo modules.

The power-modeling tool evaluation revealed that the original power-reduction goal of a factor of 100 is unreasonable; it shows that the approach originally proposed (concentrating primarily on adjusting the clocking rate for the computing elements: digital signal processor [DSP] and microcontroller) is bounded by a factor of 4. Better than a factor of 10 is achievable, but only by increasing the dynamic control and efficiency of operation over all elements of the sensor system (controller, DSP, analog, communications, global positioning, and others).

(2) *ICF study.* We completed the evaluation phase of the ICF study. We studied five canonical topologies (and their various physical realizations) using the seven-layered open-system interconnection reference model. The nonarbitrated-carrier detect addressable shared multipoint topology was deemed to best meet the requirements for NG-UGS. Two commercially available variants, the I2C bus and the controller area network (CAN) bus, were selected for implementation and demonstration.

(3) *Hardware components for NG-UGS bench-top testing.* The touchstone for the bench-top exercises will be a copied subset of the most mature TUGS unit configured to match the set of modules making up the NG-UGS subsystem. The bench-top NG-UGS will contain the following modules: system controller (performing minimal TUGS control function), DSP (executing the TUGS spectrogram), data acquisition (one channel of signal conditioning and analog/digital [A/D] conversion), and a transceiver (identical Hummingbird transceiver used in TUGS). The NG-UGS modules will be connected using fabric adapters, interface modules for the ICF. To facilitate the bench-top

Better than a factor of 10 is achievable, but only by increasing the dynamic control and efficiency of operation over all elements of the sensor system (controller, DSP, analog, communications, global positioning, and others).

demonstrations, we developed the fabric adapters to be capable of being configured for either the I2C- and CAN-bus ICF variety with no attempt at optimized layout or packaging.

We designed and manufactured the circuit boards for prototype fabric adapters.

The C55 processor circuit boards, for the dual roles of NG-UGS DSP and system-controller modules, are designed, manufactured, and in assembly.

The circuit boards for the NG-UGS data-acquisition modules have also been designed and manufactured. They are in assembly with firmware in development.

Copies of the TUGS circuit boards, to be used as the bench-top touchstone, have been manufactured and assembled; they are currently in testing. The Hummingbird transceivers have arrived.

(4) Software components for NG-UGS bench-top testing. The spectrogram function was carved from the existing suite of TUGS algorithms and verified on a non-Sandia-owned TUGS unit.

To facilitate the bench-top demonstrations, we developed the fabric adapters to be capable of being configured for either the I2C- and CAN-bus ICF variety with no attempt at optimized layout or packaging.

26535

The Endowment of Simulator Agents with Human-Like Episodic Memory

J. C. Forsythe, N. M. Berry, D. A. Schoenwald, E. V. Thomas, E. P. Parker

The challenge of making intelligent national security decisions is increasing for people ranging from the engineer refurbishing a nuclear weapon for which original designers are no longer available, to the future combat-system commander controlling hundreds to thousands of semiautonomous entities, as well as to the intelligence analyst poring over terabits of data from disparate sources.

This project advances cognitive-modeling capabilities to significantly improve intelligent-systems technologies. The goal is to develop adaptive tailored systems that learn and communicate, thus matching the needs of the humans-in-the-loop of complex systems. This work involves simulation of human episodic memory, which includes reasoning and conducting mental simulations based on stories. These capabilities are consistent with human naturalistic decision making.

Sandia's application involves technology to endow machines with human-like episodic memory. Such a machine would store meaningful representations of experiences, recognize similarities between ongoing and past events, and reason and communicate based on experience.

A second application involves synthetic humans for simulation and training. To realistically model variability in individual behavior, synthetic entities must be endowed with diverse life histories. With this capability exists potential to simulate cultural factors and create entities endowed with life experiences of specific individuals.

Sandia's application involves technology to endow machines with human-like episodic memory. Such a machine would store meaningful representations of experiences, recognize similarities between ongoing and past events, and reason and communicate based on experience.

- **Conceptual design.** The project began with a baseline cognitive model that emphasized human naturalistic decision-making processes. We developed a conceptual design that expanded the baseline to include episodic memory processes. As an episode unfolds, events trigger activation of concepts in the semantic network. Over a series of time steps, the pattern of activation in the network changes as some concepts are activated and others deactivated. Memory for an episode consists of instructions for replaying the sequential patterns of activation. However, the memory does not need to provide a

perfect replica. Instead, by representing patterns of activation as schema, considerable data compression occurs. Finally, by referencing memories to time and place and then incorporating pointers to instances of important concepts, hooks can serve as retrieval cues in recalling specific episodes.

- *Initial semantics and grammar.* Our initial approach emphasized identifying a universal collection of themes or story primitives. Definition of these primitives began by considering taxonomies developed through analysis of folklore and ethograms of social behavior. This work has produced an initial collection of primitives for schema (i.e., semantics) and templates for the sequential patterns of semantic activation associated with their recognition (i.e., grammar).

A second approach considered the same issue for machine applications. In this approach, schema are somewhat application-specific. For instance, a building equipped with an array of sensors and a centralized processing system might share a common set of schema with another similarly equipped building, but most likely, little overlap would occur with the schema that a mobile robot uses. These schema provide the semantics. An episode involves the sequential activation of schema, and recurrent sequences of schema correspond to familiar themes or storylines.

- *Method for mapping application domain to semantics and grammar.* Given an application domain, the first step involves identification of schema. In our approach, the intelligent system, with its sensors and control systems, is simulated using UMBRA. For demonstration, we chose a scenario wherein an intelligent system must find a source of smoke. We equipped the system with the cognitive model described in the previous section. Over a series of training-simulation runs, data were collected to activate concepts within the system's semantic network. Statistical analysis provides the means to identify recurrent patterns of activation (i.e., schema). When schema have been defined, follow-up analyses enable the identification of recurrent sequences of schema (i.e., themes).

- *Initial integration with learning algorithms.* We developed concepts to fully incorporate learning mechanisms and to put mechanisms in place to allow initially for associative learning of semantic relationships. Further development will be required to learn stimulus-response-type relationships.

Our initial approach emphasized identifying a universal collection of themes or story primitives. Definition of these primitives began by considering taxonomies developed through analysis of folklore and ethograms of social behavior. This work has produced an initial collection of primitives for schema (i.e., semantics) and templates for the sequential patterns of semantic activation associated with their recognition (i.e., grammar).

- *Demonstration of limited capability, semantics, and grammar.* The demonstration includes (1) cognitive model integrated into the control system of an UMBRA-based intelligent system, (2) cognitive model operated as system searches a building to locate a source of smoke, and (3) data obtained after completing an UMBRA run provides basis for recognition of schema and sequences of schema.

Refereed

Forsythe, J. C. 2001. "Toward a Human Emulator: A Framework for the Comprehensive Computational Representation of Human Cognition." *Proc. Human Factors and Ergonomics Society Annual Meeting* (Minneapolis, MN, October 2002).

Forsythe, J. C. 2001. "Toward a Human Emulator: Computational Representations of Human Cognition." Paper presented to ATEDS, San Diego CA, March.

Other Communications

Forsythe, J. C. 2000. "Computational Representations of Human Behavior: Naturalistic Decision Making, Organic Factors and Knowledge Representation." Paper presented to DoD Human Factors TAG, El Paso, TX, December.

26536

Automated Combat Course of Action (COA) Development

M. E. Senglaub

Conventional military planning parallels decision-making efforts in the strategic-weapons communities and is gaining in complexity. The military decision-making process is used to develop operational orders for combat courses of action (COAs). These COAs are similar to strategic-weapons system requirements in that COAs define the functionality of a combat system. The growth of information technologies, sensors, and computational capabilities—while promising much—is adding to the work associated with decision making, either in design requirements or in combat COAs.

The project objective is to use evolutionary computational technologies—including genetic programs, genetic algorithms, fuzzy logic, and Bayesian networks—to construct a framework that will explore the operational and/or design space to optimize system performance within identified constraints. Optimization requires analytical metrics to assess the quality of a solution. These metrics are the fitness functions mentioned in the literature. To capture the complexities of next-generation operations, the command-and-control component must be present in the fitness algorithms. This component is lacking in accessible strategic planning tools, but exists in a U.S. Navy simulation that this project will use. The construct of an automated COA process must include a dynamic adversary. Traditional approaches play a static adversary against blue forces; evolutionary game theory shows that this approach will result in suboptimal COA construction. With this construct, Sandia must undertake a multilevel approach that captures behavior at tactical and strategic levels and includes learning algorithms to maintain the dynamic aspects of combat simulation.

The project identified a unique approach to perform combat COA analyses and development. The multilevel hierarchy provides optimal use of evolutionary computational technologies and existing combat-analysis tools. Joint Forces Command (JFCOM) expressed a desire to include dynamic adversarial models in combat simulations and command decision-making processes. Work performed in a human cognition effort was folded into the COA effort to add

The project objective is to use evolutionary computational technologies—including genetic programs, genetic algorithms, fuzzy logic, and Bayesian networks—to construct a framework that will explore the operational and/or design space to optimize system performance within identified constraints.

sophistication to the construct. The functional model would employ a statistical representation of systems at the tactical level. Thus, the model could use evolutionary computational technologies in the optimization process. At the strategic level, Sandia is planning to use the Naval Simulation System for fitness evaluations. This would provide a reasonably familiar interface for commanders.

Preliminary analyses using evolutionary game theoretics demonstrated a need for dynamic adversarial models. When the adversary (red force) learns, the offensive (blue)-force tactics differ from tactics developed in the absence of red learning.

We based the functional cognition model on a Peircean model of scientific inquiry or reasoning model with extension defined by Lefebvre and Apter. This permits an eventual inclusion of social, cultural, and physiological effects on the process of human cognition and decision making.

We based the functional cognition model on a Peircean model of scientific inquiry or reasoning model with extension defined by Lefebvre and Apter. This permits an eventual inclusion of social, cultural, and physiological effects on the process of human cognition and decision making.

26537

An Advanced Learning Model for Agent Behavior

R. J. Pryor, D. C. Barton

Sandia development of agent-based applications is experiencing significant growth. Examples of applications include warfighting, terrorism, robotics, infrastructure security, and economics. The success of these applications will depend mostly on how realistic our models of agent behavior are. Behavior is the logic that governs all decisions of the agent. In warfighting, for example, an agent may be faced with a decision to attack or retreat from an engaging enemy. His decision process would draw on military tactics as well as human behavior. Currently, Sandia has no methodology to realistically model this agent. The most effective models of behavior have been either neural networks or genetic programs. Neural networks are highly effective classifiers but have limited computational capability. Genetic programs have the opposite properties.

We propose a new learning model with the benefits of both neural and genetic networks. The new model uses a layered approach to allow learning sessions that incorporate previous knowledge. A layer is planar space containing interconnected neurons and genetic programs. As an agent reaches the limit of the current layered configuration, a new layer would be added to increase the agent's decision capabilities. A massively parallel (MP), evolutionary programming model will be developed to evolve the configuration. If this work is successful, agent models could, for the first time, handle problems that depend heavily on human decision making. This would increase the demand for Sandia's uniquely powerful agent-based simulations.

(1) We found that layering neural networks worked, but the networks were not as powerful as we had expected. In a mixed model—one with genetic programs and neural networks—the genetic programs won the competition for space on the gene. We concluded that genetic programs were more powerful and more capable.

(2) We discovered a way to layer genetic programs. This model will allow us to retain learning from previous sessions. The model, which uses only genetic programs, is also easier to implement.

Sandia development of agent-based applications is experiencing significant growth. Examples of applications include warfighting, terrorism, robotics, infrastructure security, and economics. The success of these applications will depend mostly on how realistic our models of agent behavior are. Behavior is the logic that governs all decisions of the agent. In warfighting, for example, an agent may be faced with a decision to attack or retreat from an engaging enemy.

(3) We completed and tested several model versions. This is ongoing work, and we are finding more robust model configurations. We are testing the models using an unmanned-aerial-vehicle (UAV) problem.

(4) We completed a powerful UAV simulator and placed it on the Web for general viewing. This is a Windows application that reads in genetic programs and displays the flight of one or more UAVs.

(5) We discovered a way to encode a genetic program in a simple ASCII (American Standard Code for Information Interchange) file. This allows us to easily move programs from one platform to another. We are looking at using this ASCII representation in our evolutionary-mutation operations.

We completed a powerful UAV simulator and placed it on the Web for general viewing. This is a Windows application that reads in genetic programs and displays the flight of one or more UAVs.

26538

Threat-Assessment Study for Short-Pulse Laser Technologies in Directed-Energy and Countersensor Applications

S. M. Cameron, P. J. Federico, S. B. Dron, L. A. Boye

Recent developments in subpicosecond high-energy laser research create new potential vulnerabilities for optical detectors, threat-warning sensors, and self-protection technologies. In particular, the unique interplay of focusing condition, nonlinear dispersion, coherent spectral bandwidth, and ionization achievable with such lasers can produce a self-regularizing waveguide channel. This channel propagates high-power ultrashort pulses with enhanced spectral brightness and highly directional emittance characteristics. Unprecedented power density, unique temporal-spatial coherence signatures, and broad spectral self-phase modulation are all associated with refractively guided propagation of self-focused ultrashort optical pulses in atmosphere and optical media. Therefore, new unconventional intensity-driven susceptibility mechanisms may be possible in sensors and components at range.

Such emerging capability has significant implications for laser directed-energy (DE) threats against future remote-sensing systems. Commercially available short-pulse laser technology combined with the global proliferation of advanced optical technologies could, for adversaries, create opportunities for operational and military exploitation during the next 5 to 10 years.

This project will specifically address issues of laser threat-warning and interdictive modes in optical detectors for incident ultrashort laser-pulse interactions. As part of this effort, Sandia will assess the evolving threat-development cycle of foreign femtosecond-laser capability for military application. We will conduct laboratory experiments on sensor phenomenology and will evaluate the technological implications for the intelligence community. The proposed interdisciplinary teaming integrates complementary expertise.

The project approach consisted of two interactive parallel efforts: (1) baseline experiments and (2) threat analysis. The experimental portion addressed fundamental physics issues of propagation control, threat warning, and effects susceptibility. The assessment component evaluated

This project will specifically address issues of laser threat-warning and interdictive modes in optical detectors for incident ultrashort laser-pulse interactions. As part of this effort, Sandia will assess the evolving threat-development cycle of foreign femtosecond-laser capability for military application.

technology maturity and the development cycle for operational deployment of short-pulse lasers.

Sandia accomplished the following tasks:

(1) Initiated contacts and conducted technology briefings with the cognizant national threat-assessment committees.

(2) Completed analysis of the unclassified and classified database searches using the initial keyword suites and found significant international research in this area.

(3) Designed and constructed a representative test fixture for laser-interaction phenomenology experiments.

(4) Assessed vulnerabilities and hardening strategies for generic system architectures.

(5) Identified potential modifications to threat-warning receivers for short-pulse laser applications.

(6) Established technology critical paths, key facilities proliferation paths, and environmental indicators.

(7) Conducted automated analysis of the unclassified database abstracts using Sandia's V_xInsight™ (a powerful, flexible tool for exploring data collections).

(8) Conducted manual analysis of the classified database hits.

(9) Investigated the use of V_xInsight™ to analyze the classified database hits.

(10) Correlated database information statistically to identify patterns: key facilities, people, and technologies.

(11) Continued parametric experiments to evaluate effectiveness of hardening and threat-detection options.

(12) Began mission analysis for specific DE engagement scenarios.

Sandia designed and constructed a representative test fixture for laser-interaction phenomenology experiments.

26539

Algorithms for Improved Performance in Cryptographic Protocols

C. L. Beaver, R. C. Schroeppe, V. A. Hamilton, N. D. Blair-Stahn, L. M. Miller

Cryptographic protocols allow critical data to be protected across insecure communication lines. Asymmetric (public-key) algorithms are the cryptographic tools that these protocols use to authenticate and provide data nonrepudiation. The mathematical operations in these asymmetric algorithms require excessive computation and bandwidth. Hence, authentication protocols are too slow and consume too much bandwidth for many technologies (e.g., wireless communications, ad hoc networks, sensor technologies). These applications and new military applications such as minimally manned warfare need fast, reliable cryptographic protocols to ensure communication integrity.

Using elliptic curves in public-key computations has allowed computations and bandwidth to be somewhat reduced. This project seeks to advance research on using elliptic curves to find even more efficient algorithms and to make public-key cryptography available to a wider range of computing environments. Sandia further proposes to study hyperelliptic curves to learn if the curves can be used as a cryptographic venue that increases efficiency for computation and bandwidth requirements.

- *Completed baseline literature search and begin draft of final report.* We gained an understanding of work accomplished in the field and the nature of outstanding issues. The information gathered is too extensive to include in this report, but the following accomplishments and findings are notable: a new (although unsuccessful) attack on the elliptic-curve discrete logarithm problem called *xedni calculus*; new point-counting algorithms; and a lack of significant new research on hyperelliptic curves.

- *Completed initial elliptic/hyperelliptic curve implementations.* These implementations are crucial to evaluate our ideas and lend insight. Our implementations thus far include the following:

- LISP code developed for working with elliptic curves over GF(2) (Galois fields).

This project seeks to advance research on using elliptic curves to find even more efficient algorithms and to make public-key cryptography available to a wider range of computing environments. Sandia further proposes to study hyperelliptic curves to learn if the curves can be used as a cryptographic venue that increases efficiency for computation and bandwidth requirements.

- Code to scan through continued-fraction representations of hyperelliptic-curve groups. The continued-fraction representation is full of patterns that may mature into insights into the group structure.

- C codes to perform elliptic-curve operations. The codes will be available in our cryptographic library for customer use.

- *Began performance analysis.* Performance analysis on the above algorithms indicated that we are heading in the right direction. The C code implements algorithms such as a halving algorithm that is three times faster than the usual elliptic-curve addition algorithm.

- *Investigated Frey-Gaudry-Smart attack.* Frey, Gaudry, and Smart give a method for computing discrete logarithms on elliptic curves by mapping the problem to a corresponding problem on higher genus curves. For curves of sufficiently high genus, the discrete log problem is easier, and so, if this is possible, it presents an attack on the elliptic-curve discrete logarithm. In particular, this attack may work particularly well for elliptic curves defined over *field towers*. Field towers can be constructed for fields with composite order and may provide a computational advantage for elliptic-curve arithmetic. Our research has been using field towers to speed up computations, so we were particularly interested to see if this attack threatened our approach. However, our investigations indicate that this attack is not very practical except possibly for curves defined over very small ground fields.

The most important product may come from new research ideas that we discover during this project. We are also developing other directions of interest:

- One of the most computationally intensive operations in elliptic curve-based cryptographic algorithms is the algorithm for adding two points. We are exploring various algorithms that generalize the addition of two points on an elliptic curve. In particular, we are exploring formulas for adding three points at a time and for combinations like $2A+B$ and larger multiples such as $3A$ and $4A$. Also, we examined replacing the usual cubic-curve equation defining an elliptic curve with a quartic curve and replacing the line joining two points (in the chord-and-tangent addition/doubling algorithm) with a parabola.

- It has been suggested that divisors on a hyperelliptic curve may be a useful group on which to base a discrete log cryptosystem. To date, algorithms to do computations on

The most important product may come from new research ideas that we discover during this project. ...

We are exploring various algorithms that generalize the addition of two points on an elliptic curve. In particular, we are exploring formulas for adding three points at a time and for combinations like $2A+B$ and larger multiples such as $3A$ and $4A$.

hyperelliptic curves do not appear more efficient than on elliptic curves. We are trying to apply improvements already made in the ground-field arithmetic for elliptic curves to hyperelliptic curves. We are also considering alternative ways of adding hyperelliptic-curve points.

- We are looking at particular sequences and problems related to the logarithm problem to speed up computations. We contracted with an expert to help investigate some of these issues.

- We are also investigating recent point-counting algorithms.

We are trying to apply improvements already made in the ground-field arithmetic for elliptic curves to hyperelliptic curves. We are also considering alternative ways of adding hyperelliptic-curve points.

Other Communications

Schroeppel, R. C. 2001. "Elliptic-Curve Point Halving Wins Big." Paper presented to the Midwest Arithmetical Geometry in Cryptography Workshop, Urbana-Champaign, IL, 18 November.

26540

Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting

D. F. Dubbert, R. E. Heintzleman, K. O. Wessendorf, P. A. Dudley

For the past decade, wireless communication systems have reaped the benefits of digital-circuit technologies. Benefits include reduced cost, size, and weight, and increased flexibility of communications devices. Sandia believes digital technology has advanced sufficiently that—coupled with Sandia's innovative radar design, waveform synthesis, and digital-sampling technologies—we are ready to embark on a digital revolution.

Sandia-developed radars (for remote sensing, targeting, and fuzing) demand the highest levels of performance for signal generation and signal processing in terms of operation frequency, dynamic range, bandwidth, and robustness. Recent advances in high-speed digital technology have anticipated the unique marriage of the latest high-speed digital technology and digital-signal generation and processing techniques with Sandia's expertise in radar-system design, development, and exploitation. As a result, digital-radar technology is established as the next-generation solution to remote-sensing and communications systems, which must be low cost, miniaturized, lightweight, and highly flexible.

Sandia made significant progress in two areas, which make up the two halves of the digital-radar solution: (1) advanced waveform synthesis and (2) the digital receiver.

- *Advanced waveform synthesis.* We developed a novel technique called *quadrature error-corrected digital-waveform synthesis (QECDWS)*. We believe QECDWS will be the next-generation solution to radar-exciter technology at Sandia. We developed both the patentable QECDWS idea and the supporting analysis, simulation, and calibration techniques for a wide-band radar exciter that employs an image-rejection QECDWS.

- *Digital receiver.* We changed our focus from an originally proposed receiver/exciter module test vehicle to a digital-receiver (DRX) module as an upgrade to our existing synthetic-aperture radar (SAR) systems. All technologies and techniques employed in the DRX—including digital oversampling, digital-quadrature demodulation, and high-

Sandia made significant progress in two areas, which make up the two halves of the digital-radar solution: (1) advanced waveform synthesis and (2) the digital receiver.

performance, efficient finite-impulse response (FIR) filtering—are part of the wider-scope digital-radar concept. We developed a high-level block-diagram-and-requirements definition of the DRX module, began major component specification and lab testing, and performed numeric simulations of the quadrature demodulator and first-stage FIR filter. We also began laboratory evaluation and data analysis pertaining to a commercially available track-and-hold amplifier for future DRX application.

- *Digital radar system.* The characteristics of the digital-radar building blocks spawned concepts for a new breed of radar system. We documented a high-level conceptual design for a wideband, high-performance radar system. This concept is an example of how the digital-radar technology building blocks and digital-radar techniques might be used in future Sandia-developed radars for SAR as well as fuzing and targeting applications.

Other Communications

Doerry, A. W., and D. F. Dubbert. 2001. “Quadrature Digital-Waveform Synthesis and Calibration for Synthetic-Aperture Radar.” Sandia Technical Report SAND2001-0680, Sandia National Laboratories, Albuquerque, NM (March).

We developed a high-level block-diagram-and-requirements definition of the DRX module, began major component specification and lab testing, and performed numeric simulations of the quadrature demodulator and first-stage FIR filter.

26541

Triggered Isomer Research

P. J. Griffin, M. G. Mazarakis, L. C. Sanchez

Isomers are long-lived, excited states of nuclei. Isomers release their excess energy by electromagnetic decay in the form of gamma rays. Isomers have been investigated for years; however, recent triggering experiments of the 31-year $^{178}\text{Hf}^{\text{m}2}$ isomer revealed exciting possibilities for a new high-energy-storage capability. Particularly interesting is $^{178}\text{Hf}^{\text{m}2}$ because of its high-energy density (1.4 GJ/g or 0.33 ton of trinitrotoluene [TNT] per gram), long half-life (31 years), and the recently demonstrated ability to induce its decay with an x-ray (in the range of 10 to 40 keV). If the energy release can be controlled and the isomer can be produced at reasonable cost, $^{178}\text{Hf}^{\text{m}2}$ will have numerous applications in very lightweight munitions and propulsion. This could revolutionize missile defense (e.g., homeland defense) by enabling light, highly maneuverable antimissile warheads that do not have to hit to kill. Because the isomer energy release is ionizing radiation, the energy release could enable penetrators with significant agent-defeat capability. Isomers could empower engines with significantly longer flight times than today's chemical systems.

If isomers are to be a useful energy-storage medium, the next step is to build a break-even experiment that demonstrates to engineers that more energy can be obtained from the isomer energy-storage medium than is required to trigger it.

This project will develop a detailed design for an isomer energy-storage medium break-even experiment. The project will include a detailed radiation analysis, a heat-transport analysis, and a structural analysis of the isomer system. A detailed experimental program will be laid out to demonstrate the break-even point. To support the validity of the experiment, both a safety analysis and an environmental-effects estimate will be performed. We defined a production process that can produce enough material for the break-even experiment.

- *Evaluate reactor/accelerator production methods.* We conducted triggering experiments to generate design data. Task 1 was delayed to take advantage of Air Force Office of Scientific Research (AFOSR) work currently being sponsored

This project will develop a detailed design for an isomer energy-storage medium break-even experiment. The project will include a detailed radiation analysis, a heat-transport analysis, and a structural analysis of the isomer system. A detailed experimental program will be laid out to demonstrate the break-even point. To support the validity of the experiment, both a safety analysis and an environmental-effects estimate will be performed.

in Europe and at the University of Central Florida. However, the triggering experiments continued and were successful. Triggering was identified to occur between 10 and 20 keV, with a best-estimate energy of 10.65 keV. Triggering was demonstrated to increase with increasing voltage on the bremsstrahlung accelerator at constant current. The design of the follow-on experiments at Argonne and Brookhaven national laboratories' synchrotrons was completed. This task is being partially extended to use information currently generated as part of the AFSOR-sponsored work.

- *Update CEPXS and FEMP design codes.* We updated the FEMP code to deal with alpha calculations. We determined CEPXS to be compatible with FEMP; no additional modifications are required. We will make enhancements on an as-needed basis for the FEMP code.

- *Analyze current triggering experiments.* We analyzed all available project data to identify the x-ray-triggering energy range of interest. Recent experimental results from the University of Texas–Dallas and Lawrence Livermore National Laboratory gave conflicting data at low x-ray energies (near 10 keV). We made detailed photon-shielding calculations; computational results indicated that low-photon fluxes will exist at these energies, thus leading to inaccurate results. Any future data from in-progress experiments, along with to-be-published data from AFOSR investigators, will be examined in detail as soon as data are available.

- *Analyze isotopic-production results from high-flux isotope reactor (HFIR) production experiments.* The HFIR production experiments are complete. The analysis of these data identified difficulties in the production of $^{178}\text{Hf}^{m2}$ along with its separation and purification.

We updated the FEMP code to deal with alpha calculations.

We determined CEPXS to be compatible with FEMP; no additional modifications are required. We will make enhancements on an as-needed basis for the FEMP code.

26542

A Scientific Basis for Robotic Ground-Vehicle Design

P. R. Klarer, M. R. Vaughn, K. M. Jensen

Mobile robots have recently seized center stage for remote information gathering in the military and intelligence worlds. The difficult operational environments and mission requirements are driving systems engineers to push the performance of current unmanned ground vehicles beyond the performance for which the vehicles were designed. Currently vehicle design is only loosely tied to the mission and mostly based on prior designs and experience. Therefore, Sandia is developing a design methodology for mobile robots.

The methodology begins with mission analysis, then optimizes performance requirements, and includes a modeling-and-simulation environment to optimize designs and estimate probabilities of mission success. This project will result in a new and unique capability to define and design mobile robotic-vehicle systems based on customers' mission requirements, providing Sandia with a differentiating capability in robotic-vehicle design.

Theoretical and analytical work includes a basic understanding of the dynamics of vehicle interactions with discrete obstacles and the identification of several potential approaches for quantifying the interactions of generic vehicles with obstacles and terrain. We developed an approach for model verification through field experimentation; experiments have begun and will continue.

This project will result in a new and unique capability to define and design mobile robotic-vehicle systems based on customers' mission requirements, providing Sandia with a differentiating capability in robotic-vehicle design .

26543

Adaptive and Mobile Ground Sensors

A. B. Maish, R. L. Williams

Sandia proposes a novel and practical use of robotic vehicles to characterize the contents and characteristics of high-valued targets. In particular, robotic vehicles that carry seismic/acoustic sensors can be used to significant advantage. We propose an adaptive-mobile-array (AMA) technique whereby sensor-based robots autonomously redeploy based on in situ measurements of seismic/acoustic emissions from underground targets. Additionally, the robots can provide significant insertion mobility during deployment to place the array in an optimal high-signal, low-observable position relative to the target.

The novel technical approach involves several huddled sensors used to estimate the characteristic frequencies and wavelengths of the target emanations. We will use an array-optimization algorithm to estimate in situ frequencies and create a coherent array to estimate the target bearing. The outputs of this array algorithm will autonomously instruct the robotic sensors to redeploy (approximately 1 to 10 m). Slight readjustments of the array would then be made until the array hones in on the source. In effect, only a handful of mobile sensors provide very precise bearing estimates.

This project is designing, developing, and implementing the technical innovations required to bring AMAs to reality. In particular, the effort is addressing (1) algorithms for coherent/mobile beam formation, (2) modification of an existing robotic-vehicle design to incorporate a modular/deployable payload capability, (3) deployment of seismic sensors well coupled to the ground, and (4) optimization of sensor-to-robot communications. The project will culminate in a field demonstration using robotic vehicles. The field demonstration will involve a realistic scenario such as the community experiments at the Nevada Test Site.

Sandia has accomplishments in project planning, system-configuration evaluation, adaptive sensor-array signal-processing modeling and verification, and hardware design for sensor-array deployment. We developed a detailed project plan and a high-level control architecture plan to guide detailed controls development.

The novel technical approach involves several huddled sensors used to estimate the characteristic frequencies and wavelengths of the target emanations. We will use an array-optimization algorithm to estimate in situ frequencies and create a coherent array to estimate the target bearing.

The system-configuration evaluation integrated a variety of considerations, including mission-operational constraints, sensor- and signal-processing issues, target and terrain characteristics, robotic-vehicle performance parameters, and sensor-deployment and -retrieval considerations. We completed the initial evaluation of all these considerations; the result is that the vehicle and seismic-sensor configuration has been changed to the present, preferred option. The original configuration had one sensor per vehicle and used a suite of vehicles to deploy seismic sensors that were wired to the vehicles. The preferred configuration uses a single vehicle to deploy and retrieve multiple radio-linked stand-alone seismic-sensor packages and then stand off, so the vehicle does not couple wind-induced vibrations into the ground near the sensors. The acoustic-sensor array is still mounted on a single vehicle using extendible masts to vary sensor spacing up to 1 m apart because, with ground mounting, achieving 4 cm sensor relative-placement accuracy would be difficult.

Commercial geophones use a spike to couple the sensor to the ground, but lightweight robotic vehicles cannot push such spikes into hard ground. We identified and tested three classes of torsional-insertion force devices and identified some that achieve good penetration with reasonable forces. We then completed field tests on the relative signal-coupling performance of these devices. We determined that sensors without any coupling devices were acceptable.

Another important part of this project is development of sensor signal-processing algorithms and algorithms to guide the sensor-array configuration. This effort started with a detailed evaluation of array signal processing to quantify the benefits of adaptability and to identify areas for algorithmic development. Array gain, mainlobe width of the array pattern (and its variants), the relative amplitude of sidelobes, and spatial aliasing have been identified as intermediate measures of array performance. Field experiments followed the system study and initial design efforts. One experiment quantified the impact of wind on key aspects of the acoustic-array design. Another field test simulated the adaptation of an array of seismic sensors that the robot would perform in a typical mission.

The data acquired during this field exercise will assist in the development of the array signal-processing software. We began to develop the array signal-processing software by defining the interface between the array signal-processing

Commercial geophones use a spike to couple the sensor to the ground, but lightweight robotic vehicles cannot push such spikes into hard ground. We identified and tested three classes of torsional-insertion force devices and identified some that achieve good penetration with reasonable forces. We then completed field tests on the relative signal-coupling performance of these devices.

subsystem and the rest of the robot. We also defined the necessary software modules, their tasks, calling sequence, and logical data flow.

We achieved the primary goal of hardware development. The goal was to demonstrate the capability to deploy, recover, and redeploy seismic sensors while achieving high-quality coupling to the ground. We mounted the prototype seismic-sensor-deployment hardware on a high-mobility dual-body robotic vehicle and demonstrated it using teleoperational controls. We designed the prototype for tolerance to positional errors. Additionally, we demonstrated a variable-sized acoustic array using six extendible masts.

We achieved the primary goal of hardware development. The goal was to demonstrate the capability to deploy, recover, and redeploy seismic sensors while achieving high-quality coupling to the ground.

26544

Algorithm Development for Prognostic Health Monitoring and Maintenance

L. P. Swiler, J. B. Kelley, J. E. Campbell, T. P. Swiler

This work will evaluate, develop, and integrate algorithms for prognostic health monitoring and maintenance (PHMM). The project will result in a decision-support system to help evaluate maintenance strategies for risk, time, and cost. We will dynamically update the optimal recommendations for changing conditions and sensor monitoring. The range of applications and customers for a PHMM tool is very broad. The PHMM algorithms will be tested and validated for a real system of interest for which Sandia can obtain extensive statistical failure data, most likely the F-16 or the future combat system.

Our research is divided into two major areas:

(1) For a PHMM system to be robust, the system must integrate information from a variety of sources and thus consider all evidence that affects a prognosis for system health. To integrate this information, we are developing an evidence engine. The evidence engine uses a Bayesian belief network (BBN) for fusing information at the sensor-feature and failure-mode levels. Additional prognostic algorithms will detect trends, abstract and identify sensor features, estimate remaining useful life, and more.

(2) We are developing algorithms to analyze the consequences of various maintenance actions. These algorithms will be included in the consequence engine to provide a recommended course of action based on the current system state, pending problems, and planned equipment use. The consequence engine will include a scenario generator that automatically creates a suite of potential maintenance actions. Consequence-engine algorithms will calculate the impact of each proposed action on system failure and present a set of high-ranking potential actions.

We began developing algorithms for both the evidence engine and the consequence engine and conducted a comprehensive literature search for prognostic algorithms. We are working with the Applied Research Laboratory at Pennsylvania State University to understand the types of algorithms involved in condition-based maintenance. Several of us took a course on BBN.

We are developing algorithms to analyze the consequences of various maintenance actions.

These algorithms will be included in the consequence engine to provide a recommended course of action based on the current system state, pending problems, and planned equipment use.

- *Evidence engine.* We developed an architecture for the evidence engine and are defining objects (data and algorithms) that will populate it. We have a report outlining prognostic algorithms, a preliminary design document, and alpha-version software to perform evidence integration. The current version of the evidence-engine software takes a list of failure modes and information relating to those failure modes (such as time-to-failure distributions, current age, sensors, and others) and projects remaining useful life based either on sensor-feature extraction and trend extrapolation, or on a BBN that is updated according to maintenance and inspection evidence.

- *Consequence engine.* We designed the data and object models for the consequence engine, and development of the algorithms is under way. We have also started to identify and develop algorithms that will evaluate the impact of maintenance actions. We implemented software that will take as input a maintenance-and-use schedule, spares information, and time-to-failure data on components. This software then generates maintenance and failure events and evaluates performance measures such as total downtime, equipment availability, and cost. This software is the prototype for the consequence engine. It has successfully passed initial alpha testing.

Other Communications

Swiler, L. P. 2001. "Algorithm Development for Prognostic Health Monitoring and Maintenance, Final Report." LDRD 01-0329 (September).

We developed an architecture for the evidence engine and are defining objects (data and algorithms) that will populate it. We have a report outlining prognostic algorithms, a preliminary design document, and alpha-version software to perform evidence integration.

26545

New Mechanism for Upset of Electronics

G. M. Guillermo, L. D. Bacon, R. J. Walko, R. C. Pate, L. L. Molina, P. E. Patterson

This project is investigating the conditions under which selected electronic circuits and systems can be driven out of stable operation through exploitation of nonlinear dynamical system behavior; the project is also exploring the role such behavior can play in causing functional upsets or electronic-system disablement through exposure to the proper high-power microwave (HPM) radiation environment. Virtually all electronic circuits and systems possess nonlinear features and phenomenology that make them subject to erratic, complex behavior under certain operating conditions. This behavior, which is referred to as deterministic chaos, appears to arise in all forms of nonlinear dynamical systems. This behavior is found in the life sciences, economics, mechanical and fluid systems, chemical reactions, electrical systems, optics, and quantum mechanics, to name a few. Within the context of electronic circuits and the flow of data and/or control signals designed to function in a specified manner, the appearance of chaotic behavior is a serious departure from the desired stable regime of operation. Onset of chaos can thus lead to the functional upset or disablement of the system. Under the proper conditions, transition of a nonlinear system from stable operation to unstable chaotic behavior can occur rapidly through relatively modest changes in one or more operational parameters. This raises the possibility that electronic systems of interest may be subject to new forms of functional upset through this mechanism by exposure to electromagnetic (EM) stimuli having the appropriate signal characteristics at power- and energy-density thresholds well below those traditionally required for upset or damage from conventional HPM exposure.

The project combines analytical modeling with experimental investigations involving both direct-drive and EM coupling to several representative electronic, electromechanical, and/or electrooptical systems of interest to the departments of energy and defense.

Project goals include identification, characterization, and demonstration of chaos-related vulnerabilities, defensive countermeasures, and exploitation approaches and techniques.

The project combines analytical modeling with experimental investigations involving both direct-drive and EM coupling to several representative electronic, electromechanical, and/or electrooptical systems of interest to the departments of energy and defense.

Sandia searched and reviewed literature pertaining to applied chaos theory and chaos-related behavior, as well as to effects and control in practical analog and digital (A/D) circuits. Initial modeling and experimental work focused on simple driven-diode-resonator circuits operating at low frequencies (below 2 MHz).

Working with this simple class of circuits provided a starting point to understand chaotic-behavior characterization within electronic circuits. The initial experimental work included developing the required laboratory test-bed and data-acquisition system; this initial work allowed us to explore various data-capture, -visualization, and -analysis techniques. We directed considerable effort toward understanding the cause-effect relationship of chaotic behavior in this simple circuit as a function of the nonlinear characteristics of the diode. Relative to other circuit parameters, voltage-dependent diode-junction capacitance and reverse-recovery characteristics dictate chaotic behavior. SPICE-circuit modeling showed general qualitative agreement with experiments, but differs in quantitative detail for reasons still under investigation. We are pursuing improved diode models that incorporate more semiconductor physics, along with plans to modify diode-carrier recombination times with neutron irradiation and to evaluate the effect on circuit behavior. We identified A/D circuits that are more representative of real-system elements for further investigation. We selected the phase-locked loop (PLL) specifically as the next area of focus. This selection stems from the widespread use of PLLs in communications and control systems, as well as our recent coincidental observation of possible chaotic PLL upset in radio transmitters during unrelated project testing. Improved direct-injection and EM-coupling test-bed development, data-capture, and data-visualization capabilities are under way for testing, diagnostics, and data-analysis capabilities into the gigahertz range.

Working with this simple class of circuits provided a starting point to understand chaotic-behavior characterization within electronic circuits. The initial experimental work included developing the required laboratory test-bed and data-acquisition system; this initial work allowed us to explore various data-capture, -visualization, and -analysis techniques.

26546

Flexible Robotic Maintenance Facility

W. D. Drotning, P. A. Watterberg, W. J. Prentice, C. S. Loucks

The Robotics and Intelligent Machines Roadmap for the Department of Energy identified classes of processes that could be automated. The Roadmap identified technology bases that underlie noncontact, contact, and multiprocesses. Relevant to the Roadmap, a proposed Sandia project strives to develop advanced design tools for flexible robotic workcells and to apply these tools to conceptualize an automation-intensive maintenance facility for a class of complex systems. We envision a facility designed for automated operations and to accommodate an entire class of complex systems, including weapon systems. Facility costs could be amortized over multiple systems and processes. The facility will have multiprocess automation equipment to reduce maintenance manning requirements. The initial target environment is military-aircraft maintenance, although the resulting tools will be applicable to the design of robotic workcells for other complex systems. A system study of military-aircraft-depot maintenance will identify high-payoff automation opportunities.

Elements of this vision have been realized for the aircraft-painting/-coating process and for nuclear weapon-component spray cleaning. In developing advanced painting/coating/cleaning systems, we discovered a need for more advanced design tools, which this project will develop. Tools will be targeted at environments requiring many changes in task or workpiece. The tools will allow rapid analysis of a workcell configuration—including commercial and custom hardware—for operations on any of a class of systems. The needed tools will integrate modeling and simulation, automated path planning, automated path generation, and minimization methods to support workcell-architecture analysis. These tools will allow assessment of designs with variable workpiece position. The required tools will use automated path planning to minimize the number of robot positions the operator must specify. We will select a key process technology for analysis using the tools.

We made a first selection and identification of key technologies and processes for maintenance tasks. We studied the compilation of current aircraft-maintenance-site

Elements of this vision have been realized for the aircraft-painting/-coating process and for nuclear weapon-component spray cleaning. In developing advanced painting/coating/cleaning systems, we discovered a need for more advanced design tools, which this project will develop.

information to identify existing and potential technology-development areas. We reviewed projects by others related to maintenance, repair, and overhaul modernization (automation) efforts. The depot-site visits helped reveal a need for technologies that facilitate automation of multiple processes on large aircraft structures. The reachability analysis tool and tools for automated path generation and registration are needed and will benefit broad process areas such as cleaning, coating, decoating, sealing, fastener removal/insertion, and inspection. Also, we began interacting with a major robot supplier for the aircraft industry; the interaction aimed at identifying technology-development needs from the supplier side. As a result of this interaction, we identified the reachability analysis tool as a core element for a key technology for large robotic-maintenance systems.

We improved software tools for design analysis and extended them to encompass greater breadth for eventual application as a generalized design tool. We extended the robot-system reachability analysis to more robot designs. We enhanced design tools for automated path planning and generation to incorporate those complex robot systems with redundant joint configurations. By employing advanced inverse-kinematic solution methods and optimization techniques, the prior design tools for automated path generation have been enhanced to provide greater flexibility and generality, as well as improved performance for complex robotic systems.

We selected a candidate process-technology need for demonstration using the analysis tools. The process of seam filling/caulking appears to be an important technology where automation has been hindered by lack of advanced technology. The process is representative also of a wide variety of in-contact processes that require model-based position analysis, and sensor-based workpiece characterization, robot-motion control, and process monitoring/feedback. We have begun to plan technology development to demonstrate this maintenance process.

The depot-site visits helped reveal a need for technologies that facilitate automation of multiple processes on large aircraft structures. The reachability analysis tool and tools for automated path generation and registration are needed and will benefit broad process areas such as cleaning, coating, decoating, sealing, fastener removal/insertion, and inspection.

Other Communications

Drotning, W. D., C. D. Loucks, W. J. Prentice, and P. A. Watterberg. 2001. "Flexible Automation for Aircraft Maintenance." *Proc. DMC 2001*, accepted.

26547

Distributed Autonomous Navigation

G. R. Eisler, D. D. Padilla, J. J. Carlson, C. L. Lewis

This project will develop a scientific framework for distributed navigation using swarms of vehicles. This framework will allow navigation with or without the availability of the global positioning system (GPS). Sandia's approach will extend Sandia's unique capabilities in terrain-aided navigation. In most terrain-aided navigation systems, altitude measurements from a single vehicle are correlated against a digital elevation map (DEM) to determine position. These solutions require many measurements over a substantial length of terrain, which is impractical for most land and water vehicles. To compensate, we will investigate the application of additional features such as terrain gradients and bearings to landmarks, along with the use of swarms of communicating vehicles. These features, combined with the relative three-dimensional (3-D) positions of each vehicle, will provide a geometric template that will be correlated against map data.

Another unique focus of this research will apply optimization techniques to determine optimal swarm formations for navigating through specific types of terrain and will study whether the formations should be adaptive. Variations in parameters such as terrain characteristics and map availability will determine factors such as feature selection and measurement, and the number of vehicles and their formation needed for an optimal solution.

Accomplishments include development of preliminary map-correlation algorithms and simulation environment, surveying a test-bed area to calibrate sensors and verify simulation models, comparing numerical dynamic programming and weighted-graph algorithms for computational efficiency in terrain-traversal-type problems, and demonstrating improved position estimation using terrain data from multiple vehicles with intermittent GPS coverage.

An initial simulation environment employs terrain elevation and slope to correlate, with the least possible vehicle motion, a collective of vehicles. The simulation allows trade-offs between positions on the terrain, numbers of vehicles, vehicle dispersal pattern, and relative-sensing errors. The general approach consists of inserting the vehicle contingent into an area where the system has map knowledge only and

Possible locations for a five-vehicle template on DTED data for terrain adjacent to Sandia's Remote Vehicle Range Facility.

Another unique focus of this research will apply optimization techniques to determine optimal swarm formations for navigating through specific types of terrain and will study whether the formations should be adaptive. Variations in parameters such as terrain characteristics and map availability will determine factors such as feature selection and measurement, and the number of vehicles and their formation needed for an optimal solution.

the ability to measure relative locations and altitude with respect to a lead vehicle. (We have assumed differenced, uncorrected GPS values.) Using this information for the vehicles locked in place as a template, we search the map by moving the template to cover all possible positions, then find the difference between measured relative altitude and the altitude computed using map-elevation data. Those template positions showing sum-of-error differences among the vehicles below a given threshold are accepted as possible vehicle-collective locations. Then a slope correlation is conducted to encompass all possible vehicle locations. We choose to move vehicles with the lowest or most negative correlated slope sums compared with kindred-vehicle locations, according to map data only. The simulation shows that vehicle placements, error thresholds on possible positions, and terrain content (i.e., elevation change) are critical in correlating position.

The research premise is that a cooperating system of vehicles may minimize some ambiguity of estimated vehicle positions. To help verify this idea, we decided to employ a well-characterized test-bed for algorithm verification and sensor calibration. Using the superior real-time kinetic (RTK) accuracy, we commissioned a GPS survey with a local firm to map the motocross course. We took approximately 25,000 points to generate a 1-foot interpolated map.

Choosing different relative-positioning sensors is key to implementing the proposed algorithms. Baroaltimeters and direction antennas are candidate technologies to determine elevation and bearing; however, for relative vehicle-to-vehicle distance, current component-search efforts reveal a lack in the accuracy and comprehensiveness versus that which GPS affords. As a result, we propose investigating the integration of distributed Kalman estimation with degraded-navigation solutions from pseudoinertial measurement to localize position.

The major project segments are position estimation/localization and mission planning/execution. When position is assessed, the contingent must move to expedite a given mission. Our university collaboration has generated path-planning algorithms for the mission segment. Currently, we are comparing dynamic programming based on a nonuniform-grid approach and weighted-graph algorithms on the basis of computation speed and comprehensiveness for modeling the important aspects of multivehicle traversals.

... we decided to employ a well-characterized test-bed for algorithm verification and sensor calibration. Using the superior real-time kinetic (RTK) accuracy, we commissioned a GPS survey with a local firm to map the motocross course. We took approximately 25,000 points to generate a 1-foot interpolated map.

26548

Obstacle Detection for Autonomous Navigation

D. D. Padilla, F. J. Oppel, III, M. W. Scott, M. R. Muguira, J. J. Carlson

This project will develop a mathematical framework for obstacle detection. Sandia expects the framework to help solve many complex obstacle-detection problems critical to successful autonomous navigation. One project goal is to characterize sensing requirements for physical characteristics of obstacles, vehicles, and terrain. For example, a specific vehicle traveling at a specific velocity over a specific terrain requires a sensor with a certain range of detection, resolution, field of view (FOV), and sufficient sensitivity to specific obstacle characteristics. In some cases, combinations of sensors may be required to distinguish between different hazardous obstacles and benign terrain. In our framework, the problem will be posed as a multidimensional, multiple-hypothesis, pattern-recognition problem. Features will be extracted from selected sensors that allow hazardous obstacles to be distinguished from benign terrain and other types of obstacles. A weighted-nearest-neighbor decision model will fuse feature measurements to minimize classification errors. In addition, classical estimation theory will provide the framework for estimating obstacle characteristics such as position and size.

Another project goal is to characterize different terrain classes for positive (e.g., rocks, trees, fences) and negative (e.g., holes, ditches, drop-offs) obstacles. The density of various hazards per square kilometer will be statistically quantified for different terrain categories (e.g., high desert, ponderosa forest, and prairie). This quantification will reflect the scale or size and mobility of different vehicle types. The trade-offs between obstacle detection, position location, path planning, and vehicle-mobility capabilities will also be characterized.

Our work focused on developing a theoretical and robust framework for obstacle detection. Principles of classical decision and estimation theory provided a mathematical basis. Part of this framework includes an architecture for both sensor- and control-algorithm development. The architecture defines standard data structures

This project will develop a mathematical framework for obstacle detection. Sandia expects the framework to help solve many complex obstacle-detection problems critical to successful autonomous navigation.

including a local, vehicle-based, occupancy grid and a global, world-based, occupancy grid. Using the architectural framework, we implemented an ultrasonic obstacle-detection system that uses commercially available sensors and are porting it to the AutoNav platform (HAGAR).

A major portion of our work involved the characterization of obstacles, terrain, and sensing requirements. The density of various obstacles was statistically quantified for different terrain categories. This quantification is intended to reflect the scale, or size, and mobility of different types of vehicles. Another major effort involved the investigation and evaluation of different sensor technologies for obstacle detection. The performance of conventional ultrasonic sensor was greatly enhanced with algorithms developed to process the raw echo return signal. Structured light technology proved to provide an efficient, eye-safe, obstacle-sensing capability in subdued lighting. We investigated techniques for extending the application of structured light to bright, sunlit environments.

We evaluated two scanning laser radar (LADAR) systems and one scannerless LADAR. One scanning system, the Acuity Range Sensor, shows significant potential. We also evaluated the potential for using offboard sensors (i.e., not on the robot) using a state-of-the-art LADAR terrain-mapping system. We also investigated the application and capabilities of stereo vision. One system (Digiclops) provides real-time 3-D images and has potential advantages compared to the active, laser-based systems. We also investigated the potential for an acoustic, phased-array imaging system. We successfully simulated the acoustic-imaging sensor and began developing a prototype array to validate our simulation results.

A major portion of our work involved the characterization of obstacles, terrain, and sensing requirements. The density of various obstacles was statistically quantified for different terrain categories. This quantification is intended to reflect the scale, or size, and mobility of different types of vehicles.

28775

Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications

T. S. Luk, T. R. Nelson

High-peak spectral-brightness coherent x-ray sources would allow implementation of powerful new spectroscopic-imaging modalities and nonlinear interactions in the multikilovolt spectral region for condensed matter and plasmas. Lasing in this regime would be useful for x-ray harmonic generation, protein crystallography, x-ray diffraction (XRD) of materials, radiographic testing, and next-generation backlighters and igniters for fusion experiments. Recent experimental measurements at the University of Illinois–Chicago point to coherent x-ray production using the combination of relativistic self-focused propagation and high-field multiphoton excitation of gaseous hollow atoms using a femtosecond-Terawatt-ultraviolet (UV) laser. Enhanced emission features in the excited atomic-charge states (xenon [Xe]) generated in the interaction exhibit evidence of line-narrowing and gain ($g_L \sim 40/\text{cm}$) with a spectral brightness exceeding $10^{31}/\text{s}(\text{mrad})(\text{mm})^2$ per (.1%BW). This project seeks to confirm evidence of x-ray lasing and to match the electron-density profile, guided-mode characteristics, and plasma dispersion to optimal target design for x-ray production and emittance. Theoretical analysis will model the relation between self-focused spatial confinement and atomic-field ionization producing x-ray flux.

This project seeks to confirm evidence of x-ray lasing and to match the electron-density profile, guided-mode characteristics, and plasma dispersion to optimal target design for x-ray production and emittance. Theoretical analysis will model the relation between self-focused spatial confinement and atomic-field ionization producing x-ray flux.

We performed calibrated spectroscopic-x-ray diagnostics to characterize the x-ray properties of the self-focused channel in Xe formed by a Terawatt-UV-femtosecond laser. Preliminary evidence leads to the conclusion that hollow-atom ionization in a self-trapped plasma channel is a model system that closely represents ideal conditions sought for multikilovolt amplification. The confluence of these phenomena, namely (1) nonlinear propagation in plasma resulting from relativistic charge-displacement self-channeling, and (2) direct selective inner-shell multiphoton excitation, can create unprecedented conditions for power compression. Estimates of the gain and brightness were derived from spatially resolved spectral data. Observations are consistent with the theoretical properties of a dielectric

waveguide in which guided x-ray modes in the channel are self-organized by matching of the group velocities for the exciting UV and x-ray pulses. The ability of the plasma channel to guide amplified x-rays in a preferred spatial mode will automatically confer spatial coherence to the generated x-ray emission. We characterized the guided x-ray modes by independent variation of the electron density and dispersion and showed them to support chirp-pulse compression in the waveguide. Future experiments will probe on- and off-axis temporal profiles of the x-ray gain on a single-shot basis.

The ability of the plasma channel to guide amplified x-rays in a preferred spatial mode will automatically confer spatial coherence to the generated x-ray emission.

34487

Atmospheric Plasma Applications

T. J. Renk

High-density, high-energy atmospheric plasmas offer unique opportunities for application to national needs, including energy conversion using high-pressure magnetohydrodynamics (MHD)-generating devices for compact, high-power-density generators; surface processing and decontamination for advanced manufacturing; surface decontamination for environmental and emerging threat applications; high-efficiency lighting; and plasma-control surfaces for aerospace vehicles. High-density plasmas offer unique characteristics for revolutionary capability enhancements, including microsecond response, production of effects at an extended distance away from the source, and electrically activated, immediately deactivated, and high localized energy densities. These applications are directly related to Department of Energy (DOE) missions for advanced manufacturing, mitigating material-aging effects for stockpile stewardship, surface processing and decontamination for hazardous and radioactive contaminants, and response to emerging national threats. Detailed understanding of the ionization process and plasma characteristics is essential to optimization for specific applications. The work in this project is a theoretical and experimental benchmarking of the production, control, and optimization of high-pressure plasmas. Sandia will base the modeling and analysis on IPROP, APC, EMPHASIS, and QUICKSILVER codes, which are presently available. We will focus experimental effort on a small set of benchmarks to verify the accuracy of the IPROP and APC codes in the low-voltage electron-beam regime and to validate plasma density predictions. A 200 kV electron beam experiment at Sandia will be relevant for benchmarking the key plasma parameters. We will extrapolate to energy-conversion and surface-processing applications of interest. This work enhances Sandia's capabilities by developing new modeling capability with high-energy-density plasmas. These improvements will be applicable to future pulsed-power development, advanced simulator design and development, and new high-power-density generating capability.

These applications are directly related to Department of Energy (DOE) missions for advanced manufacturing, mitigating material-aging effects for stockpile stewardship, surface processing and decontamination for hazardous and radioactive contaminants, and response to emerging national threats. ...

This work enhances Sandia's capabilities by developing new modeling capability with high-energy-density plasmas. These improvements will be applicable to future pulsed-power development, advanced simulator design and development, and new high-power-density generating capability.

Creating and sustaining plasma in the atmosphere can be accomplished with a number of sources, such as corona discharge, low-voltage arcs, or electron beams. In general, the energy expended for each electron created from the source is about 35 eV per plasma electron. The plasma lifetime is determined by competing chemistry effects, the most prominent effects being electron attachment and recombination. Attachment is the process by which an electron becomes attached to a neutral molecule to create a relatively long-lived negative ion. Two- and three-body processes dominate. Recombination is the process by which electrons are recombined with positive constituent ions to once again form neutral molecules. Again, two- and three-body processes govern recombination.

Reaction rates for the principal processes can be found in the literature. Calculation of plasma formation is then a matter of modeling beam passage through the gas, combined with the appropriate formation and decay rates for electrons in the gas.

Sandia used two simulation codes to analyze this problem: the LSP and APC codes, which were developed and benchmarked originally in the Charged Particle Beam Program. Both of these codes have air-chemistry-reaction calculations as an integral part of the analysis and produce temporal and spatial distributions. Simulation results show a good degree of self-consistency between the codes and good agreement with a limited amount of time-averaged and spatially averaged data from literature.

Results indicate that beam energy on the order of 100 keV is adequate to produce plasma volumes of the proper extent for material-processing applications, with an extended range in air on the order of 20 cm in length and width of more than 10 cm.

Calculation of plasma formation is then a matter of modeling beam passage through the gas, combined with the appropriate formation and decay rates for electrons in the gas.

34488

Feasibility Study on Fire-Suppression Properties of the Sandia Decon Foam

C. V. Williams

Sandia developed a nontoxic, noncorrosive aqueous foam with enhanced physical stability for the rapid mitigation and decontamination of chemical and biological warfare (CW/BW) agents. Please see Website (<http://www.nwmp.sandia.gov/SNLdecon/>).

A range of methods including systems that yield desirable properties for fire-suppression foams can deliver the Sandia foam. Although the foam's effectiveness against CW/BW agents is well established, the additional capability of being a fire suppressant would provide a dual-use capability. If the Sandia foam can suppress and control fires, the foam could significantly enhance the level of protection for critical nuclear weapon facilities, and suppression systems could now provide the additional protection of decontamination and CW/BW-agent removal.

Class A and Class B fires were set according to ASTM (American Society for Testing Materials) Standards. The Class A tests are conducted on wood-cribs constructed of 2-by-4 kiln-dried spruce or fir lumber. The Class B tests are conducted in pans containing commercial-grade heptane.

Class A fires were conducted according to ASTM Standards D4442-92. The Class A tests were conducted on wood-cribs constructed of 2-by-4 kiln-dried spruce or fir lumber. The cribs were constructed of interlocking layers, as shown in the chart on the next page.

The wood cribs are ignited using a 2-minute burn of commercial-grade heptane. The cribs were allowed to burn for at least 8 minutes prior to attempts to extinguish the fire.

Two versions of the foam based on the Sandia formulation were tested: DF-100 (the original formulation) and the commercial equivalent of DF-100 with a surfactant used in firefighting foams.

We conducted two Class B fire tests. Neither formulation was effective against the Class B fire.

Extinguishing of Class B fires is important because terrorists use petroleum products as accelerants. (Consider the September 11 attack.) We identified a nontoxic surfactant.

Although the foam's effectiveness against CW/BW agents is well established, the additional capability of being a fire suppressant would provide a dual-use capability. If the Sandia foam can suppress and control fires, the foam could significantly enhance the level of protection for critical nuclear weapon facilities, and suppression systems could now provide the additional protection of decontamination and CW/BW-agent removal.

Future work includes addition of this surfactant to DF-100 and testing for CW/BW and fire-suppression capability.

Five Class A fire tests were conducted:

- 2 ea Crib 20-A
- 1 ea Crib 30-A (192 wood members)
- 2 ea Crib 40-A (224 wood members)

Both formulations are effective in extinguishing the Class A fires.

We demonstrated fire-suppression capability of the Sandia Decon foam, DF-100, for Class A fires.

We demonstrated fire-suppression capability of the modified commercial product based on the Sandia decontamination foam.

We identified a surfactant that shows promise in being effective against Class B fires and is compatible with the Sandia decontamination formula.

We demonstrated fire-suppression capability of the modified commercial product based on the Sandia decontamination foam.

Classi- fication	#/Wood members	Trade size/length wood members/ mm	Arrangement of wood members in crib
20-A	160	38x89x1581	10 layers of 15 on edge, one top layer of 15
30-A	192	38x89x1895	10 layers of 18 on edge, one top layer of 10 flat
40-A	224	38x89x2213	10 layers of 21 on edge, one top layer of 14 flat

34489

Feasibility Study for Improved Less-Lethal Weapons

R. P. Toth

In the Department of Energy (DOE) mission to ensure safety and security of nuclear weapons, DOE security forces operate in urban environments with large numbers of civilians. Consequently, DOE security forces (in common with military missions in peacekeeping and civil riot control) need weapons that reversibly incapacitate with minimal lasting effects. The cache “nonlethal weapons” is a misnomer, insofar as mortality and morbidity statistics from experience in the Middle East and Northern Ireland clearly contradict that premise.

Conventional less-lethal weapons for peacekeeping missions are of two types: kinetic weapons such as rubber bullets for blunt trauma, and nonkinetic weapons such as sticky foam and tear-gas to immobilize or incapacitate. Blunt trauma routinely kills and maims. Sticky foam limits friendly-force movement and leaves a major clean-up problem. Tear-gas is deadly in closed spaces and causes long-term ocular as well as pulmonary injury.

The weapons needed for DOE security forces, military peacekeeping, civil riot control, and so forth should cause temporary and reversible disability. Ideally, the effects should be controlled via a reliable, dose-response relationship that could be varied over range and degree of incapacitation as the weapon is deployed.

This new class of weapons could act by chemical or physical means. The Geneva Convention enters the discussion insofar as chemical and blinding weapons are prohibited. The weapon of choice for urban use would appear to be acoustic because of low cost, adaptable operational concepts, a wide safety margin, and controllable exposure conditions for range and effect.

Acoustic weapons for this purpose would not simply be a loud noise, but would be designed to interfere with postural reflexes via vestibular effects. The mechanism of action could be biphasic pressure changes at the inner ear to mimic rapid head movements, to induce nystagmus and ataxia, and to upset postural controls.

The weapon of choice for urban use would appear to be acoustic because of low cost, adaptable operational concepts, a wide safety margin, and controllable exposure conditions for range and effect.

This project reviews candidate technologies for less-than-lethal weapons and selects one that offers the best possibility for temporary and reversible incapacitation. The technologies reviewed were those described in the DoD Joint Nonlethal Weapons Program (JNLW). The technology categories received were acoustic, biotechnical, chemical, electromagnetic (EM), mechanical, and optical.

Others have identified eye damage as the most frequently mentioned major concern as a weapon-effects failure. This began with blunt trauma (mechanical) and certainly will feature prominently in chemical, optical, and EM NLW. Eliminating these traumas leaves biotechnical and acoustic as the remaining technologies. Biotechnical methods include behavior-altering drugs, malodorants, and biological products such as acids, enzymes, and toxins. Sandia rejected these because of unpredictable dose-response curves and dose distributions that may vary by 100:1 with present methods of dispersion.

The selected technology was acoustic. Established NLW effects for this technology are diversionary devices (flash-bang), blast-wave (overpressure) effects, and high-intensity sound and infrasound. We found all of these to be unsatisfactory. The first and third do not incapacitate, but merely distract. Furthermore, accommodation to that distraction is not only possible but rapid. The second may incapacitate, but blast overpressure requires explosives or propellants and carries a significant risk of conversion to lethal effects by window breakage. The last mechanism, infrasound, may incapacitate; but these effects are largely anecdotal unless inconveniently long-exposure durations are employed. We concluded, therefore, that a new acoustic mechanism is needed.

Acoustic methods do offer the advantage that lethality is virtually impossible. A new mechanism of action affecting the inner ear offers the best promise for reversible and temporary incapacitation. Vestibular effects may be that mechanism. Bipedal posture and locomotion may be modeled as an inverted pendulum. The zone of stability is narrow, a cone of about 15°. Thus, it is sensitive to disruption.

Posture is maintained by a complex integrative network of sensors (chiefly in the inner ear) and effectors (spinal and leg muscles) mediated by the extra-pyramidal motor system and cerebellum. Sandia will exploit vestibular disinformation to destabilize postural reflexes. In this way,

Acoustic methods do offer the advantage that lethality is virtually impossible. A new mechanism of action affecting the inner ear offers the best promise for reversible and temporary incapacitation. Vestibular effects may be that mechanism. Bipedal posture and locomotion may be modeled as an inverted pendulum. The zone of stability is narrow, a cone of about 15°. Thus, it is sensitive to disruption.

reversible loss of posture, nausea, nystagmus, and disorientation are possible through acoustic pathways.

The equipment needed for this destabilization must produce rapidly alternating pressure waves at the junction of the cochlear and vestibular systems—namely, the *fenestra ovalis*. The acoustic signal needed is a pulse packet. The generator choices are explosive and electrical. We selected electrical means for generation of the acoustic impulse since electrical generation offers the possibility of useful repetition rate and freedom from difficulties of handling explosives or propellants. We designed an acoustic impulse generator with a large-bore (6-inch ID [inner diameter]) stainless-steel pipe terminated at one end with a breech plate and an impedance-transforming conical taper at the other end. The impulse was generated by a high-voltage (40 kV) discharge between titanium electrodes. The 40 kV was produced by a two-stage Marx bank charged to 20 kV. The generator comprises a capacitor-charging power supply, a pair of carborundum-charging resistors, a pair of gas switches, a pair of balancing resistors, and a trigger network.

Initial measurements with microphones yielded a peak sound pressure level (SPL) of 174 dB at 3 m. Subsequent measurements with a blast probe indicated peak SPL of 198 dB. Marx diagnostic circuits suggest an erection time of approximately 50 to 100 ns and a discharge time of approximately 200 ns. Discharge peak current is approximately 4 kA.

The acoustic signal needed is a pulse packet. The generator choices are explosive and electrical. We selected electrical means for generation of the acoustic impulse since electrical generation offers the possibility of useful repetition rate and freedom from difficulties of handling explosives or propellants.

34490

Feasibility Study for 5x Enhanced Energetic Materials

L. M. G. Minier

A large energy-release gap ($\sim 10^9$ calories/g) exists between conventional and nuclear energetic materials (EMs). Types of advanced EMs are perceived to span this gap. Evolutionary advanced EMs are modified conventional explosives that provide 1.2 to 1.5 more power than the current best performer, HMX (1,3,5,7-tetranitro-1,3,5,7-tetraazacyclooctane). Novel advanced EMs, such as nanostructured materials and all- or high-nitrogen (N) solids, are estimated (quantum-mechanical models) to provide 2 to 10 times more power than HMX. Exotic materials such as Fermi liquids (10^3 more power than HMX) and nuclear isomers (10^6 more power than HMX) are examples of advanced EMs that may exist in the distant future.

Sandia is focusing on the evolutionary and novel advanced EMs, as these are likely the advanced EMs of the near future (5 to 10 years). This small, yet significant, increase in power and performance can provide incredible advantages. For example, a weapon and delivery system can be miniaturized and still provide the same or an enhanced lethality. Improved performance would allow for directional-detonation waves and sustained reactions at the high temperatures and pressure that may be experienced by high-speed penetrators.

To address the development and threat posed by advanced EMs, an active partnership between the Department of Defense (DoD), the Department of Energy (DOE), academia, and relevant industrial partners needs to be formed and nurtured to help provide an awareness and a foundation for others in the U.S. to build needed programs to address issues related to advanced EMs.

Our efforts are tied to the EM community and will help to build partnerships outside of Sandia and seed awareness and investments into understanding the science and development of advanced EMs. Most important, the efforts from this project will be used to assess, guide, and develop the ability to synthesize and formulate advanced EMs at Sandia.

Sandia is focusing on the evolutionary and novel advanced EMs, as these are likely the advanced EMs of the near future (5 to 10 years). This small, yet significant, increase in power and performance can provide incredible advantages.

The following summarizes our findings and recommendations:

- High-nitrogen (N) EM and nanoscale technologies that form nanoscale aluminum (Al) (ingredient to some advanced propellants) are currently being worked on in the United States. The high-N compounds and nanoscale technology are likely the best investment of advanced EM when addressing advanced and miniaturized components. Achieving an advanced EM that performs five times greater than HMX in the near future will be difficult; two times greater power is a more reasonable goal. We set up potential collaborations with both the Los Alamos (LANL) and Lawrence Livermore (LLNL) national laboratories' synthetic groups to provide guidance in developing syntheses.

- We have the computational tools and the people available to probe the interactions occurring on a mesoscale; mesoscale interactions must be investigated to develop a complete understanding of the new materials and to understand how the materials can be applied to systems, especially when miniaturized.

- We conducted several interviews with DOE, DoD, and other agencies (government and private), and conducted literature searches regarding advanced EM research.

Achieving an advanced EM that performs five times greater than HMX in the near future will be difficult; two times greater power is a more reasonable goal. We set up potential collaborations with both the Los Alamos (LANL) and Lawrence Livermore (LLNL) national laboratories' synthetic groups to provide guidance in developing syntheses.

34694

Ultrahigh-Temperature Ceramic Material Research

R. E. Loehman, S. J. Glass, A. E. Hodapp, Jr., J. J. Mecholsky, Jr.

To sustain the Department of Energy's (DOE's) capabilities and technology base for nuclear weapon design and production, materials with improved properties are needed for thermal protection of next-generation reentry vehicles. Sharp leading edges and nosetips on these vehicles will have to withstand exposure to high temperatures ($> 2200^{\circ}\text{C}$) and severe thermal cycling in both neutral and oxidizing environments. These extreme conditions will require materials that possess superior oxidation resistance, low creep, and excellent thermal-shock properties.

Ultrahigh-temperature ceramics (UHTCs) are promising candidates for such applications. ZrB_2 and HfB_2 and composites of those ceramics with SiC are two particular families of UHTCs that are currently under development for sharp leading edges. These ceramics are appealing because their melting temperatures are 3245°C for ZrB_2 and 3380°C for HfB_2 , and because they may form protective, oxidation-resistant coatings in use.

HS and ZS composites are potential materials for high-temperature, thermal-shock applications such as for components on reentry vehicles. To establish material constants necessary for evaluation of *in situ* fracture, Sandia examined bars fractured in four-point flexure using fractographic principles. We determined the fracture toughness from measurements of the critical-crack sizes and the strength values and established the crack-branching constants to use in forensic fractography for future in-flight tests. The fracture toughnesses range from about $13 \text{ MPam}^{1/2}$ at room temperature to about $6 \text{ MPam}^{1/2}$ at 1400°C for ZrB_2 - SiC composites and from about $13 \text{ MPam}^{1/2}$ at room temperature to about $4 \text{ MPam}^{1/2}$ at 1400°C for HfB_2 - SiC composites. Thus, the toughnesses of either the HS or ZS composites have the potential for use in thermal-shock applications. Processing and manufacturing defects limited the strength of the test bars. However, examination of the microstructure on the fracture surfaces shows that the processing of these composites can be improved. There is potential for high-shock conditions if the processing and handling are controlled.

We determined the fracture toughness from measurements of the critical-crack sizes and the strength values and established the crack-branching constants to use in forensic fractography for future in-flight tests.

We made the following conclusions and recommendations:

(1) The toughnesses of $\text{ZrB}_2\text{-SiC}$ and $\text{HfB}_2\text{-SiC}$ composites are sufficient for use in a thermal-shock environment.

(2) Processing and manufacturing defects limited the strength of the bars.

(3) Processing of the materials can be improved.

(4) Fractographic principles can be used in future failure analysis of *in situ* tests of components from these materials.

(5) Wider test bars should be fabricated in any future flexure tests to be able to measure the mirror boundaries and obtain the necessary constants for forensic analysis.

(6) Careful attention should be given to the alignment and rotational flexibility of any four-point flexure test setup to avoid errors in loading.

(7) Thermal-shock tests such as quenching in water or oil or continuous-wave (CW) laser irradiation should be planned to evaluate the thermal-shock capabilities.

For example, quench tests into oil or water are a possibility. Water is not as good as oil because of the difficulty in knowing the heat-transfer coefficient for quenching into water. If a CW laser with a capability of at least 1 kW/cm^2 , and a spot size of at least 1 cm^2 is available, then irradiation of a thin (i.e., less than 1 cm) plate of the material can be a quick test of the thermal-shock resistance of the materials.

Water is not as good as oil because of the difficulty in knowing the heat-transfer coefficient for quenching into water. If a CW laser with a capability of at least 1 kW/cm^2 , and a spot size of at least 1 cm^2 is available, then irradiation of a thin (i.e., less than 1 cm) plate of the material can be a quick test of the thermal-shock resistance of the materials.

Refereed

Mecholsky, J. J., Jr. 2001. "Reliability of UHTC Materials for Next-Generation Space Vehicles." Sandia Technical Report SAND2001-2896, Sandia National Laboratories, Albuquerque, NM.

Mecholsky, J. J., Jr. 2001. "Report on the Fracture Analysis of $\text{HfB}_2\text{-SiC}$ and $\text{ZrB}_2\text{-SiC}$ Composites." Sandia Technical Report SAND2001-2898, Sandia National Laboratories, Albuquerque, NM.

34696

Modeling Building Air Flow for Autonomous Robotic Agents

D. A. Schoenwald, C. E. Hickox, Jr., R. O. Griffith, J. E. Brockmann

Many targets exist that harbor weapons of mass destruction (WMD), command-and-control centers of adversaries, and enemy-training and materiel-storage locations. These targets are difficult to penetrate using conventional weapons and forces. Such facilities may be underground, deeply buried, hardened, or otherwise difficult to access by conventional forces.

This project examined the concept of a collective of autonomous unmanned agents that can penetrate such a facility and deny access to it or render the facility inoperative through the dispersal and subsequent ignition of sources for fuel/air explosives. Sandia's goal in this project was to do a feasibility study on deploying such a collective.

The project delivered a computer simulation of robotic vehicles in a building that traverse the hallways, spread out uniformly through the building, release a fuel aerosol, and detonate the fuel to create a fuel/air explosive.

We based the simulation on an UMBRA simulation of vehicles setting up a communication network in the building by spreading out while still maintaining radio-frequency (RF) contact. We used many of the same principles in the fuel/air explosive simulation. We analyzed the flow matrix of the forward air-flow distribution of the building with a memo detailing the approach used. We used a zonal model to avoid the prohibitive computational expense of finite-element (FE) models. A concentration model can then use this flow matrix to compute the concentration of a contaminant anywhere in the building.

Further work will study the optimal strategies that the autonomous vehicles would employ to disperse the fuel inside a building and when to detonate it.

The project delivered a computer simulation of robotic vehicles in a building that traverse the hallways, spread out uniformly through the building, release a fuel aerosol, and detonate the fuel to create a fuel/air explosive.

34697

Investigation of Advanced Digital-Video Compression for the Control of Robotic Platforms

J. J. Harrington

This study explored the possibility of compressing digital-video data to permit teleoperation of robotic vehicles using low-data-rate communication channels. Most robotic vehicles used at Sandia rely on separate radios to convey analog video, command, status, and one-way differential global positioning system (GPS) correction data. This implies that three radios and their respective antennae must be located and powered on the robot. Although combining differential GPS signals into the command link is straightforward, analog video must first be digitized, which raises the bandwidth dramatically.

Current data-compression algorithms exist to lower digital-video bandwidth compared with analog video, but whether sufficient compression can be attained to use cell-phone or other narrow-bandwidth radios for the purpose of robotic control is not clear. To help answer this question, we evaluated wavelet compression and the Strathclyde-compression transform (SCT). Lossy compression techniques result in spatial and temporal degradation of video imagery, which has a negative impact on the ability to teleoperate robotic vehicles. Therefore, this study used metrics gathered from performance data to assess and compare different compression algorithms.

We addressed three robotic-application areas in this study. The first pertained to the teleoperation of a mobile land vehicle where we used two test approaches. One approach involved an electric-powered, remote-controlled car. This technique was later replaced with a video race-car game. A second application focused on the control of a robotic manipulator. Finally, we considered a reconnaissance-type scenario.

One test conclusion was that video-compression algorithms have progressed to the point of providing viable alternatives to analog-video transmission. Communication links that convey data from 9600 bps to 28.8 kbps permitted teleoperation of mobile platforms from 30 percent to 75 percent of the same performance level achieved with full-

We addressed three robotic-application areas in this study.

The first pertained to the teleoperation of a mobile land vehicle where we used two test approaches. One approach involved an electric-powered, remote-controlled car. This technique was later replaced with a video race-car game. A second application focused on the control of a robotic manipulator. Finally, we considered a reconnaissance-type scenario.

bandwidth video. We controlled manipulators at 90 percent of the performance level using 9600 bps compared to regular video. Single images were compressed to 8000 bits and yielded sufficient detail to accomplish many reconnaissance-type missions.

The compression algorithm used to gather most of this information was based on the SCT, which was freely supplied to Sandia on a temporary license for evaluation by Essential Viewing Systems Limited. SCT is a vector-based algorithm and uses a codebook of primitive images that it compared to a portion of the image to compress. Upon finding a good match, only a reference of the codebook word was transmitted, which resulted in compression of the original information. Initially, we matched and transmitted 32-by-32-pixel blocks; that resulted in a poor representation of the actual image because of differences between the codebook and block. However, as time permitted, these initial blocks were subdivided by four, and each was individually matched in the codebook. This brought out more of the original image detail. This process continued until blocks were divided into very small areas that resulted in a detailed image. The algorithm spent most of its resources in areas that had the most difference between the last transmitted codebook words and the actual image. This implied that resources were spent where motion occurred and that compression also took place from one frame to another.

SCT was implemented only in software and required full use of a 200 MHz Pentium computer or equivalent. (This fact will restrict its use in power-constrained systems.) The algorithm was not tolerant to bit errors, so some form of channel coding was required. During this study, we tried one form of wavelet compression, but it required at least 800 kbps to transfer the compressed image; this was far beyond the capabilities of many useful data links. However, Motorola demonstrated a wavelet technique that, from initial observations, exceeded the compression capabilities of SCT. This version was tolerant to bit errors and contained fewer artifacts than SCT. Regardless of which technique proves best, advanced video-compression techniques will definitely enhance Sandia's robotic initiatives and extend our applications into many new areas.

The algorithm spent most of its resources in areas that had the most difference between the last transmitted codebook words and the actual image. This implied that resources were spent where motion occurred and that compression also took place from one frame to another.

34698

Microfuze

L. S. Weichman, S. B. Rohde, M. J. Retter, S. M. Harris, W. C. Curtis, III

The primary mission of the weapon fuze is to provide system-safety enablement and subsequent control of weapon detonation events. Within this architecture, the fuze integrates inputs from various environmental sensors and, if the preset conditions for weapon function are realized, supplies the required detonator stimulus. Present electronic fuzes found in Department of Energy (DOE) and Department of Defense (DoD) applications are based on bridge-wire or foil detonator technologies that require a high-voltage, high-current stimulus and consequently occupy volumes from several to tens of cubic inches. Furthermore, traditional fuzing safety within these architectures is predicated on the “uniqueness” offered by the electrical stimuli required to initiate the main charge detonators.

Evolving mission scenarios for future DOE and DoD weapon platforms will soon outpace the capabilities of today’s fuzing technologies. Targeting buried assets and meeting tomorrow’s battlefield engagements will require advanced fuzing architectures characterized by “intelligent” function under multiple, high-G impacts. Achieving increased fuze functionality in a size constraint implicit with high-G survivability implies development of novel system architectures, incorporating new concepts in munitions safety and the realization of miniaturized component suites based on emerging processes and technologies. Establishing a sound technical foundation and effective integration of Sandia’s expertise in safety enablement, microdetonics, silicon (Si) surface micromachines (SMMs), microsensors, and semiconductor electronics will prove essential in achieving the required revolutionary advancement in the fuzing community.

We will direct the ultimate realization and embodiment of the proposed science and technology foundation toward accomplishing the required safety and fuzing functions on a single substrate, or “chip.” If successful, the “fuze-on-a-chip” would give future system designers the tools necessary to address next-generation fuzing functions in an environment currently not obtainable by today’s technology.

The initial focus and resultant technical direction are based on obtaining a firm grasp of future DoD/DOE fuzing

Establishing a sound technical foundation and effective integration of Sandia’s expertise in safety enablement, microdetonics, silicon (Si) surface micromachines (SMMs), microsensors, and semiconductor electronics will prove essential in achieving the required revolutionary advancement in the fuzing community.

community needs and identifying technological “gaps” or “enablers” evident along that path to fruition. To that end, we (1) completed a preliminary survey of application, requirements, and “state-of-the-art” developments, (2) developed safe and arm (S&A) architectures, concentrating team focus, highlighting critical component needs, enabling technologies, and identifying process compatibility issues, (3) completed a prototype S&A “slider” design and submitted the component for fabrication, (4) fabricated and began initial characterization of microinitiators, igniters, and energetic materials, and (5) developed focused activity for future work.

Our early surveys reflect the desire for cost-effective fuzing applications that can initiate multiple detonation events and reliably function under high-G environments without compromising munitions safety. Based on these initial contacts, we sharpened our focus on the development and hardware realization of S&A architectures based on the use of primary explosives and a corresponding low-voltage (less than 50 V) stimulus. From our preliminary S&A architectures, we identified “generic” functions and components that form the essence of our fuze architectures and have further prioritized their role in the realization of the microfuze concept.

We initiated the development and integration of safety-critical mechanisms required for interruption/control of the explosive train with microinitiators/igniters and energetic materials (EMs). Our initial activities examined the suite of available microelectromechanical systems (MEMS) fabrication technologies (surface-micromachining, LIGA [acronym for the German term *Lithographie, Galvanoformung, und Abformung*, for lithography, electroforming, and molding], and bulk Si etching) for processing issues associated with monolithic integration of the initiator and/or direct deposition of high explosives and metal flyers on the S&A “shuttle.” This study revealed a number of formidable sequencing and processing compatibility issues with the desired level of component integration and available EM sets. As an example, for safety and mitigation of facility contamination, it is highly desirable, if not essential, to apply the high-explosive materials as the final processing step. However, applications of the EMs on SMM components that were previously released introduced significant requirements for masking critical MEMS features or otherwise controlling contamination of the mechanism. If the EMs are deposited prior to mechanism release, we found that subsequent MEMS processes and acid etches were incompatible with the targeted

Our early surveys reflect the desire for cost-effective fuzing applications that can initiate multiple detonation events and reliably function under high-G environments without compromising munitions safety. Based on these initial contacts, we sharpened our focus on the development and hardware realization of S&A architectures based on the use of primary explosives and a corresponding low-voltage (less than 50 V) stimulus.

EMs. Consequently, the best short-term candidate for integrating explosives is hand assembly, and the long-term prospect is identifying and utilizing high explosives, reactive agents, or thermites compatible with the vapor deposition and MEMS fabrication processes (i.e., mask or release). As a short-term goal, we determined the optimum explosive train dimensions, identified a compatible packaging strategy, and completed the design of a bulk Si S&A device capable of receiving and shuttling a small “cup” containing a lead charge of CL-20.

We fabricated and received a number of microbridge configurations and EMs. We received microbridges comprising aluminum (Al), nickel (Ni), platinum (Pt), palladium (Pd), and Si (semiconductor bridges [SCBs]) and are currently characterizing them for flyer dynamics and electrical performance. EMs received include CL-20 pellets configured in 0.040-inch and 0.125-inch diameters for subsequent evaluations as lead and booster materials. In addition, we procured reactive bridge (titanium/boron [Ti/B]) microdetonators and are investigating automotive “air-bag” technologies to address process compatibility issues and mass manufacturing (i.e., cost) concerns.

We fabricated and received a number of microbridge configurations and EMs. We received microbridges comprising aluminum (Al), nickel (Ni), platinum (Pt), palladium (Pd), and Si (semiconductor bridges [SCBs]) and are currently characterizing them for flyer dynamics and electrical performance.

Refereed

Collins, M. V., L. E. S. Rohwer, A. D. Oliver, M. G. Hankins, and D. A. Hirschfeld. 2001. “Optimization of Anodic Bonding to MEMS with Self-Assembled Monolayer (SAM) Coatings.” Paper presented to the SPIE Micromachining and Microfabrication Conference, San Francisco, CA, 21–25 October. SAND2001-2398C.

Other Communications

Hoke, D., and S. Harris. 2001. “Advanced Research and Development on Microelectromechanical-Based Fuzing and Microenergetics.” Paper presented to the Defense Manufacturing Conference, Las Vegas, NV, 26–29 November.

Oliver, A. D., M. V. Collins, L. E. S. Rohwer, and J. S. Custer. 2001. “Wafer-Scale Hermetic Micropackages for Surface Micromachines.” Paper presented at Workshop on Microsystems Technology and Applications, Huntsville, AL, July.

35008

Intelligent Projectile Development*D. W. Kuntz, A. E. Hodapp, Jr., S. M. Kohler*

To enhance the Department of Energy's (DOE's) capabilities and technology base for countering the proliferation of weapons of mass destruction (WMD), a new system approach is being considered that would employ electromagnetic (EM) launchers (coil-guns) to accelerate intelligent projectiles. These projectiles would be designed to operate at velocities of 2–6 km/sec and to maneuver independently through the atmosphere to attack high-valued targets (hard and deeply buried targets, and ballistic or cruise missile threats). This system approach requires advancement of a variety of technologies to ensure successful design and development of the intelligent projectiles. This effort is intended to scope these technology needs in two specific areas: electronic component hardening and miniaturization and lightweight thermal protection system (TPS) design. Sandia will collaborate with the U.S. Navy and Defense Advanced Research Projects Agency (DARPA) to better understand the nature of these challenges and to improve our ability to field such a system designed to counter these national security threats.

The objective of the intelligent projectile project was twofold: (1) an evaluation of current and future TP materials that can effectively meet requirements for a sea-level launch of a long-range projectile at velocities ranging from 2.0 to 6.0 km/sec, and (2) an evaluation of survivability and miniaturization potential for navigation, guidance, and control (NG&C) components that are exposed to gun and resulting flight environments. The concern is the ability to constrain the volume of NG&C and TP subsystems to provide payload volume sufficient for meeting lethality and/or cargo-carrying requirements. A 3- to 5-year forecast was desired to establish goals for development of a projectile.

We conducted a study to determine packaging requirements for NG&C and TP subsystems. We ignored acceleration and electromagnetic interference (EMI) hardening of electronic components because we determined early on that solutions were available. We used a slender 155 mm diameter, 60 kg projectile and a 98 mm, 15 kg scaled derivative for the study. We obtained several important results, listed below, from the analysis.

The objective of the intelligent projectile project was twofold: (1) an evaluation of current and future TP materials that can effectively meet requirements for a sea-level launch of a long-range projectile at velocities ranging from 2.0 to 6.0 km/sec, and (2) an evaluation of survivability and miniaturization potential for NG&C components that are exposed to gun and resulting flight environments.

(1) NG&C systems for 155 mm and larger projectiles can likely be developed from modified off-the-shelf components.

(2) A significant reduction in NG&C system volume is required to package the long-range 98 mm projectile.

(3) Ultrahigh-temperature ceramic (UHTC) materials have application as shape-stable nose tips for velocities up to 3.0 km/sec (maximum velocity for 98 mm projectile); W is good to 2.5 km/sec.

(4) Internally insulated (RTV silicone) bare steel walls can be used as the projectile outer surface for launch velocities up to 3.0 km/sec.

(5) Improvement in the performance of internal insulation is desired to increase payload volume.

(6) Current ablative nose tip (carbon-carbon) and heatshield (carbon phenolic) materials can provide TP for projectiles launched at 3.0 to 6.0 km/sec.

Results of our survey indicate that UHTC materials and solutions for NG&C miniaturization could be available within the next 3 to 5 years. Solutions for acreage TP and high-velocity nose tips seem to be restricted to use of previously developed/currently available materials.

Results of our survey indicate that UHTC materials and solutions for NG&C miniaturization could be available within the next 3 to 5 years.

39016

Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat

W. T. Gutierrez, J. D. Rogers, D. E. Salguero, M. W. Kniskern, K. T. Stalker, W. H. Ling

Potential adversaries are increasingly using hard and deeply buried facilities to prevent critical military capabilities from being held at risk by the United States' current weapons and delivery means. There are thousands of hard and deeply buried military facilities within states that are given consideration in U.S. military planning. A small but significant fraction of these facilities are associated with weapons of mass destruction (WMD) or with their delivery means as well as other functions. It is widely believed that effective defeat of hard and deeply buried targets (HDBTs) may be achieved by including advanced and emerging technologies in new weapon systems.

This project supported an element of the national effort that focuses technical expertise on the critical and growing problem posed by HDBTs. An excerpt from Senate Report 105-189, which accompanies the National Defense Authorization Act for Fiscal Year 1999, highlights the importance of this issue and the benefits of Sandia's technical involvement: "The committee commends the Under Secretary of Defense for Acquisition and Technology and the Assistant Secretary of Energy for Defense Programs for beginning to develop ways to use the Nation's investment in science and technology at the Department of Energy National Laboratories for national defense goals in the post-Cold War era. The committee notes that in response to the recommendations contained in the National Defense Authorization Act for Fiscal Year 1998, the Departments of Defense and Energy have agreed to collaborate in areas that are key to addressing the challenge of defeating the hard and deeply buried targets that shelter the war-making capabilities, including weapons of mass destruction, of rogue states."

We completed a thorough review and documentation of relevant DOE technologies that may be useful in various ways to defeat HDBTs.

We also completed a careful examination of the hard targets using a systems approach that characterizes common

It is widely believed that effective defeat of hard and deeply buried targets (HDBTs) may be achieved by including advanced and emerging technologies in new weapon systems. ...

This project supported an element of the national effort that focuses technical expertise on the critical and growing problem posed by HDBTs.

approaches and seeks to identify common vulnerabilities that could be exploited.

We pursued tasks associated with an assessment of a group of special-interest targets. We met with the appropriate country working group, the Army Greybeard Study group and the Defense Advanced Research Projects Agency (DARPA) Greybeard study group. After finding a few nuggets of information that were helpful, they also found some unexpected problems. There currently is little focus on “fixed sites” in the country of interest (current interest is in watching maneuver units), and thus the studies were not as exhaustive as might have been expected.

Other Communications

Gutierrez, W. 2001. *Report to Congress Directed by the Floyd D. Spence National Defense Authorization Act for FY2001*, October.

Energy and Critical Infrastructures

The Energy and Critical Infrastructures investment area seeks to enhance the surety (safety, security, and reliability) of our nation's energy and other critical infrastructures and to provide security against malevolent attacks. Surety is defined as confidence that a system will perform in acceptable ways in both intended and unintended circumstances. The Energy and Critical Infrastructures area invests in research with the potential to impact national security applications through (1) creation of unique nuclear energy concepts and products, (2) improved surety of information systems and the power grid, (3) advanced technology in areas such as energy efficiency and clean energy, and (4) improved manufacturing processes that will enhance product quality and minimize environmental impact.

Computer networks at Sandia and elsewhere are currently protected by network intrusion-detection (NID) systems. These systems monitor networks for activities that indicate a possible attack or misuse of the information system. However, current NID systems work only down to the Internet Protocol level. Data and control flows below that level are not protected. The "Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks" project is developing an

ATM intrusion-detection system that monitors the signaling flows associated with a variety of ATM protocols to determine if insider or outsider attacks are being conducted against the ATM network. A patent disclosure has been submitted.

26550

Solid-State Ballistic Chemical Sensors*A. H. McDaniel, R. C. Hughes, R. J. Bastasz, S. A. Casalnuovo*

Sandia will develop a new type of solid-state detector, sensitive only to hydrogen (H) and H-containing moieties and derived from a palladium (Pd)-based metal-insulator-semiconductor (MIS) device. We will create a chemically selective sensor impervious to poisoning, oxidative interference, and H-induced metal-phase transitions—all of which severely limit similar technology. This goal will be accomplished by direct injection of protons into the detector. We plan to incorporate small-scale ionizer structures into Pd-MIS devices that have been coated with an inert material, such as gold (Au), which acts as an energetic-particle filter. The ionizer produces atomic and molecular ions, which are then accelerated into the solid filter. Selectivity results from different transmission factors for various ions through the filter and is a function of parent molecular weight, pass energy, and ionization cross section. We call this technique ballistic chemical sensing because ion-kinetic energy is an essential parameter in the detection process.

We will create a chemically selective sensor impervious to poisoning, oxidative interference, and H-induced metal-phase transitions—all of which severely limit similar technology. This goal will be accomplished by direct injection of protons into the detector.

We designed, fabricated, and characterized first- and second-generation capacitors for (1) nascent capacitance-voltage (C-V) response, (2) sensitivity to molecular H and carbon monoxide (CO), and (3) sensitivity to ionized H. Design flaws in first-generation structures processed using electron-beam evaporation through shadow masks necessitated the migration to the complementary metallic-oxide semiconductor (CMOS). Devices exhibited ideal C-V characteristics, with process yields at about 20 percent.

Activities related to experimental design and device characterization occurred. Prior to initiating experiments, a data-acquisition platform had to be developed to enable dynamic, real-time acquisition of electrical response under ion-beam irradiation, neutral-gas exposure, and thermal cycling. We investigated three methods to monitor the response of the Pd-metal-oxide semiconductor (MOS) capacitors: (1) tracking the change in capacitance by sweeping the entire C-V curve, (2) tracking the bias voltage associated with a fixed capacitance in the flat-band region, and (3) integrating the area under the C-V curve. Method 2 proved more sensitive and less susceptible to thermal interference

than Method 3; and Method 2 required less post processing with a faster frequency response than Method 1.

In addition to developing data-acquisition capabilities, we revised the experimental test stand so individual dies could be mounted onto a high-vacuum manipulator apparatus without additional packaging. This eliminated a concern associated with *in situ* heating during characterization. A second vacuum chamber was designed and fabricated for more extensive investigation of sensor response to hydrocarbons using a commercial ion source and for experiments to evaluate the efficiency of field-emitter arrays as a source of energetic particles.

We exposed both bare and Au-coated sensors to various gas mixtures containing H₂, CO, and oxygen (O₂) at 50 Torr and 373 K to gauge the ultimate sensitivity of the devices, the reactivity of sensor surfaces (bare and coated), as well as to test for any H leakage into the Au-coated sensor—that is, leakage through voids in the overlayer or by other means. The extent of the C-V shift indicates that the capacitors are very sensitive to molecular H and that O₂ exposure decreases the time required to flush atomic H from the device. In addition, coexposures of H₂ and CO indicate that CO blocks the admission of H atoms into the structure. The coated Pd-MOS devices may need to be redesigned to mitigate background from molecular H₂.

The root mean square (rms) voltage traces (Method 3) have a Au-coated sensor during irradiation by an energetic-ion beam at various temperatures. We used a Colutron proton accelerator to produce monoenergetic, mass-analyzed, neutral-free H₃⁺ ions. Data verify the hypothesis that ballistically implanted protons can be detected with Pd-MOS capacitors, and that the relaxation of the device is governed by a thermally activated process.

Finally, Monte Carlo calculations have begun using the TRIM simulation code to predict transmission factors for energetic protons through prospective filter materials. Silicon nitride, titanium nitride, indium-tin oxide, and carbon are under consideration, with the ultimate goal of creating a layer material such that the implanted proton range varies strongly with kinetic energy.

We used a Colutron proton accelerator to produce monoenergetic, mass-analyzed, neutral-free H₃⁺ ions. Data verify the hypothesis that ballistically implanted protons can be detected with Pd-MOS capacitors, and that the relaxation of the device is governed by a thermally activated process.

10356

Varying QoS for Fixed and Mobile Networks

J. T. Michalski, J. D. Dillinger, T. D. Tarman, R. P. Tsang, J. P. Brenkosh, J. M. Eldridge

With the recent unprecedented growth of the global network, it has become imperative to provide an appropriate minimum level of communication performance for applications. This will become possible when all of the intermediate switches and routers support bandwidth guarantees in their queuing disciplines.

The approach to quality of service (QoS) for networks is dependent on three primary areas: (1) the application stream, (2) the marking and network level control of this stream, and (3) the identification and reservation of appropriate network resources for the stream.

Sandia's lab system is essentially a bandwidth broker system that provides signaling for distributive resource management applications that require Internet Protocol (IP) network QoS. The bandwidth broker system is an essential component for allowing distributed applications to share network resources while receiving a predictable level of network QoS. This bandwidth broker is composed of two primary parts: the policy decision point (PDP) and the policy enforcement point (PEP).

The PDP is responsible for downloading policy information so that each data flow on the network can be assigned a level of QoS. This is accomplished on the network devices through queuing scripts. The PEP is the component that resides on the network devices that provide the distribution of bandwidth for the application flows (i.e., routers and switches). The PEP communicates to the PDP through a signaling protocol called common open policy service (COPS). COPS is a simple query-and-response protocol used in a client/server mode to exchange policy information.

The queuing scripts that are resident on the network devices are responsible for identifying, marking, filtering, and policing the data that transverse the network. These scripts are designed to provide the appropriate profile for data transport across the network. The scripts are downloaded by the policy enforcement points to provide the implementation of an end-to-end QoS network.

Sandia's lab system is essentially a bandwidth broker system that provides signaling for distributive resource management applications that require Internet Protocol network quality of service.

We completed and implemented queuing filters that allow the QoS attributes to be mapped into network data flows.

We completed scripting code, using the differential service model (Diffserv) to define, mark, and police classification and scheduling for the LINUX router. This code defines two functions: first, it defines a route classifier used to identify and mark a flow with a unique identifier; and second, it maps marked data flows into a defined queuing discipline. The marked flow is then treated throughout the network according to the policy manager's definitions.

We completed an interface protocol to communicate QoS control information among network resource devices. We completed the communications interface protocol based on the COPS provisioning model, which comprises a PDP and a PEP. The PDP, which is located on a server, communicates with the PEP, which is located on the network routers. The PDP downloads to the PEP policy information consisting of the applications that will get preferential treatment. This policy is enforced by the PEP, which downloads the appropriate queuing scripts that implement the instructed policy.

To determine whether our lab approach could maintain its prioritizing flows of "QoS attributes" on a much larger network, we completed a software modeling project that allows the QoS components of our project to be mapped across an expansive network.

We created two scenarios within the model. The first scenario looks at priority queuing at the node level. It displays two router nodes implementing priority queues, then shows the resulting bandwidth utilization of pre- and post-queuing. The second scenario tracks an application flow across an expansive network and compares and contrasts the flow's attributes both with and without the use of priority queuing.

To determine whether our lab approach could maintain its prioritizing flows of "QoS attributes" on a much larger network, we completed a software modeling project that allows the QoS components of our project to be mapped across an expansive network.

10360

High-Surety SCADA for the Critical Energy Infrastructures

R. E. Carlson, M. C. Kidd, A. E. Bentley, C. L. Beaver, R. C. Patrick, J. E. Stamp, D. P. Duggan, R. G. Cox, J. M. Depoy, R. A. Sarfaty, J. J. Torres

The domestic critical energy infrastructures are a complex and interdependent network that is vital to the national security and social well-being of our nation. The control mechanisms for these infrastructures are often referred to as SCADA (Supervisory Control and Data Acquisition) systems. The President's Commission on Critical Infrastructure Protection has identified that the widespread and increasing use of SCADA for control of energy systems provides an increasing ability for an adversary to cause serious damage to the energy infrastructures. To meet the new infrastructure threats and requirements, not only must contemporary SCADA systems be able to report the infrastructure state with confidence, but they also need to measure the entire infrastructure, be robust in their communication, and be timely and optimal in their control. In addition, the SCADA must provide these services under adverse conditions. These are attributes that a SCADA system needs to enhance the surety (security, safety, and reliability) of the underlying infrastructure. In the first two years, the difficult aspect of this SCADA research was separating the role of standards from proprietary systems and discerning stable architectures from those that are likely to change significantly. With this understanding, we developed an intuition for how surety will influence the composite system that is SCADA. The fundamental problems in the third year are mapping SCADA into the High-Surety SCADA Specification (HSSS) and validating this architecture on the Sandia SCADA Test-bed (SST). The HSSS will ensure that Sandia becomes the "provider of choice" in this domain for technologically enhancing the surety of our national energy infrastructures. Validation of the HSSS on the Sandia SST will provide a differentiating aspect of this research that promises to be valued by both government and industry after the third year.

To meet the new infrastructure threats and requirements, not only must contemporary SCADA systems be able to report the infrastructure state with confidence, but they also need to measure the entire infrastructure, be robust in their communication, and be timely and optimal in their control infrastructures.

(1) We completed the development of the SST configuration.

(2) We developed an HSSS for the requirements developed in the TC 57 forum, implemented several security features of the HSSS on the SST, and demonstrated these features.

(3) We performed a Red Team analysis of the HSSS. The SST and key management test-beds are complete, and we are in the process of merging them. Red Team analysis will occur on a regular basis as the HSSS evolves.

The SST and key management test-beds are complete, and we are in the process of merging them. Red Team analysis will occur on a regular basis as the HSSS evolves.

10361

Agent-Based Mediation and Cooperative Information Systems

L. R. Phillips, H. E. Link, S. V. Spires, S. Y. Goldsmith

Agent-mediated information management is the most promising solution to the problem of integrating and accessing large legacy data stores and for utilizing networked information sources such as the Internet. Sandia has developed coalitions of agents that assist human users and other agents with cooperative information processing and execution of complex tasks. Sandia's Standard Agent Architecture II (SAA2) is a general-purpose development environment for constructing multiagent systems that assist a diverse set of users with knowledge-intensive tasks in a network environment.

Sandia has taken on the issues of cybersecurity as a research direction. Carnegie-Mellon University's (CMU's) RETSINA framework was used in proof-of-principle efforts involving intelligent software agents cooperating asynchronously to perform goal-directed registration tasks. The collaboration between CMU and Sandia has significantly enhanced Sandia's technology base and reputation in agent-based information systems. We developed agent-based mediation functions that enable interoperation and cooperative problem solving within agent complexes. By operating in the context of a "foreign" agent technology, we have been able to address and automate many complex tasks needed for intercommunication among different agent communities.

Sandia's agents currently examine the Internet packet stream for features known to be interesting as an outgrowth of the work by which different kinds of data streams are recognized. Our technical challenges involved the development of standards for knowledge- and data-sharing; ontological leveling of different knowledge bases; and representation, control, and enforcement of operational policy for complex systems.

This project significantly advanced the state of the art in cooperative information retrieval and operation, enabling the development and prototype deployment of an advanced information system for enterprise security monitoring. Future

The collaboration between CMU and Sandia has significantly enhanced Sandia's technology base and reputation in agent-based information systems. We developed agent-based mediation functions that enable interoperation and cooperative problem solving within agent complexes.

efforts may involve concurrent engineering, battlefield management, infrastructure modeling, and enterprise integration.

We accomplished our original goals and also can now provide several more advanced capabilities that are an outgrowth of the process. Our efforts are focused on cybersecurity rather than on commerce, which was our original focus. Many of the more complex cooperative processes for which we developed ontologies and that we can carry out involve such issues as sharing information securely, establishing distributed trust, modifying existing coalitions, and updating key shares—all issues that received minimal consideration at the time we developed our original research proposal.

Our most important accomplishment is an agent-based mechanism by which complicated cooperative behaviors known as *conversations* can be specified for SAF (Standard Agent Framework) agents, and the agents carry them out as appropriate. (The entire sensory universe of these agents is the information network to which they connect.) Under some circumstances, important elements of the conversation, such as the identity of the message sender, agreement among the participants as to the message contents, discovering the involvement of bad actors, and removal and addition of coalition members, can not only be known by the participating agents but also can be mathematically guaranteed and carried out successfully, even in the presence of adversaries.

In our previous work, we developed a relatively mature architecture, met our goals, and were ahead of schedule in some regards. In the process, however, we had become aware of several unforeseen issues. These issues were (1) the agents' need to deal with all inputs and act appropriately for every message, regardless of type, (2) the agents' need to accommodate new kinds of inputs dynamically, and (3) the agents' need for a declarative form of goal-achievement procedure rather than the static process descriptions currently in use. We were able to achieve all of these capabilities.

We implemented a “disambiguator” front end that is capable of rapidly classifying incoming messages and discarding those not instantly recognized. This significant self-protection mechanism is trainable, i.e., it learns to recognize new kinds of signals if it is provided with several labeled positive examples of the new signal type.

We accomplished our original goals and also can now provide several more advanced capabilities that are an outgrowth of the process. Our efforts are focused on cybersecurity rather than on commerce, which was our original focus.

Another important accomplishment is the development of a standardized, robust mechanism for establishing communication with humans. This mechanism is supplanted by recently implemented cryptographic protocols that guarantee successful procedural outcomes, even when some of the players are adversaries.

We recognized that we had accomplished adequate interspecies communication to support the security work. We began to refocus our efforts on a means to enable groups of agents to carry out complicated group communications acts for which the final information state could be guaranteed. This capability was needed for environments where adversaries might be present. We also recognized that the adversaries who penetrated our agent groups could prevent the success of friendly operations unless we implemented processes specifically designed to succeed even when penetrated. Most of our work, therefore, focused on realization of the necessary ontological and operational structures to enable us to specify these secure operations and have the agents carry them out.

Our agents are currently capable of complex interactive behavior with other agents and humans. Many of the existing behaviors are focused on conduct of operations that have provable outcomes with security consequences.

*We began to refocus our efforts
on a means to enable groups
of agents to carry out
complicated group
communications acts for which
the final information state
could be guaranteed.*

10362

Dynamically Self-Configurable Network Protocol

B. P. van Leeuwen, J. Espinoza, D. L. Harris, M. D. Torgerson

Nodal mobility leads to frequent network topological changes, which requires routes to be reestablished. The communication medium is a radio channel shared by many contending users. These ad hoc networks are of importance in the context of reliable information systems, tactical battlefield communications, antipersonnel landmine replacement communications, mobile robotic communications, and other distributed communication networks.

This project addresses the problem of adaptive message routing in a decentralized packet communication network with nodal mobility. With the rapid advances taking place in this area, the Sandia approach is to incorporate the necessary attributes of current research in protocols into a hybrid approach for ad hoc routing. This hybrid approach offers the greatest amount of flexibility by applying varying degrees of a link-state approach in combination with an on-demand approach to ad hoc routing.

The objective of our research is to investigate current routing and media-access algorithms and to develop a security approach to protect the control information that supports the networks' ability to self-configure communication topology dynamically. A major product will be a description of methods to secure the routing control plane and a description of the overhead impacts on the network. The security approaches will be applicable to networks having an initial random node distribution or containing mobile nodes.

Our research will take advantage of existing network protocols and components of protocols used in networking technologies, with a focus on minimizing the amount of control necessary since these nodes may be mobile and have limited life spans (e.g., be battery-operated). The research will describe methods of securing networks that have the described attributes. Efforts will include simulating a model network using the routing protocol with security approaches on the OPNET (operating network). We will characterize, evaluate, and optimize network performance (e.g., throughput and packet delay) for the described approaches.

The objective of our research is to investigate current routing and media-access algorithms and to develop a security approach to protect the control information that supports the networks' ability to self-configure communication topology dynamically. A major product will be a description of methods to secure the routing control plane and a description of the overhead impacts on the network. The security approaches will be applicable to networks having an initial random node distribution or containing mobile nodes.

Finally, our research will present a demonstration simulation and possibly demonstrate the developed protocol on an actual communication network.

Our recent accomplishments include incorporating into our simulation environment a hybrid approach for *ad hoc* routing. In addition, we developed a model to account for the system overhead impacts that cryptographic algorithms will have on network communications. We studied cryptographic algorithms and their implementations and mapped them to typical hardware implementations for a node in an *ad hoc* network. The mapping provided processing latency values and data packet length increase values that were incorporated into our simulations.

In addition, our work developed a method to examine the impacts of incorporating information assurance approaches at the link layer of the network protocol stack. Our activities extended a high-fidelity model of a Carrier-Sense Multiple-Access/Collision Avoidance (CSMA/CA) medium access approach to enhance our simulation capability. This provided the ability to examine the impacts of information assurance at the link layer under various scenarios and network configurations.

We developed simulations with these models to represent operational scenarios requiring information assurance. These simulations were run to determine the optimal protocol parameters and network performance under these optimal parameters. The simulations were critical to our efforts to identify the impacts of information assurance approaches under various application-layer traffic characteristics and movement parameters. The results have given us an ability to accurately determine the information assurance approach that best fits the application traffic, the network characteristics, node movement characteristics, and routing parameters.

Our research also identified several specific threats directed at the routing data of an *ad hoc* network. We addressed security issues that arise from wrapping authentication mechanisms around *ad hoc* routing data. We showed that this bolt-on approach to security may make certain attacks more difficult, but still leaves the network routing data vulnerable. We also showed that under a certain adversarial model, most existing routing protocols cannot be secured with the aid of digital signatures. Digital signatures are well known to come with a significant computational and

Our recent accomplishments include incorporating into our simulation environment a hybrid approach for ad hoc routing. In addition, we developed a model to account for the system overhead impacts that cryptographic algorithms will have on network communications. We studied cryptographic algorithms and their implementations and mapped them to typical hardware implementations for a node in an ad hoc network.

bandwidth overhead cost. So, it is crucial for system designers to understand what value, if any, is added to the system by the addition of digital signatures to secure routing information, and to understand the actual computational and bandwidth overhead costs.

We are completing two SAND reports to document the outcomes of our investigations, descriptions of the model and simulation development, and simulation results.

So, it is crucial for system designers to understand what value, if any, is added to the system by the addition of digital signatures to secure routing information, and to understand the actual computational and bandwidth overhead costs.

10388

Hybrid Processing of Measurable and Subjective Information in Surety Analysis

J. A. Arlin

Conventional systems-surety analysis is basically applicable only to data that are measurable or derived from a physical model. However, most analyses, including high-consequence system-surety analysis, must also utilize subjectivity. Considerable effort has been expended on analytically incorporating engineering judgment. For example, Dempster-Shafer theory establishes a framework in which frequentist probability and Bayesian incorporation of new data are subsets. Although both Bayesian and Dempster-Shafer methodologies allow judgment, neither derives results that can indicate the relative amounts of subjective judgment and measurable data in the results.

Most high-consequence systems have difficult-to-analyze features when assessed by conventional approaches. For example, in the Sandia nuclear weapons program, the probability that a weapon responds safely when exposed to an abnormal environment must be ensured to meet a specific requirement. There are also nonprobabilistic Department of Energy and Department of Defense requirements (e.g., for determining the adequacy of positive measures). The type of processing required for these and similar situations transcends conventional probabilistic and human factors methodology.

The methodology developed in this project provides a hybrid-mathematics-based process that allows tracking of the degree of subjective information in the output, thereby providing more informative as well as more appropriate results. The results can be applied to these types of situations and, in general, to the surety assessment of high-consequence systems. The results can also improve the information currently provided to decision makers. Objective inputs are derived in a conventional manner; the subjective inputs are derived from the combined engineering judgment of experts in the most appropriate fields. Both types of inputs are processed mathematically in a hybrid structure. In addition to providing output constituents (including portrayal of uncertainty) corresponding to each input type, their individual contributions to the resultant uncertainty are determined and provided as part of the output information.

... in the Sandia nuclear weapons program, the probability that a weapon responds safely when exposed to an abnormal environment must be ensured to meet a specific requirement. ...

The type of processing required for these and similar situations transcends conventional probabilistic and human factors methodology. ...

The methodology developed in this project provides a hybrid-mathematics-based process that allows tracking of the degree of subjective information in the output, thereby providing more informative as well as more appropriate results.

Our current efforts are aimed at final tool development and combining the tools developed in previous years into a hybrid end-product software package, Coordinated Objective/Subjective Mathematically Enhanced Tools (COSMET). We have achieved the following:

(1) The multiobjective decision tool is nearly complete. This tool will provide a possibilistic weighting of factors contributing to a decision (e.g., judgment of the robustness of a system-surety program). The intent is also to contribute to systematically understanding the various decisions that can be reached by the people who all have access to the same information.

(2) We completed the COSMET software package.

(3) We completed one of the most formidable tasks in the project, the hybrid combination methodology. This methodology involves all tools developed during this project, as well as possibilistic and probabilistic hybrid analysis.

(4) We developed a final workshop and received a conference commitment from the Society for Risk Analysis.

This tool will provide a possibilistic weighting of factors contributing to a decision (e.g., judgment of the robustness of a system-surety program).

Refereed

Cooper, J. A. 2001. "Decision Analysis for Transportation Risk Management." *Special European Safety and Reliability Issue on Risk Decision and Policy*, accepted.

Cooper, J. A. 2001. "Hybrid Safety Analysis Using Subjective and Objective Components." *Proc. 3rd International Conference on Intelligent Processing and Manufacturing of Materials 1* (Vancouver, BC, Canada, 29 July–3 August): 238–245.

Cooper, J. A., and J. M. Covan. 2001. "Decision Support for Strategic/Tactical Risk Management." *Proc. 19th International System Safety Conference 1* (Huntsville, AL, 10–14 September): 117–125.

Covan, J. M., and J. A. Cooper. 2001. "Maintaining Surety for High-Consequence Systems." *Proc. 19th International System Safety Conference 1* (Huntsville, AL, 10–14 September): 113–117.

D'Antonio, P. E., J. A. Cooper, and R. D. Hartman. 2001. "A Risk-Based Systemic Approach to Reducing Air Transportation Accidents." *Proc. 19th International System Safety Conference 1* (Huntsville, AL, 10–14 September): 92–103.

Other Communications

J. A. Cooper. 2001. "Hybrid Mathematics Aid for Safety-Relevant Decisions." *Proc. 2001 European Safety and Reliability Conference*, accepted.

10393

Production Surety and Disruption Vulnerability Analysis

D. A. Jones, C. A. Phillips, W. E. Hart, G. F. List, L. K. Nozick, M. A. Turnquist

The goal of this project is to develop new capabilities for improving planning under uncertainty, focusing on production and transportation surety in the nuclear weapons complex (NWC). Sandia's focus is on optimization models for resource-constrained planning, with emphasis on production and transportation operations. Explicit recognition of uncertainties in the solutions to these models leads to creation of plans that are less vulnerable to disruption and more robust under a variety of unknown future conditions. Furthermore, the expected degree of compliance with specified performance standards can be quantified.

During the project, we explored different mathematical formulations of resource-constrained planning under uncertainty, and we created prototype models for neutron generator (NG) production planning and Office of Transportation Safeguards resource planning. A major accomplishment was the development of mathematical formulations that allow explicit evaluation of trade-offs between the expected performance of a resource-constrained system and the degree of confidence that the solution will satisfy specified minimum criteria (solution robustness). The technology resulting from this effort will have impact across several strategic business units (SBUs), including Energy and Critical Infrastructures and Nonproliferation and Materials Control. Because effective modeling of the NG facility and Transportation Safeguards Division (TSD) operations has a direct impact on the nuclear weapons stockpile, we believe this research also provides direct benefit to the Nuclear Weapons SBU by providing more robust production and transportation plans.

The objective of planning under uncertainty is to identify solutions that perform well under a variety of unknown future circumstances. We concentrated on three types of uncertainty that are important in the NWC:

The goal of this project is to develop new capabilities for improving planning under uncertainty, focusing on production and transportation surety in the nuclear weapons complex. ... A major accomplishment was the development of mathematical formulations that allow explicit evaluation of trade-offs between the expected performance of a resource-constrained system and the degree of confidence that the solution will satisfy specified minimum criteria (solution robustness).

- External (e.g., uncertain demands that the system must meet),
- Resource availability (e.g., unexpected breakdowns in equipment), and
- Resource productivity (e.g., uncertain yield from a manufacturing process step).

These uncertainties create doubt about whether a specified set of resources will be able to produce a required set of outputs. If the output requirements are not met, some cost is attached to the failure. This cost is not necessarily in monetary terms. In any given system, there is some penalty for not meeting the demands placed on the system. One way to reduce the likelihood that the requirements will not be met is to acquire spare resource capacity. This clearly has a cost (usually monetary) and optimization attempts to find a solution that minimizes total cost (i.e., balancing the costs of not meeting demands against the costs of carrying excess capacity). A measure of risk can be defined from the probability distribution of the unmet system requirements.

We created an approach to robust optimization that provides explicit insight into the trade-off between the expected cost of operating the system and the degree of risk incurred. This trade-off is essential in assessing system vulnerability and to making informed decisions that balance risk against cost.

The benefits of our research in planning under uncertainty include increased efficiency, reduced vulnerability to disruption, and increased ability to meet schedules with high confidence.

Our efforts led to a series of insights about structuring the process of planning under uncertainty and methods for expressing uncertainties in optimization models. These methods, in turn, led to the development and implementation of useful and more robust models. The robust optimization formulation allows for explicit evaluation of trade-offs between expected performance under uncertain conditions, and the degree of confidence in meeting specified minimum performance levels. This trade-off is essential in assessing system vulnerability. Advances in robust optimization are critical to advancing the state of the art in planning under uncertainty and are particularly critical to many application domains including the NWC. Although we focused our research on NWC production and transportation modeling,

Our efforts led to a series of insights about structuring the process of planning under uncertainty and methods for expressing uncertainties in optimization models. These methods, in turn, led to the development and implementation of useful and more robust models. The robust optimization formulation allows for explicit evaluation of trade-offs between expected performance under uncertain conditions, and the degree of confidence in meeting specified minimum performance levels. This trade-off is essential in assessing system vulnerability. Advances in robust optimization are critical to advancing the state of the art in planning under uncertainty and are particularly critical to many application domains including the NWC.

this approach can be extended to other areas where the explicit consideration of planning under uncertainty will provide more robust decisions.

Refereed

Jones, D. A., M. A. Turnquist, C. R. Lawton, L. K. Nozick, G. F. List, and B. Wood. 2001. "Robust Optimization for Fleet Planning Under Uncertainty." *Transportation Research, Part E* (Exeter, England: Pergamon Press), in review.

Jones, D. A., M. A. Turnquist, E. A. Kjeldgaard, C. R. Lawton, L. K. Nozick, G. F. List, and B. Wood. 2001. "Logistics Planning for Environmental Remediation Under Uncertainty." *Computers and Operations Research* (New York, NY: Elsevier Science, Inc.).

Nozick, L. K., M. A. Turnquist, and G. F. List. 2001. "Project Management Under Uncertainty, with Applications to New Product Development." *Proc. IEEE Engineering Management Conference*, accepted.

Other Communications

Jones, D. A., M. A. Turnquist, and E. A. Kjeldgaard. 2001. "Decision Support for Alignment Planning: An Approach Based on Project Management Under Uncertainty." Sandia Technical Report, in review.

Jones, D. A., M. A. Turnquist, E. A. Kjeldgaard, C. R. Lawton, L. K. Nozick, G. F. List, and B. Wood. 2001. "Production Surety and Disruption Vulnerability Analysis." Sandia Technical Report, in preparation.

10395

Source Code Assurance Tool*J. Espinoza, P. L. Campbell*

This project was designed to advance the state of the art in software surety science. The goal of the project is to develop a software application, the Source Code Assurance Tool, that would assist an analyst or team of analysts in the assessment of a system that is either software or nonsoftware.

Because any system of reasonable size contains a range of technologies, the assessment of such a system typically requires a team of analysts, each of whom bring to the table a unique body of expertise. For efficiency's sake, the responsibility for various assessment activities is often partitioned. One member is given responsibility for the mechanical aspects of the system, another for physical security issues, a third to address the software, a fourth to analyze the networking, and yet others to consider electrical engineering problems and handle system issues. While this arrangement is efficient from a project management viewpoint, it introduces problems into the assessment of the system. Each analyst may understand his own portion of the system very well, but may not understand how behaviors associated with his portion of the system play together with the rest of the system to deliver undesirable outcomes. For this reason, there is a need for a tool that will help analysts answer the following questions of other analysts:

- What happens if my portion of the system delivers this kind of event to your portion of the system?*
- How could your part of the system deliver this kind of event to my part?*

Currently, assessments do not have tools to help answer the intrapartition questions. This set of needed tools requires an even larger context within which it can operate so that the analysts can collectively study the entire system. Moving to this point is one goal of Sandia's Source Code Assurance Tool project.

We developed a prototype of the Source Code Assurance Tool using commercial-off-the-shelf software: a slicing engine, CodeSurfer from GrammaTech, and the graph editor and layout toolkits from Tom Sawyer Software. Bringing both tools together into a new tool allows the user to construct and slice across what we call a system, since their communication is not through labeled sections of memory.

The goal of the project is to develop a software application, the Source Code Assurance Tool, that would assist an analyst or team of analysts in the assessment of a system that is either software or nonsoftware. ...

Currently, assessments do not have tools to help answer the intrapartition questions. This set of needed tools requires an even larger context within which it can operate so that the analysts can collectively study the entire system. Moving to this point is one goal of Sandia's Source Code Assurance Tool project.

The user constructs a graph of the system using the graph editor and then slices it using CodeSurfer. We also submitted two technical advances: a Visual Programming Tool (VPT) and Range Value Propagation (RVP)–Approximate Computing.

VPT solves two problems. First, it increases the human-machine bandwidth. Second, it enables a programmer to show program structure. One problem with current programming languages is that they are text-based. Text is one-dimensional (1-D) and, therefore, linear and sequential. These characteristics limit the bandwidth of the channel. Pictures, on the other hand, are 2-D. For the human, pictures can provide more information more quickly than text alone. Our tool, VPT, enables programmers to express functionality via graphs, which are inherently 2-D. This capability moves programming from text to pictures, enabling a larger channel between the programmer and the machine. At the same time, VPT enables the programmer to show program structure at a larger scale than is convenient with existing tools. The programmer can recursively nest collections of graph nodes to indicate this higher-level structure. The meaning of these higher-level nodes is program-dependent, so there are no type names for the nodes at these levels.

RVP addresses the problem of range analysis on a system. Program slicing identifies the statements and functions that define or use the value of a particular variable or variables (for simplicity, we assume that a slice tracks a single variable); however, it tells the analyst nothing about the values that the variable can assume. Without actually executing the system, the analyst cannot determine the relationship between input values and output values. RVP addresses this problem. RVP requires a statement in a new language, defined as part of RVP, for each component (defined almost immediately). This statement maps the inputs of that component to its outputs. (For ease of explanation, we assume that a component is a function, in which case RVP will require a statement for each output statement and return statement in the function.) The new language provides a way of computing on ranges of values. The analyst provides a range of values for each input statement in the slice. The analyst can then ask that RVP compute the intermediate and final ranges. This provides approximate computation. The analyst can use RVP to better understand the relationship between input and output. To preserve tractability, we consider ranges consisting of only

We also submitted two technical advances: a Visual Programming Tool (VPT) and Range Value Propagation (RVP)–Approximate Computing. VPT solves two problems. First, it increases the human-machine bandwidth. Second, it enables a programmer to show program structure.

integer values. Future work may consider ranges of real values, vectors, matrices, and strings.

This advance is based on the observation that program slices are components connected by arcs that carry tokens that, in the case of data flow, have values. What is the benefit if those values are used in the slice? RVP is an answer to that question. An important assumption of range analysis is that the output is a continuous function of the input. Range analysis allows an analyst to determine the range of values for a given component in a slice based on the range of values for a previous component in the slice. That is, the analyst can say, "If x can take on this range of values, then y can take on that range of values." The approach allows for dynamic analysis, so that the analyst can answer the question, "What range of values can y take on if x takes on this new range of values?" Note that RVP may not be as precise as execution. Its value is that it provides insight into input/output behavior.

This advance is based on the observation that program slices are components connected by arcs that carry tokens that, in the case of data flow, have values. What is the benefit if those values are used in the slice? RVP is an answer to that question.

Other Communications

Campbell, P. L., and J. Espinoza, Jr. 2001. "Source Code Assurance Tool: An Implementation." Sandia Technical Report SAND2001-3094, Sandia National Laboratories, Albuquerque, NM (October).

Campbell, P. L., and J. Espinoza, Jr. 2001. "Visual Structure Language." Sandia Technical Report SAND2001-1093, Sandia National Laboratories, Albuquerque, NM (October).

Craft, R. L., P. L. Campbell, and J. Espinoza, Jr. 2001. "Source Code Assurance Tool: Preliminary Functional Description." Sandia Technical Report SAND2001-3092, Sandia National Laboratories, Albuquerque, NM (October).

10718

A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems

T. J. Gardner, S. B. Margolis, R. P. Manginell, R. Kottenstette, D. L. Mowery

The development of a small, stable on-chip flame/combustor (i.e., a microcombustor [μ Combustor]) would permit the adaptation and translation of several very useful macroscopic devices into the microsystem domain: on-chip flame ionization detectors (microFIDs [μ FIDS]), microreactors, micropropulsion, energy conversion, and, importantly, heating and thermal management. The argument for the use of on-chip combustive heating is compelling. The energy density of butane (including storage cylinder mass) is 50 times that of the best high-output batteries (LiMnO_2 nonrechargeable). Thus, a tiny fuel tank could replace several bulky batteries in hand-held microanalytical systems like the μ ChemLab™ and would supply a μ Combustor for efficient heating of essential components.

Sandia is developing a μ Combustor as a basis for thermal-energy management in microsystems as well as in the development of new μ FID devices for use for intelligent process control of energy-intensive processes (e.g., reactors, distillation columns, dryers in the petrochemical industry). Stable flames are difficult to achieve on a small scale, due to enhanced heat loss arising from large surface-to-volume ratios. Catalytic materials provide a natural surface-based method for flame ignition and stabilization of the reaction zone. Further stabilization can be achieved by the use of a thermally isolating membrane as a support for microfabricated fuel injectors. One key enabling technology for the μ Combustor will be the development of active and stable (deactivation-resistant) catalyst materials (likely supported precious metal catalysts) for the combustion of different feedstocks, ranging from hydrocarbons (e.g., butane or propane) to hydrogen. Deposition of these catalysts in a high-surface-area form on relevant platforms (i.e., resistively heated filaments) to facilitate rapid combustion may also be required for device fabrication.

The development of a small, stable on-chip flame/combustor (i.e., a microcombustor would permit the adaptation and translation of several very useful macroscopic devices into the microsystem domain: on-chip flame ionization detectors, microreactors, micropropulsion, energy conversion, and, importantly, heating and thermal management. ... Sandia is developing a μ Combustor as a basis for thermal-energy management in microsystems as well as in the development of new μ FID devices for use for intelligent process control of energy-intensive processes (e.g., reactors, distillation columns, dryers in the petrochemical industry).

We achieved our milestone associated with designing, fabricating, and testing a prototype μ FID device, although considerable improvements are still necessary to demonstrate μ FID performance and feasibility. Despite problems reproducing a self-sustaining microcombustion process in the new polyether ether ketone (PEEK) fixture, this fixture has been useful in identifying micro-hotplate failure modes at elevated temperature. These unanticipated problems have also delayed the development of an alternate μ Combustor device designed to operate with hydrocarbon fuels. Because of our problems reproducing the microcombustion process, we returned to our initial experimental μ Combustor fixture and initiated an experimental matrix to understand the fundamental phenomena involved in μ Combustor performance and the effects of a wide range of process variables. Early results from these experiments again demonstrated a self-sustaining microcombustion process, with the added improvement of successful reignition of the μ Combustor device following termination of the combustion process. This result has important ramifications for μ FID sensing applications in microsystems (e.g., μ ChemLabTM) since these detectors need to be cycled on and off almost indefinitely in service.

Catalyst evaluation efforts in a conventional microreactor show the sensitivity of thin-film platinum catalyst materials to deactivation under oxyhydrogen combustion conditions. Promising catalyst activity and stability were shown for a supported catalyst layer deposited onto silicon nitride (SiN), indicating that significant potential improvements in device performance could result if appropriate processing techniques can be identified to deposit such films. Modeling results provided a theoretical basis for the extension of flame extinction limits due to the presence of a catalytic surface.

This project was selected for presentation at the program review of the Department of Energy Headquarters. Because of our success in demonstrating a self-sustaining μ Combustor, as well as the wide-ranging potential applications of on-chip combustion, we recently filed a Sandia Technical Advance.

We achieved our milestone associated with designing, fabricating, and testing a prototype μ FID device, although considerable improvements are still necessary to demonstrate μ FID performance and feasibility. .. Early results from these experiments again demonstrated a self-sustaining microcombustion process, with the added improvement of successful reignition of the μ Combustor device following termination of the combustion process. This result has important ramifications for μ FID sensing applications in microsystems (e.g., μ ChemLabTM) since these detectors need to be cycled on and off almost indefinitely in service.

Refereed

Margolis, S. B., and T. J. Gardner. 2001. "Extinction Limits of Nonadiabatic, Catalyst-Assisted Flames in Stagnation-Point Flow." Sandia Technical Report SAND2001-8172, Sandia Technical Laboratories, Albuquerque, NM (February).

Mowery, D. L., T. J. Gardner, G. C. Frye-Mason, R. Kottenstette, R. P. Manginell, and S. B. Margolis. 2001. "Development of a Novel On-Chip Catalytic Microcombustor Device." Paper presented to the 15th Annual Meeting of the Western States Catalysis Club, Provo, UT, 23 February.

Mowery, D. L., T. J. Gardner, G. C. Frye-Mason, R. Kottenstette, R. P. Manginell, and S. B. Margolis. 2001. "Development of a Novel On-Chip Catalytic Microcombustor Device." Paper presented to the 17th North American Catalysis Society Meeting, Toronto, Ontario, Canada, 8 June.

10725

A Micro-GC–Based Controller for Energy-Intensive Processes

F. Gelbard, D. A. Loy, G. C. Frye-Mason, D. R. Wheeler, R. P. Manginell, D. A. Schneider, R. Kottenstette, S. K. Showalter, G. R. Dulleck, Jr.

Intelligent sensors are not widely used to control drying and distillation processes in U.S. chemical and petroleum sectors. A reluctance to implement new, energy-saving technologies can be attributed to a lack of proven sensors that can adapt to a variety of complex processes and detect a wide variety of compounds within a single process. Currently, pilot-scale processes are empirically scaled to full-scale processes with safety factors added to meet quality control standards. Quantitative analytical testing is time consuming and not currently possible in real time. Drying and distillation in the U.S. chemical and petroleum sectors consume about 12 Quads of energy annually. Intelligent, real-time control-based, robust, configurable sensors with a wide dynamic range are needed to implement a science-based solution that can improve the process efficiency and decrease energy consumption. Research and development are required to meet this goal.

The focus of this effort is to develop a viable industry solution for science-based, real-time control of chemical and petroleum processes to increase process efficiency and to decrease energy consumption. Research and development will be required for sensor development, online calibration, data fusion, and system-integration architectures. Current research efforts on the μ ChemLab™ sensors will provide the fundamental platform for the microsensor-based system. Key sensor research elements will focus on identifying new absorbing materials and methods for coating the micro-gas chromatograph (mGC) column, online delivery of reference samples, investigating and implementing new front ends (such as valve matrices), identifying and implementing carrier-gas options and detectors, and developing a quantitative rather than qualitative output.

Sandia will integrate these elements into a workable prototype that can be used for intelligent real-time process control. We will use existing industry ties to ensure viability of the directions taken during the execution of this project.

The focus of this effort is to develop a viable industry solution for science-based, real-time control of chemical and petroleum processes to increase process efficiency and to decrease energy consumption. Research and development will be required for sensor development, online calibration, data fusion, and system-integration architectures. Current research efforts on the μ ChemLab™ sensors will provide the fundamental platform for the microsensor-based system.

- *mGC columns.* We developed and tested a micropacked GC column using research-grade materials obtained in small batches. The diameters of these materials are smaller than commercially available support materials. This column, packed with very small solid packing material, has demonstrated excellent separation of ethane, ethylene, methane, and acetylene. Since this unique support material is not commercially available, we devoted some amount of effort toward production of our own adsorptive phase in the sizes necessary to fit our current micropacked GC columns.

- *Thermal conductivity detectors.* Work proceeded on the use of our early preconcentrator filaments (thermally isolated on a silicon nitride [SiN] membrane) as potential thermal conductivity detectors. We performed these tests at the breadboard level with macro control and acquisition systems. The tests indicated proof-of-concept, but the system size used for testing is too large to be compatible with our chromatography package. We will work to create a detector of compatible size.

- *Preconcentrator sol-gel chemistry.* We characterized silica and silica-silsesquioxane sols used to prepare preconcentrator films. At issue was the stability of the sols over time: Did the polymeric species continue to grow even at 0°C and impact the preparation of preconcentrators? We used silicon-29 nuclear magnetic resonance (NMR) to characterize the standard sols and were able to show definite changes over time at temperatures above minus 30°C. For consistent, reproducible results, it is important for the sols to be kept at or below minus 30°C. We also prepared several sols with a phenylsilsesquioxane co-monomer to see if we could fabricate porous films with a more organophilic character. Characterization of porosity of such films by ellipsometry is not possible, so other avenues were explored, including testing as preconcentrators. We also synthesized a phenylene-bridged silsesquioxane monomer that we showed would retain porosity in bulk form regardless of polymerization conditions or processing. Preconcentrators coated with the sol-gel-processed, phenylene-bridged polysilsesquioxane showed no sign of improved performance. However, it was not possible to ascertain if the thin films were porous.

- *Thin-film characterization.* Due to the difficulties associated with characterizing the porosity in thin films used for preconcentrators, we overhauled and tested a commercial surface acoustic-wave (SAW) thin-film porosimeter with a variety of thin films. We tested the device with a variety of

Work proceeded on the use of our early preconcentrator filaments (thermally isolated on a silicon nitride [SiN] membrane) as potential thermal conductivity detectors. We performed these tests at the breadboard level with macro control and acquisition systems. The tests indicated proof-of-concept, but the system size used for testing is too large to be compatible with our chromatography package. We will work to create a detector of compatible size.

thin films based on well-defined silica colloids (Stober spheres) from which we can calculate the surface area based on film thickness and colloid particle diameter. However, we discovered that the instrument suffered from poor precision. Preliminary runs with a Sandia-built thin-film surface acoustic porosimeter based on a Quantachrome porosimeter show a high degree of reproducibility between runs and for independently prepared samples.

- *Solid-state, gas chromatographic standards.* This task focused on developing a class of polymers, olefin-sulfur dioxide copolymers, as solid-state precursors to hydrocarbons that can serve as standards for GCs. The advantage of the solid polymer was its potentially very long shelf life compared with liquid standards. Furthermore, by varying the molecular weight of the olefin co-monomer, we can provide standards for a wide range of boiling points and/or column retention times. We prepared and characterized 1-octene-sulfur dioxide copolymer and a 1-butene-sulfur dioxide copolymer as two representative samples of polymers with low ceiling temperatures and low decomposition activation barriers that permit their depolymerization to afford hydrocarbon monomers in quantitative yields. We determined the materials decomposition onsets using thermal gravimetric analysis and characterized the polymers with hydrogen-1 NMR spectroscopy. We prepared a technical advance for the invention of using these materials as solid-state, thermally generated standards.

- *Acetylene preconcentrators.* We performed preconcentrator work to test proof-of-principle for a chemically active adsorption and transformation process. We developed and tested acetylene and ethylene preconcentrator systems; however, these experiments were not successful. The following adsorbents were rejected either by testing or by review of the literature: Nobel metals, polyvinylpyrrolidone, potassium hydride, and catechol boranes.

This task focused on developing a class of polymers, olefin-sulfur dioxide copolymers, as solid-state precursors to hydrocarbons that can serve as standards for GCs. The advantage of the solid polymer was its potentially very long shelf life compared with liquid standards. Furthermore, by varying the molecular weight of the olefin co-monomer, we can provide standards for a wide range of boiling points and/or column retention times

10732

A MEMS Microelectric Generator

R. D. Habbit, Jr., A. A. Jojola, T. R. Christenson, R. G. Jungst, W. H. Greenwood, M. Gonzales, A. D. Oliver, J. G. Young, D. A. Hoke

Sandia will develop a microelectromechanical systems (MEMS)–based device that parasitically harvests energy from a moving host (e.g., a vehicle, soldier, or ship) by converting mechanical motion into electricity. Electrical energy generated from the device will extend the operational field life of a rechargeable battery array designed to power miniature electronic sensors and/or transmitters. We are developing an integrated electrical generation and storage system consisting of a LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding)–based electromagnetic (EM) generator, a power-conversion circuit, and a rechargeable battery array. Peak output from the MEMS EM generator is expected to be 30 mA at 3.3 V. The design goal for the size of an integrated generator is less than 2 cm by 2 cm by 2 cm.

This project consists of three distinct technical development areas: (1) the energy storage, (2) the generator, and (3) energy conversion and distribution. Batteries are the primary method of energy storage chosen for this project. The initial focus for power generation is macroscale electromagnetic power (EMP) generation. The energy conversion and distribution is a future development effort.

The energy-storage development activities focused on commercial off-the-shelf (COTS) batteries first. In previous phases of the project, the batteries were tested for continuous discharge. Next, we tested a subset of the button-cell batteries for pulse performance. The pulse drain and charge performance testing consisted of repetitively discharging and then slowly recharging the battery. This testing will more accurately reflect the expected actual use. Data obtained indicated the batteries will perform better than originally expected.

Earlier, we critically reviewed the EM generator design, which led to several mechanical design changes and a new drawing set. The result was a refocus of technical efforts. Concurrently, we conducted a review of available COTS ferrite cores and obtained samples for the prototype device. We performed a tolerance study on the ferrite cores that revealed the need for slight changes on some of the generator

Sandia will develop a microelectromechanical systems (MEMS)–based device that parasitically harvests energy from a moving host (e.g., a vehicle, soldier, or ship) by converting mechanical motion into electricity. Electrical energy generated from the device will extend the operational field life of a rechargeable battery array designed to power miniature electronic sensors and/or transmitters.

piece part drawings. The piece parts were fabricated in the shop, and we assembled a macroscale working prototype.

We subjected the assembled prototype device to a generic sine sweep (1 octave per minute, limited to 0.05-inch 0-peak amplitude from 10 to 31 Hz, and limited to 5g 0-peak amplitude from 31 to 2000 Hz) on the vibration table. We conducted this test to evaluate and identify the device's natural frequencies and voltage output. The 5g 0-peak amplitude sine sweep test also served as a ruggedness test. We conducted the sine sweep test first. Following the assessment of the sine sweep data, we subjected the devices to the generic truck transport (truck bed) vibration environment.

Initial testing revealed several deficiencies in the initial design. While the initial design may have had an optimal magnetic design, the ferrite cores attracted the magnet toward the winding sleeve. This resulted in large frictional drag, minimizing the overall output of this design. In fact, the generator had zero output during the random truck environment. Once the magnetic core was removed, the overall output significantly improved; however, the output was substantially lower than desired.

We refocused on making progress toward a demonstrator and understanding the factors affecting performance and efficiency. Not only was the initial microgenerator design tested, five other configurations also were tested. Each configuration yielded some improvement over the previous design. In addition to testing the Sandia design, we tested a COTS geophone. The geophone consistently yielded higher voltages than our custom designs; however, when we connected the two designs to a load, we found that the custom designs handled the load better. The research and testing led to a new design, for which we have filed a Technical Advance. This new design has the potential to significantly improve performance.

We developed a power-conditioning circuit to rectify the EM output signal so that it could be used to power an electronic device. The circuit consisted of a full bridge rectifier and a light-emitting diode (LED) as a load. Only the later custom designs produced sufficient power to light the LED. None of them, however, was able to produce enough power to continuously light the LED.

In addition to testing the Sandia design, we tested a COTS geophone. The geophone consistently yielded higher voltages than our custom designs; however, when we connected the two designs to a load, we found that the custom designs handled the load better. The research and testing led to a new design, for which we have filed a Technical Advance. This new design has the potential to significantly improve performance.

10748

Nanostructured Silicon Surfaces for Cost-Effective Photovoltaic Efficiency Improvements

D. S. Ruby, S. A. Kemme, S. H. Zaidi, R. J. Buss

Sandia is evaluating a new regime of plasma surface texturing by using silicon (Si) solar cells as an experimental vehicle. The goal of this work is to develop plasma models to explain, predict, and guide the plasma texturization process. These models will be useful in future applications whenever surface texture evolution needs to be better understood and utilized.

We are also developing optical modeling to optimize the surface texture required for maximum performance. These optical models developed are expected to be extremely useful in many of the nanoscale optoelectronic applications currently under development. Additionally, the development of textured surfaces on low-cost multicrystalline silicon (mc-Si) solar cells could significantly advance the photovoltaic (PV) industry and potentially enable new thin-film crystalline-silicon (c-Si) approaches that may produce high-power, lightweight, mobile power supplies.

This interdisciplinary project utilizes Sandia's expertise in PVs, plasma processing, sensor-based controls, and process modeling to develop environmentally benign processes that can reduce costs and improve product performance. We used large-area (130 cm²) commercial mc-Si solar cells as the test vehicle so that performance improvements will be immediately transferable to mass production. Successful completion of this project will also provide validated process models that can be used in a variety of applications for surface texturing, such as to promote adhesion for neutron generator (NG) assembly, and to optimize new optoelectronic devices.

The PV market is growing at the rate of about 25 percent annually, stimulated by reactions to electricity shortages currently being felt in the western United States. Mc-Si PV modules currently comprise about 60 percent of worldwide PV module production. Sandia's technology could significantly impact current U.S. market growth in that Sandia's technological advances are relevant to significantly boosting the performance of all mc-Si PV modules sold.

This interdisciplinary project utilizes Sandia's expertise in PVs, plasma processing, sensor-based controls, and process modeling to develop environmentally benign processes that can reduce costs and improve product performance. ...

Sandia's technology could significantly impact current U.S. market growth in that Sandia's technological advances are relevant to significantly boosting the performance of all mc-Si PV modules sold.

We developed a maskless plasma-texturing technique using noncorrosive etch gases for mc-Si cells using reactive ion etching (RIE), which results in much higher cell performance than is seen in standard untextured cells. We achieved elimination of plasma damage while reducing front reflectance to extremely low levels. The internal quantum efficiencies that we obtained are higher than those on planar and wet-textured cells, and boost cell currents and efficiencies as much as 11 percent on mc-Si and 2.5 percent on 130 cm² mc-Si cells.

Our university colleague fabricated small 4 cm² mc-Si cells on RIE-textured wafers to test the relative merits of various texturing and damage-removal processes. We obtained up to a 7 percent increase in output power, which approaches the expected maximum of about 10 percent on mc-Si.

The RIE-texture process produces extremely low reflectance surfaces. The solar-weighted reflectance of the cells after texturing are about 3.5 percent, including reflectance from the gridlines. However, the RIE process causes some shallow surface damage that results in the recombination of carriers generated by short-wavelength light absorbed near the surface. We obtain a low blue response. The damage removal etch, which consists of a 10 sec dip in a nitric hydrogen fluoride (HF) acid mixture, removes the entire damaged region, indicated by the complete recovery of the blue response to that of untextured cells. Because so little texture is removed, the solar-weighted reflectance increases to only 5.9 percent and 7.0 percent for titanium (Ti)-assisted and conditioned textures, respectively. Cell performance increases in comparison to planar cells, which have a typical 13 percent reflectance.

The major process-modeling goal was to develop an ability to simulate and ultimately predict our plasma surface-texturing process. Sandia already has code (AURORA) developed for modeling the chemistry of these plasmas, and this code has been used successfully. We also have code (ICARUS) for direct simulation of two-dimensional (2-D) plasma etch. We began developing a new code (SURFMOD) that will ultimately take the mechanism developed with AURORA and interface with ICARUS to simulate surface topography evolution. The code interfaces are yet to be fully developed, but the main architecture is in place and allows simulations of the plasma-texturing process. The code allows gas-phase species to interact with a surface, either depositing or etching. It allows the particle surface dynamics to be

We developed a maskless plasma-texturing technique using noncorrosive etch gases for mc-Si cells using reactive ion etching (RIE), which results in much higher cell performance than is seen in standard untextured cells. We achieved elimination of plasma damage while reducing front reflectance to extremely low levels. The internal quantum efficiencies that we obtained are higher than those on planar and wet-textured cells, and boost cell currents and efficiencies as much as 11 percent on mc-Si and 2.5 percent on 130 cm² mc-Si cells.

specified for each species. Thus, ions etch depending on their angle with the surface normal, while neutral radicals etch isotropically, and each species has its own kinetics.

We believe that the texturing effect is the consequence of micromasking by metal atoms or clusters sputtered onto the surface. The code allows a time-dependent deposition of metal clusters on the surface, which leads to significant roughening. We measured the time behavior of the blackening effect and successfully modeled the early development of fine, 40 nm features that compare very well with a scanning electron microscope (SEM) photo of the developing topography.

We utilized numerical models to predict the hemispherical reflectance of various 1-D Si gratings. The simulated spectra and the measured spectra appear to be in general agreement with regard to both spectral feature location in the waveband and reflectivity values. By averaging the results of the numerical models to take into account the slight variation in depth and pitch of the grating features over the area of the reflectance measurement, we obtained very good agreement for both polarizations of incident light.

We ... successfully modeled the early development of fine, 40 nm features that compare very well with a scanning electron microscope (SEM) photo of the developing topography.

Other Communications

Ruby, D. S., S. H. Zaidi, S. Narayanan, B. M. Damiani, and A. Rohatgi. 2001. "RIE-Texturing of Multicrystalline Silicon Solar Cells." *Proc. 12th International Photovoltaic Science and Engineering Conference 1* (Cheju, South Korea, June).

10758

Network Intrusion Detection Using Adaptive Critic Neural Networks

T. J. Draelos, M. J. Collins, D. P. Duggan, E. V. Thomas

Intrusion detection (ID) is a need and a problem that is not going to go away soon. The challenge of detecting novel exploits and attacks deserves special attention. Adaptive critic designs (ACDs) do not appear to have been used for ID prior to this Sandia project. This research explores four experiments of adaptive host-based ID techniques in an attempt to develop systems that can detect novel exploits. The technique considered to have the most potential is ACDs because of their utilization of reinforcement learning, which allows learning exploits that are difficult to pinpoint in sensor data. Preliminary results of ID using an ACD, an Elman recurrent neural network, and a statistical anomaly-detection technique demonstrate an ability to learn to distinguish between clean and exploit data. Sandia used the Solaris Basic Security Module (BSM) as a data source and performed considerable preprocessing on the raw data. We recommend a detection approach called generalized signature-based ID as a middle ground between signature-based ID, which has an inability to detect novel exploits, and anomaly detection, which detects too many events, including events that are not exploits. The primary results of the ID experiments demonstrate the use of custom data for generalized signature-based ID, and the ability of neural network-based systems to learn in this application environment.

Intrusion detection (ID) is a need and a problem that is not going to go away soon. The challenge of detecting novel exploits and attacks deserves special attention. Adaptive critic designs (ACDs) do not appear to have been used for ID prior to this Sandia project.

Comparison of different intrusion-detection approaches in reality. Generalized signature-based detection is expected to result in fewer errors because signature-based detection learns (knows) too little of the exploit space, and anomaly detection requires learning too much information.

Our preliminary results confirm the ability of neural networks and statistical anomaly detectors to learn the differences between clean and exploit data and suggest that this reinforcement learning approach to ID deserves more attention. Although our research barely scraped the surface of the potential of ACDs, it yielded promising initial results.

Our accomplishments included successful demonstrations of the following:

- (1) Generalized signature-based ID as a valid approach.
- (2) The use of recurrent neural networks to discriminate between clean and exploit data.
- (3) The development and use of ACDs to discriminate between clean and exploit data.
- (4) The development and use of statistical anomaly detection algorithms (the exponentially weighted moving average algorithm) to identify exploits in Defense Advanced Research Projects Agency (DARPA) 1999 ID test data.

This research yielded three lessons: (1) first and foremost, much work will be required to achieve effective detection of novel exploits, (2) although the concept of IDS control is promising, practically speaking, a better course of action appears to be to incorporate the most effective mechanisms into the IDS, and consequently, IDS control is probably not truly useful, and (3) with current ID sensors, considerable effort must be devoted to data preprocessing before presentation to a neural network. Even more importantly, the availability of new sensors designed from the ground up for automated ID would dramatically improve the possibility of detecting intrusions.

... the availability of new sensors designed from the ground up for automated ID would dramatically improve the possibility of detecting intrusions.

10759

Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry

D. R. Gallup, R. E. Carlson, C. L. Beaver, M. D. Torgerson, W. D. Neumann

The electric power industry uses supervisory control and data-acquisition (SCADA) systems to monitor and control power production and distribution. SCADA systems are a critical part of the electric power infrastructure. They typically have a master station/substation hierarchy. The master station communicates with a large number of substations, and some communications may occur between substations. The communications traffic consists of frequent messages (0.2 to 5 messages per second per substation) of a few to a few dozen bytes in length. Industry standards require that security not delay message processing by more than 2 msec–4 msec. In this project, Sandia investigated the various security aspects and requirements of the SCADA system communication networks.

Based on this investigation, we developed a method of managing cryptographic keys and cryptographic algorithms that are appropriate for securing communications on SCADA systems.

We developed a cryptographic method for providing complete message security. Our approach uses the new advanced encryption standard (AES), also known as *Rijndael*, for encrypting messages, and the 256-bit version of the secure hash algorithm (SHA) for deriving digital signatures. Encryption is used to hide the contents of messages. The digital signatures are used to verify that the sender of a message is who he claims to be. We also developed an approach to allow substations to communicate securely with one another. This secure communication is achieved by exchanging AES keys using public-key cryptography that is based on elliptic-curve mathematics. Finally, we developed a method of managing all of the cryptographic keys and cryptographic algorithms. This method allows an electric utility to apply our approach without needing to become an expert in cryptography.

We successfully implemented our SCADA security approach on a simulated SCADA system. We implemented

The electric power industry uses supervisory control and data-acquisition (SCADA) systems to monitor and control power production and distribution. SCADA systems are a critical part of the electric power infrastructure. ... Sandia investigated the various security aspects and requirements of the SCADA system communication networks. ...

We successfully implemented our SCADA security approach on a simulated SCADA system.

our secure communication system on a simulated SCADA network. Our implementation meets all of the efficiency and compatibility requirements of typical SCADA networks.

Other Communications

Beaver, C. L., D. R. Gallup, W. D. Neumann, and M. D. Torgerson. 2001. "Key Management for SCADA." Sandia Technical Report SAND2001-3252, Sandia National Laboratories, Albuquerque, NM (October).

10763

Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines

J. H. Chen, C. A. Kennedy, J. C. Hewson, A. R. Kerstein, J. E. Dec, T. Echekki, S. D. Mason

Homogeneous charge-compression ignition (HCCI) engines are an attractive alternative to diesel engines, offering the potential for high diesel-like efficiencies while concurrently producing extremely low emissions vehicle (super-ULEV) standards without expensive after-treatment. An HCCI engine operates on the principle of compressing a dilute premixed charge until it autoignites and burns volumetrically. This is a relatively new realm of combustion in which the mixture is often sufficiently dilute so as to prevent flame propagation; hence, combustion occurs volumetrically. For appropriate mixture and fuel type, engines have been successfully operated in an HCCI mode. However, achieving appropriate combustion across the load-speed map of the engine, and slowing the combustion to achieve a smooth heat-release time-history to prevent engine damage and noise, remain formidable challenges. Recent zero-dimensional (0-D) computational studies show that it is difficult to achieve a smooth heat-release history with a fully homogeneous mixture. A key technical challenge is how to actively control the intake protocol and in-cylinder fluid motion to obtain the needed heat-release time profile across the operating conditions of the engine.

Sandia is implementing novel computational and modeling tools for the purpose of developing active control strategies for in-cylinder fuel/air/residual mixture composition and temperature in HCCI engines. We will use the computational tools in parametric studies to actively control the in-cylinder fuel/air/exhaust-gas residual mixture composition and temperature space/time history to obtain a smooth heat-release time profile across the load-speed map of the engine. If we are able to develop successful control strategies, the numerical tools will be invaluable for providing guidance to engine designers, significantly jump-starting HCCI design efforts.

We developed simplified chemical-kinetic models that retain only the rate-limiting time scales for the various stages of ignition. Models have been developed for hydrogen (H),

Sandia is implementing novel computational and modeling tools for the purpose of developing active control strategies for in-cylinder fuel/air/residual mixture composition and temperature in HCCI engines. ... If we are able to develop successful control strategies, the numerical tools will be invaluable for providing guidance to engine designers, significantly jump-starting HCCI design efforts.

which represents high-temperature ignition chemistry characteristic of gasoline fuels, and heptane, which represents lower-temperature diesel-like fuels. These models suggest that it will be possible to elucidate expressions for ignition times as a function of mixture composition and operating conditions. More significant for the issue of control-model development, these expressions will provide the leading order scaling of the ignition times with changes in engine operating parameters. We covered a range of engine speeds and loads as well as a range of mixing rates for the fuel and air in one-dimensional turbulence (ODT) parameter studies using both n-heptane and H fuels.

We evaluated simulated engine performance on the basis of pressure-time histories, evolution of mixture probability-density functions (PDFs), and individual-cycle space-time-temperature maps. This information enabled the diagnostics of conditions in which ignition did not occur or was not sustained. Parameter studies indicated critical parameter ranges where mixing influences ignition; these ranges include those where ignition timing and heat-release rates appear to be optimal. In particular, small-scale fluctuations, typically neglected for HCCI modeling, are shown to be key to ignition for certain ranges of parameters. For these conditions, completely homogeneous mixtures do not ignite, but mixtures retaining small-scale inhomogeneities resulting from finite mixing times do ignite reliably. In many of the cases where small-scale fluctuations are present, some degree of premixed flame propagation is observed to occur around ignition kernels.

Another phenomenon that is not included in traditional HCCI models, premixed propagation, is seen in the current ODT and direct numerical simulations (DNS). Preliminary statistics from ODT of the joint PDF of mixture composition and enthalpy indicate that, for engine conditions, the PDFs evolve to a non-Gaussian shape. Both the mixture fraction and enthalpy distributions have significant skewness, suggesting that hard-to-ignite regions persist even after long mixing times. These statistics impact the ignition behavior and the unburned hydrocarbon emissions.

The autoignition of turbulent spatially heterogeneous H/air mixtures has been studied using DNS with detailed chemistry for pressures ranging from 1 to 10 atmospheres. These simulations reproduce an array of autoignition events that are dependent on the mixing/dissipation rates. Similar to the ODT results, DNS simulations show the presence of

These models suggest that it will be possible to elucidate expressions for ignition times as a function of mixture composition and operating conditions. More significant for the issue of control-model development, these expressions will provide the leading order scaling of the ignition times with changes in engine operating parameters.

ignition kernels/propagation fronts. The fronts established are initially lean premixed flames, with rare occurrences of triple flames, depending on the probability of propagating through stoichiometric conditions. The simulations further show the existence of both ignited and partially extinguished kernels resulting from relatively high dissipation rates. The relevant chemistry that dominates during the induction phase of autoignition, and the competing effect of dissipation of heat and radicals, is highly dependent on the initial thermochemical state and the local mixing conditions. In the present simulations we encountered all three homogeneous explosion limits, depending on the local mixing conditions. To simulate compression ignition in DNS, we added an artificial mass source term in the governing equations. We validated the method for compression ignition of a homogeneous premixed dilute H/air charge at 20:1 compression ratios. We implemented the stiff time integrator, ARK, in the DNS code and validated it for 0-D stiff ignition delay times.

We validated the method for compression ignition of a homogeneous premixed dilute H/air charge at 20:1 compression ratios. We implemented the stiff time integrator, ARK, in the DNS code and validated it for 0-D stiff ignition delay times.

Refereed

Echekki, T., and J. Chen. 2001. "Direct Numerical Simulation of Autoignition in Nonhomogeneous Hydrogen/Air Mixtures." *Proc. 2nd Joint Meeting of the U.S. Sections of the Combustion Institute* **Paper 184** (Oakland, CA, 25–28 March): 10.

Hewson, J., A. Kerstein, J. Chen, and J. Dec. 2001. "The Effect of Inhomogeneities on Ignition under HCCI-Engine Conditions." *Proc. 2nd Joint Meeting of the U.S. Sections of the Combustion Institute* **Paper 5** (Oakland, CA, 25–28 March): 10.

10767

Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks

T. D. Tarman, K. C. Bauer, E. L. Witzke, W. F. Young, B. R. Kellogg

Currently, network intrusion-detection systems (NIDS) are in place in networks at Sandia and our customers. NIDS allow site security personnel to monitor network devices and hosts for activities that indicate a possible attack, misuse, or operational anomaly in the information system. Since NIDS protect against attacks from inside and outside users, they provide a complementary service to devices that protect internal networks against outside attacks (e.g., encryptors and firewalls). However, current NIDS only work down to the Internet Protocol (IP) level. Data and control flows below IP are not covered by the current technology. This represents a risk to Asynchronous Transfer Mode (ATM) network backbones, which are found inside many enterprises (including Sandia), public carriers, and the Internet. This makes ATM networks vulnerable to a variety of denial-of-service attacks, routing infrastructure attacks, and other attacks.

This project is developing an ATM intrusion-detection system that monitors the signaling flows associated with a variety of ATM protocols (e.g., virtual circuit setup, call routing, local area network [LAN] emulation) to determine if insider or outsider attacks are being conducted against the ATM network. We will research and document issues such as analysis of ATM protocol attacks, sensor performance on high-bandwidth links and switch fabrics, and scalability issues. We will develop prototype ATM intrusion-detection systems that incorporate methods to address these specific concerns.

Sandia is uniquely qualified to make significant contributions to this area due to our recognized leadership in ATM security and high-speed encryption, and our in-depth experience with ATM protocols and IP NID. Results from this work will lead to key technologies that can be incorporated into the ATM intrusion-detection devices for Sandia and DOE technologies. This work will also enhance Sandia's leadership in ATM security.

This project is developing an ATM intrusion-detection system that monitors the signaling flows associated with a variety of ATM protocols (e.g., virtual circuit setup, call routing, local area network [LAN] emulation) to determine if insider or outsider attacks are being conducted against the ATM network. ... Sandia is uniquely qualified to make significant contributions to this area due to our recognized leadership in ATM security and high-speed encryption, and our in-depth experience with ATM protocols and IP NID. Results from this work will lead to key technologies that can be incorporated into the ATM intrusion-detection devices for Sandia and DOE technologies.

We completed development of a software-based ATM intrusion-detection system and demonstrated it in small laboratory environments at Sandia and at the Stevens Institute of Technology (SIT, formerly with Arizona State University), and in a large unclassified test network for the DoD. In all of these demonstrations, the system successfully detected a mock ATM peer group leader takeover attack, as described in a MILCOM 1999 paper. This successful detection involved all of the subcomponents in our ATM intrusion-detection architecture, including the active-direct sensors (for the Private Network-to-Network Interface [PNNI] protocol), the passive-direct sensors (for the User-to-Network Interface [UNI] protocol), the indirect sensors (for the Simple Network Management Protocol [SNMP]), the assessment engine, the rule editor, and response components (both active and passive). During the attack, the assessment engine successfully responded by sending a notification to the administrator and by isolating the offending intruder by shutting down an appropriate port on the switch to which it attached. In addition, the DoD installation showed the scalability of the basic, software-based architecture by successfully “sifting through the noise” of a large number of new switch events to successfully detect the mock attack.

As part of our collaboration with SIT, we examined scalability and response timeliness issues associated with our intrusion-detection approach and with distributed intrusion-detection systems in general. We delivered a working ATM intrusion-detection system to SIT, set it up in the SIT lab, and demonstrated the system. SIT progress reports indicate the need to partition a distributed intrusion-detection system into two components: a strategic component that extracts parameters (sensor notifications), and a tactical component that is configured by the strategic part with network reconfiguration rules and responds according to these rules.

Another aspect of this work was the continued development of the UNI sensor, which is a passive-direct sensor (i.e., a sensor that directly monitors ATM protocol flows, but does so silently, without actively participating as a network device). We designed this sensor to facilitate separation of the sensor configuration user interface from the actual sensor device, which allows distributed management of multiple UNI sensors. The UNI sensors themselves were designed to be implemented on a LINUX platform, with some

We completed development of a software-based ATM intrusion-detection system and demonstrated it in small laboratory environments at Sandia and at the Stevens Institute of Technology (SIT, formerly with Arizona State University), and in a large unclassified test network for the DoD. In all of these demonstrations, the system successfully detected a mock ATM peer group leader takeover attack ... During the attack, the assessment engine successfully responded by sending a notification to the administrator and by isolating the offending intruder by shutting down an appropriate port on the switch to which it attached.

functionality in hardware and the rest in software. We developed a language for communicating filter specifications between the user interface and the sensor, as well as a protocol for securely transferring filter specifications (based on secure shell, with public-key cryptography). Although all sensor components were implemented in software, we made progress in the design and implementation of the hardware components on an Altera system on a programmable chip (SOPC) platform.

Given the current network market conditions, vendor interest has now shifted away from ATM and toward IP-based flow-switching techniques such as multiprotocol label switching (MPLS). Therefore, this project also spent some time analyzing the MPLS protocols to determine how the ATM intrusion-detection architecture can be applied to MPLS networks.

We developed a language for communicating filter specifications between the user interface and the sensor, as well as a protocol for securely transferring filter specifications (based on secure shell, with public-key cryptography).

Refereed

Tarman, T. D., and E. L. Witzke. 2000. "Intrusion-Detection Considerations for Switched Networks." *Proc. SPIE Photonics East 2000: Enabling Technologies for Law Enforcement and Security* **4232** (Boston, MA, 5–8 November): 85–92.

Tarman, T. D., E. L. Witzke, K. C. Bauer, B. R. Kellogg, and W. F. Young. 2001. "Asynchronous Transfer Mode (ATM) Intrusion Detection." *Proc. MILCOM 2001*, accepted.

10771

Silicon/Carbon Nanocomposites for Rechargeable Battery Applications

D. Ingersoll, K. J. Gross, M. A. Rodriguez

The utility of nanomaterials has been determined to be the next arena of advanced materials development, in which entering this nanosize domain may drastically alter material behavior, at least compared to their larger-sized brethren. The limitations of energy storage devices (e.g., batteries) such as runtime, power, and voltages, are imposed by the intrinsic characteristics of the materials used, including the anode and cathode materials. Consequently, by improving the performance of these materials either alone or together, the overall performance of the battery can be improved, thereby enabling new missions or expanding old ones.

Toward this end, Sandia initiated development of new composite nanomaterials for use as the anode material in reversible energy storage systems that have theoretical capacities an order-of-magnitude greater than the current state-of-the-art materials. These new materials can be combined with existing cathode and electrolyte materials to create energy storage devices with vastly improved volumetric and gravimetric energy densities (i.e., smaller and lighter batteries). Our primary focus is on developing silicon (Si) and Si/carbon (C) nanocomposites in which the C overlays and coats the Si. Our reason for selecting Si is based on its inability to form high-lithium (Li)-content alloys, and the possibility of using this alloy as a high-energy, reversible storage medium. The C overlayer should protect the Si from irreversible oxidation/passivation and also provide a secondary means of chemical energy storage, as it, too, forms reversible compounds with Li. Nanomaterials are needed to provide reasonable rate characteristics for practical devices, as well as to improve the reversibility of the alloy/de-alloy process during oxidation and reduction.

We developed two methods for generating C coatings. The first method employs a fluidized bed reactor where catalytic decomposition of a hydrocarbon precursor takes place directly on the material. We evaluated a number of precursor hydrocarbons, including methylene, pyrrole, and pyridine, alone as well as in mixtures. We also performed a cursory evaluation of the physical characteristics of the C

The utility of nanomaterials has been determined to be the next arena of advanced materials development, in which entering this nanosize domain may drastically alter material behavior, at least compared to their larger-sized brethren. ...

Sandia initiated development of new composite nanomaterials for use as the anode material in reversible energy storage systems that have theoretical capacities an order-of-magnitude greater than the current state-of-the-art materials.

formed. The second method evaluated is based on mechanical means and is done during formation of the Si nanoparticles. In this case, Si and C are introduced into the mill just prior to processing. Preliminary results indicate that a small amount of silicon carbide (SiC) is formed during this process; however, it appears that the bulk of C remains unreacted. Also, evidence exists for silicon oxide (SiO) formation; however, early indications are that the amount of SiO formed is small. We are attempting to evaluate the final structure created.

We also continued to develop methods for preparation of Si nanomaterials, and two areas are continuing to be pursued. The first area, chemical synthesis, is proceeding apace, and 150 mg of material have finally been prepared. This material is currently being characterized, and the testing to date indicates that the material that was prepared and isolated is our target material. The other approach we are still pursuing is the mechanical-milling approach, primarily due to the larger sample sizes that can be prepared. We modified our approach from last year and developed nanomaterials. We performed electrochemical evaluation of the nanomaterial produced last year by selective chemical oxidation, and we found that the surface oxide layer present is completely passivating (we had hoped for a porous, nonpassivating structure). Various approaches to remove the passivation layer (e.g., hydrogen reduction) were not successful.

We also continued to develop methods for preparation of Si nanomaterials, and two areas are continuing to be pursued.

The first area, chemical synthesis, is proceeding apace, and 150 mg of material have finally been prepared. This material is currently being characterized, and the testing to date indicates that the material that was prepared and isolated is our target material. The other approach we are still pursuing is the mechanical-milling approach, primarily due to the larger sample sizes that can be prepared.

1999I

Use of Apatite and Substituted Apatites for *In Situ* Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water

R. C. Moore

This work describes a new in situ technique for placement of apatite, $\text{Ca}_{10}(\text{PO}_4)_6(\text{X})_2$, where X is monovalent anion such as OH^- , Cl^- or F^- . It is well documented that apatite is a strong sorbent for radionuclides and heavy metals. The new placement process is based on injecting a solution of calcium citrate and sodium phosphate into soil. As the citrate is biodegraded, calcium (Ca) is gradually released and immediately reacts with the phosphate to form insoluble calcium phosphates that transform into apatite. In this work, we formed apatite in soil by adding a solution containing sodium citrate, calcium chloride, sodium phosphate, ammonium nitrate, and sodium fluoride at a pH of 8. We analyzed the apatite precipitated on the soil particle surfaces by x-ray diffraction (XRD); it closely matched the pattern of hydroxyapatite, $\text{Ca}_{10}(\text{PO}_4)_6(\text{OH})_2$. Batch sorption studies using soil in which apatite was formed indicated that strontium (Sr) and uranium (U) are irreversibly sorbed to the apatite. Column studies are under way. We adapted the process for irreversible sorption of technetium (Tc). We will investigate redox reagents for use with Tc. This work also investigated the use of bovine apatite to sequester arsenic (As). Initial experiments indicated that As was quickly removed by contact with bovine apatite. We identified the material responsible for As sorption and completed sorption experiments. A pilot plant study on using the material in new process is under way. The process is based on using magnesium oxide (MgO) to sorb As and remove the MgO by centrifugal methods.

In this project, Sandia developed a new *in situ* technique for placement of apatite, $\text{Ca}_{10}(\text{PO}_4)_6(\text{X})_2$, where X is monovalent anion such as OH^- , Cl^- or F^- . Apatite is a strong sorbent for radionuclides and heavy metals. The new placement process is based on injecting a solution of calcium citrate and sodium phosphate into soil. As the citrate is biodegraded, Ca is gradually released and immediately reacts

In this project, Sandia developed a new in situ technique for placement of apatite, $\text{Ca}_{10}(\text{PO}_4)_6(\text{X})_2$, where X is monovalent anion such as OH^- , Cl^- or F^- . Apatite is a strong sorbent for radionuclides and heavy metals.

with the phosphate to form insoluble calcium phosphates that transform into apatite.

We formed apatite in soil by adding a solution containing sodium citrate, calcium chloride, sodium phosphate, ammonium nitrate, and sodium fluoride at a pH of 8. We analyzed the apatite precipitated on the soil particle surfaces by XRD and closely matched the pattern of hydroxyapatite, $\text{Ca}_{10}(\text{PO}_4)_6(\text{OH})_2$. Batch sorption studies using soil in which apatite was formed indicated that Sr, U, and Tc are irreversibly sorbed to the apatite.

Also in this work, we investigated the use of $\text{Mg}(\text{OH})_2$ to sequester As. Experiments indicate As is quickly removed by contact with $\text{Mg}(\text{OH})_2$. We developed a pilot plant study on using the material in a new process, and it is under construction. We have submitted two patent applications.

Experiments indicate As is quickly removed by contact with $\text{Mg}(\text{OH})_2$. We developed a pilot plant study on using the material in a new process, and it is under construction. We have submitted two patent applications.

Refereed

Moore, R. C. 2001. "Formation of *In Situ* Apatite for Containment of Radionuclides and Heavy Metals." *Environmental Science and Technology*, submitted.

Moore, R. C, A. Hasan, F. Salas, and D. Lucero. 2001. "In Situ-Formed Apatite Barriers for Containment of Radionuclides and Heavy Metals." Paper presented to Migration '01, Austria, 15 September.

20416

Information-Sharing Security Module Research and Development

L. A. Snyder, C. L. Beaver, R. C. Schroepel, W. D. Neumann

The nation's critical infrastructures (water, electric power, communications, oil and gas, banking and finance, transportation, emergency services, and continuity of government) are increasing their use of the Web for exchanging sensitive or confidential information and for financial transactions.

This project will research and develop a system architecture for an information-sharing security module that could be configured to meet a wide range of security needs for various Web-based information applications requiring information security ranging from low to high.

The research and development will focus on the complex problem and the technical challenge of providing simultaneous authenticity and anonymity services, seemingly opposite goals. To achieve this goal, there must also be the capability of including cryptography, key management (certificate authority, distribution, revocation), secure broadcast (rapid dissemination of information securely), and access control (the prevention of an outsider or insider from using keys in an unauthorized manner) services. These information-sharing security services are required for high-consequence industry and government applications.

The next step in our process of developing our capability to provide this anonymous, authentication communication protocol with message revocation is to complete the software implementation and to test this research concept. This includes the following capabilities:

- (1) A multilevel communication structure to allow message revocation while maintaining anonymity;*
- (2) An update of the current encryption algorithm to the new advanced encryption standard, the Rijndael cipher;*
- (3) A logging and audit system;*
- (4) A simulated trusted center authority for demonstration and proof-of-concept purposes;*
- (5) An interface with our indications and warning system; and*
- (6) An onion-router to randomize message traffic.*

The nation's critical infrastructures (water, electric power, communications, oil and gas, banking and finance, transportation, emergency services, and continuity of government) are increasing their use of the Web for exchanging sensitive or confidential information and for financial transactions.

This project will research and develop a system architecture for an information-sharing security module that could be configured to meet a wide range of security needs for various Web-based information applications requiring information security ranging from low to high.

Our prior research led to several system goals: anonymity of message author, anonymous communication paths, authentication of group membership, integrity and privacy of data, protection against system abuse by insiders, and ease of use by those employing the system. Encryption of messages using a symmetric key algorithm is used to provide integrity and privacy of data; if a message is altered after being encrypted, it won't decrypt properly, and unauthorized users cannot read encrypted messages. The encryption requirement also provides for authentication of group membership, since only group members can obtain valid keys to encrypt and decrypt data. Anonymity of message author is achieved through text processing of the message to eliminate clues to authorship. Furthermore, no clues to authorship can be gained through the encryption or transmission process.

The encryption keys are generated per message, based on possession of a compact disk (CD) and knowledge of secret information; however, this process does not compromise anonymity since all users have identical keying material. We keep the communication paths anonymous by use of an onion-routing system. One or more users may be grouped into "domains," and while we describe anonymous communications between domains, we mitigate the threat of insider abuse with an anonymous message revocation capability. (We define a domain to be a collection of one or more users identified as a single entity. We define domain-to-domain communications to be the communications between domains, and intradomain communications to be the communications between users within a domain.)

The system is easy to use. A user inserts the CD, and the software programs then execute all protocols. The protocols are transparent to the users. A user of our system may be an individual or an entire group (e.g., a business). A group may have multiple users at a site, yet wish to be identified as a single entity.

Our protocols provide anonymous, authenticated communications between domains. If a domain consists of multiple users (e.g., a company with several employees using the software), then we recognize that the communications that must be anonymous to outside domains may not need to be anonymous to others within the same domain. (Certainly a business expects control over the communications of its employees.) Hence, intradomain communications are authenticated, yet give the option for anonymity, revocable anonymity, or no anonymity. This multilevel structure allows

Our protocols provide anonymous, authenticated communications between domains. If a domain consists of multiple users (e.g., a company with several employees using the software), then we recognize that the communications that must be anonymous to outside domains may not need to be anonymous to others within the same domain.

us to revoke messages anonymously at the domain-to-domain communication level. Our protocols provide anonymous, authenticated communications between domains. If a domain consists of multiple users (e.g., a company with several employees using the software), then we recognize that the communications that must be anonymous to outside domains may not need to be anonymous to others within the same domain.

One application of our design is in support of PDD 63, under which individual industry owners may communicate infrastructure and cyber problems or issues to the information-sharing and analysis center (ISAC). The ISAC may then send the information on to a central government agency where the data will be evaluated with data from other sources to see if there is a larger problem. In such a model, the individual industry users may be members of a utility, such as an electric power owner or water company. The ISAC members may be representatives from a particular set of industry providers (e.g., water, banking and finance, telecommunications). The ISACs send their information to some central location that could be, for example, a government organization such as the National Information Protection Center, which would gather and analyze the data.

Our protocols provide anonymous, authenticated communications between domains. If a domain consists of multiple users (e.g., a company with several employees using the software), then we recognize that the communications that must be anonymous to outside domains may not need to be anonymous to others within the same domain.

Refereed

Beaver, C. L., R. C. Schroepfel, and L. A. Snyder.
2001. "Anonymous Authenticated Information Sharing." *Proc. 2001 IEEE Workshop on Information Assurance and Security, IEEE Systems, Man and Cybernetics Information Assurance Workshop* (West Point, NY, 5 June): 161–168.

21559

Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures

A. B. Baker, S. H. Conrad, D. L. Harris, L. A. Malczynski, W. E. Beyeler, G. A. Mann

In this project, Sandia is producing an integrated framework and a dynamic simulation model of key aspects of nuclear energy, nuclear materials storage and disposition, global nuclear materials management (GNMM), defense nuclear materials, and nuclear proliferation risk, and will link nuclear energy dynamically to global energy, greenhouse-gas emissions, and other measures of environmental impact. Specifically, this framework will “reduced-form” model the back end of the nuclear fuel cycle (waste storage and disposition), the front end of the nuclear fuel cycle (nuclear power generation), and the defense materials system (nuclear materials from weapons).

To provide for integrated energy and environmental systems integration, this project also will reduced-form model global energy demand by sector (e.g., industrial, transportation, or electricity), by fuel (i.e., oil, natural gas, coal, nuclear, renewables, and hydrogen [H]), and for global carbon (C) emissions. The Defense Materials Module will reduced-form model the nuclear materials flow from weapons to the back end of the fuel cycle, and we will benchmark it to credible sources as far as possible. Research will proceed in parallel for these main modules and for dynamic characterization of both proliferation risk and environment. Thus, this project will produce an integrated model of nuclear energy, energy-based C emissions, and GNMM of defense- and civilian-generated waste streams, which will permit strategic assessment of integrated research needs as well as provide a tool for complex policy analysis. In addition to C emissions, this model will estimate other environmental impacts from exploration, drilling and mining, and energy conversion.

The proposed model enhancements will facilitate critical decision making in support of regional and global assurance of the safety and security of nuclear materials and environmentally acceptable, reliable, and cost-effective energy production.

In this project, Sandia is producing an integrated framework and a dynamic simulation model of key aspects of nuclear energy, nuclear materials storage and disposition, global nuclear materials management (GNMM), defense nuclear materials, and nuclear proliferation risk, and will link nuclear energy dynamically to global energy, greenhouse-gas emissions, and other measures of environmental impact. ..

The proposed model enhancements will facilitate critical decision making in support of regional and global assurance of the safety and security of nuclear materials and environmentally acceptable, reliable, and cost-effective energy production..

In earlier work, we developed a real-time, laptop-portable, dynamic simulation model that integrates key aspects of the fuel cycle, civilian and defense nuclear materials generation and disposition, and energy and greenhouse-gas emissions. That model predicts trends through the year 2050. Subsequently, we improved that model significantly in the following five areas:

(1) We segmented the global model to allow for regional and global examination and evaluation of nuclear materials, environmental impact, and proliferation risk.

(2) We added energy options to include additional forward-looking alternative technologies such as Generation IV nuclear reactors, and production and use of H as a fuel. These alternative technologies are likely to be realized before the year 2050, and therefore need to be modeled to facilitate the exploration and evaluation of future policy issues and research investments.

(3) Our measures of proliferation risk are also improved. The original model was based on *ad hoc* concepts of the relative utility of various nuclear materials from the potential proliferator's perspective. We refined these concepts by accounting for the cost to steal or develop a nuclear weapon by alternative means. The improved proliferation risk measures were developed within a concurrent project.

(4) We better quantified the environmental impact of alternative fuel choices. The original model included only C emissions as a measure of environmental impact. The improved model includes more than 15 measures, including impacts on water and land.

(5) We improved the back-end module. This extension allows policymakers to weigh alternatives, such as a once-through fuel cycle versus a closed fuel cycle. Similarly, various disposition options are considered for military and commercial nuclear materials.

In earlier work, we developed a real-time, laptop-portable, dynamic simulation model that integrates key aspects of the fuel cycle, civilian and defense nuclear materials generation and disposition, and energy and greenhouse-gas emissions. That model predicts trends through the year 2050. Subsequently, we improved that model significantly....

26549

Very High Temperature Gas-Cooled Reactor

R. J. Lipinski, D. R. Anderson, S. A. Wright, P. S. Pickard, E. J. Parma, Jr., A. C. Marshall

The goal of this project is to develop concepts for next-generation power reactors that provide more-efficient, lower-cost systems with less waste and that are inherently safe and proliferation resistant. The desired reactor-design characteristics include the use of very high temperature fuels—graphite and oxide, high-temperature coolants—helium (He) and molten-fluoride salts, low-power density and high-neutronic efficiency, and high-burnup core designs. A project goal is to identify approximately two to three baseline designs that should be considered for more detailed assessment.

(1) High-temperature fuels assessment. The fuels assessment considered both graphite-based coated-particle fuels and oxide-based systems to achieve higher temperatures. The emphasis was on the graphite fuels. Oxide materials (beryllium oxide [BeO], aluminum oxide [Al₂O₃]) provide high-temperature performance, but were considered unlikely to provide adequate fission-product retention at higher temperatures.

To achieve operating temperatures above 1250°C, higher-temperature fission-product coatings on the tri-isotopic (TRISO)-fuel particle, such as zirconium carbide (ZrC), is being researched (Japan) and is the most likely option. Other refractory carbides (such as niobium carbide [NbC]) have higher temperatures but are less understood. Temperatures in the range of 1400°C to 1500°C may be possible for long periods but with some selective fission-product retention issues.

Assessment results are as follows:

- Current silicon-carbide (SiC) graphite provides a baseline—assured path to > 1000°C, but requires innovative element design.
- ZrC provides a higher-temperature coating—generally better fission-product retention, but requires additional materials research.
- Multiple coatings may work for a wider range of fission-product retention, but at some additional cost.
- We identified a modified-coating TRISO fuel as the baseline fuel.

The goal of this project is to develop concepts for next-generation power reactors that provide more-efficient, lower-cost systems with less waste and that are inherently safe and proliferation resistant. ... A project goal is to identify approximately two to three baseline designs that should be considered for more detailed assessment.

(2) Heat-transfer, fuel-element configurations. To maximize the coolant-outlet temperature for a given maximum fuel temperature, the fuel-element configuration must be designed for as low a temperature drop from the fuel to coolant as possible. We analyzed several alternative geometries that reduced the temperature drop. Heat-transfer studies showed that the molten-salt temperature drops between fuel and coolant for an annular geometry were on the order of 160°C. For He, the total temperature drop was 305°C. Results suggest that He-cooled systems will require small channels with large surface areas to achieve desired operational temperatures. The molten-salt systems will allow a wider range of fuel geometries.

We also developed models to study the potential for passive-decay heat removal. Core and vessel designs could be made passively safe for both molten-salt and gas coolants for configurations with a core radius of 300 cm and operating at 5 W/cm³. The molten-salt heat-transfer advantages are significant, including reduced-temperature drop and high-heat capacity. Annular fuel-element configurations will be used as the baseline, with a pebble or particle concept being developed as the advanced-technology case.

(3) Criticality, neutronics. The goal of the neutronic studies was to determine the allowable ranges of criticality, burnup, and reactivity coefficients for candidate cores based on the identified high-temperature fuel options. Studies included graphite-coated particle and Be-based oxide systems using both uranium (U) and U thorium (Th) cycles. Using the Monte Carlo neutronics code MCNP (Monte Carlo N-particle), we determined the potential for breeding or conversion of fertile isotopes to fissile isotopes for a range of fuel and fuel-to-moderator ratio. Both the U-238-to-plutonium-239 (Pu-239) cycle and the Th-232-to-U-233 cycle were studied. The results show that achieving extremely long run times without refueling in a thermal reactor requires low-power densities (5 W/cm²) and heavy-metal-to-carbon-density ratios of 0.6 or greater. To achieve the optimum burnup, larger fuel-particle diameters than currently considered are needed.

(4) Systems selected for further evaluation. We identified three approaches to consider for more detailed analysis.

—Very high temperature gas-cooled reactor (VHTGR)—Loop-type, prismatic graphite-moderated/-reflected, coated-particle fuel, He-cooled.

The goal of the neutronic studies was to determine the allowable ranges of criticality, burnup, and reactivity coefficients for candidate cores based on the identified high-temperature fuel options. ...

The results show that achieving extremely long run times without refueling in a thermal reactor requires low-power densities (5 W/cm²) and heavy-metal-to-carbon-density ratios of 0.6 or greater. To achieve the optimum burnup, larger fuel-particle diameters than currently considered are needed.

–Ultrahigh-temperature gas-cooled reactor (UHTGR)—Loop-type, graphite-moderated/-reflected, pebble fuel in nominally 1 m columns in annular-graphite moderator, coated-particle fuel, He-cooled.

–Advanced high-temperature reactor (AHTR)—Pool-type, molten-salt-cooled, prismatic graphite moderator, coated-particle fuel.

We will weigh the benefits of these approaches against cost/feasibility in future efforts.

*We will weigh the benefits of
these approaches against
cost/feasibility
in future efforts.*

26551

Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations

T. M. Nenoff, D. E. Trudell, R. L. Jarek, S. M. Thornberg

Sandia will combine expertise in catalyst/zeolite synthesis, nanoscale-reaction kinetic testing, catalytic testing, and reactor design to produce a novel catalytic purification system that is highly energy-efficient and that will greatly impact both the chemical and petrochemical industries. Current processes for manufacturing the commodity feedstock cumene (isopropylbenzene) involves a two-step process of heating reactants with corrosive acid catalysts (300°C), cooling for transport (25°C), followed by another energy-intensive distillation product separation (130°C). Reaction and separation in a one-pot reactor, noncorrosive zeolite catalysts, and the elimination of the cooling and transport steps will combine to produce a more efficient process with a tremendous payback in energy savings (approximately 2 trillion BTUs/year in the year 2020).

We are highly qualified to undertake this novel research, due to our expertise in (1) catalyst synthesis and testing, and (2) nanoscale kinetic studies. Synthesized catalysts will be reacted with benzene and propylene reactants to produce the feedstock cumene. Optimized catalyst choice will be determined through nanoscale kinetic studies obtained by Fourier Transform–Ion Cyclotron Resonance/Mass Spectroscopy (FT–ICR/MS), a uniquely suited analytic tool. These nanoscale studies will translate to bulk-scale catalytic reactions in a unique one-pot combined catalytic reaction/distillation cumene synthesis process (130°C–200°C).

Our lab is equipped for full reactants and product characterization, including in-house reactors, FT-ICR/MS, and gas chromatography (GC)/MS product characterization. With FT-ICR/MS, we will fragment the zeolite catalyst by laser ablation, then allow it to interact with the hydrocarbon (HC) molecules. This will give us binding energies, gas-phase reactivity, and selectivity of the catalyst per HC system. We will then use the FT-ICR/MS data to determine the catalyst choices for bulk reactor testing. Combining FT-ICR/MS and catalytic synthesis/testing allows for an optimization of catalyst choice per cumene production.

Sandia will combine expertise in catalyst/zeolite synthesis, nanoscale-reaction kinetic testing, catalytic testing, and reactor design to produce a novel catalytic purification system that is highly energy-efficient and that will greatly impact both the chemical and petrochemical industries. ... Reaction and separation in a one-pot reactor, noncorrosive zeolite catalysts, and the elimination of the cooling and transport steps will combine to produce a more efficient process with a tremendous payback in energy savings (approximately 2 trillion BTUs/year in the year 2020).

We are conducting an investigation to identify the most efficient combination of HC mixtures and catalysts to develop an energy-efficient method to produce cumene. The study is part of a larger Sandia study of optimized catalytic reactions. Those early experiments led to this project.

We are comparing different reactants and their efficiency for producing cumene. Four zeolites (beta-zeolite [300:1], beta-zeolite [25:1], hydrogen [H]-zeolite-yttrium [Y] [4:1], and H-zeolite-Y [30:1]) were studied along with different amounts of propylene (14.5 percent and 33.3 percent in nitrogen [N₂]), different mixing rates, and different reaction vessels (T reactor and pot reactor). The complete investigation included 21 experiments. The experiments carried out in this study are meant to transform the current process for producing cumene.

Our accomplishments and findings include the following:

(1) A pot-reactor design and use is more efficient for benzene consumption and cumene production.

(2) Catalyst zeolite beta (75:1 silicon [Si]:aluminum [Al]) produces highest-yield cumene and most-consumed benzene.

(3) Optimized reaction conditions are zeolite beta (see item 2), 150°C, 3/5 reactor stirring speed.

(4) *In situ* MS studies of reaction indicate reaction completed at 60 minutes; cumene production and benzene consumption level off at that time.

(5) Laser ablation studies of zeolitic catalysts are in progress. MS analysis of zeolite fragments is under way.

We are conducting an investigation to identify the most efficient combination of HC mixtures and catalysts to develop an energy-efficient method to produce cumene. The study is part of a larger Sandia study of optimized catalytic reactions. Those early experiments led to this project.

Other Communications

Jarek, R. L., S. M. Thornberg, S. Barrow, and T. M. Nenoff. 2001. "Energy-Efficient Catalytic Reaction and Production of Cumene." Sandia Technical Report SAND2001-3050, Sandia National Laboratories, Albuquerque, NM (September).

26552

A Model of Infrastructure Interdependency Using Communication Agents

D. C. Barton, E. D. Eidson, K. L. Stamber, D. A. Schoenwald, R. J. Pryor, R. G. Cox, A. J. C de Baca

U.S. infrastructure has always been vulnerable to malevolent acts and natural disasters. Today, the most serious threat comes from the increasing complexity and growing interconnectedness of the national infrastructure. The communication infrastructure interconnects all other infrastructures within the national network and enables the transfer of goods, services, and information. Communication constitutes the foundation and is the determining factor in the economic functioning of a society. Several research institutions, including Sandia, are developing agent-based models to simulate infrastructure systems. Current agent-based infrastructure models are limited by their treatment of communication as the always-successful passing of a message between agents. In other words, models do not specifically represent the communication infrastructure. No model simulates the differences among communication by telephone, computer, wireless, or other networks; thus, simulations cannot determine the systemwide impact of specific failures in communication. Nor can current models simulate the impact of other infrastructure failures on the communication infrastructure. Sandia is developing a more useful agent-based model of infrastructure interdependency. The Sandia model represents communication as a separate agent system capable of creating, transforming, sending, receiving, and storing information and messages over time and across distance. Our model treats communication infrastructure as message passing between agents.

This project is developing an agent-based model of infrastructure systems, a model that explicitly simulates the dependence of intra-infrastructure transactions on the communication infrastructure. Although Sandia is already considered a leader in infrastructure-interdependency analysis, specific handling of communication systems in our agent-based models will clearly differentiate Sandia's capabilities in agent-based infrastructure simulations. Project success will provide a unique capability for developing financial-threat assessments (i.e., business-case models) to

U.S. infrastructure has always been vulnerable to malevolent acts and natural disasters. Today, the most serious threat comes from the increasing complexity and growing interconnectedness of the national infrastructure. ... This project is developing an agent-based model of infrastructure systems, a model that explicitly simulates the dependence of intra-infrastructure transactions on the communication infrastructure.

better understand the economic impact of critical-infrastructure failures and the potential impact that financial failures might have on national security.

One of Sandia's project goals is to redesign our agent-based simulation architecture so communication between infrastructure agents is routed through a network of agents representing the communication infrastructure.

We completed background research on the fundamental interactions between communication services and infrastructure systems. We researched the following:

- Basic techniques used by communication companies to handle signal traffic
- Vulnerabilities caused by dedicated satellite configurations
- Dependence of communication systems on power supply
- Reliance of power-generation plants on communication
- The dependence of power-market transactions on the Internet and public-telephone networks.

We defined the following five general categories of agents for inclusion in the agent model that represents a converged-communications market: (1) wholesale supplier, (2) retail supplier, (3) commercial private-network customer, (4) small-business customer, and (5) mass-market (residential) consumer. We also defined the potential adaptive behaviors of communication suppliers and communication customers that will first be implemented in the model. We completed a study from open-source data on the economic impact of telecommunication outages. We found per-hour-cost estimates for several businesses (i.e., brokerage firms and Fortune 1000 companies). From U.S. Senate testimony, we compiled average losses per unplanned telecommunication outage for the following sectors: securities, manufacturing, telecommunications, banking, transportation, retail, and insurance.

We developed a basic message-passing design that includes the interaction of telecommunication agents in the exchange of information between agents. We designed a communication protocol for message passing between agents and modified the existing agent library to utilize these functions. Communication agents are generalized suppliers of communication service.

We developed a basic message-passing design that includes the interaction of telecommunication agents in the exchange of information between agents. We designed a communication protocol for message passing between agents and modified the existing agent library to utilize these functions.

We generalized the basic-agent structure to a provider/user design that employs standardized routines. We redesigned all agents in the model as generalizations of this basic-agent structure, which represents providers and users. We wrote standardized-event routines into the agent library to represent transactions between agents. We implemented the communication company agent as a communication supplier and a user of the materials and power necessary to provide this service. This change will greatly facilitate our ability to more rapidly generate new agent types. We rewrote existing agents using the new design.

We completed the specification of a problem set that simulates reliance of nuclear-power generation on infrastructure transactions; the problem tests the model and interprets the impact of infrastructure interdependencies. We also developed and tested a problem set that examined the impact of power-generation interruption on the industrial sector, both within the blackout region and in areas surrounding the blackout. We prepared the results for presentations that demonstrate the utility of the agent-modeling approach to calculating the economic impact of infrastructure outages.

We redesigned model output so that Extensible Markup Language (XML) files are also produced by a simulation run. We wrote an interactive application that parses the XML file and produces a graphic display. A user can interact with the output data by choosing agents or particular variables for graphic display. The application currently runs on UNIX platforms and is being extended to Windows.

We completed the specification of a problem set that simulates reliance of nuclear-power generation on infrastructure transactions. ... We also developed and tested a problem set that examined the impact of power-generation interruption on the industrial sector, both within the blackout region and in areas surrounding the blackout. We prepared the results for presentations that demonstrate the utility of the agent-modeling approach to calculating the economic impact of infrastructure outages.

Refereed

Barton, D. C. 2001. "Analysis of Complexity in Infrastructure System Using Agent-Based Microsimulation." Chapter in *Complex Systems and Policy Analysis: New Tools for a New Millennium*, edited by J. Kadtke (Arlington, VA: Rand).

Other Communications

Barton, D. C., E. Eidson, and B. Murphy-Dye. 2001. "Analysis of Infrastructure Systems Using Agent-Based Microsimulation." Abstract presented at INFORMS Conference, November.

26553

Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants

R. C. Hughes, D. A. Lucero, C. E. Davis, M. J. Kelley, L. K. McGrath, M. L. Thomas, A. A. McLain, J. A. Zirzow, M. W. Jenkins, M. T. Itamura

Tens of thousands of sites containing toxic-chemical spills, leaking underground-storage tanks, and chemical-waste dumps require accurate characterization and long-term monitoring to reduce health risks and ensure public safety. In addition, the Environmental Protection Agency is regulating more than 2-million underground-storage tanks containing hazardous (and often volatile) contaminants; these tanks require some form of monitoring to detect tank and pipe leaks. However, current methods are costly and time-intensive; also, limitations in sampling and analytical techniques exist. For example, the Department of Energy's Savannah River Site requires manual collection of nearly 40,000 groundwater samples per year; this sampling can cost between \$100 and \$1,000 per sample for off-site analysis. In addition, as much as 80 percent of the costs associated with site characterization and cleanup of a Superfund site can be attributed to laboratory analyses. Analysis integrity can be compromised during sample collection, transport, and storage. Finally, although commercial tools are available for chemical detection (e.g., gas chromatographs), few have been adapted for use in geologic environments for long-term monitoring or remediation applications. Therefore, a need exists for inexpensive, real-time, continuous, in situ sensing and characterization methods.

We performed a literature review of existing and emerging sensor technologies that may be applicable to subsurface monitoring of volatile organic compounds (VOCs). The objective was to identify technologies that provide similar capabilities as the chemiresistor sensor proposed in this project and to determine the advantages and disadvantages of each.

We designed and fabricated a rugged package for the chemiresistor; the package allows the sensor to be placed in subsurface environments (wet or dry) and accommodates both data- and power-transmission requirements of the sensor. We designed, fabricated, and tested a prototype sensor package and cable that satisfy these requirements.

Stainless-steel package for chemiresistor package.

Deployment of a sensor package at the Sandia Chemical Waste Landfill.

We performed calibration studies of the chemiresistors in 100 percent relative-humidity environments. Studies showed that certain polymers can be used successfully in these “wet” environments. In addition, because of the low solubility of many VOCs in water, the chemiresistors can detect compounds such as m-xylene at concentrations as low as 1 part per million (by mass) in water.

We evaluated alternative polymers and additives (e.g., surfactants) to detect chemicals of interest in the presence of high humidity. We selected three to four polymers for optimal array and created inks for deposition onto dyes for chemiresistor fabrication.

We developed novel methods to characterize contaminants *in situ*. The methods use the time-dependent sensor data. We conducted experiments that demonstrate the potential to use these *in situ* sensors to locate the contaminant source during a leak. Additional characterization and optimization methods were also developed using both “passive” and “active” sensing methods. These novel methods were documented and submitted in a Sandia Technical Advance.

We designed and constructed one-dimensional experiments to test the chemiresistor-sensor package and characterization methods in porous media. We observed repeatable results and demonstrated the ability to estimate location of the source term for a contaminant leak using transient *in situ* sensor data and mathematical models of chemical diffusion in porous media.

We initiated a long-term field test at Sandia’s Chemical Waste Landfill. We suspended an *in situ* chemiresistor package 60 feet down a well (D3) to determine sensor longevity and the impacts of temperature, humidity, and barometric-pressure variations (which are being measured at nearby meteorological stations in Tech Areas 3 and 5).

We performed a field test at the HazMat Spill Center at the Nevada Test Site with staff from Bechtel Nevada Corporation. We tested the *in situ* chemiresistor-sensor package in a sand-filled 55-gallon drum contaminated with trichloroethylene (TCE). We recorded real-time data during contaminant emplacement and remediation (air venting) to demonstrate the real-time capabilities of sensor. Also we evaluated the impacts of diurnal-temperature variations and water condensation.

We performed calibration studies of the chemiresistors in 100 percent relative-humidity environments. Studies showed that certain polymers can be used successfully in these “wet” environments. In addition, because of the low solubility of many VOCs in water, the chemiresistors can detect compounds such as m-xylene at concentrations as low as 1 part per million (by mass) in water.

Refereed

Ho, C. K., R. C. Hughes, M. W. Jenkins, M. T. Itamura, M. Kelley, and P. G. Reynolds. 2001. "Microchemical Sensors for *In Situ* Monitoring and Characterization of Volatile Contaminants." *Proc. International Containment and Remediation Technology Conference and Exposition* (10–13 June, Orlando, FL).

Other Communications

Burroughs, C. 2001. "Real-Time Soil and Groundwater Chemical Sensor May Become Electronic 'Sniffer' of the Future." *Sandia Lab News* 53(19) (Sandia National Laboratories, Albuquerque, NM, 21 September), edited by C. K. Ho and R. C. Hughes.

Ho, C. K. 2001. "Characterization Methods for Real-Time *In Situ* Sensing of Volatile Contaminants." Sandia Technical Advance SD-6894, Albuquerque, NM (April).

Ho, C. K. 2001. "LDRD Web Page: Micro-Chemical Sensors for *In Situ* Monitoring and Characterization of Volatile Contaminants." Sandia Technical Report SAND2001-0977W, Sandia National Laboratories, Albuquerque, NM (March).

Ho, C. K., M. T. Itamura, M. Kelley, and R. C. Hughes. 2001. "Review of Chemical Sensors for *In Situ* Monitoring of Volatile Contaminants." Sandia Technical Report SAND2001-0643, Sandia National Laboratories, Albuquerque, NM (March).

Ho, C. K., M. W. Jenkins, R. C. Hughes, and P. G. Reynolds. 2001. "Microchemical-Sensor Package for *In Situ* Monitoring." Sandia Technical Advance SD-6976, Albuquerque, NM (August).

26554

Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management

Y. Wang, C. J. Brinker, C. R. Bryan, Y. Yang

Successful nuclear-waste (and environmental) management requires the development of novel functional materials that can be used for effective waste treatment, containment, and monitoring. Traditional approaches for material development are no longer able to meet increasing waste-management needs. Fortunately, with the emergence of nanotechnology, we are now able to manipulate material structures at nanoscales, thus opening up unlimited possibilities for new functional material development. Sandia will investigate the potential applications of mesoporous nanostructured materials (NsMs) in waste management. Mesoporous NsMs possess nanopore structures and are synthesized using self-assembled supramolecular templating processes. Due to very large surface area, controllable pore size, and overlapped electrical double layer, NsMs can potentially be good ion getters, separation membranes, catalysts, and sensing materials with high sorption capacity and chemical selectivity. Specifically, we will (1) study the sorption capability of mesoporous NsMs versus non-nanostructured materials, (2) use surfactant-templating processes to synthesize mesoporous anionic clays and test their sorption capacity for arsenate and other anions, (3) modify the pore surface chemistry of mesoporous silica with functional molecules for developing high-performance ion getters and sensing materials for volatile organic compound (VOC) detection, and (4) if the time allows, investigate the photocatalytic effect and pore-size control of mesoporous titanium dioxide (TiO₂) films on the oxidation of organic chelators. This work will demonstrate a wide range of applications of NsMs in nuclear-waste management and establish the theoretical foundation and engineering approaches for such applications. One of the final products of this project will be a set of functional materials with demonstrated capabilities that can be potentially used as high-performance ion getters, catalysts, and sensing materials. The success of the project will create a synergistic

Successful nuclear-waste (and environmental) management requires the development of novel functional materials that can be used for effective waste treatment, containment, and monitoring. ...

Sandia will investigate the potential applications of mesoporous nanostructured materials (NsMs) in waste management. ...

This work will demonstrate a wide range of applications of NsMs in nuclear-waste management and establish the theoretical foundation and engineering approaches for such applications.

effect across Sandia's nuclear-waste/environmental management, advanced material development, and chemical-sensor development.

(1) We determined the capability and kinetics of anion sorption on conventional-anionic clays.

(2) We initiated the synthesis of mesoporous layered double hydroxides (LDH).

(3) We synthesized simple-composition mesoporous materials and carried out the preliminary test for ion-sorption capability and kinetics.

Specifically, we measured the capability and kinetics of various anions on activated and nonactivated hydrotalcite. Activated materials were found to have much higher sorption capacities than the nonactivated ones. We clarified the detailed sorption mechanism. We synthesized various nanostructured materials using supramolecular-templating processes and tested them for their surface-chemical properties and ion-uptake capabilities. We demonstrated that the surface charge on mesoporous materials can be 45 times as high as that on non-mesoporous materials. We demonstrated that the overlap of electric double layer (EDL) has a significant effect on ion sorption on mesoporous materials. The effect was fully taken into account by the existing surface-complexation models. Our work has proved the concept of using mesoporous materials as effective ion adsorbents in nuclear-waste management. We synthesized and characterized about 30 different surfactant-templated LDH. We made considerable progress in understanding the packing of surfactant molecules in the interlayer of LDH. We tested some of these materials for anion sorption, and they showed very promising results. We filed one patent application related to the synthesis of LDH.

Our work has proved the concept of using mesoporous materials as effective ion adsorbents in nuclear-waste management. We synthesized and characterized about 30 different surfactant-templated LDH. We made considerable progress in understanding the packing of surfactant molecules in the interlayer of LDH. We tested some of these materials for anion sorption, and they showed very promising results.

26555

Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles

H. A. Michelsen, R. L. Farrow, P. O. Witze

Newer-generation compression-ignition direct-injection (CIDI) diesel engines were designed for low-particulate-matter mass emissions and to emit no visible soot. However, CIDI diesels may generate far greater numbers of small particles than do older diesel engines. Hybrid cars incorporating CIDI engines are expected to be commercially available in the U.S. by 2004. New evidence strongly suggests that gasoline engines also emit large numbers of small particles under some operating conditions. These small (submicron) particulates are classified as a toxic emission in California. The emissions may pose a greater health risk than larger soot particles and are expected to have a significant impact on Earth's climate. Therefore, small-particulate emissions are an emerging concern.

Sandia is developing the capability to determine size and mass distributions of submicron soot particles. This capability will support future studies on soot formation in flames as well as in diesel and gasoline engines and studies on particle evolution when cooled and diluted. Our goal is to study nanoparticle formation and evolution using noninvasive optical techniques, particularly laser-induced incandescence (LII), to measure particle-mass concentrations and to use laser elastic scattering (LES) to determine particle size.

We built a system to collect LII data and have used this system to record time-resolved LII signals from ethylene and propane-diffusion flames over a wide range of laser fluences. LII involves using laser irradiation to heat soot particles to temperatures (2500 K to 4500 K) at which the particles incandesce and then detecting the emitted light. To heat the particles, we used the second harmonic of a neodymium (Nd):YAG laser with pulse energies at 532 nm ranging from 10 to 430 mJ and corresponding to fluences of 0.027 to 1.16 J/cm². We passed this beam through a laminar-diffusion flame with an outer annular coflow of air, and we imaged the broadband-LII signal from the central portion of the laser beam onto a photodiode with a response time of less than 0.3 ns. At laser fluences below approximately 0.2 J/cm²,

Sandia is developing the capability to determine size and mass distributions of submicron soot particles. This capability will support future studies on soot formation in flames as well as in diesel and gasoline engines and studies on particle evolution when cooled and diluted. Our goal is to study nanoparticle formation and evolution using noninvasive optical techniques, particularly laser-induced incandescence (LII) to measure particle-mass concentrations and to use laser elastic scattering (LES) to determine particle size.

signals increase dramatically with increasing fluence. More light is absorbed at increased fluence, leading to higher temperatures and LII signals. As the fluence increases above 0.2 J/cm^2 , the maximum signal increases less significantly than in the lower-fluence regime, and the peak becomes sharper and moves to earlier times. The particles become hot enough to sublime at these fluences, which leads to rapid cooling during the laser pulse in addition to particle-size reduction and, consequently, lower absorption.

To analyze these data and study the applicability of LII, we developed a model to describe the heating of soot particles during the laser pulse and the subsequent cooling of the particles by radiative emission, sublimation, and conduction to the surrounding atmosphere. The model also accounts for physical phenomena such as (1) changes in the particle density and specific heat with temperature, (2) oxidation of the particle, (3) primary-particle annealing, (4) laser-induced melting, and (5) nonequilibrium pressure and temperature gradients at the particle surface during sublimation. This model reproduces the general features that the data demonstrated. However, the inclusion of melting in the model predicts temporal profiles that are not seen experimentally. This result suggests that, under our experimental conditions, the particles do not melt (in contrast to studies on bulk graphite).

To narrow the model uncertainties, we are developing a flame-based source of soot that will allow us to determine and control parameters, such as initial-particle and ambient-gas temperatures and the partial pressure of oxygen. We are using a scanning-mobility particle sizer (SMPS) to characterize the source. We tried two noncombustion-based methods for soot generation. The first method was to atomize a liquid suspension of lampblack in methanol and then dry the resulting aerosol. Using a medical nebulizer with a capacity of 6 cm^3 limited the runtime to about 6 minutes. During this time the methanol was preferentially atomized, and the lampblack concentration in the suspension increased, resulting in a continual increase in the lampblack-aerosol concentration. In addition, vaporized methanol condensed in the SMPS, influencing the measured size distribution. Using a nebulizer with a larger volume to increase the runtime caused day-to-day increases in lampblack concentration that resulted in a mixture of unknown concentration. Changing the solution frequently enough to avoid this problem created a chemical-waste disposal problem.

To analyze these data and study the applicability of LII, we developed a model to describe the heating of soot particles during the laser pulse and the subsequent cooling of the particles by radiative emission, sublimation, and conduction to the surrounding atmosphere. ...

This model reproduces the general features that the data demonstrated. However, the inclusion of melting in the model predicts temporal profiles that are not seen experimentally. This result suggests that, under our experimental conditions, the particles do not melt (in contrast to studies on bulk graphite).

We also tried laser ablation of pure graphite. During a 2-hour period, the particle-size distribution was fairly uniform, but the concentration fell by nearly an order of magnitude because the stationary graphite surface eroded. Spinning and translating the graphite rod to continuously provide a fresh surface and, thus, correct this problem is too complex and does not allow for changes in the soot composition and morphology.

To further test the model, we will measure the spectrally resolved LII signal during and after the laser pulse from which we will infer time-resolved temperatures as the particle is heated and cooled. We purchased the spectrograph, calibrated it using an arc lamp, and wrote software to facilitate use of the data collected.

To further test the model, we will measure the spectrally resolved LII signal during and after the laser pulse from which we will infer time-resolved temperatures as the particle is heated and cooled.

26556

Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion

S. Y. Lin, J. B. Moreno, J. G. Fleming

Thermophotovoltaics (TPV) convert the radiant energy of a thermal source into electrical energy using photovoltaic (PV) cells. TPV has a number of attractive features including fuel versatility (nuclear, fossil, solar, and others), quiet operation, low maintenance, low emissions, light weight, high-power density, modularity, and the possibility for cogeneration of heat and electricity. If the efficiencies could be raised to about 30 percent, TPV could also be used for distributed power and automotive applications wherever fuel cells, microturbines, or cogeneration are being considered.

TPV is an old concept but has only recently attracted much research interest because of the above features of TPV and recent advances in low-bandgap (0.5 to 0.7 eV) III-V semiconductor technology. Low-bandgap PV cells are required to work with radiators at manageable temperatures (1300 K to 1800 K).

This project will primarily examine approaches to improving the radiative efficiency. A number of approaches (blackbody radiators with optical filters or selective radiators using rare-earth elements) have been advanced, but none of these approaches has yet been able to advance TPV-conversion efficiencies beyond 10 percent.

Sandia will examine photonic crystals and advanced-optical structures to substantially improve the radiative efficiency in TPV. Photonic lattices use a periodic modulation of the refractive index to alter the photonic density-of-states spectrum. Photonic lattices can alter the radiative spectrum and angular distribution of a radiator, or lattices can be used as an optical filter with a potentially 180° acceptance angle for a three-dimensional (3-D) photonic lattice (also called the photonic crystal).

(1) Successful realization of 3-D metallic-photonic crystals. We directed much interest at the 3-D metallic-photonic crystal since obtaining a larger photonic bandgap as well as for achieving a new electromagnetic phenomenon and for high-temperature (greater than 1,000°C) incandescent-lamp applications. Studies of metallic-photonic crystals

Thermophotovoltaics (TPV) convert the radiant energy of a thermal source into electrical energy using photovoltaic (PV) cells. ...

This project will primarily examine approaches to improving the radiative efficiency. ...

Sandia will examine photonic crystals and advanced-optical structures to substantially improve the radiative efficiency in TPV.

mostly concentrate on microwave and millimeter wavelengths, mainly because of fabrication difficulties.

Using a novel method, we have, for the first time, realized a 3-D metallic-photonic crystal in the infrared (IR) wavelength. We realized fabrication of the tungsten (W) structures by selectively removing silicon (Si) from already fabricated polysilicon/silicon-dioxide (SiO_2) structures, backfilling the resulting mold with chemical-vapor-deposited W, and then removing excess W on the wafer surface. The 1-D W rodwidth is $1.2\ \mu\text{m}$, and the rod-to-rod spacing is $4.2\ \mu\text{m}$. The bottom V-groove is formed because of the slow potassium hydroxide etching planes of the substrate. The step coverage of the deposition process is not 100 percent; this leads to the keyhole formation in the center of the more deeply embedded lines.

(2) Experimental observation of the largest-ever photonic bandgap in the IR wavelengths. The measured reflectance (black) and transmission (blue) spectra are for light propagating along $\langle 001 \rangle$ axis. The simultaneous observation of a high reflectance and a low transmittance for $\lambda > 6\ \text{mm}$ is indicative of a large metallic-photonic bandgap. The attenuation is approximately 30 dB at $\lambda = 10\ \mu\text{m}$ for our four-layer sample, or equivalently a 7.5 dB attenuation per layer, also the strongest ever reported for any 3-D crystal in the IR. The high transmission at $\lambda \sim 5\ \mu\text{m}$ is from band propagation of light through this otherwise impenetrable metallic mesh.

(3) Discovery of the nature of light propagation in a W 3-D photonic crystal. To gain insight into the nature of light propagation in a metallic-photonic crystal, we carried out a finite-difference time-domain calculation for a six-layer W 3-D photonic crystal structure. We found that the periodic metallic-air boundaries mold the flow of the lightwave, dictate its transport characteristics, and particularly slow down the speed of light at the photonic band edge.

Using a novel method, we have, for the first time, realized a 3-D metallic-photonic crystal in the infrared (IR) wavelength. ...

The measured reflectance (black) and transmission (blue) spectra are for light propagating along $\langle 001 \rangle$ axis. The simultaneous observation of a high reflectance and a low transmittance for $\lambda > 6\ \text{mm}$ is indicative of a large metallic-photonic bandgap. The attenuation is approximately 30 dB at $\lambda = 10\ \mu\text{m}$ for our four-layer sample, or equivalently a 7.5 dB attenuation per layer, also the strongest ever reported for any 3-D crystal in the IR.

26557

Specific Anion Nanoengineered Sorbents for Water Purification

D. M. Teter, J. L. Krumhansl, P. V. Brady, N. R. Khandaker

Water surety will be one of the dominating issues of the twenty-first century. Access to safe and affordable drinking water is essential to both domestic welfare and international security. One of the outstanding needs in water treatment is materials that can affordably and effectively remove toxic anions such as arsenate, chromate, perchlorate, fluoride, and selenate. At present there are no inexpensive and effective anion getters. The looming obstacle of inadequate arsenic (As) treatment also dooms many poor countries to diminishing health and wealthier countries to rapidly escalating water-treatment costs.

Nanoengineered materials developed at Sandia are poised to provide a technological solution to prevent this problem. Recently, we predicted a priori a materials ability to remove contaminants. We are now able to predict the outcome of sorption processes at the atomic scale, and engineer materials to selectively sorb contaminant anions. Early experimental work confirms that these materials sorb As and chromium (Cr) and have the potential to substantially lower drinking-water treatment costs. Because our materials proceed from a fundamental understanding of anion sorption, we expect that they can likewise be repeated for other groundwater contaminants and open up a nearly unlimited global market for purification of drinking water.

New approaches are needed for removing As from drinking water to reduce the financial impact of tighter regulatory standards. Lowering allowable drinking-water levels of As from 50 parts per billion to 10 parts per billion—or lower—will result in new water-treatment costs exceeding \$1 billion nationwide if existing As-removal technologies (such as coagulation/microfiltration with aluminum [Al] or iron [Fe], fixed-bed filtration using activated alumina (AA) or granular ferrihydrite [GFH]) are used.

Development of new filter media, or coagulants, possessing higher As affinities is a potentially effective means to lower As-removal outlays. Existing coagulation and filtration approaches rely on the double-layer properties of Al or Fe hydroxides to electrostatically sorb arsenate from

Water surety will be one of the dominating issues of the twenty-first century. Access to safe and affordable drinking water is essential to both domestic welfare and international security. ... Nanoengineered materials developed at Sandia are poised to provide a technological solution to prevent this problem. Recently, we predicted a priori a materials ability to remove contaminants. ... Because our materials proceed from a fundamental understanding of anion sorption, we expect that they can likewise be repeated for other groundwater contaminants and open up a nearly unlimited global market for purification of drinking water.

solution. Double-layer affinities for arsenate can be boosted during coagulation and filtration by engineering mixed-oxide (MOX) surfaces to have a higher zero point of charge (zpc). We used initial kilodalton (Kd) measurements to identify materials with high zpc and maximal As sorption tendencies. These results were then used to predict, and ultimately design, high-zpc MOXs. Freundlich isotherms were then measured for candidate sorbents, as well as AA and GFH. We ultimately performed rapid small-scale column tests to establish the relative As-removal efficiencies of candidate materials under pilot-scale water-treatment conditions. Because the double-layer properties that control filtration and coagulation removal are closely linked, the MOX stoichiometries developed for fixed-bed filtration studies can be used to develop new coagulation strategies.

Because the double-layer properties that control filtration and coagulation removal are closely linked, the MOX stoichiometries developed for fixed-bed filtration studies can be used to develop new coagulation strategies.

32575

Active Management Systems for Water-Quality Monitoring

P. R. Lewis, H. R. Westrich, R. C. Hughes, E. E. Tarver, III, P. J. Rodacy, S. M. Brozik

Water is our most valuable shared resource, but in the next 20 years, half the countries in the world will face significant water shortages. These shortages will significantly limit economic development, lead to widespread health problems, and cause regional and international conflicts. Emerging threats to water supplies from terrorism, natural disasters, pollution, ineffective management, and excessive demands could cause major instabilities worldwide that will affect national security.

Sandia has completed a strategic planning effort for water, reviewing and assessing our future role in this area. In support of our DOE mission, Sandia developed capabilities in systems engineering, environmental restoration, geohydrology, infrastructure protection, international security, modeling, and materials science that are presently being used in several water-related projects. To enhance our ability to support future water security and sustainability initiatives to reduce conflict and improve national security, we integrated these capabilities and projects into a focused, labwide, water program. Our water research and development activities will be focused in three areas: (1) improving water infrastructure protection, (2) improving cooperative water-management approaches to reduce conflict, and (3) developing solutions to reduce water scarcity through better treatment and conservation techniques.

The three activities presented support research in these focus areas. The first effort will look at the use of innovative μ ChemLab™ technology to enable inexpensive, real-time monitoring for chemical/biological agents and other contaminants in water supply and distribution systems. The second effort will look at the use of new high-resolution, multispectral remote-sensing data, including synthetic-aperture radar (SAR), to measure surface water flows to enable inexpensive active river management. The third effort will look at using novel dynamic simulation modeling approaches to develop an integrated surface- and

Water is our most valuable shared resource, but in the next 20 years, half the countries in the world will face significant water shortages. ...

Sandia has completed a strategic planning effort for water, reviewing and assessing our future role in this area. In support of our DOE mission, Sandia developed capabilities in systems engineering, environmental restoration, geohydrology, infrastructure protection, international security, modeling, and materials science that are presently being used in several water-related projects.

groundwater-management tool to improve the assessment of water policy and management options and decisions by water managers.

We evaluated individually several emerging technologies that we envision as forming the basis of an integrated active water-management system that includes everything from the actual sensor to the knowledge-based system used for decision making. The concept includes the notion of real time where *real time* can mean results in seconds or minutes. Active management encompasses modeling and simulation to better understand how the system responds to various inputs and outputs. Results for specific technologies are listed below.

Biological sensing. We briefly investigated ion-mobility spectrometry (IMS) as a means for trace, field-based chemical detection and for differentiation of biological organisms (bacteria and viruses) in water supplies. Issues of sample injection and ionization were mastered despite the relatively large mass and size of the biologic agents. Modeling of the system suggests that biologic agents should be detectable and differentiable by the IMS sensor system.

Trihalomethanes sensing. Trihalomethanes (THMs) are a by-product of the chlorination process and are Environmental Protection Agency-regulated compounds. After minor changes to the μ ChemLab™ sensor system, we detected all four compounds. Three of the four compounds were discriminated with baseline resolution. In an analysis cycle lasting only 80 sec, the system achieved a detection limit of 30 parts per billion. We realized a new design for concentrating volatile organics in the execution of this project.

Inorganics sensing. We evaluated the capabilities of IMS and laser-induced fluorescence (LiF) analytic techniques for anion analyses. We used electrospray ionization to inject nitrate and nitrite solutions for IMS analysis. Detection limits appear feasible down to low parts-per-billion levels. A literature search indicates that indirect LiF methods could be adapted for inorganic anion analysis in the μ ChemLab™ liquid-phase system.

Chemiresistor sensing. Chemiresistors offer rapid and inexpensive detection of a variety of harmful chemicals in water; however, detection limits are in need of improvement. By coupling the Sandia micro-hotplate preconcentrator with an array of Sandia chemiresistors, we achieved significant

After minor changes to the μ ChemLab™ sensor system, we detected all four compounds. Three of the four compounds were discriminated with baseline resolution. In an analysis cycle lasting only 80 sec, the system achieved a detection limit of 30 parts per billion. We realized a new design for concentrating volatile organics in the execution of this project.

improvement in the detection limits of volatile-organic compounds (VOCs) under field-sampling conditions.

Remote sensing. We assessed state-of-the-art remote-sensing and research expertise at Sandia relative to their potential for remote measurement of river discharge. Though existing technologies show promise, remote-sensing systems need substantial development to increase accuracy to the levels needed for full utilization. Sandia research activities, especially in SAR development, could play a major role in remote-sensing improvements for water-quantity measurements.

Resource management. Employing the decision framework of system dynamics, we developed a water-budget model for the Middle Rio Grande River Basin. The model balances surface- and groundwater supply against growing demand in the municipal, agricultural, and industrial sectors. The integrated model allows the user to probabilistically assess alternative water-management/-conservation strategies in real time. Specifically, sustainability of water supply is quantitatively determined for uncertain changes in the climate, population growth, water-conservation policies, bosque management, and agricultural irrigation practices.

Other Communications

Danneels, J. 2001. "Active Water Management."
Sandia Technical Report, in preparation.

*Sandia research activities,
especially in SAR development,
could play a major role in
remote-sensing improvements
for water-quantity
measurements.*

32807

Low-Work-Function Material Development for the Microminiature Thermionic Converter

D. B. King, D. R. Jennison, C. C. Battaile, K. R. Zavadil

Microminiature thermionic converters (MTCs) provide a unique approach to developing power sources. Possible applications range from micron- to large-scale and include microrobotics and sensors, space-based power, mobile and remote electrical-power sources, and commercial-power production. MTCs can be scaled from the microwatt range to kilowatts. Sandia has made significant progress in developing small-scale MTCs; however, the electrode materials are not well understood, and thermionic properties are highly sensitive to the electrode-chemical content, bulk and surface structure, and manufacturing processes. Advanced theoretical and modeling capabilities are required to achieve the desired thermionic emission from the electrode materials, aid in the electrode-fabrication process, and enhance the performance of MTC diodes. Sandia's advanced thermionic theory and detailed modeling of properties that influence thermionic-electron-emission performance will greatly enhance understanding of thermionic diodes. (Using only an experimental approach is costly; a better theoretical understanding is needed to guide the expensive fabrication process.)

Sandia developed and tested a prototype MTC diode. The diodes are an innovative design using advanced-electrode materials to convert heat to electricity. These diodes have the potential for operating at low temperatures (below 1200 K), while increasing conversion efficiency (up to 25 percent) and increasing the electrical-power density to tens of watts per cubic centimeter. Currently, prototype MTCs fall short of theoretical performance predictions because of poor performance from the electrode materials. The integration of Sandia's development and test experience, advanced modeling, microfabrication, and materials expertise will make Sandia a leader for advanced thermionic-energy-conversion technology and MTC development.

We made progress in both modeling and initial verification experiments. We demonstrated the successful fabrication of a thin-film microdispenser cathode. We deposited the film as a set of modulated tungsten (W) and a

(a) Schematic of simulation lattice: Colored sites are grains, black sites are pores, and white sites are diffusing. (b) Example of simulation microstructure: Colored regions are tungsten grains, empty regions are pores, and red spots are diffusing barium.

Images of (a) a million-site porous polycrystal, and (b) a map of the total flux at each node in it. The colors in (a) simply distinguish different grains, and in (b) they represent an arbitrary logarithmic flux scale where blue is low and red is high.

BaO:CaO:Al₂O₃, 4:1:1 mole fraction layer using sputter deposition. We terminated the surface of this film with a thin layer of scandia and rhenium. The film is electron emissive at temperatures up to 1300 K. We completed microstructural- and compositional-evolution measurements with time and temperature. Annealing resulted in W coalescence into particles and formation of voids. Coalescence was coupled with the formation of a W phase that acts as a reductant to form free barium (Ba). These results demonstrate that the mechanisms for Ba generation and transport to the cathode surface can be built into thin-film cathodes. Retaining metal termination at the surface is key to lowering the work function. Scanning-electron spectroscopy shows that annealing eventually results in loss of very thin metal-surface layers into the bulk. We are testing thicker films using W/iridium layers. This alloy forms hexagonal closest-packed domains that, when modified by Ba and oxygen (O), further lower the surface work function.

Modeling to correlate Ba transport and pore/grain structure focused on code development and creation of a preliminary digital-microstructure model. We created microstructures using evolution models that ensure topologically realistic structures. The mathematical modeling comes from combining Fick's laws of diffusion with finite-difference (FD) techniques. The diffusivity between FD nodes assumes an individual value depending on whether the nodes lie on a grain boundary, pore wall, or elsewhere. We gauged the efficiency of transport "free surface" of the microstructure. Results show that flux at the free surface varies significantly with grain size only at low-pore densities where grain-boundary diffusion contributes to the overall flux. As high-diffusivity pore walls are introduced into the microstructure, the flux increases and becomes more uniform across the range of grain sizes. At higher pore densities where pore interiors dominate, the flux decreases.

We used density-functional calculations to calculate the probable energy structures for Ba-O surface complexes with various coverage percentages. We constructed a slab composed of seven layers of W atoms. We calculated three coverage schemes and their resulting work functions: 1/2 monolayer of Ba (Ba has a radius of 2.22 Å versus 1.41 for W, so full coverage is not possible within a single layer) - 2.25 eV; 1/2 monolayer of each Ba and O, making 1 monolayer of BaO - 2.7 eV; and then 1 monolayer of Ba above 1 monolayer

We completed microstructural- and compositional-evolution measurements with time and temperature. Annealing resulted in W coalescence into particles and formation of voids. Coalescence was coupled with the formation of a W phase that acts as a reductant to form free barium (Ba). These results demonstrate that the mechanisms for Ba generation and transport to the cathode surface can be built into thin-film cathodes. Retaining metal termination at the surface is key to lowering the work function.

of O in contact with the W(110) surface (i.e., chemisorbed O - 1.7 eV). This indicates that it is not Ba, nor a layer of Ba over chemisorbed O/W(110), but BaO on W(110) that minimizes the work function. Since Ba is more electropositive than W, BaO preferentially forms when Ba exists on the surface of W, and oxidized Ba has a small-enough radius so 1 monolayer of BaO is nearly coplanar on W(110).

We completed a patch model that calculates the potential energy-barrier profile that is generated above a thermionic surface when patches of different work functions contact each other. Two work-function distributions can be modeled (a step distribution and an exponentially varying distribution). We calculated the energy-barrier profile as a function of work-function distribution and diode bias. We also completed transmission coefficient models of electrons crossing the emission surface with and without patches using quantum techniques. The patch and transmission models are used to model the average effective-transmission coefficient, D_E , of the entire emitter surface. We completed two models of D_E and inserted them into the diode-performance code.

We completed a patch model that calculates the potential energy-barrier profile that is generated above a thermionic surface when patches of different work functions contact each other.

Refereed

King, D. B., J. R. Luke, and K. R. Zavadil. 2001. "The Microminiature Thermionic Converter." *Proc. AIP Conference, Space Technologies and Applications International Forum* **552** (Albuquerque, NM, 11–14 February): 1152–1157.

Marshall, A. C., and D. B. King. 2001. "Application of Revised Thermionic Theory to MTC Diodes." *Proc. AIP Conference, Space Technologies and Applications International Forum* **552** (Albuquerque, NM, 11–14 February): 1158–1164.

Zavadil, K. R., and D. B. King. 2001. "Thin-Film Dispenser Cathodes for Thermionic Micro-Devices." *Proc. Fall 2001 MRS Meeting*, accepted.

Zavadil, K. R., D. B. King, and J. A. Ruffner. 2001. "A Novel Thin-Film Dispenser Cathode for Thermionic Emission." *Proc. AIP Conference, Space Technologies and Applications International Forum* **552** (Albuquerque, NM, 11–14 February): 1165–1170.

32809

Autonomous Microexplosive Subsurface Tracing System

N. R. Warpinski, S. H. Kravitz, M. C. Grubelich, S. E. Eskridge, B. V. Ingram, R. J. Carlton, B. M. Melof, J. J. Nogan, G. R. Dulleck, Jr.

In this project, Sandia seeks to image the location and geometry of hydraulically induced or naturally occurring fractures in subsurface petroleum or waste-disposal reservoirs. The basic concept is to use existing fracturing technology (e.g., pump trucks, fluid systems) to insert autonomous microenergetic packages throughout the hydraulic fracture, have those packages function (i.e., trigger and explode) under appropriate conditions, detect the induced seismic energy with available seismic-receiver arrays, and use conventional processing techniques to determine the source location, thereby marking the fracture. The packages are to be designed and built to function at appropriate times or under appropriate environmental conditions (e.g., timer, pressure switch, reaction with fluid), have sufficient energy and risetime to produce detectable seismic waves, and have external packaging capable of surviving in a harsh environment (high-pressure, somewhat-elevated temperature, highly abrasive, aqueous conditions). To fit in the fracture, the microenergetic devices need to be quite small but may have a shaped design with a small cross-sectional area. To realize this technology, the key research questions that need to be addressed are the following:

- (1) Determine the minimum detectable size of a microenergetic device using seismic monitoring. We are currently working in the range of a few tenths of an inch.*
- (2) Construct trigger mechanisms to function at appropriate times and conditions. Trigger mechanisms being investigated are both reactive coatings and electronic devices.*
- (3) Produce a device with energy-release rates appropriate for seismic monitoring. We identified materials with appropriate parameters and are characterizing them.*
- (4) Pack sufficient energy into a package small enough to fit into subsurface fractures. We are studying packaging shapes and volumes.*

A combination of modeling, laboratory experiments, and field tests are required to achieve the objectives. We envision that the successful development of autonomous microenergetic devices could then be used for other

In this project, Sandia seeks to image the location and geometry of hydraulically induced or naturally occurring fractures in subsurface petroleum or waste-disposal reservoirs.

applications involving both critical infrastructures (pipelines, dams) and military (underground structures) applications.

We made progress on the autonomous microexplosives along two parallel lines of work: (1) finding and characterizing the energetic materials that are appropriate and (2) developing methods for triggering that material.

We expended considerable work on finding a primer mix to initiate a detonation. Originally, cesium (Cs) or related metals were expected—when put in contact with water in the fractures—to react vigorously and supply sufficient heat to vaporize the water and generate a steam explosion. However, testing in a specially constructed test chamber showed that the pressure pulse generated by such a reaction was insufficient for project parameters.

The poor reactions of such metals set off a search for other materials. Many that were tested produced violent reactions, but all with insufficient energy or poor reliability. We discovered two reactions that appear to be more than sufficient, including the reaction of silver nitrate and magnesium (Mg) upon contact with water and ceric ammonium nitrate, and Mg upon contact with water. We investigated both reactions at length and found them to show prompt and reliable vigorous activity that can fire an explosive component and possibly to be sufficiently energetic alone that an explosive component may not be required.

Thus, a material system has essentially been chosen. The system will include a silver nitrate and Mg primer mix that will react with water to initiate an output charge (if necessary). We have already selected bis(5 nitrotetrazolato) pentaaminecobalt(III) perchlorate (BNCP) for the output charge because of its good energy output and ability to detonate in a very short distance. Work is ongoing on tailoring the materials to obtain an optimum pulse.

Considerable work remains to characterize the materials. We are constructing a Henkin tester to evaluate the time for the materials to cook off at temperature and are designing other test programs. Additionally, the test chamber has had a complete pressure evaluation to prepare for testing.

The triggering-process work took place along two separate approaches. The simple approach was to design a case with a corrodible plug having an appropriate “safe time” based on fracturing conditions and other parameters (typically a couple of hours).

We discovered two reactions that appear to be more than sufficient, including the reaction of silver nitrate and magnesium (Mg) upon contact with water and ceric ammonium nitrate, and Mg upon contact with water. We investigated both reactions at length and found them to show prompt and reliable vigorous activity that can fire an explosive component and possibly to be sufficiently energetic alone that an explosive component may not be required.

The more sophisticated triggering process involves the use of a microsemiconductor bridge (SCB). In this design, some power source (battery or capacitor) would power a timer to fire the SCB. Work in this area has proceeded along three lines: (1) developing a micro-SCB that could function with a low-power source, (2) finding and testing low-power-source timers, and (3) evaluating both capacitors and batteries for the internal-power requirements.

In developing the micro-SCB, the main problems have been the substrate material, the packaging, W film stress, and gold (Au) delamination. We are now trying quartz as an alternative to silicon (Si) for the substrate material because Si reduces the potential for short circuit of the bridge during assembly, eliminates the need for silicon-dioxide (SiO_2) barrier between amorphous Si and the substrate, and enhances thermal and electrical insulation of the device from the package and ground.

In the fabrication area, we made enhancements to the standard W-sputtering process, eliminated the titanium (Ti) barrier between the Si and W, and are circumventing a Au-delamination problem. We constructed and tested both Si- and quartz-substrate SCB devices, showing that these devices will fire at 20 V, and the function time is inversely proportional to voltage applied. These devices fired a 75 mg charge of titanium subhydride potassium perchlorate (THKP) pressed to 12 Kpsi (thousand pounds per square inch), a small-enough charge to fit into the envisioned microexplosive pellet.

Investigation of timers and power sources show that the timers probably require more power than a microcapacitor could provide and that concentrating on miniature batteries for power may be necessary. Both sources provide sufficient energy to fire the SCB. Work continues on developing a method to turn on the power source (e.g., just before it gets injected).

In the fabrication area, we made enhancements to the standard W-sputtering process, eliminated the titanium (Ti) barrier between the Si and W, and are circumventing a Au-delamination problem. We constructed and tested both Si- and quartz-substrate SCB devices, showing that these devices will fire at 20 V, and the function time is inversely proportional to voltage applied. These devices fired a 75 mg charge of titanium subhydride potassium perchlorate (THKP) pressed to 12 Kpsi (thousand pounds per square inch), a small-enough charge to fit into the envisioned microexplosive pellet.

Other Communications

Warpinski, N. R., M. C. Grubelich, and S. H. Kravitz.
2001. "Autonomous Micro-Explosive Subsurface Tracing System." Sandia Technical Report SAND2001-0731, Sandia National Laboratories, Albuquerque, NM (March).

32810

Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar

C. J. Weiss, T. W. H. Caffey

Borehole-radar (BHR) systems can provide essential subsurface information for environmental, geotechnical, or energy-exploration use. Existing BHR, operating in pulsed mode, are used for shallow applications such as environmental site characterization.

BHRs are not useful for oil and gas exploration because the high-peak power requires dielectric materials that cannot be successfully operated at the high temperatures found at great depth. A new type of continuous-wave (CW) BHR, featuring a very high efficiency, heat-tolerant amplifier, has great potential for deep subsurface imaging. Sandia has already developed a prototype of the CW BHR and has worked to make this technology into a viable commercial instrument. The new instrument is designed to operate in the frequency range of 12.5 to 4004 kHz at depths of more than 8000 feet and at temperatures of 70°C.

Previous work did not support the advanced analysis and imaging of the BHR data. The objective of this project is to apply Sandia's advanced electromagnetic modeling and inversion algorithm to the data collected by BHR.

Modifications to the BHR instrument are currently under way, and a second field exercise is tentatively planned. Analysis of this upcoming dataset will appear in a future report.

We developed a new three-dimensional (3-D) modeling code to enable the analysis of BHR data on modest-sized desktop workstations. Based on the staggered-grid finite-difference (FD) technique, the code (FDM3D) eliminates 55 percent of the massive storage costs associated with solving the FD system of linear equations. This is achieved by employing a matrix-free paradigm, where at each step of the iterative linear solver, the matrix action is computed "on the fly" without the need to store the matrix. Thus, model problems that previously required more than 2 GB of in-core memory on a high-end workstation can now be evaluated on commodity personal computers (PCs).

Sandia has already developed a prototype of the CW BHR and has worked to make this technology into a viable commercial instrument. The new instrument is designed to operate in the frequency range of 12.5 to 4004 kHz at depths of more than 8000 feet and at temperatures of 70°C. ...

We developed a new three-dimensional modeling code to enable the analysis of BHR data on modest-sized desktop workstations. ...

Thus, model problems that previously required more than 2 GB of in-core memory on a high-end workstation can now be evaluated on commodity personal computers.

Preliminary analysis suggests that the instrumentation noise is sufficiently high that any inversion procedure would likely produce nonsensible results.

Regardless, we evaluated various “What if ...?” scenarios to determine what the BHR instrument response should be.

32815

Security Models of Agent-Based Coalitions

S. Y. Goldsmith, R. C. Parks, C. L. Beaver, L. R. Phillips, W. F. Young, H. E. Link, M. C. Kidd, S. V. Spires

Sandia's Advanced Information Systems Laboratory has pioneered development of intelligent agent-based coalitions that utilize group cryptography to maintain high-integrity operations under attacks from both outsiders and malicious insiders. These systems refresh code components and secret data periodically to render ineffective efforts that compromised agents make to destroy the integrity of the coalition.

Under previous work, some simple stochastic models of the dynamic integrity of such a coalition under various refresh regimes were developed to support engineering of prototype-agent systems. We incorporated proactive-threshold protocols into the autonomous-agent collective.

In this research project, we will study system models and security policies surrounding autonomous-multiagent coalitions that use proactive-threshold protocols to certify collaborative computations and consensual results. We will not investigate the cryptographic protocols per se. We will model the dynamics of the agent coalition with respect to security parameters, describing how the parameters change over time and are influenced by various update regimes under various security policies.

Sandia accomplishments include the following:

- *Development of security policies for autonomous collectives.* We analyzed the policy issues surrounding deployment of an autonomous coalition in an institutional computing environment. Our primary accomplishment was to identify the coalition's security parameters and the influence exerted upon these parameters by the institutional security policy. Primary security parameters are

- (1) Rate of share refresh—determines how often key shares are changed.

- (2) Group-size limit—determines the maximum number of members of a group.

- (3) Individual membership limit—determines the maximum number of groups for each agent.

- (4) Number of authoritative groups—determines the number of groups with command capability.

Sandia's Advanced Information Systems Laboratory has pioneered development of intelligent agent-based coalitions that utilize group cryptography to maintain high-integrity operations under attacks from both outsiders and malicious insiders. ...

In this research project, we will study system models and security policies surrounding autonomous-multiagent coalitions that use proactive-threshold protocols to certify collaborative computations and consensual results.

(5) Command allocations—maps sets of critical commands to groups.

(6) Reputation thresholds—minimum reputation values for “good standing.”

We identified the following policy considerations that influence the security parameters:

- (1) Primary security requirements for each data resource: integrity, confidentiality, availability.
- (2) Priority of requirements for each resource.
- (3) Organizational jurisdiction over each data resource.
- (4) Threat models for each data resource
- (5) Assessment of past insider malfeasance.
- (6) Attrition rate of personnel with security-critical roles.
- (7) Assessment of past security breaches.
- (8) Network topology, security, and monitoring resources.

- (9) Business processes, organizational data flows.

We developed a collective-security model of an autonomous-agent collective based on the concept of a social norm. The norm game requires a threshold-based reputation mechanism to identify chronic malfeasors and a retribution mechanism for punishing the offenders. Moreover, the literature suggests that a second-order retribution mechanism in which agents who fail to punish offenders are also punished is necessary for stability. We developed a concept for a secure-agent ecology that involves self-replicating agents with a limited lifetime. The agent collective can adopt either a k -selected regime or an r -selected regime in response to the security conditions in the environment.

• *Validation of models/protocols in the agent test-bed.*

We completed coding and functional test of the following protocols:

- (1) Bracha’s Broadcast Algorithm.
- (2) Pederson’s Verifiable Secret Sharing over the Integers (IPVSS).
- (3) Share Update for Shoup’s Threshold Signature Algorithm.
- (4) Shoup’s Asynchronous Binary Byzantine Agreement (ABBA).
- (5) Agreement on a Core Set (ACS).

We developed a collective-security model of an autonomous-agent collective based on the concept of a social norm. ...

We developed a concept for a secure-agent ecology that involves self-replicating agents with a limited lifetime.

- *OPNET simulations.* We implemented the basic-cohesion protocol for an agent collective. We intend to model more complex coordination protocols.

We implemented the basic-cohesion protocol for an agent collective.

32816

Vulnerability Assessment of National Power Grid

D. M. Kunsman, R. E. Carlson, A. E. Lutz, R. V. Matalucci, D. G. Robinson

This research effort concentrates on the identification of critical nodes within the national bulk power system and the use of distributed generation as a means of diminishing the impact of the disruption of those nodes. There are over 11,000 generation facilities, in excess of 200,000 miles of very high voltage transmission line, and thousands of substations that constitute one of the largest machines ever constructed in the United States: the national power grid. Between 1980 and 1989 there were 5000 worldwide attacks against power transmission lines and towers; 386 of these were documented attacks against U.S. energy assets. The cost of a power disruption has been estimated to be approximately \$1–\$5 per kWh, including both direct and indirect costs. An outage in August 1996 cost the state of California in the neighborhood of one-billion to three-billion dollars. In addition to the obvious costs to consumers and the direct impact on the U.S. economy, there are obvious national security implications as well. As noted in a special U.S. Senate report, the “destruction of bulk energy systems would not only affect the ability of the U.S. to mobilize its forces, but would obviously impact the ability to support the war effort of a NATO member.” Through the identification of critical elements and the quantification of the consequences of their failure, site-specific vulnerability analyses can be focused at those locations where additional security measures could be effectively implemented. In particular, with appropriate sizing and placement within the grid, distributed generation in the form of regional power parks may reduce or even prevent the impact of widespread network power outages. Even without additional security measures, increased awareness of sensitive nodes can provide a basis for more effective national, state, and local emergency planning.

Sandia has previous experience in investigating bulk power-grid reliability and had noted deficiencies in the models the utilities used to analyze the reliability of the grid. The models available to analyze the system, as a system, in the new deregulated environment, are fundamentally not up to the

This research effort concentrates on the identification of critical nodes within the national bulk power system and the use of distributed generation as a means of diminishing the impact of the disruption of those nodes. ... Sandia has previous experience in investigating bulk power-grid reliability and had noted deficiencies in the models the utilities used to analyze the reliability of the grid.

challenge before them. The algorithms are only approximate and have missed critical nodes in the past. The models only perform one-at-a-time contingency analysis, which is a bottom-up examination of the effects of faults on the system and not a comprehensive systems approach to the problem. The models also do not include supervisory control and data acquisition (SCADA) elements, and, last, distributed energy resources are not included; such resources could be used for mitigation of reliability problems.

(1) *Modeling the power grid.* In collaboration with New Mexico State University, we reviewed the traditional contingency-analysis approaches. We have begun constructing the framework for the power-grid vulnerability assessment by examining how a sequence of events should be defined. In addition, we investigated efficient ways to approximate the severity of an event. Last, we started developing a unique contingency/sensitivity-analysis algorithm.

(2) *Incorporating the inclusion of the SCADA elements into the power-grid model.* We investigated alternative approaches to the modeling and pursued this through several different avenues. We studied whether the Sandia massively parallel (MP) computer—Computational Plant (CPlant), with its distributed architecture—is a viable platform for integrating the SCADA model with the above power flow and sensitivity/uncertainty portions of the modeling effort.

(3) *Examining the mitigation potential of power-park generation.* For the distributed-energy resources, or “power parks,” we have been heavily engaged in modeling efforts. We developed a model of hydrogen production by steam reforming of hydrocarbon fuels. Furthermore, we constructed the initial software interface for Simulink to make calls to the chemical kinetics (CHEMKIN) package, which provides thermodynamic properties and equilibrium analysis. In addition, we attended the DOE Hybrid Power Conference at the University of California—Irvine National Fuel Cell Research Center.

For the distributed-energy resources, or “power parks,” we have been heavily engaged in modeling efforts. We developed a model of hydrogen production by steam reforming of hydrocarbon fuels. Furthermore, we constructed the initial software interface for Simulink to make calls to the chemical kinetics (CHEMKIN) package, which provides thermodynamic properties and equilibrium analysis.

Engineering Sciences

The Engineering Sciences investment area focuses on science-based life-cycle engineering. The goal is to develop a pervasive, validated, science-based simulation environment requiring the integration of simulation with experimental and test procedures. These simulations will be unprecedented in physical and geometric fidelity, spatial and temporal resolution, and subsequent computational size, and in significantly increasing the role of validated engineering modeling and simulation in the full life cycle of weapon systems and components, while achieving mission goals with reduced resources, reduced costs, and increased system and component reliability.

Electrokinetics is a microfluidic phenomenon that has numerous potential national security and commercial applications. The “Applied Microfluidic Physics” project addresses the challenges of microscale electrokinetics, including the lack of design tools and methodologies, incomplete understanding of the physical phenomenon, the difficulty of microscale diagnostics, limited availability and characterization of supporting hardware, and an incomplete suite of miniaturizable instruments. Applications of this work include chemical, biological, and environmental sensors, geno-

mics and proteomics, drug discoveries, and clinical medicine. Accomplishments include a published and validated theory of ideal electrokinetics; two patents have been filed related to these advances and new software has been developed. The impact of this LDRD project is fundamental, technological, and practical.

10336

Structural Simulations Using Multiresolution Material Models

S. W. Key, D. C. Hammerand, R. S. Chambers

This project is developing computational methods for hierarchical modeling of homogeneous and heterogeneous materials. Starting with a simplified model, Sandia is introducing increasingly more comprehensive material representations into the simulation to the extent required to meet a predefined error tolerance.

The success of this concept depends on the successful completion of four tasks: (1) the identification of a hierarchical sequence of material models, (2) the development of an error analysis that indicates the required level of material representation as the simulation unfolds, (3) the design of a solution strategy and software architecture that will support the simultaneous refinements in mesh and material representation, and (4) the development of meshing technologies that automatically convert detailed experimental measurements of material inhomogeneities into practical analysis meshes suitable for adaptive refinement.

- We performed complementary studies of unfilled viscoelastic potting epoxy and heterogeneous elastic materials, and constructed a family of approximations to the nonlinear viscoelastic constitutive law for potting epoxy.

- We formulated error measures needed to describe the differences in the nonlinear continuum response of various members of a general material model family.

- We developed 14 alternatives for the criteria and the process of switching for the adaptive modeling of potting epoxy and implemented them in the Sandia finite-element code JAS3D.

- We performed examples demonstrating material model refinement and coarsening for the various adaptive schemes for potting epoxies. For heterogeneous materials, we identified a nested family of constitutive models that span from a simple homogeneous characterization to a formulation representative of the microscale processes of interest.

- We developed the ability to incorporate item-specific material inhomogeneity data as generated from computerized x-ray tomography (CT).

This project is developing computational methods for hierarchical modeling of homogeneous and heterogeneous materials. Starting with a simplified model, Sandia is introducing increasingly more comprehensive material representations into the simulation to the extent required to meet a predefined error tolerance. ...

- We created and implemented algorithms for generating quadrilateral two-dimensional (2-D) and hexagonal 3-D meshes from CT scans of particle-filled composites.

- We formulated and implemented error measures for controlling the errors in user-defined quantities of interest in the linear analysis of heterogeneous elastic materials.

- We developed and implemented the criteria and switching process necessary to adaptively select the level of fine-scale features that must be included for the accurate determination of local quantities of interest in linear elastic heterogeneous materials.

- We generated numerical solutions using adaptive material model refinement to control the error in local quantities of interest for heterogeneous structures.

- We implemented and studied fictitious domain algorithms for particle-filled composites that allow reduction to analysis of individual component pieces (particles and matrix).

- We developed stochastic and worst-scenario approaches to characterize the uncertainty in results arising from uncertainty in the input data for a boundary-value problem. The uncertainties considered are related to either uncertainty in the domain arising from segmentation of CT images or the uncertainty corresponding to material or loading data, which is only known in a statistical sense.

- We conducted preliminary physical experiments to provide data to benchmark the computational modeling of particle-filled composite materials.

- We wrote numerous reports and journal articles related to the project.

We implemented and studied fictitious domain algorithms for particle-filled composites that allow reduction to analysis of individual component pieces (particles and matrix).

Refereed

Babuska, I., and J. Chleboun. 2001. "Effects of Uncertainties in the Domain on the Solution of Neumann Boundary Value Problems." *Mathematics of Computation*, accepted.

Bajaj, C., J. Warren, and G. Xu. 2001. "A Smooth Subdivision Scheme for Hexahedral Meshes." *J. Visual Computer*, Special Issue on Recursive Subdivision, accepted.

Mae, H. 2000. "Microstructural Characterization of Glass-Epoxy Specimens." M.S. Thesis, University of Texas at Austin, Austin, TX.

Oden, J. T., and K. Vemaganti. 1999. "Adaptive Hierarchical Modeling of Heterogeneous Structures." *Physica D* **133**: 404–415.

Oden, J. T., and K. Vemaganti. 2000. "Adaptive Modeling of Composite Structures: Modeling Error Estimation." *International J. Computational Civil and Structural Engineering* **1**: 1–16.

Oden, J. T., and K. Vemaganti. 2000. "Estimation of Local Modeling Error and Goal-Oriented Adaptive Modeling of Heterogeneous Materials, Part I: Error Estimates and Adaptive Algorithms." *J. Computational Physics* **164** (October): 22–47.

Oden, J. T., S. Prudhomme, D. C. Hammerand, and M. S. Kuczma. 2001. "Modeling Error and Adaptivity in Nonlinear Continuum Mechanics." *Computer Methods in Applied Mechanics and Engineering*, accepted.

Podnos, E. G. 1999. "Applications of Fictitious Domain Method to the Analysis of Composite Materials." Ph.D. dissertation, University of Texas at Austin, Austin, TX.

Vemaganti, K., and J. T. Oden. 2001. "Estimation of Local Modeling Error and Goal-Oriented Adaptive Modeling of Heterogeneous Materials, Part II: A Computational Environment for Adaptive Modeling of Heterogeneous Elastic Solids." *Computer Methods in Applied Mechanics and Engineering*, accepted.

Other Communications

Babuska, I., and J. Chleboun. 2001. "Effects of Uncertainties in the Domain on the Solution of Dirichlet Boundary Value Problems." TICAM preprint, Texas Institute for Computational and Applied Mathematics, Austin, TX.

Bajaj, C., and G. Xu. 2001. "Anisotropic Diffusion of Noisy Surfaces and Noisy Functions on Surface." TICAM Report 01-07, Texas Institute for Computational and Applied Mathematics, Austin, TX (February).

Bajaj, C., Q. Wu, and G. Xu. 2001. "Anisotropic Diffusion of Noisy Volumetric Images." TICAM Report, Texas Institute for Computational and Applied Mathematics, Austin, TX (July).

Hammerand, D. C., J. T. Oden, S. Prudhomme, and M. S. Kuczma. 2001. "Modeling Error and Adaptivity in Nonlinear Continuum Mechanics." Sandia Technical Report SAND2001-0132, Sandia National Laboratories, Albuquerque, NM (February).

Hammerand, D. C., S. W. Key, J. T. Oden, I. Babuska, G. Rodin, C. Bajaj, S. Prudhomme, and K. Vemaganti. 2001. "Structural Simulations Using Multiresolution Material Models." Sandia Technical Report, in preparation.

Vemaganti, K. 2000. "Modeling Error Estimation and Goal-Oriented Adaptive Modeling of Perforated Materials." TICAM Report TR 00-25, Texas Institute for Computational and Applied Mathematics, Austin, TX.

10338

Mechanisms of Adiabatic Shear Failure

D. B. Dawson, R. A. Regueiro, B. R. Antoun, Y. Ohashi

High-rate loading of structural alloys can result in adiabatic shear, an extreme and usually catastrophic low-energy form of localized deformation. Adiabatic shear failures are observed in impact, ballistic penetration, and high-rate deformation processing. Some aspects of the phenomenon are known, but accurate phenomenological and computational models do not exist. This leads to the current uncertain situation where, in a modeling- and simulation-based environment, susceptibility to catastrophic adiabatic shear failure may only be detected in full-system testing or service. Current computational approaches to improved localization modeling do not address the complexity of adiabatic shear, with its inherently tight coupling of temperature and mechanical fields.

Sandia is conducting a systematic, coupled experimental and analytical study to establish deformation and failure mechanism maps, to develop innovative applications-oriented scaling laws, and to design criteria relating critical physical aspects to adiabatic shear failure susceptibility.

Using the torsional Kolsky technique, we completed an experimental screening matrix of adiabatic shear susceptibility for a wide range of steels, aluminum (Al) alloys, and titanium (Ti) alloys that are used in Sandia defense programs. We used the results of the screening tests to select two of these alloys, 6061 Al and Ti-₆Al-₄V Ti, for a more detailed examination of adiabatic shear band initiation characteristics. These alloys represent the two primary types of adiabatic shear band initiation characteristics, the deformation type (6061) and the transformation type (Ti-₆Al-₄V). We tested specimens over a wide range of strain rates and imposed shear strains to determine shear band initiation criteria, and we studied characteristics of incipient and fully formed shear bands using metallographic sectioning of specimens.

The results of the screening tests disclosed that while the torsional Kolsky technique has advantages for the study of adiabatic shear phenomena, it also has shortcomings. Principal among these are limitations on achievable strain rates and

Sandia is conducting a systematic, coupled experimental and analytical study to establish deformation and failure mechanism maps, to develop innovative applications-oriented scaling laws, and to design criteria relating critical physical aspects to adiabatic shear failure susceptibility. ... We tested specimens over a wide range of strain rates and imposed shear strains to determine shear band initiation criteria, and we studied characteristics of incipient and fully formed shear bands using metallographic sectioning of specimens.

sensitivity to geometrical defects produced during specimen preparation. Therefore, we developed a novel new specimen geometry that alleviates most of these concerns. We evaluated the resultant dynamically loaded compression-shear specimen both experimentally and analytically and found it to provide a capability for large, high-rate shear strains confined to a well-characterized gauge section. Experiments with the compression-shear geometry were conducted both dynamically and quasi-statically, with a range of gauge widths, to achieve a very wide range of shear strain rates. We examined both high-rate shear deformation properties and adiabatic shear characteristics for a range of alloys selected from the initial torsional Kolsky screening tests. The compression-shear geometry proved to be particularly well suited to the study of shear band initiation, through the use of stop-collars to limit displacement. Evaluation of experimental results shows that conservative engineering design criteria for avoidance of adiabatic shear should currently be based on shear instability rather than on shear localization.

To facilitate modeling of adiabatic shear band initiation and growth, we determined material constants for selected alloys from the experimental project and implemented a modified adiabatic temperature evolution equation that more accurately represents conversion of plastic work to heat. Using this model, we completed simulations of torsional Kolsky and compression-shear specimens. We showed that we can achieve accurate simulation of uniform shear deformation, but no localization occurs without a geometric inhomogeneity. When a small, arbitrary discontinuity is incorporated, computational simulations show that rapid localization to shear discontinuity occurs. We examined the effects of uncoupled versus coupled thermomechanical analysis for the torsional Kolsky geometry. Differences between the analyses were small but potentially significant, suggesting that an uncoupled analysis may not be sufficiently accurate.

... we developed a novel new specimen geometry that alleviates most of these concerns. We evaluated the resultant dynamically loaded compression-shear specimen both experimentally and analytically and found it to provide a capability for large, high-rate shear strains confined to a well-characterized gauge section.

10340

Crack Nucleation and Growth: Combining Validated Atomistic and Continuum Modeling

J. E. Houston, A. K. Schmid, J. C. Hamilton, R. Q. Hwang, P. A. Klein, J. A. Zimmerman, S. M. Foiles

Fracture and decohesion are critical material failure modes that impact areas ranging from advanced component development to the aging of stockpile components. Consequently, computational models of these processes are essential to Sandia's programmatic interests. The wide range of length scales involved has dramatically hampered the computer modeling of fracture. For example, ductile fracture involves the interactions between dislocations (i.e., defects in the atomic crystal lattice) and crack tips, and produces long-range elastic forces at microscopic and macroscopic scales. Similarly, brittle fracture entails atomic and molecular bond-breaking caused by the concentration of stress fields at the crack tip, where the origin of these stresses is at remote boundaries. Thus, it is imperative to couple the atomistic understanding provided by solid-state physics with the stress analysis provided by continuum mechanics. Sandia has a coordinated project in which experimental investigation of prototypical fracture events will guide modeling using atomistic and continuum techniques. Project goals are to achieve a common working vocabulary that merges the ideas of atomistic and continuum analyses to determine the areas in which continuum models need to be enriched to reflect atomic-scale processes and to validate these methods by comparison with nanoscale experiments.

We performed further validation of our atomistic models by comparing new nanoindentation simulations with recent experiments showing the formation of subangstrom-height hillocks on scanning-tunneling microscope (STM)-indented gold (Au) (001) surfaces. These hillocks are positioned at significant distances away from the indentation region. In theory, these hillocks are produced by the dissociation of V-shaped dislocation loops that form and then propagate away from the indentation region. Atomistic simulation confirms this subsurface structure and connects the hillocks to the underlying stacking faults bounded by the dissociated partial dislocations. The heights of the hillocks

Sandia has a coordinated project in which experimental investigation of prototypical fracture events will guide modeling using atomistic and continuum techniques. Project goals are to achieve a common working vocabulary that merges the ideas of atomistic and continuum analyses to determine the areas in which continuum models need to be enriched to reflect atomic-scale processes and to validate these methods by comparison with nanoscale experiments.

observed in simulation, approximately 0.6 Å, are in agreement with experimental measurements.

We developed an atomistic simulation code capable of modeling ionic crystals. This code uses a charge-neutralization, truncated-radius formalism to evaluate the Coulomb portion of the interatomic potential. Simulations of the nanoindentation of magnesium oxide (MgO) exhibit Hertzian behavior and a critical load at which material failure occurs. Visualization of these simulations does not display dislocation structures, but further analysis is needed to identify cracks. For comparison, we performed nanoindentation experiments using a diamond-tip indenter; however, irregular behavior in the loading curve, failure to detect any defect formation, and scanning-electron microscope (SEM) examination of the indenter suggest the tip we used possessed a complex shape resulting in a larger-than-expected tip radius.

We further analyzed and compared the static and dynamic responses of atomistic and continuum models of steady-state, two-dimensional crack propagation. The parameters for the two material models are selected to produce identical elastic modulus, fracture energy, and cohesive strength. Under quasi-static loading, the two models possess nearly identical traction distributions on the crack line and fail due to brittle cleavage at the same load. However, whereas dynamic loading of the continuum model results in brittle cleavage, the response of the atomistic model is strain-rate dependent, and displays multiple mechanisms of dissipation such as material vibration and, at high strain rates, dislocation emission. A detailed analysis of the two models exhibiting brittle cleavage shows the continuum crack accelerating to the continuum-limiting speed of the Rayleigh wave speed. In contrast, the atomistic crack reaches a speed of one-fifth this value and then propagates at constant speed. Examination of the rate of kinetic-energy generation in the atomistic model demonstrates a nearly linear increase with increasing applied strain, while this rate vanishes for the continuum model as the limiting speed is approached. For the atomistic simulation, Fourier transform of the wavelet transform of displacements perpendicular to the crack line for atoms in front of and behind the crack tip shows that the moving crack concentrates kinetic motion to a specific wavelength approximately five times the lattice parameter. Reduction of the interaction range of the interatomic potential produces only slight alterations of both the terminal crack speed and the concentration wavelength. We conclude that the

We developed an atomistic simulation code capable of modeling ionic crystals. This code uses a charge-neutralization, truncated-radius formalism to evaluate the Coulomb portion of the interatomic potential.

dispersion effects noticed for the atomistic results could only be introduced into a continuum model by using a nonlocal description of material behavior.

Refereed

Klein, P. A., J. A. Zimmerman, and E. P. Chen. 2001. "Development of Cohesive Models from the Study of Atomic-Scale Fracture Processes." *Proc. 10th International Conference on Fracture* (San Diego, CA, 2 December).

Rodríguez de la Fuente, O., J. A. Zimmerman, M. A. González, J. de la Figuera, J. C. Hamilton, W. W. Pai, and J. M. Rojo. 2001. "Dislocation Emission Around Nanoindentations on a (001) fcc Metal Surface Studied by STM and Atomistic Simulations." *Physical Review Lett.*, in review.

Zimmerman, J. A., C. L. Kelchner, P. A. Klein, J. C. Hamilton, and S. M. Foiles. 2001. "Surface-Step Effects on Nanoindentation." *Physical Review Lett.* **87** (15 October): 5507.

Zimmerman, J. A., P. A. Klein, and S. M. Foiles. 2000. "Effect of Surface Steps on Dislocation Structure During Nanoindentation." *Proc. Materials Research Society Symposium* **649** (Fall) (Boston, MA, 1 December).

Other Communications

Foiles, S. M., J. A. Zimmerman, and P. A. Klein. 2001. "Atomic-Level Simulation of Dislocation Nucleation During Nanoindentation." Paper presented to the Annual Meeting of the Division of Computational Physics, APS, Cambridge, MA, 25 June.

Foiles, S. M., J. A. Zimmerman, and P. A. Klein. 2001. "Atomic-Level Simulation of Dislocation Nucleation During Nanoindentation: Role of Surface Steps." Paper presented to the USACM 6th U.S. National Congress on Computational Mechanics, Dearborn, MI, 2 August.

Zimmerman, J. A., O. Rodríguez de la Fuente, M. A. González, J. de la Figuera, J. C. Hamilton, and J. M. Rojo. 2001. "Atomistic Simulation of Nanoindentation." Paper presented to the USACM 6th U.S. National Congress on Computational Mechanics, Dearborn, MI, 2 August.

10341

Applied Microfluidic Physics*E. B. Cummings, S. K. Griffiths, R. H. Nilson*

A one-billion-dollar market for electrokinesis-based microfluidic systems is emerging as its utility in clinical diagnostics, drug discovery, and chemical analysis is recognized. Electrokinetic-based technologies promise to fill urgent national security needs in counterterrorism and to counter chem/bio warfare. Sandia conceived this project to target critical technical challenges that impede the progress of this microfluidic technology. This project focuses a coupled theoretical, numerical, and experimental effort on targeted problems: (1) the incomplete physical understanding of electrokinesis, (2) the absence of critical device primitives such as low-dispersion turns and injectors, and (3) the poor understanding of transport in, and the capabilities of, engineered post arrays.

We made significant progress in tackling each one of the impediments to microfluidic technology. In the course of addressing these problems, we also developed novel design synthesis methodologies, implemented novel and powerful microscale flow diagnostics, and invented a new class of microfluidic devices that are based on dielectrophoresis, a second-order electrostatic-transport phenomenon.

We achieved our progress by targeting critical issues with closely coupled theoretical and computational analysis and detailed, high-accuracy experiments. The problems that we specifically targeted included (1) establishing and experimentally validating the conditions required for “ideal electrokinesis,” an important limiting case of general electrokinesis in which the fluid flows exactly like the ionic current within the fluid, (2) understanding and minimizing ideal electrokinetic flow and dispersion in turns (primitive devices needed to miniaturize microfluidic device footprints and provide layout flexibility to designers), (3) conceiving of schemes for injecting carefully metered slugs of analyte into a secondary chamber or column with minimal hydrodynamic dispersion (a primitive function required in nearly all chip-based separations), and (4) understanding flow and dispersion in uniform arrays of posts (widely proposed engineered replacements for the random-packed beds in chromatography and fractionation).

A one-billion-dollar market for electrokinesis-based microfluidic systems is emerging as its utility in clinical diagnostics, drug discovery, and chemical analysis is recognized.

Electrokinetic-based technologies promise to fill urgent national security needs in counterterrorism and to counter chem/bio warfare. Sandia conceived this project to target critical technical challenges that impede the progress of this microfluidic technology. ...

We made significant progress in tackling each one of the impediments to microfluidic technology.

In the course of successfully addressing these targeted problems, we also (1) developed an optical flow diagnostic methodology that provides diffraction-limited velocity fields with demonstrated accuracies better than 1 percent, (2) produced and released user software for analyzing the ideal electrokinetic flow in quasi-planar geometries of arbitrary connectedness and geometry, and (3) invented a novel class of devices that employ dielectrophoresis to fractionate, concentrate, and manipulate particles over a size range that includes viral, bacterial, and protozoan pathogens and cells. This invention promises to enable inexpensive, no-moving-parts devices that perform sample-preparation steps analogous to those performed in size-exclusion columns, ultracentrifuges, and sieves.

Over the past year, we enhanced the function of our user software to allow studies of dielectrophoretic transport and diffusion. We released this software within Sandia where it has been used by several other groups to understand flow in manifolds, transport in injection devices having multiple channel depths, and dispersion in rough-walled columns. The development and support of this software will continue past the end of this project as it is extended to be a general-purpose dielectrophoresis tool for Sandia designers and researchers. We also extended our optical flow diagnostic tools to produce diffraction-limited velocity histogram fields. We used this extended methodology to demonstrate the excellent agreement (better than 1 percent) between the ideal electrokinetic velocity field generated by the general-purpose flow solver and the experimentally observed flowfields in uniform arrays of posts. This demonstration is a latest and most convincing validation of our ideal electrokinetic theory. We filed a patent on our dielectrophoretic method and apparatus. We filed three related disclosures and are in the process of more filings based on the developments from this project.

Finally, we performed numerical studies of sample dispersion in uniform arrays of posts as well as theoretical analysis relating the long-time dispersive behavior of an array to the velocity fields within a single-unit cell and fluid properties.

... we also ... invented a novel class of devices that employ dielectrophoresis to fractionate, concentrate, and manipulate particles over a size range that includes viral, bacterial, and protozoan pathogens and cells. This invention promises to enable inexpensive, no-moving-parts devices that perform sample-preparation steps analogous to those performed in size-exclusion columns, ultracentrifuges, and sieves. ...

Refereed

Griffiths, S. K., and R. H. Nilson. 2000. "Band Spreading in Two-Dimension Microchannel Turns for Electrokinetic Species Transport." *Analytical Chemistry* **72** (November): 5473–5482.

Griffiths, S. K., and R. H. Nilson. 2001. "Low-Dispersion Turns and Junctions for Microchannel Systems." *Analytical Chemistry* **73**: 272–278.

Other Communications

Cummings, E. B. 2001. "Ideal Electrokinesis and Dielectrophoresis in Arrays of Insulating Posts." *Proc. AIAA* (Reno, NV, February).

Griffiths, S. K., and R. H. Nilson. 2000. "Electro-Osmotic Fluid Motion and Late-Time Solute Transport at Nonnegligible Zeta Potentials." *Analytical Chemistry* **72** (October): 4767–4777.

Griffiths, S. K., and R. H. Nilson. 2000. "Method and Apparatus for Producing a Thin Sample Band in a Microchannel Device." Patent filing SD-8263, Livermore, CA, 4 November.

Griffiths, S. K., and R. H. Nilson. 2001. "Pleated and Coiled Columns for Microchannel Systems." Technical Advance SD-8325, Livermore, CA, 10 January.

Nilson, R. H., and S. K. Griffiths. 2001. "Inverted Method for Simulation of Electrokinetic Transport in Microchannel Devices." *Proc. 4th International Conference on Modeling and Simulation of Microsystems, MSM2001* (Hilton Head, SC, 19–21 March).

10343

Innovative Measurement Diagnostics for Fluid/Solid and Fluid/Fluid Interactions in Rotating Flowfields

B. A. Amatucci, R. J. Erven, S. J. Beresh, J. F. Henfling, C. J. Bourdon

This project was designed to develop new measurement capabilities to examine the interaction of a propulsive spin jet in a transonic freestream for a model in a small-scale wind tunnel. The technical challenge was to examine data packages and pressure sensors and to incorporate those technologies into a small-scale model for Sandia's Trisonic Wind Tunnel (TWT). The challenge of incorporating specialized microsensors and custom-made data packages is offset by the reduced costs of conducting flow-physics experiments in a small research-based facility.

The project motivation was the type of jet/fin interactions commonly occurring during deployment of some weapon systems. In particular, the two phenomena of interest were the interaction of the propulsive spin jet with the freestream in the vicinity of the nozzle, and the impact of the spin rocket plume and its vortices on the downstream fins. The main thrust of the technical developments was to incorporate small-size, Lagrangian-type sensors for pressure and roll-rate on a scale model, and to include data acquisition, transmission, and power circuitry onboard.

We achieved an informative investigation of the applicability of novel miniaturized diagnostics for wind tunnels. The goal was to determine methods of measuring flow properties in small-scale wind tunnels at low cost. The project required integration of pressure instrumentation, onboard jets, and data telemetry. We accomplished most of our goals, including use of micron-scale pressure sensors, an onboard telemetry system for data acquisition and transfer, onboard jet exhaust, and roll-rate measurements. We designed, fabricated, and tested a new wind tunnel model and incorporated the ability to house multiple microelectromechanical systems (MEMS)-based pressure sensors, interchangeable vehicle fins with pressure instrumentation, an onboard multiple-channel telemetry data package, and a high-pressure jet exhaust simulating a spin rocket motor plume. We conducted experiments for a variety

View of the wind-tunnel model illustrating the complexity of wiring of the pressure instrumentation and the data telemetry system.

This project was designed to develop new measurement capabilities to examine the interaction of a propulsive spin jet in a transonic freestream for a model in a small-scale wind tunnel.

of MEMS-based pressure sensors to determine performance and sensitivity in order to select pressure transducers for use.

We made the data-acquisition and analysis path most successful by using multiple 16-channel data processors with telemetry capability to a receiver outside the wind tunnel. The development of the various instrumentation paths led, with intensive efforts, to the fabrication of a new wind tunnel model and installation for baseline nonrotating experiments, to validate the durability of the technologies and techniques. We successfully investigated a wide variety of instrumentation and experimental techniques and ended with basic experiments for a nonrotating model with jet on. We completed the project through shakedown of diagnostics in a new wind tunnel model for a nonrotating case.

- *Telemetry system development and implementation.*

Our initial technical approach for data acquisition was to pursue the development at Sandia of a data-acquisition and -storage system. The size of models in Sandia's TWT facility, along with past successes of data package specialists, indicated that acquisition/storage during an experiment is a successful technique. During our previous work, it became apparent that our scale was too small and that larger resources were required for success with data storage. Thus, the path was changed toward data telemetry using a custom, miniaturized acquisition/telemetry/power package designed and fabricated by others. Subsequently, we conducted successful experiments with a one-channel system using pressure-sensor input and successful transmission through the TWT walls. Based on the one-channel system results, we acquired 16-channel systems for use with the MEMS-based pressure microsensors. The new units utilized a rechargeable battery pack and integrated processor/telemetry circuitry.

- *Model design and fabrication.* Although initial experiments for the one-channel telemetry system were completed with a modified model on an existing spin mechanism, it became evident that a new model was needed. In the design of the new model, accommodations were made for Lucas NovaSensor pressure devices, SRI 16-channel thermocouple monitor (TM) systems, and nozzles to produce an onboard propulsive jet. Specifications for the model were given to MicroCraft, which then completed the design and fabrication of the model. The model was structured in a "clamshell" design to facilitate placement of the pressure

... we conducted successful experiments with a one-channel system using pressure-sensor input and successful transmission through the TWT walls. Based on the one-channel system results, we acquired 16-channel systems for use with the MEMS-based pressure microsensors. The new units utilized a rechargeable battery pack and integrated processor/telemetry circuitry.

sensors, TM package, and wiring. One fin of the wind tunnel model was instrumented by Kulite with flush-mounted pressure sensors.

- *Pressure instrumentation on the model.* We designed the pressure instrumentation for two distinct applications. First, to measure pressures along the body and between the fins, we integrated Lucas NovaSensor MEMS-based sensors in the model longitudinally. We placed Kulite-manufactured sensors in one fin to measure the differential pressure while accommodating the very thin structure of the fin. We epoxied the MEMS-based sensors into a recessed cavity on the model and wired them to the TM package. Both of these types of sensors measured the pressure field during the transonic experiments.

- *Onboard jet implementation.* The propulsive spin jets were emulated by two nozzles on opposite sides of the model and supplied with cold gas by plumbing through the model and sting. We supplied nitrogen to a central settling chamber and then distributed it to the opposed nozzles at various pressure ratios. Multiple nozzles were fabricated and interchangeable in the model.

- *Wind tunnel experiments.* During this project, we invested extensive effort in (1) development of the technology paths for each element of the instrumentation package, and (2) assembly, wiring, and checkout of the components on board the model. To validate the 16-channel TM system and sensors, we conducted limited experiments for a nonrotating case. We acquired and transmitted successful pressure data for transonic flight conditions.

The primary outcomes of this research are extensive understanding of existing and future instrumentation for wind tunnel experiments and the viability of making these vital fluid dynamic measurements at reasonable cost on a small scale.

The primary outcomes of this research are extensive understanding of existing and future instrumentation for wind tunnel experiments and the viability of making these vital fluid dynamic measurements at reasonable cost on a small scale.

Refereed

Amatucci, V. A., S. J. Beresh, J. F. Henfling, and R. J. Erven. 2001. "Application of Microsensors and Telemetry Systems for Small-Scale Wind Tunnel Experiments." *Proc. 40th AIAA Aerospace Sciences Meeting* (Reno, NV, 14–17 January 2002), accepted.

Other Communications

Amatucci, V. A., S. J. Beresh, J. F. Henfling, and W. H. Rutledge. 2001. "Jet/Fin Interactions on a Rotating Body in a Transonic Wind Tunnel Facility." *Proc. 95th Supersonic Tunnel Association International Meeting (STAI)* **95** (Hampton, VA, 29 April–2 May): 1–11.

10765

Energetic-Material Burn and Detonation at the Mesoscale

A. M. Renlund, M. R. Baer, S. H. Kravitz, K. L. Erickson, P. K. Walker, A. S. Tappan

The success or failure of an ignited energetic material (EM) to propagate a burn or detonation is determined by material properties and reactions at the mesoscale. Burn models cannot adequately account for surface-area burning effects without understanding burning at high pressure in small fissures. Similarly, rarefactions from sides and from grain boundaries are efficient at quenching shocks, leading to failure of a detonation wave at some critical diameter. Whether or not a detonation can be sustained at small (submillimeter) diameters may depend on engineering the EM without traditional grains while incorporating microporosity into the material.

A novel and intriguing prospect is rapid energy release from binary EMs, traditional pyrotechnic and propellant materials, which may have three to five times the energy density of conventional high explosives. If these materials can be engineered so that reactions can occur without strong influence from diffusion times to mix fuel and oxidizer, we may develop new EMs capable of higher output.

In this project, Sandia applies innovative experiments to observe burning and detonation at the mesoscale. We rely heavily on advances made in semiconductor manufacturing to create structures in which burning and detonations can occur at these very small scales. For example, we will create burn channels of varying cross-sections, load the channels with EM, and monitor the burning rate using integrated gauges and high-resolution optical diagnostics. For detonations, we will examine the propagation of reactive waves in materials engineered with porosity but without the traditional grain structure used in macroscopic EM applications, and study the novel nanoscale mixed materials. All material deposition and patterning techniques will be compatible with modern microelectronic fabrication technology.

State-of-the-art simulations of deflagration and detonation are now incorporating effects of microstructural elements. These experiments will provide insight into the controlling mechanisms associated with the reliability and

In this project, Sandia applies innovative experiments to observe burning and detonation at the mesoscale. We rely heavily on advances made in semiconductor manufacturing to create structures in which burning and detonations can occur at these very small scales.

safety of energetic components and will address issues for using EMs to provide useful work in new classes of microcomponents.

To determine which EMs would be likely candidate materials to function at this small scale, we developed an experiment that could rapidly test a number of materials. Small capillary tubes were flame-drawn closed at one end in a manner that created a tapered internal diameter. Depending on the individual experiment, the capillary varied from 1.5 to 5 cm in length and from 300 μm to 1100 μm in initial tube internal diameter. We filled each capillary with the candidate material and ignited it from the open end with a hot-wire igniter. In some cases, we used an igniter material such as 50:50 black powder/magnesium powder to facilitate ignition. We monitored the event with video and performed post-mortem analysis to determine at what internal diameter the burn failed. A number of materials were tested, but the best performers of this test were BTATz (3,6-bis-(1H-1,2,3,4-tetrazol-5-yl-amino)-s-tetrazine), which failed at a diameter of 250 μm , DAATO3.5 (diamino-azo-tetrazine mixed N-oxides), which failed at a diameter of 380 μm , and 18.5:81.5 Al/CuO thermite, which failed at an internal diameter of 415 μm . These experiments resulted in a list of materials that deserve further study at this small scale.

In addition to developing novel materials for use at the mesoscale, the behavior of EMs currently in use continues to be an important goal of this project. We made great progress in the deposition and patterning of PETN (pentaerythritol tetranitrate). We vapor-deposited PETN to achieve thick films of good quality up to 10 μm thick. We patterned these films by two techniques: reactive-ion etch (RIE) and silicon-dioxide (SiO_2) mask lift-off. RIE led to significant film degradation and marginal pattern quality. Preliminary results with lift-off are very encouraging; excellent patterning is achieved, but with substantial film disruption.

We constructed a specialized test chamber in which to perform small-scale experiments. The chamber has ports for optical, electronic, and fiber-optic access. The chamber is constructed with optical-quality Lexan, allowing imaging from almost every angle. This new chamber allows for benchtop testing of small test devices, without the past problems associated with testing in a large explosive chamber. These problems include cleanliness, ease of diagnostic

In addition to developing novel materials for use at the mesoscale, the behavior of EMs currently in use continues to be an important goal of this project. We made great progress in the deposition and patterning of PETN (pentaerythritol tetranitrate). We vapor-deposited PETN to achieve thick films of good quality up to 10 μm thick.

implementation, ignition signal transmission, throughput limitations, and general ease of use. With this new chamber, we dedicated a capability to examine the mesoscale behavior of EMs.

We demonstrated integration of EMs into Si test devices. A Si test device consisting of a 300 μm wide by 100 μm deep channel, with a 500 μm diameter ignition site, was covered with a glass coverslip using an ultraviolet-curing epoxy. We left the ignition site uncovered and loaded lead styphnate through this opening. We ignited the lead styphnate with a 532 nm laser and monitored reaction using a high-speed camera. Detonation was evidenced by the extremely fast progression of the reaction wave and damage to the glass coverslip. The Si test device survived the test. Based on this test, further work on the detonation of EMs at scales on the order of 100 μm appears very promising.

We are studying various ignition mechanisms for application in microenergetic devices. We fabricated new semiconductor bridge (SCB) devices using gold overcoats on the aluminum lands to facilitate wire bonding. Bridges were 10 μm , 15 μm , or 20 μm long by approximately 2 μm thick. These devices were tested at low voltage and demonstrated normal SCB function at threshold energies below 30 μJ . Such device performance was shown to ignite a burn in pyrotechnic mixtures. We also tested these SCBs at higher voltage and proved them reliable up to 300 V, which should allow them to serve as initiators for prompt detonation.

... further work on the detonation of EMs at scales on the order of 100 μm appears very promising.

10788

Small-Scale Multiaxial Deformation Experiments on Solder for High-Fidelity Model Development

W. Y. Lu, P. T. Vianco, T. E. Buchheit, T. J. Lim, H. E. Fang, B. L. Boyce

Deformation of engineering materials is complex; the ambient temperature deformation of low-melting-point alloys is complicated by competing, thermally activated mechanisms. The interrelation between temperature, stress state, deformation, microstructural coarsening, and localization is not understood. This Sandia investigation examines the following three areas, with a focus on understanding the underpinning physics:

(1) The failure of solder joints is often preceded by the formation of localized coarsened bands, but there is no fundamental understanding about the energy criteria that govern coarsening or localization. Uniaxial tension and shear experiments have not revealed the underpinning mechanisms; it is not known whether resolved shear, hydrostatic, or deviatoric strains are the critical factors nor how they interrelate with thermal activation.

(2) Deformation mechanism maps are widely applied in continuum-level deformation models. However, these maps do not differentiate between the effects of shear and tension. A thorough understanding of the role of multiaxial stress states on deformation mechanisms will lead to an understanding of critical deformation conditions.

(3) As joint size decreases, mechanical behavior changes from true polycrystalline behavior to a scale where bulk- and size-independent constitutive relations no longer hold. Current models do not incorporate a length scale that would allow exploration of this effect. Experiments at a range of length scales will provide a foundation for the development of deformation models that account for size effects. We will decrease the length to the point where breakdown of continuum is found.

High precision and rigorous control of microstructures is necessary to succeed in these investigations. The resulting small-scale, multiaxial experimental methodology will be an enabling technology for other applications (e.g., the microstructural evolution of multiphase alloys), which until now have not benefited from such local experiments.

The picture shows the side view of a deformed "thin" solder specimen. The undeformed width of the specimen was 0.084 mm, and the edges initially were straight. The curved edges of the deformed specimen show nonuniform deformation, and grain rotation and boundary sliding can be observed from this SEM picture.

High precision and rigorous control of microstructures is necessary to succeed in these investigations. The resulting small-scale, multiaxial experimental methodology will be an enabling technology for other applications (e.g., the microstructural evolution of multiphase alloys), which until now have not benefited from such local experiments.

We successfully manufactured and tested solder samples at sizes smaller than 0.35 mm, our smallest sample in previous work. The smallest samples tested from our current work were 0.084 mm thick. These thinner specimens showed a significantly reduced peak stress as compared with the greater than 0.35 mm samples tested, suggesting considerable geometric influences due to sample size. With regard to microstructure evaluation, scanning electron microscope (SEM) micrographs suggested grain-boundary sliding as the predominant mode of deformation, and there were only two grains through the thickness of these ultrathin samples. The deformation was obviously not uniform, demonstrating that the continuum deformation assumption was no longer valid in these samples.

Through collaboration with researchers at University of Michigan–Dearborn, we also conducted small-scale axial fatigue experiments for the development of solder damage model that accounts for sample size.

We began our investigation of multiaxial deformation of solder with pure torsion experiments. We designed both solid and thin-walled tubular specimens and fabricated them in two different diameters: 5.08 mm and 2.54 mm. We conducted experiments on an MTS Torsion Master mechanical test system. The shear stress-strain curves are consistent despite differences in geometry and size of the specimens tested, indicating no scale effects across these sizes.

Microstructure evaluations of torsional specimens reveal that partially failed specimens have nondistinct grain boundaries and coarsened phase sizes relative to our pretested samples.

In addition to monotonic loading experiments, we also performed axial and torsional cyclic loading tests and studied the fatigue life, damage accumulation, and microstructure features such as phase size and crack. More experiments are required to confirm our results.

We designed and developed a multiaxial tension-torsion creep testing system to test thin-walled tubular solder specimens. Testing is under way to investigate the interrelationships between multiaxial stress states and microstructural deformation mechanisms, especially those associated with development of the deformation mechanism maps.

We successfully manufactured and tested solder samples at sizes smaller than 0.35 mm, our smallest sample in previous work. The smallest samples tested from our current work were 0.084 mm thick. These thinner specimens showed a significantly reduced peak stress as compared with the greater than 0.35 mm samples tested, suggesting considerable geometric influences due to sample size.

Refereed

Lim, T. J., and W. Y. Lu. 2000. "Length Scale Effect on the Mechanical Properties of 63Sn-37Pb Solder Alloy." *Proc. 2000 ASME International Mechanical Engineering Congress and Exposition, Packaging of Electronic and Photonic Devices* **28** (Orlando, FL, 5–10 November): 203–206.

Lim, T., and W. Y. Lu. 2001. "Multiaxial Cyclic and Monotonic Behavior of a 63Sn-37Pb Solder Alloy." *Symposium on Mechanics of SMT and Photonic Structures*, accepted.

Wei, Y., C. L. Chow, E. Fang, M. Neilsen, T. Lim, and W. Lu. 2001. "Failure Analysis of Miniature Solder Specimen." *Symposium on Mechanics of SMT and Photonic Structures*, accepted.

26520

Uncertainty Propagation in Models of Thermofluid Systems

H. N. Najm, M. T. Reagan

Sandia is studying uncertainty propagation in models of thermofluid systems. This work is necessary to validate experimental results of these models and to enable use of the models as predictive engineering tools. Consequently, developing improved and efficient techniques to investigate the propagation of uncertainty in models of thermofluid systems (such as models for fire, soot, and radiation) is relevant to Sandia's Defense Programs mission. We will investigate this issue in collaboration with Johns Hopkins University.

We will develop, implement, and evaluate four approaches to quantitative assessment of uncertainty propagation using combinations of spectral, pseudospectral, and Monte Carlo (MC) studies. We will work on one-dimensional (1-D) and 2-D reacting flows, with uncertainties in reaction-rate parameters, thermodynamics, and transport. The spectral/pseudospectral approach involves reformulating the governing equations. However, the approach can be applied also in a nonintrusive spectral construction that involves appropriate processing of MC-computation results with the original equations; this could reduce accuracy and efficiency, but where existing legacy codes are used as is. A hybrid MC pseudospectral approach is also feasible and may lead to an efficient implementation. Each approach has specific advantages and costs that depend on the physical system at hand. The approaches will be developed, implemented, and evaluated in 1-D/2-D flames and outline the optimal ranges of application and utility. Mathematical and numerical formulations for the MC, pseudospectral, and nonintrusive spectral approaches are discussed here.

(1) We formulated the intrusive- and nonintrusive-spectral stochastic approach to assess propagation of uncertainties in transport properties, reaction-rate parameters, and thermodynamic properties in reacting multidimensional thermofluid systems. To formulate the intrusive-spectral construction for general chemical mechanisms, we identified a useful pseudospectral variant of the method that (a) substantially simplifies the reformulated governing equations,

Sandia is studying uncertainty propagation in models of thermofluid systems.

This work is necessary to validate experimental results of these models and to enable use of the models as predictive engineering tools.

(b) significantly enhances computational efficiency, and (c) provides a modular construction to convert a deterministic formulation to a stochastic one. This achievement has potential as an automatic deterministic-stochastic conversion tool for existing codes.

(2) We developed an approach using local-polynomial approximation for spectral treatment of specific governing equations; the equations are those that present challenges in propagating chaos expansions. This approach allows us to propagate spectral information for exponentials and other nonpolynomial functions without using MC simulations. This approach is necessary to propagate uncertainty in chemical source terms.

(3) For thermofluid systems, we developed numerical constructions for intrusive-spectral/-pseudospectral stochastic formulations and for MC simulations. These constructions include spectral stochastic projection-method solutions of nonreacting thermally stratified Boussinesq low-MACH-number 2-D flow with uncertainty in transport properties and boundary conditions, and pseudospectral 0-D chemical-reactor solutions, using a stiff integrator, with uncertainty in rate parameters and thermodynamic properties. We tested these constructions by using the Sandia DAKOTA code for sample generation for computations based on a deterministic reacting-flow solver and comparing the results to the pseudospectral construction for the same problem.

(4) We developed a numerical methodology for the full low-MACH-number reacting-flow problem. The methodology is based on the pseudospectral formulation. The construction is an extension of the above stochastic nonreacting, low-MACH-number flow technique and existing deterministic, large-density-ratio, low-MACH-number reacting-flow techniques. One significant challenge pertained to handling the chemical source term. We identified a workable construction that uses the above local polynomial approximation, based on multidimensional Taylor series (including second-order terms), to represent the net reaction rate of progress for each reaction. We confirmed this local polynomial approximation to be of sufficient accuracy. For the local polynomial approximation, probability-density function (PDF)—in reaction-rate parameters, thermodynamic properties, concentrations, or temperature—can be propagated to find the corresponding PDF for the chemical-source term.

We developed an approach using local-polynomial approximation for spectral treatment of specific governing equations; the equations are those that present challenges in propagating chaos expansions. This approach allows us to propagate spectral information for exponentials and other nonpolynomial functions without using MC simulations. This approach is necessary to propagate uncertainty in chemical source terms.

This approach fails on the individual activation-energy exponential terms, but is safe on the net-reaction rate of progress.

Refereed

Le Maitre, O. P., M. T. Reagan, H. N. Najm, R. G. Ghanem, and O. M. Knio. 2001. "A Stochastic Projection Method for Fluid Flow. II. Random Process." *J. Computational Physics* (Academic Press), submitted.

26521

Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements

S. P. Kearney, R. W. Schefer, S. J. Beresh, T. W. Grasser

Sandia is researching simulation-based life-cycle engineering, which—along with studies from the Accelerated Strategic Computing Initiative (ASCI)—has resulted in models of unprecedented size and fidelity. Model validation requires high-resolution, multiparameter diagnostics. Within the thermal/fluids disciplines, the need for detailed, high-fidelity measurements exceeds the limits of current engineering sciences capabilities and severely tests the state of the art; therefore, a diagnostic development effort is warranted. The focus of this project is to develop and apply filtered Rayleigh scattering (FRS) for high-resolution, nonintrusive measurement of velocity, temperature, and pressure.

With FRS, the flow is laser-illuminated, and Rayleigh scattering from naturally occurring sources is detected through a molecular filter. The filtered transmission may be interpreted to yield point or planar measurements of three-component velocities and/or the thermodynamic state. This capacity for multiparameter, nonintrusive instrumentation represents an unprecedented advance beyond existing techniques in the Engineering Sciences Center and in the larger scientific arena. The FRS technique is well suited for production-scale facilities, where many other techniques are difficult to implement. Potential validation applications include simultaneous three-component velocity, temperature, and pressure measurements in compressible flows to support SACCARA/PREMO validation, and full-field temperature measurements in reacting or nonreacting flows for FUEGO and SIERRA/CALORE validation.

Sandia is researching simulation-based life-cycle engineering, which ... has resulted in models of unprecedented size and fidelity. Model validation requires high-resolution, multiparameter diagnostics.

Key accomplishments include the following:

- (1) Installed an injection-seeded Nd:YAG laser and automated the control and scanning of the injection-seeded laser frequency.
- (2) Designed, acquired, and calibrated molecular-filter cells.
- (3) Designed and constructed a versatile laboratory-scale jet apparatus for diagnostic-development measurements.
- (4) Set up a functional FRS-imaging system.

(5) Developed software to interpret the molecular scattering images.

(6) Acquired CARS temperature data in a pulsed-diffusion flame to validate the FRS temperature measurements.

We completed the installation and alignment of an injection-seeded Nd:YAG laser. Injection seeding is crucial for FRS measurements because the laser-beam frequency must be finely tuned to a desired spectral location in the molecular-filter absorption profile. Scanning the injection-seeded frequency over a broad range is also critical to calibrate the molecular filters themselves. We developed a fully automated data-acquisition-and-control system for the control and monitoring of the seeder laser. The system has successfully characterized multiple molecular-filter cells. Failure of the original seeder supplied with the Nd:YAG system impeded progress slightly. A newer model replaced the seeder, and the system is now functional.

We obtained custom-made molecular-filter cells from a commercial supplier. The filters include temperature control and, upon receipt, were fitted with a vacuum and buffer-gas supply system to tailor the molecular absorption profile to any given experimental need. The filters are glass cylinders containing iodine vapor, which exhibits a unique absorption spectrum over the tunable range of the Nd:YAG laser system. It is this absorption spectrum that gives the FRS technique its sensitivity by spectrally filtering the Rayleigh-scattered light signal in a temperature- and velocity-sensitive manner. The cells are thermally jacketed and carefully temperature-controlled to maintain a constant gas density under vacuum conditions. This allows relatively simple control of the absorption line strength and width by adjusting the cell's gas composition, temperature, and pressure, offering a superior flexibility to the FRS system that permits switching between temperature and velocity measurements over a wide range of flow conditions with minimal alterations to the optical system.

A functional FRS imaging system that includes all laser sheet-forming optics, laser frequency and power monitoring, and multiple-CCD (charge-coupled device)-camera detection was constructed in the Engineering Sciences Experimental Facility (ESEF). Prior to implementing the FRS optical setup for production-scale measurements, it is necessary to perform laboratory-scale diagnostic-development experiments. These experiments will be conducted in both supersonic jets and low-speed heated jets. Since such jet

We completed the installation and alignment of an injection-seeded Nd:YAG laser. Injection seeding is crucial for FRS measurements because the laser-beam frequency must be finely tuned to a desired spectral location in the molecular-filter absorption profile. Scanning the injection-seeded frequency over a broad range is also critical to calibrate the molecular filters themselves. We developed a fully automated data-acquisition-and-control system for the control and monitoring of the seeder laser. The system has successfully characterized multiple molecular-filter cells.

facilities were not already available to us, we designed and constructed them as part of the current project. This jet facility is extremely versatile and allows for velocity-temperature imaging in sonic and MACH 3.7 jets and for temperature imaging in a low-speed turbulent jet with an exit temperature of 800 K. We are presently acquiring FRS thermal images from the low-speed jet.

We developed custom software for interpretation of the emerging FRS images and assessment of the FRS measurement uncertainty in house. The software can deduce temperature or velocity by convolving molecular-filter calibration data, obtained from automated seeder frequency scanning, with the theoretically calculated Rayleigh-scattering spectrum. The software is highly flexible and can be used in both nonreacting and reacting flows and for any given flow-gas composition with known transport coefficients.

As part of the FRS diagnostic development effort, validation data for FRS temperature measurements are currently being acquired at the Combustion Research Facility.

We developed custom software for interpretation of the emerging FRS images and assessment of the FRS measurement uncertainty in house. ... The software is highly flexible and can be used in both nonreacting and reacting flows and for any given flow-gas composition with known transport coefficients.

Other Communications

Beresh, S. J. 2001. "Aerodynamic Instrumentation for Sandia's Aerosciences Experimental Activities." Paper presented to the AIAA Aerodynamic Measurement Technology Technical Committee, Anaheim, CA, 11 June.

Kearney, S. P. 2000. "Experimental Methods for Convective Heat Transfer." Paper presented to Joint SNL/CESTA Fire-Research Conference, Sandia National Laboratories, Albuquerque, NM, October.

Kearney, S. P. 2001. "Laser Diagnostics for Convective-Heat Transfer—Planar Laser-Induced Fluorescence and Filtered Rayleigh Scattering." Poster presentation at the ASME International Mechanical Engineering Congress and Exposition (IMECE), New York, NY, November.

26522

A Physically Based Approach to Modeling Ductile Fracture

P. A. Klein, D. J. Bammann, B. R. Antoun, S. X. McFadden

Sandia is developing a new computational tool for modeling crack growth in ductile materials. Ductile fracture is the most common mode of fracture in metals where the material fails from a combination of excessive bulk deformation and cracking. Crack initiation and growth in ductile materials consume energy because of the evolution of bulk plastic and damage processes and the creation of new free surfaces. The response and evolution of the dissipation mechanisms is inherently scale- and strength-dependent; therefore, a computational model of these damage processes must reproduce the physical dimensions and stresses in the fracture-process zone.

Development of this computational tool begins with a fundamental, thermodynamically sound description of the failure process that encompasses both ductile failure and fracture mechanics. Developing a thermodynamic theory that includes the dissipation of the bulk material and the surface energy of a cohesive zone requires developing a new kinematical description of the failure process to couple these concepts at a basic level. In situ scanning electron microscope (SEM) observations of initiating and evolving fracture zones will reveal the scale over which the failure mechanisms act in Defense Program (DP) alloys 6061 aluminum (Al) and 304L stainless steel (SS) and in copper (Cu). These observations are essential for motivating micromechanical models of the decohesion processes that incorporate the effects of mode mixity in the loading, temperature, loading rate, and load reversals. The effect of load reversals must be incorporated into the computational model to model fatigue.

We formulated the coupling between bulk deformation processes and cohesive-surface relations. The coupling acts first by linking the initialization of failure surfaces with a critical-void volume fracture, and second by coupling the surface-traction evolution relations to the state of material stress, dislocation densities, and damage at initiation. With sample calculations, we demonstrated how including the damage mechanics in the bulk model of plasticity is unsuitable for modeling ductile fracture. Our preliminary,

Three-dimensional plastic zones.

Sandia is developing a new computational tool for modeling crack growth in ductile materials. Ductile fracture is the most common mode of fracture in metals where the material fails from a combination of excessive bulk deformation and cracking.

three-dimensional crack-growth simulations demonstrate the variation in crack-tip plasticity through the sample thickness. We developed a complete thermodynamic description showing the relationship between the evolution of plastic strain, mechanisms of dislocation storage, and the growth of voids during the fracture process. We formulated a simplified analytical model for degree of heating in the near-tip region as a function of plastic response, thermal conduction, and crack-growth rate. For the materials we will be testing, the model predicts significant temperature rises over the dimensions we are considering. The analysis supports our initial assumption that a complete thermomechanical description of the fracture process is needed to model ductile fractures in detail. The results also indicate that the local temperature changes should be large enough for detection in experiments. We are preparing for *in situ* SEM observations of fracture. We completed material selection and are finalizing the specimen design. We obtained the precracking specimens of 6061, 304L, and Cu. After these specimens are fatigue-loaded to produce a sharp initial precrack, we will extract microbeam samples for loading the *in situ* SEM three-point bending state. We designed, fabricated, and installed the three-point bending state in the SEM. Calibration of the load system is under way. The experimental observations will first provide a view of the size and structure of the fracture process zone. This will motivate the development of traction-evolution laws based on models void coalescence, ligament bridging, or other processes that our observations have identified. We developed a system to map displacements around the crack tip by tracking surface marker. In addition, we have begun developing a plastic-strain mapping method based on the coherence of the diffraction pattern produced by back-scattered electrons in the SEM. This method will allow us to get quantitative information about the amount of plastic strain generated around the crack tip. Using a newly acquired field-emission SEM, we should be able to obtain micron-scale resolution of changes in plastic strain. Additionally, the experiments will provide data for validating the predictions of simulated crack growth.

We developed a complete thermodynamic description showing the relationship between the evolution of plastic strain, mechanisms of dislocation storage, and the growth of voids during the fracture process. We formulated a simplified analytical model for degree of heating in the near-tip region as a function of plastic response, thermal conduction, and crack-growth rate.

26523

Radiation Aging of Stockpile and Space-Based Microelectronics

H. P. Hjalmarson, S. C. Witzak, P. A. Schultz, J. R. Schwank, M. R. Shaneyfelt, C. E. Hembree, C. H. Seager

Sandia is using an experiment-theory collaboration to develop a complete computational model of three important radiation effects phenomena: (1) enhanced low-dose-rate sensitivity (ELDRS), (2) pre-irradiation elevated-temperature stress (PETS), and (3) latent-interface-trap buildup (LITB). We combined two earlier studies. One is the experimental effort suggesting that the ELDRS problem can be related to LITB for transistors that have undergone PETS. The second is the theoretical effort relying on a hydrogen (H)-dimerization mechanism to explain the ELDRS problem. In this new project, our goal is to build upon previous work to develop a unified explanation for the three experimental phenomena.

In an initial assessment phase, we modified the continuum kinetics-transport code to include additional sites for radiolytic H within the oxide. Calculations made with the new code suggest that we can explain the LITB and PETS data by postulating new sites that release H. We developed a plan for new experiments involving total dose and dose-rate studies for which the temperature was varied and completed some of these experiments. We discovered that PETS had no effect on devices for which the passivation layer had been removed. We explored the temperature dependence of the H dimerization model by developing an analytical model.

Going beyond this phase, we modified the H dimerization model. In the modified model, we assume that neutral H is directly released from sites in the oxide instead of assuming that protons became neutralized at the interface. We made this change in the model because electronic structure calculations indicated that protons would not become neutralized at the interface.

The stimulus for the modified model was theoretical. However, the scientific literature contains information that supports this model. Evidently, release of neutral H was dropped from consideration once evidence for protons was accumulated.

Sandia is using an experiment-theory collaboration to develop a complete computational model of three important radiation effects phenomena: (1) enhanced low-dose-rate sensitivity (ELDRS), (2) pre-irradiation elevated-temperature stress (PETS), and (3) latent-interface-trap buildup (LITB).

We began a new experiment to seek evidence for release of neutral H. Preliminary results show evidence for both neutral H and protons, as expected in the modified model. We also developed, but did not test, a modified theory.

26524

Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach

D. R. Noble, S. W. Attaway, S. R. Subia, J. R. Weatherby, P. K. Notz, P. R. Schunk, T. A. Baer

Sandia is conducting a study on solidification and blood flow, which might seem to have little in common. However, each topic involves a fluid in contact with a deformable solid. In these systems, the fluid-solid interface moves as the solid advects and deforms, often traversing the entire domain of interest.

Currently, fluid-solid-interface problems cannot be simulated without conducting innumerable, expensive remeshing steps and mesh manipulations, or without decoupling the solid and fluid motion. Despite recent progress in mechanics modeling, this glaring inadequacy persists. We seek a new technique that tracks the interface implicitly and circumvents the need for remeshing and remapping. The fluid-solid boundary is tracked with a level-set algorithm that changes the equation type dynamically, depending on the phases present. This novel approach to coupled mechanics problems promises to give accurate stresses, displacements, and velocities in both phases simultaneously. This effort involves high-risk research in Eulerian solid mechanics of bodies defined by an implicit interface (not defined by a mesh contour). An equally difficult task is equating the solid and fluid stresses at this implicit interface. Simulating fluid mechanics requires a Eulerian formulation to avoid mesh entanglement. Solid mechanics formulations, however, tend to be Lagrangian, as it is easier to track material interfaces, compute strain, and apply boundary conditions (BCs). We will handle the complete problem in a Eulerian context using level sets to define the solid-fluid interfaces. We will apply the advances made in level-set methods for multiphase fluids to this more difficult problem involving multiple physics.

High-payoff applications are as numerous as the complex moving geometry problems that we seek to address every day. A small subset includes solidification and polymerization with accurate residual-stress determination and biological applications, such as cell deformation and blood rheology. Many of these problems cannot be adequately addressed using existing methods, but may be quantitatively simulated using the methods we propose.

Sandia is conducting a study on solidification and blood flow, which might seem to have little in common. However, each topic involves a fluid in contact with a deformable solid. In these systems, the fluid-solid interface moves as the solid advects and deforms, often traversing the entire domain of interest.

We looked at two formulations to simulate solid-fluid interactions in a context where a level-set function determines the interface and a Eulerian-frame description solves the mechanics in both phases. We also broadened the project scope to study the implementation of boundary and interface conditions at embedded interfaces that slice through elements and are not defined by mesh boundaries. We also investigated a hybrid arbitrary-Lagrangian-Eulerian (ALE)-Eulerian technique that uses an overlapping-grid approach where the fluid mesh covers the entire domain and the solid mesh covers the solid material. The overlapping-mesh approach has proved to be a valuable test-bed for studying proposed embedded-interface methods.

We developed formalisms for both Eulerian-mechanics formulations and tested a highly simplified one-dimensional (1-D) solidification problem. These two methods are called *continuous-field method* and *continuous-equation method*. The first uses field quantities, including velocity and displacement, that span the interfacial region, but the equation types dynamically change as we move from one phase to the next. The second uses a single viscoelastic equation to describe the physics in both phases and a hypoelastic velocity-stress tensor-velocity gradient discretization in both phases. We developed a mathematical formalism for both techniques. A first implementation of the continuous-field method was shown to yield an accurate, fully coupled simulation of an elastic solid in contact with a viscous fluid; this is our analogue to a solidification problem, but with a stationary interface. Similarly, we completed implementation for the continuous-equation method, and it too shows accurate results for the stationary-interface solidification problem.

Surpassing our original milestones, we examined a complex 2-D problem with the overlapping-grid approach, where location of the solid is communicated to the fluid by the level-set function. The problem has a fluid flowing past an elastic-solid valve, causing deformation. From this we have learned two important things. First, our current approach using a method that decouples the level set from the bulk mechanics will not work for coupled fluid-solid interactions (FSI), because material interface locations from the level set are needed to apply the correct mechanics. Thus, we spent considerable effort reintegrating the level-set equations into the bulk equations. This was difficult because of the cross-coupling between the level set and the material properties. Second, our quasi-static solid-mechanics formulation in

Surpassing our original milestones, we examined a complex 2-D problem with the overlapping-grid approach, where location of the solid is communicated to the fluid by the level-set function. The problem has a fluid flowing past an elastic-solid valve, causing deformation. From this we have learned two important things.

GOMA was inadequate for FSI problems. To accurately describe the dynamics of the phases, solid inertia was critical. We expended much effort to implement an energy-conserving formulation of the equations for solid inertia.

The third milestone involves verifying and benchmarking the two mathematical formalisms against a known, previously verified algorithm based on an ALE approach. To perform these benchmarks, we must not only handle the bulk mechanics, but also address the interfacial physics, namely the application of BCs. This was the third thrust area. By combining a newly developed ghost-fluid capability with the continuous-field approach, we successfully simulated a steady-state fluid structure interaction problem. The method allows us to implicitly enforce the interfacial balance along a boundary that does not correspond to a mesh surface. This may be the first ghost-fluid implementation in the finite-element context. We collaborated with the University of Washington regarding LaGrange multipliers and their application to enforcing interfacial conditions at embedded boundaries in a weak sense. Combinations of the ghost-fluid and LaGrange-multiplier methods promise rich methods for imposing sharp interfacial conditions.

By combining a newly developed ghost-fluid capability with the continuous-field approach, we successfully simulated a steady-state fluid structure interaction problem.

The method allows us to implicitly enforce the interfacial balance along a boundary that does not correspond to a mesh surface.

This may be the first ghost-fluid implementation in the finite-element context.

Refereed

Baer, T. A., D. R. Noble, and R. R. Rao. 2001. "Level-Set Tracking of Fluid Interfaces Using Finite Elements." *Proc. International Conference on Computational Engineering and Sciences, ICES 2001* 1 (Puerto Vallarta, Mexico, 20–23 August): CD.

Noble, D. R., T. A. Baer, and R. R. Rao. 2001. "Contact-Angle Specification in Level-Set Simulations." Paper presented to the DFD Meeting of the American Physical Society, San Diego, CA, November.

Other Communications

Finlayson, B. A. (University of Washington). 2001. "Finite-Element Methods for Problems with Moving and/or Irregular Boundaries." Report to Dr. Rekha Rao, Sandia National Laboratories, Seattle, WA, 28 August.

26781

Effect of Dielectric Photoelectric Effect on Surface Breakdown

R. E. Jorgenson, L. K. Warne

Sandia wrote a Monte Carlo (MC) code to simulate the early stages of high-voltage breakdown that occurs in air across a dielectric surface. The application of this research is to understand breakdown caused by lightning in nuclear weapons components. During surface breakdown, as electrons collide with neutrals in a gas, photons of various energies are released. Some of the photons have high enough energies to cause neutrals ahead of the streamer (a breakdown wave) front to ionize and thus advance the front. These are the only photons of importance in volumetric breakdown, and we have accounted for these using the data of Penney and Hummert. When a dielectric surface is introduced, however, the lower-energy photons, which are released in a collision that excites the neutral, must also be considered because the photons can release electrons from the dielectric surface ahead of the front through photoemission. Because these lower-energy photons propagate further and because more of them exist than the photons that ionize directly, we anticipated that the low-energy photons play a major role in advancing the surface streamer. Discussions in recent literature confirm this effect. No quantitative modeling on the effect has been done thus far. In collaboration with Texas Tech, we will obtain data on this effect in such a form that the effect can be included in our MC breakdown code.

Sandia assembled some data from the literature on subprocesses that may contribute photoemission from breakdown, and we incorporated the subprocesses into the code. Where data were lacking, we used bounding approximations. This allowed us to examine the existing experimental data to determine data adequacy and to change the code structure to account for the new processes. The subprocesses we assembled were (1) creating a photon from a collision between an electron and a gas neutral, (2) transporting the photon through the gas to the dielectric surface, and (3) releasing an electron from the surface due to photoemission. From the limited photoemission data available on insulators, apparently to release electrons, the photons must have a wavelength of less than approximately 2400 Å.

Sandia wrote a Monte Carlo (MC) code to simulate the early stages of high-voltage breakdown that occurs in air across a dielectric surface.

The application of this research is to understand breakdown caused by lightning in nuclear weapons components.

Therefore, we need to obtain data on the number of photons created during an inelastic collision and their energies; we will restrict our search to wavelengths of less than 2400 Å. We found some collision cross-sections for nitrogen; cross-sections are necessary when calculating the number of photons created. We also did a preliminary examination of the transport of photons through the gas; transport consists of a complex process of emission, absorption, and re-emission. With the bounding approximations in the code, at a high field of 3 MV/m, the photoemissions from the surface seem to cancel the effect of secondary electron emission, which causes low-energy electrons to stick to the surface of the dielectric. The balance of these two effects might change at lower field levels, which we have yet to investigate.

We also did a preliminary examination of the transport of photons through the gas; transport consists of a complex process of emission, absorption, and re-emission.

Other Communications

Jorgenson, R. E., L. K. Warne, and E. E. Kunhardt.
2000. "Lightning-Induced Arcing: An LDRD Report."
Sandia Technical Report SAND2000-3044, Sandia
National Laboratories, Albuquerque, NM (December).

Grand Challenges

The Grand Challenges investment area investigates innovative ideas with the potential for dramatically impacting national-level concerns and for creating technologies and processes required for the twenty-first century. Grand Challenges engage lab-wide multidisciplinary research teams that establish critical mass in participation and funding to focus on world-class research. High-risk, potentially outrageous ideas are considered for investigation. In addition, all Grand Challenges research efforts must identify linkage to supporting Sandia's business goals.

The goal of the "Molecular Integrated Microsystems (MIMS)" project is to combine molecularly tailored nanomaterials with addressable microdevices to demonstrate the first-ever programmable MIMS devices for protein and peptide analysis. MIMS have the potential to provide new means for encoding information and safeguard weapons, to open completely new routes to attack important problems in chemistry and biology, and to lead to the development of a new class of materials that combines biological functions and molecular systems with robust and manufacturable materials. The full benefit of the

current trend in miniaturization will be achieved only when microscale addressability is used to control materials properties and molecular interactions. The ability to manipulate nanoscale structures and molecular interactions is at the heart of the next revolution in programmable microsystems. This work has received three patents and has several patents pending.

10399

Information Collection

D. D. Spencer, F. T. Mendenhall, R. M. Axline, M. W. Scott, R. J. Simonson, T. S. Prevender, L. C. Bartel, G. A. Thomas, M. C. Walck, R. D. Robinett, III, W. R. Bolton, Jr., R. W. Crocker, K. T. Stalker, G. J. Elbring, L. A. Boye, D. L. Keese, S. A. Dupree, A. K. Miller, R. J. Bickerstaff, R. C. Ormesher, H. M. Poteet, M. R. Daily, W. D. Morse, K. O. Wessendorf, L. R. Thorne, L. G. Stotts, J. L. Russell

This project is classified and no summary is available.

11130

Molecular Integrated Microsystems (MIMS)

L. M. Napolitano, D. Y. Sasaki, S. A. Kemme, B. C. Bunker, D. R. Wheeler, S. A. Casalnuovo, A. K. Singh, S. M. Brozik, T. J. Shepodd, A. P. Thompson, A. R. Burns, B. G. Potter, Jr., K. S. Potter, C. J. Brinker, E. T. Southwell, B. J. Kirby, J. V. Volponi, R. P. Manginell, M. L. Garcia, C. M. Matzke, G. M. Jamison, J. Han, R. D. Elliott, K. Wally, A. Artau, M. E. Warren, A. W. Walker, N. C. F. Woo, D. J. Throckmorton

Microfabrication tools and processes developed for the microelectronics industry make it possible to miniaturize devices including chemical analysis systems, navigational components, and mechanical locks. Sandia's experience with microsystems has shown that direct miniaturization of conventional architectures can provide significant benefit through increased portability, low power consumption, and improved speed of operation. We believe that the full benefit of miniaturization will be achieved only when microscale addressability is used to control nanoscale materials properties and molecular interactions.

In Sandia's molecular integrated microsystems (MIMS) project, we are pursuing a revolutionary approach to microsystems in which microscale patterning of functional materials is combined with local addressing (electrical, optical, and thermal fields) to provide fully programmable systems and architectures. The overall goal of this project is to combine molecularly tailored nanomaterials with addressable microdevice architectures to demonstrate the first-ever programmable MIMS devices for protein and peptide analysis and encoded optical interconnects.

We built on the technical advances made previously as we began developing engineering approaches required to design and construct proof-of-principle devices that will meet our target capabilities. New molecular sorting and detection approaches were developed, including EK (electrokinetic) trapping and switchable polymer coatings. We demonstrated the first-ever programmable preconcentration of proteins in solution. We developed new fluidic architectures around newly discovered Mobile Monolith Technology. Our programmable optics work explored a set of photosensitive materials that shows extremely promising optical response. As

Sandia's experience with microsystems has shown that direct miniaturization of conventional architectures can provide significant benefit through increased portability, low power consumption, and improved speed of operation. We believe that the full benefit of miniaturization will be achieved only when microscale addressability is used to control nanoscale materials properties and molecular interactions.

we optimize our fabrication approaches, we continue to build on our understanding of the underlying phenomena for each case.

The major technical activities for the MIMS project focused on down-selecting materials and platforms with the highest potential for function and integration. We also began designing new chip-based architectures that utilize on-the-fly programming to address our top-level goals for biochemical analysis of proteins and peptides, and the development of new optical safety and surety architectures.

- *Biochemical analysis.* We developed a completely new architecture for analysis of proteins and peptides that builds on the overall MIMS vision and takes advantage of our technical discoveries. The new architecture, microProLab, combines programmed biomolecule capture and release, on-chip separations, and microfluidic routing. The major features of this new architecture are (1) preconcentration of dilute protein and peptide samples, (2) programmed protein injection into separation columns, (3) on-chip biochemical separations, (4) mobile monolith-based valves to route and segment flow stream, and (5) coupled modules to perform new separations on reconstituted analyte plugs.

The development of the microProLab architecture depends on significant technical advances that have been made in each of the component areas.

- *Protein and peptide preconcentration.* We invented and demonstrated two new approaches that can be used to preconcentrate proteins and peptides out of a fluid stream. In the first approach, which we call *EK trapping*, the integration of a nanoporous material in the microfluid stream acts to capture biomolecules from solution in the presence of an applied electric field. When the electric field is removed, the biomolecules are released back into solution. Using this approach, we demonstrated 1,000-fold preconcentration of proteins in solution, followed by sharp injection back into the fluid stream. We also developed a new set of nanoporous materials with closely controlled pore sizes that we hope will further improve the performance of our E-K Trapps.

Our second approach to preconcentration involves switchable polymer films integrated onto a microfabricated hotplate structure. The polymer films undergo a structural phase transformation that causes the reversible adsorption and desorption of proteins from solution. We demonstrated this approach in a fully integrated microchip device.

We developed a completely new architecture for analysis of proteins and peptides that builds on the overall MIMS vision and takes advantage of our technical discoveries. The new architecture, microProLab, combines programmed biomolecule capture and release, on-chip separations, and microfluidic routing.

- *On-chip peptide separations.* We developed a set of photopatterned, cast-in-place porous polymers and demonstrated their integration in microfluid channels for on-chip separations. Using this approach, we demonstrated the separation of a wide range of peptides with separation times of less than one minute.

- *Valving and routing.* Valving and segmenting flow streams in microfluid systems is a major challenge, and we developed a completely new approach to achieve on-chip microfluid routing. Our approach utilizes another form of cast-in-place polymers that act as mobile fluid barriers. The barriers can be reversibly positioned within the microchannels using external pressure signals. We used this new approach to develop check valves, diverters, and fluid channel segmenters. Valves built from this new technology are capable of sealing against pressures up to 1000 pounds per square inch.

- *Programmable optical interconnects.* The ability to route optical energy on demand has the potential to open the way for new weapons-surety applications. We identified and explored a set of polymers that can be optically programmed and demonstrated this programming as a means to route, in real time, optical signals in either waveguide or free-space optical configurations. The materials can be “written” at wavelengths consistent with current solid-state lasers and used to guide light in the visible wavelengths.

- *Market Intelligence and External Committee.* The MIMS External Advisory Committee endorsed our research plan and accomplishments and asked us to work toward plans to integrate the exciting new components developed thus far in the MIMS project.

The MIMS External Advisory Committee endorsed our research plan and accomplishments and asked us to work toward plans to integrate the exciting new components developed thus far in the MIMS project.

Refereed

- Hasselbrink, E. F., J. E. Rehm, and P. H. Paul. 2001. "Design Rules for Active-Control Injection Programs in Microchip Analysis Columns." *Electrophoresis*, accepted.
- Hasselbrink, E. F., J. E. Rehm, B. J. Kirby, and T. J. Shepodd. 2001. "Flow Control Devices Fabricated Using *In Situ* Photopolymerization of Mobile Monoliths." Paper presented to the Gordon Research Conference on the Physics and Chemistry of Microfluidics, Oxford, United Kingdom.
- Huber, D. L. 2001. "Formation of Polymer Monolayers Via Chain Transfer Techniques." *J. American Chemical Society*, accepted.
- Huber, D. L., J. G. Kushmerick, T. Dunbar, C. Matzke, R. P. Manginell, and B. C. Bunker. 2001. "Switchable Protein Adsorption on Tethered Polymer Films." *Science*, accepted.
- Kirby, B. J., A. R. Wheeler, T. J. Shepodd, J. A. Fruetel, E. F. Hasselbrink, and R. N. Zare. 2001. "A Laser-Polymerized Thin-Film Silica Surface Modification for Suppression of Cell Adhesion and Electroosmotic Flow in Microchannels." Paper presented to μ TAS, Monterey, CA.
- Kirby, B. J., E. F. Hasselbrink, J. E. Rehm, and T. J. Shepodd. 2001. "Active Flow Control Using Mobile Polymer Monolith Microvalves." Paper presented to the Gordon Research Conference on the Physics and Chemistry of Microfluidics, Oxford, United Kingdom.
- Kushmerick, J. G., J. E. Houston, and B. C. Bunker. 2001. "Hydration Forces: The Role of Interphase Water." *Science*, accepted.
- Ngola, S. M., Y. Fintschenko, W. Y. Choi, and T. J. Shepodd. 2001. "Conduct-as-Cast Polymer Monoliths as Separation Media for Capillary Electrochromatography." *Analytical Chemistry* **73**: 849–856.
- Rehm, J. E., T. J. Shepodd, and E. F. Hasselbrink. 2001. "Mobile Flow Control Elements for High-Pressure Microanalytical Systems Fabricated Using *In Situ* Polymerization." Paper presented to μ TAS, Monterey, CA.
- Shediac, R., S. M. Ngola, D. J. Throckmorton, D. S. Anex, T. J. Shepodd, and A. K. Singh. 2001. "Reverse-Phase Electrochromatography of Amino Acids and Peptides Using Porous Polymer Monoliths." *J. Chromatography A*, accepted.
- Singh, A. K., D. J. Throckmorton, and T. J. Shepodd. 2001. "Rapid Separations of Peptides and Amino Acids in Glass Microchips by Reverse-Phase Electrochromatography." Paper presented to μ TAS, Monterey, CA.
- VanderNoot, V. A., G. Hux, J. Schoeniger, and T. J. Shepodd. 2001. "Isoelectric Focusing Using Electrokinetically Generated Pressure Mobilization." Paper presented to μ TAS, Monterey, CA.

27328

A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting

J. M. Gee, H. K. Moffat, R. M. Biefeld, E. D. Jones, G. M. Peake, J. P. Wilcoxon, C. C. Mitchell, W. C. Sweatt, J. R. Creighton, A. F. Wright, W. W. Chow, M. J. Hafich, G. H. Evans, J. J. Figiel, S. A. Kemme, A. J. Fischer, C. I. H. Ashby, D. D. Koleske, R. J. Shul, J. R. Wendt, J. A. Emerson, M. E. Coltrin, A. A. Allerman, C. H. Seager, L. E. S. Rohwer, S. R. Kurtz

Solid-state light-emitting diodes (LEDs) that emit across the visible spectrum have developed rapidly. LEDs have opened possibilities for generating white light for general-purpose illumination at efficiencies far higher than existing conventional light sources. The conversion to high-efficiency (approximately 50 percent at the wall-plug) solid-state lighting has the potential to save up to \$100 billion per year on electrical-energy costs. The technology will also create completely new applications based on solid-state lighting compactness, ruggedness, large intensity variation, directionality, reduced heat output, programmable color rendering, and amenability to high-frequency modulation for communication purposes.

Developing a high-efficiency solid-state white-light source will require (1) improved LED and/or vertical-cavity surface-emitting laser (VCSEL) efficiency to the 50 percent range, (2) extended color spectrum of these high-efficiency optical emitters into the yellow, green, blue, and possibly also ultraviolet (UV) ranges, and (3) a substantially reduced cost.

The goal of this Grand Challenge project is to establish the fundamental science and technology bases required to realize this vision of ultra-efficient solid-state illumination. Sandia is pursuing a balanced research program that addresses the following topics: solid-state materials theory and characterization, optimization of III-nitride growth and substrates, metalorganic chemical-vapor deposition (MOCVD) chemistry, reactor design and control, luminescent-conversion materials, and solid-state lighting packaging.

These pursuits will position Sandia as the national leader in these areas. This endeavor will also result in the development of infrastructure and associated synergistic technology of vital importance for national security needs in the important III-nitride material system and other associated technologies (such as semiconductor nanoclusters).

The goal of this Grand Challenge project is to establish the fundamental science and technology bases required to realize this vision of ultra-efficient solid-state illumination.

Sandia is in the early stages of this project. However, our progress suggests the project will have a significant impact on solid-state lighting and on gallium nitride (GaN) technology. Achievements to date include the following:

(1) We hosted a workshop in collaboration with DOE Office of Building Technology (BTS) and produced a technology roadmap for inorganic, solid-state lighting.

(2) We described the effect of Ga vacancies and N interstitials on hydrogen (H) in GaN. We refined models of H kinetics in GaN.

(3) We transferred GaN MOCVD growth processes to a new growth reactor.

(4) We improved our sapphire reactive-ion etching (RIE); this improvement is critical for extending low-defect cantilever epitaxy to larger areas and reducing defects over nucleation mesas. Also, we confirmed that the crystallographic tilt of the cantilever epitaxy is not too large a concern. Cantilever epitaxy is a Sandia invention that could dramatically reduce dislocations in GaN epitaxy on common lattice-mismatched substrates (e.g., sapphire).

(5) We examined important chemical-reaction sink processes in aluminum-gallium-nitride (AlGaN) MOCVD growth, and we believe the parasitic chemical reactions occur in the hot zone rather than the cold zone. Understanding this chemistry is very important for designing next-generation large-throughput MOCVD reactors.

(6) We began characterizing gas-flow instabilities using laser-deflection techniques. Flow instabilities are believed to be a larger concern for GaN MOCVD because the growths are typically performed at high pressures and temperatures.

(7) We began development of new *in situ* temperature monitoring using emissivity-corrected pyrometry for GaN MOCVD.

(8) We developed a new concept for significantly improved light extraction in LEDs and began collaborating with a private company to realize visible photonic lattices in LEDs.

(9) We improved some important components (*p*-type contacts, stress control for distributed Bragg reflectors [DBRs], and more) for UV LEDs and VCSELs. We also developed a rapid-turnaround process that cuts in half the time to fabricate an LED for improved experimental efficiency.

(10) We characterized a triphosphor blend using commercial inorganic phosphors for near-UV excitation and

... our progress suggests the project will have a significant impact on solid-state lighting and on gallium nitride (GaN) technology.

with good color rendering. We also began characterizing semiconductor nanocrystals and developing encapsulation for the nanocrystals.

Refereed

- Ashby, C. I. H., C. C. Mitchell, J. Han, N. A. Missert, P. P. Provencio, D. M. Follstaedt, G. M. Peake, and L. Griego. 2001. "Low-Dislocation-Density GaN from a Single Growth on a Textured Substrate." *J. Applied Physics* **77** (November): 3233.
- Han, J., K. E. Waldrip, and J. J. Figiel. 2001. "MOCVD Growth and Characterization of AlGaIn/GaN/GaInN Vertical-Cavity Surface-Emitting Lasers." Paper presented to the 10th Biennial Workshop on MOVPE, San Diego, CA, March.
- Han, J., K. E. Waldrip, S. R. Lee, J. J. Figiel, S. J. Hearne, G. A. Petersen, and S. M. Myers. 2001. "Control and Elimination of Cracking of AlGaIn Using Low-Temperature AlGaIn Interlayers." *Applied Physics Letters* **78** (January): 67.
- Jones, E. D. 2001. "LED Solid-State Lighting for Illumination: Status Report." *Proc. SPIE Conference* (January).
- Jones, E. D. 2000. "Solid-State Light-Emitting Diodes for General Illumination: An OIDA Workshop Preliminary Report." Paper presented to the LED Solid-State Lighting Roadmapping Workshop, Washington, DC, October.
- Myers, S. M., A. F. Wright, G. A. Petersen, W. R. Wampler, C. H. Seager, M. H. Crawford, and J. Han. 2001. "Diffusion, Release, and Uptake of Hydrogen in Magnesium-Doped Gallium Nitride: Theory and Experiment." *J. Applied Physics* **89**: 3195.
- Waldrip, K. E., J. Han, S. J. Hearne, J. J. Figiel, G. Peterson, and S. M. Myers. 2000. "Control and Elimination of Cracking of AlGaIn Films Using Low-Temperature AlGaIn Interlayers." Paper presented to the Fall 2000 Meeting of the Materials Research Society, Boston, MA, November.
- Wampler, W. R., S. M. Myers, A. F. Wright, J. C. Barbour, C. H. Seager, and J. Han. 2001. "Lattice Location of Hydrogen in Mg-Doped GaN." *J. Applied Physics* **90**: 108.
- Wright, A. F. 2001. "Interaction of Hydrogen with Gallium Vacancies in Wurtzite GaN." *J. Applied Physics* **90**: 1164.
- Zhou, H., M. Diagne, E. Makarona, A. V. Nurmikko, J. Han, K. E. Waldrip, and J. J. Figiel. 2000. "Near-Ultraviolet Optically Pumped Vertical-Cavity Laser." *Electronics Letters* **36** (October): 1777.

Other Communications

- Ashby, C. I. 2000. "Cantilever Epitaxy: A Simple Lateral Growth Technique for Reducing Dislocation Densities in GaN and Other Nitrides." Paper presented to the 198th Meeting of the Electrochemical Society, Notre Dame, IN, October.
- Ashby, C. I., *et al.* 2001. "Cantilever Epitaxy and Its Potential for GaN Substrates with Whole-Wafer Dislocation Densities Below 10^7 cm^{-2} ." Paper presented to the 43rd Electronic Materials Conference, Phoenix, AZ, June.
- Breiland, W. G., L. A. Bruskas, A. A. Allerman, and T. W. Hargett. 2001. "Emissivity-Correcting Pyrometry for OMVPE Applications." Paper presented to the 10th Biennial Workshop on Organometallic Vapor Phase Epitaxy, San Diego, CA, 11–15 March.
- Coltrin, M. E., C. C. Mitchell, and J. Han. 2001. "Kinetics and Transport in Gallium Nitride Epitaxial Lateral Overgrowth." Paper presented to the 199th Meeting of the Electrochemical Society, Washington, DC, March.

- Coltrin, M. E., C. C. Willan, and M. E. Bartram. 2000. "Crystal Growth Kinetics and Transport in GaN Epitaxial Overgrowth." Paper presented to the 47th Annual Meeting of the American Vacuum Society, Boston, MA, October.
- Coltrin, M. E., C. C. Willan, and M. E. Bartram. 2000. "GaN Epitaxial Lateral Overgrowth Kinetics." Paper presented to the American Institute of Chemical Engineers, Los Angeles, CA, November.
- Creighton, J. R. 2001. "Low-Temperature Nitride Precursor Reactions." Paper presented to the 10th Biennial Workshop on Organometallic Vapor Phase Epitaxy, San Diego, CA, 11–15 March.
- Gee, J. M. 2001. "National Security Implications of Solid-State Lighting." *Proc. OIDA Workshop on Solid-State Lighting, CS-MAX* (Boston, MA, 9–11 July).
- Han, J., K. E. Waldrup, and J. J. Figiel. 2000. "Growth and Characterization of AlGaIn/GaN DBR Mirrors for UV Surface-Emitting Devices." Paper presented to the Fall 2000 Meeting of the Materials Research Society, Boston, MA, November.
- Jones, E. D. 2001. "National White Lighting Initiative: What's It All About?" Paper presented to the 31st Winter Colloquium on Physics of Quantum Electronics Conference, Snowbird, UT, January.
- Peake, G. M., A. J. Fischer, J. Han, J. J. Figiel, C. C. Mitchell, and R. M. Biefeld. 2001. "UV LEDs with AlInGaIn/InGaIn and AlGaIn/InGaIn Active Regions Grown by OMVPE." Paper presented to the 10th Biennial Workshop on Organometallic Vapor Phase Epitaxy, San Diego, CA, March.
- Simmons, J. A. 2001. "The Solid-State Lighting Initiative: Synergisms with Office of Science Materials Science Programs." Paper presented to the Energy Materials Coordinating Committee, Washington, DC, March.
- Willan, C. C., M. E. Coltrin, and J. Han. 2000. "Mass Transport Processes in the Epitaxial Lateral Overgrowth of Gallium Nitride." Paper presented to the Fall 2000 Meeting of the Materials Research Society, Boston, MA, November.
- Wright, A. F. 2001. "Interaction of Hydrogen with Gallium Vacancies and Nitrogen Interstitials in Wurtzite GaN." Paper presented to the 4th International Conference on Nitride Semiconductors, Denver, CO, 16–20 July.
- Wright, A. F., and S. M. Myers, Jr. 2001. "Modeling of Hydrogen Behavior in Wurtzite GaN." Paper presented to the New Mexico American Vacuum Society Meeting, Albuquerque, NM, 23–24 May.

28776

Interfacial Bioscience Grand Challenge (IBIG)

J. S. Schoeniger, M. J. Stevens, R. C. Hughes, A. R. Burns, M. M. Young, S. M. Brozik, A. K. Singh, D. Y. Sasaki, M. D. Rintoul, R. Behrens, Jr., G. H. Kruppa, M. Z. Hadi, J. M. Faulon, S. A. Datwyler, J. Hong, R. B. Jacobsen, A. M. Highley, A. Slepoy

Molecular interactions in the membrane are critical to the action of known biological and chemical warfare (BW/CW) agents and are thus central to the development of new detection approaches and drugs to block these agents. Although a third of proteins in the genome are membrane proteins, existing techniques can rarely determine their structure. The development of techniques to analyze membrane-protein structure and molecular interactions in the membrane stands out as having major implications for national security-related biotechnology programs. The scientific goal of the Interfacial Bioscience Grand Challenge (IBIG) is to have a major impact on—and to develop unique experimental and computational capabilities for—the understanding of membrane-protein structure and dynamics of membrane-protein structural changes related to toxin action and cell signaling. To reach this goal, the IBIG challenge will integrate a core of technologies that can provide structural and functional information about membrane systems at the molecular level. The core technologies include (1) new methods for protein structure determination using cross-linking and mass spectrometry (MS), (2) a suite of novel scanning-probe microscopies (SPM) combined with single-molecule biophysical measurements, and (3) development of state-of-the-art membrane-protein simulation capabilities using massively parallel (MP) computers.

The project is divided into three technical areas: (1) structure, (2) simulation, and (3) imaging. The goals of these cores are as follows:

(1) The structure core uses a new method called *MS3D* for elucidating membrane-protein structures, protein-protein interactions, and protein-conformational changes at an atomistic level. *MS3D* involves the specific chemical cross-linking of small amounts of target proteins, followed by high-resolution, high-sensitivity MS to extract interatomic-distance information.

(2) The image core uses Sandia's strength in SPM to examine protein structure, function mobility, dynamics, and

... the IBIG challenge will integrate a core of technologies that can provide structural and functional information about membrane systems at the molecular level. The core technologies include (1) new methods for protein structure determination using cross-linking and mass spectrometry (MS), (2) a suite of novel scanning-probe microscopies (SPM) combined with single-molecule biophysical measurements, and (3) development of state-of-the-art membrane-protein simulation capabilities using massively parallel (MP) computers.

interactions in the membrane at the single-molecule level. Established Sandia capabilities include atomic-force microscopy (AFM) and the use of SPM to measure molecular forces. Because SPM requires planar samples, this technology is well suited to studying membrane proteins, and a well-established body of related scientific work exists. Sandia has begun to develop new instruments allowing simultaneous use of AFM and single-molecule spectroscopy or electrochemistry.

(3) The simulation core involves using MP computers and unique parallel codes to understand molecular dynamics of membrane systems and protein modeling.

... this technology is well suited to studying membrane proteins, and a well-established body of related scientific work exists. Sandia has begun to develop new instruments allowing simultaneous use of AFM and single-molecule spectroscopy or electrochemistry.

Materials Science and Technology

The Materials Science and Technology (MS&T) investment area researches materials that behave in a predictable manner during all phases of their life cycle. Research investigations focus on advancing Sandia's commitment to microsystems; these microsystems will utilize optical, electromechanical, magnetic, and chemical functions to sense, think, act, and communicate. Research efforts also support the revolution in nanoscale science and technology; this research offers the opportunity to build tailored materials and structures atom by atom. Technological developments are expected that will rival the impact of the transistor.

The “Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth” project is facilitating the production of tailored nanoscale materials growth. The characteristics seen as the structural dimensions of materials approach the nanometer level are novel phenomena that have the potential to revolutionize science, materials, and next-generation production. Current manufacturing techniques are insufficient to achieve this small scale. As a result, molecular self-assembly has attracted a great deal of interest since this provides a possible spontaneous

mechanism by which nanometer-sized arrays can be formed without mechanical intervention. This work led to graduate research awards from the Materials Research Society and the American Chemical Society.

10300

Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films

A. R. Burns, J. A. Shelnutt, C. J. Brinker, D. Y. Sasaki, S. A. Kemme,
F. B. Van Swol

This project scientifically tailored “smart” interfacial films and three-dimensional (3-D) composite nanostructures to exhibit photochromic responses to specific highly localized chemical and/or mechanical stimuli, self-assembled materials that possess intense and environmentally sensitive optical properties (absorbance, fluorescence), thus enabling their use as detectors of specific stimuli and transducers when interfaced with optical probes. The conjugated polymer polydiacetylene (PDA) proved to be the most promising material in many respects, although it has some drawbacks concerning reversibility.

Throughout this work we used multitask scanning probes (atomic-force microscopy [AFM] and near-field scanning optical microscopy [NSOM]) offering simultaneous optical and interfacial-force capabilities to actuate and characterize the PDA, with localized and specific interactions for detailed characterization of physical mechanisms and parameters. In addition to forming high-quality mono-, bi-, and trilayers of PDA via Langmuir-Blodgett (LB) deposition, we were successful in using the diacetylene monomer precursor as a surfactant that directed the self-assembly of an ordered, mesostructured inorganic host matrix.

Remarkably, the diacetylene was polymerized in the matrix, providing a PDA-silica composite. The inorganic matrix serves as a perm-selective barrier to chemical and biological agents, and provides structural support for improved material durability in microsystems. Our original goal was to use the composite films as a direct interface with microscale devices as optical elements (e.g., intracavity mirrors, diffraction gratings), taking advantage of the very high sensitivity of device performance to real-time dielectric changes in the films. However, we were unsuccessful in these efforts, mainly due to the poor optical quality of the composite films.

We investigated the thermochromic transition of a trilayer PDA film organized into crystalline domains on a silicon substrate. We obtained spectroscopic ellipsometry and

This project scientifically tailored “smart” interfacial films and three-dimensional composite nanostructures to exhibit photochromic responses to specific highly localized chemical and/or mechanical stimuli, self-assembled materials that possess intense and environmentally sensitive optical properties (absorbance, fluorescence), thus enabling their use as detectors of specific stimuli and transducers when interfaced with optical probes.

fluorescence intensity measurements with *in situ* temperature control. PDA films exhibit a reversible thermal transition between the initial blue form and an intermediate “purple” form that exists only at elevated temperatures (303 K to 333 K), followed by an irreversible transition to the red form after annealing above 320 K. We propose that the purple form is thermally distorted blue poly-PCDA (10,12-pentacosadiynoic acid) and may represent a transitional configuration in the irreversible conversion to red. This hypothesis is supported by the appearance of unique features in the absorption spectra for each form, as derived from the ellipsometry measurements.

Significant fluorescence emission occurs only with the red form and is reduced at elevated temperatures while the absorption remains unchanged. Reduced emission is likely related to thermal fluctuations of the hydrocarbon side chains. We have performed time-resolved fluorescence measurements of the irreversible transition. Using a first-order kinetic analysis of these measurements, we deduce an energy barrier of 17.6 plus or minus 1.1 kilocalorie mol⁻¹ between the blue and red forms.

We report the self-assembly of conjugated polymer/silica nanocomposite films with hexagonal, cubic, or lamellar mesoscopic order, using polymerizable amphiphilic diacetylene molecules as both structure-directing agents and monomers. The self-assembly procedure is rapid and incorporates the organic monomers uniformly within a highly ordered, inorganic environment. Polymerization results in PDA/silica nanocomposites that are optically transparent and mechanically robust. Compared to the corresponding ordered diacetylene-containing films prepared as Langmuir monolayers or by LB deposition, the nanostructured inorganic host alters the diacetylene polymerization behavior, and the resulting nanocomposite exhibits unique thermo-, mechano-, and solvatochromic properties. We believe self-assembly to be an efficient general approach to the formation of conjugated polymer/inorganic nanocomposites, wherein the inorganic framework serves to protect, stabilize, and orient the polymer, mediate its performance, and provide sufficient mechanical integrity to enable integration into devices and microsystems.

Due to poor film quality of the PDA/silica nanocomposites and background fluorescence in LB films, progress was limited in implementing PDA films as sensors in microoptical systems. The observation that the blue form does not fluoresce, whereas the red form does, enhances the optical sensitivity of the films as they undergo the blue-red phase

We report the self-assembly of conjugated polymer/silica nanocomposite films with hexagonal, cubic, or lamellar mesoscopic order, using polymerizable amphiphilic diacetylene molecules as both structure-directing agents and monomers.

transformation in response to external perturbations. Thus, our goal was to quantitatively determine the dynamic range of fluorescence as the films underwent the transformation. Starting with blue-phase films, we patterned red-phase regions with a 10-minute deep-ultraviolet (DUV) exposure through a photomask. We were surprised to discover that with 1 mW, 488 nm excitation, the excitation itself had a strong effect on the blue regions: a five-minute exposure increased the fluorescence intensity by a factor of approximately eight. Red-phase regions were unaffected by laser exposure. Since the blue-red conversion occurs thermally at greater than 60°C, we do not think this effect is due to laser heating. However, our results suggest that care must be taken to use very low powers or short exposure times in any fluorescence-based sensor using these films. When we excited the films for short exposure times (10 sec), there was no detectable change in the fluorescence of the blue-phase film with multiple exposures. Under these conditions, the red-phase regions had only a 28-times increase in fluorescence intensity over the blue phase. This is a poor dynamic range and suggests that during initial polymerization, some red-phase regions were created, thereby giving the “blue” film a significant amount of fluorescence.

... our goal was to quantitatively determine the dynamic range of fluorescence as the films underwent the transformation. ... We were surprised to discover that with 1 mW, 488 nm excitation, the excitation itself had a strong effect on the blue regions: a five-minute exposure increased the fluorescence intensity by a factor of approximately eight.

Refereed

Burns, A. R., R. W. Carpick, D. Y. Sasaki, J. A. Shelnutt, and R. Haddad. 2001. “Shear-Induced Mechanochromism in Polydiacetylene Monolayers.” *Tribology Lett.* **10** (March): 89–96.

Lu, Y., Y. Yang, A. Sellinger, M. Lu, J. Huang, H. Fan, R. Haddad, G. Lopez, A. R. Burns, D. Y. Sasaki, J. A. Shelnutt, and C. J. Brinker. 2001. “Self-Assembly of Mesoscopically Ordered Chromatic Polydiacetylene/Silica Nanocomposites.” *Nature* **410** (19 April): 913–917.

10301

Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments

F. D. Wall, N. A. Missert, C. C. Battaile

Reducing the size scale at which we measure and understand corrosion-based degradation pathways is of primary importance to scientific stewardship of the enduring stockpile. Central to this goal is to understand atmospheric degradation of aluminum (Al)-based alloys. Galvanic interactions play a primary role in atmospheric degradation of (1) Al alloys due to electrochemically active second-phase particles and (2) high-purity Al used in microelectronics due to intimate contact with more noble metals (i.e., gold [Au] bondpads). A mechanistic understanding of the atmospheric electrochemical failure modes requires a precise spatial description of potential and current within a corroding system. Measuring the potential field and resulting current map on a small-length scale in an adsorbed electrolyte is not possible using conventional electrodes and measurement techniques. Atmospheric electrochemical sensors must be coplanar and physically oriented to reduce intersensor path lengths while providing sufficient surface area for quantification of the corrosion processes. Sandia has taken a two-pronged approach to developing adequate electrodes. The first relies on our expertise in nanoengineering techniques and yields thin-film electrodes. The second uses more traditional components such as thin-metal foils and small-diameter wires.

To measure the adsorbed environment independent of the interfacial response of a metal electrode, it was necessary to use inert materials and to design an electrode that exhibits minimum parasitic capacitance. We used a combination of lithographic techniques and careful sample design and surface finishing to produce an electrode consisting of two parallel Au traces. We fabricated the traces to have a long edge length to maximize the signal, but a low cross-sectional area to minimize interelectrode capacitance. We used electrochemical impedance spectroscopy (EIS) to determine the frequency response of the electrode as a function of relative humidity (RH) from 1.5 percent to 85 percent RH. The data indicate the ability to quantify the resistivity of the system at all measured RH values. Solution resistance values extracted from the raw

Reducing the size scale at which we measure and understand corrosion-based degradation pathways is of primary importance to scientific stewardship of the enduring stockpile. Central to this goal is to understand atmospheric degradation of aluminum (Al)-based alloys. ... Sandia has taken a two-pronged approach to developing adequate electrodes.

data indicate S-curve-type behavior as a function of RH. These data demonstrate the ability to detect a critical RH for enhanced electrochemical conductance; in this case, the critical RH is approximately 30 percent.

We fabricated metal-foil electrodes and combination metal-foil/metal-wire electrodes from Al and copper (Cu) to measure the corrosion behavior of Al and galvanic corrosion behavior of Al-Cu couples as a function of RH and contaminant level. The galvanic couple experiments proved to be extremely sensitive to minute currents flowing between the Cu and the Al. Quantitative measurements of corrosion current were made as a function of RH in the presence of 20 parts per billion chlorine gas. The data clearly discriminate the system behavior from 0 percent RH to 80 percent RH and indicate a critical RH of 50 percent. Furthermore, the galvanic experiment is extremely sensitive to localized degradation. We also fabricated sensors using Al for both electrodes, either two parallel foils or a parallel foil and wire combination. We used both sensors to determine the ability to intentionally perturb the system and measure localized breakdown. We found that imposing a current and measuring the potential response provided a sensitive means of detecting breakdown. Transients in the potential trace correspond to oxide rupture and repassivation. We found that the wire microelectrodes (25 μ diameter) required either a much higher driving force or a longer induction time for breakdown to occur when compared to the much-larger foil electrodes. This result supports a statistical description for breakdown on small features under atmospheric conditions (e.g., microelectronics failures).

Our results demonstrate that electrochemical measurements are a viable means of making quantitative, *in situ* measurements under mildly accelerating atmospheric conditions. Based on the current work, it will be possible to implement *in situ* monitoring in atmospheric studies, better characterize the conditions leading to accelerated damage, and provide insight into the mechanisms of degradation. Furthermore, the sensor technology that we have developed provides a stepping-stone for the design of early-warning corrosion sensors.

Our results demonstrate that electrochemical measurements are a viable means of making quantitative, in situ measurements under mildly accelerating atmospheric conditions. Based on the current work, it will be possible to implement in situ monitoring in atmospheric studies, better characterize the conditions leading to accelerated damage, and provide insight into the mechanisms of degradation. Furthermore, the sensor technology that we have developed provides a stepping-stone for the design of early-warning corrosion sensors.

Refereed

Wall, F. D. 2001. "The Study of Small Length-Scale Corrosion Processes Using Microelectrodes." (Invited) Paper to be presented to the Gordon Conference on Electrochemistry (January 2002).

Other Communications

Wall, F. D., and M. A. Martinez. 2001. "Quantifying Atmospheric Corrosion Using Stacked Foil Electrodes." Paper presented to the Meeting of the Electrochemical Society, Washington, DC, 25 March.

10302

Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS

M. T. Dugger, M. J. Stevens, D. Y. Sasaki, G. S. Grest

Control of friction and wear between moving, contacting parts of micromachines is necessary to advance their performance and lifetime. Current surface treatments that reduce adhesion to improve fabrication yield use covalently bound self-assembling monolayers (SAMs) of short linear molecules. These films are prone to progressive and irreversible damage under shear force during device operation, due to chemical cleavage from the surface or in the molecular chain.

A small team of experts in tribology, chemistry, nanoscale probes, and molecular dynamics (MD) simulation has attempted to develop a new class of SAM lubricants for micromachines. These lubricants would offer self-healing properties from damage incurred during machine operation, and a built-in mechanism to release shear energy through reversible chemical cleavage.

One example of such a lubricant is a self-organizing liquid crystalline (LC) material with built-in functionality for strong surface attraction to maintain a uniform surface coverage, and a lamellar structure that will absorb friction forces between the noncovalently interacting layers. Sandia has used both new and existing advanced scanning probe techniques to study nanoscale adhesion, friction, and structural properties of the films and the kinetics of damage repair. We used existing specially designed micromachines with isolated tribological contacts to quantify friction and wear performance for microsystem applications. We advanced MD simulation methods to study the effect of molecular structure and defects on shear properties at the interface.

Synthesis and performance investigations focused on two candidate materials developed earlier in this project. Amphiphile synthesis focused on double-tail molecules that exhibit thermotropic LC behavior. We have demonstrated spreading of these molecules on flat surfaces. Low-surface-energy, nonfunctional perfluorinated polyethers do not form ordered molecular structures, but do show good lubricating behavior. These films were deposited on silicon and found to form conformal coatings. A detailed characterization of the

... both new and existing advanced scanning probe techniques to study nanoscale adhesion, friction, and structural properties of the films and the kinetics of damage repair. We used existing specially designed micromachines with isolated tribological contacts to quantify friction and wear performance for microsystem applications. We advanced MD simulation methods to study the effect of molecular structure and defects on shear properties at the interface.

friction of the amphiphiles and perfluoropolyethers using pin-on-disk and scanning probe methods showed a friction coefficient below 0.2 on flat surfaces. A detailed examination of these lubricants in actual microelectromechanical systems (MEMS) structures showed that only the perfluoropolyether-lubricated devices exhibited low friction in the actual MEMS structure.

By starting with a disordered system and determining whether the system would reassemble, we assessed the ability of amphiphile systems to reassemble in MD simulations. Results show that insufficient density leads to defects in the surface lamellae. The ideal system would spread to cover as much surface as possible. We investigated hyperbranched film behavior by constructing a polymer network with a gradient of branches.

A detailed examination of these lubricants in actual microelectromechanical systems (MEMS) structures showed that only the perfluoropolyether-lubricated devices exhibited low friction in the actual MEMS structure.

Refereed

Dugger, M. T. 2001. "Microtribology and Microelectromechanical Systems (MEMS)." (Invited) Paper presented to the STLE 2001 Annual Meeting, Orlando, FL, 20 June.

Dugger, M. T. 2001. "Quantification of Friction in Microsystem Contacts." Chapter in book *Nanotribology: Critical Assessment and Research Needs* (Klewer), accepted.

Dugger, M. T., and S. V. Prasad. 2000. "Surface Treatments for Microsystems: Coating Issues and Tribological Measurement Methods." Paper presented to the Fall 2001 Meeting of the Materials Research Society, Boston, MA, 26 November.

Garcia, C. R., R. J. Salzbrenner, M. T. Dugger, and T. E. Buchheit. 2001. "Behavior and Reliability of MEMS Through Tensile Testing and Friction and Wear Testing." Paper presented to the 6th Annual Student Symposium, Albuquerque, NM, 9 August.

Lemieux, C. M., R. J. Salzbrenner, and M. T. Dugger. 2001. "Friction Behavior of OTS Monolayers Upon Interaction with Scanning Probe." Paper presented to the 6th Annual Student Symposium, Albuquerque, NM, 9 August.

Other Communications

Dugger, M. T., T. E. Buchheit, and S. V. Prasad. 2001. "Tribology and Mechanics of Microsystem Materials." Briefing on Tribology and Mechanics Capabilities to DARPA, Albuquerque, NM, 15 June.

10303

Linking Atomistic Computations with Phase-Field Modeling

J. J. Hoyt, F. M. Hosking, V. Tikare

The phase-field model (PFM) has proven to be a very powerful tool for modeling microstructural evolution during complex materials-processing techniques. Although the method can be used to study grain growth and particle coarsening, the PFM is particularly effective in predicting dendrite formation and solute redistribution during solidification and is therefore very useful in the numerical modeling of joining operations—welding, soldering, and brazing. To date, most of the work utilizing the phase-field concept has focused on the development of the numerical technique and the study of generic microstructures; microstructure modeling applied to specific alloy systems has been rare. The lack of direct comparison between model predictions and actual microstructures in real alloys stems from the fact that many materials parameters—mobilities, free energies, surface energies, gradient energy coefficients, etc.—are required as input in the PFM, and often these parameters are difficult to obtain experimentally. Sandia's purpose in this project is to employ atomistic calculations to obtain numerical values of all parameters necessary to model microstructural evolution.

The microscopic solvability theory of dendritic solidification demonstrates that anisotropy in the solid-liquid interfacial free energy and/or the kinetic coefficient, although very small, determines the shape and velocity of dendrites that form during solidification of a supercooled pure material or a supersaturated alloy. We succeeded in developing a molecular dynamics (MD) technique capable of resolving the small anisotropy in the interfacial energy and applied the technique to copper (Cu), nickel (Ni), gold (Au), silver (Ag), and lead (Pb). Our method is based on monitoring the fluctuations in the position of the solid-liquid interface during an MD simulation.

The kinetic coefficient is the proportionality constant between the velocity of a planar solidifying interface and the undercooling. We developed a free-solidification MD technique that measures the solid-liquid boundary position as a function of time as the entire system is held at some

Sandia's purpose in this project is to employ atomistic calculations to obtain numerical values of all parameters necessary to model microstructural evolution.

specified temperature below the melting point. The resulting velocity versus undercooling behavior yields directly the kinetic coefficient. We applied the free-solidification results to the 100, 110, and 111, and find an anisotropy between 100/110 of 17 percent, a value that is about an order of magnitude larger than the anisotropy in interfacial energy. In addition, we compared the temperature dependence of the solidification rate for all the elements studied to the model due to Broughton, Gilmer, and Jackson, and found quite good agreement for the case of 100 and 110. Experimental verification of our MD approach was achieved in a recent study. Using the values of anisotropies computed in our study, Bragard, *et al.*, performed phase-field calculations of dendrite growth in Ni. With no adjustable parameters, the results showed very good agreement with experiment for the dendrite-tip velocity versus undercooling data.

We are extending the atomistic simulation techniques to the case of binary alloys. We combined Monte Carlo techniques with thermodynamic integration methods to compute the bulk concentrations and densities for the solid and liquid phases in two-phase equilibrium in the Cu-Ni system. The equilibrium properties allow for the equilibration of a solid-liquid simulation cell. We computed the density profiles across the solid-liquid boundary and the Gibbsian adsorption of Cu relative to Ni for the 100 and 111 orientations.

With no adjustable parameters, the results showed very good agreement with experiments for the dendrite-tip velocity versus undercooling data.

Refereed

Hoyt, J. J., M. Asta, and A. Karma. 2001. "Method for Computing the Anisotropy of the Solid-Liquid Interfacial Free Energy." *Physical Review Lett.* **86**: 5530–5533.

10304

A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms

J. C. Barbour, J. W. Braithwaite, K. R. Zavadil, J. P. Sullivan, A. F. Wright, W. G. Breiland, N. A. Missert, M. J. Campin

A physics-based understanding of atmospheric corrosion is an important aspect in developing the capability to predict stockpile reliability. Corrosion modeling is hindered by limited knowledge of primary mechanisms and large numbers of coupled chemical reactions, which depend on complex interactions of materials with environment and functionality. This multidimensional problem requires fundamentally new experimental approaches that can provide timely quantitative information on critical phenomena occurring in corrosion-phase space.

Sandia is combining parallel miniature experimentation with ultrasensitive microanalytical techniques to efficiently explore this phase space and to identify mechanisms and kinetics for copper (Cu) sulfidation in the Microdomain Laboratory. This approach differs from convention by focusing on microscopic-length scales, the relevant scale for corrosion. Combinatorial experiments (arrays of microlabs) will quantify the direct and synergistic effects of morphological and metallurgical variables (e.g., alloying, defect density in the Cu oxide [CuO] and bulk, diffusivities, porosity), environmental variables (e.g., sulfur [S] content in air, light exposure, water-droplet size, distribution versus humidity), and functionality (e.g., electric current conduction). Novel diagnostics include conductivity microsensors to locally quantify pH, pO_2 , and pH_2S , in situ electrical conductivity, light scattering to monitor real-time evolution of corrosion reactions, local ion-selective potentiometric monitoring of reaction products, and, ultimately, microcalorimetry sensors. This project enables a new and rapid approach to determine physical models for complex chemical processes of key importance to Department of Energy technology needs.

This project enables a new and rapid approach to determine physical models for complex chemical processes of key importance to Department of Energy technology needs.

Our accomplishments include (1) the measurement of sulfidation activation energies as a function of relative humidity (RH), (2) the discovery of the effect that light enhances the sulfidation rate, (3) the identification of longer sulfidation induction times at lower humidities, (4) the

implementation of *in situ* optical measurements of sulfidation, and (5) the transmission electron microscopy (TEM) analysis of the sulfide-layer microstructure.

The sulfidation activation energies gave clues to the different primary growth mechanisms at low and high RH. For thicker sulfide layers (beyond about 150 nm) at high RH, the growth mechanism is limited by solid-state diffusion as evidenced by the square root of time dependence for the thickness. The initial sulfide layer at low RH grew linearly with time and an activation energy between 0.03 eV and 0.18 eV. This behavior is consistent with gas-phase diffusion-limited growth. The activation energy at low RH was 0.34 eV, which is consistent with mixed kinetic mechanisms of surface-reaction-limited, solid-state transport-limited, or gas-phase transport-limited growth. Furthermore, the sulfide layer thickness grew linearly with time, out to thicknesses of many micrometers, and never showed a transition to square root of time dependence (as in the high-RH case). The discovery that light could speed the sulfidation of our samples in the linear time-dependence regime indicated that increased electron-hole generation sped the reactions involved to form the sulfide layer. Copper sulfide (Cu_2S) is a *p*-type semiconductor, and, therefore, the generation of excess electrons enhances the sulfidation rate.

Finally, TEM of cross-sectioned samples demonstrated the primary difference in microstructure between the low- and high-RH sulfide layers. At high RH, the initial grains formed were small (about 2 nm–5 nm in diameter), and then larger grains grew (about 100 nm wide) when the sample transitioned from the linear growth regime to the square root of time-growth regime. At low RH, the initial grains were typically large (about 100 nm) and remained large throughout the sulfidation.

... the sulfide layer thickness grew linearly with time, out to thicknesses of many micrometers, and never showed a transition to square root of time dependence (as in the high-RH case). The discovery that light could speed the sulfidation of our samples in the linear time-dependence regime indicated that increased electron-hole generation sped the reactions involved to form the sulfide layer.

Other Communications

Barbour, J. C., J. W. Braithwaite, M. J. Campin, A. F. Wright, W. G. Breiland, N. A. Missert, J. P. Sullivan, K. R. Zavadil, and J. G. Zhu. 2001. "Evaluation of Mechanisms for Atmospheric Sulfidation of Copper." Paper presented to the Spring 2001 Materials Research Society Meeting, San Francisco, CA, 16–20 April.

10305

Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth

A. K. Schmid, N. C. Bartelt, P. J. Feibelman, N. A. Missert, R. Q. Hwang, K. R. Zavadil, M. E. Bartram, C. J. Brinker

Novel, exciting phenomena that have the potential to revolutionize science, materials, and next-generation production methods are manifested as structural dimensions approach the nanometer level. However, advances in lithography are insufficient to achieve this feature scale. As a result, molecular self-assembly has attracted a great deal of interest since it provides a possible spontaneous mechanism by which nanometer-sized arrays can be formed without mechanical intervention. Although these “low-tech” processes are highly dependent on system/material specifics, Sandia proposes that new techniques and the underlying science can be developed in a manner that extends the natural order of self-assembling systems. Our approach is based on previous work in which we fabricated templates of unprecedented size and regularity. These templates will then be applied to form nanoarrays based on a wide range of materials with tunable properties and nanoscale selective-area overgrowth patterns for improving the materials quality of thin films.

Sandia proposes that new techniques and the underlying science can be developed in a manner that extends the natural order of self-assembling systems. Our approach is based on previous work in which we fabricated templates of unprecedented size and regularity.

We studied the influence of various amphiphilic structure-directing agents (e.g., surfactants, diblock and triblock copolymers) on the size, orientation, and connectivity of pores of the corresponding thin-film mesophases prepared by evaporation-induced self-assembly (EISA). To increase the “transparency” of the films to chemical vapor deposition (CVD) infiltration, we explored the use of polystyrene-polyethylene oxide (PEO-PS-PEO) triblock copolymers as a means to increase the pore size from about 2.5 nm (previously obtained for surfactant-templated films) to about 20 nm. We also employed a soft lithographic procedure, micromolding, in capillaries as a means to spatially define the films on the substrate surface. The idea was that both the mesoscale pore size and macroscale feature sizes could influence the subsequent CVD infiltration step. We also continued to explore the aerosol-assisted self-assembly process as a means to make extremely thin films, again to enhance their transparency.

Initial studies of silicon dioxide (SiO_2) films on sapphire did not produce films with nanosized holes suitable for epitaxial lateral overgrowth (ELO) growth. In lieu of more substrates, we continued to pursue our studies of the kinetics that control ELO, using patterns as small as 1μ . From this work, we obtained facet-dependent growth kinetics for five different crystal faces as a function of temperature and V-III ratio. These studies provide insight into how growth would proceed from templates such as those produced by sol-gel-based SiO_2 .

We investigated the effects of sulfur interactions with copper (Cu) using variable-temperature scanning-tunneling microscopy (STM). We monitored the process of mass transport. We imaged motion of nanoscale features with time resolution that permits the identification of key processes in the assembly of Cu structures.

... we continued to pursue our studies of the kinetics that control ELO, using patterns as small as 1μ . From this work, we obtained facet-dependent growth kinetics for five different crystal faces as a function of temperature and V-III ratio.

Refereed

Fan, H., S. T. Reed, T. Baer, T. R. Schunk, G. P. Lopez, and C. J. Brinker. 2001. "Hierarchically Structured Functional Porous and Composite Mesostuctures Produced by Evaporation-Driven Self-Assembly." *Microporous Mesoporous Materials* **44–45**: 625–637.

10306

Wetting and Spreading Dynamics of Solder and Braze Alloys

G. L. Kellogg, R. Q. Hwang, N. D. Shinn, G. S. Grest, F. M. Hosking, F. G. Yost, E. B. Webb, III, D. R. Jennison, J. J. Stephens, Jr.

This project has two purposes: (1) to develop a scientific understanding of the microscopic processes that control wetting and spreading dynamics in materials systems related to soldering and brazing, and (2) to design improved active-braze alloys by investigating the thermodynamic aspects of reactive wetting of eutectic silver (Ag)-copper (Cu) alloys on ceramic substrates.

The first task exploits new advances in experimental surface techniques and atomistic modeling methods to study wetting and spreading phenomena on length scales that range from angstroms to microns. Sandia uses the unique imaging capabilities of the low-energy electron microscope (LEEM) and scanning-tunneling microscope (STM) to characterize the interfacial region when materials such as lead (Pb) and tin (Sn) are deposited on Cu surfaces. We determine the atomic structure of the surface phases that form and characterize the transitions between phases. We also use LEEM to observe the spreading behavior of small molten droplets on fully characterized metal surfaces. We then use results from these studies to test the validity of atomic potentials being developed to simulate the dynamics of wetting and flow. We currently have accurate, empirical potentials that we are applying in large-scale simulations involving Pb, Cu, and Ag.

In the second task, we are developing new active-metal-braze alloy compositions based on thermodynamic considerations and testing the proposed materials for improved performance. The goal is to achieve strong hermetic seals in the brazing of kovar to alumina.

The two tasks merged with our successful LEEM studies of model alumina oxides grown on NiAl substrates and our investigations of empirical potentials for Sn, vanadium (V), and titanium (Ti). Fundamental investigations of active-braze materials on model alumina surfaces under well-controlled conditions and realistic simulations will provide a science-based approach for the design of improved active-braze materials.

... we are developing new active-metal-braze alloy compositions based on thermodynamic considerations and testing the proposed materials for improved performance. The goal is to achieve strong hermetic seals in the brazing of kovar to alumina.

To investigate the role of Sn in promoting the wetting of Pb on Cu surfaces, we initiated experiments with the LEEM in which Sn was either pre-deposited on the Cu surface or co-deposited with Pb. We found that Sn growth on Cu at elevated temperatures exhibits interesting behavior in itself, with the formation of subsurface dislocation features and diffusion of Sn into the bulk. In the co-deposition studies, we found Sn to have a significant effect on the evolution of Pb self-assembled structures of Pb on Cu(111). The degree of the effect varies from small variations in the temperature at which meta-stable stripes become droplets to the formation of totally new atomic arrangements.

In our simulation studies, we used our previously developed empirical potentials for Pb and Cu to tune the interaction between Cu and Pb so as to reproduce the relative stability of submonolayer surface alloy phases observed in LEEM experiments. This potential permits investigation of Pb drops wetting and spreading on Cu substrates. We also performed a thorough investigation of Ag drops spreading on Cu(100) substrates via atomistic simulation. These are the first such simulations where alloying reactions were permitted to occur during spreading. We examined the structural progression of the interfacial region along with corresponding kinetics. These simulations provide a contrast to spreading in a nonalloying system, Pb on Cu.

In ultrahigh-vacuum experimental studies of metal wetting and flow on oxide surfaces, we deposited Cu and Ag on titanium-dioxide (TiO_2) substrates and studied them with the STM. Rather than growing laterally and covering the substrate (i.e., two-dimensional growth), the Cu and Ag islands grew upward to form islands with high-aspect-ratios. We observed a striking behavior in the dependence of island size and density on metal dose, namely, the metal islands grew to a temperature-dependent size and then essentially stopped growing.

In our studies to develop improved active-braze alloys for kovar-to-alumina seals, we investigated Ag-2 wt.% (silver 2 percent by weight) zirconium (Zr) and Ag-3.4 wt.% (silver 3.4 percent by weight) hafnium (Hf) eutectic alloys. These brazes are more thermodynamically stable and should lead to better wetting and interface coverage than the commercial brazes studied in the past. Experiments showed that not only did the Ag-Zr alloy react and wet more completely, but also that it could be brazed in vacuum as well as in hydrogen. This

In our simulation studies, we used our previously developed empirical potentials for Pb and Cu to tune the interaction between Cu and Pb so as to reproduce the relative stability of submonolayer surface alloy phases observed in LEEM experiments. This potential permits investigation of Pb drops wetting and spreading on Cu substrates. We also performed a thorough investigation of Ag drops spreading on Cu(100) substrates via atomistic simulation. These are the first such simulations where alloying reactions were permitted to occur during spreading.

lends manufacturing flexibility to the Sandia products that may utilize it. Zirconia is well known to be a more stable oxide than alumina at temperatures greater than approximately 1000 K, which is below the brazing temperature. To be prepared for the potential instability of zirconia below 1000 K, we also developed the Ag-Hf alloy. Hafnia is more stable than alumina at all temperatures. We completed reaction thermodynamic calculations for the Zr alloy, but the available thermodynamic data for Hf reactions is extremely scarce. We filed a Technical Advance for these alloys.

We completed reaction thermodynamic calculations for the Zr alloy, but the available thermodynamic data for Hf reactions is extremely scarce. We filed a Technical Advance for these alloys.

Refereed

Kellogg, G. L. 2001. "Direct Observations of Nanoscale Self-Organization on Solid Surfaces." Paper presented to the American Society of Mechanical Engineers (ASME) Annual Meeting, New York, NY, 11–16 November.

Plass, R. A., J. A. Last, N. C. Bartelt, and G. L. Kellogg. 2001. "Self-Assembled Domain Patterns." *Nature* **412** (30 August): 875.

Plass, R. A., N. C. Bartelt, and G. L. Kellogg. 2001. "Dynamic Observations of Nanoscale Self-Assembly on Solid Surfaces." *J. Phys. Condensed Matt., Proc. 7th European Conference on Surface Crystallography and Dynamics* (Leiden, The Netherlands, 26–29 August).

Stephens, J. J., Jr., F. M. Hosking, C. Walker, and F. G. Yost. 2001. "A Study of Zirconium as an Active Element for Brazing." Paper presented to the TMS Annual Meeting, New Orleans, LA, 12 November.

Webb, E. B., III, and G. S. Grest. 2001. "Atomistic Simulations of Wetting and Spreading in Metallic Systems." *Tech. Proc. of the International Conference on Computational Nanotechnology* **89** (Hilton Head Island, SC, 19 March): 1.

Webb, E. B., III, and G. S. Grest. 2001. "Liquid/Vapor Surface Tension of Metals: Embedded Atom Method with Charge Gradient Corrections." *Physical Review Letters* **86** (5 March): 2066–2069.

Yost, F. G. 2000. "Kinetics of Reactive Wetting." *Scripta Materialia* **42** (December): 801.

Other Communications

Kellogg, G. L. 2001. "Wetting and Spreading Dynamics of Solder and Braze Alloys." Presentation to the Sandia Program Review, Albuquerque, NM, 12 July.

Plass, R. A., N. C. Bartelt, and G. L. Kellogg. 2001. "The Evolution of Self-Assembled Domain Structures: Pb on Cu(111)." *Physical Review Lett.*, submitted.

10307

Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms

D. M. Haaland, R. Bernstein, D. K. Melgaard, E. V. Thomas, J. A. Timlin, C. M. Wehlburg, F. W. Koehler, M. H. Van Benthem

Twenty years ago, Sandia developed new quantitative multivariate spectral analysis methods that caused a quantum leap in the capabilities of quantitative spectroscopy over previous univariate methods. By combining the massive amounts of data generated using new commercial two-dimensional (2-D) infrared (IR) imaging spectrometers with the Sandia invention of powerful new hyperspectral information extraction algorithms, we developed the ability to perform quantitative spectroscopy without the need for calibration standards. We can now rapidly obtain 2-D spectral images of aging polymeric and energetic materials (EMs) and directly extract pure-component spectra of all spectrally active chemical species in samples, which include the spectra of degradation products. We improved the methods by employing a fast initial method to estimate better starting points for our iterative techniques. We explored using our prediction-augmented classical least-squares (PACLS) algorithms in the quantitative analysis of hyperspectral images (HSI) without standards. We evaluated our new generalized-augmented classical least-squares methods for their relative improvement over standard classical least-squares methods.

Through this new work, we have directly impacted materials-degradation diagnostics by improving our ability to distinguish multiple aging mechanisms, and by improving IR sensitivity and chemical selectivity. By implementing new equality constraints into the methods and by greatly enhancing the speed of the algorithms, we improved the multivariate-curve-resolution (MCR) algorithms that are the basis of quantitative spectral analysis without standards. The chemical specificity and spatial mapping of IR spectroscopy has allowed us to quantify degradation products of neoprene to help understand degradation mechanisms, kinetics, and diffusion. In our prior work on this project, we met and exceeded our original goals. We greatly enhanced and programmed new proprietary algorithms for improved spectral image analysis on both single-processor personal

Twenty years ago, Sandia developed new quantitative multivariate spectral analysis methods that caused a quantum leap in the capabilities of quantitative spectroscopy over previous univariate methods. ... We can now rapidly obtain 2-D spectral images of aging polymeric and energetic materials (EMs) and directly extract pure-component spectra of all spectrally active chemical species in samples, which include the spectra of degradation products.

computers (PCs) and parallel-processor computers, tested them on various datasets, and demonstrated their impact when applied to the image spectral data from aged materials of importance in the Stockpile Stewardship Program.

Our rapid success at achieving quantitative analysis without standards for real aged samples placed us ahead of our original goals for this project. We investigated the usefulness of adding a SIMPLISMA (Simple-to-Use Interactive Self-Modeling Mixture Analysis) front end on the MCR algorithm. Because MCR performs faster when given good initial estimates in the iteration, and because it is less likely to fall into a local minimum solution, coupling the fast SIMPLISMA with the more flexible MCR algorithm sped up the computation by reducing the numbers of iterations required for convergence in the MCR algorithm.

In an unanticipated advance, we determined how to implement equality constraints into the MCR algorithm using the PACLS method. In the literature, equality constraints in MCR have been implemented incorrectly. We implemented a new method of applying equality constraints for pure-component spectra of chemical species and system artifacts known to be present in the HSIs of a given sample. We also tested new MCR methods with simulated and real HSI data to demonstrate the usefulness of the new methods.

We also developed a series of generalized-augmented classical least-squares algorithms. We submitted two journal papers and two patent applications on the methods. These methods are known as spectral-residual-augmented classical least-squares (SRACLS), scores-augmented classical least-squares (SACLS), and concentration-residual-augmented classical least-squares (CRACLS). All three algorithms are fast and yield prediction accuracy that appears to be as good as or better than our proprietary hybrid algorithm. Therefore, we spent time and effort exploring the properties of these algorithms for HSI analysis. We tested the algorithms with simulated spectral data and found them to perform as well as the hybrid algorithm and the standard partial least-squares algorithm when all added spectral and concentration noise is random. We may expect to find advantages when correlated errors are present, but this correlated error simulation was beyond the scope of this project. The new methods have advantages in speed of updating the models and in interpretation of the pure-component spectral estimates. In addition, we found that we can use repeat-image spectra and

*In an unanticipated advance,
we determined how to
implement equality constraints
into the MCR algorithm using
the PACLS method ...
We implemented a new method
of applying equality
constraints for pure-
component spectra of chemical
species and system artifacts
known to be present in the
HSIs of a given sample.*

the PACLS method to correct for the detrimental effects of correlated noise and nonconstant noise variance in the data. We showed that this new approach outperforms the maximum noise fraction (MNF) transform method developed for satellite HSI analysis. However, we investigated a further extension of this approach in other work and found it to yield even better results than the approach that used PACLS in the HSI analysis.

Finally, we pursued the coupling of spectral and spatial information in the sample during the analysis of HSIs of real samples. We found that the use of scores from the eigenvector analysis of spectral image repeats allows us to correct for the spatial representation of instrumental artifacts.

... we found that we can use repeat-image spectra and the PACLS method to correct for the detrimental effects of correlated noise and nonconstant noise variance in the data.

Refereed

Haaland, D. M., and D. K. Melgaard. 2001. "New Augmented Classical Least-Squares Methods for Improved Quantitative Spectral Analyses." *Vibrational Spectroscopy* (Amsterdam, Netherlands), submitted.

Haaland, D. M., and D. K. Melgaard. 2001. "New Classical Least-Squares/Partial Least-Squares Hybrid Algorithm for Spectral Analyses." *Applied Spectroscopy* **55** (January): 1–8.

Haaland, D. M., and D. K. Melgaard. 2000. "New Prediction-Augmented Classical Least-Squares (PACLS) Methods: Application to Unmodeled Interferants." *Applied Spectroscopy* **54** (September): 1303–1312.

Melgaard, D. K., D. M. Haaland, and C. M. Wehlburg. 2001. "Concentration-Residual-Augmented Classical Least-Squares (CRACLS): A Multivariate Calibration Method with Advantages over Partial Least-Squares." *Applied Spectroscopy* (Manhattan, KS), submitted.

Other Communications

Haaland, D. M., D. K. Melgaard, C. M. Wehlburg, and L. E. Martin. 2001. "Augmented Classical Least-Squares Methods for Improved Quantitative Spectral Analyses." Paper presented to the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, Detroit, MI, 7–12 October.

Haaland, D. M., D. K. Melgaard, C. M. Wehlburg, and L. E. Martin. 2001. "New Extensions of the Prediction-Augmented Classical Least-Squares Method for Quantitative New Infrared Spectral Analyses." Paper presented to the Pittsburgh Conference, New Orleans, LA, 4–9 March.

Haaland, D. M., D. K. Melgaard, F. W. Koehler, C. M. Wehlburg, and L. E. Martin. 2001. "New Augmented Classical Least-Squares Methods for Improved Quantitative Spectral Analyses." Paper presented to the 1st International Conference on Advanced Vibrational Spectroscopy, Turku, Finland, 19–24 August.

Haaland, D. M., F. W. Koehler, and C. M. Wehlburg. 2001. "Improved Multivariate Analysis of Hyperspectral Images with the Use of the Error Covariance." Paper presented to the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, Detroit, MI, 7–12 October.

Haaland, D. M., F. W. Koehler, and M. C. Celina. 2001. "Multivariate Methods Applied to Hyperspectral FT-IR Imaging for Quantitative Analysis." Paper presented to the Society of Photooptical Instrumentation Engineers (SPIE) Bios 2001 Spectral Imaging Conference, San Jose, CA, 20–26 January.

Koehler, F. W., IV, M. C. Celina, and D. M. Haaland. 2001. "Quantitative Analysis Without Standards of EPDM Polymer Degradation Products by FT-IR Spectroscopy." Paper presented to the Eastern Analytical Symposium and Exposition, Atlantic City, NJ, 29 October–3 November.

Melgaard, D. K., D. M. Haaland, C. M. Wehlburg, and L. E. Martin. 2001. "A Comparison of the Augmented Classical Least-Squares Calibration Methods." Paper presented to the Pittsburgh Conference, New Orleans, LA, 4–9 March.

10308

Microscale Shock-Wave Physics Using Photonic Driver Techniques

R. E. Setchell, A. V. Farnsworth, Jr., W. M. Trott

Sandia's goal for this project is to establish a new capability for conducting shock-wave physics experiments at low per-experiment costs through a reduction in experimental length and time scales. Applications would involve either bulk-processed materials with minimal dimensions or microscale materials that can be made only with sample dimensions that are too small for conventional experiments. This new capability, which is based on Sandia's earlier development of laser-driven optical detonators, utilizes the rapid absorption of optical energy from a large, Q-switched, solid-state laser to accelerate a small planar disk of a material of interest (a launch process known as photonic driving). The disk (or "flyer") subsequently impacts another material, generating in both materials shock waves having amplitudes and durations that depend on the properties of the two materials, the impact velocity, and the disk thickness.

Subnanosecond interferometric diagnostics (based on an optically recording velocity interferometry system, or ORVIS) were developed previously to examine the motion and impact of laser-driven flyers. To address a broad range of materials and stress states, photonic driving levels must be scaled up considerably from optical detonator conditions. Higher photonic driving levels, however, require special beam-shaping optics and raise concerns over laser-induced damage in the optics and thermally driven phase transitions in the laser-accelerated materials.

We previously attained the goal of achieving an order-of-magnitude increase over detonator conditions, addressed flyer-fabrication issues, and extended photonic driving levels to two orders of magnitude above optical detonator conditions. We designed and fabricated a diffractive optic to avoid laser-induced breakdown while injecting the laser beam into a large-core optical fiber that spatially homogenized the beam intensity. We imaged the fiber output onto an optical substrate to provide a uniform intensity distribution over the flyer launch surface. We significantly updated a CTH-based hydrocode used previously for optical detonator development and used it to assess design options for flyers and targets. We

Sandia's goal for this project is to establish a new capability for conducting shock-wave physics experiments at low per-experiment costs through a reduction in experimental length and time scales. ... This new capability, which is based on Sandia's earlier development of laser-driven optical detonators, utilizes the rapid absorption of optical energy from a large, Q-switched, solid-state laser to accelerate a small planar disk of a material of interest (a launch process known as photonic driving).

examined different flyer boundary conditions (BCs) experimentally to assess loss mechanisms that could reduce acceleration efficiencies.

Next, we addressed both the practical applications of that initial capability and the extension of photonic driving levels to two orders of magnitude above optical detonator conditions. The applications of interest required significant efforts to fabricate flyer assemblies for studying polycrystalline silicon and to utilize bulk-processed materials in validation experiments. We used a new line-imaging ORVIS system to examine flyer planarity during acceleration. A capability for fast-framing photography was added to a second photonic driver system to qualitatively assess lateral plasma motion and flyer integrity issues. To achieve our goal for photonic driving levels, we designed a new diffractive beam-shaping optic for open-air beam delivery specifically for the lasers used in this project.

Most recently, we evaluated several custom designs of diffractive beam-shaping optics, continued to address sample fabrication issues, and conducted a series of validation experiments on both bulk and thin-film materials with well-established shock properties. We now have achieved the project's most substantial results. To obtain shock Hugoniot properties for a material of interest, "reverse-impact" experiments are necessary in which a disk of this material is laser-accelerated and impacted into a window material having well-established shock properties. By measuring the flyer impact velocity and the subsequent velocity of the impact interface, a direct measurement of a Hugoniot state for the flyer material can be obtained. For material samples that are tens of microns or more in thickness, a single ORVIS streak camera can adequately record both the flyer acceleration history and the subsequent velocity history of the impact interface. We conducted a number of these experiments using 2.5 mm diameter, 0.1 mm thick flyers made from bulk-processed 6061-T6 aluminum (Al), which has been extensively characterized in conventional gun experiments. We measured shock Hugoniot states for axial stresses from 1.9 to 8.6 GPa that agreed with conventional measurements to within 2 percent. These experiments utilized the best of several custom designs of diffractive beam-shaping optics.

For studies of material samples that can only be made in smaller thicknesses, the ORVIS system must be modified to add a faster second-streak camera that records only the impact event. With this modification completed, we conducted thin-

A capability for fast-framing photography was added to a second photonic driver system to qualitatively assess lateral plasma motion and flyer integrity issues. To achieve our goal for photonic driving levels, we designed a new diffractive beam-shaping optic for open-air beam delivery specifically for the lasers used in this project.

film validation experiments by accelerating 12.7 μ thick samples of polyimide bonded to 0.1 mm thick Al flyers. The resulting Hugoniot states were consistent with conventional measurements on thicker samples of this material. Attempts to use this capability on 4 μ thick films of polycrystalline Si were frustrated by difficulties in fabricating good-quality films on small metallic flyers. The best films were obtained on 30 μ thick molybdenum (Mo) flyers, but experiments with these assemblies resulted in poor ORVIS records, indicating that the films were not surviving the acceleration process.

We used the modified version of the CTH hydrocode to examine these experimental conditions. This two-dimensional hydrocode had been successful in simulating the results with 6061-T6 Al flyers and had also been used to assess the consequences of nonplanar laser profiles. Simulations of the polysilicon experiments showed excessive thermal transport through the Mo flyer. Although there was insufficient time for an experimental demonstration, the simulations indicated that a 10 μ thick layer of alumina added to the base of the flyer would have minimized this difficulty.

We used the modified version of the CTH hydrocode to examine these experimental conditions.

Other Communications

Farnsworth, A. V., R. E. Setchell, and W. M. Trott. 2002. "A Computational Study of Laser-Driven Flyer Plates." *Proc. 12th APS Topical Conference on Shock Compression of Condensed Matter 2001* (Atlanta, GA, 24–29 June 2001).

Trott, W. M., R. E. Setchell, and A. V. Farnsworth. 2002. "Development of Laser-Driven Flyer Techniques for Equation-of-State Studies of Microscale Materials." *Proc. 12th APS Topical Conference on Shock Compression of Condensed Matter 2001* (Atlanta, GA, 24–29 June 2001).

Trott, W. M., R. E. Setchell, J. N. Castaneda, and D. M. Berry. 2001. "Evaluation of a Diffractive Microlens-Array Beam Shaper for Use in Acceleration of Laser-Driven Flyers." *Proc. Society of Photooptical Instrumentation Engineers (SPIE) International Symposium on Optical Science and Technology: Laser Beam Shaping II 4443* (San Diego, CA, 29 July–3 August).

10734

Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis

R. A. Neiser, Jr., E. V. Thomas, R. C. Dykhuizen, F. W. Spencer, D. M. Haaland

The goal of process-based quality is to accept War Reserve (WR) product without inspection. For simple processes, traditional feedback control of process input variables might achieve this goal. However, input-based (upstream) control systems are a major source of Defense Program production problems for complex processes, because it is impractical, if not impossible, to understand and control all of the factors that affect process output. With recent advances in sensor technology, process modeling, intelligent data analysis, and computing power, a broadly applicable next-generation control technology that monitors and controls process output rather than input may now be possible.

Substantial technical challenges must be overcome to realize this goal. For real-time, output-based (downstream) process control, it is necessary to rapidly interpret and correctly respond to large amounts of temporally and spatially varying data, which requires an innovative new approach to data analysis. Highly complex relationships between process inputs and outputs must also be correctly modeled, and cost-effective robust sensors must be developed. In addition, relationships between sensor observations and product microstructure, properties, and performance must be understood and integrated into the control system.

For some complex processes, e.g., thermal spray, a first-generation downstream process controller based on in-flight monitoring and control of the spray plume may be achievable because some of the requisite technology already exists. For example, we already have considerable expertise in state-of-the-art diagnostic sensors and process modeling. To extract needed information from large, rapidly varying, complex data in real time, we will build upon concepts developed for Chem-Lab-on-a-Chip to create a new statistical methodology that combines response surface modeling with multivariate statistical process control (SPC) and a modified simplex search algorithm that incorporates the concept of dynamic annealing.

... we already have considerable expertise in state-of-the-art diagnostic sensors and process modeling. To extract needed information from large, rapidly varying, complex data in real time, we will build upon concepts developed for Chem-Lab-on-a-Chip to create a new statistical methodology that combines response surface modeling with multivariate statistical process control (SPC) and a modified simplex search algorithm that incorporates the concept of dynamic annealing.

The most important work on this project was to continue testing different approaches to feedback controlling particle temperatures and velocities in the thermal spray process. We previously developed and tested a modified simplex search method. While the modified simplex method worked, recent testing revealed that its response time to system drift was not always fast enough and that it could have difficulty converging to an adequate solution in a timely fashion. While it may be possible to improve the temporal performance of the modified simplex, we decided that testing a Jacobian-based proportional-integral-derivative (PID) control scheme offered more potential.

We derived a generalized solution to determine the control vectors (i.e., the Jacobian matrix) to be used for a system in which the number of process inputs is either greater than or equal to the number of process outputs to be optimized. The extra degrees of freedom that exist if the number of inputs exceeds the number of outputs can be used in a number of useful ways; for example, one can choose the set of control vectors that have the shortest length and therefore require the least adjustment of the system to achieve the desired result. The special case of using up to three process inputs (three gas-flow rates) and two process outputs (particle temperature and velocity) was written into a LabView code for controlling a wire-fed flame spray process. In addition to determining the gas control vectors to be used, it was also necessary to determine the P, I, and D constants that provide stable system performance using a traditional Ziegler-Nichols method.

We tested the Jacobian-based PID control scheme extensively on the wire-fed flame spray system using copper wire as the feedstock material and an Accura Spray Sensor from Tecnar to provide real-time particle temperatures and velocities. The results of this testing were very encouraging. The system response time was substantially improved over the simplex search approach. The response time is essentially limited to how quickly the gas flows can be adjusted. In addition, we demonstrated that the new control scheme was readily capable of correcting the two major sources of process drift that have been identified: torch hardware exchanges and improper centering of the wire in the flame.

We tested the Jacobian-based PID control scheme extensively on the wire-fed flame spray system using copper wire as the feedstock material and an Accura Spray Sensor from Tecnar to provide real-time particle temperatures and velocities. The results of this testing were very encouraging. The system response time was substantially improved over the simplex search approach.

As a result of the successful testing of the new control scheme, we decided to transfer this feedback-control approach to the wire flame spray system being used to coat neutron generators at Sandia. The new control scheme should be in use on the production floor soon.

Other Communications

Neiser, R. A., R. C. Dykhuizen, A. J. Mayer, and C. Duncan. 2001. "Controlling the Wire Flame Spray Process." Paper presented to Linking Research to Practice, NSF seminar at SUNY Stony Brook, Stony Brook, NY, August.

Neiser, R. A., R. C. Dykhuizen, F. W. Spencer, and A. J. Mayer. 2001. "Two Methodologies for Controlling Thermal Spray Processes." Paper presented to the International Conference on Metallurgical Coatings/Thin Films, San Diego, CA, May.

Smith, M. F., and R. A. Neiser. 2001. "Kinetic and Thermal Spray Technology at Sandia." Paper presented to the Propulsion Environmental Working Group, Mesa, AZ, February.

10735

Physical Basis for Interfacial Traction-Separation Models

N. R. Moody, M. S. Kent, E. D. Reedy, Jr.

Many weapon components contain interfaces between dissimilar materials where cracks can initiate and cause component failure. In recent years, many researchers in the fracture community have adopted a cohesive zone model for simulating crack propagation based on traction-separation (T-U) relations. Sandia is implementing this model in its Accelerated Strategic Computing Initiative (ASCI) codes. There is, however, one important obstacle to using a cohesive zone modeling approach: at the present time, T-U relations are chosen in an ad hoc manner.

The goal of the present work is to determine a physical basis for mesoscale-level T-U relations. We proposed experiments that would elucidate the dependence of such relations on adhesive and bulk properties. Work will focus on epoxy/solid interfaces, although the approach is applicable to a broad range of materials. Sandwich-layered double-cantilevered beam (SDCB) and free-surface film nanoindentation fracture toughness tests will generate a unique set of data spanning length scales, applied mode mixities, and yield (plastic) zone constraint. We will define the crucial roles of crack-tip plastic zone size and interfacial adhesion by varying epoxy-layer thickness and using coupling agents or special self-assembled monolayers (SAMs) in preparing samples. We are probing the nature of the yield zone in collaborative experiments run at the Advanced Photon Source and will use high-resolution optical methods to measure crack-opening displacements of the SDCB specimens.

This work will provide an understanding of the major mesoscale phenomena governing polymer/solid interfacial fracture and will identify the essential features that must be incorporated in a T-U-based cohesive zone failure model. We believe that models using physically based T-U relations will provide a more accurate and widely applicable description of interface cracking than models using ad hoc relations. Furthermore, these T-U relations will provide an essential tool for using models to tailor interface properties to meet design needs.

The goal of the present work is to determine a physical basis for mesoscale-level T-U relations. ...

This work will provide an understanding of the major mesoscale phenomena governing polymer/solid interfacial fracture and will identify the essential features that must be incorporated in a T-U-based cohesive zone failure model.

We determined mode mixity and constraint effects on interfacial fracture toughness, investigated a potentially viable T-U relationship, and expect to image crack-tip deformation zones soon. In addition, we made good progress on understanding epoxy/solid interactions, design of tensile fracture samples, and the development of techniques to perform crack-growth simulations to assess potential T-U relationships. The combination of nanoindentation and stressed overlayers provided the capability to study mode mixity and constraint effects on interfacial fracture of thin epoxy films.

The first results clearly showed that interfacial fracture toughness decreased with decreasing film thickness and mode mixity. We assessed the ability of a relatively simple, rate-independent T-U relationship to simulate observed behavior. Crack-growth simulations using this relationship showed that there is a dramatic increase in the size of the yield zone and the energy to propagate a crack along an epoxy/metal interface with increasing amounts of shear loading. We made several design iterations of a sample holder for *in situ* x-ray scattering and diffraction of notched polymer samples under load and are in contact with Advanced Photon Source staff to acquire beam time for microfocusing x-ray-scattering experiments. In related tasks, we designed a tensile brazil nut (TBN) sandwich sample to give an 80° variation in applied mode mixity in a specimen with a millimeter-scale epoxy bond. This design provides a substantial advantage over other common types of interfacial fracture samples. We also developed a method for systematically varying interfacial interactions in the TBN specimen, using mixed SAMs. Finally, we developed the ability to sputter-deposit overlayers with controlled thickness and stress levels. The result gives a controlled approach to the study of interfacial fracture processes.

... we designed a tensile brazil nut (TBN) sandwich sample to give an 80° variation in applied mode mixity in a specimen with a millimeter-scale epoxy bond. This design provides a substantial advantage over other common types of interfacial fracture samples. We also developed a method for systematically varying interfacial interactions in the TBN specimen, using mixed SAMs. Finally, we developed the ability to sputter-deposit overlayers with controlled thickness and stress levels. The result gives a controlled approach to the study of interfacial fracture processes.

Other Communications

Kent, M. S., H. Yim, A. Matheson, J. Sorenson, E. D. Reedy, Jr., K. Schubert, and M. Mitchell. 2001. "Use of Self-Assembled Monolayers to Control Interface Bonding in a Model Study of Interfacial Fracture." *Proc. 24th Annual Meeting Adhesion Society* (Williamsburg, VA, February): 300–302.

Moody, N. R., D. F. Bahr, M. S. Kent, J. A. Emerson, and E. D. Reedy, Jr. 2001. "Adhesive Failure of a Thin Epoxy Film on an Aluminized Substrate." *Proc. Fall Meeting Materials Research Society, Fundamentals of Nanoindentation and Nanotribology II* **649** (Boston, MA, November 2000): Q6.3.1–6.

Moody, N. R., D. F. Bahr, M. S. Kent, J. A. Emerson, and E. D. Reedy, Jr. 2001. "Thickness Effects on Adhesion of Epoxy Films." *Proc. 24th Annual Meeting Adhesion Society* (Williamsburg, VA, February): 309–311.

10740

Diagnostics for Joining Solidification/Microstructural Simulations

C. V. Robino, J. A. Brooks, J. R. Michael, A. C. Hall, T. J. Headley

Solidification is an important aspect of welding, brazing, soldering, laser-engineered netshaping (LENS™) fabrication, and casting. For these processes, solidification affects and, in many instances, controls the final microstructure and properties of the product. The current trend toward utilizing large-scale process simulations and materials response models for simulation-based engineering is driving the development of new modeling techniques. However, the effective utilization of these models and simulations is currently limited by a lack of fundamental understanding of the subprocesses and interactions involved.

In this project, Sandia is identifying key physical phenomena in, and expanding and refining our mechanistic descriptions of, solidification in the iron-chromium-nickel (Fe-Cr-Ni) system. This alloy system displays a wide range of behavior, is well known from a thermochemical perspective, is of interest internally and externally, and strongly leverages previous work. The experimental study is coupled to modeling efforts focused on solidification processes in the same alloy system and provides necessary mechanistic descriptions and input data for these models. We developed and will continue to refine new and expanded experimental techniques, particularly those needed for in situ measurement of the kinetic features of the solidification process. This approach identified several unexpected features of the solidification process, including the observation that the solidification front is more dynamic than previously thought, and the observation of a previously unreported orientation relationship between ferrite and austenite.

In previous work, we demonstrated the suitability of high-resolution optical techniques for studying solidification, and our subsequent efforts concentrated on expanding the capabilities of this technique. This expansion focused on four areas:

- (1) Increasing spatial and temporal resolution,
- (2) Improving the observation environment,
- (3) Extracting quantitative information from the video records, and

In this project, Sandia is identifying key physical phenomena in, and expanding and refining our mechanistic descriptions of, solidification in the iron-chromium-nickel (Fe-Cr-Ni) system. This alloy system displays a wide range of behavior, is well known from a thermochemical perspective, is of interest internally and externally, and strongly leverages previous work. The experimental study is coupled to modeling efforts focused on solidification processes in the same alloy system and provides necessary mechanistic descriptions and input data for these models.

(4) Assessing data needs for modeling.

We installed a new high-speed video system with a temporal resolution of 0.05 msec and improved spatial resolution. An additional feature, automated antiblooming, is advantageous in the harsh environment associated with metallic alloy welding and solidification. We also purchased an integrated data-acquisition system that can synchronously collect 16 differential- or 32 single-channel external inputs (e.g., travel stage acceleration, temperature, and arc current) and associate these inputs with individual image frames. We used the camera to observe weld melting and solidification fronts at high spatial and temporal resolution.

Oxide formation during welding hampers our efforts directed at solidification front imaging. We overcame this difficulty by incorporating the imaging system into a glove box workstation. We directed significant effort at extracting quantitative information from the video records. In addition to determination of dendrite arm spacings, we developed algorithms for determination of dynamic quantities. We determined the solid/liquid interface velocity as a function of time for welds in 304L steel. The interface velocity was very dynamic and was even negative under some conditions. The causes for this dynamic behavior may include process features (e.g., travel-speed irregularity or momentum transfer from the arc), or they may be characteristic of thermal/solutal interactions. These causes are under continuing investigation. In any case, the velocity variations result in microstructural variations that can be observed throughout the weld volume. We accomplished measurements of the solid-liquid interface velocity in a gas-tungsten arc (GTA) spot weld, and indicated increasing velocity of the front as the spot solidified. Initial attempts to observe the ferrite/austenite solidification mode change were unsuccessful.

We did not pursue temperature field mapping because of work by others.

In earlier studies we showed that in primary ferrite solidified structures, austenite can either nucleate in the liquid (F/A [ferrite] solidification), or in the solid at Ni-enriched solidification boundaries (ferrite solidification [F solidification]). The different mechanisms led to two basic ferrite morphologies: skeletal and lathy. In the lathy morphology, we identified two orientation relationships: Kurdjumov/Sachs (KS) and Nishiyama/Wasserman (NW). No orientation relationships had previously been reported in the skeletal morphology other than closely aligned [100]

We accomplished measurements of the solid-liquid interface velocity in a gas-tungsten arc (GTA) spot weld, and indicated increasing velocity of the front as the spot solidified.

directions of the two phases along the primary solidification direction. We now have identified a new orientation relationship in skeletal ferrite, of both parallel planes and directions. Unlike the KS and NW orientations, this orientation has never been reported for any ferrite/austenite structures. We observed this structure in both welds and LENSTM processes. In addition, in the LENSTM samples some skeletal-appearing structures were found to exhibit the NW orientation relationship; this, again, is new. We believe with the small solidification size, interface breakdown leading to the lathy structure does not always occur during the transformation of ferrite to austenite, as is commonly observed in conventional weld and cast structures.

These findings provide insight into the complexity of the solidification and solid-state transformations in austenitic stainless alloys. Solidification cracking behavior of stainless-steel alloys is also strongly tied to the mode of solidification. These findings shed further light on the role interfacial energies may play in preventing solidification cracking. These observations are also extremely important in the support of modeling and simulation of solidification processing of stainless-steel alloys.

We now have identified a new orientation relationship in skeletal ferrite, of both parallel planes and directions. Unlike the KS and NW orientations, this orientation has never been reported for any ferrite/austenite structures. We observed this structure in both welds and LENSTM processes.

Refereed

Brooks, J. A., N. Yang, and J. Krafcik. 2001. "Clarification on the Development of Skeletal and Lathy Ferrite Morphologies in Stainless-Steel Welds." *Science and Technology of Welding and Joining*, accepted.

Brooks, J. A., T. J. Headley, and C. V. Robino. 2001. "Microstructure Design for Laser-Deposited 304L Stainless Steel." *Metallurgical Transactions A*, accepted.

Headley, T. J., and J. A. Brooks. 2001. "A New Orientation Relationship Between Ferrite and Austenite Observed in Solidification Structures of Stainless Steels." *Metallurgical Transactions*, accepted.

Other Communications

Brooks, J. A., C. V. Robino, and S. H. Goods. 2000. "Weldability and Properties of a Free Machining Stainless Steel." Paper presented to the IIW Asian Pacific International Congress, Melbourne, Australia, November.

Brooks, J. A., C. V. Robino, and T. J. Headley. 2000. "Microstructure Modeling and Property Prediction in Laser-Engineered Net Shape Structures." Paper presented to the University of Wollongong, Australia, November.

Hall, A. C., C. V. Robino, G. A. Knorovsky, M. Reece, D. O. MacCallum, J. A. Brooks, A. Newman, and J. Krafcik. 2000. "Weld Visualization for Investigation Solidification." Paper presented to IMOG Subgroup Meeting on Joining, Oak Ridge, TN, April.

10741

Effects of Microstructural Variables on the Shock-Wave Response of PZT 95/5

R. E. Setchell, J. A. Voigt, B. A. Tuttle, E. L. Venturini, M. U. Anderson

Sandia has responsibility for the design and production of explosively driven power supplies. These devices utilize shock-wave depoling of the ferroelectric ceramic PZT 95/5 (lead zirconate titanate) to provide a high-voltage output. Production of these devices will change within a few years to PZT 95/5 material prepared using a new "chem prep" process that is still under development. This process will introduce a porous microstructure that is significantly different from that found within most material presently in the stockpile.

Early studies showed that the porous microstructure can have a profound effect on performance. The rate for failures due to high-voltage breakdown at low temperatures is acceptably low only in materials made within a narrow density range through the addition of organic pore formers. More fundamentally, the dielectric and ferroelectric properties of the material and the physics of the phase transformation that governs the depoling process depend on microstructural properties in ways that are not well understood. Consequently, it is not yet apparent how to optimize microstructural features in chem prep material, and microstructural effects cannot be incorporated into current efforts to numerically simulate device operation.

This project represents the first systematic study of the basic physics of microstructural effects on PZT 95/5 electromechanical behavior under shock-loading.

Studies focused on relatively homogeneous microstructures in which the total porosity resulting from the addition of Avicel pore formers was varied. We performed 19 gas-gun experiments on a suite of chem prep materials having densities ranging from 6.98 g/cm³ to 7.65 g/cm³ (0.45 to 4.0 weight percent Avicel, respectively).

A majority of experiments used samples from a particular production-scale lot of chem prep PZT 95/5 powder mixed with 1.8 weight percent of Avicel to yield samples having an average density of 7.33 g/cm³. This density matches that of a particular mixed-oxide batch having a very different

Sandia has responsibility for the design and production of explosively driven power supplies. ...

This project represents the first systematic study of the basic physics of microstructural effects on PZT 95/5 electromechanical behavior under shock-loading.

void morphology (resulting from larger, spherical Lucite pore formers) that has been extensively characterized under the MAVEN Program. We chose experimental conditions to allow current results at this density to be compared directly with previous results from the mixed-oxide material. Shock experiments examined the purely mechanical response of unpoled material and the dynamic depoling of normally poled samples over a range of shock pressures, under both short-circuit and high-field conditions. The peak strain rate experienced by a PZT 95/5 sample during shock-loading was varied by impacting either a sapphire or alumina-filled epoxy disc that preceded the PZT 95/5 sample in a target assembly. The resulting wave transmitted into the PZT sample had a rise time of either a few nanoseconds or several hundred nanoseconds, respectively.

Comparisons with mixed-oxide experiments do not show large differences in wave structure or depoling rates. The corresponding chem prep material appeared to have slightly slower phase-transition kinetics and released slightly less total charge under a given shock-loading condition. Both materials showed depoling rates that were sensitive to the shock risetime, particularly at lower final stresses and higher final fields. Experiments with chem prep samples at lower and higher densities show that the total charge release during shock transit decreases faster than linearly, with decreasing initial density, probably due to local polarization effects that depend on pore morphology.

Reverse-impact experiments (in which an unpoled PZT sample is impacted into a window material) using laser velocity interferometry (VISAR [velocity interferometry system for any reflector]) showed large differences in Hugoniot properties over this density range. Transmitted waveforms in unpoled and poled samples were also recorded over the entire density range using laser velocity interferometry and showed that the threshold stress for the onset of pore collapse decreases very rapidly with initial density. This observation has several significant implications. If the final shock stress is above this threshold, the depoling rate depends only on the threshold stress, not on the final stress. During the operation of an actual power supply, attenuating shock stresses are above this threshold for some fraction of the shock transit through a PZT 95/5 element. The material experiencing pore collapse is subsequently subjected to a rapid unloading in which additional damage (such as fracturing) can occur while still under a high electrical field.

Experiments with chem prep samples at lower and higher densities show that the total charge release during shock transit decreases faster than linearly, with decreasing initial density, probably due to local polarization effects that depend on pore morphology.

Recent experiments confirmed that significant conduction can occur in this damaged material, leading to device failure. The probability of this failure mechanism depends on the extent to which material is subjected to the traumatic pore collapse and unloading process. The lower the initial density of the PZT 95/5 element, the greater the amount of material that will experience pore collapse. This explanation could be the basis for the rapid rise in failure probability observed in power supply applications if densities are lowered below a fairly narrow range.

Of course, remaining to be explained is the rapid rise in failure probability as densities are raised above this range, probably due to a different failure mechanism. This observation underscores the importance of continuing to examine the effects of the porous microstructure on the shock response of PZT 95/5.

*Recent experiments confirmed
that significant conduction can
occur in this damaged
material, leading to device
failure.*

Other Communications

Setchell, R. E., B. A. Tuttle, J. A. Voigt, and E. L. Venturini. 2002. "Effects of Initial Porosity on the Shock Response of Normally Poled PZT 95/5." *Proc. 12th APS Topical Conference on Shock Compression of Condensed Matter—2001* (Atlanta, GA, 24–29 June), in press.

10742

Mechanisms of Dislocation-Grain Boundary Interaction

D. L. Medlin, J. E. Houston, K. J. Gross

Incorporating the localized atomistic and microscopic effects of internal interfaces on materials properties and long-term behavior is a significant challenge for large-scale materials simulations. An improved understanding of the dislocation-grain boundary interactions that ultimately control the interfacial response to strain is critical to improving such models. Such interactions impact many materials phenomena and properties, including slip transmission, boundary migration, recrystallization, and yield strength, and are a critical element in linking atomic structure to continuum behavior. In this project, Sandia seeks to develop an experimentally based understanding of these dislocation-grain boundary interactions.

Our collaborator at Brown University grew and delivered aluminum (Al) bicrystals, and we performed initial structural characterization. We studied the core structure of a dislocation responsible for grain boundary sliding at an Al boundary using a high-resolution transmission electron microscope (TEM) and related these measurements to calculations of the grain boundary dislocation core widths, based on first principles and classical elasticity. Together, the experimental and theoretical results point to a remarkably low energetic barrier for shear in the $[111]$ direction on the interface.

Through *in situ* TEM experiments, we studied the motion of grain boundary dislocations and their interaction with grain boundary facet junctions. Our analysis showed how repulsive elastic interactions drive interfacial dislocation motion as a grain boundary rotates into a low-energy coincidence orientation.

We successfully related our experimental observations of the relaxations at a $[111]/[112]$ interface to atomistic calculations and provided a critical test of a model of grain boundary structure in terms of an array of Shockley partial dislocations (SPDs). Our results have enabled us to generalize the SPD model to describe $[110]$ tilt boundaries over a misorientation range of 50.5° to 109.5° .

We successfully related our experimental observations of the relaxations at a $[111]/[112]$ interface to atomistic calculations and provided a critical test of a model of grain boundary structure in terms of an array of Shockley partial dislocations (SPDs). Our results have enabled us to generalize the SPD model to describe $[110]$ tilt boundaries over a misorientation range of 50.5° to 109.5° .

Refereed

Foiles, S. M., and D. L. Medlin. 2001. "Structure and Climb of $1/3 \langle 111 \rangle$ Twin Dislocations in Aluminum." *Materials Science and Engineering A*, accepted.

Lucadamo, G., and D. L. Medlin. 2001. "Dislocation Emission at Junctions Between Sigma=3 Grain Boundaries in Gold Thin Films." *Acta Materialia*, submitted.

Lucadamo, G., and D. L. Medlin. 2001. "Investigation of the Origin and Dynamics of Grain Boundary Dislocations in Gold Thin Films." Paper presented to the Annual Meeting of the New Mexico Chapter of the American Vacuum Society, Albuquerque, NM, 23–24 May.

Lucadamo, G., and D. L. Medlin. 2001. "The Nucleation of Dislocations and Subsequent Interactions with Faceted Interfaces in Gold Thin Films." Paper presented to the Spring MRS Meeting, Symposium P, Dislocations and Deformation Mechanisms in Thin Films and Small Structures, San Francisco, CA, 16–20 April.

Medlin, D. L. 2001. "*In Situ* TEM Analysis of Facet Motion in Gold Sigma=3 (112) Boundaries." Paper presented to Microscopy and Microanalysis 2001, Long Beach, CA, 5–9 August.

Medlin, D. L., and G. Lucadamo. 2001. "Morphological Evolution of a Fully Faceted Grain Boundary." *Proc. Fall Meeting of the Materials Research Society, Influences of Interface and Dislocation Behavior on Microstructure Evolution* **652** (Boston, MA, November): Y3.4.1–Y3.4.6.

Medlin, D. L., S. M. Foiles, and D. Cohen. 2001. "A Dislocation-Based Description of Grain Boundary Dissociation: Application to a 90-Degree $\langle 110 \rangle$ Tilt Boundary in Gold." *Acta Materialia* **49**(18) (2001): 3687–3695.

Medlin, D. L., S. M. Foiles, and D. Cohen. 2001. "FCC to 9R Reconstruction at a 90-Degree $\langle 110 \rangle$ Tilt Boundary in Gold." Paper presented to the Spring MRS Meeting, Symposium P, Dislocations and Deformation Mechanisms in Thin Films and Small Structures, San Francisco, CA, 16–20 April.

Other Communications

Medlin, D. L. 2001. "Thinking About Grain-Boundary Structure in Terms of Shockley Partial Dislocations." (Invited) Paper presented to the Lawrence Berkeley National Laboratory/National Center for Electron Microscopy, Seminar Series, Berkeley, CA, 19 January.

10754

Functional Materials for Electrochemomechanical Actuation of Microvalves and Micropumps

J. R. McElhanon, L. L. Whinnery, Jr., S. H. Goods, D. A. Chinn

The development of integrated microsystems for Defense Programs applications, chemical sensing, and medical devices is generally recognized to require fast and efficient microactuators that can function as valves and pumps. Conventionally actuated devices can affect the operating characteristics of microsystems and cannot be miniaturized without significant loss of performance. In this project, Sandia will use electrochemomechanical (ECM) functions of conductive polymers as the work-producing unit in microactuators. We will focus on tailoring molecular structure and composition of conductive polymer gels to optimize physical/mechanical response to electrochemical stimulation.

Conductive polymer actuators have significant advantages over other approaches in their ability to produce high force and large displacement using low power. Our polymer gel development will include the design and synthesis of a variety of linear and cross-linked polymer gels. We will develop and implement methods of expansion/contraction and force generated during electrochemical stimulation. We will also measure and optimize hysteresis, reversibility, and lifetime of polymer systems. We will design, build, and test polymer actuator geometry and microelectrodes to optimize microscale performance, including response rate, displacement, force, and lifetime. ECM response (extension, force, rate, and lifetime) of conductive polymer gels will be systematically characterized with respect to applied potential, temperature, and gel electrode geometry.

Our principle goal is to obtain a fundamental understanding of structure/property/response relationships of conductive polymers with respect to the ECM phenomena and to examine the feasibility of using these materials as microactuator devices.

During our initial work on this project, we recognized that the ECM effect (rate, extension, force, and lifetime) is directly related to polymer gel structure. Initially, we focused on a lightly cross-linked poly(octyl)thiophene (POT) gel to

Our principle goal is to obtain a fundamental understanding of structure/property/response relationships of conductive polymers with respect to the ECM phenomena and to examine the feasibility of using these materials as microactuator devices.

provide structural integrity and enhanced long-term stability. Subsequently, a variety of other cross-linked and linear polythiophene gels were synthesized, and we evaluated their ECM effects. Using a more structurally rigid cross-linking agent, we prepared a new networked conductive polymer gel. We found no enhancement in extension properties due to this structural modification. The lack of any substantial difference in extension between these two structurally diverse polymer gels brought into question the necessity of any covalent cross-linking requirement in our gel systems.

To further investigate this question, we prepared two linear polymer gels, POT and poly(hexyl)thiophene (PHT). Extension studies of linear POT yielded an axial dimension change of approximately 1.5 percent. The gel actuator was reversible for the duration of the test (3,000 minutes, 150 cycles) and exhibited no signs of failure or degradation. We tentatively ascribe this robust behavior to the lack of covalent cross-linking in the polymer gel.

We also examined the ECM behavior of commercial POT. We prepared POT pellets in a mechanical press and measured extension properties. The specimen exhibited a 30 percent irreversible increase in axial dimension in the first 160 minutes of the test cycle. After several hours, the sample exhibited reversible behavior with an axial dimension change of approximately 1.3 percent, similar to what we observed with synthesized POT gel. The net axial increase in sample dimension was approximately 1 mm (33 percent). We attribute the initial irreversible dimensional change and net extension to the increased density of the compressed sample. The commercial specimen exhibited no signs of failure or degradation for the duration of the test (3,000 minutes, 150 cycles), as we observed for the synthesized linear POT.

We synthesized linear PHT gel in an analogous fashion to POT synthesis. Extension studies exhibited a reversible 4 to 6 percent increase in axial dimension, which is substantially greater than any material tested to date. Force measurements were conducted with PHT, and we obtained pressures upwards of 6 kPa at full expansion. These pressures are significantly less than the forces generated with cross-linked POT (15 kPa), and may be an advantage of cross-linked gels. However, the PHT gel exhibited a much longer lifetime (2,000 minutes for PHT versus 400 minutes for cross-linked POT) before we observed degradation. We attribute degradation in the force experiments to a combination of chemical and mechanical degradation of the gel. The fact that linear PHT has a longer

We synthesized linear PHT gel in an analogous fashion to POT synthesis. Extension studies exhibited a reversible 4 to 6 percent increase in axial dimension, which is substantially greater than any material tested to date.

reversible lifetime in force generation compared with cross-linked POT is suggestive of mechanical failure in the latter, presumably due to the cross-linked nature of the gel.

Rates of polymer actuation are similar for all polymer gels examined to date (extension and contraction occur over minutes). A study of the effect of electrolyte size on the rate of extension and contraction showed no enhancement to rate of actuation. We anticipated that engineering a well-defined porous morphology throughout the gel structure would lead to faster response times and greater extension and generation of forces. Presently, the gels have a grape-cluster appearance. We prepared a thermally induced phase-separated (TIPS) modified POT gel from commercial materials and obtained a porous, hexagonal-like gel morphology. We observed practically identical rates of actuation for this TIPS-modified gel in comparison to the analogous unmodified gels.

We anticipate that a more uniform electrode geometry will lead to enhancement of rate of actuation. We have begun a preliminary investigation of the effects of uniformly depositing electrodes on the polymer gel surface to enhance the rate of actuation. We deposited the bottoms of cylindrical gel samples with platinum and are currently examining their ECM behavior.

We prepared a thermally induced phase-separated (TIPS) modified POT gel from commercial materials and obtained a porous, hexagonal-like gel morphology.

Refereed

Irvin, D. J., S. H. Goods, and L. L. Whinnery. 2001. "Direct Measurement of Extension and Force in Conductive Polymer Gel Actuators." *Chemistry of Materials* **13**: 1143–1145.

10761

Making the Connection Between Microstructure and Mechanics

E. A. Holm, T. E. Buchheit, G. W. Wellman, C. C. Battaile

The purpose of microstructural control is to optimize materials properties. To that end, Sandia has developed sophisticated and successful computational models of both microstructural evolution and mechanical response. However, there is currently no way to couple these models to quantitatively predict the properties of a given microstructure. This problem arises because current continuum response models, such as finite element (FE), finite volume, or material point methods, do not incorporate a real length scale. Thus, two self-similar polycrystals have identical mechanical properties regardless of grain size, in conflict with theory and observations.

In this project, we take a tiered risk approach to incorporate microstructure and its resultant length scales in mechanical response simulations. Techniques considered include low-risk methods that are likely to work (albeit with shortcomings) as well as higher-payoff, higher-risk methods. Methods studied include a constitutive response model with a local length-scale parameter, a power-law hardening rate gradient near grain boundaries, a local Voce hardening law, strain-gradient polycrystal plasticity, and a subgrain breakup model. These techniques are validated on a variety of systems for which theoretical analyses and/or experimental data exist, including tension and bending experiments on bicrystals and polycrystals. We used the results to generate improved constitutive models that explicitly depend on microstructure and to provide insight into microstructural deformation and failure processes. Because mechanical state drives microstructural evolution, a strain-enhanced grain-growth model is coupled with the mechanical response simulation. The coupled model predicts both properties as a function of microstructure and microstructural development as a function of processing conditions.

Incorporating microstructure into mechanical response simulations benefits Sandia's research, development, and manufacturing missions. Solving this problem will provide a new tool for scientific insight and model development in materials science, engineering science, and process design and control for a variety of internal and external customers.

Local stress distribution during microstructural evolution in polycrystalline copper. Mechanical equilibration is performed by PPFEM with a local Voce hardening law. Microstructural evolution is simulated by a front-tracking model with strain-enhanced evolution. While local stresses evolve quantitatively, their qualitative distribution remains relatively stable despite changes in grain topology.

Stress length scales in polycrystalline copper deformed 40 percent in tension, as simulated by PPFEM with a local Voce hardening law. (a) On the microstructural length scale, critical resolved shear stress within each grain is relatively uniform, but differs from grain to grain. (b) On the subgrain scale, the critical resolved shear stress varies throughout the macroscopically homogeneous grain indicated by an asterisk in (a).

We continued investigating candidate techniques for imparting a length scale into polycrystal plasticity finite-element model (PPFEM) calculations. We first attempted to model dislocation pileup effects with a gradient in power-law hardening rate near grain boundaries. Preferential hardening near boundaries causes strain to be redistributed to the soft interior elements. By 0.1 percent strain, we homogenized the stress across the system. Since these results contradict experiments, we rejected this method as physically incorrect.

Next, we replaced power-law hardening by a saturating Voce hardening function, where the hardness of an element is related to its distance from the grain boundary taken to some exponent. With an exponent of -1, reflecting the boundary surface to volume ratio in a polycrystal, this law reproduces experimental data at many different grain sizes and gives a Hall-Petch exponent near 0.5.

We further developed the Voce hardening model in the JAS-3D FE code. We implemented periodic boundary conditions and tested for and eliminated mesh sensitivity. In a randomly textured polycrystalline copper, a network of load-bearing grains forms. Stress exhibits structure on the microstructure scale and the subgrain scale.

Using the preliminary results of the Voce model simulations, we developed a strain-enhanced microstructural evolution model. Grains are grown for several timesteps, and the microstructure is passed back to the PPFEM simulation for re-equilibration. While the stress in the microstructure changes quantitatively, grains tend to maintain their relative position in the stress distribution during growth, which indicates that grain orientation and position, and not topology, govern the local stresses on a grain.

We examined the strain-gradient plasticity model via literature search and discussions with strain-gradient modelers. We determined that the model suffers from physical and computational intractability for application to polycrystalline microstructures.

We further developed the Voce hardening model in the JAS-3D FE code. ...

Using the preliminary results of the Voce model simulations, we developed a strain-enhanced microstructural evolution model.

Refereed

Battaile, C. C., T. E. Buchheit, G. W. Wellman, M. K. Neilsen, and E. A. Holm. 2001. "Coupled Simulations of Deformation and Grain Growth." *Proc. 4th Pacific Rim International Conference on Advanced Materials and Processing* **1** (Honolulu, HI, December).

Buchheit, T. E., C. C. Bataille, G. W. Wellman, and E. A. Holm. 2001. "Providing a Length Scale by Capturing the Influence of Grain Boundaries in Polycrystal Plasticity Modeling." Paper to be presented to the TMS Annual Meeting, Seattle, WA, February 2002.

Holm, E. A. 2001. "Advances in Modeling Grain Growth and Recrystallization." (Invited) Paper presented to the TMS Fall 2001 Meeting, Indianapolis, IN, November.

Holm, E. A., and C. C. Battaile. 2001. "Computer Simulations of Microstructural Evolution." *JOM* **53**(9) (September): 20–23.

10779

Switchable Hydrophobic-Hydrophilic Surfaces

B. C. Bunker, R. P. Manginell, D. L. Huber, M. S. Kent, J. G. Curro, C. M. Matzke

The objective of this project is to investigate the use of tethered organic coatings as a means of reversibly switching the surface chemistry of components in microanalytical systems. The specific target of the project involves the development of thin films that can be switched between hydrophilic and hydrophobic states, with potential application for controlled pumping of fluids on a chip. The project involves learning how to

(1) Synthesize switchable polymers and attach them to surfaces.

(2) Optimize methods for stimulating desired configuration changes within the tethered polymers.

(3) Develop methods for probing whether desired configuration changes occur and how such changes impact surface chemistry.

(4) Model desired transitions in polymer phases and surface chemistries to aid in polymer and interface optimization.

(5) Develop model microfluidic structures that can be used to evaluate coating performance for microanalytical systems.

Scientific benefits of the project involve obtaining a deeper understanding of surface solvation and what makes surfaces exhibit properties such as hydrophobic or hydrophilic states, and obtaining insights into how polymers interact with solvents such as water, which will impact topics ranging from polymer swelling to protein folding. Technical benefits of the project involve learning how to integrate new "smart" materials and nanostructures into microanalytical systems. One unanticipated discovery in the work performed to date is that the stimulated phase transition can be used to control the adsorption and desorption of proteins and other biomolecules. Such films are now under investigation for bioanalysis and separation systems.

Our accomplishments include the following:

- *Characterization of switching transitions.* Contact-angle measurements indicate that while the swelling transition

The objective of this project is to investigate the use of tethered organic coatings as a means of reversibly switching the surface chemistry of components in microanalytical systems. ...

Scientific benefits of the project involve obtaining a deeper understanding of surface solvation and what makes surfaces exhibit properties such as hydrophobic or hydrophilic states, and obtaining insights into how polymers interact with solvents such as water, which will impact topics ranging from polymer swelling to protein folding.

leads to large changes in the advancing contact angle in water, the receding contact angle is low and insensitive to temperature. The low receding contact angle may undermine the ability of poly n-isopropylacrylamide (PNIPAM) films to drive fluids through microchannels. Work is in progress to address the contact-angle hysteresis problem by investigating alternate tethered polymers such as elastin (a biopolymer) and by using block copolymers that can be stimulated to expose hydrophobic or hydrophilic blocks on demand.

- *Reversible protein adsorption using PNIPAM films.*

Ultraviolet-visible (UV-vis), attenuated total reflectance IR and neutron-scattering experiments show that the hydrophobic-hydrophilic transition in PNIPAM films can be used to control the adsorption and desorption of proteins such as myoglobin for on-chip protein separators and preconcentrators. UV-vis spectra show that proteins do not stick to PNIPAM at room temperature. Above the transition temperature, a monolayer of myoglobin sticks to the PNIPAM. Cooling to room temperature leads to rapid protein desorption. Incorporation of the PNIPAM films into microfluidic devices has shown that protein films can be adsorbed and desorbed in less than 1 sec in response to thermal stimulation.

- *Modeling of solvent-polymer interactions.*

We developed a new integral equation theory of polymer solutions (PRISM [Polymer Reference Interaction Site Model] theory) that explicitly accounts for the presence of solvent molecules. We used the new model and molecular dynamics (MD) simulations to examine polymer phase transitions as a function of polymer concentrations. Both the theory and the MD simulations show that packing of the solvent molecules has significant impact on macromolecular structures and phase transitions in solution. Recently, we compared the models with results obtained in the program using neutron reflectivity measurements to characterize PNIPAM films in water as a function of temperature. For films with a low grafting density, the results show that PNIPAM swells in water, as do bulk gels. However, the swollen film does not collapse above the transition temperature. Films with a higher grafting density do collapse. The extent of the volume change associated with the transition is predicted by the theory, demonstrating that interactions between chains is critical to the transition.

- *Microelectronic devices for switching PNIPAM films.*

We have now fabricated the first set of thermally programmable chips for switching PNIPAM films. The chips achieve thermal control using resistive heating of gold (Au)

We have now fabricated the first set of thermally programmable chips for switching PNIPAM films.

lines deposited on a thermally insulating silicon nitride (SiN) membrane. Temperature is measured via changes in resistance on Au lines not used for heating. We determined the thermal-response characteristics with and without fluids, and we completed the software required to produce thermal pulses. We incorporated PNIPAM films into the fluidic device. We monitored film switching using protein adsorption experiments conducted under a fluorescence microscope. We introduced solutions containing fluorescently tagged myoglobin into the device. Then, we activated single heater lines in the device to trigger the phase transition. Fluorescent images show that proteins stick only to that line that has been activated within a few seconds. When the heater line is turned off, a plume of proteins is observed to desorb from the line within less than 2 sec. Now that the response characteristics of PNIPAM have been demonstrated in the micro-hotplate, we will test PNIPAM and other films for controlling fluid motion via hydrophobic-hydrophilic transitions.

We determined the thermal-response characteristics with and without fluids, and we completed the software required to produce thermal pulses.

Refereed

Ista, L. K., S. Mendez, V. H. Perez-Luna, and G. P. Lopez. 2001. "Synthesis of Poly (N-isopropylacrylamide) on Initiator-Modified Self-Assembled Monolayers." *Langmuir* **17**(9): 2522–2555.

Kushmerick, J. G., H. I. Kim, J. E. Houston, and B. C. Bunker. 2001. "Hydration Forces: The Role of Interphase Water." *Science*, accepted.

Mendez, S., J. G. Curro, M. Puetz, D. Bedrov, and G. D. Smith. 2001. "An Integral Equation Theory of Polymer Solutions: Explicit Treatment of the Solvent." *J. Chemical Physics* **115** (23 September): 5669–5678.

Mendez, S., J. G. Curro, M. Puetz, D. Bedrov, and G. D. Smith. 2001. "Integral Equation Theory for Polymer Solutions: Explicit Treatment of the Solvent." Paper presented to the American Physical Society Meeting, Seattle, WA, March.

Other Communications

Huber, D. L., R. Manginell, C. Matzke, T. Dunbar, J. Kushmerick, and B. Bunker. 2001. "Reversible Adsorption/Desorption of Proteins from a Thermally Switching Monolayer." Paper presented to the American Vacuum Society Conference, San Francisco, CA, October.

Ista, L. K., S. Mendez, S. Balamurugan, and G. P. Lopez. 2001. "Examination of Bacterial and Protein Attachment and Release Using Tunable Poly (N-Isopropylacrylamide) as a Switchable Hydrophobic/Hydrophilic Substratum." Paper presented to the American Vacuum Society Conference, San Francisco, CA, October.

Mendez, S., S. Balamurugan, L. K. Ista, and G. P. Lopez. 2001. "Surface Plasmon Resonance Techniques for *In Situ* Detection of LCST Behavior on Surface-Grafted Polymer Films." Paper presented to the American Vacuum Society Conference, San Francisco, CA, October.

Subramanian, B., J. Yan, and G. P. Lopez. 2001. "Role of Interfacial Water Properties of Oligo(ethylene Glycol) Monolayers." Paper presented to the American Vacuum Society Conference, San Francisco, CA, October.

10780

Nanostructured Materials Integrated in Microfabricated Optical Devices

D. Y. Sasaki, S. M. Brozik, M. E. Warren, M. B. Sinclair, A. R. Burns, S. A. Kemme, C. J. Brinker

This project combines Sandia's emerging strengths in nanocomposite materials with the recognized expertise and processing capabilities involving microfabricated optical device structures for the development of microsensor arrays and unique tunable microoptical devices. The project involves the design, development, and characterization of molecular (nanoscale) to micron-scale structures to achieve desired material and device function. At the core of the material is a liquid crystalline (LC) lipid bilayer that mimics the properties of a biological cell membrane. The bilayer is functionalized with molecular receptors for specific recognition of chemical and biological species, and with optical reporters that signal the occurrence of the recognition event. These molecular and supramolecular structures will be supported on a structurally oriented, mesoporous, inorganic matrix. The matrix offers structural stability and physical protection of the LC materials as well as provides a platform for forming dense LC structures for greater signal output. Together, the materials form a unique nanocomposite with molecularly dynamic organic components for rapid optical response to specific analytes coupled to a robust inorganic scaffold with highly defined and tunable surface area and pore volume.

Integration of the nanocomposites to microfabricated optical devices will occur in two stages. In the first stage, we will couple the materials onto substrate-mode platforms for combinatoric sensing arrays. The second stage will then further the materials integration by forming the material into an optical structure yielding devices that can tune their properties through chemical signaling. Multiple materials and optics issues must be addressed to successfully merge these disparate research areas. Results from this work will make great strides in creating new micron-scale sensing arrays for biopathogens and combinatorial approaches to materials and drug discovery, and also in creating unique microfabricated optical structures with rapid and tunable switching properties.

This project combines Sandia's emerging strengths in nanocomposite materials with the recognized expertise and processing capabilities involving microfabricated optical device structures for the development of microsensor arrays and unique tunable microoptical devices.

We made progress in both sensor materials synthesis and the characterization and development of the optical waveguide structures. The synthesis of optical sensor materials prepared gram quantities of the fluorophore-labeled main lipid structure to be subsequently coupled with selective receptor headgroups (i.e., boronic acids, arginine-glycine-aspartate [RGD] peptides, and saccharides).

We also characterized the sensor materials at the nanoscale using *in situ* atomic-force microscopy (AFM) to interrogate the lipid bilayer surface as chemical recognition events occur. We achieved a resolution of 10 nm, allowing us to visualize the molecular reorganization process that is activated by the recognition process. Sol-gel nanocomposite materials were also under development both with regard to film formation that yields nanostructural order through self-assembly and to surface functionalization of the silica matrix for improved performance of aged materials.

Progress of the optical waveguide structures centered on the development of two structures that we utilized as reusable optical platforms to demonstrate and characterize the optical beam/functionalized film interaction. A two-level grating design would symmetrically reflect light at both plus and minus 45°, each with an efficiency of approximately 45 percent, with a minimum feature size of 0.26 μm . We are currently pursuing the more-aggressive four-level reflective grating to asymmetrically direct the desired direction despite requiring two-mask write and etch fabrication cycles. We successfully fabricated this four-level design at a peak wavelength of 850 nm, demonstrating accurate feature definition and precise mask alignment. Next, we will focus on obtaining exact grating depths and more conformal Au deposition.

We also characterized the sensor materials at the nanoscale using in situ atomic-force microscopy (AFM) to interrogate the lipid bilayer surface as chemical recognition events occur. We achieved a resolution of 10 nm, allowing us to visualize the molecular reorganization process that is activated by the recognition process.

Refereed

Last, J. A., T. A. Waggoner, and D. Y. Sasaki. 2001. "Lipid Membrane Reorganization Induced by Chemical Recognition." *Biophysical Journal*, accepted.

Lu, Y., Y. Yang, A. Sellinger, M. Lu, J. Huang, H. Fan, R. Haddad, G. Lopez, A. R. Burns, D. Y. Sasaki, J. Shelnutt, and C. J. Brinker. 2001. "Self-Assembly of Mesoscopically Ordered Chromatic Polydiacetylene/Silica Nanocomposites." *Nature* **410** (9 April): 913–917.

10789

All-Ceramic Battery

T. J. Boyle, R. T. Cygan, J. A. Voigt, M. A. Rodriguez, D. Ingersoll, K. Rahimian

To achieve autonomy, we require the production of a thin-film all-ceramic battery that has power sources that generate the necessary power and energy to operate microsystems without substantially increasing the size of the device. Thin-film batteries are an attractive power source for these applications; however, they currently are inadequate to operate the microsystems effectively. Sandia seeks to develop a rechargeable thin-film all-ceramic lithium-ion battery (ACB) using solution route deposition methods. The ACB will have higher power output, longer runtimes, and a greatly simplified production scheme in comparison to existing technology. Several ACB prototypes (normal and inverted) have been generated using the above chemistries; however, shorting has complicated the electronic testing. Once sufficiently developed, these ACBs will have the versatility to power any number of small systems, such as microsystems and miniature autonomous robotics.

Sandia seeks to develop a rechargeable thin-film all-ceramic lithium-ion battery (ACB) using solution route deposition methods. ... Once sufficiently developed, these ACBs will have the versatility to power any number of small systems, such as microsystems and miniature autonomous robotics.

The generation of the ACB is proceeding according to plans. Currently, we have developed solution routes to cathode and anode materials. Work is focusing on developing highly lithium (Li)-conducting electrolytes.

- **Substrates.** Initial computational studies verified by select x-ray diffraction (XRD) experiments indicated that the mismatch between the oxide material and the various substrates would be too great to overcome, and a random orientation would result. We selected platinum (Pt) substrates and developed two solution routes to the cathode material (LiCoO_2).

- **Cathode.** We synthesized a series of novel precursors [Li(OR) , $\text{Li}_2\text{Co(OR)}_4$] and characterized them for use in these systems. Once generated, the films were identified by XRD. We observed two types of LiCoO_2 : high Li content and a substantially reduced Li content. We developed protocols for distinguishing LiCoO_2 from Co_3O_4 . The films demonstrated reversibility of Li insertion. We also noted an unusual electronic behavior wherein the thin film of LiCoO_2 demonstrated an anisotropic electronic behavior (conducting in-plane and insulating out-of-plane). We optimized the

processing route by the electrochemical characterization of the thin film in conjunction with XRD. This also led us to an understanding of the structural changes that occurred during cycling.

- *Anode.* We synthesized novel families of tin (Sn) precursors using mono-, bi-, and tri-dentate ligands. The optimal route utilizes an *in situ* hydrolyzed product that was fully characterized and the reaction of which that followed by ^{119}Sn nuclear magnetic resonance (NMR) experiments. We developed two routes utilizing these precursors for the anode, which shows charging capabilities but de-adhesion of the film upon discharge.

- *Electrolyte.* We investigated two types of electrolytes: inorganic ceramic and sol-gel materials. We developed two formulations that could be used as thin-film electrolytes based on sol-gel chemistry. The first was a homogeneous physical mixture of the sol-gel, polyethylene glycol (PEG), and the Li source; the second was a formulation in which the sol-gel and the PEG are covalently bonded. We further identified three Li salts that could be used, within the above-mentioned formulations, as the Li-ion source. We produced high-quality thin films (identified by scanning electron microscopy [SEM]) from these solutions and are currently testing them for their Li-ion behavior. Development of processing protocols for developing more robust films is under way.

The proposed $\text{LiLa}(\text{PO}_3)_3$ materials were centered on the metaphosphate line between LiPO_3 and $\text{La}(\text{PO}_3)_3$. Due to the low room-temperature ionic conductivities (the range is about 2×10^{-9} S/cm for $50\text{Li}_2\text{O} \cdot 50\text{P}_2\text{O}_5$ to about 2×10^{-15} S/cm for $10\text{Li}_2\text{O} \cdot 20\text{La}_2\text{O}_3 \cdot 70\text{P}_2\text{O}_5$), and the fact that the precursors were only soluble in H_3PO_4 , which subsequently dissolved the LiCoO_2 thin film, we investigated alternative materials.

Based on a systematic search of crystallographic databases for fast Li-ion conductors and the results of molecular models built for each candidate phase and evaluated potential for energy calculations, we studied alternative materials as potential electrolytes. We developed routes to these nonsol-gel electrolytes, including (1) two routes to LiLaMO_3 (M equals Ti (LLT) or Zr (LLZ)); (2) b"-aluminates LiM_5O_8 (M equals Al, Fe, Ga); (3) LiSrMO_3 (M equals Ta, Nb); and (4) LiMLaO_3 (M equals Ta, Nb).

We synthesized novel families of tin (Sn) precursors using mono-, bi-, and tri-dentate ligands. The optimal route utilizes an in situ hydrolyzed product that was fully characterized and the reaction of which that followed by ^{119}Sn nuclear magnetic resonance (NMR) experiments. ... We investigated two types of electrolytes: inorganic ceramic and sol-gel materials. We developed two formulations that could be used as thin-film electrolytes based on sol-gel chemistry.

Our main focus was on LLT = (Li,La) TiO₃ and LLZ = (Li, La) ZrO₃ reported in the literature. In an effort to evaluate the effect of composition and defects on Li diffusion at 300 K, we completed a series of molecular dynamics (MD) simulations of these structures. A composition of La 0.75, Li 0.25 provided the optimum transport for Li while ensuring defective and stable perovskite structure. For the LLZ material, we observed the fluorite structure at the processing temperatures that we could utilize for the Pt substrate. Testing of these films indicate high conductivities on the order of about 10 to 8 S/cm. We are investigating alternative substrates that can handle the higher temperatures so that the desired perovskite phase can be formed. For the remainder of the samples generated, we undertook the XRD analyses and MD methods as we did on for the lanthanum (La)-Li perovskite. Electronic testing is awaiting these results.

In an effort to evaluate the effect of composition and defects on Li diffusion at 300 K, we completed a series of molecular dynamics (MD) simulations of these structures. A composition of La 0.75, Li 0.25 provided the optimum transport for Li while ensuring defective and stable perovskite structure.

Refereed

Boyle, T. J., D. M. Pedrotty, T. M. Alam, S. C. Vick, and M. A. Rodriguez. 2000. "Structural Diversity in Lithium Aryloxides: Structurally Characterized [Li(OAr)(THF)_x]_n and [Li(OAr)(py)_x]₂ where OAr = OC₆H₅, OC₆H₄(2-Me), OC₆H₃(2,6-(Me)₂), OC₆H₄(2-Pri), OC₆H₃(2,6-(Pri)₂), OC₆H₄(2-But), OC₆H₃(2,6-(But)₂)." *Inorganic Chemistry* **39**: 5133.

Boyle, T. J., T. M. Alam, K. P. Peters, and M. A. Rodriguez. 2001. "Structural Diversity of Lithium Neopentoxide Compounds." *Inorganic Chemistry* **40**.

26525

Magnetic-Field Effects on Vacuum-Arc Plasmas

P. A. Miller, D. R. Welch, M. M. Hopkins

Sandia is studying magnetic-field effects on vacuum-arc plasmas. Compact neutron tubes employ annular-ion beams to minimize adverse effects from the space charge of ions in the beam. Presently, annular beams are formed by geometrically selecting a fraction of the total output from vacuum-arc-plasma ion sources. In principle, magnetic fields can shape the plasma into an annular shape, thereby increasing source efficiency and reducing electrical-drive requirements; this implies reduced generator size and weight. Moreover, self-magnetic fields of the arc affect the plasma output but are not included in existing models of tubes. We have begun development of diagnostics and codes to understand the field-plasma-arc interaction and to shape the plasma plume. This work is progressing on schedule.

We will continue combination of modeling and experiment. The interaction of plasma and field is a collective phenomenon. Modeling is necessary to understand and exploit our measurements and to design new field configurations to shape the plasma as desired.

If completely successful, this work will improve our understanding of important tube processes by quantifying the arc self-field effects on plasma azimuthal uniformity, and the work will allow Sandia to tailor the spatial distribution of plasma for better utilization and increased margin in tubes.

We developed a Langmuir-probe-array system, including data-acquisition and -analysis codes for conducting the experiment efficiently in the laboratory. We also developed a simple coil system and capacitor bank to provide a uniform axial magnetic field for initial tests. The first dataset showed that a relatively weak magnetic field (< 100 Gauss [G]) influenced (i.e., enhanced) the plasma plume. The plume, however, appears to have spatial and temporal structures that are not simple. Data analysis is in progress, and we will investigate these features further.

We chose to use the Large-Scale Plasma (LSP) code for modeling rather than the ICARUS code as originally proposed. We changed this because development of 3-D capability in ICARUS was suspended by another program,

If completely successful, this work will improve our understanding of important tube processes by quantifying the arc self-field effects on plasma azimuthal uniformity, and the work will allow Sandia to tailor the spatial distribution of plasma for better utilization and increased margin in tubes.

and LSP already has a three-dimensional (3-D) capability. Initial calculations with a 2-D serial version of the LSP code showed that a 500 G axial magnetic field narrowed the plasma plume, in general agreement with the experimental trends. We may perform more scoping runs with the serial version of the code. However, the present magnetic-field solver in LSP is inefficient on parallel computers. Consequently, we changed a milestone: Instead of implementing 3-D capabilities in ICARUS, we are changing the 3-D field solver in LSP to a parallel version.

Initial calculations with a 2-D serial version of the LSP code showed that a 500 G axial magnetic field narrowed the plasma plume, in general agreement with the experimental trends.

26526

Microstructural and Continuum Evolution Modeling of Sintering

V. Tikare, M. V. Braginsky, J. G. Arguello, Jr.

Sandia is studying sintering in weapons components. All ceramics and powder metals are manufactured by sintering. Sintering is a critical—possibly the most important—processing step during ceramics manufacturing. The microstructural evolution, the macroscopic shrinkage, and shape distortions during sintering will control the engineering performance of the resulting ceramic component. Yet, modeling and prediction of sintering behavior is in its infancy, lagging far behind the other manufacturing models, such as powder synthesis and powder-compaction models. Sintering models and prediction also lag behind models that predict engineering properties and reliability.

This project will develop a set of computational tools that enable us to understand, predict, and control microstructural evolution and macroscopic dimensional changes during sintering. Previous research efforts on sintering modeling have failed because the efforts treat some limited aspect of sintering, either on the microstructural- or macroscopic-continuum scale. Microstructural models treat the evolution of two or three powder particles during sintering to give detailed information about particle shapes and densification rates. However, the models fail to treat a macroscopic sintering piece (the shape change, density distribution, stress formation, and other characteristics). Continuum models apply continuum-deformation mechanics to the sintering body to predict shrinkage and component shape change. However, the deformation equations are poorly understood and not directly linked to real material systems, so application of continuum-sintering models to real materials has had limited success.

We propose a novel modeling method to treat the microstructural evolution of thousands of powder particles during sintering and to integrate the results into continuum models that predict the overall shrinkage and shape distortions in a sintering component. An equally important result of this work will be a fundamental advancement in the understanding of sintering science.

Sandia is studying sintering in weapons components. ...

Sintering is a critical—possibly the most important—processing step during ceramics manufacturing. ...

This project will develop a set of computational tools that enable us to understand, predict, and control microstructural evolution and macroscopic dimensional changes during sintering.

We developed a new algorithm to couple the microstructural model with a finite-element model (FEM) to determine the stresses and strains in the microstructure from densification by annihilation. The new algorithm for coupling the microstructural to the mechanical model is to uniformly distribute the mass in the eight grain sites (that surround the vacancy) to nine sites (including the vacancy plus the eight original neighboring sites). Thus, the strain resulting from annihilation events in the Potts microstructure model is converted to a hydrostatic, local strain in the FE solver, OOF (Object-Oriented Finite). The microstructure is then equilibrated under this applied strain.

We found a method to communicate the stressed state back to the microstructural model so as to simulate further microstructural evolution under stress. We introduced a kinetic factor into the probability equation of the Potts model. The kinetic factor is a function of the stress state of the grain site that is involved in the vacancy creation and migration part of the simulation. We extended the simple, uniform, two-dimensional (2-D) microstructural sintering model to three dimensions. The 3-D sintering model can simulate microstructural evolution in the unstressed state with normal grain growth, pore migration, vacancy formation, and annihilation.

In addition, a continuum model for sintering was implemented into Sandia's nonlinear, large-deformation, quasi-static, explicit FE code, JAS3D. Previously, we identified a promising approach that uses continuum mechanics and is based on the theories of plastic and nonlinear-viscous deformation of porous bodies. An example of this approach is a mathematical-constitutive description developed by V. V. Skorohod and further advanced by E. A. Olevsky. This phenomenological constitutive model was the initial targeted model for implementation into JAS3D and will be referred to as the Skorohod-Olevsky viscous-sintering (SOVS) constitutive model. An initial preliminary implementation of the SOVS constitutive model into JAS3D is completed. However, it was a total-stress implementation in a code that typically deals with incremental-stress-constitutive descriptions. Because the total stress implementation resulted in robustness issues, we used an alternative incremental reformulation and implementation of the SOVS model into JAS3D. The incremental implementation of the SOVS-constitutive model in JAS3D is now complete and verified

We extended the simple, uniform, two-dimensional (2-D) microstructural sintering model to three dimensions. The 3-D sintering model can simulate microstructural evolution in the unstressed state with normal grain growth, pore migration, vacancy formation, and annihilation.

against analytic solutions to various simple cases. We are in the initial stages of validating this work with Garino's sintering experiments on ZnO.

Refereed

Olevsky, E. A., V. Tikare, M. V. Braginsky, and T. J. Garino. 2001. "Simulation of Sintering of Layered Structures." *Proc. World Congress on Powder Metallurgy* (Kyoto, Japan, 10 November), in press.

Other Communications

Arguello, J. G., V. Tikare, and M. V. Braginsky. 2001. "Finite-Element Simulation of Sintering in Three-Dimensional Ceramic Components." Paper presented to the Annual Meeting of the American Ceramic Society, Indianapolis, IN, 25 April.

Braginsky, M. V. and V. Tikare. 2001. "Simulation of Microstructural Evolution During Sintering Under an Applied Stress." Paper presented to the 2001 Spring Meeting of the Materials Research Society, San Francisco, CA, 17 April.

Tikare, V., M. V. Braginsky, T. J. Garino, and E. A. Olevsky. 2001. "Mesoscale-Sintering Modeling for Process Control of Multilayered Ceramics for Wireless Technologies." (Invited) Paper presented to the Annual Meeting of the American Ceramic Society, Indianapolis, IN, 25 April.

26527

Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters

L. L. Whinnery, Jr., T. J. Shepodd, W. R. Even, Jr., S. K. Griffiths, R. H. Nilson

Sandia is studying microsystems for weapon-subsystem applications. Microsystems are being evaluated as replacements for a number of weapon subsystems and for the potential that microsystems have to improve surety while reducing weight and volume. However, a great concern exists because long periods of dormant storage may impair the mechanical functioning of microdevices that are exposed to water, out-gassing products (organics, solvents, and silicones), and particulates (talc and dust). Low-temperature operating environments and small moving parts in contact with stationary and mating structures make capillary condensation, ice formation, and corrosion serious concerns for microsystems. Past experience provides little guidance. The desiccants currently used to manage systemwide moisture levels cannot be relied on to provide the more stringent control needed to ensure microsystem reliability.

We are developing a new generation of irreversible, chemically reacting getters designed to ensure the integrity of the local environment within microsystem packages. We intend to incorporate reactive volatile species into a polymer through covalent bonds, thus producing a nonvolatile product. These reactive getters will be combined with getters that rely on absorption media (e.g., zeolites and high-surface-area carbon [C] fibers) to scavenge nonreactive species, such as solvents. Our getter systems will rely on device packaging to limit exchange between the microsystem and the global weapon environment. Thus, the internal getters need only provide local environmental control within the microsystem package. If the getters themselves are not tacky, they will be incorporated into a tacky-polymer matrix to immobilize microparticles in a harmless location. Modeling and analysis of available data are used to estimate the ingress of undesirable species as well as the gettering rates, capacities, and geometries needed to maintain an acceptable environment within the package. To summarize, we are developing getters

Sandia is studying microsystems for weapon-subsystem applications.

Microsystems are being evaluated as replacements for a number of weapon subsystems and for the potential that microsystems have to improve surety while reducing weight and volume. ...

We are developing a new generation of irreversible, chemically reacting getters designed to ensure the integrity of the local environment within microsystem packages. We intend to incorporate reactive volatile species into a polymer through covalent bonds, thus producing a nonvolatile product.

that utilize chemical reactions, adsorption, and physical adhesion to ensure a benign dormancy environment within microdevice packages.

For the reactive volatile species, such as water and ethanol, we are evaluating uptake with two experimental setups. The first setup uses a getter material in an open vial inside a larger, closed vessel containing either liquid, vapor-phase ethanol, or water. This method allows for several vials of materials and mixtures of materials in the same atmosphere at the same time for simultaneous evaluation, thus saving time and increasing reliable comparisons between materials. The second setup involves liquid-phase reactions with the getter material in direct contact with alcohol or with a combination of alcohol and solvent. This method should be relatively faster and will allow us to monitor the progress with time using nuclear magnetic resonance (NMR). Several chemical reactions were examined for this effort. The first two, the acid-catalyzed reaction of epoxides or strained olefins with water or ethanol, were unsuccessful under reasonable reaction conditions. However, polymeric anhydrides were found to react nicely with water, ethanol, and isopropanol.

Of the unreactive volatile species observed by Thornberg and Borek, we were able to group the major constituents into four groups (silicones, perfluoroalkanes, hydrocarbons, and hydrochlorocarbons). We chose model compounds to represent these groups. The model compounds are hexamethyl disiloxane, perfluorohexane, ethylbenzene, and 1,1,1-trichloroethane. Absorption-based getters for nonreactive volatiles are being evaluated using a porous C on a fiber that is exposed to a particular environment, followed by desorption into a gas chromatography (GC) column for analysis by solid-phase microextraction (SPME).

Mathematical modeling has begun on the evolution of chemical environments in microelectromechanical system (MEMS) packages. We are using screening measurements to construct models of gettering rates for candidate materials that are not encapsulated in a polymer matrix. We are working with Interbasic Research to develop a system uniquely suited to particle gettering and counting.

Mathematical modeling has begun on the evolution of chemical environments in microelectromechanical system (MEMS) packages. We are using screening measurements to construct models of gettering rates for candidate materials that are not encapsulated in a polymer matrix. We are working ... to develop a system uniquely suited to particle gettering and counting.

26528

Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance

C. J. Brinker, S. M. Brozik, J. Cesarano, III, D. Y. Sasaki, R. J. Simonson, D. R. Dunphy

Sandia is continuing cutting-edge research on self-assembly in nanomaterials. Within a very small volume, living cells integrate recognition, amplification, and transduction properties of interest for environmental sensors. Key to practical cell-based sensors is patterned cell immobilization in robust, biocompatible environments—environments that maintain cell viability and accessibility while enabling signal transduction and transmittal. Bulk silica matrices formed by classic sol-gel processing have been used for cell entrapment. But alcohol solvents cause protein denaturation, and, upon drying, broad pore-size distributions lead to the collapse of small pores and the complete drying-out of large pores, which limits accessibility or causes cell inactivation. Furthermore, bulk gels are difficult to integrate into devices such as microelectromechanical systems (MEMS).

Recently, we prepared porous silica nanostructures by evaporation-induced self-assembly (EISA). EISA employs surfactants to direct the self-assembly of silica into periodic structures characterized by unimodal pore sizes and one-dimensional (1-D), 2-D, or 3-D connectivity of pore-channel networks that are stable during drying. Using inkjet printing, we can pattern these pore-network systems on arbitrary surfaces.

Unfortunately all surfactant structure-directing agents used to date are bio-incompatible at concentrations needed for self-assembly. This project explores new biocompatible self-assembly approaches to enable us to incorporate whole cells into MEMS architectures and to write functional nanostructures on living reconnaissance agents. The advantages of using self-assembly to create biocompatible host matrices are twofold. First, the templated pores are all the same size. These hydrophilic monosized pore networks will spontaneously fill with water to create a kinetically stable aqueous environment without an auxiliary fluidic system. Second, EISA proceeds in complex mixtures unimpeded by guest molecules or particles, so we can expect to arrange cell patterns (on arbitrary surfaces) among cells that are

Sandia is continuing cutting-edge research on self-assembly in nanomaterials. ...

Recently, we prepared porous silica nanostructures by evaporation-induced self-assembly. ...

This project explores new biocompatible self-assembly approaches to enable us to incorporate whole cells into MEMS architectures and to write functional nanostructures on living reconnaissance agents.

immobilized in fluidic architectures incorporating buffer and nutrients to sustain viability for time periods needed for reconnaissance missions. Through genetic modification, cell-based sensors can be developed for specific chemical/biological warfare (CW/BW) or explosive threats.

All detergents/surfactants used to date in the self-assembly of inorganic nanostructures are bio-incompatible and cause piercing of cell membranes and cell death. We synthesized new biocompatible surfactants with hydrophilic carbohydrate headgroups. Also, we used amphiphilic phospholipids and phospholipid derivatives as structure-directing agents; we demonstrated the first self-assembled nanostructures using this class of compounds. Finally, we used a variety of small, biologically derived mono-, di-, and trisaccharides as pore templates to create films with porosities of approximately 40 percent by volume and very narrow pore-size distributions. These pore templates are biocompatible and can be removed by exposure to buffer. Additionally, they can serve as a nutritive source for immobilized cells. The stationary phase of the yeast *Saccharomyces cerevisiae* was incorporated into precursor sols and immobilized within resultant nanostructures produced by EISA. We developed a two-dye protocol (Fun 1/Fun 2) to quantify cell viability in the sols and within nanostructures. Using this protocol, we successfully identified compositional domains within the phospholipid/silica/ethanol/water (buffer) system; in this system, we maintained cell viability for periods of more than 50 minutes in sols. We subdivided these sol components into two stable sols, namely yeast prepared in buffer and silica plus phospholipids, catalyst, water, and ethanol. We used a Robocaster configured with two liquid reservoirs to “write patterns” of immobilized yeast on fused silica substrates. Control software allowed precise mixing of the two feedstocks in correct proportions to achieve the desired (biocompatible) composition, which was metered onto the substrate through a 25 μm orifice “pen.” Having incorporated the Fun 1/Fun 2 dyes into the initial yeast/buffer suspension (prior to writing), we were able to show retention of viability of cells immobilized in a patterned, self-assembled nanostructure. This key result demonstrates the potential of EISA as a straightforward means of patterned cell immobilization.

Having incorporated the Fun 1/Fun 2 dyes into the initial yeast/buffer suspension (prior to writing), we were able to show retention of viability of cells immobilized in a patterned, self-assembled nanostructure. This key result demonstrates the potential of EISA as a straightforward means of patterned cell immobilization.

26529

Nanoclusters for Supercapacitors*J. E. Martin, T. J. Garino, R. A. Anderson, V. K. de Marquis, J. P. Wilcoxon*

Sandia is researching how to reduce space requirements for supercapacitors. High-current and high-voltage capacitors, such as those used in weapons systems, use polymer films as dielectric materials. The dielectric constant of these polymer films is very low, thus limiting the energy storage of these capacitors. Because the energy requirements are high for weapons components, these capacitors are large and occupy a significant fraction of device volume. Capacitor space requirements leave little room for the diagnostic devices that we now envision.

One way to increase available space is to create a capacitor-film dielectric with a much higher dielectric constant. If the dielectric strength could be maintained, the result would be smaller capacitors.

We will investigate whether high-dielectric-constant nanoparticles can be used to significantly increase the dielectric constant of a capacitor material and thus energy storage in film capacitors. This idea is motivated by our ability to make narrow-dispersity nanoparticles of controlled sizes from 1.6 to 10 nm—nanoparticles that are atomically smooth and have precisely controlled organic-capping-layer thicknesses. These nanoparticles should be able to increase the dielectric constant of a capacitor film by a factor of five. If such a principle applies to both organic and inorganic dielectrics, a large commercial demand is anticipated for products ranging from supercapacitors to improved automotive ignition components.

Sandia is researching how to reduce space requirements for supercapacitors. ...

We will investigate whether high-dielectric-constant nanoparticles can be used to significantly increase the dielectric constant of a capacitor material and thus energy storage in film capacitors. ...

We will investigate whether high-dielectric-constant nanoparticles can be used to significantly increase the dielectric constant of a capacitor material and thus energy storage in film capacitors.

(1) We obtained a sensitive Agilent LCR (capacitance/resistance/inductance) bridge, interfaced this to a personal computer, and wrote an extensive LabView program that enables the efficient collection of frequency- and time-dependent sample impedance data.

(2) We designed and constructed two simple but accurate dielectric cells, with which accurate permittivity measurements can be made.

(3) We developed a new method of synthesizing metal nanoclusters; the method does not use surfactants, but relies on metalorganic precursors.

(4) We studied the growth of larger nanoclusters by heterogeneous nucleation onto seed particles and used this study to develop core-shell nanoclusters of gold on iron.

(5) We determined the alternating current (AC) dielectric properties of randomly dispersed metal-nanoparticle suspensions, including solidified samples.

(6) We synthesized oxidation-resistant superparamagnetic nanoparticles that can be structured into high-permittivity structures by applied magnetic fields.

(7) We studied the effect of magnetic fields on the AC dielectric properties of magnetic nanoparticle suspensions. We found a significant enhancement of the real part of the permittivity parallel to the structuring magnetic field; this finding agreed with computer simulations of the permittivity of such structured composites.

We studied the effect of magnetic fields on the AC dielectric properties of magnetic nanoparticle suspensions. We found a significant enhancement of the real part of the permittivity parallel to the structuring magnetic field; this finding agreed with computer simulations of the permittivity of such structured composites.

26530

First-Principles Determination of Dislocation Properties

M. van Schilfgaarde, S. M. Foiles

Sandia is examining how to model the core structure of dislocations from first principles. The ability to model dislocation-core structures at the atomistic level is central to developing a basic understanding and reliable models for them. However, the inherent complexities (of mixed-relevant-length scales) have led to few attempts from the first-principles using the local-density approximation (LDA).

Sandia's accomplishments fall into two areas.

(1) We developed a formal theory of mixed lattice and electronic Green's functions; the theory allows analysis of complex defects such as dislocation and its interaction with another defect.

(2) We continued applications of an extended Peierls-Nabarro (PN) model. This latter step establishes a conceptually simple and transparent semi-analytic framework in which dependencies between generalized stacking-fault (GSF) energetics and geometrical parameters describing dislocation structure can be established. This is important because it is often problematic to find tractable relations with all degrees of freedom (DOFs) between features of the electronic structure and chemical bonding of specific materials within a direct numerical atomistic-simulations methodology. In contrast, the PN model compactly represents the dislocation-core structure in terms of few physical meaningful DOFs (such as partial separation and width); consequently, linking the core to larger length scales is easier. It greatly facilitates, for example, analysis of the kink formation of split dislocations. We propose to do this analysis. The stress dependence of the core structure is an important and often missing piece of information about dislocation properties needed for understanding some mechanical properties.

We developed and employed some important extensions to the PN model to eliminate the continuum approximation for the misfit energy and used it to analyze features of the evolution of the dislocation-core structure under various stress conditions (glide and Escaig stress). We showed that the core may assume competing multiple structures that depend on the dislocation-axis position. As we

Sandia is examining how to model the core structure of dislocations from first principles. ...

We developed a formal theory of mixed lattice and electronic Green's functions; the theory allows analysis of complex defects such as dislocation and its interaction with another defect. ...

We developed and employed some important extensions to the PN model to eliminate the continuum approximation for the misfit energy and used it to analyze features of the evolution of the dislocation-core structure under various stress conditions (glide and Escaig stress).

demonstrate for ordinary dislocations in fcc (face-centered cubic) iridium (Ir) and the ordered $L1_0$ copper gold (CuAu) calculated using *ab initio* GSF energies, these lattice-discreteness effects, missing in the original PN model, significantly affect the evolution of the dislocation under stress.

We applied the same theory to the study of dislocations in a variety of fcc-based $L1_2$ intermetallic transition-metal compounds. We believe we have an explanation of the long-standing problem of the origin of anomalous yield in $L1_2$ high-temperature superalloys. In particular we can explain why some superalloys (Ni_3Al is a prototypical example) are anomalous in their yield stress, but others (such as Fe_3Ge) are not. The explanation follows directly from features of the *ab initio* GSF entering the model. This work points out the utility of this model approach in addition to its elegant simplicity and physical transparency.

Regarding the first and more difficult area of accomplishments, we formally developed a theory that shows in a rigorous way how the near- and farfield regions can be decoupled. We showed how the total energy functional of the infinite crystal can be transformed to one involving the DOFs in the near-core region alone, with the addition of an effective, external potential that accounts for the long-range strain fields. This enables one to handle the mesoscale aspect of the problem in closed form. We used a real-space electronic LDA Green's function approach for the electronic DOFs by solving Dyson's equation, and lattice Green's functions are adapted to special geometries to eliminate the mesoscopic lattice DOFs. The latter are constructed from LDA-based linear response theory and thus involve no model or adjustable parameters. The resulting theory is fully grounded in a quantum-mechanical framework while making no substantial approximations in bridging atomic- and mesoscopic-length scales.

This development alters some important technical details of the original way we had planned to set up this problem. In the original proposal, we discussed two approaches for treating the farfield: a quasi-continuum approach and an alternative lattice Green's function. The new approach has no need for quasi-continuum theory, but instead uses the more rigorous lattice Green's function theory, albeit in a somewhat different form than originally outlined.

We believe we have an explanation of the long-standing problem of the origin of anomalous yield in $L1_2$ high-temperature superalloys. In particular we can explain why some superalloys (Ni_3Al is a prototypical example) are anomalous in their yield stress, but others (such as Fe_3Ge) are not. ...

Regarding the first and more difficult area of accomplishments, we formally developed a theory that shows in a rigorous way how the near- and farfield regions can be decoupled.

Refereed

Mryasov, O. N., Y. N. Gornostyrev, M. van Schilfgaarde, and A. J. Freeman. 2001. "Complex Evolution of Dislocation Core Structure in a Process of Motion: Model Analysis with *Ab Initio* Parameterization." *Material Science and Engineering* **A309**: 310.

32915

Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment

S. M. Thornberg, J. R. Brown

The spin-coating procedure is used in a variety of applications to coat flat substrates or objects with thin films of material. The coating material is disbursed onto the surface of the substrate, then spun off—ideally, leaving a uniform layer for subsequent processing procedures. As the material is dispensed onto a spinning wafer, spiral-shaped wavefronts called Eckman spirals can be observed as the fluid migrates outward radially across the wafer. Spin-coating has traditionally been one of the first steps in semiconductor manufacturing.

In collaboration with the University of New Mexico (UNM) and the National Aeronautics and Space Administration (NASA), we will study the effect of weightlessness on deposition and distribution of photoresist on silicon (Si) wafers. This effect will be studied aboard NASA's KC-135 aircraft housing the reduced-gravity laboratory.

This unique opportunity to test the spin-coating process in a microgravity environment will provide experimental results heretofore unavailable. Even experts in the spin-coating field are unsure of the experimental outcome but are eager to see the results. We expect the spin-coating process to be quite different from a normal 1 g environment since much of the process relies on gravity to move the fluid to and across the wafer. It is possible that this research will provide the data necessary for this or other processes to be adapted to space environments.

We spin-coated a series of Si wafers with photoresist in a zero-gravity environment and compared them with wafers prepared using identical experimental parameters in the lab. We used a Solitec Model 5110-CT spin-coater, modified to operate aboard NASA's KC-135 Reduced-Gravity Flying Laboratory, to accomplish this. Overall, we consider the experiment to have been very successful. Several main findings were established though our experimentation:

- The adhesive forces between a photoresist and the Si wafer are substantial enough to allow for the spin-coating procedure to be done without the force of gravity. Our original

Liquid photoresist forms a sphere at the end of the dispense nozzle in zero-gravity environment.

Spin-coating has traditionally been one of the first steps in semiconductor manufacturing. ... This unique opportunity to test the spin-coating process in a microgravity environment will provide experimental results heretofore unavailable.

hypothesis was that at high spin speeds, the photoresist would twist and float off of the spinning wafer; this was not the case at all. In fact, higher spin speeds may be required to achieve a desirable coating in zero gravity.

- Gravity seems to play a substantial role in the fluid dynamics that dictate the characteristics of the photoresist film in the spin-coating procedure. This can be shown by the formation of fluid wavefronts (Eckman spirals) during the dispense cycle. In all wafers prepared in the lab, two distinct Eckman spirals can be observed. However, we observed only one Eckman spiral in all the wafers prepared in zero gravity. This may prove to be of significance in the modeling of the spin-coating process. As in all the literature available on the subject, gravity is neglected when deriving the equations that approximate fluid behavior.

Refereed

Brown, J. R., and S. M. Thornberg. 2001. "Study of Polymer Spin-Coating for Photolithographic Semiconductors in a Near-Zero-Gravity Environment." Sandia Technical Report SAND2001-2948, Sandia National Laboratories, Albuquerque, NM (September).

In all wafers prepared in the lab, two distinct Eckman spirals can be observed. However, we observed only one Eckman spiral in all the wafers prepared in zero gravity.

34465

Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation

P. W. Fuerschbach

Laser spot welding is widely used for precision joining of nuclear weapon components and is a strong candidate for use in joining micromachines. However, the production of metal vapor as a consequence of high-fluence laser irradiation is a serious concern in cleanrooms. Contamination of delicate components from the metal vapor plume, ejection of metal particulates into the air and adjacent mechanisms, creation of void defects in the fusion zone, and significant loss of high-vapor-pressure alloying elements are all negative consequences of metal vaporization. Despite the widespread use of lasers for the welding of high-value-added components, little fundamental understanding of laser/material interaction exists. Without this fundamental understanding, optimization models cannot be applied to mitigate vaporization problems.

Sandia plans laser-spot-welding experiments to quantify the effect of laser-pulse parameters on weld-pool dimensions and liquid-metal expulsion propensity. In addition, we intend to refine previous laser-weld-characterization techniques and to develop new approaches for quantifying the temperature field in laser spot welds, primarily through careful measurement of alloy-element vaporization rates. Development of these analysis techniques provides a needed foundation for model prediction of laser-weld pool vaporization.

In a collaboration with Pennsylvania State University (PSU), we will also use in our research a transient, three-dimensional (3-D) model that PSU developed for the calculations of mass transfer, heat transfer, and fluid flow. We need computer-model analysis to fundamentally understand laser-induced vaporization. We expect that a new understanding of the process on a microscopic level will ultimately allow us to modify the process or to define a window of safe operating parameters so the adverse effects of vaporization in laser welding can be alleviated.

The project began with the development of a laser-beam spotsize-measuring technique employing Kapton film of varying thicknesses. The film was mounted in a 35 mm slide and exposed to focused single-laser pulses at several positions

Sandia plans laser-spot-welding experiments to quantify the effect of laser-pulse parameters on weld-pool dimensions and liquid-metal expulsion propensity. In addition, we intend to refine previous laser-weld-characterization techniques and to develop new approaches for quantifying the temperature field in laser spot welds, primarily through careful measurement of alloy-element vaporization rates.

around the lens focal plane. We measured the average of the major and minor diameter of the burnt-through hole for various beam energies and durations. We fit the variation in beam spotsize with focal position to the laser-beam-propagation equation to determine the minimum spotsize diameter. We also used the Prometec Laserscope to measure laser spotsizes under similar laser conditions. The Laserscope measurements were also fitted to the beam-propagation equation. We found that 75 μ Kapton film yielded very similar spotsize values to the Laserscope, although the Kapton film had slightly more precision error. For both techniques the bias error of the measurements is unknown since no standard measurement technique exists for calibration. Kapton is much more practical for spotsize measurement with spot-welding lasers than the Laserscope since the Laserscope must be synchronized at a 25 Hz laser-pulse frequency.

We completed screening experiments to quantify the degree of vaporization from laser spotwelds on small samples of 304L stainless steel. In these experiments, we varied laser-pulse energy from 3 J to 9 J and spot diameter from 0.38 mm to 0.75 mm. We made vaporization-loss measurements using a Mettler MT5 microbalance with 1 μ g precision. Early on, we found that mass loss per pulse was similar for tests made with either 5, 10, or 15 spotwelds per sample. Since multiple welds on these sample specimens are straightforward, all subsequent tests included 15 pulses per sample. The use of Kapton film to measure spotsize enabled an accurate determination of the beam intensity required to produce vapor loss as well as metal spatter. We found the onset of metal spatter to clearly invalidate some of the vapor-loss measurements; nonetheless, the precise determination of the spatter threshold should prove to be beneficial to analytical models of the process. We found that pulse energy clearly affects the magnitude of vapor loss. Measured vapor losses ranged from 11 μ g for 3 J pulses to 70 μ g for 9 J pulses. The effect of spotsize on vaporization was less pronounced.

We completed screening experiments to quantify the degree of vaporization from laser spotwelds on small samples of 304L stainless steel. ... the precise determination of the spatter threshold should prove to be beneficial to analytical models of the process. We found that pulse energy clearly affects the magnitude of vapor loss.

Refereed

Fuerschbach, P. W., and G. R. Eisler. 2001. "The Effect of Laser Spot-Weld Energy and Duration on Melting and Absorption." *Science and Technology of Welding and Joining*, submitted. SAND2001-1879J (June).

34466

Mechanics and Tribology of MEMS Materials*M. T. Dugger, J. R. Michael, J. A. Ohlhausen, S. V. Prasad, T. E. Buchheit*

Micromachines have the potential to significantly impact future weapon-component designs as well as other defense, industrial, and consumer-product applications. For both electroplated LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) and surface-micromachined (SMM) structural elements, the influence of processing on structure and the resultant effects on material properties are not well understood. The behavior of dynamic interfaces in present as-fabricated microsystem materials is inadequate for most applications, and the fundamental relationships between processing conditions and tribological behavior in these systems are not clearly defined.

Sandia intends to develop a basic understanding of deformation, fracture, and surface interactions responsible for friction and wear of microelectromechanical systems (MEMS) materials. This will enable needed design flexibility for these devices, as well as strengthen our understanding of material behavior at the nanoscale. The project goal is to develop new capabilities for submicroscale-mechanical and tribological measurements and to exercise these capabilities to discover fundamental knowledge of material behavior at this size scale. We will develop novel microforce and displacement sensors using SMM technology and new methodologies for isolating local variations in mechanical response of MEMS materials. Understanding the nanomechanics of surface contact is expected to result in new fundamental contributions to theories of interfacial adhesion as a function of topography. The ability to quantify friction over a wide range of pressure and velocity conditions and in controlled environments will enable fundamental understanding of the effect of environment on friction and surface durability. Increased understanding of MEMS mechanics and tribology developed in this project will permit performance and reliability of advanced MEMS components to be predicted with a sound scientific basis.

(1) We attributed the low-friction coefficient and high wear-resistance observed for SMM devices coated with tungsten (W) to a surface layer of tungsten trioxide (WO₃),

Sandia intends to develop a basic understanding of deformation, fracture, and surface interactions responsible for friction and wear of microelectromechanical systems (MEMS) materials. This will enable needed design flexibility for these devices, as well as strengthen our understanding of material behavior at the nanoscale. ... Increased understanding of MEMS mechanics and tribology developed in this project will permit performance and reliability of advanced MEMS components to be predicted with a sound scientific basis.

and adsorbed organic contamination formed within a few days of atmosphere exposure.

(2) We performed a series of investigations on silane films coating polysilicon from which we derived the following new conclusions: (a) Films that previously exhibited changes in friction response upon rubbing in lateral-force microscope experiments could be made resistant to those changes by annealing. (b) Unannealed silane films with high coverage that did not exhibit changes in friction response upon rubbing in lateral-force microscopy experiments could be made to exhibit frictional response changes by increasing the interfacial velocity between the probe and the sample surface. These observations are consistent with our model describing the origin of observed changes in friction response with rubbing on these monolayer films.

(3) We developed a procedure to quantify wear damage in SMM friction contacts. The procedure involves use of a focused ion beam to extract and orient a worn sample from the micromachine friction test device for imaging in the atomic-force microscope.

(4) We quantified adhesion measurements between LIGA surfaces using nanoindentation methods with a specially constructed LIGA-adhesion probe combined with new programming in a nanoindenter. We showed that the unique morphology present on LIGA-sidewall surfaces can result in significant adhesive forces between the sidewall and a flat surface.

(5) We continued improvement in SMM pull-tab tensile test methodology through upgraded specimen designs and use of new 25 μ cylindrical sapphire probe.

(6) We have begun experimenting with first-generation fracture-toughness and force-measurement designs in an effort to expand the material-properties measurement capabilities of MEMS devices.

We quantified adhesion measurements between LIGA surfaces using nanoindentation methods with a specially constructed LIGA-adhesion probe combined with new programming in a nanoindenter. We showed that the unique morphology present on LIGA-sidewall surfaces can result in significant adhesive forces between the sidewall and a flat surface.

Refereed

Dugger, M. T. 2001. "Microtribology and Microelectromechanical Systems (MEMS)." (Invited) Paper presented to the STLE 2001 Annual Meeting, Orlando, FL, 20 May.

Dugger, M. T. 2001. "Quantification of Friction in Microsystem Contacts." in *Nanotribology: Critical Assessment and Research Needs* (Klewer), accepted.

Dugger, M. T., S. S. Mani, D. E. Peebles, and G. A. Poulter. 2000. "Friction and Wear Resistance of Tungsten Coatings on Silicon Micromachined Devices Related to their Surface Chemistry." Paper presented to the Fall 2000 Meeting of the Materials Research Society, Boston, MA, 26 November.

Prasad, S. V., D. A. LaVan, and M. T. Dugger. 2001. "Novel Techniques for Measurement of Adhesion in LIGA Microsystems Contacts." Electronic posting on Center 1800 Web site. SAND2001-0598P (15 July).

Prasad, S. V., D. A. LaVan, T. R. Christenson, T. E. Buchheit, and M. T. Dugger. 2001. "Adhesion Measurements in LIGA MEMS Contacts Using Novel Nanoindentation Techniques." Paper presented to the Materials Research Society, Boston, MA, 27 November.

Other Communications

Dugger, M. T., and S. V. Prasad. 2001. "Surface Treatments for Microsystems: Coating Issues and Tribological Measurement Methods." Paper presented to the Fall 2001 Meeting of the Materials Research Society, Boston, MA, 26 November.

Dugger, M. T., T. E. Buchheit, and S. V. Prasad. 2001. "Tribology and Mechanics of Microsystem Materials." Briefing on Tribology and Mechanics Capabilities to DARPA, Albuquerque, NM, 15 June.

Garcia, C. R., R. J. Salzbrenner, M. T. Dugger, and T. E. Buchheit. 2001. "Behavior and Reliability of MEMS Through Tensile Testing and Friction and Wear Testing." Paper presented to the 6th Annual Student Symposium, Albuquerque, NM, 9 August.

Lemieux, C. M., R. J. Salzbrenner, and M. T. Dugger. 2001. "Friction Behavior of OTS Monolayers Upon Interaction with Scanning Probe." Paper presented to the 6th Annual Student Symposium, Albuquerque, NM, 9 August.

Prasad, S. V., A. C. Hall, and M. T. Dugger. 2000. "Characterization of Sidewall and Planar Surfaces of Electroformed LIGA Parts." Sandia Technical Report SAND2000-1702, Sandia National Laboratories, Albuquerque, NM (20 October).

34467

Dynamics of Metal/Ceramic Interfaces

K. F. McCarty

The goal of this project is to understand how metal/ceramic interfaces form, evolve, and accommodate the stress that can lead to delamination and failure. In this project Sandia emphasizes the use of advanced microscopies such as scanning-tunneling microscopy (STM) and low-energy electron microscopy (LEEM) to observe interface formation in real time. These techniques are used to measure the interfacial work of adhesion, determine the mechanisms and kinetics of interface formation, and develop an understanding of how stress is or is not accommodated. We emphasize the model ceramics of sapphire and titanium dioxide.

We used LEEM to selectively image the different surface phases that form as the nickel aluminum (NiAl) (110) surface undergoes oxidation at low temperature. We exposed the clean surface to oxide (O₂) at 325°C and then imaged it at progressively higher temperatures using LEEM. Although a relatively uniform film results, oxide-free regions (pinholes) develop when the initially amorphous oxide crystallizes. This oxide film consists of one type of alumina that has two orientational domains on the substrate. Selective imaging of the domains just after crystallization shows that nuclei of both domains are present at high density. With time and temperature, the domains coarsen greatly, as do the oxide-free regions (pinholes). By reducing the length of the domain boundaries, the coarsening reduces the energy. We wrote and submitted to an archival journal a manuscript summarizing these results.

Refereed

McCarty, K. F. 2001. "Imaging the Crystallization and Growth of Oxide Domains on the NiAl(110) Surface." *Surface Science* **474**: L165.

The goal of this project is to understand how metal/ceramic interfaces form, evolve, and accommodate the stress that can lead to delamination and failure. In this project Sandia emphasizes the use of advanced microscopies such as scanning-tunneling microscopy (STM) and low-energy electron microscopy (LEEM) to observe interface formation in real time.

34468

In Situ Characterization of Soft-Solution Processes for Nanoscale Growth

N. S. Bell, D. R. Tallant

The study of novel materials and structures with dimensions in the nanoscale (less than 100 nm) regime is an important emerging field of materials science. The small size of these materials results in quantum confinement and surface contributions that translate into novel optoelectronic properties with applications that are still being realized. Many synthesis techniques for nanomaterials are based on soft-solution processes, which include sol-gel, hydrothermal, solvothermal, micellar or organic-templating routes, and electrochemical methods. These processes involve the precipitation of ionic species or metalorganic molecules into nanoparticles or nanostructured networks. To exercise a high degree of control over these processes, a capability to follow development of supersaturation, surface processes, and formation of a precipitating system in situ is critical. In this project, Sandia is studying the superposition of different measurement techniques to characterize dynamic colloidal systems in novel ways. These studies will probe the chemical interactions during reactions and the organizational characteristics developed in the resulting colloids.

We investigated using Raman spectra to follow the precipitation reaction of zinc (Z) oxide produced by hexamethylenetetraamine (HMT). In studying the system, we found that the base-producing chemical HMT did not decompose as expected, based on a survey of the literature. The reason for the stability of the HMT is unknown, and further examination of the literature is under way. A possibility is the formation of a Z-HMT complex that stabilizes the HMT and reduces the supersaturation of the Z in the solution; both effects are detrimental to the synthesis of the desired Z oxide. The main conclusion of the study was that observation of precipitation is possible if the Z ions can be made to precipitate efficiently.

We undertook the precipitation of silver (Ag) nanoparticles to both reproduce published methods and develop new techniques. We chose four formulations from the literature, and all were successfully reproduced to form Ag nanoparticles with the reported particle-size properties. We

In this project, Sandia is studying the superposition of different measurement techniques to characterize dynamic colloidal systems in novel ways. These studies will probe the chemical interactions during reactions and the organizational characteristics developed in the resulting colloids.

performed new synthesis using variations in conventional surfactants composed of carboxylic acids, and these surface species show variations in maximum-absorption wavelength in ultraviolet-visible (UV-vis) spectroscopy. Theoretical treatment of the surface states is available in the literature, and treatment of the current synthesis methods is being considered using the Mie theory. We are also discussing issues with the National Institute of Standards and Technology (NIST) for characterizing the optical properties of nanoparticles. Present characterization techniques include UV-vis spectroscopy and atomic-force microscopy (AFM) imaging of deposited nanoparticle layers.

We synthesized polystyrene. This published procedure stated that the size distribution would be under 5 percent, as is required for particle self-assembly. Our studies investigated a number of reaction variables and found that the system is remarkably stable and insensitive to reaction conditions. However, the breadth of the particle-size distribution is larger than reported in the paper, and a more focused study of the technique is required to find the proper synthesis conditions. Observations of the polystyrene particles under dialysis show iridescent effects expected from a monodisperse suspension. The reason for the development of this behavior is unknown. Possibly the optical model used in the Coulter LS 230 particle-size analyzer is not optimized for this polystyrene material, and the optical properties may need to be independently determined. If necessary, we can perform particle-size separations by sedimentation to refine the current material. We identified a scientific corporation as a source for monodisperse silica in place of the latex in case absolute surety is required.

The addition of the acoustic spectrometer was desired for study of colloidal stability in the precipitation reaction, but clearly, the theoretical modeling used in the instrumentation is not adequate to follow behavior below 1 percent by volume solids in the solution. Therefore, we adapted our research approach to examining the effect of solution-reaction components to a synthesized-nanoparticle system rather than an *in situ* system. Nanoparticles at a concentration sufficient to provide signal in the instrument are being synthesized and collected. We will investigate these materials by titration of additional reduction reagent and source solution to provide the first observation of colloidal-stability properties of nanomaterials and how component concentration during

We synthesized polystyrene. This published procedure stated that the size distribution would be under 5 percent, as is required for particle self-assembly. Our studies investigated a number of reaction variables and found that the system is remarkably stable and insensitive to reaction conditions.

synthesis affects colloidal stability. These observations will be related to the observable effects on particle synthesis by varying reaction conditions.

34469

Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques

K. R. Zavadil, F. D. Wall

A key factor in our ability to produce and predict the stability of metal-based macro- to nanoscale structures and devices is a fundamental understanding of the localized nature of corrosion. Corrosion processes where physical dimensions become critical in the degradation process include localized-corrosion initiation in passivated metals, microgalvanic interactions in metal alloys, and chemistry in adsorbed water films in atmospheric corrosion.

Sandia is focusing on two areas of corrosion science where a fundamental understanding of processes occurring at critical dimensions is not currently available. We are studying the critical-length scales necessary for passive film breakdown in the inundated aluminum (Al) system and the chemical reactions and transport in ultrathin water films relevant to the atmospheric corrosion of Al. We require techniques that provide spatial information without significantly perturbing or masking the underlying relationships. Al-passive film breakdown is governed by the relationship between areas of the film sampled and its defect structure. We will combine low-current measurements with microelectrodes to study the size scale required to observe a single initiation event and record electrochemical-breakdown events. We will correlate the resulting quantitative measure of stability with metal-grain size, secondary-phase size, and distribution to understand which metal properties control stability at the macro- and nanoscale. Mechanisms of atmospheric corrosion on Al are dependent on the physical dimensions and continuity of adsorbed water layers as well as the chemical reactions that take place in this layer. We will combine microelectrode arrays with electrochemical sensing and electrostatic-force microscopy to monitor the chemistry and ion transport in these thin layers. These measurements will be the basis for calculating oxidant-partition coefficients and ion mobilities. We will use the techniques developed and information derived from this work to understand and predict degradation processes in electrical and structural components.

Sandia is focusing on two areas of corrosion science where a fundamental understanding of processes occurring at critical dimensions are not currently available. We are studying the critical-length scales necessary for passive film breakdown in the inundated aluminum (Al) system and the chemical reactions and transport in ultrathin water films relevant to the atmospheric corrosion of Al.

We developed an electropolishing technique for reproducibly preparing high-purity Al-wire surfaces for electrochemical testing. We found electropolishing to be most effectively performed at 0°C in a bath containing 20 percent perchloric acid, 5 percent glycerol, and 75 percent methanol. We assessed the pitting susceptibility of Al microelectrodes (25 μ diameter) in terms of a pitting potential (E-pit) as a function of polishing time. E-pit distributions did not vary significantly for polishing times between 20 sec and 120 sec; however, the longer polishing times produced more reproducible results as assessed using optical microscopy.

To facilitate development of the electropolishing technique, we fabricated electrode arrays from both 125 μ and 500 μ diameter Al wires. For each wire size, we assembled 10 arrays, each containing 10 electrodes. We used the arrays to establish baseline pitting behavior of the 125 μ diameter electrodes and, at the same time, to validate two multipotentiostats that will be used throughout this project. We determined that the potentiostats yielded E-pit values that converged to the same distribution when 30 datapoints were collected from each system. This indicates that fewer than 30 points may be insufficient to fully characterize E-pit distributions.

We are developing a capillary-based electrochemical cell to test small areas of macroscopic electrodes that are not available in wire form (e.g., Al single crystals). In a previous research effort, we assembled a system that could test reduced areas on the order of 100 μ –1000 μ in diameter. The target for this research is to be able to isolate and investigate 10 μ –50 μ diameter regions. Thus far we have prepared capillary cells down to 2 μ in diameter.

We designed, fabricated, and demonstrated a microelectrode array for use as a proximal pH detector for use in ultrathin water layers. We used conventional microelectronic fabrication techniques to develop closely spaced (2 μ interelectrode spacing) planar arrays of microelectrodes ranging from 1 μ to 20 μ in diameter. Water is allowed to wet the array surface through adsorption of H₂O from the vapor phase by incorporating the array into a gaseous-flow cell where the relative humidity and O₂ content can be controlled. We used electrochemical-impedance spectroscopy to determine the formation of a continuous water layer at the array surface by measuring a frequency-dependent impedance decrease between adjacent electrodes. We

To facilitate development of the electropolishing technique, we fabricated electrode arrays from both 125 μ and 500 μ diameter Al wires. ... We determined that the potentiostats yielded E-pit values that converged to the same distribution when 30 datapoints were collected from each system. This indicates that fewer than 30 points may be insufficient to fully characterize E-pit distributions.

accomplish O₂ detection in these thin water films by monitoring the pH transient at a sensing iridium-oxide (IrO)₂-modified electrode as a function of applied potential at an adjacent platinum (Pt)-generator electrode. Reduction of O₂ produces hydroxide ions, and the resulting pH change can be correlated with O₂ concentration. These results show that chemical information relevant to corrosion processes can be obtained under atmospheric conditions. The intent is to refine and use these tools to explore atmospheric-corrosion mechanisms.

We are refining our approach to improving the stability of the chemical sensor and to integrating imaging capability with array use. We demonstrated that electrodeposition of IrO₂ onto Pt and gold (Au) from a basic oxalate solution followed by vacuum annealing can produce a stable film that maintains an established potential versus pH response through indefinite wetting and drying cycles. These films can be deposited to thicknesses of 50 nm with this same stability. We designed and fabricated a second-generation array to maximize the degree of planarity in the sensing region of the array. We will use electrostatic-force microscopy to map the spatial distribution of the water layer formed with adsorption to aid in understanding how O₂ and hydroxide (OH⁻)-transport laterally in these films.

We are refining our approach to improving the stability of the chemical sensor and to integrating imaging capability with array use.

Refereed

Wall, F. D., and M. A. Martinez. 2001. "Homogeneous Pit Nucleation on High-Purity Aluminum." Paper presented to the 200th Meeting of the Electrochemical Society, San Francisco, CA, 3–7 September.

Zavadil, K. R., J. C. Barbour, S. H. Kravitz, and R. V. Ellis. 2001. "Potentiostatic Detection of Gases and Corrosion Products in Ultrathin Water Layers Present During Atmospheric Corrosion." Paper presented to the 199th Meeting of the Electrochemical Society, Washington, DC, 25–29 March.

34470

Nanoscale Mechanics in an Instrumented Transmission Electron Microscope

A. K. Schmid, D. L. Medlin

The importance of microsystems to defense and commercial technologies will grow rapidly. The great majority of the research and development effort has been placed rightly on understanding how to design and manufacture these systems. Although the processing technologies have matured considerably, many open questions remain about the reliability of microsystems, particularly after extended periods of dormancy. Many envisaged microsystems rely on mechanical actuation to function. These actuations produce mechanical deformations and wear at length scales considerably smaller than in conventional systems. Whether the mechanisms of deformation and friction at the small-length scales of microsystems differ from conventional devices needs to be investigated.

In this work, Sandia is addressing the reliability of microsystems by studying how materials deform and respond when they are contacted and rubbed at the nanometer-length scale. We are designing and constructing specialized test equipment that will allow the nanoscale response of contacted and sliding materials to be directly observed during operation in a transmission electron microscope (TEM). We will use these new instruments to study the nanometer-scale deformation, friction, and wear of the materials used in microsystems manufactured by LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding [process]), and surface-micromachining (SMM) processes.

We designed the prototype of a nanomechanical-positioning apparatus to perform nanoscale mechanics in a TEM. The device consists of inertially driven friction stages that permit the submicron-motion control that is necessary for indentation. Furthermore, the profile of the device fits the available space within the TEM sample area. We made the parts for the prototype and partially tested several components successfully.

Key to the success of this stage of the project is the fabrication of reliable friction surfaces that allow motion and stability once motion has stopped. We tested several candidate

The importance of microsystems to defense and commercial technologies will grow rapidly. The great majority of the research and development effort has been placed rightly on understanding how to design and manufacture these systems. ...

In this work, Sandia is addressing the reliability of microsystems by studying how materials deform and respond when they are contacted and rubbed at the nanometer-length scale.

materials, including tungsten carbide and alumina, and stainless steel and alumina, to find the optimum combination. To drive this motion, we used piezoceramic materials in a tube configuration. The drive shaft in this case runs down the length of the tube. Motion is achieved by voltage profiles applied to the piezo to cause an alternating sequence of high-acceleration expansion or contraction followed by slow relaxation. In such a profile, sliding is achieved during the high-acceleration phase while a no-sliding contact is maintained during the slow-relaxation phase. In this way, motion is achieved in steps that are of submicron size.

... sliding is achieved during the high-acceleration phase while a no-sliding contact is maintained during the slow-relaxation phase. In this way, motion is achieved in steps that are of submicron size.

34478

LIGA Microsystems Aging: Evaluation and Mitigation

C. H. Cadden, N. Y. C. Yang

LIGA is the acronym for the German term Lithographie, Galvanoformung, und Abformung, which translates to lithography, electroforming, and molding (process). Deploying LIGA structures in Defense Programs (DP) applications requires a thorough understanding of potential long-term physical and chemical changes that may occur during service. While these components are generally fabricated from simple metallic systems—such as copper (Cu), nickel (Ni), and Ni alloys—the electroplating process used to form the systems creates microstructural features that differ from features in conventional (e.g., ingot metallurgy) processing of such materials. Physical changes in nonequilibrium microstructures may occur from long-term exposure to temperatures that permit atomic and vacancy mobility. Chemical changes, particularly at the surfaces of LIGA parts, may occur in the presence of gaseous-chemical species (e.g., water vapor, high-explosive [HE] off-gassing compounds) and contact with other metallic structures.

Sandia is characterizing LIGA materials currently being produced at Sandia-Livermore. These materials include pure Ni along with nickel-cobalt (Ni-Co), and nickel-iron (Ni-Fe) alloys. We will use this baseline characterization as a reference point as we monitor changes that occur in LIGA structures over extended time periods in environments similar to those envisioned for DP applications. Finally, we will investigate conformal coating systems as needed to combat environmental degradation occurring at LIGA surfaces.

We selected four LIGA part geometries for our characterizations. Used individually and in pairs, these components will provide both mechanical and structural information regarding the effects of long-term thermal and environmental exposure in selected weapons environments. These geometries are also appropriate for evaluating candidate protective-coating systems. Production of these test parts is under way.

We designed and constructed test chambers that will contain groups of LIGA specimens for controlled temperature and environmental exposures. LIGA specimens are loaded in

Sandia is characterizing LIGA materials currently being produced at Sandia-Livermore. ...

We will use this baseline characterization as a reference point as we monitor changes that occur in LIGA structures over extended time periods in environments similar to those envisioned for DP applications. Finally, we will investigate conformal coating systems as needed to combat environmental degradation occurring at LIGA surfaces.

fixtures that maintain specific orientation and, where desired, controlled contact between a particular LIGA surface and another metallic surface. These contact surfaces consist of both LIGA/LIGA and LIGA/stainless-steel (SS) combinations. After assembly, fixtures are loaded into a SS vessel. The vessel is filled with the desired gaseous composition, and the vessel is subsequently sealed.

We conducted microstructural characterization of electrodeposited-Ni test parts. These studies focused on differences in structure obtained with and without a saccharin addition to the sulfamate-electrolyte bath used for electroplating. Results show major effects on metallurgical characteristics (i.e., the film texture, grain structure, and hardness of the electrodeposited Ni). Additionally, subsequent annealing treatments also produced different responses, resulting in differences in grain growth and hardness loss.

We conducted microstructural characterization of electrodeposited-Ni test parts. These studies focused on differences in structure obtained with and without a saccharin addition to the sulfamate-electrolyte bath used for electroplating. Results show major effects on metallurgical characteristics, (i.e., the film texture, grain structure, and hardness of the electrodeposited Ni).

34485

Science-Based Processing of Field-Structured Composites

R. L. Williamson

Over the past few years, a new class of materials has emerged called field-structured composites (FSCs) that pose interesting and novel process-control challenges. FSCs are anisotropic particle composites produced in electric or magnetic fields that exhibit highly anisotropic properties due to the chain or sheetlike structures that form as a result of the induced dipolar forces between particles. The field-structuring gives tremendous control of material properties, and the potential for practical applications is great if feedback can be used to tailor material properties to meet specific needs. Recent research at Sandia shows that these materials have colossal thermoresistance, piezoresistance, magnetoresistance, and chemiresistance, making FSCs very promising as sensors if reliably produced with a desired resistivity. These materials pose nontrivial feedback-control challenges, due to strong history effects, diverging timescales, and nonlinear dynamics. Our goal is to meet these challenges by developing science-based process control, using newly discovered methods of achieving feedback in these materials.

The major goal of the FSC work was to construct a triaxial magnetic-field apparatus and use the apparatus to control the conductivity of an FSC along one axis. The core idea was that a rotating field produced by two coils could cancel the structuring effect produced by the stationary field of the third. By adjusting the relative strengths of the alternating and static fields, we envisioned that one could control the conductivity along the stationary-field axis.

We completed the design work and constructed the apparatus. We carried out structuring/destructuring experiments using 50 μ diameter nickel (Ni) particles in mineral oil to investigate the structures that form under triaxial field conditions. A pure rotating field causes vigorous stirring of the mixture when the stationary field is switched on. Though the net-induced dipole interaction in the triaxial field system can be made to exactly cancel, strong local field effects survive and cause stirring. We investigated other, nonrotating alternating field schemes and observed novel, complex, 3-D structures. For example, we observed a lattice

Recent research at Sandia shows that these materials have colossal thermoresistance, piezoresistance, magnetoresistance, and chemiresistance, making FSCs very promising as sensors if reliably produced with a desired resistivity. These materials pose nontrivial feedback-control challenges, due to strong history effects, diverging timescales, and nonlinear dynamics. Our goal is to meet these challenges by developing science-based process control, using newly discovered methods of achieving feedback in these materials.

of sheets intersecting at right angles with the lines of intersection along the stationary field axis and made video recordings of these structures.

We performed experiments to characterize the open-loop conductivity response of Ni/gold (Au) particles in oil in the triaxial field environment. With both rotating and stationary fields applied, the sample was vigorously stirred and conductivity between electrodes low. With the rotating field turned off, conductivity increased significantly in a manner roughly proportional to stationary-field strength. Turning off the stationary field had little affect, as did subsequently cycling the rotating field on and off. However, cycling the stationary field on and off caused the conductivity to decrease by four to six orders of magnitude, providing strong evidence that the system was effectively destructured by this sequence. We observed this chain of events to be reproducible, but the behavior is, as yet, not completely understood.

The results show that the field dependence of the conductivity is much more complex than originally thought. It is clear that a simple feedback system would be incapable of producing and tracking a target conductivity under these conditions. The problem of how to control conductivity in this system is currently under consideration. Certainly, the above cycle may be repeated to produce the target conductivity, but we feel that improved methods will be found once basic understanding of the phenomenon is achieved.

The second part of the work studied field-structured plasmas (FSPs). In this study, we constructed a uniaxial magnetic-field device and mounted it into an existing arc-generating device to study the problems associated with controlling the structure of a metal-vapor plasma. We tuned the magnetic-field strength to determine the parameters necessary to confine the plasma under the cathode. We imaged the arc using a high-speed framing camera. We observed plasma focusing at arc gaps of 1 cm and 2 cm, and at field strengths of 50, 100, 170, and 230 Gauss. The focusing effect is enhanced by higher field strengths and shorter arc gaps. Macroparticle ejection by cathode spots was not significantly affected by field strength.

The second part of the work studied field-structured plasmas (FSPs). In this study, we constructed a uniaxial magnetic-field device and mounted it into an existing arc-generating device to study the problems associated with controlling the structure of a metal-vapor plasma.

34699

Exploration of New Multivariate Spectral Calibration Algorithms

D. M. Haaland, L. E. Martin, C. M. Wehlburg, D. K. Melgaard, M. H. van Benthem

Sandia previously developed a powerful new multivariate calibration algorithm that has the ability to correct many of the outstanding limitations of traditional quantitative multivariate spectral calibrations, such as minimizing the numbers of calibration samples and maintaining calibrations in the presence of drift. While investigating the limitations of this new proprietary prediction-augmented classical least squares/partial least squares (PACLS/PLS) hybrid algorithm, we developed a family of potentially better algorithms. These new algorithms have the ability to be rapidly updated during prediction without recalibration. This rapid updating feature is a significant advantage over our previous hybrid algorithm that can impact weapons projects and industrial problems where spectral quality control and/or process monitoring is desired. We demonstrated the new algorithms to improve the quantitative hyperspectral image (HSI) analyses of aged materials. Because we developed and implemented a family of four new algorithms, we need to understand the relative merits of these new multivariate algorithms, to better understand the properties and relative performance of the new methods compared to traditional multivariate calibration methods, and to explore a variety of potential applications using the new algorithms. For example, the new algorithms may be able to (1) improve the qualitative information in the derived pure-component spectra of complex samples, (2) rapidly update multivariate spectral calibration models for changes in starting products for commercial process monitoring or quality control, and (3) improve HSI analyses from many sources, including remote sensing.

We submitted a provisional patent application extending the PACLS algorithm to the concentration-residual-augmented classical least squares (CRACLS) to the U.S. Patent Office along with a second provisional patent application describing the entire family of augmented CLS methods. In addition, we received a final office action on the hybrid patent from the U.S. Patent Office, prepared a

We demonstrated the new algorithms to improve the quantitative hyperspectral image (HSI) analyses of aged materials. Because we developed and implemented a family of four new algorithms, we need to understand the relative merits of these new multivariate algorithms, to better understand the properties and relative performance of the new methods compared to traditional multivariate calibration methods, and to explore a variety of potential applications using the new algorithms.

response, and the claims were accepted. We also successfully licensed the pending patents to Thermo Nicolet Corporation. Also, a research paper describing the new family of ACLS algorithms was submitted for publication in *Vibrational Spectroscopy*.

We investigated the ability of the new algorithms to improve our ability to transfer multivariate spectral calibrations between spectrometers. We entered into a collaboration with Dow Chemical Company since they had independently obtained a set of near-infrared (NIR) spectra of a set of multicomponent organic liquid samples using spectrometers from four different manufacturers. They used these data to evaluate the current standard method of transferring calibrations between spectrometers, namely, piecewise direct standardization (PDS). We performed an evaluation of our hybrid algorithm and a subset recalibration method using the Dow datasets. We performed this evaluation blind to the Dow PDS results. The results presented to Dow demonstrated the superiority of our hybrid algorithm to both the subset recalibration method and the PDS method. In every case for each analyte and for every instrument used as a secondary spectrometer, the hybrid method outperformed PDS and subset recalibration. The predictions on the secondary instrument were also comparable to the calibrations generated on the same spectrometers, indicating no loss of prediction ability when the calibrations were transferred from the primary to secondary spectrometer. Early indications suggest that the outlier detection capabilities of the hybrid method are superior to those of the PDS algorithm. These excellent results led Dow to request information related to licensing our patent-pending algorithms.

We initiated the development of a new procedure to improve the determination of the optimal model size. The new ACLS algorithms are less prone to overfitting than traditional multivariate calibration methods such as partial least squares (PLS) and principal component regression (PCR). However, the lack of overfitting makes them less amenable to optimal factor selection. Therefore, we had to develop a new factor-selection method that will be optimal for our new ACLS methods. Our approach is to use the standard CLS model to predict the factor-analyzed residuals generated from the CLS spectral residuals from all calibration samples. Those factors that are most detrimental to the standard CLS model are the most important factors to add in the ACLS algorithm. However, too many added factors can degrade the net-analyte

We performed this evaluation blind to the Dow PDS results. The results presented to Dow demonstrated the superiority of our hybrid algorithm to both the subset recalibration method and the PDS method. In every case for each analyte and for every instrument used as a secondary spectrometer, the hybrid method outperformed PDS and subset recalibration.

signal (NAS) and lower prediction performance. Therefore, factors are ordered relative to the product of the introduced error and the NAS. These ordered factors are then added in a sequential fashion to the ACLS model using cross-validation methods to select the optimal number of factors to augment the CLS model. We programmed and are testing the algorithm to implement this idea. The same method can be used for factor selection in updating the ACLS models in prediction using repeat or subset samples.

We initiated comparisons of the predictive performance of the new ACLS methods among themselves and with traditional multivariate calibration methods using simulated data to understand and quantify the relative performance of the various methods. We generated simulated datasets based on real data to test and compare the relative performance of the algorithms. The simulations include ideal spectral noise, correlated spectral noise, concentration errors, and different amounts of these various noise sources. Preliminary prediction comparisons indicate superior prediction ability for the ACLS methods in the presence of correlated spectral noise.

We generated simulated datasets based on real data to test and compare the relative performance of the algorithms.

Refereed

Haaland, D. M., and D. K. Melgaard. 2001. "New Augmented Classical Least Squares Methods for Improved Quantitative Spectral Analyses." *Vibrational Spectroscopy*, submitted.

Melgaard, D. K., D. M. Haaland, and C. M. Wehlburg. 2001. "Concentration Residual Augmented Classical Least Squares (CRACLS): A Multivariate Calibration Method with Advantages over Partial Least Squares." *Applied Spectroscopy*, submitted.

Wehlburg, C. M., D. M. Haaland, and D. K. Melgaard. 2001. "New Hybrid Algorithm for Transferring Intra-Instrument Multivariate Quantitative Calibrations of a Near-Infrared Spectrometer." *Applied Spectroscopy*, submitted.

Wehlburg, C. M., D. M. Haaland, D. K. Melgaard, and L. E. Martin. 2001. "New Techniques for Maintaining Multivariate Quantitative Calibrations of a Near-Infrared Spectrometer." *Applied Spectroscopy*, submitted.

Other Communications

Haaland, D. M., D. K. Melgaard, F. W. Koehler, C. M. Wehlburg, and L. E. Martin. 2001. "New Augmented Classical Least Squares Methods for Improved Quantitative Spectral Analyses." Paper presented to the 1st International Conference on Advanced Vibrational Spectroscopy, Turku, Finland, 19–24 August.

Melgaard, D. K., D. M. Haaland, C. M. Wehlburg, and L. E. Martin. 2001. "A Comparison of the Augmented Classical Least Squares Calibration Methods." Paper presented to the Pittsburgh Conference, New Orleans, LA, 4–9 March.

Microsystems and Engineering Sciences Applications (MESA)

The Microsystems and Engineering Sciences Applications (MESA) investment area is working to create a delivery system comprising the facilities, infrastructure, and supporting network of capabilities needed to provide microsystems-based solutions, products, and services in support of Sandia's national security missions. This MESA delivery system will include personnel and facilities from many different parts of Sandia, and will incorporate all of the elements needed to meet specifications, cost requirements, and schedules for the delivery of reliable, microsystems-based solutions for Sandia's customers. This research will involve supporting commercial and university relationships.

The "New Architectures for Micro-Total-Analytical Systems" project leverages Sandia's unique capabilities in electrokinetic pumping and microfabrication to establish a new technology—high-performance liquid chromatography (HPLC) in miniature. While HPLC remains the preferred macroscale analytical technique, its adaptation to an integrated microscale device has proven elusive because of the lack of a miniaturizable high-pressure pump. Sandia's miniature pumps can be integrated on-chip, and several improvements to HPLC can be realized through

microfabricated sample injectors and chip-based separations media. It is our goal to achieve better separations than currently possible using an integrated microdevice. This research will bolster Sandia's efforts in the national security mission area of chemical/biological weapons non-proliferation and its efforts in biotechnology. Two patent disclosures have been filed.

10756

New Architectures for Micro-Total-Analytical Systems

P. C. Galambos, J. A. Irvin, E. F. Hasselbrink, Y. Fintschenko, M. Okandan, S. Montague, T. J. Shepodd, D. J. Bennett

The goal of this project is to leverage Sandia's unique capabilities in electrokinetic pumping and microfabrication to establish a new technology, high-performance liquid chromatography (HPLC), in the field of micro-Total Analysis Systems (μ TAS). While HPLC remains the "gold standard" macroscale analytical technique, its adaptation to an integrated microscale device has proved elusive because of the lack of a miniaturizable high-pressure (> 3000 psi) pump.

Recently, Sandia demonstrated a capillary HPLC system that utilizes its proprietary electrokinetic pumps (EKPs), which are capillary-sized pumps capable of delivering over 9000 psi pressure. Since these pumps can be integrated on-chip, and several improvements to HPLC can be realized through microfabricated sample injectors and chip-based separations media, it is our goal to achieve better separations than possible with macroscale HPLC using an integrated device. The design will incorporate EKPs, sample injector, separation media, and detection on a single chip. Besides EKPs, three Sandia technologies are essential components of this goal: (1) microfabrication of high-aspect-ratio insulating microstructures, to engineer optimal separations media and EKPs; (2) Sandia-proprietary sample injection technology technical advance (TA) to prevent parasitic dispersion during sample injection; and (3) the integration of electrodes into microfluidic channels, and the development of a robust electrochemical detection scheme. At the same time, this research will bolster Sandia's efforts toward its national security mission in the area of chemical/biological weapons nonproliferation, and its efforts in biotechnology. Furthermore, it is hoped that the research will create new applications for Sandia's microfabrication technology.

We attained porous polymer EKP pressures of 0.11 psi/V and are attempting to increase this pumping pressure to 1 psi/V by reducing pore size. We are also attempting to control the variability of pore size to achieve more reproducible pump pressures. We fabricated EKPs using a

Fabrication of EKPs using a modified SUMMiT V process.

The goal of this project is to leverage Sandia's unique capabilities in electrokinetic pumping and microfabrication to establish a new technology, high-performance liquid chromatography, in the field of micro-Total Analysis Systems.

modified SUMMiT (Sandia Ultraplanar Multilevel MEMS Technology) process that incorporates SiN films as the pump walls and uses polysilicon (poly-Si) wires to bring electrical signals to the pump electrodes. These SiN layers are included with the standard SUMMiT poly-Si layers to make a variety of structures. One of these structures uses a deep oxide cut to make electrical connection through poly-Si “wires” to the electrodes used to apply voltage to the EKP. These electrodes are photolithographically defined and, therefore, may be placed anywhere in the pump channel. Close spacing between electrodes allows the same field strength to be applied with a lower voltage.

In the initial EKP fabrication, we encountered problems with the oxide deep cut, and all of the electrical lines were shorted together. We corrected this problem with a modification to both the process and the design in the second build. We plan to perform electrical tests of the on-chip SUMMiT EKPs utilizing the glass manifolds fabricated at Sandia-California.

We initially attempted standard EK and materials tests to characterize streaming potential, streaming current, conductivity, flow rate, bacterial endotoxins test (BET), mercury porosimetry, and maximum pressure. The envelope of pump performance, however, is determined by only two quantities: neo/k gives the pressure/voltage ratio of the pump, and $neoA/F$ gives the flow rate per unit electric field. Hence, flow rate, max pressure, and a simple test of Darcy coefficient k provide all three coefficients required to characterize pump performance. Furthermore, we found that while values of neo and F vary by factors of 2 to 4, values of k vary by up to two orders of magnitude. Accordingly, the Darcy coefficient can be measured as a preliminary screening tool to identify promising formulations.

In our initial testing, we pumped water and blood through silicon nitride (SiN) channels. We also experimented with aqueous solutions on poly-Si electrodes to determine what types of solution additives and voltage signals are needed to avoid gas bubbles generated by electrolysis. We determined that a 5 percent polyethylene glycol (PEG) aqueous solution reduces electrolysis, such that a 1 MHz alternating current (AC) signal (200 V peak-to-peak across a 2μ or 4μ electrode gap) does not cause electrolysis bubbles.

In our initial testing, we pumped water and blood through silicon nitride (SiN) channels. We also experimented with aqueous solutions on poly-Si electrodes to determine what types of solution additives and voltage signals are needed to avoid gas bubbles generated by electrolysis. We determined that a 5 percent polyethylene glycol (PEG) aqueous solution reduces electrolysis, such that a 1 MHz alternating current (AC) signal (200 V peak-to-peak across a 2μ or 4μ electrode gap) does not cause electrolysis bubbles.

Refereed

Hasselbrink, E. F., E. B. Cummings, and M. T. Blom. 2001. "Dispersion in Electroosmotic Flow Through Periodic Media." Paper presented to the Gordon Research Conference, Oxford, England, 29 July.

Okandan, M., P. C. Galambos, S. Mani, and J. Jakubczak. 2001. "Development of Surface-Micromachining Technologies for Microfluidics and BioMEMS." *Proc. Society of Photooptical Instrumentation Engineers (SPIE), Microfabrication Conference, Microfluidics and BioMEMS* **4560** (San Francisco, CA, October): 21.

Okandan, M., P. C. Galambos, S. Mani, and J. Jakubczak. 2001. "Surface-Micromachined Cell Manipulation Devices for Transfection and Sample Preparation." *MicroTAS 2001* **1** (Monterey, CA, October): 156.

Shepodd, T. J., E. Franklin, J. Hotelling, R. Jensen, and Z. Prickett. 2001. "Polymer Electrokinetic Pumps: A Cast-to-Shape and Conduct as Cast Option for Moving Fluids." Paper presented to the Gordon Research Conference, Oxford, England, 29 July.

26770

Interconnection Technology for Next Generation of Integrated Microsystems

R. Chanchani, D. J. Rieger, S. Samora, T. A. Fischer, G. R. Sloan, R. D. Briggs, K. M. Norman

True microsystems of the future will require denser interconnection technologies to facilitate integration and miniaturization of electronics, optics, and microelectromechanical systems (MEMS) in a single package. Various high-density interconnection (HDI) technologies, which exist in the industry, interconnect electronics only and do not offer the flexibility and integration capability that microsystems require.

Sandia is developing an HDI-substrate technology that will facilitate integration of a broad range of microsystems for future Sandia applications (e.g., the next-generation synthetic-aperture radar [SAR], for microtags and advanced fuzing circuits). This high-density substrate technology consists of multilayers of thin-film-deposited benzocyclobutene (BCB) dielectric with copper conduction on a variety of substrates. Also within this interconnect structure, we will embed passives like resistors, capacitors, and inductors.

(1) We completed developing a baseline process on a 4-inch silicon (Si) wafer to build up a multilayer circuit with the following features:

- (a) Five copper (Cu)-conductor layers and four BCB dielectric layers,
- (b) 2μ thick Cu conductors patterned with the lift-off process,
- (c) 5μ thick BCB dielectric, and
- (d) 100μ pitch line interconnect and 35μ diameter vias.

A test vehicle structure (test vehicle I), specially designed for the BCB/Cu process development, has 4000+ daisy-chained via test structures in the inner layers, and on the top surface, it has 1000 input/output (I/O) pads for four integrated circuits (ICs). Diagnostic test ICs were flip-chip-attached to the test vehicle. One of the four ICs has a daisy-chain structure interwoven with the BCB/Cu structure. We determined the success of the process by (1) the continuity

Sandia is developing an HDI-substrate technology that will facilitate integration of a broad range of microsystems for future Sandia applications (e.g., the next-generation synthetic-aperture radar [SAR], for microtags and advanced fuzing circuits).

test of 4000+ via test structures, (2) successfully flip-chip-attaching four ICs on the substrate, and (3) the continuity of the assembled daisy-chain die.

(2) We are currently developing the following enhancements to the baseline processes:

(a) Reduce via size from 35μ to 25μ and 30μ ,

(b) Determine the feasibility of fabricating thicker BCB dielectric layers from 5μ in the baseline process to 20μ . (We included this task, which was not in the original proposal, because the initial simulation of radio-frequency [RF] circuits indicated that 20μ thick dielectric may be needed for RF applications. BCB used for 5μ thick layers is photodefinable, whereas the BCB that will be used for 20μ thick layers is nonphotodefinable. Thus, a considerably higher level of effort will be needed for process development.)

(c) Develop multilayer structure on alumina ceramic base substrate instead of Si wafer. Alumina ceramic having a different thermal characteristic than Si requires new sets of process parameters. We are currently investigating experiencing some issues with inadequate adhesion of BCB to ceramic.

(3) We completed the design of test vehicles required for the development of processes for embedded passives. There will be three test vehicles, one each for resistor, capacitor, and inductors.

We completed the design of test vehicles required for the development of processes for embedded passives. There will be three test vehicles, one each for resistor, capacitor, and inductors.

Nonproliferation and Materials Control

The Nonproliferation and Materials Control investment area examines advanced technologies for improving the physical security of weapons and special nuclear materials. This research focuses on creating innovative solutions to new national security challenges, including (1) developing global virtual presence capabilities, (2) enabling agile response to intelligence challenges, (3) developing technologies for the protection of our nation's strategic nuclear resources, (4) preparing innovative responses to biological and chemical threats, and (5) improving international cooperative threat-reduction capabilities.

The “Thin-Skin Deployable Mirrors for Remote Sensing Systems” project is working to develop an innovative space-based telescope system. Expensive large-aperture optics are critical for improving sensitivity and resolution of space-based telescopes needed for DOE nonproliferation missions. Deployable optics can resolve the conflicting needs between large operational apertures and the necessity to minimize costs. This project is pursuing a novel mirror design and shape control approach for deployable mirror systems. Deployability and shape control are

integrated directly into the mirror material by making it out of a thin-skin “smart material.” Two technical advances have been filed as a result of this research. This work has the potential to support a wide range of national security applications.

10357

A Real-Time Decision-Support Framework to Guide Facility Response to Abnormal Events

J. E. Brockmann, L. D. Brandt, K. K. Murata, S. P. Gordon, D. M. Edwards, F. Gelbard

Adverse consequences to facilities that are subject to abnormal environments can be dramatically reduced if timely and appropriate mitigation actions are taken. Success in damage limitation requires the real-time fusion of data from diverse sources. An information and decision framework is required to evaluate these data, assess the probable impacts, and develop a decision and control strategy. The framework must develop graded facility responses appropriate to the quality of information available and the predicted consequences of the event and prospective mitigation options.

This project will provide the technical basis and prototype information tools for guiding facility response in threatening environments. Sandia will develop a decision framework that propagates prediction uncertainty, addresses decision risk measures, incorporates temporal updating, and links disparate information. Robust predictive models able to utilize sparse sensor data to predict transport and consequences will be developed. We will construct an integrated decision tool and evaluate it initially against a realistic reference facility. The initial prototype will provide a proof-of-concept and indication of the performance of the new technologies. The tools will be refined and evaluated against more diverse facilities and more general environments as the final step in the research.

Successful completion of this research will provide key results supporting development of information and decision systems that improve safety and security of virtually all of the key facilities in the nation. The work will provide a technical foundation for several emerging areas of importance to Sandia, including a broad range of infrastructure protection programs. The work is particularly applicable to the development of protection systems for chemical/biological attacks on civilian infrastructure targets, a growing area of national interest. The research is structured specifically to provide Sandia with a demonstrated technological base and fundamental tools to address these problems.

This project will provide the technical basis and prototype information tools for guiding facility response in threatening environments. Sandia will develop a decision framework that propagates prediction uncertainty, addresses decision risk measures, incorporates temporal updating, and links disparate information.

We originated methods for analysis of sensor data that will enable operators to place a limited number of sensors at near-optimal locations in a building to determine the source of a release and the concentrations of the release in building locations without sensors. This information is crucial in guiding the response, such as HVAC (heating, ventilation, air conditioning) flow alteration or evacuation routes, to a release of hazardous material within a building. We learned several lessons, such as the questionable utility of single or unassociated sensors to give adequate information to determine a response, the importance of quickly determining the source location to make predictive calculations of contaminant concentration, and the importance of being able to position sensors to give this information. We identified the importance of the flow matrix through the building to make the above determinations and improved the calculational tool used to generate the flow matrix. We examined how to modify the algorithm used to determine sensor placement and source location to accommodate material deposition during transport. We developed a fast-running transport module (given the flow matrices in the building) to implement the rapid calculation of source term and unsensed room concentrations from real-time sensor data.

We developed a method for generating a building model for use with the calculational tool KCNBC from electronic blueprints that significantly speeds the model generation over doing it by hand. This improvement will reduce the cost in generating building models for calculation.

Our work has demonstrated the effectiveness of isolation of separate HVAC systems within a given building in reducing the spread of hazardous material throughout the building. This project demonstrated the significant role played by countercurrent flow through opened doorways and recirculation through the HVAC system in mixing material through a given HVAC system.

We developed a method for generating a building model for use with the calculational tool KCNBC from electronic blueprints that significantly speeds the model generation over doing it by hand. This improvement will reduce the cost in generating building models for calculation.

Refereed

Gelbard, F., J. E. Brockmann, and K. K. Murata. 1999. "Sensor Analysis Software (SAS): An Algorithm for Determining Airborne Agent Concentrations Throughout a Large Multiroom Building." Sandia Technical Report SAND99-1945, Sandia National Laboratories, Albuquerque, NM.

Gelbard, F., J. E. Brockmann, K. K. Murata, and W. E. Hart. 2000. "An Algorithm for Locating Sensors in a Large Multiroom Building." Sandia Technical Report SAND2000-0851, Sandia National Laboratories, Albuquerque, NM.

Other Communications

Gelbard, F. 2001. "Sensing, Analyzing, and Responding to Chem-Bio Threats." (Invited) Presentation to the Indoor Air Quality Workshop, East Hartford, CT, 4–5 June. SAND2001-1595A&P.

10358

Physical Model–Based Fusion of Sensor Array Data

I. R. Shokair, C. F. Melius, C. Springer, D. C. Roe, N. M. Berry

This project is aimed at development of analysis methods and computational models for detection of chemical species of interest in the presence of background contaminants, using array separation methods. One of Sandia's main objectives is the development of algorithms that utilize all useful available information to enhance detection (lower detection limits) while maintaining very low probabilities of false alarm rates. We developed such algorithms for independent multiple-channel analysis followed by a fusion algorithm to combine the individual channel results and make a final decision on a given species detection as well as estimate the probability of a false alarm. For each channel, we developed a process of hypothesis testing to calculate the probability of the following: (1) detected peak is a result of background subtraction errors, (2) shape of detected peak does not match database shape, and (3) detected peak time is incorrect due to instrument variability and is a result of an adjacent peak. These hypotheses are used to calculate the false alarm probability for a detected species in a separation channel.

We applied the analysis algorithms to an extensive set of experimental measurements, using capillary zone electrophoresis (CZE) and capillary gel electrophoresis (CGE) separations.

For a given channel, once the Adaptive Background Suppression-Peak Detection (ABD-PD) algorithm has detected a peak, a process of hypothesis testing is carried out to calculate the probabilities that (1) the detected peak is part of the background signal, (2) the detected peak does not have the correct shape, and (3) the detected peak time is incorrect because of instrumental variability (i.e., due to an adjacent peak). The analyses of these three alternate hypotheses result in a probability of false alarm for the detected species in a separation channel. The F-test (ratio of residuals) is used to compare different hypotheses. A contaminant species with the same retention time and peak shape as a species of interest cannot be analyzed as a possible alternate hypothesis, and can only be distinguished by multiple orthogonal separation processes.

This project is aimed at development of analysis methods and computational models for detection of chemical species of interest in the presence of background contaminants, using array separation methods. One of Sandia's main objectives is the development of algorithms that utilize all useful available information to enhance detection (lower detection limits) while maintaining very low probabilities of false alarm rates. We developed such algorithms for independent multiple-channel analysis followed by a fusion algorithm to combine the individual channel results and make a final decision on a given species detection as well as estimate the probability of a false alarm.

We extended the analysis algorithms to use either dependent or independent residuals for multiple-channel separations. For the analyzed data and most anticipated separations, we found that independent channel analysis is considerably more practical because of data variability and the possibility of overlapping peaks with unknown contaminants in a channel. Thus, we treated each channel as an independent sensor with its data analyzed individually. We then used a fusion algorithm to make a final decision on the detection and calculation of an overall probability of false alarms for detected species.

We applied the analysis algorithms to an extensive set of measurements of unknown samples containing varying concentrations of four biotoxins: ricin, ovalbumin, botulinum toxin, and *Staphylococcal enterotoxin B* (SEB). We used two separation channels: CZE and CGE. Some of the samples also contained unknown aerosol contaminants. Some of the initial datasets were used as training sets to obtain database information such as peak times and shapes, as well as to establish ranges of variability for use in the hypothesis testing process.

The results of analysis of the CZE data were excellent and resulted in correct detection in most cases with very low false alarm rates. Analysis of the CGE data was somewhat problematic because of large variability of retention times due to irreproducibility of the separation channel parameters.

We applied the analysis algorithms to an extensive set of measurements of unknown samples containing varying concentrations of four biotoxins: ricin, ovalbumin, botulinum toxin, and Staphylococcal enterotoxin B.

10365

Controlling Information: Its Flow, Fusion, and Coordination

T. M. Berg, R. G. Hillaire, N. M. Berry

This project investigated information, from fundamental properties and definitions to optimal information-handling algorithms for sensing applications, for application to robot collectives. Sandia borrowed the concept of Fisher information from statistics and optimal filtering and applied it to the problem of engineering information-driven sensor systems to extend results, first in distributed optimal filtering, and then in distributed collectives of robots. Fisher information is a useful engineering definition because it provides mechanisms for handling information overlap, redundancy, and reliability in distributed information-gathering systems. As we tie our Fisher information engineering results to recent results using Fisher information to derive physical laws, we open up new areas of research that should be particularly fruitful for controlling very large numbers of robots.

We used Fisher information to extend the state of the art in the optimal filtering of distributed sensor data and to develop the engineering trade-offs. The trade-off list is long and includes local sensing node complexity, global optimality measures, communication requirements, node connection requirements, memory, latency, computation, survivability and redundancy, initialization complexity, intrusion vulnerability, and adaptation requirements.

Using these results, we improved a distributed Kalman filter for tracking that allows full decentralization of all system assets.

To more effectively engineer robotic collectives or swarms, we began attacking the problem of understanding how information determines the group macrobehavior that results from local rulemaking across large numbers of actors, particularly when these robotic actors can sense their environments and interact with it in various ways.

We used Fisher information to extend the state of the art in the optimal filtering of distributed sensor data and to develop the engineering trade-offs. The trade-off list is long and includes local sensing node complexity, global optimality measures, communication requirements, node connection requirements, memory, latency, computation, survivability and redundancy, initialization complexity, intrusion vulnerability, and adaptation requirements.

10378

Characterization of Underground Facilities in an Urban Environment

M. D. Ladd, M. W. Holzrichter, G. J. Elbring, D. L. Faucett, B. P. Engler

It is well known that rogue nations may conceal facilities for the manufacture and storage of weapons of mass destruction (WMD) by placing them in urban areas. The ability to characterize and monitor these facilities is an important national concern. Because of the multisource and high-noise nature of urban environments, such sites pose special challenges for unattended sensors. Current programs such as the Hard Target Defeat Program address the nonurban, two-dimensional (2-D) monitoring domain.

The intent of this project was to develop and apply novel adaptive signal-processing methods and sensor deployment configurations to permit the characterization of concealed facilities in an urban environment. In particular, we explored seismically monitoring a suspect facility from adjacent building basements. We investigated characterization of the source vibrations and the use of advanced signal-processing techniques such as the application of adaptive array techniques to cancel out noise signals based on source location. The system developed in this research provides a new capability for the urban environment. We have directly addressed the nonproliferation and materials control need to covertly collect information that can characterize proliferation activities. This project also addressed the emerging threats need to characterize difficult targets.

Our activities focused on an iterative process for applying adaptive beamforming to field data, analyzing the results, and refining those algorithms to yield adaptive array beam-forming algorithms that can, to a significant degree, isolate the target signal from strong interferers and background noise. In this way, we achieved as much as a 27 dB improvement in the signal-to-interferer ratio. Our algorithms, based on the maximum likelihood and minimum variance approaches, relied heavily on the statistical properties of the signal and were less dependent on physical models of the signal environment, which was fortuitous because analysis showed that the seismic medium as well as the placement of the sensors on the inside of an underground concrete vault

Before and after spectrograms illustrate the suppression of an interfering signal by an adaptive beamformer.

result in a complex wavefield that is resistant to physical modeling. The complex wavefield, along with staffing constraints, resulted in our not finding a solution to the problem of estimating the location of the source of the target signal from the signal recorded by the array. Similarly, the application of polarization processing to data from a triple-component array did not yield results significantly better than results from a single-component array. This result, too, is attributed to the complex nature of the recorded wavefield.

In addition to algorithmic development, we established factors affecting sensor fidelity, such as timing accuracy and separation tolerances in deployment layouts. We studied novel deployment strategies including the use of three-dimensional (3-D) seismic arrays in neighboring buildings. Validation of algorithms used both simulation and field data.

Our research resulted in the following:

(1) A system study for a recording system for seismic monitoring of WMD activities in an urban environment. The study outlines the hardware and software options for the recording system, and

(2) A paper, to be published in the *Proceedings of the 2001 Society of Photooptical Instrumentation Engineers' Aerosense Conference*, reporting the results of the application of an early version of the adaptive beamformer.

... we established factors affecting sensor fidelity, such as timing accuracy and separation tolerances in deployment layouts.

Refereed

Holzrichter, M. W., and M. D. Ladd. 2001. "Using Array Processing to Isolate Seismic Signals from Noise and Interferers of Cultural Origin." *Proc. SPIE Aerosense Conference* **4393** (Orlando, FL, 18 April).

10693

Nanosat

W. T. Wallace, R. J. Shul, D. L. Armour, T. R. Christenson, S. H. Kravitz, D. J. Johnson, B. C. Brock, T. J. Kim, R. M. Axline, D. Ingersoll, A. P. Sylwester, A. A. Allerman, W. C. Sweatt, J. A. Nevers, J. L. Schoeneman, S. B. Rohde, C. A. Reber, H. C. Shen, A. J. Smiel, G. R. Schuster, R. A. Williams, J. A. Rawlings, J. H. Mulkern, A. M. Harris, G. B. Haschke, E. J. Gurule, D. Cruz, W. K. Schubert, C. E. Sandoval, C. B. Webb, S. F. Piekunko, D. H. Doughty, J. W. Weston, J. R. Klarkowski, S. A. Casalnuovo, S. G. Rich, M. J. Rightley, M. Armendariz, M. E. Warren, S. F. Terwilliger, D. W. Palmer, M. L. Pedroncelli, M. R. Daily, J. C. Chavez, M. K. Lau

A paradigm shift in satellite systems is occurring based on the use of small, inexpensive satellites to replace functions performed by large, expensive satellites. These “nanosatellites,” or “nanosats” (i.e., less than 10 kg), would be used in a variety of applications. These applications range from constellations of several hundred nanosats covering the globe to closely knit clusters of nanosats flying in formation and acting cooperatively for imagery, surveillance, intelligence collection, or threat detection, to single nanosats used for satellite inspection and anomaly resolution.

Numerous U.S. government agencies (e.g., Department of Energy, Central Intelligence Agency, National Reconnaissance Office [NRO], Defense Intelligence Agency [DIA], Air Force) have documented the need for small-satellite technology to meet future requirements for

A paradigm shift in satellite systems is occurring based on the use of small, inexpensive satellites to replace functions performed by large, expensive satellites. These “nanosatellites,” or “nanosats” (i.e., less than 10 kg),

Conceptual drawing of a structural battery system. The structural elements are silicon wafers. The advantage of this integrated hybrid power structure is that it incorporates energy storage, energy conversion, power management and distribution, and spacecraft structure, all into a single integrated unit, therefore potentially significantly reducing the overall size and weight of these systems on a nanosat.

surveillance of potential proliferants of chemical/biological weapons (CW/BW), for threat/missile detection, and for tracking/impact prediction.

For nanosat systems to be affordable and reliable, satellite and launch costs must be drastically reduced. Nanosat development will require a wide range of enabling technologies (e.g., miniaturization, multifunctional integration of satellite systems). Successful implementation will bring the microsystems revolution to space.

Sandia has more than 35 years' experience in developing space-based national security solutions. This experience directly supports nanosat development. Sandia also has state-of-the-art silicon (Si), compound semiconductor, and packaging facilities for microcircuits/photonics, microelectromechanical (MEMS) devices, and advanced battery technologies directly applicable to nanosat development. Other applicable areas include distributed processing, high-speed communications, and materials/fabrication technologies. These capabilities, plus the ability to integrate multidiscipline product development teams, provide the basis to successfully develop nanosats for future national security missions.

To date, we have focused our efforts on the design, prototyping, and miniaturization of critical nanosat satellite systems, using microcomponents and fabrication technologies. These systems and activities included laser communications, attitude and position determination elements, structural battery, advanced packaging, sparse-aperture applications study, and a nanosat deployment study. The systems identified above do not represent all nanosat systems (e.g., other systems would include propulsion, up- and downlink communications, thermal control, and structural elements); however, they do represent those systems that are critical to the success of a nanosat.

- *Laser communications system.* Our goal is to demonstrate a portable, full-duplex, auto-tracking, high-data-rate (1 Gbs), wide (45°) field of view, 1.5 μ wavelength, and miniaturized laser communications system. Two small enclosures house the combined transmit/receive prototype hardware. We designed and fabricated prototype hardware including the optics train, laser elements, electrooptic processing electronics (i.e., optical and high-speed digital), encryption/decryption electronics, and interface electronics (i.e., analog/digital). In addition, one enclosure included a

Sandia has more than 35 years' experience in developing space-based national security solutions.

This experience directly supports nanosat development.

Sandia also has state-of-the-art silicon (Si), compound semiconductor, and packaging facilities for microcircuits/photonics, microelectromechanical (MEMS) devices, and advanced battery technologies directly applicable to nanosat development.

joystick to demonstrate that a communications lock could be maintained while the laser optics head was moving (to simulate satellite movement in space). The unit was at least a factor of 10 smaller than our previous half-duplex demonstration. We are integrating and testing all hardware elements.

- **Attitude control.** Our goal is to demonstrate a mini three-axis reaction wheel assembly with the following performance characteristics: slew rate 2° per second, positional accuracy 0.1° , automatic software control, and miniaturized electronics to allow for a volume of less than 20 cubic inches. We met each of these goals. We measured the maximum slew rate at 19° per second. We measured positional accuracy at less than 0.1° . We successfully demonstrated automatic software control algorithm development. We designed and fabricated the electronics (including a processor, interface, and motor control [analog] boards) for all three motors. Three 2.5-inch-diameter boards with dense packing of parts on both sides were fabricated, populated, and stacked with a distance between boards of less than $1/4$ inch. We fabricated a reaction wheel assembly housing measuring 3.75 inches in diameter by 1.825 inches in height, with a volume of 20.16 cubic inches.

- **Position and attitude determination.** Our goal is to demonstrate a space-capable, carrier-phase global positioning system (GPS) receiver (for attitude determination) that is low power (less than 1 W). Activities concentrated on developing a low-power hardware solution with a GPS radio frequency (RF) front end and a low-power microprocessor to process raw navigation data. We also focused on developing carrier-

Our goal is to demonstrate a mini three-axis reaction wheel assembly with the following performance characteristics:

- slew rate 2° per second,*
- positional accuracy 0.1° ,*
- automatic software control,*
- and miniaturized electronics to allow for a volume of less than 20 cubic inches.*

Second prototype integrated reaction wheel assembly. Shown is a complete integrated and miniaturized three-axis reaction wheel assembly for use with a nanosat weighing approximately 10 kg.

phase post-processing algorithms and software to compute relative position between multiple GPS antennas, and then on using the relative position information to calculate attitude. We successfully integrated the RF front end and microprocessor, and demonstrated that they can track eight GPS satellites simultaneously and obtain both position and carrier-phase information. The measured power was 1.5 W. We developed carrier-phase software. In tests of multiple receiver sets (four receivers), both position and attitude accuracies met theoretical predictions.

- *Structural battery.* Our goal was to design and demonstrate a structural lithium (Li)-ion battery based on Si-wafer processing techniques. The design consisted of four wafers (two outer and two inner, patterned in a honeycomb pattern where the Li-ion battery material resides). To avoid wafer breakage, we glued Si wafers together using a screening process. We successfully demonstrated this gluing/screening process. We tested for compatibility between glues (epoxies) and electrolyte. We made a honeycomb pattern using a Bosch etcher. We plated large gold (Au) current collectors and Au vias on the outer two wafers. We are completing the assembly of all battery elements.

- *Advanced packaging.* Our goal is to demonstrate high-density integrated circuit (IC) interconnect wafer stacking (i.e., no printed circuit boards) with MEMS heatpipe cooling of active components. The four-layer stack included a lens assembly, analog photodiode array, digital microcontroller, and MEMS heatpipe. The stack responded to laser signals and tracked movements of the laser (it also could serve as a simple sun sensor for satellite applications, or as an auto-tracking loop for laser communications). Activities also included software development of simple tracking algorithms.

- *Sparse-aperture applications study.* Activities involved updating and documenting the results of the study.

- *Nanosat deployment study.* Our goal was to develop a concept of operations for a reconnaissance nanosat. We developed the operations approach and the conceptual nanosat design to support this approach.

We successfully integrated the RF front end and microprocessor, and demonstrated that they can track eight GPS satellites simultaneously and obtain both position and carrier-phase information.

Refereed

Haschke, G. B., B. C. Brock, and R. M. Axline. 2001. "Test Report: Gain Analysis Tool for Sparse Antenna Array Using Nanosatellites." Sandia Technical Report SAND99-2314, Sandia National Laboratories, Albuquerque, NM (September).

Other Communications

Johnson, D. J., M. Pedroncelli, and J. Nevers. 2001. "Briefings: Reaction Wheel Assembly, GPS Carrier-Phase Attitude Control, Laser Communications System Status." Presentation to NRO/DOE partnership panel members, Los Alamos National Laboratories, Los Alamos, NM, June.

Wheelis, W. T. 2001. "Briefing: Monitoring Systems Overview." Viewgraph presentation given to Lockheed Martin Corporation (LMC) executives, Albuquerque, NM, 9 February.

Wheelis, W. T. 2001. "Briefing: Nanosat Laboratory Directed Research and Development (LDRD) at Sandia National Laboratories." Viewgraph presentation given to Ben Hart, et al, from the NRO, Albuquerque, NM, 1 August.

Wheelis, W. T. 2001. "Briefing: Nanosat Research and Development (R&D) Activities at Sandia National Laboratories." Viewgraph presentation to the Space Technology Alliance Microsatellite Working Group, sponsored by AFRL, Albuquerque, NM, 15 August.

Wheelis, W. T. 2000. "Briefing: Nanosat Research and Development (R&D) at Sandia National Laboratories." Viewgraph presentation given by AFRL at the Mighty SAT II IPT Mission Workshop, Seabrook, MD, 23 October.

Wheelis, W. T. 2001. "Briefing: Nanosat Research and Development (R&D) at Sandia National Laboratories." Viewgraph presentation given to Donald Fulop, Vice President of Business Development, Lockheed Martin Corporation Space Operations, Albuquerque, NM, 29 March.

Wheelis, W. T. 2001. "Briefing: Nanosat Research and Development (R&D) at Sandia National Laboratories." Viewgraph presentation to the Intelligence Advisory Panel (IAP), Albuquerque, NM, 20 March.

Wheelis, W. T. 2001. "Briefing: Nanosat Research and Development (R&D) at Sandia National Laboratories." Viewgraph presentation to NASA Glenn Research Center personnel, Albuquerque, NM, 5 April.

Wheelis, W. T. 2001. "Briefing: Nanosat Technology Development at Sandia National Laboratories." Viewgraph presentation to representatives of the Joint Space Demonstration Initiative (primarily AFRL personnel), Albuquerque, NM, 19 July.

Wheelis, W. T. 2001. "Briefing: Nanosat Technology Development Overview." Viewgraph presentation to W. Ken Fuchs, School of Electrical and Computer Engineering, Purdue University, Albuquerque, NM, 30 August.

Wheelis, W. T. 2000. "Briefing: Satellite/Sensor Activities at Sandia National Laboratories." Viewgraph presentation to the Lockheed Martin Corporation (LMC) Advanced Technology Center (ATC), Palo Alto, CA, 19 October.

Wheelis, W. T. 2000. "Briefing: Satellite/Sensor Activities at Sandia National Laboratories." Viewgraph presentation to Space and Missile Command (SMC)-XRD group on ongoing satellite development activities at Sandia, Los Angeles, CA, 6 December.

Wheelis, W. T. 2001. "Briefing: Satellite/Sensor Activities at Sandia National Laboratories." Viewgraph presentation to Vicente Garcia, Director, Cryptology Branch, Physical Sciences Laboratory at New Mexico State University (NMSU), Las Cruces, NM, 16 January.

Wheelis, W. T. 2000. "Briefing: Status of Nanosat Research and Development (R&D) Activities at Sandia National Laboratories." Viewgraph presentation to AFRL personnel involved in Tech SAT 21 satellite development, Albuquerque, NM, 20 December.

Wheelis, W. T. 2001. "Briefing: Status of Nanosat Research and Development (R&D) Activities at Sandia National Laboratories." Viewgraph presentation to an editor for *Aviation Week Magazine*, Albuquerque, NM, 21 February.

Wheelis, W. T. 2001. "Briefing: Status of Nanosat Research and Development (R&D) Activities at Sandia National Laboratories." Viewgraph presentation to NASA Johnson Space Center (JSC) personnel, Houston, TX, 13 March.

10724

High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications

J. C. Wehlburg, C. M. Wehlburg, D. M. Haaland, J. W. Daniels, D. A. Smith, N. G. Rackley

A technical need exists for staring infrared (IR) imaging systems capable of real-time, high-speed imagery in a large number of spectral bands. Existing spectral imaging technologies do not support these rates where mechanical scanning mechanisms are too slow. Techniques that employ electronic scanning methods and two-dimensional (2-D) focal planes are required. In addition, techniques that support changing spectral sampling on-the-fly are able to match changing target and background conditions, particularly when optimization of signal-to-noise ratio (SNR) is desired. Finally, under certain noise conditions, spectral multiplexing techniques have the potential of increasing the SNR and decreasing the sample rate for a given measurement.

Two-dimensional Hadamard transform spectral imaging approaches have the potential of achieving all of the above requirements. Recent advances in micromirror array technology have allowed the possibility of realizing these designs. The micromirrors allow electronic switching of light between optical systems necessary to realize the Hadamard encoding matrices without significant loss of light. Since these devices are electronically programmable, they allow the system to be spectrally reconfigured in microseconds. Under nonphoton noise-limited conditions, Hadamard techniques achieve a ($N^{0.5}$) SNR advantage over nonmultiplexed approaches, where N is the number of spectral samples.

This project will develop a prototype staring Hadamard Transform Spectral Imager operating in the 1.25 μm –2.5 μm spectral region using commercially available micromirror arrays. Successful completion of the project would require demonstration of the technique at high scan rates and the electronically tunable features required.

Sandia's goals for this project are to (1) finalize the optical design, (2) procure the optical, electrical, mechanical, and data-acquisition (DAQ) components, (3) continue simulation development as the optical model develops, and (4) finalize the mechanical design.

This project will develop a prototype staring Hadamard Transform Spectral Imager operating in the 1.25 μm –2.5 μm spectral region using commercially available micromirror arrays. Successful completion of the project would require demonstration of the technique at high scan rates and the electronically tunable features required.

The optical design is nearly complete. We made some changes in the design to improve the efficiency of the optical system. The people using the Texas Instruments digital micromirror device (DMD) as a selection device to limit the field of view for an astronomical telescope agreed to let us use, for the radiometric model of our system, a stray-light model that they developed for the DMD.

We will have to acquire and integrate the electrical and DAQ components, but the mechanical and optical components are on hold, awaiting finalization of the optical design. We continued to evolve the simulation and, as more information about the optical design is determined, are integrating the changes into the simulation. The mechanical design has been started, but is waiting on the optical design.

We continued to evolve the simulation and, as more information about the optical design is determined, are integrating the changes into the simulation. The mechanical design has been started, but is waiting on the optical design.

Refereed

Wehlburg, C. M., J. C. Wehlburg, S. M. Gentry, and J. Smith. 2001. "Optimization and Characterization of an Imaging Hadamard Spectrometer." *Proc. AeroSense 2001, Algorithms for Multispectral, Hyperspectral, and Ultraspectral Imagery VI* **4381** (August) (Orlando, FL, April): 506.

10747

Induced Molecular Markers for Pathogen Detection: Microincubators for Rapid Toxin Expression

J. S. Schoeniger, R. Behrens, Jr., J. V. Volponi, G. H. Kruppa, J. Hong, J. S. Brennan

Existing fielded technologies for detection of biological warfare (BW) agents rely primarily on antibody-based affinity assays to sensitively detect and identify agents. Programs such as the Department of Energy (DOE) Chemical and Biological Nonproliferation Program (CBNP) have identified the development of synthetic ligands that bind to BW agents in a manner suitable for affinity assays as an outstanding need for improving BW detection systems.

This project focuses on new technologies for mapping the binding site of ligands on target proteins and for the synthesis and rapid measurement of affinity constants of small-molecule ligands for BW agent proteins. Project goals are to implement bioanalytical methods that provide an infrastructure for the development of high-affinity ligands that can be used for the detection of biological agents. The work involves development of technologies to enable new approaches to ligand development that, if successful, will expand Sandia's ability to deliver synthetic ligands for BW agent detection.

We demonstrated capabilities to enable synthesis of ligands. We are screening ligand libraries to determine if they bind to target proteins and where they bind on the target protein. We demonstrated the use of combinatorial chemistry for the creation of new affinity ligands for biological agents. We demonstrated sophisticated mass spectrometry (MS) and fluorescence anisotropy methods for analysis of noncovalent complexes that are useful for the screening of binding of potential ligands to protein targets. We implemented the infrastructure for mapping ligand binding sites on proteins using proteolysis, liquid chromatography (LC), and Fourier-transform (FT) MS for the analysis of photoaffinity ligand adducts.

- *Ligand synthesis.* Through a collaboration with North Carolina State University, we demonstrated the use of combinatorial peptides for the discovery of affinity ligands for detection of biological agents, specifically *Staphylococcal*

This project focuses on new technologies for mapping the binding site of ligands on target proteins and for the synthesis and rapid measurement of affinity constants of small-molecule ligands for BW agent proteins. Project goals are to implement bioanalytical methods that provide an infrastructure for the development of high-affinity ligands that can be used for the detection of biological agents.

enterotoxin B (SEB). SEB was ^{13}C radio-labeled using reductive methylation, incubated with combinatorial bead-based peptide libraries, then spread on photographic plates and exposed. Beads were harvested corresponding to spots on the developed plates where labeled SEB bound to the beads. Repeated screenings revealed low-affinity peptide ligands followed by the discovery of a high-affinity ligand (better than micromolar) of a similar amino acid composition but different sequence order than the group of low-affinity ligands. Additionally, we established a synthetic chemistry laboratory at Sandia-California for the synthesis of novel cross-linkers useful for development of high-affinity bidentate ligands starting from peptide monomeric ligands.

- *Ligand screening.* We implemented electrospray/MS of noncovalent protein-ligand complexes using our FT-ICR (ion cyclotron resonance) instrument. We showed that we can detect both small-molecule protein complexes and protein-protein complexes over a wide mass range from about 30 to 200 kD. (These complexes are among the largest masses of complexes ever detected using FT-ICR.) We integrated this with a microautosampler that will allow the high-throughput screening of soluble combinatorial libraries. Additionally, we completed our fluorescence anisotropy instrument and demonstrated that it is capable of discriminating a range of fluorescent molecules from free fluorescence through 3–70 kD fluorescent dextrans. This instrument will allow the identification of noncovalent complexes in solution and measurement of their affinity complexes.

- *Ligand mapping.* We implemented a variety of proteolysis/LC/MS methods that allow the identification of modified peptides. We also partially characterized two photoaffinity labeling reagents (perfluoro azidobenzenes, and diazerenes) in terms of their soluble photoreaction products and synthesized known peptide ligands to tetanus toxin. Experiments are under way to synthesize photoaffinity versions of these peptide ligands and to define the binding site of the ligand by identifying which peptides in the protein are modified upon ligand binding and ultraviolet-induced photoconjugation.

... we established a synthetic chemistry laboratory at Sandia-California for the synthesis of novel cross-linkers useful for development of high-affinity bidentate ligands starting from peptide monomeric ligands.

10762

Self-Assembled, Tamper-Detection Seals

*W. R. Even, Jr., I. G. Waddoups, P. M. Dentinger, E. B. Cummings,
W. R. Cordwell, C. E. Lee, B. A. Simmons*

Tamper-indicating devices (TIDs) contribute to consumer assurances related to food and medicine quality, validate the accuracy of electric-power meter readings, and assist in the control and accountability of special nuclear materials (SNM). Due to a wide variety of applications and TID technology losses to successful countermeasures, seal implementation efforts require a constant stream of new and innovative solutions to an ever-changing set of requirements. Sandia's work generates individually unique tamper-indicating seals with the ability to be authenticated and reset; optical activity is used as a covert authentication scheme. We successfully demonstrated thermal resettability in a preliminary seal. Initial research utilized a commercially available polymer, polyethylene phthalate, as a thermally resettable host. We incorporated metallized polyethylene terephthalate (MPET) particles as guest particles to provide a unique spatial signature and used sucrose as chiral species to provide a covert optical rotatory signature. Initial selection of this combination of materials allowed research in detection methodologies to proceed independent of final materials down-select; additional covert optical signature materials are being investigated. In collaboration with Symbol Technologies, we identified a detection scheme that could lead to the integration of these seals with high-speed, commercially available barcode scanners. This significantly reduces the effort required to employ these seals and holds the potential for resettable seals to be read in less than 1 sec at distances up to 10 feet.

After testing many commercially available materials, we selected a polyvinyltoluene/methylstyrene host material for tag development while we pursue advanced materials with improved stability and easier resettability. Commercially available 90 μ fluorescein-labeled polystyrene microspheres will be the initial guest particles. Their fluorescence is clearly imaged and distinguishable from the nonfluorescent tag image at 1 m using the prototype tag reader. We successfully purified these spheres and encapsulated them in the host material for tag testing. We imaged and evaluated surrogate tags having a range in particle concentrations, providing us with a target

... we identified a detection scheme that could lead to the integration of these seals with high-speed, commercially available barcode scanners. This significantly reduces the effort required to employ these seals and holds the potential for resettable seals to be read in less than 1 sec at distances up to 10 feet.

particle concentration. We structured the tag-reading software and tag architecture to support multiple levels of security by interspersing multiple types of particles that are distinguishable when illuminated at different wavelengths (e.g., a mixture of green and red fluorescent and black absorptive particles). The flexibility embodied in this structure minimizes technical risk while extending the mission space of the tags.

The central issue in developing a fieldable tag is the ability to process images acquired at oblique incidence and a range of distances, and rotations of tags that are illuminated nonuniformly and are mounted on curved and otherwise complicated surfaces (e.g., over a weld line or seam). We invented a novel spread-spectrum method of distributing fiduciary information across an image. This information robustly allows correction of these imaging defects in spite of superimposed particles. The technique also supports secure information embedding and retrieval. We documented it in the Sandia technical advance (SD-8326) for which we filed the patent “Self-Registering Spread-Spectrum Barcode Method.” This kind of barcode has a number of novel features: It can be overprinted, damaged, and partly or mostly obscured without loss in readability. Multiple datasets can be multiplexed on the same barcode with access requiring the correct pseudorandom encoding kernel.

We are evaluating the security of our tag and barcode methodology and assessing the susceptibilities and weaknesses of our approach.

Other Communications

Cummings, E. B., and W. R. Even. 2001. “A Self-Registering Spread-Spectrum Barcode.” Technical advance SD-8326, Sandia National Laboratories, Livermore, CA (December).

Cummings, E. B., and W. R. Even. 2001. “Self-Registering Spread-Spectrum Barcode Method.” Patent application SD-8326, Sandia National Laboratories, Livermore, CA (June).

We invented a novel spread-spectrum method of distributing fiduciary information across an image.

This information robustly allows correction of these imaging defects in spite of superimposed particles. The technique also supports secure information embedding and retrieval.

21280

Techniques for Improving and Exploiting MTI Imagery

B. R. Stallard, L. A. Boye

The Multispectral Thermal Imaging (MTI) satellite, developed by Sandia and Los Alamos National Laboratories, was launched in March 2000. MTI images in 15 accurately coregistered bands from 0.5 μm to 11 μm , with 5 m ground sample distance (GSD) in the four short-wavelength bands and 20 m GSD in the rest. A thrust of this development has been the radiometric calibration of these bands. Sandia will develop algorithms specific to MTI for producing land-surface temperature maps with unprecedented accuracy from a spaceborne sensor. In the thermal infrared (IR), the photons arriving at the sensor carry convoluted temperature and emissivity information that must be unraveled. We will produce pixel materials maps from the spectra in the 0.5 μm –2.5 μm region. The emissivity can then be estimated and the surface temperature and heat capacity calculated. Many targets of interest are subpixel in the thermal bands. Lack of data has limited demonstration of this approach with accurate pixel coregistration over a wide spectral range. We plan to improve the accuracy of the temperature map by using the spatial content of the small GSD bands of MTI, and higher-resolution images from other platforms, to enhance the effective spatial resolution of the thermal bands. Temperature maps will provide information useful for DOE nonproliferation programs, military intelligence, surveillance, crop monitoring, meteorological and climate monitoring, forestry, and ecology.

This work includes the enhancement of band co-registration, the implementation of radiometric calibration, and the correction of geometric distortion. This will result in (1) improved data cubes capable of supporting advanced data exploitation algorithms and (2) insight into the pre-processing requirements.

One focus of this Sandia project was improved band-image-to-band-image registration for the data cubes from the MTI satellite. We produced and reported on adequate software at the Society of Photooptical Instrumentation Engineers' (SPIE) AeroSense Conference. We made further improvements in this software with other funding, and we

Sandia will develop algorithms specific to MTI for producing land-surface temperature maps with unprecedented accuracy from a spaceborne sensor.

expect a robust product soon. Team members requested a number of MTI special collections, resulting in the collection of approximately 20 images pertinent to our work. In addition, several high-resolution images were acquired and compared to MTI imagery. Finally, we made progress in the application of MTI images to change detection. This requires a careful registration of the images taken in the same band but separated in time. Full automation is not yet accomplished; however, we now have a procedure for hand alignment to about one-half pixel, followed by computer alignment to about one-eighth pixel.

... we made progress in the application of MTI images to change detection.

Other Communications

Hoffman, M. M., B. R. Stallard, and L. A. Boye. 2001. "Update on MTI Results." Paper presented to the Collection Planning Conference, Las Vegas, NV, June.

Smith, J. L., S. E. Motomatsu, J. G. Taylor, K. J. Jefferson, and B. R. Stallard. 2001. "Semi-Autonomous Registration of Satellite Imagery Using Feature Fitting." *Proc. SPIE AeroSense, Society of Photooptical Instrumentation Engineers: Algorithms for Multispectral, Hyperspectral, and Ultraspectral Imagery VII* **4381** (August) (Orlando, FL, March): 447–454.

Stallard, B. R., S. E. Motomatsu, J. G. Taylor, J. L. Smith, L. A. Boye, and M. M. Hoffman. 2001. "Detection Algorithms for the Multispectral Imager: Preprocessing Issues." Sandia Technical Report SAND2001-2153, Sandia National Laboratories, Albuquerque, NM (July).

26558

Risk-Informed Proliferation Analysis Development

G. E. Rochau, C. W. Morrow, Jr., D. S. Blair, T. T. Sype, G. D. Wyss, P. E. Rexroth

Proliferation risk for fissile materials—along with cost and safety—are the top three aspects surrounding future global-energy options. Current methods for assessing proliferation risk are lacking in quantitative rigor; this shortcoming increases the difficulty of assessing proliferation risk in national decision processes. National advisory groups have endorsed developing a consistent and comprehensive assessment methodology to address proliferation in global civilian nuclear-energy systems. Keeping proliferation-resistance development in balance with safety, environmental impact, and the economy was cited as essential. Research and development are needed to find quantitative methods that achieve proliferation-resistance goals and lead to insights on where more, as well as fewer, resistance measures for both civilian and defense applications would be cost-effective.

Sandia developed a systematic “risk-informed” methodology to assess proliferation implications by using probabilistic risk assessment (PRA) techniques. Risk-informed proliferation-analysis (RIPA) methodology provides a framework to systematically characterize and quantify the potential for proliferation risk by incorporating both PRA and supporting analysis methods. These analytical techniques include vulnerability analysis, influence diagrams, and event trees as appropriate to the overall framework. The RIPA-methodology outcome provides an estimate of proliferation-consequence risk for a defined set of proliferator and system configurations in terms of cost, time, detection, and success. We developed a proof-of-concept model using flow charts to describe the commercial nuclear-fuel cycle proliferation paths leading to nuclear weapon construction.

We achieved all planned activities, which contributed to the development of the RIPA methodology.

(1) *Define a RIPA methodology.* We examined the historical development of PRA to form the basis of RIPA. The RIPA methodology builds on traditional assessment methods to produce a new approach to proliferation-assessment problems. Our approach uses deductive reasoning similar to

Sandia developed a systematic “risk-informed” methodology to assess proliferation implications by using probabilistic risk assessment (PRA) techniques. Risk-informed proliferation-analysis methodology provides a framework to systematically characterize and quantify the potential for proliferation risk by incorporating both PRA and supporting analysis methods.

that used for fault-tree analysis to construct an influence diagram. The influence diagram encompasses all major pathways that a proliferator might use to accomplish objectives (including to conduct analyses, to defeat a particular technological barrier, or to develop a complete weapons program). The completed influence diagram can be solved using techniques from event-tree analysis to gain the complete set of possible proliferation pathways represented in the diagram. When the scenario is defined, we can compute scenario characteristics by combining the characteristics of the underlying step options. Using proliferator objectives (e.g., desired number of weapons, production rate), we can compute the cost and time required to accomplish those objectives by using the options defined in the scenario. We can also estimate the likelihood that the scenario can be accomplished and without being detected (if a covert program is required). This process can be repeated for all option combinations, resulting in scenarios either for a selected proliferation pathway or for all such pathways generated above.

(2) Define the characteristic metrics of proliferators.

To avoid classification issues, we examined the various options for proliferators and limited our options to those defined in current regulations. However, we learned that all proliferation analyses are performed within the context of a specific proliferator. In general, characteristics that define proliferator intent must be specified initially to limit the analysis.

(3) Identify relevant factors and parameters. We identified the factors and parameters associated with each step of the proliferation path. In general, each part of the process—from obtaining nuclear material to fabrication of a weapon—is parametrically evaluated for cost, time, detection, and success potential. Additionally, we looked at process rates and options.

(4) Describe RIPA methodology implementation. The RIPA methodology can be implemented at any level of detail. The initial requirement is a process flow sheet for achieving proliferator. This sheet generally includes material and/or technology acquisition, fabrication steps, and options. The methodology includes options for theft and purchase of process components and materials. The methodology also includes the traditional vulnerability assessments and response-force actions. We diagram these components in an influence diagram to begin the analysis. We combine specific data with the influence diagram in a specially developed computer code, PINON, to generate and evaluate all

The RIPA methodology can be implemented at any level of detail. ...

The methodology also includes the traditional vulnerability assessments and response-force actions. We diagram these components in an influence diagram to begin the analysis.

proliferation scenarios. Proliferator characteristics are fed into PINON to limit the number of scenarios. We present the results in tables of cost, time, detection, and success potential for each scenario.

(5) Apply the RIPA methodology to a test problem. We chose diversion of plutonium from the once-through nuclear-fuel cycle to demonstrate the methodology. The demonstration examines the scenarios and generates plots of data to evaluate the most likely scenarios for decision makers.

We present the results in tables of cost, time, detection, and success potential for each scenario.

26559

Development of a Microoptic Gyroscope

R. D. Kinney, W. J. Zubrzycki, E. B. Duckett, J. T. Spooner, G. A. Vawter

Sandia uses gyroscopes for a spectrum of weapon-system-related applications. Technological progress in some important Sandia application areas depends on the availability of smaller, more-rugged gyros of the moderate-accuracy class. Examples include future joint-test assemblies, which will require inertial systems with volumes of a few cubic inches and that can withstand the rigors of reentry.

The need to minimize instrumentation impact on weapon-system dynamics drives the requirement for small-device volume. Yet accuracy must be sufficient to allow post-flight reconstruction of the trajectory without resorting to using expensive range assets such as radar stations. On the drawing board are small micro synthetic-aperture radars (SARs), which will require very small inertial sensors of at least moderate accuracy.

Because of superior ruggedness and reliability as well as lower cost, most gyros in use today are optical gyros. Suitable microoptical components (such as lasers) that could be applied to a microoptical-gyro concept are lacking. This lack has thwarted attempts to miniaturize optical gyros. Recent progress in photonic integrated-circuit (PIC) optical technology at Sandia opens a door to a practical and accurate resonant microoptic gyro (RMOG). Sandia has been a leader in developing necessary components such as semiconductor lasers, low-loss waveguides, PICs, and improved frequency modulators. These advances give Sandia a tremendous advantage toward developing a microoptic gyro.

The project goal is to further develop and apply technologies toward the development of a microoptic gyro. The gyro performance will be aimed at tactical-grade applications such as battlefield munitions, SARs, and micro-unmanned aerial vehicles.

The project goal is to further develop and apply technologies toward the development of a microoptic gyro. The gyro performance will be aimed at tactical-grade applications such as battlefield munitions, SARs, and micro-unmanned aerial vehicles.

We developed a breadboard resonant fiber-optic gyroscope (RFOG).

Our accomplishments include a model for two RFOG concepts based on first-principles, selection and ordering of the commercial off-the-shelf (COTS) components for a breadboard demonstration of an RFOG built from commercial components, testing of the components that were received,

and preliminary design of the custom feedback circuitry. A supplier was unable to deliver a key component in our original breadboard design, so we modified our design and are currently still one COTS component short of all the required components to build the breadboard.

*... we modified our design and
are currently still one COTS
component short of all the
required components to build
the breadboard.*

26560

Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation

D. S. Strong, R. D. Wickstrom, R. L. Schmidt, E. N. Reckase, J. L. Smith, R. E. Pepping

Accurate characterization of strategic intelligence sites is a critical and challenging problem. Sandia proposes exploring the synergistic exploitation of multispectral transient radiometry (MSTR) and multispectral-imaging (MSI) data to attain absolute geolocation to subpixel accuracies (potential improvement by more than two orders of magnitude). We will develop registration techniques that exploit emissive-multispectral signatures coupled with reflective signatures and will perform multispectral registration based on a number of simultaneous spectral bands. These techniques have potential to significantly outperform traditional techniques for scenes with low-intensity signatures, for which operations on a single spectral band are insufficient. Fusion of the resultant data addresses critical national-security challenges, including nonproliferation, surveillance, and global-situational awareness.

A dwelling MSTR affords an impressive broad-area search and surveillance capability for important targets and an ability to characterize transient events, but with limited spatial resolution. An MSI affords orders-of-magnitude of improved spatial resolution, in addition to high-fidelity spectral signatures. However, MSI sensors cannot dwell and have a comparatively small field of view (FOV). For global virtual presence, an innovative combination of the two technologies could yield information necessary for very accurate geolocation and scene/site characterization (e.g. battle-damage assessment [BDA]).

With expertise and ready access to MSTR and MSI systems, Sandia is uniquely positioned to exploit the combined phenomenology. To enhance geolocation, an MSTR could detect the site of interest (e.g., smoke stack, exploding bomb, fire) and cue the MSI, which would then—through thermal and spectral signatures—locate the target to higher accuracy. A proof-of-principle demonstration could be in BDA: The

Accurate characterization of strategic intelligence sites is a critical and challenging problem. Sandia proposes exploring the synergistic exploitation of multispectral transient radiometry (MSTR) and multispectral-imaging (MSI) data to attain absolute geolocation to subpixel accuracies (potential improvement by more than two orders of magnitude). ... With expertise and ready access to MSTR and MSI systems, Sandia is uniquely positioned to exploit the combined phenomenology.

MSTR detects and locates the transient event, the MSI could be cued from coarse MSTR-geolocation information, and the MSI could assess and feed back the accurate target geolocation to the MSTR. The MSI could provide additional spectral and thermal site characterization.

Sandia has achieved all planned milestones. Significant accomplishments include orchestrating collections between an MSI and an MSTR, calibrating and correcting each dataset for various sensor artifacts, and developing algorithms and software to orthonormalize the data to facilitate downstream processing.

In support of these efforts, we conducted a thorough review of traditional MSI research for applicability to registration of scenes collected in thermal bands. We produced a summary report. This research has led to three candidate techniques that are being adapted and applied to the MSI and MSTR datasets. The registration techniques are multispectral normalized correlation (MSNC), multispectral principal components, and multispectral feature registration. Based on our research, we believe that these novel and unique techniques show promise.

Initial application of the MSNC technique to two selected datasets showed results consistent with expectations. The first dataset, which was of high contrast (considered to be less challenging), involved the MSTR system detection of a set of transient events. We performed MSNC between the two systems and demonstrated an order-of-magnitude improvement in geolocation accuracy. This level of geolocation accuracy is required for detailed BDA.

The second case (which we consider more stressing) involved a nearly full-cloud-covered scene. In this case we applied MSNC across six different spectral bands simultaneously. Although there was insufficient information in any single band to perform the registration, exploiting the multiple spectral bands simultaneously made the registration possible.

Significant accomplishments include orchestrating collections between an MSI and an MSTR, calibrating and correcting each dataset for various sensor artifacts, and developing algorithms and software to orthonormalize the data to facilitate downstream processing.

26561

New Glass Technology for Enhanced Architectural Surety

S. J. Glass, C. S. Newton, R. G. Stone, E. K. Beauchamp, C. S. Watson, M. G. Vigil, S. S. Kamat

Glass is extremely sensitive to any defect that produces a stress concentration. The size of the worst defect normally controls glass strength. The worst defect and, therefore, glass strength can vary considerably from sample to sample. The implications of this behavior are that glass fractures catastrophically at stresses that are considerably below the theoretical glass strength; the failure-stress variability is unacceptably high (approximately 25 percent).

A new, two-step ion-exchange process—which results in a high-compressive stress just below the glass surface—overcomes the strength-variability and catastrophic-failure problems for glass. In this engineered-stress profile (ESP), glass cracks initiate only at high stresses, and cracks subsequently arrest. Strength distributions for ESP glass are very narrow, and the glass fragments are small. The process has been used for both specialty-glass compositions and soda-lime silica glass (PPG).

Project goals are to understand the behavior of ESP glass in architectural-surety applications and to provide engineers and architects with a glass having less lethal behavior under blast and other dynamic loading. The long-term impact of the project is to provide a new generic approach to improve glass reliability and modify its fracture behavior.

Sandia made laboratory-size and large-scale (15-inch by 15-inch) samples of ESP glass from a commercially available soda-lime silica glass and a sodium-aluminosilicate glass (Corning) by using the two-step ion-exchange process. The large-scale samples were made in a manufacturing facility, and their properties were very similar to those of laboratory samples. This demonstrated that the double-exchange process can be scaled to sizes that are representative of glazing applications. We measured the strength, strength variability, and multiple-cracking behavior for both glasses. Tests that measure the glass strength after the surface had been abraded or modified with indentation flaws showed that ESP glass is insensitive to normal surface damage.

Project goals are to understand the behavior of ESP glass in architectural-surety applications and to provide engineers and architects with a glass having less lethal behavior under blast and other dynamic loading. The long-term impact of the project is to provide a new generic approach to improve glass reliability and modify its fracture behavior.

We developed a technique to quantify the density of surface cracks that form prior to failure. We measured the loading-crack densities for samples tested at various loading rates in strength tests. We made finite-element calculations of the effects of various crack densities on crack shielding. We predicted the forces to propagate the final crack for various crack densities and compared them to the experimental results.

We designed and built hardware to test lab-scale ESP glass samples under blast-loading conditions. We calculated the predicted failure pressures and the scaling behavior of the explosive charges. This was done to estimate the blast parameters needed to cause glass failure. We tested samples with three different charge sizes as a function of the explosive standoff distances. We used the initial tests to estimate the pressure and pressure-impulse loads to cause failure of large-scale tests conducted for the U.S. Air Force. We used subsequent tests to compare the blast-failure pressures and behavior of one of the ESP glasses to annealed glass of the same composition. The differences in the blast-failure pressures between the ESP and the annealed glass are similar to those found in static-pressure tests.

We also investigated new processes to produce ESPs including field-assisted ion exchange and a combination of an ion exchange and thermal treatment. Both processes provide a faster means to make glasses with the desired stress profiles. The processes may also provide the opportunity for greater control over the stress profiles. The field-assisted ion exchange produced very high stresses in the surface of the sample to which it was applied. Because of the asymmetry in the stress profile, we had to evaluate and use new measurement techniques for samples processed using this approach.

We developed a technique to quantify the density of surface cracks that form prior to failure. ...

We designed and built hardware to test lab-scale ESP glass samples under blast-loading conditions. We calculated the predicted failure pressures and the scaling behavior of the explosive charges.

Other Communications

Abrams, M. 2001. "Processing and Properties of an Engineered-Stress Profile Soda-Lime Silica Glass." Master of Science Thesis, Pennsylvania State University, University Park, PA (September).

Glass, J. S. 2001. "Effects of Loading Conditions and Environment on the Mechanical Performance of Engineered-Stress Profile (ESP) Glasses." (Invited) Talk at PPG Technical Center, Pittsburgh, PA, 19 September.

Glass, S. J. 2000. "Reliability of Ceramics and Other Brittle Materials—The Way It Is and Unique Opportunities." (Invited) Presentation to seminar at New Mexico Institute of Mining and Technology, Socorro, NM, 25 October.

Glass, S. J., E. K. Beauchamp, C. Newton, and S. Kamat. 2001. "Effects of Environmental and Loading Conditions on the Mechanical Performance of Engineered-Stress Profile." Paper presented to the 103rd Annual Meeting of the American Ceramic Society, Indianapolis, IN, 22–25 April.

Newton, C. S., S. J. Glass, E. K. Beauchamp, D. J. Green, M. Abrams, and V. Sglavo. 2000. "Engineered-Stress Profile (ESP) Glasses—Breaking the Ceramic-Reliability Paradigm." Paper presented to the 12th Annual Rio Grande Regional Symposium on Advanced Materials, Albuquerque, NM, 16 October.

Watson, C. S. 2001. "Modification of Glass Properties Using Ion-Exchange Techniques." Master of Science Thesis, New Mexico Institute of Mining and Technology, Socorro, NM (May).

26562

Compact UV Laser Source for Chemical and Biological Sensing

D. A. V. Klinner

Sandia is developing a compact source of tunable ultraviolet (UV) radiation for high-sensitivity detection of trace species. This work emphasizes biological-warfare (BW) agents. Our research exploits recent advances in fiber lasers (originally developed for telecommunications) to possibly make instrumentation that is significantly smaller, more efficient (less power-consumptive), and less expensive than current technology allows. Specifically, we are developing a pulsed, near-infrared (NIR) (approximately 1020 to 1120 nm), ytterbium (Yb)-doped fiber laser, which will be frequency-quadrupled to the UV (approximately 255 to 280 nm) spectral region. Based on a pilot study, UV powers of several milliwatts are attainable.

The proposed laser is well suited to detect BW agents by using laser-induced fluorescence (LiF) of tryptophan, for which 266 nm radiation (frequency-quadrupled Nd:YAG laser) is often employed.

The proposed system offers several advantages:

- (1) Access to the peak of the approximately 280 nm tryptophan-absorption band*
- (2) Tunability, for avoiding interferences*
- (3) External triggering, allowing the repetition rate and timing of the optical pulses to be synchronized to external sources (e.g., to detect individual bio-aerosols).*

Furthermore, the fiber laser may be frequency-quintupled to gain access to the 220 nm absorption band of tryptophan (a factor of approximately eight larger than the 266 nm absorption) as well as absorption bands of the amino acids tyrosine and phenylalanine.

Previously, we worked on a fiber-based silicon oxide (SiO) sensor for the National Aeronautics and Space Administration (NASA). The present research, which significantly leverages the prior work, will position Sandia to apply this revolutionary new technology to BW-agent detection. Moreover, the unique combination of physical and spectral characteristics of the fiber-based laser system will enable development of a new generation of lightweight, rugged, fast-response (real-time) chemical sensors for a wide variety of applications.

Sandia is developing a compact source of tunable ultraviolet (UV) radiation for high-sensitivity detection of trace species. This work emphasizes biological-warfare (BW) agents.

We developed a polarization-maintaining, double-clad, Yb-doped fiber, which maintains the linear-polarization state of an incident-seed beam (unlike conventional optical fibers that scramble the polarization). We developed this fiber in collaboration with a specialty fiber company. The fiber has been thoroughly characterized; we measured the polarization beat length (i.e., the birefringence), the absorption spectrum for light propagating in the inner cladding (i.e., pump light), and the mode field diameter. We tested both single-mode (SM) and multimode (MM) versions of the fiber (the latter being appropriate for scaling to high peak and average powers using a distributed-mode filtering technique that we developed recently).

We constructed high-power amplifiers using the above fibers. The SM amplifier had a continuous-wave output power of 1.1 W (limited by the available pump power), and the MM amplifier provided 3.5 W. For both amplifiers, we measured the threshold, slope efficiency, and polarization-extinction ratio. For the MM amplifier, we also measured the small-signal gain spectrum and the M2 value (a measure of beam quality).

We developed a Q-switched, Yb-doped, double-clad fiber laser. We obtained an output peak power of 2 kW at repetition rates of up to 5 kHz. This laser used a bulk Pockels cell for Q-switching, which limited the maximum repetition rate. The pulse duration was 5.5 ns. Tunability of more than 40 nm was provided by a dichroic filter in the cavity. The gain fiber was pumped with a 975 nm diode using the technique of V-groove side-pumping, thus providing efficient coupling of the pump light into the inner cladding, leaving the fiber ends unobstructed and permitting compact packaging of the amplifier.

We obtained an output peak power of 2 kW at repetition rates of up to 5 kHz. This laser used a bulk Pockels cell for Q-switching, which limited the maximum repetition rate. ... The gain fiber was pumped with a 975 nm diode using the technique of V-groove side-pumping, thus providing efficient coupling of the pump light into the inner cladding, leaving the fiber ends unobstructed and permitting compact packaging of the amplifier.

Refereed

Kliner, D. A. V., J. P. Koplow, L. Goldberg, A. L. G. Carter, and J. A. Digweed. 2001. "Polarization-Maintaining Amplifier Employing Double-Clad Bow-Tie Fiber." *Optics Letters* **26** (15 February): 184–186.

Other Communications

Kliner, D. A. V., J. P. Koplow, and L. Goldberg. 2001. "Rare-Earth-Doped Fiber Lasers and Amplifiers for Chemical Sensing in the IR and UV." Paper presented to the NASA Earth Science Enterprise Technology Planning Workshop, Arlington, VA, 23–24 January.

Kliner, D. A. V., J. P. Koplow, L. Goldberg, S. W. Moore, T. J. Kulp, U. B. Goers, K. M. Armstrong, R. L. Sommers, and S. R. Birtola. 2001. "High-Power Fiber Sources for *In Situ* and Remote Detection of Trace Species." *Proc. NASA Earth Science Technology Conference* CD-ROM (College Park, MD, 28–30 August).

26563

Advanced Digital Detectors for Neutron Imaging

F. P. Doty, D. A. Chinn

Neutron radiography is an important nondestructive evaluation (NDE) method that provides unique information valuable for Sandia's mission in nonproliferation and materials control. Also, neutron radiography has important applications addressing airport security, protein structure, corrosion detection, and medicine. Neutrons probe deep inside massive objects to detect small defects and chemical composition, even through high-atomic-number materials such as lead. This project applies Sandia's recent advances in semiconductor radiation-detection materials to develop the first direct digital-imaging detectors for neutron radiography.

Current approaches are limited to scintillator-based systems relying on externally coupled photon-detection schemes that seriously limit the performance; performance is limited because of the inefficiencies inherent in photon generation and transport to the detector and because of the classical trade-off between spatial resolution and stopping power in scintillator systems. Sandia's approach relies on new solid-state sensor materials that convert neutrons directly to electronic signals through reactions

Charges generated in the conversion process are sensed directly in the conversion material, eliminating the losses associated with scintillators and resulting in large improvements in both quantum efficiency and spatial resolution.

Currently, the focus is to address fabrication issues in the candidate materials. We fabricated the most promising detectors on pyrolytic boron nitride (hBN) from the vendor Advanced Ceramics. We received and tested samples of four distinct types of hBN. Other materials tested include borates, lithium fluoride, and organic materials. Synthesis of lithium tetraborate films by a gel-casting technique was successful, and the structure was verified by x-ray diffraction (XRD).

We evaluated both as-deposited and annealed contacts for electrical performance. In addition, we evaluated

This project applies Sandia's recent advances in semiconductor radiation-detection materials to develop the first direct digital-imaging detectors for neutron radiography.

compatibility with standard microlithographic methods for the more promising materials. The most significant process advance is annealed titanium/gold (Ti/Au) on hBN. Annealing produces a linear behavior and removes asymmetry observed in reverse bias, indicating ohmic behavior. This is important to ensure uniform electric-field distribution throughout the device volume.

We evaluated prototypes with thermal neutrons produced by a nuclear reactor, using standard nuclear electronics. We evaluated performance of the various detector types fabricated to date and eliminated or ranked approaches according to efficacy.

We currently are performing detailed evaluation of application-specific integrated-circuit (ASIC) compatibility. Because of the low capacitance and extremely low leakage currents in hBN devices, extremely low noise performance is achievable, and compatibility with existing ASIC technology is expected.

The most significant process advance is annealed titanium/gold (Ti/Au) on hBN. Annealing produces a linear behavior and removes asymmetry observed in reverse bias, indicating ohmic behavior. This is important to ensure uniform electric-field distribution throughout the device volume.

26564

Microfabricated Acoustic Spectrum Analyzer

W. K. Schubert, D. R. Adkins, T. A. Friedmann, M. A. Mitchell, C. L. Willison, M. A. Butler, R. J. Shul, L. F. Anderson, D. C. Graf, J. P. Lucero

Sandia will develop a microfabricated acoustic-spectrum-analysis (MASA) chip for covert and remote monitoring. Full acoustic-spectrum analysis and even voice recognition can be accomplished by using a small microphone and extensive post-acquisition data processing. However, this slow, power-hungry process is difficult to miniaturize and implement in limited-access, hostile- or covert-environment situations.

This project will develop the basic technology to detect and recognize audible sound with a single chip. The envisioned MASA chip comprises a miniature microphone for pick-up, a frequency-mixing system to shift the signal to higher frequencies, and an integrated array of passive-resonant elements used to separate the frequency-shifted signal into its primary components. Each resonant element in the array will be tuned to detect sounds in a particular narrow frequency band. Through careful choice of sensitivity bands, the technology should be able to identify preselected (target) sounds having characteristic spectral features in the chosen frequency ranges. Pattern-recognition (PR) methods could be applied to the array response to discriminate between various sounds and to trigger an appropriate reaction; this capability could eliminate the extensive computational requirements for full-blown spectrum analysis. Even speech recognition should be obtainable with an adequate number of array elements. (Twenty bands are used in some telecommunications technology.)

The particular challenge in this application is to achieve adequate sensitivity at audio frequencies with resonators small enough to facilitate an array on a single chip. Success in this venture should provide critical building blocks for miniature acoustic-sensor systems capable of both covert and remote monitoring.

Sandia has made significant technical progress in all major project areas. We met all major milestones and achieved the key proof-of-concept demonstration for the MASA project.

Two Microresonator Technologies

The micrograph in the left panel shows a fundamental-mode flexural plate-wave (FPW) device. The 2 mm diameter FPW membrane is 0.5 micron thick. The right panel shows a surface-micromachined xylophone comprising a composite bar (amorphous diamond coated with gold) suspended by thin arms above polysilicon capacitance plates. Both devices are driven by a Lorentz force arising from the interaction of an AC current with a static magnetic field oriented perpendicular to the current in the plane of the device.

This project will develop the basic technology to detect and recognize audible sound with a single chip.

Microresonators (modeling, design, fabrication, and testing). We designed, fabricated, and tested prototypes of the two basic types. The first type of resonator is the fundamental-mode flexural plate-wave (FPW) resonator. These membrane devices have shown outstanding performance (bandwidth of 5 Hz at a resonant frequency of 50 kHz) when run in vacuum. This is more than adequate to resolve closely placed target frequencies.

The second type of resonator is the microxylophone. We designed, fabricated, and tested several generations of xylophones. We used both surface- and bulk-micromachining techniques and investigated a variety of material combinations. We measured the acoustic performance using an optical method. We used design-of-experiment methods to investigate the effects of various design parameters on the xylophone-performance characteristics and used the results to guide later design iterations. Second-generation microxylophones incorporated a capacitive-readout scheme that requires that the xylophone structure be suspended 1μ to 2μ above a fixed polysilicon-capacitor plate. This close spacing led to unexpectedly large damping effects not seen in the first-generation devices at atmospheric pressure. We verified operation under vacuum conditions using the optical readout scheme mentioned above, but were unable to demonstrate a capacitance readout scheme. These results indicate that the surface-micromachined xylophones will have to be vacuum-packaged to achieve narrow bandwidth. We demonstrated arrays of 14 resonators on a single die and could easily increase this number by a factor of two or three.

We also developed designs and submitted them through the Sandia Agile MEMS (microelectromechanical systems) Prototyping, Layout Tools, Education, and Services (SAMPLES) program in Sandia's Ultraplanar Multilevel MEMS Technology (SUMMiT V). Some wafers will be removed part way through processing to investigate methods for incorporating strain-gauge readout structures on top of the xylophone bars.

We developed finite-element (FE) analysis and equivalent circuit models for the various versions of the xylophone microresonators. These models allow us to investigate the effects of various design variations and material combinations on the operation of the devices. The equivalent circuit models suggested methods to adjust the bandwidth and resonant frequency of the devices through external circuit elements.

The first type of resonator is the fundamental-mode flexural plate-wave (FPW) resonator. These membrane devices have shown outstanding performance (bandwidth of 5 Hz at a resonant frequency of 50 kHz) when run in vacuum. This is more than adequate to resolve closely placed target frequencies.

Electronics. We designed and fabricated all major electronic subsystems in breadboard form. These included the input section using a commercial hearing-aid microphone from Knowles Electronics, frequency-shifting stage, the resonator-drive section, and the readout stage. The latter two sections are specific to the type of microresonator used (FPW or xylophone). All sections functioned as expected for the FPW version and were used in the proof-of-concept demonstration. The capacitance-based readout electronics for the xylophones did not work properly due to excessive parasitic capacitance in the interconnection circuitry. We are investigating methods to reduce the parasitic contributions through die-level hybrid integration of the readout electronics. Furthermore, we are investigating strain-gauge (impedance-based) readout methods for the xylophone resonators. This method should be simpler to implement electrically but is more difficult to fabricate.

Proof-of-concept demonstration. We successfully used the FPW version of MASA for a proof-of-concept demonstration. The system readily indicated the presence of the target sound generated by a touch-tone phone.

Intellectual property. We submitted two technical advances (TAs) as a result of work on this project. The first TA addresses the general MASA concept. The second TA deals with the methods of tuning the bandwidth and resonant frequency of the xylophone microresonators.

We successfully used the FPW version of MASA for a proof-of-concept demonstration. The system readily indicated the presence of the target sound generated by a touch-tone phone.

26565

Enabling Analytical and Modeling Tools for Enhanced Disease Surveillance

D. E. Kataoka, A. P. Zelicoff, M. W. Koch, M. M. Johnson, S. A. McKenna, M. W. Trahan, T. J. Sa

Early detection, identification, and warning are essential to minimize casualties from a biological attack. For covert attacks, sick people are probably the first indicator. An enhanced medical-surveillance system that synthesizes distributed health-indicator information and rapidly analyzes the information can dramatically increase the number of lives saved.

Current surveillance methods to detect both biological attacks and natural outbreaks are hindered by factors such as distributed ownership of information, incompatible data-storage and -analysis programs, and patient-privacy concerns. Moreover, because data are not widely shared, few data-mining algorithms have been tested on and applied to diverse health-indicator data.

This project addresses both integration of multiple data sources and development and integration of analytical tools for rapid detection of disease outbreaks. Sandia has developed an enterprise model that integrates security and access control and that can be used as the framework for communicating between distributed data and analytical tools. This work includes construction of interfaces to various commercial database products and to data-analysis algorithms under development. The outbreak-detection algorithms now under development can handle large quantities of data and incorporate multiple data sources. We are testing two approaches to determine applicability to different data sources of varying levels of detail. The first approach is a pattern-recognition (PR) technique that searches for space-time data clusters that may signal a disease outbreak. The second approach combines a predictive agent-based model (that tracks the interaction and health of agents that represent subsets of the population) and a genetic-algorithm technique (that detects outbreaks by comparing the prediction to field data or epidemiological databases). Using multiple techniques will result in reduced false alarms and greater probability of detection.

This project addresses both integration of multiple data sources and development and integration of analytical tools for rapid detection of disease outbreaks. Sandia has developed an enterprise model that integrates security and access control and that can be used as the framework for communicating between distributed data and analytical tools.

We obtained several health-indicator databases on which to test our algorithms. The first were publicly available weekly morbidity reports from France. The second were obtained through partnerships with health and military agencies. These databases include daily 911 and emergency-room-diversion data for several California counties and patient data refined by date and zip code for all California hospitals. In addition, we have agreements to gain access to extensive U.S. Air Force health data and syndromic data from other Sandia work.

We developed two data-mining techniques for outbreak detection. The first technique extends a mechanism for finding clusters in aggregated time-series data to detection in space and time. From the French data, this new space-time clustering approach has detected influenza epidemics; detection occurred with high sensitivity and specificity up to four weeks earlier than conventional approaches. Further testing with more refined datasets is under way. The second technique combines exposure, disease epidemiology, and human-behavior models in an agent-based model to predict outbreak manifestation. We developed a methodology to test predictions against actual data or epidemiological databases. We tested prediction of influenza and encephalitis outbreaks against a biological-threat disease database. Testing versus the hospital database is under way.

We developed the enterprise model that will enable platform-independent communication between distributed data and analytical tools. Software validation and verification has been completed. The software framework includes need-to-know security implemented through distributed role-based access control. We also developed software interfaces to integrate the databases.

We developed the enterprise model that will enable platform-independent communication between distributed data and analytical tools. Software validation and verification has been completed. The software framework includes need-to-know security implemented through distributed role-based access control. We also developed software interfaces to integrate the databases.

Other Communications

Koch, M. W., and S. A. McKenna. 2001. "Near-Real-Time Surveillance Against Bioterror Attack Using Space-Time Clustering." Sandia Technical Report SAND2001-0807C, Sandia National Laboratories, Albuquerque, NM (March).

26566

Microtransceiver for Tag, Beacon, and Data-Exfiltration Applications

K. W. Plummer, S. J. Leslie, K. T. Stalker, T. A. Fischer, D. Ingersoll, C. W. Ottesen, V. C. Hindman, R. Chanchani

Sandia will develop a low-power communications device with long-range capability. The device will emphasize advanced mechanical-packaging techniques to allow miniaturization and integration of necessary device electronics, power supply, antennae, and external interfaces. The electronics design will emphasize power-saving techniques for useful field lifetimes; the design will use advanced battery technologies. A unique communications scheme will be developed for efficient single- and multiple-access communications through the chosen platform. Design emphasis will be toward an existing platform requiring as few as possible platform updates and/or modifications, including the need for a custom receiver.

Initial efforts will focus on the following: technology identification and development, communications-scheme development, platform evaluation and selection, and designing and building a brassboard module to test the design methodology and theories prior to miniaturization and integration.

We identified a communications platform that was readily accessible and miniaturization circuitry to implement the desired communications scheme.

We designed a brassboard prior to designing miniaturized electronics that could prove difficult to troubleshoot. The board concept was to test as many communications schemes and circuits as possible by using reprogrammable logic and hardware jumpers. The brassboard will be capable of a variety of analog and digital communications schemes; we will implement a direct digital-synthesizer and digital-communications hardware.

We identified and outlined various benefits and shortcomings of several packaging schemes such as low-temperature co-fired ceramic (LTCC), microwave HDI (high-density interconnect), and benzocyclobutene (BCB)/Cu. Based on the analysis, we proceeded with development of BCB/Cu technology at Sandia. This technology has two major advantages over the other technologies: (1) certain types of

Sandia will develop a low-power communications device with long-range capability. The device will emphasize advanced mechanical-packaging techniques to allow miniaturization and integration of necessary device electronics, power supply, antennae, and external interfaces.

antennas can be integrated with the electronics substrate, thus eliminating one mechanical interface, and (2) using “chips last” techniques, the prototype-miniaturized devices can easily be tested and reworked.

26567

Extensibility of Knowledge-Based Human Agent Simulation

J. C. Forsythe, L. G. Nicholson, M. K. Snell, J. F. Jones, II, N. G. Brannon, P. G. Xavier, C. A. Wenner

This project advances capabilities for modeling and simulation of human-decision processes. The product pertains to assessment, training, and selection for Department of Energy (DOE) security as well as the Department of Defense (DoD), National Institute of Justice (NIJ), and other applications. Earlier work provided a framework to simulate human behavior; simulations were based on theories of naturalistic decision making and incorporated various organic factors (e.g., arousal, emotion). Previously, this framework had only been demonstrated for a single decision in a well-delineated situation.

The project focused on two advances: (1) the general simulation capabilities needed to be extended to accommodate situations where separate team members make a series of interrelated decisions, and (2) an efficient and systematic way to acquire and model knowledge for new application domains that need to be developed. In general, the objective was to transform the framework developed earlier into a practical tool to simulate human behavior.

The application emphasizes close-quarters battle (CQB), specifically interior tactics for assault against a barricaded adversary/suspect. The above developments are demonstrated using a commercial simulation, MicroSaint. This prototype demonstration illustrates how, when the knowledge attributed to individual combatants differs in the association of ideas and beliefs, opposite decisions occur concerning the use of deadly force.

- *Acquire and model expert knowledge using UNM knowledge-network approach.* Initially, we planned to select a single application to model expert knowledge. We selected CQB and, specifically, interior tactics.

We developed knowledge models for the CQB application. Here, working with background materials and subject-matter experts, we identified key concepts. Then, based on relatedness estimates obtained from subject-matter experts, pathfinder analysis derived a knowledge network. In these knowledge networks, concepts are represented as nodes

This project advances capabilities for modeling and simulation of human-decision processes.

with associative relationships between concepts expressed as links between respective nodes. The links between nodes may vary in strength reflecting the differential relatedness of concept pairs.

- *Develop methods for deriving from experts the patterns of cues associated with recognition of familiar situations.* For the CQB application, we used a method to identify situations that emphasize the actions implicit to a situation. This method appears viable because the method readily accommodates procedural situations, the nesting of situations within situations, and the interpretation of ambiguous situations.

- *Implement the above in pattern-recognition (PR) algorithms that model decision making.* We developed concepts in which cues from the environment and pre-existing knowledge provide a basis for PR. PR differentially assesses cues based on supporting or disfavoring specific conclusions, as well as—where appropriate—sufficiency versus necessity. Provisions exist for top-down influences. Specifically, recognition of a specific context differentially weighs cues favoring interpretations of ongoing events that are consistent with contextual knowledge.

- *Implement subject matter expertise in a knowledge network that mimics neural assemblies of the brain.* The initial framework emphasized a computational representation of knowledge that was motivated by current understandings from neuroscience. Specifically, the framework merged ideas from the oscillating-systems theory of cognitive processes within the brain and naturalistic decision making. However, the initial implementation was computationally intensive and, for this reason, impractical for most applications. We substantially redesigned this framework to enable practical application and implemented it using the commercial simulation MicroSaint.

- *Test simulation.* Utilizing the simulation developed in MicroSaint, testing involved proving out the simulation with different scenarios that involved one versus two agents and differing stimulus events.

- *Demonstrate the above for security/law-enforcement domain.* The testing scenarios demonstrated the simulation applied to the security/law-enforcement domain. Specifically, we modeled scenarios from CQB. The scenarios involve clearing a room that could contain either obstacles, adversaries, and/or nonhostiles.

For the CQB application, we used a method to identify situations that emphasize the actions implicit to a situation.

This method appears viable because the method readily accommodates procedural situations, the nesting of situations within situations, and the interpretation of ambiguous situations.

Refereed

Forsythe, C. 2001. "Toward a Human Emulator: A Comprehensive Representation of Human Cognition." Paper presented to ATEDS/SA, San Diego, CA, March.

Forsythe, C. 2001. "Toward a Human Emulator: A Framework for the Comprehensive Computational Representation of Human Cognition." *Proc. Human Factors and Ergonomics Society Annual Meetings (2002)* (Minneapolis, MN).

Other Communications

Forsythe, C. 2000. "Computational Representations of Human Behavior: Naturalistic Decision Making, Organic Factors, and Knowledge Representation." Paper presented to DoD Human Factors TAG, El Paso, TX, December.

26568

Secure Authenticated Sensor Packs

T. J. Draelos, R. A. Gonzales, R. C. Schroepel, C. L. Beaver, R. D. Miller, H. A. Smartt

Public-key data authentication is a vital surety mechanism for multilateral arms-control/material-monitoring agreements as well as for applications with secure-communications needs. However, the computational burden of cryptographically strong public-key algorithms limits their use in power- and size-constrained environments. Often the origin of the sensor data is the best place to generate an authentication tag (or digital signature) from a security standpoint and the most computationally limited and physically constricted setting. An ideal technology for cooperative monitoring would be an integrated sensor and public-key authentication subsystem. This subsystem would also allow the best opportunities for tamper protection because of the small size and low power dissipation.

Sandia has expertise in efficient public-key data-authentication techniques that use elliptic-curve (EC) hardware implementations and in sensor systems for cooperative monitoring. Thus, Sandia is well positioned to provide an important module to support sensor authentication. Using EC arithmetic in cryptographically strong, well-known digital-signature algorithms for public-key data authentication allows smaller key sizes and, therefore, less computation without a reduction in security. An authenticated sensor subsystem might address such issues as radiation, motion, temperature, and humidity, as well as have applications with biological, chemical, imaging, and seismic sensors.

A need exists for strong public-key cryptography for sensor-data authentication in low-power environments. Sandia has made significant progress toward meeting this need. Our research investigated sensor issues, and we worked to design the authentication subsystem as well as to implement the design using VHDL, the very high-scale integrated-circuit (VHSIC) hardware description language. The challenge is to satisfy the computational demands of cryptographically strong public-key algorithms in power- and size-constrained environments. Utilizing ECs in a specially selected digital-signature algorithm will provide public-key data authentication, nonrepudiation, and source identification with smaller key sizes. Therefore, less computation is required and

Our research investigated sensor issues, and we worked to design the authentication subsystem as well as to implement the design using VHDL, the very high-scale integrated-circuit (VHSIC) hardware description language. The challenge is to satisfy the computational demands of cryptographically strong public-key algorithms in power- and size-constrained environments.

with no reduction in security. Custom-designed hardware will provide further opportunities to reduce the size and power dissipation of the digital-signature device while supporting integration with multiple sensors.

Based on discussions with microelectromechanical systems (MEMS) designers, we decided to produce an independent authentication module to authenticate general sensor data. In other words, we deemed integration with a particular sensor on a common substrate to have no advantage over integration of discrete devices (sensor and authentication module) in a larger system. With a flexible interface accommodating most if not all potential sensors, a discrete authentication module would be the most useful and diverse. Imaging, seismic, and gamma-spectra sensors are of particular interest for compatibility purposes.

We began designing the authentication module and implemented in VHDL the digital-signature algorithm using EC operations. We selected the Optimal El Gamal digital-signature algorithm for authentication based on cryptographic strength and ability to support EC operations. Implementing this algorithm will allow variable key sizes to accommodate cryptographic strengths equivalent to the digital-signature algorithm with a 1024-bit public key and also support key sizes two and three times larger.

We worked to design and optimize the necessary EC operations. These optimizations include the following:

- *Collapsed hierarchy and reorganization of variables/operations.* Hardware design/implementation features brought improvements in size, speed, and power.
- *EC square root without multiplication.* Speed improvement.
- *Field towers.* EC multiply and divide speedup. Allows flexibility in key sizes (1x, 2x, 3x), where $x=89$ bits.
- *Finite-field quadratic solution.* Order-of-magnitude reduction in number of gates needed to solve a quadratic equation, resulting in size, speed, and power improvements.
- *Point halving.* Speedup of the most expensive digital-signature operation (nP) by a factor of three.
- *Sliding window.* Speedup of the EC point multiplication (nP) by at least a factor of two with a slight memory-storage requirement for precomputed values.

We worked to develop support software to test the necessary EC operations and to perform the circuit design, simulation, and validation in VHDL. This is a process of

We began designing the authentication module and implemented in VHDL the digital-signature algorithm using EC operations. We selected the Optimal El Gamal digital-signature algorithm for authentication based on cryptographic strength and ability to support EC operations. Implementing this algorithm will allow variable key sizes to accommodate cryptographic strengths equivalent to the digital-signature algorithm with a 1024-bit public key and also support key sizes two and three times larger.

migrating algorithms from software to hardware. Initial results of the circuit simulation are very promising.

- *Speed.* 24 msec to generate a digital signature.
- *Size.* 140,000 gates.
- *Power.* Unknown because of a lack of power models

for the complementary metallic-oxide semiconductor 7 (CMOS7) process. However, we expect power consumption to be less than 500 mA during digital-signature generation.

We began the preliminary design of the authentication module to support interface with sensors and microprocessors. In addition to the EC digital-signature algorithm, the authentication module will include memory erasure upon activation of a tamper input and power-management circuitry.

... we expect power consumption to be less than 500 mA during digital-signature generation.

26569

Remote Monitoring of Difficult, Real-Time Targets Using Video SAR Technique

T. P. Bielek, B. K. Bray, J. A. Hollowell, D. G. Thompson, M. T. Gardner, W. J. Bow, B. E. Mills

Monitoring and interpreting real-time activities at sites where access is difficult, remote, or denied is a primary issue for addressing both emerging threats and nonproliferation situations. Synthetic-aperture radar (SAR) has proven to be an effective means of remotely monitoring such sites due to its day/night, adverse-weather capabilities. Traditional SAR works well for stationary objects but is limited in its value for scenes that change quicker than a period of tens of seconds. Thus, SAR does not provide the situational awareness needed against scenes with dynamic content, such as moving targets, usually missing them completely. This limits the usefulness of SAR on a battlefield. An ideal sensor would not only be day/night, all-weather, as is SAR, but also would provide the continuous situational awareness needed against stationary as well as moving targets.

This project investigates a new technique invented at Sandia called VideoSAR, which would enable the forming of high-resolution SAR images at video rates—many times a second (about 100 times higher rate than traditional SAR). This technique exploits the human eye's sensitivity to motion and provides users with improved awareness and MASINT (measurement and signatures intelligence) signatures of scene dynamics. The fast image-update rate allows users to determine when moving targets started moving, when and where they stopped, and potentially which direction they are headed and how fast they are moving. Also, the position and identity of moving targets could potentially be determined more accurately from their shadows. While a shadow associated with a moving target would be hard to discern in a static image, it would be much more noticeable in VideoSAR, as it would be moving relative to stationary objects. MASINT signatures from ship motion and wave dynamics may also potentially be exploited. We believe VideoSAR represents a revolutionary approach to future SAR imaging.

This project investigates a new technique invented at Sandia called VideoSAR, which would enable the forming of high-resolution SAR images at video rates—many times a second (about 100 times higher rate than traditional SAR).

(1) We developed MATLAB software for the overlapped-subaperture algorithm (OSA) to automatically process SAR-phase history data in a VideoSAR-like way

(highly overlapped apertures separated by a few tenths of a second).

(2) We changed the motion compensation scheme in the current SAR software from sampling the phase histories on a Keystone grid to a polar grid. This avoids the need to identify the center of the aperture while the phase histories are being collected. We also added a continuous-circle-phase history-collection mode.

(3) We conducted three data collections aboard the Twin Otter aircraft at 1 m, 1 ft, 6 in., and 4 in. range resolutions in a spotlight mode over squint angles of 30° to 150°. The data collections involved a two-and-one-half-ton truck repeatedly driving through a four-way stop.

(4) We conducted two data collections at 1-foot-range resolution in a continuous-circle mode. One collection involved a MAZ-543 moving along roads, through gates and intersections, and performing a simulated missile launch. The second collection involved a T72 tank maneuvering in a dirt field.

(5) We processed the collected-phase history data into highly overlapped SAR images with aperture separations of 0.5 sec, 0.333 sec, and 0.2 sec at azimuth resolutions of 1 m, 1 ft, and 6 in. In the processed images, moving targets are clearly visible from their shadows.

(6) We are studying the processed complex SAR images for image exploitation and automatic target recognition (ATR). As many as four more data-collection flights are planned based on input regarding targets of interest.

(7) We began analyzing ways to optimize the OSA for processing highly overlapped apertures. A savings of 20 percent can be achieved with minor changes to the current algorithm and no degradation of image quality. We can achieve larger savings with varying degrees of image-quality degradation.

(8) The current OSA was benchmarked on the latest-generation commercial parallel-processing boards. A 1-foot-by-3-foot resolution image at 3.8 nautical miles can be formed on a single node in just under 4 sec.

We began analyzing ways to optimize the OSA for processing highly overlapped apertures. A savings of 20 percent can be achieved with minor changes to the current algorithm and no degradation of image quality. We can achieve larger savings with varying degrees of image-quality degradation.

26570

Adaptive Computer Intrusion Detection

E. A. Walther, B. A. Ingram, D. D. Hollis, C. M. Wray

All life responds to changes in internal state. Whether the cause is hunger, thirst, or injury, living systems have homeostatic mechanisms that detect and respond appropriately to change. In contrast, computer systems are oblivious; they have no generic mechanisms to detect or correct internal perturbations. Process homeostasis (pH) is a LINUX 2.2-kernel extension created to rectify this shortcoming. By observing changes in short sequences of system calls, pH can detect general changes in program behavior. When pH determines that a process is behaving unusually, pH responds by slowing down the process system calls. At a bare minimum, delays give a user time to decide whether a given action should be permitted. If the anomaly corresponds to a security violation, though, delays can help minimize damage and can even stop attacks in progress.

Sandia developed an intrusion-detection system for the RedHat LINUX 2.2.19- and 2.2.16-kernel systems. The intrusion-detection system can identify previously unidentified attacks. This system identified the silent attacker—the one who tries to remain hidden because finding the intruder in the first place is the problem, as well as a buffer-overflow attack.

pH is able to effectively use conditions. This captured behavior allows pH to detect anomalies with a low rate of false positives. Also presented are data showing that pH can detect simple configuration errors and can respond effectively to buffer overflows, TROJAN code, and kernel-security flaws.

pH has minimal impact on the runtime of the operating system, which incurs a general performance penalty of only a few percent.

pH is a prototype system that can detect and respond to changes in program behavior. This change in behavior may be due to an attack by an intruder, TROJAN code, or a new invocation of the program. pH monitors system calls in the kernel. It uses short sequences of systems calls to describe normal behavior for a given host-based system.

We implemented pH using RedHat LINUX for the 2.2.18 and 2.2.19 kernels. We generated normal profiles on several hosts. These profiles are characterized to determine the variability across hosts and users. We examined heuristics for determining when a given program profile had enough

Sandia developed an intrusion-detection system for the RedHat LINUX 2.2.19- and 2.2.16-kernel systems. The intrusion-detection system can identify previously unidentified attacks. This system identified the silent attacker—the one who tries to remain hidden because finding the intruder in the first place is the problem, as well as a buffer-overflow attack.

training data to declare that it was ready to go “normal.” If a program does not have adequate training data that are representative of its behavior when the program is running without intrusions (i.e., normal behavior), the program will be delayed in such a manner that it not only effectively locks up that program but, depending on what program it is (e.g., the bash shell), it can effectively also lock out the user.

Our analysis focused primarily on characterizing attacks, characterizing normal profiles for different hosts and users, and evaluating heuristics to determine when a program profile had enough training data to adequately describe program behavior. We did not emphasize evaluating the delay mechanism.

We showed that this system can follow buffer-overflow attacks and an attack that is classified, which were previously unknown to the system.

pH is not intended to be a stand-alone intrusion-detection system. It is designed to provide a level of protection at the kernel level that would be integrated into a system that might include firewalls, network scanning, and virus protection.

*We showed that this system
can follow buffer-overflow
attacks and an attack that is
classified, which were
previously unknown to the
system.*

26571

Link Analysis Using High-Performance Computing

E. A. Walther, M. W. Trahan

Sandia will analyze the applicability of a community-developed link-analysis process to determine its applicability to mining massive amounts of data to extract knowledge. This approach has been successfully applied to problems where the goal was to determine the linkage between persons when the connection in the database is not direct. We are interested in determining whether this approach can benefit from the added computational power available with multiprocessor machines. We will also determine the level of effort required to implement a version of the algorithm that would run on a massively parallel (MP) machine.

The amount of time required to perform the link analysis is significant. The current implementation philosophy has been to solve the speed problem in hardware. We believe that the run time of the algorithm could be significantly enhanced by implementing a version of the code using message-passing interface (MPI) that could run on an MP machine.

The Computational Plant (CPlant) machine was used to set a sorting record. Similarity between the sorting problem and the link-analysis problem leads us to believe that this approach would be successful. The CPlant architecture and scalability of the machine make it possible to consider algorithmic approaches that were not feasible to run on serial machines, but could not be used by other applications that could not afford Accelerated Strategic Computing Initiative (ASCI)-sized machines.

In addition, we plan to evaluate the methodology to see how it can be applied to data sources used by our analysts and customers. This methodology has the potential to be applied to a diverse set of problems such as tracking export-controlled items, finding connections between terrorist groups, and performing network analysis of computer linkages.

We analyzed a community-developed link-analysis process for the ability to extract knowledge from massive amounts of data. We analyzed community-developed code to determine whether parallelizing the code using MPI would facilitate data mining. We parallelized the current code using

The Computational Plant (CPlant) machine was used to set a sorting record. Similarity between the sorting problem and the link-analysis problem leads us to believe that this approach would be successful. The CPlant architecture and scalability of the machine make it possible to consider algorithmic approaches that were not feasible to run on serial machines, but could not be used by other applications that could not afford Accelerated Strategic Computing Initiative (ASCI)-sized machines.

10 processors and threading. Threading is a way to implement concurrent programming. If multiple processors are available, the concurrent program can be run in parallel. The advantage that threading has over multiprocess programming (of which using MPI is an example) is that threading shares the process resources and, therefore, has the potential for better performance.

Our initial approach considered implementing the code in parallel using MPI. This current code runs fast enough that data-mining techniques now drive data usefulness. Questions still remain about the scalability of this approach, but examining that aspect of the problem was not part of this effort.

We explored and created prototypes for several ways of mining link-analysis data using 3-D representations. We used the Flatland virtual environment to display data representations. Flatland is a highly configurable research environment developed at the University of New Mexico Albuquerque High-Performance Computing Center.

Link analysis of interacting entities is of growing importance for government and industry. (For example, monitoring the flow of goods and services between companies can be useful to detect and correct potential health-related issues such as foot-and-mouth disease.) The data collected from such transactions are typically in tabular form with listings such as “entity A and B interacted at time T with value V.” The best mathematical form to capture structure and patterns in this type of data is called a *graph* and is usually drawn as circles with connecting arcs. The circles represent the entities, and the arcs represent the interaction. Static flows through such a graph structure are usually coded as arc colors or widths, and the state of the entities is coded as circle diameter or color. Unfortunately, as graph complexity increases and time-varying behavior is added, this representation of link data can rapidly become confusing.

We created prototypes for two new representations of temporal-graph structures that are embedded in 3-D virtual environments. Early experimentation with these representations on calibration datasets shows promising results. Using one of the representations, we found an error in the simulated dataset. Remaining research issues include (1) how to make transitions between how current users analyze the data and this mathematical representation of the data, (2) what other representations are of value to the user, and (3) how best to generalize the data model.

We created prototypes for two new representations of temporal-graph structures that are embedded in 3-D virtual environments. Early experimentation with these representations on calibration datasets shows promising results. Using one of the representations, we found an error in the simulated dataset.

Currently users who do this kind of analysis predominately use textual-based information. They find possible links manually and must keep track of things with paper and pencil. Our representations show all possible links between entities (in graph parlance, *possible paths*). The visual representation simultaneously shows undiscovered paths and interest along with noise. Analysts need to be trained to use the tool that finds their paths of interest.

Our representations show all possible links between entities (in graph parlance, possible paths).

Other Communications

Summers, K. L., T. Eyring, T. P. Caudell (University of New Mexico, AHPCC); E. A. Walther, and M. W. Trahan. 2001. "Six Methods of Transaction Visualization in Virtual Environments." Paper to be presented to the Virtual Reality Conference, 24–28 March 2002, Orlando, FL.

26572

Coating Chemical Preconcentrators to Improve Chemical Agent Collection

C. L. Rhykerd, Jr., R. Kottenstette

Sandia has an interest in trace chemical-agent detection in the parts-per-billion (ppb), parts-per-trillion (ppt), and parts-per-quadrillion (ppq)-ranges. Field-ready prototypes in this sensitivity range require that a sampler and preconcentrator be integrated into a detection system (probably using microsensors). The preconcentrator manages the mismatch between the sampler flow (L/sec) and the low detector flow (mL/sec). Sandia has developed, patented, and licensed a stainless-steel screen preconcentrator for explosives; this preconcentrator improves system sensitivity by 10,000 times. However, preliminary data with a chemical weapons simulant show that this metal surface is inappropriate for chemical agents because of low efficiency of adsorption and decomposition during thermal desorption.

We plan to develop a preconcentrator subsystem to enhance chemical-agent detection and to do so within acceptable constraints. Coating the screen—to improve collection and reduce decomposition—is a logical engineering solution to this problem. Potential coating candidates include sol-gels (including silsesquioxanes), polymers, and carbon nanotubes. Successful coatings must be robust during temperature cycling to 200°C to 300°C and must adhere well to the substrate. A detection system is available for these evaluations, and we will continue our effort to leverage newly developed materials. We evaluated uncoated screens and sol-gel- and nanocarbon (NC)-coated screens.

Capitalizing on Sandia's strengths in sample collection, preconcentration, and materials, our success will lead to improved chemical-detection systems with enhanced capabilities (including sensitivity, portability, cost, and speed). This impacts applications in chemical-agent detection, explosives detection, drug detection, and environmental monitoring.

Sandia's accomplishments are as follows:

- We obtained uncoated and sol-gel-coated screens.
- We reviewed methods and, as a result, gave more

attention to screen temperature after two sol-gel-coated screens were destroyed. We chose two carbons for coatings

Photo of preconcentrator screens used in this study. From left to right: uncoated screen, sol-gel-coated screen, and NC carbon-coated screen. Quarter shown for scale. To left of quarter, screen viewed on edge.

Sandia has developed, patented, and licensed a stainless-steel screen preconcentrator for explosives; this preconcentrator improves system sensitivity by 10,000 times.

along with an NC, and a Lawrence Livermore National Laboratory (LLNL)–coated Suppelco-manufactured carbon.

- We collected data on uncoated and sol-gel–coated screens.
- We obtained an NC carbon-coated screen.
- We conducted NC carbon-coated screen experiments.

*We collected data on uncoated
and sol-gel–coated screens.*

26573

Ultralow-Power Spread-Spectrum Transceivers for Microtags to Improve Security During Critical Operations

R. W. Brocato, J. R. Wendt, R. C. Beckmann, S. A. Casalnuovo, M. B. Murphy, E. J. Heller, G. D. Omdahl, B. H. Rose

This project addresses microsystem security by developing an ultralow-powered radio-frequency (RF) receiver architecture for microtag applications. The new receiver design will enable inexpensive microdevices to control personnel access or to continuously track personnel movement during operations, as well as to monitor and track critical items or materials, and to apply smart sensors that detect, communicate, and process data, or take action. Currently, no commercial-receiver capability exists to meet low-power requirements for microtagging in security-related applications. Such receivers are not expected to become commercially available because of incompatible market demands (i.e., cost versus performance). Through this project, Sandia will advance our capability toward a wireless-communication-interface standard for microsystems.

This microsystem-based wireless RF communication receiver differs from commercial offerings by having a smaller size, reduced energy consumption, and the integration capability to meet unique application-specific features. Project emphasis is on realizing an ultraminiature, short-range (less than 1 km), energy-efficient, spread-spectrum receiver. We envision an energy-consumption improvement of two orders of magnitude. We applied Sandia's success in surface acoustic-wave (SAW) devices on gallium arsenide (GaAs) to develop a SAW correlator-receiver. This miniature RF-communication technology will provide robust data transport to identify, control, monitor, and track by time-of-arrival to multiple fixed receivers.

The enabling technology, SAW correlators, is passive-matched filters constructed of charged finger pairs (transducers) oriented relative to the phase pattern of the time-reversed spreading code. When a spread-spectrum signal is applied to the matched correlator, an output-correlation pulse occurs at the symbol frequency.

The initial challenges of this work are to prove that reproducible/robust SAW devices can be made in the 2–3 GHz range, to develop computer modeling that helps with design,

Through this project, Sandia will advance our capability toward a wireless-communication-interface standard for microsystems.

to determine the application-feature space for this technology, and to learn to test wide-bandwidth receivers (10 to 20 percent).

We developed a process to fabricate SAW devices on quartz and GaAs. The devices have fingers of feature size down to 0.1μ . The process uses electron-beam pattern definition on a polymethylmethacrylate (PMMA) resist for the fine features of the SAW. More standard photoresist and liftoff are then used to provide the larger metal features that connect to the outside world. We then test several process variations to optimize performance and yield.

Using this process, we examined three runs of SAW filters with center frequencies in the 2.40–2.65 GHz range. We characterized a range of bandwidths from 10 percent to 0.1 percent. The characterizations showed that this fabrication process is very reproducible (less than 0.001 percent) and very important for making communication systems where all the transceivers must be well matched. The yield was brought to above 90 percent. The measured results compared well with literature results of lower-frequency filters (200–500 MHz) and with computer simulations.

Part of this effort addressed development of simulations based on equations of operation for piezoelectric devices. The equations were adapted to our geometries and put in symbolic math solvers (MATHEMATICA and MATLAB) to allow comparison of the computer experimentation with SAW sample measurements. We performed initial correlator simulations, but more refinement is needed to turn this into a design tool.

We spent considerable effort determining the range of parameters possible with SAW correlators and determining if areas in the communication-application space were correct for concentration. We noted close measurements of temperature change in SAW performance above 100°C on both quartz and GaAs. We made a small study of temperature-compensation schemes. This study resulted in three paths: (1) quartz where temperature stability and high yield dominate, (2) lithium-niobium oxide (LiNbO) where insertion loss must be minimized, and (3) GaAs where a monolithic circuit is needed.

The ability to design and fabricate reproducible correlators that function at a high frequency now validates the rest of the proposed study. All knowledge was brought to bear

We developed a process to fabricate SAW devices on quartz and GaAs. The devices have fingers of feature size down to 0.1μ .

on building a variety of correlators incorporating a wide range of phase-shift codes. We fabricated these on quartz and LiNbO and are testing.

26574

Detection and Exploitation of Spread-Spectrum Waveforms

J. T. Cordaro, A. L. Schauer, T. S. Prevender, A. Martinez, J. J. Mason, R. C. Ormesher

Modern communications systems often employ spread-spectrum techniques to artificially broaden the spectrum of an otherwise narrowband signal. Spread-spectrum waveforms present a variety of advantages to the communications system designer: These spectrums provide jamming immunity, enable accurate time-of-arrival measurements, spread the signal energy over a wider frequency bandwidth (which can make the signal difficult for an eavesdropping adversary to detect), and alter the basic structure of the waveform (which can mask the underlying data format and content of the signal).

Suppose we possess an adequately sampled time-series recording of a radio-frequency (RF) receiver output. We hypothesize that the time series contains noise and may contain interference and one or more communications waveforms that an adversarial entity has sent. The problem is to detect and extract data from the adversary's RF communications.

Sandia will develop a suite of algorithms to systematically analyze the recorded time series with a goal of detecting spread-spectrum signals and extracting any underlying data signal. We will develop algorithms for both direct-sequence pseudo-noise modulation and for frequency-hop modulation. Algorithm types will address hypothesis testing, correlation analysis, and directed and random searches. Algorithm effectiveness will, in each case, depend on the amount of a priori knowledge of time-series content that we possess. Initially, the project develops, simulates, and characterizes extraction algorithms. Sandia has capabilities in several enabling technologies that are relevant to this problem: satellite systems, spread-spectrum communications, radar, real-time signal processing, and systolic computing.

We directed most of our effort to finding methods to detect wideband spread-spectrum signals. We reviewed the open literature and believe the cyclic-feature detector is the most promising type of algorithm. Detection methods that exploit specific cyclic features of the signal are less susceptible to interference compared to older energy detectors.

Sandia will develop a suite of algorithms to systematically analyze the recorded time series with a goal of detecting spread-spectrum signals and extracting any underlying data signal. We will develop algorithms for both direct-sequence pseudo-noise modulation and for frequency-hop modulation.

In addition, this kind of detector can distinguish signals from different emitters. The spectral correlation function (SCF) provides information about cyclic features. We wrote a MATLAB code that computes the SCF using a frequency-domain (fast-Fourier-transform [FFT]–based) method.

We applied the method to a few direct-sequence spread-spectrum signals to test the code. Cyclic-feature detectors can be implemented in several ways. For simulation on a personal computer, the FFT approach is appropriate. Preliminary work suggests that the frequency-domain method may be appropriate for an eventual system implementation; blocks of the necessary FFTs can be computed in parallel and, thus, be placed on a parallel-processor machine. However, because data rates for wideband signals are so large, we cannot rule out a time-domain approach that computes cross-correlation functions directly. Such a design would be realized with special-purpose (systolic) hardware.

We wrote a MATLAB code that computes the SCF using a frequency-domain (fast-Fourier-transform [FFT]–based) method.

26575

Small Power Direct-Conversion Microfluid Systems Using Logistical Fuels

K. Wally, R. W. Crocker, T. N. Raber, S. F. Rice, B. C. Wu, M. F. Wright, J. D. Taylor

Portable power supplies are critical to the prolonged operation of miniature field devices such as unattended ground sensors (UGSs), human-portable sensor packages, small robot vehicles, and even soldier-power systems for minimally manned warfare. Portable-power-supply performance poses real operational challenges to the intelligence community as well as to the departments of Energy and of Defense. Existing electrochemical-battery technology, including the best state-of-the-art rechargeable batteries (with an energy density of 480 Wh/L [watt hours per liter]), cannot meet the projected needs of most future field applications.

Sandia proposes a radically different approach to traditional battery design, namely, using liquid-organic fuel for energy. The small power systems that we are working on would use a common logistical fuel—methanol (or kerosene or hydrocarbons [HCs]). The proposed concept is readily scalable from human-portable power (less than 100 W_e [watts electric] to micropower (less than 250 m W_e [milliwatts electric]) size. The systems would consist of a small-scale hydrogen (H)-gas generator coupled to a commensurately small proton-exchange-membrane (PEM) fuel cell producing electrical power. The H-gas generator would be a supercritical-water microreactor functioning as a fuel reformer. This supercritical-water reformer (SCWR) is an innovation that we recently studied and propose to develop. The SCWR would reform methanol and water into H-rich gas to fuel state-of-the-art PEM-H fuel cells. Such cells are easily capable of direct-conversion efficiencies greater than 50 percent. Energy for the endothermic reformer comes from product H or system-electrical output. We estimate thermal efficiencies approaching 80 percent, yielding a 40 percent net-conversion efficiency to electricity. Methanol provides 4,980 Wh/L chemical-energy density. With a 40 percent net-conversion efficiency, nearly 2000 Wh/L of useful electrical energy could be derived. This system would roughly quadruple the performance that existing advanced batteries achieve.

Sandia proposes a radically different approach to traditional battery design, namely using liquid-organic fuel for energy ... We estimate thermal efficiencies approaching 80 percent, yielding a 40 percent net-conversion efficiency to electricity. ... With a 40 percent net-conversion efficiency, nearly 2000 Wh/L of useful electrical energy could be derived.

Reformer chemistry. In the SCWR, liquid-organic fuel and water are fed into supercritical water ($T = 400^{\circ}$ to 700° C, $P > 3600$ psi) where they readily reformed to H_2 and CO_2 (carbon dioxide). An illustrative chemistry for methanol is shown below:

One deficiency of conventional reformers is that carbon monoxide (CO) is not fully converted in the water-gas shift:

The result is excessive CO in the product, a potential poison for platinum (Pt)-based electrocatalysts in fuel cell electrodes. With SCWR, the supercritical water environment appears to enhance the water-gas shift, and CO concentrations drop significantly, eliminating any need for a separate water-shift reactor.

Experiments. We conducted a series of experiments to examine the feasibility of generating high yields of H from methanol in supercritical water. The reactor was 4.64 m of 1.06 mm inside diameter (ID) by 0.0625-inch-outside-diameter (OD) Inconel 625 capillary tubing coiled into 57 turns of 1-inch diameter. An electric furnace controlled by a digital temperature controller heated the reactor coil. A second identical coil outside the furnace acted as an air-cooled condenser. A high-performance liquid chromatography (HPLC) pump fed the reactor, and a pressure regulator controlled the pressure. A sample bottle with an analog pressure gauge took gas samples after the pressure regulator. We analyzed these samples using a mass spectrometer. The mass spectrometer was calibrated with known pressures of H_2 , CO_2 , CO, and CH_4 (methane), and the relative current response ratios were determined. We then normalized results to the total moles and reported them as mole fractions.

Experimental results. With reactor pressure maintained at about 4100 psi, we fed a 5-weight-percent solution of methanol through the reactor. We estimated conversion based on the methanol concentration in the condensed and cooled aqueous-liquid phase. The fractions of the C gases are reported relative to a normalized-H yield of 1.00.

We conducted a series of experiments to examine the feasibility of generating high yields of H from methanol in supercritical water.

These results suggest that H_2/CO ratios greater than 50:1 can be achieved in less than one minute at a temperature perhaps as low as 540°C . At lower temperatures, much of the carbon appears as CH_4 and CO . The high-temperature data agree very well with the calculation for equilibrium chemistry. The low- and intermediate-temperature data agree significantly less well. Apparently, the reforming process at intermediate temperatures (e.g., 550°C) in supercritical water does not reach equilibrium for shorter reaction times. At low temperatures, the experiment shows formation of a great deal of CH_4 . Obviously, dataset does not reveal the chemistry details, and no attempt has been made to account for possibly beneficial catalytic effects associated with the Inconel reactor. However, three main processes appear to control reforming in supercritical water: (1) conversion of fuel to simple gases, (2) competitive pathways to either CO or CH_4 at low temperature, and (3) subsequent conversion of CO to CO_2 by the water-gas shift reaction.

In additional tests, the reactor was brought up to 700°C and 4000 psi while pumping 0.6 mL per minute of water. When at temperature and pressure, a 5- to 25-percent-by-weight solution of methanol in water was pumped into the reactor at 0.6 mL per minute until a steady state was reached after about 15 to 20 minutes. In these initial conditions, the reaction appears to have reached the expected thermodynamic-equilibrium composition.

Conclusions. We demonstrated high-quality H (low in CO) production from the reformation of methanol in supercritical water in bench-scale laboratory experiments. These tests confirm that the SCWR process is a viable route to converting a HC fuel into H for use in fuel cells.

We demonstrated high-quality H (low in CO) production from the reformation of methanol in supercritical water in bench-scale laboratory experiments.

These tests confirm that the SCWR process is a viable route to converting a HC fuel into H for use in fuel cells.

Other Communications

Wally, K. 2001. "Micro Fuel Reformer: Hydrogen for Micro Fuel Cells." Internal Memorandum, Sandia National Laboratories, Internal Distribution Only. SAND2001-8279P (April).

26576

High-Bandwidth Optical Data Interconnects for Satellite Applications

D. K. Serkland, K. M. Geib, I. J. Fritz, J. F. Klem, K. R. Lanes, J. L. Rienstra

Optical fibers are rapidly replacing electrical cables as the medium of choice for the transmission of high-bandwidth analog and digital (A/D) signals. Coaxial cables cannot compete with the fiber's high-bandwidth capacity, low-attenuation coefficient, and immunity to electromagnetic (EM) interference. Moreover, optical fibers are cheap, reliable, and robust. Finally, for air- and space-based applications, optical fibers also offer substantial savings in weight as compared to traditional coaxial cables.

Sandia will develop high-bandwidth optical interconnects for use onboard satellites, where stringent requirements are imposed: radiation hardness, low power consumption, small mass, etc. We have pioneered research on several relevant technologies, such as vertical-cavity surface-emitting lasers (VCSELs), electroabsorption modulators (EAMs), and radiation-hard photodetectors. These gallium arsenide (GaAs)-based photonic devices have many attractive features for satellite applications, including small size, low power consumption, and compatibility with integrated circuit (IC) technologies. Moreover, these GaAs-based devices have demonstrated immunity to radiation damage.

The goal of this project is to address the future needs of focal-plane array (FPA) sensors by introducing high-bandwidth optical interconnects to transmit FPA signals within a satellite.

We first constructed an optical-interconnect test-bed to evaluate the photonic-device (e.g., laser transmitter, modulator, and photodetector) performance. We constructed a simple test-bed consisting of a GaAs VCSEL transmitter, a silicon (Si)-photodiode detector, and a low-noise receiver circuit. Optical-receiver noise often limits the performance of analog links operating near the shot-noise limit. To obtain the best receiver performance, we selected a photodiode with responsivity above 0.5 A/W and a transimpedance amplifier having an appropriate balance between its input-current noise and voltage-noise densities. The result is a receiver that can achieve a signal-to-noise ratio (SNR) of 170 dB/Hz with less

The goal of this project is to address the future needs of focal-plane array (FPA) sensors by introducing high-bandwidth optical interconnects to transmit FPA signals within a satellite.

than 1 mA of photocurrent. Because the shot-noise limit for 1 μ A of photocurrent is 155 dB/Hz, our receiver contributes negligible noise to the data link.

We used the test-bed to measure the relative-intensity noise (RIN) of our VCSEL transmitter, and we found that the RIN was -131 dB/Hz. Based on our theoretical study, we believe that this laser is suitable for analog transmission at 1 Msample per second, with 12 bits of resolution per sample. We made design modifications that are expected to lower the RIN of the VCSEL below -142 dB/Hz, which will make the VCSEL suitable for analog transmission of FPA data at 10 Msamples per second.

The second task required demonstration of a VCSEL-based analog link to transmit baseband FPA output signals to a remote digitizer. We successfully replaced the electrical link between a test FPA and a remote digitizer with an analog optical link. The optical link worked well, adding only minimal noise as compared to the direct electrical link. Although noise from the test FPA dominated the measurements, we estimate that 10.5 bits of resolution could have been obtained with a noiseless FPA.

For the third task, we designed and implemented correction circuitry on the receiver side, ahead of the digitizer, to compensate for level shifts with ambient-temperature changes. We determined that this function could be performed adequately using software, by simply calibrating the “zero level” out of the digitizer, without any significant reduction in the SNR. A factor-of-two change in the overall link gain would be required to produce a significant change in SNR, and we do not expect such large changes to occur.

The fourth task required a theoretical comparison of VCSELs versus EAMs for the performance of analog links. We took a general approach, theoretically evaluating the ultimate limits imposed by shot-noise on any optical link. For FPA applications, where typically at least 12 bits of resolution are desired, digital transmission can be scaled to higher sample rates more readily than can be analog transmission. For example, with 1 mW of shot-noise-limited optical power, analog transmission at 100 Msamples/sec with 12 bits of resolution is possible. With digital modulation, the same laser could transmit over 10 Gsamples per second, with 20 bits of resolution per sample.

Our study also met the original objective of the final task—to evaluate EAM performance in optical links. We concluded that, because of the high optical absorption of

Our study also met the original objective of the final task—to evaluate EAM performance in optical links. We concluded that, because of the high optical absorption of EAMs, a high-efficiency VCSEL transmitter delivers a larger SNR for a given power dissipation on the array.

EAMs, a high-efficiency VCSEL transmitter delivers a larger SNR for a given power dissipation on the array. Based on this conclusion, we decided against pursuing EAMs for low-power analog optical links in upcoming work.

Refereed

Serkland, D. K., K. M. Geib, T. W. Hargett, and A. A. Allerman. 2001. "Monolithic Integration of Vertical-Cavity Surface-Emitting Lasers and Wavelength-Shifted Resonant-Cavity Photodetectors." *Proc. LEOS 2001 Annual Meeting*, accepted.

26577

Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources

M. M. Moya, D. M. Haaland, E. V. Thomas, M. R. Keenan

Sandia chemometrics researchers have developed new techniques that promise to improve the robustness, performance, and utility of satellite-based hyperspectral imaging (HSI) for applications in nuclear nonproliferation, chemical and biological weapons (CW/BW) detection, and national intelligence. These applications require reliable identification, characterization, and quantification of target chemicals and materials. The performance of current spectral-analysis algorithms suffers in the presence of background and sensor noise, residual pixel calibration errors, sensor artifacts and drift, and atmospheric correction errors. Spectral-shape changes are complex, nonlinear, and time-varying. Sandia has 20 years of experience in developing multivariate algorithms for quantitative and qualitative spectral analyses in the presence of similar errors in the laboratory. The techniques augment the target model with spectra that correspond to these spectral-shape deviations. Chemistry laboratory experiments demonstrated the ability to perform quantitative spectroscopy without the need for calibration standards and the ability to extract pure-component spectra of spectrally active chemical species in heterogeneously mixed samples. Now, we are adapting robust multivariate calibration to identify and quantify materials in remote spectral sensing subject to instrumental, environmental, and atmospheric variations. We will evaluate the utility of new augmented multivariate curve resolution (MCR) for extracting pure components from mixed spectra. We will test prediction-augmented classical least squares (PACLS) and PACLS with a partial least squares post-processor for online calibration augmentation and model updating. We expect that incorporating these robust calibration techniques will significantly improve the performance of the identification/quantification algorithms. Developing the ability to identify spectra in the presence of atmospheric, environmental, and instrumental variations will interest a wide variety of customers who hope to use remote spectral imaging to recognize facilities, identify chemical and biological agents, and detect man-made anomalies.

Sandia chemometrics researchers have developed new techniques that promise to improve the robustness, performance, and utility of satellite-based hyperspectral imaging (HSI) for applications in nuclear nonproliferation, chemical and biological weapons (CW/BW) detection, and national intelligence.

We repaired and made operational the information-efficient spectral-imaging sensor (ISIS). We tested and verified the superior signal-to-noise ratio (SNR) of the Hadamard data-acquisition mode over the multispectral-acquisition mode. We implemented an efficient inverse Hadamard transform. We devised and implemented an improved spectral-radiance calibration procedure. We designed a prototype material identification experiment with 100 samples of different fabrics, including military camouflage. We designed spectral and spatial operational parameters suitable for characterizing the fabric samples. We devised methods for detecting and correcting spectral artifacts. We acquired and configured a multiuser and a LINUX workstation, including significant memory, data storage, and remote data access from both LINUX and Windows environments. We also enabled both local and remote log-on capability for flexible demonstration and data analysis. We developed HSI visualization tools for viewing both spectral and spatial dimensions and to aid in identifying spectral artifacts in both Hadamard and spectral domains.

We designed and constructed test panels that contain sample patches of 97 different fabric types. We collected ISIS data of the fabric panels and designed and implemented automated image-analysis methods to segment fabric patches from the background and to register arbitrarily rotated test panels for fabric ground truth verification at arbitrary pixel locations. We evaluated the ability of ISIS to sense fabric-to-fabric differences. We selected five fabrics that demonstrate significant spectral variability over the ISIS range. We collected variability-analysis data from the five-fabric subset to evaluate sensor variations of 1 hour, 1 day, and several weeks. We performed and analyzed a statistically designed experiment with the five fabrics, nine temporal images, and over 150,000 total spectra to quantify the sources of variation in ISIS measurements considering the following sources: (1) pixel-to-pixel variation within a fabric patch, (2) fabric patch-to-patch variation, (3) image-to-image variation, (4) fixed material effects, and (5) fixed spatial location effects. We designed a linear discriminant classifier and applied it to the five test fabrics. We achieved over 90 percent classification accuracy and found no performance degradation up to 49 days. We devised a strategy for subsampling patches to assess the effect of varying SNR. We conducted experiments to evaluate the effect of illumination level and began variation analysis. We developed a general approach to applying

We designed a linear discriminant classifier and applied it to the five test fabrics. We achieved over 90 percent classification accuracy and found no performance degradation up to 49 days.

constraints during alternating least squares (ALS). This is needed to make effective use of MCR techniques for subpatch or subpixel spectral unmixing. We designed and implemented a fast, nonnegative least squares algorithm based on orthogonal factorization. This enables more general constraints and “preferences” to be applied during ALS and MCR through use of penalty function approaches.

*We designed and implemented
a fast, nonnegative least
squares algorithm based on
orthogonal factorization.*

26578

Deployable Large-Aperture Optics System for Remote-Sensing Applications

T. D. Henson, J. W. Martin, J. M. Redmond, J. C. Wehlburg

Large-aperture optics are critical for improving sensitivity and ground resolution of future space-based telescope systems, such as those needed to monitor global-proliferation of weapons of mass destruction (WMD). Many researchers are considering on-orbit assembly of conventional rigid-optical mirrors to circumvent geometric limitations imposed by launch vehicles; however, this approach does not alleviate the tremendous cost penalty associated with the added weight of the overall system. In stark contrast to such incremental technologies, Sandia is developing a revolutionary new enabling technology for large-aperture optics. The key element of this research is an electron-gun-controlled piezoelectric thin-film mirror that can be compactly stowed for launch, deployed on orbit, and shaped to optical tolerances.

Integration of numerous contributing technologies is required to enable a thin-film mirror system for space-based remote sensing. This system must have a deployment method with quantifiable accuracy and a means of shape correction to bridge the gap between the deployed shape and the mission requirements. The corrective capability of the electron-gun-controlled thin films is established through intensive modeling and experimental investigation. Hard constraints on the initial deployment accuracy to meet mission requirements are emerging.

Sandia is developing a revolutionary new enabling technology for large-aperture optics.

Deployment sequence for a large-aperture electron-gun-controlled thin-film bimorph mirror.

This report summarizes the research effort into the development of enabling technologies for electron-gun-controlled thin-film mirrors. We made progress in the critical areas of mission-application development, optical-sensing techniques, electron-gun excitation, and shape control of thin-film mirrors, mirror-material issues, and packaging-and-deployment concepts. Results show that, although this field of research is in its infancy, many technological barriers to realization of a deployable mirror are surmountable. Continued research in this field is warranted based on the potential for dramatically reducing system size and mass while improving the resolution and sensitivity of future space-based optical systems.

To establish quantitative goals for the technology development of this research program, Sandia examined several space-based remote-sensing applications. A motivating and challenging light-detection-and-ranging (LIDAR) application emerged because of current relevance to the nonproliferation mission and the potential for improved ability through increased aperture. Sandia recently completed a study to determine the feasibility of using ultraviolet (UV) laser-induced-fluorescence (LiF) technology to detect from a satellite platform the signatures from biochemical weapons-related activities. We made field measurements for bio-aerosols and biosolids with Sandia's UV-LIDAR van. We developed a scientific model to determine the necessary LIDAR parameters to make the same measurements from satellite altitudes. This model shows that a space-based LIDAR system with a 5 m deployable collecting aperture could detect both bio-aerosols and biosolids from a low earth orbit with laser energies as small as 30 to 40 mJ at 355 nm wavelength with at least a signal-to-noise ratio (SNR) of 4. This system could be launched on a small launch vehicle (such as a Taurus) and would be very achievable with current technology. In contrast, a LIDAR system with a reasonable-size conventional-glass primary mirror (0.5 m diameter) would require a high-energy laser (greater than 2 J) with power requirements unrealizable in a current satellite system.

We conducted a literature search on optical-sensing techniques. High-fidelity sensing techniques such as interferometers or wavefront sensors are needed. Multiple-wavelength heterodyne interferometry offers a dynamic range of several orders of magnitude and subwavelength accuracy. A Shack-Hartmann wavefront sensor, which is less complex than

Results show that, although this field of research is in its infancy, many technological barriers to realization of a deployable mirror are surmountable.

the heterodyne system, may also provide high-fidelity-mirror figure measurements, but the total dynamic range is limited. It may be useful combined with some other coarse sensing system.

Determining the feasibility of deploying a thin-film mirror to an acceptable initial tolerance depends largely on the ability of the electron-gun system to correct for surface errors. To quantify this capability, we measured displacement profiles as a function of electron-beam energy and mirror back-pressure potentials. The resulting estimated curvatures indicate that relatively large curvature corrections can be implemented with beam energies as low as 400 eV. Further experiments are under way, but these initial results provide reasonable estimates of the shape changes that can be initiated, and in turn, help define the requirements for the deployment.

We devoted additional experiments and modeling efforts to refine the closed-loop control strategy. We recently achieved significant improvements in response time. Furthermore, recent research shows that mirror-figure controls are currently within the tolerances (700 nm root mean square [rms] with 3.5μ peak-to-peak) of the LIDAR design currently being exploited.

In collaboration with researchers at the Air Force Research Laboratory (AFRL), we are exploring rigidization of thin-film mirrors. Rigidized mirrors will yield a proportional decrease in control authority, but will be less sensitive to thermal and vibrational disturbances. Experiments with different rigidization techniques are currently taking place. We plan to conduct shape-control evaluation of these specimens.

Current mirror materials being considered are embedded piezo ceramics, piezo polymers, and piezo polyimides. Piezo polyimides are more stable in space applications than the piezo polymers. Further consideration is also being given to the probability of creases in the mirror surface resulting from packaging and deployment.

We identified possible deployment mechanisms through discussions with Sandia's deployable targets department. Articulated umbrella-like skeletons, inflatables, springs, and embedded shape-memory alloy wires all offer feasible solutions to the deployment problem. Umbrella-type systems are capable of packed-to-unpacked diameter ratios of 1:10. Some less-efficient packaging designs have ratios of 1:2. Mirror materials need to be further studied to verify their ability to withstand each packaging strategy with little or no permanent material deformation.

We devoted additional experiments and modeling efforts to refine the closed-loop control strategy. We recently achieved significant improvements in response time. Furthermore, recent research shows that mirror-figure controls are currently within the tolerances (700 nm root mean square [rms] with 3.5μ peak-to-peak) of the LIDAR design currently being exploited.

Refereed

Martin, J. W., J. M. Redmond, P. S. Barney, T. D. Henson, J. C. Wehlburg, and J. A. Main. 2000. "Distributed Sensing and Shape Control of Piezoelectric Bimorph Mirrors." *J. Intelligent Material Systems and Structures* **11** (October).

Other Communications

Henson, T. D. 2000. "Deployable Large-Aperture Optics Systems for Remote-Sensing Applications." Presentation to Sandia 5700 Monthly Brown Bag Seminar, Albuquerque, NM, 4 December.

Henson, T. D. 2000. "Thin-Skin Deployable Mirrors for Remote-Sensing Systems." Presentation to AFRL Cool Science and Technology Colloquium, Albuquerque, NM, 10 November.

Martin, J. W. 2001. "Electron-Gun-Controlled Thin-Film Deployable Mirrors." Paper presented to AFRL-Sandia Collaboration Discussions, Albuquerque, NM, 19 July.

Martin, J. W. 2001. "Thin-Film Mirror Piezoelectric Control." Presentation to the Sandia Technology Seminar, Albuquerque, NM, 17 August.

Martin, J. W., J. M. Redmond, T. D. Henson, J. A. Main, and G. C. Nelson. 2001. "Precision Shaping of Deployable Thin-Film Mirrors." *Proc. ASME International Mechanical Engineering Conference and Exposition* (11–16 November).

Martin, J. W., T. D. Henson, J. M. Redmond, and J. A. Main. 2001. "Large-Aperture Space-Based Optics." Paper presented to the Space and Missile Materials Symposium, Monterey, CA, 24–28 June.

26579

MicroChemLab Technologies for Early Detection of Pathogen Exposure

V. A. Vandernoot, R. Behrens, Jr., J. S. Schoeniger, J. V. Volponi, S. A. Pizarro

Sandia is developing a faster means to determine pathogen exposure. We need to discover if early biological hallmarks coincide with the immune system ramping up and if we can measure these hallmarks of immune activation in a field setting. The earliest indicators of immune-system activation include changes in the phosphorylation or levels of key signaling proteins. We will selectively collect the phosphorylated proteins from cultured immune cells by using affinity-chromatographic techniques and separating the cells by a variety of sensitive microscale techniques. We need to determine if separation patterns or fingerprints of phosphorylated proteins are indicative of the resting state of cells and if these fingerprints change in response to activation. This work could lead to the creation of a field device for first responders and emergency-medical personnel to track pathogen exposure.

Cell culture and activation protocols. The first stage was to create a cell-culture capability. We established three activation protocols for T-cells (T lymphocytes), including anti-CD3 (a protocol for T-cell activation), *Staphylococcal enterotoxin B* (SEB), and phytohemagglutinin (PHA). We implemented an enzyme-linked immunosorbant assay for IL-2 to provide an independent method to verify T-cell stimulation. We found the assay to be sensitive enough to detect the production of IL-2 in T-cells stimulated overnight with PHA (typically 200 ng/mL in activated cells). The assay also illustrated that our initial use of noncross-linked α -CD3 was not fully stimulating T-cells. We are currently optimizing the antibody stimulation with cross-linking reagents.

Methods development. We optimized conditions for harvesting and lysis of cells and the collection of total protein. Cells were centrifuged, washed once with PBS (phosphate-buffered saline) buffer, and lysed in buffer containing 1 percent Triton X-100 and protease and phosphatase inhibitors to prevent proteolysis and dephosphorylation. We have focused on the intact proteins from the cell lysates, but preliminary work shows our ability to work with peptides

Sandia is developing a faster means to determine pathogen exposure. We need to discover if early biological hallmarks coincide with the immune system ramping up and if we can measure these hallmarks of immune activation in a field setting.

from a model phosphoprotein and to characterize the metal-ion affinity-chromatography (IMAC)-enriched species by capillary-gel electrophoresis (CGE).

Phosphoprotein enrichment and capillary electrophoresis. We evaluated both IMAC and immunoaffinity methods and found them useful for enriching phosphorylated species. The phosphorylated proteins were too dilute to be seen in the lysates directly, but were visible after enrichment. Additionally, the bands were typically more numerous and darker for those samples stimulated with PHA.

Phosphoprotein fingerprinting. The total cytosolic-protein extract from resting and PHA-activated T-cells was separated by both capillary zone electrophoresis (CZE) and CGE. There are distinct differences in the electropherograms of resting cell and overnight-activated cell lysates. The total protein extract in both resting and PHA-activated T-cells was also enriched with respect to phosphoproteins using IMAC and/or immunoprecipitation. In the CGE traces of the phosphoprotein-enriched fractions, we found the first dramatic evidence supporting the central premise of this proposal, namely, the existence of differences in the phosphorylated-protein signatures of resting and activated T-cells. Work is under way to verify the reproducibility of these signature differences.

Activation time course. We also observed the changes in the phosphoprotein patterns as a function of time. We did initial work on PHA-activated cultures on cultures stimulated overnight. This is necessary to independently verify T-cell stimulation by IL-2 production (greater than 6 hours for IL-2 transcription). Phosphorylated-protein-signature differences, however, begin much sooner. We found clear indications in both the lysates and the phosphotyrosine-enriched fractions of differences in the protein patterns as early as 15 minutes. This is extremely important to the ultimate “rapid diagnosis” application of this work.

Alternative activation protocols. In addition to the PHA stimulation, we began examining the effects of anti-CD3, which stimulates T-cells through a different mechanism. Some signature differences were seen in both the monoclonal- and polyclonal-stimulated samples. In addition, the preliminary data show patterns that appear to be different from those obtained with PHA stimulation. This is significant as it suggests the possibility of pathogen-specificity inherent in the phosphoprotein patterns. Further work is needed to

In addition to the PHA stimulation, we began examining the effects of anti-CD3, which stimulates T-cells through a different mechanism. Some signature differences were seen in both the monoclonal- and polyclonal-stimulated samples. In addition, the preliminary data show patterns that appear to be different from those obtained with PHA stimulation. This is significant as it suggests the possibility of pathogen-specificity inherent in the phosphoprotein patterns.

verify these findings, especially in light of the observation that the antibody stimulation is not yet optimized, as evidenced by poor IL-2 production.

26580

Intelligent Tracking of the Telepresent Rapid-Aiming Platform

C. L. Nelson, J. J. Carlson, S. E. Eskridge, M. A. Martinez

The Telepresent Rapid-Aiming Platform (TRAP) is a remotely operated weapon system. TRAP offers significant force multiplication and enhancement by enabling near instantaneous response to attackers, increasing targeting accuracy, removing personnel from direct weapon fire, providing immunity to suppressive fire, and reducing security-force size needed to effectively respond. Test results have been exceptional, and response from the Department of Energy (DOE) sites and the U.S. Air Force is enthusiastic. Testing shows that the TRAP performs comparably to a trained marksman except for target-acquisition speeds, which are up to three times longer. Currently, the platform is enslaved to a remote operator's joystick. Tracking moving targets with a joystick is difficult, depending on target range, movement patterns, and operator skill. Even well-trained operators encounter difficulty tracking moving targets. A remote-response platform modified from the TRAP system is installed at Sandia. This installation supports an operational test and evaluation with inert ammunition. With the enhancement of intelligent tracking, the installation may form the basis for significantly improving security-force response in terms of effectiveness and numbers of responders.

We will develop automated, intelligent targeting capabilities for the TRAP—capabilities that will integrate machine-vision-based tracking with sensor- and model-based control. These developments will offload low-level targeting details, allowing an operator to focus on the immediate threat before deciding whether to issue firing commands. Our approach will integrate three-dimensional (3-D) video motion detection (3DVMD) under development at Sandia. This technology is already undergoing evaluations at several DOE and Department of Defense facilities where the TRAP could be deployed. We will use 3-D information in lieu of the joystick to automatically manipulate the TRAP's pointing angle and keep the target within weapon sites. Video from the 3DVMD system would provide immediate assessment capabilities for the operator to determine the appropriate response.

We will develop automated, intelligent targeting capabilities for the TRAP—capabilities that will integrate machine-vision-based tracking with sensor- and model-based control.

This project has been very successful. Because the TRAP is not available on a full-time basis, we configured a new platform that simulates the TRAP for algorithm development. This platform consists of a modified paintball gun mounted on a pan-and-tilt gimbal. The entire assembly is mounted on a shooting bench that was especially constructed to hold the TRAP. A video camera is rigidly mounted on the gun barrel, and a solenoid controls the trigger mechanism. The integrated video system, including the onboard camera and firing mechanism, is controlled through a single personal-computer platform.

We also made significant advances in algorithm development. These include mathematical models for projectiles under the influence of air resistance and models of targets based on the known physical kinematic constraints. We used a chronograph to acquire ballistics information, which we subsequently used to determine projectile model parameters. We optimized the model to provide the flattest trajectory across the expected range of fire. We also developed targeting solutions based on the mathematical models of the projectile and target and on the optical characteristics of the camera. These solutions provide the appropriate lead in pixel coordinates required for a bullet to hit a moving target. We developed calibration procedures for sighting and aiming. We used these procedures to determine the line-of-sight (LOS) pixel and the transformation between target position in camera coordinates (Δx and Δy with respect to the LOS pixel) and the corresponding position in pan/tilt coordinates (azimuth and elevation).

Finally, we completed the off-board sensor installation. We installed a 3DVMD system in a laboratory setting to provide position and velocity estimates of detected targets.

This project has been very successful. ...

We also made significant advances in algorithm development. These include mathematical models for projectiles under the influence of air resistance and models of targets based on the known physical kinematic constraints.

33323

Engineering Biomicrodevice Interfaces: New Microfuel Cells for Harvesting Energy from Biological Systems

D. A. Loy, C. J. Cornelius, D. Ingersoll, S. M. Brozik, S. H. Kravitz, C. A. Apblett, M. Okandan, D. A. Schneider

The Biomicrofuel Cell Grand Challenge will develop new compact power sources that can operate using fuels from biological sources. This project addresses the need for new, uninterrupted autonomous power supplies for sensor, communication, microelectronic, and health (e.g., prosthetics, pacemakers) applications where batteries are not acceptable because of size constraints and the logistics for replacement. Although microfuel cells have demonstrated clear advantages over batteries in energy density, they still rely on fuels such as hydrogen (H) or methanol that may be inconvenient for many applications.

Sandia will develop the technologies needed to interface these fuel-cell microsystems with biological systems as the renewable energy source. The challenges facing biofuel cells include (1) design of a microfuel cell compatible with biofuels, (2) selection of the optimum fuel(s), (3) engineering the biological microsystems interface for harvesting fuel, (4) identifying suitable electrochemical systems and long-lived electrodes, (5) designing, preparing, and integrating new fuel- and oxidant-selective membranes, and (6) biocompatibilization of the components.

The technological impact is a revolution in power supplies supporting the continued miniaturization of microelectronic devices. The project will also yield significant advances in membrane engineering, micropower systems, and understanding of biomicrosystem interfaces.

Recent accomplishments include successful testing of a bio-MEMs device with cells, design and construction of a quartz microbalance-based device for highly parallel membrane-permeability testing, construction and testing of a static-volume membrane test apparatus for final membrane testing, design of a new double-spiral fuel-cell architecture based on embossed thermoplastics, preparation and characterization of disulfide bridged polysilsesquioxanes as latent polymer-electrolyte membrane materials and their treatment with ozone, and preliminary testing of bipolar fuel cells with carbohydrate fuels.

The Biomicrofuel Cell Grand Challenge will develop new compact power sources that can operate using fuels from biological sources. This project addresses the need for new, uninterrupted autonomous power supplies for sensor, communication, microelectronic, and health (e.g., prosthetics, pacemakers) applications where batteries are not acceptable because of size constraints and the logistics for replacement.

We performed extensive surveys of the literature for work with microfuel cells and biofuel cells using Sci-Finder and Net Search Engines. We identified commercial, government, and academic competitors and compared their technologies with this project's objectives. These searches indicate that opportunities exist for Sandia to have significant impact in the microfuel-cell technology area and have enormous impact in the biofuel-cell technology area. These searches also identified a variety of government programs that would easily provide follow-on support to apply technologies developed in this project.

Membrane materials are an enabling component to this project. We directed our efforts toward construction and testing of a static-volume-membrane test apparatus for evaluating oxygen (O)-selective membranes, construction of a quartz-microbalance array for highly parallel screening of small quantities of membrane materials, and the preparation and characterization of new hybrid organic-inorganic membranes with latent sulfonic-acid functionalities.

We designed a new fuel-cell architecture to provide us with a new technological platform for competing in the microfuel-cell arena. The new design is based on a double spiral of anode (fuel) and cathode (oxidizer) channels to maximize surface area. The real innovation is construction of the fuel cell by embossing the architecture into the polymer-electrolyte membrane directly. This simplifies the construction, with potentially significant impact on production cost, of the device enormously and avoids the use of brittle silicon (Si) platforms that other academic and industrial groups are using. We fabricated embossing templates; efforts are under way to fabricate fuel-cell platforms.

We made enormous progress in bio-MEMs designed to increase the transport of cellular carbohydrates or other fuels through cell membranes without cell lysis. We began calculations to determine the design requirements for electrophoretic harvesting of glucose directly through the skin.

Literature surveys discovered that a Penn State researcher recently validated the highly parallel approach to fuel-cell electrode-material discovery and optimization. Based on these results and others, we selected platinum (Pt) ruthenium (Ru) as the preliminary candidate for the anode electrocatalyst and Pt for the cathode. Preliminary studies with Pt-based fuel cells with carbohydrates revealed no voltage generation, underscoring the necessity for binary alloys at the anode that are resistant to carbon monoxide poisoning. We

The real innovation is construction of the fuel cell by embossing the architecture into the polymer-electrolyte membrane directly. This simplifies the construction, with potentially significant impact on production cost, of the device enormously and avoids the use of brittle silicon (Si) platforms that other academic and industrial groups are using. We fabricated embossing templates; efforts are under way to fabricate fuel-cell platforms.

have decided not to pursue the enzymatic-based systems at this time.

This initial effort allowed us to focus effort on a new two-dimensional, heat-embossed architecture using Nobel metal electrocatalysts. We have insufficient information to permit down-selection with membrane materials and bio-MEMs. Furthermore, we ascertained that, although a scientific precedent exists for glucose-driven fuel cells, the technologies and materials developed in this project will be sufficiently innovative to provide a broad niche in fuel-cell technologies for Sandia.

... the technologies and materials developed in this project will be sufficiently innovative to provide a broad niche in fuel-cell technologies for Sandia.

Refereed

Shea, K. J., and D. A. Loy. 2001. "A Mechanistic Investigation of Gelation: The Sol-Gel Polymerization of Precursors to Bridged Polysilsesquioxanes." *Accounts of Chemical Research* **34**: 707–716.

Shea, K. J., and D. A. Loy. 2001. "Bridged Polysilsesquioxanes." *Chemistry of Materials* **13** (17 October): 3306–3319.

Shea, K. J., and D. A. Loy. 2001. "Bridged Polysilsesquioxanes: Molecular Engineering of Hybrid Organic-Inorganic Materials." *Materials Research Society Bulletin* **26** (May): 368–378.

33505

Embedded Self-Powered Microsensors for Monitoring the Surety of Critical Buildings and Infrastructures

K. B. Pfeifer, R. V. Matalucci

Predicting the performance of critical structures is vital to not only ensure occupant safety and security during naturally occurring and malevolent events, but also to determine the life-cycle deterioration rate under normal aging conditions to allow for efficient upgrades.

For this project Sandia evaluated the feasibility of applying integrated, remotely recorded microsensor systems to assess the structural performance of critical infrastructure. These measurement systems will provide forensic data on structural integrity, health, response, and overall structural performance in load environments such as aging, earthquake, severe wind, and blast attacks.

The clear objective of this project is to develop the ability to field a sensor that has neither wires protruding from a building member nor batteries and that can be embedded into a building member at fabrication.

The health of critical infrastructure, as has been so recently and tragically demonstrated by the events at the World Trade Center in New York City, demonstrates the need for systems that can autonomously measure the health of that infrastructure. We investigated the application of “self-powered” sensors to the problem of long-term detection of infrastructure health by studying the feasibility of using naturally occurring load-induced strains to excite a piezoelectric generator and power a microprocessor-controlled sensor system. That microprocessor can command and control a system that makes a measurement and then save the data from that measurement to a nonvolatile memory. Since the strains induced by the event are transient, enough energy is needed to activate the microprocessor, make the measurement, and store the data before the strain event concludes. The data are then read from the commercial-off-the-shelf (COTS) radio-frequency (RF) tag by using a reader.

We showed that the application of piezoelectric elements to harvest strain from beam elements in critical structures is feasible and could be made practical. We showed that microcontrollers can be operated by power produced only

The clear objective of this project is to develop the ability to field a sensor that has neither wires protruding from a building member nor batteries and that can be embedded into a building member at fabrication.

from strain and demonstrated the conversion and storage of electrical energy produced from this strain. In addition, we illustrated an approach to storing the data from the sensor to a nonvolatile memory and how that data could be retrieved. Thus, the placement of active sensors that do not require external power or wires and are powered by harvesting the stress applied to a building structure is a viable approach to monitoring critical infrastructure.

... we illustrated an approach to storing the data from the sensor to a nonvolatile memory and how that data could be retrieved.

33506

Photonic Lattice Coatings

T. J. Drummond, M. E. Warren, S. Y. Lin, R. J. Martinez, M. J. Morrow, D. K. Kramer, J. G. Fleming

Sandia recently developed infrared (IR) optical-bandgap structures known as photonic lattices (PLs). It has been demonstrated that the regularity and spacing of the parts can be designed to make the structure mirrorlike in particular wavelength bands. Applications such as tagging and shielding IR signatures have been described. The possibility of developing a coating (such as an adhesive and/or paint) using particulate PLs to achieve specific optical properties for both tagging and shielding applications has been discussed but not demonstrated. This project explores the feasibility of producing and applying such a coating and performs initial development. The uniqueness of this project is derived from use of particulate properties of the PL structure, as opposed to an extended solid. We developed a method to produce appropriately sized PL particulates.

During the project, we designed a process to fabricate PL particulates. While awaiting delivery of custom particulate material, we attempted to create particles from a monolithic PL. This resulted in the lattice disintegrating into its component “strands” of silicon, and this effort was not pursued further.

This project explores the feasibility of producing and applying such a coating and performs initial development.

33508

Applicability of a Self-Referencing Shearing Interferometric Vibration Detector

S. M. Stewart, C. L. Grotbeck, T. R. Nelson

This research explores a self-referencing laser-shearing interferometer as a remote vibration-detection sensor. Such a capability would provide new surveillance discriminants for artificial ground-motion and target identification. The approach uses optical shearography in a common-path-amplitude interferometer to process vibration as a differential-phase shift about baseband (homodyne) recorded as a spatial-fringe pattern at the receiver. Interference fluctuations produced by pairwise shearing of vibrating and nonvibrating parts of the target scene in adjacent pixels will sample the time evolution of the phase coherence of the reflected wavefront, which is proportional to the vibrational displacement. Because of vibration with the stationary-reference pixel (local oscillator on the ground), the phase shift is converted to lateral shear and detected by photon counting in the imaging pupil. In essence, the interference pattern obtained between original and displaced wavefronts is an edge filter for direct imaging of the vibration over the surface area. Because both signal and reference beams sample a common propagation path, the technique does not rely on source modulation and is self-compensating for Doppler broadening and temporal speckle decorrelation noise. Improved vibration sensitivity may be possible over conventional heterodyne techniques if ambient-atmospheric distortion does not disrupt signal fidelity and the optical-transfer function.

We modeled variable operating-source radiometrics, target reflectivity, vibration characteristics, and noise mechanisms to study the lateral-shearing problem. Using an experimental test-bed designed with Lambertian reflective targets and variable-piezoelectric transducers, we exercised salient features of a prototypical shearing measurement with an effects-matrix that investigated the impact of multiple-vibrational frequencies, sensor-platform motion, variable-scene reflectivity, broadband illumination, and surface relief. We conducted a parametric study of environmental variables to establish carrier-to-noise ratio (CNR) performance metrics for a photon-counting array detector. We incorporated results

This research explores a self-referencing laser-shearing interferometer as a remote vibration-detection sensor. Such a capability would provide new surveillance discriminants for artificial ground-motion and target identification.

into phenomenology and atmospheric models for mission analysis and assessment of system-performance thresholds in realistic operational environments. We performed comparative experiments to evaluate the merits of shearography versus conventional heterodyne techniques for vibration detection. We simulated the effects of atmospheric turbulence, speckle, and scintillation on phase fidelity and the optical-transfer function using a spatial-light modulator with adaptive transmission and wavefront characteristics as a precursor to future rooftop-propagation experiments. We developed processing algorithms to extract unknown vibration signatures from a noisy background.

We developed processing algorithms to extract unknown vibration signatures from a noisy background.

33509

Small-Scale High-Performance Optics

C. W. Wilson, B. L. Spletzer, M. A. Kuehl, C. L. Leger, D. E. Small

Historically, high-resolution, high-slew-rate optics have been heavy, bulky, and expensive. Recent advances in MEMS (microelectromechanical systems) technology and micromachining have changed this. Specifically, the advent of steerable submillimeter-sized mirror arrays and mass-produced diffractive optic elements provide the breakthrough technology for producing very small scale high-performance optical systems. For example, an array of steerable MEMS mirrors could be the building blocks for a Fresnel mirror of controllable focal length and direction of view. When coupled with a catoptric parabolic mirror, the steerable array could realize a microscale pan, tilt, and zoom system with no moving parts (except MEMS elements) that provides full charge-coupled device (CCD) sensor resolution over the desired view area. Another example uses an array of diffractive lenses that can be situated on or very close to the pixels of CCD array to produce an essentially flat, very wide angle lens.

A small-scale high-performance pan, tilt, and zoom imaging system would have immediate application to a number of fields, including microrobotics, medicine, and several security missions. Dense arrays of MEMS mirrors and independently steerable mirror arrays potentially applicable to such a system are currently under development. Sandia seeks to develop a demonstration system at large scale from existing hardware where we can develop pointing and image correction algorithms and software and investigate performance requirements for small-scale systems.

Our goal was to build a large-scale apparatus using existing components and to demonstrate the steerable fovea concept as well as to develop software to correct image distortions at normal video-frame rates.

We constructed the large-scale apparatus using the camera and convex parabolic mirror from a conventional 360° imaging system. We replaced the standard lens with a longer-focal-length unit to provide a higher-resolution image of a portion of the mirror. We constructed a frame that held the camera and mirror such that the optical axis of the camera and the axis of revolution of the mirror intersected at 90°. We inserted a gimbel-mounted flat mirror at the intersection point.

Sandia seeks to develop a demonstration system at large scale from existing hardware where we can develop pointing and image correction algorithms and software and investigate performance requirements for small-scale systems.

This steerable mirror allowed the field of view (FOV) of the camera to be directed to any part of the convex-mirror surface. The gimbel is controllable and the mirror position is readable from a computer interface.

In the original 360° imaging system, the video camera produced an image in which the outer edge of the convex mirror just touched the top and bottom of the image frame and the reflected image of the camera lens, centered in the image, and covered almost 20 percent of the image height. With the optical axis of the camera oriented vertically and the mirror located above the camera, the annulus of image data between the edge of the mirror disk and the outer edge of the lens represented a view covering 360° around the vertical axis and from 50° above to 60° below the horizontal plane. In a previous effort we had dewarped this doughnut-shaped image to produce a rectangular strip using a software pixel-mapping approach. In the resulting image, all horizontal and vertical edges are square. The pixel-mapping approach relied heavily on the fact that the mapping did not change from image-to-image to achieve video-rate dewarping. In the steerable fovea system, the mapping would change whenever the mirror moved. We decided to implement a texture-mapping approach that would use graphics-card hardware to achieve the dewarping. We projected the original 360° imagery onto several geometric shapes, including a flat rectangle, the inside of a cylinder, and the inside of a sphere. This last geometry provided convenient means of panning, tilting, and zooming in the image data. The narrow FOV data were also projected on the rectangular surface. All dewarping was accomplished at video rates.

We also began investigating the factors that influence the optical performance (resolution) of the proposed system. To this end we developed algorithms and a code to determine the blur-spot size for various mirror shapes and optical geometries. These tools not only allow us to analyze our current system but will also help optimize the design of future systems for desired characteristics such as reduced astigmatism, constant focal depth, and matched sensor and system resolution.

We also began investigating the factors that influence the optical performance (resolution) of the proposed system. To this end we developed algorithms and a code to determine the blur-spot size for various mirror shapes and optical geometries. These tools not only allow us to analyze our current system but will also help optimize the design of future systems for desired characteristics such as reduced astigmatism, constant focal depth, and matched sensor and system resolution.

Other Communications

Leger, C. L. 2001. "Determining the Viability of Curved Mirrors for Small-Scale High-Performance Optics." Presentation to the 6th Annual Student-Internship Program Symposium, Albuquerque, NM, 8–9 August.

34471

Terahertz Radiation Technology for MASINT

M. R. Ackermann, R. J. Simonson, F. J. Zutavern

Remote sensing—of the environment for earth resources, for military and intelligence purposes—typically relies on radio-frequency (RF) systems operating in the wavelike portion of the electromagnetic (EM) spectrum or on optical systems operating in the photonlike portion of the spectrum. The systems, which can be either active or passive, include simple RF receivers, radar, synthetic-aperture radar (SAR), light detection and ranging (LIDAR), infrared (IR), visible and even ultraviolet (UV) imaging, and nonimaging detection devices. What lies in between the long-wavelength IR systems and the short-wavelength RF systems is generically known as the terahertz (THz) band. Until recently, this area has been a largely unexplored region of the EM spectrum, as developing sources and sensors was difficult, and atmospheric absorption makes remote sensing difficult. However, with advances in solid-state materials, short-pulse lasers, and other technologies, sources and sensors for the THz band are gradually becoming more practical. This project takes a look at sources, sensors, propagation, and interaction physics, and at the possibility of using THz technology to support remote-sensing missions of interest to Sandia.

This project takes a look at sources, sensors, propagation, and interaction physics, and at the possibility of using THz technology to support remote-sensing missions of interest to Sandia.

This project provides a first look at the THz-radiation band and attempts to answer three questions:

- (1) What is the state of the art in generation and sensing of THz radiation?
- (2) What are the propagation and material-interaction issues that would determine whether THz radiation would be useful for application to remote-sensing missions?
- (3) Where should Sandia begin to pursue THz radiation for remote sensing?

(For the purposes of this report, the THz band is defined to cover the band of wavelengths from 3 mm to 30 μ m.)

Our ability to generate and sense THz radiation has exploded in the past 10 to 12 years. Advances in quantum-well (QW) semiconductor devices and ultrafast laser pulses have led the way. New techniques are being demonstrated all the time. Unfortunately, propagation physics has not changed in the past 10 to 12 millennia. The atmosphere is not friendly to THz radiation. In general, propagation is feasible in regions at the longer-wavelength end of the band (200 to 300 GHz).

Also, just past the short end of the band at wavelengths in the $20\mu\text{--}30\mu$ range are a number of attractive propagation windows for active systems; however, these wavelengths are slightly shorter than the THz band that we defined for ourselves. The $20\mu\text{--}30\mu$ range gets into the very long wavelength IR band. Although THz radiation overall looks less than promising for most long-range remote-sensing applications, a number of chemical interactions exist that would make THz systems useful as laboratory diagnostic tools. Finding out if these tools perform better than available tools will require time.

Some likely niche areas in the THz world exist that Sandia might explore. In many areas, we lead the nation or have leading-edge technology that can be applied to generation and sensing of THz radiation. One promising area is our work on ultrafast laser pulses. Another area where Sandia might find THz radiation of interest is as a diagnostic tool for chemical and materials research. Yet, these areas would be very application-specific. For long-range remote sensing, we find very limited propagation windows. Nonetheless, applications such as a ground-mapping THz active-imaging system might be of interest; such a system could be accomplished at an unused and difficult-to-detect wavelength free from biological hazards.

In many areas, we lead the nation or have leading-edge technology that can be applied to generation and sensing of THz radiation. One promising area is our work on ultrafast laser pulses.

34472

Radar Tag for the Remote Monitoring of Restricted Equipment

M. G. Vannoni, R. C. Ormesher, M. Gabbrielli, J. C. Bartberger

Accounting for heavy weapons (e.g., tanks) is an objective of conventional arms control. Agreements such as the Dayton Accords for Bosnia specify the relocation of heavy weapons to specific storage areas. These sites are periodically inspected by peacekeepers to verify that new weapons have not been added, commitments to destroy weapons have been met, and weapons have not been removed in preparation for a resumption of hostilities. Relatively large numbers of inspectors (and associated costs) are required for effective monitoring.

This project seeks to determine the feasibility of integrating synthetic-aperture radar (SAR) from the commercial RADARSAT satellite with radar reflector and tag technology to create a new, unclassified system of monitoring that will supplement on-site inspections anywhere in the world. The goal of tag development will be to enable low-resolution RADARSAT imagery to account for items that are normally too small to detect. The operational concept is that a tag that functions as a radar reflector is applied to treaty-limited items during a baseline inspection. The tag amplifies

This project seeks to determine the feasibility of integrating synthetic-aperture radar (SAR) from the commercial RADARSAT satellite with radar reflector and tag technology to create a new, unclassified system of monitoring that will supplement on-site inspections anywhere in the world.

Operational concept for the RADARSAT Radar Responsive Tag.

the item's radar cross-section, making it visible in low-resolution RADARSAT imagery. A monitoring organization can then determine, under all viewing conditions, whether the treaty-limited items are present by comparing the signatures in the image with the baseline inspection. A discrepancy between the image and the baseline declaration would trigger an on-site inspection. Tag integrity is essential and results from design features that prevent a tag's removal or substitution without visibly altering the signature.

This project will result in a feasibility analysis of the operational concept, including a conceptual design and operational procedures. The project leverages Sandia's experience in on-site inspection, tagging, tamper protection, radar reflectors, and radar imagery analysis.

This project built upon previous Sandia research and development (R&D) in radar-responsive tags and expanded this R&D to the application of arms control by using a new radar and platform. The RADARSAT tag system removes the need to regularly conduct on-site inspections by enabling the monitoring organization to determine, under all lighting and weather conditions, whether the treaty-limited items are present and their status. Major operational factors affecting the conceptual design of the tag are the effect of multiple (perhaps hundreds of) tags operating as a system in close proximity to one another and the need to protect tags from tampering.

Specific conclusions of the project include the following:

(1) A RADARSAT tag can create a visible signature in the SAR image and has a minimum estimated data transfer of 100 bits per look. This enables the tag to transmit an identification code, tampering status, and authentication code. Other factors in the tag's environment could be measured and reported with codes using small numbers of bits.

(2) If the tags are spaced close to what the RADARSAT-2 radar can resolve (3 m), the tags will overlap in the image and become an indistinguishable bright mass. Altering a tag's signal can solve this problem. Signal delays create range displacements, and small signal-frequency shifts create azimuth displacements of the tag in the SAR image. These range and azimuth shifts can artificially spread the visual appearance of closely spaced tags to form a new, virtual pattern of distinguishable objects in the image.

(3) Tags placed in close proximity to one another can cause the output of one tag to become the input to another,

The RADARSAT tag system removes the need to regularly conduct on-site inspections by enabling the monitoring organization to determine, under all lighting and weather conditions, whether the treaty-limited items are present and their status.

resulting in mutual coupling and degraded performance. A number of techniques can be used to reduce the amount of mutual coupling (e.g., choosing an appropriate antenna type, synchronizing tag clocks, splitting the dwell time, delaying the tag responses relative to one another). In practice, completely eliminating the effects of mutual coupling may be neither practical nor necessary.

(4) The data-uplink rate per tag will degrade slowly as the number of tags communicating with the satellite increases. This is a complex effect resulting from a number of factors.

(5) The tag packaging can be protected from tampering under a variety of scenarios using limit and motion switches combined with signal authentication during long periods of unattended deployment.

In practice, completely eliminating the effects of mutual coupling may be neither practical nor necessary.

34473

Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System

*K. K. Pace, A. E. Hodapp, Jr., A. C. Watts, W. T. Hobson, S. G.
Beard, Jr., M. W. Kniskern*

This project is classified.

34474

Conceptual Design of Self-Adjusting Inertial Inmate Restraints

J. T. George

Restraint methods used for the transport and/or detainment of prisoners have become an increasing concern for the safety and welfare of law-enforcement officers. There are numerous instances of physical-restraint methods being compromised and allowing escape or injury to police. There is a clear need for more effective but still inexpensive restraint approaches.

The inertial restraint system was conceived as a simple answer to handcuffs and shackles. Unfortunately, inertia reels tend to lock during sudden movements and unlock once the activity has subsided. This may impede a prisoner's movement, but would allow continued unwanted behavior.

A new approach involves an automatic tensioning system (inertia reel with locks) similar to those used in high-performance military aircraft.

Automatic tensioners, activated by accelerometer or kinetic-energy device signals, initiate a high-speed gas generator to activate tensioner reels, thereby restricting continued sudden or violent movement. In the automobiles, locking tensioners can be overridden after violent movement has stopped. Used as part of the inertial restraint system, the tensioner reels would tighten straps about the waist, immediately pulling the hands to the waist. Using shackles, activation of the tensioning reels would bring the individual's ankles together and hold them firmly, thereby restricting all but the smallest foot movements and allowing quick capture. Activation of both the handcuff- and shackle-style restraints would incapacitate the individual. An added enhancement would be remote activation (similar to garage-door-opener technology) initiated by escorting personnel.

A programmable magnetic-strip-style "key," similar to hotel room keys, would activate and deactivate the system, reducing the potential for illicit keys. Digital codes for deactivation and removal of the restraints could be transmitted via secure Internet channels to other jurisdictions for transport.

This work attempted to assess the potential for developing a technologically advanced prisoner-restraint

A new approach involves an automatic tensioning system (inertia reel with locks) similar to those used in high-performance military aircraft. ... A programmable magnetic-strip-style "key," similar to hotel room keys, would activate and deactivate the system, reducing the potential for illicit keys.

system that provides adequate safety for law-enforcement officials along with the general public, provides humane treatment for those detained, and does so in a fiscally sound way. The study used the property of inertia as the basic underlying concept for the alternative restraint system. We evaluated two ideas, one simplistic and the other technologically advanced.

Using mechanical-inertia reels as an aid in stopping unwanted movement is perhaps the most simplistic alternative to common handcuffs and shackles. Designed to stop all motion above a preset limit, inertia reels have proved effective for the aviation and automotive industries in preventing trauma and death. Unfortunately, the simplicity of the mechanical-inertia reel becomes a major drawback and casts doubt on using this technology as an alternative restraint system. Major hardware redesign would be required to prevent compromise. The design of available, low-cost inertia-reel systems lacks retraction mechanisms of sufficient strength to overcome an individual's muscular strength, and also lacks the permanent locking devices that would preclude any further movement after initial actuation.

Based on automatic-tensioning systems, a second alternative for the advanced restraint design may be more advantageous than using inertia reels. Automatic tensioners, similar in function to inertia reels but dynamically actuated, are typically activated by signals from electronic sensors. The initiation signal is based on acceleration or movement levels similar to those for mechanical inertia reels. The initiation signal is electrical in nature. When the signal is received, a small pyrotechnic charge would initiate and cause rapid gas generation. The generated gas would drive take-up spools, causing immediate retraction of excess restraint webbing. As applied to inertia-activated restraints, the automatic tensioners would respond to prisoner movements and result in rapid and total incapacitation of the subject.

Many drawbacks are evident in using inertial reel and/or automatic tensioners for advanced restraint designs. Disadvantages range from high-level redesign and development requirements to make the hardware functional to hazards associated with prisoners being restrained through explosively actuated devices. Indeed the recovery of development costs through a saleable system may far outweigh all other concerns.

The study used the property of inertia as the basic underlying concept for the alternative-restraint system. We evaluated two ideas, one simplistic and the other technologically advanced.

34475

Miniaturized Sensor Technologies for Drug Detection

C. H. Morgan, J. E. Parmeter, P. J. Rodacy, J. L. Barnett, C. D. Mowry, L. M. Ford, S. F. Bender

Many applications of trace drug detection are of utmost importance to the law-enforcement community. Especially important applications include (1) lightweight surveillance bracelets for personnel monitoring via analysis of transdermal bodily secretions, (2) portal detectors for noninvasive personnel monitoring at checkpoints, and (3) hand-held detectors to provide portable personnel screening with minimal invasiveness. The first application is geared toward identifying drug users, while the latter two are geared toward identifying drug carriers/smugglers. There is little technology at present that is commercially available for any of these applications. Current techniques for drug monitoring rely heavily on laboratory analysis of breath and fluid samples collected by compliance personnel; shortcomings of current technologies include the high cost, invasive nature, infrequent test periods, and ease of circumvention. The target applications would benefit highly from the development of relevant miniaturized sensor technologies.

Sandia will address some key drug-detection issues to work toward making the above applications a reality. Other work has developed a micro-GC/SAW (gas chromatograph/surface acoustic-wave) device and micropreconcentrator for the detection of chemical and biological agents, and a macropreconcentrator for the detection of explosives. These technologies are critical components of μ ChemLab™ and the explosive-detection portal, two highly successful Sandia programs of the last few years. Leveraging on this previous work, we will use the funding received through this project to perform preliminary investigations of using these technologies to detect illicit drugs.

To date, there has been no drug-detection work performed with the micropreconcentrator and micro-GC/SAW, and only some very rudimentary work has been done with the macropreconcentrator.

This report discusses work performed in several areas that are applying novel approaches to the collection and

Sandia will address some key drug-detection issues to work toward making the above applications a reality. Other work has developed a micro-GC/SAW (gas chromatograph/surface acoustic-wave) device and micropreconcentrator for the detection of chemical and biological agents, and a macropreconcentrator for the detection of explosives. These technologies are critical components of μ ChemLab™ and the explosive-detection portal, two highly successful Sandia programs of the last few years.

analysis of trace-drug material. The project demonstrated the following key results:

- (1) extraction of residual methamphetamine, cocaine, and heroin from seawater using solid-phase microextraction,
- (2) separation and detection of methamphetamine in methanol solution by using a micro-GC that Sandia developed and coupled with a flame-ionization detector, and
- (3) collection of methamphetamine vapor in a miniaturized (1.5-inch diameter) version of Sandia's screen preconcentrator with near 50 percent efficiency.

Further work in all of these application areas could prove useful to a variety of potential customers with interests in drug detection.

Seawater results. Heroin, cocaine, and THC (tetrahydrocannabinol, a psychoactive compound in marijuana) samples can be collected, analyzed, and positively identified in 30 minutes at 100 ppb in 2.5 percent saltwater. Using static sampling, we estimated a minimum detection limit of approximately 2 ppb of THC, 4 ppb of cocaine, and 20 ppb of heroin. Using Environmental Protection Agency (EPA) methodology and based on eight samples, the detection limits are 61 ppb, 35 ppb, and 89 ppb for cocaine, THC, and heroin, respectively, with 99 percent confidence.

However, static sampling typically provides fairly poor extraction efficiency because of diffusion limitations. Agitation of the solid-phase microextraction (SPME) fiber and/or extraction from flowing systems (e.g., pumped water) typically provides at least a 10-times increase in sensitivity (based on our experience performing explosives analysis in seawater).

Microgas chromatograph (micro-GC) results. We demonstrated the separation of methamphetamine from a methanol solution using Sandia-developed micro-GC technology. Specifically, we used a micro-GC with polydimethylsiloxane coating and a total path length of 86 cm in this separation; we performed the experiment isothermally at 50°C and a flow rate of less than 2 cm³ per minute. In limited additional experiments, separation of other drugs from solution was not obtained using the micro-GC.

Minipreconcentrator results. We developed a miniaturized version of the Sandia screen preconcentrator (SSP) with the screen diameter reduced from 6 inches to 1.5 inches. This is, in effect, a reduced-scale version of the same preconcentrator that is used in Sandia's explosives-detecting personnel portal. We evaluated this miniaturized

... static sampling typically provides fairly poor extraction efficiency because of diffusion limitations. Agitation of the solid-phase microextraction (SPME) fiber and/or extraction from flowing systems (e.g., pumped water) typically provides at least a 10-times increase in sensitivity (based on our experience performing explosives analysis in seawater).

preconcentrator for the collection of methamphetamine and cocaine vapor. In the case of methamphetamine, we obtained an average collection efficiency of 45 percent, which is very similar to what we obtained with the larger model. In the case of cocaine, preliminary results indicate an efficiency of only approximately 20 percent. These results suggest that this minipreconcentrator might be suitable as a front-end collection system to be coupled with other Sandia microtechnology.

*... this minipreconcentrator
might be suitable as a front-
end collection system to be
coupled with other Sandia
microtechnology.*

34476

The Development of Polymer-Based Antitamper Systems

T. A. Ulibarri, F. L. Lucero, K. Rahimian

Recent publications have highlighted the great need for antitamper (AT) systems. The current cooperative weapon development and foreign military sales environment necessitates the use of AT techniques. Many of the current AT techniques are extremely costly and difficult to manufacture. Effective AT techniques that can be incorporated into a wide variety of military systems must be developed. In addition, electronic components developed domestically for communications could require protection.

Recent developments in inherently conductive polymers (ICPs) synthesis and characterization have led to a new class of polymers that have unique properties that can be used for AT applications. While these materials exist, their applications are still under development. This project will investigate the tailoring and application of these materials for use in AT systems. Sandia will obtain and characterize samples of commercially available ICPs. We will investigate the chemistry of tailoring the response mode of these materials in a literature search and in the academic and commercial community.

This investigation is a feasibility study of these materials. The results of this project will establish whether these materials are truly suitable for AT applications.

Completion of this study provided a greater understanding of the chemistry and capabilities of ICPs. The information gathered in this study allows us to hypothesize specific applications directly related to our field of expertise.

We identified and cataloged commercially available ICP products and systems. We identified ICP application areas to be batteries, organic light-emitting diodes (LEDs), capacitors, chemical sensors, corrosion protection, circuit fabrication, microwave shielding, and more. Of the commercial samples obtained, we determined basic electrical- and environmental-response parameters. We assessed ease of application and adhesion to common materials. We evaluated common inspection methods, such as visualization through optical and x-ray examination, and assessed durability and lifetime. We retained samples for future assessment.

This investigation is a feasibility study of these materials. The results of this project will establish whether these materials are truly suitable for AT applications. Completion of this study provided a greater understanding of the chemistry and capabilities of ICPs. The information gathered in this study allows us to hypothesize specific applications directly related to our field of expertise.

We obtained information regarding the synthesis and derivatization of ICP systems by attending the 8th International Seminar on the Technology of Inherently Conductive Polymers. Continued conversations with academic and industrial researchers in the ICP arena also added to the knowledge base that we have developed. As the field continues to grow and more applications are developed and commercialized, these contacts will prove invaluable. Some methods that can be used to vary ICP properties are changing the dopant identity and quantity, changing the polymer substituents, changing the polymer molecular weight, and altering the processing conditions during polymerization and doping.

Some methods that can be used to vary ICP properties are changing the dopant identity and quantity, changing the polymer substituents, changing the polymer molecular weight, and altering the processing conditions during polymerization and doping.

34484

Network-Enabled Firmware

T. Q. Thai, S. T. Jones, D. P. Ghormley

Please refer to classified report.

37690

Indications and Warnings in the Cyber Domain

V. E. Echeverria, IV, D. A. Kernan, J. S. Duncan, R. M. Jansma, R. P. Fleming

Results and findings are classified.

41194

Cognition-Driven Augmented Analyst

J. S. Wagner, K. W. Larson, J. H. Ganter, R. D. Skocypec, T. M. Berg, J. C. Forsythe, N. G. Brannon, H. H. Hirano, M. Strzyzewski, P. C. Reeves, P. G. Xavier, K. W. Boyack, K. L. Hiebert-Dodd, S. E. Jordan, N. M. Berry, P. L. Asprey, C. M. Pancerella

Merging data acquisition, data management, data surety, computational modeling, algorithm development, and data visualization with an emerging capability, cognitive modeling, creates a new technology, termed cognition-driven augmented analyst (CDAA), that will have significant impact on national security. It changes the basic conceptualization of human-machine systems through a refutation of the assumptions on which nearly all technologies are being developed today. Specifically, the focus today is on machines—structuring tasks, massaging data, and generally constraining what the user knows, what the user thinks, and what the user can do. As a result, current technical approaches intended to enhance human cognitive and decision-making capabilities actually result in “disabling people’s expertise.” Across technical and program domains, increasing availability and access to data continually raise the stakes as well as the potential payoff. If the solution could be found in innovative user-interface displays, the problem would have been solved by now. Instead, the solution lies in the machine acting as a trusted peer, and sometimes idealized mentor, to the human user. CDAA does this by focusing on the human while optimizing and tailoring the power of the machines, creating a human-machine symbiosis, or a creative engine that leverages the instinctive capabilities of humans with the computational power of machines.

We assembled the team and developed a work plan for FY 2002.

... current technical approaches intended to enhance human cognitive and decision-making capabilities actually result in “disabling people’s expertise.” ... the solution lies in the machine acting as a trusted peer, and sometimes idealized mentor, to the human user.

Pulsed Power Sciences

The Pulsed Power Sciences investment area researches concepts and technologies for advanced pulsed power systems and applications critical to important DOE and national priorities. Pulsed power research covers a wide range of technology issues, including mitigation of negative electromagnetic effects on weapons, designing large pulsed power, and the optimization of the conversion of electrical energy to x-rays with the application of the x-rays generated to radiation effects.

Recently, an innovative experimental technique was developed that allows the study of dynamic material response to high pressures. The resulting pressure-density information generated with this method is crucial for generating the equation-of-state of a material, thus significantly reducing the cost and the time for generating and validating theoretical models of dynamic material response. The "Isentropic Compression Experiments on the Saturn Accelerator" project will extend the use of this technique to the Saturn generator, which will increase the accessibility to a broader

range of applications and further reduce the cost of testing by another factor of five. This research will make the technology available to a variety of Sandia weapon applications and supports new initiatives requiring timely evaluation of material properties.

28763

Use of Intense Ion Beams for Surface Modification and Creation of New Materials

T. J. Renk, P. P. Provencio, G. A. Mann

Intense ion-beam treatment can be used to produce improved surface properties and to create new metastable alloys and thin films, all in a way that is scalable to large-scale production. We will investigate the following areas:

(1) Suppression of high-voltage (HV) breakdown of metal surfaces that could allow for smaller-gap magnetically insulated transmission lines (MITLs) in future pulsed-power machines, and extend the life of neutron tubes (NTs). NT studies suggest that the breakdown source is either entrained dielectric material or mechanical polishing procedures that leave residue. Ion-beam processing has already demonstrated the ability to reduce or remove such contaminants and to refine the grain structure. The goal would be an increase in the surface breakdown strength to 1 MV/cm, in a process scalable to large surface areas, and with microstructural understanding.

(2) Improvements to the target film in NTs, either by surface modification, thin-film creation, or both. The goal is to reduce the outflow of helium (He) from the film, which leads to premature target failure.

(3) Congruent deposition of barium titanate (BaTiO_3) thin films of high dielectric constant, which could lead to very compact capacitors, Marx generators, etc.

(1) HV standoff enhancement. We treated two sets of NT electrodes using the ion beam to modify the surface, and we tested for enhanced HV-breakdown performance using a test fixture previously developed for this purpose. We compared the performance to other electrodes processed by conventional means such as electropolishing and mechanical polishing. The ion-beam-modified samples (using an argon [Ar] beam) performed well, except for some unexpected gas evolution from the sample that we subjected to the most ion-beam pulses. Follow-up work was delayed by a breakdown in the HV test fixture.

(2) We completed an experimental plan that includes the source and target-film processing to improve adhesion and increase regettering. (This work is detailed in the original proposal, except that we added palladium [Pd] to the source

We treated two sets of NT electrodes using the ion beam to modify the surface, and we tested for enhanced HV-breakdown performance using a test fixture previously developed for this purpose. We compared the performance to other electrodes processed by conventional means such as electropolishing and mechanical polishing. The ion-beam-modified samples (using an argon [Ar] beam) performed well ...

film.) While waiting for erbium (Er) and scandium (Sc) targets to arrive, we compared the microstructure of a platinum (Pt)-metal film deposited by conventional sputtering to the microstructure produced by the ion-beam-ablation process. The microstructure is very different in the ion-beam case, with fine grains and numerous dislocations. Both of these effects may lead to improvements in the ability of Er films to reduce He migration, a significant current concern. Er and Sc film studies are planned.

(3) BaTiO₃ thin films for high-density energy storage.

We collaborated with a materials chemist who has produced an ablation target containing sintered BaTiO₃. If the stoichiometric ratio of this compound is preserved in the deposited thin-film layer (congruent deposition), the resulting dielectric constant will be 3,500. This could lead to considerable improvements in energy-storage density for such items as capacitors and Marx generators. In addition, we produced a candidate target for superconducting yttrium barium copper oxide (YBCO) films under other work.

Both of these effects may lead to improvements in the ability of Er films to reduce He migration, a significant current concern. Er and Sc film studies are planned.

28764

Low-Intensity Laser Triggering of Spark Gaps

G. M. Loubriel, F. J. Zutavern, M. W. O'Malley

Extremely low energy (less than 1 mJ) laser-triggered spark gaps have been demonstrated by injecting magnesium (Mg)-aerosol particles into the gap. This result could revolutionize optically triggered gas-switching technology by enabling direct control of plasma-breakdown-based systems. Examples of such systems are high-power spark-gap arrays with remote optically isolated semiconductor or fiber-optic lasers. This project seeks to demonstrate this effect and to study the viability of using such a system to reduce laser-energy requirements for future pulsed-power inertial confinement fusion (ICF) drivers and other optically triggered spark-gap systems.

Sandia seeks a low-level effort because we have suitable lasers and diagnostics (harmonic generation of 1.06μ neodymium [Nd]:YAG or tunable $\text{Ti:Al}_2\text{O}_3$ with 100-femtosecond to 10 ns pulsewidths, fiber-amplified or gain-switched semiconductor lasers with pulsewidths as short as 30 ps under development), a variety of spark-gap housings, and a generator for the Mg-aerosol particles. The plan is to suspend a very low density (10^5 or $10^6/\text{cm}^3$) cloud of 100 nm size Mg particles in an argon/silicon-fluorine₆ (Ar/SF_6) gas mixture and then illuminate the gap with unfocused-laser radiation. The effect of the laser is to generate seed electrons by photoemission from the Mg particles, which then allows for a multichannel discharge. Our unique contributions to this research would be advanced spark-gap technology, short-pulse laser technology (solid-state, semiconductor, and fiber lasers), and a wide range of electrical and optical diagnostics for modeling and optimizing optical triggering. Because this is a nonlinear process, shorter, higher-power optical pulses may decrease the optical-energy requirement and/or improve triggering stability.

We researched several existing (nonaerosol) optically triggered gas-breakdown systems and, in some cases, discussed them extensively with other researchers.

We acquired and assembled a pulse-charging test system and diagnostics. We purchased an optically triggered spark gap and are manufacturing an optically triggered spark

Our unique contributions to this research would be advanced spark-gap technology, short-pulse laser technology (solid-state, semiconductor, and fiber lasers), and a wide range of electrical and optical diagnostics for modeling and optimizing optical triggering.

gap with optical-diagnostic windows. The system is located near a Q-switched $\text{Ti:Al}_2\text{O}_3$ laser that can be tuned and frequency-doubled or -tripled to deliver 200–900 nm radiation in 5 ns long pulses.

We devoted part of this project's initial effort to alignment and optimization for eventual frequency-doubling and -tripling.

We are presently characterizing the optically triggered spark gap without optical diagnostics by measuring risetime, delay, jitter, and the required laser energy as we change particle size, particle density, gas pressure, gas mixture, spark-gap geometry, and optical wavelength. We will use optical diagnostics and spectroscopy to characterize the gas mixture and to analyze the breakdown emission and optical trigger transmission.

We will use optical diagnostics and spectroscopy to characterize the gas mixture and to analyze the breakdown emission and optical trigger transmission.

28766

Enhanced Impulse Experimentation Capability

V. Harper-Slaboszewicz, D. E. Wackerbarth, J. I. Greenwoll

Validation of cold x-ray impulse-response models at a full-system scale is a key element of hostile-environment certification for stockpile-refurbishment activities. Key technical issues include the impulse-generation characteristics of the materials and the propagation of the surface impulse into the system, creating internal-shock environments. Material-impulse-generation characteristics can be determined in scaled experiments, and Z-pinch radiation sources can play a critical role.

A significant problem in these experiments is that impulse-generation time can be quite long, and impulse from debris created in the Z-pinch arrives before the completion of the impulse generation at the surface. Impulse generation by direct deposition into system materials of either x-rays or particle beams (existing sources) cannot meet intensity and uniformity needs over the range of interest.

In this project, Sandia investigates the use of Z-pinch debris as an impulse-simulation source.

We performed an experiment on the Saturn accelerator. The experiment shows that debris from a closed-can wire-array Z-pinch source using a thin (8-mil wall thickness) current-return can produces a reasonably uniform impulse signal. This impulse is produced by material from the current-return can moving radially with a narrow, angular distribution. The available impulse-area product measured on this experiment is about 1000 ktap cm² in a cylindrical band about 2 cm wide. Scaling to Z, up to 10,000 ktap cm² should be available. At least half of the radiation energy from the Z-pinch incident on the debris-source region is converted into kinetic energy of the debris.

The most significant problem of the source in its current form is that the impulse is produced by relatively large particles; this situation results in low simulation fidelity because the shock wave driven into the current-return can by the radiation is attenuated by the time the wave reaches the outer surface of the can. However, the use of a high-photon energy-radiation source, in conjunction with a thinner current-return can, should (according to initial calculations) allow the

This photo shows the debris pattern produced by the closed-can Saturn Z-pinch experiment for enhanced impulse experimentation capability. It shows both the cratering by the particulate debris and the uniform deposition of melted debris.

In this project, Sandia investigates the use of Z-pinch debris as an impulse-simulation source.

shock to be sufficiently strong to melt the whole current-return can. This source requires considerable refinement to be usable for impulse simulation, but the required enhancements appear feasible.

28769

Z-Pinch Power-Plant System Development

G. E. Rochau, C. W. Morrow, Jr., A. R. Parker, G. L. Benavides, C. L. Olson, R. E. Olson, K. W. Struve, S. A. Slutz, G. A. Rochau

The Z-Pinch Power Plant (ZP-3) is the first concept to use the spectacular results at Z in a power-plant application. While the initial concepts and calculations applying high-yield fusion look very promising, there are significant technical issues to be addressed. The highest-priority issues are system studies for creating a definition of the system, integrated blanket design for absorbing the fusion energy, cartridge manufacture of all the recycled materials, and cartridge installation/replacement to maintain a reasonable duty cycle. An effective system design for ZP-3 requires an integrated blanket, which can shield the permanent structures from the high-energy neutron flux and the strong shock wave, breed tritium (T), and in the process absorb the released fusion energy. Through this technique, Sandia intends to minimize the shock propagation by dispersing the energy absorption over the volume of the blanket structure. The generation of this energy requires a fusion fuel cartridge to couple the repetitive pulsed power to a replaceable load using a recyclable transmission line (RTL). Innovative engineering will be required to economically manufacture the required cartridge. The ZP-3 represents a fifth-generation nuclear power source without the burden of long-lived radioactive

The Z-Pinch Power Plant (ZP-3) is the first concept to use the spectacular results at Z in a power-plant application. ... Sandia intends to minimize the shock propagation by dispersing the energy absorption over the volume of the blanket structure.

Details of Z-pinch power-plant crucible.

waste or nuclear proliferation. As such, this system description will provide a cornerstone for launching a concept exploration initiative in fusion energy and potentially lead to large experimental and pilot facilities.

We addressed all four of our current scientific priorities: integrated blanket design, cartridge manufacture, system studies, and cartridge installation/replacement. Each of these areas allowed us to complete one concept of a Z-pinch-driven power plant.

- *Integrated blanket design.* We selected a preliminary design of an energy-absorbing blanket comprising coolant jets with intermittent voids. The approach allowed the x-rays to be absorbed in the initial layer of coolant, and the voids reduced the shock induced by the x-rays. In a similar fashion, the neutrons from the reaction were absorbed in the jets of coolant. The integrated design resulted in more than 90 percent of the fusion energy being absorbed in the coolant within 2 m of the reaction with no detrimental shock to the crucible (chamber) or radiation to reduce the crucible lifetime to less than 40 years.

- *Cartridge manufacture.* We examined the technology available to manufacture the cartridge at rates up to 72 cartridges per minute. We selected carbon steel initially because of the lack of mechanical information on the coolant materials. We found that cartridges could be manufactured at these rates using a four-step metal drawing technique without challenging the state-of-the-art manufacturing capabilities.

- *System studies.* We performed an initial system study to look at system trade-offs to guide the future work. Study results demonstrated that two major issues need to be examined. First is the fusion yield per shot. We examined a range between 1 and 20 GJ of yield. We expect 1 to 3 GJ with today's designs of inertial confinement fusion (ICF) capsules, but this results in the need for 12 Z-pinch units to produce 1100 MWe at a shot rate of 0.1 Hz. As ignition is achieved, new designs may be available that achieve 20 GJ and would result in only one Z-pinch unit for 1100 MWe. The second issue was pulse rate of the Z-pinch unit. We examined a rate between 0.1 and 0.7 Hz. The acceleration of cartridges for installation limits the pulse rate. We currently do not believe that we can tolerate pulse rates higher than 0.7 Hz. A reasonable challenge of 0.3 Hz results in 2 to 3 GJ units, producing 1100 MWe.

The integrated design resulted in more than 90 percent of the fusion energy being absorbed in the coolant within 2 m of the reaction with no detrimental shock to the crucible (chamber) or radiation to reduce the crucible lifetime to less than 40 years.

• *Cartridge installation/replacement.* We examined the complications of installing a human-sized cartridge every 3–10 sec into an 800 K radioactive environment. We found we could achieve the microTorr vacuum in the pulsed-power system, robotically insert the cartridge, and remove it easily within the system requirements. The micro positioning needed exists in today's industrial practices. We envision using hydraulic robots to avoid radiation damage to electronics.

In addition to the four priorities, we also looked at the capsules and how they would be fabricated and inserted into the cartridges. We defined the manufacturing steps for cryogenically layered beryllium (Be) capsules onsite at the rate of 72 targets per minute. These targets include a tungsten (W)-coated foam surrounding the capsule and cooled through liquid-hydrogen (H) reservoirs in a dynamic Hohlraum configuration.

We found we could achieve the microTorr vacuum in the pulsed-power system, robotically insert the cartridge, and remove it easily within the system requirements.

Refereed

Rochau, G. E., G. L. Benavides, M. S. Derzon, C. L. Olson, R. E. Olson, A. R. Parker, G. A. Rochau, S. A. Slutz, K. W. Struve, P. Pankuch, C. Gibson, C. Morrow, P. Peterson, J. Degroot, H. Tran, E. Mogahed, I. Golovkin, G. Kulcinski, R. Peterson, I. Sviatoslavsky, and M. Sawan. 2001. "ZP-3, a Power Plant Utilizing Z-Pinch Fusion Technology." *Proc. 2nd International Conference on Inertial Fusion Science and Applications* (Kyoto, Japan, 10–14 September).

28770

Recyclable Transmission Line Concept for Z-Pinch IFE

S. A. Slutz, C. L. Olson

The rep-rated Z-pinch inertial-fusion-energy (IFE) power-plant concept is an ideal means to extend the single-shot performance characteristics of the present Z machine toward energy applications. This concept uses a recyclable-transmission line (RTL) between the pulsed-power driver and the Z-pinch/target load. In a previous project, candidate materials for the RTL were tested in experiments on the Saturn accelerator and were shown to be viable.

In this project, Sandia investigates the low-mass limit for the RTL. The lowest reprocessing costs should be obtained by minimizing the mass of the RTL. Low-mass transmission lines could also help reduce the cost of a single-shot facility such as the proposed X-1 accelerator and make Z-pinch-driven space propulsion feasible. We performed calculations to determine the minimum RTL electrode mass to provide sufficient inertia against the magnetic pressure produced by the large currents needed to drive the Z-pinches.

(1) We performed calculations to determine the minimum mass required for the RTL for energy applications and space-propulsion applications. The RTL-electrode mass must have sufficient inertia to hold off the magnetic pressure produced by the large currents. Analytical calculations show the mass to be less than 1 kg. (This should be compared with the mass of the transmission line on Z, which is about 5 tons.)

(2) We found the RTL thickness to be much less than the resistive skin depth. This means that the RTL will be resistive and that the power flow to the Z-pinch load may be reduced. Therefore, experiments are necessary to assess the thin-RTL candidate low-mass materials for motion and resistive losses.

(3) We performed experiments on the Saturn accelerator at the 10 MA level to test low-mass materials and measure their resistive losses. We tested three thicknesses of carbon steel (50 μ , 100 μ , and 250 μ) and one thickness of Mylar (20 μ). The results indicate that the tested low-mass materials should carry the required large currents very efficiently.

In this project, Sandia investigates the low-mass limit for the RTL. The lowest reprocessing costs should be obtained by minimizing the mass of the RTL. Low-mass transmission lines could also help reduce the cost of a single-shot facility such as the proposed X-1 accelerator and make Z-pinch-driven space propulsion feasible.

28771

Suppression of Electron Emission from Conductors

D. J. Johnson, K. W. Struve, W. A. Stygar, J. L. McKenney, D. H. McDaniel

This project will test surface-treatment processes on 304L and 316L stainless steel (SS) and anodized aluminum (Al) for the purpose of suppressing electron emission over large planar surface areas to improve the high-voltage hold-off capabilities of the materials. The work with SS is relevant to the vacuum transmission line near the final power flow section on the Z accelerator. Improvements to voltage holdoff with SS will allow smaller transmission line spacing and lower inductance in the final convolute region. This reduction results in higher currents to the Z-pinch load and more efficient x-ray production. The work with Al is relevant to the Al grading rings at the vacuum insulator stack on the Z accelerator. Improved holdoff here will allow an upgrade to the power transmitted across the vacuum interface.

Sandia developed a “crowbar” switch to eliminate multiple reflected pulses from our 50 W cable pulser and provide a controlled variable-width flat-top pulse. Testing required the switch to operate over the testing range of 50 to 160 kV. We used a Physics International (PI) Marx switch, with the gap increased from 1 cm to 2.2 cm and located in an oil-filled container isolated from the test chamber by a vacuum insulator. We achieved the variable-voltage operation by varying the pressure from 0 to 65 psi gauge. A PT55 generator with 50 kV output triggered the crowbar switch with a time jitter of 10 ns. The PT55 was timed to give a 125 ± 10 ns pulsewidth.

We tested 17 cm diameter, 16 rms finish, 304L SS electrodes with 3 mm gaps. The electrodes had Chang curves to avoid E-field enhancement at the edges of surfaces. We treated the test electrodes with the solvent cleaning, chemical polishing (CPol), and hydrogen-vacuum firing (HVFF) processes used for Z-accelerator hardware. The test procedure involved starting at 55 kV and increasing the voltage in 3 kV steps until a short-circuit breakdown occurred. This allowed conditioning of the surface by exploding and removing small-cathode whiskers at low voltages without causing a full anode-cathode gap arc. The test results show a breakdown

This project will test surface-treatment processes on 304L and 316L stainless steel (SS) and anodized aluminum (Al) for the purpose of suppressing electron emission over large planar surface areas to improve the high-voltage hold-off capabilities of the materials.

electric field of approximately 520 kV/cm for the baseline solvent-cleaned 304L. The HVFF, CPol, and HVFF+CPol processes reduced the breakdown field by approximately 10, 20, and 25 percent. These disappointing results will be further checked along with the performance of the gold (Au) coating used on Z-accelerator convolute hardware. We performed most tests with a 304L anode that was diamond-polished before each test. We observed that electrodes used as an anode and sustaining melt marks could be cleaned and used as a cathode with no degradation in hold-off voltage. The cathode could also be reused successfully but only after cleaning to remove the metal chips blown back from the anode during the arcing.

We contracted for treatment of forty-eight 12 cm diameter SS electrodes with their intense pulsed-electron beam to achieve better surfaces for electron-emission suppression. Sandia will get these electrodes back for high-voltage (HV) testing to confirm the factor-of-two increase in voltage holdoff that the Russians report in the literature. The Russians will treat 304L and 316L SS electrodes with surfaces machined perpendicular and parallel to the axis of bar stock and the surface of plate stock. This arrangement will allow testing under the maximum and minimum of grain-boundary edges that allow inclusions such as carbon (C) and sulfur (S) to migrate to the surface and produce bubbles and craters during the treatment process. This variation occurs because grain boundaries in SS are elongated along the axis of the bar and rolling direction of the plate. The craters are thought to be a source of cathode “whisker explosions” that lead to electron emission and plasma formation.

We fabricated the 12 cm electrodes to be treated in addition to twelve 8 cm diameter electrodes of each type HV testing during optimization of the treatment process. We designed and purchased Lucite shipping containers for the 12 cm diameter electrodes to allow shipping in an inert gas. We did a preliminary design of a 300 kV linear-transformer driver to allow E-fields to 1 MV/cm if our collaborators are successful in improving our holdoff by a factor of two.

We performed most tests with a 304L anode that was diamond-polished before each test. We observed that electrodes used as an anode and sustaining melt marks could be cleaned and used as a cathode with no degradation in hold-off voltage. The cathode could also be reused successfully but only after cleaning to remove the metal chips blown back from the anode during the arcing.

28772

Solid-State Switch for Advanced Pulsed Power

F. J. Zutavern, M. W. O'Malley

The next-generation driver for advanced pulsed-power accelerators, Z-pinch, weapons effects, or radiography could be greatly improved and simplified by the use of low-jitter, low-inductance solid-state switches coupled to a very fast prime-power stage. If successful, such a system would not require the use of gas-breakdown switches and intermediate storage capacitors or other pulse-forming lines.

Sandia will build and demonstrate such a high-current switch based on laser-triggered photoconductive semiconductor switches (PCSSs). We will demonstrate the capability to discharge a capacitor bank of 8 nF, direct-current (DC) charged to approximately 200 kV through a PCSS to produce currents of approximately 20 kA (with trigger energy of 1 to 10 mJ). This bank will be composed of eight 4 nF capacitors charged to 100 kV. Optically isolated, low-inductance, high-current PCSSs will connect the capacitors in series and parallel. PCSSs were previously demonstrated to switch 220 kV at 8 kA [1] and 1 kV at 1 kA [2]. For 210 kV/8 kA, we used six switches (each 3.4 cm long, 4 cm wide) in parallel to carry 8 kA for approximately 30 ns at 10 Hz for greater than 10,000 pulses. The 1 kV result was higher-current density, longer pulses (approximately 100 ns), and DC holdoff. This result also demonstrated excellent switch longevity (greater than 1,000 pulses) and can be scaled to the voltages, currents, and size required for this application. The high-current-density scaling would result in a switch length of 6.6 cm and a width of 5 cm for the parameters of this project. The high-gain PCSSs are based on a high-field (greater than 5 kV/cm), avalanche-like effect in gallium arsenide (GaAs) that is triggered with low-energy optical pulses.

One module for this project is to develop one capacitor (100 kV, 4 nF) and the components required to deliver 5 kA. We calculated PCSS dimensions to hold these voltages for 10 msec and conduct these currents in a 100 ns wide pulse. We drew a mask for lithographic fabrication of these switches in the Compound Semiconductor Research Laboratory. We ordered and received the mask and thirty 4-inch, high-

Sandia will build and demonstrate ... a high-current switch based on laser-triggered photoconductive semiconductor switches.

resistivity, GaAs wafers. We fabricated new switches with the new mask and mounted them for testing. We assembled and tested the apparatus for charging two modules in 10 msec or less. This apparatus was operated at low currents (100 A to 1 kA) with PCSSs from previous projects. We made a direct comparison to spark-gap switching and initiated optical-triggering tests.

We are experimentally evaluating triggering options for down-selection. The options include semiconductor laser-diode arrays (LDA) located at each switch or a single large solid-state laser and an optical distribution system. We ordered LDAs to our specifications and are testing them.

Our present understanding of PCSS operation predicts that three 15 mm² by 10 mm² or six 7.5 mm² by 7.5 mm² GaAs switches and six 16-element LDAs are required to switch one module. The best option for triggering is presently believed to be stacked LDAs with 15² mm² switches. Three switches and 48 filaments (three 16-element trigger lasers) are required per module. Two pulse-charged modules are under construction and will be tested in the next 3 months. We will test the modules in series and parallel to switch 100 kV and 10 kA or 200 kV and 5 kA. Inductors will be decreased to demonstrate higher currents and shorter pulses.

*We fabricated new switches
with the new mask and
mounted them for testing. We
assembled and tested the
apparatus for charging two
modules in 10 msec or less.
This apparatus was operated
at low currents (100 A to 1 kA)
with PCSSs from previous
projects. We made a direct
comparison to spark-gap
switching and initiated optical-
triggering tests.*

32576

Isentropic Compression Experiments on the Saturn Accelerator

M. D. Furnish, J. P. Davis, C. Deeney, M. D. Knudson, J. Mason, T. K. Bergstresser, E. W. Marsh, R. J. Hickman, G. A. Mize, D. L. Barker

Recently, an innovative experimental technique, referred to as the isentropic compression experiment (ICE), was developed that allows study of dynamic material response to pressures exceeding 1 Mbar in a single experiment. The resulting pressure-density information generated with the method is crucial for generating the equation-of-state (EOS) of a material, thus significantly reducing the cost and the time for generating and validating theoretical models of dynamic material response. ICE has been successfully demonstrated on several materials using the 20 MA Z Accelerator. This resulted in a large demand for ICE shots from Lawrence Livermore National Laboratory (LLNL), Los Alamos National Laboratory (LANL), and Sandia. The purpose of this project is to extend the technique to another generator, Saturn, that will increase the accessibility to a broader range of applications and further reduce the cost of testing by another factor of five. Successful demonstration of feasibility will make this technology available to a variety of Sandia weapon applications and give Sandia leadership in new initiatives requiring timely evaluation of material properties.

We conducted an initial series of eight experiments. Conclusions from this series were as follows:

- (1) We consistently obtained quality velocity data (eight spots monitored per experiment).
- (2) We obtained a satisfactory current pulse with a smooth 200 ns risetime as one of several module configurations of Saturn that this study evaluated.
- (3) We did not adequately assess drive reproducibility because of many changes in experiment conditions.
- (4) Drive uniformity (panel-to-panel) was somewhat poorer than the 1–2 percent level.
- (5) Pressure levels achievable were approximately 10 GPa for the “LP” cube design and 40 GPa for the “HP” cube design (each of which affords four two-sample panels). (LP is a modular isentropic compression experiment configuration using a 20 mm cathode and 3 mm anode/cathode gap. HP is a

The purpose of this project is to extend the technique to another generator, Saturn, that will increase the accessibility to a broader range of applications and further reduce the cost of testing by another factor of five. Successful demonstration of feasibility will make this technology available to a variety of Sandia weapon applications and give Sandia leadership in new initiatives requiring timely evaluation of material properties.

modular isentropic compression experiment configuration using an 11 mm cathode and a 2 mm anode/cathode gap.)

We performed a second set of four experiments with the following objectives:

- (1) Test a single-sided drive concept before attempting this configuration on the Z accelerator,
- (2) Test a concept that would enable cryogenic ICE experiments to be performed on the Z accelerator, and
- (3) Test the panel-to-panel uniformity and shot-to-shot reproducibility on the Saturn accelerator.

The first objective was successfully met. Again, we obtained quality velocity-interferometry-system-for-any-reflector (VISAR) data, indicating that the experimental configuration will provide a uniform-pressure load, and thus can be fielded on Z with confidence. We also successfully met the second objective. We designed the test on Saturn to evaluate any consequences to power flow of a design that will thermally isolate a portion of the power-flow surface by using a nylon ring. The data obtained suggest no negative consequences, and thus this configuration can be used on Z with confidence.

The final objective was not successfully met. We performed two very similar experiments on Saturn for the purposes of shot-to-shot comparison. Unfortunately, significant current loss, because of arcing in the magnetically insulated transmission lines (MITLs), occurred on one of the experiments. This prevented any meaningful comparison between the shots.

In addition, we conducted several other families of experiments as described here:

- We conducted three experiments on neutron generator (NG) materials that provided useful comparisons between slightly different compositions of lead zirconate titanate (PZT) and aluminum-loaded epoxy (ALOX).
- Infrared (IR) pyrometry yielded useful sample-temperature data.
- Several experiments on premolten tin allowed development of a new technique for isentropically compressing preheated samples, and the experiments appear to have yielded the first observations of dynamic freezing in a liquid metal.

Several experiments on premolten tin allowed development of a new technique for isentropically compressing preheated samples, and the experiments appear to have yielded the first observations of dynamic freezing in a liquid metal.

Corporate Objectives

Sandia collaborates with universities to create new science and engineering for the Laboratories' science and technology base, to train the next generation of scientists and engineers, and to employ complementary resources and skills for achieving common goals. These collaborations improve Sandia's ability to recruit top students for Sandia's work force and ensure Sandia's future as a leader in science and technology.

Sandia aims to integrate new materials into polysilicon-based microfabrication technology. The "Novel Coatings for Microelectromechanical Systems (MEMS) Devices" project is pursuing two classes of new materials: superhard materials and metals. A special effort is being made to develop processes that integrate materials at the microstructure release step because such processes would afford a wider class of materials and a greater degree of flexibility to device engineers. Superhard materials were chosen with the following properties: wear resistance, hydrophobicity,

lubricity, and chemical and thermal inertness. Integration of metals into coatings offers special opportunities for realizing devices such as micro-relays. These novel coatings will enhance the strength and function of existing MEMS technology. Two patent applications have been filed.

10394

An Optically Triggered Semiconductor Switch for Firing Systems

A. Mar, G. M. Loubriel, A. G. Baca, P. A. Smith, L. D. Roose

Conventional high-current firing sets are complicated, demanding systems that require special switches. For Defense Program applications, Sandia uses a sprytron, an electrically triggered, hand-assembled vacuum switch (3 kV/3 kA). Due to the high cost of maintaining a specialized sprytron production facility and the lack of production requirements for the next 3 to 5 years, Sandia has made the decision to close the production line at EG&G that is dedicated to the production of sprytron switch tubes.

This project will develop an optically triggered gallium arsenide (GaAs) switch that performs as a sprytron but offers the added advantages of semiconductor batch manufacture, compactness, optical isolation, and low jitter. The main challenges in making this device are switch longevity (greater than 100 pulses) and ease of use. The results of this low-current study and improvements in longevity at even lower currents (about 10 A) show that it is feasible to meet the demanding requirements of the firing set application.

The techniques that we will use to improve longevity at kiloamp currents all rely on spreading the current either by using state-of-the-art semiconductor processes such as epitaxial growth, regrowth, and diffusion, or by using improved switch geometries. Such a switch would result in dramatically reduced size, reduced part count, and enhanced surety of firing sets for nuclear weapons including stockpile retrofit. Surety will be enhanced because the switch will enable new architectures, has small size to increase its high-g tolerance and free volume for features such as joint test assemblies, is optically isolated, and allows for state-of-health monitoring. Other switch applications are direct optical ignition, Q-switching lasers for the X-1 accelerator, ground-penetrating radar for environmental site reconnaissance, sensors in low-visibility environments, and high-power microwave generation.

We improved longevity at 1 kV/1 kA to 466 shots. This result employed a single-gap photoconductive semiconductor switch (PCSS) with a wider gap than previously for distributing the current, low-stress indium (In)

This project will develop an optically triggered gallium arsenide (GaAs) switch that performs as a sprytron but offers the added advantages of semiconductor batch manufacture, compactness, optical isolation, and low jitter.

solder-plating of the contacts, a diode-stack laser array, and optimized optics for anamorphic imaging of this array onto the switch for multiline triggering.

We improved PCSS longevity operating at 3 kV/3 kA. We developed a new structure using interdigitated electrodes to maximize the 3 kV/3 kA lifetime. Our new devices are able to repeatedly generate 24 parallel filaments simultaneously using a laser diode array of only eight emitters. The contacts in these devices are also solder-plated with In. We achieved 75-shot lifetime at 2.5 kA and 25 shots at 3 kA using the new devices. The interdigitated electrode structure results in current flow orthogonal to the filaments. This does not typically occur in the conventional single-gap PCSS. This lateral current flow has a magnetic field associated with it that causes the filaments to spread, or “fan,” resulting in a more diffuse current distribution. The evidence of these magnetic effects offers the intriguing possibility of their further leveraging to improve current distribution and lifetime.

New tests of rad hardness performed at Sandia demonstrate that PCSSs are able to function at various timings *during* the rad exposure, a more stringent condition than the previous year’s tests (which demonstrated functionality of 50 ms *after* the exposure.) The tests demonstrate that PCSSs are capable of holding high voltage during radiation exposure, and that the peak current switched degrades between 30 and 50 percent in the radiation environment, depending on the dose rate. This gives a system designer an idea for how much “margin” to design into an apparatus that must function in this environment.

We improved PCSS longevity operating at 3 kV/3 kA. We developed a new structure using interdigitated electrodes to maximize the 3 kV/3 kA lifetime. Our new devices are able to repeatedly generate 24 parallel filaments simultaneously using a laser diode array of only eight emitters.

Refereed

Mar, A., G. M. Loubriel, F. J. Zutavern, L. D. Roose, A. G. Baca, G. J. Denison, P. A. Smith, M. W. O'Malley, and D. J. Brown. 2001. “Fireset Applications of Improved-Longevity Optically Activated GaAs Photoconductive Semiconductor Switches.” *Proc. IEEE International Pulsed Power Conference 2001* (Las Vegas, NV, 17 June).

10407

Information Extraction from Hyperspectral Images Obtained from Satellites

D. M. Haaland, J. A. Timlin

In this research, Sandia applied a variety of newly developed multivariate analysis tools to the analysis of multispectral image (MSI) and hyperspectral image (HSI) data generated from imaging spectrometer systems to be flown on satellites for target recognition applications. We hypothesized that Sandia's newest proprietary generalized augmented classical least-squares (ACLS) methods would be able to more efficiently extract quantitative and target recognition information from multispectral and hyperspectral images. These methods included spectral-residual-augmented classical least-squares (SRACLS) and score-augmented classical least-squares (SACLS) that use eigenvector decomposition of estimates of the image error covariance data from mean-centered image repeats to eliminate spectrometer artifacts, correlated errors, and nonuniform error variance from the image analysis.

A spectral image that is repeatedly measured will be able to yield an estimate of the image error covariance if the sample does not move or change between images. An eigenvector decomposition of the mean-centered repeat spectral images will yield scores that represent the systematic errors in the concentration maps, while the eigenvectors will represent systematic errors in the estimated pure-component spectra. In combination, SRACLS and SACLS were able to iterate to better models for spectral unmixing of pixels in HSIs.

We tested these new information-extraction methods with spectral data from Sandia's information-efficient spectral-imaging sensor (ISIS) system and infrared (IR)-imaging system. We used the ISIS spectrometer to look at fluorescence spectra from binary mixtures of fluorophores in a mixed sample. We used the IR-imaging system to investigate the oxidative degradation from a neoprene sample. We were able to show that the new algorithms could be coupled with methods using augmented-constrained alternating least-squares methods to eliminate systematic spectrometer artifacts. We used the fluorophore sample to confirm that multivariate-curve resolution (MCR) with ACLS implemented

In this research, Sandia applied a variety of newly developed multivariate analysis tools to the analysis of multispectral image (MSI) and hyperspectral image (HSI) data generated from imaging spectrometer systems to be flown on satellites for target recognition applications.

could accurately reproduce the measured fluorophore emission from the image spectra without introducing any concentration or pure-component spectra in the MCR algorithm.

With the IR image of aged neoprene, serious system artifacts were present in the spectral image data. Without the new ACLS methods, the MCR analyses had greater noise on the estimated pure-component spectra and a serious striped artifact present in the estimated composition maps. With the new ACLS methods added to the MCR analysis, we were able to nearly eliminate these artifacts by augmenting the MCR alternating least-squares algorithms with scores and eigenvectors from the mean-centered image repeat spectra. In addition, these newest algorithms should have the ability to reduce the detrimental effects of atmospheric variations in viewing angle, elevation, and atmospheric interferants such as water vapor and carbon dioxide.

With the new ACLS methods added to the MCR analysis, we were able to nearly eliminate these artifacts by augmenting the MCR alternating least-squares algorithms with scores and eigenvectors from the mean-centered image repeat spectra.

Refereed

Haaland, D. M., and D. K. Melgaard. 2001. "New Augmented Classical Least-Squares Methods for Improved Quantitative Spectral Analyses." *Vibrational Spectroscopy* (Amsterdam, Netherlands), submitted.

Other Communications

Haaland, D. M., F. W. Koehler, IV, and C. M. Wehlburg. 2001. "Improved Multivariate Analysis of Hyperspectral Images with the Use of the Error Covariance." Paper presented to the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, Detroit, MI, 7–12 October.

Koehler, F. W., IV, D. M. Haaland, and M. Celina. 2001. "MNF Transform Improvements in the Quantitative Analysis of FT-IR Spectroscopic Image Data." Paper presented to the Pittsburgh Conference, New Orleans, LA, 4–9 March.

10409

Capillary Elastohydrodynamics in Manufacturing Processes

P. R. Schunk

All coating processes involve dynamic wetting. At the dynamic wetting line, the fluid contacts the solid and displaces air as the wetting line spreads across the solid surface. The speed of the dynamic wetting line results from the balance of fluid mechanics, interfacial surface tensions, and substrate elasticity.

In dynamic wetting problems treated by continuum theory, two stress singularities arise at the dynamic contact line: a singularity in the fluid stress and a singularity in the elastic stress. The singularity in the fluid stress is well known and arises from conflicting boundary conditions (BCs) that require the fluid velocity to be double-valued at the contact line; commonly, this singularity is removed by allowing slip local to the contact line. The singularity in the solid stress arises from surface tension forces acting on a line of zero thickness, which leads to a kink in the solid surface. The singularity in solid stress is removed by distributing the surface tension forces over a region of finite thickness, by solving a macroscopic equation for conservation of momentum near the contact line, or by replacing the momentum conservation equations by geometric constraints on the angles between the fluid, solid, and vapor interfaces.

This project developed a finite-element (FE) formulation for solving fluid mechanics and solid mechanics along with dynamic wetting. To accurately resolve the free surface shape and conserve mass and momentum, Sandia placed a computational node at the dynamic wetting line, which can move across the solid surface. We used arbitrary Lagrangian-Eulerian (ALE) mesh motion to allow the mesh displacement within the mesh to be different from the displacement of the underlying fluid-solid material, while the boundaries of the mesh conform to the surfaces of the fluid-solid material. Pseudosolid mesh motion is used to control the deformation of the mesh, a fictitious compressible elastic solid. The solid substrate, however, is treated as an incompressible elastic medium with the Mooney-Rivlin constitutive law characteristic of rubber materials. The fluid-solid interaction at the interface is treated by interfacial momentum balances—no slip and no penetration. There are

This project developed a finite-element formulation for solving fluid mechanics and solid mechanics along with dynamic wetting.

several formulations for the BCs at the dynamic contact line that we tested, i.e., whether to apply fixed angles between the solid, liquid, and gas interfaces, or add line forces into the momentum balances to account for surface tension. We applied the model to dynamic wetting in the upstream gap of a slot coater with a deformable substrate. In slot coating, the motion of the dynamic wetting line has significant influence on the stability of the coating process.

We analyzed the singularities at the contact line and used the results of the analysis to guide the development of a numerical method for predicting contact line motion on flexible solids. We applied the model to dynamic wetting in the upstream gap of a slot coater with a deformable substrate.

In slot coating, the motion of the dynamic wetting line has significant influence on the stability of the coating process. A comparative study shows that the flexibility affects the stability of the coating flow. The results demonstrate that the coating liquid and substrate properties, and operating parameters such as speed of solid, coating gap, and downstream pressure, influence motion of the contact line. An increase in downstream pressure or decrease in surface tension pushes the contact line further into the gap. However, substrate deformation can reduce the sensitivity of the contact line location because a decrease in substrate stiffness decreases the coating gap at the contact line. The model developed in this project is the first published FE model for dynamic wetting on flexible solid surfaces accounting for macroscopic substrate deformation at the wetting line.

The model developed in this project is the first published FE model for dynamic wetting on flexible solid surfaces accounting for macroscopic substrate deformation at the wetting line.

Refereed

Cairncross, R. A., and S. Madasu. 2000. "A Finite-Element Formulation for Modeling Dynamic Wetting on Flexible Substrates Applied to Upstream End of a Slot Coater." Paper presented to AIChE Annual Meeting, Los Angeles, CA, 3 November.

10729

Ultraminiaturization of RF Circuitry

G. R. Sloan, C. E. Sandoval, K. W. Plummer

Many synthetic-aperture radar (SAR) and radar-responsive tag applications now require microwave electronic miniaturization that is well beyond Sandia's current state of the art. However, recent advances in Lockheed Martin's (LM's) high-density interconnect (HDI) technology, in conjunction with Sandia's new research in microwave microelectromechanical structures (MEMS) and solid-state devices, position Sandia for a major breakthrough. This project proposes the development of a revolutionary radio-frequency (RF) capability by adapting HDI to advanced Sandia technology and applying the result to a multitude of advanced radar applications. Potential new applications that these advances would make possible in the national interest are legion. For example, next-generation SARs for guided munitions and small unmanned aircraft must be reduced in size by five to ten times. This technology also is deemed critical to Sandia's next-generation RF tag programs.

From the beginning, the primary goal of this project has been to evaluate the applicability/adaptability of HDI technology to Sandia radar and tag circuitry. The secondary goals are (1) to apply HDI to Sandia devices (e.g., RF MEMS and indium phosphide [InP] transistors), and (2) to support the development of ultra-efficient amplifiers.

We made substantial progress despite obstacles. We fabricated and fully tested our first prototype module. In general, test results were mixed. We were not able to provide a viable RF MEMS component for inclusion in an HDI module; however, we did prototype several high-efficiency amplifier designs. Again, the results were mixed: The exotic InP devices showed promising efficiency, but were very difficult to stabilize. HDI miniaturization is impressive, but appears to cause about a decibel of insertion loss per monolithic microwave integrated circuit (MMIC). Distributed structures model well, but the measured loss at Ku band appears to be about 15 percent higher than expected. Also, it is disappointing that LM experienced a significant processing problem; a good explanation and corresponding resolution is needed prior to the follow-on fabrication.

This is a SEM photograph of the FIB cross-section of a functional HDI interconnection via. Note that the first metallization layer extends all the way to the bottom of the via. (The via diameter is on the order of 50 microns.)

... recent advances in Lockheed Martin's (LM's) high-density interconnect (HDI) technology, in conjunction with Sandia's new research in microwave microelectromechanical structures (MEMS) and solid-state devices, position Sandia for a major breakthrough.

The following is a summary of specific recent accomplishments and key results:

- We procured, prepared, tested, and delivered the MMICs for the prototype HDI module. This process involved (1) machining and plating silver shims, (2) mounting die on shims, and (3) testing die to certify basic functionality.

- We wrote a simplified HDI design guide oriented for internal use. In conjunction, standard HDI “cells” were designed in AutoCAD. Our goal is to facilitate access to this microwave technology by other Sandia organizations without a steep learning curve for them. One organization has expressed great interest in utilizing our technology for tag miniaturization.

- We fabricated 16 modules on two carriers. The first modules went from actual fabrication to final delivery in seven months and were 20 percent under budget. The prototype module design consisted of four MMICs (switches, phase shifter, and low-noise amplifier [LNA]), five transmission line test structures (microstrip, coplanar, and stripline variants), and two distributed designs (multilayer coupler and bandpass filter). We gathered a substantial amount of data on the modules. We documented a detailed description of the test matrix and the results in an internal memorandum. The primary purposes of the testing were (1) to verify model accuracy, (2) to assess effects of HDI encapsulation on X and Ku-band MMICs, (3) to determine the performance of various HDI transmission line structures at X through Ka band, and (4) to determine if MMIC air bridges can be protected via glue ablation.

HDI packaging increased the insertion loss of all the X/Ku-band MMICs by about 1 dB. The bandwidth and the return losses of the switch and phase shifter were not significantly affected. However, the bandwidth of the X-band LNA decreased at the upper end by about 20 percent. The relative phase shift of the phase shifter was unaffected, and the dozens of air bridges on this complicated chip were not harmed. All the transmission line structures were predictable. The transmission line test structures were usable up to about 35 GHz. At frequencies greater than X-band, the loss is slightly greater than expected. This effect is modelable by increasing the dielectric loss tangent. The measured data for the distributed structures (coupler and filter) agreed well with the models.

A few modules had vias that were found to have high resistance. We used ion-beam milling and scanning electronic

We fabricated 16 modules on two carriers. The first modules went from actual fabrication to final delivery in seven months and were 20 percent under budget. The prototype module design consisted of four MMICs (switches, phase shifter, and low-noise amplifier [LNA]), five transmission line test structures (microstrip, coplanar, and stripline variants), and two distributed designs (multilayer coupler and bandpass filter).

microscopy (SEM) imaging to evaluate/compare good and bad vias. The images we obtained clearly show that the bad vias had incomplete metallization.

- We completed and fabricated several prototype designs for a novel, ultra-efficient power amp based on InP devices and magnesium titanate matching structures. The devices were obtained via an existing partnership with Sanders, and the matching structures were fabricated at Sandia. Prototypes were designed for 1, 2, and 4 mm devices. The designs showed promise in terms of efficiency and output power, but suffered from stability/runaway problems. Evaluation of the prototypes showed that the exotic InP devices are very difficult to stabilize and are subject to lethal runaway problems. We believe that an improved nonlinear model is needed before follow-on designs/modifications should be attempted

We are currently designing a follow-on module, most likely for a tag application. Also, we hope to evaluate HDI packaging of Sandia RF MEMs devices.

We completed and fabricated several prototype designs for a novel, ultraefficient power amp based on InP devices and magnesium titanate matching structures. The devices were obtained via an existing partnership with Sanders, and the matching structures were fabricated at Sandia.

10731

An Actuator Based on an Electrokinetic Pump

A. D. Oliver, C. W. Vanecek, A. M. Morales, E. F. Hasselbrink, R. M. Lee

This project seeks to enable advanced miniature actuators. Ongoing efforts to miniaturize conventional systems have created a requirement to develop a small-format mechanical driver capable of producing approximately one newton of force. We propose to meet these needs by using a new type of drive based on a unique patent-pending Sandia technology, the electrokinetic pump (EKP). The EKP is a microfluidic device that converts electrical power directly to high-pressure fluid hydraulic power.

In the laboratory, we demonstrated EKP-generated pressures to over 9000 psi at a performance exceeding 10 psi/V applied. The challenge is to take this laboratory technology to the prototype stage. Our plan is to pursue this objective in a miniaturized advanced conventional format device. We propose to use an EKP to drive a miniature mechanism. A 2 mm long EKP operating at 10 V and connected to a 100 μm diameter actuator will provide 10 mN of force to the device. The actuator will convert hydraulic force to mechanical movement by means of a bellows at the end of the capillary. The interface between the bellows and the mechanism will be a miniature linkage.

Previous versions of the EKP used silica-bead media packed into a less than 300 μm diameter silica capillary. These capillary devices are fritted using thermal fritting, which is not practical for a 3.7 cm diameter pump. Initial attempts to frit and pack large-area pumps were unsuccessful due to the extremely high pressures necessary to achieve high packing density. Due to the large cross-sectional area of the pump, high pressure leads to large forces exerted on a frit and a high probability of the frit cracking. Furthermore, it was impossible to find commercial frits compatible with 1 μm silica beads.

While we were devising an engineering means (namely, frit supports and thermal annealing, to reduce the frit pore size) to overcome this problem, we encountered a competing technology that uses a monolithic plug of porous polymer to side-step the problem. The porous polymer media is attractive because it can be cast to the desired shape, and it

In the laboratory, we demonstrated EKP-generated pressures to over 9000 psi at a performance exceeding 10 psi/V applied. The challenge is to take this laboratory technology to the prototype stage. Our plan is to pursue this objective in a miniaturized advanced conventional format device. We propose to use an EKP to drive a miniature mechanism.

does not require frits. Thus, frit leakage and cracking concerns may also be side-stepped for improved device reliability.

Finally, we realized that the performance of silica beads suffers strongly if the solution pH falls much below 7, as occurs in a high-flow-rate pump due to hydrolysis at the electrodes. The charged surface groups in polymer media do not suffer from this problem (typically, zeta potential is constant over a wide range of pH). Therefore, we pursued this avenue as the most likely candidate for “best technology.”

We devised a proof-of-principle experiment to test the possibility of using porous polymers rather than packed silica beads. We constructed a 1 cm diameter cylindrical porous polymer monolith that allowed for easy characterization of cylindrical plugs of varying length. We tested various polymer monolith recipes. The best performance to date was achieved by a polymer formulation at Sandia-Berkeley.

Tests performed on the polymer pump showed a flow rate of 0.15 mL per minute, which is the same order of magnitude that is required for a stronglink actuator. We also conducted frequency-response tests at 0 to 20 Hz. These tests found that the slew rate of the pump was constant up to 20 Hz (i.e., the amplitude of the stroke scaled inversely with frequency), which was expected. This finding validated the applicability of high-flow-rate EKPs to alternating current (AC) applications.

We performed maximum pressure tests by connecting the pump output dead-ended into a pressure transducer. Unfortunately, polymers developed at Berkeley and Sandia showed a very wide pounds-per-square-inch/volt value, and scanning-electron microscopy (SEM) of the polymers revealed that the pore size varied significantly from plug to plug. In retrospect, since the pores are generated by phase separation (an inherently thermodynamically unstable process), this variance is not surprising. Nevertheless, we devoted considerable effort to generating smaller pore polymer formulations by Sandia in separate work. Unfortunately, the best values of any polymer formulation were found to be about 0.3 ppsi/V, and typical values were found to be about 0.1 ppsi/V, compared with up to 10 ppsi/V for packed silica beads.

Thus, we tentatively conclude that, for the time being, a silica bead-based pump is the only option that would provide a pump that is a viable alternative to competing

We devised a proof-of-principle experiment to test the possibility of using porous polymers rather than packed silica beads. We constructed a 1 cm diameter cylindrical porous polymer monolith that allowed for easy characterization of cylindrical plugs of varying length. We tested various polymer monolith recipes.

technologies (e.g., piezoelectric pumps). However, silica beads have a zeta potential that is strongly dependent on pH, and this interrelationship leads to hydrolysis problems.

Refereed

Paul, P. H., D. W. Arnold, D. W. Neyer, and K. B. Smith. 2000. "Electrokinetic Pump Application in Micro-Total Analysis Systems: Mechanical Actuation to HPLC." *Proc. Micro-Total Analysis Systems 2000* (Kluwer Academic).

Other Communications

Hasselbrink, E. R., Jr., M. C. Hunter, W. R. Even, Jr., and J. A. Irvin. 2001. "Microscale Zeta Potential Evaluations Using Streaming Current Measurements." Sandia Technical Report SAND2001-8193, Sandia National Laboratories, Albuquerque, NM (May).

10739

Laser-Assisted Microgas Metal Arc Welding

P. W. Fuerschbach, R. A. Anderson, L. A. Bertram

Laser-beam welding is the principal welding process for the joining of nuclear weapon components because it provides a small fusion zone with low overall heating. However, laser energy absorption is extremely sensitive to variation in surface conditions and dimensional tolerances, and improved process robustness is needed. The current widespread use of robotic welding in U.S. manufacturing has demonstrated the reliability of gas metal arc welding (GMAW) for assembly of components with looser tolerances. Despite the robustness and metallurgical advantages of a filler metal process, GMAW has not been suitable for Sandia components because the scale of the resulting welds is too large.

Sandia is leveraging knowledge of the interactions between laser beams and arcs into developing a hybrid-filler, metal-based welding process. We are advancing a wholly new welding process by combining a fiber-optic-delivered Nd:YAG laser with a miniaturized GMAW system. The laser-assisted micro-GMAW process couples the process advantages of these two unique heat sources and enables process capabilities never before obtained with arcs and only alluded to with lasers.

The problems that arise with smooth melt-in of the miniature wire in micro-GMAW can be overcome with the assistance of a fiber-delivered laser beam. Additional workpiece heating and fusion-zone dimensions can be selected and independently controlled with the laser assistance. A research program is investigating this technology as a robust method for joining weapon components with metallurgical control. The project combines the skills of several experts who have many years' experience in analyzing electric arcs and laser beams.

In previous work, we were unable to consistently obtain droplet detachment from a 0.25 mm diameter microwire arc. Consequently, decoupling wire detachment from arc heating became the primary focus of project experiments. We investigated three distinct methods of droplet detachment.

Sandia is leveraging knowledge of the interactions between laser beams and arcs into developing a hybrid-filler, metal-based welding process.

We are advancing a wholly new welding process by combining a fiber-optic-delivered Nd:YAG laser with a miniaturized GMAW system.

(1) The first method investigated for microwire welding relies on arc forces in a detached tungsten (W) arc to propel the molten droplet to the workpiece. We assembled a test-bed with a high-speed video camera to record droplet motion. By focusing a Nd:YAG laser on the workpiece below the detached arc, we obtained base metal heating and melt-in of the droplet. We used a pulse arc power supply to melt the tip of the 0.25 mm wire and simultaneously detach the droplet. Testing with this setup revealed that we could not consistently propel the droplet to the selected workpiece location. Variations in initial tip condition significantly affected the detachment. This approach also required the location of the small-diameter wire precisely near the 1.0 mm W tip. The volume of wire melting was significantly affected by the position.

(2) The second method also relied on a detached W arc for droplet heating and used a servo-motor to drive the wire and droplet to the location on the workpiece where the laser beam was focused. Although this approach was technically challenging, we obtained encouraging welds. We found that a significantly large weld pool was required to obtain consistent droplet detachment. Droplet diameter was larger than for the first method since a 0.5 mm wire was required in the continuous current arc. As a result, the welds obtained were not significantly different from welds obtained with more conventional processes.

(3) The third method also relied on a servo-motor to propel the droplet. But instead of dipping the droplet into the weld pool, the servo rapidly accelerated the droplet on the end of the wire and obtained detachment by mechanical force instead of surface tension. We obtained rapid motion of the wire with a computer-controlled brushless servo-motor that accelerated and decelerated the wire after each current pulse in the detached arc. As with the first method, we found the initial condition of the wire to be critical in determining the direction of the droplet motion. In addition, stable and consistent detachment of the droplet could be obtained only with large drop diameters. To scale the process down for very small diameter wires is not feasible since an even greater surface tension force would need to be overcome with a small-diameter wire. Modifications to the servo-motor drive system and software were not sufficient to obtain wire accelerations greater than 10 g. It is thought that up to 100 g accelerations would be necessary to obtain consistent droplet detachment.

The second method also relied on a detached W arc for droplet heating and used a servo-motor to drive the wire and droplet to the location on the workpiece where the laser beam was focused. Although this approach was technically challenging, we obtained encouraging welds. We found that a significantly large weld pool was required to obtain consistent droplet detachment. Droplet diameter was larger than for the first method since a 0.5 mm wire was required in the continuous current arc. As a result, the welds obtained were not significantly different from welds obtained with more conventional processes.

Our experiments did not produce a preferred droplet-detachment method. The lack of a robust and precise droplet-detachment method indicated that final development of laser-assisted microwire welding could not be achieved.

10792

Ultrahigh-Resolution Radiography for Detailed Inspection of Weapon Components and Systems

R. B. James, J. J. Cashen, E. B. Duckett

For more than 60 years, x-ray film in combination with phosphor screens has been the standard medium for displaying x-ray images of objects. But despite technical advances in displays, data storage systems, and high-speed communication networks, until now there has been no method for effectively obtaining high-resolution x-ray imaging data in a fully digital format.

Recent successes at Sandia have led to the emergence of solid-state x-ray detectors produced from wide-bandgap semiconductors (e.g., cadmium zinc telluride [CZT]) that are capable of efficient capture and direct conversion of x-ray energy into current. The addition of a detector array makes this digital technology capable of providing full-view imaging for most objects, and the system would be able to read out images electronically with better image quality. Operation of the devices is based on the generation of electron-hole pairs in the detector elements due to absorption of incident x-rays. The charge carriers move under the influence of an applied voltage, and customized electronics read out each detector element for determination of the x-ray flux. The energies of the x-rays are transmitted through an object (i.e., spatial and spectral information).

Modern Silicon Valley manufacturing techniques enable the production of small position-sensitive detector elements for ultrahigh-resolution images of systems and components, while the energy information allows precise determination of the specific elements under study. Together, these features can provide a new, powerful tool for certification of weapon components. A digital x-ray system can also be used for monitoring the state of health of components to allow warnings of impending failure due to aging and/or manufacturing defects. In addition, such a system could be deployed to address issues of reliability and safety of nuclear weapons in the stockpile in the absence of underground testing. Our project goal is to demonstrate an ultrahigh-resolution x-ray imaging system using solid-state technology.

Recent successes at Sandia have led to the emergence of solid-state x-ray detectors produced from wide-bandgap semiconductors (e.g., cadmium zinc telluride [CZT]) that are capable of efficient capture and direct conversion of x-ray energy into current. The addition of a detector array makes this digital technology capable of providing full-view imaging for most objects, and the system would be able to read out images electronically with better image quality.

We are focusing our efforts on two fronts as we continue with our parallel detector development work. For the first detector technology, we pursued further enhancements in the performance of the thick-film polycrystalline mercuric iodide (HgI_2) on amorphous silicon (Si) flat-panel readout imagers. We investigated different methods of detection-layer deposition with the goal of reducing the fraction of unresponsive pixels and rows/columns. At the same time, we continued imaging studies with the 256-by-256 pixels, 60 μ -by-90 μ HgI_2 /alpha-Si pixel array on Rolamites and mechanical safe arm devices (MSADs), to determine the effectiveness of the detector technology at revealing manufacturing and aging-related nonnuclear component defects when compared to traditional film-based techniques. For the second detector technology, we applied our efforts to further the development of processing techniques for producing bulk CZT imagers with large numbers of small pixels. This included the development of means and capabilities for harvesting large single-crystal substrates from large-diameter CZT boules. In addition, we refined photolithographic metal electrode deposition and end-array passivation and encapsulation methods.

... we pursued further enhancements in the performance of the thick-film polycrystalline mercuric iodide (HgI_2) on amorphous silicon (Si) flat-panel readout imagers. We investigated different methods of detection-layer deposition with the goal of reducing the fraction of unresponsive pixels and rows/columns.

10795

Surface-Micromachined Mechanical Timer

R. D. Habbitt, Jr., M. A. Polosky, G. E. Vernon, K. A. Klody, J. A. C. Zamora, M. S. Burg, M. W. Jenkins, R. A. Renn, J. L. Dohner, S. S. Mani, L. L. Lukens

Solid-state oscillators are widely used and are well suited for many applications. However, solid-state timing devices possess two distinct soft spots: They are inherently sensitive to radiation, and they require uninterrupted external power. Surface-micromachined (SMM) mechanical timers offer an elegant solution for applications where solid-state oscillators are not ideal. Mechanical timers are insensitive to radiation and can store elastic energy for long periods of time. In addition, micromachined devices offer a suite of attributes that are quite attractive, e.g., small, light-weight systems that are insensitive to mechanical shock and vibration environments due to their nearly massless part sizes. Also, work is ongoing at Sandia to integrate electronics and optics with microelectromechanical systems (MEMS) devices; this work will eventually provide devices with even greater utility. Recent proof-of-concept MEMS devices demonstrated the feasibility of developing realistic weapon components.

This project will develop multiple mechanical timing mechanisms using Sandia's SMM process. Our vision for each device is based on a wound spiral spring that stores energy and is connected to a gear train. Terminated at the end of the gear train is an escapement mechanism that is used to provide mechanical damping. The escapement mechanism retards the unwind speed of the spiral spring and regulates the device so that timing information can be measured as a function of gear position. Our first timing device will operate like a wind-down timer and, at the end of a prescribed period of time, will close an optical path. The second device serves a mechanical clock function. This device will run for a prescribed duration and possess incremental resolution. An optical circuit consisting of vertical-cavity surface-emitting lasers (VCSELs) and photodetectors positioned above and below the clock gears, respectively, will be used to read coded information embedded in the rotating gears. The optical circuit will be implemented only in concept.

We have realized many successes with the mechanical microtimer. We successfully fabricated and operated a complete timer. We completed several new designs and

This project will develop multiple mechanical timing mechanisms using Sandia's SMM process. Our vision for each device is based on a wound spiral spring that stores energy and is connected to a gear train. ...

We have realized many successes with the mechanical microtimer. We successfully fabricated and operated a complete timer.

submitted them for fabrication. Through this project, we developed and demonstrated the use of Sandia's advanced force measurement capabilities. Finally, we demonstrated the automated testing capability. All of these accomplishments move the microtimer toward becoming a reality.

Our design accomplishments included:

- Completion of the conceptual design for a "clock-like" escapement mechanism.
- Completion of the conceptual design for the optical measurement system.
- Completion of the design for the VCSEL/photodetector assembly using flip-chip mounting techniques.
- Design of new microengines and transmissions (gear-up and gear-down).
- Completion of a preliminary design for a longer-run timer.

Our fabrication build and testing accomplishments included:

- Wafer lots RD22701A, RD22702A, and RD22703A contain the three different timer designs. FP22801A contains the three different gear-pressure angle designs. Wafer lots FP28901A&B and FP29601A contain the new microengine and transmission designs.

- We achieved a very significant step toward obtaining useful output from a microtimer. We fabricated a flip-chip photodetector.

- We built, released, and received FP22801. We evaluated the devices and identified the processing problems. We have used the devices for evaluation to the extent possible. We identified several improvements as a result of the testing and implemented these improvements on RS289 and RS296. These two new submissions will provide data on improved transmission designs and microengine designs. Both the transmission and microengine are primary components of microtimers.

- We built, released, and received RD22701A and RD22702A. We identified and implemented several improvements as a result of the testing. We have used the devices for evaluation to the extent possible.

- We completed the fabrication and release of RD22703A and successfully tested the design. We achieved full operation and observed run-down times of approximately 0.7 sec. Some of the parts appeared to have flaws, and these

Through this project, we developed and demonstrated the use of Sandia's advanced force measurement capabilities. Finally, we demonstrated the automated testing capability. All of these accomplishments move the microtimer toward becoming a reality.

are undergoing further destructive and nondestructive testing and evaluation.

- Fabrication of FP28901A&B and FP29601A is complete.

This project is driving the nondestructive force/torque measurement development. To date, we have demonstrated that the atomic-force measurement tool can nondestructively navigate the microtimer module. We also achieved appropriate contact with a feature of interest—a major accomplishment in the development and characterization of silicon micromachines.

*... we have demonstrated that
the atomic force measurement
tool can nondestructively
navigate the
microtimer module.*

16167

Pseudostationary Separation Materials for Highly Parallel Microseparations

D. L. Lindner

This project is developing new materials for performing separations in highly parallel microseparation systems. The materials synthesis and initial testing are being performed in collaboration with New Mexico Tech. The materials being developed are specialized chromatographic materials known as pseudostationary phases that are easily introduced into microfabricated channels, enable high-performance chemical separations, and can be tailored to provide a high degree of chemical diversity. These developments support a number of Sandia efforts in microanalytical devices based on highly parallel separations. One example is the Accelerated Molecular Discovery Arrays (AMDA) project, which is now part of the new Molecular Integrated Microsystems (MIMS) grand challenge project. This project will develop and apply microscale techniques to the analysis of biomolecules that carry the “signals” that control life processes such as growth, aging, memory, and emotion. The development and implementation of new separation methodologies and materials are central to the MIMS project.

- *Novel co-monomer materials for acrylamido methyl propane sulfonic acid (AMPS) copolymers.* We successfully synthesized and copolymerized dihydrocholesteryl acrylate and t-octyl acrylamide with AMPS. Both polymers provide high-efficiency separations and unique selectivity for selected analytes.

- *Siloxane polymers with varied molar mass.* We synthesized and characterized by electrokinetic chromatography (EKC) nine siloxane copolymers based on three backbones varying in nominal molar mass from 420 to 2270 g per mole. The polymers do not differ significantly in performance or selectivity with changes in molar mass.

- *Siloxane polymers with varied pendant alkyl chain length.* We synthesized, with varying alkyl chain densities, 12 ionic siloxane polymers with alkyl side chains of 5 to 18 carbons. We characterized these polymers by spectroscopy and EKC. The selectivity does not vary significantly among polymers with different alkyl chain lengths, but we observe

This project will develop and apply microscale techniques to the analysis of biomolecules that carry the “signals” that control life processes such as growth, aging, memory, and emotion. ... We successfully synthesized and copolymerized dihydrocholesteryl acrylate and t-octyl acrylamide with AMPS. Both polymers provide high-efficiency separations and unique selectivity for selected analytes.

significant differences in selectivity between polymers with different alkyl chain densities. We presented this work recently at an international conference and have published it.

- *Polymer selectivity.* We characterized the selectivity of a variety of AMPS and siloxane polymers by EKC and also by linear solvation energy relationship (LSER) analysis. This characterization led to the conclusions that the tertiary amine found in the siloxane polymers, and hydrogen (H) bonding along the backbone of AMPS copolymers, have significant effects on the selectivity of the polymers. We have one manuscript regarding this work in press and have published another.

- *Polymers with chiral pendant groups.* We synthesized and characterized siloxane polymers modified with amino acids (alanine, valine, leucine, and proline), glucose, and an AMPS copolymer with dihydrocholesteryl acrylate. However, we did not achieve chiral resolution of test chiral analytes. It is thought that nonspecific secondary interactions with the polymer backbone and/or the lack of polar or H bonding sites on the dihydrocholesteryl group may limit chiral selectivity.

- *Fluorescence and electrochemical detection.* We implemented fluorescence detection in our laboratory and conducted some experiments with electrochemical detection.

- *Separations of derivatized amino acids.* Initial experiments indicate that the siloxane polymers can separate derivatized amino acids with good efficiency and reasonable selectivity. We have not yet observed significant differences in the separation selectivity between the siloxane polymers and sodium dodecyl sulfate (SDS) micelles.

- *Additional accomplishments.* We investigated siloxane and AMPS copolymers for application in buffers modified with organic solvents at concentrations up to 60 percent. We observed the polymers to maintain good mobility and selectivity under these conditions.

We observed concentration enhancements as high as 10,000 using AMPS copolymers for preconcentration of hydrophobic solutes by sweeping. We have submitted this work for publication. We separated 13 of 15 polynuclear aromatic hydrocarbons (PAHs) in less than 2.3 minutes using an AMPS copolymer for high-speed separations. We will submit this work for publication.

We synthesized and derivatized alternating copolymers of maleic anhydride and dodecyl vinyl ether with taurine to yield copolymers of controlled comonomer ratio and

We characterized the selectivity of a variety of AMPS and siloxane polymers by EKC and also by linear solvation energy relationship (LSER) analysis. This characterization led to the conclusions that the tertiary amine found in the siloxane polymers, and hydrogen (H) bonding along the backbone of AMPS copolymers, have significant effects on the selectivity of the polymers. We have one manuscript regarding this work in press and have published another.

architecture. We showed the copolymers to provide efficient and selective separations in EKC.

We disseminated the results of this project in two posters presented at an international conference and in eight manuscripts, including five that are already published, one that is in press, and two that are submitted. Two dissertations and one master's thesis have also been published. The work resulted in invitations to give lectures at two conferences.

Refereed

Palmer, C. P. 2000. "Polymeric and Polymer-Supported Pseudostationary Phases in Micellar Electrokinetic Chromatography: Performance and Selectivity." *Electrophoresis* **21**: 4054–4072.

Peterson, D. S., and C. P. Palmer. 2001. "Alkyl-Modified Anionic Siloxanes as Pseudostationary Phases for Electrokinetic Chromatography I: Synthesis and Characterization." *J. Chromatography A* **924**: 102–110.

Peterson, D. S., and C. P. Palmer. 2001. "Synthesis and Characterization of Novel Anionic Siloxane Polymers as Pseudostationary Phases for Electrokinetic Chromatography." *Electrophoresis* **22**: 1314–1321.

Shi, W., C. J. Watson, and C. P. Palmer. 2001. "Sulfonated Acrylamide Copolymers as Pseudostationary Phases in Electrokinetic Chromatography." *J. Chromatography A* **905**: 281–290.

Shi, W., D. S. Peterson, and C. P. Palmer. 2001. "Effect of Pendant Chain Lengths and Backbone Functionalities on the Chemical Selectivity of Sulfonated Amphiphilic Copolymers as Pseudostationary Phases in Electrokinetic Chromatography." *J. Chromatography A* **924**: 123–135.

17230

Novel Coatings for Microelectromechanical (MEM) Devices

M. P. de Boer

This project aims to integrate new materials (in particular, as thin films) into polysilicon (poly-Si)-based microfabrication technology. Specifically, Sandia is pursuing two classes of new materials: superhard materials and metals. We are making a special effort to develop processes that integrate materials at the microstructure release step, because such processes would afford a wider class of materials and a greater degree of flexibility to device engineers. Consequently, processes will have to allow conformal deposition.

We are choosing superhard materials with the following properties: wear resistance, hydrophobicity, lubricity, and chemical and thermal inertness. Our initial efforts are focused on developing a process to coat poly-Si micromachines with a conformal layer of silicon carbide (SiC), a tough, radiation-hard, corrosion-resistant material that is second only to diamond in wear resistance. Furthermore, in contrast to self-assembled monolayers (SAMs) that do not withstand temperatures employed in packaging technologies, we expect SiC to be much more thermally stable. We shall explore the use of C60 and its interaction with Si to realize a thin conformal SiC layer. Carbon nitride (CN) is predicted theoretically to be even harder. We will explore ways of integrating it into micromechanical structures.

Integration of metals offers special opportunities for realizing devices such as microrelays. Standard metal deposition techniques suffer from being line-of-sight (LOS). One way of circumventing this problem is to use electroless-plating techniques, which are based on coating the structures with a self-assembled organic monolayer with a special end-group functionality that catalyzes the growth of a continuous metallic layer from solution.

In the aforementioned coating processes, little is known about the tribological properties of the resulting materials in thin-film forms. Therefore, we will also characterize these films using surface analytical techniques in our laboratory and specially designed test microstructures. Metal surfaces may be hydrophilic, in which case additional surface modification may be necessary to alleviate stiction.

SiC-coated micromechanical structures: SEM image of Sandia National Labs surface micromachining technology (SUMMiT™) after our coating process.

This project aims to integrate new materials (in particular, as thin films) into polysilicon (poly-Si)-based microfabrication technology. Specifically, Sandia is pursuing two classes of new materials: superhard materials and metals. We are making a special effort to develop processes that integrate materials at the microstructure release step, because such processes would afford a wider class of materials and a greater degree of flexibility to device engineers.

(1) We achieved a conformal layer of SiC on Si by rapid thermal annealing of C60 overlayers as well as by novel low-processing-temperature precursors, including single precursors.

SiC is well known as an attractive material for demanding mechanical and high-temperature applications and in abrasive, erosive, and corrosive media. Hence, it is a promising material for microelectromechanical systems (MEMS) and nanoelectromechanical systems (NEMS) applications in harsh environments, such as Sandia microengines. As it stands, SiC technology remains technically demanding and a nonstandard process in integrated circuit (IC) fabrication laboratories. Our research aims to address this shortcoming. For this effort, we designed and assembled an ultrahigh-vacuum chamber.

- *C60-based SiC films.* We found SiC structures to contain many voids. Given these results, we explored another method for achieving SiC-based MEMS, described next, that appears much more promising.

- *Single-precursor-based SiC films.* This method is based on chemical vapor deposition (CVD) from a single-precursor molecule. The process has several key advantages over the conventional dual-source CVD SiC deposition method: (1) The process demonstrates high-quality stoichiometric films at temperatures as low as 650°C. This temperature is low enough to enable SiC deposition post-processing. (2) The precursor is a liquid at room temperature with vapor pressure of 27 Torr and is rather benign. These characteristics make the handling aspects much simplified when compared to conventional dual-source CVD utilizing such gases as silane (SiH₄). (3) The use of the single precursor eliminates the need for elaborate gas-handling systems. (4) No precarbonization step is needed for deposition on Si and silicon dioxide (SiO₂). (5) The SiC films can be patterned using SiO₂ masking and a simple lift-off using hydrogen fluoride (HF).

The films are of much higher quality than those fabricated by the C60-based approach. The uniformity and conformality of the film are further demonstrated in the next section. We chose to focus on this approach.

(2) We characterized the SiC layer by scanning probe microscopy (SPM) and nanoindentation studies.

We utilized atomic-force microscopy (AFM) to study the topography of the SiC films. Our nanoindentation

... SiC technology remains technically demanding and a nonstandard process in integrated circuit (IC) fabrication laboratories. Our research aims to address this shortcoming. For this effort, we designed and assembled an ultrahigh-vacuum chamber.

experiments were not successful. Therefore, SiC films of varying thickness are deposited on commercially available single-crystalline Si AFM cantilevers to study mechanical properties. By modeling the cantilever as a composite beam of rectangular cross-section and assuming a uniform conformal coating on all sides, we determined a lower bound of 380 GPa for the film Young's modulus, which compares well with the previously reported data on SiC thin films.

(3) We optimized deposition parameters (e.g., time and temperature) *vis-à-vis* the results of the carbide layer characterization.

We examined the effect of 1,3-disilabutane (DSB) pressure and deposition temperature on the SiC deposition. The DSB pressures used in our experiments range between 5×10^{-5} and 5×10^{-4} Torr. The bulk of our work was conducted at a growth temperature of about 800°C. The SiC films are stoichiometric to slightly carbon rich, indicating that Si diffusion is greatly reduced at this temperature.

The most important aspect of this CVD process appears to be the temperature ramp, which helps order the SiC/Si interface, resulting in a higher-quality SiC film crystallinity. The different degree of film crystallinity is evidenced when we do a hot potassium hydroxide (KOH) etch on the films with and without the temperature ramp. The SiC films grown without the ramp show excessive pitting and corrosion.

(4) We integrated electroless deposition of copper (Cu) and gold (Au) coatings into the microstructure release process.

We found that the optimum recipe for deposition of Au by galvanic displacement should contain thiourea. Furthermore, Au deposition must proceed from HF-containing baths (unlike Cu deposition, which proceeds as well in baths containing ammonium fluoride [NH₄F]).

We successfully integrated galvanic displacement plating in the microstructure release process. The structures are rinsed and transferred to an alkanethiol bath to deposit a hydrophobic passivating monolayer on the metal (Cu or Au).

The most important aspect of this CVD process appears to be the temperature ramp, which helps order the SiC/Si interface, resulting in a higher-quality SiC film crystallinity. The different degree of film crystallinity is evidenced when we do a hot potassium hydroxide (KOH) etch on the films with and without the temperature ramp. The SiC films grown without the ramp show excessive pitting and corrosion.

Refereed

- Ashurst, W. R., C. Yau, C. Carraro, C. Lee, G. J. Kluth, R. T. Howe, and R. Maboudian. 2001. "Alkene-Based Monolayer Films as Anti-Stiction Coatings for Polysilicon MEMS." *Sensors and Actuators A: Physical* **91**(3) (July): 239–248.
- Ashurst, W. R., C. Yau, C. Carraro, R. Maboudian, and M. T. Dugger. 2001. "Dichlorodimethylsilane as an Anti-Stiction Monolayer for MEMS: A Comparison to the Octadecyltrichlorosilane Self-Assembled Monolayer." *J. Microelectromechanical Systems* **10**(1) (March): 41–49.
- Magagnin, L., R. Maboudian, and C. Carraro. 2001. "Deposition of Thin Copper Films onto Silicon with Improved Adhesion." *Electrochemical and Solid-State Letters* **C5**: 4.
- Stoldt, C. R., C. Carraro, W. R. Ashurst, M. C. Fritz, D. Gao, and R. Maboudian. 2001. "Novel Low-Temperature CVD Process for Silicon-Carbide MEMS." *Proc. 11th International Conference Solid-State Sensors and Actuators, Transducers 2001* **11** (Munich, Germany, June): 984–987.
- Stoldt, C. R., M. C. Fritz, C. Carraro, and R. Maboudian. 2001. "Micromechanical Properties of Silicon-Carbide Thin Films Deposited Using Single-Source Chemical Vapor Deposition." *Applied Physics Letters* **79**(3) (July): 347–349.

20413

DNA Microarray Technology

G. S. Davidson

DNA (deoxyribonucleic acid) microarrays are revolutionizing the field of genetics and medical research because they allow one to follow the expression of all, or a significant fraction of, the entire genome in experimental organisms. This new tool is exciting because it offers the potential to see the simultaneous interactions of all active genes in a cell and may eventually reveal a great deal of emergent phenomena that could not be detected with smaller experiments. However, because microarray laboratory methods are new and are still relatively uncharacterized, knowledge about their uses, including sensitivity, reproducibility, and other limitations are still being discovered and reported. Further, a researcher has the choice of at least three radically different DNA microarray technologies: DNA synthesized directly on chips, DNA oligonucleotides printed on glass slides, or DNA oligonucleotides printed on nylon membranes. To choose the best technology for an experiment, researchers should have access to comparable assessments of sensitivity, reproducibility, and appropriate protocols for these technologies.

*In previous work, gene expression in the yeast *Saccharomyces cerevisiae* was studied with genome microarrays printed on nylon membranes. Sandia has completed construction of an arrayer to produce microarrays on glass slides, allowing us to compare glass-based and membrane-based arrays. With that experience and equipment, we now seek to carefully investigate the sources of error in the array printing process and in the mRNA (messenger ribonucleic acid) sample preparation process. Successful completion of this work will enable microarrays to be a more reliable and more sensitive tool to investigate gene expression and regulation.*

The collaboration between Sandia and the University of New Mexico (UNM) has been quite successful. Importantly, we jointly developed the ability to conduct and analyze microarray experiments using both commercial gene array membranes and our own arrays printed on glass slides. We analyzed these experiments with commercially available software (e.g., Gene Spring) and with V_xInsight™ (Visual

Successful completion of this work will enable microarrays to be a more reliable and more sensitive tool to investigate gene expression and regulation. ... Importantly, we jointly developed the ability to conduct and analyze microarray experiments using both commercial gene array membranes and our own arrays printed on glass slides.

Explanation and Insight, a tool for exploring data collections), which was developed at Sandia. This collaboration has resulted in improvements to the V_xInsight™ software, joint publications, and numerous presentations. Importantly, it has exposed many students to researchers and research opportunities that would not have been possible without this project.

One of the most important elements of this project was the evaluation and selection of microarray printing tips, various varieties of slides (with and without DNA covalent bonding), and the identification of appropriate RNA processing methods. We evaluated three sources of printing tips, two varieties of slides, and three RNA preparation kits. As a result of this careful evaluation, we can reliably print the entire genome for *S. cerevisiae* on glass slides for use in continuing research programs. The ability to print whole genomes is a particularly important capability because there is no commercial source for microarrays with the genomes of many of the organisms studied, so they must be prepared locally.

... we can reliably print the entire genome for S. cerevisiae on glass slides for use in continuing research programs. The ability to print whole genomes is a particularly important capability because there is no commercial source for microarrays with the genomes of many of the organisms studied, so they must be prepared locally.

Refereed

Werner-Washburne, M. 2001. "Stationary Phase in Yeast: A Genomic Analysis." Paper presented to the International Conference on Yeast Genetics and Molecular Biology, Prague, Czechoslovakia, 26–31 August.

Other Communications

Washburne, M. C., B. E. Wylie, E. Fuge, J. Galbraith, M. Fleharty, J. Beber, and G. S. Davidson. 2001. "Visual Comparison of Genome-Scale Datasets." *Nature*, in review.

Werner-Washburne, M. 2001. "The Yin and Yang of Genomics: Doing it—Microarray Analysis of Stationary Phase Yeast—and Teaching It." (Invited) Talk presented to the National Science Foundation, Arlington, VA, 13 June.

20414

Shock Response of Diamond Crystals

M. D. Knudson

Sandia is investigating the shock response of single-crystal diamond to up to several megabars of pressure in a collaborative effort with the Institute for Shock Physics (ISP) at Washington State University (WSU). This project seeks to determine the following:

- (1) The usefulness of diamond as a window material for high-pressure velocity interferometry measurements.*
- (2) The maximum stress level at which diamond remains transparent in the visible region.*
- (3) The Hugoniot elastic limit (HEL) for the [110] orientation of diamond.*
- (4) Whether a two-wave structure can be detected and analyzed.*

We designed and performed experiments to scope the shock response in diamond in the 2–3 Mbar pressure range, using conventional velocity interferometry techniques (conventional VISAR [velocity interferometry system for any reflector] diagnostic). To perform more detailed and highly resolved measurements, we developed an improved line-imaging VISAR and designed experiments using this technique. Prior to performing these more-detailed experiments, additional scoping experiments are being performed at WSU using conventional techniques to refine the experimental design.

In previous experiments, we observed a two-wave structure in diamond crystals shocked to peak stresses of approximately 2–3 Mbar. From these experiments, we determined that the HEL of [110]-oriented diamond crystals is approximately 900 kbar–1 Mbar. Because of the extremely high wave speeds in diamond, the diamond samples used in these experiments were necessarily very thin, and the time duration of the experiments was likewise quite short. As a result, we found the time resolution of the experiments to be inadequate to fully resolve the features and determine accurately the HEL of diamond.

To perform more detailed and highly resolved measurements, we had to make an improvement in the velocity interferometer (VISAR) diagnostic. We pursued two different approaches. One approach was to improve the time resolution of the conventional VISAR diagnostic. WSU made

We designed and performed experiments to scope the shock response in diamond in the 2–3 Mbar pressure range, using conventional velocity interferometry techniques (conventional VISAR [velocity interferometry system for any reflector] diagnostic). To perform more detailed and highly resolved measurements, we developed an improved line-imaging VISAR and designed experiments using this technique.

some modifications to their VISAR diagnostic that enabled them to utilize much faster time-response recording equipment. This change improved the time resolution by nearly one order of magnitude. An experimental plan was formulated to use WSU facilities to explore the stress range around 1 Mbar with this improved VISAR diagnostic, to better determine the HEL of shocked diamond, and to determine the maximum stress at which diamond remains transparent. These experiments have been designed and are being fabricated. The second approach to improving the diagnostic was to fabricate a line-imaging VISAR diagnostic at Sandia's STAR (Shock Thermodynamic Applied Research) facility. This diagnostic utilizes a streak camera, and, thus, has extremely fast time resolution. The line-imaging VISAR diagnostic is near completion, and we have designed experiments utilizing this design.

This change improved the time resolution by nearly one order of magnitude.

22131

Investigation of Nanoscience Technologies

A. R. Burns

In collaboration with Harvard University, Sandia is conducting research in the general area of nanoscale structures, biomolecular materials, and their application in support of microelectromechanical systems (MEMS) technology. Harvard's expertise is crucial in fostering these fundamentally interdisciplinary developments. Specific areas include

- (1) Nanofabrication that exploits traditional methods (from silicon [Si] technology) and developing new methods.*
- (2) Self-assembly of organic and inorganic systems.*
- (3) The dynamics response on the nanoscale: assembly and dynamics of membranes and microfluidics.*
- (4) Study of the hierarchy of scales in assembly.*
- (5) Innovative imaging methods.*
- (6) Hard (engineering)/soft (biological) interfaces.*

Our focus in the applications of nanotechnology to biological systems has been on the use of a single-membrane pore to measure the length of molecules translocating through the pore. The pore may be of natural origin, such as a self-assembled bacterial protein in a lipid bilayer, or it may be an artificial structure in Si or silicon nitride (SiN).

In collaboration with Harvard University, we designed a probe station base that will accommodate both natural and artificial pore platforms. That probe station is nearing completion. We also acquired the necessary (patch-clamp) test and electronic equipment for measuring picoampere ionic currents. When it is finished, we will perform experiments on the probe platforms. We created solid-state pores less than 10 nm in diameter by an innovative technique of overlapping trenches.

We tested our fabricated SiN structures at Harvard on their probe station. The SiN structures are 5 nm, which is comparable to the protein pores.

In collaboration with Harvard University, Sandia is conducting research in the general area of nanoscale structures, biomolecular materials, and their application in support of microelectromechanical systems (MEMS) technology.

22132

Magnetic Polysilicon MEMS Devices

P. C. Galambos, M. Okandan

Micropumps are key microfluidic components that are needed in many systems that handle fluids at the micro and nano scales. Many different pumping principles exist, but only a few have been explored in the micro world due to limitations in available microfabrication technologies that place great restrictions on micropump design and performance. Recent technical successes in multilevel surface-micromachining (SMM) technology have enabled the development of sophisticated microdevices containing complex planar mechanisms. This technology allows for the fabrication of pumps that utilize a wider variety of the pumping principles used in the macro world as well as explore new pumping principles that are unique to the micro world. Sandia collaborated with Florida State University to develop new designs for a line of SMM pumps that can be driven electrostatically using standard actuators or remotely by magnetic field. We will test, characterize, and optimize the performance of these pumps under various operating conditions.

We made significant progress toward the development of pump mechanisms that are actuatable either magnetically or electrostatically. The designs we fabricated include screw pumps, planetary gear pumps, spiral pumps, viscous pumps, and centrifugal pumps. We also tested a representative planetary gear pump and a representative spiral pump. Both devices rotated as predicted by prefabrication analysis; however, the rotation rates were less than we expected, indicating a significant friction effect. Smaller similar devices should exhibit significantly less friction with a corresponding significant increase in rotation rate. All designs can be driven electrostatically using an orthogonal comb-drive microengine or a torsional ratcheting actuator (TRA). The electrostatic actuators rotate an external gear that, in turn, actuates an internal structure to move fluid. By coating the external gear with a magnetic film, any of the devices can be driven using an external magnet.

In a key step toward the development of magnetically driven MEMS, we deposited micron-thick magnetic films (neodymium-iron-boride [Nd-Fe-B]) on silicon (Si), using a pulsed-laser deposition (PLD) process at Florida State

Sandia collaborated with Florida State University to develop new designs for a line of surface-micromachined pumps that can be driven electrostatically using standard actuators or remotely by magnetic field. We will test, characterize, and optimize the performance of these pumps under various operating conditions. We made significant progress toward the development of pump mechanisms that are actuatable either magnetically or electrostatically.

University (FSU). Since PLD is a line-of-sight (LOS) process, one can envision microns- to tens-of-microns-thick layers of Nd-Fe-B deposited on top of polysilicon (poly-Si) mechanical structures (such as the pumps), which can then be actuated remotely by high-energy magnets.

The SUMMiT (Sandia Ultraplanar Multilevel MEMS Technology) pumps, which we designed for potential magnetic actuation, were also electrostatically actuatable. The electrostatic actuators used to drive the pumps were the previously developed orthogonal comb drives and TRAs. We fabricated three SUMMiT modules (approximately 3 mm by 6 mm per module) of design variations.

Due to the planar nature of the fabrication process, the screw pump consists of a small gear that rotates inside a larger gear past a crescent-shaped flow deflector. This pump design can be turned using electrostatic actuation acting on the outer gear, as can all of the other pump designs. An external magnet could also turn the outer gear if it were coated with a magnetic material. The pump inlet and outlet connections are from the back of the wafer through reactive ion-etched (RIE) holes. We used this inlet/outlet arrangement on all pump designs. We also fabricated a more complex planetary gear pump. The center of the rotating planetary system was offset relative to the external drive gear, resulting in a compressing volume over the outlet during one part of the system's rotation (fluid pushed out), and an expanding volume over the inlet during another part of the system's rotation (fluid pulled in).

The other pump design concept that we investigated also utilized an electrostatically actuated external gear, but this time the pump rotated a disk. The disk acted to throw fluid out from the inlet hole at the center of the pump toward the outlet hole at the edge of the pump. Two forces are at work to move the fluid in the desired direction: centripetal force (more important at higher pump speeds) and viscous drag (the rotating disk pulls fluid along with it). By attaching different vanes to either the rotating disk or the stationary bottom of the pump, we designed different pumps utilizing this basic concept.

We completed initial mechanical testing on one type of gear pump (the planetary gear system) and one type of rotating disk pump (a scroll pump) and are still awaiting the completion of the Bosch etch to test the pumps with fluids. Both pumps turned as predicted, indicating that the kinematic analysis that we conducted prior to fabrication was accurate. The devices tested were several millimeters in diameter, the

We completed initial mechanical testing on one type of gear pump (the planetary gear system) and one type of rotating disk pump (a scroll pump) and are still awaiting the completion of the Bosch etch to test the pumps with fluids. Both pumps turned as predicted, indicating that the kinematic analysis that we conducted prior to fabrication was accurate.

largest devices fabricated. These devices exhibited significant friction that resulted in very slow rotation rates for reasonable actuation voltages of tens of volts. We also fabricated significantly smaller devices. We will attempt to increase the rotation rate with these smaller devices, which should exhibit significantly less friction.

Our objectives for this project were substantially met with the design and fabrication of an array of pumps that are potentially magnetically actuatable. Further work will involve the evaluation of each pump concept and a second design iteration. Our immediate follow-on work will be to test the devices fabricated and to incorporate the information gained into a second set of designs.

Our objectives for this project were substantially met with the design and fabrication of an array of pumps that are potentially magnetically actuatable.

Refereed

Kilani, M. I. 2001. "Development of a Surface-Micromachined Spiral Pump." Dissertation for Ph.D., Florida State University, Tallahassee, FL.

Kilani, M. I., P. C. Galambos, Y. S. Haik, and C. J. Chen. 2001. "Electrostatically Actuated Surface-Micromachined Offset Planetary Gear Pump Design." *Proc. ASME Winter Annual Meeting, MEMS 1* (New York, NY, November): 265–269.

Kilani, M. I., P. C. Galambos, Y. S. Haik, and C. J. Chen. 2001. "University–National Laboratory Collaboration on MEMS Design Education." *Proc. ASME, Winter Annual Meeting, Educational 1* (New York, NY, November): 114–119.

22854

Theoretical Study of Sb as a Surfactant in Epitaxy of III–V Materials

A. C. Ratzel

A key strategic direction for Sandia is development of integrated microsystems. This continuing project will advance the state of the art in new metalorganic chemical vapor deposition (MOCVD) reactor designs and development of next-generation diagnostic tools. A key integration element at the silicon (Si) multichip module level will be an infrared (IR) vertical-cavity surface-emitting laser (VCSEL) to be produced via MOCVD. Unprecedented reproducibility and control of the MOCVD process will be required. In collaboration with the University of Utah, we will evaluate the current design and optimize the next-generation MOCVD reactors and develop in situ diagnostic tools as process monitors.

Our research activities centered on calculating the total energies of various reconstructions for gallium phosphide (GaP), indium phosphate (InP), antimony/gallium phosphide (Sb/GaP), and Sb/InP (001) surfaces. We created surface-phase diagrams by examining surface energy as a function of chemical potential. We used the (2 x 3) and (4 x 3) structures to calculate the surface-induced driving force for copper platinum (CuPt) and triple-period bulk ordering. We performed all calculations using VASP (Vienna *Ab Initio* Software Package) on the University of Utah's and Sandia's high-performance computers.

Our major accomplishments include

- (1) Creation of theoretical Sb/GaP(001) and Sb/InP(001) surface-phase diagrams.
- (2) Identification of Sb-terminated (x3) structures that are stable on GaP and InP materials.
- (3) Verification that replacement of P with Sb in (2 x 4) structures reduces the driving force for CuPt ordering.
- (4) Verification that Sb-terminated (x3) structures produce a driving force for triple-period ordering.
- (5) Strengthening the theory that surface structure influences the bulk properties of III–V materials grown by organometallic vapor-phase epitaxy (OMVPE).

A key strategic direction for Sandia is development of integrated microsystems. This continuing project will advance the state of the art in new metalorganic chemical vapor deposition (MOCVD) reactor designs and development of next-generation diagnostic tools.

Refereed

Wixom, R., and G. Stringfellow. 2001. "Theory of Sb-Induced Triple-Period Ordering in GaInP." *Physical Review B*, accepted.

22995

Single-Wire Explosion Experiments

R. B. Spielman

Modeling of low-temperature (1–50 eV) and low-density ($< 10^{17} \text{ cm}^{-3}$) current-carrying plasmas is difficult because of the interrelation of the plasma resistivity, joule heating, and plasma dynamics. Improvements in the known values of plasma resistivities in the parameter regimes of interest are helping this situation, but validations of the resistivity values when coupled with detailed code calculations are needed before real confidence in the Accelerated Strategic Computing Initiative (ASCI) magnetohydrodynamics (MHD) codes can be achieved.

In collaboration with Cornell University, Sandia will conduct a series of validation experiments in which we compare highly diagnosed wire explosions with predictions made by state-of-the-art ASCI MHD codes such as Sandia's ALEGRA code. These experiments will measure the detailed dynamics of wire explosions as well as the electrical heating caused by the applied current. These measured values will be compared against predictions made by the MHD codes.

Sandia measured expansion rates for the dense, exploding wire cores for several wire materials under these conditions, with and without insulating coatings, and we showed that these rates are related to the energy deposition prior to plasma formation around the wire. The most rapid and uniform expansion occurs for wires in which the initial energy deposition is a substantial fraction of the energy required to completely vaporize the wire. Conversely, wire materials with less energy deposition relative to the vaporization energy show complex internal structure and the slowest, most nonuniform expansion. We also established calibrated radial-density profiles for some silver (Ag) wire explosions, and structural details present in some wire explosions, such as foamlike appearance, stratified layers and gaps.

Studies of the effect of prepulselike conditions on the explosion of one to three wires showed that the wire expansion rate and uniformity were strongly dependent on the amount of energy deposited in the wires during a short (less than 100 ns) resistive heating phase. This resistive phase is terminated by a sudden collapse of the voltage across the wire, probably due to plasma formation. Recent experiments

In collaboration with Cornell University, Sandia will conduct a series of validation experiments in which we compare highly diagnosed wire explosions with predictions made by state-of-the-art ASCI MHD codes such as Sandia's ALEGRA code. These experiments will measure the detailed dynamics of wire explosions as well as the electrical heating caused by the applied current. These measured values will be compared against predictions made by the MHD codes.

demonstrated that it was possible to prolong the resistive heating phase of 25 mm diameter tungsten (W) and 25 mm diameter Ag wires through the use of thin insulating coatings on the wires. The additional energy that was deposited in the wires with insulation resulted in substantial increases in the observed expansion rates of the dense wire cores. Our experiments investigated the current-driven explosions of several different wire materials, including aluminum (Al), titanium (Ti), iron (Fe), copper (Cu), zinc (Zn), niobium (Nb), molybdenum (Mo), Ag, W, gold (Au), and platinum (Pt). The effect of insulating coatings on the rate and uniformity of expansion of individual 25 mm diameter Ag, Cu, and W is also presented, including more data than previously reported for Ag and W. The key parameter appears to be the energy deposited in a wire relative to the total energy required to vaporize it. W was a major element in this study because it is a commonly used wire material in wire-array Z-pinch. This is because it can easily be drawn into wires as small as 4 mm in diameter, has a high tensile strength, and is desirable for x-ray production in the keV range. However, our initial work demonstrated that the resistive energy typically deposited in W wires is a small fraction of the energy required to completely vaporize the wire. Consequently, we observed relatively slow and nonuniform expansion. By contrast, the energy resistively deposited in Ag wires is nearly that required to completely vaporize the wire, and relatively fast and uniform expansion is observed. Therefore, we included Ag wire experiments as a major element in this study because they offered such a contrast to W. In addition, as an intermediate Z material, Ag is well matched to our radiographic backlighting diagnostic. Relatively early in the explosion process, enough x-rays are transmitted through the core to allow quantitative density measurements; later in the explosion development, when the core has expanded to more than 50 times its original diameter, most of the initial mass is still resolvable by the x-rays.

As a general rule, among the many materials tested so far, high-conductivity, low-melting-point materials form more uniform, rapidly expanding columns of wire material. Thus, the core dynamics of W, Pt, Mo, and Ti wires are quite different from the core dynamics of Al, Cu, Ag, and Au wires, and we can classify most materials as belonging to one group or the other. Furthermore, we find that insulating coatings prolongs the resistive heating phase for wires in both groups of materials, thereby increasing the wire core expansion rates.

... our initial work demonstrated that the resistive energy typically deposited in W wires is a small fraction of the energy required to completely vaporize the wire. Consequently, we observed relatively slow and nonuniform expansion. By contrast, the energy resistively deposited in Ag wires is nearly that required to completely vaporize the wire, and relatively fast and uniform expansion is observed. Therefore, we included Ag wire experiments as a major element in this study because they offered such a contrast to W.

Refereed

Sinars, D. B., M. Hu, K. M. Chandler, T. A. Shelkovenko, S. A. Pikuz, J. B. Greenly, D. A. Hammer, and B. R. Kusse. 2001. "Experiments Measuring the Initial Energy Deposition, Expansion Rates, and Morphology of Exploding Wires with About 1 Kiloangstrom/Wire." *Physics of Plasmas* **8** (January): 216–220.

22996

Scattering from Nanostructured Materials

C. J. Brinker

The precise control of porosity in inorganic thin-film materials is important for applications like membranes, sensors, low dielectric constant insulators (so-called low-k dielectrics), and fluidic devices. Although classical sol-gel processing of xerogel films and new low-temperature/-pressure routes to aerogel films allow control of volume fraction porosity over the range 0.2 to 0.9, the distribution of pore size (determined by the response of the gel to drying-induced capillary stresses) can be quite broad, especially for highly porous films.

Over the past 5 years, the extension of the surfactant-templating approach from mesoporous silica powders to films using simple evaporation-induced self-assembly (EISA) procedures has enabled unprecedented control of pore size, orientation, and connectivity. EISA begins with a homogeneous solution of a soluble silica (silicic acid), alcohol, water, and surfactant prepared with an initial surfactant concentration $c_0 \ll$ the critical micelle concentration (CMC), and an acid concentration designed to minimize the siloxane condensation rate. Evaporation accompanying film deposition by dip-coating, spin-coating, inkjet-printing, and other methods concentrates the depositing film in surfactant and silica, inducing the self-assembly of micelles and their further organization into liquid crystalline (LC) silica/surfactant mesophases.

Recent efforts to structurally and chemically characterize the EISA process include spatially resolved spectroscopic studies of molecular probes, imaging ellipsometry, and time-resolved one-dimensional (1-D) x-ray scattering. Here, as in our prior reports employing molecular probes, we exploit the steady-state nature of dip-coating to spatially and temporally resolve the complete EISA process in the coating direction. By performing spatially resolved 2-D grazing-incidence small-angle x-ray scattering (GISAXS) experiments in combination with optical interferometry, we structurally characterize the evolution of a hexagonal thin-film mesophase from a homogeneous precursor solution and its further structural development during drying and calcination.

... we exploit the steady-state nature of dip-coating to spatially and temporally resolve the complete EISA process in the coating direction. By performing spatially resolved 2-D grazing-incidence small-angle x-ray scattering (GISAXS) experiments in combination with optical interferometry, we structurally characterize the evolution of a hexagonal thin-film mesophase from a homogeneous precursor solution and its further structural development during drying and calcination.

We prepared precursor solutions using the two-step procedure we reported in our prior work. Final reactant mole ratios were 1 TEOS : 20 C₂H₅OH : 5.1 H₂O : 0.0026 HCl : 0.16 C16TAB (cetyltrimethylammonium bromide). We dip-coated films on 50 μ m and 300 μ m thick silicon (Si) substrates (100) at 1.6 mm/sec (25°C and 9 percent relative humidity). We performed x-ray experiments at Argonne National Laboratories' synchrotron facility, the Advanced Photon Source, using the SRI-CAT's 1BMC beamline. In the experiment, we focused 11 keV x-rays to a 0.5-by-0.5 mm² spot on the Si substrate, at an angle of 0.35°. We collected x-ray-scattering patterns on a 2-D detector (image plate) located at a distance of 103 cm, with typical imaging times of 20 sec. Use of a divergent focused beam is advantageous when recording scattering patterns with the sample at a fixed angle, since it thickens the Ewald sphere. Image plate patterns were optically scanned in steps of 0.2 mm, yielding a 2 θ resolution of 2 mrad. Optical interferometry of a steady-state film profile during dip-coating enabled calculation of the film thickness profile along with the surfactant concentration (c) as a function of distance (z) and time above the reservoir.

The results provided some new insights into the self-assembly process. We postulate the assembly pathway to start with a lamellar film at the liquid-vapor interface that transforms into a perfect hexagonal structure above the drying line, followed by a hexagonal structure that exhibits shrinkage normal to the substrate and an in-plane expansion upon drying. The absence of capillary stresses during drying (as measured by a cantilever beam method), the inhibition of the condensation reaction due to the interaction between the silica network and the surfactant head-groups, and the incompressible nature of the surfactant aggregates, cause the shrinkage normal to the substrate to be accommodated by an in-plane expansion. It is this property of the surfactant-silica system that allows for a unimodal pore-size distribution. Study of other surfactant systems such as anionic, nonionic, and block copolymer will allow us to test a general model of self-assembly, which, in turn, will help to predict structure formation of different materials at various deposition conditions. One can envision schemes where external fields such as light, magnetic, and electric could be used to influence the dip-coating process, tuning the properties of the resultant films.

The results provided some new insights into the self-assembly process. We postulate the assembly pathway to start with a lamellar film at the liquid-vapor interface that transforms into a perfect hexagonal structure above the drying line, followed by a hexagonal structure that exhibits shrinkage normal to the substrate and an in-plane expansion upon drying. The absence of capillary stresses during drying (as measured by a cantilever beam method), the inhibition of the condensation reaction due to the interaction between the silica network and the surfactant head-groups, and the incompressible nature of the surfactant aggregates, cause the shrinkage normal to the substrate to be accommodated by an in-plane expansion. It is this property of the surfactant-silica system that allows for a unimodal pore-size distribution.

Refereed

Doshi, D. A., A. J. Hurd, and C. J. Brinker. 2001. “*In Situ* Scattering Study of Self-Assembled Mesoporous Silica Thin Films During Dip-Coating.” *J. American Chemical Society*, in preparation.

22997

The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly

C. J. Brinker

Evaporation-induced self-assembly (EISA) is a new technology for the fabrication of films with nanoscopic order (i.e., arrays of pores or lamellar composites). These films have potential applications for use in sensors, membranes, pharmacy, and catalytic systems. EISA fabrication is a dynamic process in which lyotropic liquid-crystal phases form as a function of changing conditions of component concentration and temperature. These phases have partial positional order, which can be lamellar, in which molecules organize into parallel arrays of sheets; hexagonal, with molecules ordered into a hexagonal packing of tubes; or other phases. Current analysis techniques have not been sufficient to elucidate the key aspects of the physics of formation of these materials, i.e., a thorough exploration of the liquid-crystal physics as it relates to the use of detergent solutions to template ceramics. A fundamental understanding of these key aspects would introduce the possibility of controlling the structure of the templated ceramic films via innovative techniques of liquid-crystal technology (e.g., external fields and shear).

We studied how the spatial ordering that is developed depends on the dynamic conditions of phase generation using high-resolution, synchrotron-based x-ray diffraction (XRD). The high x-ray intensity available makes possible time-dependent studies of liquid-crystal ordering, and the high angular resolution (wave vector half-width at half-height [HWHH], $\Delta\theta$ equals $0.0003 \text{ \AA}^{-1}$) makes possible precise characterization of the ordering achieved.

To develop this technique, we investigated the dynamic evolution of layer ordering of lyotropic lamellar phases as a function of time upon photoinduced removal of a solvent. As the solvent polymerizes and comes out of solution, the changes in the XRD pattern may be utilized to determine ordering induced by concentration fluctuations due to solvent gradients. These results demonstrate that high-resolution XRD may be useful in establishing the limits of ordering achieved in EISA processing and the processes of transformation between phases.

We studied how the spatial ordering that is developed depends on the dynamic conditions of phase generation using high-resolution, synchrotron-based x-ray diffraction (XRD). ... These results demonstrate that high-resolution XRD may be useful in establishing the limits of ordering achieved in EISA processing and the processes of transformation between phases.

24101

A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell

R. J. Shul

In collaboration with Lehigh University, Sandia is building a micromethanol steam reformer (MMSR) to convert methanol and water into hydrogen (H), with carbon dioxide (CO₂) as the by-product. The H will be used as fuel. Sandia developed a planar microfuel cell that is designed to use H and air as its two fuels. Typically, H is stored as a metal hydride, which contains less than 1.8 percent H by weight. This low level of storage makes a microfuel cell appear volumetrically inefficient. An MMSR will have much less volume and would require only the replacement of a small methanol fuel cartridge, rather than a bulky hydride container. We will base the MMSR on a well-known chemical reaction in which methanol would be heated to yield H and carbon monoxide (CO). Since CO will poison the fuel cell catalyst, it must be removed. A second reaction is to heat the gases with water (steam), which causes the CO to be converted to CO₂ and more H to be produced. The gases will be filtered through porous palladium (Pd), which allows only H to pass. The MMSR will utilize the technology developed in Sandia's μ ChemLab™ project, such as the micro-hotplate for creating steam and silicon (Si) microchambers for reactions and gas handling. The heat created by these reactions will be removed with our patented micro-heatpipe technology. This combination of unique Sandia capabilities makes a micro-steam reformer a winning combination both technically and economically.

The Integrated Microchemical Systems Laboratory at Lehigh University successfully completed the fabrication of components of a methanol microreformer, while at Sandia we completed a detailed study of the theoretical and experimental issues involved in the design and operation of the Si-based methanol microreformer. We carried out thermal simulations for heat loss from the reformer chip and calculations involving the endothermic heat effect of the reforming reaction to estimate the total power requirement for continuous operation of the microreformer.

We utilized micromachining technology to fabricate a prototype Si microchannel-based reformer of channel cross-

In collaboration with Lehigh University, Sandia is building a micromethanol steam reformer (MMSR) to convert methanol and water into hydrogen (H), with carbon dioxide (CO₂) as the by-product. The H will be used as fuel. ...

The MMSR will utilize the technology developed in Sandia's μ ChemLab™ project, such as the micro-hotplate for creating steam and silicon (Si) microchambers for reactions and gas handling. The heat created by these reactions will be removed with our patented micro-heatpipe technology. This combination of unique Sandia capabilities makes a microsteam reformer a winning combination both technically and economically.

section 1000μ by 230μ with a copper (Cu) catalyst layer about 33 nm thick. We interfaced the reactor with the tubing for reactant and product transport, using a stainless-steel housing machined to exact dimensions, and flexible graphite pads to provide gas-tight seals and excellent thermal contact between the chip and the housing for external heating of the reformer. We carried out runs of this prototype microreformer using a custom-made experimental setup for generation of the reactant mixtures, temperature control of the microreactor, and online measurement of the product gas composition. Results from test runs of the microreformer showed detectable amounts of H produced in this microreformer.

We fabricated a novel Pd-based micromembrane that has the potential to be used for water-gas shift reaction and H-gas separation in catalytic microreaction systems for methanol fuel reforming. The membrane is supported by a Cu film that has an array of patterned holes. Cu will also act as a catalyst in the shift reaction that will convert unwanted CO gas, produced earlier in the microreaction system during methanol fuel reforming, into H, which, in turn, will be separated by the membrane. This structure is novel because we integrated the water-gas shift reactor as well as the H-gas separator into it. The microfabrication process allows for integration of heaters and temperature sensors into the device. The Lehigh effort was also successful in performing thermal and microfluidic simulations to simulate combined thermal and fluidic interactions in microchannels. The phenomenon of wall “slip” was explicitly incorporated in these simulation models. These simulations were performed using MEMCAD, a commercial package marketed by COVENTOR (formerly MICROCOSM, Inc.), using FLUENT (marketed by COMSOL) and using customized basis function expansions in MATLAB.

We fabricated a novel Pd-based micromembrane that has the potential to be used for water-gas shift reaction and H-gas separation in catalytic microreaction systems for methanol fuel reforming. ... This structure is novel because we integrated the water-gas shift reactor as well as the H-gas separator into it. The microfabrication process allows for integration of heaters and temperature sensors into the device.

24102

Magnetically Insulated Power Flow Experiment

J. P. Vandevender, C. L. Ruiz

Magnetically insulated transmission lines (MITLs) and ion diodes have sufficient magnetic flux between the cathode and anode to insulate electrons originating on the cathode from reaching the anode. These devices have demonstrated excellent insulation efficiencies in operational facilities for more than 20 years, at electric fields of about 2×10^8 V/m. The design of higher-power MITLs for future Z-pinch x-ray sources for weapon physics and inertial confinement fusion (ICF) could benefit from efficient power flow at higher electric fields. However, magnetic insulation data from the MITE and HydraMITE high-power magnetic insulation experiments of the late 1970s showed many anomalies at 2×10^8 V/m. Other Sandia projects have reproduced and clarified three of these anomalies: ion loss to the cathode, large low-energy electrons to the anode, and axial nonuniformity of the electron loss to the anode and cathode.

Sandia no longer has a low-cost capability to study magnetically insulated power flow. A new capability for high-power-density, self-magnetically insulated power flow experiments has been developed on Sandia's Sphinx accelerator. The facility provides self-magnetically insulated power flow at 3 MV/cm for 15 ns in a 10 ns long vacuum transmission line.

Our work addressed the two anomalies that remained to be reproduced and explained. We had three objectives:

(1) To explore the potential of the Sphinx accelerator to provide a low-cost capability to study magnetically insulated power flow for future experiments.

(2) To reproduce and study the MITE experiments anomaly that the time-resolved energy/nucleon of negative ions through the anode, as diagnosed with a time-of-flight (TOF) spectrometer, often disagrees with the full gap voltage (e.g., proton energy of 500 keV with 2000 kV across the vacuum gap).

(3) To reproduce and study the MITE experiments anomaly in which the time-integrated energy distribution of negative ions coming through the anode had several distinct peaks in energy, although the potential across the gap was quite constant.

Sandia no longer has a low-cost capability to study magnetically insulated power flow. A new capability for high-power-density, self-magnetically insulated power flow experiments has been developed on Sandia's Sphinx accelerator. The facility provides self-magnetically insulated power flow at 3 MV/cm for 15 ns in a 10 ns long vacuum transmission line.

Our first objective, to explore the potential of the Sphinx accelerator, was met in that we developed and verified a low-cost capability (i.e., less than \$500 per experimental trial) for magnetically insulated power transmission. This project provided a capability for future power-flow experiments with an electrical stress of up to 3×10^8 V/m across a 7 mm magnetically insulated vacuum gap with a 15 ns pulse duration. The voltage and current monitors need to be improved for the accelerator to be useful as a standard experimental facility in this mode.

Our second objective, to reproduce and study the anomaly from the MITE experiments that the time-resolved energy-nucleon of negative ions through the anode often disagrees with the full gap voltage, was investigated with the TOF spectrometer. We fielded the TOF spectrometer; however, too few negative ions were coming through the anode to reproduce the anomalous results from the MITE experiment. The positive and negative ion emissions from the electrode surfaces were examined and found to be substantially less than the 1 A/cm^2 observed in the higher-power MITE experiment at the same electric and magnetic fields when the electrodes have been conditioned by at least one shot. The correspondingly small negative-ion current density is too small to be a significant power loss in the various experimental configurations tested. The Thomson parabola spectrometer is much more sensitive than the TOF spectrometer, so it became the primary diagnostic for this anomaly.

Our third objective, to reproduce and study the anomaly from the MITE experiments that the time-integrated energy distribution of the negative ions coming through the anode has several distinct energy peaks, was investigated with the Thomson parabola spectrometer. The Thomson parabola spectrometer was successfully fielded to record the time-integrated ion spectrum of negative ions coming through a hole in the anode of the MITL. The six exposed CR-39 plates were developed with the standard process of NaOH (sodium hydroxide) etching to reveal the ion tracks. However, the number density of ions is too small to produce a readily visible trace. Sandia no longer has the automated scanning capability for the most sensitive analysis of these plates. The plates will be preserved until a more sensitive technique is available and an opportunity exists to read out the data.

Our first objective, to explore the potential of the Sphinx accelerator, was met in that we developed and verified a low-cost capability (i.e., less than \$500 per experimental trial) for magnetically insulated power transmission. This project provided a capability for future power-flow experiments with an electrical stress of up to 3×10^8 V/m across a 7 mm magnetically insulated vacuum gap with a 15 ns pulse duration.

32573

Molecular Self-Assembly

J. G. Curro, A. L. Frischknecht

Self-assembly of molecules is nature's way of creating ordered structures on the nanometer scale. Depending on their architecture, certain molecules (such as block copolymers or low-molecular-weight surfactants) will spontaneously arrange themselves in an ordered structure on a scale that would be impossible to achieve by ordinary processing techniques. This property makes molecular self-assembly a powerful tool for producing nanostructured materials. Some applications include low-dielectric-constant materials, microfluidic devices, sensors, membranes for gas separations, and materials for optical electronics.

The purpose of this project is to develop and apply computational methods for modeling molecular self-assembly processes. Sandia developed a density-functional theory (DFT) approach for modeling the self-assembly of polymers at equilibrium. As an example, we applied this theory to the self-assembly of a block copolymer near a surface. We were able to predict the equilibrium morphology of the microphase-separated block copolymer at the interface and how the morphology changes with surface interactions.

When polymers are used in nanotechnology applications, the physical properties at the nanoscale are not the same as the corresponding bulk properties. Perhaps the most important property that characterizes polymer behavior is the glass-transition temperature (T_g). Large deviations in T_g from the bulk value have been experimentally observed for polymers in confined geometries. In this project we developed a theoretical model that not only explains the origin of these T_g shifts, but also allows us to make predictions for T_g shifts of specific polymers as a function of the size scale and surface characteristics of the confining geometry.

We developed a theoretical model using DFT for the self-assembly of block copolymers near surfaces. Calculations showed that the morphology of the resulting block copolymer depends sensitively on the interactions between the surface and the individual monomers constituting each block.

We performed modeling calculations on silica/diblock films undergoing evaporation-induced self-assembly (EISA). The structure-directing agents were block copolymers of polystyrene and poly(ethylene oxide) (PEO). These

The purpose of this project is to develop and apply computational methods for modeling molecular self-assembly processes. Sandia developed a density-functional theory (DFT) approach for modeling the self-assembly of polymers at equilibrium. ... In this project we developed a theoretical model that not only explains the origin of these T_g shifts, but also allows us to make predictions for T_g shifts of specific polymers as a function of the size scale and surface characteristics of the confining geometry.

calculations demonstrated that microphase separation occurs during the EISA process as the solvent selectively evaporates from the film and that no micellization would take place. These results were in good agreement with EISA experiments by others at Sandia.

We also developed a computational model to predict the T_g shifts of a polymer that result when the polymer is restricted to a confined geometry at the nanoscale. This model successfully explains the origin of many T_g-shift experiments in the literature for polymers in pores and channels as well as freestanding polymer films.

This model successfully explains the origin of many T_g-shift experiments in the literature for polymers in pores and channels as well as freestanding polymer films.

Refereed

McCoy, J. D., and J. G. Curro. 2001. "Conjectures on the Glass Transition of Polymers in Confined Geometries." *Physical Review Letters*, submitted.

Yu, K., A. Frischknecht, C. A. Drewien, A. Hurd, and J. Brinker. 2001. "Formation Mechanism of Silica/PS-b-PEO Mesophases by Solvent Evaporation-Induced Self-Assembly." *Macromolecules*, submitted.

32817

Molecular Simulations of MEMS Coatings

M. J. Stevens, D. M. Ford

Understanding quantitatively the role of surface interactions as a function of environment, surface (monolayer) coating, and surface roughness is critical for microelectro-mechanical systems (MEMS) performance and reliability. Critical properties such as adhesion and friction can be measured in situ on MEMS devices. The structure and dynamics of the coatings, particularly self-assembled monolayers (SAMs), are only partially understood. A better understanding of molecular-scale phenomena will enable a fundamental knowledge of performance and degradation mechanisms. Such knowledge is an essential requirement to predict the performance of MEMS devices with usage and aging.

We will study normal and shear forces in monolayer-lubricant films of SAMs using molecular dynamics (MD) simulations. These simulations will elucidate some of the intrinsic physiochemical lubricant properties that lead to energy dissipation. These simulations will extend our present computational capability in modeling nanolubrication and validate the methodology to describe the frictional properties of ultrathin films.

In collaboration with researchers at Texas A&M University (TAMU), we generated force-versus-distance curves for purely hydrocarbon SAM systems.

TAMU personnel are researching appropriate forcefields for modeling of fluorocarbon SAM systems.

We will study normal and shear forces in monolayer-lubricant films of SAMs using molecular dynamics (MD) simulations. These simulations will elucidate some of the intrinsic physiochemical lubricant properties that lead to energy dissipation. These simulations will extend our present computational capability in modeling nanolubrication and validate the methodology to describe the frictional properties of ultrathin films.

32818

Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches

M. R. Baer, P. E. Desjardin

This Sandia project addresses specifically the secondary combustion that arises from shock-induced mixing in volumetric explosives. The effects of combustion from secondary mixing from the shock can greatly alter the expansion of gases and dispersal of explosive. Furthermore, this enhanced effect may be a tailored feature for the new energetic-material (EM) systems. In recent years, remarkable progress has been made in the theory of turbulent combustion; however, much of this success is limited to simple flows such as jets and plumes. These new approaches have yet to be applied to shock-induced flows.

Simulation of turbulent combustion from first principles requires resolving several decades of time and length scale that are possible only for the simplest of flowfields at low Reynolds number for which numerical simulations are often limited to two dimensions (2-D). Solving for 3-D turbulent reacting flows of engineering interest requires the use of subgrid-scale (SGS) modeling for which only the largest scales of turbulence are directly simulated while the smallest scales are modeled. This partition of resolving flow-field dynamics on a grid and modeling of physics below the grid scales is referred to as large-eddy simulation (LES). In this approach, most of the flame area associated with combustion lies in a volume smaller than the LES grid; this situation presents a formidable challenge for SGS modeling. One method to construct SGS models of combustion is through statistical means for which a filtered-probability-density function (FPDF) or filtered-joint-probability-density function (FJPDF) of composition and temperature is either assumed or explicitly solved for using Monte Carlo (MC) techniques.

The objective of this work is to develop FPDF and FJPDF approaches for application to turbulent combustion and apply the technique to examine shock-induced combustion from explosive mixtures.

Developing SGS-combustion models occurred in two stages: a simple level I and more sophisticated level II

This Sandia project addresses specifically the secondary combustion that arises from shock-induced mixing in volumetric explosives. The effects of combustion from secondary mixing from the shock can greatly alter the expansion of gases and dispersal of explosive. Furthermore, this enhanced effect may be a tailored feature for the new energetic-material systems. ... The objective of this work is to develop FPDF and FJPDF approaches for application to turbulent combustion and apply the technique to examine shock-induced combustion from explosive mixtures.

approach. The level I combustion model was successfully developed and implemented into the CTH shock-physics code. This model is based on a conserved-scalar-presumed FPDF approach for which reactive scalars are related to a passive scalar, the mixture fraction, using state relationships. We assume a beta function to describe the variation of mixture fraction at the subgrid level and parameterize it by the filtered value of mixture fraction and its variance. We determine these two parameters through transport-evolution equations. The transport of the filter-mixture fraction employs a simple gradient-diffusion turbulence model; the variance transport equation is taken from the work of Jimenez.

We coded these two additional transport equations into CTH. We also incorporated a multispecies, single-material capability into CTH using an ideal gas equation-of-state (EOS) to allow tracking of several species needed in the combustion model. In addition, modifications to the acoustic CFL (Courant-Friedrichs-Levy) limited-time-stepping algorithm were changed to allow larger time-steps using the pressure-gradient scaling technique of Ramshaw. These changes were necessary to allow efficient time integration at advection-based time-scales.

We considered two problems for testing the level I combustion model. The first problem is a simple fuel-blob problem for which a small amount of methane is injected into air with an initial velocity. The second problem is a simulated shock event for which reactive material is dispersed into the surrounding field and allowed to react. Both problems show the potential use of the secondary combustion model and the importance of incorporating this capability. In addition, we formulated a level II combustion model and implemented it into a stand-alone research code using MC techniques. Preliminary results using the level II combustion model indicate that the methodology holds promise but will require about an order-of-magnitude increase in computational cost over the simple level I combustion model.

In summary, FPDF approaches are an attractive means to simulate the effects of turbulent combustion from shock-induced secondary mixing.

We considered two problems for testing the level I combustion model. The first problem is a simple fuel-blob problem for which a small amount of methane is injected into air with an initial velocity.

The second problem is a simulated shock event for which reactive material is dispersed into the surrounding field and allowed to react.

Both problems show the potential use of the secondary combustion model and the importance of incorporating this capability.

32819

Fundamental Studies of Water-Surface Interactions

P. J. Feibelman, J. G. Kushmerick

Insight into factors controlling the hydrophobic-hydrophilic character of surfaces is critical to new Sandia thrust areas ranging from development of microfluidic systems to understanding the folding and adhesion behavior of biomolecules. We will investigate near-surface arrangements of H₂O (hydrogen dioxide, water), experimentally and via corresponding theoretical simulations, in an effort to establish the relationship between hydration forces and the molecular structure of H₂O near a surface.

In our simulations, we will expose water molecules to model hydrophobic or hydrophilic surfaces, i.e., surfaces terminated by a short hydrocarbon chain ending with a methyl group or, for example, a carboxylic acid. We will explore binding energy and orientation of individual water molecules, then, for coverages of up to a monolayer, how inter-H₂O bonding is mediated via H bonds. Transitions from monomers to dimers to networks of interconnected rings (primarily pentamers and hexamers) will be investigated, with an eye particularly to controlling them by modifying interfacial chemistry or temperature, or by turning on an electric field. Finally, we intend to study multilayers of water to learn how far from a surface the molecular ordering persists.

In complementary experiments we will adsorb water on silicon (Si) surfaces functionalized with methyl- or carboxylic-acid-terminated self-assembled monolayers (SAMs). We will monitor water structure as a function of surface coverage using surface-sensitive infrared (IR) spectra, and the hydrophobic or hydrophilic nature of the surfaces using a special contact-angle system in which interfacial-energies are measured versus both temperature and applied voltage. We will measure short- and long-range interactions between functionalized surfaces and tips in an interfacial-force microscope (IFM), which can perform measurements under water as a function of temperature and applied voltage.

We began our investigation of hydration forces by attempting to identify a set of model surfaces of varying “hydrophobicity.” A commonly studied example of a hydrophobic surface is Au(111) covered by an ordered

Top view of the optimized - R30°-CH₃S/Au(111) structure, with Au atoms colored magenta, S atoms colored gold, C atoms colored grey, and H atoms colored white. Notice that large areas of metal are exposed, despite the presence of the methylthiolate radicals.

We will investigate near-surface arrangements of H₂O (hydrogen dioxide, water), experimentally and via corresponding theoretical simulations, in an effort to establish the relationship between hydration forces and the molecular structure of H₂O near a surface.

arrangement of alkanethiol (i.e., $\text{CH}_3(\text{CH}_2)_n\text{SH}$, or alkanethiolate, i.e., $\text{CH}_3(\text{CH}_2)_n\text{S}$) molecules, strongly bonded through their sulfur (S) atoms to the Au surface. If they are long enough (i.e., if n is roughly 10 or larger), the chains tilt together in a manner such that no Au atoms are exposed to the adjacent medium, and the surface is effectively oily or waxy, certainly “hydrophobic.” This suggested an interesting fundamental project, namely, quantifying how hydrophobic a thiolate-covered surface is as a function of chain length $n+1$. We optimized the geometries of ordered 1/3-monolayer arrangements of methylthiolate (CH_3S) and ethylthiolate ($\text{CH}_3\text{CH}_2\text{S}$) on Au(111), and then investigated the structure and energetics of H_2O co-adsorbed with CH_3S . This was accomplished using state-of-the-art density-functional theory (DFT) total-energy calculations, as embodied in the Vienna ultrasoft pseudopotential (VASP [Vienna *Ab Initio* Software Package]) code.

Already the shortest alkanethiolate, CH_3S tilts—in our calculations and in agreement with results obtained by others—and sits on the Au(111) surface not with the S atom in a symmetry site (i.e., a threefold hollow or twofold bridge), but in between these locations. Despite the tilt (because CH_3S is a short molecule), Au atoms remain exposed to the vacuum when the thiolates adopt the $\sqrt{3} \times \sqrt{3}$ - $\text{R}30^\circ$, 1/3-monolayer structure. Thus, hard-sphere repulsion does not prevent hydrogen-dioxide (H_2O) molecules from binding to exposed Au atoms if that is energetically advantageous. However, our results indicate it is not. In all of the arrangements of H_2O molecules that we tried, the molecules prefer to lie well above the height where they might bind to Au atoms. Beyond that, the most energetically favored two-dimensional (2-D) arrangement of H_2O molecules, a hexagonal layer similar to one basal layer of the naturally occurring ice-crystal, Ice-Ih (hexagonal ice), has a heat of adsorption smaller than the binding energy of H_2O in ice by some 0.2 eV per molecule. This means that the 2-D structure is unstable relative to a 3-D ice ad-cluster and that the surface is effectively hydrophobic.

We still must learn what the energetically optimal structure of H_2O molecules is next to a CH_3S -covered Au surface. It might not be a cluster similar to Ice-Ih, but perhaps something like a buckyball. At the outset of this project, the hope was that infrared-absorption measurements would help provide experimental clues in this regard. That aspect of the

*We optimized the geometries of ordered 1/3-monolayer arrangements of methylthiolate (CH_3S) and ethylthiolate ($\text{CH}_3\text{CH}_2\text{S}$) on Au(111), and then investigated the structure and energetics of H_2O co-adsorbed with CH_3S . This was accomplished using state-of-the-art density-functional theory (DFT) total-energy calculations, as embodied in the Vienna ultrasoft pseudopotential (VASP [Vienna *Ab Initio* Software Package]) code.*

project is incomplete. A recent paper by Hayashi, *et al.*, reports electron-energy-loss spectra for methylthiolate on Au(111) in good agreement with the theoretical geometry that we (and, independently, they) obtained. This gives confidence in the applicability of the density-functional approach to this important model system.

This gives confidence in the applicability of the density-functional approach to this important model system.

32914

Biomimetic Chloroplasts: An Integrated Microdevice Power Source

J. A. Shelnett, C. J. Brinker, C. J. Medforth, Y. Yang

Self-assembled, self-organized materials can provide mesoscale power sources for integrated microelectronic and microelectromechanical systems (MEMS) applications. A biomimetic chloroplast uses light energy to produce a gas or liquid as a fuel or chemical feed.

In the Sandia prototype, hydrogen (H) is generated and stored for production of electrical power generated by an on-chip integrated fuel-cell component. Similarly, a chloroplast is a biological structure that converts light energy to a storable fuel for a living cell. We are using chlorophyll-like molecules to harvest photons and direct the light energy to a reaction center for the photosynthesis of high-energy fuel molecules. Light energy is converted by the biomimetic chloroplast component into a high-free-energy chemical, which can be used in the dark and replenished when the chip is again under illumination.

This fuel or feedstock can be supplied as needed by microfluidics to a microreactor on demand. We are developing the photochemistry and catalysts required to produce H (the biomimetic photosynthetic reaction center) and also the associated self-assembling components of a light-harvesting apparatus to use in a small, efficient, integrated-power source. Self-assembled germanium (Ge), antimony (Sb), and tin (Sn) porphyrins form the integrated light-harvesting complex and reaction center; these components are self-organized and compartmentalized in porous silica nanocomposites, along with platinum (Pt) nanoparticles or hydrogenase to generate molecular H. The nanostructured silica permits access by small-electron donors (triethylamine [TEA], ethylenediaminetetraacetate [EDTA]), acceptors (methylviologen), and water through small pores, while maintaining microscale compartmentalization and organization of the larger functional molecular components in nanoscale pores.

We accomplished most of the currently scheduled tasks, including (1) demonstration of direct electron transfer from the Sn porphyrin to hydrogenase enzyme and Pt nanoparticles upon illumination by visible light in aqueous

In the Sandia prototype, hydrogen (H) is generated and stored for production of electrical power generated by an on-chip integrated fuel-cell component. Similarly, a chloroplast is a biological structure that converts light energy to a storable fuel for a living cell. We are using chlorophyll-like molecules to harvest photons and direct the light energy to a reaction center for the photosynthesis of high-energy fuel molecules.

solution, (2) tin-porphyrin photomediated H generation by hydrogenase and Pt nanoparticles in aqueous solution, (3) measurement of H-production rates for Pt-nanoparticle catalysts, (4) incorporation of Sn porphyrin into 3 nm pores of silica films in the hexagonal phase, (5) heat treatment to remove the detergent molecules used in templating the silica-nanophase formation, (6) formation of silver (Ag) and Pt nanoparticles within the pores of hexagonal-phase silica films by using the embedded Sn-porphyrin photocatalyst and light, and (7) optimization of calcining conditions and porphyrin-diffusion into silica nanophases to yield active porphyrin reaction centers.

We also showed that methylviologen is not needed as a relay molecule for transport of electrons from the photo-reduced porphyrin to Pt nanoparticles, and we initiated surface-enhanced resonance Raman and ultraviolet-visible spectroscopy of the porphyrin-metal-silica nanocomposite materials. We are nearing completion of the determination of H-generation activity of the Sn porphyrin and Pt nanoparticles embedded within the silica matrix.

We also showed that methylviologen is not needed as a relay molecule for transport of electrons from the photoreduced porphyrin to Pt nanoparticles, and we initiated surface-enhanced resonance Raman and ultraviolet-visible spectroscopy of the porphyrin-metal-silica nanocomposite materials.

34438

Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves

T. M. Nenoff

In collaboration with New Mexico State University, Sandia will provide a two-pronged approach to elucidating the molecular-level phenomena occurring during separation processes using zeolites and other molecular sieve materials: (1) molecular density-functional theory (DFT), and (2) molecular dynamics (MD) simulations. The goal of this project is to model adsorption and diffusion of binary mixtures of molecular oxygen and water in various zeolites.

In this project, we modeled the separation of a binary mixture of light gases in two microporous systems: Zeolite A and the novel zinc phosphate, $\text{Na}_3\text{Zn}_4\text{O}(\text{PO}_4)_3$. MD simulations, which probe microscopic-length scale events, provide diffusion information for binary mixtures. However, we found also that longer-length scale events are important contributors to the diffusion mechanism in molecular sieve films.

Zeolite A simulations. These results clearly show that hydrogen (H) moves more rapidly through the zeolite, but that methane has significant movement as well. The history file was also used to generate a histogram of occupancy of the adsorbate molecules in three-dimensional (3-D) bins spanning the unit cell. Because of the prohibitive size of the history files, positions could not be saved often enough to obtain a smooth-isodensity surface. Although the surface is rough, H is closer to the framework walls. Even though these corners are favorable in term of energy, if adsorbates are in the center of the unit cell, the activation energy is prohibitively large and does not allow for the molecules to go through the window into the small corner.

Phosphate molecular-sieve simulations. This simulation confirms the conclusion from the mean-squared-displacement plots that the H can move from cage to cage within the zinc-phosphate structure, but the methane is confined to the cage in which it started in the simulation. Even though the potential energy for H_2 is not favorable in the cage windows, the H molecules have enough energy to overcome that unfavorable energy. As indicated by the mean-squared-

In collaboration with New Mexico State University, Sandia will provide a two-pronged approach to elucidating the molecular-level phenomena occurring during separation processes using zeolites and other molecular sieve materials. ... The goal of this project is to model adsorption and diffusion of binary mixtures of molecular oxygen and water in various zeolites.

displacement plots, the movement of H is significant and the movement of methane is not significant. In the zinc phosphate, for the number of adsorbates studied, no clear decrease in the diffusivity of H was found as the system becomes more crowded.

Refereed

Mitchell, M. C., J. D. Autry, and T. M. Nenoff. 2001. "Molecular Dynamics Simulations of Binary Mixtures of Methane and Hydrogen in Zeolite A and a Novel Zinc Phosphate." *Molecular Physics*, in press.

34439

Scanning Tunneling Microscopy of Silicon-Based Nanostructures

B. S. Swartzentruber

As silicon (Si)-based devices in microelectronics shrink to the nanometer regime, established processes and architectures may become inadequate. For example, new interface materials or structures may be necessary to build properly functioning devices at this small scale.

In collaboration with New Mexico State University, Sandia is investigating silicon oxide (SiO) super structures using scanning tunneling microscopy (STM). We proposed a SiO superlattice structure as a barrier layer on Si that would also allow the overgrowth of crystalline Si. If successful, this concept would enable new device-architecture designs within the existing Si-processing technology currently used in the microelectronics industry.

To form reproducible, well-defined, initial substrate surfaces onto which SiO is grown, we determined that the surface-preparation procedure is critical. In particular, a long-time anneal at intermediate temperatures is required to lower the number of point defects on the surface. Such defects interfere with our ability to determine the atomic positions where the deposited O atoms react.

The substrate temperature is also a critical parameter when depositing O atoms through exposure to molecular O because substantial surface etching occurs at high-substrate temperatures, and surface roughening occurs at low temperatures. We determined the appropriate temperature window in which low-coverage thin films of oxide can be formed. We have also begun work on the overgrowth with Si.

We augmented the data-acquisition and -control software to perform measurements of the surface-electronic structure through multiple-bias imaging. In this mode STM images are acquired simultaneously, on the same part of the surface, at two biases. Typically, we image the filled- and empty-electronic states of the surface. From these images, we can more reliably determine the atomic positions of the atomic species than from single-bias images.

We currently have the tools in place to grow and to measure the electronic structure of ultrathin SiO barrier structures.

In collaboration with New Mexico State University, Sandia is investigating silicon oxide (SiO) super structures using scanning tunneling microscopy. We proposed a SiO superlattice structure as a barrier layer on Si that would also allow the overgrowth of crystalline Si. If successful, this concept would enable new device-architecture designs within the existing Si-processing technology currently used in the microelectronics industry.

34692

Self-Assembly of Polymers in Confined Geometries

J. G. Curro

Polymers are used for applications (e.g., microelectronics) with finer and finer features that approach the polymer radius of gyration. Therefore, understanding how the confined geometry influences the properties of the polymer is necessary. Miscibility characteristics, viscoelastic properties, and glass-transition temperature (T_g) of polymer in thin films can be quite different from the corresponding bulk properties.

The purpose of this project is to develop modeling capabilities to investigate the properties of polymers in confined geometries. Of particular interest is the self-assembly of block copolymers near surfaces and the behavior of polymers grafted to surfaces. The focus of the project is to apply density-functional theory (DFT) to develop modeling tools for predicting the properties of polymer near surfaces and in confined geometries.

We wrote a general DFT code to model polymers near surfaces and in confined geometries. We successfully applied this code to several important applications, including the response of surface-grafted chains, the self-assembly of block copolymers near surfaces, and modeling the shift in T_g of polymers in confined geometries.

We performed calculations of the density profile of poly(n-propyl acrylamide) chains grafted to silica surfaces as a function of surface coverage, molecular weight, and temperature. We found good agreement with x-ray-reflectivity measurements by others at Sandia on these same systems.

We modeled the effect of confined geometries on the T_g using the DFT code. We found good agreement with many experimental studies in the literature on polymers in pores, channels, and thin films. Of particular significance is our prediction that the T_g shift in freestanding polymer films is much larger than for polymers on pores. Furthermore, the DFT results demonstrate that positive and negative deviations from the bulk T_g are possible, depending on the magnitude of polymer/surface interactions.

The purpose of this project is to develop modeling capabilities to investigate the properties of polymers in confined geometries. Of particular interest is the self-assembly of block copolymers near surfaces and the behavior of polymers grafted to surfaces. The focus of the project is to apply density-functional theory (DFT) to develop modeling tools for predicting the properties of polymer near surfaces and in confined geometries.

Refereed

McCoy, J. D., and J. G. Curro. 2001. "Conjectures of the Glass Transition of Polymers in Confined Geometries." *Physical Review Letters*, submitted.

McCoy, J. D., Y. Ye, and J. G. Curro. 2001. "Tethered Chains in a Continuum Solvent: 1. Self-Consistent Field Theory of the Athermal System." *J. Chemical Physics*, submitted.

34693

Building Conscious Machines Based on the Primate Brain

R. B. Asher

Designing intelligent systems that can monitor and interact with complex, variable, and poorly modeled environments remains a challenge. This is particularly true for systems that need to be controlled in real time, such as autonomous robots, automated buildings, or traffic control in metropolitan areas.

This report describes an approach that sacrifices the time-consuming (and, for many physical systems, ill-defined) goal of searching for the global optimum in favor of a locally optimal solution in a small, restricted subset of the system. That is, an attentional mechanism selects a subset of all relevant data, in real time, as the best representation of the system status, given limited computational resources. This central representation, akin to the content of consciousness, changes as the system and the environment evolve. The organization of this architecture model is reminiscent of the cognitive architecture of the primate brain and uses a notion similar to the hypothesized function of consciousness.

A general architecture for a brainlike machine architecture. A general-purpose computational architecture was based on the following: The low-level modules are the sensors, early processing, error module, and actuators. Under normal conditions, this portion of the system operates autonomously, quickly responding to sensory inputs to perform familiar tasks as in the on-line zombie systems. The higher-level system, comprising logic (a central processing unit [CPU]) and declarative memory, implements emergency-handling and long-term planning by issuing command signals to the actuators directly and configuration signals to all other modules. This portion of the system is reminiscent of a von Neumann architecture, except the inputs and outputs are routed through the low-level computing structure.

The attentional module acts as a central information exchange. This module selects the most salient subset of the preprocessed sensory inputs and then submits search requests to the declarative memory to retrieve the most relevant past recollections. The memory should be organized in a hierarchical fashion to facilitate the search and to return

This report describes an approach that sacrifices the time-consuming (and, for many physical systems, ill-defined) goal of searching for the global optimum in favor of a locally optimal solution in a small, restricted subset of the system. That is, an attentional mechanism selects a subset of all relevant data, in real time, as the best representation of the system status, given limited computational resources. This central representation, akin to the content of consciousness, changes as the system and the environment evolve. The organization of this architecture model is reminiscent of the cognitive architecture of the primate brain and uses a notion similar to the hypothesized function of consciousness.

relevant facts. These are combined with the content of the attentional module in a compact representation labeled *awareness* (it could also be called *consciousness*). This is made accessible to the logic unit, which then plans and makes executive decisions in real time. In this view, awareness can be thought of as the state of the cache memory of the logic, containing the information that is currently of most relevance to the system. In a world of unlimited computational resources, the system logic should have access to all information collected by the cooperating agents for optimal behavior. In a finite and highly competitive world, awareness represents the compromise needed to achieve better-than-chance performance in real time (albeit, most likely not optimal in a global sense) by providing the central processor with the most relevant information only.

As a real-world example of such an architecture, consider an intelligent building such as a skyscraper. The processing modules correspond to face- and voice-recognition modules at the doors, cameras, and PCs tracking the movement of humans inside the building; temperature, humidity, and chemical sensors in every room, and so on. Again, these are the routinely operating zombie-behaviors. This vast data stream is transcribed into a detailed representation of the entire building. An attentional mechanism needs to select a subset of these data and generate a more compact representation—corresponding to the current contents of awareness—that is made available to the logic unit. The error signals assign higher priority to events, such as the detection of an intruder or a fire, compared to the routine identification of an employee walking through the front door.

Many situations require access to memory, for example, comparing an unknown face against the faces of known criminals stored in a database, or checking whether a high occupancy in one of the lecture rooms corresponds to a regularly scheduled seminar. A compact, dynamic, and flexible “awareness” representation implemented on an inexpensive personal computer might be sufficient to help manage such a large-scale system. Alternatively, the contents of the awareness module may be forwarded directly to a human operator, who in that case would be performing the function of the logic. Examples of other applications are interactive, automated office assistants, autonomous agents for hazardous industrial or extraterrestrial environments, traffic

Many situations require access to memory, for example, comparing an unknown face against the faces of known criminals stored in a database, or checking whether a high occupancy in one of the lecture rooms corresponds to a regularly scheduled seminar. A compact, dynamic, and flexible “awareness” representation implemented on an inexpensive personal computer might be sufficient to help manage such a large-scale system. Alternatively, the contents of the awareness module may be forwarded directly to a human operator, who in that case would be performing the function of the logic.

control in metropolitan areas, or managing large physical plants (e.g., oil refineries, hospitals, aircraft carriers, and so on).

The approach outlined here, inspired by the cognitive architecture of the primate brain, can provide one answer. This approach can lead to a novel computational paradigm appropriate for solving complex problems efficiently by taking decisions based on a compact representation of the most salient features of the environment and the relevant information from memory.

*This approach can lead to a
novel computational paradigm
appropriate for solving
complex problems
efficiently*

35376

Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture

N. R. Moody

There currently are few experimental testing methods that can assess nonlinear deformation and fracture phenomena on the micrometer- and submicrometer-length scales. Those that exist are often not verified using a second experimental approach. Nanoindentation techniques have been developed to probe failure modes, including film fracture and delamination, but these tests are difficult to verify without resorting to other indentation or scratching techniques. Therefore, Sandia will apply a study that will allow for the development of testing using an independent technique (bulge testing and blister testing) to materials systems of interest to film-substrate systems that can be used as models for components in the stockpile. We will perform additional testing in materials that exhibit nonlinear deformation and shear-band formation under high stresses. As both systems, nanoindentation and bulge testing, can be carried out in aqueous environments that are environmentally aggressive, we will perform testing correlation under various thermochemical environments to ensure the robust nature of the experimental procedure. We will then compare the results of all of these tests to simulations in projects supported in the Accelerated Strategic Computing Initiative (ASCI) program to show applicability of the testing methods to future verification of simulations for life cycle engineering.

In collaboration with Washington State University, we verified the nanoindentation method of generating film fracture on a specific materials system, titanium oxide (TiO) films on Ti on glass. We examined two methods of generating film fracture, a monotonic-loading and a cyclic-loading test; both proved to generate loading discontinuities during indentation. We used atomic-force microscopy (AFM) imaging in conjunction with the monotonic loading to identify cracking around the circumference of the indentation. Cyclic loading is producing fracture events on systems that do not show loading discontinuities during monotonic systems. We are currently investigating the differences between the cyclic and monotonic loading. We also carried out nanoindentation

... Sandia will apply a study that will allow for the development of testing using an independent technique (bulge testing and blister testing) to materials systems of interest to film-substrate systems that can be used as models for components in the stockpile. We will perform additional testing in materials that exhibit nonlinear deformation and shear-band formation under high stresses.

on tungsten oxide (WO) films on W; these samples are currently being analyzed using transmission electron microscopy (TEM) to correlate dislocation structures and film fracture geometries. In addition, we used AFM imaging to measure slip steps and shear bands around indentations into Ti to identify active slip systems.

We constructed two bulge test systems, one based on pressurized liquids and one based on pressurized gases. We used these systems to deflect silicon (Si) membranes formed by anisotropic etching of Si. Both systems are currently being calibrated for load and deflection and are capable of doing both monotonic and cyclic loading so that comparisons can be made between the nanoindentation and bulge test systems.

We constructed two bulge test systems, one based on pressurized liquids and one based on pressurized gases.

Refereed

Pang, M., and D. F. Bahr. 2001. "Thin-Film Fracture During Nanoindentation of a Titanium Oxide Film-Titanium System." *J. Materials Research* **16**: 2634–2643.

Woodcock, C. L., D. F. Bahr, and N. R. Moody. 2001. "Plastic Zone Development Around Nanoindentations." *Fundamentals of Nanoindentation and Nanotribology II* **649** (Materials Research Society Fall Meeting, Boston, MA, November 2000): Q7.14.1–6.

Other Communications

Bahr, D. F., M. Pang, and D. Rodriguez-Marek. 2001. "Film Fracture Phenomena During Indentation." *Fundamentals of Nanoindentation and Nanotribology II* **649** (Materials Research Society Fall Meeting, Boston, MA, November 2000): Q4.2.1–6.

36901

Microcontact Printing of Nanoparticle Arrays*P. G. Clem, S. Y. Lin*

Microcontact printing of functional molecular monolayers is a powerful technique for fabrication of photonic-bandgap (PBG) materials. Sandia has demonstrated that microcontact-printed cationic and anionic monolayers can drive the assembly of high-resolution arrays of colloidal particles. Through control of the dielectric constants of the colloidal particles and of the periodic structure of the array, it will be possible to tailor the visible and infrared (IR) optical properties of surfaces. Even greater control of optical properties will be enabled by using the colloidal nano- or microparticles as etch masks or as a seed layer for the fabrication of self-assembled three-dimensional (3-D) photonic crystals (PhC). Microcontact printing has the significant advantage over conventional nano- and micropatterning techniques in that it has the potential for rapid patterning of large areas exceeding several square meters.

The ability to fabricate large-area PhC would enable the creation of surfaces with low observability, tailored reflectance, and enhanced efficiency lighting. Sandia is performing the assembly and characterization of these surfaces in collaboration with researchers at the University of Illinois (UI). UI is assembling and characterizing the optical properties of the patterned surfaces and PhC; Sandia will participate extensively in subsequent optical characterization and synthesis of the nano- and microparticles used in this study.

We acquired and configured both an ultraviolet-visible (UV-vis) near-infrared (NIR) spectrophotometer, which will be used to characterize the self-assembled photonic materials, and a grazing angle attachment for Fourier-transform infrared (FTIR) spectroscopy to assist in self-assembled monolayer (SAM) characterization.

One milestone for this project was demonstration of micron-scale stamping technique to enable large-scale (multicentimeter area) patterning of optical materials of interest. We successfully completed all the steps required for microcontact printing of SAMs, including the fabrication of silicon (Si) masters with pitches ranging from 4 μm to 10 μm ,

The ability to fabricate large-area PhC would enable the creation of surfaces with low observability, tailored reflectance, and enhanced efficiency lighting. Sandia is performing the assembly and characterization of these surfaces in collaboration with researchers at the University of Illinois. ... Sandia will participate extensively in subsequent optical characterization, and in synthesis of the nano- and microparticles used in this study.

from which we successfully created PDMS (polydimethyl siloxane polymer) stamps.

Using this stamp, we deposited a SAM consisting of a periodic array of 2 μm diameter anionic regions on a 5 μm pitch surrounded by cation-terminated alkane thiols on a gold (Au)-coated substrate. Then, through electrostatic interactions between the patterned substrates and 1 μm amine functionalized (cationic) polystyrene colloidal particles, we deposited a square array of particles on the substrate. Through capillary forces generated upon removal of the solvent, the colloidal particles were brought toward the center of each microcontact-printed pad. Although we observed fairly good placement, the capillary focusing was not sufficient to place the particles as close to the center of each pad as desired; thus, we are synthesizing new thiol-terminated molecules to improve the contrast between the positively and negatively charged regions.

We created PDMS stamps for microcontact printing of micron-scale features from Si masters.

We printed monolayers consisting of a regular array of anion- and cation-terminated alkane thiols on substrates using microcontact lithography.

Using these patterned substrates, we deposited a square array of 1 μm polystyrene colloidal particles on a pitch of 5 μm on the substrate.

Sandia completed synthesis of micron-scale and nanometer-scale particles of polystyrene and silver (Ag). Future materials will include optically active materials such as cadmium sulfide and selenide.

UI is optimizing their reactive-ion etch facility for the creation of high-aspect-ratio structures. Once the appropriate etch parameters have been determined, the colloidal particles will be applied as etch masks.

... we deposited a SAM consisting of a periodic array of 2 μm diameter anionic regions on a 5 μm pitch surrounded by cation-terminated alkane thiols on a gold (Au)-coated substrate. ... we are synthesizing new thiol-terminated molecules to improve the contrast between the positively and negatively charged regions.

Refereed

Braun, P. V. 2001. "Multiphoton Polymerization of Waveguide Structures Within Photonic Crystals." *Advanced Materials*, accepted.

Braun, P. V. 2001. "Nanopatterned Colloidal Deposition." Paper presented to the Gordon Conference on Thin-Film and Crystal Growth Mechanisms, Williamstown, MA, July.

Braun, P. V. 2001. "Self-Organized High Dielectric Contrast Photonic Crystals." Paper presented to The Knowledge Foundation, San Diego, CA, October.

36902

Mathematical Analysis of Deception

F. B. Cohen

In the past few years, deception has emerged as one of the key techniques for effective information protection in networks. A natural side effect of the use of this technology is the desire to understand the mathematical properties underlying its utility. Several informal notions have been introduced—to wit: Deception increases the attackers' workload because they can't easily tell which of their attack attempts work and which fail; deception allows defenders to track attacker attempts at entry and respond before attackers come across a vulnerability that the defenders are susceptible to; deception exhausts attacker resources; deception increases the sophistication required for attack; deception increases attacker uncertainty.

Sandia will examine these claims and provide a more mathematical foundation for this aspect of deception as a tool for network defense. This collaborative research with the University of California–Davis benefits improved understanding that can be applied to the infrastructure of the DOE complex, since its results will prove beneficial to the wider national defense issues of computer networks.

Work continues in three areas of research: (1) a mathematical characterization of network information protection, (2) development of an experimental design for a set of collaborative experiments involving 120 students attempting to carry out red-teaming against defenses with deception enabled and disabled (blind tests) over a period of 13 weeks, which will produce an unprecedented set of data on the effectiveness of deception for information protection, and (3) developing additional attacks to measure deception effects for “close-in” deception technologies.

Sandia will examine these claims and provide a more mathematical foundation for this aspect of deception as a tool for network defense. This collaborative research with the University of California–Davis benefits improved understanding that can be applied to the infrastructure of the DOE complex, since its results will prove beneficial to the wider national defense issues of computer networks.

36904

A System Dynamics Approach to Modeling Water Demand

V. C. Tidwell, S. H. Conrad

Fresh water is central to the vitality of our society; however, national and international demands are increasingly being met through unsustainable practices. Unfortunately, management of this precious resource is complicated by the different values placed on water by various sectors of our society (i.e., industry, agriculture, environmental protection, recreation). Modeling tools are needed to quantify these differing value systems and their relation to supply.

Sandia proposes a system dynamics approach to modeling fresh-water demand. This approach provides a comprehensive framework for quantitatively modeling the values ascribed to water. Here, our concern is for market-driven values (economic) and nonmarket values (e.g., environmental, ecological, and cultural) alike. We will make efforts to conceptualize, mathematically model, calibrate, and test key value systems. As these values tend to interact, we will explore the coupling or feedback between different values and their relation to water supply. Additionally, we will explore the legal and political constraints used to protect and promote particular values. Ultimately, our goal is to develop a fresh-water demand model accessible to water managers, policy-makers, regulators, and stakeholders to help them understand the consequences of their decisions.

We are collaborating with the University of Arizona (UA). In collaboration with SAHRA (sustainability of semi-arid hydrology and riparian areas), we will gain access to field data acquired from a variety of semi-arid river basins, including the Rio Grande. More importantly, this relation will provide new understanding and predictive models for implementation in our system-dynamics water-demand model.

Researchers at the University of New Mexico (UNM) have agreed to provide data on the market and nonmarket value of water; lawyers at UNM's Utton Center will help with legal issues concerning water transfers; and professors at Penn State University and New Mexico Tech will provide data and models on river-aquifer interaction and salinity loading in the Rio Grande River. Also, a numerical test-bed for testing key components of our model was established with SAHRA

Modeling tools are needed to quantify these differing value systems and their relation to supply.

Sandia proposes a system dynamics approach to modeling fresh-water demand.

This approach provides a comprehensive framework for quantitatively modeling the values ascribed to water. ...

Ultimately, our goal is to develop a fresh-water demand model accessible to water managers, policy-makers, regulators, and stakeholders to help them understand the consequences of their decisions.

researchers at Los Alamos National Laboratory, who are constructing a high-resolution, physically detailed model of the Upper Rio Grande River watershed.

38108

Controlling Contamination in Precision Mirrors by Surface-Capping Modifications

M. E. Malinowski

High, near-normal reflectivities in the extreme ultraviolet (EUV) region can be achieved in mirrors with thin-film, multilayer structures. The molybdenum (Mo)/silicon (Si) materials pair has been successfully used to fabricate multilayer mirrors (MLMs) with reflectivities of ~ 0.67 in the EUV (~ 90 eV). A typical Mo/Si MLM is made by sputter-deposition of 40 pairs of alternating Mo and Si thin films, with a total (Si+Mo) bilayer thickness of ~ 0.7 nm and a ratio of Mo/Si thickness of ~ 0.4 . A Si "capping" layer is often deposited on top of this multilayer stack of 40 bilayers to minimize oxidation of the multilayer structure during routine handling in air. Preventing oxidation helps to maintain high reflectivities in the EUV. Since EUV light is strongly attenuated not only by oxygen (O) but also by carbon (C), it is also important to minimize C contamination of the MLM optical surface. Through previous experimental work performed at the Advanced Light Source (ALS) synchrotron at Lawrence-Berkeley National Laboratory (LBNL), Sandia showed that C buildup on MLMs is correlated with photoemission caused by EUV irradiation in the presence of high-molecular-weight hydrocarbons (HCs). Thus, reduction of the original mirror photoemission should decrease initial C buildup rates. This observation led to the concept of constructing the near-surface layers of the MLM, such that the electric field and, hence, photoemission, is minimized in this region; this led to a technical advance. The intent of this project is to build on these past experimental results and the electric-field minimization concept to fabricate, experimentally test, and model the effects of field tailoring on MLM C buildup susceptibility. The minimization of C buildup would be performed consistent with maintaining high MLM reflectivities.

We upgraded an existing MLM exposure system located on Beamline 12.0.1.2 of the ALS synchrotron at LBNL with improved data-acquisition equipment and internal manipulator modifications.

We made six separate Mo/Si MLM mirrors on Si wafers at the Lawrence Livermore National Laboratory

Through previous experimental work performed at ... Lawrence-Berkeley National Laboratory (LBNL), Sandia showed that C buildup on MLMs is correlated with photoemission caused by EUV irradiation in the presence of high-molecular-weight hydrocarbons (HCs). Thus, reduction of the original mirror photoemission should decrease initial C buildup rates. This observation led to the concept of constructing the near-surface layers of the MLM, such that the electric field and, hence, photoemission, is minimized in this region; this led to a technical advance.

(LLNL) multilayer facility; each MLM had a different Si capping-layer thickness, including 2 nm, 3 nm, 4 nm, 5 nm, 6 nm, and 7 nm.

We measured the EUV reflectivities of samples cleaved from the MLMs on the Calibration and Standards Beamline (6.3.2) of the ALS. We found the MLM with the 3 nm capping layer to have the highest reflectivity (~ 66.5 percent at near normal incidence, 13.4 nm EUV light). This was slightly higher than the 66.3 percent reflectivity measured for the sample with 4 nm Si capping layer; 4 nm is the capping-layer thickness normally used in fabrication of such Mo/Si multilayer mirrors.

When exposed to a combination of EUV+ HC vapors, samples of the 3 nm Si-capped MLM showed the least amount of initial C buildup, as manifested by maintenance of original EUV reflectivity in the carbonizing environment. The capping-layer thickness had a remarkable influence on this initial rate, and each sample with a different capping-layer thickness had a different characteristic. The samples with the 6 nm and 7 nm Si caps showed the most rapid decrease in relative EUV reflectivity.

The photoemission, or photocurrents emitted from the samples, was consistent with the notion that the C buildup on the MLMs is produced by cracking of adsorbed HC by photoelectrons. In particular, those samples that showed the highest initial photoemission (6 nm and 7 nm capping layers) showed the greatest initial decrease in EUV reflectivity, indicating high C buildup. Conversely, those samples with the lowest photocurrents retained their initial reflectivities the longest, a behavior consistent with slower initial C buildup. Auger electron spectroscopy depth profiles taken of different samples indicated thicker initial C layers on the 7 nm capped MLM than in the 3 nm capped MLM, corroborating the conclusions regarding C buildup based on the reflectivity results.

The photocurrents emitted from all samples were consistent with modulated photoemission observed in our past EUV+HC work at the ALS. These observations support the proposal that the modulation in photocurrent is due in part to the presence outside the MLM of a standing-wave electric-field intensity caused by the incident EUV light.

The results of the current work confirm ideas originally proposed in Technical Advance 8328; we filed a patent disclosure under the same number. We expect the work

We measured the EUV reflectivities of samples cleaved from the MLMs on the Calibration and Standards Beamline (6.3.2) of the ALS. We found the MLM with the 3 nm capping-layer to have the highest reflectivity (~ 66.5 percent at near normal incidence, 13.4 nm EUV light). This was slightly higher than the 66.3 percent reflectivity measured for the sample with 4 nm Si capping layer; 4 nm is the capping-layer thickness normally used in fabrication of such Mo/Si multilayer mirrors.

performed in this project to provide strategies for manufacturing multilayer EUV optical elements with improved reflectivity retention in carbonizing environments.

38109

Chip-Based Optical-Cell Manipulation*B. J. Kirby*

The goal of this project is to develop and refine techniques for nondestructive manipulation of cells in microfluidic chips using optical tweezers, followed by separation and detection of derivatized cell contents. Research focused on tweezer-compatible laser-polymerized silica surface coatings to inhibit cell adhesion. One expected area of focus, use of polymer-linked polystyrene beads to facilitate optical manipulation of cells on-chip, was deemed unnecessary for effective cell analysis and was not pursued. Sandia is collaborating with Stanford University on this work.

We implemented laser-polymerized coatings that eliminate zeta potential and inhibit cell adhesion. Demonstration experiments with mast and neuron cells showed that these coatings allow for simultaneous electroosmotic flow manipulation and optical-cell manipulation.

Tests with cells on-chip indicate that mast and neuron cells will adhere to silica surfaces if left uncoated. Our polyacrylamide coating completely eliminates cell adhesion.

Electroosmotic flow can interfere with a number of microfluidic techniques. Our coating completely eliminates electroosmotic flow.

We performed chip electrophoresis on neuron-cell lysates with good results.

We presented these results to the 1st Gordon Conference on the Physics and Chemistry of Microfluidics and will present them to the 5th International Conference for Miniaturized Chemical and Biochemical Analysis Systems.

The goal of this project is to develop and refine techniques for nondestructive manipulation of cells in microfluidic chips using optical tweezers, followed by separation and detection of derivatized cell contents. Research focused on tweezer-compatible laser-polymerized silica surface coatings to inhibit cell adhesion.

Other Communications

Kirby, B. J., A. R. Wheeler, J. A. Fruetel, T. J. Shepodd, and R. N. Zare. 2001. "A Laser-Polymerized Acrylamide Surface Modification for Suppression of Cell Adhesion in Microchannels." *Analytical Chemistry*, submitted.

Kirby, B. J., A. R. Wheeler, T. J. Shepodd, J. A. Fruetel, E. F. Hasselbrink, and R. N. Zare. 2001. "A Laser-Polymerized Thin-Film Silica Surface Modification for Suppression of Cell Adhesion and Electroosmotic Flow in Microchannels." *Proc. μ TAS 2001 Conference* (Monterey, CA).

Kirby, B. J., E. F. Hasselbrink, J. E. Rehm, T. J. Shepodd, J. A. Fruetel, A. R. Wheeler, and R. N. Zare. 2001. "Microfluidics for Single-Cell Analysis Using Integrated Chip Electrophoresis." Paper presented to the 1st Gordon Conference on the Physics and Chemistry of Microfluidics, Oxford, UK, July.

38110

Advanced Particle Control for Electric-Discharge Light Sources

N. R. Fornaciari, M. P. Kanouff

A difficulty inherent in using electric discharges to generate light is that the debris created by these sources tends to degrade the performance of the plasma-facing optics used to collect the light. There are a variety of applications for these light sources, including x-ray lasers, soft x-ray microscopy, and advanced lithographies. In the case of advanced lithography, for example, one of the most significant issues impeding commercial implementation is the lack of short-wavelength sources that can generate the necessary amount of power while maintaining an acceptable cost of ownership. Of the advanced source options available, plasma discharge sources, which generate short-wavelength light by means of direct conversion of electrical to actinic energy, have the lowest projected cost of ownership. This projection assumes, however, an essentially debris-free source that would support condenser optic lifetimes of 10^{11} pulses, or about one year of continuous operation. Currently, the best of these discharge sources is several orders of magnitude short of that goal. The contamination generated by these sources tends to degrade the reflectivity of multilayer optics used in advanced lithography systems at such a rate to make the use of these sources not economically feasible. Material and design improvements intended to reduce debris generation have been tested, but these improvements alone will not be able to reduce the debris generation sufficiently. Sandia is studying a technique that would prevent the debris that is generated by these sources from depositing on collection optics.

We set up and tested a particle and contamination mitigation approach: the gas curtain. The gas curtain uses a supersonic cross-flow to alter the trajectory of particles generated by a light source and to prevent them from depositing on plasma-facing collection optics. The setup included acquiring two new high-throughput vacuum pumps and designing and fabricating components that allowed these pumps to mate with an existing vacuum chamber. Once the hardware was assembled, we measured the helium (He)-pumping performance for each of the pumps. We found that the He-pumping performance for both pumps was better than

The contamination generated by these sources tends to degrade the reflectivity of multilayer optics used in advanced lithography systems at such a rate to make the use of these sources not economically feasible. Material and design improvements intended to reduce debris generation have been tested, but these improvements alone will not be able to reduce the debris generation sufficiently. Sandia is studying a technique that would prevent the debris that is generated by these sources from depositing on collection optics.

estimated by the supplier and that the resulting chamber pressures were below our modeling estimates. We then used these performance curves to estimate the capture efficiency for the diffuser. We tested two nozzles and found that in both cases the diffuser efficiency was better than 90 percent. These experimental results agree very closely with modeling estimates for the small nozzle. Testing of the gas curtain under operational conditions is under way.

We tested two nozzles and found that in both cases the diffuser efficiency was better than 90 percent.

38822

Wireless Infrastructure Data-Transmission System

R. V. Matalucci, K. B. Pfeifer

Increasing demands on the aging infrastructure of the U.S. have resulted in accelerated deterioration of structural components. Although steps have been taken to replace or strengthen many structures, nearly 25 percent of the nation's bridges are deficient. Replacement and strengthening are costly alternatives. Field monitoring of the in situ behavior of bridges consistently demonstrates that these structures have considerably greater remaining fatigue life and reserve strength than predicted by analytical models. Often it is found that replacement can be postponed or the level of strengthening reduced. Hence, using field measurements to establish the health of the infrastructure leads to a more effective use of resources.

One of the primary costs associated with infrastructure monitoring is related to the cost of the wires from the sensors to the data-acquisition system on site. Problems with electromagnetic (EM) noise, damaged wires, and durability of wires all contribute to the life-cycle costs associated with these wires. This project has evaluated the feasibility of a wireless system for making health-monitoring measurements on bridges and other infrastructures. Sandia aimed this work at providing a method to allow the collection of strain-gauge and other information for researcher sharing and analysis.

Recently there has been a large effort in the development of noncontacting radio-frequency (RF) tagging technology. These devices function when they are placed in proximity to a reading instrument. The reading instrument is placed a distance from the device and information is transferred from the RF tag to the reader by modulation of the input impedance of the tag. Thus, the backscattered radiation from the tag is read and interpreted by the powered reading device, thus eliminating the need for batteries or external power to operate the tag.

We conducted work to determine if RF-tagging technology could be implemented to store the data from the sensor to nonvolatile memory. Typically, RF tags have flash memory that, along with the identification information, is read out by the system. We chose to test a MicroChip MCRF355

One of the primary costs associated with infrastructure monitoring is related to the cost of the wires from the sensors to the data-acquisition system on site. Problems with electromagnetic (EM) noise, damaged wires, and durability of wires all contribute to the life-cycle costs associated with these wires. This project has evaluated the feasibility of a wireless system for making health-monitoring measurements on bridges and other infrastructures. Sandia aimed this work at providing a method to allow the collection of strain-gauge and other information for researcher-sharing and analysis.

device. This tag operates at 13.56 MHz and has 154 bits available for programming via a contact method.

Sensor measurements of critical infrastructure can be made and these data saved to an RF tag for future readout. One critical aspect of application of RF tags to this application is the ability to produce an RF resonant circuit on a circuit board. We did this by producing a printed circuit board (PCB) with 3.5 loops of 10-mil (.010-inch) traces separated by 10-mil spacings and formed into a 3-inch-square pattern on FR-4 glass for a nominal inductance of 4 MHz. When an EM signal at 13.56 MHz is near the inductor, the tank circuit tends to adsorb and store energy. This electrical energy is used to power the logic circuits in the MCRF355. The MCRF355 then selectively switches the resonance frequency and thus the impedance of the resonance circuit. The changes in the impedance of the tank circuit and the backscattered energy from the impedance mismatch can be monitored by a powered reading device. Thus, data can be transferred from the MCRF355 to the reader without external power to the MCRF355.

We tested two approaches using a switched capacitance circuit and a switched inductance circuit. Shifting between the center frequency and the shifted resonance changes the impedance of the tank circuit as viewed from the reader and represents a bit of data. Thus, 154 bits of sensor data can be measured and then read at a much later time, even while the rest of the circuit is idle.

One critical aspect of application of RF tags ... is the ability to produce an RF resonant circuit on a circuit board. We did this by producing a printed circuit board (PCB) with 3.5 loops of 10-mil (.010-inch) traces separated by 10-mil spacings and formed into a 3-inch-square pattern on FR-4 glass for a nominal inductance of 4 MHz.

39212

MEMS–Based Electromechanical Acoustic Energy Harvester

K. B. Pfeifer

The goal of this research is to develop an electro-mechanical acoustic resonator for the reclamation of energy using microelectromechanical systems (MEMS) technology. The proposed MEMS device converts acoustical energy to electrical energy, which can then be either stored for later use or utilized directly for a particular circuit application. The relatively small geometries possible in MEMS make such a device useful for small, portable devices, where battery requirements are often difficult to meet.

Sandia's long-term objectives with the project are (1) theoretical analysis of coupled electro-acousto-mechanical system, including estimation of available output power, (2) design and fabrication of device using MEMS–based technology, (3) design and fabrication of energy-reclamation circuitry, and (4) characterization and evaluation of performance, including comparison to theoretical models.

We assembled the team and developed a work plan for FY 2002.

The proposed MEMS device converts acoustical energy to electrical energy, which can then be either stored for later use or utilized directly for a particular circuit application.

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
10300	Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films	450	10316	Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry	121
10301	Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments	453	10317	Molecular Simulation of Reacting Systems	124
10302	Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS	456	10318	Massively Parallel Global Climate Model for Paleoclimate Applications	126
10303	Linking Atomistic Computations with Phase-Field Modeling	458	10328	Silicon Three-Dimensional Photonic Crystal and Its Applications	158
10304	A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms	460	10329	Monolithic Micromachined Variable Tuners for Rapid Prototyping and Optimization of Microwave Circuits	160
10305	Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth	462	10330	Quantum Tunneling Transistors for Practical Application	163
10306	Wetting and Spreading Dynamics of Solder and Braze Alloys	464	10331	Development of Magnetically Excited Flexural Plate-Wave Devices for Implementation as Physical, Chemical, and Acoustic Sensors, and as Integrated Micropumps for Sensored Systems	165
10307	Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms	467	10334	Stress-Free Amorphous Diamond for High-Sensitivity Microsensors with Integrated Microstructures	168
10308	Microscale Shock-Wave Physics Using Photonic Driver Techniques	471	10336	Structural Simulations Using Multiresolution Material Models	402
10313	Heterogeneous Simulation	114	10338	Mechanisms of Adiabatic Shear Failure	405
10314	Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions	116	10340	Crack Nucleation and Growth: Combining Validated Atomistic and Continuum Modeling	407
10315	Hybrid Sparse-Dense Incomplete Factorization Preconditioners	118	10341	Applied Microfluidic Physics	410

Appendix A: Project Number/Title Index

Project Number	Title	Page Number	Project Number	Title	Page Number
10343	Innovative Measurement Diagnostics for Fluid/Solid and Fluid/Fluid Interactions in Rotating Flowfields	413	10370	HPM Vulnerability Assessment and Tests	221
10347	Microdiagnostic MEMS Lab-on-a-Chip	57	10377	Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay	223
10349	Thin-Film Deposition Processes Incorporating <i>In Situ</i> Monitoring Capabilities	61	10378	Characterization of Underground Facilities in an Urban Environment	552
10356	Varying QoS for Fixed and Mobile Networks	317	10379	Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments	226
10357	A Real-Time Decision-Support Framework to Guide Facility Response to Abnormal Events	546	10380	Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays	229
10358	Physical Model-Based Fusion of Sensor Array Data	549	10381	Miniature UV Fluorescence-Based Biological Agent Sensor	232
10360	High-Surety SCADA for the Critical Energy Infrastructures	319	10388	Hybrid Processing of Measurable and Subjective Information in Surety Analysis	327
10361	Agent-Based Mediation and Cooperative Information Systems	321	10393	Production Surety and Disruption Vulnerability Analysis	329
10362	Dynamically Self-Configurable Network Protocol	324	10394	An Optically Triggered Semiconductor Switch for Firing Systems	672
10365	Controlling Information: Its Flow, Fusion, and Coordination	551	10395	Source Code Assurance Tool	332
10368	Surface Decontamination of Bacterial Protein Toxins by RF Power	217	10399	Information Collection	438
10369	Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures	219	10407	Information Extraction from Hyperspectral Images Obtained from Satellites	674
			10409	Capillary Elastohydrodynamics in Manufacturing Processes	676

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
10693	Nanosat	554	10732	A MEMS Microelectric Generator	341
10718	A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	335	10733	SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications	175
10719	Radiation-Induced Prompt Photo-currents in Microelectronics: Physics	172	10734	Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis	474
10720	Proton Beam Directed-Energy Weapon	235	10735	Physical Basis for Interfacial Traction-Separation Models	477
10721	Volumetric Displacement Control (VDC) of Manufacturing Tools	63	10736	Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation	239
10722	Process-Based Quality Tools to Verify Cleaning and Surface Preparation	66	10739	Laser-Assisted Microgas Metal Arc Welding	684
10723	Fabrication of Three-Dimensional Microstructures Using Soft Lithography	69	10740	Diagnostics for Joining Solidification/Microstructural Simulations	480
10724	High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	560	10741	Effects of Microstructural Variables on the Shock-Wave Response of PZT 95/5	483
10725	A Micro-GC-Based Controller for Energy-Intensive Processes	338	10742	Mechanisms of Dislocation-Grain Boundary Interaction	486
10727	Micro-High-G Acceleration Recorder	237	10744	Defining the Frontiers of Vertical, External-Cavity, Surface-Emitting Lasers	178
10728	Algorithmic Advances in Computational Structural Biology	129	10746	Predicting Function of Biological Macromolecules	97
10729	Ultraminiaturization of RF Circuitry	678	10747	Induced Molecular Markers for Pathogen Detection: Microincubators for Rapid Toxin Expression	562
10731	An Actuator Based on an Electrokinetic Pump	681			

Appendix A: Project Number/Title Index

Project Number	Title	Page Number	Project Number	Title	Page Number
10748	Nanostructured Silicon Surfaces for Cost-Effective Photovoltaic Efficiency Improvements	343	10762	Self-Assembled, Tamper-Detection Seals	564
10749	Growth and Characterization of Quantum Dots and Quantum Dot Devices	181	10763	Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	350
10751	Automatic Design of Practical Fixtures	72	10765	Energetic-Material Burn and Detonation at the Mesoscale	416
10752	Distributed Reconfigurable Homogeneous Microrobotic Systems	241	10766	Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	184
10753	Robust Planning for Autonomous Navigation of Mobile Robots in Unstructured, Dynamic Environments	243	10767	Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	353
10754	Functional Materials for Electrochemomechanical Actuation of Microvalves and Micropumps	488	10770	IMEMS Packaging and Interconnection Technology	78
10755	Microreplication: Precision Metal Parts from Electroformed Master Molds	75	10771	Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	356
10756	New Architectures for Micro-Total-Analytical Systems	540	10772	Intense Directed-Energy Theory Initiative	246
10757	Large-Scale Nonlinear Optimization Arising from PDE Models	132	10773	Assembly of LIGA Using Electric Fields	81
10758	Network Intrusion Detection Using Adaptive Critic Neural Networks	346	10774	Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes	100
10759	Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry	348	10775	Miniature Sensors for BW Agents Using Fatty-Acid Profiles	187
10761	Making the Connection Between Microstructure and Mechanics	491	10776	Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	189
			10777	Parallel Methods for Coupling-Circuit and Device-Scale Simulations	134

Appendix A: Project Number/Title Index

Project Number	Title	Page Number	Project Number	Title	Page Number
10778	A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems	136	10796	High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS	203
10779	Switchable Hydrophobic-Hydrophilic Surfaces	494	11130	Molecular Integrated Microsystems (MIMS)	439
10780	Nanostructured Materials Integrated in Microfabricated Optical Devices	497	16167	Pseudostationary Separation Materials for Highly Parallel Microseparations	692
10782	High-Al-Content AlGaInN Devices for Next-Generation Electronic and Optoelectronic Applications	192	17230	Novel Coatings for Microelectromechanical (MEM) Devices	695
10783	Microfabrication of Electromagnetic Devices	194	19991	Use of Apatite and Substituted Apatites for <i>In Situ</i> Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water	358
10784	GaAs MOEMS Technology	196	20413	DNA Microarray Technology	699
10785	Integrated Microsensors for Autonomous Microrobots	198	20414	Shock Response of Diamond Crystals	701
10786	Silicon-Integrated Planar Microbatteries	201	20416	Information-Sharing Security Module Research and Development	360
10788	Small-Scale Multiaxial Deformation Experiments on Solder for High-Fidelity Model Development	419	21280	Techniques for Improving and Exploiting MTI Imagery	566
10789	All-Ceramic Battery	499	21554	Solutions to National and Global Security Issues Based on Limited Freshwater Resources	35
10791	Fuzzy Data Mining	248	21559	Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures	363
10792	Ultrahigh-Resolution Radiography for Detailed Inspection of Weapon Components and Systems	687	22126	Understanding and Managing Threats to the Social Fabric of the United States	37
10793	Computer Numerically Controlled Micromachines	83			
10794	Electromicrofluidic Packaging	85			
10795	Surface-Micromachined Mechanical Timer	689			

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
22131	Investigation of Nanoscience Technologies	703	26513	Implementation of Fault Tolerance in Scientific Simulation Application Software	141
22132	Magnetic Polysilicon MEMS Devices	704	26514	Smart Sensor Technology for Joint Test Assembly Flights	143
22854	Theoretical Study of Sb as a Surfactant in Epitaxy of III–V Materials	707	26515	Multilevel Methods for Nonlinear Structural Mechanics	145
22995	Single-Wire Explosion Experiments	709	26516	Algorithmic Support for Commodity-Based Parallel Computing Systems	147
22996	Scattering from Nanostructured Materials	712	26517	Parallel Repartitioning for Optimal Solver Performance	149
22997	The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	715	26518	II-V: Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	205
24101	A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	716	26519	The Integration of Advanced Photonics and MEMS	207
24102	Magnetically Insulated Power Flow Experiment	718	26520	Uncertainty Propagation in Models of Thermofluid Systems	422
26508	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	87	26521	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	425
26509	Levitated Three-Axis Micro-accelerometer	90	26522	A Physically Based Approach to Modeling Ductile Fracture	428
26510	Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques	92	26523	Radiation Aging of Stockpile and Space-Based Microelectronics	430
26511	Resolving Fundamental Limits of Adhesive Bonding in Micro-fabrication	94	26524	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	432
26512	Parallel Atomistic Computing for Failure Analysis of Micromachines	139	26525	Magnetic-Field Effects on Vacuum-Arc Plasmas	502

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
26526	Microstructural and Continuum Evolution Modeling of Sintering	504	26538	Threat Assessment Study for Short-Pulse Laser Technologies in Directed-Energy and Counter-sensor Applications	268
26527	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	507	26539	Algorithms for Improved Performance in Cryptographic Protocols	270
26528	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	509	26540	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	273
26529	Nanoclusters for Supercapacitors	511	26541	Triggered Isomer Research	275
26530	First-Principles Determination of Dislocation Properties	513	26542	A Scientific Basis for Robotic Ground-Vehicle Design	277
26531	Air Sterilization and Decontamination	251	26543	Adaptive and Mobile Ground Sensors	278
26532	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	253	26544	Algorithm Development for Prognostic Health Monitoring and Maintenance	281
26533	Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents	255	26545	New Mechanism for Upset of Electronics	283
26534	Advanced Unattended Ground Sensor Technology	258	26546	Flexible Robotic Maintenance Facility	285
26535	The Endowment of Simulator Agents with Human-Like Episodic Memory	261	26547	Distributed Autonomous Navigation	287
26536	Automated Combat Course of Action (COA) Development	264	26548	Obstacle Detection for Autonomous Navigation	289
26537	An Advanced Learning Model for Agent Behavior	266	26549	Very High Temperature Gas-Cooled Reactor	365
			26550	Solid-State Ballistic Chemical Sensors	315

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
26551	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	368	26562	Compact UV Laser Source for Chemical and Biological Sensing	578
26552	A Model of Infrastructure Interdependency Using Communication Agents	370	26563	Advanced Digital Detectors for Neutron Imaging	580
26553	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	373	26564	Microfabricated Acoustic Spectrum Analyzer	582
26554	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	376	26565	Enabling Analytical and Modeling Tools for Enhanced Disease Surveillance	585
26555	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	378	26566	Microtransceiver for Tag, Beacon, and Data-Exfiltration Applications	587
26556	Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion	381	26567	Extensibility of Knowledge-Based Human Agent Simulation	589
26557	Specific Anion Nanoengineered Sorbents for Water Purification	383	26568	Secure Authenticated Sensor Packs	592
26558	Risk-Informed Proliferation Analysis Development	568	26569	Remote Monitoring of Difficult, Real-Time Targets Using Video SAR Technique	595
26559	Development of a Microoptic Gyroscope	571	26570	Adaptive Computer Intrusion Detection	597
26560	Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation	573	26571	Link Analysis Using High-Performance Computing	599
26561	New Glass Technology for Enhanced Architectural Surety	575	26572	Coating Chemical Preconcentrators to Improve Chemical Agent Collection	602
			26573	Ultralow-Power Spread-Spectrum Transceivers for Microtags to Improve Security During Critical Operations	604
			26574	Detection and Exploitation of Spread-Spectrum Waveforms	607

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
26575	Small Power Direct-Conversion Microfluid Systems Using Logistical Fuels	609	27328	A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting	443
26576	High-Bandwidth Optical Data Interconnects for Satellite Applications	612	28763	Use of Intense Ion Beams for Surface Modification and Creation of New Materials	655
26577	Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources	615	28764	Low-Intensity Laser Triggering of Spark Gaps	657
26578	Deployable Large-Aperture Optics System for Remote-Sensing Applications	618	28766	Enhanced Impulse Experimentation Capability	659
26579	MicroChemLab Technologies for Early Detection of Pathogen Exposure	622	28769	Z-Pinch Power-Plant System Development	661
26580	Intelligent Tracking of the Tele-present Rapid-Aiming Platform	625	28770	Recyclable Transmission Line Concept for Z-Pinch IFE	664
26581	Molecular-Scale Studies of Single-Channel Membrane Pores	103	28771	Suppression of Electron Emission from Conductors	665
26582	Efficient Massively Parallel Techniques for Protein Structure Generation	105	28772	Solid-State Switch for Advanced Pulsed Power	667
26583	Mapping Membrane Protein Interactions in Cell Signaling Systems	107	28775	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	291
26770	Interconnection Technology for Next Generation of Integrated Microsystems	543	28776	Interfacial Bioscience Grand Challenge (IBIG)	447
26781	Effect of Dielectric Photoelectric Effect on Surface Breakdown	435	32159	Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles	40
			32161	Micromachined Patch-Clamp Array	42
			32163	Microscale Techniques for the Study of Cell Signaling	44

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
32166	Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling	47	32913	Aging Mechanisms in Dormant MEMS Structures	209
32573	Molecular Self-Assembly	720	32914	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	728
32574	High-Throughput Instruments, Methods, and Informatics for Systems Biology	109	32915	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	516
32575	Active Management Systems for Water-Quality Monitoring	385	32923	MEMS in μ Fluid Channels	211
32576	Isentropic Compression Experiments on the Saturn Accelerator	669	33317	Training Software Agents to Reason in the Absence of Data	49
32807	Low-Work-Function Material Development for the Microminature Thermionic Converter	388	33319	Numerical Methods Applied to High-Energy Physics	152
32809	Autonomous Microexplosive Subsurface Tracing System	391	33323	Engineering Biomicrodevice Interfaces: New Microfuel Cells for Harvesting Energy from Biological Systems	627
32810	Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar	394	33505	Embedded Self-Powered Microsensors for Monitoring the Surety of Critical Buildings and Infrastructures	630
32815	Security Models of Agent-Based Coalitions	396	33506	Photonic Lattice Coatings	632
32816	Vulnerability Assessment of National Power Grid	399	33508	Applicability of a Self-Referencing Shearing Interferometric Vibration Detector	633
32817	Molecular Simulations of MEMS Coatings	722	33509	Small-Scale High-Performance Optics	635
32818	Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches	723	33602	Dispersive Photonics for Next-Generation Sensors and Microsystems	213
32819	Fundamental Studies of Water-Surface Interactions	725			

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
34438	Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves	730	34474	Conceptual Design of Self-Adjusting Inertial Inmate Restraints	644
34439	Scanning Tunneling Microscopy of Silicon-Based Nanostructures	732	34475	Miniaturized Sensor Technologies for Drug Detection	646
34465	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	518	34476	The Development of Polymer-Based Antitamper Systems	649
34466	Mechanics and Tribology of MEMS Materials	520	34478	LIGA Microsystems Aging: Evaluation and Mitigation	532
34467	Dynamics of Metal/Ceramic Interfaces	523	34484	Network-Enabled Firmware	651
34468	<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth	524	34485	Science-Based Processing of Field-Structured Composites	534
34469	Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	527	34487	Atmospheric Plasma Applications	293
34470	Nanoscale Mechanics in an Instrumented Transmission Electron Microscope	530	34488	Feasibility Study on Fire-Suppression Properties of the Sandia Decon Foam	295
34471	Terahertz Radiation Technology for MASINT	638	34489	Feasibility Study for Improved Less-Lethal Weapons	297
34472	Radar Tag for the Remote Monitoring of Restricted Equipment	640	34490	Feasibility Study for 5x Enhanced Energetic Materials	300
34473	Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System	643	34491	Nanolaser Flowchip for Real-Time Cell and Tumor Biology	111
			34692	Self-Assembly of Polymers in Confined Geometries	733
			34693	Building Conscious Machines Based on the Primate Brain	735
			34694	Ultrahigh-Temperature Ceramic Material Research	302

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
34696	Modeling Building Air Flow for Autonomous Robotic Agents	304	38109	Chip-Based Optical-Cell Manipulation	748
34697	Investigation of Advanced Digital-Video Compression for the Control of Robotic Platforms	305	38110	Advanced Particle Control for Electric-Discharge Light Sources	750
34698	Microfuzze	307	38822	Wireless Infrastructure Data-Transmission System	752
34699	Exploration of New Multivariate Spectral Calibration Algorithms	536	39016	Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat	312
34713	Nonlinear Modeling and Simulation of Pulsed Electromagnetic Stimulation and Response of Selected Excitable Biological Structures	51	39212	MEMS-Based Electromechanical Acoustic Energy Harvester	754
35008	Intelligent Projectile Development	310	39420	Self-Organizing Network Intelligent Algorithm (SONIA)	155
35376	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	738	41194	Cognition-Driven Augmented Analyst	653
35510	MyLink	54			
36901	Microcontact Printing of Nanoparticle Arrays	740			
36902	Mathematical Analysis of Deception	742			
36904	A System Dynamics Approach to Modeling Water Demand	743			
37690	Indications and Warnings in the Cyber Domain	652			
38108	Controlling Contamination in Precision Mirrors by Surface-Capping Modifications	745			

Appendix B: Awards/Recognition List

<i>Awards/Recognition</i>	<i>Project Number</i>	<i>Project Title</i>
Sandia Annual Student Intern Symposium Best Paper Award: Kimberly Butler, “Immobilization of Biomaterials in Porous Silica Thin Films”	10377	Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay
DP Award of Excellence	10393	Production Surety and Disruption Vulnerability Analysis
Arch T. Colvell Merit Award, SAE International	10739	Laser-Assisted Microgas Metal Arc Welding
Ford Foundation Fellowship: Helen Baca, graduate student	26528	Biocompatible Self Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance
DOE NETL Award for energy-efficiency research, sponsored by the DOE Office of Building Technology and State (DOE/BTS)	27328	A Revolution in Lighting: Building the Science and Technology Base Lighting
Arch T. Colvell Merit Award, SAE International	34465	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation
DOE ER100 Award	34491	Nanolaser Flowchip for Real-Time Cell and Tumor Biology

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films	10300	2											90%	2	7
Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments	10301	1	1										70%	2	6
Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS	10302	5	1					2	1				85%	2	10
Linking Atomistic Computations with Phase-Field Modeling	10303	1											90%	1	6
A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms	10304		1					1					70%	2	7
Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth	10305	1						2	1	1			80%	2	8
Wetting and Spreading Dynamics of Solder and Braze Alloys	10306	7	2	2					1				90%	2	7
Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms	10307	4	7		2				2	1	1		80%	2	6
Microscale Shock-Wave Physics Using Photonic Driver Techniques	10308		3										90%	2	7
Heterogeneous Simulation	10313				1			2		1			100%	1	6
Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions	10314	1		2			1	1					100%	1	7
Hybrid Sparse-Dense Incomplete Factorization Preconditioners	10315		5				3	2					100%	1	8
Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry	10316	1	2										90%	4	7
Molecular Simulation of Reacting Systems	10317												50%	3	7
Massively Parallel Global Climate Model for Paleoclimate Applications	10318	2											99%	1	6
Silicon Three-Dimensional Photonic Crystal and Its Applications	10328	4											100%	1	6
Monolithic Micromachined Variable Tuners for Rapid Prototyping and Optimization of Microwave Circuits	10329												15%	4	7
Quantum Tunneling Transistors for Practical Application	10330				1	1							50%	3	7
Development of Magnetically Excited Flexural Plate-Wave Devices for Implementation as Physical, Chemical, and Acoustic Sensors, and as Integrated Micropumps for Sensored Systems	10331	1	1					1		1			80%	3	7

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments	10379		1					1					100%	1	7
Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays	10380							3					80%	4	7
Miniature UV Fluorescence-Based Biological Agent Sensor	10381												60%	3	7
Hybrid Processing of Measurable and Subjective Information in Surety Analysis	10388	5	1	1	1		1						100%	2	7
Production Surety and Disruption Vulnerability Analysis	10393	3	2					1		1	2		100%	1	7
An Optically Triggered Semiconductor Switch for Firing Systems	10394	1		1									90%	2	6
Source Code Assurance Tool	10395		3	2									80%	2	7
Information Collection	10399												97%	1	6
Information Extraction from Hyperspectral Images Obtained from Satellites	10407	1	2		2				1		1		100%	1	6
Capillary Elastohydrodynamics in Manufacturing Processes	10409	1			1			1					100%	1	7
Nanosat	10693	1	16					8					80%	2	8
A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	10718	3		1				2	1				33%	3	6
Radiation-Induced Prompt Photocurrents in Microelectronics: Physics	10719	2											100%	1	7
Proton Beam Directed-Energy Weapon	10720												100%	1	6
Volumetric Displacement Control (VDC) of Manufacturing Tools	10721	1		2	2			2			1		100%	1	7
Process-Based Quality Tools to Verify Cleaning and Surface Preparation	10722	5						3	1	1			100%	1	7
Fabrication of Three-Dimensional Microstructures Using Soft Lithography	10723		1					1					90%	2	7
High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	10724	1											80%	1	7
A Micro-GC–Based Controller for Energy-Intensive Processes	10725				2								95%	1	6
Micro-High-G Acceleration Recorder	10727												50%	3	9
Algorithmic Advances in Computational Structural Biology	10728	2	1					1					75%	2	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Ultraminiaturization of RF Circuitry	10729									1			70%	2	7
An Actuator Based on an Electrokinetic Pump	10731	1	1										50%	4	7
A MEMS Microelectric Generator	10732			1									80%	2	6
SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications	10733												85%	2	7
Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis	10734		3	1				2					90%	3	7
Physical Basis for Interfacial Traction-Separation Models	10735		3										90%	2	7
Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation	10736			1				1					90%	1	7
Laser-Assisted Microgas Metal Arc Welding	10739							3			1		100%	2	9
Diagnostics for Joining Solidification/Microstructural Simulations	10740	3	3	2					1	1			90%	2	7
Effects of Microstructural Variables on the Shock-Wave Response of PZT 95/5	10741		1										90%	2	7
Mechanisms of Dislocation-Grain Boundary Interaction	10742	8	1						1				100%	2	8
Defining the Frontiers of Vertical, External-Cavity, Surface-Emitting Lasers	10744	1		1									50%	3	9
Predicting Function of Biological Macromolecules	10746	3						1	1	3			75%	2	7
Induced Molecular Markers for Pathogen Detection: Microincubators for Rapid Toxin Expression	10747							1		2			70%	3	6
Nanostructured Silicon Surfaces for Cost-Effective Photovoltaic Efficiency Improvements	10748		1	1									50%	2	7
Growth and Characterization of Quantum Dots and Quantum Dot Devices	10749	5							2				90%	2	7
Automatic Design of Practical Fixtures	10751	5	2	1				1			1		90%	2	6
Distributed Reconfigurable Homogeneous Microrobotic Systems	10752							4					90%	2	8
Robust Planning for Autonomous Navigation of Mobile Robots in Unstructured, Dynamic Environments	10753												100%	1	7
Functional Materials for Electrochemomechanical Actuation of Microvalves and Micropumps	10754	1			1			1		1			60%	3	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Microreplication: Precision Metal Parts from Electroformed Master Molds	10755												75%	3	6
New Architectures for Micro-Total-Analytical Systems	10756	4		2				2					75%	3	9
Large-Scale Nonlinear Optimization Arising from PDE Models	10757	3	1					1	1	1			85%	3	7
Network Intrusion Detection Using Adaptive Critic Neural Networks	10758												90%	2	6
Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry	10759		1					1		1			100%	1	7
Making the Connection Between Microstructure and Mechanics	10761	4						1					100%	1	7
Self-Assembled, Tamper-Detection Seals	10762		2	1	1					1			90%	1	7
Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	10763	2							1	1			100%	1	7
Energetic-Material Burn and Detonation at the Mesoscale	10765			1						1			90%	2	7
Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	10766	2											90%	2	6
Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	10767	2		1						1			100%	1	6
IMEMS Packaging and Interconnection Technology	10770		1	7	1			2					98%	2	7
Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	10771							1					95%	2	7
Intense Directed-Energy Theory Initiative	10772							1	1	2			100%	1	7
Assembly of LIGA Using Electric Fields	10773	1		1				1					50%	3	7
Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes	10774		1					1	1				75%	1	7
Miniature Sensors for BW Agents Using Fatty-Acid Profiles	10775		1	1	1			1	1	1			80%	2	7
Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	10776	5	3					2	1	2			100%	1	7
Parallel Methods for Coupling Circuit- and Device-Scale Simulations	10777												80%	3	7
A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems	10778		2	1									75%	2	7
Switchable Hydrophobic-Hydrophilic Surfaces	10779	4	4	1				2	2				80%	4	8

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Nanostructured Materials Integrated in Microfabricated Optical Devices	10780	2						1	1				85%	2	7
High-Al-Content AlGaInN Devices for Next-Generation Electronic and Optoelectronic Applications	10782	1	1	1	1								71%	2	7
Microfabrication of Electromagnetic Devices	10783	1		2	2								60%	3	7
GaAs MOEMS Technology	10784	1	1	1	1								75%	2	9
Integrated Microsensors for Autonomous Microrobots	10785			1				2					100%	1	7
Silicon-Integrated Planar Microbatteries	10786												90%	3	7
Small-Scale Multiaxial Deformation Experiments on Solder for High-Fidelity Model Development	10788	3						1	1	1			100%	1	7
All-Ceramic Battery	10789	2			2			3					80%	2	7
Fuzzy Data Mining	10791		1							0.5			75%	2	8
Ultrahigh-Resolution Radiography for Detailed Inspection of Weapon Components and Systems	10792												20%	11	7
Computer Numerically Controlled Micromachines	10793			1	1								80%	2	7
Electromicrofluidic Packaging	10794	2		2	2								90%	2	7
Surface-Micromachined Mechanical Timer	10795												100%	2	6
High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS	10796	2		2									90%	1	7
Molecular Integrated Microsystems (MIMS)	11130	11			2	1		7	5	2			95%	1	6
Pseudostationary Separation Materials for Highly Parallel Microseparations	16167	5											100%	1	6
Novel Coatings for Microelectromechanical (MEM) Devices	17230	5		2	2			1	1				100%	1	6
Use of Apatite and Substituted Apatites for <i>In Situ</i> Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water	19991	2		2	2			1					100%	2	9
DNA Microarray Technology	20413	1	2					5	2				100%	1	7
Shock Response of Diamond Crystals	20414												85%	2	7
Information-Sharing Security Module Research and Development	20416	1		1	1			1					100%	1	6

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment			
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Techniques for Improving and Exploiting MTI Imagery	21280		3										60%	3	6
Solutions to National and Global Security Issues Based on Limited Freshwater Resources	21554			1				2					100%	1	6
Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures	21559						1						90%	2	6
Understanding and Managing Threats to the Social Fabric of the United States	22126		2					1					90%	2	7
Investigation of Nanoscience Technologies	22131												100%	1	7
Magnetic Polysilicon MEMS Devices	22132	3		2				2					85%	2	9
Theoretical Study of Sb as a Surfactant in Epitaxy of III–V Materials	22854	1						1					95%	2	6
Single-Wire Explosion Experiments	22995	1											100%	1	7
Scattering from Nanostructured Materials	22996	1						1			1		85%	1	7
The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	22997							1	1				85%	2	7
A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	24101												80%	3	7
Magnetically Insulated Power Flow Experiment	24102												80%	2	7
Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508												80%	2	7
Levitated Three-Axis Microaccelerometer	26509			1									100%	1	8
Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques	26510	2			2				1				95%	1	6
Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511		3					1	1				90%	2	7
Parallel Atomistic Computing for Failure Analysis of Micromachines	26512		3					1	1				50%	3	7
Implementation of Fault Tolerance in Scientific Simulation Application Software	26513							1	1				80%	2	8
Smart Sensor Technology for Joint Test Assembly Flights	26514												100%	1	7
Multilevel Methods for Nonlinear Structural Mechanics	26515												100%	1	7
Algorithmic Support for Commodity-Based Parallel Computing Systems	26516							2					100%	1	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment			
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Parallel Repartitioning for Optimal Solver Performance	26517	3	2				1	1	1				100%	1	7
II–V:Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	26518	1	2										75%	2	8
The Integration of Advanced Photonics and MEMS	26519			2									100%	1	7
Uncertainty Propagation in Models of Thermofluid Systems	26520	1							1				100%	1	7
Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521		3										80%	2	7
A Physically Based Approach to Modeling Ductile Fracture	26522								1				85%	2	7
Radiation Aging of Stockpile and Space-Based Microelectronics	26523												100%	1	8
Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524	1	2					1		1			89%	4	7
Magnetic-Field Effects on Vacuum-Arc Plasmas	26525												80%	4	7
Microstructural and Continuum Evolution Modeling of Sintering	26526	1	3				1		1				100%	1	7
Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527												90%	3	7
Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528							1	1		1		95%	1	7
Nanoclusters for Supercapacitors	26529												100%	1	6
First-Principles Determination of Dislocation Properties	26530	1											80%	2	8
Air Sterilization and Decontamination	26531			1									90%	2	7
Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532												100%	1	7
Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents	26533	1						1	1				85%	2	7
Advanced Unattended Ground Sensor Technology	26534												90%	2	7
The Endowment of Simulator Agents with Human-Like Episodic Memory	26535	2	1	1				1		1			100%	1	7
Automated Combat Course of Action (COA) Development	26536												80%	2	8
An Advanced Learning Model for Agent Behavior	26537				1			1					100%	1	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Threat-Assessment Study for Short-Pulse Laser Technologies in Directed-Energy and Countersensor Applications	26538									1	1		90%	2	6
Algorithms for Improved Performance in Cryptographic Protocols	26539		1					2					100%	1	7
Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	26540		1	2				3		1			90%	1	7
Triggered Isomer Research	26541									4			90%	2	7
A Scientific Basis for Robotic Ground-Vehicle Design	26542												90%	2	7
Adaptive and Mobile Ground Sensors	26543									2			100%	1	7
Algorithm Development for Prognostic Health Monitoring and Maintenance	26544		1										90%	1	7
New Mechanism for Upset of Electronics	26545							1		1			90%	2	7
Flexible Robotic Maintenance Facility	26546		1										95%	2	10
Distributed Autonomous Navigation	26547									1			90%	3	8
Obstacle Detection for Autonomous Navigation	26548							5					100%	1	7
Very High Temperature Gas-Cooled Reactor	26549												100%	1	7
Solid-State Ballistic Chemical Sensors	26550								1				60%	3	7
Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	26551		1					1	1				90%	1	7
A Model of Infrastructure Interdependency Using Communication Agents	26552	1	1					1					95%	2	7
Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	26553	1	5	2				4		2			100%	1	7
Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554			1	1			1	2	6			100%	1	6
Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555												70%	2	7
Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion	26556			1	2								100%	1	6
Specific Anion Nanoengineered Sorbents for Water Purification	26557			1	1			2	1				100%	1	6
Risk-Informed Proliferation Analysis Development	26558							1					100%	1	6

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Development of a Microoptic Gyroscope	26559												75%	4	7
Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation	26560												100%	1	7
New Glass Technology for Enhanced Architectural Surety	26561		6					2	1	1			90%	2	7
Compact UV Laser Source for Chemical and Biological Sensing	26562	1	2	1									100%	1	7
Advanced Digital Detectors for Neutron Imaging	26563			3	2			3					90%	1	7
Microfabricated Acoustic Spectrum Analyzer	26564			2				1		1			100%	2	6
Enabling Analytical and Modeling Tools for Enhanced Disease Surveillance	26565		1										100%	1	7
Microtransceiver for Tag, Beacon, and Data-Exfiltration Applications	26566			1									75%	3	7
Extensibility of Knowledge-Based Human-Agent Simulation	26567	2	1					1		1			100%	1	7
Secure Authenticated Sensor Packs	26568												100%	1	6
Remote Monitoring of Difficult, Real-Time Targets Using Video SAR Technique	26569												90%	2	7
Adaptive Computer Intrusion Detection	26570												100%	2	6
Link Analysis Using High-Performance Computing	26571		1										100%	1	9
Coating Chemical Preconcentrators to Improve Chemical Agent Collection	26572							1					100%	3	7
Ultralow-Power Spread-Spectrum Transceivers for Microtags to Improve Security During Critical Operations	26573							1					80%	2	6
Detection and Exploitation of Spread-Spectrum Waveforms	26574												100%	1	7
Small Power Direct-Conversion Microfluid Systems Using Logistical Fuels	26575		1	1				2	1				90%	1	7
High-Bandwidth Optical Data Interconnects for Satellite Applications	26576	1											90%	2	9
Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources	26577								1				85%	1	7
Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578	1	6	1		1		1		3			95%	2	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
MicroChemLab Technologies for Early Detection of Pathogen Exposure	26579								1				90%	1	6
Intelligent Tracking of the Telepresent Rapid-Aiming Platform	26580									4			100%	1	7
Molecular-Scale Studies of Single-Channel Membrane Pores	26581								1				100%	1	7
Efficient Massively Parallel Techniques for Protein Structure Generation	26582	1											100%	1	7
Mapping Membrane Protein Interactions in Cell Signaling Systems	26583	2							1	1			100%	1	7
Interconnection Technology for Next Generation of Integrated Microsystems	26770												100%	1	9
Effect of Dielectric Photoelectric Effect on Surface Breakdown	26781		1										50%	3	7
A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting	27328	10	15	5						1	1		100%	1	7
Use of Intense Ion Beams for Surface Modification and Creation of New Materials	28763												40%	3	8
Low-Intensity Laser Triggering of Spark Gaps	28764												90%	3	7
Enhanced Impulse Experimentation Capability	28766												100%	2	9
Z-Pinch Power-Plant System Development	28769	1											100%	1	7
Recyclable Transmission Line Concept for Z-Pinch IFE	28770												100%	1	6
Suppression of Electron Emission from Conductors	28771												80%	3	7
Solid-State Switch for Advanced Pulsed Power	28772					1							90%	3	7
Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	28775							2	1	1			80%	3	7
Interfacial Bioscience Grand Challenge (IBIG)	28776							2	2	3			90%	2	7
Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles	32159												80%	1	6
Micromachined Patch-Clamp Array	32161												75%	3	7
Microscale Techniques for the Study of Cell Signaling	32163								1				80%	2	6
Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling	32166	2			2			1		1			80%	4	6

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment			
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Applicability of a Self-Referencing Shearing Interferometric Vibration Detector	33508							1		1			80%	2	7
Small-Scale High-Performance Optics	33509		1					1					100	2	7
Dispersive Photonics for Next-Generation Sensors and Microsystems	33602	1							1				60	2	7
Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves	34438	1						1					100	1	6
Scanning Tunneling Microscopy of Silicon-Based Nanostructures	34439							1					60	3	7
Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	34465	1						1			1		80	1	7
Mechanics and Tribology of MEMS Materials	34466	5	5					2					90	2	7
Dynamics of Metal/Ceramic Interfaces	34467	1											100	1	7
<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth	34468												75	3	7
Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469	2											90	1	7
Nanoscale Mechanics in an Instrumented Transmission Electron Microscope	34470												100	1	7
Terahertz Radiation Technology for MASINT	34471												100	1	7
Radar Tag for the Remote Monitoring of Restricted Equipment	34472												100	1	6
Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System	34473												100	2	8
Conceptual Design of Self-Adjusting Inertial Inmate Restraints	34474												65	3	8
Miniaturized Sensor Technologies for Drug Detection	34475												70	3	7
The Development of Polymer-Based Antitamper Systems	34476												100	1	6
LIGA Microsystems Aging: Evaluation and Mitigation	34478												35	4	7
Network-Enabled Firmware	34484												100	1	6
Science-Based Processing of Field-Structured Composites	34485												70	3	8
Atmospheric Plasma Applications	34487								1	1			100	1	6

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

Project Title	Project #	Performance Statistics (Number of)											Project Qualitative Assessment		
		Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Wireless Infrastructure Data-Transmission System	38822												75	2	7
Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat	39016		1										75	2	7
MEMS-Based Electromechanical Acoustic-Energy Harvester	39212												80	2	7
Self-Organizing Network Intelligent Algorithm (SONIA)	39420												100	1	7
Cognition-Driven Augmented Analyst	41194												100	1	10
		267	197	96	59	7	10	187	71	81	21	0			

† Identification of new non-LDRD-funded projects is now completed in the fiscal year following the annual report.

* Permanent Staff Hired. Laboratories operate under manpower cap. There are no increases in permanent staff.

** Goals Status

- 1 - Goals Met
- 2 - Goals Substantially Met
- 3 - Goals Partially Met
- 4 - Goals Substantially Modified
- 5 - Goals Not Met
- 11 - Project Terminated

***Hypothesis Status

- 6 - Hypotheses Proved
- 7 - Hypotheses Remains Unchanged
- 8 - Hypotheses Modified
- 9 - Hypotheses Redefined
- 10 - Hypotheses Disproved
- 11 - Project Terminated

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
450	Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films	10300												•		•					
453	Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments	10301		•	•											•					
456	Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS	10302	•	•	•			•						•		•			•		
458	Linking Atomistic Computations with Phase-Field Modeling	10303		•												•					
460	A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms	10304	•	•																	
462	Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth	10305	•													•					
464	Wetting and Spreading Dynamics of Solder and Braze Alloys	10306	•	•	•											•					
467	Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms	10307	•				•														
471	Microscale Shock-Wave Physics Using Photonic Driver Techniques	10308		•			•	•		•						•					
114	Heterogeneous Simulation	10313		•	•			•									•		•		
116	Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions	10314						•											•		
118	Hybrid Sparse-Dense Incomplete Factorization Preconditioners	10315			•																
121	Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry	10316		•	•		•						•								
124	Molecular Simulation of Reacting Systems	10317		•	•											•					
126	Massively Parallel Global Climate Model for Paleoclimate Applications	10318		•	•																
158	Silicon Three-Dimensional Photonic Crystal and Its Applications	10328										•		•							

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
551	Controlling Information: Its Flow, Fusion, and Coordination	10365	●						●								●		●		
217	Surface Decontamination of Bacterial Protein Toxins by RF Power	10368																			●
219	Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures	10369										●		●							
221	HPM Vulnerability Assessment and Tests	10370						●	●												●
223	Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay	10377							●											●	
552	Characterization of Underground Facilities in an Urban Environment	10378																			●
226	Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments	10379	●						●								●		●	●	
229	Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays	10380		●															●		
232	Miniature UV Fluorescence-Based Biological Agent Sensor	10381							●			●		●							
327	Hybrid Processing of Measurable and Subjective Information in Surety Analysis	10388	●	●			●	●													
329	Production Surety and Disruption Vulnerability Analysis	10393		●					●						●		●	●			
672	An Optically Triggered Semiconductor Switch for Firing Systems	10394					●	●	●	●		●	●	●	●						
332	Source Code Assurance Tool	10395	●	●			●														●
438	Information Collection	10399							●					●		●			●		●
674	Information Extraction from Hyperspectral Images Obtained from Satellites	10407	●	●					●		●					●		●		●	
676	Capillary Elastohydrodynamics in Manufacturing Processes	10409	●	●																	
554	Nanosat	10693	●	●					●		●	●		●		●			●		

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
335	A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	10718	•						•					•					•		
172	Radiation-Induced Prompt Photocurrents in Microelectronics: Physics	10719	•	•																	
235	Proton Beam Directed-Energy Weapon	10720											•								
63	Volumetric Displacement Control (VDC) of Manufacturing Tools	10721	•														•		•		
66	Process-Based Quality Tools to Verify Cleaning and Surface Preparation	10722	•											•		•	•	•	•	•	
69	Fabrication of Three-Dimensional Microstructures Using Soft Lithography	10723												•		•	•				
560	High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	10724	•	•					•												•
338	A Micro-GC-Based Controller for Energy-Intensive Processes	10725															•	•	•	•	•
237	Micro-High-G Acceleration Recorder	10727								•				•							
129	Algorithmic Advances in Computational Structural Biology	10728		•	•																
678	Ultraminiaturization of RF Circuitry	10729												•							
681	An Actuator Based on an Electrokinetic Pump	10731												•							•
341	A MEMS Microelectric Generator	10732							•					•							
175	SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications	10733												•					•		
474	Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis	10734	•														•		•		
477	Physical Basis for Interfacial Traction-Separation Models	10735		•												•					
239	Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation	10736						•		•		•		•			•		•		
684	Laser-Assisted Microgas Metal Arc Welding	10739										•					•		•		

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
348	Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry	10759		•																	•
491	Making the Connection Between Microstructure and Mechanics	10761	•	•	•											•					
564	Self-Assembled, Tamper-Detection Seals	10762							•												
350	Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	10763		•																	
416	Energetic-Material Burn and Detonation at the Mesoscale	10765	•	•				•			•			•		•					
184	Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	10766										•		•							
353	Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	10767			•																
78	IMEMS Packaging and Interconnection Technology	10770												•					•		
356	Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	10771									•					•					
246	Intense Directed-Energy Theory Initiative	10772		•									•								
81	Assembly of LIGA Using Electric Fields	10773												•			•		•		
100	Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes	10774							•					•		•			•	•	
187	Miniature Sensors for BW Agents Using Fatty-Acid Profiles	10775							•					•							
189	Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	10776	•						•					•		•			•	•	
134	Parallel Methods for Coupling Circuit- and Device-Scale Simulations	10777		•	•	•								•							
136	A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems	10778		•																	
494	Switchable Hydrophobic-Hydrophilic Surfaces	10779	•											•		•					
497	Nanostructured Materials Integrated in Microfabricated Optical Devices	10780	•											•							

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
360	Information-Sharing Security Module Research and Development	20416	•																		
566	Techniques for Improving and Exploiting MTI Imagery	21280							•												
35	Solutions to National and Global Security Issues Based on Limited Freshwater Resources	21554																			•
363	Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures	21559	•						•						•						
37	Understanding and Managing Threats to the Social Fabric of the United States	22126	•	•																	
703	Investigation of Nanoscience Technologies	22131	•																		
704	Magnetic Polysilicon MEMS Devices	22132												•							
707	Theoretical Study of Sb as a Surfactant in Epitaxy of III-V Materials	22854	•											•							
709	Single-Wire Explosion Experiments	22995									•		•								
712	Scattering from Nanostructured Materials	22996	•	•																	
715	The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	22997	•	•																	
716	A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	24101												•							
718	Magnetically Insulated Power Flow Experiment	24102				•					•		•								
87	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508							•	•							•		•		
90	Levitated Three-Axis Microaccelerometer	26509							•					•					•		
92	Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques	26510												•		•	•				
94	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511						•						•			•	•	•		•
139	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512	•	•	•									•							

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
141	Implementation of Fault Tolerance in Scientific Simulation Application Software	26513			•																
143	Smart Sensor Technology for Joint Test Assembly Flights	26514		•	•														•		
145	Multilevel Methods for Nonlinear Structural Mechanics	26515		•	•																
147	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516			•																
149	Parallel Repartitioning for Optimal Solver Performance	26517			•																
205	II-V:Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	26518										•		•							
207	The Integration of Advanced Photonics and MEMS	26519												•		•			•		
422	Uncertainty Propagation in Models of Thermofluid Systems	26520		•	•	•	•														
425	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521	•									•									
428	A Physically Based Approach to Modeling Ductile Fracture	26522	•	•	•											•					
430	Radiation Aging of Stockpile and Space-Based Microelectronics	26523	•	•	•	•								•							
432	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524		•																	
502	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525	•	•	•	•															
504	Microstructural and Continuum Evolution Modeling of Sintering	26526		•	•											•	•				
507	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527	•	•				•								•					
509	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528	•						•					•		•			•		
511	Nanoclusters for Supercapacitors	26529	•	•												•					

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
385	Active Management Systems for Water-Quality Monitoring	32575												•							•
669	Isentropic Compression Experiments on the Saturn Accelerator	32576		•						•			•			•					
388	Low-Work-Function Material Development for the Microminiature Thermionic Converter	32807	•	•							•			•		•					
391	Autonomous Microexplosive Subsurface Tracing System	32809								•	•			•							
394	Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar	32810	•	•																	
396	Security Models of Agent-Based Coalitions	32815	•	•				•													
399	Vulnerability Assessment of National Power Grid	32816	•	•	•	•	•														
722	Molecular Simulations of MEMS Coatings	32817	•	•	•																
723	Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches	32818		•							•										
725	Fundamental Studies of Water-Surface Interactions	32819	•	•												•					
209	Aging Mechanisms in Dormant MEMS Structures	32913	•					•								•					
728	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	32914	•	•										•		•				•	
516	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	32915												•							
211	MEMS in μ Fluid Channels	32923												•		•					
49	Training Software Agents to Reason in the Absence of Data	33317		•															•		
152	Numerical Methods Applied to High-Energy Physics	33319	•		•																
627	Engineering Biomicrodevice Interfaces: New Microfuel Cells for Harvesting Energy from Biological Systems	33323												•		•					
630	Embedded Self-Powered Microsensors for Monitoring the Surety of Critical Buildings and Infrastructures	33505								•				•							

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
632	Photonic Lattice Coatings	33506							•					•		•					
633	Applicability of a Self-Referencing Shearing Interferometric Vibration Detector	33508							•			•									
635	Small-Scale High-Performance Optics	33509												•					•		
213	Dispersive Photonics for Next-Generation Sensors and Microsystems	33602			•							•		•							•
730	Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves	34438		•													•	•		•	
732	Scanning Tunneling Microscopy of Silicon-Based Nanostructures	34439												•							
518	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	34465		•								•		•			•				
520	Mechanics and Tribology of MEMS Materials	34466												•							
523	Dynamics of Metal/Ceramic Interfaces	34467	•													•					
524	<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth	34468	•							•				•							
527	Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469		•																	•
530	Nanoscale Mechanics in an Instrumented Transmission Electron Microscope	34470														•					
638	Terahertz Radiation Technology for MASINT	34471							•			•									
640	Radar Tag for the Remote Monitoring of Restricted Equipment	34472							•												
643	Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System	34473																			•
644	Conceptual Design of Self-Adjusting Inertial Inmate Restraints	34474						•													
646	Miniaturized Sensor Technologies for Drug Detection	34475							•					•		•					
649	The Development of Polymer-Based Antitamper Systems	34476						•	•					•		•					

[illegible]

[illegible]

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
450	Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films	10300													•				
453	Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments	10301												•		•			
456	Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS	10302										•			•	•			
458	Linking Atomistic Computations with Phase-Field Modeling	10303									•				•				
460	A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms	10304								•	•				•				
462	Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth	10305								•	•								
464	Wetting and Spreading Dynamics of Solder and Braze Alloys	10306									•				•				
467	Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms	10307									•			•					
471	Microscale Shock-Wave Physics Using Photonic Driver Techniques	10308													•		•		**Biomedical
114	Heterogeneous Simulation	10313					•					•		•	•	•	•		**DARPA
116	Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions	10314														•	•		**Industry
118	Hybrid Sparse-Dense Incomplete Factorization Preconditioners	10315									•				•				
121	Advanced Large-Eddy Simulation Algorithms for Coupled-Flow Physics and Complex Geometry	10316		•				•			•				•	•	•		*NASA
124	Molecular Simulation of Reacting Systems	10317									•			•					
126	Massively Parallel Global Climate Model for Paleoclimate Applications	10318									•								

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
158	Silicon Three-Dimensional Photonic Crystal and Its Applications	10328		•							•				•				
160	Monolithic Micromachined Variable Tuners for Rapid Prototyping and Optimization of Microwave Circuits	10329								•		•		•	•	•			
163	Quantum Tunneling Transistors for Practical Application	10330									•	•			•	•			
165	Development of Magnetically Excited Flexural Plate-Wave Devices for Implementation as Physical, Chemical, and Acoustic Sensors, and as Integrated Micropumps for Sensored Systems	10331					•					•			•	•			
168	Stress-Free Amorphous Diamond for High-Sensitivity Microsensors with Integrated Microstructures	10334								•		•			•		•		*NASA
402	Structural Simulations Using Multiresolution Material Models	10336													•	•			
405	Mechanisms of Adiabatic Shear Failure	10338													•	•			
407	Crack Nucleation and Growth: Combining Validated Atomistic and Continuum Modeling	10340									•				•	•			
410	Applied Microfluidic Physics	10341					•			•		•			•	•			
413	Innovative Measurement Diagnostics for Fluid/Solid and Fluid/Fluid Interactions in Rotating Flowfields	10343													•	•			
57	Microdiagnostic MEMS Lab-on-a-Chip	10347	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
61	Thin-Film Deposition Processes Incorporating <i>In Situ</i> Monitoring Capabilities	10349												•	•	•			
317	Varying QoS for Fixed and Mobile Networks	10356								•		•	•	•	•	•			
546	A Real-Time Decision-Support Framework to Guide Facility Response to Abnormal Events	10357				•						•				•	•	•	*FBI, GSA, FEMA, Dept. of State, DoD, **Industry
549	Physical Model-Based Fusion of Sensor Array Data	10358								•		•			•	•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
319	High-Surety SCADA for the Critical Energy Infrastructures	10360		•	•	•		•		•	•	•	•		•	•		•	**Utility industry, networking & telecommunication
321	Agent-Based Mediation and Cooperative Information Systems	10361										•							
324	Dynamically Self-Configurable Network Protocol	10362	•												•	•			
551	Controlling Information: Its Flow, Fusion, and Coordination	10365		•							•	•			•	•			
217	Surface Decontamination of Bacterial Protein Toxins by RF Power	10368																•	**Counterterrorism
219	Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures	10369										•			•	•			
221	HPM Vulnerability Assessment and Tests	10370										•			•	•			
223	Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay	10377	•									•				•	•		*DARPA, DTRA
552	Characterization of Underground Facilities in an Urban Environment	10378										•				•			
226	Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments	10379	•				•		•			•	•		•	•	•	•	*NIJ, U.S. Customs, DEA, state, local, federal law enforcement, **Industry
229	Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays	10380									•	•				•			
232	Miniature UV Fluorescence-Based Biological Agent Sensor	10381										•				•			
327	Hybrid Processing of Measurable and Subjective Information in Surety Analysis	10388												•	•	•	•		*FAA
329	Production Surety and Disruption Vulnerability Analysis	10393							•						•		•		*NRC
672	An Optically Triggered Semiconductor Switch for Firing Systems	10394		•							•	•		•	•	•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
332	Source Code Assurance Tool	10395										•		•	•	•		•	**Software development
438	Information Collection	10399										•				•			
674	Information Extraction from Hyperspectral Images Obtained from Satellites	10407					•				•	•		•	•				
676	Capillary Elastohydrodynamics in Manufacturing Processes	10409																•	**CRMPC
554	Nanosat	10693		•								•			•	•	•		*AFSPC, NASA, NRO (those agencies dealing with space)
335	A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	10718	•	•			•				•	•				•		•	**Chemical industry
172	Radiation-Induced Prompt Photocurrents in Microelectronics: Physics	10719													•	•			
235	Proton Beam Directed-Energy Weapon	10720													•	•			
63	Volumetric Displacement Control (VDC) of Manufacturing Tools	10721													•	•	•	•	*Department of Commerce (NIST), **Private industry
66	Process-Based Quality Tools to Verify Cleaning and Surface Preparation	10722	•			•	•								•	•	•	•	*EPA, **Industry
69	Fabrication of Three-Dimensional Microstructures Using Soft Lithography	10723										•			•	•		•	**Industry
560	High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	10724													•	•		•	**Medical and Industry
338	A Micro-GC-Based Controller for Energy-Intensive Processes	10725	•	•		•						•				•	•	•	*EPA, **Petrochemical, Petroleum, Pharmaceutical, Process Analytical Chem Instrumentation
237	Micro-High-G Acceleration Recorder	10727													•	•			
129	Algorithmic Advances in Computational Structural Biology	10728															•		*OBER (DOE)
678	Ultraminiaturization of RF Circuitry	10729										•			•	•			
681	An Actuator Based on an Electrokinetic Pump	10731													•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
341	A MEMS Microelectric Generator	10732									•	•			•				
175	SOI-Based High-Aspect-Ratio Si Bulk Micromachining for MEMS Applications	10733										•			•				
474	Next-Generation Output-Based Process Control: An Integration of Modeling, Sensors, and Intelligent Data Analysis	10734													•	•		•	**Industrial partnership
477	Physical Basis for Interfacial Traction-Separation Models	10735													•				
239	Dynamic Range Imaging for Terrain Mapping, Position Determination, and Obstacle Avoidance in Autonomous Navigation	10736										•			•	•	•		*NASA
684	Laser-Assisted Microgas Metal Arc Welding	10739													•	•			
480	Diagnostics for Joining Solidification/Microstructural Simulations	10740													•			•	**Materials Science
483	Effects of Microstructural Variables on the Shock-Wave Response of PZT 95/5	10741													•				
486	Mechanisms of Dislocation-Grain Boundary Interaction	10742									•				•				
178	Defining the Frontiers of Vertical, External-Cavity, Surface-Emitting Lasers	10744													•				
97	Predicting Function of Biological Macromolecules	10746																•	**Biotechnology
562	Induced Molecular Markers for Pathogen Detection: Microincubators for Rapid Toxin Expression	10747										•				•	•		*DOE, CBNP
343	Nanostructured Silicon Surfaces for Cost-Effective Photovoltaic Efficiency Improvements	10748			•					•	•								
181	Growth and Characterization of Quantum Dots and Quantum Dot Devices	10749													•	•			
72	Automatic Design of Practical Fixtures	10751								•					•	•			
241	Distributed Reconfigurable Homogeneous Microrobotic Systems	10752					•					•			•	•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
243	Robust Planning for Autonomous Navigation of Mobile Robots in Unstructured, Dynamic Environments	10753					•					•			•	•			
488	Functional Materials for Electrochemomechanical Actuation of Microvalves and Micropumps	10754													•	•			
75	Microreplication: Precision Metal Parts from Electroformed Master Molds	10755													•			•	**Telecom industry
540	New Architectures for Micro-Total-Analytical Systems	10756																•	**Industry
132	Large-Scale Nonlinear Optimization Arising from PDE Models	10757									•				•				
346	Network Intrusion Detection Using Adaptive Critic Neural Networks	10758										•			•	•			
348	Key Management Techniques for Authenticating Highly Secure SCADA Systems in the Electric Power Industry	10759															•	•	*DOE, **Electric power industry
491	Making the Connection Between Microstructure and Mechanics	10761									•				•				
564	Self-Assembled, Tamper-Detection Seals	10762								•			•						
350	Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	10763									•					•			
416	Energetic-Material Burn and Detonation at the Mesoscale	10765										•			•	•	•		*Security/Intelligence
184	Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	10766								•		•						•	**Datacomm
353	Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	10767										•		•	•	•		•	**Industry and standards
78	IMEMS Packaging and Interconnection Technology	10770												•	•	•			
356	Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	10771		•	•						•	•			•				
246	Intense Directed-Energy Theory Initiative	10772														•			
81	Assembly of LIGA Using Electric Fields	10773													•	•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
100	Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes	10774	•			•	•					•		•	•	•			
187	Miniature Sensors for BW Agents Using Fatty-Acid Profiles	10775	•									•			•	•		•	**Industry
189	Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	10776	•	•			•				•	•			•	•	•	•	*EPA, NIH, DARPA, **Industry — food safety, medical
134	Parallel Methods for Coupling Circuit- and Device-Scale Simulations	10777								•					•	•		•	**Industry
136	A JAVA-Based Tool for Multifidelity Modeling of Coupled Systems	10778													•				
494	Switchable Hydrophobic-Hydrophilic Surfaces	10779								•	•	•				•			
497	Nanostructured Materials Integrated in Microfabricated Optical Devices	10780										•				•			
192	High-Al-Content AlGaInN Devices for Next-Generation Electronic and Optoelectronic Applications	10782		•											•	•			
194	Microfabrication of Electromagnetic Devices	10783									•	•		•	•	•			
196	GaAs MOEMS Technology	10784										•			•	•	•	•	*Classified, **Industry
198	Integrated Microsensors for Autonomous Microrobots	10785										•				•	•		*NASA
201	Silicon-Integrated Planar Microbatteries	10786		•						•	•	•			•	•			*DoD, **Industry
419	Small-Scale Multiaxial Deformation Experiments on Solder for High-Fidelity Model Development	10788								•					•				
499	All-Ceramic Battery	10789		•	•			•			•								
248	Fuzzy Data Mining	10791										•			•				
687	Ultrahigh-Resolution Radiography for Detailed Inspection of Weapon Components and Systems	10792								•					•	•	•	•	*NIH, **Industry
83	Computer Numerically Controlled Micromachines	10793													•			•	**MEMS

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
85	Electromicrofluidic Packaging	10794													•	•			**MEMS
689	Surface-Micromachined Mechanical Timer	10795													•				
203	High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS	10796								•		•			•	•		•	**Optical Communications
439	Molecular Integrated Microsystems (MIMS)	11130									•	•			•				
692	Pseudostationary Separation Materials for Highly Parallel Microseparations	16167										•				•			
695	Novel Coatings for Microelectromechanical (MEM) Devices	17230	•	•	•	•	•	•		•	•	•	•	•	•	•			
358	Use of Apatite and Substituted Apatites for <i>In Situ</i> Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water	19991							•										
699	DNA Microarray Technology	20413					•							•					
701	Shock Response of Diamond Crystals	20414														•			
360	Information-Sharing Security Module Research and Development	20416															•		*Critical Infrastructure
566	Techniques for Improving and Exploiting MTI Imagery	21280										•			•	•			
35	Solutions to National and Global Security Issues Based on Limited Freshwater Resources	21554		•	•					•							•		*Dept. of Agriculture
363	Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures	21559	•		•			•	•		•		•		•	•			
37	Understanding and Managing Threats to the Social Fabric of the United States	22126								•		•			•	•			
703	Investigation of Nanoscience Technologies	22131												•				•	**University
704	Magnetic Polysilicon MEMS Devices	22132													•	•			
707	Theoretical Study of Sb as a Surfactant in Epitaxy of III-V Materials	22854													•			•	**Industry
709	Single-Wire Explosion Experiments	22995													•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
712	Scattering from Nanostructured Materials	22996									•								
715	The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	22997									•								
716	A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	24101										•				•			
718	Magnetically Insulated Power Flow Experiment	24102									•				•				
87	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508								•		•			•	•			
90	Levitated Three-Axis Microaccelerometer	26509										•			•	•			
92	Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques	26510												•	•	•		•	**Industry
94	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511										•			•	•		•	**Industry
139	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512									•				•	•			
141	Implementation of Fault Tolerance in Scientific Simulation Application Software	26513													•	•			
143	Smart Sensor Technology for Joint Test Assembly Flights	26514													•				
145	Multilevel Methods for Nonlinear Structural Mechanics	26515													•			•	**Industry
147	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516									•				•				
149	Parallel Repartitioning for Optimal Solver Performance	26517									•				•				
205	II-V:Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	26518		•	•						•								
207	The Integration of Advanced Photonics and MEMS	26519								•		•			•	•		•	**Communications
422	Uncertainty Propagation in Models of Thermo-fluid Systems	26520									•				•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
425	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521									•				•	•			
428	A Physically Based Approach to Modeling Ductile Fracture	26522									•				•	•			
430	Radiation Aging of Stockpile and Space-Based Microelectronics	26523											•	•	•				
432	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524												•			•		**Industry
502	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525												•					
504	Microstructural and Continuum Evolution Modeling of Sintering	26526		•											•		•		**Industry
507	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527														•	•		**Electronics industry
509	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528	•				•				•	•				•	•	•	*DARPA, **Hewlett-Packard
511	Nanoclusters for Supercapacitors	26529								•					•	•			
513	First-Principles Determination of Dislocation Properties	26530								•	•								
251	Air Sterilization and Decontamination	26531															•		**Counterterrorism
253	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532														•			
255	Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents	26533	•			•	•					•				•	•	•	*DARPA, DoD, C/B Defense, **Industry
258	Advanced Unattended Ground Sensor Technology	26534										•			•	•			
261	The Endowment of Simulator Agents with Human-Like Episodic Memory	26535										•			•	•			
264	Automated Combat Course of Action (COA) Development	26536													•	•	•		*Emergency response

Appendix E: Major National Programs

[illegible]

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
376	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554	•				•	•											
378	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555		•				•			•						•		*EPA, NASA
381	Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion	26556			•			•			•		•				•		*DoD (Navy and Army)
383	Specific Anion Nanoengineered Sorbents for Water Purification	26557	•			•	•			•	•								
568	Risk-Informed Proliferation Analysis Development	26558							•			•	•						
571	Development of a Microoptic Gyroscope	26559										•			•			•	**Automotive industry
573	Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation	26560										•			•	•			
575	New Glass Technology for Enhanced Architectural Surety	26561						•				•			•	•		•	**Industry
578	Compact UV Laser Source for Chemical and Biological Sensing	26562						•			•				•		•		*NASA
580	Advanced Digital Detectors for Neutron Imaging	26563					•		•			•			•			•	**Airport screening industry
582	Microfabricated Acoustic Spectrum Analyzer	26564										•			•	•			
585	Enabling Analytical and Modeling Tools for Enhanced Disease Surveillance	26565													•	•	•		*Centers for Disease Control and Prevention
587	Microtransceiver for Tag, Beacon, and Data-Exfiltration Applications	26566										•				•			
589	Extensibility of Knowledge-Based Human Agent Simulation	26567										•			•	•			
592	Secure Authenticated Sensor Packs	26568										•			•	•			
595	Remote Monitoring of Difficult, Real-Time Targets Using Video SAR Technique	26569										•			•	•		•	**Industry

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
597	Adaptive Computer Intrusion Detection	26570										•			•	•			
599	Link Analysis Using High-Performance Computing	26571										•							
602	Coating Chemical Preconcentrators to Improve Chemical Agent Collection	26572										•			•	•			
604	Ultralow-Power Spread-Spectrum Transceivers for Microtags to Improve Security During Critical Operations	26573										•			•	•	•	•	*NASA, Navy, Army, NIJ **Communications industry
607	Detection and Exploitation of Spread-Spectrum Waveforms	26574										•							
609	Small Power Direct-Conversion Microfluid Systems Using Logistical Fuels	26575										•				•			
612	High-Bandwidth Optical Data Interconnects for Satellite Applications	26576										•				•	•	•	*Classified, **Industry
615	Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources	26577										•				•			
618	Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578										•			•	•	•		*NASA, AFRL, and NRO
622	MicroChemLab Technologies for Early Detection of Pathogen Exposure	26579				•									•				
625	Intelligent Tracking of the Telepresent Rapid-Aiming Platform	26580													•	•	•		*DOE
103	Molecular-Scale Studies of Single-Channel Membrane Pores	26581													•				
105	Efficient Massively Parallel Techniques for Protein Structure Generation	26582				•									•				
107	Mapping Membrane Protein Interactions in Cell Signaling Systems	26583					•										•	•	*NIH, NSF **UCSF-Sandia Consortium
543	Interconnection Technology for Next Generation of Integrated Microsystems	26770								•		•			•	•	•		*NASA
435	Effect of Dielectric Photoelectric Effect on Surface Breakdown	26781													•	•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
443	A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting	27328		•						•	•	•			•	•			
655	Use of Intense Ion Beams for Surface Modification and Creation of New Materials	28763								•	•				•				
657	Low-Intensity Laser Triggering of Spark Gaps	28764									•				•	•			
659	Enhanced Impulse Experimentation Capability	28766													•	•			
661	Z-Pinch Power-Plant System Development	28769	•	•					•	•	•		•						
664	Recyclable Transmission Line Concept for Z-Pinch IFE	28770									•		•						
665	Suppression of Electron Emission from Conductors	28771													•	•			
667	Solid-State Switch for Advanced Pulsed Power	28772									•				•	•			
291	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	28775											•		•				
447	Interfacial Bioscience Grand Challenge (IBIG)	28776									•	•			•		•		*NIH
40	Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles	32159		•						•	•						•		*DOT
42	Micromachined Patch-Clamp Array	32161																•	**Biomedical
44	Microscale Techniques for the Study of Cell Signaling	32163																•	**Alliance for Cellular Signaling
47	Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling	32166												•				•	**Biotech industry
720	Molecular Self-Assembly	32573									•				•				
109	High-Throughput Instruments, Methods, and Informatics for Systems Biology	32574					•										•	•	*NIH, **Biotechnology
385	Active Management Systems for Water-Quality Monitoring	32575															•	•	*EPA, **Industry

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
669	Isentropic Compression Experiments on the Saturn Accelerator	32576													•	•			
388	Low-Work-Function Material Development for the Microminiature Thermionic Converter	32807		•							•		•			•			
391	Autonomous Microexplosive Subsurface Tracing System	32809						•			•							•	**Fossil Energy industry
394	Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar	32810					•	•										•	**Fossil Energy industry
396	Security Models of Agent-Based Coalitions	32815								•		•	•			•			
399	Vulnerability Assessment of National Power Grid	32816									•	•				•	•	•	*NRC, NERC, FERC, **Electric Power Utilities
722	Molecular Simulations of MEMS Coatings	32817		•											•				
723	Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches	32818													•	•			
725	Fundamental Studies of Water-Surface Interactions	32819									•				•				
209	Aging Mechanisms in Dormant MEMS Structures	32913									•				•				
728	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	32914	•	•	•		•				•		•						
516	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	32915												•				•	**SEMATECH
211	MEMS in μ Fluid Channels	32923					•				•	•			•	•			
49	Training Software Agents to Reason in the Absence of Data	33317										•			•	•			
152	Numerical Methods Applied to High-Energy Physics	33319									•					•			
627	Engineering Biomicrodevice Interfaces: New Microfuel Cells for Harvesting Energy from Biological Systems	33323									•	•			•	•			**Industry

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
630	Embedded Self-Powered Microsensors for Monitoring the Surety of Critical Buildings and Infrastructures	33505										•							
632	Photonic Lattice Coatings	33506										•			•				
633	Applicability of a Self-Referencing Shearing Interferometric Vibration Detector	33508										•			•	•			
635	Small-Scale High-Performance Optics	33509										•				•			
213	Dispersive Photonics for Next-Generation Sensors and Microsystems	33602										•			•	•			
730	Molecular Modeling and Simulation for Gaseous Mixtures Adsorbed in Zeolite A and Other Novel Molecular Sieves	34438	•	•				•							•				
732	Scanning Tunneling Microscopy of Silicon-Based Nanostructures	34439									•				•				
518	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	34465													•	•			
520	Mechanics and Tribology of MEMS Materials	34466													•	•	•	•	*NASA, **Industry
523	Dynamics of Metal/Ceramic Interfaces	34467									•				•				
524	<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth	34468									•			•					
527	Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469												•		•			
530	Nanoscale Mechanics in an Instrumented Transmission Electron Microscope	34470									•				•				
638	Terahertz Radiation Technology for MASINT	34471					•					•			•	•			
640	Radar Tag for the Remote Monitoring of Restricted Equipment	34472										•				•			
643	Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System	34473										•							
644	Conceptual Design of Self-Adjusting Inertial Inmate Restraints	34474															•		**Federal/state & local police jurisdictions

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
646	Miniaturized Sensor Technologies for Drug Detection	34475										•			•	•	•	•	*NIJ, U.S. Customs, DEA, state, local, federal law enforcement, **Industry
649	The Development of Polymer-Based Antitamper Systems	34476										•			•	•			
532	LIGA Microsystems Aging: Evaluation and Mitigation	34478													•				
651	Network-Enabled Firmware	34484										•			•				
534	Science-Based Processing of Field-Structured Composites	34485	•												•				
293	Atmospheric Plasma Applications	34487													•	•			
295	Feasibility Study on Fire-Suppression Properties of the Sandia Decon Foam	34488														•	•	•	*DOJ, **Industry
297	Feasibility Study for Improved Less-Lethal Weapons	34489													•				
300	Feasibility Study for 5x Enhanced Energetic Materials	34490										•			•	•	•		*DTRA
111	Nanolaser Flowchip for Real-Time Cell and Tumor Biology	34491									•					•	•		*NIH
733	Self-Assembly of Polymers in Confined Geometries	34692								•	•				•				
735	Building Conscious Machines Based on the Primate Brain	34693										•		•		•			
302	Ultrahigh-Temperature Ceramic Material Research	34694													•	•	•		*NASA
304	Modeling Building Air Flow for Autonomous Robotic Agents	34696										•			•	•			
305	Investigation of Advanced Digital-Video Compression for the Control of Robotic Platforms	34697					•					•			•	•			
307	Microfuze	34698													•	•			
536	Exploration of New Multivariate Spectral Calibration Algorithms	34699	•				•				•	•			•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
51	Nonlinear Modeling and Simulation of Pulsed Electromagnetic Stimulation and Response of Selected Excitable Biological Structures	34713												•		•	•	•	*NIH, **Biotech & medical
310	Intelligent Projectile Development	35008										•			•	•	•		*NASA
738	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	35376													•				
54	MyLink	35510													•	•			
740	Microcontact Printing of Nanoparticle Arrays	36901		•							•					•			
742	Mathematical Analysis of Deception	36902										•		•	•	•			
743	A System Dynamics Approach to Modeling Water Demand	36904			•							•		•			•		*U.S. Geological Survey, U.S. Bureau of Reclamation
652	Indications and Warnings in the Cyber Domain	37690										•							
745	Controlling Contamination in Precision Mirrors by Surface-Capping Modifications	38108															•		**EUVL Program
748	Chip-Based Optical-Cell Manipulation	38109	•			•	•					•			•		•	•	*NIH, **Industry
750	Advanced Particle Control for Electric-Discharge Light Sources	38110								•									
752	Wireless Infrastructure Data-Transmission System	38822																•	**University collaboration
312	Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat	39016													•	•			
754	MEMS-Based Electromechanical Acoustic Energy Harvester	39212		•	•						•								
155	Self-Organizing Network Intelligent Algorithm (SONIA)	39420										•							
653	Cognition-Driven Augmented Analyst	41194													•	•			

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
450	Functional Materials for Microsystems: Smart Self-Assembled Photochromic Films	10300														•		•		•							•	
453	Innovative Experimental and Computational Diagnostics for Monitoring Corrosion in Weapons Environments	10301					•												•									•
456	Self-Healing Molecular Assemblies for Control of Friction and Adhesion in MEMS	10302		•			•		•				•			•		•	•								•	
458	Linking Atomistic Computations with Phase-Field Modeling	10303					•						•														•	
460	A Combinatorial Microlab Investigation of Critical Copper-Corrosion Mechanisms	10304					•		•	•						•		•				•					•	
462	Self-Assembled Templates for Fabricating Novel Nanoarrays and Controlling Materials Growth	10305						•						•		•		•										•
464	Wetting and Spreading Dynamics of Solder and Braze Alloys	10306					•						•	•		•		•									•	
467	Improved Materials-Aging Diagnostics and Mechanisms Through 2-D Hyperspectral Imaging Methods and Algorithms	10307																			•	•					•	
471	Microscale Shock-Wave Physics Using Photonic Driver Techniques	10308															•	•								•		
114	Heterogeneous Simulation	10313					•						•		•						•	•		•			•	
116	Volumetric Video Motion Sensing for Unobtrusive Human-Computer Interactions	10314					•				•										•						•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
407	Crack Nucleation and Growth: Combining Validated Atomistic and Continuum Modeling	10340					•						•	•				•					•				•	
410	Applied Microfluidic Physics	10341		•			•										•	•			•	•	•				•	
413	Innovative Measurement Diagnostics for Fluid/Solid and Fluid/Fluid Interactions in Rotating Flowfields	10343	•				•														•						•	
57	Microdiagnostic MEMS Lab-on-a-Chip	10347	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	
61	Thin-Film Deposition Processes Incorporating <i>In Situ</i> Monitoring Capabilities	10349														•				•		•					•	
317	Varying QoS for Fixed and Mobile Networks	10356					•	•					•		•										•		•	
546	A Real-Time Decision-Support Framework to Guide Facility Response to Abnormal Events	10357					•														•				•		•	
549	Physical Model-Based Fusion of Sensor Array Data	10358		•											•		•					•	•				•	
319	High-Surety SCADA for the Critical Energy Infrastructures	10360					•			•		•										•					•	
321	Agent-Based Mediation and Cooperative Information Systems	10361																					•		•		•	
324	Dynamically Self-Configurable Network Protocol	10362											•								•	•		•			•	
551	Controlling Information: Its Flow, Fusion, and Coordination	10365																				•						•
217	Surface Decontamination of Bacterial Protein Toxins by RF Power	10368	•														•							•			•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
219	Intense White-Light Pulse Propagation in Air Using Self-Guided Optical Filamentation: Applications to Remote Sensing and Countermeasures	10369							•										•	•		•				•		
221	HPM Vulnerability Assessment and Tests	10370					•		•																		•	
223	Dispersible Granular Sensor (Smart Sand) for Landmine Detection Based on TNT Immunoassay	10377		•																	•	•				•		
552	Characterization of Underground Facilities in an Urban Environment	10378																					•			•		
226	Dexterous Robotic Manipulation of Hazardous Materials in Unstructured Environments	10379									•				•						•	•			•		•	
229	Autonomous Dynamic Soaring Platform for Distributed Mobile Sensor Arrays	10380	•				•																				•	
232	Miniature UV Fluorescence-Based Biological Agent Sensor	10381							•										•	•		•					•	
327	Hybrid Processing of Measurable and Subjective Information in Surety Analysis	10388	•				•														•		•		•		•	
329	Production Surety and Disruption Vulnerability Analysis	10393					•				•													•	•		•	
672	An Optically-Triggered Semiconductor Switch for Firing Systems	10394	•						•	•		•							•	•		•					•	
332	Source Code Assurance Tool	10395					•																•		•		•	
438	Information Collection	10399							•													•				•		

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
674	Information Extraction from Hyperspectral Images Obtained from Satellites	10407		•						•					•	•	•			•	•	•	•				•	
676	Capillary Elasto-hydrodynamics in Manufacturing Processes	10409					•											•									•	
554	Nanosat	10693	•				•		•		•					•		•	•	•		•	•			•		
335	A Novel Microcombustor for Sensor and Thermal-Energy Management Applications in Microsystems	10718							•	•					•			•			•	•					•	
172	Radiation-Induced Prompt Photocurrents in Microelectronics: Physics	10719					•		•																	•		
235	Proton Beam Directed-Energy Weapon	10720	•				•			•																	•	
63	Volumetric Displacement Control (VDC) of Manufacturing Tools	10721									•				•							•					•	
66	Process-Based Quality Tools to Verify Cleaning and Surface Preparation	10722				•			•							•		•	•		•	•					•	
69	Fabrication of Three-Dimensional Microstructures Using Soft Lithography	10723							•								•	•	•			•					•	
560	High-Speed 2-D Hadamard Transform Spectral Imager for IR Applications	10724															•					•					•	
338	A Micro-GC-Based Controller for Energy-Intensive Processes	10725								•	•				•						•	•					•	
237	Micro-High-G Acceleration Recorder	10727							•									•	•			•				•		
129	Algorithmic Advances in Computational Structural Biology	10728		•			•						•															•
678	Ultraminiaturization of RF Circuitry	10729							•													•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
564	Self-Assembled, Tamper-Detection Seals	10762														•											•	
350	Control Strategies for Homogeneous Charge-Compression Ignition (HCCI) Engines	10763					•																	•			•	
416	Energetic-Material Burn and Detonation at the Mesoscale	10765					•		•					•		•		•									•	
184	Heterogeneous Integration of Optoelectronic Arrays and Microelectronics	10766							•									•	•	•							•	
353	Intrusion Detection for Asynchronous Transfer Mode (ATM) Networks	10767											•														•	
78	IMEMS Packaging and Interconnection Technology	10770	•		•				•									•	•	•		•					•	
356	Silicon/Carbon Nanocomposites for Rechargeable Battery Applications	10771				•				•						•		•									•	
246	Intense Directed-Energy Theory Initiative	10772					•																•			•		
81	Assembly of LIGA Using Electric Fields	10773							•		•																•	
100	Biosensors Based on the Electrical Impedance of Tethered Lipid Bilayers on Planar Electrodes	10774		•					•								•	•	•			•					•	
187	Miniature Sensors for BW Agents Using Fatty-Acid Profiles	10775		•					•								•	•			•	•					•	
189	Enhanced-Sensitivity Acoustic-Wave Biosensor Arrays	10776		•					•							•	•		•		•	•					•	
134	Parallel Methods for Coupling Circuit- and Device-Scale Simulations	10777					•		•				•										•				•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
203	High-Efficiency Optical MEMS by the Integration of Photonic Lattices with Surface MEMS	10796						●				●						●	●	●							●		
439	Molecular Integrated Microsystems (MIMS)	11130						●												●							●		
692	Pseudostationary Separation Materials for Highly Parallel Microseparations	16167													●						●						●		
695	Novel Coatings for Microelectromechanical (MEM) Devices	17230	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
358	Use of Apatite and Substituted Apatites for <i>In Situ</i> Barriers for Radionuclide Containment and Waste Stabilization and Arsenic Removal from Potable Water	19991																			●							●	
699	DNA Microarray Technology	20413		●																		●							●
701	Shock Response of Diamond Crystals	20414					●																				●		
360	Information-Sharing Security Module Research and Development	20416					●																				●		
566	Techniques for Improving and Exploiting MTI Imagery	21280																				●					●		
35	Solutions to National and Global Security Issues Based on Limited Freshwater Resources	21554								●											●								●
363	Regional Dynamic Simulation Modeling and Analysis of Integrated Nuclear Futures	21559							●												●						●		
37	Understanding and Managing Threats to the Social Fabric of the United States	22126				●																				●			

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
703	Investigation of Nanoscience Technologies	22131																				•						•
704	Magnetic Polysilicon MEMS Devices	22132						•									•	•	•	•		•					•	
707	Theoretical Study of Sb as a Surfactant in Epitaxy of III–V Materials	22854				•												•									•	
709	Single-Wire Explosion Experiments	22995								•																		•
712	Scattering from Nanostructured Materials	22996														•		•										•
715	The Liquid-Crystal Physics of Evaporation-Induced Self-Assembly	22997							•							•		•										•
716	A Micromethanol Steam Reformer for a Hydrogen-Based Microfuel Cell	24101							•									•	•			•					•	
718	Magnetically Insulated Power Flow Experiment	24102								•																•		
87	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508	•								•				•			•										•
90	Levitated Three-Axis Microaccelerometer	26509							•									•				•						•
92	Microfabrication Processes Combining Focused Ion Beam Machining and Thin-Film Vapor Deposition Techniques	26510							•					•		•	•	•	•	•		•						•
94	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511							•								•	•	•			•					•	
139	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512					•						•	•				•	•				•					•
141	Implementation of Fault Tolerance in Scientific Simulation Application Software	26513					•						•										•					•

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
143	Smart Sensor Technology for Joint Test Assembly Flights	26514					•						•									•					•		
145	Multilevel Methods for Nonlinear Structural Mechanics	26515					•						•															•	
147	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516					•						•															•	
149	Parallel Repartitioning for Optimal Solver Performance	26517					•																					•	
205	II-V:Boron-Based Semiconductors for Optoelectronic Materials and Device Studies	26518							•												•							•	
207	The Integration of Advanced Photonics and MEMS	26519							•				•					•	•	•								•	
422	Uncertainty Propagation in Models of Thermofluid Systems	26520					•																					•	
425	Filtered Rayleigh Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521	•				•															•						•	
428	A Physically Based Approach to Modeling Ductile Fracture	26522			•		•							•				•					•					•	
430	Radiation Aging of Stockpile and Space-Based Microelectronics	26523					•		•				•														•		
432	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524					•																					•	
502	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525					•																				•		
504	Microstructural and Continuum Evolution Modeling of Sintering	26526			•	•	•				•			•		•		•					•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
507	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527					•	•								•		•	•			•					•	
509	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528		•	•	•										•	•	•			•	•					•	
511	Nanoclusters for Supercapacitors	26529				•	•											•									•	
513	First-Principles Determination of Dislocation Properties	26530					•																					•
251	Air Sterilization and Decontamination	26531		•													•											•
253	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532																				•				•		
255	Rapid Ultrasensitive Chemical-Fingerprint Detection of Chemical and Biochemical Warfare Agents	26533													•	•	•				•	•					•	
258	Advanced Unattended Ground Sensor Technology	26534	•						•				•		•							•	•			•		
261	The Endowment of Simulator Agents with Human-Like Episodic Memory	26535	•				•								•		•					•		•	•		•	
264	Automated Combat Course of Action (COA) Development	26536											•										•			•		
266	An Advanced Learning Model for Agent Behavior	26537					•															•	•				•	
268	Threat-Assessment Study for Short-Pulse Laser Technologies in Directed-Energy and Countersensor Applications	26538							•							•			•	•		•				•		
270	Algorithms for Improved Performance in Cryptographic Protocols	26539													•		•					•	•		•		•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
273	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	26540	●						●													●					●	
275	Triggered Isomer Research	26541	●							●																	●	
277	A Scientific Basis for Robotic Ground-Vehicle Design	26542					●																●	●			●	
278	Adaptive and Mobile Ground Sensors	26543					●					●			●									●		●		
281	Algorithm Development for Prognostic Health Monitoring and Maintenance	26544					●															●			●		●	
283	New Mechanism for Upset of Electronics	26545					●		●													●					●	
285	Flexible Robotic Maintenance Facility	26546									●																●	
287	Distributed Autonomous Navigation	26547					●					●											●	●				●
289	Obstacle Detection for Autonomous Navigation	26548							●						●							●	●		●			●
365	Very High Temperature Gas-Cooled Reactor	26549								●												●						●
315	Solid-State Ballistic Chemical Sensors	26550								●					●			●				●						●
368	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	26551			●					●	●				●	●		●				●			●			●
370	A Model of Infrastructure Interdependency Using Communication Agents	26552					●																				●	
373	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	26553																			●	●						●

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
376	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554														•					•	•						•
378	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555								•											•			•				•
381	Photonic Crystals for Enhancing Thermophotovoltaic Energy Conversion	26556							•	•								•	•	•							•	
383	Specific Anion Nanoengineered Sorbents for Water Purification	26557			•		•					•				•		•			•						•	
568	Risk-Informed Proliferation Analysis Development	26558								•											•				•		•	
571	Development of a Microoptic Gyroscope	26559	•						•									•	•	•		•					•	
573	Synergistic Merging of Multispectral Transient Radiometry (MSTR) and Multispectral Imaging (MSI) Technology for Enhanced Global Situational Awareness Through Accurate Geolocation	26560					•								•							•	•			•		
575	New Glass Technology for Enhanced Architectural Surety	26561			•											•											•	
578	Compact UV Laser Source for Chemical and Biological Sensing	26562							•	•												•					•	
580	Advanced Digital Detectors for Neutron Imaging	26563															•					•					•	
582	Microfabricated Acoustic Spectrum Analyzer	26564							•						•			•				•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
615	Development of Robust Algorithms for Analysis of Remote Material Spectra in the Presence of Practical Error Sources	26577																				•					•	
618	Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578					•		•										•			•					•	
622	MicroChemLab Technologies for Early Detection of Pathogen Exposure	26579		•													•									•		
625	Intelligent Tracking of the Telepresent Rapid-Aiming Platform	26580													•							•				•		
103	Molecular-Scale Studies of Single-Channel Membrane Pores	26581		•																		•					•	
105	Efficient Massively Parallel Techniques for Protein Structure Generation	26582		•			•						•										•				•	
107	Mapping Membrane Protein Interactions in Cell Signaling Systems	26583		•			•										•						•				•	
543	Interconnection Technology for Next Generation of Integrated Microsystems	26770	•		•	•			•		•	•	•		•		•	•	•	•		•					•	
435	Effect of Dielectric Photoelectric Effect on Surface Breakdown	26781					•		•										•								•	
443	A Revolution in Lighting: Building the Science and Technology Base for Ultra-Efficient Solid-State Lighting	27328							•	•									•	•	•						•	
655	Use of Intense Ion Beams for Surface Modification and Creation of New Materials	28763														•	•										•	
657	Low-Intensity Laser Triggering of Spark Gaps	28764							•	•									•			•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
659	Enhanced Impulse Experimentation Capability	28766					•																			•			
661	Z-Pinch Power-Plant System Development	28769								•						•					•								•
664	Recyclable Transmission Line Concept for Z-Pinch IFE	28770								•																	•		
665	Suppression of Electron Emission from Conductors	28771							•	•				•														•	
667	Solid-State Switch for Advanced Pulsed Power	28772							•	•												•						•	
291	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	28775								•																		•	
447	Interfacial Bioscience Grand Challenge (IBIG)	28776		•			•										•	•				•	•					•	
40	Investigation of Advanced Power Plants and Multiple-Use Applications for Single-Occupancy Vehicles	32159								•																		•	
42	Micromachined Patch-Clamp Array	32161		•					•								•	•										•	
44	Microscale Techniques for the Study of Cell Signaling	32163		•																								•	
47	Computational Prototype of Chemotaxis as an Example of Whole-Cell Modeling	32166		•			•						•															•	
720	Molecular Self-Assembly	32573					•											•										•	
109	High-Throughput Instruments, Methods, and Informatics for Systems Biology	32574		•			•										•		•			•	•					•	
385	Active Management Systems for Water-Quality Monitoring	32575							•												•	•						•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
669	Isentropic Compression Experiments on the Saturn Accelerator	32576			•		•									•											•	
388	Low-Work-Function Material Development for the Microminiature Thermionic Converter	32807			•				•	•		•				•		•	•			•					•	
391	Autonomous Microexplosive Subsurface Tracing System	32809								•									•									•
394	Evaluation of a Prototype Continuous-Wave, Borehole, Ground-Penetrating Radar	32810					•			•		•										•	•					•
396	Security Models of Agent-Based Coalitions	32815													•							•		•			•	
399	Vulnerability Assessment of National Power Grid	32816					•			•			•														•	
722	Molecular Simulations of MEMS Coatings	32817					•																				•	
723	Numerical Simulation of Shock-Induced Combustion Using Probability-Density Function Approaches	32818					•																		•			
725	Fundamental Studies of Water-Surface Interactions	32819					•									•		•									•	
209	Aging Mechanisms in Dormant MEMS Structures	32913														•		•				•					•	
728	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	32914		•			•	•		•				•		•		•		•	•	•						•
516	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	32915							•							•		•									•	
211	MEMS in uFluid Channels	32923		•					•	•						•		•	•			•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
524	<i>In Situ</i> Characterization of Soft-Solution Processes for Nanoscale Growth	34468			•	•			•							•		•		•							•	
527	Determination of Critical-Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469																•			•						•	
530	Nanoscale Mechanics in an Instrumented Transmission Electron Microscope	34470			•									•				•									•	
638	Terahertz Radiation Technology for MASINT	34471							•											•		•					•	
640	Radar Tag for the Remote Monitoring of Restricted Equipment	34472																			•					•		
643	Evaluation of High-Altitude/Orbit-to-Surface Sensor Delivery System	34473	•																							•		
644	Conceptual Design of Self-Adjusting Inertial Inmate Restraints	34474																			•							•
646	Miniaturized Sensor Technologies for Drug Detection	34475							•							•	•	•			•						•	
649	The Development of Polymer-Based Antitamper Systems	34476				•			•							•										•		
532	LIGA Microsystems Aging: Evaluation and Mitigation	34478																•								•		
651	Network-Enabled Firmware	34484																				•			•		•	
534	Science-Based Processing of Field-Structured Composites	34485				•										•					•						•	
293	Atmospheric Plasma Applications	34487								•																	•	
295	Feasibility Study on Fire-Suppression Properties of the Sandia Decon Foam	34488	•														•			•							•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
297	Feasibility Study for Improved Less-Lethal Weapons	34489																							•		•	
300	Feasibility Study for 5x Enhanced Energetic Materials	34490														•										•		
111	Nanolaser Flowchip for Real-Time Cell and Tumor Biology	34491							•								•	•	•	•		•					•	
733	Self-Assembly of Polymers in Confined Geometries	34692					•						•			•		•					•				•	
735	Building Conscious Machines Based on the Primate Brain	34693	•				•						•									•					•	
302	Ultrahigh-Temperature Ceramic Material Research	34694	•		•	•																					•	
304	Modeling Building Air Flow for Autonomous Robotic Agents	34696					•																			•		
305	Investigation of Advanced Digital-Video Compression for the Control of Robotic Platforms	34697																				•					•	
307	Microfuzer	34698			•		•		•									•	•			•				•		
536	Exploration of New Multivariate Spectral Calibration Algorithms	34699		•	•		•		•	•					•							•	•				•	
51	Nonlinear Modeling and Simulation of Pulsed Electromagnetic Stimulation and Response of Selected Excitable Biological Structures	34713		•			•										•										•	
310	Intelligent Projectile Development	35008	•			•																•					•	
738	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	35376					•		•									•									•	
54	MyLink	35510						•							•		•					•	•				•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Material Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
740	Microcontact Printing of Nanoparticle Arrays	36901			•	•			•	•		•				•	•	•	•	•		•						•
742	Mathematical Analysis of Deception	36902					•						•		•								•		•		•	
743	A System Dynamics Approach to Modeling Water Demand	36904					•																		•			•
652	Indications and Warnings in the Cyber Domain	37690																					•				•	
745	Controlling Contamination in Precision Mirrors by Surface-Capping Modifications	38108							•							•		•									•	
748	Chip-Based Optical-Cell Manipulation	38109		•												•	•	•			•	•					•	
750	Advanced Particle Control for Electric-Discharge Light Sources	38110							•																		•	
752	Wireless Infrastructure Data-Transmission System	38822													•							•			•			•
312	Technology Assessment and Systems Analysis for Hard and Deeply Buried Target Defeat	39016	•						•													•				•		
753	MEMS–Based Electromechanical Acoustic Energy Harvester	39212	•						•													•		•			•	
155	Self-Organizing Network Intelligent Algorithm (SONIA)	39420					•						•		•												•	
653	Cognition-Driven Augmented Analyst	41194					•								•							•	•		•		•	

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

A

- 2,4,6-trinitrotoluene, 223
- μFluid
 - See* Microfluid
- 2-D
 - See* Two-dimensional
- Acceleration, 237
- Accelerator, 669
- Ackermann, M. R.
 - Terahertz Radiation Technology for MASINT, 638
- Acoustic
 - Energy harvester, 754
 - Spectrum analyzer, 582
 - See also:* Biosensor
 - See also:* Sensor
- Actuator
 - Magnetic, 87
 - Electrokinetic pump, 681
- Adams, D. P.
 - Combined Microfabrication Processes, 92
 - Computer-Controlled Micromachines, 83
 - Thin-Film Deposition with *In Situ* Monitoring, 61
 - Three-Dimensional Microstructures, 69
 - Verify Cleaning and Surface Preparation, 66
- Adhesion, 456
- Adhesive (bonding), 94
- Adiabatic, 405
- Adkins, D. R.
 - Adhesive Bonding in Microfabrication, 94
 - Flexural Plate-Wave Devices for Sensors, 165
 - Microfabricated Acoustic Spectrum Analyzer, 582
 - Microsensors for Autonomous Microrobots, 198
- Aging
 - Diagnostics, 467
 - LIGA, 532
 - MEMS, 209
 - Microelectronics, 430
- Alam, T. M.
 - Amorphous Diamond for Microsensors, 168
- Alford, C. R.
 - Dispersive Photonics for Sensors, 213
- Algorithm
 - Aging, 467
 - Commodity-based, 147
 - Cryptography, 270
 - Health monitoring, 281
 - Large-eddy simulation, 121
 - Remote material, 615
 - SONIA, 155
 - Spectral calibration, 536
 - Structural biology, 129
- Allen, J. J.
 - Micro-High-G Acceleration Recorder, 237
- Allerman, A. A.
 - Defining the Frontiers of VECSELS, 178
 - Nanosat, 554
 - Optoelectronic Arrays and Microelectronics, 184
 - Ultra-Efficient Solid-State Lighting, 443
- Allman, R. E.
 - Defining the Frontiers of VECSELS, 178
- Alloy, 464
- Amatucci, B. A.
 - Interactions in Rotating Flowfields, 413
- Anderson, D. R.
 - Very High Temperature Gas-Cooled Reactor, 365
- Anderson, L. F.
 - Flexural Plate-Wave Devices for Sensors, 165
 - Microfabricated Acoustic Spectrum Analyzer, 582
- Anderson, M. U.
 - Shock-Wave Response of PZT 95/5, 483
- Anderson, R. A.
 - Laser-Assisted Microgas Metal Arc Welding, 684
 - Nanoclusters for Supercapacitors, 511
- Anion, 383
- Antitamper, 649
- Antoun, B. R.
 - Mechanisms of Adiabatic Shear Failure, 405
 - Modeling Ductile Fracture, 428
- Apatite, 358
- Apblett, C. A.
 - Engineering Biomicrodevice Interfaces, 627
- Arc
 - Welding, 684
 - See also:* Vacuum-arc
- Arguello, J. G., Jr.
 - Microstructural Modeling of Sintering, 504
- Arlin, J. A.
 - Hybrid Processing in Surety Analysis, 327
- Armendariz, M.
 - Nanosat, 554
- Armour, D. L.
 - Assembly of LIGA Using Electric Fields, 81
 - Nanosat, 554
- Arms, R. M.
 - MyLink, 54
- Armstrong, R. C.
 - Smart Sensors for Joint Test Assembly Flights, 143
- Array
 - Biosensor, 189
 - Mobile sensors, 229
 - Nanoparticle, 740
 - Optoelectronic, 184
 - Patch-clamp, 42
 - Sensor data, 549
 - See also:* Microarray
 - See also:* Nanoarray
- Arsenic, 358

Author and Title Index

- Artau, A.
Molecular Integrated Microsystems, 439
- Ashby, C. I. H.
Amorphous Diamond for Microsensors, 168
Detection of Chem/Bio Warfare Agents, 255
High-Al-Content AlGaInN Devices, 192
MEMS in μ Fluid Channels, 211
Ultra-Efficient Solid-State Lighting, 443
- Asher, R. B.
Building Conscious Machines, 735
Modeling of Pulsed Electromagnetic Stimulation, 51
- Ashley, C. S.
Smart Sand, 223
- Asprey, P. L.
Cognition-Driven Augmented Analyst, 653
- Assembled
See Self-assembles
- Asynchronous Transfer Mode, 353
- ATM
See Asynchronous Transfer Mode
- Atomistic
Crack nucleation, 407
Failure analysis, 139
Phase-field modeling, 458
- Attaway, S. W.
Large-Deformation Solid-Fluid Interaction, 432
- Authenticate
SCADA, 348
Sensor packs, 592
- Automate
Combat course of action, 264
Design, 72
- Autonomous
Microrobots, 198
Robotic agents, 304
Soaring platform, 229
Tracing systems, 391
See also: Autonomous navigation
- Autonomous navigation
Distributed, 287
Obstacle detection, 289
Robust planning, 243
Terrain mapping, 239
- Axline, R. M.
Information Collection, 438
Nanosat, 554
- B**
- Baca, A. G.
High-Al-Content AlGaInN Devices, 192
Semiconductor Switch for Firing Systems, 672
- Baca, W. E.
Quantum Tunneling Transistors, 163
- Bachand, G. D.
MEMS in μ Fluid Channels, 211
Single-Channel Membrane Pores, 103
- Bacon, L. D.
HPM Vulnerability Assessment and Tests, 221
New Mechanism for Upset of Electronics, 283
- Bacteria, 217
- Baer, M. R.
Energetic-Material Burn and Detonation, 416
Simulation of Shock-Induced Combustion, 723
- Baer, T. A.
Large-Deformation Solid-Fluid Interaction, 432
- Baker, A. B.
Modeling of Integrated Nuclear Futures, 363
- Ballistic (chemical sensors), 315
- Bammann, D. J.
Modeling Ductile Fracture, 428
- Bandwidth
Actuator, 87
Interconnects, 612
- Barbour, J. C.
Copper-Corrosion Mechanisms, 460
- Barker, D. L.
Isentropic Compression Experiments, 669
- Barnett, J. L.
Miniaturized Sensor for Drug Detection, 646
- Barriers (apatite), 358
- Bartberger, J. C.
Remote Monitoring of Restricted Equipment, 640
- Bartel, L. C.
Information Collection, 438
- Bartelt, N. C.
Self-Assembled Templates for Nanoarrays, 462
- Bartlett, R. A.
Nonlinear Optimization from PDE Models, 132
- Barton, D. C.
Learning Model for Agent Behavior, 266
Model of Infrastructure Interdependency, 370
- Bartram, M. E.
Self-Assembled Templates for Nanoarrays, 462
- Bastasz, R. J.
Solid-State Ballistic Chemical Sensors, 315
- Bateman, V. I.
Micro-High-G Acceleration Recorder, 237
- Battaile, C. C.
Microminiature Thermionic Converter, 388
Microstructure and Mechanics, 491
Monitoring Corrosion in Weapons, 453
- Battery
All-ceramic, 499
Rechargeable, 356
See also: Microbatteries
- Bauer, K. C.
Intrusion Detection for ATM Networks, 353
- Beacon, 587
- Beam
Focused ion, 92
Intense ion, 655
Proton, 235
- Beard, S. G., Jr.
Orbit-to-Surface Sensor Delivery System, 643
- Beauchamp, E. K.
Glass Technology for Architectural Surety, 575

Author and Title Index

- Beaver, C. L.
 Algorithms for Cryptographic Protocols, 270
 Authenticating Highly Secure SCADA Systems, 348
 High-Surety SCADA, 319
 Information-Sharing Security Research, 360
 Secure Authenticated Sensor Packs, 592
 Security Models of Agent-Based Coalitions, 396
- Beckmann, R. C.
 Transceivers for Microtags to Improve Security, 604
- Beezhold, W.
 Radiation-Induced Prompt Photocurrents, 172
- Behavior (agent), 266
- Behrens, R., Jr.
 Early Detection of Pathogen Exposure, 622
 Interfacial Bioscience Grand Challenge, 447
 Mapping Membrane Protein Interactions, 107
 Microincubators for Rapid Toxin Expression, 562
- Bell, N. S.
 Silicon-Integrated Planar Microbatteries, 201
 Soft-Solution Processes for Growth, 524
- Benavides, G. L.
 Computer-Controlled Micromachines, 83
 Electromicrofluidic Packaging, 85
 Z-Pinch Power-Plant System Development, 661
- Bender, S. F.
 Miniaturized Sensor for Drug Detection, 646
- Bennett, D. J.
 Micro-Total-Analytical Systems, 540
- Bennett, P. C.
 Robotic Manipulation of Hazardous Materials, 226
- Bentley, A. E.
 High-Surety SCADA, 319
- Beresh, S. J.
 Filtered Rayleigh-Scattering Diagnostic, 425
 Interactions in Rotating Flowfields, 413
- Berg, T. M.
 Cognition-Driven Augmented Analyst, 653
 Controlling Information, 551
- Bergstresser, T. K.
 Isentropic Compression Experiments, 669
- Bernstein, A. C.
 Intense White-Light Pulse Propagation in Air, 219
- Bernstein, R.
 Improved Materials-Aging Diagnostics, 467
- Berry, N. M.
 Cognition-Driven Augmented Analyst, 653
 Controlling Information, 551
 Fusion of Sensor Array Data, 549
 MyLink, 54
 Simulator Agents with Episodic Memory, 261
 Smart Sensors for Joint Test Assembly Flights, 143
- Bertram, L. A.
 Laser-Assisted Microgas Metal Arc Welding, 684
- Beyeler, W. E.
 Modeling of Integrated Nuclear Futures, 363
- Bickerstaff, R. J.
 Information Collection, 438
- Biefeld, R. M.
 Characterization of Quantum Dots, 181
 Miniature UV Fluorescence-Based Sensor, 232
 Ultra-Efficient Solid-State Lighting, 443
- Bieg, L. F.
 Computer-Controlled Micromachines, 83
 VDC of Manufacturing Tools, 63
- Bielek, T. P.
 Remote Monitoring Using Video SAR, 595
- Biochemical (warfare), 255
- Biocompatible, 509
- Biological
 Computational, 129
 Harvesting energy, 627
 Macromolecules, 97
 Modeling, 51
 Sensor (compact UV), 578
 Sensor (miniature UV), 232
 Systems, 109
 Tumor, 111
 Warfare, 187
- Bio-MEMS, 509
- Biomicrodevice, 627
- Biomimetic, 728
- Bioscience (IBIG), 447
- Biosensor
 Acoustic-wave, 189
 Lipid bilayers, 100
- Bitsie, F.
 Microdiagnostic MEMS Lab-on-a-Chip, 57
- Blair, D. S.
 Risk-Informed Proliferation Analysis, 568
- Blair-Stahn, N. D.
 Algorithms for Cryptographic Protocols, 270
- Boggs, P. T.
 Computational Prototype of Chemotaxis, 47
 Nonlinear Optimization from PDE Models, 132
- Bolton, W. R., Jr.
 Information Collection, 438
- Boman, E. G.
 Parallel Repartitioning for Performance, 149
- Bonding (Adhesive), 94
- Boney, C. M.
 Informatics for Systems Biology, 109
- Borehole, 394
- Boslough, M. B. E.
 Distributed Mobile Sensor Arrays, 229
 Massively Parallel Global Climate Model, 126
- Boundary (interaction), 486
- Bourdon, C. J.
 Interactions in Rotating Flowfields, 413
- Bow, W. J.
 Remote Monitoring Using Video SAR, 595
- Boyack, K. W.
 Cognition-Driven Augmented Analyst, 653
 Informatics for Systems Biology, 109
- Boyce, B. L.
 Multiaxial Deformation Experiments on Solder, 419

Author and Title Index

- Boye, L. A.
 Improving and Exploiting MTI Imagery, 566
 Information Collection, 438
 Short-Pulse Laser Technologies, 268
- Boyle, T. J.
 All-Ceramic Battery, 499
- Brabson, J. M.
 Data Fusion and Visualization of MASINT, 253
- Bradshaw, R. W.
 Security Issues Based on Limited Freshwater, 35
- Brady, P. V.
 Sorbents for Water Purification, 383
- Braginsky, M. V.
 Microstructural Modeling of Sintering, 504
- Braithwaite, J. W.
 Copper-Corrosion Mechanisms, 460
- Branch, D. W.
 Acoustic-Wave Biosensor Arrays, 189
- Brandt, L. D.
 Real-Time Decision-Support Framework, 546
- Brannon, N. G.
 Cognition-Driven Augmented Analyst, 653
 Knowledge-Based Human Agent Simulation, 589
 Self-Organizing Network Intelligent Algorithm, 155
- Bray, B. K.
 Remote Monitoring Using Video SAR, 595
- Braze, 464
- Breiland, W. G.
 Copper-Corrosion Mechanisms, 460
- Brenkosh, J. P.
 Varying QoS for Fixed and Mobile Networks, 317
- Brennan, J. S.
 Microincubators for Rapid Toxin Expression, 562
- Briggs, R. D.
 Interconnection Technology for Microsystems, 543
- Brinker, C. J.
 Bio-MEMS and Insect Reconnaissance, 509
 Biomimetic Chloroplasts, 728
 Evaporation-Induced Self-Assembly, 715
 Molecular Integrated Microsystems, 439
 Nanostructured Materials in Optical Devices, 497
 Scattering from Nanostructured Materials, 712
 Self-Assembled Nanostructured Materials, 376
 Self-Assembled Templates for Nanoarrays, 462
 Smart Sand, 223
 Smart Self-Assembled Photochromic Films, 450
- Britanik, J. M.
 Fuzzy Data Mining, 248
- Brocato, R. W.
 Transceivers for Microtags to Improve Security, 604
- Brock, B. C.
 Nanosat, 554
- Brockmann, J. E.
 Modeling Building Air Flow, 304
 Real-Time Decision-Support Framework, 546
- Brooks, J. A.
 Diagnostics for Joining Solidification, 480
- Brown, J. R.
 Polymer Spin-Coating for Semiconductors, 516
- Brozik, S. M.
 Acoustic-Wave Biosensor Arrays, 189
 Bio-MEMS and Insect Reconnaissance, 509
 Biosensors Based on Electrical Impedance, 100
 Engineering Biomicrodevice Interfaces, 627
 Interfacial Bioscience Grand Challenge, 447
 Micromachined Patch-Clamp Array, 42
 Molecular Integrated Microsystems, 439
 Nanostructured Materials in Optical Devices, 497
 Water-Quality Monitoring, 385
- Bryan, C. R.
 Self-Assembled Nanostructured Materials, 376
- Buchheit, T. E.
 Mechanics and Tribology of MEMS Materials, 520
 Microstructure and Mechanics, 491
 Multiaxial Deformation Experiments on Solder, 419
- Bukaty, M. E.
 Advanced Unattended Ground Sensors, 258
 Data Fusion and Visualization of MASINT, 253
- Buller, D. L.
 Radiation-Induced Prompt Photocurrents, 172
- Bunde, D. P.
 Commodity-Based Parallel Computing, 147
- Bunker, B. C.
 Aging Mechanisms in Dormant MEMS, 209
 Hydrophobic-Hydrophilic Surfaces, 494
 Molecular Integrated Microsystems, 439
- Burg, M. S.
 Surface-Micromachined Mechanical Timer, 689
- Buried (target), 312
- Burns, A. R.
 Interfacial Bioscience Grand Challenge, 447
 Investigation of Nanoscience Technologies, 703
 Molecular Integrated Microsystems, 439
 Nanostructured Materials in Optical Devices, 497
 Single-Channel Membrane Pores, 103
 Smart Self-Assembled Photochromic Films, 450
- Buss, R. J.
 Nanostructured Silicon for Photovoltaics, 343
- Butler, M. A.
 Flexural Plate-Wave Devices for Sensors, 165
 Microfabricated Acoustic Spectrum Analyzer, 582
- BW
 See Biological (warfare)
- Byrne, R. H.
 Microsensors for Autonomous Microrobots, 198
- ## C
- C de Baca, A. J.
 Model of Infrastructure Interdependency, 370
- Cadden, C. H.
 LIGA Microsystems Aging, 532
- Caffey, T. W. H.
 Ground-Penetrating Radar, 394
- Calibration, 536
- Cameron, S. M.
 Intense White-Light Pulse Propagation in Air, 219
 Short-Pulse Laser Technologies, 268
- Campbell, D. V.
 Range Imaging for Autonomous Navigation, 239

Author and Title Index

- Campbell, J. E.
 Prognostic Health Monitoring, 281
- Campbell, P. L.
 Source Code Assurance Tool, 332
- Campin, M. J.
 Copper-Corrosion Mechanisms, 460
- Capillary, 676
- Carlson, D. C.
 Data Fusion and Visualization of MASINT, 253
- Carlson, J. J.
 Distributed Autonomous Navigation, 287
 Obstacle Detection for Navigation, 289
 Telepresent Rapid-Aiming Platform, 625
 Unobtrusive Human-Computer Interactions, 116
- Carlson, R. E.
 Authenticating Highly Secure SCADA Systems, 348
 High-Surety SCADA, 319
 Vulnerability Assessment of Power Grid, 399
- Carlton, R. J.
 Microexplosive Subsurface Tracing System, 391
- Carr, R. D.
 Computational Structural Biology, 129
- Casalnuovo, S. A.
 Microsensors for Autonomous Microrobots, 198
 Molecular Integrated Microsystems, 439
 Nanosat, 554
 Solid-State Ballistic Chemical Sensors, 315
 Transceivers for Microtags to Improve Security, 604
- Cashen, J. J.
 Detailed Inspection of Weapon Components, 687
- Castro, J. P.
 Multifidelity Modeling of Coupled Systems, 136
- Catalytic, 368
- Cederberg, J. G.
 Characterization of Quantum Dots, 181
- Cell
 Modeling, 47
 Signaling (microscale), 44
 Signaling (protein), 107
 Tumor, 111
 See also: Microfuel Cells
 See also: Optical
- Ceramic
 Battery, 499
 Metal interfaces, 523
 Ultra-high temperature, 302
- Cernosek, R. W.
 Acoustic-Wave Biosensor Arrays, 189
- Cesarano, J., III
 Bio-MEMS and Insect Reconnaissance, 509
- Chambers, R. S.
 Structural Simulations Using Material Models, 402
- Chanchani, R.
 Interconnection Technology for Microsystems, 543
 Microtransceiver for Data Exfiltration, 587
- Channels (μ fluid), 211
- Charge-Compression, 350
- Chavez, J. C.
 Nanosat, 554
- Chemical
 Collection, 602
 Fingerprint, 255
 See also: Sensor
- Chemotaxis, 47
- Chen, J. H.
 Control Strategies for HCCI Engines, 350
- Chinn, D. A.
 Digital Detectors for Neutron Imaging, 580
 Electrochemomechanical Actuation, 488
- Chip
 Lab, 57
 Optical-cell, 748
- Chloroplasts, 728
- Chow, W. W.
 Characterization of Quantum Dots, 181
 Ultra-Efficient Solid-State Lighting, 443
- Christenson, T. R.
 High-Aspect-Ratio Si Bulk Micromachining, 175
 MEMS Microelectric Generator, 341
 Microfabrication of Electromagnetic Devices, 194
 Monolithic Micromachined Variable Tuners, 160
 Nanosat, 554
- Circuit
 Microwave, 160
 RF, 678
 Simulation, 134
- Cleaning, 66
- Clem, P. G.
 Microcontact Printing of Nanoparticle Arrays, 740
 Microfabrication of Electromagnetic Devices, 194
- Climate, 126
- COA
 See Combat Course of Action
- Coating
 MEMS (novel), 695
 MEMS (simulation), 722
 Photonic, 632
 Preconcentrators, 602
 Spin, 516
- Cognition, 653
- Cohen, F. B.
 Mathematical Analysis of Deception, 742
- Collins, M. J.
 Computational Structural Biology, 129
 Network Intrusion Detection, 346
- Coltrin, M. E.
 Ultra-Efficient Solid-State Lighting, 443
- Combat Course of Action, 264
- Combustion
 Microsystems, 335
 Simulation, 723
- Communication (agents), 370
- Composites, 534
 See also: Nanocomposite
- Compression
 Engine, 350
 Isentropic, 669
 Video, 304

Author and Title Index

- Conductors, 665
- Conrad, G. N.
 - Fuzzy Data Mining, 248
- Conrad, S. H.
 - Modeling of Integrated Nuclear Futures, 363
 - Modeling Water Demand, 743
- Conscious (machine), 735
- Containment, 358
- Contaminant
 - Mirrors, 745
 - Volatile, 373
 - See also:* Decontamination
- Continuous-Wave, 394
- Continuum
 - Modeling (crack), 407
 - Modeling (sintering), 504
- Control
 - Contamination, 745
 - Engines, 350
 - Information, 551
 - Materials growth, 462
 - MEMS, 456
 - Micro-GC-based, 338
 - Micromachines, 83
 - Output-based process, 474
 - Particle, 750
 - Robotic platforms, 305
 - Volumetric displacement, 63
- Conversion
 - Energy, 381
 - Small power direct, 609
- Converter, 388
- Cordaro, J. T.
 - Detection of Spread-Spectrum Waveforms, 607
- Cordwell, W. R.
 - Self-Assembled, Tamper-Detection Seals, 564
- Cornelius, C. J.
 - Engineering Biomicrodevice Interfaces, 627
- Corrosion
 - Copper, 460
 - Critical-length scales, 527
 - Weapons, 453
- Countermeasures, 219
- Countersensor, 268
- Coupled
 - Flow, 121
 - Simulations, 134
 - Systems, 136
- Cox, R. G.
 - High-Surety SCADA, 319
 - Model of Infrastructure Interdependency, 370
- Crack, 407
- Craft, D. C.
 - Data Fusion and Visualization of MASINT, 253
- Craft, R. L.
 - MyLink, 54
- Crawford, M. H.
 - High-Al-Content AlGaInN Devices, 192
- Creighton, J. R.
 - Ultra-Efficient Solid-State Lighting, 443
- Crocker, R. W.
 - Direct-Conversion Microfluid Systems, 609
 - Information Collection, 438
- Crozier, P. S.
 - Function of Biological Macromolecules, 97
- Cruz, D.
 - Nanosat, 554
- Cryptography, 270
- Crystal
 - Diamond, 701
 - Liquid, 715
 - Photonic (silicon), 158
 - Photonic (thermophotovoltaic), 381
- Cummings, E. B.
 - Applied Microfluidic Physics, 410
 - Self-Assembled, Tamper-Detection Seals, 564
- Curro, J. G.
 - Hydrophobic-Hydrophilic Surfaces, 494
 - Molecular Self-Assembly, 720
 - Self-Assembly of Polymers, 733
- Curtis, W. C., III
 - Microfuze, 307
- Cyber, 652
- Cygan, R. T.
 - All-Ceramic Battery, 499
- D**
- Daily, M. R.
 - Information Collection, 438
 - Nanosat, 554
- Daniels, J. W.
 - 2-D Hadamard Transform Spectral Imager, 560
- Data
 - Absence, 49
 - Exfiltration, 587
 - Fusion (MASINT), 253
 - Fusion (sensor), 549
 - Intelligent analysis, 474
 - Interconnects, 612
 - Mining, 248
 - Transmission, 752
- Datwyler, S. A.
 - Interfacial Bioscience Grand Challenge, 447
 - Mapping Membrane Protein Interactions, 107
- Dauchy, N. W.
 - Commodity-Based Parallel Computing, 147
- Davidson, G. S.
 - DNA Microarray Technology, 699
- Davis, C. E.
 - Microchemical Sensors for Volatile Contaminants, 373
- Davis, J. P.
 - Isentropic Compression Experiments, 669
- Dawson, D. B.
 - Mechanisms of Adiabatic Shear Failure, 405
- de Boer, M. P.
 - Amorphous Diamond for Microsensors, 168
 - MEMS in μ Fluid Channels, 211
 - Microdiagnostic MEMS Lab-on-a-Chip, 57
 - Novel Coatings for MEM Devices, 695

Author and Title Index

- de Marquis, V. K.
 Nanoclusters for Supercapacitors, 511
- Dec, J. E.
 Control Strategies for HCCI Engines, 350
- Deception, 742
- Decontamination
 Air, 251
 Foam, 295
 Surface, 217
- Deeney, C.
 Isentropic Compression Experiments, 669
- Defeat (target), 312
- Deformation
 Nonlinear, 738
 Solid-fluid, 432
 Solder, 419
- Deland, S. M.
 Fuzzy Data Mining, 248
- Denison, G. J.
 HPM Vulnerability Assessment and Tests, 221
- Dentinger, P. M.
 Self-Assembled, Tamper-Detection Seals, 564
- Deoxyribonucleic acid, 699
- Deployable (optics), 618
- Deposition (thin-film), 61
- Depoy, J. M.
 High-Surety SCADA, 319
- Design
 Practical fixtures, 72
 Restrains, 644
 Robotic, 277
- Desjardin, P. E.
 Large-Eddy Simulation Algorithms, 121
 Simulation of Shock-Induced Combustion, 723
- Detection
 ATM intrusion, 353
 Carbon nanoparticles, 378
 Chemical-fingerprint, 255
 Computer intrusion, 597
 Drug, 646
 Landmine, 223
 Network intrusion, 346
 Neutron imaging, 580
 Obstacle, 289
 Pathogen (molecular markers), 562
 Pathogen (microchemlab), 622
 Seals, 564
 Vibration, 633
 Waveforms, 607
- Detonation, 416
- Devine, K. D.
 Parallel Repartitioning for Performance, 149
- Diagnostic
 Carbon nanoparticles, 378
 Corrosion, 453
 Flowfields, 413
 Joining, 480
 Materials-aging, 467
 Rayleigh-Scattering, 425
 See also: Microdiagnostic
- Diamond
 Microsensors, 168
 Shock response, 701
- Dielectric, 435
- Digital
 Detectors, 580
 Radar, 273
 Video, 305
- Dillinger, J. D.
 Varying QoS for Fixed and Mobile Networks, 317
- Directed-Energy
 Theory, 246
 Threat assessment, 268
 Weapon, 235
- Disease, 585
- Dislocation
 First-principles, 513
 Interaction, 486
- Dispersible
 Smart Sand, 223
 Photonics, 213
- Displacement (VDC), 63
- Disruption, 329
- Distributed
 Microrobotics, 241
 Mobile sensor, 229
 Navigation, 287
- DNA
 See Deoxyribonucleic acid
- Dodd, P. E.
 Radiation-Induced Prompt Photocurrents, 172
- Dohner, J. L.
 Flexural Plate-Wave Devices for Sensors, 165
 Surface-Micromachined Mechanical Timer, 689
- Dohrmann, C. R.
 Nonlinear Structural Mechanics, 145
- Doty, F. P.
 Digital Detectors for Neutron Imaging, 580
- Doughty, D. H.
 Nanosat, 554
- Doyle, B. L.
 Radiation-Induced Prompt Photocurrents, 172
- Draeos, T. J.
 Network Intrusion Detection, 346
 Secure Authenticated Sensor Packs, 592
- Drake, R. R.
 Fault Tolerance in Scientific Simulation, 141
- Driver (photonic), 471
- Dron, S. B.
 Short-Pulse Laser Technologies, 268
- Drotning, W. D.
 Flexible Robotic Maintenance Facility, 285
- Drug (detection), 646
- Drummond, T. J.
 Photonic Lattice Coatings, 632
- Dubbert, D. F.
 Low-Cost Digital Radar, 273
- Duckett, E. B.
 Detailed Inspection of Weapon Components, 687
 Development of a Microoptic Gyroscope, 571

Author and Title Index

- Ductile, 428
- Dudley, P. A.
Low-Cost Digital Radar, 273
- Duggan, D. P.
High-Surety SCADA, 319
Network Intrusion Detection, 346
- Dugger, M. T.
Mechanics and Tribology of MEMS Materials, 520
Self-Healing Molecular Assemblies in MEMS, 456
- Dulleck, G. R., Jr.
Microexplosive Subsurface Tracing System, 391
Micro-GC-Based Controller, 338
- Duncan, J. S.
Indications in the Cyber Domain, 652
- Dunlap, S. K.
Range Imaging for Autonomous Navigation, 239
- Dunphy, D. R.
Bio-MEMS and Insect Reconnaissance, 509
- Dupree, S. A.
Information Collection, 438
- Dyck, C. W.
Computer-Controlled Micromachines, 83
Monolithic Micromachined Variable Tuners, 160
- Dykhuizen, R. C.
Next-Generation Output-Based Process Control, 474
- E**
- Echekki, T.
Control Strategies for HCCI Engines, 350
- Echeverria, V. E., IV
Indications in the Cyber Domain, 652
- Edwards, D. M.
Real-Time Decision-Support Framework, 546
- Eidson, E. D.
Model of Infrastructure Interdependency, 370
- Eisler, G. R.
Autonomous Navigation of Mobile Robots, 243
Distributed Autonomous Navigation, 287
- Elastohydrodynamics, 676
- Elbring, G. J.
Characterization of Underground Facilities, 552
Information Collection, 438
- Eldred, M. S.
Nonlinear Optimization from PDE Models, 132
- Eldridge, J. M.
Varying QoS for Fixed and Mobile Networks, 317
- Electric
Field, 81
Impedance, 100
Power, 348
See also: Dielectric
See also: Microelectronic
See also: Photoelectric
- Electrochemomechanical, 488
- Electrodes, 100
- Electroformed, 75
- Electrokinetic, 681
- Electromagnetic
Microfabrication, 194
Simulation, 51
- Electromechanical, 754
See also: Microelectromechanical
- Electromicrofluidic, 85
- Electron
Emission, 665
Microscope, 530
- Electronic
High-Al-content, 192
Upset, 283
See also: Microelectronic
See also: Optoelectronic
- Elliott, R. D.
Molecular Integrated Microsystems, 439
- Emerson, J. A.
Adhesive Bonding in Microfabrication, 94
Three-Dimensional Microstructures, 69
Ultra-Efficient Solid-State Lighting, 443
Verify Cleaning and Surface Preparation, 66
- Emission (electron), 665
- Energetic
Enhanced materials, 300
Material burn, 416
- Energy
Catalytic systems, 368
Controller, 338
Conversion, 381
Harvesting (biological), 627
Harvesting (MEMS), 754
Infrastructures, 319
Physics, 152
Thermal, 335
See also: Directed-energy
- Engine, 350
- Engler, B. P.
Characterization of Underground Facilities, 552
- Ensz, M. T.
VDC of Manufacturing Tools, 63
- Environment
Dynamic, 243
Near-zero-gravity, 516
Unstructured, 226
Urban, 552
Weapons, 453
- Epitaxy, 707
- Erickson, K. L.
Energetic-Material Burn and Detonation, 416
- Erven, R. J.
Interactions in Rotating Flowfields, 413
- Esherrick, P.
Defining the Frontiers of VECSELS, 178
- Eskridge, S. E.
Microexplosive Subsurface Tracing System, 391
Reconfigurable Homogeneous Microrobotics, 241
Telepresent Rapid-Aiming Platform, 625
- Espinoza, J.
Self-Configurable Network Protocol, 324
Source Code Assurance Tool, 332
Threats to the Social Fabric of the U.S., 37
- Evans, G. H.
Ultra-Efficient Solid-State Lighting, 443

Author and Title Index

- Evans, K. O.
 Single-Channel Membrane Pores, 103
- Evaporation, 715
- Even, W. R., Jr.
 Irreversible and Reversible Getters, 507
 Self-Assembled, Tamper-Detection Seals, 564
- Excitable, 51
- Excited, 165
- Exfiltration, 587
- Explosion, 709
 See also: Microexplosive
- Extraction (information), 674
- F**
- Fabrication
 3-D Microstructures, 69
 Nanoarrays, 462
 Optical devices 497
 See also: Microfabrication
- Factorization, 118
- Failure
 Micromachines, 139
 Shear, 405
- Fang, H. E.
 Multiaxial Deformation Experiments on Solder, 419
- Farnsworth, A. V., Jr.
 Microscale Shock-Wave Physics, 471
- Farrow, R. L.
 Airborne Carbon Nanoparticles, 378
- Fatty-Acid, 187
- Faucett, D. L.
 Advanced Unattended Ground Sensors, 258
 Characterization of Underground Facilities, 552
- Faulon, J. M.
 Interfacial Bioscience Grand Challenge, 447
 Mapping Membrane Protein Interactions, 107
- Fault (tolerance), 141
- Feddema, J. T.
 Assembly of LIGA Using Electric Fields, 81
 Range Imaging for Autonomous Navigation, 239
 Reconfigurable Homogeneous Microrobotics, 241
- Federico, P. J.
 Short-Pulse Laser Technologies, 268
- Feedstock, 368
- Feibelman, P. J.
 Self-Assembled Templates for Nanoarrays, 462
 Water-Surface Interactions, 725
- Figiel, J. J.
 Ultra-Efficient Solid-State Lighting, 443
- Filamentation, 219
- Film (photochromic), 450
 See also: Thin-film
- Filtered (Rayleigh-scattering), 425
- Fingerprint (chemical), 255
- Fintschenko, Y.
 Micro-Total-Analytical Systems, 540
- Fire, 295
- Firing, 672
- Firmware, 651
- Fischer, A. J.
 Characterization of Quantum Dots, 181
 Defining the Frontiers of VECSELs, 178
 High-Al-Content AlGaInN Devices, 192
 Miniature UV Fluorescence-Based Sensor, 232
 Ultra-Efficient Solid-State Lighting, 443
- Fischer, T. A.
 Interconnection Technology for Microsystems, 543
 Microtransceiver for Data Exfiltration, 587
- Fisk, L. A.
 Commodity-Based Parallel Computing, 147
- Fixtures, 72
- Fleming, J. G.
 Advanced Photonics and MEMS, 207
 High-Efficiency Optical MEMS, 203
 Photonic Lattice Coatings, 632
 Silicon Three-Dimensional Photonic Crystal, 158
 Single-Channel Membrane Pores, 103
 Thermophotovoltaic Energy Conversion, 381
- Fleming, R. P.
 Indications in the Cyber Domain, 652
- Flores, R. S.
 Radiation-Induced Prompt Photocurrents, 172
- Floro, J. A.
 Thin-Film Deposition with *In Situ* Monitoring, 61
- Flow
 Air, 304
 Coupled, 121
- Information, 551
- Power, 718
- Flowchip, 111
- Flowfield, 413
- Fluorescence, 232
- Foam, 295
- Foiles, S. M.
 Crack Nucleation and Growth, 402
 Determination of Dislocation Properties, 513
- Ford, D. M.
 Molecular Simulations of MEMS Coatings, 722
- Ford, L. M.
 Miniaturized Sensor for Drug Detection, 646
- Fornaciari, N. R.
 Electric-Discharge Light Sources, 750
- Forsythe, J. C.
 Cognition-Driven Augmented Analyst, 653
 Knowledge-Based Human Agent Simulation, 589
 Simulator Agents with Episodic Memory, 261
- Fracture
 Ductile, 428
 Nonlinear, 738
- Framework, 546
- Friction, 456
- Friedmann, T. A.
 Amorphous Diamond for Microsensors, 168
 Microfabricated Acoustic Spectrum Analyzer, 582
- Frink, L. J. D.
 Function of Biological Macromolecules, 97
- Frischknecht, A. L.
 Molecular Self-Assembly, 720

Author and Title Index

- Fritz, I. J.
 High-Bandwidth Optical Data Interconnects, 612
- Frye-Mason, G. C.
 Micro-GC-Based Controller, 338
 Miniature Sensors for BW Agents, 187
- Fuel
 See Microfuel Cells
- Fuerschbach, P. W.
 Laser-Assisted Microgas Metal Arc Welding, 684
 Metal Vaporization from Laser Irradiation, 518
- Furnish, M. D.
 Isentropic Compression Experiments, 669
- Fusion
 Controlling information, 551
 Data (MASINT), 253
 Data (sensor), 549
- Fuzing, 273
- Fuzzy (data mining), 248
- G**
- Gabbrielli, M.
 Remote Monitoring of Restricted Equipment, 640
- Galambos, P. C.
 Electromicrofluidic Packaging, 85
 Magnetic Polysilicon MEMS Devices, 704
 Micromachined Patch-Clamp Array, 42
 Micro-Total-Analytical Systems, 540
- Gallegos, D. E.
 Advanced Unattended Ground Sensors, 258
- Gallup, D. R.
 Authenticating Highly Secure SCADA Systems, 348
- Ganter, J. H.
 Cognition-Driven Augmented Analyst, 653
- Gaps (spark), 657
- Garcia, E. J.
 GaAs MOEMS Technology, 196
- Garcia, M. L.
 Molecular Integrated Microsystems, 439
- Garcia, R. J.
 MyLink, 54
- Gardner, D. R.
 Multifidelity Modeling of Coupled Systems, 136
- Gardner, M. T.
 Remote Monitoring Using Video SAR, 595
- Gardner, T. J.
 Novel Microcombustor, 335
- Garino, T. J.
 Nanoclusters for Supercapacitors, 511
- Gas
 Cooled, 365
 Modeling, 730
 See also: Microgas
- Gee, J. M.
 Ultra-Efficient Solid-State Lighting, 443
- Geib, K. M.
 Characterization of Quantum Dots, 181
 Defining the Frontiers of VECSELs, 178
 High-Bandwidth Optical Data Interconnects, 612
 Optoelectronic Arrays and Microelectronics, 184
- Gelbard, F.
 Micro-GC-Based Controller, 338
 Real-Time Decision-Support Framework, 546
- Generator, 341
- Gentry, S. M.
 Informatics for Systems Biology, 109
- Geolocation, 573
- Geometry
 Confined, 733
 Simulation, 121
- George, J. T.
 Self-Adjusting Inertial Inmate Restraints, 644
- Getters, 507
- Ghormley, D. P.
 Network-Enabled Firmware, 651
- Gilkey, J. C.
 Levitated Three-Axis Microaccelerometer, 90
- Ginn, W. C.
 Flexural Plate-Wave Devices for Sensors, 165
- Giron, J. W.
 Advanced Unattended Ground Sensors, 258
- Giunta, R. K.
 Adhesive Bonding in Microfabrication, 94
- Givler, R. C.
 Levitated Three-Axis Microaccelerometer, 90
- Gladwell, T. S.
 Robotic Manipulation of Hazardous Materials, 226
- Glass, S. J.
 Glass Technology for Architectural Surety, 575
 Ultrahigh-Temperature Ceramic Materials, 302
- Global
 Climate model, 126
 Geolocation, 573
 Security, 35
- Goeke, R. S.
 Thin-Film Deposition with *In Situ* Monitoring, 61
- Goldsmith, S. Y.
 Agent-Based Mediation, 321
 Security Models of Agent-Based Coalitions, 396
- Gonzales, M.
 MEMS Microelectric Generator, 341
- Gonzales, M. A.
 Multifidelity Modeling of Coupled Systems, 136
- Gonzales, R. A.
 Secure Authenticated Sensor Packs, 592
- Goods, S. H.
 Electrochemomechanical Actuation, 488
- Gordon, S. P.
 Real-Time Decision-Support Framework, 546
- Gottlieb, E. J.
 Automatic Design of Practical Fixtures, 72
 Heterogeneous Simulation, 114
- Gourley, P. L.
 Nanolaser Flowchip for Real-Time Biology, 111
- Graf, D. C.
 Flexural Plate-Wave Devices for Sensors, 165
 Microfabricated Acoustic Spectrum Analyzer, 582
- Granular, 223
- Grasser, T. W.
 Filtered Rayleigh-Scattering Diagnostic, 425

Author and Title Index

- Gray, P. C.
 Air Sterilization and Decontamination, 251
 Intense Directed-Energy Theory Initiative, 246
 Numerical Methods for High-Energy Physics, 152
- Greenwooll, J. I.
 Enhanced Impulse Experimentation, 659
- Greenwood, W. H.
 MEMS Microelectric Generator, 341
- Grest, G. S.
 Self-Healing Molecular Assemblies in MEMS, 456
 Wetting and Spreading Dynamics of Alloys, 464
- Grid (power), 399
- Griffin, P. J.
 Triggered Isomer Research, 275
- Griffith, R. O.
 Modeling Building Air Flow, 304
- Griffiths, S. K.
 Applied Microfluidic Physics, 410
 Irreversible and Reversible Getters, 507
- Gross, K. J.
 Dislocation-Grain Boundary Interaction, 486
 Nanocomposites for Rechargeable Batteries, 356
- Gross, R. J.
 Automatic Design of Practical Fixtures, 72
- Grossetete, G. D.
 GaAs MOEMS Technology, 196
- Grotbeck, C. L.
 Shearing Interferometric Vibration Detector, 633
- Ground
 Sensor (unattended), 258
 Sensor (mobile), 278
 Penetrating, 394
 Vehicle, 277
 See also: Underground
- Growth
 Crack, 407
 Nanoarray, 462
 Nanoscale, 524
 Quantum dot, 181
- Grubelich, M. C.
 Microexplosive Subsurface Tracing System, 391
- Guilinger, T. R.
 Massively Parallel Global Climate Model, 126
- Guillermo, G. M.
 New Mechanism for Upset of Electronics, 283
- Gullett, P. M.
 Failure Analysis of Micromachines, 139
- Gurrieri, T. M.
 Range Imaging for Autonomous Navigation, 239
- Gurule, E. J.
 Nanosat, 554
- Gutierrez, D.
 Electromicrofluidic Packaging, 85
- Gutierrez, W. T.
 Hard and Deeply Buried Target Defeat, 312
- Gyroscope, 571
- H**
- Haaland, D. M.
 2-D Hadamard Transform Spectral Imager, 560
 Analysis of Remote Material Spectra, 615
 Improved Materials-Aging Diagnostics, 467
 Informatics for Systems Biology, 109
 Information Extraction from Satellites, 674
 Multivariate Spectral Calibration Algorithms, 536
 Next-Generation Output-Based Process Control, 474
- Habbitt, R. D., Jr.
 MEMS Microelectric Generator, 341
 Surface-Micromachined Mechanical Timer, 689
- Hachman, J. T., Jr.
 Microreplication from Master Molds, 75
- Hadamard, 560
- Hadi, M. Z.
 Interfacial Bioscience Grand Challenge, 447
- Hadley, G. R.
 Dispersive Photonics for Sensors, 213
- Hafich, M. J.
 Characterization of Quantum Dots, 181
 Dispersive Photonics for Sensors, 213
 Ultra-Efficient Solid-State Lighting, 443
- Hall, A. C.
 Diagnostics for Joining Solidification, 480
- Hamilton, J. C.
 Crack Nucleation and Growth, 407
- Hamilton, V. A.
 Algorithms for Cryptographic Protocols, 270
- Hammerand, D. C.
 Structural Simulations Using Material Models, 402
- Han, J.
 High-Al-Content AlGaInN Devices, 192
 Miniature UV Fluorescence-Based Sensor, 232
 Molecular Integrated Microsystems, 439
- Hance, B. G.
 Smart Sand, 223
- Hargis, P. J., Jr.
 Miniature UV Fluorescence-Based Sensor, 232
- Harper-Slaboszewicz, V.
 Enhanced Impulse Experimentation, 659
- Harrington, J. J.
 Advanced Digital Video Compression, 305
- Harris, A. M.
 Nanosat, 554
- Harris, D. L.
 Modeling of Integrated Nuclear Futures, 363
 Self-Configurable Network Protocol, 324
 Self-Organizing Network Intelligent Algorithm, 155
 Training Software Agents to Reason, 49
- Harris, S. M.
 Microfuze, 307
- Hart, W. E.
 Computational Structural Biology, 129
 Disruption Vulnerability Analysis, 329
- Harvest
 Energy (biological), 627
 Energy (MEMS), 754

Author and Title Index

- Haschke, G. B.
Nanosat, 554
- Hasselbrink, E. F.
MEMS in μ Fluid Channels, 211
Micro-Total-Analytical Systems, 540
Actuator-Based Electrokinetic Pump, 681
- Hauser, G. C.
Air Sterilization and Decontamination, 251
- Hazardous (Robotic), 226
- HCCI
See Homogeneous Charge-Compression Ignition
- Headley, T. J.
Diagnostics for Joining Solidification, 480
- Health, 281
- Heaphy, R.
Parallel Repartitioning for Performance, 149
- Heinstein, M. W.
Nonlinear Structural Mechanics, 145
- Heintzleman, R. E.
Low-Cost Digital Radar, 273
- Heller, E. J.
Microsensors for Autonomous Microrobots, 198
Transceivers for Microtags to Improve Security, 604
- Hembree, C. E.
Radiation Aging of Stockpile Microelectronics, 430
- Hendrickson, B. A.
Parallel Repartitioning for Performance, 149
- Henfling, J. F.
Interactions in Rotating Flowfields, 413
- Hennigan, G. L.
Multifidelity Modeling of Coupled Systems, 136
- Henry, E. A.
Micro-High-G Acceleration Recorder, 237
- Hensinger, D. M.
Reconfigurable Homogeneous Microrobotics, 241
- Henson, T. D.
Deployable Large-Aperture Optics System, 618
- Heroux, M. A.
Incomplete Factorization Preconditioners, 118
Parallel Repartitioning for Performance, 149
- Hewson, J. C.
Control Strategies for HCCI Engines, 350
- Heying, M. R.
Advanced Unattended Ground Sensors, 258
- Hickman, R. J.
Isentropic Compression Experiments, 669
- Hickox, C. E., Jr.
Modeling Building Air Flow, 304
- Hiebert-Dodd, K. L.
Cognition-Driven Augmented Analyst, 653
- Hietala, S.
Monolithic Micromachined Variable Tuners, 160
- Hietala, V. M.
Optoelectronic Arrays and Microelectronics, 184
- Highley, A. M.
Interfacial Bioscience Grand Challenge, 447
- High-Power Microwave, 221
- Hillaire, R. G.
Controlling Information, 551
- Hindman, V. C.
Microtransceiver for Data Exfiltration, 587
- Hirano, H. H.
Cognition-Driven Augmented Analyst, 653
- Hjalmarson, H. P.
Function of Biological Macromolecules, 97
Radiation Aging of Stockpile Microelectronics, 430
- Hobson, W. T.
Orbit-to-Surface Sensor Delivery System, 643
- Hodapp, A. E., Jr.
Intelligent Projectile Development, 310
Orbit-to-Surface Sensor Delivery System, 643
Ultrahigh-Temperature Ceramic Materials, 302
- Hodges, V. C.
Combined Microfabrication Processes, 92
- Hoekstra, R. J.
Parallel Repartitioning for Performance, 149
- Hohlfelder, R. J.
Amorphous Diamond for Microsensors, 168
- Hoke, D. A.
MEMS Microelectric Generator, 341
Micro-High-G Acceleration Recorder, 237
- Hollis, D. D.
Adaptive Computer Intrusion Detection, 597
- Hollowell, J. A.
Remote Monitoring Using Video SAR, 595
- Holm, E. A.
Microstructure and Mechanics, 491
- Holzrichter, M. W.
Characterization of Underground Facilities, 552
- Homogeneous Charge-Compression Ignition, 350
- Hong, J.
Interfacial Bioscience Grand Challenge, 447
Microincubators for Rapid Toxin Expression, 562
- Hopkins, M. M.
Magnetic-Field Effects on Plasmas, 502
- Hosking, F. M.
Computations with Phase-Field Modeling, 458
Wetting and Spreading Dynamics of Alloys, 464
- Houston, J. E.
Crack Nucleation and Growth, 402
Dislocation-Grain Boundary Interaction, 486
- Hoyt, J. J.
Computations with Phase-Field Modeling, 458
- HPM
See High-Power Microwave
- Huber, D. L.
Hydrophobic-Hydrophilic Surfaces, 494
- Hughes, R. C.
Biosensors Based on Electrical Impedance, 100
Interfacial Bioscience Grand Challenge, 447
Microchemical Sensors for Volatile Contaminants, 373
Microsensors for Autonomous Microrobots, 198
Solid-State Ballistic Chemical Sensors, 315
Water-Quality Monitoring, 385
- Human
Computer interactions, 116
Memory, 261
Simulation, 589

Author and Title Index

- Hutchinson, S. A.
Coupling Circuit and Device Simulations, 134
- Hwang, R. Q.
Crack Nucleation and Growth, 407
Self-Assembled Templates for Nanoarrays, 462
Wetting and Spreading Dynamics of Alloys, 464
- Hybrid
Preconditioners, 118
Processing, 327
- Hydrocarbon, 368
- Hydrogen, 716
- Hydrophobic-Hydrophilic, 494
- Hyperspectral
2-D imaging, 467
Satellites, 674
- I**
- IBIG
See Interfacial (Bioscience Grand Challenge)
- IFE
See Inertial (Fusion-Energy)
- Ignition, 350
- Imaging
Digital radar, 273
Dynamic range, 239
Hyperspectral (2-D), 467
Hyperspectral (Satellite), 674
MSTR, 573
MTI, 566
Neutron, 580
Spectral, 560
X-ray, 291
- IMEMS
See Microelectomechanical system
- Immunoassay, 223
- Impedance, 100
- Induced
Combustion, 723
Molecular markers, 562
Photocurrents, 172
Self-assembly, 715
- Inertial
Fusion-Energy, 664
Restrains, 644
- Informatics, 109
- Information
Collection, 438
Controlling, 551
Extraction, 674
Sharing, 360
Subjective, 327
Systems, 321
- Infrastructure
Energy, 319
Interdependency, 370
Surety, 630
Wireless, 752
- Infrared, 560
- Ingersoll, D.
All-Ceramic Battery, 499
Engineering Biomicrodevice Interfaces, 627
Microtransceiver for Data Exfiltration, 587
Nanosat, 554
Nanocomposites for Rechargeable Batteries, 356
Silicon-Integrated Planar Microbatteries, 201
- Ingram, B. A.
Adaptive Computer Intrusion Detection, 597
- Ingram, B. V.
Microexplosive Subsurface Tracing System, 391
- Inmate, 644
- Insect, 509
- Inspection, 687
- Insulated, 718
- Intelligent
Data analysis, 474
Projectile, 310
SONIA, 155
Tracking, 625
- Interconnection
IMEMS, 78
Microsystems, 543
Optical data, 612
- Interfaces, 523
- Interfacial
Traction-separation, 477
Bioscience Grand Challenge, 447
- Interferometric, 633
- Intrusion
ATM, 353
Computer, 597
Network, 346
- Ion beam
Machining, 92
New materials, 655
- IR
See Infrared
- Irradiation, 518
- Irvin, J. A.
Micro-Total-Analytical Systems, 540
- Isentropic, 669
- Isomer, 275
- Itamura, M. T.
Microchemical Sensors for Volatile Contaminants, 373
- J**
- Jacobsen, R. B.
Interfacial Bioscience Grand Challenge, 447
Mapping Membrane Protein Interactions, 107
- James, R. B.
Detailed Inspection of Weapon Components, 687
- Janek, R. P.
Microreplication from Master Molds, 75
- Jansma, R. M.
Indications in the Cyber Domain, 652
- Jarek, R. L.
Novel Catalytic Systems for Separations, 368
- JAVA, 136

Author and Title Index

- Jenkin, C. L.
Fuzzy Data Mining, 248
- Jenkins, M. W.
Microchemical Sensors for Volatile Contaminants, 373
Surface-Micromachined Mechanical Timer, 689
- Jennison, D. R.
Aging Mechanisms in Dormant MEMS, 209
Microminiature Thermionic Converter, 388
Wetting and Spreading Dynamics of Alloys, 464
- Jensen, K. M.
Robotic Ground Vehicle Design, 277
- Johnson, D. J.
Electron Emission from Conductors, 665
Nanosat, 554
- Johnson, M. M.
Enhanced Disease Surveillance, 585
- Johnson, W. A.
Assembly of LIGA Using Electric Fields, 81
- Johnston, A. M.
Computational Structural Biology, 129
- Johnston, J. R.
Commodity-Based Parallel Computing, 147
- Jojola, A. A.
MEMS Microelectric Generator, 341
- Jokiel, B., Jr.
Computer Controlled Micromachines, 83
VDC of Manufacturing Tools, 63
- Jones, D. A.
Disruption Vulnerability Analysis, 329
- Jones, E. D.
Characterization of Quantum Dots, 181
II-V:Boron-Based Semiconductors, 205
Ultra-Efficient Solid-State Lighting, 443
- Jones, J. F., II
Knowledge-Based Human Agent Simulation, 589
- Jones, L. A.
Mesoscale Linear Magnetic Actuators, 87
- Jones, S. T.
Network-Enabled Firmware, 651
- Jordan, S. E.
Cognition-Driven Augmented Analyst, 653
- Jorgenson, R. E.
Dielectric Photoelectric Effect, 435
- Jungst, R. G.
MEMS Microelectric Generator, 341
- K**
- Kamat, S. S.
Glass Technology for Architectural Surety, 575
- Kanouff, M. P.
Electric-Discharge Light Sources, 750
- Kataoka, D. E.
Enhanced Disease Surveillance, 585
- Kearney, S. P.
Filtered Rayleigh-Scattering Diagnostic, 425
- Keenan, M. R.
Analysis of Remote Material Spectra, 615
- Keese, D. L.
Information Collection, 438
- Keiter, E. R.
Coupling Circuit and Device Simulations, 134
- Kelley, J. B.
Prognostic Health Monitoring, 281
- Kelley, M. J.
Microchemical Sensors for Volatile Contaminants, 373
- Kellogg, B. R.
Intrusion Detection for ATM Networks, 353
- Kellogg, G. L.
Wetting and Spreading Dynamics of Alloys, 464
- Kelly, J. J.
Microreplication from Master Molds, 75
- Kemme, S. A.
Molecular Integrated Microsystems, 439
Nanostructured Materials in Optical Devices, 497
Nanostructured Silicon for Photovoltaics, 343
Smart Self-Assembled Photochromic Films, 450
Ultra-Efficient Solid-State Lighting, 443
- Kennedy, C. A.
Control Strategies for HCCI Engines, 350
- Kennicott, L. A.
Fuzzy Data Mining, 248
- Kent, M. S.
Adhesive Bonding in Microfabrication, 94
Hydrophobic-Hydrophilic Surfaces, 494
Interfacial Traction-Separation Models, 477
- Kernan, D. A.
Indications in the Cyber Domain, 652
- Kerstein, A. R.
Control Strategies for HCCI Engines, 350
Large-Eddy Simulation Algorithms, 121
- Key, S. W.
Structural Simulations Using Material Models, 402
- Khandaker, N. R.
Sorbents for Water Purification, 383
- Kidd, M. C.
High-Surety SCADA, 319
Security Models of Agent-Based Coalitions, 396
- Kim, H. I.
Aging Mechanisms in Dormant MEMS, 209
- Kim, T. J.
Nanosat, 554
- King, D. B.
Microminiature Thermionic Converter, 388
- Kinney, R. D.
Development of a Microoptic Gyroscope, 571
Levitated Three-Axis Microaccelerometer, 90
- Kirby, B. J.
Chip-Based Optical Cell Manipulation, 748
Molecular Integrated Microsystems, 439
- Klarer, P. R.
Robotic Ground Vehicle Design, 277
- Klarkowski, J. R.
Nanosat, 554
- Klein, P. A.
Crack Nucleation and Growth, 407
Modeling Ductile Fracture, 428

Author and Title Index

- Klem, J. F.
 Characterization of Quantum Dots, 181
 GaAs MOEMS Technology, 196
 High-Bandwidth Optical Data Interconnects, 612
 II-V:Boron-Based Semiconductors, 205
- Kliner, D. A. V.
 Compact UV Laser Source for Sensing, 578
- Klody, K. A.
 Surface-Micromachined Mechanical Timer, 689
- Kniskern, M. W.
 Hard and Deeply Buried Target Defeat, 312
 Orbit-to-Surface Sensor Delivery System, 643
- Knowledge-Based, 589
- Knudson, M. D.
 Isentropic Compression Experiments, 669
 Shock Response of Diamond Crystals, 701
- Koch, M. W.
 Data Fusion and Visualization of MASINT, 253
 Enhanced Disease Surveillance, 585
- Koehler, F. W.
 Improved Materials-Aging Diagnostics, 467
- Kohler, S. M.
 Intelligent Projectile Development, 310
- Koleske, D. D.
 Ultra-Efficient Solid-State Lighting, 443
- Kottenstette, R.
 Coating Chemical Preconcentrators,, 602
 Detection of Chem/Bio Warfare Agents, 255
 Micro-GC-Based Controller, 338
 Novel Microcombustor, 335
- Kramer, D. K.
 Photonic Lattice Coatings, 632
- Kravitz, S. H.
 Energetic-Material Burn and Detonation, 416
 Engineering Biomicrodevice Interfaces, 627
 Levitated Three-Axis Microaccelerometer, 90
 Microexplosive Subsurface Tracing System, 391
 Nanosat, 554
 Silicon-Integrated Planar Microbatteries, 201
- Krumhansl, J. L.
 Sorbents for Water Purification, 383
- Kruppa, G. H.
 Interfacial Bioscience Grand Challenge, 447
 Microincubators for Rapid Toxin Expression, 562
- Kuehl, M. A.
 Small-Scale High-Performance Optics, 635
- Kunsman, D. M.
 Vulnerability Assessment of Power Grid, 399
- Kuntz, D. W.
 Intelligent Projectile Development, 310
- Kurtz, S. R.
 Characterization of Quantum Dots, 181
 II-V:Boron-Based Semiconductors, 205
 Ultra-Efficient Solid-State Lighting, 443
- Kushmerick, J. G.
 Aging Mechanisms in Dormant MEMS, 209
 Water-Surface Interactions, 725
- L**
 Lab-on-a-Chip, 57
- Ladd, M. D.
 Characterization of Underground Facilities, 552
 Data Fusion and Visualization of MASINT, 253
- Landmine, 223
- Lanes, K. R.
 High-Bandwidth Optical Data Interconnects, 612
- Lantz, J. W.
 Micro-High-G Acceleration Recorder, 237
- Larson, K. W.
 Cognition-Driven Augmented Analyst, 653
- Laser
 Flowchip, 111
 Irradiation, 518
 Short-pulse, 268
 Spark gaps, 657
 UV, 578
 VCSEL, 178
 Welding, 684
- Lattice
 Photonic (coatings), 632
 Photonic (MEMS), 203
- Lau, M. K.
 Nanosat, 554
- LaVan, D. A.
 Amorphous Diamond for Microsensors, 168
- Lead zirconate titanate, 483
- Lean, J. J.
 GaAs MOEMS Technology, 196
- Lee, C. E.
 Self-Assembled, Tamper-Detection Seals, 564
- Lee, R. M.
 Actuator-Based Electrokinetic Pump, 681
- Lee, S. R.
 High-Al-Content AlGaInN Devices, 192
- Leger, C. L.
 Small-Scale High-Performance Optics, 635
- Lemke, P. A.
 Verify Cleaning and Surface Preparation, 66
- Leslie, S. J.
 Microtransceiver for Data Exfiltration, 587
- Leung, K.
 II-V:Boron-Based Semiconductors, 205
- Leung, V. J.
 Commodity-Based Parallel Computing, 147
- Levitated, 90
- Lewis, C. L.
 Autonomous Navigation of Mobile Robots, 243
 Distributed Autonomous Navigation, 287
- Lewis, P. R.
 Miniature Sensors for BW Agents, 187
 Water-Quality Monitoring, 385
- LIGA
 Electric fields, 81
 Microsystems, 532
- Light
 Sources, 750
 White, 219

Author and Title Index

- Lighting, 443
- Lilly, M. P.
Quantum Tunneling Transistors, 163
- Lim, T. J.
Multiaxial Deformation Experiments on Solder, 419
- Lin, S. Y.
Advanced Photonics and MEMS, 207
Dispersive Photonics for Sensors, 213
High-Efficiency Optical MEMS, 203
Microcontact Printing of Nanoparticle Arrays, 740
Photonic Lattice Coatings, 632
Silicon Three-Dimensional Photonic Crystal, 158
Thermophotovoltaic Energy Conversion, 381
- Lindner, D. L.
Highly Parallel Microseparations, 692
- Ling, W. H.
Hard and Deeply Buried Target Defeat, 312
- Link (analysis), 599
See also: MyLink
- Link, H. E.
Agent-Based Mediation, 321
Security Models of Agent-Based Coalitions, 396
- Lipid, 100
- Lipinski, R. J.
Very High Temperature Gas-Cooled Reactor, 365
- Liquid-Crystal, 715
- List, G. F.
Disruption Vulnerability Analysis, 329
- Lithography, 69
- Lockhart, R. R.
Micro-High-G Acceleration Recorder, 237
- Loehman, R. E.
Ultrahigh-Temperature Ceramic Materials, 302
- Logistical (fuels), 609
- Long, K. R.
Nonlinear Optimization from PDE Models, 132
- Loubriel, G. M.
Low-Intensity Laser Triggering of Spark Gaps, 657
Semiconductor Switch for Firing Systems, 672
- Loucks, C. S.
Flexible Robotic Maintenance Facility, 285
- Loy, D. A.
Engineering Biomicrodevice Interfaces, 627
Micro-GC-Based Controller, 338
- Lu, W. Y.
Multiaxial Deformation Experiments on Solder, 419
- Lucero, D. A.
Microchemical Sensors for Volatile Contaminants, 373
- Lucero, F. L.
Polymer-Based Antitamper Systems, 649
- Lucero, J. P.
Flexural Plate-Wave Devices for Sensors, 165
Microfabricated Acoustic Spectrum Analyzer, 582
- Luck, J. P.
Unobtrusive Human-Computer Interactions, 116
- Luk, T. S.
Coherent Multikilovolt X-Ray Sources, 291
Intense White-Light Pulse Propagation in Air, 219
- Lukens, L. L.
Surface-Micromachined Mechanical Timer, 689
- Lundgren, R. G.
Micro-High-G Acceleration Recorder, 237
- Lutz, A. E.
Vulnerability Assessment of Power Grid, 399
- Lyo, S. K.
Characterization of Quantum Dots, 181
Quantum Tunneling Transistors, 163
Silicon Three-Dimensional Photonic Crystal, 158
- ## M
- Machining (Ion beam), 92
See also: Micromachined
- Macromolecules, 97
- Magnetic
Actuators, 87
Insulation, 718
MEMS, 704
Plasmas, 502
Plate-wave devices, 165
See also: Electromagnetic
- Maish, A. B.
Adaptive and Mobile Ground Sensors, 278
- Malczynski, L. A.
Modeling of Integrated Nuclear Futures, 363
- Malinowski, M. E.
Controlling Contamination in Precision Mirrors, 745
- Manginell, R. P.
Hydrophobic-Hydrophilic Surfaces, 494
Micro-GC-Based Controller, 338
Miniature Sensors for BW Agents, 187
Molecular Integrated Microsystems, 439
Novel Microcombustor, 335
- Mani, S. S.
High-Efficiency Optical MEMS, 203
Surface-Micromachined Mechanical Timer, 689
- Manipulation
Optical-cell, 748
Robotic, 226
- Mann, G. A.
Intense Ion Beams for Surface Modification, 655
Modeling of Integrated Nuclear Futures, 363
- Manufacturing
Process, 676
Tools, 63
- Mapping
Membrane protein, 107
Terrain, 239
- Mar, A.
Semiconductor Switch for Firing Systems, 672
- Margolis, S. B.
Novel Microcombustor, 335
- Markers (pathogen), 562
- Marron, L. C.
Distributed Mobile Sensor Arrays, 229
- Marsh, E. W.
Isentropic Compression Experiments, 669
- Marshall, A. C.
Very High Temperature Gas-Cooled Reactor, 365

Author and Title Index

- Martin, J. E.
Nanoclusters for Supercapacitors, 511
- Martin, J. W.
Deployable Large-Aperture Optics System, 618
- Martin, L. E.
Multivariate Spectral Calibration Algorithms, 536
- Martin, M. G.
Failure Analysis of Micromachines, 139
Function of Biological Macromolecules, 97
Protein Structure Generation, 105
- Martinez, A.
Detection of Spread-Spectrum Waveforms, 607
- Martinez, M. A.
Telepresent Rapid-Aiming Platform, 625
- Martinez, R. J.
Photonic Lattice Coatings, 632
- Marx, K. D.
Smart Sensors for Joint Test Assembly Flights, 143
- MASINT
Radiation technology, 638
Underground facility, 253
- Mason, J.
Isentropic Compression Experiments, 669
- Mason, J. J.
Detection of Spread-Spectrum Waveforms, 607
- Mason, S. D.
Control Strategies for HCCI Engines, 350
- Masters, N. D.
Microdiagnostic MEMS Lab-on-a-Chip, 57
- Matalucci, R. V.
Embedded Self-Powered Microsensors, 630
Vulnerability Assessment of Power Grid, 399
Wireless Infrastructure Data-Transmission, 752
- Matzke, C. M.
Hydrophobic-Hydrophilic Surfaces, 494
MEMS in μ Fluid Channels, 211
Molecular Integrated Microsystems, 439
- Mayer, T. M.
Aging Mechanisms in Dormant MEMS, 209
Combined Microfabrication Processes, 92
- Mazarakis, M. G.
Intense Directed-Energy Theory Initiative, 246
Proton Beam Directed-Energy Weapon, 235
Triggered Isomer Research, 275
- McCarty, K. F.
Dynamics of Metal/Ceramic Interfaces, 523
- McCoy, R. F., Jr.
Miniature UV Fluorescence-Based Sensor, 232
- McDaniel, A. H.
Solid-State Ballistic Chemical Sensors, 315
- McDaniel, D. H.
Electron Emission from Conductors, 665
- McDonald, M. J.
Robotic Manipulation of Hazardous Materials, 226
- McElhanon, J. R.
Electrochemomechanical Actuation, 488
- McFadden, S. X.
Modeling Ductile Fracture, 428
- McGrath, L. K.
Microchemical Sensors for Volatile Contaminants, 373
- McKenna, S. A.
Enhanced Disease Surveillance, 585
- McKenney, J. L.
Electron Emission from Conductors, 665
- McLain, A. A.
Microchemical Sensors for Volatile Contaminants, 373
- Means, S. A.
Computational Prototype of Chemotaxis, 47
- Mechanical (timer), 689
See also: Electromechanical
- Mechanics
MEMS, 520
Microstructure, 491
Nanoscale, 530
Structural, 145
- Mecholsky, J. J., Jr.
Ultrahigh-Temperature Ceramic Materials, 302
- Medforth, C. J.
Biomimetic Chloroplasts, 728
- Mediation, 321
- Medlin, D. L.
Dislocation-Grain Boundary Interaction, 486
Nanoscale Mechanics in an Electron Microscope, 530
- Melgaard, D. K.
Improved Materials-Aging Diagnostics, 467
Multivariate Spectral Calibration Algorithms, 536
- Melius, C. F.
Fusion of Sensor Array Data, 549
- Melof, B. M.
Microexplosive Subsurface Tracing System, 391
- Membrane
Pores, 103
Protein, 107
- Memory, 261
- MEMS
See Microelectromechanical systems
- Mendenhall, F. T.
Information Collection, 438
- Meyer, G. D.
Acoustic-Wave Biosensor Arrays, 189
- Michael, J. R.
Diagnostics for Joining Solidification, 480
Mechanics and Tribology of MEMS Materials, 520
- Michalske, T. A.
Single-Channel Membrane Pores, 103
- Michalski, J. T.
Varying QoS for Fixed and Mobile Networks, 317
- Michelsen, H. A.
Airborne Carbon Nanoparticles, 378
- Microaccelerometer, 90
- Microarray, 699
- Microbatteries, 201
- Microchemical (Sensors), 373
- MicroChemLab, 622
- Microcombustor, 335
- Microcontact, 740
- Microdiagnostic, 57
- Microelectroanalytical, 527

Author and Title Index

Microelectromechanical systems

- μfluid, 211
- Aging, 209
- Biocompatible, 509
- Coatings (novel), 695
- Coatings (simulation), 722
- Energy harvester, 754
- Friction, 456
- Generator, 341
- Lab-on-a-chip, 57
- Magnetic, 704
- Mechanics, 520
- Micromachining, 175
- Optical, 203
- Packaging, 78
- Photonics, 207

Microelectronic

- Aging, 430
- Generator, 341
- Optoelectronic, 184
- Photocurrents, 172

Microexplosive, 391**Microfabrication**

- Acoustic analyzer, 582
- Adhesive bonding, 94
- Electromagnetic, 194
- Processes, 92

Microfluid

- MEMS, 211
- Physics, 410
- Small power, 609
- See also:* Electromicrofluidic

Microfuel Cells

- Harvesting energy, 627
- Steam reformer, 716

Microfuze, 307**Microgas, 684****Microincubators, 562****Microlab, 460****Micromachined**

- MEMS, 175
- Patch-clamp, 42
- Timer, 689
- Tuners, 160

Micromethanol, 716**Microoptic, 571****Microoptoelectromechanical systems, 196****Micropump**

- Actuation, 488
- Sensor, 165

Microreplication, 75**Microrobotic**

- Distributed, 241
- Microsensor, 198

Microsensor

- Diamond, 168
- Microrobot, 198
- Self-powered, 630

Microseparation, 692**Microstructure**

- Diamond, 168
- Mechanics, 491
- PZT 95/5, 483
- Simulation, 480
- Sintering, 504

Microsystem

- Aging, 532
- Interconnection, 543
- Microcombustor, 335
- Photochromic films, 450
- Photonics, 213
- See also:* Microelectromechanical systems
- See also:* Molecular (integrated microsystems)

Microtag, 604**Microtransceiver, 587****Microvalve, 488****Microwave, 160****Miller, A. K.**

- Information Collection, 438

Miller, J. E.

- Security Issues Based on Limited Freshwater, 35

Miller, L. M.

- Algorithms for Cryptographic Protocols, 270

Miller, P. A.

- Magnetic-Field Effects on Plasmas, 502

Miller, R. D.

- Secure Authenticated Sensor Packs, 592

Mills, B. E.

- Remote Monitoring Using Video SAR, 595
- Radiation Aging of Stockpile Microelectronics, 430

MIMS, 439**Minier, L. M. G.**

- Enhanced Energetic Materials, 300

Mining (data), 248**Mirror, 745****Missert, N. A.**

- Copper-Corrosion Mechanisms, 460
- Monitoring Corrosion in Weapons, 453
- Self-Assembled Templates for Nanoarrays, 462

Mitchell, C. C.

- High-Al-Content AlGaInN Devices, 192
- Ultra-Efficient Solid-State Lighting, 443

Mitchell, M. A.

- Flexural Plate-Wave Devices for Sensors, 165
- Microfabricated Acoustic Spectrum Analyzer, 582

Mize, G. A.

- Isentropic Compression Experiments, 669

Mobile

- Network, 317
- Sensor (ground), 278
- Sensor (platform), 229
- Robot, 243

Modeling

- Agent behavior, 266
- Air flow, 304
- Biological structures, 51
- Climate, 126
- Coupled systems, 136
- Crack, 407

Author and Title Index

- Data fusion, 549
- Disease surveillance, 585
- Gas, 730
- Infrastructure, 370
- Material, 402
- Nuclear futures, 363
- PDE, 132
- Phase-field, 428
- Process control, 474
- Security, 396
- Sintering, 504
- Solder, 419
- Thermofluid systems, 422
- Traction-separation, 477
- Water demand, 743
- Whole-cell, 47
- See also: Simulation*
- Modine, N. A.
 - II-V-Boron-Based Semiconductors, 205
- MOEMS
 - See Microoptoelectromechanical systems*
- Moffat, H. K.
 - Ultra-Efficient Solid-State Lighting, 443
- Molds, 75
- Molecular
 - Integrated Microsystems, 439
 - Markers, 562
 - Pores, 103
 - Self-assembly, 720
 - Self-healing, 456
 - Simulation (coating), 722
 - Simulation (gas), 730
 - Simulation (reacting systems), 124
- Molina, L. L.
 - New Mechanism for Upset of Electronics, 283
- Monitoring
 - Contaminates, 373
 - Corrosion, 453
 - Equipment, 640
 - Health, 281
 - Surety, 630
 - Targets, 595
 - Thin-film, 61
 - Water, 385
- Montague, S.
 - High-Aspect-Ratio Si Bulk Micromachining, 175
 - Micro-Total-Analytical Systems, 540
- Moody, N. R.
 - Interfacial Traction-Separation Models, 477
 - Nonlinear Deformation and Fracture, 738
 - Thin-Film Deposition with *In Situ* Monitoring, 61
 - Verify Cleaning and Surface Preparation, 66
- Moore, R. C.
 - Use of Apatite for *In Situ* Barriers, 358
- Morales, A. M.
 - Actuator-Based Electrokinetic Pump, 681
- Moreno, J. B.
 - Thermophotovoltaic Energy Conversion, 381
- Morgan, C. H.
 - Miniature Sensors for BW Agents, 187
 - Miniaturized Sensor for Drug Detection, 646
- Morrow, C. W., Jr.
 - Risk-Informed Proliferation Analysis, 568
 - Z-Pinch Power-Plant System Development, 661
- Morrow, M. J.
 - Photonic Lattice Coatings, 632
- Morse, W. D.
 - Information Collection, 438
- Mowery, D. L.
 - Novel Microcombustor, 335
- Mowry, C. D.
 - Miniature Sensors for BW Agents, 187
 - Miniaturized Sensor for Drug Detection, 646
- Moy, T. D.
 - Threats to the Social Fabric of the U.S., 37
- Moya, M. M.
 - Analysis of Remote Material Spectra, 615
- MSI
 - See Multispectral (imaging)*
- MSTR
 - See Multispectral (transient radiometry)*
- MTI
 - See Multispectral (thermal imaging)*
- Muguira, M. R.
 - Obstacle Detection for Navigation, 289
- Mulkern, J. H.
 - Nanosat, 554
- Multispectral
 - imaging, 573
 - thermal imaging, 566
 - transient radiometry, 573
- Murata, K. K.
 - Real-Time Decision-Support Framework, 546
- Murphy, M. B.
 - Transceivers for Microtags to Improve Security, 604
- Myers, R. L.
 - Three-Dimensional Microstructures, 69
- MyLink, 54

- N**
- Najm, H. N.
 - Uncertainty Propagation in Thermofluids, 422
- Nanoarray, 462
- Nanoclusters 511
- Nanocomposite, 356
- Nanoengineered, 383
- Nanolaser, 111
- Nanomaterials, 509
- Nanoparticle
 - Arrays, 740
 - Carbon, 378
- Nanosat, 554
- Nanoscience, 703

Author and Title Index

- Nanostructure
 Nuclear-waste management, 376
 Optical devices, 497
 Scattering, 712
 Silicon-based, 732
 Silicon surfaces, 343
- Napolitano, L. M.
 Molecular Integrated Microsystems, 439
- Navigation (autonomous)
 Distributed, 287
 Mobile robots, 243
 Obstacle detection, 289
 Terrain mapping, 239
- Neiser, R. A., Jr.
 Next-Generation Output-Based Process Control, 474
- Nellums, R. O.
 Range Imaging for Autonomous Navigation, 239
- Nelson, C. L.
 Telepresent Rapid-Aiming Platform, 625
- Nelson, T. R.
 Coherent Multikilovolt X-Ray Sources, 291
 Shearing Interferometric Vibration Detector, 633
- Nenoff, T. M.
 Molecular Modeling for Molecular Sieves, 730
 Novel Catalytic Systems for Separations, 368
- Network
 Firmware, 651
 Intrusion (adaptive), 346
 Intrusion (ATM), 353
 Protocol, 324
 QoS, 317
 SONIA, 155
- Neumann, W. D.
 Authenticating Highly Secure SCADA Systems, 348
 Information-Sharing Security Research, 360
- Neural, 346
- Neutron, 580
- Nevers, J. A.
 Nanosat, 554
- Newton, C. S.
 Glass Technology for Architectural Surety, 575
- Nicholson, L. G.
 Knowledge-Based Human Agent Simulation, 589
- Niese, A. D.
 Range Imaging for Autonomous Navigation, 239
- Nilson, R. H.
 Applied Microfluidic Physics, 410
 Irreversible and Reversible Getters, 507
- Noble, D. R.
 Large-Deformation Solid-Fluid Interaction, 432
- Nogan, J. J.
 Microexplosive Subsurface Tracing System, 391
- Nonlinear
 Deformation, 738
 Mechanics, 145
 Modeling, 51
 Optimization, 132
- Norman, K. M.
 Interconnection Technology for Microsystems, 543
- Notz, P. K.
 Large-Deformation Solid-Fluid Interaction, 432
- Nozick, L. K.
 Disruption Vulnerability Analysis, 329
- Nuclear
 Futures, 363
 Waste, 376
- Nucleation, 407
- ## O
- O'Malley, M. W.
 Low-Intensity Laser Triggering of Spark Gaps, 657
 Solid-State Switch for Pulsed Power, 667
- Obstacle
 Detection, 289
 Terrain mapping, 239
- Ogden, A. J.
 Assembly of LIGA Using Electric Fields, 81
- Ohashi, Y.
 Mechanisms of Adiabatic Shear Failure, 405
- Ohlhausen, J. A.
 Mechanics and Tribology of MEMS Materials, 520
- Okandan, M.
 Engineering Biomicrodevice Interfaces, 627
 Magnetic Polysilicon MEMS Devices, 704
 MEMS in μ Fluid Channels, 211
 Micromachined Patch-Clamp Array, 42
 Micro-Total-Analytical Systems, 540
- Oliver, A. D.
 Actuator-Based Electrokinetic Pump, 681
 MEMS Microelectric Generator, 341
 Three-Dimensional Microstructures, 69
- Olson, C. L.
 Recyclable Transmission Line for Z-Pinch IFE, 664
 Z-Pinch Power-Plant System Development, 661
- Olson, R. E.
 Z-Pinch Power-Plant System Development, 661
- Omdahl, G. D.
 Transceivers for Microtags to Improve Security, 604
- Oppel, F. J., III
 Heterogeneous Simulation, 114
 Obstacle Detection for Navigation, 289
- Optical
 Data interconnects, 612
 Filamentation, 219
 Firing system, 672
 Manipulation, 748
 MEMS, 203
 Microfabricated, 497
 Remote sensing, 618
 Small-scale, 635
- Optoelectronic
 AlGaInN, 192
 Boron, 205
 Integration, 184
- Ormesher, R. C.
 Detection of Spread-Spectrum Waveforms, 607
 Information Collection, 438
 Remote Monitoring of Restricted Equipment, 640

Author and Title Index

- Ottesen, C. W.
Microtransceiver for Data Exfiltration, 587
- P**
- Pace, K. K.
Orbit-to-Surface Sensor Delivery System, 643
- Package
Electromicrofluidic, 85
Getters, 507
IMEMS, 78
- Packs, 592
- Padilla, D. D.
Distributed Autonomous Navigation, 287
Obstacle Detection for Navigation, 289
- Paleoclimate, 126
- Palmer, D. W.
Nanosat, 554
- Pancerella, C. M.
Cognition-Driven Augmented Analyst, 653
MyLink, 54
Smart Sensors for Joint Test Assembly Flights, 143
- Paradiso, N. J., Jr.
Advanced Power Plants for Vehicles, 40
- Parker, A. R.
Z-Pinch Power-Plant System Development, 661
- Parker, E. P.
Intense Directed-Energy Theory Initiative, 246
Simulator Agents with Episodic Memory, 261
- Parks, R. C.
Security Models of Agent-Based Coalitions, 396
- Parma, E. J., Jr.
Very High Temperature Gas-Cooled Reactor, 365
- Parmeter, J. E.
Miniaturized Sensor for Drug Detection, 646
- Partial-differential equations, 132
- Pate, R. C.
Modeling of Pulsed Electromagnetic Stimulation, 51
New Mechanism for Upset of Electronics, 283
- Pathogen
Early detection, 622
Markers, 562
- Patrick, R. C.
High-Surety SCADA, 319
- Patterson, P. E.
Modeling of Pulsed Electromagnetic Stimulation, 51
New Mechanism for Upset of Electronics, 283
- PDE
See Partial-differential equations
- Peake, G. M.
Ultra-Efficient Solid-State Lighting, 443
- Pedroncelli, M. L.
Nanosat, 554
- Pepping, R. E.
Awareness Through Accurate Geolocation, 573
- Peter, F. J.
Levitated Three-Axis Microaccelerometer, 90
Micro-High-G Acceleration Recorder, 237
- Peters, D. W.
Dispersive Photonics for Sensors, 213
- Peterson, K. A.
Electromicrofluidic Packaging, 85
IMEMS Packaging, 78
- Pfeifer, K. B.
Embedded Self-Powered Microsensors, 630
MEMS-Based Acoustic Energy Harvester, 754
Wireless Infrastructure Data-Transmission, 752
- Phase-Field, 458
- Phillips, C. A.
Commodity-Based Parallel Computing, 147
Disruption Vulnerability Analysis, 329
- Phillips, L. R.
Agent-Based Mediation, 321
Security Models of Agent-Based Coalitions, 396
- Photochromic, 450
- Photocurrents 172
- Photoelectric, 435
- Photolithographic, 516
- Photonic
Crystal (3-D), 158
Crystal (energy conversion), 381
Dispersive, 213
Driver, 471
Lattice (coating), 632
Lattice (MEMS), 203
MEMS, 207
- Photovoltaic, 343
- Pickard, P. S.
Very High Temperature Gas-Cooled Reactor, 365
- Piekunko, S. F.
Nanosat, 554
- Pizarro, S. A.
Early Detection of Pathogen Exposure, 622
Study of Cell Signaling, 44
- Plasma
Atmospheric, 293
Vacuum-arc, 502
- Plate-Wave, 165
- Platform
Rapid-aiming, 625
Robotic, 305
Sensor, 229
- Plimpton, S. J.
Computational Prototype of Chemotaxis, 47
Computational Structural Biology, 129
Failure Analysis of Micromachines, 139
- Plummer, K. W.
Microtransceiver for Data Exfiltration, 587
Ultraminiaturization of RF Circuitry, 678
- Plut, T. A.
Monolithic Micromachined Variable Tuners, 160
- Pollock, G. M.
Self-Organizing Network Intelligent Algorithm, 155
- Polosky, M. A.
GaAs MOEMS Technology, 196
High-Aspect-Ratio Si Bulk Micromachining, 175
High-Efficiency Optical MEMS, 203
Surface-Micromachined Mechanical Timer, 689

Author and Title Index

- Polymer
 - Antitamper systems, 649
 - Self-assembly, 733
 - Spin coating, 516
- Polysilicon, 704
- Pores, 103
- Potable, 358
- Poteet, H. M.
 - Information Collection, 438
- Potter, B. G., Jr.
 - Molecular Integrated Microsystems, 439
- Potter, K. S.
 - Molecular Integrated Microsystems, 439
- Power
 - Chloroplasts, 728
 - Flow, 718
 - Grid, 399
 - Industry, 348
 - Microfluid, 609
 - Microsensor, 630
 - Plant, 40
 - Pulsed, 667
 - RF, 217
 - Transceivers, 604
 - Z-pinch, 661
- Prasad, S. V.
 - Mechanics and Tribology of MEMS Materials, 520
- Preconcentrator, 602
- Preconditioners, 118
- Predicting, 97
- Prentice, W. J.
 - Flexible Robotic Maintenance Facility, 285
- Prevender, T. S.
 - Detection of Spread-Spectrum Waveforms, 607
 - Information Collection, 438
- Primate, 735
- Probability, 723
- Production, 329
- Projectile, 310
- Proliferation, 568
- Propagation
 - Pulse, 219
 - Uncertainty, 422
- Protein
 - Membrane, 107
 - Structure, 105
 - Toxin, 217
- Proton, 235
- Prototype
 - Chemotaxis, 47
 - Microwave, circuits, 160
 - Radar, 394
- Provencio, P. P.
 - Intense Ion Beams for Surface Modification, 655
- Pryor, R. J.
 - Distributed Mobile Sensor Arrays, 229
 - Learning Model for Agent Behavior, 266
 - Model of Infrastructure Interdependency, 370
- Prypudniewicz, E. J.
 - Microdiagnostic MEMS Lab-on-a-Chip, 57
- Pseudostationary, 692
- Pulse
 - Electromagnetic, 51
 - Laser, 268
 - Power, 667
 - White-light, 219
- Pump, 681
 - See also:* Micropump
- Purification (water), 383
- PZT
 - See* Lead zirconate titanate, 483
- Q**
- QoS
 - See* Quality of service
- Quality of service, 317
- Quantum
 - Dot, 181
 - Transistor, 163
- R**
- Raber, T. N.
 - Direct-Conversion Microfluid Systems, 609
- Rackley, N. G.
 - 2-D Hadamard Transform Spectral Imager, 560
 - All-Ceramic Battery, 499
 - Polymer-Based Antitamper Systems, 649
- Radar
 - Digital, 273
 - Ground-penetrating, 394
 - Tag, 640
- Radiation
 - Aging, 430
 - MASINT, 638
 - Photocurrent, 172
 - See also:* Irradiation
- Radio-frequency
 - Circuitry, 678
 - Decontamination, 217
- Radiography, 687
- Radiometry, 573
- Radionuclide, 358
- Rahimian, K.
 - All-Ceramic Battery, 499
 - Polymer-Based Antitamper Systems, 649
- Rao, R. R.
 - Incomplete Factorization Preconditioners, 118
- Ratzel, A. C.
 - Sb as a Surfactant in Epitaxy of III–V Materials, 707
- Rawlings, J. A.
 - Nanosat, 554
- Raybourn, E. M.
 - Training Software Agents to Reason, 49
- Rayleigh-Scattering, 425
- Reactor, 365

Author and Title Index

- Reagan, M. T.
 Uncertainty Propagation in Thermofluids, 422
- Real-Time
 Decision, 546
 Flowchip, 111
 Monitoring, 595
- Reber, C. A.
 Electromicrofluidic Packaging, 85
 IMEMS Packaging, 78
 Nanosat, 554
- Rechargeable, 356
- Reckase, E. N.
 Awareness Through Accurate Geolocation, 573
- Reconfigurable, 241
- Reconnaissance, 509
- Recorder, 237
- Recyclable, 664
- Redmond, J. M.
 Deployable Large-Aperture Optics System, 618
- Reedy, E. D., Jr.
 Interfacial Traction-Separation Models, 477
 Verify Cleaning and Surface Preparation, 66
- Reeves, P. C.
 Cognition-Driven Augmented Analyst, 653
- Reformer, 716
- Regueiro, R. A.
 Mechanisms of Adiabatic Shear Failure, 405
- Remote
 Material spectra, 615
 See also: Monitoring
 See also: Sensor
- Removal (arsenic), 358
- Renk, T. J.
 Atmospheric Plasma Applications, 293
 Intense Ion Beams for Surface Modification, 655
 Proton Beam Directed-Energy Weapon, 235
- Renlund, A. M.
 Energetic-Material Burn and Detonation, 416
- Renn, R. A.
 Surface-Micromachined Mechanical Timer, 689
- Reno, J. L.
 GaAs MOEMS Technology, 196
 Quantum Tunneling Transistors, 163
- Repartitioning, 149
- Restrains, 644
- Restricted (equipment), 640
- Retter, M. J.
 Microfuze, 307
- Reversible (getters), 507
- Rexroth, P. E.
 Risk-Informed Proliferation Analysis, 568
- RF
 See Radio-frequency
- Rhodes, D. E.
 MyLink, 54
 Smart Sensors for Joint Test Assembly Flights, 143
- Rhykerd, C. L., Jr.
 Coating Chemical Preconcentrators, 602
- Rice, S. F.
 Direct-Conversion Microfluid Systems, 609
- Rich, S. G.
 Nanosat, 554
- Rieger, D. J.
 Interconnection Technology for Microsystems, 543
- Rienstra, J. L.
 High-Bandwidth Optical Data Interconnects, 612
 Informatics for Systems Biology, 109
- Riesen, R. E.
 Commodity-Based Parallel Computing, 147
- Rightley, M. J.
 Nanosat, 554
- Rintoul, M. D.
 Computational Prototype of Chemotaxis, 47
 Interfacial Bioscience Grand Challenge, 447
 Protein Structure Generation, 105
- Risk-Informed, 568
- Robinett, R. D., III
 Information Collection, 438
- Robino, C. V.
 Diagnostics for Joining Solidification, 480
- Robinson, D. G.
 Vulnerability Assessment of Power Grid, 399
- Robot
 Air flow, 304
 Digial video, 305
 Ground-vehicle, 277
 Hazardous materials, 226
 Maintenance, 285
 Mobile, 243
 See also: Microrobotic
- Rochau, G. A.
 Z-Pinch Power-Plant System Development, 661
- Rochau, G. E.
 Risk-Informed Proliferation Analysis, 568
 Z-Pinch Power-Plant System Development, 661
- Rodacy, P. J.
 Miniaturized Sensor for Drug Detection, 646
 Water-Quality Monitoring, 385
- Rodriguez, M. A.
 All-Ceramic Battery, 499
 Nanocomposites for Rechargeable Batteries, 356
- Roe, D. C.
 Fusion of Sensor Array Data, 549
- Rogers, J. D.
 Hard and Deeply Buried Target Defeat, 312
- Rohde, S. B.
 Microfuze, 307
 Nanosat, 554
- Rohwer, L. E. S.
 Ultra-Efficient Solid-State Lighting, 443
- Romero, J. A.
 Thin-Film Deposition with *In Situ* Monitoring, 61
- Roose, L. D.
 Semiconductor Switch for Firing Systems, 672
- Rose, B. H.
 Transceivers for Microtags to Improve Security, 604
- Rotating (flowfield), 413
- Rubin, R. L.
 Commodity-Based Parallel Computing, 147

Author and Title Index

- Ruby, D. S.
 Nanostructured Silicon for Photovoltaics, 343
- Ruiz, C. L.
 Magnetically Insulated Power Flow, 718
- Russell, J. L.
 Information Collection, 438
- S**
- Sa, T. J.
 Enhanced Disease Surveillance, 585
- Salguero, D. E.
 Hard and Deeply Buried Target Defeat, 312
- Salinger, A. G.
 Function of Biological Macromolecules, 97
 Nonlinear Optimization from PDE Models, 132
- Samora, S.
 Interconnection Technology for Microsystems, 543
- Sanchez, L. C.
 Triggered Isomer Research, 275
- Sandoval, C. E.
 Nanosat, 554
 Ultraminiaturization of RF Circuitry, 678
- Sarfaty, R. A.
 High-Surety SCADA, 319
- Sasaki, D. Y.
 Acoustic-Wave Biosensor Arrays, 189
 Bio-MEMS and Insect Reconnaissance, 509
 Biosensors Based on Electrical Impedance, 100
 Interfacial Bioscience Grand Challenge, 447
 MEMS in μ Fluid Channels, 211
 Molecular Integrated Microsystems, 439
 Nanostructured Materials in Optical Devices, 497
 Security Issues Based on Limited Freshwater, 35
 Self-Healing Molecular Assemblies in MEMS, 456
 Single-Channel Membrane Pores, 103
 Smart Self-Assembled Photochromic Films, 450
- Satellite
 Hyperspectral images, 674
 Interconnects, 612
- Saturn (accelerator), 669
- SCADA
 See Supervisory control and data acquisition
- Schauer, A. L.
 Detection of Spread-Spectrum Waveforms, 607
- Schefer, R. W.
 Filtered Rayleigh-Scattering Diagnostic, 425
- Schmale, D. T.
 Microfabrication of Electromagnetic Devices, 194
- Schmid, A. K.
 Crack Nucleation and Growth, 402
 Nanoscale Mechanics in an Electron Microscope, 530
 Self-Assembled Templates for Nanoarrays, 462
- Schmidt, R. C.
 Large-Eddy Simulation Algorithms, 121
- Schmidt, R. L.
 Awareness Through Accurate Geolocation, 573
- Schneider, D. A.
 Engineering Biomicrodevice Interfaces, 627
 Micro-GC-Based Controller, 338
- Schneider, H. C.
 Characterization of Quantum Dots, 181
- Schoeneman, J. L.
 Nanosat, 554
- Schoeniger, J. S.
 Early Detection of Pathogen Exposure, 622
 Interfacial Bioscience Grand Challenge, 447
 Mapping Membrane Protein Interactions, 107
 Microincubators for Rapid Toxin Expression, 562
 Smart Sand, 223
 Study of Cell Signaling, 44
- Schoenwald, D. A.
 Model of Infrastructure Interdependency, 370
 Modeling Building Air Flow, 304
 Simulator Agents with Episodic Memory, 261
- Schroder, K. L.
 Miniature UV Fluorescence-Based Sensor, 232
- Schroepfel, R. C.
 Algorithms for Cryptographic Protocols, 270
 Information-Sharing Security Research, 360
 Secure Authenticated Sensor Packs, 592
- Schubert, W. K.
 Amorphous Diamond for Microsensors, 168
 Flexural Plate-Wave Devices for Sensors, 165
 Microfabricated Acoustic Spectrum Analyzer, 582
 Nanosat, 554
- Schultz, P. A.
 Radiation Aging of Stockpile Microelectronics, 430
- Schunk, P. R.
 Capillary Elastohydrodynamics, 676
 Incomplete Factorization Preconditioners, 118
 Large-Deformation Solid-Fluid Interaction, 432
- Schuster, G. R.
 Nanosat, 554
- Schwank, J. R.
 Radiation Aging of Stockpile Microelectronics, 430
 Radiation-Induced Prompt Photocurrents, 172
- Scott, M. W.
 Information Collection, 438
 Obstacle Detection for Navigation, 289
- Seager, C. H.
 Radiation Aging of Stockpile Microelectronics, 430
 Ultra-Efficient Solid-State Lighting, 443
- Sears, M. P.
 Computational Prototype of Chemotaxis, 47
 Function of Biological Macromolecules, 97
 Protein Structure Generation, 105
- Security
 Freshwater, 35
 Microtag, 604
 Model, 396
 Module, 360
 SCADA, 348
- Self-Adjusting, 644
- Self-Assemble
 Bio-MEMS, 509
 Evaporation, 715
 Molecular, 720

Author and Title Index

- Nanoarray, 462
- Photochromic film, 450
- Polymer, 733
- Seal, 564
- Self-Configurable, 324
- Self-Guided, 219
- Self-Healing, 456
- Self-Organizing Network Intelligent Algorithm, 155
- Self-Powered, 630
- Self-Referencing, 633
- Semiconductor
 - Optoelectronic, 205
 - Photolithographic, 516
 - Switch, 672
- Senglaub, M. E.
 - Automated Combat Course of Action, 264
 - Training Software Agents to Reason, 49
- Sensor
 - Acoustic, 165
 - Array data, 549
 - Chemical (ballistic), 315
 - Delivery, 643
 - Dispersive photonic, 213
 - Drug detection,, 646
 - Ground (mobile), 278
 - Ground (unattended), 258
 - Microchemical, 373
 - Microcombustor, 335
 - Miniature (fatty acid), 187
 - Miniature (UV), 232
 - Mobile, 229
 - Motion, 116
 - Pack, 592
 - Process control, 474
 - Remote, 219
 - Smart, 143
 - Smart Sand, 223
 - UV laser, 578
 - See also:* Biosensor
 - See also:* Countersensor
 - See also:* Microsensor
- Separation
 - Hydrocarbon, 368
 - Traction, 477
 - See also:* Microseparation
- Serkland, D. K.
 - Defining the Frontiers of VECSELs, 178
 - High-Bandwidth Optical Data Interconnects, 612
 - Optoelectronic Arrays and Microelectronics, 184
- Setchell, R. E.
 - Microscale Shock-Wave Physics, 471
 - Shock-Wave Response of PZT 95/5, 483
- Shadid, J. N.
 - Incomplete Factorization Preconditioners, 118
- Shaneyfelt, M. R.
 - Radiation Aging of Stockpile Microelectronics, 430
 - Radiation-Induced Prompt Photocurrents, 172
- Sheaffer, D. A., Jr.
 - Smart Sensors for Joint Test Assembly Flights, 143
- Shear
 - Adiabatic, 405
 - Self-referencing, 633
- Shelnutt, J. A.
 - Biomimetic Chloroplasts, 728
 - Smart Self-Assembled Photochromic Films, 450
- Shen, H. C.
 - Nanosat, 554
- Shepherd, J. F.
 - Computational Prototype of Chemotaxis, 47
- Shepodd, T. J.
 - Detection of Chem/Bio Warfare Agents, 255
 - Irreversible and Reversible Getters, 507
 - Micro-Total-Analytical Systems, 540
 - Molecular Integrated Microsystems, 439
- Shinn, N. D.
 - Wetting and Spreading Dynamics of Alloys, 464
- Shock
 - Combustion, 723
 - Response, 701
 - Wave (Photonic driver), 471
 - Wave (PZT), 483
- Shokair, I. R.
 - Fusion of Sensor Array Data, 549
- Showalter, S. K.
 - Micro-GC-Based Controller, 338
- Shul, R. J.
 - Amorphous Diamond for Microsensors, 168
 - Flexural Plate-Wave Devices for Sensors, 165
 - High-Al-Content AlGaInN Devices, 192
 - High-Aspect-Ratio Si Bulk Micromachining, 175
 - Microfabricated Acoustic Spectrum Analyzer, 582
 - Micromethanol Steam Reformer, 716
 - Nanosat, 554
 - Ultra-Efficient Solid-State Lighting, 443
- Si
 - See* Silicon
- Silicon
 - Crystal, 158
 - Microbattery, 201
 - Microscopy, 732
 - On-insulator, 175
 - Photovoltaic, 343
 - Rechargeable battery, 356
 - See also:* Polysilicon
- Simmons, B. A.
 - Self-Assembled, Tamper-Detection Seals, 564
- Simmons, J. A.
 - Quantum Tunneling Transistors, 163
- Simons, R. W.
 - Data Fusion and Visualization of MASINT, 253
- Simonson, R. J.
 - Bio-MEMS and Insect Reconnaissance, 509
 - Information Collection, 438
 - Terahertz Radiation Technology for MASINT, 638

Author and Title Index

- Simulation
 Biological structures, 51
 Combustion, 723
 Coupling, 134
 Fault tolerance, 141
 Gas, 730
 Heterogeneous, 114
 Human agent, 589
 Large-eddy, 121
 MEMS coating, 722
 Nuclear futures, 363
 Reacting systems, 124
 Solidification, 480
 Structural, 402
 See also: Modeling
- Simulator, 261
- Sinclair, M. B.
 Informatics for Systems Biology, 109
 Microdiagnostic MEMS Lab-on-a-Chip, 57
 Nanostructured Materials in Optical Devices, 497
- Singh, A. K.
 Interfacial Bioscience Grand Challenge, 447
 Molecular Integrated Microsystems, 439
 Smart Sand, 223
- Sintering, 504
- Skocypec, R. D.
 Cognition-Driven Augmented Analyst, 653
- Slepoy, A.
 Interfacial Bioscience Grand Challenge, 447
 Protein Structure Generation, 105
- Sloan, G. R.
 Interconnection Technology for Microsystems, 543
 Ultraminiaturization of RF Circuitry, 678
- Sloan, L. R.
 Monolithic Micromachined Variable Tuners, 160
- Slutz, S. A.
 Recyclable Transmission Line for Z-Pinch IFE, 664
 Z-Pinch Power-Plant System Development, 661
- Small, D. E.
 Small-Scale High-Performance Optics, 635
 Unobtrusive Human-Computer Interactions, 116
- Smart
 Photochromic film, 450
 Sand, 223
 Sensor, 143
- Smartt, H. A.
 Secure Authenticated Sensor Packs, 592
- Smiel, A. J.
 Nanosat, 554
- Smith, A. V.
 Defining the Frontiers of VECSELs, 178
- Smith, D. A.
 2-D Hadamard Transform Spectral Imager, 560
- Smith, J. L.
 Awareness Through Accurate Geolocation, 573
- Smith, N. F.
 Microdiagnostic MEMS Lab-on-a-Chip, 57
- Smith, P. A.
 Semiconductor Switch for Firing Systems, 672
- Smith, T. M.
 Large-Eddy Simulation Algorithms, 121
- Smithpeter, C. L.
 Range Imaging for Autonomous Navigation, 239
- Snell, M. K.
 Knowledge-Based Human Agent Simulation, 589
- Snyder, L. A.
 Information-Sharing Security Research, 360
- Software
 Agent, 49
 Fault tolerance, 141
- SOI
 See Silicon (on-insulator)
- Solder
 Deformation, 419
 Wetting, 464
- Solid-State
 Sensors, 315
 Switch, 667
- Solver, 149
- SONIA
 Self-Organizing Network Intelligent Algorithm
- Sorbents, 383
- Southwell, E. T.
 Molecular Integrated Microsystems, 439
- Space-Based, 430
- Spahn, O. B.
 GaAs MOEMS Technology, 196
- Spark (gaps), 657
- Spectral
 Calibration, 536
 Imager (2-D), 560
 Material analysis, 615
 See also: Hyperspectral
 See also: Multispectral
- Spectrum
 Acoustic, 582
 Transceiver, 604
 Waveforms, 607
- Spencer, D. D.
 Information Collection, 438
- Spencer, F. W.
 Next-Generation Output-Based Process Control, 474
- Spielman, R. B.
 Single-Wire Explosion Experiments, 709
- Spin-Coating, 516
- Spires, S. V.
 Agent-Based Mediation, 321
 Security Models of Agent-Based Coalitions, 396
- Spletzer, B. L.
 Small-Scale High-Performance Optics, 635
- Spooner, J. T.
 Development of a Microoptic Gyroscope, 571
- Spreading (solder), 464
- Springer, C.
 Fusion of Sensor Array Data, 549
- Stabilization (waste), 358

Author and Title Index

- Stalker, K. T.
 Hard and Deeply Buried Target Defeat, 312
 Information Collection, 438
 Microtransceiver for Data Exfiltration, 587
- Stallard, B. R.
 Improving and Exploiting MTI Imagery, 566
- Stamber, K. L.
 Model of Infrastructure Interdependency, 370
- Stamp, J. E.
 High-Surety SCADA, 319
- Steam, 716
- Stephens, J. J., Jr.
 Wetting and Spreading Dynamics of Alloys, 464
- Sterilization, 251
- Stevens, M. J.
 Function of Biological Macromolecules, 97
 Interfacial Bioscience Grand Challenge, 447
 Molecular Simulations of MEMS Coatings, 722
 Self-Healing Molecular Assemblies in MEMS, 456
- Stewart, S. M.
 Shearing Interferometric Vibration Detector, 633
- Stimulation, 51
- Stockpile, 430
- Stone, R. G.
 Glass Technology for Architectural Surety, 575
- Stotts, L. G.
 Information Collection, 438
- Stress-Free (diamond), 168
- Strong, D. S.
 Awareness Through Accurate Geolocation, 573
- Structural
 Biology, 129
 Mechanics, 145
 Simulation, 402
- Structure
 Biological, 51
 MEMS, 209
 Protein, 105
 See also: Infrastructure
 See also: Microstructure
 See also: Nanostructure
- Struve, K. W.
 Electron Emission from Conductors, 665
 Z-Pinch Power-Plant System Development, 661
- Strzyzewski, M.
 Cognition-Driven Augmented Analyst, 653
- Stygar, W. A.
 Electron Emission from Conductors, 665
- Subia, S. R.
 Large-Deformation Solid-Fluid Interaction, 432
- Sullivan, C. T.
 Advanced Photonics and MEMS, 207
 High-Aspect-Ratio Si Bulk Micromachining, 175
- Sullivan, J. P.
 Amorphous Diamond for Microsensors, 168
- Summers, R. M.
 Fault Tolerance in Scientific Simulation, 141
- Supercapacitors, 511
- Supervisory control and data acquisition
 Electric power, 348
 Energy infrastructures, 319
- Surety
 Architectural, 575
 Building (microsensor), 630
 Production, 329
 SCADA (energy infrastructure), 319
 Subjective information, 327
- Surface
 Breakdown, 435
 Capping, 745
 Decontamination, 217
 Ion beams, 655
 MEMS, 203
 Orbit, 643
 Preparation, 66
 Silicon, 343
 Switchable, 494
 Timer, 689
 Water, 725
 See also: Vertical external-cavity surface-emitting laser
- Surfactant, 707
- Surveillance, 585
- Swartzentruber, B. S.
 Microscopy of Silicon-Based Nanostructures, 732
 Single-Channel Membrane Pores, 103
- Sweatt, W. C.
 Informatics for Systems Biology, 109
 Nanosat, 554
 Ultra-Efficient Solid-State Lighting, 443
- Swiler, L. P.
 Prognostic Health Monitoring, 281
- Swiler, T. P.
 Prognostic Health Monitoring, 281
- Switch
 Semiconductor, 672
 Solid-state, 667
- Switchable, 494
- Sylwester, A. P.
 Nanosat, 554
- Synergistic, 573
- Sype, T. T.
 Risk-Informed Proliferation Analysis, 568
- ## T
- Tadros, M. E.
 Modeling of Pulsed Electromagnetic Stimulation, 51
 Security Issues Based on Limited Freshwater, 35
- Tag
 Microtransceiver, 587
 Radar, 640
- Tallant, D. R.
 Soft-Solution Processes for Growth, 524
- Tamper
 Detection, 564
 See also: Antitamper
- Tappan, A. S.
 Energetic-Material Burn and Detonation, 416

Author and Title Index

- Target
 Defeat, 312
 Digital radar, 273
Remote monitoring, 595
Tarman, T. D.
 Intrusion Detection for ATM Networks, 353
 Varying QoS for Fixed and Mobile Networks, 317
Tarver, E. E., III
 Water-Quality Monitoring, 385
Taylor, J. D.
 Direct-Conversion Microfluid Systems, 609
Template, 462
Terahertz, 638
Terrain, 239
Terwilliger, S. F.
 Nanosat, 554
Teter, D. M.
 Sorbents for Water Purification, 383
Thai, T. Q.
 Network-Enabled Firmware, 651
Thermal
 Energy, 335
 Fluids, 425
Thermionic, 388
Thermofluid, 422
Thermophotovoltaic, 381
Thin-Film
 Deposition, 61
 Microfabrication, 92
Thomas, E. V.
 Analysis of Remote Material Spectra, 615
 Improved Materials-Aging Diagnostics, 467
 Network Intrusion Detection, 346
 Next-Generation Output-Based Process Control, 474
 Simulator Agents with Episodic Memory, 261
Thomas, G. A.
 Information Collection, 438
Thomas, M. L.
 Microchemical Sensors for Volatile Contaminants, 373
Thompson, A. P.
 Molecular Integrated Microsystems, 439
 Molecular Simulation of Reacting Systems, 124
Thompson, D. G.
 Remote Monitoring Using Video SAR, 595
Thornberg, S. M.
 Novel Catalytic Systems for Separations, 368
 Polymer Spin-Coating for Semiconductors, 516
Thorne, L. R.
 Information Collection, 438
Threat
 Assessment, 268
 Social fabric, 37
Three-Dimensional
 Microstructure, 69
 Photonic crystal, 158
Throckmorton, D. J.
 Molecular Integrated Microsystems, 439
Tidwell, V. C.
 Modeling Water Demand, 743
Tigges, C. P.
 GaAs MOEMS Technology, 196
 High-Aspect-Ratio Si Bulk Micromachining, 175
 Microfabrication of Electromagnetic Devices, 194
 Monolithic Micromachined Variable Tuners, 160
Tikare, V.
 Computations with Phase-Field Modeling, 458
 Microstructural Modeling of Sintering, 504
Timer, 689
Timlin, J. A.
 Improved Materials-Aging Diagnostics, 467
 Informatics for Systems Biology, 109
 Information Extraction from Satellites, 674
TNT
 See 2,4,6-trinitrotoluene
Torgerson, M. D.
 Authenticating Highly Secure SCADA Systems, 348
 Self-Configurable Network Protocol, 324
Torres, J. J.
 High-Surety SCADA, 319
Toth, R. P.
 Air Sterilization and Decontamination, 251
 Decontamination of Bacterial Toxins, 217
 Improved Less-Lethal Weapons, 297
Toxin, 217
Tracking, 625
Trahan, M. W.
 Enhanced Disease Surveillance, 585
 Intense Directed-Energy Theory Initiative, 246
 Link Analysis Using Computing, 599
Transceivers, 604
 See also: Microtransceiver
Transient
 Laser, 518
 Radiometry, 573
Transistors, 163
Transmission
 Data, 752
 Microscope, 530
 Z-pinch, 664
Tribology, 520
Trigger
 Isomer, 275
 Laser, 657
 Switch, 672
Trinkle, J. C.
 Automatic Design of Practical Fixtures, 72
Trott, W. M.
 Microscale Shock-Wave Physics, 471
Troup, C. B.
 Mapping Membrane Protein Interactions, 107
Trudell, D. E.
 Novel Catalytic Systems for Separations, 368
Tsang, R. P.
 Varying QoS for Fixed and Mobile Networks, 317
Tucker, S.
 Intense Directed-Energy Theory Initiative, 246
Tumor, 111
Tuners, 160

Author and Title Index

- Tunneling
 Microscope, 732
 Transistor, 163
 Turnley, J. G.
 Threats to the Social Fabric of the U.S., 37
 Turnquist, M. A.
 Disruption Vulnerability Analysis, 329
 Tuttle, B. A.
 Shock-Wave Response of PZT 95/5, 483
 Two-dimensional
 Hadamard Imager, 560
 Hyperspectral Imaging, 467
- U**
- Ulibarri, T. A.
 Polymer-Based Antitamper Systems, 649
 Ultraminiaturization (RF), 678
 Underground
 Facility (MASINT), 253
 Facility (urban), 552
 Unstructured environment
 Mobile robot, 243
 Robotic manipulation, 226
 Urban, 552
 UV
 See Ultraviolet
 Ultraviolet
 Sensor (Fluorescence), 232
 Sensor (laser), 578
- V**
- Vacuum-Arc, 502
 Van Benthem, M. H.
 Improved Materials-Aging Diagnostics, 467
 Multivariate Spectral Calibration Algorithms, 536
 Van Blarigan, P.
 Advanced Power Plants for Vehicles, 40
 Van Bloeman Waanders, B. G.
 Nonlinear Optimization from PDE Models, 132
 Van Leeuwen, B. P.
 Self-Configurable Network Protocol, 324
 Van Schilfgaarde, M.
 Determination of Dislocation Properties, 513
 Van Swol, F. B.
 Molecular Simulation of Reacting Systems, 124
 Smart Self-Assembled Photochromic Films, 450
 Vandernoot, V. A.
 Early Detection of Pathogen Exposure, 622
 Study of Cell Signaling, 44
 Vandevender, J. P.
 Magnetically Insulated Power Flow, 718
 Vanecek, C. W.
 Actuator-Based Electrokinetic Pump, 681
 Vannoni, M. G.
 Remote Monitoring of Restricted Equipment, 640
 Vapor (thin-film), 92
 Vaporization, 518
 Vasile, M. J.
 Combined Microfabrication Processes, 92
- Vaughn, M. R.
 Robotic Ground Vehicle Design, 277
 Vawter, G. A.
 Characterization of Quantum Dots, 181
 Development of a Microoptic Gyroscope, 571
 Dispersive Photonics for Sensors, 213
 VDC
 See Volumetric (Displacement control)
 VECSELs
 See Vertical external-cavity surface-emitting laser
 Vehicle
 Power, 40
 Robotic, 277
 Venturini, E. L.
 Shock-Wave Response of PZT 95/5, 483
 Vernon, G. E.
 Assembly of LIGA Using Electric Fields, 81
 Surface-Micromachined Mechanical Timer, 689
 Vertical external-cavity surface-emitting laser, 178
 Vianco, P. T.
 Multiaxial Deformation Experiments on Solder, 419
 Vibration, 633
 Video
 Radar, 595
 Robotic, 305
 Sensing, 116
 Vigil, M. G.
 Glass Technology for Architectural Surety, 575
 Visualization, 253
 Vizkelethy, G.
 Radiation-Induced Prompt Photocurrents, 172
 Voigt, J. A.
 All-Ceramic Battery, 499
 Shock-Wave Response of PZT 95/5, 483
 Volatile, 373
 Volponi, J. V.
 Early Detection of Pathogen Exposure, 622
 Microincubators for Rapid Toxin Expression, 562
 Molecular Integrated Microsystems, 439
 Volumetric
 Displacement control, 63
 Video motion sensing, 116
 Voth, T. E.
 Large-Eddy Simulation Algorithms, 121
 Vulnerability
 Microwave, 221
 Power grid, 399
 Surety, 329
- W**
- Wackerbarth, D. E.
 Enhanced Impulse Experimentation, 659
 Waddoups, I. G.
 Self-Assembled, Tamper-Detection Seals, 564
 Wagner, J. S.
 Cognition-Driven Augmented Analyst, 653
 Intense Directed-Energy Theory Initiative, 246
 Numerical Methods for High-Energy Physics, 152
 Self-Organizing Network Intelligent Algorithm, 155

Author and Title Index

- Walck, M. C.
Information Collection, 438
- Walker, A. W.
Molecular Integrated Microsystems, 439
- Walker, P. K.
Energetic-Material Burn and Detonation, 416
- Walko, R. J.
New Mechanism for Upset of Electronics, 283
- Wall, F. D.
Critical-Length Scales for Corrosion, 527
Monitoring Corrosion in Weapons, 453
- Wallace, W. T.
Nanosat, 554
- Wally, K.
Direct-Conversion Microfluid Systems, 609
Miniature Sensors for BW Agents, 187
Molecular Integrated Microsystems, 439
- Walsh, D. S.
Radiation-Induced Prompt Photocurrents, 172
- Walther, E. A.
Adaptive Computer Intrusion Detection, 597
Link Analysis Using Computing, 599
- Wang, Y.
Self-Assembled Nanostructured Materials, 376
- Warfare, 255
- Warne, L. K.
Assembly of LIGA Using Electric Fields, 81
Dielectric Photoelectric Effect, 435
Levitated Three-Axis Microaccelerometer, 90
- Warning (cyber), 652
- Warpinski, N. R.
Microexplosive Subsurface Tracing System, 391
- Warren, M. E.
Molecular Integrated Microsystems, 439
Nanosat, 554
Nanostructured Materials in Optical Devices, 497
Photonic Lattice Coatings, 632
- Waste
Nuclear, 376
Water, 358
- Water
Demand, 743
Fresh, 35
Monitoring, 385
Potable, 358
Purification, 383
Surface, 725
- Watson, C. S.
Glass Technology for Architectural Surety, 575
- Watterberg, P. A.
Flexible Robotic Maintenance Facility, 285
- Watts, A. C.
Orbit-to-Surface Sensor Delivery System, 643
- Waveforms, 607
- Weapon
Corrosion, 453
Inspection, 687
Less-lethal, 297
Photon beam, 235
- Weatherby, J. R.
Large-Deformation Solid-Fluid Interaction, 432
- Webb, C. B.
Nanosat, 554
- Webb, E. B., III
Wetting and Spreading Dynamics of Alloys, 464
- Weber, T. M.
Assembly of LIGA Using Electric Fields, 81
- Wehlburg, C. M.
2-D Hadamard Transform Spectral Imager, 560
Improved Materials-Aging Diagnostics, 467
Informatics for Systems Biology, 109
Multivariate Spectral Calibration Algorithms, 536
- Wehlburg, J. C.
2-D Hadamard Transform Spectral Imager, 560
Deployable Large-Aperture Optics System, 618
- Weichman, L. S.
Microfuze, 307
- Weiss, C. J.
Ground-Penetrating Radar, 394
- Welch, D. R.
Magnetic-Field Effects on Plasmas, 502
- Welding, 684
- Wellman, G. W.
Microstructure and Mechanics, 491
- Wendt, J. R.
Characterization of Quantum Dots, 181
Detection of Chem/Bio Warfare Agents, 255
Dispersive Photonics for Sensors, 213
Quantum Tunneling Transistors, 163
Transceivers for Microtags to Improve Security, 604
Ultra-Efficient Solid-State Lighting, 443
- Wenner, C. A.
Knowledge-Based Human Agent Simulation, 589
- Wessendorf, K. O.
Information Collection, 438
Low-Cost Digital Radar, 273
Range Imaging for Autonomous Navigation, 239
- Weston, J. W.
Nanosat, 554
- Westrich, H. R.
Water-Quality Monitoring, 385
- Wetting (solder), 464
- Wheeler, D. R.
Micro-GC-Based Controller, 338
Molecular Integrated Microsystems, 439
- Whinnery, L. L., Jr.
Electrochemomechanical Actuation, 488
Irreversible and Reversible Getters, 507
- White-Light, 219
- Whole-Cell, 47
- Wickstrom, R. D.
Awareness Through Accurate Geolocation, 573
- Wilcoxon, J. P.
Nanoclusters for Supercapacitors, 511
Ultra-Efficient Solid-State Lighting, 443
- Williams, C. V.
Fire-Suppression Properties of Decon Foam, 295
- Williams, R. A.
Nanosat, 554

Author and Title Index

Williams, R. L.
Adaptive and Mobile Ground Sensors, 278

Williamson, R. L.
Science-Based Processing of Composites, 534

Willison, C. L.
Microfabricated Acoustic Spectrum Analyzer, 582

Wilson, C. W.
Small-Scale High-Performance Optics, 635

Wireless, 752

Witczak, S. C.
Radiation Aging of Stockpile Microelectronics, 430

Witze, P. O.
Airborne Carbon Nanoparticles, 378

Witzke, E. L.
Intrusion Detection for ATM Networks, 353

Woo, N. C. F.
Molecular Integrated Microsystems, 439

Wray, C. M.
Adaptive Computer Intrusion Detection, 597

Wright, A. F.
Copper-Corrosion Mechanisms, 460
High-Al-Content AlGaInN Devices, 192
Ultra-Efficient Solid-State Lighting, 443

Wright, M. F.
Direct-Conversion Microfluid Systems, 609

Wright, S. A.
Very High Temperature Gas-Cooled Reactor, 365

Wu, B. C.
Direct-Conversion Microfluid Systems, 609

Wylie, B. N.
Informatics for Systems Biology, 109

Wyss, G. D.
Risk-Informed Proliferation Analysis, 568

X

Xavier, P. G.
Cognition-Driven Augmented Analyst, 653
Heterogeneous Simulation, 114
Knowledge-Based Human Agent Simulation, 589

X-Ray, 291

Y

Yang, N. Y. C.
LIGA Microsystems Aging, 532
Microreplication from Master Molds, 75

Yang, Y.
Biomimetic Chloroplasts, 728
Self-Assembled Nanostructured Materials, 376

Yee, A. A.
Data Fusion and Visualization of MASINT, 253

Yee, M. L.
Data Fusion and Visualization of MASINT, 253

Yelton, W. G.
Detection of Chem/Bio Warfare Agents, 255
Microfabrication of Electromagnetic Devices, 194

Yost, F. G.
Wetting and Spreading Dynamics of Alloys, 464

Young, J. G.
MEMS Microelectric Generator, 341

Young, M. F.
Multifidelity Modeling of Coupled Systems, 136

Young, M. M.
Interfacial Bioscience Grand Challenge, 447
Mapping Membrane Protein Interactions, 107

Young, W. F.
Intrusion Detection for ATM Networks, 353
Security Models of Agent-Based Coalitions, 396

Z

Zaidi, S. H.
Nanostructured Silicon for Photovoltaics, 343

Zamora, J. A. C.
Surface-Micromachined Mechanical Timer, 689

Zavadil, K. R.
Copper-Corrosion Mechanisms, 460
Critical-Length Scales for Corrosion, 527
Microminiature Thermionic Converter, 388
Self-Assembled Templates for Nanoarrays, 462

Zellicoff, A. P.
Enhanced Disease Surveillance, 585

Zeolite, 730

Zimmerman, J. A.
Crack Nucleation and Growth, 402

Zirzow, J. A.
Microchemical Sensors for Volatile Contaminants, 373

Z-Pinch
Power-plant, 661
Transmission line, 664

Zubrzycki, W. J.
Development of a Microoptic Gyroscope, 571
Dispersive Photonics for Sensors, 213

Zutavern, F. J.
Low-Intensity Laser Triggering of Spark Gaps, 657
Solid-State Switch for Pulsed Power, 667
Terahertz Radiation Technology for MASINT, 638