Report Title: Technical Progress on Project Entitled: “24-Channel Geophone Array for Horizontal or Vertical Boreholes”

Type of Report: Quarterly Technical Report

Reporting Period Start Date: April 1, 2003

Reporting Period End Date: June 30, 2003

Principal Author: Erik C. Westman

Date Report was Issued: July 2003

DOE Award Number: DE-FC26-01NT41063

Name and Address of Submitting Organization:

Virginia Polytechnic Institute and State University
Office of Sponsored Programs
Collegiate Square
460 Turner Street, Suite 306
Blacksburg, VA 24060

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility of the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Abstract

This report describes the technical progress on a project to design and construct a multi-channel geophone array that improves tomographic imaging capabilities in both surface and underground mines. No work was completed during this reporting period as project personnel are waiting for the mine to become available for final field testing of the array. Improved imaging capabilities will produce energy, environmental, and economic benefits by increasing exploration accuracy and reducing operating costs.

Table of Contents

Disclaimer	i
Abstract	ii
Table of Contents	iii
Introduction	1
Experimental	2
Results and Discussion	3
Conclusion	4
References	5

Introduction

The ability to accurately image conditions within a rockmass permits superior resource characterization resulting in more efficient extraction. This ability relates directly to industry goals to:

- 1) sense, visualize, and predict geological anomalies in front of mining equipment,
- 2) reduce operational downtime,
- 3) detect difficult mining conditions,
- 4) minimize waste, and
- 5) precisely characterize ore bodies.

Achieving these goals will have the benefits of reducing the amount of energy consumed by mining operations and minimizing the environmental impact of extraction.

Seismic tomography has been used successfully to monitor and evaluate geologic conditions ahead of a mining face. A review of the history and theory of tomographic imaging itself will be presented to properly illustrate the advances introduced by the multi-channel borehole geophone array.

Seismic tomography produces a map of an object's internal properties in a non-invasive fashion (Radon, 1917). By measuring the travel times of a seismic wave between source and receiver points around a rock mass, it is possible to calculate a map of the distribution of physical properties influencing seismic wave velocity within a rock mass. Tomography was first adapted to the field of medicine (Hounsfield, 1973; Cormack, 1973) and subsequently to the geosciences (Dines and Lytle, 1979). For at least 20 years, tomography has been used in the mining industry to create images of geologic features as well as stress-related features (Buchanan et al., 1981, Mason 1981, Kormendi et al., 1986). A more recent mining-specific application of tomography is an adaptation which can image stress concentrations ahead of the longwall face by using the longwall shearer itself as the seismic source (Westman et al., 1996).

Velocity tomography creates a velocity map from signal time-travel data. In this specific type of tomography, the raypath and the velocity variations along the raypath are unknown variables. By representing the medium as a grid, a forward velocity model is constructed to estimate the travel-time and the refraction path of each ray. Refraction paths are estimated by back-projection across the grid from each receiver to the source. By propagating a finite difference wavefront across the grid from a known source location, the travel-times can be estimated. Differences between the estimates and the measured travel times are used to iteratively update the velocity grid from each receiver to the source. The process is repeated a specific number of times, or until no noticeable changes occur.

Tomographic methods usually involve some sort of iterative algorithm to invert the traveltimes (Dines and Lytle, 1979; Peterson et al., 1985). A problem with these techniques is a tradeoff between resolution and stability of the solution. At some point, as one attempts to see smaller features, the inversion becomes unstable and velocity

artifacts appear. Velocity artifacts are seen as fluctuations of values between adjacent points and the smearing of anomalous zones. Therefore, too few iterations will produce an image which lacks detail, and too many will overfit the data, and produce an image with an abundance of artifacts. A cross-validation method can determine the number of iterations needed (Peterson and Davey, 1990). Also, this method can give a way to determine several solutions to a non-unique problem, which can be then averaged to produce an image that may be an improvement over a single solution obtained using all the data at once.

To complete a tomographic survey, a seismic source must be selected. Several factors must be considered, including cooperation with mining operations, regularity of signal and amount of energy. Sources, including mining-induced seismic activity (Young, 1992), mining equipment and manually input energy (Westman and Haramy, 1996) are all possible considerations. For surveys at a quarry, a drill excavating blast holes can be used as the source. The longwall shearer has been used as the source for underground coal as it provides a relatively high amplitude signal.

A primary limitation to existing seismic tomography, however, is the placement of sensors. The goal of this ongoing project is to develop an array of 24 seismic sensors capable of being mounted in either a vertical or horizontal borehole. This array will significantly improve the ability of seismic tomography to accurately image conditions within a rock mass.

Experimental

Field testing at Consol Energy's Buchanan has been delayed while waiting for the horizontal test hole to be drilled.

Results and Discussion

Consol Energy continues to express a high level of interest in the project and has agreed to drill another borehole for testing. This hole will be located in the barrier panel portion of the 5th Right longwall panel at the Buchanan mine. It is anticipated that this borehole will be completed in August, 2003. This borehole will be different than the prior borehole in that it will be drilled completely through the panel, eliminating the need for a crawler unit. Project personnel will be at the mine during drilling and will attach a vinyl-coated aircraft cable to the drill steel when it punches through the panel. As the steel is retracted, the cable will be pulled through from the headgate to the collar of the borehole in the tailgate. The array will then be attached to the cable and pulled through toward the headgate. A hammer source will be used at multiple locations (approximately 50-ft intervals) around the barrier pillar to test the performance of the array.

Conclusion

Seismic tomography is a promising technique for imaging conditions ahead of surface or underground mining, thereby increasing efficiency and reducing energy consumption

during the mining operation. A principle difficulty in using seismic tomography is the placement of multiple sensors around the mining face. Progress during the tenth calendar quarter of the project (April 1, 2003 through June 30, 2003) focused on discussions with project cooperators regarding scheduling of the final underground testing. The outcome of the project will be an enhanced ability to locate anomalies in advance of mining, thereby increasing the safety and efficiency of the mining process.

References

Buchanan, D.J., R. Davis, P.J. Jackson, and P.M. Taylor, 1981, "Fault Location by Channel Wave Seismology in United Kingdom Coal Seams," *Geophysics*, Vol. 46, pp. 994-1002.

Cormack, A.M., 1973, "Reconstruction of Densities from their Projections, with Applications in Radiological Physics," *Phys. Med. Biol.*, vol. 18, no. 2, pp. 195-207.

Dines, K.A., and J.R. Lytle, 1979, "Computerized geophysical tomography," *Proc. IEEE*, vol. 67, no. 7, pp. 1065-1073.

Hounsfield, G.N., 1973, "Computerized transverse axial scanning (tomography). 1. description of system," *Br. J. Radiol.*, vol.46, no. 552, pp. 1016-1022.

Kormendi, A., T. Bodoky, L. Hermann, L. Dianisda, and T. Kalman, 1986, "Seismic Measurements for Safety in Mines," *Geophysical Prospecting*, Vol. 34, pp. 1022-1037.

Mason, I.M, 1981, "Algebraic Reconstruction of a Two-Dimensional Velocity Inhomogeneity in the High Hazles Seam at Thoresby Colliery," *Geophysics*, Vol. 46, pp. 298-308.

Peterson, J.E. Jr, B.N.P. Paulsson, and T.V. McEvilly, 1985, "Applications of Algebraic Reconstruction Techniques to Crosshole Seismic Data," *Geophysics*, Vol 50, No. 10, pp. 1566-1580.

Peterson, J.E. Jr. and A. Davey, 1991, "Crossvalidation Method for Crosswell Seismic Tomography," *Geophysics*, Vol 56, No. 3, pp. 385-389.

Radon, J., 1917, "Über die bestimmung von functionen durch ihre integralwere lange gewisser mannigfaltigkeiten," *Ber. Verh. Saechs. Akad. Wiss.*, vol. 69, pp. 262-267.

Westman, E.C. and K.Y. Harnay, 1996, "Seismic tomography to map hazards ahead of the longwall face," *Mining Engineering*, Vol. 48, No. 11, pp. 73-79.

Westman, E.C., K.Y. Harnay, and A.D. Rock, 1996, "Seismic tomography for longwall stress analysis," *Proceedings of 2nd North American Rock Mechanics Symposium (Montreal, Quebec, June 19-21)*, ed. By M. Aubertin, F. Hassani, and H. Mitri, A.A. Balkema, pp. 397-403.

Young, R.P., 1992, "Invited Paper: Correlation between seismic velocity and induced seismicity in underground mines," Proceedings of 33rd U.S. Symposium on Rock Mechanics (Santa Fe, New Mexico, June 3-5), ed. by J.R. Tillerson and W.R. Wawersik, A.A. Balkema, pp. 1113-1122.