OFFICE OF CIVILIAN RADIOACTIVE WASTE MANAGEMENT ANALYSIS/MODEL COVER SHEET

1. OA: QA
Page: 1 of: 34

Complete Only Applicable Items

<p>2. ☒ Analysis Check all that apply</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Type of Analysis</td> <td> ☒ Engineering ☐ Performance Assessment ☐ Scientific </td> </tr> <tr> <td>Intended Use of Analysis</td> <td> ☐ Input to Calculation ☐ Input to another Analysis or Model ☐ Input to Technical Document </td> </tr> <tr> <td>Describe use:</td> <td> ☒ Input to other Technical Products </td> </tr> </table>	Type of Analysis	☒ Engineering ☐ Performance Assessment ☐ Scientific	Intended Use of Analysis	☐ Input to Calculation ☐ Input to another Analysis or Model ☐ Input to Technical Document	Describe use:	☒ Input to other Technical Products	<p>3. ☒ Model Check all that apply</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Type of Model</td> <td> ☐ Conceptual Model ☐ Abstraction Model ☐ Mathematical Model ☒ System Model ☐ Process Model </td> </tr> <tr> <td>Intended Use of Model</td> <td> ☐ Input to Calculation ☐ Input to another Model or Analysis ☐ Input to Technical Document </td> </tr> <tr> <td>Describe use:</td> <td> ☒ Input to other Technical Products </td> </tr> </table>	Type of Model	☐ Conceptual Model ☐ Abstraction Model ☐ Mathematical Model ☒ System Model ☐ Process Model	Intended Use of Model	☐ Input to Calculation ☐ Input to another Model or Analysis ☐ Input to Technical Document	Describe use:	☒ Input to other Technical Products
Type of Analysis	☒ Engineering ☐ Performance Assessment ☐ Scientific												
Intended Use of Analysis	☐ Input to Calculation ☐ Input to another Analysis or Model ☐ Input to Technical Document												
Describe use:	☒ Input to other Technical Products												
Type of Model	☐ Conceptual Model ☐ Abstraction Model ☐ Mathematical Model ☒ System Model ☐ Process Model												
Intended Use of Model	☐ Input to Calculation ☐ Input to another Model or Analysis ☐ Input to Technical Document												
Describe use:	☒ Input to other Technical Products												

4. Title:
Preliminary Dynamic Soil-Structure-Interaction Analysis for the Waste Handling Building

5. Document Identifier (including Rev. No. and Change No., if applicable):
ANL-WHS-ST-000001 REV 00

6. Total Attachments: 8	7. Attachment Numbers - No. of Pages in Each: I(6), II(20), III(CD), IV(26), V(CD), VI(10), VII(3), VIII(51)
-----------------------------------	--

	Printed Name	Signature	Date
8. Originator	Gary Wagenblast	<i>[Signature]</i>	5/1/00
9. Checker	Michael Ruben	<i>[Signature]</i>	5/1/00
10. Lead/Supervisor	Michael Ruben	<i>[Signature]</i>	5/1/00
11. Responsible	C. Gus Mattsson	<i>[Signature]</i>	5/1/00

12. Remarks:
Attachment III - CD
Attachment V - CD

MOL.20000504.0313

**OFFICE OF CIVILIAN RADIOACTIVE WASTE MANAGEMENT
ANALYSIS/MODEL REVISION RECORD**

1. Page: 2 of: 34

Complete Only Applicable Items

2. Analysis or Model Title:

Preliminary Dynamic Soil-Structure-Interaction Analysis for the Waste Handling Building

3. Document Identifier (including Rev. No. and Change No., if applicable):

ANL-WHS-ST-000001 REV 00

4. Revision/Change No.

5. Description of Revision/Change

00

Initial Issue

TABLE OF CONTENTS

TABLES.....	4
ACRONYMS AND ABBREVIATIONS	5
1. PURPOSE.....	8
2. QUALITY ASSURANCE.....	8
3. COMPUTER SOFTWARE AND MODEL USAGE	9
4. INPUT	9
4.1 DATA AND PARAMETERS	9
4.2 CRITERIA.....	14
4.3 CODES AND STANDARDS.....	15
5. ASSUMPTIONS.....	15
6. ANALYSIS/MODEL.....	17
6.1 METHOD	17
6.2 ANALYSIS AND MODEL.....	18
6.2.1 WHB Configuration.....	18
6.2.2 ACS SASSI-C Modeling	19
6.2.3 Soil Modeling and Free Field Earthquake Ground Motions	20
6.2.4 Foundation Modeling.....	22
6.2.5 Structure Modeling	23
6.2.6 Running ACS SASSI-C	25
6.2.7 Forces And Stresses.....	25
6.2.8 Steel Column and Beam Members	25
6.2.9 Plate Elements (Concrete).....	28
6.2.10 Sliding	29
6.2.11 Hydrodynamic Analysis.....	29
7. CONCLUSIONS.....	30
8. INPUTS AND REFERENCES.....	31
8.1 DOCUMENTS CITED	31
8.2 CODES, STANDARDS, REGULATIONS, AND PROCEDURES CITED	33
8.3 SOURCE DATA, LISTED BY DATA TRACKING NUMBER.....	34
9. ATTACHMENTS.....	34

TABLES

Table 4-1. WHB Material Properties	10
Table 4-2. WHB SASSI-C Section Properties	11
Table 4-3. Layer Data for Distant Earthquakes (1-2 Hz).....	11
Table 4-4. Crane Input Parameters	12
Table 4-5. Layer Data for Proximate Earthquakes (5-10 Hz).....	13
Table 4-6. Miscellaneous Data Parameters and Conversion Factors	14
Table 5-1. WHB Crane Spans	15
Table 5-2. Assumed Material Properties.....	16
Table 6-1. ACS-SASSI-C SITE and HOUSE Files.....	19
Table 6-2. ATS Process Area Results	26
Table 6-3. WP Transport Area Results	27
Table 6-4. Cross Transfer Area Results	28
Table 6-5. DC Handling Area Allowable Load/Moment Results	28

ACRONYMS AND ABBREVIATIONS

ρ	water weight (62.428 pound per cubic foot)
$\lambda_1, \lambda_2, \lambda_3$	first, second, and third root of Bessel function of natural frequencies
$\omega_{x_i}, \omega_{y_i}$	fundamental natural angular frequency of the i th pool dimension in X or Y direction (rad/sec)
ACC	accession
ACI	America Concrete Institute
ACS SASSI-C	name of soil-structure- interaction program
AISC	American Institute of Steel Construction
ANSI	American National Standards Institute
AP	Administrative Procedure
ASCE	American Society of Civil Engineers
ATS	Assembly Transfer System
$A_{x_{i,1}}, A_{x_{i,2}}, A_{x_{i,3}}, A_{y_{i,1}}, A_{y_{i,2}}, A_{y_{i,3}}$	Slosh height of first, second, and third mode at i th dimension in X or Y direction (ft)
a_{x_k}, a_{y_k}	Acceleration at control point k for horizontal X or Y direction response spectrum
col	column
CRWMS M&O	Civilian Radioactive Waste Management System Management and Operating Company
cu.	cubic
DBE	design basis event
DC	disposal container
DL	dead load
DOE	(U.S.) Department of Energy
DOF	degrees-of-freedom
Dratio	The rectangular to cylindrical tank conversion for calculating the maximum water surface displacement
DTN	data tracking number
E	east
E	elastic modulus
ft	feet
ft ²	square feet
ft ⁴	feet to the fourth power
f_{x_k}, f_{y_k}	Control point k frequency for horizontal X or Y direction response spectrum
g	gravity (32.174 ft/sec/sec)
ga	gauge
gms	grams
h	water depth (ft)
HVAC	heating, ventilating, and air conditioning
Hz	Hertz

ACRONYMS AND ABBREVIATIONS, CONTINUED

i, k	integer counter
ICBO	International Conference of Building Officials
ICN	interim change notice
ID	identification
in ²	square inches
in ⁴	inches to the fourth power
IOC	inter-office correspondance
K, kip	Unit of kip is equal to 1000 pounds force
kgms	kilo-grams
LA	License Application
lbf	foot pounds
lbs	pounds
linterp	linear interpolation
LL	live load
log	logarithmic
LV	Las Vegas
m	meters
MFD	mechanical flow diagram
MYPS	Muti-Year Planning System
N	<u>n</u> th natural frequency of the pool
N	north
n.a.	not applicable
nfx _{i,n} , nfy _{i,n}	<u>n</u> th natural frequency of <u>i</u> th pool dimension in X direction (Hz)
NRC	Nuclear Regulatory Commission
NUREG	NRC Regulation
OCRWM	Office of Civilian Radioactive Waste Management
PC	personal computer
Prep	preparation
psf	pounds per square foot
Q	quality
QA	quality assurance
QAP	Quality Administrative Procedure
QARD	Quality Assurance Requirements and Description
rad	radians
Ref	reference
S	south
S	seismic
SAN	software activity number
SASSI-C	System for Analysis of Soil Structure Interaction Version C
sec	second
shx _i , shy _i	slosh height of <u>i</u> th pool dimension in X or Y direction (ft)
SR	Site Recommendation
SRSS	square root of the sum of the squares
SSI	soil-structure-interaction
T	thickness
TBD	to be determined

ACRONYMS AND ABBREVIATIONS, CONTINUED

TBV	to be verified
TIC	Technical Information Center
U.S.	United States
UBC	Uniform Building Code
VA	Viability Assessment
vax(), vay()	Interpreted acceleration between control points from horizontal X direction response spectrum (g)
Vp	P-Wave Velocity
Vs	S-Wave Velocity
W	west
WA	Washington
WHB	Waste Handling Building
WP	waste package
WT	weight
X	coordinate system – X direction
x_i, y_i	ith pool dimension in X or Y direction (ft)
Y	coordinate system – Y direction
Z	coordinate system – Z direction

1. PURPOSE

The objective of this analysis package is to document a preliminary dynamic seismic evaluation of a simplified design concept of the Waste Handling Building (WHB). Preliminary seismic ground motions and soil data will be used. Loading criteria of the WHB System Design Description will be used. Detail design of structural members will not be performed. The results of the analysis will be used to determine preliminary sizes of structural concrete and steel members and to determine whether the seismic response of the structure is within an acceptable level for future License Application design of safety related facilities.

In order to complete this preliminary dynamic evaluation to meet the Site Recommendation (SR) schedule, the building configuration was 'frozen in time' as the conceptual design existed in October 1999. Modular design features and dry or wet waste storage features were intentionally excluded from this preliminary dynamic seismic evaluation. The document was prepared in accordance with the Development Plan for the *Preliminary/Dynamic Soil Structure Interaction Analysis for the Waste Handling Building* (CRWMS M&O 2000b), which was completed in accordance with AP-2.13Q, *Technical Product Development Planning*.

2. QUALITY ASSURANCE

The work presented in this document has been prepared in accordance with Office of Civilian Radioactive Waste Management (OCRWM) approved program document AP-3.10Q, *Analyses and Models*. An Activity Evaluation, *WHB Preliminary Earthquake Analysis for the WHB to Support SR-FY00* (Work Package 24012123M5) (CRWMS M&O 1999c) was performed in accordance with QAP-2-0, *Conduct of Activities*. This Activity Evaluation determined that this document is subject to the requirements of the *Quality Assurance Requirements and Description* (QARD) (DOE 2000). In addition, this report is quality affecting because the results will support the inputs to the applicable sections of the SR.

The WHB Structure is a QL-1 SSC based on the *Classification of the MGR Waste Handling Building System* (CRWMS M&O 1999a, Table 1), performed in accordance with QAP-2-3, *Classification of Permanent Items*. Use of any data from this report for input into documents supporting procurement, fabrication, or construction is required to be controlled as TBV in accordance with AP-3.15, *Managing Technical Product Inputs*.

This document contains the current state of knowledge of the surface facility systems. This document does not provide analysis, models, or conclusions that affect any system's critical characteristics, scientific results, or provide data that can be directly relied upon to address waste isolation issues. There will be no effect as to the safety classification of any surface structure, system or component. Certain of the references used in the preparation of this document were prepared for the VA design and contain preliminary data that are not tracked using the formal TBV/TBD process. However, potential alterations to these inputs are not expected to impact the system and process flow descriptions within this document.

The information contained in this document is considered preliminary and will not be used directly for procurement, fabrication, or construction. The information may be tracked as TBV or TBD, if needed, at the discretion of the responsible manager.

3. COMPUTER SOFTWARE AND MODEL USAGE

In order to perform sophisticated finite-element soil-structure-interaction (SSI) analyses, an industry accepted, quality assurance qualified, and efficient computer analysis code is required.

The computer code ACS SASSI-C (ACS SASSI-C V1.1. 10125-1.1-00) was selected to perform the SSI analysis. The ACS SASSI-C (a System for Analysis of Soil Structure Interaction) program is a special purpose computer code which can be used to solve a wide range of dynamic SSI problems in three-dimensions. The program SASSI is extensively used in the field of SSI analysis. It has been used in the analysis and design of structures for many commercial nuclear facilities. ACS SASSI-C is a commercially available adaptation of the original SASSI program compiled to run on a personal computer using Windows-NT operating system.

The ACS SASSI-C program is appropriate for the SSI evaluation of the WHB and was selected for use based on its accepted use in the commercial nuclear and non-nuclear industry and its capability in the three-dimensional analysis of SSI problems with finite-element modeling of structures. The ACS SASSI-C computer program has been base-lined and released for quality affecting work (CRWMS M&O 2000c). The software has been obtained from configuration management. The computer program ACS SASSI-C was used only within the range of validation. Input and output files are documented in the attachments.

Software Activity Number: SAN LV-1999-112
Software Name: ACS SASSI-C
Software Version: Version 1.1
Software Tracking Number: 10125-1.1-00

Computer: Intergraph TDZ2000 Pentium II PC
(FLUOR property number 30032258)
Computer Location: 1200 Jadwin
Room 274
Richland, WA. 99352

No other software routines (as defined in AP-3.12Q, *Calculations*) or models (as defined in AP-3.12Q) were used in this calculation.

4. INPUT

4.1 DATA AND PARAMETERS

The material in Table 4-1 describes the material properties used in the soil-structure-interaction (SSI) analysis. The data in Table 4-1 are qualified except as noted.

The material in Table 4-2 describes the member section properties of the structural elements used in the SSI analysis. The data in Table 4-2 are qualified except as noted.

The material in Table 4-3 describes the soil layer properties used in the SSI analysis for distant earthquakes. The material in Table 4-3 is qualified.

The material in Table 4-4 describes the crane information used in the SSI analysis. The data in Table 4-4 are qualified except as noted.

The data in Table 4-5 describe the soil layer data properties used for the SSI analysis for proximate earthquakes. The data are qualified.

The data in Table 4-6 describe miscellaneous data parameters and conversion factors used in the SSI analysis. The data are qualified except as noted.

Table 4-1. WHB Material Properties

Material Name (Note 7)	Material	Elastic Modulus (lbs/ in ²)	Elastic Modulus (kips/ ft ²)	Poisson's Ratio	Density (kips/ ft ³)	Material Damping
Material 1 Reference	Concrete	3,122,000 See Note 2	450,000 Conversion	0.278 See Note 5	0.150 See Note 4	0.05 See Note 5
Material 2 Reference	Concrete	3,122,000 See Note 2	450,000 Conversion	0.278 See Note 5	0.160 See Note 8	0.05 See Note 5
Material 3 Reference	Steel	29,000,000 See Note 3	4,180,000 Conversion	0.3 See Note 5	0.490 See Note 6	0.05 See Note 5
Material 4 Reference	HVAC Roof	N/A N/A	58,400 See Note 1	0.28 See Note 5	0.051 See Note 1	0.05 See Note 5
Material 5 Reference	HVAC Floor	N/A N/A	237,000 See Note 1	0.28 See Note 5	0.21 See Note 1	0.05 See Note 5
Material 6 Reference	ATS Roof 44 ft Span	N/A N/A	126,000 See Note 1	0.28 See Note 5	0.051 See Note 1	0.05 See Note 5
Material 7 Reference	ATS Roof 24 ft Span	N/A N/A	170,000 See Note 1	0.28 See Note 5	0.051 See Note 1	0.05 See Note 5
Material 8 Reference	DC Roof	N/A N/A	126,000 See Note 1	0.28 See Note 5	0.051 See Note 1	0.05 See Note 5
Note 1: See Attachment III Note 2: See ACI 349, Section 8.5.1 and Assumption 5.7 [57000*(3000) ^ .5 = 3122000 psi] Note 3: See AISC 1991, Part 6 Note 4: See ACI 349, Chapter 10. Note 5: See Assumption 5.4. Note 6: See AISC 1991, page 6-8 Note 7: Material number refers to ACS SASSI-C input variables. Note 8: See Section 6.2.5						

Table 4-2. WHB SASSI-C Section Properties

Material Name Note 4	Beam Size	Area ^(Note 2)		Torsion Moment of Inertia ^(Note 3)		Strong Axis Moment of Inertia ^(Note 3)		Weak Axis Moment of Inertia ^(Note 3)	
		(in ²)	(ft ²)	(in ⁴)	(ft ⁴)	(in ⁴)	(ft ⁴)	(in ⁴)	(ft ⁴)
Real 1 and 2	W10x49	14.4	0.100	1.39	6.7x10 ⁻⁵	272	0.0131	93.4	4.5x10 ⁻³
Reference Page ^(Note 1)	-	I-30		I-123		I-31		I-31	
Real 3 and 4	W14x61	17.9	0.124	2.20	1.06x10 ⁻⁴	640	0.0309	107	5.16x10 ⁻³
Reference Page ^(Note 1)	-	I-26		I-121		I-27		I-27	
Real 5 and 6	W14x90	26.5	0.184	4.06	1.96x10 ⁻⁴	999	0.0482	362	1.76x10 ⁻²
Reference Page ^(Note 1)	-	I-26		I-121		I-27		I-27	
Real 7 and 8	W14x132	38.8	0.269	12.3	5.93x10 ⁻⁴	1530	0.0738	548	2.64x10 ⁻²
Reference Page ^(Note 1)	-	I-26		I-121		I-27		I-27	
Real 9 and 10	W24x104	30.6	0.212	4.72	2.28x10 ⁻⁴	3100	0.149	259	1.25x10 ⁻²
Reference Page ^(Note 1)	-	I-18		I-119		I-19		I-19	
Real 11	W21x101	29.8	0.207	5.21	2.51x10 ⁻⁴	2420	0.117	248	1.20x10 ⁻²
Reference Page ^(Note 1)	-	I-20		I-126		I-21		I-21	
Real 12	W18x50	14.7	0.102	1.24	5.98x10 ⁻⁵	800	0.0386	40.1	1.93x10 ⁻⁴
Reference Page ^(Note 1)	-	I-22		I-126		I-23		I-23	
Note 1 AISC 1991									
Note 2: Conversion factors for in ² = 0.0069444 ft ² from DTN: MO9812SCCT1SAT.000									
Note 3: Conversion factors for in ⁴ = (in ²) ² = (0.0069444 ft ²) ²									
Note 4: Real number refers to ACS SASSI-C input variable.									

Table 4-3. Layer Data for Distant Earthquakes (1-2 Hz)

Basis: Section 6.2.3

Note: Data from Attachment I-1 converted to English units for ACS SASSI-C Input

Layer	Thickness (T) Ft	Depth ft	Unit Weight kip/cu.ft	P-Wave Velocity (Vp) ft/sec	S-Wave Velocity (Vs) ft/sec	P-Wave Damping Ratio	S-Wave Damping Ratio	Cut Off Frequency Vs/(5*T) Hertz
1	5.3	5.3	0.131	1802.2	794.7	0.005	0.024	30.0
2	4.9	10.2	0.131	1802.2	580.3	0.005	0.049	23.7
3	4.9	15.1	0.131	1802.2	465.9	0.005	0.067	19.0
4	7.2	22.3	0.112	2657.0	1099.6	0.005	0.043	30.5
5	8.9	31.2	0.125	3036.0	1294.1	0.005	0.040	29.1
6	9.8	41.0	0.125	3481.8	1501.6	0.005	0.039	30.6
7	11.2	52.2	0.125	3730.8	1579.0	0.005	0.041	28.2
8	11.5	63.7	0.125	4043.0	1715.2	0.005	0.042	29.8
9	21.6	85.3	0.125	4626.3	2162.2	0.005	0.019	20.0
10	21.6	106.9	0.075	4626.3	2035.7	0.005	0.028	18.8
11	21.6	128.5	0.075	4744.5	2220.5	0.005	0.008	20.6
12	21.7	150.2	0.075	4744.5	2220.5	0.005	0.008	20.5
13	24.9	175.1	0.075	5153.2	2756.2	0.005	0.007	22.1
14	24.9	200.0	0.131	5153.2	2785.2	0.005	0.006	22.4
15	24.9	224.9	0.131	5153.2	2785.2	0.005	0.006	22.4
16	25.0	249.9	0.131	5153.2	2785.2	0.005	0.006	22.3
17	100.0		0.131	10000.0	5500.0	0.005	0.005	

Table 4-4. Crane Input Parameters

CRANE ID	HOOK CAPACITY	SPAN (ft) (Note 1)	DEAD WEIGHT (lbs) (Note 2)	MAXIMUM WHEEL LOAD and SPACING (Note 2)	LOCATION	Drawing Reference for Hook Capacity (Column 2)	Reference
CH-CN-100 (Note 4)	10 TON	100	88,000	n.a.	Carrier Prep	MFD - CPB Material Handling System	CRWMS M&O 1997e
PH-CN-100 (Note 4)	125 TON	100	325,000	n.a.	Carrier Bay	MFD - Carrier/Cask Handling System.	CRWMS M&O 1997d
PU-CN-110 (Note 3)	125 TON	44	250,000	4 x 100,000 lbs @ 5 ft	ATS Process, Pool Area	MFD - Assembly Transfer System (Assembly Cask Unloading).	CRWMS M&O 1997a
PU-CN-113 (Note 3)	15 TON	44	60,000	n.a.	ATS Process, Hot Cell	MFD - Assembly Transfer System (Staging and Loading).	CRWMS M&O 1997b
PC-CN-110	85 TON	44	200,000	n.a.	CTS Process, Hot Cell,	MFD - Canister Transfer System (Large Canister).	CRWMS M&O 1997c
PD-CN-103	50 TON	44	120,000	2 x 75,000 lbs @ 12 ft	N/S Transfer Corridor	MFD - DC Handling System (Welding and Staging).	CRWMS M&O 1997f
AR-CN-100	50 TON	45	120,000	2 x 75,000 lbs @ 12 ft	EW Transfer Corridor	MFD - Canister Transfer System (Large Canister).	CRWMS M&O 1997c
PD-CN-100 (Note 5)	85 TON	90	250,000	n.a.	DC Handling	MFD - DC Handling System (Welding and Staging).	CRWMS M&O 1997f
PD-CN-105	20 TON	40	55,000	2 x 35,000 lbs @ 10 ft	Welder Maintenance	See Assumption 5.1.	
PD-H1-100	80 TON	40	200,000	n.a.	WP Transport	MFD - DC Handling System (WP Transfer).	CRWMS M&O 1997g
<p>Note 1: From Attachment II</p> <p>Note 2: From Whiting Crane Handbook (Mattsson 2000).</p> <p>Note 3: 2 cranes required for Assembly Transfer System (ATS) process lines.</p> <p>Note 4: Cranes not used in SSI analysis. Outside the bounds of the ACS SASSI-C model.</p> <p>Note 5: 2 redundant cranes in disposal container (DC) Cell.</p>							

Table 4-5. Layer Data for Proximate Earthquakes (5-10 Hz)

Basis: Section 6.2.3

Note: Data from Attachment I-2 converted to English units for ACS SASSI-C Input

Layer	Thickness (T) ft	Depth ft	Unit Weight kip/cu.ft	P-Wave Velocity (Vp) ft/sec	S-Wave Velocity (Vs) ft/sec	P-Wave Damping Ratio	S-Wave Damping Ratio	Cut Off Frequency Vs/(5*T) Hertz
1	5.3	5.3	0.131	1818.4	774.5	0.005	0.027	29.2
2	4.9	10.2	0.131	1818.4	538.9	0.005	0.061	22.0
3	4.9	15.1	0.131	1818.4	420.2	0.005	0.083	17.2
4	7.2	22.3	0.112	2659.3	1072.7	0.005	0.050	29.8
5	8.9	31.2	0.125	3079.3	1268.0	0.005	0.046	28.5
6	9.8	41.0	0.125	3536.6	1471.9	0.005	0.044	30.0
7	11.2	52.2	0.125	3788.1	1554.0	0.005	0.046	27.8
8	11.5	63.7	0.125	4115.5	1693.9	0.005	0.046	29.5
9	21.6	85.3	0.125	4632.4	2156.6	0.005	0.020	20.0
10	21.6	106.9	0.075	4632.4	2030.3	0.005	0.030	18.8
11	21.6	128.5	0.075	4750.6	2221.4	0.005	0.008	20.6
12	21.7	150.2	0.075	4750.6	2221.4	0.005	0.008	20.5
13	24.9	175.1	0.075	5248.0	2760.1	0.005	0.007	22.2
14	24.9	200.0	0.131	5248.0	2787.7	0.005	0.006	22.4
15	24.9	224.9	0.131	5248.0	2787.7	0.005	0.006	22.4
16	25.0	249.9	0.131	5248.0	2787.7	0.005	0.006	22.3
17	100.0		0.131	10000.0	5500.0	0.005	0.005	

Table 4-6. Miscellaneous Data Parameters and Conversion Factors

Data Parameter	Value	Used in.	Source
Top of the structural Mat (feet above sea level).	3681.5	Section 6.2.1	CRWMS M&O 1998, Attachment I, Figure 8.
WHB foundation shall be a structural reinforced concrete mat with a uniform thickness.	5 feet	Section 6.2.1	CRWMS M&O 1997h, Attachment I, Figure 8.
Wall and floor thickness for waste transfer pools and transfer aisles.	5 feet	Section 6.2.1	CRWMS M&O 1997h, Attachment IV.
Floor of the waste transfer pool location below the finished floor mat.	50 feet	Section 6.2.1	CRWMS M&O 1997h, Attachment I, Figure 8.
Thickness of walls where filled waste packages are opened up to 30 feet.	5 feet	Section 6.2.1	CRWMS M&O 1997h, Attachment IV.
Shielding wall and floor thickness from 30 feet above the operating to the roof.	3 feet	Section 6.2.1	CRWMS M&O 1997h, Attachment IV.
Wind velocity to base wind loads.	120 miles per hour.	Attachment III	Assumption 5.6
Number of horizontal layers on an elastic rock base.	16	Table 4-3 & Table 4-5	DTN: MO0004SESPWHB.011
Conversion factor from pounds to kips.	1000 pounds per kip		DTN: MO9812SCCT2MCU.000
Conversion factor from meters to feet.	3.28 feet per meter		DTN: MO9812SCCT1SAT.000
Conversion factor from kgms/cm ³ to kip/ft ³ .			DTN: MO9812SCCT2MCU.000
Conversion factor from km/sec to ft/sec.			DTN: MO9812SCCT1SAT.000
Conversion factor from percentage to ratio.	multiply by 0.01.		DTN: MO9812SCCT2MCU.000
Conversion factor from pounds per square inch to kips per square foot			DTN: MO9812SCCT2MCU.000
gravity (g)	32.17 ft*sec ⁻²	Attachment III	DTN: MO9812SCCT1SAT.000
Conversion factor from square inches to square feet.	0.0069444		DTN: MO9812SCCT1SAT.000
Concrete compressive strength	3000 pounds per sq in	Table 4-1	Assumption 5.7

4.2 CRITERIA

This structural analysis comprises a preliminary dynamic seismic evaluation of a simplified design concept of the Waste Handling Building (WHB). Primary structural members will be evaluated and sized to withstand the preliminary seismic ground motions. Loads will be determined in accordance with the loads defined in the WHB System Design Description (CRWMS M&O 2000d) and by direction (Mattsson 2000). Proportioning of reinforced concrete members will comply with applicable sections of "Code Requirements for Nuclear Safety Related Concrete Structures (ACI 349-97) and Commentary - ACI 349R-97." (CRWMS M&O 2000d, Section 1.2.6.20). Proportioning of steel members shall comply with applicable sections of "Specifications for the Design, Fabrication, and Erection of Steel Safety Related Structures

for Nuclear Facilities (ANSI/AISC N690-1984)” (CRWMS M&O 2000d, Section 1.2.6.23). Detail design of the concrete and steel members will not be performed.

4.3 CODES AND STANDARDS

ACI 349-97. 1998. *Code Requirements for Nuclear Safety Related Concrete Structures (ACI 349-97) and Commentary - ACI 349R-97.*

ANSI/AISC N690-1984. 1984. *American National Standard for Nuclear Facilities - Steel Safety-Related Structures for Design Fabrication and Erection.*

ANSI/ASCE 7-95. 1996. *Minimum Design Loads for Buildings and Other Structures.*

ICBO (International Conference of Building Officials) 1997. *1997 Uniform Building Code.*

5. ASSUMPTIONS

- 5.1 It is assumed that the hook capacity is 20 ton for the PD-CN-105 Welder Maintenance crane.

Basis: Mattsson 2000.

Used in: Table 4-4 and Attachment III.

- 5.2 It is assumed that the cranes listed in column 1 of Table 4-4 have the span listed in column 2 of Table 5-1

Basis: Seismic Analysis Sketches in Attachment II.

Used in Table 4-4 and Attachment III.

Table 5-1. WHB Crane Spans

CRANE ID	SPAN	LOCATION
CH-CN-100	100 FT	Carrier Prep
PH-CN-100	100 FT	Carrier Bay
PU-CN-110	44 FT	ATS Process, Pool Area
PU-CN-113	44 FT	ATS Process, Assembly Cell
PC-CN-110	44 FT	CTS Process, Hot Cell
PD-CN-103	44 FT	N/S Transfer Corridor
AR-CN-100	45 FT	E/W Transfer Corridor
PD-CN-100	90 FT	DC Handling
PD-CN-105	40 FT	Welder Maintenance
PD-H1-100	40 FT	WP Transport

- 5.3 From a depth of 15 feet to a depth of 250 feet, thirteen in-situ layers are defined. Below 250 feet depth, the in-situ material is defined as an elastic half-space having rock-like properties. Unit weights, P-wave damping, S-wave damping, and P-wave velocity for layers below 1000 feet depth (in the elastic half-space) were not supplied for all layers and were assumed to be consistent with the data supplied for depths from 250 to 1000 feet.

Basis: Based on soil layer properties (see Attachment I-1 & I-2).

Used in Table 4-3, Table 4-5, and Attachment III.

- 5.4 Table 5-2 list Poisson's Ratios and Material Damping assumed for the Materials named.

Basis: The *Standard Handbook for Civil Engineers* (Merritt 1983, Section 6-7) lists Poisson's ratio for steel as 0.30 (Material 3) and Poisson's ratio for concrete (Materials 1, 2, 4, 5, 6, 7, 8) as 0.25 increasing to 0.50 for stress beyond the proportional limit. A value of 0.278, which is within the range, was assumed for Materials 1 and 2. A value of 0.28 was assumed for Materials 3,4,5,6,7,8. NRC Regulatory Guide 1.61, Table 1, lists material and structural damping for reinforced concrete structures and for bearing bolted metal structures as ranging from 4% to 7%, depending on stress level. A value of 5% was assumed for all materials, which is within the range.

Used in Table 4-1.

Table 5-2. Assumed Material Properties

Material	Poisson's Ratio	Damping
Material 1	0.278	0.05
Material 2	0.278	0.05
Material 3	0.3	0.05
Material 4	0.28	0.05
Material 5	0.28	0.05
Material 6	0.28	0.05
Material 7	0.28	0.05
Material 8	0.28	0.05

- 5.5 Not used.

- 5.6 It is assumed that steel material properties shall be appropriate for mild steel having a yield-strength of 50 kips per square inch (ksi).

Basis: Mattsson 2000.

Used in Table 4-6.

- 5.7 It is assumed that the concrete material properties will have a 28 day compression strength of 3000 pounds per square inch.

Basis: Mattsson 2000.

Used in Table 4-6.

5.8 It is assumed that the steel columns are spaced at approximately 24 feet on center.

Basis: Mattsson 2000.
Used in Table 4-6.

5.9 It is assumed that all interior floors will use a uniform live load of 200 pounds per square foot.

Basis: Mattsson 2000.
Used in Table 4-6.

5.10 It is assumed that all roofs will use a uniform live load of 20 pounds per square foot.

Basis: Mattsson 2000.
Used in Table 4-6.

5.11 It is assumed that the figures in Attachment II depict the results of the development of the "frozen in time" concept of the Waste Handling Building of October 1999.

Basis: Mattsson 2000.
Used in Attachment II.

6. ANALYSIS/MODEL

6.1 METHOD

This preliminary SSI evaluation commenced prior to establishment of final facility design and acceptance criteria documents. Seismic ground motions and soil layer data were provided (Attachment I) based on preliminary geo-technical information of the North Portal site. Building configuration, floor and roof loading criteria, and construction materials were supplied as discretionary analysis parameters by management (Mattsson 2000). Applicable model building codes and wind loads were taken from the WHB SDD (CRWMS M&O 2000d).

Seismic response was calculated using the computer program ACS SASSI-C.

A simplified WHB configuration was developed as documented in the sketches provided in Attachment II of this document. Using the simplified WHB configuration, two 3-dimensional finite-element models were developed (one for horizontal motions and one for vertical motion) that explicitly modeled the WHB concrete walls, concrete slabs, steel columns, steel floor beams, and steel bracing. Concentrated masses were included to account for major equipment. ACS SASSI-C results consisted of member stresses in each of three orthogonal (north/south, east/west, and vertical) directions. The directional seismic results were combined by the square-root-of-the-sum-of-the-squares method using hand calculations (Attachment IV).

Results for dead load, live load, and wind loads were determined using hand calculations (Attachment III). These results were also used to size structural steel members for input to the computer model.

Compliance with model building codes was checked for primary structural members including concrete walls, concrete slabs and floors, steel columns, steel beams, and steel bracing. Model building code checks followed the applicable requirements of the American Concrete Institute (ACI 349) and the American Institute of Steel Construction (AISC N690). Load combinations and code compliance were determined using hand calculations (Attachment V).

A separate hydrodynamic analysis was completed to investigate the response of the water in the transfer channels and pools to the seismic ground motion (Attachment VI).

6.2 ANALYSIS AND MODEL

6.2.1 WHB Configuration

This preliminary dynamic evaluation was initiated in October 1999, months before the waste handling process and the WHB configuration for Site Recommendation (SR) or License Application (LA) had been finalized. In order to complete this preliminary dynamic evaluation to meet the SR schedule, the building configuration was 'frozen in time' as the conceptual design existed in October 1999 using a simplified Viability Assessment (VA) design. Modular design features and dry or wet waste storage features were intentionally excluded from this preliminary dynamic seismic evaluation.

A simplified VA design configuration of the WHB using three (two wet and one dry) process lines was developed as documented in the sketches provided in Attachment II of this document. The VA configuration consisted of five (three wet and two dry) process lines. Alternate, or enhanced, design configurations including building modularization and waste storage pools or slabs were being considered. Modular design features and dry or wet waste storage features were intentionally excluded from this preliminary dynamic seismic evaluation. This simplified WHB configuration work was needed in order to develop sufficient definition of the building and the primary structural members so that finite element models used in the dynamic analysis could be constructed.

The *Preliminary Geotechnical Investigation for Waste Handling Building, Yucca Mountain Site Characterization Project* (CRWMS M&O 1999b) recommended a mat type foundation system. For the purposes of this simplified SSI evaluation, the WHB foundation was specified as a structural reinforced concrete mat having a uniform thickness of 5 feet. The top of the structural mat was placed at elevation 3681.5 feet (see Table 4-6) above mean sea level. This elevation was given a reference elevation of +100.00 feet, for the purpose of assigning relative building elevations.

Most of the simplified WHB is at or above the finished floor mat. Only the waste transfer pools in the ATS Process area extend below the floor mat. These waste transfer pools and transfer

aisles were assigned walls and floors having a thickness of 5 feet (see Table 4-6). The floor of the waste transfer pool is 50 feet below the finished floor mat (see Table 4-6).

The primary factor for the thickness of concrete walls and elevated floors in the WHB is radiation shielding requirements. Areas where filled waste packages will be opened require 5-foot thick concrete walls and floors to a height of 30 feet above the operating floor. From 30 feet above the operating floor to the roof, the shielding wall and floor thickness is reduced to 3 feet (see Table 4-6).

HVAC areas and areas where waste packages are not opened are braced steel frames with reinforced concrete floors. Steel columns are spaced at approximately 24 feet on centers. See sketches in Attachment II.

6.2.2 ACS SASSI-C Modeling

For this analysis, WHB configuration was characterized by two 3-dimensional finite-element structures, one for evaluation of horizontal motions and one for evaluation of vertical motions. The concrete walls, concrete slabs, steel columns, steel floor beams, and steel bracing are explicitly modeled. Concentrated masses were included to account for crane mass. Element sizes do not explicitly reflect the dimensions shown on the sketches in Attachment II. In order to maintain the ACS SASSI-C model at a size that was manageable for computer computation duration, it was necessary to specify a nominal, global grid of nodes spaced in a grid of approximately 12 feet in each horizontal direction, and then use those nodes to define the structure. For example, the pool structure base slab is designed in the sketches as a spread footing design with 5 feet overhang on the outside perimeter of the pool walls. The individual structural elements were modeled using nodes available from the global node mesh giving the closest approximation to the actual structural design found in the sketches in Attachment II.

For elevations below ground level, the structure and soil nodes must lie on the soil layer depths in Tables 4-3 and 4-5. The base of the pool was located at a depth of 52.2 feet, the closest layer elevation to the pool depth of 50 feet.

In order to envelope the seismic response, considering two finite-element structures, three directions of motion, two sets of layer data, and associated free field seismic ground motions, it was necessary to prepare six separate ACS SASSI-C input files (models), Table 6-1.

Table 6-1. ACS-SASSI-C SITE and HOUSE Files

File	Finite-Element Model	Direction of Motion	Layer Data			Direction
				Table 4-3	Table 4-5	
L12x	Horizontal	East-West	1-2 Hz	YES		X
L5x	Horizontal	East-West	5-10 Hz		YES	X
L12y	Horizontal	North-South	1-2 Hz	YES		Y
L5y	Horizontal	North-South	5-10 Hz		YES	Y
L12z	Vertical	Vertical	1-2 Hz	YES		Z
L5z	Vertical	Vertical	5-10 Hz		YES	Z

The units used in the ACS SASSI-C analysis are kip, feet, and seconds. The unit of kip (K) is equal to 1,000 pounds.

6.2.3 Soil Modeling and Free Field Earthquake Ground Motions

Earthquake ground motions data (DTN: MO0004SEPTWHB.010) and soil layer data (DTN: MO0004SEPSPWHB.011) were supplied for base case (best estimate) soil properties.

Free field earthquake ground motions were supplied as six earthquake acceleration time histories at the ground surface, two for each of three seismic directions (two horizontal and one vertical). The time histories represent two earthquakes. Two reference earthquakes were developed such that their response spectra together represent the Uniform Hazard Spectrum (UHS) with an annual probability of 10^{-4} of being exceeded. The UHS is a result of the probabilistic seismic hazard analysis (PSHA) for Yucca Mountain. One reference earthquake is scaled to match the UHS in the frequency range of 1 to 2 Hz and represents a large, relatively distant event. The other reference earthquake is scaled to match the UHS in the frequency range of 5 to 10 Hz and represents a proximate event. The two response spectra are modified to reflect the effects of site response at the Waste Handling Building site. These modified spectra together form the design response spectra and serve as the target response spectra for the development of the time histories. The six acceleration time histories are identified by Horizontal 1 (1-2 Hz), Horizontal 1 (5-10 Hz), Horizontal 2 (1-2 Hz), Horizontal 2 (5-10 Hz), Vertical (1-2 Hz), and Vertical (5-10 Hz). The two sets of horizontal acceleration time histories (Horizontal 1 and Horizontal 2) are statistically independent and may be used interchangeably to represent north/south or east/west earthquakes. The distant earthquake sources are characterized by having 81.92 seconds of motion. The proximate earthquake sources are characterized by having 40.96 seconds of motion.

Plots of the six acceleration time histories are included in Attachment I.

Layer data were provided to represent the seismic response of the soil to both the proximate and distant earthquake sources. Layer data were provided for 58 layers of varying depth to a total depth of 350 meters (1150 feet). See Attachment I for tabulation of base case (best estimate) layer data for the two suites of earthquakes.

Lower bound layer data were not available at the time of release of Revision 0 of this document. Current plans are to revise this document with updates that include data and results using lower bound layer properties and applicable ground motions.

Upper bound layer data were not available at the time of release of Revision 0 of this document. Current plans are to revise this document with updates that include data and results using upper bound layer properties and applicable ground motions.

The layers in the top 76 meters (250 feet) were provided as thirteen layers having a thickness of 5.3, 4.9, 4.9, 7.2, 8.9, 9.8, 11.2, 11.5, 21.6, 21.6, 43.3, 24.9, and 74.8 feet, respectively. For the purpose of this SSI evaluation, the 43.3-foot thick layer was divided into two layers having a

thickness of 21.6 feet and 21.7 feet, and the 74.8-foot thick layer was divided into three layers of 24.9 feet, 24.9 feet, and 25.0 feet respectively. This was done in order to satisfy the ACS SASSI-C requirement that layers have a thickness of no more than one-fifth the wavelength for the maximum frequency of interest. Given the thickness of these layers and their reported shear wave velocities (see Tables 4-3 and 4-5), the ACS SASSI-C solution is considered valid for frequencies of up to 17.2 Hertz.

Below the depth of 76 meters (250 feet) the layer properties (compression wave velocity, shear wave velocity, compression wave damping, shear wave damping, and density) approach essentially constant values approximating solid rock. For the purposes of this SSI evaluation, below a depth of 250 feet the ground was specified to be an elastic half-space with solid rock properties. The lower boundary may be placed at a layer at which the shear-wave velocity exceeds 3500 feet per second, at a layer that has a shear modulus of 10 times the shear modulus of the layer immediately below the foundation, or three times the maximum foundation width below the foundation. For these three criteria, the lower soil boundary occurs at a depth of 250 feet, below which the shear wave velocity is 5500 feet per second.

Two sets of layer profile data are provided. Table 4-3 provides values for the suite of three components for the more distant design earthquake that was developed from a reference earthquake scaled to match the UHS at 1 to 2 Hz. Table 4-5 provides values for the suite of three components for the proximate design earthquake that was developed from a reference earthquake scaled to match the UHS at 5 to 10 Hz.

For the elastic half-space material properties, a shear wave velocity of 5,500 feet per second, and a compression wave velocity 10,000 feet per second, was specified. These wave velocities are an average of the data in Tables 4-3 and 4-5 for the layers below a depth of 250 feet. These wave velocities are rounded to the nearest 500 feet per second to reflect the accuracy of the data. The density of the half-space was specified as 0.131 kips per cubic foot. The actual value given in Tables 4-3 and 4-5 is 0.137 kips per cubic foot. This deviation will not significantly influence the results and will be corrected in later evaluations.

Soil modeling in ACS SASSI -C consists of the specification of the soil in two formats.

First, the site is defined using uniform thickness horizontal soil layers on an elastic half-space. For the WHB site, the soil is defined as 16 layers on an elastic rock base. For the purposes of this simplified SSI evaluation, the top 15 feet of soil is considered engineered backfill defined in three layers. From a depth of 15 feet to a depth of 250 feet, thirteen in-situ layers are defined. Below 250 feet depth, the in-situ material is defined as an elastic half-space having rock-like properties. See Table 4-3 and Table 4-5 for the soil layer properties.

Second, the soil that is replaced by the below ground portion of the building is referred to as the 'excavated soil'. This 'excavated soil' is defined in the model using three-dimensional solid finite-elements. These 'excavated soil' elements are given the structural properties commensurate with the layers from which they were removed. For the WHB, the transfer pools are embedded in the top seven soil layers. The top of the 5-foot thick base mat of the pool is at a

depth of 50 feet below the operating deck. As noted in Section 6.2.2, the nodes defining the pool base mat are at the soil layer depth of 52.2 feet.

The thickness of each soil layer is governed by the structural properties of the soil and by the maximum frequency of interest in the SSI evaluation. Given the thickness of the soil layers and their reported shear wave velocities (see Tables 4-3 and 4-5), the ACS SASSI-C solution is considered valid for frequencies of up to 17.2 Hertz based on vertical element size.

The maximum horizontal dimension for soil elements and the maximum horizontal dimension of the structure along the soil-structure interface are also governed by the structural properties of the soil and by the maximum frequency of interest in the SSI evaluation. The maximum horizontal dimension for soil elements and for structure elements along the soil-structure interface is 14 feet. Given this maximum horizontal dimension and the minimum compression wave velocity in the soil layer three (see Table 4-3) of 1802 feet per second, the ACS SASSI-C solution is considered valid for frequencies of up to 25 Hertz ($1802 \text{ fps} / (5 \text{ ft} * 14 \text{ ft})$) based on horizontal element size.

Each ACS SASSI-C node has available 6 degrees-of-freedom (DOF), three for translation and three for rotation. The nodes that are used to define the interior of the 'excavated soil' volume have not been attached to any elements used to define the foundation of the structure. These interior soil nodes have their rotation DOF fixed and thereby removed from the stiffness matrix. All other nodes have six DOF in the stiffness matrix.

6.2.4 Foundation Modeling

The WHB foundation is made of two components, the base slab at grade elevation and the walls and base slab of the pools in the ATS Process Area.

The base slab at the grade elevation is modeled using four-node quadrilateral plate elements. For the purposes of this simplified SSI evaluation, the WHB foundation was idealized as a structural reinforced concrete mat having a uniform thickness of 5 feet. The maximum horizontal dimension of the structural mat is 14 feet to accommodate the SASSI limitation for element size at the soil-structure interface.

The waste transfer pools and transfer aisles are included only in the horizontal SSI model using four-node quadrilateral plate elements. See discussion in Section 6.2.5 for the structural modeling for the horizontal and vertical analyses. The pool walls and floors were modeled having a thickness of 5 feet. The vertical element dimension equaled the layer thickness (a SASSI requirement). The floor of the waste transfer pool is 52.2 feet below the finished floor mat in order to match the soil layer depths.

6.2.5 Structure Modeling

6.2.5.1 Horizontal Analysis Model

The WHB structure has two types of construction. Areas where filled waste packages will be opened require concrete walls and floors for radiation shielding. HVAC areas and areas where waste packages are opened under water for shielding are braced steel frames with reinforced concrete floors. See Attachment VIII for an illustration of the simplified horizontal model.

The primary factor for the thickness of concrete walls and elevated floors in the waste package handling areas is the radiation-shielding requirement. The shielding wall and floor thickness requirement is 5 feet thickness to a height of 30 feet above the operating floor. From 30 feet above the operating floor to the roof, the shielding wall and floor thickness is reduced to 3 feet. The thickness of walls in the WP Transport area is 3 feet. The shielding walls and floors are modeled using four-node quadrilateral plate elements.

The steel braced frame has columns spaced at approximately 24 feet on centers (Assumption 5.8).

The roof and floor areas of the steel-framed structure are modeled using four-node quadrilateral elements. The thickness of each of the roof structural elements is arbitrarily defined in the SASSI model as 0.333 feet thick. The thickness of each of the floor structural elements is arbitrarily defined in the SASSI model as 0.50 feet thick. Roof and floor material properties are calculated in Attachment III, using elastic modulus, Poisson's ratio, density, and material damping as analysis input. The density was calculated to apply the appropriate mass for the calculated dead load using the discretionary applied thickness. The Poisson's ratio and damping for concrete were applied. The elastic modulus for the quadrilateral plate element was calculated to give the equivalent deflection for steel beam framing.

All of the concrete slabs and walls are modeled using four-node quadrilateral elements. The thickness of each of the structural elements is defined in the ACS SASSI-C model. Concrete material properties are appropriate for normal weight structural concrete having a 28 day compressive strength of 3000 pounds per square inch, using elastic modulus, Poisson's ratio, density, and material damping as analysis input. This material is designated as MATERIAL 1 in Table 4-1.

For the concrete base slab and the interior concrete floors where permanent equipment is expected to be installed, an increased concrete density of 0.160 kips per cubic foot is used to account for equipment mass for the seismic calculations. The walls of the embedded pool also were specified as concrete density of 0.160 kips per cubic foot to account for water mass in the pools. Other concrete material properties were not changed. This material is designated as MATERIAL 2 in Table 4-1.

Steel columns, beams, and braces are modeled using two-node beam elements with a third node defining the section local axes. Area and moment of inertia properties are defined for each

element. Steel material properties are appropriate for mild ASTM A588 steel having a yield-strength of 50 kips per square inch, using elastic modulus, Poisson's ratio, density, and material damping as analysis input. Steel material is designated as MATERIAL 3 in Table 4-1.

Steel columns, beams, and braces are modeled using two-node beam elements with a third node defining the section local axes. Steel column and bracing sizes are calculated in Attachment III. Five different wide-flange sections were used in the horizontal SSI analysis to represent the columns, beams, and braces. Properties of section area and moment of inertia were specified as analysis input.

Real properties 1 through 11 in Table 4-2 are used in the horizontal SSI analysis.

Overhead bridge cranes were included in the SSI evaluation by specifying concentrated masses of the dead weight of the bridge, trolley, and hoist at appropriate locations within the WHB, in both the concrete and steel portions of the building. Crane weight, maximum wheel load, and wheel spacing for the various crane hook capacities and spans were taken from the Whiting Crane Handbook (See Mattsson 2000). Preliminary sizing of crane columns was based on these maximum wheel loads (Attachment III).

Overhead bridge cranes were identified. These cranes, hook capacity, span, and their locations are shown in Table 4-4. The crane dead weight and maximum wheel load, and wheel spacing are shown in Table 4-4.

6.2.5.2 Vertical Analysis Model

Concrete walls and steel bracing are the primary lateral seismic force resisting structural elements. The seismic loads for the design of the lateral force resisting structural elements are typically dominated by the seismic response from the horizontal analysis, and the contribution of the seismic response from the vertical analysis is typically secondary by nature. Since the purpose of the SSI analysis is to provide preliminary seismic loads for the evaluation of the feasibility of the seismic design of the WHB, it is sufficient to ignore the contribution from the vertical SSI analysis. To compensate for the effect from ignoring the small contribution from the vertical seismic loads, the seismic loads from the horizontal analysis are conservatively applied to the evaluation of the concrete walls and steel bracing in order to provide some extra design margin. For the preliminary design of the steel framing at the HVAC floor, DC handling, and hot cell areas of the WHB, however, the contributions of the seismic loads from both the horizontal and vertical analyses are expected to be comparable to each other. In this particular case, it is sufficient to estimate the local vertical seismic loads in the structural elements at these areas by means of an approximate vertical SSI analysis in which the only the HVAC floor, DC handling, and hot cell areas of the WHB are considered.

Because the vertical SSI analysis is intended only for an approximate estimate of the vertical seismic loads in the local structural elements at the HVAC floor, DC handling, and hot cell areas, the structural model includes only that portion of the base slab at grade that is within these areas. The structure model is therefore surface founded in the vertical SSI analysis because the waste

transfer pools are outside these areas. See Attachment VIII for an illustration of the simplified vertical structure model. It is identical to the portion of the horizontal structure model at these areas, except that W18x50 wide-flange floor beams and girders at the typical floor panels are explicitly included. The section properties of the W18x50 member are designated beam element property REAL 12 in the vertical model.

6.2.6 Running ACS SASSI-C

Due to the large size of the WHB model, the ACS SASSI-C frequency solution could not be completed in one run. Frequency solutions could be completed for a maximum of nine frequencies in one run. Also, due to internal programming limitations, because of the size of the WHB model, the stress solutions could be completed only for a total of 16 or fewer frequencies. Consequently, each of the six ACS SASSI-C solutions were performed according to the following outline:

1. ACS SASSI-C frequency solution using 9 or fewer frequencies in the first run.
2. Compute TRANSFER FUNCTIONS.
3. One or more additional ACS SASSI-C frequency solutions for additional frequencies up to a total of 16 or fewer frequencies.
4. COMBINE results with previous frequency solutions.
5. Compute TRANSFER FUNCTIONS for combined solution.
6. Repeat Steps 3, 4, and 5 as necessary.
7. Compute STRESS results for combined solution.

The SASSI computer code solves for structural response using user-defined frequencies. The SASSI code then interpolates between the user-defined frequency solutions to obtain solutions at all frequencies between the lowest and highest frequency specified. The TRANSFER FUNCTIONS are the plots of interpolated results at all frequencies with the user-defined frequency solutions identified. The TRANSFER FUNCTIONS for the combined solutions for the six seismic evaluations are plotted in Attachment VII.

6.2.7 Forces And Stresses

Seismic SSI force and stress results in the structural elements are documented for each of the six seismic evaluations (CRWMS M&O 2000a). For each of the two earthquake sources, proximate and distant, the force and stress results for the three perpendicular seismic components are combined by the square root of the sum of the squares (SRSS) method to compute a seismic resultant (Attachment IV).

6.2.8 Steel Column and Beam Members

Results from the SASSI seismic analysis are combined with dead load (DL) and live load (LL) to determine the load demand on members in the WHB structure (Attachment V). When evaluated against allowables for service load conditions, a 1.6 factor reduction of force/stress is allowed for load combinations including seismic (ANSI N690, Table Q1.5.7.1).

Reduced member loads are defined by the following equation:

$$\frac{1}{1.6}(DL + LL + S)$$

Steel member allowable loads are calculated in accordance with allowable stress given in the *Manual of Steel Construction, Allowable Stress Design* (AISC 1991).

Primary steel members are checked in the following areas of the WHB:

- ATS Process Area
- WP Transport Area
- Cross Transfer Area, North of WP Transport area and West of the Hot Cell area
- DC Handling Area

6.2.8.1 ATS Process Area

Allowable loads for columns and braces checked in the ATS Process Area are exceeded by large margins. Very large seismic loads are induced in the columns and bracing at the corners of this part of the building. Table 6-2 shows the preliminary column and brace sizes, the member capacity and the design load.

Table 6-2. ATS Process Area Results

Member	Preliminary Size	Allowable Load (kips)	Design Load = 1/1.6 (DL+LL+S) (kips)
Column	W24x104	538	2758
Brace	W10x49	86	1006

Two options can be investigated to bring these members into compliance with allowable loads. Member sizes can be increased. The number of braces can be increased, reducing the load on each brace and reducing the column loads.

6.2.8.2 WP Transport Area

Table 6-3 summarizes the comparison between member allowable loads and design loads for members checked in the WP Transport area.

Some of the interior and exterior columns are overloaded. The size of these members can be increased to handle the design load.

The braces at all elevations are overloaded. This can be corrected by increasing the size of the members, increasing the number of braces or a combination of both.

Floor beams and girders at all elevations are overloaded. To correct these problems, the number and/or size of the beams can be increased, and the size of the girders can be increased. Increase in the size of the girders will require coordination with the mechanical group to ensure that minimum headroom requirements are maintained.

The floor girder over the welder maintenance area is overloaded. This can be corrected by increasing the size of the girder from W21x101 to W36x182.

Table 6-3. WP Transport Area Results

Member	Preliminary Size	Allowable Load/Moment (columns, kips) (beams, ft-kips)	Design Load = 1/1.6 (DL+LL+S) (columns, kips) (beams, ft-kips)
Interior column, elev 170' to 211'	W14x61	66	42
Interior column, elev 134' to 170'	W14x90	290	286
Interior column, elev 100' to 134'	W14x90	325	489
Exterior column, elev 170' to 211'	W14x61	66	188
Brace, elev 170' to 211'	W10x49	125	219
Exterior column, elev 134' to 170'	W14x90	290	395
Brace, elev 134' to 170'	W10x49	150	174
Exterior column, elev 100' to 134'	W14x90	325	294
Brace, elev 100' to 134'	W10x49	162	205
Floor beam, elev 170'	W18x50	245	875
Floor girder, elev 170'	W21x101	626	1320
Floor beam, elev 134'	W18x50	245	880
Floor girder, elev 134'	W21x101	626	1313
Floor girder, elev 170', Welder maintenance area	W21x101	626	1220
Floor girder, elev 170', Welder maintenance area	W36x182	1714	1230

6.2.8.3 Cross Transfer Area, North of WP Transport Area and West of Hot Cell Area

Table 6-4 summarizes the comparison between member capacity and design load for members checked in the Cross Transfer area.

Some of the interior and exterior columns are overloaded. The size of these members can be increased to handle the design load.

Floor beams and girders at all elevations are overloaded. To correct these problems, the number and/or size of the beams can be increased, and the size of the girders can be increased. Increase in the size of the girders will require coordination with the mechanical group to ensure that minimum headroom requirements are maintained.

Table 6-4. Cross Transfer Area Results

Member	Preliminary Size	Allowable Load/Moment (columns, kips) (beams, ft-kips)	Design Load = 1/1.6 (DL+LL+S) (columns, kips) (beams, ft-kips)
Exterior column, elev 187' to 217'	W14x90	406	243
Floor beam, elev 187'	W18x50	245	807
Floor girder, elev 187'	W21x101	626	1344
Exterior column, elev 164' to 187'	W14x90	531.5	310
Interior column, elev 164' to 187'	W14x90	531.5	233
Floor beam, elev 164'	W18x50	245	809
Floor girder, elev 164'	W21x101	626	1293
Exterior column, elev 136' to 164'	W14x90	444	454
Interior column, elev 136' to 164'	W14x90	444	433
Floor beam, elev. 136'	W18x50	245	790
Floor girder, elev. 170	W21x101	626	1298
Exterior column, elev 100' to 136'	W14x159	598	625
Interior column, elev 100' to 136'	W14x159	598	658

6.2.8.4 DC Handling Area

Table 6-5 summarizes the comparison between member allowable load/moment and design load for members checked in the DC Handling area.

The columns on either side of the DC Handling area are overloaded. The size of these members can be increased to handle the design load.

The braces are overloaded. This can be corrected by increasing the size of the members, increasing the number of braces or a combination of both.

Table 6-5. DC Handling Area Allowable Load/Moment Results

Member	Preliminary Size	Allowable Load/Moment (columns, kips) (beams, ft-kips)	Design Load = 1/1.6 (DL+LL+S) (columns, kips) (beams, ft-kips)
Roof column	W14x61	193	644
Roof column	W14x90	406	600
Brace	W10x49	231	857

6.2.9 Plate Elements (Concrete)

Plate elements are checked in Attachment V for the ATS Process Area, the WP Transport Area, the Cross Transfer Area North of WP Transport area and West of the Hot Cell area, the DC Handling Area, and the Hot Cell Area.

The results of the ACS-SASSI-C seismic analysis (Attachment IV) comprise six principal stress and moment values for a user-selected set of plate elements in the WHB. Enveloping axial shear

stress and moment values are used in the evaluation to determine the adequacy of the proposed WHB.

The shear capacity and bending capacity of the concrete elements are checked against the factored loads of $1.0 \text{ DL} + 1.0 \text{ LL} + 1.0 \text{ S}$.

The shear evaluation consists of determining the adequacy of the members to the shearing force obtained from Attachment IV comparing this value to the maximum available shear force (Attachment V) based on ACI 349.

The shear capacity in a typical 5-foot thick concrete wall based on maximum shear reinforcement is adequate for the maximum stressed element in the WHB (Attachment V). The maximum amount of shear reinforcement allowed by ACI 349 will be required.

The moment capacity evaluation consists of determining the loads of the concrete member using the combination of axial stresses and bending moments obtained from Attachment IV. The section capacity is defined in terms of area of tensile steel reinforcement required for the face of a typical 5-foot thick element. The total area of steel reinforcement required is the sum of the area required for axial forces and the area required to resist bending moments.

Steel reinforcement requirements for a typical 5-foot thick concrete slab/wall based on enveloping axial and moment demand were checked in Attachment V. The maximum reinforcement steel area required for the face of any element is 5.8 square inches of steel per foot of 5-foot thick slab. This can be accomplished by placing 4 #11 bars per foot in each face of the slab and 2 #10 in the center of the section. By inspection of the data in Table IV-1 and Table IV-3, this heavy reinforcement is limited to the base of the pool wall.

6.2.10 Sliding

The foundation of the WHB is over 400 feet wide, 500 feet long, and embedded 5 feet deep. A 55-foot deep pool approximately 130 feet wide and 164 feet long is located on the interior of the foundation slab. In addition to the friction resistance of the grade slab, the 55-foot deep pool with 5-foot thick walls is providing a key to resist sliding by means of passive soil pressure. The lateral forces on the pool walls are inherent in the SASSI calculations and stress results. The pool walls have been found to be adequate to resist these seismic forces (Attachment V). Soil pressures on the pool walls, passive soil pressures on the ends of the foundation slab, and friction forces at the slab-to-soil interface have not been evaluated. Additional sliding resistance features (keys) can be included later in detail design if soil pressures are determined to be excessive.

6.2.11 Hydrodynamic Analysis

A preliminary simplified hydrodynamic analysis was conducted to determine a maximum sloshing height for water in the transfer channels and pools and to determine maximum seismic water pressure. See Attachment VI for the calculations. See Figure 7 in Attachment II for location of the pools.

The maximum sloshing height for structures having dimensions of the WHB channels and pools and having sufficient vertical freeboard would be over 16 feet. It can be expected that water will slosh out of the pools and transfer channels during an earthquake if less than 16 feet of freeboard is present. Additional design features (baffles) can be included in detail design to reduce sloshing.

The maximum dynamic water pressure during an earthquake is roughly equivalent to the static water pressure. The dynamic water pressure is due almost entirely to the vertical seismic component. During an earthquake, therefore, the water pressure will be roughly double the static pressure, or equivalent to the pressure at a water depth of 100 feet, twice the actual pool depth.

7. CONCLUSIONS

It is the conclusion from this preliminary simplified soil-structure-interaction analysis that the WHB can be designed for seismic loads using conventional structural design criteria for nuclear facilities. The response of the WHB structure to the potential large ground motions is within acceptable for future LA design of safety-related SSCs.

The preliminary sizes of structural members used in the seismic analysis were derived using wind conditions in Table 4-6. Many of the steel members sized for wind loads proved to be too small to resist seismic loads. Two options are available to bring these members into compliance with allowable loads. Member sizes can be increased, and the number of braces can be increased, reducing the load on each brace and reducing the column loads.

Throughout the WHB, the preliminary sized braces and columns comprising the lateral force resisting system of the braced frame are overloaded, in some locations by a considerable margin. Several design options are available to mitigate this overload condition. The number of braced bays could be increased, thereby decreasing the demand on each set of braces and columns. The size of the braces and columns could be increased, thereby increasing their capacity. The braces and columns could be braced against lateral buckling at closer spacing, thereby increasing their capacity. The braced frame could be replaced by concrete shear walls of sufficient strength. By using one or a combination of these design options, the capacity of the lateral force resisting system of the WHB can be increased to safely withstand the seismic demand.

Concrete members were sized to provide minimum nuclear shielding in the waste handling areas. These concrete wall and floors can be reinforced to withstand the seismic loads. The maximum amount of steel shear reinforcement allowed by ACI 349 is required in the high stressed areas of the structure. Heavy flexural steel reinforcement is required in the floors and walls. The amount of steel reinforcement is within the maximum allowed by ACI 349.

The foundation of the WHB is over 400 feet wide, 500 feet long, and embedded 5 feet deep. A 55-foot deep pool structure having exterior dimensions of approximately 130 feet wide and 164 feet long is located on the interior of the foundation slab (See Figure II-3). In addition to the friction resistance of the grade slab, the 55-foot deep pool with 5-foot thick walls is providing a

key to resist sliding. The lateral forces on the pool walls are inherent in the SASSI calculations and stress results. The pool walls have been found to be adequate to resist these seismic forces. Soil pressures on the pool walls, passive soil pressures on the ends of the foundation slab, and friction forces at the slab-to-soil interface have not been evaluated. Additional sliding resistance features (keys) can be included later in detail design if soil pressures are determined to be excessive.

The maximum sloshing height for structures having dimensions of the WHB channels and pools and having sufficient vertical freeboard would be over 13 feet. It can be expected that water will slosh out of the pools and transfer channels during an earthquake if less than 13 feet of freeboard is present. Additional design features (baffles) can be included in detail design to reduce sloshing.

8. INPUTS AND REFERENCES

8.1 DOCUMENTS CITED

AISC (American Institute of Steel Construction) 1991. *Manual of Steel Construction, Allowable Stress Design*. 9th Edition. Chicago, Illinois: American Institute of Steel Construction. TIC: 4254.

Bandyopandhyay, K.; Cornell, A.; Costantino, C.; Kennedy, R.; Miller, C.; and Veletsos, A. 1995. *Seismic Design and Evaluation Guidelines for the Department of Energy High-Level Waste Storage Tanks and Appurtenances*. BNL 52361. Upton, New York: Brookhaven National Laboratory. TIC: 235685.

CRWMS M&O 1997a. *MFD - Assembly Transfer System (Assembly Cask Unloading)*. BCBD00000-01717-2700-67004 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0598.

CRWMS M&O 1997b. *MFD - Assembly Transfer System (Staging and Loading)*. BCBD00000-01717-2700-67008 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0602.

CRWMS M&O 1997c. *MFD - Canister Transfer System (Large Canister)*. BCBD00000-01717-2700-67009 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0603.

CRWMS M&O 1997d. *MFD - Carrier/Cask Handling System*. BCBD00000-01717-2700-67003 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0597.

CRWMS M&O 1997e. *MFD - CPB Material Handling System*. BCBD00000-01717-2700-67002 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0596.

CRWMS M&O 1997f. *MFD - DC Handling System (Welding and Staging)*. BCBD00000-01717-2700-67011 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0605.

INPUTS AND REFERENCES, CONTINUED

CRWMS M&O 1997g. *MFD - DC Handling System (WP Transfer)*. BCB000000-01717-2700-67012 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19971029.0606.

CRWMS M&O 1997h. *Surface Nuclear Facilities Space Program Analysis*. BCB000000-01717-0200-00012 REV 01. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19980204.0138.

CRWMS M&O 1998. *Repository Surface Design Site Layout Analysis*. BCB000000-01717-0200-00007 REV 02. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19980410.0136.

CRWMS M&O 1999a. *Classification of the MGR Waste Handling Building System*. ANL-HBS-SE-000001 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19990928.0184.

CRWMS M&O 1999b. *Preliminary Geotechnical Investigation for Waste Handling Building, Yucca Mountain Site Characterization Project*. BCB000000-01717-5705-00016 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19990625.0182.

CRWMS M&O 1999c. *WHB Preliminary Earthquake Analysis for the WHB to Support SR - FY00 (Work Package 24012123M5) Q*. Activity Evaluation, November 4, 1999. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19991202.0166.

CRWMS M&O 2000a. *Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input/Output Data Files*. ANL-WHS-ST-000001 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.20000414.0075.

CRWMS M&O 2000b. *Preliminary Dynamic/Soil Structure Interaction Analysis for the Waste Handling Building*. Development Plan TDP-WHS-ST-000001 REV 01. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.20000424.0699.

CRWMS M&O 2000c. *Validation Test Report for Software ACS SASSI-C*. SAN: LV-1999-112, STN: 10125-VTR-1.1-00. Las Vegas, Nevada: CRWMS M&O. URN-0289

CRWMS M&O 2000d. *Waste Handling Building System Description Document*. SDD-HBS-SE-000001 REV 00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.20000217.0249.

DOE (U.S. Department of Energy) 2000. *Quality Assurance Requirements and Description*. DOER W-0333P, Rev. 10. Washington, D.C.: U.S. Department of Energy, Office of Civilian Radioactive Waste Management. URN-0290.

Mattsson, C.G. 2000. "Assumptions for Soil-Structure-Interaction Analysis." Interoffice correspondence from C.G. Mattsson (CRWMS M&O) to G. Wagenblast (FFS), April 27, 2000, LV.SFD.CGM.04-027a. ACC: MOL.20000427.0400.

Merritt, F.S., ed. 1983. *Standard Handbook for Civil Engineers*. 3rd Edition. New York, New York: McGraw-Hill. TIC: 206892.

INPUTS AND REFERENCES, CONTINUED

Roark, R.J. 1989. *Roark's Formulas for Stress and Strain*. 6th Edition. New York, New York: McGraw-Hill. TIC: 10191.

8.2 CODES, STANDARDS, REGULATIONS, AND PROCEDURES CITED

ACI 349-97. 1998. *Code Requirements for Nuclear Safety Related Concrete Structures (ACI 349-97) and Commentary - ACI 349R-97*. Farmington Hills, Michigan: American Concrete Institute. TIC: 237635.

ANSI/AISC N690-1984. 1984. *American National Standard for Nuclear Facilities - Steel Safety-Related Structures for Design Fabrication and Erection*. Chicago, Illinois: American Institute of Steel Construction. TIC: 4279.

ANSI/ASCE 7-95. 1996. *Minimum Design Loads for Buildings and Other Structures*. New York, New York: American Society of Civil Engineers. TIC: 236611.

AP-2.13Q, Rev. 0, ICN 2. *Technical Product Development Planning*. Washington, D.C.: U. S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: MOL.20000329.1182.

AP-3.10Q, Rev. 2, ICN 0. *Analyses and Models*. Washington, D.C.: U. S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: MOL.20000217.0246.

AP-3.12Q, Rev. 0, ICN 0. *Calculations*. Washington, D.C.: U. S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: MOL.19990702.0312.

AP-3.15, Rev. 1, ICN 1. *Managing Technical Product Inputs*. Washington, D.C.: U. S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: MOL.20000218.0069.

ICBO (International Conference of Building Officials) 1997. *1997 Uniform Building Code*. Three volumes. Whittier, California: International Conference of Building Officials. TIC: 233816; 233817; 233818.

QAP-2-0, Rev. 5. *Conduct of Activities*. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19980826.0209.

QAP-2-3, Rev. 10. *Classification of Permanent Items*. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19990316.0006.

Regulatory Guide 1.61. 1973. *Damping Values for Seismic Design of Nuclear Power Plants*. Washington, D.C.: U.S. Nuclear Regulatory Commission. Readily Available

INPUTS AND REFERENCES, CONTINUED

8.3 SOURCE DATA, LISTED BY DATA TRACKING NUMBER

MO0004SEPSPWHB.011. Preliminary Seismic Design Strain Compatible Properties for the Waste Handling Building (Point D). Submittal date: 04/12/2000. Submit to RPC URN-0287

MO0004SEPTHWHB.010. Preliminary Seismic Design Acceleration Time Histories for the Waste Handling Building (Point D). Submittal date: 04/07/2000. Submit to RPC URN-0288

MO9812SCCT1SAT.000. Space and Time. Submittal date: 12/24/1998.

MO9812SCCT2MCU.000. Mechanical Units. Submittal date: 12/24/1998.

9. ATTACHMENTS

- I Layer Data and Acceleration Time Histories
- II WHB Seismic Analysis Figures
- III Preliminary Member Sizes and Dead Load, Live Load Wind Calculations
- IV Seismic Load Combination, SRSS of Directional Results
- V Dead Load+Live Load+Seismic Load Combination
- VI Hydrodynamic Data
- VII Plots of Transfer Functions
- VIII ACS-SASSI-C Plots of Horizontal and Vertical Modes

ATTACHMENT I

LAYER DATA

And

ACCELERATION TIME HISTORIES

Data in Attachment I are a tabulation and plot of data from
DTN: MO0004SEPTWHB.010 and DTN: MO0004SEPSPWHB.011. These data are
used as input to the SSI analysis.

BASE CASE LAYER DATA FOR DISTANT EARTHQUAKES 1-2 HZ

Data from DTN: MO0004SESPWHB.011

Layer	Thickness	Depth	Unit Weight	P-Wave Velocity	S-Wave Velocity	P-Wave Damping	S-Wave Damping
	m	m	Gms/cm**3	Km/sec	Km/sec	%	%
L	1	1.60E+00	2.10E+00	5.49E-01	2.42E-01	5.00E-01	2.35E+00
L	2	1.50E+00	2.10E+00	5.49E-01	1.77E-01	5.00E-01	4.87E+00
L	3	1.50E+00	2.10E+00	5.49E-01	1.42E-01	5.00E-01	6.66E+00
L	4	2.20E+00	1.80E+00	8.10E-01	3.35E-01	5.00E-01	4.29E+00
L	5	2.70E+00	2.00E+00	9.26E-01	3.95E-01	5.00E-01	4.01E+00
L	6	3.00E+00	2.00E+00	1.06E+00	4.58E-01	5.00E-01	3.92E+00
L	7	3.40E+00	2.00E+00	1.14E+00	4.81E-01	5.00E-01	4.09E+00
L	8	3.50E+00	2.00E+00	1.23E+00	5.23E-01	5.00E-01	4.17E+00
L	9	6.60E+00	2.00E+00	1.41E+00	6.59E-01	5.00E-01	1.86E+00
L	10	6.60E+00	1.20E+00	1.41E+00	6.21E-01	5.00E-01	2.78E+00
L	11	1.32E+01	1.20E+00	1.45E+00	6.77E-01	5.00E-01	7.68E-01
L	12	7.60E+00	1.20E+00	1.57E+00	8.40E-01	5.00E-01	6.77E-01
L	13	2.28E+01	2.10E+00	1.57E+00	8.49E-01	5.00E-01	5.62E-01
L	14	3.17E+01	2.10E+00	2.98E+00	1.63E+00	5.00E-01	4.27E-01
L	15	1.43E+02	2.20E+00	2.93E+00	1.71E+00	5.00E-01	5.00E-01
L	16	6.00E-01	2.20E+00	2.90E+00	1.70E+00	5.00E-01	5.00E-01
L	17	2.90E+00	2.20E+00	2.95E+00	1.72E+00	5.00E-01	5.00E-01
L	18	3.00E-01	2.20E+00	2.96E+00	1.73E+00	5.00E-01	5.00E-01
L	19	4.00E-01	2.20E+00	2.93E+00	1.71E+00	5.00E-01	5.00E-01
L	20	4.70E+00	2.20E+00	2.95E+00	1.72E+00	5.00E-01	5.00E-01
L	21	4.00E+00	2.20E+00	2.95E+00	1.70E+00	5.00E-01	5.00E-01
L	22	1.66E+01	2.20E+00	2.93E+00	1.69E+00	5.00E-01	5.00E-01
L	23	3.80E+00	2.20E+00	2.98E+00	1.71E+00	5.00E-01	5.00E-01
L	24	2.90E+00	2.20E+00	3.02E+00	1.73E+00	5.00E-01	5.00E-01
L	25	1.90E+00	2.20E+00	3.04E+00	1.74E+00	5.00E-01	5.00E-01
L	26	2.30E+00	2.20E+00	3.02E+00	1.73E+00	5.00E-01	5.00E-01
L	27	2.60E+00	2.20E+00	3.03E+00	1.72E+00	5.00E-01	5.00E-01
L	28	2.10E+00	2.20E+00	3.00E+00	1.73E+00	5.00E-01	5.00E-01
L	29	2.10E+00	2.20E+00	3.02E+00	1.75E+00	5.00E-01	5.00E-01
L	30	1.40E+00	2.20E+00	2.95E+00	1.71E+00	5.00E-01	5.00E-01
L	31	4.00E-01	2.20E+00	3.04E+00	1.76E+00	5.00E-01	5.00E-01
L	32	7.30E+00	2.20E+00	3.11E+00	1.80E+00	5.00E-01	5.00E-01
L	33	2.10E+00	3.09E+02	3.08E+00	1.78E+00		5.00E-01
L	34	1.90E+00	3.11E+02	3.13E+00	1.78E+00		5.00E-01
L	35	7.00E-01	3.12E+02	3.22E+00	1.81E+00		5.00E-01
L	36	1.40E+00	3.13E+02	3.15E+00	1.85E+00		5.00E-01
L	37	7.00E-01	3.14E+02	3.10E+00	1.81E+00		5.00E-01
L	38	1.30E+00	3.15E+02	3.13E+00	1.78E+00		5.00E-01
L	39	2.20E+00	3.18E+02	3.16E+00	1.80E+00		5.00E-01
L	40	2.20E+00	3.20E+02	3.21E+00	1.81E+00		5.00E-01
L	41	5.00E-01	3.20E+02	3.29E+00	1.84E+00		5.00E-01
L	42	1.80E+00	3.22E+02	3.34E+00	1.88E+00		5.00E-01
L	43	2.00E-01	3.22E+02	3.28E+00	1.91E+00		5.00E-01
L	44	2.30E+00	3.25E+02	3.26E+00	1.87E+00		5.00E-01
L	45	1.50E+00	3.26E+02	3.16E+00	1.86E+00		5.00E-01
L	46	3.90E+00	3.30E+02	3.00E+00	1.81E+00		5.00E-01
L	47	1.50E+00	3.32E+02	2.97E+00	1.72E+00		5.00E-01
L	48	4.00E-01	3.32E+02	2.67E+00	1.70E+00		5.00E-01
L	49	4.00E-01	3.32E+02	2.61E+00	1.54E+00		5.00E-01
L	50	2.40E+00	3.35E+02	2.52E+00	1.51E+00		5.00E-01
L	51	9.00E-01	3.36E+02	2.64E+00	1.47E+00		5.00E-01
L	52	8.00E-01	3.36E+02	2.57E+00	1.53E+00		5.00E-01
L	53	3.30E+00	3.40E+02	2.44E+00	1.49E+00		5.00E-01
L	54	5.00E-01	3.40E+02	2.06E+00	1.43E+00		5.00E-01
L	55	1.40E+00	3.42E+02	2.58E+00	1.41E+00		5.00E-01
L	56	2.40E+00	3.44E+02	2.32E+00	1.20E+00		5.00E-01
L	57	3.00E-01	3.44E+02		1.50E+00		
L	58	5.20E+00	3.49E+02		1.35E+00		

BASE CASE LAYER DATA FOR PROXIMATE EARTHQUAKES 5-10 HZ

Data from DTN: MO0004SESPWHB.011

	Layer	Thickness (Note 2)	Depth (Note 2)	Unit Weight (Note 3)	P-Wave Velocity (Note 4)	S-Wave Velocity (Note 4)	P-Wave Damping Ratio	S-Wave Damping Ratio
		m	m	Gms/cm**3	km/sec	km/sec	%	%
L	1	1.60E+00	1.60E+00	2.10E+00	5.54E-01	2.36E-01	5.00E-01	2.72E+00
L	2	1.50E+00	3.10E+00	2.10E+00	5.54E-01	1.64E-01	5.00E-01	6.08E+00
L	3	1.50E+00	4.60E+00	2.10E+00	5.54E-01	1.28E-01	5.00E-01	8.34E+00
L	4	2.20E+00	6.80E+00	1.80E+00	8.11E-01	3.27E-01	5.00E-01	4.96E+00
L	5	2.70E+00	9.50E+00	2.00E+00	9.39E-01	3.87E-01	5.00E-01	4.55E+00
L	6	3.00E+00	1.25E+01	2.00E+00	1.08E+00	4.49E-01	5.00E-01	4.44E+00
L	7	3.40E+00	1.59E+01	2.00E+00	1.15E+00	4.74E-01	5.00E-01	4.58E+00
L	8	3.50E+00	1.94E+01	2.00E+00	1.25E+00	5.16E-01	5.00E-01	4.61E+00
L	9	6.60E+00	2.60E+01	2.00E+00	1.41E+00	6.57E-01	5.00E-01	1.96E+00
L	10	6.60E+00	3.26E+01	1.20E+00	1.41E+00	6.19E-01	5.00E-01	2.97E+00
L	11	1.32E+01	4.58E+01	1.20E+00	1.45E+00	6.77E-01	5.00E-01	7.83E-01
L	12	7.60E+00	5.34E+01	1.20E+00	1.60E+00	8.42E-01	5.00E-01	6.76E-01
L	13	2.28E+01	7.62E+01	2.10E+00	1.60E+00	8.50E-01	5.00E-01	5.63E-01
L	14	3.17E+01	1.08E+02	2.10E+00	3.02E+00	1.63E+00	5.00E-01	4.29E-01
L	15	1.43E+02	2.51E+02	2.20E+00	2.95E+00	1.71E+00	5.00E-01	5.00E-01
L	16	6.00E-01	2.52E+02	2.20E+00	2.93E+00	1.70E+00	5.00E-01	5.00E-01
L	17	2.90E+00	2.55E+02	2.20E+00	2.97E+00	1.72E+00	5.00E-01	5.00E-01
L	18	3.00E-01	2.55E+02	2.20E+00	2.98E+00	1.73E+00	5.00E-01	5.00E-01
L	19	4.00E-01	2.55E+02	2.20E+00	2.95E+00	1.71E+00	5.00E-01	5.00E-01
L	20	4.70E+00	2.60E+02	2.20E+00	2.97E+00	1.72E+00	5.00E-01	5.00E-01
L	21	4.00E+00	2.64E+02	2.20E+00	2.92E+00	1.70E+00	5.00E-01	5.00E-01
L	22	1.66E+01	2.81E+02	2.20E+00	2.91E+00	1.69E+00	5.00E-01	5.00E-01
L	23	3.80E+00	2.84E+02	2.20E+00	2.94E+00	1.71E+00	5.00E-01	5.00E-01
L	24	2.90E+00	2.87E+02	2.20E+00	2.98E+00	1.73E+00	5.00E-01	5.00E-01
L	25	1.90E+00	2.89E+02	2.20E+00	3.00E+00	1.74E+00	5.00E-01	5.00E-01
L	26	2.30E+00	2.91E+02	2.20E+00	2.98E+00	1.73E+00	5.00E-01	5.00E-01
L	27	2.60E+00	2.94E+02	2.20E+00	2.96E+00	1.72E+00	5.00E-01	5.00E-01
L	28	2.10E+00	2.96E+02	2.20E+00	2.98E+00	1.73E+00	5.00E-01	5.00E-01
L	29	2.10E+00	2.98E+02	2.20E+00	3.01E+00	1.75E+00	5.00E-01	5.00E-01
L	30	1.40E+00	3.00E+02	2.20E+00	2.94E+00	1.71E+00	5.00E-01	5.00E-01
L	31	4.00E-01	3.00E+02	2.20E+00	3.03E+00	1.76E+00	5.00E-01	5.00E-01
L	32	7.30E+00	3.07E+02	2.20E+00	3.10E+00	1.80E+00	5.00E-01	5.00E-01
L	33	2.10E+00	3.09E+02		3.07E+00	1.78E+00		5.00E-01
L	34	1.90E+00	3.11E+02		3.06E+00	1.78E+00		5.00E-01
L	35	7.00E-01	3.12E+02		3.11E+00	1.81E+00		5.00E-01
L	36	1.40E+00	3.13E+02		3.19E+00	1.85E+00		5.00E-01
L	37	7.00E-01	3.14E+02		3.12E+00	1.81E+00		5.00E-01
L	38	1.30E+00	3.15E+02		3.07E+00	1.78E+00		5.00E-01
L	39	2.20E+00	3.18E+02		3.10E+00	1.80E+00		5.00E-01
L	40	2.20E+00	3.20E+02		3.13E+00	1.81E+00		5.00E-01
L	41	5.00E-01	3.20E+02		3.17E+00	1.84E+00		5.00E-01
L	42	1.80E+00	3.22E+02		3.24E+00	1.88E+00		5.00E-01
L	43	2.00E-01	3.22E+02		3.29E+00	1.91E+00		5.00E-01
L	44	2.30E+00	3.25E+02		3.23E+00	1.87E+00		5.00E-01
L	45	1.50E+00	3.26E+02		3.21E+00	1.86E+00		5.00E-01
L	46	3.90E+00	3.30E+02		3.11E+00	1.81E+00		5.00E-01
L	47	1.50E+00	3.32E+02		2.97E+00	1.72E+00		5.00E-01
L	48	4.00E-01	3.32E+02		2.93E+00	1.70E+00		5.00E-01
L	49	4.00E-01	3.32E+02		2.66E+00	1.54E+00		5.00E-01
L	50	2.40E+00	3.35E+02		2.61E+00	1.51E+00		5.00E-01
L	51	9.00E-01	3.36E+02		2.53E+00	1.47E+00		5.00E-01
L	52	8.00E-01	3.36E+02		2.63E+00	1.53E+00		5.00E-01
L	53	3.30E+00	3.40E+02		2.57E+00	1.49E+00		5.00E-01
L	54	5.00E-01	3.40E+02		2.47E+00	1.43E+00		5.00E-01
L	55	1.40E+00	3.42E+02		2.44E+00	1.41E+00		5.00E-01
L	56	2.40E+00	3.44E+02		2.06E+00	1.20E+00		5.00E-01
L	57	3.00E-01	3.44E+02			1.50E+00		
L	58	5.20E+00	3.49E+02			1.35E+00

ATTACHMENT II

WHB Seismic Analysis Figures

Figure Number	Title	Page
1	Foundation Plan Slabs at El. 50+0	II-3
2	Foundation Plan Slab at El. 100+0	II-4
3	Plan – Slabs Above El. 100+0 to El. 170+0	II-5
4	Plan – Slabs Above El. 170+0 to El. 187+0	II-6
5	Plan – Slabs Above El. 187+0	II-7
6	Plan – Walls Below El. 100+0	II-8
7	Plan – Walls at El. 100+0	II-9
8	Plan – Walls at El. 132+0	II-10
9	Plan – Walls at El. 187+0 to El. 217+0	II-11
10	Partial Plan @ El. 100+0	II-12
11	Section – Assembly Transfer	II-13
12	Section – Canister Transfer	II-14
13	Section – WP Transport	II-15
14	Section – HVAC Area	II-16
15	Section – Disposal Container Handling Cell	II-17
16	Section ATS CTS Hot Cells	II-18
17	Section ATS Pools and CTS Off-Normal	II-19
18	Section – Remediation Cell	II-20

FOUNDATION PLAN - SLABS @ EL. 50+0

FIGURE 1
FOUNDATION PLAN
SLABS AT EL. 50+0

PLAN - SLABS ABOVE EL. 100+0 TO EL. 170+0

FIGURE 3
PLAN - SLABS ABOVE
EL. 100+0 TO EL. 170+0

FIGURE 4
PLAN - SLABS ABOVE
EL. 170+0 TO EL. 187+0

PLAN - WALLS BELOW EL. 100+0

FIGURE 6
PLAN - WALLS BELOW
EL. 100+0

PLAN - WALLS @ EL. 100+0

FIGURE 7
PLAN - WALLS AT
EL. 100+0

PLAN - WALLS @ EL. 132+0

FIGURE 8
PLAN - WALLS AT
EL. 132+0

PLAN - WALLS @ EL. 187+0 TO EL. 217+0

FIGURE 9
PLAN - WALLS AT
EL. 187+0 TO EL. 217+0

PARTIAL PLAN @ EL. 100+0
(WALLS @ EL. 100+0 & EL. 124+0)

FIGURE 10
PARTIAL PLAN @ EL. 100+0

FIGURE 11
SECTION - ASSEMBLY TRANSFER

FIGURE 12
SECTION - CANISTER TRANSFER

FIGURE 13
SECTION - WP TRANSPORT

SECTION - HVAC AREA (D)

FIGURE 14
SECTION - HVAC AREA

SECTION - DISPOSAL CONTAINER HANDLING CELL (E)

FIGURE 15
SECTION - DISPOSAL CONTAINER
HANDLING CELL

SECTION - ATS AND CTS HOT CELLS (F)

FIGURE 16
SECTION
ATS AND CTS HOT CELLS

SECTION - ATS POOLS AND CTS OFF-NORMAL (G)

FIGURE 17
SECTION
ATS POOLS AND CTS OFF-NORMAL

SECTION - REMEDIATION CELL (H)

FIGURE 18
SECTION -
REMEDICATION CELL

OFFICE OF CIVILIAN RADIOACTIVE WASTE MANAGEMENT
SPECIAL INSTRUCTION SHEET

1. QA: QA

Page: 1 of: 1

Complete Only Applicable Items

This is a placeholder page for records that cannot be scanned or microfilmed

2. Record Date
05/08/2000

3. Accession Number

ATTP

MDL-20000504-0319

4. Author Name(s)
Gary Wagenblast

5. Author Organization
N/A

6. Title
CD: TITLE PRELIMINARY DYNAMIC SOIL STRUCTURE - INTERACTION ANALYSIS FOR THE WASTE HANDLING BUILDING, ATTACHMENT III (PRELIMINARY MEMBER SIZES AND DEAD LOAD LIVE LOAD WIND CALCULATIONS) ATTACHMENT IV (DEAD LOAD AND LIVE LOAD AND SEISMIC LOAD COMBINATION)
V S-9-CC 18

7. Document Number(s)
ANL-WHS-ST-000001

8. Version
REV. 00

9. Document Type
CD-ROM

DATA 18-100

10. Medium

DISK 18-100

11. Access Control Code

PUB

12. Traceability Designator
DC #23483

13. Comments

THIS IS A ONE OF A KIND SPECIAL PROCESS DISK AND CAN BE LOCATED THROUGH THE RPC

18-580

ATTACHMENT IV

Seismic Load Combination, SRSS of Directional Results

Attachment IV is the combination of seismic loads into a seismic resultant by the SRSS method.

Table IV-1: Plate Elements L5

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
62	1	5.0	SXX=	-8.76E+00	-1.64E+01				18.57
			SYX=	-1.79E+01	2.06E+01				27.23
			SXY=	8.05E+01	-1.75E+01				82.35
			MXX=	-1.05E+02	-8.01E+01				132.17
			MYX=	4.74E+01	-1.71E+02				177.73
			MYX=	-1.65E+02	9.64E+01				191.12
63	1	5.0	SXX=	5.70E+01	-1.11E+01				58.06
			SYX=	-1.76E+01	1.51E+01				23.17
			SXY=	5.80E+01	-1.38E+01				59.59
			MXX=	5.03E+01	1.56E+02				164.27
			MYX=	5.19E+01	1.32E+02				141.54
			MYX=	-4.53E+01	-2.43E+02				246.90
64	1	5.0	SXX=	3.23E+01	7.46E+00				33.16
			SYX=	-2.37E+01	-8.38E+00				25.11
			SXY=	3.07E+01	-9.92E+00				32.30
			MXX=	-2.68E+02	-2.01E+02				334.64
			MYX=	-6.29E+01	8.89E+01				108.93
			MYX=	3.62E+01	-1.77E+02				180.97
171	1	5.0	SXX=	-1.04E+01	-4.63E+00				11.36
			SYX=	-1.62E+01	2.87E+01				32.95
			SXY=	2.24E+01	-3.82E+00				22.70
			MXX=	1.76E+02	2.92E+02				340.49
			MYX=	1.57E+02	-4.50E+02				476.76
			MYX=	1.25E+02	1.90E+02				227.51
172	1	5.0	SXX=	2.49E+01	-4.26E+00				25.21
			SYX=	-2.80E+01	2.66E+01				38.59
			SXY=	1.21E+01	1.85E+01				22.07
			MXX=	3.44E+02	-4.35E+02				554.52
			MYX=	2.45E+02	-4.64E+02				524.44
			MYX=	-1.21E+02	1.84E+02				220.25
12	2	5.0	SXX=	1.06E+00	-2.66E+01				26.58
			SYX=	7.64E-01	-4.61E+01				46.13

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SXY=	-7.83E+00	6.26E-01				7.85
			MXX=	-3.07E+00	1.07E+02				106.74
			MYY=	-9.25E+00	3.27E+02				327.03
			MXY=	-1.53E+01	7.71E-01				15.34
27	2	5.0	SXX=	1.20E+00	-8.96E+00				9.04
			SYX=	2.83E+00	-5.77E+01				57.72
			SXY=	2.54E+01	2.48E+00				25.56
			MXX=	3.36E+00	-2.90E+02				289.92
			MYY=	-1.29E+01	-9.61E+02				960.69
			MXY=	1.23E+01	1.71E+00				12.43
42	2	5.0	SXX=	1.10E+00	7.89E+00				7.97
			SYX=	2.58E+00	-3.19E+01				32.00
			SXY=	1.34E+01	-2.39E+00				13.57
			MXX=	7.03E+00	-1.77E+02				177.44
			MYY=	-2.46E+01	-6.32E+02				632.78
			MXY=	8.52E+00	-1.64E+00				8.67
57	2	5.0	SXX=	9.33E-01	1.57E+01				15.68
			SYX=	9.46E-01	-1.46E+01				14.67
			SXY=	1.15E+01	6.74E-01				11.56
			MXX=	-2.25E+00	1.78E+02				178.31
			MYY=	-6.22E+00	-4.92E+02				492.14
			MXY=	1.61E+01	1.37E+00				16.19
90	2	5.0	SXX=	1.22E+00	1.26E+01				12.66
			SYX=	1.26E+00	5.87E+01				58.75
			SXY=	-5.07E+01	2.51E+00				50.74
			MXX=	-3.93E+00	-2.62E+02				261.93
			MYY=	2.10E+01	9.23E+02				922.84
			MXY=	-3.27E+01	-5.32E+00				33.10
100	2	5.0	SXX=	-8.55E+00	1.31E+01				15.60
			SYX=	-4.49E+00	7.69E+00				8.90
			SXY=	-8.19E+00	-3.05E+01				31.55
			MXX=	1.09E+02	9.97E+01				147.65
			MYY=	2.62E+02	-1.08E+02				283.37
			MXY=	6.60E+01	9.75E+01				117.74
106	2	5.0	SXX=	6.71E+00	1.39E+01				15.41
			SYX=	4.95E+00	9.18E+00				10.43
			SXY=	7.59E+00	-3.21E+01				32.94

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MXX=	1.04E+02	-9.54E+01				141.06
			MYX=	2.59E+02	1.27E+02				288.15
			MYY=	6.21E+01	-1.11E+02				126.95
119	2	5.0	SXX=	-7.68E-01	6.45E+00				6.49
			SYX=	-2.51E+00	-3.23E+01				32.38
			SXY=	1.81E+01	-1.61E+00				18.14
			MXX=	4.21E+00	1.50E+02				149.96
			MYX=	1.86E+01	-6.83E+02				683.35
			MYY=	2.82E+01	5.68E+00				28.81
9	3	5.0	SXX=	1.14E+00	1.36E+01				13.64
			SYX=	-9.33E-01	-1.25E+01				12.54
			SXY=	-5.75E+01	2.42E+00				57.50
			MXX=	9.24E+00	-1.29E+02				129.43
			MYX=	1.88E+01	9.41E+02				941.39
			MYY=	-2.26E+01	-3.74E+00				22.93
41	3	5.0	SXX=	8.33E-01	5.87E+00				5.92
			SYX=	2.36E+00	-2.73E+01				27.39
			SXY=	-1.84E+01	-1.39E+00				18.42
			MXX=	-7.09E+00	-1.76E+02				175.84
			MYX=	-1.46E+01	3.34E+02				334.52
			MYY=	2.42E+01	-3.61E+00				24.51
10	4	5.0	SXX=	-1.23E+00	1.53E+01				15.36
			SYX=	-9.57E-01	-2.64E+01				26.38
			SXY=	-6.34E+01	2.72E+00				63.47
			MXX=	1.78E+01	2.08E+02				208.56
			MYX=	3.09E+01	-7.65E+02				765.32
			MYY=	-9.07E+00	3.13E+00				9.59
45	4	5.0	SXX=	4.71E-01	7.67E+00				7.68
			SYX=	1.78E+00	-3.85E+01				38.55
			SXY=	-1.94E+01	-1.48E+00				19.43
			MXX=	-1.20E+01	4.09E+02				409.57
			MYX=	-2.51E+01	-7.25E+02				724.93
			MYY=	2.04E+01	-2.99E+00				20.58
10	5	5.0	SXX=	1.41E+00	-1.22E+01				12.27
			SYX=	-5.96E-01	-2.86E+01				28.59
			SXY=	-6.85E+01	2.37E+00				68.55
			MXX=	1.59E+01	-1.52E+02				152.33

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MYX=	2.31E+01	4.65E+02				465.87
			MYX=	-1.27E+01	3.99E+00				13.30
45	5	5.0	SXX=	-5.53E-01	-1.30E+01				13.02
			SYX=	-1.21E+00	3.81E+01				38.15
			SXY=	-2.07E+01	1.72E+00				20.81
			MXX=	1.28E+01	3.86E+02				386.01
			MYX=	-2.11E+01	-8.18E+02				818.57
			MYX=	1.36E+01	-5.62E+00				14.75
11	6	5.0	SXX=	-1.67E+00	9.40E+00				9.54
			SYX=	-3.98E-01	2.06E+01				20.61
			SXY=	-7.32E+01	2.54E+00				73.24
			MXX=	1.00E+01	-1.48E+02				148.04
			MYX=	1.87E+01	-3.20E+02				320.55
			MYX=	2.89E+01	3.64E+00				29.15
49	6	5.0	SXX=	-1.12E+00	-1.88E+01				18.87
			SYX=	1.01E+00	-3.23E+01				32.32
			SXY=	-2.21E+01	-1.19E+00				22.12
			MXX=	-2.13E+01	2.63E+02				263.96
			MYX=	-1.48E+01	-4.69E+02				469.63
			MYX=	-1.88E+01	3.80E+00				19.22
11	7	5.0	SXX=	1.90E+00	1.13E+01				11.45
			SYX=	7.99E-01	-2.27E+01				22.69
			SXY=	-7.59E+01	2.74E+00				75.98
			MXX=	-3.96E+00	-1.40E+02				139.56
			MYX=	8.44E+00	-4.79E+02				478.77
			MYX=	4.43E+01	5.43E+00				44.61
49	7	5.0	SXX=	-1.36E+00	-2.45E+01				24.56
			SYX=	8.01E-01	2.39E+01				23.95
			SXY=	-2.23E+01	-1.12E+00				22.31
			MXX=	-5.44E+00	-1.36E+02				136.41
			MYX=	-7.26E+00	-1.01E+02				101.36
			MYX=	-2.40E+01	4.77E+00				24.44
12	8	5.0	SXX=	2.02E+00	2.53E+01				25.39
			SYX=	1.34E+00	1.66E+01				16.61
			SXY=	-8.05E+01	2.62E+00				80.56
			MXX=	-5.19E+00	2.42E+02				241.76
			MYX=	-2.28E+01	8.41E+02				841.31

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MXV=	5.87E+01	4.27E+00				58.84
53	8	5.0	SXX=	9.06E-01	2.66E+01				26.62
			SYV=	1.94E+00	-3.35E+00				3.87
			SXY=	-2.37E+01	9.44E-01				23.73
			MXV=	-2.73E+00	9.35E+01				93.57
			MYV=	-1.45E+01	-5.02E+02				502.21
			MXV=	-2.90E+01	-2.76E+00				29.13
23	9	5.0	SXX=	1.04E+01	-1.10E+01	3	1	-1.51E+00	15.22
			SYV=	-1.26E+00	4.80E+00			-1.07E+00	5.07
			SXY=	6.59E+00	-2.51E+00			2.17E-01	7.06
			MXV=	1.44E+01	1.02E+01			-4.11E+01	44.74
			MYV=	-1.71E+01	-1.02E+01			2.80E+01	34.32
			MXV=	7.82E+00	1.53E+01			4.23E+01	45.67
24	9	5.0	SXX=	9.63E+00	-1.58E+01	4	1	-2.13E+00	18.64
			SYV=	-1.28E+00	4.17E+00			1.19E+00	4.52
			SXY=	6.61E+00	-2.96E+00			-3.41E-01	7.25
			MXV=	3.54E+01	-2.00E+01			-6.87E+01	79.86
			MYV=	-1.80E+01	1.16E+01			3.74E+01	43.05
			MXV=	-1.01E+01	-1.97E+01			-5.13E+01	55.87
50	9	5.0	SXX=	9.29E+00	-9.28E+00	12	1	-2.23E+00	13.31
			SYV=	-2.11E+00	7.97E+00			-2.11E+00	8.51
			SXY=	1.14E+01	-6.31E+00			-5.56E-01	13.07
			MXV=	1.65E+01	-1.40E+01			-4.72E+01	51.87
			MYV=	6.33E+01	3.28E+01			-5.68E+01	91.16
			MXV=	-8.08E+00	1.74E+01			2.10E+01	28.40
51	9	5.0	SXX=	7.95E+00	-1.35E+01	13	1	-2.30E+00	15.86
			SYV=	-2.67E+00	6.52E+00			-1.93E+00	7.30
			SXY=	1.24E+01	-7.90E+00			-9.32E-01	14.72
			MXV=	3.55E+01	1.60E+01			-6.51E+01	75.86
			MYV=	-4.14E+01	2.96E+01			-6.86E+01	85.41
			MXV=	1.32E+01	-2.27E+01			2.67E+01	37.46
77	9	5.0	SXX=	8.18E+00	-6.42E+00	21	1	-2.43E+00	10.68
			SYV=	4.38E+00	1.22E+01			2.77E+00	13.28
			SXY=	1.55E+01	-9.96E+00			-1.20E+00	18.44
			MXV=	2.43E+01	4.85E+01			2.59E+01	60.08
			MYV=	-2.37E+01	-2.72E+01			-4.77E+01	59.82
			MXV=	1.23E+01	2.74E+01			-2.86E+01	41.39

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
78	9	5.0	SXX=	-7.02E+00	-1.08E+01	22	1	-2.56E+00	13.15
			SYX=	-4.92E+00	8.21E+00			2.65E+00	9.93
			SXY=	1.84E+01	-1.29E+01			-1.18E+00	22.53
			MXX=	2.58E+01	1.49E+01			-4.25E+01	51.88
			MYX=	-2.50E+01	-2.44E+01			-6.74E+01	75.91
			MXZ=	-1.94E+01	-3.14E+01			-1.81E+01	41.08
104	9	5.0	SXX=	-8.63E+00	-3.56E+00	29	1	-2.67E+00	9.70
			SYX=	6.74E+00	1.95E+01			2.78E+00	20.79
			SXY=	2.42E+01	-1.71E+01			-1.54E+00	29.68
			MXX=	1.01E+02	1.14E+02			7.13E+01	168.14
			MYX=	1.87E+02	1.76E+02			2.12E+02	333.17
			MXZ=	-2.53E+01	-5.33E+01			5.34E+01	79.53
105	9	5.0	SXX=	8.06E+00	-1.32E+01	30	1	-3.62E+00	15.84
			SYX=	5.86E+00	8.69E+00			2.80E+00	10.85
			SXY=	2.17E+01	-1.67E+01			-1.07E+00	27.38
			MXX=	1.24E+01	1.65E+01			5.95E+01	62.97
			MYX=	1.22E+02	7.44E+01			2.08E+02	252.26
			MXZ=	-3.72E+01	3.26E+01			-5.61E+01	74.78
108	9	5.0	SXX=	-7.62E+00	-1.47E+01	33	1	4.44E+00	17.18
			SYX=	-8.83E+00	1.05E+01			-3.50E+00	14.18
			SXY=	2.21E+01	8.33E+00			1.37E+00	23.61
			MXX=	-5.94E+01	7.18E+01			6.01E+01	110.85
			MYX=	-4.76E+01	8.14E+01			9.52E+01	133.97
			MXZ=	-1.19E+01	4.08E+01			-3.53E+01	55.26
10	10	5.0	SXX=	-1.02E+01	-3.31E+00	4	2	-2.92E+00	11.10
			SYX=	-8.71E+00	9.07E+00			-2.99E+00	12.92
			SXY=	-9.11E+00	1.21E+01			-1.23E+00	15.15
			MXX=	2.42E+01	4.65E+01			-4.25E+01	67.51
			MYX=	9.49E+01	1.48E+02			-1.58E+02	236.52
			MXZ=	3.21E+01	-4.52E+01			-4.28E+01	70.01
130	10	5.0	SXX=	-7.34E+00	5.00E+00	28	2	2.12E+00	9.13
			SYX=	-7.26E+00	1.12E+01			-2.37E+00	13.52
			SXY=	-5.37E+00	8.43E+00			1.03E+00	10.05
			MXX=	2.01E+01	5.38E+01			-3.33E+01	66.39
			MYX=	4.32E+01	-3.85E+01			-9.37E+01	110.15
			MXZ=	-9.96E+00	-3.96E+01			-4.00E+00	41.03

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
250	10	5.0	SXX=	-8.41E+00	-4.42E+00	52	2	2.68E+00	9.87
			SYX=	-5.98E+00	-1.19E+01			2.66E+00	13.56
			SXY=	3.44E+00	-9.45E+00			-9.92E-01	10.10
			MXX=	-1.25E+01	4.16E+01			3.93E+01	58.57
			MYX=	-3.52E+01	-7.91E+01			1.51E+02	174.11
			MXZ=	1.30E+01	3.72E+01			2.98E+01	49.40
10	11	5.0	SXX=	-9.08E+00	-3.99E+00	4	3	-2.90E+00	10.34
			SYX=	-5.88E+00	-1.35E+01			-3.58E+00	15.11
			SXY=	-2.02E+01	-7.96E+00			2.93E-01	21.70
			MXX=	-1.43E+01	-3.46E+01			-2.38E+01	44.30
			MYX=	4.30E+01	-1.49E+02			-1.02E+02	185.77
			MXZ=	-8.44E+00	-2.98E+01			3.01E+01	43.15
241	11	5.0	SXX=	-7.14E+00	9.17E+00	73	3	-2.38E+00	11.86
			SYX=	-2.43E+00	-9.92E+00			1.70E+00	10.36
			SXY=	-1.03E+01	-4.70E+00			-2.43E-01	11.35
			MXX=	-6.05E+00	-6.53E+00			-4.38E+01	44.65
			MYX=	-1.44E+01	1.72E+01			-3.00E+01	37.42
			MXZ=	2.51E+00	3.34E+00			-9.84E+00	10.69
242	11	5.0	SXX=	-6.20E+00	9.92E+00	74	3	1.95E+00	11.86
			SYX=	-2.56E+00	-9.97E+00			-1.71E+00	10.44
			SXY=	-1.12E+01	-4.61E+00			3.24E-01	12.10
			MXX=	6.90E+00	8.14E+00			-3.02E+01	31.99
			MYX=	-1.44E+01	1.59E+01			-3.43E+01	40.39
			MXZ=	1.89E+00	2.59E+00			-1.35E+01	13.85
274	11	5.0	SXX=	-7.26E+00	1.06E+01	83	3	-1.87E+00	12.96
			SYX=	-2.94E+00	-8.76E+00			-1.63E+00	9.39
			SXY=	-9.01E+00	-4.03E+00			-3.37E-01	9.87
			MXX=	-6.47E+00	7.60E+00			-3.90E+01	40.26
			MYX=	-8.28E+00	1.55E+01			-3.11E+01	35.73
			MXZ=	2.44E+00	-2.84E+00			2.03E+01	20.67
									0.00
275	11	5.0	SXX=	-6.67E+00	1.14E+01	84	3	1.82E+00	13.37
			SYX=	-2.17E+00	-8.85E+00			-1.64E+00	9.26
			SXY=	-9.29E+00	-3.94E+00			-2.93E-01	10.09
			MXX=	-8.01E+00	-7.14E+00			-2.85E+01	30.48
			MYX=	-8.31E+00	1.61E+01			-3.58E+01	40.09
			MXZ=	2.71E+00	-3.15E+00			-1.24E+01	13.07
373	11	5.0	SXX=	-1.11E+01	1.35E+01	113	3	-1.68E+00	17.54

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SYX=	-1.12E+00	-4.17E+00			-7.73E-01	4.38
			SXY=	-3.51E+00	9.66E-01			-3.28E-01	3.66
			MXX=	3.94E+01	1.08E+01			1.48E+01	43.49
			MYX=	5.13E+00	7.37E+00			8.21E+00	12.17
			MYY=	2.93E+01	-7.32E+00			-9.10E+00	31.57
374	11	5.0	SXX=	-9.51E+00	1.53E+01	114	3	1.65E+00	18.12
			SYX=	-9.58E-01	-4.08E+00			7.06E-01	4.25
			SXY=	-3.55E+00	8.90E-01			3.88E-01	3.68
			MXX=	3.84E+01	1.20E+01			2.36E+01	46.61
			MYX=	4.35E+00	-5.32E+00			-8.75E+00	11.13
			MYY=	-2.69E+01	-8.03E+00			1.47E+01	31.70
35	12	5.0	SXX=	4.18E+01	-1.76E+01				45.31
			SYX=	-9.69E+00	1.75E+01				19.96
			SXY=	-3.83E+01	-9.97E+00				39.55
			MXX=	-1.08E+01	-1.03E+01				14.97
			MYX=	1.84E+01	-6.35E+01				66.08
			MYY=	-2.51E+01	2.96E+01				38.85
36	12	5.0	SXX=	7.90E-01	-5.49E+00				5.55
			SYX=	6.16E-01	2.26E+01				22.59
			SXY=	-6.10E+01	-3.00E+00				61.10
			MXX=	4.88E-01	-2.50E+01				24.95
			MYX=	-1.29E+00	2.04E+02				204.20
			MYY=	2.60E+01	2.93E+00				26.15
37	12	5.0	SXX=	-4.30E+01	1.56E+01				45.71
			SYX=	9.54E+00	1.53E+01				18.05
			SXY=	-3.81E+01	-9.52E+00				39.22
			MXX=	1.18E+01	-1.09E+01				16.04
			MYX=	-1.63E+01	-6.05E+01				62.61
			MYY=	-2.25E+01	-2.43E+01				33.11
38	12	5.0	SXX=	-2.47E-01	-4.90E+00				4.90
			SYX=	-8.28E-01	-2.69E+01				26.86
			SXY=	-4.94E+01	1.55E+00				49.38
			MXX=	4.59E-01	2.48E+01				24.79
			MYX=	-2.47E+00	1.17E+02				116.93
			MYY=	-3.70E+01	1.39E+00				37.04
5	15	5.0	SXX=	6.20E+00	-2.66E+00	2	6	1.41E+00	6.89
			SYX=	7.85E+00	6.94E+00			1.27E+01	16.46

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SXY=	-3.47E+01	2.64E+01			2.73E+00	43.68
			MXX=	5.07E+00	2.31E+01			2.07E+01	31.46
			MY Y=	-1.95E+01	-5.79E+01			6.39E+01	88.43
			MX Y=	-2.21E+01	-2.17E+01			-2.68E+01	40.92
23	15	5.0	SXX=	4.11E+00	-5.13E+00	6	6	1.49E+00	6.74
			SY Y=	3.50E+00	5.91E+00			9.80E+00	11.96
			SXY=	-3.34E+01	-2.15E+01			2.00E+00	39.76
			MX X=	4.08E+00	2.08E+01			-6.37E+00	22.11
			MY Y=	-1.63E+01	8.16E+01			-1.99E+01	85.52
			MX Y=	4.91E+00	1.88E+01			-6.20E+00	20.38
42	15	5.0	SXX=	6.61E+00	-2.95E+00				7.24
			SY Y=	6.85E+00	2.02E+00				7.15
			SXY=	5.31E+00	-1.73E+01				18.05
			MX X=	-4.32E+01	-7.06E+00				43.74
			MY Y=	-4.83E+01	2.41E+01				53.92
			MX Y=	-5.43E+00	-2.42E+01				24.80
45	15	5.0	SXX=	4.74E+00	9.26E-01				4.83
			SY Y=	-1.21E+01	2.38E+00				12.37
			SXY=	-2.59E+00	2.05E+01				20.66
			MX X=	-6.72E+01	2.90E+01				73.18
			MY Y=	-7.94E+01	-2.56E+01				83.47
			MX Y=	-1.18E+01	-2.02E+01				23.39
51	15	5.0	SXX=	-3.70E+00	-6.96E+00				7.88
			SY Y=	-8.37E+00	-3.86E+00				9.21
			SXY=	-3.86E+00	-1.89E+01				19.28
			MX X=	-3.70E+01	-8.93E+00				38.03
			MY Y=	3.82E+01	-1.05E+01				39.61
			MX Y=	-1.09E+01	1.99E+01				22.68
5	16	5.0	SXX=	7.10E+00	1.08E+01	2	7	-8.37E-01	12.95
			SY Y=	-4.69E+00	4.26E+00			7.22E+00	9.60
			SXY=	-2.59E+01	2.76E+01			2.43E+00	37.91
			MX X=	1.20E+01	5.29E+01			1.48E+01	56.25
			MY Y=	-1.14E+01	-3.48E+01			-3.38E+01	49.83
			MX Y=	1.14E+01	1.29E+01			-2.01E+01	26.44
23	16	5.0	SXX=	7.68E+00	1.10E+01	6	7	-1.22E+00	13.44
			SY Y=	-2.10E+00	1.44E+00			6.53E+00	7.01
			SXY=	-2.72E+01	-1.68E+01			-1.30E+00	32.00

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MXX=	2.38E+01	6.98E+01			-1.72E+01	75.66
			MYX=	5.95E+01	-1.13E+02			-4.98E+01	137.06
			MYX=	-4.59E+00	1.54E+01			-5.88E+00	17.07
57	16	5.0	SXX=	-1.19E+01	2.51E+01	10	7	-1.53E+00	27.83
			SYX=	1.09E+01	-6.12E+00			-6.46E+00	14.09
			SXY=	-2.63E+01	4.28E+01			-2.93E+00	50.29
			MXX=	-3.74E+00	-9.53E+00			-6.92E+00	12.35
			MYX=	-1.18E+01	-2.79E+01			-2.22E+01	37.56
			MYX=	-5.03E+00	-5.35E+00			7.28E+00	10.34
75	16	5.0	SXX=	-1.18E+01	1.27E+01	14	7	-1.02E+00	17.32
			SYX=	-3.57E+00	-4.49E+00			-4.57E+00	7.33
			SXY=	-2.58E+01	-1.98E+01			-2.39E+00	32.65
			MXX=	1.23E+01	3.35E+01			1.04E+01	37.15
			MYX=	2.63E+01	-4.68E+01			3.59E+01	64.59
			MYX=	1.97E+00	-1.09E+01			-3.09E+00	11.47
5	17	5.0	SXX=	-9.95E+00	1.01E+01	2	8	5.49E-01	14.19
			SYX=	-3.09E+00	-9.93E+00			3.91E+00	11.10
			SXY=	-1.85E+01	-2.11E+01			2.09E+00	28.15
			MXX=	-1.42E+01	2.12E+01			-9.61E+00	27.25
			MYX=	-2.70E+01	5.97E+01			-2.71E+01	70.89
			MYX=	1.65E+01	-1.51E+01			-8.70E+00	24.00
23	17	5.0	SXX=	5.82E+00	1.06E+01	6	8	6.60E-01	12.10
			SYX=	3.89E+00	-8.81E+00			4.04E+00	10.44
			SXY=	1.59E+01	-2.47E+01			2.89E+00	29.51
			MXX=	2.43E+01	2.46E+01			-1.41E+01	37.35
			MYX=	-2.53E+01	6.79E+01			-5.75E+01	92.48
			MYX=	-1.66E+00	-5.93E+00			3.49E+00	7.07
41	17	5.0	SXX=	-1.17E+01	2.33E+01	10	8	-1.25E+00	26.12
			SYX=	2.76E+00	5.77E+00			5.04E+00	8.14
			SXY=	-1.02E+01	2.55E+01			-1.60E+00	27.45
			MXX=	-9.03E+00	1.03E+01			7.79E+00	15.76
			MYX=	-9.68E+00	-1.55E+01			1.67E+01	24.78
			MYX=	-1.49E+01	9.21E+00			8.02E+00	19.28
3	18	3.0	SXX=	6.92E+00	-1.44E+01				15.96
			SYX=	2.32E+00	1.52E+00				2.78
			SXY=	5.61E+00	-1.11E+01				12.39
			MXX=	3.75E+00	2.01E+00				4.25

Horizontal SSI						Vertical SSI		Combined Stress SRSS	
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L5x Stress (ksf) (Note 1) (Note 5)	L5y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MY _Y =	1.81E+01	-9.45E+00				20.37
			MX _Y =	-1.37E+00	-1.72E+00				2.20

Note 1: Data from *Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input Output Data Files* (CRWMS 2000a), computer file L5xstr.out).

Note 2: Data from CRWMS 2000a, computer file L5x2hou.out.

Note 3: Data from CRWMS 2000a, computer file L5y3str.out.

Note 4: Data from CRWMS 2000a, computer file L5z_str.out.

Note 5: Units for S_{xx}, S_{yy}, and S_{xy} are kips per square foot. Units for M_{xx}, M_{yy}, and M_{xy} are foot-kips per foot.

Table IV-2: Beam Elements L5

Horizontal SSI					Vertical SSI			Combined Stress SRSS (ksf)
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Stress Output Type (Note 2)	L5x Stress (ksf) (Note 1) (Note 3) (Note 8)	L5y Stress (ksf) (Note 4) (Note 5) (Note 8)	Vertical Element No. (Note 6)	Vertical Group No. (Note 6)	L5Z Stress (ksf) (Note 6) (Note 7) (Note 8)	SRSS of Columns 4, 5, and 8 (Note 8)
1	1	P1	1.27E+03	1.38E+03				1.87E+03
11	1	P1	9.00E+02	1.23E+03				1.52E+03
29	1	P1	6.14E+02	1.23E+03				1.38E+03
30	1	P1	1.20E+03	1.47E+03				1.89E+03
53	1	P1	2.94E+02	3.50E+02				4.57E+02
54	1	P1	2.95E+02	3.85E+02				4.85E+02
57	1	P1	8.78E+02	9.60E+02				1.30E+03
60	1	P1	3.30E+02	4.08E+02				5.25E+02
								0.00E+00
5	2	P1	5.37E+01	5.66E+01	2	1	4.82E+02	4.88E+02
11	2	P1	8.61E+01	3.18E+01	5	1	4.56E+02	4.65E+02
17	2	P1	5.19E+01	5.07E+01	8	1	3.56E+02	3.64E+02
23	2	P1	4.96E+01	2.93E+01	11	1	3.00E+02	3.06E+02
29	2	P1	5.59E+01	5.63E+01	14	1	2.25E+02	2.39E+02
35	2	P1	2.60E+01	1.66E+01	17	1	1.65E+02	1.68E+02
39	2	P1	5.42E+01	5.32E+01	20	1	6.94E+01	1.03E+02
								0.00E+00
9	3	P1	7.77E+02	1.34E+02	5	2	3.86E+01	7.89E+02
10	3	P1	4.49E+00	2.85E+00	6	2	1.56E+01	1.65E+01
39	3	P1	4.87E+02	1.40E+02	12	2	2.15E+01	5.07E+02
50	3	P1	1.13E+03	1.94E+02	15	2	4.54E+01	1.14E+03
52	3	P1	6.76E+02	2.35E+02	17	2	1.60E+01	7.15E+02
								0.00E+00
11	4	P1	1.34E+02	4.39E+01	5	3	3.97E+02	4.21E+02
24	4	P1	3.90E+01	3.69E+01	10	3	3.46E+02	3.50E+02
37	4	P1	3.87E+01	3.45E+01	15	3	3.50E+02	3.54E+02
50	4	P1	2.60E+01	3.08E+01	20	3	1.90E+02	1.95E+02
63	4	P1	2.83E+02	7.29E+01	25	3	1.23E+02	3.17E+02
82	4	P1	1.54E+02	5.45E+01	28	3	6.62E+01	1.77E+02
85	4	P1	1.49E+02	5.04E+01	30	3	1.20E+02	1.98E+02
87	4	P1	2.34E+01	1.84E+01	32	3	2.23E+02	2.25E+02
								0.00E+00
14	5	P1	4.40E+01	3.22E+01	5	4	2.64E+02	2.69E+02
28	5	P1	2.75E+01	2.33E+01	10	4	1.93E+02	1.97E+02
42	5	P1	3.24E+01	2.18E+01	15	4	1.90E+02	1.94E+02
56	5	P1	1.53E+01	1.96E+01	20	4	1.42E+02	1.44E+02
71	5	P1	5.27E+02	1.03E+02	25	4	7.20E+01	5.41E+02
91	5	P1	6.36E+00	4.06E+00	32	4	4.76E+01	4.81E+01
103	5	P1	4.67E+00	3.71E+00	37	4	3.46E+01	3.51E+01

Horizontal SSI					Vertical SSI			Combined Stress SRSS (ksf)
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Stress Output Type (Note 2)	L5x Stress (ksf) (Note 3) (Note 8)	L5y Stress (ksf) (Note 4) (Note 5) (Note 8)	Vertical Element No. (Note 6)	Vertical Group No. (Note 6)	L5Z Stress (ksf) (Note 6) (Note 7) (Note 8)	SRSS of Columns 4, 5, and 8 (Note 8)
115	5	P1	6.11E+00	3.59E+00	42	4	3.24E+01	3.31E+01
127	5	P1	4.29E+00	3.02E+00	47	4	2.49E+01	2.54E+01
139	5	P1	2.76E+02	8.50E+01	52	4	1.64E+01	2.89E+02
167	5	P1	2.58E+02	7.70E+01	58	4	6.97E+01	2.78E+02
168	5	P1	2.28E+02	6.88E+01	59	4	6.66E+01	2.47E+02
173	5	P1	3.30E+02	1.16E+02	64	4	1.60E+01	3.50E+02
174	5	P1	3.14E+02	6.94E+01	65	4	2.33E+01	3.22E+02
187	5	M2	1.52E+01	-6.74E+01	70	4	3.52E+02	3.59E+02
188	5	M2	-1.45E+01	-1.30E+02	71	4	3.48E+02	3.71E+02
								0.00E+00
		M			2	5	1.36E+03	1.36E+03
		M			8	5	-8.66E+02	8.66E+02
		M			17	5	1.38E+03	1.38E+03
		M			20	5	1.37E+03	1.37E+03
		M			25	5	-9.06E+02	9.06E+02
		M			32	5	1.30E+03	1.30E+03
		M			38	5	-8.85E+02	8.85E+02
		M			47	5	1.30E+03	1.30E+03
		M			55	5	-9.80E+02	9.80E+02
		M			62	5	1.32E+03	1.32E+03
		M			68	5	-1.01E+03	1.01E+03
<p>Note 1: Data from Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input Output Data Files (CRWMS 2000a), computer file from L5xstr.out.</p> <p>Note 2: Data from CRWMS 2000a, computer file L5x2hou.out.</p> <p>Note 3: Data from CRWMS 2000a, computer file L5x2str.out.</p> <p>Note 4: Data from CRWMS 2000a, computer file L5ystr.out.</p> <p>Note 5: Data from CRWMS 2000a, computer file L5y2str.out.</p> <p>Note 6: Data from CRWMS 2000a, computer file L5z_str.out.</p> <p>Note 7: Data from CRWMS 2000a, computer file L5z2str.out.</p> <p>Note 8: Units for P1 are kips. Units for M and M2 are foot-kips.</p>								

Table IV-3: Plate Element L12

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
62	1	5.0	SXX=	-7.06	-12.12				14.03
			SYX=	12.30	-8.24				14.80
			SXY=	-59.20	-17.65				61.78
			MXX=	-73.10	101.30				124.92
			MYX=	-32.60	133.10				137.03
			MYX=	-96.40	75.56				122.48
63	1	5.0	SXX=	-45.60	-33.59				56.64
			SYX=	12.50	-8.24				14.97
			SXY=	-42.00	-17.87				45.64
			MXX=	36.20	110.80				116.56
			MYX=	35.80	127.10				132.05
			MYX=	35.70	-107.90				113.65
64	1	5.0	SXX=	-27.30	-24.13				36.44
			SYX=	16.40	6.60				17.68
			SXY=	-23.00	-16.02				28.03
			MXX=	245.00	232.10				337.48
			MYX=	66.30	-92.19				113.55
			MYX=	26.80	-76.86				81.40
171	1	5.0	SXX=	-8.70	5.54				10.31
			SYX=	13.10	-37.92				40.12
			SXY=	17.70	-4.67				18.30
			MXX=	134.00	292.10				321.37
			MYX=	-113.00	429.00				443.63
			MYX=	91.10	227.60				245.15
172	1	5.0	SXX=	-20.10	6.31				21.07
			SYX=	11.90	-34.20				36.21
			SXY=	-23.70	-23.10				33.10
			MXX=	249.00	417.60				486.20
			MYX=	168.00	447.80				478.28
			MYX=	-86.20	-258.90				272.87
12	2	5.0	SXX=	0.90	4.35				4.44
			SYX=	0.75	7.85				7.89
			SXY=	4.32	-0.73				4.38
			MXX=	2.05	-36.86				36.92
			MYX=	7.70	-123.70				123.94
			MYX=	-11.30	2.00				11.48

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
27	2	5.0	SXX=	-0.71	10.24				10.26
			SYY=	-2.20	39.86				39.92
			SXY=	-15.60	-3.40				15.97
			MXX=	3.22	-103.00				103.05
			MYY=	9.47	-328.60				328.74
			MXY=	9.69	5.22				11.01
42	2	5.0	SXX=	-0.75	8.57				8.60
			SYY=	2.15	38.03				38.09
			SXY=	12.70	1.67				12.81
			MXX=	4.23	67.26				67.39
			MYY=	11.00	-193.40				193.71
			MXY=	8.07	5.60				9.82
57	2	5.0	SXX=	0.76	-7.86				7.89
			SYY=	-0.78	7.45				7.49
			SXY=	6.87	-0.68				6.90
			MXX=	-1.62	19.90				19.97
			MYY=	-6.03	109.20				109.37
			MXY=	11.60	3.42				12.09
90	2	5.0	SXX=	0.85	-12.29				12.32
			SYY=	1.51	-24.54				24.59
			SXY=	23.20	1.82				23.27
			MXX=	-3.56	99.70				99.76
			MYY=	18.10	350.90				351.37
			MXY=	-18.30	9.23				20.50
100	2	5.0	SXX=	-6.49	-17.60				18.76
			SYY=	-4.16	14.33				14.92
			SXY=	5.95	51.05				51.40
			MXX=	-106.00	-100.00				145.73
			MYY=	-249.00	201.70				320.44
			MXY=	66.30	100.90				120.73
106	2	5.0	SXX=	6.15	-21.14				22.02
			SYY=	-5.02	17.04				17.76
			SXY=	-4.50	51.65				51.85
			MXX=	-86.30	102.70				134.15
			MYY=	-203.00	-195.00				281.49
			MXY=	61.30	-118.10				133.06
119	2	5.0	SXX=	0.54	9.20				9.22
			SYY=	1.83	-18.77				18.86

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SXY=	16.10	1.16				16.14
			MXX=	-3.70	58.14				58.26
			MYX=	17.40	235.80				236.44
			MYX=	21.00	8.29				22.58
9	3	5.0	SXX=	1.03	-19.80				19.83
			SYY=	-1.73	-36.26				36.30
			SXY=	75.50	1.29				75.51
			MXX=	-7.58	96.17				96.47
			MYX=	-16.10	197.30				197.96
			MYX=	-15.50	-7.50				17.22
41	3	5.0	SXX=	1.14	5.74				5.85
			SYY=	-2.30	42.94				43.00
			SXY=	16.80	-0.92				16.83
			MXX=	-7.93	-125.40				125.65
			MYX=	-15.50	-261.00				261.46
			MYX=	-19.70	5.85				20.55
10	4	5.0	SXX=	-1.32	-24.52				24.56
			SYY=	0.83	-10.66				10.69
			SXY=	52.60	1.73				52.63
			MXX=	10.80	152.20				152.58
			MYX=	24.60	334.00				334.90
			MYX=	-7.70	9.47				12.21
45	4	5.0	SXX=	-0.33	6.23				6.24
			SYY=	-1.29	19.17				19.21
			SXY=	-17.70	-0.80				17.72
			MXX=	11.80	-218.70				219.02
			MYX=	-23.60	-458.80				459.41
			MYX=	-15.50	-9.60				18.23
10	5	5.0	SXX=	-1.62	-26.20				26.25
			SYY=	1.97	11.03				11.20
			SXY=	51.40	2.52				51.46
			MXX=	-11.30	142.50				142.95
			MYX=	-25.90	302.80				303.91
			MYX=	-8.82	-8.03				11.93
45	5	5.0	SXX=	0.91	13.55				13.58
			SYY=	2.31	8.52				8.83
			SXY=	-18.90	-0.87				18.92
			MXX=	-12.20	-234.10				234.42

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MYY=	24.60	-435.90				436.59
			MXY=	-9.38	6.23				11.26
11	6	5.0	SXX=	-1.41	-24.81				24.85
			SYX=	-0.67	4.49				4.53
			SXY=	52.20	-1.96				52.24
			MXX=	-8.47	94.72				95.10
			MYY=	-18.50	184.50				185.43
			MXY=	22.30	-5.95				23.08
49	6	5.0	SXX=	-0.82	-30.52				30.53
			SYX=	-0.57	10.25				10.27
			SXY=	-19.70	-0.83				19.72
			MXX=	-10.40	-189.20				189.49
			MYY=	-18.50	-256.00				256.67
			MXY=	-10.80	4.07				11.54
11	7	5.0	SXX=	-1.76	-23.81				23.87
			SYX=	0.94	-17.93				17.95
			SXY=	52.10	-2.29				52.15
			MXX=	4.02	-38.31				38.52
			MYY=	-8.39	90.46				90.85
			MXY=	34.50	-4.33				34.77
49	7	5.0	SXX=	-1.06	-43.30				43.31
			SYX=	0.84	17.91				17.93
			SXY=	-19.40	1.26				19.44
			MXX=	-6.89	-117.70				117.90
			MYY=	-7.02	-119.10				119.31
			MXY=	-14.50	3.99				15.04
12	8	5.0	SXX=	-1.69	-22.69				22.75
			SYX=	0.97	-21.58				21.60
			SXY=	53.10	2.31				53.15
			MXX=	-3.86	-51.23				51.38
			MYY=	-18.80	-214.50				215.32
			MXY=	46.30	-4.85				46.55
53	8	5.0	SXX=	-0.88	-36.79				36.80
			SYX=	-1.22	13.56				13.61
			SXY=	18.00	1.10				18.03
			MXX=	2.43	-53.78				53.83
			MYY=	-12.70	-305.90				306.16
			MXY=	-23.00	4.76				23.49

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) (Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
23	9	5.0	SXX=	-9.13	-6.05	3	1	-0.88	10.99
			SYX=	-0.95	4.59			0.50	4.71
			SXY=	-5.40	-1.66			-0.17	5.65
			MXX=	10.10	5.50			41.23	42.80
			MYX=	12.30	11.59			-16.19	23.40
			MYX=	3.37	-8.68			-43.54	44.52
24	9	5.0	SXX=	-7.51	-8.78	4	1	-1.19	11.61
			SYX=	-0.87	4.11			0.52	4.23
			SXY=	-5.28	-1.93			-0.20	5.62
			MXX=	24.10	11.11			65.00	70.21
			MYX=	13.10	8.43			-22.74	27.56
			MYX=	-7.29	-15.23			40.35	43.74
50	9	5.0	SXX=	-7.28	-4.55	12	1	0.92	8.63
			SYX=	-1.66	7.16			0.94	7.41
			SXY=	-9.38	-3.84			-0.38	10.14
			MXX=	32.80	-10.71			26.52	43.52
			MYX=	-38.40	25.52			-36.33	58.70
			MYX=	4.39	-15.51			8.97	18.45
51	9	5.0	SXX=	-6.48	-6.86	13	1	-2.33	9.72
			SYX=	1.44	5.58			0.92	5.83
			SXY=	-9.41	-4.42			-0.52	10.41
			MXX=	25.50	15.43			-39.60	49.56
			MYX=	32.10	19.46			-29.89	47.98
			MYX=	10.30	-20.46			-22.48	32.09
77	9	5.0	SXX=	-6.63	-2.89	21	1	1.23	7.34
			SYX=	-2.39	10.55			1.29	10.89
			SXY=	-12.20	-5.95			-0.67	13.59
			MXX=	-16.70	-41.75			-30.76	54.48
			MYX=	16.60	-23.14			-27.83	39.82
			MYX=	-8.87	-25.66			-28.36	39.26
78	9	5.0	SXX=	-6.01	-5.17	22	1	1.32	8.03
			SYX=	-2.62	6.18			1.11	6.80
			SXY=	-13.90	-7.01			-0.71	15.58
			MXX=	20.40	-15.58			28.61	38.44
			MYX=	17.50	-31.08			33.95	49.24
			MYX=	15.60	-31.10			-17.76	39.06
104	9	5.0	SXX=	-5.88	-3.16	29	1	1.18	6.78

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SYX=	-3.78	16.61			1.26	17.08
			SXY=	-24.00	-11.66			-1.10	26.71
			MXX=	-73.40	-105.30			32.49	132.41
			MYX=	-132.00	-176.00			99.54	241.47
			MYX=	17.60	-58.24			-28.25	67.08
105	9	5.0	SXX=	5.56	-7.64	30	1	1.74	9.61
			SYX=	-3.97	-5.92			1.27	7.24
			SXY=	-16.40	-8.95			-0.61	18.69
			MXX=	-8.31	-16.72			33.50	38.35
			MYX=	-89.20	-84.20			96.86	156.30
			MYX=	29.00	20.73			-26.06	44.16
108	9	5.0	SXX=	-7.27	-8.47	33	1	2.11	11.36
			SYX=	5.71	-5.67			1.70	8.22
			SXY=	-15.80	-8.42			-1.46	17.96
			MXX=	-38.00	77.97			34.47	93.34
			MYX=	-36.20	89.06			-65.90	116.55
			MYX=	8.67	-49.26			-31.51	59.12
10	10	5.0	SXX=	-8.99	3.66	4	2	1.37	9.80
			SYX=	6.51	-7.54			2.21	10.20
			SXY=	8.60	-12.12			-1.07	14.90
			MXX=	13.60	44.93			-31.76	56.68
			MYX=	-79.60	145.30			-105.10	196.20
			MYX=	27.00	-53.86			-24.15	64.91
130	10	5.0	SXX=	-3.33	-1.87	28	2	0.93	3.93
			SYX=	5.62	-10.73			2.35	12.34
			SXY=	4.99	-8.53			-0.90	9.93
			MXX=	-15.70	51.56			14.46	55.80
			MYX=	29.70	-51.46			-42.17	72.86
			MYX=	6.77	26.20			-2.29	27.16
250	10	5.0	SXX=	-6.91	2.05	52	2	-1.10	7.29
			SYX=	5.05	-11.61			2.13	12.84
			SXY=	-2.73	-9.01			-0.65	9.44
			MXX=	7.71	39.95			-19.95	45.31
			MYX=	-27.60	50.65			76.96	96.18
			MYX=	-10.30	33.71			-15.76	38.61
10	11	5.0	SXX=	7.49	3.21	4	3	1.70	8.32
			SYX=	4.48	-14.04			1.91	14.86
			SXY=	15.60	4.42			-0.18	16.22

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MXX=	5.11	-30.93			-22.26	38.45
			MYY=	-26.70	-147.90			63.95	163.33
			MXY=	5.64	35.59			-18.33	40.43
241	11	5.0	SXX=	8.03	4.98	73	3	1.12	9.51
			SYY=	1.92	-10.19			1.01	10.42
			SXY=	8.80	-2.97			0.13	9.29
			MXX=	2.71	-2.06			38.70	38.85
			MYY=	-3.58	-6.07			29.96	30.78
			MXY=	-1.66	2.03			8.69	9.07
242	11	5.0	SXX=	5.79	5.29	74	3	1.01	7.90
			SYY=	1.77	-10.11			1.23	10.34
			SXY=	9.15	-2.79			-0.14	9.57
			MXX=	-3.23	3.90			29.36	29.79
			MYY=	-4.88	7.35			30.56	31.81
			MXY=	1.39	-1.31			-14.52	14.65
274	11	5.0	SXX=	8.34	5.21	83	3	0.74	9.86
			SYY=	1.57	-9.10			1.44	9.34
			SXY=	7.62	-2.58			0.10	8.05
			MXX=	-2.92	2.75			26.18	26.49
			MYY=	-2.96	-6.45			22.03	23.15
			MXY=	-1.27	-1.68			-17.83	17.95
275	11	5.0	SXX=	7.42	5.66	84	3	0.76	9.36
			SYY=	1.43	-9.06			-2.40	9.48
			SXY=	7.92	-2.42			-0.18	8.28
			MXX=	4.51	3.37			23.09	23.77
			MYY=	-3.43	-7.79			25.91	27.27
			MXY=	-2.01	1.59			9.05	9.41
373	11	5.0	SXX=	10.80	-7.29	113	3	-0.77	13.06
			SYY=	0.70	-4.63			0.34	4.70
			SXY=	2.97	0.79			-0.21	3.08
			MXX=	-31.60	-7.80			-8.23	33.57
			MYY=	-1.53	3.04			-3.93	5.19
			MXY=	-23.90	7.68			-6.82	26.01
374	11	5.0	SXX=	7.59	-7.77	114	3	0.69	10.88
			SYY=	0.63	-4.38			0.35	4.44
			SXY=	3.07	0.68			-0.25	3.15
			MXX=	-31.60	7.75			9.19	33.81
			MYY=	-1.48	2.43			-5.00	5.76

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			MXV=	22.90	-6.79			-6.36	24.72
35	12	5.0	SXX=	-34.30	38.15				51.30
			SYV=	-7.61	7.26				10.52
			SXY=	-25.10	-10.86				27.35
			MXV=	-8.14	-6.30				10.29
			MYV=	9.46	-28.40				29.93
			MXV=	23.40	-30.74				38.63
36	12	5.0	SXX=	0.50	3.59				3.63
			SYV=	-0.44	4.13				4.15
			SXY=	41.40	1.74				41.44
			MXV=	0.50	6.04				6.06
			MYV=	1.23	-12.58				12.64
			MXV=	18.00	-1.57				18.07
37	12	5.0	SXX=	38.50	-36.12				52.79
			SYV=	7.31	5.85				9.37
			SXY=	-24.60	10.83				26.88
			MXV=	-8.65	-5.91				10.48
			MYV=	-8.83	-27.21				28.61
			MXV=	15.60	29.01				32.94
38	12	5.0	SXX=	0.14	2.87				2.87
			SYV=	-1.01	30.31				30.33
			SXY=	37.60	1.65				37.64
			MXV=	-0.48	-18.57				18.58
			MYV=	-2.39	-80.02				80.06
			MXV=	27.40	-1.20				27.43
5	15	5.0	SXX=	-4.71	-2.67	2	6	-0.81	5.48
			SYV=	-6.94	6.60			-6.21	11.41
			SXY=	-24.60	-22.43			1.50	33.32
			MXV=	4.35	57.92			-21.32	61.87
			MYV=	-11.00	-58.81			-61.86	86.06
			MXV=	16.50	-23.35			25.63	38.40
23	15	5.0	SXX=	2.46	-4.74	6	6	-0.71	5.39
			SYV=	-2.56	-7.83			-6.12	10.26
			SXY=	28.20	-17.10			1.46	33.01
			MXV=	2.95	-13.99			-14.08	20.07
			MYV=	11.20	-59.26			-25.18	65.35
			MXV=	4.10	-12.91			-6.98	15.24

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
42	15	5.0	SXX=	-4.96	2.57				5.59
			SYX=	-5.73	1.74				5.99
			SXY=	-3.86	-19.07				19.46
			MXX=	30.50	3.54				30.70
			MYX=	-38.10	18.76				42.47
			MYX=	-3.22	4.72				5.71
45	15	5.0	SXX=	-3.53	-0.40				3.55
			SYX=	9.46	1.35				9.56
			SXY=	2.66	-14.41				14.65
			MXX=	-61.60	-9.51				62.33
			MYX=	-71.00	-10.22				71.73
			MYX=	-8.67	20.32				22.09
51	15	5.0	SXX=	2.73	-6.71				7.25
			SYX=	6.79	-3.05				7.45
			SXY=	-2.68	16.36				16.58
			MXX=	24.60	6.25				25.38
			MYX=	-30.50	8.05				31.54
			MYX=	5.72	-15.06				16.11
5	16	5.0	SXX=	6.66	-8.58	2	7	-0.59	10.88
			SYX=	-4.80	5.35			-3.08	7.82
			SXY=	-19.00	21.99			-1.76	29.11
			MXX=	6.98	47.49			12.22	49.53
			MYX=	9.81	-48.18			-39.84	63.28
			MYX=	-7.85	-11.59			23.33	27.21
23	16	5.0	SXX=	5.64	5.45	6	7	0.69	7.87
			SYX=	2.01	-3.26			-3.97	5.52
			SXY=	22.00	-14.80			-1.04	26.54
			MXX=	15.00	-92.13			-17.27	94.93
			MYX=	17.40	89.67			56.62	107.47
			MYX=	3.24	-11.08			6.26	13.13
57	16	5.0	SXX=	11.50	-16.09	10	7	-1.12	19.81
			SYX=	9.11	6.97			-3.50	11.99
			SXY=	14.90	34.32			-3.31	37.56
			MXX=	-2.90	-11.26			-8.65	14.49
			MYX=	-8.38	-28.36			-28.51	41.08
			MYX=	6.13	4.23			6.69	10.01
75	16	5.0	SXX=	-9.86	-6.55	14	7	0.64	11.86
			SYX=	1.94	5.23			3.23	6.45

HORIZONTAL SSI						VERTICAL SSI			COMBINED STRESS
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Element Thickness (ft.) (Note 2)	Stress Output Component (Note 1)	L12x Stress (ksf) (Note 1) (Note 5)	L12y Stress (ksf) (Note 3) (Note 5)	Vertical Element No. (Note 4)	Vertical Group No. (Note 4)	L12z Stress (ksf) Note 4) (Note 5)	SRSS of Columns 5, 6, and 9 (Note 5)
			SXY=	18.80	-21.48			2.08	28.62
			MXX=	9.75	30.27			-13.04	34.37
			MYY=	21.10	58.59			-46.04	77.44
			MXY=	1.48	10.44			-3.74	11.19
5	17	5.0	SXX=	8.50	-5.26	2	8	0.31	10.00
			SYY=	2.41	7.77			-3.91	9.03
			SXY=	13.10	-25.35			2.04	28.61
			MXX=	-8.62	-14.97			8.93	19.45
			MYY=	-17.40	-39.22			-25.86	50.10
			MXY=	11.30	-18.25			6.19	22.34
23	17	5.0	SXX=	-4.72	-6.31	6	8	0.44	7.89
			SYY=	3.42	7.73			-4.26	9.47
			SXY=	-11.80	-28.89			2.43	31.30
			MXX=	18.90	-22.33			14.75	32.76
			MYY=	19.10	66.30			64.79	94.65
			MXY=	1.37	-5.20			2.41	5.90
41	17	5.0	SXX=	11.10	-14.09	10	8	0.63	17.95
			SYY=	-1.96	-5.49			4.79	7.54
			SXY=	-8.00	-26.74			1.68	27.96
			MXX=	6.46	-4.35			8.13	11.26
			MYY=	-7.52	13.84			-17.44	23.50
			MXY=	-9.53	13.53			6.41	17.75
3	18	3.0	SXX=	5.98	-12.15				13.54
			SYY=	1.78	0.99				2.04
			SXY=	4.26	-9.45				10.36
			MXX=	-2.41	-1.47				2.82
			MYY=	-15.50	-8.64				17.74
			MXY=	0.76	1.44				1.63

Note 1: Data from Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input Output Data Files (CRWMS 2000a), computer file L12xstr.out.

Note 2: Data from CRWMS 2000a, computer file 12x2hou.out.

Note 3: Data from CRWMS 2000a, computer file L12y3str.out.

Note 4: Data from CRWMS 2000a, computer file Pstr.out.

Note 5: Units for Sxx, Syy, and Sxy are kips per square foot. Units for Mxx, Myy, and Mxy are foot-kips per foot.

Table IV-4: Beam Element L12

Horizontal SSI					Vertical SSI			Combined Stress SRSS (ksf)
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Stress Output Type (Note 2)	L12x Stress (ksf) (Note 1) (Note 3) (Note 8)	L12y Stress (ksf) (Note 4) (Note 5) (Note 8)	Vertical Element No. (Note 6)	Vertical Group No. (Note 6)	L12Z Stress (ksf) (Note 6) (Note 7) (Note 8)	SRSS of Columns 4, 5, and 8 (Note 8)
1	1	P	1.10E+03	2.96E+03				3.16E+03
11	1	P	1.24E+03	2.31E+03				2.62E+03
29	1	P	1.51E+03	1.99E+03				2.50E+03
30	1	P	1.17E+03	3.87E+03				4.04E+03
53	1	P	3.02E+02	6.14E+02				6.84E+02
54	1	P	2.03E+02	5.22E+02				5.60E+02
57	1	P	4.42E+02	1.55E+03				1.61E+03
60	1	P	3.35E+02	7.31E+02				8.04E+02
5	2	P	3.68E+01	2.73E+01	2	1	6.06E+02	6.08E+02
11	2	P	6.01E+01	2.67E+01	5	1	6.08E+02	6.11E+02
17	2	P	4.05E+01	2.41E+01	8	1	4.05E+02	4.08E+02
23	2	P	5.08E+01	1.62E+01	11	1	3.94E+02	3.98E+02
29	2	P	4.45E+01	2.49E+01	14	1	2.04E+02	2.10E+02
35	2	P	2.48E+01	1.48E+01	17	1	1.99E+02	2.01E+02
39	2	P	4.62E+01	2.40E+01	20	1	7.58E+00	5.26E+01
9	3	P	5.63E+02	2.17E+02	5	2	3.32E+01	6.04E+02
10	3	P	2.61E+00	2.44E+00	6	2	5.67E+00	6.70E+00
39	3	P	9.68E+02	1.74E+02	12	2	1.00E+01	9.84E+02
50	3	P	7.89E+02	3.04E+02	15	2	4.22E+01	8.47E+02
52	3	P	1.35E+03	2.38E+02	17	2	9.93E+00	1.37E+03
11	4	P	3.12E+01	2.70E+01	5	3	1.63E+02	1.68E+02
24	4	P	3.18E+01	5.39E+01	10	3	4.67E+02	4.71E+02
37	4	P	1.52E+01	1.83E+01	15	3	4.60E+02	4.61E+02
50	4	P	1.68E+01	1.35E+01	20	3	1.03E+02	1.05E+02
63	4	P	1.79E+02	8.64E+01	25	3	7.05E+01	2.11E+02
82	4	P	1.40E+02	5.95E+01	28	3	8.62E+01	1.75E+02
85	4	P	1.30E+02	7.04E+01	30	3	2.93E+02	3.28E+02
87	4	P	9.53E+00	1.02E+01	32	3	7.49E+01	7.62E+01
14	5	P	2.15E+01	1.67E+01	5	4	1.32E+02	1.35E+02
28	5	P	1.29E+01	2.13E+01	10	4	2.40E+02	2.42E+02
42	5	P	9.26E+00	1.21E+01	15	4	2.36E+02	2.36E+02
56	5	P	1.00E+01	8.35E+00	20	4	6.02E+01	6.16E+01
71	5	P	2.44E+02	1.30E+02	25	4	5.61E+01	2.82E+02
91	5	P	3.90E+00	3.20E+00	32	4	2.14E+01	2.20E+01
103	5	P	2.10E+00	3.59E+00	37	4	1.61E+01	1.66E+01

Horizontal SSI					Vertical SSI			Combined Stress SRSS (ksf)
Horizontal Element No. (Note 1)	Horizontal Group No. (Note 1)	Stress Output Type (Note 2)	L12x Stress (ksf) (Note 1) (Note 3) (Note 8)	L12y Stress (ksf) (Note 4) (Note 5) (Note 8)	Vertical Element No. (Note 6)	Vertical Group No. (Note 6)	L12Z Stress (ksf) (Note 6) (Note 7) (Note 8)	SRSS of Columns 4, 5, and 8 (Note 8)
115	5	P	1.44E+00	1.68E+00	42	4	1.27E+01	1.29E+01
127	5	P	1.63E+00	1.34E+00	47	4	9.32E+00	9.55E+00
139	5	P	1.75E+02	9.80E+01	52	4	1.39E+01	2.01E+02
167	5	P	1.67E+02	1.18E+02	58	4	5.98E+01	2.13E+02
168	5	P	1.51E+02	1.01E+02	59	4	5.74E+01	1.90E+02
173	5	P	2.16E+02	1.16E+02	64	4	1.45E+01	2.45E+02
174	5	P	2.00E+02	1.13E+02	65	4	2.07E+01	2.30E+02
187	5	M	1.08E+01	2.57E+01	70	4	-4.10E+02	4.11E+02
188	5	M	-1.00E+01	-2.73E+01	71	4	4.04E+02	4.05E+02
		M			2	5	1.65E+03	1.65E+03
		M			8	5	1.24E+03	1.24E+03
		M			17	5	1.64E+03	1.64E+03
		M			20	5	1.66E+03	1.66E+03
		M			25	5	1.23E+03	1.23E+03
		M			32	5	1.62E+03	1.62E+03
		M			38	5	1.10E+03	1.10E+03
		M			47	5	1.61E+03	1.61E+03
		M			55	5	1.13E+03	1.13E+03
		M			62	5	1.70E+03	1.70E+03
		M			68	5	1.12E+03	1.12E+03
<p>Note 1: Data from Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input Output Data Files (CRWMS 2000a), computer file L12xstr.out.</p> <p>Note 2: Data from CRWMS 2000a, computer file L12x2hou.out.</p> <p>Note 3: Data from CRWMS 2000a, computer file L12x2str.out.</p> <p>Note 4: Data from CRWMS 2000a, computer file L12y3str.out.</p> <p>Note 5: Data from CRWMS 2000a, computer file L12y2str.out.</p> <p>Note 6: Data from CRWMS 2000a, computer file Pstr.out.</p> <p>Note 7: Data from CRWMS 2000a, computer file L12z2str.out.</p> <p>Note 8: Units for P1 are kips. Units for M and M2 are foot-kips.</p>								

OFFICE OF CIVILIAN RADIOACTIVE WASTE MANAGEMENT
SPECIAL INSTRUCTION SHEET

1. QA: QA

Page: 1 of: 1

Complete Only Applicable Items

This is a placeholder page for records that cannot be scanned or microfilmed

2. Record Date
05/08/2000

3. Accession Number

ATT-P
MOL-20000504-0313

4. Author Name(s)
Gary Wagenblast

5. Author Organization
N/A

6. Title
CD: TITLE PRELIMINARY DYNAMIC SOIL STRUCTURE - INTERACTION ANALYSIS FOR THE WASTE HANDLING BUILDING, ATTACHMENT III (PRELIMINARY MEMBER SIZES AND DEAD LOAD LIVE LOAD WIND CALCULATIONS) ATTACHMENT IV (DEAD LOAD AND LIVE LOAD AND SEISMIC LOAD COMBINATION)
V 5-9-00

7. Document Number(s)
ANL-WHS-ST-000001

8. Version
REV. 00

9. Document Type
CD-ROM

DATA 5-11-00

10. Medium

DISK 5-11-00

11. Access Control Code

PUB

12. Traceability Designator
DC #23483

13. Comments

THIS IS A ~~ONE OF A KIND~~ SPECIAL PROCESS DISK AND CAN BE LOCATED THROUGH THE RPC

5-9-00

ATTACHMENT VI

HYDRODYNAMIC DATA

Data in Attachment VI are used to assess sloshing height and freeboard for water-filled transfer channels.

WATER SLOSH HEIGHT AND WATER PRESSURE INCREASES ON THE POOL WALL CALCULATIONS DUE TO EARTHQUAKE EVENT

1.0. DBE SEISMIC IN EAST-WEST (X) DIRECTION

1.1. SEISMIC SPECTRUM

According to Bandyopandhyay, et al (1995), pp. 3 through 38, 0.5% damping spectrum is used for sloshing mode.

In Roark (1989), 0.5 percent damping spectra around the pool are plotted for 1-2 and 5-10 Hz time history.

Figure VI-1 demonstrates a 10% broadening of the data.

Figure VI-1: Design Response Spectrum for Pool Sloshing - X-direction (Source see Figure VI-2 and DIR 149176 computer files: L12xpool.out, L5xpool.out)

Using the 10% broadened spectrum in Figure VI-1 set control points for the spectrum $k = 1..15$. The resulting frequencies and accelerations are:

Frequencies	acceleration (g's)
$f_{x_k} = 0.1$	0.05
0.48	1.2
0.7	2.8
0.9	3.9
1.5	6.1
2.1	7.4
2.54	7.4
3	6.3
5	3.8

6.5	2.5
8.5	2.5
20	1.66
30	1.27
45	0.83
100	0.83

$vax(f) = \text{interp}(fx, ax, f)$ and plotted in Figure VI-2.

Figure VI-2: Design Response Spectrum in X-Direction

Figure VI-3: Pool Layout

1.2. Pool Geometry

Water depth $h = 50$ ft.
 five pool width $i = 1.3$

$x_i =$	154	
	21	ft
	6	

1.3. Natural Frequencies in Slosh Mode

Mattsson (2000) provides the fundamental natural angular frequencies

$g = 32.17 \text{ ft} \cdot \text{sec}^{-2}$ (see Table 4-6).

The following equation is Eq. (6.8) from Mattsson (2000):

$$\omega x_1 := \sqrt{\frac{1.58 g}{\frac{x_1}{2}} \cdot \tanh \left[1.58 \frac{h}{\left(\frac{x_1}{2} \right)} \right]}$$

$\omega x_1 :=$	0.71	
	2.2	sec ⁻¹ * rad
	4.12	

or

	0.11	
$\omega x / (2 \cdot \Pi)$	0.35	Hz
	0.66	

Bandyopandhyay, et al. (1995), pp. 4 through 6, gives the first three natural frequencies of slosh in cylindrical tank as follows:

The first three roots of Bessel function are

$$\lambda_1 = 1.841 \quad \lambda_2 = 5.331 \quad \lambda_3 = 8.536 \quad \text{Bandyopandhyay, et al. (1995), Eq 4.5 from pp. 4 to 6.}$$

The rectangular to cylindrical tank conversion of frequency calculation (Mattsson 2000):

$$\text{fratio} = \frac{1.84}{1.58} \quad \text{fratio} = 1.16 \quad [\text{Coefficients from Mattsson 2000).}]$$

for first 3 frequencies $n = 1..3$.

The natural sloshing frequencies are

$$nfx_{i,n} := \frac{1}{2 \cdot \pi} \sqrt{\lambda_n \cdot \frac{g}{\text{fratio} \cdot \frac{x_1}{2}} \cdot \tanh \left(\lambda_n \cdot \frac{h}{\text{fratio} \cdot \frac{x_1}{2}} \right)}$$

[Bandyopandhyay, et al. (1995), Eq. 4.11 from pp. 4 to 8.]

frequencies (Hz)

nfx =	0.114	0.22	0.279
	0.35	0.596	0.754
	0.655	1.115	1.411

sec⁻¹ The natural fundamental frequencies match.

1.4. Acceleration Spectrum Values for the Associated Natural Frequencies

Find the acceleration at each natural frequency from design spectrum.

frequencies (Hz)			spectrum values (g's)	
				0.091
				0.807
				2.475
				0.412
nfx-sec =	0.11	0.22	0.28	
	0.35	0.6	0.75	
	0.66	1.12	1.41	
				vax [(nfx _i , n)/Hz] =
				2.044
				4.689
				0.59
				3.098
				5.744

1.5. Maximum Water Rises in Vertical Displacements (Slosh Height)

The maximum vertical displacement of the liquid surface for cylindrical tank is given in Bandyopandhyay, et al. (1995), Equation 4.51 from pp. 4 to 32. The rectangular to cylindrical tank conversion of maximum water surface displacement (Mattsson 2000):

$$\text{dratio} = \frac{0.527}{0.408} \quad \text{dratio} = 1.16 \quad [\text{Coefficients from Mattsson (2000).}]$$

The maximum vertical displacement of the liquid surface due to earthquake from Bandyopandhyay, et al. (1995), Equation 4.51 from pp. 4 to 32.

$$\begin{aligned} \text{first mode} \quad Ax_{i,1} &= \text{dratio} \cdot \frac{x_i}{2} \left(0.837 vax \left(\frac{nfx_{i,1}}{\text{Hz}} \right) \right) \\ \text{second mode} \quad Ax_{i,2} &= \text{dratio} \cdot \frac{x_i}{2} \left(0.073 vax \left(\frac{nfx_{i,2}}{\text{Hz}} \right) \right) \\ \text{third mode} \quad Ax_{i,3} &= \text{dratio} \cdot \frac{x_i}{2} \left(0.028 vax \left(\frac{nfx_{i,3}}{\text{Hz}} \right) \right) \end{aligned}$$

Ax =	7.61	2.99	1.64	· ft
	9.17	2.02	1.18	
	8.03	1.33	0.63	

Total slosh height

$$shx_i = \left[\sum_{m=1..3} (Ax_{i,m})^2 \right]^{0.5} \quad | \text{Bandyopandhyay, et al. (1995), Equation from pp. 4 to 32.} |$$

shx =	8.34	· ft
	9.46	
	8.16	

2.0. DBE SEISMIC IN NORTH-SOUTH (Y) DIRECTION

2.1. SEISMIC SPECTRUM

The 0.5 percent damping spectra around the pool are plotted for 1-2 and 5-10 Hz time history as shown in Figure VI-4:

Figure VI-4: Design Response Spectrum for Pool Sloshing - Y-direction (Data Source see Figure VI-5 and DIR 149176 computer files: rsmot.out, poolrs.out)

Set control points for the spectrum $k = 1..15$

Frequencies	acceleration (g's)
0.1	0.05
0.2	0.3
0.7	2.9
1	3.7
1.8	5.1
2.08	6.54
2.7	6.54
3.1	4.9
4.1	4.9
5	3.3
7	2.7
10	2.2
20	1.1
30	0.8
100	0.8

$f_{y_k} =$

$a_{y_k} =$

Figure VI-5: Pool 0.5% Damping Response Spectrum in Y-Direction

2.2. Pool Geometry

Water depth $h = 50$ ft.
 Five pool width $I = 1.3$

$$y_i = \begin{array}{|c|} \hline 87 \\ \hline 29 \text{ ft.} \\ \hline 6 \\ \hline \end{array}$$

2.3. Natural Frequencies in Slosh Mode

Mattsson (2000) gives the fundamental natural angular frequencies

$$\omega_{y_i} := \sqrt{\frac{1.58 g \cdot \tanh \left[1.58 \frac{h}{\left(\frac{y_i}{2} \right)} \right]}{\frac{y_i}{2}}} \quad [\text{Equation from Mattsson (2000).}]$$

$$\omega_{y_i} = \begin{array}{|c|} \hline 1.05 \\ \hline 1.87 \text{ sec-1 * rad} \\ \hline 4.12 \\ \hline \end{array}$$

$$(\omega_{y_i} / 2\pi) = \begin{array}{|c|} \hline 0.17 \\ \hline 0.3 \text{ Hz} \\ \hline 0.66 \\ \hline \end{array}$$

let $n = 1.3$

The natural sloshing frequencies for rectangular to cylindrical tank conversions are:

$$nfy_{i,n} := \frac{1}{2\pi} \sqrt{\lambda_n \cdot \frac{g}{\text{ratio} \cdot \frac{y_i}{2}} \cdot \tanh \left(\lambda_n \cdot \frac{h}{\text{ratio} \cdot \frac{y_i}{2}} \right)}$$

[Equation from Mattsson (2000).]

frequencies (Hz)

$nfy =$	0.168	0.293	0.371	
	0.298	0.507	0.642	sec^{-1}
	0.655	1.115	1.411	

2.4. Acceleration Spectrum Values for the Associated Natural Frequencies

Find the acceleration at each natural frequency from design spectrum

Let: $vay(g) = \text{linterp}(fy, ay, g)$

frequencies (Hz)

spectrum values (g's)

$nfy \cdot \text{sec} =$	0.17	0.29	0.37
	0.3	0.51	0.64
	0.66	1.12	1.41

$vay [(nfy_i, n)/\text{Hz}]$

0.22
0.81
2.67
0.78
1.9
3.9
1.19
2.6
4.42

2.5. Maximum Water Rises in Vertical Displacements (Slosh Height)

The maximum vertical displacement of the liquid surface due to earthquake is from Bandyopandhyay, et al. (1995), Equation 4.51 from pp. 4 to 32.

First mode $Ay_{i,1} := \text{ratio} \cdot \frac{y_i}{2} \cdot \left(0.837 \cdot vay \left(\frac{nfy_{i,1}}{\text{Hz}} \right) \right)$

Second mode $Ay_{i,2} := \text{ratio} \cdot \frac{y_i}{2} \cdot \left(0.073 \cdot vay \left(\frac{nfy_{i,2}}{\text{Hz}} \right) \right)$

Third mode $Ay_{i,3} := \text{dratio} \cdot \frac{y_i}{2} \left(0.028 \text{vay} \left(\frac{\text{nfy}_{i,3}}{\text{Hz}} \right) \right)$

$$Ay =$$

10.3	3.21	1.87
12.7	2.59	1.36
8.65	1.1	0.48

·ft

Total slosh height

$$\text{shy}_i := \sqrt{\sum_{m=1}^3 (Ay_{i,m})^2}$$

$$\text{shy} =$$

10.95
13.03
8.74

·ft

[Bandyopandhyay, et al. (1995), Eq. 4.51 from pp. 4 to 32]

3.0. DBE SEISMIC IN VERTICAL (Z) DIRECTION

The pool is surrounded by 5' thick walls and soils. The SSI of the pool is not significant in vertical direction. And there is no breathing mode or other vibration in the vertical direction. The maximum vertical acceleration $az = 0.91$.

Note: The maximum vertical ground acceleration is 0.43 for 1-2 Hz time history and 0.91 for 5-10 Hz time history.

4.0. DYNAMIC HYDRAULIC WATER PRESSURE

Maximum slosh height $\text{psf} := \frac{\text{lbf}}{\text{ft}^2}$

$\text{msh} := \text{if}(\text{max}(\text{shx}) > \text{max}(\text{shy}), \text{max}(\text{shx}), \text{max}(\text{shy}))$

$\text{msh} = 13.03 \text{ ft.}$

Water weight $\rho := 62.428 \frac{\text{lbf}}{\text{ft}^3}$

Dynamic hydraulic water pressure

Horizontal Earthquake $\text{dhwp} = \rho \cdot \text{msh} \quad \text{dhwp} = 813.53 \text{ psf} \quad \text{dhwp} = 5.65 \text{ psi}$

Vertical Earthquake: $az \cdot \rho = 56.81 \frac{\text{psf}}{\text{ft}} \quad az \cdot \rho = 0.39 \frac{\text{psi}}{\text{ft}}$

At bottom of the pool $[\text{dhwp}^2 + (az \cdot \rho \cdot h)^2]^{0.5} = 2954.68 \text{ psf}$

ATTACHMENT VII

Plots of Transfer Functions

Figures in Attachment VII are plots of data in files L5xtfmot.out, L5ztf.out, L12xtf.out, and L12ztf.out from *Preliminary Dynamic Soil Structure-Interaction Analysis for the Waste Handling Building Analysis Input Output Data Files* (CRWMS M&O 2000a). These data plots are used in the soil-structure-interaction analysis to select analysis input parameters.

Figure VII-1: L5X Transfer Functions (Data from file: L5xtfmot.out)

Figure VII-2: L5Z Transfer Functions (Data from L5ztf.out)

Figure VII-3: L12x Transfer Functions (Data from L12xtf.out)

Figure VII-4: L12z Transfer Functions (Data from L12ztf.out)

ATTACHMENT VIII

ACS-SASSI-C Plots of Horizontal and Vertical Modes

Note: Some figures in this attachment are screen prints of finite element model plots. It is characteristic when plotting these finite element models that element numbers or node numbers may overlap. Computer screen prints of the plots display these overlaps. The resulting obliteration does not affect the technical content or results.

April 2000

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 8

Figure 11

Figure 14

Figure 17

Preliminary Dynamic Soil-Structure-Interaction Analysis for the Waste Handling Building

ANL-WHS-ST-000001 Revision 00

ATTACHMENT VIII, ACS-SASSI-C Plots of Horizontal and Vertical Modes

Page VIII-19 of VIII-51

Figure 19

Figure 28

Figure 30

SASSI PREP - Model: L12y2

GROUP 5 3.4

Figure 33

Figure 35

Figure 39

Figure 40

Figure 41

Figure 44

Preliminary Dynamic Soil-Structure-Interaction Analysis for the Waste Handling Building

ANL-WHS-ST-000001 Revision 00

ATTACHMENT VIII, ACS-SASSI-C Plots of Horizontal and Vertical Modes

Page VIII-47 of VIII-51

Figure 47

Preliminary Dynamic Soil-Structure-Interaction Analysis for the Waste Handling Building

ANL-WHS-ST-000001 Revision 00

ATTACHMENT VIII, ACS-SASSI-C Plots of Horizontal and Vertical Modes

Page VIII-51 of VIII-51