Final Report (April 2004)

**The Influence of Calcium Carbonate Grain Coatings on
Contaminant Reactivity in Vadose Zone Sediments**

(DOE Grant FG07-99ER15024)

Principal Investigator:

Prof. Gordon E. Brown, Jr.
Stanford University
Stanford, CA 94305
(650) 723-9168 (phone)
(650) 725-2199 (fax)
gordon@pangea.stanford.edu

Co-Principal Investigators:

Dr. Scott Chambers
Pacific Northwest National laboratory
P. O. Box 999, MISN K8-93
Richland, WA 99352
(509) 376-1766 (phone)
(509) 376-5106 (fax)
sa.chambers@pnl.gov

Prof. Carrick M. Eggleston
University of Wyoming
P.O. Box 3006
Laramie, WY 82071
(307) 766-6769 (phone)
(307) 766-6679 (fax)
carrick@uwyo.edu

Dr. John M. Zachara
Pacific Northwest National Laboratory
P.O. Box 999, MSIN K8-96
Richland, WA 99352
(509) 376-3254 (phone)
(509) 376-3650 (fax)
john.zachara@pnl.gov

Co-Investigators:

Dr. Tom Kendelewicz, Stanford University

Graduate Student:

Colin S. Doyle, Stanford University

DE-FG07-99ER15024

Stanford University

EMSP 70121/Acct. 167E008-2BFZ452

Research Objectives

This project investigated the role of calcium carbonate grain coatings on the reactivity of several key Hanford zone contaminants such as $^{60}\text{Co}^{2+}$, $^{90}\text{Sr}^{2+}$, $[\text{}^{99}\text{TcO}_4]^-$, $[\text{CrO}_4]^{2-}$. Calcium carbonate in the Hanford subsurface is thought to play an important role in the fate of contaminant species released at the Hanford site. Calcium carbonate can play two conflicting roles in the subsurface: (1) it may enhance uptake of certain contaminants such as ^{60}Co and ^{90}Sr , and/or (2) it may impede reductive immobilization of CrO_4^{2-} and $^{99}\text{TcO}_4^-$ by Fe^{2+} present in vadose zone minerals such as magnetite, ilmenite and biotite by forming a barrier preventing electron transfer, and thus passivating the surfaces of vadose zone minerals. Seasonal cycles of saturation and dessication within the Hanford vadose zone lead to precipitation of calcium carbonate. In the subsurface calcium carbonate is present as grain coatings, intergrain fill, and as distinct caliche layers; it is a minor but ubiquitous component of the Hanford and Ringold formations which make up 85% of the Hanford vadose zone. Typically vadose zone porewater is in equilibrium (*i.e.*, saturated) with calcium carbonate, and calcium carbonate may precipitate in the subsurface when high-level waste interacts with porewater.

This project involves fundamental research into all aspects of calcium carbonate coating formation and reactivity, with particular attention to the influence of calcium carbonate grain coatings on the reductive immobilization of chromate. In the final year of this study we extended our investigation to the interaction of aqueous chromate with pyrite surfaces, because of the potential for reduction of Cr(VI) to Cr(III) on pyrite (FeS_2) which is the most abundant metal sulfide in most sediments.

Research Findings and Implications

This report summarizes the results of research conducted at Stanford University (influence of CaCO_3 grain coatings on the reduction of Cr(VI) by magnetite and biotite), which was part of the overall EMSP project. The studies performed at Pacific Northwestern National Laboratory (reactivity of natural CaCO_3 in Hanford sediments), and the University of Wyoming (growth and dissolution processes of calcite and magnesite in presence of contaminants) are beyond the scope of this report.

The formation of calcium carbonate coatings on single crystal magnetite surfaces has been investigated in order to understand how it modifies the reactivity of mineral phases with respect to aqueous chromate. We have performed these experiments using single crystal magnetite (111) surfaces as a model system for Fe(II)-containing Hanford vadose zone minerals, which include magnetite, ilmenite, and biotite. We believe that this model is an accurate reflection of the interaction between aqueous oxoanions such as CrO_4^{2-} and TcO_4^- and Fe(II)-bearing minerals such as magnetite, biotite and ilmenite in the Hanford vadose zone. The coating formation and reactivity has been studied using a combination of synchrotron based X-ray Absorption Near Edge Structure (XANES) and photoemission (PES) along with laboratory based XRD and SEM.

We investigated three routes to produce calcium carbonate coatings on single crystal magnetite (111) surfaces. The first method involved UHV deposition of calcium, followed by oxidation to CaO with O_2 , and subsequent CO_2 dosing to produce calcium carbonate films. This method, despite initial promise, resulted in a discontinuous film and was not pursued. The second method involved growth of calcium carbonate from solution, while the third allowed calcium carbonate films to build up following repeated dosing and evaporation of calcium carbonate saturated solutions. The results of the solution and evaporation grown coatings will be discussed in turn.

Growth of Calcium Carbonate from Solution

Calcium carbonate crystals were grown directly on the magnetite surface from aqueous solution by bubbling CO_2 through mixtures of CaCl_2 and NaHCO_3 solutions.

Coating growth was allowed to proceed under these conditions for between one and two hours, and resulted in coatings formed of aggregations of crystallites exhibiting calcite morphology as shown in **Figure 1**. This morphology differs from that observed in the Hanford subsurface. XRD analysis confirmed calcite as the predominant form of calcium carbonate in the coating. An assessment of film thickness was made by attenuation of the Fe $2p$ photoemission signal, and from relative intensities of Fe and Ca $L_{\text{II}}, L_{\text{III}}$ -edge XANES spectra.

These calcium carbonate films were reacted with $[\text{CrO}_4]^{2-}$ at pH 6, in solutions which were both saturated and unsaturated with calcium carbonate. Dosing of coatings with

unsaturated solutions resulted in coating dissolution and Cr(VI) reduction. With saturated solutions, coatings grown for one hour showed Cr 2*p* photoemission, whilst coatings grown for two hours did not. However Cr(III) was observed by XANES for both growth times, with a much weaker signal from the two hour coatings. Photoemission and XANES results are shown in **Figure 2**.

Significant coating degradation was observed following dosing. Degradation was more pronounced for carbonate unsaturated solutions, and typically resulted in a decreased coverage of calcite rhombs on the magnetite surface.

The presence of Cr(III) on all coatings grown in this manner and the changes in coating integrity following dosing indicate two significant points, 1) that the degree of calcium carbonate saturation in contaminant containing groundwater is of great importance for the ultimate fate of oxoanion contaminants such as CrO_4^{2-} and TcO_4^- , and 2) coatings formed through a solution precipitation method may not act as the best models for carbonate coatings in the Hanford subsurface due to their differing structure. These results do however show that calcium carbonate coatings do inhibit the reduction of chromate at the magnetite/water interface.

Figure 1: SEM micrograph of a calcium carbonate coating grown for two hours on magnetite(111). XRD analysis confirms that the coating consists of calcite.

Figure 2: Photoemission (left panel) and Cr L_{II} , L_{III} -edge XANES (right panel) spectra showing surface composition and Cr speciation following Cr(VI) dosing for (a) uncoated surfaces, (b) surfaces coated for one hour, (c) surfaces coated for two hours. For comparison, PES of a clean, uncoated, undosed magnetite (111), and XANES of representative (d) Cr(III) and (e) Cr(VI) compounds are also shown.

Growth of Calcium Carbonate by Evaporation

We developed a method which closely mimics the processes occurring in the vadose zone at Hanford where seasonal periods of saturation and unsaturation exist, leading to carbonate grain coatings and intergrain fill. This method involved the gradual buildup of a coating by repeated evaporation of a saturated calcium carbonate solution on the magnetite surface. Evaporation of calcium carbonate coatings were performed ex-situ to our UHV analysis system. This resulted in a complete and closed calcium carbonate overlayer as shown in **Figure 3**, which XRD and Ca L_{II} , L_{III} -edge XANES (**Figure 4**) showed to be primarily of calcite with some vaterite and aragonite.

These calcium carbonate films were shown to impede the reduction of $[\text{CrO}_4]^{2-}$ at the magnetite-water interface. Dosing experiments at pH 6 have been performed using chromate solutions that are saturated with respect to calcium carbonate. Survey photoemission spectra,

as shown in **Figure 5** shows photoemission scans of chromate dose magnetite surface with and without evaporated calcium carbonate coatings. For uncoated surfaces, reduced Cr(III) is present on the magnetite surface. When coated surfaces are dosed with 50 μ M chromate, no chromium species is observed on the surface, whereas following dosing with 50mM chromate solution, unreduced chromate is observed. All coatings grown via this method show complete attenuation of the surface-sensitive Fe 2*p* photopeak by the calcium carbonate overlayer, corresponding to a minimum coating thickness of approximately 10-20 Å, however it is clear from SEM examination that the coatings thickness is in the micron range. This apparent discrepancy is understood in terms of the large crystallite size observed in SEM investigations with a thinner cementing layer, built up over several evaporative cycles, which at it's minimum is on the order of the surface sensitive photoemission attenuation depth. Chromate solutions that are saturated with respect to calcium carbonate showed no reaction with evaporated coatings, or with the underlying magnetite surface. Unreduced sodium chromate was present on the calcium carbonate surface following dosing with 50mM chromate solution. This unreduced chromate remained following evaporation of the dosing solution, and was readily washed from the coating surface.

The oxidation state of chromium when present on the surface was monitored by Cr *L*_{II},*L*_{III}-edge XANES and Cr 2*p* photoemission. **Figure 6** shows Cr XANES from coated and uncoated evaporation-grown systems following 5 minute doses with sodium chromate solutions, which show that calcium carbonate coatings do retard the reductive immobilization of Cr(VI), and analogously, Tc(VII) at the magnetite/solution interface.

These findings indicate that in environments such as Hanford, where significant calcium carbonate formation occurs, that Cr(VI) and Tc(VII) should not be completely reduced because of coatings on Fe(II)-containing mineral grains such as magnetite, ilmenite and biotite. This provides a possible explanation for the recent findings of chromate as the dominant chromium species under the SX-108 tank [1].

Figure 3: SEM micrograph of calcium carbonate film formed by repeated evaporation of supersaturated calcium carbonate solutions on the magnetite (111) surface.

Figure 4: Ca LII, LIII-edge XANES spectra of carbonate coatings grown on magnetite(111), and of the calcium carbonate polymorphs calcite, vaterite, and aragonite; EG refers to coatings formed through the evaporation method, SG refers to coatings grown from solution.

Figure 5: Surface sensitive photoemission spectra for (a) uncoated, and (b,c) coated magnetite surfaces dosed with Cr(VI). (a) In the absence of a carbonate coating, chromium is reduced to Cr(III) and binds to the magnetite surface. (b) No chromium species is present following dosing with 50 μM Cr(VI) solution. (c) Unreduced Cr(VI), but no Cr(III) is present on the calcium carbonate surface following dosing with 50 mM solution.

Figure 6: Cr $L_{2,3}$ -edge XANES spectra for coated (a,b) and uncoated (c) magnetite surfaces dosed with Cr(VI). Unreduced Cr(VI), but no Cr(III) is present on the calcium carbonate surface following dosing with 50 mM solution (a). The second and third spectra compare 50 μ M chromate doses for coated (b) and uncoated (c) surfaces. Reference spectra for Cr(III) and Cr(IV), (d) and (e), are also shown. It should be noted that the Cr(VI) present in (a) is in the form of solid sodium chromate, which is highly soluble and thus mobile.

Reduction of chromate on pyrite surfaces

We have used synchrotron based soft x-ray core-level photoemission and adsorption spectroscopies to study the reaction of aqueous sodium chromate solutions with freshly fractured pyrite surfaces. The study has two complementary goals: (1) to investigate the oxidation of pyrite surfaces and identify reaction intermediates, and (2) to assess pyrite as a potential material for the reductive removal and immobilization of hexavalent chromium from solution. Pyrite surfaces were reacted with 50 μ M sodium chromate solution at pH 7 for reaction times between one minute and thirty-seven hours. Additional experiments were performed at pH 2 and pH 4 with 50 μ M sodium chromate solutions, and at pH 7 with 5mM solutions. At chromate concentrations of 50 μ M, all chromate present on the pyrite surface was in the form of Cr(III), while at 5 mM, both Cr(III) and Cr(VI) were present at the pyrite surface (**Figure 7**). Minor quantities of oxidized sulfur species (sulfate, sulfite, and zero-valent sulfur) were identified as reaction products on the pyrite surface. The amount of oxidized sulfur species observed on the surface was greater when pyrite was reacted with 5mM Cr(VI) solutions because the rate of chromium deposition exceeded the rate of dissolution of pyrite oxidation products, effectively trapping Cr(VI) and oxidized sulfur species in an overlayer of iron(III)-containing Cr(III) hydroxide.

This work shows how pyrite, an extremely cheap and readily available waste material, may be suitable for the removal of hexavalent chromium from acidic to circumneutral waste streams. The reduced chromium forms a coating on the pyrite surface, which passivates the pyrite surface towards further oxidation.

Figure 7: Chromium L_{II}, L_{III} -edge XANES showing the speciation of chromium at the pyrite surface after 5 minutes reacting with 50 μM Cr(VI) solution at pH 2, pH 4 and pH 7, and 30 seconds with 5 mM Cr(VI) at pH 7. The minerals crocoite (PbCrO_4) and chromite (FeCr_2O_4) are included as model spectra for tetrahedral Cr(VI) and octahedral Cr(III) respectively. Solid lines indicate Auger electron yield data, and broken lines are total electron yield data.

References

- [1] J.M. Zachara, C.C. Ainsworth, G.E. Brown, Jr., J.G. Catalano, J.P. McKinley, O. Oafoku, S.C. Smith, J.E. Szecsody, S.J. Traina, J.A. Warner, *Geochim. Cosmochim. Acta* **68** (2004) 13.

Information Access

Poster/Oral Presentations

Colin S. Doyle, Tom Kendelewicz, Gordon E. Brown, Jr., Scott A. Chambers, John M. Zachara (2000) The Effect of Calcium Carbonate Coatings on Cr(VI) Reduction at the (111) Surface of Magnetite. Poster Presentation, Goldschmidt 2000, September 3rd-8th, 2000, Oxford, UK.

Colin S. Doyle, Tom Kendelewicz, Gordon E. Brown, Jr., Scott A. Chambers, John M. Zachara (2000) The Effect of Calcium Carbonate Coatings on Cr(VI) Reduction at the (111) Surface of Magnetite. Poster Presentation, 28th Annual Stanford Synchrotron Radiation Laboratory Users Meeting, October 18th-21st, 2000, SLAC, Menlo Park, CA.

John M. Zachara, Scott A. Chambers, Gordon E. Brown, Jr., and Carrick M. Eggleston (2000) The Influence of Calcium Carbonate Coatings on Contaminant Reactivity in Vadose Zone Sediments. FY2001 EMSP Vadose Zone principal Investigation Workshop, November 28th-30th. W.R. Wiley Environmental Molecular Sciences Laboratory, Pacific Northwest National Laboratory, Richland, WA.

Colin S. Doyle, Tom Kendelewicz, Benjamin C. Bostick, Gordon E. Brown, Jr. (2002) Synchrotron Spectroscopic Studies of the Reaction of Cleaved Pyrite (FeS₂) Surfaces with Cr(VI) Solutions. 29th Annual Stanford Synchrotron Radiation Laboratory Users Meeting, October 7th-8th, 2002, SLAC, Menlo Park, CA.

Colin S. Doyle, Tom Kendelewicz, Benjamin C. Bostick, Gordon E. Brown, Jr. (2003) Soft X-ray Spectroscopic Studies of the Reaction of Cleaved Pyrite (FeS₂) Surfaces with Cr(VI) Solutions. 30th Annual Stanford Synchrotron Radiation Laboratory Users Meeting, October 8th-10th, 2003, SLAC, Menlo Park, CA.

Peer-Reviewed Literature

Colin S. Doyle, Tom Kendelewicz, Gordon E. Brown, Jr., Inhibition of the reduction of Cr(VI) at the magnetite-water interface by calcium Carbonate Coatings. *Applied Surface Science* (2004) in press.
doi:10.1016/j.apsusc.2004.02.035.

Colin S. Doyle, Tom Kendelewicz, Benjamin C. Bostick, and Gordon E. Brown, Jr., Soft x-ray spectroscopic studies of the reaction of fractured pyrite surfaces with Cr(VI)-containing aqueous solutions. *Geochim. Cosmochim. Acta* (2004) in press.
doi:10.1016/j.gca.2004.02.015.