DETECTION OF UNAUTHORIZED CONSTRUCTION EQUIPMENT IN PIPELINE RIGHT-OF-WAYS

QUARTERLY TECHNICAL REPORT

(January 1 through-March 31, 2004)

Principal Investigator: James E. Huebler

847-768-0551, jim.huebler@gastechnology.org

Report Issue Date: April 12, 2004

DOE Contract #: DE-FC26-01NT41160

Submitted by

Gas Technology Institute
1700 South Mount Prospect Road
Des Plaines, Illinois 60018

GTI Project Number: 61139

Submitted to

NETL AAD Document Control Bldg. 921
U.S. Department of Energy
National Energy Technology Laboratory
P.O. Box 10940
Pittsburgh, PA 15236-0940

DOE Project Officer
Daniel J. Driscoll

DISCLAIMER

“This report was prepared as an account of work sponsored by an agency of the United States Government, Operations Technology Development (OTD), and the Gas Technology Institute (GTI). Neither the United States Government, OTD, nor GTI, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, OTD, GTI, or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.”

ABSTRACT

Natural gas transmission companies mark the right-of-way areas where pipelines are buried with warning signs to prevent accidental third-party damage. Nevertheless, pipelines are sometimes damaged by third-party construction equipment. A single incident can be devastating, causing death and millions of dollars of property loss. This damage would be prevented if potentially hazardous construction equipment could be detected, identified, and an alert given before the pipeline was damaged.

The Gas Technology Institute (GTI) is developing a system to solve this problem by using an optical fiber as a distributed sensor and interrogating the fiber with a custom optical time domain reflectometer. Key issues are the ability to detect encroachment and the ability to discriminate among potentially hazardous and benign encroachments. The work continues on improving the signal-to-noise ratio of the technique. We are now able to detect weights sitting on the Hergalite fiber of as low as 0.2 pound. Detection of load fluctuations with frequencies greater than 1 Hertz is also possible. We have also purchased a brighter diode laser for use with the multimode fibers that should improve our sensitivity by a factor of ten.

TABLE OF CONTENTS

	<u>Page</u>
DISCLAIMER.....	ii
ABSTRACT.....	iii
EXECUTIVE SUMMARY	1
INTRODUCTION.....	3
EXPERIMENTAL	5
<i>Construction of the OTDR</i>	<i>5</i>
<i>Optical Fiber Selection</i>	<i>7</i>
RESULTS AND DISCUSSION	10
<i>Brief Overview of Optical Fibers.....</i>	<i>10</i>
<i>Scattering Mechanisms #1</i>	<i>11</i>
<i>Scattering Mechanisms #2: Minimum Rayleigh Scattering in a Glass Fiber.</i>	<i>13</i>
<i>Microbending.....</i>	<i>15</i>
<i>Alternate Approaches.....</i>	<i>16</i>
<i>Laser Diode Driver and Detector Electronics</i>	<i>16</i>
<i>OTDR Program.....</i>	<i>18</i>
<i>Commercial OTDR Measurements</i>	<i>19</i>
<i>Test Site.....</i>	<i>21</i>
SUMMARY OF PROJECT STATUS BY TASK.....	25
<i>Task 1. Research Management Plan.....</i>	<i>25</i>
<i>Task 2. Technology Status Assessment.</i>	<i>25</i>
<i>Task 3. Construct and Program Custom OTDR</i>	<i>25</i>
<i>Task 4. Select, Install, and Test Optical Fiber Cables.....</i>	<i>26</i>
<i>Task 5. Collect Data on Selected Right-of-Way Encroachment Types</i>	<i>27</i>
<i>Task 6: Develop Techniques to Distinguish Potentially Harmful from Harmless Encroachment.....</i>	<i>27</i>
<i>Task 7. Demonstrate Sensitivity and Discrimination Capabilities</i>	<i>27</i>
<i>Technical Problems Encountered.....</i>	<i>27</i>
<i>Project Management Issues</i>	<i>27</i>

<i>Action Requested of DOE NETL Project Manager.....</i>	<i>28</i>
<i>Work Planned for the 4th Quarter of 2003 (Oct through Dec, 2003).....</i>	<i>28</i>
CONCLUSION	28
LIST OF ACRONYMS AND ABBREVIATIONS	29
REFERENCES.....	29

LIST OF GRAPHICAL MATERIALS

<u>Figure</u>	<u>Page</u>
Figure 1. SCHEMATIC OF THE CUSTOM OTDR.....	7
Figure 2. TYPES OF OPTICAL FIBERS	10
Figure 3. A HIGHER MODE LIGHT WAVE TRAVELS A LONGER DISTANCE.....	11
Figure 4. PHOTOGRAPH OF THE OTDR CIRCUITRY.....	17
Figure 5. PHOTOGRAPH OF THE DIGITAL OSCILLOSCOPE AND THE OTDR CIRCUITRY.	18
Figure 6. ATTENUATION VERSUS POSITION IN THE FIBER WITH One & two WEIGHTs.	20
Figure 7. ATTENUATION AS A FUNCTION OF LOAD ON THE FIBER.....	20
Figure 8. VOLTAGE SHIFT AS A FUNCTION OF LOAD ON THE HERGALITE.....	21
Figure 9. AERIAL VIEW OF TEST SITE.....	22
Figure 10. SCHEMATIC OF THE TEST SITE	23

EXECUTIVE SUMMARY

Natural gas transmission companies mark the right-of-ways where pipelines are buried with warning signs to prevent accidental third-party damage. Nevertheless, pipelines are sometimes damaged by unauthorized construction equipment. A single incident can be devastating, causing death and millions of dollars of property loss. Detection of construction equipment entering a pipeline right-of-way before it can damage the pipeline would greatly reduce 3rd-party damage.

An optical time domain reflectometer (OTDR) monitoring the light reflection properties of an optical fiber buried near the pipeline can provide continuous monitoring of several miles of pipeline from a single location. A long optical fiber, similar to those used in telephone systems, is buried above the pipeline. Periodically, light pulses are sent down the optical fiber. Normally, a little light is reflected back to the source from all along the fiber. The amount of reflected light is monitored at the source with the advantage of only needing access to one end of the fiber. When construction equipment is present, the ground above the fiber is compressed and vibrated. This changes the optical properties of the fiber and the amount of the light that is reflected back to the source.

The location of the equipment is determined by measuring the time for the reflected light pulse to return. (It is not necessary for equipment to break the fiber to be detected.) The optical fiber returns to normal after the equipment leaves. Because potentially harmful encroachment is rare, methods of distinguishing harmful equipment from benign interferences, such as pedestrians and mowing equipment, are critical.

Because only a small portion of the light is reflected back, most of the light pulse continues along the optical fiber. This means that more than one event (encroachment) can be detected at the same time. This is critical in busy urban areas where encroachments can occur simultaneously along a long optical fiber. This capability also means that the signals from locations at railroad tracks and highways can be distinguished from simultaneously occurring hazardous activities and ignored. In contrast, in some extended optical fiber sensor systems, train and highway traffic dominate the signals and prevent detection of hazardous encroachment.

Phase 1 is to perform proof-of-concept. The project will work to 1.) Develop the necessary hardware and demonstrate the ability to detect construction equipment near underground pipelines and 2.) Develop methods for distinguishing between potentially hazardous and benign intrusions into the right-of-way. At the end of Phase 1, the Gas Technology Institute (GTI) will demonstrate the ability to detect construction equipment on a pipeline right-of-way and to discriminate among signal sources.

In order to provide sufficient sensitivity to detect the encroachments and to manipulate the data to discriminate among sources, a custom OTDR is required. Commercially available units do not meet our needs in terms of sensitivity and how data is processed. A key to the encroachment detection technique is substantially increased sensitivity and data acquisition speed over a conventional OTDR used to test optical communication fiber. This requires special attention to laser power and stability, detector sensitivity and stability, and instrument noise.

GTI designed a custom OTDR using a digital oscilloscope and a combination of commercially available diode lasers, photodetectors, and custom high-speed laser drivers and amplifiers. The laser diode and high-speed electronics can create the 10-nanosecond long light pulse required for 6-10 foot spatial resolution. The Hergalite[®] fiber has proven the most sensitive. We have proven that the technique can detect simultaneously occurring events. A series of improvements have been made to the technique which have increased its sensitivity from not being able to detect any load on the fiber to detecting a few pounds with signal averaging for 10 seconds to detecting fractions of a pound in subsecond time periods. With the latest improvements, we are able to detect weights sitting on the Hergalite fiber as low as 0.2 pounds. The time resolution has also been greatly improved and fluctuations of load at frequencies of greater than 1 Hertz can be detected. A brighter diode laser was purchased that promises to improve sensitivity by another factor of ten.

ANR Pipeline, a division of El Paso Gas, operates transmission pipelines in the Chicago area. They provided a suitable site for the installation of fiber optic sensors within 1.5 hours of driving time from GTI. ANR Pipeline and GTI jointly planned the installation of optical fiber distributed sensors at the site. The optical fibers were installed along the ANR operating pipeline during the week of January 6, 2003.

Because of the extra time and effort required to develop the custom OTDR, GTI began looking for additional sources of funding to complete the proof-of-concept work. During the 3rd Quarter 2003 (Jul through Sep 2003), technical progress slowed as GTI concentrated on obtaining additional, non-DOE, funding. GTI was successful in obtaining the necessary additional funding. We also added co-funding from GTI. A no-cost time extension is requested to complete the Phase 1 proof-of-concept. During the 4th Quarter 2003, little technical work was performed because of manpower constraints. This should not be a problem next quarter. A paper was written describing the project for the Natural Gas Technologies II Conference. The corresponding talk was given in Phoenix, AZ, on February 10, 2004.

INTRODUCTION

The overall objective of this project is to develop and demonstrate an optical fiber intrusion detection device that will prevent outside force damage by detecting and alarming when construction equipment is near a pipeline. Such a technology would result in safer and more reliable pipeline systems and solve a long-standing problem of the natural gas industry. Alerting a pipeline company that construction equipment is moving close to its pipe permits immediate action to stop unapproved excavation and potential damage to the pipeline. The proposed system will provide real-time policing of pipelines 24 hours a day, seven days a week. Prevention of third-party damage will reduce public and utility injuries, service interruptions, and repair costs, resulting in a safer, more reliable transmission infrastructure.

Gas transmission pipelines are buried in utility right-of-ways marked with warning signs. These right-of-ways are well maintained. Nevertheless, pipelines are sometimes damaged by construction equipment not owned by the pipeline company. Referred to as third-party damage, it is the major cause of damage to natural gas transmission pipelines (ref. 1). A single incident can be devastating, causing death and millions of dollars in property loss. One highly publicized incident occurred in Edison, NJ, in 1994. Flames shot 125 to 150 meters (400 to 500 feet) into the air near an apartment complex. Nearly 100 people were treated in hospitals as a result of the accident. Damage from the incident exceeded \$25 million (ref. 2).

A cost-effective, continuous monitoring system is required to prevent third-party damage. “One-call” systems and greater legal penalties have reduced, but not eliminated, the number of incidents. A backhoe, trencher, or auger (for digging post holes) can move into the right-of-way, begin excavation, and damage the pipeline in less than 30 minutes. A boring machine can travel beneath the surface of the ground for greater than 30 meters. This type of equipment can damage the pipeline without ever having the above ground portion of the equipment in the right-of-way.

The approach is to combine existing technologies in a novel way to achieve the required sensitivity to construction equipment and solve the critical problem of minimizing false positives. The use of an optical fiber strand as a distributed sensor has been investigated for many years. Optical time domain reflectometry (OTDR) is a standard telecommunication industry tool for testing fiber optic cables that are hundreds of kilometers long. GTI demonstrated that a fiber optic system with a commercial OTDR with a long averaging time could detect construction equipment (ref. 3). The ability to bury a fiber optic cable with a vibratory plow has also been demonstrated (ref. 4). A large number of microprocessor-based

signal processing and recognition techniques exist. Thus, the basic technologies do not need to be developed, but rather modified and extended into a practical system.

Specifically, the technique will use an optical fiber with the techniques of OTDR and signal recognition as a method to provide an alarm when unauthorized construction equipment violates a pipeline right-of-way. The optical fiber would be buried above the pipeline. Light pulses would be periodically sent down the optical fiber. Normally, no construction equipment is near the fiber and little light is reflected back to the source. Construction equipment creates vibrations in the ground. It also causes compression of the soil. When close to the optical fiber, the vibrations and soil compressions stress and/or bend the fiber, changing its light transmission and reflection properties. When this happens, some of the light is reflected back to the source where it is detected. Because the velocity of light in the fiber is known, the location of the piece of equipment is determined by measuring the time for the reflected light pulse to return. It is not necessary for equipment to break the fiber to be detected. The optical fiber returns to normal after the equipment leaves.

While third-party damage can be devastating, it occurs infrequently—much less than one hit per kilometer of pipeline a year. Every year, many intrusions occur in the right-of-way. Any encroachment detection system must be able to distinguish a benign activity from a potentially hazardous one, or the false positive count will be too high and the system will not be accepted.

To be economical, it will be necessary to monitor many kilometers of pipeline from a single location. Such long distances require a method to measure the location of each encroachment and be able to detect and monitor simultaneously occurring encroachments. This is especially true in urban areas where the pipeline passes under railroads and highways. Techniques that monitor the optical fiber as a whole (for example interferometric), can be dominated by signals from a slow moving train and not detect hazardous encroachment.

The largest technical barrier is in developing methods to distinguish and characterize the different signals. Most of these are benign with no possibility of injuring the pipeline. (e.g., mowing the right-of-way, people walking, motorcycle and ATV traffic). In addition, benign background noises (thunder, airplanes) must be distinguished from other sounds. Soil conditions (moisture content and freezing) will vary throughout the year. These variations may affect the signals detected by the optical fiber. Compared to mowing equipment, pedestrians, etc., construction equipment will be large and have characteristic signals. Seasonal and temperature changes will occur slowly and can be eliminated by creating a time-averaged baseline where the time average is long compared to movement of equipment.

EXPERIMENTAL

Construction of the OTDR

In order to collect the required data to detect and then discriminate between encroachments, a custom Optical Time Domain Reflectometer (OTDR) is needed. It must be capable of collecting and storing a waveform digitized as a function of time from each “segment of optical fiber.” The resulting time histories from individual “segments” will be used to detect encroachment, characterize signals created by construction equipment and benign background noise, and discriminate signal sources. The segments are created by sending a narrow light pulse (~10 nanoseconds) into the optical fiber and digitizing the returning signal at 100 MHz. A typical index of refraction for glass optical fiber is 1.5. Thus, the velocity of light in the fiber is 2×10^8 meter/sec. A 100 MHz digitizer collects a data point every 10 nanoseconds. Light travels 2.0 meters in that time. For data analysis purposes, the fiber is divided into two-meter segments, which is approximately the size of a backhoe.

To keep the data analysis speed and memory requirements manageable for the proof-of-concept, a fiber length of approximately 1.0 kilometer was planned. Five hundred data points (segments) are required to monitor each kilometer of fiber and will take five microseconds (corresponding to the one way roundtrip travel time of one light pulse) to collect. Separating pulses by 10 microseconds or more will keep reflection signals from overlapping. A backhoe moving at 32 kilometers/hr covers 8.9 meters/second. Thus, the high-speed data collection system will be able to collect detailed information on the motion of the backhoe. These arguments can be extended to show that several kilometers could be monitored from one location in a commercial encroachment detection system.

The data collection process can be stated another way. Each light pulse will create a waveform on the digital oscilloscope. The amplitude of this waveform at each point gives information on the activity above that segment of the optical fiber. Collecting a series of waveforms and rearranging the data into amplitude as a function of time for each digitized time increment will give the time history above each segment of the optical fiber.

GTI's technical approach is to purchase and assemble as many commercially available components as possible to construct an OTDR. Most, if not all, of the components—high-speed digitizer and large memory—and a computer system capable of collecting and analyzing the data—are commercially available.

Components from National Instruments (NI) were selected because of the ease and flexibility of assembly and programming. A digital oscilloscope has been assembled using:

- NI 5112, 100 MHz, 100 MS/s 8-bit digitizer, dual channel, with 64 MB flash memory
- PXI-1025 Mega PAC rugged portable chassis for PXI cards
- PXI-8170/850 high-performance embedded controller (850 MHz Pentium III) with 256 MB extended memory

GTI's electronic laboratory has all of the tools and equipment needed to assemble the OTDR. GTI has National Instruments' LabVIEW 6.1 Professional Software Package, Hi-Q mathematics package, and Signal Processing Toolset. The latter provides abilities for joint time-frequency analysis and wavelet analysis, which may prove useful in discriminating signals. GTI also has the latest MATLAB with its signal processing toolbox.

Other components in the OTDR include:

1. A stable, repeatable high-speed light source such as a laser diode or LED. Stability is required to eliminate any fluctuations and minimize the amount of normalization to each light pulse. Variations in light intensity would be interpreted as signals. Many diode lasers have a separate output giving the intensity of the pulse which can be used to trigger an oscilloscope and normalize input pulse amplitudes.
2. A highly reproducible pulse generator
3. A stable power supply to drive the light source. It must create light pulses of 10 nanosecond duration with a timing between pulses of ~10 microseconds.
4. A stable, high-speed detector with a dynamic range large enough to detect backscattered signals from the stressed portions of the fiber
5. Low noise amplifier and band-pass filter to amplify the signals from each detector
6. An optical coupler to inject the pulse from the light source into the optical fiber with minimal light transferring directly to the returning pulse detector. The coupler also splits the returning light pulse in two, permitting its detection.
7. Attenuator at the end of the fiber to minimize the amplitude of the reflected signal
8. Low-loss connectors

Figure 1 is a schematic of the custom OTDR showing the critical components. The requirements for each component are known. Specific parts have been selected and ordered.

FIGURE 1. SCHEMATIC OF THE CUSTOM OTDR

Optical Fiber Selection

An important component of the detection system is the choice of the optical fiber used as the sensor and its environmental shielding. The goal is to have an optical fiber that is sensitive to stress and vibrations at an affordable price. Environmentally, the cable must be impervious to water (to avoid degrading fiber properties), non-electrically conducting (to avoid damage from lightning strikes), and resistive to abrasion (being chewed by rodents, etc.). At the same time the environmental sheath must not make the system insensitive to the vibrations and stresses being measured. Part of the project is to evaluate optical fiber sensitivity and durability.

Cable lengths above the transmission pipeline site will be several hundred meters. This length will permit testing of spatial and time resolution, sensitivity to various encroachments and the ability to detect and discriminate among simultaneous events, while limiting the initial signal processing and memory storage requirements of the OTDR. One site selection criteria is the ability to leave the fiber in place for several years with access by GTI.

The first step in fiber selection was to review the mechanisms that reflect light back to the OTDR, especially those sensitive to stress and vibration. This discussion is given in the section on Results and Discussion. The next step was to compare our needs to commercially available products.

Optical fibers are commercially available because of the telecommunication market. The focus of that market is faster data transmission rates and, therefore, fibers with less sensitivity to stress, strain, and vibration. The optical fiber manufacturers work hard to minimize sensitivity to vibration and stress. They prominently mention this in their advertising. Our application calls for fiber that is sensitive to vibrations. The knowledge of how to minimize sensitivity to stress and vibration implies the knowledge to make a better sensor. This issue was discussed with several fiber manufacturers and suppliers at the Optical Fiber Conference in Anaheim the week of March 18, 2002. No one admits to having fiber that is more sensitive to vibrations. A few are thinking of making distributed sensors—but the market size appears too small for much enthusiasm on their part.

Four fibers were selected as candidates as the optical fiber sensor. The initial goal is to demonstrate the ability to detect encroachment. Choices of fibers were made primarily on the prospects for good sensitivity. The fibers and the reasons for their selection are given below.

A version of Hergalite, a multi-mode optical fiber (50 μm core/125 μm cladding) spirally wound with a “plastic wire”, has been purchased and delivered. When stress is applied to the cable, the spiral wound plastic fiber increases the microbending in the optical fiber. This type of fiber was used in the project that detected a rubber-tired backhoe with a low-cost OTDR. Three hundred meters has been purchased at a cost of \$1.20 per meter. (The manufacturer cautions against its use in areas where easy access to the cable is difficult, such as buried pipe, because the wire can be permanently deformed. When the set is permanent—the wire doesn’t return to its original position when the load is gone. It is possible that the amount of loading of buried Hergalite is too small to cause a permanent set.)

A single mode fiber was obtained from Fibercore Limited. SM600 has a wavelength design frequency of ~ 650 nm, meaning that wavelengths of 650 nm or longer will propagate as a single mode. This feature will permit using a range of wavelengths in single mode to adjust the amplitude of Rayleigh backscattering (Rayleigh backscattering increases with shorter wavelengths). This fiber has a core surrounded by a cladding (125 μm) and a “single acrylate coating,” making the fiber diameter 250 μm . This fiber has a numerical aperture of 0.10 – 0.14. The price for SM600 is \$2.36 per meter for lengths of 1.0 kilometer or more. Cabling for

moisture protection is extra. A source of jacketed Fibercore SM600 was found, however, it is too expensive to be practical. It was not purchased.

The third optical fiber that will be tested, Corning® 62.5/125, is part of Corning's line of standard multimode fibers. It is inexpensive at ~\$0.15 foot when incased in a 2.9 mm diameter jacket.

A multimode fiber, with a core diameter of 200 μm was also selected. The larger diameter should make this fiber more sensitive to mode conversion during vibration and stress. This feature will permit using a range of wavelengths in multi-mode. The manufacturer has been unresponsive to providing pricing and delivery times. This fiber was replaced with Corning® 50/125, which is similar to the optical fiber in the Hergalite—permitting a determination of the effectiveness of the stress increasing fiber.

Other potential candidates are Corning® PureMode™ HI 980, Corning® SMF-28™ is a single mode fiber, and a polarization maintaining fiber.

Corning® PureMode™ HI 980 is a single mode fiber at wavelengths of 980 nm and longer. It has a numerical aperture of 0.20. Corning advertises this fiber as “offering reduced bend attenuation due to its high core index of refraction.” It has the least attenuation of the fibers under consideration. This fiber is \$3.25 per meter in lengths of 1.0 kilometer or more. Water resistant coating and connectors are extra.

Corning® SMF-28™ is a single mode fiber commonly used in the telecommunications industry. It is optimized for use in the 1310 nm window. Its chief advantages are its low attenuation and low price.

Other possibility is a polarization maintaining fiber. Corning makes a number of them with a range of cutoff wavelengths. Light propagates in two perpendicular polarizations. Polarization maintaining fibers are pre-stressed so that the two polarizations travel independently with minimum cross talk. If the fiber is stressed some conversion from one polarization to the other occurs. If light of a single polarization is used, any light of perpendicular polarization indicates stress. The other fibers will be tried first.

RESULTS AND DISCUSSION

Brief Overview of Optical Fibers

Optical fibers are made from two transparent materials; usually glass, with differing indices of refraction. Index of refraction is the ratio of the speed of light in a vacuum to the speed of light in the material. An optical fiber is formed when a thin core of index n_1 is surrounded by an outer core (cladding) of index n_2 . If the cladding has a smaller index of refraction, and the light is incident on the interface between the two materials at an angle less than the critical angle, total internal reflection occurs. This creates an optical waveguide. Little energy is lost from the light beam and the beam can propagate for long distances. A thin buffer is often added around the cladding to provide waterproofing and additional jacketing materials are available.

FIGURE 2. TYPES OF OPTICAL FIBERS

There are two general fiber configurations: single mode and multi-mode. As shown in Figure 2, a single mode fiber the core is smaller in diameter than a multi-mode fiber core. In either case, the outside cladding diameters of single- and multi-mode fibers are typically 125 micrometers (or about the size of the human hair). Light may enter a multi-mode fiber at several angles. Some of this light will travel in the waveguide with a minimum of reflections from the core/cladding interface. Light entering at a greater angle will also propagate in the waveguide by making more reflections (higher modes). Because of the extra reflections, the higher modes must travel a greater distance and take longer to transverse the optical fiber (See Figure 3). In order to propagate in a single mode fiber, the light wave must enter the fiber nearly parallel to the axis of the fiber. Multi-mode fiber will carry more light than single-mode. On the other hand, if a pulse of light is injected into a multi-mode fiber and the fiber is bent, mode conversion

will occur, both attenuating and broadening the pulse. Mode conversion occurs when some of the light is changed from a mode with few reflections to a mode with more reflections.

FIGURE 3. A HIGHER MODE LIGHT WAVE TRAVELS A LONGER DISTANCE

Mode conversion can be effective as a sensing mechanism. A continuous light wave can be sent into a fiber and the total light intensity measured as a function of time. If mode conversion occurs because of stresses to the fiber and microbending, variations will be produced in the outputs that are proportional to the vibrations of the fiber. This is used as a stress measurement technique. Unfortunately, for our application, changes everywhere along the fiber are measured simultaneously. In the encroachment monitoring application with fiber lengths of a few miles, multiple events (disturbances to the fiber) will occur simultaneously. The use of OTDR has the potential to independently monitor the simultaneous vibrations.

Scattering Mechanisms #1

Light is attenuated as it travels down a fiber by several mechanisms. These processes include bending of the optical fiber and scattering mechanisms. A scattering mechanism absorbs the incoming light and reemits it at all angles. Some of the light is reemitted backwards into the narrow cone of acceptance formed by the fiber core. That light returns to the detector at the light source. More of the light is reemitted at angles to the incoming beam that cause it to be lost into the cladding. Our approach is to use the phenomenon of backscattering (either by detecting the backscattered light or by the decrease in light from succeeding parts of the fiber caused by the loss of light into the cladding) to detect stress to and vibration of the fiber.

Much of the scattering in an optical fiber is caused by variations in the density of the fiber. Variations in density change the velocity of light and thus the index of refraction. Density variations are unintentionally built into the fiber during its manufacture. These are caused

primarily by thermally induced fluctuations in density and variations in the concentration of dopant materials just before the glass transitions into a solid. The main use of optical fibers is in telecommunication. Thus, the fiber manufacturer tries to minimize scattering losses because they increase the attenuation in the fiber and thereby limit the distance a signal can be sent.

Stress, vibrations, temperature change, and acoustic waves induce other density variations. The scattering induced by the density fluctuations can be elastic (no change in the wavelength between the incoming and outgoing light wave) or inelastic (a shift in the wavelength between the incoming and outgoing light wave).

Rayleigh scattering often refers to the scattering of light by air molecules. However the term also applies to scattering from particles up to about a tenth of the wavelength of the light. (Green light has a wavelength of ~ 550 nanometers. Rayleigh scattering off the molecules in air creates the blue sky.) It is elastic because energy of the scattered wave is the same as the incident wave. Lord Rayleigh modeled the air molecule as an electric dipole driven by the electric field of the light wave. The scattered intensity from dipole scatterers much smaller than the wavelength of light (ref 5) is:

$$I = I_0 8\pi^4 N p^2 (1 + \cos^2\theta)/(R^2 \lambda^4) \quad \text{eq. 1.}$$

where N = number of scatterers, p = polarizability, R = distance from the scatterer, λ = wavelength of the light, θ = angle of the scattered light with respect to the incoming light. Note that light is scattered in all directions, including directly back on the incoming light.

Equation 1 is for air molecules. Changing the geometry to backscattering in an optical fiber, the attenuation, α , caused by Rayleigh scattering is given by (ref 6)

$$\alpha = 8\pi^3 (n^2-1) k T \beta / (3\lambda^4) \quad \text{eq. 2.}$$

where β = isothermal compressibility of the glass, T = temperature. For fused silica transitioning at 1500°C , this represents a loss of 1.7 dB/km at 820 nm.

Although equation 2 gives the total attenuation, part of the backscattered light propagates back through the waveguide. The important features to note are the temperature dependence of the backscattering and the very strong wavelength dependence, λ^4 . Decreasing the wavelength by a factor of two, increases the Rayleigh scattering by a factor of 16. Therefore we can adjust the amount of backscattering by the choice of the light source.

For many fiber optic sensor applications, Rayleigh scattering dominates. However, it is also possible to detect light from Raman and Brillouin scattering.

Brillouin scattering is the scattering of light from sound waves in the fiber. From the classical point of view, the acoustic waves locally change the density—i.e. the refraction and compression of the material. From the quantum point of view, the light photons interact with the acoustic or vibrational quanta (phonons). Brillouin scattering is inelastic with energy being gained or lost by the interaction with the moving sound wave. The shift in frequency is small and Brillouin light is difficult to separate from Rayleigh scattering. However, it can be separated from the original wavelength with special instrumentation. Brillouin scattering can be used to measure stress in the optical fiber. Ando Corporation makes an Optical Fiber Strain Analyzer, model AQ8603. It is a sophisticated OTDR and costs ~\$130,000. Each data trace requires 2 minutes to collect, making it too slow to characterize encroachment signal. Ando demonstrated this unit at GTI.

Raman scattering, like Rayleigh scattering, depends on the polarizability of the molecules. For polarizable molecules, the incoming light wave (photons) can excite vibrational modes of the molecules, yielding scattered photons that are diminished in energy by the amount of the vibrational transition energies. Because there can be many vibrational modes in a molecule, a spectrum of Raman scattering yields a series of lines at lower frequencies (longer wavelengths) than the incoming light. Such lines are called “Stokes lines.” If there is significant excitation of the vibrational excited states, then it is also possible to detect scattering at higher frequencies. These spectral lines are called “anti-Stokes lines.” Anti-Stokes lines are normally weaker than Stokes lines. The anti-Stokes lines are a sensitive indicator of temperature. Raman scattering is much weaker than Rayleigh scattering. Raman backscattering can be separated from Rayleigh and Brillouin scattering to improve the signal to noise ratio.

Because of the extra complexities and cost required to detect Raman and Brillouin scattering, GTI will use microbending and/or Rayleigh scattering to detect encroachment.

There are several other phenomenon and measurement techniques (mostly discrete sensors) that have the potential of measuring stress and vibrations. As in the case of Raman and Brillouin, the added complexity is not justified for our application. Thus they have not been described.

Scattering Mechanisms #2: Minimum Rayleigh Scattering in a Glass Fiber.

A second treatment of Rayleigh scattering was found that gives the theoretical minimum possible amount of Rayleigh scattering in glass optical fibers. Many commercial optical fibers are close to this limit. The advantage of this analysis is it gives the minimum signal level we

must be able to detect. Which in turn provides guidance on the light source wavelength and power level and on the detector sensitivity.

John M. Senior, Optical Fiber Communications, Prentice/Hall International 1985, pp 69-70 gives an equation giving the minimum Rayleigh scattering coefficient as:

$$\gamma_R = 8\pi^3 n^8 p^2 \beta_c k T_F / 3\lambda^4 \quad \text{eq. 3}$$

where—

γ_R = Rayleigh scattering coefficient

n = index of refraction of the fiber core [1.46]

p = average photoelastic coefficient [0.286]

β_c = isothermal compressibility at a fictive temperature T_F [$7 \times 10^{-11} \text{ m}^2 \text{ N}^{-1}$]

k = Boltzmann's constant [$1.381 \times 10^{-23} \text{ J K}^{-1}$]

T_F = The fictive temperature, which is the temperature at which the glass can reach a state of thermal equilibrium and is closely related to the anneal temperature. [1400 K]

λ = Wavelength of the incident light.

Note: The values in [] are for silica glass.

This scattering is caused by index fluctuations caused by the freezing-in of density inhomogeneities. The inhomogeneities are fundamental and cannot be avoided. Substituting the values for silica glass into equation 1 gives:

$$\gamma_R = 1.895 \times 10^{-28} / \lambda^4 \text{ m}^{-1} \quad \text{eq. 4}$$

The Rayleigh scattering coefficient is related to the transmission loss factor, ξ

$$\xi = \exp(-\gamma_R L) \quad \text{eq. 5}$$

where L = length of the fiber. The attenuation due to Rayleigh scattering in dB km^{-1} is given by:

$$\text{Attenuation} = 10 \log_{10} (1 / \xi) \quad \text{eq. 6}$$

For example at a wavelength of $0.63 \mu\text{m}$, $\gamma_R = 1.199 \times 10^{-3} \text{ m}^{-1}$, $\xi = 0.301$, and the attenuation, $\alpha_R = 5.2 \text{ dB km}^{-1}$

The attenuation can also be expressed as $\alpha_R = 10 \log_{10} (P_i / P_o)$. P_i is the input light power (watts) and P_o is the output light power at the end of the fiber. For 2.0 meters of fiber and a wavelength of $0.63 \mu\text{m}$

$$P_o = P_i 10^{-\alpha_R/10} = P_i 10^{-5.2 \times 0.002/10} = P_i 10^{-0.00104} = 0.997608 P_i$$

The amount of scattered light in a 2.0 meter section of fiber is $(1 - 0.997608) P_i = 0.0024 P_i$. This value gives the upper limit on the minimum backscattered light because only part of the light is

scattered into the fiber. For a fiber with a core index of $n = 1.46$ and a cladding index of 1.40 , the critical angle is $\theta = \arcsin(1.40/1.46) = 73.5$ degrees as measured from the normal to the core/cladding interface. $90 - 73.5$ degrees = 16.5 degrees. Using the angular dependence in equation 1, about 10% of the Rayleigh scattering is reflected back to the source.

Therefore, for a fiber with the lowest loss Rayleigh scattering at $0.63 \mu\text{m}$ and a 2-meter section of glass fiber, 0.00024 of the input power is reflected back to the source. If the input power (light) is $100 \mu\text{watts}$, $0.024 \mu\text{watts}$ (24 nanowatts) will be reflected back. Detectors can measure down to a several hundred nanowatts of light power. This information will be used to select the power output of the light sources.

The diode laser we purchased has a wavelength of $0.69 \mu\text{m}$ (690 nm) and a light power output into the optical fiber of 10.5 mW . Using the same calculations corrected for the different wavelength of the purchased laser and a 2-meter section of glass fiber, the estimated power reflected back to the source is $P_o = 0.00024 \times 0.69 P_i = 0.00017 P_i$. The diode laser has an output power of 10.5 mW , thus the reflected power with no extra stress is $\sim 1.75 \mu\text{W}$. Reducing this value for other losses in the OTDR should result in a very detectable signal for the minimum Rayleigh backscattering. Stress related backscatter would be in addition to this value. Because the amplitudes of both the intrinsic and stress/vibration induced backscatter are a function of wavelength, a relatively short wavelength (690 nm) was selected to maximize the signals.

As described above, Rayleigh backscattering is sensitive to wavelength, with more scattering from shorter wavelengths. Shorter wavelengths also mean more attenuation. Therefore we will have to make tradeoffs between sensitivity and range.

Microbending

Microbending is another method of changing the transmission properties of an optical fiber. In microbending, the curvature of the optical fiber is increased over short distances. This causes some of the light to exceed the critical angle (sometimes as the result of multiple reflections). This results in an increased loss of light in the optical fiber that can be detected by a reduction in the light backscattered from further along the fiber. Wrapping a fiber with a wire or using a fiber with periodic variations in the core diameter can increase the amount of microbending.

Alternate Approaches

Three commercial products are available for measuring the stress/vibrations in an optical fiber. One is Ando Corporation's Brillouin scattering Optical Fiber Strain Analyzer, model AQ8603. It takes 2 minutes to collect a reading, which is too slow for characterizing encroachment types.

Future Fiber Technologies is marketing an optical fiber sensor technology for use in monitoring disturbances to optical fibers. One application is for right-of-way encroachment detection. Based on their website, they use an interferometric technique to detect encroachment. Based on FFT's Australian patents, they also have a technique that monitors the entire fiber by injecting a continuous light source into the fiber and utilizing mode conversion of light at locations where there is a disturbance. Disturbances to the fiber cause some of the light to change modes. Different modes travel at different velocities. When recombined at the detector, the modes interfere causing voltage fluctuations related to the vibrations. The total amplitude is monitored as a function of time in the frequency range of 0 to 100,000 Hz. The major drawback to each FFT technology is that it does not separate or distinguish simultaneous events. If we monitor kilometers of pipeline in noisy environments from one location, this will be an issue because of the non-hazardous encroachments and passage near railroads and highways. A second technique, requiring access to both ends of the fiber is used to locate the dominant signal.

EDM Services offers products called Trip Wire®. Trip Wire is an optical fiber or conducting wire buried above the pipeline. Any optical fiber can be used. Optical time domain reflectometry for the optical fiber and electrical time domain reflectometry for the wire is used to detect breakage or severe damage to the fiber/wire. The damage is detected in a few seconds of its occurrence. Drawbacks to the approach are that the fiber must be damaged or broken for detection and then repaired after the damage has occurred. In the case of 3rd-party damage, the presence of construction equipment is sensed only after the equipment is moved on site, excavation has started, and enough soil removed to hit and damage the fiber or wire. The equipment is in eminent prospect of damaging the pipe in a few more motions.

Laser Diode Driver and Detector Electronics

The GTI detection approach sends a 10-nanosecond light pulse into the optical fiber every 10 microseconds and digitizes the returning signal at 100 MHz. A stable, repeatable light source is required to eliminate any fluctuations in the light pulses that might be interpreted as signals. A 690 nm diode laser with attached optical fiber was purchased from OECA (Opto-Elektronische Komponenten und Applikations GMBH) as the light source. It can deliver 10.5

mW of continuous light power into the fiber. We designed circuitry to create repeatable pulses for driving the diode laser. Because the amplitude of the power output and the lasing frequency are temperature dependant, precautions were taken to deliver a stable pulse. The pulse width can be varied from 8 to 20 nanoseconds. The repetition time between pulses can be varied between 300 nanoseconds and 600 microseconds. The diode laser can also operate continuously. The bias current to the laser can be adjusted to just under the lasing threshold. This keeps fluctuations in the current draw and, therefore, the operating temperature of the electronics to a minimum. The diode laser is mounted on a copper heat sink that is temperature controlled with a thermoelectric module. A 10 K Ω thermistor is mounted on the heat sink and will be used in conjunction with an automatic “ultrastable thermoelectric controller” to maintain the temperature to within ± 0.01 °F. A second thermistor will be used to adjust the temperature and verify the actual temperature fluctuations. This electronics can be used to drive diode lasers with other wavelengths.

A stable, high-speed detector with a dynamic range large enough to detect light scattered from the stressed portions of the fiber is also needed. Silicon photodiodes (FCI-HR005 and FCI-HR008 from OSI Fibercomm) were selected as the detector. Two high-speed amplifiers were designed. One will amplify the output from the photodiode built into the diode laser. The

FIGURE 4. PHOTOGRAPH OF THE OTDR CIRCUITRY.

FIGURE 5. PHOTOGRAPH OF THE DIGITAL OSCILLOSCOPE AND THE OTDR CIRCUITRY.

second will amplify the signal from the detector photodiode, which in turn will be feed into the digital oscilloscope. Originally, the laser diode and the detector were on the same circuit board and on the same temperature-controlled heat sink.

The detector was redesigned and in the process placed on its own circuit board. The new design reduced the noise floor by over a factor of ten, which will greatly help in detecting the returning light signals. New higher-powered diode lasers where obtained. They will be used as a light source for the multimode fibers.

The electronics is mounted on a custom printed circuit board in an enclosed electrical box. Figure 4 is a photograph of the laser diode drive circuitry and the photodiode detector circuitry. Figure 5 is a photograph of the digital oscilloscope and the laser diode drive circuitry and the photodiode detector circuitry.

OTDR Program

The function of the OTDR is to collect data generated by encroachment from the optical fiber over the pipeline. Conceptually, the fiber is divided into 2-meter long segments. The resulting time histories from individual segments will be used to detect encroachment, characterize signals created by construction equipment and benign background noise, and discriminate signal sources. The digital oscilloscope was programmed in National Instruments

LabVIEW 6.0 to collect the data as amplitude versus time as the returning backscattered light returns from along the fiber. This results in a series of traces, one for each light pulse spaced 10 microseconds apart. The custom OTDR permits monitoring the data corresponding to each two-meter segment as a function of time. This data is stored for later analysis.

Commercial OTDR Measurements

With the delays in completing our OTDR, we have not been able to test the optical fibers as originally planned. The opportunity arose to test the fibers in the laboratory with newly redesigned commercially available Agilent Technologies Mini OTDR mainframe with E6009A-850/1300nm multimode laser module. Figure 6 shows the results of two measurements, one with a single weight [upper, red curve] and one with a second weight [lower, green curve]. The second weight was placed 11 meters closer to the OTDR. Ten-pound weights were used with the edge of the weight resting on the Hergalite. This gives an effective load on the fiber of ~5 pounds. The signals were averaged for 30 seconds to obtain these data. There are two peaks in the curves, one for the initial light pulse and the second reflection from the end of the 275 meter long fiber. With one weight applied as shown in the upper curve, there is a small amount of reflection followed by a sharp drop in signal strength. A second weight was placed on the fiber and another step decrease is seen. The two curves are displaced from each other along the vertical axis to make it easy to compare the features in the curves. As described earlier, measuring signal losses is another method for detecting encroachment. Losses corresponding to both weights are observable, although the second produces a smaller signal loss. When the weight closer to OTDR is removed, the signal loss caused by the remaining weight increases to that of the first weight. When both weights are removed, the fiber returns to normal and no residual signal decrease is detected.

Next, a series of measurements were performed to determinate the length of time required to detect a signal. Measurement times were decreased from 100 seconds to 2 seconds without a noticeable deterioration of the signal loss.

Figure 7 shows the results of the attenuation at one location on the fiber versus the applied static load. The load was applied over a 3-inch long length of fiber. The relationship is linear. A one-pound weight was the smallest used. Signal averaging lasted 30 seconds. It is possible to detect a one-pound load.

Similar sets of measurements were performed on the Fibercore SM600. We were not able to detect any reflection or attenuation.

These results suggest that the approach being developed in this project is reasonable. Loads smaller than one pound applied to the Hergalite can be detected. Loads can be detected

FIGURE 6. ATTENUATION VERSUS POSITION IN THE FIBER WITH ONE & TWO WEIGHTS.

FIGURE 7. ATTENUATION AS A FUNCTION OF LOAD ON THE FIBER.

with averaging times less than 2 seconds—which is far more sensitive than was possible with earlier OTDRs. Rayleigh scattering is proportional to the light wavelength to the -4 power. The GTI uses a wavelength of 690 nm rather than 850 nm of the Agilent. Thus the effects should be stronger at 690 nm by a factor of 2.3. The extra, helically wound fiber in the Hergalite is very effective in generating microbend losses.

Improvements in sensitivity were made. The Hergalite fiber was re-wound to provide access to both ends and the middle of the fiber. Measurements were made demonstrating the ability to detect static weights as small as 0.2 pounds resting on the Hergalite. The output of the photodetector was monitored with a Tektronix TDS 3200 oscilloscope. Placing a weight on the Hergalite caused a voltage shift in the light intensity versus time trace. Figure 8 plots the voltage shifts as a function of load. The Agilent was not able to resolve the sub-pound loads.

FIGURE 8. VOLTAGE SHIFT AS A FUNCTION OF LOAD ON THE HERGALITE

Test Site

The OTDR and optical fiber system will be tested in the field at an operating pipeline. ANR Pipeline, Division of El Paso Energy Corporation, is providing the site. Figure 9 is an aerial photograph of the site. The site is along two operating transmission pipelines. One pipeline is 22 inches in diameter; the second is 30 inches in diameter. Overall dimensions of the site are 1430 by 2650 feet. Part of site is under cultivation, part is wooded, part is in open field, and part has a stream running through it. The path of the optical fiber sensors is in both the

farmed and unfarmed areas. The path of the transmission lines is shown by the green dotted line superimposed on Figure 9. Electrical power is available at the microwave tower located at the end of the gravel road. Instrumentation will be attached to each fiber during the testing and removed between test days.

FIGURE 9. AERIAL VIEW OF TEST SITE

Figure 10 is a schematic of the test site using the distances and depths measured when the optical fiber sensors were installed. The red dots in Figure 10 and the corresponding numbers give a running distance from the fence around the microwave tower. We made some modifications to the original plan based on the dimensions of the site. These will give us extra flexibility. The fibers run in a loop from the tower along the gravel road, across the open area, then back along the pipeline at the edge of the cultivated field and back across the field to the microwave tower. Two electrical boxes were mounted on the fence surrounding the microwave tower. A Corning® 62.5/125 fiber was installed as a loop, with an end in each of the electrical boxes. A 543-foot section (between points 887 and 1430 feet) is buried 24 inches directly above the 30-inch pipeline. A second piece of Corning® 62.5/125 was installed $\frac{1}{2}$ of the way around the loop (0 to 887 feet). The latter fiber crossed over the 22-inch pipe, stopping short of the 30-inch pipeline. The fiber was coiled and 100-foot length of bare Fibercore SM600 was spliced to the end. The last 50 feet of the Fibercore was formed into a 6-inch diameter coil and the tail end brought above the ground (near the 826 foot mark). The end coil provides extra distance so that the end of the fiber is not at the end of the path length. Similarly, 1 $\frac{1}{2}$ loops of the Corning® 50/125 was also installed. Two sections of Hergalite were spliced into the Corning® 50/125.

FIGURE 10. SCHEMATIC OF THE TEST SITE

One 50-foot length was buried 6-inches deep. The second 50-foot length was buried at two depths 12 and 18 inches. Unfortunately, the Corning® 50/125 fiber that was to be a continuous loop broke between the two sections of Hergalite. Access to the far end of the ½ loop of Corning® 50/125 is provided in an electrical box (at 887 feet). The optical fibers were buried at several depths, ranging from 6 to 24 inches. This arrangement will permit sensitivity tests at a range of depths. The deepest depths permit passage of a plow over the optical fiber without damaging it, thereby minimizing the portion of the field off limits to the farmer.

Current emphasis is on establishing sensitivity to encroachment activities; we will address durability issues later. In keeping with that approach, we buried a short section of bare Fibercore SM600 fiber. The Hergalite was packaged in a paper sleeve, permitting it to slide. The paper sleeve was sandwiched in duct tape to provide some strength. The soil backfill was completed before the soil froze. The exception was over the sensing areas containing the Hergalite which was completed after a cold snap froze the soil approximately 6-inches deep. The frozen soil was excavated to expose unfrozen dirt. This was broken up and used to cover the sensing fibers. Then the remaining soil was backfilled, but not compacted. We verified continuous light path from the electrical boxes through each sensing fiber, both during and after the fibers were installed.

Thus we have optical fiber sensors:

- Buried at 4 depths
- Parallel and perpendicular to the gravel road
- Perpendicular to the 22-inch pipeline
- 24 inches above the 30-inch pipeline
- With one length with all 4 fiber types side-by-side.

ANR Pipeline will provide access to a range of construction equipment, including an ATV, rubber-tired trucks, backhoe, and cherry picker, track mounted 36,000 and 40,000 pound excavators and track mounted bulldozers-- John Deere 450 (15,000 pounds) and John Deere 750 (25,000 pounds).

SUMMARY OF PROJECT STATUS BY TASK

Task 1. Research Management Plan

The draft “Research Management Plan” was written. The DOE Contracting Officer’s Technical Representative (COR) made suggestions to improve the plan. GTI made the improvements and submitted the final plan. This plan was accepted. A kick-off meeting was held at GTI on May 14, 2002. A Hazardous Substance Plan was submitted. No hazardous substances will be used or produced at GTI or the pipeline field site.

Task 1 is complete.

Task 2. Technology Status Assessment.

GTI prepared and submitted a draft report describing the current state-of-the-art of the encroachment detection and impact detection. The DOE COR made suggestions to improve the report. GTI made the improvements. The final version was approved by the COR.

With the exception of updates, Task 2 is complete.

Task 3. Construct and Program Custom OTDR

Task 3 is to design, construct and program a custom Optical Time Domain Reflectometer (OTDR) capable of collecting and storing a waveform digitized as a function of time from each ~ 2 meter section of optical fiber.

The computer hardware was purchased and OTDR software was written. The software will be tested after the remainder of the OTDR is constructed and functioning as desired. The initial laser diode drive circuitry and the photodiode detector circuitry were designed and built. The process of debugging and refining the circuitry identified several problems with the electronics. Most of these were related to electrical components not performing to the manufacturer specifications. Design-arounds were developed. Next the detector amplifier was redesigned and the noise floor reduced by better than a factor of ten. Although, we believe most of the problems have been fixed, the OTDR is still not functioning as desired. The debugging process continues. GTI is continuing to make improvements in signal-to-noise ratio, both in the detection hardware and the light source. A new printed wiring board for the laser detector was completed and tested. A new printed wiring board for the laser transmitter was also completed and tested. A new type of detector, an avalanche photo-detector, was purchased. It was able to

detect weights on the Hergalite fiber as low as one pound. We are also investigating a brighter laser for use with the multimode fibers.

An Agilent E6000 Series Mini-OTDR was purchased. This OTDR is much improved over the OTDRs available at the start of this project. We were able to detect two weights on the Hergalite fiber in the laboratory. The processing time was one minute, which is still too slow for our needs. However, these results indicate that we are on the right track.

This quarter GTI re-evaluated all of the system components and discovered some improvements to the system. A solution to a noise problem was implemented. 100 MHz radio signals from O'Hare Airport had been setting the noise floor and therefore limited the signal to noise ratio. This solution should also help eliminate high frequency noise at site locations with microwave towers, including the ANR site. To facilitate sensitivity measurements, the Hergalite fiber was rewound on two 12-inch diameter cores to provide access to both ends and the middle of the fiber. Sensitivity has been improved. The technique can now detect a 0.2-pound weight resting on the Hergalite. We can also see changes in the load faster than 1 Hertz. A high-power diode laser was found and ordered. A new driver circuitry must be designed and built for the new laser. This should improve sensitivity by a factor of 10.

We originally planned on having the custom OTDR ready at the end of June 2002.

Task 4. Select, Install, and Test Optical Fiber Cables

GTI's work with FOIDS and a commercial OTDR demonstrated that construction equipment can be detected with an optical fiber system. However, these measurement techniques did not have the spatial or time resolution required to characterize and discriminate among interferences. Therefore, optical fiber sensitivity and durability will be evaluated. Recent measurements have shown that some newly designed commercial OTDRs are greatly improved. Static loads of one pound are detectable by observing a loss in optical return signal. The Hergalite specialty fiber appears to be the best of the fibers we are testing.

GTI has identified the most promising optic fibers for use as the distributed sensor. A suitable test site over an operating transmission pipeline has been found. The original goal was to test the fibers in the laboratory and at GTI's pipe farm facility. Because of the delay's in building a properly functioning OTDR, we have not been able to test the fibers. With the scheduled end of the project quickly approaching, we decided to install the fibers at the fiber site. Thanks to an unusually mild winter, we were able to install the fibers in early January 2003.

This task is complete, except for installation of the fibers at GTI and the long term testing of the fiber properties.

Task 5. Collect Data on Selected Right-of-Way Encroachment Types

GTI will make measurements of the signals created in the optical fibers as each encroachment type moves over the right-of-way. These data will be used for demonstrating sensitivity of technique and signal discrimination in Task 5.

This task will start after the OTDR is complete.

Task 6: Develop Techniques to Distinguish Potentially Harmful from Harmless Encroachment.

GTI will develop techniques to distinguish potentially harmful from benign interference in the right-of-way. Minimizing the number of false positives is the key technical barrier that must be surmounted for a successful technique.

This task will start after the OTDR is complete and Task 5 measurements made.

Task 7. Demonstrate Sensitivity and Discrimination Capabilities

GTI will demonstrate to NETL the ability to detect construction equipment and to distinguish potentially hazardous from benign encroachment.

This task is not schedule to start.

Technical Problems Encountered

No technical problems that will impact the ability to perform the project or project schedule have been encountered.

Project Management Issues

There have been several issues that have adversely impacted the schedule, including the need to find a new partner to provide the test site, delays in hiring a qualified person to assist with the project, and more time and effort required to obtain the required performance of the custom OTDR. Manpower allocation problems decreased but were not eliminated this quarter resulting in less technical work being performed than planned.

Additional funding was required to complete the Phase 1 proof-of-concept. GTI found an additional sponsor, Operations Technology Development. This project was put in place last quarter. We also added co-funding from GTI. The new end date for the entire project is scheduled for December 2004. A no-cost time extension for the NETL portion of the project was approved. The new NETL end date is September 2004. Total length of Phase 1 is 39 months.

Action Requested of DOE NETL and OTD Project Managers

No action is requested of the project managers.

Work Planned for the 1st Quarter of 2004 (March through June, 2004)

The following items are planned for the next quarter:

- Complete fine-tuning of the OTDR
- Test the programming of the digital oscilloscope to collect successive waveforms, store the data, and create waveforms corresponding to a specific distance along the fiber
- Test the ability to detect loads/vibrations on optical fiber in the laboratory.
- Begin testing at the test site.

CONCLUSION

Thirty months into the 39-month project, the following conclusions can be drawn:

- The initial laboratory measurements show that the Hergalite fiber is the most sensitive choice of optical fiber cables. The data indicate that the “reset issues” identified by the Hergalite manufacturer are not an issue for our application.
- Measurements with a newly desired and improved conventional OTDR have shown that small dynamic loads varying with frequencies greater than 1 Hertz can be detected. This positive result indicates that we are on the right track.
- The problems in building the custom OTDR should not affect the technical success of the project. That difficulties that are being encountered in the custom OTDR should not be surprising considering the difficulty of the detection problem.

LIST OF ACRONYMS AND ABBREVIATIONS

COR – Contracting Officer’s Technical Representative

DOE - Department of Energy

DSLPP – Digital Sonic Leak Pinpointer

FERC – Federal Energy Regulatory Commission

FOIDS - fiber optic intrusion detection system

GPS – global positioning system

GRI – Gas Research Institute

GTI - Gas Technology Institute

IGT – Institute of Gas Technology

IRNG – Infrastructure Reliability of Natural Gas

LED – light emitting diode

NETL - National Energy Technology Laboratory

NT - Nicor Technologies

OTDR - optical time domain reflectometry

REFERENCES

1. Analysis of DOT Office of Pipeline Safety (OPS) Natural Gas Pipeline Operators Incident Summary Statistics for 01/01/86 –06/21/1999. The statistics are available from OPS’s website <http://ops.dot.gov/>
2. National Transportation Safety Board Pipeline Accident Report for Texas Eastern Transmission Corporation Natural Gas Pipeline Explosion and Fire, Edison, New Jersey, March 23, 1994. PB95-916501. NTSB/PAR-95/01.
3. Francini, R.B., Kechter, G., Leis, B.N., Narendran, V.K., Kurmer, J., “Real-Time Monitoring to Detect Third-Party Damage: Phases III and IV” GRI Final Report GRI-01/0160, April 1999.
4. Doctor, R. H., Dunker, N. A., “ Field Evaluation of a Fiber Optic Intrusion Detection System—FOIDS” ” GRI Final Report GRI-95/0077, December 1995.
5. From the physics and astronomy website: www.phy-astro.gsu.edu
6. Fiber Optic Sensors an Introduction for Engineers and Scientists, edited by Eric Udd, John Wiley & Sons, Inc. New York 1991. pp-29-31.
7. John M. Senior, Optical Fiber Communications, Prentice/Hall International 1985, pp 69-70