Magnetotelluric Data, North Central Yucca Flat, Nevada Test Site, Nevada

By Jackie M. Williams, Brian D. Rodriguez, and Theodore H. Asch

Open-File Report 2005-1243

**U.S. DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY**

U.S. Department of the Interior

Gale A. Norton, Secretary

U.S. Geological Survey

P. Patrick Leahy, Acting Director

U.S. Geological Survey, Reston, Virginia 2005

Revised and reprinted: 2005

For product and ordering information:

World Wide Web: <http://www.usgs.gov/pubprod>

Telephone: 1-888-ASK-USGS

For more information on the USGS—the Federal source for science about the Earth, its natural and living resources, natural hazards, and the environment:

World Wide Web: <http://www.usgs.gov>

Telephone: 1-888-ASK-USGS

Although this report is in the public domain, permission must be secured from the individual copyright owners to reproduce any copyrighted material contained within this report.

Introduction.....	3
Magnetotelluric Method.....	3
Magnetotelluric Survey.....	5
Magnetotelluric Data.....	6
References Cited.....	9
Appendix: Magnetotelluric Data Plots.....	11
Figure 1, Station Locations.....	12

Introduction

Nuclear weapons are integral to the defense of the United States. The U.S. Department of Energy, as the steward of these devices, must continue to gauge the efficacy of the individual weapons. This could be accomplished by occasional testing at the Nevada Test Site (NTS) in Nevada, northwest of Las Vegas. Yucca Flat Basin is one of the testing areas at the NTS. One issue of concern is the nature of the somewhat poorly constrained pre-Tertiary geology and its effects on ground-water flow in the area subsequent to a nuclear test. Ground-water modelers would like to know more about the hydrostratigraphy and geologic structure to support a hydrostratigraphic framework model that is under development for the Yucca Flat Corrective Action Unit (CAU).

During 2003, the U.S. Geological Survey (USGS) collected and processed Magnetotelluric (MT) and Audio-magnetotelluric (AMT) data at the Nevada Test Site in and near Yucca Flat to help characterize this pre-Tertiary geology. That work will help to define the character, thickness, and lateral extent of pre-Tertiary confining units. In particular, a major goal has been to define the upper clastic confining unit (UCCU) in the Yucca Flat area. Interpretation will include a three-dimensional (3-D) character analysis and two-dimensional (2-D) resistivity model. The purpose of this report is to release the MT sounding data for north central Yucca Flat, Profile 7, as shown in [Figure 1](#). No interpretation of the data is included here.

Magnetotelluric Method

The MT method is a passive surface geophysical technique that uses the Earth's natural electromagnetic fields to investigate the electrical resistivity structure of the subsurface. The resistivity of geologic units is largely dependent upon their fluid content, porosity, degree of fracturing, temperature, and conductive mineral content (Keller, 1989). Saline fluids within pore spaces and fracture openings can reduce the resistivity of a resistive rock matrix. Resistivity also can be lowered by the presence of conductive clay minerals, carbon, and metallic mineralization. It is common for altered volcanic rocks to contain authigenic minerals that have resistivities of one tenth of those of the surrounding rocks (Nelson and Anderson, 1992). Increased temperatures cause higher ionic mobility and mineral activation energy, reducing rock resistivities significantly. Unaltered, unfractured igneous rocks are moderately to highly resistive (hundreds to thousands of ohm-m), whereas fault zones will show low resistivity (less than 100 ohm-m) when they are composed of rocks that are fractured enough to have hosted fluid transport and consequent mineralogical alteration (Eberhart-Phillips and others, 1995).

Carbonate rocks are moderately to highly resistive (hundreds to thousands of ohm-m) depending upon their fluid content, porosity, fracturing, and impurities. Marine shales, mudstones, and clay-rich alluvium normally are conductive (a few ohm-m to tens of ohm-m). Unaltered metamorphic rocks (non-graphitic) are moderately to highly resistive (hundreds to thousands of ohm-m). Tables of electrical resistivity for a variety of rocks, minerals, and geological environments are included in Keller (1987) and Palacky (1987).

The MT method can be used to probe the Earth's crust from depths of tens of meters to depths of tens of kilometers (Vozoff, 1991). Natural variations of the Earth's magnetic and electric field are measured and recorded at each MT station. The primary frequency bands used by the MT method are 10,000 to 1 hertz (Hz) from worldwide lightning activity and 1 to 0.0001 Hz from geomagnetic micro-pulsations. The natural electromagnetic waves propagate vertically in the Earth because the large resistivity contrast between the air and the Earth causes a vertical refraction of the electromagnetic wave transmitted into the Earth (Vozoff, 1972).

The natural electric and magnetic fields are recorded in two orthogonal, horizontal directions. The vertical magnetic field ("tipper") also is recorded. The resulting time-series signals are used to derive the tensor apparent resistivities and phases. First, the signals are converted to complex cross-spectra using Fast-Fourier-Transform (FFT) techniques. Then, least-squares, cross-spectral analysis (Bendat and Piersol, 1971) is used to solve for a transfer function that relates the observed electric fields to the magnetic fields with the assumption that the Earth consists of a two-input, two-output linear system. Prior to conversion to apparent resistivity and phase, the tensor normally is rotated. This rotation could be into principal directions that correspond to the direction of maximum and minimum apparent resistivity, or it may be made perpendicular to the survey traverses. For a two-dimensional (2-D) Earth, the MT fields then can be decoupled into a transverse electric (TE) mode (which uses the electric field perpendicular to the survey direction and the magnetic field parallel to the survey direction) and a transverse magnetic (TM) mode (which uses the electrical field parallel to the survey direction and the magnetic field perpendicular to the survey direction). Two-dimensional modeling generally is done to fit both modes. When the geology satisfies the 2-D assumption and the MT survey is perpendicular to the geologic strike, the MT data for the TE mode represent the electric field parallel to geologic strike, and the data for the TM mode represent the electric field across strike, along the survey direction. The MT method is well suited for studying complicated geological environments because the electric and magnetic relations are sensitive to vertical and horizontal variations in resistivity. The MT method is capable of establishing whether the

electromagnetic fields are responding to subsurface terranes of effectively one, two, or three dimensions. An introduction to the MT method and references for a more advanced understanding are in Dobrin and Savit (1988) and Vozoff (1991).

Magnetotelluric Survey

From October to December of 2003, data were collected at 51 stations across the Yucca Flat Basin. The station locations were chosen to constrain the geologic/hydrostratigraphic interpretation, for proximity to roads, and to avoid, where possible, electrical noise from power lines and vehicles. The low frequency data (0.0002 to 200 Hz) were collected with an Electromagnetic Instruments, Inc., (EMI) MT24/LF 24-bit system (EMI, 2002), and the high-frequency data (4 Hz to 23,000 Hz) were collected with a portable EMI MT-1 system (EMI, 1996). For the low frequency, horizontal electric fields were measured using three copper-copper sulfate porous pot electrodes placed in an L-shaped array with dipole lengths of 30 meters (m). Titanium electrodes were used in a similar array for the high-frequency data acquisition. The orthogonal, horizontal magnetic fields in the direction of the electric-field measurement array were sensed using EMI's high magnetic permeability, mu-metal-cored induction coils. For the low frequency data, two single-station recordings of the orthogonal, horizontal components of the electric and magnetic fields and the vertical magnetic field were acquired at Global Positioning System (GPS) referenced times and were used as remote references for each other. The high frequency data were recorded as non-remote referenced single stations.

The following table lists the 51 MT station locations as recorded using a GPS during field acquisition. Coordinates are referenced to the 1866 Clarke spheroid and North American 1983 Western United States datum. Longitude and latitude format is degrees, minutes, seconds. Universal Transverse Mercator (UTM) Zone 11 South and East units are in meters. Station elevation is given in meters. The accuracy of the x, y, z component is ± 5 m.

Table 1. Station Locations

Stations	Latitude	Longitude	Elevation	UTM 11S North	UTM 11S East	Remote
1	36,53'51.5	116,11'50.3	1456	4083613	571518	34
2	36,54'37.5	116,10'21.7	1373	4085052	573699	None
3	36,54'23.0	116,08'57.9	1304	4084623	575799	None
4	36,54'04.6	116,07'37.5	1254	4084071	577772	16
5	36,53'27.0	116,03'46.3	1149	4082968	583504	None
6	36,53'36.9	116,02'23.8	1101	4083296	585543	36
7	36,53'52.5	116,00'47.0	1100	4083795	587935	30
8	36,54'18.2	115,59'08.6	1229	4084622	590362	None
9	36,57'36.4	116,12'18.9	1536	4090540	570753	46
10	36,58'01.6	116,11'05.3	1437	4091331	572566	47
11	36,58'44.4	116,09'53.3	1445	4092663	574335	50

12	36,59'36.6	116,08'07.0	1463	4094297	576949	49
13	36,59'25.0	116,06'52.1	1335	4093950	578802	48
14	36,59'27.5	116,05'36.6	1243	4094053	580670	48a
15	36,57'34.8	116,04'48.9	1299	4090592	581884	51
16	36,57'38.3	116,04'02.2	1236	4090710	583035	4
17	36,57'26.7	116,02'16.2	1182	4090375	585659	29
18	36,57'26.5	116,00'34.3	1186	4090400	588182	None
19	36,57'22.4	115,59'29.2	1199	4090289	589792	35
20	37,04'01.5	116,12'12.2	1528	4102410	570816	45
21	37,03'20.9	116,11'12.8	1490	4101166	572297	44
22	37,04'02.3	116,10'01.1	1438	4102458	574055	43
23	37,03'23.6	116,08'16.2	1347	4101290	576659	37
24	37,03'06.3	116,06'52.0	1306	4100781	578746	38
25	37,02'54.4	116,05'09.4	1261	4100434	581280	39
26	37,02'14.0	116,04'05.3	1240	4099202	582876	40
27	37,01'07.0	116,02'00.7	1209	4097167	585977	41
28	37,01'06.3	115,59'45.8	1210	4097185	589311	42
29m	37,05'38.3	116,09'55.2	1501	4105419	574177	17
30m	37,04'54.5	116,08'10.0	1367	4104092	576786	7
31m	37,05'42.2	116,06'51.2	1334	4105583	578716	None
32m	37,05'41.0	116,04'57.9	1270	4105571	581515	None
33m	37,04'56.9	116,02'58.0	1240	4104238	584489	None
34m	37,04'07.5	116,01'20.1	1241	4102745	586922	1
35m	37,04'04.8	115,59'59.5	1265	4102681	588914	19
36m	37,04'19.6	115,58'36.3	1327	4103157	590961	6
37	37,08'26.4	116,08'34.4	1489	4110620	576125	23
38	37,08'16.7	116,06'16.5	1331	4110353	579528	24
39	37,07'46.8	116,04'18.5	1292	4109457	582448	25
40	37,07'23.2	116,02'24.8	1275	4108755	585262	26
41	37,07'06.8	116,01'19.1	1317	4108275	586891	27
42	37,06'45.2	115,59'55.7	1373	4107623	588955	28
43	37,10'03.5	116,08'33.9	1531	4113609	576110	22
44	37,10'07.6	116,08'00.0	1486	4113742	576943	21
45	37,13'13.1	116,08'41.3	1612	4119451	575875	20
46	37,12'25.4	116,07'13.2	1564	4118000	578059	9
47	37,13'35.5	116,04'19.3	1575	4120201	582325	10
48	37,13'50.6	116,03'39.5	1560	4120677	583300	13
49	37,13'54.7	116,02'25.7	1486	4120819	585119	12
50	37,13'12.2	116,03'52.7	1536	4119490	582990	11
51	37,11'50.5	116,02'44.8	1356	4116992	584688	15

Magnetotelluric Data

The recorded time-series data were transformed to the frequency domain and processed to determine a 2-D apparent resistivity and phase tensor at each site. Rotation of the impedance tensor allows for decoupling into the TE and TM modes. During the analysis and interpretation process, each station is

rotated to a fixed angle determined by the given nominal profile orientation. The data provided here have not been rotated from the original north-south, east-west acquisition orientation. Low frequency time series data were edited, and cross-power files were created with Egbert's (1997) multiple-station, magnetotelluric data-processing algorithms using remote references. Cross-power files were sorted to select optimal signal-to-noise time-series data sets (see Appendix at the back of this report).

The effects of near-surface resistivity anomalies can cause what are known as "static shifts" in the data (Sternberg and others, 1988). There were no significant static shifts in these data. Cultural features also can affect the measured magnetotelluric responses. These include fences, pipelines, communication lines, railways, and other manmade conductors.

The figures in the Appendix represent the field-processed MT data for each station (shown in **boldface** type in the table above) after the time-series data were converted to the frequency domain, and the tensor-transfer function was developed.

For each station, nine separate plots are given:

1. Apparent Resistivity(x and y symbols are xy and yx components)
2. Impedance Phase (x and y symbols are xy and yx components)
3. Rotation Angle
4. Impedance Skew
5. Multiple Coherency(x and y symbols are xy and yx components)
6. Impedance Polar Plots
7. Tipper Magnitude
8. Tipper Strike
9. HzHx (x symbol) and HzHy (o symbol) Coherency

Error bars (], [) on the Apparent Resistivity, Impedance Phase, Skew, Tipper Magnitude, and Tipper Strike plots represent probable errors within one standard deviation of the sample variance (Gamble and others, 1979).

Apparent resistivity is the approximate ratio of the electric-field strength to the magnetic-field strength at a given frequency. The impedance phase is proportional to the slope of the apparent resistivity curve on a log-log plot, but from baselines at ± 45 degrees (Vozoff, 1991). A measure of the dimensionality for MT data is provided by the impedance skew of the impedance tensor (Vozoff, 1972). If the effective measured resistivity response to the geology beneath a MT station truly is one or two dimensional, then the skew will be zero. Instrument and environmental sources of electrical noise can cause non-zero skew values. Skew values typically are small (about 0.1) for relatively low-noise recordings. Higher skews (above 0.2) are an indication of either the resistivity response to 3-D geology or higher levels of noise. Manmade electrical noise, such as power lines, power generators, and moving vehicles and trains, can have

a negative effect on MT data quality. All of these local disturbances can produce incoherent noise that mainly affects frequencies above 1 Hz. Other manmade electrical noise, such as direct current electric trains and active cathodic protection of pipelines, produces coherent electromagnetic signals that mainly affect frequencies below 1 Hz.

In the survey area, noise from a number of small power lines and small moving vehicles was negligible at distances greater than 0.4 km from the noise source. Power-line signal levels were measured at each site and typically were less than 20 percent of the maximum recordable signals. Noise from larger power lines, power generators, pipelines, and trains was negligible at distances greater than 5 km. Local lightning, wind, and rainstorms also can degrade data quality. Burying the magnetic induction coils and the electric dipole wires minimized wind noise.

Predicted values of the electric field can be computed from the measured values of the magnetic field (Vozoff, 1991). The coherence of the predicted electric field with the measured electric field is a measure of the signal-to-noise ratio provided in the multiple coherency plots. Values are normalized between 0 and 1; values at 0.5 signify signal levels equal to noise levels. For this data set, coherencies generally were at an acceptable level, except at times in the frequency ranges of 0.01 to 5Hz (often referred to as the "dead band").

The field-processed MT data include some scatter and poor signal-to-noise ratios. Spectral results were inspected visually for noisy data, and the best signal-to-noise field data were combined into the final plots.

The magnetotelluric impedance polar plots provide a measure of MT data dimensionality (Reddy and others, 1977). For 1-D resistivity structures, the principal impedance polar diagram (dashed line) is a circle. For 2-D or 3-D resistivity structures, the principal impedance polar diagram (dashed line) elongates either parallel or perpendicular to strike direction. Over resistors, the principal impedance polar diagram elongates perpendicular to strike direction, and over conductors, it elongates parallel to strike direction. For 2-D resistivity structures, the additional impedance polar diagram (solid line) attains the shape of a symmetric clover leaf. For 3-D resistivity structures, the additional impedance polar diagram (solid line) elongates in one direction, and its amplitude is comparable to that of the principal impedance polar diagram (dashed line).

The magnetotelluric "tipper" is calculated from the vertical component of the magnetic field. The tipper magnitude is a measure of the "tipping" of the magnetic field out of the horizontal plane (Vozoff, 1991). It will be equal to zero for the 1-D case. It typically increases to values between 0.1 to 0.5 and seldom approaches 1, as it responds primarily to vertical

and subvertical structures. The tipper magnitude of the stations discussed in this report ranged from 0.1 to 0.6 over the lower frequencies, indicating some vertical structure at depth. The tipper strike is used to help resolve the 90-degree ambiguity in the impedance rotation angle. The HzHx and HzHy coherency is a measure of the signal-to-noise ratio of the vertical magnetic field with respect to each of the orthogonal, horizontal magnetic-field directions. Values are normalized between 0 and 1; values at 0.5 signify signal levels equal to noise levels. These three-component magnetic-field coherencies provide a check on the signal-to-noise ratio of the measured values in the tipper magnitude and tipper strike plots.

References Cited

- Bendat, J.S., and Piersol, A.G., 1971, Random data-analysis and measurement procedures: New York, Wiley Interscience, 407#p.
- Dobrin, M.D., and Savit, C.H., 1988, Introduction to geophysical prospecting (4th ed.): New York, McGraw-Hill, 867#p.
- Eberhart-Phillips, Donna, Stanley, W.D., Rodriguez, B.D., and Lutter, W.J., 1995, Surface seismic and electrical methods to detect fluids related to faulting: Journal of Geophysical Research, v. 100, no. B7, p. 12919-12936.
- Egbert, G.D., 1997, Robust multiple station magnetotelluric data processing: Geophysics Journal International, 130, p. 475-496.
- EMI, 1996, MT-1 magnetotelluric system operation manual, version 3.2: Richmond, Calif., ElectroMagnetic Instruments, Inc., 220#p.
- EMI, 2002, MT24/LF System Operation and Maintenance Manual, version 1.0: Richmond, Calif., ElectroMagnetic Instruments, Inc., 72#p.
- Gamble, T.D., Goubau, W.M., and Clarke, J., 1979, Error analysis for remote reference magnetotellurics: Geophysics, v. 44, no. 5, p. 959-968.
- Keller, G.V., 1987, Rock and mineral properties, in Nabighian, M.N., ed., Electromagnetic methods in applied geophysics theory: Tulsa, Okla., Society of Exploration Geophysicists, v. 1, p. 13-51.

- Keller, G.V., 1989, Electrical properties, in Carmichael, R.S., ed., Practical handbook of physical properties of rocks and minerals: Boca Raton, Fla., CRC Press, p. 359-427.
- Nelson, P.H., and Anderson, L.A., 1992, Physical properties of ash flow tuff from Yucca Mountain, Nevada: Journal of Geophysical Research, v. 97, no. B5, p. 823-6841.
- Palacky, G.J., 1987, Resistivity characteristics of geologic targets, in Nabighian, M.N., ed., Electromagnetic methods in applied geophysics theory: Tulsa, Okla., Society of Exploration Geophysicists, v. 1, p. 53-129.
- Reddy, I.K., Rankin, David, and Phillips, R.J., 1977, Three-dimensional modelling in magnetotelluric and magnetic variational sounding: Geophysics Journal of the Royal Astronomical Society, v. 51, p. 313-325.
- Sternberg, B.K., Washburne, J.C., and Pellerin, Louise, 1988, Correction for the static shift in magnetotellurics using transient electromagnetic soundings: Geophysics, v. 53, p.1459-1468.
- Vozoff, Keeva, 1972, The magnetotelluric method in the exploration of sedimentary basins: Geophysics, v. 37, p.980-141.
- Vozoff, Keeva, 1991, The magnetotelluric method, in Nabighian, M.N., Electromagnetic methods in applied geophysics: Tulsa, Okla., Society of Exploration Geophysicists, v. 2, pt. B, p.641-711.

Appendix

Magnetotelluric Data Plots

There are nine separate plots for each station:

1. Apparent Resistivity for the rotated maximum (x symbol) and minimum (o symbol) modes
2. Impedance Phase for the rotated maximum (x symbol) and minimum (o symbol) modes
3. Rotation Angle for the impedance tensor (corresponds to the direction of maximum apparent resistivity)
4. Impedance Skew for the impedance tensor
5. Multiple Coherency for the rotated maximum (x symbol) and minimum (o symbol) modes of the electric field
6. Impedance Polar Plots (at 12 selected frequencies)
7. Tipper Magnitude for the vertical magnetic field
8. Tipper Strike for the vertical magnetic field
9. HzHx (x symbol) and HzHy (o symbol) Coherency

Refer to the "Magnetotelluric Data" section in this report for an explanation of these plots. The "priorities" listed on the plots were determined prior to data acquisition. During post-processing the priority ranking was changed.

Figure 1. Index map showing magnetotelluric (MT) stations in and near Yucca Flat, Nevada. MT stations acquired in 2003 are numbered stars 1-51. Dashed lines are Nevada Test Site Areas 1-30.

Station 29

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0050 Hz

.0127 Hz

.0317 Hz

.0500 Hz

.0768 Hz

.160 Hz

.635 Hz

1.602 Hz

3.308 Hz

8.075 Hz

20.020 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s29r17.a02

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:19 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s29r17.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:19 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0050 Hz

.0127 Hz

.0317 Hz

.0500 Hz

.0768 Hz

.160 Hz

.635 Hz

1.602 Hz

3.308 Hz

8.075 Hz

20.020 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s30r7.a02

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:20 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s30r7.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s30r7.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:20 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0002 Hz

.0016 Hz

.0061 Hz

.0198 Hz

.0397 Hz

.0763 Hz

.201 Hz

.488 Hz

1.270 Hz

3.296 Hz

8.057 Hz

20.020 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s31nr.a01

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:20 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s31nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s32nr.a01
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:21 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s32nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0050 Hz

.0127 Hz

.0317 Hz

.0610 Hz

.101 Hz

.201 Hz

.635 Hz

1.599 Hz

3.296 Hz

8.069 Hz

20.020 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s33nr.a01

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:22 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

Station 33

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s33nr.a01
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s33nr.a01
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:22 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0039 Hz

.0100 Hz

.0201 Hz

.0402 Hz

.0635 Hz

.159 Hz

.397 Hz

.763 Hz

1.984 Hz

5.035 Hz

32.257 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s34r1.a02

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:23 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s34r1.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s35r19.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:23 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s35r19.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:23 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s35r19.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:23 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s35r19.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s35r19.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0050 Hz

.0127 Hz

.0317 Hz

.0500 Hz

.0768 Hz

.160 Hz

.635 Hz

1.602 Hz

3.308 Hz

8.075 Hz

20.020 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s35r19.a02

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:23 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s35r19.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s35r19.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s35r19.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:23 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

.0009 Hz

.0039 Hz

.0100 Hz

.0201 Hz

.0402 Hz

.0635 Hz

.159 Hz

.397 Hz

.763 Hz

1.984 Hz

5.035 Hz

32.257 Hz

Client:

Remote:

Acquired: 19:5 Mar 08, 1998

Survey Co:

Rotation:

Filename: s36r6.a02

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 13:24 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Client:
Remote:
Acquired: 19:5 Mar 08, 1998
Survey Co:

Rotation:
Filename: s36r6.a02
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 13:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Client:
 Remote:
 Acquired: 19:5 Mar 08, 1998
 Survey Co:

Rotation:
 Filename: s36r6.a02
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 13:24 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz

12.207 Hz

41.504 Hz

79.000 Hz

122 Hz

172 Hz

340 Hz

720 Hz

960 Hz

2420 Hz

3550 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 16:2 Dec 02, 2003

Survey Co:USGS

Rotation:

Filename: nts29.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:20 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Priority 7

Client: Water Resources
Remote: none
Acquired: 16:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts29.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:20 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Priority 7

Client: Water Resources
 Remote: none
 Acquired: 11:2 Dec 04, 2003
 Survey Co:USGS

Rotation:
 Filename: nts30.avg
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 16:21 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz
 ***** Hz
 1200 Hz

12.207 Hz
 172 Hz
 2420 Hz

28.320 Hz
 270 Hz
 5210 Hz

79.000 Hz
 460 Hz
 11590 Hz

Client: Water Resources
 Remote: none
 Acquired: 11:2 Dec 04, 2003
 Survey Co:USGS

Rotation:

Filename: nts30.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:21 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Client: Water Resources

Remote: none

Acquired: 11:2 Dec 04, 2003

Survey Co:USGS

Rotation:

Filename: nts30.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:21 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts30.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz

12.207 Hz

28.320 Hz

79.000 Hz

***** Hz

172 Hz

270 Hz

460 Hz

1200 Hz

2420 Hz

5210 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 14:1 Dec 04, 2003

Survey Co:USGS

Rotation:

Filename: nts31.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:21 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Station 31

Client: Water Resources

Remote: none

Acquired: 14:1 Dec 04, 2003

Survey Co:USGS

Rotation:

Filename: nts31.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:21 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Priority 7

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 04, 2003
Survey Co:USGS

Rotation:
Filename: nts31.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:21 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

Client: Water Resources
 Remote: none
 Acquired: 14:1 Dec 06, 2003
 Survey Co:USGS

Rotation:
 Filename: nts32.avg
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 16:22 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Station 32

Client: Water Resources
 Remote: none
 Acquired: 14:1 Dec 06, 2003
 Survey Co:USGS

Rotation:
 Filename: nts32.avg
 Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
 Plotted: 16:22 Dec 08, 2004
 < EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 06, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 14:1 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts32.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:22 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz

12.207 Hz

41.504 Hz

79.000 Hz

122 Hz

172 Hz

340 Hz

720 Hz

960 Hz

2420 Hz

3550 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 11:2 Dec 09, 2003

Survey Co:USGS

Rotation:

Filename: nts33.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:23 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Priority 7

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:2 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts33.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz

12.207 Hz

28.320 Hz

79.000 Hz

***** Hz

172 Hz

270 Hz

460 Hz

1200 Hz

2420 Hz

5210 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 13:4 Dec 09, 2003

Survey Co:USGS

Rotation:

Filename: nts34.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:26 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:4 Dec 09, 2003
Survey Co:USGS

Rotation:
Filename: nts34.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:26 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

APPARENT RESISTIVITY

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE PHASE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

ROTATION ANGLE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

IMPEDANCE SKEW

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

E MULT Coh.

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

POLAR PLOTS

Priority 7

4.394 Hz

12.207 Hz

41.504 Hz

79.000 Hz

122 Hz

172 Hz

340 Hz

720 Hz

960 Hz

2420 Hz

3550 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 13:2 Dec 02, 2003

Survey Co:USGS

Rotation:

Filename: nts35.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:24 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

TIPPER MAGNITUDE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

TIPPER STRIKE

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

HzHx.x Coh HzHy.o

Priority 7

Client: Water Resources
Remote: none
Acquired: 13:2 Dec 02, 2003
Survey Co:USGS

Rotation:
Filename: nts35.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:24 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

4.394 Hz

122 Hz

960 Hz

12.207 Hz

172 Hz

2420 Hz

41.504 Hz

340 Hz

3550 Hz

79.000 Hz

720 Hz

11590 Hz

Client: Water Resources

Remote: none

Acquired: 11:3 Dec 06, 2003

Survey Co:USGS

Rotation:

Filename: nts36.avg

Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4

Plotted: 16:23 Dec 08, 2004

< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >

Client: Water Resources
Remote: none
Acquired: 11:3 Dec 06, 2003
Survey Co:USGS

Rotation:
Filename: nts36.avg
Channels: Ch1 Ch2 Ch3 Ch4 Ch5 Ch3 Ch4
Plotted: 16:23 Dec 08, 2004
< EMI - ElectroMagnetic Instruments >