**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1995

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DECLASSIFIED

HW-25042

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of *for Doc*By *man 1973*
*JH Wells 11-19-94*Verified By *J E Savely 11-22-94*

NOT UCNI

- # 1. RW Benoliel
- # 2. VR Copper - PE Collins
- # 3. RB Richards - JB Work
- # 4. JR Chapman - WN Mobley
- # 5. T Prudich - LM Meeker
- # 6. OF Beaulieu - SC Smolen
- # 7. FW Albaugh - FJ Leitz
- # 8. R Ward - GL Flint
- # 9. OJ Wick
- # 10. 700 File
- # 11. 300 File
- # 12. Pink Copy
- # 13. Yellow Copy

July 16, 1952

**SPECIAL RE-REVIEW
FINAL DETERMINATION
DECLASSIFICATION CONFIRMED**

BY *J.P. Morrison* DATE *5-19-81*
BY *GE Barber* DATE *5-27-81*

This document consists of
1 pages. No. *13* of
13 copies. Series *A*

R. W. Benoliel
Process Assistant
Separations Technology Unit
Engineering Department

COPY 1 OF 1

SERVICE OF REDUCTION BOMBS, PLUTONIUM PURIFICATION AND FABRICATION
234-5 BUILDING

In reply to your request for information pertaining to the life of the reduction bombs in both the RG and RM Lines of the Plutonium Purification and Fabrication operations in the 234-5 Building, the following data are submitted.

The expected average life to rupture of the RG Line Bomb of carbon steel subjected to an internal pressure of 450 psig is ten hours at 750°C. The expected average life of the RM Line bomb of V-36 alloy is more than 100,000 hours at 750°C under the same operating conditions. These expected average life values do not include any calculated factor of safety. Since they are average figures, some bombs could be expected to have shorter life to rupture.

The RG Line bomb of carbon steel is definitely hazardous under the extreme service conditions of 450 psig and 750°C. If the use of carbon steel is to be continued it is recommended that the bombs be redesigned to reduce unit stresses.

A review of the high temperature properties of a number of materials for reduction bomb service has been made and will be issued in a separate report.

R. Ward
Head, Metallurgy
Applied Research Unit
ENGINEERING DEPARTMENT

R Ward/dh

RECEIVED

300 AREA
CLASSIFIED FILES

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER