**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1995

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

(CLASSIFICATION)

DOCUMENT NO.

HW-44353

DATE _____

July 18, 1956

COPY NO. AND

GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION

☒ RESTRICTED DATA

THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED IN THE ATOMIC ENERGY ACT OF 1954
ITS TRANSMITTAL OR DISCLOSURE OF ITS
CONTENTS IN ANY MANNER TO AN UNAUTHORIZED
PERSON IS PROHIBITED

OTHER OFFICIAL UNCLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

J. H. Brown

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS TO IT. WHEN NOT IN USE, IT MUST BE STORED IN AN APPROVED LOCKED REPOSITORY WITHIN AN APPROVED GUARDED AREA. WHILE IT IS IN YOUR POSSESSION AND UNTIL YOU HAVE OBTAINED A SIGNED RECEIPT FROM CLASSIFIED FILES, IT IS YOUR RESPONSIBILITY TO KEEP IT AND ITS CONTENTS WITHIN THE LIMITS OF THIS PROJECT AND FROM ANY UNAUTHORIZED PERSON. ITS TRANSMITTAL TO, AND STORAGE AT YOUR PLACE OF RESIDENCE IS PROHIBITED. IT IS NOT TO BE DUPLICATED. IF ADDITIONAL COPIES ARE REQUIRED, OBTAIN THEM FROM THE RELATED ISSUING FILE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW.

[illegible]

(CLASSIFICATION)

 

DECLASSIFIED

HW-44353

DISTRIBUTION

1. J. M. Atwood	12. W. J. Ozeroff
2. J. M. Batch	13. P. H. Reinker
3. J. H. Brown	14. C. R. Richey
4. L. P. Bupp - <i>E. C. Wood</i>	15. G. J. Rogers
5. J. J. Cadwell	16. H. P. Shaw
6. V. R. Cooper	17. R. J. Shields <i>J. H. Sho</i>
7. R. L. Dickeman	18. C. D. Wilson
8. J. W. Finnigan	19. E. C. Wood <i>H. F. Zuhre</i>
9. J. W. Goffard	20. F. W. Woodfield <i>File Copy</i>
10. O. H. Greager	21. H. F. Zuhre <i>300 Files</i>
11. R. T. Jaske - <i>R. J. Shields</i>	

REPORT OF THE SPECIAL STUDY GROUP

The following personnel have contributed to the conclusions contained in this report:

J. M. Atwood
J. M. Batch
J. H. Brown
J. W. Finnigan
J. W. Goffard
R. T. Jaske
C. R. Richey
G. J. Rogers
R. J. Shields
C. D. Wilson
E. C. Wood

July 18, 1956

This document consists of
21 pages. No. 5 of
21 copies. [REDACTED]

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

[REDACTED] contains restricted data
Energy Act of 1954 [REDACTED] the disclosure of its
[REDACTED] manner to an unauthorized person is prohibited.

MASTER

DECLASSIFIED

INTRODUCTION

The special study group was activated by a charter letter from Sub-Section Managers of Pile Technology on June 20, 1956. The principal objectives were: (1) to collect the information which is presently available for new reactor design and to determine what information should be developed, (2) to make a guess at pile variables, and (3) to point out development programs which must be pursued to achieve a detailed design start in two years.

The study was restricted to graphite moderated reactors with H_2O , D_2O , and organic coolants. The program was to determine technical feasibility only and detailed economic considerations were not to be included.

This report presents the conclusions of the group and some of the reasoning behind these conclusions.

SUMMARY OF CONCLUSIONS

Two general lines of attack appear possible on the problems associated with a plutonium producer which can also produce significant amounts of electrical energy. The first of these is a high pressure water cooled reactor. Because of fuel problems, an enriched lattice using extended surface fuel elements appears more feasible than a natural uranium lattice. Because little experimental physics information is available on these lattices, a program to develop such information appears to be of primary importance.

The much reduced fuel difficulties and the enormous simplification in the plumbing of the reactor make organic coolants look very attractive. Information on organics is at present very sketchy and these coolants may pose problems which are not obvious at this time. In spite of this, the potential advantages appear to warrant a sizable research and development program which should parallel, and in some cases over-lap, the water-cooled program.

There are, of course, many problems and unknowns associated with either reactor type. These problems are pointed out in the following section of the report. None of these problems appears to be insoluble, and at the moment at least, it appears that either reactor type will be feasible from a technical point of view.

Although low pressure, low temperature operation will not be discussed in this report, it appears that much of the research and development for the power producing reactors would also be applicable to a low temperature reactor.

DISCUSSION

I. Lattice Characteristics

Considerable information, both theoretical and experimental, exists regarding lattices which will operate on natural uranium. On the other hand, the knowledge of enriched lattices, especially with cluster elements or large hollow or I & E slugs, is almost entirely theoretical in nature. Because of this fact, the discussion will be arbitrarily divided into two parts. Although the fringe driven reactor concept will not be discussed in detail, the idea should be retained and re-evaluated when further lattice information becomes available.

DECLASSIFIED

A). Natural Uranium

The natural uranium lattice with solid and with some cored slugs has been investigated rather thoroughly over the past years. Various slug sizes from 0.925" to 1.66" have been checked in various lattices from 5-3/16" up to 12-3/8". The reactivity measurements can be fit by theory very well over a large fraction of these ranges but for the largest slug sizes, the agreement between theory and experiment is not so good.

The results indicate that a light water-cooled lattice which must operate on natural uranium must be fueled with solid or modestly cored fuel elements. A few scattered experiments have been performed on metallic cluster elements. The results appear below:

<u>LATTICE</u> <u>(Inches)</u>	<u>RODS IN</u> <u>CLUSTER</u>	<u>C/U</u>	<u>H₂O/U</u>	<u>Al/U</u>	<u>BUCKLING</u> <u>WET</u>	<u>BUCKLING</u> <u>DRY</u>
10-3/8	5	52	0.632	0.509	-12	63
10-3/8	7	39	0.258	0.449	--	13
14	5	95	0.632	0.509	-69	83
14	6	83	0.445	0.479	8	87
14	7	71	0.258	0.449	19	90

Rod Size = 0.926"

Graphite Density = 1.65

The best of these lattices is about 1500 ih short of the reactivity required for operation. Oxide fuel elements made from natural uranium will not be any better, and will probably be much worse, from a reactivity standpoint than metallic elements. The conclusion appears inescapable that light water cooled, natural uranium lattices require single rod fuel elements. On this basis, the lattice spacing and slug size appearing in Case I was chosen. (See page 27).

When heavy water is chosen as a coolant instead of light water, the physics is no longer so restrictive. Theoretically, lattice bucklings near 125 μ b are obtainable with single rod fuel elements. The excess reactivity could be carried in the form of control rods to produce tritium or the lattice can be deliberately designed away from maximum reactivity to provide gains in initial plutonium conversion ratio of about 6%.

Since ruptured single rod fuel elements in hot water, light or heavy, are extremely dangerous, an extended surface fuel element (eg. rod cluster or plate) is much preferred. With H₂O coolant this was not possible but with D₂O a natural uranium cluster element might produce sufficient reactivity to be technically feasible. This question can only be resolved by experiment and such an experiment should be performed. The solid rod D₂O cooled lattice appears to be more reactive wet than dry over a considerable lattice range. Whether this "fail safe" feature holds in D₂O cooled cluster lattices must also be checked experimentally.

DECLASSIFIED

With organic coolant in place of light water a modest reactivity gain (200 - 300 ih) would be expected. Organic coolant, because of the very low pressure required at high temperatures, offers the possibility of using magnesium in place of zirconium for can material and possibly for tubes. This is very attractive from a physics standpoint since bucklings as high as perhaps 135/ub can again be obtained with single rod fuel elements. Again the excess reactivity can be traded for tritium production or for plutonium conversion ratio. Perhaps a natural uranium cluster element could be made to operate with organic coolant if very high specific power is required although the rupture problem which forces consideration of cluster elements in hot water, apparently disappears when organic coolant is used.

A chart showing the bucklings of various lattices appears on the following page. These curves are all computed using the same theory and hence, although the absolute numbers may be somewhat suspect, the relative effects of various coolants are fairly obvious.

To summarize the present status of natural uranium lattices:

- (1) Light water cooling forces the use of solid, cored, or perhaps I & E fuel slugs. This conclusion is fairly well backed up by experiments.
- (2) Heavy water, on a theoretical basis, will give much more flexibility and will perhaps allow a cluster element to be used. No supporting experimental evidence at the moment.
- (3) Organic coolant, on a theoretical basis, will also provide more flexibility than H₂O and, if magnesium tubes and cans can be used, will compare favorably with D₂O on both a reactivity and conversion ratio basis. Experimental evidence required for these conclusions.

In view of the unknowns, the following experimental lattice physics program is proposed for natural uranium. Buckling measurements may be made in the small 4' exponential pile which should give an accuracy of ± 6 micro bucks. Following the exploratory program the buckling of the lattice actually chosen should be checked in a full size exponential experiment. The bucklings should be measured for various lattice spacings while dry, with H₂O, with D₂O, and with organic coolant once the stack is laid up. Conversion ratios must also be determined for those lattices which appear practical from a reactivity standpoint.

OUTER WATER ANNULUS	I & E SLUGS - CORED SLUGS	OXIDE SLUGS	CLUSTER ELEMENTS
Specified by ID and Flow Considerations	1.36" OD - 0.50" ID	None, unless the check to be run by the exponen- tial people in- dicates that ox- ide slugs are much better than presently believed.	One cluster geom- etry which will fit into the 2+" Dia. lattices. The actual element to be chosen by agree- ment among fuels, heat transfer and physics people.
	1.45" OD - 0.75" ID		
	1.66" OD - { 0.81" ID 1.1 " ID		
	2+" OD - 1 " ID which could be drilled larger.		

DECLASSIFIED

BUCKLING $\times 10^6 \text{ cm}^2$

Some of the slugs above are presently on hand while others must be procured. Thus, the numbers were chosen at least partially on the basis of availability and can be varied if desired. The first three sizes cover approximately the range expected to produce a workable organic lattice while the last size, which was purposely left indefinite should provide a natural uranium check on large slugs and cluster elements which will probably have to be enriched to become operable.

The above program is expected to take roughly 6 man years in the exponential phase. A one year time interval is assumed and this year does not include any time delays for procurement of any new graphite or fuel elements which are required.

B) Enriched Lattices

When enriched uranium lattices are considered, the problem of how and where to direct a development program becomes very complex. Conclusions were based on the following considerations.

By use of sufficient enrichment almost any lattice may be made to run and hence, any lattice is, in a very narrow sense of the word, technically feasible. Economic analysis must, of course, be used to decide which lattices are feasible in a practical sense. Because the enrichment level is now a variable, a set of lattice experiments to cover all possible geometries and enrichments is a physical impossibility. It seems that the only possible way of optimizing a lattice is by combining economics with a workable physical theory which is dependable within known limits of error.

The statements made in various reports and documents regarding enriched lattices are based, with a few exceptions, on calculations which have never been experimentally checked. Thus, the most urgent task is to verify or refute the following theoretical predictions:

- 1) Improvements in lattice performance may be obtained by using larger diameter solid slugs in an undermoderated lattice and making up the loss in reactivity by enrichment. Indications are that gains are still being made at a 1.8" slug diameter.
- 2) It is possible to push a metallic cluster element close to the cross over point, make up the reactivity loss by enrichment and come out with a very respectable initial conversion ratio. (~ 0.85).

The experimental program should cover a range of lattices which are predicted by theory and economics to be most attractive. If the calculations are confirmed, then there is data in hand immediately upon which to base design. If theory proves faulty, then at least some empirical results are available from which theory can possibly point out a few additional experiments to determine an optimum lattice. There will be a time delay of at least modest length before exponential experiments on these large lattices can begin. This time should be utilized by theoreticians and economists to compute a series of similar cases around an optimum configuration. Since predictions have been made involving both low specific power (solid or cored slugs) and high specific power (cluster elements or over sized I & E slugs) it appears that both cases should be checked experimentally.

DECLASSIFIED

For the low specific power cases, two slug sizes and two enrichments which bracket the predicted optimum should be checked experimentally for both reactivity and conversion ratio. In this way, both the absolute predictions and the predicted differences between two similar cases can be checked.

For the high specific power cases, a large variety of geometries as well as enrichments is possible. The following procedure appears practical. Choose a fuel geometry which appears feasible to fuels and heat transfer people by assuming a reasonable value of specific power. Have physics personnel and economists predict the optimum lattice spacing together with values of enrichment required, buckling achieved and initial conversion ratio for lattice spacings around the optimum. Perform experiments on three lattice spacings and two enrichments around the optimum and check the theoretical predictions as previously described.

C) Oxide Elements

Using uranium oxide will apparently require an extended surface fuel element in order to control core temperatures. The use of oxide clusters would not appear possible from a physics standpoint unless the metallic clusters turn out to be very satisfactory. Hence, it appears logical to defer any experimental physics program on oxide elements until after the program on metallic clusters is complete. A better founded decision on whether or not to proceed can be made at that time.

D) Temperature Coefficients

In addition to buckling and conversion ratio information, the temperature coefficients of reactivity must also be known if a confident choice of lattice is to be made. Present information indicates that coefficient measurements in the PCTR will be slow work indeed. The estimate was made that six weeks would be necessary to check a single lattice at three exposures—indeed six months is estimated for the first lattice. Metal coefficient measurements have been made in the test pile and presumably those can be extended to other slug geometries. Also, the exponential people are working on a method for heating an exponential pile to approximately 300°C.

In spite of these possibilities, the measurement of temperature coefficients is going to be a slow process. In addition the lattices which can be checked are limited. Wet coefficients using either H₂O or D₂O cannot be measured at high temperatures without pressure provisions which are not presently available. This difficulty can perhaps be partially overcome by using an organic with a high boiling point. Since organics are being seriously considered as coolants, this procedure would appear to be very desirable. Beside the restriction on coolant there is a size restriction on PCTR experiments. Lattices greater than about 8.5" will probably not be possible in the PCTR oven. Since cluster element lattices are presumed to be at least this large, it may be necessary to use the hot exponential pile.

Because of the slowness and difficulty in getting results on temperature coefficients, the best procedure appears to be to check buckling and conversion ratio first and, once a particular lattice is chosen, check the temperature coefficients. Of course, those lattices for which theory predicts ridiculous temperature coefficients should be regarded with suspicion.

DECLASSIFIED

II. Organic Coolants

The organic coolants such as diphenyl seem to offer tremendous advantages over water. First of all, corrosion is believed to be very low on all pertinent metallic materials. In particular, the organics apparently do not react with uranium even at high temperatures (750°F). A second advantage is the very low saturation pressures of organics at any temperature which can reasonably be expected in a Hanford type reactor.

Organic coolants have some disadvantages but the startling thing is the lack of any obvious major disadvantages. Both lattice physics and fuel difficulties are improved by the substitution of organic coolant for water which is indeed a unique development. Because of the present state of knowledge, organics certainly warrant an extensive development program. On the other hand, it would be foolish to assume that all the problems of an IPR are solved and to drop all other lines of development. Until organics prove their promises, development work on a recirculating water reactor should certainly be carried on.

A discussion of the present knowledge of organics is contained in the trip report* of Atwood, Hanthorne, and Cook and only a few of the high spots will be mentioned here. First of all, the number of organic mixtures which are possible is very large and each may have definite advantages. Monoisopropylbiphenyl, hereafter referred to as MIPB, appears to offer the most promise at the moment. Its melting point is - 40°C and its boiling point at atmospheric pressure is 290°C. Its cost is estimated on a production basis at 20 cents per pound. The total decomposition rate is 30% at 10¹⁸ nvt. This rate is based on tests in which only 5% decomposition was actually attained.

Corrosion rates for various materials are presently based on out-of-pile bomb type autoclave tests of fairly long exposure - up to 3000 hours. The observed rates are very low ranging from essentially zero for aluminum up to 1.9 mils per year on magnesium. The presence of 300 ppm water in the organic may have produced at least part of the corrosion which was observed and perhaps very dry organic will exhibit even better corrosion properties. Dynamic, in pile corrosion tests appear to be urgently needed for the usually considered pile materials.

The bomb-type tests showed a corrosion rate of 1.25 mils per year for 750°F organic on uranium. If this very low reaction rate also holds for circulating, in-pile cases, then the slug rupture problem can be reduced to the status of a major nuisance.

The experiments thus far performed used technical grade chemicals which contained some impurities. In spite of this, the activity of organics is very low and to some extent short-lived. A one gallon sample read 50 mr at one inch after seven operating days in the MTR.

The organics are known to suffer radiation damage and this damage rate rises sharply at a very high temperature - 810°F for diphenyl. The corresponding temperature for MIPB is not known. The damage product seems to vary with the material, being a soluble tar for MIPB.

* "Trip Report - Survey of Organic Coolants", Atwood, Cook, Hanthorne. (Unclassified). July 9, 1956.

DECLASSIFIED

The physical properties of MIPB are substantially unknown. The organics are somewhat toxic, but this seems to cause no concern if ordinary cleanliness is maintained. The materials are also cancer forming but again chemical plants have handled them in the past with minimum special precautions. The organics will burn and hence cause a fire hazard if used as reactor coolants. MIPB forms a fog which settles out into a liquid layer even at room temperature and hence will not provide as large an explosion hazard as diphenyl which forms a dust at room temperature.

The following facts about organic coolants must be investigated in a development program:

- 1) Measurement of physical properties (density, viscosity, thermal conductivity, heat capacity) and the effects of temperature and irradiation on those properties.
- 2) Rate of decomposition and the quantity of gases and polymers formed under combined radiation and high temperature.
- 3) Experiments to measure heat transfer coefficients as a function of heat flux and coolant composition. The temperature threshold and effects of "coking" must be determined.
- 4) The technique of purification (distillation, adsorption) must be investigated and the optimum coolant composition determined.
- 5) Corrosion effects on various materials under dynamic conditions including the effects of water and oxygen impurities. The possible formation of hydride with uranium needs checking.
- 6) A safety program of simulated leaks and flammability checks together with development of a method for switching from hot organic to cold back-up water.
- 7) Activity determinations - induced activity, pick up from walls and the effects of ruptures. Tests of unclad fuel elements.
- 8) Development of high temperature coolant system components.

III. Control Methods

Control of the IPR can be accomplished by a variety of control rod systems. The use of a standard Hanford system is, of course, possible with very little development. Minor modifications would be possible. For example, short rods entering from the far side or a complete two sided control rod system is possible.

Other systems have been proposed which appear to be worthy of some development effort. Rods containing absorbers which produce saleable isotopes, in particular lithium, appear to offer no great mechanical problems. This feature becomes increasingly desirable as the amount of control carried in the pile becomes larger. If complete xenon override is to be possible by withdrawal of poison, then this feature becomes almost a necessity.

DECLASSIFIED

Instead of withdrawing poison, highly enriched uranium rods could be held out of the pile under normal operation and inserted to provide xenon override. From the results at K pile startup, a column of J-slugs in the full sized flattened reactor was worth about 14 ih. From this it appears that a large number of enriched control rods would be necessary to provide approximately 1000 ih for xenon over-ride. Perhaps the number could be reduced somewhat by increasing the enrichment and the size of each rod, but the idea appears to involve a very sizable U^{235} inventory. Considerable analysis would be necessary to arrive at the minimum inventory required for various reactors.

"Shutter" rods appear to be feasible from a mechanical point of view. The amount of control available and the ability to make the rod "disappear" have not been demonstrated. Such a rod system would have considerable advantage in controlling hot spots and would obviate the necessity for inner and outer rod rooms since the total rod travel could be limited to one foot or less. They would require considerable cooling, however, and provision for charging and discharging on the side faces of the reactor would have to be provided in the design of such a system. In any event, some sort of stationary shim control should be developed especially if the reactor is to operate close to real limits.

The justification for these systems cannot be made without a detailed evaluation of a specific reactor proposal. They are listed because it appears that such designs are capable of realization from a mechanical standpoint, and because the concepts represent fairly modest departures from present technology which could be developed during a two year period.

The concept of moderator control with D_2O appears to involve a very large expense. The amount of D_2O to achieve xenon over-ride would be prohibitively large. Even the idea of achieving some measure of control by changing graphite temperature through the gas composition does not appear feasible in a high temperature recirculating reactor unless much higher graphite temperatures are possible. With coolant temperatures near $300^{\circ}C$, plus the temperature difference required for heat removal from the graphite, the limit of $650^{\circ}C$ on graphite temperature leaves little room for temperature swings for control purposes. This is especially true since the $650^{\circ}C$ can be achieved only with pure helium. Thus, unless the present graphite temperature limits can be substantially relaxed, there seems little chance of getting either total or hot spot control from changing gas composition.

IV. Instrumentation

Nuclear instrumentation similar to that in use in the present reactor is sufficient to allow design and construction of a new reactor. There is considerable incentive for improved instrumentation even in the present reactors and this incentive of course also exists with respect to a new reactor. An improvement over the present octant monitoring system is desirable for operating convenience and control precision. Developments now proceeding on the sub-critical monitor and other nuclear instruments will be very useful on a new reactor. Overall, there appear to be no nuclear instrumentation gaps which would prohibit construction of a new reactor.

DECLASSIFIED

For a high pressure water system a reliable flow meter must be developed. Flow meters for these conditions do exist but they are very expensive and their reliability for long term operation is questionable. Similar difficulties, though not of the same magnitude apply to temperature monitoring equipment. If a boiling cycle is chosen, an enthalpy meter, which does not now exist, must be developed if individual tube monitoring is to be possible.

An adequate number of replaceable graphite thermocouples appears to be necessary for a new reactor.

With organic coolants, the instrumentation problems will be essentially the same although slug rupture considerations may make the flow monitoring problem less critical. Possible "coking" of hot heat transfer surfaces on the other hand may produce plugging of the tube and require very sensitive flow monitors. The reduced operating pressure will simplify the flow monitor design. On the other hand, organics are "wetter" than water, and since leaks will not be tolerated, a completely leak-tight flow monitor system may introduce some difficulty. There do not, however, appear to be any insoluble problems apparent with organic coolants.

Fuel element rupture detection in a recirculating reactor is very important - especially so in a high temperature water-cooled reactor. Aside from the very critical tube plugging problem discussed under reactor safety, the release of fission products into one channel will rapidly produce contamination in all channels and in the external piping as well. Rapid detection of a rupture and rapid location of the proper tube is therefore essential in a recirculating water reactor. The present gamma monitor, on a crossheader basis is quite sensitive and would be satisfactory for detection of ruptures. However, the requirement of rapid tube identification implies that additional monitoring facilities would be necessary. The first choice is to monitor every tube. This approach is complicated in two respects. First, the sheer number of monitors required may be excessive unless more compact equipment is developed. Second, the problem of maintaining a constant delay between tube outlet and monitoring point would be aggravated by the number of sample lines involved and would be further aggravated in a pressurized, high temperature system.

A second choice which is simpler from a plumbing and instrumentation standpoint is a coordinate monitoring system. A problem peculiar to this system is that of maintaining a balanced individual tube flow into each coordinate monitoring header.

For an organic coolant, the development work required for rupture monitoring is unknown. It would appear that the problem is less critical since the consequences of continued operation with a rupture are presumably far less severe than with high temperature water. In addition, the low effluent activity may permit a simpler system.

V. Reactor Safety

Specification of the speed of control and the total control strength required must await the choice of a particular lattice. In general, the larger the reactivity jump following loss of coolant, the faster must the safety controls respond. Also,

the higher the exposure reached, the larger must be the total control strength if the reactor is to be maintained sub-critical at all times following coolant loss.

If organic is used as a coolant, the nuclear properties of the lattice alone will specify the speed of control required. Use of high temperature water, light or heavy, will introduce the problem of tube blockage by slug ruptures. Results to date indicate that at 280°C the time available between first contact of water with uranium and complete tube blocking is about two minutes in a standard Hanford assembly. This fact places very stringent requirements on the rupture detection and tube location devices and in addition demands that either the rupture be removed almost instantaneously or that the water temperature be sharply reduced in a matter of seconds.

Location, detection, and removal of an offending slug within one minute or less by a completely reliable mechanism appears to be impossible at the moment. It would be possible to scram the reactor and switch over to a low temperature coolant on a once through basis. The principal objection here is that the entire reactor and its external piping would be subjected to terrific thermal shock. Even in the present reactors a scram from equilibrium is frequently followed by rupture indications and for a high temperature reactor the number of ruptures caused by the rapid reduction in temperature could be very large.

An alternate procedure would be to switch the offending tube only over to a low temperature coolant. This could be accomplished by a valve on the front supplied by a separate small header. Once the coolant temperature is reduced, discharge of the tube can proceed either while the reactor is operating or following a shut-down depending upon the requirements imposed on the reactor. Discharge during operation would probably require check valves between the outlet nozzle and header to prevent flushing of outlet water to steam when the nozzle is opened.

The problem of tube blockage is so important and difficult that indeed no solution may be possible for a standard Hanford assembly although the wafer slug offers at least a ray of hope in this direction. It is for this reason that the organic program and the development of enriched cluster lattices are recommended. On the other hand, if natural uranium and light water cooling are required, then the problem must be solved or a power producer of the Hanford type is simply not feasible.

Providing the lattice characteristics are such that very fast acting safety controls are not required, it might be possible to forego any vertical safety rods at all and simply design an over-sized ball system. Only a fraction of the total channels would need to trip on a "normal" scram with the remainder held in reserve for emergencies in which the maximum amount of control is required. Multiple charges would be necessary in the normally dropped channels to allow immediate scram recovery.

A supplementary cooling system which is physically separate from the primary system can be designed to provide backup cooling in the event the primary system fails. Present technology is sufficient to provide such a design in a water cooled reactor while some development would be necessary with an organic coolant to permit change-

DECLASSIFIED

over from hot organic to cold water. This could perhaps be accomplished by inserting first a small quantity of cold organic as a buffer and following this with cold water. The assumption is made here that water would be the only feasible backup coolant.

The principal problem to be solved before designing such a system is the determination of the time between scram and assumption of the heat removal load by the backup coolant. For example, a system furnishing 10% of the normal flow can adequately cool the reactor 5 minutes after a scram. Shorter times will require larger systems - a full sized replacement system would be necessary for zero time. For practical economic reasons a supplementary system which can supply adequate cooling with no warning and which is as damage resistant as the pile structure itself appears infeasible.

Two important considerations influence the containment requirements for a power generating reactor. First of all, the building should not lose its structural integrity due to the pressure buildup following a major piping rupture since the rupture may be followed by fission product release. A distinction between inlet and outlet piping ruptures should be made since outlet failure would not necessarily lead to fission product release while inlet failure probably would. Thus, structural damage may be permissible for outlet failures but not for inlet failures. Meeting this requirement is made somewhat easier by lower coolant temperatures and larger volume work space at the inlet face. Existing technology is believed capable of meeting this requirement although some development aimed at simulating coolant line ruptures and attendant pressure buildup appears desirable. There are numerous difficulties in calculating this effect and the calculations made to date are believed to be extremely conservative.

The above discussion assumed that water was the coolant but in spite of the low vapor pressure of organics, the possibility of fire and/or explosion of the coolant makes the same considerations of pressure buildup applicable to organic reactors.

The second containment problem concerns the disposition of those fission products which escape from the reactor proper. The two alternatives appear to be a completely sealed building or a building provided with an exhaust air filter which removes 99% of all particulate matter. The totally sealed building is difficult because of the large pressure requirements associated with high temperature recirculating water. The exhaust filter approach requires check valve shutters for pressure release and acceptance of a moderately large escape of noble gas fission products and perhaps iodine through the filters.

Present technology is believed capable of providing either approach although the use of a sealed sphere would require significant extrapolation of demonstrated construction techniques and a sealed subterranean building would involve additional costs not immediately available to this group.

DECLASSIFIED

The central problem in specifying containment lies in determining what fraction of the total fission products escapes into the building under various circumstances. The answer will determine to a major degree the suitability of the exhaust air filtration approach. An experimental program to answer this question for the coolant failure case with no power excursion is estimated to require approximately two man years of effort.

VI. Operational Efficiency

It appears that a clear statement of the actual operational reliability requirements should be made and agreed to by G.E., the AEC, and BPA. A power producing reactor which must stay on the line continuously will differ considerably from a reactor which is allowed fairly frequent and unexpected outages. There seems to be considerable confusion on this point and careful consideration should be given to the actual requirements before the reactor concepts are narrowed to a particular design.

Complete over-ride of xenon appears possible with certain reactor types. With a D₂O cooled reactor or with organic coolant and magnesium tubes and cans, sufficient reactivity can be designed into a natural uranium lattice to provide xenon over-ride provided the specific power is not too high. The same is true of course in any enriched lattice. Using the present K reactor as an example, the following figures illustrate the magnitude of the problem:

<u>Central Tube Power</u>	<u>Total HCR Strength Required</u>	<u>Amt. of Control in Rods at Equilibrium</u>
500 kw	900 ih	450 ih
1000 kw	1500 ih	900 ih
1500 kw	2200 ih	1400 ih

The point to be remembered is that although the equilibrium xenon tends to saturate with increasing flux level, the iodine back log continues to grow. Hence, the amount of control which must be carried in control rods during equilibrium operation becomes steadily larger with increasing specific power and will eventually outrun any control system. Since this large excess in rods represents a large loss of neutrons which would otherwise be used to make plutonium, the control rods must be capable of making a useful product. Lithium rods appear feasible mechanically and from a control standpoint.

Because of the many variables, it is not possible to state whether xenon over-ride should be built into an IPR until the design is more firmly stated. Economic analysis to balance the gains against the costs would then provide the answer.

Operational charge-discharge can probably be provided if sufficient financial incentive exists. In increasing order of complexity, the various reactor types are organic, light water and heavy water. Operational charge-discharge represent probably the biggest single mechanical problem which we have considered. However, it appears that the problem can be solved if sufficient funds are available.

DECLASSIFIED

The effect of scrambling the IPR in producing a transient in BPA lines should be investigated - there seems a fair chance of scrambling all the other reactors simultaneously.

The problem of hot spot control should be studied carefully as noted in the control section. Hot spot fluctuations can cause scrams as experience at K pile points out. This is especially true if the reactor must operate close to real limits. With proper graphite coring and adequate control design, hot spots will probably not affect operational efficiency.

The problem of tube leak detection will be more important in a hot pressurized reactor than at present - especially if the coolant is organic or D₂O. In this connection it should be noted that an undermoderated lattice will gain reactivity if a tube leak develops - especially with D₂O coolant. Although this should produce no particular hazard, the magnitude of the effect should be checked.

The activity in the external piping of a recirculating system is one of the major new problems in an IPR. If serious, it will have a tremendous impact on maintenance and operational efficiency and will certainly present a design problem. Clean up of a contaminated system following a rupture could be a several day job.

VII. Coolant System

Because either a high pressure water or an organic system represents a large extension of Hanford experience, considerable development work will be necessary on the cooling system. Many of the problems now apparent in organic systems were described earlier starting on Page 10.

The materials to be used in a recirculating reactor must be checked for creep strength and corrosion resistance. Data from the H-loop indicates that the uniform corrosion rate of aluminum will be far too high to allow use of aluminum process tubes much above present H₂O coolant temperatures regardless of creep strength. It will be necessary to continue the zirconium tube fabrication program which will require an estimated 4 to 5 man years for completion. In-pile creep data on zirconium, aluminum and magnesium alloys are very desirable.

Although aluminum process tubes do not appear feasible in high temperature water, aluminum cans may be provided the exposure is limited. It should be noted that use of aluminum cans will require that all of the external piping be stainless steel to provide adequate pH control. If both tubes and cans are of zirconium, the external piping may be carbon steel. The economic choice between aluminum and zirconium must then take this point into consideration. Organic coolants will presumably require only carbon steel regardless of tube and can material.

Another possible jacket for a high temperature water systems is very thin stainless steel. This can material may be made 7 mils (or less possibly) in thickness and may prove feasible if the neutron absorption is not too bad. The actual cost in neutrons for various thickness of stainless steel should be readily available.

DECLASSIFIED

For the organic coolants aluminum-aluminum oxide alloys offer some promise for tube material. Magnesium may be possible for tube material at low pressure and is certainly very desirable from a physics standpoint. Magnesium cans appear possible although a bonding problem may arise.

Coolant system components for a recirculating water reactor are not all available without development work. Principal among these are pumps and automatic control valves of sufficient size for these conditions. Other problems which must be investigated are water purifications and cleanup, activity and decontamination problems, and water chemistry and crud formation. The residual activity in ion exchange columns after regeneration should be determined to decide whether this type of facility will permit contact maintenance. The general problem of residual activity exists for both water and organic systems. Extraction of heat from the reactor in emergencies during which the generator cannot run seems to offer no particular technical difficulty but choice of the cheapest system poses an economics problem.

A list of manpower estimates for both the organic coolant and the high temperature water case appear below:

MANPOWER ESTIMATED FOR RECIRCULATION TECHNOLOGY
ASPECTS OF THE ORGANIC COOLANT PROGRAM

Item	Probable Assigned Manpower
(1) Material purity studies, activity effects	1/2 man
(2) Corrosion, erosion studies	1
(3) Decomposition rate effects	1
(4) Clean-up evaluation, distillation, filtration	1
(5) System studies & evaluation	2
(6) Fouling effects as function of composition	1/2
(7) Physical property evaluations	1
(8) Coolant system component development & evaluation	2
(9) Hazards studies	1/2
(10) Programming ELMO and in-pile tests	1/2
(11) Test facility procurement and liaison	1
(12) Gas removal studies	1/2
	11 1/2
+ fraction of semiworks operating personnel assigned on organic test equipment	
+ Physics, Heat Transfer, Mechanical Development, Graphite and Materials aspects of program.	

Manpower estimates for Recirculation Technology Aspects
High Temperature Water Program

Materials evaluation (Al, Zr, carbon steel corrosion)	2
Studies and evaluation of rupture effects	1
Activity and decontamination studies	1

RECEIVED
JAN 10 1964

ELMO and KER scheduling and liaison	1
Water chemistry and crud formation studies	1
Purification and clean-up studies	1
Systems evaluation	1
Water plant component testing and evaluation	2
	<hr/>
	10

+ fraction of Semiworks operating personnel assigned to loops.

These assignments are assumed to hold over the entire two year development program.

VIII. Use of D₂O

In general, D₂O can be said to offer definite advantages insofar as lattice characteristics are concerned. The reactivity gain using D₂O in natural uranium lattice offers the possibility of making xenon over-ride practical. The reactivity may be traded for a substantial increase in plutonium conversion. The possibility exists that a natural uranium cluster lattice may be feasible. The wet to dry reactivity change is expected to be negative for a wide range of single rod lattices and perhaps this very desirable situation will also obtain in a cluster lattice.

In connection with this last point, a word should be said regarding a boiling reactor. Present lattice physics knowledge indicates that design of a light water boiling reactor would be very difficult. The cold, green, wet to dry reactivity change is only part of the problem of getting a stable lattice design. The reactor must be stable over a large range of temperatures and exposures which implies advance knowledge of the temperature coefficients over a wide range of exposures. Heavy water machines appear, theoretically at least, to offer much more promise for a stable boiling cycle. Because of all these uncertainties, it appears that a decision to use a boiling reactor must await physics demonstration of a workable lattice.

Aside from the advantages in lattice performance, D₂O appears to offer nothing but trouble because of its high cost. Minor leaks and spills which are of no consequence in light water reactors become crises when the coolant is worth over \$20 per pound. Although the term sounds silly, heavy water is hygroscopic and keeping H₂O out of D₂O is no small problem if very high purity must be maintained. Since the last percent or two in the purification program is very expensive, it may be possible to gain most of the advantages of heavy water at a small fraction of the cost by using mildly contaminated D₂O - H₂O mixtures.

IX. Fuel Technology

Fuel element development will require an immediate management decision. Either in-pile loops must be used and ruptures sustained in these facilities or no in-pile fuel element testing for rupture aspects will be possible until the new reactor starts up. Since theory indicates that an over-sized solid, cored, or I & E slugs

may be used in the future it is suggested that at least one large cored slug charge be irradiated in a recirculating facility. This charge should be followed by a cluster element charge of high specific power to check uranium stability in this kind of lattice. At least part of this program is already underway, although the irradiation conditions may not be completely identical with expected IPR operating conditions. Any increase in the irradiation space available for testing these over-sized fuel elements will help to minimize the fuel problems which will inevitably arise when the new reactor starts operation.

Most of the current fuel test program designed for present HAP0 piles is also applicable to some extent to IPR design. It is therefore imperative that this program proceed with all possible haste. Obviously, close liaison between fuels, heat transfer, and physics people will be very important in the work of all three groups. Among the points of interest are:

- 1) Uranium core failure - settle the question of hot vs. cold uranium for resistance to cleavage failure (ie - insulated vs. I & E slugs.).
- 2) Side failures - the tru-line feature, ribbed slugs in ribless tubes, anodized aluminum jackets and improved resistance to intergranular corrosion by some alloys (M-388).
3. Dimensional stability and warp - programs to test effects of various fabrication and heat treatment methods on in-pile stability.

Of particular concern to IPR development is the problem of reducing the consequences of slug failure. The wafer slug should be pushed as a possible way of avoiding tube blockage if single rod elements prove necessary for other reasons. The development of cluster elements should proceed concurrently since physics indicates that such an element may be practical.

The problem of providing bonding which will stand up under high temperatures should be pursued. High coolant temperatures are very desirable from a power recovery standpoint but cause difficulty with can bonds. If aluminum cans are used, the uranium-aluminum diffusion may pose a problem. Bonding problems also exist, especially on the interior surface of I & E slugs, for magnesium and zirconium jacket materials. The possibility of forming a hydride with uranium in contact with hot organic should be investigated with an eye toward slug design.

Changes in fuel elements may well cause new problems in 200 Area processing. The following are recognized at the moment:

- 1) Zr can dissolution - may be handled with HF or H₂SO₄ and would require some modification to separations plants.
- 2) Mg cans - due to H₂ evolution, explosion proofing of the dissolvers would be required.
- 3) Uranium Oxide dissolution - very little experience here and development work would be required.

- 4) Organic coolant - a solvent degreasing step might be required prior to charging the dissolvers.

PROCESS VARIABLES

INTRODUCTION

The following three cases are not presented as the probable appearance of the new reactor design. Indeed, after a two year development effort the lattice dimensions, flows and temperatures may differ considerably from these numbers. In particular, the experimental verifications of some of the present physics predictions would probably mean the employment of enriched uranium as fuel. The three cases given here assume natural uranium and only minor changes would be expected, because of the restrictions imposed by this assumption, if natural uranium were indeed to prove necessary.

Case I - Light water coolant - Metallic Uranium fuel

- 1) Lattice spacing 7.5", graphite density 1.45 (effective)
- 2) Fuel - I & E or cored natural uranium - 1.3" O.D. 1/2" I.D. - C annulus
- 3) C.R. $\approx$ 0.81
- 4) Buckling $\approx$ 90 μ b (lattice buckling)
- 5) 2700 total tubes
- 6) Coolant outlet temperature - 300°C
- 7) Coolant $\Delta T \approx$ 50°C Flow $\approx$ 154,000 gpm at 250°C
- 8) Power Recovery 25% $\approx$ 500 MW (not all exportable)
- 9) 500 MWD/T exposure (Hope for higher depending on fuel element development)
- 10) Graphite operating temperature 500°C (650°C maximum).

Comments:

Approximately this fuel geometry appears necessary if natural uranium is required. Minor variations in slug and hole size would be possible. If enrichment appears economical, a cluster lattice would probably be used with dimensions which cannot be foreseen at the moment.

The bucklings and conversion ratios for all these cases were obtained by the same calculational method. Applying this method to K-pile results in an I.C.R. of 0.83 and a buckling of 69 μ b. Reducing this number by about 2% because of the enrichment required to operate a green K-pile at power shows that K-pile and this concept are probably fairly comparable. The measured I.C.R. of 0.89 at K startup is to be compared with the 0.83 computed value and the difference is indicative of the errors inherent in straight theoretical predictions even in this straightforward geometry.

The 300°C outlet temperature represents a maximum set by zirconium creep strength. Other problems may force a reduction in this figure - for example bond stability. If aluminum tubes must be used, the 300°C will drop to below 200°C and power extraction efficiency will be very poor.

DECLASSIFIED

Case II. Heavy Water Coolant - Metallic Uranium Fuels

Most Flexible Operation

All same as Case I except:

C.R. $\approx$ 0.84

Buckling $\approx$ 125 ub

Highest Conversion Ratio

All same as Case I except:

Fuel 1.45" O.D. - 0.5" I.D.
natural uranium

C.R. $\approx$ 0.90

Buckling $\approx$ 90 ub

Comments:

With D₂O coolant sufficient flexibility becomes available to allow design anywhere between the two limiting cases above. For the first case, xenon over-ride would be possible. A metallic cluster element of natural uranium might be possible but no information is available at the moment upon which to specify a geometry. The comments on Case I apply here also.

Oxide elements do not appear practical without enrichment and the amount of enrichment will be higher than for a similar metallic element. Due to almost complete absence of experimental information, no oxide fuel case will be described.

Case III. Organic Coolant - Metallic Fuel Elements

Most Flexible Operation

Highest Conversion Ratio

1) Lattice Spacing 7.5"	7.5"
Graphite Density 1.45 (effective)	1.45 (effective)
2) Fuel-cored or I & E 1.3" O.D. 1/2" I.D.	1.47" O.D., 1/2" I.D.
3) C.R. 0.83 (Assume Mg tubes and cans)	0.90
4) Buckling 135 ub (assume Mg tubes and cans)	90 ub
5) 2700 tubes	
6) Coolant outlet T: 400°C maximum - 300°C more likely.	
7) Coolant $\Delta T \approx 100^\circ C$ Flow $\approx 154,000$ gpm Inlet Pressure ≈ 400 psi.	
8) Power recovery 25% depending on outlet and inlet temperatures possible.	
9) 500 MWD/T almost certain - probably can be considerably larger.	
10) Graphite operating temperature 500°C to 600°C depending on coolant T.	

Comments:

Use of Mg tubes and cans will provide considerable physics flexibility again in this case. The gain in reactivity can be used for xenon over-ride or can be traded for conversion ratio within the limits given above. Again minor variations in fuel geometry will be possible without enrichment.

353138712

Because the hydraulics of an organic system are not fully known, the above ΔT , flow and pressure are merely guesses. By appropriate design it may be possible to lower the pressure of the system somewhat below the 400 psi given above.

J. A. Brown

Pile Physics Unit
Pile Technology Section
ENGINEERING DEPARTMENT

JH Brown:cac

DECLASSIFIED