**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1995

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DECLASSIFIED

By Authority of PH Doc

May 1973

By JN Wells 11-21-94

Verified By Jerri Moley

11-21-94

NOT UCN

HW-29370

- 1 -

RECORD CENTER FILE

**SPECIAL RE-REVIEW
FINAL DETERMINATION
DECLASSIFICATION CONFIRMED**

BY J.P. Lerman DATE 6-9-81

BY W. Jordan DATE 7-9-81

1. V. R. Chapman - R. S. Bell
2. V. R. Cooper
3. O. F. Hill
4. W. N. Mobley - O. F. Beaulieu
5. W. J. Ozeroff
6. E. G. Pierick
7. T. Prudich - L. M. Meeker
8. A. E. Smith
9. 700 File
10. 300 File
11. Yellow Copy

September 16, 1953

This document consists of

2 pages

TO: W. N. Mobley
Superintendent - Process Sub-Section
MANUFACTURING DEPARTMENT

FROM: A. E. Smith
Leader - Z-Plant Process Technology
Technical Section
ENGINEERING DEPARTMENT

NUCLEAR SAFETY LIMITS FOR THE POWDER
RECOVERY HOOD, ROOM 234, 234-5 BUILDING

Since the operation of the Powder Recovery Hood in Room 234 or the 234-5 Building involves the handling of plutonium and its compounds, it is necessary to establish allowable plutonium concentration limits to insure the nuclear safety aspects of the operation.

In addition to the Powder Recovery Hood there are two decontamination hoods located in Room 234. Plutonium containing solutions are routinely stored in these hoods in accordance with the nuclear safety limits defined in HW-29302, Nuclear Safety - Maximum Allowable Plutonium Mass in Hoods, SWTS, 9, 10, 17, 19, Mating Room and Decontamination Hoods Room 234. Using the principles and information set forth in GEH-13844, Nuclear Safety

RECEIVED

JUL 2 1953

**300 AREA
CLASSIFIED FILES**

MASTER

DECLASSIFIED

HW-29370

- 2 -

of DP-West Operations, R. E. Schreiber to R. D. Baker, 9-9-48, and in HW-24514, Critical Mass Studies of Plutonium Solutions, F. E. Kruesi et al, 5-19-53, in the analysis of the physical arrangement of the hood, the following batch size limitations are given.

The maximum allowable mass of plutonium in the Powder Recovery Hood including the reactor vessel shall be 2000 grams of plutonium as metal, dry powder and liquid solution provided that the amount of plutonium in liquid solution shall not exceed 800 grams and further provided that the liquid solution will be analyzed before it is transferred from the reactor to RC cans whenever the mass of plutonium in the reactor could conceivably exceed 400 grams.

Approved

W. J. Ozeroff
W. J. Ozeroff - Head
Physics Unit

Sept. 18 19