**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1995

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DECLASSIFIED

HW-25285

RECORD CENTER FILE

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of per Doc

May 1973

By JH Wells - 11-19-94

Verified By JE Samsky 11-22-94

NOTUCNI

- # 1. VR Cooper
- # 2. PE Collins
- # 3. RW Benoliel
- # 4. RB Richards - JB Work
- # 5. JR Chapman - WN Mobley
- # 6. T Prudich - LM Meeker
- # 7. OF Beaulieu - SG Smolen
- # 8. FW Albaugh - FJ Leitz
- # 9. R Ward - GL Flint
- # 10. OJ Wick
- # 11. 700 File
- # 12. 300 File
- # 13. Pink Copy
- # 14. Yellow Copy

RECEIVED

August 7, 1952

JUN 20 1956

V. R. Cooper
Chief, Process
Separations Technology Unit
Engineering Department

300 AREA
CLASSIFIED FILES

This document consists of
2 pages. No. 14 of
34 copies. Series A

COPY 1 OF 1

● SERVICE OF REDUCTION BOMBS, PLUTONIUM PURIFICATION
AND FABRICATION 234-5 BUILDING

References: 1. HW-25042, Service of Reduction Bombs, Plutonium
Purification and Fabrication, 234-5 Building,
July 16, 1952.

2. Drawing No. E-2-15284, April 1, 1952.

This letter will confirm discussion of July 28 on the service life of reduction
bombs in elaboration of reference 1.

The relation between life to rupture under steady state conditions and life to
rupture under cyclic heating and loading has not been well established. A limited
amount of experimental data indicate that cyclic heating increases creep rates and,
it may be inferred, decreases life to rupture. Since no good conversion factor
exists a simplifying assumption will be used that the cumulative time at maximum
temperature and maximum stress during cyclic heating and loading is equivalent to
the same time at constant temperature and stress. This assumption is a first
approximation sufficiently accurate for a small number of cycles and relatively
short total time. The available data show that the maximum time at maximum
temperature during a single reduction is not more than ten minutes. Therefore,
the life to rupture value divided by ten minutes per reduction will be used as
the number of permissible reductions.

SPECIAL RE-REVIEW
FINAL DETERMINATION
DECLASSIFICATION CONFIRMED

BY J.P. Warrin DATE 5-19-81
BY AE Barber DATE 5-27-81

DECLASSIFIED

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DECLASSIFIED

-2-

HW-25285

The carbon steel used in the present reduction bomb, (ref. 2), has an average life to rupture of two hours at 750°C and 4400 psi. This time is equivalent to 12 reductions. For a normal reduction, in which the internal pressure does not exceed 100 psig, the maximum calculated hoop stress is 720 psi and a rupture strength of 4400 psi is therefore equivalent to a design factor of 600 per cent. For an abnormal reduction, where the pressure is 450 psig, the design factor is 135 per cent. In view of the fact that the extreme service pressure of 450 psig has been measured only on reduction of off-standard material, it is felt that the present bomb can safely be used provided each bomb is used for no more than 12 reductions and is not used for reduction of sweepings or off-standard material. It is recommended however that carbon steel be discontinued as soon as practicable in favor of higher strength, longer life material. Specifically it is recommended that reduction bombs, (ref. 2), be made of material conforming to ASTM Specification A-158, Grade TP5a. Bombs of this material will have a useful life of six hours (equivalent to 36 reductions) at a stress of 6500 psi. This stress is 200 per cent of the calculated maximum hoop stress of 3250 psi which is obtained under an internal pressure of 450 psig.

Bombs fabricated by welding of Grade TP5a steel should be preheated to 750°F, maintained above 650°F during welding, transferred without cooling to a furnace and post heated at 1600°F for 1/2 hour, then furnace cooled. Type E502-15 American Welding Society classification welding electrode should be used.

R Ward

Head, Metallurgy
Applied Research Unit
ENGINEERING DEPARTMENT

R Ward:dh

DECLASSIFIED