**West Virginia Diesel Study
CRADA MC96-034, Final Report**

M.Gautam

August 5, 1998

RECEIVED
AUG 18 1999
OSTI

U.S. Department of Energy
Federal Energy Technology Center
P.O. Box 880, 3610 Collins Ferry Road
Morgantown, WV 26507-0880

and
West Virginia University
Department of Mechanical and Aerospace Engineering
P.O. Box 6106
Morgantown, WV 26506-6106

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

FETC's Internet Address: www.fetc.doe.gov

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

**West Virginia Diesel Study
CRADA MC96-034, Final Report**

M.Gautam

August 5, 1998

U.S. Department of Energy
Federal Energy Technology Center
P.O. Box 880, 3610 Collins Ferry Road
Morgantown, WV 26507-0880

and
West Virginia University
Department of Mechanical and Aerospace Engineering
P.O. Box 6106
Morgantown, WV 26506-6106

EXECUTIVE SUMMARY

The objective of the Phase 1 (1997-1998) of the West Virginia Diesel Study, conducted at the National Center for Mining Engines and Safety, West Virginia University, was to evaluate the mass emissions rates of exhaust emissions from diesel powered equipment specified by the West Virginia Diesel Equipment Commission (Commission). The Commission laid down the tasks undertaken in the study. Data was collected on "available" technology for curtailing exhaust emissions from diesel engines earmarked for underground coal mine operations. The experimental data generated in this study is to be utilized by the WV Diesel Equipment Commission to promulgate initial rules, requirements and standards governing the operation of diesel equipment in underground coal mines. While progress on the project was reported to the Commission on a regular basis during the course of the study, the final presentation was made on February 28, 1998 at West Virginia University. This report presents the details on the test equipment, procedures, results, and conclusions and recommendations. At the risk of being more extensive than most, the Executive Summary provides the reader with quantitative information on the emissions values and subsequent emissions reductions with the prescribed exhaust aftertreatment systems.

The test engines and the respective aftertreatment systems were selected by the Commission. WVU received the equipment through the Commission. The engines and the aftertreatment devices were tested by WVU in their as-received condition. Modification of engines or exhaust aftertreatment devices were performed by the manufacturers or with their expressed consent. The testing component of the WV Diesel Study was initiated in late November 1997 after receipt of the equipment. At the onset of the investigation it became clear that diesel particulate matter was of primary concern, and for that reason this Executive Summary focuses on the findings associated with particulate matter reductions of the aftertreatment devices that were tested. Additional results are discussed in the Results and Discussion section, and the Appendices of this report. Particulate mass emission rates in g/hr and the subsequent reductions are tabulated in this section. Weighted-averages are presented for complete 8-mode tests only. The weighting factors for each of the modes may be found in Table 8.

When reporting diesel particulate matter data, it should be noted that the 30 CFR, Part 7, Subpart E considers diesel particulate matter to consist of elemental carbon, soluble organic fraction, engine wear metals, sulfates, and bound water. Therefore, the mass measurements of collected particulate matter could consist of all of these contributors. Of particular interest is the contribution of sulfates and bound water. Wall and Hoekman, (1984) reported that at 50% RH, 1.3 grams of water is present for every gram of sulfuric acid. In addition, a linear relationship between bound water and sulfuric acid was reported to exist up to 60% RH, with a rapid increase at levels above 60%. In accordance with the requirements of the 30CFR, Part 7, 40CFR, Part 86, Subpart N, and 40CFR, Part 89, WVU equilibrates the particulate matter filters at 50% RH and 70° F in an environmental chamber.

Summarized below are the test results from the four engines, namely, MWM D916-6, Lister Petter LPU-2, Isuzu C240 and Caterpillar 3306 equipped with the respective exhaust aftertreatment systems.

Summary of MWM D916-6 Results

A comparative study of high sulfur (0.37 % by mass) diesel fuel versus low sulfur (0.04 % by mass) diesel fuel was performed on a MWM D916-6. Analysts, Inc. tested samples of both fuels, and the analysis results are included in the Equipment and Procedure section of this report. Table 1 indicates that lower sulfur fuel exhibited 22 % less diesel particulate matter over the entire eight mode test cycle (weighted-average). Gaseous emissions, as expected, were basically unaffected by the fuel sulfur content.

Summary of Lister Petter LPU-2 Results

As Table 2 indicates, two different catalyzed particulate traps were tested on the Lister Petter LPU-2. Based upon the exhaust backpressure readings and particulate reductions of the first 8-mode test, it was determined that a failure had occurred in the first Rohmac/DCL particulate trap. After further inspection by DCL, WVU's findings were confirmed. Once the new particulate trap was installed, it was evident that the exhaust aftertreatment system would not be able to handle the associated high engine exhaust emissions rates. Due to backpressure limitations imposed by the engine manufacturer, only two test modes could be performed. Regeneration of the new catalyzed trap was not possible because the rate of soot deposition was much higher than the rate of combustion. In order to produce preliminary results for the Pallflex high-temperature glass-fiber paper filter, a single mode 7 test was performed. Based on WVU's recommendations, Rohmac and Lister-Petter derated the LPU-2 engine within the limits imposed by the MSHA certification requirements. Under the time constraints imposed by Phase 1 of the WV Diesel Study, further tests with the LPU-2 were not performed. However, tests have been scheduled for Phase 2 (1998-1999) of the WV Diesel Study.

Summary of Isuzu C240 Results

An Isuzu C240 was used to evaluate the emission reduction capabilities of a Rohmac/DCL exhaust aftertreatment system. The manufacturer's original system consisted of a catalyzed particulate filter in series with an oxidation catalyst. In order to explore the effects of component position within the system, the order of the oxidation catalyst and catalyzed particulate filter were reversed. In addition, the engine was operated through four modes with only an oxidation catalyst. A summary of the test results is given in Table 3. The weighted-average reduction of diesel particulate matter for the system configuration with the trap positioned upstream from the oxidation catalyst (operated over the complete eight mode cycle) was 67.7 %. Considering, however, that the testing performed for this study was the first of its kind for the Rohmac/DCL system, it should be evident that further development work could produce higher reductions in particulate matter emissions. Rohmac independently had the particulate sample filters

analyzed for sulfate content and verbally disclosed, to WVU, that sulfates contributed approximately 50% of the total measured particulate mass.

Summary of Caterpillar 3306 Results

Two aftertreatment devices were tested on a Caterpillar 3306. A Dry Systems Technology dry scrubber system (DST) and a Clean Air Systems catalyzed particulate trap were evaluated for their exhaust emissions reduction abilities. The results for the tests are presented in Tables 4a, 4b, and 4c.

Goodman Equipment Corporation, through the Commission, supplied WVU with a Caterpillar 3306 that was retrofitted with a DST system. During the initial eight-mode test, a coolant leak was detected in the heat exchanger of the DST system. Results of this test are presented in Table 4a as DST I. Prior to the second test, which consisted of only four modes (see DST II in 4a), Goodman representative performed subsequent repairs and inspections. During this second series of tests, WVU noticed that the level of collected particulate matter for the first two modes was significantly higher than expected. Expectations were based on engineering judgement and experience. Hence, the Caterpillar 3306-DST was operated through only two additional modes, Modes 5 and 7. Goodman Equipment Corporation was contacted through the Commission and informed of a possible persisting problem with the equipment. After an engine checkup by a local Caterpillar maintenance technician and various Goodman-required system inspections and clean-up procedures, the Caterpillar 3306 with the DST system was tested for a third time. The results of this complete 8-mode test are presented in Table 4b (DST III). Once again, the reductions from this system were rather low under high speed/high load (Mode 1, in particular) conditions. PM reductions at Modes 2 - 8 were greater than 91%. Modes 3, 4, 7 and 8 show reductions in excess of 95%.

Clean Air Systems provided WVU with a catalyzed particulate filter that had been designed for the Caterpillar 3306. The results of the tests are given in Table 4c. It should be noted that, although the overall weighted-average particulate reduction of the system was 72 %, this test was the first of its kind for this particular system model. In addition, the particulate sample filters were not analyzed, but, based on previous experience, WVU would expect test results to indicate that a considerable amount of sulfates were contained on the filters. Moreover, as with the Rohmac/DCL system, further development could minimize sulfate production and, hence, improve overall particulate reduction efficiency.

Recommendations

It was apparent that the manufacturers of the catalyzed trap systems, employed in this study, had not carried out any development work on these systems. Hence, there is room for considerable amount of improvement in catalyst formulation, trap selection and sizing and in the optimization of the complete packages. Prior to this study, engine manufacturers never had to comply with any real emissions requirements and this study has highlighted a critical area that needs to be addressed. Derating the LPU-2 engine is a

small example of what manufacturers may have to start doing. Selecting low-emission engines could be a first step move in the right direction. Surface temperature requirements limit the potential avenues for trap regeneration. Relaxation of the 300°F requirement would help in the implementation of regeneration techniques other than noble metal-rich catalyst formulations that lead to high sulfate formation at elevated temperatures. It is recommended that in-use (in-mine) diesel equipment be instrumented to collect data not only exhaust temperatures but also on speed (engine and vehicle), load, and the overall duty cycle. This will assist in optimizing the design of aftertreatment devices for underground mining applications.

	High (0.37 %) Sulfur	Low (0.04%) Sulfur	Particulate Reduction for Low Sulfur Fuel
Mode 1	32.33	23.77	26.46
Mode 2	25.39	20.5	19.26
Mode 3	21.11	18.65	11.66
Mode 4	14.09	10.83	23.14
Mode 5	29.70	23.03	22.48
Mode 6	21.87	16.73	23.51
Mode 7	17.12	14.46	15.51
Mode 8	5.09	2.18	57.18
Weighted-Averages			
Eff. Total	20.87	16.27	22.02

Table 1. Overall DPM Reductions for the MWM D916-6

	Bare (g/hr)	Initial Trap (g/hr)	Trap Reduct- ion %	Catalyst Only (g/hr)	Trap Reduct- ion %	New Trap, Catalyst and Paper (g/hr)	Trap Reduct- ion %	New Trap and Catalyst (g/hr)	Trap Reduction %
Mode 1	104.07	36.77	64.70	63.60	38.90				
Mode 2	3.79	3.22	15.00						
Mode 3	3.21	2.35	26.80						
Mode 4	4.10	0.90	78.00						
Mode 5	109.10	36.33	66.70	55.25	49.40				
Mode 6	5.84	1.66	71.60					1.08	81.50
Mode 7	2.88	0.37	87.20	1.69	41.30	0.13	95.50	0.65	77.40
Mode 8	0.15	0.07	53.30						
Weighted-Averages:									
Eff. Total	28.87	10.28	64.4						

Table 2. Overall DPM Reductions for the Lister Petter LPU-2

	Bare (g/hr)	Trap + Cat. (g/hr)	Trap + Cat. Reduction %	Cat. + Trap (Reverse Order) (g/hr)	Cat. + Trap (Reverse Order) Reduction %	Catalyst Only (g/hr)	Catalyst Only Reduction %
Mode 1	11.41	9.58	16.0	6.83	40.1	19.65	-72.2
Mode 2	10.27	3.86	62.4				
Mode 3	10.27	1.83	82.2	0.77	92.5	5.92	42.3
Mode 4	11.56	0.09	99.2				
Mode 5	34.73	9.58	72.4	7.12	79.4	55.12	-58.7
Mode 6	3.83	0.14	96.3				
Mode 7	3.24	0.08	97.5	0.04	98.7	1.78	45.0
Mode 8	0.24	0.03	87.5				
Weighted-Averages							
Eff. Total	10.16	3.28	67.7				

Table 3. Overall DPM Reductions for the Isuzu C240

	Bare (g/hr)	DST I (g/hr)	DST I Reduction %	DST II (g/hr)	DST II Reduction %
Mode 1	35.45	87.08	-145.6	31.10	12.3
Mode 2	55.1	57.05	-3.5	12.55	77.2
Mode 3	71.51	25.64	64.1		
Mode 4	85.87	4.11	95.2		
Mode 5	90.66	5.69	93.7	3.02	96.7
Mode 6	17.12	4.59	73.2		
Mode 7	20.71	2.26	89.1	0.97	95.3
Mode 8	3.27	0.23	93.0		
Weighted-Averages					
Eff. Total	46.23	27.16	41.2		

Table 4a. Overall DPM Reductions for the Caterpillar 3306 (DST I and DST II)

	Bare (After Engine/DST Inspection & Repair (g/hr)	DST III (After Inspection & Repair) (g/hr)	DST III (After Inspection & Repair) Reduction %
Mode 1	33.38	30.68	8.1
Mode 2	47.64	5.88	87.7
Mode 3	60.29	3.03	95.0
Mode 4	68.22	1.41	97.9
Mode 5	39.38	3.06	92.2
Mode 6	15.05	1.38	90.8
Mode 7	24.26	0.56	97.7
Mode 8	1.93	0.06	96.9
Weighted-Averages			
Eff. Total	6.589	6.59	81.8

Table 4b. Overall DPM Reductions for the Caterpillar 3306 (DST III)

	Bare (g/hr)	Clean Air Cat- Trap (g/hr)	Clean Air Cat- Trap Reduction %
Mode 1	35.45	17.42	50.9
Mode 2	55.1	23.32	57.7
Mode 3	71.51	19.35	72.9
Mode 4	85.87	0.99	98.8
Mode 5	90.66	22.5	75.2
Mode 6	17.12	13.48	21.3
Mode 7	20.71	0.89	95.7
Mode 8	3.27	0.57	82.6
Weighted-Averages			
Eff. Total	46.23	12.88	72.1

Table 4c. Overall DPM Reductions for the Caterpillar 3306 (Clean Air System)

TABLE OF CONTENTS

EXECUTIVE SUMMARY	II
TABLE OF CONTENTS	IX
LIST OF FIGURES	X
LIST OF TABLES	XI
1.0 OBJECTIVES	1
2.0 INTRODUCTION.....	2
3.0 EQUIPMENT AND PROCEDURES.....	7
 <u>3.1 TEST ENGINES AND EXHAUST</u>	
<u>AFTERTREATMENT DEVICES</u>	7
3.1.1 MWM D916-6	7
3.1.2 Lister Petter LPU-2	7
3.1.3 Isuzu C24	7
3.1.4 Caterpillar 3306-6	7
 <u>3.2 ENGINE INSTRUMENTATION</u>	8
3.2.1 MWM D916-6	9
3.2.2 Lister Petter LPU-2	9
3.2.3 Isuzu C240	9
3.2.4 Caterpillar 3306	9
 <u>3.3 OPERATING CONDITIONS</u>	12
<u>3.4 DYNAMOMETERS</u>	13
3.4.1 Water-Brake Dynamometers	13
3.4.2 Eddy-Current Dynamometers	13
3.4.3 Electric Dynamometers	13
 <u>3.5 DYNAMOMETERS USED FOR</u>	
<u>THE WV DIESEL STUDY</u>	14
3.5.1 Go-Power D-100	14
3.5.2 Mustang Dynamometers EC300	14
3.5.3 Mustang Dynamometers K400	14
 <u>3.6 DYNAMOMETER CONTROLS</u>	15
3.6.1 Water-Brake Controls	15
3.6.2 Eddy-Current Controls	15
 <u>3.7 TEST FUELS</u>	16
 <u>3.8 WVU ENGINE RESEARCH CENTER</u>	16
3.8.1 Full-Flow Exhaust Dilution Tunnel	16
3.8.2 Critical Flow Venturi	20
3.8.3 Secondary Dilution Tunnel	

3.8.4	and Particulate Sampling System	21
3.8.4	Gaseous Emission Sampling System	22
3.8.5	Exhaust Gas Analyzers	22
	3.8.5.1..HC Analyzer	22
	3.8.5.2 CO/CO ₂ Analyzers	23
	3.8.5.3 NO _x Analyzer	23
3.8.6	Bag Sampling	23
3.8.7	Instrumentation Control and Data Acquisition	24
3.8.8	Fuel and Air Flow Metering	24
4.0 QUALITY CONTROL/QUALITY ASSURANCE PLAN.....		26
5.0 QUALITY CONTROL /QUALITY ASSURANCE PROCEDURES.....		28
5.1	Emissions Testing	28
5.2	Sampling Lines and Probes	28
5.3	Pumps and Blowers	29
5.4	Exhaust Transfer Tube	29
5.5	Exhaust Analyzer Calibration and Calibration Gases	29
5.6	Additional Calibration and Maintenance Procedures	29
5.6.1	HC Analyzer	30
5.6.2	CO/CO ₂ Analyzers	30
5.6.3	NO _x Analyzer	30
5.7	Bag Sampling	31
5.8	Particulate Sampling	31
5.9	Tunnel Injections	31
5.9.1	Propane Injection	32
5.10	Data Analysis and Reporting	32
5.11	Experimental Uncertainty	33
6.0 RESULTS AND DISCUSSION		35
6.1	MWM D916-6 Results	35
6.2	Lister Petter LPU-2 Results	35
6.3	Isuzu C240 Results	38
6.4	Caterpillar 3306 Results	38
7.0 RECOMMENDATIONS.....		41
LITERATURE CITED		107

APPENDICES

Appendix A

Figure A.1-1	MWM D916-6 on an Eddy Current Dynamometer Test Bed	A-1
Figure A.2-1	LPU-2 Engine with Rohmac/DCL Control System (Side View)	A-2
Figure A.1-2	LPU-2 Engine with Rohmac/DCL Control System (End View)	A-3
Figure A.2-3	Lister Petter LPU-2 Engine with Rohmac/DCL DPM Control System on a Water Brake Dynamometer Test Bed	A-4
Figure A.2-4	Downstream Face of the Rohmac/DCL Catalyst Prior to Regeneration	A-5
Figure A.2-5	Upstream Face of the Rohmac/DCL Trap Prior to Regeneration	A-6
Figure A.2-6	Downstream Face of the Rohmac/DCL Trap Prior to Regeneration	A-7
Figure A.2-7	Rohmac/DCL Trap-Catalyst Assembly for the LPU-2 System Prior to Regeneration	A-8
Figure A.2-8	Rohmac/DCL Trap-Catalyst Assembly for the LPU-2 System following Regeneration	A-9
Figure A.3-1	Isuzu C240 with Rohmac/DCL Catalyst-Trap System (Reverse Order Configuration)	A-10
Figure A.4-1	Caterpillar 3306 with DST on an Eddy Current Dynamometer Test Bed	A-11
Figure A.4-2	End View of the DST Heat Exchanger	A-12
Figure A.4-3	Manifold Section of the DST Heat Exchanger with Coolant Leak	A-13
Figure A.4-4	Manifold Section of the DST Heat Exchanger During the Repair Process	A-14
Figure A.4-5	Internal End View of the DST Filter Canister	A-15
Figure A.4-6	DST Heat Exchanger During the Repair Process	A-16
Figure A.4-7	Manifold-Body Gasket From the DST Heat Exchanger	A-17
Figure A.4-8	Caterpillar 3306 with Clean Air Systems Trap (End View)	A-18

Figure A.4-9	Caterpillar 3306 with Clean Air Systems Trap (Side View)	A-19
Figure A.4-10	Insulated Clean Air Systems Catalyzed Trap	A-20

Appendix B – Tabulated Emissions Data Presented in g/hr

MWM Emissions Data for High and Low Sulfur Fuels	B-1
LPU-2 Emissions Data for Failed Rohmac/DCL Trap	B-2
LPU-2 Emissions Data for Rohmac/DCL Systems and Pallflex Paper Filter	B-3
Emissions Data for Isuzu C240 with Rohmac/DCL Trap and Catalyst	B-4
Emissions Data for Isuzu C240 with Rohmac/DCL Catalyst and Trap and Catalyst Only	B-5
Emissions Data for Caterpillar 3306 with DST I	B-6
Emissions Data for Caterpillar 3306 with DST I without catalyst and DST II	B-7
Emissions Data for Caterpillar 3306 with DST III	B-8
Emissions Data for Caterpillar 3306 with Clean Air System	B-9

Appendix C – Tabulated Emissions Data Presented in g/bhp-hr

MWM Emissions Data for High and Low Sulfur Fuels	C-1
LPU-2 Emissions Data for Failed Rohmac/DCL Trap	C-2
LPU-2 Emissions Data for Rohmac/DCL Systems and Pallflex Paper Filter	C-3
Emissions Data for Isuzu C240 with Rohmac/DCL Trap and Catalyst	C-4
Emissions Data for Isuzu C240 with Rohmac/DCL Catalyst and Trap and Catalyst Only	C-5
Emissions Data for Caterpillar 3306 with DST I	C-6
Emissions Data for Caterpillar 3306 with DST I without catalyst and DST II	C-7
Emissions Data for Caterpillar 3306 with DST III	C-8
Emissions Data for Caterpillar 3306 with Clean Air System	C-9

Appendix D – Emissions Data From LPU-2 Regeneration Cycles

Figure D.1-1	HC Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.1-2	CO Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.1-3	CO ₂ Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.1-4	NO _x Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.1-5	Exhaust Manifold Backpressure Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.1-6	Exhaust Gas Temperature Trace for First Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-1	HC Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-2	CO Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-3	CO ₂ Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-4	NO _x Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-5	Exhaust Manifold Backpressure Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.2-6	Exhaust Gas Temperature Trace for Second Regenerative Cycle on Lister-Petter with Failed Rohmac/DCL System
Figure D.3-1	HC Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System
Figure D.3-2	CO Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System
Figure D.3-3	CO ₂ Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System
Figure D.3-4	NO _x Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System
Figure D.3-5	Exhaust Manifold Backpressure Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System
Figure D.3-6	Exhaust Gas Temperature Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System

Appendix E- Additional Documentation

LIST OF FIGURES

Figure 1.	Schematic of WVU engine research center	19
-----------	---	----

DATA FIGURES FOR MWM D916-6

Figure 2.	Comparison of Particulate Mass Emission Rates Using Low Sulfur and High Sulfur Diesel No. 2 Fuel	42
Figure 3.	Comparison of Hydrocarbon Mass Emission Rates Using Low Sulfur and High Sulfur Diesel No. 2 Fuel	43
Figure 4.	Comparison of Carbon Monoxide Mass Emission Rates Using Low Sulfur and High Sulfur Diesel No. 2 Fuel	44
Figure 5.	Comparison of Carbon Dioxide Mass Emission Rates Using Low Sulfur and High Sulfur Diesel No. 2 Fuel	45
Figure 6.	Comparison of Nitrogen Oxides Mass Emission Rates Using Low Sulfur and High Sulfur Diesel No. 2 Fuel	46

DATA FIGURES FOR LPU-2

Figure 7.	Comparison of Particulate Mass Emission Rates for Mode 7	47
Figure 8.	Comparison of Particulate Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	48
Figure 9.	Comparison of Particulate Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	49
Figure 10.	Comparison of Particulate Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	50
Figure 11.	Comparison of Particulate Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	51
Figure 12.	Comparison of Hydrocarbon Mass Emission Rates for Mode 7	52
Figure 13.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	53
Figure 14.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	54
Figure 15.	Comparison of Carbon Monoxide Mass Emission Rates for Mode 7	55

Figure 16.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	56
Figure 17.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	57
Figure 18.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	58
Figure 19.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	59
Figure 20.	Comparison of Nitrogen Oxides Mass Emission Rates for Mode 7	60
Figure 21.	Comparison of Nitrogen Oxides Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	61
Figure 22.	Comparison of Nitrogen Oxides Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	62
Figure 23.	Comparison of Nitrogen Oxides Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	63

DATA FIGURES FOR ISUZU C240

Figure 24.	Comparison of Particulate Mass Emission Rates from Bare Engine, Rohmac/DCL System Equipped Engine, and Rohmac/DCL (Reverse Order) Equipped Engine	64
Figure 25.	Comparison of Particulate Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	65
Figure 26.	Comparison of Particulate Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	66
Figure 27.	Comparison of Particulate Mass Emission Rates from Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine	67
Figure 28.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine, Rohmac/DCL System Equipped Engine, and Rohmac/DCL (Reverse Order) Equipped Engine	68
Figure 29.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	69

Figure 30.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	70
Figure 31.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and Rohmac/DCL (Reverse Order) Equipped Engine	71
Figure 32.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, Rohmac/DCL System Equipped Engine, and Rohmac/DCL (Reverse Order) Equipped Engine	72
Figure 33.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	73
Figure 34.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	74
Figure 35.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and Rohmac/DCL (Reverse Order) Equipped Engine	75
Figure 36.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine, Rohmac/DCL System Equipped Engine, and Rohmac/DCL (Reverse Order) Equipped Engine	76
Figure 37.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	77
Figure 38.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	78
Figure 39.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine and Rohmac/DCL (Reverse Order) Equipped Engine	79
Figure 40.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine, Rohmac/DCL System Equipped Engine, and Rohmac/DCL (Reverse Order) Equipped Engine	80
Figure 41.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine and DCL Catalyst Equipped Engine	81
Figure 42.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine and Rohmac/DCL System Equipped Engine	82

Figure 43.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine and Rohmac/DCL (Reverse Order) Equipped Engine	83
------------	--	----

DATA FIGURES FOR CATERPILLAR 3306

Figure 44.	Comparison of Particulate Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	84
Figure 45.	Comparison of Particulate Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	85
Figure 46.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	86
Figure 47.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	87
Figure 48.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	88
Figure 49.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	89
Figure 50.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	90
Figure 51.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	91
Figure 52.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	92
Figure 53.	Comparison of Particulate Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	93
Figure 54.	Comparison of Particulate Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	94
Figure 55.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	95

Figure 56.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	96
Figure 57.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	97
Figure 58.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	98
Figure 59.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	99
Figure 60.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	100
Figure 61.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine, DST System(s) and Clean Air Systems Catalyzed Trap	101
Figure 62.	Comparison of Particulate Mass Emission Rates from Bare Engine and DST III System	102
Figure 63.	Comparison of Hydrocarbon Mass Emission Rates from Bare Engine and DST III System	103
Figure 64.	Comparison of Carbon Monoxide Mass Emission Rates from Bare Engine and DST III System	104
Figure 65.	Comparison of Carbon Dioxide Mass Emission Rates from Bare Engine and DST III System	105
Figure 66.	Comparison of Oxides of Nitrogen Mass Emission Rates from Bare Engine and DST III System	106

LIST OF TABLES

Table 1	Overall DPM Reductions for the MWM D916-6	vi
Table 2	Overall DPM Reductions for the Lister Petter LPU-2	vi
Table 3	Overall DPM Reductions for the Isuzu C240	vii
Table 4a	Overall DPM Reductions for the Caterpillar 3306 (DST I and DST II)	vii
Table 5	Test Engine Specifications	8
Table 6	Test Engines and Associated Exhaust Aftertreatment Devices	9
Table 7a	Observed Exhaust Temperatures and Backpressures (Mode 1-4)	10
Table 7b	Observed Exhaust Temperatures and Backpressures (Mode 5-8)	10
Table 8	The 8-Mode Test Cycle	122
Table 9a	Fuel Analysis Results for High Sulfur Fuel	19
Table 9B	Fuel Analysis Results for LOW Sulfur Fuel	20
Table 10	Observed Exhaust Temperatures After the DST Flame Arrestor	41

1.0 OBJECTIVES

The global objective of the recently completed Phase 1 of the West Virginia Diesel Study, at West Virginia University, was to evaluate mass emission rates of exhaust emissions from diesel powered equipment specified by the West Virginia Diesel Equipment Commission. The experimental data generated in this study has been utilized by the WV Diesel Equipment Commission to promulgate initial rules, requirements and standards governing the operation of diesel equipment in underground coal mines.

A more recent study, funded by the State of West Virginia and coordinated by the WV Diesel Commission, is currently in its second phase. The objective of this study is to collect data on 'available' technology for curtailing exhaust emissions from diesel engines earmarked for underground coalmine operations. The test matrix was decided upon by the WV Diesel Commission. The set of tasks accomplished by the study follows:

1. MWM D916-6 engine using high sulfur diesel fuel (0.36% S)
2. MWM D916-6 engine using low sulfur diesel fuel (0.05% S)
3. Caterpillar 3306 engine (*baseline*).
4. Caterpillar 3306 engine with catalyzed trap.
5. Caterpillar 3306 engine with a dry scrubber system.
6. Caterpillar 3306 engine with dry scrubber system - retest with the repaired heat exchanger.
7. Isuzu C240 engine with a catalyzed trap followed by a catalytic converter.
8. Isuzu C240 engine with a catalytic converter.
9. Isuzu C240 engine with a catalytic converter followed by a catalyzed trap.
10. Development of a measurement system (dynamometer test bed) for LPU-2 engine.
11. Lister-Petter LPU-2 engine (*baseline*).
12. Lister-Petter LPU-2 engine with a catalyzed trap with a catalytic converter - trap failed.
13. Lister-Petter LPU-2 engine with a catalyzed trap with a catalytic converter - retested with new trap.
14. Lister-Petter LPU-2 engine with a catalytic converter.
15. Preliminary development and testing of high temperature trap for use with catalytic converter/trap combination and for other engines.
16. Microwave Enhanced Trap Oxidizer System (METOS).
17. Exhaust gas recirculation (for NO_x reduction).
18. Arrange meeting/discussions with USDOE-FETC and WV diesel commission on Fischer-Tropsch diesel for underground mining applications.
19. Development of a portable mini-dilution tunnel system for in-field measurement of diesel particulate matter from mining engines.

NOTE: Tasks 15, 16, and 17 were assigned a low priority by the commission for the 1997-98 year. Research on these tasks will continue into the 1998-99 year.

2.0 INTRODUCTION

In considering the utilization of diesel equipment in underground mining, one often thinks of only face haulage operators. However, diesel equipment plays an equally important role in other vital functions, such as material haulage, personnel transportation and support operations. Other underground coal mine equipment that may be powered by diesel engines are shuttle cars, compressors, hydraulic pumps, generators, scoops and roof bolters. Currently, nearly 2900 diesel units are operating in the U.S. underground coalmines. This number may possibly increase to 4,000 by the turn of the century. Some of the versatility, maneuverability, and mobility of diesel power equipment make it an efficient alternative to electric powered equipment. The electrically powered equipment in underground coalmines suffer from a lack of mobility because of the restraining power cables, the "umbilical cords" attached to them. Moreover, electrically-powered equipment has many associated safety hazards.

Also, it is well established that the utilization of permissible diesel equipment poses less potential for dust or methane ignitions than does the use of electrically powered trailing cable machines (Gambill, 1978). Use of diesel equipment eliminates shock, burn or electrocution hazards commonly associated with electric trailing cables and open trolley wires. Electrical shock is one of the leading causes of injury and death in U.S. coalmines (Shanks and Weittenhiller, 1988). Currently utilized trolley wire systems consistently expose miners to a bare 300-volt DC conductor. Similarly, batteries and battery overcharging have also exposed the miners to several hazards. In addition, electric sparks are significant sources of ignition in coalmine fires (Shanks and Weittenhiller, 1988). Another important safety issue deals with the large number of back injuries that can be attributed to lifting of power cables by the miners. An additional advantage of diesel powered equipment is the potential for safe and rapid evacuation of personnel if there is a power failure. Considering higher productivity which can be obtained by using diesel equipment, on a per-ton basis, there is less human exposure to the known health and safety hazards associated with underground coal mining. As the amount of exposure necessary to mine a given quantity of coal is reduced, subsequent frequency of accidents will also diminish. Thus, the use of diesel powered equipment, with appropriate exhaust emissions controls, in mining operations may improve the overall safety.

The exhaust from diesel engines operated in the closed confines of underground mines has been a subject of concern, because of its relationship with health problems. Mine Safety and Health Administration (MSHA) has recently proposed a rule that would establish new health standards for underground coalmines that use diesel engine powered equipment. MSHA's proposal requires installation of high-efficiency filters on diesel-powered inby equipment. Within 30 months, heavy-duty outby equipment will also have to be equipped with such high-efficiency filters. Whole diesel exhaust is considered to be a probable human carcinogen (IARC, 1988) and NIOSH (1988) considers it as a potential occupational carcinogen. Cohen and Higgins (1995) suggested a small to moderate excess relative risk of lung cancer in workers who were exposed to emissions from older, uncontrolled diesel engines. This finding is particularly relevant to the mining

applications because the majority of engines used are of older design and uncontrolled, similar to those discussed by Cohen and Higgins (1995). It is understood that, to-date, no epidemiological study has presented quantitative evidence of the past exposures of the study subjects and, hence, the use of this data to estimate the magnitude of cancer risk is limited. Heavy-duty diesel vehicle exhaust particulate is of concern because long term exposure to particulate matter has been associated with excess lung cancer rates in laboratory animals [Mauderly *et al.*, 1986; Iwal *et al.*, 1986; McClellan, 1986]. Several other toxicological and epidemiological studies have also investigated the relationship between diesel emissions and the development of cancer and other diseases (HEI, 1998; California EPA, 1998; U.S. EPA, 1998). These studies have shown that long-term exposures to very high concentrations of diesel emissions produce lung tumors in rats and that soot (carbonaceous core PM), not the adsorbed chemicals, is the likely cause of tumors in this species. The intent of this discussion is not to debate the relevance of the current rat model for risk assessments. Rather, to show that these recent findings confirm WVU's earlier findings (Wallace *et al.*, 1986, 1990) that diesel soot particles can express *in vitro* genotoxic activity without extraction, as simple dispersions in surrogate pulmonary surfactant.

Abdul-Khalek *et al.* (1998), Bagley *et al.* (1996) and several supporting references suggest that advanced diesel engines yield a high number count of ultrafine particles and that these particles may pose a significant human health risk. A recent joint European study (VERT Report, 1997) evaluated the exhaust emissions from diesel engines employed in the large tunnel construction projects in Austria, Germany and Switzerland. The exclusive motivation was to minimize the effect of nanometer particles on occupational health. The study evaluated several particulate trap systems, catalytic converters, and fuel types with the objective of reducing emissions of nanometer particles. The report indicates that only particulate traps can curtail the total solid particulate count, in the fine particulate range below 50 nm, by more than two orders of magnitude. The VERT study did not address the regeneration of traps and neither did it assess the genotoxic potential of the diesel PM emitted from engines equipped with the after-treatment devices.

Diesel engines, in general, emit solid particulates in the range of 0.1 μm (100 nm) at concentrations above 1×10^7 particles/cm³. While Cohen and Higgins (1995) focussed on older engines, other reports indicate that fine diesel soot below one micron in size is produced in high number counts by modern engines running low sulfur fuel, high pressure injection and late injection timing (strategies designed to reduce the regulated emission inventory). It should be noted that most of the engines studied were turbocharged. Details of those studies have been given in a paper by Pataky *et al.* [1994] and a Health Effects Institute report [Bagley *et al.*, 1996]. Associations between suspended particulate matter and lung function parameters, respiratory symptoms, and mortality have been reported by Monn *et al.* [1995], Braun *et al.* [1992], Pope and Dockery [1992] and Dockery *et al.* [1993]. The respiratory health effects have been found to be associated with particulate matter with diameters less than 10 μm . These particles constitute the respirable range, that is, particles that penetrate the alveolated regions of the lung. In addition to the particle size, the number of inhaled particles could

be of great relevance. A change of the median particle diameter from 1 μm to 0.1 μm increases the number of particles by more than a factor of a thousand for a constant total particulate mass [Monn *et al.*, 1995]. This causes problems in the macrophage clearing mechanism. Kreyling [1994] has suggested that macrophage clearing is more efficient for a smaller number of larger particles than for a very high number of fine particles. Recent studies [Donaldson, 1994] have suggested that the very smallest particles, smaller than 0.1 μm in diameter, are toxic by virtue of their size and cause stress of lung cell lining, leading to irritation and inflammation in some areas. Size related toxicity rather than chemical composition alone, may be of greater concern because chemical composition has been shown to be highly variable [Koa and Friedlander, 1995]. Diesel particulate impact on human health has been highlighted in recent reports [HEI, 1995; NESCAUM, 1997].

The brief discussion on the effect of diesel PM (mass, number count and size distribution) on occupational health highlights the urgent need to explore viable methods for cleaning up the diesel engines. Using a four pronged approach, namely, fuels, aftertreatment and cleaner engines, and combinations there of, an effective emission reduction strategy can be developed.

Oxidation catalytic converters are being deployed nowadays in diesel engines. Catalytic converters are known to reduce the soluble organic fraction by 20% to 45%. However, the undesirable aspect of the catalytic converters is the promotion of reactions that lead to sulfate formation at temperatures above 350°C. In addition, the VERT report (1997) indicates that catalytic converters may have an effect of converting up to 40% of the NO to NO₂ and increase the NO_x toxicity. The VERT report (1997) suggested that the negative effects of catalytic converters outweigh the potential advantages. Catalyzed traps on the other hand can drastically reduce the PM emissions. However, the need to achieve on-line regeneration and the subsequent use of precious metals to assist in this regeneration, results in excessively high mass emissions rates of sulfates.

The concern about DPM has resulted in the development and application of a number of new on-board control systems that limit the quantities of PM produced by the engine, collect the DPM or convert it to a potentially less harmful form. Both ceramic and paper filters have been designed for use in underground mines, with limitations inherent in each. Paper filters must be replaced often, which has a significant impact on its acceptability. Two entirely different temperature-related problems occur with ceramic filters. One is the result of the regulated limits on equipment surface temperatures that exist for U.S. underground coal mines. The other problem arises as PM builds up in a ceramic filter in the diesel's exhaust system. The engine back pressure increases to such a high level the level that the PM must be removed (a process called regeneration) or else the engine may be damaged. Combusting these particles to less harmful gases during normal operations (on-board regeneration) is essential if the filter's use is to be continued for more than a few shifts without a special regeneration process. Catalyzed traps have also been employed to not only trap the soot but also achieve regeneration at lower exhaust temperatures under normal engine operating conditions. An important concern

with each of the new control systems or devices is whether the potential health hazard is reduced or whether more harmful contaminants are produced.

Diesel control technology in underground coal mines is clearly a more difficult task than in metal mines due to the need for maintaining permissible conditions, such as, maintaining the outside surface temperature below 300°F, which is mandated by safety regulations. Thus the primary control technology in metal mines, ceramic filters, may not be as readily applicable in coal mines. Pleated-media filters are being scrutinized very closely as a possible PM control technology for coal mine face applications.

The use of a paper like pleated media filter has some problems that need to be resolved before these filters can be accepted in mines. The exhaust temperature for these systems must be controlled to prevent the filter media from igniting. This has been accomplished by using a wet scrubber system. These wet scrubbers require significant maintenance, a foolproof system to insure proper water level, and a considerable space within the equipment. Wet scrubbers have been known to run out of water during operation. In the past the wet scrubbers have added excess moisture to the exhaust, while lowering its temperature. In addition, wet exhaust can lead to unexpected and/or premature failure of the pleated paper filters.

A dry exhaust system that cools the exhaust to an acceptable level for the pleated-media would seem to resolve several of the shortcomings of the wet scrubber systems. WVU has investigated two designs of the dry scrubber systems for two different engines. The first system, the DST Management System for an MWM-D916-6 engine, was studied under a grant from the Generic Technology Center for Respirable Dust (U.S. Bureau of Mines). The test plan was drawn up in consultation with the industry, miners and MSHA. Both transient and steady state testing with a high sulfur diesel no. 2 (0.37% S - the specified fuel at the time of the study) yielded PM emission reductions in excess of 95%. The management system is an emissions control system that may/may not utilize an oxidation catalyst. It employs dry cooling of the exhaust gases and a disposable paper filter to reduce both gaseous and particulate emissions. Another dry scrubber system designed for the Caterpillar 3306 was evaluated under the current WV Diesel Study.

A preliminary investigation of a novel high-temperature filter media was undertaken at WVU. A PM trap, using the high temperature filter, was designed, fabricated and tested on the LPU-2 engine. The filter can withstand temperatures as high as 2400°F. This is well beyond the required regeneration temperature in the trap. This preliminary design trap was located downstream of a catalyzed trap, on a LPU-2 engine, and a test on Mode 7 resulted in 96% reduction in mass emission rates of PM. The proposed high temperature trap merits further investigation.

Diesel fuel specification is also of relevance in the development of methodologies for particulate matter control. Diesel no. 2, that meets the requirements of 30CFR, Part 7, does have a lower sulfur content compared to the fuel from a few years ago, but it is still not low enough to prevent the high rates of sulfate emissions. If the fuel sulfur content

could be lowered to a few ppm, the aromatic content of the fuel be reduced and the cetane number increased well beyond 50, then the catalyzed traps or combinations of catalytic converters and traps could readily yield extremely high PM reductions. These reductions would be realized even during high speed/high load conditions and also during regeneration modes that may or may not need an external energy source.

Fischer-Tropsch (F-T) diesel fuel is one of the two types of fuels that were discussed during this study. F-T liquid fuels produced from synthesis gas (a mixture of carbon monoxide and hydrogen) are straight chain aliphatic hydrocarbons containing virtually no aromatic compounds or sulfur species. F-T diesels are currently being processed from methane (coal bed methane could be a potential source) and/or coal. The cetane number could be higher than 70, thus making it an excellent compression ignition fuel. F-T liquid fuels offer such significantly different chemistry that, when compared to typical petroleum based diesel fuels, a new PM versus NO_x variable emerges. F-T diesel, with virtually zero sulfur content, would be an excellent candidate for engines equipped with exhaust treatment devices, such as catalyzed traps. Regeneration of the traps to temperatures beyond 350°C would not lead to high sulfate emission levels and by the virtue of the low aromatic content and the high cetane number, NO_x emissions could be simultaneously reduced. It is understood that NO_x remains the hardest of all regulated emissions to alter by fuel reformulation. Shell Oil operates a gas-based middle distillate synthesis plant that supplies F-T liquid fuel as a blending stock to California. The California Air Resources Board (CARB) has mandated a maximum fuel aromatics content of 10% (poly-aromatics $<1.4\%$) and a minimum cetane number of 48. Blends of diesel no. 2 and F-T diesel (synthesized from natural gas) meet the tough emissions standards imposed by CARB.

Dr. Gautam had arranged a meeting between the Federal Energy Technology Center (FETC) and the Commission to explore the possibility of using the Fischer-Tropsch diesel fuel in the near future. WVU intends to test catalytic converters and catalyzed traps with F-T diesel fuel.

3.0 EQUIPMENT AND PROCEDURES

3.1 TEST ENGINES AND EXHAUST AFTERTREATMENT DEVICES

Exhaust emissions testing for the West Virginia Diesel Study was performed on four diesel engines. The engines were specified by the West Virginia Diesel Commission so as to encompass most power ranges that would be used during underground mining operations. Table 5 lists basic technical specifications of the engines (further engine details can be found in the Appendix).

3.1.1 MWM D-916-6

A naturally aspirated, pre-chamber, in-line six-cylinder MWM D-916 engine was used for the portion of the study that compared and contrasted the exhaust emissions produced by high (0.25%) sulfur and low (0.05%) sulfur fuel. The experimental setup is shown in Figure A.1 of the Appendix. These tests were scheduled in order to expand upon the results obtained from an earlier Bureau of Mines study performed by the PI, in which a Dry Systems Technology exhaust aftertreatment system on the same MWM D-916.

3.1.2 Lister Petter LPU-2

A naturally aspirated, pre-chamber, in-line two-cylinder Lister Petter LPU-2 engine was tested with various combinations of a DCL/Rohmac exhaust aftertreatment system. Figures A.2 – A.4 of Appendix A illustrate the engine-aftertreatment system and the test bed that was utilized for this study. The combinations of the oxidation catalyst, catalyzed soot filter, and high-temperature paper filter that were used during the experiments are outlined in Table 6.

3.1.3 Isuzu C240

An Isuzu C240, pre-chamber, in-line four-cylinder engine was also tested with various combinations of a DCL/Rohmac exhaust aftertreatment system. Illustrations of the engine-aftertreatment system and the test bed are included as Figures A.10 and A.11 of Appendix A. Details on the combinations are outlined in Table 6.

3.1.4 Caterpillar 3306

A Caterpillar 3306, in-line, direct-injection six-cylinder engine was tested with both a Dry Systems Technologies and a Clean-Air Systems aftertreatment device. The 3306-DST system is illustrated in Appendix A, Figure A.12, while the 3306-Clean Air System setups are presented as Figures A.19 – A.20. Since space constraints prevented the Clean Air trap from being mounted directly to the engine exhaust manifold, an elbow adapter pipe was fabricated. The entire assembly was then double insulated. The resultant setup provided substantial clearance with negligible temperature differences between the exhaust manifold exit and trap entrance. Two 8-Mode tests had to be performed on the DST system due to manufacturing flaws, which necessitated repair by the supplier, Goodman Equipment

Corporation. Brief documentation of the repair procedures and supporting illustrations are included in the Results and Discussion section and Appendix A. The engine specifications for the 3306 are given in Table 5, while the exhaust aftertreatment configuration is presented in Table 6.

ENGINE	MWM D-916-6	LISTER PETTER LPU-2	ISUZU C240	CAT 3306
INJECTION	Indirect	Indirect	Indirect	Direct
CYLINDERS	6 – inline	2 – inline	4 – inline	6 – inline
BORE xSTROKE (in inches)	4.13 x 4.72.	3.38 x 3.15	3.39 x 4.02	4.75 x 6.0
DISPLACEMENT	379 CID (6.234 L)	56.5 CID (0.93 L)	144 CID (2.369 L)	638 CID (10.46 L)
COMPRESSION RATIO	22:1	22:1	20:1	21:1
PEAK TORQUE (in Ft-lbs.)	211 @ 1500 rpm	33.5 @ 2150 rpm	98 @ 1960 rpm	375 @ 1320 rpm
RATED POWER (in Hp.)	82 @ 2100 rpm	20.7 @ 3100 rpm	47.4 @ 3000 rpm	123 @ 2200 rpm

Table 5. Test Engine Specifications

Engine Tested	Exhaust Aftertreatment Device
Lister Petter LPU-2	Rohmac/DCL Catalyzed Trap Followed by Oxidation Catalyst
	Rohmac/DCL Oxidation Catalyst
	Rohmac/DCL Catalyzed Trap Followed by Oxidation Catalyst and Pallflex High Temperature Glass Fiber Filter
Isuzu C240	Rohmac/DCL Catalyzed Trap Followed by Oxidation Catalyst
	Rohmac/DCL Oxidation Catalyst
	Rohmac/DCL Oxidation Catalyst Followed by Catalyzed Trap
Caterpillar 3306	Clean Air Systems Catalyzed Trap
	Drv System Technology dry scrubber system

Table 6. Test Engines and Associated Exhaust Aftertreatment Devices

3.2 ENGINE INSTRUMENTATION

Due to the time constraints imposed by the WV Diesel Study, test bed instrumentation was designed in a modular fashion so as to reduce down-time during the changeover periods between various test engines. Exhaust pressure measurements were made using Validyne Model P305 pressure transducers. These transducers were calibrated before each emissions test. Exhaust temperature measurements were made using Omega K-type thermocouples, which were calibrated on a regular basis as per manufacturer specifications. Representative exhaust temperature and pressure readings that were observed for the emissions tests are presented in Tables 7a and 7b. It should be noted that the backpressures associated with PM traps are largely dependent upon the amount of particulate loading at the time of testing. For this reason it should be understood that the values found in Tables 7a and 7b are only samples of observed values that were obtained at the time that the respective emissions tests were performed.

3.2.1 MWM D916-6

The MWM D916-6 was fitted with a pressure tap at the exit of the exhaust manifold in order to obtain total exhaust pressure measurements. However, since no aftertreatment devices were tested with this engine, pressure and temperature data were not included.

3.2.2 Lister Petter LPU-2

The Lister Petter LPU-2 engine was fitted with exhaust pressure and temperature taps at the entrance and exit of the Rohmac/DCL Aftertreatment system. The pressure differential across the trap and/or oxidation catalyst can be obtained by comparison of the respective aftertreatment configuration data with the baseline backpressure measurements. It should be noted that, due to the over-design of the exhaust-transfer tube, bare-engine total exhaust backpressure was minimal. Lister Petter requires that the maximum exhaust backpressure for the LPU-2 be less than 35 inches of water. Only once did the backpressure

Engine Exhaust Configuration	Mode 1		Mode 2		Mode 3		Mode 4	
	T E M P	P R E S S	T E M P	P R E S S	T E M P	P R E S S	T E M P	P R E S S
Lister Petter LPU-2								
Bare	1457	4.2	904	4.4	748	4.2	581	3.5
Trap 1 + Catalyst	1456	10.2	939	11.1	763	12.3	595	14.0
Catalyst Only	1370	3.2						
Trap 2 + Catalyst								
Trap 2 + Catalyst + Paper Filter								
Isuzu C240								
Bare	1071	0.4	826	1.2	646	0.3	443	0.2
Catalyst Only	1165	0.8			695	0.6		
Trap + Catalyst	1197	5.7	919	5.3	698	4.72	483	3.9
Catalyst + Trap	1197	6.0			708	4.7		
Caterpillar 3306								
Bare	1112		868		696		483	
DST I	1163	25.3	923	23.8	738	22.2	506	23.0
DST I (No Catalyst)	1118	23.0	910	23.5				
DST II	1137	22.0	913	22.2				
Clean Air Systems	1120	14.3	902	15.5	712	20.0	505	22.6
Bare II	1101	1.6	879	1.8	694	1.8	479	1.6
DST Final	1197	23.4	928	22.0	739	22.4	525	22.0

Table 7a. Observed Exhaust Temperatures (in °F) and Backpressures (in inches of H₂O) for Modes 1 - 4

Engine Exhaust Configuration	Mode 5		Mode 6		Mode 7		Mode 8	
	T E M P	P R E S S	T E M P	P R E S S	T E M P	P R E S S	T E M P	P R E S S
Lister Petter LPU-2								
Bare	1186	2.8	771	3.4	568	2.4	242	2.5
Trap 1 + Catalyst	1213	11.1	826	9.0	597	8.1	265	2.3
Catalyst Only	1204	2.0			607	1.0		
Trap 2 + Catalyst			806	25.0	595	20.0		
Trap 2 + Catalyst + Paper Filter					612	14.1		
Isuzu C240								
Bare	1092	~ 0	754	~ 0	544	~ 0	194	~ 0
Catalyst Only	1220	0.2			588	0.1		
Trap + Catalyst	1268	4.3	863	2.8	620	2.3	228	0.5
Catalyst + Trap	1195	3.8			612	2.0		
Caterpillar 3306								
Bare	1096		702		537		190	
DST I	992	15.5	759	11.9	556	10.4	207	3.2
DST I (No Catalyst)								
DST II	1030	13.3			540	9.4		
Clean Air Systems	993	10.8	708	6.7	518	8.2	192	0.8
Bare II	981	1.5	699	0.9	505	0.4	208	~ 0
DST Final	980	13.3	728	10.9	803	9.7	216	2.7

Table 7b. Observed Exhaust Temperatures (in °F) and Backpressures (in inches of H₂O) for Modes 5 – 8.

exceed this value, and that was during the initial regeneration cycle (40 inches). After this test, a Rohmac representative inspected the system and performed a pressurized cleaning.

3.2.3 Isuzu C240

As with the LPU-2, the Isuzu C240 engine was fitted with exhaust pressure and temperature taps on the entrance and exit of the Rohmac/DCL aftertreatment. Again, the pressure differential across the trap and/or oxidation catalyst can be obtained by comparison of the respective aftertreatment configuration data with the baseline backpressure measurements. Isuzu specified that the maximum engine exhaust backpressure could not exceed 40 inches of water. Values observed while testing never exceeded 30 inches.

3.2.4 Caterpillar 3306

The Caterpillar 3306 was fitted with exhaust pressure and temperature taps on an insulated elbow at the exit of the exhaust manifold. In addition, for the DST tests a thermocouple was also placed at the exit of the paper filter canister. Caterpillar recommends that exhaust system backpressure should be maintained below 34 inches of water, and this backpressure limit was never exceeded.

3.3 OPERATING CONDITIONS

All test engines were operated at eight different steady state modes. The engine speed and load factors of the 8 Mode test cycle (30CFR, Part 7) are shown in Table 8. The operating speeds and loads are similar to those listed in the ISO/DIS 8178-4 Section 6.3.1.1, "Test Cycles Type C - Off-Road Vehicles and Industrial Equipment". When overall emission reduction or weighted-averages were reported, the associated weighting factors given in Table 8 were used.

Mode Number	Engine Speed	Load Factor (%)	Weighting Factor
1	Rated	100	0.15
2	Rated	75	0.15
3	Rated	50	0.15
4	Rated	10	0.10
5	Intermediate	100	0.10
6	Intermediate	75	0.10
7	Intermediate	50	0.10
8	Idle	0	0.15

Table 8. The 8-Mode Test Cycle

3.4 DYNAMOMETERS

In order to simulate real-world loading operations on an engine in a laboratory environment, a dynamometer, or power absorber, is used. Engine testing is generally performed with one of three basic types of dynamometers. In order to familiarize the reader with the basic principles of operation, the following discussion has been included.

3.4.2 Water-brake Dynamometers

Water-brake, or fluid, dynamometers are generally divided into two categories: viscous shearing types and agitator types. Viscous shearing fluid dynamometers absorb engine loads by shearing a fluid between a rotor and a stator (housing). The amount of load is controlled by varying the flow rate of water into the housing. An agitator fluid dynamometer loads an engine by changing the direction of water flow from rotor vanes to stator (housing) vanes, i.e. an inward flow to an outward flow. The associated change in momentum results in a reaction force on the stator housing. In addition, a viscous shearing force is superimposed as the rotor cuts through the fluid moving from rotor pockets to stator pockets. Load adjustment for the agitator-type fluid dynamometers is accomplished by varying the inlet water flow rate or the restriction of the casing outlet.

3.4.3 Eddy-Current Dynamometers

Air-cooled eddy current dynamometers operate by establishing a magnetic field by energizing a set of stationary coils with DC power. Iron rotors, which are attached to the output shaft of the test engine, rotate in the magnetic field and generate eddy currents in the rotors which produce a counter force to the direction of rotational motion. The power absorbed by the dynamometer is then dependent upon the amount of DC power applied to the dynamometer and the speed at which it is rotating. The absorbed energy is converted into heat in the two externally located rotors, which are designed with curvilinear cooling fins for fast heat dissipation. The windage losses associated with this cooling are compensated for during data reduction.

3.4.4 Electric Dynamometers

Electric dynamometers operate much like electric motors. In fact, to start the test engine, the dynamometer is operated as an electric motor, while the fuel (for compression-ignition engines) or ignition (for spark-ignition engines) sources for the test engine are disabled. In such a motoring configuration, the parasitic, or frictional, losses of the engine can be measured and simulations of coast-down may be performed. Once the fuel or ignition source for the engine is activated, the dynamometer may be used to load the engine by operating in the same manner as a generator. Torque is developed due to the magnetic coupling between the armature and stator. The engine output is then determined from a side-arm load cell that is attached between the stator housing and the dynamometer mounting frame. The load applied to the engine is varied by strengthening the field voltage or reducing the load resistance.

3.5 DYNAMOMETERS USED FOR THE WV DIESEL STUDY

The testing performed for the WV Diesel Study utilized both water-brake and eddy-current dynamometers. The WV Diesel Equipment Commission did not request coast-down test cycles. Therefore, no electric dynamometers were used during this study.

3.5.1 Go-Power D-100 (Lister Petter, LPU-2)

At the onset of the study, WVU did not have an operational test bed that could accurately test smaller engines such as the LPU-2. Although many facilities have tested and reported results from engines of this power output range that were operated with large eddy current dynamometer test beds, WVU was not comfortable with such a scenario. The larger eddy current dynamometers had operating windage losses that were larger than the power output of the LPU-2 during the majority of the proposed test modes. For these modes, WVU believed that unacceptable levels of measurement errors would be encountered. Therefore, given the importance attached to the LPU-2 engine tests by the WV Diesel Equipment Commission, a Go-Power D-100 water brake dynamometer head was acquired from the WVU undergraduate design program. After mounting the Go-Power D-100 and Lister Petter LPU-2 on a custom-built test bed, preliminary tests indicated that the existing dynamometer controls for speed and torque were inadequate. These manual controls were then replaced with automated components from another water brake dynamometer that is on loan to WVU from MSHA. After system optimization, WVU retested the engine/dynamometer combination and found the speed and torque controls to be acceptable.

The Go-Power D-100 water-brake dynamometer has a continuous operating range of 14,000 rpm and a maximum operation speed of 16,500 rpm. The dynamometer is capable of absorbing 100 hp (75 kW). It can handle full continuous loading (65 ft-lb; 90 N-m) at speeds ranging from 4000 rpm through 8000 rpm.

3.5.2 Mustang Dynamometers EC300 (MWM D916-6 and Isuzu C240)

Mustang Dynamometers EC300 eddy current dynamometers were used to control the load applied to the MWM D916-6 and Isuzu C240 engines. The unit is rated for a maximum horsepower of 1100 hp (under cold conditions) and has a continuous rating of 250 hp. It can handle a continuous load of 390 ft-lbs and a maximum load of 2170 ft-lbs (cold conditions).

For the MWM D916-6 engine tests, an existing test bed was used to produce results. The MWM engine test cell was outfitted with a Dyne Systems Co. DTC-1 throttle controller and a Dyne System Co. Dyn-Loc IV dynamometer controller. For the Isuzu test cell, a custom test bed was constructed and the cell was fitted with a manual fuel control linkage and a Dyn-Loc IV dynamometer controller.

3.5.3 Mustang Dynamometers K-400 (Caterpillar 3306)

The Caterpillar 3306 engine was mounted on a customized test bed equipped with a K-400 Mustang dynamometer. The dynamometer was rated at 400 hp. Engine fueling rate was controlled pneumatically via the Caterpillar air actuator, and a Dyne-Loc IV dynamometer controller was used to control speed and load set points. Engine load measurements were made with an Interface SSM-500 load cell, mounted in a side-arm arrangement to the dynamometer housing. Engine speed was measured with an Accu-Coder Model 220C PU rotary encoder.

3.6 DYNAMOMETER CONTROLS

3.6.1 Water-Brake Controls

For the water-brake test rig, a Mason Eilan Camflex II dynamometer controller was used to vary the load applied by the dynamometer. The system consists of a control unit and an electro-pneumatic water control valve. It is capable of using either torque or speed as the controlling parameter. In the "torque mode", a torque set point is compared to output from the load cell, which is mounted to the dynamometer case. In the "speed mode", an engine speed set point is compared to output from an angular speed encoder, which is mounted on the dynamometer shaft. In either mode of operation, the controller then varies the output voltage to the water control valve, in order to achieve the controlling parameter set point.

3.6.2 Eddy-Current Controls

For the eddy-current test rigs, Dyne-Loc IV dynamometer controllers were used to vary the load applied by the dynamometer. The Dyne-Loc IV is capable of using either torque or speed as the controlling parameter. In the "torque mode", a torque set point is compared to output from a side-arm load cell, which is mounted to the dynamometer frame. In the "speed mode", an engine speed set point is compared to output from an angular speed encoder, which is mounted on the dynamometer shaft. In either mode of operation, the controller then varies the output current to the dynamometers in order to achieve the controlling parameter set point. The control unit is capable of maintaining speed and load set points to within ± 2 rpm and ± 2 ft-lbs., respectively.

For the portion of the testing where the MWM test rig was used, a Dyne Systems DTC-1 throttle controller was used to control the engine fueling-rate. The DTC-1 consists of a control unit, which is interfaced with the Dyn-Loc IV dynamometer controller, and a throttle actuator, which is mounted on the engine and attached to its fuel control linkage. By comparing an operator-defined set point with test rig output, the desired fueling rate, and hence engine speed, is obtained. The DTC-1 can be operated with either torque or speed as the controlling parameter.

3.7 TEST FUELS

The testing performed under the WV Diesel Study utilized both high (0.37%) sulfur and low (0.04%) sulfur diesel fuel number 2. The high sulfur fuel was purchased from Ashland Oil, and the low sulfur fuel was obtained from BP Oil. Analysts, Inc. tested representative samples of both fuel types, and the results of the analysis are presented in Tables 5 and 6. For the remainder of the report, the actual fuel sulfur content will be used interchangeably with the maximum standard sulfur content. According to Federal regulations, high sulfur diesel can have a maximum of 0.5 % sulfur content by weight, whereas low sulfur can have a maximum of 0.05 %. A comparative study between these two fuels was performed using the MWM D916-6 in order to determine the effects of sulfur content on baseline engine exhaust emissions. For the remainder of the study, the low sulfur fuel was used, in accordance with the requirements of 30 CFR, Part 7.

3.8 WEST VIRGINIA UNIVERSITY ENGINE RESEARCH CENTER

This section discusses the experimental equipment and procedures that were used to test the performance of the various exhaust aftertreatment systems on the engines that were selected by the West Virginia Diesel Commission. All engine testing was performed at the West Virginia University Engine Research Center in Morgantown, WV. The total exhaust dilution tunnel, gaseous and particulate matter sampling equipment, and testing and calibration procedures are presented herein.

3.8.1 Full-Flow Exhaust Dilution Tunnel

The obvious reason for performing exhaust emissions testing is to determine the effects of tailpipe exhaust on humans. In order to do this, it is necessary to simulate the dilution process of tailpipe emissions in a laboratory. Not only does this dilution process account for in-use exhaust-air interactions, but it also serves to quench post-cylinder combustion reactions and to lower the exhaust gas dewpoint in order to inhibit condensation. Exhaust line quenching is necessary in order to prevent inconsistent emissions measurements. The elimination of condensation is paramount, since water droplets can absorb certain gaseous components (for example, NO₂). In addition, the presence of water in sampling lines would affect certain instruments, such as the non-dispersive infrared analyzers, and particulate matter measurements.

Two main dilution strategies are available for engine testing, full-flow dilution tunnels and mini-dilution tunnels. A full-flow tunnel collects the entire exhaust stream from the engine and mixes it with fresh ambient air, whereas a mini-, or partial, dilution tunnel samples a portion of an exhaust stream and dilutes this sample quantity with fresh ambient air. The WVU full flow dilution tunnel was designed and operated in accordance with 30 CFR, Part 7; 40 CFR, Part 86, Subpart N; and 40 CFR, Part 89.

Fuel Properties for High Sulfur Diesel Fuel No. 2			
Properties	Measured	Minimum	Maximum
Distillation, °F			
Initial Boiling Point	374		
Recovered –5%	423		
–10%	444		
–20%	468		
–30%	484		
–40%	501		
–50%	517		
–60%	534		
–70%	553		
–80%	576		
–90%	609	540	640
–95%	640		
End Point – FBP	655		
Recovery, % volume	97.9		
Residue, % volume	1.0		
Loss, % volume	1.2		
Viscosity @40°C, cSt	2.7	1.9	4.1
Sulfur Content, % Weight	0.37		0.5
Hydrocarbon Types			
Aromatics, % volume	34.6		35
Olefins, % volume	3.1		
Saturates, % volume	62.3		
API Gravity @ 60°F	32.2		
Cetane Index (Calculated)	43.3	40	
Cetane Number (Measured)	46.0	40	
Flash Point, °F	152	125	
Analysis Conducted by: <div style="text-align: center;"> Analysts Incorporated P.O. Box 23200 Oakland, CA 94623 800-424-0099 (Voice) 510-536-5994 (Facsimile) </div>			

Table 9a. Fuel Analysis Results for High Sulfur Fuel

Fuel Properties for Low Sulfur Diesel Fuel No. 2			
Properties	Measured	Minimum	Maximum
Distillation, °F			
Initial Boiling Point	377		
Recovered -5%	414		
-10%	429		
-20%	449		
-30%	471		
-40%	490		
-50%	509		
-60%	528		
-70%	548		
-80%	571		
-90%	601	540	640
-95%	632		
End Point – FBP	648		
Recovery, % volume	97.6		
Residue, % volume	1.2		
Loss, % volume	1.2		
Viscosity @40°C, cSt	2.6	1.9	4.1
Sulfur Content, % Weight	0.04		0.05
Hydrocarbon Types			
Aromatics, % volume	29.1		35
Olefins, % volume	2.1		
Saturates, % volume	68.8		
API Gravity @60°F	35.6		
Cetane Index (Calculated)	47.9	40	
Cetane Number (Measured)	47.0	40	
Flash Point, °F	148	125	
Analysis Conducted by: <div> Analysts Incorporated P.O. Box 23200 Oakland, CA 94623 800-424-0099 (Voice) 510-536-5994 (Facsimile) </div>			

Table 9b. Fuel Analysis Results for Low Sulfur Fuel

The WVU full-flow system is based upon the critical flow venturi – constant volume sampler (CFV-CVS) concept. A blower is used to draw diluted engine exhaust through critical flow venturis, via a stainless steel 18 in. (0.46m) diameter, 40 ft.(12.2m) long dilution tunnel. The laboratory uses a 75 Hp blower in tandem with a single 400cfm and two 1000 scfm venturis in order to provide total tunnel flow rates ranging from 400 – 2400 cfm. A schematic of the test facility is shown in Figure 1.

At the entrance to the tunnel, the entire engine exhaust was injected into an annulus of dilution air upstream of a mixing orifice plate. The two streams are merged in the mixing region, and, at a distance of 15 ft. (4.6 m) downstream of the orifice plate, sample probes were placed to collect dilute gaseous exhaust samples. These probes are attached to the exhaust gas analyzer bench via electrically heated lines. At the end of the sampling region, diluted exhaust is drawn into a 4 in. (0.10 m) diameter stainless steel secondary dilution tunnel by the particulate sampling system. Additional dilution air can be injected into this secondary tunnel in order to increase the dilution ratio (this can be used to ensure a soot collection filter face temperatures of less than 125°F). This sample flow is then routed through the remainder of the particulate sampling and exhausted into the analyzer bench manifold. The design specifics and testing evaluations of the full flow exhaust dilution tunnel were reported by Smith, 1993.

3.8.2 Critical Flow Venturi

In compliance with the CFR 40, Subpart N, a constant volume sampler (CVS) was used to regulate the flow of diluted exhaust through the dilution tunnel. A constant mass flow rate is maintained in the dilution tunnel once the venturi section reaches sonic conditions (state of choked flow), as per the theory of critical flow nozzles (Smith and Matz, 1962 and ISO 9300, 1990).

Under choked conditions, the flow rate of a gas through a critical flow venturi is a function of the diameter of the venturi throat and the upstream temperature and pressure. A Viatran absolute pressure transducer, Model No 1042 AC3AAA20, recorded upstream pressure and temperature was logged via a Tayco 3-wire resistive temperature device, Model No. 68-3839. The mass flow rate was then calculated as follows:

$$Q = \frac{K_v P}{\sqrt{T}} \quad \text{Equation 1}$$

where,

- Q = flow rate in standard cubic feet per minute at standard conditions of 20°C, 101.3 KPa (68°F, 29.92 in Hg).
- K_v = calibration coefficient.
- P = absolute pressure at venturi inlet, in KPa, (Hg).
- T = absolute temperature at venturi inlet, °K, (°R).

The venturis were calibrated (Smith II, 1993) with the use of a subsonic flow venturi traceable to NIST. The CFV-CVS system utilizes a system of three critical venturis

installed in-line with a 55.9 KW. (75 Hp) centrifugal blower. Two of the venturis have a design flow rate of 28.3 m³/min. (1000 scfm) and the third has a design flow rate of 11.32 m³/min. (400 scfm). Therefore, a maximum tunnel flow rate of 67.92 m³/min. (2400 scfm) can be achieved by using this system.

3.8.3 Secondary Dilution Tunnel and Particulate Sampling System

The WVU Engine Research Center uses a proportional sampling, double dilution method for particulate matter collection and analysis. In such a system, a diluted exhaust sample is drawn from the sampling region of the full-flow dilution tunnel into a secondary dilution tunnel. The flow rate into this secondary tunnel is varied throughout an emissions test in order to draw a proportional sample from both dilution tunnels. In the secondary dilution tunnel, additional dilution air may be added in order to obtain high dilution ratios and filter face temperatures below 51.7°C (125°F). The sample flow is then drawn across PM collection filters, which enables the determination of the amount of DPM collected during a test cycle via gravimetric analysis. DPM consists of elemental carbon, soluble organic fractions, sulfates, and bound water. The PM sample flow is then exhausted into a common sampling-stream exhaust manifold.

Specifically, the WVU sampling system draws a diluted exhaust sample through a 1.3 cm (0.5 inches) diameter transfer tube, 17.8 cm (7 inches) in length, located in the sampling zone of primary dilution tunnel. The inlet faces upstream and is connected to the stainless steel secondary dilution tunnel, which is 7.62 cm (3.0 inches) in diameter and 76.2 cm (30 inches) long. The secondary tunnel provides sufficient residence time for the exhaust sample to be mixed with the dilution air, resulting in a sample with a temperature less than 51.7°C (125°F). The sample stream is drawn across a stainless steel filter holder, which attaches to the end of the secondary dilution tunnel. The filter holder houses two (a primary and a secondary) Pallflex 70 mm (2.76 inches) fluorocarbon-coated glass fiber filters, Model T60A20, upon which the DPM is collected. Two Sierra 740-L-1 series mass flow controllers and two Gast series 1023-101Q-583X rotary vane pumps control total secondary tunnel flow and secondary dilution airflow. An additional check on flow rates is provided by corrected measurements from a roots positive displacement flow meter. The total secondary flow ranges from 0 lpm to 170 lpm (0 scfm to 6 scfm) while the secondary dilution air flow ranges from 0 lpm to 85 lpm (0 scfm to 3 scfm). The mass flow controllers are routinely returned to Sierra for calibration. Additionally, the controllers are checked at WVU using a Meriam Instruments laminar flow element (LFE) Model No. 50MW20 rated at 0 m³/min to 6.52 m³/min (0 scfm to 23 scfm).

Further details of the WVU Particulate Sampling System were reported by Smith, 1993.

3.8.4 Gaseous Emission Sampling System

The WVU Engine Research Center's gaseous emissions sampling system consists of heated sample probes, heated transfer lines, and a gas analysis bench. Three heated stainless steel sample probes were installed 10 diameters downstream of the mixing zone origin in the primary dilution tunnel in order to ensure fully developed turbulent duct flow. The probe tips were inserted six inches into the diluted exhaust flow stream and were directed toward the tunnel inlet (upstream). These probes are connected to the gaseous emission sampling bench via electrically heated lines. The hydrocarbon probe and line were maintained at a wall temperature of $191^{\circ}\text{C} \pm 6^{\circ}\text{C}$ ($375^{\circ}\text{F} \pm 10^{\circ}\text{F}$) by Fuji Model #223-1806 temperature controllers, in order to prevent the higher-molecular weight hydrocarbons from condensing out in the sampling stream. The NO_x and CO/CO_2 probes and lines were maintained at $113^{\circ}\text{C} \pm 6^{\circ}\text{C}$ ($235^{\circ}\text{F} \pm 10^{\circ}\text{F}$) by the temperature controllers in order to prevent water condensation, which would lead to analyzer measurement errors.

The gas analysis system consisted of four major components: CO_2 analyzer, CO analyzer, NO_x analyzer, and a HC analyzer. The gas analysis bench housed Rosemount and Beckman analyzers and the sample flow conditioning system. Low CO and CO_2 emissions were analyzed using Rosemount 868 and 880 Series Non-Dispersive Infrared (NDIR) analyzers. NO_x measurements were performed by a Rosemount Model 955 heated chemiluminescent analyzer. A Beckman Model 958 NO_x efficiency tester was included in the bay in order to ensure that the Model 955 operated at above 90% converter efficiencies, as per CFR 40, Part 86, Subpart N. A stand-alone Rosemount Model 402 heated flame ionization detector was used to measure exhaust hydrocarbons.

3.8.5 Exhaust Gas Analyzers

In order to make this document complete, a brief explanation of analyzer theory is included in this section. Additional information on the analyzer theory and operation can be obtained from Rosemount operations manuals.

3.8.5.1 Hydrocarbon (HC) Analyzer

The hydrocarbon analyzer is a Rosemount Model 402 heated flame ionization detector (HFID). Exhaust hydrocarbon levels are measured by counting elemental carbon atoms. A regulated flow of sample gas flows through a flame that is produced by regulated flows of air and pre-mixed hydrogen/helium fuel gas (FID fuel). The flame causes ions to be produced, which are in turn collected by polarized electrodes. The ion absorption produces a current flow through the associated electronic measuring circuitry that is proportional to the rate at which carbon atoms enter the burner (Heinein and Patterson, 1972 and Reschke, 1977). The Model 402 is capable of measuring hydrocarbon concentrations from 50 parts per million (ppm) to 250,000 parts per million and produces a full-scale linear output.

3.8.5.2 Carbon Monoxide (CO)/Carbon Dioxide (CO₂) Analyzers

The CO and CO₂ analyzers are Rosemount Model 868 and 880 Non-Dispersive Infrared (NDIR) analyzers. The NDIR operates upon the principle of selective absorption. Loosely stated, the infrared energy of a particular band of wavelengths, specific to a certain gas, will be absorbed by that gas, whereas infrared energy of other bands will be transmitted. The NDIR then determines gas concentration by the amount of transmitted (or absorbed) energy. The transmission (or absorption) is directly proportional to the concentration of the measured component gas. The NDIR's do not produce a linear output; therefore it was necessary to generate calibration curves for each of the analyzers. There are two CO analyzers on the gas analysis bench, a high CO analyzer and a low CO analyzer. The high CO analyzer has ranges of 0-2 percent and 0-10 percent while the low CO analyzer has ranges of 0-1000 ppm and 0-5000 ppm. The low CO analyzer was the only CO analyzer used in this research. The CO₂ analyzer has ranges of 0-5 percent and 0-20 percent.

3.8.5.3 Oxides of Nitrogen (NO_x) Analyzer

The NO/NO_x analyzer used is a Rosemount Model 955 Chemiluminescent Analyzer. The analyzer can determine the concentration of either NO or NO + NO₂ which together is called NO_x. For the determination of NO, the sample NO is quantitatively converted into NO₂ by gas-phase oxidation with molecular ozone. When this reaction takes place, approximately 10% of the NO₂ molecules are elevated to an electronically excited state, followed by immediate reversion to the non-excited state. This conversion process produces a photon emission. A photon detector (multiplier tube) is then used to produce an instrument response that is proportional to the NO present in the original sample. The operation for NO_x is identical to that of NO except that the gas sample stream is first passed through a converter which converts the NO₂ into NO. In this case, the instrument response is proportional to the NO present in the original sample plus the NO produced by the dissociation of NO₂.

3.8.6 Bag Sampling

Diluted exhaust gas and background dilution air samples were collected in 80 liter Tedlar bags during each emissions test. After each test, the bags were analyzed and then evacuated, so as to be available for subsequent testing. The background dilution air bag was analyzed and the concentration levels were used to account for the dilution air contribution to emissions levels that were recorded during a given test. The dilute bag sample, when compared to the continuous sample, served as a quality control/quality assurance check.

3.8.7 Instrumentation Control and Data Acquisition

The software used in the study was already developed and installed in the Stationary Laboratory (Chasey, 1992) at West Virginia University. The program

utilized an RTI-815F data acquisition board and rack-mounted signal conditioning boards, comprised of Analog Devices 3B series conditioning modules.

The data acquisition programs acquired the raw data (in the form of ADC codes) and a reduction program (Pei, 1995) converted the raw data into proper engineering units.

3.8.8 Fuel and Air Flow Metering

Producing accurate dilution ratios for a full-flow dilution tunnel involves recording total tunnel volume flow rates and engine exhaust mass flow rates. Tunnel flow rates are measured using the CFV-CVS system. However, due to backpressure limitations and extreme temperatures and high particulate concentrations, engine exhaust flow rates are not directly measured. Instead, an indirect approach is used to calculate engine exhaust flow rates, where a summation of engine fuel consumption rates and engine air flow rates are used.

A Max Flow Media 710 Series Fuel Measurement System measures and performs the fuel flow rate measurements. During testing, a transfer pump directs fuel from the storage tank, through a filter, and into a vapor eliminator, which is maintained at 30 psi. Before entering a Model 214 piston-displacement flowmeter, excess fuel is routed via a pressure regulator through an internal heat exchanger and then back to the storage tank. This internal heat exchanger uses the by-pass supply fuel to cool the engine return fuel. The metered fuel supply then passes into a level-controlled tank. In this tank, it is mixed with unused engine return fuel, which has been cooled in the internal heat exchanger. The tank volume is maintained at a constant level, so the amount of metered fuel recorded during a given test period will necessarily be the quantity of fuel that is used by the engine. The exit to this mixing tank is connected to a secondary fuel pump. In most cases when the system is supplying a high-pressure injection system, this additional pump is used to further increase pressure, so as to minimize the requirements of the engine's original equipment fuel pump. Before the fuel exits the measurement system, it passes through a bubble detector, which controls a solenoid valve that connects the to-engine and from-engine fuel lines. Removal of air and fuel vapors prevents poor engine performance and flowmeter inaccuracies. After the purge solenoid, the fuel passes through an external heat exchanger, where the temperature is controlled via a Fuji Model #223-1806 temperature controllers.

Meriam Laminar Flow Elements (LFE's) measure intake air flow rates. The LFE consists of a matrix of tiny capillaries that are used to produce a laminar flow stream from the normally turbulent flow found in the intake line. As the intake air flows through the triangular-shaped capillaries, friction creates a pressure drop. Meriam supplies a calibration equation and coefficients for each LFE. These are obtained through calibrations involving a flowmeter that is traceable to NIST. Using the absolute pressure and temperature of the inlet flow is known, as well as the differential pressure across the LFE; the volume flow rate of air is obtained from Equation 2.1,

$$\dot{V}_{actual} = \{B \times (\Delta P) + C \times (\Delta P)^2\} \times \frac{\mu_{std}}{\mu_{flow}} \quad \text{Equation 2}$$

where B and C are the coefficients supplied by Meriam, and μ_{std} and μ_{flow} are standard and actual flow kinematic viscosities. The viscosity variations are calculated using correction factors expressed in Equation 2.2,

$$CorrectionFactor = \left(\frac{529.67}{459.67 + T \text{ (in } ^\circ F)} \right) \times \left(\frac{181.87}{\mu g} \right) \quad \text{Equation 3}$$

where,

$$\mu g = \frac{14.58 + \left(\frac{459.67 + T \text{ (in } ^\circ F)}{1.8} \right)^{1.5}}{110.4 + \left(\frac{459.67 + T \text{ (in } ^\circ F)}{1.8} \right)} \quad \text{Equation 4}$$

Specifically, A Meriam Model 50MC2-6 (6" I.D. – 1000 cfm) LFE was used for the MWM D916-6 and Caterpillar 3306 tests, while a Model 50MC2-4 (4" I.D. – 400 cfm) was used for the Lister Petter LPU-2 and Isuzu C240 tests. Differential pressures across the LFE are measured using an MKS 223 B, while upstream absolute pressures are measured with a Setra Model C280E transducer. LFE inlet temperatures are recorded from RTD measurements. All pressure transducers were calibrated before each emissions test.

4.0 QUALITY CONTROL/QUALITY ASSURANCE PLAN

The National Center for Alternative Fuels, Engines, and Emissions and the National Center for Mining Engines and Safety at West Virginia University are committed to a Quality Control/Quality Assurance (QC/QA) program that assures data generation and measurement of the highest quality.

The responsibility for QC/QA rests with one of the senior investigators (the principal investigator or the co-principal investigators) who have been designated as senior engineers on several projects. The senior investigator assigns a project engineer and a laboratory technician, who will not be directly involved with data generation, to assist them. The PI discusses the work plan and QC/QA plan with the project engineer. The engineer, in consultation with the senior investigators, ensures that the necessary equipment, supplies, engines, manpower, and other resources are available in accordance with the test schedule. The prime responsibility for management, project execution, work assignment, and deliverables rests with the Principal Investigator (PI). The Co-Principal Investigators (Co-PI) offer their expertise and form an integral part of the management and execution plan.

Dr. Gautam, who serves as the PI for this study, has extensive experience in heavy-duty engine emissions measurement, characterization, and analysis. He was responsible for the design, development, and execution of the emissions measurement systems on both the Transportable Laboratories and in the Engine Research Center (engine cells). Dr. Gautam also serves as the Director of the National Center for Mining Engines and Safety. He has authored technical papers in the area of emissions measurement uncertainty and on novel exhaust conditioning and sampling systems.

West Virginia University Project Management Flowchart for the West Virginia Diesel Study, 1997-1998.

5.0 QUALITY CONTROL/QUALITY ASSURANCE PROCEDURES

Quality control and quality assurance procedures adopted by the WVU Transportable Heavy Duty Vehicle Emissions Laboratory and the WVU engine test cells in the Engine Research Center are given below.

5.1 Emissions Testing

The laboratories are capable of measuring regulated and non-regulated vehicle emissions such as carbon monoxide (CO), oxides of nitrogen (NO_x), total hydrocarbons (THC), total particulate matter (TPM), carbon dioxide (CO₂), oxygen (O₂), and unburned alcohols and aldehydes. Reliable sampling is assured through system design, periodic system inspection, and scheduled instrument calibration.

In order to obtain accurate and repeatable data a strict set of rules and guidelines were developed and adhered to in the experiments. CFR 40, Parts 86 to 99, Subpart N was used as a guideline, but more stringent controls were enforced to ensure repeatability.

5.2 Sampling Lines and Probes

The sampling streams use separate sampling probes and lines with their own pumps (heated in the case of NO_x, THC, and also CO/CO₂ to avoid condensation of moisture in the lines). This design feature ensures reliable operation of the THC and NO_x analyzers.

Because of the nature of the Transportable Laboratory, its components have been designed to withstand a significant mechanical stress during transfer operations. Great care is taken in verifying that emissions measurement equipment is in order before commencement of emissions testing. Prior to performing a test schedule, supervisory personnel verify that all dilution tunnel sample probes are equidistantly located from tunnel center and are oriented with their sample inlets facing upstream. In addition inspections are made to ensure the integrity of the sampling systems. The sampling lines are leak checked (by pressurization) and back-flushed with high-pressure air in order to clean the lines of residual particulate matter. Heated sampling lines and their associated control systems (PID temperature controllers and associated thermocouples) are checked to ensure continuity between the controller, heater elements, and thermocouples. The temperature settings also are verified (THC sampling probes and lines are maintained at 375°F for diesel engines and 235°F for methanol engines while NO_x lines and probes are maintained at 250°F). Sample line temperatures, at various locations, are sampled and recorded at 10Hz at various locations throughout each test in addition to being displayed on the sampling cabinet for monitoring by the operator.

5.3 Pumps and Blowers

Prior to vehicle testing, the secondary dilution air and the secondary tunnel PM sample flow mass flow controllers are calibrated using a Roots-type positive

displacement meter and a laminar flow element. Formaldehyde and alcohol mass flow controllers (in case of alcohol fueled vehicles) are calibrated using a Gillian bubble flow meter. The above mentioned flows are also monitored and recorded during testing using a Roots type positive displacement meter.

5.4 Exhaust Transfer Tube

The exhaust transfer tube, which routes exhaust from the engine exhaust system to the inlet of the primary dilution tunnel, is checked for leaks after assembly. Joints in the tube are sealed using a high-temperature aluminum tape and periodically checked to ensure integrity. The exhaust transfer tube is insulated to minimize errors in PM measurement due to thermophoretic effects.

5.5 Exhaust Analyzer Calibration and Calibration Gases

Calibration procedures utilized by the WVU Engine Research Center are in accordance with the requirements of 40 CFR, Part 86, Subpart N. The gases used to calibrate the exhaust analyzers are certified by the supplier to have an accuracy of 1%, traceable to NIST. No gas cylinder is used if the pressure drops below 200 psig. Zero reference states for the analyzers were provided by zero gas that did not to exceed the following impurity concentrations: 1 ppm equivalent carbon response, 1 ppm carbon monoxide, 400 ppm carbon dioxide, and 0.1 ppm nitric oxide. Span reference was provided by gases with concentrations that were approximately 85% to 95% of the full-scale concentration for the respective analyzer. All exhaust gas analyzers are calibrated using appropriate ranges of calibration gas for the vehicle being tested. These calibrations are performed before each series of tests and after any instrument maintenance has been performed. For the 10-point calibration curve, a Horiba SGD-710C gas divider was used. The divider accurately produced varying concentration of component gas in 10% increments by mixing the span gas with a balance zero reference gas. The instrument readings are allowed to stabilize at each measurement point and a computer averaged (100 points) reading of the instrument is recorded. These data points and corresponding gas concentrations are fitted to a second-degree (third degree in case of NDIRs) polynomial and constitute that particular analyzer's calibration data file. This calibration file overwrites any previous calibration file for that analyzer in order to prevent using incorrect calibration files for testing. The downloaded data disk for each test contains the calibration files for each analyzer.

5.6 Additional Calibration and Maintenance Procedures

In addition to the calibration procedures, each analyzer is subjected to a range of checks and maintenance procedures as described below.

5.6.1 Hydrocarbon Analyzer

The THC analyzer is subjected to the 'FID burner peaking process' to get the highest flame ionization detector (FID) response. This process involves measuring and

recording the response of the instrument to 100% span gas and zero air with various settings of FID burner fuel and air. Upon completion of the FID burner peaking process, the fuel and air settings of the FID are placed at the setting that produced the highest instrument response, and the analyzer is calibrated.

An HC hang-up check is also performed on the heated FID. If the differences in the responses are more than two percent, the sampling probe is backflushed (direct injection of zero air into the analyzer and through the 'overflow' sampling probe) and steps are taken to rectify the problem.

5.6.2 Oxides of Nitrogen (NO_x) Analyzer

On a monthly basis, a NO_x efficiency test is performed on the NO_x analyzer. This test is performed to ensure that the analyzer converter (which converts NO₂ to NO) is performing satisfactorily. A conversion efficiency of less than 90% is considered a failure and maintenance is performed to rectify the situation. Filters in the NO_x sampling are visually inspected and replaced after analyzer maintenance has been performed and whenever necessary.

5.6.3 Carbon Monoxide (CO)/Carbon Dioxide (CO₂) Analyzers

Since moisture can affect the operation of the NDIR analyzers used for carbon monoxide and carbon dioxide, a water interference check is performed. The sample flow is passed through a refrigerator dryer to lower the dew point of the sample stream before it reaches the NDIR.

5.7 Bag Sampling (Dilute Exhaust and Background)

In the WVU Transportable Laboratories two Tedlar bags (80 liters) are used during each test to collect dilute exhaust and background samples for quantitative analysis. This bag analysis of dilute exhaust serves as a check for the continuous gas measurements. Bag sample results from the test are invariably lower than those of the continuous analyzer integrated results. The background sample is used to correct the dilute exhaust reading. This is especially important in regions where background THC is high.

In the engine test cell, a total of six bags are used. Four bags for the FTP cycle (one for each mode), one for the integrated sample of the entire cycle, and one bag for the background sample. For non-FTP testing, only two bags are used – one for the background sample and the other for the dilute exhaust sample.

Prior to each test, the bags are evacuated and the pressure in the bags is noted. Leaks in the bag sample system are indicated when the vacuum reading is less than 26" of Hg. Prior to each test, the bags are purged with zero air and evacuated.

5.8 Particulate Sampling

A 3-inch diameter, 36-inch long secondary dilution tunnel is used for collecting particulate samples on 70-mm fluorocarbon coated glass fiber filters. A proportional sample of the dilute exhaust is drawn from the primary tunnel using an oilless rotary vane pump in series with mass flow controller. Mass flow controllers are used to measure and adjust the flow rates of both secondary dilution air and dilute exhaust sample. These controllers are calibrated using corrected readings from Roots-type positive displacement meters as well as a laminar flow element. The exhaust particulate matter is collected on two (a primary and a secondary) Pallflex 70 mm (2.76 inches) fluorocarbon-coated glass fiber filters, Model T60A20. Filter face temperature is continuously monitored and recorded using a thermocouple. If the temperature rises above 125°F at any time during a test, that test is voided.

Particulate matter collection filters are conditioned prior to, and following each test. An environmental chamber is used to condition the filters at 50% relative humidity (RH) and 70°F for at least one hour but not more than 80 hours. Reference filters are conditioned along with test filters in order to account for the effects of humidity on the filter media. If the average weight of the reference filters changes between $\pm 5\%$ or more of the nominal filter loading (recommended minimum of 5.3 mg), then all sample filters in the process of stabilization (conditioning) are discarded and the emissions tests were repeated. If the average weight of the reference filters changes by more than -1% but less than -5% of the nominal filter loading, then the option is given of either repeating the emissions test or adding the amount of weight loss to the net weight of the sample. If the difference in reference filter weights changed by more than 1% but less than 5% of the nominal filter loading, then the option is given of either repeating the emissions test or accepting the measured sample filter weight values. If the weight of the reference filters changed by less than $\pm 1\%$, then the measured sample weight was used. Background filters are collected and analyzed so as to account for the contribution of the dilution air to the test PM filters (the WVU lab does not filter or condition primary or secondary dilution air). All particulate filters, reference, background, and sample, are stored in glass petri dishes (to minimize loss of particulate matter via static charge) while conditioning in the environmental chamber. These dishes are covered but not sealed to prevent dust from accumulating on the filters while allowing humidity exchange. The total particulate matter (TPM) is determined via pre- and post-weighing, using a CAHN 32 micro-balance, which has a sensitivity of 0.1 μg . The remote weighing unit of the balance is placed on a vibration isolator, and is calibrated using the weights traceable to NIST.

As mentioned earlier, the 30 CFR considers diesel particulate matter to consist of elemental carbon, soluble organic fractions, sulfates, and bound water. Wall and Hoekman, (1984) suggested that at 50% RH, 1.3 grams of water is present for every gram of sulfuric acid. In addition, a linear relationship between bound water and sulfuric acid was reported to exist up to 60% RH. The amount of bound water increases rapidly beyond 60% RH. The 30 CFR recommends humidity control in the environmental chamber to ensure accurate gravimetric analysis of PM. However, when the research objective is to determine the filtration efficiency of exhaust aftertreatment PM control

devices, sulfate formation can often skew findings and conclusions. WVU recognized the inherent inaccuracies in the PM measurement guidelines set forth in CFR 40, but chose to report all test findings in accordance with these accepted government standards.

5.9 Tunnel Injections

Tunnel injections are used as an additional quality assurance procedure to check the operation of the whole emissions measurement system including the dilution tunnel, sample lines, and analyzers. These procedures involve the release of a known amount of gas into the dilution tunnel and a comparison of amount injected to amount recovered.

5.9.1 Propane Injection

Propane injections are performed regularly in order to ensure that the CFV-CVS system was operating within Federal guidelines. The procedure serves primarily as a check on the total dilute exhaust flow rate through the primary dilution tunnel, but it also helps identify HC hang-up in the tunnel and problems in the THC sampling system. Using a calibrated critical orifice and controlled pressure, a known quantity of 99.5% propane is injected into the tunnel. The heated FID was used to measure the continuous concentration of propane in the diluted exhaust sample and dilute and background bag samples are collected. Quantities reported by the continuous and integrated bag samples (minus background) are compared to the known amount of propane injected, in to determine if the THC sampling system and the tunnel are operating correctly. A difference greater than $\pm 2\%$ between the measured and actual injected mass of propane indicated an error in diluted-exhaust mass flow rate measurements. Testing was validated only when two successive propane injection tests reported less than a $\pm 2\%$ difference.

5.10 Data Analysis and Reporting

Quality assurance for data reported from testing is achieved using multiple checks. First, the operators of the laboratory, including the senior supervisory personnel as well as technicians, have a vast amount of experience in testing a multitude of different vehicle/engine/fuel combinations. This experience is valuable in quality assurance since it allows the laboratory operators to identify problems at the test site.

As a test is performed, data is logged to a local hard disk on the data acquisition computer. After the test is completed, data is transferred to a floppy disk as well as separate backup optical drive. A data reduction program is used to extract emissions data from a binary data file and translate it into the appropriate units using calibration files. By monitoring data on-site, supervisory personnel are able to quickly identify and correct any equipment malfunctions.

5.11 Experimental Uncertainty

Determination of uncertainty was approached by considering a quantity, N , that is a function of known variables:

$$N = f(u_1, u_2, u_3, \dots, u_n) \quad \text{Equation 5}$$

The absolute error is given by:

$$E_a = \Delta N = \left| \Delta u_1 \frac{\partial f}{\partial u_1} \right| + \left| \Delta u_2 \frac{\partial f}{\partial u_2} \right| + \dots + \left| \Delta u_n \frac{\partial f}{\partial u_n} \right| \quad \text{Equation 6}$$

However, when the Δu 's are not considered as absolute limits, but as $\pm 3s$ limits, the errors are computed from the root-sum square formula.

$$E_{a_{rs}} = \Delta N = \left[\left(\Delta u_1 \frac{\partial f}{\partial u_1} \right)^2 + \left(\Delta u_2 \frac{\partial f}{\partial u_2} \right)^2 + \dots + \left(\Delta u_n \frac{\partial f}{\partial u_n} \right)^2 \right]^{1/2} \quad \text{Equation 7}$$

A normal distribution is assumed for the random errors. The "Z value" for the normal distribution for a 95% confidence level is 1.96. Adding all the bias and random errors, the total error was obtained.

$$Z_{95\%} = 1.96$$

The full dilution tunnel particulate mass equation is

$$P_{\text{mass}} = (V_{\text{mix}} + V_{\text{sample}}) * \left[\frac{P_e}{V_{\text{sample}}} - \left(\frac{P_{\text{back}}}{V_{\text{back}}} * \left[1 - \frac{1}{\text{DF}} \right] \right) \right] \quad \text{Equation 8}$$

where

P_{mass}	=	volume corrected particulate mass.
V_{mix}	=	total dilution exhaust volume.
V_{sample}	=	volume of dilute exhaust flow across the primary and secondary filters.
P_e	=	particulate mass from the gravimetric analysis.
P_{back}	=	particulate mass from the background filter.
V_{back}	=	volume of background flow across the background filter.
DF	=	dilution factor.

and the uncertainty, DP_{mass} is

$$\Delta P_{\text{mass}} = \left[\left(\frac{\partial P_{\text{mass}}}{\partial V_{\text{mix}}} \Delta V_{\text{mix}} \right)^2 + \left(\frac{\partial P_{\text{mass}}}{\partial V_{\text{sample}}} \Delta V_{\text{sample}} \right)^2 + \left(\frac{\partial P_{\text{mass}}}{\partial P_e} \Delta P_e \right)^2 + \left(\frac{\partial P_{\text{mass}}}{\partial P_{\text{back}}} \Delta P_{\text{back}} \right)^2 + \left(\frac{\partial P_{\text{mass}}}{\partial V_{\text{back}}} \Delta V_{\text{back}} \right)^2 + \left(\frac{\partial P_{\text{mass}}}{\partial \text{DF}} \Delta \text{DF} \right)^2 \right]^{1/2}$$

$$\quad \text{Equation 9}$$

A detailed error analysis of the WVU Engine Research Center can be found in Gupta, 1996.

6.0 RESULTS AND DISCUSSION

All emissions test results may be found in graphical form at the conclusion of this section. In addition, the recorded emission data for the entire study is presented in Appendix B (in g/hr) and Appendix C (in g/bhp-hr). An overview of the particulate reductions for all engine-exhaust aftertreatment configurations is included in Tables 1 - 4 at the end of the Executive Summary.

When reporting findings concerning diesel particulate matter (PM) reductions, it should be noted that the 30 CFR considers diesel particulate matter to consist of elemental carbon, soluble organic fractions, engine wear metals, sulfates, and bound water. Therefore, the mass measurements of collected PM could consist of all of these contributors. Of particular interest is the contribution of sulfates and bound water. Wall and Hoekman, (1984) suggested that at 50% RH, 1.3 grams of water is present for every gram of sulfuric acid. In addition, a linear relationship between bound water and sulfuric acid was reported to exist up to 60% RH, with a rapid increase at levels above 60%. Such bound water would tend to skew reported conclusions, particularly since water is not the PM component that is associated with any known health hazards or targeted for reduction. Increased sulfate production, which results in increased amounts of bound water on sample filters, often results from the use of high contents of noble metal catalysts, such as platinum, in aftertreatment devices. Although most manufacturers are reluctant to divulge information on their catalyst coatings, it is believed that the high sulfate production levels encountered during this study were a direct result of such large quantities.

6.1 MWM D916-6 Results

An MWM D916-6 was used to compare emissions levels produced by an engine operating on diesel fuels of different sulfur content. Specifically, the study measured the combustion products generated during engine operation with high sulfur (0.37 %) fuel and low sulfur (0.04 %) fuel. Figure 2 indicates a slight reduction in measured particulate matter, while Figures 3 - 6 indicate that gaseous emissions, as expected, were basically unaffected by the fuel sulfur content. The complete test results, averaged over three tests per operating mode, are presented in Table B.1-1 (in g/hr) and Table C.1-1 (in g/bhp-hr). In conclusion, the lower sulfur content produced a weighted 8-mode particulate matter reduction of approximately 22 %.

6.2 Lister Petter LPU-2 Results

A Lister Petter LPU-2 was used to test the emissions reduction performance of a Rohmac/DCL exhaust aftertreatment system. The engine-aftertreatment system is shown in Figures A.2-1 and A.2-2, while Figure A.2-3 illustrates the test bed setup. Emission data is presented in graphical form in Figures 7 - 23, while the reduced data for all tests is compiled in Appendix B.2-1 - B.2-2 (in g/hr) and Appendix C.2-1 and C.2-2 (in g/bhp-hr).

After results were compiled from the first 8-mode test, WVU concluded that a failure had occurred in the catalyzed particulate filter, due to the characteristically low particulate reduction values. This failure could have occurred prior to the trap being tested at WVU, or during regeneration that was performed at WVU prior to the 8-mode test. WVU and Rohmac returned the particulate filter to DCL, where backpressures were compared to other comparable models. DCL concluded that the trap had indeed failed and provided a replacement. Once the new particulate trap was installed, preliminary test indicated that the trap would not be able to handle the associated high engine exhaust emissions rates. While attempting to perform another 8-mode test, engine exhaust backpressures exceeded limitations imposed by Lister Petter. After consulting Rohmac and DCL, WVU decided to perform only a limited amount of testing with the new trap. Obviously the backpressures associated with the new trap were much higher than those of the initial trap, which had failed during pre-test operation. In order to produce preliminary results for the Pallflex high-temperature glass-fiber paper filter, a single Mode 7 test was performed.

Particulate reduction results for all LPU-2 engine-system configurations are presented in Figures 7 – 11. As the data indicates, the particulate reduction for the initial (failed) trap ranged from 15 % - 87 %, with a weighted 8-mode average of 64.4 % (see Table 2 at the end of the Executive Summary). The replacement trap-catalyst system provided an average reduction of 80 % over Modes 6 and 7. The single Mode 7 test performed with the trap-catalyst and paper filter yielded a 95 % reduction, while the catalyst only modes reduced particulate by an average of 43 %. Total hydrocarbon reductions are presented in Figures 12 – 14, with an overall average for the initial trap-catalyst system of 97 %. Similar results for HC were obtained by the other aftertreatment system configurations. . The Rohmac/DCL system provided significant reductions of carbon monoxide (CO), with an overall average of 90 % (see Figures 15 – 19). Similar reductions were obtained for the replacement trap tests, as well as the catalyst-only tests. Figures 20 – 23 indicate that, although the system made no provisions for reduction, oxides of nitrogen (NO_x) were reduced by 28 % by the original Rohmac/DCL system, with as much as 50 % reductions being produced by the catalyst only tests. Such attenuation is attributed largely to high fueling rates and, in part, to increased exhaust backpressures. High fueling rates can cause a reducing atmosphere in the exhaust, whereas high exhaust backpressures result in internal exhaust gas recirculation, which inhibits the in-cylinder formation of NO_x .

Regeneration studies were performed on both the traps. The regeneration process consisted of operating the engine at rated power for approximately five minutes, followed by a five minute run at high idle (no load at rated speed). This two-step process first elevated the exhaust temperature, in order to achieve trap light-off, and then supplied the system with excess oxygen, in order to assist the regenerative combustion process. Collected data for three regenerative cycles is found in Appendix D. Two cycles were performed on the original (failed) trap, while only one test could be run on the replacement trap, due to manufacturer-imposed backpressure limitations. Figures D.1-1 - D.1-5 represent the first regeneration test for the original (failed) trap-catalyst system, while the second regenerative cycle is included in Figures D.2-1 - D.2-5. The

regeneration tests for the initial trap seemed to exhibit trends that are characteristic of normal trap regeneration. During the first regeneration test on the original trap, hydrocarbon (HC), carbon monoxide (CO), and carbon dioxide (CO₂) traces all peaked during particulate combustion and then decreased as the trap regeneration ceased. The reduced system backpressure curve is also indicative of a regeneration process. The second regeneration study with the failed trap did not exhibit such characteristic trends. Since the engine did not experience very much operation between the first and second regenerative tests, WVU surmises that low particulate loading levels were the reason for the different results. It should be noted that the engine was operated at low load conditions for at least three hours prior to the first regeneration study. The low exhaust temperatures associated with such operation is not at all conducive to trap light-off, so, even in its failed state, the trap would have had a considerable amount of particulate loading. Data from the third regeneration test (see Figures D.3-1 – D.3-5) indicates that a successful new-trap regeneration did not occur. Unlike the failed trap tests, the replacement trap's loading and associated backpressure could not be reduced via the regeneration procedure. Since a failure path was not present, the trap had a much higher loading rate – high enough that the particulate reductions afforded by regeneration could not keep up with the rate of particulate deposition associated with continuous operation. For this reason only a limited number of modes could be run before exhaust backpressure levels exceeded Lister Petter's imposed limitations. At the conclusion of the replacement trap tests, WVU urged Rohmac to contact Lister Petter in order to derate the engine. Since then, Lister Petter has derated the LPU-2, while remaining within the constraints of MSHA's original certification. Under the time constraints imposed by Phase 1 of the WV Diesel Study, further tests of this derated LPU-2 were not performed. However, tests have been scheduled as part of Phase 2.

6.3 Isuzu C240 Results

An Isuzu C240 was used to evaluate the emission reduction capabilities of a second Rohmac/DCL exhaust aftertreatment system. Similar to the LPU-2 system, the C240 system consisted of a catalyzed particulate filter in series with an oxidation catalyst. With the experience afforded by the Lister Petter tests, WVU advised Rohmac to size the catalyst and particulate filters for the Isuzu C240 system after baseline emissions values were established. For the C240 tests, WVU and Rohmac wanted to optimize system efficiency by altering the order of the oxidation catalyst and catalyzed particulate filter. A full 8-mode test was performed with the catalyst positioned downstream of the particulate trap, while 4 modes (1, 3, 5, and 7) were tested with the catalyst positioned upstream. In addition, the engine was operated for 4 modes (1, 3, 5, and 7) with only an oxidation catalyst. While performing the 8-mode test, the trap-catalyst system did not need to be regenerated. At the conclusion of the reported emissions tests, informal regeneration procedures were performed. Although time constraints did not permit data recording, typical regeneration patterns were observed.

Test results for the Isuzu C240 are presented in Figures 24 - 43 and in Appendix Tables B.3-1 and B.3-2 (in g/hr) and Tables C.3-1 and C.3-2 (in g/bhp-hr). The weighted 8-mode average diesel particulate matter reduction for the system consisting of the

particulate trap with a downstream oxidation catalyst was 67.7% (see Table 3 at the end of the Executive Summary). Considering, however, that the testing performed for this study was the first of its kind for the Rohmac/DCL system, it should be evident that further development work could produce enhanced particulate reduction values. Rohmac independently had the particulate sample filters analyzed for sulfate content and verbally disclosed, to WVU, that sulfates contributed approximately 50% of the total measured particulate mass. Particulate reduction results for all C240 engine-system configurations are presented in Figures 24 – 27. As the data indicates, the particulate reduction for the catalyst-trap (reverse order) tests ranged from 40 % to 99 %, with an average of 78 %. However, it should be noted that the catalyst only configuration yielded an average 66 % higher PM. Obviously such an increase in PM production indicates a substantial amount of collected sulfates. The trap-catalyst system reduced HC by 79 %, but Mode 5 produced minimal (27 %) reductions. Increased regeneration activity during Mode 5 is likely responsible for such sub-par reductions. The LPU-2 system reduced CO by an average of 95 %. As expected NO_x emissions were relatively unaffected by the addition of the system (6 % increase over baseline). HC reductions for the C240 catalyst-trap (reverse order) system averaged 87%, while CO was reduced by 94 %. NO_x emissions were basically unaffected by the addition of the reverse-configuration system (6 %) reduction. The catalyst-only tests reduced HC by an average of 72 % and CO by 93 %. However CO₂ and NO_x emissions were relatively unaffected by the addition of the oxidation catalyst.

6.4 Caterpillar 3306 Results

Two aftertreatment devices were tested on a Caterpillar 3306. A Dry Systems Technology (DST) dry scrubber system and a Clean Air Systems catalyzed particulate trap were evaluated for their exhaust emissions reduction capabilities. The results for the tests are presented in Figures 44 - 66 and in Appendix Tables B.3-1 - B.3-4 (in g/hr) and Tables C.3-1 - C.3-4 (in g/bhp-hr).

Goodman Equipment Corporation supplied WVU with a Caterpillar 3306 that they had retrofitted with a DST dry scrubber system. Based upon the previous experience that the PI has had with an MWM D916-6 DST system, the PM sample filters that were collected during the first eight-mode test (DST I) suggested that there was a problem with the system received from Goodman. Since the aforementioned MWMD916-6 DST system did contain the same oxidation catalyst as this CAT 3306 system, the catalyst was omitted in an attempt to isolate the source of the problem. Results from a 2-Mode test indicated that the catalyst was not the cause of high particulate emissions. WVU concluded that the coolant in the heat exchanger was leaking into the exhaust stream. After contacting Goodman representatives, the heat exchanger was removed for leak testing. A coolant leak, caused by manufacturing flaws, was indeed detected in the heat exchanger of the DST system (see Figures A.4-3 - A.4-5). In addition exhaust passage leaks were also found in the manifold end of the heat exchanger and the filter canister (see Figures A.4-2, A.4-6, and A.4-7). Goodman representatives and Mr. Norbert Paas (inventor of the DST system) performed subsequent repairs and inspections. At the onset of the second test, WVU's visual inspection of the

sample filters for Mode 1 and Mode 2 resulted in the elimination of four modes for the remainder of the test (only Modes 1, 2, 5, and 7 were tested). The results of this 4-mode test are presented in Figures and Appendix Tables as Dry Scrubber II. Immediately following this four-mode test, Goodman and Mr. Paas were contacted. WVU was instructed to accommodate an engine checkup by a local Caterpillar maintenance technician and various Goodman-required system inspections and clean-up procedures. The results of the engine tune-up and inspection are outlined in a letter authored by Toni Bilitski (Goodman), which can be found in Appendix E. The various engine- and system-related modifications and procedures that were ordered by Goodman and Mr. Paas are also included in Appendix E. The Commission-requested release-letter confirming that the engine and the DST were ready for testing was not received until after the Caterpillar 3306 DST system was tested for a third time. The release letter is found in Appendix E, while the results of this complete 8-mode test are presented in the Figures and in the Appendix tables as DST III. Once again, the reductions from this system were rather low under high speed/high load (Mode 1, in particular) conditions.

The original DST 8-Mode indicated a weighted-average particulate reduction of 41.2 % (see Table 4a at the end of the Executive Summary). After the leak was repaired, only 4 Modes were tested, with an average reduction of 70 %. However, similar to the results found during the first 8-Mode test, Modes 1 and 2 had much lower reductions than Modes 5 and 7. During the second full 8-Mode test (DST III) the weighted-average reduction was 82 %, but Mode 1 only posted an 8 % reduction (see Table 4b).

From the DST I results, Mode 8 produced large increases in HC and CO over the bare engine values. Omitting this mode resulted in average reductions of 56 % for HC and 89 % for CO. CO₂ and NO_x emissions were not substantially affected by the addition of the DST system. The gaseous emissions from the limited 4-mode DST II tests indicated reductions of HC and CO emissions of 67 % and 92 %, respectively. As with the DST I tests, CO₂ and NO_x emissions were unaffected. The second complete 8-mode test (DST III) produced average HC reductions of 70 % and CO reductions of 85 %. For these tests, CO₂ emissions were reduced by 19 % and NO_x levels were decreased by 25 %. As a final note, Table 10 provides documentation of the exhaust temperature at the exit of the DST paper filter canister (immediately following the flame arrestor). Data presented in Table 10 was taken from the second 8-Mode test (DST III), since there were coolant leaks associated with the first set of tests. The high DST outlet temperatures in Modes 1 and 2 could explain the low PM reductions. Tests of filter efficiency, as a function of stream temperature and flow rates, were not conducted at WVU.

Clean Air Systems provided WVU with a catalyzed particulate filter that had been designed for the Caterpillar 3306. The results of the tests are given in Figures 44 – 61 and in Appendix Tables B.4-4 (in g/hr) and C.4-4 (in g/bhp-hr). The overall weighted-average particulate reduction of the system was 72 %. The average reductions in HC, CO, and CO₂ were found to be 88 %, 83 %, and 21 %, respectively. Oxides of Nitrogen (NO_x) were not substantially reduced by the Clean Air System. It should be noted that Mode 8 presented a significant problem with HC and CO emissions. As per regulations, Mode 8 testing followed Mode 7 after a period of stabilization (generally 10 minutes).

While following this standard procedure, HC and CO emissions would increase until both analyzers were out of range. In order to continue testing, the engine had to be shutdown so that the HC and CO analyzers could be purged. After startup, HC and CO emissions were still much greater than those obtained from other test modes, but there were measurable. This problem is attributed to a regeneration process that would be quenched during the shutdown period. Considering that this study serves as the first and only set of emissions tests for this particular system model, there is likely room for improvement. In addition, the particulate sample filters were not analyzed, but, based on previous experience, WVU would expect that a considerable amount of sulfates were contained on the filters. Thus, further development could minimize sulfate production and, hence, improve overall particulate reduction efficiency.

Observed Exhaust Temperatures after DST Flame Arrestor								
	Mode 1	Mode 2	Mode 3	Mode 4	Mode 5	Mode 6	Mode 7	Mode 8
Downstream Temperature	300	265.5	244	215	221	215	197.5	158.5

Table 10. Observed Exhaust Temperatures (in °F) after the DST Flame Arrestor during the Final 8-Mode Test (DST III).

7.0 RECOMMENDATIONS

The emissions tests performed under the WV Diesel Study have provided a solid starting point for the development and evaluation of diesel engine aftertreatment devices used in mining applications. Although there are systems currently operating in underground mines, in general there has been very little activity in this specialized field of engine emissions. In fact, with the exception of the DST system, the emissions tests performed on the exhaust aftertreatment devices associated with this study were the first of their kind. It would be very misleading to form lasting conclusions concerning the performance of any aftertreatment device based solely on initial results. The "first-round" performance of systems was very promising, and the participating manufacturers of this study deserve a great deal of commendation. However, further testing and refinement is obviously necessary in order to maximize each system's potential.

Further improvement in emissions reductions can be accomplished through increased research efforts. Advancements in catalyst formulation, improvements in trap selection and sizing, and reduction of base engine emissions should all be explored in order to optimize aftertreatment system performance. To date, the majority of the aftertreatment industry has not responded to the need for systems that accommodate the unique needs of mining-engines. Due to special design constraints and the limited demand in the current market, there are very few commercially available systems. Extensive testing is also required to both perfect current designs and provide additional insight for future systems. Development of oxidation catalysts and PM traps that tailor to the needs of mining-engine applications will obviously improve performance. Optimization tests of the integrated engine-aftertreatment system are very crucial to achieving high levels of emissions reductions. In addition to aftertreatment component enhancements, efforts must be made to improve the quality of engines used in underground mines. Until recently, manufacturers of in-mine engines did not have to comply with any well-defined emissions standards. This study has highlighted this critical area, and has raised points of interest that need to be addressed. Derating the LPU-2 engine, which was a direct result of this study, is a good example of what manufacturers can do to improve in-mine environments. Combined efforts by MSHA and engine manufacturers to improve current designs, while developing new ones, would provide the mining industry with a larger variety of certified, high-quality, low-emission engines.

In addition to these industry-specific contributions, limited deregulation could also improve the level of system performance. Relaxation of the 300° F surface-temperature requirement would increase the available options for trap regeneration. In doing so, the current trends involving use of noble metal-rich catalyst formulations, which lead to high sulfate formation at elevated temperatures, could be avoided. Alternative regeneration techniques could lower system costs, improve reliability, and eliminate sources of additional health concerns.

Looking forward, WVU intends to continue testing and developing emission-reduction strategies specifically aimed at mining applications. With the help of industry, labor, and the WV Diesel Commission, WVU hopes to proceed with the research program initiated by this study. It is anticipated that an integration of such key industry factions will not only result in improved system designs, but an evolutionary pattern in the development of both State and Federal emissions standards. Additional research will generate interest and improve the demand for high-efficiency aftertreatment systems. WVU's continued involvement will also serve as a vital resource for the governing bodies that are responsible for developing in-mine emissions standards. Advanced research will provide significant contributions to the existing database for mining-engine emissions and assist in the development of improved test protocols and procedures. As part of the future research program, WVU recommends that in-use (in-mine) diesel equipment be instrumented to collect data during everyday operations. Not only could data such as exhaust temperatures, pressures and emission levels be recorded, but engine speed and load could be monitored – parameters that are crucial to the development of duty cycles and test procedures that are used in laboratory testing. This will assist in optimizing the design of aftertreatment devices for underground mining applications.

Figure 2. Comparison of Particulate Mass Emission Rates from MWM D916-6 Using Low Sulfur and High Sulfur Diesel No. 2 Fuel

Figure 3. Comparison of Hydrocarbon Mass Emission Rates from MWM D916-6 Using Low Sulfur and High Sulfur Diesel No. 2 Fuel

Figure 4. Comparison of Carbon-Monoxide Mass Emission Rates from MWM D916-6 Using Low Sulfur and High Sulfur Diesel No. 2 Fuel

Figure 5. Comparison of Carbon Dioxide Mass Emission Rates from MWM D916-6 Using Low Sulfur and High Sulfur Diesel No. 2 Fuel

Figure 6. Comparison of Nitrogen Oxides Mass Emission Rates from MWM D916-6 Using Low Sulfur and High Sulfur Diesel No. 2 Fuel

Figure 7. Comparison of Particulate Mass Emission Rates from LPU-2: Mode 7

Figure 8. Comparison of Particulate Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 9. Comparison of Particulate Mass Emission Rates from LPU. 2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 10. Comparison of Particulate Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 11. Comparison of Particulate Mass Emission Rates from LPU-2: Bare Engine and DCL Catalyst Equipped Engine

Figure 12. Comparison of Hydrocarbon Mass Emission Rates from LPU-2 on Mode 7: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 13. Comparison of Hydrocarbon Mass Emission Rates from LPU-2: Bare Engine and DCL System Equipped Engine

Figure 14. Comparison of Hydrocarbon Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 15. Comparison of Carbon Monoxide Mass Emission Rates from LPU-2 on Mode 7: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 16. Comparison of Carbon-Monoxide Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 17. Comparison of Carbon-Monoxide Mass Emission Rates from LPU-2: Bare Engine and DCL System Equipped Engine

Figure 18. Comparison of Carbon-Monoxide Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 19. Comparison of Carbon-Monoxide Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 20. Comparison of Nitrogen Oxides Mass Emission Rates from LPU-2 on Mode 7: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 21. Comparison of Nitrogen Oxides Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 22. Comparison of Nitrogen Oxides Mass Emission Rates from LPU-2: Bare Engine and DCL System Equipped Engine

Figure 23. Comparison of Nitrogen Oxides Mass Emission Rates from LPU-2: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 24. Comparison of Particulate Mass Emission Rates from Isuzu C240: Bare Engine, Rohmac/DCL System and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 25. Comparison of Particulate Mass Emission Rates from Isuzu C240: Bare Engine and DCL Catalyst Equipped Engine

Figure 26. Comparison of Particulate Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 27. Comparison of Particulate Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 28. Comparison of Hydrocarbon Mass Emission Rates from Isuzu C240: Bare Engine, Rohmac/DCL System and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 29. Comparison of Hydrocarbon Mass Emission Rates from Isuzu C240: Bare Engine and DCL Catalyst Equipped Engine

Figure 30. Comparison of Hydrocarbon Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 31. Comparison of Hydrocarbon Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 32. Comparison of Carbon-Monoxide Mass Emission Rates from Isuzu C240: Bare Engine, Rohmac/DCL System and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 33. Comparison of Carbon-Monoxide Mass Emission Rates from Isuzu C240: Bare Engine and DCL Catalyst System Equipped Engine

Figure 34. Comparison of Carbon-Monoxide Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 35. Comparison of Carbon-Monoxide Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 36. Comparison of Carbon Dioxide Mass Emission Rates from Isuzu C240: Bare Engine, Rohmac/DCL System and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 37. Comparison of Carbon Dioxide Mass Emission Rates from Isuzu C240: Bare Engine and DCL Catalyst System Equipped Engine

Figure 38. Comparison of Carbon Dioxide Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 39. Comparison of Carbon Dioxide Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 40. Comparison of Oxides of Nitrogen Mass Emission Rates from Isuzu C240: Bare Engine, Rohmac/DCL System and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 41. Comparison of Oxides of Nitrogen Mass Emission Rates from Isuzu C240: Bare Engine and DCL Catalyst System Equipped Engine

Figure 42. Comparison of Oxides of Nitrogen Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System Equipped Engine

Figure 43. Comparison of Oxides of Nitrogen Mass Emission Rates from Isuzu C240: Bare Engine and Rohmac/DCL System (Reverse Order) Equipped Engine

Figure 44. Comparison of Particulate Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)*, and Clean Air Systems Catalyzed Trap

Figure 45. Comparison of Particulate Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)*, and Clean Air Systems Catalyzed Trap

Figure 46. Comparison of Hydrocarbon Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 47. Comparison of Hydrocarbon Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 48. Comparison of Carbon-Monoxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 49. Comparison of Carbon-Monoxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 50. Comparison of Carbon Dioxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 51. Comparison of Oxides of Nitrogen Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 52. Comparison of Oxides of Nitrogen Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 53. Comparison of Particulate Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)*, and Clean Air Systems Catalyzed Trap

Figure 54. Comparison of Particulate Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)*, and Clean Air Systems Catalyzed Trap

Figure 55. Comparison of Hydrocarbon Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 56. Comparison of Hydrocarbon Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 57. Comparison of Carbon-Monoxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 58. Comparison of Carbon-Monoxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 59. Comparison of Carbon-Monoxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 60. Comparison of Carbon Dioxide Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 61. Comparison of Oxides of Nitrogen Mass Emission Rates from Caterpillar 3306: Bare Engine, DST System(s)* and Clean Air Systems Catalyzed Trap

Figure 62. Comparison of Particulate Mass Emission Rates from Caterpillar 3306: DSTIII System

Figure 63. Comparison of Hydrocarbon Mass Emission Rate from Caterpillar 3306: DSTIII System

Figure 64. Comparison of Carbon-Monoxide Mass Emission Rate from Caterpillar 3306: DSTIII System

Figure 65. Comparison of Carbon Dioxide Emission Rates from Caterpillar 3306: DSTIII System

Figure 66. Comparison of Nitrogen Oxides Mass Emission Rates from Caterpillar 3306: Bare Engine and DST III System

LITERATURE CITED

- Abdul-Khalek, I.S., Kittelson, D.B., Graskow, B.R., and Wei, Q., (1998), "Diesel Exhaust Particle Size: Measurement Issues and Trends", SAE 980525
- Bagley, S. T., Baumgard, K. J., Gratz, L. D., Johnson, J. H. and Leddy, D. G., (1996), "Characterization of Fuel and Aftertreatment Device Effects on Diesel Emissions," Health Effects Institute, Research Report Number 76.
- Braun, CH., Ackermann, U., Schwartz, J., Gnehm, H.P., Rutishauser, M., and Wanner, H.U., "Air Pollution and Respiratory Symptoms in Pre-School Children", Am. Rev., Respir., Vol. 145, pp. 42-47, 1992.
- California Environmental Protection Agency, (1998), "Health Risk Assessment for Diesel Exhaust. Public and Scientific Review Panel Review Draft", Office of Environmental Health Hazard Assessment, Sacramento, CA.
- Chasey, T.D., (1992), "Design and Development of Data Acquisition and Control System Hardware and Software for Transportable Emissions Testing Laboratory", M.S. Thesis, Department of Mechanical and Aerospace Engineering, West Virginia University, Morgantown, WV.
- Cohen, A.J. and Higgins, M.W.P, (1995), "Health Effects of Diesel Exhaust: Epidemiology. In: Diesel Exhaust: A Critical Analysis of Emissions, Exposure, and Health Effects (A Special Report of the Institutes's Diesel Working Group), pp. 125-137. Health Effects Institute, Cambridge, MA.
- Dockery, D.W., Pope, W.A., Xu, Z., Spengler, J.D., Ware, J.H., Fay, M.E., Ferris, B.G., and Speizer, F.E., (1993), "An Association between Air Pollution and Morbidity in six U.S. Cities", New Engl. J. Med., Vol. 329, pp 1753-1759.
- Donaldson, K., (1994), "The Effect of Ultrafine Titanium Dioxide on Epithelial cells", Meeting of Aerosol Soc., Birmingham.
- Health Effects Institute (1995), "Diesel Exhaust: A Critical Analysis of Emissions, Exposure, and Health Effects (A Special Report of the Institutes's Diesel Working Group), pp. 125-137. Health Effects Institute, Cambridge, MA.
- Heinein, N.A. and Patterson, D.J., (1972), "Emissions and Combustion Engines", Ann Arbor Science Publishers, Inc.
- International Agency for Research on Cancer, (1989), "Diesel and Gasoline Engine Exhaust and some Nitroarenes", IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Vol. 46, Lyon, France.

Iwal, K., Udagawa, T., Yamagishi, M. and Yamada, H., "Long-Term Inhalation Studies of Diesel Exhaust on F344 SPF Rats," Proc. Int'l Satellite Symp. On Toxicological Effects of Emissions from Diesel Engines, Elsevier Sci. Pub., N. Y., pp. 349-360, 1986

Kao, K. S. and Friedlander, S. K., (1995), "Frequency Distribution of PM₁₀ Chemical Components and their Sources," Enviro. Sci. Technol., Vol. 29, pp. 198-199.

Kreyling, W.G., (1994) "Is The Mass Concentration of Particulate Air Pollution The Appropriate Parameter for Respiratory Health Effects?", Zbl. Hyg., Vol. 159, pp. 198-199.

Mauderly, J. L., Jones, R. K., McClellan, R. O., Henderson, R. F. and Griffith, W. C., "Carcinogenicity of Diesel Exhaust Inhaled Chronically by Rats," Proceedings of the Int'l Satellite Symp. on Toxicological Effects of Emissions from Diesel Engine, Elsevier Sci Publ., N. Y., pp. 397-409, 1986

Mauderly, J.H., Griffith, G.C., Henderson, R.F., Jones, R.K., McClellan, R.O., (1991), "Evidence from Animal Studies for the Carcinogenicity of Inhaled Diesel Exhaust", pp. 1-13, In: Nitro-Arenes (ed. PC Howard et al.), Plenum Press, New York.

Mayer, A. (1998), "VERT: Curtailing Emissions of Diesel Engines in Tunnel Sites", VERT Report W11/1297. TTM, Switzerland.

McClellan, R. O., "Health Effects of Diesel Exhaust: A Case Study in Risk Assessment," Am. Ind. Hyg. Assoc. J., Vol. 3, pp. 332, 1986

Monn, C. H., Braendli, O., Schaeppi, G., Schindler, C., Ackermann-Liebrich, U., Leuenberger, P. and Spaldia Team, (1995), "Particulate Matter < 10 μ m (PM₁₀) and Total Suspended Particulates (TSP) in Urban, Rural and Alpine Air in Switzerland," Atmospheric Environment, Vol. 29, No. 19. pp. 2565-2573. 1995

National Institute for Occupational Safety and Health. (1988). "Carcinogenic Effects of the Exposure to Diesel Exhaust", Current Intelligence Bulletin 50, Department of Human Health and Services. NIOSH Publication No. 88-116.

NESCAUM, (1997) "Heavy Duty Engine Emissions in the Northeast States for Coordinated Air Use Management," Boston, Mass.

Pataky, G.M., Baumgard, K.J., Gratz, L.D., Bagley, S.T., Leddy, D.G., Johnson, J.H., Effects of an Oxidation Catalytic Converter on Regulated and Unregulated Diesel Emissions", SAE Paper 940243.

Pei, Yao, (1993), "Development of Software for the Heavy-Duty Engine Testing at Engine Research Center, West Virginia University", M.S. Thesis, Department of Mechanical and Aerospace Engineering, West Virginia University, Morgantown, WV.

Pope, C.A., and Dockery, D.W., (1992), "Acute Health Effects of PM Pollution on Symptomatic and Asymptomatic Children", Am. Rev. Respir. Dis., Vol. 145, pp. 1123-1128.

Reschke, G.D., (1977), "Optimization of a Flame Ionization Detector for Determination of Hydrocarbon in Diluted Automotive Exhausts", SAE 770141.

Smith II, R.C., (1993), "Comparison of Heavy-Duty Diesel Engine Transient Emissions Measurements Using a Mini- and a Full-flow Dilution Tunnel", M.S. Thesis, Department of Mechanical and Aerospace Engineering, West Virginia University, Morgantown, WV

Smith, R.E. Jr., and Matz, R.J., (1962), "A Theoretical Method of Determining Discharge Coefficients for Venturis Operating at Critical Flow Conditions", Journal of Basic Science, pp. 434-446.

U.S. Environmental Protection Agency, (1998), "Health Assessment Document for Diesel Emission" SAB Review Draft. EPA/600/8-90/057C. Off. of Res. & Dev., Wash. D.C.

VERT Project, (1998), "VERT: Curtailing Emissions of Diesel Engines in Tunnel Sites", A. Mayer, VERT Report W11/1297. TTM, Switzerland.

Wallace WE, Keane MJ, Vallyathan V, Ong TM, Castranova V, "Pulmonary Surfactant Interaction with Respirable Dust", Proceedings: 1984 Coal Mine Dust Conference, pp. 180-186, NTIS Report #PB86 169380/AS (1986).

Wallace WE, Keane M, Xing S, Harrison J, Gautam M, Ong T, "Mutagenicity of Diesel Exhaust Soot Dispersed in Phospholipid Surfactants", In "Environmental Hygiene II", pp. 7-10; Eds. NH Seemayer and W Hadnagy, Springer Verlag, Berlin, ISBN 0-387-52735-4 (1990).

Appendix A

**Figure A.1-1. MWM D916-6 on an Eddy Current
Dynamometer Test Bed**

Figure A.2-1 LPU-2 Engine with Rohmac/DCL Control System
(Side View)

Figure A.2-2. LPU-2 Engine with Rohmac/DCL Control System (End View)

Figure A.2-3 Lister Petter LPU-2 Engine with Rohmac/DCL DPM Control System on a Water Brake Dynamometer Test Bed

Figure A.2-4 Downstream Face of the Rohmac/DCL Catalyst Prior to Regeneration.

Figure A.2-5 Upstream Face of the Rohmac/DCL Trap Prior to Regeneration

Figure A.2-6 Downstream Face of the Rohmac/DCL Trap Prior to Regeneration

Figure A.2-7 Rohmac/DCL Trap-Catalyst Assembly for the LPU-2 System Prior to Regeneration

Figure A.2-8 Rohmac/DCL Trap-Catalyst Assembly for the LPU-2 System Following Regeneration

Figure A.3-1 Isuzu C240 with Rohmac/DCL Catalyst-Trap System (Reverse Order Configuration)

Figure A.4-1 Caterpillar 3306 with DST on an Eddy-Current
Dynamometer Test Bed

Figure A.4-2 End View of the DST Heat Exchanger
(Taken During the Repairs of the Coolant Leak)

Figure A.4-3. Manifold Section of the DST Heat Exchanger
During the Repair Process
(Note Coolant Leaking From Cracks Between Mounting Holes)

Figure A.4-4 Manifold Section of the DST Heat Exchanger During the Repair Process
(Note the Crack Between the Mounting Holes)

Figure A.4-5 Internal End View of the DST Filter Canister
(Taken Following the Detection of Coolant Leak)

Figure A.4-6 DST Heat Exchanger During the Repair Process
(Note Evidence of Exhaust Leak Between High and Low
Temperature Streams)

Figure A.4-7 Manifold-Body Gasket From the DST
Heat Exchanger During the Repair Process
(Note Evidence of Exhaust Leak Between High and
Low Temperature Streams)

Figure A.4-8 Caterpillar 3306 with Clean Air Systems Trap (End View)

Figure A.4-9 Caterpillar 3306 with Clean Air Systems Trap (Side View)

Figure A.4-10 Insulated Clean Air Systems Catalyzed Trap

Appendix B

Emissions Data for MWM D916-6 with Low-sulfur (0.05%) Fuel (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	24.756	23.28	23.304	23.780
HC	3.72	4.08	3.24	3.680
CO	52.56	51.12	50.52	51.400
CO2	40092.6	37594.68	39143.88	38943.72
Nox	247.56	251.04	248.4	249.000

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	20.424	20.592	20.472	20.496
HC	5.76	4.92	4.68	5.120
CO	44.04	46.2	45.24	45.160
CO2	34315.44	34670.4	34489.8	34491.88
Nox	249.72	251.28	252.96	251.320

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	19.716	18.576	17.628	18.640
HC	4.8	4.56	4.44	4.600
CO	32.28	30.72	33.84	32.280
CO2	26066.16	25849.56	25610.4	25842.04
Nox	231.48	229.32	228.72	229.840

Mode 4				
	Test 1	Test 2	Test 3	AVG
PM	10.632	10.596	11.232	10.820
HC	2.16	2.16	2.52	2.280
CO	29.76	30.24	31.2	30.400
CO2	14191.08	14169.48	14315.4	14225.32
Nox	121.2	117.24	118.68	119.040

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	24.048	22.884	22.2	23.044
HC	2.16	2.28	1.8	2.080
CO	37.32	35.4	35.52	36.080
CO2	29745.24	29440.8	29190.84	29458.96
Nox	195.84	146.64	198.48	180.320

Mode 6				
	Test 1	Test 2	Test 3	AVG
PM	16.488	16.848	16.872	16.736
HC	2.4	2.52	2.4	2.440
CO	31.2	30.36	29.88	30.480
CO2	24414	24605.88	24289.92	24436.60
Nox	200.52	4.8	137.88	114.400

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	13.704	14.832	14.868	14.468
HC	2.28	3	3.12	2.800
CO	26.76	29.76	30.48	29.000
CO2	18239.28	18194.88	18224.4	18219.52
Nox	186.96	185.4	184.44	185.600

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	1.368	1.902	3.366	2.212
HC			0.42	0.420
CO	8.58	8.82	9	8.800
CO2	2649.72	2595.96	2541.9	2595.860
Nox	32.88	31.5	30.12	31.500

Emissions Data for MWM D916-6 with High-sulfur (0.25%) Fuel (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	33.528	33.84	29.628	32.332
HC	3.48	3.48	3.24	3.400
CO	51.12	52.44	51.96	51.840
CO2	44178.6	42818.64	43093.2	43363.48
Nox	255.6	255.12	256.68	255.800

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	25.26	25.128	25.752	25.380
HC	5.28	5.16	4.92	5.120
CO	44.4	41.52	44.16	43.360
CO2	35865	35823	36107.16	35931.72
Nox	234.24	232.92	232.44	233.200

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	21.588	20.964	20.712	21.088
HC	5.28	4.68	5.4	5.120
CO	28.92	29.52	30.48	29.640
CO2	26761.8	27064.68	26566.2	26797.56
Nox	218.16	219.48	218.04	218.560

Mode 4				
	Test 1	Test 2	Test 3	AVG
PM	13.596	14.22	14.364	14.060
HC	2.28	2.88	3.00	2.720
CO	30.72	33.36	34.08	32.720
CO2	14856.12	14707.08	14779.92	14781.04
Nox	118.92	116.76	117.24	117.640

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	31.56	29.568	27.96	29.696
HC	1.56	1.68	2.16	1.800
CO	33.84	31.56	31.08	32.160
CO2	31528.08	31080	30822.36	31143.48
Nox	185.4	179.88	184.2	183.160

Mode 6				
	Test 1	Test 2	Test 3	AVG
PM	20.208	23.268	22.092	21.856
HC	2.88	3.12	3.00	3.000
CO	26.64	27.6	26.88	27.040
CO2	25705.08	25681.08	25618.44	25668.20
Nox	189.96	188.04	187.8	188.600

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	16.536	17.352	17.46	17.116
HC	3.36	3.72	3.48	3.520
CO	23.4	27.6	25.92	25.640
CO2	18835.92	18976.08	18957.48	18923.16
Nox	176.64	177.6	175.68	176.640

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	4.578	5.814	5.526	5.306
HC	0.3	0.54	0.72	0.520
CO	8.22	12.3	15.06	11.860
CO2	2850.96	2784.6	2791.86	2809.140
Nox	24.18	22.56	22.98	23.240

Emissions Data for Lister Petter LPU-2 bare engine (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	109.464	102.612	100.128	104.068
HC	4.92	2.16	1.56	2.880
CO	799.44	653.88	613.68	689.000
CO2	16479.96	16582.32	16366.68	16476.32
Nox	31.44	32.04	32.04	31.840
Exh Temp	1457	1775	1792	1674.667

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	4.1925	3.744	3.432	3.790
HC	6.975	7.2	6.36	6.845
CO	18.75	18	17.28	18.010
CO2	11016.6	10783.8	10859.16	10886.52
Nox	51.225	51.36	51.96	51.515
Exh Temp	915	903	898	905.333

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	3.168	3.36	3.096	3.208
HC	12.72	14.28	12.36	13.120
CO	15.72	18.24	15.36	16.440
CO2	9048	9102.48	9168.12	9106.200
Nox	50.88	51.24	51.72	51.280
Exh Temp	748	747	748	747.667

Mode 4			
	Test 1	Test 2	AVG
PM	4.548	3.66	4.104
HC	6.96	4.92	5.940
CO	17.52	13.68	15.600
CO2	7016.28	7017.6	7016.940
Nox	40.44	40.56	40.500
Exh Temp	583	578	580.500

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	109.044	108.876	109.392	109.104
HC	17.52	16.8	17.04	17.120
CO	472.92	452.64	456.6	460.720
CO2	11580.48	11390.04	11270.16	11413.56
Nox	23.28	22.44	21.72	22.480
Exh Temp	1138	1162	1233	1177.667

Mode 6						
	Test 1	Test 2	Test 3	Test 4	Test 5	AVG
PM	5.388	6.78	5.532	6	5.508	5.842
HC	10.68	10.56	8.52	4.56	4.2	7.704
CO	36.24	36.12	35.04	27.72	27.72	32.568
CO2	8105.28	8010.12	7881.6	7467.72	7509.72	7794.888
Nox	58.32	50.16	48.12	40.68	40.92	47.640
Exh Temp	1349	1483	1810	1526	1560	1545.600

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	2.508	2.976	3.1575	2.881
HC	24.84	23.4	24	24.080
CO	46.44	44.64	46.2	45.760
CO2	6033.96	5989.8	5952.675	5992.145
Nox	56.52	53.88	54.525	54.975
Exh Temp	567	567	569	567.667

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	0.168	0.15	0.138	0.152
HC	0.24	0.12	0.12	0.160
CO	1.44	1.5	1.08	1.340
CO2	1297.26	1267.44	1252.08	1272.260
Nox	31.56	32.46	33.24	32.420
Exh Temp	269	231	227	242.333

Emissions Data for Lister Petter LPU-2 with failed trap (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	38.712	34.836	36.774
HC	0.12	0.06	0.090
CO	2.34	2.94	2.640
CO2	8614.26	8643.54	8628.900
Nox	16.32	16.56	16.440
Exh Temp	1452	1459	1455.500

Mode 2			
	Test 1	Test 2	AVG
PM	2.094	4.35	3.222
HC	0.06	0.15	0.105
CO	0.3	1.5	0.900
CO2	5985.72	11776.28	8880.998
Nox	24.6	48	36.300
Exh Temp	940	937	938.500

Mode 3			
	Test 1	Test 2	AVG
PM	2.19	2.505	2.348
HC	0.3	0.3	0.300
CO	1.5	1.35	1.425
CO2	9931.5	9856.125	9893.813
Nox	48.825	48.975	48.900
Exh Temp	931	763	847.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.816	0.978	0.897
HC	0.24		0.240
CO	2.04	0.6	1.320
CO2	7688.4	7647.84	7668.120
Nox	37.74	37.68	37.710
Exh Temp	596	593	594.500

Mode 5			
	Test 1	Test 2	AVG
PM	34.962	37.698	36.330
HC	0.06	0.12	0.090
CO	0.6	0.72	0.660
CO2	5920.8	5902.2	5911.500
Nox	12.48	12.24	12.360
Exh Temp	1208	1217	1212.500

Mode 6			
	Test 1	Test 2	AVG
PM	1.674	1.65	1.662
HC	0.48	0.3	0.390
CO	0.24	0.96	0.600
CO2	4311.3	4270.86	4291.080
Nox	19.68	20.28	19.980
Exh Temp	827	824	825.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.39	0.342	0.366
HC	1.02	0.96	0.990
CO	0.66	0.42	0.540
CO2	3224.1	3213.96	3219.030
Nox	25.74	25.92	25.830
Exh Temp	602	592	597.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.054	0.084	0.069
HC	0	0	0.000
CO		0.72	0.720
CO2	1290.84	1353.18	1322.010
Nox	27.48	28.5	27.990
Exh Temp	281	248	264.500

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/hr)

Mode 6						
	Test 1	Test 2	Test 3	Test 4	Test 5	AVG
PM	5.388	6.78	5.532	6	5.508	5.842
HC	10.68	10.56	8.52	4.56	4.2	7.704
CO	36.24	36.12	35.04	27.72	27.72	32.568
CO ₂	8105.28	8010.12	7881.6	7467.72	7509.72	7794.888
Nox	58.32	50.16	48.12	40.68	40.92	47.640
Ex. Temp	1349	1483	1810	1526	1560	1545.600

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	2.508	2.976	3.1575	2.881
HC	24.84	23.4	24	24.080
CO	46.44	44.64	46.2	45.760
CO ₂	6033.96	5989.8	5952.675	5992.145
Nox	56.52	53.88	54.525	54.975
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	109.464	102.612	100.128	104.068
HC	4.92	2.16	1.56	2.880
CO	799.44	653.88	613.68	689.000
CO ₂	16479.96	16582.32	16366.68	16476.32
Nox	31.44	32.04	32.04	31.840
Ex. Temp	1457	1775	1792	1674.667

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	109.044	108.876	109.392	109.104
HC	17.52	16.8	17.04	17.120
CO	472.92	452.64	456.6	460.720
CO ₂	11580.48	11390.04	11270.16	11413.56
Nox	23.28	22.44	21.72	22.480
Ex. Temp	1138	1162	1233	1177.667

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	2.508	2.976	3.1575	2.881
HC	24.84	23.4	24	24.080
CO	46.44	44.64	46.2	45.760
CO ₂	6033.96	5989.8	5952.675	5992.145
Nox	56.52	53.88	54.525	54.975
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/hr)

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	2.508	2.976	3.1575	2.881
HC	24.84	23.4	24	24.080
CO	46.44	44.64	46.2	45.760
CO ₂	6033.96	5989.8	5952.675	5992.145
Nox	56.52	53.88	54.525	54.975
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with new trap (in g/hr)

Mode 6			
	Test 1	Test 2	AVG
PM	0.978	1.182	1.080
HC	0	0	0.000
CO	0.78	0.54	0.660
CO ₂	8205.18	8042.34	8123.760
Nox	36.66	37.38	37.020
Ex. Temp	806	807	806.500

Mode 7			
	Test 1	Test 2	AVG
PM	1.05	0.24	0.645
HC	0.06	0	0.030
CO	0.84	0.9	0.870
CO ₂	6597.84	6546.24	6572.040
Nox	44.34	45	44.670
Ex. Temp	593	597	595.000

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with oxidation catalyst only (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	60.06	67.146	63.603
HC	1.44	1.2	1.320
CO	262.74	260.64	261.690
CO ₂	7997.88	7956.42	7977.150
Nox	7.08	5.82	6.450
Ex. Temp	1351	1389	1370.000

Mode 5			
	Test 1	Test 2	AVG
PM	54.828	55.662	55.245
HC	0.24	0.3	0.270
CO	0.96	1.08	1.020
CO ₂	5648.52	5607.42	5627.970
Nox	12.84	12.3	12.570
Ex. Temp	1203	1205	1204.000

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	2.874	1.128	1.056	1.686
HC	1.32	1.32	1.38	1.340
CO	0.42	0.36	0.12	0.300
CO ₂	3136.32	3115.14	3102.42	3117.960
Nox	24.66	25.02	25.32	25.000
Ex. Temp	622	601	597	606.667

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with new trap and Pallflex paper filter (in g/hr)

Mode 7			
	Test 1	Test 2	AVG
PM	0.222	0.042	0.132
HC	2.1	2.16	2.130
CO	0.6	0.84	0.720
CO ₂	5528.76	5396.64	5462.700
Nox	38.64	39.78	39.210
Ex. Temp	616	609	612.500

Emissions Data for Isuzu C240 bare engine (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	11.7	11.124	11.412
HC	4.56	6.12	5.340
CO	41.64	51.48	46.560
CO2	36463.8	36823.68	36643.74
Nox	194.76	189.6	192.180
Ex. Temp	1065	1077	1071.000

Mode 2			
	Test 1	Test 2	AVG
PM	10.344	10.188	10.266
HC	6	5.52	5.760
CO	46.8	45.48	46.140
CO2	29094.48	29156.88	29125.68
Nox	216.36	219	217.680
Ex. Temp	828	825	826.500

Mode 3			
	Test 1	Test 2	AVG
PM	9.833	10.704	10.269
HC	49.05	55.68	52.365
CO	32.175	37.08	34.628
CO2	21905.48	21872.4	21888.94
Nox	200.4	209.4	204.900
Ex. Temp	646	646	646.000

Mode 4			
	Test 1	Test 2	AVG
PM	11.27	11.85	11.560
HC	5.4	5.85	5.625
CO	23.5	23.175	23.338
CO2	13960.9	13992.98	13976.94
Nox	118	121.875	119.938
Ex. Temp	444	444	444.000

Mode 5			
	Test 1	Test 2	AVG
PM	34.392	35.076	34.734
HC	0.48	0.24	0.360
CO	111.6	110.4	111.000
CO2	24669.48	24595.2	24632.34
Nox	73.08	68.88	70.980
Ex. Temp	1092	1093	1092.500

Mode 6			
	Test 1	Test 2	AVG
PM	3.864	3.792	3.828
HC	1.44	0.72	1.080
CO	14.16	5.76	9.960
CO2	17282.76	6799.68	12041.22
Nox	91.08	35.76	63.420
Ex. Temp	758	750	754.000

Mode 7			
	Test 1	Test 2	AVG
PM	3.348	3.128	3.238
HC	3.24	3.6	3.420
CO	15	15.825	15.413
CO2	12440.28	12569.33	12504.8
Nox	97.68	93.3	95.490
Ex. Temp	542	546	544.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.222	0.264	0.243
HC	0.66	0.72	0.690
CO	14.58	13.44	14.010
CO2	1691.22	1668.12	1679.670
Nox	12.78	12.06	12.420
Ex. Temp	198	189	193.500

Emissions Data for Isuzu C240 with Trap and Oxidation Catalyst (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	9.822	9.338	9.580
HC	0.674298	0.525	0.600
CO		0.9	0.900
CO2	37554.63	37134.6	37344.62
Nox	193.6733	195.825	194.749
Ex. Temp	1199	1195	1197.000

Mode 2			
	Test 1	Test 2	AVG
PM	1.695	6.03	3.863
HC	0.675	0.675	0.675
CO	0		0.000
CO2	29320.8	29292.6	29306.7
Nox	231.3	230.1	230.700
Ex. Temp	917	921	919.000

Mode 3			
	Test 1	Test 2	AVG
PM	0.96	2.7	1.830
HC	0.45	0.45	0.450
CO	0.825	0.675	0.750
CO2	22842.68	22885.43	22864.05
Nox	206.4	200.625	203.513
Ex. Temp	697	699	698.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.06	0.1125	0.086
HC	0.3	0.375	0.338
CO	1.575	1.575	1.575
CO2	14365.2	14401.2	14383.2
Nox	103.2	95.7	99.450
Ex. Temp	482	485	483.500

Mode 5			
	Test 1	Test 2	AVG
PM	11.828	7.335	9.582
HC	0.225	0.3	0.263
CO	1.35	1.8	1.575
CO2	25221	25035.98	25128.49
Nox	68.625	65.925	67.275
Ex. Temp	1261	1275	1268.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.1575	0.12	0.139
HC	0.225	0.3	0.263
CO	0.225	0.15	0.188
CO2	18020.4	18053.55	18036.98
Nox	86.775	88.8	87.788
Ex. Temp	867	860	863.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.0675	0.09	0.079
HC	0.375	0.45	0.413
CO	1.125	0.375	0.750
CO2	13147.28	13172.93	13160.1
Nox	83.775	85.65	84.713
Ex. Temp	622	618	620.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.03	0.0225	0.026
HC	0.075	0.225	0.150
CO	0.15	4.8	2.475
CO2	1821.525	1794	1807.763
Nox	17.475	15.6	16.538
Ex. Temp	233	223	228.000

Emissions Data for Isuzu C240 bare engine (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	11.7	11.124	11.412
HC	4.56	6.12	5.340
CO	41.64	51.48	46.560
CO2	36463.8	36823.68	36643.74
Nox	194.76	189.6	192.180
Ex. Temp	1065	1077	1071.000

Mode 3			
	Test 1	Test 2	AVG
PM	9.833	10.704	10.269
HC	49.05	55.68	52.365
CO	32.175	37.08	34.628
CO2	21905.48	21872.4	21888.94
Nox	200.4	209.4	204.900
Ex. Temp	646	646	646.000

Mode 5			
	Test 1	Test 2	AVG
PM	34.392	35.076	34.734
HC	0.48	0.24	0.360
CO	111.6	110.4	111.000
CO2	24669.48	24595.2	24632.34
Nox	73.08	68.88	70.980
Ex. Temp	1092	1093	1092.500

Mode 7			
	Test 1	Test 2	AVG
PM	3.348	3.128	3.238
HC	3.24	3.6	3.420
CO	15	15.825	15.413
CO2	12440.28	12569.33	12504.8
Nox	97.68	93.3	95.490
Ex. Temp	542	546	544.000

Emissions Data for Isuzu C240 bare engine (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	11.7	11.124	11.412
HC	4.56	6.12	5.340
CO	41.64	51.48	46.560
CO2	36463.8	36823.68	36643.74
Nox	194.76	189.6	192.180
Ex. Temp	1065	1077	1071.000

Mode 5			
	Test 1	Test 2	AVG
PM	34.392	35.076	34.734
HC	0.48	0.24	0.360
CO	111.6	110.4	111.000
CO2	24669.48	24595.2	24632.34
Nox	73.08	68.88	70.980
Ex. Temp	1092	1093	1092.500

Emissions Data for Isuzu C240 with Oxidation Catalyst and Trap (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	6.9075	6.7425	6.825
HC	0.45	0.375	0.413
CO	3.3	0.825	2.063
CO2	39984.68	40076.93	40030.8
Nox	195.75	183.45	189.600
Ex. Temp	1193	1206	1199.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.705	0.84	0.773
HC	0.225	0.075	0.150
CO	2.7	1.65	2.175
CO2	22345.28	22137.15	22241.21
Nox	200.025	187.65	193.838
Ex. Temp	706	708	707.000

Mode 5			
	Test 1	Test 2	AVG
PM	7.395	6.84	7.118
HC	0.075		0.075
CO	1.575	1.05	1.313
CO2	23712.6	23642.63	23677.61
Nox	71.475	69.075	70.275
Ex. Temp	1184	1181	1182.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.0375	0.045	0.041
HC	0.075	0.075	0.075
CO	1.65		1.650
CO2	12872.25	12657.38	12764.81
Nox	77.025	78.975	78.000
Ex. Temp	613	605	609.000

Emissions Data for Isuzu C240 with Oxidation Catalyst only (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	19.788	19.512	19.650
HC	0.36	1.08	0.720
CO	4.08	3.96	4.020
CO2	36590.88	36981.6	36786.24
Nox	186.72	186.6	186.660
Ex. Temp	1065	1183	1124.000

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	53.676	53.172	58.524	55.124
HC	0.24	0.12	0.12	0.160
CO	5.04	4.44	6.6	5.360
CO2	25327.68	25662.96	25625.28	25538.64
Nox	69.36	69	72	70.120
Ex. Temp	1236	1237	1231	1234.667

Emissions Data for bare Caterpillar 3306 (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	34.15	36.756	35.453
HC	31.64706	23.4	27.524
CO	147.6471	167.28	157.464
CO2	86429.41	83610.96	85020.19
Nox	499.6471		499.647
Exh Temp	1094	1130	1112.000

Mode 2			
	Test 1	Test 2	AVG
PM	55.416	54.78	55.098
HC	32.16	30.96	31.560
CO	188.64	182.88	185.760
CO2	70344.72	70580.16	70462.44
Nox	676.68	675.48	676.080
Exh Temp	861	875	868.000

Mode 3			
	Test 1	Test 2	AVG
PM	71.856	71.172	71.514
HC	39.96	38.04	39.000
CO	169.8	167.04	168.420
CO2	56281.8	56201.16	56241.48
Nox	645.6	644.4	645.000
Exh Temp	1094	1130	1112.000

Mode 4			
	Test 1	Test 2	AVG
PM	84.47	87.28	85.875
HC	37.4583	38.4	37.929
CO	107.3709	110.2	108.785
CO2	37166.93	37021.4	37094.16
Nox	337.6966	337.2	337.448
Exh Temp	483	483	483.000

Mode 5			
	Test 1	Test 2	AVG
PM	91.608	89.712	90.660
HC	9.00	8.64	8.820
CO	158.28	147.36	152.820
CO2	56241.24	55020.12	55630.68
Nox	211.2		211.200
Exh Temp	1098	1094	1096.000

Mode 6			
	Test 1	Test 2	AVG
PM	17.364	16.884	17.124
HC	14.16	13.56	13.860
CO	52.92	52.44	52.680
CO2	41964.24	41623.92	41794.08
Nox	334.32	419.88	377.100
Exh Temp	703	700	701.500

Mode 7			
	Test 1	Test 2	AVG
PM	20.346	21.048	20.697
HC	9.72	9.84	9.780
CO	31.32	27.6	29.460
CO2	30531.24	31371.36	30951.3
Nox	490.2	489.84	490.020
Exh Temp	537		537.000

Mode 8			
	Test 1	Test 2	AVG
PM	3.2925	3.24	3.266
HC	2.025	2.25	2.138
CO	45.00	41.85	43.425
CO2	4806.3	4721.925	4764.113
Nox	59.625	60.825	60.225
Exh Temp	194	187	190.500

Emissions Data for Caterpillar 3306 with DST I (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	117.73	56.4375	87.084
HC	25.125	14.175	19.650
CO	15.6	8.925	12.263
CO2	93152.1	54524.18	73838.14
Nox	473.55	308.325	390.938
Exh Temp	1178	1147	1162.500

Mode 2			
	Test 1	Test 2	AVG
PM	57.945	56.16	57.053
HC	10.95	11.7	11.325
CO	15.375	18.225	16.800
CO2	72499.88	72084.3	72292.09
Nox	619.275	613.2	616.238
Exh Temp	920	925	922.500

Mode 3			
	Test 1	Test 2	AVG
PM	22.75	28.52	25.635
HC	11.55	11.475	11.513
CO	19.05	20.475	19.763
CO2	55716.75	55582.88	55649.81
Nox	641.325	579.075	610.200
Exh Temp	739	737	738.000

Mode 4			
	Test 1	Test 2	AVG
PM	4.043	4.178	4.111
HC	15.825	14.475	15.150
CO	21.00	22.125	21.563
CO2	36258.75	36604.5	36431.63
Nox	320.625	318.75	319.688
Exh Temp	505	507	506.000

Mode 5			
	Test 1	Test 2	AVG
PM	5.196	6.18	5.688
HC	9.6	6.72	8.160
CO	7.68	9.00	8.340
CO2	58748.4	58266.12	58507.26
Nox	222.36	221.16	221.760
Exh Temp	983	1000	991.500

Mode 6			
	Test 1	Test 2	AVG
PM	4.698	4.482	4.590
HC	1.62	1.38	1.500
CO	3.42	5.04	4.230
CO2	41920.8	41020.08	41470.44
Nox	348.42	354.12	351.270
Exh Temp	766	751	758.500

Mode 7			
	Test 1	Test 2	AVG
PM	2.154	2.358	2.256
HC	2.94	2.58	2.760
CO	5.34	3.36	4.350
CO2	30754.44	30665.22	30709.83
Nox	466.8	472.08	469.440
Exh Temp	556	555	555.500

Mode 8			
	Test 1	Test 2	AVG
PM	0.288	0.162	0.225
HC	52.56	55.98	54.270
CO	113.88	116.4	115.140
CO2	4613.64	4965.96	4789.800
Nox	47.16	48.00	47.580
Exh Temp	219	194	206.500

Emissions Data for Caterpillar 3306 bare engine (in g/hr) Emissions Data for Caterpillar 3306 with DST I with no oxidation catalyst (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	34.15	36.756	35.453
HC	31.64706	23.4	27.524
CO	147.6471	167.28	157.464
CO2	86429.41	83610.96	85020.19
Nox	499.6471		499.647
Exh Temp	1094	1130	1112.000

Mode 1			
	Test 1	Test 2	AVG
PM	108.56	88.87	98.715
HC	10.3	46.3	28.300
CO	138.7	133.4	136.050
CO2	87388.1	85469.3	86428.7
Nox	58.7	534.8	296.750
Exh Temp	1122	1172	1147.000

Mode 2			
	Test 1	Test 2	AVG
PM	55.416	54.78	55.098
HC	32.16	30.96	31.560
CO	188.64	182.88	185.760
CO2	70344.72	70580.16	70462.44
Nox	676.68	675.48	676.080
Exh Temp	861	875	868.000

Mode 2			
	Test 1	Test 2	AVG
PM	32.89	32.16	32.525
HC	40.9	39.3	40.100
CO	181.4	187	184.200
CO2	71168.2	71012.5	71090.35
Nox	646	647.9	646.950
Exh Temp	915	907	911.000

Emissions Data for Caterpillar 3306 bare engine (in g/hr)

Emissions Data for Caterpillar 3306 with DST II (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	34.15	36.756	35.453
HC	31.64706	23.4	27.524
CO	147.6471	167.28	157.464
CO2	86429.41	83610.96	85020.19
Nox	499.6471		499.647
Exh Temp	1094	1130	1112.000

Mode 1			
	Test 1	Test 2	AVG
PM	34.3875	27.81	31.099
HC	12.075	12.975	12.525
CO	13.275	13.95	13.613
CO2	84532.58	81383.4	82957.99
Nox	561.225	507.525	534.375
Exh Temp	1155	1118	1136.500

Mode 2			
	Test 1	Test 2	AVG
PM	55.416	54.78	55.098
HC	32.16	30.96	31.560
CO	188.64	182.88	185.760
CO2	70344.72	70580.16	70462.44
Nox	676.68	675.48	676.080
Exh Temp	861	875	868.000

Mode 2			
	Test 1	Test 2	AVG
PM	11.7975	13.2975	12.548
HC	10.5	10.95	10.725
CO	18.375	22.2	20.288
CO2	72514.95	72908.85	72711.9
Nox	616.125	612.225	614.175
Exh Temp	914	912	913.000

Mode 5			
	Test 1	Test 2	AVG
PM	91.608	89.712	90.660
HC	9.00	8.64	8.820
CO	158.28	147.36	152.820
CO2	56241.24	55020.12	55630.68
Nox	211.2		211.200
Exh Temp	1098	1094	1096.000

Mode 5			
	Test 1	Test 2	AVG
PM	3.12	2.925	3.023
HC	2.1	1.8	1.950
CO	4.575		4.575
CO2	43344.23	43978.8	43661.52
Nox	167.4	166.65	167.025
Exh Temp	1028	1034	1031.000

Mode 7			
	Test 1	Test 2	AVG
PM	20.346	21.048	20.697
HC	9.72	9.84	9.780
CO	31.32	27.6	29.460
CO2	30531.24	31371.36	30951.3
Nox	490.2	489.84	490.020
Exh Temp	537		537.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.99	0.945	0.968
HC	2.7	2.925	2.813
CO	1.125	3.3	2.213
CO2	31581.82	31713.3	31647.56
Nox	461.93	473.7	467.815
Exh Temp	543	536	539.500

** The results were from the repeated testing on DST after it was "fixed"

Emissions Data for Caterpillar 3306 bare engine-after checkup (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3	Test 4
PM	34.56	32.184		
HC	47.64	45.96	36.24	36.24
CO	142.2	137.76	124.32	136.56
CO2	89224.8	87880.92	91530.12	91827.36
Nox	481.68	462.72	494.28	506.64
Exh Temp	1101	1109	1094	1098
AVG				1100.333

Mode 2				
	Test 1	Test 2	Test 3	Test 4
PM	47.076	48.216		43.176
HC	50.16	50.16	41.00662	42
CO	162	162.84	168.0795	166.8
CO2	69888.84	71885.76	72709.27	72922.08
Nox	544.44	624.96	619.8675	622.32
Exh Temp	878	876.2	887	873
AVG				878.733

Mode 3			
	Test 1	Test 2	Test 3
PM	60.336	60.204	60.588
HC	47.64	46.08	48
CO	157.2	152.76	151.08
CO2	57959.4	58596.36	57997.56
Nox	613.08	603.36	612.12
Exh Temp	696	694	692
AVG			694.000

Mode 4			
	Test 1	Test 2	Test 3
PM	68.1	68.79826	68.449
HC	39.6	41.38829	40.494
CO	98.6	105.7354	102.168
CO2	36144	36756.08	36450.04
Nox	311.2	308.1475	309.674
Exh Temp	478	479	478.500
AVG			

Mode 5			
	Test 1	Test 2	Test 3
PM	39.36	39.492	39.426
HC	23.88	24.00	23.940
CO	79.2	70.8	75.000
CO2	54458.64	53988.72	54223.68
Nox	229.08	229.2	229.140
Exh Temp	975	987	981.000
AVG			

Mode 6			
	Test 1	Test 2	Test 3
PM	14.784	15.264	15.024
HC	25.32	25.2	25.260
CO	43.92	45.48	44.700
CO2	40808.52	40994.88	40901.70
Nox	385.08	377.4	381.240
Exh Temp	704	694	699.000
AVG			

Mode 7			
	Test 1	Test 2	Test 3
PM	25.236	23.292	24.264
HC	25.68	25.56	25.620
CO	30.96	30.00	30.480
CO2	30972.6	30974.64	30973.62
Nox	469.68	463.8	466.740
Exh Temp	504	505	504.500
AVG			

Mode 8			
	Test 1	Test 2	Test 3
PM	3.107071	3.383008	3.245
HC	20.62891	20.07083	20.350
CO	60.10399	61.09611	60.600
CO2	7807.28	8420.155	8113.717
Nox	106.7101	101.364	104.037
Exh Temp	208	196	202.000
AVG			

Emissions Data for Caterpillar 3306 with DST III (in g/hr)

Mode 1				
	Test 1	Test 2	Test 3*	Test 4
PM	34.932	26.46	29.268	30.220
HC		17.64	26.64	22.140
CO	14.28	8.28	8.64	10.400
CO2	80699.04	80383.8	65516.28	75533.04
Nox	385.68	372.96	346.08	368.240
Exh Temp	1198	1196	1174	1189.333
AVG				

Mode 2			
	Test 1	Test 2	Test 3
PM	5.796	5.94	5.868
HC	14.28	12.12	13.200
CO	14.28	15.12	14.700
CO2	66092.16	66595.68	66343.92
Nox	476.64	468.12	472.380
Exh Temp	929	927	928.000
AVG			

Mode 3			
	Test 1	Test 2	Test 3
PM	2.837143	3.214286	3.026
HC	14.14286	14.74286	14.443
CO	52.8	17.57143	35.186
CO2	48648.6	48369.86	48509.23
Nox	504.7714	503.5714	504.171
Exh Temp	738	740	739.000
AVG			

Mode 4			
	Test 1	Test 2	Test 3
PM	1.242857	1.56	1.401
HC	13.88571	15.17143	14.529
CO	5.142857	18.51429	11.829
CO2	31057.29	30807.94	30932.61
Nox	255.2571	259.2	257.229
Exh Temp	520	529	524.500
AVG			

Mode 5			
	Test 1	Test 2	Test 3
PM	2.808	3.348	3.078
HC	5.16	6.36	5.760
CO		5.04	5.040
CO2	46472.4	45889.08	46180.74
Nox	196.8	196.08	196.440
Exh Temp	987	973	980.000
AVG			

Mode 6			
	Test 1	Test 2	Test 3
PM	1.448571	1.277143	1.363
HC	5.657143	4.628571	5.143
CO	4.371429	0.514286	2.443
CO2	33461.66	33303.34	33382.50
Nox	282.5143	282.4286	282.471
Exh Temp	732	723	727.500
AVG			

Mode 7			
	Test 1	Test 2	Test 3
PM	0.555	0.5475	0.551
HC	5.175	4.275	4.725
CO	2.475	4.5	3.488
CO2	24698.18	24925.43	24811.80
Nox	341.325	346.575	343.950
Exh Temp		534	534.000
AVG			

Mode 8			
	Test 1	Test 2	Test 3
PM	0.084	0.042	0.063
HC	5.4	4.14	4.770
CO	25.74	26.1	25.920
CO2	4333.86	4683.06	4508.460
Nox	55.44	54.78	55.110
Exh Temp	230	202	216.000
AVG			

Emissions Data for bare Caterpillar 3306 (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	34.15	36.756	35.453
HC	31.64706	23.4	27.524
CO	147.6471	167.28	157.464
CO2	86429.41	83610.96	85020.19
Nox	499.6471		499.647
Exh Temp	1094	1130	1112.000

Mode 2			
	Test 1	Test 2	AVG
PM	55.416	54.78	55.098
HC	32.16	30.96	31.560
CO	188.64	182.88	185.760
CO2	70344.72	70580.16	70462.44
Nox	676.68	675.48	676.080
Exh Temp	861	875	868.000

Mode 3			
	Test 1	Test 2	AVG
PM	71.856	71.172	71.514
HC	39.96	38.04	39.000
CO	169.8	167.04	168.420
CO2	56281.8	56201.16	56241.48
Nox	645.6	644.4	645.000
Exh Temp	1094	1130	1112.000

Mode 4			
	Test 1	Test 2	AVG
PM	84.47	87.28	85.875
HC	37.4583	38.4	37.929
CO	107.3709	110.2	108.785
CO2	37166.93	37021.4	37094.16
Nox	337.6966	337.2	337.448
Exh Temp	483	483	483.000

Mode 5			
	Test 1	Test 2	AVG
PM	91.608	89.712	90.660
HC	9.00	8.64	8.820
CO	158.28	147.36	152.820
CO2	56241.24	55020.12	55630.68
Nox	211.2		211.200
Exh Temp	1098	1094	1096.000

Mode 6			
	Test 1	Test 2	AVG
PM	17.364	16.884	17.124
HC	14.16	13.56	13.860
CO	52.92	52.44	52.680
CO2	41964.24	41623.92	41794.08
Nox	334.32	419.88	377.100
Exh Temp	703	700	701.500

Mode 7			
	Test 1	Test 2	AVG
PM	20.346	21.048	20.697
HC	9.72	9.84	9.780
CO	31.32	27.6	29.460
CO2	30531.24	31371.36	30951.3
Nox	490.2	489.84	490.020
Exh Temp	537		537.000

Mode 8			
	Test 1	Test 2	AVG
PM	3.2925	3.24	3.266
HC	2.025	2.25	2.138
CO	45.00	41.85	43.425
CO2	4806.3	4721.925	4764.113
Nox	59.625	60.825	60.225
Exh Temp	194	187	190.500

Emissions Data for Caterpillar 3306 with CleanAir (in g/hr)

Mode 1			
	Test 1	Test 2	AVG
PM	18.473	16.365	17.419
HC	0.975	1.425	1.200
CO	3.975	0.975	2.475
CO2	90115.35	91648.88	90882.11
Nox	523.2	521.85	522.525
Exh Temp	1112	1151	1131.500

Mode 2			
	Test 1	Test 2	AVG
PM	22.2	24.435	23.318
HC	1.575	1.65	1.613
CO	2.325	2.55	2.438
CO2	73586.25	73484.33	73535.29
Nox	648.075	638.475	643.275
Exh Temp	902	901	901.500

Mode 3			
	Test 1	Test 2	AVG
PM	19.35		19.350
HC	2.25		2.250
CO	2.475		2.475
CO2	59134.35		59134.35
Nox	609		609.000
Exh Temp	712		712.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.9075	1.08	0.994
HC	3.3	3.3	3.300
CO	0.6	2.475	1.538
CO2	38571.6	38563.2	38567.4
Nox	323.925	322.125	323.025
Exh Temp	500	511	505.500

Mode 5			
	Test 1	Test 2	AVG
PM	20.84	24.16	22.500
HC	0.6	0.4	0.500
CO		2.4	2.400
CO2	58387.8	58718.7	58553.25
Nox	254.7	261.5	258.100
Exh Temp	1005	982	993.500

Mode 6			
	Test 1	Test 2	AVG
PM	13.66	13.298	13.479
HC	1.5	1.275	1.388
CO	2.175	1.8	1.988
CO2	42365.4	42364.73	42365.06
Nox	410.025	408.75	409.388
Exh Temp	718	698	708.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.848	0.923	0.886
HC	0.3	0.075	0.188
CO	4.575	5.325	4.950
CO2	31881.45	32178.6	32030.03
Nox	480.00	485.025	482.513
Exh Temp	519	516	517.500

Mode 8			
	Test 1	Test 2	AVG
PM	0.615	0.525	0.570
HC	1.65	0.525	1.088
CO	47.775	47.55	47.663
CO2	5257.65	5131.875	5194.763
Nox	65.175	63.15	64.163
Exh Temp	193	191	192.000

Appendix C

Emissions Data for MWM D916-6 with Low-sulfur (0.05%) Fuel (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	0.346	0.328	0.331	0.335
HC	0.05	0.06	0.05	0.053
CO	0.74	0.72	0.72	0.727
CO2	560.95	557.7	556.28	558.310
Nox	3.46	3.53	3.53	3.507

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	0.334	0.336	0.334	0.335
HC	0.09	0.08	0.08	0.083
CO	0.72	0.75	0.74	0.737
CO2	561.78	565.16	562.27	563.070
Nox	4.09	4.1	4.12	4.103

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	0.463	0.436	0.419	0.439
HC	0.11	0.11	0.11	0.110
CO	0.76	0.72	0.8	0.760
CO2	611.65	606.32	608.18	608.717
Nox	5.43	5.38	5.43	5.413

Mode 4				
	Test 1	Test 2	Test 3	AVG
PM	0.913	0.931	0.946	0.930
HC	0.19	0.18	0.21	0.193
CO	2.55	2.66	2.63	2.613
CO2	1218.6	1244.92	1206.29	1223.270
Nox	10.41	10.3	10	10.237

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	0.429	0.409	0.399	0.412
HC	0.04	0.04	0.03	0.037
CO	0.67	0.63	0.64	0.647
CO2	530.57	526.24	525.03	527.280
Nox	3.49	2.62	3.57	3.227

Mode 6				
	Test 1	Test 2	Test 3	AVG
PM	0.353	0.362	0.364	0.360
HC	0.05	0.05	0.05	0.050
CO	0.67	0.65	0.65	0.657
CO2	522.95	528.86	524.22	525.343
Nox	4.29		2.98	3.635

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.429	0.463	0.471	0.454
HC	0.07	0.09	0.1	0.087
CO	0.84	0.93	0.97	0.913
CO2	570.79	568.38	577.18	572.117
Nox	5.85	5.79	5.84	5.827

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	3.067	3.718	6.002	4.262
HC			0.71	0.710
CO	19.19	17.24	16.06	17.497
CO2	5945.7	5078.77	5434.11	5486.193
Nox	73.77	61.66	53.74	63.057

Emissions Data for MWM D916-6 with High-sulfur (0.25%) Fuel (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	0.44	0.453	0.394	0.429
HC	0.05	0.05	0.04	0.047
CO	0.67	0.7	0.69	0.687
CO2	580.01	572.84	573.25	575.367
Nox	3.36	3.41	3.41	3.393

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	0.414	0.411	0.421	0.415
HC	0.09	0.08	0.08	0.083
CO	0.73	0.68	0.72	0.710
CO2	587.82	585.74	589.89	587.817
Nox	3.84	3.81	3.8	3.817

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	0.512	0.488	0.491	0.497
HC	0.13	0.11	0.13	0.123
CO	0.69	0.69	0.72	0.700
CO2	634.4	629.88	629.24	631.173
Nox	5.17	5.11	5.16	5.147

Mode 4				
	Test 1	Test 2	Test 3	AVG
PM	1.158	1.213	1.198	1.190
HC	0.2	0.24	0.25	0.230
CO	2.62	2.85	2.84	2.770
CO2	1265.63	1254.47	1232.75	1250.950
Nox	10.13	9.96	9.78	9.957

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	0.553	0.523	0.499	0.525
HC	0.03	0.03	0.04	0.033
CO	0.59	0.56	0.55	0.567
CO2	552.43	550.26	549.92	550.870
Nox	3.25	3.18	3.29	3.240

Mode 6				
	Test 1	Test 2	Test 3	AVG
PM	0.432	0.499	0.47	0.467
HC	0.06	0.07	0.07	0.067
CO	0.57	0.59	0.57	0.577
CO2	549.69	550.41	545.09	548.397
Nox	4.06	4.03	3.99	4.027

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.517	0.54	0.548	0.535
HC	0.1	0.11	0.11	0.107
CO	0.73	0.86	0.81	0.800
CO2	589.04	590.97	594.75	591.587
Nox	5.52	5.53	5.51	5.520

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	8.151	10.322	9.798	9.424
HC	0.5	0.93	1.31	0.913
CO	14.62	21.85	26.73	21.067
CO2	5076.56	4944.06	4949.94	4990.187
Nox	43.01	40.07	40.72	41.267

Emissions Data for Lister Petter LPU-2 bare engine (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	6.122	5.778	5.676	5.859
HC	0.27	0.12	0.09	0.160
CO	44.71	36.82	34.79	38.773
CO2	921.7	933.69	927.82	927.737
Nox	1.76	1.8	1.81	1.790
Exh Temp	1457	1775	1792	1674.667

Mode 2				
	Test 1	Test 2	Test 3	AVG
PM	0.319	0.286	0.264	0.290
HC	0.53	0.55	0.49	0.523
CO	1.43	1.37	1.33	1.377
CO2	839.36	824.45	837.9	833.903
Nox	3.9	3.93	4.01	3.947
Exh Temp	915	903	898	905.333

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	0.326	0.342	0.319	0.329
HC	1.31	1.45	1.27	1.343
CO	1.62	1.85	1.58	1.683
CO2	930.87	925.05	943.22	933.047
Nox	5.24	5.2	5.32	5.253
Exh Temp	748	747	748	747.667

Mode 4			
	Test 1	Test 2	AVG
PM	0.881	0.727	0.804
HC	1.34	0.97	1.155
CO	3.39	2.71	3.050
CO2	1359.75	1392.39	1376.070
Nox	7.84	8.05	7.945
Exh Temp	583	580	581.500

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	7.833	7.889	7.996	7.906
HC	1.26	1.22	1.25	1.243
CO	33.98	32.8	33.38	33.387
CO2	831.94	825.37	823.84	827.050
Nox	1.67	1.63	1.59	1.630
Exh Temp	1138	1162	1233	1177.667

Mode 6						
	Test 1	Test 2	Test 3	Test 4	Test 5	AVG
PM	0.505	0.635	0.518	0.568	0.516	0.548
HC	1	0.99	0.8	0.43	0.4	0.724
CO	3.4	3.38	3.28	2.62	2.59	3.054
CO2	758.93	750.02	737.97	707.17	703.16	731.450
Nox	5.49	4.7	4.5	3.85	3.83	4.474
Exh Temp				763	780	771.500

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.367	0.435	0.458	0.420
HC	3.64	3.43	3.48	3.517
CO	6.78	6.52	6.69	6.663
CO2	882.15	875.7	862.71	873.520
Nox	8.26	7.87	7.9	8.010
Exh Temp	567	567	569	567.667

Mode 8				
	Test 1	Test 2	Test 3	AVG
PM	0.283	0.276	0.255	0.271
HC	0	0	0	0.000
CO	2.39	2.74	2.04	2.390
CO2	2162.11	2347.07	2318.72	2275.967
Nox	52.64	60.15	61.57	58.120
Exh Temp	269	231	227	242.333

Emissions Data for Lister Petter LPU-2 with failed trap (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	4.481	3.923	4.202
HC	0.02	0.01	0.015
CO	0.27	0.33	0.300
CO2	997.02	973.37	985.195
Nox	1.89	1.87	1.880
Exh Temp	1452	1459	1455.500

Mode 2			
	Test 1	Test 2	AVG
PM	0.332	0.345	0.339
HC	0.01	0.01	0.010
CO	0.05	0.12	0.085
CO2	950.12	934.63	942.375
Nox	3.9	3.95	3.925
Exh Temp	940	937	938.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.223	0.259	0.241
HC	0	0	0.000
CO	0.15	0.14	0.145
CO2	1010.78	1018.72	1014.750
Nox	4.97	5.06	5.015
Exh Temp	931	763	847.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.164	0.196	0.180
HC	0.05	0	0.025
CO	0.41	0.12	0.265
CO2	1543.86	1535.71	1539.785
Nox	7.57	7.57	7.570
Exh Temp	596	593	594.500

Mode 5			
	Test 1	Test 2	AVG
PM	5.067	5.512	5.290
HC	0.01	0.01	0.010
CO	0.09	0.11	0.100
CO2	858.09	862.9	860.495
Nox	1.81	1.79	1.800
Exh Temp	1208	1217	1212.500

Mode 6			
	Test 1	Test 2	AVG
PM	0.317	0.308	0.313
HC	0.09	0.05	0.070
CO	0.04	0.17	0.105
CO2	816.53	799.79	808.160
Nox	3.73	3.8	3.765
Exh Temp	827	824	825.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.116	0.102	0.109
HC	0.3	0.29	0.295
CO	0.2	0	0.100
CO2	959.55	956.54	958.045
Nox	7.66	7.72	7.690
Exh Temp	602	592	597.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.146	0.202	0.174
HC	0	0	0.000
CO	0	1.71	0.855
CO2	3585.66	3221.89	3403.775
Nox	76.42	67.81	72.115
Exh Temp	281	248	264.500

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/bhp-hr)

Mode 6						
	Test 1	Test 2	Test 3	Test 4	Test 5	AVG
PM	0.505	0.635	0.515	0.568	0.516	0.548
HC	1	0.99	0.5	0.43	0.4	0.724
CO	3.4	3.38	3.25	2.62	2.59	3.054
CO2	758.93	750.02	737.9	707.17	703.16	731.450
Nox	5.46	4.7	4.5	3.85	3.83	4.468
Ex. Temp	1349	1483	1810	1526	1560	1545.600

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.367	0.435	0.455	0.420
HC	3.64	3.43	3.48	3.517
CO	6.78	6.52	6.69	6.663
CO ₂	882.15	875.7	862.71	873.520
Nox	8.26	7.87	7.9	8.010
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	6.122	5.778	5.676	5.859
HC	0.27	0.12	0.09	0.160
CO	44.71	36.82	34.79	38.773
CO ₂	921.7	933.69	927.52	927.737
Nox	1.76	1.8	1.81	1.790
Ex. Temp	1457	1775	1792	11674.667

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	7.833	7.889	7.995	7.906
HC	1.26	1.22	1.25	1.243
CO	33.98	32.8	33.38	33.387
CO ₂	831.94	825.37	823.64	827.050
Nox	1.67	1.63	1.59	1.630
Ex. Temp	1138	1162	1233	11177.667

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.367	0.435	0.455	0.420
HC	3.64	3.43	3.48	3.517
CO	6.78	6.52	6.69	6.663
CO ₂	882.15	875.7	862.71	873.520
Nox	8.26	7.87	7.9	8.010
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Bare Engine (in g/bhp-hr)

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM	0.367	0.435	0.455	0.420
HC	3.64	3.43	3.48	3.517
CO	6.78	6.52	6.69	6.663
CO ₂	882.15	875.7	862.71	873.520
Nox	8.26	7.87	7.9	8.010
Ex. Temp	567	567	569	567.667

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with new trap (in g/bhp-hr)

Mode 6			
	Test 1	Test 2	AVG
PM	0.091	0.111	0.101
HC	0	0	0.000
CO	0.07	0.05	0.060
CO2	763.98	753.03	758.505
Nox	3.41	3.5	3.455
Ex. Temp	806	807	806.500

Mode 7			
	Test 1	Test 2	AVG
PM		0.033	0.033
HC	0	0	0.000
CO	0.12	0.13	0.125
CO2	924.07	916.84	920.455
Nox	6.21	6.31	6.260
Ex. Temp	593	597	595.000

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with oxidation catalyst only (in g/bhp-hr)

	Mode 1		
	Test 1	Test 2	AVG
PM	7.05	7.881	7.466
HC	0.17	0.14	0.155
CO	30.84	30.59	30.715
CO2	938.72	933.85	936.285
Nox	0.83	0.68	0.755
Ex. Temp	1351	1389	1370.000

Mode 5			
	Test 1	Test 2	AVG
PM	8.087	8.21	8.149
HC	0.04	0.04	0.040
CO	0.14	0.16	0.150
CO2	833.12	827.05	830.085
Nox	1.9	1.81	1.855
Ex. Temp	1203	1205	1204.000

Mode 7				
	Test 1	Test 2	Test 3	AVG
PM		0.325	0.303	0.314
HC	0.38	0.38	0.39	0.383
CO	0.13	0.1	0.03	0.087
CO2	901.24	895.15	891.5	895.963
Nox	7.09	7.2	7.27	7.187
Ex. Temp	622	601	597	606.667

Emissions Data for Lister Petter LPU-2 Rohmac/DCL system with new trap and Pallflex paper filter (in g/bhp-hr)

Mode 7			
	Test 1	Test 2	AVG
PM	0.033	0.006	0.020
HC	0.3	0.32	0.310
CO	0.09	0.12	0.105
CO ₂	808.3	795.97	802.135
Nox	5.65	5.87	5.760
Ex. Temp	616	609	612.500

Emissions Data for Isuzu C240 bare engine (in g/bhp-hr)

Emissions Data for Isuzu C240 with Trap and Oxidation Catalyst (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.204	0.192	0.198
HC	0.08	0.11	0.095
CO	0.73	0.89	0.810
CO ₂	637.19	634.82	636.005
Nox	3.4	3.27	3.335
Exh Temp	1065	1077	1071.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.223	0.219	0.221
HC	0.13	0.12	0.125
CO	1.01	0.98	0.995
CO ₂	627.29	627.61	627.450
Nox	4.66	4.72	4.690
Exh Temp	828	825	826.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.285	0.31	0.298
HC	1.42	1.61	1.515
CO	0.93	1.07	1.000
CO ₂	635.11	632.4	633.755
Nox	5.81	6.06	5.935
Exh Temp	646	646	646.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.752	0.767	0.760
HC	0.36	0.38	0.370
CO	1.57	1.5	1.535
CO ₂	931.57	906.15	918.860
Nox	7.87	7.89	7.880
Exh Temp	444	444	444.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.865	0.879	0.872
HC	0.01	0.01	0.010
CO	2.81	2.77	2.790
CO ₂	620.54	616.43	618.485
Nox	1.84	1.73	1.785
Exh Temp	1092	1093	1092.500

Mode 6			
	Test 1	Test 2	AVG
PM	0.127	0.125	0.126
HC	0.05	0.06	0.055
CO	0.46	0.48	0.470
CO ₂	568.7	566.64	567.670
Nox	3	2.98	2.990
Exh Temp	758	750	754.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.158	0.147	0.153
HC	0.15	0.17	0.160
CO	0.7	0.74	0.720
CO ₂	585.34	590.88	588.110
Nox	4.6	4.39	4.495
Exh Temp	542	546	544.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.249	0.295	0.272
HC	0.75	0.77	0.760
CO	16.24	14.9	15.570
CO ₂	1881.92	1847.15	1864.535
Nox	14.25	13.38	13.815
Exh Temp	198	189	193.500

Mode 1			
	Test 1	Test 2	AVG
PM	0.167	0.159	0.163
HC	0	0	0.000
CO	0	0.02	0.010
CO ₂	637.33	631.1	634.215
Nox	3.29	3.33	3.310
Exh Temp	1199	1195	1197.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.035	0.126	0.081
HC	0	0	0.000
CO	0	0	0.000
CO ₂	613.81	614.08	613.945
Nox	4.84	4.82	4.830
Exh Temp	917.29	921	919.145

Mode 3			
	Test 1	Test 2	AVG
PM	0.027	0.077	0.052
HC	0.01	0.01	0.010
CO	0.02	0	0.010
CO ₂	646.14	651.24	648.690
Nox	5.84	5.71	5.775
Exh Temp	697	699	698.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.004	0.007	0.006
HC	0	0	~
CO	0.1	0.1	0.100
CO ₂	925.35	924.75	925.050
Nox	6.65	6.15	6.400
Exh Temp	482	485	483.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.303	0.187	0.245
HC	0	0	0.000
CO	0.03	0.05	0.040
CO ₂	646.13	639	642.565
Nox	1.76	1.68	1.720
Exh Temp	1261	1275	1268.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.005	0.004	0.005
HC	0	0	0.000
CO	0.01	0.01	0.010
CO ₂	581.31	583.36	582.335
Nox	2.8	2.87	2.835
Exh Temp	867	860	863.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.003	0.004	0.004
HC	0	0	0.000
CO	0.05	0.02	0.035
CO ₂	604.7	604.26	604.480
Nox	3.85	3.93	3.890
Exh Temp	622	618	620.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.055	0.044	0.050
HC	0.12	0.23	0.175
CO	0.18	5.3	2.740
CO ₂	2013.87	1971.5	1992.685
Nox	19.32	17.13	18.225
Exh Temp	233	223	228.000

Emissions Data for Isuzu C240 bare engine (in g/bhp-hr) Emissions Data for Isuzu C240 with Oxidation Catalyst and Trap (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.204	0.192	0.198
HC	0.08	0.11	0.095
CO	0.73	0.89	0.810
CO2	637.19	634.82	636.005
Nox	3.4	3.27	3.335
Exh Temp	1065	1077	1071.000

Mode 1			
	Test 1	Test 2	AVG
PM	0.118	0.115	0.117
HC	0	0	0.000
CO	0.06	0.01	0.035
CO2	682.19	685.31	683.750
Nox	3.34	3.14	3.240
Exh Temp	1193	1206	1199.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.285	0.31	0.298
HC	1.42	1.61	1.515
CO	0.93	1.07	1.000
CO2	635.11	632.4	633.755
Nox	5.81	6.06	5.935
Exh Temp	646	646	646.000

Mode 3			
	Test 1	Test 2	AVG
PM	0.02	0.024	0.022
HC	0.01	0	0.005
CO	0.08	0.05	0.065
CO2	646.09	642.86	644.475
Nox	5.78	5.45	5.615
Exh Temp	705	708	706.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.865	0.879	0.872
HC	0.01	0.01	0.010
CO	2.81	2.77	2.790
CO2	620.54	616.43	618.485
Nox	1.84	1.73	1.785
Exh Temp	1092	1093	1092.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.195	0.181	0.188
HC	0	0	0.000
CO	0.04	0.03	0.137
CO2	625.35	626.35	649.200
Nox	1.89	1.83	1.783
Exh Temp	1184	1181	1182.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.158	0.147	0.153
HC	0.15	0.17	0.160
CO	0.7	0.74	0.720
CO2	585.34	590.88	588.110
Nox	4.6	4.39	4.495
Exh Temp	542	546	544.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.002	0.002	0.002
HC	0	0	0.000
CO	0.08	0	0.040
CO2	603.55	592.47	598.010
Nox	3.61	3.7	3.655
Exh Temp	613	605	609.000

Emissions Data for Isuzu C240 bare engine (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.204	0.192	0.198
HC	0.08	0.11	0.095
CO	0.73	0.89	0.810
CO2	637.19	634.82	636.005
Nox	3.4	3.27	3.335
Exh Temp	1065	1077	1071.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.865	0.879	0.872
HC	0.01	0.01	0.010
CO	2.81	2.77	2.790
CO2	620.54	616.43	618.485
Nox	1.84	1.73	1.785
Exh Temp	1092	1093	1092.500

Emissions Data for Isuzu C240 with Oxidation Catalyst only (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.338	0.338	0.338
HC	0.01	0	0.005
CO	0.07	0.07	0.070
CO2	624.68	640.69	632.685
Nox	3.19	3.23	3.210
Exh Temp	1185	1183	1184.000

Mode 5				
	Test 1	Test 2	Test 3	AVG
PM	1.366	1.356	1.481	1.401
HC	0	0	0	0.000
CO	0.13	0.11	0.17	0.137
CO2	644.68	654.45	648.47	649.200
Nox	1.77	1.76	1.82	1.783
Exh Temp	1236	1237	1231	1234.667

Emissions Data for bare Caterpillar 3306 (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.275	0.298	0.287
HC	0.25	0.19	0.220
CO	1.16	1.33	1.245
CO2	677.1	666.75	671.925
Nox	3.91		3.910
Exh Temp	1094	1130	1112.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.571	0.562	0.567
HC	0.33	0.32	0.325
CO	1.94	1.88	1.910
CO2	724.21	724.58	724.395
Nox	6.97	6.93	6.950
Exh Temp	861	875	868.000

Mode 3			
	Test 1	Test 2	AVG
PM	1.086	1.075	1.081
HC	0.6	0.57	0.585
CO	2.57	2.52	2.545
CO2	850.5	849.04	849.770
Nox	9.76	9.73	9.745
Exh Temp	694	698	696.000

Mode 4			
	Test 1	Test 2	AVG
PM	5.083	5.261	5.172
HC	2.25	2.31	2.280
CO	6.46	6.64	6.550
CO2	2236.71	2231.72	2234.215
Nox	20.32	20.33	20.325
Exh Temp	483	483	483.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.953	0.932	0.943
HC	0.09	0.09	0.090
CO	1.65	1.53	1.590
CO2	585.07	571.77	578.420
Nox	2.2		2.200
Exh Temp	1098	1094	1096.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.241	0.234	0.238
HC	0.2	0.19	0.195
CO	0.73	0.72	0.725
CO2	581.35	575.93	578.640
Nox	4.63	5.81	5.220
Exh Temp	703	700	701.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.419	0.433	0.426
HC	0.2	0.2	0.200
CO	0.64	0.57	0.605
CO2	628.3	645.33	636.815
Nox	10.09	10.08	10.085
Exh Temp	537		537.000

Mode 8			
	Test 1	Test 2	AVG
PM	8.531	7.507	8.019
HC	5.2	5.29	5.245
CO	116.49	96.99	106.74
CO2	12451.7	10946.15	11698.93
Nox	154.54	141.04	147.790
Exh Temp	193	186	189.500

Emissions Data for Caterpillar 3306 with DST I (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.934	0.736	0.835
HC	0.2	0.18	0.190
CO	0.12	0.12	0.120
CO2	739.4	711.49	725.445
Nox	3.76	4.02	3.890
Exh Temp	1178	1147	1162.500

Mode 2			
	Test 1	Test 2	AVG
PM	0.595	0.577	0.586
HC	0.11	0.12	0.115
CO	0.16	0.19	0.175
CO2	744.78	740.79	742.785
Nox	6.36	6.3	6.330
Exh Temp	920	925	922.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.343	0.43	0.387
HC	0.17	0.17	0.170
CO	0.29	0.31	0.300
CO2	840.47	838.69	839.580
Nox	9.67	8.74	9.205
Exh Temp	739	737	738.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.243	0.251	0.247
HC	0.95	0.87	0.910
CO	1.26	1.33	1.295
CO2	2179.95	2196.41	2188.180
Nox	19.28	19.13	19.205
Exh Temp	505	507	506.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.054	0.065	0.060
HC	0.1	0.07	0.085
CO	0.08	0.09	0.085
CO2	610.68	608.11	609.395
Nox	2.31	2.31	2.310
Exh Temp	983	1000	991.500

Mode 6			
	Test 1	Test 2	AVG
PM	0.065	0.062	0.064
HC	0.02	0.02	0.020
CO	0.05	0.07	0.060
CO2	583.06	570.07	576.565
Nox	4.85	4.92	4.885
Exh Temp	765	751	758.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.044	0.049	0.047
HC	0.06	0.05	0.055
CO	0.11	0.07	0.090
CO2	635.02	633.36	634.190
Nox	9.64	9.75	9.695
Exh Temp	556	555	555.500

Mode 8			
	Test 1	Test 2	AVG
PM	0.814	0.391	0.603
HC	148.23	134.45	141.340
CO	321.28	279.31	300.295
CO2	13017.7	11915.42	12466.56
Nox	133.14	115.17	124.155
Exh Temp	219	194	206.500

Emissions Data for Caterpillar 3306 bare engine (in g/bhp-hr) Emissions Data for Caterpillar 3306 with DST I no catalyst (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.275	0.298	0.287
HC	0.25	0.19	0.220
CO	1.16	1.33	1.245
CO2	677.1	666.75	671.925
Nox	3.91		3.910
Exh Temp	1094	1130	1112.000

Mode 1			
	Test 1	Test 2	AVG
PM	0.877	0.73	0.804
HC	0.08	0.38	0.230
CO	1.12	1.1	1.110
CO2	705.79	701.82	703.805
Nox	0.47	4.39	2.430
Exh Temp	1122	1172	1147.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.571	0.562	0.567
HC	0.33	0.32	0.325
CO	1.94	1.88	1.910
CO2	724.21	724.58	724.395
Nox	6.97	6.93	6.950
Exh Temp	861	875	868.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.338	0.331	0.335
HC	0.42	0.4	0.410
CO	1.87	1.92	1.895
CO2	731.64	730.44	731.040
Nox	6.64	6.66	6.650
Exh Temp	915	907	911.000

Emissions Data for Caterpillar 3306 bare engine (in g/bhp-hr)

Emissions Data for Caterpillar 3306 with DST II (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.275	0.298	0.287
HC	0.25	0.19	0.220
CO	1.16	1.33	1.245
CO2	677.1	666.75	671.925
Nox	3.91		3.910
Exh Temp	1094	1130	1112.000

Mode 1			
	Test 1	Test 2	AVG
PM	0.282	0.23	0.256
HC	0.1	0.11	0.105
CO	0.11	0.12	0.115
CO2	693.24	672.82	683.030
Nox	4.6	4.2	4.400
Exh Temp	1155	1118	1136.500

Mode 2			
	Test 1	Test 2	AVG
PM	0.571	0.562	0.567
HC	0.33	0.32	0.325
CO	1.94	1.88	1.910
CO2	724.21	724.58	724.395
Nox	6.97	6.93	6.950
Exh Temp	861	875	868.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.122	0.137	0.130
HC	0.11	0.11	0.110
CO	0.19	0.23	0.210
CO2	747.32	750.38	748.850
Nox	6.35	6.3	6.325
Exh Temp	914	912	913.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.953	0.932	0.943
HC	0.09	0.09	0.090
CO	1.65	1.53	1.590
CO2	585.07	571.77	578.420
Nox	2.2		2.200
Exh Temp	1098	1094	1096.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.043	0.04	0.042
HC	0.03	0.03	0.030
CO	0.06		0.060
CO2	598.28	606.38	602.330
Nox	2.31	2.3	2.305
Exh Temp	1028	1034	1031.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.419	0.433	0.426
HC	0.2	0.2	0.200
CO	0.64	0.57	0.605
CO2	628.3	645.33	636.815
Nox	10.09	10.08	10.085
Exh Temp	537		537.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.02	0.02	0.020
HC	0.06	0.06	0.060
CO	0.02	0.07	0.045
CO2	653.55	657.64	655.595
Nox	9.56	9.82	9.690
Exh Temp	543	536	539.500

** The results were from the repeated testing on DST after it was "fixed"

Emissions Data for Caterpillar 3306 bare engine - after checkup (in g/bhp-hr)

Mode 1					
	Test 1	Test 2	Test 3	Test 4	AVG
PM	0.268	0.249			0.259
HC	0.37	0.36	0.28	0.28	0.323
CO	1.1	1.07	0.96	1.05	1.045
CO ₂	690.92	680.7	707.03	707.38	696.508
Nox	3.73	3.58	3.82	3.9	3.758
Exh Temp	1101	1109	1094	1098	1100.500

Mode 2					
	Test 1	Test 2	Test 3	Test 4	AVG
PM	0.479	0.491			0.485
HC	0.51	0.51	0.42	0.43	0.468
CO	1.65	1.66	1.72	1.7	1.683
CO ₂	711.73	731.61	742.33	742.19	731.965
Nox	5.54	6.36	6.33	6.33	6.140
Exh Temp	878	876.2	887	873	878.550

Mode 3				
	Test 1	Test 2	Test 3	AVG
PM	0.903	0.901	0.908	0.904
HC	0.71	0.69	0.72	0.707
CO	2.35	2.29	2.26	2.300
CO ₂	866.91	876.53	869.64	871.027
Nox	9.17	9.03	9.18	9.127
Exh Temp	696	694	692	694.000

Mode 4			
	Test 1	Test 2	AVG
PM	4.086	4.112	4.099
HC	2.37	2.48	2.425
CO	5.92	6.32	6.120
CO ₂	2168.39	2196.44	2182.415
Nox	18.67	18.41	18.540
Exh Temp	478	479	478.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.431	0.432	0.432
HC	0.26	0.26	0.260
CO	0.87	0.78	0.825
CO ₂	596.87	591.29	594.080
Nox	2.51	2.51	2.510
Exh Temp	975	987	981.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.215	0.222	0.219
HC	0.37	0.37	0.370
CO	0.64	0.66	0.650
CO ₂	592.04	595.15	593.595
Nox	5.59	5.48	5.535
Exh Temp	704	694	699.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.546	0.504	0.525
HC	0.56	0.55	0.555
CO	0.67	0.65	0.660
CO ₂	669.73	670.34	670.035
Nox	10.16	10.04	10.100
Exh Temp	504	505	504.500

Mode 8			
	Test 1	Test 2	AVG
PM	4.724	4.647	4.686
HC	31.43	27.65	29.540
CO	91.29	84.14	87.715
CO ₂	11870.44	11586	11728.22
Nox	162.15	139.41	150.780
Exh Temp	208	196	202.000

Emissions Data for Caterpillar 3306 with DST III (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	0.274	0.209	0.23	0.238
HC		0.14	0.21	0.175
CO	0.11	0.07	0.07	0.083
CO ₂	633.92	634.51	613.89	627.440
Nox	3.03	2.94	2.71	2.893
Exh Temp	1198	1196	1174	1189.333

Mode 2			
	Test 1	Test 2	AVG
PM	0.059	0.06	0.060
HC	0.14	0.12	0.130
CO	0.14	0.15	0.145
CO ₂	669.18	674.87	672.025
Nox	4.83	4.74	4.785
Exh Temp	929	927	928.000

Mode 3			
	Test 1	Test 2	AVG
PM	0.042	0.048	0.045
HC	0.21	0.22	0.215
CO	0.79	0.26	0.525
CO ₂	723.42	720.01	721.715
Nox	7.63	7.5	7.565
Exh Temp	738	740	739.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.074	0.094	0.084
HC	0.82	0.91	0.865
CO	0.31	1.11	0.710
CO ₂	1841.32	1845.6	1843.460
Nox	15.13	15.53	15.330
Exh Temp	520	529	524.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.031	0.037	0.034
HC	0.06	0.07	0.065
CO		0.06	0.060
CO ₂	515.29	510.71	513.000
Nox	2.18	2.18	2.180
Exh Temp	987	973	980.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.021	0.019	0.020
HC	0.08	0.07	0.075
CO	0.06	0.01	0.035
CO ₂	485.58	483.72	484.650
Nox	4.1	4.1	4.100
Exh Temp	732	723	727.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.012	0.012	0.012
HC	0.11	0.09	0.100
CO	0.05	0.1	0.075
CO ₂	533.76	537.87	535.815
Nox	7.38	7.48	7.430
Exh Temp		534	534.000

Mode 8			
	Test 1	Test 2	AVG
PM	0.283	0.121	0.202
HC	18.06	11.64	14.850
CO	85.98	73.83	79.905
CO ₂	14469.02	13232.53	13850.78
Nox	185.02	154.86	169.940
Exh Temp	230	202	216.000

Emissions Data for bare Caterpillar 3306 (in g/bhp-hr)

Mode 1			
	Test 1	Test 2	AVG
PM	0.275	0.298	0.287
HC	0.25	0.19	0.220
CO	1.16	1.33	1.245
CO2	677.1	666.75	671.925
Nox	3.91		3.910
Exh Temp	1094	1130	1112.000

Mode 2			
	Test 1	Test 2	AVG
PM	0.571	0.562	0.567
HC	0.33	0.32	0.325
CO	1.94	1.88	1.910
CO2	724.21	724.58	724.395
Nox	6.97	6.93	6.950
Exh Temp	861	875	868.000

Mode 3			
	Test 1	Test 2	AVG
PM	1.086	1.075	1.081
HC	0.6	0.57	0.585
CO	2.57	2.52	2.545
CO2	850.5	849.04	849.770
Nox	9.76	9.73	9.745
Exh Temp	694	698	696.000

Mode 4			
	Test 1	Test 2	AVG
PM	5.083	5.261	5.172
HC	2.25	2.31	2.280
CO	6.46	6.64	6.550
CO2	2236.71	2231.72	2234.215
Nox	20.32	20.33	20.325
Exh Temp	483	483	483.000

Mode 5			
	Test 1	Test 2	AVG
PM	0.953	0.932	0.943
HC	0.09	0.09	0.090
CO	1.65	1.53	1.590
CO2	585.07	571.77	578.420
Nox	2.2		2.200
Exh Temp	1098	1094	1096.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.241	0.234	0.238
HC	0.2	0.19	0.195
CO	0.73	0.72	0.725
CO2	581.35	575.93	578.640
Nox	4.63	5.81	5.220
Exh Temp	703	700	701.500

Mode 7			
	Test 1	Test 2	AVG
PM	0.419	0.433	0.426
HC	0.2	0.2	0.200
CO	0.64	0.57	0.605
CO2	628.3	645.33	636.815
Nox	10.09	10.08	10.085
Exh Temp	537		537.000

Mode 8			
	Test 1	Test 2	AVG
PM	8.531	7.507	8.019
HC	5.2	5.29	5.245
CO	116.49	96.99	106.74
CO2	12451.7	10946.15	11698.93
Nox	154.54	141.04	147.790
Exh Temp	193	186	189.500

Emissions Data for Caterpillar 3306 with Clean Air System (in g/bhp-hr)

Mode 1				
	Test 1	Test 2	Test 3	AVG
PM	0.115	0.146	0.127	0.129
HC	0.01	0.01	0.01	0.010
CO	0.05	0.03	0.01	0.030
CO2	703.07	713.25	709.22	708.513
Nox	3.92	4.14	4.04	4.033
Exh Temp	1128	1112	1151	1130.333

Mode 2			
	Test 1	Test 2	AVG
PM	0.229	0.251	0.240
HC	0.02	0.02	0.020
CO	0.02	0.03	0.025
CO2	757.53	756.13	756.830
Nox	6.67	6.57	6.620
Exh Temp	902	901	901.500

Mode 3			
	Test 1	Test 2	AVG
PM	0.292		0.292
HC	0.03		0.030
CO	0.04		0.040
CO2	893.64		893.640
Nox	9.2		9.200
Exh Temp	712		712.000

Mode 4			
	Test 1	Test 2	AVG
PM	0.054	0.065	0.060
HC	0.2	0.2	0.200
CO	0.04	0.15	0.095
CO2	2315.89	2316.7	2316.295
Nox	19.45	19.35	19.400
Exh Temp	500	511	505.500

Mode 5			
	Test 1	Test 2	AVG
PM	0.216	0.246	0.231
HC	0.01	0	0.005
CO		0.02	0.020
CO2	604.37	598.97	601.670
Nox	2.64	2.67	2.655
Exh Temp	1005	981	993.000

Mode 6			
	Test 1	Test 2	AVG
PM	0.19	0.185	0.188
HC	0	0	0.000
CO	0.03	0.03	0.030
CO2	588.43	587.81	588.120
Nox	5.7	5.67	5.685
Exh Temp	718	698	708.000

Mode 7			
	Test 1	Test 2	AVG
PM	0.017	0.019	0.018
HC	0.01	0.03	0.020
CO	0.09	0.11	0.100
CO2	658.39	666.39	662.390
Nox	9.91	10.04	9.975
Exh Temp	519	516	517.500

Mode 8			
	Test 1	Test 2	AVG
PM	1.423	1.304	1.364
HC	3.9	1.29	2.595
CO	110.86	117.71	114.285
CO2	12191.36	12712.37	12451.87
Nox	151.2	156.41	153.805
Exh Temp	193	191	192.000

Appendix D

HC Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.1-1

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

CO Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.1-2

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

CO2 Concentration Trace for First Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.1-3

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

**NOx Concentration Trace for First Regenerative Cycle on Lister-Petter with
Failed* Rohmac/DCL System**

Figure D.1-4

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

**Exhaust Manifold Backpressure Trace for First Regenerative Cycle on Lister.
Petter with Failed* Rhomac/DCL System**

Time (sec)

Figure D.1-5

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

Exhaust Gas Temperature Trace for First Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.1-6

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

HC Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.2-1

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

**CO Concentration Trace for Second Regenerative Cycle on Lister-Petter with
Failed* Rohmac/DCL System**

Figure D.2-2

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

CO2 Concentration Trace for Second Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.2-3

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

**NO_x Concentration Trace for Second Regenerative Cycle on Lister-Petter
with Failed* Rohmac/DCL System**

Figure D.2-4

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

**Exhaust Manifold Backpressure Trace for Second Regenerative Cycle on
Lister-Petter with Failed* Rohmac/DCL System**

Figure D.2-5

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

Exhaust Gas Temperature Trace for Second Regenerative Cycle on Lister-Petter with Failed* Rohmac/DCL System

Figure D.2-6

*Failure was due to undersized catalyst/trap and overfueled engine (see text).

HC Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System

Figure D.3-1

**CO Concentration Trace for a Regenerative Cycle on Lister-Petter with
Rohmac/DCL System**

Time (sec)

Figure D.3-2

CO₂ Concentration Trace for a Regenerative Cycle on Lister-Petter with Rhomac/DCL System

Figure D.3-3

NOx Concentration Trace for a Regenerative Cycle on Lister-Petter with Rohmac/DCL System

Figure D.3-4

Exhaust Manifold Backpressure Trace for a Regenerative Cycle on Lister-Petter with Rhomac/DCL System

Figure D.3-5

Exhaust Gas Temperature Trace for a Regenerative Cycle on Lister-Petter with Rhomac/DCL System

Figure D.3-6

Appendix E

GOODMAN EQUIPMENT CORP

TONY BILITSKI

REGIONAL MANAGER

March 19, 1998

Ron Eberhart
Sr. Vice President
Goodman Equipment Corp.
5430 W. 70th Place
Bedford Park, Ill. 60638

Dear Ron,

Ron the following is synopsis of what happened on March 3rd and March 4th this week at WVU. Mr. Roger Fredrick from Beckwith performed all checks on the Cat 3306 engine serial # 23C2672 that had 41 hours recorded on the meter. Assisting with the testing was Mr. Dan Carder from WVU.

Specifications to check

Findings/Reset Specifications

1. Fuel rack setting discrepancy

Rack settings found: 3.35 mm full load
3.45 mm full torque

Reset rack settings to: 3.17 mm full load
3.25 mm full torque

2. Check fuel injection timing

Timing found to be OK (perfect) by pin timing to engine.

3. Check for engine blow-by.

Ran engine to operating temperature (1065 degrees F). We loaded engine and checked blow-by to be at 2" water. (4" water is the maximum spec.)

4. Check for valve lash and valve timing

Found 2 intake valves 0.004 too tight.
Adjusted to factory specification 0.015.
Found all exhaust valves 0.004 too loose.
Adjusted to factory specification 0.025.

5. Check valve seals for leaks.

Taking into consideration the results of the previous tests (example: 1065 degree operating temp) and other specifications found, it could be determined with reasonable certainty that there are no leaking valve seals in this engine.

6. Check spray patterns of injectors.

This check needed to be done at a test bench so the injectors had to be removed and then checked. All injectors tested to spec.

7. Check opening pressure of injectors.

This check needed to be done at a test bench so the injectors had to be removed and then checked. Pressure tested at 700 to 750 psi.

With items 6 & 7 completed, the injectors were then reinstalled. The engine was then run again to check for any fuel leaks. No leaks were found and the testing was considered complete.

I will be sending the original service reports from Caterpillar to your attention in Chicago.

Regards,
Tony

CONSOL Inc.
RESEARCH & DEVELOPMENT
Rt. 19 S at Indian Creek
Morgantown, WV 26505

FACSIMILE TRANSMISSION

Date: June 11, 1998

No. of Pages (including cover): 2

TO
Name: DR. GAUTAM
Company: MECH. & AEROSPACE ENGINEERING
Location: WVU
FAX No.: 293-6689
Verification Phone No: 293-3111

FROM
Name: PRAMOD THAKUR
R & D Phone No.: 304 983-3207
Department:
FAX No.: (304) 983-3209
Verification Phone No.: (304) 983-3201

Comments:

GOODMAN EQUIPMENT CORPORATION

8430 WEST 70TH PLACE • BEDFORD PARK, ILLINOIS 60638 • 708-496-1188 • FAX 708-496-9839

Telefax Transmission

December 17, 1997

To: Dan Carder
Company: University of West Virginia
Telefax No.: 304-293-6689
Pages: 2
Subject: Rohmac - LPU Emissions
From: Jack Echaliar - Product Service Manager
Copied to: TJP RHS BAH

*Clementine -
The Lister-Petter
English Setter.*

**The right diesel
for the job.**
TM

IVECO aifo

This is in response to Buck Lovern's request for base line emission data for the LPU2 engine that you are testing for Rohmac.

Please find attached some figures recently taken from an LPU3 engine. This 3-cylinder engine is identical in bore, stroke and fuel injection equipment to the 2-cylinder engine you are testing.

We should stress that these were obtained from a single engine test, and we cannot vouch for the accuracy or repeatability of these figures. We are providing them simply for you to compare with your own readings, and would ask you to keep them confidential.

If you need any further information please feel free to contact either Trevor Purnell, who is responsible for the Rohmac account, or Richard Soper, who is the engineer responsible for emissions, and who took the attached readings.

Regards,

Jack
Jack

**EXHAUST EMISSIONS
LISTER-PETTER MINE PUP
MODEL LPU-3**

Date: 15 December 1997
S/N: 4700028LPU3A801
Barometer: 29.23" Hg

Dry Bulb: 75°F
Wet Bulb: 58°F
Rel. Hum.: 35%

Speed	Load Factor	BHP Advertised	BHP Observed	Torque Observed	Speed Observed	O2 %	CO2 %	CO ppm	NO ppm	NO2 ppm	SO2 ppm	CxHy %	Exc. Air
3200 RPM	100%	28.8	29.5	18.2 lbf	3240 rpm	13.8	5.5	490	429	15	22	0.02	2.73
	75%	21.8	22.9	13.8 lbf	3316 rpm	16.4	3.3	303	351	42	0	0	4.67
	50%	14.4	15.4	9.2 lbf	3355 rpm	20	0.7	298	207	57	0	0	26.25
	0%	0	0	0	3375 rpm	21	N/R	505	65	55	0	0	N/R
2200 RPM	100%	23.3	24.1	21.3 lbf	2263 rpm	10.9	7.5	704	396	6	34	0.03	2.04
	75%	17.5	18.2	16.3 lbf	2350 rpm	15.5	4.1	999	495	59	0	0.03	3.82
	50%	11.7	12.9	10.7 lbf	2418 rpm	20.6	0.3	302	422	66	0	0.01	N/R
	0%	0	0	0	2498 rpm	21	N/R	295	102	64	0	0	N/R
2000 RPM	100%	21.3	22.1	21.6 lbf	2045 rpm	9.8	8.3	792	374	4	15	0.01	1.86
	75%	16	17.8	16.3 lbf	2179 rpm	15.4	4.2	816	493	56	0	0.02	3.82
	50%	10.7	12.2	10.8 lbf	2250 rpm	20.5	0.4	629	470	76	21	0.03	52.5
	0%	0	0	0	2333 rpm	21	N/R	254	119	50	0	0	N/R
970 RPM	0%	0	0	0	970 rpm	21	N/R	56	507	65	0	0	N/R

CALIBRATION CHECK

Pre-Test: Span Gas
Instrument Reading

897.5 1006 95.2
820 1015 109

Post-Test: Span Gas
Instrument Reading

997.5 1006 95.2
983 1009 98

Emissions Analyzer is an ECOM-AC, utilizing electro-chemical sensor cells. Probe was fitted 3 inches from exhaust manifold outlet, perpendicular to flow, in 1.5"NPT pipe.
Dynamometer is a Carl Schenck water-brake; BHP = lbf torque x RPM / 2000.

TECHNICAL DATA

QD-60-301 MC
MSHA PART 32 (SCHEDULE 24) CERTIFIED

General

Output (SAE-J 8166)

MSHA Part 32 Certified

Intermittent ratings	Gross BHP/min ⁻¹	57/3000, 48/2500
	Net BHP/min ⁻¹	53/3000, 47/2500
Mine ventilation Rqd.	CFM	5500/3000, 5000/2500
Number of cylinder		4
Displacement	cm ³	2.369
Moment of inertia GD ²	kgm ²	1.772
Speed droop		
Permanent for genset	%	4.5
Idle rpm	min ⁻¹	700
No load max rpm	min ⁻¹	<u>3260</u>

Cooling system

Water discharge volume of water pump at 80°C coolant temperature	lit/min	51/1500, 61/1800, 100/3000
Thermostat		
Opening temperature	°C (°F)	76.5 (170)
Fully opened temperature	°C (°F)	90 (194)
Top tank temperature		
Normal	°C (°F)	80 - 85 (176 - 185)
Max allowable	°C (°F)	95 (203)
Min. allowable radiator cap pressure	kg/cm ² (psi)	0.5(7)
Heat rejection	MJ/min	1.46/1500, 1.71/1800, 2.14/2500, 2.37/3000
	BTU/min	1384/1500, 1620/1800, 2025/2500, 2250/3000
Cooling water capacity (engine only)	lit.(Qts)	5.2 (5.5)

Air intake system

Inlet restriction

Air cleaner		Medium Duty	Heavy Duty
Dry type with precleaner	mmH ₂ O	250	-
Dry type with precleaner and safety element	mmH ₂ O	300	250
Max. allowable inlet restriction with dry air filter element	mmH ₂ O	635	635
Air flow	m ³ /min	151/1500, 181/1800, 302/3000	

Exhaust system

Exh. back pressure	mmHg	75	
Exh. pipe			
Min allowable internal diameter	mm	45	
Exh. temperature	°C	480/1500, 510/1800, 660/3000	
Exh. gas flow	m ³ /min	3.8/1500, 4.8/1800, 9.4/3000	

Lubrication system

Standard oil pan capacity	lit	5.5
Oil pressure	kg/cm ²	1.5 - 2.1 idle, 4.0/1500, 4.1/1800, 4.3/3000
Angularity limits of std oil pan	deg	Front up 35, Front down 35, Side to side 35

Fuel system

Feed pump suction head	m	1
Fuel pipe min. allowable internal diameter	mm	8

Electrical system

Max allowable resistance of starting circuit	mΩ	1
Recommended battery capacity	AH	12 - 100

Power take off

Front P T O	kgfm	7.5
-------------	------	-----

ISUZU DIESEL

OF NORTH AMERICA INC

NOVI, MICHIGAN

ENGINE PERFORMANCE

MODEL: **QD-60**

2.4L-4 CYL PRECOMBUSTION

APPLICATION: UNDERGROUND MINES

MSHA-PART 32-CERTIFIED

CONDITIONS: SAE-J816b-GROSS BHP

CURVE NO: 2.4-301-SG-161

SEPTEMBER 1, 1982

C240 SPECIFICATIONS

C240 SPECIFICATIONS					
Type	4 cylinder, four cycle, water-cooled, overhead valve, vertical in-line, indirect injected.				
Piston displacement	2369 cm ³ (145 CID)				
Performance (*Rating, SAE J816b)		PART 32 (Schedule 24)		PART 38 (Schedule 31)	
	RPM	BHP*	VENT (CFM)	BHP*	VENT. (CFM)
	3000 2500	57 48	5500 5000	52 43	5500 4500
Engine rotational direction	Counter clockwise as viewed from flywheel.				
Engine starting method	Electric starter motor; gear reduction type.				
Engine stop method	Fuel cut-off lever located on governor.				
Compression ratio	20:1				
Dimensions (LxWxH)	800mm (31.5 in) x 535mm (21.1 in) x 684mm (27.3 in)				
Air intake system	Naturally aspirated				
Engine mounting system	Four point support-Front; engine feet mounted to RH & LH side of block. Rear; RH & LH side FW HSG mt. pads.				
Firing order	1-3-4-2				
Fuel used	Diesel fuel				
Polarity & voltage of electric sys.	Negative grounding 12V.				
Lubrication oil capacity	Max 4.3 lit (4.5 qts) Min 3.5 lit (3.7 qts)				
Coolant capacity	5.2 lit (5.5 qts) engine only.				
Dry weight	223 kg (492 lbs)				

CRANKCASE	
Type	Cast iron; monoblock type. Five main bearing support. Aluminum alloy crankcase; removable type. Integrated water delivery pipe and lube oil gallery.
Cylinder liner	Chromard press-in liner, 1mm (.0394 in) thick. Chromium plated dry liner.

VALVE TRAIN	
Type	Cast iron; monoblock type. Overhead valve, two valves per cylinder, (one intake, one exhaust). Containing swirl combustion chambers, glow plugs & injections nozzle within the head assembly.
Cylinder head cover	Die cast aluminum alloy. Bolt mounted
Inlet Manifold	Cast aluminum alloy. Flange; two stud, ctr upwd. LH side engine.
Exhaust Manifold	Cast iron alloy. Flange; three stud, Frt upward LH side engine.
Thermostat housing	Die cast aluminum alloy mounted on front of cyl head.

DIESEL
ENGINES

ISUZU DIESEL

OF NORTH AMERICA INC

NOVI, MICHIGAN

EXHAUST FLOW AT FULL LOAD

C SERIES ENGINES

C223

C240

(QD-60)

CURVE NO: EX-1320

ENGINE RPM

DATE: FEB. 20, 1987

ISUZU DIESEL

OF NORTH AMERICA INC

NOVI, MICHIGAN

EXHAUST TEMPERATURE AT FULL LOAD

C SERIES ENGINES

C240 (QD-60)

DIESEL
ENGINES

ISUZU DIESEL

OF NORTH AMERICA INC

NOVI, MICHIGAN

INTAKE AIR FLOW FOR COMBUSTION

C SERIES ENGINES

C240

(QD-60)

ISUZU DIESEL ENGINE MODEL C240PW

(All specifications subject to change without notice.)

AMERICAN ISUZU MOTORS INC.

SK# 10-00-C001.00

goodman

GOODMAN EQUIPMENT CORPORATION

TO: WVU
FAX NO: (304) 293-6689
ATTN: Dan Carder
FROM: Brian Wiltjer
DATE: 11/11/97 REF: CAT 3306

TOTAL PAGES (Including Cover Page): **3**

IF NOT PROPERLY RECEIVED, PLEASE CONTACT THE ABOVE.

Dan,Following are the data sheets for the
engine.Brian

3306 PCNA

INDUSTRIAL ENGINE GENERAL INFORMATION SHEET

		SI METRIC	ENGLISH
General Engine Data	No. of Cylinders & Arrangement		IN-LINE SIX
	Bore & Stroke	121 x 152 mm x mm	4.75 x 6.00 in x in
	Displacement	10.5 L	638 cu in
	Compression Ratio		21 to 1
	Cycle		6
	Rotation-Facing Flywheel End		CCW
	Firing Order		1-5-3-6-2-4
Air Intake System	System Restriction Limits:		
	Max. Allowable w/Clean Dry Element	3.7 kPa	15 in H ₂ O
	Max. Allowable w/Dirty Element	6.2 kPa	25 in H ₂ O
	Cleaner Type		Dry 1 Stage
Control System	Governor Type		Hydra-Mechanical
	Shutoff Type		Manual
Cooling System (Engine Only)	Engine Coolant Capacity	15.9 L	18.8 qt
	Coolant Outlet Temperature (Max. Allowable)	93°C	210°F
	Coolant Inlet Temperature (Min. Allowable)	71°C	160°F
	Coolant Static Head (Max Allowable)	17.4 m	57 ft
	System Pressure (Min. Recommended)	48 kPa	7 psi
	Coolant System Regulator:		
	Start to Open Temperature	77-81°C	170-177°F
	Fully Open Temperature	90-94°C	198-201°F
Exhaust System	Exhaust Manifold Type		Dry
	Static Weight on Exhaust Connection (Max. Allowable)	23 kg	51 lb
	System Back Pressure (Max. Allowable)	8.5 kPa	34 in H ₂ O
Fuel System	Fuel System Type		Sleeve Meter
	Filter Type		Canister
	Priming Pump Type		Manual
	Fuel Supply Line Restriction (Max. Allowable)	20 kPa	6 in Hg
	Fuel Return Line Restriction (Max. Allowable)	20 kPa	6 in Hg
	Normal Fuel Pressure	240 kPa	35 psi
	Fuel Flow to Transfer Pump (Max.)	113.5 L/h	30.0 gph
Lube Oil System	Refill Volume with Filter Change	27 L	29 qt
	Sump Capacity:		
	Low Mark Level	18 L	20 qt
	High Mark Level	25 L	26 qt
	Oil Pressure SAE 10W30 Oil @ 93°C (210°F):		
	Normal Range	324-372 kPa	47-54 psi
	Min. @ Low Idle	69 kPa	10 psi
	Filter Type		Canister
	Oil Type Recommended		API CD
	Crankcase Ventilation Type		To Atmosphere
	Oil Cooler Type		Tube
Mounting System (Engine Only)	Length Overall	1270.0 mm	50.00 in
	Height Overall	1009.2 mm	37.93 in
	Width Overall	759.3 mm	29.87 in
	Unit Dry Weight	929.9 kg	2050 lb
	Flywheel Housing Size		SAE 1
	Static Bending Moment @ Rear Face		
	Flywheel Housing (Max. Allowable)	1356 N·m	12002 lb-in
	Dimensional Drawing Number		4W6360
Starting System (Engine with SAE 10W30 Oil)	Recommended Battery Capacity (Min.) for 90 sec. Cranking @ 0°C (32°F) and Above Ambient Temperature:		
	12 Volt Motor		1140 CCA
	24 Volt Motor		570 CCA

INDUSTRIAL ENGINE PERFORMANCE CURVE

MODEL 3306 PCNA

TM8737-00

112 kW @ 2200

SI METRIC

150 HP @ 2200

ENGLISH

Engine Speed rpm	Engine Power kW	Engine Torque N.m	Engine BMEP kPa	Fuel Rate L/h	BSFC g/kWh
2200	112	485	586	34.1	257.3
2000	106	506	607	30.7	245.7
1800	99	526	634	27.3	233.0
1600	91	542	656	25.4	234.8
1500	87	556	669	23.5	228.1
1400	83	564	676	22.0	225.1
1200	73	582	696	18.9	219.6
1000	60	569	683	15.5	220.8

Engine Speed rpm	Engine Power HP	Engine Torque LB FT	Engine BMEP PSI	Fuel Rate GAL/h	BSFC LB/HP h
2200	150	358	85	9.0	0.423
2000	142	373	88	8.1	0.404
1800	133	388	92	7.2	0.383
1600	122	400	95	6.7	0.388
1500	117	410	97	6.2	0.376
1400	111	416	98	5.8	0.370
1200	98	429	101	5.0	0.361
1000	80	420	99	4.1	0.363

Engine Speed rpm	Intake Manif Press kPa (gauge)	Intake Manif Temp °C	Exhaust Manif Temp °C	Exhaust Stack Temp °C	Air Flow m³/min	Exhaust Flow m³/min
2200	-0.6	29.4	638	616	9.6	28.7
2000	-0.6	29.4	604	582	8.9	25.5
1800	-0.6	29.4	593	571	8.2	23.2
1600	-0.6	29.4	649	627	7.4	19.7
1500	-0.6	29.4	546	524	6.9	18.4
1400	-0.6	29.4	643	621	6.4	17.0
1200	-0.6	29.4	521	499	5.4	13.6
1000	-0.6	29.4	510	488	4.4	11.1

Engine Speed rpm	Intake Manif Press IN.Hg (gauge)	Intake Manif Temp °F	Exhaust Manif Temp °F	Exhaust Stack Temp °F	Air Flow ft³/min	Exhaust Flow ft³/min
2200	-1.1	85	1180	1140	340	1012
2000	-1.0	85	1120	1080	314	899
1800	-1.0	85	1100	1060	291	819
1600	-1.0	85	1020	980	260	696
1500	-1.0	85	1015	975	243	649
1400	-0.9	85	1010	970	227	602
1200	-0.8	85	970	930	189	489
1000	-0.7	85	950	910	154	392

HEAT REJECTION DATA

Engine Speed rpm	Engine Power kW	Rejection to Coolant (Total) kW	Rejection to Exhaust (Total) kW	Rejection to Oil Cooler Coolant kW	Radiation to Atmosphere kW	Rejection to Aftercooler kW
2200	112	109				

HEAT REJECTION DATA

Engine Speed rpm	Engine Power HP	Rejection to Coolant (Total) Btu/min	Rejection to Exhaust (Total) Btu/min	Rejection to Oil Cooler Coolant Btu/min	Radiation to Atmosphere Btu/min	Rejection to Aftercooler Btu/min
2200	150	6200				