FUNDAMENTAL MODE FREQUENCY OF THE STORAGE RING SINGLE CELL CAVITY

May 6, 1992

Revised May 27, 1992

Yoon W. Kang

RF Group

Advanced Photon Source

The fundamental mode frequency of the prototype storage ring cavity has been measured with various port terminations and cavity temperatures. Since the highest tuned frequency of the prototype cavity with a tuner under the high RF power test condition is measured to be lower than the system specified frequency, a slight dimensional change in the cavity design is required for manufacturing future cavities. In addition to this, an extra dimensional correction is required to compensate the volume changes due to the tuner position and increased port sizes. In the following, the measured frequencies and the estimated frequency shift due to the volume changes are discussed. The correction to the internal dimension of the new cavity design based on the estimated frequency shift is also discussed.

I. Frequency Measurement Data

Measured frequencies of the prototype single cell cavity with various port terminations are as follows:

- (a) All four big ports are plugged. The plugs are flush to the cavity inner surface. Frequency is 352.60 MHz.
- (b) Four ports are terminated with a loop coupler, one tuner and two plates. The loop coupler is adjusted for matched input and then terminated with a matched load. The tuner is adjusted for the frequency of 351.93 MHz.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED 1

KIP

MASTER

RECEIVED

JUL 25 1995

OSTI

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

used in (1). These values are similar to the results reported in [2].

In each cover, there are sixteen small ports in two circular arrays. Each array has eight uniformly spaced ports. One array is close to the nose cone and the other is close to the rim. The eight small ports close to the rim will have much stronger interaction with the fundamental mode fields than with the ports close to the nose cone. Thus, the effects of the small ports close to the nose cones will be ignored.

Based on the measured frequency in case (c), the following steps are used to estimate the dimensional change required for new cavities:

1. The volume of the cavity is estimated to be 0.116 m^3 .
2. The volume of a small port which has a diameter of $5/8''$ and a height of $1.7''$ is $8.8 \times 10^{-6} \text{ m}^3$, thus sixteen ports will total $1.41 \times 10^{-4} \text{ m}^3$. Removing sixteen small ports will make $(\Delta f)_2 = 0.11 \text{ MHz}$. The resonant frequency is estimated to be $f_r = 351.60 + (\Delta f)_2 = 351.71 \text{ MHz}$.
3. The two big ports in the new cavities will be 102 mm high with diameter of 140 mm , increased from the 120 mm diameter used in the prototype cavity. This change will result in a volume increase of $8.364 \times 10^{-4} \text{ m}^3$. Increasing the diameter of two big ports will make $(\Delta f)_3 = -0.63 \text{ MHz}$. The resonant frequency becomes $f_r = 351.71 + (\Delta f)_3 = 351.08 \text{ MHz}$.
4. The six $1.37''$ ports with a height of $1.75''$ to be added in the cavity covers have a total volume of $3.63 \times 10^{-4} \text{ m}^3$. Installing them will give $(\Delta f)_4 = -0.28 \text{ MHz}$. These ports are assumed to be covered with blank flanges. The resonant frequency will be $f_r = 351.08 + (\Delta f)_4 = 350.80 \text{ MHz}$.

In normal operation of the cavities, maximum insertion of the plunger must be avoided. At the desired operating frequency, $f_o = 351.93 \text{ MHz}$, the tuner plunger needs to stay at around the midpoint $d = 25 \text{ mm}$. If the tuner is moved to the $d = 25 \text{ mm}$ position, the resonant frequency will be $f_r = 350.80 - \frac{(\Delta f)^t}{2} = 350.80 - 0.78 = 350.02 \text{ MHz}$ in the present prototype. This shows that the frequency of the

prototype cavity is lower than the optimum by ~ 1.9 MHz. Thus, new cavities must be machined with corrected dimensions to raise the frequency by 1.9 MHz. Note that the tunable frequency range with the plunger tuner will be $351.93 - (0.17 + 0.78) = 350.98 < f_r < 351.93 + 0.78 = 352.71$ MHz.

URMELT simulations show that a reduction of the cavity radius by 2.3 mm can raise the fundamental mode frequency by 1.9 MHz. The cavity dimension used in the URMELT program is shown in Table 1.

REFERENCES

- [1] Basic Design for the RF System of the SPring-8, K. Nakayama, H. Suzuki, E. Minehara, and T. Harami, JAERI-M 01-012
- [2] Penetration of RF Fields into Holes in Cavity Walls, R. M. Hutcheon, and R. A. Vokes, IEEE Trans. on Nuclear Science, Vol. NS-32, No. 5, October 1985

Figure 1 Storage Ring Single Cell Cavity
Tuner-Frequency Characteristic

TABLE 1. URMELT code input

```
$FILE LPLO=T LSAV=F ITEST=0 $END
$351.93 MHZ SPHERICAL CAVITY
$BOUN $END
$MESH NPMAX=10000 $END
#CAVITYSHAPE
0.0
0.0000 0.0000
0.3297 0.0000
0.3297 0.0278
-1. -0.1835
0.1462 0.2113
0.1290 0.2113
-1. -0.01421
0.1162 0.2032
0.0971 0.1626
-1. +0.01421
0.0700 0.1687
0.0700 0.300
0.0400 0.4259263
0.0000 0.4259263
0.0000 0.0000
9999. 9999.
$MODE NMODE=20 MROT=0 RWAKZ=0. FUP=2770 $END
$PLOT LCAVUS=T LMECU=T LMESH=T LFLE=T LFLH=T $END
$PRIN LER=F LEFI=F LEZ=F LHR=F LHFI=F LHZ=F
LPOWER=F LMATPR=F MODPR=6 LEZ2=F LPLE=F LPLH=F $END
```