



Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

Accelerator & Fusion Research Division

Presented at the Proceedings of the American Welding Society
Conference on Brazing, Los Angeles, CA, April 14-18, 1980

ON FABRICATION AND BRAZING OF 15A, 120 keV CONTINUOUS
DUTY ACCELERATOR GRID ASSEMBLIES

L. A. Biagi, G. W. Koehler, and J. A. Paterson

May 1980


RECEIVED
LAWRENCE
BERKELEY LABORATORY

JUL 9 1980

LIBRARY AND
DOCUMENTS SECTION

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.
For a personal retention copy, call
Tech. Info. Division, Ext. 6782.*



LBL-10558-02

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

ON FABRICATION AND BRAZING OF 15A, 120 keV CONTINUOUS
DUTY ACCELERATOR GRID ASSEMBLIES*

L. A. Biagi, G. W. Koehler, and J. A. Paterson

Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

The development of high intensity neutral beam injectors at the Lawrence Berkeley Laboratory has progressed from relatively low duty cycle, low energy devices to the next generation of continuous duty high energy units. The earlier pulsed versions were designed with edge cooled grid structures described in a previous publication.¹ The prerequisites set by the higher duty cycle devices no longer allow the edge cooling methods to be employed. Hollow molybdenum grid rails with deionized cooling water flowing at pressures of approximately 1.73×10^6 Pa- (250 PSI) at from 1.135 to 1.89 liters per minute (.3 to .5 GPM) are brazed to Type 304L stainless steel rail holders. Fig. 1.

Brazing Fixtures

All brazements are made on fixtures constructed of molybdenum and Type 304 stainless steel. These fixtures are designed to insure positive maintenance of relative positions of grid rails and rail holders while allowing for expansion at elevated temperatures during the braze cycle (Fig. 2). A "stop off" mixture of boron nitride - 325 mesh (15 gm) to 34 ml of glycerin is used to prevent diffusion bonds that can take place between clean close mating parts and screw threads under conditions of

*Work supported by U. S. Department of Energy, Office of Fusion Energy, under Contract No. W-7405-ENG-48.

high temperature in dry H_2 . These fixtures serve to position rail holders during the bellows brazing operation as well as fixturing the hollow molybdenum rails which are brazed to the rail holders in a subsequent step.

Treatment of Materials

Prior to brazing, the 304L SS rail holders are electro-polished to insure burr-free clean surfaces. The molybdenum rails and bellows are checked for vacuum integrity. After hydrostatic pressurization to 3.45×10^6 Pa (500 PSI) rails and bellows are again checked for vacuum leaks to a maximum of 1×10^{-10} std. atm. cc/sec with a helium mass spectrometer.

Molybdenum rails are straightened and stress relieved by clamping in a grooved molybdenum fixture and heating in a vacuum furnace to 850°C for 1/2 hour then at 1000°C for 1 hour. The rails are then etched to insure bright, clean surfaces for brazing. The etching is done as follows: 10-15 sec in a solution of H_2O , 6 volume, HNO_3 , 13 volume, and HF , 1 volume. Rinse in running tap water. Follow by 30 sec immersion in a solution of deionized H_2O 65 ml, CrO_3 20 gr H_2SO_4 (sp.gr. 1.84-Tech grade) 34 ml. (Add acid slowly while stirring). Sequential rinses of running tap water, 2 rinses in distilled water, and a final rinse in 190 proof ethyl alcohol are ultimately dried with a jet of dry N_2 gas.

Braze Fillers and Cycles

In the edge cooled design a Pd (25%) Cu (21%) Ag (54%) filler metal² was selected for its ability to wet molybdenum and its wide brazing range. Brazing was done in a dry hydrogen atmosphere at

925°-930°C, the approximate midpoint of the braze filler metal melting range for a period of 3 to 5 minutes. This was done to prevent blushing of the filler metal into adjacent rail slots that were not to be brazed. Although the filler metal does not become fully liquid under these conditions it does provide for an adequate mechanical and thermally effective joint without blushing problems.

The hollow rails have an additional requirement of vacuum and water-tight integrity. When the edge cooled brazing technique was used the braze failed the vacuum integrity test. At this point, after consultation with the manufacturer of the braze filler metal, it was decided to take the braze temperature to 20°C above the liquidus point of 950°C. Subsequent brazes passed all the vacuum and pressure tests. However, blushing along the rail did occur and had to be removed by controlled acid etching which did not compromise the joint integrity. This is done by using the previously mentioned etching process for 5 to 10 seconds. This procedure was done just prior to final assembly of the grid modules to insure clean surfaces. Extreme cleanliness is required to hold the high voltage gradients present across the grid structure. A 120-kV accelerator requires four different grid assemblies. Each consists of two pairs of rail holder modules (Fig. 3).

Prior to brazing of the grid rails to the rail holders, stainless steel bellows are brazed to each finger of the rail holder (Fig. 4). This was done initially using a Ni (18%) Au (82%)² eutectic filler metal in a dry hydrogen atmosphere at 970°C for 3 to 5 minutes. In order to obtain a wider spread between the melting point of the stainless steel brazement and the subsequent molybdenum brazement, a change was made to a

Pd (10) Ag(90) brazing filler metal which is brazed at 1075°C for the same time period. This alloy produces an excellent brazement and has economic benefits as well.

Conclusions


This procedure has resulted in the joining of two materials, molybdenum and 304SS, with substantially different thermal coefficients of expansion into a unique high toleranced structure. This design will serve as a test for an accelerator structure 4 times larger capable of 65 amperes at 120 keV currently under construction.

Acknowledgments

The authors wish to thank all of those who were instrumental in making this development a success. In particular, Carson Haines and his group who were responsible for the machining of the highly toleranced parts required for the various grid components and fixtures. Also, Harry Smith and Arthur Hollister for their contributions, and everyone involved at Pyromet Industries for their cooperation and assistance in hydrogen brazing of the components.


References

1. L. A. Biagi and J. A. Paterson, "On Fabrication and Design of 120 keV, 65A, 0.5 sec Accelerator Grid Assemblies," The Seventh Symposium on Engineering Problems of Fusion Research, Knoxville, TN 1977 Vol. II, p. 1413.
2. Western Gold & Platinum Co., Division of GTE Sylvania, Belmont, CA 94002.




CBB 7910-14496

Fig. 1 - Grid modules shown as installed in accelerator assembly




CBB 797-9261

Fig. 2 - Grid module on braiding fixture



CBB 7912-16490

Fig. 3 - Source grid module assembly



CBB 802-2377

Fig. 4 - Bellows to be brazed to rail holders on fixture