MASTER

EXTERNAL TRANSMITTAL AUTHORIZED

OAK RIDGE NATIONAL LABORATORY

Operated by

UNION CARBIDE NUCLEAR COMPANY

Division of Union Carbide Corporation

Post Office Box X

Oak Ridge, Tennessee

2-9395

ORNL
CENTRAL FILES NUMBER

59-3-112

COPY NO. [REDACTED]

DATE: March 25, 1959

SUBJECT: Status Report--Spectrophotometry
of Molten Fluoride Salts

TO: W. R. Grimes

FROM: Copies: See Distribution
J. C. White

JPY-24

ABSTRACT

Progress that has been made in the field of spectrophotometry of molten fluoride salts is summarized in this report. The high-temperature cell assembly which was designed and fabricated for use in this work is described, as are the various types of sample containers that have been used. Spectra of nickel fluoride, cobalt fluoride, chromic fluoride, and uranium tetrafluoride in LiF-NaF-KF (46.5 - 11.5 - 42 mole per cent) are presented.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States nor the Commission nor any person acting on behalf of the Commission makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights.

Notwithstanding any limitation with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, persons acting on behalf of the Commission include any employee or contractor of the Commission or employee of such contractor, as the case may be, who is engaged in or connected with the Commission or employee of such contractor, in the actual line of duty or in connection with the Commission or employee of such contractor, in the actual line of duty or in connection with the Commission or employee of such contractor, in the actual line of duty or in connection with the Commission or employee of such contractor.

NOTICE

This document contains information of a preliminary nature and was prepared primarily for internal use at the Oak Ridge National Laboratory. It is subject to revision or correction and therefore does not represent a final report.

The information is not to be abstracted, republished or otherwise given wide dissemination without the approval of the ORNL Patent Department.

RELEASE APPROVED
BY PATENT BRANCH

1-11-61 [Signature]
DATE SIGNATURE

3-1

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

STATUS REPORT--SPECTROPHOTOMETRY OF MOLTEN FLUORIDE SALTS

J. P. Young

In this report the progress that has been made in the studies which are being carried out to investigate the possibilities of spectrophotometric measurements in molten fluoride salts is summarized. The equipment that was developed for making spectral studies in molten fluoride salts is discussed and the results that have been obtained to date with the apparatus are presented.

The solvent which has been considered to date has been the eutectic of LiF-NaF-KF, "Flinak," (46.5 - 11.5 - 42 mole per cent) which melts at approximately 460°C. Other molten fluoride solvents will be studied as the work progresses. The immediate objectives of the present program are to obtain spectra and absorption coefficients of uranium, iridium, chromium, nickel, cobalt, vanadium, and molybdenum in the various oxidation states that are believed to be in existence in the molten fluoride salt mixture.

Apparatus

The high-temperature cell assembly, which was designed and fabricated for spectral work with molten fluoride salts, (7) is shown in Figure 1. The assembly is used with a Cary Recording Spectrophotometer, Model 14-M. The Cary spectrophotometer can be converted from normal to high-temperature use in less than a minute. The furnace is composed of two fused-silica plates, wound with platinum wire, which are so positioned in a solid, nonmetallic, insulating block (Davite) that the fluoride salt container can be placed between the heaters. This cavity is also of proper size to accommodate a normal 1-cm spectrophotometer cell. The furnace block is surrounded by "Fibrefrac" insulation and enclosed in a copper cylinder which is water cooled. The whole assembly is suspended from a plate which fits the top of the sample compartment of the Cary spectrophotometer. Suitable light ports allow complete transmission of the available light through the high-temperature cell assembly. The small removable lid permits access into the furnace. The various ports in this lid are for the introduction of thermocouples, an inert gas and for other functions.

The two heating elements are connected in series so that it is possible to heat the cavity between the heaters to a temperature of 800°C within 30 minutes. To attain this temperature, a current of seven amperes is supplied by applying 26 volts to the heaters. No automatic control of the temperature of the furnace has been incorporated into the design of the high-temperature cell assembly as yet. This could easily be done by including proper electronic components, but the nature of the present phase of this project does not seem to warrant this modification. Manual control of the voltage supplied to the heater elements is quite adequate to maintain

control of the temperature of the furnace within ± 10 per cent. The water jacket on the side of the copper cylinder keeps the outer shell of this assembly below room temperature. Above 700°C some thermal radiation is noted through the quartz window, and only the temperature of the removable lid rises to the extent of about 60 to 80°C .

Several types of sample containers have been used to contain molten fluoride salts for spectral work.⁽⁷⁾ A transmission cell was fabricated from crystalline magnesium oxide, MgO , by ultrasonic machining techniques and then rendered transparent by lapping and polishing. This cell is useful for spectrophotometric measurements down to wavelengths of 300 to 320 $\text{m}\mu$. Crystalline magnesium oxide, MgO , is inert to molten alkali fluorides and fairly inert to alkali fluoride mixtures which contain fluorides of transition elements with low atomic weights, such as iron and nickel, in low concentrations. Magnesium oxide is not inert to all fluoride salts; for example, uranium or zirconium fluorides attack this oxide quite readily.

Confining the molten fluoride salt as a pendant drop is another possible approach⁽⁶⁾ to the problem of suitably containing these corrosive melts for spectral investigation. Although it is recognized that the optical problems associated with a lens-shaped drop of liquid are indeed formidable, spectrophotometric measurements of pendant drops of molten fluoride salts appear to be feasible. A ring of platinum wire seems to be an ideal pendant drop container; however, a ring of reasonable size, 0.5 to 0.7 cm in diameter, must be maintained in a horizontal plane in order to hold a stable drop of liquid. The physical arrangement of the Cary spectrophotometer is such that pendant drops can be maintained only in a vertical position. To hold a pendant drop of liquid in this position it is necessary to confine the liquid in a closely wound coil of platinum wire. A later innovation of the coil which has proved to be extremely useful is the replacement of the coil with a platinum tube, $3/16$ -inch in diameter and 1 -cm long.

The proposed optical arrangement of a spectrophotometer designed specifically for pendant drops is shown in Figure 2. The drop, contained in a ring, is positioned at the focus of a light beam as shown. With such an arrangement the optical effects of a lens-shaped drop of sample are minimized (and for all practical purposes, eliminated). The optical design of the Cary Model 14-M spectrophotometer is such that the light beam passes horizontally through the sample compartment and is focused there. By locating the pendant drop in the focal plane of the light beam and by allowing only the light which passes through the sample to impinge on the detector, a semblance of the ideal optical design shown in Figure 2 can be obtained. In order to achieve a suitable optical balance when the Cary spectrophotometer is used as a pendant drop spectrophotometer, it is necessary to mask out about 90 to 95 per cent of the reference beam of the instrument. This is done with light absorbing screens. The design of the Cary spectrophotometer is such that it can be operated adequately under these modified conditions.

The advantages of using a pendant drop of molten fluoride salts for spectrophotometric measurements are many. Corrosion effects of the fluoride ion are definitely minimized. The containers are easily cleaned by dipping them in boiling sulfuric acid for a few minutes. The range of wavelengths available for spectral study of pendant drops should be limited only by the transmission of the solvent. It does not appear that this ideal limit has been achieved as yet with the Cary spectrophotometer, but spectral responses of molten fluoride solutions have been obtained from 2.5 μ down to 250-260 μ . The containers are easily filled by immersing them in a liquid and then withdrawing the sample. The length of the light path through the solution poses a rather serious problem with this type of container since the size of the drop is not reproducible and is somewhat difficult to measure. For this reason, quantitative spectrophotometric determinations cannot be made until suitable methods can be devised for determining the thickness of the pendant drop. Several ways of performing this task are being considered, such as the use of internal standards, photographing the drop (for use with platinum ring samples only) and geometrical calculations concerned with the platinum tube samples when the weight and density of the sample solution contained in the tube are known.

Some of the various containers for molten fluoride salts, a didymium glass bead in a platinum ring, a platinum coil, platinum ring, and crystalline magnesium oxide cell, are shown in Figure 3. Each of the containers designed to support a pendant drop is attached to a ceramic rod, as shown in the drawing. For spectral studies, this ceramic rod is positioned and extends through the center port of the lid of the cell assembly. The container is maintained in proper position by a suitable clamp which is attached to that portion of the ceramic rod that protrudes through the lid.

The didymium glass bead was used to check the feasibility of obtaining spectra of a pendant drop of sample. Aqueous solutions of neodymium chloride have also been used for this purpose in the various pendant drop containers. A typical example of the spectral response that was obtained for the didymium glass bead is shown in Figure 4. The bead was contained in the cold, high-temperature furnace assembly. The spectrum of a didymium glass plate is also shown in Figure 4 for comparison. Over the region of wavelengths from 350 to 620 μ , the spectra are essentially identical, both with respect to wavelength of maximum absorbance and to the ratio of the various peaks heights P_i to the height of the peak at 530 μ . These data are shown in Table I.

Table I

Comparison of the Absorption Spectra of a Didymium
Glass Plate and Bead

Instrument: Cary Recording Spectrophotometer, Model 14 M

Wavelength of Absorbance Maximum, $m\mu$		Ratio of Peak Heights $P_1/P_{530\ m\mu} \times 10^3$		
<u>Plate</u>	<u>Bead</u>	<u>Plate</u>	<u>Bead</u>	<u>Difference</u>
		(A)	(B)	(B-A)
530	529	-	-	-
527	525	858	850	- 8
514	513	587	599	+ 12
482	480	495	519	+ 24
479	478	514	529	+ 15
473	472	487	495	+ 7
447	445	398	385	- 13
442	438	423	407	- 16
432	431	386	375	- 11
403	402	152	145	- 7

The magnitude of the peaks is different due to the difference in thickness of the two samples. The optical response shown in the bead spectra from 620 to 700 $m\mu$ arises from the use of the Cary instrument. This effect can be eliminated by making various instrumental adjustments.

Absorption Spectra of Molten Fluoride Salts

The spectra of Flinak and NiF_2 in Flinak at 500°C are shown in Figure 5. Both of these spectra were obtained with the melt in the MgO cell (internal dimension, 0.5 cm). The optical cut-off of the MgO cell is observed at approximately 310 $m\mu$. Nickel fluoride exhibits a maximum absorbance at 434 $m\mu$, and a very insensitive, broad peak at 850 $m\mu$. Gruen⁽⁴⁾ has reported that $\text{Ni}(\text{NO}_3)_2$ in molten $\text{LiNO}_3\text{-KNO}_3$ (184°C) exhibits peaks at 425 and 775 $m\mu$. Boston and Smith⁽²⁾ have reported that NiCl_2 (as a complex anion) in molten LiCl-KCl at temperatures up to 600°C has four peaks between 512 and 695 $m\mu$ and a tremendously sensitive peak at 260 $m\mu$. Aqueous nickel solutions in 1 M HClO_4 exhibit peaks at 390 and 710 $m\mu$.⁽¹⁾

The absorbance index of NiF_2 at 434 $m\mu$ is of the order of 20 to 30 based on moles of Ni per 1000 g of solution. This expression of sensitivity will be referred to as a molal absorbance index.

In Figure 6 is shown the spectrum of CoF_2 in Flinak at a temperature of 500°C . The melt was contained in a platinum tube. The actual path length of the solution was of the order of 0.5 cm. Cobalt fluoride exhibited two peaks, at 510 and 580 $m\mu$. The molal absorbance index of the CoF_2 peak at 580 $m\mu$ is probably of the order of 10 or 20. Gruen has reported that $\text{Co}(\text{NO}_3)_2$ in molten $\text{LiNO}_3\text{-KNO}_3$ at 184°C has one peak at 560 $m\mu$.⁽¹⁾

The spectrum of CrF_3 in Flinak at a temperature of 650°C is shown in Figure 7. The sample was contained in a platinum tube. Two peaks are observed, at 445 and 685 $\text{m}\mu$. In order to dissolve CrF_3 it was necessary to keep the solution fairly hot, and at the present time the actual concentration of chromium in the melt is not known. From the data obtained, it is expected, however, that the molal absorbance index will be above 10. In aqueous solution the chromium (III) has two peaks, at 410 and 575 $\text{m}\mu$.⁽³⁾

The spectral response of UF_4 in Flinak at 550°C is shown in Figure 8. The melt was contained in a platinum coil. Well defined peaks were observed for UF_4 at 420, 470, 522, 600, and 1100 $\text{m}\mu$. From an inspection of Figure 8 a discrepancy is to be noted in the spectra of uranium at two concentrations within the wavelength region from 550 to 700 $\text{m}\mu$. It appears probable that the peak for 10 per cent U at 600 $\text{m}\mu$ is in error and that the actual peak is at 670 $\text{m}\mu$, as shown in the spectrum for a 1 per cent solution of uranium. More work is planned to resolve this question. The 1100- $\text{m}\mu$ peak for tetravalent uranium is well known and corresponds to a UCl_4 ⁽⁵⁾ peak in LiCl-KCl .

The spectra of these solutes and other solutes of interest will be studied more critically, as suitable experimental techniques are evolved, in order to obtain accurate values for spectrophotometric sensitivity. Studies are also planned to investigate the various parameters involved in these spectral measurements, such as the effect of temperature and solvent composition. Possible methods for measuring the temperature of molten fluoride salts more accurately in the high-temperature cell assembly are being evaluated. The temperatures reported in this section were obtained by applying empirical corrections to a measurement of the temperature of the Lavite furnace block and are only approximate, $\pm 50^\circ\text{C}$.

The possibility of using various chromogenic reagents as a basis for possible colorimetric determinations in molten fluoride salts is being considered. Obviously the chromogenic reagent (probably organic in nature) would have to be thermally stable up to temperatures of at least 460°C . One class of compounds which meets this specification is the phthalocyanines. Phthalocyanine and metal-phthalocyanine dyes are thermally quite stable. They sublime only at temperatures exceeding 500°C . They are not selective reagents; however, phthalocyanine exhibits two peaks at 660 and 700 $\text{m}\mu$, and when a metal such as copper, magnesium, iron, etc. is present, the two former peaks disappear and only one peak is observed at 680 $\text{m}\mu$. Although magnesium-phthalocyanine is thermally stable, it is not chemically stable and is decomposed by cold sulfuric acid. Phthalocyanine is not soluble in Flinak or even LiCl-KCl ; however, possible additions to the molecule are being considered to make the resultant compound more soluble. Magnesium-phthalocyanine was found to be soluble in molten phthalic anhydride; however, as shown in Figure 9, apparently the magnesium compound is decomposed in this solvent to yield free phthalocyanine. This decomposition is indicated by the recognizable phthalocyanine spectra. When cuprous ion was added to the same melt, copper-phthalocyanine was formed as indicated by the spectrum. These and other possible high-temperature chromogenic reagents will be studied further as time and possibilities will allow.

References

1. R. Bastian, Anal. Chem. 23, 580 (1951).
2. C. R. Boston and G. P. Smith, J. Phys. Chem. 62, 409 (1958).
3. S. S. Cooper, Anal. Chem. 19, 254 (1947).
4. D. M. Gruen, J. Inorg. and Nuclear Chem. 4, 74 (1957).
5. D. M. Gruen, S. Fried, P. Graf, and R. L. McBeth, Second United Nations International Conference on the Peaceful Uses of Atomic Energy, A/Conf. 15/P/940, July 7, 1958.
6. L. L. Merritt, Jr., Private Communication to J. P. Young, May, 1958.
7. J. P. Young, Anal. Chem. Ann. Prog. Rep. Dec. 31, 1958, ORNL-2662, p. 70.

J. P. Young

J. P. Young

UNCLASSIFIED
ORNL-LR-DWG. 34793

Figure 1

Figure 2

Proposed Optical Design for Pendant Drop Spectrophotometer

Figure 3. Sample Containers for use in Spectrophotometric Studies.

Figure 4. Absorption Spectra of Didymium Glass

Instrument: Cary Recording Spectrophotometer, Model 14 M
Reference Medium: Air

3-11

Figure 5. Preliminary Spectra of NiF_2 in LiF-NaF-KF

Figure 6. Preliminary Spectra of CoF_2 in LiF-NaF-KF

Figure 7. Preliminary Spectra of CrF_3 in LiF-NaF-KF

CRNL-LF-DMG-37332
UNCLASSIFIED

-11-

3-14

Figure 8. Preliminary Spectra of UF_4 in $LiF-NaF-KF$

Figure 9

Absorption Spectra of Some Metal Phthalocyanines in
Molten Phthalic Anhydride

3-16

Distribution

1. W. R. Grimes	14. M. A. Marler
2. G. E. Boyd	15. P. F. Thomason
3. M. T. Kelley	16. L. T. Corbin
4. F. F. Blankenship	17. A. E. Cameron
5. M. Blander	18. D. J. Fisher
6. C. D. Susano	19. S. A. Reynolds
7. J. C. White	20. G. W. Leddicotte
8. O. Menis	21. C. Feldman
9. L. J. Brady	22. T. E. Willmarth
10. J. P. Young	23. ORNL-RC
11. A. S. Meyer.	24-26. Laboratory Records
12. J. A. Norris	27. E. J. Murphy
13. H. P. House	28. M. J. Skinner

DO NOT PHOTOSTAT