Dr-2087

ORNL/TM-5266

**CACA-2: Revised Version of CACA—
A Heavy Isotope and Fission-Product
Concentration Calculational Code for
Experimental Irradiation Capsules**

E. J. Allen

MASTER

OAK RIDGE NATIONAL LABORATORY

OPERATED BY UNION CARBIDE CORPORATION FOR THE ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
Price: Printed Copy \$5.00; Microfiche \$2.25

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in the United States of America Available from
National Technical Information Service
U S Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
Price Printed Copy \$5 00, Microfiche \$2 25

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

ORNL/TM-5266

UC-77 — Gas-Cooled Reactor
Technology

Contract No. W-7405-eng-26

Reactor Division

CACA-2: REVISED VERSION OF CACA — A HEAVY ISOTOPE
AND FISSION-PRODUCT CONCENTRATION CALCULATIONAL
CODE FOR EXPERIMENTAL IRRADIATION CAPSULES

E. J. Allen

FEBRUARY 1976

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

NOTICE: This document contains information of a preliminary nature and was prepared primarily for internal use at the Oak Ridge National Laboratory. It is subject to revision or correction and therefore does not represent a final report.

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37830
operated by
UNION CARBIDE CORPORATION
for the
U.S. ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

Discarded to be used for other purposes

U.S. ATOMIC ENERGY COMMISSION
MAJOR CONTRACTOR'S RECOMMENDATION FOR
DISPOSITION OF SCIENTIFIC AND TECHNICAL DOCUMENT

*See Instructions on Reverse

1. AEC Report No. ORNL/TM-5266	3. Title CACA-2: Revised Version of CACA - A Heavy Isotope and Fission-Product Concentration Calculational Code for Experimental Irradiation Capsules, by E. J. Allen
2. Subject Category No. UC-77	
4. Type of Document ("X" one) ☒ a. Scientific and Technical Report ☐ b. Conference paper: Title of conference _____ Date of conference _____ Exact location of conference _____ ☐ c. Other (Specify, Thesis, Translation, etc.)* _____	
5. Copies Transmitted ("X" one or more) ☒ a. Copies being transmitted for standard distribution by AEC-TIC. ☐ b. Copies being transmitted for special distribution per attached complete address list.* ☐ c. Two completely legible, reproducible copies being transmitted to AEC-TIC.	
6. Recommended Distribution ("X" one) ☒ a. Normal handling (after Patent clearance): no restraints on distribution except as may be required by the security classification. ☐ b. Make available only to U.S. Government agencies and their contractors. ☐ c. Make available only within AEC and to AEC contractors. ☐ d. Make available only within AEC. ☐ e. Make available only to those listed in item 12 below. ☐ f. Other (Specify)* _____	
7. Recommended Announcement ("X" one) ☒ a. Normal procedure may be followed.* ☐ b. Recommend following announcement limitations: _____	
8. Reason for Restrictions Recommended in 6 or 7 above. ☐ a. Preliminary information. ☐ b. Prepared primarily for internal use. ☐ c. Other (Explain) _____	
9. Patent Clearance ("X" one) ☒ a. AEC patent clearance has been granted by responsible AEC patent group. ☐ b. Document has been sent to responsible AEC patent group for clearance.	
10. National Security Information (For classified document only; "X" one) ☐ a. Document does contain national security information other than restricted data. ☐ b. Document does not contain national security information other than restricted data.	
11. Copy Reproduction and Distribution a. Total number of copies reproduced 235 b. Number of copies distributed outside originating organization _____	
12. Additional Information or Remarks (Continue on separate sheet, if necessary)	

13. Submitted by (Name and Position) (Please print or type)*

N. T. Bray, Classification Officer

14. Organization

Oak Ridge National Laboratory

15. Signature

N. T. Bray

16. Date

February 2, 1976

INSTRUCTIONS

Who uses this Form: All AEC contractors except those specifically instructed by their AEC contract administrator to use the shorter Form AEC-427.

When to Use: Submit one copy of this Form with each document which is sent to AEC's Technical Information Center (TIC) in accordance with the requirements of AEC Manual Chapter 3201.

Where to send: Forward this Form and the document(s) to:

USAEC - TIC
P.O. Box 62
Oak Ridge, TN 37830

Item instructions:

- Item 1.** The first element in the number shall be an AEC-approved code to be determined as follows: (a) The responsible field office may request TIC approval of a unique code for a contractor, e.g., BNL, BMI, ORNL, etc.; (b) A program division may request TIC approval of a unique code for a program or series of reports, e.g., PNE, VUF, etc.; (c) An operations office may instruct a contractor to use the code approved for the operations office, i.e., COO, ORO, IDO, SRO, SAN, ALO, RLO, NVO; and (d) Program divisions shall use the code WASH for reports which they themselves prepare unless there is reason to use some other approved code.

The code shall be followed by a sequential number, or by a contract number plus a sequential number, as follows: (a) Contractors or programs with unique codes may complete the report number by adding a sequential number to the code, e.g., ORNL-101, ORNL-102, etc.; or PNE-1, PNE-2, etc.; or they may add the identifying portion of the contract number and a sequential number, e.g., ABC-2105-1, ABC-2105-2, etc.; (b) Contractors using the operations office code shall complete the report number by adding the identifying portion of the contract number and a sequential number, e.g., COO-2200-1, COO-2200-2, etc.; (c) Subcontractor reports shall be identified with the code used by the prime contractor; and (d) Program divisions using the WASH code shall complete the report number by adding a sequential number which they request from the Library Branch, Division of Headquarters Services.

- Item 2.** Insert the appropriate subject category from TID-4500 ("Standard Distribution for Unclassified Scientific and Technical Reports") or M-3679 ("Standard Distribution for Classified Scientific and Technical Reports") for both classified and unclassified documents, whether or not printed for standard distribution.
- Item 3.** Give title exactly as on the document itself unless title is classified. In that case, omit title and state "classified title" in the space for item 3.
- Item 4.** If box c is checked, indicate type of item being sent, e.g., thesis, translation, etc.
- Item 5.** a. If box a is checked, the number of copies specified for the appropriate category or categories in M-3679 or TID-4500 shall be forwarded to TIC for distribution.
b. If box b is checked, complete address list must be provided TIC.

c. If box c is checked, at least one copy shall be original ribbon or offset and be completely legible. A clear carbon copy is acceptable as a second reproducible copy.

- Item 6.** If box a is checked for an unclassified document, it may be distributed by TIC (after patent clearance) to addressees listed in TID-4500 for the appropriate subject category, to libraries in the U.S. and abroad, which through purchase of microfiche maintain collections of AEC reports, and to the National Technical Information Service for sale to the public.

If box a is checked for a classified document, it may be distributed by TIC to addressees listed in M-3679 for the appropriate subject category.

If a box other than a is checked, the recommended limitation will be followed unless TIC receives other instructions from the responsible AEC program division.

Box f may be checked in order to specify special instructions, such as "Make available only as specifically approved by the program division," etc.

- Item 7.** a. Announcement procedures are normally determined by the distribution that is to be given a document. If box a in item 6 is checked for an unclassified document, it will normally be listed in the weekly "Accessions of Unlimited Distribution Reports by TIC" (TID-4401) and may be abstracted in "Nuclear Science Abstracts" (NSA).

A classified document, or an unclassified document for which box b, c, d, e, or f, in item 6 is checked, may be cited with appropriate subject index terms in "Abstracts of Limited Distribution Reports" (ALDR).

b. If the normal announcement procedures described in 7a are not appropriate check 7b and indicate recommended announcement limitations.

- Item 8.** If a box other than a is checked in item 6, or if 7b is checked, state reason for the recommended restriction, e.g., "preliminary information," "prepared primarily for internal use," etc.

- Item 9.** It is assumed that there is no objection to publication from the standpoint of the originating organization's patent interest. Otherwise explain in item 12.

- Item 10.** If box a is checked, document cannot be made available to Access Permit holders (Code of Federal Regulations, 10 CFR, Part 25, subpart 25.6); if box b is checked, TIC will determine whether or not to make it available to them.

- Item 11.** Self explanatory.

- Item 12.** Use this space if necessary to expand on answers given above, e.g., item 6f and item 8.

- Item 13.** Enter name of person to whom inquiries concerning the recommendations on this Form may be addressed.

- Item 14-16.** Self explanatory.

CONTENTS

	<u>Page</u>
ABSTRACT	1
INTRODUCTION	1
CALCULATIONAL MODEL	2
OUTPUT	6
PROGRAM LISTING AND SAMPLE PROBLEM	6
Input Instructions	7
Listing of Program and Sample Problem Input	12
Sample Problem Output	19
ACKNOWLEDGMENTS	27
REFERENCES	27

CACA-2: REVISED VERSION OF CACA — A HEAVY ISOTOPE
AND FISSION PRODUCT CONCENTRATION CALCULATIONAL
CODE FOR EXPERIMENTAL IRRADIATION CAPSULES

E. J. Allen

ABSTRACT

This report describes a computer program which calculates nuclide concentration histories, power or neutron flux histories, burnups, and fission-product birthrates for fueled experimental capsules subjected to neutron irradiations. Seventeen heavy nuclides in the chain from ^{232}Th to ^{242}Pu and a user-specified number of fission products are treated. A fourth-order Runge-Kutta calculational method solves the differential equations for nuclide concentrations as a function of time. For a particular problem, a user-specified number of fuel regions may be treated. A fuel region is described by volume, length, and specific irradiation history. A number of initial fuel compositions may be specified for each fuel region. The irradiation history for each fuel region can be divided into time intervals, and a constant power density or a time-dependent neutron flux is specified for each time interval. Also, an independent cross-section set may be selected for each time interval in each irradiation history. The fission-product birthrates for the first composition of each fuel region are summed to give the total fission-product birthrates for the problem.

Key words: computer codes, calculations, in-pile tests, irradiation, burnup, fission products, thermal power, neutron flux.

INTRODUCTION

The CACA program¹ was originally written to alleviate problems in computer turn-around time, cross-section inaccessibility, large output in an undesired form, time-step limitations, power treatment limitations, and fission-product limitations of previous depletion-burnup analysis computer programs such as ORIGEN² or FABGEN.³ However, the original CACA code lacked the flexibility to handle the wide variety of problems that were encountered, and the input instructions were difficult to follow. CACA-2 was written to provide greater flexibility and the input instructions were clarified.

Some of the options in CACA-2 are better understood by considering a typical fueled irradiation test. The HRB capsules are designed to test candidate fuels for the High-Temperature Gas-Cooled Reactor Program. The capsules are irradiated for several cycles in a permanent beryllium facility of the High Flux Isotope Reactor (HFIR) to obtain partial fuel burnup after which they are placed in a HFIR removable beryllium facility (with higher flux levels) for the remaining irradiation. Each HRB capsule contains several fuel sticks with each having a unique composition. The magnitude and the time dependence of the neutron flux is different for each fuel stick. When the capsule is moved from the permanent beryllium facility to the removable beryllium facility, the neutron flux magnitude and spectrum changes. As the capsule is operating, fission-product gases escape from the fuel sticks and are measured to provide an indication of the extent of fuel particle failure in the capsule. Upon completion of the irradiation test, the fuel sticks are removed from the capsule and are inspected to evaluate their performance.

Accurate information about the irradiation history is required to determine the fuel particle failure and to evaluate the performance of the fuel. This includes nuclide concentrations, power histories, fission-product birthrates, and burnups. CACA-2 can be used to model the exact irradiation history and to calculate these various parameters for each fuel stick throughout the irradiation. CACA-2 can also be used in the design of the capsule by calculating power histories for proposed initial fuel loadings.

CALCULATIONAL MODEL

The set of differential equations which describe the nuclide concentrations as a function of time can be put into the form:

$$\frac{dN_i}{dt} = F_i(t, N_1, N_2 \dots N_m) ,$$

where

N_i = concentration of i th nuclide,

t = time,

M = total number of nuclides.

Several calculational methods were investigated that would solve the differential equations for the nuclide concentrations as a function of time. It was desired that the method be fast and accurate but yet flexible enough to solve the equations given either the neutron flux history or the power history. The method had to allow for neutron flux time variations in flux calculations and the dependence of power on nuclide concentrations in power calculations. A fourth-order Runge-Kutta method was selected based on this method's flexibility to solve the two types of problems. The length of the time step in the Runge-Kutta method was adjusted to make the calculations as fast as possible without impairing the accuracy. A time step of 6 hr was thus selected as optimal.

The following formulas are used in the Runge-Kutta fourth-order method to evaluate the nuclide concentrations with time:

$$N_i^{n+1} = N_i^n + (K_{1i} + 2K_{2i} + 2K_{3i} + K_{4i})/6 ,$$

where

$$K_{1i} = h \cdot F_i(nh, N_1^n, \dots, N_M^n),$$

$$K_{2i} = h \cdot F_i\left(nh + \frac{h}{2}, N_1^n + \frac{K_{11}}{2}, \dots, N_M^n + \frac{K_{1M}}{2}\right),$$

$$K_{3i} = h \cdot F_i\left(nh + \frac{h}{2}, N_1^n + \frac{K_{21}}{2}, \dots, N_M^n + \frac{K_{2M}}{2}\right),$$

$$K_{4i} = h \cdot F_i(nh + h, N_1^n + K_{31}, \dots, N_M^n + K_{3M}),$$

and

h = length of time step,

n = n th time step.

Seventeen heavy nuclides from ^{232}Th to ^{242}Pu were selected so that all the significant neutron fission and capture reactions in conventional fuels would be treated. The heavy nuclide chain modeled by CACA-2 is presented in Fig. 1.

Fig. 1. The heavy nuclide chain modeled by CACA-2.

The number of fission products is user specified, and the concentration of each fission product can be described by the equation:

$$\frac{dN_p}{dt} = \sum_{j=1}^{NG} \sum_{i=1}^8 Y_i N_i \sigma_{ij} \phi_j - \lambda_p N_p - N_p \sum_{j=1}^{NG} \sigma_{pj} \phi_j ,$$

where

- N_p = fission product concentration,
- Y_i = yield from i th fissionable nuclide,
- N_i = concentration of i th fissionable nuclide,
- σ_{ij} = fission cross section of i th fissionable nuclide for j th group,
- ϕ_j = neutron flux for j th group,
- λ_p = decay constant for fission product,
- σ_{pj} = absorption cross section of fission product for j th group,
- NG = total number of neutron energy groups.

Eight of the seventeen heavy nuclides are assumed fissionable which accounts for the sum from 1 to 8 in the above equation. If the half life for a particular fission product is less than the time step (6 hr), the equilibrium concentration of the fission product is calculated (to avoid numerical instabilities) or

$$N_{p\text{equil}} = \sum_{j=1}^{NG} \sum_{i=1}^8 Y_i N_i \sigma_{ij} \phi_j / \left(\lambda_p + \sum_{j=1}^{NG} \sigma_{pj} \phi_j \right) .$$

In time varying flux calculations, the flux dependence on time for each time interval throughout the irradiation history is of the following form:

$$\phi_j = \phi_j^* (F1_j + F2_j T + F3_j T^2 + F4_j T^3 + F5_j T^4 + F6_j T^5) ,$$

where

- j = neutron energy group,
- ϕ_j = flux in the time interval,
- ϕ_j^* = flux input for the time interval,
- T = time into the time interval,
- $F1_j \rightarrow F6_j$ = constants (input for each fuel region).

This method of treating fluxes is especially useful in calculating depletions and burnups of capsules which undergo cyclic irradiation histories.

In power calculations, the power is constant for the duration of each time interval. However, as the power is dependent on the nuclide concentrations, the neutron flux is adjusted after each time step (6 hr) to keep the power constant.

OUTPUT

For each initial composition, the nuclide concentrations, flux, power, and burnup are output with a user-specified output frequency as well as after each time interval in the irradiation history. At the end of the problem, the total fission-product birthrates (which are the sum of the birthrates for the first composition of each fuel region) are output with the same frequency as were the concentrations, fluxes, etc.

PROGRAM LISTING AND SAMPLE PROBLEM

The input instructions, a listing of the program, and the input and output for a sample problem are presented on the following pages. The sample problem models a fuel stick which is irradiated in a permanent beryllium facility in the HFIR for three cycles after which it is irradiated in a removal beryllium facility for nine cycles. Four compositions of the fuel stick are treated.

Input Instructions

CARDS

- A Title of problem. Format(20A4)
- B NCS, NG, ITYPE, NFP, NTIME, NC, NCM. Format(24I3)
 NCS(Max 10) = Number of cross section sets
 NG(Max 2) = Number of neutron energy groups
 ITYPE=0 = Power is specified for each time interval
 =1 = Flux is specified for each time interval
 NFP(Max 10) = Number of fission products
 NTIME(Max 50) = Number of time intervals
 NC(Max 50) = Number of fuel regions
 NCM(Max 100) = Number of concentration sets
- C Read the following cards NCS times (for each cross section set):
 1) Title of cross section set. Format(20A4)
 2) Read NG times (for each group):
 25+NFP cross sections in barns and in the order shown in
 Table 1. Format(6E12.5)
- D NFP fission-product names, eight characters allowed for each name.
 Format(9(2A4))
- E Read NFP times (for each fission product):
 The decay constant in sec^{-1} and the eight fission-product yields.
 Format(6E12.5)
 (The fission-product yields in decimal form are specified for
 each of the eight fissionable isotopes in the order shown in Table
 1.)
- F NTIME time intervals in days. Format(6E12.5)
- G Read NCM times (for each concentration set):
 The 17 heavy nuclide concentrations in atoms/barn cm and in the
 order shown in Table 2. Format(6E12.5)
 (These concentration sets must include all initial compositions
 to be calculated.)

Table 1. CACA-2 input order for cross sections

Cross section	Nuclide	Reaction
1	^{232}Th	(n, f)
2	^{234}Pa	
3	^{233}U	
4	^{235}U	
5	^{238}U	
6	^{238}Np	
7	^{239}Pu	
8	^{241}Pu	
9	^{232}Th	(n, γ)
10	^{233}Pa	
11	^{234}Pa	
12	^{233}U	
13	^{234}U	
14	^{235}U	
15	^{236}U	
16	^{237}U	
17	^{238}U	
18	^{237}Np	
19	^{238}Np	
20	^{239}Np	
21	^{238}Pu	
22	^{239}Pu	
23	^{240}Pu	
24	^{241}Pu	
25	^{242}Pu	
26	Fission product 1	(n, abs)
↓	Fission product NFP	
25+NFP		

Table 2. CACA-2 input order for
nuclide concentrations

Number	Nuclide
1	^{232}Th
2	^{233}Pa
3	^{234}Pa
4	^{233}U
5	^{234}U
6	^{235}U
7	^{236}U
8	^{237}U
9	^{238}U
10	^{237}Np
11	^{238}Np
12	^{239}Np
13	^{238}Pu
14	^{239}Pu
15	^{240}Pu
16	^{241}Pu
17	^{242}Pu

CARDS

H Read the remaining cards NC times (for each fuel region):

- 1) Volume (cc) and length (cm) of fuel region. Format(2E12.5)
- 2) For each of the NTIME time intervals specify a cross-section set. (Specify cross-section sets by the order in which the cross-section sets were read in. For example, if the second cross-section set is desired for a particular time interval, specify a 2 for that time interval.) Format(24I3)
- 3) If ITYPE is zero, specify the power in watts/cc for each of the NTIME time intervals. Note: NG must equal one if ITYPE equals zero. Format(6E12.5)

If ITYPE is one, read NTIME fluxes for each of the NG groups: The fluxes are in neutrons/cm² sec. First flux entry in each group must start on a new card. Format(6E12.5)

- 5) If ITYPE is one, read NG times (for each group):

F1, F2, F3, F4, F5, F6. Format(6E12.5)

Note: Flux during each time intervals is:

$$\phi_j = \phi_j^* (F1_j + F2_j T + F3_j T^2 + F4_j T^3 + F5_j T^4 + F6_j T^5) ,$$

where

j = neutron energy group,

ϕ_j = flux at time T in the time interval

ϕ_j^* = flux read in for the time interval jth group,

T = time into the time interval (days).

- 6) NCN. Format(I3)

NCN = Number of different compositions for the fuel region.

- 7) For each of the NCN compositions, specify a concentration set. (Specify concentration sets by the order in which the concentration sets were read in. For example, if the third and fourth concentration sets are desired, specify a 3 and a 4.) Format(24I3)

Note: Only the fission-product birthrates for the first composition of each fuel region will be summed to give the total birthrates for all the fuel regions.

- 8) Specify the frequency of output in days for each of the NCN compositions. Format(6E12.5)

(Nuclide concentrations, power, and burnup will be output with this frequency as well as after each time interval.)

Note: For meaningful total birthrates, the frequency of output must be the same for the first composition in each fuel region.

Listing of Program and Sample Problem Input

```

REAL*8 YD(10,8),DECAY(10),CON(30),POWER,FLUX(50,2),S(38,2,10),
1XP(30),Y(30),FTC(6,2),SR(38,2),FLM(2),FL(2),TTI,EA
REAL*4 ISOT(30,2),ITAT(8,4)
DIMENSION VOL(50),POW(50),DELT(50),FR(8),TITLE(20),BR(600,10),
1TIM(600),CST(30,10),FRST(8,10),AL(50),
1CONC(17,100),ICM(100),ICS(50),DAYS(100),TITR(35,2),TITCS(20,10)
REAL*4 AS(34) /'TH232 PA233 PA234 U233 U234 U235 U
1236 U237 U238 NP237 NP238 NP239 PU238 PU239 PU2
140 PU241 PU242 '/
REAL*4 BS(32) /' TIME(DAYS) FLUX(N/CM2SEC) POWER(W/CC)
1 FISSIONS/CCSEC FISSIONS/CC FINA MWD/MT
1 POWER(KW/FT) '/
REAL*4 CS(44) /'TH232FISPA234FISU233FIS U235FIS U238FIS NP2
138FISPU239FISPU241FISTR232CAPPA233CAPPA234CAPU233CAP U234CAP U235C
1AP U236CAP U237CAP U238CAP NP237CAPNP238CAPNP239CAPPU238CAPPU239CA
1P'/
REAL*4 DS(26) /'PU240CAPPU241CAPPU242CAPFISEROD1FISPROD2FISPROD3FIS
1PROD4FISEROD5FISPROD6FISPROD7FISPROD8FISERCD9FISPRO10'/
COMMON YD,DECAY,POWER,FLM,SR,FTC,FL,TTI,TSTEP,ITYPE,NG,IFF
EQUIVALENCE (Y(1),CON(1))
TSTEP = 21600.
142 FORMAT(9(2A4))
K=0
DO 60 I=1,17
DO 60 J=1,2
K=K+1
60 ISOT(I,J)=AS(K)
K=0
DO 61 I=1,8
DO 61 J=1,4
K=K+1
61 ITAT(I,J) = BS(K)
K=0
DO 62 I=1,22
DO 62 J=1,2
K=K+1
62 TITR(I,J)=CS(K)
K=0
DO 63 I=23,35
DO 63 J=1,2
K=K+1
63 TITR(I,J)=DS(K)
READ(5,95) (TITLE(I),I=1,20)
95 FORMAT(20A4)
WRITE(6,96) (TITLE(I),I=1,20)
96 FORMAT(2CX,20A4,/)
READ(5,100) NCS,NG,ITYPE,NFP,NTIME,NC,NCH
100 FORMAT(24I3)
IFP=17+NFP
MFP=25+NFP
NTP = 1+IFP
DO 301 K=1,NCS
READ(5,95) (TITCS(L,K),L=1,20)
DO 301 J=1,NG
301 READ(5,101) (S(I,J,K),I=1,MFP)
101 FORMAT(6E12.5)
DO 307 ING=1,NG
WRITE(6,302) ING
302 FORMAT(20X,'CROSS SECTION LIBRARY GROUP',I3,/)
WRITE(6,303)
303 FORMAT(35X,'CROSS SECTION SET NUMBER')
WRITE(6,304) (I,I=1,NCS)
304 FORMAT(5X,'CROSS SECTION',7X,10(I2,8X),/)
DO 305 I=1,MFP
305 WRITE(6,306) I, (TITR(I,J),J=1,2), (S(I,ING,K),K=1,NCS)

```

```

306 FORMAT(2X,I3,2X,2A4,6X,10(2X,F8.3))
WRITE(6,134)
DO 35 I=1,NCS
35 WRITE(6,37) I,(TITCS(J,I),J=1,20)
37 FORMAT(5X,'CROSS SECTION SET NUMBER',I3,' IS ',20A4)
WRITE(6,308)
308 FORMAT(1H1)
307 CONTINUE
IF(NFP.EQ.0) GO TO 350
READ(5,142) ((ISOT(I,J),J=1,2),I=1,18,1FP)
DO 1 I=1,NFP
1 READ(5,101) DECAY(I),(YD(I,J),J=1,8)
WRITE(6,310)
310 FORMAT(20X,'FISSION PRODUCT DECAY CONSTANTS AND YIELDS',/)
WRITE(6,311)
311 FORMAT(3X,'ISOTOPE',5X,'DECAY CONSTANT',10X,'FISSION PRODUCT YIELD
1S',/)
WRITE(6,220) ((TITR(I,J),J=1,2),I=1,8)
220 FORMAT(33X,8(2X,2A4))
DO 350 I=1,NFP
K=I+17
WRITE(6,313) (ISOT(K,J),J=1,2),DECAY(I),(YD(I,L),I=1,8)
313 FORMAT(3X,2A4,6X,E10.4,6X,8(2X,F8.5))
350 CONTINUE
DO 53 I=1,600
DO 53 J=1,NFP
53 BR(I,J)=0.0
NTIME=NTIME+1
READ(5,101) (DELT(I),I=2,NTIME)
DELT(1)=0.0
WRITE(6,314)
314 FORMAT(/,30X,'TIME INTERVALS (DAYS)',/)
WRITE(6,315) (DELT(I),I=1,NTIME)
315 FORMAT(2X,10(2X,E10.4))
DO 330 I=1,NCM
330 READ(5,101) (CONC(J,I),J=1,17)
WRITE(6,201)
201 FORMAT(/,30X,'CONCENTRATIONS (ATOMS/BARN CM)',/)
LNCH=NCM/10
NNCH=LNCH*10
IF(NNCH.NE.NCM) LNCH=LNCH+1
DO 202 I=1,LCNM
JNCM=I*10
NNCH=JNCM-9
IF(JNCM.GT.NCM) JNCM=NCM
WRITE(6,204)
204 FORMAT(30X,'CONCENTRATION SET NUMBER')
WRITE(6,205) (LMN,LMN=NNCH,JNCM)
205 FORMAT(2X,'NUCLIDE',10X,10(I3,8X),/)
DO 203 J=1,17
203 WRITE(6,206) (ISOT(J,K),K=1,2),(CONC(J,I),I=NNCH,JNCM)
206 FORMAT(2X,2A4,5X,10(1X,E10.4))
202 WRITE(6,134)
DO 9 N2=1,NC
READ(5,101) VOL(N2),AL(N2)
ICT=0
IBR=0
READ(5,100) (ICS(I),I=2,NTIME)
ICS(1)=ICS(2)
IF(ITYPE.NE.0) GO TO 6
READ(5,101) (POW(I),I=2,NTIME)
POW(1)=POW(2)
DO 7 I=1,NTIME
DO 7 J=1,NG
7 FLUX(I,J)=0.0
DO 8 I=1,6
DO 8 J=1,NG
8 FTC(I,J)=0.0
FTC(1,1)=1.0
GO TO 10

```

```

6 DO 406 J=1,NG
406 READ(5,101) (FLUX(I,J),I=2,NTIME)
DO 372 I=1,NG
372 FLUX(1,I)=FLUX(2,I)
DO 28 I=1,NTIME
28 POW(I)=0.0
READ(5,101) ((FTC(I,J),I=1,6),J=1,NG)
10 CONTINUE
READ(5,100) NCN
READ(5,100) (ICM(I),I=1,NCN)
READ(5,101) (DAYS(I),I=1,NCN)
DO 9 N3=1,NCN
WRITE(6,331) N2,N3
331 FORMAT(1H1,20X,'CASE',I3,10X,'COMPOSITION',I3,/)
WRITE(6,332) VOL(N2),AL(N2),ICM(N3)
332 FORMAT(10X,'VOLUME= ',F10.4,5X,'LENGTH= ',F10.4,5X,'CONCENTRATION
1SET NUMBER',I3,/)
WRITE(6,333)
333 FORMAT(20X,'CROSS SECTION SET FOR EACH TIME INTERVAL')
WRITE(6,334) (ICS(I),I=1,NTIME)
334 FORMAT(5X,25(I3,1X))
IF(ITYPE) 81,81,82
81 WRITE(6,380)
380 FORMAT(/,20X,'POWER FOR EACH TIME INTERVAL(WATTS/CC)')
WRITE(6,315) (POW(I),I=1,NTIME)
GO TO 83
82 WRITE(6,381)
381 FORMAT(/,20X,'FLUXES FOR EACH TIME INTERVAL(N/CM2SEC)')
DO 382 ING=1,NG
WRITE(6,383) ING
383 FORMAT(20X,'GROUP',I3)
382 WRITE(6,315) (FLUX(I,ING),I=1,NTIME)
WRITE(6,384)
384 FORMAT(/,20X,'POLYNOMIAL TIME CONSTANTS FOR FLUXES')
DO 385 ING=1,NG
WRITE(6,383) ING
385 WRITE(6,315) (FTC(I,ING),I=1,6)
83 CONTINUE
WRITE(6,134)
N4=ICM(N3)
ADAY=DAYS(N3)
SUMC=0.0
DO 21 I=1,17
CON(I)=CONC(I,N4)
21 SUMC=SUMC+CONC(I,N4)
DO 22 I=18,NTP
CON(I)=0.0
22 T1=0.0
NS=0
DO 9 K=1,NTIME
POWER=PCW(K)
TTI=0.0
N4=ICS(K)
DO 45 I=1,MFP
DO 45 J=1,NG
45 SR(I,J)=S(I,J,N4)
K1=DELT(K)/ADAY+1.0
A1=K1-1
DO 32 J1=1,K1
IF(J1.EQ.K1) GO TO 33
T2=T1+ADAY*86400.
GO TO 34
33 A2=DELT(K)-ADAY*A1
IF(J1.EQ.1) GO TO 38
IF(A2.EQ.0.0) GO TO 400
38 T2 = T1+A2*86400.
34 CONTINUE
NS = NS+1
L=(T2-T1)/TSTEP+1.0
DO 335 J=1,NG

```

```

335 FLH(J)=FLUX(K,J)/10.**24
    CALL DIFEQ(T1,T2,CON,L)
    PR(1) = T2/86400.
    IF (IFP.EQ.17) GO TO 169
    DO 164 I=18,IFP
    J=I-17
    YP(I)=0.0
    DO 164 M=1,NG
164 YP(I)=PL(M)*(YD(J,1)*SR(1,M)*Y(1)+YD(J,2)*SR(2,M)*Y(3)+YD(J,3)*
    SR(3,M)*Y(4)+YD(J,4)*SR(4,M)*Y(6)+YD(J,5)*SR(5,M)*Y(9)+YD(J,6)*
    SR(6,M)*Y(11)+YD(J,7)*SR(7,M)*Y(14)+YD(J,8)*SR(8,M)*Y(16))
    1+YP(I)
    DO 169 I=18,IFP
    J=I-17
    IJ=I+8
    TOH=.69315/DECAY(J)
    IF (TOH.GT.TSTEP) GO TO 169
    BA=0.0
    DO 170 M=1,NG
170 BA=PL(M)*SF(IJ,M)+BA
    CON(I)=YP(I)/(BA+DECAY(J))
169 CONTINUE
    IF (N3.NE.1) GO TO 165
    IF (IFP.EQ.17) GO TO 165
    IBR=IBR+1
    TIM(IBR) = PR(1)
    DO 146 J=18,IFP
    I=J-17
    BM=YP(J)*VCL(N2)*10.**24
146 BR(IBR,I)=BM+BR(IBR,I)
165 CONTINUE
    PR(2) = 0.0
    DO 167 I=1,NG
167 PR(2)=PR(2)+PL(I)*10.**24
    PR(4) = 0.0
    DO 168 I=1,NG
168 PR(4)=PL(I)*10.**24*(SR(1,I)*Y(1)+SR(2,I)*Y(3)+SR(3,I)*Y(4)+Y(6)
    1*SR(4,I)+Y(9)*SR(5,I)+Y(11)*SR(6,I)+Y(14)*SR(7,I)+Y(16)*SR(8,I))
    1+PR(4)
    PR(3)=PR(4)/(3.468*10.**10)
    PR(5) = CON(NTP)*10.**24
    PR(6)=PR(5)/(SUMC*10.**24)
    PR(7) = PR(6)*.8519*10.**6
    PR(8) = PR(3)*VOL(N2)*.03048/AL(N2)
    DO 173 I=1,IFP
173 CST(I,NS) = CON(I)
    DO 174 I=1,8
174 PRST(I,NS) = PR(I)
400 IF (NS.EQ.10) GO TO 171
    IF (K.NE.NTIME) GO TO 32
    IF (J1.EQ.K1) GO TO 171
    GO TO 32
171 CONTINUE
    WRITE(6,130) (ITAT(1,J),J=1,4)
130 FORMAT(2X,'CONC(ATOMS/BARN CM)',50X,4A4)
    WRITE(6,131) (PRST(1,J),J=1,NS)
131 FORMAT(22X,10(1X,F10.4))
    WRITE(6,134)
    DO 132 I=1,IFP
132 WRITE(6,133) (ISOT(I,J),J=1,2), (CST(I,L),L=1,NS)
133 FORMAT(10X,2A4,4X,10(1X,E10.4))
    WRITE(6,134)
134 FORMAT(/)
    DO 135 I=2,8
135 WRITE(6,136) (ITAT(I,J),J=1,4), (PRST(I,L),L=1,NS)
136 FORMAT(4X,4A4,2X,10(1X,E10.4))
    WRITE(6,393)
393 FORMAT(///)
    NS = 0
32 T1 = T2

```



```

9  CONTINUE
   IF (IFP.EQ.17) GO TO 370
   WRITE (6,137)
137 FORMAT (1H1)
   WRITE (6,138)
138 FORMAT (1H1,30X,'TOTAL BIRTH RATES (ATOMS/SEC) ',//)
   WRITE (6,139) ((ISOT(I,J),J=1,2),I=18,IFP)
139 FORMAT (2X,'TIME (DAYS) ',10(3X,2A4),//)
   DO 370 K=1,IBR
   WRITE (6,144) TIM(K), (BR(K,I),I=1,NFP)
144 FORMAT (2X,F9.3,2X,10(2X,E9.3))
370 CONTINUE
   STOP
   END
   SUBROUTINE DIFEQ(X,XE,Y,L)
   REAL*8 Y(30),YI(30),YF(30),AM1(30),AM2(30),AM3(30),AM4(30),H,XF,XS
1,FI,YD(10,8),DECAY(10),SR(38,2),POWER,FLM(2),FTC(6,2),B(40),TTI,FL
1(2)
   COMMON YD,DECAY,POWER,FLM,SR,FTC,FL,TTI,TSTEP,ITYPE,NG,IFP
   XF=X
   XS=XE
   FI=L
   NFE=IFP+8
   N=IFP+1
   H=(XS-XF)/FI
   DO 10 J=1,N
10  YF(J)=Y(J)
   DO 50 J=1,L
   IF(ITYPE.NE.0) GO TO 5
   FLM(1)=POWER*3.468*10.**10/(SR(1,1)*YF(1)+SR(2,1)*YF(3)+SR(3,1)*
1YF(4)+SR(4,1)*YF(6)+SR(5,1)*YF(9)+SR(6,1)*YF(11)+SR(7,1)*YF(14)+
1SR(8,1)*YF(16))
   FLM(1)=FLM(1)/10.**24
5   TTI=TTI+H/86400.
   DO 3 I=1,NFP
3   B(I)=0.0
   DO 1 I=1,NG
   FL(I)=FLM(I)*(FTC(1,I)+FTC(2,I)*TTI+FTC(3,I)*TTI**2+FTC(4,I)*TTI**
13+FTC(5,I)*TTI**4+FTC(6,I)*TTI**5)
   DO 1 M=1,NFP
1   B(M)=B(M)+SR(M,I)*FL(I)
   CALL EQUA(XF,YF,B,AM1)
   XF=XF+H/2.0
   DO 20 K=1,N
20  YI(K)=YF(K)+AM1(K)*H/2.0
   CALL EQUA(XF,YI,B,AM2)
   DO 30 K=1,N
30  YI(K)=YF(K)+AM2(K)*H/2.0
   CALL EQUA(XF,YI,B,AM3)
   XF=XF+H/2.0
   DO 40 K=1,N
40  YI(K)=YF(K)+AM3(K)*H
   CALL EQUA(XF,YI,B,AM4)
   DO 50 K=1,N
50  YF(K)=H/6.0*(AM1(K)+AM4(K)+2.0*(AM2(K)+AM3(K)))+YF(K)
   DO 60 K=1,N
60  Y(K)=YF(K)
   RETURN
   END
   SUBROUTINE EQUA(X,Y,B,YP)
   REAL*8 X,Y(30),YP(30),YD(10,8),DECAY(10),POWER,FLM(2),FL(2),TTI,
1SR(38,2),FTC(6,2),B(40)
   COMMON YD,DECAY,POWER,FLM,SR,FTC,FL,TTI,TSTEP,ITYPE,NG,IFP
   YP(1)=-Y(1)*(B(1)+B(9))
   YP(2)=B(9)*Y(1)-B(10)*Y(2)-2.971*Y(2)/10.**7
   YP(3)=B(10)*Y(2)-Y(3)*(B(2)+B(11))-2.887*Y(3)/10.**5
   YP(4)=2.971*Y(2)/10.**7-Y(4)*(B(3)+B(12))
   YP(5)=2.887*Y(3)/10.**5+Y(4)*B(12)-Y(5)*B(13)
   YP(6)=Y(5)*B(13)-Y(6)*(B(14)+B(4))+Y(3)*B(11)
   YP(7)=Y(6)*B(14)-Y(7)*B(15)

```

```

YP(8) = Y(7)*B(15)-Y(8)*B(16)-1.189*Y(8)/10.**6
YP(9) = Y(8)*B(16)-Y(9)*(B(17)+B(5))
YP(10) = 1.189*Y(8)/10.**6-Y(10)*B(18)
YP(11) = Y(10)*B(18)-Y(11)*(B(6)+B(19))-3.784*Y(11)/10.**6
YP(12) = Y(9)*B(17)+Y(11)*B(19)-Y(12)*B(20)-3.414*Y(12)/10.**6
YP(13) = 3.784*Y(11)/10.**6-Y(13)*B(21)
YP(14) = 3.414*Y(12)/10.**6-Y(14)*(B(7)+B(22))+Y(13)*B(21)
YP(15) = Y(14)*B(22)+Y(12)*B(20)-Y(15)*B(23)
YP(16) = Y(15)*B(23)-Y(16)*(B(8)+B(24))
YP(17) = Y(16)*B(24)-Y(17)*B(25)
NTP=IFP+1
IF (IFP.EQ.17) GO TO 10
DO 2 I=18,IFP
J=I-17
IJ=I+8
TOH=.69315/DECAY(J)
YP(I) = B(1)*Y(1)*YD(J,1)+B(2)*Y(3)*YD(J,2)+B(3)*Y(4)*YD(J,3)+B(4)*
1Y(6)*YD(J,4)+B(5)*Y(9)*YD(J,5)+B(6)*Y(11)*YD(J,6)+B(7)*Y(14)*
1YD(J,7)+B(8)*Y(16)*YD(J,8)-B(IJ)*Y(I)-DECAY(J)*Y(I)
2 IF (TSTEP.GT.TOH) YP(I)=0.0
10 YP(NTP)=B(1)*Y(1)+B(2)*Y(3)+B(3)*Y(4)+B(4)*Y(6)+B(5)*Y(9)+B(6)*
1Y(11)+B(7)*Y(14)+B(8)*Y(16)
RETURN
END

```

SAMPLE PROBLEM HRB CAPSULE AT MIDPLANE IN PB AND RB OF HFIR

2	1	1	5	24	1	4
CROSS SECTIONS FOR PB FACILITY OF HFIR						
.00208	2200.	243.	241.	.00859	930.	
432.	532.	5.21	37.1	0.0	24.3	
52.6	44.0	8.97	180.	6.72	93.8	
0.0	22.	221.	206.	342.	175.	
35.5	0.0	0.0	0.0	0.0	0.0	
CROSS SECTIONS FOR RB FACILITY OF HFIR						
.0081	1300.	151.	144.	.0334	550.	
281.	329.	3.96	32.2	0.0	16.1	
40.1	27.9	10.2	114.	8.44	65.6	
0.0	13.0	131.	141.	287.	109.	
34.5	0.0	0.0	0.0	0.0	0.0	
KR85M	KR87	KR88	XE133	XE135		
.000043	.038	0.0	.022	.013	.012	
0.0	.005	.004				
.000152	.065	0.0	.040	.025	.017	
0.0	.009	.007				
.0000688	.068	0.0	.053	.036	.019	
0.0	.012	.010				
.00000152	.037	0.0	.060	.068	.062	
0.0	.070	.067				
.0000210	.048	0.0	.061	.066	.059	
0.0	.075	.071				
23.	1.0	23.	1.0	23.	1.0	
23.	1.0	23.	1.0	23.	1.0	
23.	1.0	23.	1.0	23.	1.0	
23.	1.0	23.	1.0	23.	1.0	
.000587	0.0	0.0	0.0	0.0	.0000353	
.000000567	0.0	.00000206	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
.002597	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	.002563	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	0.0	0.0	0.0	0.0	
0.0	0.0	.002531	0.0	0.0	0.0	

0.0		0.0		0.0		0.0		0.0		0.0		0.0		0.0	
1.5451		1.27													
1	1	1	1	2	2	2	2	2	2	2	2	2	2	2	2
.84	E+15	0.0				.84	E+15	0.0				.84	E+15	0.0	
2.59	E+15	0.0				2.59	E+15	0.0				2.59	E+15	0.0	
2.59	E+15	0.0				2.59	E+15	0.0				2.59	E+15	0.0	
2.59	E+15	0.0				2.59	E+15	0.0				2.59	E+15	0.0	
1.0		0.0				0.0		0.0				0.0		0.0	
4															
1	3	4	2												
12.0		24.0				24.0		24.0				24.0			

Sample Problem Output

SAMPLE PROBLEM HRB CAPSULE AT MIDPLANE IN PB AND RB OF HFIR

CROSS SECTION LIBRARY GROUP 1

CROSS SECTION	CROSS SECTION SET NUMBER	
	1	2
1 TH232FIS	0.002	0.008
2 PA234FIS	2200.000	1300.000
3 U233FIS	243.000	151.000
4 U235FIS	241.000	144.000
5 U238FIS	0.009	0.033
6 NP238FIS	930.000	550.000
7 PU239FIS	432.000	281.000
8 PU241FIS	532.000	329.000
9 TH232CAP	5.210	3.960
10 PA233CAP	37.100	32.200
11 PA234CAP	0.0	0.0
12 U233CAP	24.300	16.100
13 U234CAP	52.600	40.100
14 U235CAP	44.000	27.900
15 U236CAP	8.970	10.200
16 U237CAP	180.000	114.000
17 U238CAP	6.720	8.440
18 NP237CAP	93.800	65.600
19 NP238CAP	0.0	0.0
20 NP239CAP	22.000	13.000
21 PU238CAP	221.000	131.000
22 PU239CAP	206.000	141.000
23 PU240CAP	342.000	287.000
24 PU241CAP	175.000	109.000
25 PU242CAP	35.500	34.500
26 FISPROD1	0.0	0.0
27 FISPROD2	0.0	0.0
28 FISPROD3	0.0	0.0
29 FISPROD4	0.0	0.0
30 FISPROD5	0.0	0.0

CROSS SECTION SET NUMBER 1 IS CROSS SECTIONS FOR FE FACILITY OF HFIR
 CROSS SECTION SET NUMBER 2 IS CROSS SECTIONS FOR RB FACILITY OF HFIR

FISSION PRODUCT DECAY CONSTANTS AND YIELDS

ISOTOPE	DECAY CONSTANT	FISSION PRODUCT YIELDS							
		TH232FIS	PA234FIS	U233FIS	U235FIS	U238FIS	NP238FIS	PU239FIS	PU241FIS
KR85M	0.4300D-04	0.03800	0.0	0.02200	0.01300	0.01200	0.0	0.00500	0.00400
KR87	0.1520D-03	0.06500	0.0	0.04000	0.02500	0.01700	0.0	0.00900	0.00700
KR88	0.6880D-04	0.06800	0.0	0.05300	0.03600	0.01900	0.0	0.01200	0.01000
XE133	0.1520D-05	0.03700	0.0	0.06000	0.06800	0.06200	0.0	0.07000	0.06700
XE135	0.2100D-04	0.04800	0.0	0.06100	0.06600	0.05900	0.0	0.07500	0.07100

TIME INTERVALS (DAYS)

0.0 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02
 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02
 0.1000E 01 0.2300E 02 0.1000E 01 0.2300E 02 0.1000E 01

CONCENTRATIONS (ATOMS/BARN CM)

NUCLIDE	CONCENTRATION SET NUMBER			
	1	2	3	4
TH232	0.5870E-03	0.2597E-02	0.0	0.0
PA233	0.0	0.0	0.0	0.0
PA234	0.0	0.0	0.0	0.0
U233	0.0	0.0	0.0	0.0
U234	0.0	0.0	0.0	0.0
U235	0.3530E-04	0.0	0.2563E-02	0.0
U236	0.5670E-06	0.0	0.0	0.0
U237	0.0	0.0	0.0	0.0
U238	0.2060E-05	0.0	0.0	0.2531E-02
NP237	0.0	0.0	0.0	0.0
NP238	0.0	0.0	0.0	0.0
NP239	0.0	0.0	0.0	0.0
PU238	0.0	0.0	0.0	0.0
PU239	0.0	0.0	0.0	0.0
PU240	0.0	0.0	0.0	0.0
PU241	0.0	0.0	0.0	0.0
PU242	0.0	0.0	0.0	0.0

CASE 1			COMPOSITION 1												
VOLUME=		1.5451	LENGTH=		1.2700	CONCENTRATION SET NUMBER 1									
CROSS SECTION SET FOR EACH TIME INTERVAL															
1	1	1	1	1	1	2	2	2	2	2	2	2	2	2	
FLUXES FOR EACH TIME INTERVAL (N/CM2SEC)															
GROUP 1															
0.8400D 15	0.8400D 15	0.0	0.8400D 15	0.0	0.8400D 15	0.0	0.8400D 15	0.0	0.8400D 15	0.0	0.2590D 16	0.0	0.2590D 16	0.0	
0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	
0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	
POLYNOMIAL TIME CONSTANTS FOR FLUXES															
GROUP 1															
0.1000D 01	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
CONC(ATOMS/BARN CM)															
0.0	12.0000	23.0000	24.0000	36.0000	47.0000	48.0000	60.0000	71.0000	72.0000						
TH232	0.5870E-03	0.5843E-03	0.5819E-03	0.5819E-03	0.5793E-03	0.5769E-03	0.5769E-03	0.5743E-03	0.5719E-03	0.5719E-03	0.5719E-03	0.5719E-03	0.5719E-03	0.5719E-03	
PA233	0.0	0.2252E-05	0.3732E-05	0.3637E-05	0.4821E-05	0.5594E-05	0.5452E-05	0.6093E-05	0.6507E-05	0.6342E-05	0.6342E-05	0.6342E-05	0.6342E-05	0.6342E-05	
PA234	0.0	0.2224E-08	0.3742E-08	0.3095E-09	0.4859E-08	0.5652E-08	0.4675E-09	0.6164E-08	0.6589E-08	0.5450E-09	0.5450E-09	0.5450E-09	0.5450E-09	0.5450E-09	
U233	0.0	0.3392E-06	0.1051E-05	0.1146E-05	0.2086E-05	0.3018E-05	0.3160E-05	0.4098E-05	0.4918E-05	0.5082E-05	0.5082E-05	0.5082E-05	0.5082E-05	0.5082E-05	
U234	0.0	0.3604E-07	0.1288E-06	0.1322E-06	0.2821E-06	0.4609E-06	0.4661E-06	0.6872E-06	0.9165E-06	0.9225E-06	0.9225E-06	0.9225E-06	0.9225E-06	0.9225E-06	
U235	0.3530E-04	0.2754E-04	0.2194E-04	0.2194E-04	0.1713E-04	0.1365E-04	0.1365E-04	0.1068E-04	0.8534E-05	0.8534E-05	0.8534E-05	0.8534E-05	0.8534E-05	0.8534E-05	
U236	0.5670E-06	0.1756E-05	0.2605E-05	0.2605E-05	0.3327E-05	0.3839E-05	0.3839E-05	0.4271E-05	0.4575E-05	0.4575E-05	0.4575E-05	0.4575E-05	0.4575E-05	0.4575E-05	
U237	0.0	0.5569E-08	0.1081E-07	0.9754E-08	0.1536E-07	0.1906E-07	0.1720E-07	0.2165E-07	0.2412E-07	0.2177E-07	0.2177E-07	0.2177E-07	0.2177E-07	0.2177E-07	
U238	0.2060E-05	0.2048E-05	0.2039E-05	0.2039E-05	0.2029E-05	0.2020E-05	0.2020E-05	0.2012E-05	0.2004E-05	0.2004E-05	0.2004E-05	0.2004E-05	0.2004E-05	0.2004E-05	
NP237	0.0	0.3200E-08	0.1198E-07	0.1303E-07	0.2712E-07	0.4402E-07	0.4588E-07	0.6558E-07	0.8587E-07	0.8822E-07	0.8822E-07	0.8822E-07	0.8822E-07	0.8822E-07	
NP238	0.0	0.3639E-10	0.1662E-09	0.1199E-09	0.4104E-09	0.6896E-09	0.4973E-09	0.1054E-08	0.1400E-08	0.1010E-08	0.1010E-08	0.1010E-08	0.1010E-08	0.1010E-08	
NP239	0.0	0.3277E-08	0.3354E-08	0.2497E-08	0.3316E-08	0.3326E-08	0.2476E-08	0.3288E-08	0.3259E-08	0.2456E-08	0.2456E-08	0.2456E-08	0.2456E-08	0.2456E-08	
PU238	0.0	0.3876E-10	0.3869E-09	0.3933E-09	0.1328E-08	0.2925E-08	0.3118E-08	0.5594E-08	0.8746E-08	0.9136E-08	0.9136E-08	0.9136E-08	0.9136E-08	0.9136E-08	
PU239	0.0	0.7007E-08	0.1272E-07	0.1358E-07	0.1645E-07	0.1864E-07	0.1949E-07	0.2029E-07	0.2158E-07	0.2242E-07	0.2242E-07	0.2242E-07	0.2242E-07	0.2242E-07	
PU240	0.0	0.5436E-09	0.1935E-08	0.1935E-08	0.3818E-08	0.5499E-08	0.5499E-08	0.7193E-08	0.8543E-08	0.8543E-08	0.8543E-08	0.8543E-08	0.8543E-08	0.8543E-08	
PU241	0.0	0.4350E-10	0.2874E-09	0.2874E-09	0.1855E-09	0.1855E-09	0.1855E-09	0.2222E-08	0.2921E-08	0.2921E-08	0.2921E-08	0.2921E-08	0.2921E-08	0.2921E-08	
PU242	0.0	0.1567E-11	0.2158E-10	0.2158E-10	0.1010E-09	0.2537E-09	0.2537E-09	0.5218E-09	0.8620E-09	0.8620E-09	0.8620E-09	0.8620E-09	0.8620E-09	0.8620E-09	
KR25M	0.2161E-08	0.1722E-08	0.1454E-08	0.0	0.1268E-08	0.1153E-08	0.0	0.1083E-08	0.1038E-08	0.0	0.0	0.0	0.0	0.0	
KR87	0.1176E-08	0.9358E-09	0.7877E-09	0.0	0.6831E-09	0.6176E-09	0.0	0.5766E-09	0.5493E-09	0.0	0.0	0.0	0.0	0.0	
KR88	0.3740E-08	0.2972E-08	0.2491E-08	0.0	0.2144E-08	0.1923E-08	0.0	0.1778E-08	0.1680E-08	0.0	0.0	0.0	0.0	0.0	
XE133	0.0	0.2187E-06	0.2224E-06	0.1950E-06	0.1868E-06	0.1640E-06	0.1438E-06	0.1383E-06	0.1258E-06	0.1103E-06	0.1103E-06	0.1103E-06	0.1103E-06	0.1103E-06	
XE135	0.0	0.1792E-07	0.1474E-07	0.2402E-08	0.1226E-07	0.1058E-07	0.1724E-08	0.9307E-08	0.8418E-08	0.1372E-08	0.1372E-08	0.1372E-08	0.1372E-08	0.1372E-08	
FLUX(N/CM2SEC)	0.8400E 15	0.8400E 15	0.8400E 15	0.0	0.8400E 15	0.8400E 15	0.0	0.8400E 15	0.8400E 15	0.0	0.0	0.0	0.0	0.0	
POWER(W/CC)	0.2061E 03	0.1630E 03	0.1346E 03	0.0	0.1127E 03	0.9803E 02	0.0	0.8707E 02	0.7994E 02	0.0	0.0	0.0	0.0	0.0	
FISIONS/CCSEC	0.7147E 13	0.5652E 13	0.4669E 13	0.0	0.3909E 13	0.3400E 13	0.0	0.3020E 13	0.2755E 13	0.0	0.0	0.0	0.0	0.0	
FISIONS/CC	0.0	0.6591E 19	0.1147E 20	0.1147E 20	0.1950E 20	0.1936E 20	0.1936E 20	0.2269E 20	0.2543E 20	0.2543E 20	0.2543E 20	0.2543E 20	0.2543E 20	0.2543E 20	
FINA	0.0	0.1055E-01	0.1836E-01	0.1836E-01	0.2545E-01	0.3099E-01	0.3099E-01	0.3633E-01	0.4069E-01	0.4069E-01	0.4069E-01	0.4069E-01	0.4069E-01	0.4069E-01	
END/RT	0.0	0.8984E 04	0.1564E 05	0.1564E 05	0.2168E 05	0.2640E 05	0.2640E 05	0.3094E 05	0.3467E 05	0.3467E 05	0.3467E 05	0.3467E 05	0.3467E 05	0.3467E 05	
POWER(KW/P1)	0.7642E 01	0.6044E 01	0.4992E 01	0.0	0.4180E 01	0.3635E 01	0.0	0.3229E 01	0.2946E 01	0.0	0.0	0.0	0.0	0.0	
CONC(ATOMS/BARN CM)															
84.0000	95.0000	96.0000	108.0000	119.0000	120.0000	132.0000	143.0000	144.0000	156.0000						
TH232	0.5658E-03	0.5603E-03	0.5603E-03	0.5544E-03	0.5490E-03	0.5490E-03	0.5432E-03	0.5379E-03	0.5379E-03	0.5322E-03	0.5322E-03	0.5322E-03	0.5322E-03	0.5322E-03	
PA233	0.9271E-05	0.1106E-04	0.1078E-04	0.1216E-04	0.1298E-04	0.1265E-04	0.1333E-04	0.137CE-04	0.1335E-04	0.137CE-04	0.137CE-04	0.137CE-04	0.137CE-04	0.137CE-04	
PA234	0.2380E-07	0.2849E-07	0.2357E-08	0.3138E-07	0.3353E-07	0.2773E-08	0.3443E-07	0.3542E-07	0.2930E-08	0.3542E-07	0.3542E-07	0.3542E-07	0.3542E-07	0.3542E-07	
U233	0.5235E-05	0.5851E-05	0.6131E-05	0.6787E-05	0.7422E-05	0.7751E-05	0.8186E-05	0.8560E-05	0.8907E-05	0.9052E-05	0.9052E-05	0.9052E-05	0.9052E-05	0.9052E-05	
U234	0.1600E-05	0.2347E-05	0.2373E-05	0.3218E-05	0.4035E-05	0.4066E-05	0.4908E-05	0.5676E-05	0.5709E-05	0.6462E-05	0.6462E-05	0.6462E-05	0.6462E-05	0.6462E-05	
U235	0.5488E-05	0.3755E-05	0.3755E-05	0.2610E-05	0.2003E-05	0.2003E-05	0.1652E-05	0.1510E-05	0.1510E-05	0.1478E-05	0.1478E-05	0.1478E-05	0.1478E-05	0.1478E-05	
U236	0.4960E-05	0.5146E-05	0.5146E-05	0.5238E-05	0.5263E-05	0.5263E-05	0.5254E-05	0.5230E-05	0.5230E-05	0.5199E-05	0.5199E-05	0.5199E-05	0.5199E-05	0.5199E-05	
U237	0.7225E-07	0.8604E-07	0.7764E-07	0.8950E-07	0.9257E-07	0.8353E-07	0.9145E-07	0.9282E-07	0.8376E-07	0.9081E-07	0.9081E-07	0.9081E-07	0.9081E-07	0.9081E-07	
U238	0.1975E-05	0.1956E-05	0.1956E-05	0.1938E-05	0.1923E-05	0.1923E-05	0.1907E-05	0.1893E-05	0.1853E-05	0.1877E-05	0.1877E-05	0.1877E-05	0.1877E-05	0.1877E-05	
NP237	0.1340E-06	0.1981E-06	0.2065E-06	0.2692E-06	0.3244E-06	0.3334E-06	0.3797E-06	0.4195E-06	0.4285E-06	0.4592E-06	0.4592E-06	0.4592E-06	0.4592E-06	0.4592E-06	
NP238	0.4000E-08	0.6032E-08	0.4350E-08	0.8390E-08	0.1023E-07	0.7377E-08	0.1209E-07	0.1343E-07	0.9686E-08	0.1477E-07	0.1477E-07	0.1477E-07	0.1477E-07	0.1477E-07	
NP239	0.1228E-07	0.1243E-07	0.9253E-08	0.1223E-07	0.1222E-07	0.9098E-08	0.1203E-07	0.1203E-07	0.8955E-08	0.1184E-07	0.1184E-07	0.1184E-07	0.1184E-07	0.1184E-07	
NP238	0.1635E-07	0.2736E-07	0.2905E-07	0.4392E-07	0.6063E-07	0.6349E-07	0.8059E-07	0.9777E-07	0.1015E-06	0.1165E-06	0.1165E-06	0.1165E-06	0.1165E-06	0.1165E-06	
PU239	0.3231E-07	0.4102E-07	0.4419E-07	0.4690E-07	0.5205E-07	0.5518E-07	0.5755E-07	0.6287E-07	0.6594E-07	0.6836E-07	0.6836E-07	0.6836E-07	0.6836E-07	0.6836E-07	
PU240	0.1123E-07	0.1518E-07	0.1518E-07	0.1916E-07	0.2212E-07	0.2212E-07	0.2519E-07	0.2777E-07	0.2777E-07	0.3067E-07	0.3067E-07	0.3067E-07	0.3067E-07	0.3067E-07	
PU241	0.5196E-08	0.7689E-08	0.7689E-08	0.1038E-07	0.1258E-07	0.1258E-07	0.1477E-07	0.1657E-07	0.1657E-07	0.1851E-07	0.1851E-07	0.1851E-07	0.1851E-07	0.1851E-07	
PU242	0.1972E-08	0.3492E-08	0.3492E-08	0.5719E-08	0.8216E-08	0.8216E-08	0.1132E-07	0.1444E-07	0.1444E-07	0.1807E-07	0.1807E-07	0.1807E-07	0.1807E-07	0.1807E-07	
KR25M	0.1680E-08	0.1609E-08	0.0	0.1667E-08	0.1727E-08	0.0	0.1840E-08	0.1900E-08	0.0	0.1995E-08	0.1995E-08	0.1995E-08	0.1995E-08	0.1995E-08	
KR87	0.8821E-09	0.8396E-09	0.0	0.8660E-09	0.8944E-09	0.0	0.9517E-09	0.9818E-09	0.0	0.1031E-08	0.1031E-08				

CONC(ATOMS/BARN CM)	TIME(DAYS)						
	240.0000	252.0000	263.0000	264.0000	276.0000	287.0000	288.0000

HP232	0.49572E-03	0.49040E-03	0.48572E-03	0.48572E-03	0.48052E-03	0.47592E-03	0.47592E-03
PA233	0.1304E-04	0.1312E-04	0.1313E-04	0.1280E-04	0.1287E-04	0.1287E-04	0.1255E-04
PA234	0.2863E-08	0.3394E-07	0.3397E-07	0.2810E-08	0.3329E-07	0.3331E-07	0.2755E-08
U2333	0.9807E-05	0.5111E-05	0.9343E-05	0.9676E-05	0.9365E-05	0.9188E-05	0.9514E-05
U234	0.1014E-04	0.1044E-04	0.1070E-04	0.1073E-04	0.1094E-04	0.1114E-04	0.1117E-04
U235	0.2137E-05	0.2235E-05	0.2315E-05	0.2315E-05	0.2396E-05	0.2457E-05	0.2457E-05
U236	0.5145E-05	0.5168E-05	0.5194E-05	0.5194E-05	0.5228E-05	0.5263E-05	0.5263E-05
U237	0.8205E-07	0.8972E-07	0.9164E-07	0.8269E-07	0.9064E-07	0.9275E-07	0.8369E-07
U238	0.1781E-05	0.1781E-05	0.1781E-05	0.1781E-05	0.1781E-05	0.1781E-05	0.1781E-05
WP237	0.5945E-06	0.5967E-06	0.6025E-06	0.6111E-06	0.6118E-06	0.1652E-06	0.6255E-06
WP238	0.1374E-07	0.1941E-07	0.1961E-07	0.1414E-07	0.1991E-07	0.2008E-07	0.1448E-07
WP239	0.8425E-08	0.1115E-07	0.1115E-07	0.8305E-08	0.1100E-07	0.1100E-07	0.8193E-08
PU238	0.2002E-06	0.2019E-06	0.2063E-06	0.2117E-06	0.2117E-06	0.2148E-06	0.2204E-06
PU239	0.9679E-07	0.9591E-07	0.9750E-07	0.1003E-06	0.9894E-07	0.1001E-06	0.1029E-06
PU240	0.4493E-07	0.4627E-07	0.4718E-07	0.4718E-07	0.4817E-07	0.4881E-07	0.4881E-07
PU241	0.2860E-07	0.2958E-07	0.3030E-07	0.3030E-07	0.3103E-07	0.3155E-07	0.3155E-07
PU242	0.4551E-07	0.4962E-07	0.5328E-07	0.5328E-07	0.7151E-07	0.6055E-07	0.6055E-07
CR238	0.15E-08	0.175E-08	0.175E-08	0.175E-08	0.216E-08	0.216E-08	0.216E-08
KR87	0.0	0.1162E-08	0.1113E-08	0.0	0.1212E-08	0.1062E-08	0.0
KR98	0.0	0.3328E-08	0.3293E-08	0.0	0.3315E-08	0.3274E-08	0.0
XE133	0.1625E-06	0.1840E-06	0.1870E-06	0.1640E-06	0.1849E-06	0.1874E-06	0.1643E-06
XE135	0.2219E-08	0.1379E-07	0.1370E-07	0.2232E-08	0.1382E-07	0.1370E-07	0.2233E-08

FLUX(W/CM2SEC)	0.0	0.2590E	16	0.2590E	15	0.0	0.2590E	16	0.2590E	16	0.0	
POWER(W/CC)	0.0	0.1384E	03	0.1375E	03	0.0	0.1385E	03	0.1373E	03	0.0	
FISSIONS/CCSEC	0.0	0.4800E	13	0.4767E	13	0.0	0.4805E	13	0.4760E	13	0.0	
FISSIONS/CC	0.8603E	20	0.9104E	20	0.9559E	20	0.9599E	20	0.1006E	21	0.1051E	21
FIMA	0.1377E	00	0.1457E	00	0.1530E	00	0.1530E	00	0.1610E	00	0.1683E	00
MWD/WT	0.1173E	06	0.1241E	06	0.1303E	06	0.1303E	06	0.1371E	06	0.1433E	06
POWER(KW/FT)	0.0	0.5133E	01	0.5097E	01	0.0	0.5138E	01	0.5090E	01	0.0	

VOLUME= 1.5451 LENGTH= 1.2700 CONCENTRATION SET NUMBER 3

CROSS SECTION SPT FOR EACH TIME INTERVAL

FLUXES FOR EACH TIME INTERVAL (N/CM²SEC)

GROUP 1									
0.8400D 15	0.8400D 15	0.0	0.8400D 15	0.0	0.8400D 15	0.0	0.2590D 16	0.0	0.2590D 16
0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16
0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16	0.0	0.2590D 16

POLYNOMIAL TIME CONSTANTS FOR FLUXES

0.1000D 01	0.0	0.0	0.0	0.0	0.0
------------	-----	-----	-----	-----	-----

CONC (ATOMS/BARN CM)	TIME (DAYS)									
0.0	23.0000	24.0000	47.0000	48.0000	71.0000	72.0000	95.0000	96.0000	119.0000	

[illegible]

U234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U235	0.2563E-02	0.1593E-02	0.1593E-02	0.9898E-03	0.9898E-03	0.6151E-03	0.6151E-03	0.2539E-03	0.2539E-03	0.1048E-03
U236	0.0	0.1486E-03	0.1486E-03	0.2387E-03	0.2387E-03	0.2926E-03	0.2926E-03	0.3345E-03	0.3345E-03	0.3409E-03
U237	0.0	0.5171E-06	0.5159E-06	0.1160E-05	0.1047E-05	0.1529E-05	0.1380E-05	0.5577E-05	0.5032E-05	0.6008E-05
U238	0.0	0.7109E-07	0.7109E-07	0.3298E-06	0.3298E-06	0.7224E-06	0.7224E-06	0.3132E-05	0.3132E-05	0.6279E-05
NP237	0.0	0.5366E-06	0.5924E-06	0.2423E-05	0.2637E-05	0.5082E-05	0.5231E-05	0.1244E-04	0.1298E-04	0.2077E-04
NP238	0.0	0.7168E-08	0.5169E-08	0.3751E-07	0.2705E-07	0.8242E-07	0.5943E-07	0.3776E-06	0.2723E-06	0.6542E-06
NP239	0.0	0.8313E-10	0.6190E-10	0.4647E-09	0.3460E-09	0.1082E-08	0.8060E-09	0.1706E-07	0.1270E-07	0.3680E-07
PU238	0.0	0.1309E-07	0.1509E-07	0.1466E-06	0.1571E-06	0.4486E-06	0.5097E-06	0.1655E-05	0.1760E-05	0.3810E-05
PU239	0.0	0.9533E-09	0.9745E-09	0.1901E-07	0.1913E-07	0.8500E-07	0.8528E-07	0.3658E-06	0.3702E-06	0.9675E-06
PU240	0.0	0.5358E-10	0.5358E-10	0.2168E-08	0.2168E-08	0.1443E-07	0.1443E-07	0.9287E-07	0.9287E-07	0.2945E-06
PU241	0.0	0.3956E-11	0.3956E-11	0.3034E-05	0.3034E-05	0.2836E-08	0.2836E-08	0.3562E-07	0.3562E-07	0.1316E-06
PU242	0.0	0.1502E-12	0.1502E-12	0.2498E-10	0.2498E-10	0.3780E-09	0.3780E-09	0.8672E-08	0.8672E-08	0.4745E-07
KRE5M	0.1569E-06	0.9748E-07	0.0	0.6058E-07	0.0	0.3765E-07	0.0	0.2866E-07	0.0	0.1191E-07
KR87	0.8534E-07	0.5303E-07	0.0	0.3296E-07	0.0	0.2048E-07	0.0	0.1555E-07	0.0	0.6477E-08
KR88	0.2715E-06	0.1687E-06	0.0	0.1048E-06	0.0	0.6516E-07	0.0	0.4960E-07	0.0	0.2600E-07
XP133	0.0	0.1578E-04	0.1384E-04	0.1048E-04	0.9190E-05	0.6542E-05	0.5737E-05	0.5573E-05	0.4887E-05	0.2448E-05
XP135	0.0	0.1025E-05	0.1671E-06	0.5370E-06	0.1038E-06	0.3960E-06	0.6454E-07	0.3051E-06	0.4973E-07	0.1284E-06
FLUX(N/CM2SEC)	0.8400E 15	0.8400E 15	0.0	0.8400E 15	0.0	0.8400E 15	0.0	0.2590E 16	0.0	0.2590E 16
POWER(W/CC)	0.1496E 05	0.9297E 04	0.0	0.5779E 04	0.0	0.3593E 04	0.0	0.2755E 04	0.0	0.1178E 04
FISSIONS/CCSEC	0.5189E 15	0.3224E 15	0.0	0.2004E 15	0.0	0.1246E 15	0.0	0.9553E 14	0.0	0.8084E 14
FISSIONS/CC	0.0	0.8205E 21	0.8205E 21	0.1330E 22	0.1330E 22	0.1647E 22	0.1647E 22	0.1951E 22	0.1951E 22	0.2078E 22
FINA	0.0	0.3201E 00	0.3201E 00	0.5191E 00	0.5191E 00	0.6428E 00	0.6428E 00	0.7612E 00	0.7612E 00	0.8109E 00
RWD/WT	0.0	0.2727E 06	0.2727E 06	0.4422E 06	0.4422E 06	0.5476E 06	0.5476E 06	0.6484E 06	0.6484E 06	0.6908E 06
POWER(KW/PT)	0.5548E 03	0.3448E 03	0.0	0.2143E 03	0.0	0.1332E 03	0.0	0.1022E 03	0.0	0.4367E 02
CONC(ATONS/BARN CM)										
TIME(DAYS)										
	120.0000	143.0000	144.0000	167.0000	168.0000	191.0000	192.0000	215.0000	216.0000	239.0000
TH232	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U235	0.1048E-03	0.4327E-04	0.4327E-04	0.1786E-04	0.1786E-04	0.7374E-05	0.7374E-05	0.3044E-05	0.3044E-05	0.1257E-05
U236	0.3409E-03	0.3331E-03	0.3331E-03	0.3201E-03	0.3201E-03	0.3054E-03	0.3054E-03	0.2904E-03	0.2904E-03	0.2759E-03
U237	0.5421E-05	0.5949E-05	0.5369E-05	0.5746E-05	0.5185E-05	0.5493E-05	0.4957E-05	0.5230E-05	0.4719E-05	0.4969E-05
U238	0.6279E-05	0.9360E-05	0.9360E-05	0.1223E-04	0.1223E-04	0.1484E-04	0.1484E-04	0.1720E-04	0.1720E-04	0.1931E-04
NP237	0.2135E-04	0.2695E-04	0.2753E-04	0.3107E-04	0.3163E-04	0.3353E-04	0.3407E-04	0.3477E-04	0.3528E-04	0.3511E-04
NP238	0.4717E-06	0.8630E-06	0.6223E-06	0.1003E-05	0.7236E-06	0.1088E-05	0.7849E-06	0.1132E-05	0.8163E-06	0.1146E-05
NP239	0.2740E-07	0.5647E-07	0.4204E-07	0.7486E-07	0.5574E-07	0.9168E-07	0.6826E-07	0.1069E-06	0.7957E-07	0.1205E-06
PU238	0.3992E-05	0.6234E-05	0.6474E-05	0.8404E-05	0.8684E-05	0.1011E-04	0.1041E-04	0.1131E-04	0.1162E-04	0.1206E-04
PU239	0.9769E-06	0.1749E-05	0.1764E-05	0.2519E-05	0.2538E-05	0.3169E-05	0.3192E-05	0.3662E-05	0.3689E-05	0.4004E-05
PU240	0.2945E-06	0.6189E-06	0.6189E-06	0.9923E-06	0.9923E-06	0.1344E-05	0.1344E-05	0.1635E-05	0.1635E-05	0.1853E-05
PU241	0.1116E-06	0.3111E-06	0.3111E-06	0.5433E-06	0.5433E-06	0.7806E-06	0.7806E-06	0.9889E-06	0.9889E-06	0.1153E-05
PU242	0.4745E-07	0.1517E-06	0.1517E-06	0.3472E-06	0.3472E-06	0.6335E-06	0.6335E-06	0.9886E-06	0.9886E-06	0.1382E-05
KRE5M	0.0	0.5052E-08	0.0	0.2271E-08	0.0	0.1162E-08	0.0	0.7320E-09	0.0	0.5724E-09
KR87	0.0	0.2742E-08	0.0	0.1226E-08	0.0	0.6197E-09	0.0	0.3835E-09	0.0	0.2951E-09
KR88	0.0	0.8705E-08	0.0	0.3873E-08	0.0	0.1938E-08	0.0	0.1182E-08	0.0	0.8968E-09
XE133	0.2147E-05	0.1063E-05	0.9322E-06	0.5080E-06	0.4455E-06	0.2965E-06	0.2600E-06	0.2223E-06	0.1950E-06	0.2005E-06
XE135	0.2092E-07	0.5720E-07	0.9324E-08	0.2945E-07	0.4800E-08	0.1927E-07	0.3141E-08	0.1598E-07	0.2605E-08	0.1521E-07
FLUX(W/CM2SEC)	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16
POWER(W/CC)	0.0	0.5452E 03	0.0	0.2996E 03	0.0	0.2097E 03	0.0	0.1804E 03	0.0	0.1730E 03
FISSIONS/CCSEC	0.0	0.1891E 14	0.0	0.1039E 14	0.0	0.7273E 13	0.0	0.6257E 13	0.0	0.5995E 13
FISSIONS/CC	0.2078E 22	0.2134E 22	0.2134E 22	0.2162E 22	0.2162E 22	0.2179E 22	0.2179E 22	0.2192E 22	0.2192E 22	0.2204E 22
FINA	0.8109E 00	0.8327E 00	0.8327E 00	0.8436E 00	0.8436E 00	0.8502E 00	0.8502E 00	0.8553E 00	0.8553E 00	0.8600E 00
RWD/WT	0.6908E 06	0.7094E 06	0.7094E 06	0.7186E 06	0.7186E 06	0.7243E 06	0.7243E 06	0.7287E 06	0.7287E 06	0.7327E 06
POWER(KW/PT)	0.0	0.2022E 02	0.0	0.1111E 02	0.0	0.7777E 01	0.0	0.6691E 01	0.0	0.6415E 01
CONC(ATONS/BARN CM)										
TIME(DAYS)										
	240.0000	263.0000	264.0000	287.0000	288.0000					
TH232	0.0	0.0	0.0	0.0	0.0					
PA233	0.0	0.0	0.0	0.0	0.0					
PA234	0.0	0.0	0.0	0.0	0.0					
U233	0.0	0.0	0.0	0.0	0.0					
U234	0.0	0.0	0.0	0.0	0.0					
U235	0.1257E-05	0.5188E-06	0.5188E-06	0.2142E-06	0.2142E-06					
U236	0.2759E-03	0.2619E-03	0.2619E-03	0.2485E-03	0.2485E-03					
U237	0.4484E-05	0.4718E-05	0.4257E-05	0.4478E-05	0.4041E-05					
U238	0.1931E-04	0.2119E-04	0.2119E-04	0.2285E-04	0.2285E-04					
NP237	0.3560E-04	0.3484E-04	0.3530E-04	0.3415E-04	0.3459E-04					
NP238	0.8262E-06	0.1138E-05	0.8210E-06	0.1117E-05	0.8055E-06					
NP239	0.8970E-07	0.1326E-06	0.9872E-07	0.1433E-06	0.1067E-06					
PU238	0.1238E-04	0.1246E-04	0.1277E-04	0.1257E-04	0.1288E-04					
PU239	0.4035E-05	0.4217E-05	0.4251E-05	0.4327E-05	0.4364E-05					
PU240	0.1853E-05	0.2002E-05	0.2002E-05	0.2092E-05	0.2092E-05					
PU241	0.1153E-05	0.1270E-05	0.1270E-05	0.1346E-05	0.1346E-05					
PU242	0.1382E-05	0.1782E-05	0.1782E-05	0.2167E-05	0.2167E-05					
KRE5M	0.0	0.5166E-09	0.0	0.4976E-09	0.0					
KR87	0.0	0.2636E-09	0.0	0.2527E-09	0.0					
KR88	0.0	0.7944E-09	0.0	0.7584E-09	0.0					
XE133	0.1758E-06	0.1968E-06	0.1725E-06	0.1977E-06	0.1734E-06					
XE135	0.2480E-08	0.1523E-07	0.2483E-08	0.1538E-07	0.2507E-08					
FLUX(W/CM2SEC)	0.0	0.2590E 16	0.0	0.2590E 16	0.0					
POWER(W/CC)	0.0	0.1721E 03	0.0	0.1721E 03	0.0					
FISSIONS/CCSEC	0.0	0.5969E 13	0.0	0.5969E 13	0.0					
FISSIONS/CC	0.2204E 22	0.2216E 22	0.2216E 22	0.2228E 22	0.2228E 22					

FINA 0.8600E 00 0.8646E 00 0.8646E 00 0.8692E 00 0.8692E 00
 MWD/MT 0.7327E 06 0.7366E 06 0.7366E 06 0.7405E 06 0.7405E 06
 POWER (KW/FT) 0.0 0.6382E 01 0.0 0.6393E 01 0.0

CASE 1 COMPOSITION 3

VOLUME= 1.5451 LENGTH= 1.2700 CONCENTRATION SET NUMBER 4

CROSS SECTION SET FOR EACH TIME INTERVAL
 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2

FLUXES FOR EACH TIME INTERVAL (N/CM2SEC)

GROUP 1
 0.8400D 15 0.8400D 15 0.0 0.8400D 15 0.0 0.8400D 15 0.0 0.2590D 16 0.0 0.2590D 16
 0.0 0.2590D 16 0.0 0.2590D 16 0.0 0.2590D 16 0.0 0.2590D 16 0.0 0.2590D 16
 0.0 0.2590D 16 0.0 0.2590D 16 0.0

POLYNOMIAL TIME CONSTANTS FOR FLUXES

GROUP 1
 0.1000D 01 0.0 0.0 0.0 0.0 0.0

CONC(ATOMS/BARN CM) 0.0 23.0000 24.0000 47.0000 TIME(DAYS) 48.0000 71.0000 72.0000 95.0000 96.0000 119.0000

TH232	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U235	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U236	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U237	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U238	0.2531E-02	0.2503E-02	0.2503E-02	0.2475E-02	0.2475E-02	0.2447E-02	0.2447E-02	0.2343E-02	0.2343E-02	0.2243E-02	0.2243E-02
NP237	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NP238	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NP239	0.0	0.4118E-05	0.3066E-05	0.4075E-05	0.3034E-05	0.4030E-05	0.3000E-05	0.1494E-04	0.1112E-04	0.1431E-04	0.1431E-04
PU238	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PU239	0.0	0.1560E-04	0.1665E-04	0.2241E-04	0.2345E-04	0.2457E-04	0.2560E-04	0.4283E-04	0.4665E-04	0.4488E-04	0.4488E-04
PU240	0.0	0.2376E-05	0.2376E-05	0.6696E-05	0.6696E-05	0.1015E-04	0.1015E-04	0.1667E-04	0.1667E-04	0.2128E-04	0.2128E-04
PU241	0.0	0.3529E-06	0.3529E-06	0.1778E-05	0.1778E-05	0.3518E-05	0.3518E-05	0.8670E-05	0.8670E-05	0.1278E-04	0.1278E-04
PU242	0.0	0.2651E-07	0.2651E-07	0.3109E-06	0.3109E-06	0.1049E-05	0.1049E-05	0.4093E-05	0.4093E-05	0.9093E-05	0.9093E-05
KR85H	0.5097E-11	0.6780E-09	0.0	0.1024E-08	0.0	0.1188E-08	0.0	0.4368E-08	0.0	0.4465E-08	0.4465E-08
KR87	0.2043E-11	0.3445E-09	0.0	0.5201E-09	0.0	0.6022E-09	0.0	0.2209E-08	0.0	0.2457E-08	0.2457E-08
KR88	0.5043E-11	0.1015E-08	0.0	0.1539E-08	0.0	0.1788E-08	0.0	0.6567E-08	0.0	0.7333E-08	0.7333E-08
XE133	0.0	0.1878E-06	0.1647E-06	0.3678E-06	0.3226E-06	0.4573E-06	0.4010E-06	0.1518E-05	0.1331E-05	0.1924E-05	0.1924E-05
XE135	0.0	0.2041E-07	0.3326E-08	0.3160E-07	0.5150E-08	0.3711E-07	0.6048E-08	0.1360E-06	0.2211E-07	0.1538E-06	0.1538E-06

FLUX(N/CM2SEC) 0.8400E 15 0.8400E 15 0.0 0.8400E 15 0.0 0.8400E 15 0.0 0.2590E 16 0.0 0.2590E 16
 POWER (W/CC) 0.5266E 00 0.1683E 03 0.0 0.2579E 03 0.0 0.3029E 03 0.0 0.1118E 04 0.0 0.1261E 04
 FISSIONS/CCSEC 0.1826E 11 0.5837E 13 0.0 0.8944E 13 0.0 0.1050E 14 0.0 0.3876E 14 0.0 0.4374E 14
 FISSIONS/CC 0.0 0.5795E 19 0.5795E 19 0.2094E 20 0.2094E 20 0.4050E 20 0.4050E 20 0.1006E 21 0.1006E 21 0.1843E 21
 FINA 0.0 0.2289E-02 0.2289E-02 0.8275E-02 0.8275E-02 0.1600E-01 0.1600E-01 0.3975E-01 0.3975E-01 0.7282E-01
 MWD/RT 0.0 0.1950E 04 0.1950E 04 0.7049E 04 0.7049E 04 0.1363E 05 0.1363E 05 0.3387E 05 0.3387E 05 0.6204E 05
 POWER (KW/FT) 0.1953E-01 0.6241E 01 0.0 0.9564E 01 0.0 0.1123E 02 0.0 0.4145E 02 0.0 0.4677E 02

CONC(ATOMS/BARN CM) 120.0000 143.0000 144.0000 167.0000 TIME(DAYS) 168.0000 191.0000 192.0000 215.0000 216.0000 239.0000

TH232	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PA234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U233	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U234	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U235	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U236	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U237	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
U238	0.2243E-02	0.2147E-02	0.2147E-02	0.2055E-02	0.2055E-02	0.1968E-02	0.1968E-02	0.1884E-02	0.1884E-02	0.1803E-02	0.1803E-02
NP237	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NP238	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NP239	0.1065E-04	0.1370E-04	0.1020E-04	0.1311E-04	0.9763E-05	0.1255E-04	0.9346E-05	0.1202E-04	0.8947E-05	0.1150E-04	0.1150E-04
PU238	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
PU239	0.4853E-04	0.4340E-04	0.4690E-04	0.4160E-04	0.4495E-04	0.3983E-04	0.4304E-04	0.3813E-04	0.4120E-04	0.3651E-04	0.3651E-04
PU240	0.2128E-04	0.2205E-04	0.2205E-04	0.2154E-04	0.2154E-04	0.2073E-04	0.2073E-04	0.1987E-04	0.1987E-04	0.1903E-04	0.1903E-04
PU241	0.1278E-04	0.1424E-04	0.1424E-04	0.1427E-04	0.1427E-04	0.1384E-04	0.1384E-04	0.1329E-04	0.1329E-04	0.1273E-04	0.1273E-04
PU242	0.9093E-05	0.1467E-04	0.1467E-04	0.1966E-04	0.1966E-04	0.2370E-04	0.2370E-04	0.2682E-04	0.2682E-04	0.2915E-04	0.2915E-04
KR85H	0.0	0.4854E-08	0.0	0.4702E-08	0.0	0.4515E-08	0.0	0.4326E-08	0.0	0.4142E-08	0.4142E-08
KR87	0.0	0.2450E-08	0.0	0.2373E-08	0.0	0.2279E-08	0.0	0.2183E-08	0.0	0.2090E-08	0.2090E-08
KR88	0.0	0.7325E-08	0.0	0.7098E-08	0.0	0.6817E-08	0.0	0.6532E-08	0.0	0.6254E-08	0.6254E-08
XE133	0.1687E-05	0.1987E-05	0.1743E-05	0.1946E-05	0.1706E-05	0.1874E-05	0.1644E-05	0.1797E-05	0.1576E-05	0.1721E-05	0.1721E-05
XE135	0.2507E-07	0.1544E-06	0.2517E-07	0.1499E-06	0.2443E-07	0.1440E-06	0.2347E-07	0.1380E-06	0.2249E-07	0.1321E-06	0.1321E-06

FLUX(N/CM2SEC) 0.0 0.2590E 16 0.0 0.2590E 16 0.0 0.2590E 16 0.0 0.2590E 16 0.0 0.2590E 16
 POWER (W/CC) 0.0 0.1266E 04 0.0 0.1229E 04 0.0 0.1181E 04 0.0 0.1132E 04 0.0 0.1084E 04
 FISSIONS/CCSEC 0.0 0.4391E 14 0.0 0.4262E 14 0.0 0.4095E 14 0.0 0.3924E 14 0.0 0.3758E 14
 FISSIONS/CC 0.1843E 21 0.2722E 21 0.2722E 21 0.3586E 21 0.3586E 21 0.4420E 21 0.4420E 21 0.5220E 21 0.5220E 21 0.5986E 21
 FINA 0.7282E-01 0.1075E 00 0.1075E 00 0.1417E 00 0.1417E 00 0.1746E 00 0.1746E 00 0.2062E 00 0.2062E 00 0.2365E 00
 MWD/RT 0.6204E 05 0.9161E 05 0.9161E 05 0.1207E 06 0.1207E 06 0.1488E 06 0.1488E 06 0.1757E 06 0.1757E 06 0.2015E 06
 POWER (KW/FT) 0.0 0.4695E 02 0.0 0.4575E 02 0.0 0.4379E 02 0.0 0.4196E 02 0.0 0.4018E 02

CONC(ATOMS/BARN CM)		TIME(DAYS)				
		240.0000	263.0000	264.0000	287.0000	288.0000
TH232	0.0	0.0	0.0	0.0	0.0	0.0
PA213	0.0	0.0	0.0	0.0	0.0	0.0
PA234	0.0	0.0	0.0	0.0	0.0	0.0
U233	0.0	0.0	0.0	0.0	0.0	0.0
U234	0.0	0.0	0.0	0.0	0.0	0.0
U235	0.0	0.0	0.0	0.0	0.0	0.0
U236	0.0	0.0	0.0	0.0	0.0	0.0
U237	0.0	0.0	0.0	0.0	0.0	0.0
U238	0.1803E-02	0.1726E-02	0.1726E-02	0.1653E-C2	0.1653E-02	0.1653E-02
NP237	0.0	0.0	0.0	0.0	0.0	0.0
NP238	0.0	0.0	0.0	0.0	0.0	0.0
NP239	0.8565E-05	0.1101E-04	0.8200E-05	0.1054E-04	0.7850E-05	0.7850E-05
PU238	0.0	0.0	0.0	C.C	0.0	0.0
PU239	0.3944E-04	0.3495E-04	0.3776E-04	0.3346E-04	0.3615E-04	0.3615E-04
PU240	0.1903E-04	0.1822E-04	0.1822E-04	0.1744E-04	0.1744E-04	0.1744E-04
PU241	0.1273E-04	0.1219E-04	0.1219E-04	0.1167E-04	0.1167E-04	0.1167E-04
PU242	0.2915E-04	0.3082E-04	0.3082E-04	0.3194E-04	0.3194E-04	0.3194E-04
KR65M	0.0	0.3966E-08	0.0	0.3797E-C8	0.0	0.0
KR67	0.0	0.2001E-08	0.0	0.1916E-08	0.0	0.0
KR6E	0.0	0.5988E-08	0.0	0.5732E-08	0.0	0.0
XE133	0.1509E-05	0.1648E-05	0.1445E-05	0.1578E-05	0.1384E-05	0.1384E-05
XE135	0.2154E-07	0.1265E-06	0.2062E-07	0.1211E-06	0.1974E-07	0.1974E-07
FLOX(W/CM2SEC)	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.0
POWER(W/CC)	0.0	0.1037E 04	0.0	0.9931E 03	0.0	0.0
FISSIONS/CCSEC	0.0	0.3597E 14	0.0	0.3444E 14	0.0	0.0
FISSIONS/CC	0.5986 E 21	0.6720E 21	0.6720E 21	0.7422E 21	0.7422E 21	0.7422E 21
FIMA	0.236E 00	0.2655E 00	0.2655E 00	0.2932E 00	0.2932E 00	0.2932E 00
MWD/MT	0.2015 E 06	0.2262E 06	0.2262E 06	0.2498E 06	0.2498E 06	0.2498E 06
POWER(KW/Ft)	0.0	0.3847E 02	0.0	0.3683E 02	0.0	0.0

CASE 1 COMPOSITION 4

VOLUME= 1.5451 LENGTH= 1.2700 CONCENTRATION SET NUMBER 2

[illegible]

CONC(ATOMS/BARR CM)		TIME(DAYS)									
		0.0	23.0000	24.0000	47.0000	48.0000	71.0000	72.0000	95.0000	96.0000	119.0000
TH232	0.2597E-02	0.2575E-02	0.2575E-02	0.2552E-02	0.2552E-02	0.2530E-02	0.2530E-02	0.2530E-02	0.2479E-02	0.2479E-02	0.2429E-02
PA233	0.0	0.1651E-04	0.1669E-04	0.2475E-04	0.2412E-04	0.2879E-04	0.2806E-04	0.2806E-04	0.4489E-04	0.4777E-04	0.5774E-04
PA234	0.0	0.1655E-07	0.1369E-08	0.2501E-07	0.2068E-08	0.2915E-07	0.2411E-08	0.1261E-06	0.1043E-07	0.1043E-07	0.1484E-06
U233	0.0	0.4652E-05	0.5070E-05	0.1335E-04	0.1398E-04	0.2176E-04	0.2249E-04	0.2588E-04	0.2712E-04	0.2712E-04	0.3284E-04
U234	0.0	0.5697E-06	0.5849E-06	0.2039E-05	0.2062E-05	0.4055E-05	0.4081E-05	0.1038E-04	0.1050E-04	0.1050E-04	0.1785E-04
U235	0.0	0.1507E-07	0.1507E-07	0.1005E-06	0.1005E-06	0.2786E-06	0.2786E-06	0.1142E-05	0.1142E-05	0.1142E-05	0.2476E-05
U236	0.0	0.2830E-09	0.2830E-09	0.3959E-08	0.3959E-08	0.1717E-07	0.1717E-07	0.1097E-06	0.1057E-06	0.1057E-06	0.3538E-06
U237	0.0	0.5837E-12	0.5627E-12	0.1243E-10	0.1122E-10	0.6467E-10	0.5836E-10	0.1259E-08	0.1136E-08	0.1136E-08	0.4634E-08
U238	0.0	0.3086E-13	0.3086E-13	0.1394E-11	0.1394E-11	0.1134E-10	0.1134E-10	0.3263E-09	0.3263E-09	0.3263E-09	0.1854E-08
WP237	0.0	0.2375E-12	0.2945E-12	0.1053E-10	0.1175E-10	0.8437E-10	0.9068E-10	0.1224E-08	0.1347E-08	0.1347E-08	0.6516E-08
WP238	0.0	0.2451E-14	0.1768E-14	0.1394E-12	0.1005E-12	0.1225E-11	0.8831E-12	0.3295E-10	0.2376E-10	0.2376E-10	0.1875E-09
WP239	0.0	0.2658E-16	0.1979E-16	0.1618E-14	0.1205E-14	0.1478E-13	0.1100E-13	0.1534E-11	0.1142E-11	0.1142E-11	0.9653E-11
PU238	0.0	0.2450E-14	0.3134E-14	0.2889E-12	0.2377E-12	0.3843E-11	0.4185E-11	0.7637E-10	0.8555E-10	0.8555E-10	0.6099E-09
PU239	0.0	0.120E-15	0.1270E-15	0.2497E-13	0.2538E-13	0.4547E-12	0.4545E-12	0.1246E-10	0.1286E-10	0.1286E-10	0.1204E-05
PU240	0.0	0.4455E-17	0.4455E-17	0.1844E-14	0.1844E-14	0.4956E-13	0.4956E-13	0.2025E-11	0.2025E-11	0.2025E-11	0.2521E-10
PU241	0.0	0.2300E-18	0.2300E-18	0.1834E-15	0.1834E-15	0.6968E-14	0.6968E-14	0.5442E-12	0.5442E-12	0.5442E-12	0.8343E-11
PU242	0.0	0.6112E-20	0.6112E-20	0.1035E-16	0.1035E-16	0.6123E-15	0.6123E-15	0.8102E-13	0.8102E-13	0.8102E-13	0.1718E-11
KR85H	0.4010E-11	0.907E-08	0.0	0.1804E-08	0.0	0.213E-08	0.0	0.5354E-08	0.0	0.5354E-08	0.6895E-08
KR87	0.1940E-11	0.2523E-09	0.0	0.7225E-09	0.0	0.1180E-08	0.0	0.7565E-08	0.0	0.7565E-08	0.3553E-08
KR88	0.4485E-11	0.375E-09	0.0	0.2115E-08	0.0	0.3455E-08	0.0	0.8072E-08	0.0	0.8072E-08	0.1043E-07
XE133	0.0	0.2189E-07	0.1920E-07	0.857E-07	0.7504E-07	0.1562E-06	0.1370E-06	0.3789E-06	0.3322E-06	0.3322E-06	0.5086E-06
XP135	0.0	0.2670E-08	0.4351E-09	0.7866E-08	0.1282E-08	0.1298E-07	0.2116E-08	0.3065E-07	0.4995E-08	0.4013E-07	
PLUX(W/CM2SEC)	0.8400E 15	0.8400E 15	0.0	0.8400E 15	0.0	0.8400E 15	0.0	0.2590E 16	0.0	0.2590E 16	
POWER(W/CC)	0.1308E 00	0.2848E 02	0.0	0.8064E 02	0.0	0.1314E 03	0.0	0.3179E 03	0.0	0.4128E 03	
FISSIONS/CCSEC	0.4537E 10	0.8777E 12	0.0	0.2796E 13	0.0	0.4562E 13	0.0	0.1103E 14	0.0	0.1432E 14	
FISSIONS/CC	0.0	0.7326E 18	0.7326E 18	0.4529E 19	0.4529E 19	0.1198E 20	0.1198E 20	0.3147E 20	0.3147E 20	0.5705E 20	
FINA	0.0	0.2821E 03	0.2821E 03	0.1744E-02	0.1744E-02	0.4614E-02	0.4614E-02	0.1212E-01	0.1212E-01	0.2197E-01	
MWD/MT	0.0	0.2403E 03	0.2403E 03	0.1486E 04	0.1486E 04	0.3930F 04	0.3930F 04	0.1032E 05	0.1032E 05	0.1871E 05	
POWER(KW/FT)	0.4485E-C2	0.1056E 01	0.0	0.2990E 01	0.0	0.4871E 01	0.0	0.1179E 02	0.0	0.1531E 02	

CONC (ATOMS/BARN CM)	TIME (DAYS)									
	120.0000	143.0000	144.0000	167.0000	168.0000	191.0000	192.0000	215.0000	216.0000	239.0000
TH232	0.2429E-02	0.2380E-02	0.2380E-02	0.2332E-02	0.2332E-02	0.2284E-02	0.2284E-02	0.2216E-02	0.2236E-02	0.2193E-02

PA233	0.5598E-04	0.6062E-04	0.5908E-04	0.6138E-04	0.5983E-04	0.6105E-04	0.5950E-04	0.6023E-04	0.5870E-04	0.5920E-04
PA234	0.1227E-07	0.1567E-06	0.1296E-07	0.1587E-06	0.1313E-07	0.1579E-06	0.1306E-07	0.1558E-06	0.1289E-07	0.1532E-06
U233	0.3429E-04	0.3787E-04	0.3941E-04	0.4068E-04	0.4223E-04	0.4190E-04	0.4345E-04	0.4216E-04	0.4365E-04	0.4189E-04
U234	0.1799E-04	0.2511E-04	0.2526E-04	0.3155E-04	0.3170E-04	0.3695E-04	0.3710E-04	0.4431E-04	0.4146E-04	0.4474E-04
U235	0.2476E-05	0.4044E-05	0.4044E-05	0.5626E-05	0.5626E-05	0.7080E-05	0.7080E-05	0.8338E-05	0.8338E-05	0.9379E-05
U236	0.3538E-06	0.7915E-06	0.7915E-06	0.1429E-05	0.1429E-05	0.2248E-05	0.2248E-05	0.3215E-05	0.3215E-05	0.4293E-05
U237	0.4182E-08	0.1122E-07	0.1013E-07	0.2135E-07	0.1926E-07	0.3480E-07	0.3140E-07	0.5108E-07	0.4609E-07	0.6954E-07
U238	0.1854E-08	0.6098E-08	0.6098E-08	0.1486E-07	0.1486E-07	0.2988E-07	0.2988E-07	0.5261E-07	0.5261E-07	0.8413E-07
NP237	0.6968E-08	0.2041E-07	0.2151E-07	0.4740E-07	0.4948E-07	0.9073E-07	0.9412E-07	0.1520E-06	0.1569E-06	0.2310E-06
NP238	0.1352E-09	0.6080E-09	0.4385E-09	0.1443E-08	0.1040E-08	0.2803E-08	0.2021E-08	0.4744E-08	0.3421E-08	0.7269E-08
NP239	0.7187E-11	0.3341E-10	0.2488E-10	0.8407E-10	0.6260E-10	0.1728E-09	0.1287E-09	0.3092E-09	0.2302E-09	0.5004E-09
PU236	0.6621E-09	0.2485E-08	0.2655E-08	0.6982E-08	0.7384E-08	0.1547E-07	0.1625E-07	0.2909E-07	0.3041E-07	0.4856E-07
PU239	0.1228E-09	0.5532E-09	0.5617E-09	0.1689E-08	0.1710E-08	0.3977E-08	0.4021E-08	0.7840E-08	0.7919E-08	0.1359E-07
PU240	0.2521E-10	0.1392E-09	0.1392E-09	0.4836E-09	0.4836E-09	0.1254E-08	0.1254E-08	0.2664E-08	0.2664E-08	0.4896E-08
PU241	0.8343E-11	0.5395E-10	0.5395E-10	0.2089E-09	0.2089E-09	0.5865E-09	0.5865E-09	0.1322E-08	0.1322E-08	0.2545E-08
PU242	0.1718E-11	0.1501E-10	0.1501E-10	0.7452E-10	0.7452E-10	0.2574E-09	0.2574E-09	0.6935E-09	0.6935E-09	0.1561E-08
KR85M	0.0	0.8078E-08	0.0	0.8817E-08	0.0	0.9225E-08	0.0	0.9418E-08	0.0	0.9481E-08
KR87	0.0	0.4167E-08	0.0	0.4553E-08	0.0	0.4767E-08	0.0	0.4871E-08	0.0	0.4977E-08
KR88	0.0	0.1225E-07	0.0	0.1340E-07	0.0	0.1405E-07	0.0	0.1438E-07	0.0	0.1450E-07
XE133	0.4460E-06	0.6220E-06	0.5855E-06	0.7021E-06	0.6157E-06	0.7531E-06	0.6604E-06	0.7834E-06	0.6870E-06	0.8002E-06
XE134	0.6540E-08	0.4775E-07	0.7782E-08	0.5285E-07	0.8613E-08	0.5598E-07	0.9124E-08	0.5779E-07	0.9419E-08	0.5873E-07
FLUX(W/CM2SEC)	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16	0.0	0.2590E 16
POWER(W/CC)	0.0	0.4873E 03	0.0	0.5362E 03	0.0	0.5656E 03	0.0	0.5820E 03	0.0	0.5901E 03
FISSIONS/CCSEC	0.0	0.1690E 14	0.0	0.1859E 14	0.0	0.1961E 14	0.0	0.2018E 14	0.0	0.2046E 14
FISSIONS/CC	0.5705E 20	0.8863E 20	0.8863E 20	0.1245E 21	0.1245E 21	0.1629E 21	0.1629E 21	0.2030E 21	0.2030E 21	0.2438E 21
FINA	0.2197E-01	0.3413E-01	0.3413E-01	0.4792E-01	0.4792E-01	0.6275E-01	0.6275E-01	0.7816E-01	0.7816E-01	0.9389E-01
MWD/MT	0.1871E 05	0.2907E 05	0.2907E 05	0.4083E 05	0.4083E 05	0.5345E 05	0.5345E 05	0.6658E 05	0.6658E 05	0.7999E 05
POWER(KW/FT)	0.0	0.1807E 02	0.0	0.1988E 02	0.0	0.2097E 02	0.0	0.2158E 02	0.0	0.2188E 02

CONC(ATOMS/BARN CM)	240.0000	263.0000	264.0000	287.0000	288.0000
---------------------	----------	----------	----------	----------	----------

TR232	0.2193E-02	0.2149E-02	0.2149E-02	0.2105E-02	0.2105E-02
PA233	0.5770E-04	0.5809E-04	0.5662E-04	0.5696E-04	0.5552E-04
PA234	0.1267E-07	0.1503E-06	0.1243E-07	0.1474E-06	0.1219E-07
U233	0.4339E-04	0.4134E-04	0.4281E-04	0.4065E-04	0.4209E-04
U234	0.4488E-04	0.4734E-04	0.4748E-04	0.4927E-04	0.4940E-04
U235	0.9379E-05	0.1021E-04	0.1021E-04	0.1086E-04	0.1086E-04
U236	0.4293E-05	0.5446E-05	0.5446E-05	0.6644E-05	0.6644E-05
U237	0.6275E-07	0.8956E-07	0.8081E-07	0.1105E-06	0.9974E-07
U238	0.8413E-07	0.1251E-06	0.1251E-06	0.1758E-06	0.1758E-06
NP237	0.2378E-06	0.3265E-06	0.3353E-06	0.4363E-06	0.4471E-06
NP238	0.5242E-08	0.1034E-07	0.7455E-08	0.1388E-07	0.1001E-07
NP239	0.3726E-09	0.7509E-09	0.5591E-09	0.1063E-08	0.7914E-09
PU238	0.5059E-07	0.7413E-07	0.7702E-07	0.1056E-06	0.1095E-06
PU239	0.1371E-07	0.2138E-07	0.2157E-07	0.3122E-07	0.3149E-07
PU240	0.4896E-08	0.8076E-08	0.8076E-08	0.1226E-07	0.1226E-07
PU241	0.2545E-08	0.4354E-08	0.4354E-08	0.6806E-08	0.6806E-08
PU242	0.1561E-08	0.3068E-08	0.3068E-08	0.5428E-08	0.5428E-08
KR85M	0.0	0.9465E-08	0.0	0.9400E-08	0.0
KR87	0.0	0.4901E-08	0.0	0.4870E-08	0.0
KR88	0.0	0.1449E-07	0.0	0.1441E-07	0.0
XE133	0.7017E-06	0.8081E-06	0.7087E-06	0.8101E-06	0.7104E-06
XE135	0.9572E-08	0.5911E-07	0.9635E-08	0.5913E-07	0.9638E-08

FLUX(W/CM2SEC)	0.0	0.2590E 16	0.0	0.2590E 16	0.0
POWER(W/CC)	0.0	0.5929E 03	0.0	0.5922E 03	0.0
FISSIONS/CCSEC	0.0	0.2056E 14	0.0	0.2054E 14	0.0
FISSIONS/CC	0.2438E 21	0.2850E 21	0.2850E 21	0.3263E 21	0.3263E 21
FINA	0.9389E-01	0.1098E 00	0.1098E 00	0.1256E 00	0.1256E 00
MWD/MT	0.7999E 05	0.9350E 05	0.9350E 05	0.1070E 06	0.1070E 06
POWER(KW/FT)	0.0	0.2198E 02	0.0	0.2196E 02	0.0

TOTAL BIRTH RATES(ATOMS/SEC)

TIME(DAYS)	KR85M	KR87	KR88	XE133	XE135
0.0	0.144E 12	0.276E 12	0.398E 12	0.751E 12	0.729E 12
12.000	0.114E 12	0.220E 12	0.316E 12	0.593E 12	0.575E 12
23.000	0.966E 11	0.185E 12	0.265E 12	0.487E 12	0.474E 12
24.000	0.0	0.0	0.0	0.0	0.0
36.000	0.842E 11	0.160E 12	0.228E 12	0.404E 12	0.394E 12
47.000	0.766E 11	0.145E 12	0.204E 12	0.348E 12	0.341E 12
48.000	0.0	0.0	0.0	0.0	0.0
60.000	0.720E 11	0.135E 12	0.189E 12	0.306E 12	0.300E 12
71.000	0.690E 11	0.129E 12	0.179E 12	0.276E 12	0.272E 12
72.000	0.0	0.0	0.0	0.0	0.0
84.000	0.112E 12	0.207E 12	0.283E 12	0.409E 12	0.406E 12
95.000	0.107E 12	0.197E 12	0.267E 12	0.364E 12	0.364E 12
96.000	0.0	0.0	0.0	0.0	0.0
108.000	0.111E 12	0.203E 12	0.273E 12	0.354E 12	0.355E 12
119.000	0.115E 12	0.210E 12	0.281E 12	0.353E 12	0.356E 12
120.000	0.0	0.0	0.0	0.0	0.0
132.000	0.122E 12	0.224E 12	0.299E 12	0.368E 12	0.372E 12
143.000	0.126E 12	0.231E 12	0.308E 12	0.377E 12	0.381E 12
144.000	0.0	0.0	0.0	0.0	0.0
156.000	0.133E 12	0.242E 12	0.323E 12	0.394E 12	0.398E 12
167.000	0.135E 12	0.246E 12	0.328E 12	0.401E 12	0.406E 12
168.000	0.0	0.0	0.0	0.0	0.0
180.000	0.139E 12	0.254E 12	0.339E 12	0.415E 12	0.420E 12
191.000	0.140E 12	0.256E 12	0.341E 12	0.419E 12	0.424E 12

192.000	0.0	0.0	0.0	0.0	0.0
204.000	0.143E 12	0.261E 12	0.349E 12	0.430E 12	0.434E 12
215.000	0.142E 12	0.260E 12	0.348E 12	0.431E 12	0.435E 12
216.000	0.0	0.0	0.0	0.0	0.0
228.000	0.144E 12	0.264E 12	0.353E 12	0.439E 12	0.443E 12
239.000	0.143E 12	0.262E 12	0.350E 12	0.438E 12	0.442E 12
240.000	0.0	0.0	0.0	0.0	0.0
252.000	0.144E 12	0.264E 12	0.354E 12	0.443E 12	0.447E 12
263.000	0.143E 12	0.261E 12	0.350E 12	0.440E 12	0.444E 12
264.000	0.0	0.0	0.0	0.0	0.0
276.000	0.144E 12	0.263E 12	0.352E 12	0.444E 12	0.448E 12
287.000	0.142E 12	0.260E 12	0.348E 12	0.441E 12	0.444E 12
288.000	0.0	0.0	0.0	0.0	0.0

ACKNOWLEDGMENTS

The author is grateful to H. T. Kerr for his help in structuring the program, and to B. H. Montgomery and K. R. Thoms for their many helpful comments.

REFERENCES

1. E. J. Allen, Oak Ridge National Laboratory, unpublished internal document (June 20, 1975).
2. M. J. Bell, *ORIGEN - The ORNL Isotope Generation and Depletion Code*, ORNL-4628 (May 1973).
3. H. C. Roland, *FABGEN, A Transient Power-Generation and Isotope Birth-rate Calculator*, ORNL-TM-4750 (April 1975).

ORNL/TM-5266

UC-77 — Gas-Cooled Reactor
TechnologyInternal Distribution

1-5. E. J. Allen	37. W. J. McCarthy
6. R. L. Beatty	38. S. R. McNeany
7. E. E. Bloom	39. B. H. Montgomery
8. T. E. Cole	40. H. Postma
9. J. A. Conlin	41. G. L. Ragan
10. J. H. Coobs	42. J. E. Rushton
11. W. B. Cottrell	43. J. P. Sanders
12. F. L. Culler	44. J. D. Sease
13. W. P. Eatherly	45. R. L. Senn
14. J. R. Engel	46. Myrtle Sheldon
15. G. G. Fee	47. R. L. Shepard
16. R. M. Flanders	48. T. M. Sims
17. M. H. Fontana	49. I. Spiewak
18. T. A. Gabriel	50. J. H. Swanks
19. Uri Gat	51. J. J. Taylor
20. M. J. Goglia	52. W. E. Thomas
21. H. W. Hoffman	53. K. R. Thoms
22. F. J. Homan	54. M. L. Tobias
23. C. R. Hyman	55. D. B. Trauger
24. J. D. Jenkins	56. K. H. Valentine
25. M. J. Kania	57. T. N. Washburn
26-28. P. R. Kasten	58. G. D. Whitman
29. H. T. Kerr	59. F. W. Wiffen
30. R. W. Knoll	60. W. J. Wilcox
31. T. B. Lindemer	61. R. M. Young
32. E. L. Long, Jr.	62. ORNL Patent Office
33. A. W. Longest	63-64. Central Research Library
34. A. L. Lotts	65. Document Reference Section
35. R. E. MacPherson	66-68. Laboratory Records Department
36. M. M. Martin	69. Laboratory Records (RC)

External Distribution

- 70-71. Director, Division of Nuclear Research and Application, ERDA,
Washington, D.C. 20545
72. Director, Reactor Division, ERDA-ORO
73. Research and Technical Support Division, ERDA-ORO
- 74-235. Technical Information Center, ERDA [For distribution as shown in
TID-4500 under category UC-77, Gas-Cooled Reactor Technology
(25 copies — NTIS)]