BROOKHAVEN NATIONAL LABORATORY

Annual Report

Department of Applied Science

December 31, 1969

WARREN E. WINSCHÉ, Chairman

F.T. MILES, Deputy Chairman

BROOKHAVEN NATIONAL LABORATORY

Associated Universities, Inc.

Upton, New York

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

Printed in the United States of America

Available from

Clearinghouse for Federal Scientific and Technical Information

National Bureau of Standards, U.S. Department of Commerce

Springfield, Virginia 22151

Price: Printed Copy \$3.00; Microfiche \$0.65

March 1970

725 copies

CONTENTS

SUMMARY.....	v
REACTOR PHYSICS DIVISION (04-40-01-02-1, 04-60-70-01-1)*.....	1
Reactor Physics Theoretical Group.....	1
Reactor Physics Analysis Group.....	3
Reactor Physics Experimental Group.....	8
NUCLEAR MATERIALS DIVISION (02-40-01-00-0).....	16
NATIONAL NEUTRON CROSS SECTION CENTER (04-40-01-03-1, 05-03-01-03-0).....	26
Cross Section Compilation Activities.....	26
Cross Section Evaluation Activities.....	27
Computer Applications.....	29
Cross Section Theory.....	31
EVALUATION AND TECHNICAL ASSISTANCE GROUP (04-01-91-01-0).....	33
CHEMISTRY DIVISION (05-05-03-00-0).....	35
Physical Organic Chemistry.....	35
Metal Hydrides.....	40
High-Temperature Chemistry.....	46
RADIATION DIVISION (04-40-04-03-1, 05-05-03-00-0, 08-03-02-01-0, 08-04-01-00-0, 40-04-00-00-0).....	50
Radiation Research.....	50
Chemonuclear Program.....	52
Radiation Chemical Processing.....	55
Radiation Chemical Engineering.....	60
Radiation Engineering.....	61
Atmospheric Diagnostics Program.....	67
Exploratory Research and Development.....	72
HOT LABORATORY DIVISION (05-05-03-00-0, 08-01-04-00-0, 04-40-04-04-1).....	78
Nuclear and Radiochemical Research.....	78
Analytical Chemistry Research.....	85
Medical Radionuclides.....	88
Hot Laboratory Operations.....	91
METALLURGY AND MATERIALS SCIENCE DIVISION (04-40-02-02-1, 04-40-02-03-1, 05-06-01-02-0).....	93
Sodium Technology.....	93
Superconductivity.....	120
Irradiation Effects.....	129
ENGINEERING DIVISION (04-40-03-01-1, 04-50-50-01-1, 04-60-01-10-1, 04-60-40-03-1).....	134
Heat Transfer Studies.....	134
Waste Disposal Studies.....	141
Safety Studies.....	151
Engineering Assistance Group.....	160
Pulsed Research Reactor Study.....	161

*AEC budget activity numbers.

SUMMARY

INTRODUCTION

The program of the Department of Applied Science can be divided into three categories. The first is basic research, which encompasses fundamental studies in reactor physics, chemistry, and metallurgy. Studies are also being carried out on reactor materials at high temperatures, fission product release, liquid-metal heat transfer, and superconductivity in metals.

In the second category is the long-range work of developing components that may bring about significant advances in reactor technology, radiation application, and nuclear medicine. Some of the more important phases of this work are the development of concrete-polymer materials, utilization of fluidized beds for water desalination, radiation engineering methods, waste processing devices, direct conversion concepts, radioisotopes for medical application, and isotopes for atmospheric diagnostics.

The engineering and evaluation studies and the safeguarding of nuclear materials, the third category, are focused on practical application of the work in the preceding categories. Typical studies were concerned with the use of hydroelectric pumped storage and nuclear power, and a review and evaluation of the reactor operating and maintenance account. Assistance was given to the Division of Reactor Development and Technology of the Atomic Energy Commission in the updating of earlier US AEC Reports to the President on Civilian Nuclear Power.

H. J. Kouts asked to be relieved of his duties as Associated Head of the Reactor Physics Division for experimental reactor physics in order to concentrate on his duties as Head of the Nuclear Materials Division. In November, J. Chernick was appointed Head of the Reactor Physics Division for both experimental and theoretical reactor physics.

In May J. Chernick returned from a six-month sabbatical leave at the Puerto Rico Nuclear Center of the University of Puerto Rico at Mayaguez. He presented a review paper on BNL work on Fast Reactor Data, Codes and Integral Experiments at the 1969 BNES International Conference on the Physics of Fast Reactor Operation and Design,

London, June 24-26, 1969. He then participated in the IAEA Meeting of Specialists on The Value of Plutonium Alpha, held at Winfrith, England, June 30-July 1, 1969.

M. Levine left in September for a one-year assignment to Winfrith, England, as US AEC representative for fast reactor physics.

P. Palmedo attended the meeting of the European American Committee on Reactor Physics in London in February 1969.

The National Neutron Cross Section Center served as BNL host to the IAEA-sponsored Panel on Neutron Data Compilation held at BNL on February 10-14, 1969; the meeting was attended by thirty-two participants from twelve countries.

A. Prince presented a paper, entitled Nuclear and Physical Properties of ^{252}Cf , at the Californium-252 Symposium held October 22, 1968, in New York City and sponsored by the New York Metropolitan Section of the American Nuclear Society. He also delivered a colloquium on nuclear properties of ^{252}Cf at the Physics Department of the University of Dayton, April 17, 1969.

S. Pearlstein participated in the Discussion Meeting on Nuclear Data held November 6, 1968, by the National Research Council, Washington, D.C.

M. Goldberg represented the National Neutron Cross Section Center at the Four-Centre (i.e., four principal neutron data centers) Meeting held at IAEA Headquarters, Vienna, November 30, 1968.

S. Pearlstein chaired the session on Nuclear Data at the June 16-19, 1969, meeting of the American Nuclear Society held in Seattle, Washington.

M. Drake was invited to present a paper, entitled Numerical Data Handling Techniques Used at the National Neutron Cross Section Center, at the Gordon Conference held July 21-23, 1969, in Tilden, New Hampshire.

T. Krieger delivered a lecture, entitled Activities of the National Neutron Cross Section Center, at the Nuclear Engineering Department of the University of Michigan, Ann Arbor, on September 19, 1969.

S. Pearlstein presented a paper, entitled The Evaluated Nuclear Data File and Cross Section Evaluation Working Group - Background and

Status, at an internationally attended workshop sponsored by the Radiation Shielding Information Center and held at Oak Ridge National Laboratory on October 1-3, 1969.

S. Pearlstein represented the National Neutron Cross Section Center at the fifth meeting of the world's four neutron data centers, held in Moscow, USSR, November 17-21, 1969.

C. Sastre visited the IAEA Headquarters in Vienna to consult with the staff on security seals. He also visited the site of the Marviken Reactor in Sweden and the NOK Reactor in Switzerland.

W. Higinbotham attended the IAEA Panel on Safeguards Methods for Conversion Plants and Fuel Fabrication Plants in Vienna, April 14-18, 1969. He also visited facilities at Ispra, Italy and Mol, Belgium.

H. Kouts attended the IAEA Panel on Safeguards Systems Analysis of Nuclear Fuel Cycles in Vienna, August 25-29, 1969.

W. Marcuse joined the Nuclear Materials Division this year. He came from the MITRE Corp. where he was Associate Department Head of the Systems Analysis Department.

B. Manowitz attended the IAEA Symposium on the Utilization of Large Radiation Sources and Accelerators in Industrial Processing, held at Munich, Germany, in August 1969. He presented papers on concrete-polymer materials and on the application of chemical reactor design principles to dosimetry in flow systems.

D. Metz made two lecture tours for the American Chemical Society and spoke at eight institutions on Radiation-Induced Ionic Polymerization. He also served as general chairman of a two-day seminar presented by the Radiation Division on Research in Radiation Chemical Processing for the faculty of schools of chemical and nuclear engineering. Thirty-five colleges and universities were represented by more than fifty staff members.

Concrete-polymer received a 1969 IR-100 award as one of the 100 most significant products developed in the U.S. during the year.

J. Sutherland delivered an invited seminar at the AECL Laboratories at Chalk River, Canada, in May 1969 on radiolysis in the absorbed state.

J. Weiss was elected to the position of Counselor for Chemistry, Radiation Research Society, for a term of three years.

B. Manowitz was elected to the Executive Committee of the Isotopes and Radiation Division and W. Tucker was appointed Program Chairman of

the Remote Systems Technology Division of the ANS for 1969-70. Both served as session chairmen of the ANS meeting in San Francisco in December 1969.

M. Steinberg presented an invited seminar on concrete-polymers at the Pacific-Northwest Plastics Workshop held at Washington State University, Pullman, Washington, in June 1969.

D. Huszagh served as IAEA consultant on the design of the large-scale food irradiation pilot plant being built in Buenos Aires, Argentina.

E. Divis supervised the installation of a Brookhaven Portable Cesium Development Irradiator in Buenos Aires and visited Santiago, Chile, for discussions on the unit to be installed there.

J. Cassidy supervised the removal of the ship-board irradiator from its installation in Reykjavik, Iceland, in preparation for its shipment to BNL and eventual reassignment to Seoul, South Korea.

F. Rizzo was a speaker in the IAEA-sponsored lecture series in food technology for the training of foreign technicians held at Massachusetts Institute of Technology.

J. Cusack, L. Galanter, and F. Rizzo participated in meetings with the AECL at Ottawa that established cooperative programs on source standardization and dosimetric techniques.

J. Cusack chaired an international symposium on source standardization held at BNL and attended by representatives of Great Britain, France, Canada, Chile, and of U.S. suppliers and users of radiation sources.

M. Isildar arrived from the Middle East Technical Institute, Turkey, to spend a year at BNL studying solid state polymerization techniques under the direction of G. Adler.

B. Manowitz presented invited papers on the Atmospheric Diagnostics Program at the Gatlinburg Isotopes Conference in April 1969 and at the Institute of Electrical and Electronic Engineers Nuclear Science Symposium in San Francisco in October 1969.

J. Weiss was appointed to an ad hoc committee on radiation measurements for the National Committee on Radiation Protection.

G. Adler was editor of a textbook, *Organic Solid State Chemistry*, published by Gordon and Breach Science Publishers.

L. Stang resigned as Editor of the American Nuclear Society's journal *Nuclear Applications*, a position he had held since the journal was founded in 1964, and received the Society's Distinguished

Service Award for "... his effective, diligent, efficient, and successful service, ... unselfish devotion, ... and many other exceptional services." He also presented an invited paper at the Third Annual Meeting of the Sociedad Mexicana de Medicina Nuclear, at Puebla, Mexico, April 1969.

C. Auerbach continued as Editor of *Chemical Instrumentation*, a quarterly journal published by M. Dekker.

M. Hillman co-authored a chapter, entitled Szilard-Chalmers Processes for Isotope Production, with G. Harbottle (Chemistry Department) for the IAEA *Manual of Radioisotope Production*. He also presented an invited seminar on Nuclear Level Densities at the Virginia Polytechnic Institute, Blacksburg, Virginia, April 24, 1969.

M. Hillman and B. Gordon attended the Heavy Element Symposium in Houston, Texas, November 17-19, 1969.

S. Feldberg presented invited papers on techniques of digital simulation of electrochemical problems at the Gordon Research Conference on Electrochemistry, Santa Barbara, California, January 1969, and at the New Orleans American Chemical Society Section Meeting, March 1969. He presented a series of invited lectures on the same subject at Colorado State University and discussed his work (by invitation) with members of the Chemistry Departments of Kansas University, Texas University, Louisiana State University, and Case-Western Reserve University.

P. Richards presented an invited paper at the meeting on Radiation and Isotope Technology in Latin America Development, San Juan, Puerto Rico, May 1969, and spent several days helping set up a medical radionuclide program at the Puerto Rico Nuclear Center. He also attended by invitation an AEC working meeting on cyclotron-produced medical radionuclides, St. Louis, Missouri, February 1969, and by invitation spoke on the status of short-lived isotope generators and the use of ^{99m}Tc in radiopharmaceuticals at the Radiological and Medical Physics Society of New York, New York City, January 1969.

J. Gilat gave invited seminars on the calculation of nuclear level densities and nucleon evaporation at the University of Rochester and the Lawrence Radiation Laboratory (Berkeley) in October 1969.

J. Galligan presented invited talks on radiation effects at Michigan State University, University of Kentucky, Long Island Chapter of ASM, University of Delaware, and Oak Ridge National Laboratory.

J. Weeks organized a symposium on liquid metal corrosion for the Metals Congress in October 1969. He also gave an invited talk on Metallurgy in the Nuclear Profession at Polytechnic Institute of Brooklyn on December 3, 1969.

D. Gurinsky organized a panel discussion at a 2-day Seminar on Corrosion in Nuclear and Conventional Power Plant Systems, held at Polytechnic Institute of Brooklyn, May 22-23, 1969, in New York. J. Weeks was a panelist.

M. Garber was invited as a speaker for the Brookhaven Semester Program at Tuskegee Institute, Tuskegee, Alabama, May 1969. In the fall of 1969 he was invited by Prof. M. Yaquob of Ohio State University's Physics Dept. for informal discussions of research of mutual interest.

T. Sheehan is a member of the Executive Committee of the ASME Nuclear Engineering Division, and he was the Papers Review Chairman for the Nuclear Engineering Division at the ASME Winter Annual Meeting in Los Angeles, California, November 16-20.

J. Hendrie was elected in December to fill the position of Vice-Chairman of the Advisory Committee on Reactor Safeguards, of which he has been a member for the past three years.

REACTOR PHYSICS DIVISION (04-40-01-02-1, 04-60-70-01-1)

The research in theoretical reactor physics continued to be concentrated in areas that lead to better understanding of fast reactors. These included the development of energy-space flux synthesis methods in neutron transport theory, advances in reactor kinetics, resonance absorption of neutrons, and the theory of pulsed fast reactors. The analysis was carried out of a number of experiments performed both at BNL and elsewhere in support of LMFBR objectives.

At the beginning of the year, the most serious unresolved problem in fast reactor physics was the uncertainty in the value of α for ^{239}Pu in the 1 to 10-keV energy range. As the year ended, the results from both differential and integral measurements were converging in this energy range, although considerable uncertainty remained at higher energies. The analysis of BNL experiments on Pu-Al rods in heavy water lattices contributed to the agreement, particularly at the lower end of this energy range. Further work on the analysis of the BNL experiments continued, including its pos-

sible extension to harder spectra. The analysis of heterogeneity experiments performed in BNL's FS-1 fast critical assembly was also carried out as was a preanalysis of a second experiment on α_{49} which involved the irradiation of pure ^{239}Pu boron-shielded foils in BNL's High Flux Beam Research Reactor.

The reanalysis of a number of light and heavy water critical experiments, aimed at testing the adequacy of the current ENDF/B library, was completed. This work raised questions not only of some of the ENDF/B data but also of some of the standard codes used to analyze thermal reactor data. Similarly, the BNL analysis of fast integral experiments revealed a number of inadequacies in standard codes prepared for the LMFBR program. The studies of energy-space flux synthesis for typical fast reactors showed that good agreement on reactivity and the neutron spectrum in the interior of the core is obtainable with relatively simple methods, but more complex techniques are required for good accuracy within the blanket.

The work on reactor kinetics included the study of spatial effects in reactor transients and showed that these were quite important in rapid excursions. A generalization of the prompt-jump approximation was developed as a means of increasing the size of the time step adequate for accurate fast reactor dynamics calculations. A powerful and rather general method was developed to determine bounds on allowable disturbances about equilibrium in linearly stable reactors.

In theoretical work on pulsed fast reactors, the time dependence after the pulse was investigated with the use of neutron moderation models that retain continuous lethargy dependence, and thus errors inherent in multigroup calculations are avoided. The disappearance of a purely exponential time decay mode for sufficiently subcritical fast assemblies was proven.

Computer code developments included the reactor dynamics code package NOMURK, and the Monte Carlo codes MOCA and REPCDC, which treat the high energy and resonance ranges in reactor lattices accurately. The MC² code and its auxiliaries was made operational on the CDC 6600 computer.

Work continued in Reactor Safety Evaluation Analysis for the Division of Licensing of the US AEC. The objectives here are to test safety aspects of current US power reactors. The subjects treated included control rod effectiveness, Doppler coeffi-

cients and moderator coefficients of reactivity, aspects of xenon and temperature transients, reactivity changes associated with conceivable changes in core geometry, and the response of external detectors to tilts in power distributions within the reactor core.

Work in the Experimental Reactor Physics Group was devoted exclusively to tasks in support of the LMFBR program. These tasks include studies of heterogeneous effects in fast reactors, measurements of delayed neutron parameters, fast neutron spectroscopy, Pu-Al-D₂O lattice measurements, a plutonium alpha experiment, and a compilation of fast reactor experiments.

Heterogeneity effects were studied in the central test zone of the FS-1 fast critical assembly. Activation rates and fine structure distributions were observed with ^{235}U and ^{238}U fission foils and Mn foils. The measured distributions were found to be in good agreement with preliminary DSN calculations. Similar measurements are continuing with cells having differing thicknesses of ^{235}U fuel plates.

The total delayed neutron fraction β was measured for thermal fission of ^{235}U . An important aspect of this experiment was the use of a detector with near-constant response to neutrons with energies between 25 keV and 3 MeV. The basic approach was to compare the prompt plus delayed neutron count rate, due to a ^{235}U sample in the neutron beam, with the integral count due to delayed neutrons after the termination of the neutron beam. The results of the measurements yielded a preliminary value for β of 0.00653 ± 0.00025 , which is in agreement with the currently accepted value.

A machine has been built and mechanically tested for the continuous production of delayed neutrons utilizing a continuous belt of ^{235}U ribbon. It will be installed in Neutron Source Reactor I as soon as an annex can be built to contain it. When installed, it will be possible to measure relative yields, half-lives, and energy spectra for each of the delayed neutron groups. Work has continued to refine a proton-recoil detector that will be used to measure the energy spectra of delayed neutrons.

Measurements were completed on a series of 13 exponential lattices utilizing Pu-Al fuel rods in heavy water. These data serve as bench marks for the evaluation of epithermal plutonium cross sections, since the neutron spectra of the lattices vary considerably with the degree of moderation. Preliminary analysis of the data indicates some defi-

ciencies in ENDF/B cross sections for plutonium. A complete analysis is currently being conducted by the Theoretical Reactor Physics Group.

Six ^{239}Pu foils were irradiated in the HFBR for 16 days for the purpose of determining the average value of alpha (capture-to-fission ratio) for ^{239}Pu in the epithermal neutron energy range. ^{240}Pu production rates and fission yields from these foils are now being measured by mass-spectrometric methods at Idaho Nuclear Corp.

Data from the ZPR-3, 6, and 9 assemblies have been collected for the first volume of the fast reactor experiment compilation. These data are currently under review by physicists at ANL. Agreements have been obtained from the principal foreign laboratories engaged in fast reactor physics to contribute to the compilation, and data from those laboratories are also being collected.

NUCLEAR MATERIALS DIVISION (02-40-01-00-0)

The Nuclear Materials Division acts as a Technical Support Organization (TSO) for the US AEC's Office of Safeguards and Materials Management (OSMM). The function of the group is to provide technical advice and guidance to the OSMM in a number of areas related to research and development in safeguards.

At the request of OSMM, TSO assembled instrumentation for making passive gamma and neutron measurements, and has used them in field tests at four selected plants. Measurements applicable to safeguards were made of $\text{PuO}_2\text{-UO}_2$ fuel rods, unirradiated PuO_2 scrap in 55-gal drums, concentrated PuO_2 scrap in 2-liter bottles, and small Pu-Al alloy platelets intended for use in a critical assembly. TSO also organized and participated in visits to fuel fabricators and reprocessors to familiarize contractors, now developing measuring techniques for safeguards, with the operation of these plants.

The Technical Support Organization assisted OSMM by providing an observer at the Nuclear Fuel Services plant during an IAEA safeguards inspection involving chemical processing of Yankee reactor fuel. The objective of this task was to develop a written record of observation and a partial evaluation of the IAEA inspection.

In order to evaluate their suitability for safeguards application, a study was made of available accelerator sources. The study considered linacs

and microtrons as electron sources for producing bremsstrahlung, and accelerator sources of positive ions for producing high energy neutron beams. In addition, the use of methods depending on slower neutrons (slowing-down spectrometer and reactivity methods) was also investigated.

The responsibility for conducting the OSMM systems studies program is divided between Battelle Northwest Laboratory, the National Bureau of Standards, and TSO. Part of the BNL effort was spent in reviewing the models developed by Battelle Northwest Laboratories and the National Bureau of Standards. The control elements of a safeguards system have been identified, and consideration is being given to a logical definition of the responsibility and action of each of the participants (industry, national government and international agencies) in relation to these elements. A paper describing the system of safeguards in existence in the US and summarizing safeguard systems studies was prepared with OSMM for presentation to an IAEA panel. A computer simulation has been initiated to replicate the flow of nuclear material in the fuel cycle. This simulation is intended both for analysis and design of safeguards alternatives.

The New Brunswick Laboratory, OSMM, and TSO are cooperating in a safeguards analytical laboratory evaluation program. The New Brunswick Laboratory will be the control laboratory and most of the analytical laboratories in the US that are used in Nuclear Materials Safeguards will participate.

An evaluation of the role of seals in Nuclear Materials Safeguards has been completed, and resulted in identification (and, in some cases, possible solutions) of problem areas.

Work has started on the development of criteria for identification of light water power reactor fuel assemblies. The object is to have a unique assignment of letters and numbers for fuel assemblies so that they are readable under the usual depth of water encountered in spent fuel storage ponds.

A glossary of special terms in the field of Nuclear Safeguards was prepared by TSO and has been circulated in the US and abroad for comments.

NATIONAL NEUTRON CROSS SECTION CENTER (04-40-01-03-1, 05-03-01-03-0)

The National Neutron Cross Section Center served as BNL host to the IAEA-sponsored Panel

on Neutron Data Compilation held at BNL in February 1969, at which many of the questions concerning the cooperative and exchange programs of the world's four neutron data centers were resolved.

A PDP-10 computer facility has been installed at the Center to improve the accuracy and reliability of the NNCSC's data files.

The merging of all usable data from the old Sigma Center files into the NNCSC's computer library of experimental data has been completed and an "author proof" system implemented to insure the accuracy of newly entered data.

Specifications were completed for a format to allow a large variety of bibliographic and data information to be transmitted among the four neutron data centers. All new data received at the NNCSC are being entered into this format, as well as into the format used in the Center's existing system for experimental neutron data (SCISRS I).

Various programs and subroutines comprising the new version of the NNCSC's neutron data system (SCISRS II) have been documented.

Work has been completed on computer-prepared angular distribution plots for automated production of BNL 400, *Angular Distributions in Neutron-Induced Reactions*.

Initial specifications have been defined for codes that will be used to perform physics and numerical checks on data in the evaluated neutron data system (ENDF/B). In addition, the series of computer codes developed for the "author proofs" of experimentally measured cross section data are being modified to include graphical displays of evaluated data from the ENDF/B library.

As part of the physics checking effort, the calculation of the infinite dilution resonance integrals for materials in the ENDF/B library has been completed.

Data revisions have been recommended for non-fissile materials in the ENDF/B library (deuterium, carbon, sodium, boron-10, iron, nickel, chromium, tungsten, and tantalum). Revised data sets were also recommended for the major fissile and fertile nuclides and were subsequently prepared. These revisions include recent cross section measurements and are to be incorporated in a revised version of the ENDF/B library.

As a part of the effort to obtain revised cross sections for the fissile and fertile materials, all of the model calculations for ^{238}U , ^{239}Pu , ^{240}Pu , and ^{241}Pu were completed. The compound nucleus re-

action cross sections for ^{238}U , ^{240}Pu , and ^{239}Pu have also been calculated to 5 to 10% agreement with experimental data using a coupled-channel optical model.

Studies were made of the total neutron cross section of both iron and cobalt using a Breit-Wigner multilevel scattering formalism. Bound levels were required to give good agreement with measured capture and scattering cross sections.

The new version of the NNCSC's experimental neutron data system (SCISRS II) has been considered as composed of a data library (ELCID) and its supporting software system (MAHDI). Initial programs in the MAHDI system have been developed and are in operation.

Extensive graphics tools have been developed to facilitate cross section compilation and evaluation.

The connection between the "channel radius" and "potential scattering radius" as applied to cross section fitting techniques was analyzed and recommendation given that they be treated as distinct parameters.

Some progress has been made in the derivation of a time-dependent analysis of compound nucleus decay in the continuum region, whereby the decay of a wave packet in the interior region of the nucleon configuration space has been found to be exponential.

The lack of agreement in the literature as to the connection between the transmission coefficient T and $2\pi\langle I \rangle/D$ when the latter is ~ 1 has been traced to the different possible meanings associated with Γ and D .

EVALUATION AND TECHNICAL ASSISTANCE GROUP (04-01-91-01-0)

The Evaluation and Technical Assistance Group continued to assist the AEC in program reviews and the evaluation of specific areas of interest. New studies were started on pumped storage power systems and operating and maintenance costs for nuclear power plants.

The potential of hydroelectric pumped storage power when used in conjunction with nuclear base-load stations in US power generation is being determined. The power systems will be discussed along with their operating characteristics and unique features. The effect of pumped storage on plant capacity factors and other aspects of its projected market outlook are being assessed.

The operating and maintenance costs of nuclear plants are being studied. Cost data for different types of reactors and fossil-fueled plants are being reviewed and compared, and unique features influencing operating and maintenance costs, as well as the effect of operating life of the reactor plant on these costs, are being determined.

BNL is participating in the development of codes and standards applicable to the reactor field, as part of an AEC-sponsored program at ORNL and AI for the water reactor and LMFBR programs, respectively. Detailed comments on some 18 new standards and a revised set of 62 previously issued standards have been submitted thus far. Two draft standards were also reviewed for USA Standards Institute.

CHEMISTRY DIVISION (05-05-03-00-0)

The unique features that preliminary work had attributed to the thermal decomposition of perfluorobicyclohexyl were confirmed by detailed kinetic studies in which chlorine scavenger was used to minimize radical reactions. The rate-determining step, which is considered to be the rupture of the tertiary C—C bond between the two rings, has an activation energy of 67 kcal; this is presumably the value of the bond strength. The frequency factor remains extremely high ($10^{17.7} \text{ sec}^{-1}$). Experiments have also been done without scavengers on this and other systems in order to elucidate the reactions of radicals. A second case of CF_3 transfer has been found between two perfluoroisopropyl radicals.

Xenon difluoride, XeF_2 , was shown to be a useful fluorinating agent in the vapor phase. With aromatic hydrocarbons and their derivatives, substitution rather than addition reactions occur if the conditions are right. Among the products obtained were fluoronitrobenzenes and trifluorobenzenes.

Several types of reversible oxidation were shown to be possible for metalloporphyrins, a class of compounds which includes the prosthetic groups of chlorophyll and hemoglobin. Where the central metal atom has only a single oxidation state like magnesium, oxidation of the molecule occurs through the removal of one or two electrons from the organic ring structure, and a π -cation or dication is formed. Such compounds are sometimes very electrophilic. Thus, the dication of zinc tetraphenyl porphyrin was found to react with meth-

anol or water to yield a new class of compounds called isoporphyrins. If, however, the metalloporphyrin contains a central atom which can itself be oxidized, as can Fe(II) or Co(II) , the removal of one electron can result in the formation of, for instance, an ion of ferric or cobaltic porphyrin. Subsequent removal of a second electron produces a π -cation in the case of Fe and Co. With manganese, however, the metal itself is capable of a two-electron oxidation, and a Mn(II) porphyrin becomes a Mn(IV) porphyrin ion. The nature of the oxidation reactions was determined experimentally by optical and esr spectroscopy.

In the metal hydride program the emphasis continued to be on systems with a dissociation pressure of one atmosphere or more at or near room temperature. The higher hydride of niobium, NbH_2 , was found to belong to this class and also certain alloys of the group V metals with each other. One of these was the solid solution of composition TaV_2 , which took up hydrogen to nearly the composition TaV_2H_6 , although attempts to make a dihydride of unalloyed tantalum were unsuccessful. Pressure-temperature-composition diagrams were obtained on these metals and alloys, with special attention to the (rather large) effects of small amounts of impurities. An unexpectedly large difference was noticed between the hydrogen uptake of TaV_2 solid solution and the intermetallic compound of the same composition produced by annealing. The progressive addition of hydrogen to vanadium and to niobium was found to decrease markedly the paramagnetism of the metals. Quantitative data were obtained over a wide range of compositions.

Techniques have been perfected for studying atomic motions in molten salts by measuring the energy distribution in a beam of cold neutrons scattered by the salt. The results in the case of KCl-MgCl_2 mixtures were interpreted in terms of a model in which no complex ions are present.

The solubility of gaseous HCl in the LiCl-KCl was found to increase from 4.11×10^{-5} mole fraction to 6.31×10^{-5} over the temperature range 490° to 675°C , giving a heat of solution of 3.5 kcal/mole. Cathodic chronopotentiograms were also obtained on the saturated solutions, and values for the diffusion coefficients of the reducible species (HCl or H^+) of 2.3 to $2.4 \times 10^{-4} \text{ cm}^2/\text{sec}$ were derived from the results.

The coloration of KCl crystals by K vapor of varying partial pressure was investigated quanti-

tatively, and a linear relationship between the concentration of F centers and the K pressure was found.

The free energy of formation of AgI was determined by a galvanic cell method between 300° and 450°C. The value at 300°C is -13,880 cal.

RADIATION DIVISION

**(04-40-04-03-1, 05-05-03-00-0, 08-04-01-00-0,
08-03-02-01-0, 40-04-00-00-0)**

The work in radiation research has been concerned primarily with the mechanisms of reactions induced by radiation in organic solids and liquids and in several simple inorganic compounds in the pure state and adsorbed on selected solid substrates.

The study of radical trapping, decay, and reactions with gases in irradiated solid crystalline organic compounds has included several crystalline amides of varying chain length and molecular architecture and several long chain fatty acids. The important roles of crystal structure and defects in the crystal lattice in determining the rates of solid-state reactions have been further elucidated. The radiolytic products from several highly substituted ethylene derivatives have been determined. The mechanism of the radiation-induced ionic polymerization of styrene has been studied further, and included molecular weight distributions.

An investigation of the radiolysis of carbon dioxide adsorbed on silica surfaces has identified a surface-formed formate as the precursor of carbon monoxide. Nitrous oxide has been observed to be a remarkably efficient scavenger of transferred energy from molecular sieves under irradiation. The mechanism of the radiolysis of aqueous solution of hydrazine has been modified in light of recently developed data on the pulsed and steady-state radiolysis of this system.

The preparation and study of cellulose and cellulose acetate films have continued.

The program of developing concrete-polymer materials in cooperation with the Bureau of Reclamation has had considerable success. It is jointly supported with the AEC by the Office of Saline Water, Bureau of Mines, and the Bureau of Public Roads. Interest in applications has been expressed by many organizations. Tests are under way on composites containing methyl methacrylate and styrene, and work has started on systems involving acrylonitrile, chlorostyrene, and a mixture of 90%

methyl methacrylate - 10% trimethylol propane trimethacrylate. This latter polymer in combination with concrete has provided the highest tensile and compressive strengths obtained to date. Outstanding freeze-thaw durability and resistance to corrosion by 15% HCl and by sulfate solutions has been demonstrated. Formulations for resistance to high-temperature brine and distilled water for water-desalination applications have been developed using thermosetting monomers. The possibility of utilizing waste materials such as soil, solid refuse, or sewage sludge in polymer-composites for low-cost building materials is being investigated, as are applications for ceramics that have been impregnated with polymers by radiation techniques. The use of a combination of conventional chemical catalysts and radiation to provide an economic processing system for plastics is being studied.

In the chemonuclear program, the Chemonuclear In-Pile Research Loop in the BGRR was successfully operated in a series of five week-long runs. These were made at low temperature (-30°F) for the production of ozone from oxygen. The addition of nitrogen was found to enhance ozone production significantly. Because of increasing interest in the use of ozone for water treatment, studies were made of its production on a large-scale by chemonuclear means. The method compared favorably at higher capacities with the conventional electric discharge ozonators now in use. Experiments on the fixation of nitrogen and on ozone formation were continued in the ⁶⁰Co γ flow irradiator.

The work on establishing the principles involved in the design and operation of processing equipment for carrying out radiation-induced reactions is continuing. Both theoretical analysis and experimental systems are utilized. The reaction selected for study was the photopolymerization of benzoin-sensitized methyl methacrylate. Work is continuing on problems inherent in the use of chemical dosimeters in flow systems, with the use of chemical reactor design principles. Conversion of aerated Fricke dosimeter solution was measured as a function of flow rate in two tubular and one stirred-tank reactors, with a 20-Ci ⁹⁰Sr-⁹⁰Y source in the tubular reactors, a ⁶⁰Co source in the stirred tank.

The programs in radiation engineering for the development and utilization of radiation sources are continuing. An inventory of ⁶⁰Co, ⁹⁰Sr, and ¹³⁷Cs is maintained on hand for application as

needed. Both the preparation and irradiation hot cells in HIRDL were used in a wide variety of operations. The two underwater gamma facilities were in use routinely for service irradiations. The mechanical arm manipulator was automated by an $x-y-z$ programmer so that it could position itself precisely within a 4-ft cube. Work on modifying and extending computer codes for gamma and beta dose distribution is still in progress. An apparatus for testing source corrosion was installed and utilized. Emphasis was placed on heterogeneous target studies for application to the irradiation of arrays of food cans. Improved experimental techniques were employed and computational methods for dose prediction were delineated and verified. Dose distribution studies in large-scale irradiators were made to determine the relationship between minimum, maximum, and average doses.

Interlaboratory meetings on cooperative efforts were organized, covering standardization of dosimetry procedures, interfacility comparisons, and source calibration. Training, workshop, and consultation activities continued. Offsite calibration and maintenance operations were carried out. An irradiator was installed in Argentina, and others were prepared for shipment to Chile, India, and Pakistan. Another is being returned from Iceland for inspection and maintenance before shipment to South Korea.

Data collected in field operations under the atmospheric diagnostics program have not only demonstrated the validity of the isotope ratio tracer (IRT) method as a means of tracing sulfur oxides in the atmosphere but have also shown it to be a sensitive way of measuring the degree to which sulfur has taken part in a chemical reaction. The program, conducted jointly with the Analytical Group of the Hot Laboratory Division, the Engineering Division, and the Meteorology Group of the Instrumentation and Health Physics Department, is supported in part by the National Air Pollution Control Administration. Techniques for stack-injection of sulfur hexafluoride as a collateral tracer with IRT and for its measurement in air samples have been developed. Considerable effort has gone into improving flue gas sampling methods, stressing isokinetic sampling for particulates. The three major problems under study are combustion of sulfur in power plants, the oxidation of SO_2 to sulfate in the plumes from stacks, and the behavior of SO_2 in urban atmospheres. Quantitative

relationships between degree of conversion of SO_2 and changes in the sulfur isotope ratio as the result of chemical reaction are being developed. Field work is being carried out at four power plants and in the New York and New Haven metropolitan areas. The installation and testing of the Meteorology Environmental Chamber was completed and experimental work begun.

The analytical and experimental investigation of the ball lightning phenomenon has been fruitful and is continuing. The use of cryogenic conductors for long-distance transmission of large blocks of power has been examined for technical and economic feasibility. Work has continued on MHD cycles utilizing gasified subbituminous coal as fuel.

HOT LABORATORY DIVISION

(05-05-03-00-0, 08-01-04-00-0, 04-40-04-04-1)

Progress in the area of nuclear and radiochemical research can be summarized by the following highlights. The isomeric transition of tellurium isomers from the metastable to the ground states results in the simultaneous production of two or more hot atom species, at least one of which was shown to be produced by the complete disruption of the parent molecule while a second was obviously formed from a partial disruption of the parent molecule. The Szilard-Chalmers reaction in solid titanocene dichloride showed a surprising high retention of ^{51}Ti in the original molecule. Excitation functions measured for five products from the triton bombardment of magnesium indicate that at ≤ 3.5 MeV the reaction cross section is dominated by the Coulomb barrier seen by the incoming triton. Qualitative evidence points toward a small but increasing contribution of a direct interaction mechanism in the $^{48}\text{Ca}(\alpha, n)^{47}\text{Ca}$ reaction as the bombarding energy increases and a predominantly direct interaction mechanism in the case of the $^{48}\text{Ca}(^3\text{He}, \alpha)^{47}\text{Ca}$ reaction. Nuclear level density calculations have now been refined to include the effect of the nuclear deformation, and the refined method was found to give values that are in excellent agreement with a calculational method derived by Lang; however, the new technique reveals several systematic effects of the nuclear shell structure, including a remarkably smooth dependence of the level density parameter, a , and the spin parameter, c , on the neutron number, N , with pronounced minima at the closed

shells $N=28$ and $N=50$. When this new treatment was applied to the de-excitation of ^{75}Br , for which experimental results exist, it gave better agreement for the evaporation of alpha particles than did conventional calculations and equally good agreement for the evaporation of protons.

Analytical and physical chemistry research problems included studies involving complexes containing mixed metals and others containing mixed ligands, electrochemical problems, and a parametric study related to air sampling procedures important to pollution investigations. For example, mixed-metal complexes of the form InUL_2 were found for $L = \text{citrate, malate, and tartrate}$, and the formation constants were measured. Mixed-metal complexes were also found between In(III) and Cr(III) , Fe(III) , Al(III) , and Cu(II) and between U(VI) and Cr(III) but not between U(VI) and Al(III) or Ce(III) or between Ce(III) and In(III) . Studies of mixed bromide-chloride complexes with acetonitrile showed that Ni(II) is a "hard acceptor" with respect to the halides as donors in acetonitrile solvent. From a kinetic study the mechanism of the extraction of Fe^{+3} into benzene by TTA was inferred.

In the development of medical radionuclides and their applications, a specific activity of 1400 mCi of $^{28}\text{Mg/g}$ of stable magnesium has been achieved. Thick-target yields of >3 mCi of $^{18}\text{F}/\mu\text{Ah}$ were attained with $>3\text{-MeV}$ tritons from a Van de Graaff generator. The $^{52}\text{Cr}(^3\text{He}, 3n)^{52}\text{Fe}$ reaction is being studied in an effort to improve preliminary yields of $\sim 100 \mu\text{Ci } ^{52}\text{Fe}/\mu\text{Ah}$. A proposed facility when constructed would allow spallation-induced production of a wide variety of useful new isotopes. The suitability of a prototype ^{109m}Ag generator/infusion system for producing images of the circulatory system is being evaluated in phantom studies. The procedure for labeling DTPA with ^{99m}Tc was optimized, and the stability of the labeled complex was shown to be satisfactory not only in air prior to administration but also in the body following intravenous injection.

**METALLURGY AND
MATERIALS SCIENCE DIVISION
(04-40-02-02-1, 04-40-02-03-1, 05-06-01-02-0)**

Comparative corrosion tests continue to show that Mo is the most corrosion-resistant material in high-velocity Na in a stabilized stainless steel loop; HA-25 has the best corrosion resistance of the other

alloys in that its corrosion rate appears to be less sensitive to the oxygen content of the Na than is the corrosion of stainless steels. However, deposition of Fe (from the stainless steel loop and specimens) appears to increase with the oxygen concentration of the sodium, and this deposition may have affected the weight-change measurements. When V-alloy specimens were present in the test section and the oxygen level of the Na was 3 ppm, corrosion of the V-base alloy was increased over that in the hot-trapped run, and deposits of V were found on the surfaces of stainless steel and Fe specimens. The depth of V penetration into the steel, but not the surface concentration of V on the steel, increased with temperature and caused an apparent inverse temperature-dependence of the corrosion rate of the steel specimens.

A comparison of the concentrations of Fe, Cr, and Ni in Na, as determined at a number of laboratories, with their solubilities in Na as determined at BNL indicates that Fe and possibly Cr are present in Na in amounts equal to or in excess of their solubilities at the maximum temperature of the system, and Ni is present in amounts less than its solubility at the maximum system temperature. The corrosion of steels in high-velocity Na is assumed to be a surface-controlled process; the presence of Cr and Ni in Na tends to decrease the concentration of active surface sites for corrosion, and thereby causes the observed downstream effects; oxygen in the Na increases the corrosion rate either by increasing the surface concentration of active sites or by entering into an activated complex (including Fe, O, and Na) that accelerates the corrosion process.

Experiments to study the effect of removal of particulates in Na are under way. Preliminary runs on the effect of high heat flux on the corrosion of steels showed that the region of maximum composition change corresponds with the region of highest heat flux. The first 500-hr run with weighable specimens was made at an oxygen level of ~ 25 ppm. An Fe loop is under construction to test the predictions of the corrosion models. It is made entirely of Inconel-clad Ferrovac iron.

The corrosion of V-base alloys is more sensitive to the oxygen level in the Na (at the 2 to 3 ppm level) than it is to temperatures in the range 500° to 750°C . Vanadium alloys that were previously exposed to hot-trapped sodium are not as severely attacked in Na with 2 to 3 ppm oxygen as are virgin specimens. This effect is attributed to the

pickup of carbon and nitrogen which concentrate at the surface during the hot-trapped run. None of the alloys tested have high ductility after exposure to Na containing 2 to 3 ppm oxygen.

When oxygen is added to a sodium loop, only a fraction of the oxygen added can be accounted for by an increase in the activity of oxygen in the Na. This is believed to be due to interactions of the oxygen with other species in the system.

Commercial electrochemical cells for determining the activity of oxygen in liquid Na have been improved by the use of Na_2O or Au_2O_3 reference electrodes. Cells using both electrodes have been tested in both thermal convection and pumped loops, in which their emf's differed by the theoretical amount due to the difference in reference states, and remained stable in some instances for times >3000 hr. The primary cause of failure was thermal shock due to temperature transients. The ionic transference numbers for the commercial $\text{ThO}_2\text{-Y}_2\text{O}_3$ electrolytes have been shown to be generally satisfactory for use on meters. Alternative materials that have better thermal shock resistance are attractive, however; the best appear to be the GE materials Yttralox and Thoradox. The ionic transference number of $\text{ThO}_2\text{-Y}_2\text{O}_3$ tubes appears to increase with the Y_2O_3 content of the ceramic.

Methods being studied for on-line calibration of electrochemical oxygen meters include uranium-gettering, filtration of oxygen with Li, and coulometry. Preliminary results using each method are given; the well-known buffering reactions appear to complicate the use of these methods.

Electrochemical cells for determining the carbon activity in Na have been developed. They use an Fe membrane which is equilibrated with the Na, either $\text{CaC}_2\text{-LiCl}$ or $\text{Na}_2\text{CO}_3\text{-Li}_2\text{CO}_3$ as liquid electrolytes, and either graphite or carburized iron as reference electrodes. The carbon activity in Na as measured by these cells appears to be buffered by the carbon activity of the stainless steel vessels.

The solubility of oxygen in Na has been redetermined using electrochemical methods, and gives the equation $\log_{10}(\text{ppm O}) = 6.46 - (2600/T, ^\circ\text{K})$ over the temperature range 350° to 550°C . The free energy of formation of Na_2O was also determined by this technique, and from the results a temperature-free-energy-composition diagram was prepared for the sodium-oxygen system. In the presence of unit activity Fe, a compound was noticed, the thermodynamic properties of which are in fair agreement with the reported values for

$(\text{Na}_2\text{O})_2 \cdot \text{FeO}$. Further experiments tend to confirm that the buffering of oxygen commonly found in Na in stainless steel systems is due to the formation of a Na-O-Cr complex. The potential of the oxygen meter has been found to be influenced by additions of hydrogen to sodium.

Further data are reported on the solubilities of Fe and Cr in Na. The use of a Mo crucible and an irradiated Fe insert and covered Mo buckets has caused a substantial difference in the results obtained, which has yet to be resolved. Metallic solutes in Na such as Fe, Cr, and Ni, as well as the nonmetallic constituents C and O, have been observed to segregate at sodium interfaces. The deposition of Cu from Na has the same temperature dependence as the Cu solubility at temperatures above 600°C , but a greater temperature dependence at lower temperatures, indicating that deposition is increasingly inefficient as the temperature is lowered. These experiments suggest that the Na-gas interface may be a site for particulate formation. The gettering of oxygen by U can be used to determine the mass-transfer coefficient of a sodium system, as well as the oxygen concentration. Uranium-gettering is also a useful tool in studies of the buffering reactions. The effect of oxygen on the corrosion of Fe, Ni, Cr, and Co specimens was studied in a type 316 stainless steel loop at 660° to 760°C . The mass transfer of Fe to the other specimens was the most sensitive to oxygen in the Na; the Cr specimens gained weight at the high oxygen level, and the Ni corrosion and deposition appeared to be insensitive to the oxygen concentration in the sodium.

Equipment is being set up for the determination of the high cycle fatigue properties of materials in sodium.

An analytical method has been developed for the determination of carbonate in liquid sodium, and was used to determine that the carbonate level in the FCLs and SCL is <2 ppm (as oxygen).

A treatment of hysteresis has been developed from the second law of thermodynamics for irreversible paths. The treatment has been used successfully to explain hysteresis in the superconducting transition, and to explain the experimental properties of elastic membranes. A theory has also been developed that explains the extra conductivity of superconductors above T_c , based upon the existence of bound superconducting pairs that exist above T_c . This model has been successfully used to explain the existence of conductivity

fluctuations above T_c . Since the superconducting properties of well-ordered thin films are theoretically interesting, methods of preparing them are being studied, and their structure and composition determined using low energy electron diffraction and Auger spectroscopy. Preliminary measurements were made on a Nb surface. The superconducting properties of Be alloys are being studied, since theory predicts a T_c of $\approx 30^\circ$ to 60° K may be obtainable. A value of 9.9° K has been obtained with the alloy Be_{22}Re , confirming other measurements.

The nuclear susceptibility of solid ^3He has been measured down to 5.3 mK, providing the first accurate evidence for a nuclear antiferromagnetic transition in the region below 2 mK, as predicted.

Radiation damage in Pt was studied using field ion microscopy, and the activation energy for dislocation cutting of zones was measured to be ≈ 1 eV. The effects of irradiation on the mechanical properties of W crystals have also been studied. Large bi-crystals of Cu have been prepared in preparation for irradiation to show how grain-boundary He affects the mechanisms of grain-boundary sliding. Low temperature deformation followed by recrystallization has been shown to enhance the mechanical properties of both stainless steel and Co-base alloys after irradiation. The treatment refines the grain size of the material and introduces fine precipitates that are believed to act as sinks for irradiation-produced vacancies.

ENGINEERING DIVISION

(04-40-03-01-1, 04-50-50-01-1, 04-60-01-10-1,
04-60-40-03-1)

The work of the Heat Transfer Research Group continues to be devoted almost exclusively to the study of convective heat transfer to liquid metals, and is mainly in support of the FFTF and LMFBR programs. Both liquid-phase and two-phase flows are treated in both analytical and experimental studies.

An experimental study of heat transfer to mercury flowing longitudinally through an unbaffled rod bundle was carried out for the purpose of determining the effect of lateral displacement of a rod on its local heat transfer behavior. It was found that these effects can be large. They depend primarily on three variables: rod spacing, relative cladding thickness, and relative thermal conductivity of the cladding. Displacement of a rod can produce circumferential variations in its surface

temperature comparable to the average temperature drop from the heating surface to the coolant stream. At the same time, the local heat transfer coefficients of the displaced rod decrease at all points around its circumference which explains why the rod-average heat transfer coefficient is so adversely affected by rod displacement. These results were confirmed by the results of an analytical study carried out during the past year.

Future plans call for the most emphasis to be placed on the general subject of heat transfer to liquid metals flowing in-line through rod bundles. The experimental work will include the use of sodium as coolant and rod spacings down to a pitch: diameter ratio of 1.10 . Also, increasing emphasis will be placed on the use of analytical methods.

The study of incipient-boiling of alkali liquid metals continued, with attention centered on the effect of flow on the nucleation superheat. Data obtained in a forced-convection loop with potassium were analyzed, and the results showed large reductions in incipient-nucleation superheat as flow rate increased. A theoretical explanation for this effect is being developed, based on the fluctuations of pressures at the wall caused by the turbulent flow.

A new study was initiated to study the dynamics of void propagation in liquid metals within rod bundles. Emphasis is to be placed on the vapor void propagation between subchannels as well as in the axial direction. Experimental plans call for initial experiments in a forced-convection potassium loop using an annulus test section. This is to establish the necessary instrumentation technique as well as to obtain void dynamics data for the annulus geometry. More extensive experiments are then to be performed in various rod bundles using the forced-convection sodium loop. Complementary analytical studies of the void propagation dynamics have also been initiated. Here too, the emphasis is on multichannel, cross-flow effects.

Pressure drops were measured for two-phase, upward flow of potassium in a vertical tube. Data were obtained for adiabatic and diabatic conditions. The adiabatic pressure drops were analyzed to obtain correlations of frictional losses and void fractions. Using these correlations in a stepwise integration procedure, it was shown that the pressure drops for diabatic cases (with net boiling) could also be successfully correlated.

Additional analytical studies were carried out on the following problems: (a) exact solutions for

low-Peclet-number, thermal-energy-region heat transfer in laminar flow through pipes, parallel-plate channels, and annuli, (b) heat transfer in magnetohydrodynamic channel flow with radiative boundary condition, (c) effects of cladding thickness and thermal conductivity on heat transfer to liquid metals flowing in-line through bundles of closely spaced reactor fuel rods, and (d) entrance-region and variable heat-flux effects on heat transfer to liquid metals in turbulent flow through concentric annuli.

In the waste disposal work, a number of extended runs on the phosphate glass pilot plant were carried out, mainly to determine the range of dependable operating conditions for processing simulated wastes from projected high burn-up fuels, and to develop improved mechanical designs and performance capabilities of the process units. Successful operation was obtained with a variety of Purex type wastes, including those derived from uranium burn-up levels as high as 100,000 MWd/tonne of uranium or plutonium. In a number of cases abnormal overload conditions were imposed to determine operating latitude for the major plant components, i.e., the evaporation-denitrator and the high temperature melter unit. The pilot plant operations have continued to provide basic information for the operation of the demonstration prototype plant with high level radioactive wastes at Pacific Northwest Laboratories. Investigation of a number of new design schemes and equipment modifications were initiated during the year with the main objective of reducing or eliminating certain operational difficulties, and increasing the overall capacity or throughput of the phosphate glass plant.

In the fission product release program research was concentrated on developing a fundamental understanding of the chemical reactions, release mechanisms, and transport behavior of fission products and radioactive aerosols emanating from nuclear materials under conditions likely to be encountered in LMFBR accidents.

Studies are under way to determine the chemical state and to measure the thermodynamic properties of fission products released from reactor fuels at high temperatures. A thermochromatograph to determine the deposition behavior of fission products released from plutonium fuels was constructed and installed in the alpha facility. In addition, a Knudsen effusion apparatus, designed to determine the molecular weights and thermo-

dynamic properties of fission products released from uranium and plutonium fuels, has been constructed and tested.

Both experimental and theoretical studies are under way to determine the characteristics of radioactive aerosols which might be generated as the result of a fast reactor accident. Experiments were performed using a resistance ribbon heater to rapidly vaporize PuO_2 , UO_2 , and $\text{PuO}_2\text{-Na}$ directly into an aerosol chamber. In addition, a 20-kW, 530-kc induction furnace was installed in the alpha facility to generate higher aerosol concentrations than can be obtained with the resistance heater.

The general integro-differential aerosol equation including terms for aerosol coagulation and deposition was solved using a CDC 6600 digital computer. The experimental results for PuO_2 and UO_2 aerosols were compared with those calculated and good agreement was obtained.

A program was initiated to coordinate large-scale LMFBR aerosol safety work. This will include an evaluation of the need for large-scale aerosol experiments, a recommendation of necessary tests, and a consideration of the need to develop and test consequence limiting safety systems.

Studies are being performed to provide information on the behavior of fission products in sodium systems. Knudsen cell vaporization experiments were done to evaluate the thermodynamic properties of the cesium-sodium system. In addition, a theoretical equation was developed for calculating the diffusivities of fission products in liquid which are needed in making transport calculations.

The Engineering Assistance Group contributed 283 man-months of engineering services to the support of departmental programs during 1969. The majority of this support was in the design and construction of facilities used for research in radiation processing, heat transfer, experimental physics, advanced reactor concepts, and environmental pollution. Contributions to the *High-Temperature Liquid Metal Technology Review* and to various national technical committees continued throughout the period.

Reference designs were completed for two alternative pulsed reactor concepts. The systems that have been studied as high-intensity neutron beam sources were designated reference designs B1 and B2. The reference design B1 concept is a pulsed reactor with a fast, sodium-cooled core. The re-

activity is repetitively pulsed into the superprompt critical region by means of a rotor which carries a reflector section past the edge of the core at high velocity. The neutron beams are taken from the face of the moderator region that wraps around the remainder of the core boundary. The reference design B2 concept is an accelerator-injected pulsed reactor which is similar to the B1 system except that the reactivity is repetitively pulsed to a high-prompt multiplication condition coincidentally with the injection of neutrons from an electron accelerator source. The power pulse width is smaller in this system because of the controlling influence of the short duration electron accelerator burst.

Work continued on the fuel test and development program and on the beam source studies and critical experiments that are being carried out in support of the design effort.

The evaluation of the fuel survey and of the results of the tests of unirradiated fuel materials was

completed. This work led to the selection of 60 vol % PuO_2 -Mo cermet for reference design B1 and of U-10 Mo alloy for the reference design B2 core. Ceramic fuels, UO_2 or UC , are promising alternatives for use in both concepts; however, considerable proof testing is required for these fuels under simulated pulsed conditions. Since the effects of pulsed reactor operation on ceramic material are difficult to study analytically, this fuel was not selected for the current reference designs.

The beam source studies and critical experiments progressed to a mock-up of the reference design B1 core that was fueled with ^{235}U rather than the Pu that is being considered for the reference design. The major features of the reference design, such as the poison liner that decouples the core from the moderating region, the reflector pulse block, and the moderator region, were included in the experiment, and the yield of thermalized neutrons from the moderator region was measured.

DEPARTMENT OF APPLIED SCIENCE

BROOKHAVEN NATIONAL LABORATORY

ORGANIZATION CHART

FEBRUARY 1969

Reactor Physics Division

J. CHERNICK

Reactor Physics Theoretical Group

REACTOR KINETICS

Nonlinear Space-Time Kinetics

There is a need for the development of better analytical methods which can handle nonlinear space-time reactor models. Solutions obtained by such methods can be used to check computer codes in use by industrial and other users as well as to provide insight into basic feedback mechanisms such as the Doppler effect.

The usefulness of an iterative technique for the solution of nonlinear space-time problems has been demonstrated [L.M. SHOTKIN, *Nucl. Sci. Eng.* **36**, 97 (1969)]. The application of the method to the Fuchs-Nordheim model for fast transients yields accuracies of $<1\%$ when the first two spatial modes are excited. This result is a marked improvement over conventional modal expansion methods. One of the results of the studies was the prediction of a marked spatial dip in flux during rapid transients such as those developed in SPERT experiments. In the 7.4-msec supercritical excursion in the SPERT-I core, several harmonics are excited and the NOAH code [G. LELLOUCHE, BNL 50157 (T-523)] was used to calculate them accurately. Further work on the analysis of SPERT transients is continuing because of its expected importance for fast reactor accident studies. In particular, the influence of the spatial dip on the analysis of Doppler coefficients is being investigated.

L. SHOTKIN, G. LELLOUCHE

Higher Order Prompt Jump Approximations

A persistent problem in calculations of fast reactor dynamics is the large number of time constants involved, some of which differ by orders of magnitude. If an iterative time step of the order of the shortest of the time constants is used, computations of inordinate length result. Studies have been carried out to circumvent the latter problem by generalization of an old technique, the prompt jump approximation (PJA). The method

has proved promising [R. GOLDSTEIN AND L.M. SHOTKIN, *Nucl. Sci. Eng.* **38**, 94 (1969)] when applied to point reactor kinetics where the excess multiplication factor of the reactor k (in dollars) remains less than unity. A method of treating superprompt critical excursions has also been tested. The possibility of extension of the method to space dependent problems is being explored.

In the conventional point kinetics equations,

$$\Lambda \dot{P}(t) = [k(t) - 1]P(t) + S(t),$$

$$S(t) = \sum_i \lambda_i C_i(t),$$

$$C_i(t) + \lambda C_i(t) = \alpha_i P(t).$$

The simple PJA is obtained by taking $\Lambda = l/\beta = 0$ in the first of the above equations, which makes the PJA method especially appropriate for fast reactors where $\Lambda \approx 10^{-4}$ sec.

To improve the accuracy, one expands $P(t)$ in an asymptotic series (R. GOLDSTEIN AND L. SHOTKIN, *loc. cit.*) in Λ . The generalized PJA⁽ⁿ⁾ approximation is now defined as that corresponding to keeping terms up to $O(\Lambda^n)$ in this series.

In application to reactors undergoing ramp increases in reactivity to values of k below prompt critical, it was found that the PJA (R. GOLDSTEIN AND L. SHOTKIN, *loc. cit.*) approximation was very good, particularly for fast reactor excursions. Even for thermal systems ($\Lambda \approx 10^{-2}$ sec), accuracies of $<0.1\%$ were obtained with iterative time steps of as much as 1 sec.

L. SHOTKIN, R. GOLDSTEIN

Reactor Stability Limits

Space-independent reactor models are reliably applicable only when the power level is reasonably close to its initial or equilibrium value. For large flux departures from equilibrium, spatial effects may become significant or the temperature dependence of feedback factors, heat-transfer coefficients, or even reactor geometry may change in a radical way. It thus makes sense to use some sort of perturbation expansion about equilibrium in seeking not only the stability behavior of point kinetics models but also bounds on their applicability.

A new method has been developed [L. SHOTKIN, *Nucl. Sci. Eng.* **35**, 211 (1969)] for determining the bounds on allowable disturbances in linearly stable systems for which the system remains asymptotically stable. It is based on a transformation of the set of nonlinear differential equations to a single equation valid within a given region about the equilibrium point. It is applicable to systems with quite general nonlinear feedback effects. The physics enters through the linear characteristic roots and provision is made for both real and complex roots. The method is useful in determining the range of validity of space-independent reactor models. The method has been applied to feedback problems, including the determination of a reactor excursion terminated by its negative temperature coefficient. L. SHOTKIN

THE THEORY OF PULSED FAST REACTORS

An extensive study of the decay of a neutron pulse in a fast, subcritical assembly has been carried out. The purpose of the investigation was to supply a firm theoretical foundation upon which to base the physical interpretation of pulsed-source and Rossi- α experiments in fast cores. Of particular importance in dilute fast systems is the understanding of the nonexponential time decay of the response of a fission detector and the related pseudo-modes, since this phenomenon occurs in such systems when they are only moderately subcritical. This has been evidenced by observations of nonexponential experimental die-away curves in a number of fast assemblies (SUAK, EURECA, VERA 7A).

There are two main results of the study. The first is a rigorous determination of decay constant values for which exponential decay occurs. This result was achieved for a very general class of cross sections and for exact elastic as well as inelastic scattering by an arbitrary number of nuclides. The second main result, obtained for modeled cross sections and for exact elastic scattering only, was the calculation of time-behavior (nonexponential decay) of pseudo-modes during measurement times when a system is sufficiently subcritical that exponential decay cannot occur. This time-behavior is related to certain singularities which occur in the analysis and which are not expected to depend greatly on the cross-section models. The latter conjecture is verified by experiment, since the solutions obtained are in qualitative agreement with experiment where

extensive multigroup calculations fail to achieve even qualitative agreement with experiment.

The analysis evolved through a series of published papers and summaries in which progressively more complicated models were treated. The studies for fast systems led to equations that are a great deal more complicated than those arising in the analysis of thermal systems. The asymptotics of certain special functions encountered in fast reactor analysis were found to be incorrectly evaluated in the well-known Bateman Manuscript Project. The correct asymptotics were derived and published. Finally, the discrete decay region was completely elaborated with all the assumptions on cross sections and scattering kernels relaxed and the nonexponential time-behavior of the pseudo-modes was derived for exact elastic scattering and modeled cross sections.

J. DORNING, B. NICOLAENKO

RESONANCE ABSORPTION OF NEUTRONS

Tests of Standard Codes

The main objective of the year's work was to test the adequacy of standard codes for the calculation of the resonance absorption of neutrons in reactors. The widely used codes ZUT-TUZ and RABBLE were tested by comparison with the Monte Carlo code REPCDC and both were found to overestimate resonance absorption in typical thermal reactor lattices. The significance of the tests of ZUT-TUZ and RABBLE is that they show that thermal reactor physics calculations are not in as good shape as has been claimed.

A similar study has been started on fast reactor lattices. Again, the BNL developed code REPCDC is being used as the standard of accuracy. The adequacy of MC² generated group cross sections is being tested. W. ROTHENSTEIN, R. GOLDSTEIN

Formula for Doppler Broadening

In comparing analytical methods with computer studies, it is seen that simple analytical approximations to the Doppler-broadened line shape are needed. One such approximation has been obtained by an integration of the line shape function $\psi(\theta, x)$ which extracts the Gaussian distribution. The remainder is then approximated by a rational form. The approximation has the features of giving the exact peak of the Doppler line, the exact integrated value at all energies as the exact

result, and the correct leading term for small and large x behavior. R. GOLDSTEIN

^{235}U Quasi-Resonance Fission Cross Sections

The R-matrix expression for a multilevel fission cross section can be written as a ratio of two polynomials in energy with N^J interfering levels and N^J open fission channels in spin sequence J . Quasi-resonance energies and widths can be obtained by solving the denominator of this ratio for its complex roots. A code (TRIPLET) has been developed to calculate these quasi-resonance parameters for cases of up to three interfering levels.

T. SHEA, S. PUROHIT

Analysis of Self-Indication Ratio Experiments

In collaboration with Byoun and Block of Rensselaer Polytechnic Institute an analysis has been carried out of the 1.15-keV p -wave resonance in ^{56}Fe . Measurement of the ratio was carried out at RPI with their linear accelerator. Within the limits of experimental error, the experimental and theoretical results are in good agreement.

T. SHEA, S. PUROHIT

SPACE-ENERGY FLUX SYNTHESIS METHODS

The need for simplifications in theoretical methods to be used in the design of fast breeders is well understood. The accurate determination of the space-energy power distribution of a breeder is complex and expensive, and it taxes the capacity of the most modern computers. That diffusion theory is frequently inadequate has also been amply demonstrated in the analysis of experiments on small assemblies or in studies of multizoned fast breeders.

Flux synthesis techniques based on the so-called "overlapping group" method have previously proven useful in the analysis of thermal reactors. By means of variational techniques the utility of the method has been explored for the space-energy synthesis of fast power reactors. In this method, the flux in the different regions of the reactor is expanded in terms of a set of separable energy and spatial functions.

The results of a number of variations of the above approach showed that the overlapping group method readily provides accurate estimates of the reactivity and flux in the core of a two-region (core and blanket) fast reactor. However, the calculated space-energy fluxes in the blanket were

not sufficiently accurate to obtain adequate activation rates for a number of test foils (^{240}Pu , ^{232}Th fission, etc.). The use of different trial energy spectra in the different regions of the reactor (discontinuous trial functions) resulted in somewhat improved results.

It was concluded that any claims to the completeness of synthesis methods or their accuracy are premature. While the method is promising, much further work is needed before it can be used routinely for the development of either reactor statics or dynamics codes for fast breeders.

M. LANCEFIELD

Reactor Physics Analysis Group

ANALYSIS OF BNL EXPERIMENTS

Pu-Al Rod Lattices in D_2O

A large series of exponential experiments consisting of Pu-Al fuel rods in D_2O were completed and their analysis is well advanced. A total of 28 lattices with moderator-to-fuel volume ratios ranging from 1:1 to 14.5 have been analyzed using ENDF/B cross sections and the HAMMER code corrected in the high energy range and in the resonance range by Monte Carlo codes (MOCA and REPCDC respectively). The results indicate that this series of experiments provides an excellent reference set for the testing and evaluation of plutonium cross sections as well as the calculational methods to be used for plutonium-fueled reactors. By varying the lattice pitch and the amount of (boron) poisoning, spectra with a wide range of hardness were obtained. The widest lattices were quite thermal while the bulk of the fissions occurred in the resolved resonance range (1.44 to 275 eV) with a sizable contribution from the region above 275 eV for the tighter lattices. The effect of using Schomberg and Gwin cross section sets in the range 0.1 to 25 keV has been observed and leads to improved agreement with the experimental results.

In the above analysis, it has been assumed that all the lattices are effectively asymptotic and that the experimentally measured buckling was descriptive of the shape of the flux. The main tool of analysis has therefore been the HAMMER code. However, since the tighter lattices seem not to have achieved an asymptotic spectrum, the calculations are being repeated with more complex

Table 1
BNL Pu-Al-D₂O Lattices Calculated Eigenvalues

Volume ratio (V_m/V_f)	Poison concentration, mg B/ml	Measured B^2 , m ⁻²	ENDF/B	k_{eff}	
				Gwin	Schomberg
1.0	Clean	15.68	1.0596	1.0282	1.0163
1.0	Clean	15.45	1.0625	1.0307	1.0186
1.0	Clean	17.25	1.0315	1.0018	0.9901
1.0	5.64	7.75	1.0434	1.0176	1.0031
1.0	5.90	6.45	1.0629	1.0362	1.0214
1.0	9.14	3.43	1.0313	1.0064	0.9896
1.0	9.26	2.44	1.0483	1.0229	1.0059
1.5	Clean	20.68	1.0220	1.0000	0.9915
1.5	Clean	20.75	1.0223	1.0004	0.9920
1.5	8.93	-2.46	1.0209	1.0011	0.9871
1.5	8.93	-3.08	1.0312	1.0111	0.9970
2.0	Clean	23.78	1.0151	0.9981	0.9917
2.0	Clean	23.75	1.0165	0.9995	0.9931
2.0	5.87	-0.96	1.0192	1.0070	0.9948
2.0	5.87	-0.14	1.0067	0.9944	0.9818
3.0	4.24	-1.26	0.9946	0.9847	0.9770
3.0	4.27	-2.04	1.0032	0.9931	0.9854
3.0	4.29	-2.09	1.0026	0.9926	0.9848
4.0	3.38	-2.04	0.9930	0.9852	0.9792
4.0	3.36	-2.56	1.0014	0.9934	0.9875
4.0	3.37	-3.17	1.0086	1.0006	0.9946
7.0	1.42	7.15	0.9953	0.9899	0.9869
7.0	1.42	6.70	1.0018	0.9964	0.9934
7.0	1.42	7.15	0.9968	0.9899	0.9869
7.0	1.81	0.91	0.9896	0.9848	0.9814
14.5	0.98	-4.35	0.9928	0.9901	0.9879
14.5	0.98	-4.22	0.9900	0.9874	0.9851
14.5	0.98	-4.34	0.9888	0.9861	0.9839

transport theory methods. In addition it was found that the current ENDF/B file yields a neutron age for D₂O which is in disagreement with experimental data. The ENDF/B deuterium scattering cross sections were therefore raised by 5% in better agreement both with older evaluations and with neutron ages. Again the limit of the thermal region in HAMMER had to be raised from the usual 0.625-eV cutoff to 1.44 eV in order to treat the 1-eV resonance in ²⁴⁰Pu adequately.

The results of the Monte Carlo corrected HAMMER analyses are shown in Table 1. It is clear that except for the loose lattices the ENDF/B data results in eigenvalues that are too high. The discrepancy becomes largest for the tightest ($V_m/V_f=1$) lattices in which the "uncertain alpha region" plays an important role. Disagreement

with the experimental results is much less pronounced for the case of Gwin and Schomberg's α data. On the other hand, for the better thermalized loose lattices where the results depend very strongly on the thermal value of η for ²³⁹Pu and on its low energy resonance parameters, all three sets of eigenvalues are somewhat low. O. OZER

Analysis of Pu-Alpha in the HFBR

The importance of reducing uncertainties in the value of alpha for ²³⁹Pu led to the BNL program of lattice experiments discussed above. In addition, a hard spectrum environment for the measurement of alpha was provided in the HFBR by placing boron shielded foils (both ²³⁹Pu and ²³⁵U) in the core of the reactor. The irradiation experiments were carried out at BNL while the

chemical and isotopic analyses of the irradiated and unirradiated foils were carried out at other AEC laboratories.

Preanalysis of the experiment showed a great sensitivity to alpha values, depending on whether ENDF/B or Schomberg data were used. The simultaneous use of ^{235}U foils provided a criterion for the accuracy of the experimental data. Calculations were carried out to determine the effect on the spectrum of the exact geometry of the capsules, of the effect of control rods (which are exterior to the core in the HFBR), and of fuel burnup. The latter two effects were found to be small and compensatory. The effect of foil heterogeneity within the capsule was negligible.

The results of the chemical and spectrographic analyses of the foils have recently been completed. The comparison with calculations is proceeding.

H. TAKAHASHI, T. SHIMOOKE

Heterogeneity Effects in Fast Reactor Lattices

The fast, zero-power critical facility (FS-1) is being used to provide accurate measurements of foil activation rates in typical fast reactor lattice cells. The analysis of the data by accurate transport theory calculations is providing tests of the adequacy of ENDF/B cross sections.

Initial work was directed to the analysis of traverses of a fast reactor cell by fission foils, in particular ^{235}U and ^{238}U foils. It was found that great detail in the representation of the angular as well as the energy and spatial flux was necessary for accurate calculations. The agreement of the calculated spatial foil activation with experiment was excellent for the ^{238}U foils but a few percent low for ^{235}U . An analysis of the graphite used in the experiment showed an appreciable water content. After correction for hydrogen content, the agreement of theory and experiment was well within experimental error.

H. LUDEWIG

ANALYSIS OF INTEGRAL EXPERIMENTS

Uranium-Water Lattices

The analyses of ordinary water and heavy water moderated uranium lattices carried out at BNL before 1968 were based on cross-section data in use prior to the ENDF/B compilation. The calculational methods used have been incorporated into the HAMMER code system.

During the past year a new analysis was carried out for a selected number of these lattices. The

purpose of the calculations was twofold. First, it was of interest to determine the extent to which the new nuclear data have changed the results of these prior studies. Second, the comparisons clarify differences in the methods of analysis and indicate where further work is desirable to improve the accuracy of the calculations. The main tool used for these calculations was the HAMMER code with the current set of ENDF/B cross sections. The HAMMER resonance absorption calculations were corrected with results obtained from REPCDC. In the thermalization range the Haywood kernel replaced the earlier Nelkin kernel. The ENDF/B scattering cross sections for deuterium were raised by 5% to obtain agreement with measured neutron ages.

It was found that conventional methods (ZUTUZ, RABBLE, and HAMMER) consistently overestimate resonance capture. The earlier work of Hellens and Honeck already indicated some discrepancies between the results of theory and experiment, particularly for tight lattices. The discrepancies are increased as a result of the present calculations based on ENDF/B data. A substantial part of the discrepancy is attributed to present ENDF/B values of α_{25} near thermal energies. There also remain uncertainties in ^{238}U cross-section data. Theoretical questions that arise include the adequacy of the Haywood model for determining thermal diffusion lengths, the adequacy of HAMMER estimates of neutron leakage in heterogeneous systems, and the absolute accuracy of REPCDC calculations. It is clear that there remain substantial and unresolved theoretical problems in thermal reactor physics.

W. ROTHENSTEIN

Reflected Plutonium Cores

In order to evaluate the adequacy of ENDF/B plutonium data, the analysis of a series of plutonium fueled critical spheres has been carried out. The latter include JEZEBEL, a bare LASL plutonium sphere, a selected group of LASL criticals (H. Paxton, personal communication), and a series of UCRL plutonium cores with Be, C, ^{235}U , and ^{238}U as reflectors. The criticals cover a range in ^{240}Pu content and in plutonium densities.

Since neutron scattering in plutonium is sharply peaked in the forward direction, allowance has been made for the use of P_n scattering matrices for $n \leq 5$. It was found that P_3 scattering was sufficiently accurate. Since the spectra of reflected assemblies vary spatially, a fine spatial mesh, a 99-

group library, and 16 angular quadratures were needed for accurate calculations carried out with the use of the ANISN code.

The eigenvalues obtained were all on the high side, especially for the beryllium reflected spheres. The ENDF/B tape for high energy Be cross sections, particularly the $(n,2n)$ cross sections, are therefore suspect. The calculations have also been redone by following some of the recent recommendations of the International Working Group on Fast Reactors, particularly that of the Cadarache group on alpha for plutonium from about 10 keV to 1 MeV. These values are considerably higher than DeSaussure's differential measurements. The results are in excellent agreement with all the criticality data except for ^{238}U and, again, beryllium reflected spheres.

H. LUDEWIG

COMPUTER CODE DEVELOPMENT

NOMURK

Various phases in the development of the NOMURK system of codes were completed. The system evolved from BNL experience on dynamics and safety studies of both thermal and fast reactors. A manual on the one-energy group, one-dimensional version (NOAH) has been issued. Considerable progress was made on a multigroup generalization of NOAH called SHEM. The work on these codes has been greatly aided by the results of the Theoretical Reactor Physics Group on the coupled thermohydraulics of reactor coolant channels, including the development of a two-phase, forced flow coolant boiling model. As a further checkout of NOAH, the analysis of a number of SPERT transients is being carried out. The importance of changes in the spatial distribution of the flux during such transients is detailed elsewhere. NOAH has also been used in safety and stability studies of current U.S. power reactors for the AEC's Division of Reactor Licensing.

G. LELLOUCHE

REPCDC

The calculation of effective resonance integrals in reactor lattices is an area in which simplifying assumptions are still made to obtain formulas or numerical methods that are easy to use in a computer program. Among these codes are ZUT-TUZ which is incorporated in BNL's HAMMER code and the ANL code RABBLE which is more time consuming. The former uses approximate collision probabilities to solve the integral equations for the

collision density, and the latter uses a Wigner-Seitz approximation for the lattice cell with a boundary condition that becomes inaccurate for tight lattices.

The comparison of such semi-analytical approaches with a Monte Carlo program makes it possible to determine the conditions under which corrections must be applied to the former methods and the magnitude of the corrections.

The code REPCDC has evolved from the need for such comparisons. Its immediate antecedent was the Monte Carlo code REPETITIOUS which in turn was based on Richtmyer's pioneering code REP. However these earlier codes had certain theoretical weaknesses, including restrictions on admissible nuclides and a number of simplifications compared with current ENDF/B specifications. Among these were that contributions to resonance cross sections were limited to the nearest levels, the energy spacing of unresolved resonances were taken as constant, and p -wave capture could not be included. These restrictions and others have been eliminated in the REPCDC code.

REPCDC is written in Fortran IV and runs on the CDC 6600 computer. It includes all relevant ENDF/B File 2 and File 3 information for ^{238}U , ^{235}U , and four isotopes of plutonium. It requires a fast memory of about 32K.

A large number of applications of REPCDC have already been made. Comparisons with popular collision probability methods, ZUT-TUZ, HAMMER, and RABBLE, show serious weaknesses in the latter codes in the treatment of resonance absorption in typical thermal reactor lattices. REPCDC is currently being used to test the adequacy of MC² generated cross sections for fast reactor lattices. W. ROTHENSTEIN

MOCA

The Monte Carlo code MOCA, developed some years ago at BNL, is extremely useful in the analysis of the high energy spectrum in heterogeneous reactors. In brief, where THERMOS covers the thermalization range and REPCDC the resonance range, MOCA is needed for accurate calculations at higher energies. The flexibility of MOCA has been greatly extended at other laboratories. A processing code TS04 for ENDF/B data has recently been added for rapid processing of ENDF/B data.

During the past year the MOCA code has been used extensively in the analysis of BNL's Pu-Al lattice experiments. It treats accurately the effect of air gaps, fuel, cladding, and moderator geome-

tries. It can be used to determine streaming effects, fuel advantage factors, and the effects of reactor lattice anisotropy. It obtains accurate values of higher moments of slowing down distributions in heterogeneous reactors. T. SHIMOOKE, O. OZER

REACTOR SAFETY ANALYSIS EVALUATION

Control Rod Worth

A continuing problem has been the prediction of reactivity worth of control rod patterns in pressurized water reactors (PWR) and boiling water reactors (BWR). The primary distinction is that PWR's have control rods that replace fuel elements while in BWR's a cruciform shaped rod is inserted between fuel assemblies.

The successful calculational procedure that has been developed consists of three basic parts. The first step consists of obtaining 4-group cross sections for each of the basic cells in the reactor, e.g., a fuel rod with associated moderator, a control rod with associated moderator, etc. The cross sections are obtained from the reactor lattice code HAMMER. The second step is to compute cross sections for reactor subregions containing basic cells, by use of two-dimensional calculations. Transport theory is required for BWR calculations because of the control blade geometry. For PWR's the results of homogeneous calculations were compared with the heterogeneous calculations and a weighting factor used so that the same k_{eff} was obtained. In general little adjustment was required. For BWR's flux weighting was used and the k_{eff} 's compared, with good agreement in general. The final step was a 2DB calculation of the full reactor with the various subregions already selected.

In a comparison of the above scheme with experimental results for PWR control rods, agreement within 10% was obtained. D. DIAMOND, S. PUROHIT

Doppler Coefficient of Reactivity

Because of the importance of the Doppler coefficient in terminating rapid excursions, a study was undertaken of the present uncertainty of the Doppler coefficient in PWR's contributed by uncertainties in ^{238}U resonance parameters.

The calculations were performed for oxide fuel rods over the temperature range 300° to 4000°K by use of the code ZUT-TUZ. While other work at BNL has shown that ZUT-TUZ somewhat overestimates resonance integrals, it was felt that it was sufficiently accurate for the desired differential effects.

The calculations were first carried out with a standard set of cross sections (ENDF/B). They were then varied within reasonable limits. The results indicate that the uncertainty in Doppler coefficient due to parameter uncertainties is quite small in PWR's.

S. PUROHIT

Geometrically Induced Reactivity Changes

A study was carried out of reactivity effects due to geometrical changes in the core of a PWR. The particular calculations were aimed at determining the effect of fuel element bowing which results in changes in fuel and water densities in various core regions. Except for rather extreme configurations, the changes in reactivity were not large. M. LEVINE, L. EPEL

Moderator Coefficients

Reactivity coefficients of reactors must be known throughout core life as a function of temperature and control rod configurations. The work reported here was aimed at the prediction of the overall temperature coefficient of a large PWR, particularly at the beginning of life. Long term reactivity control in the power reactors considered is achieved by the use of a soluble boron compound in the moderator coolant. Since coolant expansion removes poison from the core and therefore contributes a positive contribution to the reactivity coefficient, the effect of boron poisoning on the temperature coefficient was examined.

Reactivity coefficients were obtained from an analysis of the eigenvalues of a series of space-dependent reactor calculations at a variety of temperatures and boron concentrations. A comparison was made between two sample methods of treating the control rod distribution, either as an added absorber or as a transverse buckling. The calculations used the HAMMER code system which uses a modified version of MUFT for nonthermal energies and THERMOS for the thermal region. The cross-section data used were based on recent BNL evaluations which were shown to give good agreement with critical experiments. Reasonably good agreement with the results of start-up experiments on a PWR were obtained. L. EPEL

External Detection of Core Power Patterns

Flux measuring instruments located outside the pressure vessel of a PWR are sensitive to the power developed in the outer portion of the core because of the small migration area of water moderated reactors. The question arises as to what

extent is the response of these instruments to changes in power shapes within the core adequate when possible axial, radial, and azimuthal variations occur.

The aim of the study was to establish detector response functions that can be used to correlate detector responses with power tilts regardless of the mechanisms involved in producing these tilts. For simplicity, the analysis was based on diffusion theory and the response of a detector to unit power at a point in the core determined by an adjoint type of calculation. Separability of the response function in terms of spatial coordinates was first assumed and its validity checked by two-dimensional calculations. Calculations were first carried out for line detectors and later for point detectors, and it was found that to first order the responses differed only by an amplification factor.

M. LEVINE, A. ARONSON

Xenon Instability in Boiling Water Reactors

The saturating effects of voids places an upper limit on the stable region of operation of BWR's. A study of fundamental mode xenon induced instability in BWR's was therefore carried out by taking this effect into account. At the beginning of life this upper limit is several times the power level of BWR's of the Oyster Creek type. Thus the effect is not limiting with the present generation of power reactors. However, the effect may become more significant for higher power reactors, particularly at the end of life.

Calculations show that the location of the stability limits of the fundamental are relatively insensitive to slip ratio, core length, or rod location but are most sensitive to the degree of inlet sub-cooling and the value of the xenon absorption coefficient.

G. LELLOUCHE

Reactor Physics Experimental Group

FAST REACTOR CELL STUDIES

Core 2 of the fast critical assembly FS-1 was modified to accept a test box located in the stationary half of the assembly. Measurements of the spatial equilibrium in this test box loaded with 1.2 cells (the box and the various cells are described in the next paragraph) indicated that it was necessary to modify the fuel loading of FS-1 to create a more homogeneous region at the core center. Subsequent equilibrium measurements

with the 1.2 cells indicated that the new core loading was homogeneous. Fine structure measurements were also performed in the box loaded with 1.2 cells. Equilibrium measurements were carried out in the box loaded with 1.4 cells and begun in a voided variation of the 1.2 cells.

The test box was made of 0.125-in.-thick stainless steel; inside dimensions were $3.0 \times 3.0 \times 9.7$ in. The loading of the box was nominally the same volume percent as that of the core: 7.0% U, 9.7% stainless steel, 82.9% graphite, and small amounts of void and nickel. It was made up of 3×3 -in. plates of various thicknesses of graphite, uranium, and steel. The cells investigated were denoted as either 1.4 or 1.2 cells. These corresponded to the test box loaded with 3 and 6 unit cells respectively. A 1.2 unit cell was made up of plates arranged in the following order: (1) 0.676 in. of graphite, (2) 0.079 in. of steel, (3) 0.116 in. of U, (4) 0.079 in. of steel, and (5) 0.676 in. of graphite. The 1.4 unit cell was made up of plates in the same order but with all the thicknesses doubled. The 1.2 voided cell was similar to the normal 1.2 cell except that that half of the graphite next to the steel was removed in each of three central unit cells of the test box.

Measurements of the cell structure equilibrium in Core 2 indicated that the core loading in the vicinity of the test box was not satisfactory for carrying out measurements. This was due to the absence of ^{235}U in the edges of the central fuel plates. Core 2 was reloaded with the fuel positioned to eliminate the inhomogeneity and called Core 2-A. Equilibrium measurements in Core 2-A indicated that it was homogeneous.

A subsequent series of experiments was carried out in the 1.2 cells which examined the rate at which the fine structure in the box approached equilibrium. In these measurements traverses transverse to the cell plates (in the 9.7-in. direction) were considered as Z traverses, the vertical traverses (parallel to the plates in the 3-in. direction) were X traverses, and the horizontal traverses parallel to the plates (in the 3-in. direction) were called Y traverses. Depleted and enriched uranium foils were placed (in separate runs) in selected positions in the cells and their fission rates measured so that the rates at which the fine structure approached equilibrium in the X , Y , and Z directions were determined. These measurements indicated that equilibrium was achieved within $\frac{3}{4}$ in. of the boundary in the X and Y directions and within the first unit cell in the Z direction.

Figure 1. Relative ^{238}U and $^{238}\text{U}/^{235}\text{U}$ fission activation distributions in Cell 1.2.

The next series of experiments was the measurement of the fine structure in the central 1.2 cell of the test box using ^{235}U and ^{238}U fission product and Mn activation activities. The measured distribution of the ^{235}U and ^{238}U fission product activities (see Figure 1) were in good agreement with DSN calculations carried out by H. Ludewig of the Theoretical Group. Tests for interaction effects between foils indicated that considerably more distance had to be maintained between the Mn foils than between the ^{235}U and ^{238}U foils to avoid perturbation. The ratios of activities measured at the center of the graphite to those measured at the center of the uranium were found to be 1.149 for ^{235}U , 0.771 for ^{238}U , and 1.435 for Mn. The latter has not been corrected for self-absorption.

During the preceding sequences considerable effort was extended in developing techniques and

procedures for taking and analyzing the data. Exposure times, reactor power levels, and access time were optimized so as to reduce daily personnel radiation exposure. This resulted in a reduction in radiation exposure by a factor of 5 over the levels experienced in the initial experiments. A program was written to allow essentially on-line data analysis using the local SDS computer.

Following the completion of the 1.2 cell Mn distribution the test box was loaded with the 1.4 cells and studies were performed on the fine structure transients in the Z direction by using ^{235}U and ^{238}U fission activation. It was shown that equilibrium in the Z direction was attained in the central cell to within 0.5%. The X and Y traverses did not yield conclusive evidence that equilibrium had been achieved in these directions.

Studies of the rate at which the fine structure came to equilibrium were also carried out in the voided 1.2 cells. These studies indicated that equilibrium was achieved within 1 in. of the cell boundary in the X and Y directions. Equilibrium was approached more rapidly in the graphite than in the uranium but the rate was not measurably dependent upon the axial (Z) position at which it was measured in either material.

A measurement of the hydrogen content of the test cell graphite carried out by the Hot Chemistry Analysis Group indicated a hydrogen concentration of ≈ 300 ppm (by weight). The significance of this amount of hydrogen is being assessed by H. Ludewig of the Theoretical Group. A preliminary evaluation shows that the effect is significant in terms of foil activation distributions. H. WINDSOR, P. PALMEDO, E. WEINSTOCK

MEASUREMENT OF DELAYED NEUTRON PARAMETERS FOR ^{235}U

Half-lives, Relative Yields, and Spectra

The Continuous Production Delayed Neutron (CPDN) experiment has continued and preliminary data are now expected sometime next year. The experiment consists basically of passing a 50-m continuous steel band, containing 0.001-in.-thick ^{235}U ribbon, past a neutron beam from Neutron Source Reactor I and counting delayed neutrons at some distance from the irradiation point. By varying the speed of the band, the various delayed neutron groups can be emphasized, and individual yields and half-lives can be derived from the composite data. Of particular importance is the fact

that at each band speed one can measure, continuously, a spectrum that is constant in time.

The major emphasis in the experiment for the past year has been aimed at developing the band transport apparatus. Various steels were welded into 10-ft loops and tested on a small, high-speed machine for endurance. The results of such testing indicated that either of two steels, Barcoird or Hard-Edge Flex Back, would be more than acceptable for the purposes of the experiment. Similar testing for techniques of holding the ^{235}U ribbon to the steel band has been performed and work will continue in this area. At present, it has been found that the best way of attaching fuel to the band is simply by using a high quality adhesive tape. The ^{235}U ribbon is cut into 2-in. lengths and taped to the outside of the band at $\frac{1}{4}$ -in. intervals. Polyethylene, Mylar, Fiberglas, and cloth-backed adhesive tapes were considered, and the results of testing have shown them all to be acceptable. However, more stringent testing is required to insure integrity of the band-fuel system under various conditions. A band transport apparatus has been assembled and partially tested. This device is capable of providing band speeds from about 0.003 to 55 m/sec with a speed stability of $\pm 0.2\%$ of base speed. The apparatus currently accommodates a 27-m band and speed stability was measured as $< \pm 0.2\%$ for base speed.

A neutron detector developed at Los Alamos, with a near constant response to neutrons having energies between 25 keV and 3 MeV, was constructed and will be used to measure delayed neutron production rates. The measurements of delayed neutron spectra will rely heavily on the proton recoil proportional counters that are described in another section of this report.

A Measurement of β for Thermal Fission

The total delayed neutron fraction, β , was measured for thermal fission of ^{235}U . The currently accepted value for β was determined by the use of three absolutely determined parameters. In this experiment, the basic approach was to compare the prompt plus delayed neutron count rate due to a ^{235}U sample in a neutron beam with the count rate due to delayed neutrons at the time of beam termination (time, $t=0$). In order to obtain the delayed neutron count rate, an integral count of delayed neutrons was taken in the time interval of 1.852 to 41.852 sec following beam termination. The delayed neutron count rate was then obtained

by converting the integral count to a count rate at time zero with the use of delayed neutron relative yields and half-lives.

An important aspect of the experiment was the use of the detector with near-constant response to neutrons with energies between 25 keV and 3 MeV. Although a slight correction ($\approx 1\%$ on β) was made for the detector response difference for delayed and fission neutrons, the use of this detector greatly enhanced experimental simplicity. Additional slight corrections (all $< 1\%$ on β) were made for environmental scattering effects, neutron beam stability, and effects of fission neutrons on the beam intensity monitors.

The results of the measurement yielded a preliminary value for β , 0.00653 ± 0.00025 . The currently accepted value for β (measured about 1955) is in agreement with this value, and the errors of the two measurements are comparable. The error of this measurement due to experimental uncertainties was about 1.3% and the error due to half-life and yield uncertainties used in the analysis for β was about 3.7%.

An advantage lies with the present measurement in that the data can be reanalyzed using improved delayed neutron half-lives and relative yields (as expected from the CPDN experiment) to provide a revised value for β . J. CONANT

COMPILATION OF FAST REACTOR EXPERIMENTS

As a result of correspondence and personal visits, agreement has been obtained from the principal foreign laboratories engaged in fast reactor physics to contribute to the compilation of fast reactor experiments. In addition to the U.S. facilities, the laboratories to be covered will be Winfrith and Aldermaston (U.K.), Cadarache (France), Karlsruhe (Germany), Studsvik (Sweden), JAERI (Japan), and Obninsk (U.S.S.R.). The initial work on the compilation has shown that, because of the gaps and inconsistencies in the published literature, considerable collaboration with the original investigators will be required if the compilation is to be reasonably definitive. By the same token the need for such a compilation has become increasingly apparent.

The first set of compiled data to be published will be from the ZPR-3, -6, and -9 assemblies. These data have been compiled and are currently under review by physicists at Argonne National Laboratory. P. PALMEDO, J. CONANT, J. PHELPS

FAST NEUTRON SPECTROSCOPY

Work has continued on the development of fast neutron spectrometers. Efforts have centered around the method that uses proton recoil proportional counters. Methane filled counters have been used to cover the energy range 100 keV to 1 MeV, and hydrogen filled counters have been used to cover the energy range 1 to 100 keV. Data reduction codes have been developed and tested with measurements of a variety of fast neutron spectra. This spectrometer system will be used in the fast reactor program at Brookhaven particularly in the measurement of delayed neutron spectra.

The Brookhaven Van de Graaff accelerator was used to produce monoenergetic neutrons for the purpose of testing the spectrometer system. The ${}^7\text{Li}(p,n){}^7\text{Be}$ reaction was used to generate neutrons at several energies. These measurements were designed to verify energy calibrations based on the 615-keV ${}^{14}\text{N}(n,p){}^{14}\text{C}$ reaction, to provide information about the eV per ion pair values for carbon and nitrogen recoil, and to provide response functions for comparison with those calculated by the data analysis code JERICHO.

Figure 2. Methane counter gamma-ray responses.

The inherent sensitivity of proportional counters to gamma rays results in the need to differentiate between proton recoil events and gamma-induced events that deposit equal amounts of energy in the sensitive volume of the counter. Such differentiation can be accomplished on the basis of the difference in rise-time of the two types of pulses, as shown by Bennett [*Nucl. Sci. Eng.* 27, 16-27 (1967)]. The pulses, sorted by energy and rise-time, are stored in a two-parameter analyzer. The data of a single energy slice have the form of two peaks, the peak of shorter rise-time being the neutron information and the peak of longer rise-time being gamma information.

The initial data reduction code searched for and identified these two peaks and then summed the data in the neutron peak. This technique worked well in energy regions where the data were well behaved but was not satisfactory in regions where the peaks were not well resolved or where statistical fluctuations in the data were appreciable. A new technique has been developed which makes use of a measured gamma response function for each counter. The response is energy dependent, thus requiring that the gamma ray spectrum for each measurement be mocked-up. For example, for the measurements made with the Van de Graaff, the response function was determined for the prominent gamma rays (478 keV) associated with the ${}^7\text{Li}(p,n){}^7\text{Be}$ reaction by measuring the gamma response for several monoenergetic gamma-ray sources of similar energy. The variation of response with gamma ray energy is shown in Figure 2. The response for 478 keV was estimated from these data and the log of the response function was fit by the method of least squares to a fourth degree polynomial. The response function was normalized to the gamma-neutron data at energies where the data were well behaved. The gamma intensity as a function of energy was calculated and subtracted from the integral count rates.

In order to measure neutron energies in the keV range, the hydrogen counters must be operated at high gas gains. Unfortunately, because of space charge saturation, the usual calibration standard [615-keV ${}^{16}\text{N}(n,p){}^{14}\text{C}$] cannot be used at this high a gas gain. The technique used to overcome this difficulty is based on the relationship between gas gain and voltage suggested by Deithorn (NYO-6628). The gas gain is measured for various voltages and the data are fit to the Deithorn expression, which yields the constants for the par-

ticular counter. The gas gain can then be calculated for any counter voltage for which the Deithorn expression is valid. A thermal column was constructed at the south face of Neutron Source Reactor I in order to obtain a well thermalized neutron source for calibration measurements employing the $^{14}\text{N}(n,p)^{14}\text{C}$ reaction.

Work continued on the development of the codes to convert the measured pulse spectra to neutron spectra. The least squares technique with variable constraints was found not to be completely satisfactory and a new approach was explored. The latter consists basically of using the counter response matrix generated by the JERICO code to provide a correction to the normal method of differentiating the pulse spectrum. This technique is reasonably straightforward and has produced promising preliminary results.

W. TUNNEY, P. PALMEDO, H. KOENIGSBERG

Pu-Al-D₂O LATTICES

The importance of plutonium in the breeder-reactor economy has stimulated an interest in obtaining better values of basic cross-section data. In particular, large discrepancies have been reported in the value of alpha (σ_c/σ_f) for plutonium in the epithermal energy range, indicating a need for additional data. The series of exponential experiments reported here provides data that can be used to evaluate plutonium cross-section sets as well as analytical methods used in designing plutonium-fueled reactions.

A preliminary calculation using the HAMMER reactor code established the plutonium fuel con-

centrations and lattice pitches which would generate neutron spectra in the region of interest. Heavy water was chosen as the moderator in preference to light water because it is possible to obtain much "harder" neutron spectra in tight lattice configurations. Thirteen lattices were examined with moderator-to-fuel ratios ranging from 14.5/1 to 0.71/1 and with various amounts of boron dissolved in the heavy water. The boron provided a means of assuring subcriticality in some cases as well as hardening the neutron spectra and reducing neutron leakage from the assembly.

Material bucklings were measured by means of foil activations along the central axis and diameters of the lattices using indium, gold, and manganese. Normally, in a well moderated assembly the material buckling is energy independent and it does not matter what type of neutron detector or foil activation is used to measure it. However, it is not certain whether or not that is the case in the Pu-Al-D₂O lattices, since the neutron spectra are so hard and neutrons reflected from the surrounding media may cause the spectra to vary continuously throughout the assembly. There is, in fact, some indication of this effect, since there is a slight difference of buckling as measured with various types of foils.

An attempt was made to minimize reflector effects around the Pu-Al-D₂O lattices by placing boral and ≈ 8 in. of borax around the lattice tank, and by completely filling the tank with fuel rods as much as possible in every case. Nevertheless, the extrapolated diameter, as determined by foil activations, was somewhat greater than that expected for a bare reactor (calculated as $0.7 \lambda_{tr}$), indicat-

Table 2

Moderator/fuel vol ratio	B ₂ O ₃ concentration, mg/ml	D ₂ O purity, mol %	Foil material	Bm^2, m^{-2}	k_{eff}
0.99	29.8	97.65	Gold	$2.5 \pm .2$	1.0223
0.99	19.0	97.30	Gold	$6.5 \pm .25$	1.0371
0.99	0.0	99.26	Gold	$15.5 \pm .3$	1.0396
0.99	0.0	98.96	Manganese	$17.4 \pm .2$	1.0065
1.49	28.75	98.34	Gold	$-3.1 \pm .2$	1.0013
1.49	0.0	99.05	Gold	$19.65 \pm .3$	1.0127
1.99	18.9	97.50	Manganese	$19.8 \pm .25$	1.0101
1.99	18.9	97.70	Gold	$-0.96 \pm .2$	0.9984
1.99	0.0	98.92	Gold	$23.8 \pm .2$	0.9930
1.99	0.0	98.89	Manganese	$23.8 \pm .2$	0.9930

ing that some neutrons are reflected from the borax and boral and are returned to the core.

Disadvantage factors were measured in five lattices with the use of Pu-Al fission foils. For this purpose, sector foils were placed in the fuel and moderator regions in order to get the ratio of ^{239}Pu fission rates in the moderator and fuel regions.

Activation and cadmium ratios were measured in two lattices by using Au, In, Mn, and ^{239}Pu foils. Subsequent activations in a thermal neutron flux served to normalize the foils and detecting systems so that the results can be interpreted in terms of ratios of average microscopic cross sections for the various foil materials.

In general, the measurements of material buckling will be compared with theoretical calculations over a wide range of lattice pitches and neutron spectra. In this way the data will serve as a benchmark in verifying and selecting best sets of nuclear data. The measurements of disadvantage factors, activation, and cadmium ratios will serve to verify detailed calculations on a few of the lattices.

A preliminary analysis of some of the experimental data [*Trans. Amer. Nucl. Soc.* 12, 244 (1969)] with the use of ENDF/B cross sections was done using the measured material bucklings as input bucklings in the HAMMER reactor code. The large deviations of k_{eff} from unity indicate deficiencies in the ENDF/B cross sections for plutonium (Table 2). A detailed analysis, using all of the data and using more sophisticated methods, is currently being done by O. Ozer of the Theoretical Group.

The experimental part of this project has been completed and a report including all of the detailed information is being prepared. G. PRICE

PLUTONIUM ALPHA EXPERIMENT

Uncertainties in the epithermal capture-to-fission ratio (alpha) of ^{239}Pu and its effect on the doubling time of plutonium-fueled breeder reactors prompted a measurement of alpha in the HFBR. For this purpose, plutonium and uranium samples were exposed under a thick boron shield in the V-15 facility of the HFBR. Six ^{239}Pu foils (containing only a few ppm of the higher isotope) and six ^{235}U foils were irradiated for 16 days in the central irradiation thimble of the HFBR. Each foil contained ≈ 1 mg of fissionable material. Also included in the foil package were Co-Al foils as flux monitors.

The foil package was surrounded by a B_4C -Al shield containing 35% B_4C enriched to 90% ^{10}B . The purpose of the shield was to suppress reactions with low energy neutrons so that a significant fraction of the reaction (fission and captures) would occur in the energy region 1 to 25 keV, where the value of alpha for plutonium is in doubt.

Prior to irradiation, the plutonium foils were intercalibrated by detection of their gamma emission from 280 to 450 keV. The BNL intercomparison gave a total spread of only 5% in ^{239}Pu content. Some evidence of contamination by ^{241}Am was discovered in the gamma spectra. However, this contamination was estimated to be only a few nanograms in the fabricated foil and even less in a virgin sample of the starting material (PuO_2). It was concluded that the finished sample had been contaminated by the fabricator (Monsanto) and that the presence of ^{241}Am in such small quantities would not significantly affect the measurements as planned.

After exposure of the samples in the HFBR initial analysis of the ^{140}La fission product activity was performed with a Ge(Li) detector, following which irradiated ^{239}Pu and ^{235}U samples were sent to Idaho Nuclear Corp. (INC) and to Savannah River Laboratory (SRL) for mass spectrometric measurements. The latter obtained the $^{240}\text{Pu}/^{239}\text{Pu}$ ratio and the amounts of various fission products (^{137}Cs , ^{140}Ba , ^{95}Zr , etc.) produced in each of the foils as a result of the irradiation. However, serious internal inconsistencies have turned up in the fission product results which may be connected with discrepancies in their Pu assay.

Three unirradiated Pu samples were sent to Oak Ridge National Laboratory (ORNL) for Pu assay and were reported to vary in Pu content by as much as a factor of 2. On the other hand the BNL intercomparison gave a total spread among the samples of only 5%. The BNL measurements were originally carried out as a backup for the SRL and INC measurements, but in view of the various discrepancies they now assume greater importance.

Idaho Nuclear Corp. has not yet completed its analysis of the sample. Workers there will measure total Pu, $^{240}\text{Pu}/^{239}\text{Pu}$, and ^{137}Cs in each of the Pu samples and the corresponding quantities in the U samples, and have been appraised of the difficulties so far encountered.

Despite the discrepancies encountered with the isotopic analyses at the various laboratories, there

is considerable redundancy in the measurements. There will be sufficient data available to permit an evaluation of α for plutonium although it may require an arbitrary selection of data. Final interpretation of the measurement will be done with the assistance of H. Takahashi of the Theoretical Group.

E. WEINSTOCK

Publications

- CHERNICK, J., PRICE, G., AND LEVINE, M.M. Fast reactor data codes and integral experiments. In *Proc. Int. Conf. Brit. Nucl. Energy Soc. Physics of Fast Reactor Operation and Design, London, June 1969* (in press).
- DIAMOND, D.J. AND YIP, S. Space and time dependent neutron slowing-down. Submitted to *Nucl. Sci. Eng.*
- DIAMOND, D.J. AND YIP, S. Use of time moments in the space-time slowing-down problem. (A) *Trans. Amer. Nucl. Soc.* **12**, 211 (1969).
- DORNING, J. Extrapolation distances and diffusion parameters via pulse neutron analysis. Submitted to *Nucl. Sci. Eng.*
- DORNING, J. AND GINSBERG, A. Pulse neutron decay in heavy water spheres. Submitted to *Nucl. Sci. Eng.*
- DORNING, J., NICOLAENKO, B., AND THURBER, J. An integral identity due to Ramanujan which occurs in neutron transport theory. *Notices Amer. Math. Soc.* **16**, 235 (1969); *J. Math. Mech.* (in press).
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J.K. Some comments on pseudo-mode solutions of the initial-value problem obtained by analytic continuation: Thermal and fast systems. Presented at Conf. Transport Theory, Blacksburg, Va., Jan. 1969.
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J.K. Some mathematical considerations on Cauchy integrals related to pulsed neutron dispersion relations. *Ibid.*
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J. The asymptotic behavior of the special function $\mu(x, \beta, \alpha)$. *Notices Amer. Math. Soc.* **16**, 518 (1969).
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J.K. The theory of pulse decay in subcritical fast systems with general cross sections. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J.K. The time-behavior of pseudo-modes in subcritical fast systems described by exact elastic slowing down. *Ibid.*
- DORNING, J.J., NICOLAENKO, B., AND THURBER, J.K. Unstable decay states of far subcritical fast assemblies. (A) *Trans. Amer. Nucl. Soc.* **12**, 251-2 (1969).
- DORNING, J.J. AND THURBER, J.K. An explanation of the apparent violation of the maximum absorption theorem. (A) *Ibid.* **11**, 579-80 (1968).
- DORNING, J.J. AND THURBER, J.K. Purely discrete neutron wave phenomena in the continuum region. (A) *Ibid.*, 580-1.
- DORNING, J.J. AND THURBER, J.K. Some comments on observable modes and pseudo-modes imbedded in the continuous spectrum of the linear Boltzmann operator for the wave and poisoning problem. Presented at Conf. Transport Theory, Blacksburg, Va., Jan. 1969.
- GOLDSTEIN, R. An analytical approximation to the Doppler broadened line shape. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- GOLDSTEIN, R. AND LANCEFIELD, M. Variational functionals with trial functions having arbitrary points of discontinuity. *Ibid.*
- GOLDSTEIN, R. AND SHOTKIN, L. Decreasing the computation time of excursions near and above prompt critical. *Ibid.*
- GOLDSTEIN, R. AND SHOTKIN, L.M. Increasing the iterative time-step in fast-reactor calculations. (A) *Trans. Amer. Nucl. Soc.* **12**, 148-9 (1969).
- GOLDSTEIN, R. AND SHOTKIN, L.M. Use of prompt-jump approximation in fast-reactor kinetics. *Nucl. Sci. Eng.* **38**, 94 (1969).
- HENDRIE, J.M., HELLENS, R.L., PALMEDO, P.F. Brookhaven Fast Reactor Lattice Experiments. BNL-RP-4 (F), Oct. 1966 (issued Aug. 1969). (For official use only.)
- KOUTS, H., DOWNES, K.W., AND COURT, A.J. Safety Report for the FS-1 Critical Experiments. BNL-RP-3 (G), 1969. (For official use only.)
- LANCEFIELD, M.J. Space energy flux synthesis in transport theory. *Nucl. Sci. Eng.* **37**, 423-42 (1969).
- LANCEFIELD, M.J. The overlapping group method. (A) *Trans. Amer. Nucl. Soc.* **12**, 149-50 (1969).
- LELLOUCHE, G.S. NØAH. BNL 50157 (T-523), Jan. 1969; *Nucl. Sci. Eng.* **36**, 456 (1969).
- LELLOUCHE, G.S. On the solutions of a certain integral equation. Submitted to *SIAM J. Contr.*
- LELLOUCHE, G.S. Xenon instability in boiling water reactors. Submitted to *Nucl. Sci. Eng.*
- LUDEWIG, H. A method for treating the neutron leakage in small exponential cores. *Ibid.* **35**, 289-95 (1969).
- OZER, O. Analysis of BNL Pu-Al-D₂O lattice experiments. *Trans. Amer. Nucl. Soc.* (in press).
- PALMEDO, P.F. AND CONANT, J.F. Neutron diffusion in aluminum-water lattices: Measurements of anisotropy in the continuous eigenvalue region. *Nucl. Sci. Eng.* **36**, 326-36 (1969).
- PALMEDO, P.F. AND WEINSTOCK, E.V. FS-1 Cores 2 and 2A. BNL-RP-1 (F) (issued 1969). (For official use only.)
- PALMEDO, P.F. AND WEINSTOCK, E.V. Preliminary Fast Reactor Heterogeneity Studies in FS-1. BNL-RP-2 (F), Aug. 1969. (For official use only.)
- PHELPS, J.P. Safety Report, CEPFR-1 Critical Experiments. BNL-RP-5 (G) (issued 1969). (For official use only.)
- PHELPS, J.P., CONANT, J.F., COURT, A.J., DOWNES, K.W., AND WINDSOR, H.H. CEPFR-1B Measurements and Assembly Description. BNL-RP-7 (F) (issued 1969). (For official use only.)
- PHELPS, J.P., COURT, A.J., AND DOWNES, K.W. CEPFR-1A Measurements and Assembly Description. BNL-RP-6 (F) (issued 1969). (For official use only.)
- PHELPS, J.P. AND WEINSTOCK, E.V. Criticality measurements on nearly homogeneous enriched uranium-graphite systems. *Nucl. Sci. Eng.* **34**, 237-50 (1968).
- PRICE, G.A., LUDEWIG, H., SCHILLER, R., AND CHANDRAMOLESHWAR, K. Studies of some plutonium exponential assemblies. (A) *Trans. Amer. Nucl. Soc.* **12**, 244-5 (1969).
- PRICE, G.A. AND WINDSOR, H.H. Pu-Al-H₂O Buckling Measurements. BNL-RP-8 (F) (issued 1969). (For official use only.)

- PUROHIT, S.N. A theoretical study of U-238 Doppler coefficient and its variation with resonance parameters. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- PUROHIT, S.N. *The Doppler Coefficient of U-238 Neutron Resonances and of the PWR Fuel Cell*. BNL 50185 (T-540), July 1969.
- ROTHENSTEIN, W. Code abstract of REPCDC. Submitted to *Nucl. Sci. Eng.*
- ROTHENSTEIN, W. ENDF/B effective resonance integrals. (A) *Trans. Amer. Nucl. Soc.* **12**, 246-7 (1969).
- ROTHENSTEIN, W. Monte Carlo code for the calculation of resonance reactor rates and effective resonance integrals based on ENDF/B data (REPCDC). Informal Report BNL 13851.
- SABINE, T.M. AND WEINSTOCK, E.V. The collimation of thermal neutrons. *J. Appl. Cryst.* (in press).
- SEHGAL, B.R. Analysis of Brookhaven ^{235}U -graphite critical experiments. *Nucl. Sci. Eng.* **34**, 251-62 (1969).
- SHEA, T.E. AND PUROHIT, S.N. Doppler-broadened quasi-resonance fission cross section: Application to U^{235} . Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- SHEA, T.E., PUROHIT, S.N., BYOUN, T.Y., AND BLOCK, R.C. Temperature-dependent self-indication ratio studies on 1.15 keV resonance in iron-56. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- SHOTKIN, L. Comparison of modal and iterative approaches to space and space-time nonlinear problems. *Nucl. Sci. Eng.* **36**, 97-104 (1969).
- SHOTKIN, L.M. Instability bounds in linearly stable systems. *Ibid.* **35**, 211-19.
- SHOTKIN, L.M. Some similarities between boiling and condensing flow. (N) *Ibid.*, 154.
- SHOTKIN, L.M. The effect of slip ratio on the crucial boiling length in two-phase instability. In *Proc. Symp. Dynamics of Two-Phase Flow*, Vol. I, p. 935, Commission of the European Communities, CID, Brussels, June 1969.
- SHOTKIN, L.M., HETRICK, D., AND SCHMIDT, R. The effect of delayed neutrons on autonomous oscillations in nonlinear reactor systems. *Trans. Amer. Nucl. Soc.* **12**, 294-5 (1969).

Nuclear Materials Division

H. KOUTS

The Nuclear Materials Division is a Technical Support Organization (TSO) established to provide technical advice and guidance to the AEC's Office of Safeguards and Materials Management (OSMM) in a number of areas. These include the research and development being conducted for the AEC's program in safeguards and materials management, the identification of needs for additional research pertinent to this program, field-testing of equipment produced as a result of the research, the analysis and evaluation of data resulting from systems studies, technical aspects of the AEC's development of standards and criteria for safeguards systems, and similar technical problems involved in modifying the safeguards program to keep pace with the domestic nuclear industry. The group also assists the AEC in efforts to encourage and support other national and international safeguards systems.

TSO helped organize and participated in the Nuclear Safeguards Symposium at Los Alamos Scientific Laboratory (LASL), Oct. 27-30, 1969. In the international area, TSO was a participant in two IAEA-sponsored panels, one on the safeguarding of fabrication plants and the other on safeguards system studies.

Records of past safeguards incidents were reviewed and evaluated. The purpose of this review was to assess the weaknesses in the past methods of nuclear materials control and safeguards. Identification of these weak points will be useful in system studies aimed at upgrading safeguards practices.

The work of TSO is usually embodied in informal reports transmitted to the OSMM and usually not published. However, a brief discussion of the tasks assigned to the group is given below.

PLANT INSTRUMENTATION FIELD TESTS

One factor in developing higher levels of safeguards is the depersonalization of the safeguards system by the use of plant instrumentation to minimize the need for resident inspection personnel. The system studies now in progress will identify critical points in the nuclear fuel cycle that will re-

quire surveillance either by instruments or personnel. There are, however, many such points that can be and have been identified on the basis of past experience and evaluation of currently available data.

To provide advice and guidance to OSMM in this area, TSO has been asked to do the following:

- (1) Identify critical points in the nuclear fuel cycle that are amenable to instrumentation.
- (2) Determine types and kinds of instruments that are available for plant safeguards measurements.
- (3) Determine what development is needed.
- (4) Field test effectiveness of instruments and/or components in providing safeguards information and evaluate them from a cost-effectiveness standpoint in selected plants.
- (5) Maintain current knowledge of technical studies of instrumental development.

At the request of OSMM, TSO has assembled instrumentation for making passive gamma and neutron measurements and has used them in field tests at four selected plants. Measurements applicable to safeguards were made of $\text{PuO}_2\text{-UO}_2$ fuel rods, unirradiated PuO_2 scrap in 55-gal drums, concentrated PuO_2 scrap in 2-liter bottles, and small Pu-Al alloy platelets intended for use in a critical assembly. A description of these field tests is given below.

Gamma and Neutron Measurements of SEFOR Fuel Rods

During the summer of 1969 a series of passive measurements were made on suspect $\text{PuO}_2\text{-UO}_2$ rods from the SEFOR reactor. These measurements were a cooperative effort of groups from BNL, the General Electric Company, the Naval Research Laboratory, and SEFOR.

In these measurements, passive γ -ray and neutron methods were both used to determine the quantity of Pu in some 65 rods from the SEFOR reactor, some of which were suspected of having less than the specified Pu loading.

The γ -ray scans were done with both NaI and Ge(Li) detectors. Where the NaI was used, the count rates integrated over intervals including

three separate energy levels [60 keV (^{241}Am γ ray), 207 keV (^{237}U γ ray), and 385 keV (^{239}Pu γ ray)] were all recorded. In the case of the Ge(Li) runs, the prominent gamma rays including the 414-keV peak in the 385-keV complex were recorded. Both a coincidence rate and a total count rate were recorded in the neutron measurements.

Some of the fuel that had already been irradiated in the reactor was too radioactive to be counted with NaI. However, it was found that the Ge(Li) spectrometer gave satisfactory results with this fuel after the induced radioactivity had decayed for a few months. The neutron method was, of course, unaffected by the high γ -ray background.

In these measurements, all rods were compared with a standard rod (SEFOR is fueled with single rods of $\approx 7/8$ in. o.d.). The results of all the different methods agreed to within ≈ 2 to 3% in the deduced ^{239}Pu content. As expected, it was found that results at the 60-keV energy level showed larger variations than that of higher energy lines. However, both single and coincidence neutron measurements gave approximately the same accuracy.

Development of In-Plant Gamma-Ray Measurement Techniques

Gamma-ray instrumentation was provided to evaluate the use of passive techniques to make rough measurements for identifying and sorting 55-gal drums of low-level scrap at a fuel fabrication plant.

Application of γ -ray spectroscopy to measure nuclear materials under plant conditions requires analytical techniques that (1) can be performed by

plant personnel, (2) employ rugged equipment, (3) produce analyzed results quickly, (4) can be used in areas with fluctuating backgrounds, (5) take into account sample geometries, and (6) take into account degradation of γ rays by the sample material.

In the initial phase of this test, a four-band technique was developed and used with laboratory instrumentation in a field situation at the Nuclear Fuels Services (NFS) plant in Erwin, Tenn. On the basis of tabulated γ -ray yield and energy data, four energy bands (175 to 185 keV, 280 to 310 keV, 310 to 400 keV, and 900 to 1500 keV) were selected for measurement of ^{235}U , ^{233}U , ^{239}Pu + ^{241}Pu , and ^{238}U respectively. These bands emphasize γ rays emitted by the specific isotopes, but they are not mutually exclusive. Four-channel information shown in Table 1 illustrates the characteristic patterns of γ rays found for these isotopes. A NaI(Tl) detector and four single-channel analyzers were used to accumulate the four-channel data. Other equipment, such as a 512-channel analyzer and a precision pulser were used for calibration purposes. All equipment was temporarily installed in a 1-ton carryall van (Figures 1 and 2) which was used as a mobile laboratory at the plant site. After a few days of checking out equipment and outlining procedures for calibration and standardization of the four bands, the lab was turned over to and operated by plant personnel at NFS. The plant used the system to identify and sort 450 drums of material into categories for possible reprocessing. Measurements were made in an open field adjacent to the plant. The distance between the drums and the NaI detector was 14 ft.

Table 1
Count Ratios Found in Energy Bands

Sample type	Energy band			
	175 to 195 keV	280 to 310 keV	310 to 400 keV	900 to 1500 keV
10 g Pu	0.457	0.126	1.000 ^a	0.006
21 g ^{233}U (plus daughter products)	2.67	1.00 ^a	4.26	1.51
93.5% ^{235}U	1.00 ^a	0.008	0	0.07
^{238}U (0.2% ^{235}U)	0.07	0	0	1.00

^aNormalized to channel of interest.

Figure 1. Assay truck.

Figure 2. Assay instrumentation inside truck.

Results obtained in this field test of the four-band technique were quite encouraging. It was found that (1) the sensitivity of the method is excellent, (2) plant personnel had little trouble operating the equipment and got good results, (3) data can be accumulated rapidly, and (4) identification of the isotopes ^{233}U , ^{235}U , ^{238}U , and $^{239}\text{Pu} + ^{241}\text{Pu}$ is possible using simple equipment. Before gamma spectroscopy can be used as a working tool, instruments must be made rugged in order to withstand severe vibration and the temperature and humidity conditions typical of plant environments. In addition, more development work is needed in order to take into account fluctuating backgrounds and the degradation of γ rays due to the sample material.

Passive Neutron Measurement of Plutonium Scrap

An evaluation of passive neutron measuring techniques for nondestructive assay was also performed at the NFS. These measurements were made on recycle scrap material at the time of preparation for the plant's annual physical inventory. The material was stored in 2-liter polyethylene bottles containing 0.5 to 5 kg each of $\text{PuO}_2\text{-UO}_2$ pellets. An array of BF_3 detectors was used to make a gross neutron count of each bottle.

The amount of ^{240}Pu contained in a bottle was estimated by comparing the neutron count rate with that obtained with prepared standards. Corrections for detector efficiency and neutron multiplication were made as a function of the size and weight of the sample. Corrections fell in the range of 5 to 15%. The potential of this method for precise quantitative analysis of ^{240}Pu content is currently under investigation.

Passive Gamma and Neutron Assay of Pu-Al Plates

A test of passive γ and neutron instrumentation was made on Pu-Al alloy plates. These plates were part of an order of 2000 being manufactured by the Nuclear Materials and Equipment Corp. (NUMEC), Leechburg, Pa. The plates, which are to be used in a critical facility, are $2 \times 4 \times \frac{1}{16}$ in. thick; each contains ≈ 70 g of Pu.

The measurements of γ rays were made with a NaI detector and an off-the-shelf multichannel analyzer, both supplied by BNL. Additional measurements of γ rays were made with a Ge(Li) detector and a 1000-channel analyzer, both belonging to NUMEC. The neutron equipment was a

BNL-made neutron coincidence counter designed by the Naval Research Lab.

γ -Ray self-absorption effects were small in this case, and highly reproducible measurements were made with the NaI detector. The neutron coincidence instrument measured the ^{240}Pu content of the plates, thus providing supplementary information about the material.

U.S.-Canada Safeguard Equipment Development Program

TSO is participating in a joint program with the AECL and AECB of Canada, the Arms Control and Disarmament Agency, and the Sandia Corporation, for the development of instruments which might be used in an unattended safeguard system for reactors. TSO participation concentrated on the development of the required radiation sensors, and during the past year sensors have been supplied and tested for detecting fuel discharge from the reactor. A number of planning meetings of a Joint Working Group for this experiment have been held, both in Canada and in the U.S., with primary AEC representation being that from BNL. BNL was host to one of these meetings in June 1969.

Field Trips

TSO organized and participated in a series of visits to fuel fabricators and reprocessors for the benefit of contractors who are developing measuring techniques for the Office of Safeguards and Materials Management. The object of the visits was to identify places in the fuel cycle where techniques under development can make a substantial contribution to fuel management.

W. HIGINBOTHAM, A. COURT, K. DOWNES,
C. SASTRE, E. WEINSTOCK, M. ZUCKER

REPORT ON IAEA SAFEGUARDS INSPECTION OF NUCLEAR FUEL SERVICES AT WEST VALLEY

A part of the safeguards program of the International Atomic Energy Agency (IAEA) is the safeguarding of two Brookhaven research reactors and the Yankee nuclear power station. Safeguarding the latter has been extended to safeguarding the reprocessing of its spent fuel. Two campaigns of reprocessing of the spent fuel from the Yankee reactor have taken place since the agreement with the IAEA was extended to include reprocessing.

Both campaigns have been used by the IAEA in an experimental sense to develop appropriate methods for safeguarding reprocessing of spent fuel from nuclear power plants. The campaigns (and the safeguarding) took place at the chemical processing plant of Nuclear Fuels Services, West Valley, New York.

As part of the cooperative development of methods for international safeguards to be applied under the Nuclear Nonproliferation Treaty, the AEC arranged for observation of the two periods of IAEA safeguards. The TSO assisted the OSMM by providing an observer at the NFS plant during the second period involving safeguarding of chemical processing of Yankee reactor fuel. The objective of this task was to develop a written record of observation and a partial evaluation of the IAEA inspection.

The IAEA's operational activities began on May 2, 1969 with the inventory of 74 Yankee fuel assemblies in the NFS fuel storage basin, and it continued through July 17 when the last of the plutonium bottles was transferred to permanent storage in the recently completed N.Y. Atomic and Space Development Authority's (ASDA) Plutonium Storage Facility (PSF). The safeguarded material consists of 175.7 kg of plutonium.

The surveillance efforts at the plant were directed primarily toward the collection of process flow data obtained by reading the plant's measurement instruments.

The analytical inspectors of the IAEA used techniques involving security procedures for assuring sample integrity. They observed sample preparation or alternated with plant analysts in performing this key analytical operation. IAEA inspectors also used spikes and standards in controlling the sample integrity, and they shipped some samples to off-site laboratories for check-analysis.

The handling of accountability data was divided into three phases. Phase I consisted of the organization of the measurement data obtained by the IAEA plant and analytical inspectors, and the calculation of material quantities. This was a pre-programmed clerical operation without much data comprehension or evaluation. The second phase consisted of "real-time" material balance for the plant which was maintained by the Agency using fuel fabrication data, reactor operating data (burn-up), and input volume, density, and acidity for the dissolver solution. In the third phase, limits of error for the material balance parameters were de-

termined, and these results were used to assess the probability of diversion for the material in chemical processing. The limits of error for bulk measurements were based on the IAEA's evaluation of NFS process tank and scale calibration data. The limits of error for the analytical values were those presented by the plant. S. SUDA

REVIEW OF ACCELERATORS FOR NUCLEAR MATERIALS ASSAY

The present AEC research and development efforts on active methods of nuclear materials assay are concentrated in two main areas: (1) assay and interrogation using neutron beams, and (2) methods using a bremsstrahlung (x-ray) beam. Both techniques can be performed with radioactive sources, reactor radiation sources, or accelerators. In order to evaluate their suitability for safeguards applications, a study was made of available accelerator sources. The study considered linacs and microtrons as electron sources for producing bremsstrahlung, and accelerator sources of positive ions for producing high energy neutron beams. In addition, the use of methods depending on slower neutrons (slowing-down spectrometer and reactivity methods) was also investigated.

Electron Accelerators

Since it appeared that no ideal electron accelerator for safeguards application is available at present, one of the purposes of the study was to ascertain the future course of commercial electron accelerator development and to see if such development could be stimulated to produce devices appropriate to this application. It was felt that some compromises must be attained in the present techniques which require the use of the very versatile but quite expensive laboratory accelerators currently available. The following requirements were selected as boundary conditions for such a device.

1. Maximum no-load electron energy, 9 MeV.
2. Lowest electron energy of interest, 4 MeV.
3. Ability to run at 3 discrete energies.
4. Require 15- μ A average beam current at 1% energy resolution at 5.5 MeV.
5. Total current capability, 0.2 A at 3 μ sec.
6. Total available beam average power, $\approx$ 400 W.
7. The alternative to the above specification is a lower resolution but highly reproducible electron energy spectrum.

8. A small and transportable device, simple to operate.

9. Cost ultimately in the \$50,000 – \$70,000 price range. The first device or two could cost about \$100,000.

A number of manufacturers were questioned on their present ability to meet these requirements, and they were asked if such machines were not available, could they be developed in the near future.

Since the study of commercial radiation sources for purposes of safeguards is still continuing, it would be premature to recommend any specific device. However on the basis of the survey the following conclusions were drawn.

1. The small standing wave linacs seem to hold real promise for both neutron and gamma sources. They are simple, relatively cheap, inherently more stable than traveling wave machines, have an excellent energy spectrum, and are in demand for other applications.

2. Traveling wave linacs are, at present, more expensive than standing wave machines, have a poorer energy spectrum, and are more unstable and difficult to tune.

3. Flash x-ray machines as either neutron or gamma sources hold promise despite their large size, but this may not be an insoluble problem.

4. Betatrons seem to operate best in the wrong energy range for safeguards applications, and are quite expensive. Microtrons, as indicated below, appear to be more promising.

5. Present machines for the gamma assay methods make use of a machine with a very stable spectrum and low resolution. These low resolution machines with a high resolution magnet system have the disadvantage of being very complex, and they have low beam efficiency and high cost.

6. It has been recognized that the low energy electron machine produces more neutrons for *neutron* interrogation than the conventional positive ion *neutron* generators. Thus, the electron machines should be considered as sources for either class of radiation, so that one machine might satisfy both needs. However, no accelerator exists today which is really ideal for either application and is in a reasonable price range.

7. A fixed energy electron accelerator would reduce cost and complexity, and improve reliability, but the assay techniques must be adapted to the machine.

8. The present approach to technique development presupposes big cost reductions in electron accelerators that are now priced in the range \$150,000 to \$200,000. From this study, reductions do not seem likely. Thus, techniques that will work on inherently cheaper machines need attention.

Microtrons

Accelerators capable of producing high resolution electron beams are highly desirable where it is required to assay a material containing ^{235}U and ^{239}Pu , and to separate one from the other. Electron linacs capable of producing high beam currents with high resolution are very complex and inefficient. The microtron, widely used in the Soviet Union, is an accelerator with inherently high resolution and has promise of being relatively inexpensive to produce.

After a careful evaluation of the microtron concept, and comparing advantages and disadvantages, the following were recommended.

1. The microtron appears to be an ideal source from many standpoints, but experiments, both of a materials assay nature and also concerning fundamental accelerator technology, are needed. Examples of the first type of experiments are the study of the relative machine and target neutron and x-ray backgrounds from 4 to 8 MeV, and actual performance of some simple assays using prompt and delayed neutrons. Examples of the accelerator technology experiments are studies of machine-operating stability, cathode lifetime, ease of operation, and tuning. These experiments could be performed on existing machines in the U.S.

2. Since the microtron reliability factor is currently limited by cathode and injector lifetimes, it would be worthwhile to develop a simple and more reliable injector.

3. The microtron appears promising as an inexpensive accelerator that provides both neutrons and gamma beams for interrogation.

4. A need also exists to make a more detailed analysis of accelerator costs generally and that for the microtron in particular, including parts costs, design costs, development costs, fabrication costs, and overhaul and profit.

Positive Ion Accelerators

For nuclear materials safeguards assay, one can produce fissions in special nuclear materials either by gamma rays or by neutrons. In the preceding

parts of this study we have considered the use of gamma rays produced by microtrons and linac sources. Positive ion sources for directly producing neutron beams for interrogation purposes are being developed for nuclear materials assay. As pointed out previously, neutrons can be produced by low energy electron accelerators. However, the linac required for efficient neutron production is expensive, requires some measure of portability, and has not been fully adapted to this application as yet. Thus it is appealing to try to use a neutron interrogation beam from a present-day positive ion source, which can be small and inexpensive and which produces only neutrons and hence requires minimum shielding. This study reviewed the status of such sources.

A potential difficulty with positive ion accelerators, and a rather unique one, is that the neutrons are produced at too high an energy. Most positive ion accelerators use the (d,t) reaction to produce neutrons. This is by far the most efficient reaction for ion energies below several MeV. However, the neutrons thus produced have an energy of 14 MeV and are distributed almost isotropically. Neutron energy this high causes a shielding problem. And, what is more important for our purposes, neutrons at 14 MeV give roughly the same kind of reactions with all of the fissionable isotopes (^{233}U , ^{235}U , or ^{239}Pu). At epithermal energies, neutrons can effect a separation of the ^{235}U and ^{239}Pu interrogation signals. However, at 14 MeV the differences almost disappear. Also, at 14 MeV competing reactions such as $(n,2n)$ can cause a serious background problem.

The group at Los Alamos has been able to devise a method of using 14-MeV neutrons to compare carefully selected similar samples in a standardized geometry. However, for more general experiments, such as will be required in many safeguards applications, they have resorted to "tailored beams," i.e., neutron beams that have been moderated from 14 MeV down to 1 MeV or below. This is still preferable to starting with (d,d) neutrons, since the yield compared with a (d,t) source is so low.

A second serious problem in using the (d,t) reaction is the depletion of the target. Hence, the use of a rotating target would be required in some instances, and the accelerator must have a design that permits rapid and safe removal of used targets.

The big advantage with a positive ion accelerator is that small and inexpensive sources are com-

mercially available. These require minimum shielding, and they have, in many cases, been tested in applications where transportability is a consideration, as in safeguards work.

In order to obtain an optimum positive ion source for safeguards application, the requirements for such a source might be as follows.

1. Yield, 10^{10} to 10^{11} n/sec instantaneous.
2. Duty factor, 1 to 50%.
3. Lifetime, 500 to 1000 hr.
4. Sealed tube, no tritium handling.
5. Cost, \$25,000 to \$50,000.
6. Tube replacement, \$1500.
7. Portable, rugged, simple to operate.
8. Dark current ratio, 10^9 .
9. Dark current stability, 10 to 20%.

The two most promising approaches proposed by accelerator manufacturers to obtain these goals are (1) the pulsed voltage and ion source sealed tube approach and (2) the high voltage accelerator (1 MeV). The development of these approaches will require stimulation from the safeguards assay user since they are not off-the-shelf devices.

In addition, it is quite important here, as in the case of the commercial electron accelerators, that one perform simple nuclear materials assays on the commercial devices.

Other Active Assay Methods

In connection with the study of accelerators, other methods of active assay were evaluated. Techniques using lead slowing-down spectrometers and reactivity measurement devices were examined. The first technique appears to have limited application for the assay of regular metal fuel shapes containing ^{235}U and ^{239}Pu . The reactivity method appears to be costly, complex, and time consuming, and therefore appears to have little promise as a safeguards technique.

Radioactive materials as neutron sources will be evaluated in a future study. J. BEYSTER*

SYSTEMS STUDIES FOR NUCLEAR MATERIALS SAFEGUARDS

Systems studies are those analytical studies performed to define goals, determine ways by which these goals might be achieved, estimate the effectiveness of these methods, determine the strategies

*Consultant, Science Applications, Inc.

for implementing the methods, and estimate costs. The determination of alternative methods and strategies, and the effectiveness and costs of these, provide the basis for optimizing the methods of achieving a defined goal. In principle, the maximum effectiveness can be sought for a given cost, or the minimum cost can be found for a given effectiveness. In all studies of this kind, the definition of effectiveness is crucial. Measurement of effectiveness by different methods can lead to quite different conclusions as regards the optimum.

Particular difficulty in systems studies of nuclear materials safeguards is produced by the need to perform the analysis within a specified political context and within certain financial constraints. Certain potential strategies might in fact be forbidden for political reasons and regardless of how important the goal may seem to be, an indefinite amount of money cannot be spent to achieve it. Goals will be lowered instead. In nuclear materials safeguards, the best will have to be provided for the amount of money that will be available. It must also be realized that the analyses of the studies represent ideals that are seldom if ever approached closely, much less achieved. The studies should be regarded as only indicating the ideal solution to the problem that one seeks to approach.

Viewed this way the present program of systems studies must consist of analysis performed in the following steps. It must assess the credibility of threats of different kinds, in different contexts. It must analyze the capability of current methods to meet the threats, and determine the weaknesses of these methods. It must establish alternative methods that promise to remove the weaknesses and so meet the threats. It must assess the assurance provided by these alternative methods. It must devise strategies for achieving the methods. It must estimate the costs. It must provide schedules for meeting the alternative goals.

Responsibility for conducting the OSMM systems studies program is divided between Battelle Northwest Laboratories, the National Bureau of Standards, and TSO. A summary of the BNL effort is given below.

Systems Study Review

The systems studies efforts at Battelle Northwest Laboratory and the National Bureau of Standards have been reviewed with OSMM. As a result of these efforts plus a review of foreign systems studies,

particularly those performed at Karlsruhe, a set of systems analysis goals are recommended. These goals are of three kinds: development of computational tools, gathering of data to be used in calculations, and calculations using these tools and data. The existing and continuing work has been related to achievement of these goals.

Safeguards System Evolution

A safeguards system is characterized by a set of control elements. These control elements have been identified, and consideration is being given to a logical definition of the responsibility and actions of each of the participants (industry, national government, and international agency) in relation to these elements.

IAEA Panel on Safeguards Systems Analysis

A paper was prepared with OSMM for presentation to an IAEA Panel on Safeguards System Studies. This paper described the system of safeguards in existence in the U.S., summarized the safeguards system studies that have been performed in the U.S., identified certain problems that require solution, and described the systems studies program to be pursued.

Safeguards Simulation Model

A computer simulation has been initiated to replicate the flow of nuclear material in the fuel cycle. This simulation is intended both for analysis and design of safeguards alternatives. It will be used to evaluate alternative instrumentation capabilities in terms of their impact on total system performance, thereby providing guidance for instrumentation R&D. It will be used to compare alternative safeguards configurations which will provide information for balancing the system. In this application, the level of safeguards protection for any given budget will be equitably distributed across the fuel cycle. At a still later stage of development, data generated by the simulation will be used to simulate a safeguards information system. Still another use of the simulation will be to analyze adversary strategy. In this application, both the adversary and the authorities will generate plans and policies on the basis of information from the computer simulation.

H. KOUTS, W. MARCUSE, W. CAHILL,
L. GREEN, E. FRIEDLAND (Consultant)

SAFEGUARDS ANALYTICAL LABORATORY EVALUATION (SALE)

In the past, AEC-sponsored "round robin" analytical evaluation programs have made significant contributions in upgrading the state-of-the-art of analytical chemistry. Accordingly, a program is being developed whereby interlaboratory analytical performance for a wide range of nuclear materials will be assessed using the round robin approach.

Initial effort will be directed toward (1) establishing reference standards, wherever necessary, for in-process nuclear materials and (2) statistical determination of the degree of interlaboratory agreement attainable for these materials.

The development of the SALE program is a cooperative effort between OSM, New Brunswick Laboratory, and TSO. The New Brunswick Laboratory will be the control laboratory. Most of the analytical laboratories in the U.S. that are used in nuclear materials safeguards will participate.

Statement of the Program

At this time it is difficult to assess the accuracy of measurement for certain materials that are rou-

tinely found as inventory stock, because no reference material (standard) exists. Therefore, a primary need exists for reference material for certain plutonium and uranium compounds in this category.

The SALE program will also provide information on the performance capabilities for the analytical determination of uranium and plutonium compounds used in the special nuclear material fuel cycle. This information is needed for systems studies.

Methodology

The initial reference material will be UO_2 . Eventually about forty additional reference materials will be used in the program. The program with each sample has two stages. The first will involve determination of the reference composition of the material by the best analytical methods and equipment by certain selected laboratories. The second stage will consist of sending the samples to the participating laboratories, where more routine methods will be used. The results of these measurements should provide a measure of performance capability.

S. SUDA

Figure 3.

SEALS FOR SAFEGUARDS

An evaluation of the role of seals in nuclear material safeguards has been finished. This evaluation resulted in identification of problem areas and their possible solution in some cases. Techniques and procedures for identification and postmortem examination of seals were developed. These are now being applied on a routine basis on AEC seals. The testing of IAEA seals has been completed, and the results in the form of a movie and a report have been transmitted to the agency. A development program is under way for an improved seal concept based on metallic filaments imbedded in plastic. A display illustrating commercially available components for sealing systems is shown in Figure 3.

C. SASTRE

FUEL ELEMENT IDENTIFICATION

Work has started on the development of criteria for identification of light water power reactor fuel assemblies. The object is to have a unique assignment of letters and numbers for fuel assemblies, and to have those characters written in such a way that they are readable under the usual depth of water encountered in spent fuel storage ponds.

TSO is participating in the ANS-13 standards committee on fuel assembly criteria, as a member of the working group on standardization of identification markings on fuel assemblies for light water power reactors. The working group began its task by investigating present practices of numbering fuel assemblies, the visibility of identifying numbers, and techniques for application of numbers.

C. SASTRE

GLOSSARY OF TERMS

The glossary of special terms in the field of nuclear safeguards that was prepared by TSO has been circulated in the AEC, the US ASI Subcommittee on the Nuclear Glossary, the IAEA, and the UK group at Aldermaston, and comments have been collected. The information is incorporated in a master file which is stored on electromagnetic tape, and various selections of terms and definitions can be retrieved. The glossary has been through several drafts. At present the main effort is concentrated on a relatively short list of the most important terms, selected by the IAEA, and it is hoped that an agreed set of recommended definitions in English will be submitted to the IAEA early in 1970.

F. MILES

Publications

- COURT, A. AND HIGINBOTHAM, W.A. Survey of nuclear materials and possible measurement techniques. In *Proc. Inst. Nucl. Mater. Management Meet., Las Vegas, April 1969*, pp. 353-76.
- HIGINBOTHAM, W.A. Nuclear safeguards. *Phys. Today* **22**, 40-4 (1969).
- KOUTS, H. Systems studies for nuclear materials as safeguards. In *Proc. Inst. Nucl. Mater. Management Meet., Las Vegas, April 1969*, pp. 433-40.
- KOUTS, H. AND WILLIAMS, J.M. U.S. safeguards system studies. Presented at IAEA Panel on Safeguards Systems Analysis of Nuclear Fuel Cycles, Vienna, August 25-9, 1969.
- RASMUSSEN, N.C. A review of passive methods. Presented at Los Alamos Scientific Laboratory Symp. Nuclear Safeguards, Oct. 27-9, 1969.
- SASTRE, C. The use of seals as a safeguards tool. Informal Report BNL 13480.

National Neutron Cross Section Center

S. PEARLSTEIN

SCOPE OF ACTIVITIES

The scope of the National Neutron Cross Section Center's (NNCSC) activities includes the following:

(1) Acquisition, storage, and retrieval of experimental neutron cross section data obtained through the cooperative efforts of USAEC laboratories, the International Atomic Energy Agency, and the European Nuclear Energy Agency, as well as through bilateral agreements with other countries.

(2) Compilation and dissemination of evaluated neutron reaction cross section data received from cooperating organizations.

(3) Evaluation, systematization, and dissemination of data sets covering materials required for reactor calculations, and coordination of cross section evaluation activities through working arrangements with other laboratories.

(4) Development of new methods of cross section analysis.

As a regular service to users the NNCSC answers inquiries for tabulated data for specific cross section requests, with output in tape, printed listing, or graphically displayed form. In addition, the NNCSC acquires and distributes, on request, computer programs associated with cross section libraries that are developed and maintained by both NNCSC personnel and other reactor physics groups.

GENERAL

The NNCSC served as BNL host to a Panel on Neutron Data Compilation held at Brookhaven National Laboratory, February 10-14, 1969, and sponsored by the International Atomic Energy Agency. Thirty-two participants drawn from twelve countries attended, including representatives of the world's principal neutron data centers [NNCSC (USAEC), Saclay (ENEA), Vienna (IAEA), and Obninsk (USSR)] as well as data center users. The Panel's conclusions and recommendations, although concerned with general policy rather than technical detail, should serve

to stimulate the efforts of the principal data centers to reach agreement on the many technical questions involved in their cooperative and exchange programs and lead to the provision of better service for the Center's users.

A Digital Equipment Corporation PDP-10 computer has been installed at the NNCSC. The new computer will improve the accuracy and reliability of the Center's data files. Software acceptance tests for the PDP-10 (without discs) were completed on October 1, 1969, and the computer was officially accepted at that time. Utility programs which have been operational on other machines are now being transferred to the PDP-10. The addition of interactive graphics equipment is planned to facilitate the evaluation of neutron data.

Cross Section Compilation Activities

M. GOLDBERG

The effort to merge all usable data from the old Sigma Center files into the NNCSC's computer library of experimental data has been completed. All new data being so merged are going through the author-proof system. Author proofs consist of a listing and plot of data as entered into the library that are then sent to the measurer for his approval. First reactions have been gratifying, and a few small errors in the system noted by experimenters have been corrected.

Specifications have been completed for a format to allow transmission of nuclear cross section information among the four neutron cross section data centers (NNCSC, Saclay, Vienna, and Obninsk). This format is designed to allow a large variety of bibliographic and data information to be transmitted in an easily machine-readable format common to the four centers (for checking and indicating possible errors) and as such has not been optimized for subsequent processing and retrieval. All new data received at the NNCSC are now being entered in the transmission format. In addition, these data are being entered concurrently into the

Figure 1. CALCOMP output for natural calcium produced from EXEDRAN program.

Cross Section Evaluation Activities

M. DRAKE

EVALUATED NUCLEAR DATA FILE

NNCSC's existing system for experimental neutron data (SCISRS-I). An in-house procedures manual for the entering of data into the transmission format is being evolved.

Documentation of the various programs and subroutines comprising the new version of the NNCSC's experimental neutron data system (SCISRS-II) has proceeded rapidly, and the initial working versions are already available for use. Improvements and modifications of these programs are being made based on the Center's experience in operating them. (See Computer Applications for more detail.)

A three-dimensional CALCOMP plotting program (EXEDRAN) has been written for use in displaying differential cross section vs angle vs energy in a new computer-produced edition of BNL 400, *Angular Distributions in Neutron-Induced Reactions*, a sample of which is shown in Figure 1. Production runs have begun producing final usable CALCOMP output for this project, and program EXEDRAN has been merged with the BNL 400 production programs.

M. GOLDBERG, S. MUGHABGHAB,
L. STROMBERG, U. SCHULZE, D. GARBER,
V. MAY, H. BAUMAN

Initial specifications have been defined for a code that will be used to perform physics checks on data in the evaluated neutron cross section data system (ENDF/B). These specifications will serve as the basis for developing the first version of the PSYCHE code. A memorandum has been written that describes the various checking procedures, and this memo will be distributed for review and comment to BNL and Cross Section Evaluation Working Group people to whom the material is pertinent.

As a part of the physics checking effort, the calculation of the infinite dilution resonance integrals for isotopes and elements in the ENDF/B library has been completed. Comparisons will be made between the calculated resonance integrals and the experimentally measured resonance integrals (or evaluated resonance integrals).

A computer program is being written that performs numerical checks on the ENDF/B library data. (These checks will supplement those that are built into the existing CHECKER code.) In particular, checks are performed to see whether impossible data are given in File 2 for the resolved and unresolved resonance parameters. Also the total resolved

resonance widths are being tested against the sum of the partial widths. It is interesting to note that a number of errors were detected as a result of testing the File 2 data on several ENDF/B library tapes. This computer code is being extended to perform checks on the File 3 data (smooth cross sections). In this case the total cross section is being tested against the sum of the partial cross sections. Additional checks, such as those testing the nonelastic cross section against the sum of its partial cross sections, are also being made.

The series of computer codes that were developed for the "author proofs" of experimentally measured cross section data (reported under Cross Section Compilation Activities) are being modified so that they can be used to include graphical displays for evaluated data (from the ENDF/B library) as well. Thus far, a number of these graphical displays have been obtained for the nuclides currently being re-evaluated, and it is expected that these techniques will be used to document the revised data sets obtained by the Task Force on Fissile and Fertile Materials (reported elsewhere in this Section).

Data revisions have been recommended for non-fissile materials that include deuterium, carbon, sodium, boron-10, iron, nickel, chromium, tungsten, and tantalum. In some cases the data problems are small, and corrective actions can be made within the next two months. In other cases complete re-evaluations appear to be necessary, and these data sets will be obtained as soon as possible.

Revised data sets were recommended for the major fissile and fertile nuclides (i.e., ^{235}U , ^{238}U , ^{239}Pu , ^{240}Pu , and ^{241}Pu) by the Data Testing Subcommittee during the September 1968 meeting of the Cross Section Evaluation Working Group. This recommendation was based on results from the Phase-II data testing program, knowledge of the availability of new and significant experimental data, and the realization that a data set produced by one laboratory was sometimes inconsistent with known ratios to a data set produced by another laboratory. The latter point could be corrected by a simultaneous evaluation of fissile and fertile materials by a single group of evaluators. However, it appeared that this work could be better accomplished by a group composed of both experimentalists and evaluators, who could pool their knowledge and experience in order to insure that the revised data sets would be both internally and externally consistent (i.e., the partial cross sec-

tions for any one material would be consistent with the total cross section; also that the ratios between cross sections of different materials would be consistent with what is experimentally known about the ratios).

In order to meet these objectives, a special Task Force on fissile and fertile cross sections was selected by S. Pearlstein (BNL), M. Drake (BNL), and W. Davey (Argonne National Laboratory). This Task Force met twice during the summer of 1969 at BNL and effected a plan whereby the data set revisions needed immediately were prepared and provision made to perform the necessary long-term calculations and experiments. These revisions include recent cross section measurements and are to be incorporated in a revised version of the ENDF/B library that is now being prepared.

M. DRAKE, M. BHAT, T. STEPHENSON,
B. MAGURNO, D. CULLEN, U. SCHULZE,
E. OTTEWITTE, A. LIVOLSI

OPTICAL MODEL CALCULATIONS

All of the model calculations for ^{238}U , ^{239}Pu , ^{240}Pu , and ^{241}Pu have been completed. This work was done as a part of the effort to obtain revised cross sections for the fissile and fertile materials. The method of analysis involved using coupled-channel theory for the direct excitation of rotational levels in these deformed nuclei. The compound nuclear reactions were calculated in terms of a Hauser-Feshbach-type analysis. These results are being converted to the ENDF/B format.

In ^{238}U and ^{240}Pu the 0^+ , 2^+ , and 4^+ levels were coupled, and the total cross sections obtained were within 1 to 2% accuracy also in the total cross sections over an energy range of 0.01 to 15 MeV. These results mark a decided improvement over calculations where a spherical potential was employed. The potential scattering and direct excitation have also been completed for these isotopes. The s - and p -wave strength functions have also been calculated, and the agreement is within experimental accuracy. Efforts are now under way to carry out similar calculations for ^{241}Pu .

The compound nucleus reaction cross sections have also been calculated for ^{238}U , ^{240}Pu , and ^{239}Pu using the ABACUS code. While the agreement with experimental data is within 5 to 10%, a correction for the competitive fission mode should increase the accuracy to within 2 to 3% of the accepted experimental data.

A. PRINCE, P. TU

IRON CROSS SECTION

Resonance parameters selected from the literature and from values compiled and recommended in BNL 325 were used as the starting point in fitting the total neutron cross section data to a Breit-Wigner multilevel scattering and single-level capture formula. The value chosen for the effective scattering radius is 6 f. Two bound levels, one each for ^{54}Fe and ^{56}Fe , were required to fit the total cross section data and to match thermal capture data. The parameters for the bound levels are as follows:

	E_0 , keV	Γ_n^0 , eV	Γ_γ , eV
^{54}Fe	- 15	≈ 41.45	≈ 3.33
^{56}Fe	- 4	≈ 7.58	≈ 1.05

T. STEPHENSON

COBALT CROSS SECTION

Resonance parameters selected from the literature and from values compiled and recommended in BNL 325 were used as the starting point in fitting the total neutron cross section data to a Breit-Wigner multilevel scattering and single-level capture formula. The addition of two bound levels, one for each s -wave spin state, was necessary to give agreement with capture and scattering polarization measurements. The bound levels contribute 10.3 b to the calculated value, 37.2 b, of the capture cross section at 0.0253 eV (experimental, 37.1 b). The calculated value of σ_{coh} (1.22 b) is in only fair agreement with the experimental value (1.0 b). The calculated value of the capture resonance integral (72.5 b) is in good agreement with experimental values. Bound level parameters are as follows:

	E_0 , eV	Γ_n^0 , eV
$J=3$	-400	1.68
$J=4$	-250	0.0994

A radiation width of 0.4 eV has been used for those levels where no measurement has been made. The value of the effective scattering radius is 6.5 f.

T. STEPHENSON

Computer Applications

D. CULLEN

SCISRS-II SYSTEM

Experience with the original version of the NNCSC's experimental neutron data system

(SCISRS-I) has demonstrated the need to distinguish between the data base (library) and the programs that maintain and manipulate the data base. Therefore, the new version of this automated system (SCISRS-II) was considered to be composed of two major components:

Table 1

MAHDI System-Related Programs and Their Functions

Overlay	Name	Task description
(0,0)	EXEC	Maintains the current status and content definition of the ELCID system. Transfers this information and control to any of the five linking programs.
(1,0)	NEW	Controls the flow and format checking of new information entered into the data base and prepares author proofs of the information. All information that passes the format check will be entered into the LIMBO file.
(2,0)	UPDATE	Controls the flow of information from the LIMBO file to the LIBRARY. This is the <i>only</i> link that actually operates on the LIBRARY to accomplish changes of the current information content (e.g., insertions, corrections, or deletions).
(3,0)	ALTER	Controls the alteration process (e.g., insertion, correction, and/or deletion). The altered set is written on the LIMBO file, the original set in the LIBRARY is unchanged, and author proofs indicating alterations are prepared. If the altered set is correct, the original set in the LIBRARY may be replaced by the altered set during a subsequent UPDATE run. Alternatively, the altered set may be deleted from LIMBO if the alteration was not correct (in this case the original set in the LIBRARY is unaffected and the correct alterations may be performed on it).
(4,0)	FETCH	Controls the flow of information from the LIBRARY to the user. The information may be supplied to the user in a number of forms (listings, tapes, plots, etc.). This link thus constitutes the system/user interface and will expand to meet the needs (not desires) of the users.
(5,0)	GØØF	Handles all error messages from the MAINLINE system and indicates to the EXEC program the subsequent procedure to follow (e.g., continue processing, terminate, skip remaining input to a link, etc.).

Figure 2. Diagram of MAINLINE system.

(1) ELCID – The Experimental Library of Cross Section Information and Data. This component consists of the data base and supporting hard copy publications (e.g., data tapes or listings, plots, new editions of BNL 400, etc.).

(2) MAHDI – The Machine Access Handlers for Data and Information. This component consists of the software system that supports ELCID, including all documentation (e.g., program tapes or listings, users' manuals for the software, etc.).

MAHDI SYSTEM

MAHDI is divided into a number of subcomponents (programs), where each subcomponent performs a specific task. These subcomponents are grouped into two major categories, MAINLINE and UTILITY.

The MAINLINE subcomponents (programs) constitute the heart of the MAHDI system, and all necessary library functions are performed by these subcomponents, as defined in Table 1. All MAINLINE subcomponents run under the control of an executive program as a single system. This executive program (EXEC) exercises control over the other MAINLINE programs, since it decides not only

which link to execute next (based on input cards) but also whether the operations performed in the last link were successfully completed (i.e., no error condition arose during processing) and should be allowed to effect the current status of the system. A diagram of the MAINLINE system is shown in Figure 2.

The UTILITY subcomponents perform necessary bookkeeping or application functions in support of ELCID. Each UTILITY subcomponent operates as an independent program to accomplish its assigned task (e.g., daily system active and status reports, preparation of ELCID publications, application programs, etc.). The UTILITY subcomponents thus constitute an open-ended library of programs to support ELCID. When it is felt that a UTILITY subcomponent has become an integral part of the system, the subcomponent may be added to the MAINLINE category by including it under the control of the MAINLINE executive program.

INITIAL OBJECTIVES

The initial MAINLINE system operates on a BCD library similar to the Center-to-Center transmission format (reported under Cross Section Com-

Figure 3. Example of technique used for automatically expanding portions of a plot.

pilation Activities). Input of new information is accepted in this format; UTILITY programs will be developed (when necessary) to handle other formats. Output is supplied in the transmission format (tapes), CALCOMP-835 plots, and an interpreted listing format. The alteration process (ALTER link) is performed on a record basis using the Center-to-Center transmission format conventions.

GRAPHICS DEVELOPMENT

Extensive graphics tools have been developed to facilitate cross section compilation and evaluation. The BNL CALCOMP-835 Cathode-Ray Tube (CRT) device is used to produce 35-mm film records of data that can be used for rapid perusal of large volumes of data as well as direct copy for publication. The simultaneous display of ENDF/B evaluated data and SCISRS experimental data is used to assist the re-evaluation of the ENDF/B library. Plotting techniques to expand complex portions of data displays—similar to the action of a zoom lens in photography—have been developed. Figure 3 illustrates one such method.

D. CULLEN, W. KROPP

Cross Section Theory

T. KRIEGER

The connection between the "channel radius" and "potential scattering radius" as applied to cross section fitting techniques was analyzed. These two quantities are currently assumed to be equal in ENDF/B evaluation formulas. Actually they are different because of the influence of distant resonances on the scattering between resonances. It has therefore been recommended that they be treated as distinct parameters. The channel radius should be calculated from the well-known $A^{1/3}$ law for nuclear radii, while the potential scattering radius is to be taken from experiment.

Some progress has been made in the derivation of a time-dependent analysis of compound nucleus decay in the continuum region. The approach consists of setting up a wave packet in the "interior region" of the nucleon configuration space. The time development of this wave packet is obtained in the usual way from the "effective" Hamiltonian in the interior region. This Hamiltonian contains

a component that is rapidly varying with energy, which we assume to be random. Upon averaging the wave packet over a suitable ensemble of random Hamiltonian matrices, we find that the decay of the wave packet is exponential.

The lack of agreement in the literature as to the connection between the transmission coefficient T and $2\pi\langle\Gamma\rangle/D$ when the latter is ≈ 1 has been traced to the different possible meanings associated with Γ and D . These resonance parameters may be associated either with poles of the S matrix or with poles of the R matrix, the particular choice determining the form of the connection between T and Γ/D .

Publications

- BHAT, M.R., CHRIEN, R.E., GARBER, D.I., AND WASSON, O.A. Use of the HFBR fast-neutron chopper to measure half-lives of isomeric states populated by neutron capture. (A) *Bull. Amer. Phys. Soc.* **13**, 1422 (1968).
- BEER, M., GRAVES, R., WASSON, O.A., BHAT, M.R., MUGHABGHAB, S.F., RIMAWI, K., GARBER, D.I., AND CHRIEN, R.E. The statistics of neutron resonance partial widths. (A) *Ibid.*, 1421.
- CHRIEN, R.E., WASSON, O.A., BHAT, M.R., MUGHABGHAB, S.F., GARBER, D.I., BEER, M., AND LONE, M.A. Resonant and non-resonant neutron capture experiments at the high flux beam reactor. In *Proc. IUPAP-IAEA Int. Symp. Nuclear Structure, Dubna, USSR, July 1968* (in press).
- GOLDBERG, M.D. The specification and characterization of neutron data. In *Neutron Data Compilation - Report of a Panel Held at Brookhaven 10-14 February 1969, Informal Report IAEA-111*, pp. 107-25, 1969.
- GOLDBERG, M.D. AND HARVEY, J.A. Neutrons. In *American Institute of Physics Handbook*, 3rd Ed., Chap. 8, McGraw-Hill, New York (in press).
- GOLDBERG, M.D. AND HOOTON, B.W. Coulomb excitation of ^{45}Sc . *Nucl. Phys.* **A132**, 369-73 (1969).
- GOLDMAN, D.T., ALINE, P., SHER, R., AND STEHN, J.R. 2200-m/sec neutron absorption cross sections. (A) *Bull. Amer. Phys. Soc.* **13**, 1422 (1968).
- JOLLY, R.K., GOLDBERG, M.D., AND SENGUPTA, A.K. Collective 2^+ and 3^- excitations in Ni and Zn isotopes via inelastic deuteron scattering. *Nucl. Phys.* **A123**, 54-64 (1969).
- JOLLY, R.K., GOLDBERG, M.D., AND SENGUPTA, A.K. DWBA and the 3.12 MeV state in ^{60}Ni . *Phys. Letters* **28B**, 546-7 (1969).
- LONE, M.A., CHRIEN, R.E., WASSON, O.A., BEER, M., BHAT, M.R., AND MUETHER, H.R. Resonant and non-resonant capture of slow neutrons in $\text{Tm}^{169}(n,\gamma)\text{Tm}^{170}$. *Phys. Rev.* **174**, 1512-24 (1968).
- MOORE, S.O. *Optical Model Analysis of the Elastic Scattering of Neutrons by the Lead Isotopes and Bismuth at 0.5, 1.0, and 2.5 MeV*. BNL 50151 (T-520), Oct. 1968.
- MUGHABGHAB, S.F. AND CHRIEN, R.E. Neutron cross sections and resonance parameters of Yb isotopes. *Phys. Rev.* **174**, 1400-8 (1968).
- MUGHABGHAB, S.F. AND CHRIEN, R.E. S-wave neutron strength functions of the Gd isotopes. *Ibid.* **180**, 1131-8 (1969).
- MUGHABGHAB, S.F., GARBER, D.I., CHRIEN, R.E., AND WASSON, O.A. Neutron capture γ rays from Pr^{142} . (A) *Bull. Amer. Phys. Soc.* **14**, 514 (1969).
- MUGHABGHAB, S.F., GARBER, D.I., WASSON, O.A., AND CHRIEN, R.E. Resonant neutron capture in Te. (A) *Ibid.* **13**, 1390 (1968).
- National Neutron Cross Section Center. ENDF-110. *Description of the ENDF/B Processing Codes CHECKER, CRECT, DAMMET, PLÖTFB, and Retrieval Subroutines*. Informal Report BNL 13582.
- PEARLSTEIN, S. The Evaluated Nuclear Data File and the Cross Section Evaluation Working Group - background and status report. In *Proc. RSIC and Neutron Physics Division Seminar-Workshop, Oak Ridge National Laboratory, Oct. 1-3, 1969*, ORNL-RSIC-27, 1969 (in press).
- PRICE, D.L., CHRIEN, R.E., WASSON, O.A., BHAT, M.R., BEER, M., LONE, M.A., AND GRAVES, R. Neutron capture in ^{238}U . *Nucl. Phys.* **A121**, 630-54 (1968).
- PRINCE, A. Nuclear and physical properties of Cf^{252} . In *Proc. Symp. Californium-252, New York, Oct. 1968*, pp. 23-130, James J. Barker, Editor, CONF-681032, 1969; BNL 50168 (T-530), April 1969.
- STEPHENSON, T.E. The total neutron cross section of cobalt below 30 keV. (A) *Bull. Amer. Phys. Soc.* **14**, 190 (1969).
- STEPHENSON, T.E. AND POPEK, J. The total neutron cross section of iron below 100 keV. (A) *Ibid.* **14**, 858 (1969).
- WASSON, O.A., CHRIEN, R.E., BHAT, M.R., LONE, M.A., AND BEER, M. Direct neutron capture in $\text{Co}^{59}(n,\gamma)\text{Co}^{60}$. *Phys. Rev.* **176**, 1314-22 (1968).
- WASSON, O.A., CHRIEN, R.E., LONE, M.A., BHAT, M.R., AND BEER, M. Resonance neutron capture in $^{181}\text{Ta}(n,\gamma)^{182}\text{Ta}$. *Nucl. Phys.* **A132**, 161-76 (1969).

Evaluation and Technical Assistance Group

C.J. RASEMAN

PUMPED STORAGE POWER SYSTEMS

A study of the potential of hydroelectric pumped storage power used in conjunction with nuclear base load stations in U.S. power generation was started. The study will incorporate descriptions of proposed and operating systems, projected market outlook, and operating characteristics and unique features of the system. The effect of pumped storage on plant capacity factors will be investigated. The features of the pumped storage system are being assessed.

This type of power peaking plant is unique in that it depends upon *other* power sources for its energy supply. Therefore, combining nuclear steam generation with pumped storage is very attractive, since it leads to an improved plant factor for the nuclear base-load plant while at the same time it utilizes its low incremental cost of power to store energy. The only significant cost of the required pumping energy is for the fuel consumed in the reactor. Thus, overall fuel supplies are effectively conserved by the ability to store the output of the best generation units.

As improvements in developing nuclear plants occur, the cost of pumping energy for a pumped storage plant *decreases*. While other types of peaking plant depreciate and become obsolete, the pumped storage plant tends to become *more* efficient. A breakthrough in power generation, such as the introduction of breeders or the development of MHD generators, which would significantly affect energy costs, can be readily passed on to pumped storage units, including those already in operation.

The pumped storage plant is essentially an energy accumulator, storing the equivalent of steam-generated energy in a headwater pool. The plant uses relatively cheap energy generated in the most efficient fossil- or nuclear-fueled thermal plants during low-demand periods to pump water into a high-elevation reservoir where it is stored temporarily. During periods of peak demand, the stored water is released to produce more valuable hydro-power as it falls back to a lower reservoir.

Pumped storage plants are becoming an important source of peaking capacity, especially in the Northeast Power Region. Eight pumped storage plants with a total power of 1800 MW(e) are in operation in this country, while seven projects totaling 2200 MW(e) are under construction. Proposals for 5 additional projects with 6600 MW(e) capacity are currently before licensing boards. Some 120 other sites with a total power of $>70,000$ MW(e) have been found to be satisfactory for future use.

OPERATING AND MAINTENANCE COSTS

A study is under way to determine and evaluate operating and maintenance (O&M) costs for nuclear power plants. This involves a review and comparison of the O&M cost data for the various reactor systems being assessed by the Division of Reactor Development and Technology (RDT) and of fossil-fueled plants; identification of the unique features of each reactor system influencing O&M costs; and an investigation of the variation of O&M costs over the 30-yr life of the reactor plant.

O&M costs represent the smallest of the three major subdivisions comprising the total cost of electric power and capital and fuel costs the others. In fossil-fueled plants, O&M costs account for an average of only 15 to 22% of the total production costs, fuel costs accounting for the remainder. O&M costs account for an estimated 15 to 24% of the production costs of power produced by light water (LWR), high temperature gas-cooled (HTGR), gas-cooled fast (GCFR), and steam-cooled fast (SCBR) reactor systems, and $\approx 50\%$ for the liquid metal fast breeder (LMFBR) and molten salt breeder (MSBR) reactor systems. Similarly, the O&M costs of all these systems represent 7 to 9% of the total cost of electric power, except for the MSBR with 12%. However, even though plant maintenance constitutes only a very small percentage of the total production cost, the cost of power purchased by the utility while the generating plant is out of service for maintenance may amount to more than the overall costs of the repairs.

The data for 15 nuclear stations were analyzed to relate the size of the staff to net plant capacity. The net electrical capacity ranged between 185 and 1630 MW(e), and the total staff between 47 and 198.

The most efficient usage of manpower is expected to be attained by a 2-unit, 1630-MW(e) station with a total crew of 87 men or 0.0534 man-yr/MW(e). The total staff utilization then decreases with decreasing rated plant capacity. While the total staff remained at an average of 64 men for plants between 450 and 1000 MW(e), the ratio of man-yr/MW(e) increased from 0.0827 for plants between 600 and 1000 MW(e) to 0.1294 for plants between 450 and 600 MW(e). In the 200-MW(e) range, the staff increased to 80 men or 0.414 man-yr/MW(e).

The annual cost of consumable supplies and equipment for nuclear plants was estimated to be \$600,000, regardless of the type of reactor system, in the AEC task force evaluations of advanced converter and alternate coolant fast breeder reactors. Only the MSBR has a higher cost (\$1,065,000) presumably because of the operating and maintenance problems caused by a circulating fuel. The cost (\$200,000) estimated for an LWR in the task force evaluation of light reactors appears to be too low. This value is only in the range of a 200-MW(e) LWR in the revised AEC cost evaluation guide.

Total O&M costs for nuclear plants, although still incomplete, appear to cluster in two regions: 0.24 to 0.30 mill/kWh for LWR, HTGR, GCFR, and SCBR systems, and 0.34 to 0.38 mill/kWh for the MSBR and LMFBR systems.

The 1966 FPC survey of fossil-fueled plants generating 95% of the total U.S. power showed that the total O&M costs have decreased by 16%, from 0.87 to 0.73 mill/kWh in the 10-yr period ending in 1966. While the maintenance costs decreased

by only 0.03 to 0.36 mill/kWh in that period, operating costs dropped 0.11 to 0.37 mill/kWh. The ratio of operating to maintenance costs decreased from 1.26 to 1.03. At the same time, the ratio of O&M costs to the total production costs has remained essentially constant at 0.226 for the entire period.

CODES AND STANDARDS DEVELOPMENT

BNL is participating in the development of codes and standards applicable to the reactor field, as part of an AEC-sponsored program at ORNL and Atomic International Liquid Metal Engineering Center (LMEC). The ORNL work involves the consolidation of current power technology and engineering practices and the development of basic standards for AEC-owned water reactors. This work will also help define the existing technological base upon which advanced development programs will be built. A similar effort at the LMEC involves standards applicable to the LMFBR program.

Detailed comments on some 18 standards have been submitted. In addition, a revised set of 62 previously issued standards was reviewed. Comments on a draft ASME code for pumps and valves for use in nuclear application were submitted to the AEC. A draft standard for purchasing of small quantities of fissile material and an ISO specification on sealed nuclear energy sources was reviewed for USA Standards Institute.

Publications

SUSSKIND, H., ODETTE, R., AND BECKER, W. Controlled removal of spheres from a geometrically ordered packed bed by surface fluidization. In *Fluidization (Proc. Symp., Los Angeles, Dec. 1968)*, A.I.Ch.E. Symp. Ser. (in press).

Chemistry Division

R.H. WISWALL, JR.

Physical Organic Chemistry

FLUOROCARBON CHEMISTRY

Decomposition Kinetics

In order to understand the relative thermal instability of perfluorobicyclohexyl, one must know its decomposition kinetics accurately. Because of radical attack on the parent molecule during pyrolysis between 340° and 385°C, measurement of its rate of disappearance is not a measure of its rate of unimolecular decomposition. We have found that Cl₂ scavenges radicals rapidly enough that only a very small fraction undergo reaction with each other or with parent molecules, thus permitting the unimolecular rate constant to be determined unequivocally. A detailed study is be-

ing carried out in the temperature range 340° to 370°C. Preliminary values of the rate constant are shown in the Arrhenius plot of Figure 1. The plot gives an Arrhenius activation energy of 67.0 kcal/mole and a frequency factor of 10^{17.7} sec⁻¹ for the unimolecular reaction

The activation energy for a reaction of this type is essentially the same as the bond dissociation energy of the C—C bond being broken, since the activation energy of the back reaction (radical combination) is small or zero. Hence the strength of the bond joining the two perfluorocyclohexyl rings is ≈ 67 kcal/mole, which is relatively strong. Barlow and Tatlow (*J. Chem. Soc.* 1952, 4695-8) have suggested that some types of bonds between two tertiary C atoms are more readily broken than bonds involving primary and secondary C atoms. This is borne out in the case of perfluorobicyclohexyl; however, the reason is not that the bond between the tertiary C atoms is weak, but that the frequency factor of the decomposition reaction is very high.

In order to gain further insight into the question of the possible weakness of bonds between tertiary C atoms, we have begun kinetic studies with perfluoro-2,3-dimethylbutane, the simplest molecule with such a bond. The compound was prepared by an Ullman reaction of perfluoroisopropyl iodide with activated copper bronze powder. Product yield was $\approx 60\%$ at 200°C. Use of Cl₂ as a radical scavenger in pyrolysis of the 2,3-dimethyl butane has been shown to permit determination of rate constants for the unimolecular decomposition

These will be determined at a series of temperatures in order to determine Arrhenius activation energy and frequency factor as in the case of perfluorobicyclohexyl.

Figure 1. Rate of thermal decomposition of perfluorobicyclohexyl as a function of temperature.

The decomposition of perfluoro-2,3-dimethyl butane without additives (scavengers, energy transfer agents, etc.) is being studied in order to help determine the nature of radical-radical reactions in fluorocarbon systems. The isomerization of perfluorocyclohexyl radicals to perfluoromethylcyclopentyl radicals and the following disproportionation reactions of the latter have already been reported.

Reaction (4) corresponds to the normal type of disproportionation in hydrocarbon systems where a hydrogen is transferred, yielding an alkane and an olefin. Reaction (3), representing transfer of a CF_3 group between radicals, had not been reported previously.

We now have good evidence for CF_3 -transfer between perfluoroisopropyl radicals [Reaction (5)] at temperatures around 400°C , but little or no regular disproportionation occurs to form perfluoropropane and perfluoropropene [Reaction (6)].

Reaction (6) does occur to a small but significant extent at 450°C . Other workers have found no evidence for disproportionation of perfluoroalkyl radicals at temperatures up to 250°C . This work confirms their conclusions and shows that the reaction only becomes significant at temperatures above 400°C . D. MacKENZIE, F. BLOCH, V. WILSON,

R. SMOL, W. BROWN

Vapor-Phase Fluorination With XeF_2

We previously reported [BNL 50082 (S-70)] the very smooth and efficient addition of two fluorine

atoms to perfluoronaphthalene when vapor of the latter was heated with XeF_2 vapor at temperatures in the ranges of 100 – 200°C . Recently Hyman, Shaw, and Filler [*J. Amer. Chem. Soc.* **91**, 1563 (1969)] have shown that XeF_2 fluorinates the hydrocarbon benzene smoothly in CCl_4 solution to yield substitution products. Carrying out preparative organic reactions without a solvent can be an advantage, so we have investigated the vapor phase reaction of XeF_2 with benzene and several benzene derivatives: *p*-difluorobenzene, 1,2,4,5-tetrafluorobenzene, and nitrobenzene. Our results show that substitution products can be obtained by this method as well.

Reagents were transferred using a metal vacuum system and reactions were carried out in fluorinated nickel or Monel containers. Typically 1 to 2 millimoles of organic and a similar amount of XeF_2 were reacted overnight in a vessel of 150-cc volume at temperatures from 100° to 200°C . After the reaction period, the vessel was cooled to -78° and HF and Xe were pumped off. The organic products and unused starting material were transferred under vacuum to a glass container and analyzed by GLC. Chromatographic fractions were collected for identification by IR and mass spectrometry.

Under the above conditions, nitrobenzene was substituted readily to form *p*-, *o*-, and *m*-fluoro-nitrobenzenes. The ratio depended somewhat on temperature, but *meta* always predominated. The benzene itself was fluorinated to the monofluoro stage when the mole ratio $\text{XeF}_2:\text{C}_6\text{H}_6$ was below 0.2. With mole ratio 2.2, however, yield of difluorobenzenes was roughly equal to that of fluorobenzene, and a small amount of 1,2,4-trifluorobenzene was also formed. The relative yields of the difluorobenzenes were in the ratio of $\approx 20:1:1$ for *p:o:m*. Yields of addition products were negligible at the low mole ratios of $\text{XeF}_2:\text{C}_6\text{H}_6$. At high mole ratios (>2) addition products became appreciable, but were still small compared with the substitution products.

As the degree of substitution of the starting compound increased, however, addition reactions became predominant. With *p*- $\text{C}_6\text{H}_4\text{F}_2$, reasonable yields of trifluorobenzenes and a small yield of 1,2,4,5-tetrafluorobenzene, together with relatively large amounts of addition products (unidentified), were obtained. With 1,2,4,5-tetrafluorobenzene, no *penta*- or *hexa*-fluorobenzene could be detected in the products.

Figure 2. ESR spectra of (a) MgOEP^+ and (b) MgOEP^+-d_4 in CH_3OH at -50° . Dashed lines represent computer simulations: 1.5-G line width, Gaussian line shape, and four equivalent hydrogens, $a_{\text{H}} = 1.48$ G for (a) and four equivalent deuteriums, $a_{\text{D}} = 0.227$ G for (b).

Figure 3. ESR spectra of ZnTPP^+ in butyronitrile: (a) characteristic nine lines obtained at room temperature; (b) -54° ; (c) computer simulation of (b); four equivalent nitrogens, $a_{\text{N}} = 1.58$ G and eight equivalent hydrogens, $a_{\text{H}} = 0.316$ G; (d) ZnTPP^+-d_{20} , phenyl groups deuterated, -50° ; (e) computer simulation of (d): 0.67-G line width, Gaussian line shape, four nitrogens, $a_{\text{N}} = 1.58$ G and eight deuteriums, $a_{\text{D}} = 0.049$ G.

We conclude from this work that XeF_2 is an effective vapor phase fluorinating agent for both addition and substitution. With proper choice of conditions, it should be possible to carry out a wide variety of specific substitutions on aromatic rings. While work in solution may be necessary for compounds of low volatility, vapor phase conditions with resultant ease of manipulation will be applicable to a great many substances.

D. MACKENZIE, J. FAJER, R. SMOL

PORPHYRINS

The program on the redox reactions of porphyrins was continued in cooperation with other institutions. The main emphasis has continued to be on the oxidation, by both chemical and electrochemical means, of various metal derivatives of octaethyl porphyrin (OEP) and tetraphenyl porphyrin (TPP). Examples were found of oxidations in which one or two electrons were given up by the organic part of the molecule to yield π cations or dications, of others in which the metal was the source of one or both electrons, and of two-electron oxidations in which one electron came from the metal and the other from the organic ring system.

An electron can be removed from TPP and OEP complexes of Mg, Zn, Cd, and Cu by controlled potential electrolysis or by oxidation with I_2 , Br_2 , Cl_2 , or XeF_2 in nonaqueous solvents. The electron spin resonance (esr) spectra of the resulting cation radicals clearly indicate electron abstraction from the porphyrin ring. For example, the observed hyperfine structure (Figures 2 and 3) is assignable, with the help of deuterium labeling, to interaction of the unpaired electron with the *meso* protons (5, 10, 15, 20 positions) of MgOEP^+ and with the protons on the phenyl groups of ZnTPP^+ . Electronic absorption spectra of the radicals and of the diamagnetic dications (Figures 4 and 5) formed by abstraction of a second electron have been obtained for the above compounds.

The dication ZnTPP^{+2} , which has lost 2 electrons, is a powerful electrophile and reacts with methanol or water to yield a new class of compounds called *isoporphyrins*. The methoxy derivative (Figure 6) has been prepared:

Figure 4. Oxidation of ZnTPP in CH_2Cl_2 : 1, absorption spectrum of ZnTPP; 5, cation radical.

Figure 6. Structural formula of the isoporphyrin: $\text{ZnTPPOCH}_3^+, \text{ClO}_4^-$.

Figure 8. Spectral changes on substituting BF_4^- for Br^- in Co(III)OEP^{+2} .

and its structure was verified by nuclear magnetic resonance.

When metals capable of more than one oxidation state are incorporated into the porphyrin, metal oxidation may occur. For example, Co(II)-TPP and Co(II)OEP are initially oxidized to the corresponding cobaltic species followed by ligand oxidation at higher potentials:

Figure 5. Absorption spectra of dications in CH_2Cl_2 : ZnTPP^{+2} (heavy) and MgOEP^{+2} (light). Dotted lines represent region corrected for the Soret bands of trace diacid salts.

Figure 7. ESR spectrum of Mn obtained by *in situ* electrolysis of Mn(III)OEP^+ in $\text{C}_3\text{H}_7\text{CN}$.

Mn(II)OEP and Mn(II)TPP , on the other hand, undergo two-electron oxidation of the metal to yield Mn(IV)OEP^{+2} and Mn(IV)TPP^{+2} . The difference in behavior is readily ascertained by esr. In Mn(IV)OEP^{+2} and Mn(IV)TPP^{+2} unpaired spin is localized mostly on the metal, as indicated by the values of the hyperfine splitting constants: $a_{\text{Mn}} \approx 95 \text{ G}$ (Figure 7). In the cobalt cases, spin density is transferred from the oxidized rings onto the metal: $a_{\text{Co}} = 5.7 \text{ G}$ and 1.4 G for Co(III)TPP^{+2} and Co(III)OEP^{+2} respectively.

Solvent and gegenion effects have also been observed. $\text{MgOEP}^+, \text{ClO}_4^-$ dimerizes in CH_2Cl_2 :

The equilibrium constant at 0° for the reaction is $4.7(\pm 0.3) \times 10^3 \text{ liter/mole}$. At the same temperature no dimer is formed in methanol. Optical

Figure 9. Adsorption spectra in CH_2Cl_2 of chlorophyll *a* and its cation radical.

spectra of radicals are also influenced by complexing with anions. Figure 8 shows the optical changes due to the transformation of the radical of cobaltic octaethyl porphyrin prepared by Br_2 oxidation when the Br^- is replaced by BF_4^- :

The results of a self-consistent field molecular orbital study are in general agreement with the experimental esr and optical data and, in addition, correctly predict the reactivity of dications which leads to isoporphyrin formation. These calculations also suggest that radicals may occupy nearly degenerate ground states which in turn determine their spectroscopic properties. The ground states of ZnTPP^+ and MgOEP^+ are assigned $^2A_{2u}$ and $^2A_{1u}$ symmetries of the D_{4h} point group.

The properties discussed here are relevant to those porphyrins and related compounds which function in biological systems. An increasing body of data suggests that primary photosynthetic processes involve oxidation of chlorophyll and bacteriochlorophyll. Considering MgTPP or MgOEP as model systems, oxidized chlorophylls are properly characterized as π -cation radicals. Electro-oxi-

dation of ethylchlorophyllide *a* and chlorophyll *a* converts these molecules into bleached species whose optical (Figure 9) and esr properties are consistent with this identification. An additional feature of the magnesium porphyrins is that these molecules are easily oxidized, a fact which may account for the appearance of magnesium chlorins in the photosynthetic apparatus. In the instance of catalase and peroxidase functions, the oxidation of the prosthetic heme group is usually formulated as metal oxidation to yield Fe(IV) and Fe(V) . An alternative, supported by our results, suggests that ring oxidation as well as metal oxidation should be considered.

J. FAJER*

RADIATION EFFECTS ON HALOGENATED COMPOUNDS

Synthetic Blood

Dr. R. Geyer (Harvard School of Public Health) has successfully used fluorocarbon emulsions as blood substitutes in animals. The effects of γ irradiation on these synthetic oxygen carriers are being studied. The appearance of fluoride ion (F^-) is taken as a measure of decomposition of the fluorocarbon, and F^- is determined directly with a fluoride ion selective electrode. Concentrations of F^- produced range from $10^{-4}M$ at 10^4 rads to $2.5 \times 10^{-3}M$ at 10^7 rads at dose rates of 5×10^3 and $\approx 10^7$ rads/hr, respectively.

Decomposition of Herbicides

Chlorinated compounds decompose by radical chain reactions with large G -values under ionizing radiation. This suggests the possible use of high intensity γ irradiation to decompose surplus or unwanted chlorinated compounds such as herbicides and insecticides. Preliminary results on 2,4D (2,4 dichlorophenoxy acetic acid) and commercial 2,4D (isooctyl ester of 2,4D) indicate significant decomposition of the ester and increase in free chloride ion concentrations. The insecticide DDT is also sensitive. J. FAJER, D. MACKENZIE, B. FOX

MOLECULAR SPECTRA AND STRUCTURE

While the particular stable conformation of a small molecule appears in itself to have little bearing on the conformation assumed by a large bio-

*With D. Dolphin, Harvard University, D. Borg, BNL Medical Dept., and R. Felton, Georgia Institute of Technology.

logical molecule, nevertheless the same forces are undoubtedly operative and the complete *a priori* prediction of the latter will only come from a complete understanding of the former. Thus a study of the conformations of small flexible molecules has been initiated with particular attention in the first instance to molecules containing C—C or C—O bonds having partial double bond character and molecules containing normal C—O and C—S single bonds. In the former category methyl pyruvate, $\text{CH}_3\text{COCOOCH}_3$, has been shown to exist in the liquid and vapor phases as a mixture of two isomers: a planar *trans* isomer and a less stable, probably planar *cis* isomer, the former isomer only being present in the crystal. Figure 10 shows the effect of solvent on pairs of infrared bands due to the two isomers in solution; in each case the proportion of the more polar *cis* isomer increases in the solvent of higher dielectric constant as would be expected.

The infrared spectra of a number of phenolic acetates have been reported previously to exhibit multiple absorption bands in the carbonyl region probably because of Fermi interaction of one or more combination tones with the carbonyl fundamental, although the possibility of the coexistence of rotational isomers could not be completely rejected (H. LEE and J. WILMSHURST, *J. Chem. Soc.* 1965, 3590-4). We have now confirmed this conclusion by a study of the infrared and Raman spectra of phenyl acetate, phenyl acetate- d_3 , and phenyl- d_5 acetate. J. WILMSHURST, W. RIEL*

*With J. Horwood, Div. of Dairy Research, CSIRO, Melbourne, Australia, and H. Lee, Dept. of Chemistry, Jalan Sultan, Petaling Jaya, Kuala Lumpur, Malaysia.

Figure 10. The effect of solvent on pairs of infrared bands due to *cis* and *trans* isomers of methyl pyruvate (* = *cis* isomer).

Metal Hydrides

Much of the year's work was devoted to the hydrides of the fifth-group metals, V, Nb, and Ta, and their alloys. Some of these systems exhibit an MH_2 phase of unusually high dissociation pressure, which makes them of interest for hydrogen storage and other applications. Pressure-temperature-composition information was obtained by means of previously described techniques and apparatus, and a few measurements of magnetic susceptibility as a function of hydrogen content were obtained.

VANADIUM-HYDROGEN

It was found that the dissociation pressure of the system $\text{VH}_{0.95}$ - $\text{VH}_{1.95}$ is grossly affected by the presence of impurities in the vanadium starting material. Figure 11 shows a plot of the dissociation pressure vs temperature of $\text{VH}_{1.8}$ (a composition well within the two-phase region of the VH - VH_2 system) which illustrates the results obtained with a high-purity, zone-refined vanadium as the starting material, and a lower purity material (the latter assaying 99.5% vanadium). These curves represent data taken from a large number of pressure-composition isotherms which were determined for each material. In both cases these iso-

Figure 11. Dependence of dissociation pressure of $\text{VH}_{1.8}$ on temperature.

Figure 12. Phase diagram of the vanadium-hydrogen system.

therms were reproducible provided that the starting vanadium came from the same source. In the case of the 99.5% material, it was established that remelting in an arc furnace and annealing does not affect the dissociation pressure. In the case of the zone-refined material, remelting and annealing did increase the dissociation pressure by $\approx 10\%$; however, this may be due to contaminants introduced into the material in these extra operations. In addition, it was noted that with the zone-refined material it was much more difficult to initiate the reaction between hydrogen and the metal than with the lower purity material. Apparently the impurities in the latter acted as a catalyst. After several cycles of sorption and desorption, however, no significant difference was noted in the reaction rates of each material with hydrogen.

A phase diagram (Figure 12) for the V-H system was constructed by combining data abstracted from our results in the $\text{VH}_{0.9}$ - $\text{VH}_{2.0}$ region with those of others who explored the system between the limits V- $\text{VH}_{\approx 0.9}$. The position of the phase boundaries was not affected by purity of the starting material.

NIObIUM-HYDROGEN

The Nb-H system behaves in a manner similar to that of the V- H_2 system. A number of pressure-composition isotherms for the composition region extending from $\text{NbH}_{0.9}$ to $\text{NbH}_{\approx 2.0}$ are shown in Figure 13. The isotherms rise steeply on the left until a composition of $\text{NbH}_{\approx 1.1}$ is reached where the γ hydride phase appears. The $\gamma + \beta$ mixed phase region extends to $\text{NbH}_{\approx 1.9}$ where the isotherm begins a steep ascent indicating the disap-

Figure 13. Uptake of hydrogen by niobium.

pearance of the β phase. It may be noted that the lower temperature isotherms show an appreciable solubility of hydrogen in the γ phase which resulted in hydrogen contents up to a composition corresponding to $\text{NbH}_{2.08}$. This is not a surprising result since others have obtained $\text{NbH}_{2.07}$ via an electrolytic synthesis method and since niobium dihydride is a nonstoichiometric compound, as are other group VA hydrides.

The reaction for the plateau region may be written

A plot of the log of the dissociation pressure vs the reciprocal of the absolute temperature yields a straight line obeying the equation $\log P_{\text{atm}} = (-2090/T) + 6.8662$. From these data, partial molar thermodynamic quantities were calculated for reaction (1):

$$\begin{aligned} \Delta \bar{H}_{298} &= -9.563 \text{ kcal/mole H}_2, \\ \Delta \bar{F}_{298} &= -0.206 \text{ kcal/mole H}_2, \\ \Delta \bar{S}_{298} &= -31.4 \text{ eu/mole H}_2. \end{aligned}$$

Niobium dihydride of a composition corresponding to $\text{NbH}_{1.98}$ has a grey, metallic appearance; it is not pyrophoric and appears to be stable in air. Most of the individual pellets of the sample ex-

Figure 14. Phase diagram of the niobium-hydrogen system.

aminated had retained their original shape, although all exhibited many cracks and fissures. The material was very brittle and could easily be ground into a fine powder. The measured density was 6.7 g/cc. An x-ray diffraction pattern of the material was indexed and the material was determined to have cubic symmetry where $a = 4.53 \text{ \AA}$. This value agrees very well with previous work in which the γ phase was determined to have a face-centered cubic structure where $a = 4.536 \text{ \AA}$.

Unlike vanadium, the source and the purity of starting niobium did not significantly affect the dissociation pressure in the plateau region. However, it was noted that impurities in commercial-grade Nb (99.5% purity) did act as a catalyst in the initial reaction between hydrogen and the metal.

As with vanadium, it is possible to construct a phase diagram of the $\text{NbH}_{\approx 1}$ - NbH_2 system from data abstracted from the pressure-composition isotherms. Such a diagram is shown in Figure 14 where our data are combined with those of others who have constructed a phase diagram for the Nb- $\text{NbH}_{\approx 1}$ system. It is somewhat difficult to place exactly the $\beta(\beta + \gamma)$ phase boundary as determined by the isotherm shape; however, its placement at $\text{NbH}_{1.1}$ is consistent with the earlier work. The $(\beta + \gamma)/\gamma$ boundary, which can be more readily defined, is at $\text{NbH}_{1.94}$ at 39°C and is displaced slightly to the left as the temperature is increased.

TANTALUM-HYDROGEN

There is no report of the existence of tantalum dihydride in the literature nor have we been able

Figure 15. Uptake of hydrogen by tantalum.

to prepare it. Both zone-refined, high-purity tantalum and a lower purity grade (99.5% assay) were used as starting materials. There was no significant difference in results obtained with either material except that, as usual, the less pure material was easier to activate. The maximum hydrogen content attained corresponded to $\text{TaH}_{0.90}$. Several pressure-composition isotherms are shown for this system in Figure 15. No plateaus are evident, which is to be expected at these compositions and temperatures. The upper reaches of the 111°C isotherm curve slightly to the right, perhaps evidence of the existence of a plateau at very high pressures.

NIOBIUM-VANADIUM ALLOYS

It has been found that Nb-V alloys containing $\approx 65 \text{ wt \% Nb}$ and $\approx 35 \text{ wt \% V}$ will react reversibly with hydrogen until the hydrogen-to-metal (H/M) ratio is ≈ 2 . Figure 16 illustrates some pressure-composition isotherms from which several conclusions may be drawn: that $\approx 1/2$ of the total amount of hydrogen is available at low temperatures at moderate pressures, a new phase appears at an H/M ratio of ≈ 1.0 , and a mixed phase region extends at least to an H/M ratio of ≈ 1.8 .

Figure 16. Uptake of hydrogen by niobium-vanadium alloy.

Figure 17. Uptake of hydrogen by tantalum-vanadium alloy (solid solution).

The nature of the new phase has not yet been determined.

TANTALUM-VANADIUM ALLOYS

A pressure-composition isotherm is shown in Figure 17 for the Ta-V-H system. The dissociation pressure is extremely high in the H/M range ≈ 1.0 to 1.8. This isotherm was determined using a Ta-V solid solution containing 65 wt % Ta and 35 wt % V. As in other group VA-hydrogen systems, a pressure plateau appears in the H/M range 1 to 2. The alloy reacts readily with hydrogen initially; however, when the H/M ratio reaches ≈ 1 the reaction proceeds more rapidly if the sample is cooled to $\approx -78^\circ\text{C}$ while exposed to a H_2 gas pressure of ≈ 950 psia.

An interesting aspect of this system is that while Ta-V alloys form a continuous series of solid solutions at the freezing point, the intermetallic compound TaV_2 (also 65 wt % Ta, 35 wt % V) will form from the solid solution at $\approx 1300^\circ\text{C}$. This intermetallic compound was obtained by annealing an alloy of the proper composition at $\approx 1000^\circ\text{C}$ for 16 hr. However, the behavior of this material

Figure 18. Uptake of hydrogen by TaV_2 intermetallic compound.

toward hydrogen was quite different from that of the solid solution, and the maximum H/M ratio attained, despite extended treatment, was only 0.43. A pressure-composition isotherm for this system is shown in Figure 18.

OTHER METAL-HYDROGEN SYSTEMS

Screening tests investigating the action of hydrogen on various alloys and elements were continued. The results of these experiments are shown in Table 1. These materials were exposed to hydrogen under conditions ranging from -196°C to $+100^{\circ}\text{C}$ under a pressure of ≈ 1000 psia and from 100° to 450°C at a pressure of 350 psia.

MAGNETIC SUSCEPTIBILITY

Useful information about the state of dissolved or combined hydrogen in a metal-hydrogen phase

Table 1			
Hydrogen Uptake by Metals and Alloys			
Sample composition, wt %		Phase	Absorbed wt %
Cr	100		0.06
Cr	47	Fe Cr	0.02
Fe	55		
Mg	49	—	0.6
Cr	49		
V	55	V_3Sn	0.3
Sn	44		
V	87	Commercial alloy	1.2
Al	11		
V	81	"	0.08
C	14		
Mo	65	Solid solution	0.3
V	36		
Li	15	—	0.15
Sb	80		
Li	10	LiZn	0.2
Zn	90		
Nb	61	NbCo	0.05
Co	39		
Ni	100	—	0.10
Raney nickel		—	0.17
Al	100	—	0.04

can be obtained from electrical and magnetic measurements. A series of VH_x and NbH_x compositions was prepared (with x ranging in each case from 0 to nearly 2) and their magnetic susceptibilities were determined. The results are shown in Figure 19, which is a graph of susceptibility per gram of metal vs the hydrogen-metal ratio. Some points of interest are that H decreases the paramagnetism much faster in the Nb system than in the V, and that the change in slope occurs at the point where pressure-composition isotherms indicate the appearance of a new phase.

J. REILLY, R. WISWALL, S. ARONSON*

TEMPERATURE SENSOR

It appears possible to utilize the dependence of the dissociation pressure upon temperature of metal hydrides to design and construct sensitive and accurate devices to measure temperature.

In cooperation with the Engineering Division a preliminary experiment was carried out to determine the feasibility of such a device using titanium hydride. A photograph of such a temperature sensor is shown in Figure 20. It consists of a stainless steel bulb at one end containing 1.4 g of $\text{TiH}_{1.3}$ and connected by a length of $\frac{1}{8}$ -in.-o.d. stainless steel tubing to a pressure transducer and

*Present address: Dept. of Chemistry, Brooklyn College, Brooklyn, N.Y.

Figure 19. Magnetic susceptibility in the systems V-H and Nb-H.

Figure 20. Hydride temperature sensor.

a valve fitted with an O-ring connector. The device was connected to a vacuum-gas experimental system and the hydride was prepared *in situ*. The hydride composition was controlled so that it would fall in the plateau region and small changes in the solid composition would not appreciably affect the pressure-temperature relationship. After hydriding, the bulb was cooled to -78°C and evacuated, the valve was closed, and the device was removed from the experimental line. The bulb was inserted into the block of a calibration furnace and a temperature vs pressure curve was established (Figure 21). The points shown on the curve are equilibrium values approached from both directions. There was no evidence of hysteresis and the reproducibility and accuracy of the sensor were within the error inherent in the pressure transducer.

The advantages of such a sensor lie in its ability to determine with great accuracy temperatures within certain ranges and the possibility of constructing reliable and simple hot spot detectors.

J. CHEN, J. REILLY, R. WISWALL, G. SCHOENER

High-Temperature Chemistry

SPECTRA OF MOLTEN SALTS

A novel method of molten-salt spectroscopy involving the scattering of cold neutrons was first described in last year's progress report [BNL 50149 (S-71)]. This work has been continued, but in the High Flux Beam Reactor instead of the Brookhaven Graphite Research Reactor and with the use of a new and improved slow chopper facility. The binary liquid system $\text{ZnCl}_2\text{:KCl}$ was investigated in some detail and preliminary data were obtained for KBr and NaNO_3 .

The results for zinc chloride agree in essentials with those reported last year except that the estimate of the sound velocity at 400°C is now consistent, within experimental error, with the ultrasonic value reported by Gruber and Litovitz [*J. Chem. Phys.* **40**, 13 (1964)]. In liquid potassium chloride the neutron data correlate well with the infrared data available in the literature [*J. WILMSHURST, Ibid.* **39**, 1779 (1963)], and may be simply interpreted on the basis of a quasi-lattice structure having a repetitive two-atom "primitive cell," the three optical modes being assigned in terms of a longitudinal model at $\approx 350\text{ cm}^{-1}$ and a doubly degenerate transverse mode, active in the infrared,

Figure 22. The quasi-elastic peak obtained from the melts of ZnCl_2 , KCl, and KBr compared with that obtained from vanadium. The width of each time channel is $8\text{ }\mu\text{sec}$.

at $\approx 215\text{ cm}^{-1}$; in addition, the sound velocity, determined from the longitudinal acoustic mode, is consistent with the value of 1280 m-sec^{-1} (860°C) determined ultrasonically by Bockris and Richards [*Proc. Roy. Soc. A241*, 44 (1957)].

The question of complex ions in fused salts has long been one of controversy. In the present investigation, pure zinc chloride, potassium chloride, and potassium bromide show no evidence of complex ion formation, i.e., all the observed phonon modes could be explained simply and satisfactorily on the basis of the smallest possible stoichiometric unit. Further, in each of these three melts, there is no evidence, within experimental error, for any broadening of the quasi-elastic peak (Figure 22), whereas if complex ions were present they might be expected to be rotating to some extent, with such rotational motion being observed as a broadening of this quasi-elastic band. Thus, sodium nitrate, which contains a complex or polyatomic ion,

Figure 23. The quasi-elastic peak obtained from molten sodium nitrate compared with that obtained from vanadium.

does indeed show a definite broadening of the quasi-elastic peak (Figure 23), and we tentatively suggest that a simple study of the width of the quasi-elastic peak in the fused salts may provide a quick means for establishing the presence of a complex ion in these systems.

J. WILMSHURST, J. BRACKER

SOLUTIONS OF GASES IN MOLTEN SALTS

The measurements of halogen solubility and diffusion coefficient in molten halides were extended to hydrogen chloride. Its solubility in the $\text{LiCl}_2\text{-KCl}$ eutectic was determined, as a function of temperature, with the technique previously developed. The method, simply stated, is to isolate a known volume of eutectic saturated with HCl , sparge the HCl from the eutectic with argon, and collect the HCl in water for titration with base. Solubility values, expressed as mole fraction HCl , found at three temperatures were as follows: 490°C , 4.11×10^{-5} ; 570°C , 5.05×10^{-5} ; 675°C , 6.31×10^{-5} . A plot of $\log X$ vs $1/T$ is shown in Figure 24. A

Figure 24. Temperature dependence of HCl solubility in LiCl-KCl eutectic.

straight line is obtained from which a heat of solution $\Delta H = 3.5$ kcal can be derived. The solution process is endothermic, like that of chlorine in chlorides, and to about the same extent. The HCl solubility is somewhat greater than that of chlorine.

Diffusion coefficients were obtained by chronopotentiometry with the use of the apparatus and procedures previously described [BNL 50149 (S-71), p. 27]. The indicator electrode was vitreous carbon, a porous graphite rod was the counter electrode, and a platinum foil served as the reference electrode. The electrode reaction which occurred was the reduction of HCl at the vitreous carbon.

Many chronopotentiograms were obtained at 490° and 570°C but attempts to secure meaningful results above 570°C failed because of the softening of the Pyrex glass seal around the vitreous carbon electrode. Diffusion coefficients were calculated for the diffusion of HCl in molten LiCl-KCl eutectic. Each diffusion coefficient obtained is the average of ten or more determinations in each of two or more separate batches of salt. The experimental error can only be estimated, but because of variations between batches of salt, the difficulty of getting exact electrode areas, and the possibility of undetected bubbles, the error is assumed to be $\pm 20\%$. The diffusion coefficients of HCl in the eutectic, D_{HCl} , are $2.4 \pm 0.5 \times 10^{-4}$ cm^2/sec at 490°C and $2.3 \pm 0.5 \times 10^{-4}$ cm^2/sec at 570°C .

These values are an order of magnitude greater than usually found for metal ions in the eutectic, $\approx 10^{-5}$ cm^2/sec . A similarly large value was found

previously for the diffusion coefficient of Cl_2 in molten chlorides. It is also interesting to note that the diffusion coefficient does not increase as a function of temperature, again similar to that for Cl_2 in the eutectic. However, whereas the high diffusion coefficient results for Cl_2 were rationalized in terms of trichloride ion, Cl_3^- , and a chain conduction mechanism, it is difficult to visualize a similar explanation for the D_{HCl} results. It is more likely that the small size of the H^+ ion permits more rapid diffusion through the ionic liquid.

It was impossible to determine from the chronopotentiometric measurements whether the reduction of HCl , or H^+ , proceeds in a reversible manner in the eutectic. Further work is needed to ascertain this fact. J. VAN NORMAN,* R. TIVERS

USE OF F CENTERS IN ALLOY THERMODYNAMIC MEASUREMENTS

The thermodynamic properties of K-Pb alloys are being studied by the following technique. A crystal of KCl is equilibrated with the vapor above the alloy thus producing color centers in the KCl crystal. The color centers have a characteristic absorption spectrum, and the absorption constant at the maximum of the characteristic band is directly proportional to the pressure of potassium in the vapor as first shown by Rögner. The activity of potassium in the alloy at low pressures of potassium is

$$a_{\text{K}} = P_{\text{K}}/P_{\text{K}}^0, \quad (1)$$

where P_{K} is the potassium pressure, P_{K}^0 is the pressure of the pure liquid potassium,

$$P_{\text{K}} = cA, \quad (2)$$

where A is the absorption constant per cm and c is a constant. Also $A = (1/l) \log(I_0/I)$, where l is the crystal thickness in cm.

It follows that

$$a_{\text{K}} = A/A^0. \quad (3)$$

Thus, by measuring the absorption constant of color centers in crystals equilibrated with alloys of various compositions, the thermodynamic properties of the alloy are obtained. The above argument can also be formulated in terms of fugacities where nonideal behavior of the vapor is encountered and therefore the method does not depend upon vapor

*Present address: Dept. of Chemistry, Youngstown State University, Youngstown, Ohio 44503.

Figure 25. Apparatus for equilibrating KCl crystals with K vapor.

composition and has inherent advantages over standard vapor pressure techniques. The experimental arrangement used for the measurements is shown in Figure 25. The entire apparatus is made of stainless steel. KCl crystals are hung in the vapor space. The cover is sealed under vacuum in an induction furnace by melting a silver wire. Such a seal is vacuum tight. The apparatus is then heated in a wire-wound furnace for ≈ 20 hr. The crystals are then polished under kerosene and their spectrum obtained. Figure 26 shows results of absorption constant vs pressure of potassium as verification of Eq. (2).

Results of measurements on K-Pb alloys at 450°C are shown in Table 2 where γ_{K} is the activity coefficient. J. EGAN, J. BOOKLESS

THERMODYNAMIC PROPERTIES OF AgI

The free energy of formation of solid AgI has been determined by operating the cell

at temperatures between 300° and 500°C .

Figure 26. Dependence of optical absorption of KCl crystals on the partial pressure of K vapor to which they have been exposed.

Figure 27. Temperature-emf relation for the cell $\text{Ag(s)} | \text{AgI(s)} | \text{I}_2\text{(g)}(0.1 \text{ atm})$.

Results of emf vs temperature on one such cell are shown in Figure 27. The free energy of formation of AgI calculated from the emf is as follows:

$T, ^\circ\text{C}$	ΔG^0_{AgI}
300	-13,882
350	-13,351
400	-12,821
450	-12,314

These results agree within 50 calories with those previously reported by Hamer.

These measurements were undertaken to help choose the correct values of ΔG^0_{AgI} from several values available in the literature. The correct ΔG^0_{AgI} was necessary in order to obtain $\Delta G^0_{\text{UI}_3}$ from cell measurements of Tveekrem on the cell

J. EGAN, R. WATSON

Table 2

Optical Absorption of KCl Crystals Equilibrated With Potassium Alloys.
(x_K is mole fraction of K in alloy; A/cm is a measure of the optical absorption; a_K and γ_K are the activity and activity coefficient of K, respectively.)

x_K	A/cm	a_K	γ_K
1.00	85	1.00	1.00
0.90	82.5	0.972	1.08
0.80	76	0.893	1.11
0.70	60	0.705	1.01

Publications

- BEHL, W.K. Thermodynamic and transference number measurements in mixtures of molten LiCl-CdCl_2 by e.m.f. method. (A) Presented at Fused Salt Symposium, New York, May 1969.
- BLOCH, F.W. AND MACKENZIE, D.R. Radiolysis of cyclic fluorocarbons. II. Perfluoroaromatics at elevated temperatures. *J. Phys. Chem.* **73**, 552-7 (1969).
- CLARKE, J.T. AND FOX, B.R. Rate and heat of vaporization of graphite above 3000°K . *J. Chem. Phys.* **51**, 3231-40 (1969).
- DOLPHIN, D., FELTON, R.H., BORG, D.C., AND FAJER, J. Isoporphyrins. *J. Amer. Chem. Soc.* (in press).
- FAJER, J., BORG, D.C., DOLPHIN, D., AND FELTON, R.H. Oxidation of porphyrins: Cations and cation radicals. (A) Presented at Amer. Chem. Soc. Meet., Minneapolis, April 1969.
- FAJER, J., BORG, D.C., FORMAN, A., DOLPHIN, D., AND FELTON, R.H. π -Cation radicals and dications of metalloporphyrins. Submitted to *J. Amer. Chem. Soc.*
- FELTON, R.H., DOLPHIN, D., BORG, D.C., AND FAJER, J. Cations and cation radicals of porphyrins and ethyl chlorophyllide *a*. *J. Amer. Chem. Soc.* **91**, 197-8 (1969).
- HEUS, R.J., TIDWELL, T., AND EGAN, J.J. Investigation of the capacity of the electrical double layer in molten chlorides using a dropping metal electrode. In *Molten Salts: Characterization and Analysis*, pp. 499-508, G. Mamantov, Editor, Marcel Dekker, New York, 1969.
- VAN NORMAN, J.D. AND TIVERS, R.J. Solutions of halogens in molten halides. *Ibid.*, 509-27.
- WILMSHURST, J.K. Inelastic scattering of cold neutrons and the vibrational spectra of molten salts. (A) Presented at Gordon Res. Conf., Meriden, N.H., Aug. 25-28, 1969.
- WILMSHURST, J.K. AND BRACKER, J.M. The investigation of fused salts by the inelastic scattering of cold neutrons. In *Molten Salts: Characterization and Analysis*, pp. 291-313, G. Mamantov, Editor, Marcel Dekker, New York, 1969.
- WILMSHURST, J.K. AND LEE, H. The infrared and Raman spectra of phenyl acetate, phenyl- d_5 acetate and phenyl acetate- d_3 . *Austr. J. Chem.* **22**, 691 (1969).

Radiation Division

B. MANOWITZ

Radiation Research

D. METZ

SOLID-STATE REACTIONS

It has been postulated, based on data from reactions between gases and preirradiated crystalline amides, that a large fraction of the trapped free radicals concentrate near crystal defects. Thus anything that alters the relative number of such defects should also change the observed decay rate of the radicals, as measured by ESR. It has been shown that by annealing these crystals before irradiation, or incorporating molecules of a minor impurity constituent (such as propionamide in butyramide), or increasing the radiation dose (thereby producing radiation damage sites), all affect the radical decay rate in the predicted manner.

In the case of irradiated pure butyramide, the rate of radical decay has been studied between 25° and 100°C and appears to follow second-order kinetics. An Arrhenius plot of the data shows two accurately linear portions—that between 25° and 50°C with a temperature coefficient of 14 kcal/mole, and that between 50° and 100°C with a temperature coefficient of 28 kcal/mole. These observations are tentatively explained by a mechanism involving radical migration by hydrogen atom abstraction and the role of defects in increasing the rate of radical decay.

Solid solutions of butyramide and propionamide, when irradiated, also exhibit apparent second-order radical decay kinetics, with three linear regions in an Arrhenius-type plot, each region having low standard deviations from linearity based on as high as 40 experimental points.

The observed rapid reactions between gases diffusing into preirradiated crystalline amides had been explained on the basis of the ease of diffusion along the layerlike crystal structure of these systems. It has been found that irradiated stearic and elaidic acids, which also have a layerlike structure, behave in a manner similar to stearamide when reacted with nitric oxide. On the other hand, ole-

amide, which probably packs more loosely because of the *cis*-double band configuration, reacts much more rapidly with nitric oxide under similar treatment. M. ISILDAR, W. REAMS, G. ADLER

COLLOIDS AND SURFACE PHENOMENA

A program for the study of colloids and surfaces has been started, the object of which is to study the chemical and physical processes that occur at interfaces. Monolayer films on water have been chosen as a starting point because these systems offer a wide variety of readily prepared surfaces in which properties can be easily varied.

Some dynamic surface tension measurements of unirradiated and preirradiated stearamide, cast as monolayer on water, have been made. Some differences in pressure-area behavior were noted, but were at the extreme limits of detectability of the instrumentation used.

An automatically operating and recording Langmuir film balance is being constructed. This device is designed to obtain data under either constant pressure or constant area conditions, and will also be capable of studying regions adjacent to the monolayer.

A preliminary study of the interactions between Congo red and gum arabic indicates that the optical density of the dye is reduced in the presence of gum arabic. Since gum arabic is a polyelectrolyte, it is not clear yet what contribution the ionic strength of the solution is making to this decreased optical density over and above the direct dye adsorption. A. STINSON, G. MACRI, G. ADLER

VINYL POLYMERIZATION MECHANISMS

Since the molecular weight distribution of a synthetic polymer will be related to the mechanism of the polymerization reaction, a comparison of the distribution resulting from radiation-induced ionic polymerization of styrene and radiation-induced radical polymerization has been undertaken. For those samples polymerized by radicals, the distri-

bution curves are what one might expect from the known kinetics, where chain transfer is absent and chains are terminated by radical-radical recombination.

In the case of very pure styrene, where propagation is by ions, and from kinetic data alone, it is obvious that most molecular chains do not result from direct radiation initiation but rather through a very favorable chain transfer to monomer. The distribution curves that have been determined so far reflect this pattern in their gross behavior. A preliminary estimate at the temperature coefficient for the chain transfer to monomer is 8 kcal/mole.

A. GLINES, C. JOHNSON, D. METZ

RADIOLYSIS IN THE ADSORBED STATE

Surface changes following radiolysis of CO_2 adsorbed on silica surfaces were monitored by following changes in the infrared spectrum. Irradiation at room temperature produces an absorption band at 2944 cm^{-1} which increases in intensity with total absorbed dose. When irradiated samples were heated at various elevated temperatures, the decrease in the intensity of this absorption band paralleled the increase in the amount of CO produced. At 475°C the band finally disappeared. This behavior and the yield-dose relationship leave little doubt that the species absorbing at 2944 cm^{-1} is the main precursor of CO. The band position of 2944 cm^{-1} is characteristic of the C—H stretching frequency of a surface formate group.

The radiolytic yield of nitrogen from N_2O adsorbed on Linde Na 13X sieves has been found to be constant at $G(\text{N}_2) = 4.2$ and independent of the surface coverage from $600\text{ }\mu\text{mole N}_2\text{O}$ per gram sieve to $0.01\text{ }\mu\text{mole/g}$, except for one narrow range of surface coverage, between 0.06 to $0.08\text{ }\mu\text{mole/g}$, where $G(\text{N}_2)$ apparently increases to values as high as 16. This unexpected observation is being investigated more thoroughly. In any event, it appears obvious that N_2O in this system is remarkably efficient in scavenging the energy transfer entity, presumably the electron. Preliminary experiments have shown that low concentrations of SF_6 decrease the nitrogen yield.

J. SUCHER, J. SUTHERLAND

Radiolysis of Liquid Ammonia

Further studies of the radiolysis of liquid ammonia at total doses $< 50 \times 10^3$ rad have been inconclusive in establishing the presence of products

other than N_2 , H_2 , and N_2H_4 . Attempts to produce tetrazine derivatives by the irradiation of solutions of methyl and dimethyl hydrazine in liquid ammonia have been unsuccessful.

R. GOODRICH, J. SUTHERLAND

Radiolysis of Aqueous Hydrazine Solutions

In order to investigate the existence of such hydronitrogen compounds as diazene, triazene, tetrazane, and triazane, which have been postulated as intermediates in the oxidation of hydrazine to nitrogen, a study of the pulsed and steady-state radiolysis of aqueous solutions of hydrazine has been undertaken. In the pulsed radiolysis studies a species has been observed with the following characteristics: (a) its spectrum has a maximum absorption in the range 225 to $230\text{ }\mu\text{m}$, (b) it disappears with first-order kinetics, (c) the rate constant for disappearance is pH-dependent and ranges from $k = 139$ to 0.05 sec^{-1} , and (d) it exhibits two pK_2 values. The yield of the species has been studied as a function of dose rate, dose, and concentration of N_2H_4 . Scavenging studies with N_2O have also been performed.

Steady-state radiolysis studies show that $G(\text{N}_2)$ increases rapidly from 0.2 at $10^{-6}\text{ M N}_2\text{H}_4$ to 2 at $10^{-4}\text{ M N}_2\text{H}_4$, and approaches 3 at $10^{-2}\text{ M N}_2\text{H}_4$. Saturation of the solution with N_2O causes an increase of nitrogen yield to 6.0.

These results have led to a revision of the mechanism of the radiolysis of aqueous hydrazine solutions.

R. GOODRICH, J. SUTHERLAND

Nitrogen Exchange Reactions

Several series of experiments have been performed in collaboration with Prof. R. Axtmann (Princeton Univ.) on the radiolytic nitrogen exchange reaction.

J. SUTHERLAND

Radiolysis of Organic Compounds

The radiolysis of trimethyl ethylene and tetramethyl ethylene was studied in an effort to determine their radiation stability and degree of polymerization. Table 1 lists the G -values for gaseous products from these compounds. All yields were linear with dose from 1×10^6 to 4×10^7 rads. The liquid products of tetramethyl ethylene were investigated using vapor phase chromatography. Some butenes, pentenes, hexadienes, and octadienes were formed. An exact identification could not be made because of a lack of material for

Table 1

G-Values for Gaseous Products From the Radiolysis of Trimethyl Ethylene and Tetramethyl Ethylene

Total gas	Trimethyl ethylene	Tetramethyl ethylene
H ₂	1.18	1.22
CH ₄	0.99	1.04
C ₂ H ₂	0.16	0.17
C ₂ H ₄	0.0009	0.0022
C ₂ H ₆	n.d.	0.0018

spiking (peak enhancement techniques). In neither case was there a polymer formed above a dimer.

J. WEISS, N. CARCIELLO

Membrane Studies

This program has been continued with the primary emphasis on fabrication techniques. Cellulose and cellulose acetate membranes have been fabricated. Attempts to graft other monomers on the cellulose membrane have not been very successful to date but this work is continuing.

J. WEISS,
N. CARCIELLO

Chemonuclear Program

M. STEINBERG

FISSION FRAGMENT AND RADIATION CHEMISTRY

Nitrogen Fixation

Homogeneous Gas Phase Experiments. Both flow and static experiments were performed using a ⁶⁰Co gamma source to study N₂ fixation by irradiation of air. Figure 1 gives the G-value for NO₂ formation as a function of temperature from 100° to 650°C at pressures from 2 to 200 atm and flows from 10 to 200 cc/min. The major conclusions are:

1. As temperature increases, the G-value increases to a maximum near 500°C and then decreases. The rate determining step is given by

where N* is N atoms and ions; this is followed by further oxidation to NO₂ by

As the temperature increases, the rate of reaction (1) increases; at temperatures >500°C, the equilibrium of reaction (2) shifts in favor of NO which

Figure 1. G-value for NO₂ formation as a function of temperature from 100° to 650°C at pressures from 2 to 200 atm and flows from 10 to 200 cc/min.

Figure 2. Plot of G-value vs percent O₂ in O₂-N₂ mixtures.

can then decompose by rapid reaction with N atoms or by charge transfer and neutralization.

2. Increasing the pressure decreases the G -value, the effect being more pronounced at the higher temperature. This may be due to increased ion recombination at the higher pressures.

3. The small effect of flow rate indicates that Figure 1 can be considered to be a plot of initial G -values.

A least-mean-square analysis of flow experiments at 300° and 500°C showed that the rate of NO_2 formation can be given by

$$r = I^{0.95 \pm 0.02} (\text{N}_2)^{1.03 \pm 0.02} \quad (3)$$

and is independent of O_2 concentration from 3 to 78% N_2 .

R. DIETZ, J. SMITH, J. PRUZANSKY,
L. JEFFERSON

Ozone Synthesis. Ozone formation by the homogeneous irradiation of oxygen and $\text{O}_2\text{-N}_2$ mixtures has been studied at temperatures from 27° to -100°C . A plot of G -value vs % O_2 in $\text{O}_2\text{-N}_2$ mixtures is shown in Figure 2. The important points are:

1. The G -value increases with decreasing temperature.

2. The G -value increases with increasing pressure; this is important from a process standpoint.

3. N_2 plays a role in the formation of ozone under all conditions.

4. At room temperature there is an effect of flow rate, indicating that the G -values shown are not the initial values and that there is a significant back-reaction even at low O_3 concentration (<100 ppm). At -100°C (and also at -60°C) the G -value was independent of flow from 10 to 200 cc/min. Here the G -values shown are the initial G -values. A least-mean-square analysis of data obtained at 69 atm for 3% N_2 in O_2 gave the relationship

$$c \text{ (ppm } \text{O}_3) = 29.3 (1/SV)^{0.98 \pm 0.02} / I^{0.97 \pm 0.02} \exp(1248/RT).$$

This equation is valid to concentrations of at least 4000 ppm O_3 .

R. DIETZ, J. SMITH

Design of a Chemonuclear Ozone Process for Water Treatment

The use of ozone in the tertiary treatment of a secondary waste effluent has great potential. The high energy radiation synthesis and the electric discharge synthesis of ozone have been compared. The results of basic radiation chemistry studies and

tests with the Brookhaven Chemonuclear In-Pile Research Loop (CIRL) indicate that G -values for ozone production from oxygen in a high pressure production facility can range between 10 and 15. These energy yields are at least 2 to 3 times higher than those obtained by the electric discharge process. Isotopic radiation sources such as waste fission product ^{137}Cs can be considered mainly for treating drinking water or for smaller quantities of sewage effluent in the range of <10 million gal/day. The fission fragment chemonuclear process has a distinct economic advantage over all other systems in the high capacity range (including the electric discharge process); it produces hundreds of tons of ozone per day and is capable of treating waste effluent in the hundreds of millions gal/day to over a billion gal/day sizes. Conceptual design and cost estimates of the chemonuclear process have been made. A flow sheet of the process is shown in Figure 3. The chemonuclear process cost is half that of the electric discharge ozonizer at higher capacities. For a billion gal/day sewage capacity, removal of 20 ppm COD (chemical oxygen demand) with chemonuclear ozone could be accomplished for 1.25¢/1000 gal. There is thus a large incentive for further development of a fission fragment chemonuclear process for ozone production.

M. BELLER

Chemonuclear In-Pile Research Loop

The CIRL was operated on a regular schedule of one run per month during the first half of 1969. Five runs were made in all, each of one week's duration. These runs were made without added chemonuclear fuel, utilizing ambient pile neutrons and gammas. This gave an in-pile dose rate of 2.4 megarads/hr based on the dosimetry and flux measurements made in the loop calibration run of November 1968.

The only system that has been studied to date is the synthesis of ozone from oxygen. Parameters that were varied during the runs were pressure, temperature, flow rate, dose rate, and nitrogen additive concentration. Their influence upon ozone concentration and yield (G -value) was determined. It was found possible to operate the loop at temperatures as low as -30°F . The following relationships were established:

1. G -value is independent of dose rate in the region studied (0.8 to 2.4 megarad/hr in-pile).

2. Ozone concentration is a linear function of dose rate in the same range.

Figure 3. Chemonuclear ozone generation for water purification.

Figure 4. Operational profile of the last run of the Chemonuclear In-Pile Research Loop showing the run conditions and resulting ozone concentrations.

Table 2
Summary of Run No. 6 Parameters

Exp. No.	Press., psig	Temp., °F	Power, MW(t)	% N ₂	Flow, ft/sec	Initial ^a G-value	Max. conc., ppm
1	200	30	10	9.2	16	n.d.	54
2	200	30	10	11.0	9	5.8	56
3	200	0	10	9.9	19	7.2	53
4	200	30	15	11.7	16	6.0	95
5	200	0	15	10.1	18	8.0	67
6	800	30 to -23	15	10.2	8	10.0	305
7	200	0	15	1.5	17	12.0	325
8	500	0	15	10.0	10	11.0	130
9	800	0	15	13.3	8	12.0	138

^aAt concentrations up to 40 ppm.

3. Concentration and *G*-value are independent of linear flow velocity from 9 to 19 ft/sec.

4. At low pressure (200 psi), ozone concentration is independent of temperature, but at higher pressures (500 to 800 psi) increased concentration is favored by lower temperatures.

5. *G*-values increase with decreasing temperatures in the -30° to 70°F region.

6. At each pressure, an optimum nitrogen concentration exists which appears to result in maximum ozone concentration. Higher pressures require higher nitrogen concentrations.

7. Higher pressures favor higher ozone concentrations.

The mechanical operation of the loop was highly satisfactory with only a few easily remedied malfunctions occurring. Figure 4 is an operational profile of the last run (June 1969) showing the run conditions and resulting ozone concentrations. Table 2 summarizes the data and indicates the *G*-values obtained, which range up to 12.0. The highest concentration obtained to date (500 ppm of ozone) was on an earlier run.

The loop is currently in standby condition. Further operations are planned (when funding permits) to provide a firm basis for chemonuclear production of ozone.

W. TUCKER, M. BELLER,
J. KLEIN, E. COTE, G. ARNOLD, S. SATO

Radiation Chemical Processing

M. STEINBERG

CONCRETE-POLYMER MATERIALS

The development of precast and premix-type concrete-polymer composites as improved materials

of construction is being carried out in a joint program between the Radiation Division and the Division of Research of the Bureau of Reclamation. The program consists of monomer selection, development of process technology, testing, and the identification of potential applications. Fundamental studies are being conducted to develop a basic understanding of the concrete-polymer system.

Monomer selection is based upon cost, polymerization rate, and the application for which the material is being considered. For normal temperature applications, low-cost monomers such as methyl methacrylate and styrene are being tested. During the current year the structural properties of concrete impregnated with acrylonitrile, chlorostyrene, and a 90% methyl methacrylate-10% trimethylolpropane trimethacrylate (TMPTMA) mixture have been measured. The durability testing of these systems has been started and previously reported measurements have been extended for an additional year. Each of the monomers has considerably improved the strength and durability of concrete. The degree of improvement appears to be a function of the polymer content or loading.

The general procedure used for impregnation includes (1) evacuation of either oven-dried or undried specimens, (2) soaking in monomer, (3) wrapping of specimens in polyethylene sheet to reduce vaporization, and (4) polymerization by either radiation or thermal-catalytic methods.

The impregnation of concrete with a 90% methyl methacrylate-10% TMPTMA mixture has resulted in composites with the highest compressive and tensile strengths obtained to date. A compressive strength of 22,490 psi, corresponding to an

Figure 5. Comparison of resistance of concrete-polymer and standard concrete control samples to corrosion by 15% HCl.

increase of 327% over the controls, was obtained for a sample containing 6.3% monomer polymerized by radiation. Thermal-catalytic initiated polymerization produced a composite with a strength $\approx 11\%$ lower (20,000 psi vs 22,490 psi) than that obtained by radiation-induced polymerization even though the polymer content was $\approx 13\%$ greater (7.1% vs 6.3%). Similar results were obtained by tensile strength measurements.

In general, methyl methacrylate-impregnated specimens have given the greatest improvement in durability properties, acrylonitrile the least. Remarkable improvements in freeze-thaw durability have been obtained. Compared with a control which failed after exposure to 590 cycles (failure is defined as 25% weight loss), one specimen containing 6.7% methyl methacrylate has shown only a 0.5% loss after 5420 cycles. This corresponds to an improvement of $>800\%$. The smallest improvement has been 100% for a sample containing 5.0% acrylonitrile.

The resistance to 15% HCl is being determined. Compared with the controls which failed after 112-day exposures, none of the impregnated specimens have failed after exposures ranging

from 350 to 525 days. A photograph of the 3×6 -in. cylinders of impregnated and nonimpregnated concrete is shown in Figure 5.

Exposure of concrete-polymer to soluble sulfates has indicated essentially no attack after exposures up to 510 days. The controls were severely attacked.

The structural properties of steel-reinforced concrete-polymer materials are being determined. Increases in flexural strength of a factor of five were obtained for a sample that contained 2 vol % fiber reinforcing and was polymer-impregnated. The ultimate flexural strength of an impregnated mortar beam containing 8 vol % fiber was increased by a factor of fifteen compared with the unreinforced, unimpregnated control. The bond strength between steel reinforcing rods and concrete-polymer has been measured. Increases up to a factor of three have been obtained in pull-out bar tests.

As a material of construction for flash-distillation units in water desalination plants, a hard, glassy polymer is required that will withstand hot brine and distilled water at temperatures up to 143°C . For this specialized application, thermosetting monomers such as polyesters and epoxies are being investigated. The addition of a cross-linking agent to the more common thermoplastic monomer in order to increase their softening point to $>143^\circ\text{C}$ and to improve their chemical resistance is also being investigated. TMPTMA has been used with methyl methacrylate and styrene with good results. These materials are excellent candidates for high-temperature saline water applications.

The high temperature strengths of four monomer systems have been measured. A 60% styrene-40% TMPTMA mixture has given the greatest improvement in strength (160% at 143°C) and the smallest reduction in strength with increased temperature. The higher temperature strength data are shown in Figure 6.

A number of other potential applications are being evaluated as part of cooperative programs with other governmental agencies. Applications for pipe, housing materials, underwater structures, and roads are being studied.

The field testing of impregnated concrete pipe in high sulfate-containing soil has been initiated. Sixty 4-in.-i.d. $\times$ 24-in.-long sections of draitile were impregnated and installed under USBR supervision at the Westlands Experimental Drainage Plot in northern California. Ten lengths of

Figure 6. Concrete-polymer materials: compressive strength vs temperature, OSW-type concrete.

each of three qualities of pipe (poor, average, and high) were impregnated with methyl methacrylate. An equal number of lengths were impregnated with epoxy-styrene (see Figure 7). The corrosion resistance will be observed over periodic time intervals running from months to years.

L. KUKACKA, P. COLOMBO, A. AUSKERN,
 R. GABARAIN, G. FARBER, J. FONTANA,
 W. HORN, K. KANIGE, J. VARELA

ETHYLENE AND ETHYLENE COPOLYMERS

The general objectives of this program were to develop radiation-induced chemical processes for the polymerization of ethylene and ethylene-based copolymers. Secondary objectives included the development of the fundamentals and principles of high pressure radiation-induced processes.

The effort on the program has been decreased because of growing industrial activity in the area. A number of industrial firms have undertaken development of the process and at least one pilot-plant-scale study is under way. The flow system built at BNL for this study has been shut down but is being maintained in standby condition for future experiments on ethylene copolymers.

The current emphasis is on serving as a source of information for industrial organizations inter-

Figure 7. Concrete pipe test specimens impregnated with epoxy-styrene.

ested in radiation chemical processing in general and in ethylene polymerization and copolymerization in particular. Great interest has been shown in ethylene-carbon monoxide and ethylene-sulfur dioxide copolymers, and the request for samples has far exceeded the supply. Requests have been received from industrial and academic organizations to convert the existing flow system to the production of polyketones and polysulfones, samples of which could then be made available to interested parties for characterization. Reports have been published on both of these systems.

The information exchange agreement with the Japanese Atomic Energy Research Establishment at Takasaki has continued, and progress reports on ethylene polymerization and chemonuclear processes are exchanged on a bimonthly basis. It has been suggested that this exchange be broadened to include ethylene copolymerization. In addition, annual meetings are scheduled. A meeting of personnel from both laboratories was held at BNL on November 6-8, 1968. The meeting scheduled to be held at Takasaki in November 1969 has tentatively been postponed until 1970 because of budgetary limitations on foreign travel.

P. COLOMBO,
L. KUKACKA

SURVEY EXPERIMENTS ON APPLICATION OF ISOTOPIC RADIATION FOR CHEMICAL WORK

In the search for applications of isotopic radiation energy for chemical processing, exploratory experiments are performed to determine the existence of a radiation-induced effect. Once an effect is established, a determination of the radiation chemical yield is made. The basis for selection of a system for development is its economic potential and the novelty or uniqueness of the process or product.

Polymer Composite Materials

Using the principle of either infiltrating a porous material with a monomer or mixing various indigenous materials with a monomer and subsequent *in situ* polymerization with ^{60}Co gamma radiation may result in the synthesis of a composite material having useful structural and durability properties. A number of these composites have been produced.

Soil-Polymer. In this case ordinary soil was air-dried, mixed with methyl methacrylate monomer, and loaded into a steel form or die. The die cavity

was loaded with a piston under pressure and placed in a ^{60}Co gamma field for polymerization. A solid composite material was formed and this was tested for compressive strength. The results are given in Table 3. The compressive strength was found to be a linear function of the polymethyl methacrylate loading from 2 to 14 wt %, increasing from 6000 to 14,000 psi.

Sewage-Refuse-Cement-Polymer Concrete. As part of an overall scheme of recycling solid and liquid waste and obtaining another approach to the waste disposal problem, a composite material containing refuse and sewage sludge has been produced which has structural and durability properties. The composite is analogous to a concrete but substitutes refuse and sewage sludge for aggregate. Cement or lime is initially mixed with ground or compressed refuse and sludge, and is allowed to set. Monomer is then diffused through the mass and the composite is polymerized *in situ* by ^{60}Co gamma radiation. The polymer impregnation tends to render the composite impervious to water and to prevent decay or decomposition, and the irradiation tends to sterilize the material. The polymer-augmented refuse-sewage concrete might have applications as building blocks, underground and underwater structures, piping, seawall, piers, land-fill and in ground support operations.

Several preliminary trial runs have been made (see Table 3). A sewage-cement-polymer mix was obtained with compressive strengths as high as 12,000 psi. A refuse-cement-polymer concrete containing ~50% refuse gave a strength of 4000 psi.

Ceramic-Polymer. The objectives of the work on ceramic-polymer-composites are (1) to develop new composite materials that take advantage of the unique properties of pore-filled composites, and (2) to apply the concept of pore-filling with polymerizable material to existing materials in order to either permanently or temporarily strengthen them.

Work has progressed in two areas. An aluminum oxide-methyl methacrylate composite is being developed which has a number of potential medical applications. The material can be used as a bone substitute and as a pin for fractures. The advantages of this system over a fully porous ceramic system are that a material can be made with strength to match that of bone, such a composite is much less sensitive to fatigue than a porous material, and the polymer can be easily removed from regions where bone growth into pores is desirable.

Table 3
Summary of Polymer Composite Compositions Used in Preliminary Experiments

Type		Composition, wt %				Polymer loading (% of unloaded)	Compressive strength, psi
		Water	Portland cement	Aggregate			
Polymer-concrete (control concrete, 5000 psi)	7		14	33 sand 46 rock		6	20,000
High strength polymer-concrete (control concrete, 18,000 psi)	33		67	—		4	25,000
Soil-cement-polymer concrete	5		10	85 Thailand soil		17.5	12,500
Soil-polymer	—		—	100 soil pressed		2	6,000
Soil-polymer	—		—	100 soil pressed		14	14,000
Sewage-cement concrete	54	sewage sludge (30% solids)	46	(sewage sludge: 30% solids in water column)		—	2,200
Sewage-cement-polymer concrete (SPC)	50	sewage sludge	50	(30% sludge solids)		38	12,000
Sewage-cement-polymer concrete	40	" "	60	(30% sludge solids)		24	11,300
Refuse-cement-polymer concrete (RPC)	33		17	50 refuse		10	4,000
Sewage-refuse-cement-polymer concrete (SRPC)	18		18	54		10	a
Soil-sulfur	—		—	20% sulfur, 80% soil		—	5,000
Lt. wt aggregate-cement-polymer concrete	31		62	7% foamed glass		3	4,000

^aTests incomplete.

Toxicity problems encountered with the polymer (methyl methacrylate) may be eliminated because of the ability to use pure additive-free monomer and to sterilize while polymerizing with ⁶⁰Co gamma radiation.

Samples have been prepared of porous alumina, polymer-filled alumina, and pure polymer for implantation into test animals for determination of toxicity effects. An effort is under way to develop a ceramic composition with the proper pore size to permit bone growth into the pores.

The second area where there has been considerable effort has been in the strengthening of porous materials by polymer-filling to give them temporary strength for machining operations. Two types of materials have been investigated. One is a commercial aluminum silicate material with about 6 vol % porosity. Normal machining operations result in considerable chipping and breaking. The polymer-filled materials under the same machining conditions result in about 75 to 90% fewer failures. The polymer (methyl methacrylate) can be re-

moved after machining by a low-temperature heat treatment.

The second material tested is an extruded, unfired, aluminum oxide composition. This material has considerable porosity. It has been successfully filled and polymerized with methyl methacrylate. The composite material is much harder than unfilled aluminum oxide. Extensive evaluation of the machinability of both materials is under investigation.

A. AUSKERN, W. HORN

Radiation Polymerization in the Presence of Catalysts

At present the majority of industrial radiation processes involve the synthesis or modification of polymers. There is little doubt that the greatest potential for ionizing radiation is in this area. Although it has been shown that some radiation-polymerization reactions can compete with classical chemical-initiated systems, the economic advantage of the radiation processes has been too marginal to warrant change-overs from time-tested

conventional processes. The factors that have retarded large-scale development are the low polymerization conversion rates and the cost of high-intensity radiation facilities.

A new technique is being investigated in an attempt to increase radiation polymerization rates without increasing radiation intensity. This involves the addition of a chemical catalyst to the monomer prior to irradiation. The initial work is being conducted with styrene monomer, benzoyl peroxide, and ^{60}Co radiation. Styrene was selected because it requires a high radiation dose for polymerization. The monomer (containing 25 ppm of tert-butyl-pyrocatechol) was used as received from the manufacturer.

Polymerization rate curves were obtained both with and without the addition of 1% by wt of benzoyl peroxide to the monomer. The experiments were conducted at $\sim 25^\circ\text{C}$ and at a radiation intensity of 2.75×10^5 rads/hr. Under these conditions, styrene without benzoyl peroxide required a total dose of 2.75×10^6 rads to overcome the inhibitor. At this same radiation dose, the styrene containing 1% by wt of benzoyl peroxide had a monomer-polymer conversion of 11.0%. A total dose of 15.4×10^6 rads was required to convert the styrene-benzoyl peroxide system to polymer completely. The plain styrene showed a monomer-polymer conversion of only 25% at this dose.

With 1% benzoyl peroxide and a radiation intensity of 2.7×10^5 rads/hr at 25°C , the initial rate of styrene polymerization was 3.45%/10⁶ rads. The radiation intensity required to obtain the same rate in the absence of benzoyl peroxide was calculated to be 16.5×10^5 rads/hr.

Rate data were also obtained at reaction temperatures of 35° and 50°C . These data indicate that the rates for plain styrene and styrene containing benzoyl peroxide approach each other as temperature is increased.

Molecular weight measurements were obtained for polystyrene formed under the conditions given above. Under constant conditions of intensity and temperature, the molecular weight decreased as the concentration of benzoyl peroxide increased from 0 to 3%. It was also observed that the molecular weight increased as the polymerization temperature increased from 20° to 50°C . In all cases, however, the molecular weight distribution given in terms of the M_w/M_n ratio were generally between 1.8 and 2.4.

P. COLOMBO, J. FONTANA, R. GABARAIN

Radiation Chemical Engineering

F. HILL

RADIATION CHEMICAL REACTOR STUDIES

The principles of design and operation of process equipment in which radiation-initiated reactions are carried out are established through theoretical and experimental investigations. These investigations are concerned with the interaction of the kinetics of radiation chemical reactions with phenomena of radiation physics, fluid dynamics, and mass and heat transfer. The results of the work are useful in devising scale-up procedures, in designing irradiators for optimum source utilization or optimum product distribution, and in interpreting radiation chemical experiments where chemical and physical rate processes interact. The results should apply to irradiators for the radiation inactivation of contaminants in liquid and particulate materials as well as to radiation chemical reactors.

Chain Center Mixing in a Photopolymerization

In these experiments the rate of a photopolymerization, carried out in a partially illuminated, stirred vessel, is measured as a function of stirrer speed. A new 500-W Hg arc light source with grating monochromator has been provided for this study. In previous phases of this work involving the unsensitized photopolymerization of methyl methacrylate, considerable difficulty was encountered in obtaining reproducible data. During the past year, the benzoin-sensitized reaction has been used. The half-order dependence of initial rate of polymerization on sensitizer concentration and on absorbed intensity has been checked. The sensitized rate has been measured as a function of three methods of monomer purification: (a) washing with caustic solution followed by drying with silica gel, (b) the first procedure followed by distillation, and (c) the second procedure followed by prepolymerization using a Hg arc source followed in turn by distillation. Spectral studies of the monomer purified by the three methods indicated no variation in absorbance with method at $366\text{ m}\mu$ but appreciable variation at $314\text{ m}\mu$. The first procedure is thus adequate at $366\text{ m}\mu$ where experiments are normally conducted, whereas the second procedure would probably be required at $314\text{ m}\mu$. The initial rate was found to be essentially independent of method of purification. The rate de-

creased with time and showed a tendency to level out as conversion increased. Such variation has been noted by others [NORTH AND REED, *Trans. Faraday Soc.* 57, 859 (1961)] and ascribed to a corresponding variation in the termination rate constant with extent of conversion.

A. MULLER, J. EICHACKER

Chemical Dosimetry in Flow Systems

Problems arising in chemical dosimetry in flow systems were analyzed in terms of chemical reactor design principles and were studied experimentally.

Calculations were made of fraction conversion-dose relations in radiation chemical reactors with nonuniform distributions of dose rate and residence time in which the reactant was the aerated Fricke dosimeter solution. Reactors considered had annular reaction volumes with axial line sources and included the continuous tubular reactor and the continuous stirred tank reactor.

The calculations showed that at large conversions the rate of radial mixing in the single-pass tubular reactor and degree of segregation in the stirred tank reactor are important factors relating conversion to absorbed dose. Initial rates, however, are unaffected by mixing or degree of segregation, and, therefore, can in principle be used to determine absorbed dose. The determination may also be made from data from the tubular reactor when operated with almost total recycle.

Several aspects of the flow dosimetry problem were explored experimentally. Conversion was measured vs flow rate of the Fricke solution in two tubular reactors and one stirred tank reactor, all annular reactors with axial line sources. The two tubular reactors were nominally identical in dimensions except for radial thickness of reaction volume. A 20-Ci line source of ^{90}Sr - ^{90}Y beta particles was used in these reactors. The dose determined from the initial slope of the experimental fraction conversion-mean residence time relation obtained in single-pass laminar flow agreed very closely with the dose obtained with recycle for both reactors. In the experiments with recycle, conversion was insensitive to recycle flow rate for recycle rates large compared with the through-flow rate.

The stirred tank reactor measurements were made in a stirred 5-liter vessel with an axial strip source of ^{60}Co gamma radiation. Source strength and stirring speed were parameters. Little or no evidence of segregation was found. The dose determination could, therefore, be based on a com-

plete micromixing model. The absence of segregation was consistent with the long mean residence times used compared with measured dispersion times.

C. DAVIS, P. FALLON, A. MULLER,
M. ROTHBART

Radiation Engineering

J. CUSACK

HIGH INTENSITY RADIATION DEVELOPMENT LABORATORY OPERATIONS

Source Inventory

At the end of the year, source inventories maintained for research and development included 2.25×10^6 Ci ^{60}Co ranging from 0.1 to 500 Ci/g in specific activity and from 10 to 9000 Ci in individual source strength; 250,000 Ci ^{137}Cs ; and 5000 Ci ^{90}Sr . An additional 360,000 Ci ^{137}Cs and 45,000 Ci ^{90}Sr are on order and should be received early next year.

Approximately 166,000 Ci ^{60}Co in Mark I sources were loaned to the U.S. Army Quartermasters Laboratory at Natick, Massachusetts, for their use during the period when they were refurbishing their facility with new sources. Thirty-one thousand Ci of the Natick type rod sources were shipped to the University of North Carolina in support of DID-sponsored work there.

Cell Activities

Operations in the preparation cell included the reclamation of 139 Co sources. Forty-eight sources from the Hawaiian program were badly corroded and pitted. In a few cases the first encapsulation had also failed. All of these sources were re-encapsulated. The remainder, rejects from the Natick program, ranged from dimensionally rejected sources to some whose jackets had ruptured. These have been re-encapsulated also and will be limited to on-site use. Additional work performed in the cell included assaying of all sources added to inventory, loading and unloading of the Brookhaven Portable Cesium Development Irradiators, and service loadings and modifications for the BNL Biology Department's Gamma Field Irradiator, BNL Medical Department's Rodent Irradiator, and Veterinarian Blood Irradiator, and a Strontium-90 Ozone Generator for the U.S. Department of Health, Education and Welfare.

Service irradiations performed in the irradiation cell included monomer loaded concrete test specimens, ozone generation studies, polymerization rate studies, and enzyme sterilization studies. Continuing work such as the cesium-cobalt dose distribution comparison study was performed.

GAMMA FACILITY

Fueling of the new facility is not yet complete, and experimental irradiations are being done in both the new and old facility. During the past year about 3500 sample hours of irradiation were performed each month (see Table 4). While this is a reduction of about 1500 hr/month from last year's rate, a gradual growth is anticipated over the next few years as standardized reproducible cobalt and cesium fields are made available to researchers.

GENERAL ENGINEERING PROGRAM

Pool Elevator

A new and more compact radiation source elevator was designed, fabricated, and installed over the existing elevator located in the HIRDL irradiation cell pool. The installation is designed to utilize the present elevator as a storage platform for source plaque modules at the bottom of the pool, thus reducing the time required for source plaque alterations and increasing flexibility. If necessary, the old elevator can be made serviceable with a minimum of effort and time.

Cell Ventilation

Leaks in the duct work of the cell air system have allowed ozone to penetrate into occupied areas and, at times, have made it impossible to enter the preparation cell when the irradiation cell is in use. A complete engineering study was made and modifications designed to alleviate these problems. Construction is expected to start this year.

Automated Manipulator

The Model-300 General Mills mechanical arm was automated by the addition of an XYZ programmer that allows the arm to position itself in any of over 1×10^8 positions in a working volume 4-ft cube. The automation of this equipment will allow the simulation of perfectly uniform source plaques by the multipositioning of one source element. It will also allow the study of dose distribu-

Table 4
Use of Gamma Facility
for Period October 1968 to October 1969^a

User	Sample hours
Department of Applied Science	27,424
Physics Department	10,414
AGS Division	847
Chemistry Department	405
Instrumentation and Health Physics Department	160
Biology Department	32
Off-site	2,404
Total	41,686

^aThere were 1337 samples irradiated in 1126 separate irradiations.

tion for the purpose of designing shaped source plaques which will produce the most desirable dose distribution in finite targets.

Source Activity Standardization

In July of this year, a meeting was held at BNL to discuss the standardization and specifications of high intensity gamma sources. In attendance were representatives of interested U.S. industries, USAEC, AECL, USNBS, National Research Council of Canada, ORNL, BNL, U.S. Army Natick Laboratories, Radiochemical Center of England, and Saclay, France. The various techniques for determining the source activity, both "true" and "effective," were discussed in detail. It was agreed that extensive standard source intercomparison among the participants is desirable, and a number of sources were chosen to be distributed for this purpose. French and Canadian sources have been received at HIRDL; General Electric sources are expected shortly.

In anticipation of an increased workload on the BNL calorimeter, efforts are being made to automate its operation and increase the accuracy of its instrumentation. A study to locate and minimize all sources of error is in progress.

COMPUTER CODES

Modification of existing gamma dose distribution codes to broaden their utility was continued this year. In addition, work was begun on a computer code for cylindrical sources surrounded by

any number of concentric shields. Preliminary work was begun on a study of Monte Carlo codes which more accurately predict self-absorption in gamma sources than do "hand" calculations, thereby permitting the more accurate determination of source activities for high level sources.

A modification of the more general code QAD, developed at Los Alamos, was written and tested. This program (RAD) is used to compute gamma dose rates from a finite rectangular source to many dose points in a finite target based on a "point kernel" integration over the source volume.

The various codes developed in this program to determine shielding requirements and dose rate distribution have been distributed to and used by most of the industrial radiation processing interests. Their widespread use at BNL in this period has included design calculations for blood irradiators, animal irradiators, and chemical irradiators.

Calculations of the beta dose rate from rectangular beta source plaques in a homogeneous medium are being continued.

SOURCE DEVELOPMENT

⁶⁰Co Radiation Sources

A test lot of BNL ⁶⁰Co Mark III design was procured and specimens were sent to the Savannah River Plant for final certification. This will be completed when funds for activation are available. The Mark III source differs from the Mark II in that the nominal cobalt weight was increased to 68 g (2.4 oz) and cladding thickness decreased to 0.25 mm (0.010 in.).

A test lot of niobium-clad cobalt was procured for which a satisfactory commercial surface finishing method was found. This method will also be examined for use on stainless steel-clad sources.

¹³⁷Cs Radiation Sources

Swelling of some Mark I cesium sources at elevated temperature occurred again and the cause is being investigated. A safety feature of the rectangular cross-section design is that internal pressure is more readily detected than that in a cylindrical design. This sensitivity gives visual warning that dangerous pressures may be developing.

⁹⁰Sr Radiation Sources

A test lot of BNL-ORNL ⁹⁰Sr Mark I design was received from ORNL. This design consists

of SrSiO₃ microspheres dispersed in an aluminum matrix clad with thin stainless steel. It is of moderate efficiency and of high integrity.

Long Range Source Evaluation

Automated cycling corrosion apparatus for simulating pool-air conditions was designed, built, and given a preliminary trial. Apparatus for corrosion testing materials in aqueous systems at moderate temperatures and ambient pressure was assembled. Results of a preliminary experiment showed that a Co-Cr alloy had no change in weight after a 66-day exposure.

Corrosion specimens from research irradiator plaques were examined. The corrosion rate of the 316 SS cladding was about 1×10^{-3} mg/sq decimeter/day or 2.0×10^{-4} mils/year.

Proprietary descaling materials were received for evaluation.

DOSE DISTRIBUTION

Heterogeneous Targets

Heterogeneous target studies continued with the greatest emphasis upon improving experimental techniques and upon verification and improvement of computational methods for dose prediction in heterogeneous target systems using extended ⁶⁰Co and ¹³⁷Cs sources. In these studies infinite arrays of food cans were used as the target materials.

Results indicate that the FUDGE 4 computer code for the calculation of absorbed gamma dose satisfactorily predicts the dose distributions in multi-pass irradiator systems with heterogeneous target geometries, such as food cans, provided that the target array is thick enough to allow homogenization of the target material. For thin target arrays, such as single rows of No. 10 or No. 3 food cans, the computer codes failed to predict the dose accurately.

When the effective density of the product was calculated simply by considering the inside volume of the conveyor carrier and the mass of product in the carrier, serious overestimations of the dose and of irradiator efficiency resulted. Better agreement between computation and experiment is obtained, however, when the effective density is based upon the density of the unit cell formed by the particular array of cans being used. Equations (1), (2), and (3) are the recommended forms for calcu-

Figure 8. Square array, close packed.

Figure 9. Staggered array, close packed.

Figure 10. Open staggered array.

lating effective density for the three different square and staggered arrays of cans shown in Figures 8, 9, and 10.

Square array:

$$\text{Effective density} = W/D^2h, \quad (1)$$

Staggered array, close packed:

$$\text{Effective density} = W/2 \sqrt{3} D^2h, \quad (2)$$

Open staggered array:

$$\text{Effective density} = W/\sqrt{3}h (D^2 + DS), \quad (3)$$

where W = the total weight of the individual food can, including the weight of product and of the metal can, g; D = diameter of the can, cm; S = spacing between cans, cm; and h = height of individual food can, cm.

Figure 11. Lateral dose distributions found which would be predicted on the basis of the external spatial relationship of the target and the source.

Figure 12. Depth dose distributions found which would be predicted on the basis of the external spatial relationship of the target and the source.

Another study was motivated by concern expressed by Food and Drug Administration personnel that dosimetry being performed in the AEC food program did not take into consideration variations in lateral and depth dose distributions due to void spaces, e.g., the spaces between food cans in heterogeneous targets. The study indicates that when square or close packed and open staggered arrays of food cans are irradiated in large multipass continuous or stop-dwell irradiators,

there are no lateral dose distributions that can be attributed to void spaces between the cans. The only distributions found (Figures 11 and 12) are those that would be predicted on the basis of the external spatial relationship of the target and the source.

Dose Distribution Prediction

Dose distribution studies have been carried out in large-scale irradiators to determine the relationship between the maximum, minimum, and average doses. Until the writing of the *AEC Food Irradiator Calibration Manual* there was no agreed-upon uniform method of calibrating an irradiator. In some instances, technicians were reporting average absorbed doses to the product based upon the average of numerous dosimeters dispersed evenly throughout the food package. In other cases, maximum and minimum doses were reported. It was found that if maximum and minimum doses are accurately measured, the mean average dose to the product can be found by merely averaging the maximum and minimum doses. Further, it was found that the dose throughout the volume of the target is distributed normally.

DOSIMETRY AND DOSIMETER DEVELOPMENT

Manual Publication

The *AEC Food Irradiator Calibration Manual* was prepared for limited distribution to US AEC DID food contractors and USF&DA personnel to clarify the techniques and procedures of measuring and reporting dosimetry data.

A comprehensive manual covering the calibration of the Brookhaven Portable Cesium Development Irradiator (BPCDI) was written, and will be supplied to all recipients of the irradiator.

A manual containing detailed descriptive material on all AEC food irradiators is in preparation. The information in the manual will include conceptual description and pictures of the unit; detailed, important physical dimensions; expected dose patterns and dose rates; and throughput capacities.

Interfacility Cooperation

Three meetings, two at BNL and one in Ottawa, were held for discussions among personnel from US AEC DID, BNL, and AECL to explore possible areas in which these groups could cooperate.

The areas discussed were standardization of dosimetry procedures, interfacility comparisons, source comparisons, and standardization of techniques for curie content determination. Cooperative work has since started in each of these areas.

Absolute absorbed dose measurements were cross-checked with the U.S. National Bureau of Standards. This involved the exchange and test of Fricke dosimeters between the laboratories in two series of tests. Results indicated that the two facilities were in only fair agreement (within 5%). It is felt that the discrepancies found could be attributable to errors arising out of adverse shipping and handling conditions.

Workshop Activities

The Fourth Biennial Dosimetry Workshop was held on October 1-3, 1969, at the U.S. Army Quartermasters Laboratories, Natick, Mass. The Workshop was sponsored by the US AEC DID, hosted by Natick Laboratories, and coordinated by BNL. The main topics of discussion were production dosimetry, gamma dosimetry, surface interface effects, dose rate studies on dosimetry systems, high-energy electron dosimetry, and low-energy electron dosimetry. The Workshop was held concurrent with two dosimetry section meetings of the ASTM.

The chairmanship of the Gamma Dosimetry Section of ASTM Joint Subcommittee D9/D20 was assumed by members of the staff of the Radiation Division. Three section meetings were held this year.

Training and Assistance

Individuals who received training and consultation in radiation dosimetry and/or dose distribution calculation at BNL during the past year were from Radiation Machinery Corp., Gamma Processing Corp., Radiation Technology, Inc., US AEC DID, General Electric Co., NUMEC, U.S. Bureau of Commercial Fisheries (MPDI), and the University of Nebraska.

A member of the Radiation Division's staff assisted in the USAEC-IAEA-sponsored special lecture series in Food Technology held at Massachusetts Institute of Technology.

Irradiations in support of Columbia University's feeding study program and NASA's Apollo Astronaut Diet program were conducted.

Personnel from U.S. Army Natick Laboratories were assisted in the qualification of the Neutron

Products Irradiator in Dickerson, Maryland, for the production irradiation of 200,000 pounds of flour for the U.S. Army.

Others who were assisted in their dosimetry problems included the Dental Research Section of the Veterans Administration, General Electric Co., Radiation Technology, Inc., Gamma Processing Corp., University of Connecticut, Radiation Machinery Corp., Isotopes, Inc., University of Nebraska, U.S. Dept. of Agriculture at Savannah, Ga., Sandia Corp., Controls for Radiation, Inc., and the Swedish Atomic Energy Commission.

Cellulose Acetate Butyrate Dosimeter

Investigations of commercially available cellulose acetate butyrate indicated that it develops radiation-induced optical absorption spectra between 260 and 330 $m\mu$ when irradiated with ^{60}Co gamma rays. At 320 $m\mu$ this radiation-induced optical density bears a linear relationship to radiation dose between 1 to 50 megarads. The material was tested and found to be dose rate independent between 10^5 and 10^7 rads/hr using ^{60}Co gamma rays. The thermal stability was found to be excellent up to 60°.

Figure 13. The Brookhaven Portable Cesium Development Irradiator No. 2.

Beta Dosimetry

Experiments were started on the development of new techniques of measuring the absorbed dose from beta sources in small volume liquid flow systems where the effects of high linear energy transfer due to low energy radiation could be significant. The techniques are based upon the use of two liquid chemical dosimetry systems of known but opposite LET dependence.

Irradiator Calibrations

A Veterinarian Blood Irradiator, which utilizes 4000 Ci of ^{137}Cs , was calibrated at HIRDL using standard dosimetry techniques.

Two irradiators, one in Albuquerque, New Mexico, and one in Santa Barbara, California, were calibrated for Sandia Corp. for use in dosimetry studies aboard an instrumented space vehicle. The dosimetry was performed at BNL making use of special techniques which permitted shipment of the exposed dosimeters through the mail.

FOOD PROGRAM

Irradiator Support

In continuing support of a contract between AEC-NYOO and Lockheed for the maintenance of AEC-supported, pool-type irradiators, BNL has supplied off-site consultation and guidance. Before the expiration of this contract at the end of fiscal year 1969, a "minor" maintenance effort was conducted on the University of Florida irradiator and "major" efforts were conducted on the irradiators located at the University of California, the University of Washington, and Massachusetts Institute of Technology. Future maintenance will be the responsibility of the universities.

The Shipboard Irradiator, completely reworked at HIRDL last year and placed on loan to Iceland, is being returned to BNL for inspection and maintenance. When this is accomplished it will be shipped to the Republic of South Korea.

The Portable Cesium Irradiator was returned to HIRDL for complete modification to comply with new regulations pertaining to the transportation of radioactive material. The major modifications include the addition of a $\frac{3}{4}$ -in.-thick steel plate to all external surfaces of the cask, the strengthening of the access door closure, and the fabrication of a heavier crash frame. The added

weight of these modifications necessitated the acquisition of a new trailer and the fabrication of a more substantial base. In the interest of increased reliability and ease of maintenance, modifications were made to the inner door limit switch actuator and package shuttle mechanism. A more compact panel was assembled.

The BPCDI No. 2 (Figure 13) awaits shipment to Bombay, India, after testing, loading, and calibration at BNL. The quality of workmanship, as compared with the first unit, was much better although it was necessary to repair a void in the lead contained in the upper door. BPCDI No. 3, destined for Chile, underwent the same testing, loading, and calibration as the other units and is awaiting shipment. A second shipping frame is under construction and will remain in South America to be used for the return of this unit or the No. 1 unit currently in Argentina.

The Mark IV pool-type irradiator, scheduled for installation in Pakistan, is still awaiting shipment. The delay is due to problems in Pakistan in obtaining a suitable structure to house the unit.

Interfacility Dosimetry Calibration

Samples of standard ferric ion solution which were prepared and standardized at BNL were distributed to most major AEC food contractors. The distribution of these solutions should permit the accurate and uniform calibration of spectrophotometers in use at AEC food irradiation facilities, and should assure that the basis for absorbed dose measurement is the same at each laboratory.

At several facilities direct absorbed dose cross-calibration with the BNL facility through the interchange of dosimeters was undertaken. In all cases it was found that the techniques and methods being used to determine absorbed dose using the Fricke dosimeter were sound.

Facility Reviews

Facility reviews, jointly conducted at seven food contractor facilities by a staff member from BNL and one from US AEC DID, consisted of the detailed examination of the raw dosimetry data generated at the facility relative to irradiator calibration feeding studies and inoculated pack studies. Particular attention was given to the proper use of all dosimetry systems, the use of sound dosimeter calibration procedures, the proper use of the irradiator during product irradiation as well as during calibration, the correct placement of dosim-

eters in calibration and in monitoring, and the accurate work-up and reporting of the data.

Irradiator Calibrations

A comprehensive dose distribution calibration was performed on the Shipboard Irradiator prior to its shipment to the University of Nebraska.

An absolute dose calibration was performed on the Portable Cesium Irradiator as part of its qualifying tests for the production irradiation of 25,000 lb of potatoes for the U.S. Army Quartermaster Corps. The calibration was carried out in the field in Idaho by BNL personnel, but most of the laboratory work was performed at BNL.

Prior to their shipment to foreign consignees, the BPCDI units underwent complete calibration and characterization. An irradiator calibration manual was written for these units.

Food and Drug Administration Petition Support

An extensive and detailed review of all strawberry irradiation data generated using the Mobile Gamma Irradiator and the University of California Research Irradiator was undertaken in support of a petition to be submitted to the Food and Drug Administration by the US AEC. This petition will seek approval for the commercial irradiation of strawberries. The review encompasses the verification, recalculation, and organization of all raw data generated over a 4-yr period, its comparison with computer-generated predictions, and the preparation of a comprehensive report to be included in the petition.

A. BECHT, P. BEZLER, J. CASSIDY, E. DIVIS,
P. FALLON, L. GALANTER, D. HUSZAGH,
B. JAMES, F. KEUTE, J. MILAU, G. MILLER,*
R. MOGK, A. OLTSMANN, F. RIZZO,
E. SMITH, JR.,* B. SYLVESTER, M. TODOSOW,*
P. TREADWELL, W. VOGEL, J. WAGNER,
G. WOODSON

Atmospheric Diagnostics Program

This program is currently focused on the study of sulfur oxides as atmospheric pollutants. Their chemical and physical behavior under varied meteorological conditions is being characterized by application of the isotope ratio tracer (IRT) method developed under the program for this purpose.

*Summer Student

The work is supported jointly with the Atomic Energy Commission by the National Air Pollution Control Administration of the Department of Health, Education, and Welfare. At BNL, it is a combined effort of the Radiation Division with the Engineering Division and the Analytical Group of the Hot Laboratory Division and with the Meteorology Group of the Instrumentation and Health Physics Department.

The IRT method makes it possible to trace sulfur through the entire power plant combustion cycle, from the fuel before it enters the burners to the final dissipation of the stack plume into the environment. It offers the advantages of providing an inherent tag that is chemically precise without the use of radioactivity, since indigenous sulfur constitutes the tracer, and of providing a means of positively identifying sulfur coming from a specific source in a multisource area. The method has been demonstrated to be technically valid and is a powerful tool for studying sulfur oxides in the atmosphere.

The method makes use of the variation in the ratio of two stable isotopes of sulfur, ^{32}S and ^{34}S , that occurs in sulfur in fossil fuels from different sources. This variation is stated in terms of a "del" value that indicates the degree of enrichment ($+\delta^{34}\text{S}$) or depletion ($-\delta^{34}\text{S}$) of the sulfur in ^{34}S , expressed in parts per mil. In natural deposits, in general, sulfur in the oxidized state tends to have more positive del values, while that in the reduced state more negative, as the result of chemical and biological fractionation that the sulfur has undergone in different environments.

The various elements necessary for the application of the IRT method have been developed, tested in the field, and are in routine use. The filter pack developed for collection of SO_2 and SO_3 -sulfate samples at ground level and aloft was modified in two respects after initial field use. Stainless steel screen separators have been placed between the two filter sheets in the pack (a glass fiber prefilter to collect the particulates that carry SO_3 and sulfates, and a KOH-impregnated paper to absorb SO_2) to prevent the back-migration of SO_2 to the prefilter that occurred occasionally under conditions of high humidity. It was also found that sufficient barium was leached from the glass in the prefilter during sample processing to result in the precipitation of sulfur as barium sulfate with consequent loss from the process. A glass with a low barium oxide content was found and substituted satis-

factorily. A warm water rinse prior to use removes traces of sulfate found on the filters. Samples containing as little as 1 to 2 mg of SO_2 are now processed and the sulfur isotope ratios measured routinely. Methods and equipment for sampling flue gases for SO_2 and SO_3 in the ducts leading to stacks have been developed and are being field tested. The use of SF_6 as a collateral tracer has been adopted for plume dispersion studies. Methods of injecting SF_6 into stacks and of sampling aloft in synchronization with the sulfur oxides collection on the filter pack have been developed and used in the field. The capability for measuring SF_6 concentrations down to <0.1 ppb, using a gas chromatographic method employing an electron-capture detector, has been established. Crude oils have been found with satisfactory sulfur contents and del values to permit their use as tracer fuels in power plants for large-scale experiments.

Not only does the $^{32}\text{S}/^{34}\text{S}$ ratio provide a means of identifying sulfur in the air with respect to its source, but it has also turned out to be a sensitive measure of the extent to which a sulfur compound has taken part in a chemical reaction.

The fractionation caused by isotopic exchange following oxidation of sulfur results in changes in del values large enough for measurements to be made with a high degree of precision. These can then be related to percentage conversion of SO_2 to SO_3 or sulfate. This method has the significant advantage that it is not necessary to sample plumes quantitatively to establish the ratio of SO_2 to sulfate at a given point. Measurements are made of isotope ratios rather than of concentrations of components present in low abundance. Sample requirements are therefore less rigorous.

There are two general classes of problems to which the IRT method may be applied. One is the physical tracing of sulfur compounds through the atmosphere, such as in the study of their behavior in plumes, and of the dispersion of the plumes themselves. The second type is the study of the chemistry of pollutant sulfur. Here the data acquired to date indicate strong potentialities for the application of the IRT method, particularly when used in coordination with SF_6 tracer. Since the SF_6 is chemically inert, it provides a way of obtaining accurate dilution factors along a plume, to establish a datum against which to measure the chemical conversion of SO_2 .

Field operations are under way currently on three different studies: (1) combustion processes

Figure 14. Flue gas being sampled for SO_2 and SO_3 at breeching of power-plant stack.

in power plant boilers, (2) conversion of SO_2 aloft in stack plumes, and (3) SO_2 behavior patterns at low altitude and ground level in urban areas.

Combustion studies are being carried out at the Northport station of the Long Island Lighting Company and at the BNL steam plant. Samples are collected of SO_2 and SO_3 in the flue gas at the stack breeching and of fuels in use at the time, and then the del values determined. Considerable effort has gone into the development of equipment to ensure representative sampling of SO_2 and SO_3 in the flue gas duct. Since most of the SO_3 is carried by particulates, the gas is sampled isokinetically by matching the velocity of the stream being withdrawn through a nozzle pointing into the flow with the velocity of the main gas stream in the

duct. In this way a true distribution of particle sizes is collected. Figure 14 shows the sampling equipment being operated at the base of the Northport stack.

Based on the exchange of ^{32}S and ^{34}S between SO_2 and SO_3 ,

and a mass balance on the sulfur isotopes, the following equation is obtained that expresses the relationship between del values of the fuel and of the SO_2 :

$$\delta^{34}\text{S}_{\text{SO}_2} = \delta^{34}\text{S}_{\text{fuel}} - (K - 1)(X)(1000), \quad (2)$$

where K is the exchange coefficient and X is fraction of SO_2 converted to SO_3 . Since K is >1 , it

Table 5
Analytical Results for Stack Gas Sampled at Breech

	Fuel oil	SO ₂		SO ₃		K
	δ, ‰	conc, ppm	δ, ‰	conc, ppm	δ, ‰	
1. BNL Power Plant						
3/27/69	+7.9	1065	+7.6	25	+9.0	1.0014
4/1/69	msg	1010	+7.8	28	+9.3	1.0015
4/8/69	+8.2	1100	+7.8	29	+9.5	1.0017
5/13/69	msg	970	+7.5	20	+9.7	1.0021
2. LILCO Northport Plant						
5/22/69	+4.9	1180	+5.4	26	+7.2	1.0018
6/5/69	+4.5	1080	+4.7	26	+7.9	1.0031
		T, °C = 1500	900	25 ^a		
		K = 1.001	1.003	1.037		

^aFrom H.G. Thode, I. Monster, and H.B. Dunford, *Geochim. Cosmochim. Acta* 25, 163 (1961).

would be expected that the del value for SO₂ would be lower than that for the fuel, though for the low conversions to be expected in the furnace, the two values would be close. The del values in SO₂ and SO₃ are related by

$$K = (1000 + \delta^{34}\text{S}_{\text{SO}_3}) / (1000 + \delta^{34}\text{S}_{\text{SO}_2}) \quad (3)$$

This indicates that the del value of the SO₃ will increase as the result of exchange. The data to date, still preliminary in nature, do show this tendency. Table 5 shows del values for SO₂ to be close to those for the corresponding fuels, though slightly higher than those for Northport. For SO₃ the del values are consistently higher. The exchange constants calculated from the data agree with theoretical values.

The plume dispersion studies are being made at Northport and at Keystone, a plant operated by the Pennsylvania Electric Company in the coal-mining region of Western Pennsylvania. These stations are both modern tall-stack plants located in open countryside with a low SO₂ background. Since Northport burns oil and Keystone coal, they provide a basis for comparing the behavior of SO₂ in the emissions resulting from the two types of fuel. In these operations, samples are collected of the fuel in use, of the atmospheric background aloft, and of the plume at several distances from the stack, using a specially instrumented aircraft. Future runs will also include flue-gas samples. Sulfur hexafluoride is injected into the flue-gas before the stack. The plume is sampled

at several points along its length, simultaneously, for SO₂, SO₃-sulfate, and SF₆, using the standard filter pack for the first two and an evacuated canister for the SF₆. Concentrations of SO₂ and SO₃-sulfate are determined and the ³²S/³⁴S ratios measured using the double-beam isotope-ratio mass spectrometer. The SF₆ concentrations are measured using the gas chromatographic method.

Seven runs have been made at Keystone and four at Northport. The early runs were concerned primarily with testing methods and equipment. Emphasis was placed on the development of flight techniques, instrumentation, equipment design, and data requirements. The potentialities of the IRT method for studying SO₂ chemistry in plumes gradually became apparent after the data from these runs had been reviewed. The broadened scope of the IRT program requires the collection of a greater variety of data on each run. The need to coordinate the various elements making up the experimental package adds to the complexity already inherent in large-scale operations that must be matched to specific weather conditions. Figure 15 presents the data taken on one of the later Northport runs. This was the first run in which SF₆ was used and is typical of the runs to be made in the future. This run was made under inversion conditions, where the plume could be traced out to 18 km. Vertical and horizontal sections are shown along the plume. The plume boundaries are established by a combination of visual observation and SO₂ determination by a fast-response

Figure 16. Diurnal variation in del values in SO_2 collected at ground level in New Haven, Conn.

in New Haven and at the Astoria, Ravenswood, and Arthur Kill stations in New York. For each run, four 6-hr samples were taken over a 24-hr period and analyzed for SO_2 and sulfate. The original purpose was to demonstrate the sampling technique under field conditions and to establish background levels for future utilization in experiments. New Haven was selected because it is a compact city with only a dozen or so sources of SO_2 of any size and a single plant (English Station) in the center of town. The oil-burning plants are supplied by a small number of fuel distributors, and the del values in the fuel supplied by them are usually similar. It was anticipated that the SO_2 pattern would be quite homogeneous, so that an isotope ratio tracer fuel could be used at English

Station and superimposed on the background with little difficulty. As the data accumulated, it was evident that there was no coherent relationship between the del values in the oil being burned in the power plant, wind direction, and del values found in samples collected at the three widely spaced locations in the city.

What has been observed is that there appears to be a diurnal variation in the del values. In almost every case there is a considerable lowering of the del value during the hours of darkness and a return to higher values as daylight returns. Figure 16 shows a typical day's log in New Haven, with the hours of darkness shaded. There is some evidence to link the change in del value with variation in humidity with a resultant change in rate of oxidation of SO_2 .

Experimentation has started in the Meteorology Environmental Chamber that was installed during the year. This included instrument calibration and atmospheric chemistry in support of field operations.

G. ARNOLD, R. BALDWIN,* L. COHEN,** E. COTE, J. FORREST,*** W. JAHNIG III, J. KLEIN, G. MEINKEN,*** L. NEWMAN,*** C. SCARLETT,***

M. SMITH,** M. STEINBERG, W. TUCKER, W. TUTHILL,** I. SINGER,** R. WILSON***

Exploratory Research and Development

BALL LIGHTNING

Ball lightning is a natural atmospheric electrical phenomenon that until recently has not had a satisfactory explanation, and could not be studied in the laboratory. Now it has been possible to produce (by rf discharges) luminosities in air, of the size (~ 6 in.) seen in nature, and that persist up to one second after energy input stops. Previously, it was possible to maintain free floating "balls" indefinitely in an rf excited cavity, and a quantitative theory of their maintenance in dc fields was proposed so that the observed lifetime (several seconds) in nature could be explained.

Research in this period has concentrated on two areas: the nature of energy carriers and the non-equilibrium radiation from the ball, and the con-

*Engineering Division.

**Meteorology Group, Instrumentation and Health Physics Dept.

***Hot Laboratory Division.

firmation of the theory of input energy to balls by dc fields.

In the first area, numerous time and wavelength resolved scans of the transient luminosities produced in rf discharges have been taken for many different gases and gas mixtures. The spectra intensity at any given wavelength approximates a simple exponential decay with time. However, the variation of intensity with wavelength is quite complex.

The spectrum shows a strong OH peak at 3064 Å, strong Schumann-Runge O₂ bands (3500 to 4200 Å) and a broad continuum from 3500 to 13,000 Å. There is considerable structure, the nature of which is not yet determined, superimposed on the continuum. The spectral intensity of OH and O₂ Schumann-Runge emission corresponds to an emission temperature of ~4000°K, compared with a thermal temperature of ~2000°K measured by the resistance of fine wires in the luminosity. The average spectral intensity is fairly constant from 3000 to 13,000 Å at ~0.1W/cm²·sr·μ.

The nature of the nonequilibrium energy carriers is not yet determined, but is most probably one or both of the two lowest excited electronic states in O₂, the a¹Δ_g (1.0 eV) and the b¹Σ_g⁺ (1.68 eV) states.

Much more progress has been made on the behavior of balls in dc fields. A technique for making steady, nearly spherical combustion flames as

models for ball lightning has been developed, and by investigating such flames in dc fields of 0 to 2000 V/cm, considerable insight into the energy input processes to the ball has been gained. All predictions of the model have been confirmed, and it should be possible shortly to generate ball lightning by this technique.

Figure 17 shows the basic experimental setup. The flame is produced between two large field plates, and the current and voltage measured as a function of ball size, composition, etc. The following theoretical predictions have been verified.

1. Equal negative and positive currents linearly proportional to E^2 (Figure 18) and to diameter are drawn from the ball.

2. The ball has a net positive charge measured by pulsed current techniques.

3. Current emission is controlled by the positive ion space charge of the ball. If this is neutralized by a nearby conductor, much greater currents can be drawn.

4. The positive ion cloud leaving the ball expands because of electrostatic repulsion. The degree of expansion has been measured. It acts to collect charge from a much wider area than the

Figure 17. Apparatus for producing ball lightning.

Figure 18. Curves showing relation of current drawn from balls with diameter and voltage impressed.

ball diameter and channel it into the ball. This has been observed.

5. Strong electrohydrodynamic forces on the ball, comparable to those of gravity, have been observed.

J. POWELL, R. DOMISH

Cryogenic Power Transmission

A study was made of the economic and technical feasibility of transmission of large blocks of power for long distances via cryogenic transmission lines. The specific application considered is the transmission of 50,000 MW(e) blocks/line from power generation sites located in the lignite and subbituminous coal fields in Montana, Wyoming, and the Dakotas, to load centers in the West and East.

The estimated transmission cost is ~ 1.0 mil/kWh per 1000 miles. This is somewhat cheaper than conventional overhead lines, and much cheaper than conventional underground lines. Costs are based on a 17¢ capital charge and include refrigeration operating costs. Since the transmission line is dc, there are ac-dc conversion terminals. Conversion costs at the generation site are included in power generation costs; conversion costs at load points are not included.

The transmission line (Figure 19) is an insulated pipe (2 to 3 ft in diam) carrying a two-conductor return circuit cooled by liquid hydrogen.

Certain pure metals have very low electrical resistance at liquid hydrogen temperatures; typically, resistance at 20° K is one-thousandth that at 300° K. Thus I^2R line losses are much less; however, since some energy is required to operate a refrigeration cycle to keep the line cold, the *net* energy savings is not a factor of ~ 1000 , but a factor of ~ 20 .

Another important advantage of cryogenic transmission lines is the very large inherent capacity of a single line, much greater than that of conventional overhead or underground lines. This greatly reduces right-of-way costs. In this study, the 50,000-MW(e) design value reflects system limitations, not technical ones. The line could carry much more power; however, it would be too great a fraction of the U.S. capacity. For comparison, in 2000 AD when such lines might be used, 50,000 MW(e) will be the fraction of U.S. capacity as 5000 MW(e) is now.

The effect of various technical and economic parameters was studied. These include: type of conductor (aluminum and sodium), amount of

conductor, cost of conductor, liquid H₂ exit temperature, and line diameter. For each conductor type a set of parameters corresponding to minimum transmission cost was established. A typical result is shown in Figure 20. Transmission costs are relatively flat over a wide range of parameters since some factors tend to compensate. For example, a small conductor area has high refrigeration and low capital costs, while a large conductor area has the opposite.

Overall, sodium conductor transmission costs are slightly cheaper than those of aluminum; however, if aluminum were judged better on technical grounds, the differential would be small.

Figure 19. Cross section of 50,000-MW power transmission line.

Figure 20. Power transmission cost, mills/kWh · 1000 miles.

The optimum design for aluminum conductor transmission lines is: inlet H_2 temperature, $\sim 14^\circ K$; exit H_2 temperature, $\sim 20^\circ K$; refrigeration load, $\sim 20 \text{ kW(th)/mile}$; line diameter, 2.5 ft; distance between refrigeration stations, ~ 100 miles.

Besides power transmission, such a line can deliver large quantities (up to 4000 tons/day) of liquid H_2 to many points, for such uses as peaking power fuel, automobile fuel, chemical processes, and refrigeration. The liquid H_2 would be made at the power generation site.

Although this study was oriented toward block power transmission from the western coal fields, it is concluded that such cryogenic transmission lines are very attractive, both technically and economically, for long-distance transmission from any power site, coal and/or nuclear, and could form the backbone of a national power grid. J. POWELL

MHD Power Cycles

Most effort was devoted to cycles utilizing lignite and subbituminous fuels of the western coal fields. The fuel must be gasified before combustion in an MHD generator. This is done in a fluidized-bed gasifier operating on the carbon-steam reaction with the endothermic heat of reaction supplied from the sensible heat of the MHD exhaust.

The gasified fuel, primarily CO and H_2 , is burned with compressed air at 14 atm and fed to the MHD generator. Potassium seed (1% by volume) is used.

The overall cycle thermal efficiency is $\sim 55\%$, with an all MHD output. The compressors are driven with the steam generated by the sensible heat of the MHD exhaust.

The above results are based on calculations given in BNL 50187.

A more exact program is being written to calculate the composition and electrical conductivity of any given fuel that is gasified for an assumed degree of conversion. All important molecular species are included in this calculation. The effect of gasifier conversion efficiency on MHD generator design and cycle efficiency will be evaluated.

J. POWELL, M. STEINBERG

Publications

ABRAMS, L. AND SUTHERLAND, J.W. Infrared study of the radiolysis of CO_2 , NH_3 , and H_2 adsorbed on silica. (N) *J. Phys. Chem.* **73**, 3160-2 (1969).

ADLER, G., Editor, *Organic Solid State Chemistry*, Gordon and Breach, New York, 1969.

ADLER, G. Radiation induced reactions in crystalline amides. (A) *Acta Cryst.* **A25**, Pt. S3, S225 (1969).

ADLER, G. AND BAYSAL, B. Some solid-state aspects of vinyl polymerization in organic crystals. In *Organic Solid State Chemistry (Proc. Symp., Brookhaven National Laboratory, Upton, N.Y., March 1968)*, pp. 361-82, G. Adler, Editor, Gordon and Breach, New York, 1969.

AUSKERN, A.B. A model for the strength of cement-polymer and concrete-polymer systems. Informal Report BNL 13493.

AUSKERN, A.B. AND ARONSON, S. Electrical properties of (Th,U)C thorium carbide-uranium carbide solid solutions. (L) *J. Nucl. Mater.* **29**, 345-8 (1969).

BELLER, M., TUCKER, W., AND STEINBERG, M. Ozone synthesis in the Brookhaven Chemonuclear In-pile Research Loop. (A) *Trans. Amer. Nucl. Soc.* **12**, 498-9 (1969).

BELLER, M., TUCKER, W., STEINBERG, M., KLEIN, J., AND MANOWITZ, B. The Brookhaven Chemonuclear In-Pile Research Loop. (A) Presented at Amer. Nucl. Soc. Meet., San Juan, Puerto Rico, May 1969.

CHEN, H.T. AND HILL, F.B. Characteristics of batch and continuous equilibrium parametric pumps. To be presented at A.I.Ch.E. Meeting, Puerto Rico, May 1970.

CHEN, H.T. AND HILL, F.B. Radiation-induced polymerization in continuous stirred tank reactors. Presented at Amer. Inst. Chem. Engrs. Meet., New Orleans, March 1969.

COHEN, L.A., BALDWIN, R.A., TUTHILL, W.A., SCARLETT, C., AND SMITH, M.E. Simultaneous sampling for sulfur dioxide, sulfates, and sulfur hexafluoride in plumes. Presented at Symposium on Advances in Instrumentation for Air Pollution Control, Cincinnati, May 1969.

COLOMBO, P., GABARAIN, R.V.A., FONTANA, J., AND STEINBERG, M. A combined radiation and chemical catalyst system for improving polymerization rates. (A) Presented at Amer. Nucl. Soc. Meet. Radiation and Isotope Technology in Latin American Development, San Juan, Puerto Rico, May 1969.

DIETZ, R.N., SMITH, J.D., AND STEINBERG, M. Low temperature γ -irradiation synthesis of ozone. Presented at Amer. Chem. Soc. Meet., New York, Sept. 1969.

DIKEOU, J.T., KUKACKA, L.E., BACKSTROM, J.E., AND STEINBERG, M. Polymer concrete. A potential new construction material. Presented at Annu. Convention Amer. Concrete Inst., Chicago, April 1969; *ACI Journal* (in press).

FAUCITANO, A. AND ADLER, G. Annealing and recrystallization in the solid state polymerization in solid solutions of methacrylamide and isobutyramide. *J. Macromol. Sci.* (in press).

FAUCITANO, A., PEROTTI, A., AND ADLER, G. Reactions of gases with irradiated organic solids. II. Reactions of propionamide, *n*-butyramide, isobutyramide, and stearamide with oxygen and nitric oxide. In *Organic Solid State Chemistry (Proc. Symp., Brookhaven National Laboratory, Upton, N.Y., March 1968)*, pp. 297-321, G. Adler, Editor, Gordon and Breach, New York, 1969.

FERRARI, L.A. AND ZUCKER, M.S. Plasma betatron study. Informal Report BNL 13274.

- FERRARI, L.A. AND ZUCKER, M.S. Transient response of magnetic probes. *Rev. Sci. Instr.* **40**, 925-6 (1969).
- GALANTER, L., ROSEN, S., RIZZO, F.X. AND BARGIUK, L. GIRD - A Computer Program for Design of Shuffle-Dwell Gamma Irradiators. BNL 50148 (T-519), March 1969.
- HILL, F.B., FALLON, P.T., MULLER, A.C., AND ROTHBART, M.A. The application of chemical reactor design principles to problems of dosimetry in flow systems. In *Proc. Symp. Utilization of Large Radiation Sources and Accelerators in Industrial Processing, Munich, West Germany, Aug. 1969* (in press).
- KATZ, H. AND SEARS, J.T. Electric field phenomena in fluidized and fixed beds. *Can. J. Chem. Eng.* **47**, 50-3 (1969).
- KATZ, H. AND STEINBERG, M. Design of reformer for fossil-nuclear fueled MHD power cycle. Informal Report BNL 13285.
- KUKACKA, L.E., COLOMBO, P., STEINBERG, M., AND MANOWITZ, B. Concrete-polymer composites, potential materials for underwater applications. Presented at ASCE Conf. Environmental Engineering for the Ocean and Continental Shelf, Miami Beach, Dec. 1969.
- McNICHOLAS, J. Corrosion evaluation of oxygen electrode materials. *J. Electrochem. Soc.* (in press).
- MANOWITZ, B. Stable isotope measurement of sulfur pollutants. Presented at IEEE Nuclear Science Symposium, San Francisco, Calif., Oct. 1969.
- MANOWITZ, B. The atmospheric sulfur pollutants program at Brookhaven National Laboratory. (A) Presented at Isotopes Conference, Gatlinburg, Tenn., April 1969.
- MANOWITZ, B. AND TUCKER, W. Determination of sulfur isotope ratios in the atmospheric diagnostics program at BNL. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 1969.
- MANOWITZ, B. AND TUCKER, W.D. *The Atmospheric Diagnostics Program at Brookhaven National Laboratory: 2nd Status Report*. BNL 50206 (T-553) (in press).
- MANOWITZ, B., SMITH, M.E., NEWMAN, L., STEINBERG, M., AND TUCKER, W.D. An isotope ratio method for tracing atmospheric sulfur pollutants. Presented at Symposium on Research and Development Studies in Environmental Pollution, Washington, D.C., November 1969.
- MANOWITZ, B., STEINBERG, M., KUKACKA, L., AND COLOMBO, P. The development of concrete-polymer materials. In *Proc. Symp. Utilization of Large Radiation Sources and Accelerators in Industrial Processing, Munich, West Germany, Aug. 1969* (in press).
- METZ, D.J. Radiation-induced ionic polymerization. *Advan. Chem. Ser.* **91**, 202-18 (1969).
- METZ, D.J. AND BALLANTINE, D.S. Gamma radiation-induced ionic vinyl polymerization. *Ann. N.Y. Acad. Sci.* **155**, 468-81 (1969).
- METZ, D.J. AND KOPP, L.E. *Bibliography of Technical Publications and Reports of the Radiation Division, Brookhaven National Laboratory; July 1965 - June 1968 Inclusive*. BNL 50132 (L-407), Jan. 1969.
- OLTMANN, A. Brookhaven portable cesium development irradiator manual. Informal Report BNL 13506.
- PEROTTI, A., FAUCITANO, A., AND ADLER, G. Reactions of gases with irradiated organic solids. III. Reactions of propionamide, *n*-butyramide, isobutyramide, methacrylamide, valeramide, and stearamide with sulfur dioxide. In *Organic Solid State Chemistry (Proc. Symp., Brookhaven National Laboratory, Upton, N.Y., March 1968)*, pp. 323-42, G. Adler, Editor, Gordon and Breach, New York, 1969.
- PEROTTI, A., FAUCITANO, A., AND ADLER, G. Reaction of gases with irradiated organic solids. IV. Reactions of propionamide, *n*-butyramide, isobutyramide, valeramide and stearamide, with ethylene. *Mol. Cryst. Liquid Cryst.* (in press).
- POWELL, J. Ball lightning and experimental near-spherical flames in DC fields. Presented at Amer. Phys. Soc. Ann. Meet., Los Angeles, Nov. 1969.
- POWELL, J.R. AND FINKELSTEIN, D. Structure of ball lightning. *Advan. Geophys.* **13**, 141-89 (1969).
- RIZZO, F.X., GALANTER, L., AND KRISHNAMURTHY, K. *Tabulated Dose Distribution Data for Gamma Irradiator Design*. BNL 50147 (T-518) (in press).
- RIZZO, F.X., GALANTER, L., AND KRISHNAMURTHY, K. *Tabulated Dose Uniformity Ratio and Minimum Dose Data for Gamma Irradiator Design*. BNL 50145 (T-516) (in press).
- RIZZO, F.X. AND KRISHNAMURTHY, K. Cellulose acetate butyrate dosimeter. (A) *Trans. Amer. Nucl. Soc.* **12**, 61-2 (1969).
- ROTHBART, M.A., DAVIS, C.R., MULLER, A.C., AND HILL, F.B. Transit dose and source uniformity in a Sr^{90} - Y^{90} blood irradiator. Presented at Amer. Nucl. Soc. Meet., San Juan, Puerto Rico, May 1969.
- SATO, S. AND STEINBERG, M. Co^{60} gamma oxidation of aerated aqueous ammonium solutions. Informal Report BNL 13693.
- SATO, S. AND STEINBERG, M. Radiation chemical nitrogen fixation in air-water systems. Informal Report BNL 13692.
- SEARS, J.T. Effect of density and electron scavengers in nitrous oxide radiolysis. (N) *J. Phys. Chem.* **73**, 1143-6 (1969).
- SHENDALMAN, L.H. AND HILL, F.B. Some limiting radical concentration profiles in a batch photoreactor. (L) *Chem. Eng. Sci.* **24**, 909-11 (1969).
- SLATER, L.M. Calibration of a polonium-210 alpha source. Informal Report BNL 11926; *Int. J. Appl. Radiat. Isotop.* (in press).
- SLATER, L.M. Extraction of potassium, rubidium, strontium, and cerous polyiodides into nitrobenzene. *J. Inorg. Nucl. Chem.* **31**, 851-4 (1969).
- STEINBERG, M. Value and prospects of recovery of uranium from U.S. coal deposits. Presented at 65th Nat. Meet. Amer. Inst. Chem. Engrs., Cleveland, May 1969.
- STEINBERG, M. AND BELLER, M. Cost analysis of chemonuclear vs. electric discharge ozone production. Informal Report BNL 13691.
- STEINBERG, M. AND BELLER, M. Ozone synthesis for water treatment by high energy radiation. Presented at Amer. Inst. Chem. Engr. Annu. Meet., Washington, D.C., Nov. 1969.
- STEINBERG, M., KUKACKA, L.E., COLOMBO, P., KELSCH, J.J., MANOWITZ, B., DIKEOU, J.T., BACKSTROM, J.E., AND RUBENSTEIN, S. *Concrete-Polymer Materials, First Topical Report*. BNL 50134 (T-509) and USBR Gen. Rep. 41, Dec. 1968.

STEINBERG, M., KUKACKA, L.E., COLOMBO, P., AND MANOWITZ, B. Concrete-polymer composite materials. Presented at Amer. Nucl. Soc. Meet., San Juan, Puerto Rico, May 1969.

STEINBERG, M., POWELL, J., AND MANOWITZ, B. The western coal deposits: A national source of power. Presented at Intersociety Energy Conversion Engrg. Conf., Washington, D.C., Sept. 1969; BNL 50187 (T-542) (in press).

TAVEL, M.A. AND ZUCKER, M.S. Some quantitative results and new applications of the "phase-space time evolution" method. (A) *Trans. Amer. Nucl. Soc.* **12**, 158-9 (1969).

ZUCKER, M.S. AND FELDER, R.M. Angular distribution of charged particles emitted from a semi-infinite slab source. (A) Presented at Amer. Nucl. Soc. Meet., San Juan, Puerto Rico, May 1969.

Hot Laboratory Division

L.G. STANG JR.

Nuclear and Radiochemical Research

M. HILLMAN

CHEMICAL EFFECTS OF TELLURIUM ISOMER DECAY

The isomeric transitions of the isotopes ^{127m}Te and ^{129m}Te in aqueous solution were studied. Isomer decay is accompanied by conversion electrons, followed by the Auger cascade leaving the resulting atom in a highly charged state which reacts with its chemical environment. The proportions of the final oxidation states vary with the pH of the solution, with the initial oxidation state of the parent, and with the presence of oxygen.

Results, shown in Figure 1, were the same from ^{127m}Te and ^{129m}Te parents. The yield of Te(VI) is higher in the presence of oxygen under conditions where normally Te(IV) is not oxidized to Te(VI). This implies the formation of hot atom species or derivatives from them, which are easily oxidized to Te(VI) by oxygen, but not easily oxidized in its absence.

There is a marked difference between the results from parent Te(IV) and parent Te(VI). The Te(IV) yield is higher when starting with Te(IV) than when starting with Te(VI), and consequently the Te(VI) yield is higher when starting with Te(VI) than when starting with Te(IV). This implies a memory effect which in turn implies that the parent molecules are not totally disrupted by the Auger process, even though such disruption, or "explosion," has been observed for molecules in the gas phase. In solution, however, the disruption is partial, probably due to the nearby electrons of the solvent, which can rapidly replace the electrons lost by the molecules during the Auger process.

The amount of that product easily oxidized by oxygen to Te(VI) is independent of the nature of the parent. Figure 2 is a plot of the difference between the yield of Te(IV) formed in air and the yield of Te(IV) formed in the absence of air. The

independence of the nature of the parent implies that the easily oxidized species was a product of complete disruption of the molecule. A. WEISS

SZILARD-CHALMERS REACTIONS

The Szilard-Chalmers reactions of titanium compounds are under investigation as a continuation of the work done with organometallic compounds of zirconium and hafnium. The retention of ^{51}Ti in solid titanocene dichloride following the (n,γ) reaction on ^{50}Ti is 0.510 ± 0.021 , which is much higher than expected, but the retention in solution is 0.026 ± 0.0071 , which is about what was expected.

A. WEISS, C. SHEA

EXCITATION FUNCTIONS FOR TRITON INDUCED REACTIONS IN MAGNESIUM

A recent study of the reactions $^{26}\text{Mg}(t,p)^{28}\text{Mg}$ and $^{25}\text{Mg}(t,\alpha)^{24}\text{Na}$ showed that the excitation functions for the two reactions are almost exactly superimposable. Also, in the $^{24}\text{Mg}(t,n)$ reaction no measurable cross section leading to the high-spin ground-state isomer of ^{26}Al could be found, contrary to what might be expected on the basis of theoretical calculations and comparisons with isomer ratios found in other (t,n) reactions.

To obtain further insight into the problem, measurements were made of the cross sections for all observable nuclides produced in magnesium targets by tritons of energies up to 3.5 MeV. The five products indicated in Table 1 account for all the radioactive species except ^{26g}Al that can be produced from magnesium by (t,α) , (t,n) , or (t,p) reactions. The only major activity observed with a half-life longer than 0.5 min not attributable to the products listed is from annihilation radiation from ^{18}F , which had been produced by the (t,n) reaction on oxygen impurities in the target. Using a Ge(Li) detector, five of the products were measured in a single irradiation. Figure 3 shows the relative excitation functions for the five products. Note that they are exactly identical. This indicates

Figure 1. Yields of tetravalent ^{127g}Te and ^{129g}Te from tetravalent and hexavalent ^{127m}Te and ^{129m}Te as a function of ambient pH.

Figure 2. Differential yields of tetravalent ^{127g}Te and ^{129g}Te from ^{127m}Te and ^{129m}Te showing the fraction of Te(IV) that is independent of the presence or absence of oxygen. Yields formed in the presence of air are subtracted from the yields formed in deaerated solutions, and the difference is plotted as a function of pH.

that the reaction cross section in this energy region is dominated by the Coulomb barrier seen by the incoming triton, and the excitation functions can yield little information on details of the reaction mechanism. The shape of the excitation function agrees with that measured by Bishop for ^{24}Na and ^{28}Mg , but differs from that reported by Mori et al. [*Int. J. Appl. Radiat. Isotop.* **18**, 579-83 (1967)]. The reason for this discrepancy is unclear.

An appreciable amount of backward recoil was found for ^{24}Na and essentially none for ^{28}Mg . This is qualitatively consistent with both a direct reaction and a compound nucleus mechanism. A

Figure 3. Relative excitation functions for products from triton bombardment of magnesium.

Table 1

Summary of γ -Ray Peaks Detected in Triton Bombardment of Magnesium

Isotope	$t_{1/2}$	E , keV	Reaction
^{25}Na	1 min	390, 590, 980	$^{26}\text{Mg}(t,\alpha)^{25}\text{Na}$ [+ $^{25}\text{Mg}(t,^3\text{He})^{25}\text{Na}$]
^{28}Al	2.3 min	1780	$^{26}\text{Mg}(t,n)^{28}\text{Al}$
^{27}Mg	10 min	180, 840, 1013	$^{25}\text{Mg}(t,p)^{27}\text{Mg}$ [+ $^{26}\text{Mg}(t,d)^{27}\text{Mg}$]
^{24}Na	15 hr	2750	$^{25}\text{Mg}(t,\alpha)^{24}\text{Na}$ [+ $^{24}\text{Mg}(t,^3\text{He})^{24}\text{Na}$]
^{28}Mg	21 hr	400, 940, 1342, 1780	$^{26}\text{Mg}(t,p)^{28}\text{Mg}$

more quantitative study of this effect may, however, yield further information concerning the reaction mechanism.

J. GILAT, A. WEISS

RECOIL FROM THE $^{48}\text{Ca}(\alpha, n)^{47}\text{Ca}$ REACTION

Interest in reactions on ^{48}Ca continues because of the large neutron excess of ^{48}Ca compared to neighboring nuclides. Studies have shown that the ratio of neutron density to proton density is larger at the surface of the nucleus than in the interior. Generally, (α, n) reactions at alpha particle bombarding energies below the peak of the excitation functions are found to be produced by a compound nucleus mechanism. However, the relatively high neutron density in the nuclear surface may lead to direct interactions with neutrons at lower energies than would normally be observed. The range of the recoiling product, in this case ^{47}Ca , can yield information as to the amount of momentum transferred to the target nucleus by the projectile. A direct interaction is characterized in part by the alpha particle projectile imparting less momentum to the target nucleus than would occur in the case of compound nucleus formation, in which the full momentum would be transferred. Full momentum transfer would result in the product nucleus having a longer range. The analysis requires the comparison of the experimental

ranges with ranges calculated by collision theory for heavy ions in a stopping medium assuming full momentum transfer and correcting for recoil of evaporated particles. Experimental ranges shorter than ranges calculated from theory would indicate a contribution of a direct interaction mechanism.

For this analysis, the simplest range measurements require the target to be thicker than the range of the recoil product. However, targets of sufficient thickness have not been successfully produced by "molecular plating," although thin targets up to $100 \mu\text{g}/\text{cm}^2$ are uniformly distributed and are glassy in appearance. Nevertheless, qualitative information was obtained by determining the distribution of product between the thin target and the downstream catcher foil as a function of energy for constant thickness targets.

Figure 4 shows an improved excitation function for the $^{48}\text{Ca}(\alpha, n)^{47}\text{Ca}$ reaction as compared with that reported earlier [B. GORDON, *Nucl. Phys.* **A98**, 403-8 (1967)]. Figure 5 shows an increasing fraction of ^{47}Ca activity remaining in the target as the alpha particle bombarding energy increases. This crucial observation is interpreted as a small, but increasing contribution of a direct interaction mechanism. The average range of the recoiling

Figure 4. Excitation function of $^{48}\text{Ca}(\alpha, n)^{47}\text{Ca}$ reaction.

Figure 5. Recoil properties of ^{47}Ca produced from ^3He and ^4He reactions on $^{48}\text{Ca}(\text{NO}_3)_2$ targets. The thickness of the targets was a constant $90 \mu\text{g}/\text{cm}^2$.

product is seen to decrease with increasing energy, whereas one would expect the range to increase if either the mechanism were exclusively compound nucleus formation or the reaction proceeded with a constant distribution between direct interaction and compound nucleus mechanisms. The foils also were analyzed for ^{48}Sc produced in the $^{48}\text{Ca}(\alpha, p3n)^{48}\text{Sc}$ reaction, presumably by compound nucleus formation. In that case the fraction of ^{48}Sc remaining in the target decreases with increasing bombarding energy. The opposite behavior of ^{47}Ca product in the same foils and same irradiations lends confidence to the conclusions presented concerning the $^{48}\text{Ca}(\alpha, \alpha n)^{47}\text{Ca}$ reaction.

Irradiations using ^3He projectiles were performed to study the $^{48}\text{Ca}(^3\text{He}, \alpha)^{47}\text{Ca}$ reaction. Results indicate this reaction to be predominantly direct interaction because the large values for the fraction of activity remaining in the target indicate a low momentum transfer.

B. GORDON

FISSION RESONANCE INTEGRALS IN THE TRANSURANIUM REGION

An experimental study of fission resonance integrals in the transuranium region was begun with the investigation of the techniques of target preparation and data analysis. A foil on which is deposited a thin film of the transuranium nuclide target is placed on mica or Lexan, and is subsequently irradiated by neutrons. The fission particle tracks in the mica or Lexan are developed by etching the material with an appropriate solvent and are counted using an optical microscope. The relative (n, f) cross sections induced in ^{238}U and ^{235}U by 14-MeV neutrons were measured by track counting as a test of the method. The ratio $\sigma_f(235)/\sigma_f(238)$ for experiments using mica is 1.80 ± 0.16 and for experiments using Lexan is 1.96 ± 0.10 . These values are to be compared with the literature value of 1.99 (BNL 325). Lexan appears to be a better material for this purpose.

Plates of 1-in. diam would require a highly uniform deposit and relatively large amounts of material compared with the amount covering the areas to be counted. The molecular plates of uranium were uniform to within 3% of the average thickness. Plates of small areas of 1 to 2 mm in diam were successfully produced. These plates were not uniform; however, total area scanning which is possible on small plates disposes of the need for uniformity.

B. GORDON

TERNARY FISSION

An experiment is under way to measure the number of neutrons in coincidence with fission of ^{252}Cf into three sizable fragments [see BNL 50149 (S-71), pp. 80-1]. Only one to two events per week are detectable if the neutron background from binary fission is kept within reasonable limits, and to date only about ten events have been observed. The rate is somewhat lower than that expected, and the neutron distribution is indistinguishable from the distribution observed in binary fission. However, the statistics are still too poor to draw any conclusions.

M. MUGA, M. HILLMAN

NUCLEAR LEVEL DENSITIES

The ability to compute, and hence to predict, the closeness of the spacing between energy states in excited nuclei, i.e., their level densities, is important for the fundamental understanding of nuclear structure and the practical prediction of the direction and yields of complicated nuclear reactions. Three aspects of this problem dealing with the calculation of level densities are described here and a fourth, involving an application of the calculations, appears in the next section.

A computer program was written to literally add up the number of levels in a nucleus at a given spin and within a certain energy interval. The numbers were generated by systematically varying the arrangement of the nucleons among the single-particle levels. Seeger's rendition of Nilsson's levels for spherical nuclei was used, the spins were determined by $j-j$ coupling, and the energies, including pairing forces, were calculated by the BCS method. Most of the results were described in the previous report (*loc. cit.*, pp. 81-2).

In calculating the energy by the BCS method, the pairing parameter G is usually taken as being inversely proportional to the mass number A . We have found that this is incorrect and that G is better represented as inversely proportional to $A^{2/3}$. This is illustrated in Figure 6 by a plot of the best values of G that cause the calculated level densities to pass through the experimental neutron resonance points of 192 nuclides. There are still some unexplained difficulties for light nuclides and for nuclides near closed shells.

The calculations have now been extended to include nuclear deformation. The energy for a particular configuration of nucleons in their single

Figure 6. Illustration of the inverse dependence of the pairing parameter G on the two-thirds power of the mass number A .

Figure 8. Nuclear level densities (numerical calculation divided by commonly used algebraic approximation).

Figure 7. Numbers of energy states (on "contour lines") of ^{25}Al nucleus as a function of spin (ordinate), deformation (abscissa), and excitation energy (different sets of contours).

particle states are determined for various deformations from $\delta = -0.5$ to $+0.5$. The minimum energy and the deformation at that minimum are taken as the equilibrium energy and equilibrium deformation respectively. Thus far only the results of a test nuclide, ^{25}Al , have been obtained. These are illustrated in Figure 7. M. HILLMAN, J. GROVER*

The nuclear level densities calculated numerically show marked deviations from the commonly used algebraic form, based on an approximation to the model:

$$\rho(E, J) = \frac{K \{ \exp[2(aU)^{1/2}] \} (2J+1) \exp[-(J + \frac{1}{2})^2 \hbar^2 / 2\sigma^2]}{2\sigma^3 a^{1/4} U^{5/4}}, \quad (1)$$

where U is the effective excitation energy corrected for the effect of pairing, K is a numerical constant (usually $= \frac{1}{2}$), a is the level density parameter (related to the mean single particle level spacing), σ is the spin distribution parameter, and a rigid-body moment of inertia is usually assumed to apply. Figure 8 shows a contour plot of the ratio of the numerically calculated level density and that derived from Eq. (1). Over the region of E, J space covered, this ratio changes by about nine orders of magnitude.

Analysis shows that the main shortcoming of Eq. (1) is in the functional form of the J dependence of the level density, and that terms of higher order in J are required. An alternative form, derived by Lang [*Nucl. Phys.* **77**, 545-8 (1966)] automatically introduces the higher order terms

$$\left. \begin{aligned} \omega(E, M) &= \omega(E - M^2/2c, 0) \\ \omega(E, 0) &= K [\exp(2aU)] / (2c)^{1/2} a^{3/2} \epsilon^3 \\ \rho(E, J) &= \omega(E, M=J) - \omega(E, M=J+1) \\ c &= \langle m^2 \rangle g \end{aligned} \right\}, \quad (2)$$

where $\omega(E, M)$ is the density of states of excitation energy E and angular momentum M , and the rest of the notation follows that of Eq. (1). Figure 9 shows a comparison between the numerically calculated level density contours for ^{114}Cd and those obtained from Eq. (2). The agreement is gratifying and most of the deviations shown in Figure 8 are removed.

With properly chosen parameters equally good fits can be obtained to the numerically calculated

level densities for other nuclides. When the three parameters of Eq. (2) are fitted to reproduce the behavior of the numerical level densities, several systematic effects of the nuclear shell structure are revealed. For nuclides of $Z=35$ and $25 \leq N \leq 65$, the dependence of a on N is remarkably smooth and exhibits pronounced minima at the closed shells $N=28$ and $N=50$. The behavior of the spin parameter c is similar. The values of c are consistent with the interpretation $c = \langle m^2 \rangle g$, when the averaging is performed only over the subshells adjacent to the Fermi level. Since, in general, $\langle m^2 \rangle$ near the Fermi level is greater than a similar average taken over all occupied levels in the nucleus, $c > J_{\text{rigid}}$. J. GILAT

EVAPORATION CALCULATIONS

The effects (described in the preceding section) of the features of nuclear level density distribution on the de-excitation of excited nuclei at high angular momentum was investigated using the nuclear evaporation code GROGI [J.R. GROVER AND J. GILAT, *Phys. Rev.* **157**, 802-13 (1967)]. This program was modified appropriately to use calculated level densities for each of four nuclides of interest (for the emitting nucleus, and for neutron-, proton-, and α -daughter products, respectively) instead of a single approximate level density table used previously for all. The program was also

Figure 9. Comparison of numerically calculated nuclear level densities for ^{114}Cd with values based on a derivation by Lang. Dashed lines are the numerical calculation, solid lines are based on Eq. (2) with $a=10.10$, $c=57.87$ ($\approx 1.57 J_{\text{rigid}}$), and $\delta=1.50$.

*Chemistry Department.

Figure 10. Comparison of calculational techniques with experimental values of α particle emission.

Figure 11. Comparison of calculational techniques with experimental values of proton emission.

Table 2

Polymerization of Indium

Medium	[In] _{aq}	Constant assuming formation of	
Malate		Trimer	Tetramer
0.075 <i>M</i>	1.32 × 10 ⁻⁴	1.2 × 10 ⁶	7.2 × 10 ⁹
malate	2.65 × 10 ⁻⁴	1.5 × 10 ⁶	5.2 × 10 ⁹
+0.075 <i>M</i>	5.4 × 10 ⁻⁴	1.7 × 10 ⁶	3.8 × 10 ⁹
NaNO ₃	1.9 × 10 ⁻³	2.3 × 10 ⁶	3.0 × 10 ⁹
0.5 <i>M</i>	5.63 × 10 ⁻³	8.4 × 10 ²	1.2 × 10 ⁵
malate	8.92 × 10 ⁻³	1.1 × 10 ³	1.1 × 10 ⁵
Citrate		Trimer	Tetramer
0.2 <i>M</i>	9.40 × 10 ⁻⁵	3.2 × 10 ⁶	2.8 × 10 ¹⁰
citrate	1.62 × 10 ⁻⁶	3.9 × 10 ⁶	2.2 × 10 ¹⁰
	2.92 × 10 ⁻⁴	4.1 × 10 ⁶	1.6 × 10 ¹⁰
	5.24 × 10 ⁻⁴	4.3 × 10 ⁶	1.2 × 10 ¹⁰
	9.48 × 10 ⁻⁴	4.2 × 10 ⁶	8.7 × 10 ⁹
	1.70 × 10 ⁻³	4.2 × 10 ⁶	6.9 × 10 ⁹
	3.85 × 10 ⁻³	4.8 × 10 ⁶	5.9 × 10 ⁹
	8.12 × 10 ⁻³	5.5 × 10 ⁶	5.4 × 10 ⁹
Tartrate		Dimer	Trimer
0.02 <i>M</i>	3.50 × 10 ⁻⁶	4.1 × 10 ⁴	9.6 × 10 ⁹
tartrate	1.25 × 10 ⁻⁵	4.2 × 10 ⁴	3.6 × 10 ⁹
+0.13 <i>M</i>	5.34 × 10 ⁻⁵	4.0 × 10 ⁴	1.3 × 10 ⁹
NaNO ₃	2.10 × 10 ⁻⁴	5.5 × 10 ⁴	9.3 × 10 ⁸
0.1 <i>M</i>	2.60 × 10 ⁻⁵	5.5 × 10 ³	1.7 × 10 ⁸
tartrate	8.92 × 10 ⁻⁵	5.1 × 10 ³	6.1 × 10 ⁷
+0.05 <i>M</i>	2.74 × 10 ⁻⁴	3.8 × 10 ³	1.9 × 10 ⁷
NaNO ₃	9.46 × 10 ⁻⁴	4.2 × 10 ³	1.0 × 10 ⁷
	2.90 × 10 ⁻³	4.6 × 10 ³	6.0 × 10 ⁶

modified to include all possible reaction paths in the cascade instead of just the xn path. The transmission coefficients for particle emission are recalculated for each change of the charge of the emitting nucleus in the course of an evaporation cascade.

The calculations were applied to the de-excitation of ^{75}Br at 50.8 MeV, as produced by the following reactions:

These systems were studied experimentally by Miller et al., who measured the spectra of evaporated protons and α particles.

Two sets of calculations were carried out, one for the numerically calculated shell model level

densities and the other for a conventional level density, with $a=4/8$, and rigid-sphere moments of inertia. The relative probability of α -particle emission is strongly affected by the differences between the two-level density forms. Figures 10 and 11 show a comparison between the calculated and experimental alpha and proton spectra, respectively. It is clear that the rigid body assumption overestimates the α -particle emission by a factor of two or more, whereas the numerical level density leads to a satisfactory agreement. The proton spectrum, on the other hand, is quite insensitive to the level density assumptions, and both calculations yield comparable agreements with the experiments. The results for the ^{64}Zn - ^{11}B system are quite similar.

Regretfully, the data are not sufficient for a clear-cut decision to be made between the two types of level density. The introduction of a number of reasonable (though *ad hoc*) assumptions to the algebraic form can give even better agreement. To distinguish between the two level density schemes, additional experimental information would have to be provided, e.g., cross sections of certain products that are predicted by calculations to differ quite appreciably for the two input schemes.

J. GILAT, J. GROVER*

Analytical Chemistry Research

L. NEWMAN

MIXED-METAL COMPLEXES

The interactions of In(III) with U(VI) and citric, malic, and tartaric acids were studied. Before investigating the formation reaction of the mixed-metal complex (mmc), it was necessary to obtain information on the polymerization of both In(III) and U(VI) in the presence of these acids, since these are competing reactions with the mmc formation. Formation constants were available in the literature for the U(VI) dimerization reactions with citric, malic, and tartaric acids. These constants indicated that no U(VI) dimerization would occur at the uranium concentrations used in our experiments.

Using solvent extraction techniques, the In(III) polymerization was studied with citric, malic, and tartaric acids. Table 2 shows the resultant polym-

erization constants calculated from the simple model

$$n[\text{In}] = [\text{In}]_n$$

From these results, it was concluded that the average number of indium ions per polymer complex is between three and four for the malate and citrate systems. The tartrate complex is apparently a dimer, since no trends in the calculated dimerization constants are obvious.

Spectrophotometric data clearly showed the formation of a mmc between In(III), U(VI), and citric, malic, and tartaric acids. The existence of a mmc with citramalic acid was also demonstrated. These experiments have also shown that the ratio of In(III) to U(VI) in the mmc is 1:1.

Spectrophotometric and pH titration experiments demonstrated the number of ligands in the mmc to be two.

Data to be used in the calculation of the formation constants for the mmc's were obtained using solvent extraction techniques over large concentration ranges of In(III), U(VI), and the hydroxycarboxylic acids. Calculations of the K_{mmc} based on the reaction

where L represents the hydroxycarboxylate ligand, failed to give constant values.

Solvent extraction methods were used to investigate the U(VI) polymerization with citric, malic, and tartaric acids. Contrary to what the dimerization constants found in the literature led us to believe, U(VI) dimers are present in all our mmc studies. Calculations of the K'_{mmc} , based on the equation

which was revised to include the U(VI) dimerization yielded the values shown in Table 3.

Work is continuing on other combinations of mmc's. The following combinations have been shown to form mmc's either spectrophotometrically or by solvent extraction: In(III)-Cr(III), In(III)-Fe(III), In(III)-Al(III), In(III)-Cu(II), and U(VI)-Cr(III). The combinations Ce(III)-In(III), Ce(III)-U(VI), and Al(III)-U(VI) formed little or no mmc.

*Chemistry Department.

Table 3
Mixed-Metal Complex Formation Between Indium and Uranium

$n[\text{In}]_n$	$[\text{InL}_2]$	$2[\text{U}_2\text{L}_2]$	$[\text{mmc}]$	$[L]$	K'_{mmc}
<u>Malate</u>					
	5.1×10^{-6}	7.3×10^{-5}	1.3×10^{-4}	1.0×10^{-2}	41
	1.6×10^{-5}	6.4×10^{-5}	1.4×10^{-4}	2.0×10^{-2}	30
	1.8×10^{-5}	7.3×10^{-4}	2.8×10^{-4}	4.0×10^{-2}	32
	1.1×10^{-4}	4.4×10^{-4}	5.3×10^{-4}	7.5×10^{-2}	25
	5.9×10^{-5}	1.6×10^{-4}	2.3×10^{-4}	7.5×10^{-2}	33
	3.3×10^{-5}	8.9×10^{-5}	1.0×10^{-4}	7.5×10^{-2}	25
	2.5×10^{-4}	5.4×10^{-4}	4.7×10^{-4}	1.5×10^{-1}	25
<u>Citrate</u>					
	1.0×10^{-7}	4.8×10^{-6}	9.8×10^{-6}	1.0×10^{-2}	610
	2.1×10^{-7}	4.8×10^{-6}	9.5×10^{-6}	2.0×10^{-2}	570
	1.4×10^{-7}	1.0×10^{-5}	9.6×10^{-6}	2.0×10^{-2}	600
	2.9×10^{-7}	1.1×10^{-5}	9.4×10^{-6}	4.0×10^{-2}	560
	4.1×10^{-7}	5.1×10^{-4}	9.1×10^{-6}	4.0×10^{-2}	560
	6.7×10^{-7}	1.1×10^{-5}	9.3×10^{-6}	8.0×10^{-2}	480
	8.6×10^{-7}	5.4×10^{-6}	8.3×10^{-6}	8.0×10^{-2}	470
	1.3×10^{-4}	8.5×10^{-5}	8.1×10^{-4}	2.0×10^{-1}	170
	1.2×10^{-6}	9.0×10^{-4}	9.8×10^{-5}	2.0×10^{-1}	760
	2.7×10^{-6}	8.9×10^{-3}	9.9×10^{-4}	2.0×10^{-1}	780
	4.8×10^{-6}	2.0×10^{-3}	9.9×10^{-4}	2.0×10^{-1}	1400
	4.0×10^{-5}	9.8×10^{-5}	8.9×10^{-4}	2.0×10^{-1}	640
	2.6×10^{-5}	6.7×10^{-4}	2.9×10^{-4}	2.0×10^{-1}	1200
	7.6×10^{-7}	8.6×10^{-4}	9.8×10^{-5}	2.0×10^{-1}	1300
<u>Tartrate</u>					
1.2×10^{-6}	3.6×10^{-6}	2.3×10^{-5}	2.0×10^{-5}	2.0×10^{-2}	33
3.2×10^{-6}	6.0×10^{-6}	4.3×10^{-5}	4.9×10^{-5}	2.0×10^{-2}	36
8.5×10^{-6}	1.0×10^{-5}	7.6×10^{-5}	1.1×10^{-4}	2.0×10^{-2}	36
1.8×10^{-5}	4.0×10^{-5}	1.1×10^{-4}	8.1×10^{-5}	1.0×10^{-1}	28
4.3×10^{-5}	6.9×10^{-5}	2.0×10^{-4}	1.8×10^{-4}	1.0×10^{-1}	26
1.3×10^{-4}	1.3×10^{-4}	4.4×10^{-4}	5.4×10^{-4}	1.0×10^{-1}	29

Fe(III) malate polymerization was studied using solvent extraction methods, and a trimerization reaction was observed. The dependency of the trimerization constant on the malate concentration indicated an apparent trimer composition of $\text{Fe}_3\text{Mal}_{4.5}$. Similar nonintegral ligand dependencies have been observed in related systems.

A. ADIN, P. KLOTZ, L. NEWMAN

MIXED-LIGAND COMPLEXES

The constants for the formation of mixed-ligand complexes of Ni(II) with bromide and chloride in acetonitrile have been measured. They are

Tetraethylammonium halides were employed to adjust the total halide concentration to 0.35 and also maintain the ionic strength at that value. Contrary to most previous studies dealing with mixed-ligand complexes, those with nickel are

formed in less than statistical amounts. The ratio of the formation constants for NiCl_4^{-2} and NiBr_4^{-2} are calculated as $\log \beta_{4\text{Cl}}/\beta_{4\text{Br}} = 7.30 \pm 0.08$. This is a clear indication that nickel(II) is a class (a) or, hard acceptor with respect to the halides as donors in acetonitrile solvent.

The stepwise formation of the tetracoordinated halide complexes were measured as

$$\log K_{4\text{Cl}} = 3.05 \text{ for } \text{NiCl}_3^- + \text{Cl}^- = \text{NiCl}_4^{-2}$$

$$\text{and } ^* \log K_{4\text{Br}} = 1.80 \text{ for } \text{NiBr}_3^- + \text{Br}^- = \text{NiBr}_4^{-2}.$$

T. GILBERT, L. NEWMAN

IRON-TTA KINETICS

Under appropriate conditions the rate of extraction of Fe^{+3} into benzene by thenoyltrifluoroacetone (HTTA) was shown to be governed by the rate of formation of FeTTA^{+2} in the aqueous phase. It was shown that Cl^- catalyzes the extraction of Fe^{+3} by an increased rate of formation of FeTTA^{+2} from FeCl^{+2} . The formation of FeTTA^{+2} occurs via inverse acid-dependent and acid-independent paths. Complex formation is catalyzed by chloride ions because of the reaction

At 24°C and ionic strength 1.0,

$$k_{\text{Cl}} = 20 \text{ M}^{-1} \text{ sec}^{-1}.$$

From the lack of an acid dependence of k_{Cl} , the inferred mechanisms for the uncatalyzed formations of FeTTA^{+2} are

At 24°C and ionic strength 1.0,

$$k_i = 5 \times 10^{-1} \text{ M sec}^{-1},$$

$$k'_a = 4.4 \times 10^2 \text{ M}^{-1} \text{ sec}^{-1}.$$

The rate of dissociation of FeTTA^{+2} increases slightly at higher $[\text{H}^+]$. The dissociation is catalyzed by Cl^- and this reaction shows a marked direct hydrogen ion dependence.

A. ADIN,
L. NEWMAN

ELECTROCHEMISTRY

A variety of theoretical electrochemical problems have been treated (see Publications). Consid-

eration of electromigration in electrochemical processes may permit determination of charge on unstable species (e.g., distinguishing between the cation radical and the free radical in the electrochemical oxidation of organics). The dynamics of charging the electrode double layer have also been considered. The predictions are in good accord with the experimental work of Anson (Cal. Tech.).

Studies of the electrochemistry of the pertechnetate ion (TcO_4^-) in aqueous alkaline media showed that technetate ion (TcO_4^{-2}) is produced as an intermediate when gelatin (a surfactant) is present in solution. The technetate ion undergoes rapid disproportionation with a rate constant $k = 1.5 \times 10^5 \text{ liters moles}^{-1} \text{ sec}^{-1}$. The rate is independent of temperature and pH (>7). The indicated diffusion control is not unreasonable if the coulombic repulsion of the reacting charged species is considered.

Most recent efforts have been directed toward elucidation of the chemistry of the ligand inert chromium(III) hexacyanide ion in aqueous alkaline media. The electrochemical reduction product is the ligand labile chromium(II) hexacyanide in equilibrium with aquo-substituted species. Two of these species, the tetracyano-diaquo-chromium(II) and the tricyano-triaquo-chromium(II) appear to be most reactive in electron transfer reactions with chromium(III) hexacyanide. The result is the production of predominantly tetracyano-diaquo-chromium(III) and tricyano-triaquo-chromium(III). Elucidation of the kinetics and mechanisms of these reactions is still in the preliminary stage.

S. FELDBERG, L. JEFTIC

AIR POLLUTION

The preparation of SO_2 samples for $^{34}\text{S}/^{32}\text{S}$ isotope ratio analysis requires at one stage combusting Ag_2S to SO_2 at $>90\%$ yields to insure isotopic integrity. Using 1 to 10-mg samples of SO_2 , the effects of temperature, pressure, flow rate, etc., on these yields were established with the assumption that the isotope ratios remained intact. After the isotope ratio mass spectrometer was installed, 1-mg samples were found to give consistent $^{34}\text{S}/^{32}\text{S}$ ratios about 0.7 to 1.0 parts per thousand lower than those of 10-mg samples. Reinvestigation of parameters to correct this discrepancy gave the following average differences between 10 and 1-mg samples:

Quartz combustion tube: 96% N₂, 6% O₂ atmosphere [*Geochem. J.* 1, 35-42 (1966)]

1200°C	0.4 ₁ per thousand
1250°C	0.5 ₆ per thousand
1300°C	0.7 ₇ per thousand

Quartz combustion tube: O₂ atmosphere

1250°C	0.5 ₈ per thousand
1300°C	0.2 ₆ per thousand

Zirconia combustion tube: O₂ atmosphere

1300°C	0.1 ₁ per thousand
1350°C	0.1 ₅ per thousand

New parameters were established which minimized these errors. The quartz combustion tubes, which vitrified rapidly at 1300°C with accompanying adverse effects upon the isotope ratios, were replaced by the more resistant zirconia tube.

A sampling train has been fabricated and employed to obtain SO₂ and SO₃ concentrations in power plant flue gas. A probe, containing a quartz wool plug to retain particulates, is inserted into the breach connection of the plant. As the gas is withdrawn, SO₃ is condensed at 150° to 180°F in a thermostated bath followed by SO₂ absorption in NaOH-H₂O₂ solution. Aerosol SO₃ retained on the quartz wool is separated from water-soluble particulate sulfate by extraction with isopropyl alcohol. Measurements have been made at BNL and LILCO's Northport plant. Amounts of SO₃ and SO₂ collected have been experimentally verified to be proportional to sampling time. New equipment is under development to take accurate cross sections of aerosol and solid particulates by isokinetic sampling.

A sensitive spectrophotometric method using barium chloranilate has been adopted for measuring low soluble sulfate in representative strips of Fiberglas prefilters of high-velocity air filter packs. Ground level experimental air samples taken at BNL and LaGuardia Airport disproved any significant catalytic oxidation by the glass fibers of SO₂ to SO₃. Collected sulfate was generally proportional to sampling time, although longer samples seemed to give disproportionately higher values, especially in high particulate areas. A possible explanation for this phenomenon may be the catalysis of SO₂ to SO₃ on the larger accumulated particulate surfaces of the filter.

J. FORREST,
L. NEWMAN

Medical Radionuclides

P. RICHARDS

MAGNESIUM-28

Magnesium-28 is an important tracer in medical and biological research because magnesium is considered to be a controlling cation in many biochemical processes, and ²⁸Mg is the only isotope of magnesium with a half-life sufficiently long for studying the physiological role of this element. In 1968 the production of ²⁸Mg was improved by bombarding the end of an enriched ²⁶Mg metal rod with 3.5-MeV tritons accelerated in the Van de Graaff generator and recovering the activity by etching a thin layer from the end of the rod. However, operating experience indicated that the chemical etching technique was erratic, whereas reproducible and satisfactory results were achieved by the mechanical removal of a very thin layer (i.e., 0.0015 in.). In this method the irradiated end of the rod is gently rubbed on the flat surface of a sintered glass disc using a constant force for a set period of time. Specific activities of 250 to 500 mCi ²⁸Mg/g of Mg are produced routinely, and 1.4 Ci/g was achieved in a special case.

J. BARANOSKY, G. WALKER

FLUORINE-18

Fluorine-18 either as fluoride ion or as a complex appears to be the best agent for visualizing bone pathology by scanning techniques. Millicurie amounts are needed for collaborative studies with the BNL Medical Research Center. An early Brookhaven process involving thermal neutron irradiation of Li₂CO₃ had been successfully used to produce multimillicurie amounts of ¹⁸F locally and adopted by others to provide for the worldwide distribution of this 110-min isotope. However, the shutdown of the Brookhaven Graphite Research Reactor and the availability of Van de Graaff-accelerated 3.5-MeV tritons prompted a study of the feasibility of producing ¹⁸F by the triton irradiation of distilled water with the use of the ¹⁶O(*t,n*)¹⁸F reaction directly.

A simple arrangement provides for irradiating a liquid water target that is cooled by other (high pressure) water and separated from the triton beam by a 0.18-mil Havar foil; an air space over the target connects to a catalytic chamber for re-

Figure 12. Thick target (H_2O) production rate of ^{18}F from the $^{16}\text{O}(t,n)^{18}\text{F}$ reaction as a function of incident triton energy.

combining radiolysis gases. Beam currents as high as $10\ \mu\text{A}$ produce no buildup of pressure in the target chamber. Yields are shown in Figure 12.

Postirradiation purification involves evaporating the target water to dryness in a rotating vacuum evaporator to remove any tritium and taking up the ^{18}F -containing residue in sterile saline solution. No other radioactive contaminants have been detected in the product. The chemical form of the fluorine activity was determined by gel chromatography to be fluoride ion.

P. RICHARDS,
J. BARANOSKY

IRON-52

Because of its short (8.2 hr) half-life and the fact that it emits positrons which permit coincidence detection of the annihilation gammas, ^{52}Fe is a useful tracer for iron in medical research and diagnosis. For example, collaborative studies with the Brookhaven Medical Research Center require ^{52}Fe for visualization of functioning bone marrow and for labeling molecules of potential biological and medical interest. However, the low cross section of the conventional $^{50}\text{Cr}(\alpha, 2n)^{52}\text{Fe}$ reaction and the low (4.3%) natural abundance of ^{50}Cr require the use of enriched ^{50}Cr even to produce only tenths of millicuries; moreover, the enriched target, aside from being expensive, is available only as the oxide, a form that is difficult to manipulate chemically.

The $^{52}\text{Cr}(^3\text{He}, 3n)^{52}\text{Fe}$ reaction using electroplated natural chromium (84% ^{52}Cr) targets and the rebuilt BNL cyclotron as a source of the ^3He

beam has been studied, and preliminary experiments indicate the possibility of producing $\sim 100\ \mu\text{Ci}/\mu\text{Ah}$, a yield that certainly merits further study. A target for use in the internal beam of the cyclotron has been designed and fabricated, a post-irradiation chemical process has been tried out satisfactorily, and the excitation function is being measured to see if the target design can be optimized.

M. GREENE, E. LEBOWITZ

BROOKHAVEN LINAC ISOTOPE PRODUCER

A preliminary study showed the feasibility of producing significant quantities of a wide variety of useful isotopes by spallation reactions induced by 200-MeV protons that would be accelerated in the new Linac being constructed as a proton injector for the Alternating Gradient Synchrotron. A computer program that will calculate the activity of any isotope induced by spallation of any other isotope formed the basis for a report [BNL 50195 (T-547)] that showed that the 200-MeV proton energy available was virtually ideal for practical production purposes. Accordingly, construction of the Brookhaven Linac Isotope Producer (BLIP) was proposed. It consists of a water-filled tank arranged so that the proton beam enters at the bottom and targets can be manipulated into and out of the beam using the water as an inexpensive transparent flexible removable radiation shield. The irradiated targets will be removed and processed in existing facilities in the Hot Laboratory. Target design, cooling, neutron shielding, and structural activation are being studied.

L. STANG, JR., P. RICHARDS, E. LEBOWITZ,
C. WAIDE,* M. HILLMAN

ULTRA-SHORT-LIVED RADIONUCLIDES

Ultra-short-lived isotopes appear potentially useful in such diagnostic procedures as producing images of veins, the chambers of the heart, and the lungs. In such a system a radiopharmaceutical can be infused into the patient directly from an isotope generator and the region or organs of interest imaged by means of a scintillation camera or scanner. When a radioisotope with a half-life of a few seconds is injected intravenously most of the activity dies away during the first complete transit of the circulatory system allowing visualization of

*Engineering Division.

the area of interest with a minimum of background interference. Preliminary work of this type has been reported by Yano [*Int. J. Appl. Radiat. Isotop.* 16, 153-6 (1965)].

A generator has been developed for supplying 40-sec ^{109m}Ag formed from its long-lived parent ^{109}Cd (453-day half-life). The generator consists of a small glass column containing Dowex-50 $\times$ 8 cation exchange resin, 100-200 mesh, on which the cadmium activity is adsorbed. The ^{109m}Ag activity is eluted with 0.05 *M* HCl. Low contamination levels ($<10^{-3}$ %) have been achieved by loading the generator in such a way that the parent ^{109}Cd activity is spread over a larger volume thereby reducing radiation damage to the resin.

A full-scale ^{109m}Ag generator and infusion system was assembled for evaluation in phantom and animal studies. Figure 13 shows the generator, dual pumping system for eluting the generator and pumping buffer solution, an in-line pH meter, and a sterilizing filter. The generator was prepared using ~ 300 mCi of ^{109}Cd , but preliminary indications show that several times as much activity on the generator would be necessary for optimum application. Unfortunately the ^{109m}Ag system is not ideal because of the somewhat low energy of the

photon (88 keV) and the fact that the photon has an abundance of only 5%. As the nuclides become available other systems will be investigated and separation systems developed.

P. RICHARDS, M. GREENE, J. BARANOSKY

^{99m}Tc -DTPA CHELATE

A ^{99m}Tc -labeled chelate of diethylenetriamine pentaacetic acid (DTPA) was studied intensively to determine its chemical and biological stability and optimum method of preparation. This material, previously reported by Richards and Atkins [*Jap. Nucl. Med.* 7, 165-70 (1968)] as potentially useful for brain scanning and kidney studies, was found to be better than the pertechnetate form for brain scanning because the chelate does not accumulate in any specific organ, whereas accumulation of the pertechnetate in the salivary glands and the choroid plexus frequently causes problems in brain scans.

The procedure developed recovers 80 to 90% of the initial ^{99m}Tc in the chelate form and provides a concentrated form of product in a sterile physiological saline solution free of any unbound activity.

Stability studies using gel chromatography show 73% decomposition in 24 hr in air but only 31% decomposition in 24 hr in a nitrogen atmosphere. Since the material is usually used within a few hours of its preparation, this stability is satis-

Figure 13. Silver- ^{109m}Ag generator and prototype infusion system.

Table 4

Magnesium-28 Shipped (μCi)

	1968	1969
Jan	250	550
Feb	1400	300
Mar	600	450
Apr	^a	350
May	600	900
June	950 ^b	750
July	^b	950
Aug	500 ^c	300
Sept	—	600
Oct	200 ^c	800
Nov	400 ^c	800
Dec	250 ^c	1000

^aBGRR shutdown caused cancellation of 7 shipments.

^bNote that the BGRR was shut down permanently on June 10, 1968.

^cVan de Graaff-produced.

factory, even in air. The stability of the labeled chelate during the first hour after intravenous injection is noteworthy. Of the ^{99m}Tc activity found in the urine, >98% was still present in the chelate form, while the ^{99m}Tc distribution in blood plasma was 80 to 90% still as the chelate, 5 to 10% associated with one of the serum proteins, 1 to 4% in a molecule not yet identified but intermediate in size between the chelate and the pertechnetate ion, and <3% in the form of uncomplexed pertechnetate ion. Essentially no activity appears in the red cells. It is interesting to compare this distribution with that obtained when the activity is administered not as a labeled chelate but rather as the pertechnetate ion, in which case >99% of the ^{99m}Tc that remains in circulation 1 hr after administration is still as the pertechnetate ion and only <1% appears as a complex with serum proteins.

P. RICHARDS, J. BARANOSKY

Hot Laboratory Operations

P. RICHARDS

ISOTOPE PRODUCTION

^{28}Mg , the only radioisotope produced for commercial distribution during the year, was produced routinely once a month by bombarding ^{26}Mg with tritons accelerated in the Van de Graaff generator. Table 4 reflects the slow but steady increase in demand for this new high-specific activity material. The importance of this tracer in biomedical studies is indicated by the number of shipments made to Canada and England and the receipt of inquiries from as far away as Australia and Japan.

J. BARANOSKY, G. WALKER, A. MACAULAY

SPECIAL FABRICATION

Several additional improved lead focusing collimators and a number of special phantoms were designed and fabricated for use in collaborative studies at the Brookhaven Medical Research Center.

C. KIESLING, P. RICHARDS

RADIOGRAPHY

A total of 1405 radiographs were produced for various groups around the site during the year. The major work load continues to be the inspec-

tion of welds in pressure vessels and piping. Radiography was also used to locate electric power conduits in several concrete floors and a fault in the shielding of a new cesium irradiator fabricated off-site. Quality control inspection of drift-tube stems for the AGS continued from last year.

J. AUSTIN, H. RUGE

NEUTRON GENERATOR

The 14-MeV neutron generator provided service irradiations for the Medical, Chemistry, Instrumentation, and Physics Departments. The major use of the machine was for a whole-body activation analysis experiment for the Brookhaven Medical Research Center, the purpose of which is to develop an improved method for determining whole-body calcium and, at a later date, possibly certain other elements. Many preliminary dosimetry runs using foils and phantoms were made prior to exposing about 13 patients.

Several chemical compounds were irradiated at various levels for the Chemistry Department, and

Table 5

Summary of Liquid Waste Operations

	Dec. 26, 1967 to Dec. 25, 1968	Dec. 26, 1968 to Dec. 25, 1969
"F" waste released to sewer		
Gal	971,030	937,860
Average activity level, Ci/ml	2.46×10^{-12}	1.2×10^{-12}
Total activity, mCi	9.05	4.30
"D" waste inventory		
Gal start	65,015	50,795
Gal received	167,470	131,180
Gal to evaporator	181,690	54,830
Gal end	50,795	127,145
	1968 ^b	1969 ^b
Waste concentration operations		
Waste to evaporator ^a	181,690	60,955
Concentrate ^a	1,959	870
Volume reduction	93:1	70:1
Activity in mC, feed	4,494	3,822
Activity in mC, distillate	2.97	1.05

^aGallons.

^bNominal years (all other periods are exact years as shown).

a series of low-level dosimetry runs were made for the Health Physics Division as part of the summer training program.
J. AUSTIN

LIQUID WASTE OPERATIONS

The inventory of radioactive liquid waste was 127,145 gal at the end of the year compared with 50,795 gal at the beginning. A total of 54,830 gal were processed by the waste concentrator during the year. Table 5 summarizes the liquid waste operations.

J. BARANOSKY, A. MACAULAY,
W. AUSTIN, W. GRAY, G. WALKER

Publications

- ADIN, A., KLOTZ, P., AND NEWMAN, L. Mixed-metal complexes between indium(III) and uranium(IV) with malic, citric, and tartaric acids. Submitted to *Inorg. Chem.*
- ATKINS, H.L., HAUSER, W., NELSON, K.G., AND RICHARDS, P. Technetium-99m-DTPA: A new radiopharmaceutical for brain and kidney scanning. *Radiology* (in press).
- ATKINS, H.L., HAUSER, W., AND RICHARDS, P. Factors affecting distribution of technetium-99m sulfur colloid. *J. Reticuloendothel. Soc.* (in press).
- ATKINS, H.L., HAUSER, W., RICHARDS, P., AND ROBERTSON, J.S. Analysis of the optimum conditions for data display and image perception in photoscanning. In *Medical Radioisotope Scintigraphy (Proc. Symp., Salzburg, Austria, Aug. 1968)*, pp. 759-70, IAEA, Vienna, 1969.
- ATKINS, H.L., RICHARDS, P., AND HAUSER, W. Five years' experience with ^{99m}Tc -S colloid. (A) *J. Nucl. Med.* **10**, 386-7 (1969).
- FELDBERG, S.W. Digital simulation: A general method for solving electrochemical diffusion-kinetic problems. In *Electroanalytical Chemistry*, Vol. 3, p. 199, A. J. Bard, Editor, Marcel Dekker, New York, 1969.
- FELDBERG, S.W. Theory of regenerative second-order mechanisms in chronoamperometry. The paradox of disproportionation. *J. Phys. Chem.* **73**, 1238-43 (1969).
- FELDBERG, S.W. Theory of relaxation of the diffuse double layer following coulometric charge injection. *J. Phys. Chem.* (in press).
- GILAT, J. Algebraic approximation of the combinatorial calculation of nuclear level densities. *Phys. Rev.* (in press).
- HARBOTTLE, G. AND HILLMAN, M. Szilard-Chalmers processes for isotope production. Chapter in *IAEA Manual of Radioisotope Production* (in press).
- HAUSER, W., ATKINS, H.L., AND RICHARDS, P. Lymph node scanning with ^{99m}Tc -sulfur colloid. *Radiology* **92**, 1369-71 (1969).
- HILLMAN, M. AND GROVER, J.R. Shell model combinatorial calculations of nuclear level densities. *Phys. Rev.* (in press).
- HILLMAN, M. AND WEISS, A.J. Chemical effects of isomeric decay of ^{127m}Te and ^{129m}Te in aqueous solution. Presented at 158th Nat. Amer. Chem. Soc. Meet., New York, Sept. 1969.
- HILLMAN, M., WEISS, A.J., AND HAHNE, R.M.A. Szilard-Chalmers reactions of zirconocene dichloride and of hafnocene dichloride. *Radiochim. Acta* (in press).
- KIEFER, R.L. AND HILLMAN, M. Relative yields of ^{58g}Co , ^{58m}Co , and ^{56}Co produced by low-energy tritons. *J. Inorg. Nucl. Chem.* **31**, 915-17 (1969).
- KISSEL, G. AND FELDBERG, S.W. Disproportionation of the technetate ion in aqueous alkaline media: An electrochemical study. *J. Phys. Chem.* **73**, 3082-8 (1969).
- MARCOUX, L.S., ADAMS, R.N., AND FELDBERG, S.W. Dimerization of triphenylamine cation radicals: Evaluation of kinetics using the rotating disc electrode. *Ibid.* 2611-14.
- NELSON, R.F. AND FELDBERG, S.W. Chronoamperometric determination of the rate of dimerization of some substituted triphenylamine cation radicals. *Ibid.* 2623-26.
- PAPOUCHADO, L., ADAMS, R.N., AND FELDBERG, S. Anodic catalytic currents involving cyanide ion. *J. Electroanal. Chem.* **21**, 408-10 (1969).
- RICHARDS, P. Technetium-99m - An inexpensive route to a versatile radioisotope. In *Proc. Meet. Radiation and Isotope Technology in Latin American Development, San Juan, Puerto Rico, May 1969* (in press).
- RICHARDS, P. AND O'BRIEN, M.J. Rapid determination of ^{99}Mo in separated ^{99m}Tc . *J. Nucl. Med.* **10**, 517 (1969).
- STANG, L.G. JR. *Radionuclide Generators: Past, Present, and Future*. Presented at 3rd Annu. Meet. Sociedad Mexicana de Medicina Nuclear, Puebla, Mexico, April 1969; BNL 50186 (T-541), April 1969.
- STANG, L.G. JR., HILLMAN, M., AND LEBOWITZ, E. *The Production of Radioisotopes by Spallation*. BNL 50195 (T-547), August 1969.

Metallurgy and Materials Science Division

D.H. GURINSKY

Sodium Technology

COMPARATIVE CLADDING CORROSION TESTS

C.J. KLAMUT

The general objective of this work was to evaluate potential fuel cladding materials for advanced high-temperature LMFBRs. The tests were carried out so as to generate comparative corrosion data for these materials using the behavior of stainless steels as the base line. For this purpose, V-base, Co-base, and Mo-base alloys, and several stainless steels were selected for tests. This part of the program is nearing completion.

Table 1

Corrosion Test Materials

Alloy	Composition
HA-25	Co-20 Cr-10 Ni-15 W-2 Fe-0.1 C
HA-188(old) (HA-8188)	Co-18 Cr-17 Ni-12 W-0.1 C
HA-188(new)	Co-22 Cr-22 Ni-14 W-0.1 C
S-1 (G.E. alloy)	Co-20 Cr-10 Ni-6 Mo-2 Fe-0.05 C
UMCO-51	Co-28 Cr-19 Fe-2 Cb-0.2 C
Alloy 68-612 (BNL)	Co-22 Cr-22 Ni-14 W-1 Fe-0.6 Ti-0.03 C
Multimet	30 Fe-21 Cr-20 Ni-20 Co-3 Mo-2.5 W
Incoloy-800	47 Fe-21 Cr-32 Ni
316 SS	Fe-18 Cr-13 Ni
304 SS	Fe-18 Cr-8 Ni
321 SS	Fe-18 Cr-12 Ni-0.5 Ti
304 (Ti) SS	Fe-18 Cr-8 Ni-0.2 Ti
ORNL alloy	Fe-15 Cr-4 Al-1 Y
V-base alloy	V-20 Ti
V-base alloy	V-15 Ti-7.5 Cr
V-base alloy	V-15 Cr-5 Ti
Mo	Mo
Mo-TZM	Mo-0.5 Ti-0.1 Zr
D-11	Nb-1 Zr

Two forced circulation loops (FCL-1 and FCL-2), each made entirely of stabilized stainless steels, were used to carry out high-velocity corrosion studies. Test specimens were exposed to sodium in a rising temperature region (24 in. long) on a removable test section. The compositions of the test materials are shown in Table 1.

FCL-1

A total of 4021 hr of ΔT operation has been accumulated with this loop under the conditions shown in Table 2. With the conclusion of this run, the comparative cladding corrosion tests in this loop have been terminated. The results of weight change measurements, metallographic examination, microprobe analysis, and x-ray fluorescence analysis of specimens will be reported as each examination is completed.

The weight change measurements of the specimens tested in Run 2 were studied in the usual manner, i.e., plotting ΔW vs $1/T$ and extrapolating to 710° and 760°C. These extrapolated values are summarized in Table 3. The data shown include the corrosion rates calculated for the following materials at 4 and 15 ppm oxygen levels in Na and for 710° and 760°C: Haynes 25, Haynes 188, UMCO 51, 304 stainless steel, 321 stainless steel, and 304L (Ti added) stainless steel. Several Ferrovac E (pure iron) specimens were exposed in the last test increment. These specimens lost only about 1/10th the weight of a typical stainless steel specimen because of their concurrent pickup of Ni and Cr from the Na. Unalloyed molybdenum was also evaluated and found to show essentially no weight change at either O level in Na. X-ray fluorescence analyses are currently under way for all materials.

Haynes 25 alloy appears to have the best corrosion resistance (aside from Mo) of the materials tested. However, examination of these specimens indicated that the pickup of Fe on the surface of Haynes 25 may be complicating the weight loss measurements. A more detailed metallographic

Table 2

FCL-1 Operating Conditions (10/1/69)^a

Loop No.	Test time, hr	Type of run	Test section materials	Range of oxygen, ppm
FLC-1, Run 1	1A = 168	Cold trap	HA-25 UMCO-51	2 to 6
	1B = 336		321 SS 304 SS	
	1C = 600		Molybdenum	
	1D = 551			
Total	= 1655			
FCL-1, Run 2	2A = 192	Cold trap	HA-25 ^b UMCO-51 ^b	8 to 18
	2B = 455		321 SS ^b 304 SS ^b Molybdenum ^b HA-8188 304L(Ti)	
	2C = 455			
	2D = 429		Fe ^c	
Total	= 1531			
FCL-1, Run 3	3A = 504	Cold trap	316 SS	4 to 6

^aLoop material, 321 SS; max temperature = 760°C, test section velocity = 22 ft/sec, loop ΔT = 200°C.

^bThese specimens aged in Run 1 and were not exchanged for new specimens in Run 2.

^cPure Fe specimens interchanged with Mo specimens prior to Run 2D.

Table 3

Corrosion Rates of Materials Tested in FCL-1

Material	Corrosion rate, mils/yr			
	4 ppm O in Na		15 ppm O in Na	
	760°C	710°C	760°C	710°C
HA-25	1.4	0.3	0.8	0.2
HA-188	—	—	1.2	0.4
UMCO-51	0.9	0.3	1.5	0.4
Type 304 SS	1.0	0.5	3.2	2.2
Type 304L(Ti) SS	—	—	3.2	2.0
Type 321 SS	1.1	0.4	3.1	1.8

Table 4

FCL-2 Operating Conditions (10/1/69)^a

Loop No.	Test time, hr	Type of run	Test section materials	Range of oxygen, ppm
FCL-2, Run 1	1A = 335	Hot trap	V-20 Ti V-15 Ti-7.5 Cr	< 1
	1B = 675		V-15 Cr-5 Ti Nb-1 Zr	
	1C = 322		Mo-TZM 321 SS	
	1D = 672			
Total	= 2004			
FCL-2, Run 2	2A = 261	Cold trap	Same as Run 1	2 to 4
	2B = 260			
	2C = 266		^b	
Total	= 787			
FCL-2, Run 3	3A = 190	Cold trap	Same as Run 2C	2 to 4
Total	= 190			

^aLoop material, 321 SS; max temperature, Runs 1 and 2, = 760°C; max temperature, Run 3, = 505°C; test section velocity = 22 ft/sec; loop ΔT = 200°C.

^bPure Fe specimens were interchanged with TZM specimens prior to Run 2C.

Figure 1. Cumulative weight loss of 321 stainless steel vs test section position; 787 hr at ~3 ppm O in Na.

examination of the Haynes 25 specimens is under way. A. ROMANO, W. TREMEL, F. KULESA

FCL-2

A total of 2981 hr of ΔT operation have been accumulated with this loop under the conditions shown in Table 4. At the conclusion of Run 3A, all the test specimens were removed for final post-test examination. The exposed refractory metal specimens were examined metallographically and a mechanical properties test (measuring ductility) performed. Following these tests, some specimens were chemically analyzed for C, O, and N; the results of these tests are reported later in this report.

Type 321 stainless steel was selected as the material to be used in both loops to compare the corrosion rates in the two loops. In addition, several Ferrovac E (pure iron) specimens were exposed in this loop during Runs 2C and 3A. Figure 1 shows the results of the weight change measurements made on the 321 stainless steel specimens after 787 hr at 2 to 3 ppm oxygen level. Subsequent operation in Run 3 at 505°C maximum temperature showed essentially no additional weight changes. The unusual temperature effect observed on the aged specimen, i.e., weight loss decreasing with increasing temperature, is evidence of an interaction between these steels and something in the Na. X-ray fluorescence showed this interaction to be the pickup of V on the surface of the 321 stainless steel specimens. The effect is not as obvious with the new specimens because of the very high initial weight losses as a result of leaching of the Ni and Cr. However, it was observed in the last increment (Run 2C) that the colder new specimen lost slightly more weight than the hotter one. Results of microprobe analyses of two aged specimens having had the same prior exposure except that one was at 710° while the other was at 760°C show that the V concentrations at the surfaces of the two specimens are about equal (confirming the x-ray fluorescence results) but the depth of penetration of V in the higher temperature specimen was greater.

The Ferrovac E specimens inserted before Run 2C all gained weight during sodium exposure, and the weight gains increased with increasing temperature. X-ray fluorescence analyses of these specimens showed that the major constituents picked up were V and Cr with lesser amounts of Ni and Mn. Examination of these specimens will continue. A. ROMANO, W. TREMEL, F. KULESA

CORROSION MODELING STUDIES

The objectives of this phase of the program are to prepare a critical evaluation of existing data on corrosion and mass transfer of steels, to postulate possible corrosion mechanisms that are consistent with the above evaluation, and to design a test program that examines the critical predictions of the tentative corrosion-deposition equations and that provides needed information that is now not available.

Evaluation of Existing Corrosion Data

To evaluate the role of the solubilities of Fe, Cr, and Ni in Na in the corrosion of steels by sodium, the concentrations of Fe, Cr, and Ni in loop sodium, obtained from a number of sites, are compared in Tables 5, 6, and 7 with the predictions from the BNL solubility data for these metals (Figure 2). Although the method of sampling is different in the several laboratories, the results fall in a general pattern: the Fe and Cr analyses are equal to or greater than those of Fe and Cr solubilities at the maximum temperature of the system, whereas the Ni analyses correspond more closely to the Ni solubility at temperatures nearer the minimum temperature in the main stream of the system. The results from the BNL loops may possibly have been affected by reactions between the solutes and the Mo samplers. At 650°C, the BNL-measured solubilities and the concentrations of Fe, Ni, and Cr are in the same sequence ($\text{Fe} > \text{Ni} > \text{Cr}$) whereas selective leaching observations in loops suggest Fe should be less soluble than Ni and Cr in low oxygen Na. If we assume that a critical supersaturation is a prerequisite for precipitation, Cr, which has the steepest slope in Figure 2, would be the first metal to precipitate as Na is cooled, and Ni, with the lowest slope, would precipitate last, in agreement with observations made by both Roy and Bogers.

J. WEEKS

Postulation and Evaluation of Corrosion Mechanisms

Development of a model for the corrosion behavior of steels in Na has traditionally been stymied in explaining the low corrosion rates in view of solubility data and loop sodium analyses.

We suggest that corrosion in high velocity Na is not primarily a function of the Fe solubility, but is related to the kinetics of dissolution of Fe atoms. A steady-state corrosion equation was derived,

Table 5

Comparison Between Fe Solubility in Na and Fe Concentrations in Na in Stainless Steel Circuits

Circuit	$\Delta T, ^\circ\text{C}$	Fe in circuit Na, ppm	Solubility, ppm Fe	
			$T_{\max}$	$T_{\min}$
BNL FCL-1	760-450	60 ± 40	8.8	0.16
BNL FCL-2	760-450	22 ± 15	8.8	0.16
BNL FCL-3	350-350	16	~ 0.02	~ 0.02
GE 1-5	710-450	5	6	0.16
GE 8-9	710-450	10-12	6	0.16
MSA #1	650-612	2.3	3.0	1.9
MSA #2	650-612	1.6	3.0	1.9
EBR-II				
Primary	450-372	0.25	0.17 BK	~ 0.03
	532 hot spot		0.64 HS	
Secondary	450-305	0.25	0.16	~ 0.01
ANL 1a	500-500	5	0.4	0.4
ANL 1b	650-650	5	3.0	3.0

$$R = (\vec{K}'/\vec{K} + k')(\text{Fe}^*) + k'[(k'/\vec{K} + k') - 1]\text{Fe}_{\text{bulk}}, \quad (1)$$

in which $\vec{K}$ and $\vec{K}'$ are the rate constants for dissolution and deposition, k' is the mass transfer coefficient of dissolved Fe in Na, Fe^* is the concentration of active sites on the Fe surface, and Fe_{bulk} is the concentration of Fe dissolved in Na. For velocity-dependent corrosion this reduces to the familiar form

$$R = k'(\text{Fe}_{\text{sat}} - \text{Fe}_{\text{bulk}}), \quad (2)$$

and for velocity-independent corrosion, this reduces to

$$R = \vec{K}\text{Fe}^*. \quad (3)$$

Either $\vec{K}$ or Fe^* or both may be functions of the oxygen activity in the Na. The downstream effect is considered to arise from saturation of the Cr and Ni in Na, which, in turn, results from increased concentrations of Cr and Ni on the surface in the downstream region. This Cr and Ni can migrate on the surface to the active sites and adsorb on them, thereby reducing Fe^* and the corrosion rates. According to the above model, the oxygen effect can be treated as one of increasing Fe^* , so that Eq. (3) becomes

Table 6

Comparison Between Cr Solubility in Na and Cr Concentrations in Na in Stainless Steel Circuits

Low circuit	$\Delta T, ^\circ\text{C}$	Cr in circuit Na, ppm	Estimated solubility, ppm Cr	
			$T_{\max}$	$T_{\min}$
BNL FCL-1	760-450	4.2 ± 1	3.5	$\ll 0.1$
BNL FCL-2	760-450	7.7 ± 3	3.5	$\ll 0.1$
BNL FCL-3	350-350	2.4	$\ll 0.1$	$\ll 0.1$
GE 1-5	710-450	3	1.5	$\ll 0.1$
GE 8-9	710-450	4-2	1.5	$\ll 0.1$
MSA 1, 2, and 3	650-612	< 1	0.4	0.14
EBR-II Primary	532 HS 455-372	< 0.05	0.01 HS	—
ANL 1b	650-650	0.2	0.4	0.4

$$R = \vec{K}\{\alpha + \beta[\text{O}] + \gamma([\text{Cr}] + [\text{Ni}])\}. \quad (4)$$

In an alternative attempt to treat the oxygen effect, a model for $\vec{K}$ was developed from reaction rate theory. The steel surface (Fe^*) is presumed covered with adsorbed oxygen, and each active site then reacts with two additional oxygens in the Na to yield an activated complex that decays first to $(\text{Na}_2\text{O})_2 \cdot \text{FeO}$ and then to a solution of Fe and Na_2O in Na, since the ferrite is unstable in low-oxygen Na. The BNL corrosion data at zero downstream from FCL-1 at 4 ppm O were used to estimate ΔH^* (the heat of formation of the complex) to be ~ 44 kcal/mole, after first being modified from the measured oxygen dependence to yield corrosion rates as a function of temperature at constant oxygen activity. ΔS^* was assumed to be approximately the entropy of formation of FeO . The resultant steady-state corrosion equation is then

$$\begin{aligned} d\text{Fe}/dt = & \text{Fe}^* \{ (7.55 \times 10^{16}) (\text{O}/\text{O}_{\text{sat}})^2 \\ & \times [\exp(-44,000/RT)] \} \text{ mil/yr.} \end{aligned} \quad (5)$$

According to Eq. (5) $\vec{K}$ should vary as $(\text{O})^2$ at constant temperature, whereas the normal observation is that the corrosion rate of stainless steels varies as $(\text{O})^{-1.2}$. The difference is attributed to a negative effect of O on Fe^* , and the presence of Cr and Ni, the corrosion of which is presumed to be independent of O as suggested by the O-inde-

Table 7

Comparison Between Ni Solubility in Na and Ni Concentrations in Na in Stainless Steel Circuits

Circuit	ΔT , °C	Ni in circuit Na, ppm	Solubility	
			$T_{\max}$	$T_{\min}$
BNL FCL-1	760-450	8.4 ± 4	2.3	0.7
BNL FCL-2	760-450	8.4 ± 3	2.3	0.7
BNL FCL-3	350-350	6.9	0.3	0.3
GE 1-5, 7-9	710-450	<1-2	2	0.7
MSA 1-3	650-612	<1	1.6	1.4
EBR-II				
Primary	455-372	0.10	0.73 BK	0.4
	532 HS		1.05 HS	
Secondary	450-305	0.10	0.73	<0.3
ANL 1b	650-650	<0.2	1.6	1.6
ANL 2 ^a	650-335	4×10^{-3}	1.6	~0.3
ANL 3 ^a	550-550	$0.6 \pm .16$	1.1	1.1

^aANL #2 Mo-lined except for stainless steel at $T_{\min}$ (335°C). ANL #3 all Ni system isothermal except for 123°C cold trap.

pendence of corrosion of Inconel and Co-base alloys both of which contain as much or more Cr than the stainless steels. Also, the BNL data suggest that ΔH^* might itself be a function of the oxygen activity. The value used in Eq. (5) was calculated from the 4 ppm O data at 710°C. The term Fe^* in Eq. (5) is assumed to vary with $[C]$ and $[Ni]$ in the same manner as in Eq. (4).

The major predictions of this corrosion model are (1) the measured velocity-independent corrosion rate of an all-Fe system in Na is the maximum corrosion rate obtainable at the given temperature and oxygen levels, so that scale-up factors should have a minimum effect on the corrosion rate of the steel, (2) the corrosion of Fe should not show a downstream effect and may vary as $(O)^2$, (3) the presence of inserts of Ni or Cr in a test section should increase the downstream effect (and therefore decrease corrosion), and (4) corrosion of steels is not primarily a function of the Fe solubility. These predictions are all amenable to testing.

The experiments described in the next section are all designed to test these predictions and to demonstrate the role of high heat flux on corrosion. These include design of an all-Fe loop, development of test sections for FCL-1 that will show the role of nucleating precipitates and par-

Figure 2. Measured binary solubilities of Fe, Cr, and Ni in low-oxygen Na. $\log_{10}(\text{ppm Fe}) = 5.16 - (4310/T, ^\circ K)$; $\log_{10}(\text{ppm Cr}) = 9.35 - (9010/T, ^\circ K)$; $\log_{10}(\text{ppm Ni}) = 1.545 - (1230/T, ^\circ K)$.

ticulate removal on the corrosion process, and a study of the downstream effect and how it is affected by the presence of Ni and Cr rings placed in the test section.

A computer program of the corrosion of steels in Na in the velocity-dependent region has been developed with the assistance of J. Chen of the Engineering Division and H. Berry of the Applied Mathematics Dept. Preliminary tests of this program using a slug-flow approximation showed that the model predicts a downstream effect that is consistent with the GE observations, but has a rather unusual velocity effect. The program is being modified to introduce a more sophisticated velocity profile.

H. ISAACS, S. WACHTEL,
J. WEEKS, D. GURINSKY

DEVELOPMENT OF SOLUTION DEPOSITION TECHNOLOGY C.J. KLAMUT

FCL-1

This first run of the loop for this purpose will be to determine whether there are removable particulates suspended in Na, and, if so, what will be the effect of removing these particulates on the corrosion rate of type 316 stainless steel. A particulate-removal section has been installed in par-

allel with the main cold leg of the loop. This section contains an upstream corrosion specimen cartridge, a nozzle and baffle section, a magnetic trap utilizing a 7-kG magnet, a 2 to 5- μ filter (316 stainless steel), and a downstream corrosion specimen cartridge. It is planned to operate both with and without the particulate removal section in-line, and to measure weight changes of the 316 stainless steel specimens.

The first incremental run has recently been completed in which the normal corrosion rate of 316 stainless steel is being established. The operating conditions are identical to those of FCL-1, Run 1 (Table 2) and the test period is 504 hr. The weight change measurements are in good agreement with the early results of the 304 stainless steel specimens tested in FCL-1, Runs 1A and 1B (504 hr).

Evidence of possible particulate matter in the loops was first found in early Na sample analyses (Na collected in Mo buckets), the results of which are shown in Table 8. A. ROMANO, W. TREMEL, F. KULESA

High Heat Flux Loop

The effect of heat flux on the corrosion rate of stainless steels is being investigated in a forced circulation sodium loop with a medium frequency induction generator used as a source of high heat flux (see BNL 50161, p. 31, for loop layout). The heater was successfully tested for 1060 hr at a nominal heat flux of $1.0\text{--}1.1 \times 10^6$ Btu/hr-ft² with maximum specimen temperature of 655°C and a sodium velocity of ~ 20 ft/sec. Temperatures measured along the outside wall of the test section indicated a peak in heat flux ~ 2 in. from the outlet of the heated zone.

Results of x-ray fluorescence analyses performed on both the inside and outside surfaces of the type 304 stainless steel specimens removed after test are plotted in Figure 3 against position in the test section. Figure 4 shows estimated specimen temperature vs specimen position for comparison. Except for depletion of Mn, no essential changes in composition were noted for the specimen's outer surface which faces stagnant Na. This indicates that little corrosion has taken place on the crevice or outside of the specimen. On the inside, or flowing Na side, depletion of Mn, Ni, and Cr and enrichment in Fe is shown. The region of maximum compositional change and of maximum temperature correspond. As this run was basically a high flux heater endurance demonstration rather than a corrosion test, no weight change data were obtained.

Table 8

Analyses of Fe, Ni, Cr, and Co in FCL 1 and 2 Sodium

Loop max temperature, °C	Bucket No.	Fe	Ni	Cr	Co
750 ^a	4A	24	12	3.5	
	4B	195	3.9	3.5	
	4C	68	15	15	
	5A	65	15	4.0	
	5B	22	3.9	2.7	
	5C	38	8.2	7.3	
	Av	62	8.4	5.6	
600 ^a	6A	91	15	15	
	6B	10	2.5	1.4	
	6C	20	1.7	1.7	
	Av	40	6.4	6.0	
450 ^a	7A	21	15	9.6	
	7B	23	17	13	
	7C	26	21	21	
	Av	23	18	15	
750 ^b	8A	42	13.2	12.2	n.d.
	8B	17	5.2	3.8	<1
	8C	7	6.2	7.0	
	Av	22	8.2	7.7	

^aFCL-2 analyses.^bFCL-1 analyses.

The loop was modified to include a liquid metal sampling station to allow monitoring of the loop oxygen level. Also the test section region of the loop, which had bent because of thermal expansion and contraction of the loop, was replaced and braced. A new test section was assembled using preweighed type 316 stainless steel specimens, and a somewhat thicker vanadium Permendur susceptor was used.

After start-up the oxygen level was found to be ~ 50 ppm resulting from contamination during loop modification. Successive uranium gettering runs, made in the side stream sampling section, reduced the Na oxygen level to 7 ppm, but it is hypothesized that upon heating to high flux run conditions (100°C max Na temperature) expansion of Na into the surge tank caused more oxygen to dissolve from the surge tank walls. As a result the initial 500-hr high flux run with the type 316 stainless steel specimens was made at an average oxygen level of ~ 25 ppm.

Figure 3. Comparison of specimen inside and outside surface composition. X-ray fluorescence analyses.

Maximum outside wall temperature ($\sim 719^{\circ}\text{C}$) was significantly lower than those in previous runs at this high heat flux (av. 1.1×10^6 Btu/hr-ft²) probably because of the thicker Permendur susceptor. Thermocouples located in the flowing sodium were used to measure temperatures at the $\frac{1}{3}$ and $\frac{2}{3}$ points along the test section. Calculations were made of local heat flux in the center third of the test section using these temperatures, and these averaged 1.66×10^6 Btu/hr-ft².

Specimens removed from test after 500 hr were dark gray and had, for the most part, gained weight. Weight losses of up to ~ 0.35 mg/cm² were recorded in the high flux region. Selected specimens are undergoing examination.

A cold trap will be added to the loop because of difficulty encountered in controlling oxygen.

S. WACHTEL, J. BRANDON, M. STEPHENS

Iron Loop

A pumped sodium loop in which all wetted parts will be fabricated from pure iron (Ferrovac E) has been designed and is under construction. This loop will be used to investigate the corrosion deposition characteristics of iron in a nickel- and chromium-free environment. The loop will be, of necessity, uncomplicated with an EM pump (Ferrovac E pump cell), flowmeter, up to three 1-ft-long test sections containing flat, pure iron specimens, and a flowthrough dump tank which will be used as a Na reservoir, sampling, and oxygen control station. Oxygen will be added as Na₂O or removed by U gettering to obtain the desired concentration. The

Figure 4. Temperature profile of inner surface of specimen.

loop is fabricated of 0.500-in.-i.d. Inconel-clad Ferrovac E co-drawn tubing. The tank, fabricated of Ferrovac E sheet, will also be Inconel-sheathed. Test section and specimens have been fabricated from Ferrovac E rod and sheet, and are relatively loose fitting to minimize sticking. Because iron to iron sticking has been observed in previous work and may be a major problem, test sections will be cut from the loop rather than withdrawn as in other loops. Also, other test section designs to eliminate or minimize sticking are being studied.

S. WACHTEL

COMPARATIVE CORROSION TESTS ON REFRACTORY ALLOYS

C. KLAMUT

A total of 2981 hr of ΔT operation have been accumulated with FCL-2 under the conditions shown in Table 4. The materials tested included three V-base alloys, Nb-1 Zr, and Mo-TZM. At the conclusion of Run 3A, all the test specimens were removed for final post-test examination. New specimens and a new test section design are being planned for future testing. The new design will incorporate tensile specimens as well as weight change specimens.

The exposed refractory metal specimens are examined metallographically and then by a mechanical properties test to estimate ductility. Following this test, the specimens are chemically analyzed for C, O, and N. The mechanical test consists of compressing a soft metal (lead) between two end plugs of steel all contained inside the cylindrical test specimen. The resulting stresses cause the specimen to expand diametrically until it ruptures.

Table 9
Weight Loss Measurements of Refractory Metal Alloys^a

Material	Type of specimen ^b	Av weight loss, mg			
		Run 2A	Run 2B	Run 2C	Run 3A
V-20 Ti	Aged	-31.5	-2.7	-3.3	-3.9
	New	-52.5	—	—	+1.2
V-15 Ti-7.5 Cr	Aged	-39.4	-3.8	-3.9	-2.2
	New	-28.9	—	—	-0.7
	Downstream	-36.8	-2.3	-2.1	-2.1
	Aged				
V-15 Cr-5 Ti	Aged	-32.5	-4.6	-2.9	-0.7
	New	-28.3	—	—	—
Nb-1 Zr	Aged	-120.9	-87.9	-92.9	-5.8
	New	-179.0	—	—	-4.4

^a Runs 2A, 2B, and 2C have temperature gradient along test section of 710° to 760°C at 22 ft/sec with 2 to 4 ppm O in Na for 787 hr. Run 3A has a temperature gradient of 475° to 505°C at 22 ft/sec with 2 to 4 ppm O in Na for 190 hr.

^b Aged = prior exposure to Na. New = no prior exposure to Na.

A low maximum temperature run was performed (Run 3A) to determine whether the low temperature at which the specimens were exposed while adjusting the oxygen concentration prior to Run 2A was the cause for the very high weight losses observed on the V-base alloys and Nb-1 Zr. The oxygen level in the Na for Run 3A was held at 2 to 3 ppm. The results of the weight loss measurements of this test run and the previous runs (Run 2A, B, and C) are shown in Table 9. Results indicate the vanadium alloys lost about as much weight at 475° to 505°C as they did in Runs 2B and 2C (710° to 760°C) but not as much as they did in Run 2A. The results indicate that corrosion of the V-base alloys is not as sensitive to temperature as it is to oxygen in sodium. The decreasing rate of weight loss with time is suggestive of the behavior of metals that form protective surface films. The pickup of C and/or N on V-base alloy specimens during exposure to Na may possibly have caused this effect.

Metallographic results of the V-base alloy specimens show that those specimens that had been previously exposed to hot-trapped Na and then to Na containing 2 to 3 ppm oxygen are not as severely attacked as specimens that were exposed only to the latter. Distinct layers are visible upon etching which generally seem to be higher in hard-

Table 10
Mechanical Properties Test Results of Vanadium Alloys

Prior exposure to Na	Material	Change in ductility ^a
Hot trapped only	V-20 Ti	<10% loss
	V-15 Ti-7½ Cr	60% loss
	V-5 Ti-15 Cr	Essentially no ductility
Cold trapped only	V-20 Ti	70% loss
Cold trapped (low temperature only)	V-20 Ti	10% loss
	V-15 Ti-7½ Cr	70% loss
Both hot and cold trapped	V-20 Ti	70% loss
	V-15 Ti-7½ Cr	Essentially no ductility
	V-5 Ti-15 Cr	Essentially no ductility

^aAfter exposure. Tests made at room temperature.

ness than the matrix. The layers may contain C, O, or N, and may act as protective barriers. Analyses are under way to determine the compositions of the layers.

The preliminary test results of the mechanical properties of V-base alloys are summarized in Table 10. Of the three alloys tested, V-20 Ti is the only material that retains high ductility after hot-

trapped Na exposure and also after low temperature (500°C) exposure to 2 to 3 ppm O in Na for 190 hr. However, none of the alloys have high ductility after exposure to 2 to 3 ppm O in Na at high temperatures (710° to 760°C). The V-5 Ti-15 Cr alloy seems to be the most susceptible to loss in ductility after exposure to Na.

Preliminary results of chemical analyses show that the three V-base alloys picked up carbon during the hot trapped run (prior to exposure, ~200 ppm; after exposure, ~1500 ppm); little oxygen is picked up in this exposure. As expected, oxygen is gained during cold trap exposures; little carbon is gained in this exposure. Nitrogen seems to increase during both types of exposure and is primarily a function of operating time. A. ROMANO

STEADY-STATE SOURCE RATES FOR OXYGEN IN SODIUM B. MINUSHKIN

Previous work has demonstrated that stainless steel and/or certain impurities in sodium can buffer the oxygen activity of sodium and thus act as a source or sink for oxygen at a particular activity. The objective of this study is to determine the quantities of oxygen available from this source and the rates of absorption or release.

Preliminary tests using the sodium chemistry loop (SCL) have indicated that in certain concentration ranges only a fraction of the oxygen added as Na₂O at 350° or 400°C can be accounted for by the increase in oxygen concentration or activity of the sodium. The possible mechanisms to account for the loss of oxygen are (1) segregation of oxide at sodium-gas interface, on wetted surfaces, or as frost in the gas space of the surge tank,* (2) adsorption of oxygen on stainless steel surfaces, or (3) formation of solution compounds of oxygen with other metallic or non-metallic species.

An oxygen meter with a gas (O₂ at 1 atm) reference electrode and one with a Na,Na₂O electrode were calibrated at 400°C against the cold trap temperature and amalgamation analyses in preparation for quantitative Na₂O additions to measure the size of the oxygen source or sink.

*Cold trapping in branch lines, dead ended pipe stubs, etc., are very unlikely in the SCL because of design and trace heaters that keep these sections hot.

Figure 5. Calibration of O₂ gas and Na,Na₂O electrodes in sodium chemistry loop.

In Figure 5, results are shown as emf of both O₂ and Na,Na₂O cells vs log oxygen concentration. The emf axis of the O₂ gas cell is displaced by 1.647 V so that the lines for this and the Na,Na₂O cell correspond. The lower line is cell emf plotted against concentration derived from the cold trap temperature using the solubility relationship

$$\log C_0 = 6.46 - (2600/T, ^\circ\text{K}).$$

This relationship was derived from independent measurements by utilizing electrochemical oxygen cells and thus should be the appropriate solubility relationship to use with oxygen meters. The emf's of both cells are also plotted against oxygen content as determined by amalgamation analysis of bypass samples. Although there is scatter, these points fall on the same line as the points obtained from the cold trap temperature-solubility correlation.

The upper line is the theoretical line for both cells obtained with the use of the oxygen solubility (440 ppm at 400°C) from the above relationship. At 400°C the emf measurements, Eichelberger's correlation, and Claxton's correlation all predict

about the same solubility (~ 400 ppm). Therefore, the position of the theoretical line is not subject to significant variation because of uncertainty in oxygen solubility. In the case of the $\text{Na,Na}_2\text{O}$ cell an effective t_{ion} of unity is assumed. In the case of the gas cell the emf in sodium saturated with Na_2O has been measured (1.647 V) and a line with theoretical slope was drawn through this emf at $C_0 = 440$ ppm.

The data show that for a given emf (activity) on both the O_2 gas and $\text{Na,Na}_2\text{O}$ cells the oxygen concentration predicted from cold trap temperature or sample analysis is lower than the value predicted by theory. The deviation can be caused by (1) use of an incorrect solubility relationship or (2) a cell transference number (t_{ion}) significantly less than one. Alternatively the sodium oxide concentration in the vicinity of the meters can in fact be higher than that predicted by solubility or detected by analysis.

The agreement between recent independent solubility determinations lends confidence to the validity and accuracy of values used.* The adjustment in oxide solubility needed to reconcile the two lines is inordinately large in view of this agreement and transference number (t_{ion}) less than unity may account for only part of the deviation but the difference between the two curves and their relationship to each other cannot be accounted for by any reasonable values for t_{ion} . If the t_{ion} on the sodium side is 0.8, the slope of $\log C$ vs E would be 0.8 of the theoretical (which it is) but the deviation between the two lines should not exceed about 13 mV. Furthermore the lines should converge in the vicinity of the solubility at 400°C and should show distinct curvature over the range of oxygen concentrations tested.

During these tests the cold trap was operated continuously. This fact can provide at least a qualitative mechanism by which the actual oxygen content in the vicinity of the meters would be higher than that corresponding to saturation at the cold trap temperature. A number of observations have suggested that oxygen interacts with an impurity to form a species which is more stable at low temperature than at high temperature. When sodium is cooled and flows through the cold trap, the reaction is displaced toward formation of more of the oxygen-impurity solution consuming oxide

*The BNL emf relationship, Eichelberger's correlation, and recent BNL data obtained by amalgamation of samples from SCL (Figure 6) all show good agreement.

Figure 6. Comparison of oxygen solubility in Na as measured in the sodium chemistry loop with Eichelberger's correlation and Minushkin's electrochemical measurements.

from the stream. The cold trap then supplies more oxide to return the stream to the cold trap saturation oxide concentration. When the sodium is reheated in the vicinity of the meters some of the compound decomposes producing an oxide concentration higher than the value predicted from cold trap temperature. The actual deviation would be determined by the stoichiometry of the reaction and kinetics of the individual steps.

B. MINUSHKIN, L. EMMA,
L. NEWMAN, C. TIERNEY

IMPROVEMENT OF THE ELECTROCHEMICAL CELL FOR OXYGEN AND SODIUM B. MINUSHKIN, L. NEWMAN

Evaluation of Improved On-Line Oxygen Meters

In order to improve the electrochemical oxygen meter, comparative studies have been conducted

Table 11
Characteristics of Several Oxygen Meter Reference Electrodes

	t_{ion} at electrode/electrolyte interface	Oxygen gradient across electrolyte $P_{\text{O}_2}(\text{ref}) - P_{\text{O}_2}(\text{Na})$	Ability to accommodate changes in oxygen activity of environment
Na,Na ₂ O	~1	negligible, <10 ⁻⁵⁰ atm	liquid metal, good
Pb,PbO	1	small, ~10 ⁻¹⁸ atm	liquid metal, should be good above mp
O ₂ , 1 atm	0.2-0.7	large, 1 atm	with gas flow, excellent
Air (O ₂ at 0.21 atm)	0.2-0.7	large, 0.21 atm	with gas flow, excellent
Cu,Cu ₂ O	1	small, ~10 ⁻¹⁷ atm	poor, dependent on solid-state diffusion
	Susceptibility to contamination	Compatibility with electrolyte	General comments
Na,Na ₂ O	H ₂ , C contamination possible, may react with Al ₂ O ₃ insula- tors, etc., and metal leads	long term behavior unknown	sodium vapor transport may be prob- lem; Na ₂ O attack on ceramic may be problem at high temperature
Pb,PbO	unknown	long term behavior unknown	high melting point of lead electrolytes have cracked when temperature cycled through mp
O ₂ , 1 atm	unaffected by low level contamination	no problem evident	reliable and rugged, possible prob- lems due to low t_i
Air (O ₂ at 0.21 atm)	minimal and easily decontaminated	no problem evident	reliable and rugged, possible prob- lems due to low t_i
Cu,Cu ₂ O	high for gaseous or solid con- taminants which affect P_{O_2}	good, long term compatibility at low temperature	most long term experience at low temperature; however, inherently in- ferior to liquid metal and gas electrodes

on three different types of reference electrodes: solid metal-metal oxide (Cu-Cu₂O, Ni-NiO, Si-SiO₂), liquid metal-metal oxide (Na-Na₂O, Pb-PbO), and gas-metal (O₂-Pt, O₂-Au). The characteristics of these types of reference electrodes are summarized and compared in Table 11. These studies indicated that a number of significant operational difficulties exhibited by commercial United Nuclear Corp. (UNC) meters are attributable to inherent characteristics of the solid metal-metal oxide reference electrode (Cu-Cu₂O). Particularly at low temperatures this type of reference electrode was found to be highly susceptible to gas-phase contamination, sluggish in its ability to re-equilibrate after a temperature change, and consequently not easily reproducible. These limitations arise primarily from the fact that the solid metal-metal oxide electrodes at low temperatures must rely on relatively slow solid-state diffusion processes to

establish and maintain the desired equilibrium oxygen activity. To a large extent the liquid metal and gaseous reference electrodes overcome these problems and offer potential for improved performance.

The object of this work is to evaluate these new reference electrodes for use in on-line oxygen meters. In design features, the new electrodes are similar to the commercial Cu,Cu₂O cells, except that the getter pellets have been eliminated and the spring-loaded electrode contact is replaced by a stainless steel wire which contacts the new reference electrodes. The Na,Na₂O electrode was made by placing ~1 g of Na and 0.040 g of high purity Na₂O at the bottom of a 1/2-in.-o.d. x 8-in.-long ThO₂-15 wt % Y₂O₃ tube. An Al₂O₃ plug is located on the stainless steel contact wire ~1 in. above the Na,Na₂O level to confine the sodium vapors.

The oxygen gas reference electrodes were made by depositing a porous gold film inside the bottom $\frac{3}{8}$ in. of a $\frac{1}{2}$ -in.-o.d. $\times$ 8-in.-long ThO_2 -15 wt % Y_2O_3 tube. Electrical contact is made to the gold film with a gold mesh plug and stainless steel wire. A $\frac{1}{8}$ -in.-o.d. stainless steel tube directs a flow of oxygen gas (~ 40 cc/min) over the gold film and the gas is vented at 1 atm from the top of the electrode assembly. The oxygen gas of the reference electrode is isolated from the sodium and its cover gas.

Thermal Convection Loop Tests. Two gas-metal reference electrodes were tested in thermal convection loops. In the first case an O_2 (1 atm)-Au electrode was operated for 1133 hr at 500°C . During this period the cell was stable, responded as expected to changes in oxygen content of the sodium, and did not exhibit any evidence of drift or sensitivity to ambient air temperature. The electrolyte cracked during a temperature transient caused by a power failure. The second cell employed an O_2 (0.21 atm)-Au reference electrode and to date has operated for >3000 hr at 410°C . It too has exhibited the improved stability and reproducible response observed for the first cell. Tests with this cell have demonstrated that (in the case of air) a continuous air flow is not needed to maintain the reference electrode. No change in emf was observed with or without air flow over the gold film.

Forced Circulation Loop Tests. Two meters, one $\text{Na,Na}_2\text{O}$ and one Au, O_2 (1 atm), were installed in series in conventional finned-tube housings in a bypass circuit of the SCL, and two more similar meters in FCL-1. The meters operated at $\sim 400^\circ$ to 435°C . The cells in SCL cracked after 2000 hr as a result of thermal shock during a very fast temperature transient. The gas cell has operated satisfactorily in FCL-1 for >1500 hr without any indication of deterioration or change in calibration. The $\text{Na,Na}_2\text{O}$ cell operated satisfactorily during the first 500 hr. However, on start-up after a planned shutdown the cell became erratic. The cause of this behavior is not known at present, since other $\text{Na,Na}_2\text{O}$ cells have operated satisfactorily for longer times at this and higher temperatures.

Tests completed to date in the forced circulation loops indicate that the new electrodes exhibit improved operating characteristics and performance over the original UNC $\text{Cu, Cu}_2\text{O}$ electrodes tested in these loops for the following reasons.

(1) The calibration curves for the four new meters, as determined by cold-trap temperature

Figure 7. Calibration curves of four new meters: two with O_2 reference electrodes and two with Na_2O reference electrodes.

and sample analysis, agree within 5 mV when the expected difference in potential due to the different reference states is subtracted out. This is illustrated (Figure 7) by plotting the emf of the O_2 gas cell vs the emf of the $\text{Na,Na}_2\text{O}$ cell at 400°C . The relationship obtained,

$$E(\text{O}_2 \text{ gas at } 400^\circ\text{C}) = 1.649 \\ + E(\text{Na,Na}_2\text{O at } 400^\circ\text{C}),$$

is essentially the same as that predicted for the two cells. This indicates that both cells would indicate essentially the same oxygen content. Since the electrolyte is essentially the same as that used in the commercial meters, the improved reproducibility must be attributed to improvements in the reference electrode.

(2) The operating temperature range of on-line oxygen meters using O_2 gas reference electrodes and $\text{Na,Na}_2\text{O}$ has been extended to $>400^\circ\text{C}$. At this temperature, the calibration of the O_2 gas electrode appears stable for at least 2000 hr.

(3) The emf of the cells is not affected by ambient air temperature as is the emf of many commercial $\text{Cu, Cu}_2\text{O}$ electrodes. During prolonged periods of steady-state loop operation the output of the cells did not vary by more than ± 1.5 mV when ambient air temperatures varied from 19° to 44°C .

(4) The meter temperature coefficient in sodium $(dE/dT)_c$ is essentially equal to the theoretical

Figure 8. Schematic representation of the completely ionic range of ThO_2 -15 wt % Y_2O_3 oxygen electrolyte.

temperature coefficient when both the $\text{Na}, \text{Na}_2\text{O}$ and O_2 gas electrodes are tested. L. EMMA, A. ROMANO, C. TIERNEY, W. TREMEL, V. WILLIAMS

Alternative Solid Electrolytes

An important aspect of the development of improved on-line electrochemical oxygen monitors for sodium coolant systems is the selection and evaluation of the solid oxide electrolytes. The criteria used in selection of materials for this application are (1) compatibility with liquid sodium at temperatures to 650°C , (2) an ionic transference number of these electrolytes close to unity, (3) ease of fabrication into forms useful in sodium electrochemical oxygen meter assemblies, and (4) ability to accommodate the thermal cycling and shock conditions encountered in liquid sodium circuits.

ThO_2 -15 wt % Y_2O_3 . This is the ceramic currently being used in the Brookhaven oxygen meters and the commercial UNC meters. The ceramic is supplied by Zircoa Corporation of

America and is used in the form of $\frac{1}{2}$ -in.-o.d. $\times$ 8-in.-long tube, closed at one end. This material is compatible with sodium for long periods of time at 400°C , but can be readily fractured in a sodium system by thermal shock. Above 500°C in liquid sodium, this material deteriorates and eventually cracks.

Measurements were made of the ionic transference number of ThO_2 -15 wt % Y_2O_3 by means of emf techniques that utilize Si, SiO_2 electrodes in cells of the type

to achieve oxygen activities slightly below those characteristic of liquid sodium, and cells of the type

to study the characteristics of oxygen gas reference electrodes.

The completely ionic range for this material is shown schematically in Figure 8. The ionic range of the electrolyte is defined as that area of a free energy vs temperature plot in which the ionic transference number is >0.99 . In this region the deviation of the emf from the theoretical thermodynamic value is negligible. The shaded region of the plot to the right of the solid line designated $t_i = 0.99$ is where the emf of a cell begins to fall below the theoretical value because of the onset of electronic conductivity. The line defining $t_i = 0.5$ and the free energy functions for $\text{Na}, \text{Na}_2\text{O}$ and liquid sodium containing 1 ppm oxygen are also shown in Figure 8. High values of oxygen concentration fall intermediate between these two lines. The free energy functions for $\text{Cr}, \text{Cr}_2\text{O}_3$ and Si, SiO_2 are also shown for comparison.

Measurements have also been made on ThO_2 -15 wt % Y_2O_3 disc samples supplied to us by J.L. Bates of PNL. PNL finds their material to be more compatible with liquid sodium because of a lower impurity content and a single-phase structure. The ionic range of this electrolyte at low oxygen activities is defined by the dotted line $t_i = 0.99$ in Figure 8. The results are not significantly different from the solid line shown for the Zircoa material, and it is believed that the electrochemical behavior of these two materials in sodium oxygen meters will be indistinguishable. In conclusion, the results of these measurements show that ThO_2 -15 wt % Y_2O_3 inherently exhibits wholly ionic behavior at temperatures up to 550°C , even in sodium containing 1 ppm oxygen. At high oxygen activities

(1 atm) the ionic transference number is less than unity; however, the values are sufficiently high to allow the use of oxygen gas reference electrodes in the electrochemical sodium oxygen meters.

Other Electrolytes. Because of the poor sodium compatibility of the available ThO_2 -15 wt % Y_2O_3 tubes used in current sodium oxygen meters, a search has been made for commercial sources of alternative ceramic electrolytes which would exhibit improved sodium compatibility. The following materials, obtained in the form of disc samples, exhibit improved compatibility with liquid sodium. Our measurements of the ionic range of these materials indicate that they are potentially useful as solid electrolytes in liquid sodium to at least 500°C. The materials studied were (1) ThO_2 -~2 wt % CaO , a material being developed at the General Electric Research Laboratory under the trade name Thoralex, (2) ThO_2 - CaO - Y_2O_3 , a proprietary composition made up for BNL by the General Electric Co. (this composition, high purity ThO_2 -15 wt % Y_2O_3 , and ThO_2 - CaO are being fabricated into small quantities of short tubes by isostatic pressing for use in experimental phototype oxygen meters), (3) Y_2O_3 -~5 mole % ThO_2 material available in limited sizes and shapes from the General Electric Co. under the trade name Yttralox, and (4) ThO_2 -7 wt % Y_2O_3 disc samples supplied by PNL and reported to have good sodium compatibility.

F. SALZANO, H. ISAACS,
C. AUERBACH, W. KALINOWSKI

The Effect of Y_2O_3 Concentrations on the Oxygen Transference Number

The effect of Y_2O_3 concentration on the ThO_2 tubes used for constructing $\text{Na}, \text{Na}_2\text{O}$ oxygen meters was studied by comparing their response with that of an oxygen meter constructed with a nominal 15 wt % Y_2O_3 concentration. The latter composition has been found to give a t_{ion} value of 0.85 from the slope of its calibration curve (i.e., the deviation in slope of a potential vs the logarithm of the oxygen concentration plot from ideal behavior). Most results for 15 wt % Y_2O_3 have given t_{ion} of close to 0.85 although exceptions have been observed (one tube gave a value of unity and contained 15.8 wt % Y_2O_3).

Table 12 gives the results obtained for Y_2O_3 concentration of zero to 10% at 400° and 500°C. As seen from this table the value of t_{ion} increases with Y_2O_3 concentration. At zero Y_2O_3 concentration in pure thoria, no sensible measurements

could be made and the thoria was reduced by the sodium to give a black and friable oxide, while at 7.5 wt % Y_2O_3 the value of t_i is only one-half. However, it appears that Y_2O_3 above 15 wt % may give a t_i value very close to unity.

H. ISAACS,
W. BECKER

DEVELOPMENT OF ON-LINE CALIBRATION METHODS FOR OXYGEN METERS B. MINUSHKIN, L. NEWMAN

A technique is required that can be routinely used to calibrate initially or to redetermine the calibration of on-line oxygen meters. The device must be rugged and relatively simple to operate, and should provide calibration data that are direct and easy to interpret. Ideally a calibration of both oxygen concentration and activity vs emf is desired. The basic approach is to develop *in situ* methods for determining oxygen content by independent techniques or for making known changes in oxygen content or activity, and observing their effects in the meter.

The techniques being considered include (1) oxygen removal by uranium gettering and lithium injections, (2) oxygen addition by extrusion of solid or slurry mixtures of $\text{Na}, \text{Na}_2\text{O}$ or injection of oxygen-spiked liquid potassium, O_2 gas, or O_2 -He mixtures, (3) electrochemical techniques using coulometric additions or titrations of oxygen, and (4) oxygen activity standards - metal-metal oxide buffer solutions, sodium-sodium oxide (i.e., unity oxide activity).

On-Line Calibration by Uranium Gettering

Work has started to adapt the uranium gettering technique for calibrating oxygen meters in a loop. In preliminary tests, uranium foils were used in a batch sampling apparatus to determine the

Table 12
The Effect of Y_2O_3 Concentrations in ThO_2
on the Transference Number for Oxygen

Y_2O_3 concentration	t_{ion}	
	400°C	500°C
0	0	0
3.1	0.23	—
7.5	0.51	0.55
9.6	—	0.63
15	0.85	0.85

oxygen concentration *in situ*. In the first test a value of 12 ppm O was obtained by uranium gettering compared with a value of 10 ppm determined by amalgamation of a sodium sample collected at the same time. In the second test, uranium gettering indicated 65 ppm O, and two samples analyzed by amalgamation showed 53 and 10 ppm O; the latter sample was suspected as being contaminated. Work is continuing to refine this technique and to develop more convenient methods for inserting and removing the uranium.

L. EMMA, C. TIERNEY

Potentiometric Titration Using Lithium

Equipment was assembled that permits calibration of oxygen meters by potentiometric titration of oxygen by lithium. The apparatus is in effect a high temperature hypodermic syringe capable of adding precise quantities of lithium as a liquid alloy of Na-Li or Li-Hg to the sodium in which the oxygen meter is immersed. This technique will

Figure 9. Typical curve for titration of oxygen in liquid Na with Li-Hg alloy.

initially be applied to batches of Na; it should, however, be adaptable to flowing systems.

Initial tests were made at 340°C in a stirred stainless steel vessel containing 89 g Na. Lithium was added from a microburette as a Li-Hg alloy containing 0.046 wt % Li. A typical titration curve is shown in Figure 9. The emf of an oxygen gas cell is plotted against the cumulative amount of Li-Hg alloy added. The divisions refer to micrometer measurement of the displacement of the hypodermic syringe plunger and each division corresponds to addition of about 17 μg of lithium. If the titration reaction is assumed to be

the additions are equivalent to the titration of ~19 μg of oxygen per division. Initially there was no change in emf during incremental additions of lithium. After 18.7 mg of Li were added (1100 division) a transient response was observed in which the emf would rise following each incremental addition and then return to essentially the original value. After 31.8 mg Li were added subsequent additions produced a change in emf that persisted (Figure 9). The end point appears to be in the vicinity of 1.9 V; emf's greater than this probably reflect increases in Li and Hg activities in the Na.

These results indicate that (1) it is possible to titrate oxygen in sodium potentiometrically by controlled additions of lithium, and this may be the basis for a calibration technique, and (2) a large impurity source is present which reacts with lithium in the system. This initial effect could be caused by excess Na₂O (unlikely in this case), impurities such as nitrogen, hydrogen, or carbon, or a buffering reaction involving stainless steel components and surfaces. The amount of lithium added before permanent emf changes occurred corresponds to 36.3 mg oxygen or 410 ppm in the sodium. Approximately the same quantities of carbon and nitrogen could be involved but only 4.6 mg of hydrogen would be required to titrate 31.6 mg of lithium. Except in the case of hydrogen it is certain that these impurities could not have originated from the sodium, thus again demonstrating the presence of relatively large impurity (oxygen?) sources in stainless steel systems.

R. SINGER, G. KISSEL, R. MITCHELL

Coulometry

The coulometric addition of oxygen to and removal from sodium offers a simple, rapid, and

sensitive method for studying the behavior of oxygen in sodium. Tests have been conducted at 500°C that demonstrated that oxygen can be added or removed by the passage of current across a ThO_2 -15 wt % Y_2O_3 electrolyte. The oxygen concentration in the sodium was monitored with an oxygen meter having an oxygen-saturated-sodium reference electrode. No current was passed through the oxygen meter.

The behavior of oxygen in these tests, which used undistilled Na, was characterized by the presence of a buffering reaction which was in equilibrium at an oxygen concentration of about 100 ppm (or 90 mV). A potential arrest was also observed at a concentration of about 3 ppm (195 mV). A concentration lower than this value (or a potential >195 mV) could not be achieved in this experiment. H. ISAACS, F. SALZANO, W. BECKER

DEVELOPMENT OF AN ELECTROCHEMICAL METER FOR CARBON IN SODIUM

F. SALZANO, W. KALINOWSKI

The feasibility of using an electrochemical cell continuously to monitor changes in the chemical activity of carbon in liquid sodium has been demonstrated. Several engineering prototype electrochemical carbon meters have been built and tested in sodium contained in small static vessels for periods up to eight weeks. Two units have been installed in FCL-2 and are currently being tested during the normal course of its operation. A photograph of the first engineering prototype is shown in Figure 10.

To date, techniques have been developed that use two different electrolyte systems in the same basic sensing element, i.e., a 5-mil-wall pure iron cup, 1/2 in. o.d. × 2 in. long. The electrolytes (a CaC_2 -LiCl solution and a Na_2CO_3 - Li_2CO_3 eutectic) are being utilized in the cell configurations

and

Both systems respond to changes in the chemical activity of carbon in the sodium which result from additions of carburized iron and various other

carbonaceous reagents such as Na_2C_2 , CO, C_2N_2 , and C_2H_2 to the sodium.

The principle of operation is to allow the thin iron membrane to come to equilibrium with the liquid sodium, i.e.,

$$a_{\text{C}}(\text{Na}) = a_{\text{C}}(\text{Fe}).$$

The chemical activity of carbon in the sodium, $a_{\text{C}}(\text{Na})$, is determined by measuring the chemical activity of carbon in the iron membrane, $a_{\text{C}}(\text{Fe})$, by means of the above electrochemical carbon concentration cells in which the emf's are given by the expression

$$E = (RT/n\mathcal{F}) \ln[a_{\text{C}}(\text{R})/a_{\text{C}}(\text{Fe})],$$

where $a_{\text{C}}(\text{R})$ is the chemical activity of carbon at the reference electrode and n is the number of electrons per carbon atom involved in the electrode reaction. The response of cells (1) and (2) to changes in carbon concentration in iron has been established independently of sodium by Hawkes and Morris [*Trans. AIME* 242, 1083 (1968)] and

Figure 10. First engineering prototype electrochemical carbon meter for use in sodium.

by Salzano and Hobdell (BNL 50176 and BNL 50193), respectively.

It has been demonstrated that when cells (1) and (2) are placed in type 347 stainless steel vessels containing liquid sodium in the temperature range 600° to 700°C a constant emf is observed which reflects a fixed chemical activity of carbon in the sodium. The potentials observed for these cells are ~100 and 50 mV, respectively, at 685°C. Preliminary evidence suggests that the carbon activity in these systems is determined by an equilibrium involving the stainless steel container. Upon addition of small amounts of carbon as Fe₃C (carburized iron), sodium carbide, or other carbonaceous reagents, the emf decreases and can be made zero for transient periods, but returns to the 100-mV (cell 1) or 50-mV (cell 2) level in varying periods of time from several hours to several days depending on the total amount of carbon added to the vessel. The same general response is obtained with both cells (1) and (2) except for the equilibrium emf level which is a function of the carbon activity

Figure 11. A comparison of the emf vs temperature behavior of CaC₂-LiCl and Na₂CO₃-Li₂CO₃ electrolytes in the same sodium vessel.

at the reference electrode and the number of electrons per carbon atom involved in the electrode reaction. It is believed that the electrode reactions for cells (1) and (2) are respectively

and

although experiments to positively identify these reactions have not been performed to date.

The temperature dependence of the carbide and carbonate electrolyte cells in the same sodium vessel is shown in Figure 11. The opposite sign of the emfs is in agreement with the proposed electrode reactions. The slopes differ by a factor of four as would be expected by the ratio of the number of electrons involved in the above cell reactions. The lack of perfect agreement in the ratio of the absolute emfs of the two electrolyte systems is not completely understood. The magnitude of the emf in the case of the carbonate system is in agreement with calculations of the expected emf for a stainless steel system, if one assumes that the carbon activity is controlled by the reaction

IDENTIFICATION OF CHEMICAL SPECIES AND REACTIONS OF SOLUTES IN SODIUM B. MINUSHKIN

Solubility and Reactions of Oxygen in Sodium

Measurements of emf were made using solid electrolyte cells of the type

Cells I and II were used to determine the solubility of oxygen in sodium and the standard molar free energy of formation of Na₂O, respectively, and to construct a free energy-temperature-composition diagram for the sodium-oxygen system based on emf measurements. Cell III was used in a prelimi-

$$E = \frac{-2.3RT}{2f} \log_{10} \frac{C}{C_0}$$

$$\log_{10} C_0 = A + \frac{B}{T}$$

$$E = \frac{2.3R}{2f} (A - \log_{10} C)T + \frac{2.3RB}{2f}$$

$$\left(\frac{dE}{dT}\right)_C = \frac{2.3R}{2f} (A - \log_{10} C) = \text{Slope}$$

$$E = \left(\frac{dE}{dT}\right)_C T + \frac{2.3RB}{2f}$$

Figure 12. Relationships for determination of oxygen solubility from emf measurements.

Figure 13. Solubility of oxygen in sodium.

nary study of reactions between iron and oxygen dissolved in sodium.

A ThO_2 -15 wt % Y_2O_3 solid electrolyte tube containing the reference electrode was immersed in sodium in an inert beaker within a stainless steel tank. Provisions were made for stirring the sodium and for introducing sodium oxide or uranium foils into the sodium through an inert gas lock.

The oxygen solubility relationship was obtained from emf measurements in the following manner. Sodium containing a constant amount of oxygen was heated to a series of different temperatures and the emf was recorded after both temperature

and emf were constant for at least one hour. Knowing the electromotive force-temperature dependence for Cell I at constant oxygen $[(dE/dT)_C]$ and using uranium gettering to determine the oxygen concentration one can solve for the constants in the solubility relationship

$$\log C_0 = A + (B/T).$$

The relationships are summarized in Figure 12.

The solubility of oxygen in sodium, as determined by this method, is given by

$$\log C_0 \text{ (ppm O)} = 6.46 \pm 0.11 - (2600/T, ^\circ\text{K})$$

over the temperature range 350° to 550°C . This relationship is shown in Figure 13 along with some solubility data obtained by conventional sampling and analytical techniques and a statistical correlation of those data proposed by Eichelberger. The agreement between these relationships (or between the plotted data and the emf relationship) obtained by different and independent methods lends increased confidence to the accuracy and validity of the solubility relationship. The heat of solution of Na_2O in Na derived from these emf measurements is $\Delta H_{\text{sol}} + 12,000$ cal/mole Na_2O .

The emf of Cell II, utilizing an oxygen gas reference electrode, is related to the standard molar free energy of formation of Na_2O at constant temperature by

$$E_{\text{meas}} = (-\Delta F^\circ_{\text{Na}_2\text{O}} \bar{t}_{\text{ion}}) / 2f,$$

where E_{meas} is the measured emf of Cell II, $\Delta F^\circ_{\text{Na}_2\text{O}}$ is the standard molar free energy of formation of Na_2O , and $\bar{t}_{\text{ion}}$ is the effective ionic transference number for the cell. Measurements were made at temperatures from 325° to 550°C in sodium containing a large excess of sodium monoxide. After the initial measurements additional oxide was added without changing the emf, indicating that the sodium was in fact saturated (activity ± 1). The results of these measurements are shown in Figure 14 along with thermochemical data tabulated by Wickes and Block and by Elliot and Gleiser. The equivalent free energy of formation in kcal/g atom O was calculated from emf data assuming $\bar{t}_{\text{ion}} = 1$. Recent work indicates that the $\bar{t}_{\text{ion}}$ for the O_2 gas vs $\text{Na, Na}_2\text{O}_{(\text{sat})}$ cell is < 1 and therefore the calculated free energies may be lower than the thermodynamic values. The maximum error in the calculated free energies due to departure from ionic behavior occurs at low temperature ($\sim 325^\circ\text{C}$) and is estimated to be

Figure 14. Emf vs temperature for the cell:
 $\text{Pt}, \text{O}_2(1 \text{ atm}) \parallel \text{ThO}_2\text{-}15 \text{ wt } \% \text{Y}_2\text{O}_3 \parallel \text{Na}, \text{Na}_2\text{O}(\text{sat})$.

Figure 15. Emf-temperature-composition diagram for sodium-oxygen system.

Figure 16. Emf-temperature behavior for system containing solid and dissolved iron.

about 6 to 8 %; the error should be lower at higher temperatures.

The oxygen solubility and the $\Delta F^\circ_{\text{Na}_2\text{O}}$ values obtained from emf measurements were combined to produce a temperature-composition emf (or free energy) diagram for the sodium-oxygen system (Figure 15). The figure also shows thermochemical data for Cr_2O_3 and sodium ferrate as reported by other investigators. The diagram indicates the approximate conditions (composition and temperature) under which the metals may react with oxygen in sodium.

Preliminary studies of the interaction between oxygen and iron in sodium utilizing iron (at unit activity) reacts with oxygen dissolved in sodium (less than unit activity) to form a more stable compound. The emfs of Cell III and of similar cells which did not contain excess solid iron were measured as a function of temperature at several oxygen levels (Figure 16). At low oxygen levels (< 100 ppm) in the absence of excess iron (Cell II), the emf vs temperature data give straight lines similar to the lines of constant composition in Figure 15 for temperatures from about 300° to 550°C . In the presence of excess solid iron the emf vs temperature data has the expected slope and value for the normal oxygen content at high temperature. As the temperature is decreased, a point is reached at which the slope of the line increases abruptly. This occurs at an emf ~ 60 to 100 mV higher than the $\text{Na}, \text{Na}_2\text{O}$ saturation line. The temperature at which this break occurs appears to increase with increasing concentration. At temperatures below the break temperature a single line is obtained regardless of apparent oxygen content, which is approximately parallel to but 60 to 90 mV above the $\text{Na}, \text{Na}_2\text{O}$ saturation line. When a quantity of sodium oxide equivalent to ~ 3 times the solubility was added at 400°C , the emf initially decreased to 1.684 V (higher than the expected saturation value), then rose slowly to a value which was on the line defined by the break in the emf vs temperature data.

This behavior suggests the formation of a new species, which we attribute to a reaction between oxygen and iron in sodium. The line defined by the temperature at which the break occurs should then represent the equilibrium between dissolved oxygen, unit activity of iron, and a new Na-O-Fe phase:

The nature of the reaction and the composition of the product cannot be determined from emf data obtained to date. However, the free energy change for the reaction when the iron, Na, and the product are at unit activity is tentatively set at ~ -3 to -4.6 kcal/g-atom O (60 to 100 mV) with respect to sodium saturated with Na_2O . Assuming a theoretical calibration for the cell this would correspond to an oxygen activity of about 0.2. This value of ΔF is in fair agreement with the thermochemical value (estimated from heat of reaction data between Na_2O and Fe) for the complex $\text{FeO} \cdot 2\text{Na}_2\text{O}$ reported by Thorley and Tyzack. Further work is in progress to identify positively the nature of the reaction and composition of the product.

B. MINUSHKIN, G. KISSEL, V. WILLIAMS

The Behavior of Oxygen in Sodium

Oxygen Meter Experiments. The effects of chromium on oxygen in sodium-buffering reactions have been observed in sodium using an electrochemical oxygen meter. The observed effect is probably due to the presence of redox reactions involving an impurity in contact with the sodium. Chromium has been considered to be a possible species that could account for this effect and experiments are being conducted to determine the effects of chromium and its oxides on the behavior of oxygen in sodium.

Distilled sodium (300 g) was held in a zirconium container that was heavily oxidized in dry oxygen to form a thick adherent oxide and render the container inert to oxygen. The temperature was held at 500°C . Tests were conducted that showed no marked buffering in the distilled sodium or when small quantities of solid Cr_2O_3 (about 70 mg) and Cr (40 mg) were added to the sodium. The buffer-

ing is defined mainly by the observation of the potential increasing after small quantities of Na_2O are added to the sodium. The size of the Cr_2O_3 particles was $\sim 2 \mu$ and that of Cr, 100μ . However, after 300 mg of Cr_2O_3 were added, an apparent buffer potential occurred at a concentration of 14 ppm O. The marked observation made during this study was that, when quantities of Cr_2O_3 were added to the sodium, the measured potential increased indicating that oxygen was being removed from the sodium. The surface area of the powder added was large, but the observed decrease in oxygen concentration was too high to be accounted for by adsorption and the decrease in oxygen concentration indicates a reaction involving Cr_2O_3 and oxygen dissolved in the sodium. This work therefore strengthens the tentative explanation (made previously) of the buffering of oxygen in sodium resulting from the presence of a compound involving chromium.

H. ISAACS

The Effect of Hydrogen on Oxygen in Sodium.

Hydrogen when added to sodium interacts with the oxygen dissolved in the sodium. Figure 17 shows the response of an electrochemical oxygen meter to the addition of hydrogen to the sodium, and the rate at which hydrogen reacted with the sodium. The rate of hydrogen reaction with the sodium has been shown to be controlled by a surface reaction and therefore gives sufficient time for the hydrogen to distribute itself in the sodium and interact with the dissolved oxygen. This effect is reflected in the similarity between the rates of hydrogen reacted and increases in the potential of the oxygen meter.

H. ISAACS, W. BECKER

SOLUBILITIES AND KINETICS OF SOLUTION OF STRUCTURAL METALS IN SODIUM

H. ISAACS

Solubility of Metals in Sodium

Iron. The latest iron solubility results using irradiated high-purity iron are shown in Table 13. These results, which show <0.05 ppm Fe soluble in 650° to 800°C Na, were obtained by adding ~ 0.3 g of irradiated Fe foil to a Mo crucible containing ~ 500 ml of distilled Na. Earlier BNL iron solubility data plotted in Figure 18 were obtained using an irradiated Fe crucible filled with distilled sodium, and show 1 to 2 orders of magnitude higher Fe solubility than the recent data. The present results are of the order of magnitude

Figure 17. The effect of hydrogen on the chemical activity of oxygen in sodium.

Table 13				
Solubility of Fe in Low Oxygen Sodium ^a				
Temperature, °C	ppm Fe (radiochemical)		ppm Fe (colorimetric)	
	Na	HCl + Mo cup ^b	Na	HCl
650	0.016	0.019	≤ 1.0	≤ 0.5
700	≤ 0.05	≤ 0.05	≤ 0.5	≤ 0.5
750	≤ 0.04	≤ 0.05	≤ 1.0	≤ 0.5
800	≤ 0.05	≤ 0.20	≤ 0.6	≤ 0.5

^aSodium was contained in a Mo crucible. Uranium foil was used to getter out all oxygen in the sodium before samples were taken.

^bThe Mo bucket was leached in HCl after the Na was removed. Both the HCl solution and the Mo bucket were analyzed for ⁵⁹Fe.

Table 14	
Solubility Data of Fe in Na by Bogard (NRL 4131)	
Temperature, °C	ppm of Na
395	0.006
560	0.010
762	0.020 ^a

^aExtrapolated straight line plot of $1/T$ vs log ppm from 560°C.

of the low-oxygen iron solubility results obtained by Bogard (NRL-4131, 1953), which are shown in Table 14. The <0.05 ppm Fe solubility data are also more indicative of the measured steady-state corrosion rate of stainless steel in low oxygen sodium as determined by many investigators, if one assumes that a differential solubility is the driving force for corrosion of steels.

The solubility of Fe in 650°C sodium to which 100 to 1000 ppm oxygen were added has also been determined radiochemically; the results are given in Table 15 and plotted in Figure 19. At 100 ppm oxygen the Fe solubility increases by a factor of 10 over that at ~ 1 ppm while at 600 ppm the Fe solubility is 100 times greater. Thus these results indicate that even small amounts of oxygen in Na will cause an appreciable increase in the iron solubility results, which may in part account for some of the variations reported previously.

The current sodium sampling technique was discussed in detail in the preceding report. In brief, three "thief" type samples of ~ 1.0 g each of Na

Figure 18. Solubility of Fe in Na. Comparison of BNL results with all available data. Results using irradiated Fe crucible.

are taken simultaneously in covered Mo buckets containing two 0.076-in. holes. The sodium is then dissolved in butyl chloride, acidified, taken to dryness, water added, and counted for ⁵⁹Fe in Na. Iron in the solution is also determined colorimetrically as iron bathophenanthroline in a spectrophotometer. Each Mo bucket is then leached with HCl in order to remove any Fe on the Mo surface, and both the empty Mo bucket and the leach solution are counted. The leach solution is also analyzed for Fe in the spectrophotometer.

Many of the colorimetric Fe determinations are above the detection limit of 0.5 to 1.0 ppm as shown in preceding reports and in Table 15, while the radiochemical Fe results in low oxygen Na are always below the ⁵⁹Fe detection limit of ≤ 0.05 ppm. The colorimetric Fe analyses shown in Table

Table 15

Fe Solubility in 650°C Na to Which 1 to 1000 ppm Oxygen Were Added
(The melt was equilibrated for ~24 hr after each oxide addition before sampling.)

Sample number	Oxygen, ppm	Wt of Na, g	$\mu\text{g Fe}$ (radiochemical)			$\mu\text{g Fe}$ (colorimetric)	
			Na	HCl	Mo ^a	Na	HCl ^b
221-43, 48, 49	~1	3.62	0.06	0.07	≤ 0.02	Not run	
268-14, 17, 51	~100	4.66	1.0	≤ 0.1	≤ 0.2	5	≤ 0.5
269-15, 16, 17	~200	4.35	3.68	0.2	0.3	10	≤ 0.5
270-1, 12, 25	~300	3.79	4.18	0.2	1.1	10	1.0
271-4, 19, 23	~600	3.42	9.1	0.4	0.7	8.5	0.7
272-28, 42, 49	~700	3.56	10.2	0.6	1.1	11	1.2
273-13, 34, 55	~1000	4.27	14.6	1.0	2.8	13	1.2

^aMo bucket was counted for ⁵⁹Fe after leaching with HCl.

^bMo sample bucket leached in HCl solution after Na was dissolved in butyl chloride.

13 represent the minimum Fe results found at each temperature.

Chromium and Manganese. The determination of the solubility of Cr in 650° to 800°C low oxygen sodium using ⁵¹Cr is under way. Preliminary results suggest that the solubility of Cr in Na is ~0.4 ppm at 650°C. Figure 20 compares this result with those obtained at AI (ANL 7520), and suggests the tentative solubility curve shown on the figure. When the further Cr runs are completed, the Na-Mn liquidus will be investigated.

A. FLEITMAN, H. ISAACS, W. BECKER,
J. SAULS, G. SPIRA

Segregation of Impurities and Formation of Particles at the Sodium/Gas Interface

The surface of the sodium in contact with the inert gas was considered as a possible area where segregation of impurities may occur. The inert gas which is in contact with the cover of the sodium containing vessel is generally cooler than the sodium itself. The liquid-gas interface could also have a higher concentration of dissolved constituents because of adsorption forces.

Samples of the surface of sodium contained in a stainless steel vessel held at 500°C for more than a month were taken with shallow molybdenum containers, ~1 cm in diameter and 2 mm deep, pretreated in a manner similar to those used in solubility experiments. The containers were immersed just below the surface of the sodium and left for ~5 min to allow the surface to come to rest. After removal, the sodium in these containers was ana-

lyzed for iron and chromium. The results are shown in Table 16. This table includes the bulk concentrations of these constituents in the sodium, which were sampled in the same manner as in the solubility experiments. As can be seen from the table, the amounts of iron and chromium were greater at the surface than in the bulk and gave definitive evidence that these metals were segregated at the sodium surface. If metallic particles were formed at the sodium surface, it would be expected that some particles would sink to the bottom of the container. The samplers used to obtain sodium from the bottom of the stainless steel container consisted of a copper tube sealed at both ends with a 1-mm hole drilled through the bottom seal. The tube was filled after immersion in the sodium when it contacted the bottom of the container by initially decreasing the cover gas pressure to expel gas from the copper sampler; the pressure was then increased, compressing the gas in the samplers and forcing sodium to enter the container; these results are also given in Table 16. When these copper samplers were used to obtain samples from the bulk sodium the concentration of iron was <0.6 ppm in agreement with those shown in the table. These experiments suggest that particles of iron are formed at the surface of the sodium and can grow to sufficient size to break the surface tension forces and sink to the bottom of the container.

The nonmetallic impurities, carbon and oxygen, were found to segregate at sodium surfaces. Uranium was partially immersed in sodium

Figure 19. Solubility of Fe at 650°C in Na to which the concentrations of oxygen given were added. Results using irradiated Fe tab in Mo crucible.

Figure 20. Comparison of the BNL results at 650°C (error bar) with the Cr data of Eichelberger and McKisson (AI). Parentheses refer to methods of analyzing samples for Cr. AAS = atomic absorption spectrography.

Table 16

Concentration of Metal at the Liquid/Gas Interface

Metal	Metal concentration		
	Surface	Bulk	Bottom
Fe	100, 180 260, 130	<0.6 ^a	2.6, 1.0 0.8, 1.5
Cr	0.8, 1.7 0.8, 1.3	0.4, <0.1 0.4, 0.3, 0.1	

^aTen determinations all <0.6.

which had a bulk concentration of oxygen of the order of 1 ppm. After removing the uranium and cleaning it, the surface of the immersed uranium showed interference colors but the uranium surface at the interface between the inert gas and the sodium was grey, which indicated a thicker oxide. As the rate of oxidation of uranium is proportional to the oxygen concentration and mobility, it indicates that oxygen concentration at the sodium surface was greater giving a greater oxide thickness.

Carbon was found to deposit on all metals which were partially immersed in the sodium for periods of time of the order of 1 hr at temperatures of 400°C and higher. At a temperature of 650°C the deposit on stainless steel was of the order of 1 mm thick at the sodium surface and decreased to zero at about 5 mm above the surface. At 400°C there was only a visible black deposit.

Similar tests were carried out in a container that held sodium saturated with copper at 500°C. Tabs of molybdenum were partially inserted in this sodium and deposits of copper were found at the sodium-gas interface. Figure 21 shows the copper crystals that had grown with the 111 crystallographic face parallel to the molybdenum surface. Molybdenum foils 1.27 cm in width were immersed in copper-saturated sodium at various temperatures for 72 hr, and the amount of copper deposited was determined by chemical analysis. Weight gains of the foils were higher than the quantities of copper determined by chemical analysis. The low temperature deposits were too small to influence the process of deposition but at the high temperatures of 600° and 650°C it appeared that the porous deposit acted as a capillary network and increased the height of the "meniscus." Figure 22 shows the variation of the amounts of copper deposited as a function of reciprocal temperature.

Figure 21. Copper crystals deposited on molybdenum at the sodium surface. (500 $\times$.)

The deposition mechanism of both the carbon and the copper was concluded to result from the temperature difference between the cover gas and the sodium. The part of the metal not inserted into the sodium would be cooled by the gas, setting up a temperature gradient at the interface. The sodium that wets the metal foil would have a meniscus cooler than the bulk sodium. As the bulk of the sodium was saturated, the cooler sodium would be supersaturated and deposition would occur. The rate of deposition would depend on the difference in solubility between the bulk sodium and the solubility at the lower temperature of the inserted metal. However, if the difference in solubility at these two temperatures were great enough, the process would only depend on the solubility at the high temperature. This appears to be the case at temperatures of 600° and 650°C. Included in Figure 22 is the solubility curve for copper in sodium; the results at the high temperatures show

the same temperature dependence as the solubility. The formation of the increased meniscus would also assist in producing a cooler sodium area for deposition to take place, while at the lower temperatures a smaller gradient would be expected and no copper deposit would be large enough to assist in raising the level of the sodium in contact with the insert.

A method for the chemical polishing of sodium has been developed. This is done in an acetone-alcohol mixture and in pure acetone, and was found to give rise to pitting around metallic (cathodic) inclusions which were lifted out of the sodium, but did not preferentially dissolve around nonmetallic inclusions.

From these studies it appears that the formation of particles at the sodium/cover gas interface does occur. Solubility experiments that are in progress at BNL now use sampling containers fitted with removable covers in an attempt to overcome the

Figure 22. Weight of copper crystals deposited on molybdenum at the sodium surface as a function of temperature.

high surface concentrations of iron and chromium known to exist on the surface. The latest solubility results for iron in sodium appear much lower with this new sampling technique. Particulates may be formed as a result of the cooler cover gas as was observed in experiments involving copper and carbon deposits. The results obtained with copper deposition on molybdenum suggest that if this mechanism is the one for the formation of particulates, then, at low solubilities, the rate of formation of particles increases more rapidly with temperature than the rate of increase in solubility.

These results may also be relevant in the design of reactors with sodium as a coolant. Metal deposits would be expected to form on all surfaces in contact with the sodium-cover gas interface. For example, any probe left in the sodium would form deposits that could lead to serious removal problems if the probe remained in the sodium for extended periods of time. In a similar manner the sodium surface in surge tanks would be expected to give rise to deposits on the container walls that may eventually lead to plugging of the tank.

H. ISAACS, R. SINGER, W. BECKER

The Use of Uranium in Sodium Technology

Uranium has been found to react with oxygen at a rate proportional to the concentration of oxygen in sodium. The rate is controlled by the diffusion of oxygen in the sodium, or by the mass transfer coefficient for the relevant flow characteristics.

The mass transfer coefficient for rotating cylinders in large containers holding sodium was measured by observing the rate of weight gain of the cylinders rotated in the sodium of known oxygen concentration. The mass transfer coefficient k was found to be dependent on the peripheral velocity of the cylinders v (cm/sec) and was given by

$$k = 0.015 v^{0.5} \text{ (cm/sec}^{0.5}\text{)}.$$

The 0.5 power dependence of the velocity was checked using the same geometry but in an aqueous system where the mass transfer was measured electrochemically. In the aqueous systems the 0.5 power was also found when the cylinders were rotated in large containers, but an 0.8 power dependence of the velocity was observed when a small container was used. In the latter container the walls of the vessel influence the liquid flow characteristics and gave rise to turbulence, while in the larger container laminar flow was observed. These tests illustrate that uranium can be used to determine mass transfer coefficients in sodium.

Uranium has also been used to study the chemistry of oxygen in sodium. Previous results have shown that all the oxygen added to a sodium system could not be accounted for. Two stainless steel containers at 500°C holding 14 kg of sodium behaved differently. In one, about 3 to 5% of the oxygen added could not be accounted for, while in the second container, nominally the same as the first, up to 50% of the oxygen was apparently lost from the system. Sodium samples taken from the second container were chemically analyzed for oxygen, and the results agreed with the uranium analysis. Similar observations were also made with distilled sodium held in a molybdenum container at 650°C where 90% of the oxygen added to the sodium could not be accounted for. All these measurements indicate that oxygen is apparently lost from the sodium and further work is in progress to determine where the oxygen goes.

Other tests at 600° and 650°C have shown the same behavior that was observed at 500°C by using electrochemical oxygen meters. In these systems there exists an oxygen concentration at which

the oxygen is "buffered" and any addition or removal of oxygen is compensated for by the system to bring the oxygen concentration to the buffered value. The buffer concentration of oxygen was 9.0 ppm at 600°C and 11.2 ppm at 650°C, whereas at 500°C, using an oxygen meter, the concentration was 17 ppm. Although these results suggest that a source and sink are present in all sodium systems, the quantities of oxygen which remain unaccounted for are too large to be explained on this basis. The differences in the buffer concentrations between 500° and 600°C and 650°C using the different methods for oxygen concentration may appear conflicting as a result of differences in the method but may also reflect differences in concentrations of the species other than oxygen involved in the buffering reaction.

H. ISAACS,
W. BECKER

Corrosion of Pure Fe, Ni, Cr, and Co in 660° to 760°C Na

Experiments are in progress to determine the corrosion-deposition mechanism of stainless steels and cobalt-base alloys by studying the corrosion and interaction of pure Fe, Ni, Cr, and Co in Na.

Specimens of the metals having about 2.5 cm² of surface were simultaneously exposed to 660° to 760°C Na flowing at ~3 cm/sec in a type 316 stainless steel loop. The Na₂O content of the flowing Na was "controlled" by a diffusion cold trap. Tests of 1000-hr duration were performed at cold trap temperatures of 110°, 200°, and 400°C. Oxygen analyses of the Na (by the uranium method) were performed at the beginning and end of each run, in which virgin specimens (10 tabs of each metal) were used. Effects of the exposure on the specimens were evaluated by weight change measurements, x-ray fluorescence, and microscopic examination.

Typical weight change data are given in Table 17 and the results are plotted in Figure 23. The weight changes of the Co test specimens were similar to those of the iron specimens and are not shown. The results can be summarized by noting that Co and Fe specimens gained weight (0.7 to 0.8 mg/cm² max) while all Ni specimens lost weight (~2.0 mg/cm² max) with the exception of those Ni specimens in low oxygen (4 to 10 ppm), low temperature (660° to 700°C) Na. In general the largest Fe, Ni, and Co weight changes occurred at the highest temperature. The Co specimens were the only ones to show a slight general weight increase with an

Table 17

Corrosion of Pure Fe, Ni, Cr, and Co in Na
Containing ~110 ppm Oxygen^a
(Weight change, mg/cm² in 1000 hr.)

Temperature	Fe	Co	Ni	Cr
760° C	+0.27	0.40	-0.87	+0.06
	+0.22	0.36	-0.53	+0.04
	+0.14	0.23	-0.14	0
	+0.15	0.17	-0.56	0
	+0.16	0.16	-0.24	0
	+0.30	0.30	-0.18	+0.01
	+0.08	0.08	-1.10	0
	+0.10	0.10	-0.50	+0.06
	+0.13	0.13	-0.79	-0.11
660° C	+0.21	0.21	-1.05	+0.07

^aDiffusion cold trap at 400°C; 160 ppm oxygen at start of run; 60 ppm oxygen at end of run.

increase in oxygen. The Cr specimens showed both small weight gains and losses in 4 to 10 ppm Na but the specimens in the 110 ppm Na showed only slight weight gains or no change. The latter Cr specimens were covered with a gray film while the Cr specimens in 4 to 10 ppm Na had a matte finish.

Microscopic examination of the previously polished side of the test specimens showed them to be etched, i.e., the grain boundaries were attacked. X-ray fluorescence analysis (XRF) of the polished side of the 760° and 660°C specimens indicated that Fe, Ni, and Cr were present on the specimens. A trace of Co was found on the Ni specimens from the 110 ppm oxygen run. Results of the XRF analyses are given in Table 18. Thus it is obvious that simultaneous dissolution and deposition are occurring during the corrosion process. The mass transfer of the metals to each other indicates a trend toward quasi-equilibrium of all surfaces, e.g., under steady-state conditions the specimens in the same location will have the same surface activity.

A comparison of the "amount" of mass transfer of each metal at different oxygen concentrations is shown in Figure 24. This plot, combined with the weight change data and the results of the microscopic study, suggest the following conclusions.

(1) The weight gains of the specimens are the result of mass transfer of the metals (and of the constituents of the stainless steel loop) to each other.

Figure 23. Sodium corrosion of pure metals in 1000 hr. Weight change vs temperature.

Figure 24. Total Fe, Cr, Ni, and Co deposited on the 660° and 760°C corrosion specimens after 1000-hr tests in Na containing 4, 10, and 110 ppm oxygen.

(2) Of all the metals, Co has the lowest tendency to mass transfer in a 316 SS system.

(3) At low oxygen levels (4 ppm), mass transfer of Cr and Ni predominates. At higher oxygen levels (110 ppm), mass transfer of Fe is predominant.

(4) The corrosion of Ni (weight loss) increases sharply from 660° to 760°C but appears to be relatively insensitive to the oxygen concentration between 4 to 110 ppm.

(5) Mass transfer of Cr and Co increases slowly with oxygen content.

Table 18

X-ray Fluorescence Analysis^a
of Surface of Test Specimens After 1000-hr Exposure
to 660° to 760°C Na Flowing at ~3 cm/sec

Specimen	4 ppm Oxygen		10 ppm Oxygen		110 ppm Oxygen	
	660 °C	760 °C	660 °C	760 °C	660 °C	760 °C
% Cr on Surface						
Ni	3.82	2.44	5.35	—	4.03	4.23
Fe	2.48	1.53	3.15	2.10	3.05	3.33
Co	3.78	0.78	2.80	0.75	3.45	0.96
% Fe on Surface						
Ni	0.86	0.86	0.43	—	16.70	18.60
Co	0.43	none	0.20	0.13	11.30	2.10
Cr	none	none	0.27	0.13	0.37	0.26
% Ni on Surface						
Fe	0.89	1.05	1.16	0.82	3.40	1.47
Co	0.20	0.13	0.15	0.89	0.36	0.38
Cr	0.81	0.55	0.89	trace	0.25	trace

^aIncoloy-800 standard.

(6) Under steady-state conditions the surfaces of the 316 stainless steel loop and the Fe specimens in the same area will eventually have the same composition. The XRF analysis of the surface of the Fe specimens suggest the following 316 stainless steel surface compositions at steady state:

	660°C		760°C	
	4 to 10 ppm	110 ppm	4 to 10 ppm	110 ppm
Cr	<4%	<4%	<1%	<4%
Ni	<1%	<3%	<1%	<1.5%

A. FLEITMAN, D. HORNE, B. GALEN,
H. ISAACS, C. KLAMUT

EFFECTS OF SODIUM ON MECHANICAL PROPERTIES OF MATERIALS J. CHOW, K. HOFFMAN

The high cycle fatigue program is concerned with the testing of LMFBR materials of construction to determine the effects of sodium and steam environments on their fatigue properties and crack propagation. Heat exchanger tubing materials such as type 304 stainless steel, low Cr-Mo alloy steels, and Incoloy 800 are of special interest because of the vibration and tubing fatigue problems

that have been observed in heat exchange equipment. Tests in the cycle range of 10^5 to 10^{10} , at temperatures of 427° to 565°C , will be performed in this program.

Ultrasonic test equipment operating at a stress cycle frequency of 20,000 cps is used for accelerated testing to obtain fatigue data in the 10^8 to 10^{10} cycle range. Two MTS push-pull fatigue testing machines are being used to collect data in the 10^5 to 10^8 cycle range at a frequency of 40 to 60 cps. The MTS machine is a closed loop electrohydraulic system with a 20,000-lb load frame and a ± 5000 -lb activation and load cell. There may be a frequency effect over the wide cycle range to be studied, and the use of these two testing techniques will give an indication of this effect.

Effort to date has been to set up and calibrate the testing machines. One MTS machine has been set up and the other machine will be delivered in February 1970. The ultrasonic machine has been installed.

The installed MTS machine has been calibrated and tests are being run on type 304 stainless steel at 427°C in air. Hourglass-shaped specimens with 0.125-in. gage diameter are being used. The data obtained with this specimen will be compared with published data and also will be used for comparison with data obtained in sodium and steam environments.

Design work was completed on a sodium chamber to test specimens in a sodium environment with the MTS machines. A sodium chamber for the MTS machines and a thermal convection Na loop for the ultrasonic fatigue test machine were designed.

ANALYTICAL DEVELOPMENT

T. PRACH, W. CROCKETT, L. NEWMAN

A procedure was developed for determining carbonate in sodium whereby a sodium metal sample is amalgamated and washed with mercury inside an inert atmosphere dry box. The sodium carbonate residue is treated with sulfuric acid. The resulting carbon dioxide is swept from the acid solution with helium, collected on a liquid nitrogen-cooled glass-chip-trap, and measured on a gas chromatograph. Results on samples taken from the sodium chemistry loop and corrosion test loops indicate that <2 ppm oxygen was present as carbonate. The average deviation at this level was $<\pm 10\%$.

An amalgamation technique for the determination of carbon in sodium was attempted. During these experiments it was found that the amalgamation vessel picked up carbon contamination in the order of 20 to 40 μg when the vessel was evacuated in the air lock prior to introduction into the dry box. Continuing efforts are being made to reduce the source of this contamination which is apparently due to oil backstreaming.

Superconductivity

D. SCHWEITZER, M. STRONGIN

Studies in superconductivity represent a combined effort of the Applied Science, Physics, and Accelerator Departments. Only the portion sponsored by the Applied Science Department is reported here. It includes work on hysteresis in superconductors, studies at temperatures below 0.1°K , and superconductivity in thin films.

EQUILIBRIUM HYSTERESIS

Studies on the thermodynamic origin of hysteresis have been extended from both a theoretical and experimental approach. From the theoretical point of view there are two general types of arguments that lead to the conclusion that hysteresis can result from equilibrium. Physical theories involving single valued equations of state (i.e., $PV=nRT$, $-4\pi M=H-B$, etc.) imply reversibility by the very nature of the equality sign. In other words, the values of P , V , M , H , B , etc., are assumed to be independent of whether they are reached from lower or higher values. The first problem then is to determine a criterion from a thermodynamic equation that defines hysteresis. This can be obtained from the second law of thermodynamics which states that for a reversible path

$$\int dS = \int dQ/T, \quad (1)$$

and for an irreversible path

$$\int dS > \int dQ/T, \quad (2)$$

where Q is the heat absorbed and S is the entropy. The condition for equilibrium isothermal hysteresis between two states A and B is then one in which the Gibbs free energies of the two states are equal at the same temperature, ($G_A = G_B$), and

$$\Delta Q \neq T\Delta S. \quad (3)$$

The generalized conditions under which these two requirements are fulfilled are summarized below. Assume that the Gibbs free energies of two realizable states of a system are given respectively by

$$G_1 = U_1 - TS_1 + F_1 X_1 \quad (4)$$

and

$$G_2 = U_2 - TS_2 + F_2 X_2, \quad (5)$$

where F is a generalized force [P (pressure), H (magnetic field), ϵ (electric field), σ (surface free energy), etc.], X is the conjugate displacement [V (volume), M (magnetization) or B (induction), $\bar{Q}$ (electric charge), A (surface area), etc.] and the term FX is appropriately normalized with respect to mass or volume.

If the two states have the same Gibbs free energy at a common temperature, they are considered to be equally stable. The equilibrium condition is defined independent of reversibility as $(G_2 - G_1)_T = \Delta G_T = 0$, recognizing that equilibrium carries with it the assumption that the G -values are minimal. Since this treatment is independent of whether G_T is a minimum, it also admits to describing processes which have been termed metastable equilibria.

Applying the condition $\Delta G_T = 0$ to Eqs. (4) and (5),

$$0 = \Delta U - T\Delta S + (F_1 + F_2)/2 \Delta X + (X_1 + X_2)/2 \Delta F \quad (6)$$

and by replacing ΔU from the first law

$$0 = \Delta Q - \Delta W - T\Delta S + \bar{F}\Delta X + \bar{X}\Delta F \quad (7)$$

where

$$\bar{F} = (F_1 + F_2)/2 \quad \text{and} \quad \bar{X} = (X_1 + X_2)/2.$$

On a reversible path between the two states, the only first principle condition from the second law is $\Delta Q \equiv T\Delta S$.

Now if $\Delta G_T = 0$ and if $\Delta W \neq \bar{F}\Delta X + \bar{X}\Delta F$, then $\Delta Q \neq T\Delta S$ and no reversible path can exist between the two states in spite of the requirement that they have the same Gibbs free energy at the same temperature.

Two interesting cases satisfy the condition $\Delta W \neq \bar{F}\Delta X + \bar{X}\Delta F$. Note the convention that

$$\Delta W = \int F dx$$

and consider the case where

$$\int F dx = \bar{F}\Delta X.$$

This condition is satisfied when there is a linear relationship between the force and the displacement, i.e.,

$$\Delta \epsilon = R\Delta \bar{Q}, \quad \sigma = k_1 A + k_2$$

or

$$M = -\frac{1}{4\pi}(H - \text{constant}).$$

A second case requiring $\Delta Q \neq T\Delta S$ in Eq. (7) when $\Delta G_T = 0$, occurs for $\Delta W = 0 = \Delta X = dX$. Such a situation can be envisioned when the surface energy changes without a change in area or, in the London treatment of the magnetic work,

$$\int H dB$$

in a superconductor, when H varies while B remains constant (discussed below). (Clearly many other functional relations between F and X also satisfy the condition

$$\int F dx \neq \bar{F}\Delta X + \bar{X}\Delta F.)$$

HYSTERESIS WITH ISOTHERMAL REVERSIBILITY

We now consider the case where hysteresis permits the existence of isothermal reversible paths. Reversible paths cannot exist between states of the same free energy under conditions where there are particular types of coupling between the two variables F and X . Suppose now that there are two terms in G that can be denoted by two forces (F and $\mathcal{F}$), and displacements (X and x), i.e.,

$$G_1 = U_1 - TS_1 + F_1 X_1 + \mathcal{F}_3 x_3, \quad (8)$$

$$G_2 = U_2 - TS_2 + F_2 X_2 + \mathcal{F}_4 x_4. \quad (9)$$

Then

$$0 = \Delta Q - \Delta W - T\Delta S + \bar{F}\Delta X + \bar{X}\Delta F + \bar{\mathcal{F}}\Delta x + \bar{x}\Delta \mathcal{F}. \quad (10)$$

Now there are a sufficient number of terms to allow reversibility to occur for the conditions which prevented it in the case of one Fx term. We will use the condition of two terms in ΔW and apply it to the hysteretic superconductor in order to determine the properties of the isothermal reversible paths.

TWO STATES IN COMMON H AT CONSTANT T

Assume that the Gibbs free energy functions for two superconducting states with different surface currents in applied fields at a constant temperature are

$$G_1^s = U_1 - TS_1 - H_1 B_1 + A_1 \sigma_1, \quad (11)$$

$$G_2^s = U_2 - TS_2 - H_2 B_2 + A_2 \sigma_2. \quad (12)$$

The primary assumption that surface currents change the surface energies requires for all conditions that $\sigma_2 - \sigma_1 = \Delta\sigma \neq 0$. The London term HB is used rather than HM . M is the average value of the magnetization made up of a bulk and surface current contribution. In this treatment the contributions of bulk and surface are separated into HB and $A\sigma$ terms. The $A\sigma$ term has units of energy per unit volume. A is the actual surface area (S) per unit volume of superconductor or $A = S/(V_T - \lambda S)$. V_T is the total volume and λ is the penetration depth. When the two states have the same value of applied field

$$\Delta U - T\Delta S - H\Delta B + \bar{A}\Delta\sigma + \bar{\sigma}\Delta A = G_2^s - G_1^s. \quad (13)$$

If the two states have the same free energy we obtain, by replacing ΔU ,

$$\Delta Q - \Delta W - T\Delta S - H\Delta B + \bar{A}\Delta\sigma + \bar{\sigma}\Delta A = 0. \quad (14)$$

On reversible paths $\Delta W = \bar{\sigma}\Delta A - H\Delta B$ so that

$$\Delta Q - T\Delta S + A\Delta\sigma = 0. \quad (15)$$

On a reversible path $\Delta Q = T\Delta S$ so that $\Delta\sigma = 0$. Therefore, we obtain the expected result that no isothermal reversible path at constant H exists that fulfills both conditions $\Delta\sigma \neq 0$ and $G_1^s = G_2^s$.

TWO STATES IN DIFFERENT H AT COMMON T

For the condition where the Gibbs free energies of two states with different surface currents are the same when the applied field is not common to both states, Eq. (14) is now

$$\Delta Q - \Delta W - T\Delta S - \bar{H}\Delta B - \bar{B}\Delta H + \bar{A}\Delta\sigma + \bar{\sigma}\Delta A = 0, \quad (16)$$

where again $\Delta W = \bar{\sigma}\Delta A - \bar{H}\Delta B$ and $\Delta Q_{\text{rev}} = T\Delta S$ so that

$$-\bar{B}\Delta H + \bar{A}\Delta\sigma = 0, \quad (17)$$

where $\bar{B} = (B_2 + B_1)/2$

and $\bar{A} = (A_1 + A_2)/2$. (18)

In this case an isothermal reversible path between states of the same free energy is permissible for the condition

$$\bar{A}\Delta\sigma = \bar{B}\Delta H \quad (19)$$

or

$$\Delta\sigma/\Delta H = (B_2 + B_1)/(A_2 + A_1). \quad (20)$$

The condition $\Delta\sigma \neq 0$ is fulfilled for $G_1^s = G_2^s$ only when $\bar{B} \neq 0$. The restrictive condition $\bar{B} \neq 0$ for $\Delta G = 0$ is consistent with the usual assumption that the isothermal reversible paths for $B = 0$ occur with free energy changes. To obtain information on dB/dH we add the additional relations used to derive the analog of the Clapeyron equation. For small reversible changes between two states with the same free energy we have

$$dG_1 = A_1 d\sigma - B_1 dH \quad (21)$$

and

$$dG_2 = A_2 d\sigma - B_2 dH. \quad (22)$$

After equating (21) and (22)

$$d\sigma/dH = (B_2 - B_1)/(A_2 - A_1) \quad (23)$$

For small changes $\Delta\sigma/\Delta H \rightarrow d\sigma/dH$ and from (20) and (23)

$$(B_2 + B_1)/(A_2 + A_1) = (B_2 - B_1)/(A_2 - A_1) \quad (24)$$

or

$$B_1/A_1 = B_2/A_2 = \text{constant} = k \quad (25)$$

so that $dB = k dA$. From the definition of A ,

$$dA = \frac{S^2 d\lambda}{(V_T - \lambda S)^2} \quad \text{or} \quad \frac{dA}{dH} \sim \left(\frac{S}{V_T}\right)^2 \frac{d\lambda}{dH} \quad (26)$$

It is known that the penetration depth, λ , does not vary appreciably with field. Since $d\lambda/dH \sim 0$ and $dB/dH = k(dA/dH)$ we obtain the additional restriction $dB/dH \sim 0$ for the isothermal reversible paths between different surface current states with the same free energy. Both these conditions, $B \neq 0$ and $dB/dH \sim 0$, are observed and are characteristic features of the isothermal reversible paths of hysteretic superconductors.

A second method of deducing that hysteresis involves equilibrium is an approach which is the converse of the above. In the first approach equilibrium is assumed and hysteresis is deduced, whereas in this approach hysteresis is assumed and equilibrium is deduced.

The phenomenon of hysteresis is characterized by the property that states enclosed in the hysteretic planar area of two thermodynamic coordinates are accessible through different paths in the plane. Alternatively more than one planar path exists between two arbitrary states in the hysteretic area. It can be shown that if the Gibbs free energy G is continuous on more than one such path, then different states exist with the same Gibbs free energy. For simplicity we consider isothermal hysteresis although the treatment is equally valid when temperature is one of the variables.

Suppose that no two states have the same free energy. Assume a function $G(H, M)$ defined over the hysteretic area R so that

$$G(H_1, M_1) = G(H_2, M_2)$$

if and only if $H_1 = H_2$ and $M_1 = M_2$. (27)

Assume also that G is continuous on a path P connecting two states (H_i, M_i) and (H_e, M_e) in the area R . From Eq. (27) G must be monotonic on P .

We choose $G(H_i, M_i) < G(H_e, M_e)$. Now, consider an arbitrary point (H_p, M_p) on P lying between (H_i, M_i) and (H_e, M_e) . Clearly we have

$$G(H_i, M_i) < G(H_p, M_p) < G(H_e, M_e).$$

We set

$$\varepsilon = \min \left\{ \begin{array}{l} |G(H_e, M_e) - G(H_p, M_p)| \\ |G(H_p, M_p) - G(H_i, M_i)| \end{array} \right\} \quad (28)$$

Then any point (H_x, M_x) in the area R but not on the path P , including points infinitesimally close to P , must differ in G from the value $G(H_p, M_p)$ by more than ε , i.e.,

$$|G(H_x, M_x) - G(H_p, M_p)| > \varepsilon. \quad (29)$$

Therefore, there are two possibilities. If no two states have the same free energy in the domain R , the Gibbs free energy must be discontinuous in R . It is easy to see that any path other than P connecting the point (H_i, M_i) to the point (H_e, M_e) must be discontinuous in G . On the other hand, if G is continuous on more than one path between the same two points in R , then different states in R must have the same Gibbs free energy.

The above approaches have been successful in explaining the experimental properties of hysteretic superconductors. These concepts have also been applied successfully to the experimental hysteretic properties of elastic membranes and the pressure-volume characteristics of the lungs in mammals.

Elastic membranes play a key role as switching devices in respiration and circulation. In mammals, oxygen is collected by the blood during passage through the capillaries of the lungs and is distributed to the tissues by flow of blood throughout the body. Since the open volume of the circulatory system exceeds the volume of the blood in the body, while blood flows in some regions it is shut off in others. Switching behavior also occurs in the air-flow systems in animals. Exchange between the blood-flow and air-flow systems occurs in the lungs, i.e., between the alveoli and closely enmeshed blood vessels. The diaphragm controls the pressure around the lungs and the alveoli inflate and deflate with each breath. Because of the elasticity of the lung tissue its properties are often compared with those of a balloon and the switching behavior in the air-flow and blood-flow systems has been attributed to essentially the same phenomenon – the characteristic properties of curved elastic membranes.

Because of an oversimplification of the basic concepts describing elastic membranes, a number of important properties have not been recognized. The usual approach is to consider a spherical bubble in which the upward pressure of the gas inside the bubble, which tends to pull the bubble apart, is balanced by the downward tension due to the surface properties. At equilibrium the vector force difference is zero. The pressure acts on the cross-sectional area, and the tension, γ , acts on the circumference so that $P(\pi r^2) = \gamma(2\pi r)$ or $P = 2\gamma/r$.

Consider a soap film covering the end of a rigid tube of radius R . With no pressure differential between inside and outside, the film lies flat with an infinite radius of curvature. As the film inflates the radius of curvature decreases until the bubble is hemispherical in shape. At this point the radius of curvature is equal to the radius of the tube and is a minimum. Further inflation leads to an increase in the radius of curvature. In a plot of the pressure in the bubble vs the volume of the bubble, the curve exhibits a maximum in P corresponding to the minimum in the radius. At the maximum, $P = 2\gamma/R$.

In real systems it has been assumed that the surface tension γ changes rapidly with elongation beyond some volume, leading to an N -shaped curve in the P - V plane. The switching is then assumed to occur because negative compliances ($\Delta V/\Delta P < 0$) are unstable. The switching is illustrated in Figure 25. In a re-examination of the

Figure 25. Schematic for the switching behavior of a membrane with an N-shaped PV curve.

theory (in which equilibrium conditions for the expanding medium were included), it was found that negative compliances are, in fact, stable and that the hysteresis is a result of geometric constraints which prevent the system going from one equilibrium state to another reversibly. Application of these concepts to experiments on elastic membranes provided a means for determining the N-shaped curves and demonstrating that switching occurs with negative compliances. It can also be shown that the hysteresis is predominantly associated with the switching. Typical data are shown in Figure 26 for the pressure-volume changes of a natural rubber membrane expanded by a liquid. The type of geometry used is shown in Figure 27.

D. SCHWEITZER

ANOMALOUS FLUCTUATIONS IN SUPERCONDUCTING FILMS

Theory

Two years ago P.C. Hohenberg proved a theorem that no long range superconducting order could exist in thin films and wires because of the large fluctuations that would arise in these systems. However, there was no experimental evidence to support this conclusion. In fact, all experiments agreed with the simple mean field theory of superconductivity as in bulk three-dimensional systems. We have recently discovered a situation in which the divergence of the fluctuations in superconducting films can be observed.

The quantity observed is the extra conductivity in addition to the normal state conductivity, which arises above the transition temperature T_c because of fluctuations. Bound superconducting pairs are formed above T_c and decay back into normal electrons with a lifetime proportional to $T - T_c$. If an

Figure 26. Historetic behavior in the inflation-deflation curves of the system that switches to and from the rising portion of the N-shaped curve.

Figure 27. Schematic for method of measuring the pressure-volume characteristics of a membrane expanded by a liquid.

electric field is applied, superconducting pairs will be accelerated during their lifetimes, giving an enhancement to the conductivity. Considering only the extra current arising from the acceleration of these pairs, one obtains an extra conductivity $\sigma' = (e^2/16\hbar d)T_c/(T - T_c)$, where d is the film thickness. Expressed in terms of the film resistance per square area, $R_{\square}$, one has $\sigma'/\sigma = \tau_0/\tau$ where $\tau = (T - T_c)/T_c$, and the width of the transition is $\tau_0 = 1.52 \times 10^{-5} R_{\square}(\Omega)$. This result is finite for any T above T_c , and most experimental results performed on strong coupling superconductors like lead confirmed it well until now. We have found additional anomalous fluctuations that can be much larger than these regular ones.

The additional contribution to σ' comes from considering the normal electrons interacting with the pairs. These normal electrons give another contribution to $\sigma'/\sigma = \tau_0/(\tau - \delta) \log(\tau/\delta)$. This new contribution is divergent and depends on a cutoff δ which is the shift of T_c (normalized by T_c) due to electron-phonon scattering, electron-electron scattering, or some other pair breaking interaction. δ can be increased by adding additional pair-breaking interactions, such as by applying a magnetic field to the film. If the field is applied parallel to the film (so that the complications of vortex formation do not arise), the width of the transition should decrease from a large value to just τ_0 when $\delta \gg \tau$. In the absence of magnetic fields δ should be smaller for weak coupling systems like aluminum than for lead.

R. THOMPSON

Experimental Results

Broad transitions, an order of magnitude larger than τ_0 , have been observed earlier in aluminum films by R.D. Parks. We have constructed similar films ($R_{\square} \sim 1\Omega$) which show the same broad transitions in zero field and proved that they are caused by the anomalous fluctuations. By applying magnetic fields parallel to the film we see the width gradually reduce to τ_0 as the field strength is increased. The broadest transition $\sim 15\tau_0$ corresponds to a $\delta \sim 10^{-4}$, which is the theoretical estimate for electron-electron scattering, $\sim T/(\text{Fermi energy})$. A superconductor that is even more weakly coupled than aluminum (with a lower T_c) should show even more enhancement, but not much more since the fluctuations are only logarithmically divergent. We have also examined lead films (also $R_{\square} \sim 1\Omega$) and find transitions with widths changing according to the theory, τ_0 near

the transition and $\sim 3\tau_0$ away from T_c ($\tau \sim 0.1$). We fit the theoretical curves with $\delta \sim 0.06$, compared with the usual estimates from electron-phonon scattering $\delta \sim 0.01$ or 0.015 . In dirtier films δ is observed to increase, partly because of the increased electron-phonon coupling and perhaps because of other pair-breaking effects as well.

Our work is the first experimental confirmation of the divergence of fluctuations in superconducting films. It also indicates the weakness of the divergence, and shows the cases in which the mean field theory may be a good approximation for effects in which τ_0/τ is negligibly small. J. CROW

SUPERCONDUCTING PROPERTIES OF THIN FILMS

Preliminary experiments have indicated a large variety of unexpected behavior in superconducting films. In the regime of the thinnest films, fluctuations, surface effects caused by the substrate and overlayers, and changes in phonon spectrum and the density of states cause dramatic changes in the behavior. If ordered films only a few monolayers thick can be constructed, there is the possibility (as suggested by V.L. Ginzburg) of producing a favorable interaction for superconductivity through an excitonic mechanism. Also, in well-ordered films the lowering of T_c caused by fluctuations and the lowering of T_c in some disordered transition metals would be minimized.

To study how to make well-ordered electrically continuous films only a few monolayers thick we have started work on low energy electron diffraction and Auger spectroscopy in near-monolayer films. A cryostat has been constructed to go into the LEED apparatus and films will be studied at cryogenic temperatures. Theoretical work on how to nucleate ordered monolayer-films is also under way. By using "molecular dynamics" techniques it should be possible to study what the favorable temperatures and substrates are for growth of ordered monolayers, and in fact one can probably get some estimate of whether the construction of ordered monolayers of metals on dielectrics is possible in principle.

An initial problem being studied in the diffraction equipment is the surface Θ_{Debye} in niobium. Using the Auger spectrometer we have also made preliminary measurements of how oxygen can be removed from the niobium surface. The combined diffraction and Auger analyses should yield information about the structure of the niobium surface

that will be of great interest to people concerned with near perfect niobium surfaces, such as for accelerator cavities.

M. STRONGIN, J. DICKEY, H. FARRELL

ELECTRON IRRADIATION OF SUPERCONDUCTORS

An apparatus has been designed for studies of electron irradiation of superconductors. Features of the experiment include an integrated electron dosage up to $10^{21}/\text{cm}^2$ (this corresponds to a saturation atomic displacement of $\sim 1\%$), the temperature of the sample being kept below 2.5°K during irradiation, and a transverse magnetic field of 100 kG for critical field and critical current measurements. Construction and testing of the apparatus is nearing completion. The experiments will be done with the BNL Dynamitron in collaboration with A. Goland of the Physics Dept.

M. GARBER, D. SCHWEITZER

SUPERCONDUCTIVITY OF BERYLLIUM COMPOUNDS

If one could optimize the electron-phonon interaction for beryllium, existing theories predict that transition temperatures of the order of 30° to 60°K may be attainable. A program has been initiated to study the possibility of attaining high transition temperatures in Be alloys, compounds, and films.

Preliminary results show that Be_2X ($X = \text{Nb, Ti, Ta, or Mn}$) and Mo_2Be are not superconducting above 4.2°K . In addition, $\text{Be}_{22}X_a\text{Y}_{1-a}$ ($X = \text{Re, Y} = \text{W or Ru}$) was measured. The highest T_c was that of Be_{22}Re ($T_c = 9.9^\circ\text{K}$) confirming previously reported measurements, and monotonic decreases in T_c were observed with replacement of Re by either W or Ru. Tunneling measurements are now under way in an attempt to understand this behavior in T_c .

M. SUENAGA, J. CROW

NUCLEAR SUSCEPTIBILITY OF SOLID ^3He

An experimental study of the nuclear susceptibility of solid ^3He was completed down to 5.3°mK . The data can be fit with a Curie-Weiss straight line over the entire range of temperatures studied (5.3° to 800°mK). The low temperature data enable the sign and magnitude of the Weiss constant to be determined by extrapolation quite accurately as a function of molar volume. The results obtained provide the first accurate evidence for a nuclear

antiferromagnetic transition in the region below 2°mK . The success of this work is due in part to a careful continuous wave (CW) method of NMR absorption carried to temperatures below 10°mK and in part to a unique solution of the problems of thermometry and thermal equilibrium.

The ^3He sample was contained in an epoxy cell with 4300 #50 Formvar-insulated copper wires feeding through an epoxy pressure seal. Thermal contact to the ^3He was established with the wires, and the cell was designed so that no part of the sample was more than 0.003 cm from the nearest cooling surface in order to minimize the relaxation times. The Cu wires from the pressure cell led to a tin heat switch which was attached to the bottom of a 600-g cerium magnesium nitrate salt. Temperatures of 5.3°mK were realized at the sample by magnetically cooling the salt. A dilution refrigerator was used to cool the salt to 0.1°K before demagnetization and to perform the role of the usual "guard salt" at 90°mK . With this arrangement temperatures could be maintained below 10°mK for more than a week.

Temperatures were measured by CW NMR on ^{63}Cu and ^{195}Pt using a frequency-modulated Robinson circuit. The ^{63}Cu sample was part of the 4300 wires in the cell and the ^{195}Pt sample was 0.12 g of $5\text{-}\mu$ powder interspersed among the Cu wires. The temperature was assumed to be proportional to the ratio of a calibrator signal to the height of the NMR signal. The proportionality constant was determined at 0.4°K by using a ^3He vapor pressure thermometer. Between temperatures of 5.3° and 395°mK the ^{195}Pt and ^{63}Cu thermometers were found to agree within 5%.

Thermal equilibrium times were checked by turning on the tin heat switch and quickly cooling the sample from about 100°mK to the lower temperature of the salt. The entire lower stage below the tin heat switch cooled to 10°mK in 4 min and reached a lowest temperature of 7°mK in 30 min. Within the 5% precision of these measurements there was no disequilibrium between the thermometer and the ^3He . The cooling rate was limited by thermal contact to the salt.

A Rollin circuit in conjunction with a Varian C-1024 signal averager was used to measure the ^3He susceptibility at 714 G. The line width was broadened by the superconducting magnet inhomogeneity to 0.25 G which is much larger than the natural line width. Each signal height from the ^3He was compared with a calibrator signal which

allowed compensation for drifts in the gain of the measuring equipment and drift in the Q of the tank circuit. ^3He signals at three power levels 0.1, 1, and 4 nW were taken to check for saturation and heating effects. Only below 10° mK was saturation observed. At the lowest temperature and the highest RF power level the saturation was: 2.3% for 24.0 cc/mole, 9.5% for 23.1 cc/mole, 18% for 22.0 cc/mole, and 25% for 21.0 cc/mole solids. At the lowest power level and temperature, 1% saturation was never exceeded even for the 21.0 cc/mole solid.

In Figure 28 the inverse susceptibility, χ^{-1} , is plotted against temperature in arbitrary units. Measurements were taken on solids that were formed at molar volumes 24.0, 23.1, 22.0, and 21.0 cc/mole by the blocked capillary technique. As shown in the figure, the typical scatter in the data is 5% or less and comes mainly from the thermometer. The linear curves drawn through the data points were fitted by the method of least squares and in each case extrapolated with an intercept on the negative temperature axis. The negative intercepts are interpreted to mean that solid ^3He will order as an antiferromagnet. Recent theoretical work has predicted antiferromagnetic behavior. It would be difficult to interpret the data otherwise in consideration of the knowledge that solid ^3He has no electronic structure to produce internal electric and magnetic fields to complicate the in-

terpretation of the magnetic susceptibility as in other solids. The values of the intercepts on the temperature axis gave the Curie-Weiss constants $\theta = -2.9 \pm 0.7$ mK, -1.3 ± 0.31 mK, -0.48 ± 0.16 mK, and -0.44 ± 0.30 mK for the respective molar volumes 24.0, 23.1, 22.0 and 21.0 cc/mole. The errors quoted on the θ 's were obtained from an error analysis of the deviations of the data from the best straight line fits. Included in the errors are any curvature effects from a higher order expansion of χ in (J/kT) . The above θ 's give Néel temperatures (T_N) of 2.0 ± 0.48 mK, 0.89 ± 0.21 mK, 0.33 ± 0.11 mK, and 0.30 ± 0.21 mK respectively.

The slopes of the straight lines in Figure 28 are proportional to the Curie constant C . They scale with the inverse molar volumes within 2% for all densities studied except the 23.1 cc/mole solid which scaled to within 5.5%. Measurements were extended to 0.8 K and the data followed a Curie-Weiss law.

The magnitude of the exchange interaction, $|J|$, at each molar volume was computed and entered on the graph in Figure 29. The dashed curve represents work of Panczyk and Adams in which $|J|$ was determined from measurements of $\partial P / \partial T|_V$ at temperatures above 20 mK.

A study of the effects of ^4He impurities, present in concentrations of 125 ppm and ~ 2 ppm, was made to see if the impurity changed the susceptibility by isotopic phase separation or enhanced ex-

Figure 28. Inverse susceptibility vs temperature for various molar volumes. Closed circles, squares, and triangles refer to samples with 125 ppm ^4He impurity. Open circles for samples with ~ 2 ppm ^4He impurity. For 24.0 cc/mole solid, the closed circles, squares, and triangles distinguish measurements from different runs.

Figure 29. The exchange interaction vs molar volume. Dashed curve is $|J|$ from Panczyk and Adams.

Table 19

Effect of Prior Treatment on Tensile Properties of Irradiated Types 304 and 316 SS

Condition	Test temperature, °C	Yield strength, psi	Tensile strength, psi	Total elongation, %
Annealed 304 SS	650 ^a	22,000	30,700	11
	750	15,800	18,100	13
304 SS cold swaged 92% annealed at 760°C-16 hr	650 ^a	24,000	30,000	35
	750	11,800	12,900	27
316 SS cold swaged 45% recrystallized at 760°C-16 hr	25	140,000	148,000	10
	650	20,400	42,800	25
	750	26,800	29,500	7
	800	16,700	17,800	6.5
316 SS cold swaged 45% recrystallized at 870°C-16 hr	650	22,800	33,700	35
	750	15,400	19,000	16
	800	13,200	14,200	14
316 SS cold swaged 90% recrystallized at 760°C-16 hr	650	27,000	34,000	39
	750	13,000	15,700	39
316 SS cold swaged 90% recrystallized at 870°C-16 hr	25	109,000	121,000	23
	650	26,000	35,100	32
	750	12,800	15,200	35
	800	10,600	12,000	30
316 SS cold swaged 90% recrystallized at 1050°C-½ hr	650	23,200	38,000	22
	750	18,300	20,900	22
	800	12,800	16,100	20

NOTES: All specimens irradiated to 1.3×10^{20} ($E > 0.82$ MeV). All specimens tested at a strain rate of 0.2% per min.^aAverage of 2 tests.

Table 20

Effects of Irradiation on Cobalt Base Alloy^a With Titanium

(All specimens tested at a strain rate of 0.2% per min.)

Alloy	Irradiation fluence ^b	Test temperature, °C	Yield strength, psi	Tensile strength, psi	Total elongation, %
605-0.9 Ti	0	750	31,200	33,000	57
	0	800	17,500	19,000	87
	1.3×10^{20}	650	80,000	95,000	29
	"	750	32,400	39,800	24
	"	800	24,400	26,200	67
606-0.2 Ti	0	25	116,000	179,000	28
	0	650	74,600	82,400	45
	0	750	31,700	33,400	52
	0	800	18,500	19,800	63
	1.3×10^{20}	650	81,200	97,500	20
	"	750	41,500	42,600	22
607-0.46 Ti	0	25	117,000	178,000	15
	0	650	72,300	84,500	34
	0	750	32,900	35,000	47
	0	800	20,700	22,300	71
	1.3×10^{20}	650	80,500	94,800	23.5
	"	750	41,500	44,100	28
608-0.64 Ti	0	25	126,000	160,500	7
	0	650	78,800	92,500	45
	0	750	29,300	32,100	58
	0	800	16,700	19,000	67
	1.3×10^{20}	650	79,700	94,800	22
	"	750	40,300	42,700	39
	"	800	26,400	28,000	71

^a21 Cr-10 Ni-5 W-5 Mo-8 Fe-Co-Bal. Cold worked and recrystallized at 870°C, 16 hours prior to test or irradiation.^b $E > 0.82$ MeV; irradiation temperature $> 100^\circ\text{C}$.

IMPROVING THE POSTIRRADIATION DUCTILITY OF STAINLESS STEELS AND COBALT-BASE ALLOYS

Austenitic stainless steels such as types 304 and 316 are generally used in the fully annealed condition, in which these steels are essentially a one-phase material with grain size of about ASTM 3 to 5. This structure has the best corrosion resistance and has the best high temperature strengths. However, from the standpoint of postirradiation ductility, it is probably the most undesirable structure.

Work by us and others indicate that any method of alteration of the annealed structure by refining grain size and causing precipitation produced some improvement in irradiation behavior. The effectiveness of additions of Ti to stainless steels, as developed at ORNL, is also enhanced when the material is given a 50% reduction in area and followed by a 925°C anneal.

It is believed that the maximum postirradiation ductility is obtained if the grain boundaries of the annealed material can be broken up or obliterated. Various methods of doing this have been tried, such as low temperature deformation to form martensite (in effect altering the composition to form a two-phase fine-grained material) and heavy cold-working and low temperature recrystallization. All improve the postirradiation ductility of austenitic stainless steel at elevated temperatures. However, the heavy cold-working method seems to be the most feasible technique, and studies of this method to improve the postirradiation ductility of type 316 stainless steel and cobalt-base alloys are continuing.

Table 19 summarizes the postirradiation tensile data of types 304 and 316 stainless steel for materials given various treatments. The results show that the postirradiation ductility is improved 3 to 4-fold over that of the annealed material when it was cold-deformed to 90 to 92% and recrystallized at 760° to 870°C. The strength of the material given this treatment is comparable with that of the annealed material at 650°C but is somewhat lower at 750° and 800°C. Figure 30 shows the microstructures (at 1000×) of type 316 stainless steel given 45% and 90% cold work before recrystallization at 870°C. Note the extremely fine grain size and the profusion of precipitation in the more heavily cold-worked material.

Table 20 presents the postirradiation tensile properties of the experimental cobalt-base alloys

COLD SWAGED - 45% - ANNEALED AT 870°C

COLD SWAGED - 90% - RECRYSTALLIZED AT 870°C
MICROSTRUCTURE OF TYPE 316 STAINLESS STEEL-
1000X

Figure 30.

change interaction. In none of the molar volumes investigated, except 21.0 cc/mole, did we observe a difference in χ for the two concentrations. The 21.0 cc/mole solid did differ at temperatures < 10 mK with the data from the 125 ppm ^4He departing slightly from the Curie-Weiss law behavior, whereas the sample with ~ 2 ppm ^4He followed the Curie-Weiss law to the lowest temperature measured. M. GARBER, W. KIRK, B. OSGOOD

Irradiation Effects

The nature of irradiation-induced defects are being studied with the field ion microscope. Also, the work supported by RDT under the LMFBR program until June 30, 1969, is reported in this section.

Figure 31. The change in the $(\text{yield stress})^{2/3}$ vs defect density and average size for neutron irradiated platinum.

at 650° to 800°C. The material was cold-worked (about 50%) and recrystallized at 870°C for 16 hr. Note the very high postirradiation ductility of these materials. The high ductility is attributed to their very fine grain structure (about 3 μ). The strength of these alloys is a factor of 2 or 3 higher than that of type 316 stainless steel. This high strength and the ability to treat them for high postirradiation ductility makes the cobalt-base alloys very attractive for high temperature fuel cladding materials.

It is suggested that the fine grain structure and fine precipitates that are developed may also be beneficial in minimizing the vacancy or void formation during irradiation. Zones denuded of voids have been found next to grain boundaries. It is suggested that the very fine grain size and profusion of small precipitates in the stainless steels and cobalt alloys treated as described above will provide a large area of sinks for the vacancies. Samples are being planned for irradiation in EBR II to study this effect.

J. CHOW

EFFECTS ON THE STRUCTURE AND PROPERTIES OF MATERIALS

In the last year an extensive study has been completed of radiation damage in platinum, and has resulted in basic information about damage zones in irradiated platinum and the interaction of dislocations with radiation-produced damaged zones. These measurements consisted of field ion microscope observations of densities and sizes of depleted zones in the as-irradiated material and

Figure 32. Comparison of temperature dependence of yield stress in zone-refined tungsten crystal as a function of purification.

Figure 33. Effect of irradiation on the critical resolved shear stress of zone-refined tungsten crystals.

in the irradiated material after annealing at various temperatures. In this way changes in defect concentration and sizes were obtained. Also, measurements were made of the mechanical properties of similarly prepared specimens. These results were compared with various models of defect hardening in crystals, from which an activation energy for dislocation cutting of zones was obtained (Figure 31). This activation energy was about 1 eV and was the first direct measurement of such a dislocation-defect interaction.

Also work has continued on determining the mechanical properties of tungsten in the annealed

Figure 34. Graphite split mold for growing copper bicrystals.

and irradiated conditions. It has been possible to reduce the temperature dependence of the critical resolved shear stress by substantial amounts with very careful zone-refining and specimen preparation techniques (Figure 32). In addition, we have shown that irradiation does affect the temperature dependence of the critical resolved shear stress in zone-refined tungsten crystals. This effect, shown in Figure 33, has not been previously observed, and indicates that the Peierls-Nabarro stress need not be dominant as a resistance element to dislocation motion in tungsten.

J. GALLIGAN

GRAIN BOUNDARY SLIDING IN NEUTRON-IRRADIATED COPPER BICRYSTALS

This program was initiated to study how the presence of helium at the grain boundaries of face-centered cubic metals affects the mechanism of grain-boundary sliding. Typical test variables will include temperature, grain boundary misorientation, helium concentration, and the stress parallel to the boundary. Figure 34 shows a graphite split mold which has been designed and constructed to grow bicrystals by the Bridgeman technique. To date many large bicrystals of copper have been grown from which test samples have been cut. Helium will be generated within the samples by high-temperature irradiations in the HFBR. Although some helium will be generated by (n, α) reactions with matrix atoms, future specimens are to be doped with boron to induce more prolific helium generation according to the $B(n, \alpha)Li$ transmutation. The irradiated samples will be tested under

creep conditions, and to this end a high temperature creep facility for testing in a nonoxidizing atmosphere has been designed and is undergoing construction.

P. Soo

Publications

- ARONSON, S. AND SALZANO, F.J. The solid-state reaction of lithium hydride and aluminum. *Inorg. Chem.* **8**, 1541-2 (1969).
- ARONSON, S. AND SALZANO, F.J. Electrochemical study of the sodium-graphite reaction. (N) *Nucl. Sci. Eng.* **38**, 19 (1969).
- BRYNER, J.S. AND CHOW, J.G.Y. Fast-neutron irradiation effects on dislocation structures in iron at ambient temperature. *Acta Met.* (in press).
- CHOW, J.G.Y. Effect of irradiation on mechanical properties of cobalt base alloys. In *Irradiation Effects on Structural Alloys for Thermal and Fast Reactors*, ASTM Spec. Tech. Publ. 457, 1969.
- CHOW, J.G.Y. Improvement of high temperature ductility of irradiated Fe-Ni-Cr alloys. (A) In *Proc. IAEA Symp. Radiation Damage in Reactor Materials, Vienna, June 1969* (in press).
- CROW, J.E., STRONGIN, M., THOMPSON, R.S., AND KAMMERER, O.F. The superconducting transition temperatures of disordered Nb, W, and Mo films. *Phys. Letters* **30A**, 161 (1969).
- CROW, J.E., THOMPSON, R.S., KLENIN, M.A., AND BHATTANAGAR, A.K. Divergent fluctuations in superconducting films. Submitted to *Phys. Rev. Letters*.
- DRALEY, J.E. AND WEEKS, J.R., Editors, *Corrosion by Liquid Metals*, Plenum Press, New York (in press).
- FLEITMAN, A.H. AND ISAACS, H.S. The corrosion and mass transfer of pure iron, nickel, chromium, and cobalt in 660-760°C sodium. Presented at Metals Congr. Meet., Philadelphia, Oct. 1969; also in *Corrosion by Liquid Metals*, J.E. Draley and J.R. Weeks, Editors, Plenum Press, New York (in press).
- FLEITMAN, A.H. AND SADOFSKY, J. Precipitation reactions in a cobalt base developmental super alloy containing titanium. (A) Presented at AIME Meet., Pittsburgh, Pa., May 1969.
- GALLIGAN, J.M. Defect studies in metals. In *Vacancies and Interstitials in Metals*, A. Seeger et al., Editors, North-Holland, Amsterdam (in press).
- GALLIGAN, J.M. Deformation of tantalum. (A) *Bull. Amer. Phys. Soc.* **14**, 438 (1969).
- GALLIGAN, J.M. On the saturation of radiation hardening. *Phys. Letters* **28A**, 609 (1969).
- GALLIGAN, J.M. AND INAL, O.T. A measurement of radiation hardening and defects in irradiated platinum. (A) *Bull. Amer. Phys. Soc.* **14**, 498 (1969).
- GALLIGAN, J.M. AND OKU, T. Dislocation loops observed by field ion microscopy in neutron irradiated tungsten. *Phys. Status Solidi* **36**, K239 (1969).
- GALLIGAN, J.M., SCHULTZ, H., AND LACHENMANN, R. Low temperature strain aging in deformed tantalum. *Scripta Met.* **3**, 401-4 (1969).

- HOBDELL, M.R. AND NEWMAN, L. Some observations on the kinetics of the liquid sodium-hydrogen reaction. *J. Inorg. Nucl. Chem.* **31**, 1843-7 (1969).
- HOBDELL, M.R. AND NEWMAN, L. The reaction of HCl with liquid sodium and a sodium-barium alloy. In *Proc. Int. Conf. Sodium Technology and Large Fast Reactor Design, Argonne National Laboratory, Nov. 1968*, ANL-7520, Pt. I, pp. 490-8, 1969.
- HOBDELL, M.R. AND SALZANO, F.J. A convenient technique for stirring liquid sodium. *Nucl. Appl.* **8**, 95-6 (1970).
- INAL, O.T. AND GALLIGAN, J.M. A measurement of the activation energy of dislocation cutting of depleted zones in platinum. *Acta Met.* (in press).
- ISAACS, H.S. The determination of oxygen concentration and mass transfer coefficients in sodium using uranium. In *Proc. Int. Conf. Sodium Technology and Large Fast Reactor Design, Argonne National Laboratory, Nov. 1968*, ANL-7520, Pt. I, pp. 465-70, 1969.
- ISAACS, H.S., MINUSHKIN, B., AND SALZANO, F.J. A study of reactions between oxygen and impurities in sodium. *Ibid.*, p. 460.
- ISAACS, H.S. AND CENDROWSKI, A.P. Metallographic Award, Best in Class, ASM Metallographic Exhibit, 1969.
- ISAACS, H.S. AND SINGER, R.M. A technique for chemically polishing sodium. *J. Nucl. Mater.* (in press).
- ISAACS, H.S., SINGER, R.M., AND BECKER, W.W. Segregation of metallic impurities in sodium. (A) Presented at Metals Congr. Meet., Philadelphia, Oct. 1969.
- JEANOTTE, D. AND GALLIGAN, J.M. Vacancy annealing in tungsten. *Acta Met.* (in press).
- KIRK, W.P., OSGOOD, E.B., AND GARBER, M. Nuclear ordering of solid ^3He . *Phys. Today* (in press).
- KIRK, W.P., OSGOOD, E.B., AND GARBER, M. Sign and magnitude of the exchange interaction in solid ^3He from magnetic susceptibility measurements. *Phys. Rev. Letters* **23**, 833 (1969).
- MINUSHKIN, B. AND KISSEL, G. Solubility and reactions in sodium. In *Corrosion by Liquid Metals*, J.E. Draley and J.R. Weeks, Editors, Plenum Press, New York (in press).
- OKU, T. AND GALLIGAN, J.M. Quantum mechanical tunneling of dislocations. *Phys. Rev. Letters* **22**, 596-7 (1969).
- ROMANO, A.J., WACHTEL, S.J., AND KLAMUT, C.J. Interaction effects between dissimilar metals in high velocity sodium at temperatures up to 760°C. Presented at Metals Congr. Meet., Philadelphia, Oct. 1969; also in *Corrosion by Liquid Metals*, J.E. Draley and J.R. Weeks, Editors, Plenum Press, New York (in press).
- ROMANO, A.J., WACHTEL, S.J., AND KLAMUT, C.J. Preliminary corrosion results of Haynes 25 and 304 stainless steel with 4 and 12 ppm oxygen in sodium at temperatures up to 760°C. In *Proc. Int. Conf. Sodium Technology and Large Fast Reactor Design, Argonne National Laboratory, Nov. 1968*, ANL-7520, pp. 151-2, 1969.
- SALZANO, F.J., ISAACS, H.S., AUERBACH, C., AND MINUSHKIN, B. Ionic range of ThO_2 -15 wt % Y_2O_3 at (II) high oxygen activities. Submitted to *J. Electrochem. Soc.*
- SALZANO, F.J., ISAACS, H.S., AND MINUSHKIN, B. An EMF technique for determining the ionic range of ThO_2 - Y_2O_3 at (I) low oxygen activities. *Ibid.*
- SCHWEITZER, D.G. Evidence for two types of hysteresis. Submitted to *Phys. Rev.*
- SCHWEITZER, D.G. New switching properties of membranes in air-flow and blood-flow systems. Submitted to *Amer. J. Physiol.*
- SCHWEITZER, D.G. The role of gravity in osmotic equilibria. *Amer. J. Phys.* (in press).
- SCHWEITZER, D.G. AND ADAMS, P.D. The effect of surface energies on transport current distributions in type I superconductors. *J. Chem. Phys. Solids* (in press).
- SCHWEITZER, D.G. AND GARBER, M. Behavior of solenoids in Type I superconducting shield tubes. *Appl. Phys. Letters* (in press).
- SCHWEITZER, D.G. AND GARBER, M. Flux conservation in multiply connected Type I superconductors in fields generated in the voids. *Phys. Rev.* (in press).
- SCHWEITZER, D.G. AND GARBER, M. Properties of superconducting-normal interfaces and intermediate state configurations in Type I hollow cylinders. Submitted to *Phys. Rev.*
- SINGER, R.M., FLEITMAN, A.H., WEEKS, J.R., AND ISAACS, H.S. Measurements of the solubility of iron and chromium in sodium. In *Corrosion by Liquid Metals*, J.E. Draley and J.R. Weeks, Editors, Plenum Press, New York (in press).
- SOO, P. On the rate-controlling slip process in neutron-irradiated iron. (A) Presented at AIME Meet., Pittsburgh, Pa., May 1969.
- SOO, P. The recovery of neutron-irradiated niobium between 120° and 160°C. Submitted to *Phys. Status Solidi*.
- SOO, P. Thermal activation of slip in prestrained neutron-irradiated iron by flow stress and stress relaxation measurements. *Trans. Met. Soc. AIME* **245**, 985-90 (1969).
- SOO, P. Strain aging of niobium in the temperature range 100° to 200°C. *Phys. Status Solidi* **32**, 815-21 (1969).
- SOO, P. AND GALLIGAN, J.M. On the temperature dependence of the flow stress in some body-centered cubic metals. *Scripta Met.* **3**, 153-6 (1969).
- STRONGIN, M., KAMMERER, O.F., AND CROW, J.E. Destruction of superconductivity in disordered near monolayer metallic films. (A) *Bull. Amer. Phys. Soc.* **14**, 112 (1969); *Phys. Rev.* (in press).
- STRONGIN, M., KAMMERER, O.F., THOMPSON, R.S., AND CROW, J.E. The transition in weak superconductors. (A) *Bull. Amer. Phys. Soc.* **14**, 437 (1969).
- THOMPSON, R.S. Fluctuation resistivity of dirty superconductors. *Ibid.*, p. 128.
- THOMPSON, R.S. The influence of magnetic fields on the paraconductivity due to fluctuations in thin films. In *Proc. Conf. Science of Superconductivity, Stanford, Calif., Aug. 1969* (in press).
- THOMPSON, R.S. The microwave, flux flow, and fluctuation resistance of dirty type II superconductors. *Phys. Rev.* (in press).
- THOMPSON, R.S., STRONGIN, M., KAMMERER, O.F., AND CROW, J.E. The resistive transition in weakly coupled superconductors. *Phys. Letters* **29A**, 194-5 (1969).
- WACHTEL, S.J., ROMANO, A.J., AND KLAMUT, C.J. High-flux induction heater for sodium corrosion testing. (A) *Trans. Amer. Nucl. Soc.* **12**, 125-6 (1969).

WEEKS, J.R. Liquidus of the Na-Ag system: 0 to 6 at. % Ag. (N) *Trans. Amer. Soc. Metals* **62**, 304 (1969).

WEEKS, J.R. AND ROMANO, A.J. Liquidus curves and corrosion of Fe, Ti, Zr, and Cu in liquid Bi-Pb alloys. *Corrosion* **25**, 130-6 (1969).

WEEKS, J.R. AND SINGER, R.M. On the solubilities of Cu, Ni, and Fe in liquid sodium. (A) In *Proc. Int. Conf. Sodium Technology and Large Fast Reactor Design, Argonne National Laboratory, Nov. 1968*, ANL-7520, Pt. I, pp. 309-18, 1969.

Engineering Division

T.V. SHEEHAN

Heat Transfer Studies

J. CHEN, O. DWYER, M. HELFANT, P. HLAVAC, C. HSU,
S. KALISH, G. STRICKLAND, W. YU

EFFECTS OF CLADDING THICKNESS AND THERMAL CONDUCTIVITY ON HEAT TRANSFER TO LIQUID METALS FLOWING IN-LINE THROUGH BUNDLES OF CLOSELY SPACED REACTOR FUEL RODS

Theoretical studies are being carried out at Brookhaven to determine the effects of cladding thickness and thermal conductivity on heat transfer to liquid metals flowing in-line through bundles of closely spaced reactor fuel rods. The study, restricted to bundles with equilateral triangular spacing of the rods, is relevant to the design of fuel-element assemblies for the cores of liquid-metal-cooled nuclear reactors. In the work done thus far, the heat flux on the inner wall of the cladding was assumed to be uniform and the thermal contact resistance between the fuel and the cladding was assumed to be negligible. Initially the calculations were done for slug and laminar flows; those for turbulent flow will follow. However, for liquid-metal coolants, there is a strong similarity between fully developed heat transfer behavior for slug flow and that for turbulent flow, particularly when the dependent parameters are

expressed in dimensionless ratios and the Peclet number falls in the range 500 to 1500, the range in which most sodium-cooled reactors are designed to operate.

The magnitudes of the effects of cladding thickness and thermal conductivity on the heat transfer of the system depend on the spacing of the rods. As a result, there are three independent variables. The spacing variable is expressed in terms of P/D , where P is the distance between rod centers and D is the rod diameter; the cladding thickness variable is expressed in terms of $(r_2 - r_1)/r_2$, where r_1 and r_2 are the inside and outside diameters of the cladding, respectively; and the cladding thermal-conductivity variable is expressed in terms of the ratio k_w/k_f , where k_w and k_f are the thermal conductivities of the cladding and coolant, respectively.

In the calculations carried out thus far, the rod spacing parameter has been varied over the range $1.05 \leq P/D \leq 1.30$. This range covers typical P/D values found in current designs of sodium-cooled high-flux research and power reactors. The closer the rod spacing, the greater will be the variation of the local surface temperature and the local heat flux around the circumference of each rod. Some typical results are shown in Figure 1, illustrating the circumferential variation of the outer wall temperature of the cladding. Also, Figure 2 illustrates

Table 1
Calculated Average Nusselt Numbers for Slug and Laminar Flows

P/D	σ	Slug flow		Laminar flow	
		$[Nu_t]/[Nu_t]_0$	$[Nu_q]/[Nu_q]_0$	$[Nu_t]/[Nu_t]_0$	$[Nu_q]/[Nu_q]_0$
1.4	0.3	0.93	0.478	0.742	0.165
1.6	0.3	0.915	0.587	0.717	0.245
1.75	0.15	0.969	0.897	0.903	0.642
1.75	0.3	0.896	0.69	0.729	0.384
1.75	0.5	0.773	0.491	0.515	0.224
1.75	0.65	0.684	0.353	0.411	0.159
1.9	0.3	0.91	0.730	0.737	0.465

Figure 1. Typical curves showing the effects of variations in rod spacing, cladding thickness, and cladding conductivity on the relative circumferential variation of the temperature on the outer wall of the cladding. The curves were calculated for the condition of fully developed slug-flow heat transfer. The symbol θ represents the circumferential angle with 0° being on the line that connects the center of any two adjacent rods. The symbol $t_{w,\theta}$ represents the outer surface temperature of a rod at any angle θ ; $t_{w,30}$ is the same, except at 30° ; $\bar{t}_{w,\theta}$ is the circumferential average of $t_{w,\theta}$ over the 30-degree arc; and t_b is the bulk temperature of the flowing coolant at the same axial position as that of the other temperatures.

the effect of variation in cladding conductivity on the circumferential variation of the local heat transfer coefficient. The less the relative thickness and thermal conductivity of the cladding, the greater will be the circumferential variations of local wall temperature and local heat transfer coefficient, and the less will be the variation in the local heat flux. The circumferential variation of the rod surface temperature is of interest from the standpoints of mass-transfer corrosion and thermal-cycling fatigue.

ANALYTICAL STUDY OF THE EFFECT OF ROD DISPLACEMENT ON HEAT TRANSFER TO LIQUID METALS FLOWING THROUGH A ROD BUNDLE

The objective of this project is to study analytically the effect of displacing a rod from its sym-

Figure 2. Typical curves showing the peripheral variation of the local normalized heat transfer coefficient at fairly representative values of P/D and $(r_2 - r_1)/r_2$, as affected by changes in the thermal conductivity of the cladding. The curves were calculated for the condition of fully developed slug-flow heat transfer. The symbol h_s represents the local heat transfer coefficient; $\bar{h}_s$ represents the circumferential average of h_s ; and θ has the same meaning as in Figure 1.

metrical position on heat transfer to liquid metals flowing in-line through an unbaffled rod bundle.

The first case being considered is that of rods arranged in an equilateral pattern. One of the rods is considered to be displaced toward an adjacent rod by some fraction, σ , of the maximum possible distance. Both the velocity and temperature fields are calculated by solving the governing momentum and energy equations numerically with the use of the finite-difference approach. Some of the calculated results are given in Table 1 and illustrate the effects of P/D (pitch-to-diameter) ratio and σ on the average Nusselt number.

In Table 1 Nu_s represents the average Nusselt number for the case where the wall temperature of the displaced rod is uniform in the circumferential direction while the heat flux is uniform in the axial direction. Nu_q is the average Nusselt number for the thermal boundary condition of uniform wall heat flux in all directions. $[Nu_s]_0$ and $[Nu_q]_0$ represent the corresponding Nusselt numbers for the symmetric cases. As can be seen, an increase in σ can, under most conditions, cause a large reduction in the average Nusselt number. The reduc-

tion is seen to be particularly large for the case of laminar flow subject to the boundary condition of uniform wall heat flux in all directions.

This project is being continued with an effort to obtain the temperature solutions for rod bundles having smaller P/D ratios. Thereafter attention will be focused on the coupled convection and conduction problem by considering the effect of cladding.

Figure 3. Thermal-entry-region local Nusselt numbers for pipe flow with axial conduction. In this figure, x = axial distance and $N_{Pe} = (2r_o\rho C_p\bar{u})/k$, where r_o = radius of a pipe, C_p = specific heat, ρ = density of fluid, k = thermal conductivity, and $\bar{u}$ is the average fluid velocity. N_{Nu} is the local Nusselt number defined by $N_{Nu} = (2r_o/k)[q_w/(t_w - t_b)]$, where q_w is the wall heat flux and t_w and t_b represent the wall temperature and the bulk fluid temperature, respectively.

Figure 4. Thermal-entry-region local Nusselt numbers for parallel-plate flow with axial conduction. In this figure, x = axial distance and $N_{Pe} = (4a\bar{u}\rho C_p)/k$ = Peclet number, where a is one-half the channel height. N_{Nu} is the local Nusselt number and equals $(4a/k)[q_w/(t_w - t_b)]$. The symbols $\bar{u}$, ρ , C_p , k , q_w , t_w , and t_b are explained in the caption of Figure 3.

EXACT SOLUTIONS FOR LOW-PECLET-NUMBER THERMAL-ENTRY-REGION HEAT TRANSFER IN LAMINAR FLOW THROUGH PIPES, PARALLEL-PLATE CHANNELS, AND ANNULI

During the report period, a mathematical method was devised to solve rigorously the problem of low-Peclet-number thermal-entry-region heat transfer. The method takes into account both transverse nonuniformity in the velocity field and axial conduction. This problem has special relevance to the analytical theory of liquid-metal heat transfer in channel flow. To allow for the effect of upstream conduction, the inlet fluid temperature was considered to be uniform at $x = -\infty$. The method consists essentially of determining separately the eigenconstants for the adiabatic region $x \leq 0$ and the heated region $x \geq 0$, and then matching both the temperatures and temperature gradients at $x = 0$. To achieve the matching process, two orthonormal sets of functions were constructed from the nonorthogonal eigenfunctions, and the series expansion coefficients were determined by solving a set of relevant matrix equations. This proposed method was found to yield theoretical solutions that show excellent agreement with numerical solutions reported in the literature.

Figure 5. Thermal-entry-region local Nusselt numbers for flow through an annulus with axial conduction. Here, Z is the axial distance and $N_{Pe} = [2(r_2 - r_1)\bar{u}\rho C_p]/k$ is the Peclet number. $[Nu]_1 = [2(r_2 - r_1)/k][q_1/(t_w - t_b)]$ and $[Nu]_2 = [2(r_2 - r_1)/k][q_2/(t_w - t_b)]$ are the local Nusselt numbers, where q_1 and q_2 represent the heat flux at the inner and outer wall, respectively, of an annulus. The symbols for $\bar{u}$, ρ , C_p , k , t_w , and t_b are explained in the caption of Figure 3.

Figures 3 through 5 illustrate the local Nusselt number obtained for laminar flow through circular pipes, parallel-plate channels, and an annulus ($r_1/r_2=0.5$, where r_1 and r_2 =inner and outer radius, respectively, of an annulus) with a step change in wall heat flux at $x=0$. In Figure 5, $[\text{Nu}]_1$ and $[\text{Nu}]_2$ denote the Nusselt numbers for the cases where a uniform heat flux is maintained at the inner and outer wall, respectively, of the annulus. As can be observed, the Nusselt curves behave quite similarly despite the difference in the shape of the channel. As Peclet number is reduced, the local Nusselt number is seen to decrease more gradually and tends to distribute more uniformly throughout the thermal-entry region. The effect of axial conduction is seen to become increasingly important, the smaller the Peclet number.

HEAT TRANSFER IN MAGNETOHYDRODYNAMIC CHANNEL FLOW SUBJECT TO THE BOUNDARY CONDITION OF THE THIRD KIND

Operation of a magnetohydrodynamic (MHD) device involves handling of a fluid at very high temperatures. There exists, therefore, considerable interest in investigating the heat transfer characteristics of MHD channel flow subject to the boundary condition of the third kind, the so-called radiative boundary condition. For this problem, the governing energy equations, which take into account Joule heating, viscous dissipation, and axial conduction, can be written as:

For the region $-\infty < x \leq 0$:

$$\frac{\cosh M - \cosh M(y/a)}{\cosh M - (\sinh M)/M} \bar{u} \frac{\partial T_1}{\partial x} = \frac{k}{C_p \rho} \left[\frac{\partial^2 T_1}{\partial x^2} + \frac{\partial^2 T_1}{\partial y^2} \right], \quad (1)$$

$$\text{at } x = -\infty, \quad T_1 = T_0, \quad (2a)$$

$$\text{at } y=0 \text{ and } y=a, \quad \partial T_1 / \partial y = 0. \quad (2b)$$

For the region $0 \leq x < \infty$:

$$\begin{aligned} & \frac{\cosh M - \cosh M(y/a)}{\cosh M - (\sinh M)/M} \bar{u} \frac{\partial T_2}{\partial x} \\ &= \frac{k}{C_p \rho} \left[\frac{\partial^2 T_2}{\partial x^2} + \frac{\partial^2 T_2}{\partial y^2} \right] + \frac{\mu}{C_p \rho} (\partial u / \partial y)^2 \\ & \quad + \frac{\bar{u}^2 \sigma B_o^2}{C_p \rho} [-e + (u/\bar{u})^2], \end{aligned} \quad (3)$$

$$\text{at } x = \infty, \quad T_2 = T_f = P_1 Y^2 + P_2 \cosh 2MY$$

$$+ P_3 \cosh MY - \sum_{i=1}^3 P_i G_i, \quad (4a)$$

$$\text{at } y=a, \quad -k \frac{\partial T_2}{\partial y} = \kappa (T_2 - t_a); \quad \text{at } y=0, \quad \frac{\partial T_2}{\partial y} = 0. \quad (4b)$$

At $x=0$:

$$T_1(y) = T_2(y), \quad \frac{\partial T_1(y)}{\partial x} = \frac{\partial T_2(y)}{\partial x}, \quad (5)$$

where a =one-half of channel height; $Y=y/a$; T_1, T_2 =fluid temperature in the adiabatic and heated region, respectively; M =Hartmann number; k =thermal conductivity; C_p =specific heat; T_0 =inlet fluid temperature; t_a =ambient temperature; η =the heat generation parameter; κ =a proportionality factor; $\bar{u}$ =average fluid velocity; B_o =magnetic field induction; σ =electric conductivity; ρ =density of fluid; $e=E/\bar{u}B_o$, where E is electric field strength; $P_1 = -0.5 (e-A)^2 M^2 \eta$; $P_2 = -0.25 B^2 \eta$; $P_3 = 2B(e-A)\eta$, where $A = \cosh M / [\cosh M - (\sinh M/M)]$ and $B = -1 / [\cosh M - (\sinh M/M)]$; $\Delta = \kappa a / k$.

The solutions to the above sets of equations was obtained in explicit form, and the effects of Hartmann number, electric field factor, radiation, and heat generation parameter, as well as Peclet number, on the local Nusselt number were examined. In general, the local Nusselt number was found to increase as the Hartmann number or the radiation parameter is increased. The effect of Hartmann number becomes more significant the larger the value of Δ . Both the electric field factor and the heat generation parameter were found to cause the local Nusselt number to go through maxima or minima.

INCIPIENT BOILING OF LIQUID METALS

An understanding of the incipient-boiling phenomenon, particularly the superheating aspect of bubble nucleation, is important for the design and safe operation of liquid-metal-cooled fast reactors. In a continuing investigation, a number of runs were carried out in a forced-convection loop (with potassium) to determine the effect of flow rate on incipient-boiling (nucleation) superheat. The 0.622-i.d. vertical, cylindrical test section was induction heated and had an "as-received" surface finish. Oxygen content of the potassium was ≈ 35

Figure 6. Incipient boiling superheats for K in convective flow (K at ≈ 15.3 psia).

ppm. The operational procedure was to (a) subject the liquid-filled test section to a specific deactivation temperature-pressure condition for 2 hr, (b) obtain a number of boiling inception superheat measurements at various boiling pressures and flow rates, and (c) repeat under a different deactivation condition. For each superheat measurement, adjustments were first made to obtain the desired boiling pressure, flow rate, and heat flux at the test section. Power input to a preheater was then slowly increased in small incremental steps, thus raising the test section temperatures. A minimum wait of 20 min under steady-state conditions was observed between incremental power increases. Upon the occurrence of boiling inception, fluid and wall temperatures in the test section were recorded and the superheat, ΔT_s , calculated on the basis of pressure and wall temperature at the exit end of the test section.

Superheats were measured, after different deactivations, at boiling pressures of 8 to 24 psia and over a flow rate range of 0.2 to 3 ft/sec. Some results for one set of test conditions are shown in Figure 6. These data represent measurements made after a particular deactivation, at essentially constant pressure and heat flux, and with flow rate as the only major variable. It is clearly evident that increasing flow causes a decrease in the superheat measured at boiling initiation. For these data,

Figure 7. Correlation of turbulent flow effect on incipient boiling superheats of K ($\bar{P} \approx 15.3$ psia).

ΔT_s decreased from $\approx 90^\circ$ to $\approx 20^\circ$ F as flow velocity increased from 0.3 to 3.3 ft/sec.

A theoretical explanation for this flow effect is being developed. Based on the recognition of wall pressure fluctuations associated with turbulent flow, a phenomenological model was derived which suggests that the effect of flow on incipient-boiling superheat can be correlated in terms of the group.

$$\psi = (\rho v^2 f F_1) / (\Delta P_0 - \bar{\Delta P}) \quad (\text{units of } g_c), \quad (6)$$

where ρ = density of fluid; v = velocity; f = Moody's friction factor; F_1 = ratio of root-mean-square pressure fluctuation to wall shear stress, a known function of Reynolds number; $\bar{\Delta P}$ = time-mean pressure excess corresponding to measured ΔT_s ; and ΔP_0 = limiting value of $\bar{\Delta P}$ as $Re \rightarrow Re_{\text{critical}}$. The model predicts that ψ should be a function primarily of Reynolds number and absolute time-mean pressure ($\bar{P}$), and that ψ should generally increase with increasing Re .

Figure 7 shows the data of Figure 6 replotted as ψ vs Reynolds number. Since these data were obtained at essentially constant mean pressure, $\bar{P}$, the theory would require that the points correlate on a single curve. It is seen that the results indeed appear to do so. Furthermore, the experimental values of ψ do increase with increasing Re , as predicted.

The solid curve in Figure 7 represents the function $(\rho v^2 f F_1) / \bar{P}$. Any ψ value below this curve would correspond to a condition of liquid tension resulting from local pressure fluctuations. Such a condition would not likely occur in straight-pipe flow, and it is seen that all the experimental points did fall above this "limiting" curve.

Probe starts in liquid, comes momentarily in contact with vapor upon first bubble nucleation, is resubmerged in liquid, then again contacts vapor as boiling continues for ≈ 3 min, and finally is resubmerged in liquid as boiling ceases.

Figure 8. Void probe response to boiling inception.

VOID PROPAGATION IN LIQUID METALS

For liquid-metal-cooled reactors, there exists the possibility of violent voiding in the core due to sudden vaporization of the coolant following inadvertent power or flow excursions. The dynamics of this voiding process—the rate of void propagation—is of prime interest.

To date, studies of liquid-metal voiding have dealt primarily with single-channel geometries. Both experimental measurements and computer-code analyses of void growth rates (and associated liquid expulsion) have been limited to the one-dimensional, single-channel case. A program to extend the investigation to multichannel geometries has been initiated at BNL. Experimentally, the objective is to measure the rate of void propagation in multiple, interconnected channels (e.g., in rod bundles). The intention is to obtain time-space maps of the moving liquid-vapor interface. Variables to be studied include incipient-nucleation superheat, geometry (e.g., rod diameter, pitch, wall effect), heat flux, system pressure, and fluid-dynamic boundary conditions at the inlet and outlet of the channels. Initial experiments to develop instrumentation techniques and to obtain some

preliminary data will be carried out in the boiling K loop. Final tests will be performed in a Na-voiding facility, to be designed as an addition to the Na loop.

Complementary analytical studies are being pursued. Both fundamental analyses of specific contributory phenomena (such as rapid transient movements of liquid-vapor interface between channels) and computer-coded calculations of overall voiding behavior will be involved. The latter will differ from existing voiding codes in that multichannel effects will be included and attempts will be made to obtain a more detailed description of local behavior within the rod bundles.

The main effort to date has been in the development of instrumentation. To accomplish the desired experimental measurements, it is essential that some means be found to detect the presence or absence of voids at local points. A probe has been developed that is able to detect void/liquid conditions in a region of ≈ 0.02 in. dimension, with response time of < 1 msec. Experiments with the probe in Hg have been quite successful. First tests with the probe in K have shown that it can operate in alkali metals at temperatures up to $\approx 1600^\circ\text{F}$. Figure 8 presents a sample record of the probe's

response to incipient bubble nucleation in K at 1490°F. It is seen that very definite indications of the incipient vaporization were obtained. Current efforts are directed toward the development of a dummy heater rod instrumented with several of these void-sensing probes. Such instrumented rods will then be used to measure void propagation rates in annular and in rod-bundle geometries.

LIQUID-METAL TWO-PHASE PRESSURE DROP WITH AND WITHOUT NET VAPORIZATION

Extensive two-phase liquid-metal pressure drop data were recently obtained using two different test sections in the boiling potassium heat transfer facility at BNL. Adiabatic runs were made on test section No. 1, whereas both adiabatic and diabatic (net heat input) runs were made on test section No. 4.

The data were analyzed with the intent of deriving a method for predicting pressure drop in two-phase liquid-metal flow with net vaporization. The momentum equation is

$$\frac{dP}{dL} = -\left(\frac{g}{g_c}\right)\rho - \left(\frac{d}{dL}\right)\left[\rho_v \alpha u_v^2 \left(1/g_c\right) - \rho_l (1-\alpha) u_l^2 \left(1/g_c\right)\right] - (dP/dL)_{TP}, \quad (7)$$

where dP/dL = pressure drop per unit length, ρ = density of two-phase fluid = $\alpha\rho_v + (1-\alpha)\rho_l$, ρ_l, ρ_v = liquid and vapor densities, respectively, u_l, u_v = liquid and vapor velocities, respectively, α = void fraction, and $(dP/dL)_{TP}$ = frictional pres-

sure-loss gradient. This equation can be used in a stepwise calculation, starting with the inlet pressure, to calculate the exit pressure. However, the two unknowns, α and $(dP/dL)_{TP}$, must be obtained first. The approach taken in this work was to use the adiabatic data to establish the necessary relationships for α and $(dP/dL)_{TP}$, and then to use these relationships in a stepwise integration of Eq. (7) to calculate a pressure drop for the diabatic runs. These predicted results were then compared with the measured pressure drops.

Void fractions for the adiabatic runs were initially calculated by the Lockhart-Martinelli correlation [Chem. Eng. Progr. 45, 39-48 (1949)]. The frictional pressure drop was then calculated using Eq. (7) and the results were plotted as recommended by these same authors. The results are shown in Figure 9 where they are compared with other recent data. The same procedure was repeated with the correlations of Martinelli-Nelson, Balzhiser, Bankoff, and Baroczy. These various correlations for α and $(dP/dL)_{TP}$ were then used to calculate the predicted pressure drop, as mentioned above, for the diabatic (net vapor generation) runs. The best results were obtained with the Martinelli-Nelson [Trans. ASME 70, 694-702 (1948)] correlation which gave a standard deviation of $\approx 20\%$ when the calculated pressure drop was compared with the measured pressure drop.

Figure 9. Adiabatic two-phase pressure drop for potassium correlated by the Lockhart-Martinelli method.

Figure 10. Adiabatic two-phase pressure drop for potassium correlated by annular-flow model with empirical void-fraction correlation.

Figure 11. Void fractions for two-phase potassium flow.

Figure 12. Diabatic two-phase pressure drop for potassium.

We next analyzed the data using the annular flow model described by Levy [*Ibid.* 82, 113-24 (1960)],

$$\phi_l = [(dP/dL)_{TP} / (dP/dL)_l]^{1/2} = 1/R_l = 1/(1-\alpha). \quad (8)$$

The adiabatic pressure drop data and Eq. (8) were used together with Eq. (7) in an iterative fashion to empirically determine a void fraction correlation. The starting point in the iteration was to neglect the first two terms on the right side of Eq. (7). The final iteration gave the results shown in Figure 10. This void fraction was replotted and correlated by the method suggested by Lockhart

and Martinelli. The empirical BNL correlation thus obtained is shown in Figure 11 where it is compared with the water data of Lockhart and Martinelli and with the potassium curve recommended by Baroczy (NAA-SR-8171, 1963). Eq. (9) fits the data closely.

$$\ln(R_l) = -1.654 + 0.5660 \ln(X_{LM}) - 0.06405 [\ln(X_{LM})]^2. \quad (9)$$

This correlation for the void fraction, together with Eq. (8), was then used for the prediction of the two-phase pressure drop with net vapor generation. The results, compared with the measured pressure drop, are shown in Figure 12. The standard deviation by this method is $\approx 10\%$.

Waste Disposal Studies

L. HATCH, R. DRAGER, E. TUTHILL,
J. FEDELEM, R. FEINDT

To establish the feasibility of solidifying high-level radioactive wastes on an engineering scale, the AEC has sponsored a program to demonstrate several promising methods. The Brookhaven phosphate glass process is one of three methods that are being tested in a full-scale prototype (WSEP) at Pacific Northwest Laboratory (PNL). In support of the prototype, operation of the Brookhaven pilot plant with simulated waste was continued during the past year, and operability was demonstrated with a number of new, or projected, waste types including those from reprocessing high burnup 45,000 MWD/tonne U fuels from light-water reactors and also from reprocessing Liquid Metal Fast Breeder Reactor (LMFBR) fuels with 100,000 MWD/tonne U burnup.

PHOSPHATE GLASS PROCESS

Recent laboratory and pilot-plant studies have been directed toward establishing a satisfactory phosphate glass flowsheet for PW-4m, which is a low iron, 45,000-MWD/tonne U waste. In the search for a suitable feed composition major consideration was given to viscosity and solids deposition in the evaporator concentrate and to the character of the glass which formed at 1000°C.

In the course of this investigation an additional requirement was imposed by PNL, i.e., that 18 kW of radiolytic power be generated in 60 liters of

glass produced from a waste containing fission products equivalent to 49.7 watts/liter. However, based on our previous experience with PW-1 and PW-2 flowsheets, sufficient volume reduction could not be realized to achieve this power density in the glass product.

Consequently, a new program was initiated to determine roughly the maximum fission product loading that could be realized in the phosphate glass. It was assumed that metaphosphate glasses were the most suitable and the restriction was imposed on the system that the ratio of the sum of the metal ions to phosphorous equal $\Sigma M^+/P = 1$. By plotting Fe, Na, and P as coordinates on a triangular graph the locus of points for constant $\Sigma M^+/P = 1$ was a straight line as shown in Figure 13. Five different iron to sodium ratios were then chosen along this line, and representative formulations were tested in the laboratory by evaporating the solution and then heating to 1050°C for 1 hr. Formulations Nos. 2 and 3 formed good glasses at

1050°C. Further investigation showed that composition type No. 3 formed a good glass as low as 900°C and this composition, having a 0.25 mole % Fe and 0.75 mole % Na, was used in the subsequent tests. The question then remained as to what extent a glass of this general composition could be loaded with fission products. A number of overall compositions were then calculated (Table 2). With the four-component system (fission products, iron, sodium, and phosphorous), the mole percent of fission products ranged from 4.4 to 12.1. The maximum heat power density of the glass product was then calculated to be 0.3 W/cc of glass, or, by the PNL requirement, 18 kW/60 liters of glass. Compositions 3-2, 3-3, 3-5, and 3-7 were prepared in the laboratory and a good glass resulted in each case with a temperature of 1050°C and a period of 1 hr. In the case of composition 3-7 the fission product loading per unit volume of glass was roughly 2½ times that obtained earlier in the program with PW-1 waste; this represents a signifi-

Table 2
PW-4m Glasses Containing Various Amounts of Fission Products

Composition No.	Mole % /molarity of feed				Power density, W/cc glass	Appearance of glass
	F.P.	Fe	Na	P		
3-1	4.4	8.2	24.7	62.7	0.113	
	0.9026	1.67	5.00	12.7		
3-2	5.6	7.8	23.4	63.2	0.143	Good
	0.9026	1.25	3.75	10.15		
3-3	7.6	7.0	20.9	64.5	0.189	Good
	0.9026	0.833	2.50	7.70		
3-4	8.4	6.6	19.9	65.1	0.205	
	0.9028	0.714	2.14	6.99		
3-5	9.1	6.3	19.0	65.5	0.224	Good
	0.9028	0.625	1.88	6.45		
3-6	9.8	6.1	18.2	65.9	0.235	
	0.9028	0.556	1.67	6.04		
3-7	10.5	5.8	17.4	66.3	0.254	Good
	0.9028	0.50	1.50	5.70		
3-8	12.1	5.2	15.6	67.3	0.300 (18 kW/60 liters glass)	
	0.9028	0.390	1.17	5.07		
Comparison PW-1 (45/20)	4.2	10.0	21.4	64.6	0.105	
	0.878	2.09	4.47	13.5

Figure 13. Plot of glass compositions expressed in mole percent.

Figure 14. Plot of glass compositions showing fission product loadings.

Figure 15. Relationship of power density in PW-4m phosphate glass to fission product loading.

cant increase in plant capacity with respect to nuclear reactor energy output. Laboratory tests were made to determine viscosity, volume reduction, denitration, and other evaporator and melter characteristics with compositions Nos. 5, 7, and 8.

For comparison, the power density of PW-1, adjusted from 20,000 to 45,000 MWD/tonne fuel burnup, is also shown at the bottom of Table 2.

Since fission product loading is considered as a single fourth component of the solution, this quantity is represented as the size of each triangle shown in Figure 14.

Figure 15 shows the relation of power density in W/cc to mole percent fission product loading for the glass type considered here.

The most satisfactory formulations were then tested in pilot plant operation and compositions PW-4m-7 and PW-4m-8 were used in plant runs EM-10 and EM-11, respectively. In each of these runs operation was smooth and no plugging of process lines was experienced. In run EM-10 the glass production rate was 1.31 ft³/24 hr, which relates to the reprocessing of 0.56 tonne U at 45,000 MWD burnup/24 hr, and in run EM-11 the rates were 1.28 ft³ and 0.50 tonne U/24 hr. In each run the temperature profile indicated that substantially higher throughputs could be maintained. With each formulation the consistency of the process solution was such that there was much less tendency for solids to settle than had been the case with PW-1 waste, and this facilitated the transfer of the evaporator concentrate to the melter. The waste composition and additives to prepare the feed for PW-4m-7 and PW-4m-8 are given in Tables 3 and 4. The operating data for runs EM-10 and EM-11 are given in Tables 5 and 6.

To confirm the operability flowsheet for Purex waste type PW-4m (45,000 MWD/tonne U), the Brookhaven pilot plant was operated for a period of 65 hr (Run EM-12), and all necessary operating values were determined.

During the course of the run a number of extreme conditions were imposed on the system with the objective of establishing practical operating limits. For example, the evaporator temperature was raised until the viscosity of the concentrate became excessive and transfer to the melter was difficult. Similarly, blowdown and periodic flushing of the purge tubes, which is an established practice for preventing plugging, was purposely delayed. However, the operating data obtained represent only the periods of steady-state conditions. Based on the results of the run it was agreed by both PNL and BNL personnel that PW-4m-7 was a suitable flowsheet for use in the WSEP testing program.

The first LMFBR waste composition for WSEP demonstration that was investigated in the laboratory was based on 100,000 MWD/tonne of U at 200 MW/tonne of U and 6 months out-of-reactor cooling. Since there was little preliminary investigation with this solution, the first problem was to determine the raw waste characteristics when made up to a concentration of 100 gal/tonne. This waste represents an extreme case with respect to the amount of troublesome fission products which will be present (i.e., ruthenium, antimony, tellurium, etc.) relative to the amount of inert materials added during fuel reprocessing. Although it is recognized that the core and the blanket might be processed simultaneously (thereby resulting in lower average burnup values), the WSEP program is planned in order to investigate the case which maximizes the differences between the wastes from the fast and the thermal reactor fuels. The transplutonium elements americium and curium would be present in the wastes, since they would remain in the solvent extraction waste stream unless special steps were used for their recovery.

At 100 gal/tonne the waste solution as prepared in the laboratory could be handled only with difficulty and it is questionable whether it could be piped for any distance as a process stream. Addition of phosphoric acid made the solution considerably less difficult to handle, probably by complex formation, and confirmed the earlier suggestion that the phosphoric acid be added at the fuel

Basic Waste Composition as Reported by BNWL
(PW-4m, 100 gal/tonne, 45,000 MWD/tonne)

^a Mo does not contribute to cation equivalent.
^b Includes Na from sodium silicate.
^c Rb⁺ substituted for K⁺.
^d RE = rare earths.
^e Na in Na₂MoO₄ contributes to cation equivalent (0.2600) + (0.0620) = 0.3220.
^f Ru⁺³ substituted for Fe⁺³.
^g Rh⁺² substituted for Co⁺².
^h Pd⁺² substituted for Ni⁺².
ⁱ Tc⁺⁶ substituted for Mo⁺⁶.

Ingredients Added to Basic Waste for Phosphate Glass Feed Composition
(PW-4m-7, run EM-10)

Element	Molarity	Compound	MW	Moles	Cation equiv.	g/liter
^a Fe ⁺³	0.500	Fe(NO ₃) ₃ · 9H ₂ O	404	0.450	1.350	181.80
^b Na ⁺	1.500	NaNO ₃	85	1.400	1.400	119.00
				ΣM ⁺	<u>2.750</u>	
PO ₄	5.4372	H ₃ PO ₄ (85.0%, 1.69 sp. gr.)	98	5.4372		370.03 ml/liter
		(PW-4m-8, run EM-11)				
^a Fe ⁺³	0.390	Fe(NO ₃) ₃ · 9H ₂ O	404	0.340	1.020	137.36
^b Na ⁺	1.170	NaNO ₃	85	1.270	1.270	107.95
				ΣM ⁺	<u>2.290</u>	
PO ₄	4.9783	H ₃ PO ₄ (85.0%, 1.69 sp. gr.)	98	4.9783		338.8 ml

^aSubstituted 0.050 *M* contained in the waste. ^bSubstituted 1.000 *M* contained in the waste.

Table 5

Operating Data for Run EM-10 (Purex 4m-7, 100 gal/tonne, 45,000 MWD/tonne)	
Evaporator temperature	127.0°C
Evaporator feed rate	13.7 liters/hr
Evaporator condensate rate	8.0 liters/hr
Volume reduction factor in evaporator	2.4
Melter condensate rate	4.15 liters/hr
Glass product rate	1.55 liters/hr (1.31 ft ³ /day)
Equivalent to tonne of U/24 hr	0.56
Overall volume reduction factor from feed to glass product	8.8
Volume reduction factor from waste to glass	5.0
HNO ₃ condensate/feed	58.4%
Evaporator ΔT	11.1°C
Performance factor	1.23 liters/hr-°C
Residence time, evaporator	7.7 hr
Residence time, melter	2.25 hr
Average centerline melter temperature	1150°C
Density of glass	2.83 g/cm ³
Evaporator feed viscosity at bp (127°C)	220 cP
Evaporator feed viscosity at 100°C	176 cP
Denitration of composite sample	68.18%

Table 6

Operating Data for Run EM-11 (Purex 4m-8, 100 gal/tonne, 45,000 MWD/tonne)	
Evaporator temperature	131°C
Evaporator feed rate	11.8 liters/hr
Evaporator condensate rate	6.8 liters/hr
Volume reduction factor in evaporator	1.74
Melter condensate rate	3.5 liters/hr
Glass product rate	1.51 liters/hr (1.28 ft ³ /day)
Equivalent to tonne of U/24 hr	0.5
Overall volume reduction factor from feed to glass product	7.8
Volume reduction factor from waste to glass	5.3
HNO ₃ condensate/feed	57.6%
Evaporator ΔT	10.5°C
Performance factor	1.12 liters/hr-°C
Residence time, evaporator	8.8 hr
Residence time, melter	2.33 hr
Average centerline melter temperature	1135°C
Density of glass	2.89 g/cm ³
Anti-foam addition (mixed 100 ppm or 6.7 g/liter of distilled H ₂ O)	0.278 ml/liter of feed
Denitration of composite sample	49%
Denitration of instantaneous sample	56%

Table 7

Fast Reactor Waste Composition for WSEP Demonstration
(100,000 MWd/tonne at 200 MW/tonne, 6 months out-of-reactor time)

Chemicals from reprocessing (concentrations are at 378.5 liters/tonne)

H	0.5 <i>M</i>	U	0.01
Fe	0.16	Pu	0.001
Cr	0.046	NO ₃ ⁻¹	4.75
Ni	0.023	PO ₄ ⁻³	0.06
Na	0.1	Σ <i>M</i> ⁺ _{chem}	0.83

Fission products (F.P.)		F.P. as oxide	WSEP substitute	Metal equivalents	
				Formula basis	<i>M</i> ⁺
Se	0.005 <i>M</i>	SeO ₂		SeO ₄ ⁻²	(-0.02)
Rb	0.019	Rb ₂ O	K ₂ O	Rb ⁺	0.019
Sr	0.04	SrO		Sr ²⁺	0.08
Y + RE	0.47	(Y + RE) ₂ O ₃	RE ₂ O ₃	RE ⁺³	1.41
Zr	0.22	ZrO ₂		Zr ⁺⁴	0.88
Nb	0.002	Nb ₂ O ₅	ZrO ₂	Zr ⁺⁴	0.008
Mo	0.24	MoO ₃		MoO ₄ ⁻²	(-0.48)
Tc	0.06	TcO ₃	MoO ₃	MoO ₄ ⁻²	(-0.12)
Ru	0.22	RuO ₂	Fe ₂ O ₃	Fe ⁺³	0.66
Rh	0.06	Rh ₂ O ₃	CoO	Co ⁺²	0.12
Pd	0.16	PdO	NiO	Ni ⁺²	0.32
Ag	0.019	Ag ₂ O		Ag ⁺	0.019
Cd	0.01	CdO		Cd ⁺²	0.02
In	0.001	In ₂ O ₃	SnO ₂	Sn ⁺⁴	0.004
Sn	0.01	SnO ₂		Sn ⁺⁴	0.04
Sb	0.003	Sb ₂ O ₃		Sb ⁺³	0.009
Te	0.034	TeO ₂		TeO ₄ ⁻²	(-0.136)
Cs	0.21	Cs ₂ O		Cs ⁺	0.21
Ba	0.068	BaO		Ba ⁺²	0.136
La	0.058	La ₂ O ₃	RE ₂ O ₃	RE ⁺³	0.174
				^a Σ <i>M</i> ⁺ _{F.P.}	4.109
Transplutonium elements (TP)					
Am	0.02 <i>M</i>	Am ₂ O ₃	UO ₃	U ⁺⁶	0.12
Cm	0.001	Cm ₂ O ₃	UO ₃	U ⁺⁶	0.006
				Σ <i>M</i> ⁺ _{TP}	0.126
				^a Σ <i>M</i> ⁺ _{F.P.+TP}	4.23
				ΣΣ <i>M</i> ⁺ _T	5.06

^aThe negative metal equivalents of the elements present as anions (Mo, Se, Te) are not included in these totals. These equivalents must be subtracted from the metal equivalents to give a net metal equivalent.

Table 8

Operating Data for Run EM-13 With
Fast Reactor Feed Composition for WSEP Demonstration

(100,000 MWd/tonne U at 200 MW/tonne U;
6 months out-of-reactor time; additives:
Na, 3.00 M and Fe, 1.00 M; $\Sigma M^{+}/P = 1$)

Specific gravity of feed at 27.5°C	1.53
Boiling point	125.0°C
Specific gravity at bp	1.70
Volume reduction in evaporator	<2.0
Viscosity at 115°C	240 cP
Glass forming temperature	1210.0°C
Glass remelt temperature	650° to 700°C
Glass density	2.95
Glass rate	0.078 to 1.3 ft ³ /day
Global temperature	1340° to 1360°C

reprocessing plant to facilitate transfer to the waste processing plant.

The pilot plant was operated for 20 hr (Run EM-13) to study the performance of an LMFBR 10^5 MWD/tonne waste composition in preparation for the PNL WSEP Run No. P.G. 11. In preparation of the feed for the run, the waste shown in Table 7 was adjusted so that the Fe and Na concentrations were 1 and 3 moles/liter, respectively. H_3PO_4 was then added to make the $\Sigma M^+/P = 1$. Samples of all effluents and of the product glass were analyzed.

Based on the results of Run EM-13, shown in Table 8, the adjusted waste feed formulation was considered satisfactory for WSEP use.

Screw Pump Development

As previously stated, the air-lift feed pot which delivers evaporator concentrate to the melter has been a source of trouble particularly with the earlier waste type PW-1. More recently in PNL runs the air-lift operated satisfactorily. It should be noted that in the course of the last year, development in glass composition made it apparent that even PW-1 wastes could be adjusted by the addition of phosphoric acid and sodium so as to simulate PW-4 waste. Although the air-lift unit may well function satisfactorily for all waste types, an Archimedes screw-type lift pump (Figure 16) for transferring the evaporator bottoms to the melter has been under development at Brookhaven. Special limitations were placed on the design of the pump to allow for installation by remote handling tools in the existing process evaluation test at WSEP. The present design was made to meet existing PNL conditions; however, for future considerations a larger diameter screw pump should show better operating characteristics, i.e., lower rpm requirements.

Pilot Plant

After a number of preliminary tests with different screw designs, a screw was cut with a pitch of $\frac{1}{2}$ in./in. and a clearance between the housing and the screw of 0.010 in. In a 34-hr pilot plant test, the pump performed satisfactorily and delivered up to 6.6 liters of evaporator concentrate per hr, more than twice that anticipated for the WSEP Run P.G. 11 with LMFBR wastes. Upon completion of the run, the pump was disassembled and found to be free of deposits and showed no signs of wear. The unit was then shipped to PNL where it

Figure 16. Screw pump showing motor drive mounted at top.

Figure 17. Schematic diagram of original solution feeder.

will be further tested in the WSEP with full-level waste.

Melter Solution Feeder Development

The solution feeder shown schematically in Figure 17 is a 17-in.-long jacketed platinum tube which delivers the evaporator concentrate to the crucible at a point 6 in. above the molten glass pool. With the short period of free fall, splattering of the solution on sudden exposure to the high temperature environment is minimized. The jacket is cooled by water boiling under total reflux. Occasionally deposits have built up in the feeder and a successful remedy has been to cut off the flow of the feed and the cooling water to the condenser to allow the water in the cooling jacket to boil out of the system; the temperature of the feeder then rises

Figure 18. New solution feeder (side view).

Figure 19. New solution feeder (top view).

Figure 20. Plot of results of solution feeder studies with glycerin at 130°C.

to a level at which the deposits convert to a molten glass and drain away. Normal operation is resumed with a slow addition of water to the jacket. At normal operating rates the temperature of the evaporator concentrate is reduced on passing through the solution feeder from a range of 125° to 140°C to about 100°C. This results in a substantial increase in the viscosity of the solution which, in turn, is conducive to occasional plugging in the feeder. To avoid the temperature drop, a modified solution feeder (Figures 18 and 19) was developed to provide an insulating annulus between the delivery tube and the cooling jacket.

In a preliminary component test, results of operating the original and new solution feeders were compared to determine the effectiveness of the insulating annulus on the temperature of glycerin-water as a rough substitute for glycerin, the evaporator concentrate, entering the feeder at 130°C and flowing at various rates. These results are plotted in Figure 20. The curve for the noninsulated solution feeder shows that a feed rate in excess of 6 liters/hr was necessary to maintain the glycerin in the neighborhood of 130°C, whereas with the insulated solution feeder, only 3 liters/hr was necessary. Comparable tests will be made with simulated waste solutions.

Melter Scale-Up

In both the BNL pilot plant and PNL prototype, the phosphate glass melters have a capacity to process waste equivalent to ≈ 1 tonne of U/day. Future commercial plants would be expected to operate on a level equivalent to about 5 tonnes/day with two melters operating in parallel. Thus, on this basis, which is independent of burnup, a scale-up $\approx 2\frac{1}{2}$ times the present melter capacity would be indicated.

The present approach to increasing melter capacity involves the use of induction heating, with the relatively thin platinum wall of the crucible as a susceptor. The overall problem may be subdivided as follows.

(1) First there is the electrical engineering problem of finding a suitable machine to heat the crucible uniformly without sparking. Thus far, in a number of preliminary experiments with 450 and 500-kc RF induction machines, the necessary heat flux was not obtained and sparking between the coil and the crucible and the coil and the solution feeder occurred. Recently, satisfactory heating of the crucible was accomplished with a 10-kc, 50-

kW motor generator operating at about 20% of capacity. The heat power requirement for producing phosphate glass from waste concentrate is about 7 kW/tonne of U/24 hr, and preliminary calculations indicated that the 2½ times scale-up can be accomplished with this machine.

(2) The next problem under investigation is that of instrumentation necessary to prevent damage to the crucible from overheating. A number of control and fail-safe mechanisms estimated to have sufficiently fast response times are being considered. Thermopiles activated through ⅛-in.-o.d. sapphire light pipes, which can conveniently be placed between the windings of the induction coil without being affected by the RF, appear promising.

(3) The transfer of heat from the platinum to the concentrate as it changes from an aqueous to a molten salt system is being studied. Equipment with which to continuously feed the conical melter and to study the flow characteristics and rates of conversion is being assembled.

A number of preliminary bench-scale experiments were carried out to study the induction heating characteristics of platinum crucibles of several geometric shapes. High heat fluxes are possible with induction systems, and removal of the heat from the Pt by a moving layer of waste concentrate as glass is formed becomes the limiting factor. In these experiments, the 0.040-in.-thick platinum crucible was the susceptor. However, it remains to be determined whether the molten glass which rapidly increases in conductivity above 1000°C will couple effectively with selected inductive frequencies.

Conversion of the evaporator concentrate to a molten glass involves phase changes from the aqueous solution to a semi-solid and finally to a fused phosphate salt. The mobility of the products of these phase changes is a key problem in designing a workable crucible. To determine the degree of mobility over the complete range of phases, a platinum trough 1½ in. across and 18 in. long was enclosed in a quartz tube mounted at various angles from 20° to 45° to the horizontal. PW-4m evaporator concentrate was fed at the upper end to the platinum surface which was maintained at 1000° to 1250°C. The results were encouraging. Initially, the concentrate spattered until a thin layer of molten glass was built up. The concentrate, undergoing phase changes, then moved somewhat uniformly down the trough, apparently on the sublayer of molten glass. At the upper end

water and nitric acid escaped with moderate foaming. If the feed rate was too high, material moving in the surface region was not converted to glass before it reached the lower end. Preparations are being made to investigate the use of a heated tube instead of the trough to provide a greater heated surface, and the length and slope of the tube will be determined by the time required for the necessary temperature buildup at the center of the moving mass.

In previous discussions with ORNL and PNL, the problem of guarding against overheating the platinum (mp, 1760°C) under full heat flux together with a temporary loss of feed was emphasized. The matter was investigated with personnel from Generator Manufacturers who advised that motor-generator (MG) and radiofrequency (RF) induction machines have response times of 0.1 and 4.0 sec, respectively. These are considered to be fast enough to give the necessary burn-out protection. A conical induction coil was made with 17 turns of ¼-in. copper tubing imbedded in Norton castable Alundum 33-1 high temperature refractory cement, as shown in Figure 21. This coil was designed for use with the 10-kc, 50-kW induction generator in conjunction with the conical platinum crucible previously described. In a test, the platinum crucible was heated to ≈1200°C with a power setting of ≈20% of full load capacity. On cooling, the cemented coil showed no signs of deterioration because of thermal expansion. The coil showed good coupling, and preparations are being made to feed the crucible with evaporator concentrate and to determine the capacity for producing glass.

KRYPTON ADSORPTION

The study of the low-temperature adsorption of krypton on solid adsorbents from a dilute mixture with an inert carrier gas was brought to a close. The capacities of four adsorbents, silica gel, Linde Molecular Sieves 5A and 13X, and coconut charcoal, were determined over a wide range of temperatures and feed concentrations. Temperatures ranged from -150° to -300°F, and feed concentrations from 1 to 4000 ppm by volume. The effects of mass velocity and of bed length-to-diameter ratios on the breakthrough characteristics of the bed were also determined. Enrichment factors were determined over the entire range of experimental conditions and found to be dependent

Figure 21. Conical platinum crucible, quartz dome, solution feeder, and induction coil.

on temperature only and independent of feed concentration. Factors ranged from 2.5 for silica gel at -150°F to 100 for charcoal at -275°F . A final report has been completed.

Safety Studies

**A. CASTLEMAN, JR., I. TANG, F. HORN, G. LINDAUER,
P. BEZLER, P. HUBBERSTEY, H. MUNKELWITZ,
C. BREWSTER, D. WALES, J. DAVIS**

The primary objective of this continuing research program is to develop a fundamental understanding of the chemical reactions, mechanisms of release, and transport behavior of the fission products and radioactive aerosols emanating from nuclear materials under conditions likely to be encountered in LMFBR accidents. The results of this research work find application in (a) making reactor hazard analyses, (b) designing engineered safety features to be deployed in the event of an accident, and (c) assessing the extent of fission product vaporization and deposition in primary circuits during reactor operation.

The program, which has been oriented toward problems of the safety of sodium-cooled fast reactors during the past several years, comprises four major areas: (1) an investigation of the chemical states and the mechanisms of fission product release from fast reactor fuels, (2) studies of the formation and removal of aerosols containing fuel and coolant, (3) scale-up modeling for extending laboratory data to full-scale reactor systems, and (4) studies of the thermodynamic and transport properties of fission products in sodium systems.

RELEASE OF FISSION PRODUCTS FROM FAST REACTOR FUELS

The specific objectives of the recent studies are to (a) determine the chemical states of fission products released from reactor fuels at high temperatures and (b) measure the thermodynamic properties of the fission-product compounds identified in (a). The information obtained from these studies is essential for predicting the distribution of volatile fission products between the fuel phase and plenum inside a fuel element and their subsequent trans-

port behavior upon rupture of the fuel element in case of an accident.

The construction of a thermochromatograph and the installation of the required instrumentation in the alpha facility were completed during the report period. Although the apparatus was designed primarily for studies of plutonium fuels, test runs with irradiated uranium fuels are being conducted prior to plutonium experiments. Figure 22 shows the deposition profile obtained for fission-product ^{131}I released into a helium stream from a metallic U sample inductively heated to 1260°C . Although the peak temperature of the deposit (320°C) is slightly higher than the reported values of $280^\circ \pm 30^\circ\text{C}$ in our earlier work, the appearance of a single iodine deposit closely resembles those observed previously under similar conditions, indicating effective separation of the iodine compound from other fission products in the thermal gradient tube.

The deposition pattern of ^{131}I released from a UO_2 sample heated to 1825°C in helium is shown in Figure 23. Clearly, the 60°C peak, which has been identified as elemental iodine in our earlier

studies, results from dissociation of the iodine compound deposited at higher temperatures. A ^{132}Te peak is also shown to be present immediately upstream from the ^{131}I deposit (Figure 23).

A Knudsen effusion apparatus, designed for the purpose of determining the molecular weights and thermodynamic properties of fission products and their compounds released from uranium and plutonium fuels, has been constructed and tested during the report period. The apparatus (the schematic of which is shown in Figure 24) consists mainly of a 220-ml quartz effusion cell having a built-in orifice of ≈ 0.002 -in. diam, a thermal gradient tube with one end sealed off to form a sample meltdown region, and associated high vacuum and inert gas purification systems. The effusion cell can be maintained at constant temperatures up to 1000°C .

The unique feature of this apparatus is the combination of the effusion cell with a thermal gradient tube. As was demonstrated in earlier investigations, the function of the thermal gradient tube is to effect separation of various fission products by selective condensation along the tube walls. Thus,

Figure 22. Deposition profile of ^{131}I released from uranium at 1260°C in a helium stream.

Figure 23. Fission products ^{131}I and ^{132}Te released from fused UO_2 at 1825°C in a helium stream.

knowing the deposition behavior of the fission products, the temperature gradient can be maintained in such a manner as to allow only one pre-selected isotope or its compound to be collected in the effusion cell. The rate of effusion through the orifice is continuously measured by monitoring the radioactivity of the isotope remaining in the cell.

The theory of molecular effusion of a gas through an orifice is well established. According to the kinetic theory of gases, the rate of effusion is expressed by the following equation,

$$dn/dt = -\frac{1}{4}\bar{c}a_o\rho \quad (1)$$

where $\bar{c}$ = mean molecular speed = $\sqrt{8RT/\pi M}$, ρ = gas density = n/V , M = molecular weight, n = number of molecules of gas, a_o = orifice area, and V = volume of effusion cell. Substitution and integration leads to

$$\ln n/n_o = -(a_o K/V)(RT/2\pi M)^{1/2},$$

where n_o is the initial number of molecules within the cell and K is the Clausing factor.

A plot of the fraction of material remaining in the cell as a function of time on semilogarithmic coordinates should yield a straight line, and the molecular weight of the effusing gas can be derived from its slope provided that the constant $a_o K/V$ is known. It is general practice to calibrate the cell with a gas of known molecular weight. One convenient choice of the calibration gases is ^{85}Kr , and a number of calibration runs with this gas have been made; a typical plot is shown in Figure 25. Test runs were made at 500° and 700°C with carrier-free ^{131}I , which was prepared by oxidizing Na^{131}I with $\text{K}_2\text{Cr}_2\text{O}_7$ and distilling the free iodine into the effusion cell. A typical plot of the effusion curves is also shown in Figure 25. The slopes of the lines indicate that the effusing species is essentially

Figure 24. Effusion cell for molecular-weight measurements.

Figure 25. Effusion data for ^{85}Kr and ^{131}I at 700°C.

atomic iodine rather than I_2 . Molecular iodine would be expected to dissociate to atomic iodine at high temperatures and low concentrations.

As a prelude to studies with UO_2 and PuO_2 , a number of runs were made with fission-product iodine released from irradiated uranium specimens heated to $1350^\circ C$ *in vacuo*. The released iodine was first collected in the Knudsen cell; the thermal gradient tube containing the U melt was then removed from the effusion cell by sealing off with a torch; and the subsequent effusion experiment was carried out at a preselected temperature. A summary of the results from all experiments is given in Table 9. The apparent molecular weight of the iodine compound was found to vary with the effusion temperature; that is, the higher the temperature, the smaller the value of the observed molecular weight. The temperature dependence of the apparent molecular weight clearly shows that partial dissociation of the iodine compound to atomic iodine is taking place during the effusion experiments.

It seems therefore, that by carrying out the effusion experiment at a low enough temperature, it would be possible to obtain the true molecular weight of the nondissociated iodine compound. Unfortunately, however, the data from several experiments made at temperatures below $550^\circ C$ had to be discarded because excessive adsorption of the iodine compound on the surfaces of the quartz effusion cells interfered with the measurements. The resulting effusion curve was found to be nonlinear with a gradual trailing at the end. Therefore, the evaluation of the slope, which is proportional to the molecular weight of the vaporized species, was rather uncertain. Efforts are being made to overcome these difficulties.

AEROSOLS

The potential formation and transport of radioactive aerosols is of particular concern in the event of a fast reactor accident because of the large plutonium oxide inventory in fast reactor cores and the health hazard associated with plutonium. Likewise, the possibility that the released fission products might be transported on vaporized fuel particles is also of major importance to reactor safety. Consequently, a basic understanding of the behavior of these aerosols in closed vessels is required both in designing the engineering safety features used to mitigate the aerosol hazard and in making decisions related to reactor siting criteria. Long-

Table 9

Apparent Molecular Weight of the Iodine Compound at Different Temperatures	
Effusion temperature, $^\circ C$	Observed molecular weight
550	330
600	262
700	213
850	157
900	148

range experimental and theoretical programs are under way to provide an understanding of the formation, coagulation, and removal of aerosols composed of PuO_2 , UO_2 , and Na in closed vessels.

Experimental

A number of experiments were performed using the resistance ribbon-heater to rapidly vaporize PuO_2 , UO_2 , and PuO_2 -Na directly from the bottom of the aerosol chamber. Airborne particle sampling was accomplished using thermal precipitators, whereas wall and floor samples were obtained with a rotating disk sampler. In the wall and floor samplers, a carbon-coated copper electron microscope grid was exposed to the enclosure atmosphere at periodic intervals for a measured time. Fixed plateout and floor sampling grids were also used to obtain the total mass deposition for each removal mechanism. Experimentally determined aerosol concentrations measured at several elevations have been found to be in excellent agreement, which indicates that good mixing is attained during a run.

A problem which has been under continuing study is that of whether UO_2 aerosols can be used as a simulant for PuO_2 aerosols. The need for an accurate determination of the extent to which the characteristics of PuO_2 and UO_2 aerosols differ led to a more accurate technique for analyzing uranium at low concentrations. The analysis is accomplished by exposing the enriched UO_2 impregnated thermal precipitation grids to a thermalized neutron flux of 3.8×10^{10} n/cm²-sec. A fission fragment counter is used to determine the rate of fissioning, which is directly proportional to the mass of uranium on the grid. This technique permits one to accurately detect $0.0003 \mu g$ of uranium, an improvement of a factor of 150 over the phosphorescence technique used previously.

Although the resistance heater is extremely useful for generating PuO_2 and UO_2 aerosols with weights up to the order of a gram, the times required to generate larger quantities of these aerosols becomes prohibitive with this technique. Since there is a strong desire to study the characteristics of multigram PuO_2 and UO_2 aerosols, a 20-kW, 530-kc induction furnace was installed in the alpha facility and is being used to generate multigram UO_2 and PuO_2 aerosols at temperatures in excess of 3000°C . The aerosol is generated by inducing current in a tantalum carbide crucible which holds the fuel material to be vaporized. Vaporization occurs directly within a 1-m^3 chamber.

Analytical Studies

Analytical studies were performed to determine the time dependence of the physical behavior of an aerosol. The general integro-differential aerosol equation includes terms for thermal, gravitational and turbulent coagulation, wall plating, gravitational settling, and a source; it was solved using a CDC 6600 computer.

The method of solution involves the computation of the entire particle size spectrum as a function of time using a numerical procedure. The initial spectrum was assumed to be of the log-normal form

$$N(r,0)dr = \frac{N(0)}{\ln \sigma (2\pi)^{1/2}} \left[\exp \left(\frac{-\ln^2(r/r_g)}{2 \ln^2 \sigma} \right) \right] d \ln r, (2)$$

Figure 26. Variation of concentration with time for instantaneous source model.

where

$$N(t) = \int_0^\infty n(r,t)dr,$$

r_g is the geometric mean radius of the distribution, and σ is its standard deviation. The code calculates total number of particles per unit volume of space, percentage of particles remaining airborne, total airborne mass per unit volume of space, fraction of mass remaining airborne, total particle surface area per unit volume of space, and the statistically evaluated mean size and standard deviation of the distribution. In order to reduce the number of computer problems, the basic equations were nondimensionalized.

Parametric Study

Calculations were made to study the effect of initial aerosol mass concentration and settling height on the time dependence of the fractional mass concentration remaining airborne. The initial particle size distribution for these parametric studies was determined from Eq. (3).

$$C_0 = \frac{4}{3} \pi \rho N(t) r_g^3 \exp(4.5 \ln^2 \sigma), (3)$$

where C_0 is the weight of aerosol per unit volume of space. Equation (3) follows directly from the assumption of a log-normal distribution. Preliminary calculations showed that a log-normal distribution with a σ of 1.4 results from the rapid coagulation of high number density aerosols and therefore this value was used in Eq. (3).

The effect of initial concentration on the time dependence of the fractional mass concentration remaining airborne is shown in Figure 26 for initial concentrations ranging from 0.01 to 100 g/m^3 , a settling chamber height of 100 cm, and a particle density of 6 g/cc . As expected, the higher the mass concentration and corresponding initial radii, the more rapid the decrease in the fraction of the mass remaining airborne.

These results show that for simultaneous coagulation and settling, the geometric mean particle radius increases with time, approaches a maximum, and then decreases to a nearly constant value. The time dependence of the geometric mean particle radius is plotted in Figure 27 for each case considered.

Computations were also made to study the effect of vessel height on the rate of aerosol deposition. Figure 28 shows the fraction of aerosol mass re-

Figure 27. Variation of geometric mean radius with time for instantaneous source model.

maintaining airborne as a function of time for an aerosol of 10.0 g/m^3 initial concentration in vessels of various heights. Although increasing vessel height results in an increase in time for a given fraction of mass concentration to settle, the effect of height is less in the case of simultaneous coagulation and settling than for the case of Stokes settling only.

Comparison of Experiment With Theory

In order to compare theory with experiment, values of the initial concentration, particle size distribution, and vessel height are required. The initial size distributions obtained in our experiments were found to be log-normal and therefore they can be represented by two parameters, r_g and σ . Table 10 gives the initial parameters of the PuO_2 and UO_2 experiments for which values of the initial concentration and particle size distribution were obtained and in which the aerosols were vaporized directly into the settling chamber.

The reduction in aerosol concentration with time for the PuO_2 and UO_2 runs is plotted in Figures 29 and 30. The ordinate of the figures is the fraction of aerosol remaining in the enclosure and it was obtained by normalizing the experimental and theoretical concentrations to the initial value.

Figure 28. Effect of vessel height on aerosol concentrations for instantaneous source model.

The value of the initial concentration was obtained from a best-fit line drawn through the experimental points. Calculations for PuO_2 and UO_2 aerosols assumed an initial σ of 1.9 and an effective aerosol density of 6.0 g/cc . The mechanisms of Brownian coagulation, sedimentation coagulation, turbulent agglomeration, settling, and wall plating were included in the calculations.

Although the aerosol vaporization was generally quite rapid, the experimental conditions did not fulfill the requirements for an instantaneous source, and therefore Eq. (3) was not used to evaluate $r_g(0)$. Instead, experimentally measured r_g values obtained 3 to 5 min after cessation of vaporization were used. A σ of 1.9 represents an average of the values obtained in all of our experiments.

Referring to Figure 29, it can be seen that the calculated results are in very good agreement with the experimentally obtained concentrations. Also note that for PuO_2 -a and PuO_2 -b the initial experimental parameters given in Table 10, as well as the experimentally obtained variations of concentration with time, are very similar. This leads one to conclude that the aerosols are behaving in a reproducible manner.

A comparison of theory and experiment for the UO_2 runs (Figure 30) shows that the agreement is not as good as for PuO_2 . UO_2 -a and UO_2 -b had similar initial conditions but behaved somewhat differently experimentally. This may reflect the in-

Table 10
Initial Parameters for PuO₂ and UO₂ Experiments

Material	Experiment	$C_0(\text{calc})$, g/cm ³	$C_0(\text{meas})$, g/cm ³	r_g, μ	σ	h , cm	Atmo- sphere
PuO ₂	a	0.067	0.016	0.064	1.97	100	N ₂ +3% Ar
	b	0.067	0.013	0.057	2.01	100	N ₂ +3% Ar
	c	0.375	0.071	0.103	1.57	100	N ₂ +3% Ar
UO ₂	a	0.065	0.0105	0.074	1.50	100	N ₂ +3% Ar
	b	0.041	0.0143	0.074	2.09	100	N ₂
	c	0.303	0.051	0.110	1.81	100	N ₂

Figure 29. PuO₂ aerosols.

ability to analyze small concentrations of UO₂ as accurately as similar concentrations of PuO₂. It can be noted that the transient concentration curves predicted for these two cases are quite similar; however, the UO₂-b experimental points generally fall above whereas the UO₂-a experimental points generally fall below the predicted curves. Run UO₂-c had the highest initial concentration and the analysis of the concentration values for this run is probably better than that of UO₂-a and UO₂-b. For early times, the theoretical curve lies slightly below the experimental data, whereas at later times, the reverse is true.

Figure 30. Variation of concentration with time for UO₂ aerosols.

Because of the complexity of carrying out aerosol experiments with these materials, the agreement between the calculated results and the experimental data should be considered quite good.

SCALE-UP MODELING AND TESTS - PROGRAM COORDINATION TASK

Recently, work commenced on a new phase of the program dealing with analytical methods of scale-up, modeling, and tests, and the coordination of large-scale LMFBR aerosol safety work. Briefly,

this will include a recommendation of required future aerosol experiments, an evaluation of the need for large-scale tests, an evaluation of the type and minimum number of tests (including a consideration of the potential usefulness of large-scale test facilities existing at other laboratories), and a consideration of the need to develop and test safety systems which would limit the overall consequence of an accident. In the future, it is expected that this will include participation in planning the tests and evaluation of the results.

Initially, our effort in this area will involve a study of engineering scale-up methods together with a detailed examination of existing large-scale aerosol facilities where suitable scale-up tests might be conducted. Currently, information is being assembled on each of the existing containment test facilities and on the range of experimental conditions which can be studied in the respective vessels.

SODIUM STUDIES

Another phase of the program is under way to provide information on the behavior of fission products in sodium systems. This work is required to assess the distribution of fission products between the circulating coolant, reactor surfaces, and cold traps subsequent to either their intentional or accidental release to the primary system. Thermodynamic data also lead to a knowledge of the maximum extent to which a fission product can vaporize from the coolant in an accident, while transport data are useful in assessing the rate processes.

Because of its relative high volatility and high yield, as well as the long half-life of the 137 isotope, the behavior of fission product cesium is of particular concern. Additional Knudsen cell vaporization experiments were done to determine the thermodynamic properties of the cesium-sodium system at low temperatures and dilute cesium concentrations. A pulsed vaporization apparatus was constructed to enable the measurements to be extended to higher temperatures with correspondingly higher vapor pressures. The principle of operation of the pulsed vaporization apparatus is similar to that of the Rayleigh cell employed in making the NaI-Na measurements [see BNL 50023 (S-69)], but here periodic evacuation and pressurization of the system is employed to ensure that thermodynamic equilibrium is attained between the perturbation cycles. Preliminary experiments have been made with the cesium-sodium system.

Among the alkaline earth elements, strontium is the most important. Roberts (Ph.D. Thesis, Syracuse University, Syracuse, N.Y., 1964) reported a complex phase diagram showing several solid phases in equilibrium with different liquid compositions and pure strontium. In contrast, the diagram reported by Elliott (*Constitution of Binary Alloys, First Supplement*, p. 651, McGraw-Hill, New York, 1965) indicates the system to be a simple eutectic. No heat of mixing values have been reported for this system, and the assumption of a regular solution was required to obtain theoretical estimates of excess free energy of mixing values, ΔF^E , from the phase diagram. However, the ΔF^E values deduced from Roberts' phase diagram did not show a regular trend with compositions read along the liquidus curve, indicating that the excess entropy of mixing, ΔS^E , is not equal to 0. Since a regular solution assumption was required, we used the phase diagram reported by Elliott (*loc. cit.*) to obtain a rough estimate of the ΔF^E for strontium at infinite dilution (2885 cal/mole).

Clearly, further experimental work is needed to obtain accurate thermodynamic values for this system, and experiments are currently being planned to measure the thermodynamic properties of the Sr-SrO-Na and Ba-BaO-Na systems. As a preliminary step in determining the activity coefficient of strontium oxide in sodium, some solubility experiments were made. The results show that the solubility of strontium oxide in sodium ranges from approximately one to three parts per thousand over the temperature range 250° to 550°C.

Although the chemical states of the other fission products are relatively well established, the states of Sr and Ba in solution are less certain. At high fission product concentrations, Sr and Ba are probably elemental. However, at very low concentrations, the elements may react with the dissolved oxygen present in reactor grade sodium. Since the nature of even the oxygen species dissolved in sodium is not completely known, their interactions with the alkaline earth metals in solution are even less certain.

A theoretical study was undertaken to develop an equation for calculating the diffusivities of fission products in liquid sodium needed in making transport calculations. This work led to the development of a useful equation, which resulted from an extension of the Kirkwood approach to diffusion in liquids [D.M. HIMMELBLAU, *Chem. Rev.* **64**, 527 (1964)].

Table 11
Calculation and Experimental Self-Diffusion Coefficients of Liquids

System	$T_m, ^\circ\text{K}$	ϵ/k	$\sigma, \text{\AA}$	M	$^a D_{\text{calc}} \times 10^5$	$^b D_{\text{exp}} \times 10^5$
In	429.32	2500	3.14	114.76	1.7	1.7
Sn	505	2650	3.16	118.70	2.1	2.1
Zn	692.7	4700	2.74	65.38	2.2	2.0
Pb	600.6	2800	3.50	207.21	2.1	2.2
Cu	1356	6600	2.56	63.54	4.0	4.0
K	336.4	1760	4.46	39.10	4.1	3.9
			4.76		4.4	3.9
Na	370.97	1970	3.72	22.991	4.6	4.1 $\begin{pmatrix} 4.2 \\ 4.4 \end{pmatrix}$
			3.84		4.8	4.1 $\begin{pmatrix} 4.2 \\ 4.4 \end{pmatrix}$
Li	453.70	2350	3.04	6.940	7.9	6.5 $\begin{pmatrix} 6.4 \\ 7.2 \end{pmatrix}$
			3.14		8.2	6.5 $\begin{pmatrix} 6.4 \\ 7.2 \end{pmatrix}$
Hg	234.29	1250	3.10	200.61	1.0	1.0
Ag	1234.0	6400	2.88	107.88	3.1	2.6 $\begin{pmatrix} 1.9 \\ 3.1 \end{pmatrix}$
Ga	303	1575	2.66	69.72	1.8	1.7
Ar	83.78	124	3.42	39.944	2.2	2.0

^aWhere there is a discrepancy in the Goldschmidt radii, a D is calculated for both.

^bValues in () indicate confidence limits for reported data.

Note: All diffusivity data except for Ar are taken from A. Suddaby and P. Gray, *Proc. Phys. Soc. London* 75, 109 (1960) and rounded off to one decimal place. Ar data are taken from J.A. Palyvos and H.T. Davis, *J. Phys. Chem.* 71, 440 (1967). (The latter authors reviewed the existing Ar data and chose those considered to be most reliable.)

Table 12

Diffusion in Liquid Silver (1273°K)

(Comparison of experimental^a and predicted values.)

System	$\sigma_{ij}, \text{\AA}$	$T_m, ^\circ\text{K}$	ϵ_{ij}/k	$D_{\text{calc}} \times 10^5$	$D_{\text{exp}} \times 10^5$
Ag-Ag	2.88	1234	6400	3.2	$\begin{pmatrix} 2.8 \\ 3.5 \end{pmatrix}$
Ru-Ag	2.77	(2700)	9480	2.7	2.6
Co-Ag	2.60	1768	7820	2.7	2.7
Au-Ag	2.88	1336	6570	3.2	2.6
In-Ag	3.06	430	3780	4.0	4.0
Sn-Ag	3.02	505	4120	3.9	4.1
Sb-Ag	2.89	904	5485	3.4	$\begin{pmatrix} 2.8 \\ 4.3 \end{pmatrix}$

^aV.P. Gupta, *Acta Met.* 14, 297 (1966); V.P. Gupta, Solute diffusion in liquid metals, in *The Properties of Liquid Metals*, p. 333, P.D. Adams, H.A. Davies, and S.G. Epstein, Editors, Taylor and Francis, Ltd., London, 1967.

Table 13

Comparison Between Experimental and Predicted Diffusion Coefficients in Liquid Lead, 601°K

System	$\sigma_{ij}, \text{\AA}$	ϵ_{ij}/k	T_s	$D_{\text{calc}} \times 10^5$	$^a D_{\text{exp}} \times 10^5$
Pb-Pb	3.50	2800	1.0	2.1	2.2
Ag-Pb	3.19	4230	0.698	1.6	1.6, 2.2
Bi-Pb	3.22	(2810)	1.050	1.9	$\begin{pmatrix} 1.9 \\ 3.2 \end{pmatrix}$
Cd-Pb	3.27	3040	1.006	1.8	2.0, 1.4
Sb-Pb	3.07	3620	0.815	1.7	1.2, 2.8
Sn-Pb	3.33	2730	1.091	1.9	1.5, 0.9, 3.0
Zn-Pb	3.12	3620	0.931	1.5	$\begin{pmatrix} 1.5 \\ 2.3 \end{pmatrix}$

^aTwo or more values represent diffusivities taken from more than one investigator. Values in parentheses represent limits reported by one investigator. Data taken from M. Born and H.S. Green, *A General Kinetic Theory of Liquids*, Cambridge Univ. Press, 1949; G.I. Onoprienko, P.P. Kuz'menko, and E.I. Khar'kov, *Ukr. Fiz. Zh.* 12, 39 (1967).

$$D = \frac{0.655 T^{3/2} \sigma_{ij}}{M^{1/2} [(\epsilon_{ij}/k) \times 10^{-3}] \bar{\epsilon}},$$

where

$$\bar{\epsilon} = [-(\sigma_{ij}/R_{ij})^7 + 2(\sigma_{ij}/R_{ij})^{13}] | \bar{v}, R_{ij} = R_{ab},$$

$\bar{v}$ denotes thermal averaging, R_{ij} is the intermolecular distance for the molecular pair ij , ab represents the distance of closest approach where the kinetic energy equals the potential energy, σ_{ij} is the intermolecular distance where the effective potential well-depth is zero, and ϵ_{ij} is the effective Lennard-Jones potential well-depth. The agreement between the theoretical and calculated values for a number of systems is very good as seen in Tables 11, 12, and 13.

Engineering Assistance Group

The Engineering Assistance Group consists of twenty persons involved in engineering, design, and construction of experimental apparatus in support of departmental programs. The following are cited as representative of the project work.

A prototype machine was built for the Experimental Physics Group to produce delayed neutrons. This device utilizes a 90-ft-long endless steel tape, at speeds from 0.003 to 180 ft/sec. The design of a low geometry counter was also completed.

Design and fabrication of various devices for measuring nuclear materials have been developed along with security seals for the Nuclear Materials Group.

Our effort in the Atmospheric Sulfur Pollution Program, in cooperation with the Analytical Chemistry Group, was directed toward the development and field testing of equipment for sampling flue gases for sulfur compounds. The sampling train proved to be effective as a sulfur dioxide sampler and was subsequently tested at the Long Island Lighting Co.'s (LILCO) Northport power station. The more highly oxidized compounds (SO_3 , H_2SO_4 , and sulfates) are also of importance. These compounds are frequently in particulate form; therefore, isokinetic sampling methods must be employed and such a sampling train is ready for field testing.

Techniques were developed to inject sulfur hexafluoride (SF_6) into power plant flue gases. Typically the SF_6 is injected into the flue gas before the particulate removal system while simulta-

neously sampling the plume. One such test has been performed at the LILCO Northport power station.

Modifications to the cooling systems of both the Medical Research Reactor (MRR) and the High Flux Beam Research Reactor (HFBR) were engineered during the report period.

Preliminary design calculations and drawings have been made in support of a proposal for an irradiation facility which would utilize a beam from the 200-MeV linear accelerator. The design is based on the use of water-cooled targets immersed in a water-filled shielding tank.

As part of an investigation to measure the epithermal capture-to-fission ratio (α) of ^{239}Pu , a capsule was designed for HFBR irradiation. A foil of ^{235}U - ^{235}Pu , shielded by a B_4C -Al cylinder enriched in ^{10}B , was exposed in the reactor for one cycle; analysis is under way.

The final servicing of the research irradiators at the Universities of California, Washington, and Florida and at MIT was completed this period. This is the final stage of a two-year AEC program. Two more irradiator shipping frames were designed. These crash shields are for the bulk grain irradiator and the mobile gamma irradiator casks. Two more Brookhaven portable cesium development irradiators (Nos. 2 and 3) were completed and have been received at BNL. Two new irradiators were delivered to the BNL Medical Department, one capable of treating the blood from eight animals simultaneously, the other for whole-body exposure of rodents.

A portable ozone generator was designed, fabricated, and calibrated. The unit consists of a lead-shielded stainless steel reaction vessel, a $\frac{1}{2}$ Ci ^{90}Sr needle source, a flow controller, filters, and a rupture disk assembly.

Process controllers, programmers, test devices, etc., were designed and built for a wet/dry corrosion study, a remote-controlled mechanical arm, a cesium irradiator, a gamma monochromator, and a radiation exposure controller for a cell complex.

Modification of the heat transfer facilities continued throughout the reporting period. Three rod bundles for the mercury loop and one for the sodium loop are among the six new test sections being designed. The pitch-to-diameter ratios for these rod bundles vary from 1.1 to 1.5. The remaining test sections are for the boiling potassium facility and will be used to investigate boiling inception.

Equipment assembly and initial calibration tests were performed for the High Cycle Fatigue Test Program. This program is concerned with the determination of the fatigue properties of LMFBFR construction materials. Ultrasonic test equipment operating at a stress cycle frequency of 20,000 cps is used for accelerated testing to obtain data in the 10^8 to 10^{10} cycle range. A conventional push-pull machine is used for testing at lower frequencies in order to evaluate the effect of test frequency on the fatigue life. Equipment has been designed for both test machines to permit tests in a sodium environment.

A continuing engineering effort is involved in the review of standards for the Division of Reactor Development and Technology. During this reporting period, twenty-one separate standards were reviewed.

As a result of the increasing importance of Quality Assurance Programs in AEC work, the Engineering Assistance Group has taken the lead in preparing suggested guidelines useful not only in the Department of Applied Science, but possibly for the entire Laboratory.

Pulsed Research Reactor Study

J. HENDRIE, K. HOFFMAN, H. KOUTS, P. LEDOUX,

R. PARSICK, J. PHELPS, G. PRICE, M. REICH,

H. TAKAHASHI, H. WINDSOR

Reference design studies were completed for the two alternative pulsed reactor concepts that are being considered as high-intensity sources for neutron beam experiments. The pulsed reactor system was designated as reference design B1 and the accelerator-injected pulsed reactor was designated reference design B2. The primary purpose of these designs is to establish a basis for the evaluation of the alternative concepts as neutron sources for various beam-type experiments. The results of the fuel material survey and of the tests that were performed on unirradiated specimens of several candidate materials were evaluated. This evaluation led to the selection of fuels for the current reference design studies and to the identification of other fuels that are promising alternatives but require additional test and development before they can be considered for pulsed reactor application. A series of beam source and critical experiments culminating in a core that characterizes the major features of the reference design B1 concept have

been completed. This series of experiments included measurements of the thermal neutron yield from a moderator block placed adjacent to the core but decoupled from the core by an intermediate layer of poison material.

PULSED REACTOR

The reference design B1 core is 60 liters in volume, sodium-cooled, and fueled with a 60 vol % $\text{PuO}_2\text{-Mo}$ cermet. The reactor operates at an average power of 30 MW and the design repetition rate is 50 pulses/sec. The peak power in the burst is 4500 MW and the burst width at half-power is 115 μsec . The design characteristics of the system are summarized in Table 14. The thermal neutron yield from the moderator has been estimated from measurements made with the critical assembly. With a 5.3-cm-thick water moderator, the estimated peak thermal source flux is about 1.9×10^{16} n/cm²-sec and the pulse width is 134 μsec .

During a power burst the fuel increases in temperature by $\approx 23^\circ\text{F}$. The transient temperature profile was calculated for the axial peak of the core hot pin with the use of the three-dimensional heat transfer code LION. The temperature profiles shown in Figure 31 are at the beginning of the power

Table 14

Design Characteristics of Alternative Pulsed Reactor Concepts

	Pulsed reactor (B1)	Accelerator-injected pulsed reactor (B2)
Fuel material	60 vol % $\text{PuO}_2\text{-Mo}$	U-10 Mo
Average power, MW	30	7.2
Core volume, liters	60	30
Neutron lifetime, nsec	60	35
Reactivity swing in reflector block, β	21.00	7.50
Repetition rate, cps	50	150
Peak power, MW	4500	4000
Burst width, μsec	115	8
Thermal source flux, n/cm ² -sec	1.9×10^{16}	3×10^{15}
Thermal neutron pulse width, μsec	134	30

pulse and at times 258 and 5118 μsec later. The temperature at this location rises at a maximum rate of $228,000^\circ\text{F}/\text{sec}$ and at an average rate of $92,000^\circ\text{F}/\text{sec}$ during a pulse. This rapid temperature increase results in inertial stresses of a vibratory nature in the fuel because of its inability to expand in equilibrium with the temperature input. Preliminary analysis of these stresses for reference design B1 indicates that they are within the allowable limits that have been determined based on previous fatigue tests with a similar cermet fuel.

The core region layout is shown in Figure 32. The sodium-cooled core is contained within the core vessel along with the poison liner that decouples the core from the moderator. The control rods, beam source moderator blocks, and radial reflector region are outside the core vessel in a nitrogen-cooled zone. Provision is made for periodic replacement of the core vessel, since it will be subjected to irradiation damage due to its proximity to the core edge. The primary reflector pulse block that provides reactivity variation is carried on a rotor spinning at 3000 rpm. The secondary rotor carries a smaller portion of the reactivity effect and can be varied in speed to alter the repetition rate in the system. Both blocks must line up with the core simultaneously to produce the super-

prompt critical condition required for a power burst. A shield zone and primary system layout have also been completed for this concept.

ACCELERATOR-INJECTED PULSED REACTOR

The accelerator-injected pulsed reactor is of interest as an alternative to the pulsed reactor concept because of its capability of achieving short power burst widths. The physics analysis was completed for a core fueled with U-10 Mo alloy. The core volume is 30 liters, including a 5-liter target region. The performance of this system is limited by the capability of the accelerator and target region rather than by strength considerations in the fuel. The electron accelerator that has been selected for reference design B2 is a large standing wave linac of the Phermex class. Studies of the Phermex facility indicate that it could be scaled up to produce a 33-A peak current beam of 30-MeV electrons for a pulse duration of 3 μsec . The required repetition rate of 150 pulses/sec can be obtained with this facility. The target region for an accelerator of this type involves a major development effort. Driven by an electron accelerator with these operating parameters, the reactor core would develop a peak power of about 4000 MW with a burst width of 8 μsec . The average power level would be 7.2 MW. The complete design characteristics are summarized in Table 14 along with those of the pulsed reactor. With a 2.5-cm-thick water moderator, the peak thermal source flux in the moderator is 3×10^{15} n/cm²-sec and the pulse width is about 30 μsec .

FUEL TEST AND DEVELOPMENT PROGRAM

The evaluation of the results of the first phase of the fuel development program was completed. The fuels that were considered for application to both the pulsed reactor and the accelerator-injected pulsed reactor are tabulated in Table 15. The materials that have been selected for possible application to either concept are indicated in the appropriate column of the table. Where indicated by the footnote, the fuel is of interest only with the ²³³U isotope but the difficulty of assuring an adequate supply of this material makes its use undesirable. Thus the U-Nb-Zr ternary alloys are not suitable for the pulsed fast reactor, since the only gamma phase stable ductile composition, U-27 Zr-20 Nb, had too low a fissile material content.

Figure 31. Reference design B1. Transient temperature profile at the axial peak of the hot pin.

Figure 32. Pulsed reactor core region layout.

Table 15
Summary of Fuel Survey

Fuel	U or Pu loading, g/cc	Application		Comments
		Pulsed reactor	Accelerator injected pulsed reactor	
Alloys:				
U-40 Al	3.5			Too dilute.
U-10 Mo	15		X	
U-10 Nb	15			Inferior to U-10 Mo.
U-40 Zr	6	X ^a		
U-20 Nb-27 Zr	5.7	X ^a		
U-Pu	—	X		
Ceramics:				
UO ₂	9.2	X		
UC		X		
PuO ₂	9.6		X	
PuC			X	
Cermets and dispersions:				
60 vol % PuO ₂ -Mo	5.8	X		
60 vol % UO ₂ -Mo	5.5	X ^a		
60 vol % Pu or UO ₂ -SS				SS matrix inferior to Mo.
Liquid:				
PuO ₂ (or UO ₂)-Na paste		X	X	
Pu-Fe-Ce		X		

^aOf interest primarily with ²³³U isotope.

Similarly, the only U-Th dispersion that was successfully fabricated is unsuitable, as is the 60 vol % UO₂-Mo cermet.

The balance of the materials in Table 15 that are indicated to be of interest for either system fall into two general categories: the cermets and alloys (which possess sufficient strength to contribute substantially to the overall fuel pin integrity) and the ceramic and liquid fuels (which must be fully supported by the fuel pin claddings). The liquid and paste fuels have been eliminated as candidates at their present level of development. The steady-state irradiation behavior of the ceramic fuels, oxides, and carbides is sufficiently well known. The effects of pulse heating on these materials are not known and there is no existing basis for treating the problem analytically. Thus, ceramic fuels have not been considered for reference designs B1 and B2 except as alternative possibilities. However, in view of the technology that has developed around ceramic fuels and their economic advantages, it was decided to study techniques for simulating the

behavior of ceramic fuels under pulsed reactor conditions.

The PuO₂-Mo cermet fuel was selected for reference design B1 because it represents the only plutonium-base solid fuel that promises to maintain its structural integrity to a high burnup condition without excessive swelling. The use of plutonium with its low delayed neutron fraction also minimizes the background power between pulses, a factor of importance in time-of-flight experiments. The high cycle fatigue properties of this material were measured under an unirradiated condition with depleted uranium substituted for plutonium, and these measurements, which have been reported previously, were used as the basis for the core design. The measured properties, with a suitable correction applied to account for the effects of irradiation, are felt to provide a good estimate of the performance capability of this fuel.

The U-10 Mo alloy fuel was selected for reference design B2 because it represents a structurally integral fuel that will satisfy the lower core volume

Figure 34. Relative sub-Cd yields vs thickness of 10×10.5 -in. moderating blocks in the cryostat at room temperature.

indicated that the yields in thin blocks (up to 2 in. thick) were proportional to their density and presumably to the hydrogen density. The use of Cd or boron to isolate the moderator blocks from the surrounding stainless steel reflector moderately reduced the yield, the boron more so than the Cd. The moderator block decay times were also reduced, but to a considerably lesser degree. Introduction of additional stainless steel between the B_4C liner and the moderator blocks only nominally reduced the yield, the reduction being about 14% using a 1.9-in.-thick polymethyl methacrylate block with 1.5 in. of additional stainless steel. Additional B_4C reduced the yields more sharply, the reduction being about 33% for an additional 1.5 in. of B_4C . The cold (77°K) moderator block sub-Cd neutron yields were comparable to those measured for room temperature moderating blocks. Using a 1.91-in.-thick $\times$ 17-in.-wide $\times$ 14.8-in.-high polymethyl methacrylate block, the leakage flux at the center of the outer surface was 1.7×10^6 sub-Cd neutrons/cm²-sec-watt (Figure 34). The thermal source flux measured internally in the moderator block was a factor of 6.4 higher than the leakage flux measured at the surface.

The cores in the CEPFR-1-2 series were increased in size to approximate the size of the

pulsed reactor core. There was no Pu fuel available so enriched U was used again in this experiment. The nominal core compositions were:

Material	Volume fraction
Enriched uranium	0.18
Aluminum	0.14
Stainless steel	0.49
Void	0.19

With 214.0 kg of 93% enriched U loaded in the core of a typical assembly, the measured excess reactivity was \$0.11. This was a 63.6-liter core, almost double the size of the cores in the CEPFR-1F series.

The characteristics of the movable reflector block and the core lifetime suffered under comparison of the CEPFR-1-2 series with other series. The lifetime increased from about 57 nsec in CEPFR-1F to about 87 nsec, both measurements being done with a steel movable reflector. The α_p for a steel block decreased from about 2 to about 0.9 cents/cm².

With the same moderating block used for absolute flux measurements in CEPFR-1F, the leakage flux in CEPFR-1-2 was found to be 0.92×10^6 sub-Cd neutrons/cm²-sec-watt. These data emphasize the importance, from a physics point of view, of keeping the core small and the leakage high.

Publications

- CASTLEMAN, A.W. JR. Fission product release at Brookhaven National Laboratory. VIII. *Nucl. Safety* 10, No. 2, 182-3 (1969); IX. *Ibid.* 10, No. 4, 351-2 (1969).
- CASTLEMAN, A.W. JR. AND CONTI, J.J. A consideration of the mass effect on diffusion in the liquid state. Submitted to *Phys. Rev.*
- CASTLEMAN, A.W. JR. AND CONTI, J.J. An extension of the Kirkwood equation to diffusion in liquid-metal systems. Submitted to *J. Chem. Phys.*
- CASTLEMAN, A.W. JR., HORN, F.L., AND LINDAUER, G.C. On the behavior of aerosols under fast reactor accident conditions. (A) In *Proc. Int. Congr. Diffusion of Fission Products, Saclay, France, Nov. 1969* (in press).
- CASTLEMAN, A.W. JR. AND TANG, I.N. Fission product vaporization from sodium systems. In *Proc. Int. Conf. Sodium Technology and Large Fast Reactor Design, Argonne, Ill., Nov. 1968*, ANL-7520.I, pp. 540-8.
- CASTLEMAN, A.W. JR. AND TANG, I.N. Vaporization of fission products from irradiated uranium. II. Some observations on the chemical behavior of fission products iodine and cesium. *J. Inorg. Nucl. Chem.* (in press).
- CHEN, J.C. Effect of turbulent flows on incipient boiling superheat. In *Summaries of Presentations From First Meeting of Technical Working Group on Liquid Metal Thermal Science, Brookhaven National Laboratory, Upton, New York, May 1969*.

- CHEN, J.C. Void propagation studies. *Ibid.*
- CHEN, J.C. AND KALISH, S. An experimental investigation of two-phase pressure drop for potassium with and without net vaporization. (A) To be presented at 4th Int. Heat Transfer Conference, Paris, Aug. 31–Sept. 5, 1970.
- CHEN, J.C. AND KALISH, S. Liquid-metal two-phase pressure drop with and without net vaporization. In *Summaries of Presentations From First Meeting of Technical Working Group on Liquid Metal Thermal Science, Brookhaven National Laboratory, Upton, New York, May 1969.*
- CHEN, J.C., KALISH, S., AND SCHOENER, G.A. Probe for detection of voids in liquid metals. *Rev. Sci. Instr.* **39**, 1710-13 (1968).
- CHEN, J.C. AND YU, W.S. Entrance region and variable heat flux effects in turbulent heat transfer to liquid metals flowing in concentric annuli. Presented at 11th Natl. Heat Transfer Conf., Minneapolis, Minn., Aug. 1969; *Int. J. Heat Mass Transfer* (in press).
- DRAGER, R.F., JOHNSON, R., AND HATCH, L.P. *Decontamination of Melter Off-Gas Condensates From the Phosphate Glass Process by Distillation.* BNL 50184 (T-539) (in press).
- DWYER, O.E. Heat transfer to liquid metals flowing in-line through unbaffled rod bundles: A review. In *Heat Transfer in Rod Bundles*, pp. 139-68, ASME, New York, 1968; *Nucl. Eng. Des.* **10**, No. 1, 3-20 (1969).
- DWYER, O.E. Heat transfer to liquid metals flowing through closely spaced rod bundles. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 30–Dec. 4, 1969.
- DWYER, O.E., HLAVAC, P.J., AND HELFANT, M.A. Heat transfer to mercury flowing in-line through an unbaffled rod bundle: Effect of rod displacement on local surface temperature and heat flux. (A) To be presented at 4th Int. Heat Transfer Conference, Paris, Aug. 31–Sept. 5, 1970; *Nucl. Sci. Eng.* (in press).
- DWYER, O.E. Liquid metal boiling working group. (L) In *Liquid Metal Boiling Working Group Progress Letters*, 3rd issue, pp. 37-9, May 1969, EURATOM, Ispra, Italy. EUR/C-IS/473/69 e: IP/312/W.
- DWYER, O.E. Liquid metal heat transfer. In *Liquid Metals Handbook, Sodium and NaK Suppl.*, 1969 Ed., Chap. 5 (in press).
- DWYER, O.E. On incipient-boiling wall superheats in liquid metals. *Int. J. Heat Mass Transfer* (in press).
- DWYER, O.E. Prediction of incipient-boiling wall superheats in liquid metals where turbulence effects are negligible. In *Summaries of Presentations From First Meeting of Technical Working Group on Liquid Metal Thermal Science, Brookhaven National Laboratory, Upton, New York, May 1969.*
- DWYER, O.E. Single-phase liquid-metal heat transfer studies at BNL. *Ibid.*
- DWYER, O.E. AND BERRY, H.C. Effects of cladding thickness and thermal conductivity on heat transfer to liquid metals flowing in-line through bundles of closely spaced reactor-fuel rods. *Nucl. Sci. Eng.* (in press).
- DWYER, O.E. AND BERRY, H.C. Slug-flow Nusselt numbers for in-line flow through unbaffled rod bundles. *Ibid.*
- DWYER, O.E. AND STRICKLAND, G. Single- and two-phase heat transfer studies with sodium. In *Summaries of Presentations From First Meeting of Technical Working Group on Liquid Metal Thermal Science, Brookhaven National Laboratory, Upton, New York, May 1969.*
- EMMA, L.C., JOHNSON, R., BARTLETT, C., AND HATCH, L.P. *Disposal of Solid Wastes Generated in Fluidized-Bed Fluoride Volatility Fuel Reprocessing.* BNL 50139 (T-511), Oct. 1968.
- HENDRIE, J.M., HOFFMAN, K.C., KOUTS, H.J.C., PARSICK, R.J., PHELPS, J.P., PRICE, G.A., REICH, M., TAKAHASHI, H., AND WINDSOR, H.H. Brookhaven pulsed fast research reactor. Presented at Amer. Nucl. Soc. Meet., Albuquerque, Jan. 1969.
- HLAVAC, P.J., DWYER, O.E., AND HELFANT, M.A. Heat transfer to mercury flowing in-line through an unbaffled rod bundle: Experimental study of the effect of rod displacement. I. Presented at ASME Annu. Meet., New York, Dec. 2-5, 1968; *J. Heat Transfer* **91**, 568-80 (1969).
- HORN, F.L. AND CASTLEMAN, A.W. JR. $\text{PuO}_2\text{-UO}_2\text{-Na}$ aerosols produced by vaporization of fast reactor core materials. In *Treatment of Airborne Radioactive Wastes (Proc. Symp., New York, Aug. 1968)*, pp. 93-115, IAEA, Vienna, 1968.
- Hsu, C.J. An exact analysis of low Peclet number thermal-entry-region heat transfer in transversely nonuniform velocity fields. *A.I.Ch.E. J.* (in press).
- Hsu, C.J. Theoretical solutions for thermal-entry-region heat transfer in laminar flow through annuli at low Peclet numbers. Submitted to *Int. J. Heat Mass Transfer*.
- Hsu, C.J. AND LINDAUER, G.C. Thermal-entry-region heat transfer in magnetohydrodynamic channel flow subject to axial conduction and the boundary condition of the third kind. (A) To be presented at 4th Int. Heat Transfer Conference, Paris, Aug. 31–Sept. 5, 1970.
- LINDAUER, G.C. *Thermal Conductivity and Viscosity of Helium at Low Temperatures.* BNL 50138 (T-510), Sept. 1968.
- LINDAUER, G.C. AND CASTLEMAN, A.W. JR. On the initial size distribution of high number density aerosols. Presented at Amer. Nucl. Soc. Meet., San Francisco, Nov. 30–Dec. 4, 1969.
- LINDAUER, G.C. AND HSU, C.J. Unsteady forced-convection MHD heat transfer in a parallel plate channel. *AIAA J.* **6**, 1973-9 (1968).
- REICH, M. AND KOPLIK, B. Analysis of multidimensional thermoelastic dynamic response of reactor fuel elements. Informal Report BNL 13311.
- TANG, I.N., CASTLEMAN, A.W. JR., AND MUNKELWITZ, H.R. On the transport of fission-product cesium from sodium. *Advan. Chem. Ser.*, No. 93 (in press).
- TUTHILL, E.J. A new concept for the continuous chromatographic separation of chemical species. Submitted to *J. Chromatogr. Sci.*
- TUTHILL, E.J., STRICKLAND, G., AND WETH, G.G. Platinum for high temperature crucibles used in processing radioactive wastes. *Ind. Eng. Chem. Process Design Develop.* **8**, 36-43 (1969).
- YU, W.S. AND CHEN, J.C. *Turbulent Liquid-Metal Heat Transfer in Concentric Annuli With Axially Varying Heat Flux.* BNL 50183 (T-538) (in press).

4

4

4

4

4

4