BNWL-586

OFFICIAL USE ONLY

Rec'd, Special Projects Br., WU
NOV 15 1967

Library

MASTER

CALCULATED CRITICAL PARAMETERS
FOR FFTF FUEL UNDER MELTDOWN
CONDITIONS

C. L. Brown

SEPTEMBER 1967

AEC RESEARCH &
DEVELOPMENT REPORT

OFFICIAL USE ONLY

BNWL-586

BATTELLE

NORTHWEST

BATTELLE MEMORIAL INSTITUTE

PACIFIC NORTHWEST

3000 STEVENS DRIVE, P. O. BOX 999, RICHLAND, WASHINGTON 99352

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

PACIFIC NORTHWEST LABORATORY

RICHLAND, WASHINGTON

operated by

BATTELLE MEMORIAL INSTITUTE

for the

UNITED STATES ATOMIC ENERGY COMMISSION UNDER CONTRACT AT(45-1)-1830

PRINTED BY/ FOR THE U. S. ATOMIC ENERGY COMMISSION

~~OFFICIAL USE ONLY~~

BNWL- 586

CALCULATED CRITICAL PARAMETERS
FOR FFTF FUEL UNDER MELTDOWN CONDITIONS

By

C. L. Brown

Critical Mass Physics Section
Reactor Physics Department

September, 1967

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Approved by

P. L. Hofmann

PACIFIC NORTHWEST LABORATORY
RICHLAND, WASHINGTON

~~OFFICIAL USE ONLY~~

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

INTRODUCTION	1
SUMMARY	1
DISCUSSION	2
REFERENCES	4

CALCULATED CRITICAL PARAMETERS
FOR FFTF FUEL UNDER MELTDOWN CONDITIONS

C. L. Brown

INTRODUCTION

To provide a basis for evaluating the criticality safety of unmoderated irradiated fuel in operations where meltdown is credible, criticality parameters have been calculated for three FFTF fuels in geometries that typify meltdown conditions. This report presents the results of these calculations.

Irradiated fuel subassemblies removed from the FTR will have a high thermal heat output. To prevent fuel melting, continued cooling will be required during initial storage, transfer and inspection operations. Cooling is to be provided by immersion in sodium, forced air, and immersion in water, depending on the stage of processing.

If cooling were lost and the fuel were to melt, it is likely that the fuel pins would attain a geometry more favorable for criticality. In the normal subassembly, the pins are close-packed (0.03 in. apart) and in a 37 in. long hexagonal column. If melting were to occur, the pins could fuse into a more dense, solid cylindrical column, or "slump" into a nearly hemispherical geometry. In either instance, the fuel would have a lower critical mass than the initial subassembly.

SUMMARY

In FFTF operations involving irradiated fuel, criticality safety evaluations must take into consideration the possibility of fuel meltdown due to accidental loss of cooling. To provide a basis for these evaluations, critical masses have been estimated for unmoderated $\text{PuO}_2\text{-UO}_2$, PuC-UC , and $\text{PuO}_2\text{-SS}$ fuel pins in spherical, cylindrical, and hemispherical geometry. For 30 wt% $\text{PuO}_2\text{-UO}_2$, the critical number

of undamaged subassemblies is 15. Under meltdown conditions, the critical number would be between 7 and 11 subassemblies, depending on the resultant geometry.

DISCUSSION

The fast reactor fuels selected for this study are described in Table I.

TABLE I. Fuel Compositions Used in Meltdown Calculations

	<u>1</u>	<u>2</u>	<u>3</u>
Fuel and Enrichment	30 wt% PuO ₂ -UO ₂	30 wt% PuC-UC	30 wt% PuO ₂ -SS
Fuel OD, in.	0.218	0.218	0.218
Pin OD, in.	0.250	0.250	0.250
Fuel Length, in.	37 in.	37 in.	37 in.
Cladding Thickness, in.	0.016 SS	0.016 SS	0.016 SS
²⁴⁰ Pu, % in Pu	10.0	10.0	10.0
²³⁵ U, % in U	0.22	0.22	0.22
Fuel Density, g/cm ³	10.00	13.60	9.06
Meltdown Density, g/cm ³	9.50	12.23	8.78
 Isotopic Composition			
<u>wt%</u>			
²³⁹ Pu	19.07	21.73	18.68
²⁴⁰ Pu	2.12	2.42	2.07
²³⁵ U	0.35	0.41	--
²³⁸ U	49.05	56.84	--
O	9.48	--	2.78
SS	19.73	15.47	76.47
C	--	3.13	--

Unreflected critical radii were computed for each fuel in spherical geometry using the DTF transport code with eight energy groups.⁽¹⁾ Cross sections were generated by the FCC-IV code using the modified Russian data.⁽²⁾ Critical masses were calculated using the buckling conversion technique, with a bare extrapolation distance of 4.5 cm. These calculations represent the simulated condition of fuel that has melted into a spherical geometry with no neutron reflector around the sphere. The results of the calculations are given in Table II.

TABLE II. Unreflected Critical Masses

<u>Reference Fuel</u>	<u>Calculated Critical Sphere Radius, cm</u>	<u>Spherical Critical Mass, kg Pu</u>	<u>Equivalent No. of 217-Pin Subassemblies</u>
PuO ₂ -UO ₂	25.1	133.3	10.3
PuC-UC	19.2	87.6	-
PuO ₂ -SS	28.6	178.5	15.2

In an actual fuel meltdown situation, however, the resulting arrangement of the fuel would not be spherical; and neutron reflectors would be present. Arrangements more likely to be encountered would be a column of pins fused together; or, in a severe instance, meltdown to nearly hemispherical shape. The sphere represents the most optimum shape for criticality and is, therefore, also of interest in fuel meltdown evaluations. Calculated critical masses for the reflected sphere, cylinder, and hemisphere are presented in Table III. These values were calculated from the unreflected critical radius using a reflected extrapolation length of 7.5 cm.

TABLE III. Reflected Critical Masses

<u>Reference Fuel</u>	<u>Sphere</u>		<u>Cylinder</u>		<u>Hemisphere</u>	
	<u>kg Pu</u>	<u>SA's*</u>	<u>kg Pu</u>	<u>SA's*</u>	<u>kg Pu</u>	<u>SA's*</u>
PuO ₂ -UO ₂	91.0	7.1	139.0	10.7	177.6	13.8
PuC-UC	52.5	-	97.3	-	113.3	-
PuO ₂ -SS	128.1	11.0	177.7	15.1	240.5	20.6

*Subassemblies, assuming 217 pins.

Though these calculations are theoretical, the values should be acceptable for use in FFTF criticality safety evaluations during design stages. Experimental data to further confirm the theoretical method should be available later in the project.

REFERENCES

1. W. W. Little. Unpublished Data. Pacific Northwest Laboratory, Richland, Washington, May 23, 1967. (Personal Communication)
2. W. W. Little, Jr. and R. W. Hardie. FCC-IV, A Revised Version of the FCC Fundamental Mode Fast Reactor Code, BNWL-450. Pacific Northwest Laboratory, Richland, Washington, August, 1967.

DISTRIBUTION28 AEC, Washington

Division of Reactor Development & Technology

M Shaw, Director, RDT

Asst Dir for Nuclear Safety

Analysis & Evaluation Br, RDT:NS

Environmental & Sanitary Engrg

Br, RDT:NS

Research & Development Br, RDT:NS

Asst Dir for Plant Engrg, RDT

Application & Facilities Br, RDT:PE

Components Br, RDT:PE

Instrumentation & Control Br, RDT:PE

Systems Engineering Br, RDT:PE

Asst Dir for Program Analysis, RDT

Asst Dir for Project Mgmt, RDT

Liquid Metals Projects Br, RDT:PM

FFTF Project Manager, RDT:PM (3)

Asst Dir for Reactor Engrg

Control Mechanisms Br, RDT;RE

Core Design Br, RDT;RE

Fuel Fabrication Br, RDT:RE

Fuel Handling Br, RDT:RE

Reactor Vessels Br, RDT:RE

Asst Dir for Reactor Tech

Chemistry & Chemical Separations

Br, RDT:RT (2)

Fuel & Materials Br, RDT:RT

Reactor Physics Br, RDT:RT

Special Technology Br, RDT:RT

1 AEC Idaho Operations Office

CW Bills, Director

3 AEC Richland Operations Office

FFTF Project Office

JH Krema (2)

Engineering & Construction Div (1)

1 San Francisco Operations Office

Director, Reactor Division

4 AEC Site Representatives - PNL

PG Holsted (2)

LR Lucas

AD Toth

DISTRIBUTION, Continued

- 4 AEC Site Representatives
 - Argonne National Laboratory
 - Atomics International
 - Atomic Power Development Associates
 - General Electric Company
- 2 Argonne National Laboratory
 - RA Jaross
 - LMFBR Program Office
- 2 Atomics International
 - LE Glasgow
 - RW Dickinson
- 1 Atomic Power Development Assoc.
 - BVD Farris
- 2 Babcock & Wilcox
 - SH Esleeck
 - TP Farrell
- 2 General Dynamics Corp.
 - D Coburn
- 4 General Electric Co.
 - Dr Karl Cohen (3)
 - Bertram Wolfe
- 1 Idaho Nuclear Corporation
 - DR deBoisblanc
- 1 Stanford University
 - Dr R Sher
- 3 Westinghouse Electric Corp.
 - Dr JCR Kelly
- 121 Battelle-Northwest
 - GE Akre
 - WG Albert
 - ER Astley
 - JM Batch
 - RA Bennett
 - JR Boldt
 - CL Boyd
 - DC Boyd

Battelle Northwest, Continued

CL Brown (10)
WL Bunch
CP Cabell
AC Callen
JR Carrell
WE Cawley
WL Chase
TT Claudson
ED Clayton
PD Cohn
DL Condotta
JH Cox
JM Davidson
FG Dawson
VA DeLiso
DR Doman
GE Driver
RV Dulin
JF Erben
LM Finch
RC Free
EE Garrett
SM Gill
RA Harvey
BR Hayward
JW Helm
RJ Hennig
GM Hesson
PL Hofmann
BM Johnson
HG Johnson
RL Junkins
JH Kinginger
DD Lanning
LA Lawrence
HD Lenkersdorfer
CW Lindenmeier
HE Little
WW Little
CE Love
WB McDonald
MH Meuser
RA Moen
CA Munro
DM Nero
MG Patrick
JA Perry
RE Peterson

DISTRIBUTION, ContinuedBattelle Northwest, Continued

WE Roake
JD Schaffer
FH Shadel
DW Shannon
DE Simpson
CRF Smith
RJ Squires
GH Strong
CD Swanson
JC Tobin
KG Toyoda
M Vogel
DM Walley
JH Westsik
LA Whinery
RD Widrig
NG Wittenbrock
MR Wood
FW Woodfield
FFTF Files (2)