CLOSED ORBIT ANALYSIS

FOR

RHIC

A. G. Ruggiero

(BNL, April 13, 1984)

Closed Orbit Analysis for RHIC

Value $\hat{y}_P(s)$ not exceeded with a probability P

$$\hat{y}_P(s) = \kappa(P) \left[1 + \frac{\sin \pi \nu}{3} \right] \sqrt{\frac{\beta(s)}{\bar{\beta}}} \sqrt{2} \langle y \rangle$$

where for circular vacuum chamber

P	50%	75%	90%	98%
$\kappa(P)$	1.28	1.63	1.95	2.40

The rms value $\langle y \rangle$ of the expected closed orbit deviation

$$\langle y \rangle = \frac{1}{2\sqrt{2} |\sin \pi \nu|} \sqrt{\sum_i m_i \beta_i \bar{\beta} \psi_i^2}$$

Combining

$$\hat{y}_p(s) = K(P) \frac{1 + \frac{\sin \pi \nu}{3}}{2 |\sin \pi \nu|} \sqrt{\sum_i m_i \beta_i \beta(s) \psi_i^2}$$

Take $\nu = 34.4$ and $P = 90\%$

then

$$\hat{y}_p(s) = 1.35 \sqrt{\sum_i m_i \beta_i \beta(s) \psi_i^2}$$

The results are shown in the next table -

It seems that surveying of the quadrupoles is considerably more important than the dipole errors -

	Horizontal		Vertical	
	Quad	Dipole	Quad	Dipole
Source	Displacem.	Field Error	Displacem.	Tilt
ψ_i	$l_i, \kappa_i, \Delta y_i$	$\Delta B/B_i, \theta_{B_i}$	$l_i, \kappa_i, \Delta y_i$	θ_i, θ_{B_i}
θ_{B_i} $\Delta B/B_i$ θ_i m_i β_i $\sqrt{\sum m_i \beta_i \psi_i^2}$		0.03885 $1/4 \times 10^{-3}$ 158 26.4 m $0.000647 \text{ m}^{1/2}$		0.03885 $1/4 \text{ mrad}$ 158 26.4 m $0.000647 \text{ m}^{1/2}$
l_i κ_i Δy_i m_i β_i $\sqrt{\sum m_i \beta_i \psi_i^2}$	1.9 m 0.05 m^{-2} $1/4 \text{ mm}$ 123 $(51.6 + 7.5) \text{ m}$ $0.0020 \text{ m}^{1/2}$		1.9 m 0.05 m^{-2} $1/4 \text{ mm}$ 123 $(51.6 + 7.5) \text{ m}$ $0.0020 \text{ m}^{1/2}$	
$\hat{y}_p / \sqrt{\beta(s)}$ $\beta(s) \text{ in m}$ For $\beta(s) = 51.4 \text{ m}$	2.84 mm <u>2.0 cm</u>		2.84 mm <u>2.0 cm</u>	

Half-Integer Stop Band Width induced by closed orbit and sextupole

The equation is

$$x'' + K(s)x = gx^2$$

neglecting coupling with y-plane

Let

$$x = x_c + z$$

= closed orbit + free oscillation

Then one derives

$$z'' + K(s)z = 2gx_c z$$

The expectation value of the half-integer stopband width is then

$$\Delta\nu = \frac{1}{\pi} \sqrt{\sum_i m_i (\beta_i l_i g_i x_i)^2}$$

We have two families of sextupoles

	SF	SD
m_i	72	72
β_i	51.5 m	7.5 m
$\langle x_i \rangle_{rms}$	15. mm	5.8 mm
$l_i g_i =$ $= \frac{1}{2} \left(\frac{B''}{B\rho} \right)_i l_i$	0.05 m ⁻²	0.10 m ⁻²
$\langle \Delta v_i \rangle_{rms}$	0.10	0.012
$\langle \Delta v \rangle_{rms}$	0.105	

This is too large

Day 1 Operation Mode

1. Closed Orbit Deviations expected to be large (centimeter range)
2. With full sextupoles on the Half-Integer Stopband Width is expected to be quite large (~ 0.1)

(a) Choose β -tunes ~ 34.25
half-way between $\frac{1}{2}$ integer values

(b) Turn Sextupoles completely off/
Natural Chromaticity ~ 50

(c) Use small pencil beams:
proton beams, bunched, moderate intensity
 10^{11} particles/bunch
few bunches are enough
maybe one AGS pulse

$$\Delta p/p = \pm 0.4 \times 10^{-3} \Rightarrow \Delta v = \pm 0.02 \quad \text{O.K. P.}$$

$$\text{emittance} = 0.7 \pi \text{ mm} \cdot \text{mrad} \quad (95\% \text{ of beam})$$

$$(\equiv \pm 6 \text{ mm at } \beta = 51.4 \text{ m}) \quad \text{O.K. V.}$$

28 GeV

- (d) The beam should be able to go around
- Confidence level $\geq 90\%$
- (e) Establish one turn circulation
Read beam position at B.M.
- (f) Establish second turn circulation
Read beam position at B.M.
- (g) Compare B.M. position between first and second turn
Minimize Difference by adjusting Angle and steering at Injection
- (h) When first, second, ..., nth turn identical closed orbit has been established
- (i) Move quadrupoles to reduce closed orbit down to $\pm 2\text{mm}$ peak-to-peak level - Work out strategy!
- (j) Fine adjustment with local steering elements - work out strategy and requirements - - - !