D41E

MAY 27 1963

UNCLASSIFIED

CLASSIFICATION LEVEL
(S, C, OR U)

MASTER

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NAA-SR-MEMO -8017

This document contains 75 pages

This is copy _____ of _____ series _____

Do not remove
this sheet

Facsimile Price \$ 2.60
Microfilm Price \$ 2.57

Available from the
Office of Technical Services
Department of Commerce
Washington 25, D. C.

CLASSIFICATION TYPE
(RD OR DI)

*NAA-SR-MEMOs are working papers and may be expanded,
modified, or withdrawn at any time,
and are intended for internal use only.*

This report may not be published without the approval of the Patent Branch, AEC.

released

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission to the extent that such employee or contractor prepares, handles or distributes, or provides access to, any information pursuant to his employment or contract with the Commission.

UNCLASSIFIED

CLASSIFICATION LEVEL
(S, C, OR U)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ATOMICS INTERNATIONAL A Division of North American Aviation, Inc.		NAA-SR TDR NO. 8017	APPROVALS <i>J. Churchill</i>
TECHNICAL DATA RECORD		PAGE 1 OF 75	<i>H.M. Taylor</i>
AUTHOR H.B. Brooks (10)	DEPT. & GROUP NO. 745-50	DATE 4-3-63	
		GO NO. 7519	
TITLE <u>Design of NAA-62-2</u>		S/A NO. 4436	RECOMMENDED FOR OUTSIDE DISTRIBUTION
		TWR 44003	
PROGRAM ASCR	SUBACCOUNT TITLE Development and Evaluation of Fuel Elements		☒ YES ☐ NO <i>J. Churchill</i> SIGNATURE
DISTRIBUTION USE AN ASTERISK (*) TO INDICATE THOSE WHO ARE TO RECEIVE COMPLETE COPIES	STATEMENT OF PROBLEM To design a prototype fuel element for evaluation under Advanced Sodium Cooled Reactor(ASCR) conditions with auto- matically controlled fuel surface temperature.		
J.L. Ballif* (2)	ABSTRACT: A series of in-pile experiments has been designed to operate under approximate ASCR conditions. The fuel surface tempera- ture will be automatically controlled by means of a BF ₃ thermal neutron flux control system. Complete design calculations and results are presented which should be adequate for presentation of the experiment to the ETR safety committee.		
J.R. Churchill*			
B.B. Gillies*			
B.R. Hayward*			
W.K. McCarty* (2)			
R.M. Peterson* (3)			
T.E. Redding*			
G.M. Taylor*			
B.J. Thomas*			
D.D. Vawter*			
C.W. Wheelock*			

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 1 OF iii

CONTENTS

Abstract	
I. Introduction	
A. Objectives	2
B. In-pile Experiment Design	2
II. General Description	
A. Operating Conditions Desired, NAA-62-2	3
B. Recorder Set Points	4
C. Element Configuration	5-6
D. Instrumentation	7-8
E. Material in the Irradiation Zone Contained in Each Experiment	8
1. Non-fissionable material	8
2. Fissionable material	8
3. Poison material	9
III. Results of Design Calculations	
A. Nuclear Calculations	9-10
B. Heat Transfer	10
C. Stress Analysis	10-12
D. Hydraulic Flow	12
E. Hot Spot - Hot Channel Analysis	13-14
F. Control System	14
1. Thermal Neutron Flux Control	14-16
G. Safety Analysis of BF_3 Gas	16-17
1. Biological	16-17
2. Reactor	17
IV. Operational Procedure	
A. Installation of Console	18
B. Installation of the Experiment	19
C. Start-up Period	19-20
D. Normal Operation	20

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE ii OF iii

E. Emergency Procedures	20-21
F. Shutdowns	21
G. Discharge	21
H. Shipping	21

I. APPENDICES

I. Heat Transfer Calculations	22
II. Film Coefficient	25
III. Bulk Temperature Rise	27
IV. Hot Spot - Hot Channel Analysis	29
V. Burnout Heat Flux	35
VI. Structural Analysis	38
VII. Corrosion From BF_3	52
VIII. Nuclear Calculations	55
A. Flux Required in the Fuel	56
B. Advertised Flux Required	57
C. Burnup and Irradiation Time	58
D. Flux Depression Across the BF_3 Annulus <u>vs</u> Pressure	60
E. B^{10} Burnout Rate	61

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 111 OF 111

FIGURES

1. Sketch of ASCR Irradiation Facility - NAA-62-2	62
2. Cross-section of NAA-62-2	63
3. Picture of Exploded Rod	64
4. Exploded View of Entire NAA-62-2 Assembly	65
5. Completed Fuel and BF_3 Annulus Assemblies	66
6. Fuel Assembly with Junction Tube	67
7. Thermocouple Layout	68
8. Picture of Instrument Console	69
9. Scram Circuitry Terminals	70
10. Nuclear Mock-up of the NAA-62 Assembly	71
11. Thermal Neutron Attenuation Across the BF_3 Annulus	72
12. Block Diagram of the BF_3 Thermal Neutron Flux Control System	73
13. BF_3 Pressure and Density Change in the Annulus as a Function of Reactor Power Level	74

TABLES

I. Operating Conditions Desired, NAA-62-2	3
II. Recorder Set Points	4
III. Heat Transfer Summary	24
IV. Summation of Stress Calculations	12
V. Hot Spot - Hot Channel Analysis Summary	13

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 2 OF 75

I. INTRODUCTION

A. Objectives

The prime objective of this series of tests is to evaluate prototype fuel elements designed for use under Advanced Sodium Cooled Reactor (ASCR) conditions. The fuel element design is expected to be a multi-rod cluster containing uranium carbide fuel, cooled by flowing sodium. The exit temperature of the sodium is expected to be between 1150 and 1300°F. Peak fuel burnups ranging from a low of 10,000 mega-watt-days/metric tonne (Mwd/MTU) to more than 30,000 Mwd/MTU at constant burn-up rates are desired.

B. In-pile Experiment Design

This is the second of a series of in-pile experiments designed to approximate fuel elements operating under ASCR conditions. NAA-62-2 has the identical basic design of NAA-62-1¹, but contains one 3Z1 alloy⁷ fuel cladding. Each experiment consists of a three rod fuel element containing sodium bonded, stoichiometric UC which is water cooled and surrounded by a thermal neutron flux control system.

The thermal neutron flux control system consists of an annulus which surrounds the three rod fuel cluster pressurized with boron tri-fluoride (BF_3) gas, 90% enriched with the neutron absorbing B^{10} isotope. Gas pressure (density) in the annulus is automatically controlled to maintain constant temperature at the fuel element midplane by keeping the thermal neutron flux constant there, through the $\text{B}^{10} (n, \alpha) \text{Li}^7$ reaction. On NAA-62-1 the flux control assembly with its prototype fuel element replaced an ETR 'A' piece. For NAA-62-2, the simulated 'A' piece containing the BF_3 annulus and the fuel rod cluster are separate assemblies with individual lead tubes. The BF_3 annulus assembly will become a semi-permanent installation with the fuel clusters removed and replaced as desired.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 3 OF 75

II. GENERAL DESCRIPTION

A. Operating Conditions Desired, NAA-62-2

TABLE I

<u>Parameter</u>	<u>Condition</u>
1. Maximum Fuel Cladding Temperature, Rod 'A'	836°F
2. Maximum Fuel Surface Temperature, Rod 'A'	962°F
3. Maximum Fuel Center Temperature, Rods 'A' & 'C'	1609°F
4. Unperturbed Thermal Neutron Flux at side of 'A' piece nearest reactor core (15%, 30% > minimum necessary)	$2.02 \text{ to } 2.32 \times 10^{14} \frac{n}{\text{cm}^2\text{-sec}}$
5. Maximum Expected Fuel Surface Thermocouple reading on Rod 'A'	760°F
6. Normal Operating Range of BF_3 Pressure	15 to 350 psia
7. Mass of B^{10} in Control System Under normal operating conditions	0.4 to 7.4 grams
8. Peak Power Generation* Per Foot of single 'hot' rod	30.9 Kw/ft
9. Peak Power Generation Per Foot of 'cold' rod	24.7 Kw/ft
10. Average Power Generation Per Foot of single 'hot' rod	23.2 Kw/ft
11. Average Power Generation Per Foot of 'cold' rod	18.5 Kw/ft
12. Total Average Power Generation of cluster (1.33 peak/average)	141 Kw
13. 'Hot' Rod Peak Surface Heat Flux	$4.57 \times 10^5 \frac{\text{Btu}}{\text{ft}^2\text{-hr}}$
14. 'Hot' Rod Peak Burn-up NAA-62-2	10,000 Mwd/MT
15. 'Cold' Rod Peak Burn-up NAA-62-2	8,000 Mwd/MT
16. Irradiation Time at Full Power NAA-62-2	100 days

- * All statements concerning power generation on this page are based on 175 MeV/fission deposited in the fuel.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 4 OF 75

B. RECORDER SET POINTS

Table II

<u>Recorder Function</u>	<u>Set Points</u>	<u>Action</u>	<u>Correction</u>
Pressure	350 psia	red light <u>Information only</u>	Possibility that the BF ₃ reservoir needs filling with new gas, according to instructions in the operation manual ² , if the pressure has been steadily rising. <u>OK to operate with red light on.</u>
	450 psia	klaxon horn <u>Information only.</u>	Near control range limit of 500 psia. Must refill the reservoir during shutdown with BF ₃ . Once horn has sounded it may be inactivated.
High temperature	1700°F	red light <u>Information only</u>	None.
Low temperature Scram Protection	820°F	amber light	Initiates slow setback. Push reset button to see if condition still exists. Check pressure to verify existence of control.
Recorder-Controller	850°F	red light, klaxon horn	Initiates fast setback--follow above checks.
	760°F	Controlled temperature desired	Feeds signal to proportioning unit for automatic control.
	790°F	Activates a 1000 watt heater in BF ₃ reservoir	Additional heat input into reservoir causes gas pressure to rise, reducing fuel temperature.
	810°F	Activates an additional 2,000 watt heater in BF ₃ reservoir, and turns off the refrigerator (optional-see operations manual).	Provides a backup for the other controlling heaters.

C. Element Configuration

The irradiation capsule, NAA-62-2, consists of three (3) uranium monocarbide fuel rods in triangular array, surrounded by the neutron modulating BF_3 gas annulus (see Figures 1 through 6, beginning on page 62). The three (3) fuel rods identified as 'A', 'B', and 'C', will be oriented in the test hole so that rods 'A' and 'C' will face the reactor core center. Rod 'B', in the extreme position, will be referred to as the 'cold' rod throughout the data package. Rods 'A' and 'C' are identical in composition, having a 26" fuel column of 0.400" diameter slugs, sodium bonded to a type 304 stainless steel cladding 0.430" I.D. with a 15 mil wall. Rod 'B' has an identical fuel loading, but is clad with a 321 alloy, 0.430" I.D. with a 20 mil wall, as shown in Figure 2, page 63. The stainless steel clad rods each have two (2) in-fuel thermocouples to determine the center temperature at the fuel midplane and the surface temperature 5 inches from the bottom of the fuel column. The fuel surface thermocouple comes through the bottom endcap, up through the center of the slugs and then angles over to the side, just breaking the surface. The in-fuel thermocouples are platinum-platinum-rhodium with tantalum sheaths. Fuel-cladding surface temperatures will be measured by 6 chromel-alumel thermocouples bonded to the surfaces of all three rods. Thermocouple placement is shown in Figure 7, page 68. A cobalt neutron monitor wire is placed longitudinally on each rod between the thermocouples.

Each fuel rod assembly with thermocouples and monitor wires attached is then contained by a 52 mil wall 'A' nickel tube with double end plugs. The nickel tube has a 0.884" O.D. and a 0.780" I.D., thus forming a 0.160" annulus around the stainless steel (0.155" annulus around the 321) fuel cladding which contains the thermocouples and monitor wires. Thermal

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR # 8017
DATE April 3, 1963
PAGE 6 OF 75

bonding of the nickel tube and the hardware inside the annulus to the stainless steel fuel cladding is accomplished with sodium-potassium (NaK). A 0.060" stainless steel wire spacer is spirally wound around the nickel tube to complete the assembly. The BF_3 annulus assembly is placed in the test position first and then the three rod fuel cluster is inserted, taking care to orientate the reference mark on the fuel bundle properly with respect to the reactor core center-line, as shown in Figure 2, page 63.

The BF_3 annulus is formed by two (2) concentric right circular cylinders approximately 39" long. The inner BF_3 cylinder has an inner diameter of 2.133" and an outer diameter of 2.760" (107 mil wall) thus forming a BF_3 annulus of 171 mils. The annulus assembly has its own lead tube containing the gas line. The gas tube is 3/16" O.D. with a 0.049" wall, and the lead tube is 0.500" O.D. x 0.370" I.D. Instrumentation leads from the fuel-filler piece assembly are contained in a lead tube emanating from the three rod array.

Thermocouple leads from each fuel rod are contained by a 0.625" O.D. x 0.500" I.D. x 3.063" long neck, welded to the top of the fuel rod assembly. The three necks feed into a junction tube 2.125" O.D. x 1.995" I.D. x 6" in length. Inside this 6" tube the thermocouple leads are formed in a bundle and contained from the point on in a lead tube 0.750" O.D. x 0.652" I.D. x 25' long.

E. Instrumentation

There are two separate functions performed by the NAA-62-2 instrument console shown in Figure 8, page 69. One function performed is the sensing of changes in power generation of the fuel and automatically adjusting the B^{10} density, via pressure, for regulation. The console senses a change in power generation by measuring the fuel cladding temperature, which is proportional to the power generation, with a chromel-alumel thermocouple. Figure 7, page 68, indicates the thermocouple locations and identifies each as to type, one of which is used for control purposes. Any of the chromel-alumel thermocouples at the same elevation may be used for back-up control thermocouples once the operating characteristics of the element are established. (See Reference 2 for details.)

Another function of the console is the recording of various operating conditions and initiating protective action to help maintain the desired conditions. A pressure transducer located inside the console monitors the gas pressure in the line leading to the test hole and the output from the transducer is recorded by a millivolt recorder. If a high pressure condition exists, an annunciator in the annunciator panel is activated to call attention to the condition by means of a klaxon horn and/or lights, depending on the severity of the condition (see Figure 8 page 69, for location of annunciators). Multipoint recorders for recording temperature data complete the monitoring equipment. A single-pen strip chart recorder which will monitor the output of a selected 'high' temperature chromel-alumel thermocouple has two (2) variable set points which may be connected into the reactor scram circuitry.

All wiring of the scram circuitry inside the console is complete and terminates at terminal strips which will allow reactor operations to connect into existing scram circuitry in any manner desired (see Figure 9 , page 70). It is

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 8 OF 75

anticipated that only types of power setbacks will be used, not full scrams. The set points also operate lights and a horn in the corresponding annunciator panel to describe the temperature conditions on the fuel cladding. The platinum-platinum-rhodium, high temperature recorder, also has two (2) variable set points that indicate temperature conditions on the surface and in the center of the fuel (see Table II, page 4) by the operation of lights and a horn. The high temperature recorder is not hooked into the scram circuitry since any power excursion beyond the range of the flux control system would show up on the low temperature recorders (0-2,000°F).

F. Material in the Irradiation Zone Contained in Each Experiment

1. Non-fissionable material

<u>Type</u>	<u>Mass in Grams</u>
Sodium	17.3
NaK	390.0
3Zl Alloy	92.0
Aluminum	1,850.0
Nickel	2,210.0
Stainless Steel	14,535.0

2. Fissionable Material

The contained fuel is U 4.8 w/o C, 14.7% & 14.95% enriched with U₂₃₅. The rods range in length from 25.95 to 26.01 inches and are composed of 0.400-inch diameter slugs varying in length from 0.581 to 2.996 inches.

NAA-62-2

<u>Fuel Length in Inches</u>	<u>Total Mass Fuel in Grams</u>	<u>Average Mass Percent Carbon</u>	<u>Total Mass U in gms</u>	<u>Total Mass U₂₃₅ in gms.</u>	<u>Total Mass U in gms</u>	<u>Average Density in gm/cm³</u>	<u>Rod</u>
25.974	617.022	4.67	588.2	86.5	501.7	13.77	<u>A</u>
25.941	693.640	5.03	658.7	96.8	561.9	13.45	<u>B</u>
26.013	662.450	4.75	631.0	94.33	536.7	13.59	<u>C</u>

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 9 OF 75

3. Poison Material

The poison material is listed as the minimum, maximum expected, maximum possible not withstanding an accident, and maximum possible amount if the BF_3 in a fresh supply tank were allowed to equalize pressure in the supply tank and the annulus by accident. The assumed temperature is 212°F.

<u>Pressure</u>	<u>15 psia</u>	<u>350 psia</u>	<u>450 psia</u>	<u>1010 psia</u>
BF_3	2.66 gm	51.5 gm	65.7 gm	160 gm
containing				
B^{10}	0.38 gm	7.39 gm	9.4 gm	22.9 gm
B^{11}	0.04 gm	0.81 gm	1.1 gm	2.6 gm

III. RESULTS OF DESIGN CALCULATIONS

A. Nuclear Calculations

A summary of most of the pertinent nuclear calculations is given in Section II-A (in Table I) outlining the desired operating conditions.

Calculation indicates that 100 days irradiation with a radial average flux in the fuel of 1.62×10^{13} n/cm²-sec will result in a peak burnup of 10,000 Mwd/Tonne of contained uranium. This corresponds to 3.76×10^{20} fissions/cm³, or 7.24 atom percent of U_{235} peak burnup for Rod 'A'. See Appendix VIII for details.

An average flux in the fuel of 1.62×10^{13} n/cm²-sec is calculated to produce about 30.9 KW peak power per individual 'hot' rod foot, 24.7 KW/ft per 'cold' rod foot, or about 86.5 KW peak power per foot of the element. The peak power generation of the 'hot' rods is 1.21×10^8 Btu/ft³-hr in the fuel and including the 'cold' rod, the expected total average power generated by NAA-62-2 is about 141 KW. At this power level the contribution to the power output by gamma heating in the fuel is not significant.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 10 OF 75

Machine calculations³ using the S_n machine code results in a perturbation factor of 0.109 for the entire assembly with a negligible amount (0.003 gm/cc) of BF_3 gas. A complete description of the method of perturbation calculation is given in Appendix II-B, Reference 1.

Applying the perturbation factor of 0.109 to the average flux desired in the fuel gives a minimum perturbed flux of 1.49×10^{14} n/cm²-sec without allowing for any flux control. Allowing for a minimum reduction of 15%, the desired minimum unperturbed flux becomes 1.71×10^{14} n/cm²-sec. The maximum unperturbed flux desired is 2.38×10^{14} n/cm²-sec.

B. Heat Transfer

At normal operating conditions the hot spot temperature distribution at the midplane is calculated to be as shown in Table III, page 24.

Based on operating data from NAA-62-1 and perusal of the ETR flux map, the rod farthest from the core, i.e., the 'cold' rod, would be expected to operate with about 80% as much power generation as the 'hot' rods.

The normal power generation rate of 1.21×10^8 Btu/ft³-hr results in a fuel surface heat flux of 4.57×10^5 Btu/ft²-hr at the cladding-coolant interface of the 'hot' rods. Details of the heat transfer calculations are given in Appendices I through V, starting on page 22.

A 30% increase in power generation results in a surface heat flux of 5.94×10^5 Btu/ft²-hr. Calculation of the "burnout" heat flux using a statistically derived polynomial correlation results in a value of 3.5×10^6 Btu/ft²-hr. This is 7.66 times the nominal and is 5.89 times the surface heat flux caused by a 30% increase in power generation. See Appendix V for details.

C. Stress Analysis

The maximum calculated stress in the BF_3 container is 31×10^3 psi tension at the inside surface at each end of the

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 11 OF 75

outer tube, for a maximum possible accident pressure of 1,000 psi. The maximum stress for the normal operating pressure of 300 psi is 9,420 psi tension in the same location. The ultimate and 0.2% offset yield strength of 304 stainless steel at 120°F, corrected for a weld efficiency of 85%, are 70,000 psi and 26,800 psi, respectively (see Reference 4). The BF_3 container has a safety factor of approximately 3 under normal operating conditions and about 2 with an accidental failure pressure of 1,000 psi. Details of the stress calculations are shown in Appendix VI , pages 38 to 51.

For the nickel outer fuel rod claddings, the maximum stress calculated in Appendix VI will be 9,880 psi compression on the inside surface. The 0.2% offset yield strength⁵ for nickel is 23,000 to 26,000 psi at room temperature and should not be very much lower for the ~200°F average operating temperature. The outer cladding has a safety factor of approximately 2.3.

Stresses on the inner, or primary, fuel claddings are calculated in Appendix VI for each individual rod. At the beginning of the irradiation period there will be no fission gas released or irradiation induced fuel swelling so the stresses are caused simply by thermal expansions. Near the end of the fuel irradiation test stresses will be much higher because of the released fission gas and fuel swelling. Using the best information available⁶ estimates are made for percentages of fission gas released and fuel volume changes for the stress calculations. The results are shown in Table IV below.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017DATE April 3, 1963PAGE 12 OF 75

Rod	Initial Stress in psi, 0 Burnup	Total Burnup MWD/MTU	Maximum End of Test Stress, psi	Location on Cladding
A (304 SS)	14,017 (T)	7,500	15,320 (T)	Midplane, outer surface
B (321)	3,046 (T)	6,000	4,550 (T)	Midplane, outer surface
C (304 SS)	14,022 (T)	7,500	16,210 (T)	Midplane outer surface

Table IV Summation of Stress Calculations

The stresses shown in Table IV for the 304 stainless steel clad fuel rods are within the creep range at the 'hot spot' temperature of 881°F, but as shown in Appendix VI, the majority of the stresses are thermal in nature and should relieve after slight creep occurs. The 0.2% offset yield strength of the 321 alloy is 43,000 psi @ 1,000°F so the stresses on Rod 'B' are also safe.

D. Hydraulic Flow

The flow rate for the NAA-62 element in its specially constructed 'A' piece was determined by performing measurements on a hydraulic mock-up⁸. At a core pressure drop of 58 psi, the flow rate was determined to be 54 gpm of 110°F water. A description and the results of the flow test are given in Appendix VI, Reference 1.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 13 OF 75

D. Hot Spot Hot Channel Analysis

The following table provides a summary of the hot spot-hot channel analysis. Details are given in Appendix IV.

<u>Item</u>	<u>F_n</u>	<u>F_b</u>	<u>Additives</u>
1. Mechanical Tolerances			
a. Disadvantageous Mass Flow	1.015	-----	-----
2. Mechanical Distortion			
a. Disadvantageous Mass Flow	1.03	-----	-----
3. Uncertainty in Heat Transfer Coefficient	1.20	-----	-----
4. Determination of Critical Parameters			
a. Flow Measurements	1.03	1.04	-----
b. Pressure Measurements	-----	-----	2°F
c. Temperature Measurements	-----	-----	5°F
5. Neutron and Gamma Uncertainties			
a. Unperturbed Flux Measurements	1.20	1.20	-----
b. Perturbation Calculations	1.10	1.10	-----
c. Uncertainty in Calculated Heat Generation	1.041	1.041	-----
d. Power Generation Variation-timewise	1.35	1.35	-----
6. Variations in Heat Flux Over Element Surface			
a. Fuel Homogeneity	1.037	-----	-----
b. Non-uniformity	1.006	-----	-----
7. Increased Flux for Control System	1.15	1.15	-----
	PRODUCT	PRODUCT	SUM
	2.88	2.22	7°F

Table V. Hot Spot - Hot Channel Analysis Summary

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 14 OF 75

D. HOT SPOT - HOT CHANNEL ANALYSIS

The increase in bulk coolant temperature was determined to be approximately 19°F (Appendix III) and the film drop was calculated to be 63°F for the 'hot' rods (Appendix II). Using this information the 'hot spot' temperatures are calculated to be 273°F at the bottom and 319°F at the middle. The lowest pressure in the ETR core is 142 psia at the bottom and the boiling point of water at this pressure is 354°F. In conclusion, the experiment will be safe even if all of the factors considered in Table V occurred at the same time.

E. CONTROL SYSTEM

1. Thermal Neutron Flux Control

The BF_3 control system proved capable of depleting about 60% of the thermal neutron flux, operating at a pressure of 425 psia in an annulus 171 mils thick. Under normal conditions, necessitating a 15-20% reduction in thermal neutrons, the control system would operate in the neighborhood of 75-100 psia. These figures are borne out by S_n and I_2 machine code calculations, hand calculations using simple infinite slab geometry, and by actual experiments performed with a nuclear mock-up of the NAA-62 element and its 'A' piece (see Figure 10 page 71) in the ASCR Critical Facility. Results are shown in Figure 11, page 72.

Calculations based on data reduced from operation of NAA-62-1 indicate a 31% decrease in BF_3 density in the gas annulus caused by increased average temperature of the gas. This decrease resulted in a 21% loss of effective control. (See Appendix VIII). One reason there was such a density change was because there was a relatively large cooler volume in the gas leads from the annulus to the controlling valves. Loss of control in the new control system is minimized by having only one small lead tube from the BF_3 reservoir to the annulus. A complete description

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 15 OF 75

and gas system flow diagram is given in Reference 2 so only a general description of the control system is given here. A block diagram of the control system is shown in Figure 12 page 73, for this discussion. Basically the method of varying the gas pressure in the control annulus consists of modulating the BF_3 vapor pressure in a closed system through the use of a heater-opposed refrigeration system.

In other words, the refrigerator, running at a constant rate, tends to condense all of the BF_3 gas in a reservoir while the heaters act to evaporate the gas back into the annulus. Power input to control heater #1, as shown in Figure 12, is determined by the polarity and amplitude of the signal output from the recorder-controller. The polarity of the signal depends on the direction the temperature deviates from the control set point #1 and the signal strength depends on the amount of deviation from the control set point. The recorder-controller will be driven by the hottest fuel cladding thermocouple on the hottest rod. A retransmitting slidewire within the recorder produces a d c voltage which is proportional in polarity and amplitude to the amount of cladding deviation from the control set point. This d c signal is applied to the proportioning unit which provides adjustable rate and integration (anticipatory action) to achieve optimum control. The proportioning unit produces a current output which is fed into the power manipulator, (a silicon controlled rectifier unit) which adjusts the voltage applied to the gas reservoir control heater, #1.

The three heaters, refrigerator coil, and BF_3 reservoir shown in Figure 12, page 73, are all coiled together and thermally bonded for good heat transfer. As indicated in Figure 12, if the temperature increases to the second set point another heater is turned on to assist the control heater

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 16 OF 75

in increasing the gas pressure. If the combined effort of heaters 1 and 2 does not stop the temperature rise, the third set point is reached and the third "emergency" heater is activated. At this point the refrigerator may also be stopped, if desired. In order to have some control on the low side of the desired fuel cladding temperature the control heater will normally be on, providing enough heat to the BF_3 gas to reduce the thermal neutron flux by 15-20%. The heater-refrigeration system has demonstrated the capability of controlling the BF_3 pressure in the range of 50 to 500 psia. The lowest initial operating gas pressure is expected to be 70 to 75 psia, depending on the neutron flux obtained in the test reactor.

G. Safety Analysis of BF_3 Gas

1. Biological

BF_3 gas will cause burns on the skin at high concentrations $\gg 100$ ppm. Studies at ORNL showed that BF_3 inhaled in concentrations of 100 ppm acted as a pulmonary irritant and predisposed the body to pulmonary infections such as pneumonia. No pathological characteristics of BF_3 poisoning were found in rats, dogs, or guinea pigs exposed for 30 days to a concentration of 15 ppm.⁹ Exposed skin should be washed with water to decrease or eliminate tissue damage¹⁰. After washing, application of a wet dressing of a paste of magnesium oxide, magnesium sulfate, and glycerine is advisable.¹¹ BF_3 may be tolerated by humans up to 15 ppm, but it is very irritating to the respiratory tract^{9,11}. No medical evidence of chronic effects have been found among workmen who have been frequently exposed to small amounts for periods up to seven (7) years⁹.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 17 OF 75

When released in air the gas appears as pungent white fumes that are easy to see but very difficult to breathe. There are 16 ft^3 of gas in each new, unused, BF_3 bottle. If this gas were released in the reactor room which is $90 \times 136 \times 55\frac{1}{2}$ ft, the concentration would be about 24 ppm, if the air were stagnant. The air inside the reactor building is completely changed every 10 minutes in the console and basement floor area, hence personnel safety is assured in case of a major leak. With a flow rate of air in this area of $1500 \text{ ft}^3/\text{min}$ a leak of 0.637 liters/min (STP) outside of the console would be within the 'safe' concentration of 15 ppm. The console cabinets containing gas hardware are hooked independently into the ETR exhaust system to remove gas that might escape from small leaks. The gas hardware may be removed or replaced at any time by condensing the gas in the reservoir and in the cold trap with liquid nitrogen.

2. Reactor

If a full bottle of BF_3 were released into the coolant system, 1.02×10^{23} molecules of BF_3 would be reacted into the water. Aluminum is the principal metal in the reactor that is in contact with the coolant. The maximum net reaction of fluorine with aluminum is simply $\text{Al} + \frac{3}{2} \text{F}_2 = \text{AlF}_3$, i.e., it takes 3 fluorine atoms to displace one aluminum atom. The maximum number of aluminum atoms that could be removed is, then, 1.02×10^{23} . This would be a total mass of 4.58 grams of aluminum removed from the reactor system.

The boron 10 , spreading throughout the reactor, would rapidly be burned up leaving one lithium atom for each n, α reaction occurring. The initial concentration of B^{10} in the reactor coolant would be negligible. The ion exchange system of the ETR would quickly remove most of the foreign material.

• See also Appendix X, Induced Radioactivity, and Appendix XI, Corrosion, Reference 1.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 18 OF 75

IV. OPERATIONAL PROCEDURE

A. Installation of Console

Power for the instruments is provided to terminal strips inside the console cabinets by means of three-prong, 115 VAC leads. All instruments should be plugged into the terminal strips before connecting the outside leads. Electrical power for the reservoir heater power-state comes from a 100 KVA transformer through its companion distribution panel which has been installed at the ETR site for this purpose. The refrigeration system requires a 220 VAC, 50 ampere, single-phase power input which may also be drawn from the distribution panel. The main switch at the distribution panel will be OPEN while connections are made at the console. Initially only one set of components, of the two complete sets available, will be used. The BF_3 gas containers will be shipped in a separate container and will be hooked into the gas system by ETR personnel, according to instructions in the operation manual, Reference 2.

A purge line from the gas system console must be connected into the ETR exhaust stack for release of depleted BF_3 and associated by-product gases. There is also an exhaust tube on the top of the main gas console that should be connected into the ETR exhaust system. This tube pulls air through the lower part of the cabinet which contains the gas handling system, exhausting any BF_3 that might escape through small leaks. Console components will be installed, checked out, and operated in accordance with instructions given in the companion document, Reference 2.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TBR #8017

DATE April 3, 1963

PAGE 19 OF 75

B. Installation of the Experiment

As described in Section II-C, the simulated 'A' piece containing the BF_3 gas annulus is expected to remain in the reactor for some time for use with various fuel assemblies. The BF_3 gas line is contained in its own $\frac{1}{2}$ " OD lead tube which must be scheduled for bending before insertion in the reactor. A $\frac{3}{4}$ " OD lead tube contains thermocouple leads from the fuel cluster and should be installed for easy removal. Junction boxes, providing gas tight electrical connections through the reactor shield, are to be supplied by the Phillips Petroleum Company. PPCo will also supply 20 chromel-alumel thermocouple leads, 4 platinum-platinum 10% rhodium thermocouple leads, and a stainless steel gas line $\frac{3}{16}$ " OD x 0.049" walls, protected by a $\frac{1}{2}$ " OD x 0.65 wall lead tube. ETR personnel will install and connect all lead wires and gas line between the junction box and consoles according to instruction in Reference 2.

After connection of the in-pile thermocouple leads to the junction box terminals, a final loop resistance check should be made for comparison with the readings given in Figure 7, page 68. The thermocouple leads will then be installed and hooked into the proper 24 point recorders, according to the hook-up order given in Figure 7, page 68. Checkout of the gas system should follow procedures given in Reference 2.

C. Start-up Period

During reactor start-up, the flux control system will be operated according to instruction given in Reference 2. After stable operating temperatures are obtained, it may be necessary to adjust the control band of the recorder-controller to attain the desired fuel center temperature

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 20 OF 75

of 1600°F. Once the proper center fuel temperature is being maintained by the neutron flux control system, only normal maintenance of the system should be required.

D. Normal Operations

After steady state operation of the experiment has been established, the control console should be regularly checked during each shift. Responsibility for periodic shift checks will rest with the Atomics International site representative. Periodic checks should include the following:

1. Output of the controlling thermocouple should be verified by comparison with readings of the companion thermocouples. It is important that failure of the controlling thermocouple be detected as soon as possible.
2. The excitation voltage of 14 volts to the pressure transducers should be adjusted as is necessary.
3. The operating gas pressure should be noted to decide if cleansing and recharging of the BF_3 gas is needed.

E. Emergency Procedures

Leakage of the BF_3 gas into the reactor coolant system is highly unlikely, considering the manner in which the gas leads are contained. If gas were leaking into the reactor coolant, gradual loss of temperature control would result with the eventual sounding of an alarm. A check of the pressure recorder chart or dial indicator would indicate the nature of the problem. If a leak were to develop outside the console, the white fumes (resembling cigarette smoke) would serve to locate the spot. A leak inside the console will not be immediately apparent without visual observation since the ETR exhaust system will be pulling

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 21 OF 75

fresh air through to the exhaust stack at all times.

If there is a significant leak at any location, procedures given in Reference 2 should be followed for repairs. If very dense white fumes are around indicating a bad leak, oxygen equipment, along with rubber gloves and protective clothing for the body, should be worn.

In the event of an alarm indicated by the annunciator panel proper action can be taken by referring to Table II, page 4. A check of the strip charts and pressure meter should quickly identify the trouble.

F. Shutdowns

With the present design of the gas handling system, no special precautions need be observed prior to and during a reactor shutdown. During shutdown, nearly all of the BF_3 gas will be condensed into the reservoir automatically. The drawing out of the 'hot' BF_3 gas from the control annulus should present no problems as far as radioactivity goes (according to the results presented in Appendix IX of Reference 1). A maintenance schedule is given in Reference 2 to be followed during the shutdown period.

G. Discharge

Since the fuel assembly is designed to be removed separately from the BF_3 control annulus, it may be handled as any other fuel cluster. The lead tube may be cut at any convenient point above the 'A' piece and the assembly stored in the ETR canal for cooling before shipment.

H. Shipping

Calculations¹² indicate that NAA-62-2 must 'cool' in the canal for five (5) days before being shipped in a 10" thick walled shipping cask. Complete shipping instructions will be sent with the shipping cask.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 22 OF 75

APPENDIX I

HEAT TRANSFER CALCULATIONS

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 23 OF 75

I. HEAT TRANSFER CALCULATIONS

The temperature gradient in each annulus was computed from:

$$t = \frac{Q r_f^2 \ln r_o / r_i}{2k}$$

The temperature gradient in the fuel was computed from:

$$t = \frac{Q r_f^2}{4k}$$

where:

t = temperature gradient, °F

r_o = outer radius of annulus, in.

r_i = inner radius of annulus, in.

r_f = radius of fuel, ft.

k = thermal conductivity, Btu/hr-ft-°F

Q = power generation, Btu/hr-ft³

The following table gives the regions, radii, thermal conductivities used, and the resulting hot spot temperatures for the nominal power generation of 1.21×10^8 Btu/hr-ft³. The film drop calculation is given in Appendix II.

<u>REGION</u>	<u>MATERIAL</u>	<u>OUTSIDE RADIUS, IN.</u>	<u>THERMAL CONDUCTIVITY Btu/hr-ft-°F</u>	<u>TEMPERATURE GRADIENT °F</u>	<u>TEMPERATURE AT OUTER RADIUS °F</u>	<u>CENTRAL FUEL TEMPERATURE °F</u>
1	Water Film			63 (50)	120	
2	Ni Outer Cladding	0.442	37.5	55 (44)	183 (170)	
3	NaK	0.390	14.9 (14.6)	598 (470)	238 (214)	
4	SS Inner Cladding (3Zl)*	0.230 (235)	12.1	94 (125)	**836 (684)	
5	Na Bond	0.215	38.6	32 (24)	930 (809)	
6	UC Fuel	0.200	13	647 (518)	962 (833)	1609 (1351)

* Information on the 3Zl clad rod is in parentheses, ( ).

** Actual reading of the cladding thermocouple (out in the NaK) is calculated to be 760°F and this value will be used for the initial control point.

TABLE III HEAT TRANSFER SUMMARY

APPENDIX II

FILM COEFFICIENT AND FILM DROP

II. FILM COEFFICIENT AND FILM DROP

The velocity in the heat transfer section is 26.3 ft/sec as derived from the 54 gal/min mass flow rate and 0.66 in² cross-sectional area for flow.*⁸

The film coefficient is calculated from the Modified Colburn equation as outlined in IDO 16343:¹³

$$h = \frac{b_f V^{0.8}}{D^{0.2}} = \frac{(375)(26.3)^{0.8}}{(0.179)^{0.2}} = (7.24)(10^3) \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$$

where:

h = film coefficient, Btu/hr-ft²-°F

V = velocity, ft/sec

D = hydraulic diameter, in. (4 wetted area/wetted parameter)

b_f = base factor, from page 52 of IDO 16343, at average film temperature

The film drop for the reactor core-facing 'hot' rods is:

$$\Delta t_{\text{film}} = \frac{q}{h} = \frac{(4.57)(10^5)}{(7.24)(10^3)} = 63^\circ\text{F, and}$$

$$\Delta T_{\text{film}} = (63)(.80) = 50^\circ\text{F for the 'cold' rod in the back.}^*$$

where:

$$\Delta t_{\text{film}} = \text{film drop, } ^\circ\text{F}$$

q = surface heat flux, Btu/hr-ft²

h = film coefficient, Btu/hr-ft²-°F

---

* Due to a combination of increased enrichment and decreased thermal neutron flux because of rod location, the back rod is expected to operate at approximately 80% of the power of the 'hot' rods.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 27 OF 75

APPENDIX III

BULK TEMPERATURE RISE

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 28 OF 75

III. BULK TEMPERATURE RISE

$$\Delta t_{\text{bulk}} = \frac{\bar{Q}}{G \rho c_1}$$

$$G = \frac{(54 \text{ gal/min})(60 \text{ min/hr})}{7.48 \text{ gal/ft}^3} = 433 \text{ ft}^3/\text{hr}$$

$$\bar{Q} = 4.93 \times 10^5 \text{ Btu/hr}$$

$$= 61.4 \text{ lb/ft}^3 \text{ at } 100^\circ\text{F}$$

c_1 = heat capacity, 1 Btu/lb-°F

$$\Delta t_{\text{bulk}} = \frac{(4.93)(10^5)}{(433)(61.4)(1)} = 19^\circ\text{F}$$

NOTE: Hydraulic data from Reference 8.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 29 OF 75

APPENDIX IV

HOT SPOT - HOT CHANNEL ANALYSIS

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 30 OF 75

IV. HOT SPOT - HOT CHANNEL ANALYSIS

Descriptions of the hot spot - hot channel factors presented in Table V page 13 are given below, as outlined in IDO 16343:

A. Mechanical Tolerances (Hydraulic Effects)

1. Effect on Mass Flow - External Effects

Since the coolant flow was measured there are no hot spot or hot channel factors attributed to this item.

2. Effect of Mass Flow - Entrance and Exit Effects

No effects - same as A-1 above

3. Effect on Mass Flow Channel Effects

4. Effect of D Variation

Items 3 and 4 are considered in a lumped factor as outlined in Appendix A of IDO 16343. Neither of these items have an effect on the bulk temperature rise, so $F_b = 1$.

$$F_{h, D} = \left(\frac{D_s}{D_p} \right)^{0.2} = \left(\frac{0.120 \text{ in}}{0.110 \text{ in}} \right)^{0.2} = 1.015$$

where:

D_s = specified equivalent diameter

D_p = perturbed equivalent diameter

B. Mechanical Distortion

Mechanical distortion caused by instability and radiation damage is assumed to be twice the percent uncertainty caused by tolerance. Hence:

$$F_b = 1$$

$$F_h = 1.20$$

C. Uncertainty in the Heat Transfer Correlation Equation

As recommended in IDO 16343, the tolerance applicable to the modified Colburn equation is minus 20%. This gives:

$$F_b = 1.0 \quad F_h = 1.20$$

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR NO. 8017
DATE April 3, 1963
PAGE 31 OF 75

D. Determination of Critical Parameters

1. Flow Measurement

The flow rate was determined experimentally in a hydraulic mock-up of the experiment. The accuracy of the measurements was within $\pm 4\%$ (see Reference 8).

$$F_{b, W} = \frac{W_{\text{nominal}}}{W_{\text{minimum}}} = \frac{54}{54(.96)} = 1.04$$

$$F_{h, W} = \left(\frac{V_{\text{nominal}}}{V_{\text{minimum}}}\right)^{0.8} = (1.04)^{0.8} = 1.03$$

2. Temperature Measurements (metal)

There are no measurements to be made of the outer cladding temperature; therefore this item does not apply.

3. Pressure Measurements

Inaccuracies in pressure measurements may cause a 2°F delta t additive, (from telephone conversation with Leroy Porter, ETR project engineer, 8-26-60).

4. Temperature Measurements (coolant)

Uncertainties in determination of bulk coolant temperature may amount to $\pm 5^\circ\text{F}$ delta t additive, (same source as item 3 above).

E. Flow Distribution Effects

Does not apply.

F. Neutron and Gamma Heat Distribution

No factors (i.e., unity) since calculations are made for the maximum flux, i.e., the hottest spot.

G. Neutron and Gamma Flux Uncertainties

1. Unperturbed Flux Measurement

Variations from nominal may vary $\pm 20\%$ in the ETR,

hence

$$F_b = 1.20$$
$$F_h = 1.20$$

2. Perturbation Calculations

Detailed flux calculations were made utilizing S_n IBM machine code calculations as reported in Reference III. An accuracy of $\pm 10\%$ is assumed.

$$F_h = 1.10$$

$$F_b = 1.10$$

3. Uncertainty of Calculated Heat Generation from Assumed Flux

In the heat generation calculations the following assumptions are made:

- 1) The energy/fission (175 MeV) is accurate to $\pm 3\%$.
- 2) The fission cross-section used, 582 ± 6 barns, is accurate to 1%.
- 3) The reported U²³⁵ density is accurate to $\pm 0.05\%$, but 0.1% will be used here.

The total error is 4.1%

$$F_h = 1.041$$

$$F_b = 1.041$$

4. Experimental Power Generation Variation Timewise Without Flux Control

The local power generation of an element in the ETR may vary as much as 35% during a cycle.

$$F_h = 1.35$$

$$F_b = 1.35$$

H. Variations in Heat Flux Over Element Surface

1. Fuel Homogeneity

This will not affect bulk coolant temperatures, so $F_b = 1.00$. The UC density used in power generation calculations was 13.5 g/cc. Actual measurements on the specimens themselves show a maximum deviation from this

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. _____ TDR #8017
DATE April 3, 1963
PAGE 33 OF 75

value of 0.5003 g/cc or 3.7%. Neglecting increased flux perturbation due to a greater amount of fuel, the power generation would increase proportional to the density. Therefore:

$$F_h = 1.037$$

2. Non-uniformity of Fuel Meat and Cladding Thickness

Actual measurements on the fuel specimens used have shown nearly all of the diameters to be slightly less than the nominal 0.400 in. Therefore, no factor is associated with this item.

The nominal diameter of the outer cladding is 0.886 $\pm$ 0.005 in. A decrease in the diameter would increase the heat flux in proportion. Hence:

$$F_b = 1$$

$$F_h = \frac{0.891}{0.886} = 1.006$$

I. Effect Peculiar to the Experiment

At the request of ETR project engineering, the 15% higher than nominally required flux desired in order to utilize the BF_3 shadowing must be considered. Hence:

$$F_b = 1.15$$

$$F_h = 1.15$$

The hot spot temperature is equal to:

$$T_{\text{hot spot}} = T_{\text{inlet}} + (\pi F_h)(\Delta T_{\text{film}}) + (\pi F_b)(\Delta T_{\text{bulk}}) + \Delta T_{\text{additives}}$$

where:

$$\pi F_h = \text{the product of all } F_h$$

$$\pi F_b = \text{the product of all } F_b$$

$$\Delta T_{\text{add}} = \text{the sum of all } \Delta T_{\text{add}}$$

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 34 OF 75

$$\begin{aligned} T_{\text{hot spot}} &= 110^{\circ}\text{F} + (2.88)(63^{\circ}\text{F}) + (2.22)(19^{\circ}\text{F}) + 7^{\circ}\text{F} \\ &= 110^{\circ}\text{F} + 181.4^{\circ}\text{F} + 42.2^{\circ}\text{F} + 7^{\circ}\text{F} = 341^{\circ}\text{F} \end{aligned}$$

The boiling point at the bottom of the core, where the pressure is 142 psia, is 354°F. However, at the lower end of the assembly, where the bulk temperature rise would be maximum, the heat generation and film drop are less than 2/3 the nominal value considered above. This would give a hot spot temperature at the bottom of the assembly of:

$$\begin{aligned} T_{\text{hot spot}} &= 110^{\circ}\text{F} + (2/3)(181.4^{\circ}\text{F}) + 42.2^{\circ}\text{F} + 7^{\circ}\text{F} \\ &= 280^{\circ}\text{F} \end{aligned}$$

If the hot spot were considered to be at the midlength of the fuel, where the film drop is maximum, only 1/2 of the nominal bulk temperature rise should be used, and the pressure and boiling point are higher. In this case:

$$\begin{aligned} T_{\text{hot spot}} &= 110^{\circ}\text{F} + 181.4^{\circ}\text{F} + (1/2)(42.2^{\circ}\text{F}) + 7^{\circ}\text{F} \\ &= 319^{\circ}\text{F} \end{aligned}$$

In conclusion, the hot spot temperature is below the boiling point of the cooling water and the experiment will not cause boiling.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 35 OF 75

APPENDIX V

BURNOUT HEAT FLUX

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #2017

DATE April 3, 1963

PAGE 36 OF 75

V. BURNOUT HEAT FLUX

The burnout heat flux was calculated using the method outlined in IDO 16460:¹⁴

$$y = 0.3332 - 0.06988 X_1 + 0.1638 X_2 + 0.5319 X_3 - 0.2311 X_4 \\ - 0.006663 X_2^2 - 0.03205 X_3^2 + 0.01211 X_2 X_3$$

$$y = (q''_{bo})(10^{-6})$$

$$q_{bo} = \frac{q}{a} = \frac{\text{Btu}}{\text{hr-ft}^2}$$

$$X_1 = \text{Pressure} \frac{\text{psi}}{1000} = \frac{142}{1000} = 0.142$$

$$X_2 = \text{Temperature} \frac{\Delta T_{\text{sub}}}{10}$$

$$X_3 = \text{Mass velocity} \frac{(\text{lb})(10^{-6})}{(\text{ft}^2)(\text{hr})} = (5.8)$$

$$X_4 = \text{Length} \frac{\text{inches}}{10} = \frac{26}{10} = 2.6$$

$$\Delta T_{\text{sub}} = T_{\text{sat}} - T_1 - \frac{q''_{bo} a}{G(A)(C_p)}$$

where:

$$q = q''_{bo}$$

C_p = specific heat, 1 Btu/lb-°F

A = cross-sectional area, $(4.58)(10^{-3}) \text{ ft}^2$

G = mass velocity, $(5.8)(10^6) \text{ lb/ft}^2\text{-hr}$

T_1 = water inlet temperature, 110°F

T_{sat} = boiling temperature at operating pressure, 354°F

a = heat transfer area, 0.5 ft²

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017DATE April 3, 1963PAGE 37 OF 75

$$\begin{aligned} q''_{bo} \times 10^{-6} = & 0.3332 - (0.06988)(0.142) + (0.1638)\left(\frac{\Delta T_{sub}}{10}\right) \\ & + (0.5319)(5.8) - (0.2311)(2.6) - (0.006663) \\ & \left(\frac{\Delta T_{sub}}{10}\right)^2 - (0.03205)(5.8)^2 + 0.0702 \left(\frac{\Delta T_{sub}}{10}\right) \end{aligned}$$

and:

$$\Delta T_{sub} = 354 - 110 - \frac{q''_{bo}}{(5.8)(10^6)(4.58)(10^{-3})(1)}$$

A trial and error solution of the above two equations and two unknowns gave the following results:

$$\begin{aligned} \Delta T_{sub} &= 112^\circ\text{F} \\ q''_{bo} &= (3.5)(10^6) \text{ Btu/ft}^2\text{-hr} \end{aligned}$$

This value of burnout heat flux is 7.67 times the nominal heat flux, $(4.57)(10^5) \text{ Btu/ft}^2\text{-hr}$, and 5.9 times the nominal increased by 30%.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 38 OF 75

APPENDIX VI

STRUCTURAL ANALYSIS

PREPARED BY.	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 39 OF 75
CHECKED BY.		REPORT NO. TDR #8017
DATE: April 3, 1963	STRESS CALCULATIONS FOR BF ₃ CONTAINER	MODEL NO. NAA 62-2

OUTER TUBE

BF₃ ANNULUS

MAXIMUM PRESSURE (EQUIPMENT FAILURE) 1000 psi

MAXIMUM PRESSURE (NORMAL OPERATION) 300 psi

OUTER TUBE

OUTER

O.D. 2.975 in.

I.D. 2.760 in.

INNER TUBE

INNER

O.D. 2.417 in.

I.D. 2.131 in.

t = .107 in.

t₁ = .142 in.

CHECK STRESSES IN OUTER TUBE

AT AREA "B"

LONGITUDINAL

$$\begin{aligned}
 S_p &= \frac{PR}{2t} \\
 &= \frac{(1000)(1.433)}{.215} \\
 &= \underline{\underline{6,670 \text{ psi}}} \quad \text{TENSION}
 \end{aligned}$$

HOOP

$$\begin{aligned}
 S_p &= \frac{PR}{t} \\
 &= \underline{\underline{13,340 \text{ psi}}} \quad \text{TENSION}
 \end{aligned}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 40 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963	STRESS CALCULATIONS FOR BF ₃ CONTAINER	MODEL NO. NAA 62-2

OUTER TUBE

VIEW "B"

OUTER TUBE

CONDITION SHOWN APPLIES TO BOTH OUTSIDE AND INSIDE SURFACES OF OUTER TUBE

AT AREA "A"

ASSUME END ATTACHMENT TO BE RIGID
FORMULAS FROM REF.15 PAGE 271

MOMENT (MAXIMUM)

$$\begin{aligned}
 M_0 &= .304 \text{ Prt} \\
 &= .304(1000)(1.433)(.107) \\
 &= \underline{46.6 \text{ in.lb.}}
 \end{aligned}$$

BENDING STRESS

$$\begin{aligned}
 S' &= \frac{6(46.6)}{(.107)^2} \\
 &= \underline{24,300 \text{ PSI}}
 \end{aligned}$$

SHEAR (MAXIMUM)

$$\begin{aligned}
 V_0 &= .78 \sqrt{\text{Pr t}} \\
 &= .78(1000) \sqrt{1.433(.107)} \\
 &= \underline{306 \text{ lb/in.}}
 \end{aligned}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 41 of 75
CHECKED BY:		REPORT NO. TDR #8017
DATE. April 3, 1963	STRESS CALCULATIONS FOR BF ₃ CONTAINER	MODEL NO. NAA 62-2

OUTER TUBE

HOOP STRESS DUE TO SHEAR

$$S = \frac{-2 v_o \lambda R}{t}$$

$$\text{WHERE } \lambda = \sqrt{\frac{3(1-\nu^2)}{R^2 t^2}}$$

$$= \sqrt{\frac{3(1-.24^2)}{(1.433)^2 (.107)^2}}$$

$$= 3.32$$

∴

$$S = \frac{-2(311)(3.32)(1.433)}{.107}$$

$$= \underline{-27,700 \text{ psi}}$$

HOOP STRESS DUE TO MOMENT

$$S_2 = \frac{2(M_o) \lambda^2 R}{t}$$

$$= \frac{2(46.6)(3.32)^2 (1.433)}{.107}$$

$$= \underline{14,000 \text{ psi}}$$

HOOP STRESS DUE TO BENDING STRESS

$$S = r s_3$$

$$= (24)(24,300)$$

$$= \underline{5,830 \text{ psi}}$$

MAXIMUM COMBINED HOOP STRESS

$$\text{INSIDE SURFACE} = -27,700 + 14,000 + 5,830 + 13,340$$

$$= \underline{5,470 \text{ psi TENSION}}$$

$$\text{OUTSIDE SURFACE} = -27,700 - 5,830 + 14,000 + 13,340$$

$$= \underline{6,190 \text{ psi COMPRESSION}}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 42 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963	STRESS CALCULATIONS FOR BF_3 CONTAINER	MODEL NO. NAA 62-2

OUTER TUBE

MAXIMUM COMBINED LONGITUDINAL STRESS

INSIDE SURFACE = 6,670 24,300

= 30,970 psi T ←

OUTSIDE SURFACE = 6,670 - 24,300

= 17,630 psi C ←

VIEW "A"

OUTER TUBE

S @ 1000 psi = 17,630 psi C
@ 300 psi = 5,290 psi C

AT OUTSIDE SURFACE OF OUTER TUBE

S @ 1000 psi = 30,970 psi T
@ 300 psi = 9,300 psi T

AT INSIDE SURFACE OF OUTER TUBE

CHECK STRESS IN INNER TUBE

NOTE: CALCULATION PROCEDURE SAME AS FOR OUTER TUBE SO ONLY RESULTS WILL BE SHOWN.

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 43 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963	STRESS CALCULATIONS FOR BF_3 CONTAINER	MODEL NO. NAA 62-2

INNER BF_3 TUBE

CONDITION SHOWN APPLIES TO BOTH OUTSIDE AND INSIDE SURFACES OF INNER TUBE.

AT INSIDE SURFACE OF INNER TUBE

AT OUTSIDE SURFACE OF INNER TUBE

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 44 OF 75

STRESS CALCULATIONS FOR THE OUTER FUEL ROD CLADDING

RODS 'A' & 'C'

THERMAL STRESS

$$S_t = \frac{\Delta T \alpha E}{2(1-\mu)} \text{ where } \Delta T = 55^\circ F$$

$$\alpha = 7.1 \times 10^{-6} \text{ in/in/}^\circ F$$

$$E = 30 \times 10^6 \text{ lb/in}^2$$

$$\mu = 0.3$$

$$\therefore S_{th} = \frac{(55)(7.1 \times 10^{-6})(30 \times 10^6)}{2(1-.3)}$$

$$S_{th} = 8,370 \text{ lb/in}^2$$

T @ OUTER SURFACE

C @ INNER SURFACE

ROD 'B'

$$S_{th} = 6,700 \text{ lb/in}^2$$

T @ OUTER SURFACE

C @ INNER SURFACE

HOOP STRESS

THE PRESSURE EXERTED BY THE HELIUM GAS BOND AT OPERATING TEMPERATURES IS CALCULATED TO BE 22 PSI. THE HIGHEST PRESSURE OUTSIDE THE CLAD IS 200 PSI AT THE TOP, $\therefore$ THE MAXIMUM PRESSURE ON THE CLAD EXTERIOR IS 178 PSI.

$$S_H = \frac{PR}{t} = \frac{(178)(.442)}{.052} = 1,510 \text{ PSI. C}$$

$$\& S_T = \frac{PR}{2t} = 755 \text{ PSI C}$$

AT OUTSIDE SURFACE : HOOP = 6,860 PSI FOR RODS 'A' & 'C' (T)
 5,190 PSI " ROD 'B' (T)
 TANGENTIAL = 7,615 PSI " " 'A' & 'C' (T)
 5,945 PSI " " 'B' (T)

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 45 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR OUTER CLADDING

AT INNER SURFACE : HOOP = 9,880 Psi FOR 'A' & 'C' (C)
 = 8,210 Psi FOR 'B' (C)

TANGENTIAL = 9,125 Psi FOR 'A' & 'C' (C)
 = 7,455 Psi FOR 'B' (C)

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING

THERMAL STRESS

RODS 'A' & 'C' $S_{th} = \frac{\Delta T \alpha E}{2(1-\mu)}$

where: $\Delta T = 94^\circ F$

$\alpha = 10.25 \times 10^{-6} \text{ in/in/}^\circ F$

$E = 20.05 \times 10^6 \text{ lb/in}^2$

$\mu = 0.3$

$$S_{th} = \frac{(94)(10.25 \times 10^{-6})(20.05 \times 10^6)}{2(1-0.3)}$$

$$= \underline{13,800 \text{ lb/in}^2} \quad \begin{array}{l} T @ \text{ OUTER SURFACE} \\ C @ \text{ INNER SURFACE} \end{array}$$

SIMILARLY,

$$S_{th} = \underline{2,820 \text{ lb/in}^2} \text{ FOR ROD } \underline{'B'}$$

HOOP STRESS CAUSED BY: THERMAL EXPANSION, FISSION GAS RELEASE, AND IRRADIATION FUEL SWELLING.

ASSUMING A 1.33 PEAK/AVERAGE NEUTRON FLUX RATIO, THE AVERAGE AXIAL TEMPERATURES OF THE FUEL ROD COMPONENTS ARE :

U-C; $\bar{T} = 967^\circ F$	SODIUM BOND, Na; $711^\circ F$	$\leftarrow$ RODS 'A' & 'C'
SS 304; $\bar{T} = 664^\circ F$	HELIUM; $300^\circ F$	

U-C Thermal expansion — ROD 'A' $V_{U-C} = 48.92 \text{ cm}^3$, $\Delta T = 887^\circ F$

$$\frac{\Delta V}{V} = \beta \Delta T$$

$$\beta = 1.9 \times 10^{-5} \text{ in}^3/\text{in}^3/^\circ F$$

$$\Delta V = V \beta \Delta T = (48.92)(1.9 \times 10^{-5})(887)$$

$$\underline{\underline{\Delta V_{U-C} = 0.824 \text{ cm}^3 \text{ FOR ROD 'A'}}}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 46 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING

U-C Thermal expansion - ROD 'C' where $V_{U-C} = 48.72 \text{ cm}^3$; $\Delta T = 887^\circ\text{F}$

$$\underline{\Delta V_{U-C} = 0.820 \text{ cm}^3 \text{ FOR ROD 'C'}}$$

U-C Thermal expansion - ROD 'B' where $V_{U-C} = 51.57 \text{ cm}^3$; $\Delta T = 741^\circ\text{F}$

$$\underline{\Delta V_{U-C} = 0.727 \text{ cm}^3 \text{ FOR ROD 'B'}}$$

CLADDING EXPANSION

304 SS - RODS 'A' & 'C'

$$D_{ic} = 0.431 \text{ in}; L_c = 28.125;$$

$$\alpha = 10^{-5} \text{ in/in/}^\circ\text{F}; \Delta T = 584^\circ\text{F}$$

$$\Delta D = D_{ic} \alpha \Delta T = (.431)(10^{-5})(584)$$

$$\Delta D = 0.0025 \therefore D_{er} = 0.4335 \text{ in., 'A' \& 'C'}$$

$$\Delta L = L_c \alpha \Delta T = (28.125)(10^{-5})(584) = 0.1643 \text{ in}$$

$$\underline{L_H = 28.2893 \text{ in., 'A' \& 'C'}}$$

FOR ROD 'B' $D_{ic} = 0.4313 \text{ in}; L_c = 28.125 \text{ in.}$

$$\underline{D_{eH} = 0.4321 \text{ in}; L_H = 28.179 \text{ in.}}$$

$$321 \alpha = 2.87 \times 10^{-6} \text{ in/in/}^\circ\text{F}$$

$$\text{RODS 'A' \& 'C' COLD CLAD VOLUME} = V_c = \frac{\pi}{4} D_{ic}^2 L_c$$

$$V_c = (0.785)(0.431)^2(28.125) = 4.10 \text{ in}^3$$

$$V_H = (0.785)(0.4335)^2(28.289) = 4.17 \text{ in}^3$$

$$\underline{\Delta V_{CLAD} = 0.07 \text{ in}^3 = 1.147 \text{ cm}^3 \text{ for 'A' \& 'C'}}$$

$$\underline{\Delta V_{CLAD} = 0.024 \text{ in}^3 = 0.393 \text{ cm}^3 \text{ for 'B'}}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 47 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING

SODIUM BOND THERMAL EXPANSION

ROD 'A': $V_{Na} = 14.9 \text{ cm}^3$ $\bar{T}_H = 711^\circ\text{F}$ $T_C = 80^\circ\text{F}$	ROD 'B': $V_{Na} = 12.9 \text{ cm}^3$ $\bar{T}_H = 617^\circ\text{F}$ $T_C = 80^\circ\text{F}$	ROD 'C': $V_{Na} =$ $\bar{T}_H = 711^\circ\text{F}$ $T_C = 80^\circ\text{F}$

ROD 'A' $\Delta V_{Na} = V_{Na} \left(\frac{\rho_{80^\circ\text{F}}}{\rho_{711^\circ\text{F}}} - 1 \right) = 14.9 \left(\frac{58.6}{53.7} - 1 \right) = \underline{1.40 \text{ cm}^3}$

ROD 'B' $\Delta V_{Na} = \underline{0.99 \text{ cm}^3}$, ROD 'C' $\Delta V_{Na} = \underline{1.30 \text{ cm}^3}$

EXPANSION VOLUME AT ROOM TEMPERATURE - V_C

ROD 'A' $V_C = \frac{\pi}{4} D^2 \ell (16.387 \text{ cm}^3/\text{in}^3)$ where $\ell = 1.6 \text{ in}$ to end cap
 $V_C = (0.785)(0.1857)(1.6)(16.387) = 3.82 \text{ cm}^3 - \text{T/C junction } (.3 \text{ cm}^3)$
 $V_C = 3.52 \text{ cm}^3$

<u>ROD 'B'</u>	<u>ROD 'C'</u>
<u>$V_C = 2.69 \text{ cm}^3$</u> , $(\bar{T} \text{ of } 321 = 562^\circ\text{F})$ AT TEMPERATURE FOR USE BELOW	<u>$V_C = 2.88 \text{ cm}^3$</u>

GAS VOLUME AT OPERATING TEMPERATURE - V_H (NO FUEL SWELLING)

$$V_H = V_C + \Delta V_{CLAD} - \Delta V_{U-C} - \Delta V_{Na}$$

ROD 'A' $V_H = 3.52 + 1.147 - 0.824 - 1.40 = \underline{2.45 \text{ cm}^3}$

ROD 'B' $V_H = 2.69 + 0.393 - 0.727 - 0.99 = \underline{1.36 \text{ cm}^3}$ $\bar{T}_{321} = 562^\circ\text{F}$

ROD 'C' $V_H = 2.88 + 1.147 - 0.820 - 1.30 = \underline{1.91 \text{ cm}^3}$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 48 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY CLADDING

HOOP STRESS AT STARTUP

$$\frac{P_H V_H}{T_H} = \frac{P_C V_C}{T_C} \quad \text{or} \quad P_H = \frac{P_C V_C T_H}{V_H T_C}$$

ROD 'A'

$$P_H = \frac{(14.7)(3.52)(760^\circ\text{K})}{(2.45)(540^\circ\text{K})} = 29.7 \text{ psi}, \Delta P = 29.7 - 14.7 = 15 \text{ psi}$$

$$\sigma_{\text{HOOP}} = \frac{\Delta P D_m}{2t} = \frac{(15)(0.4335)}{2(0.015)} = (15)(14.46) = \underline{\underline{217 \text{ psi (INITIAL STARTUP)}}}$$

ROD 'B'

$$P_H = \frac{(14.7)(2.69)(660^\circ\text{K})}{(1.36)(540^\circ\text{K})} = 35.6 \text{ psi}, \Delta P = 20.9 \text{ psi} \quad \bar{T}_{HC} = 200^\circ\text{F}$$

$$\sigma_{\text{HOOP}} = \frac{(20.9)(0.4321)}{2(0.020)} = (20.9)(10.80) = \underline{\underline{226 \text{ psi (INITIAL STARTUP)}}}$$

ROD 'C'

$$P_H = \frac{(14.7)(2.88)(760^\circ\text{K})}{(1.91)(540^\circ\text{K})} = 30.1 \text{ psi}, \Delta P = 15.4 \text{ psi}$$

$$\sigma_{\text{HOOP}} = \frac{(15.4)(0.4335)}{2(0.015)} = (15.4)(14.46) = \underline{\underline{222 \text{ psi (INITIAL STARTUP)}}}$$

NOTE: AT 7500 ^{MWD} _{MTU} FUEL SWELLING ON THE HYPOSTOICHIOMETRIC U-C IN RODS 'A' & 'C' IS EXPECTED TO BE 2.5% OF THE VOLUME, WITH A 2% FISSION GAS RELEASE. ROD 'B' IS HYPERSTOICHIOMETRIC AND IS EXPECTED TO OPERATE AT A MAXIMUM OF 80% OF THE HOT RODS' POWER. FUEL SWELLING ON ROD 'B' IS EXPECTED TO BE LESS THAN 2%, i.e. ~1.8% WITH A FISSION GAS RELEASE OF 1%, FROM REFERENCE 6.

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 49 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE, April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING

FUEL SWELLING

ROD 'A' 2.5% $\Delta V_{uc} = (48.92)(.025) = 1.22 \text{ cm}^3$

$$V'_H = V_H - \Delta V_{uc} = 2.45 - 1.22 = 1.23 \text{ cm}^3$$

ROD 'B' 1.8% $\Delta V_{uc} = (51.57)(.018) = 0.93 \text{ cm}^3$

$$V'_H = V_H - \Delta V_{uc} = 1.36 - 0.93 = 0.43 \text{ cm}^3$$

ROD 'C' 2.5% $\Delta V_{uc} = (48.72)(.025) = 1.18 \text{ cm}^3$

$$V'_H = V_H - \Delta V_{uc} = 1.91 - 1.18 = 0.73 \text{ cm}^3$$

FISSION GAS RELEASE

ROD 'A' ASSUMING THAT 1 MWD = 2.73×10^{21} FISSIONS @ 193 MEV/FISSION

$$\text{THE TOTAL NO. OF FISSIONS} = (\text{NO. OF MWD}) \left(\frac{\text{MASS OF FUEL, MTU}}{\text{MTU}} \right) (2.73 \times 10^{21} \frac{\text{FIS}}{\text{MWD}})$$

$$\therefore F_T = (7.5 \times 10^3) (6.71 \times 10^{-4} \text{ MTU}) (2.73 \times 10^{21} \frac{\text{FISSIONS}}{\text{MWD}})$$

$F_T = 1.37 \times 10^{22}$ FISSIONS, 32% ARE GASEOUS PRODUCTS OF WHICH 2% MAY BE RELEASED, SO THE NUMBER OF GAS ATOMS RELEASED IS

$$N_G = (1.37 \times 10^{22}) (.32) (.02) = 8.77 \times 10^{19} \text{ ATOMS}$$

VOLUME OF FISSION GAS AT S.T.P. IS

$$V_{F.G} = \frac{N_G (22.4 \times 10^3 \text{ cm}^3/\text{gm/mole})}{N_A} \quad \text{WHERE } N_A = 6.023 \times 10^{23} \frac{\text{ATOMS}}{\text{GM/MOLE}}$$

$$V_{F.G} = \frac{(8.77 \times 10^{19}) (22.4 \times 10^3)}{6.023 \times 10^{23}} = 3.26 \text{ cm}^3$$

HELIUM VOLUME AT S.T.P IS :

$$V_{He} = \frac{V_G 492^\circ K}{T_c} = \frac{(3.52)(492^\circ K)}{540^\circ K} = 3.20 \text{ cm}^3$$

ROD 'A': TOTAL GAS VOLUME AT S.T.P = 6.46 cm^3 = V_{STP}

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 50 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING

FISSION GAS RELEASE

ROD 'B'

$$V_{FG} @ STP = 1.35 \text{ cm}^3$$

$$\text{total } V_G = 3.81 \text{ cm}^3 @ STP$$

ROD 'C'

$$V_{FG} @ STP = 3.22 \text{ cm}^3$$

$$\text{total } V_G = 5.84 @ STP$$

GAS PRESSURE IN THE RODS AT END OF TEST, WITH RESULTING STRESSES

ROD 'A' $\bar{T}_{He} = 760^\circ K$

$$P_H = \frac{P_{STP} V_{STP} T_H}{V_H T_{STP}} = \frac{(14.7)(6.46)(760^\circ K)}{(1.23)(492^\circ K)} = 119.5 \text{ psi } \Delta P = 105 \text{ psi}$$

$$\sigma_{HOOP} = \frac{\Delta P D_H}{2t} = \Delta P(14.46) = \underline{1520 \text{ psi}}; \sigma_{TAN} = \underline{760 \text{ psi}}$$

ROD 'B' $\bar{T}_{He} = 660^\circ K$

$$P_H = \frac{(14.7)(3.81)(660^\circ K)}{(0.43)(492^\circ K)} = 175 \text{ psi}, \Delta P = 160 \text{ psi}$$

$$\sigma_{HOOP} = \frac{\Delta P D_H}{2t} = \Delta P(10.80) = \underline{1730 \text{ psi}}; \sigma_{TAN} = \underline{865 \text{ psi}}$$

ROD 'C' $\bar{T}_{He} = 760^\circ K$

$$P_H = \frac{(14.7)(5.84)(760^\circ K)}{(0.73)(492^\circ K)} = 182 \text{ psi}, \Delta P = 167 \text{ psi}$$

$$\sigma_{HOOP} = \frac{\Delta P D_H}{2t} = \Delta P(14.46) = \underline{2,410 \text{ psi}}; \sigma_{TAN} = \underline{1,205 \text{ psi}}$$

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 51 OF 75
CHECKED BY:		REPORT NO. TDR #8017
DATE: April 3, 1963		MODEL NO.

STRESS CALCULATIONS FOR THE PRIMARY FUEL CLADDING - SUMMATION

ROD 'A'

AT OUTER SURFACE: $S_{HOOP} = +13,800 + 1,520 = 15,320 \text{ psi (T)}$

$S_{TAN} = +13,800 + 760 = 14,560 \text{ psi (T)}$

AT INNER SURFACE: $S_{HOOP} = -13,800 + 1,520 = -12,280 \text{ psi (C)}$

$S_{TAN} = -13,800 + 760 = -13,040 \text{ psi (C)}$

ROD 'B'

AT OUTER SURFACE: $S_{HOOP} = +2,820 + 1,730 = 4,550 \text{ psi (T)}$

$S_{TAN} = +2,820 + 865 = 3,685 \text{ psi (T)}$

AT INNER SURFACE: $S_{HOOP} = -2,820 + 1,730 = -1,090 \text{ psi (C)}$

$S_{TAN} = -2,820 + 865 = -1,955 \text{ psi (C)}$

ROD 'C'

AT OUTER SURFACE: $S_{HOOP} = +13,800 + 2,410 = 16,210 \text{ psi (T)}$

$S_{TAN} = +13,800 + 1,205 = 15,005 \text{ psi (T)}$

AT INNER SURFACE: $S_{HOOP} = -13,800 + 2,410 = -11,390 \text{ psi (C)}$

$S_{TAN} = -13,800 + 1,205 = -12,595 \text{ psi (C)}$

THESE STRESSES ARE CALCULATED FOR THE 'END OF TEST' CONDITIONS, USING THE LATEST INFORMATION AVAILABLE FOR U-C SWELLING AND FISSION GAS RELEASE, REFERENCE 6.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 52 OF 75

APPENDIX VII

CORROSION FROM BF_3

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 53 OF 75

XI. CORROSION FROM BF_3

An experiment known as NAA-13 on the radiation decomposition of BF_3 and the resultant corrosion of the containing metals was irradiated¹⁶ in the MTR. Some of the results from this test are used to determine the depth of corrosion in the NAA-62 BF_3 annulus.

Experimental data in Reference 16 indicate that for the worst case, 2.35 millimoles of fluorine were liberated in a volume of 20 cm^3 at a pressure of 60 psia and an integrated flux of 8.6×10^{19} nvt. These assumptions are made for the following calculations:

1. A constant value of 300 psia in the BF_3 annulus, giving a pressure ratio of $\frac{300}{60} = 5$, is used.
2. The amount of fluorine liberated is directly proportional to the pressure and the integrated neutron flux.

$$\text{Amount of fluorine released} = \frac{2.35 \text{ millimoles}}{20 \text{ cm}^3} = 0.118 \frac{\text{millimoles}}{\text{cm}^3},$$

determined experimentally.

Scaling to this experiment, assuming an integrated flux of 14.5×10^{19} nvt, the

$$\begin{aligned} \text{Amount of } \text{F}_2 &= (0.118 \frac{\text{millimoles}}{\text{cm}^3}) \quad (5) \quad (\frac{14.5 \times 10^{19} \text{ nvt}}{8.6 \times 10^{19} \text{ nvt}}) \\ &= 0.995 \frac{\text{millimoles}}{\text{cm}^3} \end{aligned}$$

$$\text{Total } \text{F}_2 = 0.995 \frac{\text{millimoles}}{\text{cm}^3} \quad (888 \text{ cm}^3 \text{ in annulus})$$

Total F_2 liberated = 885 millimoles. NOTE: One molecule of F_2 removes one atom Fe. In the test described in Ref. 16, iron was the only constituent of stainless steel attacked.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 54 OF 75

Number of grams of stainless steel removed is:

$$M_{Fe} = nw$$

$$M_{Fe} = (885)(56)$$

$$M_{Fe} = 49500 \text{ mg} = 49.5 \text{ grams}$$

$$\begin{aligned} \text{Volume of stainless steel} &= V_{ss} = \frac{M_{Fe}}{P \rho_{\text{alloy}}} \\ &= \frac{49.5 \text{ grams}}{(0.74)(7.85 \text{ gm/cm}^3)} \\ &= 8.53 \text{ cm}^3 = .52 \text{ in}^3 \end{aligned}$$

where:

n = number of millimoles of F_2 available

w = combining weight in milligrams/millimole of F_2
= 56

P = percent of element in alloy
= 74%

ρ = density of alloy
= 7.85 gm/cm³

$$\begin{aligned} \text{Depth of corrosion} &= \frac{\text{Volume SS}}{\text{Surface Area}} = \frac{0.52 \text{ in}^3}{572 \text{ in}^2} = .91 \times 10^{-3} \text{ in} \\ &= .91 \text{ mils} \end{aligned}$$

NAA-62-1 was operated for 779 hours at an average gas pressure of 225 psia. During the hot cell examination of the irradiated assembly, inspection of the annulus walls revealed negligible corrosion from the BF_3 .

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 55 OF 75

APPENDIX VIII

NUCLEAR CALCULATIONS

- A. Flux Required in Fuel
- B. Advertised Flux Required
- C. Burn-up and Irradiation Time
- D. Flux Depression Across BF_3 Annulus
vs Pressure
- E. B^{10} Burn-out

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 56 OF 75

II. NUCLEAR CALCULATIONS

A. Flux Required in Fuel

The energy per fission released within the capsule pertinent to heat transfer calculations was considered to be 175 MeV or 2.66×10^{-14} Btu. The power generation required in the heat transfer analysis (Appendix 1) is 1.21×10^8 Btu/hr-ft³ for the hot 'rods'.

The macroscopic fission cross-section for U²³⁵ was computed as follows:

$$\Sigma_f = \frac{(\text{enrichment})(\text{UC density})(\text{weight \% U})(\sigma_f)(\text{non } 1/v \text{ "g"})(N_a)}{(\text{atomic wt})}$$

$$= \frac{(0.147)(13.5)(.952)(582 \times 10^{-24})(.975)(0.6023 \times 10^{24})}{235.1}$$

$$= 2.74 \text{ cm}^{-1} ; 2.8 \text{ cm}^{-1} \text{ for back 'cold' rod enriched 15\%}$$

The average flux required in the fuel was computed as follows:

$$\bar{\phi}_f = \frac{(3.54)(10^{10})(P)}{V \Sigma_f}$$
$$= \frac{(3.54)(10^{10})(30.9)(10^3)}{(24.7)(2.74)}$$

$$\bar{\phi}_f = 1.62 \times 10^{13} \text{ n/cm}^2\text{-sec.}$$

where: $(3.54)(10^{10})$ = fissions/watt-sec, based on 175 MeV/
fission remaining
in fuel.

P = watts/ft

V = cc/ft

$\Sigma_f = \text{cm}^{-1}$

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017
DATE April 3, 1963
PAGE 57 OF 75

Due to the inherent radial buckling of the thermal neutron flux in the ETR reflector (20-33%) across a test hole the 'coldest' rod would 'see' only (80%) Φ_f of the 'hot' rods. Hence the back rod would 'see' an average flux of $(.80)(1.62)(10^{13}) = 1.30 \times 10^{13}$ n/cm²-sec.

B. Advertised Flux Required

The unperturbed flux required is equal to the average flux required in the fuel divided by the perturbation factor. The unperturbed flux required as a function of BF₃ pressure is given below (based on a flux required in the fuel of 1.62×10^{13} n/cm²-sec); where f is the perturbation factor³:

BF ₃ Density gm/cm ³	Pressure psia @ 212°F	f	Unperturbed Flux Required x 10 ¹⁴
0.0003	1.47	.109	1.49
0.0024	14.7	.104	1.56
0.009	50.0*	.091	1.78
0.074	450.0	.0407	3.98

In order to insure that the flux is high enough to maintain control, the minimum flux expected during a reactor cycle in the chosen position should be 15% greater than the minimum unperturbed flux required of 1.78×10^{14} . This gives a value of $1.78 \times 10^{14} \times 1.15 = 2.02 \times 10^{14}$ n/cm²-sec. for the minimum midplane flux required in the position selected.

The maximum midplane flux in the selected position should not be 30% greater than the minimum, or 2.32×10^{14} n/cm²-sec. This maximum flux required is based upon the limitation of safe operating conditions in the event of loss of control rather than the maximum flux which could be easily handled, 3.98×10^{14} n/cm²-sec.

* 50 psia is the minimum expected operating gas pressure.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 58 OF 75

C. Burnup and Irradiation Time

A sample calculation is given below to show the time required for a peak burnup of 10,000 Mwd/MTU of UC operating continuously at the design peak power level of 30.9 kw/ft:

$$\begin{aligned} \text{BU (a/o)}_{235} &= \frac{\text{Total number } U_{235} \text{ atoms fissioned/gram fuel}}{\text{Number } U_{235} \text{ atoms/gram fuel}} \\ &= \frac{\left(\frac{\text{Fissions}}{\text{MWD}}\right) \left(\text{BU } \frac{\text{MWD}}{\text{MTU}}\right) (1 \text{ gm}) \left(10^{-6} \frac{\text{MTU}}{\text{gm}}\right)}{(1 \text{ gm})(\text{w/o enrichment})(N_a)/A} \quad \text{where} \end{aligned}$$

For Rod 'A'

$$\frac{\text{fissions}}{\text{MWD}} = 2.73 \times 10^{21} \quad (\text{w/o})_E = 14.7\%$$

$$\text{BU} = 10^4 \frac{\text{MWD}}{\text{MTU}} \quad N_a = 6.023 \times 10^{23} \frac{\text{atoms}}{\text{mole}}$$

$$A = 235 \text{ gm/mole}$$

$$\begin{aligned} \therefore \text{BU(a/o)}_{235} &= \frac{(2.73 \times 10^{21})(10^4)(1)(10^{-6})}{(1)(.147)(6.023 \times 10^{23})/235} \\ &= \frac{2.73 \times 10^{19} \text{ atoms fissioned / gm}}{3.77 \times 10^{20} U_{235} \text{ atoms in 1 gm of fuel}} \end{aligned}$$

$$\text{BU (a/o)}_{235} = .724 \times 10^{-1} \text{ or } 7.24\%$$

Rod 'B' will generate approximately 80% as much power as Rod 'A' hence, the burn-up will only be:

$$\text{BU (a/o)}_{U_{235}} = (7.24)(.8) = 5.79\%$$

Rod 'C' has a different enrichment than 'A' & 'B', ie., 14.95 w/o E instead of 14.7 w/o E, so:

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 5, 1963

PAGE 59 OF 75

$$BU(a/o)_{U_{235}} = (7.24) \frac{14.7}{14.95} = 7.12\%$$

The peak atom percent burnup of Rod 'A' is comparable to

$$\begin{aligned} \text{Rod 'A'} \frac{\text{peak fissions}}{\text{cm}^3} &= \rho \frac{\text{fissions}}{\text{gm}} = \left(13.77 \frac{\text{gm}}{\text{cm}^3} \right) \left(2.73 \times 10^{19} \frac{\text{fissions}}{\text{gm}} \right) \\ &= 3.76 \times 10^{20} \end{aligned}$$

$$\text{Rod 'B'} \frac{\text{peak fissions}}{\text{cm}^3} = 2.94 \times 10^{20}$$

$$\text{Rod 'C'} \frac{\text{peak fissions}}{\text{cm}^3} = 3.71 \times 10^{20}$$

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 60 OF 75

T_{BU} = Time for peak burnup days for Rod 'A'

$$T_{BU} = \frac{BU(MTU/Rod)}{(Power \text{ in } \frac{MW}{FT})(\frac{FT}{Rod})} = \frac{(10^4)(6.71 \times 10^{-4} \text{ MTU/Rod})}{(30.9 \times 10^{-3} \frac{MW}{FT})(\frac{26 \text{ in}}{12 \text{ in/ft}})}$$
$$= .100 \times 10^3$$

T_{BU} = 100 days @ 175 MW reactor power level

= 5 reactor cycles, based on a 21 day cycle

= 200 days at site with a .50 plant factor

D. Flux Depression Across BF_3 Annulus vs Pressure

The depression of flux across the BF_3 annulus as a function of pressure assuming infinite slab geometry was computed and the results are given in Figure 11 page 72.

A nuclear mock-up of an assembly containing three Th-7.6 w/o 93% enriched U, 0.4 in diameter rods, inside of the reference design BF_3 annulus was irradiated in the ASCR Critical Facility. The BF_3 used was not enriched. The results of these tests based on flux dosimeters inside and outside the BF_3 annulus extrapolated to enriched BF_3 are also given in Figure 11 page 72. The experimental and rough analytical points were recalculated since the original data package, Reference 1, using later cross-section data (from 3813 to 4017 barns) and BF_3 densities at 80°F, to better correspond with the actual Critical Facility temperature. The I_2 machine code points are off slightly since they were also calculated with the antiquated lower absorption cross-section. The Sn machine code agrees closely with the simple hand calculations indicating a 62% reduction across the annulus at 345 psia as compared to 59.5% indicated by the hand calculations. I_2 data indicates only 45% reduction, the lower results partly caused by use of a lower neutron cross-section. An attenuation of 70%, with the ~~attenuation~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 61 OF 75

pressurized to 425 psia, appears possible. However, the efficiency of the system was somewhat less than expected for NAA-62-1, which was operated previously in the Engineering Test Reactor.

Calculations based on data reduced from operation of NAA-62-1 indicate a 31% decrease in BF_3 density in the gas annulus caused by an increased average temperature of the gas. This decrease results in an estimated 21% loss of effective control. Analysis of the data indicate strongly that an apparent increase of temperature is caused by energetic fragments (${}^7_3\text{Li}$ and ${}^4_2\text{He}$) released during the $\text{B}^{10}(\text{n}-\alpha)\text{Li}^7$ reaction. Since the pressure equalizes in the whole gas system with different temperatures involved, the density decreases in the hot volumes and increases in the colder volumes. Assuming an initial supply of pure BF_3 gas, a reduction of 31% of the gas density is calculated when operating in the 300 psia range. The data are shown in Figure 13, page 73.

E. B^{10} Burnout Rate

The BF_3 pressure may increase with time so that a system purge might be needed to reduce the operating pressure. Pressure increase could be caused by burnout of the B^{10} in the annulus, resulting in addition of more BF_3 to the annulus by the control system to maintain control. The average flux in the BF_3 annulus will probably never exceed 10^{14} n/cm²-sec. Assuming an initial concentration, N_0 , the fraction of B^{10} left after one day would be:

$$\begin{aligned} N/N_0 &= e^{-\alpha \phi t} = e^{-(4017)(10^{-24})(10^{14})(8.64)(10^4)} \\ &= e^{-(3.47)(10^{-2})} = 0.966 \end{aligned}$$

The amount of burnup per day is then:

$$\text{BU} = 1 - 0.9659 = 0.034$$

$$\text{or } \% \text{ BU/day} = 3.4$$

FIGURE 1.

PREPARED BY:	ATOMICS INTERNATIONAL A DIVISION OF NORTH AMERICAN AVIATION, INC.	PAGE NO. 75 OF 75
CHECKED BY:		REPORT NO. DAR NO. 1017
DATE: April 4, 1958	FIGURE 2. Cross-section of 11-11-2	MODEL NO.

SCRIBE LINE FOR LOCATION
OF BOTTOM IN FUEL T/C'S

AL
CENTER OF
CORE

2.975-O.D. x 2.760-I.D. SS

.171 BF₃ ANNULUS

2.417-O.D. x 2.133-I.D. SS

AL SPACER

.060 H₂O
ANNULUS

3 FUEL RODS
26" LONG

60° CCW
FROM
SCRIBE A

C

B

.886-O.D. x .782-I.D. A-NICKEL

Na/K & T/C'S

.460-O.D. x .430-I.D.
SS-RODS "A" & "C"

.470-O.D. x .430-I.D.
321 ROD "B" ONLY

UC FUEL SLUGS
0.400 DIA x 3

Na

T/C RODS "A" & "C"

Figure 3 - Picture of Exploded Rod

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. NAA-SR-TDR-8017
DATE April 3, 1963
PAGE 65 OF 75

Figure 4 - Exploded View of Entire NAA-62-2 Assembly

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. NAA-SR-TDR-8017

DATE April 3, 1963

PAGE 66 OF 75

Figure 5 - Completed Fuel and BF₃ Annulus Assemblies

Figure 6 - Fuel Assembly with Junction Tube

PREPARED BY:

ATOMICS INTERNATIONAL

A DIVISION OF NORTH AMERICAN AVIATION, INC.

PAGE NO. 68 OF 75

CHECKED BY:

REPORT NO. TDR #8017

DATE: April 3, 1963

Figure 7. Thermocouple Layout and Resistance Check for NAA-62-2.

MODEL NO.

TEMP. RECORDER #1

HIGH TEMP. RECORDER

Terminal No.	T/C No.	Final Loop Resistance Reading
1	617	143.8 Ω
2	619	155.5 "
3	629	144.0 "
4	623	149.8 "
5	625	159.4 "
6	627	149.9 "
7	629	"
8	662	149.7 "
9	612	148.0 "
10	618	154.9 "
11	622	148.8 "
12	617	"
13	624	150.7 "
14	663	145.9 "
15	B	OPEN
16	661	152.1 "
17	627	"
18	A	150.3 "
19	613	145.4 "
20	B	"
21	612	"
22	628	150.3 "
23	621	146.3 "
24	A	"

NOTE: B

MUST BE ADJUSTED
IF OPEN THROUGH
IT READS OPEN.

Terminal No.	T/C No.	Final Loop Resistance Reading
1	664	16.26 Ω
2	665	15.68 "
3	666	20.10 "
4	667	19.40 "
5	664	etc.
6	665	"
7	666	"
8	667	"
9	664	"
10	665	"
11	666	"
12	667	"
13	664	"
14	665	"
15	666	"
16	667	"
17	664	"
18	665	"
19	666	"
20	667	"
21	664	"
22	665	"
23	666	"
24	667	"

○ Chromel-Alumel; ⊕ Platinum-platinum-rhodium; ⊙ Control T/C; ⊗ Scram actuating T/C. T/C #614, Rod 'A', is to be used initially as the controlling thermocouple for the recorder controller & T/C #660 is to be used as

N 152-R-2 the scram actuating T/C for the scram protection recorder.

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. TDR-8017
DATE April 3, 1963
PAGE 69 OF 75

Figure 8 - Picture of Instrument Console

Figure 9 - Scram Circuitry Terminals

NOTE: 1. Fueled with 0.400" diameter Th 7.6 w/o U, 93% enriched.
2. Aluminum filler pieces replaced the normal coolant annuli.
3. The test was operated with natural BF₃ gas, i.e., 18% enriched in the isotope B¹⁰.

Figure-10 - Nuclear Mock-up of the NAA-62-2 Assembly

Figure 11. Thermal Neutron Attenuation Across the BF_3 Annulus

Figure 12 . Block Diagram of the BF₃ Thermal Neutron Flux Control System.

PREPARED BY:
CHECKED BY:
DATE: April 3, 1963

ATOMICS INTERNATIONAL
A DIVISION OF NORTH AMERICAN AVIATION, INC.

PAGE NO 73 OF 75
REPORT NO TDR #8017
MODEL NO

Figure No. 13 BF_3 Pressure and Density Change in the Annulus as a Function of Reactor Power Level

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. TDR #8017

DATE April 3, 1963

PAGE 75 OF 75

1. Brooks, H.B., "Design of NAA-62-1 and -2", NAA-SR-TDR #6076, January 1, 1961.
2. McCarty, W.K. & Vawter, D.D., "Operations Manual for NAA-62-2", NAA-SR-TDR #8337.
3. Roberts, R., "Perturbation Calculations for NAA-62-2", NAA-SR-TDR #8227, March 3, 1963.
4. Valvovage, W.D., Baldwin, E.E., "Materials Manual", KAPL-A-ME-1, January 1, 1954.
5. Thompson, J.G., Nickel and Its Alloys, NBS Circular 592 (United States Department of Commerce).
6. Arneson, S.O. & Schmitt, A.R., Department 733-32, Atomics International, personal communication.
7. Wagner, R.K., "Mechanical Properties of 3Z1 Alloy", NAA-SR-6431, 1961.
8. Begley, R.J., "Hydraulic Test of ASCR Prototype Element in a Simulated ETR 'A' Piece", TDR #5362, June 3, 1960.
9. McCarty, W.K., "Boron Tri-fluoride - A Resume of Its Properties and Characteristics", Atomics International Internal Document.
10. AEC Report #AECU-3548, Hooker Electrochemical Company, Niagara Falls, New York.
11. Booth, H.S. & Martin, D.R., "Boron Tri-fluoride and Its Derivatives", John Wiley & Sons, Inc, 1949.
12. Unpublished calculations by G. Mellott, Department 793-31, Atomics International.
13. Nertney, R.J., ed, "Calculated Surface Temperatures for Nuclear Systems and Analysis of their Uncertainties", IDO 16343, June 1, 1957.
14. Jacobs, R.T., Merrill, J.A., & Nertney, R.J., "Application of Statistical Methods of Analysis and Experimental Design in Predicting Burnout Heat Flux", IDO 16460, June 30, 1960.
15. Roark, R.J., Formulas for Stress and Strain, (Third edition, McGraw-Hill, The Maple Press, 1954).
16. McCarty, W.K., "Experimental Determination of the Radiation Decomposition of B¹⁰ Enriched BF₃ and the Resultant Corrosion of the Containing Materials", NAA-SR-1999, October 15, 1957.