RECEIVED APR 1 1975

U. S. ATOMIC ENERGY COMMISSION
MAJOR CONTRACTOR'S RECOMMENDATION FOR
DISPOSITION OF SCIENTIFIC AND TECHNICAL DOCUMENT

(See Instructions on Reverse Side)

1. AEC REPORT NO. BNL 19785	3. TITLE INCOHERENT TRANSVERSE SPACE CHARGE EFFECTS DURING INJECTION, RF CAPTURE AND EARLY ACCELERATION IN AGS
2. SUBJECT CATEGORY NO. UC28	

4. TYPE OF DOCUMENT (Check one):

☐ a. Scientific and technical report.☒ b. Conference paper not to be published in a journal:Title of conference 1975 Particle Accelerator ConferenceDate of conference March 12-14, 1975Exact location of conference Washington, D.C.Sponsoring organization APS, NSF, ERDA☐ c. Other (Specify) _____

5. COPIES TRANSMITTED (Check one or more applicable boxes):

☐ a. Copies being transmitted for standard distribution by AEC - DTI.☐ b. Copies being transmitted for special distribution by AEC - DTI, per attached list.☒ c. Two reproducible copies being transmitted to AEC - DTI.

6. RECOMMENDED DISTRIBUTION (Check one):

☒ a. Normal handling (after patent clearance): no restraint on distribution except as may be required by the security classification.☐ b. Normal handling in the U.S. (after patent clearance), but no foreign distribution.☐ c. Make available only to U.S. Government agencies and their contractors.☐ d. Make available only within AEC and to AEC contractors.☐ e. Make available only within AEC☐ f. Make available only to those listed in item 11., below.☐ g. Other (Specify) _____

7. RECOMMENDED ANNOUNCEMENT (Check one):

☒ a. Normal procedure may be followed.☐ b. Recommend following announcement limitations: _____

8. REASON FOR RESTRICTIONS RECOMMENDED IN 6. OR 7. ABOVE:

9. PATENT CLEARANCE (Check one):

☒ a. AEC patent clearance has been granted by responsible AEC patent group.☐ b. Document has been sent to responsible AEC patent group for clearance.

10. DEFENSE INFORMATION (For classified document only. Check one):

Document a. ☐ does b. ☐ does not contain defense information other than restricted data.

11. ADDITIONAL INFORMATION OR REMARKS (Continue on separate sheet if necessary.):

12. SUBMITTED BY: NAME AND POSITION (Please print or type)

J. Claus, Physicist

Organization

ACCELERATOR DEPARTMENT
BROOKHAVEN NATIONAL LABORATORY

Signature

J. Claus

Date

February 28, 1975

INSTRUCTIONS

Who uses this Form: All AEC contractors except those specifically instructed by their AEC contract administrator to use the shorter Form AEC-427.

When to use: Submit one copy of this form with each document (except reprints of journal articles) or with each bulk shipment which is sent to AEC's Division of Technical Information (DTI) in accordance with the requirements of AEC Manual Chapter 3201. The Chapter specifies that preprints and manuscripts of journal articles, and manuscripts of conference papers which are to be published in a journal in substantially the same form and detail should not be sent to DTI. Reprints of journal articles may be sent to DTI, but no transmittal form should be used with reprints.

Where to send: Forward this form and the document(s) to:

USAEC - Technical Information
P. O. Box 62
Oak Ridge, Tennessee 37830

Item instructions:

- Item 1.** The first element in the number shall be a code to be determined as follows: (a) The responsible field office may request DTI approval of a unique code for a contractor, e.g., BNL, BMI, ORNL, etc.; (b) A program division may request DTI approval of a unique code for a program or series of reports, e.g., PNE, VUF, etc.; (c) An operations office may instruct a contractor to use the code approved for the operations office, i.e., NYO, COO, ORO, IDO, SRO, SAN, ALO, RLO, NVO; and (d) Program divisions shall use the code WASH for reports which they themselves prepare.

The code shall be followed by a sequential number, or by a contract number plus a sequential number, as follows: (a) Contractors or programs with unique codes may complete the report number by adding a sequential number to the code, e.g., ORNL-101, ORNL-102, etc.; or PNE-1, PNE-2, etc.; or they may add the identifying portion of the contract number and a sequential number, e.g., ABC-2105-1, ABC-2105-2, etc.; (b) Contractors using the operations office code shall complete the report number by adding the identifying portion of the contract number and a sequential number, e.g., NYO-2200-1, NYO-2200-2, etc.; and (c) Program divisions using the WASH code shall complete the report number by adding a sequential number which they request from DTI's Document Management Branch in Oak Ridge.

- Item 2.** Insert the appropriate subject category from TID-4500 ("Standard Distribution for Unclassified Scientific and Technical Reports") or M-3679 ("Standard Distribution for Classified Scientific and Technical Reports") for both classified and unclassified documents, whether or not printed for standard distribution.

- Item 3.** Give title exactly as on the document itself unless title is classified. In that case, omit title and state "classified title" in the space for item 3.

- Item 4.** If box c is checked, indicate type of item being sent, e.g., thesis, translation, computer program, etc.

- Item 5.** a. The number of copies specified for the appropriate category or categories in M-3679 or TID-4500 shall be forwarded to DTI for distribution.

b. If box c is checked, at least one copy shall be original ribbon or offset and be completely legible. A clear carbon copy is acceptable as a second reproducible copy.

- Item 6.** If box a is checked for an unclassified document, it may be distributed (after patent clearance) to addressees listed in TID-4500 for the appropriate subject category, to AEC depository libraries in the U.S. and abroad, to the Clearinghouse for Federal Scientific and Technical Information for sale to the public, and to authorized foreign recipients.

If box a is checked for a classified document, it may be distributed to addressees listed in M-3679 for the appropriate subject category.

If a box other than a is checked, the recommended limitation will be followed if not inconsistent with AECM-2104, "Information for Official Use Only", and unless DTI receives other instructions from the responsible AEC program division.

Box g may be checked in order to specify special instructions, such as "Make available only as specifically approved by the program division", etc.

- Item 7.** a. Announcement procedures are normally determined by the distribution that is to be given a document. If box a or b in item 6 is checked for an unclassified document, it will normally be listed in DTI's "Weekly Accessions List of Unlimited Reports" (TID-4401) and may be abstracted in "Nuclear Science Abstracts" (NSA).

A classified document, or an unclassified document for which box c, d, e, f, or g is checked, will normally be listed in DTI's "Weekly Accessions List of Limited Distribution Reports" (TID-4400) and may be abstracted in "Abstracts of Limited Distribution Reports" (ALDR).

b. Check 7b if the normal announcement procedures described in 7a are not appropriate and indicate recommended announcement limitations.

- Item 8.** If a box other than a is checked in item 6, or if 7b is checked, state reason for the recommended restriction, e.g., "preliminary information", "prepared primarily for internal use", etc.

- Item 9.** It is assumed that there is no objection to publication from the standpoint of the originating organization's patent interest. Otherwise explain in item 11.

- Item 10.** The purpose of this item is to determine whether a given classified document can be distributed to access permittees. If box a is checked, it cannot be made available to them (Code of Federal Regulations, 10 CFR, Part 35, subpart 25.6); if box b is checked, DTI will determine whether or not to make it available.

- Item 11.** Use this space if necessary to expand on answers given above, e.g., item 6f and item 9.

- Item 12.** Enter name of person to whom inquiries concerning the recommendations on this form may be addressed.

Conf-150335-49

INCOHERENT TRANSVERSE SPACE CHARGE EFFECTS
DURING INJECTION, RF CAPTURE AND EARLY ACCELERATION IN AGS

J. Claus
Brookhaven National Laboratory
Upton, New York 11973

MASTER

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

By acceptance of this article, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INCOHERENT TRANSVERSE SPACE CHARGE EFFECTS DURING INJECTION, RF CAPTURE AND EARLY ACCELERATION IN AGS*

J. Claus
Brookhaven National Laboratory
Upton, New York 11973

Summary

After a review of the present situation in the AGS incoherent space charge effects in respectively the just injected beam, the coasting beam and the bunched beam are considered. Numerical estimates of shifts and spreads in betatron frequencies are given. The ratio of peak to average azimuthal densities in bunched beams is calculated for parabolic and uniform initial energy distributions. It is concluded that the intensity limit of the AGS is probably set by loss of particles out of vertical betatron phase via resonances and coupling in the early bunched beam.

Present Status of AGS

On several occasions dc beams of 2×10^{13} protons (i.e. with a uniform azimuthal density of 2.5×10^{10} protons/m) have been circulating in the AGS for up to a few hundred revolutions. All dc beams are eventually lost on the inner vacuum chamber wall because the rate of rise of the guiding field cannot be reduced to zero. From the loss patterns of beams with 2×10^{13} protons one concludes that such beams occupy most of the horizontal aperture. Attempts to accelerate them have consistently met with very poor capture and accelerating efficiencies, typically less than 10%. In general that efficiency decreases increasingly quickly with increasing circulating beam intensity (= intensity before capture begins); the highest accelerated intensity of 9.5×10^{12} protons/pulse was achieved with a circulating beam of $\sim 1.6 \times 10^{13}$ and $8-9 \times 10^{12}$ is obtained with less than 1.4×10^{13} . The loss of rf efficiency with increasing intensity cannot be fully explained with the loss in betatron aperture due to bunching. Typical loss patterns show after small initial losses during the first 60 revolutions after injection terminates and totaling < 10% of initial intensity a sharply increased loss rate correlated with the gap-voltage amplitude program for some 200 revolutions. This takes of the order of 25%. The rate decreases to zero gradually during the following 10,000 or more revolutions. This takes another 5% so that the net efficiency is of the order of 60% for an initially circulating beam of 1.4×10^{13} protons.

The intensity of the beam to be injected has been as high as 70 mA (of 200 MeV protons), during normal operations it is somewhere between 40 and 60 mA, and no clear optimum has been established. The emittance increases somewhat with current, half of a 50 mA beam falling inside the $1\pi \times 10^{-6}$ rad-m contour and 0.8 of it inside $3\pi \times 10^{-6}$ rad-m. It is injected during 20-25 revolutions usually leaving some of the horizontal aperture free by having the injection closed orbit somewhat on the outside of the center of the aperture and by deliberately not injecting during the last several revolutions of the available injection period. After the first 25-30% of the injection period the circulating beam increases about linearly in intensity while injection progresses until the end of the process, suggesting that a constant charge is added each turn. This behavior does not depend very strongly on the shape of the horizontal emittance at the inflector exit (i.e. eccentricity and orientation of major axis).

Since the rate of closed orbit motion in the neighborhood of the inflector (= bump collapse rate) necessary for stacking in betatron phase space is nearly constant and chosen to have even the largest partial acceptance flooded by a properly adjusted horizontal emittance ellipse of the injected beam, one would expect the circulating beam to increase quadratically rather than linearly.

In the early part of the injection period in particular, the way in which the circulating beam increases is affected by the excitation of the two bump magnets, bending magnets, one about a quarter betatron wavelength upstream of the inflector exit, the other a quarter wavelength downstream of it, which together produce the variable bump in the closed orbit at inflector azimuth. These magnets are excited by half sinusoidal currents whose relative amplitudes and phases would seem to be important for the development of the partial acceptance. In practice timing appears to be more important than amplitude ratio and neither arrives at theoretical values during tuning for maximum intensity.

Although the injected beam is known to be 1.5-2 cm high at the exit of the inflector (calculated from emittance measurement and supported by flag observation) it increases by a factor 2-3 within the first few hundred revolutions. This is not caused by obvious vertical steering errors and/or maladjustment of the vertical emittance, and seems even fairly independent of these parameters.

The energy characteristics, i.e. central energy and distribution, of the linac beam appear to be of prime importance.

Space Charge Effects in Injected Beam

Space charge effects in the just injected beam tend to invalidate previous considerations on multiturn stacking in betatron phase space since these were based on linear transformations.^{1,2} The motion of particles inside an azimuthally short sample of the just injected beam is subject to external forces, i.e. the guiding field, the self-field of any already circulating beam, the self-field of any later injected circulating beam and to internal forces, i.e. the self-field of the sample itself. If the nonlinearities in the external forces are small enough to neglect the differences of their effects on individual particles in the sample for the several revolutions necessary to define the partial acceptance for that sample, the betatron motion of those particles may be described as the superposition of one with respect to the sample's axis and one of that axis with respect to the closed orbit. Each motion is a rotation in a properly normalized transverse phase space, the rate of rotation about the axis is less than the rate of rotation of the axis about the closed orbit in the presence of space charge. The instantaneous rotation rate about the axis is a function of the radial and axial excursion with respect to that axis. In Appendix A we calculate to first order the frequency shifts as functions of the amplitudes for a circular cylindrical beam matched to the external focusing system, with a uniform population in four dimensional phase space, neglecting image effects. Applying the result to the AGS for the injected beam, assuming a beam current of 0.8×50 mA inside two dimensional emittance of $3\pi \times 10^{-6}$ rad-m, one finds a frequency spectrum

*Work performed under the auspices of the U.S. Energy Research and Development Administration.

that stretches from $v=0.31$ for particles with negligible amplitudes with respect to the sample axis in either plane to $v=0.09$ for particles with maximum excursions in each plane. The first shift is twice as large as would be found for a beam of equal dimensions and current but uniformly populated in real space. Since the actual distribution in four dimensional phase space is peaked towards the center, space charge defocusing is more nonlinear than assumed and the maximum frequency shift therefore larger.

These tune shifts cause deviations from expected transverse positions on successive revolutions and make it impossible to fully populate the partial acceptances defined by linear theory. They also distort the shapes of the partial acceptances and make their boundaries vague. As a result, the acceptance of the accelerator cannot be populated to the density of the injected beam.

Because image effects were neglected in this calculation, the frequency shifts obtained are likely to be smaller than the real ones, perhaps by 20%.³

Space Charge Effects in Circulating Beam

Space charge effects in circulating beams have been treated extensively in the literature.³⁻⁵ In³ tune shifts were calculated for a 200 MeV proton beam of 2.5×10^{10} protons/m in approximated AGS geometry, assuming half cosine distributions, axially and radially, in real space. In four dimensional phase space such distributions are about 50% denser in the center than uniform ones. These calculations take electric and magnetic image effects into account. For beam dimensions of $10 \times 6 \text{ cm}^2$ it was found that the space charge tune shifts follow from

$$\Delta\nu_x = -0.053 (1 - 0.0965 \hat{x}^2), \quad \hat{y} = 0$$

$$\Delta\nu_y = -0.283 (1 - 0.070 \hat{y}^2), \quad \hat{x} = 0$$

in the two planes of symmetry. Here $\hat{x}$ and $\hat{y}$ are the betatron amplitudes in cm (x = radial, y = axial). These results apply after the axial (= vertical) beam blow-up, mentioned earlier, has taken place. During and immediately after injection the beam should only be 1.5-2 cm high. Since the tune shifts are about proportional to charge density and the aspect ratio of the physical cross section is larger than assumed in the calculation one would expect the calculated maximum shifts $\Delta\nu_y$ to reach -1. immediately after injection. Under such conditions rapid axial blow-up is to be expected.

Space Charge Effects in Bunched Beams

The image effects in bunched beams are complicated by the difference in boundary conditions for the dc and ac components of the self-fields. The vacuum chamber wall represents the boundary for both the dc and ac components of the electric field, as well as for the ac component of the magnetic field. The dc component of the magnetic field is bounded by the iron of the guiding field magnets and free space, provided there are no other iron structures nearby nor dc currents flowing in the vacuum chamber walls. This complication is especially noticeable in moderately bunched beams, where the ac component is not much larger than the dc one. For an intensity of 2×10^{13} in the AGS and a local-to-average density ratio equal to 2^8 calculates

$$\Delta\nu_x = -0.1435 (1 - 0.053 \hat{x}^2), \quad \hat{y} = 0$$

$$\Delta\nu_y = -0.519 (1 - 0.099 \hat{y}^2), \quad \hat{x} = 0$$

The zero amplitude shift in axial direction is very large, but reduces to -0.05 for motion of maximum amplitude ($= 3 \text{ cm}$).

Azimuthal Density Distributions

In view of the importance of the azimuthal density distribution a computer program was written to study this in dependence of the energy distribution in the injected beam, the synchronous energy in the accelerator as determined by guiding field and rf frequency, peak energy gain per turn and rate of acceleration. Assuming adiabatic processes throughout, the program maps the (azimuthally uniform) energy distribution that exists before capture begins onto accelerating buckets with specified characteristics. Thereafter it projects the resulting distribution onto the phase (= azimuthal) axis, yielding the azimuthal density distribution.

Fig. 1

In Fig. 1 the ratio $\hat{\lambda}/\lambda$ of the peak and average densities as function of the difference E_0 between the central energy in the coasting beam and the synchronous energy. Curve 1 refers to stationary buckets, i.e. to zero energy gain per turn, curve 2 to 15 keV/turn. The central energy in the coasting beam is 200 MeV, the energy distribution parabolic with a base width of 500 keV.

TABLE I

keV/Turn ES+EO	0	15	150
500 + 0	1.97	2.65	4.03
270 + 110	1.60	2.24	3.37
500, Unif	1.57	2.21	3.34
920 + 0	1.97	2.32	3.19
500 + 210	1.55	1.88	2.57

Other results have been assembled in Table I where columns represent different accelerating rates and rows $\hat{\lambda}/\lambda$ as function of energy spread ES and energy offset EO. The first three rows refer all to beams with a maximum energy error of $\approx 500 \text{ keV}$, the first two with parabolic distributions, the third one with a uniform distribution. The last two rows refer to beams with a maximum energy error of 920 keV. In all cases the accelerating voltage has been chosen to yield a capture

efficiency between 0.99 and 1. Inspection of the results shows that capture of a beam with a parabolic distribution and an energy offset yields peak densities very nearly as low as that of an uniformly populated beam without offset and the same maximum error with respect to the synchronous energy. Both are rather lower than a parabolic beam without offset and the same energy spread as the uniform one. It may also be seen that larger energy spreads yield lower densities and that the densities increase with the rate of acceleration. Since the space charge induced tune shifts are proportional to $\lambda/(\sqrt{v^2-1})$ it follows that for constant shift λ may increase as $\sqrt{v^2-1}$ in first order. The relationship differs from $\lambda/\beta^2\gamma^3$ which might be expected because the area of the beam cross section decreases as $\sqrt{v^2-1}$. It allows to calculate the acceptable increase in the rate of acceleration with energy.

Discussion and Conclusion

It follows from the calculations presented that transverse space charge effects play already a fairly severe role in the early part of the cycle of the AGS at normal intensities (up to 8.5×10^{12} accelerated). In order to limit the shifts in the vertical betatron frequencies to $|\Delta\nu| \leq 0.3$ the azimuthal peak charge density must remain below $\sim 3 \times 10^{13}$ protons/m. Since it seems possible to limit λ/λ_0 to < 2.5 by proper rf techniques this corresponds with an acceleratable beam of $\sim 1.2 \times 10^{13}$ protons. Assuming that these techniques yield also capture efficiencies of the order of 80%, an accelerated intensity of 1.2×10^{13} would require a coasting beam of 1.5×10^{13} . Beams with such intensities have been fairly common practice for some years now. They might still be unsuitable in terms of their cross sectional charge distributions however.

Whether beams with frequency shifts up to 0.3 can be maintained during early acceleration depends upon the amplitude growth rates as set by the stopband structure and horizontal/vertical coupling. Since both betatron frequencies of most particles are modulated by the differences of their averages and in addition by twice a synchrotron frequency, many particles will be driven repeatedly across resonances and change their betatron amplitudes.⁷ Such changes will modify the cross sectional charge distributions and the betatron frequency distributions with them. They may also modify details of the stopband pattern because part of the pattern is generated by the beam itself via image effects⁵ in azimuthally non-uniform structures close to it (e.g. injection and extraction magnets, ferrite structure of bump magnets, pick-up electrodes, variations in vacuum chamber cross section).

It appears that maximizing the accelerated intensity depends on several factors: Control of injection and rf capture to minimize the peaks in the density distribution, reduction of stopband widths and horizontal/vertical coupling to reduce growth rates, control of acceleration such that a maximum number of particles survives the process.

References

1. J. Claus, "AGS Injection with 200 MeV Linac", BNL Inf. Report 15646, Jan. 12, 1971.
2. J. Claus et al., "Multiturn Injection Into the Converted AGS", IEEE Trans. Nucl. Sci. Vol. 3, NS-20, 342 (1973).
3. L.J. Laslett, "Intensity Limitations Imposed by Transverse Space-Charge Effects in Circular Particle Accelerators", Proc. 1963 Summer Study on Storage Rings, Accelerators and Experimentation at Super-High Energies, BNL Report 7534, 324 (1963).
4. I.M. Kapchinsky and V.V. Vladimirovsky, "Limitations

of Proton Beam Current in a Strong Focusing Linear Accelerator Associated with the Beam Space Charge", Proc. Conf. on H.E. Accel. and Inst., CERN, 274, (1959).

5. L.C. Teng, "Transverse Space Charge Effects", Argonne Report ANLAD-59, Feb. 1960.
6. P.M. Lapostolle, "Champ et Potentiel de Charge d'Espace Produit par un Faisceau de Section Elliptique dans un Tube Metallique Egalement Elliptique", CERN Report AR/Int. SG/65-27, Nov. 11, 1965.
7. F.J. Sacherer, "Transverse Space-Charge Effects in Circular Accelerators", (Thesis) LRL Report UCRL 18454, Oct. 30, 1968.
8. J. Claus, "Space Charge in the AGS and Some of its Consequences", BNL Inf. Report BNL 18113, Aug. 6, 1973.

Appendix A

Betatron Tune Shifts in Cylindrical Beam

Assuming a spherical distribution in four space with uniform density d and radius ρ one obtains for the density $\lambda(r)$ in real space $\lambda(r) = d\pi(\rho^2 - r^2)$, $r < \rho$
 $\lambda(r) = 0$, $r > \rho$.
 Thus the charge $\lambda(r)$ inside a cylinder of radius r is $\lambda(r) = d\pi r^2(\rho^2 - \frac{1}{2}r^2) = 2\Lambda(r/\rho)^2(1 - \frac{1}{2}(r/\rho)^2)$ with Λ the total charge per unit length. For the x and y components of the electric field one finds

$$E_x = \frac{\Lambda}{\pi\epsilon_0} \frac{x}{\rho^2} \left(1 - \frac{1}{2} \frac{x^2 + y^2}{\rho^2}\right)$$

$$E_y = \frac{\Lambda}{\pi\epsilon_0} \frac{y}{\rho^2} \left(1 - \frac{1}{2} \frac{x^2 + y^2}{\rho^2}\right)$$

The betatron motion of a test particle in free space (no image effects) follows from

$$x'' + (v_x/R)^2 \left(1 - \frac{\Lambda}{\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \left(\frac{R}{v_x}\right)^2\right) x = - \frac{\Lambda}{2\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \frac{x^3 + y^2x}{\rho^2}$$

$$y'' + (v_y/R)^2 \left(1 - \frac{\Lambda}{\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \left(\frac{R}{v_y}\right)^2\right) y = - \frac{\Lambda}{2\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \frac{x^2y + y^3}{\rho^2}$$

Applying the method of Krylov, Bogoljubov and Mitropolskii one finds for the frequency shifts to first order:

$$\Delta\nu_x = \Delta\nu_{x0} \left[1 - \left[\frac{3}{8} \left(\frac{\hat{x}}{\rho}\right)^2 + \frac{1}{2} \left(1 + \frac{1}{2} \cos(2(\hat{v}_x - \hat{v}_y)\frac{R}{v_x} + \theta)\right) \right] \left(\frac{\hat{x}}{\rho}\right)^2 \right] \frac{v_x}{v_x}$$

$$\Delta\nu_y = \Delta\nu_{y0} \left[1 - \left[\frac{3}{8} \left(\frac{\hat{y}}{\rho}\right)^2 + \frac{1}{2} \left(1 + \frac{1}{2} \cos(2(\hat{v}_x - \hat{v}_y)\frac{R}{v_y} + \theta)\right) \right] \left(\frac{\hat{y}}{\rho}\right)^2 \right] \frac{v_y}{v_y}$$

$$\text{where } \Delta\nu_{x0} = - \frac{1}{2} \frac{\Lambda}{\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \frac{R^2}{v_x}$$

$$\Delta\nu_{y0} = - \frac{1}{2} \frac{\Lambda}{\pi\epsilon_0\rho^2} \cdot \frac{1}{\beta^2\gamma^3} \cdot \frac{1}{E_0} \cdot \frac{R^2}{v_y}$$

represent the zero amplitude shifts and where

$$\hat{v}_x = v_x + \Delta\nu_{x0}$$

$$\hat{v}_y = v_y + \Delta\nu_{y0}$$

$2\pi R$ is the circumference of the accelerator, v_x and v_y

its unperturbed betatron frequencies, β , γ the usual relativistic velocity and energy and ρ the velocity of light.

It may be seen that the space charge induced octupole causes the betatron frequencies for most particles, (i.e. those with $\hat{x} \neq 0$ and $\hat{y} \neq 0$) to be modulated with twice the difference in betatron frequencies. In the extrema and with $\Delta v_0 \ll v$:

$$\Delta v_x = \Delta v_{x0} \left[1 - \left\{ \frac{3}{8} (\hat{x}/\rho)^2 + \frac{1}{2} (1 \pm \frac{1}{2}) (\hat{y}/\rho)^2 \right\} v_x \right]$$

$$\Delta v_y = \Delta v_{y0} \left[1 - \left\{ \frac{3}{8} (\hat{y}/\rho)^2 + \frac{1}{2} (1 \pm \frac{1}{2}) (\hat{x}/\rho)^2 \right\} v_y \right] .$$