~~CONFIDENTIAL~~

PO-C

^{#3}
Dutli

Westinghouse
Astronuclear
Laboratory

MASTER

WANL-TME-1962

August 1969

DATA ITEM S-54

NUCLEAR SUBSYSTEM
THROTTLING (U)

TRADE STUDY NO. 706

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It has been reproduced from the best available copy to permit the broadest possible availability.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

~~CONFIDENTIAL~~

~~RESTRICTED DATA~~

~~UNCLASSIFIED~~

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

3

MASTER

Subcontract NP-1

WANL-TME-1962

August, 1969

16

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Westinghouse Astronuclear Laboratory

CODE IDENT NO. 14683

COPIES OF THIS REPORT ARE AVAILABLE IN
has been re-evaluated and is now available
copy to the public at a special price of \$1.00 per copy.

SPECIAL REVIEW
FINAL DETERMINATION
Class: U

Reviewer: JRP
Class: U
Date: 4-24-82

DATA ITEM S-54

**NUCLEAR SUBSYSTEM
THROTTLING (u)**

TRADE STUDY NO. 706

~~GROUP 1~~
~~EXCLUDED FROM AUTOMATIC DOWNGRADING~~
~~AND DECLASSIFICATION~~

Classification cancelled (or changed to) _____
by authority of DOE
HA. C. 10. 02 SEP 10 1973

APPROVED BY:

F. D. Retallick
F. D. Retallick

Manager, NERVA Systems Management

INFORMATION CATEGORY
Confidential
Declassify on: 9/10/69
AUTHORIZED CLASSIFICATION DATE

~~CONFIDENTIAL~~

~~RESTRICTED DATA~~

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ACKNOWLEDGMENT

Prepared by:

R. E. Thompson
Technical Assistant
Systems Analysis

This page is Unclassified

TABLE OF CONTENTS

Section		Page
	Abstract	iii
1	Scope	1-1
2	Identification of Requirements	2-1 thru 2-4
3	Description of Approaches and Significant Characteristics	3-1
4	Comparison Matrix	4-1 thru 4-4
5	Recommendation	5-1
6	References	6-1

BLANK

This page is Unclassified

ABSTRACT

This report presents the results of an evaluation of the Nuclear Subsystem (NSS) for throttling at high specific impulse (at rated chamber temperature). The objective of the study was to analyze the NSS high I_{sp} throttling performance and its effects on the NSS design and to establish an NSS recommendation on high I_{sp} throttling based upon these analyses.

Four operating points were considered in this evaluation. Three were specific throttling points and the fourth was a no-throttling condition. The evaluation of the effects of high I_{sp} throttling on the NSS resulted in the recommendation that no specific requirement for high I_{sp} throttling operation be imposed on the design. This recommendation is based on the fact that no major advantage was identified for throttling while incorporation of throttling requirements adversely affects the NSS design and reliability. The most significant NSS penalty is that of fuel corrosion. The requirements on the SSCV and control drum span are more severe for throttling than for the no-throttling case. Another significant disadvantage is that of the requirement for a more complex control operating mode over the no-throttling case.

This recommendation does not rule out the fact that capability for high I_{sp} throttling may exist in the final design and capability for reduced temperature throttling will certainly exist. However, because of the relative advantages and disadvantages identified, any throttling in the final design should be that which is available when the most reliable and best performing NSS is determined based upon rated condition considerations.

This page is Unclassified

1. SCOPE

This trade study identifies and evaluates advantages and penalties for the NSS during high specific impulse throttling with regard to throttling point and throttling time. The study also results in a recommendation on throttling based upon NSS considerations.

~~CONFIDENTIAL~~

~~RESTRICTED DATA~~

This page is Unclassified

2. IDENTIFICATION OF REQUIREMENTS

The requirement to perform high I_{sp} throttling is stated in the NPRD -1, dated June 5, 1968, in the following manner.

The engine shall be capable of throttling at rated chamber temperature from the engine design point of 450 psia chamber pressure to a chamber pressure of (tbd) psia at a maximum rate of 50 psi/second for a duration of (tbd) minutes.

Subsequent direction was provided in Technical Directive 69-06, dated February 14, 1969. This direction stated that certain specified requirements as given in the NPRD -1 were subject to verification by the Contractor. The specified requirements in the area of throttling to be verified were:

- a. Throttled Chamber Pressure (tbd) psia
- b. Rate of Change of Chamber Pressure 50 psia/second
- c. Duration at Throttled Chamber Pressure (tbd) minutes

The NSS evaluation of the throttling requirement was performed by determining and evaluating the effects on the NSS of performing a high I_{sp} throttling maneuver. The effects that were identified are described below.

1. Performance - By high I_{sp} throttling during the initial portion of the shut-down process, a portion of the delayed neutron power is dissipated. This in turn reduces slightly the amount of after-heat which has to be removed during cooldown and, hence, there is a slight reduction in NSS after-cooling requirements. However, it is not correct to simply consider after-coolant propellant requirements in order to determine a figure of perfor-

~~CONFIDENTIAL~~

~~RESTRICTED DATA~~

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~
~~Atomic Energy~~

- (U) mance merit due to throttling since the reduced thrust level during throttling introduces penalties. Data for typical burns were compared to determine performance improvements resulting from minimization of NSS cooldown propellant requirements.
- (CRD) 2. Additional Drum Span Requirement - A design consideration is that of minimizing drum span in the reactor in order to minimize the consequences of a control drum actuator failure and to minimize the peripheral element temperature increase to minimize increased corrosion. The high I_{sp} throttling requirement will add to the drum span and drum motion at rated chamber temperature requirements unless the throttling pressure is limited to that attainable by SSCV opening alone and is allowed to vary during the NSS life.
- (U) 3. SSCV Requirements - The high I_{sp} throttling requirement influences the requirements on the SSCV. A design consideration is that of minimizing the requirements imposed upon the SSCV so that the SSCV may be selected in the context of maximizing the NSS reliability at rated conditions.
- (CRD) 4. Fuel Corrosion - Fuel element corrosion throughout the core is affected by the increased operating time required to perform a given mission if throttling is utilized. Individual peripheral fuel element bore hot end corrosion is increased by throttling due to off design core inlet temperatures and additionally increased if reactivity must be inserted by the control drums during throttling. In addition, reactivity insertion by the control drums can adversely affect interelement corrosion both during throttling operation and during all subsequent operations.
- (U) 5. Fuel Thermal Stresses - Any added fuel temperatures in the peripheral region of the core due to high I_{sp} throttling will cause higher than normal temperature gradients within the individual fuel element and between adjacent fuel

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~
~~Atomic Energy~~

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~

elements which will introduce increased stresses.

- (CRD) 6. SSA Temperature Constraints - Throttling at high I_{sp} increases the temperature of the SSA liner and tube. The throttling level at which these limits constrain the operation is dependent on the capabilities of the SSCV as to fixed or multi-position.
- (U) 7. Controller Complexity - The requirement for high I_{sp} throttling requires the controller to control satisfactorily under different operating conditions.
- (U) 8. Control Concept Complexity - The requirement for high I_{sp} throttling imposes special requirements for variable SSCV and/or control drums and can eliminate certain control concepts which would reduce the complexity of the reference design system.
- (U) 9. Severity of Malfunction - Different malfunctions of concern may exist at throttled conditions than at rated conditions and certain malfunctions may have different characteristics at high I_{sp} throttled conditions. Such malfunctions are:
1. loss of flow	3. rapid LH_2 insertion	5. SSCV fail closed
2. drum run out	4. SSCV fail open	
- (U) 10. Reliability - The requirement to throttle may affect the overall reliability of the NSS.
- (U) 11. Compatibility with Startup Mode - The throttling requirement and high I_{sp} startup mode requirement are inter-related. To have the capability for high I_{sp} throttling also provides much of the capability to perform a high I_{sp} startup. Thus, the two requirements should be considered together.

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~
~~AND~~

This page is Unclassified

12. Development - The throttling requirement could impose different development and qualification requirements in the form of analysis and testing.
13. Cost - The throttling requirement could impose different costs in the area of hardware (controls), analysis, and testing (both component and NSS).

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~
~~AND~~ 2-4

This page is Unclassified

3. DESCRIPTION OF APPROACHES AND SIGNIFICANT CHARACTERISTICS

The NPRD calls for throttling to a (tbd) point for a (tbd) duration at 50 psi/second at rated I_{sp} . To perform this evaluation, three different throttling points were identified (all at rated temperatures) and three throttling times were defined for each of the three throttling points. The characteristics of these were as follows.

- A. Nominal 80% power - The chamber pressure at this point was 350 psia. The three (3) throttling duration times were 30, 120, and 600 seconds.
- B. Nominal 60% power - The chamber pressure at this point was 270 psia. The three (3) throttling duration times were the same as above.
- C. Nominal 45% power - The chamber pressure at this point was 200 psia. The three (3) throttling duration times were the same as above.

In the comparison matrix which follows, the evaluation and comparison is between a given throttling condition. The effects of throttling for consideration as identified in Section 2 are all evaluated as being an additional advantage or disadvantage over the no-throttling consideration. The basis for the statements on the comparison matrix chart are contained in detailed design memoranda (DRM) that were generated for this study and are referenced in the matrix. These detail memoranda are included in the appendix.

CONFIDENTIAL
 RESTRICTED DATA
 AUTHORITY NCI-1734

4. COMPARISON MATRIX

Functional and Technical Design Consideration	1 No Throttling	2 Throttling 80% Power	3 Throttling 60% Power	4 Throttling 45% Power	Selection
1. Performance (Payload)	No gain	Maximum of 200 lbs. gain (less than 0.3% of propellant requirements) based on typical burns studied and if throttling point is held for approximately 100 seconds. (Reference DRM 51404, Figures II, III, IV, and V.)	Maximum of 380 lbs gain (less than 0.5% of propellant requirements) based on typical burns and if throttling point is held for approximately 120 seconds. (Reference DRM 51404, Figures II, III, IV, and V.)	Maximum of 440 lbs. gain (less than 0.5% of propellant requirements) based on typical burns studied and if throttling point is held for approximately 120 seconds. (Reference DRM 51404, Figures II, III, IV, and V.)	4-3-2-1
2. Additional Drum Span Requirements ⁽³⁾	No additional drum span required	<p>SOL⁽¹⁾: No additional requirements if SSCV can be opened.</p> <p>Max. Corrosion & Poisoning Permissible for Constant Drum Position Throttling: \$.36 for SSCV limited at 47.5°⁽⁴⁾ \$1.18 for SSCV with full open capability. EOL⁽²⁾: Additional reactivity required: \$.90 for SSCV limited at 47.5°. \$.12 for SSCV with full open capability</p> <p>Fixed SSCV Orifice (SOL & EOL): Additional reactivity required: \$.63 for orifice equivalent to 17°. \$.90 for orifice equivalent to 47.5°. (Ref. DRM 51502 and DRM 51495.)</p>	<p>SOL: \$.30 additional reactivity for SSCV limited at 47.5°. No additional requirement for SSCV with full open capability.</p> <p>Max. Corrosion & Poisoning Permissible for Constant Drum Position Throttling: Unattainable with SSCV limited at 47.5°. \$.65 for SSCV with full open capability.</p> <p>EOL: Additional reactivity required: \$1.60 for SSCV limited at 47.5°. \$.64 for SSCV with full open capability.</p> <p>Fixed SSCV Orifice (SOL & EOL): Additional reactivity required \$1.31 for orifice equivalent to 34°. \$1.60 for orifice equivalent to 47.5°. (Ref. DRM 51502 and DRM 51495.)</p>	<p>SOL: Unattainable with SSCV limited at 47.5°. \$.50 additional reactivity required for SSCV with full open capability.</p> <p>Max. Corrosion & Poisoning Permissible for Constant Drum Position Throttling: Unattainable.</p> <p>EOL: Unattainable with SSCV limited at 47.5°. \$1.80 additional reactivity required for SSCV with full open capability.</p> <p>Fixed SSCV Orifice (SOL & EOL): Unattainable with fixed orifice.</p> <p>Ref. DRM 51502 and DRM 51495.)</p>	1-2-3-4

CONFIDENTIAL
RESTRICTED DATA
4-2

Functional and Technical Design Consideration	1 No Throttling	2 Throttling 80% Power	3 Throttling 60% Power	4 Throttling 45% Power	Selection
(U) 3. SSCV Requirements	Fixed orifice (Equivalent to SSCV angles of 0-47.5°) and variable SSCV can be con- sidered.	Fixed orifice (equivalent to SSCV angles of 17-47.5°) and variable SSCV can be considered.	Fixed orifice (equivalent to SSCV angles of 34-47.5°) and variable SSCV can be con- sidered.	Fixed orifice cannot be considered. SSCV must be capable of being opened to the full open position.	1-(2 & 3)-4
4. Fuel Corrosion (CRD)	No additional fuel corrosion	<u>CONSTANT DRUM POSITION THROTTLING</u>			1-2-3-4

Similar core average corrosion rate as at rated conditions. (Reference DRM 51667, Item 3.3.)
Additional total corrosion because of increased time required at rated temperature to impart
same vehicle energy. For two minutes throttling and for the typical bums studied (Reference
DRM 51404 Tables IV-VII):

0.5 minute additional time
required at rated tempera-
ture.

0.9 minute additional time
required at rated tempera-
ture.

1.25 minutes additional
time required at rated
temperature.

NON-CONSTANT DRUM POSITION THROTTLING

In addition to the corrosion effect from the constant drum position throttling case, the following
increases in peripheral fuel element bore hot end corrosion rates result during throttling and
interelement corrosion may be adversely affected during throttling and all subsequent operations.
(Reference DRM 51667 and DRM 51461, Figure 4.)

70-94% at EOL for SSCV
limited at 47.5°.

9-12% at EOL for SSCV with
full open capability.
50-67% for fixed orifice
equivalent to 17°.
70-94% for orifice
equivalent to 47.5°.

25-30% at SOL for SSCV
limited at 47.5°.
125-165% at EOL for
SSCV limited at 47.5°.

50-67% at EOL for SSCV
with full open capability.
100-135% for fixed orifice
equivalent to 34°.
125-165% for fixed orifice
equivalent to 47.5°.

40-55% at SOL for
SSCV with full open
capability.

140-190% for SSCV
with full open capability.

CONFIDENTIAL
DEFENSE
Nuclear Energy Research
4-3

CONFIDENTIAL
DEFENSE
Nuclear Energy Research

Functional and Technical Design Consideration	1 No Throttling	2 Throttling 80% Power	3 Throttling 60% Power	4 Throttling 45% Power	Selection
5. Added Thermal Fuel Stress (CRD)	1.00	CONSTANT DRUM POSITION THROTTLING: No adverse effects. NON-CONSTANT DRUM POSITION THROTTLING: Axial stresses increase. For the example cases studied: 1. 16 times the axial stress with no-throttling. (SOL; SSCV at 47.5°). (Ref. DRM 51540, Table.) 1. 27 times the axial stress with no-throttling. (SOL; SSCV at 47.5°). (Ref. DRM 51540, Table.) 1. 38 times the axial stress with no-throttling. (SOL; SSCV at 90°). (Ref. DRM 51540, Table.)			1-2-3-4
(U) 6. SSA Temperature Constraints	No effect	SSA high temperature constraint unless SSCV can be adequately positioned.	SSA high temperature constraint unless SSCV can be adequately positioned. At least maximum flow position required.	SSA high temperature constraint unless SSCV can be adequately positioned. Full open position required.	1-(2 & 3)-4
(U) 7. Controller Complexity	No throttling allows less complex controller to be considered. (Ref. DRM 51403.)	More complex but controller complexity is independent of throttling point if any throttling is required. (Ref. DRM 51403).	More complex but controller complexity is independent of throttling point if any throttling is required. (Ref. DRM 51403).	More complex but controller complexity is independent of throttling point if any throttling is required. (Ref. DRM 51403).	1-(2, 3, & 4) Equal)
(U) 8. Control Concept Complexity	Less complex control concepts can be considered such as fixed drum and fixed SSCV systems. (Ref. DRM 51403).	More complex control systems must be used. (Ref. DRM 51403).	More complex control systems must be used. (Ref. DRM 51403).	More complex control systems must be used. (Ref. DRM 51403).	1-(2, 3 & 4 Equal)
(U) 9. Severity of Malfunction	No added severity. (Ref. DRM 51580).	The rapid flow insertion malfunction is more severe than no-throttling case. (Ref. 51580).	Rapid flow insertion malfunctions more severe than 80% case. (Ref. DRM 51580).	Not specifically evaluated but it appears that rapid flow insertion malfunction would be more severe than either 80% or 60% case. (Ref. DRM 51580).	1-2-3-4

RESTRICTED DATA
CONFIDENTIAL

RESTRICTED DATA
CONFIDENTIAL

Functional and Technical Design Consideration	1	2	3	4	Selection
	No Throttling	Throttling 80% Power	Throttling 60% Power	Throttling 45% Power	
10. Reliability	No effect.	Lowered reliability. More difficult to attain reliability goals than no-throttle case.	Lowered reliability. More difficult to attain reliability goals than 80% case.	Lowered reliability. More difficult to attain reliability goals than 60% case.	1-2-3-4
11. Compatibility with Startup Mode	Compatible with center of the map startup	Compatible with high I_{sp} startup. (5)	Compatible with high I_{sp} startup.	Not completely compatible with high I_{sp} startup because added SSCV control and added drum span would be required.	(2 & 3)-1-4. If no high I_{sp} startup requirement, then 1-(2&3)-4
12. Development and Qualification	No effect	Significantly, more analysis and testing required over no-throttling case. More reactor testing required to qualify throttling capability.	Development and checkout same as 80% case. More testing required to qualify throttling capability.	Development and checkout same as 80% case. More testing required to qualify throttling capability.	1-(2, 3 & 4 Equal)
13. Cost	No effect	Additional cost over no-throttling case. (NSS test control hardware, analysis and testing.)	Additional cost over no-throttling case. (NSS test control hardware, analysis and testing.)	Additional cost over no-throttling case. (NSS test control hardware, analysis, and testing.)	1-(2, 3 & 4 Equal)

No. 1 "No Throttling" case selected.

(1) SOL = "Start of Life" with SSCV assumed to be at 0° at rated conditions.

(2) EOL = "End of Life" and is assumed to be after 50 minutes of operation with ten starts (assumed \$1.00 corrosion plus \$0.30 poisoning).

(3) Assumes SSCV is used at rated conditions to compensate for corrosion. If drums are used to compensate for corrosion, then the additional drum span required at any time during lifetime is the same and is equal to that identified for SOL.

(4) The valve angles of 0° , 47.5° , and full open define minimum flow, maximum flow and full flow and are used to describe three SSCV positions. The minimum flow position is such that at rated conditions the SSA temperatures are at the upper limits. The maximum flow position is an intermediate valve position such that at rated conditions the SSA temperatures are at the lower limits. The full open position is the SSCV wide open. This position cannot be used at rated conditions because the hydrogen flow would be such as to drop the SSA temperatures below the low temperature limits.

(5) High I_{sp} startup is assumed to consist of a ramp to the 60% power at rated temperature point and then to rated conditions along a constant temperature line.

This page is Unclassified

5. RECOMMENDATION

The WANL evaluation of the high I_{sp} throttling information results in the recommendation that no specific design requirements be imposed on the NSS to provide the capability to perform high specific impulse throttling. This recommendation would result in the deletion of the NPRD requirement for high I_{sp} throttling.

This recommendation does not rule out the fact that capability for high I_{sp} may exist in the final design and capability for reduced temperature throttling will certainly exist. However, because of the relative advantages and disadvantages identified, any throttling in the final design should be that which is available when the most reliable and best performing NSS is determined based upon rated condition considerations.

The recommendation given above is made because of the many penalties identified with performing such a throttling maneuver. A significant penalty is that of fuel corrosion. Another significant disadvantage is that of the requirement for a more complex control operating mode over the no-throttling case. The requirements on the SSCV and control drum span are more severe for throttling than for the no-throttling case. The added fuel corrosion, complex control modes, use of SSCV, and abnormal temperature distributions resulting from a throttling requirement make the attaining of the reliability goals more difficult. These considerations result in increased development cost.

Among the three throttling cases studied, the following general conclusion can be made. The lower the throttling point, the greater the propellant saving. At the same time, the penalties on the NSS are usually greater the lower the throttling point.

This page is Unclassified

6. REFERENCES

DRM 51404 & Rev. 1	Status of Throttling Point and Time Trade Study
DRM 51403	Reactor Control System Design Studies
DRM 51540	Stress Effects for Throttling System Trade Study
DRM 51502	NERVA Drum Span Requirements
DRM 51502 & Rev. 1 & 2	NERVA Drum Span Requirements
DRM 51580	Safety Implications of Throttling at Full I_{sp}
DRM 51461	Preliminary Estimate of Effect of Throttling on Fuel Element Exit Gas Temperature
DRM 51667	Effect of Throttling on Fuel Element Corrosion
DRM51495	R-1 Engine Constraint Map

This page is Unclassified

	TITLE NSS THROTTLING TRADE STUDY REPORT NO. 706	
	DOCUMENT NO. WANL-TME-1962	DATE August 1969
ABSTRACT This trade study identifies and evaluates various advantages and penalties affecting the Nuclear Subsystem during high specific impulse throttling at rated chamber temperatures with regard to throttling point and time, and presents recommendation of high impulse throttling operation based on analysis of NSS considerations.		
Fold or Cut	DATA ITEM NO. S-54	SECURITY CLASSIFICATION OF DOCUMENT CRD
	CDRL LINE NO TBD	TOTAL NO OF PAGES 17
KEY WORDS Evaluation, Analysis, Recommendation, High Specific Impulse, Throttling, Throttling Effects, NSS, No. 706		
AUTHOR/EDITOR R. E. Thompson		PREPARING DEPT Systems Analysis
W Form 59943 DOCUMENT INFORMATION SUMMARY		