LABORATORY DIRECTED RESEARCH AND DEVELOPMENT

LABORATORY DIRECTED RESEARCH AND DEVELOPMENT

Science, Technology and Engineering

Mission Technologies

Grand Challenges

Sandia
National
Laboratories

A Department of Energy
National Laboratory

National Nuclear Security Administration

Cover photo (center, going clockwise):
 (1) demonstrating the first solid-state white-light-emitting device using quantum dots,
 (2) developing designer synthetic scaffolds using computer-controlled Robocasting technology,
 (3) demonstrating simultaneous concentration and separation of live and dead *E. coli* by using insulative (electrodeless) dielectrophoresis (iDEP),
 (4) developing complex nanomaterials that mimic structures and growth conditions of natural biominerals, (5) testing SnifferStar™ performance in a wind tunnel for use in detection of chemical agents from an airborne platform, and
 (6) developing new ceramics to be used for thermal insulation at the leading edge of hypersonic vehicles.

Abstract

This report summarizes progress from the Laboratory Directed Research and Development (LDRD) program during fiscal year 2003. In addition to a programmatic and financial overview, the report includes progress reports from 364 individual R&D projects in 14 categories.

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy's National Nuclear Security Administration under Contract DE-AC04-94-AL85000.

SAND 2004-0997
 March 2004

LDRD Annual Report Staff:

Hank Westrich
 Cynthia H. McDonald
 Donna Chavez
 Keith Ortiz

Carol Whiddon
 Rhonda Reinert
 Donna Drayer
 Douglas Prout

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
 U.S. Department of Energy
 Office of Scientific and Technical Information
 P.O. Box 62
 Oak Ridge, TN 37831

Telephone: (865)576-8401
 Facsimile: (865)576-5728
 E-Mail: gpoaccess@gpo.gov
 Online ordering: <http://www.osti.gov/bridge>

Available to the public from
 U.S. Department of Commerce
 National Technical Information Service
 5285 Port Royal Rd
 Springfield, VA 22161

Telephone: (800)553-6847
 Facsimile: (703)605-6900
 E-Mail: orders@ntis.fedworld.gov
 Online order: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>

Table of Contents

16	“...exceptional service in the national interest.”	51	Atomic-Layer Deposition of Highly Conformal Tribological Coatings
17	An Overview of Sandia’s FY 2003 Laboratory Directed Research and Development (LDRD) Program	54	Assembly of Microsystems Using Exothermic Multilayer Thin Films
24	New Challenges and Ongoing Benefits of Sandia National Laboratories’ FY2003 Laboratory Directed Research and Development (LDRD) Program	57	Intelligent Interaction Control as Applied to Metrology and Assembly of Microscale Components
27	Benefits of LDRD to Energy and Critical Infrastructures	59	Rapid-Prototyping High-Density Circuitry (RpHdc)
28	Benefits of LDRD to Nuclear Weapons (NW)	61	Elucidating the Mysteries of Wetting
31	Benefits of LDRD to Emerging Threats (ET)	64	Next-Generation Spindles for Micromilling
33	Benefits of LDRD to Nonproliferation and Materials Control (NP&MC)	66	Investigation of Bioprocesses for Advanced Manufacturing Applications

Advanced Manufacturing

35	Mesoscale Wide-Bandwidth Linear Magnetic Actuators
38	Levitated Three-Axis Microaccelerometer
40	Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques
42	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication
44	Microfabrication with Femtosecond-Laser Processing
46	Mesoscale-Controlled Motion for a Microfluidic Drop Ejector
48	Science-Based Sensing of Phase Transformations in Steels

Biotechnology

71	Molecular-Scale Studies of Single-Channel Membrane Pores
73	Efficient Massively Parallel Techniques for Protein Structure Generation
75	Mapping Membrane Protein Interactions in Cell Signaling Systems
78	High-Throughput Instruments, Methods, and Informatics for Systems Biology
83	Biomimetic Chloroplasts: An Integrated Microdevice Power Source
86	Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors
89	Cellular Observatory: Simultaneous Time- and Frequency-Resolved Microscopy
91	Modeling Biomembranes

Table of Contents

- 93 Reverse-Engineering Biological Networks: Applications in Immune Responses to Bioterrorism Threats
- 96 High-Throughput Identification of Molecular Machines Involved in Membrane Signaling and Toxin Pathways

Computational and Information Sciences

- 100 Parallel Atomistic Computing for Failure Analysis of Micromachines
- 102 Smart-Sensor Technology for Joint Test Assembly Flights
- 105 Multilevel Methods for Nonlinear Structural Mechanics
- 107 Algorithmic Support for Commodity-Based Parallel Computing Systems
- 110 Parallel Repartitioning for Optimal Solver Performance
- 113 Graduated Embodiment for Sophisticated Agent Evolution and Optimization
- 115 Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation
- 118 Robust Message Routing for Mobile (Wireless) *Ad Hoc* Networks
- 120 Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods
- 122 Micromagnetic Suspension
- 124 Sensitivities for Large-Scale Simulation Codes
- 126 IP Storage: A Performance and Security Study

- 129 A Parallel Circuit Simulator for Cell Biology
- 131 Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions
- 134 Robust Large-Scale Parallel Nonlinear Solvers for Simulations
- 136 Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security
- 139 Massively Parallel Linear Programming
- 141 A Method of Evaluating Research Using New Innovation, Risk, and Impact Indicators

Electronics and Photonics

- 145 III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies
- 148 The Integration of Advanced Photonics and MEMS
- 150 Aging Mechanisms in Dormant MEMS Structures
- 152 MEMS in μ Fluid Channels
- 155 Dispersive Photonics for Next-Generation Sensors and Microsystems
- 157 Engineered Superconductivity in Electron-Hole Bilayers
- 160 Silicon-Based RF MEMS Components
- 162 Nanoelectromechanical Oscillators (NEMOs) for RF Filtering

Table of Contents

165	Continuous-Wave Intersubband Terahertz Sources	Engineering Sciences	
167	Microsystems for Chemical Signature and Reagent Delivery	200	Uncertainty Propagation in Models of Thermofluid Systems
169	Microfluidic Cellular Sample Pretreatment	203	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements
172	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics	207	A Physically Based Approach to Modeling Ductile Fracture
174	Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia’s MDL and BAE Systems	210	Radiation Aging of Stockpile and Space-Based Microelectronics
176	Functionalized Nanoparticles for Sensor Applications	212	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach
178	Novel <i>In Situ</i> Mechanical Testers to Enable Integrated Metal Surface Micromachines	215	Multiscale Thermal Modeling
181	Compliant Thermomechanical MEMS Actuators	218	A Robust, Coupled Approach for Atomistic-Continuum Simulation
183	An Integrated, Stacked System-on-a-Chip	220	Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications
185	Micromass Spectrometer-on-a-Chip	222	High-Fidelity Frictional Models for MEMS
187	Quantum Coherence in Semiconductor Nanostructures for Improved Lasers and Detectors	225	Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames
189	MOSFET–MEMS Integration	228	Coupled Solid-Fluid Mechanical-Computational Modeling of Fracture and Fragmentation in Geomaterials, Such as Hard and Deeply Buried Targets (HDBTs)
191	Microoptical Gyroscope Via Monolithic Active/Passive Optical Integration	232	Analysis of Nanoscale Films and Particles
193	Materials Physics and Device Development for Improved Efficiency of GaN HEMT High-Power Amplifiers	234	Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices
195	Leaky-Mode VCSELs for Photonic Logic Circuits	236	Tensegrity—Smart, Adaptive Structures Through Material Biomimicry
197	Advanced Polychromator Systems for Remote Chemical Sensing	239	Coupled Acoustical/Structural Simulations of Weapons Systems

Table of Contents

Materials Science and Technology

242	Magnetic-Field Effects on Vacuum-Arc Plasmas	282	Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices
243	Microstructural and Continuum Evolution Modeling of Sintering	284	Photocontrol of Nanointeractions in Microsystems
246	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	287	Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines
248	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	289	Nanostructured Materials for Directed Transport of Excitation Energy
252	First-Principles Determination of Dislocation Properties	291	Modeling Local Chemistry in the Presence of Collective Phenomena
254	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	293	The Effects of Varying Humidity on Copper-Sulfide Film Formation
256	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	296	Solution-Based Nanoengineering of Materials
258	Mechanics and Tribology of MEMS Materials	300	Assembly and Actuation of Nanomaterials Using Active Biomolecules
262	Dynamics of Metal/Ceramic Interfaces	303	Decomposition of Contaminants Using Photochemically Active Nanoparticles
263	<i>In Situ</i> Characterization of Soft Solution Processes for Nanoscale Growth	305	Thermally Cleavable Surfactants
265	Determination of Critical Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	307	Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions
268	LIGA Microsystems Aging: Evaluation and Mitigation	309	Quantification of Environments and Surfaces Within Micropackages
271	Science-Based Processing of Field-Structured Composites	312	Assembly of Ordered Electrooptical and Bioactive Materials and Composites
274	Exploration of New Multivariate Spectral Calibration Algorithms	315	Advanced Packaging/Joining Technology for Microsystems
278	The Basics of Aqueous Nanofluidics: "Interphase" Structure and Surface Forces	319	Magnetostrictive Elastomers for Actuators and Sensors
		321	Active Photonic Nanostructures

Table of Contents

Pulsed Power Sciences

- 324 Z-Pinch Power-Plant System Development
- 327 Recyclable Transmission Line Concept for Z-Pinch IFE
- 329 Suppression of Electron Emission from Conductors
- 332 Solid-State Switch for Advanced Pulsed Power
- 334 Determination of Microstructural Properties with Isentropic Compression
- 336 Simulations of Intense Petawatt Laser Pulses with Dense Z-Pinch Plasmas
- 338 Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating
- 341 Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators
- 343 Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions

Differentiating Technologies

- 346 Adaptive Network Countermeasures
- 349 Microengine for Advanced Power Generation

Emerging Threats

- 353 Air Sterilization and Decontamination
- 355 Data Fusion and Visualization of MASINT Results for Underground Facility Characterization
- 357 Advanced Unattended Ground-Sensor Technology

- 359 The Endowment of Simulator Agents with Humanlike Episodic Memory
- 361 Algorithms for Improved Performance in Cryptographic Protocols
- 363 Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting
- 365 Adaptive and Mobile Ground Sensors
- 368 Algorithm Development for Prognostic Health Monitoring and Maintenance
- 371 New Mechanism for Upset of Electronics
- 373 Flexible Robotic Maintenance Facility
- 376 Obstacle Detection for Autonomous Navigation
- 378 Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications
- 380 Microfuze
- 383 Automated Visual Direction of Mobile Manipulation
- 385 Miniature Fourier-Transform Ion-Mobility Spectrometer for Real-Time Detection and Identification of Explosives and Chemical Agents
- 387 CONOPS Development for Automated Systems
- 389 Rapid Mitigation and Decontamination of Toxic Industrial Chemicals
- 392 EM Interactions with Systems to Enhance Security
- 394 Adaptive Awareness for Personal and Small-Group Decision Making
- 396 Use of Seismic and Acoustic Responses to Assess Bomb Damage to Underground Facilities

Table of Contents

399	Free-Space Electrooptic Sampling and Remote Mapping of Electromagnetic Fields from Emitting Structures Using Femtosecond Terahertz Transceivers
401	Information Assurance for Wireless <i>Ad Hoc</i> Networks
404	Hybrid Infrastructure Cryptography
407	Critical Technology Development for Hard Target Defeat High-G-Tolerant Fuze and High Explosives
409	Immunological Basis for High-Reliability Systems Control
411	Miniaturization of SAR Electronic Assembly Using Sandia’s Integrated Substrate Technology
413	Moving-Target Identification Using Ultrahigh-Range-Resolution Data
416	Advanced Mobile Networking, Sensing, and Controls Using Graph Theory
418	Compact Terahertz (THz) Sources for Emerging Threats Applications
420	Understanding Communication in Counterterrorism Crisis Management
422	Hypervelocity Impact-Generated Flash
425	Improving Human/System Interactions in Systems-of-Systems
428	Distributed Detection and ID Algorithm Architecture for Unattended Ground Sensors
430	Secure Chaotic Communications
432	System-of-Systems Modeling and Analysis
434	Eye-Safe Short-Range Standoff Aerosol-Cloud Finder
437	Micro Flame-Based Detector Suite for Universal Gas Sensing
441	Smart Decoy Sensor Network
443	Monomolecular Carbon Nanothread Fabrication
445	Reliability Data to Improve High-Magnetic-Field Coil Design for High-Velocity Coilguns
448	Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities
451	Wide-Area Surveillance in Synthetic-Aperture Radar Images
454	Measures of Effectiveness and Performance for MicroTalon SDAC Technologies and Systems
Energy and Critical Infrastructures	
457	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations
460	A Model of Infrastructure Interdependency Using Communication Agents
463	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants
466	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management
468	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles
471	Specific Anion Nanoengineered Sorbents for Water Purification
473	Low-Work-Function Material Development for the Microminiature Thermionic Converter
475	Autonomous Microexplosive Subsurface Tracing System

Table of Contents

477	Vulnerability Assessment of National Power Grid	513	Advanced Proton-Exchange Materials for Energy-Efficient Fuel Cells
480	Natural-Gas Production Problems: Solutions, Methodologies, and Modeling	515	Aluminate-Hydride Fuel-Cell Demonstration Project
483	High-Efficiency Turbine Blade Coatings	517	Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process
486	Time-Domain Reflectometry for Remote, Real-Time Water-Quantity/-Quality Monitoring of Perennial and Ephemeral Streams	519	Real-Time Discriminatory Sensors for Water-Contamination Events
489	Research and Development of Mathematical Algorithms to Define and Quantify Critical-Infrastructure Interdependencies	522	Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors
491	Functionalized Nanoelectrode Arrays for <i>In Situ</i> Identification and Quantification of Regulated Chemicals in Water	524	Securing Mobile Code
494	Validated Modeling of Distributed Energy Resources at Distribution Voltages	527	Novel Catalysts for Hydrogen Fuel-Cell Applications
496	Water Desalination	530	Linking Optimization and Simulation in Critical Infrastructure Systems
499	Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps	533	The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water
502	Potential Application of Microsensor Technology in Radioactive-Waste Management—With Emphasis on Headspace Gas Detection	535	Hydrogen Futures Dynamic-Simulation Model
504	Surety Enhancement for Wireless Automated-Control Networks	537	Dynamic-Simulation Modeling and Analysis Support for Senate Energy and Natural Resources Committee
506	Advanced Nuclear Engineering Analysis Technology	539	Agent-Based Control of Distributed Infrastructure Resources
509	Frameworks for Nuclear Process Transparency and Control	541	Optical Trapping of Collisionally Cooled Molecules
511	Beyond Nanoparticles—Attack on a Chemical “Holy Grail”	543	Efficacy of the Sandia Decon Formulation on the SARS Coronavirus

Table of Contents

Nonproliferation and Materials Control

546	Advanced Digital Detectors for Neutron Imaging	584	Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets
547	Microfabricated Acoustic Spectrum Analyzer	587	Detecting and Tracking the Active Insider Using 3-D Detection Technology
550	Coating Chemical Preconcentrators to Improve Chemical-Agent Collection	589	Microfabricated Dielectrophoretic Sample-Preparation System
552	Detection and Exploitation of Spread-Spectrum Waveforms	592	Automation of Microelectronic Physical Analysis
556	Robust Chemometrics for Remote Spectral Sensing	595	Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection
559	Deployable Large-Aperture Optics System for Remote-Sensing Applications	597	Secure MPLS Control Plane for Internet Connectivity
562	Arrayed Resonant Subwavelength Gratings	600	Agile, Microsystems-Enabled Receiver
565	Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies	603	Digital Signal Processing for Acoustic-Seismic Target Identification
568	Passive-Legged, Multisegmented, Robotic Vehicle	605	Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons
571	Low-Cost Photonic Lattice Structures for Remote Sensing	607	Active Network and Use of Network Processor
573	Security Monitoring and Management with Information Technology (SUMMIT)	608	Zero-Power Radio Receiver
575	Novel Methods for Ultracompact, Ultralow-Power Communications	610	Completely Passive Microwave Tag
577	Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	612	Security Coatings for Multichip Modules
580	A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	614	Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces
		616	Content-Based Video and Image Indexing System
		618	Bioaerosol Collection and Concentration for Microseparations-Based Detectors
		621	Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains

Table of Contents

623	Joint Authentication/Encryption
625	Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications
627	Leveraging Robotic Planning for Physical-Security Analysis
629	Buzzard
631	Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction
633	Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment
635	Radiation-Hardened Optoelectronic Components for Space-Based Applications
637	Novel Micro preconcentrators for CW, Explosives, and Water Surety
640	Ion-Mobility Spectrometer/Mass Spectrometer
642	Cryptographic Assurance of Execution Correctness and Confidentiality
645	Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts
647	Hyperspectral Tagging for Unique Identification
649	Fusing MSI and HSI Imagery for Subpixel Spectral Unmixing
652	Study of 3-D Focal-Region Sounding Applied to Large-Aperture Telescopes
655	Affordable, Automated Computed Tomography (CT) X-Ray Screening for Large Vehicle Bombs Preliminary Study
657	Coordinated Weapon-Platform Control Strategies for Intelligent Targeting
659	Advanced Weapons Signatures
662	Universal Detection for Chem-Bio Sensing in Microfluidic Systems
664	Multipurpose Locator-Tag System
666	Creative Networking of Commercial Products
667	Networked Device Demonstration
669	Analysis of Multichannel Internet Messaging
<hr/>	
Grand Challenges	
671	A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting
680	Interfacial Bioscience Grand Challenge (IBIG)
685	Biomicrofuel Cell
687	Augmented Cognition: Next-Generation Intelligent Systems
690	TALON
693	Near-Real-Time Characterization for Assured HDBT Defeat
696	Prompt Global Response
699	Winning the War: A Systems Approach to Defending Our Borders
702	Nonlethal Technologies for the War on Terrorism
<hr/>	
Advanced Concepts	
705	SDAC Architectural Study and Demonstration System Development

Table of Contents

708	Assessment of Information Flow Associated with Goods and People Crossing International Borders	741	A System-Dynamics Approach to Modeling Water Demand
710	Automatic Detection of Anomalous Weapon Surveillance Waveforms	744	Nanoscale Energetic Materials by Inverse Micellar Synthesis
712	Computational Social Dynamic Modeling of Groups Perpetrating Violence	747	Modeling of Rock Penetration
714	Development of a Terrorist-Activity Plan-Assessment Methodology	750	MEMS-Based Electromechanical Acoustic-Energy Harvester
716	Development of an Interactive Nuclear/WMD Terrorist Data Model	753	Predicting and Validating MEMS Interface Reliability
718	Enabling Technology for Human Collaboration	756	Direct Simulation of Solid-Fluid Systems
721	Large-Scale System-Dynamics Modeling of Water Resources on the Rio Grande	758	Support-Active Site Interactions in Heterogeneous Catalysts
722	Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application	760	An Analysis of the Automotive Industry as a Source for Weapon Components and Manufacturing Processes
<hr/>		762	Fluid-Structural Interactions in Wetting and Penetration into Porous Media
Corporate Objectives		765	Macroscopic Rates, Microscopic Observations, and Molecular Models of the Dissolution of Carbonate Phases
725	Molecular Integrated Microsystems (MIMS)	768	High-Speed Micro-EDM
729	Molecular Simulations of MEMS and Membrane Coatings (PECASE)	770	Nanoscale Hotspots Due to Nonequilibrium Thermal Transport
732	Self-Assembly of Polymers in Confined Geometries	773	Microexternal Combustion Engine: The P3 Engine Prototype
734	Building Conscious Machines Based Upon the Architecture of Visual Cortex in the Primate Brain	775	Mathematical and Algorithmic Issues in Multiphysics Couplings
736	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	778	Lipid Membranes on Nanostructured Silicon
739	Mathematical Analysis of Deception	780	Resin Infusion Between Double Flexible Tooling

Table of Contents

782	Studies on the Disbonding Initiation of Interfacial Cracks	823	Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents
784	Compliant Membranes for MEMS Microphones	825	A Biological Model for Controlling Interface Growth and Morphology
786	Multiscale Experimental/Numerical Study	827	Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions
788	Inelastic Deformation Mechanism in Shocked-Sapphire Single Crystals	830	Ornithopter
790	Sequestration of Pathogens on Nanoengineered Surfaces	832	Light-Powered Nanovehicles
793	A Combined Preconcentrator and Sensor for Live Waterborne Pathogens	834	Anomalous High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source
795	Predictive Accelerated Aging of Microsystems: The Science of Dormancy	836	Quantum Computing Accelerator I/O
798	Surety and Accountability Enhancements for Storage Containers	838	Design and Control of the Magnetic Properties of Nanoparticles
801	Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	840	Aerospace Vehicle Trajectory Optimization System by Primer Vector Methods
804	Advanced Packaging Technology for Optical Firesets	842	Algorithm Development for Smart Antennas
807	Miniature Transmitter Filter for JTA Using LIGA Technology	844	Failure Analysis and Surety Design of Composite Patching Systems
809	Novel and Robust Environmental Sensing Devices (ESDs)	847	Flow Control and Mixing in Microfluidic Devices
811	Advanced Neutron Monitors for JTA and Stockpile Monitoring	849	Topological Layout for the Optimal Design of Electrostatically Actuated MEMS
813	A Microbioreactor for Hydrogen Production	851	Atomic-Scale Scanning-Tunneling Microscopy Measurements of Nucleation and Growth of Ge/Si Alloy Structures
816	Self-Organizing Software Research and Development	853	Micro-/Nanoscale Thermomechanical Manufacturing
819	Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	855	Novel Diagnostics for Rarefied Flows in MEMS Applications
821	Computational Model of a Microbial Cell		

Table of Contents

857	Geophysical Subsurface Imaging and Interface Identification	888	Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems
859	Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer	890	Surfactant Effects on Lateral Growth and Surface Morphology of GaAs
861	Miniature High-Power RF Components Enabled by Mesoscale Manufacturing	892	3-D Large-Eddy Simulation of Turbulent Flow Based on One-Dimensional Turbulence Modeling
863	Electron- and Proton-Beam Directed-Energy Defense Weapons	894	The Derivation and Implications of “Nearly Noninformative” Priors from Metadata Conditioning
865	Electrical Conductivity of Metal Alloys	897	New Seismic-Event-Detection Technology
867	Design of Biospecific Surfaces to Control Specific Cellular Responses	899	Testing Recent Metal-/Oxide-Joining Discoveries in NW Component Manufacturing
869	High-Field Effects of GaN HEMTs	901	Photonic Encryption Using All-Optical Logic
871	Cognitive Models Applied to Human Effectiveness in National Security Environments	904	Automated Video Screening for Unattended Background Monitoring in Dynamic Environments
872	Nanomagnetic Films	906	Nanoporous-Carbon Adsorbers for Chemical Microsensors
875	A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites	908	Molecular Electronics Test Platform
877	Integrated Superhard and Metallic Coatings for MEMS	910	Development of Highly Integrated Magnetically and Electrostatically Actuated Micropumps
880	Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials	911	A Robotic Framework for Semantic Concept Learning
883	Friction in Micromachine Interfaces	912	Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems
885	Lipid Microarray Biosensor for Biotoxin Detection	916	Direct Single-Ion Machining of Nanopores
887	Advanced Manufacturing Techniques Using Rapid Prototyping	918	Investigation of the Effects of Intense Pulsed-Particle Beams on the Durability of Metal-to-Plastic Interfaces

Table of Contents

920	Advanced Techniques for Multiobjective Discrete Optimization
921	Fundamentals of Mobile-Robot Development
922	Nonradioactive Safety and Performance Issues with Supercritical Water Reactor (SCWR) Safety Technologies
923	Radiation Performance Issues with Advanced Coolants for Next-Generation Reactor
924	Smart Detectors of Enrichment of Bioaerosols
925	Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation
926	Appendix A: Project Number/Title Index
941	Appendix B: Awards/Recognition List
943	Appendix C: Project Performance Measures
959	Appendix D: DOE Critical Technologies
979	Appendix E: Major National Programs
1000	Appendix F: Dual Benefit Areas and Single-Use Categories

“...exceptional service in the national interest.”

Science and technology are the heart of the United States industrial competitiveness, national security, energy resources, environmental quality, and leadership in fundamental and applied science.

At Sandia, the Laboratory Directed Research and Development Program provides the knowledge that drives our future. We initiate research and development that spawn the knowledge that revolutionizes technology. Areas of emphasis center on our core technical competencies and the major strategic thrusts of Sandia's Institutional Plan. Leading-edge experiments that validate our work are constructed and operated on schedule, within budget, and in a safe and environmentally responsible manner.

Our work continues to produce many scientific and technological breakthroughs that lead to new technologies, markets, and businesses for the nation.

To all those who have contributed so generously of their time and talent, thanks and congratulations for a job well done.

An Overview of Sandia's FY 2003 Laboratory Directed Research and Development (LDRD) Program

K. Ortiz

Science with the Mission in Mind

Science historian James Burke is well known for his stories about how technological innovations are intertwined and embedded in the culture of the time, for example, how the steam engine led to safety matches, imitation diamonds, and the landing on the moon.¹ A lesson commonly drawn from his stories is that the path of science and technology (S&T) is nonlinear and unpredictable. Viewed another way, the lesson is that the solution to one problem can lead to solutions to other problems that are not obviously linked in advance, i.e., there is a ripple effect.

The motto for Sandia's approach to research and development (R&D) is "Science with the mission in mind." In our view, our missions contain the problems that inspire our R&D, and the resulting solutions almost always have multiple benefits. As discussed below, Sandia's Laboratory Directed Research and Development (LDRD) Program is structured to bring problems relevant to our missions to the attention of researchers. LDRD projects are then selected on the basis of their programmatic merit as well as their technical merit. Considerable effort is made to communicate between investment areas to create the ripple effect.

In recent years, attention to the ripple effect and to the performance of the LDRD Program, in general, has increased. Inside Sandia, as it is the sole source of discretionary research funding, LDRD funding is recognized as being the most precious of research dollars. Hence, there is great interest in maximizing its impact, especially through the ripple effect. Outside Sandia, there is increased scrutiny of the program's performance to be sure that it is not a "sandbox" in which researchers play without relevance to national security needs.

Let us therefore address the performance of the LDRD Program in fiscal year 2003 and then show how it is designed to maximize impact.

FY 2003 Selected Statistics	
Full-time Staff	389
Smallest Project (\$K)	10
Average Project (\$K)	272
Average Project (FTE)	1.07
Largest Project (\$M)	4.09
1st Year Projects	177
2nd Year Projects	107
3rd Year Projects	79
4th Year Projects	1

¹ James Burke, 1994, "Revolutions" episode, *Connections 2* video series produced by Discovery Communications, Inc.

Performance Against DOE Objectives

The present form of LDRD was authorized by Congress in 1991 to be the sole source of discretionary research funds. It is implemented under DOE Order 413.2A, "Laboratory Directed Research and Development," which identifies the following five objectives for the program:

- maintain scientific and technical vitality of the Laboratories,
- enhance the Laboratories' ability to address future Department of Energy (DOE) missions,
- foster creativity and stimulate exploration of forefront S&T,
- serve as a proving ground for new research, and
- support high-risk, potentially high-value R&D.

One measure of the FY 2003 program is with respect to these objectives.

Scientific and technical vitality. LDRD is essential to attracting and retaining young staff. In the last 4 years, almost a quarter of Sandia staff have supported LDRD projects. Over 46% of the full-time employee (FTE) hours spent on FY 2003 LDRD projects is from staff with fewer than 5 years of experience. In addition, LDRD projects support more postdocs (49%) than any other program at Sandia.

Future DOE missions. LDRD is essential to creating the capabilities that bring customers to Sandia, both new and returning. For example, the LDRD Program anticipated the need for research into technologies to counter chemical or biological warfare agents and other problems in homeland security several years before the 9/11 attacks. With the official standup of the Department of Homeland Security (DHS) this year, an appropriate funding structure for DHS-relevant R&D is currently being determined.

Forefront science and technology. LDRD research is at the forefront of Sandia's R&D. Five of the seven R&D 100 awards won by Sandia in 2003 were based on LDRD projects. Approximately 40% of the Laboratories' scientific and engineering publications are generated by LDRD research each year.

New research. The importance of biotechnology to national security is now recognized, for instance, in defense against biowarfare and bioterrorism. In fewer than 10 years, LDRD has placed Sandia's biotechnology initiative on the map. Sandia's biotech publications have grown from virtually nothing to rivaling the impact of the other national laboratories.

High-risk, high-value R&D. LDRD projects conduct high-risk research that would not be funded by programmatic

sources, i.e., neither the DOE nor other federal agencies. Often after an LDRD project reduces the initial risk, another sponsor will step in to fund follow-on work. An example is “A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting” (project 27328), which addresses high-risk, fundamental scientific issues necessary to improve the output of solid-state lighting devices and reduce their cost. Solid-state lighting has the potential to reduce U.S. energy costs for lighting by \$100B per year. Substantial follow-on funding is expected from a national initiative and industrial partners in FY 2005.

Performance Against OMB Measures

Another way to measure the LDRD Program is to compare it against the three criteria stipulated by the Office of Management and Budget and the President’s Office of Science in 2002²: Relevance, Quality, and Performance.

Relevance. As mentioned at the beginning, Sandia’s LDRD Program is designed to fund mission-relevant R&D. Investment areas issue calls for new R&D ideas; there is a strong programmatic component to the proposal reviews; and the investment areas often jointly fund projects of mutual interest. Following this overview, the reader will find brief discussions provided by Sandia’s Vice-Presidents for the Strategic Management Units responsible for the Laboratories’ missions in Nuclear Weapons, Nonproliferation and Materials Control, Energy and Environment, and Military Technologies.

Quality. The quality of the program is represented by external recognition, publications, and intellectual property.

In FY 2003, five of Sandia’s seven R&D 100 awards (honoring demonstrable technological significance relative to competing products and technologies) were based on LDRD research. In addition, FY 2001 LDRD efforts were awarded a Defense Programs Award of Excellence and a DOE National Energy Technology Laboratory Award for energy-efficiency research. LDRD projects also received two Arch T. Colwell Merit Awards from the Society of Automotive Engineers International. The election of Sandians Jeff Brinker and Gordon Osbourn to the National Academy of Engineering in FY 2002 was, in part, due to their long-term, creative LDRD research in materials science and laser optics.

In calendar 2002 (the last complete year for which data are available), LDRD contributed to 113 refereed publications. In the period from 1998 through 2002 (the most recent 5 years for

FY 2003 Performance	
Refereed Publications	413
Other Communications	345
Patent Disclosures	153
Patent Applications	82
Patents	18
Copyrights	17

Solid-state lighting has the potential to reduce U.S. energy costs for lighting by \$100B per year....In FY 2003, five of Sandia’s seven R&D 100 awards (honoring demonstrable technological significance relative to competing products and technologies) were based on LDRD research.

² Marburger and Daniels, May 30, 2002, “FY 2004 Interagency Research and Development Priorities.”

which data are available), Sandia LDRD produced 517 papers, of which 71% were cited one or more times—1.21 times the world average. The Institute for Scientific Information’s impact metric measures the impact on the scientific community by tallying the number of times published research is cited by other researchers. Sandia’s LDRD–related optics and acoustics publications from 1998 through 2002 were cited 5.24 times the world average, placing us second among the 140 institutions measured. In materials science and engineering, LDRD papers were cited 3.49 times the world average, placing LDRD eighth among these institutions. In physics, LDRD papers were cited 3.0 times the world average. Three of the five most highly cited Sandia papers in 2002 were from LDRD projects.

Also, since 1992 the number of patents granted and copyrights issued has increased substantially. In FY 1992, Sandia submitted 15 patent applications, 49 patent disclosures, and 6 copyrights. By FY 2003, the LDRD program had submitted 79 patent applications, 133 patent disclosures, and 10 copyrights.

Performance. The FY 2003 program is funded at \$102M, which is 5.7% of the total operating budget.³ Approximately 84% of the projects are defense-related; 73% are identified as potentially dual-use (i.e., applying to both defense and non-defense). The program closed FY 2003 within 1% of its target.

A measure of project performance is progress against identified research goals and milestones. Project milestones identify specific accomplishments in research progress. Goals refer to certain capabilities that are desired within the overall framework of a project’s research activities. In scientific inquiry, meeting all of the intended milestones and goals indicates that the research challenges have been set too low. So project teams are encouraged to create a deliberate mismatch between the group’s research aspirations and its present knowledge and resources.

In FY 2003, LDRD projects met 67% of their milestones and 46% of their goals. This indicates that there is a high level of “stretch” anticipated by LDRD participants in their research activities.

Overall, the Sandia LDRD Program is meeting its objectives and is performing well.

Sandia’s LDRD–related optics and acoustics publications from 1998 through 2002 were cited 5.24 times the world average, placing us second among the 140 institutions measured....In FY 2003, LDRD projects met 67% of their milestones and 46% of their goals. This indicates that there is a high level of “stretch” anticipated by LDRD participants in their research activities.

³ DOE Order 413.2A limits LDRD research funding to not more than 6% of the Laboratory’s total operating budget for the year, including non-DOE–funded work. The Order also allows funding of capital equipment for LDRD not to exceed 6% of its total capital equipment budget for the year, but Sandia’s LDRD Program does not assess capital equipment. The figures provided do not include the costs of construction and capital equipment.

FY 2003 Program Strategy and Process

In January 2002, Sandia's Mission Council approved the organization of the FY 2003 LDRD portfolio into four categories of investment areas: Science and Technology (S&T), Mission Technologies (MT), Grand Challenges (GC), and Other. Within these categories, the individual investment areas are the following:

- **Science and Technology Investment Areas.** Advanced Manufacturing, Biotechnology, Computational and Information Sciences, Electronics and Photonics, Engineering Sciences, Materials Science and Technology, Pulsed Power Sciences
- **Mission Technology Investment Areas.** Differentiating Technologies, Emerging Threats, Energy and Critical Infrastructures, Nonproliferation and Materials Control
- **Grand Challenges**
- **Other Investment Areas.** Advanced Concepts, Corporate Objectives

The Science and Technology investment areas principally support the nuclear weapons mission of the Laboratories while the Mission Technology investment areas principally support other missions. However, the nature of most LDRD projects is such that multiple missions typically benefit from any given project.

The Grand Challenges investment area is composed of large (greater than \$1M), multidisciplinary projects that address technical areas that are vital to the core purpose of the Laboratories.

Other investment areas include Advanced Concepts and Corporate Objectives. The Advanced Concepts investment area supports investigations related to potential future threats to national security. Corporate Objectives includes University Collaborations, the Presidential Early Career Awards for Scientists and Engineers (PECASE), and the Seniors Council. The Seniors Council investment area is new in FY 2003 and is intended to provide modest funding for the development and nurturing of exceptional research ideas and new technologies that would ordinarily be too risky for established investment areas or research ideas that bridge investment areas. Typically, LDRD projects in these other investments are late starts, i.e., they are proposed and funded after the beginning of the fiscal year.

The individual investment areas are profiled at the beginning of each section of this report.

The process for selecting LDRD projects began in March 2002 with a call for proposals from each of the above

The Seniors Council investment area is new in FY 2003 and is intended to provide modest funding for the development and nurturing of exceptional research ideas and new technologies that would ordinarily be too risky for established investment areas or research ideas that bridge investment areas.

investment areas. In response, 840 brief ideas for proposals were submitted. The Investment Area Teams (IATs) reviewed these ideas and selected 403 for development as full proposals. The idea-proposal process streamlines the process, encouraging more ideas to be submitted and decreasing the time spent writing and reviewing unsuccessful proposals.

The proposals are reviewed for technical and programmatic merit. Technical review criteria include scientific and technical soundness, creativity and innovation, and the project plan. Programmatic review criteria may include customer needs, fit within the existing technology base, competition, and potential leverage of other investments. From these proposals, 264 projects were selected by the IATs in June for funding.

FY 2003 ended with 364 active projects. There were 105 late starts (including 6 projects in S&T, 23 in MT, 5 in Grand Challenges due to processing delays, 10 in Advanced Concepts, 43 in University Collaborations, 7 in PECASE, and 11 in Seniors Council). Five projects were terminated due to job changes by the principal investigator and other reasons. Of the 364 active projects, 177 are in their first year, 107 in their second, 79 in their third, and 1 in its fourth year by special permission from DOE.

Conclusion

LDRD supports the nuclear weapon mission and has made important contributions to Sandia's ability to provide "exceptional service in the national interest." In the post-9/11 era, LDRD technologies have found service in the War on Terrorism, the war in Afghanistan, and the war in Iraq. It is expected that the newly formed Department of Homeland Security will draw heavily upon some of the R&D described in this report. Current LDRD developments in energy and environment may have significant impact on the nation's security.

Imagine James Burke 100 years from now looking at Sandia's LDRD. What story would he tell? Certainly he would tell about a solution to an important problem, perhaps related to nuclear weapons. Then he would tell about how that solution became the solution to another problem, and that to another, and so on as the ripples of innovation propagated. Naturally, the end of his story would be unpredictable to us today. However, we hope that we know about the first ripple already.

The reader is encouraged to read the project summaries in this report and get a glimpse of the future.

LDRD supports the nuclear weapon mission and has made important contributions to Sandia's ability to provide "exceptional service in the national interest." ...Current LDRD developments in energy and environment may have significant impact on the nation's security.

Additional Reading

A comprehensive discussion of DOE's and Sandia's LDRD Program management and funding sources may be found in the "Sandia National Laboratories FY 2003–2008 Institutional Plan," dated December 2002.

New Challenges and Ongoing Benefits of Sandia National Laboratories' FY2003 Laboratory Directed Research and Development (LDRD) Program

J. P. VanDevender, Vice President of Science, Technology and Engineering and Chief Technology Officer

More than 2 years after the September 11th terrorist attacks, many security concerns still threaten our nation and our way of life. Al-Qaeda terrorists are active worldwide, nuclear proliferation threats abound from North Korea to Iran, and there are increased security precautions at our borders, ports, and airports. Moreover, the Blaster Worm cyber attack and last summer's power-grid failure on the East Coast were stark reminders of the vulnerability of our nation's infrastructure to terrorists or to the breakdown of fragile or aging systems. Conflict in the Middle East continues to threaten disruption of the world's energy supply. Our challenge and responsibility as a national laboratory are to make strong and sustained investments in science and engineering that will result in new or improved technologies to mitigate or prevent threats to our national security and prosperity.

The Laboratory Directed Research and Development (LDRD) Program is Sandia's sole source of discretionary research and development (R&D) funds to enable the maintenance of the Labs' scientific and technical vitality. Over the past decade, LDRD investments at Sandia have created new technical strengths, prevented technical surprises, and enabled us to respond quickly to the emerging national security missions of the 21st century, including defense, energy, environment, public health, and climate. LDRD has positioned Sandia to be at the forefront of science and technology (S&T) so that we can achieve our highest goal: "...to become the laboratory that the U.S. turns to first for technology solutions to the most challenging problems that threaten peace and freedom for our nation and the globe." Every time there is a 9/11, an anthrax outbreak, a Columbia disaster, or a power-grid failure, and we get phone calls for our technical assistance, we move closer to fulfilling that highest goal. This is truly "service in the national interest."

Staff-generated LDRD projects are selected for their technical quality and their potential benefits to Sandia missions. The forward-looking nature of LDRD projects, coupled with the fact that principal investigators also provide solutions for real-world programmatic issues, facilitates rapid transition of

*J. P. VanDevender
Vice President of Science Technology and
Engineering and Chief Technology Officer
Sandia National Laboratories*

*LDRD has positioned Sandia
to be at the forefront of science
and technology...*

the innovative S&T to mission applications. As with most R&D, the most important applications of LDRD results reach far beyond the originally intended purpose. LDRD projects initiated years ago are having multiple and sustained benefits on current Department of Energy (DOE), Department of Homeland Security (DHS), and Work for Others (WFO) customer R&D needs. These sponsors engage Sandia because they recognize our scientific and technical leadership. The LDRD Program enables responsive and anticipatory scientific and technical solutions to national security mission needs to sustain that leadership.

Past LDRD strategic investments in microelectromechanical systems (MEMS) technologies, high-performance computing, and materials science are proving crucial for support of our continuing stockpile stewardship responsibility. From these and other fundamental LDRD-supported capabilities, Sandians have developed novel MEMS-based technologies, such as ion-mobility spectrometers, fusing systems, micromagnetic accelerometers, and ultrahigh-temperature ceramics. These LDRD-developed technologies have broader applications beyond nuclear weapons support. They have been applied to airport screening of explosives, security tags for nonproliferation, nuclear-waste or commercial transportation, the glass, steel, and aerospace industries, and more sensitive seismic detectors for treaty verification as well as characterization of oil and gas reservoirs.

We expect each of our LDRD-developed technologies to pay application dividends in many fields including nuclear weapons, nonproliferation, and homeland security. For example, LDRD investments in materials science and technology (MS&T) have led to a fundamental understanding of nanoparticle assembly and manipulation by biomolecular transport systems, which may lead to novel applications in medicine and energy systems. LDRD studies of luminescence at the nanoscale in semiconductor materials led to the first solid-state, white-light-emitting device that uses quantum dots. This innovative approach to creating white light may provide a viable alternative for a high-efficiency, low-cost source of light for homes, businesses, and infrastructure.

A highly successful LDRD-developed technology that is having major impact on national and homeland security is the μ ChemLabTM, which is the prototype chemical lab-on-a-chip system for SnifferStar, a battlefield detector of airborne toxins. Currently, μ ChemLabTM is being developed for characterization of viral signatures, with obvious applications to homeland security and public health-care issues.

As with most R&D, the most important applications of LDRD results reach far beyond the originally intended purpose. LDRD projects initiated years ago are having multiple and sustained benefits on current Department of Energy (DOE), Department of Homeland Security (DHS), and Work for Others (WFO) customer R&D needs.

Finally, one cannot underestimate the pivotal impact that LDRD—developed aerodynamic, fluid dynamic, and thermomechanical engineering codes had on the Columbia investigation. Originally developed for nuclear weapons components, the analyses from these codes helped convince NASA's Columbia Accident Investigation Board that insulating foam striking the wing during launch was the likely cause of damage that led to the shuttle's loss.

A small, decade-long LDRD portfolio in biological processes and cellular-products characterization has made possible the emergence of a strong and sustainable core biotechnology capability at Sandia to support both DOE and DHS missions. Sandia has gone from a lab with no traditional role in biologic sciences to one which, according to the Institute for Scientific Information, is a strong contributor in biochemistry and biophysics. Significant advances are being made in membrane signaling and recognition, biological warfare agent detection, portable bioagent detectors using microarray protein chips and sensitive bioagent detectors, structural proteomics platforms, and molecular modeling of membrane proteins. All this is being accomplished via the efforts of programmatic champions and talented staff, and the availability of discretionary LDRD funds.

The coupling between the mission needs of our customers and the proactive approach of the LDRD Program to meet Sandia's future mission needs is not accidental. LDRD Investment Area Teams balance the desire for short-term impact with the need for long-term mission support. The LDRD Program will balance current mission support for traditional scientific and technical areas with investments for the emerging S&T capabilities, including intelligent integrated microsystems, emergent behavior, surety S&T, biotechnology, nanoscience, and fusion energy. As Ambassador C. Paul Robinson, President of Sandia, said in an interview with the House Appropriations Committee Investigators, "LDRD is the lifeblood *and* the future of Sandia." The LDRD Program is vital to Sandia's maintaining its world-class capabilities as a national lab that DOE and the nation need to meet our missions in the 21st century.

"LDRD is the lifeblood and the future of Sandia." The LDRD Program is vital to Sandia's maintaining its world-class capabilities as a national lab that DOE and the nation need to meet our missions in the 21st century.

Benefits of LDRD to Energy and Critical Infrastructures (E&IC)

R. J. Eagan, Vice President of Energy and Infrastructure Assurance

The LDRD Program is key to the success of the Energy and Infrastructure Assurance* (E&IA) Strategic Management Unit. It provides the opportunity to develop creative research projects that support our long-term mission in energy, and it is absolutely essential to exploring new areas.

An outstanding example of success in addressing new areas of national concern is the involvement in a set of projects related to infrastructure security. This work started 6 years ago. The payoff is that LDRD-funded research formed the intellectual underpinning for Sandia's role in the National Infrastructure Surveillance and Analysis Center (NISAC). Today, NISAC is a \$27M/year program in the Department of Homeland Security. The successful partnership with Los Alamos National Laboratory would not have been developed without LDRD funds to create new models and approaches to understanding the U.S. infrastructure.

Three years ago we identified water as a major concern to international security and the domestic economy. Once again, LDRD funding of creative staff ideas laid the foundation for the comprehensive program in water quality and security that is developing today.

Many, many other examples exist where creative staff, supported by LDRD, have made major contributions to addressing serious national issues.

*R. J. Eagan
Vice President of Energy and Infrastructure Assurance
Sandia National Laboratories*

*The LDRD Program....provides
the opportunity to develop
creative research projects that
support our long-term mission
in energy, and it is absolutely
essential to exploring new
areas.*

* Energy and Infrastructure Assurance is formerly known as Energy and Critical Infrastructures.

Benefits of LDRD to Nuclear Weapons (NW)

T. O. Hunter, Senior Vice President of Nuclear Weapons

Laboratory Directed Research and Development (LDRD) is Sandia's most important program for invigorating and sustaining the science and technology (S&T) base and thereby helping to "invent" the future. It is critically important to our nation as we begin to transform our NW (nuclear weapons) stockpile to address the new national security environment in which threats may evolve more quickly, be more variable in nature, and be less predictable than in the past.

LDRD supports high-risk, potentially high-value R&D that sustains the scientific and technical vitality of the Laboratories while enhancing its ability to address current and future national security missions. The discretionary nature of LDRD funding fosters creativity, innovation, and exploration of new technology that enhances the Laboratories' S&T base and ensures that the best and brightest are focused on building the foundation that will benefit the NW program of the future.

The recent Nuclear Posture Review (NPR) specifically identified that new capabilities are required to defeat emerging threats such as hard and deeply buried targets (HDBTs) to find and attack mobile and relocatable targets, to defeat chemical or biological agents, and to improve accuracy and limit collateral damage. While the role of NW is evolving, the NPR has reaffirmed that, for the foreseeable future, the nuclear stockpile will continue to be an essential element of national security by strengthening our overall abilities to reassure our allies of U.S. commitments, dissuade arms competition from potential adversaries, and deter threats to the U.S., its overseas forces, allies, and friends. Moreover, we must be prepared for immediate, potential, or unexpected contingencies. LDRD is the vehicle that will identify, develop, and demonstrate new capabilities that will ensure that we are prepared to meet our responsibilities for ensuring that NW remain effective and that Sandia remains responsive to our customers' needs.

In this context, LDRD supports three key needs of the NW program:

- **Mission-focused versus task.** LDRD innovations create a responsive capability to explore new concepts and revisit weapon needs and requirements. For example, many of the nonnuclear components contained in today's nuclear stockpile may need to be modernized before they become "sunset technologies" that can no longer be supported cost-effectively. Looking to the future, LDRD has supported the development of

*T. O. Hunter
Senior Vice President of Nuclear Weapons
Sandia National Laboratories*

Laboratory Directed Research and Development (LDRD) is Sandia's most important program for invigorating and sustaining the science and technology (S&T) base and thereby helping to "invent" the future.

novel concepts for critical technologies, such as fuzing, that apply microtechnology, which has resulted in an integrated MEMS-based Micro-CDU. Other novel LDRD investigations have supported conceptualization and development of optically triggered photoconductive switches for firing-set systems and a low-cost digital radar to address the needs for a next-generation penetrating-weapon fuze. Currently, LDRD studies are also exploring novel methods to harden these microfuze components to high-g environments as well as advancing our penetrator technology via a high-g-tolerant fuze architecture. LDRD has also developed a high-resolution digital radiography capability that will enable nondestructive inspection of safety-critical weapon components, and is developing a capability to improve precision and reproducibility of fabricating complex microsystems using pulsed-laser technology.

- **Hedge against technological or stockpile “surprises.”**

LDRD investment strategies have included supporting studies designed to enable Sandia to quickly adapt and respond to unanticipated changes in the international security environment or to unexpected issues related to the nuclear stockpile. For example, a major issue in the qualification of some components is their response in pulsed neutron environments. LDRD has improved our understanding of the physical phenomena underlying prompt photocurrents in microelectronic devices and circuits, and this understanding is being used to improve simulation models. These models assist designers in qualifying device performance in hostile radiation environments with minimum build and test cycles. This simulation capability is increasing in importance because of test-based qualification issues, most notably associated with the cost of testing and the availability of pulse-reactor facilities for performing testing in the Department of Energy (DOE) and the Department of Defense (DoD). LDRD studies are also focused on investigating the use of microsensors that could be incorporated directly into the vacuum chamber of a neutron-generator tube to monitor the pressure during operation and aging, which will help further the science-based understanding of our neutron-generator manufacturing process. Finally, as a hedge against possible problems with nuclear safety component performance, LDRD is exploring new materials and characterizing their behavior in abnormal thermal and mechanical environments.

- **Attract, develop, and retain a premier work force.** The opportunity to work on leading-edge science with a connection to critically important national issues attracts the best and brightest people in science and engineering. LDRD provides Sandia with that opportunity to attract, develop, and retain a

LDRD investment strategies have included supporting studies designed to enable Sandia to quickly adapt and respond to unanticipated changes in the international security environment or to unexpected issues related to the nuclear stockpile.

premier work force that is necessary to solve the nation's most pressing national security problems, such as investigating novel technologies needed for critical weapons components and developing novel experimental diagnostics that support enhanced surveillance of our NW systems.

In summary, LDRD is the lifeblood for ensuring the health of our S&T base and for nurturing the critical capabilities necessary to maintain our NW stockpile. LDRD benefits the NW Strategic Management Unit through investments in high-risk, high-payoff technologies that attract exceptional research talent and enable the Laboratory to remain responsive to emerging national needs, such as addressing HDBTs, or to quickly adapt to unanticipated issues that could affect our national security. Our ability to remain responsive and adaptive in the future will depend on how well we anticipate our customers' needs and how well we translate those needs into strategic investment choices that appropriately leverage the work from our LDRD Program to extend the boundaries of the Laboratories' core science, technology, and engineering capabilities.

The opportunity to work on leading-edge science with a connection to critically important national issues attracts the best and brightest people in science and engineering. LDRD provides Sandia with that opportunity to attract, develop, and retain a premier work force that is necessary to solve the nation's most pressing national security problems,....

Benefits of LDRD to Emerging Threats (ET)

J. A. Tegnalia, Vice President of Military Technologies and Applications

The Military Technologies and Applications* (MT&A) Strategic Management Unit (SMU) has five general areas of support that benefit from the Laboratory Directed Research and Development (LDRD) Program. Those five areas include the New Triad, Surveillance and Reconnaissance, Homeland Defense/Force Protection, Minimally Manned Warfare/Efficiency of Operations, and Emerging Technology Applications. The strategy of the MT&A SMU is to transition innovative R&D solutions to the military by establishing early relationships with industry.

The MT&A SMU is also in the process of developing advanced concepts by working with the science and technology (S&T) community, industry, and the Department of Defense (DoD). The goal is to provide principal investigators a better understanding of the military utility of potential technology applications very early in the LDRD process. Early understanding should improve laboratory ability to produce LDRD results that have greater certainty for follow-on application development by the DoD.

The LDRD support to the application areas is managed by MT&A SMU Investment Area Teams for precision strike; modeling and simulation; sensors, intelligent systems, command, and control; and directed energy. The MT&A goal has been to identify S&T areas and competencies where mission technology LDRD investments are made that result in follow-on projects by DoD organizations. The MT&A SMU program managers' consensus is that much of the growth in SMU revenue since FY 1999 can be attributed to this strategy.

There are numerous examples where LDRD mission technology investment has recently accomplished or is accomplishing significant solutions for military needs. They include advanced, hard-target, penetrator missile; directed-energy systems featuring electric guns, short-pulse lasers, and high-power microwave; Swing Free Crane for stable naval logistics operations in high-sea states; unmanned aerial vehicle (UAV) synthetic-aperture radar (SAR) for improved surveillance and reconnaissance; chem-bio defense sensors for improved force protection; and modeling and simulation for military decision makers in complex environments.

* Military Technologies and Applications is formerly known as Emerging Threats.

*J. D. Tegnalia
Vice President of Military Technologies
and Applications
Sandia National Laboratories*

*There are numerous examples
where LDRD mission
technology investment has
recently accomplished or is
accomplishing significant
solutions for military needs.*

The military has provided significant funding for follow-on application development in each of those areas because of our expanded laboratory science, technology, and engineering (ST&E) competency base.

Future benefits and related SMU revenue growth will depend on our ability to strategically leverage our LDRD portfolio such that there are multiple potential benefits to military mission needs, and to ensure the success of internal partnerships with other SMUs to increase the size of the projects where more meaningful issues can be addressed.

Benefits of LDRD to Nonproliferation and Materials Control (NP&MC)

A. D. Romig, Jr., Vice President of Nonproliferation and Assessments

The Nonproliferation and Assessments* (NP&A) Strategic Management Unit is focused on the mission of reducing the vulnerability of the United States to the proliferation and use of weapons of mass destruction (WMD). The Laboratory Directed Research and Development (LDRD) Program has been and will continue to be critical to the contributions and solutions that NP&A makes to increasing our national security.

LDRD is essential to the process of advancing the science and technology of NP&A. It is the mechanism used to create, as well as to mature, new ideas, technologies, capabilities, and solutions for each of our program areas: remote sensing and verification, proliferation assessment, international security, physical security/surety, and chemical/biological nonproliferation. Because of LDRD, we can be more flexible and responsive to the quickly evolving environment around the threats and issues of WMD. It also allows us to anticipate and identify technological gaps of the future and begin working on them today.

Also, the flexibility of what can be explored with LDRD funds is unique within Sandia, and it gives the opportunity for the Laboratories' exceptional staff to pursue some of their most innovative ideas. It creates an environment where new high-risk, high-leverage technologies and ideas have the possibility of maturing to a usable state and helping solve current and future issues of national security.

In summary, with the ever-increasing danger in the world with respect to WMD, LDRD is vital to the long-term missions of the Laboratories and our contributions to the nation.

*A. D. Romig
Vice President of Nonproliferation and
Assessments
Sandia National Laboratories*

...the flexibility of what can be explored with LDRD funds is unique within Sandia, and it gives the opportunity for the Laboratories' exceptional staff to pursue some of their most innovative ideas.

* Nonproliferation and Assessments is formerly known as Nonproliferation and Materials Control.

Advanced Manufacturing

The objective of the Advanced Manufacturing investment area is to support Sandia's mission by advancing both the capability to fully understand and model manufacturing processes and the development of new processes and techniques to make product. Advanced Manufacturing promotes understanding the interactions between the design, fabrication processes, and environmental constraints, making it possible to ensure product that meets functional requirement the first time, every time. Research priorities in this investment area are manufacturability and rapid prototyping. Another important driver for manufacturing at Sandia is the need to go quickly from concept to prototype to production. The quick transitioning of R&D concepts into the manufacturing sector has become a pressing national issue identified in the many Homeland Security studies.

A new generation of micro-products is being built on complex subminiature components. These components are critical to the function of nuclear weapons and of devices being developed to address emerging threats, such as micro-sensors and micropumps. Complex microproducts have many bio-medical and pharmaceutical applications. Development of novel microfabrication techniques is required since current processes are

limited in dimensionality, material complexity, or microstructure control. *Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques* is developing novel methods to fabricate subminiature parts with nonplanar surfaces from engineering materials such as steels, kovar, plastics, and ceramics. Three patent disclosures have been filed as a result of this work.

26508

Mesoscale Wide-Bandwidth Linear Magnetic Actuators

L. A. Jones, M. P. Saavedra, T. R. Christenson, T. K. Mayer, R. Chanchani, D. Bethke, D. B. Webb, M. M. Heller, C. D. Blain

Electro-quasi-static actuators are almost always implemented in microsystems because of the ease of fabricating the electrodes. However, for mesoscale actuators—millimeter-scale devices—magneto-quasi-static actuators are more effective at producing forces and torques. The challenge with mesoscale magneto-quasi-static actuators is fabricating the magnetic windings. If permanent magnets are used in the actuator, a suitable process is also needed to fabricate the magnets.

Sandia investigated the processes necessary to fabricate mesoscale magnetic actuators. We fabricated mesoscale magnet arrays using microelectrodischarge machining (micro-EDM) and used a planar high-density circuit interconnect (HDI) process to fabricate complex high-current magnetic windings. We successfully used these processes to demonstrate the fabrication of a six-degree-of-freedom (6DOF) magnetic actuator. The actuator utilized precision-fabricated, multi-element magnet arrays and complex, high-density, three-phase, linear motor windings. We tested the actuator and showed it able to produce forces far higher than can be obtained with electro-quasi-static actuators.

Testing also showed that the windings fabricated with the HDI process can sustain very high current densities, densities that would destroy conventionally wound motor windings. We hypothesize that heat is able to easily flow out of the windings due to their intimate contact with the substrate.

The planar windings fabricated with this HDI process are extremely compact and benefit from the precision of lithographic techniques. The actuator implemented for this work demonstrates one topography and also the implementation of a magnetic bearing for precision X-Y positioning. Other promising applications include ultrathin, mesoscale rotary and linear pancake motors for precision single-axis servos.

We produced motor stator windings for the first time using the benzocyclobutene (BCB)/copper (Cu) HDI process. We fabricated four three-phase stators in close proximity on each silicon wafer. We processed only the first two layers of Cu in the six-layer design. Yield was poor due to particle contamination. Of eight wafers processed, only one wafer had

Sandia investigated the processes necessary to fabricate mesoscale magnetic actuators....The planar windings fabricated with this HDI process are extremely compact and benefit from the precision of lithographic techniques. The actuator implemented for this work demonstrates one topography and also the implementation of a magnetic bearing for precision X-Y positioning. Other promising applications include ultrathin, mesoscale rotary and linear pancake motors for precision single-axis servos.

motors with electrical continuity in all three phases, and on that wafer, only two of the four motors had three-phase continuity.

We used the first batch of wafers to test the current-carrying capacity of the stator windings. The results obtained were astounding. We achieved maximum current densities of $4\text{e}9 \text{ \AA/m}^2$ with no damage to the windings. This is equivalent to running 200 $\text{\AA}$ through 30-gauge wire.

We designed smaller stator windings to improve yields. Instead of requiring that four stators be simultaneously fabricated on one wafer, we diced the tested good stators from the fabrication wafer and bonded them onto a substrate in the proper positions relative to each other.

We successfully fabricated a platen with four Halbach arrays. Each Halbach array consisted of nine 35 MG-Oe neodymium-iron-boron magnets cut from a block using micro-EDM. Assembly of the arrays proved easier than expected when they were assembled directly in the platen over a high-permeability material.

We designed and constructed a test stand containing six laser-displacement sensors for measuring the position of the levitated platen and closing position servo loops.

We designed and constructed an amplifier circuit board containing 12-current amplifiers (four motors with three phases each).

We designed and constructed a digital interface circuit board so that a digital signal processor (DSP) could collect digital position information from the six laser-displacement sensors. The six channels of position measurements operated asynchronously at 50 kHz.

We implemented software for two DSPs, a measurement DSP and a control DSP. The measurement DSP collects position data and computes velocity estimates. The control DSP closes 10 kHz position servo loops for both levitating and motoring the platen. Three-phase vector control algorithms generate winding current commands from the normal and tangential force commands generated by the servo loops. The control DSP also interacts with the host DSP. We implemented software to stream 32 channels of data to the host at the servo rate.

We designed a wire-wound stator and fabricated the test stand structures to support this alternative approach (in case BCB/Cu stators could not be successfully fabricated). We engaged a precision coil-winding vendor to wind the stator coils, but after numerous attempts, the vendor was unable to achieve the required precision.

We successfully fabricated a platen with four Halbach arrays. Each Halbach array consisted of nine 35 MG-Oe neodymium-iron-boron magnets cut from a block using micro-EDM. Assembly of the arrays proved easier than expected when they were assembled directly in the platen over a high-permeability material.

We completed a second batch of stators using the BCB/Cu process and two layers of Cu. The yield was substantially better because of improved cleanliness procedures. Two wafers contained two completely good stators; we completed platen levitation tests using a platen with constrained lateral motions. We verified normal force production to be in good agreement with calculations. We confirmed proper commutation of the three-phase windings for generation of both normal and tangential forces.

We completed a third batch of stators with one wafer having three of four motors completely functional and conducted full magnetic suspension tests. (The previous tests with only two of four motors functional were conducted with lateral motions of the platen constrained.) We successfully controlled the platen on a 6DOF magnetic bearing. Unfortunately, before data could be taken, a disturbance in one of the servo loops caused the platen to impact one of the stators. The impact caused a short across turns in the motor stator, irreparably damaging the stator. The disturbance also caused a secondary impact and short on a second stator. With the loss of the only wafer with more than two good stators, we ended experiments.

We completed a second batch of stators using the BCB/Cu process and two layers of Cu.

The yield was substantially better because of improved cleanliness procedures. Two

wafers contained two completely good stators; we completed platen levitation tests using a platen with constrained lateral motions.

We verified normal force production to be in good agreement with calculations.

We confirmed proper commutation of the three-phase windings for generation of both normal and tangential forces.

26509

Levitated Three-Axis Microaccelerometer*F. J. Peter, R. D. Kinney, J. C. Gilkey, S. H. Kravitz*

Sandia's objective remains the significant advancement in the state of the art of accelerometer design for tactical-grade sensing applications. A quantum leap in performance improvement and cost reduction can be achieved only by a drastic new approach, not incremental improvements to existing concepts. This novel three-axis closed-loop accelerometer is implemented as a hybrid micromachine, which frees the designer from the size and material constraints of any given monolithic process and drastically expands the available design space. We can tailor the design to the dynamic range, resolution, bandwidth, and environmental requirements of the application while still preserving the benefits of microelectromechanical systems (MEMS) fabrication—precision, small size, low cost, and low power.

The project focused on understanding and solving the processing issues that contribute to three failure modes: high-voltage breakdown, poor material adhesion, and short circuits. We resolved the high-voltage breakdown and adhesion issues, but short circuits remain an ongoing issue that prevents us from yielding any usable hardware. The short-circuit issue is not a fundamental roadblock, but rather a process-control issue. Furthermore, there are no fundamental flaws in the design concept, and the hybrid implementation approach is appropriate from both a performance and a cost standpoint.

In parallel with our process-development troubleshooting efforts, we prepared for ultimate success by (1) developing an inexpensive, reliable hermetic packaging capability for the accelerometer and front-end electronics, and (2) creating a state-of-the-art control, test, data-acquisition, and analysis hardware/software capability. These packaging and test capabilities are ready to go upon receipt of functional accelerometer hardware.

We made the following accomplishments:

- Refined the gold via plating process to reduce processing flow time by 80% (from 5 days to 1 day). The payoff here is enormous and is currently paying dividends on other projects, as well.
- Developed a precision laser rework capability to open short circuits due to fabrication imperfections. This greatly reduced the pressure to achieve 100% yield off the line.

Sandia's objective remains the significant advancement in the state of the art of accelerometer design for tactical-grade sensing applications. A quantum leap in performance improvement and cost reduction can be achieved only by a drastic new approach, not incremental improvements to existing concepts.

- Instituted design changes that decouple process and assembly steps from each other as much as practical to minimize sensitivity to process yields.
- Solved the high-voltage breakdown problem by suitable combination of materials, dimensions, and process parameters.
- Solved the adhesion issues resolved by appropriate wet- and dry-cleaning procedures and a choice of materials.
- Based on control-system stability analysis, decided to mechanically decouple each degree of freedom (X, Y, Z translation, X tilt, Y tilt) from each other to greatly enhance stability.
- Designed and built higher-performance (lower-noise), smaller-volume, multichannel sense and control electronics.
- Developed a very inexpensive, reliable, hermetic semicustom package suitable for the ultimate product. We based the concept on modifying a commercial leadless chip carrier by etching conductive traces in the floor, then flip-chip mounting the accelerometer body and charge amplifier. This very inexpensive packaging scheme provides hermeticity as well as a low parasitic electrical connection between the pickoff electrode and the front-end electronics.
- Matured several key processes (conductive vias, anodic bonding, wafer lapping and polishing) to the point where they enabled and facilitated other MEMS products and applications: hybrid microsystem integration, fuel cells, biological fluid handling, microelectrochemical sensors, and bulk silicon inertial switches.

26510

Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques

D. P. Adams, J. E. Mikkalson, T. M. Mayer, M. J. Vasile

This project researched new methods for fabricating geometrically complex microscale components, instruments, and devices. Sandia developed focused-ion-beam (FIB) techniques to precisely sculpt curved-shape components and fabricate devices on nonplanar substrates. Currently, there is a need for small devices having nonplanar features. This includes miniature components critical to Nuclear Weapons and Emerging Threats, such as microactuators, microsolenoids, micropumps, and microsensors.

Specifically, we demonstrated

- (1) Damascene processes that make miniature coils (conductor widths ~ 25 nm),*
- (2) Ion-beam lathe processes that fabricate microcoils (conductor widths < 25 μm),*
- (3) Three-dimensional (3-D) ion-sculpting techniques that mill curved shapes successfully in a variety of material targets, and*
- (4) FIB chemical vapor deposition (CVD) techniques that additively sculpt curved shapes.*

We documented the details involved with successful FIB sculpting in a series of papers. This includes studies of surface-morphology evolution in different materials, as this evolution depends on ion-beam incidence angle, chemical environment (through reactive-gas-assisted processes), and ion dose. We determined the properties of prototyped devices, e.g., microcoils, demonstrating the precise nature of FIB methods to define submicron features over curved substrate geometries.

We researched FIB methods for fabricating geometrically complex features, components, instruments, and devices. We explored several techniques, including subtractive and additive FIB-based methods.

This project researched new methods for fabricating geometrically complex microscale components, instruments, and devices. Sandia developed focused-ion-beam (FIB) techniques to precisely sculpt curved-shape components and fabricate devices on nonplanar substrates. Currently, there is a need for small devices having nonplanar features. This includes miniature components critical to Nuclear Weapons and Emerging Threats, such as microactuators, microsolenoids, micropumps, and microsensors.

(left) Microcoil on glass tube patterned by an FIB lathe process. (right) Microcoil on PEEK cylinder patterned by an FIB-enabled Damascene process.

In general, we successfully used FIB techniques to prototype curved-shape components and simple devices on nonplanar substrates. For example, the ion-beam lathe process demonstrated in this work makes helical coils with feature sizes to $\sim 1\ \mu\text{m}$. We measured the properties of microcoils having micron-size features to demonstrate the precise nature of FIB methods for fabricating these structures. Although FIB techniques are not capable of parallel (rapid) manufacturing of these structures, these methods provide the ability to work with almost any solid material. Additionally, we refined techniques for the 3-D shaping of solids. We researched the ion shaping of predetermined curved shapes for a variety of target materials, including semiconductors, single-crystal metals, polycrystalline metals, and low-density aerogels. This technique shows promise in controlling shapes such as hemispheres, parabolas, and sine waves in amorphous materials such as diamond or silicon. Also, we found that net shape can be controlled well in single-crystal metals and fine-grain polycrystalline metals, although the effects of ion channeling somewhat complicate our ability to tailor feature shape. Difficulties arise in the 3-D milling of polycrystalline materials when the feature width is similar in dimension to the grain width of the target material. Also, target materials that have a variable density complicate our techniques.

Our research probed the evolution of ion-induced surface morphology (a nuisance in many applications of micromachining) as a function of ion dose, incidence angle, chemical environment (through reactive-sputtering processes), and other beam-control parameters.

Refereed

Adams, D. P., M. J. Vasile, and T. M. Mayer. 2003. Focused-ion-beam milling of diamond: Effects of H_2O on yield, surface morphology, and microstructure. *J. Vacuum Science and Technology B*, accepted.

Picard, Y. N., D. P. Adams, M. J. Vasile, and M. B. Ritchey. 2003. Focused-ion-beam-shaped microtools for ultraprecision machining of cylindrical components. *Precision Engineering* 27:59–69.

...we successfully used FIB techniques to prototype curved-shape components and simple devices on nonplanar substrates....Although FIB techniques are not capable of parallel (rapid) manufacturing of these structures, these methods provide the ability to work with almost any solid material....Also, we found that net shape can be controlled well in single-crystal metals and fine-grain polycrystalline metals,....

Other Communications

Adams, D. P. 2003. Evolution of surface morphology during focused-ion-beam sputtering and gas-assisted sputtering processes. *Proc. Microscopy and Microanalysis* 9 (August, San Antonio, Texas): 114.

26511

Resolving Fundamental Limits of Adhesive Bonding in Microfabrication

R. K. Giunta, M. S. Kent, D. R. Adkins, J. A. Emerson

As electronic and optical components reach the micro- and nanoscales, efficient assembly and packaging require the use of adhesive bonds. This work focuses on resolving several fundamental issues in the transition from macro- to micro- to nanobonding. A primary issue is that, as bondline thicknesses decrease, knowledge of the stability and dewetting dynamics of thin adhesive films is important to obtain robust, void-free adhesive bonds. While researchers have studied dewetting dynamics of thin films of model nonpolar polymers, little experimental work has been done regarding dewetting dynamics of thin adhesive films, which exhibit more complex short-range interactions. The areas of contact mechanics, capillary fluid flow, surface energetics, and wetting have all been investigated. By resolving these adhesive-bonding issues, Sandia is allowing significantly smaller devices to be designed and fabricated. Simultaneously, we are increasing the manufacturability and reliability of these devices.

We extended studies of wetting and dewetting of epoxy systems to the use of one resin system with four cross-linkers. We correlated the tendency of a system to dewet with the rate of reaction of the system. There appears to be a significant acceleration of the cross-linking reaction at the substrate surface. This acceleration was observed only in the presence of ambient moisture—the acceleration did not occur when experiments were performed in a dry nitrogen glove-box atmosphere. In the cases where the acceleration of the reaction occurred, a thick film formed on the surface that would not wash off after exhaustive rinsing with toluene. This occurred within 1 min of coating the wafer. In contrast, a bulk sample gelled after approximately 4 hrs. We suggest that, to select a system that will not dewet, one could experimentally determine whether a thick film forms on the substrate surface immediately after coating.

In other work related to wetting and dewetting, we used nanoparticles to inhibit dewetting of polymer films. PECH (polyepichlorohydrin) and BSP3 are polymers used for surface acoustic-wave (SAW) coatings in μ ChemLab™. Dewetting of these coatings adversely affects the sensitivity of the devices, particularly after exposure to solvent vapors. With the addition

This work focuses on resolving several fundamental issues in the transition from macro- to micro- to nanobonding....By resolving these adhesive-bonding issues, Sandia is allowing significantly smaller devices to be designed and fabricated. Simultaneously, we are increasing the manufacturability and reliability of these devices.

of 1% by weight of fullerenes (C60), dewetting was completely eliminated, even after exposure to solvent vapor for 1 week.

Additional work related to dispensing of polymers to create robust polymer films. We investigated drop coating and spray coating. We found that more uniform, reproducible films could be formed by spray coating films through a shadow mask, compared to drop coating in a defined area.

Other Communications

Giunta, R. K., M. S. Kent, J. S. Hall, H. Yim, S. T.

Hammerand, D. R. Tallant, and M. J. Garcia.

2003. Dewetting dynamics of thin epoxy films.

Proc. 26th Annual Adhesion Society **26** (February, Myrtle Beach, South Carolina): 151–53.

38605

Microfabrication with Femtosecond-Laser Processing

M. L. Griffith, T. S. Luk, P. Yang, D. E. Reckaway, G. R. Burns

This research investigates the special characteristics of femtosecond-laser processing for microfabrication. Sandia will explore the basic mechanisms of femtosecond-laser ablation, gain a science-based understanding of the process, and determine the process parameter space for laser processing of metals and glasses. We will study the effect of laser and environmental parameters on removal rate, feature size/definition, aspect ratio, and material structure. We will address manufacturing requirements for component fabrication, including precision and reproducibility. We will design and assemble a femtosecond-laser manufacturing system and develop the computer-aided design (CAD)-to-part sequence. Success will permit us to miniaturize multiple components.

Initial studies show that femtosecond-laser processing is a promising manufacturing technology for the fabrication of microcomponents. We demonstrated, with a basic understanding of travel velocity and layer decrement on resulting channel morphology, that complex shapes can be fabricated in stainless steel. A key factor in producing clean features is choosing the correct layer decrement that allows the ionized species to escape the channel.

Using a unique nonlinear absorption behavior, we demonstrated that femtosecond-laser pulses, when properly adjusted, can locally modify the glass structure and directly fabricate waveguides in bulk glass. The normalized Raman spectra show an increase in the 490 and 605 cm^{-1} peaks in the damaged region, indicating an increase in the number of four- and three-membered ring structures in the silica network. The formation of these four- and three-ring structures is sometimes associated with the creation of new quasi surfaces at small voids in the silica-rich matrices. In addition, the Raman band peaking between 400 and 500 cm^{-1} is significantly narrower in the spectra from laser-modified regions compared to the bulk glass. The relative narrowness of the bands in the spectra indicates that the silica networks in these areas have a smaller distribution of ring sizes, with fewer large rings. This type of modification of the silica network is typically achieved by quick melting followed by fast resolidification during the laser process. Optical measurements show that these laser-modified regions possess an optical birefringence property that can be

This research investigates the special characteristics of femtosecond-laser processing for microfabrication. Sandia will explore the basic mechanisms of femtosecond-laser ablation, gain a science-based understanding of the process, and determine the process parameter space for laser processing of metals and glasses....Success will permit us to miniaturize multiple components.

controlled by the polarization direction of the laser beam. The capability of creating and controlling birefringence properties in glass by laser processing could have significant implications for the development of novel optical devices.

Refereed

Max, K. L. 2003. Microfabrication with femtosecond laser processing. Master's thesis, Department of Mechanical Engineering, University of New Mexico, Albuquerque, New Mexico (August).

Yang, P., G. R. Burns, J. P. Guo, and A. G. Vawter. 2003. Femtosecond laser pulse induced birefringence in optically isotropic glass. *Applied Physics Letters*, submitted. SAND2003-3213J (August).

Other Communications

Griffith, M. L., M. T. Ensiz, and D. E. Reckaway. 2003. Femtosecond laser machining of steel. *Proc. SPIE, Photon Processing in Microelectronics and Photonics II SPIE4977* (Photonics West, January, San Jose, California): 118–22.

Griffith, M. L., P. Yang, G. R. Burns, and M. Harris. 2003. Microfabrication with femtosecond laser processing. *Proc. 14th Annual Solid Freeform Fabrication Symposium* **14** (August, Austin, Texas).

Yang, P., D. R. Tallant, G. R. Burns, and M. L. Griffith. 2003. Femtosecond laser pulse induced refractive index changes in glasses. Paper presented at the 2003 Materials Research Society Fall Meeting, 2 December, Boston, Massachusetts.

38606

Mesoscale-Controlled Motion for a Microfluidic Drop Ejector

P. C. Galambos, M. T. Ensiz, R. J. Shul, S. S. Mani, B. Jokiel, Jr., R. K. Giunta, M. Okandan, R. C. Givler, A. Lopez, K. R. Pohl

Sandia concentrated on testing the first MEMS (microelectromechanical systems) sideshooter ejector designs (fabricated previously) and on designing the patterning system, including packaging, that controls and directs the MEMS ejector. We submitted a patent application covering this system.

In the patterning system control and packaging area, we further developed the electromicrofluidic dual in-line package (EMDIP) for use with drop ejectors. We developed monolithic rapid-prototype flow-manifold inserts for die-attach and produced fluid-routing fluidic printed wiring boards (FPWBs) to accept the EMDIP, insert, and MEMS die assembly. We completed initial designs and purchased parts for the first ejection-control system.

In the drop-ejector testing area, we developed a flexible and user-friendly ejector test station, allowing application of power to MEMS ejectors in a side-mounted configuration, valve-controlled gravity and pneumatic liquid feed, and in-ejector pressure measurement. Experiments demonstrated dry actuation, filling with several liquids, and wet actuation (meniscus bulge), but not yet drop ejection. We have begun the second MEMS ejector design.

Our primary focus on the MEMS side of the project was to characterize the RS349 ejector designs that completed fabrication. Characterization of these designs proved to be a more difficult and time-consuming task than we originally envisioned, but it has potential long-term payoff in terms of better device packaging, a better testing setup, and a more thoroughly characterized microfluidic device.

We made significant modifications to the ejector test station. Our test setup was significantly impacted by a previous project involving electromicrofluidic packaging. The test station microfluidic package utilizes an acrylic flow manifold with a polyether ether ketone (PEEK) insert containing flow passages to which the microfluidic silicon (Si) die is attached using double-sided tape aligned with a flip-chip bonder. Fluid travels through the acrylic manifold and PEEK insert into the Si die from the back through Bosch-etched vias. We made electrical connections to the front of the electromicrofluidic die, similar to the EMDIP, developed for the electromicrofluidic

Sandia concentrated on testing the first MEMS (microelectromechanical systems) sideshooter ejector designs (fabricated previously) and on designing the patterning system, including packaging, that controls and directs the MEMS ejector. We submitted a patent application covering this system.

packaging project. The new test station has the following improved features: multiple (8) input/output (I/O) ports allowing four different liquids inlet and outlet to on-Si microfluidic devices; I/O and bleed ports allowing rapid and controlled liquid filling of devices (~ 1 min); acrylic flow manifold allowing both front and back observation of liquid in both meso- and microscale flow passages; pressure sensor built into flow manifold allowing pressure monitoring a few millimeters from the die; pressure/vacuum control using house air and vacuum; probe electrical access to the front of the die, essentially a vertical probe station with fluid connections; front-, back-, and side-magnification lenses and cameras; and mountable, high-intensity light-emitting diodes (LEDs) that can be strobed for high-speed visualization.

We conducted dry testing of ejector actuation to confirm that the ejector design was viable, to establish voltage versus displacement curves for known good ejectors, to determine the repeatability of ejector operation, and to examine the effect of various design variations on ejector actuation, specifically 4 bank versus 6 bank versus 11 bank actuator designs (a bank is 4 actuator subunits), and 6 mm versus 10 mm travel actuator designs.

The die that has a drop-ejector device is packaged into an EMDIP. The EMDIP is plugged into the FPWB. The FPWB is then inverted and mounted to the underside of the bracket on the Z-stage.

38608

Science-Based Sensing of Phase Transformations in Steels

F. J. Zutavern, C. V. Robino, P. S. Duran, M. W. O'Malley, M. Reece

The ability to control microstructure and residual stress distribution in forgings, welds, and structural materials is fundamentally based on control of solid-state phase transformations. However, the ability to directly sense and monitor the progress of phase transformations in real time under steady-state and transient thermal conditions is lacking. Recent advances in experimental and numerical approaches to the study of solid-state transformations in steels provide a basis for developing new sensors for phase-transformation kinetics. Advances in high-speed dilatometry and high-speed, high-resolution, hot-stage microscopy provide accurate data for comparison with electromagnetic (EM) and laser ultrasonic (LU) sensor results. Advanced numerical models, including a model for interpretation of dilation data and validated EM modeling of ferromagnetic materials, are also key to understanding the sensor output and sensitivity. Sandia is investigating the use of advanced active and passive EM sensors and LU methods to directly sense and monitor the progress of phase transformations in ferromagnetic steels during steady-state and transient heating conditions. Miniature inductive sensors are sensitive to magnetic permeability and resistivity changes caused by changes in temperature and related directly to the phase transition from ferrite to austenite. Short-pulse LU sensors are also sensitive to temperature and microstructural variations related to the ferrite-to-austenite phase transition, as well as stress, defects, and dimensional variations. Applications for these sensors include forging, welding, and thermomechanical processing of steels and other materials. The sensor analysis will utilize the computational models to benchmark the sensitivity of the methods and results. Success in this has broad applications to optimization of thermomechanical processing and joining of steels and other materials for the national manufacturing community.

We adapted the vacuum heat-treating and -sensing test apparatus (Gleeble) for magnetic sensors and their respective data-acquisition equipment. We outfitted the Gleeble with a precision x-y-z positioner and high-bandwidth, low-noise signal feed-throughs to accurately locate and monitor the magnetic sensors. We designed, fabricated, and tested five types of thermally protected sensors with steel samples heated to 950°C:

Sandia is investigating the use of advanced active and passive EM sensors and LU methods to directly sense and monitor the progress of phase transformations in ferromagnetic steels during steady-state and transient heating conditions. ...Applications for these sensors include forging, welding, and thermomechanical processing of steels and other materials. ...Success in this has broad applications to optimization of thermomechanical processing and joining of steels and other materials for the national manufacturing community.

water-cooled, and four types of radiation shields—thin foil, graphite, glass tube, and palladium-coated glass tube.

We programmed the Gleeble for several magnetic sensor tests. We wired control signals (voltage, current, and synchronizing trigger) from the control system to the data-acquisition system to synchronize the magnetic sensor data with the information from the control system (time, temperatures, voltage, current, and power angle) for both heating and cooling processes. We thoroughly tested the Gleeble to verify signal accuracy and timing precision with the data-acquisition system and the control signals.

We tested six magnetic sensors (radial, azimuthal, and coaxial magnetic-field orientations in vacuum and ferrite-coupled configurations) in the passive mode, where magnetic fields generated by the heating current are detected. The fast-rise, short-pulse heating current was spectrally analyzed to assess its impact on passive and active sensing. We have already identified some of the characteristic properties of the magnetic phase transition in the initial data from the passive sensors. We programmed the Gleeble to scan repeatedly across the Curie point (770°C) over a 50°C range. We acquired data for the different sensors and are analyzing them to extract magnetic phase-transformation effects.

For the active mode, where the sensor supplies a higher-frequency signal to generate magnetic fields, we designed and fabricated high-pass, high-power, analog electronic filters. These filters reduce the low-frequency heating signal generated at the sensors and protect signal generators, amplifiers, and digitizers. This is not an insignificant issue, because more than 10 kA of current can flow through the sample in 1 ms-wide pulses. The sudden rise and fall of this heating current within a few millimeters of the magnetic sensors can easily produce spikes that are greater than 1 kV. We assembled a variety of steels with a range of phase-transformation behaviors for testing. Previously unavailable data for steady-state, high-temperature EM properties have been contracted with a professional laboratory that specializes in these measurements. They are extending the temperature range of their measurements to include the magnetic phase transition (770°C). In preparation for correlation with the sensor measurements, we developed and implemented significant improvements in Gleeble dilatometry.

Contracted measurements of static B-H curves were completed and delivered to Sandia for comparison to the dynamic results measured with the Gleeble.

Tests were completed and data acquired on a range of steel samples in the Gleeble traversing the Curie point ($\sim 770^{\circ}\text{C}$) with our best passive and active magnetic sensors. The analysis of these data and final results will be provided in the final report.

We abandoned the LU part of the proposal and completed the magnetic sensor research.

52523

Atomic-Layer Deposition of Highly Conformal Tribological Coatings

T. M. Mayer, N. R. Moody, R. S. Goeke, M. T. Dugger, S. V. Prasad, R. W. Scharf

Friction and wear are major concerns in the performance and reliability of microelectromechanical systems (MEMS) devices. The severe geometric constraints of many such devices (high-aspect ratios, shadowed surfaces) make most deposition methods for friction and wear-resistance coatings impossible. Sandia proposes to produce and evaluate highly conformal tribological coatings, deposited by atomic-layer deposition (ALD), for use on surface-micromachined (SMM) and LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) structures. ALD is a chemical vapor deposition (CVD) process using sequential exposure of reagents and self-limiting surface chemistry, saturating at a maximum of one monolayer per exposure cycle. The self-limiting chemistry results in conformal coating of high-aspect-ratio structures with monolayer precision. ALD of a wide variety of materials is possible, but there have been no studies of structural, mechanical, and tribological properties of these films. We will develop processes for depositing thin (< 100 nm) conformal coatings of selected hard and lubricious films (aluminum oxide $[Al_2O_3]$, zinc oxide $[ZnO]$, tungsten disulfide $[WS_2]$, and tungsten/tungsten nitride $[W/WN]$ nanolaminates) and will measure their properties. A significant challenge is to develop instrumentation and quantitative test procedures, which do not now exist, for friction, wear, film/substrate adhesion, elastic properties, stress, etc., of extremely thin films and nanolaminates. We will employ new scanning-probe and nanoindentation techniques, along with detailed mechanics-based models, to evaluate these properties at small loads characteristic of microsystem operation. We will emphasize deposition processes and fundamental properties of ALD materials; however, we will evaluate film performance for model SMM and LIGA devices. Success will greatly expand the range of applications and long-term performance and reliability of micromechanical systems.

We achieved all of the major goals on development of the ALD reactor and material-deposition processes, preliminary screening measurements of friction and wear of ALD materials, and development of mechanical-property measurements for ALD films.

Sandia proposes to produce and evaluate highly conformal tribological coatings, deposited by atomic-layer deposition (ALD), for use on surface-micromachined (SMM) and LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) structures....Success will greatly expand the range of applications and long-term performance and reliability of micromechanical systems.

We completed construction of the ALD reactor and developed processes for depositing Al_2O_3 and ZnO . We optimized process parameters (pressure, flowrate, temperature, expose/purge times) in a design-of-experiments format. We demonstrated excellent control of deposition rate, thickness, and conformality. We devoted efforts in tribology and mechanical-property measurement to establishing measurement procedures for these very thin films. We made initial friction measurements using a linear wear tester in a ball-on-disk configuration. Measurements on 10 nm Al_2O_3 films show a friction coefficient of ~ 0.3 , comparable to the silicon (Si) substrate; however, much less wear debris was present on the Al_2O_3 -coated sample. The friction coefficient of ALD ZnO films was ~ 0.2 , significantly less than that of the sintered (large-grain) ZnO disk (0.7–0.8), and nearly independent of film thickness, up to 600 nm.

We conducted mechanical-property tests on W and Al_2O_3 films for thicknesses of 1 to 200 nm. We measured modulus and hardness values using nanoindentation. For W and Al_2O_3 films up to 10 nm thick, properties tracked substrate values. Properties for thicker films varied strongly with composition and thickness, where values of the W films increased with film thickness to values significantly higher than the substrate. The Al_2O_3 films were more compliant and softer than the W films and the substrate. We used nanoscratch tests with Berkovich and conical indenter tips to determine scratch resistance for the W and Al_2O_3 films. The conical indenter tests showed a strong surface effect and evidence of delamination and spalling at high loads due to large area contact.

Refereed

Mayer, T. M. 2003. Atomic-layer deposition for MEMS applications. Paper presented at ALD 2003, August, San Jose, California.

Mayer, T. M., J. W. Elam, S. M. George, N. R. Moody, S. V. Prasad, P. G. Kotula, and R. S. Goeke. 2002. Atomic-layer deposition of tribological coatings for MEMS devices. Paper presented at the AVS International Symposium, November, Denver, Colorado.

Mayer, T. M., J. W. Elam, S. M. George, P. G. Kotula, and R. S. Goeke. 2003. Atomic-layer deposition of wear-resistant films for micromechanical devices. *Appl. Phys. Lett.* **82**:2883.

Moody, N. R., T. E. Buchheit, B. L. Boyce, T. M. Mayer, and S. M. George. 2003. Mechanical behavior of conformal ALD films. Paper presented at the HARMST Workshop, June, Monterey, California.

Moody, N. R., T. E. Buchheit, B. L. Boyce, T. M. Mayer, and S. M. George. 2003. Thickness effects on mechanical behavior of ALD films. Paper presented at the Materials Research Society Spring Meeting, April, San Francisco, California.

Prasad, S. V., M. T. Dugger, T. M. Mayer, P. G. Kotula, and S. M. George. 2003. Atomic-layer-deposited tribological films for microsystems applications. Paper presented at the STLE Annual Meeting, April, New York, New York.

52524

Assembly of Microsystems Using Exothermic Multilayer Thin Films

D. P. Adams, T. E. Buchheit, F. M. Hosking, M. C. Grubelich, C. P. Tigges, T. T. Covert, K. A. Peterson

Sandia is researching new micro- and mesosystem assembly techniques involving energetic thin films. Energetic films consist of two or more reactive materials typically deposited as a heterostructure. If properly designed, layered materials can be stimulated in a local region to cause a self-propagating reaction (alloying) over great distances. Reactions can be ignited via a thermal impulse from some lasers, exploding bridgewires, or other mechanical methods.

A few research groups other than our project team are currently studying energetic multilayer films. These include T. Weihs (Reactive Nanotechnologies, Johns Hopkins University), T. Barbee (Lawrence Livermore National Laboratory [LLNL]), and John Moore (professor, Colorado School of Mines). Elegant work by Weihs demonstrates the relationship between multilayer design and propagation velocity for a few systems (nickel [Ni]/aluminum [Al], niobium [Nb]/silicon [Si]). Moore and his collaborators have researched combustion synthesis for many years; only recently has this group begun to investigate energetic films. As stated independently by Weihs and Moore, a great deal of research is required to make combustion synthesis a viable assembly technology.

In this project, microsystem assembly primarily involves joining. We intend to use the heat liberated by a self-propagating reaction to bond dissimilar parent materials. Joining via exothermic films holds promise for minimizing the heat on temperature-sensitive parts of a microsystem because the reaction can be rapid (> 1 m/s). We are also considering other microactuation/assembly techniques involving energetic films in this project besides joining. For example, we can use a large stress change resulting from a rapid exothermic reaction to deflect a micromechanical switch. Our current research on exothermic thin films intends to do the following:

- (1) Increase the number of known energetic material (EM) pairs that exhibit a self-propagating reaction.*
- (2) Research techniques that pattern/machine energetic films without stimulating reactions.*
- (3) Research ignition thresholds (testing involves ultrashort-pulse lasers).*
- (4) Characterize and improve the resultant mechanical properties of reacted films.*

Sandia is researching new micro- and mesosystem assembly techniques involving energetic thin films....In this project, microsystem assembly primarily involves joining. We intend to use the heat liberated by a self-propagating reaction to bond dissimilar parent materials. Joining via exothermic films holds promise for minimizing the heat on temperature-sensitive parts of a microsystem because the reaction can be rapid (> 1 m/s).

(5) *Measure stress of reacted films and determine the origin.*

(6) *Research how stoichiometric variations (away from targeted compositions) affect properties.*

(7) *Demonstrate joining over a number of length scales.*

We made the following accomplishments:

- Selected initial material systems for research
- Developed a process for sputter-depositing multilayers that avoids *in situ* (premature) reaction
- Successfully deposited unreacted metal-metal multilayers onto planar, witness samples
- Characterized microstructure, phase, and purity of unreacted multilayers
- Demonstrated self-propagating reactions on flat substrates for different multilayer designs
- Measured propagation velocities on flat substrates as a function of multilayer design
- Characterized microstructure, phase, purity, and mechanical properties of reacted multilayers.

Multilayers deposited included Ni/titanium (Ti), Al/Ti, cobalt (Co)/Al, iron (Fe)/Al, Co/Si, Al/platinum (Pt), and Ti/boron (B). We considered several properties when choosing pairs of EMs. We first required materials that exhibit a self-propagating reaction. In addition to a $\Delta H(T_{ig})$, we chose several multilayer systems because bulk alloys of similar composition exhibit ductility. Systems such as monoclinic Ni/Ti are ductile and should be able to accommodate the extrinsic stress that results from being cooled down to room temperature after the reactions. Each of the material pairs grown to date exhibits gasless reactions. This is important for “ease of handling.” Furthermore, a gasless reaction can result in a dense product.

We are researching two strategies for joining. First, we are studying multilayers that combust with the reactant materials maintained at room temperature prior to ignition. These multilayer systems are considered useful for maintaining low temperatures in heat-sensitive microsystems since no preheating is required. However, several of these material pairs are identified as difficult to handle. Second, we are studying multilayer systems, e.g., Ni/Ti, that require a slight preheat prior to ignition. The reactants must be heated briefly to a few hundred degrees Celsius to allow for a self-propagating reaction. We are researching in detail the conditions (T, t) required to ensure ignition and a self-propagating reaction for different multilayer designs. We are collaborating with the Colorado School of Mines on this effort.

We used sputter deposition to grow numerous energetic films of different design. This technique is beneficial because it offers Ångstrom-level control of film thickness and composition. Sputtering allows deposition of almost any elemental material and most compounds. Materials layered in vacuum have improved properties compared with powder or laminated-foil reactants. Vapor deposition improves purity, reaction reproducibility, and compositional control compared with powder-reactant methods. This can lead to improved mechanical properties of the reacted alloy. We deposited and tested films of different multilayer design for their reactions. In general, several material systems show a self-propagating reaction when ignited by a bridgewire.

Other Communications

Adams, D. P., C. P. Tigges, M. Rodriguez, and J. B. Kelley. 2003. Properties of reacted metal multilayers. Paper presented at the American Vacuum Society (AVS) Meeting, Baltimore, Maryland.

We used sputter deposition to grow numerous energetic films of different design. This technique is beneficial because it offers Ångstrom-level control of film thickness and composition. Sputtering allows deposition of almost any elemental material and most compounds.

52526

Intelligent Interaction Control as Applied to Metrology and Assembly of Microscale Components

D. M. Kozlowski, J. F. Jones, G. A. Johnston

Despite many compelling reasons for employing microelectromechanical systems (MEMS) devices in weapon systems, a major hindrance to the introduction of these devices remains qualification and assembly. A fundamental area that continues to plague the qualification sequence is dimensional metrology. For example, a metal spring that potentially can be used within a device is currently specified at $26.0 \pm 0.1 \mu\text{m}$. This tolerance implies a measurement resolution of $0.01 \mu\text{m}$. Thus, an efficient way to perform the qualification measurements is through a precision x-ray lithography technique used to manufacture microparts. Meanwhile, many assembly tasks seen in the weapons programs have traditionally resisted automation because positional uncertainty was far greater than assembly tolerances allowed. The inability to control the forces of contact on the workpieces hindered applications. Unlike robots, humans can easily learn complex assembly tasks, such as meshing gears or aligning and inserting spline shafts. To achieve comparable levels of assembly performance, robots need to exhibit two characteristics that are natural to humans: (1) a method for accommodating assembly tolerances less than the positional uncertainty, and (2) the ability to learn how to use forces and torques of environmental interactions to converge on a solution that produces a successful assembly.

Sandia will develop key enabling technologies for a new cost-effective approach to the gauged metrology of parts of micromachines. This approach combines rigid-body mechanics, high-fidelity compliant control, and gauge design and construction via x-ray lithography. Given a part and its specifications, we will design a gauge simultaneously with a compliantly controlled insertion strategy to assess the dimensional aspects of microparts. We will also attempt to design testing strategies that allow sliding contacts with the manipulator and that guarantee performance of the gauging task.

We completed a thorough analysis of current research in microscale interaction forces. In this analysis, we documented the theories behind various microscale phenomena and highlighted previous research accomplished in each area. The

Sandia will develop key enabling technologies for a new cost-effective approach to the gauged metrology of parts of micromachines.

most significant microscale interaction forces include surface-tension forces, van der Waals forces, electrostatic forces, and magnetic forces. These forces are complex in nature and are dependent on various factors, including humidity, surface roughness, electric charge, part geometry, etc. It is important to note that most research work focused on the area of contamination and particle adhesion in the 1970s through the early 1980s with the importance of the integrated circuit industry. Thus, complex interactions have been intensively studied for simplified cases, i.e., particles can be simply modeled as spheres. In recent years, with the increasing importance of MEMS technology, work has focused on cases dealing with more-complex geometry. However, there still appears to be limited knowledge and experimental support for these complex interactions.

We completed extensive modeling on the ParaDex I hardware. This allows for a more-detailed simulation of the ParaDex robot in both position and admittance-control applications. Thus, we can verify stability and performance before making changes to the external hardware. We also completed hardware and tooling modifications to test a micro-LIGA (the German term *Lithographie, Galvanoformung, und Abformung*, for lithography, electroforming, and molding) candidate part and gauge on a macroscale.

We began algorithm development on insertion strategies for the macrosize mating problem. For the candidate application, we identified an orientable insertion strategy and are testing the strategy. We also investigated intelligent algorithms for part mating. Currently, by devising an insertion strategy into a series of discrete states and identifying those states in an “intelligent” manner, it may be possible to devise an iterative learner for future years.

We completed extensive modeling on the ParaDex I hardware. This allows for a more-detailed simulation of the ParaDex robot in both position and admittance-control applications. Thus, we can verify stability and performance before making changes to the external hardware.

52527

Rapid-Prototyping High-Density Circuitry (RpHdc)

D. W. Davis, P. Yang, M. L. Griffith, T. K. Litts, B. D. Chavez, J. A. Palmer, J. M. Kelton, G. R. Burns, P. G. Clem

Sandia will develop a new manufacturing process to integrate complex modeling, rapid-prototype stereolithography processes, and direct-write technology for the fabrication of three-dimensional (3-D), high-density circuits. This paperless manufacturing technology provides a greater flexibility for rapid development and deployment of new designs, especially for systems with weight and space restrictions.

We will conduct the research along two intertwined paths: materials and process. The materials path will be guided by both the inherent customer requirements (physical and chemical compatibilities with different materials in the fabrication process, stability of the underlying substrate, conductivity and longevity of the drawn circuit material, etc.), and the inherent limitations of stereolithography-compatible photopolymers (low glass-transition temperatures, mechanical properties, etc.). The process studies will revolve around techniques to start, stop, fixture, and reregister stereolithography builds, as well as the mechanics of depositing the circuit materials onto the layer-manufactured substrates. We will also study techniques to embed sensors, create multilayer embedded circuits, and provide robust interconnects.

The impact of this new technology will provide for the direct writing of high-density conductive paths directly onto, and embedded in, the layers of the complex model. This technology will eliminate many of the labor-intensive tasks currently required during the assembly process. This technology will also reduce the hardware required to interconnect assemblies and will combine known technologies to develop a single electrical/mechanical "design-to-manufacturing" process in support of rapid development and deployment of fully functional prototypes as the final product.

- *Test pattern.* We designed a test pattern that would challenge the equipment suppliers with lines and spaces ranging from 1 mil to 12 mils thick.

We selected three companies for evaluation: Optomec, Inc., in Albuquerque, New Mexico, nScript in Stillwater, Oklahoma, and Micropen/OhmCraft in Honeoye, New York. These companies were able to write smaller than 2 mil lines on the test

Sandia will develop a new manufacturing process to integrate complex modeling, rapid-prototype stereolithography processes, and direct-write technology for the fabrication of three-dimensional (3-D), high-density circuits....The impact of this new technology will provide for the direct writing of high-density conductive paths directly onto, and embedded in, the layers of the complex model.

pattern we supplied. Optomec was unable to supply us with usable samples and was eliminated from the selection process.

The substrate materials selected on which to write the test patterns were FR4 and Polyimide printed wiring board (PWB) material and SI-40 stereolithography resin material.

Micropen used three different inks in their samples. Silver (Ag) and platinum (Pt) were the base materials in the inks from Paralec and Acheson. nScript used Heraeus PC5915 Ag ink in all of their samples. The Heraeus ink had the best resistive properties of all the inks used.

- *Stereolithography material compatibility.* Both Micropen and nScript were able to write and cure working patterns using conductive inks on our material samples. Our evaluation of their samples proved the compatibility issue between the substrate and the conductive ink.

The coefficient of thermal expansion (CTE) for the SI-40 is much higher than the traditional electronic substrate materials. As this is not a problem for use in a normal laboratory environment, using this material in harsh temperature environments would not be acceptable.

- *Evaluate higher-temperature stereolithography materials.* We obtained SI-40, the highest-temperature resin compatible with Sandia's SLA-250 system. We wrote the test patterns on all three selected substrates for comparison.

We collaborated with the University of Texas at El Paso (UTEP) to provide samples built using a higher-temperature resin, Prototool 20L, that claims to be usable at 200°C for extended periods of time. We received the samples from UTEP and are examining their properties. We asked UTEP to glass-load the Prototool 20L resin to see whether we can further enhance its thermal-expansion properties. We will continue to evaluate higher-temperature materials as they become available throughout this project.

- *Determine performance characteristics.* The evaluation of these samples showed that this is a good marriage of technologies. The resistance characteristics are slightly higher than the current standards used in industry, but within a usable range. This will allow us to move toward the combining of electrical and mechanical designs into one process.

- *Determine viability of process.* Through our evaluation of these samples, we determined this to be a viable process for use in a normal operating environment. We are pursuing options that could be used in a harsh, i.e., space, environment.

52528

Elucidating the Mysteries of Wetting

G. S. Grest, A. M. Grillet, D. R. Heine, B. J. Ash, R. K. Giunta, P. A. Sackinger

Nearly every Sandia-owned manufacturing responsibility and many technologies central to Sandia's business involve physical processes controlled by interfacial wetting. Interfacial forces, e.g., conjoining/disjoining pressure, electrostatics, and capillary condensation, are ubiquitous and can surpass and even dominate bulk inertial or viscous effects on a continuum level. Moreover, the statics and dynamics of three-phase contact lines exhibit a wide range of complex behavior, such as contact-angle hysteresis due to surface roughness, surface reaction, or compositional heterogeneities. These thermodynamically and kinetically driven interactions are essential to the development of new materials and processes. Several current critical technologies, for example, microelectromechanical systems (MEMs) packaging, could depend on a more complete understanding of interfacial forces.

Sandia's focus is to obtain an understanding of the factors controlling wettability in multicomponent systems by developing computational modeling tools and applying experimental diagnostics for systems and processes dominated by interfacial effects. Wettability will be probed by dynamic advancing and receding contact-angle measurements, ellipsometry, and direct determination of the capillary and disjoining forces from contact mechanics experiments. We will use molecular-scale experiments to determine the relationships between the fundamental interactions between molecular species and the substrate. We will use atomistic simulations to study the equilibrium concentration profiles near the solid and vapor interfaces and to test the basic assumptions used in the continuum approaches. These simulations will provide guidance in developing constitutive equations, which more accurately take into account the effects of surface-induced phase separation and concentration gradients near the three-phase contact line.

The lack of understanding of surface-wetting phenomena has hampered numerical modeling, as well as the advancement of microsystem engineering materials and processes. The development of accurate models for dynamic multicomponent wetting will allow improvement in science-based engineering of manufacturing processes previously developed through costly trial and error by varying material formulation and geometry modification.

Nearly every Sandia-owned manufacturing responsibility and many technologies central to Sandia's business involve physical processes controlled by interfacial wetting....Sandia's focus is to obtain an understanding of the factors controlling wettability in multicomponent systems by developing computational modeling tools and applying experimental diagnostics for systems and processes dominated by interfacial effects.

The focus of our research is to advance existing theoretical/computational tools and approaches and to develop pertinent experimental diagnostics to analyze systems and processes dominated by capillary-hydrodynamics effects. This involves a three-prong approach, combining atomistic- and continuum-level modeling with experimental studies. We concentrated on developing experimental tools and diagnostics to measure concentration segregation during wetting. In the atomistic simulations, we concentrated on determining the wetting/nonwetting phase diagram for homogeneous polymer fluids as a function of chain length and on comparing the spreading dynamics to existing continuum models.

- *Atomistic simulations.* We carried out extensive molecular dynamics (MD) simulations of interfacial wetting of short-chain polymer fluids on both atomically smooth (flat) substrates and atomic substrates. Our initial studies focused on a coarse-grained bead-spring model consisting of 10–40 beads per chain. For comparison with existing continuum theories, we studied large drops of approximately 200,000 monomers, about 10 times larger than previous simulations. For the first time, we were able to follow not only the precursor foot, which spreads diffusively, but also the spreading of the main drop. By varying the coupling of the polymer to the substrate, we determined the wetting/nonwetting phase boundary and the equilibrium contact angle as a function of substrate coupling in the nonwetting regime. For this model, we separately measured the diffusion constant, viscosity, and liquid/vapor surface tension, which are input parameters for all continuum models of spreading. For these single-component drops, the continuum approaches, which include both kinetic and hydrodynamic interactions, fit the simulations very well. Simulations on two-component fluids to test the basic assumptions used in the continuum approaches are under way.

- *Experiments.* We developed an experimental apparatus based on evanescent-wave (EW) illumination to examine the surface morphology of spreading drops. Using total internal reflection of a laser beam at the interface between a fluorescent drop and the stationary surface, we generated an EW that excites fluorescence in the surface layer of the liquid with a depth of several hundred nanometers. The light emitted by the drop is captured on a charge-coupled-device (CCD) camera, though this system can be modified for use with the confocal microscope. We tested the system using several dye solutions and noted interesting behavior in some of these multicomponent systems. In particular, rhodamine dissolved into glycerine and water forms a stable solution but tends to

Our initial studies focused on a coarse-grained bead-spring model consisting of 10–40 beads per chain. For comparison with existing continuum theories, we studied large drops of approximately 200,000 monomers, about 10 times larger than previous simulations. For the first time, we were able to follow not only the precursor foot, which spreads diffusively, but also the spreading of the main drop.

partition to the air interface. By isolating the fluorescence response of the surface layer using EW illumination, we observed the adsorption pattern of the rhodamine dye on the surface. To probe the dynamics and composition of the entire drop, we will use a recently delivered laser-scanning confocal microscope. By using multiple detection channels, we can simultaneously measure the composition of several fluorescent components.

- *Continuum simulations.* We constructed a model for the spreading of axisymmetric drops of single-component, viscous, incompressible, Newtonian, isothermal fluid with a deformable liquid/vapor interface. To relieve the well-known nonintegrable singularity at the advancing three-phase junction, the model relaxes the usual no-slip boundary condition in the vicinity of the contact line. All of the material properties (bulk and interfacial), the boundary slip model, and the initial size of the drop may be varied. With this “bridging” capability, we can make continuum simulations of drops closely matching the experimental setup, e.g., $R \sim 1$ mm, as well as of very small droplets closely matching the parameters of the MD simulations, e.g., $R \sim 20$ nm. Detailed continuum simulation results for long-time behavior, i.e., steady dynamic wetting, for different constitutive laws and slip models for very small drops are under way; we will use those models that provide the best comparison to MD simulations as the basis for simulations of the relatively large-drop behavior that will be compared to experimental results.

Refereed

Heine, D. R., G. S. Grest, and E. B. Webb, III. 2003. Spreading dynamics of polymer nanodroplets. *Physical Review E*, accepted.

Other Communications

Grest, G. S., D. R. Heine, and E. B. Webb, III. 2003. Spreading dynamics of polymer nanodroplets. Paper presented at the American Physical Society, March, Austin, Texas.

52530

Next-Generation Spindles for Micromilling

D. D. Gill

There are a wide variety of important applications for micro- and mesoscale mechanical systems in the commercial and defense sectors that require high-strength materials and complex geometries, but that cannot be produced using current microelectromechanical systems (MEMS) fabrication technologies. Micromilling has great potential to fill this void in MEMS technology by adding the capability of free-form machining of complex three-dimensional (3-D) shapes from a wide variety and combination of traditional, well-understood engineering alloys, glasses, and ceramics. Inefficiencies in micromilling result from the relationships between a cutting tool's breaking strength, the applied cutting force, and the metal-removal rate.

In examining these relationships, we observe that for a part homogeneously scaled in size by a scaling factor, k , the average machining time scales by $1/k$. If $k = 0.1$, the machining operation will take approximately 10 times as long to complete as the macroscale part. The contributions of cutting-tool edge-radius effects and spindle run-out further exacerbate this. However, cutting forces in milling do not increase with the cutting speed.

Sandia will explore the development of new ultrahigh-speed micromilling spindles. A novel air-bearing spindle design will run at very high speeds (500,000–700,000 revolutions per minute [rpm]) and provide very minimal run-out, allowing the best use of micromilling cutters and reducing overall machining time drastically. Aside from creating an enabling technology for mesofabrication, this project also seeks to build and retain knowledge at Sandia of the micromilling process by examining factors such as tool geometry, tool material, workpiece material, cutting forces, and cutting parameters and their effects on surface finish, metal removal rate (MRR), and feature resolution. We will do the design, fabrication, and testing in collaboration with the University of Florida Machine Tool Research Center (UF-MTRC).

We performed the spindle design jointly with the UF-MTRC. We completed the cutting force, finite-element analysis (FEA) for resonant frequency, air-bearing stiffness, Hertzian-contact stiffness, hoop stress, and radial-strain analyses. Based on the design and analysis, Sandia fabricated parts and acquired

Sandia will explore the development of new ultrahigh-speed micromilling spindles.

...Aside from creating an enabling technology for mesofabrication, this project also seeks to build and retain knowledge at Sandia of the micromilling process by examining factors such as tool geometry, tool material, workpiece material, cutting forces, and cutting parameters and their effects on surface finish, metal removal rate (MRR), and feature resolution.

off-the-shelf components. Initial assembly and integration of the sensors and software took place at UF-MTRC.

We ran the system at speeds up to 500,000 rpm, which is much faster than previously achieved by any cutting system. At this speed, heat due to a rubbing air bearing became a problem. The alleviation of this heat is an objective for upcoming work.

We completed a set of cutting tests at 79,000 rpm using tool diameters from 127 μm to 762 μm and a depth of cut from 42 μm to 127 μm . The slot depths were 1/6 and 1/3 of the tool diameter. We measured the tool forces during cutting, and the signature of individual teeth was clearly evident. The peak force has considerable variation, which is most likely due to asynchronous errors in the tool. We identified several causes and included the fixes in the second prototype to be built in the next round of work. Overall, the spindle was a successful first prototype and highlighted some areas that need higher precision in their manufacture, including the tool shanks, flywheel, and air bearing. Achieving the high speeds was a significant accomplishment.

We made the following accomplishments:

- (1) We ran the spindle at speeds up to 500,000 rpm!
- (2) We completed the initial spindle system, assembled the spindle, integrated the sensors and valves into the computer control system, and successfully operated it under computer control.
- (3) We characterized no-load spindle error motions and performance.
- (4) The spindle performed milling operations using commercially available tooling in aluminum (Al).

The metal-cutting ability of the initial spindle system quantified the milling of Al. We assessed areas for improving the spindle.

...the spindle was a successful first prototype and highlighted some areas that need higher precision in their manufacture, including the tool shanks, flywheel, and air bearing. Achieving the high speeds was a significant accomplishment....We ran the spindle at speeds up to 500,000 rpm!

Other Communications

Ziegert, J., J. Pathak, and B. Jokiel. 2003. An ultrahigh-speed spindle for micromilling. *Proc. ASPE 2003 Annual Meeting* **29** (October, Portland, Oregon).

68552

Investigation of Bioprocesses for Advanced Manufacturing Applications

R. L. Poole

Bioprocessing is an advanced manufacturing technology that involves the use of chemical, physical, and biological processes performed by living cells for use in other applications. Bioprocessing enables the manufacture of products with unique characteristics and has significant potential in the manufacture of several products, such as polymers, energy sources, chemicals, food products, pharmaceuticals, and biodegradation (remediation) of hazardous materials.

Perhaps the most unique and advantageous aspect of bioprocessing is the excellent control afforded during fabrication, including the sequence-by-sequence building of polymeric materials. Specifically, biological species can be used to synthesize polymers of more-uniform chain lengths or chain branching than those produced by conventional synthesis techniques. Additionally, biosynthesis could be used to produce specialty copolymers that are not available through traditional synthesis methods. These bioapplications are of particular interest to Sandia as we strive to understand polymers and nanoparticles in terms of their thermal, mechanical, optical, and electrical properties for use in nuclear weapons, satellites, and homeland defense applications.

Other bio-inspired areas of interest include sensors, encryption tools, and adhesives. It may be possible to utilize this technology to manufacture sensors that offer superior recognition of chemical and biological agents. Currently, it is possible to manufacture sensors that are able to detect only one or a few agents. However, development of the appropriate bioprocessing techniques will enable manufacture of sensors that are able to detect all materials of interest at once. This is of tremendous interest in detecting and neutralizing potential terrorist attacks using these agents. Additionally, it may be possible to use biosequencing to provide encryption and subsequent decoding of complex, sensitive data.

The development and implementation of bioprocesses in manufacturing processes has the potential to provide tremendous productivity and affordability gains to our nation's industrial base, with benefits for both industry and the national labs.

These bioapplications are of particular interest to Sandia as we strive to understand polymers and nanoparticles in terms of their thermal, mechanical, optical, and electrical properties for use in nuclear weapons, satellites, and homeland defense applications. Other bio-inspired areas of interest include sensors, encryption tools, and adhesives.

The National Coalition for Advanced Manufacturing (NACFAM) and Sandia developed a strategy for accelerating the development and implementation of biologically enabled processes in manufacturing. Biomanufacturing is the use of naturally occurring or artificially manipulated biological processes to produce a desired product. It has the potential to dramatically alter the very manner in which materials are made, energy is produced, and life is constructed, disrupting entire industries in the process.

- *Performed a thorough literature search to determine leading researchers/institutions, current research efforts, and general trends in bioprocessing.* Major research efforts in the field of biomanufacturing are currently under way at some of the nation's leading academic institutions (Massachusetts Institute of Technology, Princeton, and Harvard), government institutions (Defense Advanced Research Projects Agency, National Institutes of Health, and National Science Foundation) and industry (Cargill-Dow, Monsanto, Archer Daniels Midland [ADM], and DuPont).

- *Coordinated with experts in bioprocessing and Sandia researchers to get their input on results from the previous step, and conducted interviews with top researchers in bioprocessing to determine relevant research areas, technical issues, and potential opportunities in bioprocessing.* We reviewed ongoing research efforts at some of the top government, private, and academic institutions for biomanufacturing technologies relevant to the mission of the national laboratories. These technologies include:

- *Self-assembling electronic devices.* These are connections made by enzyme-like molecules that form bonds or activate functional groups.

- *Biomimetic lyotropic systems.* These are thermodynamically stable nanostructures that allow for the creation of templates for synthesis of nanoporous materials and nanocomposites.

- *Polymer biosynthesis.* Block copolymer architecture allows for the formation of liquid crystalline regions in high-temperature thermoplastics.

- *Polymer biosynthesis.* These thin-film applications offer ease and versatility of film and fiber processing.

- *Biosensing.* Coupling of biosensing technologies and microelectromechanical systems (MEMS) increases the sensitivity of biosensors, enabling equipment to detect lower and lower levels of chemicals and biological warfare agents.

- *Conducted interviews with potential commercial developers and end-users to determine which new technologies,*

The National Coalition for Advanced Manufacturing (NACFAM) and Sandia developed a strategy for accelerating the development and implementation of biologically enabled processes in manufacturing. Biomanufacturing is the use of naturally occurring or artificially manipulated biological processes to produce a desired product. It has the potential to dramatically alter the very manner in which materials are made, energy is produced, and life is constructed, disrupting entire industries in the process.

products, or services have the most significant applications, who are potential research partners (e.g., Sandia), and what factors are hindering or enabling the commercialization and deployment of these technologies. Several potential commercial developers and their technologies of interest were reviewed and are listed below:

- Large agribusiness concerns such as Cargill-Dow (a life-sciences partnership), Monsanto, and ADM are working on novel ways to conserve, recycle, and convert agricultural biomass into biodegradable plastics.

- Nano-/medical device manufacturers such as NanoSphere are developing cell identification/recognition systems capable of rapidly detecting a range of pathogens at the point of delivery (handheld labs).

- DuPont is working on technology to grow monomers and polymers with unique physical properties (a potential revolution in plastics and related materials).

Long-term potential applications of these related technologies include the following innovations:

- Computing will be biologically based, harnessing the data-storage and computational capabilities of deoxyribonucleic acid (DNA).

- Materials of various kinds will “biologically” self-assemble using biologic robots.

- Waste in some manufacturing processes will be virtually eliminated as the glucose recovered from agricultural waste is used as feedstock fuel for biomanufacturing processes.

- Advances in computational power and software will enable simulations to run from “lab to shelf.” This will enable advanced manufacturing in which “manufacturability” of a material will quickly follow its scientific discovery.

- The very process of traditional manufacturing (in some sectors) will be made obsolete by advanced biomanufacturing processes as materials, parts, and even components are grown and biologically assembled rather than mined, melted, bent, stamped, drilled, and manually assembled.

- *Sandia technical report/internal memo preparation and outreach.* This initial investigation has paved the way to research bioprocessing technologies as they relate to national security needs.

The very process of traditional manufacturing (in some sectors) will be made obsolete by advanced biomanufacturing processes as materials, parts, and even components are grown and biologically assembled rather than mined, melted, bent, stamped, drilled, and manually assembled....This initial investigation has paved the way to research bioprocessing technologies as they relate to national security needs.

Other Communications

Grambsch, P., J. A. Ruffner, and J. A. Emerson. 2003. Research Trends and Opportunities in Biomanufacturing Technologies. Sandia Technical Report, Sandia National Laboratories, Albuquerque, New Mexico, in review.

Grambsch, P., J. A. Ruffner, and J. A. Emerson. 2003. The State of Biomanufacturing Research and Application in the United States. Internal memorandum, Sandia National Laboratories, Albuquerque, New Mexico.

Biotechnology

The Biotechnology investment area enables Sandia research efforts that develop targeted biotechnology capabilities in support of national security missions. Biotechnology will integrate Sandia's core capabilities in advanced measurement, imaging science, nanotechnology, microsystems, protein science, and computational science, and will augment them with new biotechnical capabilities at the cellular/molecular levels. These core capabilities also will provide a unique platform from which Sandia can make significant contributions to the biomedical needs required by our mission responsibilities. The focus is on tools and capabilities to build informational and physically based systems models for toxin, pathogen, and signaling molecule interactions with cell membranes.

Accurate and complete biothreat assessment requires a deeper understanding of intricate cellular mechanisms. Better instruments, informatics, and knowledge-management methods are essential tools in this research. The needs are especially critical when working with the new high-throughput technologies, including gene and protein expression arrays. *High-Throughput Instruments, Methods, and Informatics for Systems Biology* will research both instrumentation and algorithms that directly address improved data collection and new analysis

techniques suitable for dealing with such large datasets. The new scanner and collaborative analysis tools developed in the project will facilitate investigation of the development of new biologically based biosensors for bioagents, protein detection, and for understanding the genetic basis of cancer and its treatment. Two patent disclosures and one patent application have been filed as a result of this investigation.

26581

Molecular-Scale Studies of Single-Channel Membrane Pores

A. R. Burns, B. S. Swartzentruber, J. G. Fleming, K. O. Evans

Translocation of large biomolecules (e.g., proteins, deoxyribonucleic acid [DNA]) through single-ion-channel protein pores in membranes is an emerging biotechnology that promises new rapid detection and sequencing approaches. However, it currently is not possible to fully interpret the modulated ionic current signals because too little is known about the molecular-level details of translocation. Sandia attempted to study the molecular-level structure, energetics, and kinetics of biomolecule interactions with membrane pores. Most of our effort, however, focused on the fabrication and characterization of solid-state nanopores, created with silicon (Si) micromachining techniques. These pores offer potential advantages of robustness, tailorable pore diameters, functionalized surface chemistry, and built-in detection electronics.

We demonstrated that we can readily detect a single nanopore forming in a leak-free bilayer system. We also demonstrated that we can characterize single strands of DNA and observe subtle differences in base pairs. In particular, we showed that 100-mer strands of poly-dA (adenine) exhibited three distinct populations of blockages that were somewhat different from the blockages exhibited by 100-mer strands of poly-dC (cytosine). We showed that we could also alter the blockage pattern of poly-dC by the attachment of a 25-mer poly-dT (thymine), a more distinctive pore-blocking DNA sequence. We also demonstrated that tetanus toxin forms pores in bilayer systems at pH 7.4, but not at pH 4. Thus, we verified a pH-dependent mechanism for toxin pore formation. We demonstrated our ability to fabricate leak-free solid-state nanopores with the same current sensitivity as the protein pores. However, we were stymied by the lack of observable current blockages induced by DNA translocation. We made a considerable effort to determine the root cause of this problem. Pore sizes were increased by hydrofluoric (HF) etching. We performed elaborate cleaning procedures. Finally, extensive transmission-electron microscopy revealed no clues as to why we detected reason currents, but saw no translocation blockages.

Most of our effort, however, focused on the fabrication and characterization of solid-state nanopores, created with silicon (Si) micromachining techniques. These pores offer potential advantages of robustness, tailorable pore diameters, functionalized surface chemistry, and built-in detection electronics.

Refereed

Evans, K. O., J. G. Fleming, B. S. Swartzentruber, and A. R. Burns. 2003. Single-ion-channel sensitivity with solid-state nanopores. *Biophysical J., Proc. Biophysical Society Annual Meeting* **84** (1–5 March, San Antonio, Texas): 559A.

26582

Efficient Massively Parallel Techniques for Protein Structure Generation

M. D. Rintoul, M. P. Sears, S. J. Plimpton

The primary goal of Sandia's recent work on this project was to implement the parallel-tempering Monte Carlo algorithm into a production code and to apply this code to a protein test problem to show its effectiveness. We successfully introduced the parallel-tempering algorithm to the large-scale atomistic/molecular massively parallel simulator (LAMMPS), one of the most heavily used codes at Sandia. Our acceptance of the parallel-tempering algorithm into the main code represented a major accomplishment in terms of stability and application. By incorporating the algorithm into LAMMPS, we gained not only the advantages of the high-quality existing code, but also a nice generality such that the individual "boxes" associated with the parallel-tempering simulations can be parallelized themselves. The primary application was on a five-residue peptide chain (met-enkephalin) in a water solvent. This system represented both a simple example that had published results and a truncated example of the type of system that we would like to simulate. We verified the quality of the simulation by comparison to standard molecular dynamics (MD) techniques.

Our primary goal was to ensure not only that parallel tempering was implemented, but also that it was implemented in a rigorous manner such that it would be a key technology accessible to the entire lab for application to different problems. We thus decided to implement the parallel-tempering algorithm

Our acceptance of the parallel-tempering algorithm into the main code represented a major accomplishment in terms of stability and application. By incorporating the algorithm into LAMMPS, we gained not only the advantages of the high-quality existing code, but also a nice generality such that the individual "boxes" associated with the parallel-tempering simulations can be parallelized themselves.

Model of the met-enkephalin peptide that was used in the validating study.

in LAMMPS. LAMMPS is one of the most widely used codes at Sandia and is currently the primary-cycle consumer on CPlant (Computational Plant).

There are two primary reasons why we chose LAMMPS as a vehicle for this algorithm. First, since LAMMPS has such a broad user base, implementing the algorithm in LAMMPS would give the algorithm much more exposure than writing it into a whole new code. Second, the simulation infrastructure already present in LAMMPS allowed us to concentrate on the parallel-tempering algorithm itself, and not on all of the other details associated with the molecular simulation. The ultimate result was beyond our expectations. The primary author of LAMMPS, who was also working on the issue of parallel tempering from other sources, accepted the parallel-tempering code into the main version of LAMMPS, and it appeared in the most recent official distribution.

With the implementation goal accomplished, we set out to apply this to an actual problem. Our test problem was the study of a small (five-residue) peptide chain, met-enkephalin solvated by water. This was an all-atom simulation, with the hydrogen atoms being partially simulated using the SHAKE algorithm. Although this problem was smaller than the proteins (and other large molecular systems) on which we will be applying the parallel-tempering algorithm, this proof-of-principle simulation will scale easily to larger systems. We primarily used a smaller system with a smaller number of processors so that we could run the simulation without requiring all of a large parallel machine. The results essentially indicated that our implementation was successful, with many of the results being similar to much-longer-running traditional MD simulations. A few issues remain in comparing the bond-angle space being explored by both methods, but we expect those issues to be resolved by further analysis.

The ultimate result was beyond our expectations. The primary author of LAMMPS, who was also working on the issue of parallel tempering from other sources, accepted the parallel-tempering code into the main version of LAMMPS, and it appeared in the most recent official distribution.

Other Communications

Plimpton, S. J., *et. al.* 2003. LAMMPS 2003.

www.cs.sandia.gov/~sjplimp/lammps.html.

26583

Mapping Membrane Protein Interactions in Cell Signaling Systems

M. M. Young, J. S. Schoeniger, J. M. Faulon, A. K. Singh, R. B. Jacobsen, J. Hong, G. H. Kruppa, C. B. Troup

Sandia proposed to apply the technique called MS3D (tandem MS/MS [mass spectroscopy/mass spectrometry] method) to the structure determination of the rhodopsin-transducin membrane protein complex (RTC). We made experimental progress in adapting the MS3D approach for characterizing membrane protein systems, and computational progress in the areas of experimental design, data analysis, and protein-structure modeling. We developed expression systems for mouse and human rhodopsin, alpha-, beta-, and gamma-transducins to increase our in-house stock of purified transducin. We also implemented experimental methods to probe the formation and product types generated by cross-linking the rod outer-segment membrane (ROS) with cys-cys (bis-maleimido-hexane, BMH), cys-lys (N-[ε-maleimidocaproyloxy] succinimide ester, EMCS), and lys-lys (disuccinimidyl suberate, DSS) cross-linkers. To date, we have carried out a set of experiments that investigated the effect of cross-linker concentration on the amounts and types of RTC cross-linking products formed. Gel electrophoresis and Western blots of the intact cross-linked ROS and guanosine triphosphate (GTP)-eluted fractions showed that alpha-transducin is cross-linked to rhodopsin by all three cross-linking reagents. In support of the experimental effort, we released new and greatly improved data-analysis packages called LINKS and MS2LINKS that are fully integrated into our automated peak selection and reduction software. We are also preparing a publication on BUNDLER, a Monte Carlo-simulated annealing package for the determination of transmembrane helical-domain structures by satisfying a set of theoretical and experimental constraints.

- *Experimental progress*

— *RTC expression.* Obtaining quantities of transducin sufficient for cross-linking studies from bovine retinal tissue proved to be extremely laborious and time-consuming. We therefore shifted focus to constructing expression systems for both rhodopsin and transducin. As a first step, we obtained the complementary deoxyribonucleic acids (cDNAs) for the mouse and human genes encoding rhodopsin, alpha-, beta-, and gamma-transducins. We confirmed entry vectors made from the cDNAs by sequencing and converted these entry vectors into

Sandia proposed to apply the technique called MS3D...to the structure determination of the rhodopsin-transducin membrane protein complex (RTC). We made experimental progress in adapting the MS3D approach for characterizing membrane protein systems, and computational progress in the areas of experimental design, data analysis, and protein-structure modeling.

expression vectors containing N-terminally histidine (HIS)–tagged rhodopsin and glutathione S-transferase (GST)–tagged transducin for expression in *E. coli* and baculovirus. We characterized the mouse and human set in *in vitro* extracts and found cross-reacting bands at the correct molecular weights based on HIS- and GST-specific Western blots.

We also created a baculovirus system for rhodopsin expression in SF9 and sf21 cells. We amplified and titered the virus, determined the multiplicity of infection (MOI), and performed a small-scale expression run. The yield of rhodopsin was > 1 µg/L. We are optimizing this yield.

We co-expressed alpha-transducin with the N-myristoyl transferase genes NMT1 and NMT2 for post-translational processing (addition of a myristoyl group) of the N-terminus. We detected the expression of unprocessed and processed alpha-transducin by Western blots and are working out optimum expression conditions prior to scale-up.

— *RTC cross-linking*. We treated purified ROS/transducin complex with BMH, N-EMCS, and DSS cross-linkers. Gel electrophoresis showed that as the concentration of cross-linker:protein increased, higher-molecular-weight bands appeared on the gel. These bands most likely correspond to the formation of cross-linked protein complexes.

To probe these higher-molecular-weight species, we did a Western blot with antialpha transducin antibody. We did not observe any higher-molecular-weight species in the transducin control, but these species did appear as transducin-containing bands for each of the three cross-linking reactions.

— *GTP-eluted cross-linked RTC*. Once we confirmed that we could observe cross-linked RTC formation, we probed the proteins that were principally involved in the cross-linking reactions. Cross-linking with BMH, DSS, and EMCS followed by a GTP wash showed that no higher-molecular-mass species were observed on the Western blot, indicating that alpha-transducin cross-links principally with rhodopsin and not with the beta and gamma subunits.

To reduce production of higher-order cross-linking products, we repeated the cross-linking experiments but at lower cross-linker concentrations. We observed a distinct ladder of higher-molecular-weight species, indicating that reduction of the cross-linker concentration lowered the amount of nonspecific protein-protein cross-linking.

For completeness, we investigated the effect of lowered cross-linker concentrations on the products eluted with GTP from the ROS. As before, we observed no higher-molecular-weight species in the GTP elution fractions at lower cross-linker

To reduce production of higher-order cross-linking products, we repeated the cross-linking experiments but at lower cross-linker concentrations. We observed a distinct ladder of higher-molecular-weight species, indicating that reduction of the cross-linker concentration lowered the amount of nonspecific protein-protein cross-linking.

concentrations, indicating that the alpha-transducin subunit does not form cross-linked complexes with either the beta or gamma subunit. The higher-order species we observe in the samples derived directly from ROS must therefore contain alpha-transducin/rhodopsin at the minimum (as shown by Western blotting) and possibly rhodopsin/rhodopsin cross-linked species.

We are in the process of cutting these species out of the gel and characterizing them using proteolysis and MS.

- *Computational progress*

- *Data analysis.* We developed and integrated two next-generation MS data-analysis programs, LINKS and MS2LINKS, into our automated interpretation suite. LINKS and MS2LINKS can handle multiple protein, DNA, and/or ribonucleic acid (RNA) sequences simultaneously with custom sequence-specific cleavages, modifications, and cross-linking reagents. LINKS assigns data from “bottom-up” MS3D experiments, and MS2LINKS assigns “top-down” data.

- *Modeling.* BUNDLER correctly predicts the structures of six membrane proteins of known structure using sets of theoretically derived cross-linking constraints. We showed that using a set of 27 distance constraints extracted from the literature, BUNDLER recovered the structure of rhodopsin to within 3.2 Å of the crystal structure.

Refereed

Faulon, J. L., K. L. Sale, and M. M. Young. 2003. Exploring the conformational space of membrane protein folds matching distance constraints. *Protein Science* **12**:1750–61.

Other Communications

Gray, G. A., T. G. Kolda, K. L. Sale, and M. M. Young. 2003. Optimizing an empirical scoring function for transmembrane protein structure determination. *INFORMS*, submitted.

Sale, K. L., J. L. Faulon, G. A. Gray, J. S. Schoeniger, and M. M. Young. 2003. Optimal bundling of the transmembrane helices of integral membrane proteins using sparse distance constraints. *Protein Science*, to be submitted.

We developed and integrated two next-generation MS data-analysis programs, LINKS and MS2LINKS, into our automated interpretation suite.

32574

High-Throughput Instruments, Methods, and Informatics for Systems Biology

D. M. Haaland, S. B. Martin, G. S. Davidson, E. V. Thomas, K. W. Boyack, M. B. Sinclair, B. N. Wylie, J. A. Timlin

High-throughput instruments and analysis techniques are required to make good use of the genomic sequences that have recently become available for many species, including humans. These instruments and methods must work with tens of thousands of genes at once and be able to identify the small subset of those genes that are implicated in observed phenotypes or, for instance, in response to therapies. Microarrays represent one such high-throughput method that continues to find increasingly broad application. This project improved microarray technology in several important areas. First, Sandia developed a hyperspectral scanner that discovered and diagnosed numerous flaws in techniques broadly employed by microarray researchers. Second, we used a series of statistically designed experiments to identify and correct errors in our microarray data to dramatically improve the accuracy, precision, and repeatability of the microarray gene expression data. Third, our research developed new informatics techniques to identify genes with significant differential expression. Finally, our research and development team then applied natural language processing techniques to the online literature annotating these genes. In combination, this research improved the reliability and precision of laboratory measurements and enabled substantially faster analysis and discovery of the biological meaning from the experiments.

(1) We have the required parts and expect to finish incorporating the red laser into our scanner.

(2) The instrument captures such large datasets that we had to develop new compression technologies before completing this goal. The MATLAB code was developed to stitch together the multiple scans obtained with the hyperspectral scanner for each microarray slide.

(3) We improved the overall performance of the algorithms through the combination of principal component spectral and wavelet spatial compression technologies to provide nearly 200,000-fold compression with no loss of total information. The new compression algorithms, coupled with the implementation of rigorous equality constraints in the multivariate curve resolution (MCR) quantitative spectral

Mike Sinclair operates the new Sandia-developed hyperspectral microarray scanner for genomic investigations.

...this research improved the reliability and precision of laboratory measurements and enabled substantially faster analysis and discovery of the biological meaning from the experiments.

image analysis algorithms, resulted in excellent quantitative analyses of the hyperspectral image (HSI) data.

(4) We directly investigated in detail how microarray data are processed from initial expression files, through the statistical identification of important genes, and finally through the labor- and knowledge-intensive work of reading through the relevant literature. Importantly, we now have a written protocol for this process.

(5) We completed a statistical analysis of the error structure in one common microarray technology. This tool will be useful for improving the overall process, but is particularly useful for testing the accuracy and precision of gene-finding algorithms.

(6) The weighted MCR analysis method is working and improving the quantitation of the microarray data generated by the hyperspectral scanner.

(7) We used our algorithms to detect specific patterns of gene expression, notably those that would be otherwise missed in the noisy measurements. These resulted in at least three patent applications held jointly with the University of New Mexico.

(8) We continued the development and use of the Gene Literature Exploration Environment developed with New Mexico State University.

(9) We worked with the Sandia Technology Transfer group and signed at least six nondisclosure agreements to discuss the transfer of this technology.

We used our algorithms to detect specific patterns of gene expression, notably those that would be otherwise missed in the noisy measurements. These resulted in at least three patent applications held jointly with the University of New Mexico.

Refereed

Borner, K., C. Chen, and D. W. Boyack. 2003. Visualizing knowledge domains. *Annual Review of Information Science and Technology* **37**:179–255.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Multivariate curve resolution for hyperspectral image analysis: Applications to microarray technology. *Proc. BiOS 2003*, San Jose, California.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Multivariate curve resolution for hyperspectral image analysis: Applications to microarray technology. *Proc. SPIE, Photonics West 2003* (San Jose, California).

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Multivariate curve resolution for hyperspectral image analysis: Applications to microarray technology. *Proc. SPIE, Spectral Imaging: Instrumentation, Applications, and Analysis II* **4959**:55–66.

Martinez, M. J., A. D. Aragon, A. Rodriguez, J. Weber, J. A. Timlin, M. B. Sinclair, D. M. Haaland, and M. M. Werner-Washburne. 2003. Identification and removal of contaminating fluorescence from commercial and in-house printed DNA microarrays. *Nucleic Acids Research* **31**:e18.

Mosquera-Caro, M., *et al.* 2003. Expression profiling for molecular classification and outcome prediction in infant leukemia reveals novel biologic clusters, etiologies and pathways for treatment failure. *Blood* **100** (11): 524.

Mosquera-Caro, M., *et al.* 2003. Gene expression profiling of pediatric acute lymphoblastic leukemia reveals unique genes that define patient outcome. Paper presented at Oncogenomics 2003, Phoenix, Arizona.

Mosquera-Caro, M., *et al.* 2003. Gene literature exploration environment: From gene lists to pathways of cancer cure. Paper presented at Oncogenomics 2003, Phoenix, Arizona.

Mosquera-Caro, M., *et al.* 2003. Heterogeneity of gene expression profiles in MLL-associated infant leukemia: Identification of distinct expression profiles and novel therapeutic targets for each MLL translocation variant. *Blood* **100** (11): 2943.

Mosquera-Caro, M., *et al.* 2003. Identification, validation, and cloning of a novel gene (OPAL1) and associated genes highly predictive of outcome in pediatric acute lymphoblastic leukemia using gene expression profiling. *Blood*, special issue for American Society of Hematology 2003, accepted.

Mosquera-Caro, M., *et al.* 2003. Multidisciplinary approach to microarray analysis. Paper presented at Microarray Gene Expression Data Society IV, September, Aix-en-Provence, France.

Mosquera-Caro, M., *et al.* 2003. Quality control of leukemia microarray data. Paper presented at Microarray Gene Expression Data Society IV, September, Aix-en-Provence, France.

Sinclair, M. B., J. A. Timlin, D. M. Haaland, and M. Werner-Washburne. 2003. Hyperspectral microarray scanner. *Applied Optics: Optical Technology and Biomedical Optics* (Optical Society of America: Washington, D.C.), submitted. SAND2003-2452J.

Viswanatha, D., *et al.* 2003. Gene expression profiling of pediatric acute lymphoblastic leukemia reveals unique subgroups independent of current genetic risk stratification. *Blood* **100** (11): 2978.

Werner-Washburne, M. M., B. N. Wylie, E. Fuge, J. Galbraith, M. M. Fleharty, J. Weber, and G. S. Davidson. 2002. Concurrent analysis of multiple genome-scale datasets. *Genome Research* **12**:1564–73.

Other Communications

Davidson, G. S. 2003. Analyzing microarray data: An opportunity for fruitful collaborations between clinicians, biologists, cognitive psychologists, computer scientists, statisticians, and computational linguists. (Invited) Talk presented at Computer Science Seminar, University of Malta, Msida, Malta.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, E. V. Thomas, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Improving microarray analysis with hyperspectral microarray scanning, experimental design, and multivariate data analysis. (Invited) Paper presented at the United States Army Research Institute for Infectious Diseases (USAMRIID), Fort Detrick, Maryland.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Improving microarray analysis and discovering sources of artifacts with a new hyperspectral microarray scanner. (Invited) Paper presented at Scripts Institute, La Jolla, California.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Improving microarray analysis and discovering sources of artifacts with a new hyperspectral microarray scanner. (Invited) Talk presented at the National Institutes of Health, Washington, D.C.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, and M. M. Werner-Washburne. 2003. Improving microarray analysis and discovering sources of artifacts with a new hyperspectral microarray scanner. (Invited) Paper presented at the Topics in Biological Physics Seminar Series, Department of Physics and Astronomy, University of New Mexico, Albuquerque, New Mexico.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. H. Van Benthem, M. J. Martinez, A. D. Aragon, A. Rodriguez, J. Weber, and M. M. Werner-Washburne. 2002. Hyperspectral fluorescence image scanning of microarrays for improved genome expression analyses. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 13–17 October, Providence, Rhode Island.

Haaland, D. M., J. A. Timlin, M. B. Sinclair, M. R. Keenan, M. H. Van Benthem, M. J. Martinez, and M. M. Werner-Washburne. 2003. Multivariate curve resolution for analysis of hyperspectral images. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 19–23 October, Ft. Lauderdale, Florida.

Haaland, D. M., J. A. Timlin, M. R. Keenan, M. H. Van Benthem, M. B. Sinclair, M. J. Martinez, and M. M. Werner-Washburne. 2003. Methods to improve the efficiency of the quantitative analysis of hyperspectral image data. Paper presented at the Pittsburgh Conference, 9–14 March, Orlando, Florida.

Haaland, D. M., M. R. Keenan, M. H. Van Benthem, J. A. Timlin, M. B. Sinclair, P. G. Kotula, and F. W. Koehler. 2003. Multivariate curve resolution applied to hyperspectral images. Paper presented at the Gordon Research Conference on Statistics in Chemistry and Chemical Engineering, 27 July–1 August, South Hadley, Massachusetts.

Mosquera-Caro, M., J. Potter, E. Andries, S. Martin, P. Hellman, R. Veroff, H. Kang, X. Wang, B. Camitta, J. Shuster, A. Carroll, M. Murphy, F. Schultz, C. Wilson, G. Dahl, R. Arceci, D. M. Haaland, G. S. Davidson, S. Atlas, and C. Willman. 2003. Gene expression profiling for molecular classification and outcome prediction in infant leukemia reveals novel biologic clusters, etiologies, and pathways for treatment failure. Paper presented at the 44th American Society of Hematology Annual Meeting, 6–10 December, Philadelphia, Pennsylvania.

Timlin, J. A., D. M. Haaland, M. B. Sinclair, and A. Martino. 2003. Carbon sequestration in synechococcus: Microarray approaches. Paper presented at the 2003 Genomes to Life Program Workshop, 10–12 February, Arlington, Virginia.

Timlin, J. A., M. B. Sinclair, and D. M. Haaland. 2003. Improving gene expression data with hyperspectral imaging. Paper presented at the Pittsburgh Conference, 9–14 March, Orlando, Florida.

Timlin, J. A., M. B. Sinclair, D. M. Haaland, J. Martinez, and M. M. Werner-Washburne. 2002. Hyperspectral imaging and multivariate analysis of gene expression data. Paper presented at the 14th International Genome Sequencing and Analysis Conference, 2–5 October, Boston, Massachusetts.

Timlin, J. A., M. B. Sinclair, D. M. Haaland, M. H. Van Benthem, J. Martinez, and M. M. Werner-Washburne. 2002. Hyperspectral imaging and multivariate analysis of gene expression data. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 13–17 October, Providence, Rhode Island.

Willman, C. L., M. Mosquera-Caro, S. Martin, E. Andries, J. Potter, P. Hellman, R. Veroff, H. Kang, X. Wang, B. Camitta, J. Shuster, A. Carroll, W. Carroll, G. Dahl, R. Arceci, C. Wilson, D. M. Haaland, G. S. Davidson, and S. Atlas. 2002. Analysis of gene expression profiling of acute leukemia in children: Novel biologic clusters, etiologies, and pathways for treatment failure. Paper presented at the National Institute of Cancer Director's Challenge P. I. Meeting, 6–8 November, Washington, D.C.

32914

Biomimetic Chloroplasts: An Integrated Microdevice Power Source

J. A. Shelnutt, C. J. Medforth, C. J. Brinker, Y. Yang

Self-assembled, self-organized materials can provide mesoscale power sources for integrated microelectronic and microelectromechanical systems (MEMS) applications. For example, a self-assembled biomimetic chloroplast would use light energy to produce a gas or liquid for use as a fuel or chemical feed. Specifically, a simple fuel such as hydrogen (H) could be generated and stored on-chip to provide electrical power via an integrated fuel-cell component. The chloroplast is the biological structure (organelle) that collects and converts light energy to storable fuel for a living cell. Sandia has used chlorophyll-like porphyrin molecules to harvest photons and direct the light energy to a biomimetic reaction center for the photosynthesis of high-energy fuel molecules. Light energy is collected by the porphyrin molecules and converted within the biomimetic chloroplast into a storable high-free-energy chemical, which can be used as an energy source in the dark and then replenished when the chip is again under illumination. This photosynthesized fuel or feedstock could be supplied as needed to a catalytic microreactor on demand. We developed the necessary photochemistry and associated catalysts (the biomimetic reaction center) required for producing H and also the self-assembling components of a light-energy-collecting apparatus (the biomimetic light-harvesting complex) required for a small, efficient, integrated power source. Self-assembled antimony (Sb) or tin (Sn) porphyrins form the integrated light-harvesting complex and reaction center; these have been self-organized and compartmentalized into porous silica nanocomposites and into surfactant nanoassemblies, along with H-evolving platinum (Pt) catalyst, which mimics the enzyme hydrogenase. The supporting nanostructured silica or platinized liposomal environments permit access by small electron donors, acceptors, and water through small pores, while maintaining microscale compartmentalization and organization of the larger surfactant assemblies and mesostructured silicates.

We developed the necessary photochemistry and associated catalysts (the biomimetic reaction center) required for producing H and also the self-assembling components of a light-energy-collecting apparatus (the biomimetic light-harvesting complex) required for a small, efficient, integrated power source.

We made the following accomplishments:

(1) *Self-assembly of biomimetic chloroplasts:* incorporation of Sn porphyrins into the pores of silica films and selective removal of the detergent molecules, the formation of Pt nanoparticles within the pores of silica films using light, and the

growth of shells of Pt nanocrystals on the surface of sodium dodecylsulfate micelles or distearoyl phosphatidylcholine (DSPC)/cholesterol liposomes containing the Sn porphyrin.

(2) *Demonstration of functionality*: direct electron transfer from the Sn porphyrin to the hydrogenase (Pt catalyst) under illumination by visible light in aqueous solution, and Sn-porphyrin photomediated H generation by the Pt/surfactant nanostructures.

(3) *Construction of more-advanced compartmentalized systems*: selection of porphyrins for construction of light-harvesting arrays and assembly of rudimentary light-harvesting arrays.

The most significant new accomplishment was the discovery of the platinized surfactant nanoassemblies, i.e., micelles, liposomes, and vesicles containing the photocatalytic Sn porphyrin that have been coated with three-dimensional (3-D) Pt metal dendrites or 2 nm-thick Pt dendritic sheets. The Pt nanodendrites on the surface of these surfactant assemblies are joined to make the metal shell resistant to mechanical stresses while retaining the necessary porosity. Moreover, we demonstrated that these platinized nanoassemblies efficiently photosynthesize H evolution from water by using the photocatalytic porphyrin to supply strongly reducing electrons to the Pt metal shell, which then catalyzes the reduction of water to H. These amazing Pt nanodendrite/surfactant nanoassemblies offer new and enhanced properties beyond those anticipated for the nanocomposites that we originally envisioned. In particular, the platinized surfactant assemblies are capable of generating H and thus a proton gradient across the lipid membrane. This opens the door to the possibility of building a truly functional biomimetic chloroplast that is capable of photosynthesizing adenosine triphosphate (ATP), the biological fuel produced by natural chloroplasts. Because of this success, the goal of providing the compartmentalization of function and using this hierarchical organization to mimic the biological production of proton gradients across a membrane is now achievable.

We were unable to complete the additional tasks required to prepare a truly functional compartmentalized biomimetic chloroplast because of a delay in incorporating a true light-harvesting array capable of energy transfer to the Sn-porphyrin/Pt reaction centers. However, we were able to incorporate high concentrations of the light-harvesting and photocatalytic porphyrin into liposomal bilayers. The high-porphyrin loading was necessary to improve the light-harvesting array, which was to be combined with the reaction center to form the functional

The most significant new accomplishment was the discovery of the platinized surfactant nanoassemblies, i.e., micelles, liposomes, and vesicles containing the photocatalytic Sn porphyrin that have been coated with three-dimensional (3-D) Pt metal dendrites or 2 nm-thick Pt dendritic sheets.

chloroplast photosystem mimic. These studies show that it is feasible to use porphyrin-containing platinized liposomes as biomimetic chloroplasts to produce H₂. They also show that it may be possible to incorporate ATPase into the membrane to synthesize ATP via the proton gradient across the membrane generated during H₂ evolution. If these final tasks were successful, we would truly realize a biomimetic chloroplast with a viable integrated light-harvesting/reaction-center component that produces ATP in addition to molecular H₂.

Refereed

- Haddad, R., S. L. Jia, J. Zhang, K. M. Smith, S. Gazeau, J. Pécaut, J. C. Marchon, C. J. Medforth, and J. A. Shelnutt. 2003. Mechanism and design of molecular devices based on nickel porphyrins. *Book of Abstracts, Proc. National Meeting of the American Chemical Society* **1** (September, New York, New York): INOR 11.
- Shelnutt, J. A., R. Haddad, and C. J. Medforth. 2003. Nonplanar deformations cause the red shifts in the UV-visible bands of ruffled tetraalkylporphyrins. *Book of Abstracts, Proc. Spring Meeting of the American Chemical Society* **1** (March, New Orleans, Louisiana): GEOC 65.
- Song, Y., A. K. Singh, Z. Wang, Y. Qiu, and J. A. Shelnutt. 2003. Photocatalytically nanoengineered foamlike platinum materials templated on liposomes. *Angew. Chem., Int. Ed. Engl.*, in preparation.
- Song, Y., S. R. Challa, R. E. Haddad, Y. Qiu, C. J. Medforth, R. K. Watt, F. van Swol, and J. A. Shelnutt. 2003. Synthesis and molecular simulation of the formation of di-amino acid nanotubes and Pt-nanoparticle-nanotube composites. *Chem. Commun.*, in preparation.
- Song, Y., X. Lu, Y. Yang, C. J. Medforth, F. van Swol, and J. A. Shelnutt. 2003. Synthesis and control of globular platinum-particle nanoassemblies. *Materials Research Society Abstracts* **1** (April, San Francisco, California): 324.
- Song, Y., Y. Yang, C. J. Medforth, E. Pereira, A. K. Singh, H. Xu, Y. Jiang, C. J. Brinker, F. van Swol, and J. A. Shelnutt. 2003. Controlled synthesis of 2-D and 3-D dendritic platinum nanostructures. *J. American Chemical Society*, submitted.
- Song, Y., Y. Yang, C. J. Medforth, E. Pereira, A. K. Singh, H. Xu, Y. Jiang, C. J. Brinker, F. van Swol, and J. A. Shelnutt. 2003. Controlled synthesis of 2-D and 3-D platinum dendrites using porphyrin photocatalysts. *Book of Abstracts, Proc. American Chemical Society Annual Meeting* **1** (6–11 September, New York, New York): INOR 96.
- Yang, Y., E. Pereira, Y. Song, C. J. Medforth, F. van Swol, C. J. Brinker, and J. A. Shelnutt. 2003. Controlled photocatalytic growth of platinized-micelle nanostructures. *Materials Research Society Abstracts* **1** (April, San Francisco, California): 353.

38609

Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors

S. M. Brozik, G. D. Bachand, L. J. D. Frink, P. Esherrick, R. C. Hughes, J. H. Flemming, E. L. Patrick

Sandia presents a concept for the integration of natural ion channels with electronically and optically addressable fluidic platforms to enable rapid, real-time measurements of single-molecule behavior. Transmembrane proteins (TMPs) mediate many membrane functions, including the regulation of cellular potential, selective filtration, and the regulation of nutrient and waste movement. TMPs span the lipid bilayer, requiring hydrophobic regions that penetrate the membrane and hydrophilic regions that are exposed to the aqueous medium on either side. An important class of TMPs forms channels that enable active, directional, and preferential transport of ions across the otherwise impermeable membrane in response to a specific stimulus. A good example is the serotonin type-three receptor that preferentially transports monovalent cations upon binding of serotonin to specific sites on the extracellular domain of the pentameric protein. This binding event causes the movement of 10^6 ions per second through the channel, generating an ion conductance of about 100 pS compared to the leakage conductance of about 0.02 pS. With an amplification factor exceeding 10^6 and a signal-to-noise ratio (SNR) exceeding 5000, gated ion channels integrated into a sensor would have the unprecedented ability to detect single binding events. In addition, spectroscopic measurements allow us to measure fast kinetic events and the dynamics of TMPs.

We are developing molecular modeling tools to elucidate the mechanism of ion conductance at the atomic level and understand protein-lipid interactions. As we continue to build our suite of experimental and molecular modeling tools, we are compiling structural and functional information on the serotonin receptor and gramicidin channel. This work will ultimately lead to a prototype device for sensing based on ion-transport systems. Our work on the gramicidin ion channel led to the complete characterization of the thermodynamic properties of dimer formation necessary for channel function. This work has been written and submitted for publication.

We aimed our tasks at developing combined electrochemical and single-molecule fluorescence capability and conducting both independent and combined measurements

As we continue to build our suite of experimental and molecular modeling tools, we are compiling structural and functional information on the serotonin receptor and gramicidin channel. This work will ultimately lead to a prototype device for sensing based on ion-transport systems.

leading to kinetic and structural information on the gramicidin channel and serotonin receptor. In addition, we added a modeling component to this study. Specifically, we want to compare density-functional theory (DFT) calculations on gramicidin A with experimental observations and compute free-energies of insertion for gramicidin monomers and dimers in a lipid bilayer. We designed and fabricated a fluidic platform that is electronically and optically addressable. With this platform, we successfully measured 11–20 gigohm resistances on n-hexadecane/glycerol monoleate painted bilayers. High electrical resistance is absolutely necessary to achieve single-molecule electrical measurements.

We developed spectroscopic tools and conducted measurements on the gramicidin ion channel. Specifically, we built a new infinity-corrected microscope that utilizes a very high numerical aperture microscope objective ($NA = 1.65$) used for thorough objective evanescent excitation and a cooled ICCD (intensified charge-coupled device) camera capable of single-photon detection. We also designed and constructed a confocal microscope that combines the fast single-molecule fluorescence capabilities with single-molecule imaging.

Using these capabilities, we unequivocally differentiated between rhodamine-6G labeled gramicidin monomeric subunits and channel-forming dimers and tracked their distributions at various temperatures within lipid bilayer assemblies. We achieved absolute identification of individual particles by accounting for both particle velocity and intensity, with dimer intensity being twice that of the monomers. In accordance with Stokes-Einstein's law of diffusion, we observed dimers to diffuse more slowly through the bilayer than the monomers and reported diffusion coefficients of $1.1 \times 10^{-8} \text{ cm}^2/\text{s}$ and $3.5 \times 10^{-8} \text{ cm}^2/\text{s}$ for the dimers and monomers, respectively. By correlating the diffusion data with measured fluorescence intensities of the tracked particles, it was possible to determine the distribution of monomers and dimers within the bilayer at various temperatures. These results led to the complete characterization of the thermodynamic properties of dimer formation necessary for channel function. We determined the temperature dependence of the equilibrium constant, the standard Gibbs free-energy of reaction, the standard enthalpy of reaction, and the standard entropy of reaction. We used molecular modeling tools (specifically DFT) to predict ion transport through gramicidin A. We are implementing DFT to model lipid bilayers to understand lipid protein interactions.

Refereed

Davis, R. W., E. L. Patrick, L. A. Meyer, T. P. Ortiz, J. A. Marshall, D. J. Keller, S. M. Brozik, and J. A. Brozik. 2003. The thermodynamic properties of single-ion channel formation: Gramicidin. *Proc. National Academy of Sciences*, submitted.

50772

Cellular Observatory: Simultaneous Time- and Frequency-Resolved Microscopy

D. W. Chandler, C. C. Hayden, A. K. Luong

Sandia is building a “cellular observatory.” A cellular observatory is a machine capable of monitoring multiple constituents (i.e., proteins, toxins, deoxyribonucleic acid [DNA], ribonucleic acid [RNA], etc.) within a cell in real time, as well as of monitoring the local environment for those constituents (pH, viscosity, ion concentration). We will do this by developing a new type of confocal microscope system for measuring the dynamics of interactions of cellular constituents in real time. The confocal microscope and detection system will have the ability to measure the wavelength, emission time, and polarization of each detected fluorescence photon as a function of the position of laser excitation. In this manner, we will obtain an image of a cell where each pixel contains the entire fluorescence signature (lifetime and frequency spectrum) of every type of fluorescent chromophore measured in each image frame. We may tag some cellular constituents with multiple fluorescent chromophores to make them more detectable. We will do this with unprecedented speed using fast electronics and a high-repetition-rate laser system. The higher spectral coverage (moderate resolution over the entire visible spectrum) will enable us to monitor more species simultaneously, and the higher data accumulation rate will make it possible to take image frames fast enough to monitor real-time dynamics of cellular functions.

We assembled and tested a new microscope that is unique in the world. It is capable of measuring the arrival time, polarization, and color of every photon that it detects. Furthermore, the detector is capable of detecting millions of photons per second, well above the required count rates that are typical of confocal fluorescence microscopy of biological samples. Hence, the rate of data acquisition is limited only by the fluorescence throughput of the microscope itself. This gives us an unprecedented capability to detect and analyze the fluorescence emission of several different fluorophores contained in a sample, and to identify the location and environment of each of the fluorophores. This is precisely the sort of capability that is needed to build a cellular observatory. We worked with a builder of custom-made photon detectors to develop a time- and position-sensitive photon detector capable of 100 μm spatial resolution and 50 ps time resolution. We

We assembled and tested a new microscope that is unique in the world. It is capable of measuring the arrival time, polarization, and color of every photon that it detects....This gives us an unprecedented capability to detect and analyze the fluorescence emission of several different fluorophores contained in a sample, and to identify the location and environment of each of the fluorophores.

collected emission through a microscope objective, dispersed it through a prism, and imaged it onto the face of the detector. We designed and built the electronics so that the detector can acquire data synchronously with a short-pulse laser operating at up to 50 MHz with a wide dynamic range of count rates. In this manner, we can obtain a 100 x 100 image in less than 1 s with excellent signal-to-noise. Each pixel of the image would contain the spectrum of the fluorophores imaged onto that pixel and the arrival time of every photon. We can then display the data in many different manners. We can project an image of a certain color, an image of a particular lifetime, or an image having multiple fluorescing species. In addition to the abilities of the photon detector, we can also use multiple input colors to further enhance our ability to detect multiple species.

52532

Modeling Biomembranes

M. J. Stevens, A. L. Frischknecht, S. J. Plimpton, L. J. D. Frink, D. Y. Sasaki

Understanding the properties and behavior of biomembranes is fundamental to many biological processes and technologies. Microdomains in biomembranes or “lipid rafts” are now known to be an integral part of cell signaling, vesicle formation, fusion processes, protein tracking, and viral and toxin infection processes. Understanding how microdomains form, how they depend on membrane constituents, and how they act not only has biological implications, but also will impact Sandia’s effort in developing membranes that structurally adapt to their environment in a controlled manner. To provide such understanding, we seek to create physically based models of biomembranes. Using these models, we will apply molecular dynamics (MD) simulations and classical density-functional theory (DFT) calculations to phenomena such as microdomain formation, membrane fusion, pattern formation, and protein insertion. Because lipid dynamics and self-organization in membranes occur on length and time scales beyond atomistic MD, we will use coarse-grained models of double-tail lipid molecules that spontaneously self-assemble into bilayers. Using such a model, we have already demonstrated that the time scales of lipid diffusion and fusion intermediates are accessible to MD simulations. This model enables the study of a whole set of membrane dynamics, including those listed above. These coarse-grained models can also be used in our DFT code. DFT will provide equilibrium information on membrane structure, free energies and routes to assembly of membrane-bound proteins, and free energies of permeation for water, ions, proteins, and toxins as they traverse the membrane. We will perform experimental work to further help elucidate the fundamental organizational principles. This project will produce significant new understanding of biomembrane structure and dynamics and will build a strong foundation of physically based models for further development.

We developed coarse-grained models for lipid molecules that yield fluid and gel phases. We are now calculating phase diagrams for the fluid phases to help improve the models. We are using these models to perform MD simulations and DFT calculations on two-component lipid bilayers. This work focuses on understanding microdomain (raft) formation in biomembranes. We implemented dipole interactions in the

This project will produce significant new understanding of biomembrane structure and dynamics and will build a strong foundation of physically based models for further development.

LAMMPS (Large-Scale Atomic/Molecular Massively Parallel Simulator) MD code for future treatment of coarse-grained water and charged lipids. We also performed corresponding experimental work. In particular, atomic-force microscopy (AFM) studies of two-component membranes have detected phase separation and chemical-recognition-induced phase changes. We performed AFM and fluorescence studies of lectin binding on saccharide-functionalized membranes to probe steric interactions in ligands. We successfully accomplished simulation of membrane fusion ahead of schedule and uncovered two new aspects of membrane fusion. Fusion initiation is promoted by splaying of the lipid tails, which allows single-lipid molecules to have a tail chain in both of the fusion membranes. In contrast to the traditional model of central fusion, we found fusion occurring at the contact edge where the area per lipid is larger, allowing for more tilt of the lipids, which promotes the initial molecular rearrangements needed for fusion.

*We successfully accomplished
simulation of membrane fusion
ahead of schedule and
uncovered two new aspects of
membrane fusion.*

Refereed

Bondurant, B., J. A. Last, T. A. Waggoner, A. Slade, and D. Y. Sasaki. 2003. Optical and scanning probe analysis of glycolipid reorganization upon Concanavalin A binding to mannose-coated lipid bilayers. *Langmuir* **19**:1829–37.

Sasaki, D. Y. 2003. Control of membrane structure and organization through chemical recognition. *Cell Biochemistry and Biophysics* **38**, in press.

Stevens, M. J., J. Hoh, and T. B. Woolf. 2003. Insights into the molecular mechanism of membrane fusion from simulation: Evidence for the association of splayed tails. *Phys. Rev. Lett.*, submitted.

52533

Reverse-Engineering Biological Networks: Applications in Immune Responses to Bioterrorism Threats

J. M. Faulon, J. A. Timlin, A. Slepoy, S. B. Martin, D. M. Haaland, G. S. Davidson, A. Martino, E. E. May, Z. Zhang

Sandia's aim is to determine the network of events, or the regulatory network, that defines an immune response to a biotoxin. We anticipate that by inferring a regulatory network we will be able to isolate a handful of specific regulatory elements that fingerprint a response. Ultimately, this work will provide the blueprint of a simple experiment where the biotoxin is characterized by measuring only the fingerprint elements rather than the entire immune response.

As a model system, we are studying a T-cell regulatory network triggered through activation of a tyrosine kinase receptor using a combination of pathway-knockout and time-series microarray experiments. Our approach consists of five steps: (1) microarray experiments, (2) data error analysis, (3) data clustering, (4) reverse-engineering, and (5) network dynamics analysis and fingerprint identification. The technological outcome of this study will be a suite of experimental protocols and computational tools that reverse-engineer regulatory networks, provided a minimum amount of data. The practical biological outcome of this work should be the discovery of immune-response fingerprints to a biotoxin in terms of expression levels of regulatory elements.

Inferring regulatory networks from microarray data is a new field of investigation that is no more than 5 years old. To the best of our knowledge, this work is the first attempt that integrates experiments, error analyses, data clustering, inference, and network analysis to solve a practical problem. While microarrays have been used with time-series experiments and gene- or pathway-knockout experiments, we are not aware of any study merging both types of experiments. The systematic approach of counting, enumeration, and sampling is new to the field of network reverse-engineering. The resulting mathematical analyses and computational tools should lead to new results on their own and should be useful to others who analyze and infer networks.

Using gene microarray technology, we are studying interleukin-2 (IL-2) signaling as a model system, because IL-2 plays a central regulatory role in the growth, proliferation, and survival of T-cells in immune responses. Our microarray

Inferring regulatory networks from microarray data is a new field of investigation that is no more than 5 years old. To the best of our knowledge, this work is the first attempt that integrates experiments, error analyses, data clustering, inference, and network analysis to solve a practical problem.

strategies use previous knowledge of IL-2 signaling to plan appropriate isolation and time-course experiments.

We established mouse T-cell cultures, harvested ribonucleic acid (RNA) under various conditions, and designed microarray-experiment infrastructures. We developed a single-strand complementary deoxyribonucleic acid (cDNA) synthesis and fluorescent-dye-labeling protocol to generate microarray probes. We collected our first microarray data on a time course of 0, 1, 3, and 6 hrs, and we successfully replicated these experiments. We detected induced genes with IL-2 stimulation (green-colored genes) and established that our experimental protocols are sound. We then scanned the mouse microarrays with our hyperspectral microarray scanner. We applied multivariate curve resolution (MCR) to the analysis of the hyperspectral data to discover all of the fluorescent-emitting sources and to quantify their contributions to the signal. To increase hybridization and prevent microarray slides from being affected by green contamination, we proposed a new protocol where a rotary shaker is used to improve hybridization and where the slides are passivated for 6 hrs in a 50% humid environment before a print run is started.

We used V_x Insight and k -means to cluster the well-known and publicly available Spellman yeast cell-cycle data. We smoothed and discretized the clustered profiles. We implemented a new method also to detect apparently coordinated regulation that occurs in only a subset of a collection of microarray experiments. We showed that within these subsets there are genes, with statistically unexpected correlations, that are not visible when the whole set is considered.

We developed algorithms to count, enumerate, and sample qualitative and Boolean networks matching clustered microarray data. We established the relationship between the number of data points and the number of network solutions. We tested all codes using the clustered and discretized Spellman data; we inferred a Boolean network and computed its dynamical expression profiles and attractors using Boolean dynamics. We produced a logic-circuit schematic for the inferred network. We will use this logic circuit later to simulate continuous dynamical expression profiles. We developed a clustered-enumeration technique, where enumerated networks were clustered using the distance between dynamical expression profiles. We found the number of clusters to be much smaller than the number of networks, even for small distances. We found that the relationship between the number of clusters and the number of networks follows a power law.

Our microarray experimental plans for upcoming work include hybridizing and scanning chips using the RNA we harvested. Data collected will include point-time course for several isolated pathways. We will coordinate our results with results from the hyperspectral scanner with MCR analysis to increase the statistical significance of low-expressing genes. We will identify interacting pairs of genes by clustering a large amount of published microarray data not collected from time-series experiments. To cluster pairs of genes, we must also improve our force-directed graph-layout algorithm. We implemented a preliminary version of the clustering algorithm to handle large datasets, and we plan to further improve the method as necessary. We will develop algorithms that infer networks using continuous functions and test these algorithms using the T-cell data. We will perform clustered enumeration on the same data to produce discrete models. We will compute the number of time points and isolated-pathway experiments and will plan new experiments accordingly. We will use the logic-circuit schematic to compare continuous and discrete models and will investigate the extent to which continuous concentration can be modeled as discrete Boolean states.

Refereed

Faulon, J. L., and S. B. Martin. 2003. Using graph extended degree sequence to characterize molecular graphs and biological networks. Paper presented at the American Mathematical Society Meeting, Boulder, Colorado.

Martin, S. B., R. D. Carr, and J. L. Faulon. 2003. Random removal of edges from scale free graphs. *Internet Mathematics*, submitted.

52536

High-Throughput Identification of Molecular Machines Involved in Membrane Signaling and Toxin Pathways

A. K. Singh, M. Z. Hadi, V. A. Vandernoot, G. H. Kruppa, S. Chhabra, S. P. Gaucher, D. J. Throckmorton

Sandia seeks to develop a high-throughput method to identify molecular machines (protein complexes) in a cell. Although genes are the information repository of an organism, it is the proteins that carry out all functions. Proteins rarely act alone; they interact with other proteins to perform cellular tasks. Protein complexes are responsible for almost all biological functions, including cell signaling, transport through membranes, and biotoxin pathways. Comprehensive identification of protein-protein interaction will lead to better understanding of these functions, enabling development of improved biosensors and inhibitors for chemical/biological weapon (CW/BW) agents.

The method involves using ligand-modified magnetic beads immobilized in a microtiter plate by a magnet to selectively isolate genetically tagged or native proteins and associated complexes. The purified protein complexes, bound to the magnetic beads, are then cross-linked, proteolyzed into peptides, and analyzed by Fourier-transform ion cyclotron resonance mass spectroscopy (FT-ICR/MS). We will analyze the MS data by bioinformatics software to provide identification of proteins and by constraint-based protein structure models to elucidate topology of the complexes.

We will also determine the differences in expression of protein in a microorganism in response to different stressors. The techniques used will be two-dimensional (2-D) gel electrophoresis and isotope-coded affinity tag (ICAT) analysis. After 2-D electrophoresis, we will use matrix-assisted laser desorption/ionization time-of-flight (MALDI-TOF) MS to excise, proteolyze, and analyze the bands showing differential expression. The over- or underexpressed proteins then can be used as baits to pull down complexes, as described above.

- *Growth of *Desulfovibrio vulgaris* (Hildenborough) cultures. We obtained *D. vulgaris* cultures from ATCC (a global nonprofit bioresource center) and the University of Missouri (MU) and successfully grew these cultures for up to six passes. We grew cells anaerobically at 37°C on lactate-sulfate media using sealed 50 ml culture tubes that we purged with N₂ for 2 hrs to reduce the growth media. We monitored the cell growth*

Sandia seeks to develop a high-throughput method to identify molecular machines (protein complexes) in a cell.... We will also determine the differences in expression of protein in a microorganism in response to different stressors.

using optical density measurements (OD600). We obtained triplicate growth curves for the culture from MU and a single growth curve for the culture from ATCC. We estimated doubling times from semilog plots (OD600 versus time) in the exponential region of the growth curve. We estimated the average doubling time for the culture from MU to be 280 min.

- *Diagnostic polymerase chain reaction (PCR) reactions for D. vulgaris.* We used PCR amplification runs, for amplifying a specific gene encoded within the *D. vulgaris* genome, to verify the identity of cultures that were grown. We obtained genomic deoxyribonucleic acid (DNA) of cultures from both sources using a Qiagen Genomic Tip (100G) kit. We obtained primers designed to amplify the small subunit of the nitrite reductase (NfrH) of *D. vulgaris* from Invitrogen, Inc. The primer sequences are as follows: NfrH forward: 5'-GGG ACA CGC CAA CAT TTC-3'. NfrH reverse: 5'-GGC GTT GAC CAC CTC TTT-3'. We carried out the PCR amplification using a Tetrad thermocycler from MJ Research. A 167-base pair (bp) fragment corresponding to the NfrH gene was amplified for genomic DNA of cultures from both sources, thus confirming the identity of the strains.

- *Western analysis: Time-course experiment for heat shock on D. vulgaris.* We quantified whole-cell protein extracts using the BCA assay reagent (from Sigma-Aldrich), using bovine serum albumin (BSA) as the standard. Equal amounts of protein were loaded on a 4 ~ 10% gradient SDS-PAGE (sodium dodecyl sulphate polyacrylamide gel electrophoresis) gel, transferred onto a nitrocellulose membrane, and probed with anti-HSP (heat shock protein) 70 (*E. coli*) antibody. HSP 70 from *E. coli* shows ~ 70% sequence identity to the corresponding protein from *D. vulgaris*. There was an increased production of HSP 70 with time in *D. vulgaris* cells subjected to heat shock. We then used the 0 min and 30 min whole-cell protein extracts for further analyses using 2-D gels and ICAT techniques.

- *Differential in-gel electrophoresis: Comparison of 0 min and 30 min heat-shock runs.* We labeled whole-cell protein extracts from 0 min and 30 min with Cy3 (green) and Cy5 (red) dyes and gel electrophoresis. We submitted samples to the University of Georgia's Proteomics Facility. We could clearly see differences on a proteome level for proteins that were overexpressed and repressed, as well as those that remained unchanged during the heat-shock process. We identified a total of 650 proteins out of the 3700 or so proteins in the *D. vulgaris* proteome. A total of 63 proteins showed differences between the heat-shocked (30 min) and non-heat-shocked conditions.

Currently, we are spotting ~ 96 proteins for further analysis using MS.

- *ICAT analysis: Comparison of 0 min and 30 min heat-shock runs.* As a complement to the 2-D gel analysis for the heat-shocked and non-heat-shocked proteome samples, we used the ICAT technique to accurately quantify levels of overexpressed and repressed proteins. The ICAT methodology involves labeling two distinct populations (heat-shocked and non-heat-shocked, in this case) with heavy and light reagents that are then digested with trypsin and subjected to a liquid chromatography (LC)/MS/MS analysis. Using this technique, we identified a total of 219 proteins out of the *D. vulgaris* proteome. Out of this pool of proteins, we identified seven stress-related proteins. We are currently evaluating more sensitive separation techniques to further identify proteins of interest to be used as baits for identifying molecular machines within the *D. vulgaris* proteome.

Refereed

Singh, A. K., J. Brennan, T. J. Shepodd, and D. J. Throckmorton. 2003. Gradient-elution electrochromatography in microchips. *MicroTotal Analysis Systems* **1** (October, Lake Tahoe, California): 1.

Computational and Information Sciences

The goal of the Computational and Information Sciences investment area is to develop next-generation computing and information systems capabilities that will provide a strategic benefit to the nuclear weapons program and other important Sandia business areas. Recent advances in massively parallel computing technology are greatly expanding the usefulness of computer simulations. Computational and information sciences proposals focus on system-scale modeling of nuclear weapons. Growth areas include modeling complex phenomena, multiscale modeling, optimization and prediction under uncertainty, advanced architectures, and informatics. Another important aspect of this work is creating technologies that make high-performance computers easier to use and thus broaden the impact of such computing on Sandia's programs.

Over the past decade, parallel computers have been used with great success in many important scientific simulations. A core requirement of many engineering and scientific applications is the need to solve linear and nonlinear systems of equations. *Parallel Repartitioning for Optimal Solver Performance* is making strides in parallel repartitioning to improve solver performance. By combining the parallel data-redistribution tools in

ZOLTAN with the state-of-the-art preconditioning and linear-solver technology in TRILINOS, Sandia is addressing problems surrounding partitioning and data and workload distribution. Two copyrights have been obtained on this work.

26512

Parallel Atomistic Computing for Failure Analysis of Micromachines

P. M. Gullett, A. Slepy, G. J. Wagner

To quantify microstructure-property relations related to weapon microcomponents, Sandia is developing atomistic algorithms for parallel computers that quantify continuum quantities relevant to design and finite-element (FE) codes. With these and other serial computing tools, we are performing atomistic simulations of various sizes, geometries, materials, and boundary conditions (BCs). Currently, no capability exists that can handle the different size-scale effects required to predict failure. Nonlocal continuum models have been proposed to address this problem; however, they are phenomenological in nature and are difficult to validate for microscale components. Our goal is to separately quantify damage nucleation, growth, and coalescence mechanisms to provide a basis for macroscale continuum models that will be used for micromachine design. Because microcomponent experiments are difficult, a systematic computational study that employs Monte Carlo (MC) methods, molecular statics, and molecular dynamics (MD) (embedded atom method [EAM] and modified embedded atom method [MEAM]) simulations to compute continuum quantities will provide mechanism-property relations associated with the following parameters: specimen size, number of grains, crystal orientation, strain rate, temperature, defect nearest-neighbor distance, void/crack size, chemical state, and stress state. This will be the first foundational study to quantify size-scale effects from nanometers to microns in terms of damage progression and thus potentially allow for optimized micromachine designs that are more reliable and have higher fidelity in terms of strength. To accomplish this task, several atomistic methods need to be developed and evaluated to cover the range of defects, strain rates, temperatures, and sizes that a material may see in micromachines. As such, we are providing a complete set of tools for large-scale atomistic simulations that include preprocessing of realistic material configurations, processing under different environments, and post-processing with appropriate continuum quantities. By running simulations with these tools, we can determine size-scale effects that correlate microstructure and defect configurations with mechanical properties of materials.

- *Computational tool development.* We successfully added the MEAM potential to the scalable massively parallel (MP) WARP code. The MEAM potential adds angular dependence to the computation of the atomic energy, allowing

This will be the first foundational study to quantify size-scale effects from nanometers to microns in terms of damage progression and thus potentially allow for optimized micromachine designs that are more reliable and have higher fidelity in terms of strength.

for simulation of systems that exhibit bond directionality, such as hexagonal close-packed structures, body-centered cubic structures, diamond cubic structures, and alloy systems. This new functionality provides a powerful computational tool that is well suited for a variety of large-scale simulations with realistic system configurations. We verified the implementation using previously published surface-energy calculations.

We completed the implementation of the first scalable MP version of an MC simulation using the EAM potential. We verified the code by making comparisons with the serial MC version and by performing a scaling study.

- *Atomistic simulations.* Our work in this area focused on void growth at high strain rates and ambient temperatures under uniaxial tension. Specifically, we studied the effect of size scale on both single-crystal and polycrystalline nickel (Ni) face-centered cubic (FCC) systems containing a single void. For single crystals strained on the $\langle 100 \rangle$ direction, the stress-strain behavior is linear until yield. We see the beginnings of plastic failure when dislocations are emitted from the surface of the void. Void growth is minimal before plastic failure and grows as a linear function of plastic strain. In contrast, polycrystallines exhibit a bilinear stress-strain relationship. The slope of the initial linear response matches the elastic modulus of the single-crystal systems. At 5% strain, the slope of the stress-strain response is reduced by 30% and continues linearly until failure. This behavior is consistent across the size scales. For the single-crystal, single-void simulations, the void grows as a function of the plastic strain. When plotted accordingly, we observe no size-scale effects. However, when void growth is plotted as a function of the total strain, a definite size-scale dependence occurs. In this case, the smaller the specimen size, the slower the void growth. This trend arises because the stress-strain response stays longer in the elastic regime for smaller specimen sizes, i.e., the yield stress increases with decreasing specimen size. As such, since the void is dependent on plasticity for growing, the void grows slower for a larger-size specimen. However, if the elastic strains are subtracted from the total strains, then void growth versus plastic strain is invariant to size scale. In the polycrystalline system, minimal void growth occurs throughout the simulation. In this case, the void grows until an edge crack arises and then propagates in a mode-I fracture-mechanics manner.

We completed the implementation of the first scalable MP version of an MC simulation using the EAM potential.

26514

Smart-Sensor Technology for Joint Test Assembly Flights

K. D. Marx, C. M. Pancerella, D. A. Sheaffer, Jr., R. C. Armstrong, A. B. Doser, E. P. Parker, N. M. Berry, R. L. Bierbaum, J. L. Dimkoff, E. J. Walsh, T. J. Deyle

The world relies on sensors to perform a variety of tasks from the mundane to the sophisticated. Currently, processors associated with these sensors are sufficient only to handle rudimentary logic tasks. Although multiple sensors are often present in such devices, there is insufficient processing power for situational understanding. Until recently, no processors that met the electrical power constraints for embedded systems were powerful enough to perform sophisticated computations. Sandia performs many expensive tests using sensor arrays. Improving the efficacy, reliability, and information content resulting from these sensor arrays is of critical importance. With the advent of powerful commodity processors for embedded use, a new opportunity to do just that has presented itself.

The goal of this project was to demonstrate the feasibility of using embedded processors to increase the amount of usable information derived from sensor arrays while improving the believability of the data. We focused on a system of importance to Sandia: joint test assemblies (JTAs) for intercontinental ballistic missile (ICBM) warheads. We studied (1) two electromechanical systems to provide data, (2) sensors used to monitor those systems, (3) the processors that provide decision-making capability and data manipulation, (4) the use of artificial intelligence (AI) and other decision-making software, and (5) a computer model for the training of AI software.

The goal of this work was to show that intelligent embedded processors could be used to direct the flow of information from sensor arrays such as those used in JTA flights. We used two simple electromechanical systems with sensors as test-beds to mimic JTA instrumentation.

The heart of a smart-sensor system is the computer processor. In each of the two systems studied, we selected the processor for characteristics that would make it flyable on a JTA flight. These characteristics include small size, light weight, and no moving parts.

The first electromechanical system used was an aluminum (Al) bar mounted on a vibration shaker. The bar was instrumented with strain gauges, temperature sensors, and a

Sandia performs many expensive tests using sensor arrays. Improving the efficacy, reliability, and information content resulting from these sensor arrays is of critical importance. With the advent of powerful commodity processors for embedded use, a new opportunity to do just that has presented itself.

tachometer. We connected the sensor output through a data-acquisition board to a 170 MHz PC104 processor.

We demonstrated the capability for recognizing different situations (and hence providing the opportunity to react to them) by taking fast-Fourier transforms (FFTs) of the two streams of strain-gauge data. This made it possible to determine the state of the JTA mockup system and to detect the presence of obstacles impeding the motion of the two arms of the AI bar. This represents a quantitative milestone for the project—demonstrating that a flyable processor could perform FFTs and report results at this frequency.

We explored the potential for the use of AI as part of a decision-making process. In a JTA smart-sensor system, AI modules could learn to determine system states, detect changes in sensor output, detect failures, and then take appropriate action in response. The initial attempt to introduce AI involved the use of a self-organizing map (SOM). We used data recorded from the sensors to train a SOM, which then categorized the data.

The training of the SOM was successful. When run on a desktop computer, the SOM was capable of recognizing operating states and reporting the results. We achieved proof-of-principle up to the point of training the SOM and running it against sensor data. However, because of unanticipated idiosyncrasies of MATLAB-produced C code, we found it impossible to install the SOM on the JTA mockup computer processor and thereby demonstrate that such an AI module could run on a flyable system.

We then recognized that the computer processor described above was relatively slow and limited in memory and in flash disk space compared to processors currently available. So we purchased an 800 MHz PC104 processor. This processor was embedded in a new electromechanical system referred to as the *geophone grid (GG) system*. The GG system consisted of nine geophones arranged in a 3 x 3 grid on a floor. The idea was to use the GG system to detect and locate the occurrence of footsteps within the grid. We took data from the nine sensors at the rate of 10,000 samples/s/sensor (i.e., 90,000 total samples/s).

We analyzed the geophone data by using a neural net approach known as *back propagation*. We ran experiments with the GG/back-propagation neural network (BPNN) system, which involved training BPNNs. We used the trained BPNNs to detect the presence of footsteps near a single geophone and to determine the location of footsteps in the grid. The BPNN proved very capable in detecting a footstep via a single

When run on a desktop computer, the SOM was capable of recognizing operating states and reporting the results. We achieved proof-of-principle up to the point of training the SOM and running it against sensor data.

geophone sensor. Training and detection in the nine-sensor grid was limited to a desktop computer. However, the objective of demonstrating that the single-sensor AI system could be run on the PC104 processor was a complete success. Furthermore, there appears to be no reason that the nine-sensor BPNN would not have worked just as well on the embedded processor as on the desktop computer.

This project explored the potential that embedded commodity processors have for enabling smart-sensor systems. We demonstrated the principle and made quantitative information available from which to proceed with further development.

Other Communications

Marx, K. D., R. C. Armstrong, N. M. Berry, R. L. Bierbaum, T. J. Deyle, J. L. Dimkoff, A. B. Doser, C. M. Pancerella, D. A. Sheaffer, and E. J. Walsh. 2003. Smart-Sensor Technology for Joint Test Assembly Flights. Sandia Technical Report SAND2003-8589, Sandia National Laboratories, Livermore, California.

26515

Multilevel Methods for Nonlinear Structural Mechanics

C. R. Dohrmann, M. W. Heinstein

Robust and scalable parallel algorithms for solving structural mechanics problems are essential for computing modeling and simulation to have a significant impact on weapons programs at Sandia. Computational models with millions of unknowns are becoming commonplace in the engineering sciences. A major challenge with these models is obtaining solutions in reasonable amounts of time. For example, the critical time-step used in explicit transient dynamics decreases with mesh refinement and can increase runtimes significantly. Implicit dynamic formulations are not constrained by a critical time-step, but they do require the solution of large systems of equations. This research addresses the need to solve such equations for structural mechanics and other applications.

We made preliminary implementations of two solvers developed in this project in Sandia's parallel structural dynamics code SALINAS. In a benchmark problem, both solvers were quite competitive with the existing finite-element tearing and interconnecting—Defense Programs (FETI—DP) solver in SALINAS. A description and numerical results for one of the solvers appears in an article that was accepted for publication in *SIAM [Society for Industrial and Applied Mathematics] Journal for Scientific Computing*. We developed a mathematical theory for one of the solvers in collaboration with the Mathematics Department at the University of Colorado at Denver. This theory provides a strong mathematical foundation for the solver and shows that it scales well with the number of subdomains and the number of elements per subdomain. We documented this work in an article for publication in the journal *Numerical Linear Algebra with Applications*. We presented research results at the 6th International Association for Mathematics and Computer Simulation (IMACS) International Symposium on Iterative Methods in Scientific Computing and at the 7th U.S. National Congress on Computational Mechanics.

Robust and scalable parallel algorithms for solving structural mechanics problems are essential for computing modeling and simulation to have a significant impact on weapons programs at Sandia. ...This research addresses the need to solve such equations for structural mechanics and other applications.

Refereed

Dohrmann, C. R. 2003. A preconditioner for substructuring based on constrained energy minimization. *SIAM J. Scientific Computing*, accepted.

Mandel, J., and C. R. Dohrmann. 2003. Convergence of a balancing domain decomposition by constraints and energy minimization. *Numerical Linear Algebra with Applications*, accepted.

Other Communications

Dohrmann, C. R. 2003. A preconditioner for substructuring based on constraints and energy minimization. Paper presented at the 6th IMACS International Symposium on Iterative Methods in Scientific Computing, March, Denver, Colorado.

Dohrmann, C. R., and J. Mandel. 2003. A preconditioner for substructuring based on constrained energy minimization. Paper presented at the 7th U.S. National Congress on Computational Mechanics, July, Albuquerque, New Mexico.

26516

Algorithmic Support for Commodity-Based Parallel Computing Systems

V. J. Leung, S. P. Goudy, R. D. Carr, D. P. Bunde, C. A. Phillips, M. A. Bender, O. D. Parekh

Distributed-memory supercomputers run many parallel programs simultaneously. Users submit their programs to the job queue. When a job is scheduled to run, it is assigned to a set of available processors. Job runtime depends not only on the number of processors but also on the particular set of processors assigned to it, as well as on the routes used for communication between those processors. Jobs should be allocated to localized clusters of processors to minimize communication costs and to avoid bandwidth contention caused by overlapping jobs.

Previous experimental results demonstrate that the “average number of communication hops” between the processors allocated to a job strongly correlates with the job’s completion time. This project gave processor-allocation algorithms for minimizing the average number of communication hops between the assigned processors for grid architectures.

The associated clustering problem is as follows: Given n points in “a d -dimensional grid,” find k points that minimize their average pairwise grid distance. Exact and approximate algorithms are given for these optimization problems. Sandia implemented one of these algorithms on Computational Plant (CPlant), a Sandia supercomputer, and will include it in CPlant System Software Version 2.1, to be released. We are preparing a conference paper reporting some of our results.

Our accomplishments can be grouped into three areas: routing, allocation, and scheduling. Recent experiments on Antarctica indicate that routes we provided earlier in the project decrease completion time for some application codes by at least 50% over the routes generated by Myricom’s Simple Routes Program. Based on this work in CPlant routing, we also had an impact on the routing for Red Storm. We detected and patched a deadlock problem in the Red Storm routing algorithm.

Allocation accomplishments are grouped into three areas: one-dimensional (1-D) reduction, minimizing the number of communication hops, and the continuum problem. In the area of 1-D reduction, we delivered improved space-filling curves for CPlant Runtime Software Release 2.0.1.6 with 30% throughput improvement over the 1.x allocator. We selected the curves

Recent experiments on Antarctica indicate that routes we provided earlier in the project decrease completion time for some application codes by at least 50% over the routes generated by Myricom’s Simple Routes Program.

through a combination of analysis and experimentation. We also delivered space-filling curves for the Ross/Ronne repartition. For space-filling curves to traverse all three interconnect dimensions recursively, it must be modified for the number of planes in a partition. Such modification will not be necessary for the 2-D and 3-D allocators below.

To minimize the number of communication hops, we achieved the following results. We found (1) a linear-time exact algorithm in one dimension, (2) an efficient two-approximation algorithm in d dimensions, for any constant d , (3) some lower bounds for this algorithm, and (4) two efficient polynomial-time approximation schemes in two dimensions. We formulated the exact problem in d dimensions as a quadratic program that can be solved as either a semidefinite program or an integer linear program. Because the two-approximation algorithm balances solution quality and simplicity, we believe this is the correct processor-allocation algorithm to implement on supercomputers. Indeed, it is slated for inclusion in CPlant System Software Version 2.1, to be released. In one preliminary test with an application code, the two-approximation allocation ran 16% faster than the allocation given by the 1-D reduction above.

For the continuum problem, we formulated this optimization problem in mathematical terms. Then we considered a one-parameter family of clusters and found the shape of the optimal cluster in this limited family. From this calculation, we saw that the optimal city is not circular. Next we carried out a full variational calculation and determined an interesting nonlinear differential equation satisfied by the boundary of the optimal cluster. The optimal cluster is nearly circular in shape but is not a disk. Our principal conclusions are that as long as the allocation of processors is clustered in a tight shape having no holes or only small holes, the allocation will be extremely close to optimal.

In scheduling, we proposed a new way to quantitatively assess how well fairness is implemented by a scheduling policy. The current CPlant scheduling policy causes unfair treatment of 10% of jobs. We evaluated the effects of several possible changes to scheduling policy through simulations. These changes included changing the starvation threshold (from 24 to 72 hrs), imposing a maximum time limit for jobs, disallowing unfair jobs from the starvation queue, and using reservations for all jobs (conservative backfill variations) instead of a starvation queue mechanism. Simulations show that modifications can reduce unfairness to less than 3% of jobs.

In one preliminary test with an application code, the two-approximation allocation ran 16% faster than the allocation given by the 1-D reduction above.

With simulation, we also studied the throughput of a fixed number of processors partitioned into various numbers of clusters.

26517

Parallel Repartitioning for Optimal Solver Performance

K. D. Devine, R. T. Heaphy, M. A. Heroux, B. A. Hendrickson, E. G. Boman

The partitioning of data and work for distributed-memory solver packages is typically established by the application that calls the solver. However, the best distribution of data for the application is often not the best for the solver. Overlapping Schwarz preconditioners, for example, may have very unbalanced workloads (due to work required in the overlap regions), even if the data distribution is balanced for other phases of the solver computation. Robustness and performance of linear solvers can be greatly improved by developing partitioning strategies that are optimized for preconditioners and solvers.

By combining the parallel data redistribution tools in ZOLTAN with state-of-the-art preconditioning and linear solver technology in TRILINOS, Sandia developed partitioning strategies that enable improved performance and robustness for preconditioners and solvers. The goals of this research were as follows:

- (1) Incorporate ZOLTAN into the TRILINOS framework.*
- (2) Develop meaningful cost functions that give good parallel data redistribution for solvers.*
- (3) Develop the algorithmic theory and implementation that allow us to compute data distributions with the best properties for preconditioners.*

We made significant progress toward all of these goals. We refined our implementation of ZOLTAN in TRILINOS so that it is applicable to all TRILINOS data objects. Cost functions that include information about the application promise to influence repartitioning so that resulting decompositions are both balanced and effective for robust preconditioning; these cost functions are a new and innovative way to incorporate robustness information into partitioning models. Algorithmically, we implemented several strategies for effective preconditioning, including multiconstraint partitioning techniques and hypergraph partitioning.

Incorporation of parallel data repartitioning (PDR) into TRILINOS was an important part of this project. We improved our interface and capabilities for PDR in TRILINOS by extending PDR capabilities to three new Epetra (essential implementation) classes and completing the first generic

(black and white photo on left and color photo on right) Zoltan's hypergraph-partitioning algorithms generate a decomposition of a polymer self-assembly matrix from Sandia's density-functional theory code Tramonto. Due to its semidense structure (left), this matrix cannot be partitioned well using traditional graph partitioners. In the hypergraph decomposition (right), colors indicate the assignment of matrix rows to processors; rows and columns are permuted to reflect the decomposition. In this example, hypergraph partitioning produced decompositions with 31%–56% lower communication volume than graph partitioning.

By combining the parallel data redistribution tools in ZOLTAN with state-of-the-art preconditioning and linear solver technology in TRILINOS, Sandia developed partitioning strategies that enable improved performance and robustness for preconditioners and solvers.

implementation of PDR classes in Tpetra (templated C++ implementation). We successfully demonstrated our JAVA™ PDR capabilities in Jpetra (JAVA™ implementation) and began production use of PDR in XYCE™ with positive results.

We continued investigating cost metrics for more effective partitioning. This work resulted in an undergraduate computer-science thesis on physics-based partitioning for solver improvement in convection-diffusion problems.

We completed implementation of multiconstraint recursive-coordinate bisection-partitioning algorithms, where multiple object weights per object allow partitioning with respect to multiple criteria. We will deliver this capability in ZOLTAN v1.6.

We also made significant progress on hypergraph-partitioning algorithms. We extended our multilevel hypergraph-partitioning algorithm to include recursive bisection of data into arbitrary numbers of partitions. To quantify benefits of various coarsening and refinement strategies, we conducted a design-of-experiment analysis. The resulting hypergraph methods in ZOLTAN were competitive with existing hypergraph technology. Experiments applying the hypergraph methods to matrices from density-functional theory and circuit simulations demonstrated 30%–55% reductions in communication volume compared to graph-partitioning techniques.

Experiments applying the hypergraph methods to matrices from density-functional theory and circuit simulations demonstrated 30%–55% reductions in communication volume compared to graph-partitioning techniques.

Refereed

Boldt, M. W. 2003. An excursion in high-level mathematical modeling through convection-diffusion model problems. Senior Honors Thesis, St. John's University, Collegeville, Minnesota.

Devine, K. D. 2003. Parallel data services for dynamic, unstructured and adaptive applications. (Invited) Paper presented at Lawrence Berkeley National Laboratory, Livermore, California.

Devine, K. D. 2003. Parallel data services for dynamic, unstructured and adaptive applications. (Invited) Paper presented at Stanford SCCM.

Devine, K. D. 2003. Parallel data services for dynamic, unstructured and adaptive applications. (Invited) Paper presented at UC-Davis, Davis, California.

Devine, K. D. 2003. ZOLTAN: Parallel data services and dynamic load balancing. Paper presented at SIAM CSE'03, February, San Diego, California.

Devine, K. D., and M. A. Heroux. 2003. Minisymposium: A toolkit approach to parallel application development. Paper presented at SIAM CSE'03, February, San Diego, California.

Heaphy, R. T. 2003. ZOLTAN: Parallel data services and dynamic load balancing. (Invited) Paper presented at MRCCS/NSF 2003 Summer School: High-Performance Computing in Finite-Element Analysis, Manchester University, Manchester, England.

Heroux, M. A. 2003. An overview of TRILINOS. Paper presented at SIAM CSE'03, February, San Diego, California.

Heroux, M. A. 2003. An overview of TRILINOS. Paper presented at the IMAC Workshop, April, Denver, Colorado.

Heroux, M. A., and J. M. Willenbring. 2003. TRILINOS User's Guide. Sandia Technical Report SAND2003-2952, Sandia National Laboratories, Albuquerque, New Mexico.

Heroux, M. A., *et al.* 2003. An overview of the TRILINOS project. *ACM TOMS*, accepted.

38610

Graduated Embodiment for Sophisticated Agent Evolution and Optimization

M. B. E. Boslough, M. J. McDonald, P. G. Xavier, J. A. Sprigg, A. Breckenridge

Many problems related to national security, ranging from urban warfare to unmanned airborne vehicle reconnaissance, involve intelligent systems. In this project, Sandia seeks to develop and implement evolutionary methods to computationally optimize behaviors by designing a representation for solutions and defining a fitness function by which they can be evaluated. The ultimate goal is to develop a methodology to generate genetic programs that are competitive with human-produced results and that can be used in real-world applications.

We are pursuing this goal by developing a modeling and simulation (ModSim) environment based primarily on the Sandia framework UMBRA and by building genetic programming methods that can be integrated into the UMBRA ModSim framework. The evolutionary programming techniques provide behavior algorithms that are evolved using high-performance massively parallel (MP) computers that provide a synthetic environment that ranges from a low-fidelity “toy world” universe to high-fidelity realism.

The essence of “graduated embodiment” is captured by our strategy of evolving agent behaviors in a hierarchical fashion by staging fitness evaluation through multiple levels of fidelity. Initial behaviors must evolve in a low-fidelity universe to keep the computational requirement at a practicable level. As robust and useful behaviors develop, they can be “tuned” at a higher-fidelity, more computationally intense level. The exploration part of evolution is emphasized in the low-fidelity stage, whereas the high-fidelity simulation stage focuses on exploitation.

This project takes advantage of the fact that genetic programming at least partially possesses the three attributes that have not yet been demonstrated in automatically generated computer programs: wide applicability, scalability, and competitiveness with human-produced results. These attributes are needed to produce the ultimate goal of the system for automatically creating computer programs to produce useful behavior algorithms.

Work progressed along two main fronts: (1) development of a ModSim environment based primarily on the Sandia

The essence of “graduated embodiment” is captured by our strategy of evolving agent behaviors in a hierarchical fashion by staging fitness evaluation through multiple levels of fidelity.

framework UMBRA, and (2) development of genetic programming methods that can be integrated into the UMBRA ModSim framework to provide behavior algorithms that are evolved within a high-performance MP computing environment. We established an experimental system, as well as low- and high-fidelity environments, with associated evolutionary algorithms, for test problems. We completed initial development of our graduated evolution algorithms and started model development for a second test problem—collection of image data from a subdomain. We are near completion of initial graduated evolution algorithms.

We previously showed that the behavior optimization process is much more efficient when a complex task is broken into smaller subtasks. For example, the initial genetic flight-control algorithms that were developed for this project involve mere thousands of operations and can be described by a “genome” of a few thousand bytes. A simple doubling of the number of tasks that the behavior must deal with, or increase in fidelity, would put the problem out of reach on most compute clusters. We showed that using building-block efficiency is true, even when the various subtasks are independently optimized in parallel by using a “policy tree” that was encapsulated as a root node with a set of pointers to the various behavior graphs. We explored the separate optimization of the different branches of the full behavior graph. These results support our hypothesis that genetic programming of robotic behaviors is best pursued by integrating functional building blocks.

We showed that using building-block efficiency is true, even when the various subtasks are independently optimized in parallel by using a “policy tree” that was encapsulated as a root node with a set of pointers to the various behavior graphs.

38611

Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation

P. D. Hough, M. M. Johnson, A. S. Yoshimura, D. A. Jones, M. L. Martinez-Canales

In recent years, optimization has become an increasingly valuable tool for solving a wide range of problems in areas such as stockpile stewardship, aerospace engineering, computational chemistry, environmental management, manufacturing, health care, and transportation. In most of these applications, it is assumed that all information needed to formulate and solve the optimization problem of interest is known and that the final solution is not only optimal, but also reliable in some sense. As a result, these problems are formulated and solved as deterministic problems.

With the continued growth in the use of computer modeling and simulation, treating the related optimization problems in a deterministic fashion has become inadequate. This is a direct result of the uncertainty that arises in the models that are used. In this situation, the question of how reliable the results of the simulation are becomes important. The response to these questions has been a growing effort to understand, quantify, and take into account the various uncertainties that arise in the computational models. To continue to be effective, optimization algorithms must follow suit.

Sandia's goals in this project are to develop robust and scalable optimization algorithms that will effectively solve mission-critical optimization problems in which uncertainty arises and to incorporate them into software tools that will enable analysts to make use of them. We will base these algorithms on stochastic programming, which encompasses both the evaluation of functions defined by deterministic models with well-characterized sources of uncertainty and the evaluation of functions defined by stochastic models. The work will be demonstrated on an enterprise modeling application known as Weapons of Mass Destruction, Decision Analysis Center (WMDDAC).

To realize the goals of the project, we completed three primary tasks. First, we developed an optimization algorithm in which deterministic decision points were replaced by probabilistic decisions to account for variabilities in a stochastic simulation. We then completed a batch version of the WMDDAC enterprise simulation framework. Finally, we

Sandia's goals in this project are to develop robust and scalable optimization algorithms that will effectively solve mission-critical optimization problems in which uncertainty arises and to incorporate them into software tools that will enable analysts to make use of them.

implemented a JAVA™ wrapper that enables integration of the C++ optimization library with the JAVA™ WMDDAC application.

We developed an optimization algorithm that makes use of frequentist statistical principles to make decisions. This includes the introduction of statistics-based decision metrics for choosing trial iterates, determining the acceptability of an iterate, and deciding if the optimization algorithm has converged. The statistics for these decisions are gathered by sampling the function space at appropriate points in the algorithm. In particular, we replace traditional search directions with a combination of directions that ensure convergence of the deterministic optimization algorithm and those that constitute a meaningful statistical sample as determined by Monte Carlo–based sampling techniques (e.g., Latin hypercube, orthogonal array, etc.). Decision thresholds are set according to variability in the function and the degree of confidence required or achievable given limited resources.

To implement a batch version of the WMDDAC application, we developed a new component called a BatchJob to represent user behavior. A BatchJob replaces the graphical user interface (GUI) and interacts directly with the simulation by implementing the GUI methods that are expected by the simulation and invoking methods on the simulation that would normally be invoked by the user via the GUI. Runtime behavior is embodied in a set of Rules and Flags. A Rule is an “if-then” statement that represents user logic. The “if” part of the Rule is encoded in a Condition, which defines a specific state that must exist for the Condition to be satisfied. The “then” part of the Rule is implemented as a set of Actions to be performed when the Condition is satisfied. Actions can affect the simulation in every way that a user can affect it during interactive runs through the GUI. To be consistent with the interactive simulation, the Rules are evaluated at the beginning of each simulated day, giving them the opportunity to affect the simulation on a daily basis. Flags represent the user’s persistent memory during the simulation and can be accessed or set by any Conditions or Actions belonging to any Rules in the BatchJob.

We generated the JAVA™ wrapper for the C++ optimization library (OPT++) using SWIG. This automated process has the benefits of minimizing the amount of JAVA™ code required to implement the interface and automating the documentation process. Furthermore, changes in OPT++ are easily incorporated into the JAVA™ wrapper by simply rebuilding the code, and debugging of C++ and JAVA™ code can be done

We generated the JAVA™ wrapper for the C++ optimization library (OPT++) using SWIG. This automated process has the benefits of minimizing the amount of JAVA™ code required to implement the interface and automating the documentation process.

simultaneously. This wrapper enables the integration of the OPT++ code and the WMDDAC code that is required to solve optimization problems associated with the WMDDAC set of enterprise modeling applications. Finally, we defined a path forward for demonstrating this new technology on an application of interest.

Other Communications

Ammerlahn, H. R., P. D. Hough, and A. S. Yoshimura. 2003. Nonlinear Optimization for Stochastic Simulations. Sandia Technical Report SAND2003-8802, Sandia National Laboratories, Albuquerque, New Mexico.

38612

Robust Message Routing for Mobile (Wireless) Ad Hoc Networks

M. M. Johnson, H. R. Ammerlahn, M. E. Goldsby, B. P. Van Leeuwen, A. S. Yoshimura, H. Y. Chen, R. P. Tsang, N. R. Bierbaum, D. Kilman

As nodes in mobile ad hoc networks come to be used as operational units, performing distributed computations under program control, it will be desirable to provide an effective programming model for them. Such mobile nodes communicate over an asynchronous wireless-communication channel, and communication protocols used for mobile ad hoc networks typically provide only best-effort message delivery. Protocols (such as Transmission Control Protocol, or TCP) that provide reliable, in-order delivery in wired networks are unsuitable for ad hoc or other wireless communication. Sandia will implement reliable, ordered message delivery on top of an ad hoc communication protocol. In total, the research and development brings together four complementary efforts coordinated around the common theme of robust messaging in wireless ad hoc networks. Considered in terms of the seven-layer open-system interconnection (OSI) model for network protocols, the four portions of the work address issues in Layers 2, 3, and 4, the Link, Network, and Transport layers, respectively. The first portion provides an analysis of throughput and latency in wireless medium access control (MAC) protocols (Layer 2) and develops guidelines for achieving good ad hoc network performance. The second portion describes enhancements made to existing simulation models of wireless MAC and routing protocols (Layer 3). We used the enhanced models in support of the work described in the third portion, which presents a new transport protocol (Layer 4) superior to TCP for use in wireless ad hoc networks. The third portion also introduces several innovative techniques for improving performance in the route discovery phase of ad hoc routing protocols. The fourth portion presents a novel, highly scalable ad hoc routing protocol based on geographic principles.

This research demonstrates the effects of load on the throughput and latency of *ad hoc* mobile networks. The effects of load are manifested by the increased number of collisions. Each collision necessitates a retransmission. In a heavily loaded network, a node may attempt several retransmissions before achieving a successful transmission. This translates into lower network utilization (due to the capacity wasted by retransmitting the same packet), as well as sharp increases in

Sandia will implement reliable, ordered message delivery on top of an ad hoc communication protocol. In total, the research and development brings together four complementary efforts coordinated around the common theme of robust messaging in wireless ad hoc networks.

network latency. It is difficult to specify an exact network load that will be appropriate for achieving high network utilization and low packet latency. As shown in this study, the performance of an *ad hoc* network is dependent upon many factors, including network topology, packet size, the ratio of interference range to transmission range, and the particular MAC protocol implementation. However, general guidelines for achieving good performance in *ad hoc* networks include the following: (1) the use of larger packet sizes (600 bytes +), (2) the use of a locality-based topology where nodes that communicate more frequently are within each other's transmission range, and (3) the maintenance of network loading of less than 50% between nodes in the same transmission range, and less than 40% between nodes in different transmission ranges. In addition, the simulation created for this project demonstrates the basic viability of the original design approach. The enhancements designed as an extension to the project make the approach significantly more attractive. All elements of the simulation are available for further use by follow-on research. Finally, we developed a novel routing protocol based on geographic principles and using coordinates derived only from the connectivity of the network. It was shown to perform at least as well as geographic routing based on physical coordinates and considerably better in the presence of transmission obstacles. We employed simple means of dealing with the failings of geographic routing, which will work with either virtual or physical coordinates, with three-dimensional physical node layouts, and in the presence of obstacles. The protocol shares the excellent scalability properties of conventional geographic routing protocols.

38613

Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods

M. L. Leininger, I. B. Nielsen

Coupled-cluster theory has enabled the computation of molecular properties with an accuracy often exceeding that of experiment. Despite the tremendous progress in computer architectures, the high-degree polynomial scaling of this method represents the greatest obstacle in the accurate theoretical treatment of mainstream chemical problems. Although it has long been recognized that this super-linear scaling is nonphysical, the development of efficient reduced-scaling algorithms to massively parallel (MP) computers has not been realized. Sandia plans to address this high-scaling cost of the coupled-cluster method by implementing locally correlated linear-scaling algorithms in a way that will enable the iterative solution of the nonlinear coupled-cluster equations involving several billion unknowns, and scaling to thousands or millions of processors. Fault tolerance will be essential in allowing these distributed-memory applications to run on the next-generation machines, such as the Sandia Red Storm computer. We will implement the code in a modular fashion, developing general components for the distribution of large datasets across memory and disk, the solution of nonlinear equations, and the handling of faults in distributed-memory applications. We will make these components available to other Sandia projects. Programmatically, this work will benefit those modeling the molecular structures and the chemical reactions of central importance to Sandia programs in materials modeling and biochemistry. The ability to accurately describe large chemical systems is critical in validating models used in Sandia's materials-aging efforts and in providing accurate scoring functions for evaluating protein ligand-binding affinities.

We addressed the following points:

- Selection of the approach for obtaining linear scaling
- Implementation of the chosen linear-scaling correlation model
- Study of performance relative to the conventional correlation model
- Parallel implementation and performance analysis
- Fault-tolerance strategies.

Sandia plans to address this high-scaling cost of the coupled-cluster method by implementing locally correlated linear-scaling algorithms in a way that will enable the iterative solution of the nonlinear coupled-cluster equations involving several billion unknowns, and scaling to thousands or millions of processors.

These points constitute all the steps required for development and implementation of a parallel fault-tolerant algorithm for linear-scaling coupled-cluster electronic structure computations, which is the ultimate goal of the project. We are well under way to reaching this goal.

After analyzing two different linear-scaling correlation models, we selected the local correlation model as the basis for our project. To study the scaling behavior of the model, we implemented a program to perform local second-order Möller-Plesset perturbation theory (MP2) computations. We obtained significantly reduced scaling and demonstrated the excellent performance of the algorithm by locating crossover points for the linear method versus a canonical algorithm.

We parallelized the local correlation program using a parallelization strategy that prevents communication bottlenecks and allows a coarse-grained parallelism. We demonstrated the efficiency of the parallel program by measuring the speedup for a series of runs on a distributed-memory machine using message-passing interface (MPI).

The implementation of the MP2 program included finalizing the sparse data representation required to fully exploit the advantages of the local correlation model as well as final tuning of the contraction routines used in the major computational steps.

We have worked out strategies for implementing fault tolerance. Whereas fault handling is relatively straightforward in the part of the code that employs replicated data arrays, a more sophisticated fault-handling scheme involving partial replication of data had to be devised for the part of the code that employs distributed data.

We obtained significantly reduced scaling and demonstrated the excellent performance of the algorithm by locating crossover points for the linear method versus a canonical algorithm.

38614

Micromagnetic Suspension

L. A. Romero, A. A. Giunta, W. E. Hart

Friction and surface-related issues are obstacles to realizing reliable micromechanical devices. The difficulty arises since classical bearings scale poorly as one decreases the size of the system. In this project, Sandia seeks two novel types of magnetic levitation that employ arrays of permanent magnets. It is known that it is impossible to have stable levitation in a static magnetic field if the levitating body is not spinning. In one of our configurations, we achieved stable levitation with a passive (no feedback) alternating magnetic field. In the other configuration, we achieved stability by spinning the rotor.

The first of these concepts has been demonstrated in electromagnetic traps for ions. However, no one has ever attempted to use similar principles to levitate objects larger than ions. The second form of levitation was demonstrated in the science toy the Levitron. Once one develops the theory for doing either of these forms of levitation, it is in principle simple to find configurations of magnets that will give stable levitation. However, these configurations can be highly sensitive to imperfections in the alignment of the system.

We plan to use robust optimization techniques to find configurations of magnets that yield stable levitation when they are perfectly aligned, and that can also tolerate imperfections in the alignment of the system. This involves finding ways of analytically characterizing the robustness of a given configuration and using optimization techniques to optimize this robustness.

We plan to implement the designs we produce. The successful development of this technology will permit the design of high-speed, rotating, micromechanical devices.

The following is a summary of our main accomplishments.

(1) We are building a specific design of an alternating magnetic-field Levitron. We arrived at this design by optimizing an objective function that measured the robustness of a given configuration. We believe that the new design is more than an order of magnitude more robust than our first attempts at such a design.

(2) We improved our objective function for evaluating the robustness of a horizontally spinning Levitron.

(3) We began analyzing the effect of friction on the stability of these systems. This is a very subtle issue since friction has

It is known that it is impossible to have stable levitation in a static magnetic field if the levitating body is not spinning. In one of our configurations, we achieved stable levitation with a passive (no feedback) alternating magnetic field.

been found to not always be a stabilizing effect on these systems.

(4) We developed constrained global optimizers in the COLIN library and developed a preliminary interface between the COLIN and the DAKOTA (Design Analysis Kit for Optimization and Terascale Analysis) toolkit.

(5) We published and presented an extended abstract, “An Introduction to the COLIN Optimization Interface,” at the Workshop on Memetic Algorithms.

We licensed Coliny and COLIN.

Refereed

Hart, W. E. 2003. An introduction to the COLIN optimization interface. *Proc. Genetic Evolutionary Computation Conference (GECCO)* (Chicago, Illinois): 216–21.

Romero, L. A. 2003. Passive levitation in alternating magnetic fields. *SIAM J. Applied Mathematics*, accepted.

Romero, L. A. 2003. Spin-stabilized magnetic levitation of horizontal rotors. *SIAM J. Applied Mathematics*, accepted.

38615

Sensitivities for Large-Scale Simulation Codes

B. G. Van Bloemen Waanders, T. M. Smith, E. R. Keiter, R. A. Bartlett, C. C. Ober

Key innovations in the area of compressible fluid flow, electrical simulation, and abstract linear algebra interfaces have impacted not only PREMO and XYCE™, but also the general simulation community. Adjoint and direct sensitivity capabilities in XYCE™ provided an efficient solution technique for a doping profile study for a circuit exposed to radiation. Sandia's development of a powerful shape optimization capability resulted in numerically superior methods for PREMO's forward solution algorithms. In preparation for SIERRA and Nevada integration, we developed general linear algebra interfaces based on performance, development, and functionality criteria. We strongly leveraged our internal and external collaborations this year to achieve our milestones and, as a result, have substantially grown our research partnerships. In parallel to the direct and adjoint integration efforts, we developed multiple prototyping codes in an attempt to accomplish algorithmic research goals. A considerable amount of complex work remains to achieve the ultimate goal of this project, to apply internal sensitivities to large transient optimization problems. Building on a large foundation of research and development accomplishments, however, we are positioned to effectively use direct and adjoint sensitivities in a variety of applications, in particular, large-scale shape optimization and parameter estimation.

We made significant progress toward providing sensitivity capabilities to electrical-circuit (XYCE™) and compressible fluid-flow simulation (PREMO). Additionally, we addressed the problem of interfaces for intrusive sensitivities. Our goal is to add sensitivity capabilities into codes for use in large-scale optimization problems. Parameter estimation problems have dominated our efforts with XYCE™. Technical issues related to non-smoothness have been addressed through the use of analytic functions, but this work must be extended to more devices by looking at smooth formulations with automatic differentiation. We will investigate time-integration methods that will automatically calculate transient sensitivities by leveraging time-integration development. DAKOTA (Design Analysis Kit for Optimization and Terascale Applications) has been interfaced to provide optimization and uncertainty

Sandia's development of a powerful shape optimization capability resulted in numerically superior methods for PREMO's forward solution algorithms.

quantification services. Intrusive methods (MOOCHO) will be interfaced using linear algebra abstractions and adjoint sensitivities to provide efficient optimization capabilities.

Shape optimization of a weapon system is the goal for PREMO. This is perhaps one of the more difficult optimization problems because reduced gradient evaluations require the computation of mesh movement and sensitivities for changes in the shape. Solution approaches make use of finite-volume discretizations with explicit or implicit methods. The SIERRA discretization method and the initially planned matrix-free method do not support adjoint sensitivities. We implemented exact sensitivities using automatic differentiation (AD) for first- and second-order methods. Numerical experiments showed that when the first-order AD Jacobian is used as a preconditioner for an implicit method, the solver performs significantly better than any other solution method currently implemented.

Adding sensitivities for optimization to a production code is a time-consuming task and requires knowledge of the internal linear algebra. This has led to development of general interfaces that will significantly improve the implementation not only for XYCE™ and PREMO, but potentially for many other simulation codes, as well.

Adding sensitivities for optimization to a production code is a time-consuming task and requires knowledge of the internal linear algebra. This has led to development of general interfaces that will significantly improve the implementation not only for XYCE™ and PREMO, but potentially for many other simulation codes, as well.

Refereed

Bartlett, R. A. 2003. MOOCHO and object-oriented interface and interface for algorithms for PDE-constrained nonlinear programming. Paper presented at IMA, January, Minneapolis, Minnesota.

Bartlett, R. A., and B. G. Van Bloemen Waanders. 2003. Vector reduction/transformation operators. *ACM Transaction on Mathematical Software* **V**:1–25.

Bartlett, R. A., M. A. Heroux, and K. R. Long. 2003. TSFCORE. Sandia Technical Report SAND2003-1378, Sandia National Laboratories, Albuquerque, New Mexico.

Bartlett, R. A., M. Berggren, and B. G. Van Bloemen Waanders. 2003. Derivative calculation for Euler-Roe dissipation scheme. Paper presented at the Computational Mechanics Conference, July, Albuquerque, New Mexico.

52540

IP Storage: A Performance and Security Study

H. Y. Chen, I. D. Cohen, J. A. Vanrandwyk

High-performance, networked file/storage is needed to solve input/output (I/O) bottlenecks in large computing platforms. Frequently, parallel techniques such as Parallel File Transfer Protocol (PFTP) are employed to achieve reasonable aggregate throughput. These techniques suffer end-host bottleneck due to protocol processing and memory copies in moving data. Moreover, these techniques lack failover mechanisms to survive network glitches.

The emerging Internet Protocol (IP)–based storage places message/file and storage I/O onto an Ethernet/IP network, offering block I/O performance to remote clients. It achieves high performance by offloading Transmission Control Protocol (TCP)/IP and data movement in hardware. Sandia’s preliminary tests demonstrated line-rate throughput with direct disk I/Os. IP–based storage has the potential to resolve the I/O technical issues mentioned previously.

We plan to integrate failover and parallel techniques already deployed in storage subsystems with those adopted in IP networks. Performance metrics include end-to-end failover and load balance. We will study the effects of propagation delay on I/O usage models in high-performance computing and will explore optimization techniques to mitigate its adverse effect.

We also plan to evaluate applications of IP storage in parallel and cluster computing systems, such as Red Storm and Computational Plant (CPlant). Cluster file systems combine the common-name space for data sharing with block I/O, which may alleviate the bottleneck of network file system (NFS) servers. Quality of service provided in IP networks enables the multiplexing of storage and message data onto a single network, offering a cost-effective way to implement large-scale cluster and parallel file systems.

IP storage exposes mission-critical data to external threats, requiring the convergence of IP Security Protocol (IPsec) with storage and file-level protection to ensure authenticated users with authorized access to stored data. To satisfy storage-performance requirements, line-speed encryption is needed for data integrity and privacy. We will promote and partner with industry to implement application-specific integrated circuit (ASIC)–based filtering and IP-level encryption.

We conducted the following background study to prepare for our research: (1) profiled traffic characteristics of scientific

Sandia’s preliminary tests demonstrated line-rate throughput with direct disk I/Os. IP–based storage has the potential to resolve the I/O technical issues mentioned previously.

computing applications, (2) completed Internet Small Computer System Interface (iSCSI) training to gain knowledge of the iSCSI transport mechanism, (3) participated in technical conferences to learn the security mechanisms specified in the iSCSI architecture, and (4) attended RedHat Kernel and Driver classes to understand the Linux system's role in process management, memory management, file system, and storage-device control.

We researched and selected benchmark, system, and network-monitoring tools from the public domain to conduct our experiments. We also developed a versatile test integration and control program. This program provides a platform for integration of test definition, execution, and organization of results and information to ensure accurate and meaningful analyses. We wrote the program in a general manner to support other testing projects, and we will release it later for general Sandia use.

We partnered with Adaptec, Cisco, SysKonnnect, and Network Appliance to prototype a small-scale iSCSI test-bed. The Adaptec host bus adapter implements iSCSI in firmware, along with its TCP/IP offload engine. Cisco and SysKonnnect together provide a software iSCSI solution that we use to contrast the performance of the Adaptec implementation. The NetApp storage subsystem exports its volume manager through a software-based iSCSI interface and its kernel TCP/IP stack.

We baselined the performance of iSCSI using the "testrun" program described above. Our preliminary results indicate the following:

(1) A single iSCSI session can saturate the gigabit (Gb) Ethernet capacity.

(2) The performance of Software iSCSI requires the Jumbo Frame support to achieve link-rate throughput and generated 1.5 GHz of CPU (central processing unit) load at the client computer.

(3) The software-based iSCSI on the storage server cannot sustain the performance for more than one Gb Ethernet interface. The software-based iSCSI has additional tasks such as buffer management and disk I/O to optimize and handle. Thus, it is critical for the storage server to implement hardware-based iSCSI.

(4) The hardware-based iSCSI exhibited lower percent CPU load per megabyte of data transferred per second.

Our preliminary study showed that iSCSI can deliver Fibre Channel (FC)-like performance and, by leveraging on the ubiquitous deployment of IP and Gb Ethernet, the cost-performance ratio of iSCSI is better than FC. For wide-area

applications, however, iSCSI would require multiple TCP connections to map striped remote disks in a single iSCSI session to offset the slow-recovery problem caused by TCP's congestion-avoidance algorithm. In addition, all iSCSI implementations need to expose tuning parameters such as SCSI command window size, maximum SCSI data burst, and segment length, etc., to fill high-bandwidth and long-delay pipes such as the ASCI DISCOM (distance computing).

52541

A Parallel Circuit Simulator for Cell Biology

R. L. Schiek, E. E. May, S. A. Hutchinson

The next revolution in biology, building on the deluge of available genomics and proteomics data, will be based on understanding the genetic and metabolic signaling pathways that define how a cell and ultimately an organism works. Recent work shows that the mechanisms of gene expression and the interdependence of signaling pathways in the cell can be modeled as complex electrical circuits. Cells are akin to signal processors that receive inputs (deoxyribonucleic acid [DNA] sequences or genes), process information (transcription, for example), and produce outputs (proteins).

Sandia is extending the XYCE™ circuit simulation program to create a large-scale, parallel, biocircuit simulator. This will require the development of individual circuit elements representing molecular machines and also an accurate description of the coupling between elements. Synthesis will continue up the functional hierarchy to the construction of single cells and the simulation of cell cultures. Initially, we will use the tool to model cell-level responses to environmental stresses. Ultimately, we will use XYCE™'s parallel capabilities to simulate a full cell culture.

Though computationally and biologically challenging to create, such a tool will be an aid in the fundamental understanding of cellular biology and eventually lead to models of microbial and cellular processes of interest to the Department of Energy, such as for waste remediation and energy production.

Our goals centered on developing the theoretical framework in which a biological circuit simulator would operate. Primary goals included defining primitive circuit analogs and mechanisms for signal propagation and stability assessment. Additionally, this project must demonstrate that the primitive circuit analogs can mimic biological or chemical control systems and select model target systems.

Regarding primitive circuit components and signal propagation, we defined circuit analogs representing biochemical signal sources and the transmission of such signals for both intra- and extracellular reactions. To achieve this goal, we derived a theoretical framework relating traditional biochemical quantities such as concentration and chemical-species type to an electrical circuit's typical quantities of charge, voltage, and current flow. Such a framework allows one

Sandia is extending the XYCE™ circuit simulation program to create a large-scale, parallel, biocircuit simulator...Ultimately, we will use XYCE™'s parallel capabilities to simulate a full cell culture.

to translate biological and chemical events like species production, diffusion, and reaction directly into circuit systems that a circuit simulator can model.

An unanticipated benefit of the developed biochemical-to-electrical-circuit framework is that different electrical circuit types (logical, digital, and analog) are most applicable to different biochemical systems, depending on the type of biochemical data known. Specifically, if only genetic-expression patterns are known, then a logical circuit can be constructed. If one knows stoichiometry, then a digital circuit will suffice; with kinetic data an analog circuit is the best model.

We selected model problems in the complex chemical-switching example of the Belousov-Zhabotinskii reactions and the biochemical regulation example of tryptophan expression in *E. coli*. We chose such systems because the quantity of existing data behind them aids in model verification. Success with these first systems is critical to modeling full cells and cell cultures.

Refereed

Schiek, R. L., and E. E. May. 2003. Development of a massively parallel, biological circuit simulator. *Proc. IEEE Computer Society: Computational Systems Bioinformatics (CSB2003)* (11–14 August, Stanford, California): 620–22.

52542

Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions

J. P. Castro, M. A. Gonzales, P. D. Hough, A. A. Giunta, P. N. Demmie

With the advent of massively parallel (MP) computers, computational speed has increased tremendously. Unfortunately, the scaling of computational models seems to always exceed compute times. This problem escalates when solving an optimization problem that requires many of these computationally intensive jobs to complete. Therefore, Sandia proposes a dynamic algorithmic approach to make the optimization calculation more computationally efficient for a wide range of applications, including earth-penetrator analysis, thermal analysis, and electrical-device modeling.

The goals of this project are to develop dynamic and computational time-saving optimization algorithms by taking advantage of interactions between multifidelity models. If a system has models of different fidelities, the low-fidelity, computationally cheaper model is used in a global manner to guide the finding of the optimum of the high-fidelity model (HFM), thus reducing the design space of the problem. Within the reduced design space, a set of rules or guidelines determines the best optimization procedure for the higher-fidelity model, overall reducing the total computational time. This may be taken a step further by developing algorithms with feedback mechanisms so that the processes of determining the optimization scheme and model fidelity are done dynamically, i.e., dynamic multifidelity-multilevel hybrid optimization.

Sandia is addressing three major technical challenges in this project. First, we must develop algorithms and their corresponding feedback mechanisms for the dynamic multifidelity-multilevel hybrid optimization scheme. Second, we must integrate the newly developed schemes into a software environment (ENTERO) that extends the DAKOTA (Design Analysis Kit for Optimization and Terascale Applications) optimization software toolkit's current capabilities with multilevel hybrid and multifidelity optimization into a more dynamic approach. Finally, if deemed feasible, we must develop a convergence proof for dynamic multifidelity-multilevel hybrid optimization. The primary goals for this year's project were to integrate DAKOTA within ENTERO, to develop optimization benchmark calculations and metrics with earth-penetrator models, and to develop a limited dynamic optimization scheme for N-fidelity level of models and a fixed optimization strategy.

...Sandia proposes a dynamic algorithmic approach to make the optimization calculation more computationally efficient for a wide range of applications, including earth-penetrator analysis, thermal analysis, and electrical-device modeling.

To ultimately develop the software and algorithms that implement a dynamic multifidelity-multilevel hybrid optimization scheme, we are taking an iterative approach throughout the life of this project.

We completed the initial integration of DAKOTA within ENTERO, resulting in the ENTERO/DAKOTA environment. The completion of this goal encompassed completion of the following tasks:

- Implemented within the ENTERO environment a DAKOTA application module. This module holds data that are unique to DAKOTA, e.g., type-of-optimization algorithms. The data associated with a particular optimization strategy are added to the DAKOTA module automatically by the software, depending on the type of optimization strategy chosen by the user.
- Implemented within the ENTERO environment a DAKOTA input-file parser for an input deck capable of producing input files for multifidelity and multilevel optimization runs of interest. In particular, parameter studies and surrogate-based optimization (SBO) studies may be generated.
- Implemented a driver to execute the DAKOTA optimization process within the ENTERO environment via Extensible Markup Language (XML) workflows for grid services. This provides a means to launch and manage data remotely through grid services.
- Implemented an initial iteration of the DAKOTA toolkit's method of external coupling to simulation codes during the optimization process and captured this within the ENTERO environment. This was captured within the software through a workflow manager specifically for DAKOTA.

We completed the development of optimization benchmark calculations and metrics with earth-penetrator models. The completion of this goal encompassed the completion of the following tasks:

- Gathered a set of PRONTO earth-penetrator models of differing fidelities (elastic and rigid). We developed an optimization problem that was simple enough to run quickly but that had a nontrivial solution. The crux of the problem is to minimize the mass by varying the density subject to the constraints:
 - penetration depth > 60 in.
 - acceleration in the core $< 10,000 \text{ g} = 3.217 \times 10^5 \text{ ft/s}^2$
- Computed benchmark calculations for the earth-penetrator models using the DAKOTA toolkit's provably

convergent methods. We chose the DAKOTA optimization strategy SBO, i.e., two-level multifidelity optimization. To provide a metric of computational speed and accuracy, we evaluated three optimization strategies at various starting points to acquire a more complete metric:

- SBO: low-fidelity model (LFM) = rigid-body case, high-fidelity model (HFM) = elastic-body case
- SBO: LFM = curve-fit elastic-body case, HFM = elastic-body case
- Gradient method: elastic-body case
- Developed software within the ENTERO /DAKOTA environment to execute DAKOTA SBO calculations.

Creation of a limited dynamic optimization scheme for N-fidelity level of models and a fixed optimization strategy is currently under development. The scheme will entail using the LFM to sample design space in conjunction with the HFM evaluating the optimum. The LFM will give asynchronous updates to the HFM on the probable location of the optimum as the LFM samples the design space in real time. Crucial to this scheme is the correct mapping of the design variables between the HFM and the LFM. We believe that we have the mechanisms to implement this scheme and will integrate and implement this strategy in upcoming work.

Refereed

Castro, J. P., A. A. Giunta, P. N. Demmie, M. A. Gonzales, and P. D. Hough. 2003. Developing a computationally efficient dynamic multilevel hybrid optimization scheme using multifidelity model interactions. Paper presented at USACM—7th U.S. National Congress on Computational Mechanics, 27 July, Albuquerque, New Mexico.

52543

Robust Large-Scale Parallel Nonlinear Solvers for Simulations

T. G. Kolda, R. P. Pawlowski

Sandia has a wide range of highly nonlinear-phenomena models that critically depend on robust nonlinear solvers. For example, the radiation-hardened Pentium-processor simulation involves over 70,000 devices, and current solution methods are not robust because convergence depends on correctly setting parameters that are extremely problem-dependent. Similar robustness issues occur in reacting-flow simulations for the design of chemical vapor deposition (CVD) reactors. Future goals such as predicting the dispersion of toxic chemicals in water systems or buildings and modeling weapon electrical systems in hostile environments will be even more difficult and require advances in solver technology.

Our goal is to develop novel nonlinear-solution methods that are both more robust and more efficient than Newton's method. We propose research on two complementary approaches to address this problem: the limited-memory Broyden's method and the Tensor method. Both methods focus on using an entirely different model rather than improving Newton's method directly. Broyden's method replaces the Jacobian with an approximation. Tensor methods are based on a higher-order model and have been shown to overcome problems with singularity in the Jacobian.

Our preliminary results show promise for these methods, which will allow us to perform simulations critical to Sandia's mission. To make these codes accessible to many codes at Sandia, we will implement these methods in NOX, a nonlinear-solver library that is part of the TRILINOS framework.

We focused on implementing and testing prototypes of two new nonlinear-solver methods. The goal was to test the performance of the prototypes on a set of Sandia simulations to identify any bottlenecks or implementation and efficiency issues. We implemented prototype versions of both the Broyden and Tensor methods in the NOX nonlinear-solver framework. The Broyden implementation has already evolved into a scalable, parallel implementation.

We tested and improved these methods considerably. Specifically, we developed an effective initialization strategy for Broyden's method. To the best of our knowledge, this is a novel idea with respect to limited-memory implementations.

...we developed an effective initialization strategy for Broyden's method. To the best of our knowledge, this is a novel idea with respect to limited-memory implementations.

We also developed a new method for solving the quadratic subproblem in the Tensor method.

Our preliminary numerical results illustrate promise for these methods. For transient codes, Broyden's method is faster and, in some cases, even more robust. This will positively impact many application areas at Sandia, including compressible flows (PREMO), reacting flows (MPSalsa), solid mechanics (Adagio/SALINAS), and electrical-circuit simulation (XYCE™). Our initial results with the Tensor method show that it can solve problems where Newton's method fails; these problems are characterized by near-singular Jacobians. This is important for design simulations that model conditions near catastrophic events (bifurcations) such as ignition or detonation.

Our initial results with the Tensor method show that it can solve problems where Newton's method fails; these problems are characterized by near-singular Jacobians. This is important for design simulations that model conditions near catastrophic events (bifurcations) such as ignition or detonation.

52544

Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security

B. G. Van Bloemen Waanders, W. E. Hart, C. A. Phillips, R. L. Bilisoly, S. A. McKenna, V. C. Tidwell, D. M. Rogers

Water-distribution networks are highly vulnerable to chemical and biological (C/B) terrorist attacks. Numerous cases are cited where harmful substances appeared in water-distribution systems and went unnoticed until, unfortunately, a high number of illnesses were reported in medical facilities. To help prevent these types of catastrophes, physical security of key water-network facilities is being considered; however, other obvious access points such as fire hydrants and even household taps remain unprotected. Sandia's intent in this project is to develop methods to help characterize the behavior of terrorist attacks on large water-distribution networks and provide methods that can help locate the source of the contaminant and control the spread of the harmful agents.

Alternative approaches to security therefore need to be considered, and one of the more-promising approaches consists of interfacing real-time warning systems to an array of sensors distributed throughout a network. A considerable amount of research is being devoted to sensor technology, and our assumption is that sometime in the near future, sensors will be able to detect most potentially harmful C/B agents in water. If this is a valid assumption, optimization algorithms interfaced to a numerical simulator can predict the location of the terrorist attack and also help mitigate the spread of the agents. To accurately and efficiently predict the original location of an attack, we are using source inversion by mathematically resolving the differences between observed and predicted observations. This optimization technique relies on a numerical simulator that accurately characterizes the behavior of fluid flow and chemical transport. Although this is one of the key challenges of the project, other critical technical issues need to be resolved, such as where to place sensors, how to quantify uncertainties associated with a number of network parameters, what the threats are, and how to assess/prioritize risk.

We made significant progress in understanding the C/B threats faced by water-distribution systems, successfully interfaced the Sandia inversion, optimization, and uncertainty

Sandia's intent in this project is to develop methods to help characterize the behavior of terrorist attacks on large water-distribution networks and provide methods that can help locate the source of the contaminant and control the spread of the harmful agents.

program DAKOTA (Design Analysis Kit for Optimization and Terascale Applications) with the industry-standard hydraulic model EPANET, developed a new Poisson-process water-demand-function generator, conducted one of a very limited number of tracer tests in water-distribution systems to assist in evaluating the model behavior, interacted with the Environmental Protection Agency's National Homeland Security Research Center, and interacted with water utilities to gain access to their datasets of distribution-system hydraulic characteristics.

We initiated development of a framework approach that will allow us to integrate our modeling tools into the risk-assessment methodology for water (RAM-W) that has been widely used in the potable water industry for conducting vulnerability assessments. We began development of a Markov latent-effects model to evaluate the contribution of various threat attributes on the *probability of attack* term used in the risk assessments. We developed a first-order ability to calculate the fate and transport of potential C/B agents in a 5000-node skeleton distribution-system network for a city of about 750,000. This demonstrates the temporal and spatial spread of contaminants within the system. We initiated a denial-of-service approach that will allow us to numerically calculate which nodes represent the most critical to physical attacks. We developed an initial sensor-placement optimization model and demonstrated it in a subset of a network. The results demonstrate the number of sensors needed to reduce the percentage of the population affected by a contamination event. We successfully demonstrated a first-order source-inversion location identification for the Sandia distribution-system network.

We initiated development of a framework approach that will allow us to integrate our modeling tools into the risk-assessment methodology for water (RAM-W) that has been widely used in the potable water industry for conducting vulnerability assessments.

Other Communications

Berry, J., L. Fleisher, W. E. Hart, and C. A. Phillips. 2003. Sensor placement in municipal water networks. Paper presented at the Environment and Water Resources Institute, June, Philadelphia, Pennsylvania.

McKenna, S. A., S. Buchberger, and V. C. Tidwell. 2003. Examining the effects of variability in short time-scale demands on solute transport. Paper presented at the Environment and Water Resources Institute, June, Philadelphia, Pennsylvania.

Van Bloemen Waanders, B. G., R. Bartlett, L. Biegler, and C. Laird. 2003. Nonlinear programming strategies for source detection of municipal water networks. Paper presented at the Environment and Water Resources Institute, June, Philadelphia, Pennsylvania.

52546

Massively Parallel Linear Programming

C. A. Phillips, B. A. Hendrickson, V. E. Howle, E. G. Boman, O. D. Parekh, M. A. Heroux

Sandia will develop a massively parallel linear-programming (LP) solver. LP is the optimization of a linear objective function subject to linear constraints. Companies and universities have expended huge efforts over decades to produce fast, stable, serial LP solvers. Current parallel codes run on shared-memory systems and have little or no distribution of the constraint matrix. We have seen no reports of runs beyond 16 processors, except for special classes of problems.

LPs of enormous scale arise in mitigation planning for homeland defense. Simulations of population interactions performed for the National Infrastructure Simulation and Analysis Center (NISAC) can produce graphs with 10 billion edges. Efficiently partitioning such graphs models effective use of limited law enforcement personnel to enforce quarantines or use of limited vaccines to contain epidemics. LPs can compute optimal strategies to attack supervisory control and data-acquisition (SCADA) networks in a new analysis system based on hidden Markov models. SCADA networks control critical U.S. infrastructures such as the power grid and natural-gas distribution. Some Sandia LP logistics applications require parallelization for speed.

A scalable LP solver will benefit the PICO integer-programming (IP) solver. IPs are LPs with additional integrality constraints. IPs can solve resource-allocation, network-security, and decision-support problems, e.g., sensor placement in networks. Serial LP solvers limit initial speedup, especially for problems with difficult, large formulations.

We will base our scalable LP code on an efficient serial implementation of Mehrotra's interior-point predictor-corrector algorithm. The computational core of this algorithm is the assembly and solution of a sparse linear system. Significant research will be required to determine effective techniques for data distribution, assembly of the linear system, and handling of small pivots in the Cholesky factorization (essential for robustness of the interior-point method) that scale to thousands of processors. We will also consider preconditioned iterative methods.

Our first task was to select a large-scale LP application, the LP formulation, and data characterization. This was to be a large-scale graph application with relevance to homeland (in

Sandia will develop a massively parallel linear-programming (LP) solver....We will base our scalable LP code on an efficient serial implementation of Mehrotra's interior-point predictor-corrector algorithm.

particular, infrastructure) security. We identified four such applications and have moderate-scale test examples for two. The first application is sensor placement for municipal water systems, provided by another project. The second application is sensor placement in roadways to detect nuclear materials. The third application is mitigation planning for biowarfare. Our fourth application is the computation of strategies to attack SCADA networks. This is an LP (not an IP) in a new analysis system based on hidden Markov models developed elsewhere at Sandia.

Our second task is an initial parallel interior-point code using the most scalable direct Cholesky solver. We integrated the Parallel Watson Sparse Matrix Package (PWSMP) solver into pPCx, using the pPCx native interface. We also modified pPCx to use a standard TRILINOS interface. This gives us access to iterative solvers and will give us access to the Cholesky solvers recently added to TRILINOS. In particular, we added DSCPack to TRILINOS, working with the package author.

The third task is to modify the PICO LP interface to allow parallel solvers for bounding while solving IP problems. We modified the core of PICO and the IP solver to include a new “ramp up” procedure to be used early in a branch-and-bound computation when there is not sufficient subproblem parallelism to keep a large number of processors busy. For example, at the root of the search tree, there is only one problem. In this setting, it is best to exploit parallelism in the branch-and-bound steps themselves (parallel bounding, usually an LP solve, parallel branching such as cut generation and gradient calculation, parallel incumbent search, etc.). A parallel LP solver naturally fits into this new ramp up, certainly for the root solve, and possibly even for early subproblems if a significant number of cuts (additional constraints) are added.

59916

A Method of Evaluating Research Using New Innovation, Risk, and Impact Indicators

K. W. Boyack, A. Backer

In this age of modern information availability, organizations are searching for ways to capture tacit knowledge and use that knowledge to evaluate and select between new ideas. We are continually falling behind in our retention of knowledge due to the rapidity with which new information becomes available, and from a lack of good tools to help us retain what we have learned. Sandia seeks a method of evaluating research ideas by creating new indicators that, in essence, provide a numerical history of accumulated knowledge. These will be topic- or research community-based innovation, risk, and impact indicators that can give the researcher, administrator, or evaluator a means to quickly evaluate an idea within the context of the history of similar ideas. These indicators will also facilitate focused access to pertinent literature for those with a desire to gain more detailed knowledge and thereby improve their ideas.

We will tailor the indicators and evaluation system to the needs of staff at Sandia, through creation of a specific ontology and by integrating the system with other efforts under way in Integrated Information Services (IIS). We will calculate indicators to match the Sandia ontology, but will also include the hottest non-Sandia research topics from a large body of publication data. Success in this project will have multiple impacts. On a theoretical level, it will provide data to test and evaluate theories of scientific progress and innovation. On a more applied level, this system will have great benefit to this research, enabling investment teams to quickly evaluate ideas in the context of global publishing. In a similar way, this system will benefit Sandia's nuclear weapons programs by providing indicators within a global context.

One of the original metrics was to generate an unclassified Sandia-specific ontology based on our publication record. Although the ontology is not complete, this work has commenced. We retrieved all Sandia publications back to 1996 from the Science Citations Indexes, INSPEC, and the Engineering Index. We eliminated duplicate records (those found in multiple databases) and generated a list of topics from the Sandia publication record.

Another of the original metrics was to use focused datasets to investigate means of quantifying innovation and application

Sandia seeks a method of evaluating research ideas by creating new indicators that, in essence, provide a numerical history of accumulated knowledge....On a more applied level, this system will have great benefit to this research, enabling investment teams to quickly evaluate ideas in the context of global publishing.

phases of publication. Use of power laws over time shows promise as an indicator of phase in that a few seminal publications typically define the start of a new research field or question. According to one model of research progress, these seminal publications are highly started early on, but less so as one progresses through the innovation and application phases, thus changing the distribution of references from a cluster of publications.

We did a great deal of work with one very focused dataset from the Science Citation Index—that of 20 years of publication data from the *Proceedings of the National Academy of Sciences* (PNAS) journal. One key finding was that the calculation of research communities (defined by clusters of papers) is highly dependent on the distribution of references. The PNAS data were driven by the revolution involving sequencing, cloning, etc., which is defined by a few extremely highly cited references. The effect of these few references was to reduce the number and increase the size of the apparent research communities. Excluding these references from the calculation gives research communities of a size and scale that are more consistent with common research practices. This work resulted in an invited talk at a National Academy of Sciences-sponsored colloquium on “Mapping Knowledge Domains” and an accompanying paper submitted to PNAS. A second paper is also in preparation.

We also examined power-law characteristics of these research communities over time to explore their usefulness as indicators of scientific progress. This work is ongoing.

Another of the original metrics was to look at citation distributions over time as a potential indicator. While citation distributions have been much studied over the years, we investigated ranking distributions as a part of our work with the PNAS data and found that they are very good for comparing recent work to old work, thus alleviating the need to wait many years for citation data to collect before evaluating publications.

We established relationships over the past few months with experts in the fields of social-network analysis, science and technology indicators, and text mining that have brought us into contact with ideas and algorithms that will enhance the outcomes of this work. In particular, we entered into collaboration with Dick Klavans, who has significant experience with large firms in the area of scientific progress and competitive intelligence, using literature databases to show clients where potential disruptive technologies are likely to come from. Work with Mr. Klavans will help us to meet our

goals and produce a working system based on analysis of the scientific literature.

Refereed

Boyack, K. W. 2003. Mapping knowledge domains: Characterizing the proceedings of the National Academy of Sciences. *Proc. National Academy of Sciences, Arthur M. Sackler Colloquium on Mapping Knowledge Domains* (9–11 May, Irvine, California).

Electronics and Photonics

The Electronics and Photonics investment area explores innovative solutions to national problems that build on Sandia's existing strengths. Developing microsystems that sense, process, act, and communicate supports Sandia's mission needs. Research focus areas include microdevice concepts that enable advances in microelectronics, photonics, microelectromechanical systems, and sensors. Other important research includes using semiconductor fabrication techniques to combine electronic, optical, mechanical, and chemical functions into integrated systems; new approaches to integration, packaging, and micropower systems are being investigated.

NEMOs (nanoelectromechanical oscillators) are mechanical oscillators with small dimensions and high-resonance frequencies. These devices would be valuable as simple, inexpensive, passive radio-frequency (RF) filters for Sandia projects, including narrowband communications, radar, and RF signal processing. *Nanoelectromechanical Oscillators (NEMOs) for RF Filtering* will create high-quality factor (Q) nanoelectromechanical oscillators for RF signal processing. The primary obstacle to NEMOs is to maintain high-Q with a high-resonant frequency. This obstacle will be overcome by using

a new microelectromechanical systems (MEMS) material and a new vertical-cantilever NEMO design that will be easy to fabricate. Performance will be improved by using parametric amplification to increase the resonance amplitude and narrow the dispersion, and by performing fundamental studies of energy dissipation in nanosized structures to understand how to increase Q. One patent disclosure has been filed by this project.

26518

III-Antimonide/Nitride–Based Semiconductors for Optoelectronic Materials and Device Studies

G. M. Peake, J. F. Klem, E. D. Jones, S. R. Kurtz, N. A. Modine, T. W. Hargett, D. K. Serkland, M. J. Cich, A. A. Allerman, K. E. Waldrip

Vertical-cavity surface-emitting lasers (VCSELs) operating at 1.3–1.55 μm would revolutionize communication technology due to the high efficiency and the excellent beam quality and manufacturability of VCSELs. Current promising materials are based on indium gallium arsenide nitride (InGaAsN) or gallium arsenide antimonide (GaAsSb), both grown on GaAs substrates where the superior thermal conductivity and index contrast of aluminum gallium arsenide (AlGaAs) distributed Bragg reflector (DBR) mirrors can be employed. However, because of poor valence or conduction-band alignments, these systems do not satisfy the needed temperature stability. Sandia believes that the GaAsSbN material system is a superior candidate for the 1.3–1.55 μm semiconductor laser system because it offers fewer difficulties with strain-layer growth and may be made to span a range of bandgaps from 0.8 to 1.2 eV (1.55–1 μm). However, lack of basic information concerning this alloy restricts its use in semiconductor devices. Therefore, we propose to thoroughly investigate the GaAsSbN alloy system. The growth of this material for laser applications is completely new and has not been investigated. The material properties of this alloy are poorly characterized, and it affords an excellent opportunity for Sandia's world-class expertise in growth and characterization of novel semiconductors. This investigation will also enable us to expand the understanding of dilute nitride alloys beyond our existing world-class efforts in InGaAsN. We assembled a research team for this project that has demonstrated leadership in the research and device community through publications, invited presentations, and record device performance in developing new semiconductor alloys.

We accomplished the first measurement of GaAsSbN transport properties, including mobility, electron and hole mass, and exciton-reduced mass. We presented the first description of the organometallic vapor-phase epitaxy (OMVPE) of GaAsSbN. Growth studies of GaAsSbN indicated kinetically limited growth, and we calculated the activation energy. We investigated temperature, group III, and group V growth-rate dependencies. We collected electroluminescence from edge-emitting and vertical-cavity laser structures. We grew GaAsSbN by both molecular beam epitaxy (MBE) and metal-organic chemical vapor deposition (MOCVD) well past 1.3 μm ,

Sandia believes that the GaAsSbN material system is a superior candidate for the 1.3–1.55 μm semiconductor laser system because it offers fewer difficulties with strain-layer growth and may be made to span a range of bandgaps from 0.8 to 1.2 eV (1.55–1 μm). ...The growth of this material for laser applications is completely new and has not been investigated.

with room-temperature emission of $> 1.4 \mu\text{m}$ for the OMVPE material and low-temperature (4 K) photoluminescence (PL) of the MBE material out to $1.66 \mu\text{m}$, which is one of the longest-wavelength type-I materials ever grown coherently on GaAs substrates. We measured the reduced exciton mass of GaAsSbN at about twice that found for GaAsSb by comparing the diamagnetic shift versus the magnetic field.

We found the OMVPE growth of GaAsSbN to be kinetically limited in the range of $520^{\circ}\text{--}600^{\circ}\text{C}$ with an activation energy of 10.4 kcal/mol . The growth rate is linear with group III but has a complex dependence on the group V constituents. N (nitrogen) from 1,1 -dimethylhydrazine was more efficiently incorporated for samples with no In, as was reported for other dilute nitride systems grown by OMVPE, MBE, and chemical beam epitaxy (CBE). We achieved room-temperature PL wavelengths $> 1.3 \mu\text{m}$ for unannealed GaAsSbN. Increasing temperature during growth increases the emission wavelength at the expense of intensity and full-width half-medium (FWHM). A 4 K PL of $\text{GaAs}_{0.69}\text{Sb}_{0.3}\text{N}_{0.01}$ shows a red shift of $55\text{--}77 \text{ meV}$, an increase in FWHM of $2.4\text{--}3.4$ times the FWHM, and a decrease in intensity of $1\text{--}2$ orders of magnitude as compared to $\text{GaAs}_{0.7}\text{Sb}_{0.3}$. High-temperature annealing of OMVPE GaAsSbN does not show substantial blue shift, and we attribute this to the single group III chemistry. Mobility is slightly degraded compared to GaAsSb with the addition of N, similar to the degradation of InGaAsN compared to InGaAs, with a 300 K mobility of $350 \text{ cm}^2/\text{V/s}$ at $1.0 \times 10^{17}/\text{cm}^3$ background-hole concentration, and a 77 K mobility of $1220 \text{ cm}^2/\text{V/s}$ at a background-hole concentration of $4.8 \times 10^{16}/\text{cm}^3$ for lattice-matched $\text{GaAs}_{0.94}\text{Sb}_{0.05}\text{N}_{0.01}$. A calculation of the hole mass was $0.37\text{--}0.40 m_0$ for $\text{GaAs}_{0.7}\text{Sb}_{0.3}$, and we estimate an electron mass of $0.2\text{--}0.3 m_0$ for $\text{GaAs}_{0.69}\text{Sb}_{0.3}\text{N}_{0.01}$.

Although we have yet to achieve room-temperature continuous-wave (CW) lasing of this material, we met all of the other objectives of this project. The goal of room-temperature CW lasing of this material is close at hand and will be accomplished in the near future.

We grew GaAsSbN by both molecular beam epitaxy (MBE) and metal-organic chemical vapor deposition (MOCVD) well past $1.3 \mu\text{m}$, with room-temperature emission of $> 1.4 \mu\text{m}$ for the OMVPE material and low-temperature (4 K) photoluminescence (PL) of the MBE material out to $1.66 \mu\text{m}$, which is one of the longest-wavelength type-I materials ever grown coherently on GaAs substrates.

Refereed

Peake, G. M., A. A. Allerman, T. W. Hargett, K. E. Waldrip, J. F. Klem, N. A. Modine, D. K. Serkland, and M. J. Cich. 2003. OMVPE of GaAsSbN for 1.3-micrometer emitters. Paper presented at the 11th Biennial Workshop on OMVPE, 20–24 July, Keystone, Colorado.

Peake, G. M., J. F. Klem, N. A. Modine, E. D. Jones, A. A. Allerman, and S. R. Kurtz. 2002. Theoretical and experimental investigations of GaAsSbN on GaAs substrates for 1.3–1.55 micrometer emission on GaAs substrates. *Proc. Longwave on GaAs Workshop* 1 (4–5 June, Napa, California).

Peake, G. M., K. E. Waldrip, T. W. Hargett, N. A. Modine, and D. K. Serkland. 2003. OMVPE of GaAsSbN for long-wavelength emission on GaAs. *J. Crystal Growth*, accepted.

Wixom, R. R., G. B. Stringfellow, and N. A. Modine. 2003. Theory of Sb-induced triple-period ordering in GaInP. *Physical Review B* 64:201322.

Wixom, R. R., N. A. Modine, and G. B. Stringfellow. 2003. Theory of surfactant (Sb)-induced reconstructions on InP(001). *Physical Review B* 67:115309.

Other Communications

Jalali, F., L. Hampton, K. E. Waldrip, N. A. Modine, J. F. Klem, G. M. Peake, and E. D. Jones. 2002. Low-temperature photoluminescence studies of GaAsSbN quantum wells on GaAs. Paper presented at the 14th Annual Rio Grande Regional Sponsored Symposium on Advanced Materials, October, Albuquerque, New Mexico.

Jones, E. D., K. E. Waldrip, F. Jalali, N. A. Modine, J. F. Klem, and G. M. Peake. 2002. Low-temperature photoluminescence studies of narrow-bandgap GaAsSbN quantum wells on GaAs. Paper presented at the 202nd Meeting of the Electrochemical Society, 20–25 October, Salt Lake City, Utah.

Waldrip, K. E., E. D. Jones, F. Jalali, N. A. Modine, J. F. Klem, and G. M. Peake. 2002. Low-temperature photoluminescence studies of GaAsSbN quantum wells on GaAs. Paper presented at the Four Corners APS Fall Meeting, October, Salt Lake City, Utah.

Waldrip, K. E., E. D. Jones, F. Jalali, N. A. Modine, J. F. Klem, and G. M. Peake. 2002. Low-temperature photoluminescence studies of narrow-bandgap GaAsSbN quantum wells on GaAs. Paper presented at the Fall Materials Research Society Meeting, December, Boston, Massachusetts.

Waldrip, K. E., L. N. Hampton, F. Jalali, N. A. Modine, J. F. Klem and G. M. Peake. 2003. Low-temperature photoluminescence studies of GaAsSbN/GaAs narrow-bandgap quantum wells. Paper presented at the New Mexico Chapter of the American Vacuum Society Meeting, April, Albuquerque, New Mexico.

26519

The Integration of Advanced Photonics and MEMS

J. G. Fleming, G. R. Hadley, S. Y. Lin

There is considerable interest in optical microelectromechanical systems (MEMS). However, such devices typically do not take advantage of the full range of possibilities that arise from the wave nature of light. Such devices typically consist of conceptually simple, but structurally complex, mechanical systems that are really just movable mirrors. On the other hand, one potentially interesting area of photonics research is that of ring resonators and waveguide couplers. Physically, these are relatively simple structures, but they have the potential of being able to act as narrow, high-efficiency band filters/drops and couplers. Progress in this area was hindered by fabrication and switching difficulties. The application of MEMS to this area potentially solves both problems. Further, the size scale of such devices is almost ideal for MEMS; small displacements give rise to large changes in optical properties. This added functionality can not be realized by current MEMS technology.

Sandia demonstrated the fabrication of two different classes of devices that demonstrate this principle. In the first class of devices, we designed and fabricated a suspended, movable silicon (Si) waveguide. We designed this waveguide to be actuated so it could be brought into close proximity to a ring resonator or similar structure. In the course of this work, we also designed a technique to improve the input coupling to the waveguide. While these structures were successfully fabricated, they were not robust enough to survive our relatively crude assembly and test processes. We then redesigned our devices so that instead of moving the waveguides themselves, we moved a much smaller optical element into close proximity to the waveguides. Using this approach we successfully fabricated splitters, switches, resonators, and attenuators. We successfully tested switches, splitters, and attenuators. We found the quality of the silicon nitride (SiN) waveguides fabricated in this work to be qualitatively compatible to those made using semiconductor materials.

We continued to test our second-generation structures, both the structures previously released and the new devices. We investigated a problem that was occurring with certain of the larger coupling structures and ring resonators. We found that quite often one of the spring suspensions holding these

Sandia demonstrated the fabrication of two different classes of devices that demonstrate this principle. ...we also designed a technique to improve the input coupling to the waveguide.

structures was broken in the course of the release process. We ended up attributing this to the internal stress associated with the tungsten (W) deposition process combined with the high stiffness of these SiN-based waveguide structures. The simple solution to this problem involves moving the actuator farther above the photonic element and reducing the contact to a single-point contact. Reducing the stress of the W level is also a possibility; however, at this stage we consider the internal tensile stress of the W film to be an advantage since it eliminates problems with stiction; the actuation voltage was not a problem.

We also more intensively investigated the performance of the ring resonator structures. We earlier demonstrated switches, splitters, and attenuators, all in the same technology, integrated with SiN waveguides with performance similar to that of semiconductor waveguides. However, we were unable to successfully demonstrate the narrowband ring resonator structures. There are several possibilities for this. The first is that the linewidth of the channel drop is too fine to be resolved readily with the detection equipment. This is possible since the linewidth expected from the literature was less than 1 nm. Another possibility is that the coupling in this vertical configuration was insufficient. A final, and perhaps most probable, possibility is that the presence of the metal actuator directly over the resonator and its 2 μm cladding leads to an increase in absorption and drop in the system Q (quality). This problem would also be solved by the addition of a smaller-point metallic contact right in the center of the ring where there is relatively little modal intensity.

Refereed

Fleming, J. G., and S. Y. Lin. 2002. Novel application of MEMS to microphotronics. Paper presented at the Fall MRS Conference, December, Boston, Massachusetts.

32913

Aging Mechanisms in Dormant MEMS Structures

T. M. Mayer, M. P. De Boer, B. C. Bunker, B. I. Kim

Thin organic films can render microelectromechanical systems (MEMS) surfaces hydrophobic, eliminating the catastrophic effects of capillary-driven interfacial adhesion. However, even treated surfaces can demonstrate strong adhesion and station after long-term environmental exposures due to aging and restructuring within the antistiction films. The physics and chemistry of interactions between micromachine components is poorly understood. Consequently, micromachine performance as a function of time and storage conditions ("dormancy") cannot yet be predicted. In this project, Sandia seeks to elucidate the mechanisms of property evolution in hydrocarbon and fluorocarbon coatings with an emphasis on self-assembled monolayers (SAMs). We employ a suite of in situ experimental probes to determine (1) how the molecular structures and compositions of MEMS surfaces change with time and environmental exposure, (2) how these molecular changes influence the interfacial adhesion between well-defined, nanometer-scale, single-asperity contacts, and (3) whether models based on molecular- and nanoscale experiments can be used to predict the evolving interactions between rough surfaces in model micromachine components. The result of this project will be the development of physical and chemical models for dormancy in MEMS that span molecular-, nanometer-, and micron-length scales. The models will provide a framework for evaluating MEMS environmental and packaging requirements and for developing more robust MEMS designs and antistiction coatings.

We completed an extensive matrix of measurements of degradation of a number of candidate hydrophobic films in high-temperature and high-humidity environments. These tests define accelerated aging conditions that pinpoint issues of long-term reliability in these coatings in MEMS applications. We included films of octadecyltrichlorosilane (OTS), dimethyldichlorosilane (DDMS), octadecene (OD), perfluorooctyltrichlorosilane (FOTS), perfluorooctyl-tris-dimethylaminosilane (FOTAS) in a matrix with temperatures of 50°–80°C, relative humidity of 80%–100%, and sampling intervals of 2 weeks to 6 months. Measurements included atomic-force microscope (AFM) measurements of morphology, interfacial-force microscope (IFM) measurements of adhesion

...Sandia seeks to elucidate the mechanisms of property evolution in hydrocarbon and fluorocarbon coatings with an emphasis on self-assembled monolayers (SAMs)....The result of this project will be the development of physical and chemical models for dormancy in MEMS that span molecular-, nanometer-, and micron-length scales. The models will provide a framework for evaluating MEMS environmental and packaging requirements and for developing more robust MEMS designs and antistiction coatings.

and friction, and ellipsometric measurements of film thickness before and after exposures. We identified stability issues with all films somewhat after exposure to harsh environmental conditions. We observed morphological changes associated with debonding of the films to the silicon dioxide (SiO_2) substrate and water adsorption in or under the films with many samples. Parallel measurements of water adsorption at room temperature clearly show that water penetrates the films and adsorbs at the film-substrate interface. The behavior of the film morphology and adhesion is quite complex, and a straightforward mechanism of film degradation is not yet apparent. It seems likely that hydrolysis of the Si-O interfacial bonds in all cases is responsible for film degradation. Further detailed experiments are necessary to elucidate this mechanism. The extreme exposure conditions employed in this study are clearly not recommended for accelerated aging protocols.

Refereed

Hankins, M. G., P. J. Resnick, P. J. Clews, T. M. Mayer, D. R. Wheeler, D. M. Tanner, and R. A. Plass. 2002. Vapor deposition of amino-functionalized self-assembled monolayers on MEMS. Paper presented at SPIE, November, San Jose, California.

Hankins, M. G., P. J. Resnick, P. J. Clews, T. M. Mayer, D. R. Wheeler, D. M. Tanner, and R. A. Plass. 2003. Vapor deposition of amino-functionalized self-assembled monolayers on MEMS. *SPIE* **4980**:238.

Kim, B. I., B. C. Bunker, T. M. Mayer, M. P. de Boer, and M. G. Hankins. 2003. Self-assembled monolayer aging in humid environments. Paper presented at APS, March, Austin, Texas.

Kim, B. I., B. C. Bunker, T. M. Mayer, M. P. de Boer, and M. G. Hankins. 2003. The effects of humidity on stiction and friction in micromachines. Paper presented at the APS Meeting, March, Austin, Texas.

Kosuri, M. R., H. Gerung, Q. Li, S. M. Han, B. C. Bunker, and T. M. Mayer. 2003. Vapor-phase adsorption kinetics of 1-decene on Si(100). *Langmuir*, accepted.

Kosuri, M. R., R. Cone, Q. Li, S. M. Han, B. C. Bunker, and T. M. Mayer. 2003. Adsorption kinetics of 1-alkanethiols on hydrogenated Ge(111). *Langmuir*, accepted.

Mayer, T. M. 2003. Atomic-layer deposition for MEMS applications. Paper presented at ALD 2003, August, San Jose, California.

32923

MEMS in μ Fluid Channels*T. L. Sounart, S. S. Mani, G. D. Bachand, M. Okandan, C. M. Matzke*

Microelectromechanical systems (MEMS) comprise a new class of devices that includes various forms of sensors and actuators. Recent studies show that microscale cantilever structures are able to detect a wide range of chemicals, biomolecules, or even single bacterial cells. In this approach, cantilever deflection replaces optical fluorescence detection, thereby eliminating complex chemical tagging steps that are difficult to achieve with chip-based architectures. A key challenge to utilizing this new detection scheme is the incorporation of functionalized MEMS structures within complex microfluid (μ fluid) channel architectures. The ability to accomplish this integration is currently limited by the processing approaches used to seal lids on pre-etched μ fluid channels. This project combines Sandia's leading capabilities in MEMS processing with our newly developed low-temperature photolithographic method for fabricating μ fluid channels to construct MEMS-instrumented μ fluidic chips. We explored in situ cantilevers and other similar passive MEMS devices as a new approach to directly sense fluid transport and successfully monitored local flowrates and viscosities within μ fluid channels. We also incorporated actuated MEMS structures into μ fluidic channels and addressed the electrical and hydrodynamic limitations of actuation in liquids. We accomplished electrostatic actuation in water and invented a novel technique for monitoring local electrical conductivities.

We further studied the interaction of fluid with the flow/viscosity sensor in μ fluidic channels. We demonstrated repeatable results for additional fluids, including silicone oils, and extended the measured flowrate range down to 2 μ L/min. Measurements demonstrated a linear response between flowrate and angular deflection for 4.6 cP silicone oil, up to 20 μ L/min.

The linear range for liquids with viscosities similar to water is limited to about 5 μ L/min because of nonlinear inertial effects. We determined the maximum sensitivity of the device to fluid flow to be 12.5 ± 0.2 mrad/(mL/min). We also simulated the fluid motion and sensor-plate deformation with finite-element modeling (FEM) analyses, which demonstrates the importance of edge effects on the sensor response.

We designed electrostatically actuated, microfabricated cantilever sensors and integrated them into μ fluidic channels. One of the key challenges for actuated sensors embedded in

This project combines Sandia's leading capabilities in MEMS processing with our newly developed low-temperature photolithographic method for fabricating μ fluid channels to construct MEMS-instrumented μ fluidic chips.... We accomplished electrostatic actuation in water and invented a novel technique for monitoring local electrical conductivities.

liquid-filled channels is interference of the liquid with the actuation mechanism. Using alternating-current (AC) drive signals, we demonstrated electrostatic actuation in many liquids, at potentials low enough to avoid electrochemistry. We measured the frequency response in liquids spanning a decade of dielectric permittivities and four decades of conductivity, and developed a theory that predicts the characteristic actuation frequency. We successfully actuated sensors in water, requiring a frequency of only 100 kHz for maximum displacement. Our analysis demonstrated the importance of the native oxide on silicon (Si) actuator response and revealed a method for control of the actuation frequency. For native Si devices, we initiated actuation at frequencies less than 1 MHz, in electrolytes of ionic strength up to 10 mmol/L. We developed a benchtop high-power/high-frequency amplifier and fabricated it to enable actuation in water at applied potentials up to 100 V. This instrument has found extensive use inside and outside Sandia, and over 15 units have been built to date, with 3 more on order.

We invented a technique for measuring conductivity electromechanically. We discovered the basis for the technique from the study of electrostatic actuation in liquids, in which it was revealed that for Si actuators in most liquids, the actuation frequency is linear in conductivity and independent of other fluid properties. We measured fluid conductivities from 70 nS/cm to 200 μ S/cm with a Si MEMS device.

Another key challenge for dynamic μ fluidic sensors is liquid damping. Most microcantilevers are overdamped in water and are thus not viable resonance sensors. Cantilevers shorter than approximately 100 μ m may resonate, but their sensitivities are extremely low due to a low quality factor. We explored coatings for damping reduction in MEMS based on hydrophobic slip at liquid-solid interfaces. We determined that damping reduction from hydrophobic self-assembled monolayer (SAM) coatings is not significant, but a new coating recently developed at Sandia was demonstrated to significantly reduce drag in macroscale systems. We began synthesis of these coatings in microscale systems and measured a 5% drag reduction in a microcapillary even though it was only poorly coated. We expect orders-of-magnitude more reduction in damping when proper synthesis is accomplished in microscale devices.

...a new coating recently developed at Sandia was demonstrated to significantly reduce drag in macroscale systems. We began synthesis of these coatings in microscale systems and measured a 5% drag reduction in a microcapillary even though it was only poorly coated. We expect orders-of-magnitude more reduction in damping when proper synthesis is accomplished in microscale devices.

Refereed

Czaplewski, D. A., B. Ilic, M. Zalalutdinov, W. L. Olbricht, A. T. Zehnder, H. G. Craighead, and T. A. Michalske. 2003. Fully encapsulated micromechanical viscometer. *J. Microelectromechanical Systems*, New York City, New York: IEEE, submitted.

Sounart, T. L., T. A. Michalske, and K. R. Zavadil. 2003. Frequency-dependent electrostatic actuation in microfluidic MEMS. *J. Microelectromechanical Systems*. New York City, New York: IEEE, submitted.

Other Communications

Czaplewski, D. A., B. Ilic, M. Zalalutdinov, W. L. Olbricht, A. T. Zehnder, H. G. Craighead, and T. A. Michalske. 2003. In-channel micromechanical plate interacting with fluid flow. *Digest of Technical Papers, Proc. Transducers '03* **1** (June, Boston Massachusetts): 392–95.

Sounart, T. L., and T. A. Michalske. 2003. Electrostatic actuation without electrolysis in microfluidic MEMS. *Digest of Technical Papers, Proc. Transducers '03* **1** (June, Boston, Massachusetts): 615–18.

Sounart, T. L., K. R. Zavadil, and T. A. Michalske. 2003. Electrostatic actuation in bioMEMS. Paper presented at the AVS 50th International Symposium, November, Baltimore, Maryland.

33602

Dispersive Photonics for Next-Generation Sensors and Microsystems

G. A. Vawter, D. W. Peters, J. R. Wendt, S. Y. Lin, S. A. Kemme, G. R. Hadley, C. Alford, M. J. Hafich, W. J. Zubrzycki, J. Guo

Artificially structured photonic bandgap (PBG) materials are commonly investigated for their unique ability to block and guide light. However, an exciting aspect of PBGs that has received relatively little attention is the extremely high refractive-index distortion near the edge of the bandgap but within the range of frequencies capable of propagating within the PBG material. In fact, it was recently proposed that a negative refractive index may be realized with the correct PBG configuration. Sandia investigated, both numerically and experimentally, the design and performance of such PBG materials intended to optimize the “distortion” of refractive index to realize new classes of photonic devices. Potential benefits include stripes of positive and negative refractive index forming a planar “lens train” capable of guiding light much like a sequence of spherical lenses guides a Gaussian beam.

We expect these optical properties of PBGs to yield new and unexpected applications as understanding and fabrication technology develop in the next few years. It is feasible that guided light might be focused to extremely high intensity and used to probe micro- or nanocavities filled with organic material in a chemical or biological sensor role, such as cytology, or that refractive index of a fluid could be monitored with a very sensitive threshold wherein the strong index distortion effect would dramatically alter the optical properties of a waveguide or resonant cavity.

We continued the tight relationship of numerical simulation and experimental measurement. We measured light scattered out of the dispersive PBG surface as a means of evaluating refraction at the PBG incident waveguide interface and propagation within the PBG material itself. We designed and fabricated new devices with improved optical properties. We used three-dimensional models to better understand coupling of light to out-of-plane radiation modes. We investigated new devices such as couplers to high-numerical-aperture PBG waveguides. We explored applications conceptually, including biological and chemical sensors, using the strong focusing effect of the negative-index PBG device to create an ultrahigh-light-intensity region around a single hole within the PBG material resulting in an extremely strong interaction between

Sandia investigated, both numerically and experimentally, the design and performance of such PBG materials intended to optimize the “distortion” of refractive index to realize new classes of photonic devices....We expect these optical properties of PBGs to yield new and unexpected applications as understanding and fabrication technology develop in the next few years.

the optical field and the air, or other material, in the hole within the PBG material.

Refereed

Hadley, G. R. 2002. Negative index behavior in hexagonal-symmetry photonic crystals. Paper presented at the Progress in Electromagnetics Research Symposium, July, Boston, Massachusetts.

Hadley, G. R. 2003. Numerical modeling of out-of-plane losses of photonic crystal waveguides. Paper presented at the Integrated Photonics Research Topical Meeting, June, Washington, D.C.

Peters, D. W., G. R. Hadley, G. A. Vawter, G. S. Subramanian, J. R. Wendt, and J. Guo. 2003. Coupling into single-row-defect photonic crystal waveguides using a photonic crystal exhibiting negative refraction. Paper presented at PIERS 2003, October, Honolulu, Hawaii.

Peters, D. W., G. R. Hadley, G. S. Subramanian, G. A. Vawter, and J. R. Wendt. 2002. Focusing of light into a row defect waveguide using the negative refraction behavior of a photonic crystal. Paper presented at PECS IV, October, Los Angeles, California.

38616

Engineered Superconductivity in Electron-Hole Bilayers

M. P. Lilly, J. L. Reno, J. A. Simmons, L. L. Stephenson, R. G. Dunn

Sandia will fabricate and measure transport characteristics of an electron-hole bilayer (EHBL). Due to the strong attractive interaction between the oppositely charged carriers, we expect this system to make a transition to a superconducting state at low temperatures. The EHBL will be implemented in gallium arsenide/aluminum gallium arsenide (GaAs/AlGaAs) heterostructures, where individual layers can be in close proximity to maximize the Coulomb energy. Additional critical features will be high electron and hole mobilities, low sheet densities, and independently contacted layers. Through the use of bandgap engineering, these parameters can be tuned to optimize the device.

The success of this project relies on the integration of four techniques: molecular beam epitaxy (MBE) crystal growth, use of undoped heterostructures, dual-side lithography, and Coulomb drag transport measurements. Since the superconducting state depends on interactions between the layers, extremely high mobility MBE heterostructures are required. To avoid problems that arise with doping bipolar systems, we implemented undoped heterostructures. The carriers are generated using self-aligned contacts in a field-effect transistor (FET) geometry. We demonstrate that this technique is consistent with high mobility and low density. In the proposed EHBL device, self-aligned contacts are needed above and below the bilayer. The main focus this year was to characterize the low-density behavior of low-density electrons, improve undoped techniques, and incorporate the epoxy bond and stop etch (EBASE) technique with undoped double-layer heterostructures.

First, we reported measurements of the temperature (T) dependence of the resistivity for an undoped single-layer heterojunction for a range of densities. The high-density data are characterized by decreasing resistivity as the T decreases. This result is in quantitative agreement with acoustic phonon scattering. Over a wide range of intermediate densities, we observe a local maximum at low T. In this regime, ionized impurity scattering leads to a competition between screening (resistivity linear with T) for T less than the Fermi temperature and degenerate to nondegenerate Fermi statistics (resistivity proportional to $1/T$) for T greater than the Fermi T. This causes

Sandia will fabricate and measure transport characteristics of an electron-hole bilayer (EHBL). Due to the strong attractive interaction between the oppositely charged carriers, we expect this system to make a transition to a superconducting state at low temperatures.

the formation of the peak. Scattering calculations, including phonons and ionized impurities, are in excellent qualitative agreement with the data for the intermediate densities. The lowest densities exhibit insulating behavior. The power-law T dependence observed here is not consistent with either weak or strong localization and remains an open question.

This combination of detailed transport measurements and comparison to scattering theory is an important contribution to the two-dimensional (2-D) metal-insulator transition (MIT) community. Within the standard framework of Fermi liquid theory, we do not expect a 2-D MIT. Our work on high-mobility 2-D electrons shows that the underlying physics is Fermi liquid physics and not a new many-body effect.

Second, we observed weak localization phenomena and electron-electron conductance corrections in undoped single-layer heterostructures. To observe superconductivity in EHBLs, interlayer Coulomb correlations must be strong. One way to achieve this is to use low sheet densities, but not so low that the 2-D layers become insulating. Due to the unusual insulating behavior mentioned above, we initiated a study of the transport characteristics of a moderate-mobility 2-D electron system. For each density and T , the magnetoresistance exhibits a clear parabolic background that is due to an electron-electron interaction correction to the conductivity. At the lowest density, we observed a very fragile peak at 0.28 K that arises from quantum correction to the resistivity (weak localization). The characteristic shape of the weak localization peak can be used to extract the electron-phase lifetime. This information will be a useful tool for future experiments on EHBLs where the predicted superconductivity will arise from phase-coherent electron-hole pairs.

Third, we began fabrication of 2-D bilayers using undoped techniques. To extend the fabrication techniques to undoped bilayer systems, the self-aligned contacts on the surface of the sample must be integrated with the EBASE technique and back-side processing. To simplify the process, we designed the first generation of bilayer devices for hole-hole bilayers rather than the more complicated EHBL. Initial tests of hole-hole bilayers find evidence that the 2-D layers are formed, but current leaking from the gates into the bilayer limits our ability to measure transport after the bilayer is established. We expect rapid progress in combining EBASE and self-aligned contacts.

This information will be a useful tool for future experiments on EHBLs where the predicted superconductivity will arise from phase-coherent electron-hole pairs....To simplify the process, we designed the first generation of bilayer devices for hole-hole bilayers rather than the more complicated EHBL.

Refereed

Lilly, M. P., J. L. Reno, J. A. Simmons, I. B. Spielman, J. P. Eisenstein, L. N. Pfeiffer, K. W. West, H. Hwang, and S. D. Sarma. 2003. Resistivity of dilute 2-D electrons in an undoped GaAs heterostructure. *Physical Review Letters* **90**:056806.

Other Communications

Lilly, M. P. 2003. "Metallic" behavior of dilute 2-D electron systems. Paper presented at the Condensed Matter Seminar, Princeton University, Princeton, New Jersey.

Lilly, M. P. 2003. "Metallic" behavior of dilute 2-D electron systems. Paper presented at the Condensed Matter Seminar, University of Texas, Austin, Texas.

Lilly, M. P. 2003. "Metallic" behavior of dilute 2-D electron systems. Paper presented at the Solid-State Seminar to Theory Group, Los Alamos National Laboratories, Los Alamos, New Mexico.

Lilly, M. P. 2003. The contentious metallic state of two-dimensional electrons in semiconductors. Paper presented at the Physics Colloquium, Texas A&M University, College Station, Texas.

38617

Silicon-Based RF MEMS Components

C. W. Dyck, S. E. Allen, J. E. Stevens, J. G. Fleming, M. S. Baker, C. D. Nordquist

Radio-frequency microelectromechanical systems (RF MEMS) is an enabling technology for the next generation of communications and radar systems in both military and commercial sectors. These devices have low insertion loss and low-static power consumption, are lightweight, and are capable of high levels of integration with other components. Successful development of this technology would directly benefit strategic business units and the commercial sector for frequency ranges below 10 GHz. Historically, III–V compound semiconductor material has been used for RF communications components. However, Sandia has fabricated and characterized low-loss prototype silicon (Si)-based RF MEMS switches. Leveraging this development, we designed and are nearing completion of 4-bit RF MEMS phase shifters. We also designed analog filters using the Si stand-off process that will begin fabrication soon. We will design and begin fabrication of prototype microdeployable antennas using actuation or fluidic approaches that allow for the flexibility in deploying antenna structures when needed for operation.

We completed fabrication and characterization of the capacitive switch (ohmic switch in a shunt configuration). The switch is an aluminum (Al) bridge that is suspended 2 mm above a tungsten (W) bottom metal contact. The bottom contact is connected to a thin Al shunt metal that is connected to ground by a large capacitor under the co-planar waveguide (CPW) ground line. The bridge is also the signal line of a CPW transmission line. In the up state, there is an air gap between the bridge and the contact metal. Incident microwave signals propagate through the switch with minimal reflection because there is a high-impedance path to ground. When a bias voltage that exceeds the pull-in voltage is applied between the substrate and the signal line, the bridge snaps down into contact with the underlying contact metal, forming a low-impedance path to ground through the large capacitor and reflecting incident signals. This is the downstate.

We completed a 4-bit, true-time delay, Ku-band, phase-shifter design using the ohmic shunt switch described in the previous paragraph. The phase shifter consists of four sections with two path lengths in each section that can be selected with the RF MEMS switches. All 8 path lengths are unique, resulting

Radio-frequency microelectromechanical systems (RF MEMS) is an enabling technology for the next generation of communications and radar systems in both military and commercial sectors. ...Successful development of this technology would directly benefit strategic business units and the commercial sector for frequency ranges below 10 GHz....Sandia has fabricated and characterized low-loss prototype silicon (Si)-based RF MEMS switches.

in 16 possible path-length combinations. The phase-shifter fabrication is nearing completion. The wafers still require metal deposition, planarization, and release processing in the Computer Semiconductor Research Laboratory (CSRL). We modified the ohmic switches slightly for application to RF MEMS phase-shifter circuits. We added a thin-film resistor layer to actuate the structures, instead of the substrate biasing that the current structures use. Simulations indicated that resistor values of greater than 20 k Ω were sufficient to isolate the actuation pads from the microwave circuit. We also changed the bridge metal to gold (Au) to reduce the contact resistance between the bridge and the bottom metal.

We modified our original tunable filter plans by changing from a discrete filter design to an analog filter design. Analog filters are preferable since they continuously cover the band of interest. The filter design specifications are a four-pole filter with a 1 GHz bandwidth and a 3 GHz tunability range, centered in the Ku band. We will fabricate the filter using the Si stand-off technology. The filter consists of seven tunable interdigitated comb-drive capacitors. Four are connected in series to maintain a constant bandwidth over the tuning range, and three are shunted to ground to control the center frequency tuning. Three stub inductors are connected from the signal line to ground. We are also developing an air-dielectric stripline process using the Si stand-off technology, as early design simulations indicated that filters using CPW transmission lines had high metal losses. This process consists of Au-covered W signal lines suspended 30 μ m above a standard Si substrate.

We are now focusing on designing and beginning processing of a microdeployable fluidic or actuated antenna.

38619

Nanoelectromechanical Oscillators (NEMOs) for RF Filtering

J. P. Sullivan, T. A. Friedmann, C. W. Dyck, J. R. Wendt, D. W. Carr, C. P. Tigges, R. V. Ellis

The goals of this project are to create high-frequency and high-quality (high- Q) nanoelectromechanical oscillators (NEMOs) for radio-frequency (RF) signal processing, and to demonstrate a solution to charge trapping in capacitively coupled RF microelectromechanical systems (MEMS) switches. NEMOs are mechanical oscillators with critical dimensions < 50 nm and GHz resonance frequencies. These devices would be valuable as simple, inexpensive, passive RF electrical filters or as platforms for sensor arrays, and they would be expected to benefit Sandia programs in RF communications or sensing systems for homeland security.

The primary obstacle to developing NEMOs is maintaining high Q with a high resonant frequency, f . Sandia will address this obstacle by (1) using a new, ultrahigh modulus MEMS material, amorphous diamond (aD), with f twice that of silicon (Si), (2) using a new in-plane array of NEMOs that is easy to fabricate and permits the use of novel optical-detection schemes, (3) using approaches, such as parametric amplification, to increase the resonance amplitude and narrow the dispersion, and (4) performing fundamental studies of energy dissipation in nanosized structures to understand how to increase Q . We found surfaces to control internal dissipation in many small oscillator structures, so we will evaluate the effect of surface losses through the use of materials that have abrupt surface termination, such as aD.

A second objective of this project is to eliminate the reliability problem in capacitively coupled RF MEMS switches due to oxide charging. We will use the dissipative dielectric, aD, for the dielectric spacer layer and will evaluate its performance. We expect that this material should enable improved performance due to its charge-dissipation capability, its extreme smoothness (permits thin dielectrics), its hydrophobicity (reduces stiction), and its wear resistance.

We made several important breakthroughs in this work. We developed a new laser annealing process that now permits the creation of stress-free aD films using an entirely room-temperature process. This would enable a solution to the longstanding problem of integrating MEMS with existing microelectronics on the same wafer. With this new

Interferometric profile of the aD capacitively coupled RF MEMS switch. (Lateral dimensions are several hundred microns; the vertical scale is exaggerated.)

These devices would be valuable as simple, inexpensive, passive RF electrical filters or as platforms for sensor arrays, and they would be expected to benefit Sandia programs in RF communications or sensing systems for homeland security.

development, aD MEMS could be fabricated on top of or alongside microelectronics and Si MEMS without increasing the thermal budget. This new technique relies on the use of excimer-laser annealing, which involves the application of light pulses with photon energies of 5 eV. At these high photon energies, most of the energy is absorbed within the aD film, and the energy is sufficient to permit the local bond breaking required for stress relaxation. The total energy deposited into the sample is quite small, however, leading to a negligible net temperature increase of the substrate. Using pulsed-laser annealing, we demonstrated near full-stress relaxation with a single 20 ns-long light pulse.

We made important developments in the fabrication and measurement of NEMOs. We fabricated unique structures consisting of arrays of in-plane NEMOs that have critical dimensions down to 50 nm and resonance frequencies up to several hundred megahertz. We invented a novel optical measurement technique to measure in-plane motion of these structures, and initial measurements showed detectable resonant frequencies over 100 MHz and quality factors over 600. This technique relies on measurements of changes in the optical reflectance from the arrays and is capable of detecting motion down to 10^{-5} nm/Hz^{1/2}. This novel measurement approach led to a patent disclosure and additional funded projects in the area of inertial sensing. The NEMO arrays themselves are also showing promise for the realization of new sensor structures based on functionalized NEMOs. (The high surface area and extreme sensitivity to small displacements should enable high chemical sensitivity.)

We successfully fabricated and tested RF MEMS switches that incorporate aD as a charge-dissipating spacer dielectric. The switches showed the best performance of any capacitively coupled switch that we have fabricated to date, with insertion loss of - 2.0 dB and isolation of - 18 dB at 18 GHz. In addition, the switches could be cycled repeatedly without change in performance or evidence of dielectric charging, which is very encouraging for the development of reliable, long-lifetime switches. Importantly, the technologies and approaches that we developed in this project are unique and exclusive to Sandia. They could support the research needs of other government agencies such as the Department of Homeland Security and the Defense Advanced Research Projects Agency (DARPA).

We developed a new laser annealing process that now permits the creation of stress-free aD films using an entirely room-temperature process.

...We made important developments in the fabrication and measurement of NEMOs. We fabricated unique structures consisting of arrays of in-plane NEMOs that have critical dimensions down to 50 nm and resonance frequencies up to several hundred megahertz.

Refereed

- Alam, T. M., T. A. Friedmann, P. A. Schultz, and D. Sebastiani. 2003. Low-temperature annealing in tetrahedral amorphous carbon thin films observed by ^{13}C NMR spectroscopy. *Physical Review B* **67**:245309-1–245309-11.
- Carr, D. W., J. P. Sullivan, and T. A. Friedmann. 2003. Laterally deformable nanomechanical zeroth-order gratings: Anomalous diffraction studied by rigorous coupled-wave analysis. *Optics Letters* **28**:1636–38.
- Chasiotis, I., S. W. Cho, T. A. Friedmann, and J. P. Sullivan. 2003. Mechanical properties of tetrahedral amorphous diamond-like carbon (ta-C) MEMS. *Proc. 2003 SEM Annual Conference and Exposition on Experimental and Applied Mechanics* (2–4 June, Charlotte, North Carolina).
- Chen, X., J. M. Gibson, J. P. Sullivan, and T. A. Friedmann. 2003. Fluctuation microscopy of medium-range ordering in amorphous diamond-like carbon films. *Applied Physics Letters*, submitted.
- Friedmann, T. A., J. P. Sullivan, R. V. Ellis, T. M. Alam, and T. E. Buchheit. 2002. Tetrahedral amorphous-carbon (ta-C) for MEMS applications. Paper presented at the 2002 AVS National Meeting, 4–8 November, Denver, Colorado.
- Friedmann, T. A., J. P. Sullivan, R. V. Ellis, T. M. Alam, T. E. Buchheit, and M. P. de Boer. 2002. Tetrahedral amorphous-carbon (ta-C): Materials properties and MEMS. Paper presented at the Fall 2002 Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.
- Friedmann, T. A., T. M. Alam, J. P. Sullivan, P. A. Schultz, R. V. Ellis, M. Parrinello, and D. Sebastiani. 2002. Structure and stress relaxation in ta-C studied by ^{13}C nuclear magnetic resonance. Paper presented at SMAC 2002—4th Specialist Meeting on Amorphous Carbon, 5–6 September, Barcelona, Spain.
- Friedmann, T. A., T. M. Alam, J. P. Sullivan, T. E. Buchheit, R. V. Ellis, and M. Mitchell. 2002. Stress relaxation mechanisms in tetrahedral amorphous-carbon for MEMS applications. Paper presented at Diamond 2002, 9–13 September, Granada, Spain.
- Sullivan, J. P., T. A. Friedmann, R. V. Ellis, and T. M. Schofield. 2002. Internal dissipation in amorphous diamond MEMS oscillators. Paper presented at the 2002 Fall Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.

38620

Continuous-Wave Intersubband Terahertz Sources

M. C. Wanke, R. J. Foltynowicz, S. Samora, G. A. Vawter, C. T. Fuller, A. V. Smith, J. L. Reno

There is a general lack of compact solid-state sources between 1 and 10 terahertz (THz), a challenging spectral region lying between optical devices at high frequencies and electronic devices at low frequencies. This region is of great technological importance for higher-bandwidth space-based and short-range terrestrial communications, atmospheric sensing, and near-object analysis for chem-bio sensing. While the last few years have seen significant advances and development in ultrashort-pulsed terahertz sources, many important applications require continuous-wave (CW) sources, which remain in their infancy. Sandia is examining two approaches toward terahertz generation based on intersubband transitions.

In the first, a quantum cascade (QC) laser simultaneously emits two mid-infrared (MIR) frequencies differing by a few terahertz. These are used to pump a nonlinear optical material to generate terahertz radiation via parametric interactions. As a specific example, we will examine difference frequency generation by three-wave mixing in a specifically engineered intersubband transition. In general, the efficiency of the frequency mixing increases with the pump power; thus, we will examine approaches to integrate the mixing material such that it shares the same waveguide as the QC laser, where the intracavity field strength is the strongest.

Our second approach is to pursue QC lasers that operate at terahertz frequencies. This is simpler than a mixing approach and has been demonstrated by other groups over the last year with operation wavelengths spanning 70–100 μm . However, they are more difficult to design and have reliability and reproducibility issues. Currently these lasers operate only at temperatures below 90 K and are expected not to operate at high temperatures. We are exploring designs for better performance, robustness, and reliability and are testing novel designs that may have potential for higher-temperature operation.

We achieved higher-performance MIR QC lasers. The performance enhancements included higher-temperature operation (200 K pulsed) and higher-power outputs than previously achieved. We currently are developing designs for running these lasers in single-mode operation, as compared to

There is a general lack of compact solid-state sources between 1 and 10 terahertz (THz), a challenging spectral region lying between optical devices at high frequencies and electronic devices at low frequencies. This region is of great technological importance for higher-bandwidth space-based and short-range terrestrial communications, atmospheric sensing, and near-object analysis for chem-bio sensing....Sandia is examining two approaches toward terahertz generation based on intersubband transitions.

the current multimode spectra. We improved the growth-rate stability to ensure reproducible well and barrier widths throughout the long molecular beam epitaxy (MBE) growth times required for long-wavelength QC lasers. In addition, we continue to improve the fabrication process to lower waveguide losses. We grew and fabricated and currently are characterizing several laser designs with multiple MIR and terahertz frequencies. We also significantly enhanced the design tools and characterization tools. We added more materials parameters and many scripts for automation to the laser design software. We also improved the data-acquisition software for more automation to improve characterization throughput, in conjunction with improvements to the measurement hardware. Finally, in response to the lack of material parameters known in the terahertz necessary for modeling the nonlinear materials for terahertz generation, we built a time-domain terahertz spectrometer to measure the material parameters.

38621

Microsystems for Chemical Signature and Reagent Delivery

R. J. Simonson, R. Kottenstette, H. Fan, S. M. Brozik, C. J. Brinker, R. P. Manginell, A. R. Straumanis, A. Robinson

Networked systems of low-cost, small, integratable chemical sensors will enable monitoring of nonproliferation and materials control (NMC) targets and chemical weapons threats. Sandia-designed prototype chemical-sensor systems are currently undergoing extended field testing supported by the Department of Energy and other government agencies. Use of autonomous chemical monitoring in homeland security and other high-consequence applications will demand a high level of system surety, which Sandia is uniquely positioned to provide. A required surety component will be verification of microanalytical system performance, which can be achieved by providing a programmable source of chemical signature(s) for autonomous calibration of analytical systems. In addition, such a controlled chemical source could be used to dispense microaliquots of derivatization reagents, extending the analysis capability of chemical sensors to a wider range of targets. Sandia plans to continue our development of microfabricated systems for controlled release of selected compounds (calibrants or derivatization reactants) into the analytical stream of microsensor systems. To minimize pumping and valve requirements of microfluidic systems, and to avoid degradation issues associated with storage of dilute solutions, we developed several candidate solid-phase reservoir materials that can be patterned onto arrays of thermally activated membrane devices. We demonstrated a useful solid-phase reservoir film that produces useful calibration signature vapors by decomposition of solution-deposited organic salts. We continue to investigate alternative deposition methods, including layered self-assembling silica films produced from aqueous phases at low temperature and incorporation of desired moieties into decomposable organic polymers, and solution-phase deposition of thermally decomposable organic salts. Our final goal for this project is the integration of the resulting microcalibration source arrays with Sandia's microfabricated gas-phase chemical-analysis systems.

We made a number of accomplishments this year.

- We fabricated 2 x 5 prototype arrays with both 1 x 1 mm and 2.2 x 2.2 mm active thermal elements.

Use of autonomous chemical monitoring in homeland security and other high-consequence applications will demand a high level of system surety, which Sandia is uniquely positioned to provide. ...Sandia plans to continue our development of microfabricated systems for controlled release of selected compounds (calibrants or derivatization reactants) into the analytical stream of microsensor systems.

- We designed, assembled, programmed, calibrated, and demonstrated an automated microdispenser system for reproducible coating of solid-phase reservoir films onto the active elements of prototype microcalibrator arrays.
- We evaluated deposition of reservoir films by automated spray coating through a shadow mask.
- We measured thermal coefficient of resistance (TCR) values for resistive heater and thermistor circuits on the prototype array devices, and determined TCR variance to ensure precise temperature control during desorption.
- We demonstrated reproducible temperature control of individually addressed desorption elements using dedicated computer-interfaced control circuits.
- We demonstrated thermally controlled reactive desorption of a useful calibrant compound (tributyl amine) from precursor-coated microfabricated thermal array elements.
- We determined the quantitative reproducibility of tributyl amine production from precursor-coated array elements.
- We verified that the variability of the desorption amplitude is strongly dependent on substrate surface termination chemistry prior to deposition of the precursor compound.
- We developed a substrate surface preparation procedure that provides for reproducible tributyl amine production with less than 2% relative standard deviation.

38622

Microfluidic Cellular Sample Pretreatment

C. D. James, S. M. Brozik, S. S. Mani, M. Okandan, M. Manginell, P. C. Galambos

Sandia refined the objectives for this project by broadening the scope of the project to increase the effectiveness of our proposed devices. We seek to produce a microsystem that can rapidly detect any biological agent at low concentrations, with the primary difficulty of developing such a system being the wide range of analytes (bacterial cells, viruses, and toxin molecules) that need to be handled, collected, and then detected. Another feature that will improve speed and flexibility is that the system should be able to detect multiple agents within a single sample simultaneously. In addition, having orthogonal assay capability (for instance, one assay for identifying external protein markers, and another for identifying deoxyribonucleic acid [DNA] sequences) is another feature that enhances detection specificity and reduces false positives.

Our strategy for addressing these concerns is to use microspheres as the bridge between nanometer-sized particles (DNA, toxins, antigens, etc.) and the micro-/mesoscale fluidic systems that we recently developed. We will use the microspheres as capture-and-carry tools for small-molecule detection assays. A new addition to this project is our proposed use of dielectrophoresis (DEP) to collect and separate the microspheres based on size and polarizability properties. Our previously defined goal of cell lysis using a microdevice is now further enhanced in that we have developed a strategy for capturing and concentrating target molecules from within the cell lysate. The tagged particles will provide the surface area and specificity for capturing minute quantities of antigens, DNA/ribonucleic acid [RNA] molecules, and internal protein markers. The particles, being large in comparison to the molecules, can then be collected and separated before being sent off for analysis. Finally, real-time polymerase chain reaction (PCR) with a commercially available system will be interfaced with our microdevice in the first step of genetic identification of a particular agent.

We focused on using DEP as a tool for concentrating and separating analytes such as cells and particles. Our intention is also to use DEP to separate target analytes, allowing the system to detect low concentrations of multiple agents using a single device. We successfully separated latex particles from a mixture of bacterial cells and particles. The nature of DEP affords rapid

Frequency-dependent dielectrophoresis of latex microspheres and bacteria. Upon changing the frequency and amplitude of the voltage, the microspheres are first released (100 kHz), followed by the bacteria (0 V).

separation, depending on the polarizability differences between the two constituents that are being separated. Analytes of roughly the same size can be separated quickly, as will be shown in the case of 1 μm latex particles and *Staphylococcus aureus* bacterial cells. By altering the frequency, we optimized the DEP force to provide rapid separation. In addition, we developed a novel method, termed *dielectrophoretic focusing*, to provide spatial separation of particles with similar polarizability properties but different sizes. We successfully separated 1 μm and 3 μm particles, and we developed a method for enhancing the separation through cycled application of phase-delayed fluid pressure and DEP. We also tested new schemes for integrating microfluidic chips to mesoscale fluidic systems using a flow manifold. Current testing shows that good seals between the chip and the manifold can be achieved with optimization of the coupling process. We currently are conducting sensitivity tests on our real-time PCR system to determine the detection limits of sample volume and DNA concentration. We are also examining the effect of surface modification on the DEP of the microspheres.

...we developed a novel method, termed dielectrophoretic focusing, to provide spatial separation of particles with similar polarizability properties but different sizes. We successfully separated 1 μm and 3 μm particles, and we developed a method for enhancing the separation through cycled application of phase-delayed fluid pressure and DEP.

Refereed

Bennett, D. J., B. Khusid, C. D. James, P. C. Galambos, M. Okandan, D. Jacqmin, and A. Acrivos. 2003. Combined field-induced dielectrophoresis and phase separation for manipulating particles in microfluidics. *Applied Physics Letters*, accepted.

Bennett, D. J., B. Khusid, P. C. Galambos, C. D. James, and M. Okandan. 2003. A dielectrophoretic particle and cell concentrator. Paper presented at the National Society of Black Engineers 29th National Convention, March, Anaheim, California.

Bennett, D. J., B. Khusid, P. C. Galambos, C. D. James, and M. Okandan. 2003. A dielectrophoretic particle and cell concentrator. *Transducers '03 Technical Digest, Proc. 12th International Conference on Solid-State Sensors, Actuators, and Microsystems* **1** (June, Boston, Massachusetts): 50.

Bennett, D. J., B. Khusid, P. C. Galambos, C. D. James, and M. Okandan. 2002. Manipulation of particles in microfluidic channels by means of traveling wave dielectrophoresis—Design, analysis, and experimental results. Paper presented at the Workshop on Electric and Magnetic Phenomena in Micro- and Nanoscale Systems, ASME Mechanical Engineering Congress, November, New Orleans, Louisiana.

Bennett, D. J., B. Khusid, P. C. Galambos, C. D. James, and M. Okandan. 2002. Manipulation of particles in microfluidic channels by means of traveling wave dielectrophoresis—Design and analysis. Paper presented at the Symposium on Electrohydrodynamics, 14th U.S. National Congress of Applied Mechanics, June, Blacksburg, Virginia.

James, C. D., D. J. Bennett, P. C. Galambos, and M. Okandan. 2003. Dielectrophoretic manipulation of analytes for biological assay applications. Paper presented at the 45th Electronic Materials Conference, June, Salt Lake City, Utah.

Okandan, M., P. C. Galambos, R. Manginell, C. D. James, S. S. Mani, and B. Draper. 2003. BioMEMS/microfluidics: Technology and devices. *Proc. Materials Research Society 2003 Meeting, Symposium N5.1* (April, San Francisco, California): 272.

52548

Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics

S. Y. Lin, P. G. Clem, W. W. Chow, J. R. Wendt, J. G. Fleming, G. S. Subramanian, I. F. El-Kay

Over the past 15 years, basic photonic crystals (PhCs) operating in optical wavelengths have been theoretically investigated and experimentally realized. New directions must now be set to understand fundamental photon-matter interactions and thus realize active photonic components for integrated and silicon (Si) photonics applications.

Sandia is focusing on three key areas in this project:

(1) Light-emitting and nonlinear switching in PhCs—an aspect of electron-photon interaction. We will design and implement new microcavity configurations. Also, we will implement new methods to introduce optical-gain media into a PhC for gain control and amplifier application.

(2) Optical interconnects—an aspect of photon-photon interaction. Silicon-on-oxide is a mature technology and compatible with layered two-dimensional (2-D) PhC design. We intend to build silicon-on-oxide-based optical components and study their mutual interaction for achieving complex optical functionality. Two examples are waveguide-cavity and cavity-cavity interaction for channel-dropping filter applications.

(3) Thermal emission of PhCs. By understanding the underlining photon-phonon interaction, blackbody radiation can be changed and wasted thermal energy recycled. We will report new findings that go beyond what the traditional thermodynamic law predicted.

Indeed, the next challenge in PhC research is in material integration, in on-chip integration of photonic components, and lastly, the realization of Si lasers.

We focused our research effort primarily on 3-D metallic PhC, as its radiation exhibits unusual and exciting properties that could impact our future energy applications and energy conservations. Meanwhile, we also achieved great success in realizing photonic components for optical-switching and optical-interconnect applications. This work led to two keynote speeches, two patents allowed, and one paper published.

(1) Observation of sharp emission near the band edge of 3-D metallic PhCs at 3.5–4.5 μm wavelength. We realized a 3-D tungsten (W) PhC with a photonic band edge at $\sim 4 \mu\text{m}$ wavelength. Its thermal emission is suppressed in the bandgap regime and, at the same time, exhibits sharp peaks near the band

...we also achieved great success in realizing photonic components for optical-switching and optical-interconnect applications. This work led to...two patents allowed,....

edge. We further observed that energy-conversion efficiency from one side of the sample reaches $\sim 40\%$. We attributed this finding to a complete metallic photonic bandgap (PBG) in the infrared (IR) and the enhanced density of photon states near the band edge of our W PhC.

(2) *Experimental realization of 3-D metallic PhC at near-IR (NIR) wavelength of 1.5 μm wavelength.* Our next effort is to reduce the emission wavelength of our PhC sample into NIR (1–2 μm wavelength) and eventually into visible (400–700 nm) wavelengths. An emission at 1.5 μm is an important first step for realizing highly efficient thermal photovoltaic (PV) electric generators. A gallium antimonide (GaSb) PV cell used for this application has a wavelength cutoff at 1.7 μm .

(3) *Experimental realization of PBG y-splitters and a high-Q (high-quality) PBG microcavity.* We report the successful experimental realization of a PhC y-splitter, operating at $\sim 1.6 \mu\text{m}$. Our device has a large splitting angle of 120 deg a miniaturized size of $\sim (3 \times 3) \text{ mm}^2$, and y-splitter loss of (0.5–1) dB at 1640–1680 nm, making it promising for integrated photonic-circuit applications. We also successfully realized a high-Q microcavity operating at 1517 nm using a 2-D PhC slab approach. With this accomplishment, we are now ready to explore nonlinear material coatings for electrooptical-switching experiments.

We report the successful experimental realization of a PhC y-splitter, operating at $\sim 1.6 \mu\text{m}$ We also successfully realized a high-Q microcavity operating at 1517 nm using a 2-D PhC slab approach.

Refereed

Lin, S. Y. 2003. Photonic bandgap effect in layer-by-layer metallic photonic crystals. *J. Applied Physics* **93**:38.

Lin, S. Y., E. Chow, and J. Bur. 2003. Low-loss, wide-angle Y-splitter at 1.6-micrometer wavelengths built with a two-dimensional photonic-crystal. *Optics Letters* **27**:1400–402.

Lin, S. Y., J. G. Fleming, and I. F. El-Kady. 2003. Experimental observation of photonic-crystal emission near a photonic band edge. *Applied Physics Letters* **83**:593–95.

Lin, S. Y., J. G. Fleming, Z. Y. Li, I. F. El-Kady, R. Biswas, and K. M. Ho. 2003. Origin of absorption enhancement in a tungsten, three-dimensional photonic crystal. *J. Optical Society of American B* **20**:1538–41.

Lin, S. Y., J. Moreno, and J. G. Fleming. 2003. Three-dimensional photonic-crystal emitter for thermal photovoltaic power generation. *Applied Physics Letters* **83**:380–82.

52549

Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia's MDL and BAE Systems

J. D. McBrayer, R. D. Nasby, R. S. Bennett, R. S. Flores, D. J. Savignon, T. A. Hill, B. K. Smith, R. McFarland, B. L. Draper

Radiation-hardened nonvolatile chalcogenide random-access memories (C-RAMs) represent a revolution in capability for nuclear-circumvention, program-storage, and satellite-application system designers. This technology provides an inherently radiation-hardened memory cell, since the recall information is not based on stored charge but rather on a physical phase transition. It offers read speeds and densities approaching commercial DRAM (dynamic random-access memory). It needs no refreshing and operates at voltages competitive with commercial microelectronics.

C-RAM uses the physical phase-change properties of a germanium antimony tellurium (GeSbTe) chalcogenide alloy as the means of storing information. The information is written by changes in resistance due to current-induced controlled-phase transitions of the chalcogenide material. The polycrystalline state (low resistance) provides the "zero," and the amorphous state (~ 1000x greater resistance) provides the "one."

Creating these devices by co-processing between Sandia's Microelectronics Development Laboratory (MDL) and BAE Systems will provide Sandia with direct knowledge of the potential of chalcogenide technology. This project will accelerate the development of C-RAM for immediate use in enhanced remote sensing and other defense initiatives.

We signed a nondisclosure agreement (NDA) that allowed BAE Systems to provide Sandia with the necessary information to design C-RAM prototype devices.

We completed test and evaluation of the C-RAM test structures fabricated by BAE Systems. Early Sandia results did not match the results, on the same devices, made by BAE Systems. These discrepancies were caused by minor differences in the setup of the testers at each organization. This experience reveals the sensitivity of C-RAM devices. This sensitivity, in part, is the reason why this nonvolatile technology has such a high potential in providing designers with a technology that will allow many new systems.

In general, the test results were more positive than originally expected, such that we are designing a more-

Creating these devices by co-processing between Sandia's Microelectronics Development Laboratory (MDL) and BAE Systems will provide Sandia with direct knowledge of the potential of chalcogenide technology. This project will accelerate the development of C-RAM for immediate use in enhanced remote sensing and other defense initiatives.

aggressive prototype device. The design will be completed in future work.

We also completed the extraction of device and design parameters, the test-structure evaluation, and the documentation of Sandia's most advanced silicon-on-insulator (SOI) radiation-hardened complementary metallic-oxide semiconductor (CMOS) technology, which we will use as the front-end CMOS processing for the C-RAM prototype. In addition, we successfully converted BAE Systems' design information into Sandia's design tools.

We also completed the extraction of device and design parameters, the test-structure evaluation, and the documentation of Sandia's most advanced silicon-on-insulator (SOI) radiation-hardened complementary metallic-oxide semiconductor (CMOS) technology,....

52551

Functionalized Nanoparticles for Sensor Applications

D. R. Wheeler, R. J. Simonson, M. G. Blain, S. W. Howell, S. M. Dirk, K. D. Childs

Sandia will functionalize nanoparticles with short conducting molecules that will contain sensing functionalities that will modulate their conductivity based on their interaction with analytes. We will assemble these functionalized nanoparticles into nanogaps for generated nanosized sensors. We will design these nanogap sensors based on functionalized nanoparticles for the fabrication of arrays of sensor elements.

This project consists of a number of different elements to enable the use of functionalized nanoparticles for sensor applications. The first requirement is the appropriately functionalized nanoparticle. The second is a method to assemble the particles. The third requirement is the generation of a nanogap to contain the nanoparticles.

The functionalized nanoparticles will contain two types of ligands. The first is a short nonconjugated molecule similar to agents currently used. The other will be bifunctionalized to bridge two nanoparticles and biconjugated to dominate conduction between particles. Therefore, the bridging ligand will dramatically affect the conductivity of the nanoparticle assembly. Additionally, the use of bifunctional ligands will generate a cross-linked network of particles that will be exceptionally stable.

The methodology to assemble the nanoparticles is two-pronged. The first relies on our new sacrificial ligands on the nanoparticle. The sacrificial ligands will allow nanoparticles to be generated and purified with a coating that can be replaced with the desired ligands before, during, or after their introduction into the nanogap. The second assembly method relies on the demonstrated technique of alternating current (AC) trapping followed by in situ stabilization.

We will fabricate the nanogap arrays in two different methods relying on Sandia's nanofabrication expertise. The first method relies on the use of a sacrificial thin oxide between two electrodes. The second method will employ controlled evaporation of metal between two overlapping, but not touching, electrodes.

We made progress in nanoparticle synthesis, ligand synthesis, nanogap fabrication, infrastructure for testing, and collaborations. We synthesized the bridging ligands for the

Sandia will functionalize nanoparticles with short conducting molecules that will contain sensing functionalities that will modulate their conductivity based on their interaction with analytes.... We will fabricate the nanogap arrays in two different methods relying on Sandia's nanofabrication expertise.

control experiments (no sensing elements). We are nearly finished with the ligands containing elements for sensing nerve agents. Additionally, we generated a series of molecules that will allow us to functionalize surfaces for nanoparticle attachment. The chemistry that we developed is unique and will have far-reaching consequences.

We synthesized nanoparticles with sacrificial ligands. This allows us to synthesize charge-free nanoparticles unlike those used in previous work. We assembled cross-linked arrays of particles using commercial bridging ligands and demonstrated their sensing ability. We made nanoparticles of both platinum and gold. We made sacrificial ligands from amines and nitriles. We replaced the sacrificial ligands with isocyanides and thiols to generate more stable arrays. We have begun to understand the chemistry of the replacement process. We assembled structures and characterized them by atomic-force microscopy (AFM).

We collaborated with a molecular-electronics group at Rice University (RU) to generate nanogaps with electrode spacing between 20 Å and 15 nm. We began electrical characterization of the gaps. We began fabricating a Sandia-designed nanogap device that may have improved the electrical characteristics. Lastly, we have been proving our ideas and approaches using mesogapped electrodes on the micron-size scale. Our work with RU also leverages for molecular electronics.

Finally, we began to characterize a series of nanogaps (40–70 nm) from Sandia-California's Extreme Ultraviolet Lithography (EUVL) Program. We developed the infrastructure to truly drive our project. We built probe stations with time-gated delivery of analytes. We began impedance spectroscopy and IV measurements on nanoparticle arrays on mesogaps and demonstrated that we can build macroscopic devices similar to those of other researchers. Our work generated a number of leveraged interactions. These include our invited collaboration on two Defense Advanced Research Projects Agency (DARPA) molecular-sensing proposals and a significant collaboration with RU.

The chemistry that we developed is unique and will have far-reaching consequences.

Other Communications

Dirk, S. M., S. W. Howell, M. G. Blain, R. J. Simonson, and D. R. Wheeler. 2003. Chemical sensor applications of molecular electronics. Paper presented at the Gordon Research Conference on Chemistry of Electronic Materials, 13–18 July, Connecticut College, New London, Connecticut.

52552

Novel *In Situ* Mechanical Testers to Enable Integrated Metal Surface Micromachines

S. J. Hearne, C. W. Dyck, P. G. Kotula, M. P. De Boer, S. M. Foiles, T. E. Buchheit, D. M. Follstaedt

The ability to integrate metal and semiconductor microsystems to perform highly complex functions, such as radio-frequency microelectromechanical systems (RF MEMS), will depend on developing free-standing metal structures that offer improved conductivity, reflectivity, and mechanical properties. Three issues have prevented the proliferation of these systems: (1) warpage of active components due to through-thickness stress gradients, (2) limited component lifetimes due to fatigue, and (3) low yield strength. To address these issues, Sandia is focusing on developing and implementing techniques to enable the direct study of the stress and microstructural evolution during electrodeposition and mechanical loading. We are accomplishing the study of stress during electrodeposition of metal thin films by integrating a multibeam optical stress sensor (MOSS) into an electrodeposition chamber. By coupling the in situ stress information with ex situ microstructural analysis, we will obtain a scientific understanding of the sources of stress during electrodeposition. These results are providing a foundation upon which to develop a stress-gradient-free thin film directly applicable to the production of free-standing metal structures. We are addressing the issues of fatigue and yield strength by developing novel surface-micromachined (SMM) tensile and bend testers by interferometry and transmission-electron microscope (TEM) analysis. The MEMS tensile tester has a Bosch-etched hole to allow for direct viewing of the microstructure in a TEM before, during, and after loading. This approach allows for the quantitative measurement of stress-strain relations while imaging dislocation motion, and for the determination of fracture nucleation in samples with well-known fatigue/strain histories. This technique facilitates the determination of limits for classical deformation mechanisms and helps to formulate a new understanding of the mechanical response as the grain sizes are refined to a nanometer scale. These studies will result in a science-based infrastructure to enhance the production of an integrated metal-semiconductor system that will directly impact RF MEMS and LIGA (the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) technologies at Sandia.

These studies will result in a science-based infrastructure to enhance the production of an integrated metal-semiconductor system that will directly impact RF MEMS and LIGA (the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) technologies at Sandia.

We made significant progress toward understanding the mechanisms that control stress evolution during electrodeposition of nickel (Ni) films and also toward developing a fundamental understanding of the mechanisms that control fatigue and yield in nanostructured materials.

- *MEMS tensile testing.* An important aspect of the project is to demonstrate a new MEMS device for measuring tensile and fatigue properties of materials used in MEMS. The ultimate goal is to quantify these material properties to unprecedented accuracy while performing TEM analysis of the evolving microstructure. We achieve this quantification by applying strain with precise control. We evaluated two separate processing approaches to make the MEMS device for aluminum-film analysis. Results from these evaluations identified and resolved processing issues for both approaches, and we anticipate the fabrication of fully integrated test structures from both processes.

- *Stress measurements during electrodeposition.* We fabricated an electroplating cell with an *in situ* stress sensor, which allowed for real-time stress measurement during electrodeposition. The system to characterize the stress evolution during Ni electrodeposition forms a process that is identical to that used in both RF MEMS and LIGA technologies at Sandia. This work demonstrated that a correlation exists between intrinsic stress and the plating rate. We also began a study of the stress-created coalescence of Ni islands. All previous attempts to measure the island-coalescence stress in Ni and all other materials to date have been hampered by the stochastic nucleation of islands, which causes both the coalescence event to be spread out temporally and the islands to be of irregular size and geometries. Using controlled nucleation, we conclusively demonstrated that the functional dependence of the stress on island size and dimensionality is consistent with a Hertzian contact model.

- *Tensile test sample.* We also performed an investigation into the use of other test vehicles for tensile and bend testing. This work culminated in the development of a tensile-testing structure vertically actuated using a nanoindenter, done in collaboration with MTS System Corporation. The structure is a lithographically patterned metal film stretched across a Bosch-etch hole. The nanoindenter then deflects the beam downward and measures the stress-strain response by applying a force in the center of the beam.

- *Fatigue-property testing methodologies.* We worked on developing the basic components for *in situ* fatigue and creep testing. We implemented phase-shifting interferometry (PSI) on

We made significant progress toward understanding the mechanisms that control stress evolution during electrodeposition of nickel (Ni) films and also toward developing a fundamental understanding of the mechanisms that control fatigue and yield in nanostructured materials.

our long-working-distance interferometer. The PSI algorithms enable full-field deflection calculations across continuous structures. This technique can be transferred easily to a recently constructed ultrahigh-vacuum (UHV) chamber capable of elevated temperature actuation. Integrating these components will be straightforward and will enable us to collect near-real-time displacement data (< 1 s) to implement fatigue and creep testing.

- *Correlate stress evolution during electroplating to microcantilever curvature.* We made advances in comparing the curvature observed during Ni electrodeposition to that of free-standing microcantilevers. We electroplated macroscopic samples from a standard sulfamate bath used for fabrication of RF MEMS devices in the stress-sensor plating cell described above and compared these samples to microcantilever samples plated under identical plating conditions. Initial results indicate that there is good agreement between the macroscopic unpatterned films and the microcantilevers, even with highly complex stress profiles.

Other Communications

Hearne, S. J., J. A. Floro, C. W. Dyck, T. Christenson, D. Dibble, J. Kelly, W. Fan, and S. Brueck. 2003. Stress evolution during electrodeposition of Ni. Paper presented at MRS, April, San Francisco, California.

Hearne, S. J., J. A. Floro, C. W. Dyck, T. Christenson, W. Fan, and S. Brueck. 2003. Stress creation during island coalescence of thin films. Paper presented at AVS, May, Albuquerque, New Mexico.

52553

Compliant Thermomechanical MEMS Actuators

M. S. Baker, J. L. Dohner, T. J. Headley, R. A. Plass, K. A. Klody

Surface-micromachined (SMM) thermal actuators have been demonstrated to provide a 100x higher output force and 10x lower actuation voltage than the traditional electrostatic actuators typically used in microelectromechanical systems (MEMS). Additional advantages include high yield, stictionless motion, and smaller consumed area on the wafer. Sandia seeks to develop a predictive modeling capability that will enable the design of thermal actuators that overcome the disadvantages associated with high power consumption while continuing to provide an order-of-magnitude-higher force output and improved displacement characteristics than their electrostatic counterparts. In addition, we will conduct a science-based study of the reliability and predictability of thermally activated MEMS structures after repeated thermal cycling. This study will be broadly applicable to any thermal MEMS device.

We focused on model development and actuator design for both single- and double-staged electrothermal actuators, as well as for single-staged optothermal actuators. The nonlinear thermal and mechanical nature of these actuators complicates device modeling, requiring customized codes and nonlinear finite-element (FE) techniques. In future work, we will focus on assessing the reliability of the fabricated devices, including the effects of the elevated temperatures, thermal cycling, and humidity on the polysilicon (poly-Si) material properties over time; we will also test fatigue and lifetime reliability of the devices.

Thermal actuation has the potential to meet the high-force, low-voltage actuation requirements for MEMS and to meet a broad range of Strategic Business Unit needs. The advantages and the potential reliability enhancements associated with thermal actuation also add value to the nuclear weapons (NW) applications such as the W80 project, specifically in the area of flight-system-compatible radiation-hardened mechanical nonvolatile memories and other critical weapon-reserve (WR) components.

Our goals focused primarily on developing a parametric model of an SMM poly-Si thermal actuator. We completed this model using a custom heat-transfer analysis written in MATLAB to solve the thermoelectric portion of the problem, and then coupled the model to a nonlinear finite-element (FE)

Sandia seeks to develop a predictive modeling capability that will enable the design of thermal actuators that overcome the disadvantages associated with high power consumption while continuing to provide an order-of-magnitude-higher force output and improved displacement characteristics than their electrostatic counterparts. ...The advantages and the potential reliability enhancements associated with thermal actuation also add value to the nuclear weapons (NW) applications....

solution to solve the mechanical problem. We also extended this model to apply to optothermal actuators, where the heat is supplied by laser radiation rather than from Joule heating due to an applied current. Preliminary test results compare well with modeled predictions, and we will conduct additional experiments to further improve model accuracy and enable reliable predictive modeling of the actuator. We submitted a module of actuator designs with test structures to measure actuator displacement and output force as a function of the geometry and input power through the SAMPLES program for fabrication in the Sandia Ultraplanar Multilevel MEMS Technology V (SUMMiT-V™) process. The module is available for characterization.

We also began reliability studies on previously fabricated thermal actuators. We will use the results from these initial discovery experiments to develop a more-detailed test matrix for in-depth reliability studies that will be conducted in upcoming work. Reliability testing of thermal actuators required a significant modification to the existing test equipment, as this equipment was originally intended to be used for electrostatic-actuator characterization at high voltages and very low currents. This modification is under way and will provide a test-bed for future in-depth characterization.

52554

An Integrated, Stacked System-on-a-Chip

R. Chanchani, T. A. Fischer, C. W. Ottesen, M. E. Warren, D. Bethke, D. W. Peterson, K. Norman, D. J. Rieger, G. D. Peterson, B. A. Brunett

In a miniaturized microsystem, the major difficulty is in integrating different device technologies in a small volume. In this project, Sandia proposed a unique concept to integrate different device technologies by stacking wafers in three dimensions. The final product will be a fully integrated system-on-a-chip, including passive and active devices made of different technologies. The uniqueness of this concept is (1) in the use of benzocyclobutene (BCB) as a “glue” layer between wafers, which will allow us to incorporate interconnect structure and embedded passives within the “glue” layer; and (2) in the use of through-hole vias with a lower aspect-ratio obtained by thinning the top wafer (20–125 μm thick). A lower-aspect-ratio via will make electrical connections between wafers easier to fabricate and more reliable.

We resolved the conceptual issues relating to yields and stacking wafers of varying die sizes. Next, we developed the following processes:

- (1) Thinning wafers to 110 μm*
- (2) Bonding two silicon (Si) wafers using 5 μm -thick BCB as the “glue” layer*
- (3) Fabricating vias ranging in size from 75 μm to 750 μm using Bosch-etching and laser-drilling methods*
- (4) Demonstrating the concept to precisely separate dies in a wafer by dry etching the streets.*

For future work, we propose to thin wafers to less than 50 μm and stack them, and to insulate and metallize vias to make a complete two-wafer, electrically functioning stack.

(1) We had several technical discussions and resolved the conceptual issues relating to yields and stacking dies of varying die sizes. We then presented these issues and their resolution.

(2) We developed processes for wafer thinning, wafer bonding, and fabrication of vias in parallel.

- We demonstrated the wafer thinning and handling of wafers to a thickness of 110 μm . The wafers were thinned at a vendor facility. Our process to handle thinned wafers, although developed using 110 μm -thick wafers, will also potentially handle thinner wafers (< 50 μm). A process to attach a wafer to a glass carrier and then cleanly debond the carrier wafer after wafer thinning was a significant development.

...Sandia proposed a unique concept to integrate different device technologies by stacking wafers in three dimensions. The final product will be a fully integrated system-on-a-chip, including passive and active devices made of different technologies.

- We successfully demonstrated bonding of two Si wafers using BCB as a glue layer. The main issues were air voids, which we eliminated by specially developed techniques.
 - We made vias ranging in size from 75 μm to 750 μm using Bosch-etching and laser-drilling techniques.
 - We demonstrated the precise separation of dies in a wafer by dry etching the streets.
- (3) We are combining the individual processes developed earlier to make a two-wafer stack.

52555

Micromass Spectrometer-on-a-Chip

M. G. Blain, R. L. Jarecki, Jr., K. L. Linker, K. O. Wessendorf, R. S. Bennett, D. Cruz, D. E. Austin

Breakthrough improvements in microsensors for high-consequence applications, including chemical/biological warfare agents, medical diagnostics, and explosives detection, will be realized only with the development of ultrasensitive and ultrasensitive microfabricated detectors that are able to unambiguously identify the compound of interest. A micron-scaled mass spectrometer (MS)-on-a-chip would set the performance standard for such microdetectors. For example, the combination of a microgas-chromatograph (micro-GC) separation column with a micromass-spectrometer (micro-MS) detector, i.e., a micro-GC/MS, would provide an extremely sophisticated capability for specific and unambiguous molecular identification, which is not currently available. A micro-MS could also serve as a stand-alone microanalytical system in its own right. While the effort to develop a complete micro-MS system must address sample introduction, ion source, mass analyzer, ion detector, vacuum, and power subsystems, Sandia is focusing on the development of the mass-analyzer portion of the spectrometer and has simulated the operation of and begun the microfabrication of a 2 cm² prototype mass analyzer consisting of an array of massively parallel (MP), micron-sized cylindrical ion traps (CITs) fabricated on a silicon substrate. The analyzer was designed with an integrated ion detector and has the theoretical mass range for detecting biomolecules and their derivatives. We collaborated with Purdue University to define the operating protocol of an MP chip-sized array of mass analyzers with integrated ion-collection plate by operating the protocol with a laboratory-scale ion source, and vacuum and power-delivery systems at Purdue.

We initiated the design, simulation, and prototype microfabrication of a chip-based mass analyzer consisting of an array of MP, micron-sized CITs with an integrated ion detector. We simulated the ion-trapping characteristics and performance of an $r_0 = 1$ mm CIT. The trap geometry terms, including end-cap thickness, end-cap- to ring-electrode spacing, and end-cap and ring-electrode thickness, were varied within the constraints of processing feasibility to elucidate the appropriate trap structure. We used trap operating radio-frequency (RF) voltage and frequency as input boundary conditions. We calculated ion

Sandia is focusing on the development of the mass-analyzer portion of the spectrometer and has simulated the operation of and begun the microfabrication of a 2 cm² prototype mass analyzer consisting of an array of massively parallel (MP), micron-sized cylindrical ion traps (CITs) fabricated on a silicon substrate.

trajectories and time-dependent electric fields using SIMION and the Purdue-developed ITSIM simulation packages. Using the simulation results, a mask set for fabricating a prototype trap array at Sandia's Compound Semiconductor Research Laboratory (CSRL) was designed, ordered, and delivered. Fabrication of a prototype array of traps was completed, and a self-aligned trap geometry was defined in alternating layers of aluminum and silicon dioxide. Poor profile control of the trap electrode surfaces, however, prompted a redesign of the process flow to take advantage of Sandia's Microelectronics Development Laboratory (MDL) and photonic lattice technology. We began processing the redesigned prototype using molded tungsten process technology to define the ion-trap components, including the ring electrode, lower and upper end-cap elements, and ion-collection plate. Initial test protocols for the prototype CIT array were developed at Purdue University's Aston Lab for research in MS. In collaboration with Purdue University, we initiated design of the RF waveform and timing diagrams necessary for testing of the prototype analyzer.

52556

Quantum Coherence in Semiconductor Nanostructures for Improved Lasers and Detectors

R. M. Biefeld, S. K. Lyo, N. A. Modine, D. A. Serkland, J. G. Cederberg, H. C. Schneider, W. W. Chow, R. J. Foltynowicz, E. L. Blansett, S. R. Kurtz, M. C. Phillips

Advances in atomic physics have led to the demonstration of “lasing without inversion” (LWI). This novel phenomenon has brought worldwide attention, but to date has been observed only in atomic beams and doped insulators. LWI can occur when the system is quantum coherent (QC)—when scattering is sufficiently absent that carriers’ wave functions retain memory of their phase. Wave-function coherence and interference can be used to generate a variety of optical phenomena, including LWI, electromagnetically induced transparency (EIT), dark-state spectroscopy, “slow light,” and “stopped light.”

We made advances on all efforts toward observing and manipulating coherent phenomena in semiconductor quantum dot (QD) structures. Our theoretical effort produced a microscopic theory of QC effects in semiconductor QDs that are coupled to continuum states in a quantum well (QW). This model predicts that LWI and EIT should be observed for dephasing rates of $2 \times 10^{-12} \text{ s}^{-1}$, typical of what has been observed at room temperature and under high-excitation conditions for semiconductor QDs.

Experimentally, we generated QDs with emission at 1.33 eV. The QDs show inhomogeneous broadening of 20 meV at room temperature, comparable to the state of the art for similar structures. Electron microscopy measurements show that the indium gallium arsenide (InGaAs) QDs have diameters of 20 nm and heights of 2 nm, in agreement with simulations of the laser-gain spectra. We developed the capability to form stacks of QDs without sacrificing the optical properties observed for single layers of QDs. This will be necessary to produce samples with sufficiently high QD concentrations to observed coherence effects. We demonstrated lasing from optically pumped InGaAs QDs at room temperature under pulsed excitation of a mode-locked titanium:aluminum oxide (Ti:Al₂O₃) laser. Studies of the lasing spectrum and threshold power on experimental parameters (i.e., pump wavelength, excitation power, operating temperature, and laser design) provided insight on optical gain of QD active regions. These results suggest that the QDs are of sufficient quality to serve as a model system to study coherence

We made advances on all efforts toward observing and manipulating coherent phenomena in semiconductor quantum dot (QD) structures. Our theoretical effort produced a microscopic theory of QC effects in semiconductor QDs that are coupled to continuum states in a quantum well (QW).

effects. Demonstration of a conventional QD laser is also an important milestone toward developing LWI in semiconductor heterostructures. We prepared the necessary optical equipment. Initial experiments indicate that transient absorption attributed to the QD active region exists at room temperature. This is a major step toward observing coherence effects experimentally.

The theoretical development narrows the experimental conditions under which LWI and EIT can be observed. We will extend our theory to investigate carrier transport in electronically coupled systems. We will develop a microscopic treatment of dephasing to improve the model. We will perform measurements of the energy-transfer rate among carriers in an electrically coupled system such as QDs stacked on QWs and coupled QDs. These experiments will allow further model refinement. We will grow specific samples for EIT and energy-transfer experiments. We will pursue growth of QD active regions emitting at the technologically important wavelengths of 1.3 and 1.55 μm . We will develop electrically injected lasers at 0.98, 1.3, and 1.55 μm to characterize QD active regions for future experiments to observe LWI.

Demonstration of a conventional QD laser is also an important milestone toward developing LWI in semiconductor heterostructures. We prepared the necessary optical equipment. Initial experiments indicate that transient absorption attributed to the QD active region exists at room temperature. This is a major step toward observing coherence effects experimentally.

Refereed

Chow, W. W., H. C. Schneider, and M. C. Phillips. 2003. Theory of quantum coherence phenomena in semiconductor quantum dots. *Physical Review A*, accepted.

Cederberg, J. G., F. H. Kaatz, and R. M. Biefeld. 2003. The impact of growth parameters on the formation of InAs quantum dots on GaAs(100) by MOCVD. *J. Crystal Growth*, accepted.

Other Communications

Cederberg, J. G., F. H. Kaatz, and R. M. Biefeld. 2003. Optical and structural properties of InAs, InAsSb, and InGaAs quantum dot active regions grown by MOCVD. Paper presented at the 39th Symposium of the American Vacuum Society (AVS), New Mexico Chapter, 29–30 April, Albuquerque, New Mexico.

Phillips, M. C., J. G. Cederberg, H. C. Schneider, and W. W. Chow. 2003. Gain characteristics of quantum dot lasers: Experiment and theory. Paper presented at Frontiers in Optics/Laser Science XIX, 5–9 October, Tucson, Arizona.

52557

MOSFET–MEMS Integration

B. L. Draper, R. J. Huber, J. B. Stanley, M. B. Sinclair, G. S. Rightley, K. B. Pfeifer, M. Okandan, A. H. Hsia, S. S. Mani

Many micromechanical systems would benefit from having on-chip electronic devices for sensing, signal conditioning, logic, and/or for driving the mechanical devices. Sandia's Polychromator, a programmable diffraction grating that will be the heart of a new holographic correlation radiometry system, is a good example of such a system. If on-chip logic and line drivers were available, the number of wire bonds to the Polychromator could be reduced from nearly 1100 to fewer than 20. System size, complexity, and reliability would be greatly enhanced. There are also many potential applications in mirror arrays and biomicroelectromechanical systems (bio-MEMS) applications, where on-chip amplification of extremely small electrical signals is essential to the success of the system.

We demonstrated the ability to use Sandia Ultraplanar Multilevel MEMS Technology V (SUMMiT-V™) to fabricate electronic devices simply and with very few additional processing steps compared to a MEMS-only technology. We developed the technique to include a wide variety of transistor styles with more processing latitude, explored the process and design limits, greatly extended the voltage range, fabricated some simple integrated MEMS, and began to develop process and electrical models.

While the first year of the project was primarily dedicated to the investigation of device physics and limitations, the work in the second year was chiefly circuit design. We began the design of a new test chip containing a wide variety of digital and analog circuits that will contribute to our knowledge of on-chip sensing and control of complex MEMS.

Through a series of experiments in Sandia's Microelectronics Development Laboratory (MDL), we extended the operation of the transistors from 10 V to about 80 V. We showed that dielectric degradation is not an insurmountable problem with the process, and we built devices with a wide range of designs and process parameters using the full SUMMiT-V™ process flow.

We accomplished high-voltage operation through the combination of several changes to the process flow. Low substrate-doping concentrations and diffused junctions with large radii of curvature gave us junction breakdowns of about 80 V. Thickening the gate oxide from 12 to 100 nm improved its

We demonstrated the ability to use Sandia Ultraplanar Multilevel MEMS Technology V (SUMMiT-V™) to fabricate electronic devices simply and with very few additional processing steps compared to a MEMS-only technology.

breakdown voltage to nearly 80 V. Finally, modifying the transistor's geometry reduced the probability of failure due to impact ionization from energetic electrons.

One of our early concerns was over the potential of gate-dielectric degradation due to dopant diffusion or physical damage at the extremely high MEMS-processing temperatures. However, secondary ion mass spectrometry (SIMS) analysis revealed little or no dopant intrusion, and electrical tests showed that the gate oxide is still a fairly good insulator at the end of the SUMMiT-V™ process.

Using a new dedicated test chip, we verified that we can use space-saving linear transistor layouts instead of large annular devices. Secondly, we explored the trade-offs between processing and device geometry. Finally, we demonstrated the use of the full SUMMiT-V™ process flow to make a small integrated system combining semiconductor field-effect transistors (SFETs) and mechanical components.

We received a patent for the basic semiconductor SFET process. We filed a patent application for the SFET device architecture and submitted a technical advance for extending the operation to high voltages. We presented data at the Spring 2003 Materials Research Society Meeting and submitted a full paper to the *IEEE Journal of Microelectromechanical Systems*.

We received a patent for the basic semiconductor SFET process. We filed a patent application for the SFET device architecture and submitted a technical advance for extending the operation to high voltages.

Refereed

Okandan, M., P. Galambos, R. Manginell, C. James, S. S. Mani, and B. L. Draper. 2003. BioMEMS/microfluidics: Technology and devices. *Proc. Materials Research Society 2003 Spring Meeting, Symposium N5.1* (21–25 April, San Francisco, California.): 272.

52566

Microoptical Gyroscope Via Monolithic Active/Passive Optical Integration

R. D. Kinney, G. A. Vawter, W. J. Zubrzycki, G. M. Peake, J. J. Hudgens, J. R. Wendt, J. G. Fleming, J. Guo, F. B. McCormick, M. J. Shaw

Technological progress in some weapon application areas is dependent on the availability of small, rugged, accurate gyros ($\sim 10^\circ/\text{hr}$ bias uncertainty). Examples include future W87 joint test assemblies (JTAs) that require inertial systems with volumes of a few cubic inches to minimize impact on weapon-system dynamics. The sensor must withstand re-entry environments, yet its accuracy must be sufficient to allow reconstruction of trajectory without the use of range assets, e.g., radar stations.

Industry has adopted optical gyros due to their superior reliability and lower cost. However, attempts to miniaturize optical gyros have been thwarted from lack of suitable microoptical components and monolithic optical integration know-how. Sandia developed the individual photonic components necessary for a resonant microoptical gyro (RMOG), an aluminum gallium arsenide (AlGaAs) distributed Bragg reflector (DBR) laser, a GaAs phase modulator, and a GaAs photodiode detector. The remaining challenge is monolithic integration of these components on a chip. Previous active/passive devices used silicon (Si) optical bench techniques for integration. We seek more comprehensive integration, where active and passive components are fabricated on a single chip. Monolithic integration will increase device ruggedness, reduce manufacturing complexity, and eliminate optical losses from alignment errors. We will couple this chip with a low-loss, multiloop, Si oxynitride (SiON) waveguide resonator to produce a high-performance RMOG.

The project goal is to demonstrate an RMOG produced from a monolithic photonic integrated circuit coupled with a Si nitride (Si_3N_4) waveguide resonator.

Work on the distributed-feedback (DFB) laser as a monochromatic light source integrated into the GaAs photonic chip has proceeded through design, fabrication, and testing of the first-generation device and design completion of the second-generation laser. We configured the first-generation laser after an existing non-DFB laser to improve the grating etch and the regrowth learning curve. Although the first laser performed poorly, we were successful in understanding a

Sandia developed the individual photonic components necessary for a resonant microoptical gyro (RMOG), an aluminum gallium arsenide (AlGaAs) distributed Bragg reflector (DBR) laser, a GaAs phase modulator, and a GaAs photodiode detector. The remaining challenge is monolithic integration of these components on a chip.

number of previously unknown process issues. With this new information, we completed a new design for a laser carefully tailored to the needs of this project. The remainder of the GaAs photonic-chip development focused on designs for integrated phase modulators, photodiodes, interconnecting optical waveguides, and the process technology needed to build these components on a single chip. We completed designs and also considerable process development. We identified a key challenge in the techniques used to include both optically active (i.e., capable of generating or absorbing light) and optically passive (i.e., transparent) devices on a single chip. The technique, impurity-free vacancy diffusion, employs critical surface-preparation steps. We found the commonly published steps seen in the literature to be unreliable. We identified a new method of vacancy diffusion and are poised to use this method in upcoming work.

We completed the silica planar lightwave circuit (PLC) second-generation design and fabrication. This includes an optimized gyro loop and many test structures intended to yield important information about optical losses as a function of wavelength and structure size. In addition, we completed an elaborate matrix of process adjustments that we expect to point to the best process steps for low-loss waveguides fabricated in these materials.

We identified a new method of vacancy diffusion and are poised to use this method in upcoming work....We completed the silica planar lightwave circuit (PLC) second-generation design and fabrication....we completed an elaborate matrix of process adjustments that we expect to point to the best process steps for low-loss waveguides fabricated in these materials.

52570

Materials Physics and Device Development for Improved Efficiency of GaN HEMT High-Power Amplifiers

D. D. Koleske, D. M. Follstaedt, A. A. Allerman, S. R. Kurtz, A. F. Wright, N. A. Missert, C. H. Seager, C. P. Tigges, A. G. Baca, R. D. Briggs, R. J. Shul

Gallium nitride (GaN)–based microwave power amplifiers have been identified as critical components in Sandia’s next-generation microsynthetic-aperture radar (micro-SAR) operating at X-band and Ku-band (10–18 GHz). To miniaturize the SAR, GaN–based amplifiers are necessary to replace bulky traveling wave tubes. Specifically, for micro-SAR development, highly reliable GaN high-electron-mobility transistors (HEMTs), which have delivered a factor of 10 improvement in power performance compared to gallium arsenide (GaAs), need to be developed. Despite the great promise of GaN HEMTs, problems associated with nitride-materials growth currently limit gain, linearity, power-added efficiency, reproducibility, and reliability. These material-quality issues are primarily due to heteroepitaxial growth of GaN on lattice-mismatched substrates. Because silicon carbide (SiC) provides the best lattice match and thermal conductivity, SiC is currently the substrate of choice for GaN–based microwave amplifiers. Obviously, for GaN–based HEMTs to fully realize their tremendous promise, several challenges related to GaN heteroepitaxy on SiC must be solved.

In this project, Sandia proposes a concerted effort to solve these materials issues through in-depth research on GaN/aluminum (Al)GaN growth on SiC. We will investigate and solve problems that limit device performance, including electron traps in GaN and AlGaN layers, dislocations, the quality of semi-insulating GaN, the GaN/AlGaN interface roughness, and surface pinning of the AlGaN gate. We will minimize the role of dislocations by leveraging our world-leadership position in growing low-dislocation GaN by transferring our patented cantilever epitaxy to SiC. We will develop predictive models of the transistor channel’s two-dimensional (2-D) electron gas and surface potential through transport measurements and band-structure modeling. We will also investigate charge trapping in GaN and AlGaN. To nullify surface charge, we will develop alternate methods of passivation and recessed-gate processing for HEMTs, which will require the developments of nondamaging etch techniques. Constant feedback between material properties, physical

Gallium nitride (GaN)–based microwave power amplifiers have been identified as critical components in Sandia’s next-generation microsynthetic-aperture radar (micro-SAR) operating at X-band and Ku-band (10–18 GHz)....Sandia proposes a concerted effort to solve these materials issues through in-depth research on GaN/aluminum (Al)GaN growth on SiC.

understanding, and device performance will enable rapid progress.

We established growth conditions to achieve HEMTs with electron mobilities $> 1300 \text{ cm}^2/\text{V s}$, sheet charge $> 1 \times 10^{13} \text{ cm}^{-2}$, and sheet resistivity $< 400 \text{ W/cm}^2$. In addition, we established baseline HEMT processing conditions. We achieved step-flow growth of AlGaIn alloys using low-ammonia conditions. We accomplished etching of $6 \text{ }\mu\text{m}$ -deep posts in SiC and initial GaN cantilever-epitaxy growths, resulting in GaN films with fewer dislocations as verified with transmission-electron microscopy (TEM).

We used density-functional theory (DFT) to calculate the defect energy levels for both carbon and oxygen, which can act as electron traps. The carbon concentration in GaN films has been shown to depend on the dislocation density. We used a contacted electroreflectance technique to investigate intrinsic electric-field-induced properties in AlGaIn/GaN heterostructures and the spectral features associated with the AlGaIn barrier, the 2-D electron gas (2-DEG) at the interface, and bulk GaN.

52571

Leaky-Mode VCSELs for Photonic Logic Circuits

D. K. Serkland, G. R. Hadley, W. W. Chow, E. L. Blansett, G. M. Peake, K. M. Geib

Leaky-mode vertical-cavity surface-emitting lasers (VCSELs) offer new possibilities for the integration of microcavity lasers to create optical microsystems. A leaky-mode VCSEL emits light horizontally, in the plane of the semiconductor wafer, which allows the light to interact with other lasers, modulators, and detectors on the same wafer. The fabrication of leaky-mode VCSELs based on effective index modification was proposed and demonstrated at Sandia recently but has not been adequately developed for use in applications. The goal of this project is to advance the design and fabrication of leaky-mode VCSELs to the point where initial applications can be attempted. In the past year, we concentrated on overcoming previous difficulties in the epitaxial growth and fabrication of these advanced VCSELs. In future work, we will focus on applications of leaky-mode VCSELs, such as all-optical processing circuits based on gain quenching.

The development of circuits that can process data directly in the optical domain will enable encryption and decryption of data on optical fibers at very high rates for secure communications. As time and resources permit in future years, we intend to explore the use of leaky-mode VCSELs to achieve higher-brightness sources, which are relevant to laser radar and remote-sensing applications.

We focused on overcoming historic problems in the growth, fabrication, and characterization of leaky-mode VCSELs so that we can effectively address applications of these novel devices in future work. We developed new methods for growth and fabrication of leaky-mode VCSELs. Additionally, we performed new theoretical simulations to gain insight into the fundamental principles of operation and to identify more effective methods of optical characterization.

The general approach to the realization of effective index changes is to perform a partial epitaxial growth of the VCSEL, remove the wafer from the growth reactor to implement a patterned shallow etch, and return the wafer to the reactor to complete the VCSEL growth. The etched regions experience a slight blue shift of their microcavity-resonance frequency, which acts equivalently to a decrease in the effective index of

Leaky-mode vertical-cavity surface-emitting lasers (VCSELs) offer new possibilities for the integration of microcavity lasers to create optical microsystems....The fabrication of leaky-mode VCSELs based on effective index modification was proposed and demonstrated at Sandia recently but has not been adequately developed for use in applications. The goal of this project is to advance the design and fabrication of leaky-mode VCSELs to the point where initial applications can be attempted.

refraction. The historic difficulties have been to control the accuracy of the shallow etch depth and the propagation of the discontinuities at the edges of the etched regions during the final epitaxial growth. We developed a new etching technique involving repeated cycles of oxidation and removal of the surface oxide, which allows us to precisely remove 2.25 nm of gallium arsenide (GaAs) per cycle. To better control the propagation of the step discontinuities during the second epitaxial growth, we switched from using semiconductor wafers that are cut 2 deg off axis to using wafers that are cut precisely along crystal planes.

52575

Advanced Polychromator Systems for Remote Chemical Sensing

J. J. Allen, K. B. Pfeifer, J. L. Dohner, M. B. Sinclair, S. S. Mani

The Polychromator is a microelectromechanical systems (MEMS)–based programmable diffraction grating that serves as the backbone of an infrared (IR) correlation radiometer. Applications of this device range from battlefield detection of chemical agents to remote monitoring of gaseous emissions. Deflection patterns of the individual grating elements of the Polychromator can be programmed to produce desired spectral-transmittance profiles. For remote chemical detection, IR radiation collected from a target is correlated with a series of predetermined reference spectra. The reference spectra are application-dependent and determined using multivariate techniques to optimize the sensitivity and selectivity of chemical detection. Once programmed with a sequence of reference spectra, the Polychromator system performs real-time multivariate analysis of the collected IR radiation. This project will enhance Sandia’s position as a world leader in programmable diffractive optics. Specifically, we propose to develop an advanced Polychromator, designed for fabrication within the Sandia Ultraplanar Multilevel MEMS Technology V (SUMMiT-V™) process, which will enable repeatable manufacture and advanced capability of the programmable grating. In addition to having superior vertical-travel range and low-voltage actuation, we will design the Polychromator to have additional programmable degrees of freedom (DOFs) such as tilting of the individual beams. This more-generalized motion will enable the production of blazed profiles for enhanced sensitivity of chemical detection. The increased number of DOFs will enable greater flexibility and higher fidelity of spectral synthesis. The advanced programmable grating technology developed in this project will also enable a variety of other optical devices such as beam-steering devices and adaptive optics based on diffractive principles.

The status of milestones is as follows:

- We completed design of first-generation advanced Polychromator programmable grating structures for large-stroke, low-voltage, multiple-DOF actuation.
- We completed fabrication of first-generation devices in SUMMiT-V™ process.
- We completed evaluation of first-generation devices.

This project will enhance Sandia’s position as a world leader in programmable diffractive optics. Specifically, we propose to develop an advanced Polychromator, designed for fabrication within the Sandia Ultraplanar Multilevel MEMS Technology V (SUMMiT-V™) process, which will enable repeatable manufacture and advanced capability of the programmable grating.

- The projected performance of the advanced Polychromator chemical sensor summarized from grating test data will be completed on schedule.

We made the following accomplishments:

- We submitted for fabrication two concepts for a vertical programmable diffraction grating on three different SUMMiT-V™ reticle sets. The concepts are a pull-down and a push-up diffraction grating.

- We designed a rotary diffraction grating that addresses the venetian blind diffraction grating for a multiport beam-steering device for future work.

- We performed evaluation testing on the pull-down and rotary diffraction gratings.

- We developed a new concept for the optical configuration of the Polychromator that will greatly increase the optical efficiency of the system.

- We performed the projection of performance of the optical system and Polychromator grating devices designed to date.

- We developed a new optical system for the Polychromator that modifies the requirements for the MEMS grating devices.

We developed a new concept for the optical configuration of the Polychromator that will greatly increase the optical efficiency of the system.

Engineering Sciences

The Engineering Sciences investment area encompasses the core engineering disciplines that support the Nuclear Weapons Strategic Business Unit and other Sandia priorities. The goal is to develop a validated, science-based simulation environment. This requires the integration of experimental, simulation, and test activities required for pertinent physics discovery and validation. The challenge is to provide engineering understanding through simulation unprecedented in physical and geometric fidelity, and spatial and temporal resolution. This will advance the understanding in the engineering disciplines critical to Sandia's national security mission. Research emphasis includes micro- and nanoscale phenomenology, technologies supporting Sandia thrusts in homeland security, and technologies critical to advanced weapon concepts.

Sandia has developed engineering models of unprecedented size and fidelity requiring high-resolution multiparameter diagnostics. Within the thermal/fluids disciplines, the need for detailed, high-fidelity measurements exceeds the limits of current engineering sciences capabilities. The focus of *Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements* is the development and application of filtered Rayleigh scattering (FRS) for high-resolution, nonintrusive measurement of

velocity, temperature, and pressure. Two FRS measurement systems have been implemented, one at the Combustion Research Facility (CRF) and another at the Hypersonic Wind Tunnel (HWT), so that FRS combustion and aerosciences investigations can proceed simultaneously. This capacity for multiparameter, nonintrusive instrumentation represents an unprecedented advance beyond presently available techniques in the Engineering Sciences Center and in the larger scientific arena.

26520

Uncertainty Propagation in Models of Thermofluid Systems

H. N. Najm, M. T. Reagan

Uncertainty quantification (UQ) in models of thermofluid systems is necessary for model validation with respect to experimental results, and for the development of predictive engineering models. The focus of this project was the development and demonstration of alternative intrusive and nonintrusive UQ techniques using Polynomial Chaos (PC) theory in the context of reacting flow. Intrusive techniques involve significant reformulation of the model governing equations and associated computational code, while nonintrusive techniques provide wrappers around black-box legacy solvers. Sandia studied two nonintrusive techniques, including conventional Monte Carlo (MC) and coupled MC–PC constructions. We also studied intrusive pseudospectral PC constructions. These were done in the context of zero-dimensional (0-D) and 1-D reacting systems. We used results to analyze and compare these various UQ techniques, in terms of computational efficiency and general utility for enhancing understanding of uncertainty propagation in computational models.

We focused largely on the continued development of a robust validated intrusive pseudospectral stochastic UQ solver for reacting flow. Highlights of our accomplishments include the following:

(1) We completed the development of an intrusive UQ solver for a low-Mach-number reacting flow with detailed chemistry. The construction involves a projection scheme solution of the momentum equations coupled with an operator-split stiff solver for the species- and energy-conservation equations. We used the resulting distributed parallel code to study a 1-D flame, allowing for uncertainty in chemical rate constants and thermodynamic properties. This study revealed spatial growth of uncertainty with downstream distance through the flame. It also highlighted the computational challenges involved in solving the intrusive UQ governing equations in the presence of strong nonlinearities. This work also identified significant challenges with outflow boundary condition–driven instabilities for longtime computations of this flow. These challenges were not fully resolved in the context of this work, and they require further study.

The extent of computational challenges with strong chemical nonlinearities has driven significant research with collaborators at Johns Hopkins University and University

This study revealed spatial growth of uncertainty with downstream distance through the flame. It also highlighted the computational challenges involved in solving the intrusive UQ governing equations in the presence of strong nonlinearities. This work also identified significant challenges with outflow boundary condition–driven instabilities for longtime computations of this flow.

d'Evry on the development and evaluation of alternative PC formulations based on wavelet bases. We showed these new formulations to efficiently handle steep nonlinear behavior, and they hold much promise for resolving computational challenges with intrusive reacting-flow UQ computations with PC expansions.

Refereed

Le Maitre, O. P., H. N. Najm, R. G. Ghanem, and O. M. Knio. 2003. Multiresolution analysis of Wiener-type uncertainty propagation schemes. *J. Computational Physics*. New York, New York: Academic Press.

Le Maitre, O. P., M. T. Reagan, B. J. Debusschere, H. N. Najm, R. G. Ghanem, and O. M. Knio. 2003. Natural convection in a closed cavity under stochastic, non-Boussinesq conditions. *SIAM J. Scientific Computing*, submitted.

Le Maitre, O. P., M. T. Reagan, H. N. Najm, R. G. Ghanem, and O. M. Knio. 2003. A stochastic projection method for fluid-flow II. Random process. *J. Computational Physics* **181**:9–44.

Le Maitre, O. P., R. G. Ghanem, O. M. Knio, and H. N. Najm. 2003. Uncertainty propagation using Wiener-Haar expansions. *J. Computational Physics*. New York, New York: Academic Press, submitted.

Reagan, M. T., H. N. Najm, R. G. Ghanem, and O. M. Knio. 2003. Uncertainty quantification in reacting-flow simulations through nonintrusive spectral projection. *Combustion and Flame* **132**:545–55.

Other Communications

Knio, O. M., and R. G. Ghanem. 2002. Polynomial chaos product and moment formulas: A user utility. Technical Report, The Johns Hopkins University, Baltimore, Maryland.

Najm, H. N., M. T. Reagan, B. J. Debusschere, O. M. Knio, A. A. Matta, R. G. Ghanem, and O. P. Le Maitre. 2002. Uncertainty quantification in computations of reacting thermofluid systems. Paper presented at the Workshop on Predictability of Complex Phenomena, Santa Fe, New Mexico.

Najm, H. N., M. T. Reagan, B. J. Debusschere, O. M. Knio, R. G. Ghanem, and O. P. Le Maitre. 2003. Modeling reacting flow with uncertainty quantification. Paper presented at the 19th ICDERS, Hakone, Japan.

Najm, H. N., M. T. Reagan, B. J. Debusschere, P. P. Pebay, O. M. Knio, R. G. Ghanem, and O. P. Le Maitre. 2003. Uncertainty quantification in low-Mach-number reacting-flow computations. Paper presented at SciCADE 2003, Trondheim, Norway.

Reagan, M. T., H. N. Najm, O. M. Knio, and R. G. Ghanem. 2002. Understanding uncertainty propagation through spectral analysis. Paper presented at the 55th Annual Meeting of the Division of Fluid Dynamics of the American Physical Society, Dallas, Texas.

Reagan, M. T., H. N. Najm, O. M. Knio, R. G. Ghanem, and O. P. Le Maitre. 2003. Spectral methods for uncertainty quantification in reacting-flow systems. Paper presented at the 7th U.S. National Congress on Computational Mechanics, July, Albuquerque, New Mexico.

Reagan, M. T., H. N. Najm, R. G. Ghanem, and O. M. Knio. 2002. Analysis of parametric uncertainty propagation in detailed combustion chemistry. *Computational Fluids and Solid Mechanics* **2**, ed. K. J. Bathe. Elsevier Science:1501–5.

26521

Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements

S. P. Kearney, R. W. Schefer, S. J. Beresh, T. W. Grasser

Simulation-based life-cycle engineering and the Accelerated Strategic Computing Initiative (ASCI) program have resulted in models of unprecedented size and fidelity. The validation of these models requires high-resolution, multiparameter diagnostics. Within the thermal/fluids disciplines, the need for detailed, high-fidelity measurements exceeds the limits of current capabilities in engineering sciences and severely tests the state of the art; therefore, a diagnostic development effort is warranted. The focus of this project is the development and application of filtered Rayleigh scattering (FRS) for high-resolution, nonintrusive measurement of velocity, temperature, and pressure.

With FRS, the flow is laser-illuminated, and Rayleigh scattering from naturally occurring sources is detected through a molecular filter. The filtered transmission may be interpreted to yield point or planar measurements of three-component velocities and/or thermodynamic state. Different experimental configurations may be employed to obtain compromises between spatial resolution, time resolution, and the quantity of simultaneously measured flow variables. This capacity for multiparameter, nonintrusive instrumentation represents an unprecedented advance beyond presently available techniques in the Engineering Sciences Center at Sandia and in the larger scientific arena. Furthermore, measurements may be made using naturally occurring scattering centers, thus eliminating potentially intractable difficulties associated with particulate or chemical seeding in a hypersonic or reacting environment.

The focus of this project is the development and application of filtered Rayleigh scattering (FRS) for high-resolution, nonintrusive measurement of velocity, temperature, and pressure....This capacity for multiparameter, nonintrusive instrumentation represents an unprecedented advance beyond presently available techniques in the Engineering Sciences Center at Sandia and in the larger scientific arena.

The FRS diagnostic has been cultivated at Sandia to serve multiple Engineering Sciences disciplines. FRS permits measurement of multiple quantities with a single diagnostic tool. (top) Aerospaces programs such as B-61 (a) are supported by FRS fluid velocity imaging in a supersonic jet (b). (bottom) Sandia's Fire Science and Combustion Research programs (c) are supported by FRS temperature imaging in a sooting flame (d). Without FRS, such optical-imaging thermometry is otherwise impossible.

Molecular-filter absorption of scattered light from solid boundaries also makes FRS advantageous for detailed boundary-layer measurements. These advantages make FRS an attractive alternative to developed techniques and offer a substantial payoff impacting multiple thermal/fluids disciplines. Moreover, a virtually identical experimental configuration may be used for both aerodynamic and thermal diagnostic applications simply by adjusting the laser and molecular filter. These measurements are ideally suited for use in production-scale facilities, where many other techniques are difficult to implement. Potential validation applications include simultaneous three-component velocity, temperature, and pressure measurements in compressible flows to support SACCARA/PREMO validation, and full-field temperature measurements in reacting or nonreacting flows for FUEGO and SIERRA/CALORE validation.

These advantages make FRS an attractive alternative to developed techniques and offer a substantial payoff impacting multiple thermal/fluids disciplines.

Our key accomplishments include (1) evaluation of FRS thermometry in premixed combustion environments, (2) extension of FRS to a more challenging diffusion flame using a joint FRS–Raman-imaging approach, (3) application of FRS to a sooting flame, and (4) construction and shakedown of a second FRS system for velocity measurements in Sandia’s hypersonic wind tunnel (HWT).

We extensively investigated FRS thermometry for fire and combustion applications. We followed a systematic approach, where we gradually increased the degree of difficulty of the temperature-imaging measurements. Measurements in a premixed, methane-air flat flame, which we began previously, served as our initial test of FRS thermometry in reacting flows. This nonsooting, premixed flame allowed us to assess the impact of chemistry-dependent variations on FRS-measured temperatures, which we judged to be the largest source of systematic error in FRS temperature measurements. In premixed hydrocarbon flames of this nature, our data show that previous assumptions regarding scattering cross section in air-fed combustion can lead to bias errors as large as 200 K. When we reinterpret the FRS data using refined cross sections that were based on even approximate burnt-gas composition, we find that these uncertainties are decreased to 50 K or less over a broad range of stoichiometries.

We then extended FRS thermometry to diffusion (nonpremixed) flames where the variations in local-scattering cross section are more severe than in premixed combustion. We made combined FRS–fuel Raman-imaging measurements to jointly measure the flame temperature and fuel mole-fraction in

a vortex-strained methane-air diffusion flame. Addition of the fuel Raman-imaging data allowed us to make an accurate measure of the local scattering cross section to overcome this significant source of bias. To our knowledge, this is the first application of FRS in a nonpremixed flame and the first reported joint FRS–Raman results. The joint FRS–Raman results were nominated for an honors quality award at the American Society of Mechanical Engineering (ASME) International Mechanical Engineering Congress and Exposition (IMECE) Conference.

We concluded the FRS combustion-imaging study by assessing the applicability of FRS in a sooting, premixed ethylene-air flame. The FRS technique is attractive for measurements in sooting flames, where strong interference from soot scattering overwhelms the Rayleigh signal and renders conventional (unfiltered) Rayleigh measurements impossible. The molecular filter provided a significant degree of rejection of soot-scattering interference in this flame, with a factor of 1000–1500 rejection measured with our commercial injection-locked Nd:YAG (neodymium:yttrium-aluminum-garnet) laser. We established an informal collaboration with researchers at the Propulsion Directorate of the Air Force Research Laboratory (AFRL) at Wright-Patterson AFB, Ohio, and visited the AFRL facility in which an injection-locked Nd:YAG system with additional line-narrowing provided by an intracavity etalon was used to provide a factor of 7 increase in rejection of soot interference. We currently are quantifying the upper sooting limit for FRS thermometry applications in premixed sooting flames and hope to apply FRS with joint ultraviolet Raman imaging for temperature and fuel-mole-fraction imaging in support of an ongoing effort directed at soot formation in diffusion flames. These FRS measurements in sooting flames have a direct link to support of the ASCI program.

We also applied our FRS optoelectronic system to velocity measurement in supersonic flows in support of the Sandia aerosciences program (links to SACCARA and ASCI/PREMO). We acquired measurements of the stream-wise velocity component in a Mach 3.7 nitrogen jet. The FRS–measured velocities in the jet core are in good agreement with predictions from potential flow theory. We also acquired a second injection-locked Nd:YAG laser through capital-equipment funding and used this laser to construct a second FRS system at the Sandia HWT facility. Presently, this system is operational, and the hypersonic velocimetry measurements

We made combined FRS–fuel Raman-imaging measurements to jointly measure the flame temperature and fuel mole-fraction in a vortex-strained methane-air diffusion flame. Addition of the fuel Raman-imaging data allowed us to make an accurate measure of the local scattering cross section to overcome this significant source of bias. To our knowledge, this is the first application of FRS in a nonpremixed flame and the first reported joint FRS–Raman results. The joint FRS–Raman results were nominated for an honors quality award....

are to be completed under follow-on funding from the Engineering Sciences Research Foundation Tech Base program.

Refereed

Beresh, S. J., S. P. Kearney, C. J. Bourdon, and T. W. Grasser. 2003. Development of a Doppler global velocimeter for a highly overexpanded supersonic jet. *Proc. 41st AIAA Aerospace Sciences Meeting and Exhibit*, AIAA paper number 2003-0915 (January, Reno, Nevada).

Kearney, S. P., R. W. Schefer, S. J. Beresh, and T. W. Grasser. 2003. An experimental study of vortex-flame interaction using joint filtered-Rayleigh and Raman-scattering imaging. Paper presented at the 52nd Annual Meeting of the American Physical Society, Division of Fluid Dynamics, November, New York, New York.

Kearney, S. P., R. W. Schefer, S. J. Beresh, and T. W. Grasser. 2003. Joint Raman-filtered Rayleigh technique for temperature imaging in nonpremixed flames. *Optics Letters*, to be submitted.

Kearney, S. P., R. W. Schefer, S. J. Beresh, and T. W. Grasser. 2003. Temperature and fuel mole fraction imaging in vortex-strained diffusion flames by a joint FRS–Raman-imaging approach. *Combustion and Flame*, to be submitted.

Kearney, S. P., R. W. Schefer, S. J. Beresh, and T. W. Grasser. 2003. Temperature imaging of vortex-flame interaction by filtered Rayleigh scattering. *Proc. IMECE '03, ASME International Mechanical Engineering Congress and Exposition (IMECE)* (November, Washington, D.C.).

Kearney, S. P., S. J. Beresh, C. D. Carter, and J. W. Crafton. 2003. Filtered Rayleigh scattering in vortex-strained and sooting flames. Paper to be presented at the 42nd AIAA Aerospace Sciences Meeting and Exhibit, Reston, Virginia.

Kearney, S. P., S. J. Beresh, T. W. Grasser, and R. W. Schefer. 2003. A filtered Rayleigh-scattering apparatus for noninvasive temperature imaging. Paper presented at the 51st Annual Meeting of the American Physical Society, Division of Fluid Dynamics, November, Dallas, Texas.

Kearney, S. P., S. J. Beresh, T. W. Grasser, R. W. Schefer, P. E. Schrader, and R. L. Farrow. 2003. A filtered Rayleigh-scattering apparatus for gas-phase and combustion-temperature imaging. *Proc. 41st AIAA Aerospace Sciences Meeting and Exhibit*, AIAA paper number 2003-0584 (January, Reno, Nevada)

26522

A Physically Based Approach to Modeling Ductile Fracture

P. A. Klein, D. A. Zeigler, S. X. McFadden, B. R. Antoun, D. J. Bammann

This project will result in a new computational tool for modeling crack growth in ductile materials. Ductile fracture is probably the most common mode of fracture in solids where material fails by a combination of excessive bulk deformation and cracking. The initiation and growth of cracks in ductile materials consume energy due to the evolution of bulk plastic and damage processes as well as the creation of new free surfaces. A computational model of these processes must reproduce the physical dimensions and stresses in the fracture process zone because the response and evolution of the dissipation mechanisms are inherently scale- and strength-dependent. The development of this computational tool begins with a fundamental, thermodynamically sound description of the failure process that encompasses both ductile failure and fracture mechanics. The development of a thermodynamic theory that includes the dissipation of both the bulk material and the surface energy of a cohesive zone requires the development of a new kinematical description of the failure process to couple these concepts at a basic level. In situ scanning-electron microscope (SEM) observations of the initiation and evolution of fracture zones will reveal the scale over which the failure mechanisms act in Defense Programs alloys 6061 aluminum (Al) and 304L stainless steel (SS) and in copper. These observations are essential for motivating micromechanical models of the decohesion process that incorporate the effects of mode mixity in the loading, temperature, loading rate, and load reversals. The effect of load reversals must be incorporated into the computational model-to-model fatigue.

We previously performed some preliminary work on mapping plastic strains around the crack tip using electron back-scatter diffraction (EBSD) patterns. The method is based on image-analysis techniques, which quantify the degradation in EBSD pattern quality that results from dislocation storage. Quantification of strain using the EBSD pattern quality requires calibration based on specimens that have been strained to a known amount. We prepared calibration specimens by performing interrupted tensile tests on 304L SS and 6061 Al, obtained from the same lot as the three-point-bend specimens

This project will result in a new computational tool for modeling crack growth in ductile materials....[such as] Defense Programs alloys 6061 aluminum (Al) and 304L stainless steel (SS) and in copper. These observations are essential for motivating micromechanical models of the decohesion process that incorporate the effects of mode mixity in the loading, temperature, loading rate, and load reversals.

we were using for our fracture experiments. The tensile samples were sectioned, mounted with the tensile axis normal to the mount surface, ground, polished, and lightly etched. We tried an electropolish on the 6061 Al, but SEM images and EBSD patterns showed that the light chemical etch provided better results. We determined strain for each calibration specimen by measuring the diameter of the polished surface and comparing it to the as-machined diameter of the tensile samples. We calculated a power-spectrum density (PSD) from the square root of the sum of the squares of the real and imaginary Fourier coefficients. We calculated a power-spectrum first moment (PSFM) by multiplying the PSD values by their frequency and summing the products. The patterns show a qualitative decrease in sharpness with an increase in strain. However, the PSFM values for 304L and 6061 calibration samples were unable to distinguish between the as-received condition and the other calibration samples. These results were disappointing, and it is not clear why the method failed. One possibility is that the digital camera is not capable of capturing the necessary pattern detail, just as is the case for earlier-generation imaging systems. Another issue to consider is the effect of the specimen surface. While we took precautions to have well-prepared surfaces, and the SEM operator was careful not to view the diffraction sites longer than necessary, it is still possible that surface conditions played a role.

In our modeling efforts, we extended the mechanism-based cohesive zone relations developed previously to include yield-point behavior. Yield-point behavior implies that cohesive relations may prescribe rigid response of the cohesive zone if the applied stresses drop below those required to activate the failure processes. Mathematically, yield-point behavior dictates that the cohesive relations act at times as constitutive relations, where the tractions must be determined locally based on the applied loads, and at other times as constraints, where the tractions are determined globally based on enforcement of the constraints. Difficulties arise in enforcing the rigid constraints and switching smoothly between conditions of constraint and flow. Additionally, implementation of the local update equations for the cohesive relations must take into account that each component of traction may independently switch between being a local or a global unknown. We investigated both penalty-based and augmented Lagrangian formulations for enforcing constraints. We determined that an augmented Lagrangian formulation is a better choice for enforcing the rigid constraints in the cohesive zone because the allowable tolerances on enforcement of the constraints in the fracture

process zone must be very tight. The tight tolerances are required because of a combination of the small characteristic opening displacements and the high stresses in the fracture process zone. Even small errors in enforcement of the rigid constraints produce large errors into the associated tractions and introduce instabilities in the solution procedure. Additionally, we implemented a revised cohesive surface element using node-based integration of the cohesive tractions. A node-based integration is required because Gaussian quadrature methods generally do not produce the correct ratio of constraints to degrees of freedom over the surface elements. Conditions of over-constraint produce highly fluctuating values of the constraint tractions, while conditions of under-constraint allow spurious modes of deformation.

Refereed

Hao, S., W. K. Liu, P. A. Klein, and A. Rosakis. 2003. Modeling and simulation of intersonic crack growth. *Proc. International J. Solids and Structures*, accepted.

Klein, P. A., D. J. Bammann, S. X. McFadden, J. W. Foulk, and B. R. Antoun. 2003. A mechanism-based thermomechanical cohesive zone approach for modeling ductile fracture. Paper presented at the 7th U.S. National Congress on Computational Mechanics, July, Albuquerque, New Mexico.

Klein, P. A., D. J. Bammann, S. X. McFadden, J. W. Foulk, and B. R. Antoun. 2003. A mechanism-based thermomechanical cohesive zone approach for modeling ductile fracture. Paper presented at the ASME Mechanics and Materials Conference, June, Scottsdale, Arizona.

Klein, P. A., D. J. Bammann, S. X. McFadden, J. W. Foulk, and B. R. Antoun. 2003. A mechanism-based thermomechanical cohesive zone approach for modeling ductile fracture. *Proc. Society for Experimental Mechanics Annual Conference* **1** (Charlotte, North Carolina): 211.

26523

Radiation Aging of Stockpile and Space-Based Microelectronics

H. P. Hjalmarson, P. A. Schultz, C. E. Hembree, J. R. Schwank, M. R. Shaneyfelt, S. C. Witzak

Sandia is investigating the effects of other passivation layers on pre-irradiation elevated temperature stress (PETS) and enhanced low-dose-rate sensitivity (ELDRS). In addition, we will remove the passivation layers from devices known to exhibit latent interface trap buildup (LITB) and determine whether LITB is also associated with hydrogen (H) release from the passivation layer as suggested by the model. With these experiments, we will be able to demonstrate the effects of passivation layers on current stockpile components and methods for reducing ELDRS and PETS effects for future stockpile components. Based on the experimental results, we will modify the dimerization model as required. Furthermore, we will perform electronic-structure calculations on passivation-layer materials to explore H release mechanisms and to estimate H migration rates. Our overall goal is to use the results of the experiments and modeling to conclusively determine the mechanisms for ELDRS, PETS, and LITB.

We developed a suite of bimolecular-reaction models to explain the fundamental problem addressed in this project, the ELDRS of bipolar transistors to radiation damage. These models are in qualitative agreement with experiments, and it appears likely that one of these mechanisms will be able to explain data quantitatively. However, we have not obtained the material parameters needed for these models from the test structures. Thus, further continuum calculations needed to verify the theory remain to be done. We did perform electronic-structure calculations on postulated source sites to explore H release mechanisms and to estimate H migration rates. However, we did not complete conclusive measurements of H concentrations before the end of this project. These measurements and other characterizations of the oxide and passivation films are necessary to fully apply the theory to data. In spite of problems with developing a conclusive explanation of ELDRS, we developed a new passivation process that led to a practical method for preventing ELDRS.

...we will be able to demonstrate the effects of passivation layers on current stockpile components and methods for reducing ELDRS and PETS effects for future stockpile components....Our overall goal is to use the results of the experiments and modeling to conclusively determine the mechanisms for ELDRS, PETS, and LITB.

Refereed

Hjalmarson, H. P., R. L. Pease, S. C. Witczak, M. R. Shaneyfelt, J. R. Schwank, A. H. Edwards, C. E. Hembree, and T. R. Mattsson. 2003.

Mechanisms for radiation dose-rate sensitivity of bipolar transistors. *IEEE Trans. Nuclear Science*, accepted.

26524

Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach

D. R. Noble, D. J. Segalman, P. R. Schunk, J. R. Weatherby, S. R. Subia, T. A. Baer, E. D. Wilkes

Solidification and blood flow seemingly have little in common, but each involves a fluid in contact with a deformable solid. In these systems, the fluid-solid interface moves as the solid advects and deforms, often traversing the entire domain of interest. Currently, these problems cannot be simulated without innumerable, expensive remeshing steps, mesh manipulations, or decoupling of the solid and fluid motion. Despite the wealth of progress recently made in mechanics modeling, this glaring inadequacy persists.

Sandia proposes a new technique that tracks the interface implicitly and circumvents the need for remeshing and remapping. The fluid-solid boundary is tracked with a level-set algorithm that changes the equation type dynamically, depending on the phases present. This novel approach to coupled mechanics problems promises to give accurate stresses, displacements, and velocities in both phases simultaneously.

This effort involves high-risk research in Eulerian solid mechanics of bodies defined by an implicit interface (not defined by a mesh contour). An equally difficult task is to equate the solid and fluid stresses at this implicit interface. Simulating fluid mechanics requires a Eulerian formulation to avoid mesh entanglement. Solid-mechanics formulations, however, tend to be Lagrangian, as it is easier to track material interfaces, compute strain, and apply boundary conditions (BCs). We propose to handle the complete problem in a Eulerian context using level sets to define the solid-fluid interfaces. We will apply the advances made in level-set methods for multiphase fluids to this more difficult problem involving multiple physics.

High-payoff applications are as numerous as the complex moving geometry problems we seek to address every day. A small subset includes solidification and polymerization with accurate residual-stress determination and biological applications like cell deformation and blood rheology. Many of these problems cannot be adequately addressed using existing methods, but may be quantitatively simulated using the methods we propose.

We made accomplishments in three major areas. First, we generalized the previously developed embedded BCs, which are capable of describing multidimensional interfacial

Sandia proposes a new technique that tracks the interface implicitly and circumvents the need for remeshing and remapping. ...High-payoff applications are as numerous as the complex moving geometry problems we seek to address every day. A small subset includes solidification and polymerization with accurate residual-stress determination and biological applications like cell deformation and blood rheology. Many of these problems cannot be adequately addressed using existing methods, but may be quantitatively simulated using the methods we propose.

discontinuities within finite elements (FEs), for numerous types of fluid-fluid and fluid-solid interfaces. We developed three classes of methods for assembling element contributions for elements that span an interface: (1) subgrid methods, where adaptive Gauss quadrature is performed to integrate across a diffuse but narrow band along the interface, (2) subelement methods, where element subdivision is used to separate the interfacial regions, allowing the integration to conform to the interface even when the elements do not, and (3) ghost fluid methods, in which the interfacial elements are integrated twice, once for each side of the interface. Each of these methods has its niche problems for which performance is optimal. However, issues still remain with parasitic currents and other measures of the solution quality.

Second, we developed a hybrid technique where we loosely coupled the fluid-structural interactions with an overlapping mesh method in which Lagrangian solid mechanics was coupled to Eulerian, viscous fluid mechanics. These hybrid methods are useful for a certain class of physics applications such as gravure coating and dendrite dynamics that do not need a fully Eulerian approach. Overlapping mesh techniques are ideal for applications that involve solid materials that move through a significant portion of the fluid domain but are not excessively deformed. We improved a loosely coupled overlapping technique with Lagrangian solid mechanics and Eulerian fluid mechanics and exercised this technique on several validation and verification problems. We showed the method to simulate much larger deformation than that possible with arbitrary Lagrangian Eulerian (ALE) methods without expensive remeshing and remapping steps. The loose coupling has poor convergence, so we used a bordered algorithm to improve communication between the solid and fluid matrices, thus improving convergence.

Third, following Chessa, *et al.*, we implemented an extension velocity equation into our FE test-bed to allow solutions of problems where the level set no longer follows a fluid-phase boundary. This allows us to follow solid boundaries for solidification problems, and reaction fronts for electroplating and related applications. We are using the extension velocity, coupled with the sharper interface work, to solve a solidification problem for a welding application.

...we developed a hybrid technique where we loosely coupled the fluid-structural interactions with an overlapping mesh method in which Lagrangian solid mechanics was coupled to Eulerian, viscous fluid mechanics. These hybrid methods are useful for a certain class of physics applications such as gravure coating and dendrite dynamics that do not need a fully Eulerian approach.

Refereed

Baer, T. A., D. R. Noble, R. R. Rao, and A. Grillet. 2003. A level-set approach to 3-D mold filling of Newtonian fluids. *Proc. 4th ASME–JSME Joint Fluids Engineering Conference (ASME FEDSM '03)* **1** (July, Honolulu, Hawaii): S-364.

Noble, D. R., P. R. Schunk, E. D. Wilkes, R. R. Rao, and T. A. Baer. 2003. Finite-element simulations of fluid-structure interactions via overset meshes and sharp embedded interfacial conditions. *Proc. Moving Boundary 2003* **1** (November, Santa Fe, New Mexico): 1.

Noble, D. R., T. A. Baer, R. R. Rao, and P. R. Schunk. 2003. A hybrid ghost fluid—extended finite-element method. *Proc. 7th U.S. National Congress on Computational Mechanics (USNCCM 7)* **1** (July, Albuquerque, New Mexico): 269.

Wilkes, E. D., and R. R. Rao. 2003. An overlapping grid algorithm for finite-element solution of fluid-structure interaction problems. *Proc. 7th U.S. National Congress on Computational Mechanics (USNCCM 7)* **1** (July, Albuquerque, New Mexico): 281.

Other Communications

Baer, T. A. 2003. 1-D prototyping of extended finite-element algorithm. Internal Sandia memorandum to D. R. Noble, *et al.*

Noble, D. R. 2003. Hybrid ghost fluid—extended finite-element method. Internal Sandia memorandum to R.R. Rao, *et al.*

Wilkes, E. D., D. R. Noble, R. R. Rao, T. A. Baer, and P. R. Schunk. 2003. An overlapping grid algorithm for finite-element solution of fluid-solid interaction problems. Internal Sandia memorandum to Distribution, Sandia National Laboratories, Albuquerque, New Mexico.

38682

Multiscale Thermal Modeling

E. S. Piekos, C. C. Wong, S. Graham, Jr.

Successfully predicting the performance and reliability of many devices hinges on accurate knowledge of their thermal response in normal and abnormal environments. Unfortunately, the assumptions underlying common numerical tools and material property data used for predicting thermal behavior fail in the microscale regime. In this regime, phonon interaction with surfaces and microstructural entities, not the usual phonon-phonon scattering, dominates thermal resistance. Heat flow thus becomes dependent on direction and feature size. As devices shrink, these effects will become increasingly important as highly localized heating is caused by reduced thermal conductivity. This project is aimed at providing tools for increasing our understanding of microscale heat-transport phenomena and translating this understanding into efficient models for representing these effects in commonly used macroscale codes.

This research concentrates on exploring thermal transport in thin silicon (Si) films using both experiments and numerical simulation. Experimental efforts use microfabricated heaters and probes to measure the effect of various microstructural and processing effects on the thermal conductivity of single and polycrystalline Si films in a parameter space (i.e., film thickness, grain size, dopants, temperature) of interest to Sandia. These data form a physical reference for the development of models intended to predict the impact of microstructural and length-scale effects on thermal transport in microscale devices. While the general framework of these models will be applicable to a wide number of devices that are dominated by phonon transport, the efforts of this work will be applied first to thermal microelectromechanical systems (MEMS) that use polycrystalline Si as the functional material. The development of both modeling tools and thermal-property microstructural data has been requested by, and will be invaluable to, the development of thermal actuators by Sandia weapons designers and MEMS fabricators.

We significantly advanced both our numerical and experimental capability with regard to microscale thermal transport. This increased capability has produced a wealth of new data and understanding that will be used to further improve our simplified models for macroscale codes.

A packaged sample mounted in the cryostat for testing at a range of temperatures.

We significantly advanced both our numerical and experimental capability with regard to microscale thermal transport. This increased capability has produced a wealth of new data and understanding that will be used to further improve our simplified models for macroscale codes.

In the computational area, we implemented new submodels in the Monte Carlo (MC) phonon-scale heat-transfer simulator and identified areas in which its generality can be improved by removing assumptions. In addition, we parallelized the code to enable the treatment of more ambitious problems in the time available for this work.

The addition of submodels allows the simulation of more complex materials and geometries. The isotope/doping submodel was constructed based on Rayleigh-scattering arguments. Subsequent predictions of bulk thermal conductivity of single-crystal Si with and without isotopes showed an excellent agreement with experimental data, lending credence to both the isotope and the phonon-phonon scattering submodels. The boundary scattering submodel was drawn from the direct-simulation Monte Carlo (DSMC) technique for gases. Subsequent predictions of the thermal conductivity of thin (1 μm and 340 nm) single-crystal Si films showed good agreement with experimental data, capturing the size effect far better than available analytic models. We constructed a grain-boundary scattering model based on fitting observed grain sizes with a lognormal distribution. Subsequent predictions of the thermal conductivity of polycrystalline Si films showed good agreement with experimental results. In this case, the flexibility of the MC simulation allows a more accurate representation of the microstructure than the semi-analytic models, which typically employ only an average grain size. Finally, we attempted a new phonon-phonon scattering submodel based on ideas gleaned from DSMC for gases. While this model is not yet successful, it has the promise of removing the near-equilibrium assumption, as well as several empirical constants, present in our current relaxation time-based scheme.

In the experimental area, we expanded our dataset to include doped and undoped single-crystal films, as well as polycrystalline films deposited and annealed under a range of conditions. Due to their lower thermal conductivity, accurate measurement on the polysilicon (poly-Si) films required the development of samples with the heaters placed on suspended membranes. Due to the many variables involved in producing poly-Si, as well as its prevalence in the MEMS under development at Sandia, this dataset is particularly useful to both the modeling and the design community.

We constructed a grain-boundary scattering model based on fitting observed grain sizes with a lognormal distribution. Subsequent predictions of the thermal conductivity of polycrystalline Si films showed good agreement with experimental results. In this case, the flexibility of the MC simulation allows a more accurate representation of the microstructure than the semi-analytic models, which typically employ only an average grain size.

Refereed

Graham, S., Jr., B. W. Olson, C. C. Wong, E. S. Piekos, A. D. McConnell, and K. E. Goodson. 2003. The effects of processing conditions on the thermal conductivity of polycrystalline silicon films. *Proc. International Mechanical Engineering Congress and R&D Expo 2003*, accepted.

Piekos, E. S., C. C. Wong, and S. Graham, Jr. 2003. Insights into phonon transport gained via DSMC simulations. *Proc. International Mechanical Engineering Congress and R&D Expo 2003*, accepted.

Piekos, E. S., S. Graham, Jr., and C. C. Wong. 2003. Concurrent computational and experimental investigation of thermal-energy transport by phonons. Paper presented at the Materials Research Society Spring Meeting, April, San Francisco, California.

Other Communications

Foiles, S. M., J. J. Hoyt, E. B. Webb, III, C. J. Kimmer, S. G. Liter, E. S. Piekos, and C. C. Wong. 2003. Enhanced Understanding of Microscale Thermal Transport. Sandia Technical Report SAND2003-2996P (Internal White Paper), Sandia National Laboratories, Albuquerque, New Mexico.

Piekos, E. S. 2003. Modeling microscale thermal transport via particle simulation. *Proc. 5th Biennial Tri-Laboratory Engineering Conference*, accepted.

38684

A Robust, Coupled Approach for Atomistic-Continuum Simulation

J. A. Zimmerman, P. A. Klein, E. B. Webb, III, J. J. Hoyt, R. E. Jones, C. J. Kimmer, S. Aubry

With the growing focus on predictive modeling and simulation, Sandia must develop the capability to model deformation and failure in multiple scale settings. We are developing a robust approach for coupled atomistic-continuum simulation, capable of both quasi-static and finite temperature/dynamic analyses. Sandia currently does not have this simulation capability. Our methodology will simulate systems at finite temperatures correctly, which involves the transfer of energy from the continuous spectrum of vibrations in the atomistic region to the separate modes of a scalar temperature field and “long” elastic waves in the continuum. Existing schemes found in the literature make no attempt to differentiate between the exchange of thermal and elastic energy. A comprehensive framework is being created to relate the dynamic motion of atoms with the kinetics of a continuum. Our approach introduces high-fidelity physics to capture nanoscale processes while using continuum mechanics to model, in a computationally efficient manner, the elastic deformation for the majority of a system with microscale dimensions.

An essential requirement of our work is the development of definitions for continuum quantities that can be evaluated locally within an atomistic region. Historically, continuum variables are only defined in terms of equilibrium thermodynamics. The instantaneous, individual atomic contributions to these averages do not have the same physical interpretation as the corresponding “point-wise” continuum quantities. We are investigating and developing physical measures of stress, deformation, temperature, and heat flux that are calculable in an atomistic simulation and have well-defined meanings when evaluated in the continuum limit.

This work will ultimately allow analysis of inherently multiscale problems such as stiction and wear in microelectromechanical systems (MEMS), nanoindentation, and fracture in microdevices.

We developed a coupled atomistic-continuum approach for zero-temperature, quasi-static simulations. The formulation of this approach contains features such as modeling the entire computational domain with a continuum representation and uses overlapping atomic crystals in localized regions of interest.

With the growing focus on predictive modeling and simulation, Sandia must develop the capability to model deformation and failure in multiple scale settings. We are developing a robust approach for coupled atomistic-continuum simulation, capable of both quasi-static and finite temperature/dynamic analyses.....

This work will ultimately allow analysis of inherently multiscale problems such as stiction and wear in microelectromechanical systems (MEMS), nanoindentation, and fracture in microdevices.

This formulation contains a much more robust approach for atomistic-continuum coupling than previous efforts. It maintains the integrity of both types of analysis while also minimizing fictitious interfacial forces between atomistic and continuum regions.

We implemented routines within the continuum simulation code to enable it to perform this quasi-static formulation. We are constructing routines needed for all expressions developed within our formulation that are essential for the calculation of energies and forces. Once our formulation is fully implemented, we will perform verifying test simulations of zero-temperature, quasi-static nanoindentation and surface relaxation of stretched nanowires to ensure proper transmission of forces. We documented our formulation for quasi-static, atomistic-continuum coupling and are preparing a manuscript suitable for publication within a refereed journal.

We studied definitions of temperature and heat flux with regard to calculation within atomistic simulation. We also researched several models of thermal-energy transport and noted the suitability of each model with respect to spatial and time scales. We performed molecular dynamics (MD) simulations to characterize the behavior of thermal variable definitions and their consistency with continuum models of heat transport, e.g., Fourier, Maxwell-Cattaneo. We also performed spatial- and time-averaging simulation studies to determine the size limits at which fluctuations do not overwhelm the expectation values of continuum properties. Our results indicate that the use of a few thousand atoms and/or averaging over a few thousand time-steps constrains fluctuations in temperature to an acceptable degree. We have begun using these results to construct a thermomechanical continuum model for use in finite-temperature, finite-element calculations.

We are constructing routines needed for all expressions developed within our formulation that are essential for the calculation of energies and forces. Once our formulation is fully implemented, we will perform verifying test simulations of zero-temperature, quasi-static nanoindentation and surface relaxation of stretched nanowires to ensure proper transmission of forces. We documented our formulation for quasi-static, atomistic-continuum coupling....

Refereed

Zimmerman, J. A., E. B. Webb, III, J. J. Hoyt, R. E. Jones, P. A. Klein, and D. J. Bammann. 2003. Evaluation of continuum stress in atomistic simulation. *Proc. 2nd MIT Conference on Computational Fluid and Solid Mechanics* **1** (19 June, Cambridge, Massachusetts): 804–807.

Zimmerman, J. A., R. E. Jones, P. A. Klein, D. J. Bammann, E. B. Webb, III, and J. J. Hoyt. 2002. Continuum Definitions for Stress in Atomistic Simulation. Sandia Technical Report SAND2002-8608, Sandia National Laboratories, Livermore, California.

38685

Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications

D. J. Rader, J. N. Castaneda, M. A. Gallis, T. W. Grasser, J. R. Torczynski, W. M. Trott, L. E. Klebanoff

Momentum and heat transfer to surfaces immersed in noncontinuum transitional (rarefied)-gas flows continue to be active areas of research. Gases exhibit noncontinuum effects when the characteristic length scale of the system becomes comparable to the gas mean free path. Thus, rarefaction becomes important when either system length scales become small (e.g., microelectromechanical systems [MEMS]) or when gas pressures become low (e.g., semiconductor manufacturing). To predict momentum and heat fluxes, it is essential to understand the details of the gas-surface interaction; unfortunately, despite considerable effort, reliable interaction mechanisms are still lacking. Only two relevant experimental studies are found in the literature, and these two studies present limited data that are not in complete agreement. A combined experimental/modeling study is under way to better understand the critical role of gas-surface interaction in rarefied-gas flows. Sandia will make extensive, well-characterized experimental measurements of heat flux, gas density and/or temperature profiles, and aerosol forces in a quiescent transition-regime gas between two parallel plates. We will conduct tests with a broad range of diagnostics for a variety of gases (monatomic and polyatomic) using carefully controlled, well-characterized surfaces of different types (metals, ceramics) and conditions (rough, smooth). We will compare the experimental results to modeling predictions to identify areas of model strength and weakness. We will pay particular attention to validating current gas-wall interaction models and to developing new models, if needed. This work will have immediate benefit for extreme ultraviolet lithography (EUVL) particle protection work, will help validate rarefied-gas model performance, and will help develop the modeling and experimental tools that will be needed in Microsystems and Engineering Sciences Applications (MESA).

We completed the design, construction, and assembly of the experimental test chamber and most supporting systems. Operation of the test chamber shows that all of the key environmental-control subsystems are performing according to accuracy specifications that meet or exceed our design

This work will have immediate benefit for extreme ultraviolet lithography (EUVL) particle protection work, will help validate rarefied-gas model performance, and will help develop the modeling and experimental tools that will be needed in Microsystems and Engineering Sciences Applications (MESA).

requirements. High-precision pressure transducers are providing pressure measurements with an accuracy of better than 0.1% of reading. An automated flow controller maintains exceptionally stable chamber pressures; for example, the system can maintain a pressure of 30.00 ± 0.01 mTorr over long periods of operation. Temperature measurements made with calibrated, precision thermistors are accurate to better than 0.01 K. Temperature uniformity across the plates is maintained to better than 0.05 K. Two positioning robots control plate separation to within 10 μm .

We selected electron-beam fluorescence to provide a noninvasive measurement of the gas-density profile between the two plates. We installed an electron-beam subsystem in the test chamber. Tests show that the electron gun is operating according to specifications, providing an electron beam of suitable intensity with a diameter of about 200 μm . Demonstration of electron fluorescence in a gas-filled chamber is delayed due to challenges associated with beam alignment. A new design that will simplify the beam-alignment process is nearly complete.

We completed preliminary heat-flux measurements between two temperature-controlled plates separated by a small gap containing low-pressure nitrogen gas. These measurements showed that the conductive heat flux across 0.2 and 1 cm gaps can be clearly distinguished from radiation for pressures between 10 and 1000 mTorr. We performed verification studies of the direct-simulation Monte Carlo (DSMC) numerical method for the present parallel-plate geometry to demonstrate that the calculations approach the expected Chapman-Enskog continuum limit. This verification provides compelling support that the present DSMC implementation provides an excellent description of gas-gas collisions and is therefore a sound basis for exploring gas-surface effects. We found DSMC calculations for the ratio of nitrogen heat-flux across a 0.2 cm gap at 50 and 1000 mTorr to be in good agreement with the corresponding, measured heat-flux data.

Temperature measurements made with calibrated, precision thermistors are accurate to better than 0.01 K. Temperature uniformity across the plates is maintained to better than 0.05 K. Two positioning robots control plate separation to within 10 μm .

38686

High-Fidelity Frictional Models for MEMS*E. D. Reedy, Jr., M. P. De Boer, R. E. Jones, B. R. Antoun, A. D. Corwin, M. J. Starr*

Frictional losses play a dominant role in microsystem performance and reliability, but are not yet well-enough understood to enable the high-fidelity modeling and simulation needed for weapon component design and qualification. Surface interactions, currently treated in a global sense using classical friction laws, are insufficient for microelectromechanical systems (MEMS) in which single asperities and their interplay with interfacial roughness are the primary energy-dissipation mechanisms. First, Sandia will construct three-dimensional (3-D) computer models of the interface on the basis of surface topography, constitutive frictional relations for the asperity contacts, and surface interactions due to van der Waals forces. Second, we will evaluate and optimize novel MEMS friction test structures to explore a wide pressure-velocity space and develop necessary metrologies that yield information on slip for nanometer displacements. This will allow us to resolve microsecond time frames and enable the determination of velocity and stick-slip effects over many orders of magnitude. Third, we will model the frictional response at the mesoscopic scale. This modeling/experimental approach will allow us to connect frictional response across the length scales and will form the basis for microdomain-aware contact algorithms to be incorporated into the evolving multiphysics SIERRA code infrastructure. Successful completion of the project will yield validated grid-scale models for MEMS interfaces that accurately treat dissipation mechanisms.

This tightly coupled experimental/analysis project progressed on multiple fronts. We are measuring friction on the asperity, MEMS, and wafer-scale over a broad range of pressures and velocities to guide and validate the development of a MEMS-scale friction model. We are also performing simulations that explicitly model asperity interactions, including cross-gap surface forces, as well as developing a complementary homogenized model for grid-scale calculations.

We used atomic-force microscopy (AFM) images to determine the statistical parameters characterizing polycrystalline silicon (poly-Si) surface roughness and found that poly-Si surfaces contain a significant number of asperities with a height higher than that expected for a Gaussian

Successful completion of the project will yield validated grid-scale models for MEMS interfaces that accurately treat dissipation mechanisms.

distribution of surface heights (outliers). Rough surfaces have an even larger number of these outliers than smooth surfaces. Our AFM studies also revealed the presence of small particles on poly-Si surfaces, and some, although not all, of the high asperities on the surface are due to these particles. We are now trying to identify the source of these particles and determine whether these particles are persistent in actual MEMS devices and, hence, integral to contact behavior.

We also measured MEMS-scale friction with an inchworm test structure. As anticipated, the measured static friction is strongly dependent on the surface coating and is independent of normal load over a wide range of loads. There were also two unexpected findings. The first unexpected finding was that pre-sliding tangential deflections play an important role in frictional characteristics at the MEMS scale. That is, as tangential load is applied, but before the static friction limit is reached, stable in-plane deflections occur. We directly measured slip distances of 100 nm or more using a subpixel interpolation technique. Because the step size of our model inchworm test structure is only 40 nm, these stable pre-sliding deflections can dominate the operational behavior of this device. In the MEMS literature it was previously assumed that static coefficients of friction adequately governed device response. Our detailed experimental/modeling comparison revealed that this is decidedly not the case. Our second unexpected finding was that friction in MEMS is observed even when we apply a small tensile (negative) load to the inchworm test structure. We believe that the nonzero friction at zero and negative load is due to an adhesive contribution between the frictional counterfaces and have confirmed this with both interferometry and other static measurements. This finding represents a deviation from Amonton's Law for MEMS friction at low loads.

We extended our simulation capabilities by implementing an adhesion model into a beta version of the PRESTO finite-element (FE) code and used this capability to investigate the impact of adhesion on contact area. For the adhesion energies of interest ($15\text{--}50\text{ mJ/m}^2$), the effect of adhesion is most evident at relatively low loads, and indeed a nonzero contact area is predicted even when there is no applied compression. This latter finding is consistent with the inchworm measurement of friction under a tensile load. We also made progress in developing a computationally efficient, grid-scale model for designing and simulating the performance of MEMS components. The well-known Greenwood-Williamson (GW) analytic model has been generalized and implemented within an FE framework to make possible grid-scale calculations that

Our second unexpected finding was that friction in MEMS is observed even when we apply a small tensile (negative) load to the inchworm test structure. We believe that the nonzero friction at zero and negative load is due to an adhesive contribution between the frictional counterfaces and have confirmed this with both interferometry and other static measurements. This finding represents a deviation from Amonton's Law for MEMS friction at low loads.

include the effect of the rough surfaces. This framework is not specialized to the Gaussian distribution used in the original GW model and can employ a non-Gaussian summit height distribution with outliers such as we observed in our recent AFM measurements. We have also begun to develop a discrete version of GW, where the integration over the distribution is replaced with a discrete sum, to investigate how large the population of asperities must be for a GW model to apply.

Refereed

De Boer, M. P., *et al.* 2003. High-performance surface-micromachined inchworm actuator. *J. Microelectromechanical Systems*, accepted.

Jones, R. E. 2003. Models for contact loading and unloading of rough surfaces. *International J. Engineering Science*, submitted.

Jones, R. E., and D. Zeigler. 2003. A method for determining the asperity distribution of contacting rough surface. *ASME J. Tribology*, submitted.

Other Communications

Carpick, R. W., and J. D. Batteas. 2003. Scanning-Probe Studies of Nanoscale Adhesion Between Solids in the Presence of Liquids and Monolayer Films. To appear in *Handbook of Nanotechnology*, ed. B. Bhushan. Springer-Verlag.

Flater, E. E., *et al.* 2003. Toward prediction of MEMS performance: A topographic study of polycrystalline silicon for statistical modeling of rough surfaces in contact. Paper presented at the 25th Annual Symposium on Applied Surface Analysis, 3–6 June, Urbana, Illinois.

Jones, R. E. 2003. Modeling contact of rough surfaces. Paper presented at the 7th U.S. National Congress on Computational Mechanics, 27–31 July, Albuquerque, New Mexico.

Luck, D. L., *et al.* 2003. Evidence for pre-sliding tangential deflections in MEMS friction. *Transducers '03, Proc. 12th International Conference on Solid-State Sensors and Actuators* 1 (8–12 June, Boston, Massachusetts): 404–407.

38687

Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames

C. R. Shaddix, J. M. Suo-Anttila, R. W. Schefer, L. G. Blevins, S. P. Kearney, K. A. Jensen, T. C. Williams

Fires pose the dominant risk to the safety and security of nuclear weapons, nuclear transport containers, and Department of Energy and Department of Defense facilities. The thermal hazard from these fires primarily results from radiant emission from high-temperature flame soot. Therefore, it is necessary to understand the local transport and chemical phenomena that determine the distributions of soot concentration, optical properties, and temperature to develop and validate constitutive models for large-scale, high-fidelity fire simulations.

Soot formation has been extensively investigated in steady flames, using simple, pure hydrocarbon fuels. However, measurements and predictive models are lacking for soot formation when burning practical transportation fuels or for buoyant, unsteady diffusion flames representative of practical fires. In particular, we need temporally and spatially resolved measurements of the velocity and temperature fields; of the key chemical species responsible for soot formation and oxidation; and of soot concentration, size, and optical properties to provide the flux and rate information required to accurately determine soot production, transport, and radiation.

The work in this project will make a vital improvement in Sandia's ability to predict heat flux from fires by performing experiments in steady and pulsed diffusion flames, using both simple hydrocarbon gases (methane and ethylene) and a JP-8 surrogate fuel mixture. In situ laser diagnostic techniques for the hydroxide (OH) radical and the velocity field are being refined and perfected for sooty flames. In addition, we are applying novel laser diagnostics for soot, acetylene, and polynuclear aromatic hydrocarbon (PAH) concentrations, together with extractive analysis of soot morphology (via transmission-electron microscopy [TEM] grid sampling) and soot optical properties. Finally, we are attempting novel laser techniques for temperature measurements in flames (including filtered Rayleigh scattering). Spatially and temporally resolved measurements of thermal radiation will allow detailed comparisons between estimated and measured heat flux.

We performed extensive, phase-resolved measurements of OH and PAH planar laser-induced fluorescence (PLiF) and soot

Fires pose the dominant risk to the safety and security of nuclear weapons, nuclear transport containers, and Department of Energy and Department of Defense facilities....The work in this project will make a vital improvement in Sandia's ability to predict heat flux from fires by performing experiments in steady and pulsed diffusion flames, using both simple hydrocarbon gases (methane and ethylene) and a JP-8 surrogate fuel mixture.

laser-incandescence-induced (LII) (both simultaneously and individually) in a series of canonical methane and ethylene flames established on a pulsed slot burner. We also obtained corresponding planar images of near-infrared (NIR) soot emission. We obtained particle-imaging velocimetry measurements of the local flow velocity for the cold-flow inlet conditions and currently are obtaining them for the canonical flames. Fast-response thermopile detectors with an attached light-pipe demonstrated the ability to perform temporally resolved measurements of local thermal emission from the radiant flames. We made improvements to a thermophoretic TEM grid-sampling probe (for analyzing soot morphology and microstructure) after consulting with the original developer of this diagnostic. We assembled and demonstrated a modified sampler to effectively capture soot particles with minimal local disturbance of the flame.

We determined that under some forcing conditions in the pulsed slot flames, the dominant airside vortex shedding frequency became equal to $f/2$, and in some cases even $f/3$ or $f/4$. Under these conditions, the internal, soot-containing regions of the flame become uncoupled from the flame's outer vortical motions, appearing to result in enhanced soot formation.

We established inverse diffusion flames of air burning in methane and ethylene on the slot burner and performed imaging of OH and PAH PLiF, soot LII, and NIR soot emission in these flames.

We designed and fabricated a new, pulsed co-annular burner and are performing initial testing. This burner is fully conducive to planar sheet imaging. One version of this burner will operate on gaseous fuels and has a loudspeaker attached to the fuel plenum to produce controlled, repeatable, unsteady flames. We designed a matching burner for operation on JP-8 surrogate. We achieved flash vaporization of the JP-8 surrogate through the use of an electrically heated ceramic capillary pump/vaporizer. We accomplished modulation of the vapor fuel flow through the use of a model airplane engine cylinder attached to an electric motor.

We designed and fabricated a new, pulsed co-annular burner and are performing initial testing. This burner is fully conducive to planar sheet imaging.

Other Communications

Williams, T. C., C. R. Shaddix, and P. Desgroux. 2003. The response of pulsed, buoyant diffusion flames to forcing frequency and amplitude. *Proc. 3rd Joint Meeting of the U.S. Sections of the Combustion Institute V* (16–19 March, Chicago, Illinois): C10.

52537

Coupled Solid-Fluid Mechanical-Computational Modeling of Fracture and Fragmentation in Geomaterials, Such as Hard and Deeply Buried Targets (HDBTs)

R. A. Regueiro, R. E. Jones, R. P. Jensen, D. S. Preece, A. F. Fossum, A. A. Brown

Modeling fracture and fragmentation in geomaterials due to various loading and environmental conditions is a challenging problem and requires the latest in experimental, constitutive-modeling, and computational-solution-method technology. At Sandia, current geomaterial constitutive models and computational methods are incapable of predictively modeling the transition of continuous rocklike material to fragmented rock material within the context of coupled solid-mechanics and fluid-mechanics physics. To address this need, we seek to develop a physically based geomaterial constitutive model and computational method that can predictively model this transition. The constitutive-modeling effort will leverage an ongoing project that experimentally investigates the fundamental mechanisms of rock penetration, and the computational-development effort will rely on the coupled-physics, adaptive-mesh, massively parallel (MP) code-development framework named SIERRA.

Two problems that would be better understood with such a modeling capability are the defeat of hard and deeply buried targets (HDBTs) and the long-term performance of deep geologic nuclear-waste repositories. It would be useful to be

At Sandia, current geomaterial constitutive models and computational methods are incapable of predictively modeling the transition of continuous rocklike material to fragmented rock material within the context of coupled solid-mechanics and fluid-mechanics physics....we seek to develop a physically based geomaterial constitutive model and computational method that can predictively model this transition.

One-way coupling of discrete-element method (DEM)/finite-element method (FEM) (approach 2).

able to predict the behavior of these buried structures when they are subjected to extreme dynamic-loading conditions such as high-velocity-penetration events, explosive blasts, or seismic events. Presently, the mechanics of rock penetration are poorly understood, and there are no empirical data that can be used to forecast long-term performance (over thousands of years) of deep geologic nuclear-waste repositories. Obtaining approval of the Nuclear Regulatory Commission becomes difficult if the Department of Energy is restricted to using existing methodologies. In addition to modeling the defeat of HDBTs and the long-term performance of nuclear-waste repositories, the resulting computational-analysis tool will be useful for understanding fracture and fragmentation in geomaterials such as concrete, rock, frozen soil, and heavily overconsolidated clay encountered in tunneling construction, oil and natural-gas production, and depleted reservoirs used for subsurface sequestration of greenhouse gases.

We added a softening capability to our geomaterial plasticity model and conducted a bifurcation analysis assuming strong and weak discontinuity kinematics for both the rate-independent and rate-dependent forms of the model. For the rate-independent version of the model, different bifurcation conditions result for strong and weak discontinuities, as well as when bifurcation is continuous or discontinuous. Continuous bifurcation assumes that at the instant of bifurcation there is plastic loading outside the discontinuity as well as within/on it. Discontinuous bifurcation assumes there is elastic unloading outside the discontinuity and plastic loading within/on the discontinuity. For weak discontinuity, there is a difference between continuous and discontinuous bifurcation conditions, whereas for strong discontinuity, there is no difference. Since we plan to focus only on modeling strong discontinuities in this project, we do not distinguish between continuous and discontinuous bifurcation. Regardless, whether considering strong or weak discontinuity, or continuous or discontinuous bifurcation, we are left with solving for the unit normal η that satisfies the loss of ellipticity condition $\det A=0$, which results from the condition that traction is continuous across the discontinuity. This bifurcation condition $\det A=0$ in essence tells us that, at a given stress state, a discontinuity is admissible in our material body. This condition is necessary but not sufficient for the discontinuity to appear. It turns out that for the rate-dependent version of the model for finite, positive values of viscosity, loss of ellipticity $\det A=0$ will not be met (unless the viscosity is so small that the model is nearly rate-

In addition to modeling the defeat of HDBTs and the long-term performance of nuclear-waste repositories, the resulting computational-analysis tool will be useful for understanding fracture and fragmentation in geomaterials such as concrete, rock, frozen soil, and heavily overconsolidated clay encountered in tunneling construction, oil and natural-gas production, and depleted reservoirs used for subsurface sequestration of greenhouse gases.

independent), and hence the bifurcation condition $\det A=0$ is not a meaningful bifurcation condition for the rate-dependent geomaterial model. This requires us to determine a physically meaningful bifurcation condition for the rate-dependent version of the model. It seems physically meaningful to have similar bifurcation criteria for both rate-independent and rate-dependent versions of the model. This is one of the goals of this project and relies on observations from an experimental project that is investigating the failure mechanics of hard rock.

We tested a general three-dimensional (3-D) numerical algorithm that determines the bifurcation stress state at which strong and weak discontinuity modes of localized deformation are admissible to the boundary-value problem.

We began implementing the enhanced-strain hexahedral element in SIERRA via the sd3dh8 selectively reduced integration hexahedral element.

We developed a traction-displacement post-bifurcation geomaterial constitutive model and implemented it via a cohesive surface-element formulation. This same traction-displacement model will be implemented via the enhanced strain formulation in SIERRA. We will use a rigid-plastic model because it avoids introducing fictitious elastic compliance along the discontinuity surface.

We also demonstrated a one-way coupling of the discrete-element method (DEM) and the finite-element method (FEM) as applied to a shock wave meeting a buried tunnel. An example showed how discrete elements (in this case, circular disks) overlap quadrilateral FEs. These discrete elements are then constrained to move according to the displacement of the FE. The FE mesh calculates the far-field initial-boundary-value problem (in this example, a traveling shock wave). Another approach to DEM/FEM coupling that we plan to investigate is the following: The geomaterial constitutive model determines orientation and location of strong discontinuities; if a portion of the FE mesh becomes separated from the rest of the mesh, it is then treated as a discrete element, which can further fragment based on the geomaterial model and mesh within each discrete element.

Other Communications

Regueiro, R. A., and M. T. Manzari (Dept. of Civ. Env. Eng., George Washington University). 2003. Post-failure analysis of geomaterials with strong discontinuities. *Proc. 16th Engineering Mechanics Conference*, ASCE CD-ROM (16–18 July, Seattle, Washington): 1–6.

52609

Analysis of Nanoscale Films and Particles

E. D. Reedy, Jr.

Nanoscale films and structured materials are of increasing interest in emerging technologies of importance to Sandia. For example, hard tribological coatings, with a thickness of ~ 10–50 nm, are being considered for silicon microelectromechanical systems (Si-MEMS) and nickel (Ni)-LIGA (the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) structures. One critical aspect in the successful development of such materials is assessing their performance and durability. There are a number of potentially useful test methods to evaluate nanoscale films and particles. For example, stressed overlayers can induce ~ 10 nm-thick films to delaminate from a substrate, and nanoclusters can be pushed off of a substrate to which they adhere with a nanoscratch tester. Unfortunately, fundamental material parameters are not measured directly in such tests; rather, detailed mechanics-based models must be used in conjunction with the experimental data to deduce the desired properties. The deformation and failures generated in nanoscale tests are typically quite complex, and adhesion and elastic deformation often dominate material response (yielding normally occurs only at very high stress levels at the nanoscale). We anticipate that we will require adhesion and cohesive-zone (CZ) fracture models for our research.

We aimed this study at developing finite-element modeling (FEM) capabilities for simulating nanoscale tests. This work focused on methods to model (1) the adhesion of a particle to a substrate, and (2) the delamination of a thin film from a substrate. We modeled adhesion as a normal attractive force that depends on the distance between opposing material surfaces, while we simulated delamination using a CZ model. Both of these surface-interaction models were recently implemented into a beta version of Sandia's three-dimensional (3-D), transient-dynamics PRESTO finite-element (FE) code. Contact capabilities in PRESTO are provided by Sandia's Algorithms for Contact in a Multiphysics Environment (ACME), and we implemented CZ and adhesion models via ACME. There was also an initial effort to develop a third surface-interaction model that combines a nanometer-scale friction model with the adhesion model. This "junction" model was motivated by recent atomic-force microscope (AFM) data suggesting that the magnitude of nanometer-scale frictional

Nanoscale films and structured materials are of increasing interest in emerging technologies of importance to Sandia....We aimed this study at developing finite-element modeling (FEM) capabilities for simulating nanoscale tests.

resistance depends on the bimaterial pair's adhesion energy, but is independent of the contact stress.

We verified the PRESTO implementation of the adhesion and CZ models and performed numerous illustrative calculations. In all of these calculations, the materials were idealized as linear elastic. In fact, elastic deformation often dominates in nanostructured materials since conventional dislocation-based plastic deformation mechanisms are suppressed at this length scale. In one set of calculations, we determined the force required to pull a 25 nm-radius polysilicon (poly-Si) cylindrical off of a thick poly-Si substrate as a function of adhesion energy. To permit comparison with an available elasticity solution, we assumed the adhesional surface stress to be independent of the cross-gap distance up to a critical gap distance, beyond which surface stress vanished; we used a critical distance of 1 nm in all calculations. Calculated results were within 10% of the theoretical results for a coarse mesh with a minimum element size of 1.0 nm, and were within 2% when the minimum element size was reduced to 0.1 nm.

In another set of calculations, we pulled a 100 nm-thick tungsten layer off of a Si substrate. These calculations employed a CZ model similar to that originally formulated by Tvergaard and Hutchinson (*Journal of the Mechanics and Physics of Solids*). In this CZ model, the traction-separation relation is based on a potential function that depends on a scalar, effective separation. We analyzed a two-dimensional plane-strain model for a delaminated strip to permit the comparison of the calculated results with an analytic solution. We determined that the length of the delamination was a function of the center deflection for various values of adhesion energy, and there was good agreement between theory and the FE calculation. Other work included a preliminary attempt to model the buckle-driven delamination of a biaxially stressed film from a thick substrate. Large, dynamic, transverse deflections generated as the thin film abruptly buckles from the substrate complicate these calculations.

In one set of calculations, we determined the force required to pull a 25 nm-radius polysilicon (poly-Si) cylindrical off of a thick poly-Si substrate as a function of adhesion energy. To permit comparison with an available elasticity solution, we assumed the adhesional surface stress to be independent of the cross-gap distance up to a critical gap distance, beyond which surface stress vanished; we used a critical distance of 1 nm in all calculations. Calculated results were within 10% of the theoretical results for a coarse mesh with a minimum element size of 1.0 nm, and were within 2% when the minimum element size was reduced to 0.1 nm.

52611

Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices

J. R. Torczynski, M. W. Glass, M. A. Gallis

Sandia proposes developing a radiation-transport-based method to simulate noncontinuum gas flows for microscale devices with moving parts. Current noncontinuum gas-flow simulation methods are inadequate. Navier-Stokes-based techniques lump all noncontinuum effects into a boundary condition (BC), which is known to be inaccurate for near-free-molecular flows. Direct-simulation Monte Carlo (DSMC), the only generic noncontinuum technique available, requires long run times and large numbers of computational molecules for the low-speed, transient, three-dimensional (3-D) gas flows in microscale devices. The proposed method seeks to exploit the analogy between free-molecular flow and radiation transport. In each situation, transport is effected by particles (photons, molecules) traveling ballistically from one surface to another. Particle-surface interactions are directly analogous, and complex geometries (as exist in microsystems) can be treated. We will develop the proposed method to simulate transient flows with diffuse and/or specular surfaces and will assess the method by application to steady flows between two parallel plates, for which many results are available (analytical and DSMC). These plates will be stationary or move in their own planes and will have equal or different temperatures.

We made the following accomplishments:

- (1) We implemented and verified symbol-manipulation algorithms to determine the collision terms for discrete molecular velocities and to encode these collision terms in standard FORTRAN.
- (2) We developed and verified a FORTRAN code implementing transport, collisions, and boundary interactions (diffuse reflection, specular reflection, bounce-back reflection, and linear combinations thereof). We applied this code to gas flows between parallel plates and examined two types of flows in detail: Couette flow, which is isothermal but has the walls moving tangentially; and Fourier flow, which is motionless but has the walls at different temperatures. We examined these flows from near-free-molecular to near-continuum conditions. We examined models with the following numbers of discrete-molecular-velocity states: 8, 32, 56, 88, and 136. These models contain one free parameter, the speed scale of the discrete-velocity states. In all cases, although the method produced

Sandia proposes developing a radiation-transport-based method to simulate noncontinuum gas flows for microscale devices with moving parts....The proposed method seeks to exploit the analogy between free-molecular flow and radiation transport....We will develop the proposed method to simulate transient flows with diffuse and/or specular surfaces and will assess the method by application to steady flows between two parallel plates, for which many results are available (analytical and DSMC).

qualitative agreement with DSMC and analytical results, the method's results typically differed by 10% or more from known results. This discrepancy is related to the coarseness of the representation of the distribution of molecular velocities; however, reduction of the error to an acceptable level appears to require a very large number of velocity states. Thus, the method does not appear to be promising.

52613

Tensegrity—Smart, Adaptive Structures Through Material Biomimicry

P. A. Klein

Tensegrity is the word coined by Buckminster Fuller as a contraction of tensional integrity. A tensegrity system is established when a set of discontinuous compressive components interacts with a set of continuous tensile components to define a stable volume in space. Tensegrity structures are mechanically stable, not because of the strength of individual members, but because of the way the entire structure distributes and balances mechanical stresses. Tensile forces naturally transmit themselves over the shortest distance between two points, so the members of a tensegrity system are precisely positioned to best withstand stress. Thus, tensegrity systems offer a maximum amount of strength for a given amount of material.

Man-made structures have traditionally been designed to avoid developing large tensile stresses. In contrast, nature always uses a balance tension and compression. Tensegrity principles apply at essentially every size scale in the human body. Macroscopically, the 206 bones that constitute our skeleton are pulled up against the force of gravity and stabilized in a vertical form by the pull of tensile muscles, tendons, and ligaments.

Sandia proposes a feasibility study to explore the potential of applying tensegrity principles in designing materials with desired functionalities. We may exploit principles of self-assembly of tensegrity to produce materials that have intrinsic capabilities for adapting to changing loads (self-healing), as with the ongoing reconstruction of living bone under loading. Such materials should have microstructures that could be controlled, or altered, by externally applied signals as by electrophoresis or induced phase changes. Simulations could explore the time- and load-dependent response of such adaptive materials.

The objective of this work was to find potential applications for the principals of solid and materials mechanics in understanding the structure and function of biological materials. This is the first step to understanding biological materials from a mechanics perspective to develop new materials that mimic the advantageous properties of biomaterials. Tensegrity principals have been used to link the structure and function of biological materials. We performed a literature survey to

Man-made structures have traditionally been designed to avoid developing large tensile stresses. In contrast, nature always uses a balance tension and compression....Sandia proposes a feasibility study to explore the potential of applying tensegrity principles in designing materials with desired functionalities....Such materials should have microstructures that could be controlled, or altered, by externally applied signals as by electrophoresis or induced phase changes. Simulations could explore the time- and load-dependent response of such adaptive materials.

establish a thorough understanding of such structures and proposed applications. Current tensegrity research can be categorized into four areas:

- (1) Structures, including architectural and space applications
- (2) Mathematics, including graph theory, group theory, geometry, and symmetry
- (3) Mechanics, including linear/nonlinear, static/dynamic, vibration, and modal analysis
- (4) Biology, including cell structure and biomechanics.

The numerous examples of existing man-made tensegrity structures clearly demonstrate the utility of the idea. The research in mathematics has been largely focused on developing a rigorous description of tensegrity structures with the intent of classifying them in terms of symmetries, which can then be used to systematically generate tensegrity structures of increasing complexity. Basic mechanics of short compressive members and extended tensile members can readily be applied to develop computer models that predict how tensegrity structures sustain loads.

The most fascinating application of tensegrity principals comes in the area of biology. Many researchers in the fields of cell biology and biomechanics are using tensegrity concepts to good effect. For example, a model explaining deformability of adherent cells has been proposed using tensegrity architecture. What is missing in the study of biological materials in terms of tensegrity principals is a notion of how the materials come to develop this structure in the first place. The idea of hierarchical self-assembly is the natural complement to the hierarchical structural principal of tensegrity. It is often noted in the literature that self-assembly of biomolecules is a promising avenue toward development of new materials. Engineering principles for micro- and nanofabrication can be discovered from the study of molecular self-assembly phenomena in nature. Biological tissues serve as model factories for the production of macromolecular structures, where the processes of molecular self-assembly and macroscopic growth are integrated in robust systems, which display self-healing and adaptivity. With this in mind, Sandia is developing the extension of this work that will study the processes of self-assembly and growth in collagen from the macromolecular to the continuum scale. The mathematical description of growth constitutes a highly complex system that requires mixture theory with coupled diffusion-reaction and mechanics, and differs significantly from classical continuum formulations of closed systems. This project provides the opportunity for

The most fascinating application of tensegrity principals comes in the area of biology. Many researchers in the fields of cell biology and biomechanics are using tensegrity concepts to good effect....Sandia is developing the extension of this work that will study the processes of self-assembly and growth in collagen from the macromolecular to the continuum scale.

Sandia to uncover fundamental principles in the extension of characteristics of biological systems to the development of new engineering materials, and to extend its leadership in computational and engineering science to a pioneering role in biotechnology.

This project provides the opportunity for Sandia to uncover fundamental principles in the extension of characteristics of biological systems to the development of new engineering materials, and to extend its leadership in computational and engineering science to a pioneering role in biotechnology.

52615

Coupled Acoustical/Structural Simulations of Weapons Systems

T. F. Walsh, J. L. Dohner, H. Sumali

Many engineering systems of interest to the weapons community, including MEMS (microelectromechanical systems), SAWS (surface acoustical-wave systems), re-entry vehicles, buried bunkers and caves, acoustical weapons, and submarines, require simulations with the capability for coupled acoustical-structure interactions. The finite-element (FE) code SALINAS (a massively parallel [MP] structural dynamics code) recently demonstrated the capability of solving problems with over 100 million degrees of freedom in MP computations, and thus provides a unique capability for solving complex structural analysis problems. However, SALINAS currently lacks an acoustical capability.

The complexities of the weapons applications provide several research issues in the area of coupled acoustic/structure simulations.

- It is unknown how acoustical phenomena differ from the microscale to the macroscale, and whether the same physical laws can be used. This will require some research on the acoustical formulation and implementation. Large amplitude and dispersion effects may become important in many of the weapons systems applications.

- MEMS, buried bunkers and caves, submarines, and re-entry vehicles are all exterior problems and thus require domain truncation procedures. Infinite elements accomplish this most effectively, but time-domain formulations and load balancing with these elements in coupled simulations are still areas of research.

This research will provide acoustical simulation capability within the SALINAS framework, including infinite elements and acoustics with shear. Initially, we will focus on a representative MEMS model for validation and comparisons to experiment, and then follow this with other applications listed above.

(1) We developed FE acoustic formulations based on fluid velocity potential and fluid displacement.

(2) We investigated domain decomposition and diagonal scaling preconditioners for parallel implementation of coupled structural acoustics.

(a) Symmetric diagonal scaling reduced the number of iterations for the parallel linear solves by at least a factor of 2.

Simulation of scattering of a plane acoustic wave on an elastic sphere. The isocontours of velocity potential are shown.

The finite-element (FE) code SALINAS recently demonstrated the capability of solving problems with over 100 million degrees of freedom in MP computations,...However, SALINAS currently lacks an acoustical capability....This research will provide acoustical simulation capability within the SALINAS framework....

(b) For the coupled structural-acoustics problem, we found an arbitrary domain decomposition to be the most convenient approach, though not necessarily the most efficient.

(c) For the fluid-displacement formulation, both pressure and shear waves in fluid can be captured by an acoustic formulation that includes viscosity. Since commercial acoustics codes ignore viscosity, this is considered a new result.

(3) We built an acoustic-wave tube for the purposes of testing acoustic loading on simple structures. The tube was an effective means of testing acoustic loading on simple structures.

(4) We built a microtorsional disk and tested it for the purpose of examining the effect of acoustic-shear-wave dissipation in MEMS.

Materials Science and Technology

The Materials Science and Technology investment area supports Sandia's national security mission by developing innovative materials and materials-processing concepts to enhance our ability to steward the nuclear weapon stockpile and to minimize or mitigate possible national security threats. Research investigations focus on advancing Sandia's commitment to microsystems utilizing optical, electro-mechanical, magnetic, and chemical functions to sense, think, act, and communicate. Research efforts also support the revolution in nanoscale science and biotechnology, science-based materials and processing, and predictable performance of complex systems. This research offers the opportunity to build tailored materials and structures atom by atom. Technological developments are expected that will rival the impact of the transistor.

Micromachines have the potential to significantly impact future weapon-component designs as well as other defense, industrial, and consumer-product applications. The influence of processing on structure and the resulting effects on material properties are not well understood. *Mechanics and Tribology of MEMS Materials* will develop a basic understanding of deformation, fracture, and surface interactions responsible for friction and wear of microelectromechanical systems

(MEMS) materials. This will enable needed design flexibility for these devices, as well as strengthen our understanding of materials behavior at the nanoscale. Increased understanding of MEMS mechanics and tribology developed in this project will permit performance and reliability of advanced MEMS components to be predicted with a sound scientific basis.

One patent disclosure has been filed.

26525

Magnetic-Field Effects on Vacuum-Arc Plasmas

P. A. Miller, M. M. Hopkins, D. R. Welch

The two primary goals of this project are (1) to better understand the role of the self-magnetic field on the vacuum-arc ion source in neutron tubes (NTs) and (2) to realize magnetic shaping of the plasma plume from the ion source. The role of magnetic fields has heretofore largely been ignored, both in experimental tube work and in Accelerated Strategic Computing Initiative (ASCI) computations. Sandia's work will improve the science base for NTs. We gathered experimental data and computational modeling of the effects of applied magnetic fields on arc impedance and on plasma plume shape. We performed tests using magnetic fields to achieve annular plasma plumes. Such shapes would be better matched to the geometric acceptance region of present types of NTs. Such shaping would enable more efficient use of plasma, thereby allowing reduced power-supply requirements.

The two primary goals of this project were (1) to better understand the role of the self-magnetic field on the vacuum-arc ion source in NTs and (2) to realize magnetic shaping of the plasma plume from the ion source. This project, now complete, showed that few-hundred-Gauss magnetic fields indeed have strong effects on the vacuum arc, such as increasing the potential drop across the arc by a factor of 2. This project demonstrated that applied magnetic fields can reshape the plasma plume. Two-dimensional (2-D) calculations using the LSP code predicted that a simple uniform axial magnetic field of 300 Gauss would produce an annular plasma plume. Experiments showed similar trends, but the annularity is less pronounced than predicted, and 3-D effects were strong. Data showed an azimuthal asymmetry that prevented producing a smooth annulus. This spatial nonuniformity apparently is due to the interaction of the applied magnetic field with the self-field of the arc. The experiment also detected temporal instability (radio-frequency oscillations) in cases where the plasma crossed magnetic-field lines. This instability is likely to be an interchange (flute) instability. Currently, 3-D code calculations with a new version of LSP are in progress.

The role of magnetic fields has heretofore largely been ignored, both in experimental tube work and in Accelerated Strategic Computing Initiative (ASCI) computations. Sandia's work will improve the science base for NTs.

26526

Microstructural and Continuum Evolution Modeling of Sintering

V. Tikare, J. G. Arguello, Jr., M. V. Braginsky, J. P. Arellano

Sandia developed two models that give a complete description of sintering at the mesoscale and at the macroscale. The first is a kinetic, Monte Carlo (MC) model that simulates microstructural evolution at the mesoscale during sintering. The second is a continuum, finite-element model (FEM) that simulates component shrinkage and deformation at the macroscale. We validated both models by comparing the results to analytical predictions and to experimentally determined behavior. We also showed that together they are able to give more accurate solutions to sintering of components. We showed the utility of these models by applying them to several problems of sintering, including sintering of a powder compact of aligned elongate particles.

All ceramics and powder metals, including the ceramics components that Sandia uses in critical weapons components, such as lead zirconate titanate (PZT) voltage bars and current stacks, multilayer ceramic METs, alumina/molybdenum and alumina cermets, and zinc oxide (ZnO) varistors, are manufactured by sintering. Sintering is a critical, possibly the most important, processing step during manufacturing of ceramics. The microstructural evolution, the macroscopic shrinkage, and the shape distortions during sintering will control the engineering performance of the resulting ceramic component. Yet modeling and prediction of sintering behavior is in its infancy, lagging far behind the other manufacturing models, such as powder synthesis and powder compaction models, and behind models that predict engineering properties and reliability. We developed a model that is capable of simulating microstructural evolution during sintering, providing constitutive equations for macroscale simulation of shrinkage and distortion during sintering. We also developed macroscale sintering simulation capability in JAS3D.

The mesoscale model can simulate microstructural evolution in a complex powder compact of hundreds or even thousands of particles of arbitrary shape and size by (1) curvature-driven grain growth, (2) pore migration and coalescence by surface diffusion, and (3) vacancy formation, grain-boundary diffusion, and annihilation. We validated this model by comparing predictions of the simulation to analytical predictions for simple geometries. We then used the model to

Sandia developed two models that give a complete description of sintering at the mesoscale and at the macroscale....We validated both models by comparing the results to analytical predictions and to experimentally determined behavior. We also showed that together they are able to give more accurate solutions to sintering of components....Sintering is a critical, possibly the most important, processing step during manufacturing of ceramics.

simulate sintering in complex powder compacts. We obtained sintering stress and materials viscous moduli from the simulations. These constitutive equations were then used by macroscopic simulations for simulating shrinkage and shape changes in FEM simulations.

We combined the continuum theory of sintering embodied in the constitutive description of Skorohod and Olevsky with results from microstructure evolution simulations to model shrinkage and deformation of ceramics. The continuum portion is based on an FE formulation that allows 3-D components to be modeled using Sandia's nonlinear large-deformation FE code, JAS3D. This tool provides a capability to model sintering of complex 3-D components. We verified the model by comparing it to simulation results published in the literature. We validated the model using experimental results from various laboratory experiments performed by Garino.

In addition, we used the mesoscale simulations to study anisotropic shrinkage in aligned, elongated powder compacts. Anisotropic shrinkage occurred in all compacts with aligned, elongated particles. However, the direction of higher shrinkage was in some cases along the direction of elongation and in other cases in the perpendicular direction, depending on the details of the powder compact. In compacts of simple-packed, monosized, elongated particles, shrinkage was higher in the direction of elongation. In compacts of close-packed, monosized, elongated particles and of elongated particles with a size and shape distribution, the shrinkage was lower in the direction of elongation.

We also explored the concept of a sintering stress tensor rather than the traditional sintering stress scalar concept for the case of anisotropic shrinkage. We presented a thermodynamic treatment of this, as well as a method to calculate the sintering stress tensor.

We developed a user-friendly code that can simulate microstructural evolution during sintering in 2-D and in 3-D. This code can run on most UNIX platforms and has a motif-based graphical user interface (GUI). The microstructural evolution is shown as the code is running, and many of the microstructural features, such as grain size, pore size, the average grain-boundary length (in 2-D) and area (in 3-D), etc., are measured and recorded as a function of time. The overall density as the function of time is also recorded.

The continuum portion is based on an FE formulation that allows 3-D components to be modeled using Sandia's nonlinear large-deformation FE code, JAS3D. This tool provides a capability to model sintering of complex 3-D components.

Refereed

Bell, N., T. Headley, and V. Tikare. 2003. TEM examination of reacting silver nanoparticles in percolating sphere networks. *J. Materials Research Society*, to be submitted.

Tikare, V., M. V. Braginsky, and E. A. Olevsky. 2003. Numerical simulation of solid-state sintering I: Sintering of three particles. *J. American Ceramic Society* **86**:49–53.

Tikare, V., M. V. Braginsky, E. A. Olevsky, and D. L. Johnson. 2003. Numerical simulation of anisotropic shrinkage in a 2-D compact of elongated grain. *J. American Ceramic Society*, submitted.

Zavaliangos, A., V. Tikare, and E. A. Olevsky, editors. 2003. Modeling and numerical simulation of materials behavior and evolution. *Proc. Materials Research Society*.

Other Communications

Arguello, J. G., V. Tikare, T. J. Garino, and M. V. Braginsky. 2003. Three-dimensional simulation of sintering using a continuum modeling approach. *Proc. Electronic Sintering 2003* **3** (September, State College, Pennsylvania).

Tikare, V., M. V. Braginsky, T. J. Garino, J. G. Arguello, and E. A. Olevsky. 2003. Numerical simulation of sintering at multiple length scales. *Proc. Electronic Sintering 2003* **3** (September, State College, Pennsylvania).

26527

Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters

L. L. Whinnery, Jr., S. K. Griffiths, R. H. Nilson, T. J. Shepodd

Microsystems are currently being evaluated as possible replacements for a number of weapon subsystems with the expectation of improved surety combined with reduced weight and volume. However, there is great concern that long periods of dormant storage may impair the mechanical functioning of microdevices that are exposed to water, outgassing products (organics, solvents, and silicones), and particulates (talc and dust). Low-temperature operating environments and small moving parts in contact with stationary and mating structures make capillary condensation, ice formation, and corrosion true concerns for microsystems. Past experience provides little guidance, and the desiccants currently used to manage system-wide moisture levels cannot be relied on to provide the more stringent control needed to ensure microsystem reliability.

Sandia is developing a new generation of irreversible, chemically reacting getters specifically targeted toward ensuring the integrity of the local environment within microsystem packages. We intend to incorporate volatile species into a polymer through covalent bonds, thus producing a nonvolatile product. We will combine these reactive getters with getters that rely on absorption media (e.g., zeolites and high-surface-area carbon fibers) to scavenge nonreactive species, like solvents. Our getter systems will rely on device packaging to limit exchange between the microsystem and the global weapon environment. Thus, the internal getters need only provide local environmental control within the microsystem package. If the getters themselves are not tacky, they will be incorporated into a tacky polymer matrix to immobilize microparticles in a harmless location. We will use modeling and analysis of available data to estimate the ingress of undesirable species as well as the gettering rates, capacities, and geometries needed to maintain an acceptable environment within the package. We will develop getters that utilize chemical reactions, adsorption, and physical adhesion to ensure a benign dormancy environment within microdevice packages.

We concentrated on scavenging water, ethanol, and isopropanol with commercially available isocyanate and anhydride polymers. Gettering of a reactive species with maleic anhydride polymers involves ring opening of the anhydride

Microsystems are currently being evaluated as possible replacements for a number of weapon subsystems with the expectation of improved surety combined with reduced weight and volume....Sandia is developing a new generation of irreversible, chemically reacting getters specifically targeted toward ensuring the integrity of the local environment within microsystem packages....We will develop getters that utilize chemical reactions, adsorption, and physical adhesion to ensure a benign dormancy environment within microdevice packages.

polymer to form an ester and carboxylic acid (for reaction with ethanol and isopropanol) or a dicarboxylic acid (for reaction with water). For reaction with an isocyanate polymer, a urethane linkage results from getting ethanol and isopropanol. Isocyanate reaction with water results in forming an intermediate carbamic acid, which spontaneously decomposes to yield CO₂ (carbon dioxide) and a primary amine. We investigated functionalized polymers as the getting species to minimize the chance of contamination of the local atmosphere with another volatile organic species.

We used weight change to monitor reactions during getting capacity evaluations (excess solvent). We used infrared spectroscopy to examine the changes in functional groups accompanying the reaction. A commercially available isocyanate polymer resulted in 73%, 29%, and 36 % conversion, for water, ethanol, and isopropanol, respectively. With the intent of trying to get higher capacities (percent conversion), we next looked at polymeric anhydrides. Initial testing with commercially available poly(maleic anhydride-alt-1-octadecene) resulted in 0%, 73%, and 8% conversion, for water, ethanol, and isopropanol, respectively. Similar experiments using 4-dimethylaminopyridine (DMAP) as catalyst gave 78%, 69%, and 70% conversion, for water, ethanol, and isopropanol, respectively. Stoichiometric reaction resulted in 33%, 47%, and 59% conversion, for water, ethanol, and isopropanol, respectively. Preliminary results show that poly(ethylene-alt-maleic anhydride) is an excellent getter for water with an experimental weight gain of 11.7% (82% conversion) after only one week of reaction.

We also worked with Inter Basic Resources to design and build a particle-counting system to evaluate various particle-getting strategies (tacky polymers, permanently charged polymers). The system is operational, and control experiments are currently under way.

26528

Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance

C. J. Brinker, H. K. Baca, R. J. Simonson, D. Y. Sasaki, J. Cesarano, III, S. M. Brozik

Emerging worldwide threats of biological and chemical terrorism, including recent experiences with anthrax, have established the need for miniaturized, stand-alone sensor systems. Rapid progress in genomics affords the potential for development of cell-based sensor arrays that effectively use a living cell's complex biochemical-response pathways to provide unprecedented functional information about chemical and biological warfare (CW/BW) agents. Living cells, in a manner analogous to the canaries once used to detect toxic gases in coal mines, respond to unknown toxicants in a physiologically relevant manner, incorporating signal recognition, amplification, and transduction in a remarkably complex yet compact package.

Currently, noninvasive detection of cellular response to toxic substances relies predominantly on measuring metabolic products exported by the cell, changes in cell adhesion, or the response of electrogenic cells such as neural networks. These methods, which are application-driven for specific, identified toxins, lack flexibility and may require complicated microelectronic interfaces.

Central to the development of functional microarray cytosensors is the localization and confinement of the cell on a sensor platform while maintaining cell viability, sustainability, and functionality. Bulk silica matrices formed by "classical" sol-gel processing have been used for cell entrapment, but

Rapid progress in genomics affords the potential for development of cell-based sensor arrays that effectively use a living cell's complex biochemical-response pathways to provide unprecedented functional information about chemical and biological warfare (CW/BW) agents.

(a) A porous nanostructure silica matrix forms around the cell through phospholipid-directed self-assembly, providing protection and confinement in a self-sustained buffered environment and conserving cell functionality; (b) at the molecular scale, genetically engineered cells provide signal detection, amplification, and transduction; (c) biocompatible patterning separates buffered cells from sol components and positions cells for individual addressability.

alcohol solvents and broad pore-size distributions limit cell viability and accessibility. Furthermore, bulk gels are difficult to integrate into devices like microelectromechanical systems (MEMS). Sandia used evaporation-induced self-assembly (EISA) to immobilize cells within periodic silica nanostructures, characterized by unimodal pore sizes and pore connectivity, that can be patterned using inkjet printing or photopatterning. By introducing a living cell into an inorganic/surfactant system capable of self-assembly, we added both a metabolically active entity and a heterogeneous, dynamically controlled surface to the system. We found that the interface plays an important role in both promoting cell viability and directing the structure of the inorganic phase, with the cell actively influencing its microenvironment.

- *Biocompatible cell immobilization.* We used a several-pronged approach to provide the biocompatible materials and processing conditions necessary to maintain cell viability while retaining control over the microstructure of the inorganic host. Biocompatible templates, high water content, buffered sols, and compartmentalization of sol components within multiple reservoirs prior to coating allowed us to immobilize genetically engineered *Staphylococcus cerevisiae* cells in a nanostructured silica host and to detect an environmental stimulus through expression of green fluorescent protein (GFP). Because traditional surfactants are highly toxic to cells in the concentration ranges needed to direct self-assembly, we replaced them with amphiphilic phospholipids that are integral parts of the cell membrane. Phosphocholines, with zwitterionic headgroups and short, double hydrocarbon tails, minimize disruptive electrostatic interactions with cell membranes and can form micelles with significantly high curvature to give three-dimensional (3-D) interconnected phases rather than the usual planar bilayers found in membrane structures. We found no loss in viability or functionality of cells exposed to low concentrations of short-tailed diacylphosphatidylcholines for over 2 hrs. While cells immobilized in silica alone show little viability after several hours, the viability of cells immobilized in the presence of lipid is 75% at 2 hrs and 50% at 4 days.

- *Cell-directed self-assembly and characterization of the silica/cell interface.* Using confocal fluorescence microscopy of fluorescently labeled lipids combined with *in situ* grazing-incidence small-angle x-ray scattering (GISAXS, performed at the XOR-1 (x-ray operations and research) beam-line, Advanced Photon Source, Argonne National Laboratory), we found that conducting EISA in the presence of living yeast cells

Sandia used evaporation-induced self-assembly (EISA) to immobilize cells within periodic silica nanostructures,....By introducing a living cell into an inorganic/surfactant system capable of self-assembly, we added both a metabolically active entity and a heterogeneous, dynamically controlled surface to the system. We found that the interface plays an important role in both promoting cell viability and directing the structure of the inorganic phase, with the cell actively influencing its microenvironment.

strongly influences the self-assembly pathway, with the cell surrounded by a multilayered organized lipid interface that dictates the structure formed during organization of the silica phase and maintains cell viability and functionality. Results from Fourier-transform infrared (FTIR) studies of immobilized cells indicate that a cell-based process gradually degrades exogenous lipids in the biocomposite film, with the living cell possibly using surrounding lipids as a nutrient source.

- *Cell signaling.* We induced GFP expression in both films and micromolded channels that had condensed and dried in air for over 24 hrs. We used hyperspectral imaging (HSI) to successfully map GFP expression in immobilized cells, confirming the potential for the remote sensing and individual addressability of reporter cells. We achieved expression of fluorescent proteins in *S. cerevisiae* using a pYES2 (high copy number) expression vector and the CFP (cyan fluorescent protein) and YFP (yellow fluorescent protein) genes present in pDH3 and pDH5, respectively, producing large amounts of unlocalized fluorescent protein. We constructed two additional cell lines in which the fluorescent protein sequence is integrated into the genomic sequence of *S. cerevisiae* S288C and regulated by an *S. cerevisiae* gene.

- *Cell patterning and localization.* The development of biocompatible sol-gel systems with appropriate rheology and pH has allowed us to pattern cells through inkjet printing (IJP). By controlling the extent of condensation through choice of precursors and reaction conditions, we can maintain the viscosity of the sol at a level that allows flow through a printer nozzle, with formation of the polymerized gel stage occurring as the solvent evaporates or is absorbed after printing. We patterned cells and sol sequentially, with centering of the cell occurring within the sol droplet as the sol coalesces and the silica condenses. We successfully mapped GFP expression in immobilized cells using HSI and developed processes and automated techniques for precision deposition of materials onto planar and nonplanar substrates. We deposited the materials in three dimensions with resolutions as fine as 100 μm . The delivery can be accomplished by drop-on-demand IJP or with a precisely controlled syringe and orifice. We attached a laser profilometer to the robotic deposition equipment to measure the topology of the substrate. We also created software that can modify a computer-aided-design (CAD) file of the desired pattern to be built in a conformal fashion on the substrate. We demonstrated the precise deposition of inks, ceramics, and polymers.

We also created software that can modify a computer-aided-design (CAD) file of the desired pattern to be built in a conformal fashion on the substrate. We demonstrated the precise deposition of inks, ceramics, and polymers.

Refereed

Calvert, P. 2003. Inkjet printing for building multilayer devices. (Invited) *Polymer Preprints, Proc. 226th American Chemical Society National Meeting* (September, New York, New York).

Other Communications

Baca, H. K., and C. J. Brinker. 2003. Biocompatible cell immobilization in self-assembled nanostructures. (Invited) Paper presented at the DOE Nanoscale Science Research Centers Workshop: Building for the Nanoscience Revolution, February, Albuquerque, New Mexico.

Baca, H. K., C. Ashley, T. Hartenberger, D. D. Dunphy, and C. J. Brinker. 2003. Biocompatible self-assembled nanostructures and characterization of the abiotic/biotic interface. Paper presented at the Materials Research Society Meeting, April, San Francisco, California.

Baca, H. K., C. Ashley, T. Hartenberger, D. R. Dunphy, and C. J. Brinker. 2003. Cell immobilization in nanostructures formed by biocompatible self-assembly. Paper presented at the Center for Micro-Engineered Materials, Semiannual Industrial Advisory Board, March, Albuquerque, New Mexico.

Calvert, P. 2003. Inkjet printing as a mimic for biological growth. (Invited) Paper presented at the Materials Research Society Spring Meeting, April, San Francisco, California.

Calvert, P. 2003. Inkjet printing of materials as a mimic of biological growth. (Invited) Paper presented at the Georgia Tech Nanotechnology Meeting, Atlanta, Georgia.

Calvert, P. 2003. Inkjet printing of materials as a mimic for biological growth. (Invited) Paper presented at the University of Florida College of Dentistry, July, Gainesville, Florida.

Calvert, P. 2003. Inkjet printing of self-assembling polymers. Paper presented at the Materials Research Society Spring Meeting, April, San Francisco, California.

Cesarano, J., III. 2003. Robocasting three-dimensional structures with fine-particle pastes. Paper presented at Particles 2003: Imaging, Marking, and Printing Applications of Particle Technology, August, Toronto, Canada.

26530

First-Principles Determination of Dislocation Properties

J. C. Hamilton, D. L. Medlin

Sandia used first-principles methods to determine important properties of grain boundaries. We calculated diffusion rates for carbon (C) in nickel (Ni) grain boundaries showing a very large anisotropy in diffusion rates with fast diffusion occurring along the tilt axis. We studied the faceting of grain boundaries and proved that the conventional understanding of finite facet sizes is wrong. This involved a careful calculation using first principles of grain-boundary stress. We published several papers on these subjects.

We studied the finite-size faceting of grain boundaries and showed that the standard model for equilibrium stabilization of finite facets by grain-boundary stress is wrong for aluminum (Al) sigma 3 null-type facets. The theoretical analysis involved three important aspects. We first developed a quantitative analytical model using continuum elasticity. This analytical model gave the minimum critical value for the grain-boundary stress required to stabilize finite facets. We next calculated numerical values for the grain-boundary stress using the embedded atom method (EAM) and first-principles codes. Both methods showed that the grain-boundary stress was much too small to stabilize finite facets. Finally, we confirmed this result by an EAM calculation comparing the energy of various grain-boundary configurations with different facet sizes. We found that the energy was a monotonically increasing function of facet size, indicating that the facet size would tend toward infinity in equilibrium. We concluded that finite facets are likely due to kinetic effects at least for this well-studied grain boundary.

We also used first-principles calculations with the elastic band method to calculate diffusion pathways and activation energies for C in Ni sigma 3 null-type grain boundaries. We found that diffusion is much faster along the tilt axis.

Sandia used first-principles methods to determine important properties of grain boundaries....We first developed a quantitative analytical model using continuum elasticity. This analytical model gave the minimum critical value for the grain-boundary stress required to stabilize finite facets.

Refereed

Hamilton, J. C., D. J. Siegel, I. Daruka, and F. Leonard. 2003. Why do grain boundaries exhibit finite facet length? *Physical Review Letters* **90**:24602.

Siegel, D. J., and J. C. Hamilton. 2003. First-principles study of the solubility, diffusion and clustering of carbon in nickel. *Physical Review B* **68**:094105.

Siegel, D. J., M. van Schilfgaarde, and J. C. Hamilton. 2003. Understanding the magnetocatalytic effect: Magnetism as a driving force for surface segregation. *Physical Review Letters*, submitted.

32915

Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment

S. M. Thornberg, J. D. Sanders, J. R. Brown, C. J. Flack

A variety of applications use the spin-coating procedure to coat flat substrates or objects with thin films of material. The coating material is disbursed onto the surface of the substrate, then spun off, ideally leaving a uniform layer for subsequent processing procedures. As the material is dispensed onto a spinning wafer, spiral-shaped wave fronts can be observed as the fluid migrates outward radially across the wafer. Spin-coating has traditionally been one of the first steps in semiconductor manufacturing.

In collaboration with the University of New Mexico, Sandia performed an experiment aboard the National Aeronautics and Space Administration's (NASA's) KC-135 Reduced Gravity Flying Laboratory to study the feasibility of spin-coating in a weightless environment. This was the final round in a three-year series of annual flights, started in March 2001. We successfully prepared a significant portion of wafers in zero-gravity (0-G) in the 2003 flight campaign (a total of 25)—more than in the previous 2 years combined.

The goal of this experiment was to spin-coat a series of silicon (Si) wafers with photoresist in a 0-G environment and compare them with wafers prepared using identical experimental parameters in the lab. Although the original experimental matrix underwent some changes during the course of the experiment, we acquired a significant population of data. We successfully prepared 3 wafers on the first flight and 26 wafers on the second flight. Analysis of these wafers confirms that the modifications made to recent experiments eliminated several notable problems present in previous experiments. Also, data extracted from these wafers seem to reinforce what was determined from the previous experimentation, specifically that gravity plays an integral role in the fluid dynamics that dictate the characteristics of the photoresist thin film. Most notably, all of the wafers prepared in the absence of gravity exhibit a significantly thicker photoresist film than those prepared under normal gravity conditions. These differences are much more pronounced than expected, with an average film ranging from a thickness 22% greater (5600 RPM set) to 29% greater (7000 and 7400 RPM sets) than the 1-G wafer counterparts.

...Sandia performed an experiment aboard the National Aeronautics and Space Administration's (NASA's) KC-135 Reduced Gravity Flying Laboratory to study the feasibility of spin-coating in a weightless environment....Analysis of [prepared] wafers confirms that the modifications made to recent experiments eliminated several notable problems present in previous experiments....Most notably, all of the wafers prepared in the absence of gravity exhibit a significantly thicker photoresist film than those prepared under normal gravity conditions.

We established several main findings through our experimentation:

- The adhesive forces between a photoresist and Si wafer are substantial enough to allow for the spin-coating procedure to be done without the force of gravity.

- Lower dispense volumes and higher spin speeds used in a recent experiment allowed the photoresist film to stabilize within the allotted 0-G time frame. This confirmed that the spin-coating procedure can be accomplished successfully in the environment present aboard the KC-135, presenting a basis for possible future experimentation.

- Results gathered in each year of this experiment confirm that gravity seems to play a substantial role in the fluid dynamics that dictate the characteristics of the photoresist film in the spin-coating procedure. This can be shown by the consistently greater film thickness observed in the wafers prepared in 0-G, as well as by the formation of fluid wavefronts (Eckman spirals) during the dispense cycle. In all of the wafers prepared in the lab, we observed two distinct Eckman spirals. However, we observed only one Eckman spiral in all of the wafers prepared in 0-G. This may prove to be of significance in the modeling of the spin-coating process because, in all of the literature available on the subject, gravity is neglected when deriving the equations that approximate fluid behavior.

Results gathered in each year of this experiment confirm that gravity seems to play a substantial role in the fluid dynamics that dictate the characteristics of the photoresist film in the spin-coating procedure.

Other Communications

Brown, J. R., and S. M. Thornberg. 2003.
Continued Investigation of Polymer Spin-Coating
for Photolithographic Semiconductor
Development in a Near Zero-Gravity
Environment. Sandia Technical Report
SAND2003-4167 (internal publication), Sandia
National Laboratories, Albuquerque, New
Mexico.

34465

Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation

P. W. Fuerschbach, G. R. Eisler

The production of metal vapor as a consequence of high-intensity laser irradiation is a serious concern in laser welding. Despite the widespread use of lasers in manufacturing, little fundamental understanding of laser/material interaction in the weld-pool exists. In this project, Sandia completed laser-welding experiments on 304 stainless steel (SS) that have advanced our fundamental understanding of the magnitude and the parameter dependence of metal vaporization in laser spot-welding. We compared calculations from a three-dimensional (3-D), transient numerical model with the experimental results. Convection played a very important role in the heat transfer, especially toward the end of the laser pulse. The peak temperatures and velocities increased significantly with the laser power density. The liquid flow is mainly driven by the surface tension and, to a much less extent, by the buoyancy force. Heat transfer by conduction is important when the liquid velocity is small at the beginning of the pulse and during weld-pool solidification. We found the effective temperature determined from the vapor composition to be close to the numerically computed peak temperature at the weld-pool surface.

We investigated alloying element loss from the weld-pool during laser spot-welding of SS both experimentally and theoretically. The experimental work involved determination of work-piece weight loss and metal-vapor composition for various welding conditions. We numerically simulated the transient temperature and velocity fields in the weld-pool. We modeled the vaporization rates of the alloying elements using the computed temperature profiles. The fusion-zone geometry could be predicted from the transient heat-transfer and fluid-flow model for various welding conditions. The laser power and pulse duration were the most important variables in determining the transient temperature profiles. The velocity of the liquid metal in the weld-pool increased with time during heating, and convection played an increasingly important role in the heat transfer. The peak temperature and velocity increased significantly with laser power density and pulse duration. At very high power densities, the computed temperatures were higher than the boiling point of 304 SS. As a result, the evaporation of alloying elements was caused by both the total

...Sandia completed laser-welding experiments on 304 stainless steel (SS) that have advanced our fundamental understanding of the magnitude and the parameter dependence of metal vaporization in laser spot-welding.

pressure and the concentration gradients. The calculations showed that the vaporization occurred mainly from a small region under the laser beam where the temperatures were very high. We found the computed vapor loss to be lower than the measured mass loss because of the ejection of the tiny metal droplets owing to the recoil force exerted by the metal vapors. We predicted the ejection of metal droplets by computations and verified the prediction by experiments.

Refereed

He, X., T. DebRoy, and P. W. Fuerschbach. 2003. Alloying element vaporization during laser spot welding of stainless steel. *J. Phys. D*, accepted.

He, X., T. DebRoy, and P. W. Fuerschbach. 2003. Heat transfer and fluid flow during laser spot welding of 304 stainless steel. *J. Phys. D* **36**:1388–98.

He, X., T. DebRoy, and P. W. Fuerschbach. 2003. Probing temperature during laser spot welding from vapor composition and modeling. *J. Applied Physics*, accepted.

34466

Mechanics and Tribology of MEMS Materials

M. T. Dugger, B. L. Boyce, T. E. Buchheit, J. A. Ohlhausen, S. V. Prasad, J. R. Michael

Micromachines have the potential to significantly impact future weapon-component designs as well as other defense, industrial, and consumer-product applications. For both electroplated (LIGA [the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding]) and surface-micromachined (SMM) structural elements, the influence of processing on structure and the resultant effects on material properties are not well understood. The behavior of dynamic interfaces in present as-fabricated microsystem materials is inadequate for most applications, and the fundamental relationships between processing conditions and tribological behavior in these systems are not clearly defined. Sandia intends to develop a basic understanding of deformation, fracture, and surface interactions responsible for friction and wear of microelectromechanical systems (MEMS) materials. This will enable needed design flexibility for these devices, as well as strengthen our understanding of material behavior at the nanoscale. The goals of this project are to develop new capabilities for submicroscale mechanical and tribological measurements, and to exercise these capabilities to investigate material behavior at this size scale.

We evaluated the Weibull strength distribution of SMM polysilicon (poly-Si) for each of the five structural Si layers in the SUMMiT-V™ (Sandia Ultraplanar Multilevel MEMS Technology V) process over a wide range of stressed surface areas (200–20,000 μ^2), thereby revealing the previously elusive Weibull size effect, as well as a strong layer dependence. The layer dependence, thought to be at least partially due to microstructural variations, was consistent with a recently developed polycrystal elasticity model based on electron-backscatter-diffraction (EBSD) orientation maps of SUMMiT-V™ crystallography. We developed new techniques and applied them to characterize the role of temperature and process steps, i.e., sacox cuts, on the observed strength behavior. Finally, we fabricated and evaluated a next generation of MEMS test structures, including compact-tension fracture-toughness structures and bend structures.

We used SMM structures that contain isolated tribological contacts to investigate interface performance of alkylsilane

Structure and topography of microsystem materials, showing an atomic-force microscope (AFM) image of sidewall morphology in plasma-etched polycrystalline silicon (top), EBSD at the boundary between polycrystalline silicon layers (middle), and EBSD image of a worn surface of electroformed nickel showing grain-boundary tilting near the wear surface (bottom).

Sandia intends to develop a basic understanding of deformation, fracture, and surface interactions responsible for friction and wear of microelectromechanical systems (MEMS) materials.

monolayers after storage in inert environments, and after exposure to a variety of thermal and radiation environments. Results show that both octadecyltrichlorosilane (OTS) and perfluorodecyltrichlorosilane (PFTS) exhibit little change in hydrophobicity or friction after Co-60 radiation exposures at a total dose of up to 500 krad. However, exposure to temperature cycles consistent with packaging technologies, in the presence of low levels of water vapor, produces degradation of hydrophobicity and increase in static friction for OTS films while producing no significant degradation in PFTS films. In addition, we developed a range of new friction-measurement tools for SMM structures. These include devices that permit a wider range of applied forces to be generated between contacting surfaces and structures where the contacts may be latched into position to retain load without application of power. The latter are important structures for examining the effects of aging on the interface behavior of contacts under load.

We developed new methodologies to study wear and subsurface deformation in electroplated metals for microsystems (LIGA). The methodology involves the application of focused-ion-beam (FIB) techniques to prepare cross sections of wear tracks. EBSD analysis of wear-scars on electroformed nickel (Ni) revealed the formation of two subsurface zones, each with its own characteristic features that are different from those of the bulk microstructure. We observed bending of columns in the direction of sliding, breakdown of columnar grains into equiaxed fine-grain structure, and formation of low-angle grain boundaries. We also observed formation of low-angle grain boundaries and spread in the orientation of pole figures. This work demonstrated that FIB techniques are ideally suited for preparing cross sections of shallow wear-scars generated under low loads.

We also demonstrated the feasibility of characterizing adhesion between electroplated LIGA materials using a commercial MTS Nanoindenter XP with a LIGA-fabricated adhesion probe tip in place of the standard Berkovich diamond indenter. It is well recognized that under the action of surface forces, the surfaces are drawn together and a finite area of contact is established for zero applied load. If an external load is applied, the contact area increases, but on reducing the load, the contact area decreases reversibly. When the applied external load is removed, an additional load or a pull-off force is required to fully separate the two surfaces. Two widely referred models, the Johnson-Kendall-Roberts (JKR) model and the Derjaguin-Muller-Toporov (DMT) model, account for small but finite contact area at zero applied load in the presence of surface

We developed new methodologies to study wear and subsurface deformation in electroplated metals for microsystems (LIGA).

forces. In our measurements, we programmed the nanoindenter to collect data in the negative load regime until the surfaces were completely separated. We fabricated LIGA Ni probe tips with a variety of radii of curvature and pressed them into contact with a metallographically polished LIGA Ni disk. Load-displacement curves for these experiments showed negative loads in the unloading segments. This negative load or pull-off force allows us to quantify the adhesion forces between surfaces after removal of the applied load.

Refereed

Buchheit, T. E., G. W. Wellman, and B. L. Boyce. 2002. The role of microstructure in MEMS deformation and failure. *Proc. IMECE 2002, Symposium on Recent Advances in Damage Mechanics* (18–22 November, New Orleans, Louisiana).

LaVan, D. A., B. L. Boyce, and T. E. Buchheit. 2002. Size and frequency of defects in silicon MEMS. *Proc. IMECE 2002, Symposium on Recent Advances in Damage Mechanics* (18–22 November, New Orleans, Louisiana).

Prasad, S. V., J. R. Michael, and T. R. Christenson. 2002. EBSD studies on wear-induced subsurface regions in LIGA nickel. *Scripta Metallurgica* **48**:255–60.

Romig, Jr., A. D., M. T. Dugger, and P. J. McWhorter. 2003. Materials issues in microelectromechanical devices: Science, engineering, manufacturability, and reliability. *Acta Materialia*, accepted.

Other Communications

Boyce, B. L. 2003. Stochastic strength distributions in polysilicon MEMS. Paper presented at the Materials Research Society Fall Symposium, November, Boston, Massachusetts.

Dugger, M. T., and S. V. Prasad. 2002. Tribological measurement on MEMS platforms. Paper presented at the American Vacuum Society Annual Meeting, 4–8 November, Denver, Colorado.

Dugger, M. T., R. J. Hohlfelder, and D. E. Peebles. 2003. Changes in adhesion, static and dynamic friction of surface-micromachined MEMS due to lubricant degradation. Paper presented at the Society of Tribologists and Lubrication Engineers, 28 April–1 May, New York, New York.

Dugger, M. T., R. J. Hohlfelder, and D. E. Peebles. 2003. Degradation of monolayer lubricants for MEMS. *Proc. SPIE* **4980** (January, San Jose, California): 138–50.

Garino, T. J., A. M. Morales, and B. L. Boyce. 2003. The mechanical properties, dimensional tolerance and microstructural characterization of micromolded ceramic and metal components. Paper presented at the High-Aspect-Ratio Microstructure Technology Workshop, June, Monterey, California.

Prasad, S. V., T. R. Christenson, M. T. Dugger, J. R. Michael, and C. W. Vanecsek. 2003. The reliability of dynamic interfaces in LIGA microsystems. Paper presented at the American Society for Precision Engineering, 22–23 January, Gainesville, Florida.

Tanner, D., and M. T. Dugger. 2003. Wear mechanisms in reliability methodology. *Proc. SPIE* **4980** (January, San Jose, California).

34467

Dynamics of Metal/Ceramic Interfaces*K. F. McCarty, N. C. Bartelt*

Sandia's goal in this project is to understand how metal/ceramic interfaces form, evolve, and accommodate the stress that can lead to delamination and failure. We emphasize the use of advanced microscopies such as scanning-tunneling microscopy (STM) and low-energy-electron microscopy (LEEM) to observe interface formation in real time. We use these techniques to measure the interfacial work of adhesion, determine the mechanisms and kinetics of interface formation, and develop understanding of how stress is or is not accommodated. We combine real-time measurements of process dynamics with modeling to determine what physical processes govern system evolution.

We used LEEM to further evaluate how nickel aluminum (NiAl) undergoes oxidation to make a metal/ceramic interface. Careful imaging revealed that the rod-shaped spinel phase did not transform into the gamma alumina ($\gamma\text{-Al}_2\text{O}_3$) phase, as previously thought. Instead, the $\gamma\text{-Al}_2\text{O}_3$ nucleated on the sides of the rods and grew along their length. This establishes that the rod phase is metastable with respect to the same $\gamma\text{-Al}_2\text{O}_3$ phase produced by low-temperature oxidation. That is, eventually islands of the $\gamma\text{-Al}_2\text{O}_3$ phase nucleate and grow during the high-temperature oxidation. We identified the $\gamma\text{-Al}_2\text{O}_3$ phase using dark-field microscopy and extensively studied the strain-relieving interfacial dislocations present in this phase. The dislocations formed networks, the most common of which was a sawtooth array. Within an oxide island, the dislocations oscillate back and forth, and the dislocation grows (adds teeth) in length as the oxide island grows. Finally, we studied the density at which the rods nucleated as a function of substrate temperature and oxygen pressure. High-island density was favored at low temperature and high oxygen pressure.

Sandia's goal in this project is to understand how metal/ceramic interfaces form, evolve, and accommodate the stress that can lead to delamination and failure....We combine real-time measurements of process dynamics with modeling to determine what physical processes govern system evolution.

Refereed

McCarty, K. F. 2003. Imaging the crystallization and growth of oxide domains on the NiAl(110) surface. *Surface Science* **474**:165.

34468

In Situ Characterization of Soft Solution Processes for Nanoscale Growth

N. S. Bell, D. R. Tallant, M. A. Rodriguez

The study of novel materials and structures with dimensions in the nanoscale (< 100 nm) regime is an important, emerging field of materials science. The small size of these materials results in quantum confinement and surface contributions that translate into novel optoelectronic properties whose applications are still being realized. Many synthesis techniques for nanomaterials are based on soft solution processes (SSPs), which include sol-gel, hydrothermal, solvothermal, micellular or organic templating routes, and electrochemical methods. These processes involve the precipitation of ionic species or metal-organic molecules into nanoparticles or nanostructured networks. To exercise a high degree of control over these processes, it is critical to have the capability to monitor the development of supersaturation, surface reactions, and formation of phase or precipitate in situ. Sandia will study the superposition of different measurement techniques to characterize dynamic colloidal systems in new ways. These studies will probe the chemical interactions during reactions, and the organizational characteristics developed in the resulting colloids. Of particular interest are properties influencing colloidal dynamics such as zeta potential and particle-size development.

The goal of this project was to explore experimental methods for measuring kinetic effects between the colloidal stability of nanoparticles and their environmental conditions. This information will be useful to understanding the formation methods for nanoparticle materials and their processing to create self-assembled structures.

We attempted to observe the nucleation event of zinc oxide (ZnO) precipitation using hexamethylenetetraamine (HMT) by Raman spectroscopy but were unsuccessful. The time necessary to measure zeta potential was also too long for the nucleation event to be resolved. Monitoring of zeta-potential changes in a dispersion was possible.

We constructed the acoustic rheometer apparatus. The acoustic scattering models necessary to infer particle-size changes require further development, and thus we have not completed studies using the instrument. After development of the acoustic scattering algorithms, the instrument will be

The study of novel materials and structures with dimensions in the nanoscale (< 100 nm) regime is an important, emerging field of materials science....Sandia will study the superposition of different measurement techniques to characterize dynamic colloidal systems in new ways. These studies will probe the chemical interactions during reactions, and the organizational characteristics developed in the resulting colloids.

functional and provide assistance to studies of paste rheology and extrusion modeling.

We could not detect measurements of the flow of nanoparticles in microcapillaries under electrophoresis fields for extrapolation of nanoparticle zeta potential by diffusion-gradient methods. We rejected the use of fluorescent dyes because the method would not be comparable to studies of the kinetic effects of the desired system.

Experiments with dispersion of a model alumina nanopowder were successful in determining the best dispersant mechanism for achieving a high-volume solid loading. Polyelectrolyte dispersants with minimum layer thickness were effective and showed the least sensitivity to excluded volume effects from the adsorbed layer thickness. Electrostatic repulsion is theorized to be ineffective due to the background salt concentration that is inherent to nanopowder surface-area charging effects.

In studies with the alumina nanopowder, we found that steric dispersants with estimated thickness on the order of 2.5 nm were successful for achieving a high solids loading equivalent to that of a polyelectrolyte layer. Steric dispersants of lower thickness exhibited flocculated rheological response in relation to their thickness. Rheological fitting with conventional models was of limited effectiveness in understanding the data. We propose that dissolved gas from the atmosphere increases the adhesion forces between surfaces to cause the increased elastic character and low solids loading for fluid flow.

We achieved success in the understanding of routes to stabilization of nanoparticles. We could not achieve resolution of the *in situ* interfacial processes in the formation of nanoparticle colloids.

Experiments with dispersion of a model alumina nanopowder were successful in determining the best dispersant mechanism for achieving a high-volume solid loading. Polyelectrolyte dispersants with minimum layer thickness were effective and showed the least sensitivity to excluded volume effects from the adsorbed layer thickness.

Refereed

Bell, N. S., and M. A. Rodriguez. 2003. Dispersion properties of an alumina nanopowder using molecular, polyelectrolyte, and steric stabilization. *J. Nanoscience and Nanotechnology*, accepted.

34469

Determination of Critical Length Scales for Corrosion Processes Using Microelectroanalytical Techniques

K. R. Zavadil, F. D. Wall

A key factor in Sandia's ability to produce and predict the stability of metal-based macro- to nanoscale structures and devices is a fundamental understanding of the localized nature of corrosion. Corrosion processes where physical dimensions become critical in the degradation process include localized corrosion initiation in passivated metals, microgalvanic interactions in metal alloys, and localized corrosion in structurally complex materials like nanocrystalline metal films under atmospheric and inundated conditions. This project focuses on two areas of corrosion science where a fundamental understanding of processes occurring at critical dimensions is not currently available. We will study the critical length scales necessary for passive film breakdown in the inundated aluminum (Al) system and the chemical processes and transport in ultrathin wafer films relevant to the atmospheric corrosion of nanocrystalline tungsten (W) films. Techniques are required that provide spatial information without significantly perturbing or masking the underlying relationships. Al passive film breakdown is governed by the relationship between area of the film sampled and its defect structure. We will combine low-current measurements with microelectrodes to study the size scale required to observe a single initiation event and record electrochemical breakdown events. We will correlate the resulting quantitative measure of stability with metal-grain size, secondary-phase size, and distribution to understand which metal properties control stability at the macro- and nanoscale. Mechanisms of atmospheric corrosion on W are dependent on the physical dimensions and continuity of adsorbed wafer layers as well as the chemical reactions that take place in this layer. We will combine electrochemical and scanning-probe microscopic (SPM) techniques to monitor the chemistry and resulting material transport in these thin surface layers. We will develop a description of the length scales responsible for driving the corrosion of the nanocrystalline metal films. We will use the techniques developed and information derived from this work to understand and predict degradation processes in microelectronic and microsystem devices critical to Sandia's mission.

A key factor in Sandia's ability to produce and predict the stability of metal-based macro- to nanoscale structures and devices is a fundamental understanding of the localized nature of corrosion.... We will use the techniques developed and information derived from this work to understand and predict degradation processes in microelectronic and microsystem devices critical to Sandia's mission.

We validated a statistical description of pit nucleation on pure Al formulated previously in this project by showing a mathematical link between constant-potential and potentiodynamic testing. We quantified the potential dependence of pit nucleation rate by constructing survival probability plots based on potentiostatic experiments performed across a range of applied potentials. We used the resulting data to calculate the potential dependence of pit nucleation rate. We achieved validation of our statistical model by using this information to calculate a predicted potentiodynamic behavior and showing a good fit between predicted response and our experimentally determined distribution. We extended these statistical studies to address the role of microgalvanic coupling effects in the binary Al-copper (Cu) alloy system. We constructed arrays (24 electrodes) of solutionized and peak-aged Al-4Cu from both 175 μm - and 380 μm -diameter electrodes. Open-circuit testing showed that most electrodes exhibited net cathodic current that was balanced by anodic behavior on a small fraction of the electrodes. We observed fewer anodic sites on the smaller electrodes, consistent with an area-based dependency of nucleation probability. Coupling a large-area, solutionized ingot of Al-4Cu to an array resulted in anodic sites exclusively on the ingot electrode, suggesting a minor role for secondary-phase precipitates in determining the location of at least one type of pitting phenomenon.

We demonstrated the ability to track the atmospheric corrosion of nanocrystalline W films using a combination of SPM, surface spectroscopy, and electrochemical techniques. We showed that corrosion in a thin wafer layer is localized, producing accentuated dissolution pits. Characterization of the pit sizes and density as a function of time shows that these anodic sites, once initiated, continue to propagate with the remainder of the film surface supporting the cathodic reduction of oxygen. We demonstrated that distribution of the tungstate by-product of corrosion occurs through diffusion through the surface wafer layer and precipitation. This precipitate is substantially conductive, preventing the repassivation of the surface toward further corrosion. Our work shows that atmospheric corrosion in these nanocrystalline thin films continues to propagate, further developing surface roughness until the film is completely breached. We developed methods for conducting nanoscale imaging at controlled humidity and temperature using variants of atomic-force microscopy and scanning-tunneling microscopy. We extended our work to examine morphological development in the passive oxide on nanocrystalline Al under inundated conditions. We

demonstrated the ability to detect the growth of oxide nodules as a first stage in the equilibration of an initially dry oxide with an aqueous solution environment. These nodular structures have implications for localized corrosion initiation. We developed and demonstrated a number of characterization strategies to describe the critical length scales necessary to initiate and propagate localized corrosion in materials critical to Sandia's microelectronic and microsystems technology.

Refereed

Wall, F. D., and M. A. Martinez. 2003. A statistics-based approach to studying pit initiation: Intrinsic and deficit-driven pit initiation phenomena. *J. Electrochemical Society* **150** (4): B146–B157.

Wall, F. D., M. A. Martinez, and J. J. Vanden Avyle. 2003. The relationship between induction time for pitting and pitting potential for high-purity aluminum. *J. Electrochemical Society*, submitted.

Zavadil, K. R., J. A. Ohlhausen, and P. G. Kotula. 2003. Nanoscale morphology development in the passive oxide on aluminum and the relationship to pitting. (Invited) Paper presented at the 204th Meeting of the Electrochemical Society, 12–16 October, Orlando, Florida.

Zavadil, K. R., J. A. Ohlhausen, and P. G. Kotula. 2003. Nanovoid and pore formation as pre-pitting phenomena in the passive oxide on aluminum at moderate chloride concentrations. *J. Electrochemical Society*, submitted.

Other Communications

Zavadil, K. R., and P. G. Kotula. 2003. Corrosion of nanocrystalline tungsten thin films used in Si-based microsystems. Paper presented at the 2003 Spring Meeting Materials Research Society, 22–25 April, San Francisco, California.

34478

LIGA Microsystems Aging: Evaluation and Mitigation

C. H. Cadden, N. Y. C. Yang

The deployment of LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) structures in Defense Program applications requires a thorough understanding of potential long-term physical and chemical changes that may occur during service. While these components are generally fabricated from simple metallic systems such as copper (Cu), nickel (Ni), and Ni alloys, the electroplating process used to form them creates microstructural features that differ from those found in conventional (e.g., ingot metallurgy) processing of such materials. Physical changes in nonequilibrium microstructures may occur due to long-term exposure to temperatures sufficient to permit atomic and vacancy mobility. Sandia focused the technical effort on two activities.

Ni-0.5Ni (weight percent) is a promising high-strength material for several LIGA applications, but its structure and properties are not well understood. We conducted a detailed characterization of Ni-manganese (Mn) electrodeposits, with particular emphasis on microstructural examination and correlation to mechanical properties.

The second activity involved a characterization of the dormancy and aging effects of nominally pure Ni electrodeposits (plated from a Ni sulfamate bath). We examined surfaces of LIGA parts in the initial state (as plated) as a baseline for comparison after exposure to thermal cycling in a controlled environment. We also performed mechanical strength testing for baseline and “aged” material.

Our work focused on two areas: a detailed characterization of Ni-Mn electroplated material and the characterization of dormancy and aging effects of baseline Ni (from the Ni sulfamate process) LIGA structures in controlled environments.

- *Ni-Mn characterization.* We examined a variety of Ni-Mn deposits having chemical compositions on both sides of the nominal 0.5 weight percent value. The deposits all exhibited a columnar grain morphology, with the long axis parallel to the plating direction. The microstructural features of these Ni-Mn deposits are much smaller than those found in essentially pure Ni deposits evaluated previously, which accounts for the increased hardness and strength of the Ni-Mn material. Additionally, we noted an effect of aspect ratio in deposited

The deployment of LIGA...structures in Defense Program applications requires a thorough understanding of potential long-term physical and chemical changes that may occur during service....Our work focused on two areas: a detailed characterization of Ni-Mn electroplated material and the characterization of dormancy and aging effects of baseline Ni (from the Ni sulfamate process) LIGA structures in controlled environments.

features. Specifically, we found both the Mn variation through thickness and the total Mn content to increase with aspect ratio. Finally, we also found grain-texture orientation to be dependent on the Mn concentration, with compositions above and below a critical composition of 0.2 weight percent exhibiting different textures.

- *Dormancy of electrodeposited Ni structures.* We prepared four types of specimens for dormancy: tensile bars, washers, gears, and u-springs. We assembled the latter three types of specimens to investigate changes at the contact between the parts during dormancy. We probed microstructural changes using properties determined from the tensile bars. Additionally, these parts came from six different batches of processed material.

We assembled six tensile bars and four of each of the latter specimens for each dormancy condition: four times in each of two environments (“dry” and “moist” nitrogen) and a control.

We documented the surface appearance of all specimens prior to dormancy with an optical microscope. We archived digital images of the parts at low magnification (85x) along with images at higher magnifications (up to 2614x) of distinguishing features such as scratches and processing artifacts. We gave primary attention to the lapped and release surfaces. The lapped surface is prepared mechanically and the release surface is prepared chemically. We examined the sidewalls less systematically since these surfaces are not flat, and thus high-quality images cannot be obtained with standard light microscopy techniques.

After dormancy, we again examined the surfaces and collected digital images with a stereomicroscope. We chose the stereomicroscope for the post-test images because it offered better lighting conditions and greater depth of focus, although at the cost of limits on magnification (only up to 150x). These post-test images concentrated on the same locations as for the pretest images except that the magnifications were generally limited to 150x. We took additional images with the optical microscope as deemed necessary for characterization of specific features; the higher magnification pretest images were not systematically reproduced post-test.

Comparison of pretest and post-test images does not show a significant difference for any of the observed parts. Since we avoided scanning-electron microscopy (SEM) of the parts before testing, we do not have high-magnification images pretest. However, based on comparison of pretest and post-test images collected from the light microscopes, features revealed by SEM post-test were apparently present before dormancy.

We loaded all tensile bars to fracture in a universal testing machine. We determined strains with a laser extensometer focusing on tape attached to the tensile bar at the extremes of the gauge section. We performed testing at a constant crosshead displacement of 0.003 mm/s, which corresponds to an initial strain rate of about $2 \times 10^{-4} \text{ s}^{-1}$. We could not obtain accurate modulus measurements with laser extensometry; therefore, we assumed a modulus of 200 GPa for yield strength determinations with an offset of 0.5% strain. We chose the relatively large offset to accommodate the uncertainty of the strain measurement in the elastic regime.

The mechanical test results indicate that tensile properties vary significantly from one production batch to another, but exhibit very little change over the time intervals examined in this project.

Refereed

Yang, N. Y. C., T. J. Headley, J. J. Kelly, and J. M. Hruby. 2003. Metallurgy of high-strength Ni-Mn microsystems fabricated by electrodeposition. *Scripta Materialia*, accepted.

34485

Science-Based Processing of Field-Structured Composites

R. L. Williamson

Field-structured composites (FSCs) are anisotropic particle composites that can be produced by hosting magnetic particles (e.g., nickel [Ni], iron [Fe], cobalt [Co]) in a liquid monomer and polymerizing the mixture in the presence of a magnetic field. They exhibit highly anisotropic properties due to the chain or sheetlike structures that form as a result of induced dipolar forces. By producing FSCs in a triaxial magnetic field and adjusting the relative strengths of the triaxial field components, a variety of structures can be made that cannot be produced in any other way. Field-structuring potentially enables one to produce materials with tailored material properties to meet specific needs. Sandia's goal in this work was to use feedback to produce Ni-based FSCs with known, stable electrical conductivities and predictable, reproducible responses to changes in temperature, strain, and chemical environment. To facilitate this, we developed an improved method of depositing gold (Au) onto Ni microparticles to ensure passivation against Ni oxidation. We successfully coated both 5 μm and submicron Ni particles. We subsequently demonstrated in a series of carefully controlled experiments, wherein particle chains were produced in both rubbery and glassy polymer encapsulants, that the electrical conductivity develops in response to cure stresses after the gel point is reached, eliminating feedback control as a possible means of controlling conductivity in the fully cured matrix. On the other hand, particle foams showed finite conductivity at the gel point, but the gel point conductivity did not affect the final composite conductivity. Thus, the original hypothesis, that FSC conductivity can be actively controlled using feedback while the host polymer is still in the liquid state, was proven false. On the other hand, we reproducibly synthesized stable FSCs without feedback that had predictable properties and response characteristics. We made prototype sensors and exposed them to various chemical environments, giving rise to reversible changes in conductivity of 10–12 decades.

We developed a method for coating Ni microparticles with Au to passivate them against oxidation. The method makes use of commercially available coating solutions and was successfully used to coat 5 μm -diameter Ni particles as well as submicron particles. FSCs produced with these particles

By producing FSCs in a triaxial magnetic field and adjusting the relative strengths of the triaxial field components, a variety of structures can be made that cannot be produced in any other way. Field-structuring potentially enables one to produce materials with tailored material properties to meet specific needs. Sandia's goal in this work was to use feedback to produce Ni-based FSCs with known, stable electrical conductivities and predictable, reproducible responses to changes in temperature, strain, and chemical environment.

showed no appreciable degradation in conductive properties for months, whereas FSCs produced with particles coated using the original method exhibited significant property degradation within 24 hrs.

We constructed a circuit to measure current flow through an FSC sample in response to a 1 mV potential during polymerization of the encapsulant using a picoammeter. We used the results to calculate sample resistance as a function of time. Au-coated Ni particles were hosted either in a polyester/styrene blend to form glassy composites or in silicone polymer to form rubbery composites. We made prepolymer/particle mixtures at a concentration of 6.8 volume percent and degassed all samples before loading them into the triaxial magnetic-field device. We produced chain-structured composites by applying a uniaxial field, and particle foam structures using a heterodyned triaxial field. These measurements gave the following results: (1) Chains produced in a uniaxial magnetic field in the glassy polymer show no measurable electrical conduction until well after the polymer gel point is reached. (2) Turning off the magnetic field at the gel point does not affect the final conductivity of the chain-structured composites. (3) Chain-structured composites in the rubbery polymer show a small amount of conductivity at the gel point, decreasing slightly when the structuring field is turned off, but the final conductivity is much larger and independent of when the field is turned off after the gel point is reached. (4) Particle foams in the glassy polymer show appreciable conduction at the gel point, but the final conductivity is similar to that measured for the uniaxial samples. The conclusion from this series of experiments is that final conductivity is almost completely controlled by cure shrinkage in the polymer that occurs after the gel point when it is no longer possible to manipulate structure. It appears that dipolar interactions between particles are simply too weak to generate sufficient contact pressure between the particles to produce appreciable current conduction. Thus, there is nothing to be gained by attempting to control final conductivity using complex field-processing techniques to manipulate structure.

Finally, we produced and tested prototype sensors. We made each sensor by placing a drop of 6.8 volume percent particle/resin mixture on a glass slide that had been Au-coated except for a single, uncoated strip across the center. We placed the particle/resin mixture on the slide so as to bridge the uncoated strip. We placed each slide in a uniform magnetic field while the polymer cured so that particle chains formed a bridge across the uncoated gap. We attached leads to each end of the slide and

exposed the sensors to saturated toluene vapor while measuring the sensor resistance. Typically, resistance increased from a few ohms to around 10^8 ohms. The response was reversible, the resistance returning to a few ohms several minutes after the vapors were removed. The resistance was also extremely responsive to temperature, the response depending on the cure temperature of the resin. A great deal of work has yet to be done if reliable sensors with well-characterized responses are to be produced. The sensors were equally sensitive to other chemical vapors such as pentane.

Refereed

Martin, J. E., R. A. Anderson, and R. L. Williamson. 2003. Generating strange interactions in particle suspensions. *Composites Science and Technology* **63**:1097–1103.

Martin, J. E., R. A. Anderson, and R. L. Williamson. 2003. Generating strange magnetic and dielectric interactions: Classical molecules and particle foams. *J. Chemical Physics* **118**:1557–70.

Williamson, R. L., J. E. Martin, and J. L. Williamson. 2003. Evolution of the electrical conductivity of field-structured particle composites. *J. Applied Physics*, submitted.

34699

Exploration of New Multivariate Spectral Calibration Algorithms

D. M. Haaland, D. K. Melgaard, M. H. Van Benthem, C. L. Stork

Sandia has developed a number of powerful new multivariate calibration algorithms that have been demonstrated to correct many of the outstanding limitations of traditional quantitative multivariate spectral calibrations and to greatly extend our ability to solve new problems. We developed a family of augmented classical least-squares (ACLS) multivariate algorithms, and we greatly improved multivariate curve resolution (MCR) methods. The ACLS algorithms have the ability to be rapidly updated during prediction without recalibration while the MCR techniques allow us to perform multivariate calibrations without the use of standards. The rapid updating feature of the ACLS algorithms is a significant advantage over previous chemometric algorithms. We will continue to quantify the relative merits and predictive performance of these new multivariate algorithms relative to traditional multivariate calibration methods, and we will explore exciting new potential applications using the improved MCR algorithms. For example, the new ACLS algorithms can take advantage of weighted least-squares methods to accommodate nonuniform noise in spectral data. The ability to better handle nonuniform spectral noise will be tested with simulation calibration data. We will use the improved MCR capabilities to test our hypothesis that they can be used to improve spectral calibrations that are currently limited by the reference methods required to build multivariate calibration methods. Since reference errors are often the limiting factor in multivariate spectral calibrations, reducing or eliminating this limitation would be a significant advance in chemometric data-analysis capabilities. If we can successfully reduce the impact of reference errors in spectral calibrations, then we also have the opportunity to determine whether the generally high precision of spectral measurements can be used to decrease errors in the primary reference methods. Success at this goal could have a very significant impact on all of our instrumental analytical reference tools.

We completed the rigorous comparison begun previously of the ACLS and the traditional partial least-square (PLS) using simulated data, and we submitted for publication a paper describing our results. The focus of the simulations was to reflect realistic deviations from a linear model by using pure

Sandia has developed a number of powerful new multivariate calibration algorithms that have been demonstrated to correct many of the outstanding limitations of traditional quantitative multivariate spectral calibrations and to greatly extend our ability to solve new problems....Success at this goal could have a very significant impact on all of our instrumental analytical reference tools.

component spectra taken from a dilute aqueous solution of glucose, ethanol, and urea. The nonlinearities represented attenuation of detector response at higher intensities. We also introduced correlated noise derived from repeat sample spectra of the dilute solutions taken on several different days. This focus proved important since the closer the simulations came to real data, the more favorable the ACLS models were to PLS models.

These results became particularly important as we noted the efficacy of ACLS for transfer of multivariate calibrations between different spectrometers. Thermo Electron, which had previously licensed our ACLS algorithms, generated experimental near-infrared (NIR) data for us from inorganic solutions of chlorobenzene, heptane, and toluene on 11 different spectrometer configurations. Using these data, we investigated the effectiveness of ACLS in calibrating on data from one configuration and predicting on data from a different configuration. After examining the initial datasets, we obtained additional data with a repeat sample measured between each set of three samples for the most difficult transfer problems. Important to the results of our study was that ACLS was as good as or better than PLS in almost all cases. Even more significant was the finding that the ACLS transfer did not require recalibration, while the PLS model required recalibration each time. As such, the ACLS prediction was faster and more flexible, allowing more selective transfer methodologies. A particularly effective transfer method was to identify the sample with the closest spectrum to the prediction sample using only the measured spectra from the calibration samples and the unknown sample to be predicted. We used the difference between the spectra for that sample on the calibration and prediction configurations as the transfer in the ACLS calibration model, giving significantly improved predictions. While relatively easy to implement with ACLS, the effort for a comparable PLS approach would likely be prohibitive in most cases.

We attempted to use the iterative MCR method applied to NIR spectra of calibration samples to improve the gravimetrically determined reference sample concentrations. We applied MCR with nonnegativity and equality constraints to the NIR experimental data, which were originally obtained with high-reference concentration accuracy, but tested after we artificially degraded the concentration accuracy with artificial noise. Thus, we have real experimental spectra with poor concentration reference values, but with the underlying true concentrations accurately known. We found that the MCR did

not successfully improve the reference concentrations since the nonnegativity constraints were not adequate to sufficiently drive the reference concentrations to the correct concentrations. It is now clear that the appropriate constraint to use to improve the reference concentrations is to constrain the spectral residuals of the iterative MCR procedure to have minimal correlated errors. Unfortunately, funding was not adequate to implement these new constraints, which would require iterative Simplex optimization of the spectral residuals.

To take advantage of and exploit our improved MCR capabilities using rigorous least-squares constraints, spectral and spatial data compression, and efficient out-of-core memory algorithms, we designed an improved MATLAB user interface. To facilitate the development, we programmed an image-handling prototype that already has resulted in increased productivity for Sandia users when applied to hyperspectral images (HSI). Based largely on the prototype MATLAB software, the initial design of the more comprehensive MCR visualization package has been completed.

...we programmed an image-handling prototype that already has resulted in increased productivity for Sandia users when applied to hyperspectral images (HSI). Based largely on the prototype MATLAB software, the initial design of the more comprehensive MCR visualization package has been completed.

Refereed

Melgaard, D. K., and D. M. Haaland. 2003. Comparisons of prediction abilities of augmented classical least-squares and partial least-squares with realistic simulated data: Effects of uncorrelated and correlated errors with nonlinearities. *Applied Spectroscopy*, submitted.

Van Benthem, M. H., M. R. Keenan, and D. M. Haaland. 2003. Application of equality constraints on variables during alternating least-squares procedures. *J. Chemometrics* **16**:613–22.

Other Communications

Haaland, D. M. 2003. Recommendations for minimum requirements in chemometric research. Paper presented at the Pittsburgh Conference, 9–14 March, Orlando, Florida.

Haaland, D. M., D. K. Melgaard, F. W. Koehler, C. M. Wehlburg, and L. E. Martin. 2002. New augmented classical least-squares methods for improved quantitative spectral analyses. Paper presented at the Thermo Nicolet Symposium Series, 12 December, Greenbelt, Maryland.

Haaland, D. M., D. K. Melgaard, F. W. Koehler, C. M. Wehlburg, and L. E. Martin. 2003. New augmented classical least-squares methods for improved quantitative spectral analyses. Paper presented at the Thermo Nicolet Symposium Series, 16 January, San Diego, California.

Melgaard, D. K., and D. M. Haaland. 2002. Nonlinearities, how well do multivariate calibration methods handle them? Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 13–17 October, Providence, Rhode Island.

Melgaard, D. K., D. M. Haaland, S. Lowry, and C. M. Wehlburg. 2003. Methods for eliminating calibration transfer errors using augmented classical least-squares. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 19–23 October, Fort Lauderdale, Florida.

Rivera, D. A., M. K. Alam, W. G. Yelton, R. J. Simonson, and D. M. Haaland. 2002. Application of multivariate calibration methods to surface acoustic-wave array data. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 13–17 October, Providence, Rhode Island.

Van Benthem, M. H., M. R. Keenan, and D. M. Haaland. 2003. Computing rigorous solutions to equality- and inequality-constrained least-squares problems during multivariate curve resolution. Paper presented at the Federation of Analytical Chemistry and Spectroscopy Societies Meeting, 19–23 October, Fort Lauderdale, Florida.

Wehlburg, C. M., D. M. Haaland, and D. K. Melgaard. 2003. Assessing the robustness of calibration transfer techniques. Paper presented at the International Federation of Process Analytical Chemistry, 21–24 January, Tucson, Arizona.

38688

The Basics of Aqueous Nanofluidics: “Interphase” Structure and Surface Forces

P. J. Feibelman, B. C. Bunker, D. M. Teter, K. Leung, D. L. Huber

To understand flow through narrow pores, biomaterials properties, micromachine operation, and other key nanofluidic phenomena, we need to learn how the unexpectedly strong forces measured as far as tens of nanometers from water-solid interfaces are mediated by near-surface water structure. Using ab initio calculations and a suite of incisive experiments, Sandia will identify and characterize icelike, clathratelike, and possibly other arrangements of water molecules in the “interphase” adjacent to ice-nucleating, hydrophobic, and intermediate surfaces. The measurement techniques, including infrared (IR) spectroscopy, interfacial-force microscopy (IFM), and contact angle studies, will illuminate the relations among interphase structure and energetics, mechanical properties, and hydration forces. Our theoretical efforts will target an explanation of how templates produced by strong short-range interactions nucleate near-surface ordering of water molecules. For this purpose, we will develop and deploy a computational scheme in which the near-surface transition region is described by a classical water potential, specifically designed to reproduce the ab initio phases and properties of bulk water, while an ab initio description of the immediate surface vicinity provides a boundary constraint amounting to a template. After initial work in which we develop and validate novel experimental and theoretical methods, we will apply theory and experiment concurrently to a set of representative cases, including an AgI surface (epitaxy with ice), a clean metal, and a self-assembled-monolayer (SAM)–covered (oily) surface. We will thus learn the microscopic underpinnings of the relation between hydration force strength, surface chemistry, e.g., hydrophilicity, and physics, e.g., epitaxial match.

We implemented quantum-mechanics/molecular-mechanics (QM/MM) capability in the electronic-structure code VASP, which treats aqueous solutes quantum-mechanically and water classically. We successfully compared QM/MM ammonium-ion and alcohol-hydration structures to the experiment and found that aqueous formate ion QM/MM calculations disagree with *ab initio* molecular dynamics (MD). We computed kappa-alumina surface water-adsorption energetics for comparison to QM/MM computations.

Using ab initio calculations and a suite of incisive experiments, Sandia will identify and characterize icelike, clathratelike, and possibly other arrangements of water molecules in the “interphase” adjacent to ice-nucleating, hydrophobic, and intermediate surfaces.... We will thus learn the microscopic underpinnings of the relation between hydration force strength, surface chemistry, e.g., hydrophilicity, and physics, e.g., epitaxial match.

When we compared *ab initio* vibration spectra for intact and partially dissociated water structures on ruthenium (Ru) (0001) to the naturally occurring crystalline form of ice crystals, “ice Ih,” we found that free oxygen-deuterium (O-D) bond dissociation eliminates the highest-energy O-D stretch, as in sum-frequency-generation experiments, and also that associated, reduced zero-point energy stabilizes partially dissociated adlayers.

We pursued the idea that reaction with surface impurities underlies wetting in numerous cases and showed that boron (B), carbon (C), or O atoms on rhodium (Rh) (111) will cause reactive wetting of this surface. The C atoms are the most effective.

We began studying why proton disorder improves water overlayer binding in some calculations, as well as water-clusters on palladium (Pd) (111), to interpret scanning-tunneling microscopy (STM) data. We solved the Navier-Stokes equation for water-drainage between the approaching tip and sample given high-viscosity interphase adjacent to surfaces. The solution’s functional form agrees with Kim, Kushmerick, and Houston’s IFM data, allowing an interphase viscosity to be extracted.

We computed residual entropy of ultrathin ice films to extend wetting calculations to finite temperature and estimated van der Waals corrections to *ab initio* energetics of water on metals by computing argon (Ar) adsorption (since Ar and H₂O have similar electronic polarizabilities).

We investigated spiropyran films, which ultraviolet (UV) light makes more polar and visible light returns to nonpolar. Using IFM, we monitored how such changes affect surface forces in air, water, and formamide-electrolyte solutions. We monitored net surface polarity by measuring contact potential with the IFM tip hovering above the surface. We measured tip-substrate interactions versus applied voltage for effective interfacial region work function. We found that contact potential switches reversibly on cyclical UV and visible light exposure. Its shift of - 0.27 V on UV exposure is consistent with 10% spiropyran ring openings, creating dipoles pointing toward the surface. In aqueous salt solution, the same reaction manifests in doubling of electrical double-layer forces. For a positively charged amine-coated tip, the double-layer force is repulsive, consistent with the creation of positive surface charges rather than fixed dipoles. IFM results in water reconcile with contact-potential measurements because anionic phenolic oxygen is neutralized by protonation. In proton-containing

We solved the Navier-Stokes equation for water-drainage between the approaching tip and sample given high-viscosity interphase adjacent to surfaces. The solution’s functional form agrees with Kim, Kushmerick, and Houston’s IFM data, allowing an interphase viscosity to be extracted.

solutions with low-enough pH, ring-opening thus creates cationic surface sites, not dipoles.

Refereed

Bunker, B. C., B. I. Kim, J. E. Houston, R. Rosario, A. A. Garcia, M. Hayes, D. Gust, and S. T. Picraux. 2003. Direct observation of photo-switching in tethered spiropyrans using the interfacial-force microscope. *Nano Letters*, accepted.

Feibelman, P. J. 2003. Comment on “vibrational recognition of hydrogen-bonded water networks on a metal surface.” *Phys. Rev. Lett.* **059601**:91.

Feibelman, P. J. 2003. Effect of high-viscosity interphases on drainage between hydrophilic surfaces. *Langmuir*, submitted.

Feibelman, P. J. 2003. Reactive wetting: H₂O/Rh(111). *Phys. Rev. Lett.* **90**:186103.

Feibelman, P. J. 2003. Surface theory moves into the real world. *J. Vacuum Science and Technology* **A21**:S64.

Huber, D. L., R. P. Manginell, M. A. Samara, B. I. Kim, and B. C. Bunker. 2003. Programmed adsorption and release of proteins in a microfluidic device. *Science* **301**:352.

Kim, B. I., J. G. Kushmerick, J. E. Houston, and B. C. Bunker. 2003. Viscous “interphase” water adjacent to oligo(ethylene glycol)-terminated monolayers. *Langmuir* **19**.

Kim, B. I., M. A. Samara, D. L. Huber, J. E. Houston, and B. C. Bunker. 2002. Hydration forces on a switchable bioactive surface. Paper presented at the AVS 49th International Symposium, 3–8 November, Denver, Colorado.

Leung, K., and S. B. Rempe. 2003. *Ab initio* molecular dynamics study of glycine tautomerization in water. *J. Phys. Chem. B*, submitted.

Leung, K., A. Luzar, and D. Bratko. 2003. Dynamics of capillary drying in water. *Phys. Rev. Lett.* **90**:065502.

Leung, K., and S. B. Rempe. *Ab initio* molecular dynamics study of the aqueous formate ion. *J. American Chemical Society*, submitted.

Other Communications

Feibelman, P. J. 2002. How water wets a metal surface. Paper presented at the PNNL Research Seminar, October, Richland, Washington.

Feibelman, P. J. 2003. Reactive wetting: H₂O/Rh(111). Paper presented at the American Physics Society March Meeting, March, Austin, Texas.

Feibelman, P. J. 2002. Vibrations of water absorbed on Ru (001). Paper presented at the American Vacuum Society, November, Denver, Colorado.

Feibelman, P. J. 2003. Viscous effects in water near a hydrophilic surface. Paper presented at the Chemical Department Seminar, University of Cambridge, June, Cambridge, United Kingdom.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Chemical Department Colloquium, University of Cambridge, July, Cambridge, United Kingdom.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Physics Colloquium, RWTH, July, Aachen, Germany.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Physics Colloquium, University of Aarhus, September, Aarhus, Denmark.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Physics Colloquium, University of Leiden, July, Leiden, The Netherlands.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Physics Colloquium, University of Twente, July, Enschede, The Netherlands.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Research Seminar at Columbia University, May, New York, New York.

Feibelman, P. J. 2003. Why water wets precious metals. Paper presented at the Research Seminar at the IBM TJ Watson Lab, May, Yorktown Heights, New York, New York.

Kim, B. I., B. C. Bunker, D. L. Huber, J. E. Houston, S. T. Picraux, R. Rosario, A. A. Garcia, M. Hayes, and D. Gust. 2003. Surface forces on switchable bioactive surfaces studied by interfacial-force microscope. Paper presented at the 39th Symposium of the AVS New Mexico Chapter, 29–30 April, Albuquerque, New Mexico.

Kim, B. I., T. M. Mayer, M. G. Hankins, M. P. De Boer, and B. C. Bunker. 2003. Self-assembled monolayer aging in humid environments. Paper presented at the March American Physical Society Meeting, 3–7 March, Austin, Texas.

Leung, K. 2003. Plane-wave, ultrasoft pseudopotential-based hybrid QM/MM simulation of water-materials interactions. Paper presented at the American Physical Society Meeting, March, Austin, Texas.

Leung, K., A. Luzar, and D. Bratko. 2003. Dynamics of capillary drying in water. Paper presented at the American Physical Society Meeting, March, Austin, Texas.

Leung, K., and S. B. Rempe. 2003. *Ab initio* molecular dynamics study of the aqueous formate ion. Paper presented at the American Chemical Society Fall Meeting, 11 September, New York, New York.

38689

Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices

A. M. Morales, M. L. Leininger, J. R. McElhanon, P. J. Cole

This year Sandia focused on the synthesis of a variety of photoresponsive azobenzene polymers/molecules that were similar to and compatible with polymethylmethacrylate (PMMA), including a nonpolymerizable molecule for incorporation into a nanolayer superlattice. We applied a variety of analytical techniques to PMMA blends of the polymers/molecules to select the most promising candidate for subsequent fabrication. These techniques include ultraviolet-visible (UV-vis) absorption spectroscopy, ellipsometry, thermal mechanical analysis, microscopy, and spectroscopic examination of heat-treated samples. These analytical techniques lower the technical risk for multilayer fabrication by ensuring that the chromophore chosen for fabrication will have the desired optical properties, will be available in large-enough quantities, and will be thermally stable during fabrication. We will fabricate the superlattices by polymeric coextrusion and currently are assembling the coextruder. The extrusion dies and take-up device need to be fabricated. We are modeling the polarizabilities of the different molecules under consideration at high levels of theory and at different stacking configurations.

We made the following accomplishments:

- *Defined best nanolayering techniques.* Based on its physical operating principles (no solvents needed, laminar flow, and dies define layers), polymeric multilayer coextrusion will generate superlattice structures with submicron-layer thicknesses.

- *Defined best nanolayer characterization techniques.* Atomic-force microscopy (AFM) and field-emission scanning-electron microscopy (SEM) can resolve structures on the order of 100 nm. We currently are investigating the best cross-sectioning technique, possibly microtoming.

- *Developed techniques to modify internanolayer coupling.* We included this task to allow for the fabrication of superlattices from noncompatible polymers. However, polymeric coextrusion can produce superlattices from polymers normally noncompatible, e.g., polymers that do not weld to each other. Thus, this milestone is obviated by our nanolayering technique.

- *Selected most promising multilayer system.* Based on the ongoing optical measurements, we will use the diazobenzene

...Sandia focused on the synthesis of a variety of photoresponsive azobenzene polymers/molecules that were similar to and compatible with polymethylmethacrylate (PMMA), including a nonpolymerizable molecule for incorporation into a nanolayer superlattice....These analytical techniques lower the technical risk for multilayer fabrication by ensuring that the chromophore chosen for fabrication will have the desired optical properties, will be available in large-enough quantities, and will be thermally stable during fabrication.

molecule with highest index-of-refraction change in the solid state to produce a multilayer system.

38690

Photocontrol of Nanointeractions in Microsystems

N. S. Bell, J. Cesarano, III, G. M. Jamison, S. Y. Lin, M. Piech, T. M. Long

The manipulation of physical interactions between structural moieties on the molecular scale is a fundamental hurdle in the realization and operation of nanostructured materials and high-surface-area microsystem architectures relying on such nanointeraction-based phenomena as self-assembly, fluid flow, and interfacial tribology. Conventional nanointeraction control strategies typically involve the tailoring of material structures either during synthesis or through invasive post-synthesis processing, with no opportunity for real-time, remote modulation of intermolecular and/or interparticle forces. By contrast, Sandia's proposed research focuses on the reversible phototuning of such interactions through the introduction of photosensitive molecular structures into the material system. This new material strategy provides optical actuation of nanointeractions impacting behavior on both the nano- and macroscales with the potential for impact in directed nanostructure formation, microfluidic rheology, and tribological control.

The work identified organic structures possessing known photophysical effects with a high probability for influencing target interaction processes, e.g., physical entanglement, hydrophobicity/-philicity, local electrostatic charge, or pH changes. Their incorporation into polymeric chemistries will allow their application to inorganic colloids as photoactive surfactants to enable the photoactuated (PA) control of interparticle nanointeractions to reduce the defect content of colloidal crystal arrays (artificial opals). Primary demonstration of successful nanointeraction control will be provided by zone refining of assembled colloidal crystals. A successful demonstration will provide proof that colloidal crystal arrays can be used to form complete photonic bandgaps (PBGs) by the elimination of defects that currently prevent bandgap development. Extension of these fundamental findings can also provide optically tuned microfluidic rheology and tribological control useful in a range of microsystems with an impact in Department of Energy Defense Programs technologies for stockpile safety and security.

Organic synthesis of the photocontrolled groups that affect behavior is a component that is critical to the success of this

...Sandia's proposed research focuses on...the introduction of photosensitive molecular structures into the material system....A successful demonstration will provide proof that colloidal crystal arrays can be used to form complete photonic bandgaps (PBGs) by the elimination of defects....Extension of these fundamental findings can also provide optically tuned microfluidic rheology and tribological control useful in a range of microsystems with an impact in Department of Energy Defense Programs technologies for stockpile safety and security.

project. We identified two chemistries, azobenzene and benzospiropyran, that show viability for production of a number of films and structures for the investigation of photocontrolled response. Terminating surfaces with monolayers of various photosensitive derivatives is a difficult multistage process, but we achieved some success with azobenzene that shows multiple switching variations that are steady and constant. Additional work will continue with these groups modified with fluorinated groups. Fluorinated silanes are commonly used in microelectromechanical systems (MEMS) applications for the prevention of stiction and have the potential to allow for photomodulation in aqueous systems.

Success in the photoactuation in colloidal crystal structures depends on the attachment of the photosensitive groups to the monodisperse silica colloids. We focused on ring-opening metathesis polymerization (ROMP) as a technique for the surface grafting of PA polymers due to its high tolerance to a wide variety of functional groups present in many dyes, gentle reaction conditions necessary for the production of polymer, and the ability to carry out these modifications in the presence of water. To date, there are no reports of ROMP polymers that have been grafted from the surface of silica beads or plates. To aid in the incorporation of dyes into the grafted polymers, we developed a general monomer containing a reactive amino terminus (for the attachment of a variety of dyes) as well as a norbornene terminus for ROMP. We demonstrated that this monomer produces polymer in its acyl-protected form as well as with a PA dye attached (bis[trimethylthienyl]maleimide). However, all attempts to graft ROMP polymers from the surfaces of silica beads were unsuccessful.

The termination of the silica particle surfaces with the photosensitive organic moieties is a technical hurdle that must be overcome for project success. There are numerous examples in the literature, and we expect success soon.

Success requires the use of a polymer with PA physical expansion/contraction. In the course of this research, we discovered that research for a photomechanical polymer has been pursued for decades, and no viable candidates in the solid state have been found. As an alternative demonstration of the use of photocontrolled nanointeractions, this project will lower the concentration of defects in colloidal crystal arrays using the photoreversible agglomeration and deagglomeration of particles arranged in a colloidal crystal array. The effectiveness can be followed by the methods that we proposed for observation of the photomodulated lattice in real time. The probability for success is greater with this demonstration, as literature

examples of a photodispersed system using spiropyran-terminated particles do exist.

38691

Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines

D. C. Dibble, J. J. Kelly

The performance of LIGA (acronym for the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) micromachines is directly linked to the mechanical, magnetic, and tribological properties of the electrodeposited alloys used in component fabrication. Surface-active compounds are used in the electrodeposition process to control grain nanostructure, composition, and internal stress of the alloy. Additives dramatically alter these properties and can greatly enhance the mechanical strength of the component, or they may contribute to undesirable effects, such as fracture embrittlement. Additives for electrodeposition processes are empirically developed. More importantly, there is little, if any, physicochemical understanding of the relationship between additive structure and electrochemical action. Sandia seeks to develop the science base needed for the rational development of alloy-deposition processes in LIGA using additives and other advanced electrodeposition techniques, such as pulsed current electrodeposition. We will develop nanoscale diagnostics that can be performed in situ during electrodeposition. We will use these diagnostics to characterize in detail the electrodeposits at the nanometer scale. The efforts of such an investigation will clearly focus on improving process conditions and will be facilitated by a close collaborative effort between fundamental surface science and electrochemical engineering methods.

We developed a state-of-the-art capability to image surfaces by scanning-probe microscopy in an electrochemical environment. We used this capability to understand the electrochemical deposition of metals. We also achieved the following:

- Observed the morphological evolution of 200 nm of nickel (Ni) while imaging the same $1\ \mu\text{m}^2$ area and recorded the morphological evolution with a resolution better than 10 nm by *in situ* atomic-force microscopy. At this magnification, we can clearly see changes in growth morphology caused by the presence of additives to the Ni bath.
- Controlled and imaged with subnanometer resolution the predominant nucleation sites and two-dimensional (2-D) to 3-D growth transition of Ni films of a fraction of a monolayer to

Sandia seeks to develop the science base needed for the rational development of alloy-deposition processes in LIGA using additives and other advanced electrodeposition techniques, such as pulsed current electrodeposition.... We developed a state-of-the-art capability to image surfaces by scanning-probe microscopy in an electrochemical environment. We used this capability to understand the electrochemical deposition of metals.

at least six monolayers thickness by control of deposition potential with an *in situ* scanning-tunneling microscope.

- Studied the effects of saccharin, coumarin, manganese, and boric acid on the evolving microstructure of Ni deposited from both Watts Ni and Ni sulfamate electrolytes over a range of deposition potentials and current densities. Time- and current-resolved image sequences clearly show the nucleation, growth, coalescence, and coarsening process of these films.
- Deposited, while imaging, Ni and Ni alloys in electrolytes that are different from LIGA baths only in that the metal-ion concentration is diluted to slow deposition rate.
- Determined that deposit morphology at fixed overpotential and integrated current for Ni and alloy films to 200 nm thickness is very repeatable in our system.
- Characterized the surface morphology of LIGA substrates and developed a procedure to pattern polycrystalline gold and copper substrates with similar morphologies.

Other Communications

Dibble, D. C., and J. J Kelly. 2003. *In situ* scanning-probe microscopy of the effects of additives on electrodeposited nickel. Paper presented at the Materials Research Society Meeting, April, San Francisco, California.

Dibble, D. C., and J. J Kelly. 2003. *In situ* scanning-probe microscopy of the effects of additives on electrodeposited nickel. Paper presented at Modern Microscopy/Scanning 2003, May, San Diego, California.

38692

Nanostructured Materials for Directed Transport of Excitation Energy

M. B. Sinclair, J. A. Floro, D. Y. Sasaki

One functionality that is extremely desirable for nanostructured materials is the ability to efficiently activate or interrogate structures within a nanomaterial using optical energy. However, given the packing densities obtainable with nanofabrication, direct focusing of incident optical energy onto individual nanostructures is impractical. The research described in this project will determine how the phenomenon of energy transfer can be harnessed to provide this functionality. Energy transfer is the process by which excitation energy resulting from absorption of photons can become delocalized and move from the site where the photon was absorbed. Energy transfer plays a prominent role in the photosynthetic process, where “light-harvesting antennas” efficiently absorb sunlight and deliver the excitation energy to the photosynthetic reaction center. The antennas comprise arrays of absorbing organic chromophores that are coupled via near-field electromagnetic (EM) interactions. Sandia will use the tools of nanotechnology to control the structure and, hence, the energy-transport properties of chromophore arrays. We will use nanolithography to pattern substrates in a manner that will allow us to measure the extent of delocalization in chromophore arrays. We will also use nanolithography to create site-energy and site-spacing gradients within chromophore arrays in an effort to drive excitation energy transport in predetermined directions. We will also utilize self-assembly techniques such as self-assembled monolayers (SAMs) and Langmuir-Blodgett (LB) films to control the growth, structure, and energy-transport properties of chromophore arrays. Recent theoretical investigations led to the prediction that surface plasmon coupling between adjacent nanoparticles in metallic nanoparticle chains can lead to energy delocalization and transport. We will fabricate metallic nanoparticle chains using both nanolithography and self-assembly. Using a variety of optical microscopies, we will develop methods to couple EM energy into these structures and characterize their energy-transport properties.

In the past we used LB techniques to prepare energy-transporting J-aggregates. These aggregates form upon compression of a two-dimensional monolayer film of dye-derivatized amphiphilic molecules spread on a water surface. We used fluorescence microscopy to monitor the size and shape

Sandia will use the tools of nanotechnology to control the structure and, hence, the energy-transport properties of chromophore arrays. We will use nanolithography to pattern substrates in a manner that will allow us to measure the extent of delocalization in chromophore arrays.

of the aggregated domains. Characteristic changes in the molecular emission spectrum that occur upon aggregation indicate the delocalization of excitation energy within the chromophore array. We also demonstrated the ability to transfer these aggregates to solid substrates for further investigation and/or integration with lithographically prepared structures. In addition, we synthesized highly crystalline arrays of strongly interacting organic chromophores. These crystals exhibit metallic-like reflectivity over a wide spectral band, indicative of strong coupling between the molecules in the array. Propagation of EM energy in surface exciton modes, in a manner similar to the plasmonic energy transport predicted for metallic nanostructures, should be possible.

We also systematically explored metallic-island formation and self-assembly during epitaxial deposition of silver on magnesium oxide (MgO) substrates. In general, we found that the island size increases with deposition temperature. Through suitable choices of deposition temperature, rate, and thickness, we prepared island arrays with average island sizes of 40 nm and with narrow, monomodal size distributions. Over a range of deposition thicknesses, the island size remains the same, while the density of the islands increases with the total thickness of the deposition. Thus, we were able to demonstrate experimental control over both the island size and the spacing, both of which are critical for fabricating candidate plasmonic structures for optical characterization. We also investigated methods to prepare terraced MgO substrates that can act as templates for the self-assembly of aligned nanoparticle chains. In particular, we found that MgO annealed in oxide (O_2) at high temperature forms (110) faceted surfaces along steps created during cleaving.

...we were able to demonstrate experimental control over both the island size and the spacing, both of which are critical for fabricating candidate plasmonic structures for optical characterization. We also investigated methods to prepare terraced MgO substrates that can act as templates for the self-assembly of aligned nanoparticle chains.

In particular, we found that MgO annealed in oxide (O_2) at high temperature forms (110) faceted surfaces along steps created during cleaving.

38693

Modeling Local Chemistry in the Presence of Collective Phenomena

N. A. Modine, M. E. Chandross

Many materials science problems are characterized by the interplay of two phenomena: chemical specificity (CS), controlled by the detailed behavior of chemical bonds, and collective phenomena (CP), where new behavior emerges from many body interactions. Sandia developed the core capabilities required for the world's first robust and efficient model bridging the length scales involved in these phenomena. To maintain a preeminent focus on materials science, we applied our approach to help understand the interplay between chemistry and collective phenomena during the aging of a complex material system, Zeolite-3A-based desiccants. Such investigations require a coupling of quantum mechanical (QM) methods and classical methods into the same simulation since classical simulation techniques cannot model CS reliably, while QM methods alone are incapable of treating the extended length and time scales characteristic of CP. In typical situations where the reactions responsible for CS are localized, while the weaker, longer-range interactions involved in CP can be classically represented, an efficient QM-to-classical coupling can be obtained by exploiting the natural spatial locality of electronic structure (Kohn's nearsightedness). Previous efforts along these lines used a simplified, empirical QM model and thus are limited to a narrow range of materials. In contrast, our first-principles approach has the potential to impact numerous mission-critical Sandia programs. In addition to the aging and reliability of desiccants, our model eventually could be applied to problems such as (1) science-based processing for ceramic/metal joints, e.g., in neutron tubes, where the relationship between chemical composition (CS) and interface integrity (CP) is poorly understood, and (2) proteomics, where active sites (CS) interact with a complex background consisting of the rest of the protein and its aqueous environment (CP).

We implemented an initial dynamic model bridging between QM and classical length scales and began preliminary work on our most challenging tasks. We coupled QM and classical regions by electrostatic and classical bonding interactions, and integrated the SOCORRO electronic structure code with the LAMMPS (Large-Scale Atomic/Molecular Massively Parallel Simulator) classical molecular dynamics (MD) code. Identifying the physical correspondence between

Many materials science problems are characterized by the interplay of two phenomena: chemical specificity (CS), controlled by the detailed behavior of chemical bonds, and collective phenomena (CP), where new behavior emerges from many body interactions. Sandia developed the core capabilities required for the world's first robust and efficient model bridging the length scales involved in these phenomena.

quantum and classical interaction terms to avoid the under- or overcounting of interactions in systems with covalent bonds that cross the quantum/classical interface was an unanticipated challenge. We continue to make progress on this issue. Furthermore, we identified a very promising technique for efficiently extending our approach to the case of large displacements of the atoms in the classical region, and we plan to implement this technique in the near future.

On the materials science front, we studied three different molecules absorbed in Zeolite-4A: water, ammonia, and the ammonium ion. Unlike previously studied systems, we found that these molecules prefer to absorb into the 8-oxygen rings of the zeolite structure, where crowding effects between the absorbed molecules and the native ions are important. Based on these observations, we are investigating a possible explanation for the irreversible aging observed in zeolite-based weapons desiccants. Furthermore, we developed a one-half-cell refinement of our original one-eighth-cell model that should give a very accurate representation of the behavior of molecules absorbed into the 8-oxygen rings of Zeolite-4A, while still allowing a considerable savings in computational cost. We are currently systematically evaluating the accuracy of this hierarchy of models. Finally, we began to optimize the performance of our algorithms by implementing an alternative approach to obtaining localized electronic states based on the Grassmann Conjugate Gradient algorithm.

...we identified a very promising technique for efficiently extending our approach to the case of large displacements of the atoms in the classical region, and we plan to implement this technique in the near future.

Refereed

Jaramillo, E., M. E. Chandross, and N. A. Modine. 2003. Adsorption of small molecules in LTA-type zeolites. 1. NH_3 , CO_2 , and H_2O in Zeolite-4A. *J. Physical Chemistry B*, submitted. SAND2003-2534J.

Other Communications

Modine, N. A., M. E. Chandross, and E. Jaramillo. 2003. Multiscale modeling of small molecules absorbed in Zeolite-4A. Paper presented at the APS March Meeting, 3–7 March, Austin, Texas.

38705

The Effects of Varying Humidity on Copper-Sulfide Film Formation

J. P. Sullivan, M. J. Campin, J. C. Barbour, R. G. Copeland, T. M. Mayer, N. A. Missert

Atmospheric corrosion of electrical components has been linked to a significant number of materials-related concerns for the long-term storage of the nuclear weapons (NW) stockpile. Further, the increasing use of copper (Cu) in commercial systems requires a long-term commitment to understand Cu corrosion mechanisms to reliably predict corrosion rates for commercial-off-the-shelf discrete components in the future stockpile. This project will study the effects of varying relative humidity (RH) in the sulfidation of Cu—a demonstrated and recurring corrosion problem for electrical devices. The complex interactions between a sulfidizing environment and an oxidized Cu surface are dependent upon RH and temperature. Small changes in the ambient temperature near room temperature may cause significant changes in the sulfidation mechanism that can lead to greatly differing morphology of the corrosion product layer. This corrosion product layer, primarily copper sulfide (Cu_2S), can impede mechanical functions of connectors and switches and alter the performance of electrical components. A detailed study of the critical steps during the initial stages of water-layer adsorption on an oxidized Cu surface and subsequent Cu sulfidation will allow identification of the relevant mechanisms governing the sulfide nucleation and growth processes. Sandia's measurements will identify critical kinetic processes in the initial stages of growth to ultimately obtain quantitative, predictive models of Cu sulfidation. We will use advanced high-resolution transmission-electron microscopy (TEM) techniques to correlate the microstructure of the Cu_2S product layer with the Cu sulfidation rate as a function of RH. In addition, we will use simulations of Cu diffusion in the presence of spatially varying source terms to model differences in growth rate at high and low RH. The experimental results obtained in this project will be used to support the creation of computational models of sulfidation that are being developed at Sandia.

Detailed experiments involving extensive high-resolution TEM revealed significant microstructural differences between Cu_2S 's sulfides formed at low and high RH. We knew from prior experiments that the sulfidation rate at low RH remains linear in time up to a sulfide thickness approaching or

Atmospheric corrosion of electrical components has been linked to a significant number of materials-related concerns for the long-term storage of the nuclear weapons (NW) stockpile. Further, the increasing use of copper (Cu) in commercial systems requires...[an understanding of] Cu corrosion mechanisms...for commercial-off-the-shelf discrete components in the future stockpile....Sandia's measurements will identify critical kinetic processes in the initial stages of growth to ultimately obtain quantitative, predictive models of Cu sulfidation.

exceeding $1.0\text{ }\mu\text{m}$, while the sulfidation rate at high RH becomes sublinear at a sulfide thickness less than about $0.2\text{ }\mu\text{m}$ and eventually approaches zero. TEM measurements of the Cu_2S morphology revealed that the Cu_2S formed at low RH has large-sized grains (75 to greater than 150 nm) that are columnar in structure with sharp, abrupt grain boundaries. In contrast, the Cu_2S formed at high RH has small equiaxed grains of $20\text{--}50\text{ nm}$ in size. Importantly, the small grains formed at high RH have highly disordered grain boundaries with a high concentration of nanovoids.

We performed two-dimensional diffusion modeling to determine whether the existence of localized source terms at the $\text{Cu}/\text{Cu}_2\text{S}$ interface could be responsible for the suppression of Cu sulfidation at long times at high RH. The models indicated that the existence of static, localized source terms would not predict the complete suppression of growth that was observed. Instead, the models suggest that the diffusion of Cu through Cu_2S becomes restricted during Cu_2S formation at high RH. The leading speculation is that the extensive voiding that exists at grain boundaries in this material greatly reduces the flux of Cu between grains, leading to a reduction in the rate of sulfide film formation.

These experiments provide an approach for adding microstructural information to Cu-sulfidation-rate computer models. In addition to the microstructural studies, we developed new micropatterned test structures to offer insight into the point-defect structure of Cu_2S and to permit measurement of surface reaction rates during Cu sulfidation. We measured the surface reaction rate by creating micropatterned Cu lines of widths ranging from $5\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$. When sulfidized, the edges of the Cu lines show greater sulfidation than the center, an effect known as *microloading*.

Measurement of the sulfidation profile enables an estimate of the ratio of the diffusivity of hydrogen sulfide (H_2S) in the gas phase to the surface reaction-rate constant, k . Our measurements indicated that the gas-phase diffusivity exceeds k by more than 10, but less than 100. This is consistent with computer simulations of the sulfidation process. We developed other electrical test structures to measure the electrical conductivity of Cu_2S that forms on Cu. This information can be used to determine relative vacancy concentrations in the Cu_2S layer as a function of RH. The test structures involved micropatterned Cu disks and thin films, and the initial measurements showed that the electrical approach is feasible for point-defect studies in Cu_2S .

Refereed

Campin, M. J., J. C. Barbour, J. W. Braithwaite, J. G. Zhu, and P. P. Provencio. 2003. Structural studies of the initial stages of copper sulfide film growth: Influence of humidity. *Microscopy and Microanalysis, Proc. 2003 Annual Meeting of the Microscopy Society of America* **8** (2) (3–7 August, San Antonio, Texas).

Campin, M. J., J. G. Zhu, J. P. Sullivan, J. C. Barbour, J. W. Braithwaite, and P. P. Provencio. 2003. Structural studies of copper sulfide film growth: Influence of humidity. *J. Materials Research*, submitted.

Campin, M. J., J. P. Sullivan, J. C. Barbour, J. W. Braithwaite, P. P. Provencio, and J. G. Zhu. 2003. Structural studies of copper sulfide film growth: Influence of humidity. *Proc. Materials Research Society Meeting* **781** (22–25 April, San Francisco, California): Z2.6.1–Z2.6.6.

Other Communications

Campin, M. J. 2003. Microstructural investigation of copper corrosion: Influence of humidity. Ph.D. Thesis, Department of Physics, New Mexico State University, Las Cruces, New Mexico.

39017

Solution-Based Nanoengineering of Materials*J. A. Voigt, T. J. Boyle, R. T. Cygan, B. C. Bunker, J. Liu, L. J. Criscenti*

Solution-based synthesis is a powerful approach for creating nanostructured materials. Although there have been significant recent successes in its application to fabricating nanomaterials, the general principles that control solution synthesis are not well understood. Sandia's purpose in this project is to develop the scientific principles required to design and build unique nanostructures in crystalline oxides, II/VI semiconductors, and other technologically significant materials using solution-based molecular self-assembly techniques. The ability to synthesize these materials in a range of different nanoarchitectures (from controlled-morphology nanocrystals to surface-templated three-dimensional [3-D] structures) will provide new opportunities for the development of interactive interfaces for optics, electronics, and sensors. The wide range of interfacial nanostructures of zinc oxide (ZnO), including hexagonal rods, hollow hexagons, and oriented thin sheets, produced recently via nucleation and growth from aqueous solutions illustrates the potential of this approach. The key to controlled fabrication of such nanostructures lies in understanding the factors that control nucleation and growth processes. To achieve this understanding, we will conduct systematic nucleation and growth studies that combine (1) synthesis using carefully controlled and monitored flow-reactor systems, (2) characterization of surface chemistry and complexation, and (3) molecular modeling. We will use unique flow reactors to control all of the critical system parameters such as supersaturation levels, hydrodynamics, and the concentrations of additives that promote nucleation and influence relative growth rates on specific crystal faces. We will use techniques such as Fourier-transform infrared (FTIR) spectroscopy, surface-charge measurements, and interfacial-force microscopy (IFM) to monitor the extent and orientation of additive adsorption and the effect that such agents have on interfacial properties. Finally, we will use surface-energy calculations based on interatomic potentials to model ligand adsorption on hydrated crystal surfaces. We will use these calculations to design crystallographically specific adsorbate ligands that we will synthesize and test as surface-specific nucleation promoters and growth inhibitors.

Solution-based synthesis is a powerful approach for creating nanostructured materials....[although] the general principles that control solution synthesis are not well understood. Sandia's purpose in this project is to develop the scientific principles required to design and build unique nanostructures in crystalline oxides, II/VI semiconductors, and other technologically significant materials using solution-based molecular self-assembly techniques. ...[This] will provide new opportunities for the development of interactive interfaces for optics, electronics, and sensors.

(1) *Advances in molecular modeling of ZnO surfaces and ligand adsorption.* We greatly expanded our predictive capabilities, i.e., much improved agreement between experimental results and model predictions, through extension of previous modeling efforts. Again using the ZnO system as our model system, we developed representative periodic models for the three primary ZnO growth surfaces, (100), (101), and (001), in which surface oxygens were protonated as expected in an aqueous solution at 25°C and pH 7 (similar to experimental growth conditions) according to the revised multisite complexation (MUSIC) model. We used two-dimensional (2-D) molecular-mechanics calculations to derive relative binding energies of several different adsorbates on each of the zincite surfaces. We initially equilibrated each ZnO surface to allow for complete surface relaxation and then obtained optimized configurations for each adsorbate-surface system. We derived binding enthalpies from the energy difference between the optimized configuration and one in which the adsorbate was appreciably removed from the surface.

We calculated binding energies for the various adsorbates (acetate, chloride, citrate, ethylenediaminetetraacetate [EDTA], hexamethylenetetraamine [HMT], methane, nitrate, perchlorate, thiol, and water) onto the three ZnO surfaces, (001), (100), and (101).

The most intriguing result from the present molecular-modeling study is our success in matching the experimental result, specifically, that citrate binds much more strongly to the (001) zincite surface than to either the (101) or the (100) surface. The experiments demonstrate a strong growth inhibition on the (001) surface, leading to a more platy ZnO morphology.

(2) *Controlled ZnO nucleation.* To better control both nucleation and growth of ZnO heterostructures, we developed a continuous-flow-reactor system and began to investigate patterned, templated nucleation. The flow-reactor system is simple in design. It consists of a small cylindrical reaction chamber (total volume = 6 ml) that is suspended horizontally in a constant-temperature water bath. The film substrate is laid flat in the cylinder with the intended growth surface down and submerged in growth solution that is continuously fed into and out of the reactor. This, in contrast to the previously used batch-reactor system, provides constant composition growth conditions and the ability to introduce growth modifiers with great control.

Nucleation control via templating off of patterned substrates offers the potential for controlling ZnO rod spacing and array

The most intriguing result from the present molecular-modeling study is our success in matching the experimental result, specifically, that citrate binds much more strongly to the (001) zincite surface than to either the (101) or the (100) surface. The experiments demonstrate a strong growth inhibition on the (001) surface, leading to a more platy ZnO morphology.

configurations. We had some initial success in this area. We previously developed the process for nucleating and growing ZnO arrays off of seed films of nanoparticles of ZnO. The patterning of these films offers a method for controlling where ZnO arrays are nucleated.

(3) *Advances in growth of ZnO and other systems.* Through use of a growth modifier in the ZnO system, we produced a wide range of unusual complex microstructural features that are remarkably similar to biomaterials. For example, using multiple-step-seeded nucleation and growth, and using citrate as the surface modification agent (as discussed in the modeling section above), we produced large arrays of ZnO nanostructures that are very similar to those from biogenic calcium carbonate. The growth of the oriented nanoplates is quite unusual and is directly related to the function of the organic acid (citrate) that prohibited the growth of rods and promoted the growth of plates. We applied the film-growth approach developed for the ZnO system to several other materials systems to produce oriented nanostructures, including conductive polymers, titanium dioxide (TiO₂) nanowires, and mesoporous silicates. For example, we used a novel hierarchical and self-similar crystal-growth process to produce controlled-morphology mesoporous silicate film structures with ordering from the nano- to macroscale.

Through use of a growth modifier in the ZnO system, we produced a wide range of unusual complex microstructural features that are remarkably similar to biomaterials.

Refereed

Liu, J., Y. Lin, L. Liang, J. A. Voigt, D. L. Huber, Z. R. Tian, E. Coker, B. McKenzie, and M. J. McDermott. 2003. Templateless assembly of molecularly aligned conductive polymer nanowires: A new approach for oriented nanostructures. *Chem. Euro. J.* **9**:605–11.

Tian, Z. R., J. A. Voigt, J. Liu, B. McKenzie, and M. J. McDermott. 2003. Biomimetic arrays of oriented ZnO nanorods and columns. *J. Am. Chem. Soc.* **124**:12954–55.

Tian, Z. R., J. A. Voigt, J. Liu, H. Xu, and M. J. McDermott. 2003. Dendritic growth of cubically ordered nanoporous materials through self-assembly. *Nano Letters* **3**:89–92.

Tian, Z. R., J. Liu, H. Xu, J. A. Voigt, B. McKenzie, and C. M. Matzke. 2003. Shape-selective growth, patterning, and alignment of cubic nanostructured crystals via self-assembly. *Nano Letters* **3**:179–82.

Tian, Z. R., J. Liu, J. A. Voigt, B. McKenzie, and H. Xu. 2003. Hierarchical and self-similar growth of self-assembled crystals. *Angew. Chem. Int. Ed.* **42**:414–17.

Other Communications

Criscenti, L. J., R. T. Cygan, and J. A. Voigt. 2003. Molecular modeling of the adsorption of anionic and molecular species to zincite surfaces. Paper presented at the 225th American Chemical Society National Meeting, 23–27 March, New Orleans, Louisiana.

Liu, J., Z. R. Tian, and J. A. Voigt. 2003. Spontaneous hierarchical growth, patterning, and alignment of self-assembly materials. Paper presented at the Materials Research Society Spring Meeting, 20–25 April, San Francisco, California.

Tian, Z. R., J. A. Voigt, J. Liu, and B. McKenzie. 2003. Generalized solution synthesis of large arrays of oriented nanowires and their applications. Paper presented at the Materials Research Society Spring Meeting, 20–25 April, San Francisco, California.

Tian, Z. R., J. Liu, J. A. Voigt, H. Xu, M. J. McDermott, and B. McKenzie. 2003. Biomimetic syntheses of extended and oriented ZnO nanostructures. Paper presented at the 225th American Chemical Society National Meeting, 23–27 March, New Orleans, Louisiana.

Tian, Z. R., J. Liu, J. A. Voigt, H. Xu, M. J. McDermott, and B. McKenzie. 2003. Large arrays of oriented nanowires: Generalized solution syntheses and applications. Paper presented at the 225th American Chemical Society National Meeting, 23–27 March, New Orleans, Louisiana.

Tian, Z. R., J. Liu, J. A. Voigt, H. Xu, M. J. McDermott, B. McKenzie, and C. M. Matzke. 2003. Hierarchically growing, patterning, and aligning self-assembled nanostructured materials. Paper presented at the 225th American Chemical Society National Meeting, 23–27 March, New Orleans, Louisiana.

Voigt, J. A., Z. R. Tian, E. Coker, L. J. Criscenti, J. Liu, R. T. Cygan, B. McKenzie, and D. Sipola. 2002. Solution synthesis of ZnO columnar film microstructures. Paper presented at the 2nd International ZnO Workshop, 23–25 October, Dayton, Ohio.

Voigt, J. A., Z. R. Tian, J. Liu, L. J. Criscenti, R. T. Cygan, and B. McKenzie. 2003. Bioinspired synthesis of large arrays of extended and oriented nanostructures. Paper presented at the Materials Research Society Spring Meeting, 20–25 April, San Francisco, California.

52531

Assembly and Actuation of Nanomaterials Using Active Biomolecules

G. D. Bachand, R. P. Manginell, M. P. De Boer, S. J. Hearne, J. Liu, B. C. Bunker, C. M. Matzke

The formation and functions of living materials and organisms are fundamentally different from those of synthetic materials and devices. Synthetic materials tend to have static structures and are not capable of adapting to the functional needs of changing environments. In contrast, living systems use energy to create, heal, reconfigure, and dismantle materials in a dynamic, nonequilibrium fashion. The overall goal of this research is to organize and reconfigure functional assemblies of nanoparticles using strategies that mimic those found in living systems. The strategy for the active assembly of nanostructures is based on the principles used by diatomaceous algae to assemble silica shells. Sandia will study active assembly by using active biomolecules to create nanowires for programmable interconnects via the on-chip manipulation of gold (Au) nanoparticles. In this system, we will use kinesin motor proteins and microtubules (MTs) to direct the transport of Au nanoparticles on lithographically defined array patterns such that the particles form nanowires and associated interconnects. The strategy for the responsive reconfiguration of nanostructures will mimic the principles used by fish to change skin color. In this strategy, we will use active biomolecules to mediate the optical properties of quantum-dot (QD) arrays through modulation of interparticle spacing. Here, we will control the spacing between different-sized QDs by activation of kinesin motor proteins, and subsequent fluorescence resonance energy transfer (FRET) will occur between QDs as the interparticle spacing is changed. In this work, we will be able to create and reconfigure synthetic nanostructures using biomimetic processes that direct energy consumption to single molecules, and we will also be able to remove diffusional and entropic limitations. The ability to use active biomolecules and nanomaterials in integrated systems could revolutionize the exploitation of nanostructured material in complex systems.

We focused on establishing platforms for (1) synthesis and functionalization of biomolecules and synthetic nanoparticles, (2) development of microfluidic systems for directed transport of MT shuttles, and (3) characterization of MT-nanoparticle

Active transport of microtubule fibers coated with 30 nm Au nanoparticles. This video demonstrates the ability of kinesin motor proteins to translocate a microtubule functionalized with Au nanoparticles.

Sandia will study active assembly by using active biomolecules to create nanowires for programmable interconnects via the on-chip manipulation of gold (Au) nanoparticles.

composite structures. Overall, we achieved excellent progress on these goals.

We isolated a robust kinesin motor from a thermophilic fungus (*Thermomyces lanuginosus*) and cloned it into a protein expression system. We genetically engineered this kinesin to create unique chemical “handles” in the cargo-carrying region of the motor protein to bind nanoparticle cargo. These handles included a 10x histidine tag capable of binding divalent metals and a unique cysteine residue for performing thiol-based chemistry. This activity established a rapid, reliable, and flexible system for producing large quantities of a stable kinesin motor protein with multiple functional handles.

We synthesized Au nanoparticles and cadmium selenide (CdSe) nanocrystal QDs at Sandia and Los Alamos National Laboratory, respectively. We attached Au nanoparticles and QDs to MT shuttles using biotin-streptavidin functionalization of individual components. We used varying ratios of unlabeled biotinylated tubulin to polymerize MTs, which resulted in MTs with a range of loading capacity. We then attached streptavidin-labeled Au nanoparticles and nanocrystal QDs to the MTs. We characterized the resulting composite materials using transmission-electron, atomic-force, and fluorescence microscopy. The data suggest that the nanoparticle coating is relatively dispersed and uniform along the length of the MT. We assembled highly ordered nanostructures at high ratios (> 50%) of biotinylated tubulin. Overall, we demonstrated the successful assembly of composite nanomaterials consisting of a functionalized biopolymer and metal/semiconductor nanoparticles.

We performed transport-based assays to assess the ability of kinesin motor proteins to transport nanoparticle-coated MTs. In these assays, we tethered kinesin motors to a silicon surface such that the head region is capable of transporting MTs across a surface. In these experiments, the kinesin motor proteins were able to successfully transport Au-coated, but not QD-coated, MTs in motility assays, suggesting differing interactions between the nanoparticles and biological components. We observed kinesin transport of QD-coated MTs when the MTs were modified to contain a cargo-binding domain in the middle of the MT. Together, these experiments provided a fundamental demonstration that nanoparticle transport can be achieved using kinesin motor proteins.

We designed, fabricated, and tested prototype microfluidic devices for the ability to direct the transport of MT shuttles using both physical (lithographic features) and chemical barriers (self-assembled monolayers [SAMS]). The results

Overall, we demonstrated the successful assembly of composite nanomaterials consisting of a functionalized biopolymer and metal/semiconductor nanoparticles. ...these experiments provided a fundamental demonstration that nanoparticle transport can be achieved using kinesin motor proteins.

indicated that amine- and alcohol-terminated SAMs provided the best chemical barriers and the most efficient guiding of MT in lithographically defined channels. These experiments help establish critical parameters for directed transport of nanoparticle-MT composites in microfluidic systems.

We prepared initial designs of the microcantilever arrays and submitted them for processing at Sandia's Microelectronics Development Laboratory (MDL). These designs should permit characterization of the mechanical forces associated with the polymerization of MT arrays tethered to microfluidic surfaces.

We achieved critical milestones and established a number of key technologies necessary to achieve the final goals of demonstrating active assembly of nanostructures and responsive reconfiguration of nanostructures.

Refereed

Bachand, G. D. 2003. Active and dynamic nanomaterials based on active biomolecules. Paper presented at Nanotechnology 2003: Big Things in Little Packages, American Association for the Advancement of Science (AAAS), 13–14 February, Denver, Colorado.

Boal, A. K., J. M. Bauer, S. B. Rivera, R. G. Manley, G. D. Bachand, R. P. Manginell, and B. C. Bunker. 2003. Engineered microchannels for active nanomaterials assembly. Paper presented at the Bio-, Micro-, Nanosystems Conference (IEEE-EMBS), 7–10 July, New York, New York.

Bunker, B. C., G. D. Bachand, A. K. Boal, S. B. Rivera, T. J. Headley, J. M. Gaudioso, J. B. Bauer, R. P. Manginell, H. Hess, and V. Vogel. 2003. Nanoparticle transport using microtubules and motor proteins. Paper presented at the American Vacuum Society 50th International Symposium, 2–7 November, Baltimore, Maryland.

Hess, H., G. D. Bachand, and V. Vogel. 2003. Motor proteins in synthetic materials and devices. *Encyclopedia of Nanoscience and Nanotechnology*, accepted.

Liu, J., G. D. Bachand, B. C. Bunker, A. K. Boal, and S. B. Rivera. 2003. Active assembly of dynamic and adaptive materials based on motor proteins and microtubules. Paper presented at the 2003 World Congress on Medical Physics and Biomedical Engineering, 23–30 August, Sydney, Australia.

Rivera, S. B., A. K. Boal, B. C. Bunker, J. Liu, and G. D. Bachand. 2003. Conjugation and transport of quantum dots and nanoparticles by microtubule-associated kinesin motor proteins. Paper presented at the Bio-, Micro-, Nanosystems Conference (IEEE-EMBS), 7–10 July, New York, New York.

Rivera, S. B., and G. D. Bachand. 2002. Expression and characterization of kinesin from *Thermomyces lanuginosus*. Paper presented at the 2002 American Chemical Society—Rocky Mountain Regional Meeting, 12–15 October, Albuquerque, New Mexico.

52698

Decomposition of Contaminants Using Photochemically Active Nanoparticles

K. F. McCarty, R. A. Kemp, T. J. Boyle, D. R. Jennison, B. A. Simmons, A. J. Antolak, T. Zifer

The decomposition of hazardous biological (viruses and bacteria) and nonbiological (e.g., nerve agents, H_2S , HCN) compounds can be realized using a new class of photochemically active nanoparticles that have been fine-tuned for decontamination applications. Several metal oxides (TiO_2 , ZnO , Fe_2O_3 , WO_3) demonstrate the ability to destroy contaminants upon exposure to ultraviolet (UV) light; however, to make them of practical use, their activity must be improved. These materials work by photoactivating water and oxygen to create highly reactive species (e.g., $OH^\bullet$) that readily decompose the compounds described above. Sandia's approach is to develop highly photoactive, doped nanomaterials using novel synthetic routes. We will link materials-synthesis studies to understanding the underlying physical mechanisms of these reactions through the use of in situ microscopy and spectroscopy. We will couple these efforts to first-principles calculations examining the advantages of likely dopants, followed by a study of reaction processes and statistical mechanical modeling of the reaction dynamics after a material/dopant is selected. In this manner, we will unravel the complex interrelationship between nanostructure, composition, and photochemical activity. Directed by this understanding, we will use sol-gel and surfactant-based supramolecular self-assembly techniques to engineer optimized nanostructures with specified compositions. We will verify the photochemical activity of these improved materials by testing. The ultimate outcome of this work will be the development of a new class of highly active materials for wide-ranging decontamination applications.

We developed and optimized the synthesis methods of TiO_2 (titanium dioxide) nanoparticles from hydrolysis-directed synthesis using two distinct techniques: (1) sol-gel chemistry and (2) self-assembled supramolecular surfactant microemulsions. We also developed and applied methods to physically characterize the nanoparticles, including their size, degree of agglomeration, and crystal structure. We implemented a two-pronged approach to evaluate photocatalytic activity. First, we developed and employed a simple procedure to screen nanoparticles for photocatalytic activity. The procedure measures the rate at which UV light decomposes an organic

The decomposition of hazardous biological (viruses and bacteria) and nonbiological (e.g., nerve agents, H_2S , HCN) compounds can be realized using a new class of photochemically active nanoparticles that have been fine-tuned for decontamination applications....we will unravel the complex interrelationship between nanostructure, composition, and photochemical activity...The ultimate outcome of this work will be the development of a new class of highly active materials for wide-ranging decontamination applications.

molecule (the dye methyl orange) in an aqueous suspension of nanoparticles. This testing established that our TiO_2 nanoparticles exhibit photocatalytic activity for decomposition that is already more than five times that of commercial TiO_2 particles. Second, we began developing the capability to test the activity to decompose bioagent simulants and nonbiological (e.g., nerve-agent simulants, H_2S , HCN) compounds. After reviewing the literature, we designed a reactor using off-the-shelf components to measure the efficiency of bioagent decomposition.

Our materials development was aided by efforts to understand the underlying physical mechanisms using first-principles electronic-structure calculations and *in situ* microscopy. The calculations analyzed the nature of nitrogen-doped TiO_2 . We successfully developed a simple route to this material, which is yellow in color and is believed to absorb in the visible (unlike pure TiO_2 , whose bandgap is in the UV). The calculations show that nitrogen substituting for lattice oxygen is likely responsible for the visible absorption. Finally, we used low-energy-electron microscopy to investigate the rate at which TiO_2 reacts with oxygen in the presence and absence of UV irradiation. The surprising lack of UV enhancement of the reaction rate limits the possible microscopic processes.

The calculations analyzed the nature of nitrogen-doped TiO_2 .

We successfully developed a simple route to this material,....

52699

Thermally Cleavable Surfactants

B. A. Simmons, K. Rahimian, G. M. Jamison, J. R. McElhanon, L. A. Domeier, T. Zifer

Surfactants are molecules that have the ability to self-assemble into a variety of supramolecular structures. These structures, and the intrinsic amphiphilic nature of the oil-water interface they possess, have been used in numerous laboratory and industrial processes, including the synthesis of advanced materials. A major problem associated with the use of surfactants is their subsequent removal after use and the recovery of segregated materials. Sandia successfully developed two novel approaches to surfactant removal using thermally degradable surfactants and metathesis depolymerization that contain weaklinks internal to the molecule itself. The thermal degradation is based upon a reversible Diels-Alder reaction, which has already found utility at Sandia in the preparation of removable encapsulants, foams, adhesives, and dendrimers. We based the metathesis depolymerization degradation on a catalyzed alkane ring-forming reaction of the surfactant that has been widely used in polymer science.

Surfactant removal becomes significant in the realm of extended mesoporous nanosized structures, such as ceramics, polymers, inorganic nanocrystals, and polymer-ceramic composites. The present technique of material recovery is typically a combination of centrifugation, calcination, and solvent washing that destroys the desired architecture and functionality of the synthesized material. The incorporation of a cleavable linkage would solve this problem by allowing for the removal of the surfactant molecules through the formation of a hydrophilic section and a hydrophobic section. These two sections then dissolve into the appropriate phase and are permanently removed from the system through their respective cleaving process. We will computationally model and correlate phase behavior and supramolecular self-assembly of the synthesized surfactants with experimental results to develop a fundamental knowledge of these molecules. Once we obtain a working knowledge of these systems, we will synthesize previously unobtainable extended ceramic, polymeric, and composite materials within these systems, recovered after cleavage, and fully characterized.

We identified two synthetic routes for the incorporation of a cleavable linker to be incorporated within a surfactant

Sandia successfully developed two novel approaches to surfactant removal using thermally degradable surfactants and metathesis depolymerization that contain weaklinks internal to the molecule itself....Surfactant removal becomes significant in the realm of extended mesoporous nanosized structures, such as ceramics, polymers, inorganic nanocrystals, and polymer-ceramic composites....[W]e will synthesize previously unobtainable extended ceramic, polymeric, and composite materials within these systems, recovered after cleavage, and fully characterized.

molecule. We used these two synthetic routes to prepare and analyze a new class of nonionic and anionic monomeric cleavable surfactants. These linkers are based upon Diels-Alder thermally degradable linkages and Grubbs catalyzed ring-forming depolymerization. We also began the initial synthesis of a Gemini surfactant that possesses a Diels-Alder linkage in the spacer between the two surfactants. As a result of this work, we submitted two technical advances and an abstract for a presentation at the Fall 2003 American Chemical Society National Meeting.

The Diels-Alder surfactant linkage consists of a diene and a dienophile adduct situated between the hydrophilic and hydrophobic moieties of the surfactant. We synthesized and characterized five new surfactants containing two different polar head groups with varying hydrophobic tails. Structural characterization for all surfactants was determined by H-proton nuclear magnetic resonance (NMR). We began initial characterization of dynamic and static surfactant behavior on two of the surfactants. Deprotonation of the head groups yielded surfactants that form aqueous micellar aggregates above a critical micelle concentration as indicated by dye micellization, dye solubilization, and surface-tension measurements. When exposed to elevated temperatures, typically in the range of 80°–95°C, the surfactants lose their surface-active properties and disassociate into oil and water-soluble components.

We also synthesized and characterized a surfactant that can undergo a variation of metathesis depolymerization. These surfactants possess a cleavable element that is susceptible to a catalyst that essentially transforms the hydrophobic tail section of the surfactant molecule into alkane rings. After a small amount of the catalyst is added to a surfactant solution, NMR results indicate the formation of alkane rings and a decrease in surfactant molecule concentration.

Other Communications

Long, T. M., B. A. Simmons, J. R. McElhanon, D. A. Loy, D. R. Wheeler, K. Rahimian, and G. A. Jamison. 2003. Metathesis depolymerization removable surfactant template. Paper presented at the American Chemical Society National Fall Meeting, 10 September, New York, New York.

McElhanon, J. R., T. Zifer, S. R. Kline, G. A. Jamison, K. Rahimian, D. A. Loy, D. R. Wheeler, and B. A. Simmons. 2003. Thermally cleavable surfactants based on Furan-Maleimide Diels-Alder adducts. *J. American Chemical Society*, to be submitted.

52700

Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions

E. H. Majzoub, K. J. Gross, D. R. Tallant, V. Ozolins

The transformation mechanisms of sodium aluminum hydride (NaAlH_4) to its decomposition products of hexahydride (Na_3AlH_6), and sodium hydride (NaH) are of technological importance. This material is currently of interest to both auto manufacturers and the hydride-storage community as a whole for its promising hydrogen (H) weight percentage (around 5 wt.%, more than double the current technology) and its differing nature from the traditional interstitial hydrides.

The material was discovered to be “reversible” through hydriding and dehydriding reactions by the addition of a “dopant,” typically a transition metal such as titanium (Ti). However, the mechanism, or action, of the dopant is still an open question. This mechanism increases the reaction kinetics by many orders of magnitude, catapulting the material from a standard chemical-reducing agent to the forefront of H-storage technology.

NaAlH_4 and other hydrides in this class of materials differ from the classic interstitial hydrides in that these materials have ionic character, with covalently bonded constituents in the atomic-cell structure. This is in stark contrast to the “lattice gas” models used to describe the interstitial hydrides, and new models are needed here. The H bonding and movement in the bulk structure of these materials is certainly different and is also dramatically affected by the addition of transition-metal “dopants.”

Sandia will continue development of models and preparation of samples to expose the mechanism and possible defect structures introduced into the lattice by the addition of “dopant” materials.

The proper understanding of these principles in NaAlH_4 may be applicable to a wider range of this class of materials. Because this class of materials also includes compounds with a much higher weight percent of H, there is promise that the Department of Energy goals for over 6–7 wt.% H can be achieved.

Our first two tasks were sample preparation and data collection. Much of the data collection was done at the National Institute of Standards and Technology (NIST), at the NIST Center for Neutron Research (NCNR). Data collected included both neutron diffraction and inelastic neutron scattering (INS).

...[S]odium aluminum hydride (NaAlH_4) [and] its decomposition products of hexahydride (Na_3AlH_6), and sodium hydride (NaH) are of....interest to both auto manufacturers and the hydride-storage community as a whole for its promising hydrogen (H) weight percentage (around 5 wt.%, more than double the current technology) and its differing nature from the traditional interstitial hydrides....Sandia will continue development of models and preparation of samples to expose the mechanism and possible defect structures introduced into the lattice by the addition of “dopant” materials.

INS data were collected for pure NaAlH_4 and also the related compound LiAlH_4 (lithium aluminum hydride). Other inelastic data were collected as well and involved various decomposition products.

Sample preparation for the neutron diffraction required the production of the deuteride, incurring many lengthy steps. The diffraction data were successfully collected and analyzed through the Rietveld refinement procedure for powder diffraction. We performed first-principles (*ab initio*) calculations using both the local-density approximation (LDA) and the generalized-gradient approximation (GGA) and compared them to the Rietveld refined data to determine which approximation would better reproduce the experimental observations. This allows us to use these modeling tools with verification and validation of their applicability.

Refinement results from the work also included the first data regarding structural changes to the alanate lattice structure upon doping with Ti. The results indicate that there is no large structural modification upon doping, but the results are inconclusive on very subtle changes, such as small atomic-position modifications within the unit cell. These changes should be observable with the new single-crystal samples.

We compared *ab initio* phonon-mode calculations qualitatively to INS data collected in our first task. This work is still ongoing, and quantitative comparisons are “in the works.”

We collected Raman spectroscopy and nuclear magnetic resonance (NMR) data; they promise to provide helpful information in the near future.

*The diffraction data were successfully collected and analyzed through the Rietveld refinement procedure for powder diffraction. We performed first-principles (*ab initio*) calculations using both the local-density approximation (LDA) and the generalized-gradient approximation (GGA) and compared them to the Rietveld refined data to determine which approximation would better reproduce the experimental observations. This allows us to use these modeling tools with verification and validation of their applicability.*

52701

Quantification of Environments and Surfaces Within Micropackages

S. M. Thornberg, R. A. Plass, J. S. Custer, M. R. Keenan, K. R. Zavadil, D. R. Tallant, D. E. Peebles

The expanding role of microsystems from new devices to microinstrumentation up to highly integrated total analytical systems (μ TAS) requires a new approach to reliability science. For long-term reliability and proper device function, the internal gaseous environment must be carefully maintained or controlled and surface contamination kept to a minimum. Therefore, tools are needed to measure not only surface contamination but also the gas composition and pressure.

Aging processes can significantly degrade the long-term performance and reliability of dormant microelectromechanical systems (MEMS) devices. This degradation results from materials interactions with the evolving microenvironment by changing both bulk and interfacial properties (e.g., mechanical and fatigue strength, interfacial friction and stiction, and electrical resistance). Eventually, device function is threatened and, as such, these aging processes are considered as high-negative-consequence processes. Examples include displacement of antistiction coatings, adsorption/condensation or reaction in occluded device spaces and gaps, adsorbate-assisted chemical processes at contacting surfaces, and field-assisted chemical processes (i.e., anodic oxidation).

Sandia developed methods for measuring internal pressure and gas composition inside typical anodically bonded cavities (~ 3 mL volume) and surface composition in a variety of small length-scale structures. We found elevated hydrogen concentrations in some devices and not in others. Surface chemical information is generated using a combination of scanning-probe microscopy (SPM), time-of-flight secondary ion mass spectrometry (TOF-SIMS) and scanning infrared (IR) spectroscopy. Multivariate statistical methods are applied for both individual techniques and across technique domains to optimally extract both compositional and spatial variations. As an example, we demonstrated the ability for a vapor silane-coupling agent to penetrate an occluded-volume microstructure via the thermal and moisture-driven displacement mechanisms.

Our methods extend beyond silicon (Si)-based microsystems enabling application to systems comprising III–V semiconductor materials carbon-based systems, LIGA (acronym for the German term Lithographie, Galvanoformung,

Sandia developed methods for measuring internal pressure and gas composition inside typical anodically bonded cavities (~ 3 mL volume) and surface composition in a variety of small length-scale structures....Our methods extend beyond silicon (Si)-based microsystems enabling application to systems comprising III–V semiconductor materials carbon-based systems, LIGA...processing, and biotechnological applications.

und Abformung, for lithography, electroforming, and molding) processing, and biotechnological applications.

The aging processes of chemical and physical materials can significantly degrade the long-term performance and reliability of dormant microsystems. This degradation results from materials interactions with the evolving microenvironment by changing both bulk and interfacial properties (e.g., mechanical and fatigue strength, interfacial friction and stiction, electrical resistance). Eventually, device function is clearly threatened and, as such, these aging processes are considered to have the potential for high (negative) consequences.

Sandia is developing analytical characterization methodologies for identifying the chemical constituents of packaged microsystem environments, and test structures for proving these analytical techniques. To accomplish this, we are developing a MEMS test device containing structures expected to exhibit dormancy/analytical challenges, extending the range of detection for a series of analytical techniques, merging data from these separate techniques for greater information return, and developing methods for characterizing the internal atmosphere/gases.

We developed a microsystem test module to include common structures as well as an occluded-volume test structure that can be accessed using mechanical actuation. The device is a poly-1,2 laminate Si beam inserted into a poly-3 tunnel. The top of the beam represents one surface of an occluded volume in the inserted configuration that is subject to chemical modification from all subsequent-release chemistry process steps as well as any dormancy-related modification processes. These beams can be extracted with preservation of their surface chemistry and with minimal particle production.

Analytical technique development is focusing on characterization of critical microsystem components at length scales relevant to microsystems. An example of microsystem components analysis is highlighted in our TOF-SIMS characterization of the occluded-volume structure previously described. The multivariate approach, a key component of our toolset, essentially identifies co-varying ion energies (ion types) and assigns them to discrete phases. The unique compositional differences in this case are subtle changes in the volatile self-assembled monolayer (VSAM) fragmentation pattern and the variation in surface H₂O and OH levels.

Multivariate analysis of the TOF-SIMS data identified the composition of specific lateral-force microscopy (LFM)

The aging processes of chemical and physical materials can significantly degrade the long-term performance and reliability of dormant microsystems. ...Sandia is developing analytical characterization methodologies for identifying the chemical constituents of packaged microsystem environments, and test structures for proving these analytical techniques.

features like the hydrous silica particulates, and organics as residual photoresist from the patterning process.

We developed and demonstrated methods for sampling and analyzing gases inside MEMS devices to be repeatable for packages having internal volumes of at least 3 mL. The gases analyzed include hydrogen, helium, methane, nitrogen, oxygen, argon, carbon monoxide, and carbon dioxide. Most of the devices measured appeared to be hermetic; however, we measured elevated levels of hydrogen (up to 10%) on several devices. The current sampling method, crushing, used to release the internal gases, is destructive and leaves little chance for subsequent surface analyses. However, we demonstrated a less-destructive method for opening these devices using laser radiation on several devices. Laser opening causes the lid to be separated from the substrate, leaving the device contents intact.

52702

Assembly of Ordered Electrooptical and Bioactive Materials and Composites

J. Liu, G. D. Bachand, C. J. Brinker, F. B. Van Swol, B. A. Simmons

The discovery of intrinsic metal-like conductivity in conjugated polymers represents a significant milestone in polymer chemistry and materials science, as recently recognized by the 2000 Nobel Prize Award in Chemistry. This project aims to address several key issues related to the performance and utility of conductive polymers. Sandia's objectives are to do the following:

(1) Develop new methods to assemble ordered conducting materials on multiple length scales. We will explore both self-assembly and directed nucleation and growth approaches to produce oriented and aligned polymer nanostructures and microstructures.

(2) Establish fundamental structure-property relationships of nanostructured conjugated polymers. We propose to investigate films in which conjugated polymers and polymer-nanocrystal composites are confined to ordered structures with one-dimensional (1-D), 2-D, and 3-D connectivity and are separated by either insulating or semiconducting walls. Such composites are ideal model systems in which to test and understand the role of nanostructuring in determining charge and energy-transport properties.

(3) Integrate the new materials/structures with microelectronic/microfluidic devices. This strategy holds the promise for inexpensive electronic/optical devices. We will also develop microarrays of such materials for quantitative and high-sensitivity detection of chemical and biological agents. The proposed research will not only contribute to our new strategy thrust in complex functional materials, but it will also have a positive impact on the Department of Energy's missions in energy and national security.

(1) Synthesis and self-assembly of tailored nanoparticles and composites.

- Semiconducting nanoparticles.* We utilized the templating environment provided by surfactant self-assembly to control the morphology, crystallinity, and physical properties of cadmium sulfide (CdS) semiconductor nanoparticles synthesized within these systems. Over the course of this work, we utilized water-in-oil microemulsions based on a technique developed by Simmons, *et al.*, using combinations of anionic and zwitterionic surfactants to synthesize CdS nanoparticles

The proposed research will not only contribute to our new strategy thrust in complex functional materials, but it will also have a positive impact on the Department of Energy's missions in energy and national security.

with directed control over particle size and crystal structure. We characterized these particles using x-ray diffraction (XRD), electron microscopy, and luminescent spectroscopy. These results indicate that the environment in which it was synthesized directly impacts the particle morphology and crystallinity.

- *Conjugated dithiol-interconnected gold (Au) nanocrystal/silica array.* We first formed ordered Au nanocrystal/silica arrays (~ 90 nm in thickness) on silicon (Si) wafer or glass substrates through self-assembly of water-soluble Au nanocrystal with silica.

(2) *Self-assembly of mesostructured conjugated polymer silica nanocomposites.*

- *Self-assembly of mesostructured conjugated polymerizable polyphenylenevinylene (PPV) silica nanocomposites.* We synthesized a new PPV containing surfactant (PPV-EG4). We fabricated PPV/silica nanocomposites with ordered mesostructure (lamellar or hexagonal) using PPV-EG4 as both structure-directing agents and monomers in the evaporation-induced self-assembly (EISA) process. The preliminary XRD and transmission-electron microscopy (TEM) results showed that higher humidity will increase the d-spacing of the PPV-EG4/silica lamellar/hexagonal mesophases. Further structure and properties study is ongoing.

- *Conjugated poly(2,5-thienylene ethylene) (PTE)/silica nanocomposites.* We also developed a robust, one-pot polymer-synthesis procedure to prepare PTE, which is particularly interesting because it has exhibited high quantum yields, lower bandgaps than benzene analogs, and stability to air and moisture, via the palladium-catalyzed polymerization of aryl diiodides with acetylene gas in aqueous media. We determined mesostructured PTE/silica nanocomposites by XRD, ultraviolet-visible (UV-vis), Fourier-transform infrared (FTIR), and TEM experiments. This novel approach provides a unique route to synthesize mesostructured conjugated polymer/inorganic nanocomposites.

(3) *Generalized approaches for conducting nanostructures.* We are developing a generalized approach to prepare oriented conducting nanostructures. We demonstrated that a general seeded method can be used to prepare large arrays of oriented titanium dioxide (TiO₂) nanowires and nanotubes. TiO₂ is one of the mostly widely used industrial materials, with applications ranging from functional filling materials for textiles, paints, paper, and cosmetics, UV blockers and smart surface coating, photovoltaic (PV) cells, batteries, adsorption separation,

We also developed a robust, one-pot polymer-synthesis procedure to prepare PTE, which is particularly interesting because it has exhibited high quantum yields, lower bandgaps than benzene analogs, and stability to air and moisture, via the palladium-catalyzed polymerization of aryl diiodides with acetylene gas in aqueous media....This novel approach provides a unique route to synthesize mesostructured conjugated polymer/inorganic nanocomposites.

sensing, optical emission, photonic crystals, to catalysis and photocatalysis. These titania nanostructures can also be prepared easily as conformal coatings on metal substrates. The oriented arrays of titania nanotubes, continuous films, and coatings should have potential for catalysis, filtration, sensing, PV cells, and effective electrochemical electrodes.

(4) *Novel self-assembled monolayers (SAMs) for selective and ultrasensitive chemical and biological sensing.* We extensively investigated optical fluorescence imaging and electrochemical sensing for chemical and biological detection. Both techniques require labeling of the targets and extensive sample preparation. We are interested in developing novel SAMs that can be integrated with nanostructured materials we developed under this project for direct electronic detection without labeling. To this end, we developed an electrochemically active SAM. The surface chemistry of the SAMs can be tailored to selectively bind chemical or biological agents. The binding state and nonbinding state showed distinctively different electrochemical response. The transduction mechanism can be a direct voltage output. No chemical labeling is required. The detection is, at minimum, semiquantitative. Using this kind of SAM, we demonstrated reliable, selective detection of toxic heavy metals, i.e., mercury (Hg), down to the 5 ppq (10^{-9} ppm) level, eight orders of magnitude lower than most commercial instruments. We further showed that we can perform selective protein detection down to the 0.01 ppq level (about 100 molecules/ml). This result is many orders of magnitude lower than the best results reported in the literature, and is indeed pushing toward single-molecule detection with a very simple instrument and without any labeling technique.

This result is many orders of magnitude lower than the best results reported in the literature, and is indeed pushing toward single-molecule detection with a very simple instrument and without any labeling technique.

Refereed

Liu, J., Y. Lin, L. Liang, J. A. Voigt, D. L. Huber, Z. R. Tian, E. N. Coker, B. McKenzie, and M. J. McDermott. 2003. Templateless assembly of molecularly aligned conductive polymer nanowires: A new approach for oriented nanostructures. *Chemistry-A European J.* **9**:605.

Simmons, B. A., S. Li, V. T. John, G. L. McPherson, A. Bose, W. Zhou, and J. He. 2003. Morphology of CdS nanocrystals synthesized in a mixed surfactant system. *Nano Letters* **2**:263.

52703

Advanced Packaging/Joining Technology for Microsystems

C. V. Robino, E. A. Holm, G. A. Knorovsky, J. R. Michael

Current microelectronics packaging technologies are thought inadequate for potential microsystems applications. The capability to join microelectromechanical systems (MEMS) components into complex three-dimensional (3-D) assemblies will enable flexible design options, and may be necessary for stockpile applications. Proof-of-concept experiments have identified two complementary new technologies—micron-scale high-energy-density (HED) fusion welding and focused-ion-beam deposition joining (FIBDJ)—that could jointly address these key microsystem needs. Sandia is identifying and quantifying the materials properties/process interactions that control microscale joinability in HED welding and FIBDJ.

At the micron scale, materials properties that dominate joining response differ significantly from those at macroscopic sizes. We are studying microscale HED welding with concurrent experimental and modeling approaches. We are characterizing laser and electron beams both spatially and temporally, and in terms of energy transfer to the work. Modeling shows that melt ejection may preclude joining at less than 100 μm beam diameters for typical laser pulses, but did not incorporate surface-tension effects. Model improvements are incorporating these effects and are using molecular dynamics (MD) simulations to provide surface tensions. We used Surface Evolver (SE) simulations to guide experiments and to determine whether surface tension can be used to aid joint coalescence. Expected results are quantitative mechanistic descriptions of microscale fusion welding and definitions of microscale weldability.

We are evaluating FIBDJ as an alternative approach. Experiments include characterization of operating parameters, precursor gas species and dynamics, joint geometry, energy transfer, and development of microstructure and properties. Kinetic Monte Carlo modeling is aiding interpretation of deposit evolution and its relation to FIBDJ processing. We use the models to derive quantitative mechanistic descriptions of micron- and submicron-size FIBDJ connections and to optimize processing parameters.

We expect residual stress and distortion to be key issues. We will address these at the latter stages of the project and will draw on experience gained from ongoing nuclear weapons (NW)–funded work at the submillimeter-size scale.

The capability to join microelectromechanical systems (MEMS) components into complex three-dimensional (3-D) assemblies will enable flexible design options, and may be necessary for stockpile applications. Proof-of-concept experiments have identified two complementary new technologies...that could jointly address these key microsystem needs. Sandia is identifying and quantifying the materials properties/process interactions that control microscale joinability in HED welding and FIBDJ.

We used SE to examine the conditions under which through-thickness fusion spot welds either heal or drill, and developed a processing diagram that describes the interplay between joint-aspect ratio and ejected fraction in producing coalesced joints. These calculations demonstrate the utility of SE for analyzing coalescence problems and can provide essential guidance needed for process schedule development at high surface-area-to-volume ratios. For example, the calculations indicate that for small amounts of ejected material (to about 35% of the volume for through-thickness welds with a depth-to-radius ratio of one), the weld heals, creating a concave but continuous surface on both sides. However, beyond some critical ejection fraction, the drilled hole not only persists but may even enlarge, leaving a permanent hole.

We installed a scanning-electron microscope (SEM) and are converting it to an electron-beam welding station. We conducted initial characterization of beam characteristics and performance using carbon-film ablation experiments. We identified and initiated more rigorous methods for spatial and energy characterization of the beam. We also accomplished preliminary welds between 25–50 μm -diameter alloy wires. We further refined our previously developed melt/drill model for microlaser welds by consideration of the melt-pool resonance. Detailed comparison of theoretical thresholds with previously determined experimental thresholds indicates the importance of laser pulse length and temporal pulse shape in promoting melting rather than drilling in microwelds.

We designed and fabricated a silicon (Si) MEMS die that includes a variety of mechanical test samples, although fabrication schedules delayed our initial experiments in this area. The die includes provision for tensile, double shear, ball bond shear, torsion, distortion, and crack propagation tests. We experimentally explored operating parameter ranges for FIBDJ and developed procedures for bridging joint gaps as large as 2 μm . For some values of parameter space, the ion beam's effect is to remove material faster than it deposits, and for other values, the deposit becomes highly nonuniform. Longer pixel dwell times during deposition with the ion beam require a larger spacing between pixels (negative overlap). Dwell times as long as 0.4 μs /pulse resulted in sputtering of the substrate for overlaps smaller than a critical value. It appears that dwell times of 0.1–0.2 μs with an appropriate overlap can provide good deposits while maintaining acceptable deposition rates. This work also demonstrated the significant role of gas dynamics in the FIBDJ process, and additional experiments designed to

assess the effects of gas dynamics are planned. We initiated assessment of the composition, microstructure, and properties of FIBDJ deposits. This assessment shows that deposits made with gallium (Ga) ion sources and the standard platinum (Pt) organometallic precursor contain significant amounts of carbon and Ga. We initiated an effort to evaluate alternative deposition species that would provide a predominantly Pt deposit. These include a commercially available $\text{Pt}(\text{acac})_2$ sample that has very promising characteristics, as well as solvated Pt mesityl and neopentyl derivatives. We hope that development of efficient electron-beam deposition will alleviate the observed Ga contamination. Tensile strength measurements for micron-size Pt FIBDJ joints in Si yielded values in the range of 0.2–0.9 GPa, depending on flaw (porosity) density, and compare favorably with 2.3 GPa for the Si “base metal” and 0.13–0.165 GPa for bulk Pt. Low-temperature aging of the deposits resulted in appreciable hardening, although transmission-electron microscope (TEM) evaluations did not reveal significant microstructural changes.

Refereed

Semak, V. V., G. A. Knorovsky, and D. O. MacCallum. 2003. On the possibility of micro-welding with laser beams. *J. Physics D* **36** (17): 2170–74.

Other Communications

Hall, A. C., G. A. Knorovsky, R. A. Roach, and G. J. Shelmidine. 2002. Validating predictions of keyholing phenomena in laser weld models. Paper presented at the IMOG/JOWOG Joining Subgroup Meeting, December, Livermore, California.

Hall, A. C., G. A. Knorovsky, R. A. Roach, and G. J. Shelmidine. 2002. Validating Predictions of Keyholing Phenomena in Laser Weld Models. Sandia Technical Report SAND2002-3501, Sandia National Laboratories, Albuquerque, New Mexico.

Knorovsky, G. A., and D. O. MacCallum. 2003. Recoil force measurements during pulsed Nd:YAG laser spot welds. *ICALEO 2003* CD-ROM (October, Jacksonville, Florida).

Knorovsky, G. A., D. O. MacCallum, A. C. Hall, and G. J. Shelmidine. 2002. Some diagnostic techniques for characterization of keyhole mode laser welds. Paper presented at the IMOG/JOWOG Joining Subgroup Meeting, December, Livermore, California.

Knorovsky, G. A., V. V. Semak, and D. O. MacCallum. 2002. Fusion zone behavior in micron-size laser welds. Paper presented at the IMOG/JOWOG Joining Subgroup Meeting, December, Livermore, California.

MacCallum, D. O., and G. A. Knorovsky. 2002. Recent work in characterization of laser beams. Paper presented at the IMOG/JOWOG Joining Subgroup Meeting, December, Livermore, California.

MacCallum, D. O., and G. A. Knorovsky. 2002. Spot size measurements for ultrasmall laser welds. *Proc. ICALEO 2002* (October, Scottsdale, Arizona): CD-ROM.

Shriempf, J. T., V. V. Semak, G. A. Knorovsky, and D. O. MacCallum. 2003. Application of melt ejection criterion in simulation of micromachining with lasers. *Proc. SPIE LASE 2003* **24977** (January, San Jose, California): CD-ROM.

52705

Magnetostrictive Elastomers for Actuators and Sensors

D. L. Huber, R. A. Anderson, J. E. Martin

A need exists for soft actuators that have a much larger response than piezoelectrics and that can respond in microseconds. Applications include artificial muscles in robots and stress/strain sensors based on permittivity or permeability changes. Sandia showed theoretically that large magnetostrictive effects can be obtained from composites of magnetic nanoparticles in an elastomer, if the nanoparticles have been preorganized into chainlike agglomerates using magnetic fields. Such magnetostrictive elastomers (MEs) have a magnetic permeability that increases rapidly with compression, and thus contract in a magnetic field, providing the particles are spaced by a soft matrix. This effect should be especially large for nanoparticles, where calculations show that the stresses should be comparable to that of human muscle. "Latched" MEs could also be made with particles having large magnetic remanence. A short magnetic pulse would magnetize the particles, causing permanent composite contraction without further power consumption, until an opposing coercive pulse removes the magnetization, releasing the contraction. One challenge in realizing MEs is preventing contact between magnetic nanoparticles during chaining. The most effective method of precoating the nanoparticles with a thin layer of low-modulus elastomer is through a surface-initiated polymerization, wherein an initiating group covalently linked to the surface is used to grow polymers in situ, forming a defect-free coating. MEs should have wide application as large-strain actuators, and as soft sensors for robotic fingertips. We expect strains that are 10x–100x those of piezoelectrics, and stress-response times limited only by the inductance time of the coil.

We constructed an optical cantilever magnetostriction measurement apparatus having a strain resolution of 1 ppm and used it to show that the magnetostriction of MEs is dependent on the square of the applied field, as predicted. We developed large-effect MEs based on micron-size carbonyl iron (Fe) particles structured into chains by a magnetic field, and quantified the extent to which demagnetizing fields reduce the measured magnetostriction. In controlled swelling experiments, we discovered that the magnetostriction increases linearly with the initial ME strain, which is a surprising finding. We are in the beginning stages of developing a model to explain this result.

A need exists for soft actuators that have a much larger response than piezoelectrics and that can respond in microseconds. Applications include artificial muscles in robots and stress/strain sensors based on permittivity or permeability changes. Sandia showed theoretically that large magnetostrictive effects can be obtained from composites of magnetic nanoparticles in an elastomer, if the nanoparticles have been preorganized into chainlike agglomerates using magnetic fields.... We expect strains that are 10x–100x those of piezoelectrics, and stress-response times limited only by the inductance time of the coil.

We developed a synthesis of high-susceptibility Fe nanoparticles using a novel surfactant-solvent system. These superparamagnetic particles have saturation magnetizations as high as 80% of bulk Fe, and particle susceptibilities of as much as 34 (meter-kilogram-second [mks] units, at cryogenic temperatures), far exceeding the classical limit of 3 for multidomain particles. We produced oxygen-barrier coatings on Fe nanoparticles by slowly reducing a gold (Au) salt in the presence of Fe nanoparticles. The Au successfully coated the Fe particles, and the coatings prevent any noticeable oxidation. Unfortunately, the Au coating destroyed the magnetic properties of the nanoparticles, leaving the nanoparticles only weakly magnetic and impossible to structure. For this reason, inorganic oxide barriers will likely be abandoned in favor of organic oxygen barriers.

Refereed

Huber, D. L., E. L. Venturini, J. E. Martin, P. P. Provencio, and R. J. Patel. 2003. Synthesis of highly magnetic iron nanoparticles suitable for field-structuring using a beta-diketone surfactant. *J. Magnetism and Magnetic Materials*, accepted.

Other Communications

Huber, D. L., J. E. Martin, E. L. Venturini, and P. P. Provencio. 2003. Preparation and structuring of iron nanoparticles. Paper presented at the American Chemical Society Meeting, September, New York, New York.

58907

Active Photonic Nanostructures

M. B. Sinclair, N. S. Bell, G. S. Subramanian, T. J. Boyle, J. C. Barbour, M. H. Crawford, S. Y. Lin, P. G. Clem, J. G. Fleming

Photonic crystals (PhCs) are periodically modulated dielectric structures that alter the flow of electromagnetic energy in many profound and potentially useful ways. Photonic bandgaps (PBGs), transmission resonances, restricted or enhanced densities of state, and modified spontaneous emission rates are all features of photonic lattices. However, these structures are entirely passive components; there are no means to alter, turn on, turn off, or modulate the unique photonic properties of these structures. Sandia's goal in this project is to integrate these passive PhC structures with active materials to provide "active" functions such as optical amplification, lasing, light switching and steering, optical logic, chemical sensing, etc. In addition to greatly expanded functionality of PhC structures, incorporation of active materials will offer new opportunities for the investigation of the novel physics arising from the strong modification of the photonic density of states and photonic band structures as they impact electron-photon interactions. We are exploring a number of approaches to the "activation" of PhCs, including fabricating the PhCs from active materials such as light-emitting materials, nonlinear optical materials, piezoelectric, or electromechanical materials. Fabrication efforts include both top-down lithographic approaches and bottom-up self-assembly methods. Another approach involves doping of passive PhC structures such as high-quality (Q) resonators with optically active materials such as quantum dots (QDs) or rare-earth ions. Yet another approach involves integrating the PhCs with active layers of light-emitting, piezoelectric, or electromechanical materials. In addition, we are investigating energy-transfer processes for possible use as a means to couple energy into and out of the PhC structures. This project is a collaboration between Sandia and Los Alamos Labs and draws upon the demonstrated strengths of these institutions in PhC structures, colloidal QDs, energy transfer in composite nanomaterials, nanomechanics, and self-assembly.

We fabricated two dimensional (2-D) PhCs containing high- Q -factor microcavities. These photonic microcavities are key components for many strategies directed toward the integration of active materials such as light-emitting QDs, electrooptic ceramics, or electromechanical materials. We measured Q

Sandia's goal in this project is to integrate these passive PhC structures with active materials to provide "active" functions such as optical amplification, lasing, light switching and steering, optical logic, chemical sensing, etc. In addition to greatly expanded functionality of PhC structures, incorporation of active materials will offer new opportunities for the investigation of the novel physics arising from the strong modification of the photonic density of states and photonic band structures as they impact electron-photon interactions.

factors approaching ~ 1600 in waveguide geometries. We also fabricated synthetic opal structures containing large concentrations of high-Q colloidal QDs for lasing and nonlinear optical switching. We also fabricated synthetic opal structures using self-assembly of polystyrene nanospheres that we intend to infiltrate with high-refractive-index, low-loss materials using sol-gel or electrodeposition methods. We demonstrated that fabricating a 2-D photonic-lattice structure on the upper surface of the diode can drastically modify the overall light-extraction efficiency. We successfully patterned substrates with 200 nm and 400 nm lines and spaces using nanocontact printing, which enables rapid, physical patterning of features on surfaces without e-beam lithography. We can use nanocontact printing to pattern optically active nanorods of zinc oxide (ZnO) arrays of metal nanoparticles onto 100 nm x 1 cm waveguide lines and to template opal assembly. In the materials-synthesis arena, we developed new solution-based synthetic routes to the production of metal and semiconductor colloidal nanoparticles. We can produce both spherical and rod-like particles.

We demonstrated that fabricating a 2-D photonic-lattice structure on the upper surface of the diode can drastically modify the overall light-extraction efficiency. We successfully patterned substrates with 200 nm and 400 nm lines and spaces using nanocontact printing, which enables rapid, physical patterning of features on surfaces without e-beam lithography.

Refereed

Boyle, T. J., M. A. Rodriguez, D. Ingersoll, H. Y. Fan, D. M. Pedrotty, and S. C. Vick. 2003. Single-source lithium cobalt double alkoxides for nanoparticles and thin films of LiCoO_2 . *Chemistry of Materials*, in press.

Bunge, S. D., K. M. Krueger, T. J. Boyle, M. A. Rodriguez, T. J. Headley, and V. L. Colvin. 2003. Growth and morphology of cadmium chalcogenides: The synthesis of nanorods, tetrapods, and spheres from CdO and $\text{Cd}(\text{O}_2\text{CCH}_3)_2$. *J. Materials Chemistry* **13**:1705.

Bunge, S. D., T. J. Boyle, and T. J. Headley. 2003. Synthesis of coinage-metal nanoparticles from mesityl precursors. *Nano Letters* **3**:901.

Subramanian, G. S., S. Y. Lin, J. R. Wendt, and J. M. Rivera. 2003. Tuning the microcavity resonant wavelength in 2-D photonic crystal by modifying cavity geometry. *Applied Physics Letters*, in press.

Pulsed Power Sciences

The Pulsed Power Sciences investment area researches concepts and technologies for the next generation of pulsed-power systems and high-energy-density science. Emphasis is placed on applications critical to nuclear weapons and national security. Our mission is to support experimental and computational capabilities for application to stockpile stewardship, emerging threats, basic science, industrial competitiveness, and future energy production. Pulsed-power research includes all aspects of pulsed-power technology, electromagnetics (EMs), high-yield and inertial fusion, high-energy petawatt lasers, high-magnetic-field pressures, and applications of pulsed-power systems to dynamic materials creation and characterization.

The next-generation driver for advanced pulsed-power accelerators, Z-pinch, weapons effects, or radiography could be greatly improved and simplified by the use of solid-state switches coupled to a very fast prime power stage. *Solid-State Switch for Advanced Pulsed Power* seeks to build and demonstrate such a high-current switch based on laser-triggered photoconductive semiconductor switches. Particular emphasis was placed on semiconductor trigger lasers for the photoconductive

semiconductor switches, as efficient triggering improves synchronization and lifetime and reduces the overall switching-system size and cost. One patent disclosure and one patent application have been filed.

28769

Z-Pinch Power-Plant System Development

C. W. Morrow, K. W. Struve, G. L. Benavides

The Z-pinch power plant (ZP-3 or ZPPP) is the first concept to use the results at Sandia's Z accelerator in a power-plant application. Assuming high-yield fusion pulses of 1 to 20 GJ per shot at a rate of 0.1 Hz, we conceived a unique shock- and energy-absorbing system to contain the energy. The concept under investigation answers the need for system standoff from the fusion reaction by using a replaceable mechanical cartridge that is manufactured in an on-site factory. We conducted system studies on integrated blanket design for absorbing the fusion energy, manufacturing cartridges of all recycled materials, and installing the cartridge to maintain a reasonable duty cycle. An effective system design for ZP-3 requires an integrated blanket that can (1) shield the permanent structures from the high-energy neutron flux and the strong shock wave, (2) breed tritium (T), and (3) in the process absorb the released fusion energy. The generation of this energy requires a fusion fuel cartridge to couple the repetitive pulsed power to a replaceable load using a recyclable transmission line (RTL).

Sandia's Z-pinch technology has led to the efficient generation of x-rays. Using high-current pulses from pulsed-power technology, this technology compresses high-density plasma to produce x-rays of an energy and intensity sufficient to indirectly ignite a fusion capsule. Research on Sandia's Z accelerator progressed enough to begin examining the application of Z-pinch technology to potential commercial fusion projects.

In 2000, Sandia funded two three-year projects to explore the application of Z-pinch technology to the production of electrical power. One project investigated the physics and theoretical development needed to achieve fusion ignition. The ZP-3 described in this system description results from the activities of another project. This project is the first realization of a Z-pinch power application. The project included one conceptual design taken far enough to identify technical and programmatic issues.

Our initial conceptual design of a fusion power plant is promising. It appears that, with optimization, the plant can be economically competitive. Because it generates its own fuel, the power plant reduces U.S. dependency on foreign sources. Operational waste is minimal, as is the final decommissioning waste. Neither waste stream contains long-term radioactivity. The concept provides energy self-sufficiency and is inherently nonproliferating. A ZP-3 by its nature is inherently safe.

Our initial conceptual design of a fusion power plant is promising. It appears that, with optimization, the plant can be economically competitive. Because it generates its own fuel, the power plant reduces U.S. dependency on foreign sources.

Perhaps most importantly, while extensive research and development will be needed to bring it to fruition, a ZP-3 project is technically feasible today.

This project included participants from four major universities and from numerous Sandia departments. Each participant brought specific skills to the project. The objective of the first year was to define a concept of a ZP-3 that used the latent knowledge of the diverse team. In the second year, the multidisciplinary/multiorganizational team evaluated the design and identified technical issues. In the third year, we continued the evaluation studies and developed an outline of a more extensive development program. Limited funding limited our ability to optimize the design. Thus, we evaluated the concept for general issues rather than make detailed refinements to the design. Potential benefits over other inertial-fusion-energy (IFE) designs are numerous. Some of the benefits of our conceptual design are as follows:

- A ZPPP would reduce U.S. dependency on foreign energy sources. The fusion process uses deuterium (D) and T as fuel. D is extracted from seawater. The D/T/lithium (Li) combination generates more T than it uses.
- The design eliminates spatial standoff requirements to protect final driver-conditioning elements (focusing lenses, mirrors, etc.) used in other IFE designs.
- While Sandia benefits from future unscheduled National Ignition Facility (NIF) experiments, this concept relies on the demonstrated ability of Z-pinch technology to achieve compression using x-rays.
- Using a linear transmission driver (LTD), pulse-generator capital cost should be below \$20 per joule installed. This allows larger fuel capsules with higher energy yield and shot frequencies 2 orders of magnitude lower than other IFE concepts (0.1 Hz).
- Instead of multiple lasers, ignition comes about through one high-energy pulse down an RTL designed for destruction by the fusion reaction.
- Instead of having to protect final driver-conditioning elements, we destroy them. The structural simplicity of the RTL allows this.
- Instead of requiring a clean laminar-flow regime, this concept works best with chaotic mixing of FLiBe (mixture of fluorine, lithium, and beryllium) in the detonation chamber. This removes the need for a high-vacuum environment.
- The use of a large vessel behind an FLiBe first wall means structural components are relatively free of neutron damage. They will survive 30–40 yrs of operation.

- The RTL concept requires the fabrication of 31–32 million transmission lines per year for a 1 GW plant. We investigated the feasibility and economics of such a plant.

Refereed

Rochau, G. E., C. W. Morrow, and P. J. Pankuch. 2003. A concept for containing inertial fusion energy pulses in a Z-pinch-driven power plant. *J. Fusion Science and Technology* **43**:456–67.

Rochau, G. E., C. W. Morrow, C. L. Olson, P. J. Pankuch, H. Tran, R. Lumin, and D. Kammer. 2002. An IFE power plant using Z-pinch indirect drive. Paper presented at the American Nuclear Society 2002 Winter Meeting, 19 November, San Diego, California.

Rochau, G. E., G. L. Benavides, M. S. Derzon, C. L. Olson, *et al.* 2001. ZP-3, a power plant utilizing Z-pinch technology. *Inertial Fusion Sciences Applications 2001* (September, Kyoto, Japan): 706–11.

28770

Recyclable Transmission Line Concept for Z-Pinch IFE

S. A. Slutz, G. E. Rochau, W. A. Stygar, C. L. Olson, R. A. Vesey, K. R. Cochrane, C. W. Morrow

The recyclable transmission line (RTL) concept for Z-pinch inertial fusion energy (IFE) provides the basis for a rep-rated Z-pinch power plant. High yield from Z-pinch-driven inertial confinement fusion (ICF) targets is a goal of the Defense Programs Sandia Z Program. A major program to develop everything else that is needed to produce a rep-rated Z-pinch power plant is just starting; the primary physics issues are addressed in this project. The basic concept is to construct the RTL out of a reactor coolant material (such as FLiBe, a mixture of fluorine, lithium, and beryllium), or a material that is immiscible in the coolant (such as low-activation ferritic steel), so that the material can be recycled after each shot and recast or restamped to make another RTL for a subsequent shot. We designed this project to study RTL electrical turn-on, RTL electrical conductivity characteristics, RTL minimum mass limits, Z-pinch-driven high-yield targets for Z-pinch RTL IFE, RTL shrapnel formation, and related physics development issues for the RTL concept. We will perform experiments on the Saturn accelerator at the 10 MA level. This work complements the related research on Z-pinch power-plant system development.

Our accomplishments validate the RTL concept for Z-pinch-driven IFE. Experiments on Saturn at the 10 MA level investigated the electrical turn-on of several candidate RTL materials and showed that all materials tested had excellent turn-on characteristics at electrical stress levels corresponding to full reactor parameters. Further tests on Saturn showed that a minimum mass for an RTL with high-efficiency electrical conductivity could be about 50 kg (substantially less than the 5-ton transmission line on Z). Structural calculations for this RTL show that the chamber pressure must be no more than about 10–20 Torr (a modest requirement) to prevent buckling of the outer conductor. Target simulations led to dynamic hohlraum targets that have fusion yields in the 1–4 GJ range (as is needed for Z-pinch IFE). Recent simulations studied the melting and shrapnel formation that the RTL undergoes after the blast. All of the results of this project support the conclusion that the RTL concept is a viable approach to Z-pinch IFE, and that a substantial program to develop this IFE approach is warranted.

Recent simulations studied the melting and shrapnel formation that the RTL undergoes after the blast. All of the results of this project support the conclusion that the RTL concept is a viable approach to Z-pinch IFE, and that a substantial program to develop this IFE approach is warranted.

Refereed

Slutz, S. A., C. L. Olson, and P. F. Peterson. 2003. Low-mass recyclable transmission lines for Z-pinch-driven inertial fusion. *Physics of Plasmas* **10**:429–37.

28771

Suppression of Electron Emission from Conductors

D. J. Johnson, W. E. Fowler, W. A. Stygar, K. W. Struve, H. C. Ives, III

This project consisted of testing surface-treatment processes for stainless steel (SS) and aluminum (Al) for the purpose of improving the high-voltage (HV) holdoff of these materials. Applications are the vacuum insulator-grading rings and self-magnetically insulated vacuum transmission line on the ZR (Z refurbishment) upgrade machine and other pulsed-power applications such as flash radiograph machines. Some of the treatments Sandia tested for SS include different-quality surface finishes; five pulsed E-beam surface treatments (EBESTs) supplied by the Institute of High-Current Electronics (IHCE), Tømsk, Russia; and chromium-oxide layers applied at Sandia. Treatments for Al were surface quality and a variety of dielectric coatings such as anodization and wipe-on polymers.

It was difficult to get precise breakdown thresholds for the treatments tested because the thresholds are sensitive to cleaning and voltage-application protocols. With cleaning in a filtered-air environment, we observed the following: All of the EBEST types tested gave an HV hold-off factor of 2 better than typical machined surfaces and similar to mirror-finish SS. We noted this for EBEST types with a factor of 100 variation in the dielectric-inclusion density that we expected to effect breakdown. Also, the EBEST surfaces retained good holdoff after arc damage if debris were removed. Anodized coatings on Al also give a factor-of-2 improvement in HV holdoff. However, anodized Al loses this improvement when the damage is severe. Chromium oxide on SS shows a 40% and 20% improvement in holdoff before and after damage from many arcs. Finally, we observed that the hold-off E-field for bare metal surfaces decreased as the inverse square root of the gap. This has been observed by previous studies with much longer pulses and has been attributed to the acceleration of loosely bound particles from the anode to the cathode that form cathode plasma. This scenario seems unlikely here because the 150 ns pulses used are too short.

The importance of cleaning protocol to attain optimum HV holdoff with bare-metal electrodes became clear at the end of the previous project year. Therefore, we designed and installed a filtered clean-air system around our HV test stand. This system used a high-efficiency particulate air (HEPA) filter and fan that supplied filtered air into a plastic tent over the

With cleaning in a filtered-air environment, we observed the following: All of the EBEST types tested gave an HV hold-off factor of 2 better than typical machined surfaces and similar to mirror-finish SS. ...Anodized coatings on Al also give a factor-of-2 improvement in HV holdoff.

equipment. This system gave an air purity of $\sim 100/\text{m}^2$ particles with size $> 0.5 \mu\text{m}$. Cleaning metal-surface electrodes with acetone and Kimwipes in the filtered air gave a 30% improvement in HV holdoff. This also reduced, but did not eliminate, the necessity for electrical conditioning by incrementally increasing the pulsed voltages.

We tested anodized coatings on 15 cm-diameter Al electrodes before and after the filtered-air system was operational. The coatings were on smooth- and rough-machined Al, with and without an etch to improve bonding. New anodized coatings gave holdoffs of $\sim 1.4 \text{ MV/cm}$, which was a factor of 2 higher than bare Al. Unfortunately, holdoff dropped to $\sim 0.7 \text{ MV/cm}$ when the coatings were damaged from breakdowns. We also acquired data with a polymer coating (EVO 191) mixed with diffusion pump oil that has common use in pulsed-power applications. Local application of the coating to the arc marks eliminated most reoccurrences, and an entire surface coating gave a holdoff of $\sim 0.9 \text{ MV/cm}$.

We received 12 cm-diameter EBEST electrodes from IHCE and tested them with 2.2 mm-wide gaps. The electrodes were 304L and 316L rod stock, and 304L plate stock SS. We gave the 304L plate hydrogen-vacuum-furnace-fired (HVFF) + EBEST and EBEST + titanium ion implantation. Evaluation of the surfaces showed the EBEST 304L rod electrodes had ~ 10 dielectric-inclusion craters/ mm^2 . These craters occur when the inclusions are evaporated during the EBEST process. The EBEST+ HVFF electrodes were the best-quality surfaces with only ~ 0.1 crater/ mm^2 . The results showed holdoff of $\sim 1.05 \text{ MV/cm}$ for all five EBESTs independent of crater density and roughness. This differed from previous preliminary tests with 8 cm-diameter EBEST electrodes that showed better holdoff for smoother surfaces with fewer craters. We attribute the consistent results for the 12 cm electrodes to improved surface cleanliness achieved in the filtered-air environment.

The high holdoffs for EBEST SS and anodized Al made it necessary to test at higher voltages. We built a linear induction voltage adder (LIVA) to raise the maximum voltage at the test gap from 265 to 500 kV. This system used a metglass core to add the voltage from parallel cables from our HV pulser. We tested the LIVA, made upgrades to the HV support hardware in the vacuum chamber, and then performed the first electrode tests. We achieved breakdowns with anodized Al with up to $\sim 3.8 \text{ mm}$ gaps. Tests showed the same hold-off E-field for 2 and 3.8 mm gaps within the statistical spread of the data. We also tested chromium-oxide-coated SS and saw holdoff of $\sim 0.9 \text{ MV/cm}$, which was $\sim 30\%$ higher than bare SS.

A test series for machined-surface SS using 2.4 mm gaps showed the holdoff dropping from 1 to 0.7 MV/cm as radius (Ra) increased from 0.05 to 0.5 μm . However, Al surfaces with Ra = 0.08, 0.7, and 3.2 μm gave the same holdoff. Tests using the LIVIA with EBEST SS gave a hold-off E-field that dropped as the inverse square root of the gap for gaps varying from 2.2 to 7.5 mm. Later tests with bare-machined and polished SS and Al gave similar decreases with larger gaps.

Refereed

Johnson, D. J., H. C. Ives, M. E. Savage, and W. A. Stygar. 2003. High-voltage hold-off of large-surface-area metal electrodes with dielectric surface layers. *Proc. 14th IEEE International Pulsed Power Conference* (June, Dallas, Texas).

28772

Solid-State Switch for Advanced Pulsed Power

F. J. Zutavern, M. W. O'Malley, A. Mar

The purpose of this project was to test the feasibility of switching large capacitor banks with low-inductance photoconductive semiconductor switches (PCSSs). These switches could eliminate many intermediate storage components of large pulsed-power systems, achieving reductions in cost and space. Sandia's plan was to demonstrate the capability to discharge 80 nF of capacitance charged to 200 kV through PCSSs delivering ~ 20 kA to a load in 100 ns. This capacitance consisted of eight 40 nF, 100 kV, 25 nH capacitors that would be switched with optically isolated, high-gain PCSSs switching two capacitors in series by four capacitors in parallel.

We first determined the number of switches that would be required to stand off 200 kV and conduct 20 kA. High-gain PCSSs always carry current in filaments that must be precisely controlled to achieve reasonable switch lifetimes. We used semiconductor trigger lasers to control the timing and location of the filaments. Our tests with single PCSSs demonstrated that each capacitor requires six 7.5 x 7.5 mm² gallium arsenide (GaAs) switches and six 16-element semiconductor lasers (96 filaments/switch at ~ 100 A per filament, giving a lifetime greater than 10,000 pulses).

Next, we used the single PCSS results to model the current and voltage that would be produced by combining these components and to show that it would meet the project requirements. We next performed switching tests with PCSSs conducting four and eight filaments. These demonstrated that our system requirements could be met. However, our biggest problem turned out to be the procurement of reliable multi-element semiconductor lasers. Although we tried many sources, none could produce lasers that would consistently give reliable triggers. We proposed an alternative trigger laser based on vertical-cavity surface-emitting laser (VCSEL) technology, but that is a new research project. The conclusion is that although the concept of PCSSs is feasible, until we can obtain reliable multi-element trigger lasers, PCSS projects should be limited to lower currents where fewer filaments are required.

We completed the following tasks for this project:

(1) We assembled and tested a high-voltage test-bed to test PCSS-discharging capacitors over a range of 50–200 kV and

A new type of semiconductor laser (top left), emission pattern (top right), and a linear VCSEL (lower left) are being developed to trigger high-power PCSSs instead of conventional edge-emitting laser (EEL) stacks (lower middle). The current and voltage capability of a PCSS is vastly improved by triggering multiple current filaments (lower right) with arrays of straight-line lasers. Stacking conventional EELs is an expensive, low-yield process. Arrays of linear VCSELs that match the size and shape of the PCSS can be produced completely monolithically.

The conclusion is that although the concept of PCSSs is feasible, until we can obtain reliable multi-element trigger lasers, PCSS projects should be limited to lower currents where fewer filaments are required.

0.1–20 kA in a 100 ns-wide nearly critically damped pulse. This required a variable configuration of capacitors, inductors, and loads.

(2) We fabricated PCSSs to determine the dimensions for optimum switching and hold-off properties. We drew lithographic masks to diffuse donors into the substrate and evaporate contacts for switches with dimensions of (1.5, 0.75, 0.5 cm long) x (2.0, 1.0, 0.75 cm wide).

(3) We procured and tested a large variety of trigger lasers, including stacked edge-emitting lasers and individual edge-emitting chips.

(4) We designed and fabricated linear VCSELs at Sandia specifically for triggering linear filaments in PCSSs.

(5) We tested new and existing PCSSs in series and in parallel and with one to eight current filaments per switch up to 120 kV and 1 kA.

Other Communications

Zutavern, F. J., J. C. Armijo, S. M. Cameron, G. J. Denison, J. M. Lehr, T. S. Luk, A. Mar, M. W. O'Malley, L. D. Roose, and J. Van Rudd. 2003. Optically activated switches for low-jitter pulsed-power applications. *Proc. International Pulsed Power Conference 2003* (June, Dallas, Texas).

39669

Determination of Microstructural Properties with Isentropic Compression

M. D. Furnish, R. J. Hickman, H. E. Fang, C. C. Henderson, J. Mason, T. R. Christenson, W. M. Trott, J. W. Podsednik

Of special promise for providing dynamic mesoscale response data is the line-imaging velocity interferometry system (VISAR), an instrument for providing spatially resolved velocity histories in dynamic experiments. Sandia prepared two line-imaging VISAR systems capable of spatial resolution in the 10–20 μm range, at the Z and STAR facilities. After validating both systems, we applied the instrument at STAR to selected experiments on a compressed-gas gun, chosen to provide initial data for several problems of interest, including (1) pore-collapse in copper (Cu) (70 μm -diameter hole in single-crystal Cu), and (2) response of a welded joint in dissimilar materials (tantalum [Ta], niobium [Nb]) to ramp loading relative to that of a compression joint. The instrument appears capable of resolving details such as the volume of a collapsing isolated pore. The preparation of other experiments, such as LIGA (the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding)—stamping mechanics, dynamic compression of highly porous Cu, and a larger-scale pore-collapse experiment, allowed the assessment of diffusion bonding as an alternative to glue bonding.

We designed and constructed two line-VISAR interferometers with $\sim 10 \mu\text{m}$ maximum spatial resolution. One is at the Z facility (9/10 screenbox), and one is at the STAR facility (gas-gun range). Both interferometers have the capability of user-selectable sensitivity (velocity-per-fringe settings), facilitated by a programmable stepper-motor positioning of the delay-leg mirror. We demonstrated the requisite resolution on two static Z tests, although unrelated issues prevented the actual measurement of shot waveforms at Z.

We constructed a series of well-controlled tests to use the high-resolution line-imaging VISAR at STAR. These included carefully controlled assessments of pore collapse in Cu, LIGA–stamping measurements, dynamic compression of highly porous Cu, and comparison of the dynamic failure of a Ta-Nb weld and a Ta-Nb glue joint. Due to a progressively more-intermittent functioning of the Imacon 500 streak camera in early qualification tests of the STAR system, we performed three of these tests on a similar VISAR system at the Explosives

Of special promise for providing dynamic mesoscale response data is the line-imaging velocity interferometry system (VISAR), an instrument for providing spatially resolved velocity histories in dynamic experiments.

Component Facility 2.5 in. gas gun. Some of the test results were limited due to the lower resolution of the existing Imacon camera system.

Among the tests executed, we found that the collapse volume of a pore can be estimated to within a factor of 2 with a quick examination of the fringe record. A more-formal analysis gave agreement to the 15% level. Fringe-intensity information may convey useful tilt information for these systems because of the long relay system and highly specular surfaces used. We monitored the distortion of surfaces adjacent to a failing weld and glue joint. Although the glue joint clearly broke, the behavior of the weld was more difficult to infer. It appears that material distortion was extensive near the weld joint.

We tested diffusion bonding, which is appropriate for some types of bonds, where glue bonds would result in excessive ramp time, wave heterogeneity, or other undesirable perturbations. Magnetic bonding or plating directly onto Isentropic Compression Experiment (ICE) panels is also a viable bonding scheme for certain types of experiments.

Refereed

Furnish, M. D., W. M. Trott, J. Mason, J. W. Podsednik, W. D. Reinhart, and C. A. Hall. 2003. Assessing mesoscale material response via high-resolution line-imaging VISAR. *Proc. APS Shock Compression of Condensed Matter-2003* (July, Portland, Oregon).

39670

Simulations of Intense Petawatt Laser Pulses with Dense Z-Pinch Plasmas

R. B. Campbell, J. S. DeGroot, D. R. Welch

Sandia proposes to use two codes—LSP (Large-Scale Plasma, a simulation code) and Sandia's QUICKSILVER—to develop a simulation capability for studying fast-igniter physics.

The Z machine experiment has become reknowned for attaining ultra-intense x-ray pulses, which can be used to obtain high densities. There is now considerable interest in using short laser pulses to study laser-plasma interactions in an as yet unexplored parameter regime. The implicit algorithms and hybrid physics in LSP should allow us to begin unique research into the interaction and transport physics of the fast particles generated by the laser beam–plasma interactions. They might also allow us to study the interaction of intense lasers with solid- or near-solid-density targets. The greatest innovation will come in extending the simulations to conditions beyond those already simulated by standard PIC (particle-in-cell) codes.

The specific knowledge areas that will benefit from these experiments include weapons physics, weapons effects, and basic light-matter interaction physics. In keeping with the Laboratories' paradigm of science-based stockpile stewardship, simulation must be an integral part of understanding these experiments.

We studied electron-beam collimation from graded material and vacuum gaps. This can be important for radiography and fast-ignition (FI) applications, both of which are anticipated in the PW (petawatt) upgrade of Z-Beamlet. We published an article in *Physics of Plasma* on the theory of this process.

We performed initial simulations of FI-hotspot plasmas and studied parasitic heating in the corona of FI hotspots. We submitted a paper to the *Inertial Fusion Sciences and Applications (IFSA) Proceedings* on this work.

We performed an initial comparison of simulations with experimental data from the GEKKO/PW system at Osaka University.

We examined ionization dynamics in dense matter and determined the role of the hot-electron species, as well as the detail necessary in an equation-of-state (EOS) model for the integrated simulations. We presented a paper on this work at the IFSA 2003 Conference.

The Z machine experiment has become reknowned for attaining ultra-intense x-ray pulses, which can be used to obtain high densities. There is now considerable interest in using short laser pulses to study laser-plasma interactions in an as yet unexplored parameter regime.

We upgraded the LSP conductivity model to include the Lee-Moore-Desjarlais (LMD) model with optional Thomas Fermi model for ion-charge state.

We tested the new implicit field-solver for application to the FI problem. We found the new solver to be faster, more robust, and able to tolerate longer time-steps.

We studied the effects of different conductivity, charge state, and idealized EOS models on fast-electron transport in an aluminum slab. We presented this work at the *IFSA 2003 Conference*.

We performed an initial examination of proton focusing from irradiated concave and spherical shell targets and identified possible limitations on proton focusing.

Refereed

Campbell, R. B., R. A. Vesey, S. A. Slutz, T. A. Mehlhorn, J. S. DeGroot, and D. R. Welch. 2003. Simulations of petawatt laser-generated electron beams in pre-compressed fast-ignition hot-spot plasmas. *Proc. 3rd Inertial Fusion Science and Applications (IFSA)* (5–12 September, Monterey, California).

Campbell, R. B., T. A. Mehlhorn, D. R. Welch, B. V. Oliver, and J. S. DeGroot. 2003. Collimation of petawatt laser-generated relativistic electron beams propagating through solid matter. *Physics of Plasmas* **10**:4169–72.

MacFarlane, J. J., I. E. Golovkin, P. R. Woodruff, D. R. Welch, B. V. Oliver, T. A. Mehlhorn, and R. B. Campbell. 2003. Simulation of the ionization dynamics of aluminum irradiated by intense short-pulse lasers. *Proc. 3rd Inertial Fusion Science and Applications (IFSA)* (5–12 September, Monterey, California).

Welch, D. R., B. V. Oliver, J. J. MacFarlane, R. B. Campbell, and T. A. Mehlhorn. 2003. Hybrid simulation of energetic electron-beam propagation in solid-density aluminum. *Proc. 3rd Inertial Fusion Science and Applications (IFSA)* (5–12 September, Monterey, California).

52737

Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating

P. K. Rambo, I. C. Smith, C. S. Ashley, B. D. Thurston, R. S. Broyles, W. A. Johnson, E. D. Branson, S. T. Reed, C. A. Valleau

A high-energy (< 3 kJ) petawatt laser at Sandia's Z-Beamlet facility could have applications toward fusion research, advanced radiography, and fundamental physics. Such a laser capability will require large-aperture high-damage-threshold gratings for use in pulse compression. Existing gold-coated gratings have 95% efficiency and damage at laser fluences above 0.5 J/cm^2 for 0.5 ps pulses, requiring meter-scale optics to reach the 1 kJ level. New multilayer dielectric gratings promise improved damage thresholds and efficiencies but are at a prototype stage, with scalability being a key question. Sol-gels exhibit high damage thresholds in the nanosecond regime, but little has been done to examine sol-gel behavior for shorter pulses. Similarly, sol-gel can have gratings written into it. We propose coating a high-damage-threshold mirror with sol-gel, which can be done up to the meter scale with a simple dip or meniscus coater. If the sol-gel is appropriately photosensitive, ultraviolet (UV) light with an interference pattern on it can be applied to the sol-gel to create a permanent periodic modulation to its index of refraction. Since the substrate is a mirror, this periodic structure will act as a double-pass transmission sol-gel grating for another incident wavelength, with the whole structure used as a reflection grating. Optimization of the key variables should allow high efficiency to be obtained in conjunction with high damage threshold, allowing the gratings to be used in a pulse compressor. This technique is a novel improvement over existing grating architectures that require large-aperture etching, a difficult task to achieve uniformly.

Movie showing patterned hydrophobic behavior.

Initial concept validation focused on two key elements in the development of the proposed sol-gel (or mirror-backed volume-phase) gratings: the design (modeling) and the achievable index modulations (chemistry).

Using commercial software, we modeled the grating performance. Results (assuming a modest refractive-index modulation of 0.16 based on volume-phase gratings in dichromated gelatin) showed a first-order diffraction efficiency of $> 98\%$ over a bandwidth capable of supporting < 100 fs pulses. We determined the corresponding thickness to be 2.6

This technique is a novel improvement over existing grating architectures that require large-aperture etching, a difficult task to achieve uniformly.

μm , which nears the region where coating uniformity should be acceptable. The corresponding acceptance angles about the Littrow angle were limited, but modest compressor modifications could accommodate this. Modeling further indicates that grating design benefits from higher index modulations and thinner grating layers, improving both bandwidth and acceptance angle.

Modeling also allowed initial laser-induced damage threshold (LIDT) issues to be investigated. We solved the nonlinear differential equation that describes short-pulse damage and benchmarked it against published results in bulk fused silica. Extrapolating this model to the lower-density situations associated with sol-gels and aerogels (taken to be 1/10 and 1/100 of normal fused silica density, respectively) showed an increased LIDT of about 10% and 20% at 0.5 ps for the assumed sol-gel and aerogel densities, respectively. In addition, we performed initial electric-field-enhancement modeling of grating structures on a high-efficiency design for a sol-gel grating. An electric-field map of the results for a single period shows a field enhancement near 2 inside the grating structure. The net result of such field-enhancement placement is either that one is driven again toward thin gratings and high-index modulations (to push the enhancement outside the grating structure), or that one takes advantage of the enhancement lying solely in the material (since bulk LIDTs exceed that found at interfaces).

In the chemistry aspect, we aimed for high-index modulation in thin, uniform, sol-gel coatings of a few microns in thickness. Because single-layer, crack-free sol-gel coatings are generally limited to $< 1.0 \mu\text{m}$, thick-film approaches (e.g., aerogels) must be considered for grating applications. Silica aerogel films with $> 95\%$ porosity and a refractive index of $n=1.05\text{--}1.11$ may be deposited at $> 1 \mu\text{m}$ thickness. We demonstrated that the porosity of the film may be exploited for infiltration with a high-refractive-index sol-gel material (e.g., zirconium dioxide [ZrO_2], titanium dioxide [TiO_2]) to achieve variations in refractive index. While aerogel films with TiO_2 ($n=2.2$) infiltration suggest that the pores may not be completely filled, ZrO_2 infiltration yields a refractive index of near 1.8 ($\Delta n = 0.76$), with scanning-electron microscope/energy dispersive analysis through x-ray (SEM/EDAX) confirming that a Zr signature is present throughout the complete thickness of the aerogel film.

In addition, we investigated methods to pattern the deposition of the high- n phase to form the grating by (1) selective dewetting of methyl-terminated regions of the aerogel

film into hydrophobic or hydrophilic regions (to direct subsequent high- n deposition) by UV/ozone treatment, or (2) incorporation of a silica sol, including a photosensitive molecule to form denser regions with higher n upon exposure to UV. We treated aerogel films with hexamethyldisilazane (HMDS) to replace surface OH groups with $-\text{CH}_3$. We used a UV/ozone apparatus on the unmasked areas of the HMDS-treated aerogel coating, rendering these areas hydrophobic. We achieved contact angles from 160 deg to 15 deg and could re-expose them to HMDS vapors to increase contact angles to near 150 deg, almost entirely restoring water-repelling tendencies. These results suggest that such patterning would allow subsequent infiltration of the high- n sols to be confined to particular regions of the film, as required to form a grating structure. The silica photoacid generator (PAG) system showed photoactivity upon UV exposure when the silica PAG was infiltrated into the aerogel. We qualitatively confirmed presence of the PAG within the aerogel film by incorporating a pH-sensitive indicator dye that shows the pH change caused by the PAG upon UV exposure.

Other Communications

Ashley, C. S., S. T. Reed, E. D. Branson, P. K. Rambo, and I. C. Smith. 2003. Aerogel composite diffraction gratings for high laser damage-threshold applications. Paper presented at the 7th International Symposium on Aerogels—ISA7, 2–5 November, Alexandria, Virginia.

52738

Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators

J. R. Woodworth, D. E. Bliss, D. L. Johnson, J. M. Elizondo-Decanini

Sandia seeks to determine the optimum parameters needed to reliably laser-trigger water switches in terawatt-class pulsed-power accelerators. Presently, water switches are operated in a self-break mode, with the associated jitter in time and amplitude. The large jitter of self-breaking water switches has forced use of gas switches as master timing elements in multimodule accelerators. These gas switches are expensive, fragile, and difficult to field-grade or to make work at all above 5 MV. Replacing these gas switches with low-jitter-triggered water switches will allow simpler, more robust accelerator designs that operate with higher field stresses and provide more energy to the load. In addition, triggering water switches in Z refurbishment (ZR) would allow improved timing between the power pulse and the petawatt laser, allowing the petawatt to be used in fast-ignition fusion experiments.

Laser triggering will initiate the streamer formation conditions at the electrode surface, provide an ionized path that behaves as an extension of the electrode, and provide trigger control and timing.

We discovered that modest amounts of green laser light can cause several-centimeter-long breakdown arcs in pure water. We also discovered that water in front of and behind the breakdown arc is highly vibrationally excited, which may effectively extend the length of water with reduced breakdown strength to over 30 cm. Since unfocused green laser light can also be transported long distances in pure water, eliminating the need for a gas-filled laser crossover tube, we are focusing our efforts on green laser triggering.

We demonstrated that we could form hard breakdown arcs in water by focusing the output from an ND:YAG (neodymium:yttrium aluminum garnet) laser at any of three wavelengths: 1060 nm, 532 nm, and 354 nm. Laser energy required to break down water with the three wavelengths was 2.7 mJ, 1 mJ, and 10 mJ for wavelengths of 1060 nm, 532 nm, and 355 nm, respectively. The breakdown thresholds were 2200 J/cm², 110 J/cm², and 1200 J/cm² at 1060, 532, and 355 nm, respectively. We were unable to form hard breakdown arcs in water with 266 nm light because of transient, laser-beam-induced index-of-refraction gradients that scattered the

These gas switches are expensive, fragile, and difficult to field-grade or to make work at all above 5 MV. Replacing these gas switches with low-jitter-triggered water switches will allow simpler, more robust accelerator designs that operate with higher field stresses and provide more energy to the load.

ultraviolet (UV) laser beam away from the focal point before an arc could form.

In addition to literature searching the transmission properties of water at 1064, 532, and 355 nm, we measured the transmission of water from Sandia's accelerator tanks at 266 nm, finding that the 1/e absorption length of light at this wavelength is about 0.6 m.

We completed and tested a system that will allow us to study laser-triggered water switching at pulsed voltages of 150 kV, but have not yet begun experiments.

Other Communications

Woodworth, J. R., and D. L. Johnson. 2003. Laser-triggered water switching. *Proc. 15th IEEE Pulsed Power Conference* **15** (June, Dallas, Texas): 345–48.

52739

Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions

J. P. Davis, J. J. Hoyt, S. M. Foiles

The behavior of materials under dynamic high-pressure conditions is directly relevant to stockpile stewardship and is of scientific interest. In particular, there is a programmatic need for improved understanding of liquid-solid phase-transition behavior. The purpose of this project is to study the freezing transition, and a possible liquid-liquid structural transformation, in tin (Sn) under compression. Sandia continued to improve a technique to subject molten metals to a ramped compression wave, which allows access to dynamic pressure-temperature conditions not attainable using traditional impact techniques. We analyzed preliminary experimental data to determine the presence or absence of solidification. Continuing work will investigate the equation of state (EOS) for Sn and the kinetics of the solidification process. We will develop continuum models to aid analysis of the experimental results. We completed extensive ab initio molecular dynamics (MD) calculations for liquid Sn at different pressures and temperatures. We are now using these data to develop empirical potentials that can be used for larger-scale MD simulations of solidification kinetics. We will also use these data to determine the EOS of liquid Sn as a function of pressure and temperature for development of a continuum model. We expect this work to develop future capability and expertise at Sandia in a novel area of materials dynamics characterization that is of high interest to stockpile stewardship, beyond the scope of existing programmatic work. The results will also improve the fundamental understanding of solidification processes, aiding both the prediction of material behavior under dynamic loading and the modeling of more traditional processes such as welding and soldering.

We performed first-principles MD simulations of Sn using the SOCORRO code. In particular, we obtained structure and properties results along the zero-Kelvin isotherm and the zero-pressure isobar and found excellent agreement with existing experimental data. We completed computations over a wide range of pressures and temperatures. We used the database of atomic forces and properties thus generated to investigate several possible empirical interatomic potentials. Though we found these potentials to be unsatisfactory for liquid Sn, work is

We expect this work to develop future capability and expertise at Sandia in a novel area of materials dynamics characterization that is of high interest to stockpile stewardship, beyond the scope of existing programmatic work. The results will also improve the fundamental understanding of solidification processes, aiding both the prediction of material behavior under dynamic loading and the modeling of more traditional processes such as welding and soldering.

continuing with more advanced potential functions to find one that is suitable for liquid Sn.

As part of our Stockpile Stewardship Campaign 2 activities, we executed several experiments on the Z accelerator to study isentropic compression of molten Sn. With some support from this project, improvements have been made to the experimental apparatus that result in higher-purity molten Sn samples and better repeatability of sample preparation. We completed preliminary analyses of experimental velocity measurements using an existing continuum model for multiphase Sn. This work included an investigation of temperature effects on interferometer window materials. Results from the new experiments with higher-purity Sn do not show any evidence of a liquid-liquid transition and suggest that the liquid-solid transition occurs more slowly and is delayed relative to earlier experiments with less-pure Sn. This result refocused out-year efforts for this project toward the effects of impurities on solidification dynamics. The present investigation also shows that the existing continuum model is not adequate for describing dynamic freezing in Sn.

With some support from this project, improvements have been made to the experimental apparatus that result in higher-purity molten Sn samples and better repeatability of sample preparation.

Other Communications

Davis, J. P., and D. B. Hayes. 2003. Isentropic compression experiments on dynamic solidification in tin. *Shock Compression of Condensed Matter—2003, Proc. 13th APS Topical Conference on Shock Compression of Condensed Matter* (20–25 July, Portland, Oregon).

Foiles, S. 2003. *Ab initio* molecular dynamics simulations of molten Sn. *Shock Compression of Condensed Matter—2003, Proc. 13th APS Topical Conference on Shock Compression of Condensed Matter* (20–25 July, Portland, Oregon).

Differentiating Technologies

The Differentiating Technologies investment area focuses on research activities that accelerate the development of novel sensing, microsystems, and cybersecurity technologies. Investments are being planned for advanced, remote infrared (IR) optical sensing; novel microchip designs for sensor networks; and advanced cybersecurity countermeasures. New materials are being investigated for IR sensing applications that will enable the realization of very high sensitivity and highly wavelength-specific detection schemes. In addition, researching and developing “adaptive countermeasures” has the potential to produce new methods of defeating cyber attacks.

Computer network security is vital to national security. *Adaptive Network Countermeasures* is developing methods to increase the security of computer networks. Most network attacks begin with accurate reconnaissance. Current network protocols provide information useful to attackers, including active network addresses, what services are running, and possibly enough information to deduce what operating systems are running on networked computers. This allows attacks to be efficiently tailored to specific computers. Sandia is developing network software that will provide attackers with information that suits our ends

rather than theirs. The project will develop software that will watch unused subnets and reply to attackers answering for all addresses and all ports. Then the project will study how such a system can identify and mislead or confuse an attacker.

38744

Adaptive Network Countermeasures

J. A. Vanrandwyk, J. A. Hutchins, T. J. Toole, E. D. Thomas

For most attackers, conducting accurate system or network reconnaissance is the critical first step of the attack process. If a defender can thwart an attacker's reconnaissance efforts, it will be considerably more difficult and time-consuming for that adversary to successfully attack the network.

Traditionally, protocol stack implementations (e.g., Transmission Control Protocol/Internet Protocol [TCP/IP]) provide, rather than limit, information to attackers. This includes providing information about what addresses on the network are active, what services are running on systems, and possibly enough information to deduce what operating systems are running on networked computers. With this information, an attacker can tailor a specific attack to a computer, thus not wasting time or risking detection of himself/herself by attempting attacks that may not succeed.

Some measures used to thwart reconnaissance activities have included perimeter defenses (e.g., firewalls and routers) to limit information available to attackers. Defenders have also used "honeypots" as a method to attract, then distract an attacker. These approaches leave large gaps in the scope of their protection.

If we can provide attackers with information that suits our ends rather than their ends, we can greatly increase the time and skill required to map our networks, computers, and available services.

If we can provide attackers with information that suits our ends rather than their ends, we can greatly increase the time and skill required to map our networks, computers, and available services.

ANC (adaptive network countermeasures) leverages established methods of anomaly detection and profiling to create a next-generation network countermeasure system. ANC has established its importance in cybersecurity infrastructure.

Sandia proposes a new area to examine: adaptive network countermeasures (ANC). We will develop software that a defender can use to watch unused subnets and reply to attackers answering for all addresses and all ports. Then we will study how such a system can identify, then mislead or confuse a widely used reconnaissance tool. Finally, we will simulate protocol stacks and applications to distract an attacker without offering the vulnerabilities found in real honeypot systems.

In our research we combined the common network security ideas of network countermeasures, automated response, and honeypots to create ANC. Our goal was threefold: to provide a comprehensive and robust network countermeasure system, to dynamically (in real time) detect and respond to malicious traffic directed to nonexistent and existent machines on our network, and to design and build an extensible architecture for conducting the aforementioned activities.

Our design, and thus our project, was split into two main parts: the countermeasures component (Honeyd Enabled Network Countermeasures [HENC], pronounced “Hank”), and the decision-making component (Athena). The two components were each designed to run on their own machines with a back channel for unidirectional communication. We chose Honeyd, a virtual honeypot software package, to act as the base for our countermeasure system. We made significant improvements and modifications to Honeyd and built an architecture around it to satisfy our countermeasure system’s requirements. Athena makes the ANC system adaptive by changing how it responds based on input from different modules. Athena accepts two different types of input: (1) from intrusion-detection system (IDS) modules and (2) from general information (GI) modules. When information from these two module sets is combined and correlated by Athena, Athena determines what countermeasures, if any, HENC will send.

We tested our system in several ways. First, we wrote a program to send Athena alerts of incoming network attacks as fast as it could, and Athena was able to handle the load without losing data. This showed us that the ANC system should be able to defend a network as large as that of a national laboratory. In addition, we tested the time between detecting an inbound attack and effecting countermeasures, and our system performed acceptably. This is important because network attacks can be lethal in a very short period of time. Finally, we tested our system on a production network to make sure that the ANC system would correctly identify malicious traffic and tag it for countermeasures with a very low false-positive rate. This

Sandia proposes a new area to examine: adaptive network countermeasures (ANC). We will develop software that a defender can use to watch unused subnets and reply to attackers answering for all addresses and all ports. Then we will study how such a system can identify, then mislead or confuse a widely used reconnaissance tool. Finally, we will simulate protocol stacks and applications to distract an attacker without offering the vulnerabilities found in real honeypot systems.

gives us the assurance that our system will defend the network without interfering with production use of the network.

The ANC system has proven to work well in our test environment and in limited production testing. We believe that a full-scale implementation of this system on a production network would produce significant results in repelling Internet attacks while not interfering with legitimate use of the network.

Our work demonstrates that we can provide a comprehensive and robust countermeasure system. The system responds quickly enough to be effective in repelling active attackers. Network datagrams generated by the system appear authentic and succeed in leading malicious users in the direction of our choosing.

The ANC system is able to dynamically (in real time) detect and respond to malicious traffic directed to nonexistent and existent machines. This behavior allows us to send countermeasures to protect a machine that is conducting typical business via the network without interfering with that legitimate communication.

The Athena portion of the ANC system has proven to be an intelligent system for detecting malicious behavior and acting on it dynamically. Athena can take information from several different sources, correlate that information to provide a threat assessment of a potential malicious user, and issue commands to the countermeasure system to act on that threat. We wrote the code modularly so that additional information sources can be added easily to the existing set. Athena's "brain" can be reprogrammed easily by modifying or rewriting its correlation () function.

HENC and Athena combine in the ANC system to provide a comprehensive, robust, and intelligent network countermeasure system.

The ANC system is able to dynamically (in real time) detect and respond to malicious traffic directed to nonexistent and existent machines. This behavior allows us to send countermeasures to protect a machine that is conducting typical business via the network without interfering with that legitimate communication....HENC and Athena combine in the ANC system to provide a comprehensive, robust, and intelligent network countermeasure system.

Other Communications

Van Randwyk, J. A. 2002. Position paper on active countermeasures for computer networks. HotOS IX: The 9th Workshop on Hot Topics in Operating Systems, submitted. SAND2002-8625C.

Van Randwyk, J. A. 2002. Position Paper on Active Countermeasures for Computer Networks. Sandia Technical Report SAND2003-8398, Sandia National Laboratories, Livermore, California.

41674

Microengine for Advanced Power Generation*B. L. Haroldsen, S. Liu, T. N. Raber, A. M. Morales, M. A. Hekmaty, J. H. Chen, A. N. Karpetis*

The utility of many small electronic devices is limited by the power supply. Sandia is developing a mesoscale Stirling engine capable of producing 10 to 20 W of electrical power using a hydrocarbon fuel. The engine is expected to provide an order-of-magnitude reduction in weight compared to standard lithium ion batteries. The project includes design and integration of a combustor and an engine. We are developing two engine prototypes. The first uses a cylindrical piston design fabricated with conventional machining processes. It has been assembled, and testing is under way. We fabricated the second prototype, with a rotary piston design, with SU8-based ultraviolet (UV) lithography and electroforming. The planar geometry of the rotary design is more compatible with the fabrication process, and it enhances heat transfer to the working gases. Although other engine designs perform better at macroscales, we believe the Stirling engine cycle is better suited to small-scale applications. The ideal Stirling cycle requires efficient heat transfer. Consequently, unlike other thermodynamic cycles, the high heat-transfer rates that are inherent with miniature devices are an advantage for the Stirling cycle. Furthermore, since the Stirling engine uses external combustion, the combustor and engine can be scaled and optimized semi-independently. Continuous combustion minimizes issues with flame initiation and propagation. It also allows us to consider a variety of techniques to promote combustion that would be difficult in a miniature internal combustion engine. We modeled and successfully tested a number of different combustor configurations with device scales down to 0.5 mm. We based the combustor design on the excess enthalpy concept with an internal catalyst. The project is producing important technical advances in microcombustion, miniature-engine design, microfabrication and metrology of metal and ceramic parts, and the application of advanced diagnostics at small scales.

- *Piston Stirling engine.* We assembled the first prototype engine and have started testing it. This engine used radially arranged cylinders and pistons connected to a central shaft connected to a commercial micromotor/generator. We fabricated the parts with conventional miniature machining processes. We used the electric motor to turn the engine, which allowed us to measure friction, compression, and other

The utility of many small electronic devices is limited by the power supply. Sandia is developing a mesoscale Stirling engine capable of producing 10 to 20 W of electrical power using a hydrocarbon fuel. The engine is expected to provide an order-of-magnitude reduction in weight compared to standard lithium ion batteries. ...The project is producing important technical advances in microcombustion, miniature-engine design, microfabrication and metrology of metal and ceramic parts, and the application of advanced diagnostics at small scales.

parameters without supplying a heat source. Tests showed that friction torque of the engine was about the same as the motor (~ 0.14 oz in.). The measured pressure matched the calculated values quite well, indicating minimal leakage past the pistons. The primary problem is excess dead volume in the regenerator. Testing of the device continues.

- *Rotary Stirling engine.* We prototyped the first rotary engine using SU8-based UV lithography and electroforming. SU8 is a commercially available negative-tone epoxy-based photoresist that can be spun and patterned in thickness of tens of microns. For the present work, we patterned the molds using a Sandia SU8 formulation that has improved resolution at extreme thicknesses ($400\text{ }\mu\text{m}$ or more). We then electroformed the engine components in these molds from a Watts nickel-plating bath. The electroformed parts were released from the SU8 with a combination of thermal cycling and mechanical removal. We obtained sidewall surface roughnesses of the order of $1\text{ }\mu\text{m}$ root mean square (rms) or better.

- We partially assembled the individual parts to study how they fit and move together. We measured the gaps between the rotor and the housing at the apices from an x-radiograph using a VIEW Engineering Voyager V6 x 12 Programmable Optical Microscope at 10x magnification. We believe this is the first instance where high-aspect-ratio gaps between assembled electroformed microparts have been measured. The gaps ranged from 8 to $12\text{ }\mu\text{m}$. This fit is acceptable, but further reduction is desirable and should be obtainable by optimizing the SU8 processing. To this end, we carried out a series of exposure doses to identify the dose that provided vertical SU8 sidewalls.

- *Microcombustor testing.* Experimentally, we explored a number of combustor configurations based on the excess enthalpy concept. The tube-within-a-tube configuration was most successful. We fed a stoichiometric premixture of methane and oxygen through a thin platinum/20 iridium tube and then counterflowed it through a concentric glass tube. With proper flowrates and geometry, the mixture ignited at the exit port, and the flame back-propagated and anchored at the tip of the inner tube. After a preheat time, we observed catalyst “ignition.” By adding a ceramic insulator, we virtually eliminated the transient time for catalyst ignition. The inside diameter (I.D.) of the inner tube was 0.5 to 1 mm. The I.D. of the outer tube varied on different tests. The tube length was 10 mm. The heat output of the device was 3–6 W. Further increase in flow is possible.

- *Modeling of combustion and heat transfer in microcombustors.* We used CFDRC’s (CFD Research Center) CFD-ACE code and a spectral element code that we are

Experimentally, we explored a number of combustor configurations based on the excess enthalpy concept. The tube-within-a-tube configuration was most successful....After a preheat time, we observed catalyst “ignition.” By adding a ceramic insulator, we virtually eliminated the transient time for catalyst ignition.

modifying to couple with Surface CHEMKIN. The spectral element code provides greater accuracy to study heterogeneous/homogeneous combustion, whereas the commercial code is used for parametric studies. We studied a premixture of hydrogen and air, a system with well-known surface (catalytic) kinetic rates. We varied various parameters for each of these cases to bring out the salient features of the combustion within the device. The maximum temperature was approximately 1200 K, and the conversion of H_2 to H_2O was never complete. Both observations point to the predominance of a heterogeneous (catalytic) combustion within the inner tube.

A second set of computations was concerned with the relative roles of heat conduction, convection, and radiation in transferring heat from the combustor to the engine. We considered a fin, and we explored the trade-offs between different partition materials. From the simulations, heat transferred through radiation constitutes up to 50% of the total heat flux.

Other Communications

Haroldsen, B. L., A. M. Morales, M. Bankert, and T. N. Raber. 2003. Design and fabrication of a mesoscale Stirling engine. Paper presented at the High Aspect Ratio Microstructure Technology Conference, 15–17 June, Monterey, California.

Emerging Threats

The Emerging Threats investment area addresses Sandia's national security mission by developing and applying high-impact technologies to counter new classes of threats (e.g., chemical and biological attacks and other forms of terrorism) that have been emerging since the end of the Cold War, and most notably since recent terrorist attacks upon the United States. Focus areas for research include intelligent systems incorporating sensors, communications, processing, and data exploitation; precision defeat; modeling and simulation of real-world processes and phenomena; and directed energy. This goal is accomplished primarily through partnerships to broaden the application base for Sandia's mission-driven technologies.

Digital radar technology will be the next-generation solution to remote-sensing and communications systems that are required to be low cost, miniaturized, lightweight, and highly flexible. For the past decade, wireless communication systems have reaped the benefits of digital circuit technologies to reduce cost, size, and weight, and to increase flexibility of communications devices. *Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting* is well on the way to

realizing digital receiver and advanced waveform synthesis hardware, which will help set the stage for next-generation digital radars. Three patent disclosures have been filed.

26531

Air Sterilization and Decontamination*R. P. Toth, P. C. Gray, G. C. Hauser, R. Tandon*

Sandia completed full-scale development and physical tests of a novel plasma reactor designed to protect building and vehicle occupants exposed to chemical and biological warfare (CBW) threats. Conventional methods of protection from airborne CBW threats have serious limitations. For example, high-efficiency particulate aerosol (HEPA) filters have particle-size pass-band characteristics that fit many virions; interior positive pressure loses its effectiveness if windows, walls, or hulls are breached; and ultraviolet (UV) illumination suffers not only from shadow effects with heavy loads, but from repairable deoxyribonucleic acid (DNA) damage as well. To address these concerns, we proposed a new technology based on an extreme form of thermal destruction known as pyrolysis.

Pyrolysis requires temperatures in excess of 1000°C, which we attained by means of a radio-frequency (RF)–driven plasma reactor. Our major goals were to up-scale airflow and RF systems to serve a heating, ventilation, and air conditioning (HVAC) zone while retaining 10–100 of millisecond dwell times to ensure supernumerary kill. These two development paths converge in a plasma reactor fabricated in refractory materials.

Airflow studies succeeded with a swirl chamber that can flow a maximum of 80,000 cfh with the specified dwell time. We completed the design and construction of an RF system to produce a microwave discharge over 60 cm in length with over 1100°C in the kill zone. Furthermore, the RF system can operate five of these plasma reactors in parallel to handle a maximum of 400,000 cfh. The fabrication of these full-scale plasma reactors in refractory materials was a major problem. Our previous attempts with aluminum oxide (Al_2O_3) and silicon carbide (SiC) failed because of cracks from thermal shock and RF attenuation, respectively. We reverted to fused quartz after power control could be regulated adequately to prevent thermal decomposition. We successfully tested the quartz plasma reactor in the RF applicator without damage from repeated thermal shock or continued operation at over 1100°C. We did not measure survival curves due to time and budget limitations.

The work breakdown structure comprised the following:

(1) Design and construction of an RF system to sustain a microwave discharge of over 60 cm in length. An important subtask here was the design, fabrication, and test of waveguide chokes to limit RF leakage from such a large structure.

(2) Design of a plasma reactor with mass flow in the 10,000 cfh range with dwell times in the 10–100 ms range.

Sandia completed full-scale development and physical tests of a novel plasma reactor designed to protect building and vehicle occupants exposed to chemical and biological warfare (CBW) threats....we proposed a new technology based on an extreme form of thermal destruction known as pyrolysis....Our major goals were to up-scale airflow and RF systems to serve a heating, ventilation, and air conditioning (HVAC) zone while retaining 10–100 of millisecond dwell times to ensure supernumerary kill. These two development paths converge in a plasma reactor fabricated in refractory materials.

(3) Characterization of flow velocity to validate dwell time.

(4) Determination of RF power needed to sustain such a plasma of at least 1100°C in the kill zone from which to estimate the number of such plasma reactors that can be operated in parallel.

(5) Fabrication in refractory materials of a plasma reactor that meets these specifications.

(6) Testing of such a plasma reactor in the RF applicator for resistance to thermal shock and sustained operation.

(7) Determination of survival curves.

We completed all but the last of the seven objectives. The RF system produced a 62 cm microwave discharge at over 1100°C in the kill zone and beyond by about 10 cm. We designed and fabricated two waveguide chokes, but tested only one of them. The design based on rectangular dominant mode limited RF leakage to 20 mW/cm² at 1 m on axis at the supply end, and 10 mW/cm² at 0.3 m on the discharge end. Both patterns were only 15 deg wide on axis of the broad wall. At the narrow wall, we recorded only 2 mW/cm² at 0.3 m.

We attained the mass-flow and dwell-time goals with a novel triple helix that incorporated the means to reduce pressure reflection. Maximum mass flow was 80,000 cfh. We measured airflow velocity in three dimensions (3-D) to disclose a super-coiled flow pattern. The RF power needed to sustain such plasma discharge would allow five plasma reactors to be operated in parallel. We fabricated the plasma reactor in fused quartz according to the design principles we had established in flow models. We subjected the quartz plasma reactor to numerous heat and cool-down cycles with as much as 3 kW absorbed per cycle. The quartz showed excellent resistance to thermal shock despite its complex structure and numerous welds needed for fabrication.

We fabricated the plasma reactor in fused quartz according to the design principles we had established in flow models. We subjected the quartz plasma reactor to numerous heat and cool-down cycles with as much as 3 kW absorbed per cycle. The quartz showed excellent resistance to thermal shock despite its complex structure and numerous welds needed for fabrication.

26532

Data Fusion and Visualization of MASINT Results for Underground Facility Characterization

M. D. Ladd, M. E. Bukaty, J. M. Brabson, M. L. Yee, A. A. Yee, J. S. Salazar, D. C. Craft, M. W. Koch, C. L. Jenkin

Fusion and visualization of MASINT (measurement and signal intelligence) data is a growing need for the all-source analyst, as the potential for gathering various types of nonimage data increases. It is increasingly important that capabilities exist for combining image and nonimage data, as foreign facilities and activities of interest seek more ways to hide from overhead imaging view. Sandia concentrated on the quantitative fusion of both image and nonimage data to yield more information for the analyst than is possible with either data source separately. The goal is to produce results from field-test data demonstrating a quantitative increase in confidence of the detection of various events related to the functioning of an underground facility (UGF). The test data include synthetic-aperture radar (SAR), acoustic, and seismic data. We will fuse these data using both simultaneous (multiple data sources for the same event) and sequential (data sources for several events over time) fusion tools. We use decision-level fusion, with decisions and confidence measures generated by algorithms for each source of data.

We completed recognition algorithms and implemented them for processing all three sources of data: SAR, acoustic, and seismic. The results of these algorithms were decisions as to the likelihood (confidence) that certain events took place based on the test data. The events searched for were determined *a priori* based on existing signature data on similar events expected to take place in and around a UGF. We then entered the confidence values for the various events into a relational database constructed for the purpose of facilitating fusion of the various results. We then fused these results using two distinct fusion algorithms. One algorithm, the Sequential Probability Ratio Test (SPRT), evaluated data collected simultaneously by SAR, acoustic, and seismic sensors on particular events. The other algorithm, Knowledge Generation (KG), evaluated sequences of events detected by SAR, acoustic, and seismic sensors. In both cases, we demonstrated that the fusion algorithms were able to provide additional information in the form of higher confidence values in the case of SPRT, and automatic recognition of key sequences of events in the case of

Sandia concentrated on the quantitative fusion of both image and nonimage data to yield more information for the analyst than is possible with either data source separately. The goal is to produce results from field-test data demonstrating a quantitative increase in confidence of the detection of various events related to the functioning of an underground facility (UGF).

KG. While the results are based on limited sets of test data, the algorithms used lay the foundation for future work in the area of multisensor fusion for event monitoring with multiple sensors, particularly with imaging and nonimaging sensors.

Visualization work previously provided foundational JAVA™-based tools that enable the user to access information at various levels, from initial decision data up to and including fusion results. Another key aspect of the visualization tools is the ability to present both image and nonimage data in a coherent manner.

26534

Advanced Unattended Ground-Sensor Technology

D. E. Gallegos, M. R. Heying, M. E. Bukaty, J. W. Giron

During recent years, unattended ground sensors (UGSs) have proven very useful for detecting, identifying, and characterizing difficult targets. However, current UGS technology places severe restrictions on real-world deployment. Specifically, their excessive bulk and their inability to covertly off-load data make them difficult to deploy in denied territories. In addition, redeveloping a distinct custom UGS for each set of varying mission requirements is often prohibitive in time and cost.

To address these challenges, Sandia is developing a novel architecture, referred to as Scalable Digital Signal Processing (SDSP), based on the incorporation of a coherent interconnect fabric (ICF) that could lead to small, modular, reconfigurable sensors that could be inserted rapidly into a wide range of deployment mechanisms: microglider, projectile, robot, or hand. Our goal is to achieve a significant decrease in power consumption, thereby dramatically reducing the battery payload: the volumetric “fat” in UGS. Our architectural approach would enable the use of sophisticated power management, dynamically variable clock-rate devices, and UGS-optimized signal processing to automatically optimize the watts-per-MIPS (million instructions per second) arrangement for a given task.

Similarly, we are addressing the covert data communications challenges by a novel adaptation of cell-phone techniques that will reduce the size and power consumption of the communications transceiver. We are adapting digital cell-phone transceivers (DCPTs) for covert local communications. We are using direct-sequence spread-spectrum transmissions in the cell-phone band to establish covert cells with low probability of detection. We will then hand off these low-power communications to a “mother ship” for secure worldwide satellite communications (SATCOM).

This project will design, develop, and demonstrate a prototype miniature ground sensor based on the novel SDSP and DCPT architecture. This architecture will be modular in nature and will provide the needed capability to rapidly respond to new data-collection needs.

(1) *Develop hardware components required for benchtop demo/test.* We demonstrated with actual hardware a low-power

...Sandia is developing a novel architecture, referred to as Scalable Digital Signal Processing (SDSP), based on the incorporation of a coherent interconnect fabric (ICF) that could lead to small, modular, reconfigurable sensors that could be inserted rapidly into a wide range of deployment mechanisms: microglider, projectile, robot, or hand. Our goal is to achieve a significant decrease in power consumption, thereby dramatically reducing the battery payload: the volumetric “fat” in UGS.

scalable ICF for UGS modules. We connected three UGS modules using the I2C variant of the fabric adapter (FA). We configured two of the modules as bilevel trip sensors that provided bursty excitation data to the fabric for traffic and power evaluation. We configured the third module as the interface to a “destination” node that provided the monitoring capability for the data flow on the fabric.

We built and unit-tested the following hardware modules, but did not connect them to the fabric because the firmware required to link them to the fabric was not completed:

- Low-power TMS320VC5510 DSP board,
- Low-power analog board, and
- Global positioning system (GPS) module.

We made preliminary FA power measurements. These measurements do not incorporate the full range of power management features of the microcontroller contained on the FAs.

(2) *Develop software components required for benchtop demo/test.* We developed and implemented an FA-to-FA messaging protocol and used it in the benchtop demonstration. This generic protocol provides for source and destination addressing, variable payload lengths, and data integrity checks. It allows for data-transfer acknowledgments (above and beyond what is provided by the I2C interface). We did not implement these acknowledgments.

We developed the following software modules (for the C5510 DSP) using the Rational Rose Real-Time Unified Modeling Language tool and are awaiting completion of the FA integration firmware for linkage to the fabric:

- Acoustic spectrogram module,
- Data-acquisition module,
- Bilevel trip fusion discrimination algorithm, and
- System-controller module.

(3) *General.* We learned many lessons regarding the use a generic FA architecture for rapid implementation of modular UGS systems.

26535

The Endowment of Simulator Agents with Humanlike Episodic Memory

J. C. Forsythe, R. G. Abbott, A. E. Speed, P. G. Xavier, C. E. Lippitt

This project seeks to extend the capabilities of the cognitive modeling framework currently under development at Sandia by extending its memory and learning capabilities. Previously, we demonstrated a capability whereby a psychologically plausible method for recording, recalling, and querying episodic memory was created. We leveraged this capability to enable the cognitive model to augment its knowledge of the domain by making generalizations based on its experiences.

Specifically, we implemented an episodic memory on the user desktop. This software has the capability to record the “to” fields and subject lines of all incoming and outgoing e-mails as well as to record the names of any attachments being exchanged. The model can then use this information to determine the relationships between people and between people and projects, augmenting itself by adding new people, concepts, and projects to its existing associative network and context library.

(1) Information previously had to be processed by the cognitive model, then processed offline before populating a queriable episodic memory. We developed the capability to generate a queriable log that is available in real time. The user can query the episodic memory about an event that just occurred as easily as about an event that occurred two weeks prior.

(2) Previous search capabilities were somewhat limited. To search episodic memory, the user had to know specifics about the implementation of the episodic log. This year, we hid much of this functionality. Now, the search can ask for any episodes that fall within a specified time range (e.g., what was happening on September 23, 2003, between 8:30 and 9:00 A.M.) and find an episode based on the name, or partial name, of any concept used by the cognitive model (e.g., recall an episode where George Bush is mentioned). Episodes can be found based on the activation intensity level (e.g., recall the five most memorable episodes—those that have concepts with the largest activation intensity level). If an internal episodic memory index is known, it can be used to recover the entire episode that surrounds that event. This is primarily intended for programmatic use, but it is available to the end user, too.

This project seeks to extend the capabilities of the cognitive modeling framework currently under development at Sandia by extending its memory and learning capabilities....we implemented an episodic memory on the user desktop.

This software has the capability to record the “to” fields and subject lines of all incoming and outgoing e-mails as well as to record the names of any attachments being exchanged. The model can then use this information to determine the relationships between people and between people and projects, augmenting itself by adding new people, concepts, and projects to its existing associative network and context library.

In the most general case, a query can be formed that will find the best N matches for a multipart query where several simultaneous constraints are used to find the matching episodes. Any of the abovementioned search methods can be combined into a single search request, e.g., “What were all the messages sent to George Bush in September 2003 about the Terrorist Threat project that included Geena Davis?”

(3) This year, we extended the search with regard to the specificity of the questions that can be asked. Specifically, the user can specify

(a) things that are required (e.g., “I only want to know about e-mails I’ve sent to George Bush.”),

(b) things that are desired (e.g., “I want to know about all e-mails regarding episodic memory, but I’m most interested in those that have George Bush in one of the ‘To’ fields.”),

(c) required time relationships (e.g., “I want to know about situations in which A happens, then B, then C, but I don’t want to know about situations in which B happens, then C, then A.”),

(d) desired time relationships (e.g., “I want to know about situations in which A, B, and C happen, but especially A, then B, then C.”), and

(e) unscored query records (e.g., “I would like to have all e-mails relevant to episodic memory, but if George Bush is on those e-mails, I’m less interested in them.”).

(4) The model is now able to recognize when something new is presented to it. In its previous instantiations, the model could not handle novel information. We enabled it to recognize when it does not recognize something (i.e., it does not recognize a name in the “To” field of an e-mail), it is able to determine where that novel stimulus most likely belongs in terms of its understanding of the world based on the other stimuli present in the same episode (i.e., it sees other names in the “To” field that it recognizes and words in the subject line that it recognizes and indicate the projects to which these names and words are related), and it is able to query the user regarding the accuracy of this relationship (i.e., it requests that the user indicate if that new name be added to one of the projects, or if it should ignore that name). Furthermore, it is able to start out with very minimal knowledge of e-mail interactions and build a mental model from the ground up—it starts almost as a *tabula rasa*.

The model is now able to recognize when something new is presented to it....it is able to determine where that novel stimulus most likely belongs in terms of its understanding of the world based on the other stimuli present in the same episode...and it is able to query the user regarding the accuracy of this relationship. ...Furthermore, it is able to start out with very minimal knowledge of e-mail interactions and build a mental model from the ground up—it starts almost as a tabula rasa.

26539

Algorithms for Improved Performance in Cryptographic Protocols

C. L. Beaver, D. R. Gallup, R. C. Schroepfel, E. M. McNicholas, L. M. Miller, N. D. Blair-Stahn

Public key cryptographic algorithms provide data authentication and nonrepudiation for electronic transmissions. The mathematical nature of the algorithms, however, means they require a significant amount of computation, and encrypted messages and digital signatures require high bandwidth. Accordingly, there are many environments (e.g., wireless, ad hoc, remote-sensing networks) where public key requirements are prohibitive and cannot be used. The use of elliptic curves (ECs) in public key computations provided a means by which computations and bandwidth can be somewhat reduced. Sandia's research in this project sought to find even more efficient algorithms and to make public key cryptography available to a wider range of computing environments. We improved upon several algorithms, including one for which a patent has been applied. Further, we discovered some new problems and relations on which future cryptographic algorithms may be based.

We submitted a patent application for an EC algorithm that offers an efficiency improvement and also avoids "side-channel attacks."

The expensive operation in an EC-based cryptographic algorithm is the computation of a multiple of a point. One main component of that algorithm involves taking a reciprocal. Our idea is to save all these computations until the end and do them at the same time so we can simultaneously compute all the reciprocals. The idea uses a "reciprocal savings trick" developed by Peter Montgomery. Besides being more efficient, the algorithm also protects from side-channel attacks. With the normal algorithm for scalar multiplication, an attacker often can carefully observe the computational device and determine whether it is executing a point addition or a point doubling. The pattern of doublings interleaved with some additions can be used to recover the bits of the key. Since we group all these operations at the end, the attacker is thwarted.

We also contracted with Bill Gosper to explore another idea for faster operations with "points" on systems that are closely related to elliptic and hyperelliptic curves. He developed a number of "point-addition" formulas for these systems. His work confirms that these systems could be used as alternatives

Sandia's research in this project sought to find even more efficient algorithms and to make public key cryptography available to a wider range of computing environments. We improved upon several algorithms, including one for which a patent has been applied. Further, we discovered some new problems and relations on which future cryptographic algorithms may be based.

to ECs in, for example, key exchange. More work is needed to make his discoveries efficient. As it stands, his formulas need more arithmetic than the usual EC methods, but they may be competitive with hyperelliptic curves, which have much more complex point-addition formulas. His formulas may also be sped up by judicious specialization and careful choices of some of the system parameter values as 0 or 1 to eliminate some terms from the formulas. Another idea to examine is to use GF2 fields, where squaring is essentially a free operation and terms with even coefficients (2, 4, etc.) drop out.

We explored another such system, closely related to classic elliptic function theory over the complex numbers. This scheme also seems not quite competitive with the usual elliptic function methods.

26540

Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting

D. F. Dubbert, P. A. Dudley, D. Greenway, Jr., T. Hardin, R. E. Heintzleman

Sandia developed two fundamental concepts for radar receiver/exciter (RX/EX) subsystems. The technique of Quadrature Error Corrected Digital Waveform Synthesis (QECDWS) facilitates the realization of a high-frequency, wide-bandwidth radar exciter, which reduces the complexity of the associate analog up-conversion circuitry. This, in concert with a digital receiver (DRX), which migrates former analog RX functions into the digital domain, allows for an unprecedented simplification of the analog and microwave portions of the radar RX/EX. The utilization of modern field-programmable gate arrays (FPGAs) in both the QECDWS and the DRX adds a new level of system flexibility, reconfigurability, and performance. The digital RX/EX is core to future synthetic-aperture radar (SAR) systems developed at Sandia, which emphasize small size and weight, low cost, and high performance. The ultimate digital RX/EX is realized when considering radar systems for fuzing and moderate-resolution imaging applications, which require low to moderate RF bandwidths and RF center frequencies.

Accomplishments span the three major project areas: the DRX, the advanced waveform synthesis, and the advanced digital radar concepts.

Sandia developed two fundamental concepts for radar receiver/exciter (RX/EX) subsystems. The technique of Quadrature Error Corrected Digital Waveform Synthesis...in concert with a digital receiver...allows for an unprecedented simplification of the analog and microwave portions of the radar RX/EX.

The DRX is considered the first major hardware advance toward the realization of a next-generation digital radar.

- *Digital receiver.* We designed the 6U (6 x 9 in.) VME (Versa-Module Eurocard) DRX module as an upgrade to our current Advanced Radar Systems (ARS) SAR experimental platform. The DRX is considered the first major hardware advance toward the realization of a next-generation digital radar. This module completes the design, testing, and radar integration phase successfully and is scheduled to fly along with the Ka-band ultrahigh-resolution SAR system soon. In addition, a 3U (4 x 6 in.) cPCI (compact Peripheral Component Interconnect) DRX has been designed and is currently in the final board layout phase. This DRX is a critical component of the miniSAR system developed at Sandia.

- *Advanced waveform synthesis.* The 3U cPCI QECDWS completed initial tests and is ready for next-level miniSAR integration testing. As part of this development effort, we submitted a patent application for the quadrature error corrected synthesis techniques and calibration techniques ("Improved Quadrature Waveform Synthesizer," SD-6761, May 2003).

- *Digital radar concepts.* We proposed several advanced radar digital RX/EX concepts. These include the upgrades to current-generation Sandia SARs using the 6U VME DRX, the Defense Advanced Research Projects Agency (DARPA) MicroSAT digital RX/EX, and concepts for next-generation fuzing radars (radar altimeter).

This DRX is a critical component of the miniSAR system developed at Sandia.

Refereed

Doerry, A. W., and D. F. Dubbert. 2003. Digital signal processing applications in high-performance synthetic-aperture radar processing. *Proc. 37th Asilomar Conference on Signals, Systems, and Computers*, accepted.

Dubbert, D. F. 2002. A digital IF receiver module for high-performance airborne SAR applications. *Proc. Workshop on Synthetic-Aperture Radar Technology RD-MG-03-01* (October, Redstone Arsenal, Huntsville, Alabama).

Dubbert, D. F. 2002. A high-speed quadrature error corrected chirp synthesizer module for SAR application. *Proc. Workshop on Synthetic-Aperture Radar Technology RD-MG-03-01* (October, Redstone Arsenal, Huntsville, Alabama).

Radder, J. 2003. Implementation of a High-Throughput Variable Decimation Pane Filter Using the Xilinx System Generator. Sandia Technical Report SAND2003-0286, Sandia National Laboratories, Albuquerque, New Mexico.

Other Communications

Dubbert, D. F. 2003. FPGAs play big roles in the development of small radars. *Wireless Design and Development*, accepted.

26543

Adaptive and Mobile Ground Sensors

A. B. Maish, R. L. Williams

The goal of this project is to demonstrate the use of robotic vehicles for deploying and autonomously reconfiguring seismic and acoustic sensor arrays with high accuracy (centimeters) to enhance our capability to locate and characterize denied targets.

Seismic and acoustic sensors configured in phased arrays are used for multiple tasks.

- *Tuned to specific frequencies to create narrow beams, they are used to help in source localization (bearing).*
- *Using coherent superposition of multiple sensors, they are used for increasing gain for longer-range detection and scanning for specific frequencies.*

Sandia previously determined that the optimal configuration for this project was not to have numerous robots that carry sensors, but to have one larger vehicle deploying sensor pods that communicate by radio frequency (RF) rather than by cable or fiber. By successfully achieving the goal of a reconfigurable sensor array, this project enables us additionally to enhance the foundation of our core mobile robotic-vehicle and sensor capabilities by making dramatic progress in multiple areas that significantly enhance our responsiveness in a wide range of timely business opportunities. These areas include the following:

- *Sensor-array processing algorithms. Real-time processing of sensor-array data and autonomous reconfiguration algorithms has not been achieved.*
- *Sensor-array hardware and communication. Multisensor synchronous communication of seismic-array data to a central processor has not been achieved by RF before.*
- *Vehicle-control code architecture. Modular robotic-vehicle control for semiautonomous operation is not currently available.*
- *Precision vehicle-placement control. Autonomous precision placement of vehicles to centimeter accuracies in unstructured (outdoor) environments has not been achieved.*
- *Small autonomous vehicle mobile manipulation. We have not previously incorporated manipulation on a semiautonomous vehicle of this small scale.*

This very ambitious project was successful in accomplishing the major goals identified for the robotic vehicle and the sensor-array parts of the project. We developed and

The goal of this project is to demonstrate the use of robotic vehicles for deploying and autonomously reconfiguring seismic and acoustic sensor arrays with high accuracy (centimeters) to enhance our capability to locate and characterize denied targets....By successfully achieving the goal of a reconfigurable sensor array, this project enables us additionally to enhance the foundation of our core mobile robotic-vehicle and sensor capabilities by making dramatic progress in multiple areas that significantly enhance our responsiveness in a wide range of timely business opportunities.

successfully demonstrated a robotic vehicle operating a modular control-system architecture that autonomously deployed and retrieved a sensor pod with centimeter positional accuracy. We developed a multisensor simultaneous-operation radio communications system and a digital signal-processor (DSP)–based signal-processing algorithm that can autonomously process the multisensor-array data and determine optimal array configuration for redeployment. We were not able to demonstrate a fully integrated system as originally planned due to limited funding, but we did not encounter any technical obstacle that would prevent such a demonstration in the near term.

We made major accomplishments in both the robotic vehicle and sensor algorithm and hardware areas over the course of this project.

- *Autonomous robotic vehicle capable of deploying and retrieving sensors.*

- We completed modifications on the SandDragon dual-body mobile robotic vehicle supporting the global positioning system (GPS) antenna, compass, and camera.

- We assembled, installed, and tested a new sensor deployment and retrieval nondexterous manipulator with 3 in. misalignment tolerance.

- We completed restructuring the vehicle-control code into a modular, multithread architecture facilitating the addition of new vehicle-control modules such as autonavigation algorithms being developed under other projects.

- We transferred the SMART autonomous vehicle code from operating partially on the base station to operating entirely on the vehicle, making the vehicle control entirely autonomous.

- We developed and tested control software for the sensor deployment and retrieval manipulator.

- We demonstrated centimeter-accuracy navigation using differentially corrected GPS.

- We developed and tested software interface modules to communicate between the vehicle and the sensor DSP that processes the sensors' signals and runs the array-optimization algorithm.

- We demonstrated deployment of sensors with centimeter accuracy relative to a GPS base station, and subsequent retrieval of those sensors autonomously.

- *Sensor-array software and control-system development.*

- We procured and evaluated a vehicle-based commercial DSP processor single-board computer (Orsysâ microlineä C6711) with a synchronous serial-communication daughter card and a commercial radio-frequency (RF) transceiver card

(Symbol Spectrum 24 802.11b wireless local-area network [LAN]) capable of simultaneous communication with 16 sensor pods.

— We developed and tested the operating code for the DSP. We generated the code with the Rational Rose Realtime™ modeling tool. The code consists of five capsules that interface with the radio, the vehicle-interface universal asynchronous receiver-transmitter (UART), the signal-processing (beam-forming) software module, the robotic-vehicle controller interface module, and the array-sensors controller module.

— We developed and tested the signal-processing and array-optimization algorithm code for the DSP using field data.

— We developed and tested the robotic-vehicle controller interface module.

— We developed and tested the radio interface, including the signal data management software.

— We procured and evaluated the sensor processor (TI-C5510) and analog prototype boards and the RF transceiver daughter card for the sensor pods. We also assembled and tested five demonstration field-sensor boxes.

— We conducted benchtop demonstrations of multisensor, synchronized (i.e., retaining original relative signal timing from the different sensors) data transfer via RF to the DSP transceiver unit.

While some additional work is needed to demonstrate this integrated, autonomous, robotically deployed, reconfigurable seismic and acoustic sensor-array system, we demonstrated the core technical achievements necessary to complete this system. These achievements are major accomplishments that even by themselves open the door for follow-on investments.

...we demonstrated the core technical achievements necessary to complete this system. These achievements are major accomplishments that even by themselves open the door for follow-on investments.

26544

Algorithm Development for Prognostic Health Monitoring and Maintenance

L. P. Swiler, A. B. Doser, J. E. Campbell, K. S. Lowder

Prognostics refers to the capability to predict the probability of system failure over some future time interval; an alternative definition is the capability to predict the remaining useful life of a system. Prognostics are integrated with health monitoring (through inspections, sensors, etc.) to provide an overall prognostics and health management (PHM) systems capability that optimizes maintenance actions and results in higher availability at a lower cost. Sandia sought to develop PHM tools that can be applied to a wide variety of equipment (repairable, nonrepairable, manufacturing, weapons, battlefield equipment, etc.) and that require minimal customization to move from one system to the next. Thus, our approach was to develop a toolkit of reusable software objects/components and architecture for their use.

We developed two software tools: an Evidence Engine and a Consequence Engine. The Evidence Engine integrates information from a variety of sources to take into account all the evidence that impacts a prognosis for system health. The Evidence Engine has the capability for feature extraction, trend detection, information fusion through Bayesian belief networks (BBNs), and estimation of remaining useful life. The Consequence Engine involves algorithms to analyze the consequences of various maintenance actions. The Consequence Engine takes as input a maintenance and use schedule, spares information, and time-to-failure data on components, then generates maintenance and failure events and evaluates performance measures such as equipment availability, mission-capable rate, time to failure, and cost.

We developed algorithms, an architecture, and approaches for developing PHM. In addition, we developed two software tools that can be applied to a wide variety of equipment with minimal customization. As part of the software development, we created a toolkit of reusable software objects. The two software tools developed in this project are the Evidence Engine and a Consequence Engine.

- *Evidence Engine.* The Evidence Engine integrates information from a variety of sources to take into account all the evidence that impacts a prognosis for system health. In addition to the prototype Evidence Engine, we developed some modular software objects that perform a “step” in the evidence

Sandia sought to develop PHM tools that can be applied to a wide variety of equipment (repairable, nonrepairable, manufacturing, weapons, battlefield equipment, etc.) and that require minimal customization to move from one system to the next.... We developed algorithms, an architecture, and approaches for developing PHM. In addition, we developed two software tools that can be applied to a wide variety of equipment with minimal customization.

integration stage (such as taking the value of a sensor feature and translating it to failure-mode-state probabilities). We developed some examples to demonstrate the usefulness of various techniques. The techniques for information fusion include BBNs and feature classification using Kohonen self-organizing maps (SOMs). These two methods are useful to evidence integration. We also developed a signal-processing algorithm for frequency domain comparison of vibration signals, such as accelerometer data. Finally, we developed a theoretical approach for updating time-to-failure distributions and implemented it in software.

- *Consequence Engine.* The purpose of the Consequence Engine is to predict the effect that repair/replace/inspect/wait strategies will have on the system if that action is taken. This “consequence analysis” part of the problem must be performed in such a way that the expected benefit from performing each alternative can be calculated. Then, given a set of alternatives each with an expected cost/benefit, the alternative (or subset of alternatives) can be chosen that maximizes the expected benefit for the minimum cost.

The Consequence Engine takes the system health predictions from the Evidence Engine and develops projections into the future—what will be the overall impact on the system if a certain action is taken. Simulation is used to model the long-term impact of possible maintenance/inspection strategies for each failure mode on overall system performance and cost. We chose simulation as the basis for the Consequence Engine because of its flexibility. The simulation mimics the reliability behavior of equipment in terms of simulated equipment failures, repairs, scheduled maintenance, and inspections. We based the simulation on user-definable maintenance and inspection schedules and a reliability model with time-to-failure and time-to-repair distributions for all failure modes. We included a spares model since the availability of spares may be a major factor in decision making when a pending failure is identified. By running repeated simulations, we can use the Consequence Engine to calculate performance metrics such as mean time between failures (MTBF), mean time to repair (MTTR), availability, maintenance cost, downtime cost, etc. Thus, by running the simulation with different maintenance schedules, one can examine the consequences of alternative equipment-maintenance scenarios. Optimization (using genetic algorithms) is a capability that we added to the Consequence Engine to support the generation of optimal maintenance actions.

The consequence analysis supports rapid evaluation of the potential effectiveness of a PHM system. PHM systems, no matter how well designed, may either fail to detect a pending problem (false negative) or report a problem when none exists (false positive). False positives can result in unnecessary (and expensive) maintenance. False negatives can allow failures to occur that should have been caught. If important decisions are based in part on PHM predictions, the costs of a false negative can be very high. For example, the decision may be made that military equipment is “good to go” for a mission when a pending failure has gone undetected by the PHM system. The Consequence Engine can help to understand the cost/benefit trade-offs for a PHM system, depending on its error rates.

Refereed

Swiler, L. P., and W. E. Grube. 2003. Prognostics for accessory drive gearboxes on fixed-wing aircraft. *Proc. Machinery Failure Prevention Technology Conference* **57** (14–17 April, Virginia Beach, Virginia): 201–10.

Other Communications

Swiler, L. P. 2003. Prognostics and health management: An overview. Paper presented at the INFORMS (Institute for Management Sciences and Operations Research) Meeting, 20–22 October, Atlanta, Georgia.

26545

New Mechanism for Upset of Electronics

R. A. Salazar, L. D. Bacon, L. L. Molina

Sandia studied nonlinear dynamical effects on electrical systems. We will use our knowledge to explore chaotic behavior of more complicated systems. A major effort completed within our study was the development of a more accurate model of the "Linsay" circuit. The Linsay circuit is the simplest electronic circuit that demonstrates basic chaotic behavior. The definition of chaotic behavior is complicated, but the properties of a chaotic circuit are easy to understand. Essentially, the electrical parameters of a chaotic circuit are deterministic and follow the same physical laws of any other circuit. Yet, the behavior of the chaotic circuit is too complicated to describe with a set of simple equations. We developed a model based on the Linsay circuit that is in good agreement with measured results.

We also studied the behavior of a phase-locked loop (PLL) and modeled the operation of the PLL under normal operation conditions. PLL simulations derived from models developed during previous work were in close agreement with measured PLL behavior. We also studied the effects on a PLL and its chaotic behavior when subjected to interference. Under certain conditions, the PLL exhibits chaotic behavior. We developed a theory (supported by measurements) that predicts the behavior of the PLL under the influence of RF.

We developed a Linsay model that has a much higher level of agreement than found in the literature. Most researchers are content with differences of a factor of 2 between experimental and simulation results. The agreement between our measured results and our experimental results are within a few percent. Understanding the behavior of the Linsay circuit is crucial to understanding circuits that are more complicated.

We looked at linear and nonlinear properties to evaluate the quality of the model. The time domain and the frequency domain results of measured and simulation results are in very good agreement. In addition, the Lyapunov numbers and other nonlinear properties are also in good agreement between the simulated and measured results. Our model is different from other models in that we included the behavior of the minority carriers at the p - n junction. We adjusted the effective diffusion capacitance to correct for the effective minority carrier distribution. The diffusion capacitance and the conductance of the p - n junction are frequency dependent. By scaling the effective diffusion capacitance and conductance, the simulated

Sandia studied nonlinear dynamical effects on electrical systems. We will use our knowledge to explore chaotic behavior of more complicated systems....We developed a Linsay model that has a much higher level of agreement than found in the literature. Most researchers are content with differences of a factor of 2 between experimental and simulation results. The agreement between our measured results and our experimental results are within a few percent.

results are in very good agreement with the measured results. Without scaling, the measured and simulation results do not compare.

We also studied the behavior of a PLL and developed a model of the PLL under normal operation conditions. PLL simulations derived from models that we developed were in close agreement with measured PLL behavior. We used the model to study the effects of radio-frequency (RF) interference on a PLL. Under certain conditions, the PLL exhibits chaotic behavior. We determined that the RF interference caused the PLL chip to miscount the number of cycles at its sampling point in the circuit. This miscount causes an error in the feedback voltage to the voltage-controlled oscillator (VCO) that generates the PLL output. The feedback loop has a significantly delayed frequency stability. The delay in the loop is the mechanism that caused the circuit to behave nonlinearly (chaotically).

Refereed

Loubriel, G. M., A. Mar, R. A. Salazar, and L. D. Bacon. 2003. High-power microwave, radio frequency, and component development at Sandia National Laboratories. *Proc. International Conference of Electromagnetics in Advanced Applications ICEAA '03* 1 (September, Torino, Italy): 393–99.

26546

Flexible Robotic Maintenance Facility*W. D. Drotning, C. S. Loucks, W. J. Prentice, P. A. Watterberg, D. M. Kozlowski*

One of the results of the Department of Energy's (DOE's) Robotics and Intelligent Machines Roadmap was to identify classes of processes that could be automated. The Roadmap identified the automation technology bases that underlie noncontact, contact, and multiprocesses, and highlighted the need for the development of technology aimed at automation for multiple systems and classes of processes. The goals of this project were to develop advanced design tools for flexible robotic workcells, to apply these tools to analysis of an automation-intensive flexible maintenance facility, and to demonstrate use of the analysis on a key maintenance process technology. An additional goal was to develop new hardware technology to support automation of this key process. Sandia expects that the eventual benefits of this effort will be increased utilization of facilities and capital equipment and reduced cost in automation programming, leading to reduced overall maintenance and operations costs.

We envision a facility that is designed for automated operations and that can accommodate an entire class of complex systems so that the cost can be amortized over multiple systems and processes. We used military aircraft maintenance as the initial target environment for this work, although the resulting tools are applicable to the design of robotic workcells for other complex systems.

We performed a system study of military aircraft depot maintenance to identify high-payoff automation opportunities and technology needs. As part of this project, we developed, enhanced, and integrated a set of advanced design and analysis tools. The tools allow rapid analysis of a workcell configuration for operations on any component of a class of systems. The tools integrate modeling and simulation, automated path planning and generation, and minimization methods to support analysis of workcell architectures. They allow assessment of designs with variable workpiece position and use automated methods to minimize the number of robot positions that must be specified. We selected an in-contact maintenance process for technology development and pilot demonstration, showing application of the tools for analysis and design as well as robot control.

The goals of this project were to develop advanced design tools for flexible robotic workcells, to apply these tools to analysis of an automation-intensive flexible maintenance facility, and to demonstrate use of the analysis on a key maintenance process technology. An additional goal was to develop new hardware technology to support automation of this key process....the eventual benefits of this effort will be increased utilization of facilities and capital equipment and reduced cost in automation programming, leading to reduced overall maintenance and operations costs.

Development of the flexible design and analysis tools focused on integrating and enhancing the automated reachability analysis tool and the automated path-generation and optimization tools. The goal was to build these into a framework that is accessible to engineers in a more robust and generalized analysis tool and that eliminates the *ad hoc* nature of past implementations of these tools. To this end, we integrated these tools into UMBRA, an application framework for advanced controls, simulation, and visualization. From prior tools, the robot-specific knowledge needed to be separated from application knowledge so that new robot objects can be implemented rapidly without modification to the process application or user-interface software.

The final product is a demonstration of the integrated tool that shows the flexibility of the tool for analysis of maintenance operations. The demonstration comprises the analysis of an automation facility (robot workcell) containing two different workpieces, e.g., P-3 and B-2 aircraft, for operation with two different processes, such as sanding (contact) and coating (noncontact). In the UMBRA framework, we defined and developed a robot workcell and constructed workpieces. Next, we chose a process for a selected area of the workpiece. The analysis tools generated a robot work path to accomplish the task. We then performed a reachability analysis to determine whether the task could be performed by the particular robot in this position. Automated methods can be invoked to optimize the position. Subsequently, we tested the path in simulation for workcell interferences and collisions and generated a robot path. We then downloaded the path to the robot controller for actual execution. For the demonstration, we planned a sanding process path and followed it on a curved aircraft surface.

We selected precision surface finishing and preparation as an important and broadly needed process where automation has been hindered by lack of advanced technology. It is also representative of a wide variety of in-contact processes that may employ model-based position analysis, sensor-based workpiece characterization, robot motion control, and process monitoring/feedback. We designed and developed a surface-finishing (“sanding”) device with active compliance as an end-effector for a robot manipulator arm. The device uses a portable sanding tool attached to a 6-degree-of-freedom (6DOF) parallel kinematic manipulator, based on a Stewart platform design. We designed and developed the 6DOF manipulator device to achieve active compliance to curved surfaces using high-performance force control. We also designed, analyzed, and optimized a unique 5DOF parallel manipulator concept.

The final product is a demonstration of the integrated tool that shows the flexibility of the tool for analysis of maintenance operations.

Other Communications

Drotning, W. D., D. M. Kozlowski, C. S. Loucks,
W. J. Prentice, and P. A. Watterberg. 2003.

Automation Tools for Flexible Aircraft
Maintenance. Sandia Technical Report
SAND2003-3501, Sandia National Laboratories,
Albuquerque, New Mexico.

26548

Obstacle Detection for Autonomous Navigation

D. D. Padilla, M. R. Muguira, J. C. Neely, J. J. Carlson, D. K. Novick

Since the terrorist acts of 9/11 there is an ever-increasing need for autonomously navigating vehicles for counterterrorism and defense missions. The limiting factor in autonomous navigation is the ability to sense and map the environment. This project will develop a mathematical framework for obstacle detection. Sandia expects the framework to provide a basis for solutions to many complex obstacle-detection problems critical to successful autonomous navigation. One goal of this project is to characterize sensing requirements in terms of physical characteristics of obstacles, vehicles, and terrain. For example, a specific vehicle traveling at a specific velocity over a specific terrain requires a sensor with a certain range of detection, resolution, field of view (FOV), and sufficient sensitivity to specific obstacle characteristics. In some cases, combinations of sensors may be required to distinguish between different hazardous obstacles and benign terrain. In our framework, the problem is posed as a multidimensional, multiple-hypothesis, pattern-recognition (PR) problem. We will extract features from selected sensors that allow hazardous obstacles to be distinguished from benign terrain and other types of obstacles. A Weighted-Nearest-Neighbor (WNN) decision model will fuse feature measurements to minimize classification errors. In addition, classical estimation theory will provide the framework for estimating obstacle characteristics such as position and size. Another goal of this project is to characterize different terrain classes with respect to both positive (e.g., rocks, trees, fences) and negative (e.g., holes, ditches, drop-offs) obstacles. The density of various hazards per square kilometer will be statistically quantified for different terrain categories (e.g., high desert, ponderosa forest, and prairie). This quantification will reflect the scale, or size, and mobility of different types of vehicles. We will also characterize the trade-offs between obstacle detection, position location, path planning, and vehicle mobility capabilities.

Our work focused on investigating and developing sensing technologies for obstacle detection as well as on developing a simulation environment for obstacle detection.

No single sensing technology exists that is capable of fully characterizing complex, natural terrain. We explored innovative ways to use existing sensors. Through the evolution of various

This project will develop a mathematical framework for obstacle detection. Sandia expects the framework to provide a basis for solutions to many complex obstacle-detection problems critical to successful autonomous navigation. One goal of this project is to characterize sensing requirements in terms of physical characteristics of obstacles, vehicles, and terrain....Another goal of this project is to characterize different terrain classes with respect to both positive (e.g., rocks, trees, fences) and negative (e.g., holes, ditches, drop-offs) obstacles.

autonomous systems and missions, sensor engineers need to be able to combine multiple sensors without impacting the entire system, i.e., plug-and-play modules. We developed a simulation environment using the modular architecture framework considered previously. The simulation uses various sensor attributes (spatial and range resolution, probability of detection and false alarm, FOV, and range of detection) to compute metrics of performance.

The most widely used sensor for autonomous navigation is commercial ultrasonics intended for operation in controlled environments to detect the presence of objects. These sensors output a range measurement based on the time of flight of the first return to exceed a set threshold and even detect a blade of grass. A significant amount of effort focused on the development of detection/classification algorithms using the raw echo return signal of conventional ultrasonics. Typical half-power beamwidths of these sensors are 8 deg, resulting in poor spatial resolution. We addressed this deficiency by building an acoustic, phased-array imager providing a three-dimensional (3-D) profile of its FOV. For liquid and solid media, acoustic imaging is a highly developed tool and is in use in several sciences. Acoustic imaging in air is a difficult task and requires more investigation before it may be realized for autonomous vehicle navigation. We tested several transmitters/receivers in various configurations before the final design was concluded. Testing shows agreement between simulation and hardware verification results.

In addition, we evaluated the potential of using high-resolution aerial photography for mapping and obstacle detection as well as for a scanning laser range finder.

28775

Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications

A. Mar, T. R. Nelson

Sandia will use a terawatt fs laser system at the University of Illinois at Chicago (UIC) to extend the parameter space being evaluated for laser-based directed energy, photoexcited x-ray lasers, and remote sensing, to include ultraviolet (UV) coupling at critical powers in a relativistic self-focusing regime. Improvements to this laser system have produced a peak source brightness sufficient to access a fundamentally new regime of guided electromagnetic propagation in plasmas. As a consequence, excited matter combining concentrated energy density with well-ordered spatial-gain structure can be created in a trapped focusing state. The resulting laser-driven excited states exhibit new physical processes that can enhance radiative coupling to classically forbidden inner-shell states, thereby enabling the production of “hollow” atoms with inverted electronic configuration and core electron vacancies optimal for rapid x-ray recombination, x-ray amplification, and favorable stimulated emission rates. Using this novel drive configuration, we can realize a table-top x-ray laser operating in the multikilovolt spectral regime. A comprehensive understanding of the unprecedented dynamics of such a process will provide a new general method for power compression in materials.

We observed single-pulse measurements of spectral hole-burning of the Xe(L) 3d→2p hollow-atom transition arrays from a self-trapped plasma channel. These results provide new information on the dynamics of saturated amplification in the $\lambda \sim 2.8\text{--}2.9 \text{ \AA}$ region. Specifically, these results (1) demonstrate a very favorable energy efficiency and (2) point to the potential for development of a new attosecond x-ray technology. Of chief importance is the fact that the spectral hole-burning on transitions in the Xe³⁴⁺ and Xe³⁵⁺ arrays reaches full suppression of the spontaneous emission and presents simultaneously a corresponding width $\Delta h\nu_x \cong @ 60 \text{ eV}$, a value adequate for efficient amplification of multikilovolt x-ray pulses down to a limiting length $\tau \sim 30 \text{ as}$. The depth of the suppression at $2.86 \text{ \AA}$ indicates that the gain-to-loss ratio is ≥ 10 . Further, an independent determination of the x-ray pulse energy from damage produced on the surface of a titanium foil in the far field of the source gives a pulse energy of 20–30 mJ, a

Sandia will use a terawatt fs laser system at the University of Illinois at Chicago (UIC) to extend the parameter space being evaluated for laser-based directed energy, photoexcited x-ray lasers, and remote sensing, to include ultraviolet (UV) coupling at critical powers in a relativistic self-focusing regime....A comprehensive understanding of the unprecedented dynamics of such a process will provide a new general method for power compression in materials.

range that correlates well with the observation of the spectral hole-burning and indicates an overall extraction efficiency of ~ 10%.

34698

Microfuze

L. S. Weichman, D. R. Koehler, E. S. Hafenrichter, S. M. Harris, R. J. Shul, S. H. Kravitz, E. J. Welle, S. M. Wooden, A. S. Tappan

The primary mission of the weapon fuze is to provide uncompromising munitions safety and subsequent control of weapon detonation events. Within this architecture, the fuze integrates inputs from various mechanical or environmental sensors and, if the preset conditions for weapon function are realized, supplies the required detonator stimulus. However, evolving mission scenarios for future weapon platforms will soon outpace the capabilities of today's "tool-box" of fuzing technologies. The ability to hold our adversaries' hard and deeply buried targets (HDBTs) at risk is critical to supporting the U.S. policy of power projection and deterrence. Today's high-velocity penetrating weapons targeting those buried assets or tomorrow's battlefield engagements will require advanced fuzing architectures characterized by "intelligent" function under high-G impacts. Achieving increased fuze functionality in a size constraint implicit with high-G survivability implies development of novel system architectures incorporating new concepts in munitions safety and the realization of miniaturized component suites based on emerging processes and technologies.

Recent groundbreaking advances in microtechnologies are enabling a new generation of miniature fuze designs. The relatively small geometries, low mass, and low inertia of microelectromechanical systems (MEMS)–based devices make the technology attractive for next-generation fuze applications that will experience extremely high-G environments. Developing a sound technical basis together with the effective integration of Sandia's expertise in munitions safety, microdetonics, and silicon surface micromachines will prove essential in achieving the required revolutionary advancements. To that end, we directed the ultimate realization and embodiment of the science and technology foundations developed under this project toward accomplishing the required safety and fuzing functions on a single substrate or "chip." We achieved technology developments in characterization of a MEMS–based mechanical safe and arm (S&A) device and the demonstration of a compatible explosive train.

We fabricated and characterized a second generation of MEMS S&A devices and successfully demonstrated functionality of the microfuze explosive train. We also

Recent groundbreaking advances in microtechnologies are enabling a new generation of miniature fuze designs. The relatively small geometries, low mass, and low inertia of microelectromechanical systems (MEMS)–based devices make the technology attractive for next-generation fuze applications that will experience extremely high-G environments.... We achieved technology developments in characterization of a MEMS–based mechanical safe and arm (S&A) device and the demonstration of a compatible explosive train.

mechanically evaluated pertinent MEMS S&A design parameters, demonstrating S&A functions, validating dynamic models, and providing an initial assessment of the MEMS S&A design and associated processes. We subjected a total of 19 devices to specific test conditions, generating centrifugal forces and extreme shear loading.

We conducted centrifuge tests to validate and improve the analytical models used in predicting the spin rates where latching of the shuttle mass would occur. In this case, we tested nine units reflecting eight design combinations or latch conditions. Six of these units survived the specified test program and, when the prescribed latch environment was exceeded, successfully latched into the arm position. In all cases the predicted or modeled actuation G-levels required to latch the mechanism were higher when compared to the measured environment. We also observed that the required actuation levels further decreased in varying degrees on subsequent runs, suggesting potential spring or material fatigue. Finally, our analysis suggests that model performance and fatigue properties improve significantly with spring width.

We used drop table testing to obtain higher and, ultimately, destructive levels of input acceleration or G-force. The objective of this test set was to achieve a first look at failure modes under extreme shear loading. We subjected a total of 10 devices to multiple incremental shocks characterized by short pulse durations ($< 900 \mu\text{s}$). We observed various failure modes, thereby providing further insight into process and material properties/margins. Catastrophic delamination occurred in one device, and several other units were characterized as “stuck” or “sticky,” meaning there was either no movement or the shuttle moved and remained displaced from the equilibrium position. Two of the ten devices remained functional after exposure to the specified shock levels and ultimately latched at shock levels approximately 75% of the predicted values.

We completed model verification activities and are currently fabricating a third generation of MEMS S&A hardware. The third-generation design hardware set is intended to demonstrate S&A functions within the confines of a realistic munitions configuration while exposed to simultaneous setback shock and spin environments. We will use three explosive levels in these offset gun tests, each with correlating setback acceleration and spin rates that will induce G-levels exceeding 50 kG. A soft catch of the gun round will minimize mechanical damage to the units under test due to de-acceleration of the round. Upon recovery, we will examine the devices for structural failures and overall performance.

We completed model verification activities and are currently fabricating a third generation of MEMS S&A hardware.

We performed a number of different explosive experiments that illustrate the need to provide better control of confinement, density, and quality of the explosive material. From these results we developed new diagnostic fixtures for locating, holding, and pressing the explosive materials, thereby facilitating quantitative measurements of explosive performance such as particle velocity.

In our most recent test set, we characterized the performance of the complete microfuze explosive train. In this configuration, we pressed a small amount of silver azide (0.38 mm x 0.50 mm) directly against a pellet of CL-20 (1 mm x 1 mm). We positioned this combination in turn directly above the low-voltage igniter consisting of a 200 μm titanium/boron reactive bridge. We verified subsequent detonation of the complete explosive train by measuring peak particle velocities approaching 2.42 mm/ μs , which agrees well with the particle velocities of ~ 2.6 mm/ μs found in larger slapper-initiated pellets. This test provided positive confirmation that detonation of the CL-20 pellet had occurred due to detonation transfer from the silver azide confined in a configuration that is geometrically similar to that of the final microfuze design.

38623

Automated Visual Direction of Mobile Manipulation

P. C. Bennett, T. S. Gladwell, M. J. McDonald, C. W. Wilson, R. J. Anderson

Sandia seeks to develop semiautonomous mobile manipulation technologies that enable engagement of threat devices and forces in remote environments. Most current remote-technology development for national security applications focuses on sensing and situational awareness. However, in close-quarter environments with ill-defined characteristics, the need for direct interaction with adversarial situations creates a unique need for new manipulation technologies. In addition, remote-system technologies must be capable of adapting to and engaging widely diverse threat environments if they are to be generally useful. Example environments subject to security threats include Department of Energy secure facilities, legacy production facilities containing hazardous-waste materials, Department of Defense urban conflict situations, and public environments subject to terrorism acts. All of these situations require direct engagement of devices and forces in highly controlled ways to minimize collateral damage.

Explicitly, we plan to develop modular control technologies that enable robust operation of mobile manipulators in extremely hazardous environments. We will accomplish this by reducing dependence on high-performance sensing, facilitating plug-and-play system reconfiguration, enhancing human interfaces, and providing error and damage recovery. Such remote-system concepts have eluded successful implementation in the past due to the lack of formalisms for system integration. We will build upon past advances at Sandia to provide mathematical formalisms to support rapid integration of heterogeneous capabilities into operational systems with well-characterized performance. We will extend modular architectures developed at Sandia, to include mathematically sound integration of visual and other sensor-based control approaches. In addition, we will extend these control environments to support novel vision-based human-machine interfaces and vision-based remote-systems-control approaches.

- We completed integration of camera calibration software into the visual tracking system that is mounted on the mobile manipulation platforms, and developed simple hardware

Sandia seeks to develop semiautonomous mobile manipulation technologies that enable engagement of threat devices and forces in remote environments....Explicitly, we plan to develop modular control technologies that enable robust operation of mobile manipulators in extremely hazardous environments....We will build upon past advances at Sandia to provide mathematical formalisms to support rapid integration of heterogeneous capabilities into operational systems with well-characterized performance.

that can be installed easily on the pan-tilt unit for calibration when camera replacement is required.

- We demonstrated automatic goal designation and visual tracking.

- We developed a new tracking head and installed it on the mobile robotic manipulator platforms.

- We investigated statistical pressure snakes for identification and tracking. We greatly enhanced the traditional monocular snake algorithm for use in unstructured environments by implementing a full-color snake. We demonstrated the resulting algorithm to identify and track visual targets in various lighting conditions, even in the presence of shadows across the target.

- We created interface software where the operator initiates automatic identification and tracking of the object by a mouse click on the video image.

- We demonstrated the visual servoing concept controlling both a pan-and-tilt camera unit and a mobile remote manipulator system.

- We integrated a reachable volume into the human-machine interface display for any current manipulator location and a given commanded operation (resulting in a derived position and orientation).

- We are close to achieving reachability-guided automated grasping and positioning.

The technology needed to support vision direction of mobile manipulation provided a technology base in x-ray targeting of internal components within improvised hazardous packages. Both the National Nuclear Security Administration (NNSA) and the Counterterrorism Oversight Group initiated projects with us to extend our vision-based targeting technology to targeting of internal components.

The technology needed to support vision direction of mobile manipulation provided a technology base in x-ray targeting of internal components within improvised hazardous packages. Both the National Nuclear Security Administration (NNSA) and the Counterterrorism Oversight Group initiated projects with us to extend our vision-based targeting technology to targeting of internal components.

38624

Miniature Fourier-Transform Ion-Mobility Spectrometer for Real-Time Detection and Identification of Explosives and Chemical Agents

E. E. Tarver, III, R. J. Bastasz, R. T. Jennings, M. E. Alford, K. B. Pfeifer

Ion-mobility spectrometry (IMS) is recognized as one of the most sensitive and robust techniques for the detection of narcotics, explosives, and chemical warfare agents. Increasing threat of terrorist attacks, the proliferation of narcotics, Chemical Weapons Convention treaty verification as well as humanitarian de-mining efforts have mandated that equal importance be placed on the analysis time as well as the quality of the analytical data. (1) IMS is unrivaled when both speed of response and sensitivity have to be considered. (2) The problem with conventional (signal averaging) IMS systems is the fixed-duty cycle of the entrance gate that restricts to less than 1% the number of available ions contributing to the measured signal. Furthermore, the signal-averaging process incorporates scan-to-scan variations that degrade the spectral resolution. With external second-gate Fourier-transform ion-mobility spectrometry (FT-IMS), the entrance gate frequency is variable and can be altered in conjunction with other data-acquisition parameters to increase the spectral resolution. In addition, with FT-IMS the entrance gate operates with a 50% duty cycle and so affords a seven- to tenfold increase in sensitivity. Recent data on high explosives are presented to demonstrate the parametric optimization in sensitivity and resolution of our system. In addition to parametric optimization, our design review led to modification and improvement of both the time-of-flight drift tube and the electronic gating grids to enhance performance and ease of manufacture.

The primary accomplishments to date involve modifications to the drift tube test-bed, a redesign of drift tube internal/external dimensions, complementary/alternative materials (stainless steel, aluminum) for drift tube construction, and a new electronic-gating grid design to improve manufacturability and assembly while maintaining performance. We developed a new ion-focusing drift tube design and are currently evaluating it under various parametric conditions to achieve optimum sensitivity and resolution.

The drift tube was internally redesigned to focus the ions into the most homogeneous portion of the electric field

The primary accomplishments to date involve modifications to the drift tube test-bed, a redesign of drift tube internal/external dimensions, complementary/alternative materials (stainless steel, aluminum) for drift tube construction, and a new electronic-gating grid design to improve manufacturability and assembly while maintaining performance. We developed a new ion-focusing drift tube design and are currently evaluating it under various parametric conditions to achieve optimum sensitivity and resolution.

gradient, the core. We achieved this by modifying the internal diameter of the flight tube with a two-stage design. The ionization source and the first 5 of 20 guard rings are 7.64 mm inside diameter (I.D.), while the final 15 guard rings are 14.71 mm I.D. The outside diameter (O.D.) of the separating insulators and the guard rings are all 1.0 in. Precise alignment is now achieved with a simple v-block. In addition, we redesigned the electronic gating grid that terminates the ionization and focusing segment (7.64 mm I.D. source block and the first 5 guard rings) for ease of manufacture, handling, and durability. We designed a 1.0 in. ceramic base with lithographed circuitry to facilitate bonding 10.0 μm gold wires that make up the grid. The gating grid initiates the 14.71 mm I.D., and we fabricated the 15-guard-ring separation region that terminates at the Faraday collector. We also achieved alignment of the entire ionization, separation, signal-collection system with the same simple v-block. The drift tube assembly is now constructed as a stand-alone assembly for plug-in to the detector housing.

The test-bed and drift tube design modifications led to a lighter-weight, smaller-size drift tube much better suited for incorporation into our hand-held detector. The appropriate machining and fabrication of the parts are complete. The added result is a new, more compact and functional design for the instrument enclosure. Final selection of electronic-circuit components and board design continues.

All mechanical and electronic subassemblies that have so far been selected are undergoing test and evaluation. We are evaluating further size reduction of components and ruggedized mounting of the components inside the enclosure.

Refereed

Tarver, E. E., III. 2003. External second-gate Fourier-transform ion-mobility spectrometry: Parametric optimization for detection of weapons of mass destruction. Paper presented at the International Symposium on Sensor Science, 14–22 June, Paris, France.

Other Communications

Tarver, E. E., III. 2003. External second-gate Fourier-transform ion-mobility spectrometry: Parametric optimization for detection of weapons of mass destruction. *Proc. 37th Annual IEEE International Carnahan Conference on Security Technology*, accepted.

The test-bed and drift tube design modifications led to a lighter-weight, smaller-size drift tube much better suited for incorporation into our hand-held detector. The appropriate machining and fabrication of the parts are complete. The added result is a new, more compact and functional design for the instrument enclosure.

38625

CONOPS Development for Automated Systems

M. E. Senglaub, J. J. Harrington, P. R. Klarer, D. L. Harris, E. M. Raybourn, R. G. Abbott, C. E. Lippitt

The objectives of the concept of operations (CONOPS) effort are to identify technologies and develop an architecture that permits designers and field commanders to work collaboratively to design new systems. The focus of the work is to be able to define the operational constructs for these systems in combat environments. As a result of our efforts, Sandia identified an architecture that enabled the integration of a number of optimization approaches covering the spectrum of needs in this type of systems analysis activity. We also identified cutting-edge approaches from the fields of communication and information science that enhance the ability for professionals from disparate fields to better communicate in the design and development effort. We identified a number of highly utilitarian technologies that will have significant impact on the systems engineering design process. These technologies include Pareto optimization for multiobjective problems; neural evolutionary automated topology (NEAT), an evolutionary neural net concept that should enhance the design of controllers; the use of Extensible Markup Language (XML) as an interface technology for systems analysis; and model-based programming as an approach for robustly integrating state-space technologies into the systems engineering design process. Effort also went into considering an architecture that could ultimately integrate evolutionary game theory constructs into the analysis effort. This is needed to put a more realistic spin on the evolution of optimal system and operational constructs.

We identified a Pareto optimization and designed it into a parallel structure with classic evolutionary optimization techniques to enable transitions between single- and multiple-objective optimizations. The approach is efficient and provides the systems engineer with the ability to perform a systems analysis that identifies the Pareto front in an arbitrary number of dimensions and allows the decision maker to perform what-if analyses in a post-analysis mode.

We identified NEAT technology as a very robust tool for developing and evolving system functional configurations and operational constructs. Its ability to evolve topologies and weights concurrently makes it a very powerful search technology.

The objectives of the concept of operations (CONOPS) effort are to identify technologies and develop an architecture that permits designers and field commanders to work collaboratively to design new systems. The focus of the work is to be able to define the operational constructs for these systems in combat environments....Sandia identified an architecture that enabled the integration of a number of optimization approaches covering the spectrum of needs in this type of systems analysis activity.

The latest enlightenment as a result of the effort involves the model-based programming technology introduced at the National Aeronautics and Space Administration. Implementing it into the hybrid solution methodology identified here enables a new level of optimization associated with complex design. It has been recognized that state-space approaches are superior to older design paradigms, but an efficient linking technology was undefined. Using the ideas of model-based programming provides a linkage between state-space modeling and advanced optimization technologies.

Exploration and testing of the XML constructs demonstrated a very interesting and useful approach for moving information and data between analytical algorithms and technology databases. It may also provide a basis for dynamically defining control functionality in future design development activities.

Other Communications

Senglaub, M. E. 2003. Operational analysis considerations. Paper presented at the Naval Post Graduate School, 19 March, Monterey, California.

38626

Rapid Mitigation and Decontamination of Toxic Industrial Chemicals

M. D. Tucker, R. G. Betty, J. T. Lean

Recent attention has focused on responding to terrorist events involving chemical and biological warfare (CBW) agents. Sandia's recent work on the development of the DF-100 and DF-200 Sandia decontamination technologies successfully addressed biological toxins, biological pathogens, and chemical warfare (CW) agents that traditionally have been developed for military use (e.g., Sarin, VX, and mustard). However, a more likely scenario would be for terrorists to steal readily available toxic industrial chemicals (TICs) such as anhydrous ammonia, phosgene, hydrogen cyanide, and chlorine gas for use as chemical agents. This prevents difficulties such as producing highly toxic CW agents in a safe manner, the acquisition of precursors for chemical agents that are closely monitored, and the direct handling of the agents during dissemination. In fact, the Federal Bureau of Investigation (FBI) considers the terrorist use of TICs to be more likely than the use of the traditional military-type CW agents.

The objective of this project was to develop a technology to rapidly decontaminate TICs. However, this presents a considerable technical challenge because TICs represent a set of chemicals that have vastly different properties. Some TICs, for example, are highly water-soluble (e.g., sulfur dioxide), while others are only sparingly soluble (e.g., malathion). Some must be neutralized by chemical oxidation (e.g., sulfur dioxide) or nucleophilic attack (e.g., malathion), while others must be neutralized by chemical reduction (e.g., chlorine). Therefore, the principle of this work is that we have not focused on the development of a single formulation that can detoxify all of these chemicals, but instead we have focused on the development of a small set of formulations (three) that will have the capability of detoxifying a broad range of TICs.

Development of this technology enhances Sandia's portfolio for dealing with the top six terrorist weapons of mass destruction (WMD) threats identified by the FBI. In order, these are biological toxins, TICs, biological pathogens, radionuclides, CW agents, and nuclear weapons.

We gathered data from the U.S. Department of Justice (DOJ) and the U.S. Department of Transportation (DOT) sources that identify TICs that are a terrorist threat based on accessibility, production volumes, and physical and chemical

...the Federal Bureau of Investigation (FBI) considers the terrorist use of TICs to be more likely than the use of the traditional military-type CW agents....we have focused on the development of a small set of formulations (three) that will have the capability of detoxifying a broad range of TICs. Development of this technology enhances Sandia's portfolio for dealing with the top six terrorist weapons of mass destruction (WMD) threats identified by the FBI.

properties. The DOJ, for example, has identified 21 TICs at the highest threat level, 38 TICs at a medium threat level, and 39 TICs at a low threat level. The DOT has developed a threat list that contains 24 high-threat TICs. These threat lists include irritants (e.g., sulfur dioxide and anhydrous ammonia), choking agents (e.g., phosgene and hydrogen cyanide), organophosphorous pesticides (e.g., malathion and parathion), and volatile organic compounds (VOCs) (e.g., isocyanates). The lists include both gases and liquids.

A review of the fundamental chemistry of the threat-list TICs reveals that the majority of these chemicals can be neutralized by four reaction mechanisms: (1) chemical oxidation, (2) nucleophilic attack, (3) chemical reduction, and (4) buffering. For example, 15 out of 21 TICs on the DOJ high-threat-level list can be neutralized with these reaction mechanisms. In general, there are only two classes of TICs that cannot be decontaminated using these mechanisms: (1) strong acids and bases that are best neutralized by nonaqueous technologies (such as solid bicarbonate) to avoid violent reactions that may occur when water is added to strong acids or bases, and (2) TICs that contain toxic metals (which, by definition, cannot be chemically neutralized).

We developed reactive formulations for each of the reaction mechanisms described above; the chemical oxidation and nucleophilic attack mechanisms were combined into one formulation, giving a total of three reactive formulations. The focus was on the development of foams because this gives a method to rapidly deploy the reactive formulations over large areas, which is especially applicable for use by the first responder. A summary of the three reactive foams already developed and their broad range of capabilities is listed below:

Foam A: To decontaminate TICs subject to oxidation or nucleophilic attack (e.g., malathion, sodium cyanide, phosgene)

Foam B: To decontaminate TICs subject to chemical reduction (e.g., chlorine, fluorine)

Foam C: To decontaminate TICs subject to chemical buffering (e.g., ammonia)

We selected several TICs so that the capability of each reactive foam (A, B, and C) can be verified and so that both liquid and gas decon can be evaluated. TICs tested include malathion (liquid), butyl isocyanate (liquid), sodium cyanide (solid), carbon disulfide (liquid), phosgene (gas), chlorine (gas), hydrogen cyanide (gas), and ammonia (gas). All liquid and solid tests were performed at Sandia. All of the gas-phase testing was conducted at the Southwest Research Institute

The DOT has developed a threat list that contains 24 high-threat TICs. These threat lists include irritants (e.g., sulfur dioxide and anhydrous ammonia), choking agents (e.g., phosgene and hydrogen cyanide), organophosphorous pesticides (e.g., malathion and parathion), and volatile organic compounds (VOCs) (e.g., isocyanates). The lists include both gases and liquids.

(SWRI) in San Antonio, Texas. The reactive foams were effective against all of the TICs tested.

Refereed

Tucker, M. D. 2002. DF-200: An enhanced Sandia decontamination foam for neutralization of CBW agents and toxic industrial chemicals. Paper presented at the 3rd International Symposium on the Protection Against Toxic Substances, December, Singapore, Malaysia.

38627

EM Interactions with Systems to Enhance Security

L. F. Rinehart, G. J. Denison, P. W. Cooper, L. D. Bacon, J. M. Lundstrom

In this project, Sandia will explore novel electromagnetic (EM) interactions of high-frequency (HF) radio-frequency (RF) waves that will help understand the vulnerability of circuits and systems with the goal in mind to enhance security of Department of Energy installations. One possible application is the use of RF to stop vehicles without harming their occupants. We will study and select this and other applications, and will study high-priority scenarios in detail. This project is a high-risk, state-of-the-art approach that may provide protection against many threats in different scenarios. These could include military operations, military operations in urban terrain, terrorist threats, hostage situations, and other police actions. We will devote the research to EM coupling calculations and experiments, acquiring systems that are relevant to security, and performing tests on the systems. We will enhance security by coupling EM energy to the target systems in a nonlethal manner. Thus, this improvement could be used in many environments such as facilities in urban environments.

- *RF coupling to random (blasting-cap) wires.* We produced a thorough study of RF coupling to blasting-cap wires in their full range of possible deployment orientations. Blasting caps are similar to most RF coupling scenarios; randomly oriented (with respect to the incident RF) wiring constitutes an antenna with some energy-collecting area, which delivers the collected energy to a mismatched load (the hotwire initiating element in the blasting cap).

To establish the boundaries of the RF threat to electroexplosive devices (EEDs), we performed experiments to measure RF coupling to blasting-cap wires in various configurations. We made common- and differential-mode measurements and measured common- to differential-mode conversion. We repeated each measurement in three axes and with the blasting-cap wires extended incrementally from 0 (bundled, as when new) to 2.4 m (the full extension of the wires that come with the caps).

Since only differential-mode energy couples to the blasting-cap bridgewire, this was the most pertinent measurement. Effective differential-mode energy-collecting area varied from $\sim 10^{-3} \text{ m}^2$ to $\sim 10^{-5} \text{ m}^2$ over the frequency range from 20 MHz

This project is a high-risk, state-of-the-art approach that may provide protection against many threats in different scenarios. These could include military operations, military operations in urban terrain, terrorist threats, hostage situations, and other police actions....We will enhance security by coupling EM energy to the target systems in a nonlethal manner. Thus, this improvement could be used in many environments such as facilities in urban environments.

to 3 GHz. These figures include the impedance mismatch between the wiring “antenna” and the bridgewire “load.” They include both energy that is coupled in differential mode and energy that is converted from common to differential mode.

- *Direction change.* With the completion of the blasting-cap work, we changed the direction of the project for the remainder of the year. Experiments are under way to investigate the changed emphasis. We made good progress in measuring coupling of signals on HF carriers.

38628

Adaptive Awareness for Personal and Small-Group Decision Making

C. M. Pancerella, H. H. Hirano, R. D. Kyker, S. Tucker, R. J. Malins, A. B. Doser, E. P. Parker, A. E. Speed

A number of military and civilian applications can benefit greatly from intelligent agents that can process sensor data, reason about a situation, enhance both personal and situational awareness, warn humans about situations, and act as decision-making aids. Existing environmental sensors (chemical and biological), location sensors, and health sensors provide an interesting collection of sensors that can be used by intelligent agents to recognize cues from sensor data and previous experience, warn humans of possible scenarios, and advise humans during stressful situations. By coupling sensors, secure wireless communications, and intelligent agents, Sandia will prototype an adaptive awareness, warning, and decision-making tool for use by individuals and teams in stressful chemical situations.

To realize this tool, we will develop a sensor-independent architecture for integrating self-awareness information across a distributed team and the design approaches, concepts, and software agents for a tool that supports squad-level decision making. Distributed agents coordinate to deliver both personal awareness and situational awareness. Agents reason across sensor and simulation data and communicate with other agents.

Underlying the agent reasoning will be the Recognition Primed Decision (RPD) model, which describes human decision making in real, stressful situations. The RPD model describes how human decision makers integrate information, develop cues, and learn to recognize situations based on relevant cues. The products of recognition are an understanding of goals, expectations, cues, and courses of action.

Over time, agents learn. Hence, the tool's capability will improve as information from previous attacks and expert models is used to prime the recognition capability of the chemical monitor system. Agents will create situational story lines; another adaptation of the RPD model will also use data gathered by the team.

By coupling sensors, secure wireless communications, and intelligent agents, Sandia will prototype an adaptive awareness, warning, and decision-making tool for use by individuals and teams in stressful chemical situations.

(1) We determined that this hardware/software framework is better suited for first responders than warfighters, based on new research showing cognitive states of warfighters.

(2) We collected body media data from several users and developed self-organizing maps (SOMs) to analyze these data.

- (3) We developed a new clustering algorithm for training SOMs, which requires human intervention during training.
- (4) We published a new clustering algorithm as “Decision-Aiding Algorithm for Interpreting Physiological Data in Hazardous Situations,” *Proceedings of the Fifth IASTED International Conference on Signal and Image Processing*.
- (5) We completed development of the agent framework and ported it to personal processor hardware.
- (6) We submitted a paper to The Second Institute of Electrical and Electronics Engineers (IEEE) International Conference on Pervasive Computing (PerCom 2004).
- (7) We secured real physiological data from firefighter instructors at the Fire Institute, University of Illinois, Champaign-Urbana.
- (8) We analyzed the firefighter data and used the clustering algorithm in the analysis. We developed a SOM to recognize these data.
- (9) We integrated the SOM into the agent framework.

Refereed

Doser, A. B. 2003. Decision-aiding algorithm for interpreting physiological data in hazardous situations. *Proc. 5th IASTED International Conference on Signal and Image* (13–15 August, Honolulu, Hawaii).

38629

Use of Seismic and Acoustic Responses to Assess Bomb Damage to Underground Facilities

L. C. Bartel, D. F. Aldridge, M. D. Ladd, N. P. Symons, G. J. Elbring, G. E. Sleaf, M. E. Kipp, R. E. Abbott

The precise location of the weapon explosion and resulting pressures within the target facility are critical for both bomb damage assessment (BDA) and battlefield planning. Simultaneous observations of seismic and acoustic waves coupled with state-of-the-art modeling offer the opportunity to determine detailed blast location and predict pressure regimes within buried facilities. Weapon detonation in rock produces significantly different seismic- and acoustic-energy partitioning from detonation in the void of the facility. Interior detonations produce additional variations arising from possible blast venting through facility openings. Understanding and modeling the amount of energy generated in both seismic and acoustic modes can provide critical information to determine where the blast occurred and estimate the resulting pressures within the facility. Numerical simulations utilizing an existing three-dimensional (3-D) seismic-acoustic algorithm demonstrated the capability to model these differing seismic and acoustic signatures.

Sandia seeks to develop a methodology to quantify BDA through seismic and acoustic numerical simulations and by analyzing data, both preexisting and new data collected at community experiments. Critical aspects include the inelastic behavior of the blast, its coupling into elastic- and acoustic-wave propagation models, and the acoustic-seismic coupling in the facility and at the air-earth interface. The end result will be a validated numerical capability to predict pressures within underground facilities for various bomb-drop scenarios that will be of great interest to the Department of Defense, in particular, the Defense Threat Reduction Agency (DTRA).

One of the key technical issues is to define the nonlinear-elastic boundary and use the time-dependent particle velocities on this boundary as input to a 3-D elastic-wave propagation code. We have an existing 3-D-wave propagation code to accept this input. Previously, we used the state-of-the-art Sandia code PRESTO for the nonlinear calculations. However, ongoing research into PRESTO indicates that some nonphysical periodic behavior is present in nonlinear explosive modeling. Given the apparent numerical problems with

Sandia seeks to develop a methodology to quantify BDA through seismic and acoustic numerical simulations and by analyzing data, both preexisting and new data collected at community experiments....The end result will be a validated numerical capability to predict pressures within underground facilities for various bomb-drop scenarios that will be of great interest to the Department of Defense, in particular, the Defense Threat Reduction Agency (DTRA).

PRESTO, we are looking toward using the Sandia shock-physics code CTH for the nonlinear deformation simulations. The calculations using the CTH code are under way. Substantial time and effort have been expended over the last 10 years on verification and validation of CTH results.

Another key issue is the acoustic-seismic coupling at the air-earth interface. We are treating the coupling and attenuation at the air-earth interface using a poroelastic approach; however, depending on the earth material at the air-earth interface, the poroelastic approach may not be necessary as indicated from the comparison to some actual field data. For this study, we adopted the approach of using a single Lagrangian variable to specify the material behavior at a point whether it is a porous solid or air. We are in the process of including this approach to poroelasticity in the framework of an existing code. A SAND report detailing our pragmatic approach to poroelasticity is in preparation.

The ultimate goal of this research is to use seismic and acoustic responses to estimate the pressure to access bomb damage. Our method to accomplish this goal revolves around (1) determining the explosion source location using a location algorithm, and (2) deconvolving the recorded responses to obtain the pressure on a spherical boundary surrounding the explosion. This spherical boundary is the nonlinear-linear elastic boundary. For accomplishing the first objective, we are using a grid-search algorithm; for response deconvolution, we are using an analytical model.

The source-location algorithm searches over a grid of possible source locations, while varying the source initiation time and a whole-space wave-propagation velocity, to achieve a minimum travel-time misfit. We applied the source-location algorithm to both numerically simulated data and actual field data. Even though the algorithm assumes a homogeneous whole space, the locations determined using the algorithm agreed quite well with the actual locations for cases where there is topography (both simulated and actual data). In particular, we used the acoustic responses for an actual bomb drop to locate the detonation point to within a few meters.

The analytic model that we are using to deconvolve seismic and/or acoustic responses to determine the pressure on a sphere surrounding the source assumes a homogeneous whole space where the wave speeds and density are constant. We used this algorithm to deconvolve acoustic-pressure responses and vertical particle-motion seismic velocities to estimate the pressure and/or radial stress on a sphere surrounding the source. We applied the algorithm to synthetic and actual field data.

Both the simulated and field data involved an underground tunnel complex. For synthetic data examples, the inferred pressure on a sphere surrounding the source from the deconvolved responses agrees quite well with forward-modeling results for several scenarios. For actual bomb-drop data, the deconvolved seismic traces gave reasonable values for the radial stress on a 5 m radius sphere surrounding the source. This pressure was on the order of the fracture strength of rocks.

Refereed

Aldridge, D. F., L. C. Bartel, N. P. Symons, and N. R. Warpinski. 2003. Grid search algorithm for 3-D seismic source location. Paper presented at the 73rd Annual Society of Exploration Geophysicists Meeting, 26–31 October, Dallas, Texas.

Other Communications

Aldridge, D. F. 2002. Elastic Wave Radiation from a Pressurized Spherical Cavity. Sandia Technical Report SAND2002-1882, Sandia National Laboratories, Albuquerque, New Mexico.

38655

Free-Space Electrooptic Sampling and Remote Mapping of Electromagnetic Fields from Emitting Structures Using Femtosecond Terahertz Transceivers

S. M. Cameron, T. S. Luk, F. J. Zutavern, J. V. Rudd

New optoelectronic sensor technologies are required to remotely measure spatial and temporal distributions of free-space pulsed radiation, and to probe localized electric field- and space-charge distributions in circuit and emitter structures at range. The ability to measure high-frequency field transients and the associated short-pulse-duration electromagnetic (EM) power spectrum is a critical diagnostic tool for assessing susceptibility of directed-energy weapons threats against electromechanical structures, for ultrawide-band (optical/radio frequency [RF]) cross-mode signature discrimination, and for nonresonant (direct current [DC]-terahertz) impulse ranging of EM scattering signatures. Femtosecond terahertz transceivers based on the reciprocal behavior of optical rectification (difference mixing) and the Pockels effect in a nonlinear crystal can be used to alternatively transmit an EM interrogation waveform and to electrooptically sample a perturbed return signal from a targeted component on an optical carrier. By introducing a linearly chirped optical probe pulse for mixing with the microwave field, it is possible to encode (wavelength-division multiplex [WDM]) the temporal modulation onto the baseband optical-frequency spectrum and subsequently decode (demultiplex) the waveform signature (frequency, time, space) in a single-shot measurement using spectral dispersion. Interaction kinematics will modify the broadcast pulse, and the resulting analysis can be used to externally probe an integrated circuit, spatially map radiated field patterns, or interrogate carrier dynamics of an illuminated semiconductor interface. Because the EM pulse is rectified from the intensity derivative of the optical pulse, adaptive pulse-shaping techniques can be used to produce arbitrary modulation formats to exploit coupling or enhance signatures with application to communications, tomographic imaging, and remote sensing.

Sandia recorded higher-quality signals with electrooptic (EO) sampling, including measurements with greater signal-to-noise and bipolar sensitivity. We tested many modifications or incorporated them into the EO diagnostics to improve sensitivity and bandwidth. In addition to measuring emission from a photoinduced electron-hole (e-h) plasma in gallium

The ability to measure high-frequency field transients and the associated short-pulse-duration electromagnetic (EM) power spectrum is a critical diagnostic tool for assessing susceptibility of directed-energy weapons threats against electromechanical structures, for ultrawide-band (optical/radio frequency [RF]) cross-mode signature discrimination, and for nonresonant (direct current [DC]-terahertz) impulse ranging of EM scattering signatures.

arsenide (GaAs), we also sampled the low-frequency tail (5–70 GHz) of an optical plasma breakdown source at an air-glass (BK7) and air-metal interface. These emission sources represent two fundamentally different types of plasma phenomena, both generated with a short-pulse laser (SPL) (< 2 mJ, 800 nm, 150 fs, fiber-seeded, chirped pulse Ti:Al₂O₃ regenerative amplifier). We recorded the low-frequency measurements with conventional d -dot millimeter-wave (mmW) techniques that we are extending to reach the low-frequency end of our EO sampling system for cross-calibration.

In the EO sampling system, we improved sensitivity by optimizing the alignment of the parabolic mirrors with the terahertz source and the ZnTe, EO sampling crystal, and incorporating a dielectric-coated pellicle mirror that passes terahertz and reflects optical to co-propagate the beams. We improved bandwidth (by trading off sensitivity) using a range of ZnTe crystals (thickness 0.05, 0.1, 0.2, 0.5, and 4 mm) to reduce the dispersion mismatch between the terahertz signal and the optical probe beam. We replaced crossed polarizers with balanced detection using a Babinet-Soleil compensator and Wollaston prism reducing the common mode background from random spatial scattering in the ZnTe. We improved signal optimization by automating the optical path delay to record real-time EO waveforms in 1–10 s.

Other Communications

Zutavern, F. J., J. C. Armijo, S. M. Cameron, G. J. Denison, J. M. Lehr, T. S. Luk, A. Mar, M. W. O'Malley, L. D. Roose, and J. V. Rudd. 2003. Optically activated switches for low-jitter pulsed-power applications. *Proc. SPIE* (June, Dallas, Texas).

38659

Information Assurance for Wireless Ad Hoc Networks

B. P. Van Leeuwen, F. J. Oppel, III, J. T. Michalski, W. E. Anderson, B. Hart

Wireless networks are critical to many national security systems. Commercial industry is focusing their wireless research and development efforts toward efficient routing, bandwidth efficiency, and cost-effective implementation with little emphasis on security and information assurance (IA). This research will bridge the gap between commercial efforts and government IA requirements for wireless communication networks. The Department of Energy (DOE) and other federal agencies (OFA) have critical network-centric distributed systems that depend on successful, timely, and secure wireless communications. Currently, no effective solution exists for wireless IA, resulting in severe network vulnerabilities and survivability issues, as demonstrated by the recent vulnerabilities discovered in the 802.11 wireless local-area network (LAN) standard.

This research will leverage wireless ad hoc network routing methods characterized in previous Sandia research. Subject to the networks' control-plane data requirements, we will select the most appropriate architectures to balance control-plane security with a typical scenario (i.e., distributed autonomous robotic effort), and develop and apply cryptographic and noncryptographic approaches for system IA. We will use modeling and simulation (M&S) to determine the effectiveness and scalability of the approach under the influences of wireless channel interference, impairments, and adversarial stressors. This research will build Sandia's M&S capability by integrating the OPNET (operating network) and UMBRA simulation environments with the high-level architecture (HLA). We will develop higher-fidelity network models to represent wireless networks for national security systems in difficult environments such as urban terrain.

An effective solution for the security and survivability vulnerabilities of wireless ad hoc networks will provide Sandia with an advantage in developing the network security and IA for network-centric systems being considered by DOE and OFA. In addition, the research will build on our ability to assess and improve security lifecycle of wireless systems and to predict performance of the developed approaches with an advanced simulation capability.

This research will build Sandia's M&S capability by integrating the OPNET (operating network) and UMBRA simulation environments with the high-level architecture (HLA). We will develop higher-fidelity network models to represent wireless networks for national security systems in difficult environments such as urban terrain. An effective solution for the security and survivability vulnerabilities of wireless ad hoc networks will provide Sandia with an advantage in developing the network security and IA for network-centric systems being considered by DOE and OFA.

Our research activities resulted in advances in two primary areas impacting secure wireless *ad hoc* networks. We advanced the state of the art in M&S secure wireless *ad hoc* networks. This capability allows us to evaluate system design choices and analyze design trade-offs. The M&S capability is critical to support analyses of our advances in securing wireless *ad hoc* networks with distributed certificate authorities (CAs).

The research team created a scenario in our M&S environment that demonstrates our developed system-level M&S capability. The capability interoperates the UMBRA system-level simulator with the OPNET network simulator via the HLA standard. The capability demonstrates an analysis tool that helps us get answers to critical design questions in network-centric systems that depend on timely and assured command/control information exchange among group members. The system simulation capability allows us to examine the system operation with the impacts of the selected information architecture, communication architecture, IA methods, wireless network protocols, and wireless channel. We made advancements in modeling the wireless channel in complex terrains. We developed a channel model that dynamically receives communication line-of-sight levels for each transmitting-receiving node pair and uses this value in calculating the large-scale path loss and fading characteristics of the channel. This channel model increases the fidelity of our simulations in scenarios that include urban terrains. For simulation run-time reductions we created models to represent the *ad hoc* routing and simple channel effects that run in UMBRA without co-simulating the network simulator. This results in lower-fidelity simulation outputs but is useful in quick-turnaround “what-if” cases.

In addition, our research resulted in advances in the area of IA in wireless *ad hoc* networks. Our primary contribution includes two advances to facilitate a distributed CA approach in wireless *ad hoc* networks. Our first advance is a method that employs verifiable secret shares (VSS) to discover compromised nodes that attempt to disrupt network operation by contributing bogus certificate shares in a network with distributed CAs. The approach assumes the certificate shares are valid until an invalid certificate is generated and thus can be more efficient than current implementations. A node will expend the necessary resources to verify each certificate share only after an invalid certificate is generated. Our second advance is a method that uses a controlled group cast to control the depth of propagation of a certificate share request. This method adaptively controls the number of nodes that receive a

Our research activities resulted in advances in two primary areas impacting secure wireless ad hoc networks. We advanced the state of the art in M&S secure wireless ad hoc networks. This capability allows us to evaluate system design choices and analyze design trade-offs. The M&S capability is critical to support analyses of our advances in securing wireless ad hoc networks with distributed certificate authorities (CAs). ...In addition, our research resulted in advances in the area of IA in wireless ad hoc networks. Our primary contribution includes two advances to facilitate a distributed CA approach in wireless ad hoc networks.

request for a certificate share. As the density of nodes that can contribute a certificate share varies, the method adjusts the number of hops the request is propagated to, resulting in more efficient use of the network's scarce resources.

38669

Hybrid Infrastructure Cryptography

M. D. Torgerson, W. D. Neumann, R. C. Schroeppe, M. J. Collins, D. L. Harris, T. J. Draelos, C. L. Beaver

In resource-constrained environments such as ad hoc wireless networks, existing cryptographic protocols are not suited to the security needs of the environment. Symmetric key protocols provide bandwidth and computationally efficient security solutions; however, they are difficult to manage and require an increased level of end-to-end security. Public key protocols make key management in large networks possible, but they are both computationally and bandwidth intensive. These public key protocols also require a large support structure to operate. Diffie-Helman-type key-exchange algorithms are an attempt to bridge the gap between public and symmetric key techniques. These types of key-exchange algorithms are orders of magnitude too slow to use in a dynamic environment. No cryptographic technology currently exists to provide scalable, real-time security for large dynamic networks.

Sandia investigated the possibility of merging the two types of protocols to provide a new type of cryptographic infrastructure, thus striking a balance between the two extremes. We found a number of significant advances in both public key and symmetric key technologies. These advances led to spin-off research efforts, a patent, and several publications. We also developed a modeling tool to test the efficiency of various cryptographic protocols to be applied to a variety of network situations.

We developed an extensive list of new cryptographic technologies. To turn these new techniques into a viable product, we focused efforts on an extensive review and analysis of the techniques, their implementation to verify predicted functionality, and refinement as necessary.

We developed and extensively analyzed a new method of speeding up existing Discrete Log-type digital signatures and key-exchange algorithms, yielding a speed-up factor of between eight and nine times for a standard implementation of digital signal algorithm (DSA)-type signature. The new method requires a minimal amount of secure storage as compared to the possibly tens of thousands of bytes required for competing methods. We filed a patent on the new method and incorporated it into the hardware design of a Sandia-developed low-power authentication chip and into Sandia's Cryptographic Library. Outside technical papers are to follow.

Sandia investigated the possibility of merging the two types of protocols to provide a new type of cryptographic infrastructure, thus striking a balance between the two extremes. We found a number of significant advances in both public key and symmetric key technologies. These advances led to spin-off research efforts, a patent, and several publications. We also developed a modeling tool to test the efficiency of various cryptographic protocols to be applied to a variety of network situations.

We developed and analyzed an efficient method of extending one-time public key signatures to r -time signatures without the reduction in security typically noted with such extensions. Our implementations of these signatures show a 100-fold speed-up over many typical public key signature methods. As a hybrid between symmetric and public key methods, this r -time scheme has many functional qualities of both types of signatures. The largest drawback is a somewhat greater transmission overhead. Outside technical papers are in preparation.

We devised a verifiably secure block cipher with many of the security benefits of cipher-block-chaining, but without the computational drawbacks. The method is parallelizable and pipelinable, and has an extremely small hardware footprint. In addition, it combines a virtually free authentication step. Even though this technology has great potential, pursuit of it did not meet the objectives of this research. As such, it was handed over to a much more suitable Sandia research effort. Since the hand-off, the method has been refined and extended to a new mode of cipher operation. Initial efforts have begun to include it in various standards.

One concern about hybrid cryptographic methods led to the question of the applicability of side-channel attacks. This effort produced a survey of such attacks.

Because of the project's examination of various simple networks and their trust requirements, we developed a method of obtaining efficient private channels within a private network. Our subsequent analysis revealed the security bounds for the method. We found that the method can be applied only in situations where the communication system has very tight management of data throughput.

We developed a network-modeling tool that allows testing and comparison of various security algorithms in various network models. This tool allows for the validation of our estimation on the computational efficiency of cryptographic protocols. It also allows measurements of the security-driven communication bottlenecks. We completed this second functionality for a limited number of network topologies. Overall, the performance measures of our developed protocols were within our prediction estimations and have proven to be competitive from a computational standpoint.

We investigated the possibility of combining symmetric and public key techniques. In the process, we discovered a number of technologies that separately enhance public key and symmetric key cryptography. In the r -time signature schemes there is a combination of both. We believe that this hybrid area

We developed and analyzed an efficient method of extending one-time public key signatures to r -time signatures without the reduction in security typically noted with such extensions. Our implementations of these signatures show a 100-fold speed-up over many typical public key signature methods. As a hybrid between symmetric and public key methods, this r -time scheme has many functional qualities of both types of signatures.

is still rich in undiscovered technologies. Further discoveries may yield significant performance enhancements in resource-constrained environments.

49915

Critical Technology Development for Hard Target Defeat High-G-Tolerant Fuze and High Explosives

C. L. Smithpeter, R. S. McEntire, S. M. Harris, M. W. Pilcher, P. D. O'Malley, S. N. Greene, L. S. Weichman, E. J. Welle

The primary purpose of this project is to accelerate technical maturity for high-gravity (high-G)–tolerant intelligent fuzing, high-explosive (HE) fill, and the penetrator-bomb housing. Sandia will accomplish this objective through a series of concurrent design, fabrication, and testing of fuzing, HE, and penetrator technologies guided by modeling and simulation in high-G environments. The technical challenge for fuzing is developing the electronics for weapon safety/function and the mechanical materials/structures to survive a high-speed impact generating in excess of 20 kg. The challenge for the HE fill is to not initiate in the impact, yet maintain integrity for reliable function at the desired time. The penetrator challenge is to provide sufficient strength to survive a 20 kg impact at high speed.

- *Fuzing.* We reviewed our arming safety design with the Army fuze-safety review board, who found a number of potential issues. We revised the design to correct these issues, which also increased the flexibility of the design to future requirements. We assembled two fuzes into a penetrator and fired them from a gas gun into concrete targets to demonstrate impact-shock survival. Both fuzes survived and functioned through a 6 kg impact lasting 4 ms. Subsequently, we fired a fuze in a penetrator case into a hardened concrete target on a sled-track test. The fuze survived the impact but failed to record the impact profile. In a follow-up engineering investigation, we identified a low-battery condition as the most likely failure mode but could not definitively identify the failure. The fuze did survive the sled track and was fully functional post-test, which was one of the test objectives.

- *Explosive charge.* The goal of the explosive train work is to develop a detonator, booster, and main charge capable of reliable operation and survival at high-G levels. The objective of the detonator work is to evaluate the detonator performance (flyer velocity and shape) using a design of experiments (DOE) (varying flyer thickness, charge cavity diameter, charge column height). The DOE matrix results indicated that any of the detonator designs would initiate a plastic-bonded explosives (PBXN)-5 booster. We chose PBXN-5 as the best booster

The primary purpose of this project is to accelerate technical maturity for high-gravity (high-G)–tolerant intelligent fuzing, high-explosive (HE) fill, and the penetrator-bomb housing. Sandia will accomplish this objective through a series of concurrent design, fabrication, and testing of fuzing, HE, and penetrator technologies guided by modeling and simulation in high-G environments.

explosive because of its high-output pressure, mechanical strength, and initiability. Due to uncertainties in the CTH (a shock-physics code) modeling and concerns about damaging the fuze, we decided to abandon the cylindrical booster and pursue a hemispherical booster. We are subjecting the laser-explosive (LX)-17 main charge to two sets of tests: initiation and mechanical survival. Since CTH modeling indicates that our smallest booster is at least twice the diameter needed to reliably initiate LX-17, we will direct our initiation testing at validating the CTH results. The recent sled-track impact within the penetrator demonstrated that the HE charge will survive a high-G impact, in particular, not fracturing.

- *Penetrator.* We increased the scale of the Monolithic Ballasted Penetrator (MBP). In this effort, we uncovered new issues not encountered in the prototype castings. Although we were able to address the issues of gas evolution by experimenting with various ceramic compositions, the issue of hot tearing and shrinkage for the full-scale mold remains to be addressed. We decided to transition to a welded design because the tearing and shrinkage problems could not be addressed with the existing budget and schedule. The new welded mates rough-machined the forward and aft sections into a penetrator. A Hot Isostatic Press (HIP) fabrication process forms the machined and welded casing around the tungsten ballast. The HIP process also repairs any tears in the material, thereby improving the quality and uniformity of the material. We successfully demonstrated the HIP process. In addition, an early welded version of this penetrator impacted into a hardened concrete target at supersonic speeds from a rocket sled. The welded penetrator survived impact and achieved the desired penetration performance in a sled-track test. The sled-track impact also demonstrated the function of compression pads that allow thermal expansion and contraction as well as maintain HE contact with the detonator during impact.

52577

Immunological Basis for High-Reliability Systems Control

W. A. Amai, E. A. Walther

Software in various real-time control systems is typically reactive to error conditions as they occur, and handling these error conditions is usually solely up to the creativity and vision of the software designer or the expertise of the operator. A recent and growing body of computer immunology research has focused on the security of general-purpose operating systems. This project begins the research into immune response for control systems, where the response must occur in real time, and the system must keep running to manage real-time events. An immune system applies a two-phased approach to protection. First, it learns normal system behavior. Then it monitors for anomalous behavior, and if abnormal behavior is detected, the immune system activates an autonomic response based on the severity of the behavior. Such an immune system is distinguished from a traditional exception-handling mechanism in its ability to learn new pathogens. An integral immune system ensures high reliability of a control system by enabling it to maintain operation without operator intervention. The first year of the proposed research establishes implementation ground rules for an immune system on a real-time control system and demonstrates such a system. In future work, we propose to investigate a distributed immune system that itself is resistant to corruption and can mount a noncentralized response to anomalies.

We completed the construction of the test-platform hardware, including a SandDragon robotic vehicle, radio box, and operator control unit. We ported the existing robot control software, support libraries, and development environment to Linux, and verified correct function against the original software. We designed and implemented an immune system by patching the Linux kernel with an interface monitor and adding a response program. We developed a graphical control program to use on the operator control unit for communicating with the response program, managing the experimentation process, and collecting experimental data. We developed a test plan and began executing that plan by experimenting with the platform and immune system to develop profiles of normal control-system behavior under differing operational conditions. The exciting result of these experiments was that anomalous behavior in the multithreaded control program could indeed be

This project begins the research into immune response for control systems, where the response must occur in real time, and the system must keep running to manage real-time events.

detected by the immune system. We defined a list of graduated responses to system anomalies and implemented one of the automatic responses.

We proved our hypothesis that interesting system behavior can be captured for a real-time control program, using an immune system originally for computer security but extended to the domain of real-time control. Automatic detection and response allows greater system reliability to be achieved by decreasing the need for monitoring and intervention by a human operator.

We proved our hypothesis that interesting system behavior can be captured for a real-time control program, using an immune system originally for computer security but extended to the domain of real-time control.

52579

Miniaturization of SAR Electronic Assembly Using Sandia's Integrated Substrate Technology

R. Chanchani, G. D. Peterson, M. Armendariz, K. McGuire, R. B. Hurley, K. Norman, D. Bethke, T. A. Fischer, D. J. Rieger

Currently, the substrate technology of choice for synthetic-aperture radar (SAR) electronics is low-temperature co-fired ceramic (LTCC). However, LTCC technology by itself will be inadequate for the next generation of SAR, which is expected to be further miniaturized (5–30 lb) with higher operational frequencies (> 15 GHz). The drawbacks of LTCC substrate technology are its relatively large minimum feature size (100 μm), poor dimensional tolerances (± 250 $\mu\text{m}/\text{in.}$), and limited capability for embedding passives. Sandia proposes to further LTCC technology by combining it with our integrated substrate technology (IST) made of a multilayer stack of benzocyclobutene (BCB) polymer dielectric with copper (Cu) conductors. IST technology is capable of high-density interconnect structure (minimum feature size of 25 μm), better dimensional tolerances (± 2 μm), and incorporation of a wider range of embedded passive components (radio-frequency [RF] filters). The combination of LTCC technology and IST technology will benefit from the best attributes of both technologies. When demonstrated, this technology would also be applicable to a wide variety of emerging threat-related applications such as microtags, microtransmitters, distributed wireless sensors, and integrated network systems.

We completed the fabrication of a test vehicle containing the critical features of a SAR circuitry so that RF performance of this technology could be characterized. The RF electrical tests indicated that BCB can produce high-frequency transmission-line components with an operating frequency range in excess of 20 GHz. However, to match impedance of the intended designed values with the measured values, the design rules need to be modified.

We made the following accomplishments:

(1) *Completed test-vehicle fabrication.* This test vehicle contains SAR circuit structures like stripline and microstrip filters, cross-talk, coupled resonators, insertion losses, and 3 dB and 6 dB attenuators. The module design involves five Cu conductor layers and four BCB dielectric layers. Two bottom layers are 20 μm -thick BCB layers (non-photodefinable), and two top layers are 5 μm -thick BCB layers (photodefinable). We

Sandia proposes to further LTCC technology by combining it with our integrated substrate technology (IST) made of a multilayer stack of benzocyclobutene (BCB) polymer dielectric with copper (Cu) conductors....The combination of LTCC technology and IST technology will benefit from the best attributes of both technologies. When demonstrated, this technology would also be applicable to a wide variety of emerging threat-related applications such as microtags, microtransmitters, distributed wireless sensors, and integrated network systems.

encountered two main processing issues during fabrication of the substrate. The 20 μm BCB layers, which were non-photodefinable, were prone to delamination, and we had to develop special process steps to avoid these defects. The design layout of the embedded termination resistors was not optimum and requires a redesign.

(2) *Built and characterized embedded inductors with 3 μm -thick Cu.* The best-quality (Q) value we obtained was 42. This Q value is higher than the Q value of 30 obtained with 2 μm -thick Cu. The results show that the performance of inductors, which is critical for SAR circuitry, can be further optimized.

52580

Moving-Target Identification Using Ultrahigh-Range-Resolution Data

J. S. Salazar, M. W. Koch, D. W. Harmony, J. A. Hollowell

Locating, tracking, and identifying moving targets during battle are crucial for military success. Recent conflicts have shown that stationary battlefield vehicles are rarely in the open. Conventional two-dimensional (2-D) synthetic-aperture radar (SAR) imaging is ineffective against moving vehicles. Alternately, 1-D high-range-resolution (HRR) profiles can be formed when a vehicle is moving, and in a fraction of the time needed to produce a SAR image.

Ground moving-target indication (GMTI) can be reliably performed using long-standoff radars. The possibility exists that HRR profiles associated with GMTI can be used to identify moving targets. However, using HRR profiles poses new and formidable challenges to target identification. The limited information content represented in HRR profiles combined with other HRR characteristics further complicates the inherent difficulties in automatic target recognition (ATR).

Sandia proposes using ultrahigh-range-resolution (UHRR) profiles as the basis for our moving-target identification research. Our first effort is to extract stable features from UHRR data that can be exploited in multilook 1-D ATR algorithms. We will use multiple UHRR profiles to compensate for the limited target information in a single HRR profile. We believe that accruing a moving-target hypothesis by combining robust match metrics on multilook UHRR features will lead to successful moving-target ATR algorithms.

This research applies robust 1-D template-based ATR approaches for evidence acquisition, followed by evidence accrual using a sequential probability ratio test (SPRT). This approach is geared toward combining and exploiting information from multiple radar “looks” at a target, and thus produces higher-confidence identification calls that would not typically be possible with single-look HRR or UHRR approaches.

We showed how using the SPRT allows us to combine multiple HRR looks to identify target vehicles at low error rates. In effect, the SPRT pursues a gathering and combining of evidence from target observations only as long as the statistical test has a value between the upper and lower stopping boundaries, A and B, respectively.

Sandia proposes using ultrahigh-range-resolution (UHRR) profiles as the basis for our moving-target identification research....This research applies robust 1-D template-based ATR approaches for evidence acquisition, followed by evidence accrual using a sequential probability ratio test (SPRT). This approach is geared toward combining and exploiting information from multiple radar “looks” at a target, and thus produces higher-confidence identification calls that would not typically be possible with single-look HRR or UHRR approaches.

Once the test goes above A or below B, the classifier makes a decision and uses no more observations. These upper and lower stopping boundaries are determined by the desired false-alarm error rate and the desired missed-detection error rate. We also developed and/or applied various extensions to the SPRT for handling the unknown class, composite hypotheses, dependent data, and contaminated target signatures. This is a unique capability of approach and an important one in that these problems appear in many sequential pattern-recognition (PR) problems.

This research leverages two PR tests adapted for 1-D target-identification applications under a previous effort. We use these tests for matching stored templates of targets to HRR profiles. One test is based on a mean-square error (MSE) metric, and the other is based on a multinomial pattern-match (MPM) metric. While there is some correlation between the MSE-based and MPM-based tests, we showed that there is enough independence to give improved performance when fusing the MSE and MPM results. This shows how the SPRT framework can be used to solve multiple layers of data fusion.

We demonstrated our approach using range-Doppler data of moving vehicles collected by the Veridian/ERIM Corporation's data-collection system (DCS) for the Defense Advanced Research Projects Agency's (DARPA's) Moving Target Feature Phenomenology (MTFP) Program. Theoretical results allowed us to estimate the average number of observations needed to make a decision and verify the statistical models. The results showed that we can fuse information from multiple HRR looks and different match metrics to produce a high-confidence decision.

We presented algorithms for identifying HRR vehicle sequences. We based these algorithms on the SPRT, which takes a stream of observations and classifies the stream as pertaining to a target or a nontarget. Modifications of the SPRT allow contaminated target signatures and dependent observations. The desired error rates determine the SPRT's upper and lower decision boundaries. From this property, we developed a method of computing the confidence of a decision. We also used power analysis to develop statistical models of the worst-case nontarget class. Importantly, this approach does not require training with every possible nontarget that will be seen by the sensor.

The results of this research represent new and important steps toward an HRR and UHRR ATR capability that is much needed in battlefield scenarios. These results combined previous research done at Sandia with newly developed

The results of this research represent new and important steps toward an HRR and UHRR ATR capability that is much needed in battlefield scenarios. These results combined previous research done at Sandia with newly developed capabilities to further advance the state of the art in the moving-target ATR problem using HRR and UHRR data.

capabilities to further advance the state of the art in the moving-target ATR problem using HRR and UHRR data.

Refereed

Koch, M. W., J. S. Salazar, and D. W. Harmony.
2003. Vehicle identification using high-resolution-range profiles and the sequential probability ratio test. Paper presented at the Military Sensing Symposia on Sensor and Data Fusion, June, San Diego, California.

52581

Advanced Mobile Networking, Sensing, and Controls Using Graph Theory

J. T. Feddema, B. P. Van Leeuwen, P. R. Wolfenbarger, D. E. Small, M. A. Kuehl, C. L. Lewis, L. S. Harvey, J. J. Harrington

This project will advance the state of communication, sensing, and control for mobile distributed systems by taking an integrated approach. Sandia will use graph theoretic methods to analyze the input/output reachability and structural controllability and observability of a decentralized system. Embedded in each node, this analysis will automatically reconfigure an ad hoc communication network for the sensing and control task at hand. We will also use the graph analysis to create the optimal communication flow control based on spatial distribution of the network nodes. Edge-coloring algorithms tell us that the minimum number of time slots in a network is equal to either the maximum number of adjacent nodes (or degree) of the undirected graph or the maximum degree plus one. Therefore, the more spread out the nodes are, the fewer the number of time slots needed for communication, and the smaller the latency between nodes. In a coupled system, this results in a more-responsive sensor network and control system. We will develop network protocols to propagate this information, and we will develop distributed algorithms to automatically adjust the number of time slots available for communication. In addition, we will develop information-assurance methods compatible with these protocols to support operation in an environment where adversaries may attempt to disrupt service. These protocols and algorithms must be extremely efficient and updated only as network nodes move. We will analyze the efficiency by analytical and simulation techniques and implement these algorithms on multirobot systems already in use at Sandia.

We developed a decentralized software algorithm for determining the optimal time-slotting and flow control of a large spatially distributed Time-Division Multiple Access (TDMA) mobile network. We embedded the software in Sandia's network robot (Netbot) vehicles, and we are in the process of simulating the algorithms in QualNet and implementing the same software on our Robotic All-Terrain Lunar Exploration Rover (RATLER) vehicles. The software uses local information from its nearest neighbors to build a graph of the network, and a distributed coloring algorithm to determine the order in which a node may communicate. From

Netbot vehicles forming communication network.

This project will advance the state of communication, sensing, and control for mobile distributed systems by taking an integrated approach.

this graph, we are also able to determine the observability of the sensor network and the controllability of mobile nodes. We compared the algorithm to Collision Sense Multiple Access (CSMA) and time-slotted linear and polylogarithmic algorithms. For a network of 10,000 nodes, a colored TDMA network will have a communication delay across the network that is a factor of 800x smaller than a linear broadcast network. We also found that the overhead associated with coloring when nodes move is approximately equal to the communication delay across the network (e.g., approximately 4 s for 10,000 nodes spread out over a 50 x 50 mi area and each radio having a 1 mi communication radius).

We also made progress in understanding the trade-offs between communication and control. In collaboration with Santa Clara University, we learned how to solve for the system stability using linear matrix inequalities, a convex optimization technique. This technique is more general than the previous vector Liapunov method that we were using, and we believe that it can be parallelized for even more-efficient computation over a network.

Other Communications

Feddema, J. T., R. D. Robinett, and R. H. Byrne. 2003. An optimization approach to distributed controls of multiple robot vehicles. *Proc. IEEE/RSJ International Conference on Intelligent Robots and Systems, Workshop on Control and Cooperation of Intelligent Miniature Robots* **1** (31 October, Las Vegas, Nevada): 1–16.

Schoenwald, D. A., and J. T. Feddema. 2002. Stability analysis of distributed autonomous vehicles. *Proc. IEEE Conference on Decision and Control* **1** (December, Las Vegas, Nevada): 887–92.

52582

Compact Terahertz (THz) Sources for Emerging Threats Applications

A. Mar, G. A. Vawter, J. R. Wendt, F. J. Zutavern, M. W. O'Malley

This project will develop options for compact sources of electromagnetic (EM) radiation in the so-called "THz gap" of the EM spectrum for covert communications and directed energy. This regime is very attractive for covert applications because of the lack of readily available instrumentation and the potential compactness of highly directional transmitters. Secure communications at terahertz (THz) frequencies could employ strong absorption lines in atmospheric propagation to confine the range of potential interception, as required, for example, by the future combat system (FCS). The highly directional nature of THz radiation could also be used to enhance disruption effects on radio-frequency (RF) communications (a concept we have demonstrated at microwave frequencies) and other RF electronics. Compact and relatively inexpensive sources will also be required for large-scale deployment of THz-based technologies such as imaging devices for homeland defense.

Currently, THz research typically involves the use of large and costly laboratory femtosecond-laser systems. Sandia will develop heterodyned continuous-wave (CW) lasers and harmonic mode-locking of diode lasers to generate THz with compact systems of turnkey simplicity. We will combine such new compact optical sources with photoconductive semiconductor switch (PCSS) technology for THz generation and detection.

THz technology has direct implications for many applications involving miniaturized high-voltage electronics, such as neutron generators, radars, high-power microwave (HPM) systems, lasers, and others. Imaging based on THz radiation (t-rays) could be used for inspection and qualification of weapon components, such as neutron tubes and firing sets. T-rays penetrate through nonconducting materials such as those used in high-voltage potting and image materials by the variation of the complex dielectric constant. T-ray images are thus complementary to x-rays, whose image contrast is provided by the atomic number of the materials imaged.

We demonstrated mode-locked diode lasers at the fundamental and second harmonic, obtaining repetition rates of ~ 20.6 GHz and ~ 38.5 GHz from nominally identical cavity lengths. A centered saturable absorber induces the second harmonic (CPM [colliding pulse mode locked]), as opposed to

THz technology has direct implications for many applications involving miniaturized high-voltage electronics, such as neutron generators, radars, high-power microwave (HPM) systems, lasers, and others.

Imaging based on THz radiation (t-rays) could be used for inspection and qualification of weapon components, such as neutron tubes and firing sets. T-rays penetrate through nonconducting materials such as those used in high-voltage potting and image materials by the variation of the complex dielectric constant. T-ray images are thus complementary to x-rays, whose image contrast is provided by the atomic number of the materials imaged.

the facet absorber for the fundamental. We measured linewidths on the order of 10 KHz. We will generate higher frequencies by using shorter cavities, but we did the initial demonstration at < 50 GHz so we could use a high-speed photoreceiver and millimeter-wave spectrum analyzer.

We established the fabrication process for THz mode-locked lasers, involving the following steps: (1) epitaxial growth, (2) slot etch for intracavity reflectors (ICRs), (3) deposit oxide and benzocyclobutene (BCB), (4) oxide and BCB patterning, (5) rib waveguide etch, and (6) contact metal, wafer lapping.

We installed the new Chemically Assisted Ion Beam Etching (CAIBE) tool for dry-etched ICRs. This is a critical tool for the fabrication of ICRs.

- A broad energetic ion beam is used with a local partial pressure of reactive gas to achieve highly anisotropic etched profiles.
- Separation of the ion flux and reactive species provides exquisite control over vertical and lateral etch profiles.
- Stage tilt with sample rotation adjusts sidewall angles where vertical walls cannot be achieved at normal incidence.

We designed new mask sets for this laser structure that include the following:

- CPM configuration, $300\text{ }\mu\text{m}$ cavity length ~ 280 GHz repetition rate (second harmonic)
- Two-absorber CPM configuration, $300\text{ }\mu\text{m}$ cavity length ~ 420 GHz repetition rate (third harmonic)
- CPM with combined ICR/absorber, two-absorber CPM configuration, $300\text{ }\mu\text{m}$ cavity length
- ICR coupled-cavity laser ICR configuration with facet absorber, main cavity length = $300\text{ }\mu\text{m}$, etched cleave mark defines coupled-cavity length, cleave positions placed for $N=2$ (280 GHz), $N=5$ (560 GHz), and $N=13$ (1.68 THz).

We also developed a full set of tools for microelectronic packaging, including die pick and place, wafer scribe, and wire bonder.

52583

Understanding Communication in Counterterrorism Crisis Management

M. M. Johnson, R. Tam, P. D. Hough, D. D. Djordjevic, A. S. Yoshimura, J. C. Forsythe, M. L. Bernard

In response to terrorist attacks, joint decisions are required by multiple agencies under conditions of high stress. Teams with diverse membership face issues such as short time cycles, high stakes, incomplete data, and conflicting interests. Weapons-of-mass-destruction (WMD) terrorism exercises have pointed out that communication barriers between organizations impede an effective response. In the WMD Decision Analysis Center (WMD-DAC), Sandia is using distributed computer simulation and visualization tools to address issues surrounding terrorist attacks. Simulations provide a means to explore WMD terrorism defense through interactive, dynamic, "what-if" computerized war-gaming. Traditional Department of Defense (DoD) distributed simulations are based on distributed interactive simulation (DIS) or high-level architecture (HLA) specifications. These simulations rely primarily on two communication paths: (1) electronic exchange through DIS/HLA interconnected machines running loosely coupled, federated computer models, and (2) participant-participant and participant-machine interactions between participants playing distinct roles. This second category of communication has a large impact on the outcome of decisions made as part of the simulation. Currently, participant-participant and most participant-machine interactions are not captured in these exercises. Sandia's Enterprise Modeling Architecture (EMA) supports distributed, multiparticipant simulation using HLA and provides a unique distributed architecture with need-to-know (NTK) controls. The EMA allows control of information flow and also control of what is revealed and known to multiple, geographically dispersed participants. Participants are allowed to see a controlled view of the simulation, based on their agency's role. Sandia proposes to incorporate communication measurement into our simulations by monitoring participant-participant and participant-machine communications as part of the HLA-simulation data stream. We will require participants representing different agencies to use communication portals provided by the EMA-based WMD-DAC environment. This project will develop the capability to monitor the quantity and quality of interagency communication during interactive simulations in the WMD-DAC, thus increasing its value for WMD terrorism preparedness.

This project will develop the capability to monitor the quantity and quality of interagency communication during interactive simulations in the WMD-DAC, thus increasing its value for WMD terrorism preparedness.

- *Human communication*

(1) We completed a literature survey of existing group decision and communication research.

(2) We benchmarked relevant team communication and decision models for quantifying how people interact in a team environment.

(3) We developed an extended communication assessment and evaluation model based on Robert Bales' Interaction Process Analysis (IPA) and the Klein Cognitive Task Analysis methodologies.

- *Scenario development*

(1) We interviewed domain experts, including California and New Mexico public health officials, operators, and managers from emergency operations centers for several international airports in the San Francisco Bay Area, and WMD first responders.

(2) We developed partnerships with existing Sandia projects, including the Sandia Borders Grand Challenge project.

(3) We developed scenario extensions for two biological-attack detection and response simulations around urban-area- and facility-based anthrax releases. We defined roles and joint decision points for inducing the high-stress environment targeted in this project.

(4) We held two external simulation-driven tabletop exercises that employ facility and urban-area response strategies for the San Francisco International Airport and the Alameda County Public Health Department.

- *Technology development*

(1) We completed a requirements analysis and design of digital communication mechanisms including chat, e-mail, virtual fax, text-to-speech, and speech-to-text.

(2) We implemented and integrated chat, virtual e-mail, and text-to-speech functionality.

(3) We completed a prototype implementation of speech-to-text capability.

(4) We completed a requirements analysis of the HLA Federation Object Model (FOM) for e-mail, chat, and virtual fax integration into the simulation communication stream.

(5) We completed a requirements analysis of data archive and retrieval mechanisms for storing digital communication artifacts.

52584

Hypervelocity Impact-Generated Flash

R. J. Lawrence, J. E. Bailey, W. D. Reinhart

Kill assessment continues to be a major issue for the nation's missile-defense program. In the most relevant scenarios, incoming targets are intercepted with kill vehicles at closing velocities of 8–15 km/s or more. Impact flash offers the potential of near-instantaneous kill assessment for these types of engagements. This project is establishing the feasibility and credibility of using impact flash in this role. Typically, this problem requires the identification of the source materials and their post-impact state at times as soon after the engagement as possible. Analysis of the radiative output from the hypervelocity-impact debris provides the desired mechanism. The visible, ultraviolet (UV), and infrared (IR) signals associated with the impact flash are dependent on the impact velocity and the materials of both the impact and the target, and offer the potential for providing these data. However, we are only now beginning to systematically study these phenomena at the required impact velocities.

Two unique facilities at Sandia are capable of achieving the required impact conditions: the three-stage gun (impacts at up to 16 km/s) and the Z machine (magnetically driven flyers at ≤ 28 km/s). With these two approaches, we can achieve operational parameters for missile-defense engagements and improve our chances of successfully achieving the project goals. Further, we will be able to look at new synergistic phenomena related to hypervelocity impact (e.g., momentum enhancement, the behavior of warm-dense matter) at even higher loading levels—regimes that have never been quantitatively investigated.

Two unique facilities at Sandia are capable of achieving the required impact conditions: the three-stage gun (impacts at up to 16 km/s) and the Z machine (magnetically driven flyers at ≤ 28 km/s). With these two approaches, we can achieve operational parameters for missile-defense engagements and improve our chances of successfully achieving the project goals. Further, we will be able to look at new synergistic phenomena related to hypervelocity impact...at even higher loading levels—regimes that have never been quantitatively investigated.

Impact flash spectra from Z for aluminum-on-aluminum impact at 25 km/s.

This project is developing, testing, and analyzing diagnostic techniques to measure the time variation of hypervelocity-impact-generated flash on both the Z accelerator and the three-stage light-gas gun. Characteristics include intensity, spatial and temporal variation, and spectral distribution in various wavelength regimes. We are considering both continuous and line spectra.

The goals for this project were to (1) adapt Z-based spectroscopy diagnostics for impact-flash measurements on Z and demonstrate that these measurements could be made, (2) transfer to and develop similar spectroscopy diagnostics for the three-stage gas gun at the Shock Thermodynamics and Applied Research (STAR) facility and demonstrate the successful employment of these diagnostics, and (3) demonstrate the capability for theoretical and numerical modeling of hypervelocity-impact events and spectrally resolved flash output characteristics. We successfully accomplished all of these goals.

We obtained two opportunities for “piggy-back” experiments on hypervelocity-flyer development shots on the Z machine. On the first shot, we obtained an impact-flash spectrum for a 25 km/s aluminum (Al)-flyer impact on an Al target. We obtained two additional spectra from impacts at ~ 24 km/s, but these spectra have yet to be fully reduced or analyzed. They were for Al-on-Al and Al-on-quartz configurations.

We modeled the first Z experiment in two spatial dimensions with the multidimensional hydrocode ALEGRA. We processed the output with the spectral-analysis code SPECT3D. Nonetheless, the numerical models demonstrated the capability of simulating the impact-flash phenomena; we will achieve refinements with further analysis.

We installed a new target chamber on the gun. This will reduce potential contamination issues that could compromise the gun-based spectral measurements, and because of its larger size, will extend the experimental read-time before the debris interacts with the chamber walls. To provide spectral diagnostics on the gun, we procured an optical multichannel analyzer (OMA) and associated spectrometers and installed them at the facility. As part of the set-up and installation procedures for this equipment, we conducted several shots using Al flyers impacting various targets at velocities approaching 6 km/s. One of those targets was indium, which we are considering as a surrogate sample material for uranium. We obtained impact-flash spectra from that shot, showing that gas-gun tests can now be used in this mode.

We consulted with other Sandia groups and are planning small collaborative efforts to assist with spectral analysis and the data reduction required for material identification and impact-engagement analysis. Our projections for this effort led to considerable interest in the Department of Defense community, in particular the Missile Defense Agency. Although dependent on the results of this project, related support is likely. Additional collaborative work with Lawrence Livermore National Laboratory, which will involve flash measurements at longer spectral wavelengths and at later times after impact, will probably come to fruition in upcoming work.

Our projections for this effort led to considerable interest in the Department of Defense community, in particular the Missile Defense Agency.

Other Communications

Kelly, D. P., *et al.* 2003. CLP quarterly progress review—Briefing to DoD of project results and possible DoD applications. Paper presented at the MDA/CLP Quarterly Progress Review, 12 August, Washington, D.C.

Lawrence, R. J., *et al.* 2003. Hydrocode benchmarking and impact flash for kill assessment—Briefing to DoD of project status and possible DoD applications. Paper presented at the CLP Semiannual Review, Sandia National Laboratories, 20 May, Livermore, California. SAND2003-1757P.

Lawrence, R. J., *et al.* 2003. Hypervelocity impact flash—Briefing of project status. Internal Sandia LDRD Review, 30 April, Albuquerque, New Mexico.

Lawrence, R. J., *et al.* 2003. Hypervelocity impact flash—Briefing of project status. Internal Sandia LDRD Review, 30 January, Albuquerque, New Mexico.

52585

Improving Human/System Interactions in Systems-of-Systems

*S. Tucker, M. J. McDonald, C. E. Lippitt, J. C. Forsythe, P. G. Xavier,
S. E. Jordan, N. G. Brannon, D. P. Miller*

A number of military and civilian applications will benefit greatly from human–system interfaces (HSIs) that mimic interactions between humans. Humans are adept at conveying information with a variety of techniques, including speech, gestures, props, and drawing. By coupling technologies that mimic these interactions, Sandia seeks to develop interface technologies for complex systems that are both intuitive and user-centric in design. Intuitive interfaces become appealing with increasing system complexity, such as in large systems-of-systems (SoS). While this work is useful to a variety of interactions with systems, our initial focus will develop an HSI for modeling and simulation (M&S), especially analytic tools. To date, the capability of most M&S applications is underutilized, due to poor management by humans. The push to utilize M&S for more complex analytics has created tools that are usable only by dedicated modelers due to extensive training time and steep learning curve. This paradigm has the end-user of the analyses, the person posing the questions, going to the modelers to have the questions answered. The overall goal of our work is to allow the end-user to become directly engaged in the simulation, to be able to play “what-if” games, and to gain insight into problems. To meet this goal, we are developing a user-centric HSI prototype based on the taxonomy of observed human interactions by integrating both a three-dimensional (3-D) tangible and a 2-D touch interface developed for the SimLab displays. The M&S framework is Sandia’s UMBRA, which needs object-oriented (OO) containers to support the easy creation of hierarchical systems representations. We will implement the concepts of architectural description languages (ADLs) utilizing Extensible Markup Language (XML) to support the OO need. The capability we are developing supports national security programs (Department of Energy/Department of Defense/Department of Human Services) in areas with systems such as C4ISR (Command, Control, Communications, Computer, Intelligence, Surveillance, and Reconnaissance), autonomous vehicles, sensor systems, and military operations on urbanized terrain (MOUT).

Sandia seeks to develop interface technologies for complex systems that are both intuitive and user-centric in design....The capability we are developing supports national security programs (Department of Energy/Department of Defense/Department of Human Services) in areas with systems such as C4ISR (Command, Control, Communications, Computer, Intelligence, Surveillance, and Reconnaissance), autonomous vehicles, sensor systems, and military operations on urbanized terrain (MOUT).

Our accomplishments include the following:

(1) We performed a literature review on current augmented reality (AR)/tangibles research.

(a) We used V_xInsight for high-level review.

(b) We read and catalogued relevant research studies.

(2) We attended workshops, discussions, and panels on AR/tangibles.

(a) We attended IEEE VR2003 Conference meeting discussions.

(b) We attended SIGGRAPH 2003 Conference meeting discussions.

(c) We attended the AR/Tangibles Workshop at the Association for Computing Machinery's (ACM's) Computer-Human Interface 2003 Meeting.

(d) We attended the Virtual Environments (VE) panel and talks on VE at the Human Factors and Ergonomic Society's 2003 meeting.

(3) We developed a tangible interface to the UMBRA environment to investigate video-tracking technology as a beneficial user interface to simulators. We developed the interface using code from the AR Toolkit.

(a) We demonstrated the ability to dynamically add and manipulate simulation objects via tangible symbols using the tracking technology.

(b) We integrated Graviton's Augmented Chemistry into UMBRA to ascertain its ability to provide 3-D control.

(4) We demonstrated a developed tangible interface by using tangibles to place and move multiple objects and cameras in the UMBRA environment.

(5) We performed a study of Joint Conflict and Tactical Simulation (JCATS) user tasks and evaluated the JCATS HSI usability.

(a) The skills of controlling one's entities during play are dominated by the graphical user interface (GUI) skills of the player, not by the abilities of the player to recon, sense, interpret, decide, deploy, shoot, plan, or strategize.

(b) Experience with other systems (personal computers, PDAs [personal data assistants], etc.) hinders performance with the JCATS interface throughout its use, making it very difficult to conclude that performance in the simulation is due to those variables of interest.

(6) We performed a functional task analysis on personnel from Logistics and an external MOUT facility to generate a taxonomy.

(7) We performed a study of ADLs as a means to easily integrate entities, behaviors, and connections into more

complex entities to enable the easy development of hierarchical SoS representations.

(8) We identified the need to formalize system representation and found two candidate technologies:

(a) ADLs

(i) We investigated Carnegie Mellon's ACME presentation as an ADL description to implement with XML.

(ii) We investigated xADL, an ADL developed by the Institute for Software Research at the University of California, Irvine.

(iii) We built a prototypical OO system representation based on ACME and began investigating XML representations for it.

(b) XML Modeling and Simulation Frameworks (XMSF).

52586

Distributed Detection and ID Algorithm Architecture for Unattended Ground Sensors

M. D. Ladd, H. D. Nguyen, B. P. Van Leeuwen, A. A. Yee

During recent years, unattended ground sensors (UGSs) have proven useful in detecting, identifying, and characterizing difficult targets, such as tactical UGS (TUGS), and time-critical targets (Steel Eagle/Rattler). However, current research has focused on a “single-point” capability; that is, a single sensor performs most, if not all, of the system’s functional capability. In the future, large arrays of low-cost, intelligent sensors will become practical due to technological advances in computing and communications driven by commercial, e.g., cell phones, as well as military needs, e.g., Army future combat system (FCS). Consideration of how to effectively use a network of heterogeneous sensors with a distributed algorithm is a new area of research, and the design of distributed identification algorithms for such a network considering all the factors of power usage, algorithm performance, and data-transmission failure rates is new. In this project, Sandia will develop and demonstrate on a test-bed network of UGSs a distributed, scalable, and fault-tolerant algorithm architecture for detection, identification, and location of multiple targets traversing a large field of UGSs. The project will also develop a working model of the distributed algorithm architecture, along with a cost/benefit analysis for trade-offs between local processing and data communication. The result will be a new and potentially powerful system (heterogeneous network of UGSs and detection sensors using a distributed algorithm) for data collection and analysis over wide areas, along with a new method for the combination of data from multiple UGSs. This work also introduces a new methodology for optimal design of distributed algorithm software architectures for heterogeneous sensor networks. Possible applications for such a network and distributed algorithm include facility monitoring, traffic monitoring, and multiple ground-target tracking.

We accomplished significant work toward developing a distributed classification algorithm. In conjunction with the TALON project, we acquired field-test data using multiple acoustic arrays at spatially separate locations. We preprocessed the data and used it in quick-look processing to verify that the position of targets could be determined. Accurate determination of direction of arrival (DOA) is a necessary step for properly combining the data from separate arrays, thereby ensuring that

...Sandia will develop and demonstrate on a test-bed network of UGSs a distributed, scalable, and fault-tolerant algorithm architecture for detection, identification, and location of multiple targets traversing a large field of UGSs. The project will also develop a working model of the distributed algorithm architecture, along with a cost/benefit analysis for trade-offs between local processing and data communication. The result will be a new and potentially powerful system...for data collection and analysis over wide areas, along with a new method for the combination of data from multiple UGSs.

data being shared among distributed, networked sensors are, in fact, from the same target. We employed advanced algorithms to further refine the ability to determine the location of targets using the array data. Constrained optimization algorithms showed promising results, specifically robust minimum variance beamforming (RMVB). We also modified existing vehicle-classification algorithms for distributed implementation. We performed studies of previous work and participated in Sandia's μ TALON algorithm workshop. These activities resulted in multiple algorithm-development efforts that are in progress. One effort is developing a wake-up algorithm that would be used by a lone sensor in the distributed network to activate other sensors in the network in a cascading fashion, thus reducing overall power usage. Another effort is developing an algorithm to use partial classification results from one sensor in other sensors in the network. These algorithm-development efforts are on track for completion in upcoming work.

52587

Secure Chaotic Communications

R. A. Salazar, L. L. Molina, L. D. Bacon

Sandia is developing a secure communications system based on chaos. Researchers have suggested many chaotic schemes. Our goal is to develop a robust communications system that is very secure. The basis of most secure systems is a long sequence of nonrepeating numbers that is difficult to identify. The longer the sequence, the more difficult the sequence is to identify. A chaotic sequence is one that never repeats and, in theory, is infinitely long. The ideal sequence is one that never repeats. The cryptography community refers to a nonrepeating random sequence as a one-time pad. The cryptography community considers the use of a one-time pad a perfect encryption system.

Researchers have suggested many schemes, including Chaotic Masking, Chaotic Shift Keying (CSK), Differential Chaotic Shift Keying (DCSK), Chaotic On-Off Keying, and Frequency Hopping (FH). Of the many schemes suggested, we consider the FH scheme the most probable to meet our goal. We base this conclusion on the properties of a normal hopping system. FH systems are spread-spectrum. One advantage is low probability of intercept. Another advantage is difficulty to jam a message. Both of these advantages come about due to increased noise caused by the increased bandwidth. Due to processing gain, the intended receiver is able to reduce the wide-bandwidth noise and decode the transmitted message, while an adversary could not. In addition, FH systems are robust to propagation effects such as fading.

We studied the current state of the art in chaotic communications and discovered that the study of chaotic communications is in its infancy. Many of the systems studied are analog in nature—few digital schemes currently exist. Although each proposed scheme has some level of security, each scheme falls far short of meeting criteria set by the cryptography community. Bit-error-rate performances for some schemes have analytical solutions, while researchers have used simulations to determine bit-error-rate performance. The schemes we studied are as follows:

(1) *Chaos Masking*. The transmitter adds chaotic-based noise to the message. The intended receiver is able to remove the noise and recover the message. This scheme has a degree of security. Chaos is broadband, so a simple band-pass filter will not block the noise.

Sandia is developing a secure communications system based on chaos. Researchers have suggested many chaotic schemes. Our goal is to develop a robust communications system that is very secure....The ideal sequence is one that never repeats. The cryptography community refers to a nonrepeating random sequence as a one-time pad. The cryptography community considers the use of a one-time pad a perfect encryption system.

(2) *CSK (Chaos Shift Keying)*. Two (or more) chaotic orbits (each orbit representing a symbol) are established and transmitted. This scheme has a degree of security. Cryptographers assume that the adversary has the details of the system and only the key is needed to decode a message.

(3) *Chaotic On-Off Keying*. A special case of CSK, this scheme sends a binary message by transmitting either a chaotic or nonchaotic signal.

(4) *DCSK (Differential Chaos Shift Keying)*. A more robust system, this scheme transmits the chaotic signal twice. The second bit is either as the first or inverted. The receiver uses a correlator to compare the phase relationship between the two signals. This is the most promising scheme based on robustness of the signal and the bit error rate. The bit error rate for DCSK approaches the performance of coherent and noncoherent Frequency Shift Keying, and coherent and noncoherent Binary Phase Shift Keying. The communications community commonly uses these two schemes as references to evaluate the performance of other communications systems.

Evaluating the level of security that each system provides is a more-difficult problem. Most of the schemes studied in the literature base the level of security on the ability of the transmitter and the receiver to synchronize to the chaotic sequence, while an outside observer cannot synchronize to the chaotic sequence. To an outside observer, the sequence looks random. Although based on a chaotic pattern, one cannot repeat the sequence without knowing the details of the chaotic generator. Not only does the system receiving the message need to know the transmitting system, but it also needs to know the coefficients of the system. Even if the receiver knows the approximate value of the coefficients, any error in the estimated coefficients causes the receiver sequence to diverge from the correct sequence. This sensitivity to initial conditions is a basic property of chaotic systems. The smallest changes in initial conditions develop into a completely different sequence. However, the range of the error sequence is well within the normal expected range. Even if an intruder was able to establish short-term synchronization, noise introduced from the communication channel is sufficient to cause the intruder to lose synchronization. We have a basic design for a chaotic FH communications system. We are developing a detailed design that we will construct in upcoming work.

52588

System-of-Systems Modeling and Analysis

D. J. Anderson, J. E. Campbell, E. M. Hinman-Sweeney

Evaluating design concepts for a complex system-of-systems (SoS) involves predicting SoS performance and identifying critical operational parameters across a broad trade space, presenting a multidimensional research challenge. Even for a single system, performance is characterized by several measures of effectiveness (MOEs). For future combat systems (FCSs), the SoS level is defined to be a 1000-platform unit of action (UA). Analyzing the performance of several design options of a complex SoS across external parameters and multiple MOEs generates a massive number of trade-space combinations, producing extreme computational issues.

Evaluation of performance at the SoS level is critical to achieving high-performance objectives. SoS analysis requires predicting performance at the SoS level in contrast to the traditional platform-by-platform approach. SoS analysis must examine a multitude of design and technology options to optimize mission effectiveness across wide parameter spaces. The need to establish SoS performance requirements and translate these SoS requirements down to optimal or near-optimal individual platform requirements for system design and development is required. This challenge is further extended by the complexity presented with new technology. Currently, about the only method to gain some performance knowledge at the SoS level is through traditional warfight simulation codes, which are costly and time-consuming.

The goal of this project is to develop an integrated modeling and simulation environment that addresses the complex SoS modeling and analysis needs. The approach involves developing, enhancing, and integrating (1) state-modeling methodologies, (2) simulation objects, (3) time-step simulation methodology, (4) experimental design and optimization for trade-space exploration, and (5) agent-based simulation tools for detailed concept and scenario analysis. Sandia will apply the methodology to an FCS UA concept to demonstrate the approach.

This project achieved the following accomplishments to date:

- We identified and further defined several challenges to SoS modeling and analysis.
- We modified existing software tools to simultaneously analyze and optimize multiple MOEs.

The goal of this project is to develop an integrated modeling and simulation environment that addresses the complex SoS modeling and analysis needs....Sandia will apply the methodology to an FCS UA concept to demonstrate the approach.

- We developed an initial systems-engineering definition of information superiority MOE that addresses sensing, potential conflict of sensor information, communication, and information verification for addressing modeling of MOEs other than reliability.

- Initial design efforts are under way for a new state-modeling interface to replace the current generic interface.

- We are evaluating procedures to provide rapid, automatic development of scenario-specific input data based on a baseline dataset and a combination of conditions that define the scenario.

- We collaborated with the Simulation and Optimization Laboratory at the University of Illinois, Urbana-Champaign, to develop robust, multiobjective optimization schemes and post-optimal procedures for selecting the best solutions based on decision-maker preferences.

- To address analyzing hundreds of systems in an SoS analysis, we began work on model simplification, model referencing, and encapsulation schemes that will take advantage of the fact that an SoS may involve many identical platforms.

- We are developing an approach for dealing with the massive redundancy present in many SoS problems, combining scaling up existing redundancy algorithms, encapsulating redundant arrangements, and taking advantage of the identical components, subsystems, and platforms that often occur in SoS redundancy groupings.

- We developed a simulation object that integrates a multi-MOE state model with simulation and provides real-time status of multiple MOEs, including the possibility that an MOE may have multiple levels (not just success or failure), calculation of the probability that any MOE will be in one of several levels up to the end of the mission, and sensitivity analysis to identify the most likely problem areas for the MOE.

- We identified several potential sources of “singularities and nonlinearities” and are examining techniques for dealing with them.

52589

Eye-Safe Short-Range Standoff Aerosol-Cloud Finder

K. L. Schroder, R. P. Bambha, I. R. Shokair, T. A. Reichardt, T. P. Tooman

There has been considerable interest in the use of Sandia-developed standoff ultraviolet (UV) laser-induced fluorescence (LiF) techniques to detect and discriminate biological-agent aerosols in the indoor environments of critical facilities. One challenge for this application is laser safety. The exposure of personnel to UV laser energy must be kept below the maximum exposure limits. One solution is to use an eye-safe aerosol-cloud finder to scan the room to localize suspect aerosol clouds, discriminate them from background aerosols and the many solid objects in the field of regard, and cue the UV-LiF to briefly probe the cloud.

Sandia proposes to determine the feasibility of a short-range (30 m), eye-safe infrared (IR) (1550 nm), indoor, aerosol-cloud-finding light-detection and -ranging (lidar) system. We will select candidate components and model, develop, and demonstrate the approach in a laboratory proof-of-principle experiment. We will evaluate the utility of multiple techniques, including high-speed digitization and amplitude/rise-time discrimination, a multiple-beam technique of discriminating a glancing incidence on a solid object, and an up-converting IR detector under development by Sandia in a separate project. We will also assess the applicability of the techniques to single-pulse discrimination of aerosols from solid objects from a moving platform.

We completed a conceptual design of the short-range aerosol-cloud finder. A Sandia-designed microlaser-pumped optical parametric generator (OPG) will serve as the eye-safe laser source. The laser will produce a two-pulse sequence. The first pulse is used as a time-of-flight (TOF) measurement of the distance to a solid object, and the second pulse is used for aerosol detection. The distance measurement is required because the aerosol signal is expected to be several orders of magnitude less than the signal from a topographic target at near-normal incidence. It may be important to gate the aerosol-backscatter signal so the detection scheme is not saturated by the backscatter from solid objects.

A lens will focus the backscatter into a single-element IR detector. The 1064 nm output of the laser will trigger the detection electronics. A low-gain acquisition channel will

There has been considerable interest in the use of Sandia-developed standoff ultraviolet (UV) laser-induced fluorescence (LiF) techniques to detect and discriminate biological-agent aerosols in the indoor environments of critical facilities. One challenge for this application is laser safety....Sandia proposes to determine the feasibility of a short-range (30 m), eye-safe infrared (IR) (1550 nm), indoor, aerosol-cloud-finding light-detection and -ranging (lidar) system.

measure the range to the near-normal topographic background. We will then switch the electronics to the high-gain mode for detection of aerosol clouds. The background topographic backscatter signal will be temporally gated out of the acquisition period. Temporally resolving the return signal may allow us to differentiate between glancing incidences on sharp objects and aerosol clouds.

We designed and assembled a proof-of-principle experimental system. The Nd:YAG (neodymium:yttrium aluminum garnet) microlaser pump, fabricated by Onyx Optics, consists of a 1 mm-thick piece of undoped YAG, a 7 mm-thick piece of a 1.1%-doped Nd:YAG, a 1.9 mm-thick piece of Cr^{4+} :YAG, and an 8 mm-thick piece of undoped YAG diffusion-bonded together. The end faces are polished and have dielectric mirror coatings directly deposited to form a 17.7 mm-long monolithic passively Q-switched laser. This laser is end-pumped, imaging 808 nm pump light from the fiber-coupled diode laser into the Nd:YAG laser. The fiber coupler, focusing lens, and Nd:YAG rod are housed in separate machined aluminum (Al) blocks. We added Al spacers to optimize the focusing of the fiber output into the Nd:YAG rod. We bolted the housings together to form a single unit that is temperature-controlled by a common thermoelectric cooler (TEC). When pumped with $\sim 300 \mu\text{s}$ -long 11.8 W pulses of 808 nm light, the monolithic Nd:YAG laser produces two Q-switched pulses, each 2.2 ns long, separated by 100 μs .

The OPG periodically poled lithium niobate (PPLN) crystal is 5 mm long x 3 mm wide x 1 mm thick (Crystal Technologies). The faces of the crystal are antireflective-coated for 1064 nm, 1.6 μm , and 3.3 μm . The faces of the crystal have a wedge angle of 5 deg to eliminate etalon effects or parametric oscillation in the crystal, and the crystal is heated to 140°C to avoid photorefractive damage. The crystal period of 29.8 μm is suitable for phase matching of the 1064 nm Nd:YAG pump beam to generate a signal wavelength of 1.58 μm and an idler wavelength of 3.27 μm . We acquired over 20% conversion from the microlaser output to the OPG signal output.

We configured a receiver and acquired initial backscatter measurements from topographic targets. These measurements serve as a test of the ability of the low-gain channel to detect topographic backscatter, as well as its ability to examine the temporal response of the system electronics. The trigger and acquisition waveforms from an initial test of the system with a solid backscatter target placed ~ 2 m from the detector demonstrated that we are able to measure the TOF adequately. The peak width of the topographic backscatter also

demonstrates that the digitizer bandwidth should be sufficient to discriminate topographic backscatter from the temporally broader backscatter from a 1 m aerosol cloud.

We used a Hamamatsu H9170-75 near-IR photomultiplier tube (PMT) in initial aerosol-detection experiments. The PMT has very high sensitivity due to its internal gain, and the rise time is 0.9 ns. The sensitivity and high speed of the PMT allow aerosol plumes to be detected with a wide range of densities and background-to-plume separations important for testing detection algorithms.

52590

Micro Flame-Based Detector Suite for Universal Gas Sensing

R. P. Manginell, P. R. Lewis, P. G. Clem, M. W. Moorman, D. R. Wheeler, T. W. Hamilton, S. K. Showalter, A. Robinson, J. E. Miller

The flame-ionization detector (FID) is universally applied in gas chromatography (GC). The nitrogen-phosphorous detector (NPD) is 50x–500x more specific for compounds containing these elements, e.g., chemical warfare (CW) agents. A powerful array detector is possible through an NPD-FID combination. Miniaturization of these detectors for portability has been hampered by the heat-transfer properties of microsystems. Sandia developed a platform to enable both detectors; catalyst-coated microhotplates minimize heat losses on the microscale and permit catalytically stabilized combustion in this domain. This is a radically different approach from conventional FID.

We used our platform to demonstrate a catalytically stabilized FID and showed that it expands the limits of flammability, as compared with a conventional FID, and permits surface- and gas-phase combustion alike; we recently completed a constant-flow hydrocarbon delivery system for further testing. The microCombustor (μ Combustor) platform is also nearly integrated with a CW-simulant vapor generator to test the NPD; it is our intention to test catalysts that may also adapt the NPD mechanism to the specific detection of chemicals containing chlorine (Cl), fluorine (F), and sulfur (S), which are characteristics of other CW/blister agents.

Sandia developed a platform to enable both detectors; catalyst-coated microhotplates minimize heat losses on the microscale and permit catalytically stabilized combustion in this domain. This is a radically different approach from conventional FID.

(below) A hotplate with variable width was developed that operates at lower voltage and with a smoother temperature gradient. This mitigates hot spots and electromigration damage (finite-element [FE] model shown).

We will combine these detectors in an array. Each array detector uses the same platform; only the specific catalyst and/or temperature may change. The detection electronics are similar in all cases. We tested an in-house-developed electrometer and a commercial system. We submitted designs for an NMOS (negative [N]-channel metallic oxide semiconductor) preamplifier monolithically integrated with the platform, the first ever of its kind. On-chip preamplification should allow significant improvement since on-chip capacitances are significantly lower than in conventional devices.

Through experiment/modeling, we are steadily improving the reliability of the platform during combustion. We predicted/designed new devices incorporating high-temperature materials, e.g., molybdenum disilicide (MoSi_2), integrated electrodes, and improved mechanical robustness. We designed and built monolithic 10-element arrays, along with temperature-control circuitry and packaging. We extensively tested three methods of depositing/patterning catalysts on the surface of the platform: spray, microPen, and anodization. Currently, spray coating and anodization show the most promise.

The $\mu\text{Combustor}$, used as a basis for the FID and NPD, is a microhotplate with a supported catalyst deposited on its active area. We investigated the use of a microPen or a nebulizer to deposit commercial-supported catalysts. We showed that the microPen can define catalysts with high resolution. Clogging of the system tubing can take place at research coating volumes; it should fare better in manufacturing. Nebulizer spray coating through a mask has not yet matched the edge definition of the microPen, but we did not observe clogging. We are also evaluating a longer-term solution for reliable catalyst production, *in situ* anodization. Work is under way to dope this material with appropriate catalysts.

The $\mu\text{Combustor}$ initiates/sustains combustion in a fuel/air mixture. We showed that the catalytic $\mu\text{Combustor}$ expands conventional limits of flammability (LOF) of H_2 , $\text{C}_1\text{--C}_3$, and natural gas, e.g., propane's LOF is 2.1%–9.5%, whereas the $\mu\text{Combustor}$ yields 1%–11.5%. Expanded LOF are important because they allow our FID to operate over broader conditions with reduced fuel consumption. Moreover, we demonstrated three possible combustion regimes, determined by temperature: reaction-rate-limited and mass-transfer-limited surface combustion and gas-phase combustion. This is important since the FID prefers flame liftoff, while the NPD/thermo-catalytic ionization detector (TCID) prefers surface reactions.

To create the FID and NPD/TCID, we placed electrodes around the catalyst to collect ions. In the first demonstration of our FID, we used a thin-film monolithic electrode and a counter electrode placed in a flow lid glued over the device. We demonstrated detection of ~ 1%–3% ethane at 20 V bias. While important for establishing the FID mechanism, this configuration required significant assembly. To remedy this, we built a test fixture with miniature electrodes surrounding the μ Combustor. While significantly easier to assemble, the larger fixture volume decreased combustion efficiency and increased bias voltages. Results for ~ 1%–3% ethane were comparable to the original tests but required ~ 200 V. Further, grounding/shielding issues arose due to the fixture and the in-house electrometer. We significantly minimized these problems with a commercial electrometer. We will improve the in-house electrometer concurrently with testing the commercial electrometer.

We are machining a new low-volume fixture that retains ease of assembly. One or two microhotplates can be used, and the fixture permits nonpremixed fuel/air. Microhotplate heater connections are also shielded. Another source of noise in our original apparatus was flow-rate variation with gas concentration. We rebuilt the system for constant flow; for hydrocarbon concentrations less than 10%, the system controls flow to better than 0.5%. To independently verify system response, we purchased an Agilent MicroGC system, and calibration is nearly complete. For NPD testing, we developed rubidium (Rb)-based catalysts and methods of depositing them. Integration of the NPD with a vapor generator for CW simulants is nearly complete and testing is imminent.

We fabricated three μ Combustor designs: a basic design, one with thin-film electrodes, and a 10-element array for eventual integration of the FID and NPD into a monolithic array. (We designed and tested a multielement control circuit for the latter.) We used these designs in FID testing and studied them for increasing device lifetime. Based on this, we implemented high-temperature adhesion layers (tantalum [Ta]), thicker metals, and passivation overcoats. We are investigating the stability of Ta adhesion layers and other high-temperature materials like MoSi_2 .

We are using experimentally verified finite-element models to design μ Combustors for improved temperature uniformity and durability. We submitted mask designs for a μ Combustor/FID/NPD integrated with an NMOS preamplifier. If successful, this will be the first-ever example of on-chip preamplification in an FID/NPD. This mask also includes integration of the FID

We submitted mask designs for a μ Combustor/FID/NPD integrated with an NMOS preamplifier. If successful, this will be the first-ever example of on-chip preamplification in an FID/NPD.

with a GC and a preconcentrator (PC). Flame simulation has been somewhat inconclusive. MPSalsa simulations predict ignition temperatures different from those observed experimentally. Other groups have used commercial codes to successfully model similar situations.

Refereed

Moorman, M. W., R. P. Manginell, C. W. Colburn, D. L. Mowery-Evans, P. G. Clem, and N. S. Bell. 2003. Microcombustor array and microflame ionization detector for hydrocarbon detection. *Proc. SPIE Micromachining and Microfabrications, MEMS Components and Applications* **4981** (25 January, San Jose, California): 40–50.

63966

Smart Decoy Sensor Network

J. L. Kalb, L. H. Marshall, J. A. Rohwer

Flight-test experiments utilize arrays of instrumented decoys to demonstrate target-discrimination capability. The decoys include light-weight instrumentation systems (LWIS) to provide trajectory and infrared (IR) truth data on these decoys. The potential to require a larger number of instrumented decoys presents a concern associated with radio-frequency (RF) spectrum utilization, while down-link communication is a technical challenge in current missions. The decoys could be configured into a communication and sensor network to resolve spectrum and link issues and to provide a spatially diverse vantage point of engagement and end-game diagnostics. Communication and sensor assets could be included on the bus to allow for communication to the ground and for stabilized line-of-sight (LOS) sensors directed to end-game diagnostics.

The instrumentation and sensors on the decoys must be very lightweight and operate on very low power. The dynamic stability of the objects presents communication link challenges associated with LOS problems with antenna patterns. This dynamic communication-link situation will require further subtlety as the decoys are required to share common wireless-network assets as opposed to the traditional point-to-point frequency multiplexed approach.

The design of end-game sensors to be deployed in the decoys has great potential and has been given very little detailed consideration. IR, optical, or chemical seedant sensors could be deployed on several decoys for redundancy. The advantage of collaborative reporting is especially applicable to end-game sensing as the various decoys will have different vantage points for the intercept event.

We completed an application study to determine the utility and viability of wireless-network techniques to a “typical” missile-defense flight-test scenario. The network is intended to allow for many (10 to 100) objects to be networked together on a single frequency. We determined that the size and functionality supported in typical wireless-network communication devices will support the typical decoy and target scene elements.

We completed a trade study to trade off several commonly used network architectures to the experiment scenario described above and evaluated the strengths and weaknesses of the various protocols in the study.

We completed an application study to determine the utility and viability of wireless-network techniques to a “typical” missile-defense flight-test scenario. The network is intended to allow for many (10 to 100) objects to be networked together on a single frequency. We determined that the size and functionality supported in typical wireless-network communication devices will support the typical decoy and target scene elements.

We outlined a baseline wireless-network solution and evaluated it against the flight-test communications requirements, including data volume, transmission rate, transmission distance, and operating power consumption. The resulting baseline design will meet the current test requirements and offers many operational advantages, including frequency optimization, error detection, and transmission link margin improvement.

The work in this project formed part of the technical foundation of a wireless-network concept that is receiving very positive reviews within the Missile Defense Agency (MDA) program leadership at Sandia.

*The work in this project formed
part of the technical
foundation of a wireless-
network concept that is
receiving very positive reviews
within the Missile Defense
Agency (MDA) program
leadership at Sandia.*

63968

Monomolecular Carbon Nanothread Fabrication

J. F. Jones, B. R. Roher, B. S. Swartzentruber

Sandia seeks to establish the feasibility of creating arbitrarily long “carbon nanothread.” We intend to do this by joining individual carbon nanotubes (CNTs) end to end with electron-beam “welding.” A primary technical challenge is manipulation of the nanotubes. We hypothesized that CNTs could be manipulated as rigid bodies with two scanning-tunneling microscopes (STMs) guided by an operator using a scanning-electron microscope (SEM). We made significant progress toward rigid-body-like CNT manipulations and laid the groundwork for performing these manipulations in future work.

We will use STM tips to grip CNTs. Theory predicts that the dielectrophoretic effect induced by STM tips should produce a significant force on CNTs. The dielectrophoretic force is roughly proportional to the volume of the manipulated object, its polarizability, the strength of the local electric field, and the magnitude of the field gradient. The volume of a CNT is large relative to a single atom; its polarizability is good (using the polarizability of graphite as a guide) even in a vacuum. The strength of the local field is directly related to the applied voltage and to the distance from the tip, both of which are controllable. The magnitude of the E-field gradient is related to the tip and substrate geometry. The CNT’s volume and polarizability (which are directly related to its conductivity) are the key factors that make it a good candidate for a dielectrophoretic-based method of gripping and manipulation.

The research performed under this effort has prepared the way for rigid-body manipulation of CNTs on three fronts:

- (1) Condensing and understanding previous nanomanipulation research and its relation to performing arbitrary manipulations of CNTs in space,
- (2) Simulating interaction forces that are likely to occur during nanomanipulation with an STM gripper utilizing dielectrophoresis, and
- (3) Developing the hardware platform for performing nanomanipulation, namely, operating an STM within an SEM.

The research performed in conjunction with this effort helps establish the feasibility of this type of manipulation and serves as the initial steps toward achieving it. During this research, we discovered no insurmountable barriers to our ultimate objective

Sandia seeks to establish the feasibility of creating arbitrarily long “carbon nanothread.” We intend to do this by joining individual carbon nanotubes (CNTs) end to end with electron-beam “welding.” A primary technical challenge is manipulation of the nanotubes. ...We made significant progress toward rigid-body-like CNT manipulations and laid the groundwork for performing these manipulations in future work.

of performing arbitrary manipulation and assembly operations with CNTs. We anticipate that follow-on research activities will allow us to achieve this goal.

Other Communications

Roher, B. R., J. F. Jones, and B. S. Swartzentruber. 2003. In Preparation of Rigid-Body Manipulation of Carbon Nanotubes. Sandia Technical Report SAND2003-3472, Sandia National Laboratories, Albuquerque, New Mexico.

63969

Reliability Data to Improve High-Magnetic-Field Coil Design for High-Velocity Coilguns

R. J. Kaye, G. A. Mann

Coilguns are electromagnetic guns that could launch large (60 kg) warheads or reconnaissance devices at velocities > 2 km/s to targets at hundreds of nautical miles at 50 nmi/min. Coilguns could also be used to accelerate weapon components or penetrator packages up to 30 cm diameter to speeds of 3 km/s for impact studies. Because of their ability to tailor the accelerating force over the entire launch, coilguns can launch fragile components to high speed with controlled setback force.

Given that we have launched 50 mm projectiles to 1 km/s, the next proposed step is to demonstrate 2 km/s with a small-scale bore gun that would consist of 80 high-magnetic-field (20–30 Tesla) coils stacked end-to-end. The utility of both the small-scale demonstration gun and the larger bore guns that use a large number of coils is predicated on the coil's lifetime. Sandia proposes to establish a test-bed to generate reliability data (shot-life) of existing coils, determine failure mechanisms, and provide a basis for projecting lifetime of future guns.

Reusable high-magnetic-field coils have operated at 60-Tesla field levels, but have not demonstrated long lifetimes at those levels. Lifetime is significantly greater at the 20–30-Tesla levels where the coilgun would operate. Although typical high-magnetic-field coils used for materials testing differ from coilgun coils in aspect ratio and boundary conditions, many of the construction materials and techniques are similar.

Coilguns have launched projectiles to 1 km/s, and there is interest in their application for long-range precision-strike weapons. These applications will require coil operation at the same 30-Tesla magnetic-field strength as coils previously tested, but with larger bore diameters and mechanisms for heat rejection to accommodate firing rates of several shots per minute. The incorporation of a cooling system will impact the mechanical design and response of the future coils.

To assess the impact of such changes, we evaluated the ruggedness and reliability of the existing 50 mm bore coil designed in 1993 by repeatedly testing at stress levels associated with operation in a coilgun. We built a two-coil test-bed with a static projectile where each coil is energized by its own 75 kJ capacitor bank. We created simulation models of the forces generated in this test-bed with the SLINGSHOT circuit

Coilguns are electromagnetic guns that could launch large (60 kg) warheads or reconnaissance devices at velocities > 2 km/s to targets at hundreds of nautical miles at 50 nmi/min. Coilguns could also be used to accelerate weapon components or penetrator packages up to 30 cm diameter to speeds of 3 km/s for impact studies. ...Sandia proposes to establish a test-bed to generate reliability data (shot-life) of existing coils, determine failure mechanisms, and provide a basis for projecting lifetime of future guns.

code to obtain loads equivalent to the worst case anticipated in a 50 mm coilgun that could launch a 236 g projectile to 2 km/s.

Bench measurements of the inductance and resistance versus frequency of the seven remaining HFC5 coils built in 1993 identified which coils were viable for testing, and only one was found defective, despite others having slightly damaged feeds. Measurements of the gradient of the effective coil inductance in the presence of the projectile were in excellent agreement with values from SLINGSHOT. This indicates that the prediction of thrust should likewise be very good. Problems with the response of load cells during measurements of thrust, however, preclude comparison to the calculations until a pulsed calibration of the cell can be conducted. Regardless, we demonstrated noise immunity for this millivolt-level measurement with shielding and techniques that are applicable to future gun experiments.

Repeated testing of the coils demonstrated no failures after 205 shots. These tests were done in 50-shot groups from 50% to 90% of the stress levels anticipated in the 50 mm coilgun, in 10% increments. This method obtained as many shots as possible on the coil while working below a known failure mechanism in the winding layer-to-layer transition at the 100% stress level that was seen in 1993. The number of shots achieved to date without a failure is an order of magnitude greater than any number achieved in previous testing. Although this testing has been done only on two coils, the results are encouraging as it demonstrates there are no fundamental weak links in the design that will cause a very early failure. The testing also demonstrates that the swaged litz cable-to-feed joint is quite robust, even when slightly damaged in handling, and the joint design will be considered for future coils.

We suggest several recommendations for future coil designs based on this study.

(1) We recommend a composite ring to reinforce the composite shells where the layer-to-layer transition essentially splits the shell in half at the ends of the winding.

(2) Feeds to the coils must be shortened to reduce the potential damage to the junction to the litz cable and strengthened to prevent damage when the cables are attached and tightened.

(3) Future designs must consider embedded strain and temperature diagnostics to provide a state-of-health of the coil and possibly predict impending failure. Since the probes need to be fiber-optic-based for immunity to electromagnetic interference, significant precautions must be taken to protect

Measurements of the gradient of the effective coil inductance in the presence of the projectile were in excellent agreement with values from SLINGSHOT.

This indicates that the prediction of thrust should likewise be very good.

both the probe and its transmission line, particularly the egress from the coil.

(4) Additional static testing is needed up to the 100% gun stress level on the existing HFC5 model to establish shot life and failure mechanisms other than the weak transition previously discovered.

(5) Lifetime data for high field coils of similar construction and field strength developed at the National High Magnetic Field Laboratory should be compared to this study's data to provide a benchmark for lifetime characteristics and failure mechanisms.

63970

Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities

R. G. Betty, M. D. Tucker

Sandia developed and commercially licensed a nontoxic, noncorrosive formulation for the rapid mitigation and decontamination of chemical-biological warfare (CBW) agents. Originally developed for use in civilian populations, the technology is of extreme interest to military applications. The U.S. Army (CENTCOM [Central Command]) and Marines (MARCORSYSCOM [Marine Corps System Command]) recently procured the formulation for potential replacement of the current military stockpile of DS2, a highly toxic and corrosive CBW decontaminant.

Although fire-fighting foams utilize surfactants, those historically in use by the fire-fighting industry are of a different chemistry from the surfactant in the Sandia CBW-decontamination formulation. It is highly desirable, from a logistical point of view, to develop a formulation that would have both the CBW decontamination and the fire-fighting capabilities. This would enable civilian first-responders and the military to purchase one foam formulation meeting both fire-suppression and CBW-decontamination capabilities. Dual-capability foam would provide a significant enhancement to the protection of critical infrastructure and be of high commercial value.

We conducted an investigation to determine what currently commercially available surfactants considered for use as fire suppressants would also have the appropriate chemistry for use with the DF-200 CBW decontamination formulation. Once identified, surfactants were obtained and prepared in modified formulations, then tested for efficacy of CBW simulant decontamination. We assessed modified formulations for stability and foam-expansion characteristics, viscosity, and surface-tension measurements. We performed a series of bench-scale film-formation and sealability tests to assess the ability of modified formulations to adequately spread and form a seal over a hydrocarbon surface. We selected and submitted two modified formulations for off-site standardized testing of Class B fire-suppression capability.

The initial emphasis of this project was to assess the use of alternative surfactants (or mixed surfactant blends) with fluorosurfactants on the CBW-agent simulant decontamination efficacy of modified decontamination formulations. The results

Sandia developed and commercially licensed a nontoxic, noncorrosive formulation for the rapid mitigation and decontamination of chemical-biological warfare (CBW) agents. Originally developed for use in civilian populations, the technology is of extreme interest to military applications....It is highly desirable, from a logistical point of view, to develop a formulation that would have both the CBW decontamination and the fire-fighting capabilities.

of initial simulant decontamination efficacy tests provided data that suggested a general trend in formulation design. Because commercial aqueous film-forming foam (AFFF) formulations are in the range of 3%–6% concentrates, effort was made to minimize the components of dual-use formulations, with continued effort in providing adequate CBW-agent simulant efficacy. We performed a thorough study of the effects of individual components and groups of components on surface tension, and surface-tension measurement of proposed modified formulations. Results from these tests provided further direction in formulation design and modification. Finally, to assess the fire-suppression capability of modified dual-use formulations, we performed laboratory-scale standardized AFFF film-formation and sealability tests per *Military Specification MIL-F-24385F, Fire Extinguishing Agent, Aqueous Film-Forming Foam (AFFF) Liquid Concentrate, for Fresh and Sea Water*, section 4.7.6. We used the results of these film-formation tests to select dual-use formulations submitted for standardized Class B fire-suppression tests per Underwriters' Laboratories (UL) 162, "Standard for Foam Equipment and Liquid Concentrates, Class B Fire Tests-Topside Discharge Devices," section 10.

Laboratory results indicated efficacious CBW-agent simulant decontamination in dual-use formulations comprising an alternative surfactant, fluorosurfactant(s), and additional components required for their foaming or CBW-agent decontamination capability. The dual-use formulations provided chemical-agent simulant decontamination efficacy of greater than 99.9% after 1.0 hr of contact time. We demonstrated dual-use formulations to provide > 7 log kill of anthrax simulant at 30 min of exposure. Surface tension of modified formulations was in the range of 24–29 dynes/cm, compared to 18.9 dynes/cm for a commercial AFFF formulation and to 33 dynes/cm for DF-200. We performed film-formation and sealability tests. The commercial AFFF formulation passed this bench-scale test for a 10 min period, at which time testing was terminated; DF-200 failed the test at 0 min; the dual-use formulations passed the test up to 8 min. We selected and submitted two dual-use formulations for UL 162 testing, performed at Southwest Research Institute in San Antonio, Texas. The two formulations were unsuccessful at extinguishing the Class B (heptane) fires per the standard protocol. The formulations were each deployed at a rate of 2 gal per min from the Intelagard Merlin compressed-air foam-deployment device. Visual observation of the UL 162 tests indicated a film spread of approximately 30% into a 7 ft x 7 ft

pan of burning heptane fuel, not adequately effective to achieve one of the critical goals of the project.

Based on bench-scale tests conducted at Sandia, the prospect of designing a dual-use formulation for CBW-agent decontamination and fire-suppression capability is promising. Results of bench-scale tests indicate a reduction in surface tension and improvement in film formation and sealability of modified dual-use formulations compared to the DF-200 formulation. CBW-agent simulant decontamination efficacy of a dual-use formulation was nearly as effective, with a reduction in the required surfactant concentration and an overall reduction in total nonaqueous components, on a weight-percent basis.

It is clear that a better understanding is required of the fundamental interactions as they relate to a successful fire-suppressant and CBW-agent decontaminant. We will pursue further funding for this technology. Further investigation may begin by performing fundamental research into the following elements: alternative or additional methods to accomplish the surface-tension reduction; a study of phenomena such as thermal stability and heat capacity; foam stability; spreading, film formation, and film stability; environmental biodegradability; and toxicity.

Results of bench-scale tests indicate a reduction in surface tension and improvement in film formation and sealability of modified dual-use formulations compared to the DF-200 formulation. CBW-agent simulant decontamination efficacy of a dual-use formulation was nearly as effective, with a reduction in the required surfactant concentration and an overall reduction in total nonaqueous components, on a weight-percent basis.

64711

Wide-Area Surveillance in Synthetic-Aperture Radar Images

B. K. Bray, J. A. Richards

Automatic target recognition (ATR) systems operate in conjunction with synthetic-aperture radar (SAR) sensors to detect and identify targets of interest. These ATRs, however, are designed to operate with high-resolution imagery, in which it is easier to tell the difference between targets. There are no existing ATRs that can effectively operate on wide-area-surveillance SAR imagery; the coarser sensor resolution, coupled with the high coverage rate, makes target recognition and cueing for wide-area surveillance a significant challenge.

The primary goal of our proposed research is to investigate how Sandia's existing ATR capabilities can be extended to provide smart cueing capability to the image analyst when the SAR sensor is in wide-area-surveillance mode. To test this theory, we will create a generic cueing capability for military vehicles, in which target-like regions of interest are identified and cued to the image analyst for further scrutiny. To further assist the image analysts, we will augment this generic cueing capability with an optional identification back-end that is trained to identify a limited library of military vehicles. This modified identification back-end will provide sorted lists of the most likely identifications that were found in the most recently collected imagery. Both generalized cueing and sorted identification will significantly help the SAR image analysts by helping them prioritize their time when the SAR sensors are performing medium-resolution wide-area surveillance.

Our existing SAR ATR algorithm suite comprises three stages: a front-end prescreening stage, an indexing stage, and a back-end identification stage. Implementation of each stage requires training based on characteristic imagery. Therefore, the first step in this project was to reform existing higher-resolution SAR imagery into medium-resolution SAR imagery characteristic of wide-area-surveillance mode. This task was straightforward and presented no difficulty.

The second step was to extract relevant target signatures and adapt our existing prescreening front-end (FOA) and identification back-end algorithm to use this data. For FOA, as expected, the lack of pixel resolution reduced the ability to separate vehicles from natural clutter. In particular, for most features calculated by FOA, the separation between vehicles and natural clutter was reduced. For medium-resolution

The primary goal of our proposed research is to investigate how Sandia's existing ATR capabilities can be extended to provide smart cueing capability to the image analyst when the SAR sensor is in wide-area-surveillance mode....Both generalized cueing and sorted identification will significantly help the SAR image analysts by helping them prioritize their time when the SAR sensors are performing medium-resolution wide-area surveillance.

imagery, the feature of relative brightness is more important in separating vehicles from natural clutter than is the case for higher-resolution imagery. Fortunately, the FOA false-alarm rate (FAR) for 1 m resolution imagery proved to be low enough that following stages should be able to handle the processing requirements in a real-time system.

The adaptation of our existing back-end target-identification module, the trimmed multinomial pattern matcher (TMPM) algorithm, proved to be relatively straightforward. Although the coarser pixel resolution associated with wide-area surveillance necessarily reduces classification ability, it appears that 1 m imagery still allows reliable classification of many military targets. In particular, even at 1 m resolution, each target that we investigated displays distinguishing features that should enable its discrimination from clutter, from other targets, and from confuser vehicles. The largest issue in the use of TMPM for coarse-resolution imagery involves the selection of algorithmic thresholds, including the fraction of pixels that can be trimmed for calculation of the match metric, and the minimum pixel match deviation for allowing this trimming. For 1 m imagery, the choice of these parameters is driven by two factors: first, the small number of pixels available for any given target, and second, the relatively greater similarity between targets.

The third step was to develop a generalized indexer—the middle stage of the end-to-end ATR—to reduce clutter false alarms. This proved to be the most challenging component of the project. We developed three different algorithms before finding a satisfactory method to reliably and robustly extract a “blob” covering each target’s radar return. Once the method for extracting, parameterizing, and storing target blobs was implemented in a manner facilitating extraction of profile features, we began to develop features that could possibly be used to separate vehicles from natural clutter. Most of the features dealt with the slope and curvature of the leading edge of the radar return, since the leading-edge return provides a robust, characteristic indicator of the presence of a target and facilitates the rejection of broad classes of clutter. We developed additional features to provide information about the relationship of the primary leading edge to the secondary leading edge, enabling better target discrimination and clutter rejection.

Our original project plan called for a fourth step involving the integration of these three stages into a complete end-to-end system and the characterization of the trade-offs between probability of detection and FAR. We were unable to complete this step, largely because the development of a stable, robust

generalized indexer proved more difficult than originally anticipated. Fortunately, integration of the three stages into a complete end-to-end system presents no fundamental technical challenges, and should be possible with little additional time and effort at some point in the future.

65828

Measures of Effectiveness and Performance for MicroTalon SDAC Technologies and Systems

L. A. Jones, M. D. Ladd, M. L. Yee, F. J. Oppel, III, E. P. Parker

Sandia attempted to identify some performance advantages offered by present and near-future technologies for small, widely distributable Sense, Decide, Act, and Communicate (SDAC) systems. Our goal was to provide specific examples where the Department of Energy (DOE) investment in Microsystems and Engineering Systems Applications (MESA) has high utility for developing new classes of sensor systems that help our national security posture.

We studied two examples. The first example was the insertion of battlefield sensors via conventional munitions. Every weapon that is launched against enemy forces represents an opportunity to insert sensors into enemy territory. The challenge is surviving the ride in, especially if the ride is on a penetrator weapon into a hardened target, followed by a high-explosives blast in close proximity. If the sensor package survives and can reestablish communications with blue forces, sensors will have been inserted into areas that are otherwise difficult or impossible to reach any other way.

Extremely high forces are encountered close to a detonation of high explosives. An advantage provided by microsystems is the integration of suites of microsensors and their supporting electronics into highly shockproof packages. Systems that are monolithically integrated onto a single substrate can survive much higher forces than traditional sensors and electronics. We modeled the accelerations encountered close to a high-explosives blast using hydrocodes, and it is clear that high-g-tolerant sensor packages will be needed. High-g sensors and electronics may be an area of high-investment utility for MESA.

The second example examined was the impact on network latency of additional nodes in large SDAC systems. Network latency is a measure of performance for SDAC systems, and it might be adversely affected by adding stationary nodes in a field of mobile nodes. Large-scale efforts are under way at Sandia to model fields of SDACs, and we added a metric in these models to measure the impact of additional nodes made possible by the use of microsystems.

We considered numerous application areas for SDAC systems, including homeland/physical security, nonproliferation

Sandia attempted to identify some performance advantages offered by present and near-future technologies for small, widely distributable Sense, Decide, Act, and Communicate (SDAC) systems. Our goal was to provide specific examples where...Microsystems and Engineering Systems Applications (MESA) has high utility for developing new classes of sensor systems that help our national security posture....Large-scale efforts are under way at Sandia to model fields of SDACs, and we added a metric in these models to measure the impact of additional nodes made possible by the use of microsystems.

and materials control, nuclear weapons, and battle-damage assessment (BDA). We chose two specific examples where the DOE investment in MESA has high utility for developing new classes of sensor systems.

We selected a concept for BDA where a sensor package rides a penetrator into a hardened target. We identified measures of effectiveness for the system, with the most significant being the ability of the sensor package to transmit relevant information before and after the impact with the target. We identified measures of performance with the most significant being the shock resistance of the sensor package.

We completed a hydrocode analysis to examine the shock requirements for a sensor package near a high-explosives blast. The amount of explosives modeled roughly approximated a large Joint Direct Attack Munitions (JDAM)–equipped bomb. The peak accelerations experienced by a nearby sensor package ranged between 100 and 1000 million g's, which destroyed the sensor package. This analysis represents a worst case. We made some attempts to mitigate the shock by adding material buffers between the high explosives and the sensor package, but in all cases the sensor package was destroyed. Future studies would focus on a sensor package in the new Small Diameter Bomb (SDB), which carries a much smaller warhead. Also, shock mitigation strategies would be studied to reduce the accelerations experienced by the sensor package.

We added a measure of performance for network latency to an SDAC system model. The measure of performance captures the impact of adding stationary nodes in a field of mobile nodes. The SDAC system model is being developed as part of a larger project and implements the physics of radio-frequency electromagnetic-wave propagation in addition to digital-network dynamics.

Energy and Critical Infrastructures

The Energy and Critical Infrastructures investment area supports Sandia's national security mission by developing and applying technologies for energy security, the surety of critical infrastructures, and their related environmental quality issues. The Energy and Critical Infrastructures area will mitigate international conflict through making clean, affordable energy and water available in the U.S. and elsewhere, especially in those areas of the world where tensions are high, by investing in the development of clean and efficient energy sources, unique and effective nuclear technology, infrastructure security, and water safety and sustainability.

In recent years, it has become increasingly clear that growing worldwide demand for potable water exceeds readily available supplies. Consequently, scarcity of fresh water is resulting in heightening political and economic tensions around the globe. *Specific Anion Nano-engineered Sorbents for Water Purification* is solving technological challenges innate to water safety, security, and sustainability by developing new methods for reducing dissolved arsenic (As) in water. Recent investigations resulted in new methods for enhancing As

uptake during standard coagulation and lime-softening. Additionally, Sandia identified a means for boosting As uptake *in situ* in As-contaminated aquifers. Three patent applications were submitted. This work involved collaboration with researchers at the University of New Mexico and elsewhere.

26551

Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations

T. M. Nenoff, G. B. Quijada, S. M. Thornberg, I. C. Abraham, D. E. Hunka

Sandia seeks to combine expertise in catalyst/zeolite synthesis, nanoscale-reaction kinetic testing, and catalytic testing to produce a novel selective catalytic system that is highly energy efficient and to develop analytical tools for rapidly assessing the nanoscale performance of catalysts. Current processes for manufacturing the commodity feedstock cumene (isopropylbenzene) involve a two-step process of heating reactants with acid catalysts ($= 300^{\circ}\text{C}$), and in some cases, cooling for transport ($= 25^{\circ}\text{C}$), followed by an energy-intensive distillation product separation ($= 130^{\circ}\text{C}$). Reaction and separation in a one-pot reactor and noncorrosive zeolite catalysts and the elimination of the cooling and transport steps will combine to produce a more efficient process with a potential tremendous payback in energy savings.

In this project, we will react synthesized catalysts with benzene and propylene reactants to produce the feedstock cumene. We will determine optimized catalyst choice through development and application of nanoscale kinetic tools obtained with Fourier-transform ion cyclotron resonance mass spectroscopy (FT-ICR/MS), a uniquely suited analytic tool. With FT-ICR/MS, the zeolite catalyst is fragmented by laser ablation and then allowed to interact with the hydrocarbon molecules. This gives binding energies, reaction mechanisms and kinetics, and gas-phase reactivity and selectivity of the catalyst per hydrocarbon system. Results from the nanoscale studies will guide which catalysts are tested in bulk scale in a unique one-pot combined catalytic reaction/distillation cumene synthesis process (130° – 200°C).

We had a number of accomplishments, all of which are resulting in publications in peer-reviewed journals, and one of which was submitted as a technical advance (TA) for a U.S. patent.

We successfully designed, built, and tested a new reactive/distillation reactor. The combined quartz and stainless-steel system allows for the introduction of the reactants propene and benzene into the reactor tower; reaction occurs over the catalyst, followed by (due to the difference in boiling points) separation of cumene product from excess benzene. This one-step system, which we submitted as a TA, does not require distillation for separation of the cumene from excess benzene, thereby allowing for enormous cost savings.

Sandia seeks to combine expertise in catalyst/zeolite synthesis, nanoscale-reaction kinetic testing, and catalytic testing to produce a novel selective catalytic system that is highly energy efficient and to develop analytical tools for rapidly assessing the nanoscale performance of catalysts....Reaction and separation in a one-pot reactor and noncorrosive zeolite catalysts and the elimination of the cooling and transport steps will combine to produce a more efficient process with a potential tremendous payback in energy savings.

We studied both batch and continuous fixed-bed catalytic reactions as methods for comparison of catalysts for cumene production. We conducted a number of experiments to find the best reaction conditions that yielded the highest production of cumene. We also investigated the life span and activity of modified beta catalysts. We performed quantitative analysis of product mixture by gas chromatography (GC) and found that beta zeolite produced the highest yield of all the materials tested, at 200°C in the batch reactor and at 225°C in the fixed-bed reactor. A benzene:propylene dilution of 7:1 molar ratio was the optimum in the batch reactor, whereas a ratio of 14:1 was the best for the fixed-bed reactor. Moreover, studies on the lifespan of modified beta catalysts showed that beta-Ga zeolite maintains the best activity for the first 3 hrs of reaction.

We achieved hydrocarbon (HC) attachment to zeolite fragments by introducing an HC gas into the FT-ICR/MS cell after laser ablation of the zeolite. Ethene, propene, and 1- and 2-butene successfully reacted with beta zeolite. For beta zeolite, we found that the OH cluster series reacted to the greatest extent with each HC gas that was injected into the cell to produce $[\text{SiO}_2]_n\text{OCxH}_{2x+1}$. For ethene and 1- and 2-butene, attachment to the AlO_2 series also occurs to produce $[\text{SiO}_2]_n\text{AlO}_2\text{CxH}_{2x}$. Although HC attachment is assigned through exact mass determination from the high resolution of the FT/MS, experiments with fully deuterated HCs confirmed these assignments. Each repeated experiment performed to date confirmed attachment as the series produced undergoes a mass shift of “x” daltons.

Refereed

Abraham, I. C., D. E. Hunka, G. Buelna, T. M. Nenoff, and S. M. Thornberg. 2003. Silica cluster generation from beta zeolite and surface-modified beta zeolite. *J. American Society Mass Spectrometry*, to be published.

Buelna, G., and T. M. Nenoff. 2003. A new reactive/distillation reactor system for the production of cumene. *J. Molecular Catalysis*, to be published.

Buelna, G., M. Kartin, and T. M. Nenoff. 2003. Alkylation of benzene using batch and continuous fixed-bed reactors. *Catalysis Communications*.

Buelna, G., R. Jarek, I. C. Abraham, S. M. Thornberg, and T. M. Nenoff. 2003. Real-time study of cumene formation based on GC-MS analysis. *J. Molecular Catalysis A: Chemical* **198** (1-2): 289-95.

Other Communications

Buelna, G., and T. M. Nenoff. 2003. Energy-efficient production of cumene. Paper presented at NAM, June, Cancun, Mexico.

Hunka, D., I. C. Abraham, T. M. Nenoff, and S. M. Thornberg. 2003. Hydrocarbon attachment to beta zeolite clusters generated using laser ablation and studied by Fourier-transform ion cyclotron resonance mass spectrometry (FT-ICR/MS). Paper presented at ASMS, 8-12 June, Montreal, Canada.

Thornberg, S. M., D. E. Hunka, I. C. Abraham, G. Buelna, and T. M. Nenoff. 2003. Hydrocarbon attachment to zeolite fragments using laser-ablation Fourier-transform ion cyclotron resonance mass spectroscopy. Paper presented at NAM, June, Cancun, Mexico.

26552

A Model of Infrastructure Interdependency Using Communication Agents

D. C. Barton, R. G. Cox, E. D. Eidson, D. A. Schoenwald, R. J. Pryor, J. A. Sprigg

U.S. infrastructure has always been vulnerable to malevolent acts and natural disasters. Today, however, the most serious threat comes from the increasing complexity of the system and its growing interconnectedness. The communications infrastructure is the link that allows interconnections between all other infrastructure networks and enables the transfer of goods, services, and information. Communications literally constitutes both the foundation and an upper limit to the economic functioning of a society.

Several research institutions, including Sandia, are developing agent-based models to simulate infrastructure systems. These models treat communications infrastructure simply as message passing between agents. A limitation of current agent-based infrastructure models is that communications is treated simply as always-successful message passing between agents. In other words, the communications infrastructure is not specifically represented. None of these models simulates the differences in communicating over telephone, computer, wireless, or other networks, and thus cannot determine the impact of specific failures in communications on the whole system. Nor can current models simulate the impact of other infrastructure failures on the communications infrastructure. A more useful agent model of infrastructure interdependency is one that would interpret communications as a separate agent system capable of creating, transforming, sending, receiving, and storing information and messages over time and across distance.

This project developed an agent-based model of infrastructure systems that explicitly simulates the dependence of infrastructure transactions on the communications infrastructure. Specific handling of communication systems in our agent-based models will clearly differentiate Sandia's capabilities in agent-based infrastructure simulations. This project provides a unique capability for developing financial threat assessments (i.e., business case models) to better understand the economic impact of critical-infrastructure failures and the potential impact that financial failures might have on national security.

This project developed an agent-based model of infrastructure systems that explicitly simulates the dependence of infrastructure transactions on the communications infrastructure....This project provides a unique capability for developing financial threat assessments...to better understand the economic impact of critical-infrastructure failures and the potential impact that financial failures might have on national security.

This project revised and restructured the Aspen-EE model to include a more realistic representation of the telecommunications infrastructure. This new model of infrastructure interdependency is called CommAspen, and communications is treated as an integrated agent system capable of creating, transforming, sending, receiving, and storing information and messages over time and across distance. CommAspen can be used to model communications networks or medium-specific vulnerabilities to failures and their dependence on supporting infrastructures like power. CommAspen can also be used to simulate the interdependent effects of market decisions and disruptions in the telecommunications infrastructure on other critical infrastructures in the U.S. economy, such as electric power, banking, and finance.

Revising Aspen-EE to become CommAspen entailed a major restructuring effort. We changed the model structure to an architecture that is much more generic and functional, and that allows us to build different types of agents based on capabilities or functionality. And, instead of having different types of markets, each with its specific rules, there is a generic market with a set of general rules. Using the inheritance capabilities of C++, we rewrote the general rules for both agents and markets to create specific types of capabilities that are tailored for the type of context and problem being addressed.

There are several ways that the notion of infrastructure is implemented in CommAspen. One method of representing certain types of infrastructure in CommAspen is through the use of spigots and sinks. Such infrastructures are for commodities that run continuously, like water from a municipality and electricity from a local utility. A sink is where a producer puts product into an infrastructure. For example, a power company may have an electric generator cranking out water in the desert. It would put power on the transmission lines by passing the power into the associated sink. A spigot is where a consumer gets the product, such as turning on the lights in a residence or getting water from a spigot.

We developed a new communications network for CommAspen. No previous Aspen model contained this type of structure. The purpose of the communications network is to represent more realistically the process by which agents communicate with each other across electronic media. The traditional message-delivery system, used in CommAspen and in previous Aspen models, features instantaneous receipt of a message once that message is sent. With the new network, delays are built into the process. Importantly, the new

We developed a new communications network for CommAspen. No previous Aspen model contained this type of structure.

communications network does not supplant the traditional message-delivery system. Instead, it is used in tandem with that system to handle only financial transactions that are used for the sample telecommunications problem.

The central hub of the communications network is a global router, a special agent in CommAspen. The router is connected to CommTerminals (communications terminals) that belong to the individual CommAgents in the simulation, forming what is known as a *star topology*. Agents use their CommTerminals to send messages to other agents.

Finally we implemented case studies of communication network congestion and router outages. The case studies focused on the finance/communications interdependency and provided a measure of the impact of communications failure on the economy.

The project implemented a series of case studies to test the model.

- Completed design and implementation of router and communications terminal classes to build communications networks in the model. We tested finance/communications interdependency.
- Implemented cases studies of communications network congestion and router outages. The case studies focused on the finance/communications interdependency and provided a measure of the impact of communications failure on the economy.
- Submitted a paper for publication in the *Proceedings 2004 American Control Conference*.

Other Communications

Barton, D. C., E. D. Eidson, D. A. Schoenwald, R. G. Cox, and R. K. Reinert. 2003. Simulating Economic Effects of Disruptions in the Telecommunications Infrastructure. Sandia Technical Report SAND2003-4473, Sandia National Laboratories, Albuquerque, New Mexico.

Cox, R. G., and R. K. Reinert. 2003. A Conceptual Model for U.S. Telecommunications Infrastructure—2003. Sandia Technical Report, Sandia National Laboratories, Albuquerque, New Mexico (in review).

Schoenwald, D. A., D. C. Barton, and M. A. Ehlen. 2003. An agent-based simulation laboratory for economics and infrastructure interdependency. *Proc. 2004 American Control Conference*, accepted.

26553

Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants

R. C. Hughes, L. K. McGrath, M. L. Thomas, C. E. Davis, C. K. Ho, J. L. Wright, A. S. Kooser

Tens of thousands of sites containing toxic chemical spills, leaking underground storage tanks, and chemical-waste dumps require characterization and long-term monitoring to reduce health risks and to ensure public safety. In addition, over two million underground storage tanks containing hazardous (and often volatile) contaminants are being regulated by the Environmental Protection Agency, and some form of monitoring is required to detect leaks from the tanks and pipe network. However, current methods are costly and time-intensive, and limitations in sampling and analytical techniques exist. For example, the Department of Energy Savannah River Site requires manual collection of nearly 40,000 groundwater samples per year, which can cost between \$100 and \$1000 per sample for off-site analysis (not including the cost of collection). In addition, as much as 80% of the costs associated with site characterization of a Superfund site can be attributed to laboratory analyses. The integrity of these analyses can also be compromised during sample collection, transport, and storage. Finally, although commercial tools are available for chemical detection (e.g., gas chromatographs [GCs]), few have been adapted for use in geologic environments for long-term monitoring or remediation applications. Therefore, a need exists for inexpensive, real-time, continuous, in situ sensing and characterization methods.

*Video of chemiresistor demonstration
(additional photos and video available at
www.sandia.gov/sensor).*

We performed numerous experiments at both the In Situ Sensing Lab and at the Integrated Materials Research Laboratory (IMRL) Chemiresistor Lab at Sandia to support the chemiresistor development and evaluations. Investigations included the following:

- We optimized and selected polymers for our particular applications and analytes of interest.
- We developed temperature control of the chemiresistor chip to improve the accuracy and stability of the chemiresistor sensors.
- We performed an analysis of the carbon concentration and carbon type on the sensitivity and noise of the chemiresistor to determine the optimal combinations. We employed theoretical models for polymer/carbon composites to predict the resistivity of our chemiresistors.

- Analysis of the limit of detection of our chemiresistors showed that without preconcentration, the limit of detection to trichloroethylene (TCE) was ~ 10 ppmv. With preconcentration, we found the limits of detection for m-xylene to be lowered by over 2 orders of magnitude.

The design and testing of preconcentrators to enhance the apparent sensitivity of the chemiresistors were also significant parts of our work. We fabricated the preconcentrators and developed tests that evaluated the heating and response of the preconcentrators. We also designed and tested an integrated preconcentrator/chemiresistor probe for field use.

We also investigated alternative designs and applications that produced some novel alternatives to the chemiresistor. These included the chemicouple, the ChemStick, and the bioresistor.

We evaluated data-analysis methods to determine approaches that could be used to provide both discrimination and quantification of target analytes with multiple input variables. We investigated the Visual Empirical Region of Influence (VERI) method along with partial least-squares. We also developed and deployed multivariate regression models generated by *Statistica*.

We also conducted three field studies to test the performance of the *in situ* chemiresistor sensor in actual environmental field conditions. We performed tests at Edwards Air Force Base, California, the Nevada Test Site, and the Chemical Waste Landfill, New Mexico, to determine engineering requirements for sensor deployment, data acquisition, power requirements, telemetry, data processing, and information dissemination. These tests culminated in a Web site that posts near-real-time data from chemiresistors and other sensors deployed at the Chemical Waste Landfill (www.sandia.gov/sensor/cwl). Results indicate that the chemiresistors are good candidates for long-term unattended *in situ* monitoring of volatile organic compounds (VOCs) in subsurface environments.

Finally, a “return on investment” revealed that this project has produced seven patent applications and eight technical advances, a dozen scientific publications, nearly 20 invited and contributed presentations, media coverage in over 30 magazines and news publications, a cooperative research and development agreement, Work for Others contracts, and collaborations with academic universities and other national laboratories.

...a “return on investment” revealed that this project has produced seven patent applications and eight technical advances, a dozen scientific publications, nearly 20 invited and contributed presentations, media coverage in over 30 magazines and news publications, a cooperative research and development agreement, Work for Others contracts, and collaborations with academic universities and other national laboratories.

Refereed

Ho, C. K. 2003. Development of an *in situ* chemiresistor sensor for continuous monitoring of volatile organic compounds in air, soil, and water. Paper presented at the 2003 FAME Symposium, August, Minneapolis, Minnesota.

Ho, C. K. 2003. From chemiresistor sensors to real-time subsurface hydrocarbon monitoring systems: Lessons learned. Paper presented at the National American Chemical Society Meeting, March, New Orleans, Louisiana.

Ho, C. K., and C. F. Lohrstorfer. 2002. Demonstration of chemiresistor microsensors for subsurface monitoring of volatile organic compounds. *Proc. Spectrum 2002 Conference 1* (CD-ROM) (August, Reno, Nevada): 1–7.

Ho, C. K., and C. F. Lohrstorfer. 2003. Subsurface monitoring of TCE using an *in situ* chemiresistor sensor. *Groundwater Monitoring and Remediation*, accepted.

Ho, C. K., E. R. Lindgren, K. S. Rawlinson, L. K. McGrath, and J. L. Wright. 2002. Development of a surface acoustic-wave sensor for *in situ* monitoring of volatile organic compounds. *Sensors 3*:236–47.

Ho, C. K., L. K. McGrath, and J. May. 2003. *In situ* chemiresistor sensors for monitoring subsurface contaminants. Paper presented at the 2003 CUPA Conference, February, Anaheim, California.

Hughes, R. C., C. K. Ho, and C. E. Davis. 2003. Chemiresistor microsensor arrays for detecting volatile organic chemicals. Paper presented at the 17th International Forum on Process Analytical Chemistry, February, Phoenix, Arizona.

Rivera, D. A., M. K. Alam, C. E. Davis, and C. K. Ho. 2002. Characterization of the ability of polymeric chemiresistor arrays to quantitate trichloroethylene using partial least-squares (PLS): Effects of experimental design, humidity, and temperature. *Sensors and Actuators B: Chemical 92*:110–20.

Rivera, D. A., M. K. Alam, C. K. Ho, and C. E. Davis. 2002. Application of multivariate calibration methods to chemiresistor array data. Paper presented at the Federation of Applied Chemistry and Spectroscopy Society Meeting, October, Providence, Rhode Island.

Rivera, D. A., M. K. Alam, C. K. Ho, C. E. Davis, R. J. Simonson, and W. G. Yelton. 2003. Augmented least-squares techniques and hybrid least-squares techniques for calibration maintenance of chemiresistor and surface acoustic-wave sensors. Paper presented at the Pittsburg Analytical Conference, March, Orlando, Florida.

Other Communications

Ho, C. K., J. L. Wright, L. K. McGrath, E. R. Lindgren, K. S. Rawlinson, and C. F. Lohrstorfer. 2003. Field Demonstrations of Chemiresistor and Surface Acoustic-Wave Microchemical Sensors at the Nevada Test Site. Sandia Technical Report SAND2003-0799, Sandia National Laboratories, Albuquerque, New Mexico.

Ho, C. K., L. K. McGrath, and J. May. 2002. FY02 Field Evaluations of an *In Situ* Chemiresistor at Edwards Air Force Base. Sandia Technical Report SAND2002-4135, Sandia National Laboratories, Albuquerque, New Mexico.

26554

Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management

Y. Wang, K. Yu, Y. Yang, P. L. Pohl, C. R. Bryan, C. J. Brinker, H. Gao

Successful nuclear-waste (and environmental) management requires the development of novel functional materials that can be used for effective waste treatment, containment, and monitoring. Traditional approaches for materials development are no longer able to meet increasing waste-management needs. Fortunately, with the emergence of nanotechnology, we are now able to manipulate material structures at nanoscales, thus opening up unlimited possibilities for new functional materials development. This project investigates the potential applications of mesoporous nanostructured materials (NsMs) in waste management. Mesoporous NsMs possess nanopore structures and are synthesized using self-assembled supramolecular templating processes. Due to very large surface area, controllable pore size, and overlapped electrical double layer, NsMs can potentially be good ion getters, separation membranes, catalysts, and sensing materials with high-sorption capacity and chemical selectivity. Specifically, Sandia will (1) study the sorption capability of mesoporous NsMs versus non-NsMs, (2) use surfactant-templating processes to synthesize mesoporous anionic clays and test their sorption capacity for arsenate and other anions, and (3) modify the pore-surface chemistry of mesoporous materials with functional molecules for developing high-performance ion getters. This work will demonstrate a wide range of applications of NsMs in nuclear-waste management and establish the theoretical foundation and engineering approaches for such applications. The success of the project will create a synergistic effect across Sandia's nuclear-waste/environmental management, advanced materials development, and chemical sensor development organizations, and can potentially attract investments from various customers.

We made significant progress in understanding the effect of nanoscale confinement on ion sorption by mesoporous materials. We demonstrated that the nanoscale confinement has a significant effect, most likely via the overlap of the electric double layer (EDL), on ion sorption onto mesoporous materials. We performed a molecular simulation using a density-functional theory to calculate ion-adsorption coefficients as a function of pore size. The calculation shows that as the pore size is reduced to nanoscales (< 10 nm), the adsorption

Transmission-electron microscope (TEM) (left) and high-resolution TEM (right) images of the titanium-oxide nanotubes synthesized using the method developed at Sandia.

This work will demonstrate a wide range of applications of NsMs in nuclear-waste management and establish the theoretical foundation and engineering approaches for such applications.

coefficients of ions can vary by more than 2 orders of magnitude relative to those for unconfined interfaces. We gained a great deal of experience in the purposeful control of morphologies and structures, e.g., interlayer spacing, of layered double hydroxides (LDHs) using surfactants. The engineered LDH materials show useful chemical and physical properties. Based on our knowledge obtained from synthetic materials, we developed a technique to form a continuous layer of metal-oxide nanocrystallites on granular bauxite materials for large-scale applications. We also developed a procedure for synthesizing nanotubes of titanium dioxide (TiO_2).

Refereed

Bryan, C. R., Y. Wang, H. Xu, P. S. Braterman, and H. Gao. 2003. Kinetics of anion sorption by Mg-Al layered double hydroxides. *Proc. Materials Research Society Symposium*.

Wang, Y., C. R. Bryan, H. Xu, and H. Gao. 2003. Nanogeochemistry: Geochemical reactions and mass transfers in nanopores. *Geology* **31**:387–90.

Wang, Y., C. R. Bryan, H. Xu, and H. Gao. 2003. Surface chemistry of mesoporous materials: Effect of nanopore confinement. *Proc. Materials Research Society Symposium*. **751**:121–25.

Wang, Y., C. R. Bryan, H. Xu, P. L. Pohl, Y. Yang, and C. J. Brinker. 2003. Interface chemistry of nanostructured materials: Ion adsorption on mesoporous alumina. *J. Colloid and Interface Science* **254**:23–30.

Xu, Z. P., and P. S. Braterman. 2003. High affinity of dodecylbenzene sulfonate for layered double hydroxides (LDH) and the resulting morphologies. *J. Mater. Chem.* **13**:268.

26555

Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles

H. A. Michelsen, T. B. Settersten, P. O. Witze

Newer-generation compression-ignition direct-injection (CIDI) diesel engines, which have been designed for low-particulate-matter mass emissions, emit no visible soot, but they may generate far greater numbers of small particles than older diesel engines. Hybrid cars incorporating CIDI engines are expected to be commercially available in the U.S. by 2004. New evidence strongly suggests that gasoline engines also emit large numbers of small particles under some operating conditions. These small (submicron) particulates are classified as a toxic emission in California, may pose a greater health risk than larger soot particles, and are expected to have a significant impact on the Earth's climate. Small particulate emissions are thus of emerging concern.

Sandia is developing a new capability at the Combustion Research Facility (CRF) to determine size and mass distributions of submicron soot particles for future studies of their formation in flames and in diesel and gasoline engines and their evolution when cooled and diluted. Our goal is to study nanoparticle formation and evolution using noninvasive optical techniques, particularly laser-induced incandescence (LII), for measuring particle mass concentrations and elastic laser scattering (ELS) for determining particle size. We are refining quantitative aspects of LII/ELS and determining sensitivities of these techniques to particle morphology and composition. In addition, we are investigating whether laser-induced desorption (LID) can be used to identify the composition and volume fraction of volatile coatings that condense on these particles in combustion emissions. Complementary modeling studies focus on processes by which these particles absorb, scatter, and emit light, and evolve during laser heating and radiative, evaporative, and conductive cooling.

LII involves heating the soot particles by laser irradiation to temperatures (2500–4500 K) at which they incandesce, i.e., emit observable blackbody radiation, and detecting the emitted light. In our experiments, we heated soot particles with pulses of ~ 70 ps duration (20 Hz) at 532 nm from a regeneratively amplified Nd:YAG (neodymium:yttrium aluminum garnet) laser. Because LII is extremely nonlinear with laser fluence, a

Sandia is developing a new capability at the Combustion Research Facility (CRF) to determine size and mass distributions of submicron soot particles for future studies of their formation in flames and in diesel and gasoline engines and their evolution when cooled and diluted. Our goal is to study nanoparticle formation and evolution using noninvasive optical techniques, particularly laser-induced incandescence (LII), for measuring particle mass concentrations and elastic laser scattering (ELS) for determining particle size.

homogeneous laser-beam spatial profile is critical for interpreting the results. Our experimental setup includes an aperture placed in the laser beam and imaged into the flame to provide a homogeneous spatial profile, which we characterized using a charge-coupled-device (CCD) camera. We imaged the signal onto one side of the slit of a streak camera and collected it over the wavelength range 590–900 nm. We collected ELS simultaneously on each laser shot on the other side of the slit. Using this arrangement, we collected data from an atmospheric ethylene coflow diffusion flame to fluences as high as 0.3 J/cm^2 with a temporal resolution of $\sim 65 \text{ ps}$.

We will use these data to refine an LII model that accounts for particle heating by laser absorption, oxidation, and annealing, and for particle cooling by sublimation, conduction, and radiation. The model also includes mechanisms for convective heat and mass transfer, melting, and nonthermal photodesorption of carbon clusters. We designed this experiment to investigate the latter mechanism, fast photodesorption.

At laser fluences below $\sim 0.2 \text{ J/cm}^2$, temperatures increase rapidly during the laser pulse and slowly decay (on microsecond time scales) following the laser pulse. This slow decay is predominantly due to conductive cooling. At higher fluences, particles quickly reach and surpass the sublimation temperature of $\sim 4000 \text{ K}$, becoming superheated, and then cool via sublimation back to the sublimation point. Sublimation also causes particles to decrease in size. At higher fluences, decay rates during and just after the laser pulse are fast, which may be largely attributable to photodesorption of carbon (C) clusters.

The model descriptions of cooling and mass loss by sublimation and photodesorption are the most important terms for calculating the temporal behavior and magnitude of the LII signal at fluences above 0.2 J/cm^2 . This part of the model is also the most complex and, in the case of photodesorption, the most uncertain. Although previous studies suggested that laser photodesorption of C clusters from graphite can proceed by a nonthermal mechanism, the nature of this mechanism, including the number of photons required, is not known. Our model includes such a mechanism with a cross section and enthalpy of reaction approximated by comparing the results with the data. We added this mechanism to the model to account for a fast decay in signal during a 7 ns laser pulse at high fluences. Including the nonthermal photolysis term also allows the model to reproduce the lack of fluence dependence of the peak signal at fluences above 0.2 J/cm^2 when a 7 ns laser pulse is used to heat the particles.

To make these measurements more useful for understanding these fast processes, we will improve our optical layout to (1) increase the signal so that we can improve our temporal resolution and (2) record LII profiles at fluences higher than 0.3 J/cm².

Refereed

Michelsen, H. A. 2003. Understanding and predicting the temporal response of laser-induced incandescence from carbonaceous particles. *J. Chemical Physics* **118**:7012–45.

Michelsen, H. A., P. O. Witze, D. Kayes, and S. Hochgreb. 2003. Time-resolved laser-induced incandescence of soot: The influence of experimental factors and microphysical mechanisms. *Applied Optics* **42**:5577–90.

Other Communications

Michelsen, H. A. 2003. Exploring the applicability and limitations of laser-induced incandescence for soot detection. (Invited) Talk presented at Wright-Patterson Air Force Base, August, Dayton, Ohio.

Michelsen, H. A., P. O. Witze, B. Axelsson, T. B. Settersten, E. H. Chrysostom, D. Kayes, and S. Hochgreb. 2003. Understanding and predicting the temporal response of laser-induced incandescence from carbonaceous particles. Paper presented at the Western Spectroscopy Association 50th Anniversary Meeting, January, Monterey, California.

26557

Specific Anion Nanoengineered Sorbents for Water Purification

P. V. Brady, N. R. Khandaker, J. L. Krumhansl, M. D. Siegel

The U.S. drinking-water limit for arsenic (As) has been lowered from 50 mg/L to 10 mg/L. The annual nation-wide cost of compliance is estimated to be several hundred million dollars, much of the burden falling on rural water systems. This has prompted a renewed search for cheaper, more effective As-removal approaches. Sandia developed a series of As-removal technologies in anticipation of the new drinking-water limit. They were developed from a comprehensive analysis of the chemical controls over As uptake by solids and are collectively referred to as specific anion nanoengineered sorbents (SANS). SANS includes new filter media possessing higher uptake capacity for As than industry standards, new approaches to enhance lime-softening and coagulation-removal of As, and a new approach for lowering As levels in situ in an aquifer.

(1) We conducted a pilot test at Kirtland Air Force Base to compare sorbent performance.

(2) We performed pilot testing of coagulation SANS through CH2M-Hill at Fallon, Nevada.

(3) We performed pilot testing of filtration SANS through CH2M-Hill at El Paso, Texas.

(4) We performed pilot testing of filtration SANS through the University of New Mexico.

(5) We submitted two patents on *in situ* SANS and lime-softening SANS.

(6) We wrote four manuscripts, but have not yet submitted them, pending patent office action.

(7) We pursued licensing of SANS; it is now pending.

(8) We experimentally examined the impact of copper leaching from SANS.

(9) We manufactured several kilograms of SANS for pilot testing.

(10) We standardized the SANS manufacture approach.

(11) We made several conference presentations describing performance.

(12) We developed a surface complexation model describing As uptake by SANS.

(13) We did surface titrations measuring the pH-dependent surface charge of SANS.

Computer image of arsenate ion sorbing onto an oxide surface. The image is generated using a form of quantum mechanical modeling called density-functional theory that examines the electrostatic potential surfaces of the two materials.

Sandia developed a series of As-removal technologies in anticipation of the new drinking-water limit. They were developed from a comprehensive analysis of the chemical controls over As uptake by solids and are collectively referred to as specific anion nanoengineered sorbents (SANS).

(14) We explored perchlorate sorbing materials (SANS and others).

(15) We filed a technical advance describing perchlorate sorption and retention by novel materials.

32807

Low-Work-Function Material Development for the Microminiature Thermionic Converter

D. B. King, D. R. Jennison, C. C. Battaile, K. R. Zavadil

Microminiature thermionic converters (MTCs) provide a unique approach to developing power sources. Possible applications range from micron- to large-scale and include microrobotics and sensors, space-based power, mobile and remote electrical-power sources, and commercial power production. MTCs can be scaled from the microwatt range to kilowatts. Sandia made significant progress in developing small-scale MTCs; however, the electrode materials are not well understood, and thermionic properties are highly sensitive to the electrode chemical content, bulk structure, and manufacturing processes. Advanced theoretical and modeling capabilities are required to achieve the desired thermionic emission from the electrode materials, aid in the electrode-fabrication process, and enhance the performance of MTC diodes. Sandia's advanced thermionic theory and detailed modeling of properties influencing thermionic-electron-emission performance will greatly enhance understanding of thermionic diodes. Using only experimental development is costly; a better theoretical understanding is needed to guide the expensive experimental fabrication process.

A combined experimental and theoretical program is guiding the development of advanced electrode materials. Sandia's materials and computing capabilities are used to develop complex physical models of thermionic emission from the electrode surfaces. This integration of Sandia's development and test experience, advanced modeling, microfabrication, and materials expertise will make Sandia a world leader for advanced thermionic-energy-conversion technology and MTC development. We developed and tested a prototype MTC diode. The diodes are an innovative design using advanced electrode materials to convert heat to electricity. These diodes have the potential for operating at low temperatures (below 1200 K), while increasing conversion efficiency (up to 25%) and increasing the electrical power density to tens of watts per centimeter squared. Currently, the prototype MTCs fall short of theoretical-performance predictions due to poor performance from the electrode materials. This program is vital to the development of potentially revolutionary MTC devices.

We further developed a thin-film microdispenser cathode and identified the primary limits to reliable operation of the

Sandia's advanced thermionic theory and detailed modeling of properties influencing thermionic-electron-emission performance will greatly enhance understanding of thermionic diodes....Sandia's materials and computing capabilities are used to develop complex physical models of thermionic emission from the electrode surfaces. This integration of Sandia's development and test experience, advanced modeling, microfabrication, and materials expertise will make Sandia a world leader for advanced thermionic-energy-conversion technology and MTC development.

films. We specifically focused on characterizing the microstructural evolution and emission properties of the films as a function of annealing time and temperature and compared these changes with commercial macroscale dispenser cathodes. We were awarded a U.S. patent for this concept.

After first-principles theoretical studies demonstrated accuracy in the computation of the work function of the clean tungsten (W) surfaces of (100) and (110), we turned to the study of barium (Ba), barium oxide (BaO), and mixed Ba, strontium (Sr), and oxygen (O) overlayers. In agreement with experiment, we found in somewhat reduced overlayers that the preferred structure is BaO/SrO/W(100). We noted that the rock-salt structure of the first two layers causes great stability. However, the work function of this material, at 1.8 V, is far above the lowest experimental numbers. We found that pure Ba metal has the same work function as an overlayer of BaO, which violates simple models where surface dipoles determine the work function. Finally, we found it is necessary to have a bilayer of BaO to reduce the work function to experimentally observed values of about 1.3 V. We therefore suggest that the rock-salt stability prevents the monolayer of BaO from ever forming, and if that much Ba is in the surface, it will always form islands of bilayers of BaO. Further theoretical and experimental analyses are indicated.

Microstructure modeling work continued on the structural evolution of layered films. We focused on the effects of surfactant on the coarsening of two-phase layered structures. We performed simulations of microstructural coarsening in a varying concentration field, with coarsening rate proportional to concentration. After an initial transient during which the multiphase layers “collapse” onto one another near the surfactant source, we observed that directional coarsening was qualitatively similar to experimental observations.

We successfully benchmarked the patch model developed previously against thermionic emission of actual microdispenser test cathodes. This cathode type exhibited non-Schottky-type current emission in the Schottky regime of operation (emission was higher than expected). We incorporated into the patch model a model that we developed previously to predict this anomalous emission based on field incursion into the cathode film material.

We specifically focused on characterizing the microstructural evolution and emission properties of the films as a function of annealing time and temperature and compared these changes with commercial macroscale dispenser cathodes. We were awarded a U.S. patent for this concept.

32809

Autonomous Microexplosive Subsurface Tracing System

N. R. Warpinski, S. H. Kravitz, M. C. Grubelich, J. Nogan, B. P. Engler, R. R. Rivas, G. R. Dulleck, Jr., P. W. Cooper

The objective of the autonomous microexplosive subsurface tracing system is to image the location and geometry of hydraulically induced fractures in subsurface petroleum reservoirs. Sandia based this system on the insertion of a swarm of autonomous microexplosive packages during the fracturing process, with subsequent triggering of the energetic material (EM) to create an array of microseismic sources that can be detected and analyzed using existing seismic receiver arrays and analysis software. The project included investigations of energetic mixtures, triggering systems, package size and shape, and seismic output. Given the current absence of any technology capable of such high-resolution mapping of subsurface structures, this technology has the potential for major impact on the petroleum industry, which spends approximately \$1 billion per year on hydraulic fracturing operations in the U.S. alone.

Our accomplishments include (1) the development of a preparation method for the MgAgNO_3 mixture that appears to be an optimum formulation, (2) initial assembly of microexplosive pellet canisters for use in testing, (3) testing of the microexplosive mixture (and other formulations) in the test chamber, (4) further study of pellet-shape effects, (5) continued optimization of the semiconductor bridge (SCB) for use in microapplications, and (6) continued examination of timing and power capabilities and limitations.

Previous work showed the MgAgNO_3 mixture to be a suitable energetic mixture for the microexplosive based on its fast burn rate and activation when contacted by water. We prepared some test pellets with the formulation (including mixing procedures for the MgAgNO_3 , capsule preparation, and sealing) as 1 g microexplosives. The microexplosives were designed as pellets in the shape of an elongated cylinder. Design estimates showed that elongated capsules would align with the flow direction in the typical non-Newtonian fluids used in hydraulic fracturing applications (i.e., would not turn broadside and bridge). However, these elongated cylinders would not be appropriate in Newtonian fluids, and spherical pellets would be required.

Given the current absence of any technology capable of such high-resolution mapping of subsurface structures, this technology has the potential for major impact on the petroleum industry, which spends approximately \$1 billion per year on hydraulic fracturing operations in the U.S. alone.

We also tested other 1 g materials, including the MgAgNO_3 , pentaerythritol tetranitrate (PETN), titanium subhydride potassium perchlorate (THKP), diazudinitrophenel (DDNP), and bis(5 nitrotetrazolato)pentaaminocobalt(III) perchlorate (BNCP), in the microexplosive chamber to compare pressure response in order to have other options if the MgAgNO_3 were too slow a rate under actual practice. As would be expected, all of these provided faster pressure rises, with the PETN and BNCP being the highest, and the THKP and DDNP being intermediate and possible candidates for a secondary charge or for an electronic triggered system. Some flexibility in the system is necessary because different applications may require considerably different energy and frequency content.

While work continued on optimizing the SCBs for this microexplosive application, other work focused on the entire firing circuit. Such a circuit would include a microtriggering processor and a voltage generator with a discharge element. When powered with a miniature 3 V battery, the circuit is capable of firing several low-ohm SCBs. Rise times of the devices were on the order of 1 μs , and several hundred microjoules of energy were transferred.

The final project task was to be a field test in a cement block or an outcrop to test the amount and frequency content of the energy coupled into the rock when the microexplosive is fired within a proppant and fluid-filled fracture. While we completed the design of a field test in a cement block and initiated preparations, we could not obtain an Air Force permit in any reasonable timeframe and did not conduct the field test.

32816

Vulnerability Assessment of National Power Grid

D. G. Robinson, A. E. Lutz, R. E. Carlson

In this project, Sandia concentrated on the identification of critical nodes within the national bulk-power system. These are nodes that would cause the most widespread, immediate damage if they were disrupted through natural events or terrorist action. Through the identification of critical elements, we can focus site-specific vulnerability analyses at those locations where additional security measures could be effectively implemented. Even without additional security measures, increased awareness of sensitive nodes can provide a basis for more-effective emergency planning such as the pre-positioning of critical spares. Contingency analysis has been the focus of much research in the past few years, but the emphasis has remained on naturally occurring failure rates. Rather than duplicate the direction of these research efforts, we decided to emphasize a more systemic theoretical approach. We investigated three alternative methodologies: complex network theory, polyhedral dynamics, and particle swarm intelligence.

The objective of this research was the development of a methodology to identify vulnerabilities within the national bulk-power system. We investigated three areas of interrelated research. The first two areas involved preliminary investigation of modeling methods for including secure control and data acquisition (SCADA) and power parks within traditional power-flow analyses. The third area, the largest, involved developing algorithms to identify vulnerable points. Software developed to support the last area was intentionally left open to allow SCADA and power-park models to be introduced as they matured.

Accomplishments associated with the SCADA modeling effort began with the development of a preliminary model of SCADA system elements. We then represented the SCADA model in the Unified Modeling Language (UML) in the Rational Rose™ development environment for real-time systems. Unfortunately, the model never became stable enough to integrate with other software developments. Further development is the objective of a separate ongoing research project.

The power-park modeling activity resulted in the development of a model of a typical distributed-energy system using a library of Simulink modules. The system generates H₂

In this project, Sandia concentrated on the identification of critical nodes within the national bulk-power system. These are nodes that would cause the most widespread, immediate damage if they were disrupted through natural events or terrorist action.

by means of a steam-methane reformer (SMR) that runs at steady state. The H_2 is fed a fuel-cell stack to follow a local load over a daily-use cycle, or compressed and stored in a high-pressure vessel for later use. When connected to a model of the grid, the stored H_2 could be used by the fuel cell to supply power to the grid. The model evaluates the combined efficiency of the power system. Rather than integrate the Simulink model with the C programs, we successfully used the model to justify spin-off of the research into an H_2 unique research project.

The majority of funding focused on the identification of vulnerabilities within the physical elements of the bulk-power system; thus, this constituted the bulk of the research and the results. The objective of this portion of the research was to explore alternative, nontraditional methods of identifying critical elements in a bulk-power system. Through the identification of critical elements and the quantification of the consequences of their failure, we can focus site-specific vulnerability analyses at those locations where additional security measures can be effectively implemented. Also, with appropriate sizing and placement within the grid, distributed generation in the form of regional power parks may reduce or even prevent the impact of widespread network power outages. Even without additional security measures, increased awareness of sensitive nodes can provide a basis for more-effective national, state, and local emergency planning. Locations and types of critical nodes can also be used to pre-position spares.

Historically, utilities identify single points of vulnerability through a first-order contingency analysis. The reaction of the grid to the disruption is analyzed using a computer model of the power redistribution that results. Reliability indices are collected and the simulation of contingencies continues until convergence is reached. With the computational power available today, enumeration of all possible single-point contingencies is a possibility. However, nonlinearities and synergistic effects preclude simply exploring and ordering all first-order contingencies.

We investigated three alternative methodologies: complex network theory, polyhedral dynamics, and particle swarm intelligence. We selected an approach based on artificial intelligence swarm methods and applied this approach to a number of bulk-power-system test cases. We demonstrated that optimal points of disruption can be identified.

The algorithm we developed can easily be extended to other infrastructures or mixtures of infrastructures. In addition, the approach is scale-free and can be used at the local distribution level as well as on large systems on the order of national

The algorithm we developed can easily be extended to other infrastructures or mixtures of infrastructures. In addition, the approach is scale-free and can be used at the local distribution level as well as on large systems on the order of national interconnections. (The algorithm is readily suited for implementation on massively parallel computational platforms.)

interconnections. (The algorithm is readily suited for implementation on massively parallel computational platforms.)

We are currently working with engineers at the Bonneville Power Association (BPA) to integrate the algorithm with the BPA power-flow code and to apply the method to the Western States Coordinating Council's power interconnect.

Refereed

Lutz, A. E., R. S. Larson, and J. O. Keller. 2003. Thermodynamic comparison of fuel cells to the Carnot cycle. *Int. J. Hydrogen Energy* **27**:1103–11.

Lutz, A. E., R. W. Bradshaw, J. O. Keller, and D. E. Witmer. 2003. Thermodynamic analysis of hydrogen production by steam reforming. *Int. J. Hydrogen Energy* **28**:159–67.

38662

Natural-Gas Production Problems: Solutions, Methodologies, and Modeling

J. C. Lorenz, J. F. Holland, R. G. Keefe, B. W. Arnold, S. P. Cooper, W. A. Olsson, J. M. Herrin

Natural gas is a clean fuel that will be the most important domestic energy resource of the 21st century. Ensuring a stable supply is essential for our national energy security. This research project will maximize the extractable volume of gas while minimizing the environmental impact of surface disturbances associated with drilling and production. Sandia is developing a system for comprehensive evaluation and modeling of the total gas system within a basin, focusing on problematic horizontal fluid-flow variability. We are addressing this through interpretation and analysis of core (rock sample) and outcrop data to interpret and predict directional flow and production trends. We are modeling the deformation history of the reservoir strata and undertaking the natural-gas production from the strata. Side benefits will include a first-order approximation of probable carbon-dioxide (CO₂) flow patterns during sequestration (injection and storage) of this greenhouse gas, and reduced environmental impact of drilling due to reduced number of required wells for resource extraction.

We are undertaking these tasks through a cooperative and integrated systems approach involving industry, government, academia, and a multiorganizational team within Sandia. We will have received from El Paso Production Co. extensive core data, production data, maps, seismic data, coal desorption analyses, production analyses, and engineering studies. We received unlimited access to the Vermejo Park ranch for field study, the area of principle production on the New Mexico side of the basin.

Ultimately, this approach will provide innovative ideas and technologies to reduce the overall environmental impact of drilling. More importantly, the products of this research will not be location-specific but can be extended to other areas of gas production throughout the Rocky Mountain area. Thus, this project has the potential to grow into a continuing program designed to solve problems associated with natural-gas production at developing sites, or at old sites under redevelopment.

Our team of geologists, engineers, modelers, and rock mechanicians has reached several important conclusions to date.

Sandia is developing a system for comprehensive evaluation and modeling of the total gas system within a basin, focusing on problematic horizontal fluid-flow variability. ...Ultimately, this approach will provide innovative ideas and technologies to reduce the overall environmental impact of drilling....this project has the potential to grow into a continuing program designed to solve problems associated with natural-gas production at developing sites, or at old sites under redevelopment.

(1) The thick shale sequence that underlies the reservoir-bearing strata has not behaved passively as expected, but rather models using the large-deformation, nonlinear finite-element code JAS3D suggest that it was of primary importance during deformation of the entire stratigraphic sequence during Laramide thrusting.

(2) The significantly different Poisson's ratio of coal was shown to be of primary importance in the location of the volcanic injections (dikes and sills) that permeate the basin. Whereas vertical dikes would be emplaced in most strata at depths below 1500 ft, horizontal sills are the preferred mode of injection in coal beds up to 8000 ft deep due to differences in the *in situ* stress caused by the Poisson's ratio that can range up to twice that of other strata.

(3) Natural fractures trend approximately east-west as expected across much of the basin, but secondary fractures were superimposed onto the east-west patterns where local anticlines and faults interrupted the thrust-related stress trajectory during fracturing. Secondary fracture sets are also present near the western edge of the basin, trending north-south. The origin of these fractures is as yet obscure.

(4) We developed several testable hypotheses for the differences in gas-water production ratios for areas north and south of the Vermejo Park anticline. These hypotheses include differences in erosion levels in the two areas and differences in the underlying tectonics and structure.

(5) We tentatively identified the local north-south fracture patterns as the cause of local anomalies in production and of local north-south interference patterns.

(6) We developed a mechanical stratigraphy for the stratigraphic succession and related it to significant differences in fracture patterns through the section. Long parallel extension fractures occur in limestones and in the strata containing numerous lithic sand grains; more closely spaced but shorter, parallel extension fractures occur in the cleaner, better-cemented sandstones. We identified conjugate fractures in the well-cemented conglomerates and locally in some of the strata at the distal edge of the basin.

Examination of several thousand feet of core shows that subsurface fracture patterns mimic surface patterns to some degree, but that significant differences exist. Fractures in nonsand lithologies are more common in the subsurface than examination of the outcrops would suggest. We have identified no conjugate fracture patterns in the subsurface.

Other Communications

Arnold, B. W., J. M. Herrin, J. C. Lorenz, and P. W. Basinski. 2003. Statistical and geostatistical analyses of coal-bed methane production in the Raton Basin, New Mexico, and Colorado.

Abstracts with Programs, Proc. American Association of Petroleum Geologists Annual Meeting 1 (April 2004, Dallas, Texas).

Cooper, S. P., J. C. Lorenz, and R. G. Keefe. 2002. Interpreting natural fracture patterns in outcrop in the Raton Basin of Colorado and New Mexico.

Abstracts with Programs, Proc. American Association of Petroleum Geologists, Rocky Mountain Section Meeting 1 (8–10 September, Laramie, Wyoming): 21.

Cooper, S. P., P. M. Basinski, R. Larson, J. M. Herrin, and R. G. Keefe. 2003. Natural fracture patterns within the Raton Basin of Colorado and New Mexico. *Abstracts with Programs, Proc. American Association of Petroleum Geologists Annual Meeting 1* (April 2004, Dallas, Texas).

Herrin, J. M. 2003. Integrating geologic and hydrologic information to mitigate produced water in the Raton Basin of New Mexico and Colorado. *Proc. International Petroleum Environmental Conference 1* (8–11 October, Albuquerque, New Mexico).

Herrin, J. M., P. M. Basinski, J. C. Lorenz, S. P. Cooper, C. A. Rautman, and B. W. Arnold. 2003. Integrating geologic and hydrologic information to identify coal-bed methane sweet spots in the southern Raton Basin, New Mexico. *Abstracts with Programs, Proc. American Association of Petroleum Geologists Mid-Continent Meeting 1* (11–14 October, Tulsa, Oklahoma).

Lorenz, J. C., S. P. Cooper, and R. G. Keefe. 2003. Syn-sedimentary deformation in the central Raton Basin, Colorado and New Mexico: A potential control on sandbody orientation. *Abstracts with Programs, Proc. American Association of Petroleum Geologists Annual Meeting 1* (11–14 May, Salt Lake City, Utah): A107.

38664

High-Efficiency Turbine Blade Coatings

D. L. Youchison, R. E. Nygren, T. L. Aselage, G. A. Hebner, M. A. Gallis, F. J. Bauer, T. J. Tanaka, T. J. Lutz, J. M. McDonald, S. Graham, Jr.

The development of advanced thermal-barrier coatings (TBCs) of yttria-stabilized zirconia (YSZ) that exhibit lower thermal conductivity through better control of electron beam–physical vapor deposition (EB-PVD) processing is of prime interest to both the aerospace and power industries. In this project, Sandia seeks to produce lower thermal conductivity, graded-layer, thermal-barrier coatings for turbine blades in an effort to increase the efficiency of high-temperature gas turbines.

We developed the processing technology to create graded TBCs by coupling ion-beam–assisted deposition (IBAD) with substrate pivoting in the alumina-YSZ system. We used the electron beam-1200 kW (EB-1200) PVD system to deposit a variety of TBC coatings with submicron-layered microstructures and reduced thermal conductivity below 1.5 W/mK. The use of IBAD produced fully stoichiometric coatings at a reduced substrate temperature of 600°C and a reduced oxygen background pressure of 0.1 Pa. We also used IBAD to successfully demonstrate the transitioning of amorphous PVD–deposited alumina to the α -phase alumina required as an oxygen diffusion barrier and for good adhesion to the substrate's Ni_2Al_3 bondcoat. This process replaces the time-consuming thermally grown oxide formation required before the YSZ deposition. In addition to the process technology, we performed direct-simulation Monte Carlo (DSMC) plume modeling and spectroscopic characterization of the PVD plumes.

The project consisted of five tasks. These included the production of layered periodic microstructures in the coating, the DSMC modeling of particle transport in the PVD plume, functional graded-layer development, the deposition of all layers to form a complete coating, and related materials characterization. We used IBAD, beam sharing through advanced digital rastering, substrate pivoting, hearth calorimetry, infrared (IR) imaging, fiber-optic–enabled optical-emission spectroscopy, and careful thermal management to achieve all the proposed milestones.

Earlier work included attempts to produce layered YSZ with the EB-1200 using 30 deg substrate pivoting at 90 s

...Sandia seeks to produce lower thermal conductivity, graded-layer, thermal-barrier coatings for turbine blades in an effort to increase the efficiency of high-temperature gas turbines. ...This process replaces the time-consuming thermally grown oxide formation required before the YSZ deposition.

intervals. These features were on the 10 μm scale. We demonstrated layering to submicron levels and produced layers with a periodic thickness of only 0.5 μm . This was our highest periodicity.

Computer simulations concentrated on particle transport in mixed plumes. In one-species plumes, the deposition rate is essentially a constant fraction of the evaporation rate dependent on geometry and vacuum conditions. However, in mixed plumes, heavier atoms or clusters can impact the transport of lighter atoms through collisions. The DSMC results show that relative deposition rates are no longer simply related to the evaporation rates of individual constituents.

We successfully controlled mixed plumes from a dual-source PVD arrangement. Deposition of alumina/YSZ graded layers was now possible with the EB-1200.

We successfully deposited α -phase alumina using IBAD. We demonstrated an easily controllable process to transition physical vapor-deposited amorphous alumina to α -phase alumina using IBAD. This technology greatly reduces the processing time from the several hours required to thermally grow the oxide layer and its subsequent phase-transformation heat treatment to only a few minutes. The settings and parameters used for the process are patentable, and we submitted a technical advance.

Due to schedule limitations, we did not minimize the pure alumina-layer thickness. Although we added a few coatings to thermal fatigue during normal processing, we did not perform a systematic campaign of thermal fatigue testing and a ranking of coatings based on our figure-of-merit due to poor adhesion.

We successfully performed optical-emission spectroscopy in the 900°C environment of the PVD plume. We obtained spectra for various operating parameters for both IBAD and non-IBAD plumes.

We identified the best samples produced to date and measured their material properties, such as composition and phase, with energy-dispersive x-ray (EDX) and x-ray diffraction (XRD). We measured thermal conductivity using the 3 ω technique.

This project successfully demonstrated that IBAD and substrate pivoting can create a layered morphology on the submicron level in YSZ that results in reduced thermal conductivity compared to commercially available EB-PVD coatings. The pivoting changes the grain orientation and increases the number of grain boundaries, while periodic IBAD kept the PVD columnar grains from growing too large, thus maintaining the higher intergranular porosity that impedes

This project successfully demonstrated that IBAD and substrate pivoting can create a layered morphology on the submicron level in YSZ that results in reduced thermal conductivity compared to commercially available EB-PVD coatings.

thermal conduction. We obtained reduced conductivities as low as 1.4 W/m·K.

Refereed

Youchison, D. L., M. A. Gallis, R. E. Nygren, J. M. McDonald, and T. J. Lutz. 2003. Effects of ion-beam–assisted deposition, beam sharing and pivoting in EB-PVD processing of graded thermal-barrier coatings. *Surface Coatings and Technology*.

38665

Time-Domain Reflectometry for Remote, Real-Time Water-Quantity/-Quality Monitoring of Perennial and Ephemeral Streams

V. C. Tidwell, D. S. Ruby, L. M. Desonier, J. R. Brainard, J. D. Roberts

Thousands of acre-feet of water go unutilized in New Mexico every year because of inadequate stream gauging, costing the state millions of dollars in lost economic development. Sandia proposed time-domain reflectometry (TDR) as a remote, real-time method for monitoring the quantity and quality of perennial and ephemeral stream flows. TDR operates by propagating an electromagnetic (EM) pulse down a transmission line while monitoring the returned signal. The pulse is susceptible to reflection by dielectric discontinuities (i.e., air-water and water-sediment interfaces) and attenuation by clays and salts. Thus, with one method we can measure the depth of water, depth of scour, sediment load, and salinity both simultaneously and at numerous locations across the channel.

Development of this monitoring system will begin in the laboratory where we will test, calibrate, and optimize the TDR sensor for this application. We will conduct controlled experiments under static conditions using sand tanks and under simulated stream conditions using the Sediment Erosion Flume at Sandia-Carlsbad. We will also design, test, and optimize a remote-monitoring package, including photovoltaic (PV)/battery power, telemetry, Web-based data management/visualization, and analysis software. As part of this effort we will investigate ways to miniaturize and minimize the cost of the monitoring system. In cooperation with the U.S. Geological Survey (USGS), we will conduct field-testing of the full TDR monitoring package on local perennial/ephemeral streams.

Water managers in New Mexico agree that stream gauging is one of the highest-priority issues in the state. Relative to current technology, the TDR system offers the advantage of real-time monitoring, concurrent water-quality/-quantity monitoring, and improved precision by way of multiprobe sampling, all at a reduced cost. As such, we believe this monitoring technique has significant market potential, both here and abroad, once fully developed.

(1) *TDR data analysis.* Key to the success of this project is the ability to extract information on stream stage, channel profile, and salinity from the measured TDR trace data.

Sandia proposed time-domain reflectometry (TDR) as a remote, real-time method for monitoring the quantity and quality of perennial and ephemeral stream flows.

...Relative to current technology, the TDR system offers the advantage of real-time monitoring, concurrent water-quality/-quantity monitoring, and improved precision by way of multiprobe sampling, all at a reduced cost.

As such, we believe this monitoring technique has significant market potential, both here and abroad, once fully developed.

Because of the dielectric variability along the probe (i.e., mixture of air, water, and/or sediment), we needed advanced analysis to interpret our measured data. For this reason we adopted frequency-based, multisection analysis pioneered in the electronics industry. We achieved refinement of the multisection model, thus providing a powerful framework for analyzing TDR traces. The model directly accounts for the effects of the coaxial cable, cable/probe connection, and the depth, dielectric, and conductivity of each phase present along the waveguide (as many phases as desired).

We also pursued efforts to automate TDR trace analysis. This involved combining the forward multisection model with an inverse model. The inverse model fits the multisection model to the trace data and subsequently extracts the optimized parameters (e.g., dielectric, depth, and conductivity of each phase present). PEST, a public domain software package for nonlinear parameter estimation, provides the engine for performing the inverse modeling. By combining PEST with the forward multisection model, we now have the capability for fully automated analysis of acquired TDR trace data.

(2) *Laboratory studies.* We performed static tank studies to quantitatively evaluate the precision and accuracy of the TDR monitoring system. Experiments involved sequentially varying the depth of water, depth of sediment, salinity, and coaxial cable length while measuring the resulting traces. In all, we performed over 650 unique and repeated measurements. Inverse modeling of the traces yielded the length of each phase along the waveguide as well as the conductivity for comparison with that independently measured in the tank (by way of graduated scale and conductivity meter). Results from a series of repeated tests suggest that the precision of the TDR in measuring the depth of water and sand is $\pm 3.6 \times 10^{-4}$ m, while conductivity is measured with a precision of 1.95×10^{-4} $\mu\text{S}/\text{cm}$. Accuracy of the TDR measurements is $\pm 3.4 \times 10^{-3}$ m for sensing the location of an air/water or water/sediment interface and $\pm 7.4\%$ of actual for the conductivity. Additionally, we found the measured precision and accuracy to be independent of the location of the interface along the length of the probe and independent of the length of coaxial cable (up to 55 m) connecting the probe to the cable tester.

(3) *Field studies.* We established a permanent monitoring site on the Rio Grande in Albuquerque at the Central Bridge. This site corresponds to one of the USGS permanent gauging stations. The installed instrumentation package consists of a TDR cable tester, multiplexer, data logger, cellular modem, and multiple probes. Power is supplied by a 75 W PV module fitted

We achieved refinement of the multisection model, thus providing a powerful framework for analyzing TDR traces. The model directly accounts for the effects of the coaxial cable, cable/probe connection, and the depth, dielectric, and conductivity of each phase present along the waveguide (as many phases as desired).

with a sealed battery (4-day storage), charge controller, and lightning arrestor. This sensor package is interfaced with a material monitoring system (MMS) for managing, storing, and analyzing the TDR data. Integrated into the MMS is the inverse modeling software (i.e., PEST) for real-time automated analysis of the TDR traces. Results from the MMS are available for display on the Web.

Refereed

Tidwell, V. C., and J. R. Brainard. 2003. Channel profile monitoring with time-domain reflectometry. Paper presented at the Sediment Monitoring Instrument and Analysis Research, 9–11 September, Flagstaff, Arizona.

Tidwell, V. C., and J. R. Brainard. 2003. Laboratory evaluation of time-domain reflectometry for continuous monitoring of stream stage, channel profile and aqueous conductivity. *Water Resources Research*, submitted.

Tidwell, V. C., J. R. Brainard, J. D. Roberts, and R. A. Jepsen. 2002. Monitoring sediment transport, stream stage, and salinity with time-domain reflectometry. Paper presented at the Fall Meeting of the American Geophysical Union, 6–10 December, San Francisco, California.

38667

Research and Development of Mathematical Algorithms to Define and Quantify Critical-Infrastructure Interdependencies

W. E. Beyeler, L. D. Olson, B. D. Murphy-Dye, D. E. Gallegos, M. A. Turnquist, C. R. Lawton, D. A. Jones

Reliable operation of infrastructures depends on the surety of other infrastructures. Those researching critical-infrastructure surety need to understand and quantify infrastructure interdependencies. Research efforts to date aimed at quantifying infrastructure interdependencies have centered on the identification of direct physical connections between particular components in one or more infrastructures. Although valid, this approach limits understanding to defined physical connections, requires valid datasets for each infrastructure, and requires constant maintenance and updating of both the database and the connections as infrastructures change. This is compounded by the private, competitive nature of the majority of the nation's infrastructures.

In this project, Sandia sought mathematical algorithms that can be used to define the relationships among infrastructures. First, we utilized domain expertise to identify obvious functional relationships within and among infrastructures. Second, we identified available data to apply against a series of functional forms to determine whether perceived relationships can be properly defined. Lastly, we defined the general framework of Dynamic Availability Analysis for modeling infrastructure interdependencies. We believe the modeling framework will substantially increase the accuracy and decrease the cost of infrastructure monitoring, assessment, and design. This work's scope includes the electric-power, natural-gas, oil, water, and communications infrastructures, but has focused on electric power and natural gas.

A literature review found a lack of high-level models or functional forms that we could use to define relationships either within or among infrastructures.

Examination and assembly of publicly available data sources led to the conclusion that data coverage is substantively less than ideal. Business entities that comprise many infrastructures are reluctant to volunteer detailed data about the systems they own without regulatory requirement. Even with regulatory requirements, requests for protection of data sources are common. Much of the data available from government sources, often resulting from regulatory reporting requirements,

Reliable operation of infrastructures depends on the surety of other infrastructures. ...In this project, Sandia sought mathematical algorithms that can be used to define the relationships among infrastructures...We believe the modeling framework will substantially increase the accuracy and decrease the cost of infrastructure monitoring, assessment, and design. This work's scope includes the electric-power, natural-gas, oil, water, and communications infrastructures, but has focused on electric power and natural gas.

is updated infrequently and may be provided at a level of aggregation to prevent the disclosure of information on individual firms. These constraints on basic data limit the strength of tests that can be performed on our models, compromise our ability to anticipate the system state, and motivate us to prefer models that explicitly consider uncertainty.

We then utilized domain expertise to identify obvious functional relationships within and among infrastructures. Relationships between the electric-power and natural-gas infrastructures focused on developing an understanding of potentially disruptive events in each infrastructure (well catalogued by industry and government alike) so as to determine which of these events provides an “actionable” window through which preventive action might be taken. Weather-related incidents in the electric-power infrastructure are understood, but little modeled. Demand-satisfaction incidents in both the electric-power and natural-gas infrastructures led to a conclusive mathematical form that incorporates both infrastructures, gauging unknown values with other known relationships (such as those between the current demand for natural gas by different customer classes and historic residential market price for the same).

Success in this development effort led to external research efforts that were centered on the development of a methodology used to define mathematical relationships that focused on the “health” of interdependent infrastructures.

We defined a general framework of Dynamic Availability Analysis for modeling infrastructure interdependencies. This included the examination of useful temporal measures of availability and application of uncertainty to both static and dynamic example networks. This effort highlighted the importance of gaining an understanding of uncertainty to develop a clear picture of the expected performance of interdependent systems.

We believe the modeling framework will substantially increase the accuracy and decrease the cost of infrastructure monitoring, assessment, and design.

Success in this development effort led to external research efforts that were centered on the development of a methodology used to define mathematical relationships that focused on the “health” of interdependent infrastructures. ...We believe the modeling framework will substantially increase the accuracy and decrease the cost of infrastructure monitoring, assessment, and design.

38668

Functionalized Nanoelectrode Arrays for *In Situ* Identification and Quantification of Regulated Chemicals in Water

W. G. Yelton, W. Einfeld, D. J. Muron, M. J. Kelly, K. B. Pfeifer, M. P. Siegal, J. Sergeant

Most chemical species currently regulated by the national water-quality standards and other compounds, such as endocrine disrupters, that are under consideration for regulation are redox-active species that can be identified and quantified by electrochemical techniques. Standard microelectrodes, and even commercial nanoband electrodes, require the addition of extra chemicals to condition the water before analysis and, therefore, are not useful for most real-time, *in situ* sampling. Trained personnel are required to analyze these microelectrodes, which cannot be used either for distributed remote analysis in a water system or in a dipstick mode for on-site testing of drinking water. An array of suitably functionalized nanoelectrodes could be incorporated into a small, integrated sensor system that can identify many species rapidly and simultaneously under field conditions without chemical addition and with signal-to-noise ratios (SNRs) up to 1000-fold greater than conventional electrodes.

Sandia seeks to investigate the use of functionalized nanoelectrodes as a sensor-array system for rapid, noncontaminating field analysis. The self-assembled template for these arrays will consist of conducting nanoelectrodes, whose diameter, length, and surface areal density can be systematically controlled. Chemical selectivity can be provided by chemical alteration of the metal nanoelectrode surfaces. Electrochemical deposition of a range of different metals to functionalize the nanoelectrodes will produce different current/voltage relationships from electrode elements in the array as the analytes of interest are subjected to electrochemical analysis. Enhanced selectivity and sensitivity for specific metals, such as heavy-metal industrial pollutants and radioactive nuclides, can be conferred by electrodeposition of thin organic conducting polymers containing functional groups, such as crown ethers, that selectively bind and preconcentrate the metals of interest for redox sampling.

We completed three generations of gold nanoelectrode arrays: low-density arrays (10^5 – 10^6 electrodes/ 0.2 cm^2), high-density arrays (10^9 – 10^{10} electrodes/ 0.2 cm^2), and arrays of both densities where the counter electrode is

Sandia seeks to investigate the use of functionalized nanoelectrodes as a sensor-array system for rapid, noncontaminating field analysis.

integrated with the working electrode. The three key characteristics of these arrays are the size, radius, and spacing of the electrodes. We validated the concept and demonstrated the expected advantages of nanoelectrode arrays using the first generation of low-density arrays in deionized (DI) water to detect 1 mM concentrations of $\text{Fe}^{2+}/\text{Fe}^{3+}$. Our low-density arrays outperformed commercial electrodes of the same geometric area in sensitivity and displayed greater reduction of open-circuit noise for low-conductivity solutions.

We completed the design, and a system is now under construction to allow rapid measurement of the transient currents required for optimum nanoelectrode performance. This high-speed potentiostat consists of three subsystems. The first is a rapid, three-level potential driver circuit that has two programmable potential levels and a third voltage determined by the open-circuit voltage across the nanoelectrode array. The three-level potential driver circuit can provide signals with pulsewidths from as short as 200 ns to as long as is desired for measuring a particular analyte. The second subsystem is a high-speed, transimpedance amplifier with a built-in integration circuit (IC) to convert a short-current pulse into a proportional static voltage. The last subsystem is a digital controller that provides triggering pulses and voltage-control programming to the potential driver, inputs data from the transimpedance amplifier, and communicates with a laptop for data extraction and control.

Electrochemical analysis protocols for chemically modified electrodes show good electrochemical activity for the ferricyanide/ferrocyanide redox couple commonly used as a test analyte for electrochemical analysis. We demonstrated them to be functioning working electrodes for electrochemical analysis of arsenic (As)(III) and As(V). Here, we used the poly(pyrogallol) modified electrodes in a three-step electrochemical protocol: (1) preconcentration of As(III) and As(V) within the pyrogallol polymer at open circuit from water samples at neutral pH, (2) electrocatalytically assisted reduction of As(III) and As(V) to As(0) in 1 M HCl, and (3) anodic stripping voltammetry in 1 M HCl for determination of As concentration. Combining the results of this poly(pyrogallol)-based analysis with published procedures for As(III) determinations provides the desired speciation of As(III) and As(V). We demonstrated our procedure for the direct determination of As(V) at poly(pyrogallol)-modified electrodes at parts-per-million concentrations, well above the target detection limits of 5 parts per billion. However, the dramatic improvements ($\sim 1000\times$) in sensitivity expected with the

Our low-density arrays outperformed commercial electrodes of the same geometric area in sensitivity and displayed greater reduction of open-circuit noise for low-conductivity solutions.

implementation of nanoelectrode arrays using the custom electronics described above could extend the usefulness of this chemically modified electrode approach to the desired detection limits.

Future work will include a focus on development of electroanalytical protocols for one or more other target analytes of interest. Here, we will select chemicals that are presently regulated under the Environmental Protection Agency (EPA) Safe Drinking Water Act, and/or EPA Contaminant Candidates, which contain chemicals that are not presently regulated but are suspected to pose public health hazards and which may be regulated in the future, pending results of ongoing research into possible adverse health effects. In fact, protocol development for these other target analytes (which include, among other species, antimony, cadmium, lead, copper, selenium, and nickel) will likely be considerably simpler than for As because published reports exist that describe procedures for electroanalysis without addition of reducing agents, oxidizing agents, chelating agents, or surfactants. In addition, we will explore the use of Nafion® films as protective coatings for functionalized nanoelectrode arrays to assist in protection from fouling of electrode surfaces in field applications. The potential extension of electrode lifetimes provided by these protective coatings should minimize the number of nanoelectrode assemblies that must be fielded as spare parts for the replaceable working electrode in the envisioned dipstick technology package.

38672

Validated Modeling of Distributed Energy Resources at Distribution Voltages

M. E. Ralph, J. W. Stevens, III, N. D. Wasson, J. D. Boyes, W. I. Bower, S. A. Knapp-Kleinsorge

Lack of validated models of distributed energy resources (DER) is a significant barrier to their deployment. To date, the impact of aggregated DER has been modeled primarily on transmission systems. However, sources that are presently being commercialized and those in the foreseeable future will operate at low voltage and connect via transformers to local distribution systems. This project will develop and experimentally validate models of transient and steady-state source behavior for incorporation into utility distribution-analysis tools. Development of these models has not been prioritized either by the distributed-generation industry or by the inverter industry.

The technical challenge is that although the electrical behavior of rotating machines such as diesel generators has been well characterized, no utility-compatible models are available for power-electronic inverters. Inverters are the utility interface for microturbines, fuel cells, photovoltaic (PV) inverters, variable-frequency wind generators, and virtually any system using electrical-energy storage.

Sandia developed a functioning model of a selected DER in collaboration with both the manufacturer and industrial power-systems analysts. The model is written in the PSCAD simulation language, a variant of the Electromagnetic Transients Program (EMTP), a code that is widely used and accepted by utilities. We will refine and experimentally validate the model. We will then incorporate it into utility distribution-analysis tools and use it to study a variety of DER issues.

We developed a computer model of a PV inverter using the PSCAD simulation language. The model incorporates pulsewidth-modulation details and provides a clear visual demonstration of inverter operation. We will use it as a valuable instructional tool for new staff, customers, and sponsors. We obtained details of the inverter controls from the manufacturer, Xantrex Technologies, and incorporated them into the model. These included regulation of voltage, current, and utility interconnection controls, including voltage trip settings.

We modeled the utility distribution system at Sandia's Distributed Energy Technologies Laboratory (DETL). We then connected the inverter model to the local grid model to simulate

This project will develop and experimentally validate models of transient and steady-state source behavior for incorporation into utility distribution-analysis tools. ...Sandia developed a functioning model of a selected DER in collaboration with both the manufacturer and industrial power-systems analysts.

generation of PV power into the grid. We simulated and performed steady-state power generation into the grid using the on-site PV array as prime power using actual DETL hardware. The results showed reasonable agreement. We made efforts to focus the modeling activity on issues of concern to utility distribution engineers. We documented utility distribution-system issues related to distributed generators in a white paper written under a related but separately funded project.

We consulted Salt River Project (SRP), a major utility with whom we recently had a Cooperative Research and Development Agreement (CRADA), regarding their perspective on distributed generation issues. SRP stated clearly that the issue of islanding was their highest priority with respect to distributed generation. Xantrex provided details of the anti-islanding controls, and we incorporated them into the model. We simulated and performed loss of grid using actual DETL hardware. Again, results showed good basic agreement. We identified needs for further refinements of the model.

38673

Water Desalination

T. E. Hinkebein, J. E. Krumhansl, L. Evans, J. E. Miller, J. A. Voigt, T. M. Nenoff

The in situ crystallization team is focused on desalination of inland ground, primarily brackish water with inexpensive, environmentally safe materials by a low-energy process. Sandia focused on waters with characteristic salt concentrations typical for New Mexico and the Tularosa Basin, in particular, with total dissolved solids (TDS) on the order of 2000–3000 ppm. Over 90% of the existing industrial methods for water desalination are based on distillation and reverse-osmosis (RO) technologies. We applied an entirely new approach based exclusively on chemical processes. We based our strategy on in situ crystallization, ion exchange, and precipitation of inorganic phases able to sequester the major ionic constituents of brackish water. The resultant ion-exchanged materials would contain the removed ions; these materials can then be either recycled, safely deposited in landfills without salt leaching, or used as a sellable building material (for example, incorporated into cement).

The water desalination and purification team focused their new perspective on the removal of salt from saline waters through the use of forward osmosis (FO) and a designer solute. By focusing on the use of FO to remove salt from the water, two important drawbacks associated with RO may be avoided—high-pressure costs and membrane fouling. The FO process is predicated on the identification of a designer solute. This material must provide a high osmotic potential and be compatible with the chosen membrane. The membrane for our process must meet three criteria. It must be nonreactive with the osmotic agent; it must be stable at the temperature of the osmotic agent; and the flux across the membrane must be maximized, preferably with near 100% selectivity.

We focused on three main types of materials:

- Anionic getters – materials that incorporate anions (Cl⁻, SO₄²⁻ and CO₃²⁻)
- Cationic getters – materials that incorporate cations (Na⁺, Mg²⁺ and Ca²⁺)
- Ionic getters – materials that incorporate both anions and cations.

We developed a method that provides significant anionic sequestration from brackish waters. This method is based on synthetic hydrotalcites (HTCs). We based the synthesis of these

Sandia focused on waters with characteristic salt concentrations typical for New Mexico and the Tularosa Basin, in particular, with total dissolved solids (TDS) on the order of 2000–3000 ppm.... We applied an entirely new approach based exclusively on chemical processes.... The water desalination and purification team focused their new perspective on the removal of salt from saline waters through the use of forward osmosis (FO) and a designer solute. By focusing on the use of FO to remove salt from the water, two important drawbacks associated with RO may be avoided—high-pressure costs and membrane fouling.

materials on inexpensive starting chemicals, which react and precipitate at room temperature for a short time. After calcination and immersion in saline water, the calcined material recovers its initial structure. In this process, each mole of regenerated HTC incorporates two anionic equivalents from the salt solution. We showed that calcined HTCs have an average anionic incorporation capacity of 0.95 mEq/g.

The best ability for cationic sequestration was with an amorphous silica and a crystalline zirconia phosphate (c-ZrP). We successfully synthesized permutite, which exhibits a high sodium-exchange ability; 15% aluminum (Al), the ion-exchange capacity, is 2.7 mEq/g. We also synthesized zirconia phosphate. The ion-exchange capacity of c-ZrP in strongly basic conditions (pH ~ 10.5) was 1.77 mEq/g and probably could be used for large-scale desalination. The synthesis of this material is based on relatively cheap reagents and requires simple processes under mild reaction conditions. When saturated, c-ZrP could be either regenerated or safely disposed of in the environment at a landfill.

We successfully ran column studies with an anion getter and the permutite on a simulant of Tularosa Basin water. The result was 25 ppm TDS in the water at pH = 5.7.

We defined and demonstrated a “best-case” thermal FO process and performed economic evaluations. Based on the results, we refined our approach, defined new design criteria, and began experimentation and demonstration of the refined approach. We obtained results for a thermally based FO approach to desalination with a combination of a hydrophobic porous membrane and a common food additive. The fluxes are reasonable, and the vapor transport mechanism gives essentially 100% salt discrimination. We obtained fluxes as high as 14 l/m²/hr with an FO membrane, but it was degraded by the pH (9) agent. The economic analysis indicated that large savings over seawater RO are not achieved with the initial thermal approach and identified target areas for improvement in the refined design. Also, membranes must be optimized so that higher fluxes are achieved, and so that pretreatment is not required.

We refined our approach in response to economic drivers. To bypass the need for subambient cooling and heat recovery, we began to evaluate osmotic agents whose solubility responds to changes in pH. We evaluated agents that can be precipitated by low to moderate pressures of CO₂. Compounds that are ideal for our application will have a high maximum solubility at neutral to slightly basic pH (S_{Max}, pH_{Max}), a low intrinsic solubility (S_N), and pK_a in the range of 5–7. Compounds that

fit this profile include phenols and aromatic acids. Operation in the acidic regime will also simplify membrane optimization.

Beginning from concentrations of 10 wt.% salts, we reduced concentrations over orders of magnitude through pH manipulation. We are developing a complete set of equations to model pH adjustment and precipitation through CO₂ addition. The positive results achieved suggest that a low-cost (energy and capital investment), single-stage process that is not susceptible to parasitic thermal losses is a possibility.

The positive results achieved suggest that a low-cost (energy and capital investment), single-stage process that is not susceptible to parasitic thermal losses is a possibility.

Refereed

Bontchev, R. P., S. Liu, J. A. Voigt, J. K. Krumhansl, and T. M. Nenoff. 2003. Synthesis, characterization and ion-exchange properties of hydrotalcite $\text{Mg}_6\text{Al}_2(\text{OH})_{16}(\text{A})_x(\text{A}')_{2-x} \cdot 4\text{H}_2\text{O}$ (A, A' = Cl⁻, Br⁻, I⁻ and NO₃⁻, $2 \geq x \geq 0$) Derivatives. *Chem. Mater.* **15**:3669.

Other Communications

Bontchev, R. P., J. K. Krumhansl, J. A. Voigt, and T. M. Nenoff. 2003. Desalination of Brackish Waters Using *In Situ* Crystallization and Ion Exchange of Inorganic Phases. Sandia Technical Report SAND2003-2953, Sandia National Laboratories, Albuquerque, New Mexico.

Miller, J. E. 2003. Review of Water Resources and Desalination Technologies. Sandia Technical Report SAND2003-0800, Sandia National Laboratories, Albuquerque, New Mexico.

38674

Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps

J. Cesarano, III, P. O. Witze, J. N. Stuecker, J. E. Miller, P. R. Schunk, R. M. Ferrizz, T. J. Gardner

Diesel-particulate emission, or soot, is a global problem, but current technologies for meeting looming regulations are costly and prone to failure. NO_x formation from methane combustion in electric-power plants is also an environmental concern, but materials and catalyst reliability issues have prevented the application of catalytic combustors that circumvent NO_x formation. Sandia seeks to utilize a commercially viable, scalable, direct ceramic fabrication technique as the basis for creating revolutionary systems for diesel-particulate trapping and destruction and for catalytic methane combustion. Traditional fabrication techniques are limited to producing “honeycomb”-structured extrudates and foams. Our technique is not only more flexible in terms of the shape of the ceramic product, but also allows a broader range of materials and catalysts to be used.

Our design is a three-dimensional (3-D) cross-hatched mesh, formed from alternating layers of precisely spaced rods (similar in design to Lincoln logs). Direct fabrication inherently ensures that the rods meld together and form a strong bond upon sintering. The sintered meshes will have controlled porosity in three dimensions, but no line-of-sight pathways. This macrostructure ensures adequate tortuosity and a high surface-to-volume ratio, while maintaining predictable permeability and low-pressure drop.

Diesel-particulate emission, or soot, is a global problem, but current technologies for meeting looming regulations are costly and prone to failure. ...Sandia seeks to utilize a commercially viable, scalable, direct ceramic fabrication technique as the basis for creating revolutionary systems for diesel-particulate trapping and destruction and for catalytic methane combustion.

Robocast lattices eliminate mass transfer limitations; even at a gas flowrate of 13,000 sccm, the reaction can still go to completion. Traditional honeycomb supports cannot achieve this.

The incorporation of, or fabrication from, a catalytically active material will allow efficient combustion of methane without NO_x formation. Similarly, the structures will trap soot particles that will then be catalytically combusted, thereby indefinitely extending the life of the trap.

Research challenges include the following: efficient particle trapping with low pressure drop, catalyst design for severe combustion environments, mechanical and chemical stability, flow and filtration simulation for optimizing designs, and real-time performance characterization. Our expertise in ceramic processing, catalysis, engine diagnostics, and modeling uniquely positions us to overcome these challenges to create “real-world” systems with broad impact in clean-energy utilization.

We completed two refereed publications, several presentations, a technical advance, and a patent application. Our project was acknowledged by *Chemical & Engineering News* as one of the top materials developments in 2002 and received Sandia’s “Gold Team Performance Award” for development of lattices suitable for bone implants. The accomplishments are separated into three related topics below.

(1) *Precombustion*. Preliminary data suggested that robocast lattice geometry improves catalyst performance by a factor of 4. We completed very controlled experiments to verify our observations and understand the mechanism for enhancement. We characterized effects of volume, surface area, mass of active catalyst, gas flowrate, and residence time. Robocast lattices washcoated with hexaaluminate catalyst induce conversion of methane at lower temperatures and more completely than similarly washcoated honeycombs. Lattices made completely with hexaaluminate exhibit even more dramatic behavior, decreasing the temperature for complete conversion by more than 150°C. We found similar results for combustion of propane with platinum. We used a model system (the catalytic oxidation of carbon monoxide) to prove lattices improve mass transfer. We anticipated, and our computer simulations verified, that this is due to increased turbulence in the flow.

(2) *Diesel-particulate traps*. We characterized the performance of a commercial diesel-particulate trap on a Volkswagen engine to obtain a performance benchmark. We selected two materials for our traps, alumina and silicon carbide. We successfully made structures as large as 90 mm.

(3) *Spin-offs related to lattices*. We submitted a joint proposal with Engelhard. Caterpillar, Corning, and Delphi are

Our expertise in ceramic processing, catalysis, engine diagnostics, and modeling uniquely positions us to overcome these challenges to create “real-world” systems with broad impact in clean-energy utilization....Our project was acknowledged by Chemical & Engineering News as one of the top materials developments in 2002....

interested in our catalyst supports and possibilities of reforming hydrogen for fuel cells. Praxair is considering our lattices as a radiation shield with a low-pressure drop. A collaboration with the University of Illinois proved that our lattices may be suitable for biomedical bone scaffolding.

Refereed

Ferrizz, R. M., J. E. Miller, J. Cesarano, III, J. N. Stuecker, and L. R. Evans. 2003. Novel monolithic supports for catalytic combustion. *Proc. 18th North American Catalysis Society Meeting* (June, Cancun, Mexico).

Stuecker, J. N., J. Cesarano, III, J. E. Miller, R. M. Ferrizz, and J. E. Mudd. 2003. Novel three-dimensional ceramic lattices as catalyst supports and diesel-particulate traps. *Diesel Emissions Measurement and Modeling, Proc. Society of Automotive Engineers 2003 World Congress* (March, Detroit, Michigan).

Stuecker, J. N., J. E. Miller, R. E. Ferrizz, J. E. Mudd, and J. Cesarano, III. 2003. Advanced support structures for enhanced catalytic activity. *Industrial and Engineering Chemistry Research*, accepted.

Other Communications

Cesarano, J., III. 2003. Robocasting: Moldless fabrication of ceramics and composites. (Invited) Paper presented at Alfred University for the Department of Ceramic Engineering and Materials Science, April, Alfred, New York.

Cesarano, J., III, J. N. Stuecker, J. E. Miller, and R. M. Ferrizz. 2003. Three-dimensional ceramic lattices as catalyst supports. Paper presented at the Annual Meeting of the American Ceramic Society, April, Nashville, Tennessee.

Miller, J. E., R. M. Ferrizz, J. Cesarano, III, and J. N. Stuecker. 2003. Catalyst development at Sandia National Laboratories for automobile applications. Paper presented at the Materials Science Seminar at Colorado School of Mines, February, Golden, Colorado.

38677

Potential Application of Microsensor Technology in Radioactive-Waste Management—With Emphasis on Headspace Gas Detection

Y. Wang, M. L. Thomas, R. C. Hughes, P. I. Pohl, C. K. Ho, C. R. Bryan, H. Gao

Measurements of headspace gas in waste containers or in waste-disposal facilities are generally required for the demonstration of compliance with the Resource Conservation and Recovery Act (RCRA) or transportation requirements as well as for general safety. The existing methods for such measurements are time-consuming and expensive, and also increase a worker's exposure to hazardous environments. Therefore, a reliable, real-time, and in situ gas-detection technique is highly desirable. Sandia expects that molecular hydrogen (H_2) and volatile organic compound (VOC) microsensors developed at Sandia will have a wide range of applications in radioactive-waste management with appropriate further development and adaptation.

We proposed the following work: (1) test the long-term stability of both H_2 and VOC microsensors and make necessary improvements, (2) optimize the ability of VOC microsensors for the discrimination of individual VOCs that are present in transuranic wastes, and (3) study the feasibility of using microsensors as a screening tool to discriminate two populations of waste drums according to a prespecified total VOC concentration limit. One outcome of this work is a set of microsensors specifically adapted to waste characterization and monitoring that can be transferred to a private company for large-scale manufacturing. The work also will generate sufficient technical data that currently are not available but are needed for the use of these sensors in the area of nuclear-waste management. Success in the work may lead to a large scale of deployment of these sensors across the Department of Energy's waste-generator sites and waste-storage/-disposal facilities. The work will greatly enhance our expertise in nuclear-waste management by leveraging Sandia's strength in microsensor development. Finally, it will strongly impact the investment area of monitoring systems.

We tested the H_2 SCANTM H sensor with additional VOCs, specifically chloroform, carbon tetrachloride, and toluene. The data obtained further support our previous observation that the presence of VOCs can impact H sensor readings. To minimize

Sandia expects that molecular hydrogen (H_2) and volatile organic compound (VOC) microsensors developed at Sandia will have a wide range of applications in radioactive-waste management with appropriate further development and adaptation. ...The work will greatly enhance our expertise in nuclear-waste management by leveraging Sandia's strength in microsensor development. Finally, it will strongly impact the investment area of monitoring systems.

this effect, we coated the sensor surface with sol-gel and observed some improvement in sensor response. We also evaluated the impact of aging and VOC exposure on H sensor response time. The impact seems minimal.

We made significant progress in testing and improving VOC sensors. We developed a technique for depositing uniform-sensing polymer films, which can significantly improve both the sensitivity and the stability of the sensor. We also determined the optimal carbon black loading ratio. Based on solubility parameters, we selected 10 candidate polymers and tested their responses to the VOCs of interest. The test results show that poly(ethylene-vinyl acetate) (PEVA), polystyrene, poly(isobutylene) (PIB), and poly(vinyl acetate) (PVAc) are the most sensitive among the selected materials. More tests are planned. All of these tests will help us to select a minimal set of polymers for differentiating individual VOCs.

We also made progress in preconcentrator development. The best preconcentration potential was exhibited by the combination of m-xylene on a Carboxen 1000 preconcentrator. Future work will focus on investigating the suitability of using carbon nanotube materials as the absorbent phase in a preconcentrator device.

We made significant progress in testing and improving VOC sensors. We developed a technique for depositing uniform-sensing polymer films, which can significantly improve both the sensitivity and the stability of the sensor. We also determined the optimal carbon black loading ratio.

38678

Surety Enhancement for Wireless Automated-Control Networks

W. F. Young, D. P. Duggan, J. M. Depoy, M. D. Torgerson, E. L. Witzke, J. D. Dillinger, J. E. Stamp, J. A. Hutchins

This project originally focused on developing secure network architectures for process-control systems (PCSs) utilized by offshore oil-drilling platforms. However, the terrorist attacks of September 11th quickly moved security of critical infrastructure (CI) elements such as the water and electric-power utilities to the forefront. Cyber assessments of these CI elements pointed to the urgency in correcting security problems in current PCSs that include a combination of wired and wireless segments, as well as pending PCS implementations. To meet these immediate security challenges, Sandia modified the direction of this project to focus primarily on these types of control systems. The modification required was not extreme, and the changes mainly centered on the particular type of PCS instantiations used for case studies in the research.

Sandia's first year of work consists primarily of vulnerability analysis, identification of key characteristics of relevant PCS architectures, operating network (OPNET) model development, and vulnerability validation in the OPNET environment. The goal is to study the vulnerabilities created by the use of wireless communications in the modern PCS environment. This will allow the development of architectural mitigation strategies, which will be validated in the OPNET modeling environment in upcoming work. The end result will be architectural security improvements, dictated by an information assurance (IA) perspective, for modern process-control systems. These IA-based solutions are vital to the nation's CI.

The accomplishments of the research fall into two main categories: (1) the development of an analysis approach to hybrid wired/wireless systems, and (2) the development of a surety design approach to Supervisory Control and Data Acquisition (SCADA) systems.

The first important accomplishment is described in our report titled "Views of Wireless Network Systems." We detail information contained on the many different views of a wireless network system. The method of using multiple views of a system to assist in the determination of vulnerabilities comes from the Information Design Assurance Red Team Methodology (IDARTTM) of system analysis. The goal of the methodology is to identify architectural vulnerabilities of a

This project originally focused on developing secure network architectures for process-control systems (PCSs) utilized by offshore oil-drilling platforms. However, the terrorist attacks of September 11th quickly moved security of critical infrastructure (CI) elements such as the water and electric-power utilities to the forefront. Cyber assessments of these CI elements pointed to the urgency in correcting security problems in current PCSs that include a combination of wired and wireless segments, as well as pending PCS implementations. To meet these immediate security challenges, Sandia modified the direction of this project to focus primarily on these types of control systems.

system to some specific level of adversary. We use the views to help determine vulnerabilities that might exist within various architectural pieces of the system.

Our second primary accomplishment is seen in the document “Communication Vulnerabilities and Mitigations in Wind Power SCADA Systems,” presented and published in the *WindPower 2003 Conference Proceedings*. This paper focused on securing wind-power SCADA systems that utilize commercial-off-the-shelf information technology (IT). The use of IT within SCADA systems provides the benefits of low implementation cost and ease of interoperability, but introduces the potential for new security vulnerabilities. To address these new vulnerabilities in wind-power SCADA systems, we applied lessons learned from our SCADA assessment activities, design and implementation experience in secure communication systems, and knowledge of wind-power operations. We present a SCADA security policy framework and provide two IT “best practices” examples. We also list several typical SCADA/IT vulnerabilities.

Refereed

Young, W. F., M. A. Rumsey, J. E. Stamp, and J. D. Dillinger. 2003. Communication vulnerabilities and mitigations in wind-power supervisory control and data-acquisition systems. *Proc. Windpower 2003 Conference* **1** (18–21 May, Austin, Texas): 103–7.

Other Communications

Duggan, D. P., and W. F. Young. 2003. Views of Wireless Network Systems. Sandia Technical Report SAND2003-3623, Sandia National Laboratories, Albuquerque, New Mexico.

38679

Advanced Nuclear Engineering Analysis Technology

M. F. Young, V. J. Romero, K. K. Murata

This project was designed to apply computing technology developed for the analysis of weapons systems to state-of-the-art accident analysis of a nuclear reactor system. The Sandia SIERRA parallel computing platform for Accelerated Strategic Computing Initiative (ASCI) codes includes high-fidelity thermal, fluids, and structural codes whose coupling through SIERRA can be specifically tailored to analyze complex multiphysics problems. Presently, however, the suite lacks several physics modules unique to the analysis of nuclear reactors. The Nuclear Regulatory Commission MELCOR code, not presently part of SIERRA, was developed to analyze severe accidents in present-technology reactor systems. Completion of this research would demonstrate the feasibility of performing high-fidelity rapid analyses of safety and design issues needed to support the development of next-generation power reactor systems. Previously, we evaluated the SIERRA code suite for its current applicability to the analysis of next-generation nuclear reactors and the feasibility of coupling MELCOR models with the SIERRA suite. We selected a simplified spent-reactor-fuel pool problem as a demonstration problem for future study. We selected two computational fluid dynamics (CFD) codes, GILA and MPSalsa, to experiment with coupling to MELCOR for this problem. We ran two MELCOR processes in coupled mode on the demonstration problem. We developed message-passing interface (MPI) coupling routines for MELCOR and GILA. We made substantial progress in coupling these two codes and demonstrating the feasibility of the coupling concept.

We chose the spent-reactor-fuel pool as the demonstration problem in this project. In this problem, we would assume that the fuel pool had been drained of water and allowed to heat up from decay heat in the fuel. The problem would use MELCOR for the fuel-pin behavior, including temperature and clad oxidation rates. A CFD code would provide convective gas flow using the fuel-pin temperatures and clad oxidation rates as boundary conditions (BCs). We proceeded with evaluation of the various proposed code architectural constructions defined early in the project.

We reached the conclusion that coupling MELCOR to the SIERRA framework codes was not feasible at this time. The most important reason for this conclusion is the SIERRA

This project was designed to apply computing technology developed for the analysis of weapons systems to state-of-the-art accident analysis of a nuclear reactor system. ...Completion of this research would demonstrate the feasibility of performing high-fidelity rapid analyses of safety and design issues needed to support the development of next-generation power reactor systems.

framework itself. This framework is intended to separate the functions of computer implementation of a code and the physics side of code design by providing common functions for solution, mesh generation, output, etc., and to allow coupling of codes inside the framework. Unfortunately, the framework is of use only to finite-element (FE) codes, provides no “hooks” to allow easy coupling to codes outside the framework, and has a huge learning barrier to incorporating a new code into the framework. It also became apparent as we reviewed ASCI code capabilities that many of the codes are in the beta stage of development. This early development stage has several consequences, including lack of documentation (particularly for FUEGO, which is the best candidate for coupling to MELCOR for the demonstration problem), missing critical physics models, and no developer time for collaboration available for activities outside of ASCI development.

For the above reasons, we investigated the pre-ASCI versions of the codes and other CFD codes available at Sandia. These codes tend to be more established, with more models in place. Also, since the older codes are not in development, the codebases are more stable. Codes investigated for possible use in the demonstration problem included MPSalsa, Vulcan, the FAA code, and GILA, which are all three-dimensional (3-D) CFD codes. MPSalsa is an equilibrium/transient FE code; Vulcan is a transient block-structured code; the FAA code, developed to analyze smoke transport in airplanes, uses a body-fitted mesh; and GILA is a transient FE code.

Important criteria in selecting a code include easy mesh generation, stability, documentation, implementation of physics models needed (in this case, convection, turbulence, and chemical-reaction physics), an active development/user group, and the ability to run on a parallel machine. We selected MPSalsa as the main candidate and GILA as a backup.

The current investigation focuses on evaluating the CFD codes on simplified problems and on development of coupling algorithms and methods for coupling to MELCOR. We defined simplified meshes and test problems for a fuel bundle in the spent-fuel pool to gain familiarity with the CFD codes on this type of problem. The current approach to coupling CFD to MELCOR is oriented around user functions in both codes, with MPI as the “glue” to communicate between the codes. This approach provides the primary coupling mechanism, and each code sees the other as providing BCs. The problem of coupling between two codes having different spatial fidelities also must be addressed; this involves defining appropriate coarse-to-fine-grid and fine-to-coarse-grid operators for the coupling

functions. The operators currently are being researched. One uncertain aspect of the coupling is possible time instability if the coupling is not fully implicit.

We demonstrated coupling with the simplified problem using two MELCOR processes. We modified the parallel virtual machine (PVM) routines in MELCOR to include MPI calls. We made substantial progress in coupling MELCOR with GILA, including exporting/importing variables from MELCOR and from GILA through an executive program. Due to the cancellation of the third year of this project, no further work on the demonstration problem will be done.

We made substantial progress in coupling MELCOR with GILA, including exporting/importing variables from MELCOR and from GILA through an executive program.

49770

Frameworks for Nuclear Process Transparency and Control

Y. McClellan, G. E. Rochau, P. E. Rexroth, D. L. York

A key objective of transparency is providing the environment for exchanging scientific and nuclear technology without the fear of diversion or proliferation. Many nations are considering closed- or multiple-application nuclear fuel cycles and developing advanced reactor and fuel-cycle designs. Proliferation-resistance features that prevent the theft or diversion of nuclear material and reduce the likelihood of diversion from the civilian nuclear-power fuel cycle are critical for global nuclear futures. Such resistance is a framework or quantitative measure of a nuclear process's ability to keep the associated materials secure and ensure the legitimate use. Any integrated approach to proliferation resistance requires the incorporation and integration of monitoring, process-automation, surveillance, and information-system technologies. This provides a transparent vigilance and assurance of the security of nuclear materials and facilities and encourages the development of holistic fuel cycles. Sandia had three objectives in this project: to (1) develop a transparency toolbox, (2) develop a transparency framework, and (3) demonstrate the framework.

A key element in the deployment of global nuclear technology is the ability to collect and analyze information in a timely fashion to ensure the safe and secure use of such technology and to prevent the theft of nuclear material. Many nations are considering nuclear fuel cycles, reprocessing, and developing advanced reactor and fuel-cycle designs for future energy needs. The key to achieving success, enhancing proliferation resistance, and maintaining this resistance through transparency is the early integration of proliferation-resistance requirements into nuclear and fuel-cycle research, design, and development (RD&D), taking advantage of technology that benefits operation and monitoring. Technologies to support transparency measures and nuclear-materials safeguards continue to evolve. Sensor platforms have become more modular in nature; they provide more functions and improve data-security capabilities. These advances will only improve over the next 10 years and can be used by transparency to improve the current situation. Expanding the use of process automation provides an opportunity to build in transparency monitors that ensure process operation as expected by the

manufacturer, the nation, and the world. We developed the transparency-toolbox database to identify technologies that can benefit the tracking of material during the nuclear-fuel-handling cycle. As part of developing this database, we designed software that provides a user-friendly interface.

To develop the transparency framework, we employed a systems-based probability risk assessment. We used deductive reasoning to construct an influence diagram that encompasses all of the major activities during the nuclear-fuel-handling cycle. The influence diagram is solved to obtain the complete sets of system failures. One of the system failures represents the possible ways to accomplish the diversion of nuclear material. We demonstrated this framework on a reactor. We developed a software program to demonstrate how effectively and efficiently monitoring systems can track nuclear material on-site and remotely.

We developed the transparency-toolbox database to identify technologies that can benefit the tracking of material during the nuclear-fuel-handling cycle. As part of developing this database, we designed software that provides a user-friendly interface.

52591

Beyond Nanoparticles—Attack on a Chemical “Holy Grail”

R. A. Kemp, J. E. Miller, J. T. Moore

One of the “Holy Grails” set by the Department of Energy in energy-related catalysis chemistry is the direct and selective partial oxidation of hydrocarbons using molecular oxygen rather than expensive alternatives such as peroxides or nitrous oxide (N_2O). A key commodity chemical produced in ~ 12 billion pounds/year capacity is propylene oxide (PO). PO is now currently produced by multistep processes that use environmentally unfriendly reagents or produce co-products. We propose to expand Sandia’s technical base and expertise by attacking this problem by use of homogeneous catalysis. Molecular-level control of catalysts is the ultimate in catalyst design—despite years of effort in industry and academics, no heterogeneous catalyst system has yet directly produced PO in high-enough conversion and selectivity to be commercially implemented. One key feature of this project is the design of a catalytic cycle in which each step of the cycle has literature precedent using middle- to late-transition metals. However, combining these assorted reactions into a rational catalytic cycle will require the correct combination of metals and ligands. If we are successful, the potential impact on Sandia’s scientific reputation could be enormous—there are many examples of commercially produced, partially oxidized organic products. However, the most significant impact if we are successful would be in energy savings due to the improved efficiencies of partial oxidation processes, as well as the learning that might be applied to other partial oxidation routes. Sandia’s expertise and experience in catalysis will be enhanced if we are successful.

(1) Our initial synthetic effort is in preparing multidentate pincer ligands. This class of ligand has a greater degree of oxygen stability than most organic ligands, hence, the choice for initial screening studies. We prepared several ligands with small and large R groups attached to phosphorus to allow different steric effects to be probed. We added different R’ groups to the aromatic rings to aid in solubility and ligand purification. We now have in hand approximately eight different pincer ligands to use.

(2) We prepared platinum (Pt) complexes of these pincer ligands and are in the process of characterizing these organometallic species.

We propose to expand Sandia’s technical base and expertise by attacking this problem by use of homogeneous catalysis....there are many examples of commercially produced, partially oxidized organic products. However, the most significant impact if we are successful would be in energy savings due to the improved efficiencies of partial oxidation processes, as well as the learning that might be applied to other partial oxidation routes.

(3) We are preparing “free phosphine” nonchelating versions of the pincer ligands to compare with the Pt species in (2).

(4) We prepared numerous complexes of middle-transition metals with the SALEN ligand system to investigate earlier transition metals. We identified a Co-H species that appears to react with elemental O₂, hopefully to give an inserted hydroperoxide (although not confirmed yet).

(5) Through collaboration with the University of Washington, a student is currently working on the synthetic collaboration on rhodium (Rh) and iridium (Ir) chemistry of the pincer ligands.

(6) We are exploring options with a local professor of synthetic organic chemistry to aid us in the synthesis of modified pincer ligands. Sandia approved this collaboration, and we are awaiting final approvals to begin it. This collaboration will allow a much larger number of ligands to be prepared, thus allowing us to make progress more quickly.

52592

Advanced Proton-Exchange Materials for Energy-Efficient Fuel Cells

C. J. Cornelius, D. Ingersoll, G. S. Grest

Fuel cells are a critical component of a hydrogen (H)-based economy, and they provide an alternative power technology that will secure our nation's energy needs by reducing our dependence on foreign oil. Sandia's focus in this project is the development of novel proton-exchange membrane (PEM) materials that are superior to Nafion®, the state-of-the-art PEM material. Fuel cells based on Nafion® are thermally limited to temperatures near 80°C because of its mechanical properties and lowered proton conductivity resulting from decreased PEM hydration with increasing temperature. Lower operating temperatures prevent utilization of other potential catalysts and limit the power output of the fuel cell. To overcome these technical challenges, we will develop high-temperature solid-state proton-conducting polymers (no water required for proton conduction), robust hydrated proton-conducting polymers, and hybrid inorganic-organic PEM materials in this project. These new PEM material properties will result in higher-power-output densities, improved catalyst efficiency, and reduced fuel-cell cost because of lower catalyst loading. These PEM material improvements will make a significant impact in realizing an H-based economy. Furthermore, these novel PEM materials will also be a significant technical advancement for methanol and ethanol fuel cells. During an earlier project, first-generation PEM materials for methanol fuel cells possessed conductivities approaching Nafion® by utilizing a molecular-engineering design approach.

Our accomplishments include the capability to evaluate the proton conductivity of PEM materials, the ability to test PEM materials in a working fuel cell, successful preliminary modeling of block PEM copolymers, and the creation of first-generation PEM materials. To gain fundamental insights regarding the structure-property relationships of these PEM materials, we established a collaboration with a polymer physicist at Clemson University to do small-angle neutron scattering (SANS) and small-angle x-ray scattering (SAXS) studies of the polymer microstructure. Other successes in this project include the testing of non-Nafion® polymers in a working H and methanol fuel cell. We completed preliminary elevated-temperature work with non-Nafion® PEM materials at

Sandia's focus in this project is the development of novel proton-exchange membrane (PEM) materials that are superior to Nafion®, the state-of-the-art PEM material. ...These new PEM material properties will result in higher-power-output densities, improved catalyst efficiency, and reduced fuel-cell cost because of lower catalyst loading. These PEM material improvements will make a significant impact in realizing an H-based economy. Furthermore, these novel PEM materials will also be a significant technical advancement for methanol and ethanol fuel cells.

130°C. Initial work also led to the development of techniques to “paint” on cathode and anode electrodes to non-Nafion® PEM materials, which is a critical requirement for achieving high-power outputs. Ongoing efforts include testing high-temperature PEM materials at elevated temperatures and characterizing PEM material properties.

Initial work also led to the development of techniques to “paint” on cathode and anode electrodes to non-Nafion® PEM materials, which is a critical requirement for achieving high-power outputs.

52593

Alanate-Hydride Fuel-Cell Demonstration Project

K. J. Gross, R. S. Larson, S. Spangler, M. P. Kanouff, K. D. Stewart, J. P. Chan

An entirely new class of lightweight reversible hydrides has been discovered (the alanates). These titanium (Ti)-doped sodium aluminum hydride (NaAlH₄) materials have reversible hydrogen (H)-storage capacities of up to 5 wt.%, making them nearly four times lighter than commercial metal hydrides. For this reason, they have been considered a breakthrough for the onboard H storage for fuel-cell vehicles. This project will be the first demonstration of the utilization of the alanates for an H-storage application. Challenges addressed include packaging of the alanate, modeling and measuring kinetic and thermodynamic rates for rapid fill and H delivery, and ultimately, the demonstration of a small fuel-cell system utilizing the alanate storage.

The kinetics of H absorption by the alanate improves with elevated temperatures. Sandia's initial work focused on balancing the thermodynamics of these hydrides with start-up conditions. We will employ modeling of the hydride kinetics and thermodynamics to develop the optimal H-storage system. We will place a major focus on novel engineering designs based on additional modeling of thermal transport and system thermal management. The results of modeling and experimental measurements will lead to a demonstration system using an off-the-shelf fuel cell with the optimized hydride storage.

We tested hydride systems that provide H-storage capacities of 2.8–3.5 wt.%. This compares favorably with classic hydride capacities of 1.5–1.9 wt.%. However, there is still much room for improvement. We are developing nonreactive Ti dopants and modified direct-synthesis materials with the potential to increase the alanate's reversible capacity toward the theoretical 5.6 wt.% capacity.

In preparation for the production of larger quantities of materials, we nearly completed the installation of a dedicated airless synthesis station. We coordinated efforts with a Department of Energy (DOE)–funded engineering materials science project to share results and materials. Under that project, 120 grams of Ti-doped alanate was carefully prepared to measure thermal properties of the alanates. In addition to providing material-properties data that are very useful for this project, we will use the alanate material in our demonstration

An entirely new class of lightweight reversible hydrides has been discovered (the alanates). These titanium (Ti)-doped sodium aluminum hydride (NaAlH₄) materials have reversible hydrogen (H)-storage capacities of up to 5 wt.%, making them nearly four times lighter than commercial metal hydrides. For this reason, they have been considered a breakthrough for the onboard H storage for fuel-cell vehicles. This project will be the first demonstration of the utilization of the alanates for an H-storage application.

test-beds when the thermal-property measurements have been completed. We completed the design of the test-beds, including an engineering safety analysis, and will soon receive the first series from a local manufacturer.

We tested a commercial fuel cell under various operating conditions, including running the fuel cell on a pair of Sandia-developed 200 standard liter H_2 hydride beds. We constructed a complete fuel-cell variable-load-and-instrumented test station. We began taking measurements of key operating parameters, fuel-cell temperature distribution, and thermal management. From these data, we determined the temperature and heating energy that can be delivered to the hydride beds. In parallel, we developed a model of the thermodynamic and heat-transfer properties of the hydride bed.

52594

Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process

R. W. Bradshaw, R. S. Larson, A. E. Lutz

The iodine-sulfur (I-S) cycle for the thermochemical splitting of water to produce hydrogen (H) is recognized as the most efficient such process and is particularly well suited to coupling to a high-temperature nuclear-power reactor for process heat. Despite the long development history of this process, an important, but unresolved, design issue is the separation of I from the multicomponent process fluid prior to the primary H-production step. This aspect of completing a full-scale design requires detailed knowledge of the vapor-liquid equilibrium (VLE) diagram that describes the phase-separation behavior of I, water, and hydriodic acid at process conditions. This multidimensional phase diagram is necessary to design a pressurized distillation component and is not currently available.

Sandia attempted to significantly expand the phase-equilibrium database that will facilitate implementing the I-S water-splitting process on a commercial scale. We designed the study to combine experimental measurements of VLE and equation-of-state (EOS) modeling of equilibrium solutions using Sandia's CHEMKIN (chemical kinetics) software. We will conduct VLE experiments for the system I-hydriodic acid-water at elevated temperature and pressure relevant to the I-S process. The Liquid CHEMKIN software that we developed as part of a previous project will be enhanced and applied to model the nonideal behavior of the liquid phases. The formulation of a real-gas EOS will extend the applicability of the laboratory data to a wide range of process-design calculations concerning the I-separation step in the overall process.

The goal of the laboratory phase of this study was to design, fabricate, and operate a pressure vessel to acquire preliminary VLE data. The measurements would include the phase compositions (two liquid phases and the vapor phase) and the vapor pressure for a range of temperatures and initial compositions of the constituents. The experimental work was significantly and negatively affected by greater-than-anticipated difficulties in constructing a suitable equilibrium cell capable of containing the highly corrosive mixture of I, hydriodic acid, and water at temperatures of nominally 200°C. Delays in procuring a pressure cell suitable for handling this mixture forestalled this

Sandia attempted to significantly expand the phase-equilibrium database that will facilitate implementing the I-S water-splitting process on a commercial scale. We designed the study to combine experimental measurements of VLE and equation-of-state (EOS) modeling of equilibrium solutions using Sandia's CHEMKIN (chemical kinetics) software....The Liquid CHEMKIN software that we developed as part of a previous project will be enhanced and applied to model the nonideal behavior of the liquid phases.

approach. Based on the initial attempt to design a cell for high-pressure studies, we developed several alternative designs that may be able to accommodate the stringent requirements necessary to attain thermodynamic equilibrium in this multicomponent system while accessing the cell to sample all phases. As a backup, we assembled a secondary cell from glass and polytetrafluoroethylene (PTFE) components and ran several tests at lower temperature and pressure than originally proposed. We operated this cell at nominally 120°C, above the liquidus temperature of I, and 40 psi. We collected samples from the water-rich liquid phase and analyzed them for I content.

The goal of the computational modeling part of this project was to develop the capability to construct phase diagrams that describe the behavior of the HI-iodine-water system by making enhancements to Sandia's CHEMKIN package of codes. We adopted a four-step approach to obtain a set of codes that can do the necessary computations. First, we adapted the EQUIL code and its STANJAN-based subroutines to make use of the physical properties provided by the Liquid CHEMKIN subroutine library. Second, we used the newly modified EQUIL code to construct some representative phase diagrams based on the nonideal liquid models of other multicomponent systems currently existing in Liquid CHEMKIN. This demonstrated that the CHEMKIN suite can model the kinds of complex phase behavior associated with nonideal liquid mixtures, in particular, the existence of azeotropes and the phenomenon of phase splitting. Next, we added the model needed to represent the thermodynamic properties of HI-iodine-water mixtures to Liquid CHEMKIN. Although Liquid CHEMKIN already has some ability to handle ionic solutions and nonideal mixtures of nonelectrolytes, we needed a model that addresses both of these complexities simultaneously. Due to convergence problems in the code, we did not completely satisfy the final step of using the thermodynamic model adopted in the third step to compare the results of EQUIL computations with experimental data to evaluate any unknown parameters for the HI-iodine-water system. This problem could be overcome with additional effort.

52595

Real-Time Discriminatory Sensors for Water-Contamination Events

P. R. Lewis, D. R. Wheeler, G. R. Dulleck, Jr., W. Einfeld, R. P. Manginell, S. M. Dirk, D. E. Trudell

America's water-distribution systems are vulnerable to contamination either through malicious intent or accidental methods. Online methods such as free available chlorine (Cl), total organic carbon (TOC), and conductivity sensors can quickly determine state changes in the system (assuming good baseline information is available). However, current methods of organic sample collection/analysis are costly, slow, and useful primarily for imposition of fines, not for protection of the consumers. Mitigation steps need to be performed immediately, following detection of contaminants in the water system, not days after the sample is collected. Sensors identifying specific contaminants would allow water-system operators options to address the problem by suspending water flow in the parts of the system where contamination has been detected. Real-time identification of the contaminant(s) would be helpful in determining effective mitigation methods and procedures, as well as in providing timely notification to the water-utility customers.

The gas-phase μ ChemLab™ developed by Sandia can detect volatile organic compounds (VOCs) and semivolatile organic compounds (SVOCs) via gas-phase sampling. This unique Sandia-developed detection system would have uses for cost-efficient determination of environmental contaminants such as toxic industrial compounds, as well as chemical contaminants that might be introduced through malevolent anthropomorphic actions. This versatile device could be adapted for use as a small-footprint, low-cost, reliable, sensitive, and quickly deployable water sensor. We demonstrated purge and trap (P&T), as well as solid-phase microextraction (SPME), in proof-of-principle experiments with this device with contaminants of regulatory concern. We also analyzed chemical-weapon (CW) hydrolysis products. Further development of this system requires changes that include sizing to meet the required form factor, a front-end condensed-phase sampling system, analyte-specific coatings/separation methods, possible derivatization methods, and calibration standards. Coupled with this is the need for field-testing and determination of system reliability/stability in a condensed-phase analysis system.

America's water-distribution systems are vulnerable to contamination either through malicious intent or accidental methods....The gas-phase μ ChemLab™ developed by Sandia can detect volatile organic compounds (VOCs) and semivolatile organic compounds (SVOCs) via gas-phase sampling. This unique Sandia-developed detection system would have uses for cost-efficient determination of environmental contaminants. ...This versatile device could be adapted for use as a small-footprint, low-cost, reliable, sensitive, and quickly deployable water sensor.

(1) *Collect a listing of current regulatory organic compounds and identify appropriate simulant species for water-soluble CW agents and their hydrolysis products; select a subset of these compounds as our target set.* We completed this task by collecting information from publicly available sources regarding di-n-butyl phthalate (DBP), Environmental Protection Agency (EPA) methods, Edgewood Chemical Biological Center (ECBC) water-sensor guidelines, etc. We developed two general categories for this information: disinfection by-products (halogenated organics) and CW hydrolysis products (alkyl phosphonates). We also identified potential interferants that our system must be able to discriminate against by either selective uptake during collection, chromatographic discrimination, or surface acoustic-wave (SAW) detector adsorbent selection.

(2) *Identify potential capture absorbents for concentrating VOCs and SVOCs; research commercially available separation absorbents and possible derivatization methods.* We identified commercially available capture and separation absorbents that can be incorporated into our system. Unfortunately, a lack of parts limited our ability to actually test these materials in microelectromechanical systems (MEMS) devices, although we did test on a macroscale. We fabricated a few columns for separation; however, their flow restrictions made them unusable for our application. We synthesized the first generation of the trap tag-and-release material and tested it with acetic acid to show that it works as designed. We verified derivatives using thermogravimetric analysis (TGA)-infrared (IR) tests.

(3) *Build alpha-test stripping cell prototype to be used with macro-gas chromatographs (macro-GCs) in the lab.* We fabricated a macro alpha-testing cell that can be reconfigured for use with each of the three methods of collection: P&T, trap tag-and-release, and solid-phase extraction. We currently are testing the system with new pumps and valves. The pumps have 40% greater power than previous ChemLab pumps (although at a power penalty), and the valves are designed to handle liquids as well as gases. We monitor and control this system, along with the SAW detector system, using a custom-built program. This system allows us to collect data and analyze them using the combined system, rather than just testing each of the parts separately.

(4) *Test macro-P&T of simulants with identified absorbents on macro-GC system, evaluate detection limits and times needed for analysis.* We took the absorbents identified in (2) and used small sections of commercial GC columns to demonstrate the separation of the VOC and SVOC materials on

full-size GC systems with flame ionization detectors (FIDs). We also tested a subset of the VOCs on a SAW device using a planer preconcentrator (PC) to collect head-space samples and then separated and detected the materials. We have not determined detection limits for each of the compounds because this will depend on the parameters of the PC, which has not yet been optimized.

(5) *Test macro solid-phase-extraction PC system on a macro-GC system; evaluate detection limits and times needed for analysis.* We used coated MEMS columns, fabricated from two different adsorption materials (BSP3 and Carbowax), as solid-phase collectors to demonstrate collection of analytes from a water stream. After collection, we air-dried the columns and then heated and focused them onto a standard planar PC. We then fired the PC and detected material using a commercial FID. We determined lower limits of 1 ppm using this method. Calculations indicate that a detection level of 1/10 of the 1 ppm limit will be necessary.

In other work, we are working on a component of our device that will allow us to use commercially available and packaged collection materials rather than microscale parts for interfacial adsorption/capture. This will offer the potential advantages of decreasing the cost of any system device and possibly increasing the capture efficiency, while taking advantage of commercially proven coatings and materials.

Other Communications

Showalter, S. K., P. R. Lewis, D. R. Wheeler, D. E. Trudell, and R. P. Manginell. 2003. Application of the gas-phase μ ChemLab™ platform to analytical water-detection methods. Paper presented at the American Chemical Society National Meeting, September, New York, New York.

52596

Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors

S. A. Wright, P. S. Pickard, M. E. Vernon, P. H. Helmick, M. F. Young, S. M. Luker

Nuclear-power systems are receiving increasing attention as the enabling technology for new and challenging Department of Energy (DOE), National Aeronautics and Space Administration (NASA), Department of Defense (DoD), and commercial space and terrestrial applications. The key factor in this interest is the ability of closed-Brayton-cycle (CBC) systems to efficiently produce electricity. This project examines the system-wide coupling issues between nuclear reactors and CBC power-conversion systems. Sandia is performing the overall project effort in three major tasks. The first task consists of developing a dynamic systems model for the reactor and the closed-loop power-conversion system. The second task focuses on developing and fabricating a low-cost CBC electrically heated test-loop that will be used to verify the dynamic systems model. The third task consists of examining alternative advanced dynamic power-conversion systems that might prove useful for terrestrial or space-based power-conversion systems.

In addition to using this combined analytical and experimental approach, we are collaborating with potential users and customers of these systems. Collaborations with NASA and commercial aerospace corporations are currently in progress. We expect this work to provide a basis for multiple future Sandia programs in the ongoing DOE, NASA, commercial, and defense applications.

We made major accomplishments in dynamic model development, test-loop hardware design, publications, and attraction of additional funding. Our major accomplishments were as follows:

(1) We developed both a lumped-parameter dynamic systems model and a dimensionally distributed dynamic systems model for the coupled reactor and CBC system. The lumped-parameter model predicts regions of stable operation and the dynamic response to electrical-load fluctuations. The more detailed dimensionally distributed dynamic model is capable of predicting start-up and shut-down transients.

(2) We presented and published a paper describing the dynamic model at the American Institute of Aeronautics and

This project examines the system-wide coupling issues between nuclear reactors and CBC power-conversion systems. Sandia is performing the overall project effort in three major tasks....We expect this work to provide a basis for multiple future Sandia programs in the ongoing DOE, NASA, commercial, and defense applications.

Astronautics (AIAA) 1st International Energy Conversion Engineering Conference.

(3) We successfully acquired a Cooperative Research and Development Agreement (CRADA) with Northrup-Grumman Space Technologies (NGST) to collaborate with them in the development of a dynamic systems model for a nuclear-electric-propelled spacecraft.

(4) We successfully acquired a CRADA (consisting of shared-vision funds) with Lockheed Martin Corporation. Sandia will apply our dynamic model to nuclear-electric spacecraft designs and to evaluate start-up, normal, and off-normal operational transients as part of a study.

(5) We analyzed a variety of thermodynamic advanced/alternative power-conversion systems for both space and terrestrial applications. We are preparing a paper describing these results to be published in *Space Technology and Applications International Forum-STAIF 2004*.

Refereed

Wright, S. A. 2003. Dynamic model of a space-reactor Brayton-cycle system. *Transactions of the American Nuclear Society Meeting* (16–20 November, New Orleans, Louisiana).

Wright, S. A. 2003. Preliminary results of a dynamic systems model for a closed-loop Brayton cycle coupled to a nuclear reactor. *Proc. 1st International Energy Conversion Engineering Conference (AIAA Meeting)* (17–21 August, Portsmouth, Virginia).

Wright, S. A., and R. D. Beets. 2003. Application of a digitally controlled reactor architecture to space reactors. *Transactions of the American Nuclear Society Meeting* (16–20 November, New Orleans, Louisiana).

52597

Securing Mobile Code

C. L. Beaver, L. G. Pierson, M. D. Torgerson, P. L. Campbell, T. J. Draelos, R. C. Schroepel, D. L. Harris, W. E. Anderson, W. D. Neumann, H. E. Link

Sandia proposes to investigate the following question: Can we compute securely and reliably on untrusted hosts?

We believe that this question addresses the next step in the development of secure computing:

(1) The first step was symmetric key cryptography, which enabled secure communication. However, this required a trusted courier to establish keys.

(2) The second step was public key cryptography, which enabled establishment of keys without trusted couriers. However, this required that the remote host be trusted.

(3) The third step will be to enable remote secure computing, even on untrusted hosts over untrusted links. We believe the key to this is secure mobile code.

Mobile code moves from host to host. It is subject to the problem of “mutual suspicion”: The host is suspicious of the code, and the code is suspicious of the host. Encrypted functions are one promising approach to solving the latter problem. Research shows that encrypted functions can be used to hide the nature of computations, but perhaps only for computations represented by rational functions. We will try to answer the following questions about encrypted functions:

- Can they be applied to generic computational problems?*
- Can they provide sufficient performance?*
- Are they sufficiently secure for problems of national importance?*

Our approach will be to evaluate current research and try to extend and create new results with the goal of developing practical applications that can be applied to problems of national interest. We will combine theoretical research with prototyping of the communications and algorithms to achieve a greater understanding of problems and vulnerabilities.

Important applications of our results would include secure outsourcing of computations to aid in modeling and simulation of complex systems and aid in process control systems for critical infrastructures. Furthermore, the research has potential for commercial value in the arena of content protection.

- Literature search and annotated bibliography. We conducted an extensive literature search and created an*

Sandia proposes to investigate the following question: Can we compute securely and reliably on untrusted hosts?

...Important applications of our results would include secure outsourcing of computations to aid in modeling and simulation of complex systems and aid in process control systems for critical infrastructures. Furthermore, the research has potential for commercial value in the arena of content protection.

annotated bibliography of over 100 pages that we believe captures all important work done in the area. Further, we created a binary bibliography tree that categorizes the research based on classifications such as software-versus-hardware models, encrypted functions, obfuscated functions, etc. We also have a computer program that takes as input these categories and generates a lattice, which provides more expressiveness.

- *Threat model.* In the mobile-code scenario, we assume the adversary has complete access to executable code, control over execution, and input and output. Our threat model considers the threats against confidentiality, integrity, availability, access and nonrepudiation of the assets of data, code, execution, input, and output.

- *Research.* Our main research was in the areas of obfuscating functions and proving results about the existence of obfuscated functions.

(1) There are many efforts to produce obfuscators. One such technique is called *white-boxing*. In the white-box model, the adversary (in our case, the host running the mobile code) has full access to the code and controls its execution. The code must be such that the adversary cannot learn its true function or any secrets it may be protecting. In one paper, the authors apply white-boxing to the Data Encryption Standard (DES) through a process of encoding a series of linear integer computations and nonlinear table lookups as a series of randomized table lookups. The result is a simple algorithm to propagate input data through the tables until a final output is computed, without exposing any information about the algorithm or the intermediate results during the process. We deciphered the process described by the papers, implemented the authors' proposed algorithm, identified a potential flaw in the algorithm, and implemented a new similar algorithm with several minor improvements. We began analyzing the attacks presented by the papers and attempting an implementation of the attack, which indicates that the attack may not actually work. We started a paper describing our improvements and an analysis of the security impact of our improvements. We began considering the generality of the white-box technique, which is not addressed by the original authors. Although the implementation may be more complicated, it may be possible to white-box an arbitrary program by compiling it to a virtual machine (VM) instruction set with a small register size, to precompute the VM's effects based on the program, and to white-box the resulting sequence of operations after representing the machine instructions as table lookups. We hope to proceed with the design and begin a prototype implementation of a simple VM in the upcoming

work. The advantage of such a technique would be the obfuscation of an arbitrary program, preventing it from being reverse-engineered without extreme (hopefully prohibitive) effort on the part of an adversarial host computer.

(2) Recently, it was shown that constructing a generalized obfuscator for either Turing machines or circuits using the “virtual black-box” definition of obfuscation is impossible. This led many to conclude that the theoretical definition of obfuscation needs to be changed or a “possibility” result given for certain types of useful complexity classes. This deduction, however, is arguably flawed since obfuscation takes on many forms, depending on the application at hand. We are attempting to show that theoretical obfuscation is still possible for certain types of applications, in particular, remote computing and obfuscated encryption systems.

52598

Novel Catalysts for Hydrogen Fuel-Cell Applications

I. C. Abraham, S. M. Thornberg, R. L. Jarek, M. J. Kelly, E. N. Coker, W. A. Steen, J. E. Miller

Catalysts in hydrogen (H) fuel-cell applications have had to rely heavily on high concentrations of platinum (Pt). The high cost and scarce supplies of Pt are important barriers toward the commercialization of fuel cells, given the present requirements of almost 25 g per cell for automotive applications. A more inexpensive and readily available catalyst would aid the development of fuel-cell-powered vehicles. Small differences in particle size have been shown to affect catalytic activity for clusters of a few dozen atoms. However, traditional catalyst-characterization techniques, where testing and synthesis are separate steps, make it difficult to determine the optimal particle size.

Sandia will use laser-ablation mass spectrometry (MS) to generate a range of cluster sizes of known mass, whose adsorption of H and carbon monoxide (CO) molecules will be measured in vacuo. This unique approach is a rapid and parallel method to provide fundamental data that will test the catalyst chemistry prior to synthesis. We will investigate non-Pt catalysts, e.g., tungsten (W) and alloys of Pt with other metals, e.g., ruthenium (Ru). We will then design supported catalysts using the optimal cluster size, thereby significantly decreasing the total amount of metal required and potentially yielding catalysts that are more resistant to CO deactivation. We will then test optimum catalyst designs for electrolytic efficiency and resistance to CO poisoning by electrochemical measurements of fuel-oxidation processes. We will test promising electrodes in a prototype fuel cell. This research has the potential for dramatic reductions in the cost of fuel-cell electrodes.

We assembled the quadrupole ion guide and achieved associated vacuum apparatus and high vacuum (10^{-10} Torr). We are now using the Nd:YAG (neodymium:yttrium aluminum garnet) laser to align the enclosed optical-beam path into the laser-ablation chamber containing the Pt rod. The apparatus was configured to be tested outside of the Fourier-transform mass-spectrometry (FTMS) vacuum chamber using a Channeltron detector. This interim step will ensure that ions are in fact being channeled by the ion guide, prior to adding the timing and ion-trapping complications inherent in coupling the ion guide to the FTMS instrument. We have encountered no substantial

Sandia will use laser-ablation mass spectrometry (MS) to generate a range of cluster sizes of known mass, whose adsorption of H and carbon monoxide (CO) molecules will be measured in vacuo. This unique approach is a rapid and parallel method to provide fundamental data that will test the catalyst chemistry prior to synthesis....This research has the potential for dramatic reductions in the cost of fuel-cell electrodes.

technical difficulties up to now, although the accomplishment of the laser-ablation milestone has been delayed.

We purchased, installed, and tested TurboMole software, which will allow examination of metal clusters via advanced molecular mechanics methods that utilize the *ab initio* (e.g., Hartree-Fock) calculations as a high-accuracy force field. This will allow for a very comprehensive search of cluster geometries for a set of low-energy isomers that we can then further analyze in detail.

We performed initial calculations with up to three Pt atoms and obtained excellent agreement with experimental results obtained for the Pt₂ cluster, with calculated to experimental dissociation energy of 3.26 and 3.14 eV, respectively. These are encouraging results, as the electronic state of Pt makes these determinations problematic.

Encapsulating Pt within a zeolite and partially filling the zeolite pores with conductive carbon (carbonized furfuryl alcohol) achieved our milestone of synthesizing catalyst particles of a controlled size. This novel synthesis method resulted in a technical advance (Sandia Advance # SD-7389/S-100,498). A final step in the catalyst preparation is to remove the zeolite “host” by dissolution, thus increasing both the porosity of the matrix and the Pt mass fraction. This step is currently being investigated.

We achieved unprecedented control over Pt cluster size through the ability to vary Pt concentration (zeolite type, ion-exchange conditions), initial cluster size (zeolite pore/cavity size, thermal treatment), and potential for sintering (degree of pore filling by polymer). For example, heating 20 wt.% Pt zeolite X to 400°C at 2°C/min yielded 3–6 nm Pt particles (ca. 1000–9000 atoms), while heating at 0.1°C/min yielded 0.6–0.9 nm clusters (ca. 6–14 atoms), as confirmed by transmission-electron microscope (TEM) photographs. BET (Brunauer-Emmett-Teller) analysis confirmed that the materials retained relatively high surface areas (typically 130–450 m²/g, compared to the parent zeolite surface area of 600 m²/g). This is because the furfuryl alcohol is able to infiltrate only the larger voids of the zeolite lattice, leaving smaller, gas-permeable voids penetrating the entire crystalline material. Initial electrochemical tests confirmed the presence of a conductive catalyst, and gas chemisorption studies confirmed high Pt dispersions (ratio of surface atoms to bulk atoms). These novel composite materials serve as a model system with a high level of control over cluster size in a realistic catalyst environment.

We performed electrochemical testing (cyclic voltammetry) of several catalyst materials. The voltammograms for the seven

We achieved unprecedented control over Pt cluster size through the ability to vary Pt concentration (zeolite type, ion-exchange conditions), initial cluster size (zeolite pore/cavity size, thermal treatment), and potential for sintering (degree of pore filling by polymer).

powder samples did not produce the distinct features characteristic of Pt in aqueous electrolytes (peaks for oxygen monolayer deposition/removal, H monolayer deposition/removal, etc.); however, there was clearly an enhancement in the current density for H evolution at the working electrode, which is a likely indication that the powder samples did contain electrochemically active forms of Pt.

Refereed

Coker, E. N., and I. C. Abraham. 2003. Novel platinum/carbon catalysts with cluster size control for hydrogen fuel cells. *Proc. DOE Non-Platinum Electrocatalyst Workshop* (21–22 March, New Orleans, Louisiana).

Coker, E. N., D. L. Mowery-Evans, and J. E. Miller. 2003. Synthesis of novel platinum/carbon catalysts for use in hydrogen fuel cells. Paper presented at the 17th Annual Western States Catalysis Club Meeting, 28 February, Golden, Colorado.

Coker, E. N., I. C. Abraham, R. L. Jarek, S. M. Thornberg, D. L. Mowery-Evans, and J. E. Miller. 2003. Platinum cluster size optimization via chemical synthesis and laser-ablation mass spectrometry: Development of enhanced fuel-cell catalysts. *Proc. 18th Annual Conference of the North American Catalysis Society* (1–6 June, Cancun, Mexico).

Coker, E. N., W. A. Steen, J. E. Miller, and I. C. Abraham. 2003. Synthesis of novel platinum/carbon catalysts for use in hydrogen fuel cells. *Proc. 4th DOE National Laboratory Catalysis Conference*, accepted.

Steen, W. A., E. N. Coker, M. J. Kelly, J. E. Miller, and I. C. Abraham. 2003. Platinum/carbon catalysts for use in hydrogen fuel cells—Synthesis and characterization. *Proc. 15th Annual Rio Grande Symposium on Advanced Materials*, accepted.

52606

Linking Optimization and Simulation in Critical Infrastructure Systems

D. A. Jones, C. R. Lawton, C. A. Phillips, M. A. Turnquist, L. K. Nozick

Sandia has an ongoing, intensive set of activities to explore critical infrastructure interdependencies. To date, the modeling tools developed in this effort have been simulation-based. We propose to research and develop optimization-based models designed to work in conjunction with simulation. This approach will assist in identifying optimal strategies for decisions made in complex interconnected infrastructure systems under uncertain and dynamic conditions, especially in response to failures (whether natural, accidental, or malicious). The goals of this effort are to identify optimal strategies for mitigating vulnerabilities and to develop effective strategies to restore functionality.

We will leverage the Leontief-based modeling approach, which is based on dynamic input/output (I/O) modeling, as a framework for connecting simulation and optimization models of complex interconnected infrastructure systems. The dynamic I/O paradigm creates a structure to link the complex behavioral elements of simulations to overall relationships among key variables that are necessary for the optimizations. This is particularly important in investigation of failure modes, when rapidly changing conditions produce an uncertain decision-making environment. We will leverage our expertise in optimization under uncertainty to create a new set of tools for supporting effective decision making related to critical infrastructure vulnerabilities.

With the successful completion of this research, the algorithms and techniques developed will provide crucial insight for the decision-making processes associated with critical infrastructure protection. Strategies that allow for more effective protection of these systems will result, increasing our national security. This result has direct applicability to the National Infrastructure Simulation and Analysis Center (NISAC) program and Sandia's Critical Infrastructure Protection program as a whole.

In our initial proposal, we identified Leontief-based, dynamic I/O modeling as a likely framework for connecting simulation and optimization models of complex interconnected infrastructure systems. We proposed to explore both linear and nonlinear approximations of I/O functions that would represent

Sandia has an ongoing, intensive set of activities to explore critical infrastructure interdependencies....With the successful completion of this research, the algorithms and techniques developed will provide crucial insight for the decision-making processes associated with critical infrastructure protection. Strategies that allow for more effective protection of these systems will result, increasing our national security.

the important simulation-model characteristics for incorporation into the optimization model. We are on track toward achieving these goals.

We are creating a linkage between optimization and simulation models that capitalizes on the strengths inherent to each technique. We use a simulation model to represent detailed characteristics of a modeled system. Based on experiments with the simulation, we estimate a set of parameters, e.g., coefficients in equations, for the I/O representation.

We then use the equations from the I/O representation to form constraints for the optimization analysis. By solving this optimization, we can identify ways to improve the system, e.g., where to make investments to reduce vulnerabilities. The output from the optimization is a set of tentative design decisions that are reflected as changes in the I/O structure. These changes are then translated into modifications of operating rules that can be tested in the simulation.

As we pursued this avenue of research, we identified a more-specific modeling approach that has provided significant insight into effective strategies for modeling interconnected infrastructures. This approach is based on modeling uncertain evolution of the condition and capacity of infrastructure networks over time using Markov and semi-Markov processes. This idea lends itself very naturally to a combined simulation/optimization analysis to produce strategies for addressing the goals of this effort. We invested significant time focusing on the Markov-based modeling approach because it gives us an excellent starting point for our overall research objectives. The Markov-based approach leads naturally to the more-general dynamic I/O framework. This more-general mathematical framework, which will be the focus of upcoming research, allows for the construction of optimal investment strategies in infrastructure systems where the underlying simulation models are non-Markovian.

As a result of investigation into this Markov-based approach, we satisfied all of the current milestones. We successfully described a detailed approach for addressing highly dynamic representations of interconnected infrastructure networks. We documented a method for estimating the necessary modeling coefficients and successfully tested initial versions of the mathematical framework on small test problems. We are on track to address formulation modifications, including a nonlinear representation, in future work.

...we identified a more-specific modeling approach that has provided significant insight into effective strategies for modeling interconnected infrastructures.

Refereed

Nozick, L. K., M. A. Turnquist, D. A. Jones, J. R. Davis, and C. R. Lawton. 2003. Assessing the performance of interdependent infrastructures and optimizing investments. *Hawaii International Conference on System Science*, accepted.

52608

The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water

R. C. Moore

This project is divided into two parts. First, Sandia will develop a new process for the formation of apatite in soil and groundwater for containment of radionuclides and heavy metals. Although apatite has been successfully formed in soil and water, the mechanism of apatite formation, including kinetics, and the mechanism of radionuclide sorption must be known before it can be applied in the field. We propose that the mechanism of radionuclide sorption and apatite formation be determined. We will determine the mechanism through batch and column experiments, desorption experiments, and analysis of apatites with sorbed radionuclides. The second part of this work is aimed at developing new, inexpensive sorbents to remove arsenic (As) from drinking water. The original aim of this work was to use magnesium hydroxide ($\text{Mg}[\text{OH}]_2$) as a sorbent. We propose to investigate the use of Sorrel's cement for As sorption. Preliminary experiments indicate that Sorrel's cement sorbs As. In addition to investigating the use of Sorrel's cement as As sorbents, we also propose work with zirconium (Zr)-doped activated carbon and zeolites. Preliminary experiments indicate Zr-doped material can quickly and effectively sorb As from water.

...Sandia will develop a new process for the formation of apatite in soil and groundwater for containment of radionuclides and heavy metals.

(1) We determined that the mechanism of As sorption by $\text{Mg}(\text{OH})_2$ was through H bonding. We made this determination through solids analysis using x-ray diffraction (XRD), Fourier-transform infrared (FTIR), and Raman spectroscopy.

(2) Sorption by hydroxyapatite appears to be through the formation of phosphate complexes or technetium (Tc) stannous phosphate complexes that sorb to hydroxyapatite. Carbonate and high-phosphate concentrations strongly affect Tc sorption.

(3) We completed column studies on As sorption by Zr. The water in our building contains very high concentrations of iron (Fe) and copper (Cu) and interfered with the experiments. We completed a final column study using water from a different system but have not analyzed the results.

(4) We found sorption to hydroxyapatite to be stable for months, whereas simply reducing Tc lasted only for several weeks. Additionally, it appears that oxalate forms strong complexes or insoluble compounds with Tc.

(5) Reducing agents other than tin (Sn), including hydrazine and sodium dithionate, were not as effective at reducing Tc and sorption to hydroxyapatite.

53591

Hydrogen Futures Dynamic-Simulation Model

T. E. Drennen, S. A. Jones, P. S. Pickard, A. E. Lutz, J. O. Keller, L. A. Malczynski

The overall goal of this project is the creation of a high-level dynamic-simulation model of the integrated hydrogen (H) enterprise by key sector, including H production, distribution, storage, and consumption. The Hydrogen Simulation Model (H₂Sim) allows the user to explore various technology options for each component of a complete H system, tracking both the costs of the delivered H and the carbon (C) emissions associated with each technology. H₂Sim will allow policy, corporate, and research and development (R&D) decision makers to gain a much better understanding of the future H enterprise, the implications of alternative enterprise configurations, and a strategic understanding of where R&D investment might have the greatest impact on making the H enterprise successful.

This modeling effort involves a Sandia Albuquerque/Livermore team of experts in H, nuclear, and fossil energy; energy efficiency; transportation; modeling; and economics. We successfully completed a working model that includes production, storage, transportation of the H, and its use in the transportation sector. We will further refine the model in upcoming work to include detailed consideration of C sequestration options and stationary end-use applications.

H may become an integral part of our energy sector in the coming decades. Exactly how an H economy might develop is unknown and is dependent on both the economics and the actual stage of development. For example, whereas it might make sense initially to transport H by truck to fueling stations, in the longer term, the low-cost option may be pipelines. The overall purpose of H₂Sim is to provide a clear and consistent method for comparing the various production, storage, transport, and end-use options for H.

Our major accomplishment thus far is completion of the first version of H₂Sim. The model is ready to be shown within Sandia. Following external peer review of the model, it can be shown externally. H₂Sim includes the production, storage, and transport of H, as well as its end use in vehicles. Major accomplishments include the following:

(1) *Identification of various system components to include in model.* There are several competing visions for how an H economy might develop. The main components of the system

The overall goal of this project is the creation of a high-level dynamic-simulation model of the integrated hydrogen (H) enterprise by key sector, including H production, distribution, storage, and consumption....This modeling effort involves a Sandia Albuquerque/Livermore team of experts in H, nuclear and fossil energy; energy efficiency; transportation; modeling; and economics. We successfully completed a working model that includes production, storage, transportation of the H, and its use in the transportation sector.

include feedstocks (natural gas, coal, oil, waste, electricity, nuclear, or centralized solar power), H production options (reforming, gasification, electrolysis, thermochemical, and noncatalytic partial oxidation [NPO]), transportation (truck, rail, ship, or pipeline), storage (compressed, liquid, or solid), and end use, whether stationary (for commercial, industrial, or residential use), or for transportation (direct H combustion or fuel cells). This blueprint drove model development.

(2) *Extensive literature review and validation of assumptions.* The literature review was a crucial component early in the project. We incorporated technical and economic assumptions from each source into a detailed Excel spreadsheet that allows each team member access to key assumptions from a wide variety of sources.

(3) *Beta version of H_2Sim .* Development of the model involved turning the blueprint for the system components into a detailed, workable model.

60628

Dynamic-Simulation Modeling and Analysis Support for Senate Energy and Natural Resources Committee

T. E. Drennen, D. L. Harris, O. H. Paananen, P. H. Kobos, L. A. Malczynski

Sandia was asked to provide technical and policy support to the Senate Energy and Natural Resources Committee as they wrote and debated a national energy bill. This support included updating existing Sandia models to support possible requests for analysis of various energy issues. We updated three models: the U.S. Energy and Greenhouse Gas Model (USEGM), the Electricity Generation Cost Simulation Model (GenSim), and the Global Energy Futures Model (GEFM). We provided two analyses to the Senate Energy Committee: an analysis of the potential impact on carbon emissions by a phaseout of nuclear; and an analysis of S.139, "Climate Stewardship Act," sponsored by Senators McCain and Lieberman.

The Senate Energy and Natural Resources Committee was aware that Sandia had developed several policy-level energy-policy models relevant to the debate on energy policy: the USEGM, the GenSim, the GEFM, and the Dynamic Simulation Model of the National Security Consequences from Energy Supply Disruptions, USESM. At the time the request was made, Senator Domenici, Chairman of the Senate Energy and Natural Resource Committee, planned to hold a comprehensive debate on U.S. energy policy. It was in this context that Sandia's models would be most useful. Due to a change in congressional priorities, the debate shifted to consideration of the previous year's energy bill; the comprehensive debate we prepared for did not materialize. The scope of our support was therefore curtailed.

(1) We updated four models in preparation for possible requests from the Senate Energy and Natural Resources Committee: USEGM, GenSim, GEFM, and USESM. We wrote all four models in PowerSim Constructor, a dynamic-simulation modeling software package.

(2) We made considerable improvements to several of the models, including advanced user interfaces and translating the models into a newer version of the modeling software (PowerSim Studio 2001).

(3) We responded to two requests for analysis from the Senate Energy and Natural Resources Committee. The first request related to the impact on carbon emissions of various

Sandia was asked to provide technical and policy support to the Senate Energy and Natural Resources Committee as they wrote and debated a national energy bill. This support included updating existing Sandia models to support possible requests for analysis of various energy issues....The Senate Energy and Natural Resources Committee was aware that Sandia had developed several policy-level energy-policy models relevant to the debate on energy policy: the USEGM, the GenSim, the GEFM, and the Dynamic Simulation Model of the National Security Consequences from Energy Supply Disruptions, USESM.

levels of nuclear phaseouts. We considered three scenarios: a phaseout of nuclear by 2003, a phaseout by 2010, and no relicensing of existing nuclear plants. We did this analysis using the updated USEGM.

The second request from the Committee was to use the USEGM to analyze the potential impact of passage of Senate Bill 139, the “Climate Stewardship Act,” sponsored by Senators McCain and Lieberman.

64811

Agent-Based Control of Distributed Infrastructure Resources

L. R. Phillips, P. G. Cordeiro, J. W. Stevens, III, A. A. Akhil, J. W. Ginn, L. A. Weiland, R. B. Smith, M. E. Ralph

The goal of this project is to demonstrate that an intercommunicating coalition of Sandia's Standard Agent Architecture (SAA) software agents can control a microgrid securely, efficiently, and effectively. A microgrid is a cooperatively operated cluster of small (100 kW or less) electric-power generators called microsources. Demonstration of an automated microgrid will greatly enhance the potential of microgrids to penetrate the distributed generation market, which supports the Department of Energy's ambitious goal of 26.5 GW (at least 265,000 microsources) of new distributed-energy resource capacity by 2010. Widespread penetration can occur only with automated control because the large number of elements precludes manual control. Our overall plan is to develop a group of agents that use a shared strategy to control a simulated microgrid, then transition to hardware by substituting actual microsources for simulated ones. We intend that everything in the project's final demonstration will be real: real agents on real computers operating real hardware. We also expect to use the simulation to illustrate operation of a more-complex microgrid than resources will permit. In parallel, we will develop a control algorithm that will enable the agents to optimally allocate microgrid (or similar) resources. The initial control algorithms will involve neither agents nor hardware and will depend on many simplifying assumptions. We will remove assumptions and increase the number of entities that the algorithm can accommodate to enable operation of a realistic plant. A third effort will develop individual device-control tactics, enabling a single agent to control a single microsource. This three-pronged approach will culminate with a coalition of agents controlling several microsources and communicating with one another to operate the cluster as a coordinated microgrid. The inherent communications security (COMSEC) and operations security (OPSEC) capabilities of SAA agents will enable demonstration of secure operation with only incremental funding.

The most important features of this work include the following:

Our overall plan is to develop a group of agents that use a shared strategy to control a simulated microgrid, then transition to hardware by substituting actual microsources for simulated ones....This three-pronged approach will culminate with a coalition of agents controlling several microsources and communicating with one another to operate the cluster as a coordinated microgrid.

- (1) Formulation of a demonstration that satisfies project needs, provides an achievable goal, and illustrates the potential of both SAA agent technology and microgrid technology
- (2) Demonstration of an applicable control framework
- (3) Operation of the necessary agent software
- (4) Completion of the Caterpillar generator software model.

We also made significant progress in defining and constructing the simulated microsources needed for testing agent behavior without needing to activate the hardware microsource generators and in constructing agents that will execute the scenario.

The demonstration scenario consists of two microsources serving four loads and several load-increase/load-decrease events. Supervisory control can achieve minimum cost by properly allocating loads to microsources, whereas local control assigns each load to its nearest source. We achieved our goal to exhibit a control framework in which the supervisory result is superior to the local result.

Currently, the challenge is to achieve optimal results with a distributed system not controlled by a single supervisor. Preliminary results indicate this can be done, although scaling to a distributed situation with more than a few generators will require a more-advanced control strategy. We enlisted the aid of a Sandia expert in advanced controls to assist in this scaling.

We completed the software model for the Caterpillar and started work on the Capstone microturbine model. We also operated the agent running the simple control algorithm in our lab, although we have not yet actually communicated with the generators.

We also made significant progress in defining and constructing the simulated microsources needed for testing agent behavior without needing to activate the hardware microsource generators and in constructing agents that will execute the scenario.

65557

Optical Trapping of Collisionally Cooled Molecules

D. W. Chandler

The observation of Bose-Einstein condensation in a gas of sodium atoms in 1995 set the atomic-molecular-optical (AMO) physics community on its ear and re-energized the field. Extraordinary advances in AMO physics have yielded atom lasers, atom interferometry, and fundamental reactions and scattering among ultracold atoms. These advances point to new applications in metrology, quantum computing, and others.

The AMO community has been stymied, however, in its efforts to extend this work from atoms to states of ultracold molecules. If successful, broad impact is anticipated in chemical science as well as on new applications resulting from controlled quantum processes in molecules. The challenge is that the optical cooling of alkali atoms does not work for molecules because they lack the required “two-level” optical transitions. Specialized cases (photoassociation of cold alkali atoms) have been demonstrated, but, to date, no general approach has proved successful for assembling collections of ultracold molecules.

Recently Sandia observed collisional arrest of lab-frame velocities of ~ 108 quantum-state–selected nitric oxide (NO) molecules in a crossed-molecular-beam–scattering apparatus. This technique is applicable to many molecules and for many quantum states, and represents, we believe, an opportunity for a breakthrough in the AMO science of ultracold molecules. We seek to demonstrate optimization of the scattering dynamics for collisional arrest and to optically trap the molecules in crossed laser beams, thereby demonstrating that they are cooled well below 1 K. This demonstration will be the first step toward the ultimate goal of demonstrating the first Bose-Einstein condensation of molecules.

We demonstrated the cooling of a molecule by a single collision between the molecule and an atom in a crossed-molecular-beam apparatus, giving the molecule a laboratory velocity that is nominally zero. The technique relies on a kinematic collapse of the laboratory velocity distribution of molecules that are scattered with a particular recoil velocity vector in the center-of-mass frame. This approach is generally applicable to a broad range of molecular and atomic species. The method relies on the fact that in binary collisions, one of the collision partners can have a final center-of-mass-frame

We seek to demonstrate optimization of the scattering dynamics for collisional arrest and to optically trap the molecules in crossed laser beams, thereby demonstrating that they are cooled well below 1 K. This demonstration will be the first step toward the ultimate goal of demonstrating the first Bose-Einstein condensation of molecules.

velocity that is exactly equal in magnitude and opposite in direction to the velocity of the center of mass, thus yielding a laboratory-frame velocity that is identically zero. This outcome is not only general in principle, but it is also realizable under easily accessible experimental conditions in crossed atomic and molecular beams. The method does not rely on any particular physical property of either colliding species, since zero velocity is a consequence of the experimentally selectable energy and momentum of the collision pair. Moreover, this technique can be used to prepare a single, selectable rovibronic quantum state for trapping.

We demonstrated this technique using inelastic collisions between NO molecules in one beam and argon (Ar) in the other, specifically $\text{NO}(^2\Pi_{1/2}, j^1=0.5) + \text{Ar} \rightarrow \text{NO}(^2\Pi_{1/2}, j^1=7.5) + \text{Ar}$. Using an existing crossed-molecular-beam experimental apparatus that is not specifically optimized for the production of cold molecules, we generated scattered $\text{NO}(^2\Pi_{1/2}, j^1=7.5)$ with a velocity distribution that is centered about zero, with an upper-limit root-mean-square velocity of 15 m s^{-1} . We achieved densities of $108\text{--}109 \text{ NO molecules cm}^{-3}$ in this single $(^2\Pi_{1/2}, v^1=0, j^1=7.5)$ rovibrational quantum state. We used the technique of velocity-mapped ion imaging to characterize the scattering distribution and density of scattered NO molecules.

We repaired an Ar⁺ ion laser to use as a far-off resonant laser trap. Very cold molecules are trapped at the focus of a laser beam. The demonstration of trapping of cold molecules will lead to further cooling of molecules by evaporation.

66233

Efficacy of the Sandia Decon Formulation on the SARS Coronavirus

C. V. Williams, C. A. Souza, M. D. Tucker, J. M. Bieker

The purpose of this project is to evaluate the efficacy of the Sandia DF-200 decontamination formulation against the Secure Acute Respiratory Syndrome (SARS) virus. We also evaluated whether the active ingredients could be reduced to a lower level to make the DF-200 more environmentally friendly while still maintaining an efficacy of 7-log kill in a relatively short time period (5 min or less). For this study, we used preliminary testing with MS-2 bacteriophage to simulate single-stranded ribonucleic acid (RNA) viruses, known to exhibit greater resistance to decontamination. We used the Escherichia coli T4 bacteriophage virus to simulate double-stranded deoxyribonucleic acid (DNA) viruses. Inoculum in suspended media that was developed as adhered populations on various test surfaces was tested against the various decontamination formulations.

We used results from the preliminary work for continued decontamination research against Bovine coronavirus (BCV) at Kansas State University (KSU). BCV is the internationally accepted SARS surrogate. We revived and plated the host cells used in this study (HRT-18 [human rectal tumor-18]). We propagated the BCV to achieve a 5-log plaque-forming-unit inoculum level. We conducted efficacy testing using commercially available Sandia decontamination formulation. We conducted preliminary toxicity studies on the neutralizer, neutralizer + decon formulation, and the decon formulation. This more closely mimics the real SARS environment.

Studies continue at KSU with the Sandia investigators to statistically validate results, conduct the studies with an organic load, and evaluate efficacy on surfaces. We have initiated the process to acquire the SARS virus and will repeat the studies on the SARS virus in the BioLevel 3 Laboratory at KSU.

(1) Sandia developed protocols to conduct virus inactivation studies using the Sandia decon formulation. We developed a neutralizer to quench the decon reaction at the desired times. This is critical to validate the speed at which the Sandia decon formulation inactivates the viruses.

(2) We conducted efficacy studies against two bacterial viruses on the commercially available Sandia decon formulation. These formulations were effective in inactivation of the surrogate viruses within 2 min.

The purpose of this project is to evaluate the efficacy of the Sandia DF-200 decontamination formulation against the Secure Acute Respiratory Syndrome (SARS) virus. We also evaluated whether the active ingredients could be reduced to a lower level to make the DF-200 more environmentally friendly while still maintaining an efficacy of 7-log kill in a relatively short time period (5 min or less).

(3) Results of these efficacy studies indicate that the oxidizing agent can be reduced by half and still maintain the desired efficacy, even in the presence of organic load.

(4) Surface studies indicate that modified formulation DF-200 is 99.9% effective in 2 min against the MS-2 surrogate on a porcelain surface.

(5) Results of the feasibility studies on the BCV showed that we could conduct coronavirus inactivation studies in mammalian cells using the Sandia decon formulation.

(6) Results indicate that the Sandia formulation is effective in inactivating the BCV down to levels as low as 10% of the standard formulation.

Results indicate that the Sandia formulation is effective in inactivating the BCV down to levels as low as 10% of the standard formulation.

Nonproliferation and Materials Control

The Nonproliferation and Materials Control investment area seeks innovative ideas for reducing the nation's vulnerability to threats from the use of weapons of mass destruction—including nuclear, biological, or chemical weapons. Innovative research will promote a collective of capabilities and products that will enable development of organized system-level responses to national security challenges. This research focuses on (1) technologies for international security, (2) security systems and technologies, (3) response to biological and chemical threats, (4) technologies for intelligence, and (5) global virtual presence.

Robust Chemometrics for Remote Spectral Sensing has developed new techniques that promise to improve the robustness, performance, and utility of satellite-based hyperspectral imaging for applications in nuclear nonproliferation, chemical and biological weapons detection, and national intelligence. These applications require reliable identification, characterization, and quantification of target chemicals and materials. The performance of current spectral analysis algorithms suffers in the presence of background and sensor noise, residual pixel calibration

errors, sensor artifacts and drift, and atmospheric correction errors. Developing the ability to identify spectra in the presence of atmospheric, environmental, and instrumental variations will enable us to use remote spectral imaging to recognize facilities, identify chemical and biological agents, and detect man-made anomalies. Two patent disclosures and two patent applications have been filed.

26563

Advanced Digital Detectors for Neutron Imaging

F. P. Doty, B. A. Brunett, K. O. Wessendorf, D. H. Morse, D. A. Chinn

Sandia investigated new materials for direct electronic detection of neutrons. Our initial work concentrated on inorganic crystals including boron nitride (BN) and lithium tetraborate. We used pulse detection of alpha particles for initial screening of materials. Later we confirmed detector operation with neutrons from a nuclear reactor. We found pyrolytic BN to polarize severely over a relatively short time under bias. We investigated lithium tetraborate synthesis from aqueous gels. We spin-coated films on glass and silicon substrates, thermally processed them, and confirmed the structure by x-ray diffraction (XRD). However, we synthesized no neutron-sensitive films in this effort and directed additional effort toward electronic organic detector materials.

We evaluated three classes of new materials for direct electronic detection of thermal neutrons. We demonstrated detection of thermal neutrons in commercial pyrolytic BN detectors. Count-rate polarization limits the utility of the commercial samples evaluated to date. We also demonstrated direct detection of neutrons in commercial lithium tetraborate crystals and investigated a low-cost, high-volume production method for this material. We successfully synthesized thick films of spin-cast lithium tetraborate gel from aqueous solutions. We heat-treated the gels to remove water and effect the phase transformation, and confirmed the correct structure by XRD. (None of the in-house-synthesized films was confirmed to be sensitive to neutrons.) We received U.S. Patent 6,388,260 on May 14, 2002, for solid-state neutron detectors and method for use. We evaluated the use of boron-loaded organic semiconductors. We acquired additional funding for neutron detection under Work for Others and Department of Energy exploratory research.

We evaluated three classes of new materials for direct electronic detection of thermal neutrons....We successfully synthesized thick films of spin-cast lithium tetraborate gel from aqueous solutions....We received [a patent] on May 14, 2002, for solid-state neutron detectors and method for use.

26564

Microfabricated Acoustic Spectrum Analyzer

E. J. Heller, D. R. Adkins, R. J. Shul, T. A. Friedmann, L. F. Anderson, H. L. Stalford

In this project, Sandia seeks to develop a microfabricated acoustic spectrum analyzer (MASA). The device is based on a passive array of resonant micromechanical filter elements, intended to produce a Fourier spectrum for incoming analog signals, and is intended for use in remote and covert monitoring. Much of the work was in the development of small, low-loss micromechanical filters that could be tuned to an array of resonant frequencies. Such an array must be small enough to take advantage of silicon (Si) integration technology. Additional work focused on the development of compact, low-power control circuitry to detect signals from the resonant array. We fabricated most of the resonant structures in Si to allow full integration with external control microelectronics. Although several micromechanical filter structures were produced for this project, the final year focused on the further development of a micro-teeter-totter membrane resonator and several micromechanical resonator devices fabricated in SUMMiT-V™ (Sandia Ultraplanar Multilevel MEMS Technology V) in the Microelectronics Development Laboratory (MDL). The micro-teeter-totter resonator consists of a Si membrane structure supported at the ends by narrow beams, and is driven by a Lorentz force using a current loop patterned on top of the membrane. The SUMMiT-V™ structures consist of fixed-fixed beams that use either planar capacitor or comb-capacitor drive and detection elements. Several of these devices also used piezoresistive meander lines to detect deflection of both cantilevered and fixed-fixed beam structures. Resonant frequencies of these SUMMiT-V™ structures have yet to be measured. However, we produced arrays consisting of up to eight elements of the micro-teeter-totter using both 5 and 10 μm -thick silicon-on-insulator (SOI) substrates on 6 mm x 6 mm die, and filed a patent application for the micro-teeter-totter structure and fabrication process. The micro-teeter-totter devices have resonant frequencies between 10 KHz and 50 KHz, depending on the thickness of the membrane used. We completed a demonstration MASA device using micro-teeter-totter resonant filters.

Much of our work was in the development of small, low-loss micromechanical filters that could be tuned to an array of resonant frequencies, and the majority of the work focused on

Array of eight micro-teeter-totter resonators.

*...Sandia seeks to develop a microfabricated acoustic spectrum analyzer (MASA).
...we produced arrays consisting of up to eight elements of the micro-teeter-totter using both 5 and 10 μm -thick silicon-on-insulator (SOI) substrates on 6 mm x 6 mm die, and filed a patent application for the micro-teeter-totter structure and fabrication process.*

developing arrays of micro-teeter-totter resonant structures. The micro-teeter-totter is a Lorentz-driven device. We patterned a metal conductor loop on a thin Si membrane that is supported by struts at each end. We applied a magnetic field, generated by small permanent magnets, in the plane of the membrane and perpendicular to the direction of current flow, resulting in a force into and out of the plane. In response to alternating currents in the metal conductor loop, the structure “rocks” side-to-side like a teeter-totter, with a resonant frequency that is dependent on the width of the struts, the thickness of the membrane, the stress in the membrane, and the mass of the metal on the membrane. The fabrication process begins with a commercially available SOI wafer. We first defined the metal for the current loop on the membrane area. We then protected this metal and defined the membrane area for a Si deep reactive-ion etch (DRIE). The front of the membrane is now complete. Finally, we patterned the backside of the substrate, opposite each membrane, and etched it using Si DRIE. Results from the test were for 5 μm -thick micro-teeter-totter membranes, and the membranes should have had identical resonant frequencies. However, processing variations resulted in a 34 Hz difference in the resonant frequency of the structures. These results also showed a 7 ohm impedance change at resonance as well as the very narrow bandwidth of these devices.

In addition to the micro-teeter-totter resonator structure, we fabricated several micro-resonator structures in the SUMMiT-VTM microelectromechanical systems (MEMS) process in the MDL. The micro-xylophone bridge structure is driven by capacitive forces that are generated by applying a voltage between the moving fixed-fixed beam and the substrate. A piezoresistive meander line located where the beam is attached to the substrate measures the motion of the moving beam. We have not yet measured the resonant frequency of these structures. The piezoresistive element is located near the end of the beam, where it attaches to the substrate. We used a number of reticle sets to make these devices in SUMMiT-VTM. The structures of the resonators in reticle sets rs307 and rs307 (rerun) consisted of cantilevers and xylophone bars. We fabricated these with the special processing of a nitride layer to electrically isolate beam-drive electronics from sensor-output electronics (i.e., piezoresistive device). The structures of the resonators in the reticle set rs377 consisted of clamped-clamped beams. We fabricated these using a technology similar to that developed in rs307 (rerun), with the exception that we fabricated an additional nitride layer on top. We developed a

vertical comb-drive for the drive mechanism, which used all five layers (P0, P1, ..., P4) of SUMMiT-V™. Finally, we fabricated reticle set rs337 using the SwIFT™ process. The structures of the resonators in the reticle sets rs337 consist of both horizontally and vertically clamped-clamped beams.

26572

Coating Chemical Preconcentrators to Improve Chemical-Agent Collection

C. L. Rhykerd, Jr., R. Kottenstette, M. A. Mitchell

This project is investigating technology to improve the collection and detection of chemical agents by coating existing screen preconcentrators. This work is intended to benefit trace-detection programs for the Department of Energy (DOE), Department of Defense (DoD), and Department of Homeland Security (DHS).

Trace chemical-agent detection in the parts-per-billion (ppb), parts-per-trillion (ppt), and parts-per-quadrillion (ppq) ranges interests many Sandia customers, including the DOE, DoD, Rapid Assessment and Initial Detection (RAID) and National Emergency Search Teams (NEST) teams, law enforcement, and first responders. Field-ready prototypes with this sensitivity range require integrating a sampler and preconcentrator into a detection system (likely using microsensors). The preconcentrator manages the mismatch between the sampler flow (L/s) and the low detector flow (mL/s). For explosives, Sandia has developed, patented, and licensed a stainless-steel screen preconcentrator, improving system sensitivity by 10,000x. However, preliminary data with a chemical weapons simulant show that this metal surface is inappropriate for chemical agents because of low efficiency of adsorption and decomposition during thermal desorption.

We seek to develop a preconcentrator subsystem to enhance chemical-agent detection within the constraints acceptable to potential customers. Coating the screen to improve collection and reduce decomposition is a logical engineering solution to this problem. Potential coating candidates include sol-gels, polymers, and carbon nanotubes (CNTs). Successful coatings must be robust during temperature cycling to 200°–300°C and must adhere well to the substrate. A detection system is available for these evaluations, and a continuing effort to leverage newly developed materials at Sandia will be pursued.

Capitalizing on Sandia's strengths in sample collection, preconcentration, and materials, our success will lead to improved chemical-detection systems with enhanced capabilities, including sensitivity, portability, cost, and speed. This benefits customers interested in chemical-agent detection, explosives detection, drug detection, and environmental monitoring.

Capitalizing on Sandia's strengths in sample collection, preconcentration, and materials, our success will lead to improved chemical-detection systems with enhanced capabilities, including sensitivity, portability, cost, and speed.

We coated and evaluated several candidate materials for improving collection and concentration of volatile chemicals. This work advances engineering solutions for trace-detection systems for chemical warfare (CW) agents, high vapor pressure explosives, and more volatile chemicals generally. Coated materials tested improved analyte retention and collection. Higher desorption temperatures and characterization of vapor adsorption need more study. The coatings studied improved preconcentrator performance and are robust enough to be considered useful for portable trace-detection systems.

Coating Sandia's screen preconcentrator can enhance collection of volatile explosives and chemical agents. We recorded electron micrographs of two of the coatings. These micrographs show islands of coating for liquid drop coatings, but uniform results for spray-coated screens.

We injected drops containing nitroglycerine (NG) and dimethyl methyl phosphonate (DMMP) onto the screens, heated the screens to desorb the explosives into the detector (PCP-100 or Smiths Centurion), and recorded the detector response (mobility spectrum). We completed collection of data for the uncoated and coated screens with DMMP and NG analytes.

NG detection on coated screens (< 5 ng limit of detection) led to better understanding of desorption temperature control and resulted in reliable DMMP detection with limits of detection well below 20 ng, more than 50x improvement in detection. Increasing the desorption temperature of the coated screens, even above 250°C, improved DMMP release. Adsorption efficiency remains poorly characterized, but the coatings clearly improve retention of the analytes. A desorption temperature of 200°C seems to drive all the DMMP off of the coating in three to five heat cycles, with predictable exponential decay of the mass desorbed. Uncoated screens show negligible retention after one heat cycle. This result shows that the coatings enhance analyte collection and retention as desired. Flash heating to 300°C cleans off the screen completely. These coatings are robust, with demonstrated performance after hundreds of heat cycles at 200°C.

This work advances engineering solutions for trace-detection systems for chemical warfare (CW) agents, high vapor pressure explosives, and more volatile chemicals generally. Coated materials tested improved analyte retention and collection....NG detection on coated screens (< 5 ng limit of detection) led to better understanding of desorption temperature control and resulted in reliable DMMP detection with limits of detection well below 20 ng, more than 50x improvement in detection.

26574

Detection and Exploitation of Spread-Spectrum Waveforms

J. T. Cordaro, R. C. Ormesher, D. D. Cox, R. M. Holman, G. B. Haschke, B. D. Guess, C. R. Collins, J. J. Mason, R. M. Axline

Sandia explored the technical area of signal intelligence (SIGINT) collection and processing of spread-spectrum radio-frequency (RF) communications waveforms. We developed, integrated, and field-tested a complete prototype, tactical, balloon-based collection system that supports interception, relaying, sampling, and processing of RF signals having frequencies anywhere in the S-ISM (S-industrial, scientific, and medical) band. A transponder, carried by the balloon, relays intercepted S-band signals to a ground station via a C-band downlink. A general-purpose transmitter, developed as part of this project, allows us to send either mock-adversary transmissions or friendly communications signals through the transponder to the ground station. As the primary focus of this project, we developed MATLAB-based signal-processing algorithms, which we have used to analyze sampled signals collected by the ground stations. Using these algorithms, and with little or no prior knowledge of the incoming sampled waveforms, we can extract both external and internal waveform parameters of certain classes of waveforms.

We developed, integrated, and field-tested a complete prototype, tactical, balloon-based collection system that supports interception, relaying, sampling, and processing of RF signals having frequencies anywhere in the S-ISM (S-industrial, scientific, and medical) band.

We made the following accomplishments:

- Developed and prototyped new communications intelligence (COMINT) algorithms, based on the concept of code-free despreading.
- Derived and prototyped a number of previously known COMINT algorithms.
- Developed expertise in the various elements of the COMINT problem.
- Forged a Sandia/university partnership with the Physical Sciences Laboratory at New Mexico State University.
- Specified functional requirements for the Goldmine system and subsystems.
- Designed and implemented the Goldmine Transmit Station.
- Designed and implemented the Goldmine Ground Station.
- Conducted S and C ISM-band frequency surveys.
- Performed successful laboratory integration tests.

- Performed numerous air-link tests with the Goldmine transponder on South Baldy, a mountain in northern New Mexico.
- Executed one unsuccessful tethered-balloon test.
- Executed one successful free-fly-balloon demonstration.
- Used the Goldmine system infrastructure to perform friendly communications tests.
- Produced a prototype system and a model development process that show how we can, at relatively low cost, prove-in COMINT, SIGINT, or communications systems prior to more expensive airborne or satellite-borne deployment of these systems.

We are integrating the Goldmine capabilities into a planned demonstration test for the Global Personnel Recovery System (GPRS).

The well-developed state of the art in COMINT makes innovative contributions a significant challenge. Nonetheless, we developed algorithms that may represent improvements to the current art. We derived a number of existing (i.e., previously known) COMINT algorithms. Sandia technology areas are directly applicable to the problems of COMINT collection and exploitation. In particular, both synthetic-aperture radar (SAR) and spread-spectrum communications systems expertise provide an excellent basis for COMINT collection-system and algorithm developments. Many existing COMINT algorithms exploit periodicities and regularities normally exhibited by direct-sequence, spread-spectrum (DSSS) waveforms. Requirements for the COMINT transponder are very similar to those of a DSSS transponder, with the notable difference that the COMINT transponder is likely to have to cover a much wider bandwidth (to cover a range of frequencies spanned by the COMINT targets of interest).

A balloon host platform has the advantage of high altitude (80–100 kft) and large radio horizon (250–300 mi) in comparison with winged aircraft, including unmanned aerial vehicles (UAVs). In comparison to a satellite-based system, a balloon host is at a relatively shorter range from its ground station. This allows the ground station to employ a smaller antenna and obtain the same performance as a satellite ground station.

Balloons move slowly, providing relatively long mission times. The slow velocities also produce small Doppler offsets; this simplifies the ground receiver in comparison to the cases of a winged aircraft or a satellite host.

In certain scenarios, balloons could be a low-cost alternative to winged aircraft for COMINT.

The well-developed state of the art in COMINT makes innovative contributions a significant challenge. Nonetheless, we developed algorithms that may represent improvements to the current art.

Balloons can provide a low-cost alternative for testing and proving-in payloads that are to be eventually placed on a satellite host.

With the traditional free-fly balloon-launch techniques employed in the Goldmine tests, the balloon cannot be launched when ground wind speeds exceed about 5 mph. These restrictions may be acceptable for demonstration or testing scenarios; however, they are certainly unacceptable when we consider using a balloon as a tactical military asset. To mitigate these restrictions, one must look at different launch schemes.

- Another issue with helium-filled balloons is the fragility of the envelope material. Using very thin material (a fraction of a mil) reduces envelope weight, which allows the balloon to be smaller for a fixed payload weight. However, it appears that a fieldable tactical system should employ more rugged envelope material, and we should seek significant weight reduction in the payload and power supply.

Other Communications

Axline, Jr., R. M. 2003. Goldmine classified algorithms and analysis. Internal memorandum, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M. 2003. Goldmine level-2 processing and estimated link margin for type-1 waveforms. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M. 2003. Goldmine signal model and coherent algorithm ideas. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M. 2003. Goldmine system and subsystems requirements document. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M. 2003. Goldmine tether test plan. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M. 2003. Type-2 link-margin calculations for the Goldmine FY03 demo and other system design issues. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Axline, Jr., R. M., D. D. Cox, G. B. Haschke, B. D. Guess, R. M. Holman, and C. R. Collins. 2003. Goldmine LDRD Final Report: Detection and Exploitation of Spread-Spectrum Waveforms. Sandia Technical Report, Sandia National Laboratories, Albuquerque, New Mexico, in review.

Cordaro, J. T. 2003. Goldmine phase noise. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Cox, D. D., and T. Hooker. 2003. Frequency survey at South Baldy Peak. Memo, Sandia National Laboratories, Albuquerque, New Mexico.

Hooker, T. 2003. A novel balloon-based platform for information operations. White paper, Physical Sciences Laboratory, New Mexico State University, Las Cruces, New Mexico.

Hooker, T. 2003. Goldmine project final report. Technical report, Physical Sciences Laboratory, New Mexico State University, Las Cruces, New Mexico.

Physical Sciences Laboratory Staff and Sandia National Laboratories Staff. 2003. Near-space sensor system, Goldmine demonstration plan. White paper.

Zaklan, Z. 2003. Goldmine free-flight operations plan. Physical Sciences Laboratory, New Mexico State University, Las Cruces, New Mexico.

26577

Robust Chemometrics for Remote Spectral Sensing

M. M. Moya, C. B. Boney, D. M. Haaland, E. V. Thomas, M. R. Keenan, M. H. Van Benthem, C. L. Stork

For over 20 years, chemistry researchers have been developing increasingly flexible and robust multivariate analysis methods to predict the composition of chemical mixtures from laboratory spectrometer data. More recently, remote-sensing scientists have constructed and deployed imaging spectrometers to enable remote spectral analysis. However, analyzing remote imagery poses more challenging problems, such as the intervening atmosphere, more complex backgrounds and interferences, and uncontrollable environmental conditions. In this project, Sandia investigated chemometric analysis methods that possess potential to mitigate some of the difficulties with remote sensing. In particular, robust chemometrics (RoChem) extended and applied two chemometric analysis techniques to remote-sensing applications.

...Sandia investigated chemometric analysis methods that possess potential to mitigate some of the difficulties with remote sensing. In particular, robust chemometrics (RoChem) extended and applied two chemometric analysis techniques to remote-sensing applications.

(Leaf graphic)
Image of plant used to construct vegetation spectra for training sets.
(left) Nonresolved camouflage spectra obtained with no neutral-density filter. (middle) Nonresolved/nonvariable plant spectra obtained with different neutral-density filters. (right) Resolved/variable plant spectra obtained by sorting pixels.

In our first application, we applied robust prediction to discriminate camouflage from vegetation and estimate their subpixel quantities. Robust prediction is valid for applications that can implement an *a priori* training phase, which requires availability of the sensor, targets, and typical backgrounds. The trained algorithm predicts quantities of the trained spectra in new mixtures. Robust prediction methods cannot extract information from single images, but can provide powerful discrimination for wide-area-search and target-recognition applications.

To apply and test robust prediction, we collected training and test data in the spectral range 700 to 1000 nm with the information-efficient spectral imaging sensor (ISIS). We collected images of infrared (IR)-reflecting camouflage samples and vegetation. We observed that the various orientations of the plant leaves produced a large range of spectral intensities and nonlinear variations in spectral shape, as well. We generated a variable training set that included illumination-related spectral variations and a control training set that included intensity variations of the average plant spectrum, but no spectral shape variations. We applied dry-lab mixing to emulate subpixel mixing of the vegetation and camouflage spectra. We trained a Principal Components Regression model with and without the spectral variabilities and tested the trained models with new subpixel mixtures to predict their mixture quantities. Training with variabilities reduced the standard deviation of the quantification error by a factor of 3.7.

In our second application, we applied a fast and rigorous multivariate curve resolution (MCR) algorithm to remotely sensed hyperspectral images. MCR is an algorithmic approach that focuses on recovering the concentration and spectral profiles of the components in an unresolved mixture when little or no prior information is available about the nature and composition of these mixtures. Although MCR has been successfully applied in the characterization of laboratory-based spectroscopic measurements, this is one of the first applications of this algorithm in the field of remote sensing.

MCR applies constraints to an alternating least-squares algorithm to produce spectral estimates that correspond to physically relevant components. We apply constraints to narrow the solution space to those that are physically acceptable. Under this project, we developed rigorous equality constraints [Van Benthem, Keenan, and Haaland, 2002] and fast, rigorous inequality constraints [Van Benthem and Keenan, 2002]. We developed methods of combining equality and inequality

Although MCR has been successfully applied in the characterization of laboratory-based spectroscopic measurements, this is one of the first applications of this algorithm in the field of remote sensing.

constraints [Keenan and Van Benthem, 2002] and demonstrated the utility of preference constraints.

We applied MCR to ISIS images of mixtures of fluorescent dyes with highly overlapping chemical spectra and demonstrated MCR's ability to extract the individual spectra and quantify their spatial distribution despite their spectral similarity. [Keenan, *et al.*, 2002] describes the application and results in more detail. [Stork, Van Benthem, and Keenan, 2003] describes the results of applying MCR to remotely sensed hyperspectral data.

Refereed

Van Benthem, M. H., M. R. Keenan, and D. M. Haaland. 2002. Application of equality constraints on variables during alternating least-squares procedures. *J. Chemometrics* **16**:613–22.

Other Communications

Keenan, M. R., and M. H. Van Benthem. 2002. Fast algorithm for general equality- and inequality-constrained least-squares for problems having multiple solution vectors. Technical Advance, submitted.

Keenan, M. R., J. A. Timlin, M. H. Van Benthem, and D. M. Haaland., 2002. Algorithms for constrained linear unmixing with application to the hyperspectral analysis of fluorophore mixtures. *Proc. SPIE* 4816:193.

Moya, M. M., W. J. Bow, M. W. Koch, J. S. Salazar, D. M. Haaland, M. R. Keenan, M. H. Van Benthem, and E. V. Thomas. 2002. On Hyperspectral Data Exploitation. Sandia Technical Report SAND2002-3691, Sandia National Laboratories, Albuquerque, New Mexico (November).

Stork, C. L., M. H. Van Benthem, and M. R. Keenan. 2003. A new application for multivariate curve resolution. Paper presented at the Spectral Analyst Exchange Forum (SAEF) #4, October, Albuquerque, New Mexico.

Stork, C. L., M. H. Van Benthem, and M. R. Keenan. 2003. Multivariate Curve Resolution for the Analysis of Remotely Sensed Thermal Infrared Hyperspectral Images. Sandia Technical Report SAND2003-3851, Sandia National Laboratories, Albuquerque, New Mexico.

Van Benthem, M. H., and M. R. Keenan. 2002. Algorithm for fast computation of inequality-constrained least-squares. Technical advance SD-7166, Sandia National Laboratories, Albuquerque, New Mexico (9 April).

Van Benthem, M. H., and M. R. Keenan. 2002. Fast algorithm for the solution of inequality-constrained least-squares problems. Paper presented at Chemometrics in Analytical Chemistry, September.

Van Benthem, M. H., M. R. Keenan, and D. M. Haaland. 2002. Applying quality constraints during alternating least-squares factor analysis. Paper presented at PittCon, 17–21 March, New Orleans, Louisiana.

26578

Deployable Large-Aperture Optics System for Remote-Sensing Applications

J. W. Martin, B. T. Macke, H. Sumali, P. M. Chaplya

Large-aperture optics are critical for improving sensitivity and ground resolution of future space-based telescope systems, such as those needed to monitor global proliferation of weapons of mass destruction (WMD). While many researchers are considering on-orbit assembly of conventional rigid optical mirrors to circumvent geometric limitations imposed by launch vehicles, their approach does nothing to alleviate the tremendous cost penalty associated with the added weight of the overall system. In stark contrast to such incremental technologies, Sandia is developing a revolutionary new enabling technology for large-aperture optics. The key element of this research is an electron-gun-controlled piezoelectric thin-film mirror that can be compactly stowed for launch, deployed on orbit, and shaped to optical tolerances.

An integrated program of computational modeling and experimentation yielded a solid foundation for the demonstration of closed-loop thin-film shape control. The enormous potential of this technology has captured the interest of the remote-sensing community, and further research is needed to develop a fully deployable optical system based on this concept. We are collaborating with the University of Kentucky to develop the technology needed for a deployable electron-gun-controlled imaging system. We will develop suitable deployment concepts independently in collaboration with researchers at the Air Force Research Laboratory (AFRL) division. We will conduct a deployable-system demonstration that could benefit the Department of Energy (DOE), the Department of Defense (DoD), and the National Aeronautics and Space Administration (NASA) applications.

This was an exciting and difficult year for this project. We conducted a parallel path of research for deployable large apertures, the DO project. The DO project worked in conjunction with our project to build a large-aperture (30 in.) telescope system.

The new telescope system demonstrated that a 30 in. thin-film primary-mirror-based telescope could provide an image comparable to a similar-sized glass primary-mirror-based telescope. The purpose of this demonstration was to show the proof-of-concept of using a thin-film material as a primary mirror. Because of irregularities in the material and nonuniform

(a)

(b)

(c)

Shape control of a flexible mirror using an electron gun: (a) desired shape, (b) voltage distribution, (c) achieved shape.

Sandia is developing a revolutionary new enabling technology for large-aperture optics.

shapes (optically) in the thin-film primary mirror, most optical designers thought that an image would not be possible. However, we obtained an image that was comparable to an image obtained using glass as a primary mirror. The glass image had a resolution of approximately 0.78 mm/pixel, while the thin-film image had a resolution of approximately 0.859 mm/pixel. Qualitatively, we are now measuring the mirror's point-spread function to compare to the system using glass as a primary mirror. Techniques and infrastructure improvements are needed to work with an imaging system of this size. These improvements are ongoing.

We examined other options for a lightweight, deployable primary mirror. These options are a preform, a nanolaminate/composite mirror, and the polyvinylidene fluoride (PVDF) thin-film mirrors from past use in this project. Stiffness issues (examined previously) would prevent a nanolaminate mirror from being controlled using the techniques that we developed in this project.

After acquiring a Shack-Hartmann measurement system, we split our focus into two areas: (1) incorporation of the Shack-Hartmann system into our control system, and (2) closed-loop control of a bimorph, which was the original goal. We maintain that one of the biggest hurdles to closed-loop control of deployable large apertures is a measurement system for real-time control. Due to the mathematics of the measurement system, the large matrices of data being manipulated occur on the order of 2 or 3 Hz. This makes real-time control difficult at best. Integration of this system is ongoing. An optical technician is performing the final stages of this work.

We successfully produced four "independent" control areas on a thin-film beam and adjusted the beam to various shapes. Work on producing specific shapes continues. We recently found that part of the difficulty was in "cross-talk" between the electroded control areas and are analyzing this problem. The final integration of the Shack-Hartmann measurement system into our control system will greatly decrease these difficulties. It will also allow for quasi-real-time three-dimensional (3-D) surface control that has been lacking in our previous point-source measurement techniques.

To date, the project has shown both macro- and nanocontrol of thin-film bimorph specimens. We used techniques to prove that closed-loop control is possible, and ongoing improvements are leading to a controlled mirror system. We developed new ideas for building and designing optical systems. These ideas are the basis of a new project at Sandia with the goal of developing ultralarge, lightweight, and cheap optical systems

We successfully produced four "independent" control areas on a thin-film beam and adjusted the beam to various shapes. Work on producing specific shapes continues.

using all of the new tool kits that were developed from this project.

Other Communications

Sumali, H., J. W. Martin, P. M. Chaplya, and J. Redmond. 2003. Shape control of a flexible mirror using an electron gun. *Dynamic Systems and Controls, Proc. 2003 ASME International Mechanical Engineering Congress and Exposition (IMECE 2003)* **41084** (November, Washington, D.C.): 12.

38618

Arrayed Resonant Subwavelength Gratings

S. A. Kemme, C. L. Grotbeck, D. W. Peters, T. R. Carter, S. Samora, M. E. Warren, G. R. Hadley, J. R. Wendt

Sandia seeks a novel optical device that produces a dense two-dimensional (2-D) array of wavelength- and mode-selective reflectors. The resonant subwavelength grating (RSG) acts as a photonic crystal as it reflects any specific spectral, spatial component from a wideband light beam. All of the light is transmitted straight through the device, except for the 100%-reflected narrow-wavelength (0.01–20.0 nm) and angular (~ 1 mrad) band of interest. This new concept of an RSG was first theoretically proposed in 1990 (S. S. Wang, et al., JOSA A, vol. 7, no. 8), but it is only recently that fabrication efforts were undertaken. This unexplored component addresses the anticipated needs of the remote-sensing and data-communications communities, such as the Emerging Technologies Strategic Business Unit's call for miniaturization of synthetic-aperture radar (SAR), and the Nonproliferation and Materials Control Strategic Business Unit's call for small-satellite research. Because this component can perform in both sensing and communications functions, the RSG is an enabling technology for a distributed and interconnected sensor web. Currently, a comparable technology for 2-D arrays does not exist.

As a narrow-band notch filter, the RSG is an optimal multiplexing/demultiplexing component for optical-communication and -sensing applications. Unlike thin films, RSG characteristics may be abruptly altered from one lateral position to the next to realize a 2-D array of wavelength filters or oriented polarizers. Further, RSGs are advantageous for secure wideband communications where free-space, broadcasted information could be spectrally encoded or polarization encoded and covertly detected over narrow angular bands. In the 2-D array configuration, RSGs can be matched to an array of detectors or chemical/biological cells for integrated optical sensing. Applications include narrow-band filter arrays for fluorescence detection or single-chip integrated spectrometer detection arrays.

The arrayed RSG utilizes a remarkable individual component with predicted efficiency of 100%. Incorporating this component into a limited-extent format will result in expected reduced peak efficiency. We theoretically and

The arrayed RSG utilizes a remarkable individual component with predicted efficiency of 100%. Incorporating this component into a limited-extent format will result in expected reduced peak efficiency.

experimentally characterized these issues for an RSG in the near-infrared (NIR)-wavelength regime.

We used frequency-division multiplexing (FDM) Helmholtz equation simulations to model finite-size RSGs. We compared these rigorous numerical calculations to simulations of their infinite-extent counterparts. The spectral response for the case of a finite beamwidth and for a finite grating width shows similar traits in that with decreasing size of the beam or grating, the peak reflectivity shifts to a longer wavelength and decreases in magnitude. Likewise, the peak broadens as the size in either case is decreased. However, the appearance of a secondary peak is limited to the case of the finite beam and may be explained by the inclusion of nonzero angular components in any finite beam. Aperturing an input plane results in an exponential shift in the resonant wavelength as the aperture width decreases. Peak reflectivity suffers a similar exponential decrease as aperture width narrows.

We fabricated and characterized several large-area (diameters > 1.00 mm) RSGs with reflectivities as much as 100.2% relative to deposited bulk gold. Moreover, the sidebands were flat and < 5% across the 300 nm wavelength band. The spectral full-width, half-medium (FWHM) was as low as 4 nm, but was double that for the wafers with varying aperture widths. Decreasing the RSG aperture width while keeping the incident-beam diameter large (1.0 mm) reduced the peak reflectance from 100.2% to 63% to 34% to 12% for aperture widths of 2.00 mm, 0.48 mm, 0.24 mm, and 0.08 mm, respectively.

Measured spectra for nonzero plane-wave incidence angles confirmed theoretical predictions that a system asymmetry introduced a second peak in the reflectance spectrum. This is predicted in infinite-extent RSGs and remains the case when the RSG aperture is of finite extent. The measured wavelength separation between the two peaks is a linear function of incidence angle for the angles between ± 2.0 deg. The second peak emerges at an off-normal incidence angle as low as 0.1 deg. These results for nonzero incidence angles are independent of aperture size and would also be evident in a multiple k -vector converging or diverging incident-beam configuration.

Helmholtz simulations predict that finite gratings have a reduced reflectivity and that this reflectivity is highly dependent on the method with which the grating and/or waveguide is terminated. Reflection from the end facet of a waveguide termination may either enhance or degrade the reflectivity compared to the reflectivity of a structure with a similar finite grating, but with infinite waveguide. Enhancement or

Measured spectra for nonzero plane-wave incidence angles confirmed theoretical predictions that a system asymmetry introduced a second peak in the reflectance spectrum.

degradation is determined by whether the reflection from the end facet is in phase or out of phase with the reflections from the grating feedback. Dependence of the reflectivity is near sinusoidal with the length of the grating. Maximum effect of the end-facet termination is seen in finite-extent devices with reflectivities near 50%, where a 30% variation in reflectivity is evident with small changes in the end-facet dimensions.

RSG simulations and measurements indicate that a large, resonant visible-to-NIR-wavelength range (0.7–1.0 μm) is accessible, given material and fabrication restraints. The available materials in this wavelength regime are low-refractive-index contrast materials, causing the RSG characteristics such as peak wavelength and spectral response shape to be extremely sensitive to imprecision in fabrication and testing. Small changes in deposition thicknesses, refractive indices, grating period, and incident-beam angles shift or reduce the resonance peak dramatically. While this makes fabrication and testing difficult, it speaks to the RSG's utility as a sensing component.

Refereed

Kemme, S. A., D. W. Peters, J. R. Wendt, T. R. Carter, S. Samora, and G. R. Hadley. 2003. Integration and tolerance issues for resonant subwavelength gratings. *Proc. SPIE* (August, San Diego, California).

Kemme, S. A., M. E. Warren, W. C. Sweatt, J. R. Wendt, D. W. Peters, G. R. Hadley, T. R. Carter, S. Samora, D. W. Peterson, and K. M. Geib. 2002. Moving diffractive optical elements from stand-alone components into microoptical systems. *OSA Trends in Optics and Photonics, Diffractive Optics & Micro-Optics* **75** (June, Tucson, Arizona): 109–14.

Peters, D. W., S. A. Kemme, and G. R. Hadley. 2003. FDM Helmholtz modeling of finite-grating and waveguide-width effects on resonant subwavelength grating reflectivity. *Proc. SPIE* (August, San Diego, California).

Peters, D. W., S. A. Kemme, and G. R. Hadley. 2002. Low-sideband resonant subwavelength-grating array design. *OSA Trends in Optics and Photonics, Diffractive Optics & Micro-Optics* **75** (June, Tucson, Arizona): 290–95.

38681

Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies

T. J. Kulp, S. E. Bisson, D. A. V. Kliner, R. P. Bambha

The need to search an area for chemical emissions is shared by several of Sandia's strategic business areas. Buried facilities can be revealed when they release effluents (Emerging Threats and Nonproliferation & Materials Control [NP&MC]).

Similarly, rapid sensing of gas leaks produced in natural-gas transmission is key to protection of critical infrastructures.

We seek technology to fundamentally advance laser remote sensing of chemical plumes in the infrared (IR), where most species absorb at characteristic wavelengths. Range-resolved IR lidar (light detection and ranging), using the atmosphere as a backscattering medium, has been difficult because of poor-quality detectors and low-atmospheric-scattering cross sections.

We will develop and demonstrate a miniature, range-resolved IR lidar. We will develop a novel upconverting detector to shift the frequency of IR signal photons to the visible, where they can be detected with far greater sensitivity. We will enable the laser transmitter and the upconverter by new quasi-phase-matched (QPM) nonlinear materials, which exhibit much higher nonlinearity than standard materials, and by high-power fiber amplifiers. The upconverter can also serve as a high-sensitivity detector for space applications for NP&MC. Moreover, the fiber amplifier and QPM-material development will contribute significantly to electronics and photonics initiatives.

We performed upconversion measurements supporting the theoretical predictions made previously. We made them using an IR helium-neon laser emitting at 3.39 μm wavelength that was mixed up to 809.9 nm in a 1.1 cm-long periodically poled lithium niobate (PPLN) crystal poled with periods ranging between 20.4 and 21.8 μm . They show agreement with theoretical modeling (performed by Sandia's nonlinear optics group) to within a factor of 2.1. This, combined with our past demonstration of resonant-cavity enhancement, ensures our success in achieving the desired performance for the range-resolved IR lidar.

We have assembled the final cavity for the resonantly enhanced upconverter. It is a bowtie-ring design that contains four reflective optics resonating the 1064 nm pump wave and

...the fiber amplifier and QPM-material development will contribute significantly to electronics and photonics initiatives.

transmitting the relevant signal and upconverted waves. The cavity is locked using the Pound-Drever-Hall method, in which the input wave is modulated at a frequency corresponding to the mode spacing of the cavity, and a frequency modulation indicating degree of coupling into the cavity is used as an error signal. We characterized the quality of injection of the pump into the cavity, and locking of the cavity to the pump is in process. Following this, we will confirm the upconversion efficiency of the resonantly enhanced system.

We purchased a Gage 100 MHz 12-bit analog/digital card to accomplish digitization of the lidar signal at a range resolution of 5 ft. The Gage card is installed in a personal computer (PC) that operates a LabView data-collection program.

We modeled the optical path of the receiver to design the receiver optics and the link to the upconverting detector. The receiver for the upconverting differential absorption lidar system must accept backscattered radiation from the atmosphere and properly format it into the upconverter crystal/cavity. Optimal focusing into the PPLN dictates formation of a relatively undistorted Gaussian beam waist with a confocal parameter having a length that is about one-fourth that (50 mm) of the crystal. The waist necessary has a ω_0 of 120 μm and a high f -number (55). We thus found that formatting this return beam into the crystal requires an optical system with an effective focal length of approximately 3 m. The appropriate receiver optic is designed and is now in procurement. The California site-matching funds also supported the development of in-house capability to fabricate QPM materials.

We completed the following tasks:

- Developed a procedure to obtain photolithographic masks appropriate for printing poling patterns,
- Developed and successfully demonstrated a procedure to print mask patterns on three lithium niobate wafers in Sandia's Chemical and Radiation Detection Laboratory clean-room facility,
- Fabricated a cell that houses the lithium niobate wafer and provides contact to liquid electrolytes,
- Assembled electronic circuitry for poling consisting of a PC-based waveform generator, high-voltage amplifier, voltage dividing and safety circuitry, and the software necessary to control the poling process, and
- Poled the first lithium niobate wafers.

We focused the fiber-laser development aspects of this project on bringing the capability to manufacture fiber amplifiers in-house and on constructing fiber sources for the IR transmitter, the upconverter, and other projects. We developed a

They [upconversion measurements] show agreement with theoretical modeling (performed by Sandia's nonlinear optics group) to within a factor of 2.1. This, combined with our past demonstration of resonant-cavity enhancement, ensures our success in achieving the desired performance for the range-resolved IR lidar.

new method for efficient side-pumping of fiber amplifiers and are equipping the new fiber laboratory to implement this method routinely. We constructed a fully packaged, polarization-maintaining, ytterbium-doped fiber amplifier for use in a broadly tunable IR source for greenhouse-gas detection. We are incorporating this laser into a prototype instrument. We also demonstrated efficient generation of the second, third, fourth, and fifth harmonics of a pulsed fiber amplifier (to provide light from the near-IR through the deep-ultraviolet). We continued our collaboration with the Naval Research Laboratory.

We developed a new method for efficient side-pumping of fiber amplifiers and are equipping the new fiber laboratory to implement this method routinely.

Refereed

Kliner, D. A. V., F. Di Teodoro, J. P. Koplow, S. W. Moore, and A. V. Smith. 2003. Efficient second, third, fourth, and fifth harmonic generation of a Yb-doped fiber amplifier. *Optics Commun.* **210**:393.

Kliner, D. A. V., F. Di Teodoro, J. P. Koplow, S. W. Moore, and A. V. Smith. 2002. Efficient UV and visible generation using a pulsed Yb-doped fiber amplifier. *Conference on Lasers and Electro-Optics, OSA Technical Digest* (Long Beach, California): CPDC10-1.

Kliner, D. A. V., F. Di Teodoro, J. P. Koplow, S. W. Moore, and A. V. Smith. 2003. Efficient visible and UV generation by frequency conversion of a mode-filtered fiber amplifier. *Proc. SPIE, Advances in Fiber Lasers* **4974** (27–28 January, San Jose, California): 230–35.

Koplow, J. P., S. W. Moore, and D. A. V. Kliner. 2003. A new method for side-pumping of double-clad fiber sources. *J. Quantum Electron.* **39**:529.

Kulp, T. J., S. E. Bisson, R. P. Bambha, T. A. Reichardt, U. B. Goers, K. W. Antolek, D. A. V. Kliner, B. A. Richman, K. M. Armstrong, R. Sommers, R. Schmitt, P. E. Powers, O. Levi, T. Pinguet, M. Fejer, J. P. Koplow, L. Goldberg, and T. G. McRae. 2003. The application of quasi-phase-matched parametric light sources to practical infrared chemical-sensing systems. *Applied Physics* **B** 75:317–27.

38695

Passive-Legged, Multisegmented, Robotic Vehicle

D. R. Hayward, M. C. Reineke, P. R. Klarer

Mobility of sensor packages and access to traditionally denied areas for the purpose of intelligence gathering present challenges that we are beginning to address. The desired destinations can be impeded by both natural and manmade obstacles. Traditional efforts have stressed autonomous behavior development based on processing sensor information and path planning rather than on using simple processing and extreme terrain agility. Sandia proposes to develop a robotic vehicle that is very terrain agile and that is small enough to gain access to normally denied areas by passing through small openings.

This concept for a terrain-agile robotic platform is a simple legged vehicle that is modular and scalable, but that will initially be sized to fit through the fabric openings of a chain-link fence. The vehicle will comprise multiple segments, each of which has fixed appendages (legs) that resemble oars extending from a boat. Motion is achieved by pushing with these legs, which can flex to fold next to the body when passing through a constricted area. Each segment is attached to another segment using a two-axis-of-motion actuated joint. The joint can be moved vertically or horizontally. In flat terrain, horizontal joint actuation will provide the forward force. The minimum number of segments is two, but greater mobility benefits will be realized by using three or more segments. Each joint will be controlled by a microprocessor with driver circuits. Power and data will be bussed to all the segments to allow synchronization of joint motions. The major effort of the project will be the mechanical design of the joints and the development of the control architecture and algorithms to provide synchronized motion for forward motion and climbing. A further goal is to include obstacle detection in the lead segment to determine when vertical actuation is needed to “step” over an obstacle.

We developed concepts to accomplish mobility via simple actuation and legs that were not actuated. We based the first two concepts explored on a rotational actuation of the joint between the body modules. The single-axis concept restricted the joint motion to a single axis and was shown in dynamic simulations to produce forward motion when the module joints were sequenced in the proper manner. A second concept used the unrestricted actuation of the same joint to produce motion of the

Dynamic simulation of single-axis concept.

Sandia proposes to develop a robotic vehicle that is very terrain agile and that is small enough to gain access to normally denied areas by passing through small openings....The major effort of the project will be the mechanical design of the joints and the development of the control architecture and algorithms to provide synchronized motion for forward motion and climbing.

forward-body module that described a cone. Analysis of this type actuation did not determine a motion sequence for efficient forward motion. We did not pursue these versions to demonstration because of recognized problems with weight, complexity, and lack of payload volume. These concepts also depended strongly on the leg and foot design.

We developed other concepts to address the design concerns of the single axis and the conical concepts. The push/pull concepts used axial actuation instead of rotation actuation that moved the forward-body module either back and forth, or conically. These concepts showed promise for producing simple mobility that did not depend heavily on leg and foot design, and addressed the payload, weight, and complexity issues of the previous concepts. We designed several versions and built some. We successfully demonstrated forward motion for the push/pull concept.

As the project ended, we did not completely build and test the last concept for the push/pull type. Therefore, while we can make no confirmed conclusions about its performance, we expect its design to produce the longest stroke (about 2 in.) of the concepts that have been conceived, and therefore it should be very effective at producing mobility. As with most designs, we expect that design iterations would be required to arrive at a mission-ready design.

The final push/pull concept that we built and initially tested near the end of the project produced a stroke of about 0.8 in. and obtained steering and mobility with the same actuators. This version required the use of four actuators. Moving one side's actuators to a shorter extension would produce steering in that direction. It produced forward mobility, but improvement in design detail is needed. The initial control electronics included only two motor *h*-bridges, for evaluating only the mobility characteristics of the concept. The actuators exhibited different internal friction and therefore different actuation rates. Since they were driven in pairs, one would reach full extension (or retraction) and trip a limit switch before the other could reach full extension or retraction. This caused a bias in the direction of travel (unintentional steering) and finally resulted in a very short stroke as the pair became further separated in stroke. In retrospect, it would have been better to take the time to address the steering issue at the same time as the forward-mobility issue and include the additional *h*-bridges.

The push/pull concept does produce mobility. Dependence on equal friction for mobility has issues that need to be addressed. Leg and foot concepts must be developed, and

ganging more than three units together and coordinating their movement should be explored to enhance functionality.

Although we did not demonstrate the goal of crawling through a chain-link fence, we believe that the goal was close and could be attained with minor refinements of this concept.

38696

Low-Cost Photonic Lattice Structures for Remote Sensing

W. C. Sweatt, S. Y. Lin, G. R. Hadley, M. B. Sinclair, T. J. Drummond, D. W. Peters, T. R. Christenson, M. B. Ritchey

Sandia has made significant progress toward the design of photonic bandgap (PBG) materials for the infrared (IR) to be manufactured using deep x-ray lithography (DXRL) techniques. The structures designed could, for example, be non-emitting in the thermal IR band with wavelengths from 8 mm to 15 mm. This type of coating could be used for controlling the temperature of spacecraft, modifying its visibility, etc.

The DXRL process has one significant advantage over other methods of manufacturing PBG materials—areas as large as 6 in. x 22 in. can be made in a single exposure. However, it is difficult to fabricate features small enough for photonic lattices that operate in the 8 mm to 15 mm band. Our efforts in this research project focused on (1) finding PBG designs that require larger features for operation in the thermal IR, (2) devising methods of making masks (for the printing) that allow relatively small features to be printed at angles other than normal, and (3) fabricating these structures.

The structure called “Yablonovite” was the first PBG material designed and fabricated for microwave wavelengths. Difficulties encountered while trying to fabricate this material for mid-infrared (MIR) wavelengths (using DXRL) led us to a number of innovations. First, we developed an advanced mask-fabrication scheme for creating tilted structures with small cross section. Second, we developed a new plating base using “very low Z” materials. This plating base emits only a small amount of secondary electrons when exposed to x-rays. Third, we found two new PBG designs that are far more amenable to DXRL manufacture than is Yablonovite. One is what we call the “tilted log pile.” It dawned on us that if the Iowa State log pile were tilted up about a diagonal, it could be fabricated with DXRL. Sadly, just after the technical advance was written, the idea was published by someone else. The other PBG architecture found is the cubic array of cubes.

Another idea crossed our path during the course of this project. A “moth-eye” structure on the surface of a refractive element can minimize reflections from near-normal to grazing incidence (where standard antireflective [AR] coatings fail). We studied PBG moth-eye structures and showed that they work better than moth-eye structures near grazing incidence. Finally,

Sandia has made significant progress toward the design of photonic bandgap (PBG) materials for the infrared (IR) to be manufactured using deep x-ray lithography (DXRL) techniques....The DXRL process has one significant advantage over other methods of manufacturing PBG materials—areas as large as 6 in. x 22 in. can be made in a single exposure.

we developed the capability to model PBG structures at Sandia. Thus, classified or sensitive designs can be modeled easily.

Refereed

Sweatt, W. C., T. R. Christenson, and S. Y. Lin.
2002. Low-cost, large-area fabrication of
yablonovite in the infrared. *PECS IV (IEEE)* **1** (21
October, Los Angeles, California).

38698

Security Monitoring and Management with Information Technology (SUMMIT)

L. A. Cano, S. M. Deland, A. P. Heath, Jr., G. N. Conrad

This project was initially set up to develop tools that would identify potential insider threats. Insiders pose the greatest threat to an organization because they know where sensitive information resides and how this information is protected.

Using simulation tools to model facility activities, Sandia developed and/or adapted various analytical tools that identified patterns of behaviors for individuals. Individuals interact with various networks—other people, particular facilities, and services, e.g., access to sensitive information, computer network access, and phone network access—to do their jobs. By studying these interactions, we can identify signatures and/or patterns of behavior. These signatures can be studied over time to check for significant and/or anomalous changes in behavior. Looking at a broad range of behaviors and interactions increases the chances of identifying anomalous changes in someone's signatures.

We can easily adapt knowledge-generation and data-mining tools to identify and validate individual signatures, as well as track any changes to them. As an individual's behavior evolves, system checks can be conducted to ensure that these are allowed changes. Suspicious behaviors such as unauthorized access to sensitive information can be captured and evaluated quickly to minimize the threat of potential insider activity.

The SUMMIT project identified a suite of tools that we can use to analyze data and identify potential insider threats. These are first-generation tools. We anticipate that as these tools get better, we will be able to provide better situational awareness to security providers.

The SUMMIT project leveraged Sandia-generated products, e.g., the Knowledge-Generation tool, along with commercially available data-mining products (Clementine by SPSS) to develop insider-threat analysis tools.

We used these insider-threat analysis tools on real and simulated data to develop behavioral signatures for individuals. We broadly defined networks to include people interactions, computer network interactions, phone network interactions, and access to sensitive information.

We identified various domains where individuals interact and correlate their behaviors across these domains to develop individual signatures. We defined anomalous behavior as

Using simulation tools to model facility activities, Sandia developed and/or adapted various analytical tools that identified patterns of behaviors for individuals....The SUMMIT project identified a suite of tools that we can use to analyze data and identify potential insider threats. These are first-generation tools.

significant deviations from these signatures that should trigger further investigation. SUMMIT tools are already in use in real-world applications.

We accomplished the following:

- Use of arena simulation tool from Rockwell Software to model a facility.
- Use of Knowledge-Generation tool to extract information from real and simulated data sources.
- Use of Clementine SPSS data-mining tool to analyze and organize raw data.
- Adaptation of network theory to better understand how to categorize various interactions between an individual and his environment.

38699

Novel Methods for Ultracompact, Ultralow-Power Communications

R. C. Ormesher, J. J. Mason, P. A. Dudley, T. D. Atwood, V. Guzman-Kammler

Sandia developed a new algorithm, based on Turbo decoding, for the joint estimation of coded data, carrier phase, and symbol timing. The new algorithm achieves processing gains of 4 to 5 dB when compared to conventional methods, such as serial demodulation and decoding. The joint estimator allows the delay and phase-locked loops (PLLs) to work at lower bit energies where Turbo codes are most useful. We analyze comparative performance results for constraint lengths of 3, 5, and 7, for rate 1/2 and 1/3 codes of block lengths of 1000 bits. The algorithm is computationally more difficult than the sequential estimation problem. Therefore, we are developing a fast hardware implementation of the algorithm using a field-programmable gate array (FPGA).

We completed the following tasks:

- We reviewed the requirements for several systems, including the Global Personnel Recovery System (GPRS). Several key requirements make implementing a Turbo encoder, at low signal-to-noise ratios, very difficult. These include the clock stability and velocity requirements of the mobile transmitter.
- We performed a literature search and believe that we are current on the latest technology for Turbo decoding and encoding. To date, we have not found an approach that meets our specific requirement for a low-probability-of-intercept system with requirements similar to those specified by GPRS and similar systems.
- We proposed a new approach that we believe would solve our problem. The approach is built on two new algorithms that require both Viterbi and Turbo decoding. Our interest is in the Turbo decoding, but the building block for this is the newly developed Integrated Viterbi Algorithm. As originally proposed, the new decoding algorithm incorporates the phase- and time-delay estimators within the encoder.
- We studied several papers that describe how to implement Turbo decoders on programmable gate arrays. We used these as a starting point for implementing the new algorithm on hardware.
- We implemented part of the new algorithm in MATLAB and in C. The part that we implemented contains the delay

Sandia developed a new algorithm, based on Turbo decoding, for the joint estimation of coded data, carrier phase, and symbol timing. The new algorithm achieves processing gains of 4 to 5 dB when compared to conventional methods, such as serial demodulation and decoding.

estimator integrated into the Turbo decoder. We performed Monte Carlo simulations to verify the algorithm implementation.

- We completed the development and implementation of two algorithms: the Integrated Viterbi Algorithm and the Integrated Turbo Algorithm (ITA).

- We implemented ITA in C and conducted Monte Carlo simulations to evaluate performance in terms of bit-error rate (BER) at various levels of E_b/N_0 (bit energy-to-noise power-density ratio).

- We investigated the performance using the following parameters: a message block length of 1000 bits, an encoder constraint length of five, and a rate 1/3 unpunctured Turbo code. We used many secondary parameters, such as time and phase oscillator drift rates, loop bandwidths, and spreading code and interleaver sequences, to fully specify the simulation. Using this parameter set, we showed that the algorithm achieved a BER of 1×10^{-5} at an E_b/N_0 of less than 2 dB, yielding a power savings of at least 4–5 dB over existing methods.

- We completed a high-level hardware design of the new ITA for an FPGA. Based on the high-level design, we created a spreadsheet that allows us to perform trade-off studies using key system parameters, such as data rates, message length, and spreading codes. We completed a significant portion of the detailed FPGA design.

- We compared the performance of the ITA to standard processing over an industrial, scientific, and medical (ISM)-band radio-frequency (RF) link using equipment assembled by the Goldmine project. This link consists of an S-band transmitter, a C-band to S-band translator (or “bent-pipe”), and a C-band receiver. The transmitter and receiver were located on Sandia property on Kirtland Air Force Base, while the bent-pipe was put on free-flying, high-altitude balloons. Results showed that the new algorithm performed similarly to simulated results.

For this research effort we were able to develop a novel algorithm that achieved significant improvements when compared to existing techniques. Through simulation, we demonstrated that the new algorithm achieves processing gains of 4 to 5 dB when compared to conventional methods. We made significant progress in developing an FPGA to implement the new algorithm. Finally, we demonstrated that the new algorithm performs, as expected, over an RF link using an RF transponder on a free-flying balloon.

For this research effort we were able to develop a novel algorithm that achieved significant improvements when compared to existing techniques. Through simulation, we demonstrated that the new algorithm achieves processing gains of 4 to 5 dB when compared to conventional methods. We made significant progress in developing an FPGA to implement the new algorithm.

38701

Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items

M. C. Wanke, F. T. Mendenhall, S. M. Brozik, M. M. Manginell, S. A. Kemme, M. E. Warren, D. W. Peters, P. Esherick, E. L. Patrick, W. T. Sommerville, M. L. Phillips, A. Santos, T. Carter

The purpose of this project was to identify and investigate technologies that could be applied to produce covert, passive, and unique tags for potential use in a wide variety of applications. Sandia investigated two technology areas: optical tags and biological tags.

Within the area of optical technologies, we investigated three different approaches:

- The use of retroreflecting, half-metallized dielectric microspheres (beads) that produce a reflected signal within a narrow angle when illuminated with an on-axis infrared (IR) light source. A reflecting tape that utilizes these beads is commercially available, but the tape format is not sufficiently covert for the applications of interest here.*
- The use of coatings containing specifically oriented carbon nanotubes (CNTs), which potentially could give polarization-dependent reflected signals when illuminated with an appropriate light source.*
- The development and application of coatings (“paints”) containing upconversion phosphors, which produce no visible signal when illuminated with visible light, but which do produce a visible signal when illuminated with IR light of the appropriate wavelength. The color of each coating should, if possible, be designed to match the background color of the object to be tagged.*

In the area of biological tags, work focused on the specific application of tagging classified documents. Our approach was to attempt to print a unique deoxyribonucleic acid (DNA) sequence—the tag—onto a piece of paper among 20 or more other equally unique DNA sequences. Taking advantage of the highly specific interaction between a particular strand of DNA and its complement, it should then be possible to detect such a tag via fluorescence by reacting the tag DNA sequence with a labeled complement strand. We performed detailed experiments to determine combinations of paper types and chemical treatments that allow attaching DNA to paper in sufficient quantities for this reaction to be observed.

The purpose of this project was to identify and investigate technologies that could be applied to produce covert, passive, and unique tags for potential use in a wide variety of applications. Sandia investigated two technology areas: optical tags and biological tags.

We investigated several potential optical and biological tagging technologies. The principal results and conclusions include the following.

We successfully demonstrated the use of retroreflecting, half-metallized microspheres as a tag that can be probed and detected using IR light. Such microspheres can be dispersed over sand such that they are not very evident under room-light illumination, and the dispersal pattern can be detected easily by a retroreflected signal when the microspheres are appropriately illuminated. This passive optical tag is made more covert by illumination with a nonvisible light source. To this end, we quantified the utility of the metallized microspheres with an on-axis, near-infrared (NIR) 930 nm light-emitting diode (LED). Furthermore, we demonstrated that the retroreflected signal essentially disappears when “footprints” are made in the areas of sand originally covered with the microspheres. This suggests possible time-stamp applications such as monitoring drug trafficking across borders. The metallized microspheres are inexpensive and easily applied. Consequently, they can function as passive, remotely probed optical tags. However, they direct a relatively low-contrast, source-dependent signal back to the observer. The wavelength response of the microspheres could be made more specific, i.e., moved into a nonvisible regime, by fabricating the microspheres using material that is absorptive in the visible region of the spectrum. This possible solution might merit further investigation.

The limited experiments performed with CNT coatings were not successful. We observed no polarization dependence of reflected light signals from these materials with four different nanotube-based materials that we obtained from commercial sources. This might be due at least in part to imperfect alignment of the nanotubes.

We successfully demonstrated the development of “paints” containing upconversion phosphors, with both a clear paint and a white paint having been produced. These coatings are invisible (or nearly so) under room-light illumination, but show a strong visible reflected signal when probed with a 980 nm IR laser. Useful features of this technology with respect to tagging include the fact that there is visible signal only for an IR probe in a very narrow frequency range, the demonstrated capability of altering the color of the coating to match the color of the item to be tagged, and the fact that these coatings appear to be fairly robust. Since this effort was begun late in the second year of the project, further experiments to optimize these coatings would be very useful.

We successfully demonstrated the development of “paints” containing upconversion phosphors, with both a clear paint and a white paint having been produced. These coatings are invisible (or nearly so) under room-light illumination, but show a strong visible reflected signal when probed with a 980 nm IR laser.

The biological tagging studies demonstrated the use of DNA as a unique, covert, and passive tag for authenticating a specific document. Using a polymerase chain reaction (PCR) approach, we showed that one specific DNA sequence (the tag) could be identified on paper among 21 other unique sequences. We accomplished this by developing a chemical method to deionize paper, since the ions initially present on the paper interfere with the PCR reactants. In the use of hybridization as a detection/verification scheme, the hybridization time used for standard gene array technologies was reduced significantly, from > 12 hrs to only 1–2 hrs. This has already had a substantial impact in the genomic community. We determined a method for creating reactive sites on paper necessary for covalent attachment chemistries used in three-dimension printing, and we attached streptavidin-coated beads with bound DNA to paper successfully, producing readily available DNA binding sites for hybridization and subsequent detection. Finally, these efforts led to a visual demonstration of this technology. In this demonstration, the hybridization reaction was detected on paper following reaction of a labeled complementary DNA sequence with the tag sequence. Using laser goggles, we can observe the associated fluorescence when the tagged spot on the paper is illuminated with a green laser pointer.

The biological tagging studies demonstrated the use of DNA as a unique, covert, and passive tag for authenticating a specific document....This has already had a substantial impact in the genomic community.

Other Communications

Peters, D. W., S. A. Kemme, M. C. Wanke, T. Carter, S. M. Brozik, M. M. Manginell, E. L. Patrick, A. Santos, P. Esherick, M. L. Phillips, W. T. Sommerville, and J. E. Parmeter. 2003. Investigations of Novel Optical and Biological Tagging Technologies. Sandia Technical Report SAND2003-3852, Sandia National Laboratories, Albuquerque, New Mexico.

38702

A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell

T. L. Aselage, G. Nagasubramanian, D. T. Berry, P. H. Helmick, D. P. Adams, C. M. Matzke, M. A. Rodriguez, G. L. Zender, J. R. Michael, M. P. Siegal

Radioisotope fuels are considered for use in long-life power sources because of their enormous capacity or stored energy, more than 1000 times greater than that of gasoline. Many different schemes have been proposed for converting the energy of radioisotope decay products into electricity.

Beta cells are solid-state devices that directly convert energy of beta particles into electricity. Analogous to solar cells, beta cells are semiconductor junction devices whose internal field separates and collects electronic charge carriers generated by the passage of a beta particle.

The idea of a beta cell is an old one, dating at least to the 1950s. Early tests showed that energetic beta particles, such as those emitted by strontium-90, damage and degrade the output of devices based on conventional semiconductors such as silicon (Si). As a result, beta cells that are based on conventional semiconductors are restricted to the use of only low-energy beta emitters such as tritium or nickel-63. The power output of beta cells from such weak beta emitters is very low.

Prior research at Sandia, under the auspices of the Department of Energy (DOE) Basic Energy Sciences program, identified a novel class of semiconductors, icosahedral borides, in which radiation damage appeared to spontaneously “self-heal.” One outcome of this discovery was a project to explore whether icosahedral boride semiconductors (IBSs) could serve as the basis for beta cells that would employ more energetic beta sources.

A Defense Advanced Research Projects Agency (DARPA)–sponsored project established the feasibility of icosahedral boride beta cells. In particular, (1) it confirmed the “self-healing” of radiation damage under intense electron bombardment, (2) it grew films of semiconducting icosahedral boron arsenide ($B_{12}As_2$), and (3) electron-beam bombardment of a simple junction fashioned from one of these films produced an open-circuit electromotive force.

This project explored, through improved film growth and characterization, through studies of doping strategies, and through testing and modeling of simple devices, whether

Prior research at Sandia...identified a novel class of semiconductors, icosahedral borides, in which radiation damage appeared to spontaneously “self-heal.” One outcome of this discovery was a project to explore whether icosahedral boride semiconductors (IBSs) could serve as the basis for beta cells that would employ more energetic beta sources.

icosahedral boride beta cells represent a technology that would be of benefit for Sandia applications.

Growth of crystalline films of IBSs requires unconventionally high temperatures. Researchers at Kansas State University (KSU) collaborated on this project to grow icosahedral borides using high-temperature ($> 1200^{\circ}\text{C}$) chemical vapor deposition (CVD). Funding for KSU was provided under a separate DOE/EPSCoR (Experimental Program to Stimulate Competitive Research) grant.

We chose silicon carbide (SiC) as a substrate material for CVD of icosahedral borides by growers associated with the prior DARPA program. The selection of SiC was based on the perceived advantages of its nearly 1:2 basal-plane lattice match with B_{12}As_2 and its perceived high-temperature stability. KSU researchers continued the use of SiC as the substrate of choice.

Films of B_{12}As_2 are now routinely grown on (0001) SiC with near-perfect c -axis alignment of the B_{12}As_2 film with the substrate. Several-micron-thick films can be grown in under an hour. Both accomplishments are substantial improvements in the growth of B_{12}As_2 on SiC.

Our characterization of these B_{12}As_2 films uncovered several problems inherent to growth on SiC. First, two different rotational variants are found in the B_{12}As_2 films. These domains have identical c -axis orientations, but differ by a rotation of 60° about the c -axis. Second, four different translational variants can arise from the 1:2 ratio of the lattice constant of the substrate and the film. Although indistinguishable from one another by diffraction techniques, high densities of translational domain boundaries are observed with cross-sectional transmission-electron microscopy (TEM). Finally, energy-filtered TEM shows an interfacial reaction layer, most likely of a boron carbide, at the interface between the SiC substrate and the B_{12}As_2 film.

Films grown on SiC thus have inherent defects. A substrate with higher conductivity than SiC would also be wanted in a beta-cell configuration. We devoted little effort to growth on alternate substrates.

We studied a number of refractory metals and metalloids (diborides, silicides, carbides) as potential electrical contacts that would survive high-temperature CVD growth. Most films did not survive high-temperature contact with SiC. Tantalum carbide (TaC) emerged as the most stable material, and we grew several B_{12}As_2 films on TaC films.

Early ideas to dope B_{12}As_2 n -type suggested substituting selenium (Se) for arsenic (As) within the structure (analogous

Films of B_{12}As_2 are now routinely grown on (0001) SiC with near-perfect c -axis alignment of the B_{12}As_2 film with the substrate. Several-micron-thick films can be grown in under an hour. Both accomplishments are substantial improvements in the growth of B_{12}As_2 on SiC.

to doping Si *n*-type by phosphorus substitution). However, a simple theoretical investigation of Se substitution's effect on the complicated bonding of icosahedral borides showed this strategy unlikely to succeed. Films grown by CVD with Se present in the vapor remain *p*-type.

We fabricated simple device structures consisting of a nickel ohmic contact on the backside of a SiC substrate and a metal contact, usually gold (Au), on the front side of the $B_{12}As_2$ film. We tested these devices under electron bombardment in a scanning-electron microscope and produced open-circuit potentials similar to those of the DARPA project.

Unlike the DARPA films, however, the new KSU films were sufficiently thick to allow the experimenters to tune the electron-beam energy to probe the several interfaces in the device: Au/ $B_{12}As_2$ (a gold–boron arsenide interface) and $B_{12}As_2$ /SiC (a boron arsenide–silicon carbide interface). These experiments, coupled with Monte Carlo simulations of electron-beam penetration as a function of beam energy, proved that the electrical response was generated at the $B_{12}As_2$ /SiC junction.

SiC thus plays an active role in the junction. SiC, however, is known to suffer from radiation damage. Additionally, the series resistance of these devices was quite high, 10,000 ohms or greater. Both factors would limit the utility and lifetime of a beta cell based on a SiC/ $B_{12}As_2$ junction.

Finally, we evaluated all solid-state thin-film lithium cells comprising LiPON (lithium phosphorous, oxynitride) as separator and electrolyte film, lithium anode, and $LiCoO_2$ (lithium cobalt oxide) cathode as potential charge-storage devices for beta-cell output. The cells have very good capacity and rate capability at room temperature. Capacity diminishes with decreasing temperature, with little capacity remaining at - 50°C. Capacity was not diminished at temperatures as high as 80° C, but the cell's resistance increased at high temperatures.

Refereed

Lu, P., J. H. Edgar, and T. L. Aselage. 2003. Growth of icosahedral $B_{12}P_2$ thin films on 6H-SiC(0001) by chemical vapor deposition. Paper presented at the Materials Research Society Fall Meeting, December, Boston, Massachusetts.

Nagarajan, R., J. H. Edgar, J. Pomeroy, M. Kuball, and T. L. Aselage. 2003. Investigation of thin-film growth of $B_{12}As_2$ by chemical vapor deposition. *New Applications for Wide-Bandgap Semiconductors, Proc. MRS Spring Meeting* **764**, ed. J. Pearton, J. Han, A. G. Baca, J. I. Chyi, and W. H. Chang (21–25 April, San Francisco, California): C3.58.

Nagasubramanian, G., and D. H. Doughty. 2003. Electrical characterization of all-solid-state thin-film batteries. *J. Power Sources, Proc. 23rd International Power Sources Symposium* (22–24 September, Amsterdam, Netherlands).

38703

Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets

M. M. Moya, C. L. Walker, J. L. Smith, A. R. Lappin, B. K. Ford

Characterizing the geology, geotechnical aspects, and rock properties of deep underground facility (UGF) sites can enhance targeting strategies for both nuclear and conventional weapons. Sandia investigated the utility of remote spectral sensing for augmenting the geological and geotechnical information provided by traditional methods. The project primarily considered methods based on data collected from space-based sensors, which allow clandestine collection of data from denied sites. The bulk of the investigation focused on developing and applying novel data-analysis methods to estimate geologic and geotechnical characteristics in the vicinity of deep UGFs. We explored in detail two such methods, one for measuring thermal rock properties and one for classifying rock types. We also examined several other data-exploitation techniques, developed under other projects, for their potential utility in geologic characterization.

Characterizing the geology, geotechnical characteristics, and rock properties of deep UGF sites can enhance targeting strategy for both nuclear and conventional weapons. The purpose of this study was to investigate the utility of remote spectral sensing for augmenting the geological and geotechnical information provided by traditional methods. The study primarily considered methods based on data collected from space-based sensors. The first step in the investigation was to identify geologic and geotechnical data that are not generally available from other sources. This exercise resulted in identification of specific data needs, such as the following:

- Specific rock types,
- Contacts between bedrock/parent material and unconsolidated or younger materials,
- Locations of significant secondary phases within geologically young materials,
- Location of lithologic and structural contacts,
- Slope angles for drainage and ridgeline analyses, and
- Physical characteristics of the rock mass, such as fracture spacing and porosity.

To develop and assess new data-exploitation methods for geological characterization in denied areas, we principally considered a selection of the available space-based spectral sensor systems as being representative of currently available

Data segmentation into clusters: Each cluster contains one parent mode, associated minor modes, and all seed points that track to those modes. Seed points represent the cluster.

data-gathering systems. The systems considered included the following:

- LANDSAT thematic mapper,
- MTI,
- Advanced spaceborne thermal emission and reflection radiometer (ASTER), and
- HYPERION.

After reviewing the many geologic information needs, we identified two areas on which to focus our development efforts. In addition, we investigated various methods developed under other projects at Sandia that have the potential to enhance interpretation of remotely sensed data to aid a geologist's characterization of a remote site.

The first principal area of study was to demonstrate the feasibility of estimating rock-mass thermal property data from a single image. The proposed method calculates temperature differences near sun/shade boundaries to estimate the key thermal parameters of the surrounding rock. We also conducted field measurements to evaluate the concept of extracting information from sunshade temperature differences. The results of the analytical and experimental study demonstrated the feasibility of the concept, but do not provide a complete solution. Many complicating factors have yet to be dealt with in a comprehensive way.

The second principal area of investigation involved the use of multispectral data, which capture broadband spectral features and general spectral shape, to discriminate general categories of rock type. For our effort, we identified seven general categories of rock type and selected representative laboratory spectrometer spectra from the ASTER hyperspectral database. We filtered the laboratory data to emulate MTI spectra and investigated the spectral separability of the classes using separability metrics. The conclusion drawn from this effort is that rock types can be mathematically separated based on their multispectral signatures, even in the presence of adverse factors such as vegetation, water, and other minerals.

Finally, we examined several other techniques for potential application to geological investigations.

- *Spatial and spectral derivative filtering.* This technique enhances specific features of interest.
- *Supersampling.* This method employs microscanning, resulting in a fourfold increase in resolution.
- *Robust spectral segmentation.* The algorithm segments the scene based on spectra that have the same general shape characteristics, thus allowing a rough identification of the location of different rock types in the scene.

- *Synthetic-aperture radar (SAR)*. Interferometric SAR data can be used to construct high-resolution digital elevation models.

This study demonstrated the feasibility of measuring thermal rock properties from single MTI images and the feasibility of broadly classifying rock types using multispectral image data. Although these methods are not ready for direct application and while additional technical problems must be overcome to reach this goal, this study does recommend continued development of both efforts.

Other Communications

Costin, L. S., M. M. Moya, A. R. Lappin, C. L. Walker, B. K. Ford, and J. Stormont. 2003. Remote-sensing data exploitation for geologic characterization. Paper presented at the Interagency Geologic Assessment Team Meeting, 6 February, Washington, D.C.

This study demonstrated the feasibility of measuring thermal rock properties from single MTI images and the feasibility of broadly classifying rock types using multispectral image data.

38706

Detecting and Tracking the Active Insider Using 3-D Detection Technology

C. L. Nelson, C. Q. Little

Vulnerability analysis studies show that one of the worst threats against a facility is that of an active insider during an emergency evacuation. When a criticality or other emergency alarm occurs, employees immediately go along evacuation routes to designated areas. Procedures are then implemented to account for all material, classified parts, etc. There currently is no method to detect or track an insider during this situation in which items could be removed and either hidden for later retrieval or thrown over the fence. The 3-Dimensional Video Motion Detection (3DVMD) technology could be used to detect and track possible insider activities during alarm situations, as just described, as well as during normal operating conditions. 3DVMD technology uses multiple cameras to create 3-D detection volumes or zones. It tracks movement throughout detection zones and extracts high-level information, such as the number of people and their direction of motion. In the described alarm scenario, deviances of evacuation procedures taken by an individual could be immediately detected and relayed to a central alarm station. The insider could be tracked, and any protected items removed from the area could be flagged. 3DVMD could also be used to monitor items such as machines that are used to build classified parts. During an alarm, detection could be made if items were removed from the machine. Overall, the use of 3DVMD technology during emergency evacuations would help to prevent the loss of classified items and would speed recovery from emergency situations. Further, security could also be added by analyzing tracked behavior (motion) as it corresponds to predicted behavior, e.g., behavior corresponding with the execution of required procedures. This information would be valuable for detecting a possible insider not only during emergency situations, but also during times of normal operation.

We developed technology to assist in detecting and tracking insider activities within a Department of Energy facility. The basis for the technology is 3-D video motion detection, which provides significant high-level information about activity within a monitored room. This high-level information is used to identify certain alarm conditions, such as (1) violation of a two-man rule, (2) violation of process control procedures, (3) improper evacuation procedures, (4) unauthorized access to

We developed technology to assist in detecting and tracking insider activities within a Department of Energy facility. The basis for the technology is 3-D video motion detection, which provides significant high-level information about activity within a monitored room.

protected areas, and (5) unauthorized item removal. The system is designed to accommodate numerous other scenarios that may be specific to a given facility. We also added a data-logging feature to the system to record and play back video in which alarm conditions occurred.

Although the developed technology is video-based, it is not a system that requires continual viewing by a human operator. One of the difficulties with detecting insider activity is the reluctance of facilities to use cameras, which could be perceived as a lack of trust in people to do their jobs, i.e., a “big brother” syndrome. With this system, however, high-level processing performs all the monitoring activity that otherwise would be done by an operator. It is only when alarm conditions arise that an operator would need to either observe the live video or play back the recorded alarm scenario. This is particularly beneficial in the event of facility alarm conditions that require an evacuation. Although the video would not be observed immediately, it would be available for playback when the evacuation condition is terminated. If an alarm condition were raised during the evacuation, a procedure with an increased security level could be implemented immediately, e.g., external fences would be monitored in case an unauthorized item was removed and thrown over the fence to be retrieved later.

This technology could be tailored to specific procedures as required by a facility. It is developed to allow the addition of new features and alarm conditions. It could be integrated with existing systems to receive external sensor input and to provide alarm information for external analysis.

Refereed

Nelson, C. L. 2003. High-Resolution 3-D Insider Detection and Tracking. Sandia Technical Report SAND2003-3385, Sandia National Laboratories, Albuquerque, New Mexico.

38707

Microfabricated Dielectrophoretic Sample-Preparation System

E. B. Cummings, B. A. Simmons, K. R. Long, R. Shediak, A. K. Singh, G. J. Fiechtner

This project developed designs of dielectrophoresis-based particle filter/concentrators and spectrometers with applications for embedded and stand-alone processing of samples to remove unwanted particles, to selectively concentrate target particles, and to disperse particles spatially and temporally by their electrical properties. Such functions have promise for automated sample preparation. These devices represent a new class of analytical and processing apparatus—there are no analogs at either the micro- or macroscale. The project produced and validated designs of uniform-array-based batch concentrators, developed and tested designs of nonuniform-array-based batch concentrators, and developed designs of continuous-flow post-, ridge-, and facet-based particle concentrators and continuous-flow ridge-based particle spectrometers. Sandia tested and developed all designs through numerical simulations using Laplace, a microfluidic simulation tool that we developed under this project. This project also produced a general zero-dispersion design methodology for microfluidics and MuCAD, a software computer-aided design (CAD) tool to assist designers of these advanced microdevices.

Our accomplishments will have a lasting impact on the design of electrically driven microfluidic systems. We began by developing and optimizing dielectrophoretic particle filter/concentrators based on the following:

- Trapping in uniform post arrays,
- Trapping in nonuniform post arrays, and
- Continuous flow through uniform post arrays.

The first family of devices spawned a project for concentrating pathogens in drinking water. Jointly, these projects demonstrated their effectiveness for concentrating and separating bacteria, including *E. coli*, *B. subtilis*, *B. cereus*, and bacillus spores. We also invented a stamped and rolled or stacked geometry to support commercializable devices that scale to high flowrates and filed a patent.

We conceived devices based on nonuniform arrays of posts early in the project and submitted them for fabrication. At the time, the designs exceeded our fabrication capabilities, and their development was deferred. Later, we developed a novel

Sandia tested and developed all designs through numerical simulations using Laplace, a microfluidic simulation tool that we developed under this project. This project also produced a general zero-dispersion design methodology for microfluidics and MuCAD, a software computer-aided design (CAD) tool to assist designers of these advanced microdevices. Our accomplishments will have a lasting impact on the design of electrically driven microfluidic systems.

device architecture that avoided many of the problems that hampered fabrication of the previous designs. These devices were successfully fabricated in glass and plastic. Experiments confirmed that these devices collect bacteria from a flowing liquid stream, but a complete evaluation was terminated with the project's funding. Nevertheless, we filed a technical advance and are pursuing a patent.

The development of the third class of devices instigated significant breakthroughs in electrokinetic and dielectrophoretic design. We previously observed a phenomenon of streaming dielectrophoresis, in which dielectrophoresis redistributes and redirects particles without immobilizing them. We observed experimentally and in simulations that this phenomenon caused particles to follow columns of posts in an array when columns are oriented at modest angles with respect to the liquid flow because of an enhancement or depletion effect, a result we published. The difference between the flow and particle-propagation vectors continuously filters and concentrates. While designing such a concentrator, we developed a methodology for maintaining a uniform electric field across a tilted interface between a patterned array and open channel, which led directly to a general solution for asymptotically zero-dispersion microfluidic design.

This faceted design methodology allows engineers to design flow manifolds, turns of arbitrary angle, expansions, offsets, etc., using a calculator or numerical transcendental equation solver. We experimentally verified and filed a patent for this methodology and presented and published elements of the methodology. We presented the resulting streaming dielectrophoretic designs at an invited talk and in an invited article and filed a patent.

The work in faceted microfluidics, in turn, spawned two novel classes of dielectrophoretic devices employing two-level channels: faceted filter/concentrators, and corduroy filter/concentrators and spectrometers. These 2 ½-D (2 ½-dimensional) methodologies dramatically simplify the design of streaming dielectrophoretic devices and tremendously improve power efficiency. We filed a provisional patent for the faceted dielectrophoretic method and apparatus and a utility patent for the corduroy method and apparatus. The corduroy designs are to be embedded in microsystems for a number of Sandia programs, and the faceted methodology is an enabling technology for a new project that proposes to enhance the sensitivity of chemical detectors.

The stated goal of this project was to have device designs ready for implementation, and we delivered designs, simulation

...we developed a novel device architecture that avoided many of the problems that hampered fabrication of the previous designs. These devices were successfully fabricated in glass and plastic. Experiments confirmed that these devices collect bacteria from a flowing liquid stream,....we filed a technical advance and are pursuing a patent.

software, custom CAD software (MuCAD), and most importantly, rational design methodologies to microfluidics engineers.

Refereed

Cummings, E. B. 2003. Continuous-flow microfluidic particle filter/concentrators based upon streaming dielectrophoresis in arrays of insulating posts. (Invited) *IEEE Engineering in Medicine and Biology J.*, accepted.

Cummings, E. B., and A. K. Singh. 2003. Dielectrophoresis in microchips containing arrays of insulating posts: Theoretical and experimental results. *Analytical Chemistry* **75**:4724–31.

Cummings, E. B., G. J. Fiechtner, A. K. Singh, B. A. Simmons, Y. Fintschenko, and B. Lapizco-Encinas. 2003. Continuous streaming dielectrophoretic particle filter/concentrators. *μ TAS 2003: Proc. 7th International Conference on Miniaturized Chemical and Biochemical Analysis Systems* **1** (October, Squaw Valley, California).

Fiechtner, G. J., and E. B. Cummings. 2003. Faceted design of channels for low-dispersion electrokinetic flows in microfluidic systems. *Analytical Chemistry* **75**:4747–55.

Fiechtner, G. J., and E. B. Cummings. 2003. Faceted microchannels for low-dispersion electrokinetic flows. *μ TAS 2003: Proc. 7th International Conference on Miniaturized Chemical and Biochemical Analysis Systems* **1** (October, Squaw Valley, California).

Fiechtner, G. J., and E. B. Cummings. 2003. Low-dispersion electrokinetic flows for expanded separation channels in microfluidic systems: Multiple faceted interfaces. *J. Chromatography A*, accepted.

Fiechtner, G. J., and E. B. Cummings. 2003. Low-dispersion turns for electrokinetic flows in microfluidic channels using faceted design. Paper presented at the 26th International Symposium on Capillary Chromatography and Electrophoresis, May, Las Vegas, Nevada.

Other Communications

Cummings, E. B. 2003. Ideal electrokinesis and dielectrophoresis. (Invited) Paper presented at the APS March Meeting, March, Austin, Texas.

Cummings, E. B., and G. J. Fiechtner. 2003. Dielectrophoresis device and method having insulating ridges for manipulating particles. U.S. Patent Application, Sandia Technical Advance No. SD-8480.

Cummings, E. B., and G. J. Fiechtner. 2003. Piecewise uniform conduction-like flow channels and method therefore. U.S. Patent Application No. 10/456,772.

Fiechtner, G. J., and E. B. Cummings. 2003. Method and apparatus for concentration and filtration. U.S. Provisional Patent Application, Sandia Technical Advance No. SD-8483.

38708

Automation of Microelectronic Physical Analysis

T. J. Drummond, D. L. Barton, V. R. Yarberr, E. A. Walther, R. P. Fleming, J. M. Green, C. R. Jorgensen

Integrated circuit (IC) verification and remanufacture of obsolete ICs are important problems for chips that have been manufactured in small lots. To verify or remanufacture a circuit, it must be described in sufficient detail to reconstruct the circuit layout. Original design information may be incomplete or contain errors that complicate the process.

Destructive verification/analysis is undesirable, as it requires an adequate supply of chips. Tracing circuit design by hand is too labor-intensive and tedious to be practical. Previous automated methods looked at pattern matching. Pattern matching has been applied to two-dimensional (2-D) circuit images, but the 2-D images typically have problems with ghosting. In addition, the 2-D image loses height information. This height information contains data that can effectively be used to reconstruct the manufactured circuit.

The main thrust of this work was to convert a topographical description of a two-level metal, single polysilicon logic circuit into a 3-D map of conductive traces and identify connection points between traces and between traces and substrate.

We used a laser-scanning microscope to acquire a series of 2-D images. We used these data to construct a 3-D image of the circuit. Independently, we constructed a 3-D model of the circuit from mask layout data. These two 3-D representations were differenced, and the differences were highlighted in the visual representation.

The test example chosen to model is a Sandia-designed IC, SA3305, which is the interrupt controller from the SA3300 16-/32-bit microcontroller family. This family of ICs was built using the Sandia two-layer metal IC process. We created a process model definition using the layer stackup along with the nominal thickness dimensions. The process model is a simplified model that contains only those steps that generate physical features such as depositions and etches. Process steps that did not affect the height of physical features, such as diffusion or ion implantation, were not included. We used this process model definition to drive the creation of various 2-D cross sections and 3-D renderings. To compare 3-D representations, baseline geometry must first be derived from the original design layout. By applying each of the fabrication

The main thrust of this work was to convert a topographical description of a two-level metal, single polysilicon logic circuit into a 3-D map of conductive traces and identify connection points between traces and between traces and substrate.

steps to the GDSII 2-D layout geometry, the resultant 3-D geometry can be derived in a virtual environment. We can then compare this as-designed 3-D geometry to the geometry extracted from images of the actual chip using a set of feature identification rules based on the predicted geometry height and area.

We generated the 2-D cross sections of the layout using the MEMS (microelectromechanical systems) 2-D process visualizer. We generated the 3-D geometry using the MEMS 3-D modeler. These tools are a part of the Sandia MEMS design tool suite originally developed for use with SUMMiT™ (Sandia Ultraplanar Multilevel MEMS Technology), a Sandia-developed MEMS process. We adapted these tools for use with this circuit application using the process model definition mentioned above. We added facet geometry extraction to provide an interface to the collision differencing system via AutoCAD (computer-aided design).

We acquired image data with a Zeiss laser-scanning microscope, LSM320, using a red helium-neon 633 nm laser source. The LSM has a confocal imaging capability that allows the depth of focus to be very shallow. The sample stage is stepped in height in 100 nm increments with the focal plane and depth of focus fixed. Light is nominally collected only from the focal plane at each step. We then used the image stack, typically containing 80–100 images, to construct a topology. We acquired images from bare die that had been subjected to an anisotropic etch to remove transparent oxide layers and leave behind the exposed bare metal and silicon surfaces comprising the circuit.

We manipulated the image stack with Flatland, an open visualization/virtual reality application development environment developed at the University of New Mexico. It allows software authors to construct and users to interact with arbitrarily complex graphical and aural representations of data. The tagged image file format (TIFF) files generated by the confocal imaging microscope were considered as layers, read into Flatland, and filtered to reduce the pixel data to only the most important data. In other words, the filter reduced the “noise” from the data. The AutoCAD model of the chip was read into Flatland. There the data were scaled, rotated, and translated until they overlapped and could be compared. To find their point of greatest intersections, a collision algorithm tested the chips versus the facets of the AutoCAD file, and all such colliding cubes and facets were marked. We maximized this collision count, creating a best fit of the image data to the AutoCAD mask data.

Refereed

Holton, D., T. Eyring, V. R. Yarberry, C. R. Jorgenson, T. J. Drummond, E. A. Walther, and T. P. Caudell. 2003. Integrated circuit verification using three-dimensional virtual environments. *Microelectronics J.*, to be submitted.

38712

Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection

S. M. Cameron, J. V. Sandusky, T. A. Pitts, M. J. Kelly, M. H. Beggans, S. R. Vigil, S. H. Kravitz, D. J. Rieger

The development of frequency-agile and spectrally diverse lasers has increased the potential for accidental or intentional optical damage to ocular or sensor systems and created new performance requirements for protection and hardening. Future device concepts must exhibit prompt response and recovery, broadband frequency response, high radiant strength, low operational thresholds, and negligible insertion losses that could degrade system performance. These challenges can potentially be met by integrating photon localization and nonlinear optics in a photonic lattice to produce a nonabsorptive structure whose refractive-index profile and spectral reflectivity are regulated dynamically by incident light intensity. A distributed multilayer composed of alternating high and low nonlinear layers can be designed to respond actively to optical radiation, wherein the transmission of low-intensity light is determined by the unperturbed linear refractive index and the onset of high-intensity illumination induces changes in the index of refraction through a second-order Kerr nonlinearity to produce a bandgap.

Sandia's work included the design, performance modeling, and materials fabrication development of an exploratory nonlinear photonic crystal based on porous silicon (po-Si) for optical limiting applications. We used linear metrology and nonlinear optical characterization techniques (Kerr gate, z-scan) in combination with finite-difference time-domain codes to optimize performance and constitutive material parameters. We investigated strategies for vacuum deposition and superlattice structures based on Si or zinc oxide compounds to improve fabrication capability. We also initiated first-order calculations to investigate enhancements to the nonlinear response based on doped resonant microcavities (defects) or semiconductor quantum dots in the local electric field.

The key issues in developing a photonic lattice optical limiter are materials characterization, device fabrication, optical (linear and nonlinear) metrology, and propagation modeling. We successfully fabricated initial candidate material systems (20-layer pairs, each approximately 120 nm thick) in po-Si/Si oxynitride using both electrochemical transformation and vacuum deposition techniques. We completed linear metrology

Sandia's work included the design, performance modeling, and materials fabrication development of an exploratory nonlinear photonic crystal based on porous silicon (po-Si) for optical limiting applications.

in the samples using Fourier-transform infrared spectroscopy, ellipsometry, wavefront sensing, and scanning-electron microscopy to assess optical quality, estimate porosity, and detect the presence of material under-layering properties. We conducted nonlinear optical analysis using both z-scan and time-resolved pump/probe Kerr gating apparatus with a femtosecond titanium-sapphire laser to measure the Kerr nonlinearity and two-photon absorption, respectively. Thin-film surface quality and the presence of bulk Si made unambiguous interpretation of the nonlinear contribution unique to po-Si difficult and will require further experiments by nonlinear reflection or spectral interferometry. The material fabrication quality continued to improve during the project lifetime as we transitioned from electrochemical to more precisely controllable vacuum deposition methods. We applied finite-difference methods to modeling the local field and nonlinear response through the quarter-wave nonlinear dielectric mirror stack to assess performance and bandwidth. We constructed a simple nonlinear beamsplitter to validate predictions of the model and suggest system integration strategies, including optimization paths for materials development.

38713

Secure MPLS Control Plane for Internet Connectivity

T. D. Tarman, W. F. Young, M. D. Torgerson, J. T. Michalski, L. G. Pierson, S. P. Black

As rapid Internet growth continues, global communication becomes more dependent on Internet availability for information transfer. Recently, the Internet Engineering Task Force (IETF) introduced a new protocol, multiple protocol label switching (MPLS), to provide high-performance data flows within the Internet. MPLS emulates two major aspects of the asynchronous transfer mode (ATM) technology. First, each initial Internet protocol (IP) packet is routed to its destination based on previously known delay and congestion avoidance mechanisms. This allows for effective distribution of network resources and reduces the probability of congestion. Second, after route selection, each subsequent packet is assigned a label at each hop, which determines the output port for the packet to reach its final destination. These labels guide the forwarding of each packet at routing nodes more efficiently and with more control than traditional IP forwarding (based on complete address information in each packet) for high-performance data flows.

Label assignment is crucial for the prompt and accurate delivery of user data. However, the protocols for label distribution were not adequately secured. Thus, if an adversary compromised a node by intercepting and modifying or simply injecting false labels into the packet-forwarding engine, the propagation of improperly labeled data flows could create instability in the entire network. In addition, some virtual private network (VPN) solutions take advantage of this “virtual channel” configuration to eliminate the need for user data encryption to provide privacy. VPNs relying on MPLS require accurate label assignment to maintain user-data protection.

This research developed a working security architecture that demonstrated how to deploy confidentiality, authentication, and nonrepudiation in the global-network label-switching control plane. Sandia developed simulation models and laboratory test-bed implementations that demonstrate this concept and transferred results from this research to industry via standards in the Optical Internetworking Forum (OIF).

This project implemented the MPLS/optical-network control-plane security architecture that we developed earlier. We implemented the architectural concepts in two ways: (1) in

This research developed a working security architecture that demonstrated how to deploy confidentiality, authentication, and nonrepudiation in the global-network label-switching control plane. Sandia developed simulation models and laboratory test-bed implementations that demonstrate this concept and transferred results from this research to industry via standards in the Optical Internetworking Forum (OIF).

an operating network (OPNET) simulation model, and (2) in a small Linux test-bed.

We constructed a simulation model to validate this project's hypothesis for large networks. The central question addressed by this model was, "How does this architectural concept scale for large networks?" and, more specifically, "What is the network overhead associated with this approach?" and "What is the load on the network monitor's central processing unit (CPU)?" The simulation model incorporated a variety of possible control-plane anomalies and implemented algorithms for detecting anomalous behavior and securing control-plane protocols against man-in-the-middle attacks. Simulation results showed little network overhead and CPU loading on the network monitor.

We ported the implementations developed for the simulation model to a laboratory test-bed consisting of Linux MPLS switches. This work was conducted by students in Sandia's College CyberDefenders program. It showed the viability of implementing these concepts in commercial-grade network equipment and will be used for further technology-transfer activities.

This project enabled the transfer of technology associated with control-plane monitoring to Bytex Corporation for inclusion in an upcoming product. This project also facilitated the development of implementation agreements in the OIF that specified mechanisms for securing control-plane protocols from man-in-the-middle attacks, and mechanisms for monitoring control-plane activity in optical networks.

This project accomplished its objective and confirmed the hypothesis that an efficient architecture can be used to implement better security assurances for MPLS control-plane protocols. Our approach, which incorporates secured control-plane communications and monitoring of a distributed MPLS network, is not only effective, but was shown to be commercially viable.

This project enabled the transfer of technology associated with control-plane monitoring to Bytex Corporation for inclusion in an upcoming product. This project also facilitated the development of implementation agreements in the OIF that specified mechanisms for securing control-plane protocols from man-in-the-middle attacks, and mechanisms for monitoring control-plane activity in optical networks.

Refereed

Tarman, T. D. 2002. Control plane hardening and monitoring in switched networks. Paper presented at Lightspeed Europe, December, London, United Kingdom.

Tarman, T. D. 2003. Network security: More than an end-to-end problem. Paper presented at the Workshop on Modeling and Simulation-Based Robust, Secure, and Ultrasecure Networks, May, Hoboken, New Jersey.

Other Communications

Tarman, T. D., R. Graveman, R. Esposito, and J. Naegle. 2003. Auditing and logging specification outline. Paper presented at Optical Internetworking Forum contribution oif2003.033.00, Fremont, California. SAND2003-0388C.

38722

Agile, Microsystems-Enabled Receiver

C. D. Nordquist, T. R. Christenson, G. R. Sloan, G. M. Kraus, T. A. Plut, C. W. Dyck, R. D. Briggs, C. P. Tigges, A. G. Baca

The goal of this project is to develop and integrate radio-frequency (RF) microelectromechanical systems (MEMS) and gallium nitride (GaN) device technologies to create an agile receiver front-end. The module consists of a MEMS transmit/receive (T/R) switch, a MEMS tunable filter, and a GaN low-noise amplifier (LNA), providing significant advantages over existing radar front-ends. The low loss of the RF MEMS elements will allow tunable filters and T/R switches to precede the LNA without significantly degrading the noise figure, facilitating both jammer protection and real-time adaptivity. The GaN LNA offers high dynamic range and natural immunity to overload damage, eliminating the need for a separate limiter. The module, interconnected via monolithic and multichip-module (MCM) techniques, will be several times smaller than current radar front-ends.

Realizing these advances presents formidable technical challenges in electronic materials, processing, and devices. To achieve optimum performance, the RF MEMS components require careful design, well-controlled processing, and detailed characterization. The GaN transistors present challenges in materials growth, device processing and testing, and thermal management. Finally, the integration of these novel technologies into a single module will require accurate component characterization and electrical design. Once these challenges are met, the module will provide lower loss and higher power than existing packages much larger in size.

Sandia intends to integrate the resulting R module with an advanced GaN power amplifier, producing circuitry that will comprise a miniaturized, fully integrated T/R function for multiple applications: synthetic-aperture radar (SAR), fuzes, tags, active phased arrays, and communications. The jammer resistance, signal agility, ultraminiaturization, and high-power density offered by such a module are essential facilitators for next-generation precision-guidance and reconnaissance radars. Some specific, high-impact applications include modulation-agile covert communications, multiplatform tags, fuze upgrades, and mini-SARs for reconnaissance (satellites/unmanned aerial vehicles [UAVs]) and precision guidance (weapons).

Sandia intends to integrate the resulting R module with an advanced GaN power amplifier, producing circuitry that will comprise a miniaturized, fully integrated T/R function for multiple applications: synthetic-aperture radar (SAR), fuzes, tags, active phased arrays, and communications. The jammer resistance, signal agility, ultraminiaturization, and high-power density offered by such a module are essential facilitators for next-generation precision-guidance and reconnaissance radars.

We fabricated low-loss RF MEMS switches that demonstrated less than 0.1 dB of loss and greater than 20 dB of isolation through 10 GHz and lifetimes greater than 10 million cycles in a laboratory ambient. Initial reliability studies indicate that the primary lifetime-limiting mechanism is contamination from the process and testing ambient. To further characterize these switches, we developed test procedures for testing switching speed, power-handling capability, and long-term direct current (DC) and RF switch performance. Using these techniques, we demonstrated 17 W of RF power through a closed RF MEMS switch. However, an individual RF MEMS switch will be unable to handle the desired 50 W of power, so we designed and fabricated novel switching circuits to handle this power for T/R applications.

We developed and demonstrated several types of tunable and switched low-loss RF MEMS capacitors for tunable microwave integrated circuits such as phase shifters and filters. These tunable capacitors have demonstrated quality factors (Qs) greater than 200 at 20 GHz and self-resonant frequencies over 60 GHz. The switched capacitors demonstrate the ability to perform both as a tuning element for filters and as a capacitive switch, with 20 dB of isolation and 0.4 dB of loss at 20 GHz. Using a switched capacitor, we demonstrated a coplanar-strip MEMS filter that switches 38% between X-band and Ku-band for frequency-agile radars. This filter occupies a chip area of 1.5 mm x 2.2 mm and has a bandwidth of 15% with less than 2 dB of loss. To improve on this filter, we designed and fabricated a three-pole comb-line filter with 2-bit digital switching between 8 and 12 GHz that has the potential to demonstrate less than 2 dB of loss.

We made significant progress toward growing and fabricating practical GaN field-effect transistors (FETs) on high-thermal-conductivity silicon carbide (SiC) substrates. We characterized the DC, RF, noise, and gate-lag properties of on-wafer devices with 0.25 μm gate length, indicating that Sandia's current GaN technology, while not optimized for the noise figure, will be adequate for the LNA application. We will use these measurements to design the GaN-based hybrid LNA in the coming year.

We expect to demonstrate soon the integration of these important elements into a radar front-end; this demonstration will be an important step toward miniature radars and other electronic systems.

We expect to demonstrate soon the integration of these important elements into a radar front-end; this demonstration will be an important step toward miniature radars and other electronic systems.

Other Communications

Dyck, C. W., T. A. Plut, C. D. Nordquist, G. M. Kraus, G. D. Schmidt, K. L. Gass, P. S. Finnegan, I. C. Reines, and C. T. Sullivan. 2003. A compact MMIC-compatible RF MEMS switch. *Proc. SPIE Micromachining and Microfabrication Symposium: MEMS Components and Applications for Industry, Automobiles, Aerospace, and Communication II* **4981** (29 January, San Jose, California): 222–29.

Nordquist, C. D., A. Muyschondt, M. V. Pack, P. S. Finnegan, C. W. Dyck, I. C. Reines, G. M. Kraus, G. R. Sloan, and C. T. Sullivan. 2003. A MEMS high-Q tunable capacitor for reconfigurable integrated circuits. *Proc. SPIE Micromachining and Microfabrication Symposium: MEMS Components and Applications for Industry, Automobiles, Aerospace, and Communication II* **4981** (28 January, San Jose, California): 1–8.

48746

Digital Signal Processing for Acoustic-Seismic Target Identification

K. T. Malone, M. W. Koch, G. B. Haschke

Acoustic-seismic target identification continues to be an important area of research in support of a wide variety of applications. Significant advances in detecting, tracking, classifying, and identifying a wide range of targets are necessary to meet the needs of the user communities. Sandia's effort in this project concentrated on developing algorithms in four vital areas: fundamental frequency estimation, seismic detection, cylinder classification, and target identification. Correct fundamental frequency estimation is required to generate proper feature vectors for use in classification and identification algorithms. A robust seismic-detection algorithm aids in detecting quieter targets. An improved cylinder classifier can aid in classifying those targets that are difficult to identify explicitly from acoustic data. New identification algorithms increase identification performance on known targets and also assist in separating targets from nontargets.

Acoustic-seismic signal processing for target classification and identification combines multiple algorithms to effectively accomplish the required task. We concentrated our efforts on developing algorithms in four vital areas: fundamental frequency estimation, seismic detection, cylinder classification, and target identification. The following summarizes the major accomplishments in each of these areas.

(1) A robust fundamental frequency estimator is critical to properly generating feature vectors from acoustic emissions. These feature vectors are then used by the cylinder-classification and target-identification algorithms. Previous algorithms for fundamental frequency estimation computed estimates based solely on the current frame of acoustic data. We extended these algorithms to incorporate prior estimations and track history for addressing targets with complex acoustic emissions. Results to date are encouraging, although future work is necessary to fully realize the potential of this approach.

(2) We developed a constant-false-alarm-rate seismic-detection algorithm for ground vehicles. This algorithm automatically adapts to the seismic background level. Field tests indicate that the algorithm is very effective.

(3) Proper cylinder classification can aid in identifying targets with similar acoustic signatures. We investigated the performance of several types of neural-network classifiers and

Sandia's effort in this project concentrated on developing algorithms in four vital areas: fundamental frequency estimation, seismic detection, cylinder classification, and target identification.

compared them to nearest-neighbor classifiers. We obtained significant improvement by integrating the classifier outputs over time.

(4) We extended the sequential probability ratio test (SPRT), an identification algorithm from previous work, to increase performance and to better discern targets from nontargets. We determined that the dependencies among contiguous feature vectors skewed the simulation results from the theoretical results. It is difficult to model the dependencies due to the fact that the data were nonstationary. Instead, we used a Markov chain to model the dependencies present in the template-matching scores. Preliminary results using a limited target set are promising. However, to add robustness and fully characterize the algorithm performance requires further work.

52706

Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons

J. A. West, B. J. Kirby

In the last 10 years, the development of deoxyribonucleic acid (DNA) gene array or “microarray” technology capable of detecting thousands of genes in a single experiment has rapidly advanced and become a widespread application technology. Two significant drawbacks to this technology in its current format are the long and tedious processing time for ribonucleic acid (RNA)/DNA sample preparation, taking up to 2 days, and exquisite sensitivity of the aforementioned samples to degradation from ambient DNA and RNA nucleases. To tackle these inherent weaknesses in gene array analysis, Sandia is developing a μ TAS (micro-Total Analysis System) gene array that can concentrate, fluorescently label, and hybridize target genes on a single device. The potential advantages of such a device are the dramatically reduced sample throughput time, decreased sample degradation, and small size, which are amenable to portable devices. This device will combine the use of microfluidics and microarrays to facilitate the detection of unknown target genes. Here we present an optimized strategy for DNA microarray probe synthesis that requires less than 30 min in benchtop synthesis. We demonstrate comparable hybridization efficiencies with much reduced time of analysis. Moreover, the current method will be more amenable to integration with the fabricated microfluidic chip as the labeling reaction is enzyme-free. We further report the fabrication of the first integrated microfluidic chip with both sample-processing channels for monolith polymerization and the fabrication of a high-density gene array on the same chip.

(1) *Definition of polymer substrate.* We collaborated internally to produce a glycidyl methacrylate porous polymer monolith that can be functionalized after polymerization in a channel. Scanning-electron microscopy (SEM) micrographs show that the polymer adheres to the channel wall and can be functionalized after formation using epoxide-amine chemistry.

(2) *Isolation of messenger RNA (mRNA) with polymer substrate.* After determining the successful post-functionalization of the monolith with an amine containing fluorescent dye, we functionalized the monolith with an oligonucleotide (oligo d(T) 30mer-c6-amine) to trap mRNA in

To tackle these inherent weaknesses in gene array analysis, Sandia is developing a μ TAS (micro-Total Analysis System) gene array that can concentrate, fluorescently label, and hybridize target genes on a single device. The potential advantages of such a device are the dramatically reduced sample throughput time, decreased sample degradation, and small size, which are amenable to portable devices.

the monolith. We currently are confirming the success of this chemistry.

(3) *Design of microfluidic mRNA trapping trip.* To date, we have designed four different chips that have both mRNA capture channels and microarray spotting areas. We produced photolithographic masks of the designs, and the fabrication process is under way.

(4) *Gene list query for microarray.* We currently are compiling a database of Category A, B, and C class pathogens, toxins as well as current emerging infections (Center for Disease Control [CDC]). To date, this list includes 79 infectious diseases, organism species, and classification associated with disease, genome type (DNA/RNA and single-strand/double-strand [ss/ds]) GeneBank ascension numbers, and virulence regions in the genome.

(5) We filed a technical advance on the technical developments for the microfluidic gene array—SD #8433, “Development of a Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons.” We currently are preparing the patent application.

We filed a technical advance on the technical developments for the microfluidic gene array..., “Development of a Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons.” We currently are preparing the patent application.

52707

Active Network and Use of Network Processor

T. Q. Thai, T. D. Tarman, S. T. Jones, D. P. Ghormley

This is a classified report.

52708

Zero-Power Radio Receiver

R. W. Brocato, J. R. Wendt, E. J. Heller, G. Omdahl, S. Jones, E. J. Gurule, C. L. Gibson

Sandia seeks to develop a radio receiver that is completely passive, requiring no operating power. This receiver will be a much more sophisticated version of the zero-power crystal-set radios that were used decades ago. Its construction will leverage developments in Sandia's state-of-the-art capabilities in microfabrication. This modern zero-power radio receiver will make use of completely passive electronic components with the centerpiece being a surface acoustic-wave (SAW) correlator.

The SAW correlator required for this radio receiver will make use of a long, precisely selected code at a given frequency to serve as a "key." Previous work demonstrated correlators built with "key" lengths of 127 bits, allowing up to 1038 unique combinations. We will use significantly longer codes to effectively narrow the receiver bandwidth even more. We can then use the radio energy from this "key" to turn on a transistor switch used to power a standard radio transceiver or other electronic device.

Since the zero-power radio receiver requires no operating power, it is ideal for use in waking up remote-sensing systems that may be left dormant for weeks or months at a time. The entire radio receiver will consist of an antenna, an input-matching network, a SAW correlator, a passive peak-detection circuit, and a field-effect transistor (FET) switch. It can be built in a small button-sized volume (minus the antenna) and could potentially receive signals transmitted via satellite. The goal of this project is to design a receiver that can be passively activated from a transmitter at a range of at least 10 mi.

Our work centered on the development of long-code SAW correlators suitable for use in a zero-power radio receiver. We successfully developed and used the first deliverable, a high-level simulation test-bench running under SPICE. Other, simpler models running under MATLAB were also developed and are in use on this project.

First, we developed and evaluated several medium-length SAW correlators for operation at 2.45 GHz. The use of the electron-beam machine for fabrication of these devices led to arguably the best-performing microwave-frequency SAW correlators ever built. A technical paper detailing the results of

...we developed and evaluated several medium-length SAW correlators for operation at 2.45 GHz. The use of the electron-beam machine for fabrication of these devices led to arguably the best-performing microwave-frequency SAW correlators ever built.

this work was given at the IEEE Electronic Components Technical Conference in New Orleans.

Testing of these devices provided insight for the system study that we next conducted. This study determined optimal operating frequency and physical size limitations of the receiver. The study concluded that optimal precision of the electron-beam-fabricated devices is achieved at around 1 GHz; however, optimum antenna size occurs at much higher frequencies. We concluded an optimal operating frequency for the entire system to be 2.45 GHz. Specific applications may have differing constraints that may call for a different value.

The results of the study led to the development of higher-performance medium- and long-code correlators at 0.918 and 2.45 GHz. The evaluation of these correlators led to further refinements in the design of high-frequency SAW correlators. We produced long-code SAW correlators suitable for use in a zero-power radio receiver. However, the received signal power is required to be high, thus limiting the useful range of the receiver. This is not a fundamental limitation, but merely indicates the need for greater refinement in the process gain available from the correlator. Ongoing work will serve to extend the range of a zero-power radio receiver built using SAW correlators by improving the quality and length of the correlator.

We also developed support components for a low-power radio receiver. We devised a passive envelope detector and tested several different versions. The development of this critical component opens up the possibility of building extremely long high-gain correlators using a novel correlator structure. We also developed and tested ultrawideband antennas.

We submitted several technical advances and expect that one or more patents will result directly from this work.

The results of the study led to the development of higher-performance medium- and long-code correlators at 0.918 and 2.45 GHz. The evaluation of these correlators led to further refinements in the design of high-frequency SAW correlators.

Refereed

Brocato, R. W., E. J. Heller, G. Omdahl, J. R. Wendt, S. Jones, and D. Palmer. 2003. High-frequency SAW correlator module. *Proc. 53rd Electronic Components and Technology Conference* (May, New Orleans, Louisiana): 458–63.

Brocato, R. W., E. J. Heller, J. R. Wendt, E. J. Gurule, G. Omdahl, C. L. Gibson, J. Smith, and D. Palmer. 2003. Ultrawideband communication using a SAW correlator zero-IF architecture. *Proc. IEEE Topical Conference on Wireless Communication Technology*, accepted.

52709

Completely Passive Microwave Tag

R. W. Brocato, G. Omdahl, E. J. Heller, J. R. Wendt, E. J. Gurule, C. L. Gibson, S. Jones

Sandia seeks to build a completely passive radar-readable tag to work at frequencies of 1 to 5 GHz. Recent advancements in Sandia's surface acoustic-wave (SAW) microfabrication capabilities indicate that it is possible to build a SAW-based completely passive tag that will work with low-power microwave radars. This expands on previously developed SAW correlators. The tag size will be 1 mm³, minus the antenna.

A SAW correlator delivers a frequency-modulated impulse signal when stimulated with a properly phase-coded signal at the correct frequency. The impulse signal from a receiving SAW correlator can be used to drive a second SAW correlator. The impulse response of the second SAW correlator can be another unique code that will be transmitted back to the exciting radar. The principle is similar to that used in a microwave corner reflector, but the advanced coding capability of the SAW correlator enables use of a complex and unique code. The returning signal will appear as a unique, very wideband, and very discrete signature to the tracking radar. The return signal may also be below the background-noise level, but can still be highly detectable due its spread-spectrum, coded nature.

A passive microwave tag should enable low-cost, long-term tagging and tracking of objects from low-power, ground-based radars. This can enable tracking of goods within a facility without the vulnerabilities of current passive tag-based systems. This can also have applications for vehicle- or people-tracking in homeland defense, nonproliferation, and security applications. Our final goal is a fieldable, passive tag of immediate use in one or more Sandia system applications.

The centerpiece of the passive tag is the retransmitting, coupled SAW correlator. Work focused on developing the three components that make up this device: a forward- and reverse-operating SAW correlator and an envelope detector. We conducted a system study that compared the pros and cons of various operating frequencies, signal-power levels, and component-design variations. Next, we fabricated a series of optimized SAW correlators operating at 918 MHz and 2.45 GHz, based on the results of the system study. These are possibly the best-performing microwave-frequency SAW correlators ever built. Nonetheless, the evaluation of these correlators led to further refinements in the design of high-

...we fabricated a series of optimized SAW correlators operating at 918 MHz and 2.45 GHz, based on the results of the system study. These are possibly the best-performing microwave-frequency SAW correlators ever built.

frequency SAW correlators. We created and tested a variety of different configurations. This process led to an overall refinement in correlator performance and yield. The correlator serves to concentrate the energy from the incoming radio wave, so a high-quality correlator greatly extends the tag range. We are optimizing both overall correlator length and correlator peak-to-sidelobe performance.

We built and evaluated suitable ultrawideband antennas. We evaluated a commercial envelope detector, but found it to be unsuitable. A custom envelope detector is under development. We suitably optimized forward- and reverse-operating SAW correlators. We demonstrated a complete retransmitting, coupled SAW correlator. Current work centers on refinement of a very long-code, low-loss correlator for use in the tag.

We submitted a total of four technical advances—(1) Electrically Programmable SAW Correlator, (2) SAW Correlator RF Tag, (3) Optical Addressing and Wake-up of an Optical Tag, and (4) SAW Correlator-Based Communication Architecture—and expect this work to lead to one or more patents.

Refereed

Brocato, R. W., E. J. Heller, G. Omdahl, J. R. Wendt, S. Jones, and D. W. Palmer. 2003. High-frequency SAW correlator module. *Proc. IEEE Electronic Components and Technology Conference* (May, New Orleans, Louisiana): 1980–7.

Brocato, R. W., E. J. Heller, J. R. Wendt, E. J. Gurule, G. Omdahl, C. L. Gibson, J. Smith, and D. W. Palmer. 2003. Ultrawideband communication using a SAW correlator zero-IF architecture. *Proc. IEEE Topical Conference on Wireless Communication Technology*, accepted.

52710

Security Coatings for Multichip Modules

R. A. Neiser, Jr., B. A. Tuttle, K. Rahimian, J. Cesarano, III, D. J. Cook, A. C. Hall, J. J. Clement, R. J. Martinez

Sandia's goal in this work is to develop new tamper-resistant coatings for multichip modules (MCMs) used in electronics. Much of the current edge that exists for the U.S. military relies on sophisticated electronics. Protecting this valuable technology is becoming an increasingly important consideration in battlefield deployment and foreign sales of military equipment. The central task of this project is to develop a new ceramic coating system that can be applied to MCMs using flame-spray processing. Currently available tamper-resistant coatings are limited in number and in the types of devices that can be protected. The proposed solution offers a number of advantages over existing technology. Effective tamper-resistant coatings must provide good protection to the electronic parts while not affecting their functionality. They must also be relatively inexpensive and easy to apply. Furthermore, the coating process should have sufficient flexibility to accommodate different board compositions, geometries, chip sizes, and operating conditions (e.g., temperature and humidity ranges, vibrations, and accelerations). Our approach is to synthesize a number of candidate ceramic powders, to spray them onto test coupons, and to evaluate their performance. After completing screening studies, we will select the most promising materials to coat electronic test vehicles. We will inspect the test vehicle to ensure that the electronic components function after the coating has been deposited and that adequate protection has been provided.

Our activities focused on (1) selecting candidate materials for the tamper-resistant coatings, (2) testing various methods that fabricate them into viable feedstock materials, and (3) establishing an appropriate electronic-test-vehicle capability on which to deposit coatings. We developed a set of criteria to aid in the selection of candidate materials. After listing a wide range of materials, we selected two ceramic compositions as promising candidates. We investigated three different approaches for applying the ceramic: powder flame spraying using a Metco 6P torch, ceramic-rod flame spraying using a Rokide torch, and a modified version of wire flame spraying using a Metco 5K torch. Powder flame spraying appears to be the most promising approach at this time, and upcoming work will focus on this technology. We identified a commercial

Sandia's goal in this work is to develop new tamper-resistant coatings for multichip modules (MCMs) used in electronics. Much of the current edge that exists for the U.S. military relies on sophisticated electronics. Protecting this valuable technology is becoming an increasingly important consideration in battlefield deployment and foreign sales of military equipment.

source for the two ceramic formulations in powder form and placed an order for procuring several kilograms. The powders are typically too fine for powder flame spraying. We took a freeze-drying and sintering approach to coarsen the powders into the appropriate size range. Practice runs using aluminum oxide as a surrogate material suggest that this approach is valid. We currently are testing the freeze-drying and sintering approach with the actual materials. We performed a number of experiments to test fabrication methods for ceramic rods. Getting straight rods that melted and atomized properly in the flame proved to be challenging. In addition, we demonstrated that the standard method for operating the Rokide gun produces particle velocities that are too high for this application. For these reasons, we are not considering further work on ceramic rods and the Rokide gun. The modification to wire flame spraying involved fabricating a polymeric fiber that was heavily loaded with ceramic powder. We fabricated several fibers with different ceramic loadings. However, the loading rates are probably too low to be practical, and proper melting and centering of the fiber in the flame will probably be difficult.

We made substantial progress on designing and procuring electronic modules (called “Sandia Test Vehicles” [STVs]) that can serve as test-beds for the MCMs used in military electronics. The STV consists of Sandia’s Assembly Test Chip (ATC version 2.6) mounted on a BN-300 polyimide circuit-board material. Metal traces on the board go to an edge connector that plugs into a cable that leads to a specially designed piece of test hardware. We ordered STVs from a commercial vendor. The STV is designed to be interrogated during the spray process so that damage to the gold bondwires can be immediately identified. The test vehicle will also allow one to monitor the gradual degradation of bondwires and their joints both on the chip and on the board as the coating process and subsequent environmental testing are performed. We set up and tested a spray station for mounting the STVs in front of the Metco 6P torch. We expect that initial spraying onto the STVs using the freeze-dried and sintered powders will occur soon.

We made substantial progress on designing and procuring electronic modules (called “Sandia Test Vehicles” [STVs]) that can serve as test-beds for the MCMs used in military electronics.

52711

Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces

C. E. Hickox, Jr., W. S. Winters, Jr., J. E. Brockmann, A. S. Geller, B. M. Rush, M. J. Martinez, D. K. Gartling

This project addresses modeling and simulation for contaminant transport in interior architectural spaces and is motivated by the need to reduce the risks from and mitigate the effects of attacks with chemical and biological (C/B) agents. Sandia's goals are (1) to develop and implement an integrated suite of validated computational tools that describe contaminant transport with sufficient accuracy to support credible risk assessments and consequence analyses, (2) to utilize the computational procedures in an integrated approach to identify effective strategies to protect facilities and to mitigate the effects of attacks through the implementation of passive and active control strategies, and (3) to validate the simulation strategies through comparisons with existing experimental data.

To support systems studies, we will develop a multizone airflow simulation code and investigate the coupling of this code with computational fluid dynamics (CFD) simulations. We will determine the appropriate CFD modeling and simulation strategies for application to contaminant transport in complex interior spaces through the use of commercial and in-house CFD software. We will develop simplified CFD simulation strategies that will allow for the efficient investigation of large-scale problems. All computational tools will be validated against existing experimental data.

We modified the technical thrust of our original proposal to reflect a more tightly focused activity that addresses the prediction of contaminant transport in buildings and that is organized around fundamental technical approaches to modeling and simulation based on idealized multizone representations and detailed CFD.

We developed a new multizone simulation code, NETFLOW, that includes the capability of performing full transient simulations for airflow, contaminant transport, and thermal effects, and that represents an improvement in capabilities over existing multizone simulation strategies. The structure of this code is compatible with that of CFD codes, which will facilitate linking between multizone and CFD codes.

We developed a new multizone simulation code, NETFLOW, that includes the capability of performing full transient simulations for airflow, contaminant transport, and thermal effects, and that represents an improvement in capabilities over existing multizone simulation strategies. The structure of this code is compatible with that of CFD codes, which will facilitate linking between multizone and CFD codes.

We validated the code against experimental data obtained in the so-called *German Village experiments*.

We successfully linked the multizone simulation code, NETFLOW, with an in-house CFD code, RIO, to provide a combined multizone/CFD simulation for contaminant transport in a realistic building.

We performed CFD simulations of contaminant transport for several model rooms and compared the results for laminar and turbulent flows. We demonstrated that detailed CFD simulations produce results that differ significantly, in local detail, from those associated with typical multizone simulations. Hence, it is important to simulate contaminant transport accurately within critical areas of a building. A fundamental difficulty that we identified regarding CFD simulations is related to the selection and implementation of an appropriate turbulence model for the low-Reynolds-number turbulence, accompanied by possible buoyancy effects, anticipated within interior spaces.

To further elucidate the nature of the transient velocity fluctuations observed in interior spaces, we performed a velocity survey for a typical conference room. We will use information on the velocity fluctuations measured to guide the implementation of turbulence models for CFD simulations and to aid in the development of diffusion models for application in multizone and simplified CFD simulations.

We identified initial approaches for simplified CFD simulations of transport in interior spaces. These approaches include potential flows, inviscid flows with vorticity, and other reduced-order models. These approaches offer significant simplifications over traditional simulations based on the Navier-Stokes equations coupled with a low-Reynolds-number turbulence model. The development of simplified simulation strategies holds promise for more-efficient simulations of large-scale indoor environments. We compared potential-flow and laminar-flow simulations for a two-room model problem.

We used experimental data for contaminant transport obtained in the German Village experiments and at the Albuquerque Sunport to validate and guide the development of multizone simulations.

52712

Content-Based Video and Image Indexing System

T. D. Russ, J. J. Carlson, C. L. Nelson, P. A. Davidson, Jr.

Video and image data are knowledge-rich sources of information, but their utility for current and future systems is limited without autonomous methods for understanding and characterizing their content. Sandia's proposed system addresses this issue by exploiting the spatial and temporal information available in video imagery to gain scene understanding. This will allow video imagery to be organized by spatial objects that may include faces or identified targets, by the motion signatures associated with their objects, and/or even by the interactions between objects that occur in a sequence of images. We can then use this information to autonomously characterize video data and/or provide content-specific information to a number of systems that seek information from images and video. Such capabilities may benefit systems dedicated to the detection of insiders, alarm patterns, unauthorized activities in material-monitoring applications, etc. A direct benefit of this approach is the ability to browse and perform query-based searches for useful and interesting information after video data have been acquired and stored. These searches can provide a tremendous benefit for use in intelligence-agency, government, military, and Department of Energy site investigations.

A direct benefit of this approach is the ability to browse and perform query-based searches for useful and interesting information after video data have been acquired and stored. These searches can provide a tremendous benefit for use in intelligence-agency, government, military, and Department of Energy site investigations.

We established a framework for the Video Indexing System that comprises three major units: video archiving, video processing, and video query. We developed the video archiving unit to enable compact, efficient acquisition of large amounts of video information over long periods of time. The archive consists of low-level, motion-content video sequences consisting of images with detected differences from an adaptable background reference. We are developing the video processing unit to examine the low-level, motion-content video sequences to create object clusters from which object attributes can be extracted and on which tracking algorithms can be performed. The important information extracted from this stage is then written to a database file that the Video Query Unit can examine for interesting video segments based on user input. We will investigate the application of a new background-estimation algorithm that is capable of extracting the background from dynamic scenes where the background may be observed as little as 1% of the time. This capability will enable the use of the

technology developed in this project in more dynamic environments.

52713

Bioaerosol Collection and Concentration for Microseparations-Based Detectors

K. Wally, D. J. Rader, M. P. Kanouff, E. B. Cummings, C. R. B. Ellis

The ability to detect biological agents is vital to national security and homeland defense needs, spurring development of compact systems for sensitive field-detection of these agents. A universal challenge for these systems is the efficient autonomous collection and selective concentration of highly dispersed threat agents for detection against the enormous background of benign particles. The challenge is even greater when the goal is concentrated liquid microsamples for input to liquid-based microanalysis and detection systems. A general approach is to follow a two-stage strategy of aerosol collection followed by post-collection concentration to microsample levels. The greater the ability of the collection stage to separate and concentrate, the less demand is placed on the post-collection concentration stage. Conversely, the greater the capabilities of the concentration stage, the more tolerant to the performance of the collection stage. These twin considerations guided our development activities as we worked to perfect Sandia-proprietary collection and concentration technologies for this purpose. In the area of aerosol-collection technology, we are pursuing a strategy of focusing and inertial separation via aerodynamic particle size to achieve initial concentration and separation sufficient to allow impingement collection into mere microliters of liquid collection solution. We are exploiting our microfluids- and electrokinetic (EK)-flow capabilities to attempt direct microimpingement collection into open microchannels of collection fluid. Such an approach minimizes otherwise large evaporation losses and provides minimal input volume to burden subsequent post-collection concentration stages. In the area of post-collection particle concentration in liquid, we pursued a strategy of exploiting dielectrophoretic phenomena to concentrate and selectively sort particles. Our unique approach uses arrays of passive dielectric microstructures rather than arrays of electrodes. For concentration of solubles, such as biotoxin proteins, we are considering a variety of physical, electrical, and chemical means.

For aerosol collection, we demonstrated, through fluid-dynamic modeling and through experiment, the following:

- (1) focusing based on aerodynamic particle size,

The ability to detect biological agents is vital to national security and homeland defense needs, spurring development of compact systems for sensitive field-detection of these agents. ...we worked to perfect Sandia-proprietary collection and concentration technologies for this purpose.

(2) inertial separation for a focusing impactor (FI) geometry, and

(3) inertial separation for an opposed-flow virtual cyclone (OFVC) geometry proprietary to Sandia.

During OFVC testing, we sporadically observed particle deposition as an anomalous squiggly line, stationary in space and steady over time. Subsequent engineering science (ES) modeling of an irregularity in the inlet surface of the OFVC geometry predicts similar behavior, leading us to believe the anomalous behavior can be explained, and thereby avoided.

In the area of direct impingement of focused particles into open microchannels, we explored, through ES modeling and through experiment, the issues of evaporation, hydraulic pressure, and wicking for open microchannels. We obtained experimental results consistent with modeling prediction. During these tests, we learned that particles collected in the free surface of the collection liquid become trapped by surface-tension forces. Subsequent order-of-magnitude comparison of various forces (e.g., inertial, viscous, electrical, etc.) potentially acting on micron-sized particles suggests that surface-tension forces are thoroughly dominant, indicating that free-surface trapping will be a serious impediment to direct microimpingement if it cannot be overcome. Ultimately, particles must become submersed if they are to flow into closed microchannels for subsequent analysis or detection. Potential solutions based on the overcoming of surface tension via various physiochemical means have been hypothesized; now further modeling and experimentation are required.

For dielectrophoretic (DEP) particle concentration, we demonstrated, both through ES modeling and through experiment, the selective concentration of bioparticles at dielectric microposts. Also, recent modeling results for a newly conceived “corduroy” geometry suggest that it may be a highly effective microstructure for DEP particle manipulation, especially particle concentration and particle sorting. We prepared a technical advance for this new concept for a patent application.

For solubles concentration, we completed energy calculations for evaporation or pervaporation, suggesting that electrical or chemical concentration may be preferable from the point of view of energy-consumption requirements. We are now looking at solubles concentration via dewatering using hygroscopic solutions of certain salts (e.g., LiBr) as a water sink and transport medium in an absorption cycle mode.

...recent modeling results for a newly conceived “corduroy” geometry suggest that it may be a highly effective microstructure for DEP particle manipulation, especially particle concentration and particle sorting. We prepared a technical advance for this new concept for a patent application.

Other Communications

Wally, K., E. B. Cummings, C. R. B. Ellis, M. P. Kanouff, and D. J. Rader. 2002. Particle “Front End” for Compact WMD Threat-Detection Systems: Integrated Microsystem Concepts for Intelligent Particle Collection, Separation, Preconcentration, and Processing. Sandia Technical Report SAND2002-8586, Sandia National Laboratories, Albuquerque, New Mexico (November) (limited distribution).

52714

Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains

T. W. Lane, R. Sapra

Although the incidence of infection by naturally occurring strains of biowarfare agents is low, it is important to discern the difference between infection by a natural background strain and by an unusual one that may have been enhanced by genetic engineering. A number of vectors exist for the cloning and expression of genes in important taxa such as Bacillus. These are the genetic engineer's tools used to alter an organism, and traces of their use can be left in the organism modified. These toolmarks take the form of genetic elements such as exogenous promoter sequences, antibiotic resistance genes, and multiple cloning sites. By detecting these, one can discern the difference between a naturally occurring strain of an organism like B. anthracis and one that has been genetically modified.

A finite but growing number of vectors exist for Bacillus. Sandia is analyzing the toolmarks left behind by genetic modification by each of these vectors, then developing polymerase chain reaction (PCR) and hybridization technologies to detect these modifications. These toolmarks can be predicted by modeling and then verified experimentally. There may be multiple ways of detecting a given vector, and many vectors may share the same toolmarks. It will not then be necessary to experimentally verify each vector. The end product of this work will be an integrated assay in a microarray architecture designed to detect genetically engineered pathogens. This work would be carried out in B. cereus, a strain closely related to B. anthracis. The techniques will be applicable to other organisms.

We developed the probe library for the detection of toolmarks and are ready to create our first set of arrays. Development of the probe library passed through three phases. First, we sought out plasmid maps and deoxyribonucleic acid (DNA) sequence data for a large representative sample of the genetic tools that are used by molecular biologists. We made a particular effort to seek out the first-generation or parental plasmids that we used to create subsequent versions of plasmids. By characterizing the relatively smaller number of parental plasmids, we generated probes to detect large numbers of their "offspring." In the second phase, we dissected those vectors into their constituent genetic elements and compiled, compared, and grouped the DNA sequences of those elements

The end product of this work will be an integrated assay in a microarray architecture designed to detect genetically engineered pathogens. This work would be carried out in B. cereus, a strain closely related to B. anthracis. The techniques will be applicable to other organisms.

into different classes for the purpose of detection. We then designed two oligonucleotide probes for each toolmark, each targeting against a different region of the toolmark. We compared the DNA sequences of the probes to target strain sequences to prevent cross-reactivity and false positives. This duplication of probes will serve as an internal control. We completed the assembly of the robot for the production of microarrays and are currently initiating the process of producing the first microarrays for testing. We will create our initial set of toolmark microarrays and initiate the testing against control strains. We also will work out conditions for the hybridization assays and labeling of target strain DNA.

52716

Joint Authentication/Encryption

T. J. Draelos, R. C. Schroepel, M. D. Torgerson, C. L. Beaver, R. A. Gonzales, W. E. Anderson

In this project, Sandia addresses three primary issues associated with systems that perform both encryption and data authentication:

(1) Explore the combining of encryption and data authentication. For example, during encryption, hash the internal state of the cipher instead of the entire message for authentication. In some cases, authentication would be free with encryption.

(2) Minimize the size of the authentication tag. The bandwidth overhead of data authentication can often be a problem, especially for small messages.

(3) Explore efficient software and hardware implementations of joint encryption/authentication algorithms.

We invented a new paradigm for authenticated encryption, where the internal state of the cipher is used to provide the authentication. This methodology has a number of benefits. The encryption has properties similar to cipher-block-chaining (CBC) mode, yet the encipherment and authentication mechanisms can be parallelized and/or pipelined. The authentication overhead is minimal, so the computational cost of the authenticated encryption is very nearly that of the encryption process. Also, the authentication process remains resistant against some initialization vector (IV) reuse. We developed a class of encryption algorithms that are based on cryptographic hash functions. Because of the hash-function construction, the ManTiCore4 (MTC4) class of methods supports variable encryption block sizes up to twice the hash output block length and trivially supports variable key lengths. We also developed a more general construction for using the internal state of any round-based block cipher as an authenticator. As a concrete example of the general construction, we used the Advanced Encryption Standard (AES) as the encryption primitive.

- *Research hash algorithms and determine which are appropriate for use. Currently, we are utilizing the SHA-1 and MD5 hash algorithms because of their wide acceptance and popular use for message-authentication codes. We are also exploring the use of a reduced set of rounds in SHA-1 for the hash function of the MTC4 cipher.*

We invented a new paradigm for authenticated encryption, where the internal state of the cipher is used to provide the authentication.... We developed a class of encryption algorithms that are based on cryptographic hash functions.

- *Research encryption algorithms and determine which are appropriate for use.* We explored two encryption methods for authenticated encryption. The first method is based on a four-round Luby-Rackoff construction and uses hash functions in each round. The other encryption method is the AES.

- *Create first-try joint authentication/encryption algorithms.* We developed three joint authentication/encryption (authenticated encryption) algorithms that take advantage of the internal state of a cipher as the basis of a message authenticator.

- The MTC4 algorithm is based on a four-round Luby-Rackoff construction and can utilize SHA-1 or MD5 for its rounds functions.

- The Reduced MTC4 (RMTC4) algorithm substitutes a faster mixing operation for the hash function in rounds 1 and 4.

- The AES-AUTH algorithm uses the AES for encryption and an inexpensive function of its middle state for authentication.

- *Implement and test first-try algorithms in software.* We implemented the MTC4, RMTC4, and AES-AUTH algorithms in C; they compared quite favorably with the standard use of AES for encryption and HMAC-SHA-1 or HMAC-MD5 for authentication. These algorithms are block parallelizable and, for large messages, provide authentication essentially free of charge.

We submitted a paper describing the MTC4, RMTC4, and AES-AUTH algorithms to the Selected Areas in Cryptography Conference.

Other Communications

Beaver, C. L., T. J. Draelos, R. C. Schroepfel, and M. D. Torgerson. 2003. ManTiCore: Encryption with Joint Cipher-State Authentication. Sandia Technical Report SAND2003-1488C, Sandia National Laboratories, Albuquerque, New Mexico.

52717

Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications

R. E. Loehman, D. W. Luntz, S. J. Glass, P. G. Kotula

Thermal-insulation materials for sharp leading edges on hypersonic vehicles must be stable at very high temperatures (2000°C); they must resist evaporation, erosion, and oxidation; and they should exhibit low thermal diffusivity to limit heat transfer to support structures. Materials with those properties are required for development of hypersonics for prompt and precise delivery to difficult targets, a need that is highlighted in the Emerging Threats Strategic Business Unit business plan. The most promising materials for that application are the family of ultrahigh-temperature ceramics (UHTCs), comprising zirconium diboride (ZrB_2) and hafnium diboride (HfB_2), and composites of those ceramics with silicon carbide (SiC). Those ceramics are hard and have very high melting temperatures (3245°C for ZrB_2 and 3380°C for HfB_2); they are reported to form protective, oxidation-resistant coatings, and to have low vapor pressures at potential-use temperatures. However, in their present state of development, UHTCs exhibit poor strength and thermal-shock behavior, a deficiency that has been attributed to inability to make them as fully dense ceramics with good microstructures.

Sandia's initial evaluation of earlier UHTC specimens made by others suggested that their poor properties were due to features that could be traced to errors in ceramic processing. Our original proposal was based on our belief that UHTC properties could be improved by applying our fundamental understanding of ceramic processing to eliminate the defects that had so far limited UHTC properties.

Results of our work exceeded even our optimistic expectations. We made UHTCs in both the ZrB_2 and HfB_2 systems that are 100% dense or nearly so, and that have favorable microstructures, as indicated by preliminary electron microscopic examination. In addition, we hot-pressed UHTCs with a much wider range of SiC contents than anyone previously has been able to make. Availability of a range of compositions and microstructures will give system engineers added flexibility in optimizing their designs.

Because all subsequent tasks depend on availability of high-quality UHTC materials, we devoted most of our initial effort to developing the process for making them. Our plan was to try hot pressing initially, and if we were unable to make fully dense

Results of our work exceeded even our optimistic expectations. We made UHTCs in both the ZrB_2 and HfB_2 systems that are 100% dense or nearly so, and that have favorable microstructures, as indicated by preliminary electron microscopic examination. In addition, we hot-pressed UHTCs with a much wider range of SiC contents than anyone previously has been able to make. Availability of a range of compositions and microstructures will give system engineers added flexibility in optimizing their designs.

materials that way, to attempt reactive hot pressing. In fact, hot pressing was extremely successful, and we did not have to consider the reactive processing proposed as a backup. We made both ZrB_2 -SiC and HfB_2 -SiC compositions with densities greater than 95% with SiC contents from 2% to 20%.

It is particularly significant that we learned to make fully dense HfB_2 and ZrB_2 UHTCs with SiC contents down to 2%. No one has ever reported nearly full-density UHTCs with less than 20% SiC, and conventional wisdom was that the larger amount of SiC was necessary to achieve full density in hot-pressed HfB_2 and ZrB_2 . Our results provide a much broader range of possible compositions for application as thermal insulation, and we expect that properties such as strength, thermal conductivity, and oxidation resistance will vary with SiC content.

We made specimens in the required shapes to do the mechanical tests. Initially, we are determining microhardness and fracture toughness because they are good screening tests for material quality, and it is easier to do than some of our other planned measurements. We used Vickers indentations over a range of loads to measure the hardness and the fracture toughness of nine experimental compositions. We found that the ZrB_2 -20% SiC material has the highest toughness value and second-highest hardness value. The hardness and fracture toughness values of the HfB_2 -20% SiC material were a close second to those of the ZrB_2 -20% SiC UHTC.

We collaborated with the University of New Mexico (UNM) to provide needed data on thermal conductivity/diffusivity and oxidation resistance of the different UHTC compositions. UNM also set up and calibrated the laser-flash thermal-diffusivity apparatus and is cutting and grinding UHTC specimens for the first measurements.

Other Communications

Loehman, R. E. 2002. Ultrahigh-temperature ceramics for advanced thermal insulation. Paper presented at the Department of Materials Science, 14 November, Houston, Texas.

Loehman, R. E., M. Dowlapalli, P. Lu, D. Ellerby, E. Irby, and S. M. Johnson. 2002. Microstructural analysis of hot-pressed HfB_2 and ZrB_2 . Paper presented at the Fall Meeting of the American Ceramics Society, October, Seattle, Washington.

It is particularly significant that we learned to make fully dense HfB_2 and ZrB_2 UHTCs with SiC contents down to 2%.

No one has ever reported nearly full-density UHTCs with less than 20% SiC, and conventional wisdom was that the larger amount of SiC was necessary to achieve full density in hot-pressed HfB_2 and ZrB_2 . Our results provide a much broader range of possible compositions for application as thermal insulation,....

52718

Leveraging Robotic Planning for Physical-Security Analysis

P. G. Xavier, S. E. Jordan, M. K. Snell, R. R. Peters

Physical-security analysis against terrorists attempts to estimate a minimum probability of system effectiveness, PE. The assumed model is $PE = PI * PN$, where PI is the probability of interruption (detecting adversaries in a timely sense) on a path through a graph modeling the site, and PN is the probability that the security forces neutralize the adversary force in combat, given timely detection. Current tools find only PI-minimizing paths, and there is no guarantee that such a path will result in the minimal PE. PN estimates are based on labor-intensive, human-in-the-loop simulations.

This project brings together path-planning and vulnerability-analysis expertise to better estimate minimum PE. The basic idea is to develop approximation models for the PE for which best (minimizing) paths can be found by applying or extending robot-path/trajectory-planning techniques. These models should identify lower PE candidate paths than the best PI paths because they consider attrition. As it turns out, Sandia's PE model matches the new proposed Department of Energy equation for system effectiveness.

We have been developing an approximation model, associated planning algorithms, and a planning tool for finding best paths based on minimizing the PE for a key adversary—a designated adversary team member whose purpose is to personally commit the act of theft or sabotage that is the main goal of the adversary mission. This planning tool will be operable standalone and could also be used in conjunction with other security-analysis tools.

In upcoming work, we will extend the planning tool to enable it to be applied to multiple-adversary attack analysis. The basic extension is to add a planning capability that finds a trajectory for an adversary team member to disrupt the guard that is the key defender with respect to the key adversary's planned trajectory.

We developed an approach that calculates the system effectiveness $PE(K)$ against a designated adversary entry team member K (the key adversary), whose job is to collect material for theft or to carry out sabotage; attainment of his/her mission goal is thus the central determinant of adversary mission success. Given key adversary K's trajectory in the planned attack, the model computes $PE(K)$, taking into account barriers

This project brings together path-planning and vulnerability-analysis expertise to better estimate minimum PE. The basic idea is to develop approximation models for the PE for which best (minimizing) paths can be found by applying or extending robot-path/trajectory-planning techniques. These models should identify lower PE candidate paths than the best PI paths because they consider attrition.

(delay and detection), alarms, multiple guard patrol and response patterns, and attrition. Spatial relationships (e.g., distance, line-of-sight) among adversaries, guards, and the site model that impact combat and detection can be included.

We applied this PE(K) calculation under various assumptions to yield a series of path-planning problems whose solutions are trajectories that approximately minimize system effectiveness with respect to K. The expression for PE(K) for a given trajectory is the exponential of an integral over that trajectory, and we thus apply PE(K) as the cost function to be minimized by a trajectory on a spatial graph overlaid on a site map. The basic idea behind finding a minimal PE(K) trajectory “lifts” the spatial graph into space-time, making it a space-time graph, and finds a minimal-cost path in this graph. The best m trajectories may also be found. We formulated a series of problems with increasingly relaxed assumptions and have been developing algorithmic approaches to finding paths that approximately minimize PE(K) with respect to them.

We overcame a theoretical snag in our approach, thus making an algorithmic breakthrough that enables the adversary plan to account for probability of detection. We began implementation of the prototype planning tool and are on track to soon have basic planning capabilities, as well as automated spatial graph generation, in 2 1/2-dimensional environments.

We overcame a theoretical snag in our approach, thus making an algorithmic breakthrough that enables the adversary plan to account for probability of detection. We began implementation of the prototype planning tool and are on track to soon have basic planning capabilities, as well as automated spatial graph generation, in 2 1/2-dimensional environments

52719

Buzzard

J. R. Salton, J. C. Neely, H. M. Poteet, B. L. Spletzer, D. S. Callow, G. J. Fischer, C. L. Lewis

Sandia is studying the feasibility of developing the energy extraction, mobility, and communications aspects of a robotic vehicle for classified missions. This type of vehicle would have obvious applications in reconnaissance, distributed sensing, and communications. The vehicle can accomplish long-duration missions, travel long distances, and achieve long-range communications. This will allow for the establishment of valuable distributed sensing grids for reconnaissance and maintenance. Sandia has unique small-scale high-pressure valves, high-stiffness multi-degree-of-freedom joints, and advanced behavior algorithms that enable the development of a small-scale, highly articulated vehicle. This degree of mobility will be necessary to successfully accomplish its required missions.

This vehicle would be useful in a broad spectrum of military and civilian applications and could have far-reaching implications in the realm of law enforcement and in infrastructure integrity. The abilities of this type of vehicle represent a novel capability that is not currently seen in any existing robotic system. All of this represents a potentially substantial advancement in tactical advantage.

From the onset, this study was treated as three separate efforts. The first of these was energy extraction. While the basic scientific premise here seemed simple, its application is not proven and presents significant challenges to implement. Therefore, we performed an analysis to estimate its feasibility. Once this was initially established, we designed and manufactured a scaled laboratory test apparatus to empirically verify the results of the analysis. The initial test results from this helped to refine the analysis to increase its fidelity. We completed these refinements, and the analysis is now in agreement with the test apparatus. All of this led to the conclusion that the theory behind this part of the project is feasible. However, its implementation would require the same proof-of-concept at full scale, and then it would need to be integrated into a working system.

The second area of study was communications. Sandia has studied this type of communication extensively for other related applications. Therefore, the majority of the effort for this portion of the feasibility study was to interface with the group

Sandia has unique small-scale high-pressure valves, high-stiffness multi-degree-of-freedom joints, and advanced behavior algorithms that enable the development of a small-scale, highly articulated vehicle. This degree of mobility will be necessary to successfully accomplish its required missions....The abilities of this type of vehicle represent a novel capability that is not currently seen in any existing robotic system. All of this represents a potentially substantial advancement in tactical advantage.

that performed the related research to verify that their methods could be implemented for the proposed applications. The conclusion was that the science of the application poses no problems. However, like the energy-extraction effort, full-scale development testing would have to be performed to verify this. We expect that this could be accomplished successfully. This would then also need to be combined into a fully integrated system.

Finally, we studied the unique mobility requirements for this type of vehicle. Although deemed feasible, we established that this portion of the development would require sufficient time and funding to get started. Therefore, this will be the greatest area of concentration for the vehicle-development funding provided by others. This follow-on project, if successful, will allow transfer of some of the technologies developed for this effort to other robotic-mobility challenges yet to be conquered.

52720

Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction

O. B. Spahn, D. P. Adams, C. A. Boye, F. R. Gass, S. S. Mani, D. J. Dagel

Recent world events underscore the need for a satellite-based persistent global-surveillance capability. To be useful, the satellite must be able to continuously monitor objects the size of a person anywhere on the globe and to do so at a low cost.

One way to satisfy these requirements involves a constellation of satellites in low-earth orbit capable of resolving a spot on the order of 20 cm. To reduce cost of deployment, such a system must be dramatically lighter than a traditional satellite-surveillance system with a high spatial resolution. The key to meeting this requirement is a lightweight optics system with deformable primary and secondary mirrors and an adaptive optic subsystem correction of wavefront distortion.

Microelectromechanical systems (MEMS) micromirrors will correct for aberrations in the primary mirror and improve image quality, thus reducing the optical requirements on the deployable mirrors. To meet this challenge, MEMS micromirrors must meet stringent criteria on their performance in terms of flatness, roughness, and resolution. While Sandia's SUMMIT foundry provides the world's most sophisticated surface MEMS technology, it must be augmented by other technologies. We expect significant baseline-process modifications, such as utilization of silicon-on-insulator (SOI) substrates for improved mirror stiffness. In addition, we must develop novel designs to meet severe requirements on mirror travel range and accuracy. We will optimize mirror designs by finite-element (FE) analysis validated experimentally, upon which we will fabricate mirror arrays and carry out a subsystem demonstration.

We completed preliminary studies of various mirror designs to obtain the best mirror figure. We designed, fabricated, and modeled several mirror iterations. To better understand critical process parameters such as stress and stress gradient, we co-located test structures with the mirrors and resultant stress parameters measured on the entire wafer, resulting in a stress map as a function of the wafer position. To accomplish this in a timely manner, we automated stress measurements that now enable us to characterize a quarter of a 6 in. wafer in a matter of

...the satellite must be able to continuously monitor objects the size of a person anywhere on the globe and to do so at a low cost.

...Microelectromechanical systems (MEMS) micromirrors will correct for aberrations in the primary mirror and improve image quality.

...MEMS micromirrors must meet stringent criteria on their performance in terms of flatness, roughness, and resolution.

minutes. Furthermore, we carried out several modifications to the baseline SUMMIT process to further improve the mirror figure. We designed, fabricated, and modeled 500 μm -diameter mirrors with a radius of curvature of ~ 1 m, with a resultant sag of 31 nm ($\lambda/18$ at 550 nm). Separately, we fabricated and tested various actuation mechanisms. We evaluated thermal, electrostatic, and novel “zipper” actuation mechanisms for positioning accuracy, with “zipper” actuation appearing to be most promising.

We plan to investigate the design space to explore applicability of a MEMS micromirror array to a broader range of problems, while focusing on a specific ultralightweight, low-earth-orbit telescope challenge. We will predict mirror performance in terms of travel control and surface characteristics using FE analysis and behavioral-level modeling. This will be experimentally validated by fabrication and characterization of the theoretically most promising designs. Finally, we will obtain data on the control over mirror travel range and accuracy, as well mirror surface characteristics for use in future micromirror-array designs in the following years. In addition, we will explore aspects of the integration of SUMMIT technology on SOI substrates, such as process compatibility and feasibility of SUMMIT layer inversion.

Refereed

Gass, F. R., D. J. Dagel, D. P. Adams, G. D. Grossetete, O. B. Spahn, S. A. Kemme, S. S. Mani, and K. J. Malloy. 2003. Stress and curvature in MEMS mirrors. *Proc. SPIE, MOEMS and Miniaturized Systems III* **4983** (27–29 January, San Jose, California): 87–93.

52721

Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment

P. L. Dreike, A. V. Farnsworth, Jr., G. D. Cable, D. E. Carroll

Sandia seeks to develop algorithms that will evaluate the yield and penetration of an earth-penetrating nuclear weapon (EPNW) from optical and possibly electromagnetic pulse (EMP) signatures measured remotely. Knowledge of the yield and penetration performance of the weapon gives a good indication of the likely damage to a deeply buried hard target. Sensors could be on aircraft or satellites.

Light and EMP signals are produced in the air, so it is necessary to model coupling of nuclear energy from below ground to the air. For some penetrations, there may be a partially filled hole back to the surface for which to account. We use generic energy sources and the CTH and ALEGRA shock physics codes to model nuclear energy production by some device, and the codes then model transfer of shock energy and ejection of dirt into the air. The CTH and ALEGRA outputs of material density, pressure, and temperature will be post-processed to compute the light signals (eleven spectral bands 0.4–3.2 μm) as a function of time and viewing angle. We will validate these results code-to-code and compare them with photographic data from the Johnny Boy test of a shallow-buried nuclear detonation. We will also look for other opportunities to validate the code results. We will model transport of neutrons and gamma rays to the air with the MCNP code to evaluate situations that could produce EMP as well as light signals.

We will compute a library of optical signatures for a range of yields, penetration conditions, and viewing angles. We expect that the optical signature shapes in particular will display dependencies on the yield, penetration conditions, and viewing angle. It seems likely that the presence or absence of EMP signals will be inversely correlated with successful penetration. From these dependencies we will develop algorithms for assessing the yield and penetration from measured signals.

- Review potential EPNW yield and penetration performance to define the yield-penetration parameter space of interest for this study.

- Do a literature search for relevant experiments and previous calculations. We found original films of the shallow-buried 0.5 kt Johnny Boy event that we can use in our validations.

Sandia seeks to develop algorithms that will evaluate the yield and penetration of an earth-penetrating nuclear weapon (EPNW) from optical and possibly electromagnetic pulse (EMP) signatures measured remotely. Knowledge of the yield and penetration performance of the weapon gives a good indication of the likely damage to a deeply buried hard target.

- Complete optical signature post-processors for two-dimensional (2-D) and 3-D CTH and write users manual. Post-processors for the CTH and ALEGRA radiation hydrodynamics codes from previous projects are taking more effort than planned to complete and validate.

- Validate CTH and ALEGRA modeling of the Johnny Boy fireball and its light output. Both codes produce air shock waves whose shapes are very similar to the photographed fireball shapes. Modeling light output depends on completing the postprocessors.

- Calculate gamma-ray fluxes reaching the air from a buried burst and make a decision on whether to study EMP generation. We calculated time-dependent propagation of direct and neutron-produced gamma rays to the surface for a range of depths and source energies. We decided against additional investigation of EMP signals.

- Model light signals from the fireballs made by a tactical and strategic yield at various depths and heights above the surface by modeling Johnny Boy and a shallow-buried 400 kT explosion with CTH and ALEGRA. We discovered and corrected two deficiencies in the CTH radiation-transport algorithms in the process of running the 400 kT burst.

Other Communications

Dreike, P. L. 2003. Potential yield and penetration performance of earth-penetrating nuclear weapons in the “near” and “far” term. (U) (SRD) Internal memorandum to C. Andy Boye, Sandia National Laboratories, Albuquerque, New Mexico.

Dreike, P. L. 2003. Production of high-frequency EMP signals by earth-penetrating nuclear weapons. (U) (SRD) Classified internal memorandum to C. Andy Boye, Sandia National Laboratories, Albuquerque, New Mexico.

52722

Radiation-Hardened Optoelectronic Components for Space-Based Applications

D. K. Serkland, P. E. Dodd, G. M. Peake, K. M. Geib, P. A. Snipes, E. L. Blansett, K. R. Lanes

Sandia seeks to develop radiation-hardened vertical-cavity surface-emitting lasers (VCSELs) and photodiodes to be integrated with radiation (rad)-hard driver and receiver electronics from an external vendor (Peregrine Semiconductor Corporation). This will enable the delivery of space-qualified optical transmitters and receivers to the satellite group at Sandia.

We investigated the radiation hardness of VCSELs and photodiodes by looking at the effects of both total-dose and single-event upsets (SEUs) on the electrical and optical characteristics of VCSELs and photodiodes. We investigated the effects of SEUs on bit-error rate in an emitter-detector link, as well as the temporal characteristics of these SEUs.

We fabricated radiation-hardened VCSELs and p-i-n photodiodes for use in satellite applications. These devices offer high bandwidth, low power consumption, and electrical compatibility with rad-hard complementary metallic-oxide semiconductor (CMOS) circuits. We provided devices for Peregrine Semiconductor Corporation, an external vendor that manufactures rad-hard driver and receiver electronics. Devices based on gallium arsenide (GaAs), such as ours, are known to have superior radiation hardness compared with silicon (Si). The radiation hardness is improved by the use of small-volume optically active regions characteristic of GaAs VCSELs and photodiodes. We intended to further redesign VCSEL and photodiode epitaxial structures to achieve less susceptibility to radiation-induced damage, but a reduction in our funding limited these efforts.

Total-dose measurements determine the overall lifetime of the VCSELs and photodiodes in satellite systems. Although previous studies of proton effects have been published, we measured proton dose on our devices, which helps establish a baseline and permits comparison with prior work. We investigated the effects of a total dose of 63.3 MeV protons on the optical and electronic properties of both VCSELs and photodiodes. In addition, we studied neutron-dose effects on VCSELs, GaAs p-i-n photodiodes, and Si photodiodes, and compared proton versus neutron effects.

Devices based on gallium arsenide (GaAs), such as ours, are known to have superior radiation hardness compared with silicon (Si). The radiation hardness is improved by the use of small-volume optically active regions characteristic of GaAs VCSELs and photodiodes.

In contrast to total-dose effects, transient or single-event effects are a new area of study, with clear implications for optical link-error rates on satellites. We investigated the effects of SEUs on our VCSELs and photodiodes. We used protons with an energy of 63.3 MeV at low fluence levels to produce occasional ionization events, with a resultant change in VCSEL output power or a transient response in the photodiodes. We made bit-error-rate measurements with VCSEL-photodiode links, with either the VCSEL or the photodiode shielded from radiation to determine which device was more susceptible to producing errors. In addition, we investigated the transient response of these devices to better understand the temporal characteristics that lead to the soft errors.

52723

Novel Micropreconcentrators for CW, Explosives, and Water Surety

R. P. Manginell, S. K. Showalter, R. J. Shul, D. R. Adkins, P. R. Lewis, S. S. Sokolowski, M. Moorman, R. Kottenstette, M. P. Siegal

Selective sample preconcentration is an essential step in microanalytical systems. Sandia's microfabricated planar preconcentrator concentrates semivolatile compounds, such as chemical warfare (CW) agents, and desorbs them rapidly. Unfortunately, chemical uptake is not as great as it could be due to surface-area limitations. In this project, Sandia is developing new micropreconcentrators (micro-PCs) that (1) increase uptake, (2) retain rapid desorption, and (3) broaden the applicable analyte set to include water quality/surety and explosives.

Thus far we have designed, fabricated, modeled, and tested two new types of high-surface-area micro-PCs. The first has a flow-through adsorbent support, which is fabricated on a free-standing membrane, allowing for high-efficiency collection, high throughput, and pressure insensitivity. Unoptimized, this design has desorption speeds at least 100x faster than conventional PCs, at one-tenth the power; compared with the planar PC, the flow-through design desorbs more slowly, but has significantly greater uptake and marginally higher power requirements. Simple design changes will increase desorption speed by approximately 4x while maintaining uptake of at least a factor of 2 over planar devices. In the second design, sample flow is parallel to the isolation membrane through heated fins. We are using multidomain finite-element modeling (FEM) to predict faster-desorbing designs.

We tested both designs with sol-gel adsorbents; they also allowed us to take advantage of commercial adsorbents such as Hayesep A, PoropackQ, etc. This has, in turn, improved our ability to concentrate CW agents, water contaminants (trihalomethanes [THMs]), and toxic industrial chemicals (TICs). We also demonstrated the use of a thin film of nanoporous, laser-ablated carbon as an adsorbent for THMs and TICs on our new designs. Whereas the planar PC was unsuccessful with explosives, the increased uptake of the new designs should permit success. We will study this next. We filed two technical advances on these ideas and prepared a patent application. These devices are allowing us to address lower concentrations and/or new analytes.

Thus far we have designed, fabricated, modeled, and tested two new types of high-surface-area micro-PCs. The first has a flow-through adsorbent support, which is fabricated on a free-standing membrane, allowing for high-efficiency collection, high throughput, and pressure insensitivity. Unoptimized, this design has desorption speeds at least 100x faster than conventional PCs, at one-tenth the power;....

We are developing new PCs, based on the use of a silicon-nitride (SiN) membrane for thermal isolation of an active, heated zone. We added three-dimensional (3-D) micromachined structures to the membrane's active zone to increase adsorptive-coating area. The 3-D support is thermally conductive for rapid heating and optimal chemical release.

We fabricated two kinds of 3-D PCs. A flow-through design (3DPCv1) utilizes concentric cylinders of Si as the 3-D adsorbent support. We created a process to etch holes through the center of the membrane to allow the sample to flow through the support. The second design (3DPCv2) uses "fins" of Si supported on the isolation membrane and protruding into the sample flow as the adsorbent support; here, flow is parallel to the membrane. Some devices have adsorbent packing stops. Thin glass lids with entrance/exit holes can be glued or anodically bonded over the fins to complete the sample channel. We also fabricated this device with a Si membrane, using silicon-on-insulator (SOI) instead of SiN-coated wafers. This rendition allows anodic bonding of interconnection tubes; we developed a method of anodic attachment of tubes. We completed a patent application on these designs.

Following microfabrication, adsorbents are applied to the support surface or are packed in its interior. We evaluated several techniques, including spray or drop coating of sol-gels, affixing commercial adsorbents into a PDMS (poly(dimethylsiloxane)) binder, packing with commercial adsorbents, and laser ablation of conformal nanoporous carbon films. PDMS binders and packing stops are important since they allow us to take advantage of commercial materials developed for TICs and THM compounds; materials tested include TenaxTA, Carboxen PorpackQ, and HaysepA.

We tested collection/desorption of the 3-D PCs using a benchtop gas chromatograph (GC) outfitted with a flame-ionization detector. Connecting the 3-D PCs to the GC required fixturing. For 3DPCv1, we built a miniature fixture; for 3DPCv2, we used glass lids. For CW agent response, we tested dimethyl methylphosphonate (DMMP). To evaluate TICs and THMs, we used furan, acrolein, acrylonitrile, methyl-vinyl ketone, and chloroform.

While the desorption peak width of the 3-D PC needs improvement, the collection capacity of the 3-D PC is superior to the planar device. The spacing of the individual supports in the 3-D PC, in contrast with the planar PC, can be tailored for improved performance. This feature, as well as the increased uptake of the 3-D PC, should compensate for the slower ramp rate of this device.

We fabricated two kinds of 3-D PCs....We completed a patent application on these designs.

We undertook multidomain FEM of the 3-D PC using ANSYS. We performed steady-state and transient electrothermal modeling for optimization purposes. We used steady-state (stagnant air, vacuum, and forced convection) and transient measurements for model validation. Typical t_{90} response of the flow-through 3-D PC is 0.6–1 s to 200°C, which is intermediate between the planar PC (~ 10 ms) and the conventional PC (~ tens of seconds). Now that the thermal model is performing well, we can predict improved designs. As a first attempt, we will study simply thinning the support walls since the initial designs had conservatively large supports. We will optimize support temperature uniformity and ramp rate while improving structural integrity. We are also performing mechanical modeling in ANSYS.

52724

Ion-Mobility Spectrometer/Mass Spectrometer*D. E. Austin, J. E. Parmeter, S. M. Thornberg, D. E. Hunka*

Sandia seeks to build an ion-mobility spectrometer/mass spectrometer (IMS/MS) system that will improve the trace detection of explosives and chemical/biological (C/B) materials. IMS detectors can quickly identify explosives or chemical agents from the location of the peaks in the IMS spectrum, but they do not provide information regarding the actual mass number of the species (ion) responsible for each peak. A typical spectrum has many peaks, and most of them are unidentified. A laboratory research instrument is needed that can determine the molecular makeup of the material that produces these peaks to reduce false alarms, improve detection limits, and develop multivariate analysis techniques for the quantitative discrimination of mixtures. A unique IMS development tool, to identify the mass number of peaks in the spectrum, will be provided by the integration of Sandia's IMS technology with an MS. We propose to design and build an interface that can take the ions from an IMS, introduce those ions into an MS to determine the mass number of those ions, and correlate the mass with a particular IMS spectral feature. Sandia currently has no capability to interface our state-of-the-art IMS systems (micro-IMS systems, Explosives Detection Personnel Portal, Explosives Detection Vehicle Portal, the Materials Access Area [MAA] Checkpoint, and Fourier-transform [FT] IMS) to an MS. Such a system would not only aid in the development and diagnostics of current IMS systems; it also would be invaluable in exploring alternative C/B targets that could be detected with an IMS instrument.

Work focused on the design and construction of the IMS/MS research instrument and preliminary system testing. We selected the IMS and MS instruments and developed an IMS/MS interface design based on a survey of previously developed IMS/MS systems. New Mexico State University (NMSU) has one of only a few scientists with extensive instrumental design experience in the development of IMS/MS systems. Based on his research and previous work of other groups, we selected a triple-quadrupole MS for the MS portion of the IMS/MS instrument. Selection criteria for the MS system included sensitivity, flexibility, reliability, and cost. We purchased and delivered the components of the triple-quadrupole MS. Based on the collaborative efforts with NMSU, the first IMS system that will be tested is a unit utilized in the Sandia-built

A laboratory research instrument is needed that can determine the molecular makeup of the material that produces these peaks to reduce false alarms, improve detection limits, and develop multivariate analysis techniques for the quantitative discrimination of mixtures. A unique IMS development tool, to identify the mass number of peaks in the spectrum, will be provided by the integration of Sandia's IMS technology with an MS....Such a system would not only aid in the development and diagnostics of current IMS systems; it also would be invaluable in exploring alternative C/B targets that could be detected with an IMS instrument.

explosives-detection portal. Work proceeded in the development of ion optics simulations to further refine the interface design and maximize the introduction of ions from the IMS to the MS. Interface design considerations include keeping it as flexible as possible to accommodate future research with other Sandia-built IMS systems such as the micro-IMS systems, Explosives Detection Personnel Portal, Explosives Detection Vehicle Portal, MAA Checkpoint, and FT IMS. Once the MS is operational and interfaced mechanically with the IMS, we will collect preliminary data and will document the system design plus our preliminary experimental results.

52725

Cryptographic Assurance of Execution Correctness and Confidentiality

L. G. Pierson, E. L. Witzke, K. W. Insch, T. D. Tarman, P. L. Campbell, P. J. Robertson, J. M. Eldridge

Today's general-purpose processors, based on Von Neumann architecture, allow the execution of any arbitrary sequence of instructions. This key to success is also a vulnerability, as malicious code can easily be substituted and executed. Also, programs that attempt to protect data from disclosure are fraught with difficulty since the keys and instructions used by the program to encrypt its data can be inspected and reverse-engineered.

Can cryptographic means be introduced into this architecture to restrict the execution of arbitrary instruction sequences to a single intended sequence of instructions? Furthermore, can cryptographic methods be incorporated that protect software-based encryption keys from disclosure, yet still allow cryptographic computations using these data?

Sandia will develop a processor that can execute code correctly, even if an adversary owns the processor. The processor guarantees both the integrity and the confidentiality of the code: The adversary cannot determine the sequence of instructions, nor can the adversary change the instruction sequence in a goal-oriented way.

Our approach differs from previous attempts in two ways. First, we use a "chaining" encryption/authentication mode, which detects instruction swapping. Second, we add redundant information, which detects intra-instruction bit manipulation.

The approach being investigated can be tailored to provide transparency (authentication only) and nontransparency (encryption and authentication), and for use with exportable algorithms. We are also investigating methods of "bootstrapping" the key generation and management to achieve transparency in an environment of mutual suspicion.

After simulating a simplified (JAVA™) version of such a processor, the next step is to implement our approach on a "real" hardware processor. This step will require resolution of difficulties presented by variable instruction size, encrypted cache operation, and protection through interrupt cycles. When perfected and incorporated into a single application-specific integrated circuit (ASIC), these techniques may also enable greatly improved protection of computer-controlled critical infrastructures.

Sandia will develop a processor that can execute code correctly, even if an adversary owns the processor. The processor guarantees both the integrity and the confidentiality of the code:....The approach being investigated can be tailored to provide transparency (authentication only) and nontransparency (encryption and authentication), and for use with exportable algorithms.

We currently are prototyping some components of the design.

We focused on the detailed design of a cryptographic system to protect instruction-stream confidentiality and sequence authenticity while coping with the complexities of variable-length instructions, conditional branches, subroutines, interrupts, caches, instruction pipelines, etc. To simplify this difficult problem, we chose to prototype these protections for a “reconfigurable hardware processor” in a programmable logic device (PLD), followed by a more extensive design to cope with the additional complexity of a modern Intel processor. We developed a hardware design to protect the instruction stream delivered to an Altera NIOS processor compiled into a state-of-the-art PLD. Our effort will result in the cryptographic “shrink-wrapping” of a simple software application and the demonstration of its protected execution on this initial reconfigurable hardware prototype.

After selecting “Plaintext Block Chaining” mode for encryption and for instruction-stream authentication, we devised multiple methods for synchronizing the decryption/authentication process at the targets of instruction branches. We analyzed trade-offs between speed, required memory space, and security. We chose a method suitable for processing control-flow branches, including conditional jumps, subroutines, and interrupts for implementation in the prototype.

We analyzed methods of encoding these data elements into a form suitable for prototype implementation and developed a design for the Altera NIOS reconfigurable processor. We have begun to implement a prototype of this design. As we implement this reconfigurable prototype, we are analyzing the additional features expected to be required to accommodate the more complex Intel-32 architecture and will incorporate them into a separate design document.

Refereed

Tarman, T. D., E. L. Witzke, and L. G. Pierson. 2002. On the use of trusted objects to enforce isolation between processes and data. *Proc. IEEE International Carnahan Conference on Security Technology* (21–23 October, Atlantic City, New Jersey).

Other Communications

Campbell, P. L., L. G. Pierson, and T. D. Tarman. 2003. Principles of Faithful Execution in the Implementation of Trusted Objects. Sandia Technical Report SAND2003-2328, Sandia National Laboratories, Albuquerque, New Mexico.

Campbell, P. L., L. G. Pierson, and T. D. Tarman. 2003. Prototyping Faithful Execution in a JAVA™ Virtual Machine. Sandia Technical Report SAND2003-2327, Sandia National Laboratories, Albuquerque, New Mexico.

52726

Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts

J. W. Martin, R. A. Anderson, M. C. Celina, R. A. Assink, S. T. Winters, G. D. Jones, D. M. Mowery, P. M. Chaplya, T. Dargaville, K. T. Gillen, J. L. Schroeder

Sandia is involved in a feasibility assessment of novel adaptive-optics systems with improved sensitivity and ground resolution for future space-based remote-sensing systems, for example, needed to monitor weapons of mass destruction (WMD) proliferation. This is a new enabling technology for large-aperture optics using thin piezoelectric polymer films based on polyvinylidene fluoride (PVDF). As a major achievement in related studies, we showed electron-gun-based control loops to successfully control the dimensional features of piezoelectric PVDF films. Equally important is to establish how PVDF materials will perform or change their characteristics in low-earth-orbit space environments. A comprehensive materials-performance study is absolutely critical since PVDF and copolymers will degrade or undergo changes when exposed to vacuum ultraviolet (UV) irradiation, thermal cycling, atomic oxygen, and other environmental factors. We are engaged in a broad assessment of various PVDF copolymers, in terms of understanding critical properties for piezo performance, correlating those with mechanical properties and predicting changes under long-term exposure conditions. Materials performance will depend on primary polymer properties (polymer manufacturer), thermal and processing history (film producer), and molecular orientation and poling technologies (piezoelectric optimization). There currently is no commercial material available that is optimized for the intended application. We are investigating the accelerated degradation of PVDF and exploring the fundamental dependence of piezo properties on molecular structure, morphology, and damage accumulation in radiation and temperature environments. We are attempting to quantify and simulate the expected space environments and understand the performance of artificially aged PVDF materials under electron-gun-control conditions. This project will deliver the materials science basis to select, optimize, and understand the properties of these unique polymers that have the potential to make large-diameter space-based adaptive optics a reality.

This is a new enabling technology for large-aperture optics using thin piezoelectric polymer films based on polyvinylidene fluoride (PVDF). As a major achievement in related studies, we showed electron-gun-based control loops to successfully control the dimensional features of piezoelectric PVDF films....This project will deliver the materials science basis to select, optimize, and understand the properties of these unique polymers that have the potential to make large-diameter space-based adaptive optics a reality.

We assembled an excellent team with broad backgrounds in polymer characterization, performance, degradation, and lifetime prediction, as well as expertise in piezo property characterization and measurement instrumentation and other specialized analytical support. Based on existing literature, we recognize the key issues affecting the performance of fluorinated polymers and expected damage in anticipated space environments and have explored all available polymer and piezo characterization methods. We established the broader framework for the most suitable piezo measurement methods. We purchased relevant instrumentation and other components designed to be set up and allow for rapid piezo performance monitoring. We obtained a full range of PVDF copolymers, manufactured films, and piezo sensors and characterized their chemical and physical properties. We conducted initial studies on piezo phase and detailed chemical/morphology analysis using x-ray diffraction and nuclear magnetic resonance with excellent results to justify future work. We correlated all PVDF property data and assessed them to develop the most sensitive approaches to monitor the aging of PVDF. We also engaged with piezo film manufacturers to use or incorporate some of their existing equipment and expertise for piezo property optimization issues. Access to a National Aeronautics and Space Administration (NASA) materials-selector database in space environments has been granted and will allow for better prediction of damage variables under different orbital conditions.

Refereed

Celina, M. C., J. W. Martin, R. A. Assink, P. M. Chaplya, S. T. Winters, and R. L. Clough. 2003. Characterization, performance, and optimization strategies for PVDF thin-film piezoelectric materials. Poster presented at Fluorine in Coatings Conference, Orlando, Florida.

63965

Hyperspectral Tagging for Unique Identification

H. A. Smartt

A hyperspectral tag can be embedded in a material without noticeably affecting the visual properties of the material, but can be detected with a spectrometer. Every object reflects, transmits, and absorbs photons differently, depending on wavelength. This variance can be considered a “spectral signature.” The combined material and tag will have a signature different from that of either alone. Sandia’s main objective in this research is to develop an algorithm to correctly and repeatedly identify an embedded tag in a material.

The tags were powdered minerals with “interesting” signatures in the near-infrared (NIR). The material was paint, specifically developed for application to metal surfaces. We combined the tags and materials in various concentrations and applied them to an aluminum background. We used an NIR spectrometer to collect multiple spectra from each combination for repeatability.

We applied an algorithm to the individual material and tags as well as to the various combinations to determine how well it seemed to model their signatures. The signature of white paint appeared similar for both the model and the collected data; however, the model for blue paint had a much higher reflectance in the middle of the NIR region than its collected signature and therefore had poor results. All tags appeared to have correct models. We calculated correlation coefficients to mathematically compare the signatures.

Having established that the algorithm correctly models the tags and the white paint, the next step was to use the correlation coefficient as a threshold for detection. The idea is that given an unknown spectrum, the correlation coefficient will be near unity if the spectrum is composed of the expected material and tag. If the spectrum is simply that of the material (or a different combination), the correlation coefficient should be lower than the threshold. We compared each tag/material combination with all other tag/material combinations and the materials alone. Unfortunately, the correlation coefficient did not prove useful. When seeking the tag in any white-paint sample, the correlation coefficient indicated a match both when the tag was present and when it was not. In the white paint alone, the correlation coefficient was near 99.99%. If the unknown spectrum consisted of the white paint and tag, the correlation coefficient

Sandia’s main objective in this research is to develop an algorithm to correctly and repeatedly identify an embedded tag in a material.

was near 99.3%. The correlation coefficient should have been higher when the unknown spectrum did indeed contain the expected tag. In cases where the unknown spectrum was blatantly different than expected, the correlation coefficient did indicate a mismatch. For example, if the unknown spectrum was blue paint and kaolinite, and the expected combination was white paint and kaolinite, the correlation coefficient was near zero. However, this is not a realistic scenario since visibly blue and white paints are different.

One possible reason for the high correlation coefficients of white paint and all tags is that the signatures were all similar in shape. Another possibility is that the model was not accurate due to the complex nature of the reflectance, which was not accounted for. The algorithm requires the reflectance to calculate dielectric constant, which is also a complex number. Determining the imaginary part of the reflectance is nontrivial and not well studied.

Hyperspectral tagging is certainly feasible. However, the model to determine the presence of the tag is not yet mature. The possible simple solution is to find a tag that is spectrally different from the material in the infrared (IR), but similar in the visible (so as not to change the appearance of the material). More complex solutions involve the current algorithm with the complex nature included, or nonlinear unmixing models.

63967

Fusing MSI and HSI Imagery for Subpixel Spectral Unmixing

J. L. Smith, C. M. Wehlburg, J. A. Mercier, M. R. Keenan, J. D. Schisler, J. P. Kern

Remotely sensed imagery obtained from space-based instruments inherently has a limitation in either spatial or spectral resolution. This limitation is not likely to be overcome until there is a significant advance in sensor technology. Hyperspectral sensors provide spectral resolution on the order of 10 nm and are capable of discerning many materials of interest, but their large ground sample distance (GSD) (30 m in the case of HYPERION) does not allow unmixing of materials on the scale of interest to most investigators. The multispectral thermal imager (MTI) has a 5 m GSD that is adequate for identification of smaller-scaled features, but lacks the spectral fidelity to identify specific materials in most cases. In this project, Sandia endeavored to use the multispectral imagery (MSI) with its superior GSD in conjunction with the hyperspectral imagery (HSI) to take advantage of the strengths of each.

To eliminate registration issues, we will use synthetic data for this project. The technical approach for this project is to constrain each 5 x 5 m subsection of a synthetic 30 m HYPERION pixel to meet the criteria taken from the corresponding 5 m MTI pixel. The final mixture result must meet the individual 5 m criteria and sum to match the spectra of the HYPERION 30 m pixel.

The expected result of this project is a proof-of-concept method and candidate algorithm that will provide superior spectral unmixing for large GSD hyperspectral data. In addition, the unmixed spectra HSI will be mapped to their appropriate location in the higher spatial resolution image.

Our aim in this work was to provide unmixing of an entire HSI. To eliminate the image-to-image registration issues, this study used synthetic data generated with Synthetic Scene Generation Model software. We generated four image cubes of the scene: 30 m HSI (210 spectral bands), 5 m MSI (10 spectral bands), and 1 m HSI (210 spectral bands), and 8-bit panchromatic 1 m imagery. We generated the hyperspectral data to mimic HYPERION data. The 5 m multispectral data mimicked MTI, and we used the 1 m data as ground truth. We wrote an unmixing algorithm called "MCR4SAT" in the Interactive Data Language. This language is used extensively

Sandia endeavored to use the multispectral imagery with its superior GSD in conjunction with the hyperspectral imagery (HSI) to take advantage of the strengths of each....The expected result of this project is a proof-of-concept method and candidate algorithm that will provide superior spectral unmixing for large GSD hyperspectral data.

by the remote-sensing community and offers built-in speed and optimization routines for large data arrays. This is a modified version of the robust Multivariate Curve Resolution–Alternating Least Squares algorithm written at Sandia and used in chemometrics.

This modified algorithm takes as its input an array of hyperspectral samples—a concentration/component matrix from the multispectral samples that make up each hyperspectral pixel. Each $n \times n$ multispectral area that corresponds to a single hyperspectral pixel must have an associated component, concentration, and spectral matrix. We did this using a windowing method on the result of unsupervised classification on the multispectral image. From this, we determined the number of components, their concentrations, and their multispectral spectra based on the number of pixels within the $n \times n$ window with the same spectral classification. Concentrations and components can be constrained to the input values; however, after testing we concluded that because these values are based on the preprocessing classification, they will require a bounded constraint.

The preprocessing step is important in determining the level of accuracy for materials that exist in the scene in very small quantities. We classified the multispectral data using an unsupervised method and used that information as the basis of the hyperspectral unmixing. Essentially, from the classification image, a concentration and component matrix can be created for each hyperspectral pixel from the aggregate information of the multispectral pixels that make up one hyperspectral pixel. Using the concentration and component matrix, and a multispectral spectrum for each component, the multispectral pixels with the same components from anywhere in the image can be input to the “MCR4SAT” software.

We wrote a module to constrain the solutions to the multispectral spectra, but have not integrated it into the general program.

During the research, we added two additional concepts. We realized that an ideal way to present the results of the unmixing is to create a new HSI with the resolution of the multispectral, 5 m image. We devised a mapping method to maintain the addresses of pixels represented in the mixture matrix.

The other concept developed during the work is “seeding.” Seeding is the act of providing one or more of the component hyperspectral spectra into the unmixing algorithm. There may be a small number of pure hyperspectral pixels within the scene. These pixels are identified in the multispectral classification image, and the corresponding hyperspectral spectra will be

We wrote an unmixing algorithm called “MCR4SAT”

in the Interactive Data Language. This language is used extensively by the remote-sensing community and offers built-in speed and optimization routines for large data arrays.

This is a modified version of the robust Multivariate Curve Resolution–Alternating Least Squares algorithm written at Sandia and used in chemometrics.

mapped into a known spectra matrix with their associated class number. For the cases where one or more of the components have already been identified, either as pure pixels or in a previous mixed-pixel iteration, the spectral matrix can be seeded with the known hyperspectral spectra. The software module for seeding is almost complete, but lacks rigorous testing.

We completed limited testing with good unmixing results. This path of research still looks very promising.

64214

Study of 3-D Focal-Region Sounding Applied to Large-Aperture Telescopes

M. W. Smith

Aperture size imposes, by way of diffraction, a fundamental limit on the spatial resolution that can be attained with an imaging system that operates at a given distance from a target. It is therefore natural to seek to improve image resolution by increasing the size of the collection aperture of a remote-sensing system. On the other hand, as aperture size increases it becomes technically more difficult, and financially much more expensive, to maintain a figure quality that holds geometrical aberrations to a level that is negligible compared to diffraction effects. In this project, Sandia investigated an approach that has been called a post-detection phase-diversity technique. The basic concept is to allow for variable focus as an inherent system capability to acquire multiple defocused images, each one of which has slightly different, and complementary, spatial-frequency content. The proper deconvolution and merging of these images produce a composite image that is superior to the image that can be acquired at any single focal setting. This project investigated the theoretical basis of this approach and completed numerical simulations that include the effects of noise and various levels of third-order spherical aberration.

...Sandia investigated an approach that has been called a post-detection phase diversity technique....This project investigated the theoretical basis of this approach and completed numerical simulations that include the effects of noise and various levels of third-order spherical aberration.

We completed the following work.

(1) We collected, read, and summarized 20 papers dealing with the topic of wavefront sensing by means of phase diversity and another 12 papers dealing with the topic of joint deconvolution of multiple images.

(2) We implemented some fairly simple point-spread function (PSF) calculations in MATLAB that rely on the standard approximations of scalar diffraction theory for the limiting case of the Fraunhofer regime. We treated defocus as a quadratic variation in phase as a function of normalized pupil coordinate. We considered only the ideal case of monochromatic illumination.

(3) We discovered a workable inversion algorithm during the course of the literature survey. This algorithm is a generalization of the standard Wiener-Helstrom inverse filter, extended to combine data from multiple images.

(4) We chose an Ikonos image of the Washington, D.C., mall area as a representative scene for modeling purposes. We based noise levels on radiometric calculations for a system in low-earth orbit with a 1 m-diameter primary mirror.

(5) We performed modeling simulations in which the amount of spherical aberration and the signal-to-noise were both varied. We chose a set of four defocus settings and performed all the simulations with these same four settings. We tried out various algorithms to select the number of defocus settings and the amounts of defocus automatically, but the final image-restoration results did not appear to be any better than the results produced by our initial four settings, which were chosen “by eye” to make the modulation transfer function (MTF) as flat as possible.

(6) We presented the results of the work in the “Novel Optical System Design and Optimization VI” session of the SPIE conference held in San Diego.

We drew three main conclusions from this work.

(1) Three-dimensional (3-D) focal region sounding is neither a completely new nor highly speculative concept. Rather, it is closely related to the established technique of phase-diversity imaging. However, our concept of tailoring the number and type of diverse images to ameliorate specific aberrations and optimize the system MTF does appear to be a new idea.

(2) Diversity imaging alone will probably not be able to compensate for more than a few waves, probably less than 10 waves, of aberration. Basically, once the MTF falls below the noise floor for a given system, it does not matter what image-restoration techniques one attempts to apply; one will only “amplify the noise.” For this reason we advocate a three-tier system that would consist of a large, but highly aberrated primary, plus some active optics for partial wavefront correction, plus a diversity-imaging scheme.

(3) Based on very cursory numerical studies of coma, and based on the insight that we gained working with spherical aberration, we now believe that simple defocus (quadratic phase diversity) will be effective only for “even” aberrations, such as field curvature, spherical aberration, and astigmatism. In all of these cases, the focal point varies longitudinally along the optical axis as a function of either pupil coordinate or field coordinate. Longitudinal defocus (quadratic phase diversity) thus brings different zones of the pupil or field into sharp focus. However, for “odd” aberrations such as coma, the focal point is displaced laterally, or transverse to the optical axis, as a function of pupil coordinate. In such cases, defocus will only make the MTF worse at all spatial frequencies. Some type of nonquadratic phase diversity will almost certainly be required to address “odd” aberrations such as coma.

Three-dimensional (3-D) focal region sounding is neither a completely new nor highly speculative concept. Rather, it is closely related to the established technique of phase-diversity imaging. However, our concept of tailoring the number and type of diverse images to ameliorate specific aberrations and optimize the system MTF does appear to be a new idea.

Other Communications

Smith, M. W. 2003. Simulated performance of an optical system that uses deconvolution of multiple, phase-diverse, aberrated images. *Proc. SPIE Annual Meeting* **5174-9** (August, San Diego, California).

64215

Affordable, Automated Computed Tomography (CT) X-Ray Screening for Large Vehicle Bombs Preliminary Study

J. A. Hunter, M. M. Selph, G. J. Lockwood, L. B. Bishop

Sandia designed and fabricated a scaled-down tractor-trailer to model a fixed gantry of x-ray beams and detectors using an existing x-ray system at Sandia. We fabricated a simple aluminum (Al) box 6 in. square by 12 in. long to model a tractor-trailer. We filled the Al box with wood and one cylinder of brass and one cylinder of plastic. The plastic cylinder represents a volume of an explosive in a mixed-cargo container. We took transmission and backscatter x-ray images at various x-ray energies. We rotated the Al box along its long axis from 0–180 deg in 15 deg increments. At each of these rotational angles, we recorded two-dimensional (2-D) x-ray images by scanning the model under the x-ray tube. We combined these x-ray images to form one computed tomography (CT) image. Although the CT image resolution is quite low, the difference in material densities of the Al box, the wood cargo, and the brass cylinder is observable.

Further research is called for to image the difference in plastic densities and further refine the number of fixed x-ray tubes and detectors.

(1) Build a model to determine the feasibility of a fixed gantry system of x-ray beams and detectors that can automatically generate a set of CT images to screen for large vehicle bombs. We demonstrated a model that can generate transmission and backscatter x-ray and CT images of a mixed cargo. We imaged the size and density of different materials, but they are not shown as a function of suspicious densities.

(2) Determine if lower-resolution (i.e., large voxel, a 3-D pixel) images can distinguish materials with very different absorption coefficients. We demonstrated that low-resolution CT images can distinguish materials of different mass-absorption coefficients. More research is required in enhancing the reconstructed CT images, especially around the plastic explosive simulant.

(3) Determine if CT images provide better information than a standard transmission image for automated explosives detection. We demonstrated that orthogonal transmission x-ray images show the size and position of mixed cargos. More research is needed to say how much more information is

A depiction of a fixed gantry of x-ray beams and detectors to detect large vehicle bombs.

Sandia designed and fabricated a scaled-down tractor-trailer to model a fixed gantry of x-ray beams and detectors using an existing x-ray system at Sandia. ...Further research is called for to image the difference in plastic densities and further refine the number of fixed x-ray tubes and detectors.

available in a CT image over a transmission x-ray image, especially as a function of suspicious densities.

- *Review of the risks/issues.*

- Does a CT image produce additional information not available in commercial transmission x-ray systems?

Although only one CT image has been made from this experiment, it does show more information than a conventional transmission x-ray, even though it is at a low resolution. The difference in density is evident in mixed cargos. A simple transmission x-ray can show whether there is a difference in a written manifest, but not the exact size and position of suspicious densities.

- How many beams and detectors are needed to produce an image with minimal resolution to detect large volumes of explosives?

More research is needed to fully answer this question. If an x-ray tube generates a fan beam, then possibly only two or three x-ray tubes are needed. Our research shows that the 1 ft-sized plastic scintillation detectors with photomultiplier tubes (PMTs) would work fine as detectors, but the final number of detectors is not yet firm.

Although only one CT image has been made from this experiment, it does show more information than a conventional transmission x-ray, even though it is at a low resolution. The difference in density is evident in mixed cargos. A simple transmission x-ray can show whether there is a difference in a written manifest, but not the exact size and position of suspicious densities.

64355

Coordinated Weapon-Platform Control Strategies for Intelligent Targeting

C. L. Nelson, J. J. Carlson

Sandia focused on developing algorithms that detect, track, and prioritize multiple targets and coordinate the control of multiple weapon platforms to eliminate all threats and to ensure the safety of protected assets. Currently, most weapon platforms are used for long-range target engagements in exterior environments. In this project, we emphasized close-quarter engagements, where it is very difficult for a single weapon to eliminate all threats before being overtaken. The approach taken was to leverage the previous intelligent targeting developments as well as previous developments in decentralized cooperative control.

The first task was to identify risk functions for optimization purposes in cooperative control. Optimal platform control strategies use probabilistic models developed in previous intelligent targeting work that convey the probability of hitting a target from a given platform in terms of target size, position, and motion relative to the platform, as well as ballistic characteristics of ammunition being used.

The second task involved the development of cooperative control algorithms that optimize the risk functions developed in the first task.

The third task was to implement the algorithms on the prototype intelligent targeting platforms. A two-platform prototype system was available for algorithm testing. The threat environment consisted of a target gallery made up of eight pop-up targets. The targets were controlled with a separate system that could randomly pop up from one to eight targets at a time. Targets could also pop up individually or in combinations with a random amount of time in between. This was a sufficient arrangement to test the optimization solutions.

The innovation behind this project was to extend the development efforts that have so far involved only a single platform firing on a single target. The focus was to develop algorithms that detect, track, and prioritize multiple targets and coordinate the control of multiple weapon platforms to eliminate all threats and to ensure the safety of protected assets. Currently, most weapon platforms are used for long-range target engagements in exterior environments. In this project, we emphasized close-quarter engagements, where it is very difficult for a single weapon to eliminate all threats before being

Sandia focused on developing algorithms that detect, track, and prioritize multiple targets and coordinate the control of multiple weapon platforms to eliminate all threats and to ensure the safety of protected assets. Currently, most weapon platforms are used for long-range target engagements in exterior environments. In this project, we emphasized close-quarter engagements, where it is very difficult for a single weapon to eliminate all threats before being overtaken.

overtaken. The approach taken was to leverage the previous intelligent targeting developments as well as previous developments in decentralized cooperative control.

The first task was to identify risk functions for optimization purposes in cooperative control. Optimal platform control strategies use probabilistic models developed in previous intelligent targeting work that convey the probability of hitting a target from a given platform in terms of target size, position, and motion relative to the platform as well as ballistic characteristics of ammunition being used.

The second task involved the development of cooperative control algorithms that optimize the risk functions developed in the first task.

The third task was to implement the algorithms on the prototype intelligent targeting platforms. A two-platform prototype system was available for algorithm testing. The threat environment consisted of a target gallery made up of eight pop-up targets. The targets were controlled with a separate system that could randomly pop up from one to eight targets at a time. Targets could also pop up individually or in combinations with a random amount of time in between. This was a sufficient arrangement to test the optimization solutions.

64356

Advanced Weapons Signatures

L. A. Boye, A. M. Renlund, J. D. Corey, M. R. Hagan, M. J. Kaneshige, M. M. Hoffman, M. S. Oliver, C. O. Schmidt, II, D. L. Green

Sandia is nationally recognized for its expertise in detection of transient electrooptical events. Sandia has over 25 years' experience in performing optical measurements against explosive events and applying these measurements to operational systems built by Sandia. Advanced weapons enhance blast overpressure conditions and produce localized atmospheric oxygen depletion. Explosive chemistry differs from that of conventional explosives and may alter observable signatures. The materials used in these systems burn brighter and longer than do conventional explosives. This project proposes to measure the optical signatures of highly advanced energetic materials (EMs) for subsequent discrimination techniques from other explosive events.

Under previous research, we conducted measurements and collections against preliminary calibration events at the Explosive Components Facility (ECF). Thus far, these measurements show promise for scaling with prior exterior explosive events. The deployment of radiometric systems against the thermobarics tests will present a rare and unique opportunity for Sandia to extend empirical model development and data analysis to advanced weapons systems. This project will support radiometric monitoring of these ECF events, in addition to the monitoring of exterior field tests.

The use and proliferation of advanced weapons is of interest to the U.S. military and to nonproliferation and intelligence communities. Models developed at Sandia were employed successfully to identify specific information about conventional explosive events. This project will attempt to test and extend these models to advanced weapons systems and to help in defining an extensive investigation of signature collections for future collection systems enhancements.

Sandia's ECF performed thermobaric testing and conducted a special series of interior-chamber, confined-configuration, low-yield, thermobarics events. The operations of these tests were already being funded by Defense Threat Reduction Agency (DTRA). In this project, Sandia took advantage of this ongoing testing series and conducted the radiometric optical measurements and collections against these events. Preliminary calibration events at the ECF helped to establish a radiometric

This project proposes to measure the optical signatures of highly advanced energetic materials (EMs) for subsequent discrimination techniques from other explosive events....The deployment of radiometric systems against the thermobarics tests will present a rare and unique opportunity for Sandia to extend empirical model development and data analysis to advanced weapons systems.

“piggy-back” test procedure and configuration. In addition to leveraging the opportunity to piggy-back on some of the scheduled DTRA-funded tests, this project extended the ECF testing series and provided for additional advanced weapons tests of various explosives for comparative baselining of the thermobaric events. The deployment of the radiometric optical equipment provided a unique complement to the ECF’s established suite of imaging, radio-frequency (RF), temperature, pressure, pyrometry, and other measurements, since they were not doing radiometric monitoring. The radiometric monitoring contributed additional temporal validation for event-signature characterization and event-anomaly tracking for the variety of explosive materials tested. We conducted more than 40 events comprising C-4, Comp-B, tritonal, and advanced weapons materials, including thermobarics. The events ranged in size from 50 to 700 gm. All explosions took place in the confined chamber, both in air and in an evacuated environment with nitrogen. We collected the optical data with single-element, narrow-bandwidth filtered radiometers ranging in wavelength from 0.485 μm to 3.5 μm .

The optical data collected from the chamber tests with conventional explosives scaled well with empirical models of optical signatures collected with conventional explosive events conducted in air. The advanced weapons, thermobarics signatures, were sufficiently distinct in magnitude and temporal character from the conventional explosives to show potential for signature discrimination.

We compiled the raw data results and images from all of the ECF test series, including the optical signatures collected under this project, and added them to a master database structure developed and maintained at Sandia. This database is accessible on the Sandia Restricted Network (SRN) extra-net. The radiometrically calibrated optical data are incorporated into a Microsoft Access/Visual Basic database called the Self-Contained Data Retrieval System (SCR). The SCR, developed by Sandia and Los Alamos Technical Associates (LATA) for automatic data storage and retrieval as a function of an explosive test event, runs on a stand-alone computer. The SCR contains descriptive information about the events with comprehensive search capability and empirical algorithms for calibration, comparison, analysis, and scaling of the optical radiometric signatures. The SCR includes data from the various series of open-air and now ECF-chamber explosive events optically monitored by Sandia.

In addition to the small-yield, interior ECF collections, we completed this project using funding for “piggy-back”

The deployment of the radiometric optical equipment provided a unique complement to the ECF’s established suite of imaging, radio-frequency (RF), temperature, pressure, pyrometry, and other measurements, since they were not doing radiometric monitoring. The radiometric monitoring contributed additional temporal validation for event-signature characterization and event-anomaly tracking for the variety of explosive materials tested.

collections against some exterior testing. DTRA conducted explosive events at Chestnut Range, Kirtland Air Force Base (KAFB), New Mexico; the tests comprised a series of 5–50 lb conventional explosives and thermobarics material in a variety of geometrical and physical configurations. We collected optical signals and video images with the assistance of personnel from Sandia, LATA, Computer Sciences Corporation (CSC), and Sandia Video Services.

Opportunities for additional radiometric signal collections of thermobaric and conventional testing will continue to be available. These tests include a possible Sandia ECF test series and several exterior events planned by various government agencies, such as local tests at KAFB and White Sands by DTRA. We collected a significant set of optical signatures and recommend the publication of a classified report documenting the specific measurements, analysis, and results.

64385

Universal Detection for Chem-Bio Sensing in Microfluidic Systems

J. A. Fruetel, A. McIlroy, B. A. Horn, D. A. V. Kliner

One of the biggest challenges continuing to plague development of biowarfare-agent (BWA) detectors is automating and integrating sample preparation, a time-consuming and complex process requiring specialty reagents. Significant savings in detector-development time and cost could be realized using a detection method that requires neither reagents nor predetection sample processing. Currently, microfluidic chem-bio sensors such as μ ChemLabTM employ laser-induced fluorescence (LiF) detection of dye-labeled biomolecules to detect BWA levels as low as 1–10 ng/ml. This method requires fluorescent tagging of target species. Sandia seeks to develop a miniature near-infrared (NIR) absorption cell based on cavity-ringdown spectroscopy to detect proteins (present in all BWAs) at sensitivities comparable to LiF without the need for dye labeling. Cavity ringdown was developed at Sandia for in situ combustion monitoring and remote gas sensing with detection sensitivities greater than or equal to competing spectroscopic methods, including LiF. The proposed system would use commercially available, low-cost, communications diode-laser technology. To test the concept, we would partially immerse a fiber cavity in the liquid sample and monitor absorption of the evanescent wave at the fiber surface. Application of the absorption cell to microfluidic separations could then be evaluated for a set of test proteins.

We focused primarily on developing expertise in design of fiber-ringdown cavities for microfluidic applications and scoping the most important design parameters for the ultimate implementation of the method.

We performed detailed analysis of fiber cavities, including determining the dependence of finesse and transmittance on various fiber parameters (loss, angle of end-facets, coating reflectivity, mode-field diameter, etc.). Following this analysis, we procured appropriate fibers from multiple manufacturers to determine the utility of commercially finished fibers. For selected fibers, we determined flatness of end-facets. We then measured the finesse of fiber cavities with uncoated faces using a tunable, narrow-linewidth (single-longitudinal mode), external-cavity diode laser operating at ~ 1550 nm, a wavelength appropriate for detecting protein absorbance in the ultimate device. We compared these finesse measurements with

Sandia seeks to develop a miniature near-infrared (NIR) absorption cell based on cavity-ringdown spectroscopy to detect proteins (present in all BWAs) at sensitivities comparable to LiF without the need for dye labeling.

the flatness measurements and with calculations. We found good agreement between the calculations and measurements, giving us confidence in our fiber-cavity model. This analysis pointed out that the critical parameter for commercial fibers is the angle of the fiber entrance and exit faces to the fiber core. We identified commercial sources with tight-enough angle tolerances for this application, alleviating the need for custom polishing.

To fabricate fiber cavities in-house, we developed and demonstrated methods for gold-coating fiber end faces to provide known reflectivity. Using this method, we fabricated several fiber cavities with a range of values for the finesse and with two values of the free-spectral range. We measured the finesse and free-spectral range of the fiber cavities and compared these measurements with calculations. We found good agreement between the predicted and measured values. The maximum finesse achieved was 32 (i.e., ~ 100 optical passes in 3 e-folding times of the cavity).

To understand the interaction of the evanescent wave with a surrounding fluid environment, we began calculating the dependence of evanescent field on fiber parameters (numerical aperture, thickness of cladding, etc.). We identified a commercial optics modeling code, implemented it for this purpose, and undertook initial design calculations.

We established a collaboration with others at Sandia, who are developing a method that enables expansion of separation channels in microfluidic devices to create wide, shallow regions without loss in separation efficiency. Together, we developed strategies to couple fiber-based evanescent-field cavity-ringdown detection with wide-channel microfluidic designs to enable high-sensitivity absorbance detection in microfluidic separation devices. The combination of fiber-ringdown detection and the wide-channel architecture would achieve on-chip absorption pathlengths of at least 1 m. With this pathlength we anticipate that detection levels equal to or better than those achieved by LiF are possible without the need to tag the analyte.

...we developed strategies to couple fiber-based evanescent-field cavity-ringdown detection with wide-channel microfluidic designs to enable high-sensitivity absorbance detection in microfluidic separation devices. The combination of fiber-ringdown detection and the wide-channel architecture would achieve on-chip absorption pathlengths of at least 1 m. With this pathlength we anticipate that detection levels equal to or better than those achieved by LiF are possible without the need to tag the analyte.

65148

Multipurpose Locator-Tag System

D. Greenway, Jr., G. R. Schuster, D. S. Blair

Fissile-material inventories have become the subject of an increasing number of international treaties and agreements. The monitoring and inspection (M&I) regimes for many of these agreements are still being negotiated. Whereas the treaties and agreements may have originally been negotiated based on arms-control concerns, it is now recognized that they present a valuable tool in the nonproliferation arena as well. For both objectives, arms control and nonproliferation, material accounting and control is a vital issue. Due to multilateral concerns about proliferation and the growing concern of non-nation states obtaining fissile material, introduction of new technologies into an M&I regime is now possible. There is increased need for robust non-line-of-sight tags on materials that can be used to monitor location at distances through walls and building structures.

With the intrinsically high radiation associated with the storage of large quantities of fissile materials, the use of human monitors becomes problematic due to risks to the monitors. Human intervention in the storage and inventory activities raises the risk of material diversion and theft.

The tag-reading system to be evaluated uses the industrial, science, and medical (ISM) radio-frequency (RF) bands, minimizing export-control issues. The frequency bands are 2.4 GHz and 5.8 GHz, much higher than most tags fielded in the past. These frequencies have very short wavelengths for penetrating structures, combined with the use of spread-spectrum signals to reduce the effects of multipathing and interference. The use of multiple antennas and software enhancements allows the system interrogation of tags at longer ranges compared to conventional tags. The tags receive a signal at one frequency and respond on another, and the determination of exact positions is based on signal timing and delays. Sandia will perform actual field testing of various deployment scenarios.

We set up and tested a commercial radio-frequency identification (RFID) locator system and determined the limitations and accuracy of the equipment for a typical building. The system accuracy was less than expected. With adequate complement of equipment, this system could cover a large area (approximately 250,000 sq ft) with a resolution of 10 ft x 10 ft. This could locate or place a tag to within a small room or zone.

Due to multilateral concerns about proliferation and the growing concern of non-nation states obtaining fissile material, introduction of new technologies into an M&I regime is now possible. There is increased need for robust non-line-of-sight tags on materials that can be used to monitor location at distances through walls and building structures....Sandia will perform actual field testing of various deployment scenarios.

We found the range and accuracy of this indoor tag-location system to be less than required for our task. However, this system would be adequate for a number of applications needing only general location and movement data.

Sandia has expertise in microelectronics and signal processing. Application of these talents could add value to the system, e.g., increased location accuracy, longer range, and longer battery life.

Sandia has expertise in microelectronics and signal processing. Application of these talents could add value to the system, e.g., increased location accuracy, longer range, and longer battery life.

66159

Creative Networking of Commercial Products

T. Q. Thai, D. Loffredo

This is a classified report.

66160

Networked Device Demonstration*J. M. Childs, Z. L. Lovelady, T. Q. Thai, W. R. Cordwell*

Networks allow applications to utilize the resources provided by all the devices connected to that network. This work is part of Sandia's larger goal to facilitate the collaboration of a diverse set of lightweight devices not typically considered as platforms for network routing. Typical networks require duplex links between all nodes in a network. However, in some cases, such as radio networks, nodes may be connected only by Simplex links. A new routing protocol called the Sun Lego Universal Routing Protocol (SLURP), developed in previous work, can utilize Simplex links. The protocol also discovers and supports routing in ad hoc networks. The ad hoc network requirement forces the protocols to continue to function even when less-capable devices occupy important nodes in the network. For the protocol to reach its maximum potential, the design of this implementation had to be carefully considered so that it could be easily ported to devices with differing architectures and link technologies. The resulting architecture allowed the protocol to be implemented easily on a heterogeneous set of hardware devices and link technologies in a physical demonstration network.

This project demonstrated that SLURP can support collaborative applications across *ad hoc* networks with Simplex links using lightweight devices in a heterogeneous environment. As part of this larger goal, we made several key accomplishments. First was the porting of the code to a diverse set of computing platforms, including the 186, 386, MIPS 300, and 686 processor platforms running on operating systems (OSs), including @CHIP-RTOS, DOS, Linux, and Windows XP. This demonstrated that the SLURP protocol could work seamlessly across a diverse set of computing platforms. We designed the software code that interacted with OSs and hardware to simplify porting the protocol. This design work facilitated the addition of multiple-link layer technologies like serial or Ethernet with point-to-point or broadcast connections. This initial work will expedite the addition of further platforms and connections. We created an example collaborative application to demonstrate the capabilities of SLURP. The application allows devices in the SLURP to advertise their resources and to facilitate their use by other devices on the network. We utilized these example collaborative applications along with built-in metric gathering tools to demonstrate the

This work is part of Sandia's larger goal to facilitate the collaboration of a diverse set of lightweight devices not typically considered as platforms for network routing. ...For the protocol to reach its maximum potential, the design of this implementation had to be carefully considered so that it could be easily ported to devices with differing architectures and link technologies. The resulting architecture allowed the protocol to be implemented easily on a heterogeneous set of hardware devices and link technologies in a physical demonstration network.

capabilities and performance of collaborative networks created with this system.

66161

Analysis of Multichannel Internet Messaging

C. E. Nove, M. P. Beede, J. D. Sonnek, R. F. Maclin, C. O. Rogers

This is a classified report.

Grand Challenges

The Grand Challenges investment area investigates innovative ideas with the potential for dramatically impacting national-level concerns and for creating technologies and processes required for the twenty-first century. Grand Challenges engage lab-wide multidisciplinary research teams that establish critical mass in participation and funding to focus on world-class research. High-risk, potentially outrageous ideas are considered for investigation. In addition, all Grand Challenges research efforts must identify linkage to supporting Sandia's business goals.

Understanding and protecting against biological weapons is a major concern for homeland security. *Interfacial Bioscience Grand Challenge (IBIG)* may result in new ways to detect biotoxins and drugs that will block them. This investigation is trying to understand the mechanisms of "signaling and intoxication" through which biological agents, such as anthrax or botulism, might enter a body's cells and try to kill them. Researchers are using methods for determining protein structure with mass spectrometry; a suite of novel scanning-probe microscopes to image structure and dynamics;

and state-of-the-art membrane-simulation capabilities using massively parallel computers to model the proteins' conformation and interactions. IBIG is directed toward developing new technologies for analyzing the interactions of cell membrane systems, which should catalyze a substantial leap forward, creating a unique niche for Sandia in biotechnology. One patent disclosure has been filed.

27328

A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting

J. M. Gee, D. M. Follstaedt, A. A. Allerman, J. P. Wilcoxon, S. R. Kurtz, R. P. Pawlowski, G. R. Hadley, R. M. Biefeld, J. R. Wendt, R. L. Simpson, A. J. Fischer, G. H. Evans, D. D. Koleske, A. G. Salinger, K. H. A. Bogart, N. A. Missert, D. R. Tallant, A. F. Wright, G. M. Peake, C. C. Mitchell, M. E. Coltrin, C. H. Seager, H. K. Moffat, W. C. Sweatt, J. R. Creighton, R. J. Shul, E. D. Jones, J. A. Emerson, J. J. Figiel, K. E. Waldrip, J. Y. Tsao, S. A. Kemme, W. W. Chow, M. P. Moran, K. Leung, L. E. S. Rohwer

Solid-state optical devices provide a new method for producing white light for general-purpose illumination at efficiencies far higher than existing conventional light sources. Lighting accounts for around 20% of all electricity consumption. The conversion to high-efficiency (~ 50% at the wall plug) solid-state lighting has the potential to improve energy security and energy efficiency, to reduce environmental impact by reducing energy consumption, and to provide jobs in a large industry. The core semiconductor technology (alloys of indium-aluminum-gallium-nitride [In-Al-Ga-N]) is also of interest for a variety of national security applications (e.g., ultraviolet [UV] light-emitting diodes [LEDs] for bioagent detection, high-power high-frequency electronics, etc.). Sandia is assisting in the development of a technology roadmap on solid-state optical devices (LEDs and vertical-cavity surface-emitting lasers [VCSELs]) for lighting applications. There is significant interest in establishing a national research program in solid-state lighting. The proposed Next-Generation Lighting Initiative would fund solid-state lighting research at \$480M over 10 years.

A solid-state white-light source suitable for general-purpose illumination will need (1) improved LED and/or VCSEL efficiency to the 50% range across the visible spectrum, (2) improved white-light generation and packaging using LEDs, and (3) two-orders-of-magnitude reduction in cost through, for example, improved metal-organic chemical vapor deposition (MOCVD) growth. The goal of this Grand Challenge project is to establish the fundamental science and technology base that, according to the Next-Generation Lighting Initiative roadmap, will be required for this vision of ultraefficient solid-state illumination to become a reality. In so doing, we will position Sandia to be the national leader in these areas, and thus to play a major role in the Next-Generation Lighting Initiative. We anticipate that this will result in substantial additional future

The goal of this Grand Challenge project is to establish the fundamental science and technology base that, according to the Next-Generation Lighting Initiative roadmap, will be required for this vision of ultraefficient solid-state illumination to become a reality. In so doing, we will position Sandia to be the national leader in these areas, and thus to play a major role in the Next-Generation Lighting Initiative.

program development funding to Sandia. Further, and perhaps more importantly, this endeavor will also result in the development of infrastructure and associated synergistic technology of vital importance for national security needs.

(1) *(Al,In)GaN materials physics*. Extending our comprehensive model of hydrogen (H) dynamics in GaN, we identified the dominant magnesium (Mg)-H bonding configuration, identified a surface energy barrier to H out-diffusion, and showed that it can be reduced by annealing in reactive ambients.

(2) *Low-defect epitaxy and substrates*. We further refined our cantilever epitaxy (CE) technique for defect reduction in GaN grown on sapphire. We identified mechanisms that produce “block dark defects” in CE and developed methods to eliminate them. We also applied reflectance monitoring to develop a model of nucleation layer evolution and used it to improve control and repeatability of our nucleation process.

(3) *III-nitride MOCVD growth chemistry*. We used *in situ* laser scattering to discover the formation of InN, GaN, and AlN nanoparticles and modeled their formation. We began experiments to probe these nanoparticles *in situ*. Also, we identified the adduct origin of Mg “memory effects” in MOCVD reactors and began mapping reactor growth conditions to alleviate them.

(4) *In situ MOCVD process monitors*. We improved our UV pyrometry technique for substrate temperature measurement by adding emissivity correction and decreasing the minimum temperature from 900°C to 750°C.

(5) *UV LEDs*. We demonstrated a 1.3 mW LED at 290 nm, roughly 10x the previous world record. For visible LEDs, we improved the yield of our flip-chip process for 2x light extraction, improving the reflective *p*-type metallization. Also, we evaluated CE substrates and demonstrated a decreased temperature dependence of blue LEDs grown on them. Finally, we demonstrated good-quality 400 nm LEDs on the Emcore reactor.

(6) *Luminescent materials*. We fabricated the world’s first quantum-dot (QD)–based LED, which used CdS nanocrystalline QDs as phosphors. We demonstrated a white LED using an ensemble of QDs synthesized in a single step and a QD world-record 60% quantum efficiency.

...this endeavor will also result in the development of infrastructure and associated synergistic technology of vital importance for national security needs.... We demonstrated a 1.3 mW LED at 290 nm, roughly 10x the previous world record.... We fabricated the world’s first quantum-dot (QD)–based LED, which used CdS nanocrystalline QDs as phosphors. We demonstrated a white LED using an ensemble of QDs synthesized in a single step and a QD world-record 60% quantum efficiency.

Refereed

- Bogart, K. H. A., D. D. Koleske, A. A. Allerman, A. J. Fischer, K. W. Fullmer, K. C. Cross, and C. C. Mitchell. 2003. Effects of surface modification on n- and p-type GaN ohmic contacts. *Applied Physics Letters* or *J. Vacuum Science and Technology*, to be submitted.
- Chow, W. W., H. C. Schneider, and M. C. Phillips. 2003. Theory of quantum interference phenomena in semiconductor quantum dots: Frequency upconversion in InGaN. *Physical Review A*, in preparation.
- Coltrin, M. E., and C. C. Mitchell. 2003. Mass transport and kinetic limitations in MOCVD selective-area growth. *J. Crystal Growth* **254**:35–45.
- Creighton, J. R., W. G. Breiland, M. E. Coltrin, and R. P. Pawlowski. 2002. Gas-phase nanoparticle formation during AlGaIn MOVPE. *Applied Physics Letters* **81**:2626.
- Gee, J. M., J. Y. Tsao, and T. E. Drennen. 2003. Potential impact of new energy-efficiency technologies on global climate change: The example of solid-state lighting. *Mitigation and Adaptation to Global Change, An International Journal Devoted to Scientific, Engineering, Socio-Economic and Policy Responses to Environmental Change*, submitted.
- Hader, J. J., V. Moloney, S. W. Koch, and W. W. Chow. 2003. Microscopic modeling of gain and luminescence in semiconductors. *IEEE Special Issue on Quantum Electronics*.
- Inoki, C., T. Kuan, C. Lee, R. Feenstra, D. D. Koleske, D. Diaz, P. Bohn, and I. Adesida. 2003. Growth of GaN on porous SiC and GaN substrates. *J. Electronic Materials*, submitted.
- Koleske, D. D., A. J. Fischer, A. A. Allerman, C. C. Mitchell, S. R. Kurtz, J. J. Figiel, and K. W. Fullmer. 2002. Improved UV LED brightness with 3-D GaN nucleation grains on sapphire. *Applied Physics Letters* **81**:1940.
- Koleske, D. D., M. E. Coltrin, A. A. Allerman, K. C. Cross, C. C. Mitchell, and J. J. Figiel. 2003. *In situ* measurements of GaN nucleation layer decomposition. *Applied Physics Letters* **82**:1170.
- Myers, S. M., and C. H. Seager. 2003. Hydrogen isotope exchange and the surface barrier in p-type gallium nitride. *J. Applied Physics*, submitted.
- Oila, J., K. Saarinen, A. Wickenden, D. D. Koleske, R. Henry, and M. Twigg. 2003. Ga vacancies and grain boundaries in GaN. *Applied Physics Letters* **82**:1021.
- Provencio, P. P., D. M. Follstaedt, N. A. Missert, D. D. Koleske, C. C. Mitchell, A. A. Allerman, and C. I. H. Ashby. 2002. Characterization of “dark-block” defects in cantilever epitaxial GaN on sapphire. *Proc. Fall 2002 Materials Research Society Symposium* **743**.
- Rohwer, L. E. S., and A. M. Srivastava. 2003. Development of phosphors for LEDs. *Interface* (Electrochemical Society).
- Schneider, H. C., W. W. Chow, P. M. Smowton, E. J. Pearce, and S. W. Koch. 2003. Many-body effects in quantum-dot lasers. (Invited) *Proc. Photonics West 2003 Conference* (25–31 January, San Jose, California).
- Seager, C. H., S. M. Myers, A. F. Wright, D. D. Koleske, and A. A. Allerman. 2003. Drift, diffusion and trapping of hydrogen in p-type GaN. *J. Applied Physics*, submitted.

Shul, R. J., R. D. Briggs, K. H. A. Bogart, A. J. Fischer, D. D. Koleske, A. A. Allerman, S. Jones, C. C. Mitchell, and C. Sanchez. 2003. High-density plasma etching of wide-bandgap materials. Vugraphs presented at MRS Spring Meeting, 22–25 April, San Francisco, California.

Tsao, J. Y. 2003. Solid-state lighting: Lamp targets and implications for the semiconductor chip. *Proc. 2003 International GaAs MANTECH Conference* (19–22 May, Scottsdale, Arizona).

Tsao, J. Y. 2003. The U.S. “LEDs for general illumination 2002” roadmap. *Laser Focus World* (June).

Wampler, W. R., and S. M. Myers. 2003. Hydrogen release from magnesium-doped GaN with clean ordered surfaces. *J. Applied Physics*, submitted.

Wright, A. F., C. H. Seager, S. M. Myers, D. D. Koleske, and A. A. Allerman. 2003. Hydrogen configurations, formation energies, and migration barriers in GaN. *J. Applied Physics*, submitted.

Other Communications

Allerman, A. A., A. J. Fischer, D. D. Koleske, K. H. A. Bogart, R. J. Shul, and S. R. Kurtz. 2002. MOCVD growth of AlGa_N alloys for 300 nm LEDs. Paper presented at the 2002 Fall Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.

Allerman, A. A., A. J. Fischer, D. D. Koleske, K. H. A. Bogart, R. J. Shul, S. R. Kurtz, J. J. Figiel, K. C. Cross, and K. W. Fullmer. 2003. MOCVD growth and performance of light-emitting diodes for 300 nm emission. Paper presented at Photonics West, 25–31 January, San Jose, California.

Allerman, A. A., A. J. Fischer, M. H. Crawford, K. H. A. Bogart, R. J. Shul, D. D. Koleske, S. R. Lee, and S. R. Kurtz. 2003. Growth and characterization of AlGa_N alloys for 290–300 nm light-emitting diodes. Paper presented at the 11th Biennial Workshop on OMVPE, 20–24 July, Keystone, Colorado.

Allerman, A. A., and D. D. Koleske. 2003. Thermal annealing of sapphire for GaN epitaxy. Technical advance disclosure SD-7226/S99851.

Allerman, A. A., R. M. Biefeld, D. M. Follstaedt, D. D. Koleske, C. C. Mitchell, N. A. Missert, P. P. Provencio, and L. E. S. Rohwer. 2003. Development of key technologies for white lighting on light-emitting diodes (LEDs). Quarterly Technical Report—Q3Y1, Sandia National Laboratories.

Allerman, A. A., R. M. Biefeld, W. G. Breiland, R. D. Briggs, M. E. Coltrin, J. R. Creighton, K. C. Cross, J. J. Figiel, D. M. Follstaedt, D. D. Koleske, N. A. Missert, C. C. Mitchell, A. Ongstad, P. P. Provencio, L. E. S. Rohwer, and K. E. Waldrip. 2003. Development of key technologies for white lighting based on light-emitting diodes (LEDs). Quarterly Technical Report—Q4Y1, Sandia National Laboratories.

Biefeld, R. M., A. A. Allerman, K. H. A. Bogart, J. R. Creighton, J. A. Emerson, D. M. Follstaedt, D. D. Koleske, C. C. Mitchell, N. A. Missert, P. P. Provencio, L. E. S. Rohwer, S. G. Thoma, G. Wang, and J. Wilcoxon. 2003. Development of key technologies for white lighting based on light-emitting diodes (LEDs) technical report—budget period 1. Technical Report (LumiLeds).

Bogart, K. H. A., C. C. Mitchell, K. C. Cross, R. D. Briggs, and C. I. H. Ashby. 2003. Plasma etching of sapphire. Technical advance disclosure, Sandia National Laboratories (May).

Bogart, K. H. A., D. D. Koleske, A. A. Allerman, A. J. Fischer, K. W. Fullmer, K. C. Cross, and C. C. Mitchell. 2002. Effects of LED processing steps on the surface of GaN epilayers. Paper presented at the AVS International Symposium, 4–8 November, Denver, Colorado.

Bogart, K. H. A., M. H. Crawford, A. J. Fischer, D. D. Koleske, K. W. Fullmer, F. Jalali, R. J. Shul, and S. Jones. 2003. Plasma processing-induced contact defects in high % n-type AlGaIn for UVLEDs. Paper presented at the Tri-Services DARPA Workshop, 17–21 August, Grants Pass, Oregon.

Bogart, K. H. A., M. H. Crawford, A. J. Fischer, D. D. Koleske, K. W. Fullmer, F. Jalali, R. J. Shul, S. Jones, I. Adesida, and D. Selvanathan. 2003. Investigations of plasma etching and contact processing on AlGaIn alloys containing 0 to 50% Al. Paper presented at the 50th AVS International Symposium, 3–7 November, Baltimore, Maryland.

Chow, W. W. 2002. Wide-bandgap group-III nitride semiconductor lasers. (Invited) Paper presented at the OSEP Optics Seminar, University of Colorado, 21 October, Boulder, Colorado.

Coltrin, M. E., and C. C. Mitchell. 2002. Mass transport and kinetic limitations in GaN epitaxial lateral overgrowth. Paper presented at the 2002 Fall Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.

Coltrin, M. E., C. C. Mitchell, and D. D. Koleske. 2003. Gallium nitride crystal facet evolution and kinetics. Paper presented at the 39th Symposium of the NM Chapter of the AVS, 29–30 April, Albuquerque, New Mexico.

Crawford, M. H., A. A. Allerman, A. J. Fischer, K. H. A. Bogart, D. D. Koleske, W. W. Chow, S. R. Kurtz, and S. R. Lee. 2003. Progress and challenges in the development of AlGaIn-based deep-UV light emitters. (Invited) Paper presented at the Impurity-Based Electroluminescence in Wide-Bandgap Semiconductors Workshop, 13–16 April, Santa Fe, New Mexico.

Creighton, J. R., G. T. Wang, M. E. Coltrin, and W. G. Breiland. 2003. Nature of the parasitic chemical reactions occurring during AlGaIn OMVPE. Paper presented at the 15th American Conference on Crystal Growth and Epitaxy, 20–24 July, Keystone, Colorado.

Creighton, J. R., W. G. Breiland, and M. E. Coltrin. 2002. Gas-phase nanoparticle formation during AlGaIn MOCVD. Paper presented at the AVS 49th International Symposium, 4–8 November, Denver, Colorado.

Creighton, J. R., W. G. Breiland, and M. E. Coltrin. 2002. Parasitic reactions and particulate formation during AlGaIn MOCVD. Paper presented at the National Meeting of the American Institute of Chemical Engineers, 3–8 November, Indianapolis, Indiana.

Creighton, J. R., W. G. Breiland, and M. E. Coltrin. 2003. Sources of the parasitic chemical reactions during AlGaIn OMVPE. Paper presented at LumiLeds Lighting, 26 March, San Jose, California.

Cross, K. C., K. H. A. Bogart, C. C. Mitchell, and R. D. Briggs. 2003. Plasma etching of cantilever epitaxy sapphire substrates. Paper presented at the 50th AVS International Symposium, 3–7 November, Baltimore, Maryland.

- Eichler, C., D. Hofstetter, and W. W. Chow. 2003. Microsecond timescale lateral mode dynamics in a narrow-stripe InGaN laser. Paper presented at CLEO 2003, 1–6 June, Baltimore, Maryland.
- Follstaedt, D. M., D. D. Koleske, C. C. Mitchell, N. A. Missert, A. A. Allerman, and P. P. Provencio. 2003. Developing cantilever epitaxy of GaN for advanced devices. Paper presented at 2003 EMC, 25 June, Salt Lake City, Utah.
- Follstaedt, D. M., N. A. Missert, C. C. Mitchell, K. C. Cross, and D. D. Koleske. 2003. Counting dislocations in GaN: Contrast in TEM, AFM and CL. Paper presented at the NM Chapter of AVS 39th Symposium, 28–30 April, Albuquerque, New Mexico.
- Follstaedt, D. M., P. P. Provencio, D. D. Koleske, N. A. Missert, C. C. Mitchell, C. I. H. Ashby, and A. A. Allerman. 2002. Cantilever epitaxy of GaN on sapphire: Further reductions in dislocation density. Paper presented at the 2002 Fall Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.
- Gee, J. M. 2003. What the PV specialists might like to know about solid-state lighting. Paper presented at the National Center for Photovoltaics and DOE Solar Program Review Meeting, 24–26 March, Denver, Colorado.
- Gee, J. M., J. Y. Tsao, and J. A. Simmons. 2003. Fundamental science initiatives to enable the solid-state lighting revolution. Paper presented at the LED 2002 Conference, Intertech, 21–23 October, San Diego, California.
- Gee, J. M., J. Y. Tsao, and J. A. Simmons. 2003. Solid-state lighting research at Sandia National Laboratories. Paper presented at the Workshop on Solid-State Lighting, Georgia Institute of Technology, 9–20 February, Atlanta, Georgia.
- Gee, J. M., J. Y. Tsao, and J. A. Simmons. 2003. The role of GaN semiconductors in the solid-state lighting revolution and synergisms with national security. Paper presented at the 2003 Military Sensing Symposium, Materials Specialty Group, 24–28 February, Tucson, Arizona.
- Gee, J. M., S. Y. Lin, J. G. Fleming, and J. B. Moreno. 2003. Energy applications of photonic crystals. Paper presented at Photonic and Electromagnetic Crystals–IV (PECS–IV), UCLA, 29–31 October, Los Angeles, California.
- Kaplar, R. J., S. R. Kurtz, D. D. Koleske, and A. J. Fischer. 2003. Electroreflectance studies of stark-shifts and polarization-induced electric fields in InGaN quantum wells. Paper presented at 2003 EMC, 25–27 June, Salt Lake City, Utah.
- Koleske, D. D., A. A. Allerman, A. J. Fischer, M. H. Crawford, K. H. A. Bogart, and S. R. Kurtz. 2003. Development of group IIIA/group IIIB nitride quantum wells for brighter 550–590 nm light-emitting diodes. Technical Advance disclosure SD-7459/S-102,188 (May).
- Koleske, D. D., A. J. Fischer, A. A. Allerman, C. C. Mitchell, K. C. Cross, S. R. Kurtz, J. J. Figiel, K. W. Fullmer, and W. G. Breiland. 2002. Improved brightness of 380 nm GaN light-emitting diodes through intentional delay of the nucleation island coalescence. Technical advance disclosure SD-7301/S100358 (October).
- Koleske, D. D., M. E. Coltrin, A. A. Allerman, K. C. Cross, C. C. Mitchell, J. J. Figiel, and M. J. Russell. 2003. GaN nucleation evolution on sapphire. Paper presented at the 50th International Symposium of the AVS Science and Technology Society, 2–7 November, Baltimore, Maryland.

Koleske, D. D., M. E. Coltrin, K. C. Cross, C. C. Mitchell, A. A. Allerman, and J. J. Figiel. 2003. GaN nucleation layer evolution on sapphire before high-temperature growth. Paper presented at the 15th American Conference on Crystal Growth and Epitaxy, 20–24 July, Keystone, Colorado.

Koleske, D. D., M. E. Coltrin, S. R. Lee, K. C. Cross, C. C. Mitchell, A. A. Allerman, and J. J. Figiel. 2002. Toward quantification of GaN film evolution of sapphire. Paper presented at the 2002 Fall Materials Research Society Meeting, 2–6 December, Boston, Massachusetts.

Lee, S. R., W. G. Breiland, and D. D. Koleske. 2003. The effect of film-thickness nonuniformity on *in situ* wafer-curvature measurements of thin-film stress. Paper presented at the 2003 APS March Meeting, 3–7 March, Austin, Texas.

Mitchell, C. C. 2003. Defect reduction in gallium nitride using cantilever epitaxy. Master's Thesis, University of New Mexico Electrical Engineering Department, Albuquerque, New Mexico (4 April).

Mitchell, C. C., D. D. Koleske, D. M. Follstaedt, N. A. Missert, K. H. A. Bogart, K. C. Cross, M. E. Coltrin, and A. A. Allerman. 2003. Defect reduction in gallium nitride using cantilever epitaxy. Paper presented at the 39th Symposium of the New Mexico Chapter of the AVS, 29–30 April, Albuquerque, New Mexico.

Mitchell, C. C., D. D. Koleske, D. M. Follstaedt, N. A. Missert, P. P. Provencio, A. A. Allerman, and M. E. Coltrin. 2003. Understanding GaN growth evolution in cantilever epitaxy yields improved material. Paper presented at the 15th American Conference on Crystal Growth and Epitaxy, 20–24 July, Keystone, Colorado.

Myers, S. M., W. R. Wampler, C. H. Seager, B. L. Vaandrager, D. D. Koleske, and A. A. Allerman. 2002. Influence of ambient on surface-inhibited H release from P-GaN. Paper presented at the 2002 Fall Meeting of the Materials Research Society, 2–6 December, Boston, Massachusetts.

Rohwer, L. E. S., and J. P. Wilcoxon. 2003. Characterization of II-VI semiconductor nanocrystals for solid-state lighting applications. (Invited) Paper presented at the Nanomaterials for Aerospace Symposium, January, Corpus Christi, Texas.

Rohwer, L. E. S., J. P. Wilcoxon, B. L. Abrams, S. M. Woessner, and S. G. Thoma. 2003. Semiconductor quantum dots for white-light generation. Paper presented at the 203rd Electrochemical Society Meeting, 27 April–2 May, Paris, France.

Schneider, H. C., W. W. Chow, and S. W. Koch. 2003. Influence of coupling between localized and continuum states in quantum-dot systems. Paper presented at Nonlinear Optics and Excitation Kinetics in Semiconductors (NOEKS), 24–28 February, Karlsruhe, Germany.

Seager, C. H., D. R. Tallant, A. F. Wright, J. Yu, and W. Götz. 2003. Luminescence behavior of GaN co-doped with Si and C. Paper presented at the 2003 Spring Materials Research Society Meeting, 21–25 April, San Francisco, California.

Shul, R. J., R. D. Briggs, K. H. A. Bogart, A. J. Fischer, D. D. Koleske, A. A. Allerman, and C. C. Mitchell. 2003. High-density plasma etching of wide-bandgap materials. Paper presented at the 2003 Spring Materials Research Society Meeting, 21–25 April, San Francisco, California.

Simmons, J. A. 2002. Fundamental science needs for solid-state lighting, basic energy sciences on basic research needs to assure a secure energy future.” (Invited) Paper presented at the Workshop for the Office of Science, 22 October, Gaithersburg, Maryland.

Simmons, J. A. 2002. Research at Sandia in solid-state lighting technologies. (Invited) Seminar at General Electric Corporate Research and Development, 25 September, Schenectady, New York.

Simmons, J. A. 2003. Solid-state lighting research at Sandia National Laboratories. (Invited) Paper presented at the 203rd Electrochemical Society Meeting, 27 April–2 May, Paris, France.

Simmons, J. A. 2003. The next-generation lighting initiative. (Invited) Paper presented at the Phosphor Global Summit 2003, 19–21 March, Scottsdale, Arizona.

Tsao, J. Y. 2003. Materials issues in solid-state lighting. (Invited) Paper presented at the AVS 50th International Symposium, 2–7 November, Baltimore, Maryland.

Tsao, J. Y. 2003. Science and technology challenges in solid-state lighting. (Invited) Paper presented at the Workshop on Selective, Patterned and Self-Assembled Growth in Nanostructures, 6–8 January, Hong Kong, China.

Tsao, J. Y. 2002. The U.S. solid-state lighting roadmap: Targets and technical challenges. (Invited) Paper presented at the 2002 OIDA Annual Forum, 20 November, Washington, D.C.

Tsao, J. Y. 2003. The U.S. solid-state lighting roadmap: Targets and technical challenges. (Invited) Paper presented at the 2003 International Conference on Compound Semiconductor Manufacturing Technology, 19–22 May, Scottsdale, Arizona.

Tsao, J. Y., D. C. Meister, and A. E. Miksovic. 2003. Solid-state lighting Website 2003 update. <http://lighting.sandia.gov>.

Wang, G. T., and J. R. Creighton. 2003. Adduct formation chemistry between magnesocene (MgCp_2) and NH_3 : Origin of the “memory effect.” Paper presented at the 15th American Conference on Crystal Growth and Epitaxy, 20–24 July, Keystone, Colorado.

Wang, G. T., and J. R. Creighton. 2003. Adduct formation chemistry between magnesocene (MgCp_2) and NH_3 : Origin of the “memory effect.” Paper presented at the 39th Symposium of the NM Chapter of the AVS, 29–30 April, Albuquerque, New Mexico.

Wang, G. T., and J. R. Creighton. 2003. Complex formation between magnesocene (MgCp_2) and NH_3 : Origin of the “memory effect.” Paper presented at the 50th AVS International Symposium, 3–7 November, Baltimore, Maryland.

Wang, G. T., and J. R. Creighton. 2003. Identification of the adducts formed between magnesocene (MgCp_2) and NH_3 : Origin of the “memory effect.” Paper presented at the 2003 TMS Electronic Materials Conference, 25–27 June, Salt Lake City, Utah.

West, A. M., S. R. Lee, A. A. Allerman, D. D. Koleske, S. R. Kurtz, K. E. Waldrip, J. J. Figiel, and C. Abernathy. 2003. Correlation between threading dislocation density and mobility of GaN-based HEMTs. Paper presented at 2003 EMC, 25–27 June, Salt Lake City, Utah.

Wilcoxon, J. P., L. E. S. Rohwer, and P. P. Provencio. 2003. Optical properties of II-VI and IV semiconductor nanoclusters for use as phosphors. (Invited) Paper presented at the 203rd Electrochemical Society Meeting, 27 April–2 May, Paris, France.

Wright, A. F. 2002. Using density-functional theory to help understand the behavior of defects in wurtzite GaN. (Invited) Paper presented at Texas Tech University, 7 November, Lubbock, Texas.

Wright, A. F., C. H. Seager, S. M. Myers, D. D. Koleske, and A. A. Allerman. 2003. Hydrogen drift, diffusion and trapping in p-type GaN. Paper presented at the 2003 Spring Materials Research Society Meeting, 21–25 April, San Francisco, California.

Wright, A. F., C. H. Seager, S. M. Myers, D. D. Koleske, and A. A. Allerman. 2003. Hydrogen drift, diffusion and trapping in p-type GaN. Paper presented at the 39th Symposium of the NM Chapter of the AVS, 29–30 April, Albuquerque, New Mexico.

28776

Interfacial Bioscience Grand Challenge (IBIG)

J. S. Schoeniger, R. C. Hughes, J. Hong, T. W. Lane, P. S. Crozier, M. D. Rintoul, D. Y. Sasaki, S. L. Rempe, J. M. Faulon, M. Z. Hadi, R. B. Jacobsen, A. K. Singh, A. Slepoy, K. O. Evans, M. M. Young, M. J. Stevens, S. P. Maharrey, R. Behrens, Jr., A. R. Burns, S. M. Brozik, J. A. Whaley, P. Lane, L. J. D. Frink, R. J. Bastasz, C. B. Troup, A. M. Highley, G. H. Kruppa

Sandia focused on developing bioanalytical tools for elucidating structure-function relationships in membrane proteins (MPs). IBIG was motivated by the need to improve understanding of structure-function issues in MPs, the inadequacy of current methods, and the importance of MPs in processes, such as pathogenesis and intoxication, relevant to the action of biological agents. Despite significant progress in recent years, there is no compelling evidence that the majority of MPs will be amenable to analysis using standard structure tools (x-ray crystallography, nuclear magnetic resonance [NMR]). IBIG was originally technology focused and was structured into three technology development cores: structure, imaging, and simulation.

IBIG's first external advisory committee (EAC) recommended that we restructure the project to introduce a greater biology focus, as well as aggressively hire and pursue outside collaborations with biological scientists. The second EAC report strongly endorsed our technical results and progress in establishing our biology infrastructure, terming our approach "very powerful" and "unique." The report recommended that the project further focus on a specific proof-of-principle biological problem offering clear-cut validation of our methods. Based on this recommendation, the project focused principally on bovine rhodopsin as a target MP. We demonstrated that new cross-linking and mass spectrometry (MS) methods could obtain numerous constraints on interatomic distances in rhodopsin, and we developed several new cross-linking chemistries and MS techniques. We demonstrated that our molecular modeling software could resolve the transmembrane bundle structure of this protein based solely on bioinformatic considerations and distance constraints derivable from cross-linking experiments. Finally, we published state-of-the-art massively parallel molecular dynamics (MD) simulations of rhodopsin. Based on these accomplishments, the third EAC concluded that we had "developed leading-edge scientific methodologies...in a most difficult area...." The report went on

This graphic shows interatomic distances found to be spanned by chemical cross-linkers on the cytoplasmic face of rhodopsin. Lysine-to-lysine distances are shown in blue and lysine-to-cysteine distances in orange.

...we published state-of-the-art massively parallel molecular dynamics (MD) simulations of rhodopsin. Based on these accomplishments, the third EAC concluded that we had "developed leading-edge scientific methodologies...in a most difficult area...."

to state, “The approach that you are pioneering has real potential to add a better understanding of the dynamic fluctuations in MP structure, which, until now, have been by necessity treated as static structures.”

Through our work on IBIG, we created new approaches to problems in MP structure and function studies. We demonstrated that chemical cross-linking and probes of protein surface reactivity, combined with modern MS methods, can be used to measure interatomic distances in MPs. We also created novel MS methods and new cross-linking chemistries. To utilize the intermolecular constraint data generated by cross-linking methods, and to investigate the information content of cross-link-based constraints, we developed new software for modeling MP structures and implemented a massively parallel MD code for atomistic simulation of MPs.

IBIG demonstrates that a significant number of constraints could be obtained from an MP using the model protein rhodopsin. The basic approach to deriving interatomic distance constraints in proteins using chemical cross-linking is to expose the native protein to a cross-linker of defined length, and then to cleave the protein into peptides and determine which atoms in which peptides are joined by a cross-linker of a given backbone length. This establishes an upper bound on the distance of closest approach of these atoms. Our results generalize earlier work on soluble proteins that demonstrated that the distance constraints obtained by this approach (known as the MS3D method) can be used to filter out incorrect structural models. Because MS3D experimental methods are quite labor-intensive, we also developed (and submitted for patent) a top-down approach that simplifies the MS3D analysis by using electrospray ionization mass spectrometry (ESI-MS) directly on the cross-linked reaction product mixture, followed by fragmentation and mobility spectrometer/MS (MS/MS) analysis on protein ions containing a cross-link to localize the cross-link position. This top-down method eliminates the need for monomer separation, proteolytic digestion, and high-performance liquid chromatography (HPLC)/MS on the proteolytic peptides. Results show that the top-down method can provide distance constraints derived from cross-links for small proteins. We have now demonstrated a variety of cross-linking chemistries including lysine, cysteine, tyrosine, arginine, and acidic amino-acid residues.

Computational work in IBIG demonstrated that an approach similar to that in the original MS3D publication will work for defining the geometry of the transmembrane helix bundle (HB) in MPs. Assembling HBs requires searching the conformational

Through our work on IBIG, we created new approaches to problems in MP structure and function studies. We demonstrated that chemical cross-linking and probes of protein surface reactivity, combined with modern MS methods, can be used to measure interatomic distances in MPs. We also created novel MS methods and new cross-linking chemistries....we developed new software for modeling MP structures and implemented a massively parallel MD code for atomistic simulation of MPs.

space of the HBs subject to both experimental and theoretical constraints between its component helices. We demonstrated a three-stage approach for building HBs from a set of distance constraints and secondary structure elements (SSEs) comprising the following steps:

(1) Screen a library of greater than 100,000 possible structures satisfying a set of theoretical considerations to extract those satisfying the experimental distance constraints.

(2) Score the remaining structures using a function that penalizes structures for not satisfying distance constraints and for deviation from “average” MP properties determined from a survey of existing structures.

(3) Refine the best structures by rigid rotation and translation of the SSEs to minimize their score.

Our results show that the number of structures decreases exponentially with increasing number of distances, and increases exponentially with increasing errors on the distance increases. For seven helix MPs, at least 15 distances with errors less than 8 Å are needed to produce a number of solutions that is small enough to be processed by our refinement procedures. We also developed a scoring function based on an *ad hoc* coarse-grained force field, validated it using a test set of five known transmembrane (TM) protein structures, and showed that the higher the score, the farther a structure is from its target structure.

To investigate the structural dynamics of rhodopsin, and to relate cross-links and interatomic distances, we modified Sandia’s Large-Scale Atomic/Molecular Massively Parallel Simulator (LAMMPS) code to make it compatible with molecular simulation methods and protocols widely accepted in the computational biology community. We performed a 40 ns simulation of dark-adapted rhodopsin in a lipid bilayer surrounded by water. This represents state-of-the-art simulation capability and enables simulations of the strain energy of cross-link formation, allowing interpretation of cross-link kinetics data.

To investigate the structural dynamics of rhodopsin, and to relate cross-links and interatomic distances, we modified Sandia’s Large-Scale Atomic/Molecular Massively Parallel Simulator (LAMMPS) code to make it compatible with molecular simulation methods and protocols widely accepted in the computational biology community. We performed a 40 ns simulation of dark-adapted rhodopsin in a lipid bilayer surrounded by water. This represents state-of-the-art simulation capability and enables simulations of the strain energy of cross-link formation, allowing interpretation of cross-link kinetics data.

Refereed

Bondurant, B., J. A. Last, T. A. Waggoner, A. Slade, and D. Y. Sasaki. 2003. Optical and scanning-probe analysis of glycolipid reorganization upon Concanavalin A binding to Mannose-coated lipid bilayers. *Langmuir* **19**:1829–37.

Burns, A. R. 2003. Domain structure in model membrane bilayers investigated by simultaneous atomic-force microscopy and fluorescence imaging. *Langmuir* **19**:8358–63.

Crozier, P. S., M. J. Stevens, and T. B. Woolf. 2003. 40 ns molecular dynamics simulation of rhodopsin in an explicit DOPC bilayer. Paper presented at the Biophysical Society Symposium, San Antonio, Texas.

Crozier, P. S., M. J. Stevens, L. R. Forrest, and T. B. Woolf. 2003. Molecular dynamics simulation of dark-adapted rhodopsin in an explicit membrane bilayer: Coupling between local retinal and larger-scale conformational change. *J. Molecular Biology* **333**:493–514.

Faulon, J. L., K. Sale, and M. M. Young. 2003. Exploring the conformational space of membrane protein folds matching distance constraints. *Protein* **12**:1750–61.

Huber, T. A., A. Slade, J. A. Last, B. Bondurant, and D. Y. Sasaki. 2003. Lectin and neurotoxin interactions with glycolipid membranes as monitored by liposome leakage studies. Paper presented at the American Chemical Society National Meeting, New York, New York.

Jang, H., P. S. Crozier, M. J. Stevens, and T. B. Woolf. 2003. Molecular dynamics simulations of two structurally defined intermediates in the bacteriorhodopsin photocycle. Paper presented at the Biophysical Society Symposium, San Antonio, Texas.

Kruppa, G. H., J. S. Schoeniger, and M. M. Young. 2003. A top-down approach to protein structural studies using chemical cross-linking and Fourier-transform mass spectrometry. *Rapid Communications in Mass Spectrometry* **17**:155–62.

Novak, P., G. H. Kruppa, J. S. Schoeniger, and M. M. Young. 2003. A top-down approach to protein structural studies using chemical cross-linking and Fourier-transform mass spectrometry. Paper presented at ASMS, 8–12 June, Montreal, Canada.

Novak, P., G. H. Kruppa, M. M. Young, and J. S. Schoeniger. 2003. A top-down method for the determination of residue-specific solvent accessibility in proteins. *J. Mass Spectrometry*, accepted.

Novak, P., M. M. Young, J. S. Schoeniger, and G. H. Kruppa. 2003. A top-down approach to protein structure studies using chemical cross-linking and Fourier-transform mass spectrometry. *European J. Mass Spectrometry*, accepted.

Schilling, B., M. M. Young, G. Dollinger, and R. K. Guy. 2003. Isotopically labeled cross-linking reagents: Resolution of mass degeneracy in the identification of cross-linked peptides. *Bioorg. Med. Chem. Lett.*, accepted.

Schoeniger, J. S., R. B. Jacobsen, G. H. Kruppa, P. Novak, M. Ayson, P. Lane, K. Sale, and M. M. Young. 2003. Exploring the structure and dynamics of rhodopsin using chemical cross-linking and LC/MS. Paper presented at ASMS, Montreal, Canada.

Slade, A., D. Y. Sasaki, T. Waggoner, A. Burns, and C. Yip. 2003. Nanoscale imaging of biological toxin-lipid bilayer interactions by scanning-probe microscopy. Paper presented at the Biophysical Society Symposium, 1–5 March, San Antonio, Texas.

Young, M. M., P. Novak, G. H. Kruppa, and J. S. Schoeniger. 2003. A top-down approach to residue specific solvent accessibility and reactivity studies on proteins. Paper presented at ASMS, Montreal, Canada.

Young, M. M., P. Novak, J. S. Schoeniger, and G. H. Kruppa. 2002. Identification of protein folds by MS3D. Paper presented at ACS, Boston, Massachusetts.

41193

Biomicrofuel Cell

C. A. Applebitt, C. J. Cornelius, C. H. Fujimoto, D. B. Fein, B. A. Simmons, K. R. Zavadil, C. L. Staiger, A. R. Straumanis, J. H. Flemming, S. K. Eisenbies, S. M. Brozik, S. H. Kravitz, D. W. Peterson, M. H. Beggans, K. Wally, A. W. Walker, M. J. Kelly, D. Ingersoll, M. Okandan, R. A. Kemp

Sandia will develop new, compact power sources that can directly and efficiently convert biological fuels, such as glucose or sucrose, into electricity. This project addresses the need for new, autonomous power supplies for chem-bio and ground-based sensor platforms, communications, and microelectronics applications. While current fuel cells have demonstrated clear advantages over batteries in energy density, they still rely on fuels such as hydrogen or methanol that may be inconvenient for many applications. We will develop fuel-cell technologies with biological systems as the renewable energy source. The challenges facing biofuel cells include (1) design of a high-power-density, low-power (< 10 mW) fuel cell compatible with biofuels, (2) preparation of mechanically stable, embossable polymer electrolyte membranes (PEMs), (3) engineering the appropriate biological interface, (4) development of long-lived, precious-metal or enzymatic electrodes that will completely oxidize the biofuel, (5) design, preparation, and integration of new fuel and oxidant-selective membranes, and (6) integration of the complete system. This project was recognized by its External Advisory Committee (EAC) as being unique in its systems approach to biofuel cells. They also recognized that the project is poised to yield significant and broadly applicable advances in (1) PEMs and (2) new electrocatalysts that will help realize a U.S. hydrogen economy, (3) innovative microfuel cell and biomicromachine architectures, and (4) more sophisticated and robust enzymatic systems. We propose to increase the focus on new PEMs, accelerate the discovery of long-lived electrocatalysts, improve the energy utilization of biofuels, and drive toward a versatile biofuel-cell system. Furthermore, to provide a power supply for chem-bio weapon and ground-based sensor platforms, we are proposing a modified, more aggressive project structure that will yield a working prototype biofuel cell by the end of the fiscal year.

We assembled a small fuel cell based on current methanol catalysts that showed power levels up to 270 mW/cm^2 at room temperature. A bipolar stack of six cells generated 0.8 W of power on 1 sccm of hydrogen and 3 sccm of oxygen, in a 2.6

This project was recognized by its External Advisory Committee (EAC) as being unique in its systems approach to biofuel cells. They also recognized that the project is poised to yield significant and broadly applicable advances in (1) PEMs and (2) new electrocatalysts that will help realize a U.S. hydrogen economy, (3) innovative microfuel cell and biomicromachine architectures, and (4) more sophisticated and robust enzymatic systems.

cm³ volume. We tested single cells at room temperature using 1 molar glucose solutions and showed them to generate up to 0.54 mW/cm² of power, again at room temperature. By making the glucose fuel supply high in pH (by the addition of KOH), we achieved powers of up to 0.74 mW/cm².

We developed new membrane materials that are superior to the commercially available Nafion® developed by DuPont. We fabricated membrane resistances of up to 99 m Siemens/cm² (as opposed to Nafion®'s 80 m Siemens/cm²) and tested them in fuel-cell systems using hydrogen/oxygen and methanol/oxygen. We achieved power densities higher than 760 mW/cm² at 80°C, approximately a factor of 2 better than Nafion®.

Enzyme-based catalysts for the air side of the fuel cell showed a power density of up to 2 mW/cm², and we developed a new methodology for immobilization and “wiring” of these enzymes to the cathode that improved the current collection rate of the cathodes. We also investigated lifetime of the enzyme catalysts, with the air-side enzymes running for up to 21 days at 5 mA/cm² with only nominal degradation in performance.

We fabricated microneedle-based harvesters for use on animal hosts, and several experiments on plant-based harvesting showed both the viability of the approach and the technical challenges of engineering a single solution for many different plant species. We completed system-level engineering of a multicell array capable of breathing ambient air, and initial tests on this planar array architecture showed an open circuit performance of 4.2 V.

Refereed

Beggans, M. H., S. H. Kravitz, C. P. Tigges, J. H. Flemming, K. A. Peterson, G. Benavides, D. Ingersoll, T. P. Swiler, and M. Griffith. 2003. Monopolar fuel-cell array with chaotic mixing chevrons for using plant-derived sugars as fuel. *Proc. Electrochemical Society Fall 2003 Meeting*, accepted.

We developed new membrane materials that are superior to the commercially available Nafion® developed by DuPont. We fabricated membrane resistances of up to 99 m Siemens/cm² (as opposed to Nafion®'s 80 m Siemens/cm²) and tested them in fuel-cell systems using hydrogen/oxygen and methanol/oxygen. We achieved power densities higher than 760 mW/cm² at 80°C, approximately a factor of 2 better than Nafion®.

41194

Augmented Cognition: Next-Generation Intelligent Systems

L. J. Ellis, N. G. Brannon, P. G. Xavier, K. W. Larson, J. C. Forsythe, J. H. Ganter, J. S. Wagner, D. P. Gallegos, P. C. Reeves, A. I. Gonzales, M. C. Chang

The relentless proliferation of data and information has resulted in a significant national security challenge involving people attempting to detect and characterize hidden but meaningful patterns in complex situations. Today, analysts deliberate over massive, disparate data sources to extract subtle patterns or indicators that will provide actionable information for decision makers. These analysts are faced with expanding and asynchronous data sources, increasingly complex interactions with collaborators, unreasonable timeframes for analysis and decision making, situation evolution over long timeframes, and limited personal contextual knowledge. The combination of these complications can easily result in false negatives, situation mischaracterization, or complacency, any one of which could result in a significant and serious national security lapse, depending on the situation and the threat.

This project advances Sandia's innovative approach to address this data/knowledge imbalance. We are creating the technology to exploit the perceptive capabilities that are exhibited by biological systems and to exploit a cognitive collective of diverse individual experts to assist analysts and decision makers to detect, interpret, and act on meaningful, but hidden patterns. The integration of these approaches into a tightly coupled system has the potential to result in detection and interpretation capabilities that are significantly superior to those presently achievable.

We conducted work along two technical tracks, perceptive systems and cognitive systems, and completed a successful external advisory committee (EAC) review. Our accomplishments included the following:

- *Perceptive systems.* For recognizing visual patterns in natural conditions, we developed a proof-of-concept application called SceneWatcher. Difficulties with conventional computer vision include lighting angle and shadows, occlusion by other objects, size (scale), and aspect (pose). Using a new neuromimetic commercial-off-the-shelf software library from SpikeNET, SceneWatcher did well in very cluttered backgrounds with partial occlusion.

This project advances Sandia's innovative approach to address this data/knowledge imbalance. We are creating the technology to exploit the perceptive capabilities that are exhibited by biological systems and to exploit a cognitive collective of diverse individual experts to assist analysts and decision makers to detect, interpret, and act on meaningful, but hidden patterns. The integration of these approaches into a tightly coupled system has the potential to result in detection and interpretation capabilities that are significantly superior to those presently achievable.

Development of our own neurocomputing technologies began with SPLab, a medium-fidelity neuron model best suited to sound recognition. (This development was in conjunction with the Seismic Ear project.) To achieve a highly flexible research and development environment without extensive dedicated programming, we wrote SPLab for the MATLAB programming, processing, and visualization environment. For speed, we wrote computing-intensive core modules of SPLab in compiled languages (C/C++).

The principal SPLab technical milestone attained was the verification of core neural simulations, including the neural gain function (the nonlinear and dynamical relationship between current and voltage across the cell membrane), and neural dynamics for simple networks. Other work provided essential insights into appropriate levels of neuromimicry.

In the area of vision, we analyzed publications on the Rank-Order Coding (ROC) theory and models of rapid primate vision. We implemented a prototype algorithm called ROCIT in MATLAB and began parallel development of an accelerated version called SpikeWave in C++. We also began initial work on test sets and protocols for verification (consistency), validation (correctness), and evaluation (performance relative to other technologies) of our results.

- *Cognitive systems.* The primary objective for the cognitive-systems track is to implement the three level-1 capabilities described below within the context of a capabilities demonstration and to quantitatively validate performance gains:

- *Expert models.* Cognitive models based on the knowledge of specific experts from different disciplines provide separate interpretations of data derived from various sources.

- *Cognitive collective.* Cognitive models for different experts interact to recognize patterns collectively that no single model would be capable of recognizing alone.

- *Interactive interface.* A visualization interface enables a user to interrogate expert cognitive models to gain an understanding of what facets of the model's knowledge led to the model's reaching a given conclusion or to compare expert cognitive models as they respond to cues from various data sources.

We implemented the level-1 capabilities in a capabilities demonstration focused on detection of patterns of behavior consistent with an insider threat. A validation study is currently under way.

Implementation of level-1 capabilities involved development of a prototype cognitive system for detecting behavior consistent with an individual who is preparing for, or

is in the process of, gaining access to electronically stored classified information for unauthorized purposes, which may include that individual's unauthorized access to the classified information.

To advance thinking in the area of cognitive systems, promote collaboration, and establish a leadership role for Sandia, we co-hosted a Cognitive Systems Workshop with the University of New Mexico that featured 25 speakers representing industry, government, and academia.

50065

TALON

F. T. Mendenhall, M. B. Murphy, R. A. Griffiths, R. W. Stinnett, L. G. Stotts, M. C. Reineke, L. J. Ellis, S. M. Deland, M. D. Ladd, P. J. Eicker, M. R. Ackermann, J. B. Woodard, J. R. Yoder, M. J. McDonald, F. J. Oppel, III, R. L. Williams, E. P. Parker, P. R. Bryson, K. T. Stalker, D. P. Gallegos, J. J. Carlson, J. W. Hampton, K. T. Malone

The Sandia TALON Grand Challenge was born from a desire of the Sandia Mission Council to help the country following the 9/11/01 terrorist attack on the United States. That desire created a mandate to the TALON Team—"Make a difference in the War on Terrorism."

Based on the groundwork laid by the Advance Concept Group, this team accepted the challenge of bringing the TALON concepts to life through the development of collaborative networks of unattended ground sensors (UGSs) to detect, identify, and track adversary assets moving into and out of areas of interest (caves, underground facilities [UGFs], factories, etc.)

The technical challenges associated with this project include the following:

- (1) Insufficient sensor lifetime in expected environments*
- (2) Inability to deal with targets of interest*
- (3) Unacceptably high false-alarm rates*
- (4) Operational dangers of sensor emplacement*
- (5) Sensors that are easy to detect, spoof, and overrun*
- (6) Data exfiltration*
- (7) Inability to cope with expected data flow*
- (8) Inability to predict and optimize sensor array*

performance.

These technical challenges require a systems approach to creating solutions that are outside of the normal needs of commercial problems, and therefore little progress has been made over several decades in addressing the requirements based on national security applications.

TALON is focused on overcoming these technical barriers and thus enabling sensor arrays to be used in national security missions.

- *Network backbone development.* We completed the design and development of a low-power network backbone, which is one of the core accomplishments. While the architecture is described in more detail in other documentation, the concept is to build a modular architecture in which each

These technical challenges require a systems approach to creating solutions that are outside of the normal needs of commercial problems, and therefore little progress has been made over several decades in addressing the requirements based on national security applications.

TALON is focused on overcoming these technical barriers and thus enabling sensor arrays to be used in national security missions.

node can be configured to support a number of different functions, including interfacing to sensors either through radio-frequency (RF) communication or through direct connection to analog input ports, low-power wake-up, complex signal processing, network communication (hopping), and satellite communication (including two-way communication for command and control). The modular network-node architecture allows the nodes to be configured easily into a myriad of cluster designs.

We leveraged state-of-the-art low-power commercial technology and developed a tiered hardware architecture that is expected to extend the lifetime of a ground sensor from a few months to nearly a year (assuming a 400 Wh battery). Predicted power for the new design represents a 15x reduction in power consumption over the power consumption of the TUGS (Tactical Unattended Ground Sensor) system developed by Sandia.

- *Network protocol development.* Communications within a cluster occur via an *ad hoc* network. We performed a trade study of various networking protocols and selected Dynamic Source Routing (DSR) as an appropriate network protocol for the UGS environment. This protocol is the lightest decentralized routing algorithm available and provides the self-configuration and self-healing aspects essential for the UGS environment. DSR was shown to have the lowest routing-power consumption, and this protocol scales well as the number of nodes increase.

- *Environmental effects on RF propagation.* We performed an analysis of RF propagation when both the transmit and the receive antennae are near the ground. Calculations indicate that RF strength falls off as $1/R^4$ and is frequency independent for flat, open terrain. We validated these calculations with a series of measurements. We also researched models for foliage effects and urban-terrain effects.

- *Target detection and classification.* The final and most viable approach for detecting and classifying some of the harder TALON targets requires the use of a visible-spectrum imager. This sensor incorporates new classification algorithms to classify the targets by size (small, medium, large). We submitted technical advances on target-tracking algorithms based on results of this research.

- *Flexible and extensible data-management component.* We completed the design for the data-management component. One of the key challenges in data management for sensor systems is being able to adapt easily to new sensor types or to support multiple versions of the same type of sensor (where

We leveraged state-of-the-art low-power commercial technology and developed a tiered hardware architecture that is expected to extend the lifetime of a ground sensor from a few months to nearly a year (assuming a 400 Wh battery). Predicted power for the new design represents a 15x reduction in power consumption over the power consumption of the TUGS (Tactical Unattended Ground Sensor) system developed by Sandia.

different versions may send different data or use different formats). The Extensible Markup Language (XML)–based description enables dynamic message parsing and dynamic data management—little or no new code is required to communicate and manage data from a new or updated sensor type.

- *Modeling and simulation.* In the modeling and simulation task, we made significant progress on four objectives:

- (1) Develop methods to analyze system performance
- (2) Develop simulation models to support systems' trade studies and performance-assessment analysis
- (3) Analyze dynamic system performance
- (4) Assess scalability and extensibility of the current design.

We developed models in the UMBRA modeling and simulation framework and documented the model features in our proposal for future work on this project. We used the models to perform initial mission planning for recent field exercises.

We defined a set of “information-based” performance metrics, that is, metrics focused on whether there was sufficient information to accomplish the mission, and we identified a number of variable parameters (e.g., sensor location, spacing, vehicle speed, etc.) that affect performance.

In the area of dynamic systems analysis, we completed detailed data gathering and initial modeling in power consumption, network protocols at all of the Open Systems Interconnection (OSI) layers, and issues related to sensor layout and terrain.

55079

Near-Real-Time Characterization for Assured HDBT Defeat

D. R. Gardner, J. D. Rogers, B. P. Engler, A. F. Fossum, L. C. Bartel, P. Yarrington, L. S. Costin, D. J. Holcomb, G. J. Elbring, M. C. Walck, M. L. Yee, N. P. Symons, K. T. Stalker, K. D. Meeks, J. L. Sichler, R. J. Fogler, R. T. Gilchrist, D. J. Frew, J. T. Hollenshead, R. L. Williams, J. W. Hampton

The technical approach of this project is to collect penetration and seismic data using a network of air-deployable, earth-penetrating sensors and active sources to generate a near-surface seismic velocity map, and to combine the penetration data and velocity map to identify potential aim points for a nuclear earth-penetrating weapon (EPW) at a hard and deeply buried target (HDBT) site.

The project involves several high-risk technical challenges. One of these is obtaining adequate resolution of the near surface of the HDBT site with a sparse, irregular array of seismic sources and sensors. The arrays used in this project will be much sparser and more irregular than those used in geotechnical engineering applications.

Another high-risk technical challenge is correlating penetration data with the seismic velocity map. The seismic velocity map is developed from elastic material properties (e.g., the shear modulus), while penetration events are governed by nonlinear elastic-plastic material properties, such as yield strength and loading hysteresis. Methods to integrate penetration data with seismic velocity maps will be required to develop a composite description of target material properties and their spatial distribution in the near-surface layer.

Other technical challenges include shock hardening of componentry such as geophones, global positioning system (GPS) electronics, and other electronic components; emplacing seismic sensors near the surface in a variety of soils; collecting accelerometer data from more deeply buried probes; and forming efficient ad hoc data-collection networks. Addressing all these challenges requires a multidisciplinary systems approach and will draw on Sandia's expertise in seismic imaging, air-deployed sensors and sensor networks, earth penetrators, and modeling and simulation, and will enhance Sandia's capabilities in these areas.

Success of the project will provide the technological basis for increasing our confidence that an EPW will survive impact and that a targeted HDBT will be defeated. The project has other potential Department of Defense extensions as well.

Addressing all these challenges requires a multidisciplinary systems approach and will draw on Sandia's expertise in seismic imaging, air-deployed sensors and sensor networks, earth penetrators, and modeling and simulation, and will enhance Sandia's capabilities in these areas. Success of the project will provide the technological basis for increasing our confidence that an EPW will survive impact and that a targeted HDBT will be defeated.

We made significant progress in developing seismic algorithms, sensor specifications, and penetrator designs.

We developed a concept of operations involving two arrays of penetrating devices, one array of smaller sources and sensors for seismic mapping, and a second array of probes for collecting penetration data, deployed as separable penetrators. *Ad hoc* networks collect penetrator and seismic data and transmit them via satellite to a remote site to construct the penetrability map.

We determined that a 10–300 Hz frequency range will capture the vast majority of velocity structures anticipated, and that the maximum tolerable error in the source and sensor locations is $\sim 1/4$ of the minimum anticipated wavelength (~ 1 m).

We developed a refraction microtremor code and tested the sensitivity of the generated dispersion curves to noise in the raw waveform data. We developed a multiple-filtering, Hilbert transform code for extracting the surface-wave dispersion curves from the waveform data, and tested the sensitivity of the generated dispersion curves to measurement error, contrasts in the velocity structure, and layer depth and thickness. We tested both codes using synthetic data for a fault model.

We are implementing Fresnel-ray paths in the surface-wave tomography code to more realistically model energy transmission. The code uses a combination of directed random models with damped least-squares linear inversion to generate the seismic velocity structure. We developed an innovative technique for determining the number of layers in the initial velocity model. We studied the effects of dispersion-curve truncation on the predicted velocity structure. We will collect field data for testing the code in upcoming work.

We identified and are investigating a co-kriging method for combining the seismic velocity data with the point penetrability data to generate the area penetrability map.

We conducted preliminary tests of a geophone and a microelectromechanical systems (MEMS) seismometer, northing/tilt sensor, and network radio module for shock hardness and are analyzing the test results.

We determined that differential carrier-phase GPS technology provides relative sensor locations to an accuracy of ± 30 cm with a high degree of confidence. We will test a commercial GPS receiver for shock hardness. We determined range and bandwidth requirements for a network radio and identified a commercial unit with sufficient capability to demonstrate proof-of-principle while using license-free industrial, scientific, and medical (ISM) bands.

We developed an innovative technique for determining the number of layers in the initial velocity model.

We explored light (~ 30 lb) penetrator designs to emplace seismic sensors near the surface with a normal impact velocity of 75 m/s for a range of soil penetrabilities and a maximum deceleration of 5000 g. We developed an initial separable-penetrator design that can meet these requirements. We then developed an innovative conceptual design for a nonseparable penetrator with a variable cross-sectional area that meets the design requirements; preliminary simulation results indicate that this design has a maximum deceleration of ~ 2000 g.

We developed a conceptual separable-penetrator design for a probe to measure deceleration histories (which are then time-reversed and integrated to give the force on the penetrator as a function of velocity, and hence the penetrability of the material) and began investigating designs for transmitting data from the probes to the aft portion at the surface.

We then developed an innovative conceptual design for a nonseparable penetrator with a variable cross-sectional area that meets the design requirements; preliminary simulation results indicate that this design has a maximum deceleration of ~ 2000 g.

55086

Prompt Global Response

J. M. Macha, M. A. McWherter-Payne, K. W. Sorensen, T. S. Prevender, K. T. Stalker, M. R. Ackermann, D. W. Kuntz, R. E. Loehman, R. D. Tucker, M. S. Howard, M. H. Imbert, J. R. Salton, J. B. Christensen, W. H. Rutledge

Sandia's vision in this project is to develop advanced technologies and integrated capabilities for hypersonic flight systems applicable to a wide range of future military and access to space needs.

Prompt global response (PGR) addresses two key technical challenges that are requisite to the system capability that we envision: (1) the development of advanced design, material, and analysis capabilities for a thermal protection system (TPS) to enable long-range, endoatmospheric, hypersonic flight, and (2) the development of advanced precision navigation and guidance methods and hardware for applications requiring nonreliance on the global positioning system (GPS). A corollary technical challenge is the miniaturization and increased efficiency of electronic components to maximize payload volume and minimize booster size and cost.

The project will provide a pace-setting operational, unmanned, long-range, high-speed, precision-navigation flight system with application to a variety of national defense needs. PGR will also lead to collaborations with the military and civilian space sectors. Candidate programs for collaboration may include the Defense Advanced Research Project Agency's (DARPA's) Force Application and Launch from the Continental United States (FALCON), the Air Force's Common Aerospace Vehicle (CAV), and the National Aeronautical and Space Agency's (NASA's) Space Launch Initiative (SLI). We expect the continued development of enhanced capabilities, flight-hardware fabrication and assembly, and demonstration/application activities beyond this project.

The multiyear objectives of the PGR project reflect the dual nature of the desired impact, i.e., to provide motivation and focus for development of advanced technologies and integrated capabilities for hypersonic vehicles, and to complete a pathfinder demonstration mission. The accomplishments are (1) the initiation of teaming relationships with external agencies, and (2) a conceptual design for a specific application scenario.

The project will provide a pace-setting operational, unmanned, long-range, high-speed, precision-navigation flight system with application to a variety of national defense needs. PGR will also lead to collaborations with the military and civilian space sectors.

Our key technical accomplishments include the following:

- We completed preliminary assessment of power and volume requirements for a synthetic-aperture radar (SAR)–based navigation system.
- We performed an initial feasibility study of a ground-beacon concept for non-GPS navigation.
- We performed preliminary analyses of current and modified-/advanced-concept TPSs.
- We developed aerodynamic, thrust, and control models of potential operational boosters for a variety of applications.
- We performed parametric studies of vehicle glide performance to optimize trajectories for maximum range or to meet re-entry test-bed requirements (RTB).
- We completed conceptual designs for the RTB and other mission applications.
- We performed advanced configuration and aerophysics simulations.

Non-GPS-dependent navigation is one of our technology focus areas for PGR. We concluded that a purely inertial system with sufficient accuracy for the applications of interest is not feasible with respect to size, cost, or development schedule. We performed an initial feasibility analysis of using SAR as an altitude-ranging or a scene-matching navigation aid. We performed the analysis for flight velocities up to Mach 20 and at altitudes representative of the various PGR application scenarios. We also completed an initial study of waypoint and/or terminal navigation based on a ground-beacon concept. The beacons are essentially a backup or substitute for the GPS constellation.

The other PGR technology focus is the development of advanced design, material, and analysis capabilities for a TPS to enable long-range, endoatmospheric, hypersonic flight. Based on extensive aerothermal analyses, we concluded that the desired long glide ranges are not possible with the existing TPS design of our baseline vehicle. Our simulations of the existing design predict substantial recession of the wing leading edge on the windward side of the vehicle. The simulations also show that internal temperatures quickly exceed the service limit of the metal substructure. The solution to the wing leading-edge recession problem is the development of new outer-layer materials that can tolerate the high re-entry heating rates without decomposing or changing shape. We are collaborating with another project to determine the applicability of ultrahigh-temperature ceramics (UHTC) to PGR. We also are investigating the applicability of carbon composite matrix (CMC) materials.

We based our predictions of the material temperatures on assumptions about the nature of the boundary-layer flow along the length of the vehicle. In turn, we inferred the character of the boundary layer from existing correlations developed from experimental hypersonic re-entry data that may not be applicable to the present problem. We are addressing this critical issue by participating with peer researchers in industry and academia to develop an improved, physics-based, hypersonic transition prediction method. Progress to date in this collaboration includes the collection and review of nonzero angle-of-attack experimental data as a benchmark for future computational results, and a project plan for extending the e^n linear stability method to cross-flow boundary layers.

We made significant progress in identifying sponsors and acquiring external funding for “technology demonstration and application” efforts that complement the project’s focus on “technology development.” The most notable achievement in this area is our collaboration in the Next-Generation Launch Technology (NGLT) program, which is an element of NASA’s SLI. Sandia will develop an RTB hypersonic flight system. The RTB will provide a dedicated, timely, and cost-effective means of advancing the technology readiness level (TRL) of vehicle systems technologies through multiple demonstrations in a relevant re-entry flight environment. We received \$400K from NASA for concept-definition activities.

We made significant progress in identifying sponsors and acquiring external funding for “technology demonstration and application” efforts that complement the project’s focus on “technology development.” The most notable achievement in this area is our collaboration in the Next-Generation Launch Technology (NGLT) program, which is an element of NASA’s SLI. Sandia will develop an RTB hypersonic flight system.

55087

Winning the War: A Systems Approach to Defending Our Borders

T. D. Woodall, R. G. Hillaire, M. W. Koch, C. Q. Little, M. M. Johnson, J. C. Reinhardt, H. R. Ammerlahn, J. Lipkin, C. A. Pura, M. J. McDonald, R. D. Habbit, Jr., T. D. Russ

The current importance and urgency of the U.S. war on terrorism requires system-integration and system-of-system approaches to developing solutions for homeland security. Nowhere are these needs more evident than in securing our borders. The Department of Homeland Security (DHS) requested \$37.5B (Presidential request) to begin to address the spectrum of homeland security challenges. For border security, the U.S. faces the difficult balancing act of keeping bad actors and their materials out while maintaining or enhancing the flow of legitimate goods and services. Sandia must respond with tools and technology that help both the decision makers and the technology developers focus limited resources while preserving the legitimate flow of goods and people across our borders. We will take important steps to meet this challenge by developing a border simulation tool and a three-dimensional (3-D) facial-recognition system. The parallel development is mutually beneficial.

To form the systems perspective, we will develop simulation software that can assess the system composed of the flows of goods and people across borders. The Border Security Simulation is a tool for (1) personnel resource allocation, (2) border solution validation (e.g., technology and operational options), (3) security and commerce trade-off valuation, and (4) assessment of flow in changing conditions.

We will integrate this suite of tools into a simulation framework to broadly address the problem sets of three distinct types of customers:

(1) Homeland security and related agencies to perform cost/benefit trade-off studies for new technologies, develop system standards and requirements, and compare security effectiveness of technology/operational solutions

(2) System users to model the deployment of concepts of operations for new procedures and/or new technologies and allocate resources

(3) Technology developers to focus applied research and development on key parameters to improve system effectiveness and model the utility of technology concepts.

The Micro Optical Radar (MOR) technology development will provide simulation validation and address facial-

Algorithms used for facial recognition: fitting two faces.

For border security, the U.S. faces the difficult balancing act of keeping bad actors and their materials out while maintaining or enhancing the flow of legitimate goods and services.... We will take important steps to meet this challenge by developing a border simulation tool and a three-dimensional (3-D) facial-recognition system.

recognition security challenges to detect the few faces from the many.

We leveraged the Enterprise Modeling Architecture (EMA) as the basis for a Borders Simulation Application modeling U.S. border ports of entry (POEs). To address scalability and multifidelity model challenges, we enhanced the EMA to provide

- data visualization of large geographic regions, POEs, and threats,
- a batch execution framework for facilitating trade-off and sensitivity analyses, and
- a prototype computer infrastructure for parallel execution of models.

We implemented several application components, including transportation and low-fidelity San Ysidro POE models, and a dynamically reconfigurable, scalable workspace displaying POE and technology throughput and operations statistics. We completed conceptual-model design and data-source identification. Finally, we also completed documentation of Criteria for Model Integration Candidacy, a technical integration feasibility survey of existing third-party models (including Border Wizard and National Infrastructure Simulation and Analysis Center [NISAC] applications), and the exchange of technical specifications for incorporation of the NISAC Seaport Model.

We defined the U.S. border system for modeling and simulation. We performed a porosity study that characterized the San Diego region of the U.S. border system. The porosity study started with a geospatial analysis of the region to identify every threat mode of entry across the U.S. border, including facility designs and operations. We found that the threat can be grouped into 96 categories with access to 113 entry facilities and more than 150 mi of unattended coast and land access. We then identified the national security policies that we will evaluate using the simulation: How to use technologies to detect nuclear contraband and how to transition border operations through the “DHS threat levels” to balance security relative to social and economic costs. We also developed a modeling simulation specification. The specification consists of descriptions of the threats, facilities, procedures, and technologies.

The MOR Team had several key advancements. We developed and demonstrated feasibility of Micro LADAR (laser radar) at the single pixel level. We developed a viable system concept for facial biometric identification of individuals at

points of entry (e.g., pedestrian crossings, airports, etc.). Work conducted under this project to improve understanding, motion compensation, and accuracy of current baseline technology for facial recognition assisted in attracting a \$7.2M baseline technology project from the National Aeronautics and Space Administration (NASA). The requirement for very high resolution is common between facial recognition and space-vehicle inspection and other applications. The MOR team assured Sandia's leadership position in 3-D LADAR as confirmed by NASA's investment. The MOR technology, once proven under this project, is poised to improve national security and ensure Sandia's leadership role.

During the year the 3-D facial-recognition algorithm development team made significant progress. Two approaches to 3-D data acquisition were pursued: internal data acquisition and collaboration with academic resources. The University of Munster provided 240 range images of 24 individuals. We acquired additional images from Sandia-owned or -developed sensors. Recently, we acquired a new 3-D sensor so that we can augment the data we have and expect to acquire with high-resolution 3-D faces that can be acquired relatively fast.

We initiated approaches for facial detection and recognition. We implemented the Iterative Closest Point algorithm to perform facial detection, pose estimation, and correction. The method registers two-point clouds by an iterative method that uses an energy-minimization criterion to guide it. We also implemented an approach to match an acquired 3-D face point representation using the Hausdorff metric. The Hausdorff metric can be extended easily to handle missing and extra information. We assessed a preliminary examination of recognition performance using the Swiss database, which was not corrected for facial pose. The results demonstrate the importance of having a metric that tolerates partial shapes and spurious information for improved performance.

Refereed

Wright, L. J., and T. D. Russ. 2003. Facial recognition in physical security. *Proc. INNM 44th Annual Meeting* 1 (July, Phoenix, Arizona).

Work conducted under this project to improve understanding, motion compensation, and accuracy of current baseline technology for facial recognition assisted in attracting a \$7.2M baseline technology project from the National Aeronautics and Space Administration (NASA). The requirement for very high resolution is common between facial recognition and space-vehicle inspection and other applications. The MOR team assured Sandia's leadership position in 3-D LADAR as confirmed by NASA's investment. The MOR technology, once proven under this project, is poised to improve national security and ensure Sandia's leadership role.

62827

Nonlethal Technologies for the War on Terrorism

P. D. Coleman, J. L. Dohner, L. F. Rinehart, D. B. Seidel, L. D. Brandt, L. E. Larsen, W. R. Bolton, Jr., S. H. Scott, T. J. Reser, M. C. Wanke, A. G. Baca, J. E. Pacheco, V. M. Hietala, R. P. Toth

This project will establish the technical feasibility for a dramatically new method to counter elements of the terrorist threat and affect the way we engage adversaries when lethal force is not appropriate. A nonlethal response opens a range of options for dealing with the situation by temporarily incapacitating hostiles without injury. High-frequency radio frequency (RF) has been shown to create a strong flee reaction. However, present systems designed for this RF application are based on vacuum-tube technology and, thus, are expensive, large, and fragile. Further, conventional semiconductors do not have the required power. In this project, Sandia seeks to build a microelectromechanical systems (MEMS)–fabricated micro vacuum electronic source that could be arrayed to yield a robust, high-power, and relatively inexpensive alternative to present systems. These sources can find uses in access denial (military and civilian use), higher-resolution synthetic-aperture radars (SARs), wideband communications, and imaging through obscurants (including clothing and epoxies used in weapons manufacturing).

With respect to RF vacuum microdevices, we (1) used a three-dimensional (3-D) simulation code (HFSS) to study effects on oscillator cavity grids on cavity Q, (2) began particle-in-cell (PIC) code (QUICKSILVER) parameter scans to identify beam parameters required to obtain oscillations, (3) ordered field-emitter array (FEA) diodes (Spindt type), (4) started a conceptual design of coupling of transit time oscillator (TTO) to output antenna, (5) started a conceptual design of a proof-of-principle cavity structure, and (6) developed fundamental frequency-mode-locked cavities (~ 40 GHz).

For the acoustic element, we (1) procured a mannequin for acoustic testing, (2) acquired a shielded enclosure, (3) started modeling and simulation of the plasma discharge, (4) started simulation of the impulse propagation and head-related transfer function, and (5) began work on an electroacoustic source.

The Systems and External Advisory Board (EAB) element (1) identified one Department of Energy (DOE) security office (SO) system scenario—protection of DOE storage facilities, and (2) is setting up the EAB. The members of the EAB will

This project will establish the technical feasibility for a dramatically new method to counter elements of the terrorist threat and affect the way we engage adversaries when lethal force is not appropriate....Sandia seeks to build a microelectromechanical systems (MEMS)–fabricated micro vacuum electronic source that could be arrayed to yield a robust, high-power, and relatively inexpensive alternative to present systems.

represent the Department of the Under Secretary of Defense (Science and Technology) Weapons Systems, the University of Medicine & Dentistry of New Jersey, U.S. Army TACOM-ARDEC (Picattiny Arsenal), and DOE/SO-10 (Security Policy).

Advanced Concepts

The Advanced Concepts investment area seeks solutions to future national security threats and problems that do not yet exist, but are on the horizon. Sandia has the opportunity to develop new tools that could fundamentally transform U.S. abilities to fight the “War on Terrorism.” The goals of these transformational capabilities are to create agile, networked responses utilizing the full capabilities of the nation, to deny the ability of the adversaries to hide their intention and plans, to enable exquisite situational understanding of unfolding events, to harden the homeland, to deliver discriminating effects against diffuse targets, and to alter perceptions of U.S. adversaries.

Developing new energy sources is critical to maintaining national security. Large natural-gas reserves exist on the seafloor in the form of methane hydrates; native bacteria digest and metabolize these methane hydrates. *Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application* will begin the first scientific investigation into the interaction between biological organisms and methane-hydrate energy sources. Understanding how these organisms utilize hydrates will

enable development of this new energy source. The successful completion of this work will be of great interest to the National Methane Hydrate Program, the Department of Energy, and several companies that are pursuing the realization of a methane-hydrate energy resource.

60866

SDAC Architectural Study and Demonstration System Development

N. M. Berry, J. Z. Davis, N. M. Nachtigal, R. D. Kyker, C. W. Van Dyke, D. P. Stark, T. H. Ko

The integration of wireless communication with existing sensor technology has greatly enhanced the potential for creating distributed sensor networks capable of providing fixed and mobile sensor/responder platforms. These complete system platforms are classified by their fundamental capabilities to Sense—multimodal sensing of environmental events, Decide—smart analysis of environmental sensor data, Act—response to environmental events, and Communicate—internal to system and external to humans (SDAC). Collectively, this project will require surveys, evaluation, analysis, and development of a demonstration system to illustrate the SDAC vision.

The field of wireless sensor networks is related to the larger field classified as “networked systems of embedded computers” by the National Research Council (NRC). The NRC believes this field represents the next revolution of computer technology that ideally cuts across numerous multidisciplinary fields of study. While there have been many studies in sensor networks over the last 5 years, none of these projects directly addresses our four mission areas in the war on terrorism (WoT). In addition, these projects do not provide fundamental methodologies that detail requirements needed to map current or future sensors onto the SDAC (Sense, Decide, Act, Communicate) systems for the WoT domain.

While the field of wireless sensor networks is ideally suited for dealing with situations that address the WoT, it also represents the newest challenge facing multidisciplinary research in the areas of embedded systems, wireless technology, power consumption, *ad hoc* routing, distributed computing, and information technology in general. Since this study is uniquely situated near the beginning of the nation’s thrust in this field, our results will become a driving influence on current and future SDAC-oriented system development. Our approach to this problem is further justified by the NRC recommendation that “...work in this area will probably be confined to domain- and application-specific systems unless a concerted, comprehensive effort is made to broaden and deepen the research endeavor.” While our study is not fully comprehensive, our results will provide deeper and broader insights for researchers in the wireless-sensor-network arena.

Phase one of this research attempted to survey the four WoT areas: military operations on urbanized terrain (MOUT), border,

The field of wireless sensor networks is related to the larger field classified as “networked systems of embedded computers” by the National Research Council (NRC). The NRC believes this field represents the next revolution of computer technology that ideally cuts across numerous multidisciplinary fields of study....Since this study is uniquely situated near the beginning of the nation’s thrust in this field, our results will become a driving influence on current and future SDAC-oriented system development.

mobile force and site protection, and intelligence. Of these four, we decided to reduce the set to MOUT and border-patrol considerations only. We based this change on lack of operational personnel or information from the other two areas. This scenario development resulted in the creation of requirements and capabilities for SDAC sensor systems for these two areas.

Phase two of the research consisted of a survey of existing sensor systems. Combining the requirements and capabilities from the scenario evaluation, the project team proposed a potential hardware and software architecture for SDAC sensor systems. We based the proposed system on a modular architecture approach that treats all aspects of the sensor hardware as individual encompassed nodes or subsystems. These nodes include power, communication, sensor boards, and processing, all attached via an I2C bus. These hardware nodes are integrated with software into a module-level architecture. Collectively, the modular units represent distributed system control, scalable and adaptable software/hardware, functional separation of computation, and parallel processing. Individual modules are performance-optimized.

Phase three of the research dealt with the development of a demo system for the SDAC MOUT domain. The scenario comes from the classic military question of friendly forces versus enemy. The demo required the ground distribution of sensors, each containing either a seismic, acoustic, or passive infrared (PIR) sensor. These unattended ground sensors illustrate a sensor fence placed behind troops as they advance forward, thus warning them of enemy troops moving in behind the advancing forces. The demo uses a collection of these sensors and a transponder sensor being held by a person to detect friendly forces. If a person passes through the sensor field without a transponder, the sensor field denotes an enemy has entered the area.

The results of the SDAC project and demo give some interesting insights into other issues pertaining to sensor systems. These include preliminary metrics and trade-off formulas for determining what capabilities are favored for a certain sensor application, a survey of existing capabilities for current sensor-system development, and a proposed module architecture that builds on existing designs and provides next-generation insight into flexible hardware/software for sensor systems.

Refereed

Davis, J. Z., R. D. Kyker, and N. M. Berry. 2003. Modular sensor network node architecture for event-driven systems. *International Telemetry Conference*, accepted.

Other Communications

Davis, J. Z., R. D. Kyker, and N. M. Berry. 2003. A System-Level Hardware Architecture for Distributed Sensor Network Nodes. Sandia Technical Report SAND2003-8209, Sandia National Laboratories, Albuquerque, New Mexico.

62270

Assessment of Information Flow Associated with Goods and People Crossing International Borders

L. R. Phillips, J. W. Strachan, S. V. Spires

In this project Sandia provided an information-flow map detailing information flow and technology infrastructure, current ports-of-entry data, and information collection, interpretation, and dissemination methods and technologies required for movement across U.S. borders. We used the resulting knowledge of this information flow and its supporting infrastructure to identify deficiencies and critical needs with respect to current security requirements. We identified how these gaps can be addressed using technologies being developed at Sandia. Currently, information-flow protocols are fragmented across multiple governmental agencies in multiple countries and are not available in an integrated format. Our experience on the U.S.–Mexico border in the mid-90s provided ready contact with border agencies there; we also enlisted the aid of a member of the Transportation Resource Board to provide information on U.S.–Canada border operations. We used existing documentation, Web-based information, and local expertise, as available, to form a complete picture of North American land-based trade, and our Sandia contacts and knowledge resulted in an accurate picture of where Sandia technology can expedite border commerce while improving the U.S. border-security posture.

We accessed many rich sources of border-trade information in several domains: civil coalitions, commercial firms, transportation experts, Web sites, North American governmental agencies responsible for border security and commerce, published hardcopy documents, and local expertise. We observed extensive change and interconnectivity among the civil and governmental entities, policies, concerns, processes, methods, and technology that make up and influence North American cross-border movement; the text-based hyperconnectivity makes documentation relatively easy to update and interconnect as needed.

We achieved the following:

- We acquired and updated an information-flow map from the 1996 Sandia border-trade study.
- We amassed an extensive collection of material, references, and live Web links to pre-existing published information relevant to the cross-border process.

We used existing documentation, Web-based information, and local expertise, as available, to form a complete picture of North American land-based trade, and our Sandia contacts and knowledge resulted in an accurate picture of where Sandia technology can expedite border commerce while improving the U.S. border-security posture.

- We made preliminary recommendations in two Sandia technology areas.
- We designed a preliminary Web site for our final report to enable dynamic information nexus given fast-changing trade/security/technology.

Sandia is one of the members of the SW Border Technologies Consortium. Through the consortium we made a number of contacts with people involved in border commerce-related work being done at New Mexico State University, the University of Arizona, and the University of Texas at El Paso. We continue to acquire information through these sources.

62826

Automatic Detection of Anomalous Weapon Surveillance Waveforms

K. W. Larson, J. H. Ganter, T. M. Sterk, S. A. McKenna, B. J. Merchant, J. L. Mitchiner, L. A. Ingham-Hill, B. J. Gomez, W. A. Hareland, S. J. Lambert

Weapon surveillance testers produce time-value data and generate weapon test reports (WTRs) that systems-evaluation engineers review to ensure that performance matches acceptable norms. Instances arise for which the WTR data fall within norms, but detailed examination, with respect to past data traces and calling for efforts beyond the attention that can reasonably be afforded, reveals the possibility of developing defects. Deriving full value from costly laboratory and flight test programs and ensuring that the Stockpile Stewardship Program becomes more predictive of developing problems in an aging stockpile are now within reach.

Sandia proposes to build a Waveform Anomaly Detection System (WADS) that will alert personnel to evolving, and sometimes subtle, problems that can cause future performance failures. We will develop and apply a prototype system that demonstrates feasibility for systems-evaluation engineers to train and optimize a detector that recognizes and flags suspect behaviors. This will enhance our ability to anticipate and correct stockpile problems.

The WADS prototype will provide the following:

- *A means to establish feasibility and to create market demand by users*
- *Increased understanding of the problems, needs, and potential solutions in weapon surveillance*
- *A foundation for future applications that will examine datasets with increasing complexity.*

The mission-critical data of this project may provide a useful test-bed for advanced techniques of pattern recognition. The WADS is an expert system for a real, mission-critical problem. The research that this project supports will set the stage for a system to comprehensively improve the ability of Sandia to manage the aging stockpile.

The key results of the project follow:

- *We conducted a survey of potential techniques to detect anomalous waveforms.*
- *We convened, briefed, and solicited for advice an expert panel to advise the project investigator on technical issues.*

The mission-critical data of this project may provide a useful test-bed for advanced techniques of pattern recognition. The WADS is an expert system for a real, mission-critical problem. The research that this project supports will set the stage for a system to comprehensively improve the ability of Sandia to manage the aging stockpile.

- We identified two promising methods, segmentation and cross-correlation. We chose the cross-correlation method for the prototype.

- We implemented the cross-correlation method in a prototype application.

- We included features in the prototype application for the visualization and manipulation of waveforms (pre- and post-processing).

- The prototype application, WADS, makes use of software developed in Sandia's ground-based nuclear explosion monitoring (GNEM) program, MATLAB, and external open-source software.

- The cross-correlation method uses a hierarchical clustering technique known as a *dendrogram* to interactively explore the similarity of past waveforms and to display results.

- WADS supports a batch-test mode that is conceptually compatible with the weapon report methodology used at the Weapons Evaluation Test Laboratory (WETL).

- The prototype received positive reviews from the team as a useful tool for waveform analysis in the stockpile surveillance program.

The prototype application, WADS, makes use of software developed in Sandia's ground-based nuclear explosion monitoring (GNEM) program, MATLAB, and external open-source software.

Other Communications

Larson, K. W., R. Simons, S. J. Lambert, and W. A. Hareland. 2003. A Method and Prototype Implementation for Detecting Anomalous Features in Time-Series Stockpile Surveillance Data. Sandia Technical Report SAND2003-3459, Sandia National Laboratories, Albuquerque, New Mexico.

62970

Computational Social Dynamic Modeling of Groups Perpetrating Violence

N. M. Berry, J. D. Smrcka, J. G. Turnley, T. D. Moy, M. Pickett, M. Lee, T. H. Ko

This project applied the concepts of computational social dynamics to explore the emergence of group behavior related to the perpetration of violent acts of aggression from terrorist and terrorist-like organizations. The ability to observe social simulations at these levels of interactions between actual agents provides a unique insight into how social relationships, societal rules, and environmental factors can be integrated into a complete world model. While these simulations cannot be used to predict social behavior, they provide a tool for observing social behavior for a variety of situations. The Seldon gang model deals with inner-city gang development and concentrates on organizational issues related to terrorist-like groups. Using the gang model, the research team extended the model to encompass a Middle-Eastern terrorist model.

The multidisciplinary field of computational social dynamics has evolved through simulation techniques originating with macro-, micro-, and eventually the finer-grained agent-based modeling systems. The ability to observe social simulation at this level provides unique insight into how social relationships, societal rules, and environmental factors can be integrated into a complete world model. The main objective of this project was to apply the concepts of computational social dynamics as the team explores the emergence of group behavior for terrorist-like organizations.

To achieve this task, we assembled a multidisciplinary team of social and computer scientists to respectively survey and evaluate gang literature and agent-based modeling. Based on the integration of these two activities, the team designed a gang model based on inner-city youth. To ensure expansion of the gang model, the team incorporated general organizational capabilities that would potentially be reusable in future terrorist-model development. Using this design, the team developed a preliminary agent-based social simulation toolkit. The toolkit contains an environment for the agent-based model, including graphical user interface, visualization tools, and model configuration.

The completed toolkit provided an initial analysis tool that can be used by domain experts to evaluate how these hypotheses play out in the established simulated environment.

This project applied the concepts of computational social dynamics to explore the emergence of group behavior related to the perpetration of violent acts of aggression from terrorist and terrorist-like organizations....Using the gang model, the research team extended the model to encompass a Middle-Eastern terrorist model.

Each user is able to configure the simulation by setting a collection of parameters. These parameters are fed into the simulation model and visualized back to the user using one of the visualization techniques.

The important results of this project capitalize on the growing interest in agent-based human social simulation, by designing and developing a unique hybrid architecture to capture a finer granularity of human social behavior. This is achieved with two categories of agents: (1) youth-agent represents the population of young males ages 15–19, and (2) abstract-agent represents nonhuman entities, which interact with the youth-agent(s). In the gang model, schools and concept of a gang are examples of abstract-agents. The interactions between the youth-agent(s) and a school or gang abstract-agent cause necessary adjustments in the youth-agent(s) parameter set. A similar reaction occurs when a pair of youth-agents interacts. It is the combination of interactions between the different agents that drives the simulation to illustration of youth-agents moving in and out of gang organizations. By setting the necessary parameters, the user is able to test his/her hypothesis and visualize how quickly gangs evolve, or how some youths never migrate toward a gang.

We recently concentrated on evaluating the gang simulation model and the progression toward determining what changes needed to occur to migrate the model into a terrorist model. Upon initial evaluation of the social scientist team, we utilized the same basic concepts of the gang model with the necessary change for the terrorist domain. The result of proposed migration extended the abstract-agent to 4–5 entities. It also provided the team with the opportunity to potentially explore multiple social networks and the interactions that occur between these networks. Future follow-on research hopes to further explore how agent social simulation can be used to experiment with terrorist groups to illustrate what factors attract individuals to these organizations.

62971

Development of a Terrorist-Activity Plan-Assessment Methodology

G. N. Conrad, I. Dubicka, M. M. Warrant, D. P. Miller, A. E. Speed, W. A. Stubblefield, O. H. Bray

This research will design methodologies and tools that provide security analysts with the ability to rank-order sets of possible plans of terrorist attacks. Red Teams, in a war-game type of setting, will use these rank-ordered plans as they seek to understand, prevent, and mitigate terrorist activity. This research will work closely with another project that is working to automate the derivation of the terrorist plans. Given a set of generated plans, a context, and rules, Sandia will give each plan a set of scores as an evaluation of its plausibility, likelihood, and potential consequence, etc. For example, are the targets and capabilities in the plan consistent with a specified group? To support this scoring process, we will define and prototype an information repository. The primary goal is to determine what scores mean, how they will be used, and how the analyst community can use collaborative methods so that their expertise can be elicited to improve automated scoring. This plan-scoring capability does not currently exist and is unproven. We will explore innovative human-computer interfaces, such as virtual blackboards, to enable a collaborative environment. Such interfaces will allow security analysts to capture and improve their scoring methodologies as teams and individuals. We will also explore cognitive models that will enhance the automated capabilities of the scoring system. Our designs will explore visualization capabilities that allow the analysts to view a plan with its various scores and within a given context. Additionally, we will develop our designs and definitions in a framework that encompasses need-to-know requirements and consistent improvement through system-feedback loops. The capabilities to be explored will enhance the ability of security analysts to ensure homeland security, and will have applicability to other problems such as insider threats and network intrusion issues.

The capabilities to be explored will enhance the ability of security analysts to ensure homeland security, and will have applicability to other problems such as insider threats and network intrusion issues.

We developed an influence model that relates parameters of plans and groups that could be used in ranking plan/group combinations either from comparing intelligence data with observables for plans and groups or with capabilities of groups compared with requirements of plans. The influence model has not yet been validated by representatives of analyst groups. We developed scoring processes for several different types of

scoring and integrated their data requirements into the information model and database design developed in another project. Some scoring factors relate to plans, e.g., technical feasibility, complexity, risk, visibility, and resources required. Other scoring factors relate to groups, e.g., objectives, resources, risk tolerance, level of planning detail, size and areas of operations, and relationships with other groups. Still others relate to the linkage between plans and groups, e.g., common factors about plans and groups that would determine whether or not a specific plan is consistent with how a particular group operates. For example, does a plan address a group's objectives? Is it consistent with a group's resources and the amount of those resources the group is willing to commit to a single operation? Is the plan similar to things the group has done in the past? Is a plan within a group's risk tolerance and the level of complexity they can deal with? For scoring using intelligence data, we would compare current data with the set of observables identified for all of the tasks involved in carrying out a plan. We expect an iterative process using both types of scoring to be used by the analyst. A group of experts focusing on generic tasks (e.g., acquiring a specific type of weapon or material, for example, for a radiological dispersal device [RDD] or getting people into the country) and alternatives for performing them would specify the appropriate scoring factors and values. This involves a different type of group exercise that we have not yet done. We developed templates to capture plan, task, and scoring data during the Red Team exercise. However, much of the Red Team discussion involved finding an alternative that was technically feasible, given their assumptions, and would meet stated objectives ("satisficing") rather than in comparing alternatives and finding the best one ("optimizing"). From the Red Team exercise and from the decision-analysis literature, the project team gained insights into modeling decision making from both the terrorist planners' and the analysts' perspectives and in features needed for software that would assist the analyst in making good decisions.

62972

Development of an Interactive Nuclear/WMD Terrorist Data Model

A. L. Sobel, O. H. Bray, J. D. Corey, I. Dubicka, W. J. Tedeschi, M. C. Foehse, L. W. Gillen

The goal of this research was to develop an interactive, computer-based data model and populate it with relevant information for a broad range of possible nuclear-related terrorist planning and attack scenarios. Each developed attack scenario would consist of detailed plans and plan fragments, along with a reasonable set of permutations based on previously observed related events or postulated plausible events. The plan fragments would be logically interrelated computationally via chronologically or functionally sequential relationships. The data model would be structured such that it will interface with another computer-based model (to be developed in other work) that would query the present model for use in developing nuclear-terrorist-attack rules and assessments. The ultimate goal for the nuclear-terrorist data model would be to allow subsequent development and deployment of automated computer-based tools to aid the intelligence community analyst. These tools would enable more effective synthesis of all-source intelligence data, thereby allowing earlier predictions of plausible planned or impending nuclear-terrorist attacks of high interest. Such a capability does not exist today. New types of automated human-computer relationships would be explored, characterized, quantified, and exploited to greatly enhance national security.

We developed an information model to capture terrorist scenarios and plans. Objects in the model include scenarios, plans, tasks, generic tasks, objectives, targets, weapons, delivery methods, indicators, observables, resources, skills, roles, attacks, coordinated attacks, groups, people, hypotheses, and multiple scoring factors. The scoring information provides a way to link the model to the products of another project. We checked the information model for internal consistency, although not validity, but it has been reviewed by various analysts and has good face validity. The information model, developed using ORM (Object Role Modeling), was converted to a data model and an SQL (Structured Query Language) Server database design. We created an SQL Server database and populated it with a limited amount of surrogate data for tasks. Since the model and the database are still evolving, we developed a script for easily loading the evolving version of the

The ultimate goal for the nuclear-terrorist data model would be to allow subsequent development and deployment of automated computer-based tools to aid the intelligence community analyst. These tools would enable more effective synthesis of all-source intelligence data, thereby allowing earlier predictions of plausible planned or impending nuclear-terrorist attacks of high interest. Such a capability does not exist today.

New types of automated human-computer relationships would be explored, characterized, quantified, and exploited to greatly enhance national security.

database from spreadsheets. We held one Red Team game that resulted in two detailed terrorist plans and a number of variations or plan fragments. The information model provided a framework for capturing some, but not all, of the data and alternatives generated during the game. Given the team planning process, all of the data probably cannot be captured in real time, as opposed to post-game processing and data entry. However, considering the Red Team as a potential user of the database, a better interface would allow more of the data to be captured and used during the game. Along these lines, we conceptualized an icon-based user interface based on the key objects in the information model. We have not entered the game data into the database, but much of it fits within the database structure, and with minor database changes even more would fit.

63971

Enabling Technology for Human Collaboration

A. B. Doser, W. B. Jones, C. M. Johnson, D. J. Warner, T. A. Murphy

In this project, Sandia explored the potential of enabling technology to improve the performance of small groups. The purpose was to investigate and develop new methods to assist groups working in high-consequence, high-stress, ambiguous, and time-critical situations, especially those for which it is impractical to adequately train or prepare. We constructed a test-bed for exploratory analysis of a small group engaged in tasks with high cognitive and communication performance requirements. The system consisted of five computer stations, four with special devices equipped to collect physiologic, somatic, audio, and video data. We recruited and engaged test subjects in a cooperative video game. Each team member was provided with a sensor array for physiologic and somatic data collection while playing the video game. We explored the potential for real-time signal analysis to provide information that enables emergent and desirable group behavior and improved task performance.

The data collected in this study included audio, video, game scores, physiological, somatic, keystroke, and mouse-movement data. We explored the use of self-organizing maps (SOMs) to search for emergent trends in the physiological data as it correlated with the video, audio, and game scores. This exploration resulted in the development of two approaches for analysis, to be used concurrently—an individual SOM and a group SOM. We trained the individual SOM using the unique data of each person and used the data to monitor the effectiveness and stress level of each member of the group. We trained the group SOM using the data of the entire group and used the data to monitor the group's effectiveness and dynamics. Results suggested that both types of SOMs were required to adequately track evolutions and shifts in group effectiveness.

The main purpose of this project was to demonstrate the potential for the tools developed here to improve the effectiveness of groups and to suggest possible hypotheses for future exploration.

In phase one of this project, we constructed a MENTOR/PAL© test-bed and found it to be fully functional. In phase two, we recruited test subjects and asked them to collaborate in a group video exercise. We used the test-bed equipment to collect

...Sandia explored the potential of enabling technology to improve the performance of small groups. The purpose was to investigate and develop new methods to assist groups working in high-consequence, high-stress, ambiguous, and time-critical situations, especially those for which it is impractical to adequately train or prepare....The main purpose of this project was to demonstrate the potential for the tools developed here to improve the effectiveness of groups and to suggest possible hypotheses for future exploration.

various physiological and somatic data from the subjects. In addition, we recorded audio, video, and exercise results. We conducted a total of 10 sessions. In each session, we adjusted the settings of the video exercise to make it more challenging. As an added stress, we rotated subjects in and out of the study, which forced the remaining subjects to become accustomed to a different group makeup.

We began analysis by watching the subjects and making observations concerning leadership and cooperation characteristics of the group. We analyzed performance, both group and individual. We analyzed each session videotape for examples of events of interest, including cooperation, conflict, leadership, and character death. We time-synchronized these events of interest and compared them to the heart-rate data, using time/frequency techniques, to check for correlations. We found correlations and isolated evidence of group cooperation using the heart-rate data.

The results of the heart-rate analysis led to the development of two different ways to approach the physiological and somatic data using SOMs. We tested both approaches on actual subject data and found them to yield interesting potential for future use. We developed one approach using separate SOMs to monitor the productivity of each individual. It was shown that a separate SOM was needed for each individual. The second approach used a conglomeration of data for the group to train a SOM to monitor the effectiveness of the group. We showed that this SOM may be able to identify signatures of group cooperation and conflict. It was suggested that both types of SOMs be used in conjunction to improve the functionality of the group. We made suggestions concerning how the two SOMs may be used together.

The work in this project constitutes the first steps in the development of research in this area at Sandia. Its purpose is to demonstrate proof-of-concept and pose questions that can be explored in future studies. Throughout the study, suggestions were noted for future work. They are included here.

(1) Inclusion of the electroencephalogram (EEG) collection in future work may provide evidence of a correlation in what is termed in this report "low-confidence events." The addition of EEG data would no doubt create a more accurate SOM.

(2) Eye-tracking technology could be implemented and incorporated into the SOM to make many of the classification of "high-confidence events" automatic.

(3) Running parallel studies using multiple subject groups on the same tasks would help to confirm or disprove the observations noted in this study.

The results of the heart-rate analysis led to the development of two different ways to approach the physiological and somatic data using SOMs. We tested both approaches on actual subject data and found them to yield interesting potential for future use....The work in this project constitutes the first steps in the development of research in this area at Sandia. Its purpose is to demonstrate proof-of-concept and pose questions that can be explored in future studies.

(4) The leader of the group seemed to exhibit stress at the death of others, and later, another member of the group seemed to behave the same way. Further testing should be done to determine if this is a signature of leadership, collaboration, or coincidence.

(5) Further analysis should be performed on the effect on the group of having subjects enter and exit the study at prescribed intervals.

(6) The MENTOR/PAL© concept should be explored further to find if there truly is a difference between individual and group physiological dynamics, as was observed in this study.

(7) More recorded data parameters could be included in the SOM training to likely produce a more-complete picture of group effectiveness.

(8) The Human Studies Board agreement could be amended, allowing for two independent observers to view the videotapes. Such analysis could produce publishable results and supporting material for physiological data findings.

(9) A specialized wavelet-based transform could be designed to examine heart rate and other data with desired time/frequency resolution in spectral areas of interest.

Other Communications

Merkle, P. B., A. B. Doser, C. M. Johnson, W. B. Jones, D. J. Warner, and T. A. Murphy. 2003. Group collaboration technology development. Paper presented at the NASA-NIOSH Human Performance Conference, Houston, Texas.

Merkle, P. B., G. Yonas, A. B. Doser, W. B. Jones, C. M. Johnson, D. J. Warner, and D. Sparks. 2003. MENTOR/PAL© LDRD Project. Sandia video segment, Sandia National Laboratories, Albuquerque, New Mexico.

Merkle, P. B., C. M. Johnson, and W. B. Jones. 2003. Brain-machine interfaces: The network. Paper presented at the Lockheed-Martin Skunkworks Symposium, Albuquerque, New Mexico. SAND2003-1204P.

64386

Large-Scale System-Dynamics Modeling of Water Resources on the Rio Grande

H. D. Passell, V. C. Tidwell, G. C. Newman

This project will build the world's first large-scale, system-dynamics (SD) water-management model, providing a powerful "decision-support" tool for resource planners. It is innovative because of the multisystem approach (i.e., hydrology, ecology, agriculture) applied at a large geographic scale. This project will enhance Sandia's current leadership in this field.

- *Technical strengths. SD modeling integrates the behavior of multiple interacting systems that change over time, including feedbacks and time lags. Sandia leads in the application of SD modeling to water resources and has built a small model of the Middle Rio Grande Basin (MRGB, 100 river mi, 24,000 mi² watershed) that now plays an important role in regional water planning.*

The proposed project would create a model many times larger than the existing MRGB model, from Fort Quitman (near El Paso) to the Gulf of Mexico (1170 river mi, 149,000 mi² watershed). This introduces significant technical problems, including the following: (1) How must data resolution, handling, and modeling techniques change? (2) How can we integrate data collected over multiple jurisdictions, with different data-quality standards and temporal/spatial scales? (3) Can a useful large-scale model be built within reasonable time/cost constraints?

- *Programmatic strengths. Water scarcity is widely recognized as a critical national/international security issue. New and highly innovative solutions are required to avert social, political, and economic destabilization over water scarcity. Sandia's water initiative focuses on applying Sandia technologies to water safety, security, and sustainability at all scales. This project will lead to large-scale modeling capabilities that can be applied in river basins around the world, and to other large-scale modeling projects (i.e., oil and gas distribution, electricity, transportation, etc.).*

The first task in modeling the lower Rio Grande was to begin an exhaustive search for information and data available on lower Rio Grande hydrology. We convened our first project meeting, during which we resolved various data and modeling issues and created a schedule for activities and accomplishments.

This project will build the world's first large-scale, system-dynamics (SD) water-management model, providing a powerful "decision-support" tool for resource planners. It is innovative because of the multisystem approach (i.e., hydrology, ecology, agriculture) applied at a large geographic scale. This project will enhance Sandia's current leadership in this field.

67542

Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application

B. A. Simmons, R. W. Bradshaw, T. W. Lane, S. Chhabra

*Clathrate hydrates are crystalline inclusions of water and gas and are the world's single largest natural-gas reservoir. These hydrates are typically found on the seafloor, where methane-oxidizing and sulfate-reducing bacteria digest and metabolize these methane hydrates. A type of polychaete worm, *Hesiocaeca methanicola*, is believed to feed off of the bacteria located in the hydrate zones and also to contribute to the dissolution of hydrates in exposed sediments. Sandia seeks to begin the first scientific investigation into this interaction between biological organisms and methane-hydrate energy sources. By understanding how these organisms utilize hydrates as an energy source for their specific metabolic cycles, we may be able to tap into that pathway for our own energy demands. By bringing an applied-science solution to this field, we can quickly answer the question of how these organisms interact and thrive, if at all, on artificially created gas hydrates in the laboratory. We will determine if we can grow methanotrophic bacteria in artificially generated methane hydrates and measure their growth rates and methane-oxidation rates. We will then repeat with a seafloor-hydrate core sample and measure the presence and activity of *Hesiocaeca methanicola*. We will use these experiments to develop a knowledge base aimed at understanding the interactions between biological organisms and methane hydrates, and ultimately harnessing this hydrate life cycle for energy production and storage. The successful completion of this work will have applications to the Department of Energy and others pursuing the realization of a methane-hydrate energy resource, and for whom understanding this interaction could be critical. Sandia has the requisite and unique combination of expertise in the areas of materials science, analytical chemistry, biochemistry, and molecular and cellular biology that is vital to the success of this project.*

We initiated this research project by identifying suitable biological organisms. We identified a psychrophilic methanotroph, *Methylosphora hansonii*, and received two samples of this organism. We are currently culturing these methane-oxidizing bacteria at 4°C in an artificial sea-salt medium in the presence of oxygen and methane.

Sandia researchers are trying to determine the link between methane stored in the form of hydrate crystallites (left) and biological organisms (right, labeled with a fluorescent DNA stain). These organisms may process this stabilized methane as a metabolic source of energy. It is hoped that this research may lead to a fundamental understanding of this life cycle that could then benefit our own energy needs. Image of methane hydrates was obtained from www.netl.doe.gov.

Sandia seeks to begin the first scientific investigation into this interaction between biological organisms and methane-hydrate energy sources.

Additionally, we purchased a reactor from Parr Instruments that we will use for the formation and testing of methane hydrates and their impact on biological activity. We will conduct these experiments in closed low-pressure vessels (< 300 psig) held at 2° – 8°C in a methane-water system, with periodic sampling to verify activity through cell-counting techniques as well as metabolic indicators from the oxidation of methane. These experiments will quickly show the feasibility of using artificial hydrates as a high-pressure petri dish for these organisms.

We are also in the process of contacting the National Methane Hydrate Program to obtain and utilize a core sample of seabed hydrates that contain the organisms mentioned above. At the end of this project, we will compile and assemble a report on using artificial hydrates to study biological organisms and their metabolic activity thereof, and the recommended next steps for future work.

Corporate Objectives

Sandia collaborates with universities to create new science and engineering for the Laboratories' science and technology base, to train the next generation of scientists and engineers, and to employ complementary resources and skills for achieving common goals. These collaborations improve Sandia's ability to recruit top students for Sandia's work force and to ensure Sandia's future as a leader in science and technology.

The ability to manipulate nanoscale structures and molecular interactions is at the heart of the next revolution in programmable microsystems. We believe that the full benefit of this technology will only be achieved when microscale addressability is used to control materials properties and molecular interactions. *Molecular Integrated Microsystems (MIMS)* is pursuing a revolutionary approach to microsystems in which microscale patterning of functional materials is combined with local addressing (electrical, optical, thermal fields) to provide fully programmable systems and architectures. The

overall goal of this project is to combine molecularly tailored nanomaterials with addressable microdevice architectures to demonstrate a device for sorting complex protein mixtures that are important for bio-threat and human health problems. This project has filed a total of 14 patent disclosures and 8 patent applications. The work has received two patents and the E. O. Lawrence award.

11130

Molecular Integrated Microsystems (MIMS)

L. M. Napolitano, A. K. Singh, J. Liu, A. P. Thompson, C. J. Brinker, B. C. Bunker, G. D. Bachand, K. Wally, B. J. Kirby, R. F. Renzi, S. A. Casalnuovo, T. J. Shepodd, R. Shediach, D. L. Huber, D. S. Reichmuth, S. Song, S. A. Pizarro, P. Selvaganapathy

Sandia completed a system to interface to and run a two-dimensional (2-D) separation on chip for analysis of cytokines in the presence of albumin. A fluid interface directly bolts to a custom-designed dual-channel laser-induced fluorescence (LiF) module, allowing interface of fluids with the microchip and collection of two-point fluorescence data. The entire system is approximately 4 in. x 4 in. x 6 in., including power, lasers, detectors, chip, and fluidic interface.

We evaluated several separation techniques for cytokine profiling and performed on-chip separations of multiple cytokines. We evaluated two techniques for concentration and subsequent elution of cytokines, demonstrating 1–2-orders-of-magnitude concentration. We developed and tested microfluidic valving capable of controlling both high voltage and high pressure.

We developed complex microchips involving chip-level integration of several photopatterned polymer elements (separation media, valving, preconcentration) and implemented them to analyze cytokine samples with a view toward early pathogen detection based on cytokine profiling.

- **Separation.** We evaluated multiple separation methods for cytokine profiling, including (1) sodium dodecyl sulphate polyacrylamide gel electrophoresis (SDS-PAGE) using photopatterned polyacrylamide, (2) native PAGE, (3) isoelectric focusing, and (4) zone electrophoresis.

All of these methods can resolve cytokines, but the key question is which two of these are the easiest to couple on the same chip. A functional coupling requires the two separations to be orthogonal in nature to provide maximum information and resolution. It also requires that between the two separations, there is compatibility in buffer, surface functionalization, and fluid transport mechanism. Based on these criteria, we chose SDS-PAGE and zone electrophoresis as the two separations to couple.

Using *in situ* photopolymerized polyacrylamide gel, on-chip SDS-PAGE separations of a mixture of three cytokines (epidermal growth factor [EGF], interleukin-2 [IL2], and interferon alpha [IFN α]) and albumin occurred within 20 s and required a separation length of less than 1 cm. Without denaturing in SDS, multiple complexes did exist within some

Hybrid microfluidic system for high-pressure-flow control. (Top) Microfluidic valving in an open position. Flow proceeds from left to right within glass microchannels. (Bottom) Upon application of an external control pressure, a mobile element consisting of a porous polymer with perfluorinated interstitial liquid moves to seal the channel closed. These microfluidic valves uniquely enable routing of flows in high-pressure analysis systems.

Sandia completed a system to interface to and run a two-dimensional (2-D) separation on chip for analysis of cytokines in the presence of albumin.

cytokine samples, preventing native PAGE from resolving cytokine mixtures. In the second dimension, the cytokines would be resolved based on charge/hydrated radius.

- *Preconcentration.* We designed two concentration techniques for cytokine processing via controlled retention and release.

(1) We synthesized porous poly(n-isopropyl acrylamide) (PNIPAM) structures in capillaries and microfluidic chips through an *in situ* polymerization. We demonstrated these porous polymers to concentrate protein through controlled adsorption and release. Passing a dilute protein solution through the polymer at a slightly elevated temperature (40°C) causes the protein to be efficiently adsorbed. Cooling to room temperature releases the accumulated protein from the surface, creating a more concentrated protein solution. We concentrated protein solutions by more than an order of magnitude.

(2) Electrokinetic (EK) trapping involves the retention of protein molecules at nanoporous interfaces when an electric field is applied. Subsequent elution of the accumulated protein upon pressure flow allows for controlled release.

We demonstrated the EK trapping of albumin (bovine serum albumin [BSA] and cytokines [IL-2]) in porous monoliths fabricated in capillaries. We also demonstrated microfabrication of the porous monolith, with varying lengths between 2 cm and 2 mm, in glass chips with optimization of the polymerization time and ultraviolet (UV) wavelength. We also demonstrated trapping of a variety of proteins (BSA, lactalbumin, cytokines [EGF, IL-2]) and their subsequent elution on chip.

- *Microfluidic valving.* We developed microfluidic valving for control of high pressures and voltages on chip. Chip-level integration requires that valve materials be changed to allow for processing of a variety of solvents and insulation against electrical current, and that world-to-chip interfaces be robust enough to allow operation over periods of months. Materials changes allowed valve operation in a wide variety of solvents, and we achieved control of voltage through hybridization of polymer structures with high-dielectric-strength interstitial liquid.

Current valve elements have been in continuous high-pressure operation for months without failure and have allowed for autonomous operation of model high-pressure control systems (e.g., on-chip reversed-phase [RP] high-performance liquid-chromatography [HPLC] analysis) over tens of thousands of control steps.

- *Integration—chip-level.* We chose EK trapping for chip-level integration because no temperature control was needed.

Current valve elements have been in continuous high-pressure operation for months without failure and have allowed for autonomous operation of model high-pressure control systems (e.g., on-chip reversed-phase [RP] high-performance liquid-chromatography [HPLC] analysis) over tens of thousands of control steps.

We serially deposited EK trapping media, PAGE separation media, and microfluidic valving in the microfluidic chip.

We developed protocols for integrated operation of preconcentration stage capillary zone electrophoresis (CZE) separation and demonstrated SDS-PAGE separation.

We used the integrated system to analyze cytokine samples with a view toward blood-sample analysis for presymptomatic detection of disease.

- *Integration—microfluidic packaging.* We developed a complete system to interface to and run a 2-D separation on chip, including fluidic manifold, multipoint LiF detection, power, and software control.

Refereed

Hasselbrink, Jr., E. F., T. J. Shepodd, and J. E. Rehm. 2003. High-pressure microfluidic control in lab-on-a-chip devices using mobile polymer monoliths. *Analytical Chemistry* **74** (19): 4913–18.

Huber, D. L., R. P. Manginell, M. A. Samara, B. I. Kim, and B. C. Bunker. 2003. Programmed adsorption and release of proteins in a microfluidic device. *Science* **301**:352.

Kirby, B. J., and E. F. Hasselbrink, Jr. 2003. The zeta potential of microfluidic substrates. 1. Theory, experimental techniques, and effects on separations. *Electrophoresis*, accepted.

Kirby, B. J., and E. F. Hasselbrink, Jr. 2003. The zeta potential of microfluidic substrates. 2. Data for polymers. *Electrophoresis*, accepted.

Kirby, B. J., A. R. Wheeler, R. N. Zare, J. A. Fruetel, and T. J. Shepodd. 2003. Programmable modification of cell adhesion and zeta potential in silica microchips. *Lab on a Chip* **3**:5–10.

Kirby, B. J., T. J. Shepodd, and E. F. Hasselbrink, Jr. 2003. Voltage-addressable on/off microvalves for high-pressure microchip separations. *J. Chromatography A* **979**:147–54.

Reichmuth, D. S., and B. J. Kirby. 2003. Effects of ammonioalkyl sulfonate internal salts on electrokinetic micropump performance and reversed-phase high-performance liquid-chromatographic separations. *J. Chromatography A, Proc. HPLC 2003* **1013** (April, San Diego, California): 93–101.

Other Communications

Artau, A., A. K. Singh, and T. J. Shepodd. 2002. Electrokinetic trapping of proteins in cast-to-shape matrices. *MicroTAS 2002* **1** (November, Nara, Japan): 476–78.

Bunker, B. C., D. L. Huber, R. P. Manginell, B. I. Kim, A. K. Boal, G. D. Bachand, S. B. Rivera, J. M. Bauer, and C. Matzke. 2003. Incorporation of bioactive materials into integrated systems. *Proc. SPIE* **5220** (August, San Diego, California).

Fintschenko, Y., B. J. Kirby, E. F. Hasselbrink, Jr., A. K. Singh, and T. J. Shepodd. 2003. Miniature and Microchip Technologies. Chapter in *Monolithic materials: Preparation, properties, and applications*. Amsterdam: Elsevier.

Han, J., and A. K. Singh. 2002. Miniaturization of protein separation: Isoelectric focusing and SDS-PAGE. *MicroTAS 2002* **1** (November, Nara, Japan): 596–98.

Kirby, B. J., and A. K. Singh. 2002. *In situ* fabrication of dialysis membranes in glass microchannels using laser-induced phase-separation polymerization. *MicroTAS 2002* 2 (November, Nara, Japan): 742–44.

Kirby, B. J., and T. J. Shepodd. 2002. Microvalve architectures for high-pressure hydraulic and electrokinetic fluid control in microchips. *MicroTAS 2002* 1 (November, Nara Japan): 338–40.

Nilson, R. H., S. K. Griffiths, and A. K. Singh. 2002. Injection of sample bands from open channels into packed separation columns. *MicroTAS 2002* 1 (November, Nara, Japan): 97–9.

Reichmuth, D. S., T. J. Shepodd, and B. J. Kirby. 2003. Nanoengineered microvalves for control of harsh solvents and high pressure in microfluidic systems. *J. Microelectromechanical Systems*, to be submitted.

Reichmuth, D. S., T. J. Shepodd, and B. J. Kirby. 2003. RP-HPLC microchip separations with subnanoliter on-chip pressure injections. *MicroTAS 2003* 2 (October, Squaw Valley, California): 1021–24.

Shediac, R., S. A. Pizarro, A. E. Herr, and A. K. Singh. 2003. Ultrafast on-chip separations of cytokines by SDS-PAGE using UV-initiated polyacrylamide. *MicroTAS 2003* 2 (October, Squaw Valley, California): 971–73.

Singh, A. K., D. J. Throckmorton, and B. J. Kirby. 2003. Electrokinetic focusing of proteins at nanopore interfaces. (Invited) Paper presented at the AIChE Meeting, November, San Francisco, California.

Singh, A. K., D. J. Throckmorton, B. J. Kirby, and A. P. Thompson. 2002. A novel miniaturized protein preconcentrator based on electric-field-addressable protein capture and release. *MicroTAS 2002* 1 (November, Nara, Japan): 347–49.

Song, S., A. K. Singh, T. J. Shepodd, and B. J. Kirby. 2003. Microchip dialysis of proteins using *in situ* photopatterned nanoporous polymer membranes. *Analytical Chemistry*, submitted.

Song, S., T. J. Shepodd, A. K. Singh, and B. J. Kirby. 2003. Microchip-based dialysis of protein samples using photopatterned nanoporous membranes. *MicroTAS 2003* 1 (October, Squaw Valley, California): 421–24.

32817

Molecular Simulations of MEMS and Membrane Coatings (PECASE)

A. P. Thompson

Self-assembled monolayers (SAMs), which are ultrathin organic layers that are chemically and/or physically attached to solid inorganic supports, are important in many areas of technology. Two prime examples are MEMS (microelectromechanical systems) and gas-separation membranes. SAMs are used in MEMS components as adhesion and friction reducers. Although their performance can be measured in situ on MEMS devices, the structure and dynamics of the SAM coatings is only partially understood. A better understanding of the molecular-scale phenomena will provide fundamental knowledge of performance and degradation mechanisms. Such knowledge is an essential requirement to predict the performance of MEMS devices with usage and aging. SAMs have also been used as key elements in gas-separation membranes. In several laboratories, membranes have been created by the deposition of SAM films on nanoporous supports, such as silica and alumina. These “hybrid” membranes show significantly increased selectivity for heavier organics and vapors, meaning that they will be useful for environmentally relevant separations such as the removal of volatile organic compounds (VOCs) from air. However, the mechanisms that lead to this increased selectivity have not been isolated; this is essential if better hybrid membranes are to be developed. Sandia proposes to use molecular simulation as a means to study the structure-property relationships of SAMs in both MEMS devices and gas-separation membranes. The MEMS studies will use molecular dynamics (MD) simulations to study the effects of chain length and degree of fluoro-substitution on the ability of SAMs to reduce adhesion forces between silica surfaces. The membrane studies will use a combination of MD and Monte Carlo simulations to predict the transport rate of various gas species across a SAM-treated nanoporous membrane, and to examine the molecular-level transport mechanisms that occur. We will also carry out some experiments to validate the simulations.

Sandia carried out several activities related to the synthesis and testing of novel composite membranes that are composed of nanoporous ceramic supports decorated with organic phases. Experimental work focused on the relationship between synthesis variables (e.g., chemical functionality and reactivity

Although their performance can be measured in situ on MEMS devices, the structure and dynamics of the SAM coatings is only partially understood. A better understanding of the molecular-scale phenomena will provide fundamental knowledge of performance and degradation mechanisms. Such knowledge is an essential requirement to predict the performance of MEMS devices with usage and aging....Sandia proposes to use molecular simulation as a means to study the structure-property relationships of SAMs in both MEMS devices and gas-separation membranes.

of the organic phase, hydration state of the porous support) and the permselectivity performance of the membranes in environmentally important separations (e.g., recovery of VOCs from air, separation of butane from natural gas). Molecular simulations aided us in this task by elucidating the relationship between molecular-level structure and separation performance. Simulation results strengthened certain key hypotheses from the experimental work.

We made significant progress in several areas of the composite organic-inorganic membrane project. We published one paper on the separation of binary gas mixtures (propane/nitrogen and butane/methane) using 5 nm porous membranes modified with octadecyltrichlorosilane surface films. We also submitted a paper on the use of synthesis variables, such as the hydration state of the surface and the functionality of the organic reagent, to rationally modify permeation properties. In collaboration with Texas A&M University, Department of Chemistry, we evaluated several new surface-chemistry routes to deposit organic phases on the porous materials. These new routes provide better means to control surface coverage in the composites. We completed our initial work on toluene/nitrogen vapor-permeation experiments for VOC recovery applications, using aromatic dendrites as the organic surface phases. For these separations, the selectivity was nearly equal to that of the best polymer currently used in industry, and the permeance was much higher.

We also had a major finding from our molecular modeling work on these systems. MD simulations indicated that the ability of the organic phase to span the entire width of the nanopores was key in providing high selectivity. This finding was consistent with our experimental observations related to the chemical nature and functionality of the organic phase.

...we evaluated several new surface-chemistry routes to deposit organic phases on the porous materials. These new routes provide better means to control surface coverage in the composites. We completed our initial work on toluene/nitrogen vapor-permeation experiments for VOC recovery applications, using aromatic dendrites as the organic surface phases. For these separations, the selectivity was nearly equal to that of the best polymer currently used in industry, and the permeance was much higher.

Refereed

Javaid, A., and D. M Ford. 2003. Solubility-based gas separation with oligomer-modified inorganic membranes. Part II. Mixed gas permeation of 5 nm alumina membranes modified with octadecyltrichlorosilane. *J. Membrane Science* **215**:157–68.

Javaid, A., D. A. Krapchetov, and D. M Ford. 2003. Membranes for solubility-based gas separations from the deposition of self-assembled monolayers on microporous alumina. *J. Physical Chemistry B*, accepted.

Javaid, A., S. Gonzalez, E. Simanek, and D. M Ford. 2003. Hierarchically nanostructured organic-inorganic membranes for environmentally important separations. Paper presented at the American Institute of Chemical Engineering Annual Meeting, November, San Francisco, California.

34692

Self-Assembly of Polymers in Confined Geometries

J. G. Curro

Self-assembly of molecules is nature's way of creating ordered structures on a nanometer scale. Depending on their architecture, certain molecules such as block copolymers will spontaneously order themselves on a scale that would be impossible to achieve by ordinary polymer-processing techniques. This property makes self-assembly a powerful tool for producing nanostructured materials. Some applications include low dielectric constant materials, microfluidic devices, sensors, membranes, microelectronics, and microelectromechanical systems (MEMS) devices.

As polymers are used for these applications, it is necessary to understand how the confined geometry influences the properties of the polymer. It is well known that miscibility, viscoelastic properties, density, and the glass transition in thin films can be quite different from the corresponding bulk properties. The purpose of this project is to develop the computational tools to model the properties of polymers near surfaces and in confined geometries.

Sandia will collaborate on this project with the New Mexico Institute of Mining and Technology.

We incorporated the effect of attractive polymer/polymer and surface interactions on free chains into our density-functional theory (DFT). We used this theory to study the density profiles of linear polymers near a surface as a function of the strength of attraction, and we compared the results with molecular dynamics (MD) simulations. We showed DFT to be extremely accurate for athermal systems (repulsive interactions only), but it is only in qualitative agreement with simulation when the attractions are turned on. Unlike bulk systems where the environment around a given site is isotropic, monomers near a surface experience an anisotropic environment, and the density profile depends sensitively on the balance between surface attractions that draw the polymer to the surface and molecular attractions that cause the polymer to de-wet the surface. Additional research is required to improve the ability of DFT to accurately account for this balance of interactions.

By contrast with free chains, our modifications to DFT can successfully account for the effect of attractions on tethered chain systems. We applied this DFT to poly(*n*-isopropyl acrylamide) (PNIPAM) polymer tethered to modified gold

It is well known that miscibility, viscoelastic properties, density, and the glass transition in thin films can be quite different from the corresponding bulk properties. The purpose of this project is to develop the computational tools to model the properties of polymers near surfaces and in confined geometries.

surfaces in contact with water. The results are in good agreement with the neutron reflectivity experiments of Kent and Yim. In particular, both theory and experiment show significant differences in the concentration profiles of the polymer at temperatures below and above the lower critical solution temperature of the bulk polymer in aqueous solution.

We generalized our DFT to allow the computation of the forces between surfaces. This allows us to directly compare our theoretical results with atomic-force microscopy experiments.

Refereed

McCoy, J. D., Y. Ye, and J. G. Curro. 2003. Application of density-functional theory to tethered polymer chains. Paper presented at the American Physical Society Meeting, March, Austin, Texas.

Ye, Y., J. D. McCoy, and J. G. Curro. 2003. Application of density-functional theory to tethered polymer chains: Effect of intermolecular attractions. *J. Chemical Physics* **119**:555.

34693

Building Conscious Machines Based Upon the Architecture of Visual Cortex in the Primate Brain

G. C. Osbourn, G. Yonas

A very productive approach to gaining a better understanding of human vision at the system level has been to use eye-tracking devices to evaluate local image statistics at the locations visited by the eyes, while animal or human observers inspect complex visual scenes. Most such research interested in characterizing “where the eyes look” has focused on local image properties at fixated locations. In parallel, computer-vision research has attempted over the past decades to detect features and objects in imagery by means of local operators, such as edge detectors. One major difficulty with these approaches is their inherent susceptibility to noise, yielding many irrelevant false positives when confronted with natural scenes. Based on Sandia’s past experience with modeling such interactions in detailed psychophysical models on the one hand, and on developing large-scale models with real machine-vision applications on the other hand, we propose to incorporate these interactions into our bottom-up attention model and to tune its parameters using supervised learning, with teaching signals provided by novice and expert visual analysts looking at complex overhead imagery. The present proposal will focus on integrating those and further modeling and experimental results into a biologically inspired model of early visual processing that can be applied to natural scene and overhead imagery. The work will be performed in collaboration with Cal Tech University.

We developed three new model components to significantly enhance our ability to predict human eye movement patterns: (1) short-range orientation interactions (for clutter reduction), (2) long-range orientation interactions (for contour facilitation), and (3) retinal filtering (for fovea versus periphery effects). An often forgotten fact of our visual life is that our visual acuity is best only in the central several degrees of our visual field. Our ability to perform tasks with peripheral vision decays dramatically with increasing eccentricity. This effect is modulated by spatial frequency, in that peripheral vision’s deficit relative to foveal vision is much worse for high spatial frequencies than for low spatial frequencies. In particular, previous psychophysical studies have quantified the eccentricity and spatial frequency dependence of two tasks:

We developed three new model components to significantly enhance our ability to predict human eye movement patterns:

- (1) short-range orientation interactions (for clutter reduction), (2) long-range orientation interactions (for contour facilitation), and (3) retinal filtering (for fovea versus periphery effects).*

(1) contrast detection (how much contrast does a grating patch need to be distinguishable from a uniform gray background), and (2) orientation discrimination (how much contrast is needed so that a horizontal grating can be distinguished from a vertical grating). It has also been shown that people tend to make saccades to locations near their current fixation point. Thus, on average, saccades tend to neglect more peripheral locations. In other words, a peripheral location requires much higher salience (such as a flashing light) to elicit a saccade than does a central location.

We asked whether we could quantitatively predict this effect in our eye-tracking data by modulating the saliency model's internal maps according to data from the literature on contrast detection and orientation discrimination. Again, we found that this modification provides a significant improvement in the model's ability to predict human eye movements. Furthermore, we found that we were able to obtain similarly good results with an approximation of the retinal filter, in which the final saliency map is modulated with a mask that decays exponentially away from the fixation location. This is an ideal outcome in biologically inspired computational modeling. We designed a detailed retinal filter based on independent physiological data, showed that this filter lends a substantial benefit to the saliency model, and then showed that there is a simple and efficient approximation that maintains the benefits of the full model.

...we found that we were able to obtain similarly good results with an approximation of the retinal filter, in which the final saliency map is modulated with a mask that decays exponentially away from the fixation location. This is an ideal outcome in biologically inspired computational modeling.

35376

Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture

N. R. Moody

This project is a joint research project between Sandia and Washington State University. There currently are few experimental testing methods that can assess nonlinear deformation and fracture phenomena on the micrometer and submicrometer length scales. Those that exist are often not verified using a second experimental approach. Nanoindentation techniques have been developed to probe failure modes, including film fracture and delamination, but these tests are difficult to verify without resorting to other indentation or scratching techniques. Therefore, a study that will allow for the development of testing using an independent technique (bulge testing and blister testing) will be applied to materials systems of interest to film-substrate systems that can be used as models for components in the stockpile. We will perform additional testing on materials that exhibit nonlinear deformation and shear band formation under high stresses. As both systems, nanoindentation and bulge testing, can be carried out in aqueous environments that are environmentally aggressive, we will perform testing correlation under various thermochemical environments to ensure the robust nature of the experimental procedure. We will then compare the results of all of these tests to simulations in projects supported in the Accelerated Strategic Computing Initiative (ASCI) program to show applicability of the testing methods to future verification of simulations for lifecycle engineering.

There currently are few experimental testing methods that can assess nonlinear deformation and fracture phenomena on the micrometer and submicrometer length scales. Those that exist are often not verified using a second experimental approach. ...a study that will allow for the development of testing using an independent technique (bulge testing and blister testing) will be applied to materials systems of interest to film-substrate systems that can be used as models for components in the stockpile.

Atomic-force microscope (AFM) deflection images show light areas as the tip moves down and dark areas as the tip moves up. Darker or lighter areas correspond to increasing or decreasing slope.

We demonstrated the effectiveness of the bulge-testing method in comparing with indentation-induced testing. We are examining a microelectromechanical systems (MEMS) structure, Si/Ti/Pt/PZT/Au (where PZT is lead zirconate titanate, $\text{Pb}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$). One significant area of interest is the interface between the platinum (Pt) and silicon (Si), and the effects of a titanium (Ti) adhesion layer. Another area of concern is the strength of the entire system when pressure is applied to a thin membrane.

We carried out bulge testing of the structure and determined the strain at failure for the entire stack. Fracture testing on the MEMS structures (3 mm-square membranes, with a total thickness of 3 μm) demonstrated that the failure strain on the membrane is 0.35% when PZT is pressurized in tension, but fails at only 0.17% when the film is pressurized in compression. We used these results to carry out nanoindentation testing, comparing the strain at failure using indentation-induced fracture to the bulge-testing results.

Previous studies demonstrated that adhesion between the Pt and Si was a concern during fatigue bulge testing. We performed an indentation-induced adhesion test to verify that the interfacial fracture could be quantified. The addition of a Ti adhesion layer between Pt and silicon dioxide (SiO_2) improves the adhesion of the film from 0.4 to 1.8 J/m^2 .

The work of tracking deformation around indentations to examine the influence of underlying substrate on film fracture has continued. Of primary importance in this area of the work is the identification of slip behavior with stacking fault energy (SFE) in face-center cubic (FCC) alloys. Low SFE causes very planar slip around indentations, while higher SFEs cause wavy glide. The slip systems can be identified in all cases using atomic-force microscopy and orientation-imaging microscopy.

Refereed

Bahr, D. F., C. L. Woodcock, M. Pang, K. D. Weaver, and N. R. Moody. 2003. Indentation-induced film fracture in hard film–soft substrate systems. *International J. Fracture*, accepted.

Bahr, D. F., K. A. Nibur, K. R. Morasch, and D. P. Field. 2003. Hydrogen and deformation: Nano- and microindentation studies. *J. Metals* **55**:27–50.

Volinsky, A. A., D. F. Bahr, M. Kriese, N. R. Moody, and W. W. Gerberich. 2003. Nanoindentation methods for interfacial fracture testing. In *United Kingdom Encyclopedia on Comprehensive Structural Integrity*, vol. 8, *Interfacial and nanoscale failure* (Elsevier), vol. ed. W. W. Gerberich and W. Yang; editors-in-chief, I. Milne, R. O. Ritchie, and B. Karihaloo. SAND2002-8616.

Other Communications

Bahr, D. F., K. A. Nibur, K. A. Morasch, and D. P. Field. 2002. Probing hydrogen–deformation interactions using nanoindentation. *Proc. International Conference on Hydrogen Effects on Material Behavior and Corrosion Deformation Interactions* (Jackson Lake Lodge, Moran, Wyoming).

Cordill, M. J., N. R. Moody, and D. F. Bahr. 2003. Adhesion of thin ductile films using the stressed overlayer method. *Proc. TMS Annual Meeting, Surface Engineering: In Materials Science II* (San Diego, California): 41–7.

Cordill, M. J., T. Muppidi, and D. F. Bahr. 2003. Grain-size effects on the adhesion of thin ductile films. *Mechanical Properties Derived from Nanostructuring, Proc. MRS Spring Meeting* (San Francisco, California).

Nibur, K. A., and D. F. Bahr. 2003. Indentation techniques for the study of deformation across grain boundaries. *Mechanical Properties Derived from Nanostructuring Materials, Proc. MRS Spring Meeting* (San Francisco, California).

Nibur, K. A., and D. F. Bahr. 2003. Localized deformation around nanoindentations and the effects of hydrogen on dislocation cross slip. *Proc. TMS Annual Meeting, Materials Lifetime Science and Engineering* (San Diego, California): 69–75.

36902

Mathematical Analysis of Deception

N. A. Durgin, F. B. Cohen, J. D. Howard

In the last few years, deception has emerged as one of the key techniques for effective information protection in networks. A natural side effect of the use of this technology is the desire to understand the mathematical properties underlying its utility. Several informal notions have been introduced regarding this, for example:

- Deception increases the attacker's workload because he can't easily tell which of his attack attempts work and which fail.*
- Deception allows defenders to track attacker attempts at entry and respond before attackers come across a vulnerability to which the defenders are susceptible.*
- Deception exhausts attacker resources.*
- Deception increases the sophistication required for attack.*
- Deception increases attacker uncertainty.*

The goal of this project is to examine these claims and provide a more mathematical foundation for this aspect of deception as a tool for network defense. Sandia's collaborative research with the University of California at Davis and the Center for Cyber Defenders (CCD) benefits improved understanding that can be applied to the infrastructure of the Department of Energy complex, since its results will prove beneficial to the wider national defense issues of computer networks.

The results of our research seem to support the common notions about deception that are outlined in the abstract. Deception techniques have the demonstrated ability to increase attacker workload and reduce attacker effectiveness. In addition, deception can decrease the defender's effort required for detection and provide substantial increases in the defender's understanding of the attacker's capabilities and intent. Anecdotal evidence seems to indicate that even belief that deception technology is in use on a system can result in some benefit to the defender, because attackers don't trust their results and do more cross-checking, resulting in slower progress. This research resulted in four papers and five patent applications, as well as several related projects that are already under way to deploy deception technologies to defend information systems at both the network and host levels.

The goal of this project is to examine these claims and provide a more mathematical foundation for this aspect of deception as a tool for network defense. Sandia's collaborative research...benefits improved understanding that can be applied to the infrastructure of the Department of Energy complex, since its results will prove beneficial to the wider national defense issues of computer networks.

This research also resulted in the creation of a set of patents that includes techniques associated with substitution of system calls, the use of process lineage for deception and detection of attacks, the creation of dual systems for deception, and a range of other techniques, all derived from the mathematical understandings developed in this project.

Refereed

Cohen, F. C., and D. K. Rogers. 2003. Leading attackers through attack graphs with deceptions. *Computers and Security* **22** (5): 10.

36904

A System-Dynamics Approach to Modeling Water Demand

V. C. Tidwell, H. D. Passell

Fresh water is central to the vitality of our society; however, national and international demands are increasingly being met through unsustainable practices. Unfortunately, management of this precious resource is complicated by the different values placed on water by various sectors of our society (i.e., industry, agriculture, environmental protection, recreation). Modeling tools are needed to quantify these differing value systems and their relation to supply.

Sandia seeks a system-dynamics approach to modeling freshwater demand. This approach provides a comprehensive framework for quantitatively modeling the values ascribed to water. Here, our concern is for market-driven values (economic) and nonmarket values (e.g., environmental, ecological, and cultural) alike. We are making efforts to conceptualize, mathematically model, calibrate, and test key value systems. As these value systems are interrelated, we will explore the coupling or feedback between different values and their relation to water supply. Additionally, we will explore the legal and political constraints used to protect and promote particular values. Ultimately, our goal is to develop a freshwater-demand model accessible to water managers, policy makers, regulators, and stakeholders to help them understand the consequences of their decisions.

This work is a collaboration with the University of Arizona and the National Science Foundation (NSF) Science and Technology Center for Sustainability of Semi-Arid Hydrology and Riparian Areas (SAHRA). By leveraging our efforts with SAHRA, we will gain access to field data acquired from a variety of semi-arid river basins, including the Rio Grande. More importantly, this relation will provide new understanding and predictive models for implementation in our system-dynamics water-demand model.

Sandia, in collaboration with the Middle Rio Grande (MRG) Water Assembly, the Middle Region Council of Governments (MRCOG), and the Upton Transboundary Resources Center at the University of New Mexico, began developing a 50-year sustainable water-use plan for Bernalillo, Sandoval, and Valencia counties in north-central New Mexico. The purpose of the plan was to sustainably balance current and future water demand with projected supplies in a way that is

Sandia seeks a system-dynamics approach to modeling freshwater demand.

...Ultimately, our goal is to develop a freshwater-demand model accessible to water managers, policy makers, regulators, and stakeholders to help them understand the consequences of their decisions....we will gain access to field data acquired from a variety of semi-arid river basins, including the Rio Grande.

publicly acceptable and politically feasible. To assist in this process, we developed a model of the MRG planning region for quantitatively evaluating trade-offs, in terms of water savings and costs, between alternative water-conservation strategies, engaging the public in the decision process, and explaining the complexity in the regional water system.

The MRG planning model was developed in a system-dynamics framework using the commercial software package PowerSim. The model operates on a yearly time-step and includes a 38-year calibration period (1960–1998) and a planning horizon that extends to the year 2050. Basic model elements include surface-water and groundwater supplies balanced against municipal, agricultural, evaporative, and riparian demand. Specifically, the surface-water system comprises the Rio Grande and three area reservoirs. Inflows include the main stem of the Rio Grande, tributary flows, interbasin transfers from the Colorado River (each of which is subject to drought), and sewage returns. Losses from the surface-water system include evaporation from the river and reservoirs, agricultural consumption, transpiration from the riparian corridor along the Rio Grande, and pumping-induced river leakage. Groundwater inflows include mountain-front recharge, interbasin flows, and river leakage, while withdrawals include groundwater pumping and discharge to the river/shallow aquifer system. Municipal demand is driven by population growth and per capita demand disaggregated by residential, commercial, industrial, and institutional uses.

Also built into the model are 24 different water-conservation strategies suggested by the public. These include such measures as utilizing low-flow appliances, xeriscaping, gray-water reuse, block water pricing, restoring the riparian corridor, improved irrigation efficiency, and alternative reservoir management. In this way, the model allows the user to explore the consequences, in terms of water savings and cost, associated with alternative water-conservation strategies relative to the “no-action” alternative.

The model operates on a personal computer and takes a matter of seconds to complete a simulation. Results are expressed in terms of the Rio Grande Compact balance (key legal institution for the basin), groundwater depletions, water savings, and costs (construction, operation, and maintenance). A user-friendly interface guides the user through the model and assists him in selecting alternatives and interpreting results. Within this interactive environment, the user moves slider bars and selects radio buttons to enact various conservation measures and to regulate the level of implementation.

Also built into the model are 24 different water-conservation strategies suggested by the public....the model allows the user to explore the consequences, in terms of water savings and cost, associated with alternative water-conservation strategies relative to the “no-action” alternative.

This modeling-mediated water-planning process was unique in several respects. Simply the scope and diversity of issues that the planning process addressed were unusual. The water plan, and therefore the model, had to address endangered species issues, legal compact delivery requirements, as well as interests from residential, industrial, and agricultural water users. This project was also unique because of the level of collaboration with the general public. In developing this model, anyone was welcome to enter the process at any point and to contribute ideas for adapting the model. Finally, and perhaps most unique, this project documented public attitudes about models in general and this model in particular. In fact, survey respondents overwhelmingly supported (> 80%) the model and its use in setting regional water policy and in engaging the public in water planning.

Refereed

Cockerill, K., V. C. Tidwell, and H. D. Passell. 2003. Assessing public perceptions of computer-based models. *Environmental Management*, submitted.

Tidwell, V. C., H. D. Passell, S. H. Conrad, and R. P. Thomas. 2003. System-dynamics modeling for community-based water planning. *J. Aquatic Sciences*, submitted.

Passell, H. D., V. C. Tidwell, S. H. Conrad, R. P. Thomas, and J. Roach. 2003. System-Dynamics Modeling for Community-Based Water Planning: An Application to the Middle Rio Grande. Sandia Technical Report SAND2003-3653, Sandia National Laboratories, Albuquerque, New Mexico.

38717

Nanoscale Energetic Materials by Inverse Micellar Synthesis

A. S. Tappan, J. P. Wilcoxon, W. M. Trott, R. Behrens, Jr., S. P. Maharrey, S. M. Woessner

Sandia is investigating inverse micellar synthesis (IMS) as a technique for preparing nanoscale energetic materials (EMs). Particle sizes of materials such as metals, oxidizers, and composite mixtures can be precisely controlled by this technique, and this synthesis can result in particles as small as a few nanometers. The lower limits of useful particle size of aluminum (Al) for EM formulations are being realized as the surface-area-to-volume ratio is increased, thus increasing the ubiquitous surface coating of nonenergetic aluminum oxide. Inverse micellar synthesis allows for pure Al particles to be synthesized and should allow them to be passivated against oxidation by a coating of a compound that would contribute to the energy release. By careful selection of the passivation layer, composite EM energy densities twice that of high-melting explosive are possible. Of particular importance are the precise control and enhancement of chemical energy release in overcoming dissipative processes at the small length scales characteristic of microelectromechanical systems (MEMS) devices for future components. IMS is one application of nanotechnology that will result in higher energy-release rates and higher energy densities in EM compositions.

Characterization of these materials is critical to understanding the enhancement to EM performance and mechanisms of this enhancement. We will use standard analysis techniques, such as standard safety tests, electron microscopy, calorimetry, light scattering, and chromatography, to characterize the chemical and physical properties of these materials. We will use Fourier-transform ion cyclotron resonance mass spectrometry (FTICR-MS) as an analysis technique for these nanoparticles. We will examine characterization of performance of EMs formulated with nano-EMs by shock studies, utilizing a line-imaging optically recording velocity interferometry system (ORVIS) to observe reactive wave growth and evaluate the contribution of the nanoscale material to this reactive wave growth.

The approach of this project was to apply IMS to chemical reactions with literature precedent to create materials with desirable energetic properties. We chose Al as the first material to investigate due to its high heat of combustion and the large

Sandia is investigating inverse micellar synthesis (IMS) as a technique for preparing nanoscale energetic materials (EMs). Particle sizes of materials such as metals, oxidizers, and composite mixtures can be precisely controlled by this technique, and this synthesis can result in particles as small as a few nanometers....IMS is one application of nanotechnology that will result in higher energy-release rates and higher energy densities in EM compositions.

existing body of information on its properties. We developed a synthetic technique for multiple syntheses to be carried out concurrently. We synthesized a series of Al nanoclusters with this technique, in which we controlled cluster size by the amount of surfactant used. One route results in Al clusters that are remarkably monodisperse and have diameters of 1.8 nm, as measured by transmission-electron microscopy. We also synthesized larger clusters.

We found the 1.8 nm-diameter Al to be very air sensitive, as expected, but could be passivated to a limited extent by deposition of platinum (Pt), copper (Cu), and tungsten (W) by reducing the corresponding Pt(II), Cu(II), and W(IV) salt precursors solubilized in inverse micelles. This reduction also produced some Pt, Cu, and W clusters, and this homogeneous growth must be eliminated in future work. We used size-exclusion chromatography to investigate the size distribution of both bare Al clusters and the Al clusters passivated by Pt, Cu, and W. We observed both pure Pt, Cu, and W clusters and coated clusters. The most effective deposition occurred with Pt peak widths, characteristic of the size dispersion of the clusters, that were relatively narrow in the case of the Pt and Cu clusters, but broadened for the W-coated nanoclusters. Passivation will continue to be the main focus of this portion of the project.

Application of FTICR-MS to this project focused principally on evaluation of the various sample-preparation methods and ionization techniques available with our instrument. Our first clusters investigated were the model systems, cesium iodide (CsI) and molybdenum disulfide (MoS_2), formed by direct ionization of either solid CsI salt or MoS_2 nanoclusters off of a Cu matrix-assisted laser desorption-ionization (MALDI) plate and using both the ultraviolet (UV) laser and gallium (Ga) ion gun. We obtained successful measurements of clusters out to roughly 1000 daltons in the time-of-flight (TOF) apparatus for both species and also measured the CsI clusters with the FTICR instrument. We undertook system redesign to address limitations in mass range and resolution available in the TOF apparatus and ion-transfer efficiencies into the FTICR analysis cell; preliminary results show improvement.

A principal task involved the characterization and improvement of spatial resolution in the line-imaging ORVIS. We expect optimized spatial resolution to be important in maximizing the value of this diagnostic as a probe of chemical reactivity occurring over very small length scales. As presently configured, target magnification is controlled and varied by three achromat lenses that serve to collect light from the target

We developed a synthetic technique for multiple syntheses to be carried out concurrently. We synthesized a series of Al nanoclusters with this technique, in which we controlled cluster size by the amount of surfactant used. One route results in Al clusters that are remarkably monodisperse and have diameters of 1.8 nm, as measured by transmission-electron microscopy. We also synthesized larger clusters.

and then down-collimate this light ahead of the interferometer cavity. We demonstrated performance near the diffraction limit for this system.

The present method for reducing the interferometer data introduces spatial averaging, which constrains the effective spatial resolution. We are nearing completion of an alternative experimental design that promises to eliminate this constraint. With this method, the line image is separated using polarizing beamsplitters. This optical configuration generates four image planes that are quadrature-coded by the polarization. We designed and fabricated a specially designed image-preserving fiber bundle to transmit these image planes at very high resolution to a single recording streak camera. Initial tests of this bundle in combination with high-magnification optics in the line-imaging ORVIS indicate that significant improvements in spatial resolution should be achievable. We determined, and completed compatibility studies on, an energetic formulation that should allow meaningful application of this technique to the study of the contribution of nanoscale EMs to reactive wave growth.

Other Communications

Tappan, A. S., J. P. Wilcoxon, and S. M. Woessner. 2003. Nanoscale energetic materials by inverse micellar synthesis. Paper presented at Expanding the Envelope: Nanomaterials for Aerospace Symposium I (27–30 January, Corpus Christi, Texas).

We designed and fabricated a specially designed image-preserving fiber bundle to transmit these image planes at very high resolution to a single recording streak camera. Initial tests of this bundle in combination with high-magnification optics in the line-imaging ORVIS indicate that significant improvements in spatial resolution should be achievable. We determined, and completed compatibility studies on, an energetic formulation that should allow meaningful application of this technique to the study of the contribution of nanoscale EMs to reactive wave growth.

38718

Modeling of Rock Penetration

L. S. Costin, D. J. Frew, R. D. Hardy, W. A. Olsson, D. J. Holcomb, A. F. Fossum

A basic approach to defeating a hard and deeply buried target (HDBT) requires the weapon to penetrate the target rock sufficiently to ensure that adequate energy coupling is achieved. However, the mechanics of penetrating rock are poorly understood. The influence of such basic factors as porosity, hardness, stratification, and fracture density on penetrability is virtually unknown. The objective of this project is to develop a basic understanding of the mechanics of rock penetration that will lead to enhanced modeling capabilities to support the design of new penetrator systems. Sandia developed a new constitutive model for rock that incorporates some, but not all, of the important behaviors. To begin validating the model, laboratory work focused on obtaining key data on rate sensitivity and other effects. Using these as inputs, the model demonstrated good agreement with penetration experiments conducted on limestone. In addition to the detailed numerical modeling approach, we explored new analytical approaches to understand the penetration process. We also leveraged work from other projects to collect unique datasets on near-field rock conditions before and after full-scale penetration experiments. These datasets can be used for examining scaling issues and validating modeling methods.

Work continued on the development of a constitutive model to specifically address the unusual conditions encountered during rock penetration. Projectile penetration analyses made with the rock model revealed that the stress state in the rock surrounding a striking projectile ranges from triaxial extension in a large portion of rock ahead of the projectile to triaxial compression in the rock adjacent to the projectile, while the rock in the vicinity of the nose of the projectile experiences a state of pure shear. Because the deformation mechanism is different for triaxial extension from that for triaxial compression, we conducted laboratory tests in the Sandia Rock Mechanics Laboratory to determine the strength of Salem limestone in triaxial extension as compared with the strength of the same rock in triaxial compression. We found a 30% reduction in strength for Salem limestone from triaxial compression to triaxial extension for the same mean stress. In addition, the mode of failure changed from shear failure to extensile failure. Based on these results, we enhanced the model

The objective of this project is to develop a basic understanding of the mechanics of rock penetration that will lead to enhanced modeling capabilities to support the design of new penetrator systems. Sandia developed a new constitutive model for rock that incorporates some, but not all, of the important behaviors.

by modifying the third deviatoric stress invariant functional form such that the model can now handle such strength reductions in extension up to 50%. New analyses demonstrate that the model is capable of reproducing the stress-strain behavior observed in the laboratory.

To ensure that we accounted for strain-rate effects on rock response during penetration, we conducted a series of unconfined and confined split Hopkinson pressure-bar experiments on an Indiana limestone to study its strain-rate dependence over different stress paths. The confined dynamic experiments are a unique dataset made possible by the recent development of a confinement cell integrated into the Hopkinson bar apparatus. This new experimental technique allows us to more closely replicate states of stress appropriate to the penetration problem during a dynamic test. To date, we have found that this Indiana limestone is highly strain-rate sensitive over all of the confining pressure regions tested. We incorporated results from these experiments into the rock model and will use them to benchmark the penetration tests on the same limestone collected under other programs.

As an alternative to the basic physics model approach to understanding rock penetration, we developed an energy-balance approach and applied it to the few existing acceleration-time (g -time) datasets. The outstanding feature of these datasets for concrete and soils is the near constancy of the deceleration. Energy loss per unit displacement equals the deceleration, so a constant deceleration implies that energy is being deposited in the rock at a constant rate as a function of penetrator forward motion. To the extent this is true, the implication is that the primary energy-absorption mechanism responsible for stopping the penetrator is independent of rate.

In an attempt to find a more tractable experimental arrangement for investigating the response of rock to the large, rapid strains incurred during penetration, we reviewed earlier Sandia work on fracturing of rock using linear explosive charges to generate high-pressure gas in a borehole (gas-frac). The problem has similarities to the penetrator-rock interaction problem, but is much more tractable experimentally. We can control loading rates by suitable choice of explosives or propellants, and we can simulate the successive stages of penetration by varying hole size and maximum pressure reached during the explosion or deflagration. The original problem bears some resemblance to the question of penetrability. It is interesting that the relationship involved uniaxial strength, yield stress, and a modulus, all quantities that are empirically related to penetrability. It is our intent to pursue

...we enhanced the model by modifying the third deviatoric stress invariant functional form such that the model can now handle such strength reductions in extension up to 50%. New analyses demonstrate that the model is capable of reproducing the stress-strain behavior observed in the laboratory.

additional experimentation to validate these concepts, which could lead to a more physically based penetrability index than the currently used *S*-number.

Other Communications

Fossum, A. F. 2003. Rate-sensitive, transversely isotropic material model for large-scale computational geomechanics. *Proc. 7th U.S. National Congress on Computational Mechanics* (July, Albuquerque, New Mexico).

Warren, T. L., A. F. Fossum, and D. J. Frew. 2003. Penetration into low-strength (23 MPa) concrete: Target characterization and simulations. *International J. Impact Engineering*.

39212

MEMS–Based Electromechanical Acoustic-Energy Harvester

K. B. Pfeifer

Harvesting acoustic energy from ambient sources is a novel approach to powering remote-sensor systems either in remote locations or in otherwise inaccessible locations in critical structures. Sandia investigated a microelectromechanical systems (MEMS)–based design for an electroacoustomechanical energy-harvesting component that couples Helmholtz resonance cavities with piezoelectric films to greatly improve the efficiency of converting acoustic energy to electrical energy.

We completed a theoretical analysis of the coupled electroacoustomechanical system, including estimation of available output power. Design and fabrication of a thin-membrane device using MEMS–based technology is approximately 85% complete, lacking only the final deep reactive-ion etch (DRIE) step required to free the membranes. Other progress includes development of an advanced-packaging scheme for the membrane, an experimental plan for obtaining impedance and power measurements, and characterization and debugging of the DRIE process on silicon (Si) test wafers to prepare for the etching of actual devices.

We processed the topside of the wafers, but the formation of the membrane through DRIE from the backside is yet to be completed. To complete these steps, we needed to use a new Surface Technology Systems (STS) DRIE that was recently installed at the University of Florida (UoF). After installation, we conducted test runs on blank Si test wafers to determine etch rates, sidewall profiles, selectivity to photoresist, and mask undercut. Initial results for shallow etches looked promising, with clean sidewall profiles, decent selectivity to photoresist (on the order of 50:1 or greater), and an etch rate in Si of 1.12 $\mu\text{m}/\text{min}$.

Problems arose when we attempted deeper etches. The etch rates remained consistent in the deeper etches; however, significant sidewall erosion was occurring and was easily visible via scanning-electron microscope (SEM) images. We attempted several different etch-recipe variations, as well as different techniques for bonding the test wafers to a support wafer. The support wafer was necessary because the DRIE process was being used to go through an entire wafer, and when the Si was almost completely etched through, a thin layer of Si

Sandia investigated a microelectromechanical systems (MEMS)–based design for an electroacoustomechanical energy-harvesting component that couples Helmholtz resonance cavities with piezoelectric films to greatly improve the efficiency of converting acoustic energy to electrical energy.

We completed a theoretical analysis of the coupled electroacoustomechanical system, including estimation of available output power.

remained. This thin layer was soon etched away as the process continued. However, the backside of the wafer was continually cooled by a flow of helium (He) in the DRIE machine; this flow caused a pressure differential across the thin Si layer, resulting in a fracture of the Si at the bottom of the etched hole. The fracture created loose fragments of Si that contaminated the process chamber.

When we run the DRIE process on the actual devices, we will still have this issue to consider, as the etch will stop on the buried-oxide layer, leaving the thin Si membrane that would still be damaged by the He flow. We therefore have to bond the etched wafer to a handle wafer to prevent the He from flowing directly across the membrane structures. The necessity of a handle wafer, however, created some complications as good thermal contact was required to keep the top wafer cool during the DRIE. In an attempt to maintain good thermal contact, we applied a material called COOL-GREASE® to the bottom wafer.

As the results to date show significant sidewall erosion, a question remains as to the efficacy of this method for maintaining thermal contact. We are investigating the exact cause of the sidewall erosion to eliminate this problem before etching the actual devices.

We constructed well-characterized acoustic-waveguide test systems at the UoF that will be used to characterize the devices. We installed the MEMS on the end of the waveguide that is driven by a speaker on the other end. In between, we placed two calibrated reference microphones that serve as feedback to the operator and allow precise characterization of the energy incident on the MEMS devices. We can obtain the acoustic input power via measurement of the acoustic pressure at the reference microphone, and we can measure the acoustical input impedance via the two-microphone method of measuring impedance. We mounted the two reference microphones in a rotating plug that allows for easy switching of positions to average out any microphone phase differences. Additionally, we can measure the output voltage/power and output impedance at the terminals.

We can use this setup to measure many of the device parameters. The resonant frequency of the membrane and the Helmholtz resonator can be found from the frequency-response function, as can the maximum output voltage and power. As the input power is also known, we can calculate the efficiency. Additionally, we can place a load across the electrical terminals of the energy harvester and monitor the effects. We can vary the

resistance of the load to experimentally determine the optimal loads for maximum power and maximum efficiency.

41427

Predicting and Validating MEMS Interface Reliability

M. P. De Boer, M. B. Sinclair, R. A. Plass

Microelectromechanical systems (MEMS) show great promise for delivering systems solutions for Sandia applications. However, failure at contacting and sliding surfaces is of critical concern. The physics and chemistry of the interfaces created, and their evolution due to aging, are not well understood. Predicting and validating MEMS interface reliability require applying knowledge of molecular-scale behavior of hydrophobic and hydrophilic surfaces to model characteristics of real MEMS devices. A crucial factor is the nanometer-scale roughness of the real interfaces. In this project, we shall employ a joint experimental and modeling approach that links length scales from Ångström to millimeter to elucidate the mechanisms that cause change in performance of test structures sensitive to adhesion under accelerated aging conditions. Capillary forces are one major mechanism for large adhesion increase in MEMS. A simple Laplace-Kelvin approach is limited at the nanometer scale. Density-functional theory (DFT) was developed to accurately describe solvation forces in polydisperse nanopore networks and will be applied to model the rough interfaces we will investigate. We shall also construct a test system that enables measurement of interfacial properties under controlled conditions such as temperature and humidity. This will enable us to explore the interactive effects of these factors with the coating and surface roughness. By measuring and modeling the evolving interface as a function of aging conditions, we will develop validated lifetime models. This project will result in the development of reliable interfacial models at the molecular scale for MEMS performance and service life.

The thrust of this project is to measure and model adhesion of hydrophilic and hydrophobic surfaces versus vapor partial pressure and surface roughness. Our work concentrated on obtaining reproducible and understandable baseline data for hydrophilic surfaces. In previous work, adhesion on a hydrophilic surface increased with relative humidity (RH) beginning at 30% RH. In our current work, we saw no increases until ~ 90% RH, even though models predict we should begin to see effects at lower values. Without good baseline data, it is difficult to assess the effect of monolayer coatings that we apply to our surfaces. We addressed several important issues that may

Microelectromechanical systems (MEMS) show great promise for delivering systems solutions for Sandia applications. However, failure at contacting and sliding surfaces is of critical concern. ...By measuring and modeling the evolving interface as a function of aging conditions, we will develop validated lifetime models. This project will result in the development of reliable interfacial models at the molecular scale for MEMS performance and service life.

be affecting the reproducibility. By building a very clean chamber with *in situ* plasma cleaning, we eliminated most sources of adventitious hydrocarbon contamination. The plasma clean makes the surfaces uniformly hydrophilic, but introduces another concern. We examined whether surface charging due to the plasma clean plays a role in our results and demonstrated that it does not. We obtained wafers from the same lot as our earlier results and found that we still could not reproduce earlier adhesion results. However, using atomic-force microscopy (AFM), we observed high counts of $\sim 10\text{--}30$ nm-high particles (approximately 20 per mm^2). We are addressing the particle issue with fabrication engineers. We also observed that another solvent vapor (methanol) behaves similarly to water in the adhesion-versus- p/p_{sat} trend, which is consistent with our concern that particles obscure the desired results. We assessed the effect of monolayers on our adhesion results and observed no effect at 100% RH for up to 3 days. These monolayers did not show degradation in AFM measurements.

We remain critically concerned that our experiments, and SUMMIT-VTM (Sandia Ultraplanar Multilevel MEMS Technology V) stiction in general, are sensitive to the presence/absence of particles and not to the effect of coatings. Therefore, we continued to track down and eliminate the source of the particles. We found several clues. First, heating to 400°C during the plasma clean does not remove the particles. (This simulates the matrix-resist dry asher that we used in 1998—we speculated that the particles were fluorocarbons as have recently been found on other parts in the fab, but this is apparently not the case.) Second, a descum after HF:HCl release/peroxide dip was used in 1998, but is not part of the process flow today. The process flow today employs only a peroxide dip at room temperature after release, which does not make the substrates hydrophilic. If a “descum” step after peroxide dip is performed, samples come out cleaner after air drying (~ 20 per mm^2 and ~ 0.1 μm diameter for peroxide only to ~ 2 per μm^2 for descum) and also after critical-point drying (CPD) (from $\sim 2\text{--}4$ per μm^2 and ~ 0.1 μm diameter to ~ 0.5 per μm^2 and $\sim 0.05\text{--}0.1$ μm diameter). We found that this result depends on the process and not on which CPD tool is used. This suggests that the particles are soluble in the descum solution, which is 1:1:12 ammonium hydroxide:peroxide:water at 90°C. We tested adhesion of cantilevers that received the descum treatment. Results were not uniform as they were in 1998, but a few did show increasing adhesion at $\sim 70\%$ RH. Apparently there are too many particles to obtain the effect we seek. Scanning-electron microscopy (SEM) resolves the remaining particles well. We are now

We assessed the effect of monolayers on our adhesion results and observed no effect at 100% RH for up to 3 days. These monolayers did not show degradation in AFM measurements.

applying Auger microanalysis to determine the chemical content of the remaining particles. If they are silica-based, a vapor HF step available to us will remove them entirely. We are also trying other experiments to get at the problem.

41726

Direct Simulation of Solid-Fluid Systems

B. K. Cook

Numerous important industrial and natural processes are dominated by the interaction of particles (or a cemented particulate matrix) with neighboring particles and a surrounding fluid. For example, in the petroleum industry, sanding is a billion-dollar problem that results from the erosion of sand from an oil-bearing sandstone formation during production. Our understanding of the discontinuous physics underlying these processes and our associated predictive capabilities have been limited by continuum modeling approaches and difficult-to-perform experimental studies. An alternate approach is to simulate these systems at the grain scale. However, until recently, the direct simulation of these three-dimensional (3-D), dynamic solid-fluid systems has proven computationally intractable.

Rapid increases in parallel-based computational resources combined with the development of efficient and robust modeling schemes are marshalling in an exciting era of simulation-based discovery into the behavior and prediction of the dynamics of particle-fluid systems. Leveraging these developments, Sandia is developing an unprecedented computational capability for the dynamic simulation of the coupled solid and fluid phases, fully resolving the interaction of individual solid particles (and particle assemblages) with other solid particles and the surrounding fluid. This project focuses on the refinement and parallel implementation of a numerical scheme that uses the lattice-Boltzmann (LB) method and the discrete-element method (DEM) to solve the underlying governing equations for the fluid and solid phases, respectively. We are developing a powerful simulation environment to enable the computational exploration of solid-fluid physics.

We are performing this work in collaboration with researchers from the Massachusetts Institute of Technology (MIT). In addition to the aforementioned fossil-energy applications, the DEM is useful for understanding and modeling the mechanics that govern the behavior of materials undergoing large deformations, which is important for many Defense Programs problems such as penetration, shock-structure interaction, and blast damage.

Building upon earlier work, we formalized and validated a new element representation and a new contact-detection algorithm for DEM analysis. This representation, which is

This figure shows two pseudo-ellipsoidal elements represented using the equivalent sphere method and the contact detected by the algorithm.

...Sandia is developing an unprecedented computational capability for the dynamic simulation of the coupled solid and fluid phases, fully resolving the interaction of individual solid particles (and particle assemblages) with other solid particles and the surrounding fluid....We are developing a powerful simulation environment to enable the computational exploration of solid-fluid physics.

called the method of equivalent spheres, approximates ellipsoids as partial spheres that are oriented to maintain C^1 continuity along the plane of contact between the spheres. The representation maintains the simplicity of clustered spheres without the drawback of discontinuous normals. We formalized the algorithm for determining the contact point and the unique normal, and demonstrated its empirical convergence properties. We implemented the equivalent-sphere ellipsoid alongside planes and spheres to allow a deeper richness in the computational modeling of particulate systems.

We made progress on the development of an advanced simulator architecture supporting modular, Web-based deployment and cross-application interoperability. We designed a schema for representing general 3-D particles and adapted the schema to the Extensible Markup Language (XML). We developed methods to convert the DEM model to VRML97 (Virtual Reality Modeling Language), which is forward-compatible with the emerging X3D standard, for ease of communication over the Internet. We implemented the foundation of the code in the object-oriented NET framework, which has the benefits of being easily adapted to Web service implementation for use by other DEM researchers and for extensive integration of XML.

We made progress on the development of an advanced simulator architecture supporting modular, Web-based deployment and cross-application interoperability.

Refereed

Johnson, S. M., J. R. Williams, and B. K. Cook. 2003. Contact-detection algorithm for an ellipsoid approximation for discrete-element modeling. *Engineering Computations*, accepted.

Johnson, S. M., J. R. Williams, and B. K. Cook. 2003. Contact-detection algorithm for an ellipsoid using equivalent contact spheres. *Proc. 7th International Conference on Computational Plasticity* (7–10 April, Barcelona, Spain): CD-ROM.

Other Communications

Johnson, S. M., J. R. Williams, and B. K. Cook. 2003. Application of an ellipsoidal approximation to discrete-element modeling. Paper presented at the 7th U.S. National Congress on Computational Mechanics, 27–31 July, Albuquerque, New Mexico.

42461

Support–Active Site Interactions in Heterogeneous Catalysts

R. A. Kemp, A. G. Hascall

To rationally synthesize heterogeneous catalysts, it is imperative to comprehend the function of the various components of the catalyst. It is of utmost importance to know how a support interacts with the active site of the catalyst. In fact, in the catalysis world this lack of fundamental understanding of the relationship between active site and support is the single largest reason catalysis is considered an “empirical” or “black-box” science rather than a well-understood one. In this study, Sandia will look at an industrially important catalyst system with an eye toward explaining the relationship between the support and the active site. Along with the interest in understanding the catalyst in a fundamental sense, we also have the very real possibility of significantly affecting the technology and economics of ethylene oligomer production. We will prepare novel homogeneous ethylene oligomerization catalysts and deposit them inside the pores of nano- and mesoporous materials. Essentially, we will eventually tailor the size and scale of the catalyst active site and its surrounding environment to match the size of the molecular product(s) we wish to make. The overall purpose of the study will be to understand the effects that steric constraints and pore structures can have on growing oligomer chains. We wish to limit oligomer growth at defined lengths by using the steric constraints imposed by the pore walls of the nano- or mesoporous supports. We anticipate that significant knowledge from this study will provide future opportunities for multidisciplinary teams at Sandia to examine other catalyst systems in depth. In the future, understanding the relationship between support and active site should and will certainly lead to faster development and implementation of advanced catalysts. Ultimately, this study should even aid in making catalysts as selective as biological enzymes.

Our goal is to prepare new, well-characterized homogeneous catalysts for the oligomerization of ethylene, and then to bind these organometallic species on various porous supports. We accomplished the following:

(1) We prepared new nickel (Ni)-based complexes containing Shell higher olefins process (SHOP)-type ligands (P-O chelates) and crystallographically characterized one of these complexes. This structure gives insight into the three-

In this study, Sandia will look at an industrially important catalyst system with an eye toward explaining the relationship between the support and the active site. ...We anticipate that significant knowledge from this study will provide future opportunities for multidisciplinary teams at Sandia to examine other catalyst systems in depth. In the future, understanding the relationship between support and active site should and will certainly lead to faster development and implementation of advanced catalysts. Ultimately, this study should even aid in making catalysts as selective as biological enzymes.

dimensional (3-D) structures of industrially relevant olefin oligomerization catalysts.

(2) We prepared and structurally characterized new Ni-based catalysts that contain novel carbene ligands in place of the traditionally used phosphines. The other arm of the chelate is either a pyridyl-group or a ketone. We determined the major influences of ligand structure on the chelating ability of the ligand.

(3) We prepared a series of Ni-acac catalysts to serve as homogeneous catalysts.

(4) We prepared the carbene complexes mentioned above with a triethoxysilyl tether to allow grafting to a silica-based support.

(5) We are developing a synthetic methodology to produce anchored hexafluoroacetylacetonate Ni complexes.

(6) We are preparing complexes of other metals (including chromium).

(7) We prepared mesoporous silicas to act as catalyst supports. We prepared SBA-15, a hexagonally structured mesoporous silica, and a mesocellular foam (MCF) to act as supports. Additionally, we began putting these organometallic species inside zeolite pores of faujasite. Unfortunately, to date none of the attempts to use the SHOP-type ligands as templating agents were successful in producing a “ship-in-a-bottle” type of system.

(8) We constructed a low-medium-pressure (< 150 psig) apparatus to test ethylene oligomerization and developed an analytical methodology to measure catalyst performance. A high-pressure system is under development.

(9) An attempted collaboration with Shell to use their equipment in testing these catalysts unfortunately fell apart due to intellectual property (IP) issues.

42483

An Analysis of the Automotive Industry as a Source for Weapon Components and Manufacturing Processes

R. J. Steichen

Many of the commercial and captive suppliers who provided weapons components and manufacturing processes during the Cold War no longer have the capacity or desire to remain suppliers for future systems. In addition, potential needs to deploy technologies for homeland security will require working relationships with U.S. industry. For example, radiation-hardened semiconductor suppliers declined from 20 to 2 from 1985 to 1990. Finding or creating alternative suppliers will depend on Sandia's acquiring in-depth technical and business understanding of both suppliers' industrial capabilities and their cost-management opportunities. Most suppliers exit because the margins are too low (low volume, few orders) to sustain continued production.

For weapons components, it is important to recognize that each supplier is actually embedded in a value chain that stretches from the supplier's suppliers to the customer's customers. Approaching the "supplier" problem as a value chain provides the opportunity to work with potential suppliers in defining improvement opportunities in (1) linkages with suppliers, (2) linkages with customers, (3) process linkages within the value chain of the nuclear weapons (NW) complex, and (4) linkages across lines of business within Sandia, the Department of Energy (DOE), and the federal government. In short, addressing today's defense needs requires more fully engaging the capability of U.S. industry.

Implementing new technologies in weapons systems requires addressing three stages in the technology supply chain: (1) discovery/development engineering, (2) testing/verification engineering, and (3) supply-chain development. The automotive supply chain comprises 6% of the U.S. gross national product (GNP). The technology needs in the automotive industry sector are remarkably similar to those in weapons systems. Automotive components have lifetime, reliability, temperature, thermal-cycle, mechanical-shock, and design/manufacturing requirements that are similar to those for weapons components. They also rely heavily on advances in technologies such as metal forging, encapsulated electronics, microelectromechanical systems (MEMS) devices, sensors,

Many of the commercial and captive suppliers who provided weapons components and manufacturing processes during the Cold War no longer have the capacity or desire to remain suppliers for future systems....Finding or creating alternative suppliers will depend on Sandia's acquiring in-depth technical and business understanding of both suppliers' industrial capabilities and their cost-management opportunities. ...addressing today's defense needs requires more fully engaging the capability of U.S. industry.

power sources, materials, and computational-based modeling/simulation.

Compatibility has been established for mission needs that involve the following technologies: computer design/simulation/optimization, MEMS, sensors, manufacturing processes, batteries, hydrogen science, and others.

After an extensive discovery process, Sandia is pursuing projects with capable industry partners, which include the following:

(1) Goodyear funded a new initiative to develop a tire-pressure sensor based on MEMS technology. This application, used inside a tire, provides an opportunity to verify MEMS durability (on a large-volume scale) in a real-world environment.

(2) We initiated a project with Goodyear involving the membrane separation of hydrocarbons with DOE/Office of Industrial Technologies (OIT) funding.

(3) Toyota approved a proposal for collaborative research on a new class of hydrogen-storage materials. Discussions are also proceeding to consider other technology collaborations.

(4) Ford Motor Co., Advanced Manufacturing Technology Center, engaged Sandia in their technology planning process. Their intent is to fund collaborative projects tied to manufacturing. Previously, Ford's involvement with the national laboratories has been exclusively through DOE-funded consortia.

(5) Ferrari (through Lockheed Martin) is considering an initiative on crash dynamics for F-1 racing.

(6) We are also working with NACFAM (National Coalition for Advanced Manufacturing) to expand access to U.S. automotive manufacturers and suppliers.

The key to forming productive, collaborative relationships has been the detailed assessment of specific technology needs of automotive and weapons applications.

Compatibility has been established for mission needs that involve the following technologies: computer design/simulation/optimization, MEMS, sensors, manufacturing processes, batteries, hydrogen science, and others.

44136

Fluid-Structural Interactions in Wetting and Penetration into Porous Media

P. R. Schunk

Penetration of a fluid into a porous material or removal of a fluid from a porous material is often accompanied by deformation of the porous medium due to fluid structural interactions between the wetting fluid and the porous solid network. The mechanics of wetting in media that deform due to fluid and capillary forces is not well understood. In this project, Sandia will develop a fundamental theory and mathematical model of wetting on deformable solids with application to fluid impregnation into porous media such as paper.

We developed a theory for the drying of a polymer solution coating on a paper substrate that predicts transport of water into the pores in the paper and removal of water from the coating/paper system. Paper exhibits a dual-scale fibrous porous structure, with small pores in the paper fibers and large pores between the fibers. At low-moisture contents, water absorbs into the micropores in the fibers, but the macropores contain only vapor. Moisture can transport by diffusion or capillary flow through the fibers and by vapor diffusion in the macropores. The degree of swelling and change in porosity of the paper can be predicted by a microstructural model of fiber deformation. A suitable microstructural model will enable predicting changes in porosity and pore-size distribution due to capillary forces acting within the porous medium. There are several common approaches to modeling moisture transport in porous media that differ in the choice of field variable(s) and in their accuracy at certain ranges of saturation or capillary pressure.

The theoretical formulations anticipated from this work will be useful to several programs at Sandia, including modeling and simulation of flow in porous materials, as well as projects associated with the energy and environment business units.

To predict changes in the microstructure of paper during drying and moisturization, we developed a single-fiber deformation model. Wet paper fibers resemble thick-walled tubes, and during processing (drying and calendaring), the thick-walled tubes collapse to a ribbonlike shape. This collapse is caused by capillary pressure of water in the lumen of the tube exerting tensile stresses on the tube wall. The single-fiber model balances elastic stresses in the fiber wall to a transmural pressure caused by the capillary pressure of condensed water in

...Sandia will develop a fundamental theory and mathematical model of wetting on deformable solids with application to fluid impregnation into porous media such as paper....The theoretical formulations anticipated from this work will be useful to several programs at Sandia, including modeling and simulation of flow in porous materials, as well as projects associated with the energy and environment business units.

the lumen. The single-fiber model treats the fiber wall as an isotropic hyperelastic material. Deformation of the tube is predicted using ABACUS, a commercial finite-element (FE) package. With ABACUS, it is possible to predict deformation of a tube from a nearly elliptical cross section to a ribbonlike geometry in which the lumen is essentially completely collapsed. The geometry of collapsed tubes from the model matches qualitatively with observations of drying paper fibers. Experiments were also conducted at Drexel to observe the shape of tubes collapsing under negative, i.e., lower on inside, transmural pressures. The experiments and model both predict that the cross section remains elliptical up to a critical value of the transmural pressure (normalized by the elastic modulus). At this critical pressure, the lumen collapses rapidly until opposite walls of the tube touch, and then the cross-sectional area of the tube plateaus.

We used the predicted fiber shapes from the single-fiber model to predict macroscopic properties of paper using an idealized microstructural model. We developed an idealized unit cell structure to reproduce the key features of paper. The idealized unit cell contains layers of paper fibers, with fibers in each layer parallel to each other and fibers in adjacent layers perpendicular to each other. We imported the fiber cross sections from the single-fiber model into the unit cell structure. We used the unit cell structure to create an FE mesh in FEMLAB to model transport within the interfiber pore space. To predict effective diffusion coefficients, a water-vapor concentration difference is imposed across the unit cell, and the flux of water vapor is predicted by solving the diffusion equation within the interfiber pore space. The model predicts that the effective diffusion coefficient decreases by about a factor of 2 between the wet and dry states. The porosity of the paper also decreases by about the same amount.

We will use the results from this microstructural model of transport properties in paper to predict the drying and moisturization of paper coatings. The procedure used here to predict transport properties is not particularly complicated, although it is computationally intensive because the diffusion model is three-dimensional with an irregular domain structure. In the future, it will be useful to predict other transport properties (permeability, fiber diffusion coefficient, conductivity, etc.) by the same technique. Another likely extension to this model is to model the transient diffusion into the fiber wall and swelling of the fiber wall during moisturization.

We will use the results from this microstructural model of transport properties in paper to predict the drying and moisturization of paper coatings. The procedure used here to predict transport properties is not particularly complicated, although it is computationally intensive because the diffusion model is three-dimensional with an irregular domain structure. In the future, it will be useful to predict other transport properties (permeability, fiber diffusion coefficient, conductivity, etc.) by the same technique.

Refereed

Jain, A., R. A. Cairncross, K. N. Christodoulou, and E. Rozenbaum. 2003. Multilayer mathematical model for drying of a water-based emulsion coating applied on a silicone-coated paper substrate. *Drying Technology Journal*, accepted.

Madasu, S. 2002. Wetting on flexible substrates: A finite-element formulation. Ph.D. dissertation, Drexel University, August, Philadelphia, Pennsylvania.

Madasu, S., and R. A. Cairncross. 2003. Effect of substrate flexibility on dynamic wetting: A finite-element model. *Computer Methods in Applied Mechanics and Engineering* **192**:2671–701.

Madasu, S., and R. A. Cairncross. 2002. Static wetting on flexible substrates: A finite-element formulation. *International J. Numerical Methods in Fluids*, accepted.

45279

Macroscopic Rates, Microscopic Observations, and Molecular Models of the Dissolution of Carbonate Phases

R. T. Cygan

Our understanding of the kinetics of dissolution and growth of carbonate phases is critical to a variety of natural, industrial, and environmental processes. Fortunately, the relatively fast dissolution rates of carbonate phases provide a suitable time-scale for the laboratory investigation of these materials compared to the orders-of-magnitude slower rates for oxide and silicate phases. Sandia evaluates and combines various macroscopic and microscopic experimental techniques with molecular-modeling methods to derive a general mechanistic model for the dissolution of various metal carbonate phases. This work combines real-time morphology observations from the atomic-force microscope (AFM) with dissolution rates from macroscopic flow-through reactors. Etch-pit dissolution mechanisms can be directly linked to molecular models of carbonate surfaces with particular emphasis on the surface structure, surface energy, and formation of dissolution steps. Molecular simulations of the various metal carbonates provide a technically rigorous basis for the intercomparison of bulk and surface structures, surface energies, and relative stabilities of the reacting surfaces. Additionally, the simulations offer a model that explains the energetics of double-kink sites and how this mechanism relates to the dissolution process for carbonates.

This research combines the results of experimental dissolution experiments performed at Harvard University with state-of-the-art molecular-simulation methods developed at Sandia. The unique aspect of the present study is that carbonate dissolution rates are determined through geometry calculations of real-time surface modifications as observed by AFM of single crystals while simultaneously determining macroscopic dissolution rates based on the effluent solution. Experiments are performed at a wide range of pH conditions and for various endmember carbonate phases, including calcite (CaCO_3), magnesite (MgCO_3), rhodochrosite (MnCO_3), siderite (FeCO_3), and smithsonite (ZnCO_3).

Results of the microscopic and macroscopic dissolution measurements of the dominant (10–14) cleavage surface as a function of solution pH suggest the occurrence of multiple dissolution mechanisms dependent on phase chemistry and pH

This research combines the results of experimental dissolution experiments performed at Harvard University with state-of-the-art molecular-simulation methods developed at Sandia. The unique aspect of the present study is that carbonate dissolution rates are determined through geometry calculations of real-time surface modifications as observed by AFM of single crystals while simultaneously determining macroscopic dissolution rates based on the effluent solution.

region. Fast dissolution occurs at the low pH region, suggesting an acceleration of reaction mediated by the protonation of surface sites and the removal of carbonate material to form a surface covered by shallow pits. Intermediate to high pH regimes exhibit a relatively slow dissolution rate, which is interpreted as a crossover to a water-mediated mechanism. Calcite exhibits the most rapid dissolution rate, with the other phases following the general trend in rate based on water-ligand exchange rates, which are related to metal-ion charge to size ratios. Smithsonite behaves contrary to this generalization and dissolves almost as fast as calcite; however, the AFM surfaces exhibit a mixed dissolution morphology of corrosion features with deep pits. The formation of shallow and rhombohedral dissolution pits are quite common for the carbonate materials. Dissolution of rhodochrosite provides an excellent example of pit formation. Pit growth typically occurs at the surface expression of linear defects associated with the bulk material or with minor point defects that congregate at the carbonate surface. Low pH conditions induce a more asymmetrical development of dissolution pits and result in arrowhead-shaped structures. Crystallographic control of pit growth (carbonate dissolution) is expected and can be directly linked to molecular simulations.

The molecular-simulation component of this study addresses the issue of correlating the observed dissolution rates to the energetics of surface, ledge, and pit formation. We used our previous work on the development of accurate forcefields for carbonate phases as a basis for refining the potentials through parameterization with new data and with converting the more complex shell model, to represent electronic polarization of oxygen, to a simplified yet accurate rigid ion model. We accomplished this through the simulation and analysis of bulk carbonate structures for the five carbonate structures noted above plus three transition-element carbonate phases (CdCO_3 , CoCO_3 , and NiCO_3). We developed a carbonate forcefield and successfully applied it to bulk, surface, pit, edge, and kink calculations. We expect the forcefield to be used in future simulation studies, especially with those involving surface hydration and the sorption of organic molecules.

We calculated bulk and surface energies for endmembers of the isostructural rhombohedral carbonate mineral family, including calcium, cadmium, cobalt, iron, magnesium, manganese, nickel, and zinc compositions. The calculations for the bulk agree with the densities, bond distances, bond angles, and lattice enthalpies reported in the literature. The calculated energies also correlate with measured dissolution rates: the

We developed a carbonate forcefield and successfully applied it to bulk, surface, pit, edge, and kink calculations. We expect the forcefield to be used in future simulation studies, especially with those involving surface hydration and the sorption of organic molecules.

lattice energies show a log-linear relationship to the macroscopic dissolution rates at circumneutral pH. Excess pit formation decreases with increasing pit size, which is consistent with the nonlinear dissolution kinetics hypothesized for the initial stages of pit formation. As a probe into the terrace-ledge-kink theory of dissolution, we calculated the energies of ion pairs translated along surface steps and found them to predict experimentally observed microscopic step retreat velocities.

Refereed

Duckworth, O. W., and S. T. Martin. 2003. Connections between surface complexation and geometric models of mineral dissolution investigated for rhodochrosite. *Geochimica et Cosmochimica Acta* **67**:1787–1801.

Duckworth, O. W., R. T. Cygan, and S. T. Martin. 2003. Linear free-energy relationships between dissolution rates and molecular modeling energies of rhombohedral carbonates. *Langmuir*, submitted.

46070

High-Speed Micro-EDM

G. L. Benavides, S. P. Moylan

When two electrodes are in close proximity in a dielectric liquid, application of a voltage pulse can produce a spark discharge between them. Some of the energy in the discharge is transferred to the electrodes and results in the heating of highly localized regions of the electrodes. If the regions are heated above their melting temperature, molten droplets or vaporized material may be ejected from the electrodes. Pulsed application of the voltage results in repeated breakdown of the dielectric and material removal, and consequently to a continuous machining process called electrical discharge machining (EDM). Since material removal is controlled by the melting/vaporization temperature of the electrode materials, EDM proved to be enormously beneficial for machining complex shapes in hard materials that are difficult to fabricate by conventional means. A variant of the EDM process is micro-EDM, so called because it utilizes low discharge energies ($\sim 10^{-9}$ – 10^{-5} J) to remove small volumes of material. Spark erosion by micro-EDM provides significant opportunities for producing small features and microcomponents such as nozzle holes, slots, shafts, and gears in hard alloys and advanced ceramics; very rapidly solidified micropowders; and colloidal suspensions. If the speed and precision of micro-EDM processes can be significantly enhanced, they have the potential to be used for a wide variety of micromachining applications including fabrication of microelectromechanical systems (MEMS) components. It is these topics that constitute the core of this research.

Micro-EDM complements and is compatible with other microsystem technologies developed for the Microsystems and Engineering Sciences Applications (MESA) Program. This project seeks to develop the technology to increase the throughput of the micro-EDM process (i.e., high speed) and to uncover the science behind the process. Micro-EDM, as well as other microsystem technologies, promises to keep our nuclear weapon stockpile safe, secure, and reliable.

We obtained the critical components to the micro-EDM experimental setup. We purchased a z-axis linear stage and corresponding motion controller. To complete the two-stage motion device, we obtained a piezoelectric actuator along with a voltage amplifier to drive the actuator. We are developing a hybrid servosystem, comprising a piezoelectric actuator and

Micro-EDM complements and is compatible with other microsystem technologies developed for the Microsystems and Engineering Sciences Applications (MESA) Program. This project seeks to develop the technology to increase the throughput of the micro-EDM process (i.e., high speed) and to uncover the science behind the process. Micro-EDM, as well as other microsystem technologies, promises to keep our nuclear weapon stockpile safe, secure, and reliable.

direct current (DC) motor, for tool electrode feed. The objective here is to develop a fast-response servosystem for micro-EDM that will significantly enhance the duty cycle during machining. Finally, and most importantly, the custom-built power supply was delivered. We calibrated all of these components individually.

We quantified errors in the motion devices with a laser interferometer and capacitance probes. The total travel of the z-stage was 250 mm. We checked the long-scale motion of the z-stage with the laser interferometer. For movements of 10 mm or longer at the maximum velocity of 2 mm/s, the positioning error was approximately 0.025%, or less than 75 μm over the entire stage. Movements of 1 mm were checked at 0.1 mm/s and 0.01 mm/s and resulted in positioning errors of less than 1 μm . We checked shorter movements of the z-stage at speeds more characteristic of micro-EDM with a capacitance probe. The largest positioning error was a 2% overshoot on a move of 10 μm at 1 $\mu\text{m/s}$ (the slowest speed investigated), and all errors on moves of 50 μm or shorter were less than 1 μm . The capacitance probe was also used to calibrate the piezoelectric actuator. The total travel of the actuator was 50 μm , and the position was relatively linear over the applied voltage range of 0–100 V (position = 0.54 x voltage).

We used a high-speed oscilloscope to quantify error and establish operational limits on the power supply. We observed that actual pulsewidths overshoot the commanded pulsewidth by approximately 10%. However, this was rather consistent over the range of pulses tested (100 ns–10 μs) and therefore can be accounted for in future experiments. Because the goals of the project are geared more toward the lower energies, only the lower limits of the power supply were found. The supply cannot consistently produce square waves shorter than 100 ns, and even at that speed, the applied voltage was limited to 75 V or less. Also at these high speeds and low voltages, we anticipate that higher peak current settings will be necessary (greater than 0.5 A). The typical energy range realizable with the power supply is 0.5 μJ to 20 mJ. This will facilitate a systematic exploration of feature sizes that can be realized by micro-EDM.

We used an existing machine, the Agiecut Excellence at Sandia, to help benchmark the new machine being built. In a rather important step in this benchmarking process, we established the minimum feature size attainable on the Agie machine by cutting test parts at various machine settings. No feature smaller than 20 μm was cut successfully, and often the 20 μm features were significantly oversized.

46685

Nanoscale Hotspots Due to Nonequilibrium Thermal Transport

S. Graham, Jr., E. S. Piekos

Sandia directed recent experimental and modeling efforts toward the issue of temperature localization and hotspot formation in the vicinity of nanoscale heat-generating devices. The nonequilibrium transport conditions that develop around these nanoscale devices result in elevated temperatures near the heat source that cannot be predicted by continuum diffusion theory (CDT). Efforts to determine the severity of this temperature-localization phenomenon in silicon (Si) devices near and above room temperature are of technological importance to the development of microelectronics and other nanotechnologies. In this work, we developed a new modeling tool to explore the magnitude of the additional thermal resistance that forms around nanoscale hotspots from temperatures of 100–1000 K. The models are based on a two-fluid approximation in which thermal energy is transferred between “stationary” optical phonons and fast-propagating acoustic-phonon modes. The results of the model showed excellent agreement with experimental results of localized hotspots in Si at lower temperatures. The model predicts that the effect of added thermal resistance due to the nonequilibrium phonon distribution is greatest at lower temperatures, but is maintained out to temperatures of 1000 K. The resistance predicted by the numerical code can be integrated easily with continuum models to predict the temperature distribution around nanoscale heat sources with improved accuracy.

Additional research efforts also focused on measurement of the thermal resistance of Si thin films at higher temperatures, with a focus on polycrystalline Si (poly-Si). In this work, we intended to provide much-needed experimental data on the thermal-transport properties for micro- and nanoscale devices built with this material. Initial experiments showed that the exposure of poly-Si to high temperatures may induce recrystallization and radically increase the thermal-transport properties at room temperature. In addition, we observed that the defect density plays a major role in the rate of change in thermal resistivity as a function of temperature.

Recent research showed that the temperature rise near nanoscale semiconductor devices can yield dramatically larger temperatures than those predicted using CDT. We previously experimentally demonstrated this phenomenon in micron-scale

In this work, we developed a new modeling tool to explore the magnitude of the additional thermal resistance that forms around nanoscale hotspots from temperatures of 100–1000 K.

doped-Si resistors at low temperatures. To explain the size scale and temperature range over which this phenomenon is important, as well as the magnitude, additional modeling and experiments are necessary.

We developed a theory for heat conduction from an electronically generated optical-phonon hotspot. The approach is to avoid atomistic or particle-based numerical models and to focus on providing corrections to CDT, which is normally used in existing hydrodynamic electron-transport models. The analytical subcontinuum thermal model developed here predicts reduced phonon conduction from the nanoscale optical-phonon hotspot and compares well with experimental data. A key challenge of this analysis is the large departure from equilibrium of phonon states within a variety of energy ranges and branches. We addressed this challenge by defining separate temperatures for stationary and propagating phonons. This two-fluid approximation for phonons simplifies the phonon dispersion such that energy moments of the Boltzmann equation yield coupled but simplified equations for the two phonon fluids. Another key assumption is the use of a single overall scattering time, which enables the simplification of the collision integral to yield a closed-form thermal resistance between the temperature of phonons transporting heat and an average phonon temperature. This two-fluid resistance is a subcontinuum correction to the resistance calculated from diffusion theory that can be readily incorporated into hydrodynamic models. This results in a calculated resistance of the heat transfer from a stationary reservoir of optical phonons to the acoustic mode, resulting in an additional resistance above that predicted by CDT.

We compared the two-fluid model predictions with experimental data in single-crystal Si. The data showed excellent agreement between model and experimental results. We also explored additional comparisons of the thermal resistance of ballistic phonon transport near a spherical hotspot in bulk Si with the two-fluid resistance model. The two-fluid resistance provides the impedance due to strong excitation of a stationary phonon mode, and the ballistic resistance provides the impedance due to emission of propagating phonons from the hotspot. We found the two-fluid resistance to be larger than the resistance due to ballistic emission by a factor of more than 20 for a hotspot of radius 10 nm at room temperature. This is due partly to the severe assumption about the nature of phonon excitation inherent in the two-fluid model. The cumulative resistance is about 850 times larger than the resistance calculated from the diffusion theory. This factor decreases to

around 30 as temperature in bulk Si is increased from 300 K to 1000 K. Thus, the resulting two-fluid thermal resistance is dominant when the hotspot is small compared to the acoustic-phonon mean-free-path and over most applicable temperature ranges for nanoscale transistors. The resistance predicted here serves as a correction term for predicting the temperature rise in a transistor using CDT. The two-fluid model developed here is intended as a starting point for exploring the problem of phonon transport in nanotransistors where subcontinuum phenomena will be stronger due to reduced size-scale dimensions.

In additional work, the measurement of thermal conductivity in nanoscale poly-Si showed a large dependence on recrystallization, grain growth, and defect density when exposed to elevated temperatures. Thus, the prediction of intrinsic thermal resistance in these materials is strongly dependent on temperature history and deposition conditions. Extension of these results to higher temperatures is under way with SUMMiT-V™ (Sandia Ultraplanar Multilevel MEMS Technology V) poly-Si currently in production at Sandia.

Refereed

Sinha, S., and K. E. Goodson. 2003. Two-fluid resistance to heat conduction from subcontinuum optical phonon hotspots. *J. Applied Physics*, accepted.

46686

Microexternal Combustion Engine: The P3 Engine Prototype

C. A. Applett

This work is directed toward the development of a micro power-generation system based on an external-combustion dynamic heat engine. The design of this microelectro-mechanical system (MEMS)-based microheat engine, the P3 microengine, is based on a four-part strategy. First, thermal power is conducted into the P3 engine from an external heat source. The use of an external-combustion heat engine to produce power yields great flexibility in the choice of a fuel source for the power system. Second, thermal power is converted to mechanical power through the expansion and compression of a two-phase working fluid by the oscillation of a flexible membrane. The use of a flexible membrane to expand and compress a two-phase working fluid eliminates the requirement to manufacture complex micromachines such as rotary compressors and turbines. This approach also enables the use of a novel thermodynamic cycle that approaches the ideal vapor Carnot cycle. Third, mechanical power is converted into electrical power through the use of a thin-film piezoelectric generator that can be manufactured using MEMS fabrication techniques, but still delivers high conversion efficiency. Fourth, since batch micromanufacturing methods excel at producing many identical copies of two-dimensional (2-D) structures, the engine design is based on a modular, 2-D architecture. In particular, Sandia's work, in collaboration with Washington State University, focuses on two goals: (1) the fabrication of a prototype P3 microengine and (2) the experimental characterization of the microengine's operation.

The P3 microengine uses a two-phase working fluid, with phase changes between the fluid phase and the gas phase, and concurrent expansion to drive the piezoelectric generators. For optimal expansion during a compression stroke of the engine, the contents of the working fluid should all be the same compound. Any dissolved gases in the working fluid will be outgassed in the engine over time and will lead to a slow buildup of gas within the chamber, which robs the engine of performance. Getting a degassed fluid into the working chamber was nontrivial, as the working fluid tends to absorb gases from the surrounding environment, particularly oxygen. We overcame the major technical hurdle, which was to remove dissolved gases from the two-phase fluid, and thus improved

This work is directed toward the development of a micro power-generation system based on an external-combustion dynamic heat engine....Sandia's work...focuses on two goals: (1) the fabrication of a prototype P3 microengine and (2) the experimental characterization of the microengine's operation.

performance of the engine. We developed a technique to transfer working fluids that had been degassed previously into the working chamber without exposing them to the atmosphere, thereby ensuring that only a single material was present in the working chamber. We expect engine speeds and efficiency to improve through the use of thermal switches to remove the heat from the working fluid.

We expect engine speeds and efficiency to improve through the use of thermal switches to remove the heat from the working fluid.

Refereed

Whalen, S. A., L. W. Weiss, C. D. Richards, D. F. Bahr, and R. F. Richards. 2003. Characterization of the thermodynamic working cycle in a MEMS-based microheat engine. *Proc. IMECE '03* **41426** (15–21 November, Washington, D.C.): 1–7.

47517

Mathematical and Algorithmic Issues in Multiphysics Couplings

C. M. Stone

One may have different physical processes (e.g., flow, transport, reactions) occurring within the same physical domain, or one may have different physical regimes (e.g., surface/subsurface environments, fluid/structure interactions) interacting through interfaces. Sandia is investigating issues related to the determination of appropriate matching or transmission conditions (e.g., flux balance, conservation of mass, energy, momentum, etc.) across multiphysics interfaces. Specific energy and environmental Department of Energy (DOE) examples include the matching of different multiphase flow regimes, the coupling of geomechanics and geophysics codes with reservoir flow, and the coupling of surface water to groundwater.

When coupling multiple physics and/or multiple domains through interfaces, one must account for the coupling through discretization strategies. Mortar finite-element (FE) methods can be used for coupling different physical domains and also for multiscale resolution, as one can couple highly refined regions where one wants to capture fine-scale phenomena with more coarsely refined regions through the use of a mortar space. Also of interest will be the development of coupling approaches that do not require mortar spaces, e.g., the coupling of discontinuous Galerkin (DG) methods with continuous and mixed FE methods for treating different physical phenomena and/or different grids.

We plan to explore effective time-stepping schemes for solving general partial differential equations (PDEs) arising in multiphysics applications. The choice of time-steps is critical in deriving fast and accurate algorithms for large-scale coupled multiphysics problems. We will study theoretical as well as practical issues related to the time-stepping in the individual domains and in the coupled multiphysics applications. In particular, we will develop fully implicit and time-split approaches for systems of coupled PDEs. Depending on the nature of these equations and the feedback between them, the couplings can be “loose” or “tight” in time.

The modeling of fluid/structure interaction is of growing importance in both energy and environmental applications. Computational challenges in solving a coupled system of equations include (1) high computational cost, (2) selection of a

Sandia is investigating issues related to the determination of appropriate matching or transmission conditions (e.g., flux balance, conservation of mass, energy, momentum, etc.) across multiphysics interfaces.

Specific energy and environmental Department of Energy (DOE) examples include the matching of different multiphase flow regimes, the coupling of geomechanics and geophysics codes with reservoir flow, and the coupling of surface water to groundwater.

coupling method to optimize runtimes and accuracy for different types of physical applications, and (3) solvability and stability of a discretized linear system. The purpose of this research was to investigate techniques for coupling flow and geomechanics in porous media that are suitable for parallel computation. In particular, our main objective was to develop an iterative technique that can be as accurate as a fully coupled model but that allows for robust and efficient coupling of existing complex models (software). Stability issues will be our primary goal in the future.

In coupled geomechanics and reservoir modeling, the FE discretization of the force-balance equation leads to very large linear systems, whose solution is both time- and memory-consuming. The ICCG (Incomplete Cholesky Factorized Conjugate Gradient) is a popular technique for solving for displacements, but the technique is limited to about 60,000 nodal points on desktop machines. Most large three-dimensional (3-D) field-scale problems will have to be run on parallel machines. In this project, we used a reduced-communication, supercoarsening multigrid method that can be used in a combinative way with other domain-decomposition-based preconditioners to achieve faster convergence with high parallel scalability. A preliminary test case of 1.5 million grid blocks with up to 59 processors showed a parallel efficiency of above 90%.

The second computational issue we addressed is the efficiency and accuracy of different operator-splitting techniques. We compared three methods for coupling multiphase porous flow and geomechanics. We constructed sample simulations to highlight the similarities and differences in the techniques. One technique uses an explicit algorithm to couple porous flow and displacements, where flow calculations are performed every time-step and displacements are calculated only during selected time-steps. A second technique uses an iteratively coupled algorithm, where flow calculations and displacement calculations are performed sequentially for nonlinear iterations during time-steps. The third technique uses a fully coupled approach, where the program's linear solver must solve simultaneously for fluid-flow variables and displacement variables. We ran comparison problems for both single-phase and three-phase flow problems involving poroelastic deformations.

Among these coupling schemes, the iterative approach is more attractive due to the fact that it (1) is accurate and stable, (2) preserves the software's modularity, and (3) provides a straightforward way to couple an existing porous-flow

...we used a reduced-communication, supercoarsening multigrid method that can be used in a combinative way with other domain-decomposition-based preconditioners to achieve faster convergence with high parallel scalability. A preliminary test case of 1.5 million grid blocks with up to 59 processors showed a parallel efficiency of above 90%.

simulator with an existing geomechanics simulator. The primary drawback to this method is that the calculations may display a first-order convergence rate in the nonlinear iterations. However, we reformulated the classical iterative method in a more-general framework and showed that the method can be viewed as performing one preconditioned Richardson iteration on a fully coupled system. The rock-compressibility term used in a flow model is nothing but a preconditioner for the Schur-complement pressure equation. We gained two folds by this interpretation. First, an iterative-coupling implementation can be more easily adapted to a fully coupled scheme. In this setup, solving the two coupled field equations simultaneously is, from an implementation point of view, no more complicated than repeatedly using a classical operator-splitting method. This is worth noticing because people tend to implement and use the loosely coupled or iteratively coupled methods because these methods are numerically more explicit compared to a fully coupled scheme. Second, our interpretation provides the possibility to analyze convergence behavior of the iterative-coupling method. The pressure mass matrix scaled by the rock-compressibility term can also be generalized as a preconditioner to other iterative linear solvers in a fully coupled scheme.

Refereed

Dean, R. H., X. Gai, C. M. Stone, and S. E. Minkoff. 2003. A comparison of techniques for coupling porous flow and geomechanics. *Proc. SPIE Reservoir Symposium* **1** (79700) (3–5 February, Houston, Texas): 1–9.

Gai, X., R. H. Dean, M. F. Wheeler, and R. Liu. 2003. Coupled geomechanical and reservoir modeling on parallel computers. *Proc. SPIE Reservoir Simulation Symposium* **1** (79700) (3–5 February, Houston, Texas): 1–11.

47795

Lipid Membranes on Nanostructured Silicon*D. Y. Sasaki*

In this project, Sandia will develop unique hybrid nanostructures that interface nanolithographically defined silicon (Si) surfaces with molecularly dynamic, self-assembled materials. Our goals are to (1) develop a mechanistic understanding of how the self-assembled materials interface with the structured substrate, (2) examine how the nanostructure influences the mobility of the molecular assemblies, and (3) develop an understanding of how to manipulate the interfacial interactions and mobility of the molecular assemblies to tailor features in the material from the micro- to nanoscale. The hybrid structures will be composed of a nanolithographically defined Si substrate patterned with lines or posts with a pitch of ~ 360 nm and feature widths of tens to hundreds of nanometers. The self-assembled material will be a lipid-bilayer membrane composed of fluorescent-labeled and/or functionalized lipids. Coupling of the bilayer to the Si wafer could be achieved by either the vesicle-fusion or membrane-stamping techniques. We will perform characterization of the hybrid structure by atomic-force microscopy (AFM), fluorescence recovery after photobleaching (FRAP), and confocal microscopy. AFM and confocal microscopy will evaluate whether the lipid membrane is spanning the top pillars of the structure or conformally coating the surface. We can then use all three methods to monitor the dynamic motion of lipids in the membrane and determine the effect of the underlying nanostructured surface on asymmetric motion of the lipids. The results of this project will impact numerous areas, in particular nanoarchitecture, biosensors, and biocompatible surfaces for bioMEMS (microelectromechanical systems). This work will be the first to interface a precise, regular nanostructured semiconductor substrate with a molecularly dynamic self-assembled material. The research involved here will lay the groundwork for understanding how structured substrates influence the macroscopic structure of a coupled lipid membrane and the molecular dynamics (MD) within the membrane.

We are developing unique hybrid nanostructures that interface nanolithographically defined Si surfaces with molecularly dynamic, self-assembled materials. Our goals are to (1) develop a mechanistic understanding of how the self-assembled materials interface with the structured substrate,

...Sandia will develop unique hybrid nanostructures that interface nanolithographically defined silicon (Si) surfaces with molecularly dynamic, self-assembled materials....The results of this project will impact numerous areas, in particular nanoarchitecture, biosensors, and biocompatible surfaces for bioMEMS (microelectromechanical systems). This work will be the first to interface a precise, regular nanostructured semiconductor substrate with a molecularly dynamic self-assembled material. The research involved here will lay the groundwork for understanding how structured substrates influence the macroscopic structure of a coupled lipid membrane and the molecular dynamics (MD) within the membrane.

(2) examine how the nanostructure influences the mobility of the molecular assemblies, and (3) establish methods that allow the manipulation of interfacial interactions and mobility of the molecular assemblies to tailor features in the material from the micro- to nanoscale. We prepared nanostructured Si substrates, formed vesicles from doped lipid membranes, investigated solution conditions that promote vesicle fusion to the nanostructured Si surfaces, obtained images of the hybrid structures with AFM, conducted FRAP experiments on the supported lipid bilayers, and prepared nanostructured channels in Si wafers. Structured Si wafers, prepared in collaboration with the Center for High-Technology Materials at the University of New Mexico via nanolithography, exhibit line patterns with a pitch of ~ 360 nm, depths of 200 nm, and linewidths of about 100 nm. We cleaned the wafers with ultraviolet/ozone to remove any hydrocarbon contamination, then placed them in the solution for either AFM or fluorescence-microscope experiments. We prepared liposomes of dipalmitoylphosphatidylcholine by extrusion through two stacked filters with 200 nm to yield 200 nm-diameter unilamellar vesicles. We then added the liposomes to the solution cell and allowed them to fuse with the Si substrate at room temperature. Scanning of the surface with tapping-mode AFM provided images that revealed coverage of the surface with lipid membrane. From the FRAP experiments, we found that the lipids have confined mobility with higher diffusion rates running parallel to the line structures in the underlying substrate.

49769

Resin Infusion Between Double Flexible Tooling

J. A. Ruffner

The potential for cost savings was the motivating factor behind the development and construction of a novel composite manufacturing technique known as the Resin Infusion Between Double Flexible Tooling (RIDFT) at the Florida A&M University–Florida State University (FAMU–FSU) College of Engineering. It is a two-stage process—resin infusion and wetting followed by vacuum forming. Sandia places dry reinforcement between two membranes, secures the membranes, and then infuses the resin under a vacuum. In the vacuum-forming stage, which follows infusion, we draw the membranes over a male mold (the final product shape) by applying a vacuum. The use of a one-sided mold provides huge cost and time benefits when compared to the conventional processes for resin transfer molding (RTM). In the RIDFT process, the one-sided molds are not subjected to high pressures and can thus be made by rapid-prototyping methods with metallic or nonmetallic materials. The RIDFT process also has lower tooling costs when compared to RTM, since a one-sided mold is used with a reusable bagging system. The potential for savings is even more evident in the production of large component parts. Moreover, the use of fabrics rather than preimpregnated materials (prepregs) (as with SCRIMP®) further enhances affordability. A recent cost study indicated that RIDFT has a 24% cost advantage over SCRIMP®.

The RIDFT process also lends itself to the incorporation of reconfigurable tools that can conform to different geometric configurations, thus reducing tooling requirements and the development of cycle times. Since infusion of resin is done between translucent silicon diaphragms, we can incorporate ultraviolet (UV)-curing techniques in the RIDFT process. However, the RIDFT process is limited to line-of-sight geometric shapes.

The goal of this work is to further improve the RIDFT process by (1) incorporating a UV-curing capability for reducing production-cycle times and (2) investigating the viability of in-mold coating by use of gel coats or thin films. The use of thin films and gel coats will necessitate a study of the ability of the curing gel coat or thin film to conform to the required mold geometry during the forming step. The current study will build upon experience gained with the working

The potential for cost savings was the motivating factor behind the development and construction of a novel composite manufacturing technique known as the Resin Infusion Between Double Flexible Tooling (RIDFT)The potential for savings is even more evident in the production of large component parts. Moreover, the use of fabrics rather than preimpregnated materials (prepregs) (as with SCRIMP®) further enhances affordability. A recent cost study indicated that RIDFT has a 24% cost advantage over SCRIMP®.

prototype, further enhancing the applicability of the RIDFT process.

(1) *Incorporation of UV curing.* We purchased and installed the equipment necessary to incorporate the UV curing. We completed a literature review of this technology and an experimental plan. In future work, we will continue incorporation of the UV-curing technique into the RIDFT process.

(2) *In-mold coating.* We completed initial assessment studies of the viability of using thermoformable paint films to in-mold-coat the RIDFTed components. We presented our findings at the 2003 annual convention of the American Composites Manufacturers Association (ACMA). We found that although the use of paint films is viable, several challenges exist. In this study, we used Avery Dennison Avloy films. These films require a temperature of 270°F to soften for forming. As such, manufacturers using these films thermoform them before adding the fiber-resin mix. However, with the RIDFT process, the idea is to place the film within the two diaphragms prior to resin infusion. The problem is that the heat used in softening the films prematurely cures the resin. This results in poor forming of the component, e.g., flared corners. Nonetheless, we achieved a measure of success by reducing the heating exposure from 3 min to 2 min. The resulting component was fully formed, but the adhesion between the film and the substrate was poor. Proper adhesion requires increasing the heating time. We thus proposed to raise the curing temperature of the resin by changing the catalyst. This will be done in the next phase of the work. Additionally, further testing is ongoing using GE Lexan films.

Refereed

Toro, N., and O. I. Okoli. 2003. In-mold coating of composites manufactured with the resin infusion between double flexible tooling process. *Proc. Composites Fabricator Association* (October, Anaheim, California).

49772

Studies on the Disbonding Initiation of Interfacial Cracks

E. D. Reedy, Jr.

As feature sizes and footprints of microelectronics packages decrease, understanding the fundamentals of adhesion at small interfacial disbond length scales is becoming critical to understanding the overall reliability of the semiconductor assembly. Difficulties in rigorously applying interfacial fracture mechanics to small-scale disbond problems have encouraged a shift in focus from the study of the disbond propagation to the study of the initiation event using a stress-intensity approach to characterize failure at singularities other than disbonds. Interfacial edges and corners serve as singular stress locations similar to those at a disbond crack tip, and are believed to be the origins of initiation when the intensity of the stress field reaches a critical level. In this research, Sandia is characterizing the initiation event at different singularities for interfaces relevant to microelectronics assemblies. We will employ a tensile butt-joint geometry in fundamental studies to examine the underfill/passivation interfacial response under both monotonic and fatigue loading. In subsequent studies, we will employ flip-chip geometries that will allow for the characterization of initiation under more-realistic thermal- and mechanical-fatigue loadings.

We tested butt joints with several different types of underfill/passivation interfaces, including both model and commercial underfill epoxy systems. Interestingly, when we compared these results to propagation data generated from asymmetric double-cantilever-beam testing, there seemed to be a correlation between the initiation and propagation events. Though the fundamental interplay between mechanical and chemical contributions for a propagating interfacial disbond is well established, the fundamentals for the initiation phenomenon are still unknown. To better understand the observed correlation, we are testing tensile butt joints with controlled surface interactions. We will compare these results to crack propagation results generated elsewhere at Sandia for the asymmetric double-cantilever-beam geometry.

We also performed fatigue testing of the commercial underfill systems. Fatigue results show that subcritical initiation occurs and that the strength of the singularity has a large impact on the lifetime of the interface. The preliminary results at low-cycle fatigue levels suggest a linear trend with applied delta-K

In this research, Sandia is characterizing the initiation event at different singularities for interfaces relevant to microelectronics assemblies.

values and cycles-to-failure, similar to that seen for propagating disbonds. We also applied this fatigue testing to two flip-chip geometries, examining both corner and edge singularities. We employed an acoustic emission technique to detect the initiation event, while we used scanning acoustic microscopy to determine the origins of failure. As expected, preliminary results show that the edge singularity is much more resistant to initiation than the corner singularity. In fact, the edge singularity specimens have not exhibited disbond initiation even at the 500–1000-cycle range, while the corner singularity specimens are failing at less than 100 cycles. To further understand the effects of singularity strength, we are investigating modified tensile butt-joint geometries with free corners, embedded edges, and embedded corners.

In upcoming work, we will continue both fundamental and flip-chip studies, including testing of the other singularity types and beginning an examination of the correlation between thermal and mechanical fatigue on subcritical initiation.

Refereed

McAdams, B. J., and R. A. Pearson. 2003. Initiation and propagation at the underfill/passivation interface in flip-chip assemblies. *Proc. Semiconductor Research Corporation TECHCON 2003, P006075* **1** (25–27 August, Dallas, Texas): 1–4.

McAdams, B. J., and R. A. Pearson. 2003. Initiation of interfacial delaminations relevant to flip-chip assemblies. *Proc. 26th Annual Meeting of the Adhesion Society* **1** (23–26 February, Myrtle Beach, South Carolina): 194–96.

50396

Compliant Membranes for MEMS Microphones

D. R. Sandison

Sandia's objective in this project is to develop a microelectromechanical systems (MEMS)–based real-time acoustic array. Development of the MEMS microphone took place at the University of Florida (UoF). The MEMS microphone is a dual backplate capacitive microphone that utilizes electrostatic force feedback. The microphone consists of a diaphragm and two porous backplates, one on either side of the diaphragm. This forms a capacitor between the diaphragm and each backplate. The MEMS microphone was designed and simulated at the UoF and fabricated at Sandia using the SUMMIT-V™ (Sandia Ultraplanar Multilevel MEMS Technology V) process. This SUMMIT-V™ process is unique in that it provides five planar layers of polysilicon (poly-Si) that can be used to construct the three plates of the microphone.

Once we processed the microphones with SUMMIT-V™, the final post-processing steps, which include topside metallization and backside deep reactive ion etch (DRIE) and membrane release, began at the UoF. Once post-processing is completed, we will first characterize the microphone in an open-loop configuration. We will design the initial packaging to accommodate the acoustic testing facilities at the UoF, specifically two acoustic plane-wave tubes. After we design and fabricate the packaging, we will characterize the microphone in terms of its sensitivity, bandwidth, linearity, and noise floor. Once we extensively characterize the microphone in the open-loop configuration, work will shift to characterizing the device in a closed loop.

While the microphone was in production at Sandia, it was rigorously simulated using finite-element (FE) analysis. The simulations included determining the linear range of the device, the effects of a bias voltage, and how the capacitance of the device varied with pressure.

Also during this time, our UoF collaborator worked on the closed-loop interface circuitry. This circuitry will implement force feedback to keep the displacement of the diaphragm small. The benefits of this scheme include an extended frequency response as well as increased sensitivity. The feedback loop will be realized using a sigma-delta modulator. The major components of this design include a charge amplifier, a compensator, and a comparator. The UoF assisted

Sandia's objective in this project is to develop a microelectromechanical systems (MEMS)–based real-time acoustic array....The MEMS microphone was...fabricated at Sandia using the SUMMIT-V™ (Sandia Ultraplanar Multilevel MEMS Technology V) process. This SUMMIT-V™ process is unique in that it provides five planar layers of polysilicon (poly-Si) that can be used to construct the three plates of the microphone.

in the design of the charge amplifier, which is currently in the final stages of design.

We completed the microphone fabrication at Sandia and returned the die to the UoF. Once we received the microphones, we began the final post-processing steps. After we finalized the process flow for the remaining steps, we obtained the required masks and wafers.

50717

Multiscale Experimental/Numerical Study*P. M. Gullett*

Work on this project was conducted in collaboration with the University of Colorado. Sandia's work previously focused on two topics in the area of nano-/microscale deformation and damage of emerging materials for defense applications. The first topic of research is in situ fatigue damage of cast magnesium (Mg) where we examined high-cycle and low-cycle fatigue damage in cast AM60B Mg. The second topic of research is atomistic simulations of face-centered cubic (FCC) materials. Work in this area focused on the structure and elastic properties of small-scale metallic materials, such as nanowires.

- *In situ fatigue damage of cast Mg.* We examined high-cycle and low-cycle fatigue damage in cast AM60B Mg. We conducted the *in situ* fatigue tests in an environmental scanning-electron microscope (SEM) under both high vacuum and 20 Torr of water vapor. In both environments, we observed fatigue cracks to form and grow within the dendrite cells and through the interdendritic regions. Cracks formed during cycling in vacuum were more uniformly distributed and showed lack of complete closure upon unloading in contrast to cracks formed during cycling in water vapor. The cracks formed in water vapor were much more isolated and indicated significant environmental attack and associated embrittlement at the crack tip, as evidenced by the near-perfect mating of crack faces upon unloading. The water-vapor environment accelerated the formation of selected, isolated cracks, leading to more localized damage compared to the highly distributed damage growth and coalescence observed in the material cycled in vacuum. More recent results focused on *in situ* monitoring of the growth rate of microstructurally small cracks in cast Mg with lengths as small as 30 μm . The microstructurally small cracks interact strongly with the microstructure and tend to arrest at particle-laden interdendritic regions and at regions with high aluminum in solid solution. The above results have significant ramifications on developing a multiscale fatigue model of cast Mg.

- *Atomistic simulations of FCC materials.* Work in this area focused on the structure and elastic properties of small-scale metallic materials, such as nanowires. Specifically, we used atomistic simulations to study a surface stress-induced phase transformation in FCC nanowires. The emergence of the transformation is controlled by wire size, initial orientation,

Sandia's work...focused on two topics in the area of nano-/microscale deformation and damage of emerging materials for defense applications. The first topic of research is in situ fatigue damage of cast magnesium (Mg)...The second topic of research is atomistic simulations of face-centered cubic (FCC) materials.

boundary conditions, temperature, and initial cross-sectional shape. For a $\langle 100 \rangle$ initial crystal orientation and wire cross-sectional area below 4 nm^2 , surface stresses alone cause nanowires to transform from an FCC structure to a body-centered tetragonal structure. The transformation occurs roughly when the compressive stress caused by tensile surface stress components in the length direction exceeds the compressive stress required to transform the bulk material to its higher-energy metastable crystal structure. We also examined the elastic properties of the wires in detail. The elastic properties of the small-scale FCC materials depend strongly on the phase transformation and also on the ratio of the surface area to the volume of the wire.

52174

Inelastic Deformation Mechanism in Shocked-Sapphire Single Crystals

M. D. Knudson

Sandia is collaborating with Washington State University (WSU) to understand the deformation mechanisms in shocked-sapphire single crystals and to incorporate these mechanisms into a continuum model. In particular, the work will focus on understanding the inelastic behavior of sapphire shocked along different crystallographic axes; previous work at WSU has shown that the inelastic behavior varies with orientation. Presently, there are no material models for shocked sapphire that can be used to simulate the observed anisotropic, inelastic response. Experiments at WSU (gas-gun, shock-wave experiments) and at the Sandia Z accelerator (quasi-isentropic experiments) will provide wave profiles for comparison with numerical simulations. Detailed comparisons of the mechanical response under these distinctly different loading conditions (shock and quasi-isentrope) should provide insight into the mechanism governing inelastic deformation. A good material model is required to use sapphire as an interferometer window in quasi-isentropic experiments; this will directly benefit material dynamics studies at Sandia, directly benefiting pulsed-power sciences.

We performed a literature review of mechanical twins. We reviewed and evaluated twinning models governing the quasi-static loading of single-crystal sapphire, as proposed in the literature. We implemented and tested an isotropic one-dimensional (1-D) twinning model, similar to that proposed by Johnson and Rohde, using their alpha-iron work. These calculations provided evidence that the time-dependent profiles produced by such a model are not distinctive from profiles created using dislocation models, i.e., a dislocation model could be “forced” to display the same profiles produced by the twinning model. We therefore determined that we needed experiments to justify the implementation of a twinning model for sapphire.

We designed a set of shock-recovery experiments for single-crystal sapphire to verify the presence or absence of twinning. We performed recovery experiments on *r*-cut crystals. The recovered samples consisted of fragments ranging from just less than 1 cm in size to powder. All recovered samples showed a high density of microfracture exhibited by a milky appearance. The recovered sample fragments match or exceed the

Sandia is collaborating with Washington State University (WSU) to understand the deformation mechanisms in shocked-sapphire single crystals and to incorporate these mechanisms into a continuum model. In particular, the work will focus on understanding the inelastic behavior of sapphire shocked along different crystallographic axes....A good material model is required to use sapphire as an interferometer window in quasi-isentropic experiments; this will directly benefit material dynamics studies at Sandia, directly benefiting pulsed-power sciences.

dimensions reported in published reports of previous recovery work (Chen, UC Davis 1994; Wang & Mikkola, *Mat. Sci. & Eng.*, A148, pp. 25–32, 1991). We are using transmission-electron microscopy (TEM) to determine the extent of twinning in the recovered samples.

We calculated the stress states behind the initial longitudinal (or quasi-longitudinal) wave in shocked sapphire using an approach proposed by Jim Johnson. The calculated stress states were resolved onto the slip systems reported by Snow and Heuer. By comparing the calculated results with experimental observations, we observed that basal slip and basal twinning occur at relatively low stresses and display significantly higher Schmid factors for *r*-cut crystals. We concluded that basal slip and basal twinning are likely the dominant mechanisms of inelastic deformation for the *r*-cut orientation. Currently, there is no anisotropic twinning model for shock compression.

A shock-twinning model based on the quasi-static double-cross-slip mechanism proposed by Pirouz, *et al.* (*Acta Mater.*, vol 44, no. 5, pp. 2153–64, 1996) is being implemented in the Institute for Shock Physics' (ISP's) 1-D shock-wave propagation code. We will test the uniqueness of this model and will simulate existing shock-wave profiles obtained from previous experiments. We will also simulate ramp-loading profiles obtained from Z-accelerator isentropic compression experiments. We may also perform VISAR (laser interferometry system) experiments to obtain additional shock profiles. The emphasis of this study will be on modeling *r*-cut sapphire above its Hugoniot elastic limit (HEL). Depending on the success of the model developed for *r*-cut sapphire, we may examine the responses of *c*- and *a*-cut sapphire.

Refereed

Fuller, H., and Y. Gupta. 2003. Inelastic deformation mechanism in shocked sapphire. Paper presented at the APS Topical Conference on Shock Compression of Condensed Matter, July, Portland, Oregon.

52538

Sequestration of Pathogens on Nanoengineered Surfaces

M. S. Kent, D. L. Huber, J. G. Curro, J. A. Fruetel, M. D. Nyman

*Recent events have heightened awareness of the vulnerability of U.S. water resources to bioterrorism. There is a critical need for rapid sensing, as well as for improved mitigation technologies. In this project, Sandia is developing materials that sequester pathogens based on chemical interactions rather than size. We are targeting these materials for both sensing and improved water-treatment applications. Regarding sensing, we are developing a preconcentrator for a μ ChemLab biosensor that will capture and concentrate pathogens from water streams and then release them in a concentrated pulse. Regarding mitigation, our goal is to develop filtration materials that allow for lower pressures, higher flowrates, and improved efficiency relative to current ultrafiltration technology. The work focuses on two materials shown previously to interact strongly with bacteria or viruses: poly(*n*-isopropyl acrylamide) (PNIPAM) and polyoxometalates (POMs). PNIPAM is the best-known temperature-responsive polymer, possessing a lower critical-solution temperature (LCST) at 31°C. Our collaborators at the University of New Mexico (UNM) showed that bacteria reversibly adsorb/desorb onto PNIPAM-coated surfaces as the temperature is varied above/below the LCST. POMs are anionic, metal-oxo clusters with 6–30 metal octahedra of tungsten (W), molybdenum (Mo), niobium (Nb), vanadium (V), or tantalum (Ta) (d0), often assembled around one or two central tetrahedra. POM clusters have a charge ranging from ~ -4 to -20 and are known to interact strongly with viruses and some bacteria through electrostatic interactions. We divided our work roughly equally between materials development and fundamental studies. The final deliverables will include a report of the maximum concentration factor achieved and the species selectivity attained for the preconcentrator application, and a comparison of the performance with currently available ultrafiltration materials for the filtration application.*

We made progress in synthesizing PNIPAM and POMs films on flat surfaces and on high-surface-area media, characterizing such films, modeling the PNIPAM conformational change with temperature, and performing initial adsorption assays involving two species of bacteria.

Recent events have heightened awareness of the vulnerability of U.S. water resources to bioterrorism. There is a critical need for rapid sensing, as well as for improved mitigation technologies. In this project, Sandia is developing materials that sequester pathogens based on chemical interactions rather than size. We are targeting these materials for both sensing and improved water-treatment applications.

We devoted much effort to synthesizing PNIPAM and POMs films with varying characteristics on flat surfaces, as well as on high-surface-area porous media. We synthesized PNIPAM films using chain-transfer free-radical polymerization, atom-transfer radical polymerization (ATRP), plasma polymerization, and end-functionalized preformed polymers. These different synthetic methods led to films that vary in surface density, polydispersity, molecular weight (M), and extent of cross-linking. Flat substrates included silicon, glass slides, and gold-coated slides. High-surface-area media included 100 mm-diameter glass beads and silica gel.

We characterized the PNIPAM coatings and the response to temperature (T) change using neutron reflection (NR), surface-plasmon resonance (SPR), infrared (IR), and contact-angle measurements for films on glass slides. At high surface density, we determined the extent of conformational change and the change in hydrophobicity with T as a function of M using ATRP. The change in water contact angle was observed to occur over a very small T range, within about 1°, whereas the conformational change was observed by NR and SPR to occur over a much wider range. We used IR to characterize the adsorbed amount on glass beads and silica gel.

We applied self-consistent field theory to the problem of predicting the concentration profile of tethered PNIPAM macromolecules in aqueous solution. We performed calculations over a range of T both above and below the bulk LCST. We found good qualitative agreement between the theory and the neutron-scattering measurements.

We performed adsorption assays with glass slides, as well as with packed columns, to determine whether these physical characteristics affect either the adsorption or release characteristics. Results to date are still preliminary and inconclusive. Initial work with *Bacillus subtilis* on coated glass slides confirmed that it adsorbs preferentially to hydrophilic surfaces. However, the behavior was time-dependent (adsorption decreased over time) and difficult to reproduce quantitatively. We performed other work with *Cobetia marina*. Our UNM collaborators previously showed that *C. marina* adsorbs strongly on hydrophobic surfaces but weakly on hydrophilic surfaces, a fact reproduced at Sandia. Adsorption tests with *C. marina* in columns containing hydrophobic or hydrophilic glass beads showed that a very high fraction of bacteria was removed from solution in both cases. Further, with PNIPAM-coated glass beads all the bacteria was removed from solution at 40°C, but little bacteria was released upon flushing the column with artificial seawater at 15°C. This suggests that

the bacteria are being filtered and that the pore size is too small. In other work, our UNM colleagues obtained evidence that acid/base characteristics may control adsorption/desorption of *C. marina* rather than simply hydrophobicity.

Regarding POM-based materials, we devised two methods for preparing POM surfaces for the anionic POMs: (1) using amine-functionalized self-assembled monolayers (SAMs) to organize a monolayer of POMs, and (2) using ammonium surfactants to form a surfactant-POM material that can be cast into a film. We carried out bacteria-attachment studies on these two series using *C. marina*. For the POM-surfactant films, there was a distinct trend of increasing attachment with decreasing negative charge on the POM. This can be explained as the surface becoming more hydrophilic with increasing POM charge. We recently synthesized some new POM materials: (1) an aluminum POM-surfactant material that is positively charged, and (2) a lacunary POM that can bind any metal. The latter enables tests of the effect of different metals on bacteria attachment. We also synthesized some highly charged, base-stable Nb-based POMs and sent them to the Sandia-California member of the team for optical-property and protein-interaction investigations.

Refereed

Mendez, S., and J. G. Curro. 2003. Modeling polyethylene/benzene solutions with an integral equation theory. *J. Chemical Physics*, submitted.

Yim, H., M. S. Kent, S. Mendez, S. S. Balamurugan, G. P. Lopez, and S. Satija. 2003. Temperature-dependent conformational change of PNIPAM grafted chains at high surface density in water. *Macromolecules*, submitted.

Yim, H., M. S. Kent, S. Satija, S. Mendez, S. S. Balamurugan, and G. P. Lopez. 2003. Vertical phase separation of PNIPAM grafted chains in water. *Physical Review Letters*, submitted.

Other Communications

Mendez, S., B. Subramanian, S. S. Balamurugan, G. P. Lopez, J. D. McCoy, H. Yim, M. S. Kent, and J. G. Curro. 2003. Characterization and modeling of temperature-induced structural changes of poly(N-isopropyl acrylamide) brushes. Preprint, AIChE Meeting.

52539

A Combined Preconcentrator and Sensor for Live Waterborne Pathogens

Y. Fintschenko, B. A. Simmons, E. B. Cummings, B. H. Lapizco-Encinas

Sandia demonstrated the components of a bacteria concentrator that is based on a recent discovery (U.S. patent application filed) in which an electric field applied across a two-dimensional (2-D) array of microfabricated insulating posts separates, isolates, and concentrates 0.1–10 μm particles (including bacteria and inert particles) dielectrophoretically, based on their physique: polarizability, geometry, and structure. We demonstrated a design that is scalable to continuously concentrate and filter bacteria from water samples at > 1 liter per hour and that provides the collected samples to a microfluidic separation channel.

The concentrator design principle is that concentration occurs in stages by a sequence of physically specific interactions. (1) During collection, a moderate applied direct-current (DC) electric field dielectrophoretically traps particles in size-specific zones of the device containing a high-volume, nonuniform array of insulating posts, while other solutes and water flow unimpeded to a waste stream. (2) Trapped particles within a selected size range are released in a concentrate to a medium-volume array having a DC offset. Particles are retrapped in zones of this secondary device that are specific to the internal physique of the particles. (3) Selected particles are then released to a tertiary low-volume dielectrophoretic sieve bearing an electric-field-generated conductivity gradient to further filter and select particles that physically respond to osmolality and conductivity, a live-particle signature. (4) A sharply pulsed electric field lyses the selected cells, releasing their contents to a canonical microfluidic separation channel.

We demonstrated that the trapping behavior distinguishes between living cells, dead cells, and inert matter in the same size range. We will now focus on the design and testing of the multiple stages. The final goal remains the coupling between the dielectrophoretic concentrator and an actual microfluidic separation channel for practical water monitors based on a wide range of separation and sensor technologies.

We reproduced previous results using green fluorescent-labeled polystyrene beads to verify proper operation of the insulative (electrodeless) post-dielectrophoresis (iDEP) microfluidic. We demonstrated the selective “trap-and-release”

Image of iDEP simultaneous concentration and separation of live and dead E. coli, 10 times magnification, inverted fluorescence microscope. Live cells are green; dead cells are red. A field of 1.3 kV/cm was applied.

Sandia demonstrated the components of a bacteria concentrator that is based on a recent discovery (U.S. patent application filed) in which an electric field applied across a two-dimensional (2-D) array of microfabricated insulating posts separates, isolates, and concentrates 0.1–10 μm particles (including bacteria and inert particles) dielectrophoretically, based on their physique: polarizability, geometry, and structure.

concentration for two types of bacteria versus an inert background. We achieved the selective trap-and-release concentration and separation of live-versus-dead *E. coli* bacteria using our first-generation designs. We successfully differentiated and concentrated two different viable cell types, *E. coli* and *Bacillus subtilis*, using the trap-and-release iDEP. We also demonstrated iDEP trapping of viral particles. We developed, fabricated, and successfully tested an iDEP concentrator scalable for high-flow-rate applications. We tested a next-generation nonuniform array iDEP device using fluorescently labeled polystyrene beads. We successfully tested an efficient replication method that uses Bosch-etched silicon wafers containing next-generation features to replicate those features into polymeric thin-film substrates. We also generated two technical advances, two presentations, and two posters. We prepared and submitted one paper to the peer-reviewed journal *Analytical Chemistry* and are preparing a second manuscript for submission to the peer-reviewed journal *Electrophoresis*.

We successfully differentiated and concentrated two different viable cell types, E. coli and Bacillus subtilis, using the trap-and-release iDEP. We also demonstrated iDEP trapping of viral particles. We developed, fabricated, and successfully tested an iDEP concentrator scalable for high-flow-rate applications.

Refereed

Fintschenko, Y., B. A. Simmons, B. H. Lapizco-Encinas, and E. B. Cummings. 2003. Insulating post electroless dielectrophoresis for the selective concentration of bacteria. (Invited) *Proc. μ TAS 2003*. M. A. Northrup, K. F. Jensen, and D. J. Harrison, eds. (Boston, Massachusetts: Kluwer Academic Press): 65–8.

Lapizco-Encinas, B. H., B. A. Simmons, E. B. Cummings, and Y. Fintschenko. 2003. High-throughput electrodeless dielectrophoresis of viruses in polymeric microdevices. *Proc. μ TAS 2003*. M. A. Northrup, K. F. Jensen, and D. J. Harrison, eds. (Boston, Massachusetts: Kluwer Academic Press): 607–10.

Cummings, E. B., G. J. Fiechtner, A. K. Singh, B. A. Simmons, Y. Fintschenko, and B. H. Lapizco-Encinas. 2003. Continuous streaming dielectrophoretic particle filter/concentrators. *Proc. μ TAS 2004*, accepted.

Other Communications

Cummings, E. B., G. J. Fiechtner, Y. Fintschenko, B. H. Lapizco-Encinas, B. A. Simmons, and T. H. Cauley. 2003. Engineered dielectrophoretic-separation-column packings. Paper presented at GRC on the Physics and Chemistry of Microfluidics, August, Big Sky, Montana.

Lapizco-Encinas, B. H., B. A. Simmons, E. B. Cummings, and Y. Fintschenko. 2003. Dielectrophoretic concentration and separation of live and dead bacteria in an array of insulators. ACS, submitted.

52727

Predictive Accelerated Aging of Microsystems: The Science of Dormancy

M. T. Dugger, T. M. Mayer, M. P. De Boer, R. A. Plass, J. V. Cox, F. J. Peter, D. M. Tanner, B. Jokiel, Jr., T. J. Skousen, J. A. Ohlhausen

Qualification of microsystems for defense applications is critically dependent on our ability to build confidence in their performance, by accurately predicting the evolution of their behavior over time in the stockpile. Sandia will establish a science-based, system-level predictive capability for operation, aging, and reliability of packaged microsystems for Defense Programs applications. The effort will be weighted toward experimental exploration in early work, but will include more modeling as the project progresses. We will package surface-micromachined (SMM) surety devices (e.g., the discriminating microswitch and nonvolatile memory) with existing diagnostic structures in packages with optically transparent lids to facilitate quantitative measurements of performance. We will use various packaging technologies to produce a range of realistic gaseous environments in the packages. We will subject packages to accelerated aging and stress tests to explore dormancy and operational environment effects on reliability and performance. We will run functional tests and quantitative measurements (adhesion, friction) without opening the packages. We will perform quantitative measurements in situ where possible. Device tests and post-test analyses of surface composition, morphology, and gas composition will identify failure modes and underlying physical mechanisms relevant to defense microsystems. We will then use controlled experiments combined with simulations to determine the kinetics of specific phenomena and build age-aware constitutive models that capture their dependence on environmental parameters. We will integrate knowledge from this and existing studies into a science-based toolset that we will apply to packaged microsystems. We will validate failure mechanisms identified by simulation with test structures and through collaborations with microsystem-level qualification activities.

We designed and fabricated an SMM “aging module” that incorporates prototype weapon devices and diagnostic structures on the same die. This die permits prototype devices to be tested for functionality after accelerated aging, and then friction and adhesion measurements using the diagnostic structures. The module includes half a discriminating microswitch (DMS) and one bit of nonvolatile memory (NVM).

Qualification of microsystems for defense applications is critically dependent on our ability to build confidence in their performance, by accurately predicting the evolution of their behavior over time in the stockpile. Sandia will establish a science-based, system-level predictive capability for operation, aging, and reliability of packaged microsystems for Defense Programs applications.

A torsional ratcheting actuator (TRA) is included that has an output gear with monitor. Diagnostic structures include cantilever beams for adhesion and a sidewall tribometer for friction, respectively. Structures are also included to evaluate the chemistry of hidden surfaces and the structure of monolayer films after aging.

The focus of our work was on testing and characterizing the prototype surety devices. After fabrication, we released, dried, and supercritically carbon dioxide (SCCO)–dried the devices. In addition, we used a vapor self-assembled monolayer (VSAM) coating on half of the parts. These are all batch processes defined in the Microelectronics Development Laboratory (MDL).

We packaged dormancy modules in Kyocera ceramic 24-pin dual in-line packages. We dispensed the die attach adhesive using an Asymtec automated dispenser. We then placed the die in packages by a Palomar 3500 pick-and-place robot. We cured the epoxy (150°C for 30 min), followed by attachment of aluminum bond wires using a Delvotek automatic wire bonder. We clipped a sapphire lid to the top of the package and vacuum-baked them at 150°C for 2 hrs. We then sent the packages down a belt furnace to reflow the gold (Au)-tin (Sn) solder and permanently affix the lids. The first attempt yielded poor results in the functionality of most devices. The VSAM TRA had the best yield at 78%, and the SCCO–dried NVM had 55%. All other cases yielded less than 15%.

We performed failure analysis of the DMS to isolate the failures into discrete sections. The test methodology used focused-ion-beam (FIB) cutting to remove parts of the structure, working backward from the last gear and testing functionality after each FIB cut. The failures appear to be along the actuators. With no load, some actuators exhibited no motion. Further analysis is currently under way to determine the mechanism of failure in the actuators.

The modeling work includes device-level and interface-level models. While the interface-level models will help us better understand the surface physics, they are not as essential to the project's objectives as the device-level models. Thus our early modeling efforts focused on the device-level models. The two candidate prototype devices are a gear on a hub (relevant to DMS) and the NVM contact bar.

We generated the first gear-hub model from computer-aided design data. Detailed geometry is not necessary for studying the gear-hub interaction of a single gear, thus we developed a simplified model (maintaining the same rotational inertia as the gear). To determine the mesh density required to accurately

represent contact stresses, we are solving a cylinder-on-cylinder contact problem (with the same hub/hole geometries) with ADAGIO.

We are assembling time-dependent degradation information on VSAM films from parallel experimental efforts. Our initial approach is to develop a simple Arrhenius-like expression for the thermal activation of VSAM degradation. While we have demonstrated this degradation behavior for physical measurements of film thickness, we have not yet confirmed simple kinetic behavior for adhesion characteristics of the films.

Refereed

Romig, Jr., A. D., M. T. Dugger, and P. J. McWhorter. 2003. Materials issues in microelectromechanical devices: Science, engineering, manufacturability, and reliability. *Acta Materialia*, accepted.

Dugger, M. T., R. J. Hohlfelder, and D. E. Peebles. 2003. Changes in adhesion, static and dynamic friction of surface-micromachined MEMS due to lubricant degradation. Paper presented at the Society of Tribologists and Lubrication Engineers Annual Meeting, 28 April–4 May, New York, New York.

Other Communications

Dugger, M. T., and S. V. Prasad. 2003. Tribological measurement on MEMS platforms. Paper presented at the American Vacuum Society International Symposium, 4–8 November, Denver, Colorado.

52728

Surety and Accountability Enhancements for Storage Containers

J. W. O'Connor, T. E. Bennett, S. C. Lindblom, C. L. Woodcock, S. K. Namperumal, J. R. McElhanon, M. C. Jackson

As world politics change and treaties result in reductions of fielded weapon systems, a need for handling nuclear warheads exists whether the weapon exists in a fully assembled state in the stockpile or as a partially disassembled Alt configuration. Large quantities of surplus warheads are expected from stockpile reductions, yet an insufficient number of storage assets exist for a large-scale drawdown. (Existing shipping-container inventories are inadequate.) A research and development team successfully executed a half-scale prototype design for a low-cost warhead storage container. Although we did not address several engineering issues, we demonstrated the global structure of the approach to be innovative and sound. Sandia will conduct an engineering feasibility assessment with more rigor applied to weapon-inventory issues. The overarching goal would be to provide a new design alternative specifically for storage and lay the foundation for a lightweight/inexpensive container paradigm.

The challenge involves the production of a prototype container of significant quality, with communications capability, and at a manufacturing cost that would revolutionize warhead storage and surety needs as identified in the nuclear weapons (NW) "surety fearless forecast." Engineering efforts will focus on the incorporation and integration of tags/seals, and optical and wireless means of inventory informational-driven communications. Evaluation of the prototype will include both physical and computational testing. The engineering effort will represent collaborations between materials, surety design, ancillary equipment, and engineering sciences organizations.

- We researched and reviewed material technologies for container fabrication. We identified and investigated two approaches toward structural containers: (1) commercial rotomolded containers and (2) in-house-manufactured structurally sound composite containers. We demonstrated the ability to pre-impregnate new composite materials from ATK Thiokol.

- We upgraded the modeling software on the filament-winding machine to enhance the ability to do cost-effective manufacturing.

Sandia will conduct an engineering feasibility assessment with more rigor applied to weapon-inventory issues. The overarching goal would be to provide a new design alternative specifically for storage and lay the foundation for a lightweight/inexpensive container paradigm.

- We designed and demonstrated two viewing windows for inventory management.
- We researched inventory-management system architectures. We looked at a wide range of technologies, including wireless networking hardware/software and low-power imaging equipment.
- *Storage-container materials development.* We investigated two approaches toward the manufacture of storage containers. The first was a low-cost approach using commercially available rotomolded materials. We obtained a variety of containers and evaluated them as candidates for storage containers that would be compatible with the inventory-management features that we are developing. The second approach involved evaluating a variety of pre-preged composite materials available from ATK Thiokol and Cytec Engineered Materials. Thiokol specializes in composite materials for rocket boosters and other National Aeronautics and Space Administration (NASA) projects. Cytec manufactures composite materials utilized in aircraft wing construction. We prepared several test coupons using these materials and are on track to manufacture a quarter-scale container using down-selected composite materials that will incorporate a filament-wound Kevlar exterior. This prototype will incorporate an electronic bus for integration of electrical inventory-management devices. In addition, we upgraded the modeling software required for the filament-winding machine to enhance the ability to do cost-effective manufacturing.
- *Viewing window for inventory management.* One inventory-management feature that we wished to provide in a storage container was integration of a smart viewing window. We conducted a technical search evaluating commercially available smart-window technologies. Specifically, we were interested in windows that were opaque (off-state) under normal operating conditions and transparent (on-state) only when triggered. We identified two commercial technologies. The first involves a liquid crystalline polymer (LCP) that is supported and suspended between either a flexible plastic or glass window. The opaqueness of the window is a result of light scattering due to the randomly oriented LCP. Upon applied voltage, the LCP becomes ordered, effectively eliminating light scattering, allowing the viewer to see through the window. The second approach utilizes a similar technology called a *suspended particle device* (SPD). SPD refers to light-absorbing microscopic particles that are suspended between two electronically coated surfaces. The film is placed between two panes of electrically conductive coated glass or plastic. By

turning the electrical voltage up or down, one can manually or automatically increase or decrease the amount of light transmitted through the glass or plastic window. When the device is in the “off” state, no voltage is applied, and the particles are randomly dispersed and absorb light, creating a dark opaque appearance. When it is in the “on” state, the particles will align, and the view through the glass or plastic will change from dark to clear. One advantage of the SPD window over the LCP window is that the former is darker and more opaque than the latter.

We began evaluating commercial optical-fiber bundles as another alternative to inventory management, and progress has been steady.

52729

Nuclear-Safety Weaklinks for Thermal and Mechanical Environments

A. C. Hall, K. Rahimian, K. Eras, S. J. Glass, S. G. Thoma

Sandia's nuclear-safety triad relies upon stronglinks, barriers, and weaklinks. There are multiple stronglink and barrier options for firing sets, but only one thermal weaklink (the gel-Mylar capacitor). Production and nuclear-safety concerns make this weaklink technology high risk. There are no weaklink options for shock and crush environments. This project began with the goal of developing new weaklink technologies for thermal and mechanical (shock or crush) environments.

We pursued a thermal weaklink based on a new dielectric material that converts to a conductor when exposed to elevated temperatures. We demonstrated that the resistivity of this material changes by over 5 orders of magnitude in response to a thermal insult. This material could be used to reliably short a capacitor in response to a thermal insult. To take this initial work to a demonstrated weaklink will require optimizing the dielectric for a capacitor, understanding its chemistry, and ascertaining its reliability. We also pursued a shock/crush weaklink based on engineered stress profile (ESP) glass. This material fractures predictably at a specific stress level and can be metallized. We are investigating implementation schemes based on frangible circuit boards or flat cables. We are also investigating the radiation hardness of both materials.

The proposed thermal weaklink could provide several advantages over existing technology. It is less sensitive to the direction and size of the thermal insult. It can be integrated with mica-paper capacitor technology and is identifiable after weapon assembly. The high mechanical strength of mica-paper capacitors could allow the capacitor weaklink to serve as a nuclear-safety barrier. The proposed shock/crush weaklink would improve nuclear-safety themes by providing a weaklink where none exists. It may also lay the foundation for passive (no power required) sensors, useful for other applications.

We concentrated on developing two materials for thermal and mechanical weaklinks. We studied a polymeric system (polyvinyl alcohol ([PVA])/silver nitrate [AgNO_3]) for thermal weaklink applications. At 150°C , this material undergoes chemical changes that result in its resistivity decreasing by over 5 orders of magnitude. It becomes irreversibly conductive. We are developing this material as the dielectric of a firing-set

Fragmentation behavior: (row 1) baseline; (row 2) after thermal aging at 200°C ; (row 3) after 5 Mrads of gamma radiation.

The proposed thermal weaklink could provide several advantages over existing technology. It is less sensitive to the direction and size of the thermal insult. It can be integrated with mica-paper capacitor technology and is identifiable after weapon assembly....The proposed shock/crush weaklink would improve nuclear-safety themes by providing a weaklink where none exists.

capacitor. We are developing ESP glass for mechanical (shock/crush) weaklink applications. ESP glass is a specific ion-exchanged glass that fractures at highly predictable stress levels.

Much of the development focused on materials behavior of ESP glass and PVA/AgNO₃. These experiments included radiation exposure and long-term aging. We showed the reaction initiation temperature of PVA/AgNO₃ films to be 150°C, regardless of film composition. We identified chemical-reaction products as carbon dioxide (CO₂) and water. We incorporated PVA/AgNO₃ into bulk and thin-film epoxies as powder and fibers. Above 150°C, we observed large resistivity changes in the composite. We gave ESP glass and PVA/AgNO₃ a 5 Mrad gamma-ray exposure at Sandia's Gamma Irradiation Facility. Neither material showed any significant changes after exposure. Long-term thermal-aging studies are in progress.

We investigated effects of ionization condition on central tensions in ESP glass. We conducted thermal-shock tests. ESP glass samples failed several seconds after being shocked; normal glass samples failed immediately. We investigated metallization techniques, including cold spray (> 0.005 in. thick) and physical vapor deposition (~ 350 nm thin). Thin films did not affect fragmentation or hold fragments together. Thick coatings did affect fragmentation. We developed analytical models that describe ESP glass stress profiles and fragmentation behavior. We developed and explored a number of crush weaklink design concepts. These concepts include passive (no power) sensors that could be integrated into weaklinks.

We fabricated an electrical test-bed. This test-bed is designed to deliver simulated firing signals to prototype weaklink (shock or crush) components. We will use it to test the behavior of weaklink prototypes. This test-bed will allow us to verify the performance of our prototypes under electrical conditions similar to those in the firing set of a weapon.

We developed analytical models that describe ESP glass stress profiles and fragmentation behavior. We developed and explored a number of crush weaklink design concepts. These concepts include passive (no power) sensors that could be integrated into weaklinks.

Refereed

Glass, S. J. 2003. Fracture and fragmentation of brittle materials: The good, the bad, and the ugly. (Invited) Paper presented at a seminar, Colorado School of Mines, 6 March, Golden, Colorado.

Glass, S. J., and R. Tandon. 2003. Controlling the mechanical behavior of stressed glass. Paper presented at the 8th ECERS Conference and Exhibition of the European Ceramic Society, 29 June–3 July, Istanbul, Turkey.

Glass, S. J., and R. Tandon. 2003. Controlling the mechanical behavior of stressed glass. Paper presented at the 105th Annual Meeting of the American Ceramic Society, 27–30 April, Nashville, Tennessee.

Glass, S. J., and R. Tandon. 2003. Controlling the mechanical behavior of stressed glass. Paper presented at the International Conference on the Fracture Mechanics of Ceramics, 25–28 February, Houston, Texas.

Glass, S. J., and R. Tandon. 2003. Strength and fragmentation of stressed glass. Paper presented at the 5th International Meeting of Pacific Rim Ceramic Societies, 29 September–2 October, Nagoya, Japan.

Glass, S. J., E. K. Beauchamp, S. Kamat, and A. Varshneya. 2002. Strength and fragmentation of stressed glass. Paper presented at the Glass and Optical Materials Division Meeting, 14–16 October, Pittsburgh, Pennsylvania.

Glass, S. J., E. K. Beauchamp, S. Kamat, K. Schwing, and R. Tandon. 2002. Strength and fragmentation of ion-exchanged glass. Paper presented at the 14th Annual Rio Grande Regional Symposium on Advanced Materials, 21 October, Albuquerque, New Mexico.

Kamat, S. S., E. K. Beauchamp, and S. J. Glass. 2002. Finite-element analysis of dicing behavior in thermally tempered and ion-exchanged glasses. Paper presented at the 14th Annual Rio Grande Regional Symposium on Advanced Materials, 21 October, Albuquerque, New Mexico.

Sglavo, V., D. J. Green, M. Abrams, S. J. Glass, and R. Tandon. 2003. Measurement of residual stresses in glass components: A comparison of different experimental techniques. Paper presented at the 105th Annual Meeting of the American Ceramic Society, 27–30 April, Nashville, Tennessee.

Tandon, R., and S. J. Glass. 2003. Controlling the fragmentation behavior of stressed glass. *Proc. 8th International Symposium on Fracture Mechanics of Ceramics* **14–15** (25–28 February, Houston, Texas). SAND2003-0775J.

Tandon, R., and S. J. Glass. 2002. Indentation behavior of ion-exchanged glass. Paper presented at the 14th Annual Rio Grande Regional Symposium on Advanced Materials, 21 October, Albuquerque, New Mexico.

Tandon, R., and S. J. Glass. 2002. Indentation behavior of ion-exchanged glass. Paper presented at the 27th Annual Conference and Exposition on Advanced Ceramics and Composites, 26–31 January, Cocoa Beach, Florida.

52730

Advanced Packaging Technology for Optical Firesets

B. Jokiel, Jr., M. V. C. Robinson, F. J. Peter, D. W. Peterson, L. S. Weichman

Developing packaging technologies for complex microsystems is of critical interest to Microsystems and Engineering Sciences Applications (MESA) and nuclear weapons (NW) initiatives. One very important example of a microsystem application is for optical firesets that need a miniature high-power optical switch for high-consequence signals that couples relatively large amounts of power from an optical fiber to a photovoltaic (PV) cell via a microelectromechanical systems (MEMS)–based discriminator. Realizing this microsystem will require the development of new and unique packaging technologies that integrate electrical, optical, and mechanical components with full consideration for hermeticity, materials compatibility, physical layout, assembly processes, manufacturability, and reliability. Sandia will explore these constraints with the goal to develop assembly and packaging technologies to combine all needed optical-switch components in a small volume. The final package must provide for (1) electrical connections to the MEMS and PV device, (2) precision alignment of the optical elements in three dimensions to accommodate out-of-plane beam paths, (3) thermal management, (4) repeatable and robust assembly processes for ease of manufacturing, (5) hermeticity, and (6) system reliability commensurate with weapon reserve (WR) applications.

The first step will be to consider several different conceptual system/package designs for the high-power optical-switch portion of an optical fireset. Each design would specify the critical component parameters as well as the required packaging technologies. We will identify and research key assembly processes for each design to evaluate manufacturability issues. A down-select to the best overall packaging technology will occur at the end of current work, based on evaluation of the conceptual designs, experimental data from assembly-process development, and preliminary failure-mode analysis. We will devote upcoming work to developing the full packaging technology, resulting in the delivery of technology demonstration units at the end of this project.

Developing packaging technologies for complex microsystems is of critical interest to Microsystems and Engineering Sciences Applications (MESA) and nuclear weapons (NW) initiatives....Realizing this microsystem will require the development of new and unique packaging technologies that integrate electrical, optical, and mechanical components with full consideration for hermeticity, materials compatibility, physical layout, assembly processes, manufacturability, and reliability. Sandia will explore these constraints with the goal to develop assembly and packaging technologies to combine all needed optical-switch components in a small volume.

We investigated four different paradigms for optical manipulation (MEMS shutters, movable mirror devices, optical fiber, and PV steering). We eliminated the fiber and PV steering concepts early. The required interaction of the fiber or PV with the MEMS discrimination device dictated by NW safety requirements did not lend itself to silicon MEMS applications and raised significant reliability issues. MEMS shutter systems cannot create out-of-line beam paths and therefore will not ultimately meet NW safety requirements; however, their simple structure and many assembly difficulties are ideally suited to be used as test devices for the perfection of basic packaging-unit processes necessary for hermetic optical packaging. We found MEMS mirror devices to be the most versatile methods for controlling and switching optical energy and to have the highest potential to meet NW safety requirements. We developed a new hermetic-package architecture adaptable to different applications, satisfying NW safety requirements that provide an out-of-line optical path, an exclusion region, and a potential to incorporate a passive monitoring circuit.

We investigated methods for attaching fiber to ferrule, ferrule to housing, MEMS to package, package to housing, and PV to housing. We leveraged existing work to develop hermetic optical-fiber ferrule designs suitable for brazing, press-fitting, or welding. We investigated the use of adhesives, but did not find them to be a reliable alternative for a hermetic package. A ferrule lightly pressed into the housing with a laser weld appears to be a good choice. The housing itself will be precision-machined from Kovar with gold plating in places where it is needed (on the surfaces connecting to the 40- and 18-pin ceramic leadless chip carriers [LCCs] for the MEMS and PV die attach, respectively). We used the 40- and 18-pin LCCs due to their availability, embedded electrical connections, and large areas for attachment (seal rings). Die attach for both the PV and the MEMS die may require precision-bond line-thickness control, which we will investigate further. We investigated methods for attaching the LCCs to the housing, including solder reflow and thermocompression bonding. It appears that using indium (In) in a thermocompression bond has a number of advantages for use with MEMS devices, including active alignment, low-temperature processing, and no out-gassing, all of which are important to the assembly of a MEMS device. The order of the operations and assembly steps is as follows: (1) solder fiber to ferrule, (2) precision lap and polish fiber tip, paying close attention to overall ferrule length, (3) machine Kovar housing, (4) apply In performs to both housing and LCCs, (5) light-press the ferrule into housing and

We found MEMS mirror devices to be the most versatile methods for controlling and switching optical energy and to have the highest potential to meet NW safety requirements. We developed a new hermetic-package architecture adaptable to different applications, satisfying NW safety requirements that provide an out-of-line optical path, an exclusion region, and a potential to incorporate a passive monitoring circuit.

laser-weld interface, (6) attach MEMS die to 40-pin LCC and wirebond, (7) use Karl Suss thermocompression bonder to align and attach 40-pin LCC to housing, (8) use Karl Suss thermocompression bonder to align and attach 20-pin LCC to housing, and (9) coat assembly with underfill material to strengthen the In compression bond.

52731

Miniature Transmitter Filter for JTA Using LIGA Technology

M. A. Forman, A. M. Morales, D. M. Skala, D. R. Boehme

The substantial miniaturization of transmit-and-receive components for Joint Test Assembly (JTA) flights can be achieved through the reduction in volume of microwave bandpass filters. To continue the drive toward the miniaturization of telemetry components, it is necessary to reduce the size of the passive filter, which typically dominates the volume of commercial transmitter and receiver components.

This reduction in volume can be achieved through filters comprising quasi-lumped elements. Quasi-lumped elements are electrically small discontinuities implemented with uniplanar high-aspect-ratio transmission lines, which provide significantly larger interconductor capacitances than traditional thin-film microstrip lines. These high capacitances provide the mechanism for creating high- Q (quality) filters, which are otherwise unrealizable with standard fabrication techniques.

Sandia will fabricate the high-aspect-ratio transmission lines using the LIGA (the German term Lithographie, Galvanoformung, und Abformung, for lithography, electroforming, and molding) microfabrication process. The LIGA process enables the creation of transmission lines with aspect ratios of or better than seven to one and conductor sidewall slopes greater than 89.9 deg. These high-aspect-ratio transmission lines provide the required interconductor capacitances necessary to create quasi-lumped elements for use in high- Q filters.

To date, we have completed transmission-line and prototype-filter simulations, created and submitted an exposure mask, and taken preliminary steps toward the fabrication of microwave circuitry. Our focus grew from just filter design to encompass the characterization of the transmission line, which demonstrates, in simulation, very useful characteristics.

We completed initial simulations of the high-aspect-ratio transmission lines. Simulations show that the electrically thick, micromachined coplanar waveguide possesses decreased dielectric loss, significantly reduced conductor loss, and propagation characteristics conducive to the creation of high- Q filters.

Simulations show that this high-aspect-ratio finite-width conductor-backed coplanar waveguide (CPW) provides the

Rendering of the quartz wafer with copper LIGA components in the form of radio-frequency (RF) coplanar waveguide transmission lines.

lowest loss of any CPW line demonstrated to date. Additional benefits are low dispersion, low radiation leakage, suppression of higher-order modes, and the elimination of airbridges. The transmission line demonstrates strong potential for use in low-loss uniplanar filters and high-power, high-frequency transmission lines.

The dominant source of loss in CPW transmission lines is conductor loss, which is due to high current densities at conductor edges. By increasing the thickness of the conductor by means of the LIGA fabrication process, current densities and ohmic losses drop. Simulations show a significant reduction in conductor loss from -15.28 dB/m for a 9 μm CPW to -3.95 dB/m for a 500 μm CPW at 20 GHz. Simulations show a reduction in total loss from -15.5 dB/m for a 9 μm CPW down to -4.0 dB/m for a 500 μm CPW at 20 GHz. Note that the total loss of the micromachined transmission line is on the same order as traditional microstrip transmission lines with none of the drawbacks.

Upon completion of the simulations, we created, submitted, and approved an initial mask.

Currently delivery of the circuitry is delayed because of fabrication difficulties with the experimental quartz-on-copper process. Delays are due to the cracking of the quartz substrate during polishing, as well as difficulties with the final release etch.

52732

Novel and Robust Environmental Sensing Devices (ESDs)

M. A. Polosky, D. C. Graf, P. Lemke, B. Jokiel, Jr., S. M. Wooden, F. Uribe, A. W. Roesler, R. A. Kellogg, J. W. Franklin

Environmental sensing devices (ESDs) are used as surety components throughout the nuclear stockpile. The stockpile ESDs cover a broad range of acceleration setpoints. The devices have been problematic from the standpoint that they are difficult to manufacture (due to precision spring tolerances) and are difficult to maintain (due to potential fluid leakage). As such, there is a critical need to develop next-generation ESDs that support both current and future surety themes.

Current ESD technologies rely on fluid for damping to attain appropriate g-second responses. Issues related to thermal expansion and hermetic sealing are problematic for this type of damping technology. Also, current ESDs provide only an acceleration switching function and utilize an electrical switch closure for output. Sandia seeks to develop a new class of ESDs that provide both analog and digital output and utilize nonfluid damping techniques. The design will continue to utilize the mechanical-based component theme to meet nuclear-safety requirements but will include advancements in the input/output (I/O) scheme. We will develop information in the form of unique signal generation coupled to switch closures and analog signals proportional to acceleration environment. Also, we will investigate alternate damping means such as eddy-current damping, magnetic damping, and mechanical damping.

We will concentrate on the ESD design while exploring solutions in all of Sandia's relevant micromachining technologies. This project will result in a fully functional prototype ESD characterized relative to nuclear weapons requirements.

We developed, fabricated, and demonstrated three microelectromechanical systems (MEMS)-based ESD concepts. The first device is fabricated in a new novel batch-fabrication LIGA (the German term *Lithographie, Galvanoformung, und Abformung*, for lithography, electroforming, and molding), process that precludes arduous hand-assembly. We fabricated the device with bonded rare-earth (RE) magnetic material embedded in the sense mass. As the sense mass translates over a conductive substrate, eddy currents are generated. Eddy currents set up forces that oppose the motion of the sense mass. Our goal is to utilize these forces to

Environmental sensing devices (ESDs) are used as surety components throughout the nuclear stockpile....Sandia seeks to develop a new class of ESDs that provide both analog and digital output and utilize nonfluid damping techniques. ...We will concentrate on the ESD design while exploring solutions in all of Sandia's relevant micromachining technologies. This project will result in a fully functional prototype ESD characterized relative to nuclear weapons requirements.

damp the sense mass motion and achieve a usable g-second product. Output from this device is an electrical switch closure.

The second prototype, also fabricated in LIGA was a precision ESD to operate in low-gravity (low-g) environments. The device has two forms of output: an electrical switch closure and a separate analog signal proportional to acceleration. The analog circuit uses a giant magnetoresistive (GMR) sensor and a shaped RE magnet to measure sense-mass displacement. Initial “bench-top” testing yielded 1.5 V/g sensitivity for the arrangement. Currently a low-temperature co-fired ceramic (LTCC) package is under fabrication at Honeywell FM&T. Integration and “full-up” testing will take place soon.

The third prototype, built on the earlier version, integrates an electrical coil to form a microgenerator. We fabricated a demonstration device using micro-electrodischarge machining (micro-EDM). Test results agree well with modeling predictions. We are able to generate a 1.4 V alternating current (AC) signal as the sense mass oscillates. This microgenerator concept will enable enhanced surety architectures, such as charging various warhead electrical system (WES) electrical circuits during a re-entry environment.

We fabricated a demonstration device using micro-electrodischarge machining (micro-EDM). Test results agree well with modeling predictions. We are able to generate a 1.4 V alternating current (AC) signal as the sense mass oscillates. This microgenerator concept will enable enhanced surety architectures, such as charging various warhead electrical system (WES) electrical circuits during a re-entry environment.

52733

Advanced Neutron Monitors for JTA and Stockpile Monitoring

N. R. Hilton, J. K. Estrada, A. M. Morales, C. M. Cuppoletti

Conventional Sandia neutron monitors, used for scoring neutron generators in joint test assembly (JTA) flights and for stockpile validation studies, rely on the knock-on proton (KOP) technique for neutron detection. The KOP detectors are very effective if placed close to the neutron source, but lack adequate sensitivity if located any distance from the generator. In addition, we found KOP detectors to be sensitive to x-rays from the neutron generator, which interferes with their ability to judge neutron output. We also used another neutron-detector technology based on scintillation detection for neutron monitors. Scintillation detectors have excellent sensitivity and can be placed some distance from the neutron generator, but they lack adequate “directionality” when placed at a distance and cannot distinguish the output from individual neutron generators. We seek a new neutron monitor, based on microfabricated scintillation detectors, that combines the advantages of scintillation detectors with the ability to independently score individual neutron generators. Our proposed detector consists of scintillator segments that can track the scattered proton in a scintillation neutron detector. We will perform (1) radiation-transport studies to determine expected distribution of neutrons at the detector (with respect to energy and direction) and the track of protons produced in the detector by neutron scattering, and (2) design, development, fabrication, and testing of new neutron detectors.

(1) We completed luminous jet calculation of scattered protons in polymethyl methacrylate (PMMA) scintillator in the code TRIM and repeated it with LabView and MATLAB.

(2) We computed the response of the stacked thin-plate detector design using simple computation approximations, but that will be followed by more sophisticated modeling in MCNPX.

(3) We completed the first etching experiments on PMMA with fluors, but we switched from a PMMA to a polyvinyl toluene (PVT)–based chemistry for the scintillators.

(4) We designed and constructed the angular/x-ray response apparatus. We configured the x-ray and neutron source and are installing the precision rotary stages.

(5) We evaluated single photocathode photomultiplier tubes (PMTs) and began our evaluation of multi-anode PMTs and

Photograph of 100 μm -thick PVT scintillator film. The photograph was taken by light emitted by the scintillator when excited with UV light.

We seek a new neutron monitor, based on microfabricated scintillation detectors, that combines the advantages of scintillation detectors with the ability to independently score individual neutron generators.

avalanche photodiode (APD) arrays to complete the evaluation of optical readout technologies with experimental results.

(6) We designed a thin-plate demonstration experiment.

(7) We fabricated thin-plate demonstration modules and will fabricate more to optimize deposition of PVT layers.

(8) We measured the angular response and are ready to begin x-ray testing to find the sensitivity of the thin-plate modules to demonstrate feasibility.

(9) We completed the final LIGA (the German term *Lithographie, Galvanoformung, und Abformung*, for lithography, electroforming, and molding) fabrication experiments and determined the dimensional parameters of LIGA fabrication with fluor-loaded PMMA scintillator parts. We did this using spin-coated PVT scintillators.

52740

A Microbioreactor for Hydrogen Production

A. W. Walker, B. J. Kirby

This work will utilize Sandia's expertise in microfabrication and protein immobilization to create an enzyme-based microreactor for hydrogen (H) production.

Microorganisms are used to produce valuable products. Recent work has explored combining the organisms' complex biochemical recognition and in vivo signal transduction with microdevices to create an integrated "biomicrodevice" capable of sensing and transmitting.

Using microorganisms in a production process or microelectronic platform is complex, requiring genetic manipulation and control of growth conditions. In addition, the presence of the cellular membrane and the complex metabolism of the organism create an unstable system with slow kinetics and poor efficiencies.

It is therefore desirable to create a cell-free protein system that can carry out the signal transduction or molecular synthesis in the absence of rate-limiting and energy-depleting cell structure and machinery. Cell-free multiprotein systems are complex. Compounds (or electrons) must be passed from one protein to the next; enzyme cofactors also need to be available and regenerated.

This work proposes to create a microbioreactor capable of converting glucose-6-phosphate to H. Previous researchers demonstrated that a soluble cell-free enzyme system can convert glucose-6-phosphate to H. We intend to immobilize these proteins on a microfabricated glass structure, thus creating an integrated microbioreactor capable of converting glucose-6-phosphate to H. Enzymes that convert glucose to glucose-6-phosphate have also been studied; thus, the possibility exists to expand the reactor in the future to produce H directly from glucose.

This work will explore ways to immobilize proteins on microfabricated structures while maintaining protein function and protein-protein communication. This work could also result in a platform for studying and utilizing complex reaction and signaling pathways.

This project resulted in the development of an inexpensive and robust in-line H sensor. We created the H detection system by adapting a high school biology "kit" intended to monitor nitrogen (N) fixation. The adapted system was able to monitor H production in real time at concentrations below 1 ppm.

This work will utilize Sandia's expertise in microfabrication and protein immobilization to create an enzyme-based microreactor for hydrogen (H) production....This work will explore ways to immobilize proteins on microfabricated structures while maintaining protein function and protein-protein communication. This work could also result in a platform for studying and utilizing complex reaction and signaling pathways.

The key enzyme required for the production of H from glucose is encoded by the “extremophilic” microorganism *Pyrococcus furiosus*. This unique hydrogenase is required in this work because it uses NADPH (nicotinamide adenine dinucleotide phosphate, reduced form) (as opposed to ferredoxin) as an electron donor. Thus, by incorporating enzymes into the system that couple glucose oxidation with the regeneration of NADPH from NADP (nicotinamide adenine dinucleotide phosphate, oxidized form) (e.g., glucose dehydrogenase), we are able to produce H from glucose. In other words, if the enzyme’s glucose dehydrogenase and hydrogenase are placed in solution together, and glucose and NADP are added to the reaction mix, the glucose will be oxidized to gluconic acid and, in so doing, will generate NADPH. The hydrogenase enzyme is then able to use the NADPH as an electron donor to generate molecular H and, as a result, NADPH is oxidized back to NADP. The cycle then repeats until the supply of glucose is exhausted. The enzyme is extremely sensitive to oxygen and is thus a challenge to work with.

We obtained the following experimental results:

(1) We used the hydrogenase enzyme to produce H in solution in the absence of other enzymes. We added both artificial and the natural (NADPH) electron donors to the reaction mix to enable H production. We used a total reaction volume of 2 ml to demonstrate H production on a small scale. We obtained yields of H exceeding 90%; however, we observed a maximum production rate of just ~ 500 nmol/hr.

(2) We produced H via enzymatic conversion of glucose where all reaction components (including enzymes) were in solution (as opposed to immobilized within a microfluidic reactor). In this system, we added the enzymes glucose dehydrogenase and hydrogenase to a reaction mix containing NADP and glucose. We observed H production at a maximum production rate of ~ 500 nmol/hr. Once H production stopped (presumably due to the depletion of the supplied glucose), we added additional glucose to the system and again observed H production.

(3) To realize the vision of this work, we generated the reaction that using enzymes in solution would have to be incorporated into a microreactor architecture by immobilizing the enzymes on a substrate. Toward this end, we immobilized the enzymes glucose dehydrogenase and hydrogenase on porous silica beads. Initial results showed that H was produced at rates roughly 20x less than the rates observed in solution. In addition, when we added additional glucose, no additional H

was produced. We believe that this decreased rate is due to buffer-compatibility issues involved in the immobilization process. A buffer exchange was done, and we repeated the experiment. We observed very little H production and determined that the immobilization process had inactivated the hydrogenase enzyme.

Though this work failed to reach its goals, it clearly demonstrated that H can be enzymatically produced from glucose. To reach the goals of this work, a considerably larger research effort involving more competencies will be required. Most notably, enzyme-engineering techniques will need to be employed to increase H production rates.

52741

Self-Organizing Software Research and Development

G. C. Osbourn, A. M. Bouchard

Sandia previously made progress in developing a new statistical mechanics approach to designing self-organizing systems that are unique to Sandia. The primary application target for this ongoing research was the development of new kinds of nanoscale components and hardware systems. However, this research also enables an out-of-the-box connection to the field of software development. With appropriate modification, the collective-behavior physics ideas for enabling simple hardware components to self-organize may also provide design methods for a new class of software modules. Our current physics simulations suggest that populations of these special software components would be able to self-assemble into a variety of much larger and more complex software systems, and that this self-organization process can be steered. If successful, this would provide a radical (disruptive technology) path to developing complex, high-reliability software unlike any known today. This high-risk, high-payoff opportunity does not fit well into existing Sandia funding categories, as it is well outside the mainstreams of both conventional software-development practices and the nanoscience research area that spawned it. We propose a significant effort aimed at realizing a larger-scale self-organizing software system, and to demonstrate the unique capabilities and advantages of this radical new approach for software development.

We identified a few crucial properties of proteins and their interactions that are sufficient to enable the processes of self-assembly and computation. (1) Proteins have tremendous selectivity of their binding sites, operating much like a lock and key. (2) Binding or unbinding a ligand at one of these sites can result in a conformational change of another part of the protein. This conformational change can perform some sort of actuation, such as moving (e.g., in motor proteins) or catalyzing an assembly or disassembly reaction (e.g., in enzymes). (3) A conformational change can also expose (or hide) additional binding sites, which in turn can bind and cause a conformational change resulting in actuation, or exposing or hiding yet another binding site.

We abstracted these important self-assembly and computational properties of proteins into an “agent,” the

Our current physics simulations suggest that populations of these special software components would be able to self-assemble into a variety of much larger and more complex software systems, and that this self-organization process can be steered. If successful, this would provide a radical (disruptive technology) path to developing complex, high-reliability software unlike any known today.

fundamental building block of our self-assembling software. An agent can store data, perform some simple or complex computation, or both. Each agent has binding sites that can bind only to matching sites (property [1]). Once bound, property (2) enables it to actuate (perform its computation). Property (3) enables it to then bind to another agent, to trigger it to execute next, so that a sequence of computations may be carried out in a specific order. We developed the infrastructure to allow software self-assembly processes to occur and to provide an example of the use of this approach to self-assemble and modify software modules.

We demonstrated the synthesis of some simple software systems as a test of our biophysics-emulating, dynamic self-assembly scheme. Sets of software building blocks actively participate in the construction and subsequent modification of the larger-scale programs of which they are a part. Self-assembly generates hierarchical modules (including both data and executables), creates software execution pathways, and concurrently executes code via the formation and release of activity-triggering bonds. Hierarchical structuring is enabled through encapsulants that isolate populations of building-block binding sites. The encapsulated populations act as larger-scale building blocks for the next hierarchy level. Encapsulant populations are dynamic, as their contents can move in and out. Such movement changes the populations of interacting sites and also modifies the software execution.

We showed that our new approach offers novel constructs for constructing large hierarchical software systems and reusing parts of them. For example, we implemented a self-assembling software construct called a “situation.” Situations provide a mechanism for “sensing” whenever certain conditions or events occur by providing passive agents with empty binding sites. These binding sites correspond to the conditions of interest, and when all sites are bound, the sensing agent is activated to report or trigger a desired response. Situation detection is asynchronous. It is also passive, in that no repeated active polling by the agent itself is required to detect the events.

We also implemented an “external override.” This self-assembling software construct overrides the behavior of the existing code, and it is imposed externally, i.e., the original source code “inside” the executable is not modified; instead, additional agents are added from the outside to effect the override. External overrides, inspired by the biological roles of protein phosphorylation, temporarily (or permanently) switch off undesired subsets of behaviors (code execution, data access/modification) of other agents.

We showed that our new approach offers novel constructs for constructing large hierarchical software systems and reusing parts of them.

“Monitoring” is a special case of the override and situation processes and was implemented to inspect the code or the status of its agents. Monitors are like the external override in that they are implemented by inserting agents into the execution pathway during runtime. They are like the situation in that they can sense sought-after conditions of the running code and report on activity or on the data that are being manipulated. Monitoring and querying differ only in their usage. Monitoring is used to “keep an eye on” some aspect of the code.

Refereed

Bouchard, A. M., and G. C. Osbourn. 2003. Dynamic self-assembly and computation: From biological to information systems. *Proc. 1st International Workshop on Biologically Inspired Approaches to Advanced Information Technology*, submitted. SAND2003-3441C.

Osbourn, G. C., and A. M. Bouchard. 2003. Dynamic self-assembly of hierarchical software structures/systems. *Proc. AAAI Spring Symposium: Computational Synthesis SS-03-02* (24–26 March, Stanford, California): 181–88.

52742

Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly

P. M. Dentinger, W. Bauer, S. Pathak

Highly specific interactions between deoxyribonucleic acid (DNA) could potentially be amplified if the DNA interactions were utilized to assemble large-scale parts. Fluidic assembly of microsystem parts has the potential for rapid and accurate placement of otherwise difficult-to-handle pieces. Ideally, each part would have a different chemical interaction that allowed it to interact with the substrate only in specific areas. One easy way to obtain a multiple chemical permutation is to use synthetic DNA oligomers. Sandia prepared silicon (Si) parts using Si-on-insulator (SOI) technology microfabrication techniques. We developed several surface-chemistry protocols to react commercial oligonucleotides to the parts. However, we achieved no obvious assembly. It was thought that small defects on the surface did not allow the microparts to be in close enough proximity for DNA hybridization, and this was, in part, confirmed by interferometry. To assist in the hybridization, we manufactured plastic, pliable parts and developed a new chemistry. However, assembly was still absent, even with the application of force. It is presently thought that one of three mechanisms is preventing the assembly. The surfaces of the two solid substrates cannot get in close enough proximity, the surface chemistry lacks sufficient density to keep the parts from separating, or DNA interactions in close proximity on solid substrates are forbidden.

We have found that the problem is now focused onto three remaining hypotheses, with a clear understanding and an experimental plan to determine which is correct. We attempted several DNA-directed microelectromechanical systems (MEMS) piece-part assemblies. As yet, we have observed no DNA-directed assembly. The present limitations include at least a quantitation of the surface chemistry on the as-derived piece parts, physical constraints such as particulate matter and surface roughness, and the potential that constrained DNA/DNA interactions are forbidden. One can get a better understanding of the surface chemistry by doing intermediate assays on amine concentrations. The particulate count can be diminished by decreasing the part size, and we developed quantitative interferometry to characterize these improvements. We discussed several suggestions for quantifying surface

Highly specific interactions between deoxyribonucleic acid (DNA) could potentially be amplified if the DNA interactions were utilized to assemble large-scale parts.

Fluidic assembly of microsystem parts has the potential for rapid and accurate placement of otherwise difficult-to-handle pieces.

chemistry on the piece parts and getting around the particulate-matter and surface-roughness limitations. These suggestions should allow one to test the thought that constrained DNA/DNA interactions are possible or not for solid/solid assembly.

52743

Computational Model of a Microbial Cell

S. J. Plimpton, M. D. Rintoul, A. Slepoy

*Sandia seeks to develop an initial version of a particle-based simulation model of a prototypical microbial (prokaryotic) cell. Individual proteins, protein complexes, and other organic molecules are represented as single particles in the model. Particles diffuse via Brownian motion and react with other nearby particles, each time-step in accord with chemical-reaction equations. Geometric compartments within the model represent organelles within the cell, membranes, and the cell itself. We have used the model thus far to study a simple kinase signaling cascade as a comparison to well-mixed Gillespie-style stochastic models, and to model a portion of the carbon-fixation pathway in carboxysomes of the *Syncechococcus* microbe.*

Sandia seeks to develop an initial version of a particle-based simulation model of a prototypical microbial (prokaryotic) cell.

We developed a simulation model for microbial cells with the following key features:

- (1) Particles in the model represent a protein, a protein complex, or other reacting molecule.
- (2) The model contains a hierarchy of geometric compartments. Individual compartments can represent the cell nucleus or other vesicles, two-dimensional (2-D) membranes between 3-D compartments, and the cell itself.
- (3) Particles move within the simulation geometry via Brownian motion (a random walk). Each particle species is assigned a diffusion coefficient. As particles hit compartment boundaries, permeability rules are enforced so that particles can move from one compartment to another.
- (4) Each time-step, pairs of nearby particles react according to an input set of chemical rate equations. Reactions produce new particle species. Thus the model captures both chemistry and spatial effects within a simplified cellular geometry.

We have simulated two test problems thus far. We successfully modeled a three-stage kinase signaling cascade that involves seven molecular species and a similar number of reactions. The results agreed with those from a well-mixed (nonspatial) Gillespie stochastic model when the diffusion coefficients were large.

We began to model a portion of the carbon-fixation process in *Syncechococcus* (a marine microbial cell) using approximately 20 species and chemical reactions. In this model, bicarbonate ions diffuse into the cell cytoplasm and concentrate within the carboxysome organelle, where they are converted to

CO₂. RuBisCO protein complexes then convert the CO₂ to organic sugars.

We designed the data structures and computations of the model to allow for parallel computation, which would enable simulations with millions of particles. To date, all of our simulations have been small workstation-class computations; thus, we have not yet implemented the parallel portions of the code.

52744

Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents

R. C. Hughes

Present methods of air sampling for low concentrations of chemicals like explosives and bioagents involve noisy and power-hungry collectors with mechanical parts for moving large volumes of air (think DustBuster). However, there are biological systems that are capable of detecting very low concentrations of molecules with no mechanical moving parts. An example is the silkworm moth antenna, which is a highly branched structure where each of 100 branches contains about 200 sensory “hairs” that have dimensions of 2 μm wide by 100 μm long. The hairs contain about 3000 pores, which is where the gas-phase molecules enter the aqueous (lymph) phase for detection. Simulations of diffusion of molecules indicate that this “forest” of hairs is “designed” to maximize the extraction of the vapor-phase molecules. Since typical molecules lose about four decades in a diffusion constant upon entering the liquid phase, it is important to allow air diffusion to bring the molecule as close to the “sensor” as possible. The moth acts on concentrations as low as 1000 molecules per cubic centimeter (one part in $1\text{e}16$). A three-dimensional (3-D) collection system of these dimensions can be fabricated by micromachining techniques available at Sandia. The trick will be to figure out how to line the “hairs” with chemical sensors of high sensitivity. This project addresses the design issues of turning 2-D sensor arrays like electrochemical ion channel detectors into essentially a 3-D array.

This project addresses the design issues of turning 2-D sensor arrays like electrochemical ion channel detectors into essentially a 3-D array.

We studied the structures that insects, particularly moths, use to gather volatile organic compounds (VOCs) from the air and detect them. The chemical sensors themselves are ion channels in the walls of olfactory nerve cells that are very small in dimension; the individual ion channels have capture areas of only about 10 nm in diameter. However, the structures that extract the VOCs from the air are roughly 2 μm wide and 100 μm long. To begin our simulation of these structures with micromachined components, we designed a 3-D structure that places a micromachined hotplate with absorbent material on it in close proximity to a chemiresistor that is formed on a planar, photolithographically defined set of electrodes. The absorber on the hotplate has dimensions of 0.04 cm^2 with a thickness of about 50 μm . The individual absorber particles are made from commercial Carboxen 1000 and are ground to dimensions of

about 25–50 μm . The chemiresistor electrodes are 50 μm apart, and the chemiresistor material is about 1 μm thick. The 3-D structure allows the absorber particles to approach within about 1 mm of the chemiresistor material. The air sampling is performed by passing air containing a VOC (xylene in our experiments) across the absorber material for specified lengths of time. The absorbed xylene is then released in a very fast heat pulse provided to the hotplate. The heat-driven diffusion of the plume of xylene produces a pulse signal on the chemiresistor, showing that the plume of chemical has been detected. By varying the flowrate of the chemical plume across the absorber material, we showed how the flowrate affects the number of xylene molecules that are absorbed in a given time. By using this form of preconcentration, we were able to enhance the sensitivity of our system by about a factor of 100 over the chemiresistor alone. In future studies we hope to show that by micromachining posts of different dimension and spacing and coating them with the absorber particles, we can mimic VOC extraction capabilities of the moth antenna. We showed these natural designs by fluid-flow tests to be highly efficient in extracting VOCs from air.

The insects not only have excellent air-sampling efficiency, but the chemical sensors to which the molecules are delivered are capable of detecting almost all of the molecules reaching them. The chemiresistors that we used in our air-sampling studies are much less sensitive and require concentrations in the ppm level for a good signal-to-noise. This is compared to the moth-detection level of about 1 part in $1\text{e}16$. In this project, we also looked at how micromachined devices might be used to mimic single-molecule detection. We are devising ways to fabricate extremely small pores in dielectric films based in a planar silicon support structure. In future projects, we hope to be able to use these artificial pores as single-molecule detectors similar to ion channels. If we are able to make them work, it will be relatively easy to create arrays of these single-molecule detectors that then can be coupled to the micromachined air-sampling arrays.

Refereed

Davis, C. E., C. K. Ho, R. C. Hughes, and M. L. Thomas. 2003. Enhanced detection of m-xylene using a preconcentrator with a chemiresistor sensor. *Sensors and Actuators*.

52745

A Biological Model for Controlling Interface Growth and Morphology

E. A. Holm, J. J. Hoyt

Biological systems create proteins that perform tasks more efficiently and precisely than conventional chemicals. For example, many plants and animals produce proteins to control the freezing of water. Some biological antifreeze proteins (AFPs) simply decrease the freezing temperature of water. Other AFPs inhibit the solidification process itself, even below the freezing point. These molecules bond to specific sites at the ice/water interface and are theorized to suppress solidification chemically or geometrically. Not only do these tailored proteins slow freezing, but they also smooth the ice/water interface, preventing cell damage upon freezing. They operate at low concentrations and without becoming engulfed in the solid. In this project, Sandia investigated the theoretical and experimental data on AFPs and performed analyses to understand the unique physics of AFPs. We analyzed the experimental literature to determine chemical mechanisms and effects of protein bonding at ice surfaces, specifically thermodynamic freezing-point depression, suppression of ice nucleation, solute drag on the moving solid/liquid interface, and stearic pinning of the ice interface. Understanding these novel antifreeze mechanisms could enable important medical and engineering applications. Ultimately, the biological model can provide a new perspective on a variety of novel and established technologies.

Our efforts focused on a search of the biological AFP literature and an analysis of current data and models using materials science tools. The focus of this effort centered on four proposed AFP mechanisms: thermodynamic freezing-point depression, suppression of ice nucleation, solute drag on the moving solid/liquid interface, and stearic pinning of the ice interface.

- A literature search conclusively revealed that thermodynamic freezing-point depression and/or suppression of ice nucleation is insufficient to explain the dramatic effects of AFPs on freezing. The undercoolings observed (up to 1.9°C in polar fish, for example) are far too large for solution thermodynamics to account for. Furthermore, at these undercoolings, the critical nucleus size of ice particles is small, and numerous heterogeneous nucleation sites exist, so ice-

Sandia investigated the theoretical and experimental data on AFPs and performed analyses to understand the unique physics of AFPs. ...Understanding these novel antifreeze mechanisms could enable important medical and engineering applications. Ultimately, the biological model can provide a new perspective on a variety of novel and established technologies.

crystal nucleation will be substantial. Both of these mechanisms were eliminated from further study.

- It is now well established that AFPs act to significantly slow the growth of ice crystals within the blood stream. Thus, we investigated whether the growth-rate suppression can be explained by the phenomenon of solute drag. It is well known within the metallurgical literature that concentrations of impurities as low as the ppm level can significantly reduce the rate of grain-boundary migration in alloys. Using the generally accepted theory of solute drag proposed by Cahn, combined with the mobility theory of Mikheev and Chernov with physical parameters suitable for AFPs, our analysis reveals that solute drag cannot explain the action of AFPs. The shift of the velocity versus undercooling relationship with solute drag relative to the intrinsic rate is very small, much less than 0.1°C . It appears the concentration is too low and/or the binding energy too small to explain the very slow ice growth rates observed in nature.

- Some biologists propose that AFPs inhibit solidification due to their size rather than their chemistry. To move past the array of large proteins, the solidifying surface must increase in area, which costs energy. Materials scientists are familiar with such “particle pinning” in a variety of systems. Following an analog of the Smith-Zener theory for particle pinning in solids, we analyzed geometric pinning by AFPs as a function of molecular size, concentration, solidification driving force (latent heat), and the surface properties of the AFPs (hydrophobicity). From this analysis, we predicted substantial slowing of the solidifying interface and a decrease in the maximum attainable ice-crystal size. However, while promising, this analysis does not explain how AFPs resist becoming engulfed in the growing ice crystal. That mechanism remains unknown.

The operation of AFPs remains a fertile area for further chemical and thermodynamic study. The science is complex, but the payoff may be substantial.

52746

Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions

M. D. Numan, C. J. Brinker

Sandia investigated three general synthetic approaches to incorporate polyoxometalates (POMs) as functional units in nanostructured materials: (1) POMs as building blocks for ordered arrays in which the POMs serve as both structural units and hosts for chemically bonded, functional subunits, (2) mesostructured silica films doped with POMs, and (3) aerosol-spray of precursor solutions of POM-based media for materials with hierarchical nano-/mesostructures. We developed a general procedure to form POM-surfactant arrays from POMs that vary in charge from 16- to 7+. We characterized the structures of these arrays. In general, they are lamellar with increasing (001) d-spacing with increasing POM charge. These POM-surfactant arrays then serve as precursors for thin-film formation, or may be reacted further to link the clusters to impart structural rigidity, or may be reacted further to incorporate a functional subgroup such as a luminescent metal. We also successfully produced silica-based films doped with POMs. In these materials, we showed that POM catalyzes decomposition of the organic template. Evaporation-induced ordering of the POM-surfactant material by aerosol-spray pyrolysis produces nanostructures that differ from the parent material.

(1) We developed a general procedure for ordering POM arrays in the thin-film and powder forms.

(2) We proved that the POMs remain intact (i.e., functional) as ordered arrays.

(3) We investigated array ordering as a function of POM charge.

(4) We incorporated POMs in surfactant-templated silica films and demonstrated removal of the surfactant template while leaving the POMs intact.

(5) We demonstrated the capability of aerosol-spray techniques to produce a mesoscale ordering of the nano-ordered POM arrays.

(6) A publication in press is partially supported by this work: *Synthesis, Structure, and Molecular Modeling of a Titanoniobate Isopolyanion*, by Nyman, *et al.*

- *General procedure for ordered POM arrays.* The following reaction occurs rapidly in aqueous solution, at room temperature and at any scale:

We developed a general procedure to form POM-surfactant arrays from POMs that vary in charge from 16- to 7+....These POM-surfactant arrays then serve as precursors for thin-film formation, or may be reacted further to link the clusters to impart structural rigidity, or may be reacted further to incorporate a functional subgroup such as a luminescent metal. We also successfully produced silica-based films doped with POMs. In these materials, we showed that POM catalyzes decomposition of the organic template.

A = counterion for POM; y = charge on POM; S = surfactant; X = counterion for surfactant.

Thus far, we have successfully carried out this reaction for anionic, cationic, and lacunary (anionic) POMs that range in charge from 16- to 7+. The POM-S product precipitates and can then be redissolved in a less-polar solvent and cast in a film, recrystallized for structural characterization, or further reacted in a nonaqueous medium to impart functionality or structural rigidity, such as by binding to a luminescent metal or a linking metal, respectively.

- *Retention of POM structure in ordered arrays.* We used infrared (IR) spectroscopy to show the POMs remain intact in these reactions for POM-S with POM = $[SiNb_{12}O_{40}]^{16-}$ and S = $(CH_3)_3N^+-C_{16}H_{33}$; a C₁₆-chain-length ammonium surfactant (commonly known as CTAB). The POM-S spectrum is essentially the sum of the spectra of the CTAB and the POM.

- *Preliminary characterization of POM-S ordering.* Characterization of the POM-S materials by powder x-ray diffraction (XRD) and transmission-electron microscopy (TEM) reveals a lamellar structure for the POM-S arrays. In general, the (001) *d*-spacing increases with increasing charge of the POM, which directly corresponds with increasing number of surfactants required for charge-balance. All the POM-S materials show different periodicities by electron diffraction, suggesting that arrangements in the two-dimensional (2-D) plane perpendicular to (001) vary as a function of POM charge/geometry.

- *Incorporation of POMs in surfactant-templated silica films.* We investigated aqueous sol-gel routes to porous surfactant-templated silica films doped with POMs, using non-ionic surfactant Brij 56 as the pore template. XES studies did not show any evidence for ordering at the POM/silica volume ratio studied (1:9), suggesting that POMs inhibit ordering. We used several strategies to remove the surfactant template to leave a porous material. The mechanism for surfactant removal by ultraviolet (UV) treatment appears to be a photocatalytic process involving the POM dopant, as surfactant-templated films lacking any POM do not exhibit any surfactant removal under the conditions employed.

- *Formation of ordered particles by evaporation-induced self-assembly of an aerosol.* Ordered particles were formed by dissolving the POM/surfactant complex $[HNb_6O_{19}][CTAB]_7$ in ethanol and running this solution through an aerosol generator. Subsequent evaporation of solvent in this aerosol initiated self-

assembly of particles with different mesoscale ordering than that seen in the parent complex before dissolution in alcohol.

Refereed

Nyman, M. D., L. J. Criscenti, F. Bonhomme, M. A. Rodriguez, and R. T. Cygan. 2003. Synthesis, structure, and molecular modeling of a titanoniobate isopolyanion. *J. Solid-State Chemistry*, accepted.

52747

Ornithopter*B. L. Spletzer, J. R. Salton*

Sandia seeks to develop a covert air vehicle. A mesoscale air vehicle that mimics a bird offers exceptional mobility and the possibility of remaining undetected during flight. Although some such vehicles exist, they are lacking in key areas: unassisted landing and launching, true mimicry of bird flight to remain covert, and a flapping flight time of any real duration. Current mainstream technology does not have the energy or power density necessary to achieve birdlike flight for any meaningful length of time; however, Sandia has unique combustion-powered linear actuators with the unprecedented high energy and power density needed for birdlike flight. Sandia developed the small-scale, high-pressure valves and small-scale ignition to make this work. We will study the feasibility of using this to achieve vehicle takeoff and wing flapping for sustained flight. This type of vehicle has broad applications for reconnaissance and communications networks, and could prove invaluable for military and intelligence operations throughout the world. We conducted initial tests on scaled versions of the combustion-powered linear actuator. The test results showed that heat-transfer and friction effects dominate the combustion process at “birdlike” sizes. The problems associated with microcombustion must be solved before a true birdlike ornithopter can be developed.

The development of a birdlike ornithopter should be based on a combustion system to provide sufficient energy density. Basing the design on a combustion-powered linear actuator originally developed to drive the Sandia hopping robots solves many of the problems inherent with internal-combustion engines and provides exceptional power and energy. Assuming a thermodynamic efficiency of 15%, a combustion system could provide sufficient power for hours of flight rather than the few minutes available with battery systems.

Tests show a thermodynamic efficiency in excess of 30% and a power density of 10 hp per cubic inch of displacement volume. These actuators can be well matched to a flapping wing in required force, stroke, and frequency.

For this feasibility study, we performed limited testing to verify the potential for achieving vehicle takeoff and wing flapping for sustained, long-duration flights of at least 1 hr.

The current size of the linear actuator was too large for a practical bird-size ornithopter. Therefore, development and

Sandia seeks to develop a covert air vehicle. A mesoscale air vehicle that mimics a bird offers exceptional mobility and the possibility of remaining undetected during flight. ...Current mainstream technology does not have the energy or power density necessary to achieve birdlike flight for any meaningful length of time; however, Sandia has unique combustion-powered linear actuators with the unprecedented high energy and power density needed for birdlike flight.

testing of smaller-scale combustion-driven linear actuators were necessary. However, the efficiency of combustion systems tends to drop with cylinder diameter for a number of reasons, and the primary goal of the tests was to determine whether sufficient efficiency could be attained in smaller scale.

We conducted several tests to measure the change in thermal efficiency of the combustion-driven linear actuator as the diameter of the combustion chamber is reduced. For a combustion-chamber size of 0.625 in. and greater, the thermal efficiency of the actuator is approximately 30%. However, as the combustion-chamber size is decreased below 0.625 in., the efficiency drops rapidly, dropping essentially to zero for a 0.25 in.-diameter combustion chamber. This is the largest size considered practical for a bird-size ornithopter.

Several factors could be at play. Wall-heat-transfer effects begin to dominate the combustion process. Wall quenching not only affects the combustion process, but also the ignition phenomena. A chamber diameter of 0.25 in. (6 mm) is certainly approaching the quenching diameter where a flame simply will not propagate. Since the surface area of the combustor becomes large compared to the combustion volume, piston friction begins to play a more important role in energy output of the linear actuator. Along the same lines, leakage between the piston and the cylinder becomes more dominant as the cylinder diameter decreases. Leakage will reduce the energy delivered to the piston. Research in the area of microcombustion is currently being conducted at many universities and institutions and was considered beyond the scope of this project.

Preliminary analysis of potential power systems showed that internal-combustion-engine power was the only system capable of the power densities necessary for any type of sustained flight lasting more than a few minutes. It was thought that the Sandia combustion-driven linear actuator developed for the Hopper robot could be modified and scaled to provide an actuator for a flapping air vehicle. Initial tests of the actuator in sizes scaled to the size of interest show that the thermal efficiency is too low at small piston diameters.

52748

Light-Powered Nanovehicles*J. A. Shelnutt, D. Y. Sasaki, C. J. Medforth*

Sandia investigated the possibility of constructing nanoscale metallic vehicles powered by biological motors or flagella that are activated and powered by visible light. The vehicle's body is to be composed of the surfactant bilayer of a liposome coated with metallic nanoparticles or nanosheets grown together into a porous single crystal. The diameter of the rigid metal vesicles is from about 50 nm to microns.

Illumination with visible light activates a photosynthetic system in the bilayer that can generate a pH gradient across the liposomal membrane. The proton gradient can fuel a molecular motor that is incorporated into the membrane. Some molecular motors require adenosine triphosphate (ATP) to fuel active transport. The protein ATP synthase, when embedded in the membrane, will use the pH gradient across the membrane to produce ATP from adenosine diphosphate (ADP) and inorganic phosphate. The nanoscale vehicle is thus composed of both natural biological components (ATPase, flagellum, actin-myosin, kinesin-microtubules) and biomimetic components (metal vehicle casing, photosynthetic membrane) as functional units. Only light and storable ADP, phosphate, water, and weak electron donor are required fuel components. These nanovehicles are being constructed by self-assembly and photocatalytic and autocatalytic reactions. The nanovehicles can potentially respond to chemical gradients and other factors, such as light intensity and field gradients, in a manner similar to the way that magnetic bacteria navigate. The delivery package might include decision-making and guidance components, drugs or other biological and chemical agents, explosives, catalytic reactors, and structural materials.

We expected in one year to be able only to assess the problems and major issues at each stage of construction of the vehicle and the likely success of fabricating viable nanovehicles with our biomimetic photocatalytic approach. Surprisingly, we were able to demonstrate that metallized photosynthetic liposomes can indeed be made. We completed the synthesis of metallized liposomes with photosynthetic function included, and studied these structures by electron microscopy. We used both platinum (Pt) and palladium (Pd) nanosheeting to coat the micelles. The stability of the vehicles to mechanical stress and the solution environment is enhanced by the single-crystalline Pt or Pd coating on the vesicle. With analogous platinized

Sandia investigated the possibility of constructing nanoscale metallic vehicles powered by biological motors or flagella that are activated and powered by visible light.

...The nanovehicles can potentially respond to chemical gradients and other factors, such as light intensity and field gradients, in a manner similar to the way that magnetic bacteria navigate. The delivery package might include decision-making and guidance components, drugs or other biological and chemical agents, explosives, catalytic reactors, and structural materials.

micelles, it is possible to dry the vehicles and resuspend them with full functionality. However, the liposomes drying on a transmission-electron microscope (TEM) grid may cause the platinized liposomes to collapse, although probably stay viable in solution. It remains to be shown whether a proton motive force across the metallized bilayer membrane can be generated and whether we will also be able to incorporate various functional capabilities, including ATP synthesis and functional molecular motors. Future tasks to complete the nanovehicles would be the incorporation of ATP synthase into metallized liposomes and the incorporation of a molecular motor into metallized liposomes.

Refereed

Song, Y., Y. Yang, C. J. Medforth, E. Pereira, A. K. Singh, H. Xu, Y. Jiang, C. J. Brinker, F. van Swol, and J. A. Shelnutt. 2003. Controlled synthesis of 2-D and 3-D platinum dendrites using porphyrin photocatalysts. *Book of Abstracts, Proc. Fall Meeting of the American Chemical Society* **1** (September, New York, New York): INOR 96.

52749

Anomalous High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source

C. J. Brinker, R. C. Hughes, S. M. Brozik

Sandia used electrochemical impedance spectroscopy (EIS) to characterize the effect of surfactant-templated mesoporous silica films deposited onto silicon (Si) electrodes on the electrical properties of the electrode space-charge region in an aqueous electrolyte solution. We observed a significant shift in apparent flat-band potential for electrodes modified with the silica film when compared to bare electrodes; the reliability of these data is suspect, however, due to contributions from surface states to the overall capacitance of the system. We measured electrode current under illumination as a function of potential and found it to increase as the electrode was driven further into depletion, as expected. To assist in the interpretation of these EIS data, we performed a series of measurements at platinum (Pt) electrodes with the hope of decoupling electrode and film contributions from the EIS spectra. Surprisingly, the frequency-dependent impedance data for Pt electrodes coated with a surfactant-templated film were nearly identical to those observed for bare Pt electrodes, indicating that the mesoporous film had little effect on the transport of small electrolyte ions to the electrode surface. We did not observe pore-blocking agents (tetraalkylammonium salts) to inhibit this transport process. However, untemplated (nonporous) silica films dramatically increased film resistance, indicating that our EIS data for the Pt electrodes are reliable.

(1) We used EIS to characterize the effect of surfactant-templated mesoporous silica films deposited onto Si electrodes on the electrical properties of the electrode space-charge region in an aqueous electrolyte solution. We measured the potential and frequency-dependent impedance for bare *p*-doped Si electrodes (resistivity = 1–10 ohm-cm) and compared them with data for the same electrode material coated with a ca. 200 nm silica film templated with a three-dimensional (3-D) cubic pore structure. We observed a significant difference in the impedance spectra between modified and unmodified Si electrodes. A plot of $1/C^2$ versus *E* (Mott-Schottky plot) was not linear at low frequency (500 Hz) and low potential, presumably due to surface states. At higher frequency (10 kHz) and more negative potentials, however, a large-enough linear region existed in the data to extrapolate the flat-band potential.

Sandia used electrochemical impedance spectroscopy (EIS) to characterize the effect of surfactant-templated mesoporous silica films deposited onto silicon (Si) electrodes on the electrical properties of the electrode space-charge region in an aqueous electrolyte solution.

Although the reliability of these data is not certain, we observed a shift in the flat-band potential for electrodes coated with the porous silica film, consistent with the induction of positive charge in the space-charge region by the negatively charged film. We measured electrode current under illumination as a function of potential and found it to increase as the electrode was driven further into depletion, as expected. We delayed further experiments with silica-film-modified Si electrodes until a more thorough understanding of the effect of the mesoporous silica film on ionic transport can be obtained.

(2) We performed a series of measurements at Pt electrodes with the hope of decoupling electrode and film contributions from the EIS spectra. Surprisingly, the frequency-dependent impedance data for Pt electrodes coated with a surfactant-templated film were nearly identical to those observed for bare Pt electrodes, indicating that the mesoporous film had little effect on the transport of small electrolyte ions to the electrode surface. We performed experiments at different pHs (7, 4, and 2), different ionic strengths (50–250 mM KCl), and with films with different pore sizes (ca. 7, 3, and 2 nm). We observed no reproducible differences in any of these data. We did not observe pore-blocking agents (tetraalkylammonium salts) to inhibit this transport process. However, untemplated (nonporous) silica films dramatically increased film resistance, indicating that our EIS data for the Pt electrodes are reliable.

52750

Quantum Computing Accelerator I/O*C. P. Tigges, N. A. Modine, R. C. Schroeppel, A. Ganti*

In a superposition of quantum states, a bit can be in both the states “0” and “1” at the same time. This feature of the quantum bit, or qubit, has no parallel in classical systems. Currently, quantum computers consisting of 4 to 7 qubits in a “quantum computing register” have been built. Innovative algorithms suited to quantum computing are now beginning to emerge, applicable to sorting and cryptanalysis, and other applications. A framework for overcoming slightly inaccurate quantum gate interactions and for causing quantum states to survive interactions with the surrounding environment is emerging, called quantum error correction. Thus there is the potential for rapid advances in this field.

Although quantum information processing (QIP) can be applied to secure communication links (quantum cryptography) and to crack conventional cryptosystems, the first few applications will likely involve a “quantum computing accelerator” similar to a “floating-point arithmetic accelerator” interfaced to a conventional Von Neumann computer architecture. Sandia seeks to develop a roadmap for solving some of the problems associated with maintaining quantum information, and with getting data into and out of such a “quantum computing accelerator.”

This work focused on “quantum I/O (input/output) technologies” by applying quantum optics on semiconductor nanostructures to leverage Sandia’s expertise in semiconductor microelectronic/photonic fabrication techniques, as well as its expertise in information theory, processing, and algorithms. The work will be guided by understanding of practical requirements of computing and communication architectures. Follow-on work to fabricate and evaluate appropriate experimental nano-/microstructures will be proposed as a result of this work.

This work performed a detailed assessment of QIP developments to plot an appropriate direction for further Sandia work in this area.

The initial stages of this project surveyed recent developments in all of the technologies required to develop practical quantum computers. Current thinking is that scaling nuclear magnetic resonance (NMR) techniques to large numbers of qubits will be difficult. Even though scaling ion traps to large numbers of qubits is feasible in principle,

Sandia seeks to develop a roadmap for solving some of the problems associated with maintaining quantum information, and with getting data into and out of such a “quantum computing accelerator.”

This work focused on “quantum I/O (input/output) technologies” by applying quantum optics on semiconductor nanostructures to leverage Sandia’s expertise in semiconductor microelectronic/photonic fabrication techniques, as well as its expertise in information theory, processing, and algorithms.

maintaining the quantum coherence of large numbers of trapped ions will be difficult. Cavity quantum electrodynamics is a newer experimental arena for quantum computation, and may be especially useful in coupling quantum states stored in different technologies. Since Sandia has great expertise in semiconductor nanostructures, follow-on work will likely focus on evolving the quantum-dot technology and cavity quantum electrodynamics.

The mathematics behind QIP is relatively mature (compared with the quantum device technologies). Algorithms for specific applications (in particular, for cryptanalysis) are well established, but the gulf between the QIP mathematics/algorithms and the engineering of physical devices that can support these computations is wide. This project developed synergy between information theorists and device physicists so that personnel from both communities understand the requirements and constraints associated with practical realizations of these applications.

The “technology roadmap” developed as part of this work identified several areas expected to be fruitful for further Sandia work. These include (1) high-speed, high-power electronics for control of quantum elements, (2) microelectromechanical systems (MEMS) cantilever technology for quantum computer output, (3) photonic lattice technology for controlled qubit couplings, (4) gallium arsenide (GaAs)–based quantum computer technology, (5) improved quantum coding design for quantum error correction, and (6) quantum algorithm development for specific applications of Department of Energy interest.

This project developed synergy between information theorists and device physicists so that personnel from both communities understand the requirements and constraints associated with practical realizations of these applications.

52797

Design and Control of the Magnetic Properties of Nanoparticles

B. A. Simmons

Magnetic spinel ferrite nanoparticles, $M\text{Fe}_2\text{O}_4$ ($M = \text{Mn}, \text{Mg}, \text{Zn}, \text{Co}, \text{Fe}$, etc.), offer great opportunities in the technological application of magnetic nanoparticles for the national security missions that Sandia has undertaken. Microfluidics has great potential in separation of radioactive materials and biological agents. Rapid and reliable detection of biological agents has also become increasingly urgent in our war against terrorism. Introduction of magnetic nanoparticles into microfluidics provides an additional lever in the process. The magnetic force is relatively easy to manipulate without adding costly instrumentation onto the existing microfluidic circuitry. By introducing magnetic nanoparticles into biodetection agents, the magnetic signal from the nanoparticles can be easily and quickly detected. The biological ligands that respond to specific biological agents used in bioterrorism can be attached to magnetic nanoparticles. When the probing agents find the targets through biological recognition, the magnetic nanoparticles will also congregate around the targets in suspicious samples. The magnetic signals from the nanoparticles then serve a transducer to turn the biological signals into easily detected physical signals. For such applications, the magnetic properties of nanoparticles need to be as strong as possible. Furthermore, the surface chemistry of the nanoparticles has to match the chemistry of the liquid media of microfluidics and/or the recognition requirements of biological probing agents. The spinel ferrite nanoparticulate systems have compositional and structural flexibilities that enable their magnetic properties to be fine-tuned to match the specific requirements of each given application. The surface of spinel ferrite nanoparticles can be chemically modified to match the requirements in the applications of microfluidics and biodetection.

We made direct correlations between the magnetic properties of nanoparticles and the quantum couplings at the atomic level, including electron spin-spin (S-S) and electron spin-orbital angular momentum (L-S) couplings at crystal lattices. Such correlations allow us to design and fine-tune the magnetic properties of spinel ferrite nanoparticles through changing their chemical composition and nanoparticle size. By introducing covalent linkages between molecules and the

Magnetic spinel ferrite nanoparticles, $M\text{Fe}_2\text{O}_4$ ($M = \text{Mn}, \text{Mg}, \text{Zn}, \text{Co}, \text{Fe}$, etc.), offer great opportunities in the technological application of magnetic nanoparticles for the national security missions that Sandia has undertaken. Microfluidics has great potential in separation of radioactive materials and biological agents. Rapid and reliable detection of biological agents has also become increasingly urgent in our war against terrorism.

surface nanoparticles, we modified the surface of nanoparticles with a variety of organic ligands. For instance, we modified the surface of cobalt and manganese ferrite nanoparticles (CoFe_2O_4 , MnFe_2O_4) with benzoic acid and 4-mercaptobenzoic acid. Furthermore, by introducing a link molecule onto the surface of magnetic nanoparticles, we linked large protein such as antibodies of human and chicken immunoglobulin (IgG) onto the nanoparticle surface through covalent peptide bonds. The antibodies on magnetic nanoparticles remain bioactive and still recognize the respected antigens. The results from our surface-chemistry studies surely demonstrate that our specially designed magnetic nanoparticles can be used in microfluids and in detection of biological agents.

The results from our surface-chemistry studies surely demonstrate that our specially designed magnetic nanoparticles can be used in microfluids and in detection of biological agents.

Refereed

Vestal, C. R., and Z. J. Zhang. 2003. Atom transfer radical polymerization synthesis and magnetic characterization of MnFe_2O_4 /polystyrene core/shell nanoparticles. *J. American Chemical Society* **124**:14312–13.

Vestal, C. R., and Z. J. Zhang. 2003. Effects of surface coordination chemistry on the magnetic properties of MnFe_2O_4 spinel ferrite nanoparticles. *J. American Chemical Society* **125**:9828–33.

Vestal, C. R., and Z. J. Zhang. 2003. Normal micelle synthesis and characterization of MgAl_2O_4 spinel nanoparticles. *J. Solid-State Chemistry* **175**:59–62.

Vestal, C. R., and Z. J. Zhang. 2003. Synthesis of CoCrFeO_4 nanoparticles using microemulsion methods and size-dependent studies of their magnetic properties. *Chemistry of Materials* **14**:3817–22.

52825

Aerospace Vehicle Trajectory Optimization System by Primer Vector Methods

A. C. Watts

The global positioning system (GPS) has revolutionized positioning and timing capabilities for both the military and civilian populations. Yet scientists and researchers continue to push the envelope to find new and innovative ways to draw more from GPS signals. The current research is twofold. The first is an investigation of GPS pseudolite-based relative navigation with the goal of achieving position accuracies considerably better than 1.0 m. This portion of the research has application in any environment that requires high position accuracy and/or environments where GPS coverage is insufficient for a variety of reasons. The second is the incorporation of inertial navigation system (INS) measurements into the GPS tracking loops so that signal lock can be maintained in extreme acceleration environments. This portion of the research has applications in rocket-boosted vehicles flown by Sandia, the National Aeronautics and Space Administration (NASA), and the Department of Defense (DoD).

We performed research in GPS pseudolite-based relative navigation, performed in part at the Navigation Systems and Technology Laboratory (NSTL) at NASA's Johnson Space Center.

As a result of this research, we demonstrated that in the absence of cycle slips, pseudolite-based relative navigation can be achieved in real time with an accuracy on the order of 10 cm. Cycle-slip detection and repair remains the key difficulty in fielding a system that works in real time. One potential solution of this problem may be incorporation of additional measurements, such as optical or inertial, to help resolve the cycle slips.

Currently, we are examining the use of star cameras/trackers to perform autonomous deep-space relative navigation. The Deep Space 1 mission is the only deep-space vehicle to date that has performed autonomous navigation. With the advent of larger numbers of smaller and cheaper satellites, we desire to explore methods by which autonomous navigation can be performed in a robust manner.

The global positioning system (GPS) has revolutionized positioning and timing capabilities for both the military and civilian populations. Yet scientists and researchers continue to push the envelope to find new and innovative ways to draw more from GPS signals....This portion of the research has applications in rocket-boosted vehicles flown by Sandia, the National Aeronautics and Space Administration (NASA), and the Department of Defense (DoD).

Refereed

Monda, E. 2003. GPS pseudolite relative navigation. Paper presented at the Astrodynamics Specialist Conference, 18 August, Big Sky, Montana.

52826

Algorithm Development for Smart Antennas

R. J. Franco, J. A. Rohwer, M. T. Oswald, L. H. Marshall, M. A. Forman

Sandia investigated adaptive antennas in conjunction with beam-forming techniques. That is, adaptive antenna methods are typically constrained by the direction of desired signal and the direction(s) of the undesired interferer(s). There is generally little control of the pattern in between. Thus, our effort began with a survey of antenna synthesis techniques to outline their performance and consider possible application in an adaptive antenna configuration. The synthesis techniques reviewed included, but were not necessarily limited to, the Fourier-transform, Woodward-Lawson sampling, Dolph-Chebyshev, iterative sampling, and Schelkunoff polynomial methods. The adaptive algorithm first studied was the normalized least mean square (LMS). It basically creates a basis to produce array-weighting coefficients to produce a maximum in the direction of the desired radiation while generating orthogonal bases using singular value decomposition to control the directions of nulls to suppress undesired radiation.

During the course of the study it became apparent that the pattern synthesis techniques could become quite sensitive to errors in the weighting coefficients. Thus, the effort also considered the impact of the electromagnetic environment upon the derived coefficients. That is, all techniques, standard synthesis or adaptive, generate the required weights to produce the specified radiation pattern; the resulting coverage will be affected by errors in the hardware to generate the coefficients and by the fact that active element impedances will change as the coefficients themselves are modified dynamically. Thus, using the weights, or coefficients, from the output of any synthesis or adaptive technique will not yield the expected null depths in the presence of mutual coupling. As a result, we completed a study of the impact of mutual coupling upon the performance of the LMS algorithm and demonstrated that the coupling must be considered during the generation of the corresponding array-weighting coefficients.

(1) We surveyed radiation pattern synthesis techniques.

(2) We investigated the performance of the LMS Adaptive Algorithm with isotropic and directive element patterns.

(3) We completed a series of simulations for two-, four-, and eight-element linear arrays, contrasting their performance with and without mutual coupling included.

Sandia investigated adaptive antennas in conjunction with beam-forming techniques. That is, adaptive antenna methods are typically constrained by the direction of desired signal and the direction(s) of the undesired interferer(s). There is generally little control of the pattern in between.

Depending on the exact angles of the signal of interest (SOI) and the interferer (INT), we can modify the null depth in the direction of the undesired radiation significantly.

During the course of the study it was apparent that the synthesis techniques could be quite sensitive to errors in the excitation coefficients. Thus, we quantified the impact of the electromagnetic environment by taking the ideal coefficients from the various algorithms assuming dipole radiators and then using a nonradiating network to produce the weights in the Numerical Electromagnetics Code (NEC). In this manner, we characterized the impact of the electromagnetic coupling environment and demonstrated that future adaptive synthesis methods should include mutual coupling to provide a robust solution.

*...we characterized the impact
of the electromagnetic
coupling environment and
demonstrated that future
adaptive synthesis methods
should include mutual
coupling to provide a robust
solution.*

52976

Failure Analysis and Surety Design of Composite Patching Systems

D. C. Hammerand, D. P. Roach

This research deals with scarf repair of composite materials that include both solid laminates and honeycomb sections. The focus of this project is to evaluate the structural performance of defective repairs in severe loading conditions (fatigue loads). To achieve the overall scope of the project, there is a need to investigate the tensile strength and fatigue behavior of bonded external patch repairs of solid laminates. These data will serve as a baseline for evaluating defective repairs. To reach the objectives of this phase of work, Sandia evaluated the performance of bonded external patch repairs of solid laminates using numerical analysis and an experimental program. We performed the numerical analysis on AS4/3501-6 solid laminate composite panels with a [-60, +60, 0]s stacking sequence. We used the commercial finite-element (FE) code ANSYS to perform the numerical analysis that includes modeling each individual layer explicitly and accounting for the differences in material properties between the parent and patch materials. The experimental project consists of fabricating 32 (12 in. x 27 in.) panels to evaluate all parameters necessary to obtain the fatigue strength of defective repairs. We have tested nine panels so far. We tested three panels in direct tension to evaluate the ultimate strength of the panels. We tested three panels with a 1 in. hole drilled in the center to simulate damage caused by tension and then evaluated the residual strength. Three panels were scarf-repaired and tested in tension to evaluate the retained strength. In all tested panels, we performed nondestructive testing (NDT) to examine the conditions of the panels prior to testing. In the destructive tests, we evaluated the stress and the end strain as well as the strains in zones adjacent to the repair patches for each of the tested specimens.

This work focused on destructive evaluation of repairs performed by the industry as well as on developing a project plan for experimental and numerical investigations of repairs of solid laminates. We carried out the destructive evaluation on three repaired honeycomb composite sections. The first section contains two good repair patches that are circular interior and rectangular edge. The second honeycomb section contains a rectangular interior repair that we classified as a bad repair due to simulated defects within the repair patch. The last section

This research deals with scarf repair of composite materials that include both solid laminates and honeycomb sections. The focus of this project is to evaluate the structural performance of defective repairs in severe loading conditions (fatigue loads). To achieve the overall scope of the project, there is a need to investigate the tensile strength and fatigue behavior of bonded external patch repairs of solid laminates.

contains two circular repairs in which one is classified as good repair while the other is bad repair. We focused the destructive evaluation on sectioning the panels into 1 in. strips and performing microscopic analysis of the bond surface of the skin as well as performing flexural tests on the honeycomb strips and direct tensile tests on the skin only. We adopted four-point loading conditions for the flexural test. We recorded the load versus mid-span deflection and monitored the mode of failure. For the direct tensile tests, we recorded load versus strain on both parent and patch materials. We compared the test results of the flexural and tensile tests of the sections containing patches to those of the same test configurations on sections with parent material only. During the testing program, we used a video camera to monitor the failure of the specimens and to record the failure initiation. Based on the testing program and the available data, we found that patch repair increases the overall stiffness of the panel. Also, the connection between the patch and the parent material may be a point of concern.

Further work performed included fabricating 32 (12 in. x 27 in.) panels made of six-ply laminate using the AS4/3501-6 material with an orientation of $[-60, +60, 0]_s$. We conducted direct tension tests on pristine panels, damaged panels (1 in. hole drilled in the center), and good repaired panels. The test results included load versus strains mounted in different areas of each of the tested panels. We also used Rossette strain gages to measure strain in three directions at specified locations.

We developed an FE model based on the commercially available FE code ANSYS to evaluate the performance of scarf repairs as a function of the ply orientation angles and the stacking sequence. The numerical model evaluated the normal tensile stress in the patch and the shear stress at the interface between bonded layers as a function of the ply stacking sequence and orientations. The model assumed perfect bond between the repair ply layers and the parent materials. We used actual material properties for both the parent materials and the patch within the model, taking into consideration the difference in the material properties of the patch and the parent materials resulting from different fabrication processes. Qualitatively, the model results match the collected experimental data. Quantitative validation of the numerical model using experimental data is still in progress.

Refereed

Hamoush, S. 2003. Destructive evaluation of patch repairs of composite structures. *Structural Faults and Repairs 2003* (1–3 July, Commonwealth Institute, London, United Kingdom).

Hamoush, S. 2002. Destructive evaluation of patch repairs of honeycomb composite aircraft sections. *Proc. 2nd FAA CEO Meeting* (24 October, Wichita, Kansas).

52977

Flow Control and Mixing in Microfluidic Devices

A. C. Sun

Sandia is studying flow control and mixing in microfluidic devices. As one means of microfluidic flow control, we considered electroosmosis both to control the liquid flowing through the channels and as a pumping technique. We utilize living radical photopolymerization (LRPP) to produce polymeric microfluidic devices. LRPP allows for excellent control of microchannel geometry and can be used to chemically modify the surfaces of the channels by attaching charged species or other functional groups. This ability allows us to modify the zeta potential of the surface and, in turn, manipulate the electroosmotic flow in the channel. With LRPP, we can also change the dimensions of the channels. With these considerations, we focused on developing a model that takes into account step changes in both zeta potential and cross section.

The completed electroosmotic-flow model predicts velocity profiles in channels with step changes in zeta potential and cross-sectional area. This model uses the Stokes equation for flow and the boundary condition for the electroosmotic slip velocity when the Debye layer is thin. The model assumes fully developed laminar flow and predicts velocity profiles in long channels; however, it is not valid near the step changes of zeta potential or cross-sectional area. The model also takes into consideration an applied pressure drop in the microchannel. By selecting the appropriate channel dimensions, zeta potentials, and applied pressure drop, the velocity profile in a channel can be tailored for the system. An interesting application of the model is the design of systems that produce flat velocity profiles in certain regions of the channel. Flat velocity profiles are useful in reducing dispersion.

To use the electroosmotic-flow model for channel design, we investigated the zeta potential of the base material. The material exhibits a negative zeta potential, resulting from a negative surface charge. We performed experiments to manipulate the concentrations of the ingredients in the monomer forming the base material to produce the maximum magnitude of the zeta potential. Specifically, we varied the acrylic-acid concentration, and the maximum zeta potential occurred at a 1 wt.% concentration. Once we determined the zeta potential of the base material, the next step was to graft

monomers on the surface of the base material to manipulate the zeta potential. The initial graft monomers were PEG and 2-DMAEMA. Both materials significantly changed the zeta potential of the surface. The PEG graft has a neutral zeta potential and DMAEMA has a positive zeta potential. We also plan to graft acrylic acid to produce a negative zeta potential that is different from the negative zeta potential of the base material. We now plan to create microfluidic channels with step changes in zeta potential due to surface grafting. These channels will allow us to compare measured velocity profiles to the electroosmotic-flow-model predictions. Once we verify the electroosmotic-flow model, it will serve as a design tool for future microfluidic channels.

Mixing is typically a slow process on microfluidic devices. We developed porous polymer plugs (PPPs) to disrupt the laminar nature of microfluidic flow, resulting in mixing. We focused on developing a model to predict the concentration profile within the PPP. This model is an advection/dispersion model based on the effective dispersivity of the PPP. With this model, we can predict the mixing effectiveness of a PPP. The next step is the experimental validation of the model. The goal is to relate plug properties such as pore size and number of pores to the effective dispersivity of the PPPs. Once the effective dispersivity is understood, this model will help us to design PPP mixers for future microfluidic systems.

Refereed

Brotherton, C. M., and R. H. Davis. 2003. Electroosmotic flow in channels with step change in zeta potential and cross section. *J. Colloid Interface Science*, accepted.

Other Communications

Brotherton, C. M., and R. H. Davis. 2003. Flow control and mixing in microfluidic devices. Paper presented at the Gordon Research Conference on Microfluidics, 25–29 August, Big Sky, Montana.

53372

Topological Layout for the Optimal Design of Electrostatically Actuated MEMS

J. J. Allen

In recent years, the potential of topology optimization has been studied intensively and successfully applied to the design of microelectromechanical systems (MEMS) structures. The main advantage of this computer-based design optimization methodology is the capability to generate conceptually novel layouts without requiring close-to-optimal initial designs.

Sandia will use the media of MEMS to fully exploit the potential of topology optimization, as well as advance the state of the art of MEMS design. The following aspects of this work are unique from heretofore-published research:

- *Topology optimization has not been used in the context of a full two-way-coupled problem. This work focuses on electrostatic mechanical coupling since this is relevant to the design of MEMS.*

- *The layout of the entire structure is subject to topology optimization. This includes internal structural elements and also the shape of the interface between the electrostatic field and the structure. Of particular interest from a theoretical and also from a design point of view is the generation of this interface, which is flexible throughout the process, therefore avoiding rigid structural boundary topology, as is standard in topology optimization.*

The collaborating parties on this research bring expertise on topology optimization and MEMS design. We will have the unique opportunity to verify numerical results with experimental results, since optimal MEMS structures designed will actually be built and tested. This close work with the device side of MEMS technology will ensure continuity between theoretical numerics and actual performance.

- *Implementation of sensitivity analysis.* We successfully implemented the direct method of sensitivity analysis of an electromechanical system. This involved the computation of all electromechanical derivatives by hand for better efficiency as compared with an automatic differentiator. We also implemented the adjoint method and verified analysis capabilities.

- *Shape optimization.* We performed the shape optimization of a MEMS device using the implemented sensitivities. This work included optimization of an

Sandia will use the media of MEMS to fully exploit the potential of topology optimization, as well as advance the state of the art of MEMS design.... We will have the unique opportunity to verify numerical results with experimental results, since optimal MEMS structures designed will actually be built and tested. This close work with the device side of MEMS technology will ensure continuity between theoretical numerics and actual performance.

electrostatically actuated device coupled with a microfluid pump.

- *Topology investigation of MEMS.* Initial work involved the current state of the art of topology optimization using a fixed boundary for one-way–coupled electrothermalmechanical problems. We also investigated a two-way–coupled electrostatic-mechanical problem.

We integrated the above accomplishments into a software package capable of performing optimization of MEMS devices. In addition, we combined the optimization of electrostatically actuated MEMS devices with reliability analysis and simulated them to improve the reliability of MEMS devices.

53464

Atomic-Scale Scanning-Tunneling Microscopy Measurements of Nucleation and Growth of Ge/Si Alloy Structures

B. S. Swartzentruber

In collaboration with Arizona State University (ASU), Sandia transitioned from building the elevated-temperature scanning-tunneling microscope (STM) to calibrating it and performing initial experiments. We obtained atomic-resolution images at substrate temperatures of 550°C, allowing us to monitor both silicon (Si) and germanium (Ge) deposition in real time during gas-source molecular beam epitaxy (MBE) from disilane and digermane, respectively.

The aim is to apply the atom-tracking STM method to characterize Ge adatom diffusion on the null facets bounding pyramid clusters.

The efforts at ASU transitioned from building the elevated-temperature STM to calibrating it and performing initial experiments. We obtained atomic-resolution images at substrate temperatures of 550°C, allowing us to monitor both Si and Ge deposition in real time during gas-source MBE from disilane and digermane, respectively. By controlling the digermane pressure during growth, we can control the Ge deposition rate in the range of 0.01 to 0.75 monolayers/min. These rates correspond well with those observed by other investigators. Initial Ge growth experiments confirm the well-known Stranski-Krastanov growth mode and identify the size at which Ge pyramid clusters overcome the nucleation barrier. By monitoring the evolution of island sizes during growth, this critical island base width is 11 nm for growth at 550°C at a deposition rate of 0.30 ML/min. We also confirm that Ostwald ripening occurs for these growth conditions. We observe that all pyramid clusters within the STM field of view disappear during the last stages of the experiment. *Ex situ* atomic-force microscopy imaging finds that the pyramid clusters have dissolved into very large dome clusters existing outside of the STM field of view.

In addition to the efforts at ASU, we also performed experiments at Sandia. The aim is to apply the atom-tracking STM method to characterize Ge adatom diffusion on the null facets bounding pyramid clusters. To do so, we began to characterize Ge diffusion on Ge null surfaces formed by growing Ge on Si null substrates. We succeeded in growing

...Sandia transitioned from building the elevated-temperature scanning-tunneling microscope (STM) to calibrating it and performing initial experiments....The aim is to apply the atom-tracking STM method to characterize Ge adatom diffusion on the null facets bounding pyramid clusters.

these surfaces at Sandia in preparation for the atom-tracking experiments.

53465

Micro-/Nanoscale Thermomechanical Manufacturing

A. C. Sun, J. A. Emerson

In the hot-embossing process, a micromachined silicon (Si) master is heated and pressed into a thermoplastic polymer layer atop a Si substrate. The applied heat and force transfer the master pattern in a negative relief replica in the polymer sample, resulting in feature sizes as small as 10 nm. This work investigates the flow of polymer during hot embossing of micrometer- to nanometer-sized features. Experimental and computational work determines the relation between stamp size, process parameters, and resulting feature sizes. The ultimate goals of this work are to develop design rules for manufacturing nanometer-scale devices from advanced organic materials, and to fabricate several working devices with a manufacturing approach derived from these rules.

Work to date includes experiments performed at Georgia Tech and simulations performed at Sandia. Experiments performed to date demonstrated a micro-/nanoimprint manufacturing technique capable of forming electrical interconnects in a polymer bilayer and investigated the influence of processing parameters (load time, load rate, temperature, etc.) on replicated feature fidelity. We showed transfer of master-feature patterns during hot-embossing printing of a conducting polymer-structural polymer bilayer to produce electrically isolated regions of conducting polymer atop a buffer polymer layer. We replicated features from 100 nm to 20 μm in the polymer bilayer.

Investigation of the influence of processing parameters on imprinted feature size and width yielded insight to the path of polymer flow during imprint lithography. Masters with feature heights and widths ranging from 1–5 μm and periodicities of 20 and 30 μm were printed into different polymers at varied temperatures, load times, load rates, and maximum loads. We found that elevated master-feature heights, imprint temperatures, and load rates resulted in taller imprinted features, while wider master features resulted in shorter imprinted features. We found imprinted-feature width to increase with increasing master-feature height and width, temperature, load rate, and load time.

Research at Sandia produced working GOMA models simulating the hot-embossing process. Initial models of purely deforming viscous liquids and elastic solid-elastic solid

This work investigates the flow of polymer during hot embossing of micrometer- to nanometer-sized features.

Experimental and computational work determines the relation between stamp size, process parameters, and resulting feature sizes. The ultimate goals of this work are to develop design rules for manufacturing nanometer-scale devices from advanced organic materials, and to fabricate several working devices with a manufacturing approach derived from these rules.

interactions led to increasingly complex simulations featuring solid-liquid contact, Bingham-plastic material models, and primitive temperature-dependent polymer viscosities. We developed various master-feature geometries and applied them at imprint conditions matching experimental conditions. We have performed simulations only for micrometer-sized features and are yet to suitably represent true material properties. The first modeling results have already aided experimental design. The simulations reveal that the polymer flow may depend on the direction of heat flow during printing; if the indenter is heated, nonuniformities in the polymer may be suppressed. If the polymer is heated, the printing may be less uniform. Georgia Tech has initiated experiments to examine this phenomenon.

Refereed

Rowland, H. D., and W. P. King. 2003. Transport during hot-embossing nanomanufacturing studied via AFM and SEM. *ASME IMECE 2003*, accepted.

Other Communications

Rowland, H. D., and W. P. King. 2003. A direct nanoimprint method for patterning electrically conducting polymer. *Nanoimprint and Nanoprint Technology Conference 2002*, accepted.

53585

Novel Diagnostics for Rarefied Flows in MEMS Applications

C. J. Bourdon, M. A. Gallis, S. P. Kearney

Until recently, the inability to make in situ measurements within microscale devices under rarefied and compressible flow conditions made it impossible to improve and validate computational models of such flows, where the geometric scale can approach the mean-free-path of the gas molecules at ambient conditions. Quantities such as tangential-momentum accommodation coefficients, thermal accommodation coefficients, electric wall-potential effects, and wall-roughness effects have all been either inferred from external bulk-flow measurements, or derived implicitly or explicitly from direct-simulation Monte Carlo (DSMC) or molecular dynamics (MD) simulations, respectively. Estimates of these coefficients and effects can vary as much as 50% for common materials under controlled conditions, and the effect of compressibility is still largely unknown. A more-reliable estimate of these properties is critical to accurate models of wall slip, aerodynamic damping, and micropropulsion, all of which are important to Sandia.

The lack of established techniques for studying microflows under rarefied and compressible conditions has resulted in a dearth of experimental data, and thus a general lack of understanding of this important flow regime. Consequently, there is a need for the development of diagnostic tools for accurate nonintrusive in situ measurements within microdevices. This project focuses on developing a seedless nonintrusive diagnostic technique for deducing velocity information and estimating the tangential-momentum accommodation coefficient within microsystems with dimensions in the range of a few to tens of microns. Sandia focused on an experimental technique called Raman Excitation Plus Laser-Induced Electronic Fluorescence (RELIEF) to accomplish this goal. These experiments will be accompanied by a thorough examination of existing analytical slip models and DSMC simulations of the microchannel flows. We will then compare the experimental results with DSMC computations to judge the performance of current computational models and to provide accurate data on surface-accommodation.

Our major accomplishments include selecting RELIEF as the diagnostic technique for oxygen velocity measurement in microsystems, assembling the RELIEF optical system and laser-beam frequency-monitoring system, analytically

The lack of established techniques for studying microflows under rarefied and compressible conditions has resulted in a dearth of experimental data, and thus a general lack of understanding of this important flow regime. ...This project focuses on developing a seedless nonintrusive diagnostic technique for deducing velocity information and estimating the tangential-momentum accommodation coefficient within microsystems with dimensions in the range of a few to tens of microns.

determining the effect that diffusion has on the RELIEF signal at low pressure, and creating a vacuum chamber for performing low-pressure RELIEF measurements.

RELIEF is a variant of molecular-tagging velocimetry, where a volume of gas molecules is “tagged” by vibrational excitation via stimulated Raman pumping (SRP) and then probed after a known time delay by driving fluorescence processes accessible only from the excited vibrational level. We developed the RELIEF system around existing lasers and intensified camera systems. We assembled the RELIEF system, along with an O₂ CARS (coherent anti-Stokes Raman scattering) system, to monitor the frequency and spatial overlap of the dye and Nd:YAG (neodymium:yttrium aluminum garnet) beams used in the Raman pumping process. We monitored the tunability of the dye laser to 0.05 cm⁻¹ accuracy. We observed the O₂ CARS signal to be significantly Stark-broadened, indicating that we have excellent overlap of the Raman excitation beams and sufficient power in them to drive the SRP process and vibrationally tag a high percentage of the oxygen molecules.

Because RELIEF is a molecular-tagging technique, the diffusive nature of the molecules can seriously degrade the signal quality at low pressures. We verified the magnitude of the diffusivity of oxygen by DSMC simulations and derived an analytical model to aid in the development of an accurate displacement measurement technique. We estimated that velocity data can be gathered at pressures down to 5 Torr with an accuracy of ± 3 m/s. We assembled a small vacuum chamber with accurate pressure-monitoring equipment and an oil-free vacuum pump for performing RELIEF measurements to verify this model.

53586

Geophysical Subsurface Imaging and Interface Identification

G. A. Newman, R. S. Tuminaro, P. B. Bochev, D. M. Day

Geophysical subsurface imaging is recognized as vital for addressing national security challenges faced by the U.S. In energy security, geophysical imaging has been essential in locating oil and gas fields, thus helping to lessen this nation's dependence on foreign oil. It also is a critical technology in the detection and characterization of underground facilities, including hard and deeply buried targets (HDBTs), and subsurface contamination related to Department of Energy waste legacy issues.

Geophysical imaging relies on the mathematical process called inversion. To stabilize the process, a smooth model constraint is typically imposed on the subsurface geophysical properties (conductivity, velocity, density, etc.) such that they are only allowed to vary smoothly. While such constraints can eliminate unrealistic geological models, they come with a price of reduced model resolution, seriously limiting the applicability and relevance of geophysical imaging technologies for national security concerns. Initially, Sandia will emphasize electromagnetic (EM) applications in this project; however, the scope of the proposed methodology is much broader and pertinent to other geophysical applications, medical imaging, and nondestructive evaluation of materials in engineering.

To address this problem, we are implementing a new type of geophysical inversion for interface identification. It will enable the location of underground structures and facilities, oil and gas deposits, and environmental-site characterization at a scale not previously possible. Construction of the interfaces will require new optimization procedures and massively parallel linear (ML) and nonlinear (NOX) solver tools developed under the Accelerated Strategic Computing Initiative (ASCI) program. We will use exact sequences of finite-element (FE) methods to discretize Maxwell's equations. We will extend optimal algebraic multigrid (AMG) solvers to handle variable conductivity and complex coefficient matrices. To obtain reliable and sharp interfaces, we will first use smooth reconstructions of the interface for the initial topology estimate, followed by well-posed parameterization of the surfaces based on interface tracking, fictitious domains, and level-set approaches.

Geophysical subsurface imaging is recognized as vital for addressing national security challenges faced by the U.S. In energy security, geophysical imaging has been essential in locating oil and gas fields....It also is a critical technology in the detection and characterization of underground facilities,...and subsurface contamination....Initially, Sandia will emphasize electromagnetic (EM) applications in this project;....

We developed and incorporated a multigrid linear solver into our EM imaging code that provides smooth topological estimates of geological interfaces using structured meshes. We use this multigrid scheme to invert complex linear systems associated with the forward problem, arising from the time-harmonic Maxwell's equations. Solution to a large geophysical inverse problem typically requires thousands of linear solves. The computational cost of the inversion process is essentially a product of the number of forward solves and the cost per solve. The new multigrid solver has enabled the scalable and efficient solution of the forward problem throughout the frequency range. Recent test data show relative insensitivity to both frequency and mesh resolution in the number of iterations required per linear system. For high-frequency simulations and coarse meshes, the new scheme is competitive with the previous solver technology. However, the real advantages are apparent when comparing run times at low frequencies and for fine meshes; the multigrid solver is 5x to 10x faster.

To sharpen image reconstruction of an interface requires the capability to solve the forward problem on an unstructured mesh, which avoids modeling the interface using a staircase approximation. Such meshes can readily simulate interface problems that involve curved geometries. To accomplish this task we developed a C++ FE library that implements an exact sequence of FE spaces. The importance of these discrete exact sequences for our subsurface geophysical imaging code stems from the nature of the forward problem, Maxwell's equations, which require the precise discretization of the curl operator for fast and efficient solution by multigrid methods. In addition, we modified the software used to supply geophysical information to the finite-difference code to also generate the data structures needed by the FE library.

The new multigrid solver has enabled the scalable and efficient solution of the forward problem throughout the frequency range....For high-frequency simulations and coarse meshes, the new scheme is competitive with the previous solver technology. However, the real advantages are apparent when comparing run times at low frequencies and for fine meshes; the multigrid solver is 5x to 10x faster.

53587

Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer

E. S. Hertel, Jr.

Gas dispersion and plume development in the urban atmosphere has become a topic of increasing significance because of its direct effect on the many people who reside in or near large urban areas. Research studies in this field are concerned with gaining a better understanding of the physical mechanisms involved in plume dispersion and developing more accurate models to predict plume behavior to enhance public safety and health. There are many issues surrounding the topic of gas dispersion that are directly related to public safety and health. First, because cities are becoming more populated, pollution is increasing and threatening the health of the people. Pollutants in the air are not only the result of cars but also of factories producing harmful chemicals that are released to the atmosphere near or within a city. Accidental gas leaks from a chemical laboratory are also possible, and finally, gas releases with the intent to harm, as in biological or chemical warfare (BW/CW).

With the harmful effects of pollution in cities, possible accidental gas leaks, and threats of BW or CW, improved characterizations of near-surface plumes are needed to better address these challenges. In light of these growing concerns, Sandia conducted detailed experiments of near-field plume dispersion through a compact uniform array of cylindrical barrels. We intend that results from the study both benefit the physical understanding of near-field plume behavior in the presence of surface-mounted obstacles and provide information that will aid in the development of models used to predict dispersion in urban environments. To truly understand the physical nature of plume development through an array of surface-mounted obstacles, it would be necessary to analyze many different parameters such as the effects of thermal stability, source height, source geometry, obstacle layout, source location, flow conditions, etc., on the plume.

Results of our research included statistical profiles, distributions, and intermittency factors of the concentration within the array as a function of source configuration and atmospheric stability. The present results indicate a relaxation toward Gaussian behavior along the plume centerline. The rate

With the harmful effects of pollution in cities, possible accidental gas leaks, and threats of BW or CW, improved characterizations of near-surface plumes are needed to better address these challenges....Sandia conducted detailed experiments of near-field plume dispersion through a compact uniform array of cylindrical barrels....results from the study...benefit the physical understanding of near-field plume behavior in the presence of surface-mounted obstacles and...will aid in the development of models used to predict dispersion in urban environments.

of this Gaussian-like behavior depends on atmospheric stability conditions. Plume dispersion through the array appears to be independent of source initial conditions under neutrally stable conditions. We conducted the data analyses for a paper for journal publications tentatively titled, "The Effect of Source Geometry and Atmospheric Stability on Ground-Level Plume Dispersion Through a Compact Barrel Array." Finally, we conducted a detailed analysis of sonic anemometer data to better understand the flow physics within and immediately above the barrel array.

Refereed

Miner, H. M. 2003. Near-surface atmospheric plume dispersion through a compact cylinder array. *J. AMS* 1:1.

Miner, H. M. 2002. Evolution of ground-level scalar concentrations through a compact cylinder array embedded in the atmospheric surface layer. Paper presented at the 2002 ASME International Mechanical Engineering Congress and R&D Expo, New York, New York.

53588

Miniature High-Power RF Components Enabled by Mesoscale Manufacturing

G. L. Benavides, D. J. Brandt, C. D. Nordquist, C. W. Dyck

Weapon systems and communications require smaller, more-compact transmitters for a variety of uses: fusing and guidance radars, radio-frequency (RF) tags, and agile satellite communications. Current methods of making miniature RF components with microelectromechanical systems (MEMS) are sufficient for low- to medium-power applications (low 10s of watts); however, as the amount of power required increases, the scale of the devices also must increase as do the material demands. This points to the need to investigate other manufacturing processes that are capable of handling a wide set of conducting and nonconducting materials with small feature sizes (microns) on miniature (millimeter) parts. Sandia seeks to create a means to manufacture such RF components. The goals for this project are (1) to create sound method(s) for integrating multiple mesomachining processes to enable the low-volume, batch-style manufacture and assembly of mesoscale components, and (2) to illustrate and prove the success of mesomachining process integration, for which we will design, build, and test an RF switch. In this manner, we will achieve our goals for furthering mesomachining processes for the Manufacturing Science and Technology area by having defined product requirements, focus, and deliverables from the Nuclear Weapons Strategic Business Unit. We will leverage three mesomachining processes to manufacture constituent components for this project: (1) microwire electrodischarge machining (EDM), (2) microstereolithography, and (3) precision machining. We will combine the processes into an integrated manufacturing process to provide Sandia with a capability for mesomanufacturing that does not exist anywhere else, which is well suited to fulfill design requirements that cannot be readily satisfied by traditional MEMS approaches. This will further strengthen Sandia's role in microsystem design and production, enabling new, previously impractical designs for electronic and mechanical components.

Work focused on the design and manufacturing process engineering for a high-powered latching relay. The design requirements dictate a mesoscale device with basic design parameters of a 0.36 mm² contact area, two poles, a 1 mm total air-gap distance, and a 3 mm pole-separation distance. We developed a compliant, bi-stable mechanism concept over a

We will combine the processes into an integrated manufacturing process to provide Sandia with a capability for mesomanufacturing that does not exist anywhere else, which is well suited to fulfill design requirements that cannot be readily satisfied by traditional MEMS approaches. This will further strengthen Sandia's role in microsystem design and production, enabling new, previously impractical designs for electronic and mechanical components.

magnetic latching scheme, for which we submitted a technical advance, to achieve latching action and to reduce the overall number of parts required. We pursued two versions of the relay—one with metal contacts, contactor springs, and preload, and the other with a metal-contactor spring structure and plastic package with built-in preload springs. We abandoned the first version after several design iterations and prototypes due to fundamental performance and manufacturability issues. We found the second version to be far superior in terms of performance and manufacturability. We defined a set of processing steps for the batch fabrication of metal parts using wire EDM and a diamond-turning machine. We also defined processing steps for the fabrication of plastic package parts with integral preload springs using micro rapid prototyping (RP) and the batch assembly of metal and plastic subcomponents into a finished set of latching relays. We fabricated a number of prototype metal and RP parts to define the final set of process parameters. We fabricated individual contactor-spring assemblies and working packages with integral springs that demonstrate not only the feasibility but also the great potential that advanced mesomachining has to create components important to national security.

We developed a compliant, bi-stable mechanism concept over a magnetic latching scheme, for which we submitted a technical advance, to achieve latching action and to reduce the overall number of parts required.

53589

Electron- and Proton-Beam Directed-Energy Defense Weapons

M. G. Mazarakis, T. J. Renk, T. R. Lockner

One of the most pressing military concerns for the U. S. Navy in the early 21st century is the emerging threat of high-speed (Mach 2), sea-skimming missiles that are expected to be widely available to opposing naval and shore offensive forces. Terminal defense of high-value aircraft carriers against such sea-skimming missile attack is presently inadequate. Traveling at 700 m/s, the time available from detection to destruction is on the order of 20 s, and terminal maneuvering makes interception particularly difficult close in to the target. A rapid-response, high-lethality, flexible aiming and firing defensive system is essential for continued protection of the U.S. naval fleet, and carrier battle groups, in particular.

Following the terrorist attack and destruction of the Twin Towers in New York City, the need for protection of critical infrastructure and high-value assets for homeland security is a continuing issue. Rapid response is necessary since the threat can be launched near the target or may not be identified until it has come into close proximity to the target. Speed-of-light (lasers) and near-speed-of-light (particle beams) defense systems may be able to fulfill this need.

Presently our combat vehicles do not have any protection against fast-moving smart missiles. The need for such protection will become even more paramount as future enemy forces and terrorists will acquire more and more smart munitions. Therefore, a portable lightweight beam weapon with a speed-of-light response (electron beam) will be the necessary protection for our battlefield troops.

We studied the propagation of the 10 kA 1 GeV proton beam by channel-tracking technique. Numerical simulations and analytical theory work suggest the feasibility of our idea. We studied the soft kill and incapacitation of commercial electronic devices by electron-beam radiation exposure. We measured a minimum dose level. Further studies and experiments are necessary to validate our results and establish dose-rate effects. We evaluated the feasibility of a light electron-beam weapon. It appears to us feasible, and an RF-type electron accelerator could fulfill the task.

We recalculated the beam requirements for the proton-shield approach and identified the parameters and design of a possible proton-accelerator delivery system. Finally, we

Terminal defense of high-value aircraft carriers against...sea-skimming missile attack is presently inadequate. ...Presently our combat vehicles do not have any protection against fast-moving smart missiles. The need for such protection will become even more paramount as future enemy forces and terrorists will acquire more and more smart munitions. Therefore, a portable lightweight beam weapon with a speed-of-light response (electron beam) will be the necessary protection for our battlefield troops.

propose the most possible technology for a 1 GeV 10 kA proton accelerator.

We looked at two particle-beam defense scenarios and the system requirements for them to be effective.

The first scenario utilizes either proton particles of 200–300 MeV in the form of ionic cloud (“proton shield”) for short-range defense, or 1 GeV proton beams for long-range ~ 10 km engagement. In both versions, the proton-particle weapon has a primary objective to detonate the high explosives (HE) on board the missile and a secondary objective to incapacitate the electronic systems.

The second scenario is strictly for short-range (200 m) battlefield defense utilizing ~ 200 MeV electron beams. This system could probably kill or incapacitate the guidance or arming, fuzing, and firing (AF&F) system to prevent final guidance or detonation on the target.

53590

Electrical Conductivity of Metal Alloys

M. P. Desjarlais, T. K. Mattsson

Our knowledge and understanding of material properties at extreme conditions are mostly founded on measurements. Traditional methods for calculating the equation of state (EOS) and electrical conductivity encounter many difficulties in the warm dense matter regime. Recent advances in the field of density-functional theory (DFT) offer a new approach for this class of problems. Fundamental properties of matter, such as the variation of pressure and electrical conductivity with density and temperature, can be calculated without fitting to experimental data. Furthermore, it offers a framework within which the EOS and optical properties can be calculated in a consistent manner. Work according to this principle has already substantially improved the fidelity of Sandia's advanced modeling codes; aluminum (Al) is now described correctly at temperatures and pressures adequate to pulsed-power and high-energy-density research. The success of modeling Al at a new level of accuracy puts focus on the need to describe also more-complex materials in similar detail. Stainless steel (SS) is such a material; the complexity lies in its being an alloy of transition metals, whose electronic structure is fundamentally different from those of simple metals like Al. SS is also of high importance to the design and function of pulsed-power accelerators since it is the material of choice for magnetically insulated transmission lines. We modeled SS from first principles, exploring the phase diagram in regions important to Sandia, as well as calculating the electrical conductivity at these conditions. We made experimental measurements of the conductivity of SS in collaboration with the University of Maryland (UM). The results of these experiments are in very good agreement with the calculated values, further validating the approach.

We determined that the proposed approach of first-principles quantum molecular dynamics (QMD) simulations, coupled with Kubo-Greenwood calculations of the optical conductivity, is viable not only for simple metals like Al, but also for complex alloys such as SS. In addition, we made careful considerations to optimize parameters and system sizes for accuracy and available computational resources. We also developed improved analysis tools in Mathematica, like velocity-velocity correlation functions and calculation of the static structure factor. These Mathematica-based analysis tools

Work according to this principle has already substantially improved the fidelity of Sandia's advanced modeling codes; aluminum (Al) is now described correctly at temperatures and pressures adequate to pulsed-power and high-energy-density research. ...We modeled SS from first principles, exploring the phase diagram in regions important to Sandia, as well as calculating the electrical conductivity at these conditions.

streamline the analysis, making it faster and more reproducible, thus improving reliability. Our calculations to date have resulted in an increased knowledge of the properties of SS at high temperatures. We determined that the critical point of SS is around 9000 K and 1.5 g/cc. A usable EOS for SS was generated at UM by adding Maxwell constructions to a SESAME SS EOS. In addition, calculated direct-current conductivities for solid iron and SS agree very well with available data. We completed conductivity isotherms at 4000 K, 8000 K, 16,000 K, and 30,000 K for SS from twice solid density down to 0.32 g/cc (about 1/24 of solid density). We used the results of the QMD calculations to generate a wide-range conductivity model with the Lee-More-Desjarlais (LMD) algorithms. This new wide-range conductivity model very accurately reproduces the QMD results and extends over a broad range using traditional methods outside the critical area treated by the QMD calculations. Experiments with tamped exploding SS wires were carried out at UM. The electrical conductivities measured in these experiments are in very good agreement with the QMD results, further validating the approach.

53681

Design of Biospecific Surfaces to Control Specific Cellular Responses

S. M. Brozik

Many cell types require adhesion to the extracellular matrix protein fibronectin (FN) to properly function. Upon binding FN, integrin receptors promote cell adhesion/spreading and cluster to form focal adhesions (FAs), which mediate intracellular signaling events. Integrin binding, FA area and shape, and cell shape all impact cell-adhesion strength and signaling. These factors can be influenced directly through mechanical manipulation of the surface on which the cell is grown. The objective of this project is to control cell orientation, adhesion, and signaling by adjusting the topography of the surface on the micro- and nanometer scale. To accomplish this goal, Sandia is using hot-embossing imprint lithography to create microscale and nanoscale grooves and pores on polymer substrates. Since the process is independent of material, various polymers can be used, including chemically treated surfaces. This will enable further control of cell factors. Metrology of the surfaces will include atomic-force microscopy (AFM), stylus profilometry, and scanning-electron microscopy (SEM). Once these surfaces are validated, we will examine osteoblast adhesion, signaling, and differentiation. This novel and robust experimental system will elucidate the individual and combined effects of cell shape and ligand density on adhesion strength, FA formation, and cell signaling. This information is critical for many applications, such as the design of next-generation biomimetic materials and engineered implants that will perform to a higher standard in vivo.

The overall objective of this project is to use micro- and nanoimprint lithography to create textured surfaces that provide optimal surfaces for adhesion and configuration of cells. This work is being conducted in collaboration with Georgia Tech. The proposed work is divided into three phases. The first phase involves using hot-embossing imprint lithography to create microscale features for cell growth. We will evaluate cell morphology and compare it to current methods of creating cellular growth substrates to establish hot-embossing imprint lithography as a rapid-prototyping method. The second phase is to scale down the texturing to nanoscale features since cell structures at the FA sites are on the order of 10 nm. We will evaluate the FA shape, composition, and strength at this point to determine optimal conditions. The final phase is to combine

The objective of this project is to control cell orientation, adhesion, and signaling by adjusting the topography of the surface on the micro- and nanometer scale. To accomplish this goal, Sandia is using hot-embossing imprint lithography to create microscale and nanoscale grooves and pores on polymer substrates....This novel and robust experimental system will elucidate the individual and combined effects of cell shape and ligand density on adhesion strength, FA formation, and cell signaling.

micro- and nanoscale topography of the optimal conditions on a wafer-scale substrate to be used in a high-throughput cell-adhesion analysis system. This will provide an optimized surface topography that can be applied to implanted medical devices.

We tested a reliable biotinylation procedure that covalently links biotin molecules to lysine side groups on human plasma fibronectin (pFN). Western blots confirm the success of this interaction. ELISA (enzyme-linked immunosorbent assay) testing shows that the stock of biotinylated human pFN conjugates with avidin-coated substrates in an efficient manner. We quantified initial adhesion strength to the biotinylated pFN by a centrifugation assay developed in our lab at Georgia Tech. Initial results indicate that cells interact with the biotinylated pFN in a virtually identical manner as compared to unmodified pFN. After fabrication of the alkanethiol self-assembled monolayers, we will micropattern avidin islands of varying diameters (2, 5, 10, and 20 μm) and immobilize specific concentrations of biotinylated pFN to those surfaces. This grants control of the previously mentioned experimental parameters. We will use these ligand-coated surfaces for adhesion, imaging, and signaling experiments. So far, we have collected cell morphology data for a hot-embossed polymer with microscale features. We evaluated cell body, nucleus, and FAs for alignment and shape, and the results matched what would be expected based on previously published methods of creating substrates for cell growth.

Refereed

Charest, J. L., L. E. Bryant, A. Garcia, and W. P. King. 2003. Hot embossing for micropatterned cell substrates. *Langmuir*, submitted.

53682

High-Field Effects of GaN HEMTs

R. J. Shul

Transport measurements are of vital importance to electronic semiconductor devices. While low-field mobility measurements are a routine measurement for evaluating semiconductor materials, high-field measurements have been more problematic and less commonly used. A new technique developed by Arizona State University (ASU) was recently applied to bulk gallium nitride (GaN) and is currently being evaluated for aluminum gallium nitride (AlGaN)/GaN high-electron-mobility transistors (HEMTs). The technique uses specially developed test structures with an etch constriction and high-voltage pulsed measurements. GaN processing capabilities at Sandia aided the methodology developed at ASU for testing and modeling. Now that the new method for high-field transport has been developed, we can evaluate new GaN materials and transistor device structures for their impact on saturated velocity. These measurements can also be correlated to the performance metrics available from transistor characterization. We propose to create structures from bulk GaN and AlGaN/GaN structures with intentional variation of defect density (through cantilever epitaxy), interface roughness, and intentional variations of the transistor structure, and to evaluate the high-field electron velocity of these structures.

We grew AlGaN/GaN heterostructures with a GaN cap on silicon carbide (SiC) at Sandia. We measured these substrates using a hall setup to obtain the mobility in the two-dimensional electron gas (2-DEG). The substrates produced mobilities of 1500 to 1600 cm²/Vs with electron carrier concentrations of 1×10^{13} cm⁻². We then etched mesa structures into these samples using an inductively coupled plasma (ICP) etching system at Sandia. We then sent these samples to ASU to finish the fabrication process. The first set of these devices did not yield due to poor ohmic contacts. We designed a series of experiments to identify the best metallization scheme to reduce the contact resistance. We used a titanium/aluminum/nickel/gold (Ti/Al/Ni/Au) contact; it provided contact resistances that were at least an order of magnitude lower than the previous metal contacts. We fabricated a second set on test structures using the new metallization process. We tested the structures with a pulsed-voltage input and measured the voltage drop across the etched constriction as well as the current through it. Using these measurements, we determined the electron velocity

GaN processing capabilities at Sandia aided the methodology developed at ASU for testing and modeling. Now that the new method for high-field transport has been developed, we can evaluate new GaN materials and transistor device structures for their impact on saturated velocity.

and electric field. These devices demonstrated improved performance over previous devices, but still broke down at relatively low fields (50 kV/cm). This early breakdown was due to inadequately passivating the device surface. We performed a series of experiments to enhance the passivation process. In particular, we performed experiments to determine the effects of using an N^2 -plasma treatment before the growth of the silicon nitride (SiN) passivation film over the device.

Theoretically, the N^2 -plasma would clean the surface and satisfy all the dangling bonds on the GaN surface, which would improve the electrical properties and enhance the velocity-field characteristic. These N^2 -plasma-treated samples performed better at low fields, confirming the hall mobility measurement; however, the samples still behaved oddly at high fields. We now think that the pulse generator currently being used has too long a pulsewidth (200 ns), which is heating the sample during testing, causing lower velocities at high fields. ASU purchased a new pulse generator capable of pulsewidths as low as 20 ns to complete the testing of the velocity-field curve. We will fabricate and test more samples to compare the velocity-field curves of different qualities of material.

54210

Cognitive Models Applied to Human Effectiveness in National Security Environments

A. B. Doser, M. L. Bernard

Augmented reality (AR) technology has become a useful tool in human-machine work organizations. There are many changes that have taken place over the last two decades: computer desktop displays, simulated and animated displays, large room/wall projection displays, multimedia information management, head-mounted displays, and virtual reality (VR) displays. While these developments are useful to human performance, there are many unresolved issues that adversely affect the utility of these tools. The proposed research investigates human factors and psychophysical issues in AR systems as related to task performance. The proposed research has three objectives:

(1) Investigate the performance of human signal detection (HSD) in an AR environment. This will consider multiple and simultaneous changes in sensory information characteristics. The main task is to understand how humans distinguish signal from surrounding noise using an AR system.

(2) Develop quantitative models that can be used to characterize HSD performance in an AR environment. It is assumed that human signal performance is influenced by the quality of signal and contextual knowledge of the task.

(3) Develop a theory to qualify human perceptual control of context actions using existing theories on perceptual and cognitive processes that are now parsed through multiple information integration in a virtual space.

Augmented reality (AR) technology has become a useful tool in human-machine work organizations. There are many changes that have taken place over the last two decades: computer desktop displays, simulated and animated displays, large room/wall projection displays, multimedia information management, head-mounted displays, and virtual reality (VR) displays....The proposed research investigates human factors and psychophysical issues in AR systems as related to task performance.

54211

Nanomagnetic Films

M. W. Jenkins

Recent advances in chemical synthesis allow the fabrication of molecular nanomagnets. Micro- and nanodevices that could be enabled by nanomagnets will require a reproducible process for creating thin films. The instability of these nanomagnets at high temperatures precludes the use of many established thermal techniques for depositing thin films. Sandia is collaborating with Texas A&M University to develop nonthermal laser techniques for the deposition of thin films of the molecular magnet manganese(II)-acetate (Mn(II)). Pulsed-laser deposition (PLD) involves hitting a pellet of Mn(II) with a short laser pulse, causing the material to be sent out in a spray that deposits on a substrate. Another technique involves dissolving the Mn(II) in a solvent and freezing the solution. This solution is then hit with a laser pulse. This method allows the solvent to absorb most of the laser energy, helping to maintain the integrity of the Mn(II) molecules. The characterization of initial films shows encouraging results. If these techniques prove successful, the ability to deposit and pattern thin films of molecular magnets can lead to an enhanced understanding of quantum magnetism and advances in areas like magnetic storage and quantum computing.

Many standard film-deposition techniques involve thermal evaporation of the film material. The thermal instability of Mn(II) molecular magnets makes these techniques impractical for making films. We worked on the development of other techniques for the deposition of thin films of Mn(II). One technique used is PLD. This technique involves making a compressed pellet of the Mn(II) powder and ablating it with a laser. We used two laser systems: a nitrogen laser, with energy around 2 mJ, and an excimer laser, with energies ranging from 200 to 400 mJ. The purpose of using two different systems is to determine the optimum laser energy, pulsewidth, pulse frequency, etc., for the creation of high-quality films that maintain the molecular and magnetic properties of the starting material. The deposited films are characterized using x-ray photoelectron spectroscopy (XPS), superconducting quantum interference device (SQUID) magnetometry, electron-spray ionization mass spectrometry (ESI-MS), and atomic-force microscopy (AFM). We use XPS and ESI-MS to compare the chemical makeup of the deposited films to that of the starting material. The SQUID measurement allows comparison of the

Sandia is collaborating with Texas A&M University to develop nonthermal laser techniques for the deposition of thin films of the molecular magnet manganese(II)-acetate (Mn(II))....The characterization of initial films shows encouraging results. If these techniques prove successful, the ability to deposit and pattern thin films of molecular magnets can lead to an enhanced understanding of quantum magnetism and advances in areas like magnetic storage and quantum computing.

magnetic properties of the films to that of the starting material. We use AFM to determine the roughness and homogeneity of the films. Results to date indicate that the lower energy of the nitrogen laser yields better-quality films with less fragmentation of the Mn12 molecules.

Another technique for depositing the films, which we will explore next, is Matrix-Assisted Pulsed-Laser Evaporation (MAPLE). MAPLE is a technique in which the Mn12 is dissolved in a solvent and the solution is frozen. This frozen solution acts as the target for the laser ablation. The advantage of this technique is that the solution absorbs most of the energy of the laser pulse, leaving the Mn12 molecules intact. Dissolving the Mn12 also allows the molecules to break down into small clusters, or even single molecules, leading to smoother, more-uniform films. In preparation for depositing films using MAPLE, we worked on determining the properties of the Mn12 molecules in solution. We used dynamic light scattering (DLS) to determine the size of clusters present in a solution (or dispersion) of Mn12 in acetonitrile. We also used ESI-MS to confirm that the Mn12 molecules stay intact in the acetonitrile.

While most of the research being conducted is focused on PLD and MAPLE, we are also exploring other methods of depositing and patterning films. A simple technique of dipping a silicon substrate into a solution of Mn12 yields very thin films with high smoothness. We are also exploring a method of using an AFM tip to write patterns (known as the *dip-pen method*) for patterning Mn12 structures.

Refereed

Means, J. L., *et al.* 2003. Films of molecular magnets deposited by low-energy laser ablation. To be submitted.

Other Communications

Means, J. L., *et al.* 2003. Pulsed laser deposition of Mn₁₂ acetate films using a low-energy nitrogen laser. Paper to be presented at the March 2004 Meeting of the American Physical Society, 22–26 March 2004, Montreal, Canada.

Seo, D., *et al.* 2004. Thin films of Mn₁₂ molecular magnets by the dip-and-dry method. Paper to be presented at the March 2004 Meeting of the American Physical Society, 22–26 March 2004, Montreal, Canada.

Viswanathan, M., *et al.* 2003. Films of Mn₁₂ acetate by pulsed-laser evaporation. Paper to be presented at the March 2004 Meeting of the American Physical Society, 22–26 March 2004, Montreal, Canada.

Viswanathan, M., *et al.* 2003. Magnetic properties of Mn₁₂ acetate films: Evidence for cluster glassy magnets. Paper to be presented at the March 2004 Meeting of the American Physical Society, 22–26 March 2004, Montreal, Canada.

54213

A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites

J. W. Foulk, III

Carbon nanotubes (CNTs) are extremely small structures, only a few atoms in circumference and up to 100 nm in length. Physically, they can be viewed as single crystals in one direction having a unit cell that repetitively propagates with the symmetry of a helix. Like their predecessor, the buckyball, CNTs consist of C atoms bound by strong covalent bonds. CNTs are also considered giant linear fullerenes, or closed convex cage molecules containing only hexagonal and pentagonal faces that form a network analogous to a macroscopic beam and truss structure.

One of the promised advantages of CNTs lies in their ability to support large loads under tension. The minuscule diameter of a nanotube leaves almost no room for the numerous imperfections or microcrevices that plague many standard engineering materials. Thus, CNTs can undergo relatively large deformations with no visible signs of fracture. However, while CNTs can be produced in the lab, performing experiments on individual nanotubes has proven quite difficult. As such, experiments have focused on bundles of nanotubes while studies of the response of individual nanotubes have been resigned to computational techniques.

Although numerical methods have progressed dramatically, modeling a molecule containing thousands of atoms using first-principles remains computationally expensive. Classical molecular dynamics (MD) approaches of specifying interatomic forces also remain limited by the number of atoms.

Micromechanics techniques wherein effective nanotube properties are used to obtain effective composite properties in a self-consistent manner have been applied for several test cases, indicating the effects of various volume-fraction contents of nanotubes on the composite properties. Composite properties have also been obtained through the application of a three-phase composite-cylinders technique and compare favorably with the aforementioned self-consistent approach. In addition, the effects of clustering have been incorporated and show significant impact to the transverse-to-fiber direction properties at lower global volume fraction of fibers in the matrix.

We used a composite-cylinders approach using a variety of different-sized single- and multiwalled nanotubes to obtain the effective properties of CNTs, thereby allowing the hollow

Carbon nanotubes (CNTs) are extremely small structures, only a few atoms in circumference and up to 100 nm in length....One of the promised advantages of CNTs lies in their ability to support large loads under tension.

isotropic nanotube to be treated as a solid transversely isotropic fiber. The effective fiber is then introduced on the composite level using both self-consistent and Mori-Tanaka methods for a wide variety of nanotube volume fractions to obtain effective composite properties for aligned fiber and randomly oriented fiber composites.

We also obtained composite properties through the application of a three-phase composite-cylinders technique where the composite cylinder consists of the zero-stiffness hollow phase, the rolled-graphite phase, and the surrounding polymer-matrix phase. We calculated elasticity solutions and used them to obtain the effective properties; they compare favorably with the aforementioned self-consistent approach.

Finally, we incorporated the effects of clustering into the aforementioned self-consistent approach; they show significant impact to the transverse-to-fiber direction properties at lower global volume fraction of fibers in the matrix.

...we incorporated the effects of clustering into the aforementioned self-consistent approach; they show significant impact to the transverse-to-fiber direction properties at lower global volume fraction of fibers in the matrix.

Other Communications

Oh, E. S., A. P. Awasthi, G. D. Seidel, D. C. Lagoudas, and J. C. Slattery. 2003. Elastic properties of single-wall carbon nanotubes: Transitioning atomic to continuum scales. Paper presented at ICCES, 24–29 July, Corfu, Greece.

57300

Integrated Superhard and Metallic Coatings for MEMS

M. P. De Boer

Sandia seeks to integrate new materials (in particular as thin films) into polysilicon (poly-Si)-based microfabrication technology. Specifically, we will pursue two classes of new materials: superhard materials and metals. We are making a special effort to develop processes that integrate materials at the microstructure release step, because such processes would afford a wider class of materials and a greater degree of flexibility to device engineers. Consequently, processes will have to allow conformal deposition.

We will choose superhard materials with the following properties: wear resistance, hydrophobicity, lubricity, and chemical and thermal inertness. Our initial efforts will focus on developing a process to coat poly-Si micromachines with a conformal layer of silicon carbide (SiC)—a tough, radiation-hard, corrosion-resistant material, second only to diamond in wear resistance. Furthermore, in contrast to self-assembled monolayers (SAMs), which do not withstand temperatures employed in packaging technologies, SiC is expected to be much more thermally stable. We will explore the use of C60 and its interaction with Si to realize a thin conformal SiC layer. We predict that carbon nitride theoretically is even harder. We will explore ways of integrating it into micromechanical structures.

Integration of metals offers special opportunities for realizing devices such as micorelays. Standard metal-deposition techniques suffer from being line-of-sight. One way of circumventing this problem is to use electroless plating techniques, based on coating the structures with a self-assembled organic monolayer with a special end-group functionality that catalyzes the growth of a continuous metallic layer from solution.

In the aforementioned coating processes, little is known about the tribological properties of the resulting materials in thin-film forms. Therefore, we will also characterize these films using surface analytical techniques in our laboratory and specially designed test microstructures. Metal surfaces may be hydrophilic, and hence, additional surface modification may be necessary to alleviate stiction.

This work expanded the structural materials base for surface micromachining. It also developed a selective deposition method of metals onto poly-Si surfaces.

Sandia seeks to integrate new materials (in particular as thin films) into polysilicon (poly-Si)-based microfabrication technology. Specifically, we will pursue two classes of new materials: superhard materials and metals. We are making a special effort to develop processes that integrate materials at the microstructure release step, because such processes would afford a wider class of materials and a greater degree of flexibility to device engineers. Consequently, processes will have to allow conformal deposition.

Although poly-Si is an excellent material for room-temperature applications in microelectromechanical systems (MEMS), it is not stable at temperatures above 500°C. This research funding enabled groundbreaking research in establishing SiC, which should be stable up to 1400°C, as a potential candidate for MEMS. In addition, SiC is radiation hard and possesses surfaces that are physicochemically very stable, in particular in oxidizing environments (where diamond, or diamondlike carbon [DLC], is volatile). For these reasons, we prefer SiC for operations involving harsh environments (e.g., corrosive, abrasive, high temperatures, high electric fields, high radiation levels). Previously, SiC could be deposited only at 1200°C. With the present work, SiC can be deposited at 700°C. This makes it much more compatible with complementary metallic oxide semiconductors (CMOSs), and makes processing significantly easier. Previously, SiC could not be selectively etched with respect to silicon dioxide (SiO₂) or silicon nitride (SiN), common masking materials. In this work, we developed a new gas chemistry that etches SiC with high selectivity to silicon oxide (SiO). We also measured the expected value of SiC modulus (four times that of Si). Therefore, besides harsh-environment operation, we can achieve higher-frequency resonators, important in radio-frequency applications.

This work also shows that metals can be galvanically deposited as surface coatings in poly-Si MEMS after they are released. This is important because poly-Si is not an optically reflective material and because its electrical resistance is high. The materials, such as gold, copper, and rhodium, that are deposited by this method are optically reflective and much more conductive. The galvanic process is compatible with any poly-Si surface-micromachined design. It does not require a special shadow mask that is usually used in the more-common post-processing approaches. We also coated the metals with hydrophobic monolayers so that they are adhesion-resistant.

Although poly-Si is an excellent material for room-temperature applications in microelectromechanical systems (MEMS), it is not stable at temperatures above 500°C. This research funding enabled groundbreaking research in establishing SiC, which should be stable up to 1400°C, as a potential candidate for MEMS.

Refereed

Gao, D., M. B. J. Wijesundara, C. Carraro, R. T. Howe, and R. Maboudian. 2003. High modulus poly-SiC technology for RF MEMS. *Proc. 12th International Conference on Solid-State Sensors and Actuators, Transducers '03* 2 (June, Boston, Massachusetts): 1160.

Gao, D., M. B. J. Wijesundara, R. T. Howe, and R. Maboudian. 2003. Characterization of residual strain in SiC films deposited using 1,3-disilabutane for MEMS application. *J. Microfabrication, Microlithography and Microsystem*, accepted.

Gao, D., R. T. Howe, and R. Maboudian. 2003. High-selectivity etching of 3C-SiC films using HBr-based transformer-coupled plasmas. *Applied Physics Letters* 82:1742–44.

Magagnin, L., C. Carraro, and R. Maboudian. 2003. Adhesion evaluation of immersion plating copper films on silicon by microindentation measurements. *Thin Solid Films* 434:100–5.

Valente, G., C. Stoldt, C. Carraro, and R. Maboudian. 2003. Theoretical and experimental study of the chemisorption of 1,3-disilabutane on the Si(100) surface. *J. Chemical Physics* 118:6089–97.

Wijesundara, M. B. J., C. R. Stoldt, C. Carraro, R. T. Howe, and R. Maboudian. 2003. Nitrogen doping of 3C-SiC films grown by single-source chemical vapor deposition. *J. Thin Solid Films* 419:69–75.

57307

Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials

D. L. Lindner

In this project, Sandia is evaluating and developing methods and materials for performing microscale liquid-phase separations of biological compounds. The research and development are being performed in collaboration with the University of Montana. We are developing methods to analyze compounds of biological significance using specialized chromatographic materials known as pseudostationary phases. These materials are easily introduced into microfabricated channels, enable high-performance chemical separations, and provide a high degree of chemical diversity. The results of these studies will support a number of Sandia efforts in microscale separations and analysis. The development and implementation of new separation methodologies and materials is central to the detection and identification of biomolecules that indicate the presence and identity of biological warfare agents (BWAs) and agents of bioterrorism, as well as for the detection and identification of chemical toxins, chemical warfare agents (CWAs), and explosives.

As pseudostationary phases for electrokinetic chromatography (EKC), amphiphilic polyelectrolytes like those being developed in this project have been shown to provide significant advantages over conventional micellar pseudostationary phases. These novel polymeric phases may play an important role in the development of miniaturized instruments for the selective determination of a variety of chemical compounds of interest to the Department of Energy and Department of Defense. The current studies develop the application of these materials to the analysis of specific target biomolecules and classes of biomolecules, as well as continue to develop novel polymeric materials with potentially improved performance, selectivity, and commercial viability.

We developed optimized methods for the separation of naphthalene-2,3-dicarboxaldehyde (NDA) derivatized amino acids using two polymers. One of the polymers has an acrylamide backbone, while the other has a siloxane backbone. The polymers provided efficient and selective separations. We transferred and optimized these methods with laser-induced fluorescence (LiF) detection. The two polymers performed well with LiF detection, and we obtained excellent separations.

We are developing methods to analyze compounds of biological significance using specialized chromatographic materials known as pseudostationary phases....The development and implementation of new separation methodologies and materials is central to the detection and identification of biomolecules that indicate the presence and identity of biological warfare agents (BWAs) and agents of bioterrorism, as well as for the detection and identification of chemical toxins, chemical warfare agents (CWAs), and explosives.

Peptides proved more difficult to separate using the polymers. In general, the separations generated with the polymeric phases were of lower efficiency and selectivity relative to those obtained with micellar phases. We investigated several series of peptides to determine the reason for the limited performance. We observed no general trend in performance with respect to peptide structure, although all peptides with molecular weight in excess of 1000 g/mol gave relatively poor results.

We characterized the separation of derivatized amino acids with respect to selectivity and sensitivity. The separation selectivity of amino acids is significantly different from that observed with conventional micelles or conventional chromatography. The two polymers show some differences in selectivity. For example, threonine and serine are not resolved with the siloxane polymer, but are well resolved with the acrylamide polymer, while isoleucine and leucine could be resolved only with the siloxane phase. Tyrosine, a more-polar amino acid, migrates after methionine and valine with the acrylamide polymer but before methionine and valine on the siloxane phase.

Sensitivity in the ultraviolet absorbance mode is comparable to that obtained with conventional micelles. Sensitivity with fluorescence detection is excellent, but is not as good as capillary electrochromatography (CEC) due to relatively high background levels. We derivatized amino acids at 4.3×10^{-8} M with signal-to-noise ratios of 45 and 30, and detection limits of 3 nM and 4 nM with the siloxane and acrylamide polymers, respectively. It is not clear whether the background signal, which was 50% greater with the acrylamide polymer than with the siloxane polymer, is due to scattering or fluorescence of impurities in the polymers.

We characterized the performance and limitations of the polymeric phases for the separation of biological macromolecules. Polymeric phases may be limited for application to the separation of peptides of higher molecular weight (> 1000 daltons). These peptides are separated with poor efficiency and poor selectivity. This may be due to the relatively cohesive nature of the polymeric phases. We are currently attempting to characterize this behavior.

We will develop conditions for the synthesis of carbohydrate-based polymers with systematic variations in structure using a model structure, poly(dimethylene galactaramide).

We developed polymerization conditions, and the polymerization was successful. Modifying the backbone with

glutaric anhydride to produce an anionic polymer appears to be successful, but satisfactory purification methods still need to be developed. Recent results indicate that there may be cross-linking between the polymer chains during modification with the glutaric anhydride. To minimize cross-linking, we are now investigating the modification of the polymer using lower concentrations of reagents in 1-methyl-2-pyrrolidinone.

We also are exploring an alternative approach to the addition of ionic pendant groups. We modified both poly(dimethylene glucaramide) and poly(hexamethylene glucaramide) with chloroacetic acid to yield the carboxymethyl derivatives. There is no chance of cross-linking in this case, and the resulting polymers are water-soluble.

We plan to characterize the model polymer for use as a pseudostationary phase in EKC.

We have not yet employed the model polymer due to problems with purification and solubility. We believe that both problems are related to cross-linking of polymer chains during the modification reaction. We are currently addressing this problem and will develop novel polymer chemistries in upcoming work.

Refereed

Palmer, C. P., S. M. Schulte, and R. Loflin. 2003.

Development and application of polymeric pseudo-phases for electrokinetic chromatography.

Paper presented at the 58th Northwest Regional ACS Meeting, June, Bozeman, Montana.

57308

Friction in Micromachine Interfaces

B. R. Antoun

Understanding and controlling friction in micromachine interfaces is critical to the reliability and operational efficiency of most miniature microdynamic systems. The very high adhesion (friction) forces, compared to the restoring forces of such small devices, often present major obstacles in the design of reliable microelectromechanical systems (MEMS). Using surface micromachining, Sandia will fabricate arrays of microstructures for friction testing and test them using a multiprobe high-vacuum station. We also will emphasize the control and actuation of the friction devices, as well as the modeling of the dynamic response and the mechanics involved at the contact interface. Specifically, the ultimate goal of this research is to fabricate and test resonators (active microstructures) and microcantilevers (passive microstructures) to obtain insight into the effect of surface topography, material properties, surface chemical state, environment, and contact loading on the static and dynamic friction behaviors.

This research is part of critical work needed to understand microscale friction mechanics to meet the rapidly evolving needs of design, performance assessment, and qualification of microcomponents. The Department of Energy's weapon component groups are becoming increasingly interested in microsystem design alternatives for many subsystems such as stronglinks, fuses, and environmental-sensing devices. In many cases, the small size of the microcomponent enables enhanced functionality compared to its macro counterpart, and the associated reduction in volume enables the inclusion of additional safety and telemetry devices in the weapon system.

We developed a first-generation MEMS friction-testing device. We designed this device to yield results in both static and dynamic friction in sidewall contact of MEMS interfaces. Based on the results gained from this device, the MEMSCAP foundry designed and is currently fabricating a second-generation device. This Generation II design is far advanced from the Generation I design and includes several different devices for studying the interfacial behavior of MEMS devices under static and dynamic conditions.

The Generation II design includes three main classes of devices. The first type includes various friction-testing structures that can be used to study friction in both sidewall

Using surface micromachining, Sandia will fabricate arrays of microstructures for friction testing and test them using a multiprobe high-vacuum station...the ultimate goal of this research is to fabricate and test resonators (active microstructures) and microcantilevers (passive microstructures) to obtain insight into the effect of surface topography, material properties, surface chemical state, environment, and contact loading on the static and dynamic friction behaviors.

contact and horizontal contact. The second type includes several stiction-testing devices. Stiction is a phenomenon prevalent in MEMS devices in which mechanical restoring forces are insufficient to overcome surface adhesive forces at contacting interfaces. The final type is a release device that is used to test a design method for releasing adhered structures.

57309

Lipid Microarray Biosensor for Biotxin Detection

D. L. Lindner

Lipids and membrane proteins present in the membranes of neuronal and other human cells are natural receptors for a number of bacterial toxins and viruses whose sensitive detection is of interest in biological warfare or terrorism incidents as well as in clinical medicine. Artificial lipid bilayers, supported on a sensor surface, that contain the receptor lipids (or membrane proteins) mimic cells that are invaded by these bacterial toxins and viruses and, hence, can be used as sensitive probes for detecting them. Sandia seeks to develop microarrays of supported lipid bilayers, with each element containing receptors for a different pathogenic agent, for simultaneous detection of multiple biological toxins and viruses. We will pattern lipid arrays on a substrate such as glass or silicon (Si) using a novel polymer-based dry lift-off technique that is suitable for patterning of biological molecules. Conventional liftoff involves removal of photoresist layers by organic solvents and, hence, is not very suitable for chemically sensitive or biological materials. Our dry lift-off technique uses a conformal Parylene layer, which is a pinhole-free vapor-phase-deposited inert polymer. The biosensor consists of a Si or glass microchip on which arrays of lipids containing receptors have been deposited using photolithographic patterning, followed by vesicle fusion and a dry liftoff. We expose the chip to samples containing toxins, and transduce the binding of toxin to the receptor into a fluorescence signal using a secondary fluorophore-labeled antibody in a "sandwich" assay or employing a fluorophore-labeled toxin in a competitive assay followed by detection with a charge-coupled device (CCD).

Our accomplishments include successful microfabrication of Si chips, successful formation of receptor-populated lipid domains and binding of tetanus C and cholera B toxins, detection of toxin concentration down to 10 nM concentration, evaluation of nonspecific binding to lipid domains and bare Si surface, and initial trials of design of a microfluidic network for loading multiple lipid compositions in one chip.

- *Microfabrication of Si chips.* We achieved the fabrication of polymer-coated Si chips with exposed areas of the Si substrate with sizes in the 1–50 mm range. The fabrication of the Si chips made use of polymer coating in conjunction with standard photolithography techniques. We

Sandia seeks to develop microarrays of supported lipid bilayers...for simultaneous detection of multiple biological toxins and viruses....Our accomplishments include successful microfabrication of Si chips, successful formation of receptor-populated lipid domains and binding of tetanus C and cholera B toxins, detection of toxin concentration down to 10 nM concentration, evaluation of nonspecific binding to lipid domains and bare Si surface, and initial trials of design of a microfluidic network for loading multiple lipid compositions in one chip.

coated whole Si wafers with polymer by vapor deposition. Subsequently, we patterned the polymer by photolithography and reactive-ion etching (RIE). We used the resulting patterns of exposed Si substrate for the selective deposition of the lipids containing the ganglioside receptors.

- *Characterization of patterned lipids.* We incubated and successfully bound vesicles of lipids containing ganglioside receptors to the Si substrate in the areas left exposed by the etched polymer. We imaged the deposited lipids by epifluorescence and showed that lipid domain formation is achieved in all exposed areas. We observed lipid domains in all feature sizes and noted no significant spreading after removal of the polymer coating. The deposited lipids and gangliosides are functional, as shown by the effective toxin binding. Nevertheless, it is not certain that the deposited lipids have formed supported lipid bilayers. Modification of lipid composition could lead to formation of supported lipid bilayers. Further characterization of the deposited lipids by atomic-force microscopy (AFM) could reveal if they have formed bilayers or just deposited as bound vesicles.

- *Binding and detection of toxins.* After patterning the lipids, we incubated the chips with different concentrations of the toxins specific to the ganglioside receptors. The polymer could be lifted off before or after the incubation with the toxins. Polymer liftoff prior to protein incubation allowed us to identify that the proteins bound specifically to their receptors and only bound weakly to the bare Si substrate. Nevertheless, polymer liftoff after incubation with the proteins provided lower background fluorescence and better limit of detection. Therefore, for the calculation of the lowest concentration detectable, we removed the polymer after incubation with the toxin. We performed detection by epifluorescence using an upright microscope with water-immersion objectives and a CCD camera. The lowest concentrations detected to date for tetanus C and cholera B toxin fragments is 0.5 mg/mL (ca. 10 nM). The detection of lower concentrations could be possible with the use of a more-sensitive camera or by other microscopy techniques.

57310

Advanced Manufacturing Techniques Using Rapid Prototyping

M. L. Griffith

The focus in this project was the use of the three-dimensional (3-D) Systems Viper si2 stereolithography apparatus (SLA) rapid-prototyping (RP) machine for direct manufacturing of mesoscale parts (with features on the order of microns to millimeters) in a variety of applications of interest to Sandia. These include microfluidic components and mesoscale, discrete electrical components such as switches and coils. Capability to produce this class of devices expands Sandia's ability to develop chemical/biological sensors and other miniaturized national security products. This research seeks to explore micropart manufacturability and to develop a design guide for micromanufacturing using the high-resolution capabilities of the 3-D System Viper si2 SLA RP machine.

The Viper si2 SLA machine incorporates a high-resolution build mode with a 75 μm (3 mil) beam diameter and 50 μm (2 mil) build layer thickness. Using these specifications, the University of Texas at El Paso successfully manufactured, on a limited basis, microholes with diameters on the order of 50 μm and embedded microchannels with cross-sectional lengths on the order of 100 μm . Negative features are limited, in part, by the Viper si2 beam control, and positive features are limited by the laser-beam diameter and layer thickness.

We demonstrated the micromanufacturing capabilities of the Viper si2 SLA machine in several applications. We limited the applications to single layers for successful 50 μm -diameter hole fabrication and simple geometries with sufficient access for post-cleaning for successful embedded channel and microswitch fabrication.

We investigated SLA-based fabrication approaches on a variety of mesoscale components. These devices included a fuel-cell manifold, a mold for a retinal-implant frame, two styles of evolution arrays for chemical/biological materials, a mesoscale latching relay, and an electromicrofluidic package.

The focus in this project was the use of the three-dimensional (3-D) Systems Viper si2 stereolithography apparatus (SLA) rapid-prototyping (RP) machine for direct manufacturing of mesoscale parts (with features on the order of microns to millimeters) in a variety of applications of interest to Sandia....Capability to produce this class of devices expands Sandia's ability to develop chemical/biological sensors and other miniaturized national security products.

57311

Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems

A. D. Oliver, J. S. Custer, L. E. S. Rohwer, B. H. Stark

Sandia developed new technologies for low-temperature microelectromechanical systems (MEMS) packaging. We developed a technique based on a thin film of electroplated nickel (Ni) to vacuum/hermetically seal MEMS on the wafer level with a minimum of wasted die area. We also developed a technique to seal large ($\sim 10\ \mu\text{m}$) fluidic access channels with deposited lead-free solders. We apply the solders to the wafer with a special defluxing process that enables MEMS and solder compatibility on the same die. This technique could enable MEMS devices and integrated circuits (ICs) to be sealed together.

To characterize the package, we developed a new type of thermal-pressure sensor that utilizes the thermal conductivity of gas to determine vacuum levels. This sensor can measure pressures as low as 1 mTorr with a rated accuracy of $3\ \mu\text{Torr}$. This allows us to measure leak rates as low as $1\text{E-}17\ \text{cm}^3/\text{s}$. With these sensors, we monitored a package sealed at 1 Torr for 70 days with no detectable increase in pressure.

We developed a packaging technology that employs a thick Ni film to vacuum-seal a MEMS structure at the wafer level. We fabricated the package in a three-mask process by electroplating a $40\ \mu\text{m}$ -thick Ni film over an $8\ \mu\text{m}$ sacrificial photoresist layer that is removed prior to package sealing. The large fluidic access port enables an $800 \times 800\ \mu\text{m}$ package to be released in less than 3 hrs. For sealing the fluidic access port, we investigated several mechanisms based on localized melting and solder bumping. This package was fabricated with an integrated Pirani gauge to further characterize the different sealing technologies. We used these gauges to establish the hermeticity of the different sealing technologies and measured a sealing pressure of $\sim 1\ \text{Torr}$.

The integrated Pirani gauge that we developed is crucial to package characterization. The fabrication of surface-micromachined Pirani gauges is complicated by the need for precise stress control to prevent thermal shorting to the substrate. Our work differs from previous Pirani gauges in that we utilize a novel doubly anchored structure that stiffens the structural membrane while not substantially degrading performance to measure fine leak rates. Due to a low-mask-

Sandia developed new technologies for low-temperature microelectromechanical systems (MEMS) packaging. ...We also developed a technique to seal large ($\sim 10\ \mu\text{m}$) fluidic access channels with deposited lead-free solders....This technique could enable MEMS devices and integrated circuits (ICs) to be sealed together.

count, low-profile device, this test can be conducted cheaply without substantial modifications to the package design.

We also demonstrated a technique to premold and transfer lead-free solder balls for MEMS/electronics packaging applications. We used a reusable bulk-micromachined silicon wafer to mold solder pastes and remove excess flux prior to transfer to a host wafer. The solder molding and transfer process allows defluxing and outgassing of the solder paste, enabling vacuum-capable solders and MEMS to be fabricated on the same die. We used this technique to fabricate micromachined thin-film vacuum packages. We demonstrated long-term (~ 3 months) reliability of these packages through integrated Pirani gauges.

Refereed

Stark, B. H., and K. Najafi. 2003. An integrated process for post-packaging release and vacuum-sealing of electroplated nickel packages. *Proc. 12th International Conference on Solid-State Sensors and Actuators (Transducers '03)* **II** (9–15 June, Boston, Massachusetts): 1911–14.

Stark, B. H., Y. Mei, C. Zhang, and K. Najafi. 2003. A doubly anchored surface-micromachined Pirani gauge for vacuum package characterization. *Proc. IEEE MEMS Conference 2003* **I** (19–23 January, Kyoto, Japan): 506–9.

58336

Surfactant Effects on Lateral Growth and Surface Morphology of GaAs

E. S. Hertel, Jr.

Many III-V semiconductor applications require epitaxial growth on patterned substrates. These include epitaxial lateral overgrowth (ELOG), formation of low-dimensional structures, and v-groove lasers. Growth on patterned substrates can also be used for investigating fundamental surface processes occurring during epitaxial growth. Control of the morphological evolution of planar and patterned surfaces is critical for reliably generating high-quality structures for electronic and optical applications. In this project, Sandia grew gallium arsenide (GaAs) by organometallic vapor-phase epitaxy (OMVPE) on singular GaAs (001) wafers, which we patterned with mesa structures. We investigated the surfactant effects of Te, Sb, and Bi by systematically adding di-ethyl tellurium (DETe), tri-methyl antimony (TMSb), and tri-methyl bismuth (TMBi) to the atmospheric-pressure horizontal-flow reactor. We characterized evolution of the surface morphology and mesa structures by Nomarski optical microscopy and atomic-force microscopy (AFM). We observed Sb and Bi to increase the [110] lateral growth rate by as much as 300%. While Te had no effect on the lateral growth rate, it induced interesting changes to the surface morphology that we postulate to be caused by an increase in the Ehrlich-Schwoebel (E-S) barrier. We used a simple one-dimensional (1-D) kinetic simulation to investigate the effect that kinetic parameters (hop frequency, sticking coefficients, E-S barrier) have on the evolution of patterned surfaces. We used the results of these simulations to assist in the interpretation of experimental observations.

OMVPE is used for commercial production and research of III-V optical devices. The key to fabricating excellent devices is a complete understanding of growth phenomena. Epitaxy, performed under typical conditions, on the GaAs (001) surface proceeds by incorporating adatoms at $\langle 110 \rangle$ steps. Lateral growth rates, or step velocities, are usually an order of magnitude larger than the vertical growth rate. Due to differences in step dynamics, $[-110]$ and $[110]$ steps grow at different rates that are dependent on the AsH_3 overpressure and the growth temperature. For example, for GaAs grown at a vertical growth rate of $2 \mu\text{m/hr}$, the $[110]$ and $[-110]$ lateral growth rates were measured to be 5.3 and $16.8 \mu\text{m/hr}$,

...Sandia grew gallium arsenide (GaAs) by organometallic vapor-phase epitaxy (OMVPE) on singular GaAs (001) wafers, which we patterned with mesa structures. ...We used the results of these simulations to assist in the interpretation of experimental observations.

respectively. This anisotropy in the lateral growth can have dramatic effects upon the evolution of surface morphology. Islands, mounds, and patterned features will evolve anisotropically, elongating in the direction of faster lateral growth.

This study showed that by adding small amounts of isoelectronic surfactants to the growing surface, we can control the [110] lateral growth. At a TMSb/AsH₃ ratio of 0.005, the [110] lateral growth rate increased to 45 $\mu\text{m/hr}$. For Bi, a TMBi/AsH₃ ratio of 0.002 increased the [110] lateral growth rate to 50 $\mu\text{m/hr}$. We used kinetic simulations to correlate an increase in diffusion hop frequency with enhanced lateral growth. We postulate that the enhanced lateral growth is due to increase of adatom hop frequency in the fast growth direction.

Additions of Te (DETe) induced several changes to the GaAs morphology. Angular pits (on the planar surface) and trenches (at the edges of mesas) were formed when we added DETe to the reactor. We found the slope of the pit and trench sidewalls to increase with higher DETe concentrations. We established that the E-S barrier results in “slope selection” during epitaxial growth by creation of an uphill diffusion bias. The E-S barrier inhibits diffusion of adatoms from the top of 2-D islands, resulting in mound formation. The slope of these growing mounds will continually increase until mass transport off of the mounds completely compensates the uphill current and a stable slope is created. Growth will then occur in step-flow on these quasi-vicinal surfaces. Kinetic simulations corroborate the correlation of E-S barrier with increasing angle of trenches formed at the base of mesa structures. We also observed that Te decreases root-mean-square (RMS) roughness of the planar surface between mesa structures and has no effect on GaAs lateral growth.

Refereed

Wixom, R. R., L. W. Rieth, and G. B. Stringfellow. 2003. Surfactant-modified lateral growth of GaAs(001). Paper presented at the 2003 Electronic Materials Conference, Salt Lake City, Utah.

Wixom, R. R., N. A. Modine, and G. B. Stringfellow. 2003. Theory of surfactant (Sb)-induced reconstructions on InP (001). *PRB* **67**:115309.

Other Communications

Wixom, R. R., L. W. Rieth, and G. B. Stringfellow. 2003. Surfactant-modified lateral growth of GaAs(001). *J. Crystal Growth*, accepted.

Wixom, R. R., L. W. Rieth, and G. B. Stringfellow. 2003. The surfactant effects on homoepitaxial growth on patterned (001) substrates. *J. Crystal Growth*, accepted.

59034

3-D Large-Eddy Simulation of Turbulent Flow Based on One-Dimensional Turbulence Modeling

R. C. Schmidt

Sandia seeks to develop and demonstrate a fundamentally new approach to large-eddy simulation (LES) turbulence modeling based on the recently developed one-dimensional turbulence (ODT) model of Kerstein. The primary goals of this project are to complete a detailed formulation of the new method, implement it computationally, and apply it to canonical problems that will test its performance and provide proof-of-principle demonstrations of the utility of the approach for engineering and scientific applications.

The specific objectives initially defined are summarized as follows:

(1) Complete a detailed description of a constant property formulation of the new method.

(2) Implement the new method in an LES code (capable of performing appropriate test problems).

(3) Simulate fully developed turbulent channel flow and evaluate model performance.

(4) If time permits, perform calculations for and evaluate model performance of two additional well-studied canonical turbulence problems:

(a) turbulent flow over a backward-facing step, and

(b) isotropic turbulence decay (IDT) in a periodic box.

(1) Our initial work led to recognition that many different model formulations were viable, each with the possibility of having certain advantages (and/or disadvantages). Therefore, we formulated three somewhat distinct models to explore these possibilities. We denote them here as (a) the LES/ODT eddy-dissipation model, (b) the LES/ODT direct-closure model, and (c) the ODT/LES two-component model. We formulated each of the models in sufficient detail to allow for implementation and testing within an LES code.

(2) We wrote and designed a structured-grid LES code in FORTRAN 90 for use as a test-bed for these new models. We addressed a variety of numerical issues in this aspect of the work, including code validation and verification (although not beyond that which we felt is needed for a research tool), post-processing utilities for statistics and plotting, and routines for proper initialization of the turbulence characteristics needed in

Sandia seeks to develop and demonstrate a fundamentally new approach to large-eddy simulation (LES) turbulence modeling based on the recently developed one-dimensional turbulence (ODT) model of Kerstein. The primary goals of this project are to complete a detailed formulation of the new method, implement it computationally, and apply it to canonical problems that will test its performance and provide proof-of-principle demonstrations of the utility of the approach for engineering and scientific applications.

the test problems. We fully tested and utilized boundary conditions (BCs) for fully periodic flow in three dimensions (3-D). BCs for channel flow are in place, but not yet fully tested. BCs for backward-facing step flow are not yet complete. We implemented the first two LES/ODT model formulations and are now implementing the third formulation, ODT/LES.

(3) It became clear as work progressed that the best test problem for code debugging and for initial model evaluation was the IDT problem. This is because the BCs are simpler, problem solution time is shorter, and detailed experimental and direct numerical simulation (DNS) data are readily available.

(4) We performed calculations using two of the three model formulations on the problem of IDT in a periodic box. The particular conditions simulated corresponded to the classic experiments of Compte-Bellot and Corrsin. Initial results are encouraging and were presented at a minisymposium on Turbulence Simulation at the 7th U.S. National Congress on Computational Mechanics.

We formulated three distinct methods for LES closure, wrote an LES code, and tested two of three formulations tested for IDT. We plan now to test the third formulation and test all of the models at higher Reynolds numbers and on the other turbulent-flow configurations targeted. Because this approach is so radical and new, these aspects of the research will be critical in providing the proof-of-principle data necessary to complete the goals of this project.

Other Communications

Schmidt, R. C., A. R. Kerstein, R. McDermott, and S. Wunsch. 2003. Development of coupled LES/ODT turbulence simulation models. *Proc. 7th U.S. National Congress on Computational Mechanics USACM 1* (27–31 July, Albuquerque, New Mexico): 741.

60626

The Derivation and Implications of “Nearly Noninformative” Priors from Metadata Conditioning

R. G. Cox

The purpose of this project is to provide an early evaluation of a promising idea. Sandia’s hypothesis here is that an interpretation of Roy Frieden’s work deriving the laws of Physics from Fisher Information (Physics from Fisher Information, Cambridge University Press, 1999) provides a way to develop prior distributions on data, much as Bayesian analysis requires prior distributions on parameters. We believe that Frieden’s Extreme Physical Information (EPI) principles can be generalized to conditions that equate local measures of information, e.g., Fisher information, with global measures of information, e.g., Shannon information or entropy. Equating such functionals results in density functions that could be considered as natural or canonical noninformative data distributions. These distributions meet certain conditions on the nature of the parameters, but not their values per se. We call these metadata conditions. These conditions add information, so we call the distributions nearly noninformative. For example, equating Fisher and Shannon information results in a Gaussian; equating a relativistic Stam information and a global information that meets an uncertainty principle results in wave equations in quantum mechanics. The purpose of this research is to determine whether this idea can be logically and easily extended into an area of applied research of interest to the Department of Energy (DOE).

There were three stages to the research. First, we did a more thorough literature search to confirm the novelty of the idea and illuminate how it might be related to existing research threads. Next, we hypothesized that a “question space” interpretation to equating local and global information measures would allow us to apply this idea to the general class of decision problems that DOE would commonly face. For example, it would enable us to perform uncertainty analyses that would not have the structural certainty biases implicit in techniques such as Monte Carlo analysis on design codes. Third, we would develop a research strategy that would exploit this hypothesis in the development of new techniques under a larger and more-focused project.

We gathered and briefed more than 100 articles in the areas of local information measures, statistical theory, information geometry, maximum-entropy techniques, complexity theory,

The purpose of this project is to provide an early evaluation of a promising idea. Sandia’s hypothesis here is that an interpretation of Roy Frieden’s work deriving the laws of Physics from Fisher Information...provides a way to develop prior distributions on data, much as Bayesian analysis requires prior distributions on parameters. ...The purpose of this research is to determine whether this idea can be logically and easily extended into an area of applied research of interest to the Department of Energy (DOE).

and information theory. We found some parallel ideas, but no direct statement equivalent to what we were hypothesizing, nor any contradiction of the hypothesis. We discovered that information-geometry and maximum-entropy techniques provided promising new application areas for the hypothesis.

We developed the question space interpretation, which resulted in equating the number of questions that bounded the interval in which a parameter may lie (“Is the parameter bigger than breadbox X?”) with the number of sample points from a distribution with that given parameter value (“What is the next data sample from the distribution?”). We found that interpretation, although canonical, was difficult to translate into assumptions commonly made when modeling the sort of engineered systems in the DOE mission space.

We then developed alternative interpretations that we hoped would be more directly applicable to DOE systems. We worked with the “Fisher=Shannon => Gaussian” condition and developed nine other plausible interpretations:

- a differential interpretation based on De Bruijn’s identity
- entropy as a capacitated resource bounding the number of system observers
- an equivalence between the lack of observability of a score function under expectation and the lack of observability of microstates
- relating the ability to discriminate microstates with the number of microstates
- an information-geometry condition equating a Riemannian metric with natural dual connections developed for exponential families
- an invariance argument similar to those made to support the assignment of noninformative Bayesian priors
- a requirement to interpret global information as a variance
- a complementarity condition for a maximum-entropy problem
- the naive interpretation of global information reflected in every local neighborhood, thus a “holographic” system.

Sadly, none of these is so intuitive that it can be used directly to extend an existing analysis technique in a given problem area without further conceptual development. Those that are the closest to such a formal operational development are the holographic, question space, invariance, information-geometry, and complementarity conditions. But each of these directions would require its own research program to formalize the specific concept and reach a stage that is normally the

starting point for engineering research of the type done at Sandia.

The research hypothesis remains sound and still holds great promise as a platform for fundamentally new techniques in uncertainty analysis and maximum-entropy problems, as well as evaluating and interpreting the results of agent-based modeling.

60627

New Seismic-Event-Detection Technology

K. W. Larson, A. Backer, D. Hart, B. J. Merchant

The Seismic Ear hypothesis proposes that a new technology for seismic-event detection may be created by applying a technique in the field of computational neuroscience to the field of seismic monitoring for underground nuclear explosions. Sandia developed the computational neuroscience technique to model the process of human audition; it uses the principle of transient partial synchrony among a set of interacting neurons. We showed the technique to be robust to noise and certain types of signal variation. We designed this project to prove the concept through prototype demonstration. Tasks in the project include model development and validation, adaptation to the seismic domain, initial testing, design and implementation of a learning rule, and final testing.

Accomplishments for the Seismic Ear, a new seismic-event-detection technology project, include the following:

- We designed and implemented a mathematical model for partial-transient-synchrony neural networks. The model is implemented in C for speed; however, many set-up and post-processing tasks are programmed in MATLAB for highly efficient configuration and data manipulation. The model is called SPLab.
- We performed dynamical testing to understand the phenomena of partial transient synchrony.
- We created an interface from SPLab to the domain of seismic waveforms. The interface creation was facilitated by the existence of extensive seismic processing capability in Sandia's GNEM program.
- We conducted initial testing of seismic data. The initial testing was inconclusive. Analysis and modifications will be undertaken with follow-on funding.

We designed a learning rule, allowing better network training and function, but have not tested or implemented it. The learning rule will be tested with follow-on funding.

Sandia developed the computational neuroscience technique to model the process of human audition; it uses the principle of transient partial synchrony among a set of interacting neurons. We showed the technique to be robust to noise and certain types of signal variation. We designed this project to prove the concept through prototype demonstration.

Other Communications

Larson, K. W., and D. Hart. 2003. The Seismic Ear: A New Seismic-Event-Detection Technology—First Progress Report. Sandia Technical Report SAND2003-3460, Sandia National Laboratories, Albuquerque, New Mexico.

61045

Testing Recent Metal-/Oxide-Joining Discoveries in NW Component Manufacturing

D. R. Jennison, P. A. Schultz, R. S. Goeke

The vacuum envelope of neutron tubes produced by Sandia requires that metal parts be brazed to an alumina ceramic. For a variety of reasons, there has been an ongoing search for a better process. Theoretical work by Sandia appears to offer a solution. In particular, the theory predicts that aluminum (Al)/alumina ceramic interfaces (a material combination that will possibly be used in an advanced tube design) may be produced that are stronger than Al itself. During this project, we confirmed this prediction. In addition, we derived promising steps, such as surface-glass reduction, and suggested promising steps, such as rotation during bonding. These have raised, or are expected to raise, the success rate for producing hermetic seals into the high 90% range. Such results could also lead to a commercial patent application.

Using brazing to join neutron-tube parts requires an active compound between the parts and heating to very high temperatures. This achieves a reaction between the components. If it were possible to join the parts by simple “diffusion bonding,” lower temperatures could be used, a manufacturing step would be eliminated, and in principle, greater reliability could be achieved. With diffusion bonding, for example between alumina ceramic and Al metal, the parts are first baked at ultrahigh voltage (UHV) to remove surface contaminants. Then the still-heated parts (at about 500°C, much lower than braze temperatures) are simply pressed together. The softened metal fills irregularities inherent in the micron-scale roughness and comes into direct contact with the alumina crystals, which have the alpha-Al₂O₃, or sapphire, phase. Different materials have different thermal-expansion coefficients. If joined at elevated temperature, interfacial stress results upon cooling. The diffusion-bonding method in principle will result in less stress after cooling than a braze, and therefore can result in more reliable and simpler joining.

Only recently has the actual binding strength of a metal to alumina been determined by experiment. Upon comparing the best first-principles theories to experiment, we found that an older version of density-functional theory (DFT) agreed much better with experiment than a newer method. The reason for this was explained by an extension of work done by others. They published corrected values that showed the problem lay with

The vacuum envelope of neutron tubes produced by Sandia requires that metal parts be brazed to an alumina ceramic. For a variety of reasons, there has been an ongoing search for a better process. Theoretical work by Sandia appears to offer a solution....we derived promising steps, such as surface-glass reduction, and suggested promising steps, such as rotation during bonding. These have raised, or are expected to raise, the success rate for producing hermetic seals into the high 90% range. Such results could also lead to a commercial patent application.

the surface-energy part of the analysis. Having proved the ability to compute accurately the work of adhesion between metals and oxides, a natural extension was to use our insights to assist with Sandia problems of nuclear weapons interest.

Sandia joined work on the advanced neutron tube (AdvNT), where the above progress could possibly be used in the joining team. We attempted to form a hermetic seal between two alumina buttons. We placed a piece of Al foil in between and did diffusion bonding after the cleaning step. Initially, the success rate was about 25%. However, the alumina was "sandi94," which contains 94% sapphire microcrystals and 6% glass. Dr. Jennison explained that the glass was a potential problem, for while his calculations showed that Al would bind to sapphire with an interface that was stronger than the adhesion between even the atomic planes in the metal, it would not bind strongly to glass. We tried two things to improve success. We thickened the Al foil to 3 mils so it could better fill the roughness in the ceramic surfaces, and we ion-bombarded the ceramic surfaces before bonding. Since the ions remove glass much more easily than they remove sapphire, the latter had the effect of decreasing the surface-glass fraction.

Now the success rate jumped to over 75%. However, several things remain that could bring it close to 100%. It was pointed out that firing alumina in a dry hydrogen atmosphere further removes surface glass without damaging the sapphire, and suggested that we use aluminas with a lower glass content (< 1% is available). Finally, it was suggested that we twist the parts during bonding, as it is impossible for the machined surfaces to be completely parallel; thus, twisting would bring more surface into contact, probably without affecting what is already bonded, as it is much easier to rotate metal-metal planes than the metal-oxide interface. While we have not yet tested the latter suggestions, we plan to try an ultrasound treatment during bonding as an alternative to twisting. We have also explored using silver, which is softer.

Having proved the ability to compute accurately the work of adhesion between metals and oxides, a natural extension was to use our insights to assist with Sandia problems of nuclear weapons interest. Sandia joined work on the advanced neutron tube (AdvNT), where the above progress could possibly be used in the joining team.

61046

Photonic Encryption Using All-Optical Logic

J. D. Tang, R. C. Schroepel, G. A. Vawter, J. D. Tang, T. D. Tarman, D. K. Serkland

As existing transport networks evolve into intelligent all-optical networks, end-to-end connections are beginning to look like virtual fibers. The elimination of optical-electrical-optical (OEO) conversions within network equipment allows for a vast increase in network capacity due to enabling technologies such as dense wavelength division multiplexing (DWDM). This is an important trend for Sandia and the Department of Energy (DOE) complex due to the increasing need to interconnect high-performance computing and visualization platforms, often in a “network protocol agnostic” fashion. However, as signaling and switching technologies progress toward an all-optical architecture, network-encryption technology, which remains in the electrical domain, fails to keep pace. Because network encryption is paramount to the Sandia/DOE mission, lack of encryption mechanisms for all-optical networks seriously limits our ability to utilize these exciting new technologies and to reach bit rates currently not viable under electronic methods.

Over the past 5 years, Sandia has been developing all-optical devices that perform Boolean logic functions on optical inputs and produce optical outputs without intermediate electrical conversion. These all-optical logic gates are built upon two distinct technologies—self-electrooptic-effect devices (SEEDs) and gain-competition technologies. These devices may form logical building blocks suitable for designing a photonic encryptor. We are developing a technically feasible design for a photonic encryptor that is based on a simple, but useful, encryption algorithm that can be built within the limitations of the SEED and/or gain-competition devices. The encryptor will be able to process an optical data stream with known characteristics and will exhibit scaling properties to bit rates unreachable through traditional OEO methods. This project has examined cryptographic algorithms in detail and determined innovative implementation approaches that can be implemented within the constraints of current optical logic-gate technology. In addition, we also explored novel encryption approaches that utilize other photonic properties (e.g., dispersion, polarization, etc.) that may be modulated by these devices.

We performed a paper study of encryption algorithms and documented the feasibility for use with all-optical logic. We also examined other methods of encryption in the optical

We are developing a technically feasible design for a photonic encryptor that is based on a simple, but useful, encryption algorithm that can be built within the limitations of the SEED and/or gain-competition devices. The encryptor will be able to process an optical data stream with known characteristics and will exhibit scaling properties to bit rates unreachable through traditional OEO methods.

domain for network encryption, including chaotic mode-locked semiconductor lasers, quantum cryptography using coherent-state noise, and single-photon quantum key distribution. We are designing building blocks of optical logic for use in encryption. We are currently using C programming to validate a “lightweight yet nontrivial” encryption algorithm for demonstration purposes.

This project assessed industry-standard encryption algorithms and found that strict electrical-to-optical translations of the Data Encryption Standard (DES), the Advanced Encryption Standard (AES), and A5 ciphers are not feasible for all-optical implementation due to large gate count and parallel operation. We proposed a “lightweight yet nontrivial” encryption algorithm that would incorporate low gate count and operate in a cascaded, serial fashion. Upon cryptanalysis of this demonstration algorithm, we found that it achieves diffusion and confusion through many repeated, cascaded stages.

We examined the operational characteristics of both the SEEDs and gain-competition devices for use as Boolean complete logic. We are focusing on employing interconnected SEEDs for implementing NAND/AND, NOR/OR, and XOR functionality. We designed simple XOR functionality for the gain-competition technology. SEEDs are also flexible enough to provide conditional delay and conditional inverting functionality—both necessary for the demonstration algorithm. We currently are validating the demo algorithm in a C program, which shows encryption and decryption of a bit stream.

Due to the clocked nature of the SEED technology, the project team discovered that preset, inputs, and clock signals must be pipelined in time slots to implement simple logic gates. The NAND/AND, NOR/OR functions require three time slots to effectively represent a digital 1 or 0. The XOR comprises two logic gates with outputs cascaded into a third gate. This function requires five time slots to act as a two-input–one-output XOR. Inverters and buffers require two and three time slots to represent a 1 or 0. This implies that timing of inputs must be designed carefully within each allotted slot.

Because there is no known software that can model these devices at a circuit level, we are making an effort to model the functionality of the SEEDs and the gain-competition devices in an optical circuit in PSPICE. PSPICE allows us to model macro characteristics of the devices in the context of a logic element as opposed to device-level computational modeling. By representing light intensity as voltage, we are attempting to generate “black box” models that accurately represent the intensity response and logic levels in both technologies. By

Because there is no known software that can model these devices at a circuit level, we are making an effort to model the functionality of the SEEDs and the gain-competition devices in an optical circuit in PSPICE. PSPICE allows us to model macro characteristics of the devices in the context of a logic element as opposed to device-level computational modeling.

modeling the behavior at the systems level, we can incorporate systems design tools and a simulation environment to aid in the overall functional design. Using these “black-box” models, we intend to interconnect and cascade them in an encrypting/scrambling algorithm based on a study of candidate encryption algorithms. We found that our “lightweight yet nontrivial” low-gate-count, cascable encryption algorithm is most feasible given device and processing constraints.

In attempts to incubate the readiness of these tools for qualifying a large-scale design, we intend to examine demonstration algorithms and refine the “lightweight yet nontrivial” scheme as well as investigate other low-gate-count, serial, cascable demonstration algorithms for encryption. We also intend to continue the design of building blocks for a set of Boolean complete logic. Appropriate follow-on work includes completing a set of XOR, NAND/AND, NOR/OR, inverter, and buffer gates for both the SEED and gain-competition technologies.

61047

Automated Video Screening for Unattended Background Monitoring in Dynamic Environments

J. J. Carlson, D. D. Padilla, J. C. Neely

In this project, Sandia addressed the development of automated video-screening technology to assist security forces in protecting our homeland against terrorist threats. A prevailing threat is the covert placement and subsequent remote detonation of bombs (e.g., briefcase bombs) inside crowded public facilities. These locations are ideal for terrorist attacks because (1) many facilities do not screen people entering or exiting the facility due to high costs and intense manpower requirements, (2) it is relatively easy to place a bomb unnoticed because of all the surrounding activity, (3) there is a high potential for large numbers of casualties, and (4) the idea of someone bombing a crowded public facility strikes fear into the hearts of nearly all Americans.

Although video-surveillance systems are increasingly more common in public facilities, current systems are unable to detect the placement of bombs. It is also unlikely that security personnel could detect a bomb, or someone placing a bomb, by observing live video from surveillance cameras. The problems lie in the large number of cameras required to effectively monitor a large area, the limited number of security personnel employed to protect these areas, and the intense diligence required to effectively screen live video from even a single camera. Different from existing video motion detection (VMD) systems, the proposed video-screening technology will be capable of detecting changes in the static background of an otherwise dynamic environment—environments where motion and human activities are commonplace. Instead of subtracting the background to detect movement or changes in a scene, we will subtract the dynamic scene variations to produce an estimate of the static background. We will use subsequent comparisons of static-background estimates to detect changes in the background. We will use detected changes to alert security forces of the presence and location of potential threats.

Work involved both feature discovery and algorithm development. We investigated features that can be extracted easily from video data and that are useful for background extraction in dynamic scene environments where motion and human activity are commonplace (e.g., inside a subway station, airport, or bus depot). We developed algorithms using these

...Sandia addressed the development of automated video-screening technology to assist security forces in protecting our homeland against terrorist threats....Although video-surveillance systems are increasingly more common in public facilities, current systems are unable to detect the placement of bombs. ...Different from existing video motion detection (VMD) systems, the proposed video-screening technology will be capable of detecting changes in the static background of an otherwise dynamic environment—environments where motion and human activities are commonplace.

features to extract the static background of a dynamic scene. We used subsequent comparisons of static-background estimates to detect changes in the background (e.g., the placement of a briefcase bomb next to a trash can). The system could be used to alert a security guard of the presence and location of detected changes. The guard could then make a visual assessment of any potential threats and plan an appropriate response. We proved the feasibility of the technical concept.

- *Technical need.* The problem we are addressing is the development of automated video-screening technology to assist security forces in protecting our homeland against terrorist threats. A prevailing threat is the covert placement and subsequent remote detonation of bombs (e.g., briefcase bombs) inside crowded public facilities. These locations are ideal for terrorist attacks because (1) many facilities do not screen people entering or exiting the facility due to high costs and intense manpower requirements, (2) it is relatively easy to place a bomb unnoticed because of all the surrounding activity, (3) there is a high potential for large numbers of casualties, and (4) the idea of someone bombing a crowded public facility strikes fear into the hearts of nearly all Americans.

Although video-surveillance systems are increasingly more common in public facilities throughout the U.S., current systems are unable to detect the placement of bombs. The mere presence of surveillance cameras is assumed to provide some degree of deterrence. It is also unlikely that security personnel could detect a bomb, or someone placing a bomb, by observing live video from surveillance cameras. The problems lie in the large number of cameras required to effectively monitor a large area, the limited number of security personnel employed to protect these areas, and the intense diligence required to effectively screen live video from even a single camera. Our approach was to develop an automated video-screening technology that is capable of detecting changes in the static background of an otherwise dynamic environment. Different from existing VMD systems that operate in primarily static environments, the system is intended for operation in a dynamic environment where motion and human activities are commonplace. Instead of subtracting the background to detect movement or changes in a scene, we subtract the dynamic scene variations to produce an estimate of the static background. Subsequent comparisons of static-background estimates are used to detect changes in the background. We can use detected changes to alert security forces of the presence and location of potential threats.

62269

Nanoporous-Carbon Adsorbers for Chemical Microsensors

M. P. Siegal, W. G. Yelton

Chemical microsensors rely on partitioning of airborne chemicals into chemically selective films to collect and measure trace quantities of hazardous vapors. Polymer sensor coatings in use today are typically slow to respond and difficult to apply reproducibly. The objective of this project is to produce a durable sensor-coating material based on graphitic nanoporous carbon (NPC), a new material first studied at Sandia, for collection and detection of volatile organic compounds (VOCs), toxic industrial chemicals (TICs), chemical warfare agents (CWAs), and nuclear-processing precursors. Preliminary studies using NPC films on exploratory surface acoustic-wave (SAW) devices and as a μ ChemLabTM membrane preconcentrator suggest that NPC will outperform existing, irreproducible coatings for SAW sensor and μ ChemLabTM preconcentrator applications. Success of this project will provide a strategic advantage to the development of a robust, manufacturable, highly sensitive chemical microsensor for public health, industrial, and national security needs. We use a line-of-sight (LOS) physical deposition process to grow NPC films at room temperature with negligible residual stress, and hence, it can be deposited onto nearly any substrate material to any thickness. Controlled deposition yields reproducible NPC density, morphology, and porosity without any discernible variation in surface chemistry. NPC coatings $> 20 \mu\text{m}$ thick with density $< 5\%$ that of graphite have been demonstrated. NPC can be “doped” with nearly any metal during growth to provide further enhancements in analyte detection and selectivity.

We exposed several issues related to SAW device surface preparation and NPC materials. Improvements include a more complete removal of the now-several-years-old protective photoresist on the SAW devices using an oxygen plasma treatment, resulting in greater reproducibility of SAW devices using NPC sensing coatings. We also learned that more than one form of nanostructured carbon bonding can occur for NPC films with the same density based on deposition energetics. Such structures have widely different surface-chemistry properties. For NPC produced using low-deposition energies, optimal NPC density for acetone adsorption is between 0.25 and 0.5 g/cm^3 . We demonstrated that NPC adsorbs acetone

The objective of this project is to produce a durable sensor-coating material based on graphitic nanoporous carbon (NPC), a new material first studied at Sandia, for collection and detection of volatile organic compounds (VOCs), toxic industrial chemicals (TICs), chemical warfare agents (CWAs), and nuclear-processing precursors. ...Success of this project will provide a strategic advantage to the development of a robust, manufacturable, highly sensitive chemical microsensor for public health, industrial, and national security needs.

linearly with coating mass up to at least 1 mg/cm^2 , offering the possibility of greater sensitivities with increased adsorbing mass without the signal dampening associated with film stresses. Transmission-electron microscopy reveals that lower-density NPC has both larger and greater numbers of nanopores than higher-density NPC, and that decreasing NPC density also increases the interplanar spacing between graphene sheet fragments within the ultrathin carbon wall structures. These physical differences effectively increase the available surface area for analyte gas adsorption with decreasing NPC density, with only the structural integrity of the internal NPC wall structures a limiting factor in determining the lowest-useful-density NPC coating.

Refereed

Siegal, M. P., W. G. Yelton, D. L. Overmyer, and P. P. Provencio. 2003. Nanoporous-carbon films for gas microsensors. *Langmuir*, accepted.

63972

Molecular Electronics Test Platform

A. A. Talin, P. M. Dentinger, L. L. Hunter

Sandia fabricated and characterized an electrode-array test structure, designed for electrical probing of molecules and nanocrystals. We used extreme ultraviolet lithography (EUVL) to define features of the electrical test platform. As fabricated, the platform includes nominal electrode gaps of 0 nm, 40 nm, 50 nm, 60 nm, 70 nm, and 80 nm. We achieved additional variation in electrode gap by controlling the exposure conditions, such as dose and focus. To enable EUVL-based nanofabrication, we developed a novel bilevel-photoresist process. The bilevel photoresist consists of a combination of a commercially available polydimethylglutarimide (PMGI) bottom layer and an experimental EUVL photoresist top (imaging) layer. We measured the sensitivity of PMGI to EUV exposure dose as a function of photoresist prebake temperature and, using these data, optimized a metal lift-off process. We achieved reliable fabrication of 700 Å thick gold (Au) structures with sub-1000 Å critical dimensions, even without the use of an Au adhesion layer, such as titanium (Ti). We used several test platforms to characterize electrical properties of organic molecules deposited as self-assembled monolayers (SAMs).

Sandia fabricated and characterized an electrode-array test structure, designed for electrical probing of molecules and nanocrystals. We used extreme ultraviolet lithography (EUVL) to define features of the electrical test platform....To enable EUVL-based nanofabrication, we developed a novel bilevel-photoresist process.

(1) We developed a robust EUVL-based nanofabrication process that allows for lift-off-type metal patterning without metal tearing. The very thin resist used for EUVL makes this process necessary for actual fabrication.

(2) We fabricated and characterized electrode-array platforms with direct lithographic control of 10 nm of the electrode gap.

(3) We assembled a computer-controlled electrical-characterization probe station capable of probing micron-size devices.

(4) We developed an alternating current (AC) dielectrophoretic trapping technique and demonstrated trapping of single Au nanospheres with diameters ranging from 30 nm to 150 nm, and carbon nanotubes.

(5) We characterized experimentally electron transport of clean Au electrodes with Au nanospheres.

(6) We measured the effect of SAMs on electron transport across nanosphere-bridged electrodes: C14H29-SH, C6H11-SH, and HS-C6H4-SH.

(7) We demonstrated a reliable process for producing electrode gaps with molecular dimensions (below 5 nm) using a combination of EUVL and electromigration.

(8) We collaborated with the National Aeronautical and Space Agency (NASA)/AMES Laboratory, based on Sandia's providing an EUVL-fabricated platform for molecular and nanoparticle electrical characterization.

(9) We established a similar collaboration with Hewlett-Packard Labs.

(10) We presented our findings at the Electron, Ion, Photon, and Nanofabrication Conference in Tampa, Florida.

Refereed

Talin, A. A., G. F. Cardinale, T. L. Wallow, P. Dentinger, S. Pathak, D. Chinn, and D. R. Folk.
2003. Extreme ultraviolet lithography-based nanofabrication using a novel bilevel photoresist. Paper presented at the Electron, Ion, Photon Beam and Nanofabrication Conference, 27 May, Tampa, Florida.

64709

Development of Highly Integrated Magnetically and Electrostatically Actuated Micropumps

P. C. Galambos, A. Lopez, K. R. Pohl

In this project, Sandia sought to develop viscous pump devices in collaboration with Florida State/Florida A&M University (FSU/FAMU). These devices can be either electrostatically or magnetically driven. Work progressed in the following areas: (1) dry actuation of viscous pumps (optimum waveforms developed), (2) flow-resistance measurements of pump/pipe combinations, (3) identification of magnetic particles for use in flow system, (4) magnetic coatings, (5) wet testing of viscous pumps with various liquids, and (6) new electrostatic and magnetic actuator and particle-manipulation designs.

Three new SUMMiT™ (Sandia Ultraplanar Multilevel MEMS [microelectromechanical systems] Technology) designs came out of this work. These designs incorporate lessons learned during testing and analysis of the previous devices. Their most important aspect is the incorporation of new higher-torque pump actuators. We demonstrated qualitative pumping of water and other liquids, but still need our first complete pump curve. We made flow-resistance measurements (the pipe curve) for the pumps. Finally, we have mostly overcome the problems of actuating devices dry and have developed optimum drive signals.

...Sandia sought to develop viscous pump devices in collaboration with Florida State/Florida A&M University (FSU/FAMU). These devices can be either electrostatically or magnetically driven.

Refereed

Sosnowchik, B. D., P. C. Galambos, K. V. Sharp, M. W. Jenkins, M. W. Horn, and J. R. Hendrix. 2003. Dry actuation testing of viscous drag micropumping systems utilizing novel waveforms. *Proc. SPIE Micromachining Conference*, accepted.

65556

A Robotic Framework for Semantic Concept Learning

P. G. Xavier

Sandia seeks to enable autonomous robots to learn a semantic representation of an environment through interaction with objects and people. We propose (1) development of a basic hardware and software framework for real-time distribution of sensor data to modules for processing and decision making, and (2) development of an associative memory capable of adaptively learning complex associations among multiple input and output modalities. Our collaborator at the University of Illinois has already created and demonstrated an initial robust distributed software architecture that allows the robot to make decisions and act based on auditory, visual, and tactile inputs. This architecture is being developed into a full communication framework integrating a variety of the robot's processing modules.

The proposed associative memory consists of a cascade of ergodic hidden Markov models (HMMs), which have been shown to automatically learn some of the underlying structure of a set of inputs. Lower levels of the cascade consist of a number of HMMs for multiple modalities. On the robot, the lowest level would consist of models for various auditory, visual, proprioceptive, and kinesthetic features. We will then use the state sequences of these HMMs as the inputs to a subsequent layer of HMMs for concept learning. This idea can be extended to more layers for learning higher-level concepts. This particular approach appears to be novel for concept learning and, moreover, capable of modeling some of the deep structure of language and reality.

This technology should enhance usability of robots in Department of Energy/national security missions, particularly homeland security and at nuclear sites. Currently, use of robots—e.g., in the search for, investigation of, and neutralization of terrorist devices—is hampered by the problem that a robot's "vocabulary" and understanding of what it encounters is limited to what has been programmed or downloaded from a database.

Sandia seeks to enable autonomous robots to learn a semantic representation of an environment through interaction with objects and people....Currently, use of robots—e.g., in the search for, investigation of, and neutralization of terrorist devices—is hampered by the problem that a robot's "vocabulary" and understanding of what it encounters is limited to what has been programmed or downloaded from a database.

65558

Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems

E. E. May, A. M. Johnston, W. E. Hart, R. J. Pryor, J. P. Watson

A fundamental challenge for all communication systems, engineered or living, is the problem of achieving efficient, secure, and error-free communication over noisy channels. Information theoretic principals have been used to develop effective coding theoretic algorithms to successfully transmit information in engineering systems. Living systems also successfully transmit biological information through genetic processes such as replication, transcription, and translation, where the genome of an organism is the contents of the transmission.

Decoding of received bit streams is fairly straightforward when the channel-encoding algorithms are efficient and known. If the encoding scheme is unknown or part of the data is missing or intercepted, how would one design a viable decoder for the received transmission? For such systems, blind reconstruction of the encoding/decoding system would be a vital step in recovering the original message. Communication engineers may not frequently encounter this situation, but for computational biologists and biotechnologists, this is an immediate challenge.

The goal of this work is to develop methods for detecting and reconstructing the encoder/decoder system for engineered and biological data. Building on Sandia's strengths in discrete mathematics, algorithms, and communication theory, we are using linear programming and will use evolutionary computing techniques to construct efficient algorithms for modeling the coding system for minimally errored engineered data stream and genomic regulatory deoxyribonucleic acid (DNA) and ribonucleic acid (RNA) sequences. The objective for the initial phase of this project is to construct solid parallels between the biological literature and the fundamental elements of communication theory. In this light, our work focused on defining the genetic-channel characteristics and providing an initial approximation for key parameters, including coding rate, memory length, and minimum distance values. A secondary objective addressed the question of determining similar parameters for a received, noisy, error-control (EC) encoded dataset. In addition to these goals, we initiated exploration of algorithmic approaches to determine if a dataset could be approximated with an error-control code.

The goal of this work is to develop methods for detecting and reconstructing the encoder/decoder system for engineered and biological data. Building on Sandia's strengths in discrete mathematics, algorithms, and communication theory, we are using linear programming and will use evolutionary computing techniques to construct efficient algorithms for modeling the coding system for minimally errored engineered data stream and genomic regulatory deoxyribonucleic acid (DNA) and ribonucleic acid (RNA) sequences.

We used several approaches in this work, including (1) information theoretic techniques, (2) cryptographic analysis, and (3) optimization methods.

In engineering systems, channel characteristics determine the EC coding used. We investigated mutation rates for the replication process (modeled as an error-introducing communication channel) of various organisms. From analysis of mutagenesis data, we noted the following.

(1) The relationship between prokaryotic mutation rates and genome size exhibits power-law behavior. This does not hold for higher eukaryotes. (2) A link may exist between the mutation rate of a biological agent and the agent's pathogenicity. Initial findings show that the Biological Safety Level (BSL)-1 category contained the agent with the lowest error rate while BSL-3 contained the agent with the noisiest genetic channel. (3) Based on mutation rates we calculated the genetic-channel capacity. Although there is very little difference among the organisms studied, the channel capacity of higher eukaryotes tends to be slightly larger than that of the DNA microbes. Overall initial channel-capacity calculations imply a very high coding rate, one with minimal redundancy of the form $(n=N, k=N-1)$. To determine EC coding parameters, we developed a method for determining k for an $(n=N, k)$ linear block code. We analyzed the (7,4) Hamming, (16,11) Hamming, and (32,17) codebooks using a variation of the Shannon entropy. Codebook codewords contained randomly generated $T=0.5$ error bits. Entropic profiles asymptotically approached correct k values, even in the presence of noise.

The goal of our cryptographic study was to search RNA streams for mathematical relationships or exploitable patterns. These relationships and patterns, if they exist, will improve our understanding of how biological sequences store, process, and handle genomic data. We performed initial work on *E. coli* genes and leader sequences. Analysis methods included the following:

- (1) Lexicographical sorting to find matching substreams and to obtain statistics on matching substring lengths,
- (2) One- and two-element Markov models to determine if short common patterns exist,
- (3) Finding linear generators for RNA sequences mapped to $GF(2^2)$ to determine the existence of hidden linear relationships, and
- (4) Analyzing the effect of various mappings of null to the elements in $GF(2^2)$, to see if there are mathematical reasons to choose one mapping over another.

Lexicographical sorting found that leader sequences have larger matching substreams on average than the full *E. coli* gene sequence. The mean maximal matching substring length was 7.35 for nontranslated leader sequences (intergenic sequences), 6.89 for the translated leader sequences, and 4.32 for the complete gene sequence. Currently, we have found no obvious patterns using Markov modeling. Additional studies are needed. The final two tests were intimately connected. The research showed that the linearity of a stream depends on how the bases are mapped. In particular, the overall linearity of the stream (a ratio of the number of elements generated by a polynomial over the degree of its generating polynomial) depends on which base is mapped to the zero element. Mapping cytosine to the zero element (the other bases can be mapped to any of the remaining three elements) gave the highest linearity ratios.

The problem of reconstructing an encoder/decoder system can be viewed as an optimization problem. We formulated the problem as an integer program (IP), which can be solved exactly using available branch-and-bound technology. At present, these algorithms effectively reconstruct encoders/decoders for error-free channels. However, scalability is a major issue, as we currently are unable to solve the reconstruction problem for large, noisy channels. There are two issues with scalability. The first is the strength of the lower bound, which in the current formulation appears quite weak. This is causing a huge branch-and-bound tree, such that nodes can rarely be pruned. The second is the memory consumption of the IP formulation (related to the number of nodes), which scales as the product of n and the number of codewords m . To achieve scalability for realistically sized biological systems, we need different problem formulations and advances in solver technology.

Refereed

May, E. E. 2003. Coding theory meets molecular biology. Paper presented at the 2003 Conference of Ford Fellows, October, San Juan, Puerto Rico.

May, E. E. 2003. Optimal generators for a systematic block code model of prokaryotic translation initiation. *Proc. 25th IEEE EMBS Conference* (17–21 October, Cancun, Mexico).

May, E. E. 2003. Toward a biological coding theory discipline. Master's thesis, North Carolina State University, Raleigh, North Carolina.

May, E. E., M. A. Vouk, D. L. Bitzer, and D. I. Rosnick. 2003. An error-correcting code framework for genetic sequence analysis. *J. Franklin Institute*, Elsevier, submitted.

May, E. E., M. A. Vouk, D. L. Bitzer, and D. I. Rosnick. 2003. Coding theory-based models for protein translation initiation in prokaryotic organisms. *J. BioSystems*, accepted.

Other Communications

May, E. E. 2003. Biological coding theory. (Invited) Paper presented at the Santa Fe Institute, September, Santa Fe, New Mexico.

65559

Direct Single-Ion Machining of Nanopores*P. Rossi, A. K. Norman, T. A. Friedmann, D. M. Follstaedt*

Sandia seeks to use individual high-energy, heavy ions to directly produce nanometer- and possibly subnanometer-size pores in membranes, through “Coulomb explosions” (also known as electronic sputtering). The ultimate goal of this research is to understand the combination of ion-solid interaction physics and materials science that controls the diameter and depth to which nanopores can be spontaneously produced by individual ions in ultrathin membranes. There currently are numerous Sandia applications for membranes with a highly controlled array of nanopores, or even a single nanohole, where this pore diameter approaches or even goes below 1 nm. The research and technology are therefore well aligned with the current and future emphasis of several Sandia Strategic Business Units (SBUs) and Strategic Management Units (SMUs) on nanotechnology.

Sandia explored the feasibility of generating nanometer-size holes in thin membranes. Our approach combined both experiments and theoretical calculations. There were already significant capabilities extant at Sandia to undertake this work. We used beams of 374 MeV gold (Au) +25 and 241 MeV I+19 ions from the recently completed radio-frequency (RF) quadrupole linear accelerator (LINAC) to drill these nanoholes. We envisioned exposing ultrathin membranes (~ 10 nm) or SiO₂, Si₃N₄, MICA, and diamondlike carbon in the experimental project and then searching for nanoholes using the transmission-electron microscopy (TEM) or alternative techniques invented by the project. We first made theoretical analysis using molecular dynamics (MD) calculations of atomic-force microscopy (AFM) scans of ion-craters, and later of the nanoholes. We then used the theory to design further exposures to test how well the diameter of such nanoholes can be controlled.

We also sought out synergistic collaborations with other Sandia projects that could benefit from the unique nanohole membranes produced by this project.

We made several modifications of the tandem RF quadrupole (RFQ) beam line and achieved a substantial increase of the ion rate. The improvement is about a factor of 5 for the most energetic ions, i.e., Au-197 at 374 MeV, increasing from about 10^3 to $5\text{--}10^3\text{ cm}^{-2}\text{ s}^{-1}$. We continue to work toward the goal of increasing this flux another factor of 10.

The ultimate goal of this research is to understand the combination of ion-solid interaction physics and materials science that controls the diameter and depth to which nanopores can be spontaneously produced by individual ions in ultrathin membranes....Sandia explored the feasibility of generating nanometer-size holes in thin membranes. Our approach combined both experiments and theoretical calculations. There were already significant capabilities extant at Sandia to undertake this work.

With Lawrence Livermore National Laboratory, we are employing the MD program MDCASK to simulate different experimental conditions. The aim is to single out “promoters” fostering the formation of holes, like stress, temperature, inclination, and electric field.

Most recently, we prepared thinned TEM specimens of (0001) sapphire and irradiated them with 374 MeV Au ions. We chose sapphire because its atomic bonding is very ionic, and Coulomb explosions are believed to occur more readily in ionic materials. TEM imaging found the sites where the Au ions passed through thin (~ 30 nm) material. The images show a crater and piled-up material at both the incident and exit positions through the specimen. The craters are ~ 5 nm across. Some images appear to show a low-density ion track (~ 4 nm across) passing through the specimen. Work is also proceeding on Si_3N_4 films where we have also observed craters.

It is unclear whether we have observed fully formed nanoholes, and this will be our focus in upcoming work. The difficulty we have had in forming such nanoholes is probably due to the large thickness of the initial foils (> 30 nm). It is also worth exploring whether lower-energy ions can do a better job of making Coulomb perforations; this was reinforced with recent discussions with personnel at a school in Spain. Although their stopping power is smaller, the energy release is more confined.

Refereed

Doyle, B. L., F. D. McDaniel, and P. Rossi. 2002. Using the new Sandia RFQ for nanofabrication. Paper presented at the 17th International Conference on Application of Accelerators in Research and Industry, 12 November, Denton, Texas.

McDaniel, F. D., B. L. Doyle, P. Rossi, D. L. Buller, R. W. Hamm, and H. Schone. 2003. The tandem-RFQ LINAC booster at Sandia National Laboratories. *Proc. AIP 17th International Conference on Applications of Accelerators in Research and Industry*, AIP Press **680** (12 November, Denton, Texas): 986–90.

66170

Investigation of the Effects of Intense Pulsed-Particle Beams on the Durability of Metal-to-Plastic Interfaces

T. J. Renk, M. C. Celina, P. P. Provencio

Sandia's unique pulsed-power capability was originally developed to simulate the effects of nuclear explosions on weapon components, and to investigate nuclear fusion for power generation. In recent years, we have shown that exposure to pulsed-power beams can improve the wear durability of metal surfaces. The cyclic heating and cooling caused by such beams (10^9 K/s) leads to grain refinement, dispersal of second-phase particles, and formation of metastable phases, all of which can lead to durability improvements. In some applications where counterfaces exist between metals and polymers, we desire to reduce wear of both the polymer and metal surfaces, either by hardening the surfaces, reducing the friction between the counterface surfaces, or both. In the case of polymers, hardening can be produced by promoting cross-linking of the polymer. The understanding of the effects of pulsed-power beams on the wear durability of these surfaces will contribute to our understanding of the wear durability of similar materials used in various defense applications.

We will collaborate with outside partners who are investigating the durability of materials used in artificial hip joints. The materials to be investigated include metal (titanium [Ti] and cobalt-chromium-molybdenum [Co-Cr-Mo] alloy) and ultrahigh-molecular-weight polyethylene (UHMWPE). The objectives include improvement of the abrasion resistance of the UHMWPE, and reduction of friction wear of the contact surface between UHMWPE and the metal counterface. We will investigate biocompatibility by the production of doped thin-film coating. We will use ion beams to produce thin films and surface alloying of the metals, and electron beams to cross-link the UHMWPE.

These experiments will broaden our experience base of working with different materials in RHEPP (repetitive high-energy pulsed power)-1 and contribute to the durability of components used in national security missions.

We began treatment of materials, provided by DePuy Orthopaedic, Inc. UHMWPE samples were ion-beam treated, and DePuy started an analysis (self-funded). A Ti alloy being considered for use has also been processed. We are sending UHMWPE samples Efremov for treatment by electron beams.

The understanding of the effects of pulsed-power beams on the wear durability of these surfaces will contribute to our understanding of the wear durability of similar materials used in various defense applications....These experiments will broaden our experience base of working with different materials in RHEPP (repetitive high-energy pulsed power)-1 and contribute to the durability of components used in national security missions.

We are investigating both ions and electrons for their potential to cross-link and harden the UHMWPE surface.

A treatment plan is also in place with Alvarado Orthopedics (California), and Sandia received samples. The goal here is to also improve surface mechanical hardness, but also to encourage bone on-growth by choosing the composition of a thin film that will be deposited by Sandia.

66450

Advanced Techniques for Multiobjective Discrete Optimization

J. E. Campbell

A wide variety of practical applications can be modeled as discrete optimization problems. Many of these problems are intractable and require specialized algorithms to obtain even near-optimal solutions within reasonable computing time. Moreover, many such problems must be addressed using several objective functions. Therefore, multicriteria discrete optimization procedures are needed to obtain sets of Pareto optimal solutions. Though such solutions satisfy certain desirable properties (i.e., nondominance), this leads to large sets of solutions that require additional analysis to determine a good subset of Pareto optimal solutions ("best-of-the-best" solutions). Procedures that assess the relative quality of sets of Pareto optimal solutions are needed to address this problem.

Sandia will focus on development of algorithms for obtaining Pareto optimal solutions and on procedures to understand the trade-offs between these solutions. We will then use such results to develop algorithms for post-optimality analysis of Pareto optimal-solution sets. Given a large set of Pareto optimal solutions, we will develop algorithms to obtain sets of "best-of-the-best" Pareto optimal solutions. Because discrete optimization problems cover a wide range of applications, this research has numerous potential applications. The collaboration will be with the University of Illinois.

Many systems, such as future nuclear-power plants, can benefit from this work. Future power plants will incorporate prognostic health and monitoring (PHM) to warn of pending equipment failures and recommend an optimal strategy. An optimal strategy would simultaneously minimize maintenance cost, equipment-failure probability, and replacement cost of electricity. Currently, multiple objectives are combined (e.g., using weights) to a single objective that is optimized. The current approach makes it difficult to satisfy decision makers that the trade-offs are understood. This project seeks to develop solutions that are simultaneously optimal for all objectives so that trade-offs can be studied quickly and easily.

Sandia will focus on development of algorithms for obtaining Pareto optimal solutions and on procedures to understand the trade-offs between these solutions. We will then use such results to develop algorithms for post-optimality analysis of Pareto optimal-solution sets....Many systems, such as future nuclear-power plants, can benefit from this work....This project seeks to develop solutions that are simultaneously optimal for all objectives so that trade-offs can be studied quickly and easily.

66610

Fundamentals of Mobile-Robot Development*J. D. Morrow*

A productive approach to gaining a better understanding of the fundamentals of mobile-robot development is through lectures, exercises, and field research that convey the distinctions of autonomous, rapid-robotic-movement technology, including topics of specialized sensors, mobility, mapping, game theory, high-performance computing, and self-reliant systems. Some applications include space exploration, border security, and desert maneuvers, which motivate mobile robots to operate in barren terrain.

Challenges include boulders, streambeds, slopes, and cliffsides, and these become more difficult to negotiate with increasing speed. The issues and systems that pertain to desert robots are unique, and the technical state of the art is insufficient for the functionality and rigor needed for future systems.

Sandia is performing this work in collaboration with research from Carnegie Mellon University. The relevance to the Department of Energy is to address issues involved with using mobile robots in hostile desert environments that are relevant for security applications.

...a better understanding of the fundamentals of mobile-robot development is through lectures, exercises, and field research that convey the distinctions of autonomous, rapid-robotic-movement technology, including topics of specialized sensors, mobility, mapping, game theory, high-performance computing, and self-reliant systems.

66809

Nonradioactive Safety and Performance Issues with Supercritical Water Reactor (SCWR) Safety Technologies

F. Gelbard

The next generation of nuclear-reactor designs will need to feature enhanced safety, a substantially lower cost of electricity, and minimized waste streams to enhance sustainability. Supercritical light water is being considered as a coolant in a direct-cycle reactor design. This coolant can operate at high temperatures and thus offers thermal-efficiency improvements of over 33% above current operating plants. Because the coolant remains in a single phase, a phase separator is not required; thus, plant design is simplified while building on the extensive and successful experience of current light-water reactors.

Sandia will investigate experimentally three key aspects of this new technology with the same apparatus. First, we will measure the corrosion rates of zircaloy, stainless steel, and inconel in supercritical water. The feasibility of using supercritical water hinges on the corrosion resistance of such metals to the proposed coolant. Second, heat-transfer rates and flow-stability regimes of supercritical fluids have not been accurately determined. Current heat-transfer correlations deviate by over 150% for the same conditions near the critical point. Natural circulation provides a passive cool-down mechanism in the event of pump failure. We will determine natural-circulation flow-stability regimes. Third, an intriguing phenomenon is the rapid depressurization of a supercritical water chamber that may occur in a loss-of-coolant accident transient. Two-phase flow under such conditions is fundamentally different from that in single-phase flow, and we suspect that such flow of a supercritical fluid will act differently than either a single-phase or a two-phase system due to highly nonlinear property variations. This work will help to identify issues associated with such accident scenarios in future supercritical water reactor (SCWR) designs. The collaboration is with the University of Wisconsin.

The work will assist nuclear engineers in the Department of Energy's weapons (National Nuclear Security Administration [NNSA]) and nuclear energy (NE) programs.

Supercritical light water is being considered as a coolant in a direct-cycle reactor design....This work will help to identify issues associated with such accident scenarios in future supercritical water reactor (SCWR) designs.

66810

Radiation Performance Issues with Advanced Coolants for Next-Generation Reactor

D. M. Kunsman

A promising new coolant for nuclear reactors is supercritical water. This coolant is inexpensively made from common water and can be utilized at much higher temperatures than coolants used in existing reactors. The higher-temperature operation capability significantly increases thermal efficiency. Supercritical fluids are used industrially for chemical separations, and data are available on the physical and chemical properties of such fluids. However, the data are incomplete for supercritical water in the presence of high radiation fields. In particular, experiments are needed to establish the rate of radiolysis when supercritical water is exposed to a large neutron source such as the core of a nuclear reactor. In this process, significant amounts of hydrogen can be generated, which is a safety issue.

To measure the rate of radiolysis, Sandia will build an apparatus that will transport supercritical water near the core of the reactor. We will perform the experiment in beam port 2 of the University of Wisconsin's nuclear reactor (UWNR) during full power (1 MW). Developing the apparatus will require satisfying design specifications for the neutronics, the thermal hydraulics. The neutronics analysis will include a model of the UWNR, which will be used to predict the neutron flux field to determine operation parameters and shielding requirements. Similarly, a thermal-hydraulic analysis is needed because of the high temperatures and pressures expected in a small irradiation volume and for small-diameter feed/return lines. To properly understand the pumping requirements, we must also perform a full analysis of the expected pressure drop.

The work will enable nuclear engineers to better serve in the Department of Energy's weapons and nuclear energy programs.

A promising new coolant for nuclear reactors is supercritical water. ...Supercritical fluids are used industrially for chemical separations, and data are available on the physical and chemical properties of such fluids....The work will enable nuclear engineers to better serve in the Department of Energy's weapons and nuclear energy programs.

67716

Smart Detectors of Enrichment of Bioaerosols*D. A. V. Kliner*

Rapid detection of bioaerosols is required for monitoring and protection of critical facilities from a bioagent release. Existing detect-to-warn bioaerosol triggers are sensitive but lack adequate specificity (i.e., high false-positive rate). Sandia is investigating two new approaches to real-time optical detection of bioaerosols that address this problem in a practical manner: laser-induced fluorescence (LiF) and two-dimensional angular optical scattering (TAOS). In the LiF technique, the ultraviolet laser beam excites the aerosols and detects their fluorescence. The TAOS technique entails a laser beam being incident upon the aerosol particle and detecting the elastically scattered light. The angular dependence of the scattered intensity is a function of the particle's size, shape, surface texture, and composition. Thus, with the help of an image-processing routine, the angular distribution of the scattered light could be used to differentiate bioagents from the background environment.

For both of these techniques, we will tune the wavelength of the laser source to increase sensitivity as well as specificity. In LiF, a shorter-wavelength source could greatly improve signal-to-noise ratio. To this end, we will attempt to shift the excitation wavelength from 266 nm to 220 nm. In addition, we will investigate the use of two wavelengths (on and off absorption) in the hope of increasing the specificity of the device even further. As for TAOS, shifting the source into the infrared increases the sensitivity of TAOS to differences in molecular structure. Currently, the plan is to shift into the 3–5 μm window, where atmospheric absorption is low and background noise from blackbody radiation is not overwhelming the signal.

This proposal addresses our Department of Energy/national security mission relevant to homeland security/defense needs. Studies show that providing a sensitive, low-false-positive early-warning system is key to reducing fatalities from a bioagents-release event.

Sandia is investigating two new approaches to real-time optical detection of bioaerosols that address this problem in a practical manner: laser-induced fluorescence (LiF) and two-dimensional angular optical scattering (TAOS). ...This proposal addresses our Department of Energy/national security mission relevant to homeland security/defense needs. Studies show that providing a sensitive, low-false-positive early-warning system is key to reducing fatalities from a bioagents-release event.

68063

Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation

J. C. Hewson, S. R. Tieszen

This research focuses on the computational study of hydrocarbon diffusion flames with emphasis on the modeling of complex chemical kinetics and detailed transport for fuels of practical industrial interest. The work provides knowledge necessary for modeling and analysis of fire environments to directly support Sandia's weapon-safety mission and Sandia's role as a national security laboratory.

The initial stage of previous research examined soot formation in one-dimensional, counterflow, methane-diffusion flames. This research concentrates on modeling the flame structure and pollutant-formation characteristics of diffusion flames using practical aviation fuels such as JP-8. For the current study, we modeled JP-8 as a six-component surrogate blend of well-known hydrocarbons that together mimic the thermophysical properties of the parent fuel. The chemistry of this is modeled with a large, semidetained kinetic mechanism consisting of 260 species participating in 7001 gas-phase reactions. To validate this blend mechanism, we are examining lean, nonsooting counterflow-diffusion flames using the surrogate mixture as well as its individual constituent species as fuels. Individual numerical solutions and calculated and rich extinction limits are compared with experimental data. Although the solution of a counterflow JP-8 surrogate flame is tractable on a single processor, a significant reduction in computational time will be realized through the parallelization of the counterflow flame model on a distributed memory system. The present counterflow model will also be extended to account for soot formation and to predict soot dynamics in JP-8 surrogate flames via a sectional aerosol dynamics model.

This research focuses on the computational study of hydrocarbon diffusion flames with emphasis on the modeling of complex chemical kinetics and detailed transport for fuels of practical industrial interest. The work provides knowledge necessary for modeling and analysis of fire environments to directly support Sandia's weapon-safety mission and Sandia's role as a national security laboratory.

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
11130	Molecular Integrated Microsystems (MIMS)	725	26521	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	203
26508	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	35	26522	A Physically Based Approach to Modeling Ductile Fracture	207
26509	Levitated Three-Axis Microaccelerometer	38	26523	Radiation Aging of Stockpile and Space-Based Microelectronics	210
26510	Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques	40	26524	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	212
26511	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	42	26525	Magnetic-Field Effects on Vacuum-Arc Plasmas	242
26512	Parallel Atomistic Computing for Failure Analysis of Micromachines	100	26526	Microstructural and Continuum Evolution Modeling of Sintering	243
26514	Smart-Sensor Technology for Joint Test Assembly Flights	102	26527	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	246
26515	Multilevel Methods for Nonlinear Structural Mechanics	105	26528	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	248
26516	Algorithmic Support for Commodity-Based Parallel Computing Systems	107	26530	First-Principles Determination of Dislocation Properties	252
26517	Parallel Repartitioning for Optimal Solver Performance	110	26531	Air Sterilization and Decontamination	353
26518	III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies	145	26532	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	355
26519	The Integration of Advanced Photonics and MEMS	148	26534	Advanced Unattended Ground-Sensor Technology	357
26520	Uncertainty Propagation in Models of Thermofluid Systems	200	26535	The Endowment of Simulator Agents with Humanlike Episodic Memory	359

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
26539	Algorithms for Improved Performance in Cryptographic Protocols	361	26557	Specific Anion Nanoengineered Sorbents for Water Purification	471
26540	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	363	26563	Advanced Digital Detectors for Neutron Imaging	546
26543	Adaptive and Mobile Ground Sensors	365	26564	Microfabricated Acoustic Spectrum Analyzer	547
26544	Algorithm Development for Prognostic Health Monitoring and Maintenance	368	26572	Coating Chemical Preconcentrators to Improve Chemical-Agent Collection	550
26545	New Mechanism for Upset of Electronics	371	26574	Detection and Exploitation of Spread-Spectrum Waveforms	552
26546	Flexible Robotic Maintenance Facility	373	26577	Robust Chemometrics for Remote Spectral Sensing	556
26548	Obstacle Detection for Autonomous Navigation	376	26578	Deployable Large-Aperture Optics System for Remote-Sensing Applications	559
26551	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	457	26581	Molecular-Scale Studies of Single-Channel Membrane Pores	71
26552	A Model of Infrastructure Interdependency Using Communication Agents	460	26582	Efficient Massively Parallel Techniques for Protein Structure Generation	73
26553	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	463	26583	Mapping Membrane Protein Interactions in Cell Signaling Systems	75
26554	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	466	27328	A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting	671
26555	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	468	28769	Z-Pinch Power-Plant System Development	324
			28770	Recyclable Transmission Line Concept for Z-Pinch IFE	327

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
28771	Suppression of Electron Emission from Conductors	329	33602	Dispersive Photonics for Next-Generation Sensors and Microsystems	155
28772	Solid-State Switch for Advanced Pulsed Power	332	34465	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	256
28775	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	378	34466	Mechanics and Tribology of MEMS Materials	258
28776	Interfacial Bioscience Grand Challenge (IBIG)	680	34467	Dynamics of Metal/Ceramic Interfaces	262
32574	High-Throughput Instruments, Methods, and Informatics for Systems Biology	78	34468	<i>In Situ</i> Characterization of Soft Solution Processes for Nanoscale Growth	263
32807	Low-Work-Function Material Development for the Microminiature Thermionic Converter	473	34469	Determination of Critical Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	265
32809	Autonomous Microexplosive Subsurface Tracing System	475	34478	LIGA Microsystems Aging: Evaluation and Mitigation	268
32816	Vulnerability Assessment of National Power Grid	477	34485	Science-Based Processing of Field-Structured Composites	271
32817	Molecular Simulations of MEMS and Membrane Coatings (PECASE)	729	34692	Self-Assembly of Polymers in Confined Geometries	732
32913	Aging Mechanisms in Dormant MEMS Structures	150	34693	Building Conscious Machines Based Upon the Architecture of Visual Cortex in the Primate Brain	734
32914	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	83	34698	Microfuze	380
32915	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	254	34699	Exploration of New Multivariate Spectral Calibration Algorithms	274
32923	MEMS in μ Fluid Channels	152	35376	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	736

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
36902	Mathematical Analysis of Deception	739	38618	Arrayed Resonant Subwavelength Gratings	562
36904	A System-Dynamics Approach to Modeling Water Demand	741	38619	Nanoelectromechanical Oscillators (NEMOs) for RF Filtering	162
38605	Microfabrication with Femtosecond-Laser Processing	44	38620	Continuous-Wave Intersubband Terahertz Sources	165
38606	Mesoscale-Controlled Motion for a Microfluidic Drop Ejector	46	38621	Microsystems for Chemical Signature and Reagent Delivery	167
38608	Science-Based Sensing of Phase Transformations in Steels	48	38622	Microfluidic Cellular Sample Pretreatment	169
38609	Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors	86	38623	Automated Visual Direction of Mobile Manipulation	383
38610	Graduated Embodiment for Sophisticated Agent Evolution and Optimization	113	38624	Miniature Fourier-Transform Ion-Mobility Spectrometer for Real-Time Detection and Identification of Explosives and Chemical Agents	385
38611	Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation	115	38625	CONOPS Development for Automated Systems	387
38612	Robust Message Routing for Mobile (Wireless) <i>Ad Hoc</i> Networks	118	38626	Rapid Mitigation and Decontamination of Toxic Industrial Chemicals	389
38613	Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods	120	38627	EM Interactions with Systems to Enhance Security	392
38614	Micromagnetic Suspension	122	38628	Adaptive Awareness for Personal and Small-Group Decision Making	394
38615	Sensitivities for Large-Scale Simulation Codes	124	38629	Use of Seismic and Acoustic Responses to Assess Bomb Damage to Underground Facilities	396
38616	Engineered Superconductivity in Electron-Hole Bilayers	157			
38617	Silicon-Based RF MEMS Components	160			

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
38655	Free-Space Electrooptic Sampling and Remote Mapping of Electromagnetic Fields from Emitting Structures Using Femtosecond Terahertz Transceivers	399	38677	Potential Application of Microsensor Technology in Radioactive-Waste Management—With Emphasis on Headspace Gas Detection	502
38659	Information Assurance for Wireless <i>Ad Hoc</i> Networks	401	38678	Surety Enhancement for Wireless Automated-Control Networks	504
38662	Natural-Gas Production Problems: Solutions, Methodologies, and Modeling	480	38679	Advanced Nuclear Engineering Analysis Technology	506
38664	High-Efficiency Turbine Blade Coatings	483	38681	Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies	565
38665	Time-Domain Reflectometry for Remote, Real-Time Water-Quantity/-Quality Monitoring of Perennial and Ephemeral Streams	486	38682	Multiscale Thermal Modeling	215
38667	Research and Development of Mathematical Algorithms to Define and Quantify Critical-Infrastructure Interdependencies	489	38684	A Robust, Coupled Approach for Atomistic-Continuum Simulation	218
38668	Functionalized Nanoelectrode Arrays for <i>In Situ</i> Identification and Quantification of Regulated Chemicals in Water	491	38685	Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications	220
38669	Hybrid Infrastructure Cryptography	404	38686	High-Fidelity Frictional Models for MEMS	222
38672	Validated Modeling of Distributed Energy Resources at Distribution Voltages	494	38687	Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames	225
38673	Water Desalination	496	38688	The Basics of Aqueous Nanofluidics: “Interphase” Structure and Surface Forces	278
38674	Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps	499	38689	Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices	282
			38690	Photocontrol of Nanointeractions in Microsystems	284

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
38691	Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines	287	38707	Microfabricated Dielectrophoretic Sample-Preparation System	589
38692	Nanostructured Materials for Directed Transport of Excitation Energy	289	38708	Automation of Microelectronic Physical Analysis	592
38693	Modeling Local Chemistry in the Presence of Collective Phenomena	291	38712	Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection	595
38695	Passive-Legged, Multisegmented, Robotic Vehicle	568	38713	Secure MPLS Control Plane for Internet Connectivity	597
38696	Low-Cost Photonic Lattice Structures for Remote Sensing	571	38717	Nanoscale Energetic Materials by Inverse Micellar Synthesis	744
38698	Security Monitoring and Management with Information Technology (SUMMIT)	573	38718	Modeling of Rock Penetration	747
38699	Novel Methods for Ultracompact, Ultralow-Power Communications	575	38722	Agile, Microsystems-Enabled Receiver	600
38701	Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	577	38744	Adaptive Network Countermeasures	346
38702	A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	580	39017	Solution-Based Nanoengineering of Materials	296
38703	Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets	584	39212	MEMS-Based Electromechanical Acoustic-Energy Harvester	750
38705	The Effects of Varying Humidity on Copper-Sulfide Film Formation	293	39669	Determination of Microstructural Properties with Isentropic Compression	334
38706	Detecting and Tracking the Active Insider Using 3-D Detection Technology	587	39670	Simulations of Intense Petawatt Laser Pulses with Dense Z-Pinch Plasmas	336
			41193	Biomicrofuel Cell	685
			41194	Augmented Cognition: Next-Generation Intelligent Systems	687
			41427	Predicting and Validating MEMS Interface Reliability	753

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
41674	Microengine for Advanced Power Generation	349	49770	Frameworks for Nuclear Process Transparency and Control	509
41726	Direct Simulation of Solid-Fluid Systems	756	49772	Studies on the Disbonding Initiation of Interfacial Cracks	782
42461	Support-Active Site Interactions in Heterogeneous Catalysts	758	49915	Critical Technology Development for Hard Target Defeat High-G-Tolerant Fuze and High Explosives	407
42483	An Analysis of the Automotive Industry as a Source for Weapon Components and Manufacturing Processes	760	50065	TALON	690
44136	Fluid-Structural Interactions in Wetting and Penetration into Porous Media	762	50396	Compliant Membranes for MEMS Microphones	784
45279	Macroscopic Rates, Microscopic Observations, and Molecular Models of the Dissolution of Carbonate Phases	765	50717	Multiscale Experimental/Numerical Study	786
46070	High-Speed Micro-EDM	768	50772	Cellular Observatory: Simultaneous Time- and Frequency-Resolved Microscopy	89
46685	Nanoscale Hotspots Due to Nonequilibrium Thermal Transport	770	52174	Inelastic Deformation Mechanism in Shocked-Sapphire Single Crystals	788
46686	Microexternal Combustion Engine: The P3 Engine Prototype	773	52523	Atomic-Layer Deposition of Highly Conformal Tribological Coatings	51
47517	Mathematical and Algorithmic Issues in Multiphysics Couplings	775	52524	Assembly of Microsystems Using Exothermic Multilayer Thin Films	54
47795	Lipid Membranes on Nanostructured Silicon	778	52526	Intelligent Interaction Control as Applied to Metrology and Assembly of Microscale Components	57
48746	Digital Signal Processing for Acoustic-Seismic Target Identification	603	52527	Rapid-Prototyping High-Density Circuitry (RpHdc)	59
49769	Resin Infusion Between Double Flexible Tooling	780	52528	Elucidating the Mysteries of Wetting	61
			52530	Next-Generation Spindles for Micromilling	64

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
52531	Assembly and Actuation of Nanomaterials Using Active Biomolecules	300	52544	Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security	136
52532	Modeling Biomembranes	91	52546	Massively Parallel Linear Programming	139
52533	Reverse-Engineering Biological Networks: Applications in Immune Responses to Bioterrorism Threats	93	52548	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics	172
52536	High-Throughput Identification of Molecular Machines Involved in Membrane Signaling and Toxin Pathways	96	52549	Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia's MDL and BAE Systems	174
52537	Coupled Solid-Fluid Mechanical-Computational Modeling of Fracture and Fragmentation in Geomaterials, Such as Hard and Deeply Buried Targets (HDBTs)	228	52551	Functionalized Nanoparticles for Sensor Applications	176
52538	Sequestration of Pathogens on Nanoengineered Surfaces	790	52552	Novel <i>In Situ</i> Mechanical Testers to Enable Integrated Metal Surface Micromachines	178
52539	A Combined Preconcentrator and Sensor for Live Waterborne Pathogens	793	52553	Compliant Thermomechanical MEMS Actuators	181
52540	IP Storage: A Performance and Security Study	126	52554	An Integrated, Stacked System-on-a-Chip	183
52541	A Parallel Circuit Simulator for Cell Biology	129	52555	Micromass Spectrometer-on-a-Chip	185
52542	Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions	131	52556	Quantum Coherence in Semiconductor Nanostructures for Improved Lasers and Detectors	187
52543	Robust Large-Scale Parallel Nonlinear Solvers for Simulations	134	52557	MOSFET–MEMS Integration	189
			52566	Microoptical Gyroscope Via Monolithic Active/Passive Optical Integration	191

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
52570	Materials Physics and Device Development for Improved Efficiency of GaN HEMT High-Power Amplifiers	193	52588	System-of-Systems Modeling and Analysis	432
52571	Leaky-Mode VCSELs for Photonic Logic Circuits	195	52589	Eye-Safe Short-Range Standoff Aerosol-Cloud Finder	434
52575	Advanced Polychromator Systems for Remote Chemical Sensing	197	52590	Micro Flame-Based Detector Suite for Universal Gas Sensing	437
52577	Immunological Basis for High-Reliability Systems Control	409	52591	Beyond Nanoparticles—Attack on a Chemical “Holy Grail”	511
52579	Miniaturization of SAR Electronic Assembly Using Sandia’s Integrated Substrate Technology	411	52592	Advanced Proton-Exchange Materials for Energy-Efficient Fuel Cells	513
52580	Moving-Target Identification Using Ultrahigh-Range-Resolution Data	413	52593	Alanate-Hydride Fuel-Cell Demonstration Project	515
52581	Advanced Mobile Networking, Sensing, and Controls Using Graph Theory	416	52594	Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process	517
52582	Compact Terahertz (THz) Sources for Emerging Threats Applications	418	52595	Real-Time Discriminatory Sensors for Water-Contamination Events	519
52583	Understanding Communication in Counterterrorism Crisis Management	420	52596	Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors	522
52584	Hypervelocity Impact-Generated Flash	422	52597	Securing Mobile Code	524
52585	Improving Human/System Interactions in Systems-of-Systems	425	52598	Novel Catalysts for Hydrogen Fuel-Cell Applications	527
52586	Distributed Detection and ID Algorithm Architecture for Unattended Ground Sensors	428	52606	Linking Optimization and Simulation in Critical Infrastructure Systems	530
52587	Secure Chaotic Communications	430	52608	The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water	533

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
52609	Analysis of Nanoscale Films and Particles	232	52708	Zero-Power Radio Receiver	608
52611	Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices	234	52709	Completely Passive Microwave Tag	610
52613	Tensegrity—Smart, Adaptive Structures Through Material Biomimicry	236	52710	Security Coatings for Multichip Modules	612
52615	Coupled Acoustical/Structural Simulations of Weapons Systems	239	52711	Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces	614
52698	Decomposition of Contaminants Using Photochemically Active Nanoparticles	303	52712	Content-Based Video and Image Indexing System	616
52699	Thermally Cleavable Surfactants	305	52713	Bioaerosol Collection and Concentration for Microseparations-Based Detectors	618
52700	Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions	307	52714	Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains	621
52701	Quantification of Environments and Surfaces Within Micropackages	309	52716	Joint Authentication/Encryption	623
52702	Assembly of Ordered Electrooptical and Bioactive Materials and Composites	312	52717	Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications	625
52703	Advanced Packaging/Joining Technology for Microsystems	315	52718	Leveraging Robotic Planning for Physical-Security Analysis	627
52705	Magnetostrictive Elastomers for Actuators and Sensors	319	52719	Buzzard	629
52706	Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons	605	52720	Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction	631
52707	Active Network and Use of Network Processor	607	52721	Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment	633
			52722	Radiation-Hardened Optoelectronic Components for Space-Based Applications	635

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
52723	Novel Micropreconcentrators for CW, Explosives, and Water Surety	637	52738	Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators	341
52724	Ion-Mobility Spectrometer/Mass Spectrometer	640	52739	Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions	343
52725	Cryptographic Assurance of Execution Correctness and Confidentiality	642	52740	A Microbioreactor for Hydrogen Production	813
52726	Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts	645	52741	Self-Organizing Software Research and Development	816
52727	Predictive Accelerated Aging of Microsystems: The Science of Dormancy	795	52742	Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	819
52728	Surety and Accountability Enhancements for Storage Containers	798	52743	Computational Model of a Microbial Cell	821
52729	Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	801	52744	Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents	823
52730	Advanced Packaging Technology for Optical Firesets	804	52745	A Biological Model for Controlling Interface Growth and Morphology	825
52731	Miniature Transmitter Filter for JTA Using LIGA Technology	807	52746	Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions	827
52732	Novel and Robust Environmental Sensing Devices (ESDs)	809	52747	Ornithopter	830
52733	Advanced Neutron Monitors for JTA and Stockpile Monitoring	811	52748	Light-Powered Nanovehicles	832
52737	Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating	338	52749	Anomalously High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source	834
			52750	Quantum Computing Accelerator I/O	836
			52797	Design and Control of the Magnetic Properties of Nanoparticles	838

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
52825	Aerospace Vehicle Trajectory Optimization System by Primer Vector Methods	840	53590	Electrical Conductivity of Metal Alloys	865
52826	Algorithm Development for Smart Antennas	842	53591	Hydrogen Futures Dynamic-Simulation Model	535
52976	Failure Analysis and Surety Design of Composite Patching Systems	844	53681	Design of Biospecific Surfaces to Control Specific Cellular Responses	867
52977	Flow Control and Mixing in Microfluidic Devices	847	53682	High-Field Effects of GaN HEMTs	869
53372	Topological Layout for the Optimal Design of Electrostatically Actuated MEMS	849	54210	Cognitive Models Applied to Human Effectiveness in National Security Environments	871
53464	Atomic-Scale Scanning-Tunneling Microscopy Measurements of Nucleation and Growth of Ge/Si Alloy Structures	851	54211	Nanomagnetic Films	872
53465	Micro-/Nanoscale Thermomechanical Manufacturing	853	54213	A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites	875
53585	Novel Diagnostics for Rarefied Flows in MEMS Applications	855	55079	Near-Real-Time Characterization for Assured HDBT Defeat	693
53586	Geophysical Subsurface Imaging and Interface Identification	857	55086	Prompt Global Response	696
53587	Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer	859	55087	Winning the War: A Systems Approach to Defending Our Borders	699
53588	Miniature High-Power RF Components Enabled by Mesoscale Manufacturing	861	57300	Integrated Superhard and Metallic Coatings for MEMS	877
53589	Electron- and Proton-Beam Directed-Energy Defense Weapons	863	57307	Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials	880
			57308	Friction in Micromachine Interfaces	883
			57309	Lipid Microarray Biosensor for Biotoxin Detection	885
			57310	Advanced Manufacturing Techniques Using Rapid Prototyping	887

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
57311	Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems	888	62270	Assessment of Information Flow Associated with Goods and People Crossing International Borders	708
58336	Surfactant Effects on Lateral Growth and Surface Morphology of GaAs	890	62826	Automatic Detection of Anomalous Weapon Surveillance Waveforms	710
58907	Active Photonic Nanostructures	321	62827	Nonlethal Technologies for the War on Terrorism	702
59034	3-D Large-Eddy Simulation of Turbulent Flow Based on One-Dimensional Turbulence	892	62970	Computational Social Dynamic Modeling of Groups Perpetrating Violence	712
59916	A Method of Evaluating Research Using New Innovation, Risk, and Impact Indicators	141	62971	Development of a Terrorist-Activity Plan-Assessment Methodology	714
60626	The Derivation and Implications of “Nearly Noninformative” Priors from Metadata Conditioning	894	62972	Development of an Interactive Nuclear/WMD Terrorist Data Model	716
60627	New Seismic-Event-Detection Technology	897	63965	Hyperspectral Tagging for Unique Identification	647
60628	Dynamic-Simulation Modeling and Analysis Support for Senate Energy and Natural Resources Committee	537	63966	Smart Decoy Sensor Network	441
60866	SDAC Architectural Study and Demonstration System Development	705	63967	Fusing MSI and HSI Imagery for Subpixel Spectral Unmixing	649
61045	Testing Recent Metal-/Oxide-Joining Discoveries in NW Component Manufacturing	899	63968	Monomolecular Carbon Nanowire Fabrication	443
61046	Photonic Encryption Using All-Optical Logic	901	63969	Reliability Data to Improve High-Magnetic-Field Coil Design for High-Velocity Coilguns	445
61047	Automated Video Screening for Unattended Background Monitoring in Dynamic Environments	904	63970	Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities	448
62269	Nanoporous-Carbon Adsorbers for Chemical Microsensors	906	63971	Enabling Technology for Human Collaboration	718
			63972	Molecular Electronics Test Platform	908

Appendix A: Project Number/Title Index

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
64214	Study of 3-D Focal-Region Sounding Applied to Large-Aperture Telescopes	652	65559	Direct Single-Ion Machining of Nanopores	916
64215	Affordable, Automated Computed Tomography (CT) X-Ray Screening for Large Vehicle Bombs Preliminary Study	655	65828	Measures of Effectiveness and Performance for MicroTalon SDAC Technologies and Systems	454
64355	Coordinated Weapon-Platform Control Strategies for Intelligent Targeting	657	66159	Creative Networking of Commercial Products	666
64356	Advanced Weapons Signatures	659	66160	Networked Device Demonstration	667
64385	Universal Detection for Chem-Bio Sensing in Microfluidic Systems	662	66161	Analysis of Multichannel Internet Messaging	669
64386	Large-Scale System-Dynamics Modeling of Water Resources on the Rio Grande	721	66170	Investigation of the Effects of Intense Pulsed-Particle Beams on the Durability of Metal-to-Plastic Interfaces	918
64709	Development of Highly Integrated Magnetically and Electrostatically Actuated Micropumps	910	66233	Efficacy of the Sandia Decon Formulation on the SARS Coronavirus	543
64711	Wide-Area Surveillance in Synthetic- Aperture Radar Images	451	66450	Advanced Techniques for Multiobjective Discrete Optimization	920
64811	Agent-Based Control of Distributed Infrastructure Resources	539	66610	Fundamentals of Mobile-Robot Development	921
65148	Multipurpose Locator-Tag System	664	66809	Nonradioactive Safety and Performance Issues with Supercritical Water Reactor (SCWR) Safety Technologies	922
65556	A Robotic Framework for Semantic Concept Learning	911	66810	Radiation Performance Issues with Advanced Coolants for Next-Generation Reactor	923
65557	Optical Trapping of Collisionally Cooled Molecules	541	67542	Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application	722
65558	Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems	912			

<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>	<i>Project Number</i>	<i>Title</i>	<i>Page Number</i>
67716	Smart Detectors of Enrichment of Bioaerosols	924			
68063	Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation	925			
68552	Investigation of Bioprocesses for Advanced Manufacturing Applications	66			

Appendix B: Awards/Recognition List

<i>Awards/Recognition</i>	<i>Project Number</i>	<i>Project Title</i>
R&D 100 Award, 2003, “Isolated Cast-in-Place Microvalves”	11130	Molecular Integrated Microsystems (MIMS)
Outstanding Paper— NSREC 2003 Conference	26523	Radiation Aging of Stockpile and Space-Based Microelectronics
Professional Achievement in Ceramic Engineering Award, from American Ceramic Society and National Institute of Ceramic Engineers: Veena Tikare	26526	Microstructural and Continuum Evolution Modeling of Sintering
Student Poster Award, Center for Micro-engineered Materials (CMEM) Semi-annual Industrial Advisory Board Meeting	26528	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance
Humboldt Fellow Award from the Humboldt Foundation, sponsored by the German Government: Weng Chow	27328	A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting
Election as a Fellow of the American Physical Society: Mike Coltrin		
2004 Bomem-Michelson Award: David M. Haaland	32574	High-Throughput Instruments, Methods, and Informatics for Systems Biology
Robocasted Lattice Structures selected as One of Best New Materials Developments in 2002 by <i>Chemical and Engineering News</i>	38674	Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps
Poster Award from the Microscopy Society of America (MSA): Michael Campin	38705	The Effects of Varying Humidity on Copper-Sulfide Film Formation
John Manson Student Research Award, Society of Plastic Engineers	49772	Studies on the Disbonding Initiation of Interfacial Cracks
Best Paper in Session (TECHCON 2003)—Semiconductor Research Corporation		
Election as a Fellow of the American Physical Society: Dr. Shawn-Yu Lin	52548	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics

Appendix B: Awards/Recognition List

<i>Awards/Recognition</i>	<i>Project Number</i>	<i>Project Title</i>
NUE awarded to Texas A&M for Nanoscale Issues in Manufacturing, by the National Science Foundation	54211	Nanomagnetic Films
Scanning Hall Probe Microscope for Nanomagnetism Research and Student Training, given to Texas A&M University by the National Science Foundation		
First-place poster competition at 1 st Annual TiiMS-URETI Review Meeting from Texas Institute for Intelligent Bio-Nano Materials and Structures for Aerospace Vehicles	54213	A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites
Outstanding Young Scientist or Engineer, 2003 Women of Color Research Science and Technology Award, Career Communications Group, Inc.	65558	Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Project Title	Project #	Refereed Publications	All Other Reports and Publications	Patent Disclosures	Patent Applications	Patents	Copyrights	Students	Post-docs	Permanent Staff Hired*	Awards	New Non-LDRD-Funded Projects†	% Milestones Completed	Goals Status**	Hypotheses Status***
Molecular Integrated Microsystems (MIMS)	11130	7	14	5	5				1		1		80%	2	7
Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508			1						1			80%	2	6
Levitated Three-Axis Microaccelerometer	26509												50%	3	7
Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques	26510	2	1	1	2	1		1					90%	1	7
Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511		1					2					100%	1	7
Parallel Atomistic Computing for Failure Analysis of Micromachines	26512												80%	3	7
Smart-Sensor Technology for Joint Test Assembly Flights	26514		1					1					90%	2	6
Multilevel Methods for Nonlinear Structural Mechanics	26515	2	2										90%	2	6
Algorithmic Support for Commodity-Based Parallel Computing Systems	26516						2	1					100%	1	7
Parallel Repartitioning for Optimal Solver Performance	26517	11					1	2					90%	1	6
III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies	26518	5	5										90%	1	7
The Integration of Advanced Photonics and MEMS	26519	1		2									90%	1	6
Uncertainty Propagation in Models of Thermofluid Systems	26520	5	7						1				60%	3	8
Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521	8						1					100%	1	7
A Physically Based Approach to Modeling Ductile Fracture	26522	4											90%	2	7
Radiation Aging of Stockpile and Space-Based Microelectronics	26523	1									1		90%	2	8
Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524	4	3										85%	4	9
Magnetic-Field Effects on Vacuum-Arc Plasmas	26525												100%	2	8
Microstructural and Continuum Evolution Modeling of Sintering	26526	4	2				1	2		1	1		100%	1	6
Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527							1	1				90%	3	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment		
Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528	1	8	2				4	1		1	90%	1	6
First-Principles Determination of Dislocation Properties	26530	3							1			100%	1	6
Air Sterilization and Decontamination	26531			1								80%	2	7
Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532											70%	4	6
Advanced Unattended Ground-Sensor Technology	26534											70%	3	8
The Endowment of Simulator Agents with Humanlike Episodic Memory	26535				1							100%	1	7
Algorithms for Improved Performance in Cryptographic Protocols	26539			1	1			3				100%	1	6
Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	26540	4	1		3			2				95%	1	6
Adaptive and Mobile Ground Sensors	26543							3				95%	2	6
Algorithm Development for Prognostic Health Monitoring and Maintenance	26544	1	1		1							90%	2	8
New Mechanism for Upset of Electronics	26545	1										100%	2	6
Flexible Robotic Maintenance Facility	26546		1	1								100%	1	8
Obstacle Detection for Autonomous Navigation	26548							2				100%	1	6
Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	26551	4	3	1				2	4			95%	1	6
A Model of Infrastructure Interdependency Using Communication Agents	26552		3									100%	1	6
Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	26553	10	2	8	7			3	2	1		100%	1	6
Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554	5		1	2					5		100%	1	6
Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555	2	2									40%	3	7
Specific Anion Nanoengineered Sorbents for Water Purification	26557			2				2				100%	1	6
Advanced Digital Detectors for Neutron Imaging	26563			2	1	1						85%	3	6
Microfabricated Acoustic Spectrum Analyzer	26564			1	1			2				90%	2	7
Coating Chemical Preconcentrators to Improve Chemical-Agent Collection	26572			1								100%	3	6
Detection and Exploitation of Spread-Spectrum Waveforms	26574		13					2				100%	1	6
Robust Chemometrics for Remote Spectral Sensing	26577	1	8	2						1		90%	2	8
Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578		1	1	1			2	1	2		95%	2	7

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment		
Advanced Nuclear Engineering Analysis Technology	38679							3				90%	11	8
Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies	38681	5				2						85%	3	6
Multiscale Thermal Modeling	38682	3	2					1	1			100%	1	7
A Robust, Coupled Approach for Atomistic-Continuum Simulation	38684	2						2	2			75%	3	7
Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications	38685											50%	3	7
High-Fidelity Frictional Models for MEMs	38686	3	4					1	1			90%	1	7
Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames	38687		1						2			80%	2	7
The Basics of Aqueous Nanofluidics: "Interphase" Structure and Surface Forces	38688	11	16						1			90%	2	7
Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices	38689											100%	1	6
Photocontrol of Nanointeractions in Microsystems	38690								3	2		50%	3	7
Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines	38691		2									75%	2	7
Nanostructured Materials for Directed Transport of Excitation Energy	38692							2	3			75%	2	7
Modeling Local Chemistry in the Presence of Collective Phenomena	38693	1	1									85%	1	7
Passive-Legged, Multisegmented, Robotic Vehicle	38695							1				66%	3	6
Low-Cost Photonic Lattice Structures for Remote Sensing	38696	1		5	1				1			50%	4	7
Security Monitoring and Management with Information Technology (SUMMIT)	38698											100%	1	6
Novel Methods for Ultracompact, Ultralow-Power Communications	38699			1								85%	1	6
Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	38701		1					3	1			90%	1	6
A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	38702	3										80%	2	8
Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets	38703											100%	2	6
The Effects of Varying Humidity on Copper-Sulfide Film Formation	38705	3	1					1			1	80%	2	7
Detecting and Tracking the Active Insider Using 3-D Detection Technology	38706		1							2		100%	1	6
Microfabricated Dielectrophoretic Sample-Preparation System	38707	7	4									100%	1	6
Automation of Microelectronic Physical Analysis	38708	1						2				70%	3	7
Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection	38712								1	1		80%	2	9

[illegible]

Appendix C: Project Performance Measures

[illegible]

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment		
Distributed Detection and ID Algorithm Architecture for Unattended Ground Sensors	52586											100%	1	7
Secure Chaotic Communications	52587											100%	2	7
System-of-Systems Modeling and Analysis	52588											90%	2	7
Eye-Safe Short-Range Standoff Aerosol-Cloud Finder	52589											70%	3	7
Micro Flame-Based Detector Suite for Universal Gas Sensing	52590	1		3	1	1		2		1		90%	2	7
Beyond Nanoparticles—Attack on a Chemical “Holy Grail”	52591								1			80%	3	7
Advanced Proton-Exchange Materials for Energy-Efficient Fuel Cells	52592							1	1			92%	1	7
Alanate-Hydride Fuel-Cell Demonstration Project	52593							1				90%	2	7
Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process	52594											45%	3	7
Real-Time Discriminatory Sensors for Water-Contamination Events	52595		1									95%	1	7
Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors	52596	3		1			1	1	1			100%	1	7
Securing Mobile Code	52597							1				100%	1	7
Novel Catalysts for Hydrogen Fuel-Cell Applications	52598	5		1				1	1			80%	3	7
Linking Optimization and Simulation in Critical Infrastructure Systems	52606	1							1			100%	1	7
The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water	52608			2	1					1		90%	2	6
Analysis of Nanoscale Films and Particles	52609											75%	3	7
Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices	52611											100%	1	10
Tensegrity—Smart, Adaptive Structures Through Material Biomimicry	52613							1				100%	1	8
Coupled Acoustical/Structural Simulations of Weapons Systems	52615									3		80%	3	7
Decomposition of Contaminants Using Photochemically Active Nanoparticles	52698			1				1	1			90%	1	7
Thermally Cleavable Surfactants	52699		2	2								100%	1	6
Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions	52700											83%	2	7
Quantification of Environments and Surfaces Within Micropackages	52701											100%	2	7
Assembly of Ordered Electrooptical and Bioactive Materials and Composites	52702	2							2			100%	1	6

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)										Project Qualitative Assessment		
Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	52729	12		1								95%	1	7
Advanced Packaging Technology for Optical Firesets	52730											100%	1	7
Miniature Transmitter Filter for JTA Using LIGA Technology	52731											90%	2	8
Novel and Robust Environmental Sensing Devices (ESDs)	52732				2							85%	3	7
Advanced Neutron Monitors for JTA and Stockpile Monitoring	52733						2					90%	2	7
Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating	52737		1	1			2					80%	3	7
Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators	52738		1									80%	3	7
Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions	52739		2									80%	2	8
A Microbioreactor for Hydrogen Production	52740											60%	3	7
Self-Organizing Software Research and Development	52741	2		3					1			100%	1	6
Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	52742											75%	3	9
Computational Model of a Microbial Cell	52743											50%	3	7
Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents	52744	1										40%	4	7
A Biological Model for Controlling Interface Growth and Morphology	52745											70%	3	8
Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions	52746	1					2	2				95%	2	6
Ornithopter	52747											50%	3	10
Light-Powered Nanovehicles	52748	1		1			1	1				90%	2	7
Anomalously High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source	52749						1	1				50%	3	8
Quantum Computing Accelerator I/O	52750											95%	2	7
Design and Control of the Magnetic Properties of Nanoparticles	52797	4										100%	1	6
Aerospace Vehicle Trajectory Optimization System by Primer Vector Methods	52825	1					1					67%	3	7
Algorithm Development for Smart Antennas	52826											100%	1	7
Failure Analysis and Surety Design of Composite Patching Systems	52976		2				1					75%	2	7
Flow Control and Mixing in Microfluidic Devices	52977	1	1									100%	1	7
Topological Layout for the Optimal Design of Electrostatically Actuated MEMS	53372						1					100%	1	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Atomic-Scale Scanning-Tunneling Microscopy Measurements of Nucleation and Growth of Ge/Si Alloy Structures	53464							1					85%	2	7
Micro-/Nanoscale Thermomechanical Manufacturing	53465	1	1										100%	1	7
Novel Diagnostics for Rarefied Flows in MEMS Applications	53585												85%	2	7
Geophysical Subsurface Imaging and Interface Identification	53586												85%	2	7
Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer	53587	1	1					1					100%	1	7
Miniature High-Power RF Components Enabled by Mesoscale Manufacturing	53588			1									70%	3	8
Electron- and Proton-Beam Directed-Energy Defense Weapons	53589				3								60%	3	8
Electrical Conductivity of Metal Alloys	53590							1		1			95%	1	6
Hydrogen Futures Dynamic-Simulation Model	53591								1				90%	1	7
Design of Biospecific Surfaces to Control Specific Cellular Responses	53681	1						1					90%	1	7
High-Field Effects of GaN HEMTs	53682												70%	3	10
Cognitive Models Applied to Human Effectiveness in National Security Environments	54210							1					50%	3	9
Nanomagnetic Films	54211	1	4					1			2		100%	1	7
A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites	54213		1					1			1		50%	1	7
Near-Real-Time Characterization for Assured HDBT Defeat	55079							3	1				90%	1	7
Prompt Global Response	55086							1					95%	1	7
Winning the War: A Systems Approach to Defending Our Borders	55087	1			1			4		1			100%	1	7
Integrated Superhard and Metallic Coatings for MEMS	57300	6											90%	1	6
Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials	57307	1						1					100%	1	7
Friction in Micromachine Interfaces	57308							1					100%	1	7
Lipid Microarray Biosensor for Biotxin Detection	57309							1					100%	1	6
Advanced Manufacturing Techniques Using Rapid Prototyping	57310												100%	1	7
Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems	57311	2		2				1					100%	2	7
Surfactant Effects on Lateral Growth and Surface Morphology of GaAs	58336	2	2					1					100%	1	7

Appendix C: Project Performance Measures

		Performance Statistics (Number of)											Project Qualitative Assessment		
Active Photonic Nanostructures	58907	4							2	1			85%	2	7
3-D Large-Eddy Simulation of Turbulent Flow Based on One-Dimensional Turbulence Modeling	59034		1										100%	1	7
A Method of Evaluating Research Using New Innovation, Risk, and Impact Indicators	59916	1											80%	2	7
The Derivation and Implications of “Nearly Noninformative” Priors from Metadata Conditioning	60626							2					75%	3	8
New Seismic-Event-Detection Technology	60627		1				1						75%	3	7
Dynamic-Simulation Modeling and Analysis Support for Senate Energy and Natural Resources Committee	60628								1				90%	2	7
SDAC Architectural Study and Demonstration System Development	60866	1	1					4		1			85%	1	6
Testing Recent Metal-/Oxide-Joining Discoveries in NW Component Manufacturing	61045												95%	2	6
Photonic Encryption Using All-Optical Logic	61046							2					90%	2	7
Automated Video Screening for Unattended Background Monitoring in Dynamic Environments	61047												100%	1	6
Nanoporous-Carbon Adsorbers for Chemical Microsensors	62269	1											80%	2	7
Assessment of Information Flow Associated with Goods and People Crossing International Borders	62270												100%	1	6
Automatic Detection of Anomalous Weapon Surveillance Waveforms	62826		1				1						100%	1	6
Nonlethal Technologies for the War on Terrorism	62827												80%	3	7
Computational Social Dynamic Modeling of Groups Perpetrating Violence	62970							2					95%	1	6
Development of a Terrorist-Activity Plan-Assessment Methodology	62971												70%	4	8
Development of an Interactive Nuclear/WMD Terrorist Data Model	62972												70%	3	7
Hyperspectral Tagging for Unique Identification	63965												100%	2	8
Smart Decoy Sensor Network	63966												100%	1	6
Fusing MSI and HSI Imagery for Subpixel Spectral Unmixing	63967							2					90%	2	7
Monomolecular Carbon Nanowire Fabrication	63968		1										100%	1	7
Reliability Data to Improve High-Magnetic-Field Coil Design for High-Velocity Coilguns	63969												100%	1	7
Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities	63970												100%	3	8
Enabling Technology for Human Collaboration	63971		3	1				2					100%	1	8
Molecular Electronics Test Platform	63972	1		1				1					100%	1	8

Appendix C: Project Performance Measures

[illegible]

Appendix C: Project Performance Measures

		Performance Statistics (Number of)												Project Qualitative Assessment		
Smart Detectors of Enrichment of Bioaerosols	67716													0%		
Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation	68063													0%		
Investigation of Bioprocesses for Advanced Manufacturing Applications	68552		2											95%	2	7
		413	345	153	82	18	17	247	105	69	17	0				

† Identification of new non-LDRD-funded projects is now completed in the fiscal year following the annual report.

* Permanent Staff Hired. Laboratories operate under manpower cap. There are no increases in permanent staff.

**** Goals Status**

- 1 - Goals Met
- 2 - Goals Substantially Met
- 3 - Goals Partially Met
- 4 - Goals Substantially Modified
- 5 - Goals Not Met
- 11 - Project Terminated

*****Hypothesis Status**

- 6 - Hypotheses Proved
- 7 - Hypotheses Remains Unchanged
- 8 - Hypotheses Modified
- 9 - Hypotheses Redefined
- 10 - Hypotheses Disproved
- 11 - Project Terminated

****These projects represent university fellowships and are not included in the totals.

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
725	Molecular Integrated Microsystems (MIMS)	11130							•					•		•					
35	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508							•					•			•		•		
38	Levitated Three-Axis Microaccelerometer	26509	•	•					•										•		
40	Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques	26510											•	•							
42	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511	•	•					•					•		•	•	•	•		
100	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512		•	•											•					
102	Smart-Sensor Technology for Joint Test Assembly Flights	26514		•	•														•		
105	Multilevel Methods for Nonlinear Structural Mechanics	26515		•	•	•															
107	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516			•																
110	Parallel Repartitioning for Optimal Solver Performance	26517		•	•																
145	III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies	26518	•		•	•	•	•	•	•	•	•		•			•	•	•	•	
148	The Integration of Advanced Photonics and MEMS	26519										•		•							
200	Uncertainty Propagation in Models of Thermofluid Systems	26520	•	•	•		•														
203	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521	•	•			•							•							
207	A Physically Based Approach to Modeling Ductile Fracture	26522	•	•	•											•					
210	Radiation Aging of Stockpile and Space-Based Microelectronics	26523	•	•		•		•	•					•							
212	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524		•																	
242	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525	•	•	•																
243	Microstructural and Continuum Evolution Modeling of Sintering	26526		•												•					

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
246	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527														•					
248	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528	•						•					•		•			•		
252	First-Principles Determination of Dislocation Properties	26530		•												•					
353	Air Sterilization and Decontamination	26531																			•
355	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532							•												•
357	Advanced Unattended Ground-Sensor Technology	26534						•	•										•		•
359	The Endowment of Simulator Agents with Humanlike Episodic Memory	26535		•			•	•	•										•		
361	Algorithms for Improved Performance in Cryptographic Protocols	26539						•	•												
363	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	26540							•					•							•
365	Adaptive and Mobile Ground Sensors	26543							•										•		
368	Algorithm Development for Prognostic Health Monitoring and Maintenance	26544		•															•		
371	New Mechanism for Upset of Electronics	26545	•					•													
373	Flexible Robotic Maintenance Facility	26546		•													•		•		
376	Obstacle Detection for Autonomous Navigation	26548																	•		
457	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	26551														•		•			
460	A Model of Infrastructure Interdependency Using Communication Agents	26552	•	•																	
463	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	26553												•						•	
466	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554														•				•	

[illegible]

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
380	Microfuze	34698									•			•							•
274	Exploration of New Multivariate Spectral Calibration Algorithms	34699	•		•				•		•			•		•		•		•	
736	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	35376		•										•		•					
739	Mathematical Analysis of Deception	36902	•	•	•			•	•												
741	A System-Dynamics Approach to Modeling Water Demand	36904	•	•																	
44	Microfabrication with Femtosecond-Laser Processing	38605							•			•		•			•				
46	Mesoscale-Controlled Motion for a Microfluidic Drop Ejector	38606												•		•	•				
48	Science-Based Sensing of Phase Transformations in Steels	38608											•			•	•	•			
86	Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors	38609							•			•		•							
113	Graduated Embodiment for Sophisticated Agent Evolution and Optimization	38610		•	•				•										•		
115	Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation	38611		•																	
118	Robust Message Routing for Mobile (Wireless) <i>Ad Hoc</i> Networks	38612		•															•		
120	Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods	38613	•	•	•						•										
122	Micromagnetic Suspension	38614		•	•									•							
124	Sensitivities for Large-Scale Simulation Codes	38615			•																
157	Engineered Superconductivity in Electron-Hole Bilayers	38616												•							
160	Silicon-Based RF MEMS Components	38617						•	•					•							
562	Arrayed Resonant Subwavelength Gratings	38618							•					•							

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
491	Functionalized Nanoelectrode Arrays for <i>In Situ</i> Identification and Quantification of Regulated Chemicals in Water	38668							•							•				•	
404	Hybrid Infrastructure Cryptography	38669	•					•	•										•		•
494	Validated Modeling of Distributed Energy Resources at Distribution Voltages	38672		•																	
496	Water Desalination	38673														•					
499	Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps	38674														•	•	•			
502	Potential Application of Microsensor Technology in Radioactive-Waste Management—With Emphasis on Headspace Gas Detection	38677												•		•				•	
504	Surety Enhancement for Wireless Automated-Control Networks	38678		•																	•
506	Advanced Nuclear Engineering Analysis Technology	38679		•	•		•		•												
565	Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies	38681							•			•		•							
215	Multiscale Thermal Modeling	38682	•	•	•									•		•					
218	A Robust, Coupled Approach for Atomistic-Continuum Simulation	38684	•	•	•											•					
220	Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications	38685	•	•										•							
222	High-Fidelity Frictional Models for MEMs	38686		•				•						•							
225	Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames	38687	•	•			•			•											
278	The Basics of Aqueous Nanofluidics: “Interphase” Structure and Surface Forces	38688	•	•												•					
282	Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices	38689	•													•					
284	Photocontrol of Nanointeractions in Microsystems	38690												•		•					

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
287	Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines	38691	●													●	●				
289	Nanostructured Materials for Directed Transport of Excitation Energy	38692												●							
291	Modeling Local Chemistry in the Presence of Collective Phenomena	38693	●	●												●					
568	Passive-Legged, Multisegmented, Robotic Vehicle	38695							●										●		
571	Low-Cost Photonic Lattice Structures for Remote Sensing	38696							●					●		●					
573	Security Monitoring and Management with Information Technology (SUMMIT)	38698		●																	●
575	Novel Methods for Ultracompact, Ultralow-Power Communications	38699							●					●							●
577	Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	38701						●	●												
580	A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	38702							●						●						
584	Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets	38703		●	●				●												
293	The Effects of Varying Humidity on Copper-Sulfide Film Formation	38705		●			●							●							
587	Detecting and Tracking the Active Insider Using 3-D Detection Technology	38706					●	●	●										●		
589	Microfabricated Dielectrophoretic Sample-Preparation System	38707		●					●					●		●	●			●	
592	Automation of Microelectronic Physical Analysis	38708							●					●							
595	Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection	38712										●		●							
597	Secure MPLS Control Plane for Internet Connectivity	38713			●			●	●												
744	Nanoscale Energetic Materials by Inverse Micellar Synthesis	38717									●					●					
747	Modeling of Rock Penetration	38718		●		●				●											
600	Agile, Microsystems-Enabled Receiver	38722						●	●					●							

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
346	Adaptive Network Countermeasures	38744			●			●													
296	Solution-Based Nanoengineering of Materials	39017	●	●										●		●					
750	MEMS-Based Electromechanical Acoustic-Energy Harvester	39212	●	●										●					●		
334	Determination of Microstructural Properties with Isentropic Compression	39669											●								
336	Simulations of Intense Petawatt Laser Pulses with Dense Z-Pinch Plasmas	39670		●	●						●		●								
685	Biomicrofuel Cell	41193						●	●					●							●
687	Augmented Cognition: Next-Generation Intelligent Systems	41194	●				●	●	●					●			●		●		
753	Predicting and Validating MEMS Interface Reliability	41427	●	●	●		●	●	●	●				●	●	●	●	●	●	●	
349	Microengine for Advanced Power Generation	41674		●					●					●			●		●		
756	Direct Simulation of Solid-Fluid Systems	41726	●	●	●																
758	Support-Active Site Interactions in Heterogeneous Catalysts	42461																			●
760	An Analysis of the Automotive Industry as a Source for Weapon Components and Manufacturing Processes	42483	●	●	●		●		●	●	●	●		●		●	●		●		
762	Fluid-Structural Interactions in Wetting and Penetration into Porous Media	44136	●	●	●											●	●				
765	Macroscopic Rates, Microscopic Observations, and Molecular Models of the Dissolution of Carbonate Phases	45279	●	●	●															●	
768	High-Speed Micro-EDM	46070															●				
770	Nanoscale Hotspots Due to Nonequilibrium Thermal Transport	46685		●		●								●		●					
773	Microexternal Combustion Engine: The P3 Engine Prototype	46686						●											●		
775	Mathematical and Algorithmic Issues in Multiphysics Couplings	47517		●																●	
778	Lipid Membranes on Nanostructured Silicon	47795	●												●						

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
603	Digital Signal Processing for Acoustic-Seismic Target Identification	48746						•													
780	Resin Infusion Between Double Flexible Tooling	49769						•								•	•				
509	Frameworks for Nuclear Process Transparency and Control	49770						•													
782	Studies on the Disbonding Initiation of Interfacial Cracks	49772		•										•							
407	Critical Technology Development for Hard Target Defeat High-G-Tolerant Fuze and High Explosives	49915	•	•		•	•	•	•	•				•			•				
690	TALON	50065		•					•					•					•		
784	Compliant Membranes for MEMS Microphones	50396												•							
786	Multiscale Experimental/Numerical Study	50717														•					
89	Cellular Observatory: Simultaneous Time- and Frequency Resolved Microscopy	50772	•													•					•
788	Inelastic Deformation Mechanism in Shocked-Sapphire Single Crystals	52174								•			•								
51	Atomic-Layer Deposition of Highly Conformal Tribological Coatings	52523												•		•	•				
54	Assembly of Microsystems Using Exothermic Multilayer Thin Films	52524							•					•		•					
57	Intelligent Interaction Control as Applied to Metrology and Assembly of Microscale Components	52526	•	•															•		•
59	Rapid-Prototyping High-Density Circuitry (RpHdc)	52527										•				•	•	•			
61	Elucidating the Mysteries of Wetting	52528	•	•	•									•		•	•				
64	Next-Generation Spindles for Micromilling	52530															•				
300	Assembly and Actuation of Nanomaterials Using Active Biomolecules	52531	•											•		•					
91	Modeling Biomembranes	52532	•	•	•											•					•

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
93	Reverse-Engineering Biological Networks: Applications in Immune Responses to Bioterrorism Threats	52533	●	●																	
96	High-Throughput Identification of Molecular Machines Involved in Membrane Signaling and Toxin Pathways	52536	●	●																	
228	Coupled Solid-Fluid Mechanical-Computational Modeling of Fracture and Fragmentation in Geomaterials such as Hard and Deeply Buried Targets (HDBTs)	52537	●	●	●	●														●	
790	Sequestration of Pathogens on Nanoengineered Surfaces	52538	●	●												●					
793	A Combined Preconcentrator and Sensor for Live Waterborne Pathogens	52539							●											●	●
126	IP Storage: A Performance and Security Study	52540			●																
129	A Parallel Circuit Simulator for Cell Biology	52541	●	●	●													●			
131	Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions	52542		●																	
134	Robust Large-Scale Parallel Nonlinear Solvers for Simulations	52543		●	●																
136	Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/ Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security	52544		●	●																●
139	Massively Parallel Linear Programming	52546		●	●																
172	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics	52548										●		●							
174	Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia's MDL and BAE Systems	52549												●		●					
176	Functionalized Nanoparticles for Sensor Applications	52551							●					●		●					
178	Novel <i>In Situ</i> Mechanical Testers to Enable Integrated Metal Surface Micromachines	52552	●							●				●		●			●		

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
432	System-of-Systems Modeling and Analysis	52588		●																	
434	Eye-Safe Short-Range Standoff Aerosol-Cloud Finder	52589										●									
437	Micro Flame-Based Detector Suite for Universal Gas Sensing	52590							●					●							
511	Beyond Nanoparticles—Attack on a Chemical “Holy Grail”	52591																			●
513	Advanced Proton-Exchange Materials for Energy-Efficient Fuel Cells	52592	●													●				●	●
515	Alanate-Hydride Fuel-Cell Demonstration Project	52593	●																		
517	Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process	52594																			●
519	Real-Time Discriminatory Sensors for Water-Contamination Events	52595												●		●					
522	Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors	52596		●																	
524	Securing Mobile Code	52597							●												●
527	Novel Catalysts for Hydrogen Fuel-Cell Applications	52598														●					
530	Linking Optimization and Simulation in Critical Infrastructure Systems	52606	●	●	●																
533	The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water	52608													●					●	●
232	Analysis of Nanoscale Films and Particles	52609	●	●												●					
234	Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices	52611		●																	
236	Tensegrity—Smart, Adaptive Structures Through Material Biomimicry	52613	●													●					
239	Coupled Acoustical/Structural Simulations of Weapons Systems	52615		●	●																
303	Decomposition of Contaminants Using Photochemically Active Nanoparticles	52698														●					
305	Thermally Cleavable Surfactants	52699	●	●										●		●	●	●			

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
307	Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions	52700	●	●												●					
309	Quantification of Environments and Surfaces Within Micropackages	52701		●										●		●					
312	Assembly of Ordered Electrooptical and Bioactive Materials and Composites	52702	●											●		●					
315	Advanced Packaging/Joining Technology for Microsystems	52703	●	●								●		●							
319	Magnetostrictive Elastomers for Actuators and Sensors	52705	●	●												●					
605	Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons	52706							●												
607	Active Network and Use of Network Processor	52707							●												
608	Zero-Power Radio Receiver	52708							●					●							
610	Completely Passive Microwave Tag	52709							●					●							
612	Security Coatings for Multichip Modules	52710						●								●					●
614	Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces	52711		●																	
616	Content-Based Video and Image Indexing System	52712		●															●		
618	Bioaerosol Collection and Concentration for Microseparations-Based Detectors	52713							●												
621	Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains	52714							●												
623	Joint Authentication/Encryption	52716		●				●	●					●					●		
625	Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications	52717														●					
627	Leveraging Robotic Planning for Physical-Security Analysis	52718						●	●										●		
629	Buzzard	52719	●																●		
631	Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction	52720	●											●							

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
633	Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment	52721		•					•												
635	Radiation-Hardened Optoelectronic Components for Space-Based Applications	52722							•			•		•							
637	Novel Micropreconcentrators for CW, Explosives, and Water Surety	52723							•					•							
640	Ion-Mobility Spectrometer/Mass Spectrometer	52724	•																		
642	Cryptographic Assurance of Execution Correctness and Confidentiality	52725			•			•	•										•		
645	Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts	52726							•							•					
795	Predictive Accelerated Aging of Microsystems: The Science of Dormancy	52727						•		•				•							
798	Surety and Accountability Enhancements for Storage Containers	52728														•					
801	Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	52729					•	•								•					•
804	Advanced Packaging Technology for Optical Firesets	52730						•						•							
807	Miniature Transmitter Filter for JTA Using LIGA Technology	52731														•	•				
809	Novel and Robust Environmental Sensing Devices (ESDs)	52732	•											•		•					
811	Advanced Neutron Monitors for JTA and Stockpile Monitoring	52733		•					•							•					
338	Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating	52737										•	•								
341	Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators	52738											•								
343	Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions	52739																			•
813	A Microbioreactor for Hydrogen Production	52740												•							•
816	Self-Organizing Software Research and Development	52741	•	•															•		
819	Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	52742	•											•							

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
859	Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer	53587		•										•							
861	Miniature High-Power RF Components Enabled by Mesoscale Manufacturing	53588							•								•				•
863	Electron- and Proton-Beam Directed-Energy Defense Weapons	53589											•			•					
865	Electrical Conductivity of Metal Alloys	53590		•							•										
535	Hydrogen Futures Dynamic-Simulation Model	53591	•	•																	
867	Design of Biospecific Surfaces to Control Specific Cellular Responses	53681												•		•					
869	High-Field Effects of GaN HEMTs	53682												•							
871	Cognitive Models Applied to Human Effectiveness in National Security Environments	54210	•	•																	
872	Nanomagnetic Films	54211						•	•					•		•			•	•	
875	A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites	54213		•												•					
693	Near-Real-Time Characterization for Assured HDBT Defeat	55079		•	•																
696	Prompt Global Response	55086							•							•					
699	Winning the War: A Systems Approach to Defending Our Borders	55087		•	•			•				•		•							
877	Integrated Superhard and Metallic Coatings for MEMS	57300	•	•	•		•		•	•		•		•		•	•	•	•	•	
880	Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials	57307														•					
883	Friction in Micromachine Interfaces	57308												•					•		
885	Lipid Microarray Biosensor for Biotxin Detection	57309														•					
887	Advanced Manufacturing Techniques Using Rapid Prototyping	57310															•	•			
888	Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems	57311												•		•					

[illegible]

Appendix D: DOE Critical Technologies

[illegible]

Appendix D: DOE Critical Technologies

Pg #	Title	Project #	Science of Complex Systems	Modeling & Simulation of Complex Systems	High-Performance Computing	Nuclear Weapons Predictive Capability (Classified)	Safety Assessments & Engineering	Use Control & Security	Nonproliferation & Verification	Dynamic Testing in Severe Environments	High-Energy-Density Materials	Laser Technology	Pulsed Power and Accelerators	Microelectronics and Photonics	Nuclear Materials	Engineered Materials	Flexible Manufacturing	Environmentally Conscious Manufacturing	Intelligent Machines and Robotics	Waste Management	Other
541	Optical Trapping of Collisionally Cooled Molecules	65557	•																		
912	Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems	65558	•	•	•				•												
916	Direct Single-Ion Machining of Nanopores	65559														•					
454	Measures of Effectiveness and Performance for MicroTalon SDAC Technologies and Systems	65828						•	•					•							
666	Creative Networking of Commercial Products	66159							•												
667	Networked Device Demonstration	66160							•												
669	Analysis of Multichannel Internet Messaging	66161							•												
918	Investigation of the Effects of Intense Pulsed-Particle Beams on the Durability of Metal-to-Plastic Interfaces	66170											•			•					
543	Efficacy of the Sandia Decon Formulation on the SARS Coronavirus	66233	•																		•
920	Advanced Techniques for Multiobjective Discrete Optimization	66450	•	•																	
921	Fundamentals of Mobile-Robot Development	66610		•																	
922	Nonradioactive Safety and Performance Issues with Supercritical Water Reactor (SCWR) Safety Technologies	66809	•				•									•					
923	Radiation Performance Issues with Advanced Coolants for Next-Generation Reactor	66810	•												•						
722	Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application	67542														•					
924	Smart Detectors of Enrichment of Bioaerosols	67716	•						•					•							
925	Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation	68063		•	•																
66	Investigation of Bioprocesses for Advanced Manufacturing Applications	68552														•	•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
725	Molecular Integrated Microsystems (MIMS)	11130														•		•		*DHS, NIH, PHS
35	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508									•				•	•				
38	Levitated Three-Axis Microaccelerometer	26509									•				•					
40	Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques	26510								•					•					
42	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511	•						•		•			•	•	•				
100	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512												•	•	•		•		**Industry
102	Smart-Sensor Technology for Joint Test Assembly Flights	26514													•					
105	Multilevel Methods for Nonlinear Structural Mechanics	26515													•	•				
107	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516													•					
110	Parallel Repartitioning for Optimal Solver Performance	26517													•					
145	III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies	26518	•	•	•	•				•	•	•		•	•	•		•		**Industry
148	The Integration of Advanced Photonics and MEMS	26519								•		•			•	•				
200	Uncertainty Propagation in Models of Thermo-fluid Systems	26520	•								•				•					
203	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521									•				•					
207	A Physically Based Approach to Modeling Ductile Fracture	26522									•			•	•	•				
210	Radiation Aging of Stockpile and Space-Based Microelectronics	26523										•	•		•	•		•	•	*NRO, NSA..., **Commercial Space
212	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524								•					•			•		**Industry, Consortia
242	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525													•					
243	Microstructural and Continuum Evolution Modeling of Sintering	26526									•					•		•		**Industry

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
466	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554	•				•		•										•	**Industry
468	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555		•				•			•									
471	Specific Anion Nanoengineered Sorbents for Water Purification	26557	•			•	•			•	•									
546	Advanced Digital Detectors for Neutron Imaging	26563	•			•	•		•		•	•	•		•	•				
547	Microfabricated Acoustic Spectrum Analyzer	26564								•		•		•	•	•				
550	Coating Chemical Preconcentrators to Improve Chemical-Agent Collection	26572													•	•				*TSA
552	Detection and Exploitation of Spread-Spectrum Waveforms	26574										•				•				
556	Robust Chemometrics for Remote Spectral Sensing	26577										•			•	•				
559	Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578										•		•		•				
71	Molecular-Scale Studies of Single-Channel Membrane Pores	26581																•		*Office of Biological and Environmental Research
73	Efficient Massively Parallel Techniques for Protein Structure Generation	26582					•					•		•				•	•	*DARPA, **Pharmaceutical Industry
75	Mapping Membrane Protein Interactions in Cell Signaling Systems	26583																	•	**Industry, Academia
671	A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting	27328		•						•	•				•					
324	Z-Pinch Power-Plant System Development	28769									•		•							
327	Recyclable Transmission Line Concept for Z-Pinch IFE	28770									•									
329	Suppression of Electron Emission from Conductors	28771													•	•				
332	Solid-State Switch for Advanced Pulsed Power	28772									•		•		•	•				
378	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	28775									•				•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
680	Interfacial Bioscience Grand Challenge (IBIG)	28776									•					•		•	•	*NIH/NIAID, DHS, **Industry
78	High-Throughput Instruments, Methods, and Informatics for Systems Biology	32574					•				•			•						
473	Low-Work-Function Material Development for the Microminiature Thermionic Converter	32807		•							•		•			•				
475	Autonomous Microexplosive Subsurface Tracing System	32809						•			•									
477	Vulnerability Assessment of National Power Grid	32816									•	•			•	•		•	•	(power, water, gas, communications, etc.)
729	Molecular Simulations of MEMS and Membrane Coatings (PECASE)	32817									•				•					
150	Aging Mechanisms in Dormant MEMS Structures	32913									•				•					
83	Biomimetic Chloroplasts: An Integrated Microdevice Power Source	32914			•				•		•			•						
254	Study of Polymer Spin-Coating for Photolithographic Semiconductors in Near-Zero-Gravity Environment	32915												•				•		**Semiconductor
152	MEMS in μ Fluid Channels	32923	•			•								•						
155	Dispersive Photonics for Next-Generation Sensors and Microsystems	33602									•					•				
256	Understanding Metal Vaporization from Transient High-Fluence Laser Irradiation	34465			•										•	•				
258	Mechanics and Tribology of MEMS Materials	34466										•			•	•		•		**Industry
262	Dynamics of Metal/Ceramic Interfaces	34467									•				•					
263	<i>In Situ</i> Characterization of Soft Solution Processes for Nanoscale Growth	34468									•			•		•				
265	Determination of Critical Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469		•							•				•	•				
268	LIGA Microsystems Aging: Evaluation and Mitigation	34478													•	•		•		**Industry
271	Science-Based Processing of Field-Structured Composites	34485	•			•	•					•			•	•				
732	Self-Assembly of Polymers in Confined Geometries	34692									•				•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
734	Building Conscious Machines Based Upon the Architecture of Visual Cortex in the Primate Brain	34693										•				•		•		*National Institutes of Health
380	Microfuze	34698													•	•				
274	Exploration of New Multivariate Spectral Calibration Algorithms	34699	•				•				•	•			•	•			•	**ThermoNicolet
736	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	35376														•				
739	Mathematical Analysis of Deception	36902										•			•	•				
741	A System-Dynamics Approach to Modeling Water Demand	36904												•				•		*U.S. Geological Survey; Bureau of Reclamation
44	Microfabrication with Femtosecond-Laser Processing	38605													•	•				
46	Mesoscale-Controlled Motion for a Microfluidic Drop Ejector	38606										•			•				•	**Industry
48	Science-Based Sensing of Phase Transformation in Steels	38608		•												•			•	**Automotive Industry
86	Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors	38609										•		•	•	•				
113	Graduated Embodiment for Sophisticated Agent Evolution and Optimization	38610		•	•					•	•	•				•				
115	Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation	38611													•					
118	Robust Message Routing for Mobile (Wireless) <i>Ad Hoc</i> Networks	38612										•		•	•	•				
120	Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods	38613		•	•		•	•			•			•	•	•				
122	Micromagnetic Suspension	38614													•					
124	Sensitivities for Large-Scale Simulation Codes	38615													•					
157	Engineered Superconductivity in Electron-Hole Bilayers	38616									•									
160	Silicon-Based RF MEMS Components	38617								•		•			•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
486	Time-Domain Reflectometry for Remote, Real-Time Water-Quantity/-Quality Monitoring of Perennial and Ephemeral Streams	38665					•							•				•		*U.S. Geological Survey, U.S. Bureau of Reclamation, Army Corps of Engineers
489	Research and Development of Mathematical Algorithms to Define and Quantify Critical-Infrastructure Interdependencies	38667			•			•		•		•	•					•		*DHS
491	Functionalized Nanoelectrode Arrays for <i>In Situ</i> Identification and Quantification of Regulated Chemicals in Water	38668	•			•	•		•			•		•						
404	Hybrid Infrastructure Cryptography	38669										•		•		•		•	•	*DOE, **Industry
494	Validated Modeling of Distributed Energy Resources at Distribution Voltages	38672			•															
496	Water Desalination	38673		•						•								•	•	*BOI, EPA, DoD, **Industry
499	Revolutionary Systems for Catalytic Combustion and Diesel Catalytic Particulate Traps	38674		•				•			•									
502	Potential Application of Microsensor Technology in Radioactive-Waste Management—With Emphasis on Headspace Gas Detection	38677	•				•		•											
504	Surety Enhancement for Wireless Automated-Control Networks	38678		•								•							•	**Critical Infrastructure
506	Advanced Nuclear Engineering Analysis Technology	38679		•							•		•							
565	Identification of Chemical Plumes: Range-Resolved IR Lidar Enabled by New Photonic Technologies	38681					•	•				•			•	•				
215	Multiscale Thermal Modeling	38682												•	•					
218	A Robust, Coupled Approach for Atomistic-Continuum Simulation	38684									•			•	•	•				
220	Microscale Rarefied-Gas Dynamics and Surface Interactions for EUVL and MEMS Applications	38685												•	•					
222	High-Fidelity Frictional Models for MEMS	38686													•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
225	Soot Formation, Transport, and Radiation in Unsteady Diffusion Flames	38687	•					•							•	•		•		*DOC/NIST, NASA,
278	The Basics of Aqueous Nanofluidics: "Interphase" Structure and Surface Forces	38688								•					•					
282	Design, Synthesis, and Characterization of Soft-Matter Nanolayer Superlattices	38689													•			•		**Optics Industry
284	Photocontrol of Nanointeractions in Microsystems	38690								•	•			•						
287	Electrochemically Deposited Alloys with Tailored Nanostructures for LIGA Micromachines	38691									•				•					
289	Nanostructured Materials for Directed Transport of Excitation Energy	38692	•								•									
291	Modeling Local Chemistry in the Presence of Collective Phenomena	38693													•	•				
568	Passive-Legged, Multisegmented, Robotic Vehicle	38695										•				•				
571	Low-Cost Photonic Lattice Structures for Remote Sensing	38696	•									•			•	•				
573	Security Monitoring and Management with Information Technology (SUMMIT)	38698										•								
575	Novel Methods for Ultracompact, Ultralow-Power Communications	38699														•		•		**Defense Industry
577	Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	38701										•			•	•				
580	A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	38702							•			•	•		•	•				
584	Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets	38703										•			•	•				
293	The Effects of Varying Humidity on Copper-Sulfide Film Formation	38705													•	•				
587	Detecting and Tracking the Active Insider Using 3-D Detection Technology	38706										•				•		•		*DOE
589	Microfabricated Dielectrophoretic Sample-Preparation System	38707	•			•	•			•		•			•	•				
592	Automation of Microelectronic Physical Analysis	38708										•								

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
595	Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection	38712										•			•	•				
597	Secure MPLS Control Plane for Internet Connectivity	38713										•				•			•	**Optical Internetworking Forum
744	Nanoscale Energetic Materials by Inverse Micellar Synthesis	38717													•	•				
747	Modeling of Rock Penetration	38718										•			•	•				
600	Agile, Microsystems-Enabled Receiver	38722										•			•	•			•	**Industry
346	Adaptive Network Countermeasures	38744										•			•	•				
296	Solution-Based Nanoengineering of Materials	39017		•						•					•					
750	MEMS-Based Electromechanical Acoustic-Energy Harvester	39212		•	•						•									
334	Determination of Microstructural Properties with Isentropic Compression	39669												•	•					
336	Simulations of Intense Petawatt Laser Pulses with Dense Z-Pinch Plasmas	39670									•				•	•				
685	Biomicrofuel Cell	41193					•					•				•				
687	Augmented Cognition: Next-Generation Intelligent Systems	41194										•			•	•		•	•	*DoD, Others, **Industry, Academia
753	Predicting and Validating MEMS Interface Reliability	41427	•	•	•	•		•		•		•	•	•	•	•			•	**Industry
349	Microengine for Advanced Power Generation	41674									•	•				•				
756	Direct Simulation of Solid-Fluid Systems	41726						•		•	•			•					•	**CRADA 1581
758	Support-Active Site Interactions in Heterogeneous Catalysts	42461		•							•									
760	An Analysis of the Automotive Industry as a Source for Weapon Components and Manufacturing Processes	42483		•				•		•	•			•	•				•	**Ford, GM, Toyota, Keystone, Kistler, and other automotive component suppliers
762	Fluid-Structural Interactions in Wetting and Penetration into Porous Media	44136	•				•				•			•					•	**CRMPC Consortium • Crada, Procter and Gamble CRADA

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
765	Macroscopic Rates, Microscopic Observations, and Molecular Models of the Dissolution of Carbonate Phases	45279	•				•		•		•			•						
768	High-Speed Micro-EDM	46070													•					
770	Nanoscale Hotspots Due to Nonequilibrium Thermal Transport	46685		•						•	•					•			•	**Semiconductor
773	Microexternal Combustion Engine: The P3 Engine Prototype	46686		•							•				•					
775	Mathematical and Algorithmic Issues in Multiphysics Couplings	47517						•	•		•									
778	Lipid Membranes on Nanostructured Silicon	47795												•						
603	Digital Signal Processing for Acoustic-Seismic Target Identification	48746										•				•				
780	Resin Infusion Between Double Flexible Tooling	49769													•				•	**Industry
509	Frameworks for Nuclear Process Transparency and Control	49770											•					•		*NRC
782	Studies on the Disbonding Initiation of Interfacial Cracks	49772													•					
407	Critical Technology Development for Hard Target Defeat High-G-Tolerant Fuze and High Explosives	49915										•			•	•				
690	TALON	50065					•					•				•				
784	Compliant Membranes for MEMS Microphones	50396										•			•					
786	Multiscale Experimental/Numerical Study	50717													•					
89	Cellular Observatory: Simultaneous Time- and Frequency-Resolved Microscopy	50772																	•	**Biotechnology programs (e.g., IBIG Grand Challenge)
788	Inelastic Deformation Mechanism in Shocked-Sapphire Single Crystals	52174													•	•				
51	Atomic-Layer Deposition of Highly Conformal Tribological Coatings	52523										•			•	•				
54	Assembly of Microsystems Using Exothermic Multilayer Thin Films	52524										•			•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
57	Intelligent Interaction Control as Applied to Metrology and Assembly of Microscale Components	52526													•	•				
59	Rapid-Prototyping High-Density Circuitry (RpHdc)	52527													•	•		•	**Manufacturing Industry, University	
61	Elucidating the Mysteries of Wetting	52528	•	•		•		•			•			•	•	•				
64	Next-Generation Spindles for Micromilling	52530										•			•	•				
300	Assembly and Actuation of Nanomaterials Using Active Biomolecules	52531													•	•				
91	Modeling Biomembranes	52532					•									•		•	•	*NIH, **Pharmaceuticals, Medicine
93	Reverse-Engineering Biological Networks: Applications in Immune Responses to Bioterrorism Threats	52533									•							•	**DOE/OASCR and DOE/OBER	
96	High-Throughput Identification of Molecular Machines Involved in Membrane Signaling and Toxin Pathways	52536									•							•	**Biotechnology Industry	
228	Coupled Solid-Fluid Mechanical-Computational Modeling of Fracture and Fragmentation in Geomaterials, such as Hard and Deeply Buried Targets (HDBTs)	52537	•								•			•	•	•				
790	Sequestration of Pathogens on Nanoengineered Surfaces	52538									•			•						*DHS
793	A Combined Preconcentrator and Sensor for Liv Waterborne Pathogens	52539					•									•		•		*DHS, EPA
126	IP Storage: A Performance and Security Study	52540									•	•		•						
129	A Parallel Circuit Simulator for Cell Biology	52541	•				•													
131	Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions	52542													•					
134	Robust Large-Scale Parallel Nonlinear Solvers for Simulations	52543									•		•			•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
136	Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security	52544										•						•	•	*EPA, **Drinking Water Utilities, Security
139	Massively Parallel Linear Programming	52546												•						
172	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics	52548		•	•					•	•			•						
174	Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia's MDL and BAE Systems	52549										•		•	•	•				
176	Functionalized Nanoparticles for Sensor Applications	52551				•									•	•				
178	Novel <i>In Situ</i> Mechanical Testers to Enable Integrated Metal Surface Micromachines	52552									•			•	•					
181	Compliant Thermomechanical MEMS Actuators	52553		•								•			•	•				
183	An Integrated, Stacked System-on-a-Chip	52554										•	•		•	•				
185	Micromass Spectrometer-on-a-Chip	52555										•				•		•	•	*DHS, **Chem and Bio Nonproliferation
187	Quantum Coherence in Semiconductor Nanostructures for Improved Lasers and Detectors	52556									•				•	•				
189	MOSFET-MEMS Integration	52557										•			•	•		•	•	*DARPA, **Industry
191	Microoptical Gyroscope Via Monolithic Active/Passive Optical Integration	52566						•				•			•	•			•	**Automotive
193	Materials Physics and Device Development for Improved Efficiency of GaN HEMT High-Power Amplifiers	52570													•	•				
195	Leaky-Mode VCSELs for Photonic Logic Circuits	52571														•				
197	Advanced Polychromator Systems for Remote Chemical Sensing	52575	•									•				•				
409	Immunological Basis for High-Reliability Systems Control	52577										•			•	•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
411	Miniaturization of SAR Electronic Assembly Using Sandia's Integrated Substrate Technology	52579									•	•	•		•	•				
413	Moving-Target Identification Using Ultrahigh-Range-Resolution Data	52580													•	•				
416	Advanced Mobile Networking, Sensing, and Controls Using Graph Theory	52581										•				•				
418	Compact Terahertz (THz) Sources for Emerging Threats Applications	52582										•		•	•	•				
420	Understanding Communication in Counterterrorism Crisis Management	52583										•		•	•	•				
422	Hypervelocity Impact-Generated Flash	52584										•				•				
425	Improving Human/System Interactions in Systems-of-Systems	52585										•				•				
428	Distributed Detection and ID Algorithm Architecture for Unattended Ground Sensors	52586										•			•	•		•		*DHS
430	Secure Chaotic Communications	52587										•			•	•				
432	System-of-Systems Modeling and Analysis	52588													•	•				
434	Eye-Safe Short-Range Standoff Aerosol-Cloud Finder	52589													•	•				
437	Micro Flame-Based Detector Suite for Universal Gas Sensing	52590	•			•	•					•		•		•			•	**Industry
511	Beyond Nanoparticles—Attack on a Chemical “Holy Grail”	52591		•							•									
513	Advanced Proton-Exchange Materials for Energy Efficient Fuel Cells	52592		•	•			•		•	•			•	•	•				*OTT
515	Alanate-Hydride Fuel-Cell Demonstration Project	52593			•						•									
517	Vapor-Liquid Phase Behavior of the Iodine-Sulfur Water-Splitting Process	52594									•		•							
519	Real-Time Discriminatory Sensors for Water-Contamination Events	52595					•					•						•		*EPA
522	Advanced High-Efficiency Direct-Cycle Gas Power-Conversion Systems for Small Special-Purpose Nuclear-Power Reactors	52596		•							•		•		•	•				
524	Securing Mobile Code	52597													•			•		**Industry, Academics

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
527	Novel Catalysts for Hydrogen Fuel-Cell Applications	52598		•	•															
530	Linking Optimization and Simulation in Critical Infrastructure Systems	52606																•		**Critical Infrastructure
533	The Mechanism of Permeable Reactive Barrier Formation and Field Test of a Packed Bed for Arsenic Removal from Water	52608				•	•		•				•							
232	Analysis of Nanoscale Films and Particles	52609												•				•		**Industry
234	Radiation-Transport Method to Simulate Noncontinuum Gas Flows for MEMS Devices	52611								•					•					
236	Tensegrity—Smart, Adaptive Structures Through Material Biomimicry	52613									•			•	•	•				
239	Coupled Acoustical/Structural Simulations of Weapons Systems	52615				•									•	•		•		**Industry
303	Decomposition of Contaminants Using Photochemically Active Nanoparticles	52698				•									•					
305	Thermally Cleavable Surfactants	52699	•	•			•								•			•		**Industry
307	Transition-Metal Catalyzation of Complex-Hydride Absorption/Desorption Reactions	52700		•	•			•		•	•				•	•				
309	Quantification of Environments and Surfaces Within Micropackages	52701													•	•				
312	Assembly of Ordered Electrooptical and Bioactive Materials and Composites	52702									•									**Basic Energy Sciences
315	Advanced Packaging/Joining Technology for Microsystems	52703													•					
319	Magnetostrictive Elastomers for Actuators and Sensors	52705								•					•					
605	Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons	52706														•		•		**Industry, Homeland Defense
607	Active Network and Use of Network Processor	52707										•				•				
608	Zero-Power Radio Receiver	52708										•			•	•				
610	Completely Passive Microwave Tag	52709										•			•	•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
612	Security Coatings for Multichip Modules	52710										•			•	•				
614	Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces	52711				•						•			•					
616	Content-Based Video and Image Indexing System	52712										•			•	•				
618	Bioaerosol Collection and Concentration for Microseparations-Based Detectors	52713										•				•				
621	Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains	52714										•			•	•				
623	Joint Authentication/Encryption	52716							•			•	•	•	•	•				
625	Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications	52717													•	•		•		*NASA
627	Leveraging Robotic Planning for Physical-Security Analysis	52718							•			•	•			•				
629	Buzzard	52719										•			•	•				
631	Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction	52720										•			•	•				
633	Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment	52721										•								
635	Radiation-Hardened Optoelectronic Components for Space-Based Applications	52722														•				
637	Novel Micropreconcentrators for CW, Explosives, and Water Surety	52723	•			•	•					•	•		•			•		**Industry
640	Ion-Mobility Spectrometer/Mass Spectrometer	52724										•			•	•		•		*FAA
642	Cryptographic Assurance of Execution Correctness and Confidentiality	52725										•			•	•		•		**Industry: secure control systems
645	Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts	52726										•			•					
795	Predictive Accelerated Aging of Microsystems: The Science of Dormancy	52727								•		•			•	•		•		**Industry
798	Surety and Accountability Enhancements for Storage Containers	52728													•					

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
801	Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	52729													•	•				
804	Advanced Packaging Technology for Optical Firesets	52730													•					
807	Miniature Transmitter Filter for JTA Using LIGA Technology	52731													•	•				
809	Novel and Robust Environmental Sensing Devices (ESDs)	52732													•	•				
811	Advanced Neutron Monitors for JTA and Stockpile Monitoring	52733													•					
338	Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating	52737								•										
341	Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators	52738													•					
343	Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions	52739													•					
813	A Microbioreactor for Hydrogen Production	52740		•	•					•								•		**Microscale energy production
816	Self-Organizing Software Research and Development	52741													•			•		**Industry
819	Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	52742								•								•		**Industry
821	Computational Model of a Microbial Cell	52743								•										
823	Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents	52744	•	•		•	•					•		•	•	•				
825	A Biological Model for Controlling Interface Growth and Morphology	52745								•					•					
827	Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions	52746								•	•			•				•		**Biotechnology
830	Ornithopter	52747									•				•					
832	Light-Powered Nanovehicles	52748	•	•	•		•		•	•				•						

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
834	Anomalously High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source	52749										•				•		•		*DARPA
836	Quantum Computing Accelerator I/O	52750										•			•	•			•	**Industry: High-Performance Computing
838	Design and Control of the Magnetic Properties of Nanoparticles	52797															•			
840	Aerospace Vehicle Trajectory Optimization System by Primer Vector Methods	52825										•				•		•	•	*NASA, **LM, Raytheon, Other Defense Contractors
842	Algorithm Development for Smart Antennas	52826										•				•				
844	Failure Analysis and Surety Design of Composite Patching Systems	52976																•		*FAA
847	Flow Control and Mixing in Microfluidic Devices	52977												•	•				•	**University Collaboration
849	Topological Layout for the Optimal Design of Electrostatically Actuated MEMS	53372												•	•	•				
851	Atomic-Scale Scanning-Tunneling Microscopy Measurements of Nucleation and Growth of Ge/Si Alloy Structures	53464									•				•			•		*DARPA
853	Micro-/Nanoscale Thermomechanical Manufacturing	53465										•		•	•				•	**University Collaboration
855	Novel Diagnostics for Rarefied Flows in MEMS Applications	53585												•	•	•				
857	Geophysical Subsurface Imaging and Interface Identification	53586		•				•		•	•	•								
859	Evolution of Near-Surface Scalar Concentrations Through a Compact Cylinder Array Embedded in the Atmospheric Surface Layer	53587																	•	**University Fellowship
861	Miniature High-Power RF Components Enabled by Mesoscale Manufacturing	53588										•			•	•			•	**Industry
863	Electron- and Proton-Beam Directed-Energy Defense Weapons	53589														•			•	**Homeland Security
865	Electrical Conductivity of Metal Alloys	53590												•						
535	Hydrogen Futures Dynamic-Simulation Model	53591		•	•			•		•	•		•							

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
867	Design of Biospecific Surfaces to Control Specific Cellular Responses	53681												•	•					
869	High-Field Effects of GaN HEMTs	53682										•			•	•				
871	Cognitive Models Applied to Human Effectiveness in National Security Environments	54210												•		•				
872	Nanomagnetic Films	54211		•	•					•	•	•		•	•	•				
875	A Multiscale Approach to Modeling Carbon Nanotube-Reinforced Composites	54213												•		•				
693	Near-Real-Time Characterization for Assured HDBT Defeat	55079													•	•				
696	Prompt Global Response	55086										•				•				
699	Winning the War: A Systems Approach to Defending Our Borders	55087								•		•				•		•	•	*DHS, **Security Industry
877	Integrated Superhard and Metallic Coatings for MEMS	57300	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
880	Microscale Separations of Biological Compounds Using Novel Polymeric Separations Materials	57307										•								
883	Friction in Micromachine Interfaces	57308													•					
885	Lipid Microarray Biosensor for Biotxin Detection	57309										•								
887	Advanced Manufacturing Techniques Using Rapid Prototyping	57310										•			•					
888	Robust Hermetic Packaging Techniques for MEMS Integrated Microsystems	57311										•								
890	Surfactant Effects on Lateral Growth and Surface Morphology of GaAs	58336													•					
321	Active Photonic Nanostructures	58907		•								•				•				
892	3-D Large-Eddy Simulation of Turbulent Flow Based on One-Dimensional Turbulence Modeling	59034	•	•				•		•	•		•		•	•				
141	A Method of Evaluating Research Using New Innovation, Risk, and Impact Indicators	59916								•	•			•		•		•		**LDRD

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
894	The Derivation and Implications of “Nearly Noninformative” Priors from Metadata Conditioning	60626					•					•		•		•				
897	New Seismic-Event-Detection Technology	60627										•			•	•				
537	Dynamic-Simulation Modeling and Analysis Support for Senate Energy and Natural Resources Committee	60628		•						•	•							•	•	*Various, **Industry
705	SDAC Architectural Study and Demonstration System Development	60866										•			•	•		•	•	**Industry/University Consortia
899	Testing Recent Metal-/Oxide-Joining Discoveries in NW Component Manufacturing	61045								•	•				•	•				
901	Photonic Encryption Using All-Optical Logic	61046										•			•	•				
904	Automated Video Screening for Unattended Background Monitoring in Dynamic Environments	61047										•			•	•		•	•	*FBI, CIA, **Industry
906	Nanoporous-Carbon Adsorbers for Chemical Microsensors	62269				•						•				•				
708	Assessment of Information Flow Associated with Goods and People Crossing International Border	62270								•								•		*DOC, Customs
710	Automatic Detection of Anomalous Weapon Surveillance Waveforms	62826										•			•					
702	Nonlethal Technologies for the War on Terrorism	62827													•	•		•		*DHS
712	Computational Social Dynamic Modeling of Groups Perpetrating Violence	62970										•			•					
714	Development of a Terrorist-Activity Plan-Assessment Methodology	62971										•						•		*DHS
716	Development of an Interactive Nuclear/WMD Terrorist Data Model	62972										•						•		*DHS
647	Hyperspectral Tagging for Unique Identification	63965														•			•	**Safeguards
441	Smart Decoy Sensor Network	63966										•				•				
649	Fusing MSI and HSI Imagery for Subpixel Spectral Unmixing	63967										•			•	•				
443	Monomolecular Carbon Nanowire Fabrication	63968												•	•	•				

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
445	Reliability Data to Improve High-Magnetic-Field Coil Design for High-Velocity Coilguns	63969														•				
448	Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities	63970														•		•	•	*DHS, **First Responders, Firefighting
718	Enabling Technology for Human Collaboration	63971									•				•	•				
908	Molecular Electronics Test Platform	63972								•									•	**Electronics Industry
652	Study of 3-D Focal-Region Sounding Applied to Large-Aperture Telescopes	64214									•					•				
655	Affordable, Automated Computed Tomography (CT) X-Ray Screening for Large Vehicle Bombs Preliminary Study	64215									•	•		•						
657	Coordinated Weapon-Platform Control Strategies for Intelligent Targeting	64355													•	•		•		*DOE
659	Advanced Weapons Signatures	64356									•				•	•				
662	Universal Detection for Chem-Bio Sensing in Microfluidic Systems	64385	•			•	•								•					
721	Large-Scale System-Dynamics Modeling of Water Resources on the Rio Grande	64386	•	•				•					•			•		•		*EPA
910	Development of Highly Integrated Magnetically and Electrostatically Actuated Micropumps	64709									•			•		•			•	**Industry
451	Wide-Area Surveillance in Synthetic-Aperture Radar Images	64711									•				•	•				
539	Agent-Based Control of Distributed Infrastructure Resources	64811		•	•			•												
664	Multipurpose Locator-Tag System	65148				•			•			•								
911	A Robotic Framework for Semantic Concept Learning	65556	•				•		•							•	•		•	**University Research
541	Optical Trapping of Collisionally Cooled Molecules	65557									•									
912	Detection and Reconstruction of Error-Control Codes for Engineered and Biological Regulatory Systems	65558															•			
916	Direct Single-Ion Machining of Nanopores	65559		•													•			

Appendix E: Major National Programs

Pg #	Title	Project #	Waste Management	Energy Efficiency	Renewable Energy	ES&H	Environmental Restoration	Fossil Energy	Radioactive-Waste Management	Economic Impact	Energy Research	Intelligence & National Security	Nuclear Energy	Science Education & Technical Information	Defense Programs	Department of Homeland Security (DHS)	Department of Defense (DoD)	Other Federal Agencies*	Other (Industry, Consortia...)**	Other Federal Agencies* Other (Industry, Consortia...)**
454	Measures of Effectiveness and Performance for MicroTalon SDAC Technologies and Systems	65828				•						•			•	•	•			
666	Creative Networking of Commercial Products	66159										•					•			
667	Networked Device Demonstration	66160										•					•			
669	Analysis of Multichannel Internet Messaging	66161										•								
918	Investigation of the Effects of Intense Pulsed-Particle Beams on the Durability of Metal-to-Plastic Interfaces	66170													•	•			•	**Industry
543	Efficacy of the Sandia Decon Formulation on the SARS Coronavirus	66233												•		•	•		•	*DoAg, **Industry
920	Advanced Techniques for Multiobjective Discrete Optimization	66450											•		•	•			•	**Industry
921	Fundamentals of Mobile-Robot Development	66610												•						
922	Nonradioactive Safety and Performance Issues with Supercritical Water Reactor (SCWR) Safety Technologies	66809		•							•		•	•						
923	Radiation Performance Issues with Advanced Coolants for Next-Generation Reactor	66810		•									•							
722	Harnessing Methane-Hydrate Bacteria Interactions for Energy Source and Storage Application	67542		•	•			•												
924	Smart Detectors of Enrichment of Bioaerosols	67716														•	•			
925	Computational Studies of JP-8 Diffusion Flames with Detailed Chemistry and Particulate Formation	68063		•							•			•	•					
66	Investigation of Bioprocesses for Advanced Manufacturing Applications	68552								•					•	•			•	**Industry

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
725	Molecular Integrated Microsystems (MIMS)	11130															●	●									●		
35	Mesoscale Wide-Bandwidth Linear Magnetic Actuators	26508									●				●			●	●								●		
38	Levitated Three-Axis Microaccelerometer	26509	●				●											●				●					●		
40	Microfabrication Processes Combining Focused-Ion-Beam Machining and Thin-Film Vapor Deposition Techniques	26510								●								●									●		
42	Resolving Fundamental Limits of Adhesive Bonding in Microfabrication	26511	●	●				●	●	●						●	●	●	●	●		●					●		
100	Parallel Atomistic Computing for Failure Analysis of Micromachines	26512					●						●					●									●		
102	Smart-Sensor Technology for Joint Test Assembly Flights	26514					●						●		●							●				●			
105	Multilevel Methods for Nonlinear Structural Mechanics	26515					●						●					●					●				●		
107	Algorithmic Support for Commodity-Based Parallel Computing Systems	26516											●														●		
110	Parallel Repartitioning for Optimal Solver Performance	26517					●						●										●				●		
145	III-Antimonide/Nitride-Based Semiconductors for Optoelectronic Materials and Device Studies	26518	●					●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					●		
148	The Integration of Advanced Photonics and MEMS	26519											●					●	●	●							●		
200	Uncertainty Propagation in Models of Thermo-fluid Systems	26520	●				●			●			●															●	
203	Filtered Rayleigh-Scattering Diagnostic for Multiparameter Thermal/Fluids Measurements	26521	●							●												●					●		

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
207	A Physically Based Approach to Modeling Ductile Fracture	26522					•							•													•	
210	Radiation Aging of Stockpile and Space-Based Microelectronics	26523							•									•	•			•					•	
212	Large-Deformation Solid-Fluid Interaction Via a Level-Set Approach	26524					•									•											•	
242	Magnetic-Field Effects on Vacuum-Arc Plasmas	26525					•						•													•		
243	Microstructural and Continuum Evolution Modeling of Sintering	26526			•		•		•					•		•		•									•	
246	Assuring Ultraclean Environments in Microsystem Packages: Irreversible and Reversible Getters	26527																•									•	
248	Biocompatible Self-Assembly of Nanomaterials for Bio-MEMS and Insect Reconnaissance	26528		•	•	•										•	•	•			•	•					•	
252	First-Principles Determination of Dislocation Properties	26530					•							•		•											•	
353	Air Sterilization and Decontamination	26531		•	•												•										•	
355	Data Fusion and Visualization of MASINT Results for Underground Facility Characterization	26532																				•				•		
357	Advanced Unattended Ground-Sensor Technology	26534									•				•		•					•					•	
359	The Endowment of Simulator Agents with Humanlike Episodic Memory	26535	•				•								•		•						•		•		•	
361	Algorithms for Improved Performance in Cryptographic Protocols	26539																				•	•				•	
363	Low-Cost Digital Radar for Fuzing, Tags, SAR Imaging, and Targeting	26540	•						•													•					•	
365	Adaptive and Mobile Ground Sensors	26543																				•	•				•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
368	Algorithm Development for Prognostic Health Monitoring and Maintenance	26544	●				●															●					●	
371	New Mechanism for Upset of Electronics	26545						●																			●	
373	Flexible Robotic Maintenance Facility	26546	●				●																●				●	
376	Obstacle Detection for Autonomous Navigation	26548																				●				●		
457	Novel Catalytic Systems for Energy-Efficient Feedstock Hydrocarbon Separations	26551							●							●												●
460	A Model of Infrastructure Interdependency Using Communication Agents	26552					●																				●	
463	Microchemical Sensors for Characterization and Monitoring of Volatile Contaminants	26553																				●	●					●
466	Investigation of Potential Applications of Self-Assembled Nanostructured Materials in Nuclear-Waste Management	26554				●										●						●	●					●
468	Development of Detection Techniques and Diagnostics for Airborne Carbon Nanoparticles	26555								●												●						●
471	Specific Anion Nanoengineered Sorbent for Water Purification	26557														●						●						●
546	Advanced Digital Detectors for Neutron Imaging	26563						●	●													●	●				●	
547	Microfabricated Acoustic Spectrum Analyzer	26564	●					●														●		●			●	
550	Coating Chemical Preconcentrators to Improve Chemical-Agent Collection	26572														●		●				●					●	
552	Detection and Exploitation of Spread-Spectrum Waveforms	26574					●	●					●		●							●	●			●		

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
556	Robust Chemometrics for Remote Spectral Sensing	26577																				•					•	
559	Deployable Large-Aperture Optics System for Remote-Sensing Applications	26578	•									•										•					•	
71	Molecular-Scale Studies of Single-Channel Membrane Pores	26581		•																		•						•
73	Efficient Massively Parallel Techniques for Protein Structure Generation	26582		•			•						•				•						•				•	
75	Mapping Membrane Protein Interactions in Cell Signaling Systems	26583		•			•																					•
671	A Revolution in Lighting: Building the Science and Technology Base for Ultraefficient Solid-State Lighting	27328							•	•		•							•	•							•	
324	Z-Pinch Power-Plant System Development	28769								•																		•
327	Recyclable Transmission Line Concept for Z-Pinch IFE	28770								•																	•	
329	Suppression of Electron Emission from Conductors	28771							•					•													•	
332	Solid-State Switch for Advanced Pulsed Power	28772							•	•									•								•	
378	Laboratory-Scale Coherent Multikilovolt X-Ray Sources for Advanced Imaging Applications	28775								•		•						•									•	
680	Interfacial Bioscience Grand Challenge (IBIG)	28776		•									•				•										•	
78	High-Throughput Instruments, Methods, and Informatics for Systems Biology	32574		•					•			•	•				•						•				•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
265	Determination of Critical Length Scales for Corrosion Processes Using Microelectroanalytical Techniques	34469												•		•		•				•					•	
268	LIGA Microsystems Aging: Evaluation and Mitigation	34478												•		•		•								•		
271	Science-Based Processing of Field-Structured Composites	34485				•										•						•					•	
732	Self-Assembly of Polymers in Confined Geometries	34692					•																				•	
734	Building Conscious Machines Based Upon the Architecture of Visual Cortex in the Primate Brain	34693					•								•							•					•	
380	Microfuzze	34698																•				•				•		
274	Exploration of New Multivariate Spectral Calibration Algorithms	34699		•	•	•	•		•	•					•	•	•	•	•	•	•	•	•				•	
736	Development of Experimental Verification Techniques for Nonlinear Deformation and Fracture	35376					•		•									•									•	
739	Mathematical Analysis of Deception	36902					•	•					•										•				•	
741	A System-Dynamics Approach to Modeling Water Demand	36904					•																		•			•
44	Microfabrication with Femtosecond-Laser Processing	38605							•		•			•		•		•	•	•							•	
46	Mesoscale-Controlled Motion for a Microfluidic Drop Ejector	38606		•					•							•	•	•									•	
48	Science-Based Sensing of Phase Transformations in Steels	38608													•							•		•			•	
86	Physical and Electronic Changes Caused by Membrane Signaling as a Transduction Pathway in Affinity-Based Biosensors	38609		•			•		•								•	•	•	•		•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
113	Graduated Embodiment for Sophisticated Agent Evolution and Optimization	38610	●				●			●			●									●					●		
115	Stochastic Programming for Enterprise Modeling—Optimization for Nondeterministic Simulation	38611					●																				●		
118	Robust Message Routing for Mobile (Wireless) <i>Ad Hoc</i> Networks	38612					●				●											●	●				●		
120	Scalable Fault-Tolerant Algorithms for Linear-Scaling Coupled-Cluster Electronic Structure Methods	38613		●			●			●			●			●							●					●	
122	Micromagnetic Suspension	38614					●											●									●		
124	Sensitivities for Large-Scale Simulation Codes	38615					●						●														●		
157	Engineered Superconductivity in Electron-Hole Bilayers	38616							●									●	●								●		
160	Silicon-Based RF MEMS Components	38617							●									●	●			●					●		
562	Arrayed Resonant Subwavelength Gratings	38618							●									●	●	●							●		
162	Nanoelectromechanical Oscillators (NEMOs) for RF Filtering	38619							●									●				●					●		
165	Continuous-Wave Intersubband Terahertz Sources	38620							●										●	●		●					●		
167	Microsystems for Chemical Signature and Reagent Delivery	38621							●								●				●	●					●		
169	Microfluidic Cellular Sample Pretreatment	38622		●					●	●						●	●	●	●		●	●		●			●		
383	Automated Visual Direction of Mobile Manipulation	38623										●			●							●	●			●			

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)	
385	Miniature Fourier-Transform Ion-Mobility Spectrometer for Real-Time Detection and Identification of Explosives and Chemical Agents	38624								•								•			•	•					•		
387	CONOPS Development for Automated Systems	38625	•				•				•				•			•						•	•	•			
389	Rapid Mitigation and Decontamination of Toxic Industrial Chemicals	38626															•				•						•		
392	EM Interactions with Systems to Enhance Security	38627							•																	•			
394	Adaptive Awareness for Personal and Small-Group Decision Making	38628													•							•					•		
396	Use of Seismic and Acoustic Responses to Assess Bomb Damage to Underground Facilities	38629					•					•										•	•		•	•			
399	Free-Space Electrooptic Sampling and Remote Mapping of Electromagnetic Fields from Emitting Structures Using Femtosecond Terahertz Transceivers	38655							•										•	•		•						•	
401	Information Assurance for Wireless ^{4d} Hoc Networks	38659					•						•									•	•					•	
480	Natural-Gas Production Problems: Solutions, Methodologies, and Modeling	38662					•			•																			•
483	High-Efficiency Turbine Blade Coatings	38664	•							•						•												•	
486	Time-Domain Reflectometry for Remote, Real-Time Water-Quantity/-Quality Monitoring of Perennial and Ephemeral Streams	38665										•										•							•

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
577	Novel Tagging Technologies for the Tracking and Authentication of Documents, Property, and Other Items	38701		•															•								•	
580	A Revolutionary Long-Lived Power Supply: The Icosahedral Boride Semiconductor (IBS) Beta Cell	38702								•																•		
584	Remote-Sensing Data Exploitation for Geologic Characterization of Difficult Targets	38703					•		•													•					•	
293	The Effects of Varying Humidity on Copper-Sulfide Film Formation	38705					•		•									•									•	
587	Detecting and Tracking the Active Insider Using 3-D Detection Technology	38706													•							•	•				•	
589	Microfabricated Dielectrophoretic Sample-Preparation System	38707	•	•													•	•				•					•	
592	Automation of Microelectronic Physical Analysis	38708																	•								•	
595	Nonlinear Optical Limiters Using Photonic Bandgap Structures for Sensor Protection	38712							•									•	•	•		•				•		
597	Secure MPLS Control Plane for Internet Connectivity	38713											•										•				•	
744	Nanoscale Energetic Materials by Inverse Micellar Synthesis	38717	•											•		•		•								•		
747	Modeling of Rock Penetration	38718					•															•				•		
600	Agile, Microsystems-Enabled Receiver	38722	•						•									•	•			•					•	
346	Adaptive Network Countermeasures	38744											•										•		•		•	
296	Solution-Based Nanoengineering of Materials	39017			•	•	•		•			•				•		•		•		•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
129	A Parallel Circuit Simulator for Cell Biology	52541		•			•						•				•				•	•					•	
131	Developing a Computationally Efficient Dynamic Multilevel Hybrid Optimization Scheme Using Multifidelity Model Interactions	52542					•																				•	
134	Robust Large-Scale Parallel Nonlinear Solvers for Simulations	52543					•																				•	
136	Development of Computational Algorithms and Inversion Capabilities for Transport/Reaction Simulations of Chemical/ Biological/Radiological Terrorist Attack Scenarios in Support of Homeland Security	52544					•						•									•			•			•
139	Massively Parallel Linear Programming	52546					•						•										•				•	
172	Active Photonic-Crystal Devices for Integrated Photonics and Silicon Photonics	52548							•	•		•						•	•	•								•
174	Co-Processing of Chalcogenide-Based Radiation-Hard Nonvolatile Memories by Sandia's MDL and BAE Systems	52549							•										•			•					•	
176	Functionalized Nanoparticles for Sensor Applications	52551							•							•		•				•					•	
178	Novel <i>In Situ</i> Mechanical Testers to Enable Integrated Metal Surface Micromachines	52552							•					•		•		•	•			•					•	
181	Compliant Thermomechanical MEMS Actuators	52553					•		•									•				•					•	
183	An Integrated, Stacked System-on-a-Chip	52554	•		•	•		•	•			•	•		•		•	•	•	•	•	•		•			•	
185	Micromass Spectrometer-on-a-Chip	52555							•									•				•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
187	Quantum Coherence in Semiconductor Nanostructures for Improved Lasers and Detectors	52556							•							•		•	•	•							•	
189	MOSFET-MEMS Integration	52557							•						•			•	•								•	
191	Microoptical Gyroscope Via Monolithic Active/Passive Optical Integration	52566	•						•									•	•	•		•					•	
193	Materials Physics and Device Development for Improved Efficiency of GaN HEMT High-Power Amplifiers	52570							•									•		•		•				•		
195	Leaky-Mode VCSELs for Photonic Logic Circuits	52571							•										•	•		•					•	
197	Advanced Polychromator Systems for Remote Chemical Sensing	52575					•		•									•	•			•					•	
409	Immunological Basis for High-Reliability Systems Control	52577											•		•							•		•			•	
411	Miniaturization of SAR Electronic Assembly Using Sandia's Integrated Substrate Technology	52579	•		•	•			•	•		•						•	•	•	•			•			•	
413	Moving-Target Identification Using Ultrahigh-Range-Resolution Data	52580																				•				•		
416	Advanced Mobile Networking, Sensing, and Controls Using Graph Theory	52581											•										•			•		
418	Compact Terahertz (THz) Sources for Emerging Threats Applications	52582							•			•						•	•	•		•					•	
420	Understanding Communication in Counterterrorism Crisis Management	52583					•						•		•							•		•			•	
422	Hypervelocity Impact-Generated Flash	52584					•															•		•	•			

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
605	Development of a High-Throughput Microfluidic Integrated Microarray for the Detection of Chimeric Bioweapons	52706		●														●				●					●	
607	Active Network and Use of Network Processor	52707											●										●		●		●	
608	Zero-Power Radio Receiver	52708							●										●			●					●	
610	Completely Passive Microwave Tag	52709							●										●			●					●	
612	Security Coatings for Multichip Modules	52710			●										●	●			●							●		
614	Detailed Modeling and Simulation of Contaminant Transport in Architectural Spaces	52711					●																				●	
616	Content-Based Video and Image Indexing System	52712																				●	●				●	
618	Bioaerosol Collection and Concentration for Microseparations-Based Detectors	52713																				●					●	
621	Detecting the Toolmarks of Genetic Engineering in Bioweapons Strains	52714		●														●								●		
623	Joint Authentication/Encryption	52716											●						●	●			●				●	
625	Ultrahigh-Temperature Ceramics for Hypersonic Vehicle Applications	52717	●		●											●											●	
627	Leveraging Robotic Planning for Physical-Security Analysis	52718					●															●			●		●	
629	Buzzard	52719													●							●		●			●	
631	Ultralightweight Telescope with MEMS Adaptive Optic for Distortion Correction	52720							●										●	●							●	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
633	Modeling Signals from Earth-Penetrating Nuclear Weapons for Remote-Kill Assessment	52721					•														•					•		
635	Radiation-Hardened Optoelectronic Components for Space-Based Applications	52722							•										•	•		•					•	
637	Novel Micropreconcentrators for CW, Explosives, and Water Surety	52723		•					•						•		•	•			•	•					•	
640	Ion-Mobility Spectrometer/Mass Spectrometer	52724																				•					•	
642	Cryptographic Assurance of Execution Correctness and Confidentiality	52725						•					•		•							•					•	
645	Characterization, Performance, and Optimization of PVDF as a Piezoelectric Film for Advanced Space Mirror Concepts	52726														•										•		
795	Predictive Accelerated Aging of Microsystems: The Science of Dormancy	52727	•				•		•										•	•		•					•	
798	Surety and Accountability Enhancements for Storage Containers	52728				•																				•		
801	Nuclear-Safety Weaklinks for Thermal and Mechanical Environments	52729			•											•											•	
804	Advanced Packaging Technology for Optical Firesets	52730							•										•	•	•						•	
807	Miniature Transmitter Filter for JTA Using LIGA Technology	52731																•									•	
809	Novel and Robust Environmental Sensing Devices (ESDs)	52732							•									•	•	•		•					•	
811	Advanced Neutron Monitors for JTA and Stockpile Monitoring	52733																•				•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
338	Development of an Efficient Large-Aperture High-Damage-Threshold Sol-Gel Diffraction Grating	52737							•										•									•
341	Laser Triggering of Water Switches in Terawatt-Class Pulsed-Power Accelerators	52738								•																	•	
343	Experimental and Computational Study of Liquid-Liquid and Freezing Phase Transitions	52739					•																				•	
813	A Microbioreactor for Hydrogen Production	52740		•						•								•				•					•	
816	Self-Organizing Software Research and Development	52741					•						•									•	•				•	
819	Highly Specific Electronic Signal Transduction Mediated by DNA/Metal Self-Assembly	52742		•					•								•	•				•					•	
821	Computational Model of a Microbial Cell	52743		•			•						•															•
823	Biomimetic Air Sampling for Detection of Low Concentrations of Molecules and Bioagents	52744		•					•						•		•	•	•			•					•	
825	A Biological Model for Controlling Interface Growth and Morphology	52745		•			•							•		•	•											•
827	Nanostructured Polyoxometalate Arrays with Unprecedented Properties and Functions	52746			•											•	•	•	•									•
830	Ornithopter	52747	•																								•	
832	Light-Powered Nanovehicles	52748														•		•										•
834	Anomalous High Photocurrents in Nanostructured Electrodes: A New Local Microchip Power Source	52749		•	•												•	•				•					•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

Appendix F: Dual-Benefit Areas and Single-Use Categories

Pg #	Title	Project #	Aeronautics	Applied Molecular Biology	Ceramics	Composites	Computer Simulation and Modeling	Data Storage and Peripherals	Electronics and Photonics	Energy	Flexible Computer-Integrated Manufacturing	High-Definition Imaging and Displays	High-Performance Computing and Networking	High-Performance Metals and Alloys	Intelligent Processing Equipment	Materials Synthesis and Processing	Medical Technology	Micro- and Nanofabrication	Micro- and Optoelectronics	Photonic Materials	Pollution Minimization, Remediation, and Waste Mgmt.	Sensors and Signal Processing	Software	Surface Transportation Technologies	Systems Management Technologies	Defense-Related (mostly or purely)	Dual-Use (defense and non-defense-related)	Non-Defense-Related (mostly or purely)
448	Sandia Dual-Use Formulation for CBW/Fire-Suppression Capabilities	63970																			•						•	
718	Enabling Technology for Human Collaboration	63971					•																		•		•	
908	Molecular Electronics Test Platform	63972		•				•	•				•					•									•	
652	Study of 3-D Focal-Region Sounding Applied to Large-Aperture Telescopes	64214																	•			•					•	
655	Affordable, Automated Computed Tomography (CT) X-Ray Screening for Large Vehicle Bombs Preliminary Study	64215							•	•	•						•					•		•				•
657	Coordinated Weapon-Platform Control Strategies for Intelligent Targeting	64355													•							•				•		
659	Advanced Weapons Signatures	64356					•															•				•		
662	Universal Detection for Chem-Bio Sensing in Microfluidic Systems	64385		•					•								•		•		•	•					•	
721	Large-Scale System-Dynamics Modeling of Water Resources on the Rio Grande	64386					•			•											•							•
910	Development of Highly Integrated Magnetically and Electrostatically Actuated Micropumps	64709		•					•									•	•	•		•		•			•	
451	Wide-Area Surveillance in Synthetic-Aperture Radar Images	64711																				•				•		
539	Agent-Based Control of Distributed Infrastructure Resources	64811								•					•								•		•		•	
664	Multipurpose Locator-Tag System	65148							•												•	•				•		
911	A Robotic Framework for Semantic Concept Learning	65556									•				•						•		•	•			•	

Appendix F: Dual-Benefit Areas and Single-Use Categories

[illegible]

[illegible]

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- A**
- 3-D
 - Focal region, 652
 - Turbulent flow, 892
 - μFluid
 - See* Microfluid
 - Abbott, R. E.
 - Assessment of Bomb Damage to Underground Facilities, 396
 - Abbott, R. G.
 - CONOPS Development for Automated Systems, 387
 - Simulator Agents with Humanlike Episodic Memory, 359
 - Abraham, I. C.
 - Energy-Efficient Feedstock Hydrocarbon Separations, 457
 - Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
 - Absorption, 307
 - Accelerator
 - Pulsed-power, 341
 - Quantum computing, 836
 - Accountability, 798
 - Ackermann, M. R.
 - Prompt Global Response, 696
 - TALON, 690
 - Acoustic
 - Bomb damage, 396
 - Energy harvester, 750
 - Spectrum analyzer, 547
 - Target identification, 603
 - Weapons, 239
 - Actuate
 - Micropump, 910
 - Nanomaterials, 300
 - Actuator
 - Elastomers, 319
 - Magnetic, 35
 - MEMS (electrostatic), 849
 - MEMS (thermomechanical), 181
 - Adams, D. P.
 - Assembly of Microsystems Using Thin Films, 54
 - Icosahedral Boride Semiconductor Beta Cell, 580
 - Microfabrication Processes, 40
 - Ultralightweight Telescope with MEMS Adaptive Optic, 631
 - Adaptive
 - Awareness, 394
 - Ground sensors, 365
 - Network, 346
 - Optics, 631
 - Tensegrity, 236
 - Adhesive, 42
 - Adkins, D. R.
 - Adhesive Bonding in Microfabrication, 42
 - Microfabricated Acoustic-Spectrum Analyzer, 547
 - Novel Micropreconcentrators, 637
 - Adsorb, 906
 - Aerosol
 - Cloud finder, 434
 - See also:* Bioaerosol detectors
 - Aerospace, 840
 - Affinity, 86
 - Agent
 - Episodic memory, 359
 - Graduated embodiment, 113
 - Infrastructure interdependency, 460
 - Infrastructure resources, 539
 - Agile, 600
 - Aging
 - Microelectromechanical, 150
 - Microsystems (accelerated), 795
 - Microsystems (lithography), 268
 - Space-based microelectronics, 210
 - Air
 - Sampling, 823
 - Sterilization, 353
 - Airborne, 468
 - Akhil, A. A.
 - Agent-Based Control of Infrastructure Resources, 539
 - Alanate-hydride, 513
 - Aldridge, D. F.
 - Assessment of Bomb Damage to Underground Facilities, 396
 - Alford, C.
 - Dispersive Photonics for Sensors and Microsystems, 155
 - Alford, M. E.
 - Miniature Fourier-Transform Ion-Mobility Spectrometer, 385
 - Algorithm
 - Commodity-based, 107
 - Cryptographic protocols, 361
 - Fault tolerant, 120
 - Ground sensors, 428
 - Health monitoring, 368
 - Infrastructure interdependencies, 489
 - Multiphysics couplings, 775
 - Smart antennas, 842
 - Spectral calibration, 274
 - Terrorist scenarios, 136
 - Allen, J. J.
 - Polychromator Systems for Remote Chemical Sensing, 197
 - Topological Layout for Electrostatically Actuated MEMS, 849
 - Allen, S. E.
 - Silicon-Based RF MEMS Components, 160
 - Allerman, A. A.
 - A Revolution in Lighting, 671
 - Efficiency of GaN HEMT High-Power Amplifiers, 193
 - Semiconductors for Optoelectronic Materials, 145
 - Alloy
 - Electrical conductivity, 865
 - Lithography, 287
 - Nucleation, 851
 - Amai, W. A.
 - Immunological Basis for Systems Control, 409
 - Ammerlahn, H. R.
 - A Systems Approach to Defending Our Borders, 699
 - Robust Message Routing for Mobile *Ad Hoc* Networks, 118
 - Amplifier, 193
 - Analyzer, 547

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Anderson, D. J.
System-of-Systems Modeling and Analysis, 432
- Anderson, L. F.
Microfabricated Acoustic-Spectrum Analyzer, 547
- Anderson, R. A.
Magnetostrictive Elastomers for Actuators and Sensors, 319
PVDF as a Piezoelectric Film, 645
- Anderson, R. J.
Automated Visual Direction of Mobile Manipulation, 383
- Anderson, W. E.
Information Assurance for Wireless *Ad Hoc* Networks, 401
Joint Authentication/Encryption, 623
Securing Mobile Code, 524
- Anion, 471
- Anomalous
Photocurrents, 834
Surveillance waveforms, 710
- Antenna, 842
- Antimonide/nitride, 145
- Antolak, A. J.
Decomposition of Contaminants Using Nanoparticles, 303
- Antoun, B. R.
Friction in Micromachine Interfaces, 883
High-Fidelity Frictional Models for MEMS, 222
Modeling Ductile Fracture, 207
- Apblett, C. A.
Biomicrofuel Cell, 685
Microexternal-Combustion Engine, 773
- Aperture
Diffraction grating, 338
Radar image, 451
Remote sensing, 559
Telescope, 652
- Aqueous, 278
- Architecture
Algorithm, 428
Contaminant transport, 614
Primate brain, 734
Sense, decide, act, and communicate, 705
- Arellano, J. P.
Modeling of Sintering, 243
- Arguello, J. G., Jr.
Modeling of Sintering, 243
- Armendariz, M.
Miniaturization of SAR Electronic Assembly, 411
- Armstrong, R. C.
Smart Sensors for Joint Test Assembly Flights, 102
- Arnold, B. W.
Natural-Gas Production Problems, 480
- Array
Compact cylinder, 859
Nanoelectrode, 491
Polyoxometalate, 827
Subwavelength gratings, 562
See also: Microarray
- Arsenic, 533
- Aselage, T. L.
High-Efficiency Turbine Blade Coatings, 483
Icosahedral Boride Semiconductor Beta Cell, 580
- Ash, B. J.
Elucidating the Mysteries of Wetting, 61
- Ashley, C. S.
Large-Aperture Sol-Gel Diffraction Grating, 338
- Assembly
See Self-assembled
- Assink, R. A.
PVDF as a Piezoelectric Film, 645
- Atmosphere, 859
- Atomic
Microscopy, 851
Tribological coatings, 51
- Atomistic
Continuum simulation, 218
Parallel computing, 100
- Attack, 136
- Atwood, T. D.
Ultracompact, Ultralow-Power Communications, 575
- Aubry, S.
Atomistic-Continuum Simulation, 218
- Augmented cognition, 687
- Austin, D. E.
Ion-Mobility Spectrometer/Mass Spectrometer, 640
Micromass Spectrometer-on-a-Chip, 185
- Authentication
Encryption, 623
Tag, 577
- Automate
Concept of operations, 387
Control networks, 504
Detection, 710
Mobile manipulation, 383
Physical analysis, 592
Video screening, 904
X-ray screening, 655
- Automotive, 760
- Autonomous
Navigation, 376
Tracing, 475
- Awareness, 394
- Axline, R. M.
Detection of Spread-Spectrum Waveforms, 552
- B**
- Baca, A. G.
Agile, Microsystems-Enabled Receiver, 600
Efficiency of GaN HEMT High-Power Amplifiers, 193
Nonlethal Technologies for the War on Terrorism, 702
- Baca, H. K.
Biocompatible Self-Assembly of Nanomaterials, 248

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Bachand, G. D.
 Assembly of Electrooptical and Bioactive Materials, 312
 Assembly of Nanomaterials Using Active Biomolecules, 300
 Membrane Signaling in Affinity-Based Biosensors, 86
 MEMS in μ Fluid Channels, 152
 Molecular Integrated Microsystems, 725
- Backer, A.
 Evaluating Research Using Risk and Impact Indicators, 141
 New Seismic-Event-Detection Technology, 897
- Bacon, L. D.
 EM Interactions with Systems to Enhance Security, 392
 New Mechanism for Upset of Electronics, 371
 Secure Chaotic Communications, 430
- Bacteria, 722
- BAE Systems, 174
- Baer, T. A.
 Large-Deformation Solid-Fluid Interaction, 212
- Bailey, J. E.
 Hypervelocity Impact-Generated Flash, 422
- Baker, M. S.
 Compliant Thermomechanical MEMS Actuators, 181
 Silicon-Based RF MEMS Components, 160
- Bambha, R. P.
 Eye-Safe Short-Range Standoff Aerosol-Cloud Finder, 434
 Identification of Chemical Plumes, 565
- Bammann, D. J.
 Modeling Ductile Fracture, 207
- Bandgap, 595
- Bandwidth, 35
- Barbour, J. C.
 Active Photonic Nanostructures, 321
 Varying Humidity on Copper-Sulfide Film Formation, 293
- Barrier, 533
- Bartel, L. C.
 Assessment of Bomb Damage to Underground Facilities, 396
 Near-Real-Time Characterization for HDBT Defeat, 693
- Bartelt, N. C.
 Dynamics of Metal/Ceramic Interfaces, 262
- Bartlett, R. A.
 Sensitivities for Large-Scale Simulation Codes, 124
- Barton, D. C.
 A Model of Infrastructure Interdependency, 460
- Barton, D. L.
 Automation of Microelectronic Physical Analysis, 592
- Bastasz, R. J.
 Interfacial Bioscience Grand Challenge, 680
 Miniature Fourier-Transform Ion-Mobility Spectrometer, 385
- Battaille, C. C.
 Microminiature Thermionic Converter, 473
- Bauer, F. J.
 High-Efficiency Turbine Blade Coatings, 483
- Bauer, W.
 Highly Specific Electronic Signal Transduction, 819
- Beam
 Electron and proton weapons, 863
 Machining, 40
 Pulsed particle, 918
- Beaver, C. L.
 Hybrid Infrastructure Cryptography, 404
 Improved Performance in Cryptographic Protocols, 361
 Joint Authentication/Encryption, 623
 Securing Mobile Code, 524
- Beede, M. P.
 Analysis of Multichannel Internet Messaging, 669
- Beggans, M. H.
 Biomicrofuel Cell, 685
 Photonic-Bandgap Structures for Sensor Protection, 595
- Behrens, R., Jr.
 Interfacial Bioscience Grand Challenge, 680
 Nanoscale Energetic Materials, 744
- Bell, N. S.
 Active Photonic Nanostructures, 321
 Photocontrol of Nanointeractions in Microsystems, 284
 Soft-Solution Processes for Nanoscale Growth, 263
- Benavides, G. L.
 High-Speed Micro-EDM, 768
 Miniature High-Power RF Components, 861
 Z-Pinch Power-Plant System Development, 324
- Bender, M. A.
 Algorithmic Support for Commodity-Based Parallel Computing Systems, 107
- Bennett, P. C.
 Automated Visual Direction of Mobile Manipulation, 383
- Bennett, R. S.
 Radiation-Hard Nonvolatile Memories, 174
 Micromass Spectrometer-on-a-Chip, 185
- Bennett, T. E.
 Surety and Accountability for Storage Containers, 798
- Beresh, S. J.
 Filtered Rayleigh-Scattering Diagnostic, 203
- Bernard, M. L.
 Cognitive Models Applied to Human Effectiveness, 871
 Communication in Counterterrorism Crisis Management, 420
- Berry, D. T.
 Icosahedral Boride Semiconductor Beta Cell, 580
- Berry, N. M.
 Modeling of Groups Perpetrating Violence, 712
 SDAC Architectural Study and Demonstration System, 705
 Smart Sensors for Joint Test Assembly Flights, 102
- Beta cell, 580
- Bethke, D.
 An Integrated, Stacked System-on-a-Chip, 183
 Linear Magnetic Actuators, 35
 Miniaturization of SAR Electronic Assembly, 411
- Betty, R. G.
 Decontamination of Toxic Industrial Chemicals, 389
 Dual-Use Formulation for CBW/Fire Suppression, 448
- Beyeler, W. E.
 Critical-Infrastructure Interdependencies, 489
- Biefeld, R. M.
 A Revolution in Lighting, 671
 Quantum Coherence in Semiconductor Nanostructures, 187
- Bieker, J. M.
 Sandia Decon Formulation on the SARS Coronavirus, 543

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Bierbaum, N. R.
Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Bierbaum, R. L.
Smart Sensors for Joint Test Assembly Flights, 102
- Bilayer, 157
- Bilisoly, R. L.
Algorithms for Simulations of Chemical Attacks, 136
- Bioactive, 312
- Bioaerosol detectors
Microseparation, 618
Smart, 924
- Bioagent, 823
- Biocompatible, 248
- Biology
Attack, 136
Cell, 129
Interface growth, 825
Microscale separation, 880
Networks, 93
Regulatory system, 912
Systems, 78
- Biomembrane, 91
- Biomechanical (Bio-MEMS), 248
- Biomicrofuel cell, 685
- Biomimetic
Air sampling, 823
Chloroplasts, 83
- Biomimicry, 236
- Biomolecule, 300
- Bioprocess, 66
- Bioscience, 680
- Biosensor
Lipid microarray, 885
Membrane signaling, 86
- Biospecific, 867
- Bioterrorism, 93
- Biotoxin, 885
- Bioweapon
Chimeric, 605
Genetic engineering, 621
- Bishop, L. B.
Computed Tomography X-Ray Screening, 655
- Bisson, S. E.
Identification of Chemical Plumes, 565
- Black, S. P.
Secure MPLS Control Plane for Internet Connectivity, 597
- Blade (turbine), 483
- Blain, C. D.
Linear Magnetic Actuators, 35
- Blain, M. G.
Functionalized Nanoparticles for Sensor Applications, 176
Micromass Spectrometer-on-a-Chip, 185
- Blair, D. S.
Multipurpose Locator-Tag System, 664
- Blair-Stahn, N. D.
Improved Performance in Cryptographic Protocols, 361
- Blansett, E. L.
Leaky-Mode VCSELs for Photonic Logic Circuits, 195
Quantum Coherence in Semiconductor Nanostructures, 187
Radiation-Hardened Optoelectronic Components, 635
- Blevins, L. G.
Soot Formation in Unsteady Diffusion Flames, 225
- Bliss, D. E.
Laser Triggering of Water Switches in Accelerators, 341
- Bochev, P. B.
Geophysical Subsurface Imaging, 857
- Boehme, D. R.
Miniature Transmitter Filter for JTA, 807
- Bolton, W. R., Jr.
Nonlethal Technologies for the War on Terrorism, 702
- Boman, E. G.
Massively Parallel Linear Programming, 139
Parallel Repartitioning for Optimal Solver Performance, 110
- Bomb
Underground facilities, 396
Vehicle, 655
- Bonding, 42
- Boney, C. B.
Robust Chemometrics for Remote Spectral Sensing, 556
- Borders
Defending, 699
Information flow, 708
- Boride, 580
- Boslough, M. B. E.
Sophisticated Agent Evolution and Optimization, 113
- Bouchard, A. M.
Self-Organizing Software Research and Development, 816
- Bourdon, C. J.
Diagnostics for Rarefied Flows in MEMS Applications, 855
- Bower, W. I.
Validated Modeling of Distributed Energy Resources, 494
- Boyack, K. W.
Evaluating Research Using Risk and Impact Indicators, 141
Informatics for Systems Biology, 78
- Boyce, B. L.
Mechanics and Tribology of MEMS Materials, 258
- Boye, C. A.
Ultralightweight Telescope with MEMS Adaptive Optic, 631
- Boye, L. A.
Advanced Weapons Signatures, 659
- Boyes, J. D.
Validated Modeling of Distributed Energy Resources, 494
- Boyle, T. J.
Active Photonic Nanostructures, 321
Decomposition of Contaminants Using Nanoparticles, 303
Solution-Based Nanoengineering of Materials, 296
- Brabson, J. M.
Data Fusion and Visualization of MASINT Results, 355
- Bradshaw, R. W.
Harnessing Methane-Hydrate Bacteria Interactions, 722
Vapor-Liquid Phase of Iodine-Sulfur Water-Splitting, 517

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Brady, P. V.
Anion Nanoengineered Sorbents for Water Purification, 471
- Braginsky, M. V.
Modeling of Sintering, 243
- Brain, 734
- Brainard, J. R.
Real-Time Water-Quantity/-Quality Monitoring, 486
- Brandt, D. J.
Miniature High-Power RF Components, 861
- Brandt, L. D.
Nonlethal Technologies for the War on Terrorism, 702
- Brannon, N. G.
Augmented Cognition, 687
Improving Human/System Interactions, 425
- Branson, E. D.
Large-Aperture Sol-Gel Diffraction Grating, 338
- Bray, B. K.
Surveillance in Synthetic-Aperture Radar Images, 451
- Bray, O. H.
Interactive Nuclear/WMD Terrorist Data Model, 716
Terrorist-Activity Plan-Assessment Methodology, 714
- Breckenridge, A.
Sophisticated Agent Evolution and Optimization, 113
- Briggs, R. D.
Agile, Microsystems-Enabled Receiver, 600
Efficiency of GaN HEMT High-Power Amplifiers, 193
- Brinker, C. J.
Assembly of Electrooptical and Bioactive Materials, 312
Biocompatible Self-Assembly of Nanomaterials, 248
Biomimetic Chloroplasts, 83
High Photocurrents in Nanostructured Electrodes, 834
Microsystems for Reagent Delivery, 167
Molecular Integrated Microsystems, 725
Nanostructured Polyoxometalate Arrays, 827
Self-Assembled Materials in Waste Management, 466
- Brocato, R. W.
Completely Passive Microwave Tag, 610
Zero-Power Radio Receiver, 608
- Brockmann, J. E.
Contaminant Transport in Architectural Spaces, 614
- Brown, A. A.
Computational Modeling of Fracture in Geomaterials, 228
- Brown, J. R.
Polymer Spin-Coating for Semiconductors, 254
- Broyles, R. S.
Large-Aperture Sol-Gel Diffraction Grating, 338
- Brozik, S. M.
Biocompatible Self-Assembly of Nanomaterials, 248
Biomicrofuel Cell, 685
Biospecific Surfaces to Control Cellular Responses, 867
High Photocurrents in Nanostructured Electrodes, 834
Interfacial Bioscience Grand Challenge, 680
Membrane Signaling in Affinity-Based Biosensors, 86
Microfluidic Cellular Sample Pretreatment, 169
Microsystems for Reagent Delivery, 167
Tagging for Tracking and Authentication of Documents, 577
- Brunett, B. A.
Advanced Digital Detectors for Neutron Imaging, 546
An Integrated, Stacked System-on-a-Chip, 183
- Bryan, C. R.
Microsensors in Radioactive-Waste Management, 502
Self-Assembled Materials in Waste Management, 466
- Bryson, P. R.
TALON, 690
- Buchheit, T. E.
Assembly of Microsystems Using Thin Films, 54
Integrated Metal Surface Micromachines, 178
Mechanics and Tribology of MEMS Materials, 258
- Bukaty, M. E.
Advanced Unattended Ground-Sensor Technology, 357
Data Fusion and Visualization of MASINT Results, 355
- Bunde, D. P.
Algorithmic Support for Commodity-Based Parallel Computing Systems, 107
- Bunker, B. C.
Aging Mechanisms in Dormant MEMS Structures, 150
Assembly of Nanomaterials Using Active Biomolecules, 300
Molecular Integrated Microsystems, 725
Solution-Based Nanoengineering of Materials, 296
The Basics of Aqueous Nanofluidics, 278
- Buried (targets), 228
- Burns, A. R.
Interfacial Bioscience Grand Challenge, 680
Single-Channel Membrane Pores, 71
- Burns, G. R.
Microfabrication with Femtosecond-Laser Processing, 44
Rapid-Prototyping High-Density Circuitry, 59
- Buzzard, 629
- C**
- Cable, G. D.
Modeling Signals from Nuclear Weapons, 633
- Cadden, C. H.
LIGA Microsystems Aging: Evaluation and Mitigation, 268
- Calibration, 274
- Callow, D. S.
Buzzard, 629
- Cameron, S. M.
Photonic-Bandgap Structures for Sensor Protection, 595
Remote Mapping of Electromagnetic Fields, 399
- Campbell, J. E.
Multiobjective Discrete Optimization, 920
Prognostic Health Monitoring and Maintenance, 368
System-of-Systems Modeling and Analysis, 432
- Campbell, P. L.
Cryptographic Assurance of Execution Correctness, 642
Securing Mobile Code, 524
- Campbell, R. B.
Simulations of Intense Petawatt Laser Pulses, 336
- Campin, M. J.
Varying Humidity on Copper-Sulfide Film Formation, 293

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Cano, L. A.
Security Monitoring with Information Technology, 573
- Carbon
Adsorber, 906
Airborne, 468
Nanothread, 443
Nanotube composite, 875
Phases, 765
See also: Hydrocarbon
- Carlson, J. J.
Automated Video Screening for Unattended Monitoring, 904
Content-Based Video and Image Indexing System, 616
Obstacle Detection for Autonomous Navigation, 376
TALON, 690
Weapon-Platform Controls for Intelligent Targeting, 657
- Carlson, R. E.
Vulnerability Assessment of National Power Grid, 477
- Carr, D. W.
Nanoelectromechanical Oscillators for RF Filtering, 162
- Carr, R. D.
Algorithmic Support for Commodity-Based Parallel Computing Systems, 107
- Carroll, D. E.
Modeling Signals from Nuclear Weapons, 633
- Carter, T. R.
Arrayed Resonant Subwavelength Gratings, 562
Tagging for Tracking and Authentication of Documents, 577
- Casalnuovo, S. A.
Molecular Integrated Microsystems, 725
- Castaneda, J. N.
Rarefied-Gas Dynamics and Surface Interactions, 220
- Castro, J. P.
Dynamic Multilevel Hybrid Optimization, 131
- Catalyst
Fuel-cell, 527
Heterogeneous, 758
- Catalytic
Hydrocarbon separation, 457
Particulate trap, 499
- Catalyzation, 307
- CBW (chemical-biological warfare)
See Chemical
- Cederberg, J. G.
Quantum Coherence in Semiconductor Nanostructures, 187
- Celina, M. C.
Pulsed-Particle Beams on Metal-to-Plastic Interfaces, 918
PVDF as a Piezoelectric Film, 645
- Cell
Beta, 580
Microbial, 821
Observatory, 89
Sample pretreatment, 169
Signaling system, 75
Simulator, 129
Surface, 867
See also: Biomicrofuel cell
See also: Fuel cell
- Ceramic
High-temperature, 625
Metal interfaces, 262
- Cesarano, J., III
Biocompatible Self-Assembly of Nanomaterials, 248
Diesel Catalytic Particulate Traps, 499
Photocontrol of Nanointeractions in Microsystems, 284
Security Coatings for Multichip Modules, 612
- Chalcogenide, 174
- Chan, J. P.
Alanate-Hydride Fuel-Cell Demonstration Project, 515
- Chanchani, R.
An Integrated, Stacked System-on-a-Chip, 183
Linear Magnetic Actuators, 35
Miniaturization of SAR Electronic Assembly, 411
- Chandler, D. W.
Cellular Observatory, 89
Optical Trapping of Collisionally Cooled Molecules, 541
- Chandross, M. E.
Modeling Local Chemistry, 291
- Chang, M. C.
Augmented Cognition, 687
- Channel
Membrane pore, 71
Microfluid, 152
See also: Multichannel
- Chaotic, 430
- Chaplya, P. M.
Deployable Large-Aperture Optics System, 559
PVDF as a Piezoelectric Film, 645
- Chavez, B. D.
Rapid-Prototyping High-Density Circuitry, 59
- Chen, H. Y.
IP Storage: A Performance and Security Study, 126
Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Chen, J. H.
Microengine for Advanced Power Generation, 349
- Chem-bio
See Chemical
- Chemical
Chem-bio, 662
Decontamination, 389
Diffusion flame, 925
Ion-mobility spectrometer, 385
Nanoparticles, 511
Photochemical, 303
Plumes, 565
Preconcentrator, 550
Reagent delivery, 167
Suppression, 448
Terrorist attack, 136
Warfare, 637
Water, 491
See also: Microsensor
See also: Sensor
- Chemistry, 291
- Chemometric, 556

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Chhabra, S.
 Harnessing Methane-Hydrate Bacteria Interactions, 722
 High-Throughput Identification of Molecular Machines, 96
- Childs, J. M.
 Networked Device Demonstration, 667
- Childs, K. D.
 Functionalized Nanoparticles for Sensor Applications, 176
- Chimeric, 605
- Chinn, D. A.
 Advanced Digital Detectors for Neutron Imaging, 546
- Chloroplast, 83
- Chow, W. W.
 Active Photonic-Crystal Devices, 172
 A Revolution in Lighting, 671
 Leaky-Mode VCSELs for Photonic Logic Circuits, 195
 Quantum Coherence in Semiconductor Nanostructures, 187
- Christensen, J. B.
 Prompt Global Response, 696
- Christenson, T. R.
 Agile, Microsystems-Enabled Receiver, 600
 Determination of Microstructural Properties, 334
 Linear Magnetic Actuators, 35
 Photonic-Lattice Structures for Remote Sensing, 571
- Cich, M. J.
 Semiconductors for Optoelectronic Materials, 145
- Circuit
 Photonic logic, 195
 Rapid-prototyping, 59
 Simulator, 129
- Cleave, 305
- Clem, P. G.
 Active Photonic-Crystal Devices, 172
 Active Photonic Nanostructures, 321
 Micro Flame-Based Detector Suite, 437
 Rapid-Prototyping High-Density Circuitry, 59
- Clement, J. J.
 Security Coatings for Multichip Modules, 612
- Cloud, 434
- Coating
 Microelectromechanical, 877
 Preconcentrator, 550
 Simulation, 729
- Cochrane, K. R.
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
- Code
 Error-control, 912
 Securing mobile, 524
 Simulation, 124
- Cognition, 687
- Cognitive, 871
- Cohen, F. B.
 Mathematical Analysis of Deception, 739
- Cohen, I. D.
 IP Storage: A Performance and Security Study, 126
- Coilgun, 445
- Coker, E. N.
 Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
- Cole, P. J.
 Soft-Matter Nanolayer Superlattices, 282
- Coleman, P. D.
 Nonlethal Technologies for the War on Terrorism, 702
- Collins, C. R.
 Detection of Spread-Spectrum Waveforms, 552
- Collins, M. J.
 Hybrid Infrastructure Cryptography, 404
- Collision, 541
- Coltrin, M. E.
 A Revolution in Lighting, 671
- Combustion
 Microexternal, 773
 Particulate trap, 499
- Commercial products, 666
- Commodity, 107
- Communication
 Agents, 460
 Crisis management, 420
 Low-power, 575
 Secure chaotic, 430
- Compliant
 Actuators, 181
 Membranes, 784
- Composite
 Carbon nanotube, 875
 Field-structured, 271
 Ordered electrooptical, 312
 Patching systems, 844
- Compression, 334
- Computation/Computing
 Accelerator, 836
 Diffusion flame, 925
 Failure analysis, 100
 Phase transitions, 343
 Tomography, 655
 X-ray screening, 655
 See also: Algorithm
 See also: Model
- Concept of operations (CONOPS), 387
- Conductivity
 Metal alloys, 865
 See also: Superconductivity
- Conductor, 329
- Conformal, 51
- Connectivity, 597
- Conrad, G. N.
 Security Monitoring with Information Technology, 573
 Terrorist-Activity Plan-Assessment Methodology, 714
- Conscious, 734
- Container, 798
- Contamination
 Decomposition, 303
 Transport, 614
 Volatile, 463
 Water, 519
 See also: Decontamination

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Continuous-wave, 165
- Continuum
- Atomistic, 218
 - Sintering, 243
 - See also:* Noncontinuum
- Control
- Agent-based, 539
 - Cellular response, 867
 - Flow, 847
 - Graph theory, 416
 - Immunological, 409
 - Intelligent interaction, 57
 - Intelligent targeting, 657
 - Interface growth, 825
 - Internet connectivity, 597
 - Motion, 46
 - Nanoparticles, 838
 - Networks, 504
 - Nuclear, 509
 - Regulatory systems, 912
 - See also:* Photocontrol
- Converter (thermionic), 473
- Cook, B. K.
- Direct Simulation of Solid-Fluid Systems, 756
- Cook, D. J.
- Security Coatings for Multichip Modules, 612
- Coolant, 923
- Cooper, P. W.
- Autonomous Microexplosive Subsurface Tracing, 475
 - EM Interactions with Systems to Enhance Security, 392
- Cooper, S. P.
- Natural-Gas Production Problems, 480
- Copeland, R. G.
- Varying Humidity on Copper-Sulfide Film Formation, 293
- Copper-sulfide, 293
- Co-processing, 174
- Cordaro, J. T.
- Detection of Spread-Spectrum Waveforms, 552
- Cordeiro, P. G.
- Agent-Based Control of Infrastructure Resources, 539
- Cordwell, W. R.
- Networked Device Demonstration, 667
- Corey, J. D.
- Advanced Weapons Signatures, 659
 - Interactive Nuclear/WMD Terrorist Data Model, 716
- Cornelius, C. J.
- Advanced Proton-Exchange Materials for Fuel Cells, 513
 - Biomicrofuel Cell, 685
- Coronavirus, 543
- Corrosion, 265
- Cortex, 734
- Corwin, A. D.
- High-Fidelity Frictional Models for MEMS, 222
- Costin, L. S.
- Modeling of Rock Penetration, 747
 - Near-Real-Time Characterization for HDBT Defeat, 693
- Countermeasure, 346
- Counterterrorism
- Crisis management, 420
 - See also:* Terrorism
- Couple
- Cluster, 120
 - Mechanical modeling, 228
 - Multiphysics, 775
 - Simulation (acoustical/structural), 239
 - Simulation (atomistic-continuum), 218
- Covert, T. T.
- Assembly of Microsystems Using Thin Films, 54
- Cox, D. D.
- Detection of Spread-Spectrum Waveforms, 552
- Cox, J. V.
- Predictive Accelerated Aging of Microsystems, 795
- Cox, R. G.
- A Model of Infrastructure Interdependency, 460
 - Noninformative Priors from Metadata Conditioning, 894
- Cracks, 782
- Craft, D. C.
- Data Fusion and Visualization of MASINT Results, 355
- Crawford, M. H.
- Active Photonic Nanostructures, 321
- Creighton, J. R.
- A Revolution in Lighting, 671
- Criscenti, L. J.
- Solution-Based Nanoengineering of Materials, 296
- Crisis, 420
- Crozier, P. S.
- Interfacial Bioscience Grand Challenge, 680
- Cruz, D.
- Micromass Spectrometer-on-a-Chip, 185
- Cryptography
- Algorithms, 361
 - Confidentiality, 642
 - Hybrid infrastructure, 404
- Crystal
- Photonic, 172
 - Sapphire, 788
- CT (computer tomography)
- See* Computation/computing
- Cummings, E. B.
- Bioaerosol Collection for Detectors, 618
 - Microfabricated Dielectrophoretic Sample Preparation, 589
 - Sensor for Live Waterborne Pathogens, 793
- Cuppoletti, C. M.
- Neutron Monitors for JTA and Stockpile Monitoring, 811
- Curro, J. G.
- Self-Assembly of Polymers in Confined Geometries, 732
 - Sequestration of Pathogens on Nanoengineered Surfaces, 790
- Custer, J. S.
- Hermetic Packaging for MEMS Integrated Microsystems, 888
 - Quantification of Environments Within Micropackages, 309
- CW (chemical warfare)
- See* Chemical
- Cycle, 522

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Cygan, R. T.
 Dissolution of Carbonate Phases, 765
 Solution-Based Nanoengineering of Materials, 296
 Cylinder, 859
- D**
- Dagel, D. J.
 Ultralightweight Telescope with MEMS Adaptive Optic, 631
- Damage
 Bomb, 396
 Diffraction grating, 338
- Dargaville, T.
 PVDF as a Piezoelectric Film, 645
- Davidson, G. S.
 Informatics for Systems Biology, 78
 Immune Responses to Bioterrorism Threats, 93
- Davidson, P. A., Jr.
 Content-Based Video and Image Indexing System, 616
- Davis, C. E.
 Monitoring of Volatile Contaminants, 463
- Davis, D. W.
 Rapid-Prototyping High-Density Circuitry, 59
- Davis, J. P.
 Liquid-Liquid and Freezing Phase Transitions, 343
- Davis, J. Z.
 SDAC Architectural Study and Demonstration System, 705
- Day, D. M.
 Geophysical Subsurface Imaging, 857
- De Boer, M. P.
 Aging Mechanisms in Dormant MEMS Structures, 150
 Assembly of Nanomaterials Using Active Biomolecules, 300
 High-Fidelity Frictional Models for MEMS, 222
 Integrated Metal Surface Micromachines, 178
 Integrated Superhard and Metallic Coatings for MEMS, 877
 Predicting and Validating MEMS Interface Reliability, 753
 Predictive Accelerated Aging of Microsystems, 795
- Deception, 739
- Decision, 394
- Decomposition, 303
- Decontamination
 Air sterilization, 353
 Toxic chemicals, 389
 Virus, 543
- Decoy, 441
- Defeat (hard target)
 Characterization, 693
 Fuze, 407
- Defense
 Borders, 699
 Directed energy weapons, 863
- Deformation
 Inelastic, 788
 Nonlinear, 736
 Solid-fluid, 212
- DeGroot, J. S.
 Simulations of Intense Petawatt Laser Pulses, 336
- Deland, S. M.
 Security Monitoring with Information Technology, 573
 TALON, 690
- Delivery, 167
- Demmie, P. N.
 Dynamic Multilevel Hybrid Optimization, 131
- Denison, G. J.
 EM Interactions with Systems to Enhance Security, 392
- Dentinger, P. M.
 Highly Specific Electronic Signal Transduction, 819
 Molecular Electronics Test Platform, 908
- Deoxyribonucleic acid (DNA), 819
- Deposition
 Lithography, 287
 Thin-film, 40
 Tribological coating, 51
- Depoy, J. M.
 Surety for Wireless Automated-Control Networks, 504
- Desalination, 496
- Desjarlais, M. P.
 Electrical Conductivity of Metal Alloys, 865
- Desonier, L. M.
 Real-Time Water-Quantity/-Quality Monitoring, 486
- Desorption, 307
- Detector
 Airborne carbon, 468
 Biomimetic air sampling, 823
 Chem-bio, 662
 Enrichment of bioaerosols, 924
 Error control, 912
 Genetic engineering, 621
 Ground sensors, 428
 Headspace gas, 502
 Insider, 587
 Ion-mobility spectrometer, 385
 Lipid microarray, 885
 Micro flame-based, 437
 Microfluidic microarray, 605
 Microseparation, 618
 Neutron imaging, 546
 Obstacle, 376
 Seismic event, 897
 Semiconductor nanostructures, 187
 Spread-spectrum waveforms, 552
 Waveforms, 710
- Devine, K. D.
 Parallel Repartitioning for Optimal Solver Performance, 110
- Deyle, T. J.
 Smart Sensors for Joint Test Assembly Flights, 102
- Diagnostic
 Airborne carbon, 468
 Rarefied flows, 855
 Rayleigh-scattering, 203
- Dibble, D. C.
 Alloys for LIGA Micromachines, 287
- Dielectrophoretic, 589

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Diesel, 499
 Diffraction, 338
 Diffusion flames
 Particulate, 925
 Soot, 225
 Digital
 Detectors, 546
 Radar, 363
 Signal processing, 603
 Dillinger, J. D.
 Surety for Wireless Automated-Control Networks, 504
 Dimkoff, J. L.
 Smart Sensors for Joint Test Assembly Flights, 102
 Dirk, S. M.
 Functionalized Nanoparticles for Sensor Applications, 176
 Sensors for Water-Contamination Events, 519
 Disbonding, 782
 Dislocation, 252
 Distortion, 631
 Djordjevich, D. D.
 Communication in Counterterrorism Crisis Management, 420
 DNA
 See Deoxyribonucleic acid
 Documents, 577
 Dodd, P. E.
 Radiation-Hardened Optoelectronic Components, 635
 Dohner, J. L.
 Compliant Thermomechanical MEMS Actuators, 181
 Coupled Simulations of Weapons Systems, 239
 Nonlethal Technologies for the War on Terrorism, 702
 Polychromator Systems for Remote Chemical Sensing, 197
 Dohrmann, C. R.
 Nonlinear Structural Mechanics, 105
 Domeier, L. A.
 Thermally Cleavable Surfactants, 305
 Dormancy
 Microelectromechanical, 150
 Microsystems, 795
 Doser, A. B.
 Adaptive Awareness for Personal Decision Making, 394
 Cognitive Models Applied to Human Effectiveness, 871
 Enabling Technology for Human Collaboration, 718
 Prognostic Health Monitoring and Maintenance, 368
 Smart Sensors for Joint Test Assembly Flights, 102
 Doty, F. P.
 Advanced Digital Detectors for Neutron Imaging, 546
 Draelos, T. J.
 Hybrid Infrastructure Cryptography, 404
 Joint Authentication/Encryption, 623
 Securing Mobile Code, 524
 Draper, B. L.
 MOSFET–MEMS Integration, 189
 Radiation-Hard Nonvolatile Memories, 174
 Dreike, P. L.
 Modeling Signals from Nuclear Weapons, 633
 Drennen, T. E.
 Analysis Support for Senate Energy Committee, 537
 Hydrogen Futures Dynamic-Simulation Model, 535
 Drotning, W. D.
 Flexible Robotic Maintenance Facility, 373
 Drummond, T. J.
 Automation of Microelectronic Physical Analysis, 592
 Photonic-Lattice Structures for Remote Sensing, 571
 Dubbert, D. F.
 Low-Cost Digital Radar, 363
 Dubicka, I.
 Interactive Nuclear/WMD Terrorist Data Model, 716
 Terrorist-Activity Plan-Assessment Methodology, 714
 Ductile, 207
 Dudley, P. A.
 Low-Cost Digital Radar, 363
 Ultracompact, Ultralow-Power Communications, 575
 Duggan, D. P.
 Surety for Wireless Automated-Control Networks, 504
 Dugger, M. T.
 Atomic-Layer Deposition of Tribological Coatings, 51
 Mechanics and Tribology of MEMS Materials, 258
 Predictive Accelerated Aging of Microsystems, 795
 Dulleck, G. R., Jr.
 Autonomous Microexplosive Subsurface Tracing, 475
 Sensors for Water-Contamination Events, 519
 Dunn, R. G.
 Engineered Superconductivity in Electron-Hole Bilayers, 157
 Durability, 918
 Duran, P. S.
 Sensing of Phase Transformations in Steels, 48
 Durgin, N. A.
 Mathematical Analysis of Deception, 739
 Dyck, C. W.
 Agile, Microsystems-Enabled Receiver, 600
 Integrated Metal Surface Micromachines, 178
 Miniature High-Power RF Components, 861
 Nanoelectromechanical Oscillators for RF Filtering, 162
 Silicon-Based RF MEMS Components, 160
E
 Eddy, 892
 Eicker, P. J.
 TALON, 690
 Eidson, E. D.
 A Model of Infrastructure Interdependency, 460
 Einfeld, W.
 Identification of Regulated Chemicals in Water, 491
 Sensors for Water-Contamination Events, 519
 Eisenbies, S. K.
 Biomicrofuel Cell, 685
 Eisler, G. R.
 Understanding Metal Vaporization, 256
 Ejector, 46
 Elastomer, 319

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Elbring, G. J.
 Assessment of Bomb Damage to Underground Facilities, 396
 Near-Real-Time Characterization for HDBT Defeat, 693
- Eldridge, J. M.
 Cryptographic Assurance of Execution Correctness, 642
- Electrical, 865
- Electrochemical, 287
- Electrode
 Nanostructured, 834
See also: Nanoelectrode
- Electromagnetic (EM)
 Security, 392
 Terahertz transceivers, 399
- Electromechanical
 Energy harvester, 750
 Nanoelectromechanical oscillator, 162
- Electron
 Bilayers, 157
 Emission, 329
 Weapon, 863
- Electronic
 Membrane signaling, 86
 Molecular, 908
 Signal transduction, 819
 Structure method, 120
 Synthetic-aperture radar, 411
 Upset, 371
See also: Microelectronic
See also: Optoelectronic
- Electrooptic
 Assembly, 312
 Free-space sampling, 399
- Electrostatically (actuated)
 Microelectromechanical, 849
 Micropumps, 910
- Elizondo-Decanini, J. M.
 Laser Triggering of Water Switches in Accelerators, 341
- El-Kay, I. F.
 Active Photonic-Crystal Devices, 172
- Ellis, C. R. B.
 Bioaerosol Collection for Detectors, 618
- Ellis, L. J.
 Augmented Cognition, 687
 TALON, 690
- Ellis, R. V.
 Nanoelectromechanical Oscillators for RF Filtering, 162
- EM
See Electromagnetic
- Embodiment, 113
- Emerson, J. A.
 Adhesive Bonding in Microfabrication, 42
 A Revolution in Lighting, 671
 Micro-/Nanoscale Thermomechanical Manufacturing, 853
- Emission, 329
- Emit, 399
- Encryption
 Joint authentication, 623
 Photonic, 901
- Energetic materials, 744
- Energy
 Bacteria, 722
 Committee, 537
 Directed, 863
 Distributed resources, 494
 Excitation, 289
 Feedstock separations, 457
 Fuel cell, 513
 Harvester, 750
- Engine
 Microexternal combustion, 773
See also: Microengine
- Engler, B. P.
 Autonomous Microexplosive Subsurface Tracing, 475
 Near-Real-Time Characterization for HDBT Defeat, 693
- Enrichment, 924
- Ensz, M. T.
 Controlled Motion for a Microfluidic Drop Ejector, 46
- Enterprise modeling, 115
- Environmental-sensing device (ESD), 809
- Ephemeral, 486
- Eras, K.
 Nuclear Safety for Thermal and Mechanical, 801
- Error control, 912
- ESD
See Environmental-sensing device
- Esherrick, P.
 Membrane Signaling in Affinity-Based Biosensors, 86
 Tagging for Tracking and Authentication of Documents, 577
- Estrada, J. K.
 Neutron Monitors for JTA and Stockpile Monitoring, 811
- EUVL (extreme ultraviolet lithography)
See Lithography
- Evans, G. H.
 A Revolution in Lighting, 671
- Evans, K. O.
 Interfacial Bioscience Grand Challenge, 680
 Single-Channel Membrane Pores, 71
- Evans, L.
 Water Desalination, 496
- Excitation, 289
- Exothermic, 54
- Explosive
 Hard target, 407
 Ion-mobility spectrometer, 385
 Micropreconcentrators, 637
 Subsurface tracing, 475
- Eye-safe, 434

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- F**
- Fabrication
 Carbon nanothread, 443
 See also: Microfabrication
- Failure analysis
 Composite patching, 844
 Micromachines, 100
- Fan, H.
 Microsystems for Reagent Delivery, 167
- Fang, H. E.
 Determination of Microstructural Properties, 334
- Farnsworth, A. V., Jr.
 Modeling Signals from Nuclear Weapons, 633
- Faulon, J. M.
 Immune Responses to Bioterrorism Threats, 93
 Interfacial Bioscience Grand Challenge, 680
 Membrane Protein Interactions in Cell Signaling, 75
- Feddema, J. T.
 Advanced Mobile Networking Using Graph Theory, 416
- Feedstock, 457
- Feibelman, P. J.
 The Basics of Aqueous Nanofluidics, 278
- Fein, D. B.
 Biomicrofuel Cell, 685
- Femtosecond
 Laser processing, 44
 Terahertz transceivers, 399
- Ferrizz, R. M.
 Diesel Catalytic Particulate Traps, 499
- Fiechtner, G. J.
 Microfabricated Dielectrophoretic Sample Preparation, 589
- Figiel, J. J.
 A Revolution in Lighting, 671
- Film
 Copper-sulfide, 293
 Machining, 40
 Multilayer, 54
 Nanomagnetic, 872
 Nanoscale, 232
 Piezoelectric, 645
- Filter
 Nanoelectromechanical, 162
 Rayleigh-scattering, 203
 Transmitter, 807
- Fintschenko, Y.
 Sensor for Live Waterborne Pathogens, 793
- Fireset, 804
- Fire-suppression, 448
- Fischer, A. J.
 A Revolution in Lighting, 671
- Fischer, G. J.
 Buzzard, 629
- Fischer, T. A.
 An Integrated, Stacked System-on-a-Chip, 183
 Miniaturization of SAR Electronic Assembly, 411
- Flack, C. J.
 Polymer Spin-Coating for Semiconductors, 254
- Flame
 Detector, 437
 Particulate formation, 925
 Soot, 225
- Flash, 422
- Fleming, J. G.
 Active Photonic-Crystal Devices, 172
 Active Photonic Nanostructures, 321
 Integration of Advanced Photonics and MEMS, 148
 Microoptical Gyroscope Via Optical Integration, 191
 Silicon-Based RF MEMS Components, 160
 Single-Channel Membrane Pores, 71
- Fleming, R. P.
 Automation of Microelectronic Physical Analysis, 592
- Flemming, J. H.
 Biomicrofuel Cell, 685
 Membrane Signaling in Affinity-Based Biosensors, 86
- Flight, 102
- Flores, R. S.
 Radiation-Hard Nonvolatile Memories, 174
- Floro, J. A.
 Nanostructured Materials for Directed Transport, 289
- Flow
 Information, 708
 Microfluidic devices, 847
 Noncontinuum gas, 234
 Rarefied, 855
 Turbulent, 892
- Fluid
 Deformation, 212
 Fracture, 228
 Porous media, 762
 Rayleigh scattering, 203
 Simulation, 756
 Uncertainty propagation, 200
 See also: Microfluid
 See also: Nanofluid
- Focal, 652
- Foehse, M. C.
 Interactive Nuclear/WMD Terrorist Data Model, 716
- Fogler, R. J.
 Near-Real-Time Characterization for HDBT Defeat, 693
- Foiles, S. M.
 Integrated Metal Surface Micromachines, 178
 Liquid-Liquid and Freezing Phase Transitions, 343
- Follstaedt, D. M.
 A Revolution in Lighting, 671
 Direct Single-Ion Machining of Nanopores, 916
 Efficiency of GaN HEMT High-Power Amplifiers, 193
 Integrated Metal Surface Micromachines, 178
- Foltynowicz, R. J.
 Continuous-Wave Intersubband Terahertz Sources, 165
 Quantum Coherence in Semiconductor Nanostructures, 187

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Ford, B. K.
Geologic Characterization of Difficult Targets, 584
- Forman, M. A.
Algorithm Development for Smart Antennas, 842
Miniature Transmitter Filter for JTA, 807
- Forsythe, J. C.
Augmented Cognition, 687
Communication in Counterterrorism Crisis Management, 420
Improving Human/System Interactions, 425
Simulator Agents with Humanlike Episodic Memory, 359
- Fossum, A. F.
Computational Modeling of Fracture in Geomaterials, 228
Modeling of Rock Penetration, 747
Near-Real-Time Characterization for HDBT Defeat, 693
- Foulk, J. W., III
Modeling Carbon Nanotube-Reinforced Composites, 875
- Fourier, 385
- Fowler, W. E.
Suppression of Electron Emission from Conductors, 329
- Fracture
Ductile, 207
Geomaterials, 228
Nonlinear deformation, 736
- Fragmentation, 228
- Franco, R. J.
Algorithm Development for Smart Antennas, 842
- Franklin, J. W.
Novel and Robust Environmental-Sensing Devices, 809
- Freeze, 343
- Frequency, 89
- Frew, D. J.
Modeling of Rock Penetration, 747
Near-Real-Time Characterization for HDBT Defeat, 693
- Friction
Microelectromechanical, 222
Micromachine, 883
- Friedmann, T. A.
Direct Single-Ion Machining of Nanopores, 916
Microfabricated Acoustic-Spectrum Analyzer, 547
Nanoelectromechanical Oscillators for RF Filtering, 162
- Frink, D. L. J.
Interfacial Bioscience Grand Challenge, 680
Membrane Signaling in Affinity-Based Biosensors, 86
Modeling Biomembranes, 91
- Frischknecht, A. L.
Modeling Biomembranes, 91
- Fruetel, J. A.
Chem-Bio Sensing in Microfluidic Systems, 662
Sequestration of Pathogens on Nanoengineered Surfaces, 790
- Fuel cell
Alanate-hydride, 513
Energy-efficient, 513
Hydrogen, 527
See also: Biomicrofuel cell
- Fuerschbach, P. W.
Understanding Metal Vaporization, 256
- Fujimoto, C. H.
Biomicrofuel Cell, 685
- Fuller, C. T.
Continuous-Wave Intersubband Terahertz Sources, 165
- Furnish, M. D.
Determination of Microstructural Properties, 334
- Futures, 535
- Fuze
Digital radar, 363
High-G tolerant, 407
See also: Microfuze
- G**
- GaAs, 890
- Galambos, P. C.
Controlled Motion for a Microfluidic Drop Ejector, 46
Magnetically and Electrostatically Actuated Micropumps, 910
Microfluidic Cellular Sample Pretreatment, 169
- Gallegos, D. E.
Advanced Unattended Ground-Sensor Technology, 357
Critical-Infrastructure Interdependencies, 489
- Gallegos, D. P.
Augmented Cognition, 687
TALON, 690
- Gallis, M. A.
Diagnostics for Rarefied Flows in MEMS Applications, 855
High-Efficiency Turbine Blade Coatings, 483
Rarefied-Gas Dynamics and Surface Interactions, 220
Simulate Noncontinuum Gas Flows for MEMS Devices, 234
- Gallup, D. R.
Improved Performance in Cryptographic Protocols, 361
- GaN (HEMTs)
High-field effects, 869
Improved efficiency, 193
- Ganter, J. H.
Anomalous Weapon Surveillance Waveforms, 710
Augmented Cognition, 687
- Ganti, A.
Quantum Computing Accelerator I/O, 836
- Gao, H.
Microsensors in Radioactive-Waste Management, 502
Self-Assembled Materials in Waste Management, 466
- Gardner, D. R.
Near-Real-Time Characterization for HDBT Defeat, 693
- Gardner, T. J.
Diesel Catalytic Particulate Traps, 499
- Gartling, D. K.
Contaminant Transport in Architectural Spaces, 614
- Gas
Dynamics, 220
Flame-based detector, 437
Headspace detection, 502
Power-conversion, 522
Production problems, 480
Simulate flows, 234

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Gass, F. R.
Ultralightweight Telescope with MEMS Adaptive Optic, 631
- Gaucher, S. P.
High-Throughput Identification of Molecular Machines, 96
- Gee, J. M.
A Revolution in Lighting, 671
- Geib, K. M.
Leaky-Mode VCSELs for Photonic Logic Circuits, 195
Radiation-Hardened Optoelectronic Components, 635
- Gelbard, F.
Supercritical Water Reactor Safety Technologies, 922
- Geller, A. S.
Contaminant Transport in Architectural Spaces, 614
- Ge/Si, 851
- Genetic, 621
- Geomaterial, 228
- Geometry, 732
- Geophysical, 857
- Getters, 246
- Ghormley, D. P.
Active Network and Use of Network Processor, 607
- Gibson, C. L.
Completely Passive Microwave Tag, 610
Zero-Power Radio Receiver, 608
- Gilchrist, R. T.
Near-Real-Time Characterization for HDBT Defeat, 693
- Gilkey, J. C.
Levitated Three-Axis Microaccelerometer, 38
- Gill, D. D.
Next-Generation Spindles for Micromilling, 64
- Gillen, K. T.
PVDF as a Piezoelectric Film, 645
- Gillen, L. W.
Interactive Nuclear/WMD Terrorist Data Model, 716
- Ginn, J. W.
Agent-Based Control of Infrastructure Resources, 539
- Giron, J. W.
Advanced Unattended Ground-Sensor Technology, 357
- Giunta, A. A.
Dynamic Multilevel Hybrid Optimization, 131
Micromagnetic Suspension, 122
- Giunta, R. K.
Adhesive Bonding in Microfabrication, 42
Controlled Motion for a Microfluidic Drop Ejector, 46
Elucidating the Mysteries of Wetting, 61
- Givler, R. C.
Controlled Motion for a Microfluidic Drop Ejector, 46
- Gladwell, T. S.
Automated Visual Direction of Mobile Manipulation, 383
- Glass, M. W.
Simulate Noncontinuum Gas Flows for MEMS Devices, 234
- Glass, S. J.
Nuclear Safety for Thermal and Mechanical, 801
Ultrahigh-Temperature Ceramics, 625
- Goeke, R. S.
Atomic-Layer Deposition of Tribological Coatings, 51
Metal-/Oxide-Joining in NW Component Manufacturing, 899
- Goldsby, M. E.
Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Gomez, B. J.
Anomalous Weapon Surveillance Waveforms, 710
- Gonzales, A. I.
Augmented Cognition, 687
- Gonzales, M. A.
Dynamic Multilevel Hybrid Optimization, 131
- Gonzales, R. A.
Joint Authentication/Encryption, 623
- Goudy, S. P.
Commodity-Based Parallel Computing Systems, 107
- Graf, D. C.
Novel and Robust Environmental-Sensing Devices, 809
- Graham, S., Jr.
High-Efficiency Turbine Blade Coatings, 483
Hotspots Due to Nonequilibrium Thermal Transport, 770
Multiscale Thermal Modeling, 215
- Graph theory, 416
- Grasser, T. W.
Filtered Rayleigh-Scattering Diagnostic, 203
Rarefied-Gas Dynamics and Surface Interactions, 220
- Grating
Diffraction, 338
Subwavelength, 562
- Gray, P. C.
Air Sterilization and Decontamination, 353
- Green, D. L.
Advanced Weapons Signatures, 659
- Green, J. M.
Automation of Microelectronic Physical Analysis, 592
- Greene, S. N.
Hard Target Defeat High-G-Tolerant Fuze, 407
- Greenway, D., Jr.
Low-Cost Digital Radar, 363
Multipurpose Locator-Tag System, 664
- Grest, G. S.
Advanced Proton-Exchange Materials for Fuel Cells, 513
Elucidating the Mysteries of Wetting, 61
- Griffith, M. L.
Manufacturing Techniques Using Rapid Prototyping, 887
Microfabrication with Femtosecond-Laser Processing, 44
Rapid-Prototyping High-Density Circuitry, 59
- Griffiths, R. A.
TALON, 690
- Griffiths, S. K.
Ultraclean Environments in Microsystem Packages, 246
- Grillet, A. M.
Elucidating the Mysteries of Wetting, 61
- Gross, K. J.
Alanate-Hydride Fuel-Cell Demonstration Project, 515
Catalyzation of Complex-Hydride Reactions, 307

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Grotbeck, C. L.
 Arrayed Resonant Subwavelength Gratings, 562
- Growth
 GaAs, 890
 Ge/Si, 851
 Interface, 825
 Nanoscale, 263
- Grubelich, M. C.
 Assembly of Microsystems Using Thin Films, 54
 Autonomous Microexplosive Subsurface Tracing, 475
- Guess, B. D.
 Detection of Spread-Spectrum Waveforms, 552
- Gullett, P. M.
 Failure Analysis of Micromachines, 100
 Multiscale Experimental/Numerical Study, 786
- Guo, J.
 Dispersive Photonics for Sensors and Microsystems, 155
 Microoptical Gyroscope Via Optical Integration, 191
- Gurule, E. J.
 Completely Passive Microwave Tag, 610
 Zero-Power Radio Receiver, 608
- Guzman-Kammler, V.
 Ultracompact, Ultralow-Power Communications, 575
- Gyroscope, 191
- H**
- Haaland, D. M.
 Immune Responses to Bioterrorism Threats, 93
 Informatics for Systems Biology, 78
 Multivariate Spectral Calibration Algorithms, 274
 Robust Chemometrics for Remote Spectral Sensing, 556
- Habbitt, R. D., Jr.
 A Systems Approach to Defending Our Borders, 699
- Hadi, M. Z.
 High-Throughput Identification of Molecular Machines, 96
 Interfacial Bioscience Grand Challenge, 680
- Hadley, G. R.
 A Revolution in Lighting, 671
 Arrayed Resonant Subwavelength Gratings, 562
 Dispersive Photonics for Sensors and Microsystems, 155
 Integration of Advanced Photonics and MEMS, 148
 Leaky-Mode VCSELs for Photonic Logic Circuits, 195
 Photonic-Lattice Structures for Remote Sensing, 571
- Hafenrichter, E. S.
 Microfuze, 380
- Hafich, M. J.
 Dispersive Photonics for Sensors and Microsystems, 155
- Hagan, M. R.
 Advanced Weapons Signatures, 659
- Hall, A. C.
 Nuclear Safety for Thermal and Mechanical, 801
 Security Coatings for Multichip Modules, 612
- Hamilton, J. C.
 First-Principles Determination of Dislocation Properties, 252
- Hamilton, T. W.
 Micro Flame-Based Detector Suite, 437
- Hammerand, D. C.
 Failure Analysis of Composite Patching, 844
- Hampton, J. W.
 Near-Real-Time Characterization for HDBT Defeat, 693
 TALON, 690
- Hard
 Nonvolatile memories, 174
 Optoelectronics, 635
 HDBT (characterization), 693
 HDBT (explosives), 407
 HDBT (modeling), 228
See also: Superhard
- Hardin, T.
 Low-Cost Digital Radar, 363
- Hardy, R. D.
 Modeling of Rock Penetration, 747
- Hareland, W. A.
 Anomalous Weapon Surveillance Waveforms, 710
- Hargett, T. W.
 Semiconductors for Optoelectronic Materials, 145
- Harmony, D. W.
 Moving-Target Identification, 413
- Haroldsen, B. L.
 Microengine for Advanced Power Generation, 349
- Harrington, J. J.
 Advanced Mobile Networking Using Graph Theory, 416
 CONOPS Development for Automated Systems, 387
- Harris, D. L.
 Analysis Support for Senate Energy Committee, 537
 CONOPS Development for Automated Systems, 387
 Hybrid Infrastructure Cryptography, 404
 Securing Mobile Code, 524
- Harris, S. M.
 Hard Target Defeat High-G-Tolerant Fuze, 407
 Microfuze, 380
- Hart, B.
 Information Assurance for Wireless *Ad Hoc* Networks, 401
- Hart, D.
 New Seismic-Event-Detection Technology, 897
- Hart, W. E.
 Algorithms for Simulations of Chemical Attacks, 136
 Error-Control Codes for Engineered Regulatory Systems, 912
 Micromagnetic Suspension, 122
- Harvester, 750
- Harvey, L. S.
 Advanced Mobile Networking Using Graph Theory, 416
- Hascall, A. G.
 Support-Active-Site Interactions in Catalysts, 758
- Haschke, G. B.
 Acoustic-Seismic Target Identification, 603
 Detection of Spread-Spectrum Waveforms, 552
- Hauser, G. C.
 Air Sterilization and Decontamination, 353
- Hayden, C. C.
 Cellular Observatory, 89

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Hayward, D. R.
Passive-Legged, Multisegmented, Robotic Vehicle, 568
- HDBT (hard and deeply buried target)
See Hard
- Headley, T. J.
Compliant Thermomechanical MEMS Actuators, 181
- Headspace, 502
- Health, 368
- Heaphy, R. T.
Parallel Repartitioning for Optimal Solver Performance, 110
- Hearne, S. J.
Assembly of Nanomaterials Using Active Biomolecules, 300
Integrated Metal Surface Micromachines, 178
- Heath, A. P., Jr.
Security Monitoring with Information Technology, 573
- Hebner, G. A.
High-Efficiency Turbine Blade Coatings, 483
- Heine, D. R.
Elucidating the Mysteries of Wetting, 61
- Heinstein, M. W.
Nonlinear Structural Mechanics, 105
- Heintzleman, R. E.
Low-Cost Digital Radar, 363
- Hekmaty, M. A.
Microengine for Advanced Power Generation, 349
- Heller, E. J.
Completely Passive Microwave Tag, 610
Microfabricated Acoustic-Spectrum Analyzer, 547
Zero-Power Radio Receiver, 608
- Heller, M. M.
Linear Magnetic Actuators, 35
- Helmick, P. H.
Gas Power-Conversion Systems for Nuclear Reactors, 522
Icosahedral Boride Semiconductor Beta Cell, 580
- Hembree, C. E.
Radiation Aging of Microelectronics, 210
- HEMT
See High-electron-mobility transistor
- Henderson, C. C.
Determination of Microstructural Properties, 334
- Hendrickson, B. A.
Massively Parallel Linear Programming, 139
Parallel Repartitioning for Optimal Solver Performance, 110
- Hermetic, 888
- Heroux, M. A.
Massively Parallel Linear Programming, 139
Parallel Repartitioning for Optimal Solver Performance, 110
- Herrin, J. M.
Natural-Gas Production Problems, 480
- Hertel, E. S., Jr.
Evolution of Near-Surface Scalar Concentrations, 859
Lateral Growth and Surface Morphology of GaAs, 890
- Hewson, J. C.
Computational Studies of JP-8 Diffusion Flames, 925
- Heying, M. R.
Advanced Unattended Ground-Sensor Technology, 357
- Hickman, R. J.
Determination of Microstructural Properties, 334
- Hickox, C. E., Jr.
Contaminant Transport in Architectural Spaces, 614
- Hietala, V. M.
Nonlethal Technologies for the War on Terrorism, 702
- Highley, A. M.
Interfacial Bioscience Grand Challenge, 680
- High-electron-mobility transistor (HEMT)
High-field effects, 869
Materials physics, 193
- Hill, T. A.
Radiation-Hard Nonvolatile Memories, 174
- Hillaire, R. G.
A Systems Approach to Defending Our Borders, 699
- Hilton, N. R.
Neutron Monitors for JTA and Stockpile Monitoring, 811
- Hinkebein, T. E.
Water Desalination, 496
- Hinman-Sweeney, E. M.
System-of-Systems Modeling and Analysis, 432
- Hirano, H. H.
Adaptive Awareness for Personal Decision Making, 394
- Hjalmarsen, H. P.
Radiation Aging of Microelectronics, 210
- Ho, C. K.
Microsensors in Radioactive-Waste Management, 502
Monitoring of Volatile Contaminants, 463
- Hoffman, M. M.
Advanced Weapons Signatures, 659
- Holcomb, D. J.
Modeling of Rock Penetration, 747
Near-Real-Time Characterization for HDBT Defeat, 693
- Holland, J. F.
Natural-Gas Production Problems, 480
- Hollenshead, J. T.
Near-Real-Time Characterization for HDBT Defeat, 693
- Hollowell, J. A.
Moving-Target Identification, 413
- Holm, E. A.
Controlling Interface Growth and Morphology, 825
Packaging Technology for Microsystems, 315
- Holman, R. M.
Detection of Spread-Spectrum Waveforms, 552
- Homeland security, 136
- Hong, J.
Interfacial Bioscience Grand Challenge, 680
Membrane Protein Interactions in Cell Signaling, 75
- Hopkins, M. M.
Magnetic-Field Effects on Vacuum-Arc Plasmas, 242
- Horn, B. A.
Chem-Bio Sensing in Microfluidic Systems, 662
- Hosking, F. M.
Assembly of Microsystems Using Thin Films, 54
- Hotspot, 770

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Hough, P. D.
 Communication in Counterterrorism Crisis Management, 420
 Dynamic Multilevel Hybrid Optimization, 131
 Stochastic Programming for Enterprise Modeling, 115
- Howard, J. D.
 Mathematical Analysis of Deception, 739
- Howard, M. S.
 Prompt Global Response, 696
- Howell, S. W.
 Functionalized Nanoparticles for Sensor Applications, 176
- Howle, V. E.
 Massively Parallel Linear Programming, 139
- Hoyt, J. J.
 Atomistic-Continuum Simulation, 218
 Controlling Interface Growth and Morphology, 825
 Liquid-Liquid and Freezing Phase Transitions, 343
- HSI
See Hyperspectral imaging
- Hsia, A. H.
 MOSFET–MEMS Integration, 189
- Huber, D. L.
 Magnetostrictive Elastomers for Actuators and Sensors, 319
 Molecular Integrated Microsystems, 725
 Sequestration of Pathogens on Nanoengineered Surfaces, 790
 The Basics of Aqueous Nanofluidics, 278
- Huber, R. J.
 MOSFET–MEMS Integration, 189
- Hudgens, J. J.
 Microoptical Gyroscope Via Optical Integration, 191
- Hughes, R. C.
 Biomimetic Air Sampling for Detection of Bioagents, 823
 High Photocurrents in Nanostructured Electrodes, 834
 Interfacial Bioscience Grand Challenge, 680
 Membrane Signaling in Affinity-Based Biosensors, 86
 Microsensors in Radioactive-Waste Management, 502
 Monitoring of Volatile Contaminants, 463
- Human
 Collaboration, 718
 Effectiveness, 871
 Episodic memory, 359
 System interaction, 425
- Humidity, 293
- Hunka, D. E.
 Energy-Efficient Feedstock Hydrocarbon Separations, 457
 Ion-Mobility Spectrometer/Mass Spectrometer, 640
- Hunter, J. A.
 Computed Tomography X-Ray Screening, 655
- Hunter, L. L.
 Molecular Electronics Test Platform, 908
- Hurley, R. B.
 Miniaturization of SAR Electronic Assembly, 411
- Hutchins, J. A.
 Adaptive Network Countermeasures, 346
 Surety for Wireless Automated-Control Networks, 504
- Hutchinson, S. A.
 A Parallel Circuit Simulator for Cell Biology, 129
- Hybrid
 Infrastructure cryptography, 404
 Optimization scheme, 131
- Hydride
 Catalyzation, 307
 Fuel cell, 513
- Hydrocarbon, 457
- Hydrogen
 Fuel-cell, 527
 Futures, 535
 Microbioreactor, 813
- Hypersonic, 625
- Hyperspectral imaging, 647
- I**
- IBIG
See Interfacial Bioscience Grand Challenge
- Icosahedral boride semiconductor (IBS), 580
- Identification
 Chemical plumes, 565
 Chemicals in water, 491
 Explosives, 385
 Geophysical interface, 857
 Hyperspectral tagging, 647
 Molecular machines, 96
 Moving target, 413
 Target, 603
- Image
 Digital detectors, 546
 Digital radar, 363
 Hyperspectral imagery, 649
 Indexing, 616
 Subsurface, 857
 Synthetic-aperture radar, 451
 X-ray, 378
- Imbert, M. H.
 Prompt Global Response, 696
- Immune
 Bioterrorism threats, 93
 Systems control, 409
- Impact, 422
- Index, 616
- Inelastic, 788
- Inertial fusion energy, 327
- Informatics, 78
- Information
 Assurance, 401
 Borders, 708
 Secure monitoring, 573
- Infrared, 565
- Infrastructure
 Cryptography, 404
 Interdependencies, 489
- Infusion, 780

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Ingersoll, D.
 Advanced Proton-Exchange Materials for Fuel Cells, 513
 Biomicrofuel Cell, 685
- Ingham-Hill, L. A.
 Anomalous Weapon Surveillance Waveforms, 710
- Initiation (disbonding), 782
- Input/output, 836
- Insch, K. W.
 Cryptographic Assurance of Execution Correctness, 642
- Insect, 248
- Insider, 587
- Integrate
 Metallic coatings, 877
 Microarray, 605
 Microdevice power source, 83
 Micromachines, 178
 Micropump, 910
 Microsystem packaging, 888
 Molecular microsystem, 725
 MOSFET–MEMS, 189
 Optical, 191
 Photonics (crystal), 172
 Photonics (MEMS), 148
 Substrate technology, 411
 System-on-a-chip, 183
- Intelligent
 Augmented cognition, 687
 Interaction control, 57
 Targeting, 657
- Interdependent (infrastructure)
 Communication agents, 460
 Mathematical algorithms, 489
- Interface
 Growth, 825
 Metal/ceramic, 262
 Metal-to-plastic, 918
 Microelectromechanical, 753
 Micromachine, 883
 Subsurface, 857
- Interfacial Bioscience Grand Challenge, 680
- International, 708
- Internet
 Connectivity, 597
 Multichannel messaging, 669
 Storage, 126
- Interphase, 278
- Intersubband, 165
- I/O
 See Input/output
- Iodine-sulfur, 517
- Ion
 Fourier-transform spectrometer, 385
 Machining (focused beam), 40
 Machining (nanopore), 916
 Mass spectrometer, 640
- IP (Internet protocol)
 See Internet
- IR
 See Infrared
- Irradiation, 256
- Isentropic, 334
- Ives, H. C., III
 Suppression of Electron Emission from Conductors, 329
- J**
- Jackson, M. C.
 Surety and Accountability for Storage Containers, 798
- Jacobsen, R. B.
 Interfacial Bioscience Grand Challenge, 680
 Membrane Protein Interactions in Cell Signaling, 75
- James, C. D.
 Microfluidic Cellular Sample Pretreatment, 169
- Jamison, G. M.
 Photocontrol of Nanointeractions in Microsystems, 284
 Thermally Cleavable Surfactants, 305
- Jarecki, R. L., Jr.
 Micromass Spectrometer-on-a-Chip, 185
- Jarek, R. L.
 Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
- Jenkin, C. L.
 Data Fusion and Visualization of MASINT Results, 355
- Jenkins, M. W.
 Nanomagnetic Films, 872
- Jennings, R. T.
 Miniature Fourier-Transform Ion-Mobility Spectrometer, 385
- Jennison, D. R.
 Decomposition of Contaminants Using Nanoparticles, 303
 Microminiature Thermionic Converter, 473
 Metal-/Oxide-Joining in NW Component Manufacturing, 899
- Jensen, K. A.
 Soot Formation in Unsteady Diffusion Flames, 225
- Jensen, R. P.
 Computational Modeling of Fracture in Geomaterials, 228
- Johnson, C. M.
 Enabling Technology for Human Collaboration, 718
- Johnson, D. J.
 Suppression of Electron Emission from Conductors, 329
- Johnson, D. L.
 Laser Triggering of Water Switches in Accelerators, 341
- Johnson, M. M.
 A Systems Approach to Defending Our Borders, 699
 Communication in Counterterrorism Crisis Management, 420
 Robust Message Routing for Mobile *Ad Hoc* Networks, 118
 Stochastic Programming for Enterprise Modeling, 115
- Johnson, W. A.
 Large-Aperture Sol-Gel Diffraction Grating, 338
- Johnston, A. M.
 Error-Control Codes for Engineered Regulatory Systems, 912
- Johnston, G. A.
 Intelligent Interaction Control of Microscale Components, 57

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Joint test assembly, 811
- Jokiel, B., Jr.
 Advanced Packaging Technology for Optical Firesets, 804
 Controlled Motion for a Microfluidic Drop Ejector, 46
 Novel and Robust Environmental-Sensing Devices, 809
 Predictive Accelerated Aging of Microsystems, 795
- Jones, D. A.
 Critical-Infrastructure Interdependencies, 489
 Simulation in Critical Infrastructures, 530
 Stochastic Programming for Enterprise Modeling, 115
- Jones, E. D.
 A Revolution in Lighting, 671
 Semiconductors for Optoelectronic Materials, 145
- Jones, G. D.
 PVDF as a Piezoelectric Film, 645
- Jones, J. F.
 Intelligent Interaction Control of Microscale Components, 57
 Monomolecular Carbon Nanothread Fabrication, 443
- Jones, L. A.
 Linear Magnetic Actuators, 35
 Performance of MicroTalon SDAC Systems, 454
- Jones, R. E.
 Atomistic-Continuum Simulation, 218
 Computational Modeling of Fracture in Geomaterials, 228
 High-Fidelity Frictional Models for MEMS, 222
- Jones, S.
 Completely Passive Microwave Tag, 610
 Zero-Power Radio Receiver, 608
- Jones, S. A.
 Hydrogen Futures Dynamic-Simulation Model, 535
- Jones, S. T.
 Active Network and Use of Network Processor, 607
- Jones, W. B.
 Enabling Technology for Human Collaboration, 718
- Jordan, S. E.
 Improving Human/System Interactions, 425
 Robotic Planning for Physical-Security Analysis, 627
- Jorgensen, C. R.
 Automation of Microelectronic Physical Analysis, 592
- JP-8 fuel, 925
- JTA
See Joint test assembly
- K**
- Kalb, J. L.
 Smart Decoy Sensor Network, 441
- Kaneshige, M. J.
 Advanced Weapons Signatures, 659
- Kanouff, M. P.
 Alanate-Hydride Fuel-Cell Demonstration Project, 515
 Bioaerosol Collection for Detectors, 618
- Karpetis, A. N.
 Microengine for Advanced Power Generation, 349
- Kaye, R. J.
 Reliability Data for High-Magnetic-Field Coil Design, 445
- Kearney, S. P.
 Diagnostics for Rarefied Flows in MEMS Applications, 855
 Filtered Rayleigh-Scattering Diagnostic, 203
 Soot Formation in Unsteady Diffusion Flames, 225
- Keefe, R. G.
 Natural-Gas Production Problems, 480
- Keenan, M. R.
 MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
 Quantification of Environments Within Micropackages, 309
 Robust Chemometrics for Remote Spectral Sensing, 556
- Keiter, E. R.
 Sensitivities for Large-Scale Simulation Codes, 124
- Keller, J. O.
 Hydrogen Futures Dynamic-Simulation Model, 535
- Kellogg, R. A.
 Novel and Robust Environmental-Sensing Devices, 809
- Kelly, J. J.
 Alloys for LIGA Micromachines, 287
- Kelly, M. J.
 Biomicrofuel Cell, 685
 Identification of Regulated Chemicals in Water, 491
 Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
 Photonic-Bandgap Structures for Sensor Protection, 595
- Kelton, J. M.
 Rapid-Prototyping High-Density Circuitry, 59
- Kemme, S. A.
 A Revolution in Lighting, 671
 Arrayed Resonant Subwavelength Gratings, 562
 Dispersive Photonics for Sensors and Microsystems, 155
 Tagging for Tracking and Authentication of Documents, 577
- Kemp, R. A.
 Beyond Nanoparticles, 511
 Biomicrofuel Cell, 685
 Decomposition of Contaminants Using Nanoparticles, 303
 Support-Active-Site Interactions in Catalysts, 758
- Kent, M. S.
 Adhesive Bonding in Microfabrication, 42
 Sequestration of Pathogens on Nanoengineered Surfaces, 790
- Kern, J. P.
 MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
- Khandaker, N. R.
 Anion Nanoengineered Sorbents for Water Purification, 471
- Kilman, D.
 Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Kim, B. I.
 Aging Mechanisms in Dormant MEMS Structures, 150
- Kimmer, C. J.
 Atomistic-Continuum Simulation, 218
- King, D. B.
 Microminiature Thermionic Converter, 473
- Kinney, R. D.
 Levitated Three-Axis Microaccelerometer, 38
 Microoptical Gyroscope Via Optical Integration, 191
- Kipp, M. E.
 Assessment of Bomb Damage to Underground Facilities, 396

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Kirby, B. J.
 A Microbioreactor for Hydrogen Production, 813
 Detection of Chimeric Bioweapons, 605
 Molecular Integrated Microsystems, 725
- Klarer, P. R.
 CONOPS Development for Automated Systems, 387
 Passive-Legged, Multisegmented, Robotic Vehicle, 568
- Klebanoff, L. E.
 Rarefied-Gas Dynamics and Surface Interactions, 220
- Klein, P. A.
 Atomistic-Continuum Simulation, 218
 Modeling Ductile Fracture, 207
 Tensegrity Through Material Biomimicry, 236
- Klem, J. F.
 Semiconductors for Optoelectronic Materials, 145
- Kliner, V. D. A.
 Chem-Bio Sensing in Microfluidic Systems, 662
 Identification of Chemical Plumes, 565
 Smart Detectors of Enrichment of Bioaerosols, 924
- Klody, K. A.
 Compliant Thermomechanical MEMS Actuators, 181
- Knapp-Kleinsorge, S. A.
 Validated Modeling of Distributed Energy Resources, 494
- Knorovsky, G. A.
 Packaging Technology for Microsystems, 315
- Knudson, M. D.
 Inelastic Deformation in Shocked-Sapphire Crystals, 788
- Ko, T. H.
 Modeling of Groups Perpetrating Violence, 712
 SDAC Architectural Study and Demonstration System, 705
- Kobos, P. H.
 Analysis Support for Senate Energy Committee, 537
- Koch, M. W.
 Acoustic-Seismic Target Identification, 603
 Data Fusion and Visualization of MASINT Results, 355
 Moving-Target Identification, 413
 A Systems Approach to Defending Our Borders, 699
- Koehler, D. R.
 Microfuze, 380
- Kolda, T. G.
 Parallel Nonlinear Solvers for Simulations, 134
- Koleske, D. D.
 A Revolution in Lighting, 671
 Efficiency of GaN HEMT High-Power Amplifiers, 193
- Kooser, A. S.
 Monitoring of Volatile Contaminants, 463
- Kottenstette, R.
 Improved Chemical-Agent Collection, 550
 Microsystems for Reagent Delivery, 167
 Novel Micropreconcentrators, 637
- Kotula, P. G.
 Integrated Metal Surface Micromachines, 178
 Ultrahigh-Temperature Ceramics, 625
- Kozlowski, D. M.
 Flexible Robotic Maintenance Facility, 373
 Intelligent Interaction Control of Microscale Components, 57
- Kraus, G. M.
 Agile, Microsystems-Enabled Receiver, 600
- Kravitz, S. H.
 Autonomous Microexplosive Subsurface Tracing, 475
 Biomicrofuel Cell, 685
 Levitated Three-Axis Microaccelerometer, 38
 Microfuze, 380
 Photonic-Bandgap Structures for Sensor Protection, 595
- Krumhansl, J. L.
 Anion Nanoengineered Sorbents for Water Purification, 471
 Water Desalination, 496
- Kruppa, G. H.
 High-Throughput Identification of Molecular Machines, 96
 Interfacial Bioscience Grand Challenge, 680
 Membrane Protein Interactions in Cell Signaling, 75
- Kuehl, M. A.
 Advanced Mobile Networking Using Graph Theory, 416
- Kulp, T. J.
 Identification of Chemical Plumes, 565
- Kunsman, D. M.
 Advanced Coolants for Next-Generation Reactor, 923
- Kuntz, D. W.
 Prompt Global Response, 696
- Kurtz, S. R.
 A Revolution in Lighting, 671
 Efficiency of GaN HEMT High-Power Amplifiers, 193
 Quantum Coherence in Semiconductor Nanostructures, 187
 Semiconductors for Optoelectronic Materials, 145
- Kyker, R. D.
 Adaptive Awareness for Personal Decision Making, 394
 SDAC Architectural Study and Demonstration System, 705
- L**
- Ladd, M. D.
 Algorithm Architecture for Unattended Ground Sensors, 428
 Assessment of Bomb Damage to Underground Facilities, 396
 Data Fusion and Visualization of MASINT Results, 355
 Performance of MicroTalon SDAC Systems, 454
 TALON, 690
- Lambert, S. J.
 Anomalous Weapon Surveillance Waveforms, 710
- Lane, P.
 Interfacial Bioscience Grand Challenge, 680
- Lane, T. W.
 Detecting Genetic Engineering in Bioweapons Strains, 621
 Harnessing Methane-Hydrate Bacteria Interactions, 722
 Interfacial Bioscience Grand Challenge, 680
- Lanes, K. R.
 Radiation-Hardened Optoelectronic Components, 635
- Lapizco-Encinas, B. H.
 Sensor for Live Waterborne Pathogens, 793
- Lappin, A. R.
 Geologic Characterization of Difficult Targets, 584
- Larsen, L. E.
 Nonlethal Technologies for the War on Terrorism, 702

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Larson, K. W.
 Anomalous Weapon Surveillance Waveforms, 710
 Augmented Cognition, 687
 New Seismic-Event-Detection Technology, 897
- Larson, R. S.
 Alanate-Hydride Fuel-Cell Demonstration Project, 515
 Vapor-Liquid Phase of Iodine-Sulfur Water Splitting, 517
- Laser
 Metal vaporization, 256
 Microfabrication, 44
 Petawatt, 336
 Semiconductor nanostructures, 187
 Water switches, 341
- Lattice
 Photonic, 571
See also: Superlattice
- Lawrence, R. J.
 Hypervelocity Impact-Generated Flash, 422
- Lawton, C. R.
 Critical-Infrastructure Interdependencies, 489
 Simulation in Critical Infrastructures, 530
- Layer
 Atmospheric, 859
 Tribological coatings, 51
See also: Bilayer
See also: Multilayer
See also: Nanolayer
- Leaky, 195
- Lean, J. T.
 Decontamination of Toxic Industrial Chemicals, 389
- Lee, M.
 Modeling of Groups Perpetrating Violence, 712
- Leininger, M. L.
 Scalable Fault-Tolerant Algorithms, 120
 Soft-Matter Nanolayer Superlattices, 282
- Lemke, P.
 Novel and Robust Environmental-Sensing Devices, 809
- Leung, K.
 A Revolution in Lighting, 671
 The Basics of Aqueous Nanofluidics, 278
- Leung, V. J.
 Commodity-Based Parallel Computing Systems, 107
- Level set, 212
- Levitte, 38
- Lewis, C. L.
 Advanced Mobile Networking Using Graph Theory, 416
 Buzzard, 629
- Lewis, P. R.
 Micro Flame-Based Detector Suite, 437
 Novel Micropreconcentrators, 637
 Sensors for Water-Contamination Events, 519
- Lidar, 565
- LIGA (lithography, electroforming, and molding)
See Lithography
- Light
 Nanovehicles, 823
 Solid-state, 671
- Lilly, M. P.
 Engineered Superconductivity in Electron-Hole Bilayers, 157
- Lin, S. Y.
 Active Photonic-Crystal Devices, 172
 Active Photonic Nanostructures, 321
 Dispersive Photonics for Sensors and Microsystems, 155
 Integration of Advanced Photonics and MEMS, 148
 Photocontrol of Nanointeractions in Microsystems, 284
 Photonic-Lattice Structures for Remote Sensing, 571
- Lindblom, S. C.
 Surety and Accountability for Storage Containers, 798
- Lindner, D. L.
 Lipid Microarray Biosensor for Biotxin Detection, 885
 Microscale Separations of Biological Compounds, 880
- Linear
 Magnetic actuators, 35
 Programming, 139
 Scaling, 120
See also: Nonlinear
- Link, H. E.
 Securing Mobile Code, 524
- Linker, K. L.
 Micromass Spectrometer-on-a-Chip, 185
- Lipid
 Membranes, 778
 Microarray, 885
- Lipkin, J.
 A Systems Approach to Defending Our Borders, 699
- Lippitt, C. E.
 CONOPS Development for Automated Systems, 387
 Improving Human/System Interactions, 425
 Simulator Agents with Humanlike Episodic Memory, 359
- Liquid
 Phase transitions, 343
 Water-splitting, 517
- Lithography
 Extreme ultraviolet, 220
 Micromachines, 287
 Microsystems aging, 268
 Transmitter filter, 807
- Little, C. Q.
 A Systems Approach to Defending Our Borders, 699
 Detecting and Tracking the Active Insider, 587
- Litts, T. K.
 Rapid-Prototyping High-Density Circuitry, 59
- Liu, J.
 Assembly of Electrooptical and Bioactive Materials, 312
 Assembly of Nanomaterials Using Active Biomolecules, 300
 Molecular Integrated Microsystems, 725
 Solution-Based Nanoengineering of Materials, 296
- Liu, S.
 Microengine for Advanced Power Generation, 349
- Locator, 664
- Lockner, T. R.
 Electron- and Proton-Beam Directed-Energy Weapons, 863
- Lockwood, G. J.
 Computed Tomography X-Ray Screening, 655

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Loehman, R. E.
 Prompt Global Response, 696
 Ultrahigh-Temperature Ceramics, 625
- Loffredo, D.
 Creative Networking of Commercial Products, 666
- Logic
 All-optical, 901
 Photonic circuits, 195
- Long, K. R.
 Microfabricated Dielectrophoretic Sample Preparation, 589
- Long, T. M.
 Photocatalysis of Nanointeractions in Microsystems, 284
- Lopez, A.
 Controlled Motion for a Microfluidic Drop Ejector, 46
 Magnetically and Electrostatically Actuated Micropumps, 910
- Lorenz, J. C.
 Natural-Gas Production Problems, 480
- Loucks, C. S.
 Flexible Robotic Maintenance Facility, 373
- Lovelady, Z. L.
 Networked Device Demonstration, 667
- Lowder, K. S.
 Prognostic Health Monitoring and Maintenance, 368
- Luk, T. S.
 Microfabrication with Femtosecond-Laser Processing, 44
 Remote Mapping of Electromagnetic Fields, 399
- Luker, S. M.
 Gas Power-Conversion Systems for Nuclear Reactors, 522
- Lundstrom, J. M.
 EM Interactions with Systems to Enhance Security, 392
- Luntz, D. W.
 Ultrahigh-Temperature Ceramics, 625
- Luong, A. K.
 Cellular Observatory, 89
- Lutz, A. E.
 Hydrogen Futures Dynamic-Simulation Model, 535
 Vapor-Liquid Phase of Iodine-Sulfur Water-Splitting, 517
 Vulnerability Assessment of National Power Grid, 477
- Lutz, T. J.
 High-Efficiency Turbine Blade Coatings, 483
- Lyo, S. K.
 Quantum Coherence in Semiconductor Nanostructures, 187
- M**
- Macha, J. M.
 Prompt Global Response, 696
- Machine
 Conscious, 734
 Ion beam, 40
 Molecular, 96
 Single ion, 916
 See also: Micromachine
- Macke, B. T.
 Deployable Large-Aperture Optics System, 559
- Maclin, R. F.
 Analysis of Multichannel Internet Messaging, 669
- Magnetic
 Actuator, 35
 Coilgun, 445
 Micropump, 910
 Nanoparticle, 838
 Plasma, 242
 See also: Electromagnetic
 See also: Micromagnetic
 See also: Nanomagnetic
- Magnetostrictive, 319
- Maharrey, S. P.
 Interfacial Bioscience Grand Challenge, 680
 Nanoscale Energetic Materials, 744
- Maintenance
 Facility, 373
 Health, 368
- Maish, A. B.
 Adaptive and Mobile Ground Sensors, 365
- Majzoub, E. H.
 Catalyzation of Complex-Hydride Reactions, 307
- Malczynski, L. A.
 Analysis Support for Senate Energy Committee, 537
 Hydrogen Futures Dynamic-Simulation Model, 535
- Malins, R. J.
 Adaptive Awareness for Personal Decision Making, 394
- Malone, K. T.
 Acoustic-Seismic Target Identification, 603
 TALON, 690
- Manginell, M. M.
 Microfluidic Cellular Sample Pretreatment, 169
 Tagging for Tracking and Authentication of Documents, 577
- Manginell, R. P.
 Assembly of Nanomaterials Using Active Biomolecules, 300
 Micro Flame-Based Detector Suite, 437
 Microsystems for Reagent Delivery, 167
 Novel Micropreconcentrators, 637
 Sensors for Water-Contamination Events, 519
- Mani, S. S.
 Controlled Motion for a Microfluidic Drop Ejector, 46
 MEMS in μ Fluid Channels, 152
 Microfluidic Cellular Sample Pretreatment, 169
 MOSFET-MEMS Integration, 189
 Polychromator Systems for Remote Chemical Sensing, 197
 Ultralightweight Telescope with MEMS Adaptive Optic, 631
- Manipulation, 383
- Mann, G. A.
 Reliability Data for High-Magnetic-Field Coil Design, 445
- Manufacturing
 Automotive processes, 760
 Bioprocesses, 66
 Mesoscale, 861
 Nuclear weapon, 899
 Rapid prototyping, 887
 Thermomechanical, 853
- Mapping
 Electromagnetic fields, 399
 Protein interactions, 75

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Mar, A.
 Compact Terahertz Sources, 418
 X-Ray Sources for Advanced Imaging Applications, 378
 Solid-State Switch for Advanced Pulsed Power, 332
- Marshall, L. H.
 Algorithm Development for Smart Antennas, 842
 Smart Decoy Sensor Network, 441
- Martin, J. E.
 Magnetostrictive Elastomers for Actuators and Sensors, 319
- Martin, J. W.
 Deployable Large-Aperture Optics System, 559
 PVDF as a Piezoelectric Film, 645
- Martin, S. B.
 Immune Responses to Bioterrorism Threats, 93
 Informatics for Systems Biology, 78
- Martinez, M. J.
 Contaminant Transport in Architectural Spaces, 614
- Martinez, R. J.
 Security Coatings for Multichip Modules, 612
- Martinez-Canales, M. L.
 Stochastic Programming for Enterprise Modeling, 115
- Martino, A.
 Immune Responses to Bioterrorism Threats, 93
- Marx, K. D.
 Smart Sensors for Joint Test Assembly Flights, 102
- MASINT
 See Measurement and signal intelligence
- Mason, J.
 Determination of Microstructural Properties, 334
- Mason, J. J.
 Detection of Spread-Spectrum Waveforms, 552
 Ultracompact, Ultralow-Power Communications, 575
- Mathematical
 Deception, 739
 Infrastructure interdependencies, 489
 Multiphysics couplings, 775
- Mattsson, T. K.
 Electrical Conductivity of Metal Alloys, 865
- Matzke, C. M.
 Assembly of Nanomaterials Using Active Biomolecules, 300
 Icosahedral Boride Semiconductor Beta Cell, 580
 MEMS in μ Fluid Channels, 152
- May, E. E.
 A Parallel Circuit Simulator for Cell Biology, 129
 Error-Control Codes for Engineered Regulatory Systems, 912
 Immune Responses to Bioterrorism Threats, 93
- Mayer, T. K.
 Linear Magnetic Actuators, 35
- Mayer, T. M.
 Aging Mechanisms in Dormant MEMS Structures, 150
 Atomic-Layer Deposition of Tribological Coatings, 51
 Microfabrication Processes, 40
 Predictive Accelerated Aging of Microsystems, 795
 Varying Humidity on Copper-Sulfide Film Formation, 293
- Mazarakis, M. G.
 Electron- and Proton-Beam Directed-Energy Weapons, 863
- McBrayer, J. D.
 Radiation-Hard Nonvolatile Memories, 174
- McCarty, K. F.
 Decomposition of Contaminants Using Nanoparticles, 303
 Dynamics of Metal/Ceramic Interfaces, 262
- McClellan, Y.
 Nuclear Process Transparency and Control, 509
- McCormick, F. B.
 Microoptical Gyroscope Via Optical Integration, 191
- McDonald, J. M.
 High-Efficiency Turbine Blade Coatings, 483
- McDonald, M. J.
 A Systems Approach to Defending Our Borders, 699
 Automated Visual Direction of Mobile Manipulation, 383
 Improving Human/System Interactions, 425
 Sophisticated Agent Evolution and Optimization, 113
 TALON, 690
- McElhanon, J. R.
 Soft-Matter Nanolayer Superlattices, 282
 Surety and Accountability for Storage Containers, 798
 Thermally Cleavable Surfactants, 305
- McEntire, R. S.
 Hard Target Defeat High-G-Tolerant Fuze, 407
- McFadden, S. X.
 Modeling Ductile Fracture, 207
- McFarland, R.
 Radiation-Hard Nonvolatile Memories, 174
- McGrath, L. K.
 Monitoring of Volatile Contaminants, 463
- McGuire, K.
 Miniaturization of SAR Electronic Assembly, 411
- McIlroy, A.
 Chem-Bio Sensing in Microfluidic Systems, 662
- McKenna, S. A.
 Algorithms for Simulations of Chemical Attacks, 136
 Anomalous Weapon Surveillance Waveforms, 710
- McNicholas, E. M.
 Improved Performance in Cryptographic Protocols, 361
- McWherter-Payne, M. A.
 Prompt Global Response, 696
- MDL (microelectronics development laboratory)
 See Microelectronic
- Measurement and signal intelligence, 355
- Mechanical
 Environments, 801
 Testers, 178
 See also: Electromechanical
 See also: Nanoelectromechanical
 See also: Thermomechanical
- Mechanics
 Geomaterials, 228
 Microelectromechanical, 258
 Structural, 105
- Medforth, C. J.
 Biomimetic Chloroplasts, 83
 Light-Powered Nanovehicles, 832

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Medlin, D. L.
First-Principles Determination of Dislocation Properties, 252
- Meeks, K. D.
Near-Real-Time Characterization for HDBT Defeat, 693
- Melgaard, D. K.
Multivariate Spectral Calibration Algorithms, 274
- Membrane
Coatings, 729
Compliant, 784
Lipid, 778
Pores, 71
Protein interactions, 75
Signaling (biosensors), 86
Signaling (molecular machines), 96
See also: Biomembrane
- Memory
Episodic, 359
Nonvolatile, 174
- MEMS
See Microelectromechanical systems
- Mendenhall, F. T.
Tagging for Tracking and Authentication of Documents, 577
TALON, 690
- Merchant, B. J.
Anomalous Weapon Surveillance Waveforms, 710
New Seismic-Event-Detection Technology, 897
- Mercier, J. A.
MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
- Mesoscale, 35
- Message
Mobile networks, 118
Multichannel internet, 669
- Metadata, 894
- Metal
MEMS coatings, 877
Metal/oxide joining, 899
- Methane, 722
- Metrology, 57
- Micellar, 744
- Michael, J. R.
Icosahedral Boride Semiconductor Beta Cell, 580
Mechanics and Tribology of MEMS Materials, 258
Packaging Technology for Microsystems, 315
- Michalski, J. T.
Information Assurance for Wireless *Ad Hoc* Networks, 401
Secure MPLS Control Plane for Internet Connectivity, 597
- Michelsen, H. A.
Diagnostics for Airborne Carbon Nanoparticles, 468
- Microaccelerometer, 38
- Microarray
Lipid, 885
Microfluidic, 605
- Microbial, 821
- Microbioreactor, 813
- Microchip, 834
- Microdevice, 83
- Micro-EDM, 768
- Microelectroanalytical, 265
- Microelectromechanical systems (MEMS)
Actuators, 181
Advanced photonics, 145
Adaptive optic, 631
Aging, 150
Electrostatically actuated, 849
Energy harvester, 750
Frictional models, 222
Gas dynamics, 220
Interface reliability, 753
Materials, 258
Metallic coatings, 877
Microfluid channels, 152
Microphones, 784
Molecular simulation, 729
MOSFET, 189
Noncontinuum gas flows, 234
Packaging, 888
Rarefied flows, 855
Radio frequency, 160
See also: Bio-MEMS
- Microelectronic
Laboratory, 174
Physical analysis, 592
Radiation aging, 210
- Microengine, 349
- Microexplosive, 475
- Microfabricate
Acoustic-spectrum analyzer, 547
Adhesive bonding, 42
Femtosecond laser, 44
Machining, 40
Sample preparation, 589
- Microfluid, 46
- Microfuze, 380
- Micromachine
Failure, 100
Friction, 883
Lithography, 287
- Micromagnetic, 122
- Micromilling, 64
- Microminiature, 473
- Microoptical, 191
- Micropackage, 309
- Microphone, 784
- Micropreconcentrator, 637
- Micropump, 910
- Microscale
Gas dynamics, 220
Separations, 880
- Microscopy
Cellular observatory, 89
Ge/Si, 851
- Microsensor
Nanoporous adsorbers, 906
Radioactive waste, 502

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Microseparation, 618
- Microstructure
 - Isentropic compression, 334
 - Sintering, 243
- Microsystem
 - Accelerated aging, 795
 - Assembly, 54
 - Chemical signature, 167
 - Dispersive photonics, 155
 - Hermetic packaging, 888
 - Lithography, 268
 - Molecular integrated, 725
 - Nanointeractions, 284
 - Packaging/joining, 315
 - Receiver, 600
- MicroTalon, 454
- Microwave, 610
- Mikkalson, J. E.
 - Microfabrication Processes, 40
- Miller, D. P.
 - Improving Human/System Interactions, 425
 - Terrorist-Activity Plan-Assessment Methodology, 714
- Miller, J. E.
 - Beyond Nanoparticles, 511
 - Diesel Catalytic Particulate Traps, 499
 - Micro Flame-Based Detector Suite, 437
 - Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
 - Water Desalination, 496
- Miller, L. M.
 - Improved Performance in Cryptographic Protocols, 361
- Miller, P. A.
 - Magnetic-Field Effects on Vacuum-Arc Plasmas, 242
- MIMS (molecular integrated microsystems)
 - See* Molecular
- Miniature
 - Ion-mobility spectrometer, 385
 - Radio-frequency, 861
 - Synthetic-aperture radar, 411
 - Thermionic converter, 473
 - Transmitter filter, 807
- Mirror, 645
- Missert, N. A.
 - A Revolution in Lighting, 671
 - Efficiency of GaN HEMT High-Power Amplifiers, 193
 - Varying Humidity on Copper-Sulfide Film Formation, 293
- Mitchell, C. C.
 - A Revolution in Lighting, 671
- Mitchell, M. A.
 - Improved Chemical-Agent Collection, 550
- Mitchiner, J. L.
 - Anomalous Weapon Surveillance Waveforms, 710
- Mitigation
 - Microsystems aging, 268
 - Toxic chemicals, 389
- Mixing, 847
- Mobile
 - Graph theory, 416
 - Ground sensor, 365
 - Manipulation, 383
 - Network, 118
 - Robot, 921
 - Securing code, 524
- Model
 - Biomembranes, 91
 - Carbonate phases, 765
 - Distributed energy, 494
 - Ductile fracture, 207
 - Enterprise, 115
 - Frictional, 222
 - Geomaterials, 228
 - Group violence, 712
 - Human effectiveness, 871
 - Hydrogen futures, 535
 - Infrastructure interdependency, 460
 - Interface growth, 825
 - Local chemistry, 291
 - Microbial cell, 821
 - Natural-gas production, 480
 - Nanotube composites, 875
 - Optimization scheme, 131
 - Rio Grande, 721
 - Rock penetration, 747
 - Nuclear weapons, 633
 - Sintering, 243
 - System-of-systems, 432
 - Terrorist, 716
 - Thermal, 215
 - Thermofluid systems, 200
 - Turbulent flow, 892
 - Water demand, 741
 - See also*: Simulation
- Modine, N. A.
 - Modeling Local Chemistry, 291
 - Quantum Coherence in Semiconductor Nanostructures, 187
 - Quantum Computing Accelerator I/O, 836
 - Semiconductors for Optoelectronic Materials, 145
- Module, 612
- Moffat, H. K.
 - A Revolution in Lighting, 671
- Molecular
 - Biomimetic air sampling, 823
 - Carbonate phases, 765
 - Electronics, 908
 - Integrated microsystem, 725
 - Machines, 96
 - Membrane pores, 71
 - Microelectromechanical, 729
 - Optical trapping, 541
 - See also*: Biomolecule

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Molina, L. L.
 New Mechanism for Upset of Electronics, 371
 Secure Chaotic Communications, 430
- Monitor
 Dynamic environments, 904
 Health, 368
 Security, 573
 Stockpile, 811
 Streams, 486
 Volatile contaminants, 463
- Monomolecular, 443
- Moody, N. R.
 Atomic-Layer Deposition of Tribological Coatings, 51
 Verification Techniques for Nonlinear Deformation, 736
- Moore, J. T.
 Beyond Nanoparticles, 511
- Moore, R. C.
 Arsenic Removal from Water, 533
- Moorman, M. W.
 Micro Flame-Based Detector Suite, 437
 Novel Micropreconcentrators, 637
- Morales, A. M.
 Microengine for Advanced Power Generation, 349
 Miniature Transmitter Filter for JTA, 807
 Neutron Monitors for JTA and Stockpile Monitoring, 811
 Soft-Matter Nanolayer Superlattices, 282
- Moran, M. P.
 A Revolution in Lighting, 671
- Morphology
 GaAs, 890
 Interface, 825
- Morrow, C. W.
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
 Z-Pinch Power-Plant System Development, 324
- Morrow, J. D.
 Fundamentals of Mobile-Robot Development, 921
- Morse, D. H.
 Advanced Digital Detectors for Neutron Imaging, 546
- MOSFET, 189
- Motion, 46
- Mowery, D. M.
 PVDF as a Piezoelectric Film, 645
- Moy, T. D.
 Modeling of Groups Perpetrating Violence, 712
- Moya, M. M.
 Geologic Characterization of Difficult Targets, 584
 Robust Chemometrics for Remote Spectral Sensing, 556
- Moylan, S. P.
 High-Speed Micro-EDM, 768
- MPLS
See Multiple protocol label switching
- MSI
See Multispectral imagery
- Muguira, M. R.
 Obstacle Detection for Autonomous Navigation, 376
- Multichannel, 669
- Multichip, 612
- Multilayer, 54
- Multiple protocol label switching (MPLS), 597
- Multispectral imagery, 649
- Murata, K. K.
 Advanced Nuclear Engineering Analysis Technology, 506
- Muron, D. J.
 Identification of Regulated Chemicals in Water, 491
- Murphy, M. B.
 TALON, 690
- Murphy, T. A.
 Enabling Technology for Human Collaboration, 718
- Murphy-Dye, B. D.
 Critical-Infrastructure Interdependencies, 489
- N**
- Nachtigal, N. M.
 SDAC Architectural Study and Demonstration System, 705
- Nagasubramanian, G.
 Icosahedral Boride Semiconductor Beta Cell, 580
- Najm, H. N.
 Uncertainty Propagation in Thermo-fluid Systems, 200
- Namperumal, S. K.
 Surety and Accountability for Storage Containers, 798
- Nanoelectrode, 491
- Nanoelectromechanical, 162
- Nanoengineer
 Materials, 296
 Sorbents, 471
 Surfaces, 790
- Nanofluid, 278
- Nanointeraction, 284
- Nanolayer, 282
- Nanomagnetic, 872
- Nanomaterial, 300
- Nanoparticle
 Airborne carbon, 468
 Beyond, 511
 Functionalized, 176
 Magnetic properties, 838
 Photochemically active, 303
- Nanopore
 Adsorbers, 906
 Machining, 916
- Nanoporous, 906
- Nanoscale
 Energetic materials, 744
 Films, 232
 Growth, 263
 Hotspots, 770
 Thermomechanical manufacturing, 853

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Nanostructure
 Active photonic, 321
 Electrodes, 834
 Excitation energy, 289
 Lithography, 287
 Polyoxometalate arrays, 827
 Self-assembled, 466
 Semiconductor, 187
 Silicon, 778
 Nanothread, 443
 Nanotube, 875
 Nanovehicle, 832
 Napolitano, L. M.
 Molecular Integrated Microsystems, 725
 Nasby, R. D.
 Radiation-Hard Nonvolatile Memories, 174
 Natural gas, 480
 Navigation, 376
 Neely, J. C.
 Automated Video Screening for Unattended Monitoring, 904
 Buzzard, 629
 Obstacle Detection for Autonomous Navigation, 376
 Neiser, R. A., Jr.
 Security Coatings for Multichip Modules, 612
 Nelson, C. L.
 Content-Based Video and Image Indexing System, 616
 Detecting and Tracking the Active Insider, 587
 Weapon-Platform Controls for Intelligent Targeting, 657
 Nelson, T. R.
 X-Ray Sources for Advanced Imaging Applications, 378
 NEMOs (nanoelectromechanical oscillators)
 See Nanoelectromechanical
 Nenoff, T. M.
 Energy-Efficient Feedstock Hydrocarbon Separations, 457
 Water Desalination, 496
 Network
 Active, 607
 Biological, 93
 Commercial products, 666
 Countermeasures, 346
 Device demonstration, 667
 Graph theory, 416
 Information assurance, 401
 Message routing, 118
 Sensor, 441
 Surety enhancement, 504
 Neumann, W. D.
 Hybrid Infrastructure Cryptography, 404
 Securing Mobile Code, 524
 Neutron
 Imaging, 546
 Monitors, 811
 Newman, G. A.
 Geophysical Subsurface Imaging, 857
 Newman, G. C.
 System-Dynamics Modeling of Water Resources, 721
 Nguyen, H. D.
 Algorithm Architecture for Unattended Ground Sensors, 428
 Nielsen, I. B.
 Scalable Fault-Tolerant Algorithms, 120
 Nilson, R. H.
 Ultraclean Environments in Microsystem Packages, 246
 Noble, D. R.
 Large-Deformation Solid-Fluid Interaction, 212
 Nogan, J.
 Autonomous Microexplosive Subsurface Tracing, 475
 Noncontinuum, 234
 Nondeterministic, 115
 Nonequilibrium, 770
 Noninformative, 894
 Nonlethal, 702
 Nonlinear, 736
 Nonradioactive, 922
 Nonvolatile, 174
 Nordquist, C. D.
 Agile, Microsystems-Enabled Receiver, 600
 Miniature High-Power RF Components, 861
 Silicon-Based RF MEMS Components, 160
 Norman, A. K.
 Direct Single-Ion Machining of Nanopores, 916
 Norman, K.
 An Integrated, Stacked System-on-a-Chip, 183
 Miniaturization of SAR Electronic Assembly, 411
 Nove, C. E.
 Analysis of Multichannel Internet Messaging, 669
 Novick, D. K.
 Obstacle Detection for Autonomous Navigation, 376
 Nozick, L. K.
 Simulation in Critical Infrastructures, 530
 Nuclear
 Engineering analysis, 506
 Power-conversion, 522
 Safety, 801
 Terrorist model, 716
 Transparency, 509
 Waste management, 466
 Weapons, 633
 Nucleation, 851
 Numan, M. D.
 Nanostructured Polyoxometalate Arrays, 827
 Nygren, R. E.
 High-Efficiency Turbine Blade Coatings, 483
 Nyman, M. D.
 Sequestration of Pathogens on Nanoengineered Surfaces, 790
O
 Ober, C. C.
 Sensitivities for Large-Scale Simulation Codes, 124
 Observatory, 89
 Obstacle, 376
 O'Connor, J. W.
 Surety and Accountability for Storage Containers, 798

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Ohlhausen, J. A.
 Mechanics and Tribology of MEMS Materials, 258
 Predictive Accelerated Aging of Microsystems, 795
- Okandan, M.
 Biomicrofuel Cell, 685
 Controlled Motion for a Microfluidic Drop Ejector, 46
 MEMS in μ Fluid Channels, 152
 Microfluidic Cellular Sample Pretreatment, 169
 MOSFET–MEMS Integration, 189
- Oliver, A. D.
 Hermetic Packaging for MEMS Integrated Microsystems, 888
- Oliver, M. S.
 Advanced Weapons Signatures, 659
- Olson, C. L.
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
- Olson, L. D.
 Critical-Infrastructure Interdependencies, 489
- Olsson, W. A.
 Modeling of Rock Penetration, 747
 Natural-Gas Production Problems, 480
- O'Malley, M. W.
 Compact Terahertz Sources, 418
 Sensing of Phase Transformations in Steels, 48
 Solid-State Switch for Advanced Pulsed Power, 332
- O'Malley, P. D.
 Hard Target Defeat High-G-Tolerant Fuze, 407
- Omdahl, G.
 Completely Passive Microwave Tag, 610
 Zero-Power Radio Receiver, 608
- One-dimensional, 892
- Oppel, F. J., III
 Information Assurance for Wireless *Ad Hoc* Networks, 401
 Performance of MicroTalon SDAC Systems, 454
 TALON, 690
- Optical
 Deployable, 559
 Firesets, 804
 Limiters, 595
 Microelectromechanical telescope, 631
 Photonic encryption, 901
 Trapping, 541
See also: Electrooptic
See also: Microoptical
- Optoelectronic
 Radiation hardened, 635
 Semiconductors, 145
- Ormesher, R. C.
 Detection of Spread-Spectrum Waveforms, 552
 Ultracompact, Ultralow-Power Communications, 575
- Ornithopter, 830
- Osborn, G. C.
 Building Conscious Machines, 734
 Self-Organizing Software Research and Development, 816
- Oscillator, 162
- Oswald, M. T.
 Algorithm Development for Smart Antennas, 842
- Ottesen, C. W.
 An Integrated, Stacked System-on-a-Chip, 183
- Ozolins, V.
 Catalyzation of Complex-Hydride Reactions, 307
- P**
- P3 engine, 773
- Paananen, O. H.
 Analysis Support for Senate Energy Committee, 537
- Pacheco, J. E.
 Nonlethal Technologies for the War on Terrorism, 702
- Package
 Firesets, 804
 Microelectromechanical, 888
 Microsystems, 315
 Ultraclean, 246
See also: Micropackage
- Padilla, D. D.
 Automated Video Screening for Unattended Monitoring, 904
 Obstacle Detection for Autonomous Navigation, 376
- Palmer, J. A.
 Rapid-Prototyping High-Density Circuitry, 59
- Pancerella, C. M.
 Adaptive Awareness for Personal Decision Making, 394
 Smart Sensors for Joint Test Assembly Flights, 102
- Parallel
 Circuit, 129
 Computing (commodity-based), 107
 Computing (failure analysis), 100
 Computing (repartitioning), 110
 Linear programming, 139
 Nonlinear solvers, 134
 Protein structure, 73
- Parekh, O. D.
 Commodity-Based Parallel Computing Systems, 107
 Massively Parallel Linear Programming, 139
- Parker, E. P.
 Adaptive Awareness for Personal Decision Making, 394
 Performance of MicroTalon SDAC Systems, 454
 Smart Sensors for Joint Test Assembly Flights, 102
 TALON, 690
- Parmeter, J. E.
 Ion-Mobility Spectrometer/Mass Spectrometer, 640
- Particle
 Beams, 918
 Nanoscale films, 232
See also: Nanoparticle
- Particulate
 Diffusion flames, 925
 Traps, 499
- Passell, H. D.
 Modeling Water Demand, 741
 System-Dynamics Modeling of Water Resources, 721
- Passive
 Microwave tag, 610
 Optical integration, 191
 Robotic vehicle, 568

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Patching, 844
 Pathak, S.
 Highly Specific Electronic Signal Transduction, 819
 Pathogen
 Sequestration, 790
 Waterborne, 793
 Patrick, E. L.
 Tagging for Tracking and Authentication of Documents, 577
 Membrane Signaling in Affinity-Based Biosensors, 86
 Pawlowski, R. P.
 A Revolution in Lighting, 671
 Parallel Nonlinear Solvers for Simulations, 134
 Peake, G. M.
 A Revolution in Lighting, 671
 Leaky-Mode VCSELs for Photonic Logic Circuits, 195
 Microoptical Gyroscope Via Optical Integration, 191
 Radiation-Hardened Optoelectronic Components, 635
 Semiconductors for Optoelectronic Materials, 145
 Peebles, D. E.
 Quantification of Environments Within Micropackages, 309
 Penetrating, 633
 Penetration
 Earth, 633
 Porous media, 762
 Rock, 747
 Permeable, 533
 Petawatt, 336
 Peter, F. J.
 Advanced Packaging Technology for Optical Firesets, 804
 Levitated Three-Axis Microaccelerometer, 38
 Predictive Accelerated Aging of Microsystems, 795
 Peters, D. W.
 Arrayed Resonant Subwavelength Gratings, 562
 Dispersive Photonics for Sensors and Microsystems, 155
 Photonic-Lattice Structures for Remote Sensing, 571
 Tagging for Tracking and Authentication of Documents, 577
 Peters, R. R.
 Robotic Planning for Physical-Security Analysis, 627
 Peterson, D. W.
 Advanced Packaging Technology for Optical Firesets, 804
 An Integrated, Stacked System-on-a-Chip, 183
 Biomicrofuel Cell, 685
 Peterson, G. D.
 An Integrated, Stacked System-on-a-Chip, 183
 Miniaturization of SAR Electronic Assembly, 411
 Peterson, K. A.
 Assembly of Microsystems Using Thin Films, 54
 Pfeifer, K. B.
 Electromechanical Acoustic-Energy Harvester, 750
 Identification of Regulated Chemicals in Water, 491
 Miniature Fourier-Transform Ion-Mobility Spectrometer, 385
 MOSFET-MEMS Integration, 189
 Polychromator Systems for Remote Chemical Sensing, 197
 Phase
 Carbonate, 765
 Steel, 48
 Transitions, 343
 Water-splitting, 517
 See also: Interphase
 Phillips, C. A.
 Algorithms for Simulations of Chemical Attacks, 136
 Commodity-Based Parallel Computing Systems, 107
 Massively Parallel Linear Programming, 139
 Simulation in Critical Infrastructures, 530
 Phillips, L. R.
 Agent-Based Control of Infrastructure Resources, 539
 Information Flow Associated with International Borders, 708
 Phillips, M. C.
 Quantum Coherence in Semiconductor Nanostructures, 187
 Phillips, M. L.
 Tagging for Tracking and Authentication of Documents, 577
 Photochemical, 303
 Photocontrol, 284
 Photocurrent, 834
 Photolithographic, 254
 Photonic
 Active crystal, 172
 Bandgap, 595
 Dispersive, 155
 Encryption, 901
 Infrared lidar, 565
 Lattice, 571
 Logic circuits, 195
 Microelectromechanical, 148
 Nanostructures, 321
 Pickard, P. S.
 Hydrogen Futures Dynamic-Simulation Model, 535
 Gas Power-Conversion Systems for Nuclear Reactors, 522
 Pickett, M.
 Modeling of Groups Perpetrating Violence, 712
 Piech, M.
 Photocontrol of Nanointeractions in Microsystems, 284
 Piekos, E. S.
 Multiscale Thermal Modeling, 215
 Hotspots Due to Nonequilibrium Thermal Transport, 770
 Pierson, L. G.
 Cryptographic Assurance of Execution Correctness, 642
 Secure MPLS Control Plane for Internet Connectivity, 597
 Securing Mobile Code, 524
 Piezoelectric, 645
 Pilcher, M. W.
 Hard Target Defeat High-G-Tolerant Fuze, 407
 Pitts, T. A.
 Photonic-Bandgap Structures for Sensor Protection, 595
 Pizarro, S. A.
 Molecular Integrated Microsystems, 725

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Plasmas
 Vacuum-arc, 242
 Z-pinch, 336
 Plass, R. A.
 Compliant Thermomechanical MEMS Actuators, 181
 Predicting and Validating MEMS Interface Reliability, 753
 Predictive Accelerated Aging of Microsystems, 795
 Quantification of Environments Within Micropackages, 309
 Plastic, 918
 Plimpton, S. J.
 Computational Model of a Microbial Cell, 821
 Modeling Biomembranes, 91
 Protein Structure Generation, 73
 Plume, 565
 Plut, T. A.
 Agile, Microsystems-Enabled Receiver, 600
 Podsednik, J. W.
 Determination of Microstructural Properties, 334
 Pohl, K. R.
 Controlled Motion for a Microfluidic Drop Ejector, 46
 Magnetically and Electrostatically Actuated Micropumps, 910
 Pohl, P. I.
 Microsensors in Radioactive-Waste Management, 502
 Self-Assembled Materials in Waste Management, 466
 Polosky, M. A.
 Novel and Robust Environmental-Sensing Devices, 809
 Polychromator, 197
 Polymer
 Microscale separations, 880
 Self-assembly, 732
 Spin-coating, 254
 Polyoxometalate, 827
 Polyvinylidene fluoride, 645
 Poole, R. L.
 Bioprocesses for Advanced Manufacturing Applications, 66
 Pore
 Single-channel, 71
 See also: Nanopore
 Porous
 Fluid-structural, 762
 See also: Nanoporous
 Poteet, H. M.
 Buzzard, 629
 Power
 Beta cell, 580
 Biomimetic chloroplasts, 83
 Grid, 477
 Microchip, 834
 Microengine, 349
 Nanovehicles, 832
 Nuclear reactors, 522
 Pulse (accelerators), 341
 Pulse (switches), 332
 Radio receiver, 608
 Z-pinch, 324
 Prasad, S. V.
 Atomic-Layer Deposition of Tribological Coatings, 51
 Mechanics and Tribology of MEMS Materials, 258
 Preconcentrator
 Chemical collection, 550
 Explosives, 637
 Pathogens, 793
 Preece, D. S.
 Computational Modeling of Fracture in Geomaterials, 228
 Prentice, W. J.
 Flexible Robotic Maintenance Facility, 373
 Pretreatment, 169
 Prevender, T. S.
 Prompt Global Response, 696
 Primate, 734
 Processor, 607
 Prognostic, 368
 Programming
 Massively parallel, 139
 Stochastic, 115
 Propagation, 200
 Protection, 595
 Protein
 Cell signaling, 75
 Structure generation, 73
 Protocol, 361
 Proton
 Directed energy, 863
 Exchange, 513
 Prototype
 Advanced manufacturing, 887
 Engine, 773
 High-density circuitry, 59
 Provencio, P. P.
 Pulsed-Particle Beams on Metal-to-Plastic Interfaces, 918
 Pryor, R. J.
 A Model of Infrastructure Interdependency, 460
 Error-Control Codes for Engineered Regulatory Systems, 912
 Pulse
 Laser, 336
 Particle beams, 918
 See also: Power
 Pura, C. A.
 A Systems Approach to Defending Our Borders, 699
 Purification, 471
 PVDF
 See Polyvinylidene fluoride
Q
 Quality, 486
 Quijada, G. B.
 Energy-Efficient Feedstock Hydrocarbon Separations, 457
R
 Raber, T. N.
 Microengine for Advanced Power Generation, 349

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Radar (SAR)
 Digital, 363
 Wide-area, 451
 Rader, D. J.
 Bioaerosol Collection for Detectors, 618
 Rarefied-Gas Dynamics and Surface Interactions, 220
 Radiation
 Advanced coolants, 923
 Diffusion flames, 225
 Hardened optoelectronics, 635
 Nonvolatile memories, 174
 Radiation aging, 210
 Transport, 234
 See also: Irradiation
 Radio, 608
 Radio frequency (RF)
 Filtering, 162
 Microelectromechanical, 160
 Miniature, 861
 Radioactive-waste
 Waste management, 502
 See also: Nonradioactive
 Rahimian, K.
 Nuclear Safety for Thermal and Mechanical, 801
 Security Coatings for Multichip Modules, 612
 Thermally Cleavable Surfactants, 305
 Ralph, M. E.
 Agent-Based Control of Infrastructure Resources, 539
 Validated Modeling of Distributed Energy Resources, 494
 Rambo, P. K.
 Large-Aperture Sol-Gel Diffraction Grating, 338
 Rapid-prototyping high-density circuitry, 59
 Rarefied
 Flows, 855
 Gas dynamics, 220
 Raybourn, E. M.
 CONOPS Development for Automated Systems, 387
 Rayleigh scattering, 203
 Reactive, 533
 Reactor
 Advanced coolants, 923
 Microbioreactor, 813
 Nuclear, 522
 Supercritical water, 922
 Reagan, M. T.
 Uncertainty Propagation in Thermofluid Systems, 200
 Reagent, 167
 Real-time
 Water contamination, 519
 Water monitoring, 486
 Reckaway, D. E.
 Microfabrication with Femtosecond-Laser Processing, 44
 Reconnaissance, 248
 Recyclable, 327
 Reece, M.
 Sensing of Phase Transformations in Steels, 48
 Reed, S. T.
 Large-Aperture Sol-Gel Diffraction Grating, 338
 Reedy, E. D., Jr.
 Analysis of Nanoscale Films and Particles, 232
 Disbonding Initiation of Interfacial Cracks, 782
 High-Fidelity Frictional Models for MEMS, 222
 Reeves, P. C.
 Augmented Cognition, 687
 Reflectometry, 486
 Regueiro, R. A.
 Computational Modeling of Fracture in Geomaterials, 228
 Reichardt, T. A.
 Eye-Safe Short-Range Standoff Aerosol-Cloud Finder, 434
 Reichmuth, D. S.
 Molecular Integrated Microsystems, 725
 Reineke, M. C.
 Passive-Legged, Multisegmented, Robotic Vehicle, 568
 TALON, 690
 Reinhardt, J. C.
 A Systems Approach to Defending Our Borders, 699
 Reinhart, W. D.
 Hypervelocity Impact-Generated Flash, 422
 Remote
 Deployable optics, 559
 Geologic characterization, 584
 Kill assessment, 633
 Mapping, 399
 Sensing (photonic), 571
 Sensing (Polychromator), 197
 Sensing (spectral), 556
 Water monitoring, 486
 Rempe, S. L.
 Interfacial Bioscience Grand Challenge, 680
 Renk, T. J.
 Electron- and Proton-Beam Directed-Energy Weapons, 863
 Pulsed-Particle Beams on Metal-to-Plastic Interfaces, 918
 Renlund, A. M.
 Advanced Weapons Signatures, 659
 Reno, J. L.
 Continuous-Wave Intersubband Terahertz Sources, 165
 Engineered Superconductivity in Electron-Hole Bilayers, 157
 Renzi, R. F.
 Molecular Integrated Microsystems, 725
 Repartitioning, 110
 Reser, T. J.
 Nonlethal Technologies for the War on Terrorism, 702
 Resin, 780
 Resolution, 413
 Resonant, 562
 Resources
 Distributed infrastructure, 539
 Energy, 494
 Senate committee, 537
 Water, 721

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Response
 Cellular, 867
 Global, 696
 Immune, 93
 Seismic, 396
 Reversible, 246
 Rexroth, P. E.
 Nuclear Process Transparency and Control, 509
 RF
 See Radio frequency
 Rhykerd, C. L., Jr.
 Improved Chemical-Agent Collection, 550
 Richards, J. A.
 Surveillance in Synthetic-Aperture Radar Images, 451
 Rieger, D. J.
 An Integrated, Stacked System-on-a-Chip, 183
 Miniaturization of SAR Electronic Assembly, 411
 Photonic-Bandgap Structures for Sensor Protection, 595
 Rightley, G. S.
 MOSFET–MEMS Integration, 189
 Rinehart, L. F.
 EM Interactions with Systems to Enhance Security, 392
 Nonlethal Technologies for the War on Terrorism, 702
 Rintoul, M. D.
 Computational Model of a Microbial Cell, 821
 Interfacial Bioscience Grand Challenge, 680
 Protein Structure Generation, 73
 Rio Grande, 721
 Risk, 141
 Ritchey, M. B.
 Photonic-Lattice Structures for Remote Sensing, 571
 Rivas, R. R.
 Autonomous Microexplosive Subsurface Tracing, 475
 Roach, D. P.
 Failure Analysis of Composite Patching, 844
 Roberts, J. D.
 Real-Time Water-Quantity/-Quality Monitoring, 486
 Robertson, P. J.
 Cryptographic Assurance of Execution Correctness, 642
 Robino, C. V.
 Packaging Technology for Microsystems, 315
 Sensing of Phase Transformations in Steels, 48
 Robinson, A.
 Micro Flame-Based Detector Suite, 437
 Microsystems for Reagent Delivery, 167
 Robinson, D. G.
 Vulnerability Assessment of National Power Grid, 477
 Robinson, M. V. C.
 Advanced Packaging Technology for Optical Firesets, 804
 Robot
 Learning, 911
 Maintenance, 373
 Mobile, 921
 Planning, 627
 Vehicle, 568
 Rochau, G. E.
 Nuclear Process Transparency and Control, 509
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
 Rock, 747
 Rodriguez, M. A.
 Icosahedral Boride Semiconductor Beta Cell, 580
 Soft-Solution Processes for Nanoscale Growth, 263
 Roesler, A. W.
 Novel and Robust Environmental-Sensing Devices, 809
 Rogers, C. O.
 Analysis of Multichannel Internet Messaging, 669
 Rogers, D. M.
 Algorithms for Simulations of Chemical Attacks, 136
 Rogers, J. D.
 Near-Real-Time Characterization for HDBT Defeat, 693
 Roher, B. R.
 Monomolecular Carbon Nanothread Fabrication, 443
 Rohwer, J. A.
 Algorithm Development for Smart Antennas, 842
 Smart Decoy Sensor Network, 441
 Rohwer, L. E. S.
 A Revolution in Lighting, 671
 Hermetic Packaging for MEMS Integrated Microsystems, 888
 Romero, L. A.
 Micromagnetic Suspension, 122
 Romero, V. J.
 Advanced Nuclear Engineering Analysis Technology, 506
 Rossi, P.
 Direct Single-Ion Machining of Nanopores, 916
 Routing, 118
 RpHdc
 See Rapid-prototyping high-density circuitry
 Ruby, D. S.
 Real-Time Water-Quantity/-Quality Monitoring, 486
 Rudd, J. V.
 Remote Mapping of Electromagnetic Fields, 399
 Ruffner, J. A.
 Resin Infusion Between Double Flexible Tooling, 780
 Rush, B. M.
 Contaminant Transport in Architectural Spaces, 614
 Russ, T. D.
 A Systems Approach to Defending Our Borders, 699
 Content-Based Video and Image Indexing System, 616
 Rutledge, W. H.
 Prompt Global Response, 696

S
 Saavedra, M. P.
 Linear Magnetic Actuators, 35
 Sackinger, P. A.
 Elucidating the Mysteries of Wetting, 61
 Safety
 Nonradioactive, 922
 Nuclear weaklinks, 801

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Salazar, J. S.
Data Fusion and Visualization of MASINT Results, 355
Moving-Target Identification, 413
- Salazar, R. A.
New Mechanism for Upset of Electronics, 371
Secure Chaotic Communications, 430
- Salinger, A. G.
A Revolution in Lighting, 671
- Salton, J. R.
Buzzard, 629
Ornithopter, 830
Prompt Global Response, 696
- Samora, S.
Arrayed Resonant Subwavelength Gratings, 562
Continuous-Wave Intersubband Terahertz Sources, 165
- Sample
Biomimetic air, 823
Cellular pretreatment, 169
Dielectrophoretic, 589
Electrooptic, 399
- Sanders, J. D.
Polymer Spin-Coating for Semiconductors, 254
- Sandison, D. R.
Compliant Membranes for MEMS Microphones, 784
- Sandusky, J. V.
Photonic-Bandgap Structures for Sensor Protection, 595
- Santos, A.
Tagging for Tracking and Authentication of Documents, 577
- Sapphire, 788
- Sapra, R.
Detecting Genetic Engineering in Bioweapons Strains, 621
- SAR
See Synthetic-aperture radar
- Sasaki, D. Y.
Biocompatible Self-Assembly of Nanomaterials, 248
Interfacial Bioscience Grand Challenge, 680
Light-Powered Nanovehicles, 832
Lipid Membranes on Nanostructured Silicon, 778
Modeling Biomembranes, 91
Nanostructured Materials for Directed Transport, 289
- Savignon, D. J.
Radiation-Hard Nonvolatile Memories, 174
- Scalar, 859
- Scanning, 851
- Scharf, R. W.
Atomic-Layer Deposition of Tribological Coatings, 51
- Schefer, R. W.
Filtered Rayleigh-Scattering Diagnostic, 203
Soot Formation in Unsteady Diffusion Flames, 225
- Schiek, R. L.
A Parallel Circuit Simulator for Cell Biology, 129
- Schisler, J. D.
MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
- Schmidt, C. O., II
Advanced Weapons Signatures, 659
- Schmidt, R. C.
3-D Large-Eddy Simulation of Turbulent Flow, 892
- Schneider, H. C.
Quantum Coherence in Semiconductor Nanostructures, 187
- Schoeniger, J. S.
Interfacial Bioscience Grand Challenge, 680
Membrane Protein Interactions in Cell Signaling, 75
- Schoenwald, D. A.
A Model of Infrastructure Interdependency, 460
- Schroder, K. L.
Eye-Safe Short-Range Standoff Aerosol-Cloud Finder, 434
- Schroeder, J. L.
PVDF as a Piezoelectric Film, 645
- Schroeppel, R. C.
Hybrid Infrastructure Cryptography, 404
Improved Performance in Cryptographic Protocols, 361
Joint Authentication/Encryption, 623
Photonic Encryption Using All-Optical Logic, 901
Quantum Computing Accelerator I/O, 836
Securing Mobile Code, 524
- Schultz, P. A.
Metal-/Oxide-Joining in NW Component Manufacturing, 899
Radiation Aging of Microelectronics, 210
- Schunk, P. R.
Diesel Catalytic Particulate Traps, 499
Large-Deformation Solid-Fluid Interaction, 212
Wetting and Penetration into Porous Media, 762
- Schuster, G. R.
Multipurpose Locator-Tag System, 664
- Schwank, J. R.
Radiation Aging of Microelectronics, 210
- Scott, S. H.
Nonlethal Technologies for the War on Terrorism, 702
- Screening
Background monitoring, 904
Bombs, 655
- SCWR (supercritical water reactor safety)
See Supercritical
- SDAC
See Sense, decide, act, and communicate
- Seager, C. H.
A Revolution in Lighting, 671
Efficiency of GaN HEMT High-Power Amplifiers, 193
- Sears, M. P.
Protein Structure Generation, 73
- Secure
Chaotic communications, 430
Coatings, 612
Cognitive models, 871
Electromagnetic interactions, 392
Homeland, 136
Information technology, 573
Internet connectivity, 597
Internet protocol, 126
Mobile code, 524
Robotic planning, 627
- Segalman, D. J.
Large-Deformation Solid-Fluid Interaction, 212

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Seidel, D. B.
Nonlethal Technologies for the War on Terrorism, 702
- Seismic
Bomb damage, 396
Detection, 897
- Self-Assembled
Biomicroelectromechanical, 248
DNA/metal, 819
Nuclear waste, 466
Polymers, 732
- Self-organizing, 816
- Selph, M. M.
Computed Tomography X-Ray Screening, 655
- Selvaganapathy, P.
Molecular Integrated Microsystems, 725
- Semantic, 911
- Semiconductor
Antimonide/nitride, 145
Icosahedral boride, 580
Nanostructures, 187
Photolithographic, 254
- Senate, 537
- Senglaub, M. E.
CONOPS Development for Automated Systems, 387
- Sense, decide, act, and communicate (SDAC)
Architectural, 705
MicroTalon, 454
- Sensor
Chem-bio, 662
Chemometrics, 556
Dispersive photonics, 155
Environmental, 809
Functionalized nanoparticles, 176
Geologic characterization, 584
Graph theory, 416
Large-aperture optics, 559
Magnetostrictive elastomers, 319
Micro flame-based, 437
Mobile ground, 365
Pathogens, 793
Phase transformations, 48
Photonic (bandgap), 595
Photonic (lattice), 571
Polychromator, 197
Radioactive waste, 502
Smart (decoy), 441
Smart (flights), 102
Unattended ground (advanced), 357
Unattended ground (algorithm), 428
Volatile contaminants, 463
Water-contamination, 519
See also: Biosensor
See also: Microsensor
- Separation
Feedstock hydrocarbon, 457
Polymeric, 880
See also: Microseparation
- Sequestration, 790
- Sergeant, J.
Identification of Regulated Chemicals in Water, 491
- Serkland, D. K.
Leaky-Mode VCSELs for Photonic Logic Circuits, 195
Photonic Encryption Using All-Optical Logic, 901
Quantum Coherence in Semiconductor Nanostructures, 187
Radiation-Hardened Optoelectronic Components, 635
Semiconductors for Optoelectronic Materials, 145
- Settersten, T. B.
Diagnostics for Airborne Carbon Nanoparticles, 468
- Shaddix, C. R.
Soot Formation in Unsteady Diffusion Flames, 225
- Shaneyfelt, M. R.
Radiation Aging of Microelectronics, 210
- Shaw, M. J.
Microoptical Gyroscope Via Optical Integration, 191
- Sheaffer, D. A., Jr.
Smart Sensors for Joint Test Assembly Flights, 102
- Shediac, R.
Microfabricated Dielectrophoretic Sample Preparation, 589
Molecular Integrated Microsystems, 725
- Shelnutt, J. A.
Biomimetic Chloroplasts, 83
Light-Powered Nanovehicles, 832
- Shepodd, T. J.
Molecular Integrated Microsystems, 725
Ultraclean Environments in Microsystem Packages, 246
- Shocked, 788
- Shokair, I. R.
Eye-Safe Short-Range Standoff Aerosol-Cloud Finder, 434
- Showalter, S. K.
Micro Flame-Based Detector Suite, 437
Novel Micropreconcentrators, 637
- Shul, R. J.
A Revolution in Lighting, 671
Controlled Motion for a Microfluidic Drop Ejector, 46
Efficiency of GaN HEMT High-Power Amplifiers, 193
High-Field Effects of GaN HEMTs, 869
Microfabricated Acoustic-Spectrum Analyzer, 547
Microfuze, 380
Novel Micropreconcentrators, 637
- Sichler, J. L.
Near-Real-Time Characterization for HDBT Defeat, 693
- Siegal, M. P.
Carbon Adsorbers for Chemical Microsensors, 906
Icosahedral Boride Semiconductor Beta Cell, 580
Identification of Regulated Chemicals in Water, 491
Novel Micropreconcentrators, 637

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Siegel, M. D.
 Anion Nanoengineered Sorbents for Water Purification, 471
- Signal
 Cell, 75
 Digital, 603
 Membrane (molecular machines), 96
 Membrane (transduction pathway), 86
 Nuclear weapons, 633
 Transduction, 819
- Signature
 Chemical, 167
 Weapons, 659
- Silicon
 Lipid membranes, 778
 Microelectromechanical, 160
 Photonics, 172
- Simmons, B. A.
 Assembly of Electrooptical and Bioactive Materials, 312
 Biomicrofuel Cell, 685
 Decomposition of Contaminants Using Nanoparticles, 303
 Harnessing Methane-Hydrate Bacteria Interactions, 722
 Magnetic Properties of Nanoparticles, 838
 Microfabricated Dielectrophoretic Sample Preparation, 589
 Sensor for Live Waterborne Pathogens, 793
 Thermally Cleavable Surfactants, 305
- Simmons, J. A.
 Engineered Superconductivity in Electron-Hole Bilayers, 157
- Simonson, R. J.
 Biocompatible Self-Assembly of Nanomaterials, 248
 Functionalized Nanoparticles for Sensor Applications, 176
 Microsystems for Reagent Delivery, 167
- Simpson, R. L.
 A Revolution in Lighting, 671
- Simulation
 Agents, 359
 Atomistic-continuum, 218
 Cell biology, 129
 Contaminant transport, 614
 Critical infrastructure, 530
 Energy, 537
 Gas flows, 234
 Hydrogen futures, 535
 Laser pulses, 336
 Molecular, 729
 Nondeterministic, 115
 Nonlinear solvers, 134
 Sensitivities, 124
 Solid-fluid, 756
 Terrorist attack, 136
 Turbulent flow, 892
 Weapons, 239
- Simultaneous, 89
- Sinclair, M. B.
 Active Photonic Nanostructures, 321
 Informatics for Systems Biology, 78
 MOSFET–MEMS Integration, 189
 Nanostructured Materials for Directed Transport, 289
 Photonic-Lattice Structures for Remote Sensing, 571
 Polychromator Systems for Remote Chemical Sensing, 197
 Predicting and Validating MEMS Interface Reliability, 753
- Singh, A. K.
 High-Throughput Identification of Molecular Machines, 96
 Interfacial Bioscience Grand Challenge, 680
 Membrane Protein Interactions in Cell Signaling, 75
 Microfabricated Dielectrophoretic Sample Preparation, 589
 Molecular Integrated Microsystems, 725
- Sintering, 243
- Skala, D. M.
 Miniature Transmitter Filter for JTA, 807
- Skousen, T. J.
 Predictive Accelerated Aging of Microsystems, 795
- Sleeve, G. E.
 Assessment of Bomb Damage to Underground Facilities, 396
- Slepoy, A.
 Computational Model of a Microbial Cell, 821
 Failure Analysis of Micromachines, 100
 Immune Responses to Bioterrorism Threats, 93
 Interfacial Bioscience Grand Challenge, 680
- Sloan, G. R.
 Agile, Microsystems-Enabled Receiver, 600
- Slutz, S. A.
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
- Small, D. E.
 Advanced Mobile Networking Using Graph Theory, 416
- Smart
 Antennas, 842
 Detectors, 924
 Sensor (decoy), 441
 Sensor (flight), 102
 Tensegrity, 236
- Smartt, H. A.
 Hyperspectral Tagging for Unique Identification, 647
- Smith, A. V.
 Continuous-Wave Intersubband Terahertz Sources, 165
- Smith, B. K.
 Radiation-Hard Nonvolatile Memories, 174
- Smith, I. C.
 Large-Aperture Sol-Gel Diffraction Grating, 338
- Smith, J. L.
 Geologic Characterization of Difficult Targets, 584
 MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
- Smith, M. W.
 Focal-Region Sounding for Large-Aperture Telescopes, 652
- Smith, R. B.
 Agent-Based Control of Infrastructure Resources, 539

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Smith, T. M.
Sensitivities for Large-Scale Simulation Codes, 124
- Smithpeter, C. L.
Hard Target Defeat High-G-Tolerant Fuze, 407
- Smrcka, J. D.
Modeling of Groups Perpetrating Violence, 712
- Snell, M. K.
Robotic Planning for Physical-Security Analysis, 627
- Snipes, P. A.
Radiation-Hardened Optoelectronic Components, 635
- Sobel, A. L.
Interactive Nuclear/WMD Terrorist Data Model, 716
- Social, 712
- Soft
Nanoscale growth, 263
Superlattices, 282
- Software, 816
- Sokolowski, S. S.
Novel Micropreconcentrators, 637
- Sol-gel, 338
- Solid/fluid
Interaction, 212
Mechanical, 228
Simulation, 756
- Solid-state
Lighting, 671
Switch, 332
- Solver (parallel)
Nonlinear, 134
Repartitioning, 110
- Sommerville, W. T.
Tagging for Tracking and Authentication of Documents, 577
- Song, S.
Molecular Integrated Microsystems, 725
- Sonnek, J. D.
Analysis of Multichannel Internet Messaging, 669
- Soot, 225
- Sorbents, 471
- Sorensen, K. W.
Prompt Global Response, 696
- Sounart, T. L.
MEMS in μ Fluid Channels, 152
- Sounding, 652
- Souza, C. A.
Sandia Decon Formulation on the SARS Coronavirus, 543
- Space
Architectural, 614
Free, 399
Microelectronics, 210
Mirror, 645
Optoelectronics, 635
See also: Aerospace
See also: Headspace
- Spahn, O. B.
Ultralightweight Telescope with MEMS Adaptive Optic, 631
- Spangler, S.
Alanate-Hydride Fuel-Cell Demonstration Project, 515
- Spectral
Calibration algorithms, 274
Sensing, 556
Unmixing, 649
See also: Hyperspectral
- Spectrometer
Ion-mobility (Fourier-transform), 385
Ion-mobility (mass), 640
Micromass, 185
- Spectrum
Acoustic analyzer, 547
Waveforms, 552
- Speed, A. E.
Adaptive Awareness for Personal Decision Making, 394
Simulator Agents with Humanlike Episodic Memory, 359
Terrorist-Activity Plan-Assessment Methodology, 714
- Spin-coating, 254
- Spindles, 64
- Spires, S. V.
Information Flow Associated with International Borders, 708
- Spletzer, B. L.
Buzzard, 629
Ornithopter, 830
- Sprigg, J. A.
A Model of Infrastructure Interdependency, 460
Sophisticated Agent Evolution and Optimization, 113
- Stacked, 183
- Staiger, C. L.
Biomicrofuel Cell, 685
- Stalford, H. L.
Microfabricated Acoustic-Spectrum Analyzer, 547
- Stalker, K. T.
Near-Real-Time Characterization for HDBT Defeat, 693
Prompt Global Response, 696
TALON, 690
- Stamp, J. E.
Surety for Wireless Automated-Control Networks, 504
- Standoff, 434
- Stanley, J. B.
MOSFET-MEMS Integration, 189
- Stark, B. H.
Hermetic Packaging for MEMS Integrated Microsystems, 888
- Stark, D. P.
SDAC Architectural Study and Demonstration System, 705
- Starr, M. J.
High-Fidelity Frictional Models for MEMS, 222
- Steel, 48
- Steen, W. A.
Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
- Steichen, R. J.
Analysis of the Automotive Industry, 760
- Stephenson, L. L.
Engineered Superconductivity in Electron-Hole Bilayers, 157
- Sterilization, 353
- Sterk, T. M.
Anomalous Weapon Surveillance Waveforms, 710

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Stevens, J. E.
Silicon-Based RF MEMS Components, 160
- Stevens, J. W., III
Agent-Based Control of Infrastructure Resources, 539
Validated Modeling of Distributed Energy Resources, 494
- Stevens, M. J.
Interfacial Bioscience Grand Challenge, 680
Modeling Biomembranes, 91
- Stewart, K. D.
Alanate-Hydride Fuel-Cell Demonstration Project, 515
- Stinnett, R. W.
TALON, 690
- Stochastic, 115
- Stockpile
Monitoring, 811
Radiation aging, 210
- Stone, C. M.
Algorithmic Issues in Multiphysics Couplings, 775
- Storage
Containers, 798
Energy, 722
Internet protocol, 126
- Stork, C. L.
Multivariate Spectral Calibration Algorithms, 274
Robust Chemometrics for Remote Spectral Sensing, 556
- Stotts, L. G.
TALON, 690
- Strachan, J. W.
Information Flow Associated with International Borders, 708
- Straumanis, A. R.
Biomicrofuel Cell, 685
Microsystems for Reagent Delivery, 167
- Stream, 486
- Structural, 105
- Structure
Ge/Si, 851
Nanofluidics, 278
Photonic bandgap, 595
Photonic lattice, 571
Porous media, 762
Simulations of weapons, 239
Tensegrity, 236
See also: Infrastructure
See also: Microstructure
See also: Nanostructure
- Struve, K. W.
Suppression of Electron Emission from Conductors, 329
Z-Pinch Power-Plant System Development, 324
- Stubblefield, W. A.
Terrorist-Activity Plan-Assessment Methodology, 714
- Stuecker, J. N.
Diesel Catalytic Particulate Traps, 499
- Stygar, W. A.
Recyclable Transmission Line Concept for Z-Pinch IFE, 327
Suppression of Electron Emission from Conductors, 329
- Subia, S. R.
Large-Deformation Solid-Fluid Interaction, 212
- Subpixel, 649
- Subramanian, G. S.
Active Photonic-Crystal Devices, 172
Active Photonic Nanostructures, 321
- Substrate, 411
- Subsurface
Imaging, 857
Tracing, 475
- Subwavelength, 562
- Sullivan, J. P.
Nanoelectromechanical Oscillators for RF Filtering, 162
Varying Humidity on Copper-Sulfide Film Formation, 293
- Sumali, H.
Coupled Simulations of Weapons Systems, 239
Deployable Large-Aperture Optics System, 559
- SUMMIT (Security Monitoring and Management with Information Technology)
See Secure
- Sun, A. C.
Flow Control and Mixing in Microfluidic Devices, 847
Micro-/Nanoscale Thermomechanical Manufacturing, 853
- Suo-Anttila, J. M.
Soot Formation in Unsteady Diffusion Flames, 225
- Superconductivity, 157
- Supercritical, 922
- Superhard, 877
- Superlattice, 282
- Suppression
Chemical/fire, 448
Electron emission, 329
- Surety
Chemical, 637
Composite patching, 844
Storage containers, 798
Wireless networks, 504
- Surface
Aqueous nanofluidics, 278
Biospecific, 867
GaAs, 890
Gas dynamics, 220
Metal micromachines, 178
Micropackages, 309
Nanoengineered, 790
Scalar concentrations, 859
See also: Subsurface
- Surfactant
Lateral growth, 890
Thermally cleavable, 305
- Surveillance
Synthetic-aperture radar, 451
Waveforms, 710
- Suspension, 122
- Swartzentruber, B. S.
Atomic-Scale Measurements of Nucleation of Ge/Si, 851
Single-Channel Membrane Pores, 71
Monomolecular Carbon Nanothread Fabrication, 443

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Sweatt, W. C.
 A Revolution in Lighting, 671
 Photonic-Lattice Structures for Remote Sensing, 571
- Swiler, L. P.
 Prognostic Health Monitoring and Maintenance, 368
- Switch
 Solid-state, 332
 Water, 341
- Symons, N. P.
 Assessment of Bomb Damage to Underground Facilities, 396
 Near-Real-Time Characterization for HDBT Defeat, 693
- Synthesis
 Inverse micellar, 744
 Superlattice, 282
- Synthetic-aperture radar
 Digital radar, 363
 Miniaturization, 411
 Surveillance, 451
- T**
- Tag
 Digital radar, 363
 Hyperspectral, 647
 Locator, 664
 Microwave, 610
 Tracking, 577
- Talin, A. A.
 Molecular Electronics Test Platform, 908
- Tallant, D. R.
 A Revolution in Lighting, 671
 Catalyzation of Complex-Hydride Reactions, 307
 Quantification of Environments Within Micropackages, 309
 Soft-Solution Processes for Nanoscale Growth, 263
- TALON
 TALON, 690
 See also: MicroTalon
- Tam, R.
 Communication in Counterterrorism Crisis Management, 420
- Tanaka, T. J.
 High-Efficiency Turbine Blade Coatings, 483
- Tandon, R.
 Air Sterilization and Decontamination, 353
- Tang, J. D.
 Photonic Encryption Using All-Optical Logic, 901
- Tanner, D. M.
 Predictive Accelerated Aging of Microsystems, 795
- Tappan, A. S.
 Microfuze, 380
 Nanoscale Energetic Materials, 744
- Target
 Acoustic-seismic, 603
 Digital radar, 363
 Geologic characterization, 584
 Hard (fracture), 228
 Hard (high-G), 407
 Moving, 413
- Targeting, 657
- Tarman, T. D.
 Active Network and Use of Network Processor, 607
 Cryptographic Assurance of Execution Correctness, 642
 Photonic Encryption Using All-Optical Logic, 901
 Secure MPLS Control Plane for Internet Connectivity, 597
- Tarver, E. E., III
 Miniature Fourier-Transform Ion-Mobility Spectrometer, 385
- Tedeschi, W. J.
 Interactive Nuclear/WMD Terrorist Data Model, 716
- Telescope
 Large aperture, 652
 Ultralightweight, 631
- Tensegrity, 236
- Terahertz
 Continuous-wave, 165
 Emerging threats, 418
 Transceiver, 399
- Terrorism
 Data model, 716
 Homeland Security, 136
 Nonlethal, 702
 Plan assessment, 714
 See also: Bioterrorism
 See also: Counterterrorism
- Teter, D. M.
 The Basics of Aqueous Nanofluidics, 278
- Thai, T. Q.
 Active Network and Use of Network Processor, 607
 Creative Networking of Commercial Products, 666
 Networked Device Demonstration, 667
- Thermal
 Cleavable surfactants, 305
 Modeling, 215
 Rayleigh scattering, 203
 Transport, 770
 Weaklinks, 801
- Thermionic, 473
- Thermofluid, 200
- Thermomechanical, 181
- Thin-film
 Exothermic, 54
 Microfabrication, 40
- Thoma, S. G.
 Nuclear Safety for Thermal and Mechanical, 801
- Thomas, E. D.
 Adaptive Network Countermeasures, 346
- Thomas, E. V.
 Informatics for Systems Biology, 78
 Robust Chemometrics for Remote Spectral Sensing, 556
- Thomas, M. L.
 Microsensors in Radioactive-Waste Management, 502
 Monitoring of Volatile Contaminants, 463
- Thompson, A. P.
 Molecular Integrated Microsystems, 725
 Molecular Simulations of MEMS, 729

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Thornberg, S. M.
 Energy-Efficient Feedstock Hydrocarbon Separations, 457
 Ion-Mobility Spectrometer/Mass Spectrometer, 640
 Novel Catalysts for Hydrogen Fuel-Cell Applications, 527
 Polymer Spin-Coating for Semiconductors, 254
 Quantification of Environments Within Micropackages, 309
- Threat, 93
- Throckmorton, D. J.
 High-Throughput Identification of Molecular Machines, 96
- Thurston, B. D.
 Large-Aperture Sol-Gel Diffraction Grating, 338
- THz
See Terahertz
- Tidwell, V. C.
 Algorithms for Simulations of Chemical Attacks, 136
 Modeling Water Demand, 741
 Real-Time Water-Quantity/-Quality Monitoring, 486
 System-Dynamics Modeling of Water Resources, 721
- Tieszen, S. R.
 Computational Studies of JP-8 Diffusion Flames, 925
- Tigges, C. P.
 Agile, Microsystems-Enabled Receiver, 600
 Assembly of Microsystems Using Thin Films, 54
 Efficiency of GaN HEMT High-Power Amplifiers, 193
 Nanoelectromechanical Oscillators for RF Filtering, 162
 Quantum Computing Accelerator I/O, 836
- Tikare, V.
 Modeling of Sintering, 243
- Timlin, J. A.
 Informatics for Systems Biology, 78
 Immune Responses to Bioterrorism Threats, 93
- Tomography, 655
- Toole, T. J.
 Adaptive Network Countermeasures, 346
- Tooling, 780
- Tooman, T. P.
 Eye-Safe Short-Range Standoff Aerosol-Cloud Finder, 434
- Topological, 849
- Torczynski, J. R.
 Rarefied-Gas Dynamics and Surface Interactions, 220
 Simulate Noncontinuum Gas Flows for MEMS Devices, 234
- Torgerson, M. D.
 Hybrid Infrastructure Cryptography, 404
 Joint Authentication/Encryption, 623
 Secure MPLS Control Plane for Internet Connectivity, 597
 Securing Mobile Code, 524
 Surety for Wireless Automated-Control Networks, 504
- Toth, R. P.
 Air Sterilization and Decontamination, 353
 Nonlethal Technologies for the War on Terrorism, 702
- Toxic, 389
- Toxin
 Molecular machines, 96
See also: Biotoxin
- Tracing, 475
- Tracking
 Insider, 587
 Tagging, 577
- Trajectory, 840
- Transceiver, 399
- Transduction
 DNA/metal, 819
 Membrane signaling, 86
- Transformation, 48
- Transient, 256
- Transmission, 327
- Transmitter, 807
- Transparency, 509
- Transport
 Contaminant, 614
 Excitation energy, 289
 Radiation, 234
 Simulation, 136
 Soot, 225
 Thermal, 770
- Trap
 Catalytic particulate, 499
 Optical, 541
- Tribology
 Coatings, 51
 Microelectromechanical, 258
- Trigger, 341
- Trott, W. M.
 Determination of Microstructural Properties, 334
 Nanoscale Energetic Materials, 744
 Rarefied-Gas Dynamics and Surface Interactions, 220
- Troup, C. B.
 Interfacial Bioscience Grand Challenge, 680
 Membrane Protein Interactions in Cell Signaling, 75
- Trudell, D. E.
 Sensors for Water-Contamination Events, 519
- Tsang, R. P.
 Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Tsao, J. Y.
 A Revolution in Lighting, 671
- Tucker, M. D.
 Decontamination of Toxic Industrial Chemicals, 389
 Dual-Use Formulation for CBW/Fire Suppression, 448
 Sandia Decon Formulation on the SARS Coronavirus, 543
- Tucker, R. D.
 Prompt Global Response, 696
- Tucker, S.
 Adaptive Awareness for Personal Decision Making, 394
 Improving Human/System Interactions, 425
- Tuminaro, R. S.
 Geophysical Subsurface Imaging, 857
- Turbine, 483
- Turbulence, 892
- Turnley, J. G.
 Modeling of Groups Perpetrating Violence, 712

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Turnquist, M. A.
 Critical-Infrastructure Interdependencies, 489
 Simulation in Critical Infrastructures, 530
- Tuttle, B. A.
 Security Coatings for Multichip Modules, 612
- U**
- Unattended
 Background monitoring, 904
 Ground sensor (advanced), 357
 Ground sensor (algorithm), 428
- Uncertainty, 200
- Underground
 Bomb damage, 396
 Facility characterization, 355
- Uribe, F.
 Novel and Robust Environmental-Sensing Devices, 809
- V**
- Vacuum, 242
- Validate
 Distributed energy, 494
 Microelectromechanical, 753
- Valleau, C. A.
 Large-Aperture Sol-Gel Diffraction Grating, 338
- Van Benthem, M. H.
 Multivariate Spectral Calibration Algorithms, 274
 Robust Chemometrics for Remote Spectral Sensing, 556
- Van Bloemen Waanders, B. G.
 Algorithms for Simulations of Chemical Attacks, 136
 Sensitivities for Large-Scale Simulation Codes, 124
- Vandernoot, V. A.
 High-Throughput Identification of Molecular Machines, 96
- Van Dyke, C. W.
 SDAC Architectural Study and Demonstration System, 705
- Van Leeuwen, B. P.
 Advanced Mobile Networking Using Graph Theory, 416
 Algorithm Architecture for Unattended Ground Sensors, 428
 Information Assurance for Wireless *Ad Hoc* Networks, 401
 Robust Message Routing for Mobile *Ad Hoc* Networks, 118
- Vanrandwyk, J. A.
 Adaptive Network Countermeasures, 346
 IP Storage: A Performance and Security Study, 126
- Van Swol, F. B.
 Assembly of Electrooptical and Bioactive Materials, 312
- Vapor
 Microfabrication processes, 40
 Water-splitting, 517
- Vaporization, 256
- Vasile, M. J.
 Microfabrication Processes, 40
- Vawter, G. A.
 Compact Terahertz Sources, 418
 Continuous-Wave Intersubband Terahertz Sources, 165
 Dispersive Photonics for Sensors and Microsystems, 155
 Microoptical Gyroscope Via Optical Integration, 191
 Photonic Encrytion Using All-Optical Logic, 901
- VCSELs
 See Vertical-cavity surface-emitting lasers
- Vector, 840
- Vehicle
 Aerospace, 840
 Bombs, 655
 Robotic, 568
 Ultrahigh temperature, 625
 See also: Nanovehicle
- Velocity
 Coilguns, 445
 Impact, 422
- Verification, 736
- Vernon, M. E.
 Gas Power-Conversion Systems for Nuclear Reactors, 522
- Vertical-cavity surface-emitting lasers (VCSELs), 195
- Vesey, R. A.
 Recyclable Transmission Line Concept for Z-Pinch IFE, 327
- Video
 Indexing, 616
 Screening, 904
- Vigil, S. R.
 Photonic-Bandgap Structures for Sensor Protection, 595
- Violence, 712
- Visual
 Cortex, 734
 Mobile manipulation, 383
- Visualization, 355
- Voigt, J. A.
 Solution-Based Nanoengineering of Materials, 296
 Water Desalination, 496
- Volatile
 Contaminants, 463
 See also: Nonvolatile
- Voltage, 494
- Vulnerability, 477
- W**
- Wagner, G. J.
 Failure Analysis of Micromachines, 100
- Wagner, J. S.
 Augmented Cognition, 687
- Walck, M. C.
 Near-Real-Time Characterization for HDBT Defeat, 693
- Waldrip, K. E.
 A Revolution in Lighting, 671
 Semiconductors for Optoelectronic Materials, 145
- Walker, A. W.
 A Microbioreactor for Hydrogen Production, 813
 Biomicrofuel Cell, 685
- Walker, C. L.
 Geologic Characterization of Difficult Targets, 584
- Wall, F. D.
 Critical Length Scales for Corrosion Processes, 265

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Wally, K.
 Bioaerosol Collection for Detectors, 618
 Biomicrofuel Cell, 685
 Molecular Integrated Microsystems, 725
- Walsh, E. J.
 Smart Sensors for Joint Test Assembly Flights, 102
- Walsh, T. F.
 Coupled Simulations of Weapons Systems, 239
- Walther, E. A.
 Automation of Microelectronic Physical Analysis, 592
 Immunological Basis for Systems Control, 409
- Wang, Y.
 Microsensors in Radioactive-Waste Management, 502
 Self-Assembled Materials in Waste Management, 466
- Wanke, M. C.
 Continuous-Wave Intersubband Terahertz Sources, 165
 Nonlethal Technologies for the War on Terrorism, 702
 Tagging for Tracking and Authentication of Documents, 577
- War, 702
- Warner, D. J.
 Enabling Technology for Human Collaboration, 718
- Warpinski, N. R.
 Autonomous Microexplosive Subsurface Tracing, 475
- Warrant, M. M.
 Terrorist-Activity Plan-Assessment Methodology, 714
- Warren, M. E.
 An Integrated, Stacked System-on-a-Chip, 183
 Arrayed Resonant Subwavelength Gratings, 562
 Tagging for Tracking and Authentication of Documents, 577
- Wasson, N. D.
 Validated Modeling of Distributed Energy Resources, 494
- Waste (nuclear)
 Microsensors, 502
 Self-assembled, 466
- Water
 Arsenic removal, 533
 Contamination, 519
 Desalination, 496
 Modeling (demand), 741
 Modeling (Rio Grande), 721
 Pathogens, 793
 Purification, 471
 Reactor safety, 922
 Real-time monitoring, 486
 Regulated chemicals, 491
 Splitting, 517
 Surety, 637
 Switches, 341
- Watson, J. P.
 Error-Control Codes for Engineered Regulatory Systems, 912
- Watterberg, P. A.
 Flexible Robotic Maintenance Facility, 373
- Watts, A. C.
 Aerospace Vehicle Trajectory Optimization System, 840
- Waveform, 552
- Weaklink, 801
- Weapon
 Automotive industry, 760
 Control strategies, 657
 Directed energy, 863
 Nuclear, 633
 Signatures, 659
 Simulations, 239
 Terrorist model, 716
 See also: Bioweapon
- Weatherby, J. R.
 Large-Deformation Solid-Fluid Interaction, 212
- Webb, D. B.
 Linear Magnetic Actuators, 35
- Webb, E. B., III
 Atomistic-Continuum Simulation, 218
- Wehlburg, C. M.
 MSI and HSI Imagery for Subpixel Spectral Unmixing, 649
- Weichman, L. S.
 Advanced Packaging Technology for Optical Firesets, 804
 Hard Target Defeat High-G-Tolerant Fuze, 407
 Microfuze, 380
- Weiland, L. A.
 Agent-Based Control of Infrastructure Resources, 539
- Welch, D. R.
 Magnetic-Field Effects on Vacuum-Arc Plasmas, 242
 Simulations of Intense Petawatt Laser Pulses, 336
- Welle, E. J.
 Hard Target Defeat High-G-Tolerant Fuze, 407
 Microfuze, 380
- Wendt, J. R.
 Active Photonic-Crystal Devices, 172
 A Revolution in Lighting, 671
 Arrayed Resonant Subwavelength Gratings, 562
 Compact Terahertz Sources, 418
 Completely Passive Microwave Tag, 610
 Dispersive Photonics for Sensors and Microsystems, 155
 Microoptical Gyroscope Via Optical Integration, 191
 Nanoelectromechanical Oscillators for RF Filtering, 162
 Zero-Power Radio Receiver, 608
- Wessendorf, K. O.
 Advanced Digital Detectors for Neutron Imaging, 546
 Micromass Spectrometer-on-a-Chip, 185
- West, J. A.
 Detection of Chimeric Bioweapons, 605
- Wetting
 Mysteries, 61
 Porous media, 762
- Whaley, J. A.
 Interfacial Bioscience Grand Challenge, 680
- Wheeler, D. R.
 Functionalized Nanoparticles for Sensor Applications, 176
 Micro Flame-Based Detector Suite, 437
 Sensors for Water-Contamination Events, 519
- Whinnery, L. L., Jr.
 Ultraclean Environments in Microsystem Packages, 246

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

- Wilcoxon, J. P.
 A Revolution in Lighting, 671
 Nanoscale Energetic Materials, 744
- Wilkes, E. D.
 Large-Deformation Solid-Fluid Interaction, 212
- Williams, C. V.
 Sandia Decon Formulation on the SARS Coronavirus, 543
- Williams, R. L.
 Adaptive and Mobile Ground Sensors, 365
 Near-Real-Time Characterization for HDBT Defeat, 693
 TALON, 690
- Williams, T. C.
 Soot Formation in Unsteady Diffusion Flames, 225
- Williamson, R. L.
 Processing of Field-Structured Composites, 271
- Wilson, C. W.
 Automated Visual Direction of Mobile Manipulation, 383
- Winters, S. T.
 PVDF as a Piezoelectric Film, 645
- Winters, W. S., Jr.
 Contaminant Transport in Architectural Spaces, 614
- Wireless
 Information assurance, 401
 Message routing, 118
 Surety enhancement, 504
- Witczak, S. C.
 Radiation Aging of Microelectronics, 210
- Witze, P. O.
 Diagnostics for Airborne Carbon Nanoparticles, 468
 Diesel Catalytic Particulate Traps, 499
- Witzke, E. L.
 Cryptographic Assurance of Execution Correctness, 642
 Surety for Wireless Automated-Control Networks, 504
- WMD (weapons of mass destruction)
 See Weapon
- Woessner, S. M.
 Nanoscale Energetic Materials, 744
- Wolfenbarger, P. R.
 Advanced Mobile Networking Using Graph Theory, 416
- Wong, C. C.
 Multiscale Thermal Modeling, 215
- Woodall, T. D.
 A Systems Approach to Defending Our Borders, 699
- Woodard, J. B.
 TALON, 690
- Woodcock, C. L.
 Surety and Accountability for Storage Containers, 798
- Wooden, S. M.
 Microfuze, 380
 Novel and Robust Environmental-Sensing Devices, 809
- Woodworth, J. R.
 Laser Triggering of Water Switches in Accelerators, 341
- Wright, A. F.
 A Revolution in Lighting, 671
 Efficiency of GaN HEMT High-Power Amplifiers, 193
- Wright, J. L.
 Monitoring of Volatile Contaminants, 463
- Wright, S. A.
 Gas Power-Conversion Systems for Nuclear Reactors, 522
- Wylie, B. N.
 Informatics for Systems Biology, 78
- ### X
- Xavier, P. G.
 A Robotic Framework for Semantic Concept Learning, 911
 Augmented Cognition, 687
 Improving Human/System Interactions, 425
 Robotic Planning for Physical-Security Analysis, 627
 Simulator Agents with Humanlike Episodic Memory, 359
 Sophisticated Agent Evolution and Optimization, 113
- X-ray
 Multikilovolt, 378
 Vehicle bombs, 655
- ### Y
- Yang, N. Y. C.
 LIGA Microsystems Aging: Evaluation and Mitigation, 268
- Yang, P.
 Microfabrication with Femtosecond-Laser Processing, 44
 Rapid-Prototyping High-Density Circuitry, 59
- Yang, Y.
 Biomimetic Chloroplasts, 83
 Self-Assembled Materials in Waste Management, 466
- Yarberry, V. R.
 Automation of Microelectronic Physical Analysis, 592
- Yarrington, P.
 Near-Real-Time Characterization for HDBT Defeat, 693
- Yee, A. A.
 Algorithm Architecture for Unattended Ground Sensors, 428
 Data Fusion and Visualization of MASINT Results, 355
- Yee, M. L.
 Data Fusion and Visualization of MASINT Results, 355
 Near-Real-Time Characterization for HDBT Defeat, 693
 Performance of MicroTalon SDAC Systems, 454
- Yelton, W. G.
 Carbon Adsorbers for Chemical Microsensors, 906
 Identification of Regulated Chemicals in Water, 491
- Yoder, J. R.
 TALON, 690
- Yonas, G.
 Building Conscious Machines, 734
- York, D. L.
 Nuclear Process Transparency and Control, 509
- Yoshimura, A. S.
 Communication in Counterterrorism Crisis Management, 420
 Robust Message Routing for Mobile *Ad Hoc* Networks, 118
 Stochastic Programming for Enterprise Modeling, 115
- Youchison, D. L.
 High-Efficiency Turbine Blade Coatings, 483
- Young, M. F.
 Advanced Nuclear Engineering Analysis Technology, 506
 Gas Power-Conversion Systems for Nuclear Reactors, 522

Author and Title Index

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

Young, M. M.

Interfacial Bioscience Grand Challenge, 680

Membrane Protein Interactions in Cell Signaling, 75

Young, W. F.

Secure MPLS Control Plane for Internet Connectivity, 597

Surety for Wireless Automated-Control Networks, 504

Yu, K.

Self-Assembled Materials in Waste Management, 466

Z

Zavadil, K. R.

Biomicrofuel Cell, 685

Critical Length Scales for Corrosion Processes, 265

Microminiature Thermionic Converter, 473

Quantification of Environments Within Micropackages, 309

Zeigler, D. A.

Modeling Ductile Fracture, 207

Zender, G. L.

Icosahedral Boride Semiconductor Beta Cell, 580

Zero-gravity, 254

Zero-power, 608

Zhang, Z.

Immune Responses to Bioterrorism Threats, 93

Zifer, T.

Decomposition of Contaminants Using Nanoparticles, 303

Thermally Cleavable Surfactants, 305

Zimmerman, J. A.

Atomistic-Continuum Simulation, 218

Z-pinch

Laser, 336

Power plant, 324

Recyclable transmission line, 327

Zubrzycki, W. J.

Dispersive Photonics for Sensors and Microsystems, 155

Microoptical Gyroscope Via Optical Integration, 191

Zutavern, F. J.

Compact Terahertz Sources, 418

Remote Mapping of Electromagnetic Fields, 399

Sensing of Phase Transformations in Steels, 48

Solid-State Switch for Advanced Pulsed Power, 332