Phase II Groundwater Flow Model of Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nye County, Nevada

Revision No.: 0

May 2006

Prepared for U.S. Department of Energy under Contract No. DE-AC52-03NA99205.

Approved for public release; further dissemination unlimited.

Available for public sale, in paper, from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Phone: 800.553.6847
Fax: 703.605.6900
Email: orders@ntis.gov
Online ordering: <http://www.ntis.gov/ordering.htm>

Available electronically at <http://www.osti.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors,
in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
Phone: 865.576.8401
Fax: 865.576.5728
Email: reports@adonis.osti.gov

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

PHASE II GROUNDWATER FLOW MODEL OF CORRECTIVE ACTION UNIT 98: FRENCHMAN FLAT, NEVADA TEST SITE, NYE COUNTY, NEVADA

Contributors:

Stoller-Navarro Joint Venture

Nicole DeNovio

Greg Ruskauff

Alaa Aly

John Pickens

John Ewing

William Fryer

Toya Jones

Irene Farnham

Los Alamos National Laboratory

Edward Kwicklis

Carl W. Gable

Revision No.: 0

May 2006

Stoller-Navarro Joint Venture
7710 W. Cheyenne, Building 3
Las Vegas, NV 89129

**PHASE II GROUNDWATER FLOW MODEL OF CORRECTIVE ACTION UNIT 98:
FRENCHMAN FLAT, NEVADA TEST SITE, NYE COUNTY, NEVADA**

Approved by:

John McCord, UGTA Project Manager
Stoller-Navarro Joint Venture

Date:

Acknowledgements

This document greatly benefitted from the efforts of the following individuals:

- Barb Deshler, Christie Miller, Holly Hoenes, and Janice Rose along with the document production staff (John Flinn, Ellen Cook, and Christy Morris) for their support in preparing this document for publication.
- Keely Brooks and Tad Beard for EarthVision® support and Nathan Bryant for GIS support, and also for their support in preparing the numerous figures within this document.
- Sylvan Hersh for the many hours spent on quality assurance.
- Sig Drellack for providing geologic advice and guidance during model construction, calibration, and analysis.
- Brian Dunlap for his assistance in completing the particle track analyses.
- Bruce Crowe for the thoughtful conversations and text suggestions.
- The numerous reviewers of this document.

TABLE OF CONTENTS

List of Figures.....	vi
List of Tables	xix
List of Plates.....	xxii
List of Acronyms and Abbreviations	xxiii
List of Symbols for Elements and Compounds	xxvii
List of Stratigraphic Unit Abbreviations and Symbols.....	xxviii
Executive Summary	ES-1
 1.0 Introduction.....	 1-1
1.1 Purpose and Scope	1-1
1.2 Project Participants	1-4
1.3 Summary of the Federal Facility Agreement and Consent Order	1-4
1.4 Frenchman Flat Background.....	1-5
1.5 Summary of Phase I Frenchman Flat CAI Documentation	1-9
1.6 Major Documents Supporting the Phase II Frenchman Flat Flow Model	1-12
1.7 Report Organization	1-17
 2.0 Previous work	 2-1
2.1 Regional Models.....	2-3
2.1.1 Underground Test Area Regional Groundwater Flow Model	2-3
2.1.1.1 Regional Hydrogeologic Framework	2-3
2.1.1.2 Groundwater Occurrence and Movement	2-5
2.1.2 U.S. Geological Survey Death Valley Regional Ground-Water Flow System Model.....	2-8
2.2 Recharge Models	2-10
2.2.1 U.S. Geological Survey Recharge Model.....	2-10
2.2.2 Desert Research Institute Chloride Mass Balance Model	2-11
2.2.3 Underground Test Area Modified Maxey-Eakin Recharge Models ..	2-12
2.3 CAU Models.....	2-22
2.3.1 Phase I Frenchman Flat CAU Model.....	2-22
2.3.1.1 Phase I Frenchman Flat Hydrostratigraphic Framework Model	2-22
2.3.1.2 Conceptual Models of Groundwater Flow for the Phase I CAU Flow Model	2-24
2.3.1.3 Phase I CAU Flow and Transport Model Results	2-25
2.3.2 Desert Research Institute Geochemistry Model.....	2-25
2.3.3 Phase II Hydrostratigraphic Framework Model.....	2-28
2.3.3.1 BASE Hydrostratigraphic Framework Model	2-29
2.3.3.2 Basalt Lava Flow Aquifer (BLFA) HFM Alternative - Alternative Model #1	2-36
2.3.3.3 Detachment Fault (DETA) HFM Alternative - Alternative Model #2	2-37

TABLE OF CONTENTS (CONTINUED)

2.3.3.4	Displacement Fault (DISP) HFM Alternative - Alternative Model #3	2-37
2.3.3.5	CP Basin (CPBA) HFM Alternative - Alternative Model #4	2-38
2.4	Summary	2-38
3.0	Data and Conceptual Models	3-1
3.1	Geologic Setting	3-3
3.2	Precipitation and Recharge	3-4
3.3	Groundwater Discharge	3-5
3.4	Inflow and Outflow (Lateral Boundary Flows and Boundary Heads)	3-7
3.5	Hydraulic Heads	3-10
3.5.1	Horizontal Head Gradients	3-14
3.5.1.1	Alluvial Aquifer and Older Alluvial Aquifer	3-14
3.5.1.2	Volcanic Aquifers	3-15
3.5.1.3	Lower Carbonate Aquifer	3-15
3.5.2	Vertical Gradients	3-19
3.5.2.1	ER-5-3 Well Cluster	3-19
3.5.2.2	ER-5-4 Well Cluster	3-19
3.6	Hydraulic Properties	3-22
3.6.1	HSU Permeability Data	3-23
3.6.2	Vertical Permeability Anisotropy for Alluvium and other Units	3-24
3.6.2.1	Evidence from Borehole Flow Logs and Core Samples	3-31
3.6.2.1.1	Flow Logs	3-31
3.6.2.1.2	Core Samples	3-32
3.6.2.2	Interpretations from Frenchman Flat Multiple- Well Aquifer Tests	3-32
3.6.2.3	Evidence for Alluvial Anisotropy from Groundwater Models	3-33
3.6.2.3.1	Frenchman Flat Models	3-33
3.6.2.3.2	Regional NTS Models	3-34
3.6.2.3.3	Other Basin-Scale Regional Models	3-34
3.6.2.3.4	Anisotropy Summary	3-35
3.6.3	Permeability Depth Decay	3-36
3.6.3.1	Evidence for Depth Decay in Alluvial Permeability from Well ER-5-4 Flow Logs	3-39
3.6.3.2	The Relation Between Anisotropy and Depth Decay	3-41
3.6.4	Fault Properties	3-43
3.6.4.1	Basin-Fill Faults	3-43
3.6.4.2	Faults in Consolidated Rocks	3-48
3.7	Conceptual Flow Model Summary	3-51
4.0	Groundwater Flow Model Construction	4-1

TABLE OF CONTENTS (CONTINUED)

4.1	General Approach	4-1
4.2	Model Area	4-2
4.3	Mesh Generation	4-3
4.3.1	Mesh Refinement Criteria	4-3
4.3.2	Mesh Requirements for FEHM Streamline Particle Tracking	4-5
4.3.3	Input for Grid Generation	4-8
4.3.3.1	Water-Table Definition	4-12
4.3.3.2	Breakthrough Planes, Test Cavities, and Well Intervals	4-13
4.3.4	Selective Grid Refinement	4-15
4.3.5	Feature of Interest Refinement Criteria	4-17
4.3.6	Grid Output	4-19
4.4	Material Properties	4-27
4.4.1	Hydrostratigraphic Unit Permeability	4-27
4.4.2	Fault Permeability	4-28
4.5	Boundary Conditions	4-29
4.5.1	Recharge	4-29
4.5.2	Boundary Heads	4-30
5.0	Flow Model Calibration	5-1
5.1	Calibration Approach for the Frenchman Flat CAU Groundwater Flow Model	5-2
5.2	Calibration Data	5-9
5.3	Boundary Head Adjustments	5-12
5.4	Parameter Assignment	5-15
5.5	Calibration of the BASE-USGSD Flow Model	5-16
5.5.1	Initial Parameter Adjustments	5-17
5.5.2	Simulated Hydraulic Heads for the BASE-USGSD Model	5-19
5.5.3	Hydraulic Head and Flux Residuals	5-26
5.5.4	Estimated Hydraulic Parameters	5-32
5.5.5	Estimated Groundwater Flow Paths	5-48
5.6	Model Limitations	5-50
5.7	Summary	5-52
6.0	Conceptual Model Uncertainty Analyses	6-1
6.1	Background	6-1
6.2	Introduction	6-3
6.3	HFM Uncertainty Analysis	6-4
6.3.1	Alternative HFM Calibration Approach	6-4
6.3.2	Basalt Lava Flow Aquifer (BLFA) Flow Model Calibration	6-9
6.3.3	Detachment Fault (DETA) Alternative Flow Model Calibration	6-12
6.3.4	Aquifer Displacement (DISP) Alternative Flow Model Calibration	6-15
6.3.5	CP Basin Alternative Calibration	6-24
6.3.5.1	Calibration Strategy	6-24

TABLE OF CONTENTS (CONTINUED)

	6.3.5.2	CPBA-USGSD Simulated Hydraulic Heads	6-25
	6.3.5.3	CPBA-USGSD Hydraulic Head and Flux Residuals . . .	6-30
	6.3.5.4	CPBA-USGSD Estimated Hydraulic Parameters	6-35
	6.3.5.5	Calculated Groundwater Flow Paths for the CPBA-USGSD Alternative	6-48
	6.3.6	Summary of Hydrostratigraphic Framework Model Conceptual Model Uncertainty Analysis.	6-50
6.4		Discrete Uncertainty Analysis	6-51
	6.4.1	Northern Testing Area Travel Pathways	6-52
	6.4.2	Central Testing Area Travel Pathways.	6-59
	6.4.3	Summary of Discrete Model Uncertainty Analysis	6-64
6.5		Boundary Conditions Uncertainty Analyses.	6-64
	6.5.1	BASE HFM with Chloride Mass-Balance (DRIA) Boundary Conditions (BASE-DRIA).	6-73
	6.5.2	BASE HFM with Modified Maxey-Eakin (MME) Boundary Conditions (BASE-MME).	6-80
	6.5.3	BASE HFM with Death Valley Regional Flow System (DVRFS) Model Boundary Conditions (BASE-DVRFS)	6-87
	6.5.4	CPBA Hydrostratigraphic Framework Model with Chloride Mass-Balance (DRIA) Boundary Conditions (CPBA-DRIA).	6-94
	6.5.5	CPBA HFM with Modified Maxey-Eakin (MME) Boundary Conditions (CPBA-MME).	6-101
	6.5.6	CPBA HFM with Death Valley Regional Flow System (DVRFS) Model Boundary Conditions (CPBA-DVRFS)	6-108
	6.5.7	Alternative Approach To Boundary Head Adjustments	6-115
	6.5.7.1	Boundary Head Adjustments	6-115
	6.5.7.2	Simulated Hydraulic Heads for the Alternative BASE-USGSD Flow Model	6-118
	6.5.7.3	Hydraulic Head and Flux Residuals	6-122
	6.5.7.4	Estimated Hydraulic Parameters	6-128
	6.5.7.5	Estimated Groundwater Flow Paths	6-142
	6.5.8	Summary of Model Boundary Condition Uncertainty Analysis . . .	6-144
6.6		Constant Permeability with Depth Uncertainty Analysis	6-146
	6.6.1	Calibration Approach	6-147
	6.6.1.1	Simulated Hydraulic Heads for the BASE-USGSD with No Depth Decay in the AA and OAA Flow Model	6-148
	6.6.1.2	Hydraulic Head and Flux Residuals	6-153
	6.6.1.3	Estimated Hydraulic Parameters	6-159
	6.6.1.4	Estimated Groundwater Flow Paths	6-172
	6.6.2	Summary of Constant Permeability with Depth Uncertainty Analysis	6-174
7.0		Parameter Sensitivity Analysis	7-1

TABLE OF CONTENTS (CONTINUED)

7.1	Parameter Sensitivity Analysis	7-2
7.1.1	Results	7-3
7.2	Parameter Perturbation Analysis	7-8
7.2.1	BASE Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (BASE-USGSD) Model	7-10
7.2.2	BASE Hydrostratigraphic Framework Model and Death Valley Regional Ground-Water Flow System Recharge and Boundary Heads (BASE-DVRFS)	7-22
7.2.3	BLFA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (BLFA-USGSD) Model	7-25
7.2.4	DETA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (DETA-USGSD) Model	7-27
7.2.5	CPBA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (CPBA-USGSD) Model	7-27
7.2.6	Summary of Parameter Sensitivity Analysis	7-38
8.0	Evaluation of Groundwater Flow Paths and Travel Times in Frenchman Flat Using ^{14}C and Other Geochemical Indicators	8-1
8.1	Hydrogeologic Setting	8-2
8.2	Groundwater Carbon-Isotope Data	8-4
8.3	Approach to Correcting Groundwater ^{14}C Ages	8-9
8.4	Corrections to Groundwater ^{14}C Ages in Frenchman Flat	8-10
8.5	Comparison of DI^{14}C and DO^{14}C Groundwater Ages	8-13
8.5.1	Evaluation of Groundwater DO^{14}C and DI^{14}C Ages Using ^{36}Cl Data	8-16
8.5.2	Estimation of the Original Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratio at Wells Affected by Halite Dissolution	8-20
8.5.3	Estimation of Groundwater Age Based on Groundwater Evolutionary Trends	8-22
8.6	Evaluation of Groundwater Ages Using Deuterium and Oxygen-18	8-25
8.7	Estimation of Groundwater Flow Paths and Travel Times with PHREEQC	8-30
8.7.1	Groundwater Flow from Well UE-5 PW-2 to Well UE-5 PW-1	8-31
8.7.2	Groundwater Flow from Wells UE-5c WW and UE-5 PW-1 to Well ER-5-4	8-31
8.7.3	Groundwater Flow to Well ER-5-4#2	8-35
8.8	Groundwater Velocities	8-37
8.9	Summary and Conclusions	8-42
9.0	Summary and Conclusions	9-1
10.0	References	10-1

TABLE OF CONTENTS (CONTINUED)

Appendix A - Analysis of New Water-Level and Ground-Surface Elevation Measurements for Frenchman Flat Relative to the Phase II Frenchman Flat Hydrologic Data Document

A.1.0	Analysis of New Water-Level and Ground-Surface Elevation Measurements for Frenchman Flat Relative to the Phase II Frenchman Flat Hydrologic Data Document .	A-1
A.2.0	References.	A-20

Appendix B - Literature Review and Technical Basis for Permeability Depth Decay

B.1.0	Literature Review and Technical Basis for Permeability Depth Decay	B-1
B.2.0	References.	B-18

Appendix C - Perturbation Sensitivity Analysis Plots

C.1.0	Introduction.	C-1
C.2.0	Data Presentation	C-1
C.3.0	Access to Data	C-2
C.3.1	BASE HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model	C-2
C.3.2	BASE HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model, Fault Permeability Multiplier in Z Direction Only.	C-2
C.3.3	BASE HFM with Calibrated USGS with Redistribution Recharge and Boundary Heads, DVRFS Model	C-2
C.3.4	CPBA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model	C-3
C.3.5	CPBA HFM with Calibrated USGS with Redistribution Recharge and Boundary Heads, DVRFS Model	C-3
C.3.6	DETA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model	C-3
C.3.7	BLFA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model	C-4

Appendix D - Fault Locations

Appendix E - Saturated Media Hydraulic Properties

E.1.0	Saturated Media Hydraulic Properties	E-1
E.1.1	Objectives	E-2
E.1.2	Data Types and Prioritization	E-2
E.1.3	Data Compilation and Evaluation.	E-3

TABLE OF CONTENTS (CONTINUED)

E.1.3.1	Data Sources	E-3
E.1.3.2	Supporting Data	E-4
E.1.3.3	Data Quality Assurance	E-5
E.1.3.4	Data Transferability	E-5
E.1.4	Hydraulic Parameters	E-6
E.1.4.1	Scales of Test Data and Applicability	E-7
E.1.4.2	Test Analyses and Associated Uncertainties	E-9
E.1.4.3	Handling of Multiple Test Results for One Well	E-9
E.1.5	Analysis of Hydraulic Conductivity Data.	E-10
E.1.5.1	Methodology.	E-12
E.1.5.2	Kolmogorov-Smirnov Test for Log Normality	E-13
E.1.5.3	Spatial Distribution of Data	E-14
E.1.6	Analysis Results	E-15
E.1.7	Hydraulic Conductivity Analysis	E-15
E.1.8	Depth Dependence of Hydraulic Conductivity Analysis	E-18
E.1.9	Hydrogeologic Unit-Specific Hydraulic Conductivity Analyses	E-19
E.1.9.1	Alluvial Aquifer Hydrogeologic Unit	E-20
E.1.9.2	Volcanic Aquifer Hydrogeologic Unit.	E-22
E.1.9.3	Lava Flow Aquifer Hydrogeologic Unit	E-22
E.1.9.4	Tuff Confining Unit Hydrogeologic Unit.	E-24
E.1.9.5	Lower Carbonate Aquifer Hydrogeologic Unit	E-24
E.1.10	Test-Scale and Spatial Variability	E-28
E.1.11	Aquifer Unit Versus Confining Unit Results.	E-30
E.1.12	Aquifer Storage Properties.	E-30
E.1.13	Anisotropy	E-31
E.1.14	Limitations.	E-33
E.2.0	References.	E-36

LIST OF FIGURES

<i>NUMBER</i>	<i>TITLE</i>	<i>PAGE</i>
1-1	Location of the Frenchman Flat Model Area	1-3
1-2	Process Flow Diagram for the Underground Test Area Corrective Action Units	1-6
1-3	Frenchman Flat Model Area Showing Wells Used in Calibration of the Flow Model and Test Locations	1-7
1-4	Features of the UGTA Regional Groundwater Flow System	1-8
1-5	Location of Underground Nuclear Tests in Frenchman Flat	1-10
2-1	Information Flow into the Frenchman Flat Groundwater Flow Model	2-2
2-2	USGS Recharge Distribution with Overland Flow (USGSD)	2-13
2-3	USGS Recharge Distribution without Overland Flow (USGSND)	2-14
2-4	DVRFS Model Recharge Distribution	2-15
2-5	DRI Recharge Distribution with Alluvial Mask (DRIA)	2-16
2-6	DRI Recharge Distribution with Alluvial and Elevation Mask (DRIAE)	2-17
2-7	DRI Recharge Distribution with Alluvial Mask (DRIA) - Revised Scale	2-18
2-8	DRI Recharge Distribution with Alluvial and Elevation Mask (DRIAE) - Revised Scale	2-19
2-9	Original UGTA Modified Maxey-Eakin (MME) Recharge Model	2-20
2-10	Revised UGTA Modified Maxey-Eakin (MME-revised) Recharge Model	2-21
2-11	Hydrostratigraphic Unit Surface Map of the Frenchman Flat Model Area	2-30
2-12	Three-Dimensional View of the BASE Hydrostratigraphic Framework Model of the Frenchman Flat Area (BN, 2005a)	2-31
2-13	Three-Dimensional Image of Major Fault Structures	2-32
3-1	Location of Groundwater Pumping Wells in the Frenchman Flat Area and Vicinity .	3-6
3-2	Total Water Withdrawal from Wells in the Frenchman Flat Area and Vicinity	3-7

LIST OF FIGURES (CONTINUED)

<i>NUMBER</i>	<i>TITLE</i>	<i>PAGE</i>
3-3	Location of Wells (with Completion Interval HSUs Identified) in the Frenchman Flat Area and Vicinity	3-13
3-4	Alluvial Aquifer Well Locations and Steady-State Heads	3-16
3-5	Volcanic Aquifer and Confining Unit Well Locations and Steady-State Heads	3-17
3-6	Lower Carbonate Aquifer Well Locations and Steady-State Heads	3-18
3-7	Profile of Hydraulic Heads at the ER-5-3 Well Cluster	3-20
3-8	Profile of Hydraulic Heads at the ER-5-4 Well Cluster	3-21
3-9	Frenchman Flat Hydraulic Property Data Locations	3-25
3-10	Permeability Data for the AA HGU from the NTS and Frenchman Flat Areas	3-27
3-11	Permeability Data for the VA HGU from the NTS and Frenchman Flat Areas	3-27
3-12	Permeability Data for the TCU HGU from the NTS and Frenchman Flat Areas . . .	3-28
3-13	Permeability Data for the CCU HGUs from the NTS Areas	3-28
3-14	Permeability Data for the CA HGU from the NTS and Frenchman Flat Areas	3-29
3-15	Normalized Flow Log Data from Well ER-5-4	3-39
3-16	Match of Depth-Integrated Transmissivity Model to Normalized Flow Log Data from Well ER-5-4	3-41
3-17	Effective Anisotropy as a Function of Alluvial Thickness	3-43
3-18	Anisotropy Induced by Depth Decay for 100-m Intervals between the water table (200 m) and a Total Alluvial Thickness of 1,500 m	3-44
3-19	West-to-East and Northeast-to-Southwest Hydrostratigraphic Cross Sections Through the Frenchman Flat Area	3-47
4-1	Relationship Between Grid Refinement Levels, the Resulting Finite Element Mesh, and Computational Control Volumes	4-4
4-2	Effect of Grid Refinement on Material Continuity	4-7

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
4-3	Examples of What Occurs When a Regular Grid, (1,j), Is Truncated and Cells Above a Particular Elevation Are Removed	4-11
4-4	Expanded Views of 73 Fault Surfaces Converted to a Triangulation	4-12
4-5	Representation of the Water Table Used To Truncate the Top of the Model	4-14
4-6	Map View of the Model Area at an Elevation of 725 m Showing Multiple Levels of Refinement	4-20
4-7	Tetrahedral Grid at 3X Vertical Exaggeration Showing Only Faults	4-21
4-8	West-East Cross Section 12 km North of the South Boundary of the Model Showing Two HFMs	4-23
4-9	Example of Mesh Refinement Around Underground Nuclear Test Locations, Northern Testing Area	4-25
5-1	General Modeling Protocol	5-4
5-2	Histogram of Calibration Weights	5-12
5-3	Boundary Heads Used with the Calibrated BASE-USGSD Flow Model	5-14
5-4	Water-Table Contours for the Calibrated BASE-USGSD Model	5-21
5-5	West-East Cross Section of Simulated Heads at the Northern Testing Area for the BASE-USGSD Model	5-22
5-6	West-East Cross Section of Simulated Heads at the Central Testing Area for the BASE-USGSD Model	5-23
5-7	Comparison Between Hydraulic Heads Simulated with BASE-USGSD Flow Model and the Calibration Target Heads at the ER-5-3 Well Complex.	5-24
5-8	Comparison Between Hydraulic Heads Simulated with BASE-USGSD Flow Model and the Calibration Target Heads at the ER-5-4 Well Complex.	5-25
5-9	Groundwater Fluxes Simulated by the UGTA Regional Model and the BASE-USGSD Flow Model.	5-29
5-10	Observed Versus Simulated Well Head - BASE-USGSD Flow Model.	5-30

LIST OF FIGURES (CONTINUED)

<i>NUMBER</i>	<i>TITLE</i>	<i>PAGE</i>
5-11	Spatial Distribution of Weighted Residuals for the BASE-USGSD Model.	5-31
5-12	Residual Histogram BASE-USGSD Flow Model	5-32
5-13	Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of AA.	5-40
5-14	Calibrated Permeability in the BASE-USGSD Alternative Versus Measured Permeability of the LCA	5-41
5-15	Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of Confining HSUs	5-42
5-16	Calibrated Permeability in the BASE-USGSD Alternative Versus Measured Permeability of Volcanic Aquifers.	5-43
5-17	Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of the CCU	5-44
5-18	Calibrated Intrinsic Permeability at the Water Table for the BASE-USGSD Model	5-45
5-19	West-East Cross Section of Calibrated Intrinsic Permeability at the Central Testing Area for the BASE-USGSD Model.	5-46
5-20	West-East Cross Section of Calibrated Intrinsic Permeability at the Northern Testing Area for the BASE-USGSD Model.	5-47
5-21	Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model	5-49
6-1	Observed Versus Simulated Well Head - BLFA-USGSD Alternative	6-10
6-2	Particle Tracks Starting Near the Underground Nuclear Tests for the BLFA-USGSD Alternative.	6-11
6-3	Observed Versus Simulated Well Head - DETA-USGSD Alternative	6-13
6-4	Particle Tracks Starting Near the Underground Nuclear Tests for the DETA-USGSD Alternative	6-14
6-5	Observed Versus Simulated Well Head - DISP-USGSD Alternative with Calibrated Parameters from the BASE-USGSD Model.	6-18

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-6	Cross Section of Calibrated Intrinsic Permeability for the DISP-USGSD Alternative at the Aquifer Juxtaposition Interface	6-19
6-7	Observed Versus Simulated Well Head - Calibrated DISP-USGSD Alternative . . .	6-20
6-8	Spatial Distribution of Weighted Residuals for the DISP-USGSD Alternative. . . .	6-21
6-9	Residual Histogram DISP-USGSD Alternative	6-22
6-10	Particle Tracks Starting Near the Underground Nuclear Tests for the DISP-USGSD Alternative	6-23
6-11	Water-Table Contours for the Calibrated CPBA-USGSD Alternative	6-26
6-12	West-East Cross Section of Simulated Heads at the Northern Testing Area for the CPBA-USGSD Alternative.	6-27
6-13	West-East Cross Section of Simulated Heads at the Central Testing Area for the CPBA-USGSD Alternative.	6-28
6-14	Calibrated Boundary Heads for the CPBA-USGSD Alternative	6-29
6-15	Groundwater Fluxes Simulated by the UGTA Regional Model and the Frenchman Flat CPBA-USGSD Alternative	6-32
6-16	Observed Versus Simulated Well Head - CPBA-USGSD Alternative	6-33
6-17	Spatial Distribution of Weighted Residuals for the CPBA-USGSD Alternative. . .	6-34
6-18	Residual Histogram CPBA-USGSD Alternative	6-35
6-19	Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of AA.	6-40
6-20	Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of the LCA	6-41
6-21	Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of Confining HSUs.	6-42
6-22	Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of Volcanic Aquifers	6-43

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-23	Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of the UCCU	6-44
6-24	Calibrated Intrinsic Permeability at the Water Table in the CPBA-USGSD Alternative	6-45
6-25	West-East Cross Section of Calibrated Intrinsic Permeability in the CPBA-USGSD Alternative through the Northern Testing Area	6-46
6-26	West-East Cross Section of Calibrated Intrinsic Permeability in the CPBA-USGSD Alternative at the Central Testing Area	6-47
6-27	Particle Tracks Starting Near the Underground Nuclear Tests for the CPBA-USGSD Alternative.	6-49
6-28	Observed Versus Simulated Well Head - BASE-USGSD Model with Fault 35 Permeability Multiplier at 10^9	6-55
6-29	Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model with Fault 35 Permeability Multiplier at 10^9	6-56
6-30	Observed Versus Simulated Well Head - BLFA-USGSD Model with BLFA Permeability Increased by 10^4	6-57
6-31	Particle Tracks Starting Near the Underground Nuclear Tests - BLFA-USGSD with BLFA HSU Reference Permeability Increased by 10^4	6-58
6-32	Observed Versus Simulated Well Head - BASE-USGSD Model with Fault 38 Permeability Multiplier at 20,000	6-60
6-33	Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model with Fault 38 Permeability Multiplier at 20,000	6-61
6-34	Observed Versus Simulated Well Head - BASE-USGSD Model with Fault 38 Vertical Fault Permeability Multiplier at 10^5	6-62
6-35	Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model with Fault 38 Vertical Fault Permeability Multiplier at 10^5	6-63
6-36	Groundwater Fluxes Simulated by the UGTA Regional Model and the Frenchman Flat Model - BASE-DRIA Alternative	6-75
6-37	Observed Versus Simulated Well Head - BASE-DRIA Alternative	6-76

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-38	Boundary Heads from Calibrated BASE-DRIA Alternative	6-77
6-39	Spatial Distribution of Weighted Residuals for the BASE-DRIA Alternative	6-78
6-40	Particle Tracks Starting Near the Underground Nuclear Tests for the BASE-DRIA Alternative	6-79
6-41	Groundwater Fluxes Simulated by the UGTA Regional Model and the BASE-MME Alternative	6-82
6-42	Observed Versus Simulated Well Head - BASE-MME Alternative	6-83
6-43	Boundary Heads from Calibrated BASE-MME Alternative	6-84
6-44	Spatial Distribution of Weighted Residuals for the BASE-MME Alternative.	6-85
6-45	Particle Tracks Starting Near the Underground Nuclear Tests for the BASE-MME Alternative	6-86
6-46	Groundwater Fluxes Simulated by the DVRFS Regional Model and BASE-DVRFS Alternative.	6-89
6-47	Observed Versus Simulated Well Head - BASE-DVRFS Alternative	6-90
6-48	Boundary Heads from Calibrated BASE-DVRFS Alternative	6-91
6-49	Spatial Distribution of Weighted Residuals for the BASE-DVRFS Alternative	6-92
6-50	Particle Tracks Starting Near the Underground Nuclear Tests for the BASE-DVRFS Alternative	6-93
6-51	Groundwater Fluxes Simulated by the UGTA Regional Model and the Frenchman Flat Model - CPBA-DRIA Alternative	6-96
6-52	Observed Versus Simulated Well Head - CPBA-DRIA Alternative	6-97
6-53	Boundary Heads from Calibrated CPBA-DRIA Alternative	6-98
6-54	Spatial Distribution of Weighted Residuals for the CPBA-DRIA Alternative	6-99
6-55	Particle Tracks Starting Near the Underground Nuclear Tests for the CPBA-DRIA Alternative	6-100

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-56	Groundwater Fluxes Simulated by the UGTA Regional Model and the Frenchman Flat Model - CPBA-MME Alternative	6-103
6-57	Observed Versus Simulated Well Head - CPBA-MME Alternative	6-104
6-58	Boundary Heads from Calibrated CPBA-MME Alternative	6-105
6-59	Spatial Distribution of Weighted Residuals for the CPBA-MME Alternative	6-106
6-60	Particle Tracks Starting Near the Underground Nuclear Tests for the CPBA-MME Alternative	6-107
6-61	Groundwater Fluxes Simulated by the DVRFS Regional Model and the Frenchman Flat Model - CPBA-DVRFS Alternative	6-110
6-62	Observed Versus Simulated Well Head - CPBA-DVRFS Alternative	6-111
6-63	Boundary Heads from Calibrated CPBA-DVRFS Alternative	6-112
6-64	Spatial Distribution of Weighted Residuals for the CPBA-DVRFS Alternative . . .	6-113
6-65	Particle Tracks Starting Near the Underground Nuclear Tests for the CPBA-DVRFS Alternative	6-114
6-66	Boundary Heads Used with the Alternative Calibration of the BASE-USGSD Flow Model	6-117
6-67	Water-Table Contours for the Alternative Calibration of the BASE-USGSD Model	6-119
6-68	West-East Cross Section of Simulated Heads at the Northern Testing Area for the Alternative Calibration of the BASE-USGSD Model	6-120
6-69	West-East Cross Section of Simulated Heads at the Central Testing Area for the Alternative Calibration of the BASE-USGSD Model	6-121
6-70	Groundwater Fluxes Simulated by the UGTA Regional Model and the Alternative Calibration of the BASE-USGSD Flow Model	6-124
6-71	Observed Versus Simulated Well Head - Alternative Calibration of BASE-USGSD Flow Model	6-125

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-72	Spatial Distribution of Weighted Residuals for the Alternative BASE-USGSD Model Calibration	6-126
6-73	Residual Histogram Alternative Calibration of the BASE-USGSD Flow Model . .	6-127
6-74	Estimated Versus Measured Intrinsic Permeability of AA for the Alternative Calibration of the BASE-USGSD Model	6-135
6-75	Estimated Versus Measured Intrinsic Permeability of the LCA for the Alternative Calibration of the BASE-USGSD Model	6-136
6-76	Estimated Versus Measured Intrinsic Permeability of Aquitard HSUs for the Alternative Calibration of the BASE-USGSD Model	6-137
6-77	Estimated Versus Measured Intrinsic Permeability of VAs for the Alternative Calibration of the BASE-USGSD Model	6-138
6-78	Calibrated Permeability at the Water Table for the Alternative Calibration of the BASE-USGSD Model	6-139
6-79	West-East Section of Calibrated Permeability at the Central Testing Area for the Alternative Calibration of the BASE-USGSD Model	6-140
6-80	West-East Cross Section of Calibrated Permeability at the Northern Testing Area for the Alternative Calibration of the BASE-USGSD Model	6-141
6-81	Particle Tracks Starting Near the Underground Nuclear Tests for the Alternative Calibration of the BASE-USGSD Model	6-143
6-82	Water-Table Contours for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA	6-150
6-83	West-East Cross Section of Simulated Heads at the Northern Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-151
6-84	West-East Cross Section of Simulated Heads at the Central Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-152
6-85	Groundwater Fluxes Simulated by the UGTA Regional Model and the Calibration of the BASE-USGSD Flow Model with No Permeability Depth Decay in the AA and OAA	6-155

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
6-86	Observed Versus Simulated Well Head - Calibration of the BASE-USGSD Flow Model with No Permeability Depth Decay in the AA and OAA	6-156
6-87	Spatial Distribution of Weighted Residuals for the BASE-USGSD Model Calibration with No Permeability Depth Decay in the AA and OAA	6-157
6-88	Residual Histogram Calibration for the BASE-USGSD Flow Model with No Permeability Depth Decay in the AA and OAA.	6-158
6-89	Estimated Versus Measured Intrinsic Permeability of AA for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-165
6-90	Estimated Versus Measured Intrinsic Permeability of the LCA for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-166
6-91	Estimated Versus Measured Intrinsic Permeability of Aquitard HSUs for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-167
6-92	Estimated Versus Measured Intrinsic Permeability of VAs for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-168
6-93	Calibrated Permeability at the Water Table for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA.	6-169
6-94	West-East Section of Calibrated Permeability at the Central Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA . .	6-170
6-95	West-East Cross Section of Calibrated Permeability at the Northern Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA.	6-171
6-96	Particle Tracks Starting Near the Underground Nuclear Tests for the BASE-USGSD Model with no Permeability Depth Decay in the AA and OAA . .	6-173
7-1	PEST Parameter Correlations Greater than 0.9 for the 13 Frenchman Flat CAU BASE-USGSD Model Parameters	7-5
7-2	Composite Observation Sensitivity from PEST for the BASE-USGSD Frenchman Flat Flow Model	7-7
7-3	FLUX Perturbation Plot for BASE-USGSD Model HSU Reference Permeability . .	7-11
7-4	WELL Perturbation Plot for BASE-USGSD HSU Reference Permeability	7-12

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
7-5	Mean Head Difference for AA Water Table from HSU Reference Permeability Perturbation of BASE-USGSD Model	7-13
7-6	WELL Perturbation Plot for Depth-Decay Coefficients for BASE-USGSD Model .	7-15
7-7	Mean Head Difference for AA from Depth-Decay Coefficient Perturbation of BASE-USGSD Model	7-16
7-8	FLUX Perturbation Plot for Rock Valley Fault Permeability Multipliers of BASE-USGSD Model	7-17
7-9	WELL Perturbation Plot for Rock Valley Fault Permeability Multipliers for BASE-USGSD Model	7-18
7-10	WELL Perturbation Plot for Cane Spring Fault Permeability Multipliers for BASE-USGSD Model	7-19
7-11	WELL Perturbation Plot for Other Basin-Forming Fault Permeability Multipliers for BASE-USGSD Model	7-20
7-12	WELL and FLUX Perturbation Plots for Grouped Anisotropy Values for BASE-USGSD Model	7-21
7-13	FLUX Perturbation Plot for BASE-DVRFS HSU Reference Permeability.	7-24
7-14	WELL Perturbation Plot for BASE HFM Model HSU Reference Permeability with DVRFS Boundary Heads and Fluxes.	7-24
7-15	Mean Head Difference for AA Water Table from LCA Reference Permeability Perturbation of BASE-DVRFS.	7-25
7-16	Mean Head Difference for AA Water Table from HSU Reference Permeability of BASE-USGSD and BLFA-USGSD Models	7-26
7-17	FLUX Perturbation Plot for HSU Reference Permeability for CPBA-USGSD Model	7-29
7-18	WELL Perturbation Plot for HSU Reference Permeability for CPBA-USGSD Model	7-30
7-19	Mean Head Difference for AA Water Table from HSU Reference Permeability Perturbation of CPBA-USGSD Model	7-31

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
7-20	WELL Perturbation Plot for Depth-Decay Coefficients for CPBA-USGSD Model .	7-33
7-21	WELL Perturbation Plot for Rock Valley Fault Permeability Multipliers for CPBA-USGSD Model	7-36
7-22	WELL Perturbation Plot for Cane Spring Fault Permeability Multipliers for CPBA-USGSD Model	7-36
7-23	WELL Perturbation Plot for Other Fault Permeability Multipliers for CPBA-USGSD Model	7-37
8-1	Carbon-14 (^{14}C) Versus Delta Carbon-13 ($\delta^{13}\text{C}$) for Volcanic and Alluvial Groundwaters	8-6
8-2	Delta Carbon-13 ($\delta^{13}\text{C}$) Versus Inverse Alkalinity for Non-LCA Wells and Springs	8-6
8-3	Comparison of Groundwater ^{14}C Ages Calculated with the DIC-Based and $\delta^{13}\text{C}$ -Based Correction Methods	8-14
8-4	Comparison of DO^{14}C Ages with Average Corrected DI^{14}C Ages of Groundwater in Tuff and Alluvium in Frenchman Flat	8-15
8-5	Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratios, DO^{14}C and DI^{14}C Ages, Theoretical Reconstructions of ^{36}Cl Production, and $^{36}\text{Cl}/\text{Cl}$ Deposition Preserved in Pack-Rat Middens	8-19
8-6	Evaluation of the Contribution of Dissolved Sodium (Na) from Halite (NaCl) Dissolution in Frenchman Flat Groundwater	8-21
8-7	Corrected Groundwater DI^{14}C Ages Versus Cation Concentrations	8-24
8-8	Cation Concentrations Versus Corrected Groundwater DI^{14}C Ages	8-24
8-9	Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratios, DO^{14}C and DI^{14}C Ages, Theoretical Reconstructions of ^{36}Cl Production, and $^{36}\text{Cl}/\text{Cl}$ Deposition Preserved in Pack-Rat Middens	8-25
8-10	Delta Deuterium (δD) Versus Delta Oxygen-18 ($\delta^{18}\text{O}$) of Groundwater From the Tuffs and Alluvium in Frenchman Flat	8-26
8-11	Groundwater $\delta^{18}\text{O}$ Values as a Function of Corrected DI^{14}C Age	8-28
8-12	Groundwater δD Values as a Function of Corrected DI^{14}C Age	8-28

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
8-13	Geochemical Reactions Accounting for the Evolution of Groundwater from UE-5 PW-2 to UE-5 PW-1	8-33
8-14	Mixing Fractions of Groundwater from Wells UE-5c WW or UE-5 PW-1 in ER-5-4	8-34
8-15	Geochemical Reactions for ER-5-4 Inverse Models	8-34
8-16	Mixing Model Results for the ER-5-4 #2 Inverse Models.....	8-36
8-17	Reactions for the ER-5-4 #2 Inverse Models.....	8-36
8-18	Estimated Groundwater Ages Calculated for Alluvial and Tuffaceous Aquifers in Frenchman Flat	8-38
8-19	Groundwater Velocities Calculated for Different Well Pairs in the Alluvium in Frenchman Flat.....	8-39
8-20	Groundwater Velocities Calculated Between the CP Basin and Well ER-5-4 #2 ...	8-40
A.1-1	Well ER-5-3 (Shallow Piezometer) Water-Level History	A-7
A.1-2	Well ER-5-3 (Deep Piezometer) Water-Level History	A-7
A.1-3	Well ER-5-3 (Main/Composite) Water-Level History.....	A-8
A.1-4	Well ER-5-3 #2 Water-Level History	A-8
A.1-5	Well ER-5-3 #3 Water-Level History	A-9
A.1-6	Well ER-5-4 (Piezometer) Water-Level History	A-9
A.1-7	Well ER-5-4 (Main/Composite) Water-Level History.....	A-10
A.1-8	Well ER-5-4 #2 Water-Level History	A-10
A.1-9	Well RNM-1 Water-Level History.....	A-11
A.1-10	Well RNM-2 Water-Level History.....	A-11
A.1-11	Well RNM-2s Water-Level History.....	A-12
A.1-12	Well UE-5n Water-Level History	A-12

LIST OF FIGURES (CONTINUED)

<i>NUMBER</i>	<i>TITLE</i>	<i>PAGE</i>
A.1-13	Well WW-4 Water-Level History	A-13
A.1-14	Well WW-4A Water-Level History	A-13
A.1-15	Well WW-5A Water-Level History	A-14
A.1-16	Well WW-5C Water-Level History	A-14
A.1-17	Post of Historical, Steady-State Heads in the AA	A-15
A.1-18	Post of Contemporary, Steady-State Heads in the AA.	A-16
A.1-19	Post of Contemporary, Steady-State Heads in the TM-WTA	A-17
A.1-20	Post of Historical, Steady-State Heads in the LCA	A-18
A.1-21	Post of Contemporary, Steady-State Heads in the LCA.	A-19
D.1-1	Fault Expressions and Hydrostratigraphic Units at the Water Table	D-2
E.1-1	NTS Investigation Area Locations of Hydraulic Conductivity Data	E-11
E.1-2	Frenchman Flat Hydraulic Property Data Locations	E-16
E.1-3	Relationship of HGU Hydraulic Conductivity Distributions.	E-18
E.1-4	Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset	E-20
E.1-5	Alluvial Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset	E-21
E.1-6	Alluvial Aquifer Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset.	E-21
E.1-7	Alluvial Aquifer Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.	E-22
E.1-8	Volcanic Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.	E-23
E.1-9	Volcanic Aquifer Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset	E-23

LIST OF FIGURES (CONTINUED)

NUMBER	TITLE	PAGE
E.1-10	Volcanic Aquifer Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.....	E-24
E.1-11	Lava Flow Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset	E-25
E.1-12	Lava Flow Aquifer, Tuff Confining Unit Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset	E-25
E.1-13	Tuff Confining Unit Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.....	E-26
E.1-14	Tuff Confining Unit Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset.....	E-26
E.1-15	Lower Carbonate Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.....	E-27
E.1-16	Lower Carbonate Aquifer Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset	E-27
E.1-17	Lower Carbonate Aquifer Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset.....	E-28
E.1-18	Specific Storage Data for the NTS Investigation Area Dataset	E-32
E.1-19	Fracture Specific Storage Data for the NTS Investigation Area Dataset.....	E-33

LIST OF TABLES

NUMBER	TITLE	PAGE
ES.1-1	Summary of Alternative Hydrostratigraphic Framework Models Considered in the Frenchman Flat Flow Model	ES-6
1-1	Corrective Action Sites in the Frenchman Flat Corrective Action Unit	1-11
1-2	Major Supporting Documents	1-13
2-1	Hydrogeologic Units of the UGTA Regional Model That Occur in the Frenchman Flat Model Area	2-4
2-2	Hydrostratigraphic Units of the Frenchman Flat Area Included in the UGTA Regional Hydrostratigraphic Framework Model.	2-6
2-3	Estimated Steady-State Groundwater Budget for the UGTA Regional Groundwater Flow System.	2-8
2-4	HGUs for the Death Valley Regional Ground-Water Flow System Hydrogeologic Framework Model.	2-9
2-5	Hydrostratigraphic Units for the Phase II Frenchman Flat Hydrostratigraphic Framework Model	2-34
2-6	Summary of Alternative Hydrostratigraphic Framework Models Considered in the Frenchman Flat Flow Model	2-36
3-1	Summary of Pumping Data for Wells in Frenchman Flat and Selected Wells in CP Basin and Southern Yucca Flat	3-8
3-2	Regional Model Boundary Fluxes	3-9
3-3	Summary of Hydraulic Heads at Target Wells Within the Frenchman Flat CAU Model Domain	3-11
3-4	Summary of Water-Level Measurements	3-14
3-5	Summary of Permeability for HSUs within the Frenchman Flat CAU Model Domain	3-26
3-6	Hydraulic Conductivity Depth-Decay Coefficients for NTS Area Aquifers.	3-38
4-1	Quadrilateral Grids Define Surfaces $z(i,j)$	4-9
4-2	Breakthrough Planes Coordinates	4-14

LIST OF TABLES (CONTINUED)

<i>NUMBER</i>	<i>TITLE</i>	<i>PAGE</i>
4-3	Size of Octree Grid Cells	4-15
4-4	Parameters Defining the Level 0 Grid	4-16
4-5	Total Recharge over the Frenchman Flat Model Area.	4-30
5-1	Calibration Components and Implementation	5-5
5-2	Head Calibration Weights	5-11
5-3	Initial Intrinsic Permeability (m^2) Reference Values at Land Surface Used in CAU Flow Model Calibration	5-17
5-4	Summary Calibration Statistics for the BASE-USGSD Model.	5-28
5-5	Summary of Calibrated Reference Permeability Values and Fault Permeability Multipliers for the BASE-USGSD Model	5-37
6-1	List of Priority C Alternative Scenarios for the Frenchman Flat 3-D Hydrostratigraphic Model.	6-5
6-2	Summary of Calibrated Reference Permeability Values and Fault Permeability Multipliers	6-6
6-3	Summary Calibration Statistics for All HFMs Used with USGSD Recharge Model.	6-22
6-4	Boundary Flows (kg/s) Considered for the Different Calibrated Models	6-67
6-5	Summary of Calibrated Reference Permeability Values and Permeability Multiplier for Non-Neutral Faults for Calibrated Models with Varying Boundary Conditions	6-68
6-6	Model Summary Statistics for Frenchman Flat Steady-State Flow Model Calibrations with Varying Boundary Conditions	6-72
6-7	Summary Calibration Statistics for Alternative Calibration of the BASE-USGSD Model	6-127
6-8	Summary of Reference Permeability Values and Fault Permeability Multipliers for the Alternative Calibration of the BASE-USGSD Flow Model . . .	6-132

LIST OF TABLES (CONTINUED)

NUMBER	TITLE	PAGE
6-9	Summary Calibration Statistics for the Calibration of the BASE-USGSD Flow Model with No Permeability Depth Decay in the AA and OAA	6-158
6-10	Summary of Reference Permeability Values and Fault Permeability Multipliers for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA	6-162
7-1	PEST Composite Sensitivity Coefficients for Select BASE-USGSD Model Calibration Parameters	7-4
7-2	Portions of Model Performance Metric Taken Out of Calibration with Changes in Vertical Fault Permeability for the BASE-USGSD Model	7-23
8-1	Groundwater Carbon Isotope Data, ¹⁴ C Dilution Factors, and Dissolved Inorganic Carbon Groundwater Ages (Uncorrected and Corrected)	8-5
8-2	Selected Groundwater Chemistry Data for Frenchman Flat	8-18
8-3	Mineral Compositions and Constraints Used for PHREEQC Models	8-32
8-4	Estimated Groundwater Travel Times and Velocities	8-42
A.1-1	Calculated Water-Level Elevations from Depths to Water Measured in November 2004	A-2
A.1-2	Comparison of Steady-State Heads with Ground-Surface Elevations Measured in November 2004 and Ground-Surface Elevations from the Frenchman Flat Hydrologic Data Document	A-5
B.1-1	Investigations Addressing Depth Dependence of Permeability or Hydraulic Conductivity	B-2
D.1-1	Fault Names and Locations for Some Faults	D-1
E.1-1	Summary of NTS Investigation Area K Analysis	E-17
E.1-2	Summary of Depth-Decay Analysis	E-19
E.1-3	Variation of the Mean and SD of Hydraulic Conductivity Data by Scale of Measurements, by HSU	E-29
E.1-4	Summary of Specific Storage Analysis	E-32

LIST OF PLATES

<i>NUMBER</i>	<i>TITLE</i>
Plate 1:	Cross Sections for BASE HFMPocket
Plate 2:	Cross Sections and Plan View for Alternative HFMs Compared with BASE HFMPocket

LIST OF ACRONYMS AND ABBREVIATIONS

amsl	Above mean sea level
ASTM	American Society for Testing and Materials
BN	Bechtel Nevada
BT	Breakthrough
°C	Degrees Celsius
CAI	Corrective Action Investigation
CAIP	Corrective Action Investigation Plan
CAS	Corrective Action Site
CAU	Corrective Action Unit
CDF	Cumulative density function
cm	Centimeter
DDE_F	Data documentation evaluation flag
DEM	Digital elevation model
DOE	U.S. Department of Energy
DRI	Desert Research Institute
DRIA	DRI Chloride Mass Balance Alluvial and No Elevation Screen Recharge Model
DRIAE	DRI Chloride Mass Balance Alluvial and Elevation Screen Recharge Model
DSC	Discrete-state cell
DVRFS	Death Valley Regional Ground-Water Flow System
ECDF	Empirical cumulative distribution function
FEHM	Finite element heat-mass transfer code
FFACO	<i>Federal Facility Agreement and Consent Order</i>
FFG	Frenchman Flat Flow and Transport Model Grid
ft	Foot
g/mole	Grams per mole

LIST OF ACRONYMS AND ABBREVIATIONS (CONTINUED)

GMWL	Global meteoric water line
GPS	Global positioning system
HFM	Hydrostratigraphic framework model
HGU	Hydrogeologic unit
HSU	Hydrostratigraphic unit
K	Hydraulic conductivity
k	Intrinsic permeability
K _d	Distribution coefficient
k _h	Horizontal permeability
k _v	Vertical permeability
k ₀	Reference permeability
kg/d	Kilograms per day
kg/m ³	Kilograms per cubic meter
kg/s	Kilograms per second
km	Kilometer
km ²	Square kilometer
km ³	Cubic kilometer
kt	Kiloton
LaGriT	Los Alamos Grid Toolbox
LANL	Los Alamos National Laboratory
LLNL	Lawrence Livermore National Laboratory
m	Meter
m/d	Meters per day
m/yr	Meters per year
m ²	Square meter

LIST OF ACRONYMS AND ABBREVIATIONS (CONTINUED)

m ³	Cubic meter
m ³ /d	Cubic meters per day
Ma	Million years ago
ME	Mean error
meq/L	Milliequivalents per liter
mg/L	Milligrams per liter
mm/yr	Millimeters per year
MME	Modified Maxey-Eakin
MT	Magnetotelluric
MWAT	Multiple-well aquifer test
N/A	Not applicable
NAD	North American Datum
NDEP	Nevada Division of Environmental Protection
NNSA/NSO	U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office
NTS	Nevada Test Site
OME	Original Maxey-Eakin
OMR	Octree mesh refinement
PDF	Probability density function
PEST	Parameter estimation software
R ²	Correlation coefficient
RNM	Radionuclide migration
SD	Standard deviation
SDWA	<i>Safe Drinking Water Act</i>
SNJV	Stoller-Navarro Joint Venture
SPTR	Streamline particle tracking

LIST OF ACRONYMS AND ABBREVIATIONS (CONTINUED)

SWNVF	Southwestern Nevada Volcanic Field
TWG	Technical Working Group
UGTA	Underground Test Area
USGS	U.S. Geological Survey
USGSD	U.S. Geological Survey Redistribution Recharge Model
USGSND	U.S. Geological Survey No Redistribution Recharge Model
UTM	Universal Transverse Mercator
VSMOW	Vienna Standard Mean Ocean Water
WW	Water Well
YMP	Yucca Mountain Project
0-D	Zero-dimensional
1-D	One-dimensional
2-D	Two-dimensional
3-D	Three-dimensional
‰	Per mil

LIST OF SYMBOLS FOR ELEMENTS AND COMPOUNDS

Ar	Argon
C	Carbon
Ca	Calcium
CaCO ₃	Calcite
CaMg(CO ₃) ₂	Dolomite
Cl	Chlorine
CO ₂	Carbon dioxide
CO ₃ ²⁻	Carbonate
D	Deuterium
DIC	Dissolved inorganic carbon
DOC	Dissolved organic carbon
² H	Deuterium
HCO ₃ ⁻	Bicarbonate
K	Potassium
Mg	Magnesium
Na	Sodium
NaCl	Halite
O	Oxygen
pmc	Percent modern carbon
SiO ₂	Silicon dioxide
SO ₄ ²⁻	Sulfate
Sr	Strontium
Th	Thorium
U	Uranium

LIST OF STRATIGRAPHIC UNIT ABBREVIATIONS AND SYMBOLS

AA	Alluvial Aquifer
BLFA	Basalt Lava Flow Aquifer
CA	Carbonate Aquifer
CCU	Clastic Confining Unit
CPBA	CP Thrust Fault
DETA	Detachment Fault
DISP	Displacement Fault
LCA	Lower Carbonate Aquifer
LCA3	Lower Carbonate Aquifer-Thrust Plate
LCCU	Lower Clastic Confining Unit
LFA	Lava Flow Aquifer
LTCU	Lower Tuff Confining Unit
LVTA	Lower Vitric Tuff Aquifer
OAA	Older Alluvial Aquifer
PCU	Playa Confining Unit
PCU1U	Playa Confining Unit 1 - Upper
PCU1L	Playa Confining Unit 1 - Lower
PCU2T	Playa Confining Unit 2 - Top
TCU	Tuff Confining Unit
TMA	Timber Mountain Aquifer
TM-LVTA	Timber Mountain Lower Vitric Tuff Aquifer
TM-WTA	Timber Mountain Welded Tuff Aquifer
Tmr	Rainier Mesa Tuff
Tpt	Topopah Spring Tuff
TSA	Topopah Spring Aquifer
UCCU	Upper Clastic Confining Unit

LIST OF STRATIGRAPHIC UNIT ABBREVIATIONS AND SYMBOLS (CONTINUED)

UTCU	Upper Tuff Confining Unit
VA	Volcanic Aquifer
VCU	Volcaniclastic Confining Unit
VTA	Vitric Tuff Aquifer
VU	Volcanics undifferentiated
WCU	Wahmonie Confining Unit
WTA	Welded Tuff Aquifer

EXECUTIVE SUMMARY

This Executive Summary is a synopsis of the report entitled *Phase II Groundwater Flow Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada*, prepared for the U.S. Department of Energy (DOE). Steady-state groundwater flow models of the Frenchman Flat Corrective Action Unit (CAU) have been constructed using a range of hydrostratigraphic framework, recharge distribution, boundary head, and hydraulic parameter assignment conceptualizations. Model calibration, uncertainty, and sensitivity analyses, as well as geochemical verification were conducted and documented.

ES-1 INTRODUCTION

The DOE, National Nuclear Security Administration Nevada Site Office (NNSA/NSO) initiated the Underground Test Area (UGTA) Project to assess and evaluate the effects of underground nuclear weapons tests on groundwater at the Nevada Test Site (NTS) and vicinity through the *Federal Facility Agreement and Consent Order* (FFACO, 1996). The processes that will be used to complete UGTA corrective actions are described in the Corrective Action Strategy in the FFACO Appendix VI, Rev. 1 (December 7, 2000). The objective of the strategy is to analyze and evaluate each UGTA CAU through a combination of data and information collection and evaluation, and modeling groundwater flow and contaminant transport. For the UGTA Project, the corrective action strategy includes two major parts: a regional evaluation addressing all CAUs and a corrective action investigation (CAI) process for each of the individual CAUs. The first major part was completed with the development of the model and report entitled *Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada* (DOE/NV, 1997). The second part of the process focuses on acquisition and analysis of CAU-specific data and development of CAU-scale flow and transport models. The CAU-specific objectives are to estimate the movement of contaminants utilizing CAU-specific hydrogeologic and transport parameter data and to define contaminant boundaries.

The CAI process may be iterative, resulting in several phases of data collection, analysis, and modeling with assessment of confidence in the results at the completion of each phase. The Phase I Frenchman Flat CAI was completed in 1999. Based on external and internal review, the need for

additional work was identified, and an addendum to the corrective action investigation plan (CAIP) was developed entitled *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001). The Frenchman Flat CAIP addendum detailed the new data collection and modeling activities to address the documented deficiencies in the Phase I Frenchman Flat CAI. The new data collection activities have been completed with results incorporated into the Phase II Frenchman Flat CAU groundwater flow model, which is the subject of this report.

The CAIP identifies a three-step model development process to evaluate the impact of underground nuclear weapons testing on groundwater. The first step is the compilation and evaluation of existing and new data for use in the model, and is documented in a series of data compilation and analysis reports, including *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada* (SNJV, 2004d). The second step, the development of the Phase II groundwater flow model, is completed and documented in this report. The third and future step will be the development of the transport model to assess the migration of radionuclides away from underground nuclear test cavities in Frenchman Flat.

The Phase II data collection activities included well drilling, geophysical investigations, and hydrogeologic and geochemical investigations. The Phase II data significantly improved the understanding of local thicknesses for alluvial and volcanic hydrostratigraphic units (HSUs) in the vicinity of the underground tests, assisted in the identification of alternative hydrostratigraphic framework models for the Frenchman Flat basin, increased the hydrogeologic parameter database for Frenchman Flat, and provided geochemical data for use in testing alternative conceptual models for flow in the basin.

The underground nuclear tests conducted at Frenchman Flat were detonated in vertical shafts or drill holes in alluvium or volcanic rock within the saturated zone or 100 meters (m) or less above the water table. A total of 10 such underground nuclear tests were conducted in Frenchman Flat. Transport in groundwater is the primary mechanism for migration of the subsurface contamination away from Frenchman Flat underground nuclear tests.

The Frenchman Flat flow system is part of the Death Valley regional flow system. Frenchman Flat is a closed-drainage intermontane basin located in the southeastern portion of the NTS. It is bounded on

the north by Massachusetts Mountain and the Halfpint Range, on the east by the Ranger Mountains and Buried Hills, on the south by the Spotted Range, and on the west by the Wahmonie Hills. The valley floor of the basin slopes gently from the surrounding highlands to the lowest-lying playa area. Ground elevations range from over 1,463 m above mean sea level (amsl) in the surrounding mountains to approximately 938 m amsl at Frenchman Lake playa. The conceptual model of groundwater flow through Frenchman Flat is that the bulk of the flow occurs in the lower carbonate aquifer (LCA), and that the LCA is the only subsurface pathway by which groundwater enters and exits Frenchman Flat. The LCA forms a nearly continuous aquifer across the region except where interrupted by calderas, truncated by structural controls, or penetrated by intrusive rocks. A minor amount of water leaks from the alluvial aquifer (AA) through the tuff confining units (TCUs), which overlie the LCA over much of Frenchman Flat, and into the LCA.

Specific objectives of the Phase II Frenchman Flat CAU groundwater flow model are to:

- Incorporate pertinent information and lessons learned from the Phase I Frenchman Flat CAU models.
- Develop a three-dimensional (3-D), numerical flow model that incorporates the important physical features of the flow system and honors CAU-specific data and information.
- Simulate the steady-state groundwater flow system to determine the direction and magnitude of groundwater fluxes based on calibration to Frenchman Flat hydrogeologic data.
- Quantify the uncertainty in the direction and magnitude of groundwater flow due to uncertainty in component conceptual models (e.g., geology, boundary flux, and recharge).

ES-2 PREVIOUS WORK

The data and conceptual models used to develop the Frenchman Flat CAU flow model represent a large body of work and are described in SNJV (2004d). The regional and site-specific elements that are integrated into the Frenchman Flat flow model include:

- Regional data and models that provide the broad hydrogeologic context for the CAU-specific flow model.
- CAU-specific geologic data and models that establish the local hydrostratigraphic framework within which groundwater flows.

- Component models (e.g., geologic models, recharge models) that integrate the regional hydrogeology into CAU-specific hydrogeology.
- Alternative CAU-specific component models to address uncertainty in hydrostratigraphy, lateral boundary flux and heads, and recharge.
- CAU-specific hydrologic parameters (including their uncertainty).

An overview of the regional flow models, recharge models, and hydrostratigraphic framework models (HFMs) is presented below.

Regional Models

Two regional groundwater flow models are relevant to supporting the development of the Phase II Frenchman Flat CAU flow model. A conceptual and steady-state numerical model of the regional groundwater flow system (termed the UGTA regional model) was developed during the regional evaluation, with the description of the regional hydrogeologic framework and groundwater occurrence and movement presented in DOE/NV (1997). The Death Valley Regional Ground-Water Flow System model (DVRFS) (Belcher et al., 2004) was developed as an integrated regional modeling analysis tool to support NNSA/NSO investigations at the NTS and Yucca Mountain. Because the DVRFS was not finished at the time CAU-model supporting analyses were conducted, its results could not be as comprehensively considered as the DOE/NV (1997) model. Both regional models were used to provide supporting information (e.g., Frenchman Flat CAU boundary fluxes) for the Phase II Frenchman Flat CAU flow model.

Recharge Models

Three basic approaches have been used to develop alternative recharge models for the NTS area. These include: a net-infiltration recharge model from watershed distributed parameter modeling by the U.S. Geological Survey (USGS), chloride mass-balance modeling by the Desert Research Institute (DRI), and the modified Maxey-Eakin (MME) empirical approach. Three subsets of the USGS and two subsets of the DRI recharge maps were considered. The USGS recharge models included a recharge model with runoff or run on (redistribution) (denoted USGSD), a recharge model without redistribution (denoted USGSND), and recharge distribution from the DVRFS model (a calibrated version of the USGSD recharge distribution). Two DRI recharge models included no recharge in the alluvial areas (DRI alluvial mask alternative, denoted DRIA) and no recharge in the

alluvial area and no recharge below an elevation of 1,237 m (DRI alluvial and elevation mask alternative, denoted DRIAE case).

Phase II Base and Alternative Hydrostratigraphic Framework Models

All rocks of the NTS and vicinity can be classified as one of eight hydrogeologic units (HGU), which include the AA, four volcanic HGUs, an intrusive HGU, and two HGUs that represent the pre-Tertiary sedimentary and metasedimentary rocks. Hydrostratigraphic units are groupings of contiguous stratigraphic units that have a particular hydrogeologic character, such as an aquifer or a confining unit. An HSU may contain several HGUs but is defined so that a single general type of HGU dominates (for example, mostly welded-tuff and vitric-tuff aquifers, or mostly tuff confining units).

Four types of data collection activities were completed as part of the Phase II investigation. These activities included: the drilling and completion of five new wells in the vicinity of the two testing areas (central and northern) in Frenchman Flat; aquifer testing; geophysical investigations including gravity, ground and aeromagnetic, seismic, and magnetotelluric; and groundwater isotopic and geochemical investigations. The well drilling and geophysical investigations contributed new data and information for use in the development of the Phase II HFMs.

The Phase II Frenchman Flat area HFMs were constructed using EarthVision[®], a 3-D geologic model building and visualization software package. The Phase II Frenchman Flat HFM area encompasses more than 570 square kilometers (km²) in the southeastern portion of the NTS. The model area has a north-south length of 30 kilometers (km) and an east-west length of 19 km, and includes geologic units as deep as -5 km amsl.

An HFM that represents the consensus of the currently most viable model (called BASE) and four alternative HFMs (different geologic interpretations that are equally consistent with the available data) were developed. The BASE HFM model includes more than 70 faults and 17 HSUs (9 aquifers and 8 confining units). The structural elements are typically normal faults (basin- and range-style faults) but also include several strike-slip and older thrust faults. Only faults considered to be hydrologically significant, larger faults and the faults that seem to form significant structural boundaries, were included in the model.

Following the completion of the BASE HFM, four alternative HFMs were developed. The main criterion for selecting alternative HFMs was the potential impact of the alternative interpretation on groundwater flow and the transport of contaminants in groundwater. The characteristics of the alternative HFMs and their potential impacts on the flow model are summarized in Table ES-1:

Table ES.1-1
Summary of Alternative Hydrostratigraphic Framework Models Considered in the Frenchman Flat Flow Model

Alternative HFM	Key Difference(s) Compared to BASE HFM	Potential Impacts on Flow Model
Basalt Lava Flow Aquifer (BLFA)	The BLFA HSU is modeled as a single continuous basalt flow, rather than three separate zones.	Located at or near the water table, which may affect flow and transport of radionuclides away from underground nuclear tests in the northern testing area.
Detachment fault (DETA)	This alternative has no detachment fault present in the northern portion of Frenchman Flat.	In this alternative, removing the fault eliminates potential hydrologic consequences. Volcanic rocks were modeled as dipping moderately southward from Area 11.
Displacement fault (Aquifer Juxtaposition) (DISP)	This alternative is concerned with the locations and displacement of basin-forming faults and yields juxtaposed shallow volcanic aquifer HSUs with the LCA along a major basin-forming fault.	This alternative juxtaposes shallow aquifers against deeper aquifers, allowing a hydraulic connection between volcanic aquifers underlying the AA in Frenchman Flat to carbonate aquifers east and south from the Rock Valley fault system.
CP thrust fault (CPBA)	The CP basin alternative extends the upper clastic confining unit (UCCU) beneath all of CP basin, resulting in a continuous sheet of UCCU beneath the basin.	Some uncertainty exists in the distribution of pre-Tertiary HSUs, particularly the distribution of UCCU beneath CP basin. This alternative results in a continuous sheet of UCCU beneath the basin.

ES-3 DATA AND CONCEPTUAL MODELS

Geologic Setting

Mapping studies and subsurface borehole and geophysical data indicate that the central part of the Frenchman Flat basin is an eastward-tilted half-graben with significant vertical displacement along splays of the Rock Valley fault system that bound it along its southern, eastern, and northern margins.

Sedimentary and volcanoclastic rocks, followed by ash-fall and ash-flow tuffs and finally alluvial and playa deposits, filled the basin as it developed, along with lavas emanating from the Wahmonie volcanic center to the west of the basin. Stratigraphic relationships between alluvium and tuffs within the basin indicate that formation of the main part of the basin was initiated after eruption of the Ammonia Tanks Tuff (11.45 million years ago [Ma]) and before the eruption of the Thirsty Canyon group had been completed at 9.14 Ma. Basin development continued after deposition of the tuffs, as demonstrated by the faulted nature of the tuffs and the accumulation of more than 1,400 m of alluvium in the center of the basin. The alluvium thins toward and beyond the structural margins of the basin where it directly overlies the LCA. Along the northern, eastern, and southern margins, the tuff confining units that line the basin have been thinned by faulting and erosion, increasing the potential for hydraulic connections between the shallower material in the basin and the LCA in these areas.

Precipitation and Recharge

Precipitation in the vicinity of the NTS is strongly dependent upon elevation. In the vicinity of Frenchman Flat, precipitation gauges with records spanning up to 50 years show that precipitation for Frenchman Flat and CP basin areas is about 5 to 6 inches per year (13 to 15 millimeters per year). The low rates of precipitation lead to estimates of recharge rates that are close to zero on the basin floor to as much as several millimeters per year in the hills bordering the basin. Although the various recharge models that have been developed for Frenchman Flat differ in the details of how that recharge is distributed throughout the basin, they each produce net amounts of recharge that are, at most, 1 percent of the total amount of groundwater flow through the basin. This suggests that groundwater flow velocities will be small in parts of the basin where groundwater is derived predominantly from the recharge of precipitation.

Groundwater Discharge

Within the Frenchman Flat area and vicinity, the only mechanism of groundwater discharge to the surface is withdrawal from the flow system by wells. Transient well-related effects are very localized and likely not representative of conditions over a majority of the model area. Thus, discharge from pumping wells is not included in the model.

Inflow and Outflow (Lateral Boundary Flows and Boundary Heads)

A set of alternate boundary flows and associated boundary heads to be used with the Frenchman Flat CAU flow model were obtained from the UGTA regional model by calibrating 30 regional-scale flow models implemented with MODFLOW-2000. The 30 models represent different flow system representations derived from combinations of various hydrostratigraphic and recharge models. The different HFMs reflect the effect of uncertainty in the geology. The recharge models represent different methods of approximating recharge for the NTS area. The alternate boundary flows and heads were used to help evaluate the uncertainty in the CAU flow model associated with the choice of flow system conceptual HFM, recharge model, and boundary conditions. The approach used to calculate these fluxes does not specify the location or locations on the boundary where the flux occurs in each of the 30 models, just bounds on the total amount of net inflow or net outflow through each boundary.

In general, groundwater is simulated in the UGTA regional model as flowing from the north and east toward the south and west through the Frenchman Flat CAU-flow model domain. This is generally true regardless of the recharge model or HFM. The lateral boundary fluxes were found to be insensitive to changes in the HFM, whereas the choice of recharge model had a significant impact on the lateral boundary flows and heads, primarily by changing the heads and gradients along the boundaries of the models.

Lateral boundary flows and recharge flux estimates for the Frenchman Flat model domain were also obtained from the DVRFS model. This model is implemented using MODFLOW-2000. Flows are generally similar in magnitude and direction as compared to the boundary flows estimated from the UGTA regional model. However, differences in the simulated flows across the southern and eastern boundaries are observed between these two regional flow models. While both models simulate net inflows from the north and east into the Frenchman Flat CAU model domain, the UGTA regional model inflows from the east exceed those from the north; the DVRFS model simulates more flow into the northern boundary. In the DVRFS model, as well in the UGTA regional models, recharge constituted less than 1 percent of the total outflow from the CAU model domain.

Hydraulic Heads

Pre-pumping hydraulic heads were estimated for use in development of the steady-state Phase II Frenchman Flat CAU flow model. Water supply wells have been intermittently pumped since the early 1950s, and water withdrawals may have affected water levels in the vicinity of the pumping wells. To minimize the effects caused by water withdrawals, pre-pumping water levels at the pumping wells were estimated from measurements made during periods preceded by little or no pumping. Adjustments were made to water levels to account for borehole deviation, barometric effects, and water density differences associated with groundwater temperature variations.

Differences in heads in individual HSUs throughout the basin area are small, which leads to a generally low horizontal gradient. Hydraulic heads are very similar in the AA in Frenchman Flat, both horizontally and vertically. The direction of horizontal gradients in the AA is to the east and south in the northern testing area. In the central testing area, AA gradients are to the east and possibly south. Hydraulic heads are higher in the alluvium than the LCA, reflecting a separation of the local flow system in the AA from the regional system in the LCA caused by the lower tuff confining unit (LTCU). In the LCA, horizontal gradients are generally from east to west/southwest. Also, it appears that the LTCU is overpressurized in the central testing area and that high heads in this HSU effectively prevent groundwater movement from the alluvium downward to the LCA.

Hydraulic Properties

A compilation of permeability data from analogous HGUs in the NTS investigation area was completed and compared to more limited data from comparable HGUs in the Frenchman Flat area. Data were grouped by HGUs - such as the AA, LCA, TCU, and volcanic aquifer (VA) HGUs - so that data from similar rock types could be considered collectively and compared to the permeability of individual HSUs in the model. The permeability distribution in Frenchman Flat is conceptualized as resulting from the superposition of effects controlled by the HGU type, anisotropy, the decay of permeability with depth, and faulting.

Intrinsic permeability values determined from pumping-scale hydraulic conductivity analyses were assigned to each of the Frenchman Flat HSUs. An average temperature of 30 degrees Celsius is assumed. Both Frenchman Flat-specific permeability distributions and permeability distributions for regional equivalent HSUs were available (mean, standard deviation, minimum, and maximum).

Very little is known about the anisotropy of most of the HSUs in Frenchman Flat except for the alluvium. A number of methods were applied to estimate the anisotropy of the alluvium in Frenchman Flat. These include somewhat indirect approaches that analyze hydraulic conductivity variations from borehole flow logs and core sample data, and more direct field methods such as cross-hole hydraulic tests. Additional anisotropy values are estimated from site-specific models for Frenchman Flat that were developed either to interpret multiple-well aquifer test data from Frenchman Flat or that are calibrated based on these data, as well as regional models for the NTS and elsewhere that have estimated the anisotropy of alluvium in similar basins from steady-state and transient head data.

The fact that some of the scatter in the Frenchman Flat permeability data for the AA is attributable to uncertainty surrounding assumptions in the analysis methods, rather than to heterogeneity, combined with strong evidence from the re-analysis of the NTS data and the ER-5-4 flow log, demonstrates that depth decay should be considered for the AA (and other HSUs) in Frenchman Flat. For these reasons, the conceptual model for the flow system in Frenchman Flat continues to regard depth decay as a likely conceptual model.

Conceptual Model Summary

Groundwater flow through the Frenchman Flat basin is driven by recharge within the basin and groundwater flow from areas of higher head to the west of the basin. Hydraulic head data do not indicate large lateral or vertical gradients, and suggest that groundwater flow is slow within the basin, a conclusion that is consistent with low rates of recharge and limited inflow to the basin across the Cane Spring fault inferred from the large water level differences between the Frenchman Flat and CP basins. Rates of present-day recharge in the model area are 1 percent or less of the total fluxes estimated to pass through the model area, mostly through the LCA. The rate and direction of groundwater flow within the Frenchman Flat basin depend on the magnitude, spatial variability, and directional dependence of permeability within the basin, as well as on the vertical and lateral hydraulic gradients in the basin. The anisotropy and the variation of permeability with depth in the alluvium, in particular, will play an important role in determining whether shallow groundwater flow near the nuclear test locations moves predominantly horizontally or has a strong vertical component. The absence of significant vertical hydraulic gradients in the AA, combined with effects of depth

decay in permeability and the possibility k_H/k_z ratios potentially much greater than unity indicate that groundwater flow in the AA will be predominantly lateral to the basin margins.

Key aspects of the Phase II conceptual groundwater flow model in the Frenchman Flat CAU are summarized below:

- Regionally, groundwater flow occurring in the LCA is conducted into the northern edge of the Frenchman Flat CAU model from southern Yucca Flat and areas east, eventually discharging at Ash Meadows and possibly Alkali Flat and Death Valley. This regional conceptual model remains unchanged from Phase I.
- Recharge from sources within the basin provides only minor amounts of water to the flow system. Even when three different models of recharge (MME, USGS distributed parameter watershed, and DRI chloride mass-balance) are considered in conjunction with Frenchman Flat precipitation, the recharge contribution to the Frenchman Flat water balance is on the order of 1 percent or less. This element of the conceptual model remains unchanged from Phase I, and low local recharge is ubiquitous in Phase II.
- Flow through the LCA is largely controlled by faults and fractures, with the Rock Valley fault system as a major regional system. Whether or not the Rock Valley fault system is ubiquitously and intensely fractured enough to form megachannels, as previously suggested, remains unknown.
- Volcaniclastic, bedded, and welded tuff units with locally interbedded lava flows and breccia overlie the LCA over most of Frenchman Flat. These units are thickest on the northwest and west margins of the basin near their volcanic source areas, and thin progressively toward the east and south margins of the basin. The conceptual model, a thick section of Paleozoic carbonate rocks overlain by volcanic and alluvial units in the basin, is unchanged from the Phase I conceptual models and remains as a core component of all alternative HFMs. Confining units were encountered in the central testing area in ER-5-4 #2 and in the northern testing area in ER-5-3 #2. The alluvial and volcanic sections determined during Phase II drilling at these two locations were thicker than expected.
- Hydraulic heads are higher in the alluvium than the LCA, reflecting a separation of the local flow system in the AA from the regional system in the LCA. This interpretation remains unchanged from Phase I.
- Hydraulic heads are very similar in the AA in Frenchman Flat, both horizontally and vertically. Thus, there is very little driving force for groundwater flow in any direction.
- The heads in the LTCU, which is one of the volcanic units that separates the AA and LCA flow systems, appear to be higher than either the AA or LCA. This presents an additional barrier to regional-scale migration from the underground nuclear tests.

- Faults through the alluvium are likely to be barriers rather than conduits for flow.
- Faults in consolidated rocks may display considerable anisotropy and vary in their properties depending on their porosity and mechanical properties.

ES-4 GROUNDWATER FLOW MODEL CONSTRUCTION

Approach

The objective for construction of the Phase II Frenchman Flat CAU flow model is the transformation of the conceptual model into a mathematical model for simulating groundwater flow. The construction process includes spatial discretization, definition of boundary conditions, and initial assignment of model parameters. The modeling approach enhances and extends the Frenchman Flat CAU flow model approach presented in the Frenchman Flat CAIP addendum (NNSA/NV, 2001).

The construction of the CAU flow model involves the following step:

- Define the CAU numerical model boundaries
- Mesh generation
- Establish boundary conditions

Model Boundaries

Model boundaries are extended to include the most relevant features that could be controlling the flow directions and gradients in the AA and to take advantage of the detailed information available in the HFMs. The HFM boundaries were chosen such that they encompass perceived geologic and hydrologic domains and, to the extent possible, contain the contaminant source areas with some buffer within practical computational constraints.

The CAU numerical model lies within the HFM domain and has lower-left plan coordinates of 584,500 and 4,061,000 m (Universal Transverse Mercator [UTM] Zone 11, North American Datum [NAD] 27 m) and upper-right plan coordinates of 603,500 and 4,091,000 m. The model is aligned north-south, with no rotation. The numerical model extends from the estimated water table to the bottom of the LCA at an elevation of about -3,500 to -4,500 m above mean sea level. The hydrologic model area encompasses 570 km² of the southeastern portion of the NTS. The area has a north-south length of 30 km and an east-west length of 19 km.

Mesh Generation

A set of criteria were developed to produce a mesh that is suitable for both flow and transport calculations for the Frenchman Flat CAU using the Finite Element Heat-Mass Transfer Code (FEHM). The resultant mesh has sufficient resolution to represent features such as hydrostratigraphy, faults, contaminant source zones, wells, and the water table, yet not too refined to make computations impractical. Further, the mesh has enough resolution at the areas of structure and fault change between the different HFMs such that the same mesh is used to reasonably simulate all alternative HFMs. In general, the criteria for grid generation are as follows:

- The external boundary of the CAU model will correspond to appropriate cell boundaries within the regional groundwater flow model.
- Nodes will be placed as close as practical to each underground test location as well as at specific well locations and along the wells' open intervals.
- Nodes will be placed along faults that are identified as being important to the distribution of HSUs and the flow regime.
- The node density will be greatest in the vicinity of the underground nuclear tests and at other points of interest, such as faults, and will decrease toward the CAU-model boundaries.
- Nodes will be preferentially placed along HSU contacts to more precisely incorporate the geologic model structure in the simulations. The nodes form a pattern representative of the CAU-scale geology.
- The node spacing will vary from small in the vicinity of test cavities and wells to nearly as large as in the regional groundwater flow model grid at the CAU boundary.

The resulting grid contains 1,250,721 nodes and 7,144,765 tetrahedral elements. The grid was designed to accommodate the BASE and four alternative HFMs.

Water-Table Definition

The FEHM simulations utilize a confined aquifer approximation in which the water table defines the top of the model domain. An estimate of the water table is developed using observed heads in wells relatively shallow in the flow system and regional model results. The confined aquifer approach does not include an unsaturated zone or moving water table and, therefore, solves a simplified and computationally more efficient numerical model.

Boundary Conditions

The solution of the groundwater flow equations requires specification of head and/or flow at the edges and at internal discharge points of the numerical model. The only mechanism for discharge of groundwater to the surface in the Frenchman Flat area and vicinity is withdrawal through wells, which are not considered. Surface discharge due to pumping of wells in the Frenchman Flat area and vicinity is not incorporated into the CAU model.

Recharge is implemented in the CAU model as a specified flux condition, where a given volume (mass) of water is applied based on the recharge models. Recharge flux is considered to be constant over time but varies over the domain.

Boundary heads interpolated from the UGTA and DVRFS regional model analyses were assigned to the edge nodes of the FEHM CAU model as boundary conditions. These heads represent a mass conservative calibrated solution to the groundwater flow equation from the regional models. During the calibration process, these heads were reviewed, and in spots, revised based on further examination of measured heads and heads determined from the regional models. Different boundary head configurations were considered during the model calibration and uncertainty analyses depending on the alternative HFM and recharge distribution used in the model.

ES-5 FLOW MODEL CALIBRATION

The purpose of the Frenchman Flat flow model calibration is to transform the conceptual models into site-specific mathematical models for representing the groundwater flow system in the Frenchman Flat CAU area. This is accomplished through the guided adjustment of boundary heads and hydraulic properties for HSUs and faults within different HFMs in order to match specified targets. Targets included weighted observed water-level data with the model boundary, and boundary head and flow estimates from calibrated regional models. Recharge estimates are not used as calibration targets, but are fixed as model input values during calibration and uncertainty analyses.

A steady-state groundwater flow model was created for the Frenchman Flat CAU using the BASE HFM in conjunction with lateral boundary heads and fluxes and water-table recharge based on a USGS water-balance model of infiltration and recharge (the USGSD recharge model). The boundary

conditions for the resulting Frenchman Flat flow model (designated the BASE-USGSD flow model) were taken from the UGTA regional model by interpolating hydraulic heads produced with the regional model onto the lateral boundaries of the BASE-USGSD model. The net groundwater fluxes calculated by the UGTA regional model along the planes coinciding with the lateral boundaries of the BASE-USGSD flow model were calculated and used along with 30 hydraulic head measurements at target well locations to calibrate the CAU flow model. Measurement uncertainty and calibration weights were determined for the hydraulic head measurements by considering uncertainty in different aspects of the head measurements such as groundwater surface elevation, depth to groundwater, and borehole deviations from vertical. Permeability within the model varied among the HSUs, and as a function both of depth and of the permeability modification factors that were applied to the faults during calibration.

Calibration of the BASE-USGSD flow model was accomplished through a combination of automated parameter estimation and manual adjustments to the model parameters that were guided by sensitivity analyses. Automated parameter estimation was successful in matching boundary fluxes but was less successful in matching hydraulic heads within the flow model area. Typically, manual adjustments to the model parameters were required to obtain a set of simulated heads within the uncertainty of the measured hydraulic heads. Simulated heads generally matched the measured heads to within the uncertainty limits estimated for the measurements except at wells in the LCA near the northern boundary of the model.

The simulated heads in the AA matched the field-measured head data with a high degree of accuracy and correctly simulated the near-absence of a vertical gradient within the AA indicated in the data. A comparison of measured heads at the ER-5-3 well complex in the northern testing area with a vertical profile of simulated heads produced with the BASE-USGSD flow model indicated that both measured and modeled vertical head gradients are virtually non-existent between the alluvium and the underlying volcanic aquifers near the ER-5-3 well complex. Therefore, there seems to be very little potential for downward flow in the alluvium, despite the overall drop in heads between the alluvium and the LCA. The data and the model results indicated that most of the head loss between the alluvium and the LCA occurs across the thick confining units, like the LTCU, that are present beneath the testing areas. A similar comparison between measured and simulated heads at the ER-5-4 well complex indicates that simulated heads in the BASE-USGSD model again accurately depict the

near-constant heads in the alluvium between the water table at 734 m amsl. Again, this would suggest that there is very little downward gradient through the alluvium that would create downward flow. Simulated heads show an almost 1-m increase between the lower alluvium and the Timber Mountain welded tuff aquifer (TM-WTA), creating a pressure barrier that would also prevent groundwater movement from the alluvium to the LCA. Although data do not exist to evaluate the presence of a pressure barrier in the TM-WTA, measured hydraulic heads of more than 755 m in the LTCU at Well ER-5-4 #2 indicate that the concept of a pressure barrier in the central part of Frenchman Flat is feasible. The results of the BASE-USGSD flow model indicate that this pressure barrier could arise when high-permeability units like the TM-WTA (or similar lithologies embedded within the thick LTCU) act as confined aquifers and connect the deep parts of the Frenchman Flat basin with areas of higher head to the west.

The permeabilities estimated during calibration of the BASE-USGSD flow model were compared to the data from the general NTS area and from Frenchman Flat. The match between the estimated and measured permeabilities is good in most cases. For some HSUs, such as the AA and the LTCU, the estimated permeabilities were toward the lower end of the observed data range. The final permeability field associated with the calibrated model reflects differences among the permeabilities estimated for the different HSUs, the effect of the decay in permeability with increasing depth, and the effects of permeability changes associated with faults. The permeability fields that result from the superposition of these effects can be very complex in some areas - particularly in the northern testing area, where groundwater bifurcates, with flow north of a detachment fault flowing east or northeast, and groundwater to the south of the detachment fault flowing predominantly southward. In the central testing area, particle trajectories are toward the southeast. Eventually, all particles initially located beneath the testing areas are simulated to eventually exit the model through the Rock Valley fault system in the southwest corner of the model.

ES-6 CONCEPTUAL MODEL UNCERTAINTY ANALYSIS

Uncertainty analyses are evaluated in the context of the use of flow models to achieve the UGTA corrective action strategy specific to the Frenchman Flat CAU. The overall flow and transport modeling strategy is to establish the horizontal and vertical extent and the uncertainty in contaminant migration for each CAU. A primary goal of the flow model phase is to examine a range of permissible

fits to the calibration data recognizing the non-unique nature of the multiple conceptual models and parameter sets. The conceptual model uncertainty includes alternative HFMs, boundary condition uncertainty, and model results that have a constant permeability with depth below ground surface. These analyses are referred to as analyses of conceptual model uncertainty and the results are presented separate from parameter sensitivity analysis.

The primary goal of the assessment of the conceptual model uncertainty is to define the uncertainty of the flow model responses associated with alternative HFM uncertainty, boundary condition uncertainty, and HSU fault parameter uncertainty, and to provide guidance on how to include or represent that uncertainty in the transport simulation.

HFM Uncertainty Analysis

Steady-state groundwater flow models to assess conceptual model uncertainty were calibrated using different HFMs that interpreted aspects of the Frenchman Flat hydrostratigraphy somewhat differently. Each of the HFMs included 17 HSUs, of which 8 were considered as aquifers and 9 as confining units, and more than 70 faults that were included based on their potential hydrologic significance. Each of these HFMs was used in conjunction with a map of recharge for the Frenchman Flat area that was taken from a water-balance model of infiltration and recharge (designated the USGSD model) originally developed for the regional model area.

Independently calibrated models for the BASE and CPBA HFMs provide generally similar fits for boundary fluxes and simulated heads, with the exception of measured heads at Wells WW-C, WW-C1, WW-4, and WW-4A, where the heads are better simulated by the BASE-USGSD model. Calibration fits are generally superior for the BASE-USGSD model compared to the CPBA-USGSD alternative for multiple statistical parameters that characterize goodness of fit. Particle tracks are generally similar for the northern testing area for both models with the exception of particle tracks starting in the vicinity of the PIN STRIPE test location. The DISP-USGSD model calibration indicated that a completely open connection between the alluvium and the LCA is unrealistic, but that modest adjustments to fault parameters allow for a good simulation of water-level observations. The BLFA-USGSD and DETA-USGSD alternatives were calibrated using the unchanged parameters estimated during calibration of the BASE-USGSD model. Both models show similar patterns of particle tracks for the central testing area compared to the BASE-USGSD model and show some

variability in particle tracks compared to the BASE model for the northern testing area. The primary differences are in the direction of the particle trajectories and in HSUs traversed along the pathways. The significance of model differences will be further evaluated during transport modeling studies.

Discrete Uncertainty Analysis

Discrete uncertainty analyses were conducted to evaluate likely scenarios that would lead to longer-range contaminant transport for particles starting at the northern or central testing areas. Discrete uncertainty analyses were used to examine the effects of several model parameters on the model calibration and groundwater flow paths calculated by the BASE-USGSD and BLFA-USGSD models in the northern or central testing areas of the Frenchman Flat basin. The permeability of two faults (35 and 38) in the alluvial and volcanic sections and one HSU (BLFA) were increased to the point where the model calibration was significantly impacted. These parameters were selected because of their great uncertainty and conceptual possibility to affect flow from underground nuclear tests. Changes to parameters in the northern testing area suggest that flow trajectories may be modified through adjustment to the selected model parameters, but the ability of other model parameters to compensate for the model misfit was not determined. In this sense, the effects of these changes may be exaggerated. Changes to tested model parameters in the central testing area have little influence on the resulting flow field. The impact of these flow fields to contaminant transport for the time frame of interest will be investigated during the contaminant migration analysis that will be documented in a later report.

Boundary Conditions Uncertainty Analysis

Results from seven flow models investigating boundary condition uncertainty were evaluated. The two alternative HFMs that are most distinctly different based on calibration with the USGSD boundary conditions (BASE and CPBA HFM alternatives) were combined with the DRIA-, MME-, and DVRFS-boundary conditions. These models were used to bound the uncertainty in the CAU flow system resulting from variations in boundary conditions that were determined through the use of several regional groundwater flow models. Because areal recharge provides limited water flux into the top of the Frenchman Flat CAU flow model domain, differences among the boundary heads and boundary fluxes dominated this component in the flow field of the uncertainty analyses. An

additional analysis documenting an alternative approach to boundary head adjustments was used to evaluate additional uncertainty in the calibrated flow field.

There is an almost unbounded range of combinations of alternative HFM, recharge, boundary condition, and discrete feature assessments that could be proposed and evaluated through flow calibration and sensitivity analysis. The combination of the calibration results and the uncertainty evaluations that were conducted likely bound the range of expected model responses and particle track results. These flow model results form a foundation that will be carried forward into transport modeling to evaluate the significance of model conceptualization and pathway variation on the location of the contaminant boundary.

Results from the MME boundary conditions using the BASE HFM and CPBA HFM are most similar to the BASE-USGSD model and provided the best overall match to the hydraulic head calibration data. The simulated head in both models at Well ER-5-3 #2 is lower than heads measured in the overlying alluvium and tuffs at nearby Wells ER-5-3 and ER-5-3 #3. This signifies that the observed downward head gradient between the alluvium and LCA in northern Frenchman Flat is captured in these models. Groundwater flow paths near the NEW POINT, DIAGONAL LINE, DIANA MOON, and MINUTE STEAK test locations indicate primarily southward flow. The groundwater flow path at the northern edge of the Frenchman Flat basin appeared to be dominated by eastward advection. Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast in both models, as was observed in the BASE-USGSD model, indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction.

Results from the DVRFS boundary conditions using the BASE HFM and CPBA HFM are the most dissimilar to the BASE-USGSD model. These models provided as good a fit as other models to both the shallow hydraulic head at the observations and boundary flows. However, the simulated head in the LCA for both models was higher than heads measured in the overlying alluvium and tuffs at the ER-5-3 well cluster. This indicates an upward head gradient between the alluvium and LCA, contrary to the both hydraulic head data and the conceptual understanding of the Frenchman Flat CAU flow system. Lateral groundwater flow paths in the volcanic HSUs and basin-fill units did not appear to be impacted by the upward gradient as evidenced by the good match of the model to the hydraulic head data, and the randomly positive and negative residuals throughout the Frenchman Flat basin.

Groundwater flow paths in the central testing area are similar to models with the USGSD- and MME-boundary conditions. The groundwater flow path at the northern edge of Frenchman Flat basin appeared to be dominated by eastward advection, as observed for the USGSD- and MME-model calibrations, but flow paths simulated using the DVRFS-boundary conditions indicated water conductance was from the LVTA into the TM-WTA rather than into the LTCU.

Given the consistency in groundwater flow paths generated by both the DVRFS- and MME-boundary conditions in the BASE HFM and CPBA HFM, the variation between these HFMs when they are calibrated using the DRIA boundary conditions is striking. For the CPBA-DRIA alternative, the simulated head in LCA was higher than hydraulic head measured in the overlying alluvium and tuffs at the ER-5-3 well cluster. This indicates an upward head gradient between the alluvium and LCA, contrary to the local data and the conceptual understanding of the Frenchman Flat CAU flow system. For the BASE-DRIA calibration, there is a slight downward gradient in the vicinity of the ER-5-3 well cluster between the alluvium and LCA. Groundwater flow paths simulated by the BASE-DRIA model in the northern testing area are similar to those observed in the BASE-DVRFS alternative. Groundwater flow paths in the central testing area for both the BASE-DRIA and CPBA-DRIA alternatives indicate lateral flow in the alluvium to the southeast.

The alternative approach to boundary head modifications further confirmed the model sensitivity to the assigned boundary conditions. To improve the model simulation of observed heads in the LCA, a hydraulic connection in the volcanic units of the CP and Frenchman Flat basins was established to route the water from areas of higher head (CP basin) into the basin-fill material of the Frenchman Flat basin. Heads on the boundary adjacent to CP basin were modified to greater than 1,000 m to establish and maintain hydraulic heads in the Frenchman Flat basin. Although the calibrated HSU permeabilities and hydraulic head simulations match the data very well, this large change in boundary heads suggests that this connection may not be plausible. Advective particle tracks show a strong eastern component of flow in the northern testing area. Particle trajectories in the central testing area were very similar to those observed in other calibrated flow models. The general orientation of flow paths appears to be within the range of the other calibrated flow models that were used to evaluate either boundary condition, HFM, or discrete uncertainty. Further consideration will be given to this flow model during transport calculations to determine whether the flow field yields different transport behavior within the time of interest given reasonable transport parameters.

Overall, the boundary condition uncertainty analyses indicate that groundwater flow paths in the central testing area are similar among the calibrated flow models, but that the flow paths in the northern testing area are more sensitive to changes in boundary conditions than changes in HFM.

Constant Permeability with Depth Uncertainty Analysis

Reduction in permeability with depth has a sound technical basis. However, uncertainty exists in the implementation of permeability decay with depth and the impact of the permeability changes on the steady-state modeled flow fields for the Frenchman Flat CAU. This uncertainty was addressed by applying a constant, non-depth decayed, permeability to the AA and older alluvial aquifer (OAA) while leaving depth decay in the rest of the model.

The BASE-USGSD model with constant permeability in the AA and OAA has similar flow paths to other models used to bound conceptual model uncertainty of the Frenchman Flat flow system. In the areas near the underground nuclear testing, the model tends to overpredict heads in the LTCU and the LCA, while underpredicting heads at the edges of the basin-fill units. Assessment of radionuclide transport using realistic transport parameters will consider variability in the conceptual model of the flow system provided by this model calibration.

ES-7 PARAMETER SENSITIVITY ANALYSIS

Two approaches to local parameter sensitivity analysis were implemented for the Frenchman Flat flow model. In the first approach, parameter correlations and parameter sensitivity were evaluated using the PEST parameter estimation software. The PEST code calculates a sensitivity coefficient for each parameter with respect to all weighted observations. The second approach involves perturbing each of the parameters over a range, one at a time, from a reference value and computing the corresponding change in the model output.

Parameter Sensitivity Analyses

To describe the degree to which parameters are correlated to one another, PEST computes the correlation coefficient matrix. Because the Frenchman Flat flow model has more than 100 adjustable parameters and fewer than 35 observations, it is not feasible to calculate the full correlations among these parameters. However, some useful information from parameter correlations was calculated for a

limited number of parameters. The selection of parameters is subjective and is mainly guided by the experience gained throughout the model calibration process. Based on this experience, 13 parameters were selected for analysis with PEST.

Parameter Perturbation Analysis

A common metric of model calibration is the goodness-of-fit parameter called the objective function PHI. For the Frenchman Flat flow model, PHI can be divided into two components representing different types of calibration target data. Head measurements at wells are described by the WELL component. The FLUX component represents lateral boundary flow estimates from the regional model(s). In the perturbation analysis, input parameters were systematically increased and decreased while changes in the objective function, heads, and various fluxes were recorded. Parameter perturbation results are presented for five calibrated models:

- BASE HFM with USGSD recharge and boundary conditions (BASE-USGSD)
- BASE HFM with Death Valley Regional Ground-Water Flow System model recharge and boundary conditions (BASE-DVRFS)
- BLFA HFM with USGSD recharge and boundary conditions (BLFA-USGSD)
- DETA HFM with USGSD recharge and boundary conditions (DETA-USGSD)
- CPBA HFM with USGSD recharge and boundary conditions (CPBA-USGSD)

While sensitivity analyses are formally presented for the final calibrated models, such analyses were also carried out as an integral part of the calibration process.

Parameter Sensitivity and Perturbation Results

Three techniques are used to examine the model parameters sensitivity and correlations. The first approach calculated the correlation between a selected set of model parameters. Results show the expected inverse correlation between the LCA permeability and the fault permeability multiplier for the Rock Valley fault system, as these two control the boundary fluxes into and out of the model domain. The correlation analysis also shows the permeability values for the AA and volcanoclastic confining unit (VCU) are positively correlated, while those for the LTCU and Wahmonie confining unit (WCU) are negatively correlated. These results reflect the dependence of model-calculated AA

heads on the difference between the permeability values for the AA and the confining units underlying the AA in the Frenchman Flat basin. The LTCU and WCU are both responsible for maintaining the heads in the AA at the observed levels. These heads are higher than those in the LCA under the basin.

The second approach used for sensitivity analyses provides composite sensitivity results for the model parameters. It also provides target sensitivity values for the available calibration data, which could be thought of as importance measures relative to the flow model calibration. These results show that the most sensitive target is WW-5A. This target well is particularly sensitive to the permeability of the VCU and AA, which reflects the strong positive correlation calculated between these two permeability values. Also shown is the lack of sensitivity of water levels at target wells in the AA to the permeability of the LCA. This illustrates the two semi-independent flow regimes in the AA and the deep LCA as reflected by the model insensitivity to lateral boundary flows.

The third approach used is a perturbation analysis, which is used to examine the sensitivity of model calculations (as measured using a variety of metrics) to the different parameters, which are either varied or fixed during the model calibration. It is important to note the sensitivity of AA and OAA water levels to model parameters. Not surprisingly, these water levels showed considerable sensitivity to the AA permeability for all calibrated models. Other important aquifer permeability values are those for the TM-WTA and Timber Mountain lower vitric tuff aquifer (TM-LVTA). Sensitive aquitard reference permeability is observed for the VCU, WCU, and LTCU.

ES-8 EVALUATION OF GROUNDWATER FLOW PATHS AND TRAVEL TIMES USING ^{14}C AND OTHER GEOCHEMICAL INDICATORS

As a means to independently verify the flow paths generated by the steady-state Frenchman Flat flow model, groundwater carbon-14 (^{14}C) data from water samples from the tuffs and alluvium in Frenchman Flat were used to calculate ages (residence times). The analysis of ^{14}C associated with dissolved inorganic ^{14}C (DI^{14}C) considered the effects of calcite dissolution and isotope exchange on the groundwater DI^{14}C through two simple correction methods that estimated the dilution of ^{14}C originally in the groundwater recharge. The two correction methods yielded estimates of

groundwater ages that were in good agreement for all but one of the wells (ER-5-4 #2). The corrected DI^{14}C ages of Frenchman Flat groundwater ranged from ~ 8,500 years to ~ 29,000 years. These age dates are consistent with the model flow paths that indicate water is moving from the northern and northwestern parts of the basin and flowing toward the basin center and out of the basin center to the southeast. In general, younger groundwater is found near the low hills bordering the northern and northwestern parts of the basin, and older groundwater is found toward the basin center, reflecting the near absence of recharge through the alluvium in the basin even during the relatively wet conditions that existed in the late Pleistocene and early Holocene. The absence of groundwater DI^{14}C ages younger than the early Holocene, even along the basin margins, is consistent with paleo-climate reconstructions based on vegetation preserved in pack-rat middens and on the ages of paleo-discharge deposits that indicate modern-day arid conditions were established in the NTS area by about 9,000 years ago.

The corrected groundwater DI^{14}C ages were compared with groundwater ages calculated from ^{14}C associated with dissolved organic ^{14}C (DO^{14}C), which theoretically do not require adjustments to account for water/rock interactions. The ages of Frenchman Flat groundwater based on DO^{14}C were generally less than half of the corrected ages based on DI^{14}C . Both sets of groundwater ages were evaluated by comparing temporal variations in atmospheric $^{36}\text{Cl}/\text{Cl}$ deposition, as recorded in the groundwater $^{36}\text{Cl}/\text{Cl}$ and the estimated DI^{14}C - and DO^{14}C -based groundwater ages, with terrestrial records of $^{36}\text{Cl}/\text{Cl}$ deposition preserved in pack-rat middens that extend back almost 40,000 years. The temporal variations in groundwater $^{36}\text{Cl}/\text{Cl}$ ratios using the DI^{14}C -based ages were in good agreement with variations in atmospheric $^{36}\text{Cl}/\text{Cl}$ deposition recorded in the pack-rat midden data, whereas similar comparisons showed that the DO^{14}C ages were too young for at least half of the wells for which DO^{14}C data were available.

Past studies of the geochemical evolution of groundwater at the NTS have established that groundwater in contact with tuffs and tuffaceous sediments tends to become enriched in sodium (Na) and depleted in calcium (Ca) and other divalent cations because the tuffs themselves are high in Na and because of cation exchange. These evolutionary trends, as represented in correlations developed between Na and Ca concentrations and corrected DI^{14}C ages, were used to estimate a groundwater age at Well ER-5-4 #2 of 33,000 years and to establish a basis for identifying pairs of wells that were likely to lie along a flow path.

Relative groundwater ages and geochemical evolutionary trends were used to identify pairs of groundwaters that are likely to lie along a common flow path. Inverse geochemical models were created with the geochemical modeling code PHREEQC to confirm that plausible water/rock interactions could be found that would explain the observed chemical differences and thus, that the groundwaters could indeed lie on a specific flow path. These models confirmed that groundwater at Well UE-5 PW-1 could originate by the southerly flow of groundwater from Well UE-5 PW-2, coupled with plausible water/rock interactions. Similar models developed for Well ER-5-4 in the central part of the basin indicate this groundwater could originate from either the southerly flow of groundwater from Well UE-5 PW-1 or the southeastward flow of groundwater from UE-5c WW. Geochemical inverse models for Well ER-5-4 #2 could only explain the composition of this groundwater using both mixing and water/rock interactions. This groundwater appears to originate from a mixture of groundwater from the CP basin and groundwater from northwestern Frenchman Flat, suggesting that this groundwater may have been recharged in the low hills separating these two basins. This result agrees with evidence from hydraulic heads that the groundwater near Well ER-5-4 #2 has a strong hydraulic connection with groundwater in the vicinity of the CP basin.

Groundwater velocities were calculated at pairs of wells in the alluvium that were likely to lie along a flow path based on their relative chemical evolution. Groundwater velocities in the alluvium between well pairs with ^{14}C -based ages ranged between 0.12 meters per year (m/yr) and 0.85 m/yr. A higher groundwater velocity of 1.1 m/yr was estimated for a UE-5 PW-1 to WW-1 flow path, but this velocity is subject to greater uncertainty because it is based on an age for WW-1 groundwater estimated indirectly from its dissolved cation concentrations. An analysis of groundwater travel time for a mixture of groundwaters involving components from the CP basin (Well WW-4) and from Well UE-5c WW indicated a groundwater velocity in the volcanic rocks along the flow path of 0.60 m/yr.

The low rates of groundwater movement estimated for Frenchman Flat basin are consistent with the near absence of recharge to the basin over the last 8,500 years and with the nearly flat water table within the alluvial deposits of the basin. The estimated groundwater velocities in the alluvium calculated from the ^{14}C ages indicate that lateral transport distance of between about 120 to 1,100 m can be expected near the testing areas over the next 1,000 years.

ES-9 SUMMARY AND CONCLUSIONS

The steady-state groundwater flow model described in this report was undertaken to satisfy the groundwater flow model requirement of the *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001).

A 3-D finite-element steady-state groundwater flow model was constructed for the Frenchman Flat CAU. The emphasis of this flow model analysis is not on identification of a unique model and associated parameters. Instead, the approach was to consider conceptual model uncertainties by using different combinations of the hydrostratigraphic framework models, recharge models, hydrologic boundary conditions, and the application of depth decay were considered to propagate the high-level uncertainty associated with each of these model elements into the resulting flow fields. This suite of flow fields provides a spectrum of flow paths from individual underground nuclear tests that will be examined through transport modeling analyses.

The FFACO requires that the contaminant transport model predict the contaminant boundary at 1,000 years and “at a 95% level of confidence” (FFACO, 1996). The Frenchman Flat Phase II flow model described in this report provides, through the flow fields derived from alternative HFMs and boundary conditions, one of the tools required to compute the contaminant boundary. Other components include the simplified source model, which incorporates uncertainty and variability in the factors that control radionuclide release from an underground nuclear test, and the transport model with the associated parameter uncertainty. The synthesis of all this information contributes to the calculation of the final contaminant boundary.

The salient points of the Frenchman Flat setting and hydrostratigraphic framework model are as follows:

- Frenchman Flat is a closed-drainage intermontane basin. The valley floor of the basin slopes gently from the surrounding highlands to a playa at the lowest point in the basin.
- Frenchman Flat was filled with sedimentary and volcanoclastic rocks, followed by ash-fall and ash-flow tuffs and finally alluvial and playa deposits, as it developed. More than 1,400 m of alluvium exists in the center of the basin. The alluvium thins towards and beyond the structural margin of the basin where it directly overlies the LCA. Along the northern, eastern,

and southern margins the tuff confining units that line the basin have been thinned by faulting and erosion, increasing the potential for hydraulic connection between the shallower material and the LCA.

- The geology near Frenchman Flat is structurally complex and diverse and includes: CP basin, the Cane Spring fault, the CP thrust fault, the Wahmonie volcanic center, and an accommodation zone near Massachusetts Mountain separating southern Yucca Flat from Frenchman Flat.
- The present-day water table is deep such that the alluvium and tuffs are unsaturated beyond the faulted margins of the basin, and the alluvial and tuff aquifers in Frenchman Flat are isolated by the LCA from other such aquifers except toward the west.
- Based on geochemical differences and hydraulic head gradients the LCA does not appear to be the source of water in the alluvium (Hershey et al., 2005). Thus, the only possible source of the groundwater in the Frenchman Flat alluvium and tuffs is local recharge and inflow from CP basin or the Wahmonie Hills to the west. Although the Cane Spring fault appears to impede groundwater flow from CP basin to Frenchman Flat (Winograd and Thordarson, 1975), the absence of major basin-bounding faults along the western margin of Frenchman Flat and the monoclinical structure and lateral continuity of the HSUs in the area probably permit some flow into the western part of the Frenchman Flat basin from areas to the west.
- Three conceptual models have been proposed for groundwater flow in Frenchman Flat. These conceptual models are not mutually exclusive. The first conceptual model was proposed by Winograd and Thordarson (1975) and updated by Lacznia et al. (1996). This conceptual model was based on an assumption that water in the AA is semiperched and is characterized by a vertical flow system from the AA to the LCA through an internal outlet in the vicinity of the Frenchman Lake playa or through another local sink. In addition, this conceptual model allowed for the possibility that water moves from the AA to the LCA through slow lateral flow to the basin edge. The second conceptual model suggests flow in the AA is consistent with LCA flow direction going from north to south. This conceptualization is based on regional flow model results, which indicated this flow direction (DOE/NV, 1997), rather than by site-specific data. The third conceptual model suggested that water in CP basin to the west/northwest of Frenchman Flat leaks through the Cane Spring fault into the Frenchman Flat basin (IT, 1999a) and the general flow in the Frenchman Flat basin is from north to south/southeast. This conceptual model is supported by three observations: 1) observed water levels in CP basin are much higher than those in the Frenchman Flat basin, 2) observed water levels in the AA are lower to the south and east of the Frenchman Lake playa, and 3) water levels observed in Well UE-5c WW in the northwest alluvium are greater than those observed in the central or east basin. This conceptual model was chosen as the basis for the Frenchman Flat CAU Phase I flow model (IT, 1999a). The Phase II Frenchman Flat flow model does not make any presumptions regarding which of these three conceptual models is correct, but is designed in a way that allows aspects of all of these conceptual models to be investigated and flow directions to be determined as a result of model calibration.

- Water-level observations and aquifer tests indicate nearly absent vertical hydraulic gradients in the AA, which when combined with effects of depth decay in permeability and the possibility of k_t/k_v ratios much greater than unity indicate that groundwater flow in the AA will be predominantly lateral to the basin margins. Furthermore, the low recharge rates estimated for the basin, and the limited inflow across the Cane Spring fault, suggest that lateral groundwater movement within the basin will be slow.

The hydrostratigraphy of the Frenchman Flat CAU model area was translated into a computational grid using a grid refinement approach that was conditioned to capture the complex geometry of HSUs, structural faults, open intervals of wells, and underground nuclear test cavities. To improve model consistency and efficiency during calibration, a single finite element mesh was created that was flexible enough to allow each HFM to be easily substituted into the flow model. Mesh nodes were spaced with five levels of refinement. Nodes closer to the HSU interfaces and near fault planes had smaller spacing, with node spacing increasing where less detail was necessary to capture HFM and underground nuclear test features.

Calibration of the BASE HFM and USGSD recharge model was undertaken first, and the following observations are made:

- Based on the very good agreement between observed and simulated heads at the ER-5-3 and ER-5-4 well clusters, and the agreement of the observed and model permeabilities that produced the results, there appears to be little potential for downward flow in the alluvium. The field data and model results clearly show that most of the head loss between the alluvial and carbonate aquifer occurs across the thick tuff confining units that line the basin.
- Well ER-5-4 #2, completed in the LTCU, has head of more than 754 m, more than either the alluvial or carbonate aquifers. Thus, the concept of a pressure barrier under the central testing area is feasible. Conceptually this could occur when there are high-permeability units (locally observed in ER-5-4 #2) embedded within the LTCU that are extensive and act as confined aquifers and connect the deep parts of the Frenchman Flat basin with areas of higher head to the west.
- Flow patterns in the northern testing area north of the detachment fault tend to go east or northeast, and south of the detachment fault tend to go south. The complex hydrostratigraphy at the water table in the northern testing area is responsible for this behavior.
- Flow patterns in the southern testing area, where the hydrostratigraphy is considerably simpler than in the north, tend to the southeast.

- Model flow path analysis shows that most of the groundwater in the alluvial and tuff aquifers beneath the testing areas eventually exits the area to the southwest through the Rock Valley fault system in the LCA.
- The Rock Valley fault system is the dominant feature in the LCA, and exerts significant control on the direction of the regional groundwater movement.
- The CP basin fault has little control on lateral fluxes, but pronounced influence on the simulated hydraulic heads. Some small flow from CP basin is necessary to maintain water levels in Frenchman Flat alluvium.
- Embedded HSUs are insensitive in controlling water levels, including the BLFA, PCU1U, PCU1L, and PCU.
- The LCA permeability strongly affect the magnitude and direction of boundary flow, which is expected given the great extent and thickness of the LCA in the area. Water levels in the alluvial and volcanic HSUs were slightly influenced by changes in LCA properties that caused changes in hydraulic gradients. However, the AA is relatively isolated from the LCA.

The foundation of the flow model analysis is the Phase II hydrostratigraphic framework model (HFM) prepared and documented by BN (2005a). To investigate the uncertainty in the BASE HFM, four alternative models were developed to assess the potential impact of alternative geologic interpretations on groundwater flow and the transport of contaminants in groundwater. The alternatives and their observed consequences on the groundwater flow model when calibrated with the USGSD recharge model are as follows:

- The basalt lava flow aquifer (BLFA) alternative increases the lateral continuity of the basalt lava flow aquifer. No changes from the calibrated BASE parameter set were required to calibrate this model; it had very little impact on simulated heads. Flow paths trajectories were very similar to the BASE model in the central testing area, and in the northern testing area.
- The detachment fault (DETA) alternative removes a fault and increases the continuity of several volcanic aquifers. No changes from the calibrated BASE parameter set were required to calibrate this model; it had very little impact on simulated heads. Flow paths trajectories were very similar to the BASE model in the central testing area, and somewhat different in the northern testing area.
- The displacement fault (DISP) alternative juxtaposes shallow AA and volcanic aquifers against the LCA to evaluate the effects of increased hydraulic connections among these units. Modest reduction in fault permeability parameters were required to calibrate this alternative. The calibration demonstrated that a completely open connection between the alluvium and LCA is unrealistic.

- The CP thrust (CPBA) alternative includes an adjustment of the stratigraphy in the northwest corner of the model. This alternative agreed with the calibration data similar to the BASE model, although the BASE model was still superior. Flow path trajectories were generally similar as well, with the exception of that leaving the PIN STRIPE test location in the northern testing area.

Over the area of the Frenchman Flat CAU flow model the head distribution and recharge flows are not extensively known. An additional uncertainty component in the recharge model and associated regional model boundary conditions (see SNJV, 2005b) was also considered for the BASE and CPBA HFM alternatives (the most different HFMs calibrated with the USGSD recharge model). The BASE and CPBA HFMs were calibrated with the DRIA-, MME-, and DVRFS- boundary conditions and recharge models. It was observed that:

- Regardless of recharge model this water-balance component is very small and dominated by lateral regional flow.
- The MME recharge model and boundary conditions produced the most similar results to the BASE-USGSD and CPBA-USGSD. The downward head gradient was matched, with flow directions in the northern testing area to the east, and in the central testing area to the southeast.
- The DVRFS recharge model and boundary conditions were most different from the BASE and CPBA HFMs with the USGSD model. Good overall agreement was obtained, but the LCA head was simulated higher than that in the AA, contrary to the Frenchman Flat field data and conceptual model. Flow paths from the northern and central testing area were still similar to those from the MME recharge model and boundary conditions indicating that the upward gradient had little impact on flow paths.
- When the DRIA recharge model and boundary conditions were applied to the BASE and CPBA alternatives the differences in behavior between the HFMs was striking. For the CPBA HFM the simulated head in LCA was higher than hydraulic head measured in the overlying alluvium and tuffs, contrary to the local data at ER-5-3 #2 and the conceptual understanding of the Frenchman Flat flow system. For the BASE HFM calibration, there is a slight downward gradient in the northern testing area between the alluvium and LCA. Groundwater flow paths simulated by the BASE-DRIA model in the northern testing area are similar to those observed in the BASE-DVRFS model. Groundwater flow paths in the central testing area for both the BASE-DRIA and CPBA-DRIA models indicate lateral flow in the alluvium to the southeast.
- For the BASE-USGSD flow model, an alternative approach to boundary head modifications was investigated in which heads were adjusted on a HSU basis. In the LCA, heads were lowered on all faces of the model to improve the match of modeled heads to measured water

levels at the LCA calibration targets. In the CP basin area, heads were increased only in the tuffs to improve the match of the model to measured water levels at WW-4 and WW-4A. To calibrate both of these boundary condition changes, a hydraulic connection in the volcanic units of CP basin and Frenchman Flat basin was established to route the water from areas of higher head (CP basin) into the basin-fill material of Frenchman Flat basin. This hydraulic connection was implemented by further subdividing the Cane Spring fault and locally increasing the fault permeability. Heads on the boundary adjacent to CP basin were increased to greater than 1,000 m amsl, which is significantly higher than the observed head in these units within CP basin, to establish and maintain hydraulic heads in Frenchman Flat basin. Although the calibrated HSU permeabilities and hydraulic head simulations match the data very well, the required large change in boundary heads suggests that this connection may not be plausible with this HFM configuration. Advective particle tracks show a strong eastern component of flow in the northern testing area. Particle trajectories in the central testing area were very similar to those observed in other calibrated flow models. The general orientation of flow paths appears to be within the range of the other calibrated flow models that were used to evaluate either boundary condition, HFM, or discrete uncertainty.

- Overall, the boundary condition uncertainty analyses indicate that groundwater flow paths in the central testing area are similar among the calibrated flow models, but that the flow paths in the northern testing area are more sensitive to changes in boundary conditions than changes in HFM.

In addition to model uncertainty, there is parametric uncertainty in the model permeabilities. A review of the hydrogeologic literature demonstrates that depth decay in permeability or hydraulic conductivity has been recognized for decades by investigators in many geologic environments and has also been routinely adopted in groundwater modeling studies. For the Frenchman Flat CAU flow model, depth decay was applied to all alluvial, volcanic, and carbonate units. Sufficient data to evaluate depth decay in permeability do not exist for HSUs other than the AA and OAA, and these site-specific data do not clearly support the use of depth decay in the alluvium of Frenchman Flat. Consequently, depth decay in permeability in the alluvium is considered as a conceptual model uncertainty that was investigated by considering an alternative model in which the permeability of the AA and OAA are constant with depth. The results were as follows:

- The model was generally successful in matching the available head data within the constraints of the field-scale permeability data.
- Calibration did require higher values of anisotropy than those used with depth decay in the OAA and AA and similar values for horizontal permeability, nearly eliminating any vertical flow in the shallowest portion of the AA and OAA.

- The BASE-USGSD model with constant permeability in the AA and OAA has similar flow paths to other models used to bound conceptual model uncertainty of the Frenchman Flat flow system. Thus, while there is uncertainty in the applicability of depth decay in the AA and OAA (the HSUs into which most of the underground nuclear test radionuclide source will be applied) as well as the value of the depth decay coefficients, the parameters required to calibrate the flow model in the absence of such effects do not greatly change the direction of groundwater movement.

The steady-state groundwater flow models that were used to assess conceptual model uncertainty of the Frenchman Flat groundwater flow system demonstrated that:

- Groundwater flow near the testing areas is similar in these models despite considerably different hydrostratigraphy, approaches to defining boundary conditions, discrete HSU and fault permeability changes, and methods of model parameterization.
- All of the models evaluated demonstrated that the shallow flow system had lateral migration with only modest vertical flow until particles reached the edges of the basin.
- Upon reaching the edge of the basin, particles moved from the VCU or LTCU into the LCA and exited the flow system through the regional, Rock Valley fault system.
- To maintain higher heads in the basin-fill HSUs, compared to the lower heads present in the LCA, the calibrated head fields showed regions of higher head occurring in the volcanic HSUs. The presence of these high head zones in the volcanic HSUs effectively separates the shallow flow system from the regional flow system.
- Attempts to increase the vertical flow through the center of the basin by both decreasing and eliminating depth decay of permeability demonstrated that vertical flow is unlikely based on the need to increase anisotropy and decrease HSU permeability.
- Additionally, attempts to create a connection between the alluvial and volcanic aquifers and the LCA across a basin-bounding fault in the DISP alternative indicated that this hydrologic connection could not be maintained without a reduction in fault permeability. In this alternative a good match to heads in the area adjacent to Frenchman Lake playa was achieved through a reduction in fault permeability in the basin-fill materials.
- The flow models demonstrated that the AA and OAA of Frenchman Flat basin are fed by water originating in CP basin and the Wahmonie Hills. The proportion of flow from either of these areas is highly uncertain, but through the application of two regional models and several sets of boundary conditions the relative magnitude of water entering the basin from these two areas was varied.
- Overall, conceptual model uncertainty analyses indicate that groundwater flow in Frenchman Flat basin near the northern testing area tends to be north to south or northwest to southeast for

flow paths near NEW POINT, DERRINGER, DIANA MOON, and MINUTE STEAK test locations. Water flows through the OAA and BLFA into the AA and TM-WTA and moves to the southeast until reaching the basin edge. The groundwater flow paths seem to be dominated by the influx of water moving across the Cane Spring fault in the volcanic HSUs and into the basin-fill units along the northwest edge of the Frenchman Flat basin.

- Along the northern edge of the basin, water flows eastward within the TSA and LVTA. These units form an arcuate band of higher permeability where they intersect the water table along the northern flank of the Frenchman Flat basin. This band of higher permeability creates a strong hydraulic connection in the model between the higher hydraulic heads in the CP basin to the west and locations beneath the PIN STRIPE test.
- In the central testing area of Frenchman Flat, groundwater flow is substantially less complex than in the northern testing area. The movement of particles initially located near the water table near the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area will be through the alluvium toward the southeast.

As a means to independently verify the flow paths generated by the Phase II Frenchman Flat CAU flow model, groundwater ^{14}C data from the tuffs and alluvium in Frenchman Flat were used to calculate ages (residence times) for these groundwaters. The calculated DI^{14}C ages of Frenchman Flat groundwater ranged from ~ 8,500 years to ~ 29,000 years. In general, younger groundwater is found near the low hills bordering the northern and northwestern parts of the basin, and older groundwater is found toward the basin center, reflecting the near absence of recharge through the alluvium in the basin even during the relatively wet conditions that existed in the late Pleistocene and early Holocene. The absence of groundwater DI^{14}C ages younger than the early Holocene, even along the basin margins, is consistent with paleo-climate reconstructions based on vegetation preserved in pack-rat middens and on the ages of paleo-discharge deposits in nearby basins that indicate modern-day arid conditions were established in the NTS area by about 9,000 years ago. These age dates are consistent with the model flow paths that indicate water is moving from the northern and northwestern parts of the basin and flowing toward the basin center and out of the basin center to the southeast.

Inverse geochemical models were done with the geochemical modeling code PHREEQC to investigate the origin of groundwater at selected wells within the basin. These models confirmed that groundwater at Well PW-1 could originate by the southerly flow of groundwater from Well PW-2, coupled with plausible water/rock interactions. Similar models done for Well ER-5-4 in the central

part of the basin indicate this groundwater could originate from either the southerly flow of groundwater from Well PW-1 or from a mixture of PW-1 groundwater and groundwater flowing southeast from UE-5c WW. Geochemical inverse models for Well ER-5-4 #2 could only explain the composition of this groundwater using both mixing and water/rock interactions. This groundwater appears to originate from a mixture of groundwater from the CP basin and groundwater from northwestern Frenchman Flat, suggesting that this groundwater may have been recharge in the low hills separating these two basins. This result agrees with evidence from hydraulic heads that the groundwater near Well ER-5-4 #2 has a strong hydraulic connection with groundwater in the vicinity of the CP basin.

Groundwater velocities were calculated at pairs of wells in the alluvium that were likely to lie along a flow path based on their relative chemical evolution. Groundwater velocities were calculated between well pairs with ^{14}C -based ages. Overall, groundwater flow paths between UE-5c WW and ER-5-4 had the largest uncertainty (0.12 to 0.85 m/yr). North-to-south flow paths in the alluvium were between 0.19 to 0.25 m/yr (the PW-1 to ER-5-4 flow path) to 0.43 m/yr (the PW-2 to PW-1 flow path). A higher groundwater velocity of 1.1 m/yr was estimated for a PW-1 to WW-1 flow path, but this velocity is subject to greater uncertainty because it is based on an age for WW-1 groundwater estimated indirectly from its dissolved cation concentrations. An analysis of groundwater travel time for a mixture of groundwaters involving components from the CP basin (Wells WW-4 and WW-4A) and from UE-5c WW indicated that groundwater velocities in the volcanic rocks along the flow path was about 0.6 m/yr.

In summary, groundwater flow paths from the geochemical analysis generally support an overall northwest to southeast flow direction for shallow groundwater in the Frenchman Flat basin. The low rates of groundwater movement estimated for Frenchman Flat basin are consistent with the near absence of recharge to the basin over the last 8,500 years and with the nearly flat water table. The

estimated groundwater velocities in the alluvium indicate that transport distance of between about 100 to 1,000 m can be expected over the next 1,000 years.

1.0 INTRODUCTION

The U.S. Department of Energy (DOE), National Nuclear Security Administration Nevada Site Office (NNSA/NSO) initiated the Underground Test Area (UGTA) Project to assess and evaluate the effects of the underground nuclear weapons tests on groundwater at the Nevada Test Site (NTS) and vicinity. The framework for this evaluation is provided in Appendix VI, Rev. 1 (December 7, 2000) of the *Federal Facility Agreement and Consent Order* (FFACO) (1996). Appendix VI of the FFACO, “Corrective Action Strategy,” describes the processes that will be used to complete corrective actions including those in the UGTA Project. The objective of the strategy is to analyze and evaluate each UGTA corrective action unit (CAU) through a combination of data collection and evaluation, and modeling groundwater flow and contaminant transport. [Section 1.3](#) of this report provides a summary of the FFACO corrective action process and the UGTA corrective action strategy.

The Draft Phase I CAU models (flow and transport) for Frenchman Flat were completed and subjected to a DOE review (see [Section 1.5](#)). As a result of this review, additional corrective action investigation (CAI) work including new data acquisition and modeling was identified. These new work elements are documented in the *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001). Based on the evaluation of the new data and information collected and analyzed as a result of this Corrective Action Investigation Plan (CAIP) addendum, the decision was made to archive the Phase I Frenchman Flat CAU flow and transport models, and develop new Phase II CAU models. This report documents the development and implementation of the Phase II Frenchman Flat steady-state groundwater flow model. The development of the Phase II Frenchman Flat contaminant transport model will be documented in a future report.

1.1 Purpose and Scope

The Phase II Frenchman Flat groundwater flow model is a key element in the FFACO (1996) corrective action strategy for the UGTA Frenchman Flat CAU. The objective of this integrated

process is to provide an estimate of the vertical and horizontal extent of contaminant migration for each CAU to predict contaminant boundaries. A contaminant boundary is the model-predicted perimeter that defines the extent of radionuclide-contaminated groundwater from underground testing above background conditions exceeding the *Safe Drinking Water Act* (SDWA) standards. The contaminant boundary will be composed of both a perimeter boundary and a lower hydrostratigraphic unit (HSU) boundary. The computer model will predict the location of this boundary within 1,000 years and must do so at a 95 percent level of confidence. Additional results showing contaminant concentrations and the location of the contaminant boundary at selected times will also be presented. These times may include the verification period, the end of the five-year proof-of-concept period, as well as other times that are of specific interest.

This report documents the development and implementation of the groundwater flow model for the Frenchman Flat CAU. Specific objectives of the Phase II Frenchman Flat flow model are to:

- Incorporate pertinent information and lessons learned from the Phase I Frenchman Flat CAU models.
- Develop a three-dimensional (3-D), mathematical flow model that incorporates the important physical features of the flow system and honors CAU-specific data and information.
- Simulate the steady-state groundwater flow system to determine the direction and magnitude of groundwater fluxes based on calibration to Frenchman Flat hydrogeologic data.
- Quantify the uncertainty in the direction and magnitude of groundwater flow due to uncertainty in parameter values and alternative component conceptual models (e.g., geology, boundary flux, and recharge).

Figure 1-1 is an area map of the NTS showing the location of the Frenchman Flat CAU and the hydrologic model area. This area was selected to define the regional groundwater flow system of the Lower Carbonate Aquifer (LCA) in the vicinity of Frenchman Flat. The Frenchman Flat model area has a north-south dimension of 30 kilometers (km) and an east-west dimension of 19 km, and it encompasses more than 570 square kilometers (km²) in the southeastern portion of the NTS (BN, 2005a).

Figure 1-1
Location of the Frenchman Flat Model Area

1.2 Project Participants

The UGTA Project is a component of the NNSA/NSO Environmental Restoration Program. UGTA technical work is completed by project participants from Bechtel Nevada (BN), the Desert Research Institute (DRI), Lawrence Livermore National Laboratory (LLNL), Los Alamos National Laboratory (LANL), the Stoller-Navarro Joint Venture (SNJV), and the U.S. Geological Survey (USGS). The NNSA/NSO established a Technical Working Group (TWG) to provide expert technical support to plan, guide, and monitor UGTA technical work, and serve as internal peer reviewers of UGTA products. The TWG consists of technical experts from the participating organizations.

1.3 Summary of the Federal Facility Agreement and Consent Order

Since 1996, the Nevada Division of Environmental Protection (NDEP) has regulated the NNSA/NSO NTS corrective action program through the FFACO (1996). The processes that will be used to complete corrective actions are described in the FFACO Appendix VI, Rev. 1 (December 7, 2000), “Corrective Action Strategy”; the UGTA corrective action strategy is described in FFACO Appendix VI, Section 3.0. The FFACO revision provides the current regulatory guidance on the UGTA corrective action strategy, which is incorporated into this document. All references to the FFACO or its appendices in this document will refer to the FFACO as a whole (i.e., FFACO, 1996).

For the UGTA Project, the corrective action strategy includes two major phases: a regional evaluation addressing all CAUs and a CAI process for each of the individual CAUs. The first major phase was completed with the development of the *Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada* (DOE/NV, 1997). The flow and transport model provided the initial basis for determining the magnitude of risk from the source areas on the NTS to potential receptors and a regional context for future individual CAU investigations. The second phase of the CAI process focuses on refining the results of the regional-scale modeling through acquisition and analysis of CAU-specific data, and development of CAU-scale flow and transport models. The CAU-specific objectives are to estimate movement of contaminants utilizing CAU-specific hydrogeologic and transport parameter data and to define boundaries that encompass the extent of contamination.

Figure 1-2 shows the process flow diagram for implementing the corrective action strategy for the UGTA CAUs. The shaded black portion of the diagram illustrates the portion of the process that has been completed as part of the Frenchman Flat CAI.

The CAI process may be iterative, resulting in several phases of data collection, analysis, and modeling with assessment of confidence in the results at the completion of each phase. If further data collection, analysis, and modeling are required, a CAIP addendum will be issued to direct the new phase of activities.

1.4 Frenchman Flat Background

Frenchman Flat is a closed-drainage intermontane basin located in the southeastern portion of the NTS. It is bounded on the north by Massachusetts Mountain and the Halfpint Range, on the east by the Ranger Mountains and Buried Hills, on the south by the Spotted Range, and on the west by the Wahmonie Hills (Figure 1-3). The valley floor of the basin slopes gently from the surrounding highlands to a low-lying playa area. Ground elevations range from over 1,463 meters (m) in the surrounding mountains to approximately 938 m at Frenchman Lake Playa (BN, 2005a).

The climate of Frenchman Flat is typical of southern Nevada, characterized by limited precipitation and large diurnal changes in temperature. In the higher elevations surrounding the basin, annual precipitation is approximately 25 centimeters (cm), which includes winter snow accumulation (French, 1986). The lower elevations that make up the major portion of the CAU receive approximately 10 cm of precipitation annually, including occasional snow accumulations lasting only a few days (BN, 2005a). Daily temperatures range from a minimum of minus 5 degrees Celsius (°C) in winter to a maximum of 45°C in summer.

The conceptual model of groundwater flow through Frenchman Flat is that the bulk of the flow occurs in the LCA, and that the LCA is the only subsurface pathway by which groundwater enters and exits Frenchman Flat beneath the volcanic and basin-fill materials (Laczniak et al., 1996). A map showing the features of the UGTA regional groundwater flow system is present in (Figure 1-4). A minor amount of water may leak from the alluvial aquifer (AA) through the volcanic confining units, which overlie the LCA over much of Frenchman Flat (Laczniak et al., 1996). Thus, the AA flow system, in which testing was conducted, is semi-independent from the regional LCA system.

Figure 1-2
Process Flow Diagram for the Underground Test Area Corrective Action Units

Figure 1-4
Features of the UGTA Regional Groundwater Flow System

The DOE and the U.S. Department of Defense used Frenchman Flat for underground nuclear testing for seven years. Underground nuclear testing on Frenchman Flat began with Operation Whetstone and ended with Operation Grommet (DOE/NV, 2000). The underground nuclear tests conducted in Frenchman Flat were detonated in vertical shafts or drill holes in alluvial and volcanic rock.

Table 1-1 presents information relative to these 10 underground nuclear tests. Five of the tests were detonated in Area 5, and five were detonated in Area 11 (Figure 1-5). All but two underground nuclear tests conducted in Frenchman Flat had yield ranges specified as less than 20 kilotons (kt) (DOE/NV, 2000). Media contaminated by the underground nuclear tests on Frenchman Flat are geologic formations in the saturated zone. For this model, tests are considered to have been conducted in the saturated zone if they were located deeper than 100 m above the water table. Transport in groundwater is the primary mechanism of migration for the subsurface contamination away from the Frenchman Flat underground nuclear tests.

1.5 Summary of Phase I Frenchman Flat CAI Documentation

The Phase I Frenchman Flat CAI, completed in 1999, included hydrologic and transport data compilation, analysis, and model development. Following the Phase I CAI, comprehensive internal and external peer reviews were conducted. These reviews were evaluated to identify additional work scope (including new data collection and modeling activities), and an addendum to the Frenchman Flat CAIP (DOE/NV, 1999) was developed. The *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001) details the new data collection and modeling activities to address the documented deficiencies in the Phase I Frenchman Flat CAI. The new data collection activities identified in the Frenchman Flat Addendum have been completed. The data and analyses from the Phase I CAI and from the additional work are integrated into the Phase II Frenchman Flat flow model, which is the subject of this document.

The external peer review is documented in *External Peer Review Group Report on Frenchman Flat Data Analysis and Modeling Task, Underground Test Area Project* (IT, 1999a). The peer review document identified key issues of concern and made recommendations for addressing the key concerns. Recommendations included identifying general and specific data enhancement and data acquisition needs; incorporating alternative conceptual models to evaluate potential contaminant

Figure 1-5
Location of Underground Nuclear Tests in Frenchman Flat

Table 1-1
Corrective Action Sites in the Frenchman Flat Corrective Action Unit

Test Name	CAS Number	Date	Hole Name	UTM Zone 11, NAD 27 (m)	Yield Range (kt)	Hole Depth (m)	Working Point Depth (m)	Working Point HSU	Model ^a HSU	Surface Elevation (m)	Bottom of Hole Elevation (m amsl)
CAMBRIC	05-57-003	05/14/1965	U5e	E 592142.7 N 4075575.4	0.75	305	295	AA	AA	956	651
DERRINGER	05-57-004	09/12/1966	U5i	E 593518.3 N 4081415.4	7.8	648	255	OAA	OAA	1,040	392
DIAGONAL LINE	11-57-005	11/24/1971	U11g	E 594939.1 N 4081801.6	<20	277	264	OAA	OAA	1,038	761
DIANA MOON	11-57-003	08/27/1968	U11e	E 595265.3 N 4081581.8	<20	255	242	OAA	OAA	1,032	777
DILUTED WATERS	05-57-002	06/16/1965	U5b	E 593110.1 N 4074993.9	<20	206	193	AA	OAA	943	737
MILK SHAKE	05-57-005	03/25/1968	U5k	E 595267.2 N 4080972.3	<20	276	265	OAA	BLFA	1,021	745
NEW POINT	11-57-002	12/13/1966	U11c	E 594655.9 N 4081579.7	<20	255	239	OAA	OAA	1,030	775
MINUTE STEAK	11-57-004	09/12/1969	U11f	E 595494.8 N 4081584.4	<20	277	265	OAA	OAA	1,034	757
WISHBONE	05-57-001	02/18/1965	U5a	E 593719.6 N 4074996.1	<20	191	175	AA	AA	941	750
PIN STRIPE	11-57-001	04/25/1966	U11b	E 594386.2 N 4082708.0	<20	299	296	TM-LVTA	TM-LVTA	1,093	794

Source: Modified from SNJV, 2004d

^aModel HSU is the HSU immediately below the test at the water table if the test was conducted above the water table or the working point HSU if detonated below the water table.

AA = Alluvial Aquifer
amsl = Above mean sea level
BLFA = Basalt Lava Flow Aquifer
CAS = Corrective Action Site
NAD = North American Datum
OAA = Older Altered Alluvial Aquifer

TM-LVTA = Timber Mountain Lower Vitric Tuff Aquifer
UTM = Universal Transverse Mercator

migration scenarios; changing the modeling approach to one that uses a finite-element code to better address discrete geologic features (e.g., faults and fracture zones); and developing and applying local-scale uncertainty analysis techniques.

The internal peer review is documented in *Lessons Learned from the Frenchman Flat Corrective Action Groundwater Flow and Radionuclide Transport Model* (IT, 2000), which concluded that the Phase I Frenchman Flat CAU model was a good first model of groundwater flow and radionuclide transport at the CAU scale. The modeling successfully represented the flow system as defined in the conceptual model and predicted limited radionuclide travel distances. However, the work was not complete and, as recommended by the external and internal peer reviews, needed refinement. Identified deficiencies included lack of alternative models, insufficient grid resolution near underground nuclear tests, inadequate testing of model assumptions, and insufficient documentation of parameter uncertainty. Recommendations to address these issues were provided.

1.6 Major Documents Supporting the Phase II Frenchman Flat Flow Model

The Phase II Frenchman Flat groundwater flow model is supported by a number of major reports that describe a series of data analysis and modeling tasks. [Table 1-2](#) summarizes the groundwater flow model supporting reports and identifies their contribution to the development of the Frenchman Flat flow model.

Phase II data collection activities included well drilling, geophysical investigations, and hydrogeologic and geochemical investigations. The Phase II exploration data significantly improved the understanding of local thicknesses for alluvial and volcanic HSUs in the vicinity of the underground tests, assisted in the identification of alternative geologic framework models for the Frenchman Flat basin, increased the hydrogeologic parameter database for Frenchman Flat, and provided geochemical data for use in testing alternative conceptual models for flow in the basin.

Table 1-2
Major Supporting Documents
 (Page 1 of 4)

Report	Report Synopsis	Contribution to Flow Model
<i>Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada</i> (DOE/NV, 1997)	This report provides an initial estimate of the magnitude of risk from various underground nuclear tests on the NTS to potential downgradient receptors such as the public and the environment from possible groundwater contamination. The regional evaluation consists of data analysis, model development, and model predictions. Results of the regional evaluation of groundwater flow, tritium migration, and risk assessment performed for the underground test areas are presented in this report. The regional evaluation was used during the planning of the Frenchman Flat CAI and is the basis for the development of the CAU conceptual model.	<ul style="list-style-type: none"> • Conceptual model • Regional model framework • Boundary fluxes
<i>Value of Information Analysis for Corrective Action Unit No. 98: Frenchman Flat</i> (IT, 1997b)	This report compares the cost of acquiring new information during the Phase I CAI for Frenchman Flat with the benefit of the information acquisition. This analysis evaluates the value of selected data collection activities and analysis options in reducing uncertainty in the predicted size and location of the contaminant boundary.	<ul style="list-style-type: none"> • Identify major data needs
<i>Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada</i> (DOE/NV, 1999)	This report documents the Phase I Frenchman Flat investigation plan, which included a compilation and evaluation of existing pertinent geologic and hydrogeologic information and data to refine the conceptual model of groundwater flow and contaminant transport underlying the Frenchman Flat CAU. In addition, it specified the development and use of a 3-D, numerical, CAU-scale groundwater flow and transport model to predict the location of the contaminant boundary.	<ul style="list-style-type: none"> • Phase I data collection plan
<i>Evaluation of the Hydrologic Source Term from Underground Nuclear Tests in Frenchman Flat at the Nevada Test Site: The CAMBRIC Test</i> (Tompson et al., 1999)	This report presents the Phase I hydrologic source term model for use in the transport model for Frenchman Flat.	<ul style="list-style-type: none"> • Detailed information about the CAMBRIC test
<i>Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada</i> (NNSA/NV, 2001)	This report proposes additional work scope including new data collection and modeling for the Frenchman Flat CAU in response to comments resulting from the DOE review of the draft Frenchman Flat model of groundwater flow and contaminant transport completed in April 1999.	<ul style="list-style-type: none"> • New data collection plan • Local groundwater flow model plan • Transport model supported by a source-term model plan

Table 1-2
Major Supporting Documents
 (Page 2 of 4)

Report	Report Synopsis	Contribution to Flow Model
<i>Addendum to the Frenchman Flat Hydrogeologic Investigation Wells Drilling and Completion Criteria</i> (IT, 2001a)	This addendum contains two appendices. Appendix B presents the change from one well to two wells at the central Frenchman Flat location. Appendix D documents additional work performed at Well Cluster ER-5-3.	<ul style="list-style-type: none"> • New data collection plan
<i>Analysis of Water Levels in the Frenchman Flat Area, Nevada Test Site</i> (Bright et al., 2001)	This report provides information on the accuracy of hydraulic-head calculations, temporal water-level trends, and potential causes of water level fluctuations. Moreover, it points out the importance of accurate hydraulic heads in Frenchman Flat where the hydraulic gradients are relatively flat (less than 1 foot per mile) in the AA.	<ul style="list-style-type: none"> • Supplement water-level targets for flow model calibration
<i>Geochemically Calibrated Discrete-State Cell Model of the Frenchman Flat Hydrographic Area</i> (Hershey et al., 2001)	This report discusses a geochemically calibrated discrete-state cell (DSC) model using groundwater chemistry, isotopes, and hydraulic head data to test three different flow scenarios in Frenchman Flat.	<ul style="list-style-type: none"> • Flow paths derived from geochemical and isotopic data • Geochemically calibrated DSC model • Hydraulic head data for calibration
<i>Modeling Approach for Corrective Unit 98, Frenchman Flat</i> (IT, 2001b)	This report summarizes the data and information that are the technical basis for the groundwater flow model. Two approaches are described that propose developing the models to forecast how the hydrogeologic system, which includes the underground test cavities, will behave over time. One approach is the development of numerical process models to represent the processes that influence flow and transport. The other approach shows how simplified representations of the process models are utilized to assess the interactions between model predictions and parameter uncertainty.	<ul style="list-style-type: none"> • Code selection • Overall approach
<i>Alluvial Layering and Distribution of Reactive Phases within Drill Holes ER-5-4 and UE-5n of Frenchman Flat</i> (Warren et al., 2002)	This report presents an analysis of the geologic history of the alluvial deposition into the Frenchman Flat basin.	<ul style="list-style-type: none"> • Hydrostratigraphic framework model (HFM)

Table 1-2
Major Supporting Documents
 (Page 3 of 4)

Report	Report Synopsis	Contribution to Flow Model
<i>Death Valley Regional Ground-Water Flow System, Nevada and California—Hydrogeologic Framework and Transient Ground-Water Flow Model</i> (Belcher et al., 2004)	This report discusses the development of a 3-D transient groundwater flow model of the Death Valley region. This 3-D digital HFM was developed from digital elevation models, geologic maps, borehole information, geologic and hydrogeologic cross sections, and other 3-D models to represent the geometry of the hydrogeologic units (HGU). Faults and fractures that affect groundwater flow are also included.	<ul style="list-style-type: none"> • New regional model framework • Death Valley groundwater flow system
<i>Integrated Analysis Report for Single- and Multiple-Well Aquifer Testing at Frenchman Flat Well Cluster RNM-2s, Nevada Test Site, Nevada</i> (SNJV, 2004b)	This report presents the analysis and interpretation of hydraulic data from the Well ER-5-4 single-well test, the Well ER-5-4 #2 single-well test, and the Well Cluster RNM-2S multiple-well aquifer test, which included the ER-5-4 well and others.	<ul style="list-style-type: none"> • Hydraulic head data for calibration • Hydraulic properties data
<i>Interpretation of Hydraulic Test and Multiple-Well Aquifer Test Data at Frenchman Flat Well Cluster ER-5-3</i> (SNJV, 2004c)	This report documents the analysis of the hydraulic data collected for Wells ER-5-3, ER-5-3 #2, and ER-5-3 #3.	<ul style="list-style-type: none"> • Hydraulic head data for calibration • Hydraulic properties data
<i>Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada</i> (SNJV, 2004d)	This Phase II report describes an assessment of hydrologic data and information in support of the CAU groundwater flow model. Relevant information, existing data, and newly acquired data were analyzed for the hydrologic components of the groundwater flow system of Frenchman Flat and vicinity.	<ul style="list-style-type: none"> • Hydraulic head data for calibration • Hydraulic properties data • Discharge due to pumping • Boundary fluxes • Recharge models • Flow paths derived from geochemical analysis
<i>Transferability of Data Related to the Underground Test Area Project, Nevada Test Site, Nye County, Nevada</i> (SNJV, 2004e)	This report describes the overall data transfer process, and a procedure for determining whether data from other locations can be used by the UGTA Project to predict the transport of radionuclides.	<ul style="list-style-type: none"> • Parameter descriptions • Data transfer protocols
<i>A Hydrostratigraphic Framework Model and Alternatives for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Clark, Lincoln and Nye Counties, Nevada</i> (BN, 2005a)	This Phase II report presents the evaluation of geologic data and the resulting 3-D HFM. The framework was built utilizing a collection of stratigraphic, lithologic, and alteration data; a structural model; and results of geophysical, geological, and hydrological studies to formulate the hydrostratigraphic system.	<ul style="list-style-type: none"> • HFM • Alternative HFMs • HSU definition and description • Faults definition and geometry

Table 1-2
Major Supporting Documents
 (Page 4 of 4)

Report	Report Synopsis	Contribution to Flow Model
<i>A Preliminary Investigation of the Structure of Southern Yucca Flat, Massachusetts Mountain, and CP Basin, Nevada Test Site, Nevada, Based on Geophysical Modeling</i> (Phelps et al., 2005)	Additional gravity data were collected in the northwest Frenchman Flat area. These data better defined CP basin and the Cane Spring fault.	<ul style="list-style-type: none"> • HFM • Alternative HFM • Fault definition and geometry
<i>Evaluation of Groundwater Movement in the Frenchman Flat CAU Using Geochemical and Isotopic Analysis</i> (Hershey et al., 2005)	This report presents an evaluation of geochemical and environmental isotopic data to test two potential pathways for radionuclide transport via groundwater flow paths and out of Frenchman Flat.	<ul style="list-style-type: none"> • Conceptual flow path model • Flow paths derived from geochemical analysis
<i>Phase II Contaminant Transport Parameters for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada</i> (SNJV, 2005a)	This Phase II report documents pertinent transport data and data analyses to provide the primary reference to support parameterization of the Phase II Frenchman Flat CAU transport model.	<ul style="list-style-type: none"> • Effective porosity

1.7 Report Organization

This report is organized as follows:

[Section 1.0](#) provides a description of the purpose and scope of this report, a summary of the FFACO corrective action strategy, a short background summary of the physical characteristics and test history of the Frenchman Flat area, and a description of the documentation supporting this report.

[Section 2.0](#) reviews the previous models of the Frenchman Flat area.

[Section 3.0](#) is the conceptual model of groundwater flow that describes the underlying data and controls on the flow system. The numerical models of groundwater flow were constructed to replicate this conceptual model.

[Section 4.0](#) explains the groundwater flow model construction and demonstrates how the model was converted into its numerical representation.

[Section 5.0](#) describes the purpose of calibration and the calibration protocol, the use of parameter estimation software (PEST), and how parameter sensitivities and constraint of flow paths were utilized.

[Section 6.0](#) is the flow model uncertainty analysis.

[Section 7.0](#) is the flow model parameter sensitivity analysis.

[Section 8.0](#) evaluates groundwater flow paths and travel times in Frenchman Flat using carbon-14 (^{14}C) and other geochemical indicators.

[Section 9.0](#) is the summary and conclusions.

[Section 10.0](#) contains the reference list.

[Appendix A](#) provides the Analysis of New Water-Level and Ground-Surface Elevation Measurements for Frenchman Flat Relative to the Phase II Frenchman Flat Hydrologic Data Document.

[Appendix B](#) provides a literature review of other groundwater modeling efforts that have included a decay in hydraulic conductivity with depth in the flow system.

[Appendix C](#) presents the perturbation sensitivity analysis plots.

[Appendix D](#) presents fault locations.

[Appendix E](#) presents values for hydraulic properties for the saturated media in the NTS area.

2.0 PREVIOUS WORK

The development of a CAU-scale groundwater flow model for Frenchman Flat is a key element of the FFACO (1996) corrective action strategy. The CAU model, in its entirety, is a group of interdependent models (NNSA/NV, 2001). The flow model incorporates data related to multiple component models (e.g., geologic, recharge, groundwater flow) of the Frenchman Flat hydrogeologic system. This section presents the component models and other supporting analyses that contribute to the CAU-scale groundwater flow model.

Figure 2-1 summarizes the regional and site-specific elements that are integrated into the Frenchman Flat flow model. These elements include:

- Regional data and models that provide the broad hydrogeologic context for the CAU-specific flow model
- CAU-specific geologic data and models that establish the local hydrostratigraphic framework within which groundwater flows
- Alternative CAU-specific models that address uncertainty in hydrostratigraphy, lateral boundary flux and heads, and recharge
- CAU-specific hydrologic parameters (including their uncertainty)

The models presented in this overview represent a large body of work (Table 1-2) and are described in more detail in the integrating report *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada* (SNJV, 2004d).

Figure 2-1
Information Flow into the Frenchman Flat Groundwater Flow Model

2.1 Regional Models

2.1.1 Underground Test Area Regional Groundwater Flow Model

The Frenchman Flat flow system is part of the Death Valley flow system (Figure 1-4). A conceptual steady-state numerical model of the regional groundwater flow system was developed during the regional evaluation (DOE/NV, 1997). Summary descriptions of the UGTA regional hydrogeologic framework, and groundwater occurrence and movement (as conceptualized in the UGTA regional flow model [DOE/NV, 1997]), are presented in this section. This information has been updated, where appropriate, with information from the Frenchman Flat Phase II data collection and analysis activities.

2.1.1.1 Regional Hydrogeologic Framework

The hydrogeologic framework used in the UGTA regional flow model (DOE/NV, 1997) was based on the conceptual hydrologic system established for the NTS area by Winograd and Thordarson (1975) and Blankennagel and Weir (1973). This early work was summarized and updated by Laczniaik et al. (1996), and was further developed and refined (IT, 1996d and 1998).

For this model, the rocks of the NTS were classified using a two-level classification scheme in which HGUs are grouped to form HSUs (IT, 1996d). The HGUs were used to categorize rocks according to their ability to transmit groundwater, which is mainly a function of the primary lithologic properties of the formations, degree of fracturing, and secondary mineral alteration. The complex hydrologic properties of the volcanic rocks of the NTS and vicinity are best addressed in terms of HGUs (Blankennagel and Weir, 1973; Winograd and Thordarson, 1975). Hydrostratigraphic units are groupings of contiguous stratigraphic units that have a particular hydrogeologic character, such as an aquifer (unit through which water moves readily) or a confining unit (unit that generally impedes water movement). An HSU may contain several HGUs but is defined so that a single type of HGU dominates (for example, mostly welded tuff and vitric tuff aquifers, or mostly tuff confining units [TCUs]). The HSUs are developed into a 3-D, solid-body model that serves to define hydrogeologic model properties in the UGTA regional and CAU-scale HFMs. The methodology used to group the stratigraphic units into HSUs is documented in the *Regional Geologic Model Documentation Package* (IT, 1996d).

Geologic formations of hydrologic significance in the subsurface of the NTS region have been grouped into 10 main HGUs by Winograd and Thordarson (1975). The HGUs in the UGTA regional model that occur in the Frenchman Flat model area are summarized in [Table 2-1](#).

Table 2-1
Hydrogeologic Units of the UGTA Regional Model That Occur in the Frenchman Flat Model Area

Hydrogeologic Unit	Typical Lithologies	Hydrologic Significance
Alluvial Aquifer (AA) (AA is also an HSU in hydrogeologic models)	Unconsolidated to partially consolidated gravelly sand, aeolian sand, and colluvium; thin, basalt flows of limited extent	Has characteristics of a highly conductive aquifer, but less so where lenses of clay-rich paleocolluvium or playa deposits are present.
Welded Tuff Aquifer (WTA)	Welded ash-flow tuff, vitric to devitrified	Degree of welding greatly affects interstitial porosity (less porosity as degree of welding increases) and permeability (greater fracture permeability as degree of welding increases).
Vitric Tuff Aquifer (VTA)	Bedded tuff, ash-fall and reworked tuff; vitric	Constitutes a volumetrically minor HGU; generally does not extend far below the static water level due to the tendency of tuffs to become zeolitic (which drastically reduces permeability) under saturated conditions; significant interstitial porosity (20 to 40 percent); generally insignificant fracture permeability.
Lava Flow Aquifer (LFA)	Rhyolite and basalt lava flows; includes flow breccias (commonly at base) and pumiceous zones (commonly at top)	Generally a caldera-filling unit and/or of local extent; hydrologically complex; wide range of transmissivities; fracture density and interstitial porosity differ with lithologic variations.
Tuff Confining Unit (TCU)	Zeolitic bedded tuff with interbedded, but less significant, zeolitic, nonwelded to partially welded ash-flow tuff	May be saturated but measured transmissivities are very low; may cause accumulation of perched and/or semi-perched water in overlying units.
Clastic Confining Unit (CCU)	Argillite, siltstone, quartzite	Clay-rich rocks are relatively impermeable; more siliceous rocks are fractured, but with fracture porosity generally sealed due to secondary mineralization.
Carbonate Aquifer (CA)	Dolomite, limestone	Transmissivity values vary greatly and are directly dependent on fracture frequency.

Source: Adapted from IT, 1996d, and BN, 2005a

During the regional evaluation (DOE/NV, 1997), the HFM of the UGTA regional groundwater flow system was subdivided into nine HSUs in the Frenchman Flat area. [Table 2-2](#) summarizes the HSUs in the UGTA regional model that occur in the Frenchman Flat model area (IT, 1996d).

2.1.1.2 Groundwater Occurrence and Movement

Within the NTS region, groundwater occurs in alluvial, volcanic, and carbonate materials. Saturated alluvial materials are present in central and southern Yucca Flat, Frenchman Flat, and Jackass Flats on the NTS and in the basins located throughout the flow system. Saturated Tertiary volcanics are present in the western section of the region. The distribution and thickness of alluvial and volcanic aquifers are highly variable throughout the region and are not interpreted to be continuous. In most instances, an AA is confined to a basin by surrounding mountain ranges. In some basins, AAs are discontinuous aquifers due to structural controls elevating the bottom of the alluvium above the water table. In general, alluvial and volcanic aquifers are considered to be depositional elements overlying the regional flow system and only influence regional flow in localized areas. The underlying LCA is the principal aquifer of the Death Valley regional flow system. The LCA forms a nearly continuous aquifer across the region except where interrupted by calderas, truncated by structural controls, or penetrated by intrusive rocks.

An interesting feature of the hydraulic conductivity compiled for the region was that a linear trend was found showing a decrease in hydraulic conductivity (on a log scale) with increased depth below land surface. The data, however, displayed a significant level of scatter.

Based on the water-level dataset compiled during the regional evaluation (IT, 1996c; DOE/NV, 1997), depths to groundwater beneath the NTS and surrounding region vary greatly. Groundwater depths in the southern NTS range from about 23 m beneath upper Fortymile Wash to more than 213 m beneath Frenchman Flat, compared to more than 610 m beneath Pahute Mesa in the northern NTS (IT, 1996c; DOE/NV, 1997). Perched groundwater is found locally throughout the NTS and occurs within the TCUs and, to some extent, overlying units. In the highlands, springs emerge from perched groundwater lenses. Spring discharge rates are low, and this water is used only by wildlife.

Table 2-2
Hydrostratigraphic Units of the Frenchman Flat Area Included
in the UGTA Regional Hydrostratigraphic Framework Model

Hydrostratigraphic Unit (Symbol)	Dominant Hydrogeologic Unit(s) ^a	General Description
Alluvial Aquifer (AA) (this term is also used to designate a hydrogeologic unit)	AA	Consists mainly of alluvium that fills extensional basins such as Gold Flat, Crater Flat, Kawich Valley, and Sarcobatus Flat. Also includes generally older Tertiary gravels, tuffaceous sediments, and nonwelded tuffs (where thin) that partially fill other basins such as Oasis Valley and the moat of the Timber Mountain caldera complex.
Timber Mountain Aquifer (TMA)	Mostly WTA, minor VTA; TCU within the Timber Mountain caldera complex	The uppermost welded tuffs in the Frenchman Flat model area consists mainly of extra-caldera welded ash-flow tuffs (aquifer-like lithologies). However, the altered intra-caldera equivalent rocks within the Timber Mountain caldera are modeled as confining units.
Tuff Confining Unit (TCU)	TCU	Mostly zeolitized nonwelded tuffs.
Volcanic Aquifer (VA)	WTA, VTA, LFA	Imprecisely known grouping of volcanic rocks; generally with aquifer-like qualities. Also used as a lumping unit away from the more data-rich NTS.
Volcaniclastic Confining Unit (VCU)	TCU, minor AA, lesser CA	Complex 3-D distribution of zeolitic nonwelded tuff, gravels, mudstones, and limestones. Present in the southern portion of the Frenchman Flat model area.
Volcanics undifferentiated (VU)	WTA, TCU, lesser LFA	All Quaternary and Tertiary volcanics outside the NTS proper and the proximal NTS caldera complex.
Upper Clastic Confining Unit (UCCU)	CCU	Late Devonian through Mississippian siliciclastic rocks. Present in the northeastern corner (CP basin) of the Frenchman Flat model area.
Lower Carbonate Aquifer (LCA)	CA	Cambrian through Devonian mostly limestone and dolomite. Widespread throughout the Frenchman Flat model area.
Lower Clastic Confining Unit (LCCU)	CCU	Late Proterozoic through Early Cambrian siliciclastic rocks. Widespread throughout the Frenchman Flat model area.

^aSee Table 2-1 for definitions of HGUs

The general direction of groundwater flow in the UGTA regional flow system is from north to south and east to southwest ([Figure 1-4](#)). The direction of groundwater flow is locally influenced in areas where structural and geologic conditions have controlled the distribution and thickness of the LCA. In some areas of the UGTA regional flow system, groundwater encounters structural and geologic conditions, such as structural highs of the LCCU, that promote an upward flow component. The upward flow component brings water to discharge at the surface in the form of a wet playa or spring (not observed at Frenchman Lake). Groundwater flow between basins occurs in the form of subsurface inflow and outflow.

Horizontal hydraulic gradients are very low to the east and south of the NTS. In other areas, the prevailing flow direction and hydraulic gradients may locally be influenced by the structural position of geologic units with significantly lower transmissivity than that of the LCA. If the low-transmissive units are structurally oriented so that they are perpendicular to flow, flow might be significantly altered, causing large hydraulic gradients. If their structural orientation is parallel to the prevailing flow direction, their effect may be insignificant. Structural uplifts of the LCCU and the distribution of the UCCU have caused several of the observed steep gradients within the flow system. Low-permeability sediments along the Funeral Mountains, such as the Tertiary Death Valley Section sediments, also cause a steep hydraulic gradient between Amargosa Desert and Death Valley.

Groundwater recharge results from precipitation at higher elevations and infiltration along stream courses and in some playas. Recharge rates and distribution are estimated, and are therefore uncertain. The recharge model used in the UGTA regional flow model (DOE/NV, 1997) was based on a modification of the Maxey-Eakin method (Maxey and Eakin, 1949).

Groundwater discharges to the surface in the form of springs, seeps, and evapotranspiration in several areas. Major areas of natural groundwater discharge include Oasis Valley, Ash Meadows, Alkali Flat, Death Valley, and Penoyer Valley ([Figure 1-4](#)). Estimates of evapotranspiration have recently been updated by the USGS for the first four areas listed above (Lacznia et al., 2001). Within the NTS region and vicinity, artificial discharge occurs as groundwater pumpage from drinking water supply wells (public and domestic), agricultural wells, and industrial wells. Water supply wells for the NTS produce water from the carbonate, volcanic, and valley-fill aquifers. South of the NTS, private and public water supply wells are completed in the valley-fill aquifer. An estimate of the UGTA regional steady-state groundwater budget is provided in [Table 2-3](#).

Table 2-3
Estimated Steady-State Groundwater Budget
for the UGTA Regional Groundwater Flow System

Recharge	
Recharge from precipitation	$(1.77 \times 10^8 - 2.89 \times 10^8 \text{ kg/d})$
Subsurface inflow	$(5.4 \times 10^6 - 7.01 \times 10^7 \text{ kg/d})$
Total Natural Recharge	$(1.83 \times 10^8 - 3.59 \times 10^8 \text{ kg/d})$
Discharge	
Surface discharge (evapotranspiration)	$(1.35 \times 10^8 - 3.00 \times 10^8 \text{ kg/d})$
Subsurface outflow	$(8.5 \times 10^5 - 5.1 \times 10^6 \text{ kg/d})$
Total Natural Discharge	$(1.36 \times 10^8 - 3.06 \times 10^8 \text{ kg/d})$

Source: Modified from DOE/NV, 1997 (Table 6-4)
 kg/d = Kilograms per day

2.1.2 U.S. Geological Survey Death Valley Regional Ground-Water Flow System Model

The Death Valley Regional Ground-Water Flow System (DVRFS) model (Belcher et al., 2004) was developed as an integrated regional modeling analysis tool supporting NNSA/NSO investigations at the NTS and Yucca Mountain. The DVRFS was completed after the *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada* (SNJV, 2004d), where Phase II CAU model boundary fluxes from the UGTA regional model were presented. The DVRFS was used during the CAU flow model analysis to compute boundary fluxes, which are presented in subsequent sections. The DVRFS model incorporates newly available data and modeling tools, and combines data and insights from two previous regional-scale models to provide the most current regional-scale groundwater flow model for the Death Valley region. The two previous models were the UGTA regional flow model (DOE/NV, 1997), which was developed to evaluate radionuclide transport from underground nuclear weapons test sites on the NTS, and the Yucca Mountain Project (YMP)/Hydrologic Resource Management Program model (D'Agnese et al., 1997), which was developed to characterize the regional groundwater flow system relative to the potential radionuclide releases from the proposed geologic, high-level radioactive waste repository at Yucca Mountain.

The DVRFS integrates a 3-D hydrogeologic framework model and a 3-D groundwater flow model (Belcher et al., 2004). The hydrogeologic framework model incorporates regional geologic data and information (stratigraphy and structure) that capture the spatial geologic complexities within the

model boundary. There are 27 HGUs defined and incorporated into this model as summarized in [Table 2-4](#) (Belcher et al., 2004). The DVRFS model uses MODFLOW-2000 (Harbaugh et al., 2000), a 3-D, finite-difference modular modeling code that incorporates a nonlinear, least-squares regression technique to estimate model parameters. The DVRFS groundwater flow model has 16 layers of defined thickness, a finite-difference grid with 194 rows and 160 columns, and uniform cells 1,500 m on each side (Belcher et al., 2004).

Table 2-4
HGUs for the Death Valley Regional Ground-Water
Flow System Hydrogeologic Framework Model
(Page 1 of 2)

HGU Abbreviation	HGU Name	Description
YAA	Younger Alluvial Aquifer	Pliocene to Holocene coarse-grained basin-fill deposits
YACU	Younger Alluvial Confining Unit	Pliocene to Holocene playa and fine-grained basin-fill deposits
OAA	Older Alluvial Aquifer	Pliocene to Holocene coarse-grained basin-fill deposits
OACU	Older Alluvial Confining Unit	Pliocene to Holocene playa and fine-grained basin-fill deposits
LA	Limestone Aquifer	Cenozoic limestone, undivided
LFU	Lava Flow Unit	Cenozoic basalt cones and flows and surface outcrops of rhyolite-lava flows
YVU	Younger Volcanic Unit	Cenozoic volcanic rocks that overlie the Thirsty Canyon Group
Upper VSU	Volcanic and Sedimentary Unit	Cenozoic volcanic and sedimentary rocks, undivided, that overlie volcanic rocks of Southwestern Nevada Volcanic Field (SWNVF)
TMVA	Thirsty Canyon-Timber Mountain Volcanic Aquifer	Miocene Thirsty Canyon and Timber Mountain Groups, plus Stonewall Mountain tuff, undivided
PVA	Paintbrush Volcanic Aquifer	Miocene Paintbrush Group
CHVU	Calico Hills Volcanic Unit	Miocene Calico Hills Formation
WVU	Wahmonie Volcanic Unit	Miocene Wahmonie and Salyer Formations
CFPPA	Crater Flat-Prow Pass Aquifer	Miocene Crater Flat Group, Prow Pass Tuff
CFBCU	Crater Flat-Bullfrog Confining Unit	Miocene Crater Flat Group, Bullfrog Tuff
CFTA	Crater Flat-Tram Aquifer	Miocene Crater Flat Group, Tram Tuff
BRU	Belted Range Unit	Miocene Belted Range Group
OVU	Older Volcanic Unit	Oligocene to Miocene; near the NTS consists of all volcanic rocks older than the Belted Range Group. Elsewhere, consists of all tuffs that originated outside of the SWNVF

Table 2-4
HGUs for the Death Valley Regional Ground-Water
Flow System Hydrogeologic Framework Model
 (Page 2 of 2)

HGU Abbreviation	HGU Name	Description
Lower VSU	Volcanic and Sedimentary Unit	Cenozoic volcanic and sedimentary rocks, undivided; where named Cenozoic volcanic rocks exist, lower VSU underlies them
SCU	Sedimentary Confining Unit	Paleozoic and Mesozoic sedimentary and volcanic rocks
UCA	Upper Carbonate Aquifer	Paleozoic carbonate rocks (UCA only used where UCCU exists, otherwise UCA is lumped with LCA)
UCCU	Upper Clastic Confining Unit	Upper Devonian to Mississippian Eleana Formation and Chainman Shale
LCA_T1	Lower Carbonate Aquifer (thrust)	Cambrian through Devonian predominantly carbonate rocks, thrust
LCCU_T1	Lower Clastic Confining Unit (thrust)	Late Proterozoic through Lower Cambrian primarily siliciclastic rocks (including the Pahrump Group and Noonday dolomite), thrust
LCA	Lower Carbonate Aquifer	Cambrian through Devonian predominantly carbonate rocks
LCCU	Lower Clastic Confining Unit	Late Proterozoic through Lower Cambrian primarily siliciclastic rocks (including the Pahrump Group and Noonday dolomite)
XCU	Crystalline Confining Unit	Middle Proterozoic metamorphic and igneous rocks
ICU	Intrusive Confining Unit	All intrusive rocks, regardless of age

Source: Belcher et al., 2004

2.2 Recharge Models

2.2.1 U.S. Geological Survey Recharge Model

Two alternative recharge models, used to address recharge uncertainty, are taken from the USGS net infiltration/recharge model (Hevesi et al., 2003). The USGS net infiltration/recharge model is a distributed parameter watershed model used to estimate temporal and spatial distribution of net infiltration for the Death Valley region. The major components of this model include infiltration of rain, snowmelt, or surface water into the soil or bedrock, with subsequent bare-soil evaporation and transpiration from the root zone. All water percolating past the root zone is considered net infiltration, or recharge to the saturated zone, as unsaturated zone processes below the root zone were not considered. The two alternative USGS recharge models include the recharge model that includes a runoff/run-on component (USGSD) and the recharge model that does not include the runoff/run-on

component (USGSND). [Figures 2-2 and 2-3](#) show the recharge distribution for these two alternative models. As shown in the figures, the recharge datasets provide almost identical recharge values over the Frenchman Flat CAU model domain.

The recently released DVRFS model (Faunt et al., 2004) started with the USGSD recharge data. Recharge values were first resampled to the 1,500-m regional model grid. Then a recharge zone multiplication array was applied to the net infiltration values to match available discharge observations. Further, high recharge rates were moved from model areas where rocks near the water table had lower permeability values to downgradient areas where rocks near the water table were relatively permeable. [Figure 2-4](#) shows the recharge distribution from the DVRFS model (Faunt et al., 2004) for the Frenchman Flat Phase II CAU model domain.

2.2.2 Desert Research Institute Chloride Mass Balance Model

The DRI developed two recharge models for the NTS area using an elevation-dependent chloride mass balance approach (Russell and Minor, 2002; Russell, 2004). These models will be used to assess recharge uncertainty. The DRI chloride mass balance approach estimates recharge by analyzing the chloride concentrations of precipitation and groundwater. Higher chloride concentrations in groundwater discharged from springs result from evapotranspiration of precipitation that contains low amounts of conservative atmospheric chloride ion, thus providing a relative gauge of recharge. This information, in conjunction with soil chloride profiles in differing recharge locales (wash versus non-wash), allowed DRI to estimate recharge and associated confidence intervals of the recharge estimates. Two conceptual approaches to distributing the chloride mass balance were no recharge in the alluvial areas (DRI alluvial mask alternative, denoted DRIA) and one model for no recharge in the alluvial areas and no recharge below an elevation of 1,237 m (DRI alluvial and elevation mask alternative, denoted DRIAE). The data for each model were compiled in a geographic information system and used in a Monte Carlo analysis to determine recharge in the study area. Results of the analysis yielded estimates of the mean and standard deviation of recharge. The resultant recharge distributions for the Frenchman Flat CAU model domain for the DRIA 50th percentile is shown in [Figure 2-5](#). The recharge distribution for the DRIAE 50th percentile distribution is shown in [Figure 2-6](#) (SNJV, 2004d). The scale used to show the different recharge rates for all other recharge models does not show the variability in recharge

rates for the DRIA and DRIAE datasets. [Figures 2-7](#) and [2-8](#) show the data with a scale that reveals the spatial variability recharge rate.

2.2.3 Underground Test Area Modified Maxey-Eakin Recharge Models

The recharge distribution used in the UGTA regional groundwater flow model (DOE/NV, 1997) was constructed using a modification of the Maxey-Eakin method (Maxey and Eakin, 1949). Maxey and Eakin first described a method of estimating recharge to groundwater from precipitation in a report on groundwater in White River Valley, Nevada. In this method, recharge is estimated from precipitation by assuming that a set percentage of precipitation recharge occurs for specific ranges of precipitation. This modification incorporated:

- An updated precipitation map using more recent data
- The calculation of recharge using Maxey-Eakin coefficients
- The calculation of total recharge volumes for individual hydrographic areas
- The redistribution of a percentage of the total recharge within selected subareas to low-lying areas

[Figure 2-9](#) shows the modified Maxey-Eakin recharge distribution (denoted MME) for the Frenchman Flat CAU model area.

Subsequent to the development of the UGTA regional flow model (DOE/NV, 1997), a revised recharge distribution was generated for the NTS area by updating the original UGTA recharge model. The update included the redigitization and recontouring of the precipitation map, and the redigitization of the hydrographic areas using larger-scale maps. Following the update, a comparison to other recharge models was conducted. This updated recharge distribution model is designated as the UGTA Revised Maxey-Eakin recharge alternative. [Figure 2-10](#) shows the UGTA revised Maxey-Eakin recharge distribution for the Frenchman Flat CAU model area.

Figure 2-2
USGS Recharge Distribution with Overland Flow (USGSD)

Figure 2-3
USGS Recharge Distribution without Overland Flow (USGSND)

Figure 2-4
DVRFS Model Recharge Distribution

Figure 2-5
DRI Recharge Distribution with Alluvial Mask (DRIA)

Figure 2-6
DRI Recharge Distribution with Alluvial and Elevation Mask (DRIAE)

Figure 2-7
DRI Recharge Distribution with Alluvial Mask (DRIA) - Revised Scale

Figure 2-8
DRI Recharge Distribution with Alluvial and Elevation Mask (DRIAE) - Revised Scale

Figure 2-9
Original UGTA Modified Maxey-Eakin (MME) Recharge Model

Figure 2-10
Revised UGTA Modified Maxey-Eakin (MME-revised) Recharge Model

2.3 CAU Models

2.3.1 Phase I Frenchman Flat CAU Model

Following the completion of the NTS regional model, work was initiated to develop the Phase I Frenchman Flat CAU-specific HFM, steady-state groundwater flow, and groundwater transport models.

Based on the Value of Information Analysis (IT, 1997b), the Frenchman Flat CAIP (DOE/NV, 1999) concluded that existing data were sufficient to develop CAU-scale hydrostratigraphic, groundwater flow, and transport models. These models would then be used to evaluate the impacts of various sources of uncertainty and provide a basis for a determination whether additional data were needed to adequately simulate the location of contaminant boundaries.

At the conclusion of the Frenchman Flat Phase I modeling, all draft documentation and modeling results were reviewed by an external peer group. The results of this review were documented in the *External Peer Review Group Report on Frenchman Flat Data Analysis and Modeling Task, Underground Test Area Project* (IT, 1999a) and *Lessons Learned from the Frenchman Flat Corrective Action Groundwater Flow and Radionuclide Transport Model* (IT, 2000). Based on the external peer review results and the evaluation of lessons learned from the Phase I work, deficiencies were identified and recommendations for work to address these deficiencies were made. These recommendations led to the development of a Phase II investigation plan that was documented in the *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001).

2.3.1.1 Phase I Frenchman Flat Hydrostratigraphic Framework Model

The Phase I HFM for the Frenchman Flat area represented a CAU-specific refinement of the UGTA regional model. The mechanics of integrating the geologic data into the 3-D hydrostratigraphic model included constructing geologic cross sections; constructing contour maps for the elevation of the top of each HSU; and converting the contour maps to gridded elevations for input into visual display software and groundwater flow and transport models.

As the basis for geologic interpretation, the alluvial, volcanic, and pre-Tertiary rocks in the Frenchman Flat Phase I model area were classified as either aquifer or confining unit HGUs. The alluvial rocks included a playa confining unit (PCU) and a valley-fill aquifer unit. In general, altered (typically zeolitized) volcanic rocks were defined as confining units, and the unaltered volcanic rocks were defined as aquifer units. Finally, the pre-Tertiary siliceous clastic rocks were generally defined as confining units, while pre-Tertiary carbonate rocks were defined as aquifer units.

The conceptual model of Grauch and Hudson (1995) was used as the basis for the Phase I HFM. This conceptual model took into account gravity and aeromagnetic data from Frenchman Flat as well as theories of basin formation, and drill-hole and outcrop data. The bottom of the flow system was the Paleozoic LCA. The LCA has the largest transmissivity of the HSUs in Frenchman Flat and transmits the majority of the water from recharge areas east of the NTS to the discharge areas to the south. Tuff and volcanoclastic confining units (termed LTCU and VCU in the Phase II HFM, respectively) lie above the LCA over most of the basin except in the southeast corner, where they have been eroded. These are generally finer-grained, often zeolitized units of low permeability. The Timber Mountain Aquifer (TMA) overlies the TCU to the north, while the Wahmonie Confining Unit (WCU) overlies the TCU and VCU to the west. Both the TMA and WCU are quite heterogeneous and contain stringers of fractured aquifer material. Therefore, these units were considered more permeable than the underlying confining units. One additional unit, the UCCU, is not present in the Frenchman Flat basin but was believed to be present in CP basin, west of Cane Spring fault. The UCCU was expected to act as a barrier to downward flow in CP basin and may help keep water levels higher in CP basin than in Frenchman Flat. Finally, the shallowest unit in the center of the Frenchman Flat basin was the AA.

Drill-hole data did not exist to unambiguously define all aspects of the Grauch and Hudson (1995) conceptual model (for instance, the thickness of the alluvium under the testing areas). However, an effort was made during construction and evaluation of this model to determine whether any other models of Frenchman Flat geology could be defended. Through this analysis it was found that, although certain components of the model were subject to alternative interpretations, the basic concept of a very thick section of Paleozoic sedimentary rocks and a relatively thin sequence of overlying Tertiary volcanic rocks that has been deeply depressed, broken by faults, and buried beneath moderately thick alluvium remained intact.

The Phase I HFM is very similar to the one used in the Phase II flow model evaluation, supplemented by additional geophysical and drill-hole data as described in [Section 2.3.3](#).

2.3.1.2 Conceptual Models of Groundwater Flow for the Phase I CAU Flow Model

There is little disagreement that the direction of flow in the underlying LCA is from north-northeast to south-southwest. However, groundwater flow in the alluvium is more ambiguous. Three general models of groundwater flow in the AA were developed for Phase I as follows (IT, 1999a; Hershey et al., 2005):

- North-to-south flow. In this model, local groundwater flow parallels the presumed regional flow directions. With the flat potentiometric surface in the center of Frenchman Flat basin and the 5- to 10-m lower heads to the south and southeast (although affected by pumping), it is easy to visualize southerly flow. Under this conceptual model, water levels north of Frenchman Flat are higher than 734 m, thus serving as the source of water to the alluvium. The CP basin region west of Frenchman Flat is assumed to be isolated from Frenchman Flat and would be part of a separate flow system isolated by the Cane Spring fault. The water in the Frenchman Flat basin is assumed to drain to the south in the LCA.
- Bathtub, or horizontally stagnant, flow conditions. Under this model, the vertical gradients are much stronger than the horizontal hydraulic gradients, and the dominant direction of flow will be vertical in the testing areas. The water levels in the southern area are lower because of a decrease in confining unit thickness underlying the alluvium. In this conceptual model, the hydraulic head in the underlying LCA will be lower than the head in the alluvium. The CP basin area is assumed to be hydraulically separated from the Frenchman Flat basin by the Cane Spring fault. The bathtub model also assumes that an effective confining unit always underlies the alluvium.
- West-to-east flow. In this model, the CP basin and Mount Salier regions are the source of most of the water in the Frenchman Flat alluvium, with a small component from recharge. After entering the alluvium from the west, the groundwater will travel laterally toward the lower hydraulic head in the LCA, on the perimeter of the basin. In this model, groundwater flow will be northerly in the northern part of the basin, easterly in the eastern part of the basin, and southerly in the southern part of the basin. This model also assumes that west-central Frenchman Flat should have the highest water levels. Aspects of this scenario have been proposed by Winograd and Thordarson (1975) and Lacznia et al. (1996), particularly with respect to discharge to the LCA.

Winograd and Thordarson (1975) also propose the Cane Spring fault as a barrier, but they do not speculate that it may be leaky and allow water to enter the Frenchman Flat alluvium. They also speculate a possible fault influence in the vicinity of the western side of Frenchman Lake playa.

However, they believed that the fault might have created a vertical conduit to the LCA that helps to explain the lower water levels in Wells WW-5A and WW-5C. To the east, a major north-south splay of the Rock Valley fault system also may act as the major basin-bounding fault. The postulated large displacement on this fault places LCA in contact with volcanic rocks in contact with alluvium; this could serve as a drain to the east.

2.3.1.3 Phase I CAU Flow and Transport Model Results

The Phase I CAU steady-state numerical flow model was calibrated to the data, with a bias to underpredict water levels in the southern part of the basin. Model modifications that might improve agreement with the data in the southern area were suggested but not implemented. The peer review observed that, given the data and complexity of the hydrogeologic setting, the single calibrated model presented was not unique. The peer review also stated that other models based on different geologic conceptualizations still might be able to equally reproduce the available head measurements, and that only parameter uncertainty, and not geologic and structural uncertainty, was considered.

The Phase I transport model showed very limited radionuclide transport. However, the peer review found that the model grid block volume could be up to 10 times larger than one cavity volume, resulting in significant dilution of the initial radionuclide mass associated with an underground nuclear test and potential underestimation of radionuclide concentrations (IT, 1999a).

2.3.2 Desert Research Institute Geochemistry Model

The Phase I peer review suggested an integrated isotope and geochemistry analysis in order to better define flow paths in and around Frenchman Flat, and differentiate the appropriate conceptual model of basin hydraulics. Hershey et al. (2005) performed an isotope and geochemistry modeling analysis to assess the viable flow paths and groundwater mixing models in and around Frenchman Flat. More discussion of the available groundwater geochemistry data for the Frenchman Flat CAU is also provided in SNJV (2004d; Section 10.0). The approach used for these evaluations was consistent with that described in the *Geochemistry Technical Basis Document* (Benedict et al., 2003). Viable flow paths were first identified using conservative tracers and evaluated further using strontium (Sr) data and NETPATH (Plummer et al., 1994) and PHREEQC (Parkhurst and Appelo, 1999) software packages. These programs are used to interpret net geochemical mass balance between initial and

final water compositions along a flow path, and to calculate groundwater mixing ratios and apparent groundwater travel times (Hershey et al., 2005). Plausible flow paths that are consistently described using conservative tracers, Sr, and reactive transport (NETPATH/PHREEQC) modeling are considered to have a high probability of representing realistic groundwater pathways.

The focus of the recent geochemical data analysis of Hershey et al. (2005) was on testing the conceptual flow models developed from the Phase I groundwater modeling effort in an effort to resolve the most appropriate model (see [Section 2.3.1.2](#)). These pathways included:

(1) north-to-south flow, (2) west-to-east flow, and (3) vertical transport from the alluvial/volcanic aquifers to the LCA (bathtub model). In general, the analysis of conceptual groundwater flow paths was limited by an uneven spatial distribution of wells within the study area and by a paucity of wells completed in the LCA. The general conclusions drawn from the geochemical data assessment of Hershey et al. (2005) are as follows:

North-to-South Flow Path

Alluvium. The presence of a major north-to-south flow path within the AA was not supported using conservative tracer data, nor was a north-to-south flow path from the AA to the downgradient LCA at Army-1 WW. Although conservative tracer data yielded one successful model that suggested the possibility of a relatively deep lateral pathway through the volcanic aquifers beneath Frenchman Flat to the LCA, the model was not supported by subsequent reactive transport geochemical models. Therefore, it was concluded that southward lateral transport of groundwater out of the alluvial or volcanic units to the LCA at Army-1 WW was improbable.

Lower Carbonate Aquifer. Water-level data in the southeastern portion of the NTS are generally consistent with a north-to-south flow path within the LCA. Geochemical data tend to support this conclusion, although the fractional amount of Frenchman Flat LCA groundwater that contributes to the downgradient flux remains uncertain. At Army-1 WW, conservative tracer models predicted a minimum of approximately 35 percent Frenchman Flat LCA water, whereas reactive transport models predict a maximum of approximately 14 percent. The truth is thought to lie somewhere between. Dissolved inorganic carbon-14 (DI¹⁴C) travel times calculated for the Frenchman Flat to Army-1 WW LCA flow path ranged from 4,300 to 6,800 years.

West-to-East Flow Path

Alluvium. West-to-east flow in the AA to the LCA in eastern Frenchman Flat could not be substantiated using any of the geochemical modeling approaches (conservative tracers, Sr data, NETPATH/PHREEQC). Mixing models using groundwater from the CP basin were unsuccessful because this water is chemically distinct from other Frenchman Flat groundwater. It was noted, however, that this flow path could not be adequately tested due to a paucity of appropriate well locations.

Vertical Transport (Bathtub Model)

The possibility that groundwater is moving from the alluvial and volcanic aquifers into the LCA could only be tested at one location within the Frenchman Flat basin: Well ER-5-3 #2. A conservative tracer model was developed that required 76 to 87 percent of an undiluted LCA groundwater with approximately 13 to 24 percent alluvial groundwater. However, these models were not supported by other lines of geochemical evidence.

Conceptually similar mixing models were successfully developed involving the mixing of 70 percent of an undiluted LCA groundwater and approximately 30 percent of a volcanic groundwater to derive the composition of WW C-1, in southernmost Yucca Flat. The conservative tracer and chemical models were in good agreement in this case. Although the Sr isotope data did not support this conceptual flow path, the development of a consistent set of conservative tracer and geochemical transport models for WW C-1 suggests that vertical flow is a potential viable process in southern Yucca Flat, although it must be remembered that Yucca Fault is thought to drain the volcanic rocks overlying the LCA, a feature not observed in Frenchman Flat.

In general, Hershey et al. (2005) concluded that migration of radionuclides out of the alluvium and volcanic aquifers into the LCA is unlikely, but that there is a viable LCA flow path from Frenchman Flat to the southern boundary of the NTS, in general agreement with postulated regional flow directions.

Further analyses of groundwater flow paths and travel times in the alluvium and tuffaceous units in Frenchman Flat are presented in [Section 8.0](#). These analyses are intended to complement the analyses of Hershey et al. (2005).

2.3.3 Phase II Hydrostratigraphic Framework Model

Following the Frenchman Flat CAIP Addendum (NNSA/NV, 2001) additional characterization work was undertaken. Relevant to the HFM, these activities included the drilling and completion of five new wells in the vicinity of the two testing areas in Frenchman Flat, and geophysical investigations including gravity, ground and aeromagnetic, seismic, and magnetotelluric data. The integrated use of geophysics was suggested by the peer review (IT, 1999a). The well drilling and geophysical investigations contributed new data and information for use in the development of the Phase II HFMs.

The Phase II Frenchman Flat CAU-specific HFM was constructed using EarthVision® (Dynamic Graphics, 2002), a 3-D geologic model building and visualization software package. Input data included drill-hole data, DEM data, and outcrop and fault data from surface geologic maps. Where deemed necessary, the data were supplemented with interpretations in the form of cross sections and structure-contour maps.

The Phase II Frenchman Flat BASE HFM was constructed based on drill-hole and geophysical data collected in the Frenchman Flat model area. The conceptual model is still broadly consistent with the NTS hydrologic system described by Winograd and Thordarson (1975) and Phase I HFM, and consists of a thick, fractured LCA overlain by volcanic rocks that have been depressed and buried by alluvium.

Data collected during the Phase II acquisition clearly show that the basin is deeper than originally depicted in the Phase I HFM. In the vicinity of the underground nuclear test locations in the central portion of Frenchman Flat, the LCA is 1,000 m deeper than estimated in Phase I. In northern Frenchman Flat, near Well Cluster ER-5-3, the LCA is about 380 m deeper in the Phase II HFM (BN, 2005a).

The greater depth to pre-Tertiary rocks (e.g., LCA, UCCU, LCCU) in the Phase II model results in greater thicknesses of the overlying alluvial and volcanic deposits. The alluvium is more than 100 m thicker in the northern portion of the basin, and more than 800 m thicker beneath the central testing area. Likewise, Tertiary-age volcanic rocks are 300 m thicker beneath northern Frenchman Flat and 600 m thicker beneath the central portion of the basin (BN, 2005a).

The Phase II Frenchman Flat HFM area encompasses more than 570 km² in the southeastern portion of the NTS. The model area has a north-south length of 30 km and an east-west length of 19 km, and includes geologic units as deep as -5 km amsl (BN, 2005a). [Figure 2-11](#) is an HSU surface map of the Frenchman Flat CAU model domain showing the locations of Well Clusters ER-5-3 and ER-5-4. The wells at both of these locations penetrated Quaternary and Tertiary alluvium to depths of 622.4 m and 1,120.4 m, respectively.

A BASE HFM and four alternative HFMs (different geologic interpretations that are equally consistent with the available data) were developed. The BASE HFM represents the consensus view of the currently most viable model based on existing data. The inherent uncertainty in such a model is recognized and addressed via a suite of models that are equally permissive within the constraints of available data. The primary purpose for establishing a base model is to have a reference point for describing alternative HFMs. Details on the development of the BASE and alternative HFM development, and selection criteria for the alternative HFMs, are documented in *A Hydrostratigraphic Framework Model and Alternatives for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Clark, Lincoln and Nye Counties, Nevada* (BN, 2005a).

2.3.3.1 BASE Hydrostratigraphic Framework Model

This section summarizes the structural features, HGUs, and HSUs of the BASE HFM (the HFM considered most likely based on geologist expert judgement developed for the Frenchman Flat area and vicinity). [Figure 2-11](#) shows the HSUs at the surface for the Frenchman Flat BASE HFM. A 3-D view of this model is shown in [Figure 2-12](#). [Plate 1](#) shows cross sections through the BASE HFM.

The BASE HFM model includes a total of 71 faults and 17 HSUs (9 aquifers and 8 confining units). The structural elements are typically normal faults (basin and range-style faults) but also includes several strike-slip and older thrust faults. Only faults that were considered to be hydrologically significant were included in the model, which includes the larger faults (those with offsets typically greater than 61 m) and the faults that seem to form significant structural boundaries ([Figure 2-13](#)) (BN, 2005a).

Figure 2-11
Hydrostratigraphic Unit Surface Map of the Frenchman Flat Model Area

Figure 2-12
Three-Dimensional View of the BASE Hydrostratigraphic Model
of the Frenchman Flat Area (BN, 2005a)

Figure 2-13
Three-Dimensional Image of Major Fault Structures
 (Alluvial sequence not displayed)

Frenchman Flat is an east-tilted half-graben basin, the formation of which is directly related to the northeastern termination of the Rock Valley fault zone within an extensional imbricate fan ([Figure 2-13](#)). The main basin is bounded on the south, north, and east by a series of oblique-slip faults that extend out of the northeast-striking, left-lateral strike-slip Rock Valley fault zone and curve north and northwest, forming an imbricate fan structure. These faults are the main basin-forming faults, dropping the central portion of the basin down on the south, north, and east, and resulting in an east tilt to rocks beneath the basin, and a general eastward thickening wedge of volcanic and alluvial deposits.

Another significant structural feature is the Cane Spring fault ([Figure 2-13](#)), located in the northwestern part of the Frenchman Flat model area. The Cane Spring fault separates the Frenchman Flat basin from CP basin, which has hydraulic head values in shallow volcanic units significantly higher than those observed in Frenchman Flat basin (SNJV, 2004d).

As described in [Section 2.1.1.1](#), the rocks of the NTS have been classified for hydrologic modeling using a two-level classification scheme in which HGUs are grouped to form HSUs (IT, 1996d). New units and additional detail have been added to the basic framework definition. [Table 2-5](#) summarizes the Phase II Frenchman Flat HSUs (BN, 2005a). They are listed in approximate order from surface to basement, although some are laterally rather than vertically contiguous and not all units are present in all parts of the model area. [Plate 1](#) shows eight cross-sectional views of the hydrostratigraphic framework within the Frenchman Flat model area.

The Phase II Frenchman Flat HFM (BN, 2005a) includes considerable structural detail and stratigraphic enhancement over the UGTA regional HFM (IT, 1996d). The total number of HSUs increased from 9 to 17. Most of the detail was added to the Quaternary-Tertiary alluvial section and the Tertiary volcanic section. The single AA in the regional model has been subdivided into five HSUs. The two Tertiary volcanic HSUs in the UGTA regional HSU model were subdivided into eight HSUs for the Phase II Frenchman Flat model. Except for the LCA thrust plate, the three pre-Tertiary HSUs remain as initially defined.

Table 2-5
Hydrostratigraphic Units for the Phase II Frenchman Flat Hydrostratigraphic Framework Model
 (Page 1 of 2)

Hydrostratigraphic Unit (Symbol)	General Description
Alluvial Aquifer (AA, AA3, AA2, AA1) ^a (this term is also used to designate an HGU)	Consists mainly of alluvium that fills extensional basins. Also includes generally older Tertiary gravels, and very thin air-fall tuffs. The AA, AA1, AA2, and AA3 are equivalent hydrogeologically except for position relative to other HSUs embedded within the alluvial section.
Playa Confining Unit (PCU2T)	Clayey silt and sandy silt. Forms the Frenchman Flat playa.
Basalt Lava Flow Aquifer (BLFA)	Several (possibly dissected) basalt flows are recognized in the middle of the alluvial section of the northeastern Frenchman Flat. Related to other basalt flows in Nye Canyon.
Older Altered Alluvial Aquifer (OAA and OAA1)	Older, denser, zeolitized alluvium recognized only in northern Frenchman Flat. The OAA and OAA1 are equivalent except for position: the OAA is above the BLFA, and the OAA1 is stratigraphically beneath the BLFA.
Older Playa Confining Unit (PCU1U and PCU1L)	Deep, subsurface playa deposits in the deepest portion of Frenchman Flat. Recognized in Well ER-5-4 #2 and with 3-D seismic data. The PCU1U and PCU1L are similar except for position.
Timber Mountain Welded Tuff Aquifer (TM-WTA)	Consists mainly of welded ash-flow tuffs of Ammonia Tanks Tuff and Rainier Mesa Tuff. Unit occurs mostly in north and central Frenchman Flat. Prolific aquifer when saturated.
Timber Mountain Lower Vitric Tuff Aquifer (TM-LVTA)	Defined to include all unaltered (nonzeolitic) nonwelded and bedded tuffs below the welded Rainier Mesa Tuff (Tmr) and above the level of pervasive zeolitization. The presence of the welded Topopah Spring Tuff (Tpt) (see TSA) complicates this general description.
Upper Tuff Confining Unit (UTCU)	Relatively thin TCU above the TSA. Grouped with the LTCU where the TSA is not present.
Topopah Spring Aquifer (TSA)	The welded ash-flow lithofacies of the Tpt in the Massachusetts Mountain/French Peak area and north-central Frenchman Flat.
Lower Vitric Tuff Aquifer (LVTA)	Relatively thin VTA unit below the TSA. Grouped with the TM-LVTA where TSA is not present.
Lower Tuff Confining Unit (LTCU and LTCU1)	Generally includes all the zeolitic nonwelded and bedded tuffs in southeastern NTS. May include all units from the base of Tmr to the top of Paleozoic-age rocks. The Wahmonie Formation stratigraphic interval grades or interfingers laterally westward into the WCU. Zeolitic bedded tuffs stratigraphically below the WCU are classified as the LTCU1.
Wahmonie Confining Unit (WCU)	Mixture of lava flows, debris flows, lahars, ash flows, and air-falls. Typically zeolitic, argillic, or hydrothermally altered. Grades or interfingers laterally with the LTCU.
Volcaniclastic Confining Unit (VCU)	Older Tertiary sedimentary rocks of variable lithologies including silt, clay, limestone, gravel, and tuffaceous units. Present in southeastern half of Frenchman Flat.

Table 2-5
Hydrostratigraphic Units for the Phase II Frenchman Flat Hydrostratigraphic Framework Model
 (Page 2 of 2)

Hydrostratigraphic Unit (Symbol)	General Description
Lower Carbonate Aquifer-Thrust Plate (LCA3)	Cambrian through Devonian, mostly limestone and dolomite, rocks that occur in the hanging wall of the Belted Range thrust fault. Present only in the northwest corner (CP basin) of the model area.
Upper Clastic Confining Unit (UCCU)	Late Devonian through Mississippian siliciclastic rocks. Present only in the northwest corner (CP basin) of the model area, northwest of Cane Spring fault and southwest of Topgallant fault.
Lower Carbonate Aquifer (LCA)	Cambrian through Devonian mostly limestone and dolomite. Regional carbonate aquifer present throughout the model area.
Lower Clastic Confining Unit (LCCU)	Late Proterozoic through Early Cambrian siliciclastic rocks. Hydrologic basement present at great depth in the model area.

Source: Modified from BN, 2005a

^aThese subdivisions are equivalent hydrogeologically but are necessary to satisfy operational requirements of the hydrostratigraphic modeling software.

Following the completion of the BASE HFM, four alternative HFMs were developed. The main criterion for selecting alternative HFMs was the potential impact of the alternative interpretation on groundwater flow and the transport of contaminants in groundwater. Table 2-6 summarizes the alternative HFMs. The following discussion is taken from BN (2005a) and provides a more detailed overview of these alternative HFMs.

Table 2-6
Summary of Alternative Hydrostratigraphic Framework Models Considered
in the Frenchman Flat Flow Model

Alternative HFM	Key Difference(s) Compared to BASE HFM	Potential Impacts on Flow Model
Basalt Lava Flow Aquifer (BLFA)	The BLFA HSU is modeled as a single continuous flow, rather than three separate zones.	Located at or near the water table, which may affect flow and transport of radionuclides away from underground nuclear tests in the northern testing area.
Detachment fault (DETA)	This alternative is a no detachment fault model.	In this alternative, removing the fault eliminates potential hydrologic consequences of volcanic unit offsets across the fault. Volcanic rocks were modeled as dipping moderately southward from Area 11.
Displacement fault (Aquifer Juxtaposition) (DISP)	This alternative is concerned with the locations and displacement of basin-forming faults.	This alternative juxtaposes shallow aquifers against deeper aquifers, allowing a hydraulic connection between volcanic aquifers underlying the AA in Frenchman Flat to carbonate aquifers east and south from the Rock Valley fault system.
CP thrust fault (CPBA)	The CP basin alternative extends the UCCU beneath all of CP basin.	Some uncertainty exists in the distribution of pre-Tertiary HSUs, particularly the distribution of UCCU beneath CP basin. This alternative results in a continuous sheet of UCCU beneath the basin.

Source: BN, 2005a; SNJV, 2004d

2.3.3.2 Basalt Lava Flow Aquifer (BLFA) HFM Alternative - Alternative Model #1

The Phase II Frenchman Flat BASE HFM depicts the BLFA HSU as three separate and discontinuous bodies embedded within the alluvial section. This geometry is based on drill-hole and ground magnetic data. However, there is some uncertainty associated with this interpretation. It is not known whether these are three separate flows or erosional remnants of a single larger flow. Also, aeromagnetic and ground magnetic data do not extend far enough east to show definitively the eastern limit of the BLFA. Coincidentally, the BLFA HSU is located at or near the water table. The presence

and geometry of such an aquifer near the water table may affect flow and transport of radionuclides away from underground nuclear tests in the vicinity.

Basaltic volcanism in the Frenchman Flat basin includes buried basalt encountered in the alluvial section in multiple drill-holes in the north-northeastern part of the basin, including drill-hole ER 5-3 (Carr, 1974). The age of these buried basalt lavas is about 8.5 million years ago (Ma) (Shott et al., 1998). Local vents for the buried basalt are present in Scarp Canyon immediately north of Frenchman Flat (Crowe, 1990; Perry et al., 1998). Several of the basalt flows and dikes to the north in the Half Pint Range are associated with generally north-south trending faults (Hinrichs and McKay 1965; Byers and Miller, 1966). It is conceivable that one of the basin-forming faults in the Frenchman Flat model is the source for the Frenchman Flat basalt. If so, the BLFA could possibly provide a lateral conduit for contaminants from underground nuclear tests in northern Frenchman Flat eastward to the fault and ultimately to the LCA. This alternative will allow flow and transport modeling to explore the consequences of a continuous BLFA near the water table in the vicinity of the underground nuclear tests in northern Frenchman Flat. A comparison of the BLFA HSU in the BASE HFM to this alternative is shown on [Plate 2](#).

2.3.3.3 Detachment Fault (DETA) HFM Alternative - Alternative Model #2

Drill-hole and 3-D seismic data suggest that a detachment fault is present beneath the northern portion of Frenchman Flat, and this interpretation was included in the BASE HFM. However, because of the uncertainty of this interpretation and the potential hydrologic consequences associated with such an interpretation, an alternative HFM was developed that did not include the detachment fault. In the alternative HFM, the detachment fault is removed, and volcanic rocks are modeled as dipping moderately southward from borehole UE-11b and nearby surface exposures to the deeper intercepts in drill-holes located to the south. A comparison of the BASE HFM to this alternative is shown on [Plate 2](#).

2.3.3.4 Displacement Fault (DISP) HFM Alternative - Alternative Model #3

Because basin-forming faults typically have large vertical displacements, the juxtaposition of shallow aquifers against deeper aquifers could occur and be significant with regard to flow-and-transport modeling in the Frenchman Flat area. In the BASE HFM, no aquifers are juxtaposed due to faulting

along the main basin-forming faults. However, the locations, orientations, and amounts of displacements associated with these faults are poorly constrained. Therefore, an alternative HFM was developed that juxtaposed shallow volcanic aquifer HSUs with the LCA along a major basin-forming fault. A comparison of the BASE HFM to this alternative is shown on [Plate 2](#).

2.3.3.5 CP Basin (CPBA) HFM Alternative - Alternative Model #4

Considerable uncertainty exists with regard to the pre-Tertiary structural geology beneath CP basin. Consequently, the distribution of pre-Tertiary HSUs beneath the basin is poorly known, particularly the distribution of the UCCU. The UCCU is exposed in the footwall of the CP thrust fault just northwest of the model area, and magnetotelluric (MT) recordings seem to indicate that the UCCU is present beneath the northeastern portion of CP basin. The BASE HFM incorporates the MT data, and thus places the UCCU beneath CP basin as part of the footwall of the CP thrust and limits its extent to the northeastern portion of the basin. Overlying the footwall rocks is a continuous sheet of carbonate rocks that composes the hanging wall of the CP thrust.

Because of the uncertainties associated with the distribution of the UCCU beneath CP basin, and the potential hydrologic influence of this major confining unit, particularly with regards to groundwater flux out of southern Yucca Flat and into the northwest portions of the model area, an alternative HFM was developed for CP basin. A comparison of the BASE HFM to this alternative is shown on [Plate 2](#). The alternative model extends the UCCU beneath all of CP basin, resulting in a continuous sheet of UCCU beneath the basin. As in the BASE HFM, a continuous sheet of carbonate rock comprising the hanging wall of the CP thrust fault overlies the UCCU beneath the basin. Further, to the north of CP basin, faults 11 and 16 in the BASE HFM are combined into a single, more extensive fault (fault 74) in this alternative (not shown on [Plate 2](#)).

2.4 Summary

Several studies have investigated or described various aspects of the Frenchman Flat groundwater flow system, including two regional flow models, three recharge models developed from different principles, two HFMs, and a geochemical analysis. The UGTA regional model, Phase I CAU model, and Maxey-Eakin recharge estimates were developed as part of the first phase in the UGTA compliance strategy described in Appendix VI, Revision No. 1 (December 7, 2000) of the FFACO

(1996). The results of a peer review (IT, 1999a) at the third major decision point in the strategy, Phase I CAU flow and transport model acceptability, resulted in revision to the Frenchman Flat CAIP (DOE/NV, 1999) to undertake additional data collection and analysis activities as part of Frenchman Flat Phase II.

Of the work summarized in this section, the USGS and DRI recharge models, geochemical analysis, and Phase II HFM were performed as part of the Phase II analysis. These will be analyzed and discussed in subsequent sections as they related to the development and understanding of the Phase II CAU flow model.

3.0 DATA AND CONCEPTUAL MODELS

This section summarizes hydraulic data and interpretations that form the basis for conceptual and numerical models of the Frenchman Flat flow system. Hydraulic data for Frenchman Flat have been collected intermittently for more than 50 years, and various investigations (e.g., Winograd and Thordarson, 1975; Winograd and Pearson, 1976; IT, 1998 and 1999b; SNJV, 2004d) have interpreted the available data. The data presented in this section include the older datasets along with new data that confirm many of the basic elements of the Frenchman Flat flow system that were first recognized as early as the 1970s.

Winograd and Thordarson (1975) first described the basic features of the Frenchman Flat flow system as it is known today. They noted that hydraulic heads in the CP basin to the northwest of Frenchman Flat were approximately 113 m higher than hydraulic heads in Frenchman Flat basin, and they attributed this hydraulic discontinuity to the presence of the Cane Spring fault, which separates these basins. Water levels in both the alluvium and the welded tuffs within Frenchman Flat were determined to be several meters higher than water levels in the LCA that underlies and surrounds the basin, leading them to the conclusion that groundwater in the alluvium and tuff was semiperched and could only leave the basin by draining downward to the LCA or by flowing laterally into the LCA across the basin margins. Slightly lower water levels at several wells near Frenchman Lake Playa led them to conclude that a stronger hydraulic connection between the alluvium and the LCA existed near the playa, perhaps as a result of the thinning or faulting of the tuff aquitards that line the basin, and that drainage from the alluvium to the LCA was concentrated near the playa.

The flat hydraulic gradients within Frenchman Flat, combined with data from other areas of the NTS that indicated the permeability of alluvium is low to moderate, suggested to Winograd and Thordarson (1975) that the groundwater flux through the basin-filling alluvium and tuffs was relatively small. In the northern part of the basin, several wells drilled to different depths in the alluvium had very similar composite heads. This observation, combined with a hydraulic head measurement from the underlying tuff aquitard that was 5 to 6 m lower than the heads in the alluvium,

suggested that vertical head gradients within the alluvium were small or nonexistent, and that most of the head loss between the alluvium and LCA takes place across the deep tuff aquitards that line the basin. Thus, there was little gradient to drive downward flow in the alluvium, at least away from the vicinity of the playa. Lacznia et al. (1996) revisited the basic conceptual model first described by Winograd and Thordarson (1975), emphasizing the possibility that lateral flow from the basin through the tuff confining units could also recharge the LCA.

A later conceptual model proposed by IT (1999a) suggested that semiperched groundwater in the alluvial and volcanic aquifers of Frenchman Flat was sustained by groundwater inflow from the CP basin that leaks across the Cane Spring fault (IT, 1999a). Leakage of groundwater from the CP basin into Frenchman Flat results in groundwater flow directions in Frenchman Flat that are generally northwest to southeast. This conceptual model was supported by three observations: 1) observed water levels in CP basin are much higher than those in the Frenchman Flat basin, 2) observed water levels in the AA are lower to the south and east of the Frenchman Flat playa, and 3) water levels observed in Well UE-5c WW in the northwest alluvium are greater than those observed in the central or east basin.

Winograd and Pearson (1976) discussed groundwater flow in the carbonate rocks beneath southern Frenchman Flat and concluded from ^{14}C measurements and limited hydraulic head data that groundwater flow was relatively rapid within a hydraulic trough extending roughly 30 km between eastern Frenchman Flat at Well TW-3 and springs at the Ash Meadows discharge area. Based on the small volumes of groundwater inflow to Frenchman Flat from Yucca Flat estimated by Winograd and Thordarson (1975), Lacznia et al. (1996) concluded that most (> 95 percent) of the groundwater in the LCA beneath Frenchman Flat that ultimately discharges at Ash Meadows originates from areas east or southeast of the NTS.

As the data presented in this section demonstrate, many of the essential features of the Frenchman Flat flow system identified on the basis of relatively sparse data are confirmed with new data collected as part of the Frenchman Flat Phase II study.

3.1 Geologic Setting

Details of HFMs for the Frenchman Flat CAU and surrounding areas are provided in BN (2005a). Important differences in the conceptualization of the hydrostratigraphic framework that were permitted by the data and potentially important to the flow and transport models of the Frenchman Flat CAU are summarized in [Section 2.3.3](#). Although they differ in some of their details, the various HFMs have many similarities that rely on common conceptual models for the origin and structure of the basin.

Mapping studies and subsurface borehole and geophysical data indicate that the central part of the Frenchman Flat basin is an eastward-tilted half-graben with significant vertical displacement along splays of the Rock Valley fault system that bound it along its southern, eastern, and northern margins (BN, 2005a). Sedimentary and volcanoclastic rocks, followed by ash-fall and ash-flow tuffs and finally alluvial and playa deposits, filled the basin as it developed, along with lavas emanating from the Wahmonie volcanic center to the west of the basin. Stratigraphic relationships between alluvium and tuffs within the basin indicate that formation of the main part of the basin was initiated after eruption of the Ammonia Tanks Tuff (11.45 Ma) and before the eruption of the Thirsty Canyon group had been completed at 9.14 Ma (BN, 2005b, p. 3-4). Basin development continued after deposition of the tuffs, as demonstrated by the faulted nature of the tuffs and the accumulation of more than 1,400 m of alluvium in the center of the basin. The alluvium thins toward and beyond the structural margins of the basin where it directly overlies the LCA (BN, 2005a, Figure 3-3). Along the northern, eastern, and southern margins, the tuff confining units that line the basin have been thinned by faulting and erosion, increasing the potential for hydraulic connections between the shallower material in the basin and the LCA in these areas.

The geology northwest of Frenchman Flat is structurally complex and diverse. This area includes the CP basin, whose geology at depth is relatively uncertain; the strike-slip Cane Spring fault, which separates CP basin from Frenchman Flat basin; the Wahmonie volcanic center; and the CP thrust fault (BN, 2005a). Numerous faults that underlie CP Hogback separate the CP basin from Yucca Flat. A zone of faults near Massachusetts Mountain accommodates changes in the structural styles south of Yucca Flat and further complicates the interpretation of the geologic structure in this area. Thus, the hydrologic relation between the CP basin and both Yucca Flat and Frenchman Flat is highly complicated and uncertain. In other parts of the Frenchman Flat model area, more than 70 faults with

significant displacement (>61 m) have been recognized and are included in the hydrologic model (BN, 2005a). However, faults with small displacement are not always recognized by geophysics, and even when faults are recognized, their internal structure and the juxtaposition of HSUs across them are not well understood.

The present-day water table is deep enough that the alluvium and tuffs are unsaturated beyond the faulted margins of the Frenchman Flat basin, and the alluvial and tuff aquifers in Frenchman Flat are isolated by the LCA from volcanic or alluvial aquifers outside the basin except toward the west. Based on hydrochemical differences, as well as hydraulic head gradients, the LCA does not appear to be the source of groundwater in the tuffs and alluvium of Frenchman Flat (Hershey et al., 2005). Thus, the only possible source of the groundwater in tuffs and alluvium of Frenchman Flat is local recharge and groundwater flow from the CP basin or the Wahmonie Hills to the west. Although the Cane Spring fault appears to impede groundwater inflow from CP basin into Frenchman Flat (Winograd and Thordarson, 1975), the absence of major basin-bounding faults along the western margin of Frenchman Flat and the monoclinical structure and lateral continuity of the HSUs here probably permit some flow into the western part of the Frenchman Flat basin from areas to the west.

3.2 Precipitation and Recharge

As discussed in SNJV (2004d, Section 6.0), precipitation in the vicinity of the NTS is strongly elevation dependent. In the vicinity of Frenchman Flat, precipitation gages with records spanning up to 50 years show that precipitation for Frenchman Flat and CP basin areas is about 5 to 6 inches per year (13 to 15 mm/yr). The low rates of precipitation lead to estimates of recharge rates that are close to zero on the basin floor to as much as several mm/yr in the hills bordering the basin ([Section 2.2](#)). Although the various recharge models that have been developed for Frenchman Flat differ in the details of how that recharge is distributed throughout the basin, they each produce net amounts of recharge that are, at most, 1 percent of the total amount of groundwater flow through the basin. This suggests that groundwater flow velocities will be small in parts of the basin where groundwater is derived predominantly from the local recharge of precipitation.

3.3 Groundwater Discharge

Within the vicinity of Frenchman Flat, the major source of groundwater discharge to the surface is pumping from wells. Pumping wells of interest are those that were pumped for more than one year. Discharge data collected during short-term pumping, such as during well testing, are considered insignificant. The locations of pumping wells located within the Frenchman Flat modeling area and vicinity are shown in [Figure 3-1](#). The pumping wells include 10 NTS water-supply wells and Well RNM-2s, which was pumped for 16 years as part of the CAMBRIC radionuclide migration experiment (RNM).

The total yearly water withdrawals for wells located within the boundaries of the Frenchman Flat area and vicinity are shown in [Figure 3-2](#). The difference between the data from all wells metered or reported (solid blue line in [Figure 3-2](#)) and the water-supply wells (red line in [Figure 3-2](#)) represents withdrawal from Well RNM-2s between 1976 and 1991. The average discharge rates (based on monthly withdrawals for wells located within the boundaries of the Frenchman Flat, southern Yucca Flat, and CP basin area) are summarized in [Table 3-1](#). The NTS water supply wells that contributed to the total pumpage from 1951 to 2003 are included in this table. Total withdrawal from 1975 to 1991 for the CAMBRIC migration experiment at Well RNM-2s is also included. However, between 1967 and 2003, there are no data available for Well UE-5c WW. The total monthly volumes are based on available data only and are, therefore, an underestimation of the actual volumes pumped. Large gaps exist in the pumping records for Wells WW-5A, WW-5B, and WW-5C from the start of pumping in the wells through August 1958, and from July 1967 through December 1982. Data for the latter time period are also unavailable for Wells Army-1 WW, WW-C, and WW-C1 (SNJV, 2004d).

Based on production from the water-supply wells only, groundwater withdrawal peaked during the mid-1960s and then decreased. A larger peak in withdrawal occurred in the late 1980s and early 1990s. Water withdrawal via pumping declined between the early 1990s and about 2000, and has slightly increased since that time. Groundwater was discharged from the AA by six wells, from the TM-WTA by two wells, and from the LCA by three wells. All of these wells, except RNM-2s, are NTS water-supply wells.

Figure 3-1
Location of Groundwater Pumping Wells in the Frenchman Flat Area and Vicinity

Figure 3-2
Total Water Withdrawal from Wells in the Frenchman Flat Area and Vicinity

3.4 Inflow and Outflow (Lateral Boundary Flows and Boundary Heads)

A set of boundary flows and associated boundary heads to be used with the Frenchman Flat CAU model were obtained from the UGTA regional groundwater flow model (DOE/NV, 1997) by calibrating 30 regional-scale flow models implemented with MODFLOW-2000 (Harbaugh et al., 2000). The 30 models considered different combinations of the HFMs for Frenchman Flat (BN, 2005a) and regional recharge models such as the USGS, DRIA and Maxey-Eakin recharge models. Hydrostratigraphic framework models reflecting the different conceptual models were chosen from a larger set of conceptual models to evaluate the effect of uncertainty in the geologic models (Section 2.3.3). The recharge models represent different methods of approximating recharge for the NTS area (Section 2.2). The alternate boundary flows and heads can be used to help evaluate the uncertainty in the CAU flow model associated with the choice of flow system conceptual HFM, recharge model, and boundary conditions. The approach used to calculate these fluxes does not specify the location or locations on the boundary where the flux occurs in each of the 30 models, just bounds on the total amount of net inflow or net outflow through each boundary. A more detailed discussion of the development of boundary fluxes is provided in SNJV (2004d, Section 9.0).

Table 3-1
Summary of Pumping Data for Wells in Frenchman Flat
and Selected Wells in CP Basin and Southern Yucca Flat

Well Name	Period of Record	Average Discharge Rate (million gallons per month)	Average Discharge Rate (m ³ /d)
Army-1 WW	07/1962 to 12/2003	4.9	620
RNM-2s	10/1975 to 08/1991	23.4	2,950
UE-5c WW	02/1967 to 12/2003	Unknown ^a	Unknown ^a
WW-1	02/1964 to 03/1967	2.9	370
WW-4	01/1983 to 12/2003	3.6	450
WW-4A	12/1993 to 12/2003	4.2	530
WW-5A	03/1951 to 12/1970	1.1	140
WW-5B	05/1951 to 12/2003	2.4	300
WW-5C	03/1954 to 12/2003	3.3	420
WW-C	09/1961 to 07/1995	3.4	430
WW-C1	06/1962 to 12/2003	2.1	270

Source: USGS, 2004, and SNJV, 2004d

^aInsufficient or no data to calculate monthly total from 07/1967 through 12/1982.

m³/d = Cubic meters per day

Based on the larger set of HFM/recharge model combinations presented in SNJV (2004d, Section 9.0), a subset of models that span the range local recharge rates and boundary fluxes was selected. The boundary inflow and outflow rates across each of the CAU model boundaries is summarized in [Table 3-2](#). It is clear from this table that groundwater is simulated as flowing from the north and east toward the south and west through the Frenchman Flat CAU-flow model domain. This is generally true for the UGTA regional groundwater flow model regardless of the recharge or HFM model. The lateral boundary fluxes were found to be insensitive to changes to the hydrostratigraphic model (SNJV, 2004d, Section 9.3). The choice of recharge model, in contrast, had a significant impact on the lateral boundary flows and heads, primarily by changing the heads and gradients along the boundaries of the models.

Lateral boundary flows and recharge flux estimates for the Frenchman Flat model domain were also obtained from the DVRFS model (Faunt et al., 2004). This model is implemented using MODFLOW-2000 (Harbaugh et al., 2000). Flux estimates for the DVRFS model summarized in

Table 3-2 are based on pre-pumping steady-state conditions. Flows are generally similar in magnitude and direction as compared to the boundary flows estimated from the UGTA regional model. However, differences in the simulated flows across the southern and eastern boundaries are observed between these two regional flow models. While both models simulate net inflows from the north and east into the Frenchman Flat CAU model domain, the UGTA inflows from the east exceed those from the north; the DVRFS model simulates more flow into the northern boundary. In the DVRFS model, as well in the UGTA models, recharge constituted less than 1 percent of the total outflow from the model domain.

Table 3-2
Regional Model Boundary Fluxes

Model	North (kg/s)	West (kg/s)	South (kg/s)	East (kg/s)	HFM	Recharge Model
UGTA	-367 ^a	1,020 ^b	113	-752	BASE ^c	USGSD ^d
UGTA	-479	1,500	-6	-972	BASE	MME ^e
UGTA	-553	1,500	69.4	-961	BASE	DRIA ^f
UGTA	-367	1,020	113	-752	CPBA ^g	USGSD
DVRFS ^h	-450	341	209	-97	--	--

^aNegative flux indicates flow into the model domain.

^bPositive flux is out of the model domain.

^cBASE is the BASE HFM as defined by BN (2005a).

^dUSGSD is the USGS recharge model with redistribution (SNJV, 2004d).

^eMME is the Modified Maxey-Eakin recharge data (SNJV, 2004d).

^fDRIA is the chloride mass balance recharge model with alluvial mask (SNJV, 2004d).

^gCPBA is the alternative CP basin configuration as defined by BN (2005a).

^hDVRFS is the Death Valley Regional Ground-Water Flow System model (Faunt et al., 2004).

kg/s = Kilograms per second

The UGTA regional model boundary flow analysis is summarized in [Appendix E](#) of the Frenchman Flat hydrologic data document (SNJV, 2004d). The calculated fluxes from the UGTA regional model and the DVRFS model (Faunt et al., 2004) were based on the bottom elevations in both models in the Frenchman Flat area (approximately -4,000 m). However, the Frenchman Flat CAU Phase II model has a spatially variable bottom elevation for the LCA, which ranges between -3,800 and -4,600 m. To compare the Phase II model fluxes along the eastern model boundary with the UGTA regional and DVRFS model fluxes, only nodes above -4,000 m of elevation are included in the boundary flux calculation. This is still an approximation because parts of both the regional and local model domains

locally have a bottom elevation above -4,000 m. However, this is not expected to introduce significant errors because most of the flux in the model occurs at higher elevations, given that intrinsic permeability is assumed to decay with depth in the LCA in all the regional models (Section 4.4.1). Further, these fluxes are used principally to guide the development of the Frenchman Flat CAU flow model to ensure it is reasonably consistent with the regional groundwater system. It is noteworthy that the relative magnitude of the target boundary fluxes in Table 3-2 are consistent with the conceptual model that holds that inflow into the LCA in Frenchman Flat occurs predominantly on the east, rather than from the north from Yucca Flat (Laczniak et al., 1996).

3.5 Hydraulic Heads

This section describes the estimated pre-pumping hydraulic heads used in the steady-state Phase II Frenchman Flat flow model. The pre-pumping heads are assumed to represent long-term steady-state conditions and thus reflect the long-term behavior of the groundwater flow system before activities at the NTS began. As described in Section 3.3 water supply wells have been intermittently pumped since the early 1950s, and water withdrawals may have affected water levels in the vicinity of the pumping wells. To minimize the effects caused by water withdrawals, pre-pumping water levels at the pumping wells were estimated from measurements made during periods preceded by little or no pumping. An initial compilation and evaluation of the Phase II hydraulic head data was documented in SNJV (2004d, Chapter 8). This evaluation included a description of adjustments made to water levels to account for borehole deviation, barometric effects, and water density differences associated with groundwater temperature variations.

Subsequent to the data compilation and analysis reported in SNJV (2004d), an additional round of Global Positioning System (GPS)-based ground-elevation surveys was completed in November 2004 that resulted in refined water-level estimates. The new estimates of pre-pumping water levels that resulted from this effort and differences with the previously reported values are given in Table A.1-1 in Appendix A. The new pre-pumping water levels and the associated uncertainties are listed in Table 3-3. The well locations are shown by HSU in Figure 3-3. The updated steady-state head data listed in Table 3-3 supersede the data presented in SNJV (2004d) and are considered to reflect the long-term steady-state flow conditions in Frenchman Flat.

Table 3-3
Summary of Hydraulic Heads at Target Wells Within the Frenchman Flat CAU Model Domain
 (Page 1 of 2)

Well Reporting Name	Target Steady-State Water-Level Elevation (m amsl)	Minimum Steady-State Water-Level Elevation (m amsl)	Maximum Steady-State Water-Level Elevation (m amsl)	Total Uncertainty ^a (m)
AA				
ER 5-3 (3-in. shallow)	733.9	733.78	734.03	1.06
ER 5-3 #3	733.9	733.84	734.01	1.05
ER 5-4 (piezometer)	733.53	733.39	733.58	0.43
ER 5-4 (main/composite)	733.38	733.31	733.70	0.43
RNM-1 ^b	731.37	730.97	732.00	4.4
RNM-2	733.55	733.55	733.55	0.88
RNM-2s	733.68	733.53	733.81	0.46
UE-5 PW-1	733.79	733.65	734.01	0.71
UE-5 PW-2	733.74	733.63	733.98	0.75
UE-5c WW (composite)	734.56	734.41	734.90	0.62
UE-5f	734.9	734.90	734.90	1.43
UE-5n	733.8	733.74	734.08	0.47
WW-1	727.25	727.25	727.25	4.4
WW-5A	730.6	725.02	730.6	1.14
WW-5B	734.68	733.20	735.14	1.15
WW-5C	729.23	720.15	729.23	1.29
TM-WTA and TM-LVTA				
UE-11a	733.86	733.86	733.86	1.21
UE-11b ^c	734.63	734.63	734.63	1.16
ER 5-3 (3-in. deep)	733.41	733.09	733.88	1.19

Table 3-3
Summary of Hydraulic Heads at Target Wells Within the Frenchman Flat CAU Model Domain
 (Page 2 of 2)

Well Reporting Name	Target Steady-State Water-Level Elevation (m amsl)	Minimum Steady-State Water-Level Elevation (m amsl)	Maximum Steady-State Water-Level Elevation (m amsl)	Total Uncertainty ^a (m)
ER 5-3 (main/composite)	733.88	733.74	734.01	1.07
WW-4	845.51	845.51	845.52	2.02
WW-4A	844.10	843.93	844.24	1.21
UE-5 PW-3	733.75	733.62	733.88	0.71
LCA				
ER 5-3 #2	727.14	Could not be determined		
TW-3	725.52	725.10	726.13	1.21
WW-C	726.00	725.25	727.83	1.45
WW-C-1	727.69	727.47	728.13	1.02

^a Total uncertainty is calculated as the square root of the total variance. The total variance included: land surface elevation, measurement method, and borehole deviation uncertainty.

^b Uncertainty for water-level measurement at Well RNM-1 is higher due to uncertainty about well inclination angle.

^c Water level assigned to Well UE-11b assumes that two numbers have been transposed by mistake from "34" to "43." This is more consistent with historical data at the well, surrounding water-level measurements, and model results.

Note: Water-level data at Well ER-5-4#2 are not included in the target head dataset because no steady-state level could be determined for this well.

Figure 3-3
Location of Wells (with Completion Interval HSUs Identified)
in the Frenchman Flat Area and Vicinity

Table 3-4 lists the mean, standard deviation (SD), and range of the water levels for different HSUs in the Frenchman Flat basin. The summary does not include data for the Timber Mountain HSUs from WW-4 and WW-4a in the CP basin, which are approximately 110 m higher than in Frenchman Flat, or the water-level measurement from the LTCU at Well ER-5-4 #2, which was approximately 755 m and rising at the time this report was being written. The summary statistics in Table 3-4 confirm the conclusions from earlier studies that hydraulic heads in Frenchman Flat have little variability either within the alluvium or between the alluvium and tuff aquifers, and that heads within the alluvial and tuff aquifers are generally about 7 m higher than in the LCA.

Table 3-4
Summary of Water-Level Measurements

HSU	Number of Static Water-Level Measurements (m amsl)	Minimum Static Water-Level (m amsl)	Average Static Water-Level (m amsl)	Maximum Static Water-Level (m amsl)	Standard Deviation (m) ^a
AA	15	720.2	732.9	735.1	1.4
OAA	1	733.8	733.9	734.1	N/A
TM-WTA ^b	4	733.1	733.7	734.0	0.2
TM-LVTA	1	734.6	734.6	734.6	N/A
LTCU ^c	1	N/A	755	N/A	N/A
LCA ^d	4	725.1	726.6	728.1	1.0

^aStandard deviation reported by SNJV, 2004d.

^bWater-level measurements at CP basin for WW-4 and WW-4A are not included in the above data because they are physically separate from the Frenchman Flat basin. These measurements (844 and 845 m) are much higher than those observed within the Frenchman Flat basin.

^cThis anomalous water-level measurement was measured at Well ER-5-4 #2 and is probably not representative of the LTCU in other parts of the Frenchman Flat basin (see text for discussion).

^dThree water-level measurements outside the Frenchman Flat basin are included in these data because they are consistent with the regional LCA data and with the only LCA water-level measurements (727.1 m) available for the Frenchman Flat basin at Well ER-5-3 #2.

N/A = Not applicable

3.5.1 Horizontal Head Gradients

3.5.1.1 Alluvial Aquifer and Older Alluvial Aquifer

Water-level data from the OAA and AA show that differences in water levels in these units are small (less than 5 m) throughout the Frenchman Flat basin (Figure 3-4). The data show an overall

north-to-south gradient between the northernmost wells and the wells along the southern edge of the playa, but as noted by Winograd and Thordarson (1975), there is almost no difference in heads in the northern and central portions of the basin, and most of the head loss occurs in the vicinity of Frenchman Lake Playa; this characteristic was speculated to result from the presence of a northeast-trending barrier of unknown origin along the northwest part of the playa. As discussed earlier, the lower water levels at WW-5C, WW-5A, and WW-1 were interpreted by Winograd and Thordarson (1975) to reflect drainage from the AA to the LCA in these areas.

Because most of the wells tapping the AA (or OAA) in Frenchman Flat are aligned along a north-south trend, there is very little control on the east-west component of the hydraulic gradient. The lower water level reported for WW-1 east of the Frenchman Flat playa imparts an overall west-to-east component to the horizontal gradient. However, water levels do not change significantly in the alluvium between the western part of the basin at Well UE-5c WW and the cluster of wells in the central part of the basin near Well RNM-2s. The much lower water level at RNM-1 compared to the surrounding wells in this cluster reflects the difficulty in accurately determining the vertical depth to water in this well, which was drilled at an angle into a nuclear test cavity.

3.5.1.2 Volcanic Aquifers

Water-level data for the volcanic aquifers in Frenchman Flat are available only from Wells UE-11a, UE-5 PW-3, UE-5c WW (lower), and ER-5-3 (Figure 3-5). These data from the TM-WTA do not show meaningful differences when uncertainty is accounted for, making flow directions within this aquifer uncertain. The water levels in these wells are approximately 110 m lower than water levels measured in the same HSUs in the CP basin at Wells WW-4 and WW-4a.

3.5.1.3 Lower Carbonate Aquifer

Water-level data from the LCA in the vicinity of Frenchman Flat also show relatively little variability within and adjacent to the flow model area (Figure 3-6). Locally, hydraulic gradients are small and do not clearly indicate flow directions into or out of Frenchman Flat. However, based on these data, as well as other more regional water-level data, Winograd and Pearson (1976) proposed the presence of a groundwater trough extending between TW-3 and the regional discharge area at Ash Meadows along which groundwater flow in the LCA was channeled.

Figure 3-4
Alluvial Aquifer Well Locations and Steady-State Heads

Figure 3-5
Volcanic Aquifer and Confining Unit Well Locations and Steady-State Heads

Figure 3-6
Lower Carbonate Aquifer Well Locations and Steady-State Heads

3.5.2 Vertical Gradients

Although the data summarized in [Table 3-4](#) demonstrate the existence of an overall drop in water levels between the AA and the LCA in Frenchman Flat, recent water-level measurements made for multiple completion intervals at the ER-5-3 and ER-5-4 well clusters provide evidence that vertical hydraulic gradients within the OAA or AA are very small. Thus, there is evidence that argues against the occurrence of significant vertical groundwater flow in the northern and central testing areas.

3.5.2.1 ER-5-3 Well Cluster

Hydraulic heads were measured in multiple HSUs between the AA and LCA in each of the three wells (ER-5-3, ER-5-3 #2 and ER-5-3 #3) in the ER-5-3 cluster ([Figure 3-7](#)). These long-term water-level measurements show that vertical gradients within the OAA, or between the OAA and the TM-WTA, are small. Heads from the LTCU were not measured at the ER-5-3 well cluster. However, it is apparent that most or all of the measured head drop of 7 m between the TM-WTA and the LCA must take place across the roughly 500-m-thick LTCU that separates the LCA from the shallow tuff aquifers. This observation is particularly significant because it indicates that near the northern testing area, the LTCU provides a large degree of hydraulic separation between the shallow aquifers and the LCA even though it is relatively thin and faulted near the basin margins (Plate 1).

3.5.2.2 ER-5-4 Well Cluster

In the central testing area, hydraulic head measurements at two depths in the AA from Well ER-5-4, along with heads from nearby Wells RNM-2s and RNM-2, show very little variability with depth in the AA ([Figure 3-8](#)). During the ER-5-4 well cluster multiple-well aquifer test (MWAT) in which a bridge plug was set between the upper and lower completion intervals of ER-5-4, the difference in the head measurement was 1.22 m, indicating an overall downward gradient between the midpoints of these intervals of 0.0031 (SNJV 2004b, p. 2-3). Although this vertical hydraulic gradient is small, it is comparable to or exceeds lateral hydraulic gradients in the area, so small amounts of vertical flow could exist in the AA.

However, deeper head measurements in the LTCU at ER-5-4 #2 show that downward drainage from the AA to the LCA is not only unlikely, but actually prohibited. Hydraulic heads measured in the LTCU at ER-5-4 #2 had risen to about 754 m as of March 2004 and appeared to be stabilizing at a

Figure 3-7
Profile of Hydraulic Heads at the ER-5-3 Well Cluster

Figure 3-8
Profile of Hydraulic Heads at the ER-5-4 Well Cluster

value of approximately 755 m (SNJV, 2004d). Well ER-5-4 #2 did not penetrate the LCA, but head measurements within and adjacent to the flow model area suggest that heads in the LCA near the ER-5-4 well complex would not exceed 730 m (Figure 3-8). Therefore, the heads in the LTCU at ER-5-4 #2 are higher than the heads in both the AA and the LCA by at least 20 m.

Because the only known areas near Frenchman Flat with heads of 755 m or higher are to the west in CP basin or the Wahmonie Hills, the high heads in the LTCU at ER-5-4 #2 must be maintained by a strong hydraulic connection between ER-5-4 #2 and one of these areas. This conceptual model is supported by hydrogeologic cross sections through the ER-5-4 well cluster that show the LTCU rising up along the western flanks of the basin in the Wahmonie Hills area (Plate 1). Moreover, to prevent the heads in the LTCU from being dissipated by leakage to the overlying AA or the underlying LCA, groundwater must be moving through the LTCU under relatively confined conditions. This suggests the presence of a fractured welded interval or lava flow within the thick LTCU that is bounded by less permeable zeolitic rock. It also implies the absence of transmissive faults cross-cutting the LTCU over a several kilometer distance between the Wahmonie Hills and ER-5-4 #2. In conclusion, it appears that the LTCU is overpressurized in the central testing area and that high heads in this HSU effectively prevent groundwater movement from the alluvium downward to the LCA.

3.6 Hydraulic Properties

The rate and direction of groundwater flow depends on both the vertical and lateral hydraulic gradients, and on the magnitude, spatial variability, and directional dependence of permeability within the basin. To help develop the conceptual model of how permeability varies within the Frenchman Flat basin, an initial compilation of permeability data from analogous HGUs in the NTS investigation area was completed and compared to more limited data from comparable HGUs in the Frenchman Flat area (SNJV, 2004d). Data were grouped by HGUs — such as the AA, VA, TCU, CCU, and CA — so that data from similar rock types could be considered collectively and compared to the permeability of individual HSUs in the model. Subsequent to that analysis, additional screening, binning, and analysis of hydraulic test data from the NTS area were done for the purpose of estimating likely ranges of permeability for the different rock types present in Frenchman Flat (Appendix E). These data, along with the more limited data from Frenchman Flat, are used to provide

initial guidance on the permeability values assumed in the Frenchman Flat flow model and, later, to help evaluate alternative flow models by comparing the measured and calibrated permeabilities.

Although permeabilities are initially assigned in the model by HSU, other factors influence and modify these permeabilities, including the anisotropy assigned to the HSU, the rate of decrease in the permeability of the HSU with depth, and the permeability modifications induced by faulting. When horizontal permeabilities (k_h) are higher than the vertical permeabilities (k_v), HSUs with higher anisotropy ratios (k_h/k_v) tend to promote lateral flow at the expense of vertical flow under a given hydraulic gradient. Where permeability decreases with depth because of compaction under increasing lithologic loads, there is also an effective anisotropy introduced by this phenomenon that can exert a similar effect on flow directions (Haneberg et al., 1998). Faults provide potential conduits for flow, or can compartmentalize portions of the flow system depending on whether they channelize or block flow, or some combination of the two, depending on the relative anisotropy associated with fault zone structures like gouge zones.

In summary, the permeability distribution in Frenchman Flat is conceptualized as resulting from the superposition of effects controlled by the HGU type, anisotropy, the decay of permeability with depth, and faulting. Therefore, in addition to summarizing HSU permeability data, the following sections provide site-specific data from Frenchman Flat on anisotropy, depth decay in permeability, and fault hydraulic properties. These data are supplemented with discussions of field data or model results from other sites that might serve as appropriate analogs when sufficient site-specific data from Frenchman Flat are not available, or the site-specific data are ambiguous or contradictory.

3.6.1 HSU Permeability Data

Analysis of hydraulic conductivity data considered three distinct datasets based on the scale of the tests. Evaluations consisted of measurement scale (laboratory-scale, slug- and packer-test-scale, and pumping-test-scale), scaling and spatial distribution, vertical anisotropy, and variation due to temperature. Hydraulic conductivity parameters for each HSU are presented at the end of this section. [Figure 3-9](#) shows the locations where the hydraulic property data were obtained in the Frenchman Flat area and vicinity. For the purposes of the Frenchman Flat CAU flow model, the pumping-scale data are the most appropriate (SNJV, 2004d). Slug tests involve the movement of smaller volumes of water through the formation than would be typical for a pumping test. Therefore,

hydraulic conductivity from a pumping test is representative of a larger volume of the formation that is closer to the scale of a grid cell in the CAU model.

Table 3-5 summarizes the permeabilities from Frenchman Flat, by scale of the test, for each HSU for which there were available data. As shown in Table 3-5, a total of 28, 5, and 70 data points were obtained from pumping-scale tests, slug tests, and laboratory-scale tests, respectively. The table shows that there are only small differences in the mean or variance of the permeability in the AA with changes in the scale of measurement. In contrast, for HSUs in which permeability is controlled by the degree of fracturing (such as the LCA and TM-WTA), there is a pronounced scale effect, with mean permeability becoming much smaller with decreasing scale.

The pumping-scale permeabilities estimated for the NTS investigation area and the Frenchman Flat model area are shown for the AA, VA, TCU, CCU, and CA HGUs in Figures 3-10 through 3-14, respectively. These figures show that the relatively sparse data from the Frenchman Flat area have a relatively consistent relation with the much larger HGU dataset from the NTS area. Hence, statistics and trends in permeability with depth inferred from the larger NTS dataset could be used with some confidence to constrain or evaluate permeabilities used in calibrating the Frenchman Flat flow model.

Unfortunately, comparable datasets from the NTS investigation area do not exist to evaluate the properties of some small volume HSUs in Frenchman Flat embedded within the alluvium. These HSUs include the BLFA and the recent and older playa sediments (PCU2T, PCU1U, and PCU1L). With regard to the BLFA, analogous small-volume basalt eruptions (1 to 3 cubic kilometers [km³]) that have been studied throughout the NTS region (Perry et al., 1998) suggest that these eruptions are characterized by scoria cones and lavas consisting of thin accumulations of flow breccia and discontinuous lava lobes. Zones of enhanced fracture conductivity associated with columnar jointing are expected to occur only locally where lavas thicken in pre-eruption topographic lows.

3.6.2 Vertical Permeability Anisotropy for Alluvium and other Units

Very little is known about the anisotropy of most of the HSUs in Frenchman Flat except for the alluvium. The tuff aquifers and confining units in Frenchman Flat typically are defined on the basis of the predominant stratigraphic units and rock types within the unit, but in actuality are often a mixture of welded, vitric, and zeolitic tuffs (BN, 2005a). The variability in permeability associated with these

Figure 3-9
Frenchman Flat Hydraulic Property Data Locations

Table 3-5
Summary of Permeability for HSUs within the Frenchman Flat CAU Model Domain

HSU	Mean	Standard Deviation	Count	Minimum	Maximum	95% Confidence Interval Bounds	
						Lower	Upper
	log ₁₀ k (m ²)			log ₁₀ k (m ²)		log ₁₀ k (m ²)	
Pumping-Scale Data							
AA	-12.24	0.80	17	-13.24	-10.36	-13.81	-10.68
LCA	-12.15	1.43	5	-10.51	-9.92	-14.95	-9.36
TM-WTA TM-LVTA	-10.73	0.22	5	-11.07	-10.45	-11.17	-10.32
LTCU	-13.10	N/A	1	N/A	N/A	N/A	N/A
Slug-Test-Scale Data							
AA	-12.27	N/A	2	-12.55	-11.99	N/A	N/A
BLFA	-12.40	N/A	1	N/A	N/A	N/A	N/A
TM-WTA	11.94	N/A	2	-11.94	-11.93	N/A	N/A
Laboratory-Scale Data							
AA	-12.36	0.73	50	-14.94	-11.32	-13.80	-10.93
TM-WTA	-12.49	0.76	11	-13.91	-11.57	-13.98	-10.99
LCA	-15.70	1.38	9	-18.02	-13.72	-18.40	-13.00

Source: Modified from SNJV, 2004d, Table 5-1

m² = Square meter

lithologic variations is likely to cause permeability parallel to bedding to be higher than the permeability across the beds. However, this expected relationship becomes complicated by the variable dip of the units across the basin, and by steeply dipping faults that would be expected to enhance the permeability parallel to the fault (see [Section 3.6.4.2](#)). Because of the conceptual and data uncertainty surrounding the anisotropy of the tuffs, their anisotropy is relatively unconstrained and left as a calibration parameter. The UCCU and LCA have been subjected to multiple orogenic events that have left these HSUs with a variety of orientations and dips (BN, 2005a). Consequently, because there is no simple basis for assessing the dip of these beds or in assigning anisotropy values, no anisotropy values are assumed for these HSUs. To the extent that anisotropy exists in the LCA, it is probably associated with the structural fabric of the rock, which is implemented in the model through the inclusion of major faults like the Rock Valley fault system.

Figure 3-10
Permeability Data for the AA HGU from the NTS and Frenchman Flat Areas

Figure 3-11
Permeability Data for the VA HGU from the NTS and Frenchman Flat Areas

Figure 3-12
Permeability Data for the TCU HGU from the NTS and Frenchman Flat Areas

Figure 3-13
Permeability Data for the CCU HGUs from the NTS Areas

Figure 3-14
Permeability Data for the CA HGU from the NTS and Frenchman Flat Areas

In an alluvial system with variable hydraulic conductivity with depth at a specific location, the effective anisotropy will be a function of the variation of hydraulic conductivity with depth, the thickness of each identified layer, and the continuity of the layer. If layers have limited continuity laterally, the effective anisotropy would tend to be lower compared to a geologic environment that had larger continuity or lateral extent to the layers. The layering and its continuity, or lack thereof, results from the depositional environment that existed as the basin-fill materials were deposited. At a specific borehole location, one can calculate the anisotropy of the geologic system as the ratio of horizontal-to-vertical hydraulic conductivity. In heterogeneous geologic systems, the geometric average of individual permeabilities or hydraulic conductivities provides the best average representation (Warren and Price, 1961). The equivalent horizontal hydraulic conductivity (assumed parallel to the layering) can be estimated as the geometric average expressed:

$$K_h = \exp[\Sigma(b_i \ln K_i) / \Sigma b_i] \quad (3-1)$$

and the equivalent vertical hydraulic conductivity can be estimated as the harmonic average expressed:

$$K_v = \Sigma b_i / \Sigma (b_i / K_i) \quad (3-2)$$

where K_h and K_v are horizontal and vertical hydraulic conductivities, respectively, and K_i are the hydraulic conductivities of the individual layers b_i . It can be seen from these equations that inclusion of a few very low hydraulic conductivity layers has a relatively small effect on K_h but has a large effect on K_v and thus the magnitude of anisotropy.

Vertical anisotropy, here expressed as the ratio of horizontal-to-vertical hydraulic conductivity, can be considered to be scale dependent. At the small scale of an individual clay layer, Freeze and Cherry (1979) indicate that it is seldom greater than 10:1 and usually less than 3:1. In a layered system, they report that it is not uncommon for layered heterogeneity to lead to regional anisotropies on the order of 100:1 or even larger.

Over vertical distances of tens or hundreds of meters, anisotropy can be determined from data at a single well by evaluating the variability in hydraulic conductivity with depth from flow logs or from core-scale measurements. Over a similar range of vertical depths, anisotropy can be calculated over horizontal distances of tens or even hundreds of meters from cross-hole tests when the hydraulic responses are monitored at different elevations than the pumping interval. This type of testing was done at the ER-5-3 well cluster in northern Frenchman Flat (SNJV, 2004c) and during the MWAT conducted in the central testing area with RNM-2s as the pumping well (SNJV, 2004b).

Determination of regional-scale anisotropy from field testing is generally impractical because of the very large time scales for monitoring that generally may be required. Hence, regional-scale anisotropy is typically determined through the calibration of regional-scale groundwater flow models. In this case, the degree of vertical discretization in a numerical model can have an effect on the model calibration to determine anisotropy. If the vertical heterogeneity is known and is included at the discretization level, then smaller values of regional anisotropy are appropriate. In any case, model discretization must be considered when comparing different flow models or flow model results with field-derived anisotropy values.

A number of methods were applied to estimate the anisotropy of the alluvium in Frenchman Flat. These include somewhat indirect approaches that analyze hydraulic conductivity variations from borehole flow logs and core sample data, and more direct field methods such as cross-hole hydraulic tests. Additional anisotropy values are estimated from (1) site-specific models for Frenchman Flat that were developed either to interpret MWAT data from Frenchman Flat or that are calibrated based on these data, and (2) from regional models for the NTS and elsewhere that have estimated the anisotropy of alluvium in similar basins from steady-state and transient head data. Each of these approaches and the resulting estimates are described below.

3.6.2.1 Evidence from Borehole Flow Logs and Core Samples

This section evaluates evidence for anisotropy in the alluvium of Frenchman Flat provided by borehole flow logs and core-scale permeability data. The flow logs were measured at the ER-5-3 and ER-5-4 well clusters as part of the Frenchman Flat characterization studies (SNJV, 2004b and c). The core-scale permeabilities were measured on samples from the unsaturated zone in northern Frenchman Flat that were collected to characterize processes related to shallow waste disposal and containment.

3.6.2.1.1 Flow Logs

Borehole flow logging results for Wells ER-5-3 and ER-5-4 were examined to determine vertical variations in the hydraulic conductivity of the alluvium. Data from Well ER-5-3, which was screened individually within the OAA (441 to 543 m bgs) and the TM-WTA (723 to 794 m bgs), did not provide much information about anisotropy in the OAA because of the relatively minor amounts of flow (< 3 percent) contributed by the OAA (SNJV, 2004b and c). Although the flow logs did not provide data that could be used to calculate anisotropy ratios in the OAA, the relative amounts of flow contributed by the OAA and the TM-WTA (> 97 percent) and the relative lengths of the screened intervals in these HSUs indicated that the TM-WTA was about 50 to 150 times more permeable than the OAA near the ER-5-3 well cluster.

Well ER-5-4 is completed and fully cased through the AA to a total depth of 1,138 m bgs (SNJV, 2004d). The casing is screened over two intervals: the upper between 539 and 644 m bgs, and the lower between 956 and 1,021 m bgs. Stressed flow logging was performed at three rates and

across both screened intervals, measuring interval flow at 6-cm resolution. These data were used to calculate interval hydraulic conductivity profiles, averaged over larger 0.6-m intervals, for grouped flow rate profiles at each of the three pumping rates (Oberlander, 2001). Horizontal and vertical hydraulic conductivity, calculated as the harmonic and arithmetic interval-conductivity means, respectively, yielded calculated anisotropies close to unity for each of the screened intervals. This is not surprising, because the tested borehole intervals appear to have been located in the more permeable (and perhaps homogeneous) sections of the alluvial deposits.

3.6.2.1.2 Core Samples

Alluvium anisotropy was also examined using 7.6-cm borehole core-scale data sampled at Wells UE-5 PW-1 (34 samples) and UE-5 PW-2 (16 samples) (SNJV, 2005a). Cores were sampled at about 1- to 10-m intervals. Hydraulic conductivity was measured using a constant-head permeameter. Although the sample support is small, each core-scale datum is assumed to represent that of the complete interval between measurement points. The horizontal-to-vertical conductivity ratios (k_h/k_v) determined for UE-5 PW-1 and UE-5 PW-2 are 13 and 4, respectively. Considering the limitation of having only a small number of core samples, it is unlikely that the full possible range in hydraulic conductivities was sampled at these boreholes. Thus, the calculated anisotropies may be lower-end estimates.

3.6.2.2 Interpretations from Frenchman Flat Multiple-Well Aquifer Tests

Two MWATs were conducted in Frenchman Flat in which hydraulic responses were recorded at elevations different from that of the pumping interval. Because hydraulic stresses were transmitted across as well as along layers, directional permeabilities and anisotropy ratios could be determined from these tests.

The first MWAT was conducted in the ER-5-3 well cluster in the northern testing area and involved three wells (ER-5-3, ER-5-3 #2, and ER-5-3 #3) and two piezometers located within 36 m of each other (SNJV, 2004c). The 60-day MWAT was conducted by pumping the upper interval of ER-5-3 located in the OAA. Interpretations of the pressure response at Well ER-5-3 #3 and the shallow piezometer at ER-5-3 yielded a horizontal-to-vertical permeability ratio of 7.7 (SNJV, 2004c, Table 3-13).

A 75-day MWAT was conducted in the central testing area with RNM-2s as the pumping well and nine wells used as observation wells (SNJV, 2004b). Four of these wells (RNM-2s, RNM-2, RNM-1, and ER-5-4 [upper zone]) produced hydraulic responses that could be attributed to pumping at Well RNM-2s. Interpretations of the hydraulic responses observed at RNM-2, RNM-1, and ER-5-4 (upper zone) produced estimates of horizontal and vertical hydraulic conductivity (SNJV, 2004c, Table 4-1) that can be used to calculate anisotropy ratios of 42, 3.2 and 360, respectively. The value of 3.2 estimated from the RNM-1 response may be less reliable than the other estimates because RNM-1 monitored water levels in the CAMBRIC nuclear cavity, where sedimentary structure and permeability was undoubtedly affected by the CAMBRIC nuclear test.

The MWAT centered around RNM-2s in the central testing area was interpreted in an alternative way by the USGS, as reported in SNJV (2004c). Assuming the alluvium was homogeneous and anisotropic, numerical modeling with MODFLOW and through type-curve analysis yielded horizontal-to-vertical anisotropy ratios of 1.1 to 2.5 for the range of assumptions and methods employed in the USGS analysis, which simultaneously optimized the fit to the hydraulic response at all the observation wells (SNJV, 2004c, Table 4-3).

3.6.2.3 Evidence for Alluvial Anisotropy from Groundwater Models

3.6.2.3.1 Frenchman Flat Models

Numerical models of groundwater flow and radionuclide transport have been developed to calculate the radionuclide source term from the CAMBRIC test cavity (Tompson et al., 1999 and 2005). The recent modeling efforts were used to match radionuclide breakthrough from the CAMBRIC cavity to the pumping Well RNM-2s during the CAMBRIC migration experiment conducted between 1975 and 1991, and estimate the effects of re-infiltration of the RNM-2s discharge water through a nearby drainage ditch on water levels and radionuclide breakthrough at nearby wells. To provide a basis for property variations within the model, 10 model layers were defined based on mineralogic studies of the alluvium at nearby Wells ER-5-4 and UE-5n (Warren et al., 2002; Carle et al., 2002). Hydrologic properties of the model were identified by trial-and-error calibration to the cross-hole hydraulic responses to the MWAT conducted by pumping Well RNM-2s (SNJV, 2004c). These properties assume that each of the individual 10 model layers has an intralayer anisotropy ratio (k_h/k_v) of 2.0 (Tompson et al., 2005, Table A-2). When the thickness-weighted arithmetic and harmonic means of

the eight layers between the water table and the bottom of the model are calculated to estimate k_h and k_v of the saturated alluvium, and the resulting interlayer anisotropy ratio (k_h/k_v) of 17 is multiplied by 2 to account for the intralayer anisotropy, a total anisotropy ratio for the alluvium of 34 is obtained.

3.6.2.3.2 Regional NTS Models

Regional-scale groundwater model calibration studies at the NTS and other analog sites can be useful to determine an expected range for anisotropy. Regional groundwater modeling studies for the NTS and vicinity use depth decay in hydraulic conductivity and also vertical anisotropy during model calibration. As described in [Section 3.6.3.2](#), it is expected that both of these approaches would have somewhat similar impacts during model calibration because they both tend to reduce downward flux to achieve a similar vertical gradient (i.e., by fitting targeted head values at wells in the AA and LCA). The UGTA regional model report (DOE/NV, 1997, Table 7-7) lists anisotropies from 4.5 to 6.3 and a depth-decay parameter of 0.0037 for the zones of alluvial aquifer material. The calibrated Pahute Mesa CAU groundwater flow model used an anisotropy value of 10 in the base model and 50 in the SCCC HFM model for both the selected and all HSU calibration approaches. Faunt et al. (2004, Tables F-12 and F-13) give a calibrated anisotropy ratio of 5,000 and a depth-decay parameter of 0.0123 for basin-fill aquifers for the transient DVRFS model. Faunt et al. (2004) discussed that the basin-fill units are the most likely to exhibit stratification that would tend to decrease the vertical relative to the horizontal hydraulic conductivity. The anisotropy range (4.5 to 5,000) for basin-fill deposits from regional groundwater flow models for the NTS region is large and indicates anisotropy is a highly uncertain parameter in those studies.

3.6.2.3.3 Other Basin-Scale Regional Models

McAda and Barroll (2002) described a 3-D groundwater flow model of the Santa Fe Group aquifer system within the Middle Rio Grande basin between Cochito and San Acacia, New Mexico. This basin is one of a series of generally south-trending structural basins composing the Rio Grande Rift. The sedimentary fill of the basin is composed of valley and basin-fill deposits of up to 4,300-m thickness. They reported that previous calibrated groundwater models of the basin have used horizontal-to-vertical anisotropy ratios of 450:1 to 3,500:1 (Tiedeman et al., 1998) and 200:1 (Kernodle et al., 1995). The basin model was calibrated by McAda and Barroll (2002) with an anisotropy ratio of 150 applied uniformly throughout the model.

Regional-scale transient calibrated groundwater flow models have been reported for the Carrizo-Wilcox aquifer in Texas. The aquifer consists of fluvial-deltaic sediments with the Carrizo being more of a fluvial origin. In the downdip portions of the aquifer, thicknesses are typically thousands of meters and extend from central Texas to under the Gulf of Mexico. Fryar et al. (2003) found that while their initial calibrated pre-development steady-state model could meet the calibration criteria, the subsequent transient calibration indicated that the vertical hydraulic conductivities must be decreased by orders of magnitude. The transient calibrated value for anisotropy was 100 in the Carrizo and 10,000 in the Wilcox model layers. Ryder and Ardis (1991) developed a transient calibrated groundwater model for the U.S. Gulf Coast aquifer system. For the equivalent Carrizo and Wilcox geologic layers in their groundwater flow model, the ratio of their mean horizontal-to-vertical hydraulic conductivity was from 4,000 to 15,000.

Because of the fluvial-deltaic nature of deposition, it would be expected that the larger anisotropies (10,000 and greater) determined from the Texas Gulf Coast groundwater models are much larger than those that would be considered reasonable for Frenchman Flat. The nature of the deposits in the Middle Rio Grande basin in New Mexico, which yielded an anisotropy value of 150, may be more similar to those in Frenchman Flat.

3.6.2.3.4 Anisotropy Summary

Anisotropy at the field scale is often dominated by the effects of sedimentary layering rather than grain texture or orientation. As such, field estimates of anisotropy are affected by the lateral and vertical extent of the layering, the permeability contrasts between the layers, and the scale of the tests. Tests that affect enough of the aquifer to integrate the effects of discontinuous layers probably provide the most representative values to use in numerical models. In tests analyzed with numerical models, the calibrated anisotropy ratio may also depend on whether layers are explicitly represented in the model or are lumped together in an equivalent unit. To the extent that layering is explicitly represented in the model, the need for large values of anisotropy for individual layers within model may be reduced. Numerical models also appear to require larger values of anisotropy when transient conditions exist compared to steady state, perhaps because vertical gradients under steady-state conditions are either small or poorly characterized in many modeling studies.

In Frenchman Flat, MWATs or numerical models calibrated to the cross-well responses provide the best estimates of field-scale anisotropy. Multiple-well aquifer tests at the ER-5-3 cluster indicate the OAA has a horizontal-to-vertical anisotropy ratio of 7.7. The MWAT at RNM-2s produced a range of anisotropy estimates for the AA that included values of 1.1 to 2.5 for numerical and analytical models done by the USGS (SNJV, 2004c) to provide the best overall fit to the hydraulic response, values estimated by UGTA personnel of 42 to 360 based on the responses at wells RNM-2 and ER-5-4 (upper zone) (SNJV, 2004c), and a value of 34 estimated from the permeabilities of a multilayer model used to calibrate the flow model used to estimate the CAMBRIC source term (Tompson et al., 2005).

3.6.3 Permeability Depth Decay

A review of the literature demonstrates that depth decay in permeability or hydraulic conductivity has been recognized for decades by investigators in many geologic environments and has also been routinely adopted in groundwater modeling studies. This reduction in permeability with depth has a sound technical basis. It is generally presented in the context of porosity reduction (and correlated permeability reduction with porosity reduction) with depth as a consequence of compaction and/or geochemical processes for unfractured formations, and as a consequence of fewer fractures present and fracture closure at higher in situ stresses for fractured formations. The plots of measured hydraulic conductivities versus depth that are reported in the literature show a relatively large amount of scatter, and thus a large amount of spread about any best-fit line representing the functional relationship of decreasing permeability or hydraulic conductivity versus increasing depth. The degree of data scatter shown for plots of hydraulic conductivity versus depth for Frenchman Flat and NTS data is consistent with the degree of scatter in other published studies in the literature (e.g., Rasmuson and Neretnieks, 1986; Loucks et al., 1986; Prudic, 1991; Kuiper, 1994; Mace and Dutton, 1994; Stober, 1996; Mace, 1998; Williamson and Grubb, 2001; and Budd, 2001). However, utilizing these depth-dependent relationships has been demonstrated as a useful approach to assist in parameterizing groundwater flow models because often there are limited data available to characterize the full depth and lateral extent of all HSUs in large regional groundwater flow models. Initial depth-decay relationships based on site-specific data are valuable starting points for model parameterization that can then be modified during model calibration. An in-depth literature review and discussion of the technical basis for permeability depth decay is presented in [Appendix B](#).

Previous analyses of hydraulic conductivity data used in conjunction with the development of the UGTA regional flow model (DOE/NV, 1997; IT, 1996d) indicated that measured hydraulic conductivities across the NTS region decrease with depth below ground surface in alluvial, volcanic, and carbonate aquifers. A linear relationship between the logarithm of hydraulic conductivity and depth was fit that represents hydraulic conductivity exponentially decaying with depth (IT, 1996d). The relationship between hydraulic conductivity and depth for HSUs in the NTS area was described by the following equation:

$$K_{depth} = K_h 10^{-\lambda d} \quad (3-3)$$

where:

K_{depth} = horizontal hydraulic conductivity at specified depth (L/T)

K_h = horizontal hydraulic conductivity at land surface (L/T)

λ = hydraulic conductivity decay coefficient (1/L)

d = depth from land surface (L)

Depth decay of hydraulic conductivity has been used in groundwater flow models in the proximity of, or encompassing, the Frenchman Flat CAU model area. These models include the UGTA regional model (IT, 1996d) and the DVRFS model (Faunt et al., 2004); however, the implementation of depth decay varies by model. The UGTA regional flow model used depth decay of hydraulic conductivity for all HSUs. In the DVRFS model, depth decay of hydraulic conductivity was primarily applied to all volcanic-rock units and basin-fill units (Faunt et al., 2004) using the decay coefficients calculated by IT (1996d). Depth decay was also applied to portions of the LCA to improve the DVRFS model calibration.

For the Frenchman Flat CAU flow model, depth decay was applied to all alluvial, volcanic, and carbonate units. Mean depth-decay coefficients reported by IT (1996d) for alluvial, carbonate, and volcanic aquifers were selected for use in the Frenchman Flat flow model ([Table 3-6](#)). The larger the depth-decay coefficient, the more rapidly hydraulic conductivity (or intrinsic permeability in the case of the finite element heat-mass transfer code [FEHM]-based CAU-scale models) decreases with depth. Thus, based on the depth-decay coefficients in [Table 3-6](#), the permeability of the alluvium decreases more rapidly with depth than that of either the volcanic or carbonate rocks.

Sufficient data to evaluate depth decay in permeability do not exist for HSUs other than the AA and OAA, and these data do not clearly support the use of depth decay in the alluvium of Frenchman Flat

Table 3-6
Hydraulic Conductivity Depth-Decay Coefficients for NTS Area Aquifers

Aquifer	Decay Coefficient (m ⁻¹)		
	Lower 95% Confidence Interval	Mean	Upper 95% Confidence Interval
Alluvial	0.00724	0.00563	0.00402
Carbonate	0.00160	0.00102	0.00044
Volcanic	0.00306	0.00256	0.00205

Source: IT, 1996d

(Figure 3-10). Although the permeability data from Frenchman Flat alone do not clearly support the use of depth decay in permeability, SNJV (2004d) reported that some of the apparent scatter in hydraulic conductivity measurements was due to differences in the interpretation of the mean depths of the test intervals, and to differences in the assumptions and methods used to interpret the test response. Thus, at least some of the scatter in the AA data from Frenchman Flat represents uncertainty associated with the test interpretations and not heterogeneity associated with depositional processes. As discussed in Section 3.6.3.1, the continued use of depth decay for the permeability of the AA in Frenchman Flat is supported by an analysis of borehole flow log data from Well ER-5-4 which demonstrate that depth decay is required to explain the vertical variations in flow rates measured at that well.

A re-analysis of permeability data from the NTS investigation area (Appendix E) following completion of the modeling done in this report also supports the use of depth decay in the AA, VA, TCU, and LCA HSUs (Table E.1-2). The depth-decay coefficients estimated from the NTS dataset when these were rebinned according to the predominant HGU (Table E.1-2) indicate that the depth-decay coefficients listed in Table 3-6 are reasonable estimates. The mean values listed in Table 3-6 fall within the two SD uncertainty of the revised mean depth-decay coefficients except for the VA HGU. For this HGU, the newly estimated decay coefficient had an upper bound that was slightly lower (0.0023) than the mean value estimated for volcanic aquifers and confining units in Table 3-6.

The fact that some of the scatter in the Frenchman Flat permeability data for the AA is attributable to uncertainty surrounding assumptions in the analysis methods (rather than to heterogeneity), combined

with strong evidence from the re-analysis of the NTS data and the ER-5-4 flow log demonstrates that depth decay should be considered for the AA (and other HSUs) in Frenchman Flat. For these reasons, the conceptual model for the flow system in Frenchman Flat continues to regard depth decay (with the decay coefficients listed in [Table 3-6](#)) as a likely conceptual model, although alternative assumptions regarding the existence of depth decay in the AA are made for certain alternative models (see [Section 6.0](#)).

3.6.3.1 Evidence for Depth Decay in Alluvial Permeability from Well ER-5-4 Flow Logs

Flow logging was conducted in the alluvium at Well ER-5-4 at flow rates ranging from 70 to 176 gallons per minute. The flow logs were normalized by dividing the measured cumulative flow at any depth by the total pumping rate. When normalized to show the fraction of the total flow entering the borehole beneath the measurement depth, the flow logs nearly coincide, indicating that the relative amounts of flow entering the well are relatively insensitive to the pumping rate ([Figure 3-15](#)).

Figure 3-15
Normalized Flow Log Data from ER-5-4

Several features of the normalized flow logs provide insight about hydraulic conductivity variations in the alluvium near Well ER-5-4. First, the overall absence of abrupt increases in flow rate indicates that large variations in hydraulic conductivity associated with alluvial layering are absent within the logged depth interval. Secondly, the relatively smooth, exponentially increasing flow rates with decreasing depth indicate that flow rates increase nonlinearly with saturated thickness, and hence that hydraulic conductivity is increasing with elevation (decreasing depth) in the well. This second observation suggests that the flow log data from Well ER-5-4 could be used to estimate a depth-decay coefficient for the hydraulic conductivity of the alluvium in Frenchman Flat.

It can be shown that in a medium in which hydraulic conductivity decreases with depth according to the model used in this study equation (3-1), a corresponding expression for the transmissivity of the medium between any two depths z_2 and z_1 ($z_2 > z_1$) can be derived:

$$T_{z_2-z_1} = K_0 / (-2.303\lambda)^2 [(-2.303\lambda z_2 - 1) \cdot e^{-2.303\lambda z_2} - (-2.303\lambda z_1 - 1) \cdot e^{-2.303\lambda z_1}] \quad (3-4)$$

The fractional cumulative inflow to a well beneath a given depth depends on the hydraulic gradient toward the well and on the depth-integrated transmissivity between the effective bottom of the transmissive interval (z_2) and the depth at which the cumulative flow was measured (z_1) is:

$$Q_{z_2-z_1} = T_{z_2-z_1} (dH/dr) \quad (3-5)$$

Under the assumption that the hydraulic gradient toward the well is the same at all depths, the change in cumulative flow with elevation at a well is directly proportional to the increase in depth integrated transmissivity with elevation. Based on this approximation, a value for the depth-decay coefficient λ of the AA was estimated with equation (3-2) by visually optimizing the fit of the equation to the normalized flow log data. For this analysis, the bottom of the transmissive interval of the alluvium (z_2) was taken as the contact between the alluvium and the older playa sediments at a depth of about 2,300 ft and the value of z_1 was taken to coincide with specific depths at which the normalized cumulative flow was measured. The results of this optimization show that a value for λ of 0.01 m^{-1} provides a good fit to the normalized flow log data from Well ER-5-4 (Figure 3-16). The value for λ of 0.00563 m^{-1} estimated from the regional NTS data provides a less satisfactory (although possibly acceptable) fit, but the fit with no depth decay ($\lambda = 0.0 \text{ m}^{-1}$) clearly does not agree with the flow log data. Thus, flow log data from Well ER-5-4 appear to support the use of a conceptual and numerical

model for the alluvium in Frenchman Flat in which hydraulic conductivity decreases exponentially with depth.

Figure 3-16
Match of Depth-Integrated Transmissivity Model to
Normalized Flow Log Data from Well ER-5-4.

3.6.3.2 The Relation Between Anisotropy and Depth Decay

Using thickness-weighted arithmetic and harmonic permeabilities in directions parallel and perpendicular to bedding (Freeze and Cherry, 1979), it can be shown that for aquifers in which permeability decreases exponentially with depth as in equation (3-1), the effective anisotropy associated with the depth decay of permeability is

$$k_z/k_x = 5.304 \lambda^2 (z_2 - z_1)^2 / (e^{2.303\lambda(z_2 - z_1)} + e^{-2.303\lambda(z_2 - z_1)} - 2) \quad (3-6)$$

or

$$k_z/k_x = 2.652 \lambda^2 (z_2 - z_1)^2 / (\cosh [2.303\lambda(z_2 - z_1)] - 1) \quad (3-7)$$

where:

k_z/k_x = vertical to horizontal permeability ratio

z_2 and z_1 = the depths (m) over which the anisotropy ratio is calculated ($z_2 > z_1$)

$\cosh$ = hyperbolic cosine

To illustrate the relation between depth decay and anisotropy described by equations (3-4) and (3-5), an example was considered in which the water table is at a 200-m depth and $\lambda = 0.005 \text{ m}^{-1}$ (approximately the value of λ used for the AA). For these parameters, the effective anisotropy of the alluvium between the water table ($z_1 = 200 \text{ m}$) and total depth of the alluvium (z_2) is shown to be a function of total alluvial thickness (Figure 3-17). Alluvial thickness increases from less than 100 m along the margins of the basin to more than 1,400 m toward the center of the basin (BN, 2005a). Thus, toward the deepest part of the basin, the anisotropy induced by the depth decay is about $k_z/k_x = 0.0002$ (or, using the previous convention for reporting anisotropy, $k_H/k_v = 5000$). In contrast, where the alluvium is less than about 700 m (the saturated thickness is less than 5000 m), the overall anisotropy induced by depth decay is approximately 0.1 (or $k_H/k_v = 10$).

However, a second way of interpreting Figure 3-17 is that anisotropy induced by depth decay of permeability between any two depths depends only on the difference in their depths and not on the absolute values of their depths. For instance, anisotropy induced by depth decay between the water table depth of 200-m and a 700-m depth (roughly 0.1) is the same as the anisotropy induced by depth decay between a 700-m depth and a 1,200-m depth. This interpretation was verified by computing the anisotropy over successive 100-m depths between the water table and 1,500 m (Figure 3-18). Over each 100-m interval, k_z/k_x is approximately 0.9 (or $k_H/k_v = 1.1$) regardless of the absolute depth of the interval. This shows that on a local scale (say, the upper 100 m of the saturated zone or even the upper 500 m of the saturated zone), only a relatively modest degree of anisotropy is introduced as a result of depth decay.

In contrast, anisotropy caused by fine-scale layering could significantly affect flow directions over a much narrower range of depths (say, the upper 100 m) compared with effects introduced by depth decay, which become significant only over depth ranges of many hundreds of meters. The effects of layering and depth decay on anisotropy thus operate at different spatial scales and should be treated separately in the flow model. In summary, despite the fact the depth decay can introduce an overall anisotropy to the AA that can be very strong in the deepest parts of the basin, it is reasonable to

include an additional anisotropy term to capture the effects of smaller scale layering that would affect the trajectory of groundwater locally, such as in the upper 100 m of the saturated zone.

Figure 3-17
Effective Anisotropy as a Function of Alluvial Thickness

3.6.4 Fault Properties

3.6.4.1 Basin-Fill Faults

Although most of the approximately 70 faults that are included in the Frenchman Flat flow model are located in consolidated tuffaceous and carbonate rock, a smaller number (10 to 15) have been modeled as propagating through the alluvium to the water table. Despite their relatively small length and offset, the hydrologic properties of these faults are of interest because they are close to, and in some cases within, the areas where underground nuclear weapons tests have been conducted and are thus potential pathways for radionuclides leaving the test areas.

Figure 3-18
Anisotropy Induced by Depth Decay for 100-m Intervals between the water table (200 m) and a Total Alluvial Thickness of 1,500 m

Unfortunately, no direct observations of fault structures or measurements of hydraulic properties are available for faults in the alluvium in Frenchman Flat. However, based on studies of faults that cross-cut alluvium in other tectonically controlled basins, it seems that faults in alluvium and other poorly consolidated sediments are usually low-permeability features because of fault-induced changes to the sediment structure and the absence of open fractures (e.g., Heynekamp et al., 1999; Sigda et al., 1999; Rawling et al., 2001; Cashman and Cashman, 2000). Faults in poorly consolidated sediments consist of: (1) an outer damage zone that contains fault-related structures such as gentle folds, deformation bands, and minor slip surfaces (across which displacement is less than bed thickness); (2) a mixing zone in which displacement is greater than bed thickness and in which originally bedding structures are overprinted by a deformational fabric or completely destroyed through tectonic mixing; and (3) a central core zone that accommodates most of the slip within the fault zone and that is often characterized by multiple slip surfaces along strongly foliated clays. The mixing and damage zones are present in both the footwall and the hanging wall.

Heynekamp et al. (1999) indicate that strain in sandy layers in the damage and outer mixing zones is accommodated primarily by the formation of deformation bands, within which grain size and porosity are reduced by cataclasis (selectively affecting weaker grains like feldspar phenocrysts and lithic fragments), and by grain reorganization. These processes result in strain hardening and greater induration within the deformation band, so that additional strain is accommodated by the initiation of a nearby deformation band, eventually culminating in a swarm of such bands. Strain within clay-rich beds is accommodated primarily by bed-parallel slip and eventual reorientation of the beds as the fault core is approached. Indeed, Heynekamp et al. (1999) suggest that clay-rich fault cores develop, at least in part, from the thinning, reorientation, and smearing of clay beds. The mixing zones and clay-rich core are absent in fault zones where displacement is less than bed thickness. However, even for these small displacement faults, the deformation bands within the fault zone have lower porosity and contain significantly more clay-sized particles compared with the adjacent undisturbed sediments (Sigda et al., 1999, Table 2). In addition to these features, coarse-grained sediments within the fault zone can be preferentially cemented with calcite relative to adjacent sediments. In the Albuquerque basin of New Mexico, calcite was preferentially deposited in coarse-grained sediments of the hanging wall mixed zone of a major basin-forming fault, and its presence was used to infer the influence of the fault on paleo-flow directions (Mozley and Goodwin, 1995; Heynekamp et al., 1999).

Small-scale measurements of permeability made in the different elements of fault zones in poorly consolidated sediments indicate that (1) the permeability across deformation bands is about two to three orders of magnitude less than the sands that contain them; (2) the permeability of mixed zones is intermediate between the coarse- and fine-grained beds of the adjacent undisturbed sediments and depends strongly on the measurement location within the mixed zone; and (3) the permeability of the clay core is similar to that in adjacent undisturbed clay layers and can be about seven orders of magnitude less than that of nearby undisturbed sand layers (Sigda et al., 1999, Figure 3; Rawling et al., 2001). The net effect of faults in the alluvium is to reduce the cross-fault permeability by two or more orders of magnitude while leaving the fault-parallel permeability largely unchanged (a small increase in the calculated fault-parallel permeability may occur if the mixed zone permeability is higher than the harmonically-averaged permeability of the clay and sand layers) (Rawling et al., 2001; Figure 4).

As a result of the orders-of-magnitude reduction in the cross-fault permeability and the resulting large-scale horizontal anisotropy induced by the faults, groundwater flow in basins containing faulted sediments is expected to be preferentially aligned with the strike of the faults (Heynekamp et al., 1999; Rawling et al., 2001; McAda and Barroll, 2002). These studies, among others, have also proposed that faults in poorly consolidated sediments can compartmentalize an aquifer or petroleum reservoir, leading to higher-than-expected drawdowns when the aquifer or reservoir is pumped.

In summary, the alluvium in Frenchman Flat appears to have been deposited at least partly contemporaneously with basin development, based on the presence of through-going faults in the alluvium (BN, 2005a). The inference from mineralogic studies is that source areas for the alluvium shifted through time as structural blocks adjacent to the basin rose or fell relative to each other (Warren et al., 2002). Conceptually, the presence of growth faults within the basin is also indicated by geologic cross sections that show faulting and erosion of uplifted parts of deep volcanic and sedimentary layers in the central part of the basin (BN, 2005a, cross section B-B') and significant late-stage faulting that post-dates the deposition of the BLFA and OAA HSUs in northern Yucca Flat (BN, 2005a, cross section C-C') ([Figure 3-19](#)). Nonetheless, based on analog studies of faults in other alluvial basins, these faults are likely to be barriers rather than conduits for groundwater flow. Also, given the diverse orientations of the alluvial faults, particularly in the vicinity of the testing area in northern Frenchman Flat, the overall effect of these faults will probably be to reduce groundwater fluxes through these areas and perhaps compartmentalize the alluvial aquifer, rather than to simply reorient flow by imparting a large-scale anisotropy to the alluvium. Given the ambiguity, the uncertainty analysis sections of this report document investigations that considered potential variations in fault permeability values both in the horizontal as well as vertical directions.

The Frenchman Flat flow model domain includes more than 70 faults, most of which cross-cut volcanic rocks, carbonate rocks, and siliciclastic rocks. Descriptions of fault characteristics from outcrop studies or measurements from hydraulic tests were not available for faults in Frenchman Flat. Observations of fault properties in the vicinity of the NTS and studies reported in the literature of faults in analogous rock types are used to get a sense of the possible range of fault behaviors in Frenchman Flat.

3-47

3.6.4.2 Faults in Consolidated Rocks

Recently published studies of fault-zone architecture in consolidated rocks have made distinctions between deformation behavior in low-porosity sedimentary and crystalline rocks, and in more porous sedimentary and volcanic rocks (Forster and Evans, 1991; Caine et al., 1996; Antonellini and Aydin, 1994; Wilson et al., 2003). Faults in low-porosity rocks generally have two primary architectural elements that can be developed to varying degrees depending on protolith material, location within the fault, and extent of displacement and cementation. The first element, the core zone, accommodates most of the displacement and is characterized by low-permeability gouge or cataclasite. The second element, the damage zone, contains minor faults, fractures, and folds that enhance its permeability relative to the undamaged protolith. Together, the two fault elements tend to inhibit cross-fault flow and enhance fault-parallel flow, imparting an overall hydraulic anisotropy to the fault. In contrast, porous sedimentary and volcanic rocks tend to accommodate small amounts of strain by cataclasis and shear-induced compaction along deformation bands rather than by fracturing (Antonellini and Aydin, 1994 and 1995; Wilson et al., 2003). In sandstones, these deformation bands contain finely ground particles that have substantially lower permeability (one to four orders of magnitude) and higher capillary pressures than adjacent undeformed rock, factors that allow deformation band faults to trap oil and sometimes compartmentalize oil reservoirs (Antonellini et al., 1999). Deformation bands in nonwelded tuffs are also expected to have low absolute permeabilities compared to adjacent undeformed tuff based on the fine-grained texture of the material within the band (Wilson et al., 2003).

Despite the tendency of non-welded tuffs to accommodate small amounts of strain through the development of deformation bands, other field data suggest that fault zones in non-welded tuffs, like faults in welded tuffs, are zones of enhanced fault-parallel permeability when displacements are large. Indirect evidence for this comes from (1) the association of fast groundwater flow paths in the unsaturated zone at Yucca Mountain, identified from the distribution of bomb-pulse chlorine-36 (^{36}Cl) in an underground tunnel, with major fault breaks in an overlying non-welded tuff (Levy et al., 1999; Wolfsberg et al., 2000); (2) enhanced propagation of atmospheric barometric pressure changes through non-welded rocks in the unsaturated zone where these are cross-cut by faults (Rousseau et al., 1999); (3) the rapid drainage of perched water from small faults in nonwelded tuff confining units when these were first intersected by tunnels at Rainier Mesa (Thordarson, 1965); and (4) hydraulic

test data from the NTS that indicate a four-order-of-magnitude variation in the hydraulic conductivity values of nonwelded tuff confining units that are best explained by the presence of open fractures and faults in at least some of the tested intervals (Geldon, 2004; SNJV, 2004d, Figure 5-12). Although these data do not rule out the possibility that cross-fault permeability in nonwelded tuffs is low, they are incompatible with the idea that permeable fracture paths do not develop parallel to faults in nonwelded tuffs, at least at shallow depths.

An important factor potentially affecting the migration of radionuclides to the LCA in Frenchman Flat is the hydraulic properties of faults at depth in the volcanic confining units that separate the alluvium and tuff aquifers from the LCA. Based on drilling experience at Pahute Mesa, Blankennagel and Weir (1973) suggested that fractures and faults in relatively weak nonwelded tuffs close more readily with increasing overburden pressure than fractures or faults in more competent welded tuffs and lavas. A series of permeability tests conducted on naturally fractured cores of welded and nonwelded tuffs from Yucca Mountain provide partial confirmation of Blankennagel and Weir's (1973) hypothesis. These tests showed that fracture conductivity decreases by between 80 and 90 percent in nonwelded tuffs when effective confining stresses were increased from 10 to 120 bars, whereas fracture conductivity decreased by only about 50 to 60 percent over the same pressure range in welded tuffs (Peters et al., 1984). Although the total number of fractures tested was small (five) and other factors such as the alignment of fracture surfaces probably influenced the results of these tests, the data suggest that fractures in nonwelded tuffs at depth close more rapidly and completely than those in welded tuffs. (Note that an effective confining stress of 120 bars would be obtained at a depth of 700 to 800 m beneath Frenchman Flat, assuming overburden consisted of alluvium with a bulk density of 1,650 kilograms per cubic meter [kg/m^3]).

Another indirect indicator of the permeability of faults in the volcanic confining units separating the LCA from shallower tuff and alluvium is provided by groundwater geochemistry data. Groundwater from the LCA generally has much higher concentrations of most major constituents (except silicon dioxide [SiO_2]) than groundwater from the volcanic tuffs and tuff-derived alluvium. These characteristics make it easy to identify small components of LCA groundwater where upward leakage from the LCA has occurred, but somewhat more difficult to identify the presence of small amounts of dilute groundwater from volcanic or alluvial aquifers in the LCA. In central Yucca Mountain, where hydraulic heads in the LCA are approximately 25 m higher than in the overlying tuffs, no significant

amounts of LCA groundwater are present in the shallow volcanic aquifers, despite the presence of many major faults through the thick confining units (BSC, 2004). This observation appears to support the idea that faults in deep confining units at Yucca Mountain have been sealed through a combination of overburden pressure and mineralization. In northern Frenchman Flat at the ER-5-3 well complex, where hydraulic heads in the shallow volcanic and alluvial aquifers are about 7 m higher than in the underlying LCA, some geochemical data allow for the presence of a component of AA water in the LCA (Hershey et al., 2005). However, this interpretation could not be confirmed with other geochemical evidence, and alternative interpretations of the groundwater composition at Well ER-5-3 involving only upgradient LCA sources were identified that were considered more probable (Hershey et al., 2005; SNJV, 2006).

It has long been accepted that faults and fractures in the regional carbonate aquifer (LCA) are responsible for the generally high productivity of this aquifer (Winograd and Thordarson, 1975). Near Frenchman Flat, the existence of a so-called “mega channel” in the LCA was suggested along the Spotted Range-Mine Mountain shear zone between Frenchman Flat and Ash Meadows based on the presence of a potentiometric trough in this area and relatively young ^{14}C ages for the groundwater discharging from springs in Ash Meadows at the downgradient end of the trough (Winograd and Pearson, 1976). The variability in the discharge of springs at Ash Meadows is also consistent with the channelization of groundwater along specific structural features, rather than diffuse, porous media-like flow in the LCA (Winograd and Thordarson, 1975, Figure 35). Likewise, a groundwater trough coinciding with the Yucca Flat fault suggests that groundwater in Yucca Flat drains preferentially through this fault toward Frenchman Flat (Winograd and Thordarson, 1975; Lacznik et al., 1996). More recently, hydraulic test data from an MWAT in the LCA in Yucca Flat have demonstrated a rapid hydraulic response at a monitoring well connected by a fault to the pumping well approximately 10 km away (SNJV, 2005b). These examples of highly channelized groundwater flow directly to the north and southwest of Frenchman Flat strongly suggest the possibility that channelization of groundwater flow along faults in the LCA may be also taking place in Frenchman Flat, where hydraulic head data are too sparse to allow the conclusive identification of similar behavior. Southeast of Frenchman Flat in Indian Springs Valley, a fault in the LCA perpendicular to the regional hydraulic head gradient forms a hydraulic barrier with an associated drop in head of several hundred feet between the northern Spring Mountains and the central part of the valley (Winograd and Thordarson, 1975, Figure 33). Collectively, these observations are consistent with the

model of fault behavior in low-porosity rocks described by Caine et al. (1996) in which fault-parallel flow is enhanced by the presence of fractures and minor faults in the damage zone, whereas the development of gouge and cataclasite in the fault core limit cross-fault flow.

3.7 Conceptual Flow Model Summary

A number of studies investigated the Frenchman Flat groundwater flow system. Overall, three conceptual models have been proposed. These conceptual models are not mutually exclusive. The first conceptual model was proposed by Winograd and Thordarson (1975) and updated by Lacznik et al. (1996). This conceptual model was based on an assumption that water in the AA is semipерched and is characterized by a vertical flow system from the AA to the LCA through an internal outlet in the vicinity of the Frenchman Lake Playa or through another local sink. In addition, this conceptual model allowed for the possibility that water moves from the AA to the LCA through slow lateral flow to the basin edge. The second conceptual model suggests flow in the AA is consistent with LCA flow direction going from north to south. This conceptualization is based on regional flow model results, which indicated this flow direction (DOE/NV, 1997), rather than by site-specific data. The third conceptual model suggested that water in CP basin to the west/northwest of Frenchman Flat leaks through the Cane Spring fault into the Frenchman Flat basin (IT, 1999a) and the general flow in the Frenchman Flat basin is from north to south/southeast. This conceptual model is supported by three observations: 1) observed water levels in CP basin are much higher than those in the Frenchman Flat basin, 2) observed water levels in the AA are lower to the south and east of the Frenchman Lake Playa, and 3) water levels observed in Well UE-5c WW in the northwest alluvium are greater than those observed in the central or east basin. This conceptual model was chosen as the basis for the Frenchman Flat CAU Phase I flow model (IT, 1999a). The Phase II Frenchman Flat flow model does not make any preconceptions regarding which of these three conceptual models is correct, but is designed in a way that allows aspects of all of these conceptual models to be investigated and flow directions to be determined as a result of model calibration.

Groundwater flow through the Frenchman Flat basin is driven by recharge within the basin and groundwater flow from areas of higher head to the west of the basin. Hydraulic head data do not indicate large lateral or vertical gradients and suggest that groundwater flow is slow within the basin, a conclusion that is consistent with low rates of recharge and limited inflow to the basin across the

Cane Spring fault inferred from the large water-level differences between the Frenchman Flat and CP basins. Rates of present-day recharge in the model area are 1 percent or less of the total fluxes estimated to pass through the model area, mostly through the LCA.

The rate and direction of groundwater flow within the Frenchman Flat basin depend on the magnitude, spatial variability, and directional dependence of permeability within the basin, as well as on the vertical and lateral hydraulic gradients in the basin. The anisotropy and the variation of permeability with depth in the alluvium, in particular, will play an important role in determining whether shallow groundwater flow near the nuclear test locations moves predominantly horizontally or has a strong vertical component. Anisotropy ratios (k_h/k_v) of 7.7 estimated from MWAT at the ER-5-3 well cluster in the OAA and ratios of 1.1 to 360 estimated from the RNM-2s MWAT in the central testing area suggest that anisotropy in the alluvium will promote lateral groundwater flow in preference to vertical flow. Lateral flow in the alluvium will also be promoted by the decrease in permeability with depth in the AA that occurs as a result of sediment compaction. Evidence for the decrease in permeability with depth in Frenchman Flat is provided by analysis of flow log data from ER-5-4 and by an analysis of regional data from the AA in the NTS investigation area. Permeability data from Frenchman Flat itself show considerable scatter and do not clearly indicate a decrease in the permeability of the AA with depth, but at least some of the scatter is attributable to uncertainty associated with the interpretations and not to heterogeneity. Although depth decay in permeability introduces anisotropy to the flow system over many hundreds of meters, anisotropy introduced by depth decay is minor over scales of tens to a hundred meters, and local anisotropy associated with layering should be considered separately in the model calibration.

The absence of significant vertical hydraulic gradients in the AA, combined with effects of depth decay in permeability and the possibility of k_h/k_v ratios much greater than unity indicate that groundwater flow in the AA will be predominantly lateral to the basin margins. Furthermore, the low recharge rates estimated for the basin, and the limited inflow across the Cane Spring fault, indicate that lateral groundwater movement within the basin will be slow.

These and other aspects of the Phase II conceptual groundwater flow model in the Frenchman Flat CAU are summarized below:

- Regionally, groundwater flow occurring in the LCA is conducted into the northern edge of the Frenchman Flat CAU model from southern Yucca Flat and areas east, eventually discharging at Ash Meadows and possibly Alkali Flat and Death Valley. This regional conceptual model remains unchanged from Phase I as that of Winograd and Thordarson (1975), modified by Lacznia et al. (1996).
- Recharge from sources within the basin provides only minor amounts of water to the flow system. Even when three different models of recharge (modified Maxey-Eakin, USGS distributed parameter watershed, and DRI chloride mass balance) are considered in conjunction with Frenchman Flat precipitation, the recharge contribution to the Frenchman Flat water balance is on the order of 1 percent or less (SNJV, 2004d). This element of the conceptual model remains unchanged from Phase I, and low local recharge is ubiquitous in Phase II.
- Flow through the LCA is largely controlled by faults and fractures, with the Rock Valley fault system as a major regional system. Whether or not the Rock Valley fault system is ubiquitously and intensely fractured enough to form mega channels as suggested as Winograd and Pearson (1976) remains unknown.
- Volcaniclastic, bedded, and welded tuff units with locally interbedded lava flows and breccia overlie the LCA over most of Frenchman Flat. These units are thickest on the northwest and west margins of the basin near their volcanic source areas, and thin progressively towards the east and south margins of the basin. The conceptual model, that a thick section of Paleozoic carbonate rocks overlain by volcanic and alluvial units in the basin, is unchanged from the Phase I conceptual models and remains as a core component of all alternative HFMs. Confining units were encountered in the central testing area in ER-5-4#2 and in the northern testing area in ER-5-3#2. The alluvial and volcanic sections were thicker than expected.
- Hydraulic heads are higher in the AA than the LCA, reflecting a separation of the local flow system in the AA from the regional system in the LCA. This interpretation remains unchanged from Phase I.
- Hydraulic heads are very similar in the AA in Frenchman Flat, both horizontally and vertically. Thus, there is very little driving force for groundwater flow in any direction.
- The heads in the LTCU, which is one of the volcanic units that separates the AA and LCA flow systems, appear to be higher than either the AA or LCA. This presents an additional barrier to regional-scale contaminant migration from the underground nuclear tests.
- Faults through the alluvium are likely to be barriers rather than conduits for flow.
- Faults in consolidated rocks may display considerable anisotropy and vary in their properties depending on porosity and mechanical properties.

4.0 GROUNDWATER FLOW MODEL CONSTRUCTION

This section describes the methods used to construct the numerical groundwater flow model for Frenchman Flat. The objective is to transform the conceptual models described in [Section 3.0](#) into mathematical models that can simulate the groundwater flow system in the area surrounding the Frenchman Flat CAU. The construction process includes spatial discretization, definition of boundary conditions, and initial assignment of model parameters. The process follows that described in the American Society for Testing and Materials (ASTM) Standard Guides D 5447-93 (ASTM, 1993a) and D 5610-94 (ASTM, 1994b).

4.1 General Approach

The modeling approach followed in this document enhances and extends the Frenchman Flat CAU flow model approach presented in the Frenchman Flat CAIP addendum (NNSA/NV, 2001). Specific steps followed to develop the CAU groundwater flow model are also detailed in the Frenchman Flat hydrologic data document (SNJV, 2004d), described by ASTM (1993a), and are summarized below:

- Identify simulation objectives.
- Define the CAU geologic model.
- Define parameter distributions for model inputs.
- Define CAU flow model boundaries.
- Select a computer code.
- Generate the CAU model grid.
- Calibrate the CAU flow model.
- Perform parameter sensitivity analyses.
- Prepare the model document.

The first three steps are detailed in SNJV (2004d) and BN (2005a), and computer code selection is detailed in the Frenchman Flat CAIP (DOE/NV, 1999). The HFMs are described in [Section 2.2](#) of this report. More detail is provided below on model boundaries, grid generation, and implementation of the multiple HFMs. [Section 5.0](#) of this document describes the model calibration, [Section 6.0](#) describes the model uncertainty analysis, and [Section 7.0](#) details the parameter sensitivity analysis.

4.2 Model Area

The model area was determined to define, at a minimum, the saturated flow regime in and underneath the AA where underground nuclear testing was conducted (Figure 1-5). As described in the Frenchman Flat hydrologic data document (SNJV, 2004d), the natural physical boundaries for the Frenchman Flat CAU area are too distant to be used for the lateral boundaries of the CAU flow and transport models. Therefore, model boundaries are selected to incorporate underground nuclear tests, important hydrologic features, and wells providing hydrologic and geologic information for Frenchman Flat.

Model boundaries are extended to include the most relevant features that could be controlling the flow directions and gradients in the AA and to take advantage of the detailed information available in the HFM models. The HFM model boundaries as defined in BN (2005a) were chosen such that they encompass perceived geologic and hydrologic domains and, to the extent possible, contain the contaminant source areas with some buffer within practical computational constraints.

To the west, the model boundary traverses the eastern part of CP basin, and encompasses Wells WW-4 and WW-4A. To the east, the model is extended slightly east from Well TW-3 to provide some edge control and to ensure that the model boundary heads are consistent with a measured water level. To the north, the model boundary extends into southern Yucca Flat and includes Wells WW-C and WW-C1. To the south, the model boundary extends well below the southern edge of the AA to include the Ranger Mountains and parts of the Spotted Range. The southern model area encompasses an area where the Rock Valley fault system appears to control the flow regime in the LCA (Winograd and Thordarson, 1975). Because of the great extent of the flow system, the boundaries of the CAU flow model do not coincide with natural hydrologic and geologic boundaries. Thus, the boundaries must be estimated using well data and other regional information.

The CAU numerical model lies within the geologic model domain and has lower-left plan coordinates of 584,500 and 4,061,000 m (UTM Zone 11, NAD 27 m) and upper-right plan coordinates of 603,500 and 4,091,000 m. The model is aligned north-south. The numerical model extends from the estimated water table to the estimated bottom of the LCA at an elevation of about -3,500 to -4,500 m below sea level. The hydrologic model area encompasses 570 km² of the southeastern portion of the NTS (Figure 1-1). The area has a north-south length of 30 km and an east-west length of 19 km.

4.3 Mesh Generation

To carry out numerical modeling of flow and transport, a computational grid must be constructed. The approach to grid generation is driven by numerous factors, such as the algorithm one is using to solve the flow and transport equations (e.g., finite difference, finite element, finite volume); the level of detail available regarding the geometry of the hydrostratigraphy; the need for accuracy in resolving gradients; and the goals of the modeling analysis. The Frenchman Flat flow model uses FEHM (Zyvoloski et al., 1997a) and a computational grid generation approach based on a balanced octree refinement of an orthogonal grid.

Octree refinement is based on recursive refinement of hexahedral blocks into eight octants by planes perpendicular to each coordinate axis. The splitting of blocks is continued, creating progressively smaller cells, until refinement criteria are met (Figure 4-1). The Voronoi polygons shown in Figure 4-1 are the FEHM control volumes associated with mesh nodes.

4.3.1 Mesh Refinement Criteria

A set of criteria, outlined below, was developed to produce a mesh that is suitable for flow and transport calculations for the Frenchman Flat CAU. The resultant mesh has sufficient resolution to represent features such as hydrostratigraphy, faults, contaminant source zones, wells, and the water table, yet not too large to make computations impractical. Further, the mesh should have enough resolution at the areas of change between the different HFMs such that the same mesh is used to reasonably simulate all alternative HFMs. In general, the criteria for grid generation are as follows (DOE/NV, 1999; SNJV, 2004a):

- The external boundary of the CAU model will correspond to appropriate cell boundaries within the regional groundwater flow model. However, the regional model is rotated with respect to the coordinate system and the CAU model is not; thus, the correspondence will not be exact.
- Nodes will be placed as close as practical to each underground test location as well as at specific well locations and along the wells' open intervals.
- Nodes will be placed along faults that are identified as being important to the distribution of HSUs and the flow regime.

Figure 4-1
Relationship Between Grid Refinement Levels, the Resulting Finite Element Mesh, and Computational Control Volumes

- The node density will be greatest in the vicinity of the underground tests and at other points of interest, such as discharge wells, and will decrease toward the CAU-model boundaries.
- Nodes will be preferentially placed along HSU contacts to more precisely incorporate the geologic model structure in the simulations. The nodes will not be layered in a finite-difference sense, but rather will form a pattern representative of the CAU-scale geology.
- The node spacing will vary from small in the vicinity of test cavities and wells to nearly as large as in the regional groundwater flow model grid at the CAU boundary.

In general, it is easy to define criteria that lead to increased refinement in certain volumes of the mesh. The more difficult process is to define design criteria that limit the refined volume so that the mesh size (number of nodes and elements) does not grow beyond practical limits. The process of developing these criteria is iterative. Control files for the Los Alamos Grid Toolbox (LaGriT) (George, 1997) mesh-generation package are written to implement the criteria, and then mesh-generation calculations are performed and checked to ensure the implementation is correct. The resulting mesh is analyzed to determine whether the goals have been met. Details of this process are presented in the following sections.

4.3.2 Mesh Requirements for FEHM Streamline Particle Tracking

The streamline particle tracking (SPTR) macro within the FEHM code, which is used during transport calculations, has the capability to move particles within the simulated flow field, but this capability is only implemented for grids that meet specific criteria. The SPTR capability will work for orthogonal finite-difference grids; orthogonal finite-difference grids refined using the balanced octree mesh refinement (OMR) algorithm if the aspect ratio of grid blocks is not greater than square root of two; and orthogonal finite-difference grids that are refined using the balanced OMR algorithm if all elements in a row or column of the grid are refined. A standard finite-difference grid would be too large (e.g., too many nodes) if it were made fine enough to resolve geometric details of the HFM. The geometric details of the HFM also do not lend themselves to a method that refines entire rows or columns. Therefore, the balanced OMR method that allows targeted local refinement was used.

A practical consideration is that the computational resources (e.g., processor time, computer memory) necessary to complete a FEHM calculation is proportional to the number of nodes in the computational grid. Based on experience from previous modeling efforts, a reasonable node count target was 1 to 1.5 million nodes.

The HFM for Frenchman Flat represents a preferred model interpretation of the hydrostratigraphy (BASE) and four alternative HFMs. To simplify the flow and transport modeling, the grid design incorporates the BASE and four alternatives into a single grid. This is done by applying the grid refinement criteria to all five models separately and then creating a single grid that is the superposition of the finest cells from all five alternative HFM grids. This approach is practical for these HFMs because the volume where the models differ is limited to a small fraction of the total grid volume.

Underground nuclear test cavities where source terms will be imposed require a fine resolution grid. To avoid dilution in an initial source concentration, it is important that elements with small volumes are used near underground test cavities. For the Frenchman Flat basin area, this does not add a substantial number of nodes to the overall grid because the total volume associated with 10 underground nuclear test cavities is small compared to the total volume of the grid.

Wells in the model volume provide data on water levels and may be sources or sinks of water. The measured water levels are used as calibration targets. Therefore, it is also important to have high resolution near the open intervals of wells.

It is important to maintain continuity of material interfaces especially where there are strong contrasts in properties (e.g., permeability) across material interfaces. A thin unit (such as the BLFA) may act as a flow pathway if it has high permeability, so the grid must be refined enough to ensure lateral continuity of the unit. The same can be said for low permeability units. They may act as barriers to flow, so the grid must be refined enough to maintain lateral and vertical continuity of these units. An idealized example is shown in [Figure 4-2](#). In this figure, a thinning and thickening strip of material is shown repeated along with four progressively coarser (by a factor of two) discretization levels and the associated quadrilaterals and nodes. The areas above and below the strip are shown with dark and light shading, respectively. The material in the strip is shown as intermediate shading to qualitatively illustrate the effect of mesh refinement. In the leftmost panel, the very finest discretization level maintains continuity at all material thicknesses with the representation becoming progressively worse to the rightmost, coarsest discretization panel.

The model region is intersected by many faults. The faults offset HSUs, which can impact flow and transport. In addition, faults may act as barriers or conduits to flow and transport. It is important that

the grid be constructed so that material properties associated with faults are continuous. It is less important that the grid actually resolve the length scales associated with the zones of alteration perpendicular to the fault surfaces.

Figure 4-2
Effect of Grid Refinement on Material Continuity

The grid can be adapted to physical features but cannot exactly conform to features without an impractically large number of nodes for an area the size of the Frenchman Flat CAU model. There are a number of reasons for this. One is that the code being used, FEHM, uses Voronoi control volumes (Okabe and Boots, 1992) around each node as the computational volume to which material properties are assigned (Figure 4-1). It is possible to create Voronoi polygons that conform to simple geometries; however, for the general case, no algorithm exists that creates a conforming Voronoi tessellation of a general 3-D planar straight-line graph. The other reason is related to a requirement of the FEHM SPTR algorithm, which is implemented on orthogonal octree-refined grids. Further, the relationship between the octree grid, the associated Delaunay tetrahedral mesh, and the node-based control volumes is not one to one. As can be seen in Figure 4-1, the Voronoi volumes (areas, in this two-dimensional [2-D] example) are offset from the quadrilateral cells. Also, material properties are assigned to nodes and control volumes in FEHM, not the quadrilateral or triangular elements. However, use of local mesh refinement allows creation of high-density node distributions near features requiring detailed resolution and assignment of node properties based on the spatial

relationship between the features (HSUs, faults, well intervals, test cavities) and the grid nodes. The result is a grid that adapts to the features and places additional resolution near features of interest, allowing improvement in representing the complex geometric features within the CAU model. This is illustrated in [Figure 4-2](#), in which different levels of refinement allows one to represent the geometry at greater and greater resolution, but in the end it is only the node distribution, and the properties assigned to the nodes, that are input into the computational flow and transport model.

4.3.3 Input for Grid Generation

The inputs for grid generation are a collection of points (zero-dimensional [0-D]), lines (one-dimensional [1-D]), surfaces (2-D), and volume definitions (3-D). These are used in various ways to constrain the octree grid refinement and material property definitions.

The BASE HFM and four alternatives are constructed using the EarthVision® software tools (Dynamic Graphics, 2002). Various components of the HFM are exported as text files. These components define:

- Twenty-two surfaces, which represent the top of each HSU
- Seventy-three surfaces, which represent faults
- Seventy-two non-planar, 3-D polygons defining the boundary of each fault
- A surface that represents topography
- A surface that represents the water table

The first two items are repeated for each HFM for a total of five sets of surfaces. All surfaces are represented by a structured array of elevations, $z(i,j)$, where z is the elevation in meters, i is an index for the x coordinate (west-east direction) and j is an index for the y coordinate (south-north direction). Each surface, generated by EarthVision® for input into LaGriT, is approximated by 761 points in the x direction and 1,201 points in the y direction, for a total of 913,961 points. The horizontal separation between points, dx , dy , is uniform with $dx=dy=25$ m. The surface defined by the $z(i,j)$ array is composed of 912,000 quadrilateral cells making a surface that extends 19 km in the x direction (west-east) and 30 km in the y direction (south-north) ([Table 4-1](#)).

To build the grid, two additional HSU surface files had to be created. The first was a surface representing the bottom of the model because the existing surfaces represented the top surface of each HSU in the model but did not account for the model base. A surface with a constant elevation

Table 4-1
Quadrilateral Grids Define Surfaces $z(i,j)$

Number of Nodes	NX	761
	NY	1,201
	Total	913,961
Number of Cells	NX	760
	NY	1,200
	Total	912,000
Extents	XMIN	584,500 m
	XMAX	603,500 m
	YMIN	4,061,000 m
	YMAX	4,091,000 m
Increment	dx	25 m
	dy	25 m

of -5,500 m was used to define a volume between the top of the LCCU and bottom of the model. The second surface was created at the top of the model. The top surface provided by EarthVision® represents the top of PCU2T; however, there is volume between this surface and the water table. That volume is associated with the alluvial unit, AA3.

The information in the EarthVision® surface files, $z(i,j)$, requires some preprocessing before it can be input into the LaGriT grid generation software. The EarthVision® files contain NULL values if the HSU has zero thickness. Some HSUs only exist over a small part of the model domain, which leads to the majority of the entries being NULL. However, LaGriT expects surfaces to be defined with a z coordinate at every array entry, $z(i,j)$. The HSU surfaces are processed by reading in all surfaces into a data structure, $z(i,j,k)$, where k is the surface number. If a model has N HSUs, there will be $N+1$ surfaces. Then each (i,j) index is inspected starting at the bottom surface, $k=1$, up to the top surface, $k=22$. If an entry, $z(i,j,k)$, has a NULL value, it is assigned the z coordinate of the next lower entry, $z(i,j,k-1)$. Because the bottom of the model $z(i,j,0) = -5,500$ m and does not contain any NULL values, this approach ensures that every entry in the array has a valid z coordinate. If an HSU does not exist at a particular (i,j) location, it is represented by a top and bottom surface with the same z coordinate, signifying an HSU with zero thickness.

Adjacent pairs of surfaces are used to compute isopachs, or lines of equal stratigraphic thickness, in each HSU. This is required because HSU thickness is used as a criterion for deciding how many levels of recursive refinements the grid blocks of a particular volume receive.

Faults are represented by 73 surfaces, $z(i,j)$, with a data structure identical to that used for the HSU surfaces. The faults can be close to vertical; however, because they are represented on a grid with uniform horizontal increments, $dx=dy=25$ m, the surface cannot be exactly vertical. For example, with a constant horizontal spacing of 25 m, a vertical offset between neighboring nodes of 1,000 m produces a dip angle of about 88.6 degrees; a vertical offset between neighboring nodes of 2,000 m produces a dip angle of about 89.3 degrees; and a vertical offset of 3,000 m produces a dip angle of about 89.5 degrees. To determine which part of the surface represents a fault and which part does not, additional information is required to determine where the $z(i,j)$ surface representation terminates. As with the HSU surfaces, a NULL value is assigned to array entries where the fault does not exist. A simple example (Figure 4-3a and Figure 4-3b) illustrates this stair-stepping effect. In this example the surface $z(i,j)=x*y$ dip is less than 45 degrees (Figure 4-3a). If all quadrilateral elements with any z coordinates above $z=4.5$ are removed, the surface has a jagged boundary that varies between $z=3.5$ and $z=4.5$ (Figure 4-3b). The figure shows the same effect when the NULL cells are removed from the fault surface (Figure 4-3c and Figure 4-3d). Viewed from above, the boundary is a jagged stairstep at the 25-m resolution of the surface (Figure 4-3c). In perspective, it is apparent that the top of the fault is jagged with over 100-m excursions (Figure 4-3d). The color represents the elevation $z(i,j)$, and the stair-stepped truncation results in a jagged termination of the fault.

Fault representation is further refined by using additional information from EarthVision®: the tiploop data file contains a set of non-planar polygons that define the outline, in three dimensions, of the perimeter of each fault. A new representation of each fault is developed by the following steps. The non-planar polygon is projected onto the xy plane (all z coordinates are set to zero). The polygon is triangulated using an algorithm that clips convex corners from the polygon. The result is a triangulation that exactly conforms to the planar polygon without any interior points. A recursive refine and smooth algorithm is then used to create a triangulation with interior points and isotropic triangles with edge lengths of approximately 75 m. The triangulations are then projected vertically onto the original $z(i,j)$ fault surfaces, and a z coordinate is assigned to each node of the triangulation

based on the intersection of the node from the triangulation with the $z(i,j)$ surface. The resulting triangulations are shown in Figure 4-4.

Figure 4-3
Examples of What Occurs When a Regular Grid, (1,j), Is Truncated and Cells Above a Particular Elevation Are Removed

An example of what occurs when a regular grid $z(i,j)$, is truncated and cells above a particular elevation are removed.

- a) A simple surface grid $z(i,j)$ viewed from above and colored by z coordinate.
- b) The same grid viewed from the side after cells above $z=0.5$ are removed. The truncated edge does not have a constant elevation.
- c) One of the fault surface grids truncated at the elevation of the top and bottom of the model.
- d) The same grid viewed from the side and magnified showing the jagged edge along the truncated edge of the grid.

A representation of the topographic surface, or digital elevation model (DEM), is required for model-specific reasons. For example, when permeability is modeled as decreasing with overburden pressure, each node depth from ground surface is required. An EarthVision® $z(i,j)$ surface file with the same characteristics (e.g., grid spacing, number of nodes, extents) as the elevation is required. A $z(i,j)$ surface file similar to the one used for water-table elevation is used to represent ground surface elevation. The topographic map was generated using three data sources: (1) the majority of the area, all within NTS boundaries, was represented by the NTS project 1999 10 m DEM in UTM Zone 11

NAD 27 m, (2) topography in the northeast corner of the model was based on the USGS 7.5-minute quadrangle topographic maps that the project has on file as contours in digitized form, and (3) topographic data for the eastern strip were taken from the USGS 30 m DEM data available for download (USGS, 2005).

Figure 4-4
Expanded Views of 73 Fault Surfaces Converted to a Triangulation

4.3.3.1 Water-Table Definition

The FEHM simulations utilize a confined aquifer approximation in which the water table defines the top of the model domain. An estimate of the water table is developed using observed heads in wells relatively shallow in the flow system and regional model results. This process is explained below. The confined aquifer approach does not include an unsaturated zone or moving water table and, therefore, solves a simplified and computationally more efficient numerical model.

The water table for the Frenchman Flat CAU model is generated from several sources and is a complex derivative involving base data, additional data, and adjustment data. The base data are from the UGTA regional model output for run G0R2 (a model run using the base geologic model and the largest amount of recharge across all considered recharge datasets [SNJV, 2004d]), and have been modified with contemporary water-level measurements. Although the simulated water levels at the water table do not need to correspond to the top of the mesh in a fully confined model, this process of using a simulated water table modified to honor field measurements was completed to provide the best possible estimate of the top of the model domain.

The CP basin area was given the water-table elevations derived from the regional model target head dataset (DOE/NV, 1997). Control points are also added along the Cane Spring fault on its east side to bring the water-table elevation near the fault to a value that is close to the average water-table elevation within the Frenchman Flat basin (about 735 m).

The base and additional data were then gridded with an EarthVision® function called adjustment gridding. This function adjusts (warps) the entire grid to honor the contemporary data at the provided measurement locations.

An EarthVision® $z(i,j)$ surface file with the same characteristics as the HSUs and faults represents water-table elevation (Figure 4-5). The water table as defined by the composite of regional model results and available water-level measurements as described above is shown in Figure 4-5a. A stair-stepped representation, with steps at 880, 830, 780, and 730 m, was used to define the top of the model (Figure 4-5b). Figure 4-5c shows a view of the resulting mesh top.

4.3.3.2 Breakthrough Planes, Test Cavities, and Well Intervals

A small part of the model domain near the CAMBRIC test and Wells RNM-1 and RNM-2s has been studied in detail (Tompson et al., 2005). In that study, a number of breakthrough (BT) planes were defined to analyze radionuclide breakthrough results for transport from the CAMBRIC test. To maintain some consistency between Frenchman Flat CAU flow and transport models and the CAMBRIC models, the same planes are defined using high-resolution elements in the volumes surrounding these planes. The data used to define the planes have map coordinates (x,y) with no depth information provided. The coordinates of the planes are listed in Table 4-2.

Figure 4-5
Representation of the Water Table Used
To Truncate the Top of the Model

Table 4-2
Breakthrough Planes Coordinates

Name	Type	x Coordinate (UTM m)	y Coordinate (UTM m)
BT_P1	Line	592,015.04	4,075,718.58
		593,667.82	4,074,281.77
BT_P2	Line	592,060.31	4,075,770.65
		593,713.09	4,074,333.85
BT_P3	Line	592,175.78	4,075,903.48
		593,828.56	4,074,466.67
BT_P4	Polygon	591,988.79	4,075,688.39
		593,641.57	4,074,251.58
		593,602.21	4,074,206.30
		591,949.43	4,075,643.11

There are 10 underground nuclear test cavities within the volume of the flow and transport model. These are defined by point data. The location of each test cavity is defined by an easting (x), northing (y), and working point elevation (z) coordinate. These are tabulated in [Table 1-1](#).

Thirty-seven zones are used to represent screened intervals of wells within the model area. Each of these is represented by a line defined by an easting (x), northing (y), and two elevation (z) coordinates. The z coordinates define the lower and upper extents of the screened interval. These data are obtained from the Frenchman Flat hydrologic data document (SNJV, 2004d).

4.3.4 Selective Grid Refinement

The grid generation strategy is to selectively change the grid resolution to accommodate features in the model because building a grid with high resolution throughout is impractical. In the planning stage of the process, features that need to be resolved by the grid are identified, but it is difficult to predict the node count of the refined grid accurately. Therefore, the approach is to increase the model resolution and check the size of the resulting mesh until the mesh size grows beyond a target value. The goal for the resulting mesh was about 1 million nodes. This number is based on the analyst's experience with similar flow and transport models and available computer hardware.

The OMR is based on recursive refinement of hexahedral blocks in eight octants by planes perpendicular to each coordinate axis, and the splitting of blocks is continued until refinement criteria are met ([Figure 4-1](#)). The starting point for this procedure is a uniform, orthogonal finite-difference grid referred to as the level 0 grid. A single refinement of a cell creates eight level 1 cells, refinement of a level 1 cell produces eight level 2 cells, and so on. For the Frenchman Flat CAU model, the maximum refinement is level 4. The dimensions of the various grid levels is listed in [Table 4-3](#), and the parameters defining the level 0 grid are given in [Table 4-4](#).

Table 4-3
Size of Octree Grid Cells

	Volume (m ³)	dx (m)	dy (m)	dz (m)
Level 0	1.0×10^8	500	500	400
Level 1	1.25×10^7	250	250	200
Level 2	1.5625×10^6	125	125	100
Level 3	1.953125×10^5	62.5	62.5	50
Level 4	2.44140625×10^4	31.25	31.25	25

Table 4-4
Parameters Defining the Level 0 Grid

Number of Nodes	NX	39
	NY	61
	NZ	16
	Total	38,064
Number of Cells	NX	38
	NY	60
	NZ	15
	Total	34,200
Extents	XMIN	--
	XMAX	--
	YMIN	--
	YMAX	1,130
	ZMIN	-4,870
	ZMAX	--
Increment	dx	500
	dy	500
	dz	400

The exterior of the final computational mesh was not a parallelepiped. After the octree grid was built, some cells were removed from the bottom and top. The shape of the bottom was determined by removing cells belonging to the LCCU. The top surface was created by removing cells above the water table. Because the octree grid has discrete vertical steps at the top and the water table is relatively flat over much of the model area near an elevation of 730 m, the level 0 grid is designed to have a layer of nodes at 730 m, making it easy to truncate the top surface and have the majority of the grid top at exactly 730 m.

An additional grid construction constraint is that a balanced octree be created. In each pass of grid refinement, a set of elements are refined. After this is done, the entire grid is examined and additional cells are refined to ensure that neighboring cells differ by at most one refinement level. That is, a level 3 cell may have neighbors of level 2, 3, 4, but if a neighbor is level 1, it is refined to level 2. This step causes refinement to propagate outward from a feature (e.g., underground test cavity). However, it has the desirable property of ensuring that the grid cell size only changes by a factor of two going from one cell to another, which results in better conditioning of the coefficient matrix that is eventually solved. It is also necessary for implementation of the SPTR algorithm in FEHM.

A property of a balanced octree is that the superposition of two or more balanced octree grids is itself a balanced octree. This can be used to advantage in the grid-building process. A level 0 grid can be refined based on a set of criteria for one feature, such as faults. Independently, another level 0 grid can be refined based on criteria for a different feature, such as well screen intervals, and then these two grids can be superimposed.

The general strategy for building the grid is to use all the inputs outlined above as indicators to determine where to refine the grid. The process is iterative in that a set of logical steps are built into the LaGriT control files. One will have a good idea of what the result will be, but the exact details, such as number of nodes, can only be roughly predicted. Automated procedures are developed so that as the grid refinement process is carried out, each iterative result is analyzed, decisions are made regarding volumes that require more or less refinement, adjustments are made to LaGriT control files, and the process is repeated. The details of the refinement criteria used in the final iteration are documented in this report.

4.3.5 Feature of Interest Refinement Criteria

Rules for mesh refinement were developed for the breakthrough planes, test cavities, wells, faults, and HSUs. Each is described in this section.

The data used to describe a breakthrough plane do not have an associated vertical coordinate. To convert these data into an object that can be intersected with the grid, each line or polygon is assigned an elevation of 5,000 m and then projected downward 15,000 m to $z = -10,000$ m. The lines associated with BT_P1, BT_P2, and BT_P3 then become vertical quadrilaterals. When the four points defining BT_P4 are projected, it becomes a hexahedron.

The criteria for refining the breakthrough planes are:

- Refine to level 2 if an element is intersected by BT_P1, BT_P2, BT_P3, or BT_P4.
- Refine to level 3 if an element is intersected by BT_P1, BT_P2, BT_P3, or BT_P4 and the element centroid is above the top of PCU1U.
- Refine to level 4 if an element is intersected by BT_P1, BT_P2, BT_P3, or BT_P4; the element centroid is above the top of PCU1U; and the element centroid is above 450 m elevation.

The criteria for refining underground tests and screen intervals for wells are:

- Refine to level 4 if an element is intersected by any underground test working point.
- Refine to level 4 if an element is intersected by an open well interval or screen interval.
- Refine to level 4 if an element is within 50 m of a test or screen interval.

The refinement criteria based on HSU thickness are applied to all five (BASE and four alternative) of the HFMs.

- Refine to level 3 if an element is intersected by LTCU1, WCU, TM-LVTA or TM-WTA, where these units have thickness between 58 and 120 m.
- Refine to level 4 if an element is intersected by any HSU with a thickness between 0 and 60 m.

The criteria for refining faults are:

- Refine to level 1 if an element is intersected by a fault surface and the element is above the top of LCCU.
- Refine to level 2 if an element is intersected by a fault surface, and the element is above the top of LCA and below the top of TM-WTA.
- Refine to level 3 if an element is intersected by a fault surface; the element is above the top of LCA and below the top of TM-WTA; the element is in the southern 25 km of the model area; and the element is not in the rectangle defined by XMIN=584,500, XMAX=587,050, YMAX=4,070,285, YMAX=4,079,679.

The criteria for refining the water table are as follows. The starting point for all refinement is the level 0 grid. It is designed so that a layer of level 0 nodes is at an elevation of 730 m. This will ensure that the top surface can be truncated and the low gradient part of the water table will be represented by a flat surface at $z = 730$ m. To ensure that discrete steps in the grid surface elevation can be taken, all elements that intersect the water table where $730 \text{ m} < \text{water-table elevation} < 780 \text{ m}$ are refined to level 3, allowing the model to have a constant top elevation of 780 m where the water table is between 730 m and 780 m. Elements that intersect the water table where $780 \text{ m} < \text{water-table elevation} < 830 \text{ m}$ are refined to level 2. Elements that intersect the water table where $830 \text{ m} < \text{water-table elevation} < 880 \text{ m}$ are refined to level 3. This allows the grid to be truncated and result in a top surface elevation as shown in [Figure 4-5](#).

The top surface of the mesh is designed to approximately represent the elevation of the water table.

The criteria used to decide which OMR hexahedral elements are kept are as follows:

- If an element centroid is above the discrete water-table surface ([Figure 4-5](#)), it is removed. A similar procedure is used to remove elements from the lower part of the model.
- If an element centroid is below the top of the LCCU, it is removed.

These procedures leave some nodes in the grid that are above the water table or below the LCCU HSU. The amount these nodes can extend above or below the surface used to control the truncation is one-half the vertical dimension of the associated OMR level cell size ([Table 4-3](#)).

The resulting point distribution is connected to form a Delaunay tetrahedral mesh (Okabe and Boots, 1992). However, this mesh forms the convex hull of the point distribution developed using the OMR method. In order to remove unwanted elements and form a non-convex tetrahedral grid that conforms exactly to the exterior of the OMR grid, the grid-to-grid interpolation algorithm is applied to detect tetrahedral elements that are outside the OMR hexahedral grid. Any tetrahedral element that is outside is removed, resulting in a grid with 1,250,721 nodes and 7,144,765 tetrahedral elements. This constitutes the Frenchman Flat Flow and Transport Model Grid (FFG) ([Figures 4-6 and 4-7](#)).

4.3.6 Grid Output

Finite Element Node Coordinates and Tetrahedral Connectivity

The FFG is defined in a single file (in a format specified by and compatible with FEHM) that contains the x,y,z coordinate of each node and its tetrahedral connectivity. The file contains the coordinates of 1,250,721 nodes and the connectivity for 7,144,765 elements.

Hydrostratigraphic Unit Identification for All Hydrostratigraphic Framework Models

Each node is associated with a particular HSU and is thus assigned a number between 1 and 22, depending upon the HSU. This is done for the BASE model and each of the four alternative models. The HSU identification information for each of the five models is contained in a single file in a format specified by and compatible with FEHM. The file associates each node with a particular HSU. [Figure 4-8](#) shows an example of how materials are changed in nodes for alternate HFMs.

Figure 4-6
Map View of the Model Area at an Elevation of 725 m Showing Multiple Levels of Refinement

Figure 4-7
Tetrahedral Grid at 3X Vertical Exaggeration Showing Only Faults

Fault Identification

To ensure continuity of faults in a computational model that assigns material properties based on node control volumes, faults are first identified based on OMR hexahedral elements. Any hexahedral element intersected by a fault surface is identified as being part of that fault. Then all nodes that make up those OMR elements are identified as belonging to the fault. The result is faults that are one OMR cell thick, where the thickness is dependent on the level of refinement, and the faults are two nodes thick. There are many places where faults intersect, resulting in some nodes being identified as belonging to more than one fault (Figure 4-7). In this case, the last fault material encountering the node is assigned; some analyst inspection is usually required to make sure this is a reasonable assignment.

Identification of Exterior Nodes

Exterior nodes are identified and associated with one of six possible boundary types: top, bottom, west, east, south, or north. This is done based on the direction of the vector normal to the triangular exterior faces of the grid. The triangular faces are all orthogonal to the coordinate axis directions because of the methods used to construct the grid. Some nodes may belong to more than one boundary type. Along a 90-degree edge, a node will belong to two boundaries; for example, south and top. At a 90-degree corner, a node will belong to three boundaries; for example, south, top, and west. These exterior node boundary types are used in assigning boundary conditions to the flow and transport models.

In addition to a list of nodes, an area vector is computed for each exterior node i . This area vector provides the area associated with each exterior node and the normal vector associated with nodes. This allows one to convert a recharge map that provides information, for example, in units of meters per square meter per year into a per-node rate of kilograms per second (kg/s).

This method does not always provide the information desired for setting boundary conditions. The top of the model changes elevation via discrete stairsteps. As a result, nodes associated with any vertical face of the model facing south will be identified as part of the south boundary.

Figure 4-8
West-East Cross Section 12 km North of the South Boundary of the Model Showing Two HFMs

A second method is used to identify different boundary types. This method uses knowledge of the grid coordinates. Because the minimum and maximum extents of the model are known, the boundaries are defined as:

- South: set of all nodes such that $YMIN - e < y < YMIN + e$
- North: set of all nodes such that $YMAX - e < y < YMAX + e$
- West: set of all nodes such that $XMIN - e < x < XMIN + e$
- East: set of all nodes such that $XMAX - e < x < XMAX + e$
where e is less than the smallest grid spacing.

The top and bottom can then be computed using logic defined by:

- Top: all exterior nodes not members of the sets (south, north, west, east) and $z > 0$
- Bottom: all exterior nodes not members of the sets (south, north, west, east) and $z < 0$

Identification of Nodes Associated with Breakthrough Planes

Breakthrough planes are identified in an analogous manner to the way faults are identified. Octree mesh refinement hexahedral elements that intersect the breakthrough planes are identified and any node associated with a breakthrough plane OMR cell is identified as belonging to a node list that defines the breakthrough plane.

Identify Underground Test Cavity

Underground nuclear test nodes are defined using the same procedure described below for the open (or screened) intervals of wells. These test cavities are associated with level 4 refinement nodes in the computational mesh. The eight nodes that surround each test point are identified as being associated with this test ([Figure 4-9](#)).

Compute Distance Between Each Grid Node and Nearest Point on the DEM

The flow and transport calculations require the definition of the depth under land surface of each node of the grid. This quantity is used to assign permeabilities with a dependence on overburden or lithostatic pressure. The procedure used to do this is to use the grid-to-grid interpolation feature of LaGriT. The DEM surface is used as the source grid, and the model mesh is the sink grid. The DEM is first modified by assigning a new floating point node attribute, *elev*, which is equal to the elevation of the DEM. The z coordinates are then all set to a constant value. Grid-to-grid Voronoi

Detail in the Northern Testing Area

Figure 4-9

Example of Mesh Refinement Around Underground Nuclear Test Locations, Northern Testing Area

interpolation, which will assign the elevation attribute from the DEM grid to the nearest node in the FFG grid, is used to interpolate the *elev* attribute from the DEM *source* grid onto a floating point node attribute, *elev*, of the *sink* grid. The depth below land surface for each node is then calculated as the difference:

$$depth_below_topography(n) = elev(n) - z_coordinate(n) \quad (4-1)$$

Compute Bounding Box of Voronoi Polyhedra for Each Grid Node

The vertical extent of each computational control volume is also used for computing the depth-decay permeability, because depth decay is computed in the manner described by DOE/NV (1997). The control volume for each node is computed from the Voronoi polyhedra associated with each node. This information is provided by computing six parameters — XMIN, XMAX, YMIN, YMAX, ZMIN, ZMAX — that define the bounding box for each Voronoi polyhedron. As the control volumes for a node are not necessarily cubes or rectangles, this approach gives only approximate geometric factors for computing depth decay. This is considered a reasonable approximation in light of the overall uncertainty surrounding the depth-decay process.

Compute Well Interval Information

Open or screened interval information for each well is provided so that it can be translated to the computational mesh. Each of the open intervals of 37 wells has map coordinates *x,y* and an open interval *z1* to *z2*. The open intervals are associated with a set of nearby, level 4 refinement nodes in the computational mesh. The well interval is discretized into a set of 1-m subintervals, each of which is associated with a computational node. All 1-m subintervals associated with a unique computational node are added and a table is constructed listing:

- Well interval number
- Computational grid node number associated with subinterval
- Number of meters of subintervals associated with a well interval
- A flag indicating whether the subinterval intersects a fault and, if yes, the fault number

This information is utilized in model calibration.

Compute Sparse Matrix Coefficients for FEHM

The sparse matrix coefficients associated with the grid geometry and used by the FEHM flow and transport model are computed and written in a file format specific to FEHM. The information in that file is:

- Volume of the Voronoi cell associated with each node
- Area of each face of each Voronoi cell
- Edge graph of the tetrahedral mesh defining the connectivity between nodes

4.4 Material Properties

Each node in the FEHM mesh has an associated material property index that is used to assign hydraulic properties. The following sections describe the approach used for HSU and fault hydraulic parameter assignment.

4.4.1 Hydrostratigraphic Unit Permeability

Values used for the hydraulic properties of HSUs in the simulation of groundwater flow and transport should be consistent with available information to provide confidence in the reasonableness of the simulations. Specifically, intrinsic permeability is a basic parameter for groundwater flow modeling. Representative intrinsic permeability for the formations to be modeled, at the scale over which the model is discretized, is integral to producing defensible model predictions. Intrinsic permeability is treated as a calibration parameter in the Frenchman Flat CAU steady-state flow model. An explanation of the calibration approach and results are provided in [Section 5.0](#) of this report. There are uncertainties in the determination of representative parameter values as detailed in [Section 3.0](#). In [Sections 6.0](#) and [7.0](#) of this report, sensitivity and uncertainty analysis results will try to address some of these issues.

The reduction of permeability with depth of burial (depth decay) has been postulated as an important feature of the NTS flow system (see [Section 3.0](#)). When depth decay is used in the model the material assignment remains the same, but an additional external calculation is made. Using a unit intrinsic permeability, the control volume integrated permeability, which represents the change that occurs from depth decay, is computed and saved as FEHM permeability factors, or *fperm*.

This input is used to modify the reference intrinsic permeability, k_0 , initially input and assigned to each node of the HSU.

Depth decay via $fperm$ adjustment was computed in a modification of the depth integration described in the UGTA regional model (DOE/NV, 1997) using the following formula, which gives the permeability reduction over a vertical interval defined by $z1$ and $z2$ with depth-decay coefficient λ :

$$fperm = \frac{1}{2.303(-\lambda)} 10^{-\lambda z} \Big|_{z1}^{z2} \quad (4-2)$$

Because FEHM determines its control volumes from node locations (unlike the block-centered code used in the UGTA regional model), which also may not necessarily be rectangles or squares, the bounding control volume coordinates were used in the depth-decay calculation. In the case of non-rectangular control volumes, the computed depth decay is approximate because the height of the control volume may not be constant. This was deemed a reasonable approximation in light of the overall uncertainty surrounding the depth-decay process.

4.4.2 Fault Permeability

Faults are also specified by material zones and are specified after the HSUs are defined. However, the material properties associated with the HSU nodes remain assigned to the fault nodes pending another property assignment. The approach to parameterizing the faults is to multiply existing fault node properties (still derived from an HSU) by a permeability factor. Thus, the difficulty that could be encountered by directly assigning a fault permeability that is reconciled with each HSU that it crosses is avoided. For instance, if a fault crosses both aquifers and confining units (which most do) and a fault permeability of 10^{-16} m^2 is assigned to a node with a permeability of 10^{-12} m^2 , the aquifer would see the fault as a barrier, but a confining unit with a permeability of 10^{-16} m^2 would see the fault as neutral. This approach tacitly assumes that a fault acts the same in each HSU that it encounters. Some faults (mainly within the Rock Valley fault system) are defined differently within the LCA. In the displacement fault HFM, fault zones are defined separately for the AA than for the rest of the HSUs.

4.5 Boundary Conditions

The solution of the groundwater flow equations requires specification of head and/or flow at the edges and at internal discharge points of the numerical model. This is particularly important for the Frenchman Flat CAU model because the model boundaries do not coincide with natural hydrologic boundaries. The Frenchman Flat CAU model must account for regional inflow and outflow across all four lateral edges and internal flow from precipitation recharge. There are no internal discharge locations within the Frenchman Flat CAU flow model domain. The following sections describe the implementation of these conditions in the Frenchman Flat CAU flow model.

4.5.1 Recharge

Recharge is implemented in the CAU model as a specified flux condition, where a given volume (mass) of water is applied based on the above recharge models. Recharge flux is considered to be constant over time, but it varies over the domain as a function of altitude and soil and vegetation types. To obtain the required model input in mass per time for each top node, recharge flows were calculated as the total mass for each node. Total mass was calculated at each Thiessen polygon defining the contributing area of each node at the top of the FEHM model via geographic information system operations. When two or more nodes are located exactly above each other (a staircase formation), the recharge flux was allocated between these nodes according to their physical location. [Figure 2-2](#) through [Figure 2-10](#) show the resulting recharge distributions for the USGSD, MME, DRIA, and DVRFS datasets, respectively, as implemented for FEHM input. [Table 4-5](#) summarizes the total mass flows over the Frenchman Flat model domain area for each recharge model considered. It must be noted that the amount of recharge over the Frenchman Flat model domain is very small and does not vary significantly from one recharge dataset to another. Differences among the recharge distributions are primarily manifested in the boundary heads and lateral boundary fluxes that are derived from the corresponding calibrated regional model.

Table 4-5
Total Recharge over the Frenchman Flat Model Area

Recharge Model	Total Recharge	
	kg/s	mm/yr
DRI - Chloride Mass Balance with Alluvial and Elevation Masks (DRIAE)	4.45	0.246
DRI - Chloride Mass Balance with Alluvial Mask (DRIA)	4.54	0.251
Original Maxey-Eakin from UGTA Regional Model (OME)	22.79	1.261
Modified Maxey-Eakin from UGTA Regional Model (MME)	8.63	0.478
USGS - Rainfall-Infiltration with Redistribution (USGSD)	5.94	0.328
USGS - Rainfall-Infiltration without Redistribution (USGSND)	5.26	0.291
USGS - Death Valley Regional Ground-Water Flow System (DVRFS)	5.88	0.325

kg/s = Kilograms per second
mm/yr = Millimeters per year

4.5.2 Boundary Heads

Initially, boundary heads from the UGTA regional model analysis described in SNJV (2004d) were interpolated onto the edge nodes of the FEHM CAU model. These heads represent a mass-conservative calibrated solution to the equation that governs flow in the UGTA regional flow model (DOE/NV, 1997). During the calibration process, these heads were reviewed, and, in spots, revised based on further examination of measured heads and interpolated heads determined from the UGTA regional model. Different boundary head configurations were considered during the model calibration and uncertainty analyses depending on the alternative HFM and recharge distribution used in the model.

5.0 FLOW MODEL CALIBRATION

The Frenchman Flat CAIP (DOE/NV, 1999) and modeling approach/strategy (IT, 2001b) indicate that model calibration will be conducted after flow model construction. These documents describe calibration as “the process of matching historical data” and state that “calibration consists of determining model parameter values such that simulated heads and fluxes are consistent with observed or target values.” The ASTM Standard Guide D 5490-93 (ASTM, 1993b) defines calibration as, “... the process of refining the model representation of the hydrogeologic framework, hydraulic properties, and boundary conditions to achieve a desired degree of correspondence between the model simulations and observations of the groundwater flow system.” The purpose of the Frenchman Flat groundwater flow model calibration is to transform the conceptual model described in [Section 3.0](#) into mathematical models for representing the groundwater flow system in the Frenchman Flat CAU area. This is accomplished through the guided adjustment of boundary heads and hydraulic properties for HSUs and faults within a hydrostratigraphic framework in order to match specified targets. Targets included weighted observed water-level data within the model boundary and boundary head and flow estimates from calibrated regional models. Recharge estimates are not used as calibration targets. Instead, they are fixed as model input values during calibration and uncertainty analyses.

This section describes the flow model calibration approach and the calibration results for the BASE HFM. The BASE HFM (see [Section 2.3.3.1](#)) is the most viable model based on existing data of the subsurface geology of the Frenchman Flat CAU model area and is developed and described in detail by BN (2005a). The model calibration described in this section is based on the net infiltration/recharge dataset from the USGSD model, which is summarized in [Section 2.2.1](#); other recharge models and their associated boundary conditions are investigated during the conceptual model uncertainty analysis documented in [Section 6.0](#) of this report. Flow model parameter sensitivity analyses are presented in [Section 7.0](#).

The Frenchman Flat CAU flow model conceptual model uncertainty analysis documented in [Section 6.0](#) considered five HFMs and six recharge models. A shorthand notation is used to identify HFMs and water-balance conditions such that each model is referred to by HFM-water balance. For example, the BASE-USGSD model uses the BASE HFM (as defined in BN, 2005a) with the USGSD recharge model and boundary flows (as defined in SNJV, 2004d) as described in this section.

Similarly:

- BASE-DRIA consists of the BASE HFM with the DRI alluvial mask recharge model and boundary heads and flows.
- BASE-MME consists of the BASE HFM with the MME redistribution recharge model and boundary heads and flows.
- BASE-USGSND consists of the BASE HFM with the USGS no redistribution recharge model and boundary heads and flows.
- BASE-DVRFS consists of the BASE HFM with the DVRFS model recharge and boundary heads and flows.

Other possible HFMs (see [Section 2.3.3](#)) are:

- BLFA - Extended continuous BLFA HSU alternative
- CPBA - Extended UCCU beneath all of CP basin alternative
- DETA - No detachment fault alternative
- DISP - Displacement (aquifer juxtaposition) alternative

5.1 Calibration Approach for the Frenchman Flat CAU Groundwater Flow Model

The goal of model calibration (also called “parameter estimation,” “solving the inverse problem,” and “inversion”) is to produce a model whose results agree with available data. This process typically involves the guided adjustment of model parameters within their ranges of variation. How this is approached can be critical. For example, Freyberg (1988) presented a study in which students were given a model to calibrate and subsequently use to make a prediction. The best-calibrated model actually made the worst predictions, primarily because the best-calibrated model was developed by adjusting hydraulic conductivity on a block-by-block basis. This example demonstrates that producing the best goodness-of-fit statistics is not the sole objective of model calibration.

The ASTM Standard Guide D 5981-96 (ASTM, 1996) and Anderson and Woessner (1992) describe a general protocol for model calibration. In this protocol, each cycle of parameter adjustment should begin with sensitivity and error analysis. The sensitive parameters to be adjusted should be considered in light of the data certainty. Conceptually, the process is not much different than if an automated parameter estimation technique is used (Poeter and Hill, 1997). The general protocol used for the Frenchman Flat flow model is shown in [Figure 5-1](#).

Hill (1998) also presents a general model calibration procedure that has several components, the most relevant of which were used to calibrate the Frenchman Flat flow model. The manner in which they were addressed in the Frenchman Flat flow model is shown in [Table 5-1](#). In the trial-and-error approach, the model is run, errors analyzed, adjustments made, and the cycle repeated. This approach is typically tedious because it requires preparation of model datasets and evaluation of model results for each model adjustment. Discrete sensitivity simulations to test model behavior are also often performed in a manual fashion. The trial-and-error approach is also easily abused where changes are made in an ad hoc manner without insight into the root cause of the model misfit. However, with careful iterations of sensitivity analyses and with a proper protocol ([Figure 5-1](#)), a trial-and-error calibration can yield reasonable and reliable results. Local optimality of calibrated parameters can be checked using sensitivity and perturbation analyses.

An alternative to trial-and-error calibration is to use an automated approach where the model response to parameter changes is systematically evaluated and the more important parameters that improve calibration are identified. The PEST code (Watermark Numerical Computing, 2004) can be used for this purpose. The PEST code begins by perturbing each parameter to be considered a certain amount and recording how the model calibration changes. The Levenberg-Marquardt procedure is used to compute parameter updates that improve the model agreement with the target data. The basic algorithm used by PEST has a long history of successful use in solving groundwater problems, and is also available in such codes as MODFLOW-2000 and UCODE. For more detail, the reader is referred to the PEST documentation (Watermark Numerical Computing, 2004). Use of a parameter estimation code has several benefits, including using analyst time more effectively because less manual preparation and manipulation of datasets are required. In addition, a parameter estimation tool provides a framework that helps focus attention on analyzing model errors and their cause.

Figure 5-1
General Modeling Protocol

Table 5-1
Calibration Components and Implementation

Calibration Component ^a	Implementation in the Frenchman Flat CAU Flow Model
Apply the principle of parsimony.	Hydrostratigraphic units or other geologic properties are not subdivided. Faults are only divided when geologic rationale justified the division.
Include many kinds of data as observations.	Well head and regional model estimated fluxes at the model edges are considered.
Assign weights that reflect measurement errors.	Weights are developed from uncertainty estimates published in the Frenchman Flat hydrologic data document (SNJV, 2004d).
Evaluate model fit.	Model fit is continually evaluated with residual post plots and other tools and statistics.
Evaluate optimized parameter values.	The reasonableness of calibrated model parameters is compared to available measured values.
Evaluate the potential for additional estimated parameters.	Sensitivity analysis and post plots are used to identify locations where additional parameter adjustments are necessary.

^a Hill, 1998

The PEST code also includes a variety of statistical analyses that help develop understanding of the model. These features include sensitivity and correlation coefficients, parameter confidence limits, and eigenvalue and eigenvector analysis. The sensitivity and correlation coefficients describe how much the model calibration changes relative to a parameter's change, and how parameters may influence one another. This is useful in testing the conceptual model as to what parameters are believed to control model behavior, and what parameters may act similarly on model results. In addition, parameters that may be important to model calibration can be quantitatively identified and considered in more detail. The confidence limits and eigenvalue and eigenvector analysis are useful in understanding how well the measured data support the model parameters, and how many parameters should be considered for calibration.

The ASTM Standard Guide D 5490-93 (ASTM, 1993b) describes several approaches for evaluating the agreement between a flow model and modeled system. These procedures were used in calibrating the Frenchman Flat flow model, and include qualitative and quantitative comparisons between model results and the following:

- Measured heads at wells
- Boundary fluxes from regional models reflecting different recharge models
- Estimated ranges of HSU hydraulic parameters from pumping-scale hydraulic test data

A variety of numerical and graphical tools are used to investigate flow model calibration. These include summary statistical measures such as the mean error (*ME*), largest and smallest errors, standard deviation (*SD*) of error, and sum of weighted squared error. Error, or residual head ($r_{h,i}$), is defined as follows:

$$r_{h,i} = H_i - h_i \quad (5-1)$$

where h_i is the computed head at the location where observed head H_i is measured. A similar definition is used for boundary flux residuals ($r_{f,i}$):

$$r_{f,i} = F_i - f_i \quad (5-2)$$

where f_i is the computed flux at a location where the flux from the regional model (F_i) is determined.

Mean error is defined as follows for head residuals:

$$ME = \sum w_{h,i} r_{h,i} / n \quad (5-3)$$

where $w_{h,i}$ is the weight assigned to the head measurement H_i . Standard deviation of error is defined as follows (ASTM, 1993b):

$$SD = [\sum w_{h,i} (r_{h,i} - ME)^2 / (n-1)]^{1/2} \quad (5-4)$$

where n is the number of computed and measured heads being compared.

The sum of the weighted errors squared (also called phi, after the Greek alphabet symbol used to denote it, as well as “goodness of fit” or the “objective function”) is defined as (Watermark Numerical Computing, 2004):

$$\Phi = \sum (w_{h,i} r_{h,i})^2 + \sum (w_{f,i} r_{f,i})^2 \quad (5-5)$$

where w_h and w_f are the observation weights assigned to head and flux targets, respectively; and r_h and r_f are defined in equations (5-1) and (5-2).

If the weights assigned to calibration data change, all these measures will change even if the model results are the same. Thus, as discussed in [Section 7.2](#), it is important to compare results using a consistent weighting scheme.

During calibration, attempts should be made to reduce the mean error to zero; that is, there should be no bias in the mean error. This results in a model that has no systematic bias (in the univariate statistical sense). Errors of -1 m and +1 m produce the same mean error as -50 m and +50 m, but it is obvious that a model with 50 m of error is not in as good agreement as one with an error of 1 m. Consequently, the standard deviation, which describes the spread of the errors, is also used in the calibration process. Although the mean error may be low, a large spread in the errors signifies that the model may be inadequate.

Statistical measures are useful for summarizing model behavior but do not readily give a sense for the spatial distribution of errors. To address this issue, the following graphical analyses are also sometimes used to calibrate the Frenchman Flat flow model:

- The scattergram, or cross plot, of observed data versus computed results is useful for identifying overall goodness of fit and bias.
- Plots of posted head residuals in plan view show the spatial distribution of errors in the model. This type of plot is useful for examining whether the model errors are randomly distributed in space or, less desirably, whether errors are clustered, with positive errors in some parts of the model and negative errors in others. For the Frenchman Flat model, errors may be clustered because the observations themselves are clustered.
- Flow residuals are also examined using bar charts.
- Histograms of weighted-head residuals can be examined for normality to identify bias in the calibration and identify residual outliers.

The reader is referred to ASTM Standard Guide D 5490-93 (ASTM, 1993b) for more information regarding these types of analyses for understanding model errors, some of which are also presented in later sections of this section. The reasonableness of the flow directions is also assessed qualitatively during the calibration phase via streamline advective particle tracking. Finally, it is important to recognize that, regardless of the fitting procedure, the goal of model calibration is to find a set of model parameters that best (or at least reasonably) represent the hydrogeologic system and the available data.

The alternative models for Frenchman Flat were calibrated using a combination of automated parameter estimation with PEST and manual trial-and-error approaches. Initial attempts to optimize more than a few parameters at a time with PEST proved unsuccessful, so PEST was ultimately

applied by focusing it on specific aspects of the Frenchman Flat groundwater system. This was done by increasing the weights on specific observations of either flux ($w_{f,i}$) or hydraulic head ($w_{h,i}$) in the objective function calculations, and optimizing only model parameters that were likely to affect the model's ability to match specific observations (e.g., fluxes) based on sensitivity analyses for the BASE-USGSD model. In cases where weights were adjusted to focus the calibration on different aspects of the model, these weights were restored to the original values before calibration statistics such as the objective function value were calculated.

The calibration strategy developed for the Frenchman Flat flow model was to: (1) optimize groundwater fluxes through the sides of the model by adjusting the permeability of the LCA and major faults that intersect the model boundaries; (2) match hydraulic heads in the CP basin and other model boundaries by selectively adjusting heads along the model boundary adjacent to the basin ([Section 5.3](#)), and, when applicable, by optimizing fault permeabilities within and adjacent to the CP basin; and (3) match hydraulic heads in the alluvium and tuffs within the Frenchman Flat basin by manually adjusting the permeabilities of the alluvium, tuffs, and minor faults that sensitivity studies for the BASE-USGSD case showed were likely to have an impact on these heads.

For some recharge models and boundary conditions, it was necessary to perform these steps iteratively because nonlinear parameter interaction in later parameter adjustments could sometimes adversely impact model results achieved in earlier stages of the calibration. While only small deviations from targets were allowed when matching the groundwater head data, less strict criteria were used when matching boundary fluxes because the target values were obtained from regional groundwater models used to bracket lateral flux uncertainty. The regional model boundary flux analysis was used to ensure that the Frenchman Flat flow model was reasonably consistent with the overall flow directions and water balance in the regional groundwater system ([Section 5.2](#)). However, these regional models do not have enough hydrogeologic detail at the scale of the Frenchman Flat CAU flow model to provide information about flow in specific faults or hydrologic units, so larger deviations from the target boundary fluxes were tolerated during calibration.

5.2 Calibration Data

As previously discussed, two types of information, or targets, were used for calibration of the Frenchman Flat flow model:

- Hydraulic head from wells (SNJV, 2004d; [Table 3-3](#), and [Appendix A](#) of this document)
- Boundary flows estimated from regional model analysis using the UGTA regional model as presented in the Frenchman Flat hydrologic data document (SNJV, 2004d) and in [Section 3.4](#).

Because an automated procedure was used to aid calibration, multiplicative weight factors were developed and assigned to data with different levels of accuracy and measurement units. The PEST manual suggests that the weights be the inverse of the measurement standard deviation (Watermark Numerical Computing, 2004); measurements with a larger standard deviation receive a smaller weight. The weights, which have reciprocal units of the target data, also transform the objective function contribution from different data types into dimensionless values that can be compared regardless of measurement units.

Although the weights used in calibration of the Frenchman Flat flow model are based on measurement uncertainty (SD), as described above, other considerations often motivate the use of weights other than the inverse of SD during flow model calibration (e.g., Wolfsberg et al., 2002; DOE/ORD, 2004). For instance, it may be more important to accurately depict water-level gradients in some areas of the model compared to other areas, in which case weights are assigned by considering the required accuracy of the model in specific areas. Alternatively, when data are irregularly distributed in space, higher weight could be placed on targets in data sparse areas.

For the Frenchman Flat flow model, the assignment of weights to the hydraulic head data was accomplished by considering the individual factors that contribute to uncertainty in the head measurements. The total uncertainty in the head measurement included uncertainties associated with:

- Ground-surface elevation: derived using different measurements of ground-surface elevation.
- Water-level elevation: derived from the standard deviation of available water-level measurements at each well.
- Depth-to-water measurement: derived from the method used to measure the water level.

- Barometric effects: derived from the amplitude of water-level fluctuations in wells throughout the year (This was not considered for heads in Frenchman Flat due to the absence of reliable barometric pressure data at the time of the measurements).
- Borehole deviation correction: derived from the accuracy of the equipment used to determine the true vertical depth.
- Data frequency: derived from the temporal distribution of water-level measurements.

The derivation of these uncertainties is described in detail in the Frenchman Flat hydrologic data document (SNJV, 2004d).

Table 5-2 lists the weights used for the target heads during model calibration, and Figure 5.2 shows a histogram of the weights. The weights range between 0.05 and 2.88. The highest weights (above 2) are associated with three wells in the ER-5-4 well cluster in central Frenchman Flat and Well UE-5n, which is located in the central testing area. The weight of 0.05 applied to the measured head at Well ER-5-3 #2 is a result of a failure of heads in that well to completely stabilize to allow for a determination of a steady-state head value (SNJV, 2004d, p. 8-28).

The UGTA regional model boundary flow analysis for the Frenchman Flat CAU model is summarized in Appendix E of the Frenchman Flat hydrologic data document (SNJV, 2004d). The boundary flows for each face of the model were used as calibration targets to ensure that the Frenchman Flat CAU model is in general agreement with the regional hydrologic system. A summary of the boundary flow targets is provided in Table 3-2.

Weights used for flux targets in the calibration objective function (equation [5-5]) were determined by testing parameter sensitivity and considering the conceptual model. The west face of the model serves to both supply water to the volcanic and basin-fill HSUs and is the primary flux out of the model domain for the LCA. As a result, this face was assigned a slightly higher weight for the calibration objective function (0.04). The flux on the east face of the model was controlled by the permeability of the LCA, which is the only HSU on this model face. Therefore, a slightly lower weight was assigned to this face of the model (0.014) to account for the relative simplicity of matching the flux on this face of the model. To ensure that the direction of the balance of incoming flux was correct, the north face was assigned an equivalent weight as the west face of the model (0.04). The final face, the south, was well matched when the north, east, and west faces were correct,

Table 5-2
Head Calibration Weights

Well Reporting Name	Weight for Calibration Objective
ER 5-3 (3-in. deep)	0.84
ER 5-3 (3-in. shallow)	0.94
ER 5-3 upper (main)	0.93
ER 5-3 lower (main)	0.93
ER 5-3 #2	0.05
ER 5-3 #3	0.95
ER 5-4 upper (main)	2.33
ER 5-4 lower (main)	2.33
ER 5-4 (piezometer)	2.33
RNM-1	0.63
RNM-2	1.11
RNM-2s	0.86
TW-3	0.83
UE-11a	0.83
UE-11b	0.09
UE-5 PW-1	1.41
UE-5 PW-2	1.33
UE-5 PW-3	1.41
UE-5c WW upper	1.61
UE-5c WW lower	1.10
UE-5n	2.13
WW-1	0.23
WW-4	0.50
WW-4A	0.83
WW-5A	2.88
WW-5B	1.00
WW-5C	0.78
WW-C	0.69
WW-C1	0.98

Figure 5-2
Histogram of Calibration Weights

and was therefore assigned an equivalent weight to the east face (0.014). The values were selected in order to make the flux contribution to the objective function a small, but nonetheless significant, fraction of the head contribution to the objective function using the initial parameter estimates at the start of the model calibration.

5.3 Boundary Head Adjustments

As described in [Section 4.5.2](#), model boundary heads are based on heads interpolated from calibrated regional models onto nodes of the computational mesh along the lateral boundaries of the model domain. The starting points for the CAU model specified-head boundary conditions are the results from the UGTA regional model (SNJV, 2004d) and the DVRFS model (Faunt et al., 2004), as interpolated onto the Frenchman Flat flow model boundaries. During calibration, boundary heads adjustments were considered at three locations:

- CP basin: The UGTA regional model and the recent DVRFS model had a persistent 85-m deviation from the measured heads at Wells WW-4 and WW-4A just inside the western edge

of the CAU model domain. Simulated heads in the area were close to 760 m amsl and head measurements in local wells were near 845 m amsl. Thus, if boundary heads in this part of the model had been based on the results from the UGTA regional model or DVRFS model, a consistent error of about 85 m would have resulted that was entirely a consequence of an inaccurate boundary condition assignment.

- Southern Yucca Flat: Head measurements at Wells WW-C and WW-C1 showed that water levels in this area are about 8 m lower than simulated heads from either regional model. However, the adjustments necessary to bring the measured heads and heads calculated by the regional models into agreement were not made along the boundaries of the Frenchman Flat flow models because these adjustments caused groundwater to flow northward from Frenchman Flat into Yucca Flat within the LCA in the model, counter to the direction indicated by heads in the LCA.
- Well TW-3: This well is close to the eastern edge of the model boundary and has a water-level measurement that is about 2.5 m lower than the model-calculated heads. A reduction of water levels in the central-eastern edge of the model boundary was necessary to match the available water-level measurements at this well.

Boundary heads computed using the two regional models did not indicate significant vertical gradients in the vicinity of the model boundaries. Therefore, all boundary head corrections were made by adding or subtracting a constant head correction uniformly across the vertical dimension. The correction was made within a window centered on each well, and the correction linearly decayed to zero toward the edges of the window. [Figure 5-3](#) shows the adjusted boundary heads from the UGTA regional model (with USGSD recharge data). Other boundary heads used for boundary condition uncertainty analysis will be discussed in the conceptual model uncertainty analysis reported in [Section 6.0](#).

April 26, 2006

5.4 Parameter Assignment

Each node in the FEHM mesh has an associated material property index that is used to assign hydraulic properties. Faults are also specified by material zones and are specified after the HSUs are defined. However, the material properties associated with the HSU nodes remain assigned to the fault nodes pending another property assignment or change. In the Frenchman Flat flow model, HSU permeabilities within faults were modified, as necessary to calibrate the model, by applying a fault permeability multiplier (*fperm*) that increased or decreased HSU permeabilities by a constant factor. This approach recognizes that fault properties depend on the hydrologic and mechanical properties of the rocks through which they pass, and thus, that fault properties are likely to change along a fault.

This approach also avoids a conceptual problem that would arise if faults were assigned a constant permeability rather than a permeability multiplier. If a constant value of permeability were assigned to a fault, the fault would act as both a barrier and a conduit, depending on the permeability of the HSU adjacent to the fault. For instance, if a fault crosses both aquifers and confining units (which most do) and a fault permeability of 10^{-16} m^2 is assigned, the fault would function as a barrier with respect to flow through an adjacent aquifer with a permeability of 10^{-12} m^2 , but the fault would have no effect on flow through a confining unit with a permeability of 10^{-16} m^2 . This approach makes it somewhat more difficult to specify a fault that behaves as a barrier or a conduit in each HSU that it cross-cuts.

Depth decay of permeability in the Frenchman Flat CAU model was computed in the same manner that was applied to the UGTA regional model (DOE/NV, 1997). In this approach, the permeability assigned to a node is the integrated permeability over the range of depths spanned by the volume associated with the node ([Section 4.4.1](#)). Because FEHM determines its control volumes on the basis of node locations (unlike the block-centered code used in the regional model), and the edges of the control volumes may not necessarily comprise rectangles or squares, the coordinates defining the bounds of the control volumes were used in the depth-decay calculation. In the case of non-rectangular control volumes, this method of computing depth decay is approximate because the height of the control volume may not be constant. This was deemed a reasonable approximation in light of the overall uncertainty surrounding the depth-decay process.

5.5 Calibration of the BASE-USGSD Flow Model

This section describes the calibration of the Frenchman Flat groundwater model that uses recharge rates and boundary conditions associated with the USGS recharge map based on rainfall/runoff with re-distribution (USGSD) ([Section 2.2.1](#)). The results obtained using other recharge maps and boundary conditions are presented as part of the uncertainty analysis discussed in [Section 6.5](#)

Hydraulic conductivity data summarized by SNJV (2004d) were analyzed to obtain initial estimates of the mean HSU hydraulic conductivities and the uncertainties in order to constrain the parameter estimation process using PEST. This analysis focused on pumping-scale data specific to the Frenchman Flat CAU area when such data were available. Mean and standard deviations of hydraulic conductivity for each HSU were calculated using the arithmetic average of all interpretations of conductivity for a particular test interval (SNJV, 2004d; [Section 5.5.1](#)).

Ultimately, the approach used during both automated parameter estimation and during manual calibration of the BASE-USGSD and alternative models was to hold the value of the depth-decay coefficient constant ([Table 3-6](#)) and allow the reference permeability (that at land surface, k_0) to vary during the calibration. This reference permeability was used with a permeability reduction factor calculated based on the depth of each node to compute the depth-decayed permeability at each node in the model (Equation [4-2]). To estimate the values of reference permeability for each HSU, an approach was adopted in which permeabilities estimated with different assumptions and methods were given equal weight and allowed to contribute to parameter variability. First, test estimated hydraulic conductivity was extrapolated to land surface using the depth-decay relationship (Equation [3-3]) and the 95-percent confidence interval of the depth-decay coefficient ([Table 3-6](#)). Then, initial bounds on permissible reference permeability parameter ranges to be explored during automated parameter estimation were estimated using three to four standard deviations from the mean value, or two to three orders of magnitude from the mean when a standard deviation could not be calculated.

[Table 5-3](#) summarizes the resulting reference permeability values that were used initially for each of the Frenchman Flat HSUs. These initial bounds on the parameter ranges were intended to be large in order to allow PEST to be free to explore the parameter space without any subjective biases.

Table 5-3
Initial Intrinsic Permeability (m²) Reference Values at Land Surface Used
in CAU Flow Model Calibration

Frenchman Flat Phase II HSU	Symbol	Number of Observations	Data Analysis Results	
			Mean	Standard Deviation
			Log k ₀ (m ²)	
Alluvial Aquifer	AA	17	-8.76	1.67
Older Altered Alluvial Aquifer	OAA	AA (17) ^a	-8.76	1.67
Timber Mountain Welded Tuff Aquifer	TM-WTA	5	-6.86	0.52
Timber Mountain Lower Vitric Tuff Aquifer	TM-LVTA	TM-WTA (5) ^a	-6.86	0.52
Topopah Spring Aquifer	TSA	(VA, 38) ^b	-7.99	1.23
Lower Vitric Tuff Aquifer	LVTA	(VA, 38) ^b	-7.99	1.23
Upper Tuff Confining Unit	UTCU	LTCU (1) ^a	-11.49	N/A
Lower Tuff Confining Unit	LTCU	1	-11.49	N/A
Playa Confining Unit	PCU	(VCU, 110) ^b	-10.63	2.12
Wahmonie Confining Unit	WCU	(VCU, 110) ^b	-10.63	2.12
Volcaniclastic Confining Unit	VCU	(VCU, 110) ^b	-10.63	2.12
Lower Carbonate Aquifer	LCA	5	-8.45	1.28
Upper Clastic Confining Unit	UCCU	(UCCU, 2) ^b	-10.02	1.07

^a Data mean and range from similar Frenchman Flat HSU listed here.

^b Data mean and range from NTS-wide pumping-scale conductivity data for the HSU listed here.

Faunt et al. (2004) observed that using conductivity depth decay in the DVRFS model produced some hydraulic conductivity values outside the range of expected values and suggested that this may indicate that hydraulic conductivity does not decrease below a certain threshold. To mitigate this potential problem, the implementation of depth decay in the Frenchman Flat model included setting a minimum possible intrinsic permeability of 10⁻²⁵ m² in each HSU.

5.5.1 Initial Parameter Adjustments

Different sets of parameters were considered as adjustable or fixed during the early and late phases of the calibration. In general, the most of the calibration effort focused on optimizing HSU permeabilities, but fault permeability factors were also adjusted, as necessary, to match the target boundary fluxes or hydraulic heads. Other types of parameters were evaluated only during initial

phase of the calibration, after which they remained fixed. Parameters included in this latter category were:

- Permeability depth-decay coefficients for model HSUs (Table 3-6)
- Vertical-to-horizontal anisotropy of HSU permeabilities
- Boundary impedance for aquitard HSUs along the model boundaries.

The depth-decay coefficients for the model were set to the values listed in Table 3-6 in recognition that simultaneously estimating both the reference permeabilities and the depth-decay coefficients would induce correlations that would leave the problem of calibrating the flow model intractable. This is because (1) there is not enough range in the depths of the head measurements in any HSU to constrain the estimate of depth decay the Frenchman Flat basin, and the (2) the permeability at a given depth could be adjusted by mutual changes to either depth decay coefficient or the reference permeability, thus giving rise to an unavoidable correlation in the model parameters.

The vertical-to-horizontal anisotropy ratios were set to unity in the BLFA and LCA, to 0.015 in the LTCU, and 0.5 to all other HSUs. The relatively small value of 0.5 ($k_h/k_v = 2.0$) for most of the HSUs was driven by a recognition that depth decay in permeability also contributed an effective anisotropy to the system, and that stipulating larger values for k_h/k_v would unduly restrict the potential of the model to explore the possibility of vertical leakage between the AA and underlying HSUs. The value of 0.015 (corresponding to a $k_h/k_v = 6.667$) was chosen based on the bedded nature of the tuffs that comprise the LTCU and the need to match the simulated heads in the AA to their measured values.

The last of these parameter types, boundary impedance, is assigned to model boundary nodes in order to maintain heads interpolated from the regional model onto the BASE-USGSD flow model boundary (Zyvoloski et al., 1997a and b). Normally, a large value (10^6 or 10^7) is recommended to achieve this goal. However, in early phases of calibration, anomalously large groundwater fluxes were observed to enter the model along the four lateral boundaries adjacent to various confining units that had been assigned low permeability values. This behavior was in conflict with the expectation that confining units would transmit only small fluxes, and indicated that adjustments to the assigned boundary impedance were necessary. The problem was resolved by assigning a low value of impedance to nodes in confining HSUs when these were present along the lateral boundaries of the model. After initial testing with other values, a value of 10^{-5} was ultimately applied at boundary nodes in the confining units, but several other values were investigated during early phases of the

calibration. [Section 7.0](#) documents the sensitivities of different model results to this boundary impedance value. It should be noted that aquifer nodes along the boundaries were assigned a large impedance value (10^7), as recommended in the FEHM manual, in order to keep the assigned boundary heads constant during the flow simulations.

5.5.2 Simulated Hydraulic Heads for the BASE-USGSD Model

The simulated hydraulic heads produced by the calibrated model are shown in [Figure 5-4](#) for the water table. [Figures 5-5](#) and [5-6](#) show cross sections through the simulated head fields. Horizontal hydraulic gradients within the northern and central testing areas of Frenchman Flat are fairly flat. Although hydraulic heads in the CP basin are approximately 100 m higher than those in Frenchman Flat, hydraulic gradients within each of these two areas are relatively flat, and most of the head loss between the CP basin and Frenchman Flat is predicted to coincide with the Cane Spring fault (fault 3 in [Figure 5-5](#)). Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast ([Figure 5-4](#)), indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction.

A vertical profile of simulated head is plotted and compared against calibration target heads from the northern testing area at the ER-5-3 well complex ([Figure 5-7](#)). The calibration target heads in this figure are plotted as a function of the midpoint of the open intervals in which they were measured. The figure illustrates that vertical head gradients are virtually non-existent between the alluvium and the underlying volcanic aquifers near the ER-5-3 well complex, indicating that there is very little potential for downward flow in the alluvium, despite the overall drop in heads between the alluvium and the carbonate aquifer. Most of the head loss between the alluvium and the carbonate aquifer occurs across the thick confining units like the LTCU that are present beneath the northern testing area. Although the model overpredicts the target head in the LCA at Well ER-5-3 #2, the model accurately depicts the relatively uniform target heads within the AA and TM-WTA and the location of loss of head between the TM-WTA and the LCA across the LTCU.

The vertical profile of calibration target and simulated heads at the ER-5-4 well complex ([Figure 5-8](#)) indicates that simulated heads in the BASE-USGSD model accurately depict the near-constant heads between the water table and sea level. Simulated heads show an almost 1-m increase between the lower alluvium and the TM-WTA, which is a consequence of the higher permeability in the TM-WTA

relative to the overlying alluvium and the underlying confining units (see [Section 5.5.4](#)). The TM-WTA functions as a confined aquifer in this part of the model and connects areas of higher head adjacent to the Wahmonie Hills and CP basin to the deepest part of the Frenchman Flat basin. The higher heads in the TM-WTA, if present, would create a pressure barrier that would prevent the downward movement of groundwater from the AA into the LCA. In the BASE-USGSD model, a head loss occurs between the alluvium and the lower carbonate aquifer, but that this loss occurs entirely across the LTCU.

As described in [Section 3.5.2.2](#), the latest measurements of head in the LTCU at Well ER-5-4 #2 indicated that heads in the LTCU were in excess of 754 m and rising (SNJV, 2004d, Fig. 8-12), which is higher than any other measurement in Frenchman Flat basin. Although these measurements were not used directly in the calibration of the BASE-USGSD model because heads had failed to stabilize, they nonetheless support the concept that high-permeability intervals (in this case, within the LTCU) function as confined aquifers and connect the deep part of the Frenchman Flat basin with areas of higher head to the west. Thus, the data show a pressure barrier probably does exist in the vicinity of the central testing area, although the pressure barrier appears to be associated with high-permeability intervals within the LTCU rather than the TM-WTA. Hydraulic tests in the LTCU (SNJV, 2004b) indicated the presence of a high-permeability zone ($k = 10^{-13} \text{ m}^2$) within the LTCU that was probably associated a fractured welded interval within this largely zeolitized, nonwelded HSU.

Figure 5-4
Water-Table Contours for the Calibrated BASE-USGSD Model

Figure 5-6
West-East Cross Section of Simulated Heads at the Central Testing Area for the BASE-USGSD Model

Figure 5-7
Comparison Between Hydraulic Heads Simulated with BASE-USGSD Flow Model
and the Calibration Target Heads at the ER-5-3 Well Complex

Figure 5-8
Comparison Between Hydraulic Heads Simulated with BASE-USGSD Flow Model
and the Calibration Target Heads at the ER-5-4 Well Complex

5.5.3 Hydraulic Head and Flux Residuals

The groundwater fluxes calculated along the perimeter of the Frenchman Flat model domain with the UGTA regional model are compared to the fluxes calculated with the BASE-USGSD flow model in [Figure 5-9](#). The net fluxes calculated by the Frenchman Flat model are in good agreement with the net fluxes calculated with the UGTA model along each of the boundaries ([Figure 5-9](#)).

Simulated hydraulic heads are compared to the measured hydraulic heads that were used as calibration targets in [Figure 5-10](#) and plots of posted weighted residuals are shown in [Figure 5-11](#).

[Figure 5-10](#) shows that the simulated heads within Frenchman Flat generally agree with the measured heads to within the estimated uncertainties, but somewhat larger residuals exist at Wells ER-5-3 #2, RNM-1, WW-1, WW-5B and WW-5C, and WW-C and WW-C1.

- The simulated head at Well ER-5-3 #2, completed in the LCA, is higher than the heads measured in the LCA at this well, but lower than heads measured at nearby Wells ER-5-3 (alluvium and tuff) and ER-5-3 #3 (alluvium). This signifies that the observed downward head gradient between the alluvium and LCA in northern Frenchman Flat is captured in the model, but that its magnitude is only one-third to one-half that of the observed vertical gradient.
- The simulated heads at Well RNM-1, completed in the alluvium, are about 2.2 m higher than the heads reported for this well (731.31 +/- 1.60) (SNJV, 2004d, Table 8-3); however, because the reported heads at Well RNM-1 are approximately 2.2 m lower than the measured heads at nearby Wells RNM-2, RNM-2s and ER-5-4, it is possible that difficulties in estimating depths in Well RNM-1, which was drilled at an angle into the CAMBRIC test cavity, are primarily responsible for the head residuals at this well. Although the simulated head at RNM-1 is higher than the observed head, the simulated head falls within the error bounds associated with the measurement that reflect the difficulties in obtaining an accurate measurement at RNM-1.
- The simulated head at Well WW-1, completed in the alluvium, is about 1.2 m higher than the head reported for this well (725.25 +/- 4.4 m), but within the error bounds that result from uncertainty in nearby land surface elevation.
- The simulated hydraulic heads at Wells WW-5B and WW-5C, completed in the alluvium, are about 2 m too low and too high, respectively, compared to the measured heads (734.68 +/- 1.15 m and 729.68 +/- 1.29 m) at these wells. The low hydraulic head reported for Well WW-5C compared to heads measured at Well WW-5B to the north and Well WW-5A to the south (730.91 +/- 1.14 m) suggests that there may be a stronger hydraulic connection or

hydraulic barrier between the tuffs and the LCA in the vicinity of Well WW-5C, as originally proposed by Winograd and Thordarson (1975).

- Simulated heads in the LCA at Well WW-C and WW-C1 (both completed in the LCA) in the northwest corner of the Frenchman Flat model (southern Yucca Flat) exceed the measured heads at these wells by about 15 m. These residuals are the result of inaccuracies in the heads taken from the UGTA regional model that were used to assigned heads along the northern boundary of the Frenchman Flat CAU model ([Section 5.3](#)). These comparatively large residuals are not expected to significantly impact simulated groundwater movement through the alluvium and tuffs in the Frenchman Flat basin given the small residuals at Wells UE-5 PW-3, UE-5c WW, UE-5f, and UE-11b located on the perimeter of Frenchman Flat basin.

The plot of posted weighted residuals associated with the calibrated BASE-USGSD flow model is shown in [Figure 5-13](#). The plot is useful because it provides an indication of how errors in the simulated water levels are distributed throughout the flow model when the weights are also considered. The use of weighted residuals (rather than unweighted residuals) in the figures is appropriate because the weights are calculated from the inverse of the measurement error and therefore reflect the importance that should be place on calculated differences between the measured and simulated heads. Ideally, the distribution of weighted residuals should be randomly distributed and free of trends that would indicate a systematic spatial bias in the model results. [Figure 5-11](#) shows that positive and negative weighted residuals are contained in each region of the flow model, indicating that there is no spatial biases in the simulated heads relative to the measured heads.

Histograms of weighted residuals are sometimes used to determine whether there is a systematic bias in the calibration. Ideally, if the calibration lacks bias towards either overestimating or underestimating the heads, the weighted residuals will be normally distributed around zero. The histogram of weighted residuals from the tuffs and alluvium in Frenchman Flat shows that these residuals are approximately normally distributed around zero ([Figure 5-12](#)). The inclusion of residuals from the LCA introduces a negative bias in the residuals because of the relatively large negative residuals at Wells WW-C and WW-C1.

[Table 5-4](#) shows the metrics that characterize the goodness of fit associated with the calibration of the BASE-USGSD flow model. The table lists the mean-weighted error, maximum and minimum weighted residuals, the error variances and standard deviations, and the contributions to the objective function associated with water-level and flux target data in each of the models. The negative

mean-weighted residual calculated for the water levels in the BASE-USGSD flow model (-0.659 m) reflects the relatively large negative residuals associated with Wells WW-C and WW-C1. As indicated by [Figure 5-12](#), when only weighted residuals from the non-LCA wells are considered, the weighted residuals are approximately normally distributed around zero.

Table 5-4
Summary Calibration Statistics for the BASE-USGSD Model

MODEL	Calibration Data	Number of Data Observations	Mean-Weighted Error	Maximum Weighted Residual	Minimum Weighted Residual	Variance (m ² or kg ² /s ²)	Error Standard Deviation (m or kg/s)	Objective Function
BASE-USGSD	Well	30	-0.659	1.85	-8.24	4.50	2.12	134.8
	Flux	4	0.889	14.1	-9.57	74.4	8.63	297.7

Figure 5-9
Groundwater Fluxes Simulated by the UGTA Regional Model and the BASE-USGSD Flow Model

Figure 5-10
Observed Versus Simulated Well Head - BASE-USGSD Flow Model

Figure 5-11
Spatial Distribution of Weighted Residuals for the BASE-USGSD Model

Figure 5-12
Residual Histogram BASE-USGSD Flow Model

5.5.4 Estimated Hydraulic Parameters

The estimated hydraulic parameters in the model calibration include both the permeabilities of the HSUs in the model, as well as the permeability modification (f_{perm}) factors associated with the faults in the model. [Table 5-5](#) lists the reference permeabilities and f_{perm} factors estimated from the calibration of the BASE-USGSD flow model. The permeabilities of the HSUs estimated from calibration of the BASE-USGSD flow model are shown as a function of depth and compared against permeability data from the Frenchman Flat and the NTS investigation area in [Figures 5-13](#) through [5-17](#).

The estimated permeabilities of the AA and OAA HSUs in the BASE-USGSD flow model are compared to permeability measured in Frenchman Flat and in the general vicinity of the NTS in [Figure 5-13](#). The data for the NTS area include stream channel, floodplain, alluvial fan, and playa deposits from Yucca Mountain, the Amargosa Desert, and basins north of the NTS, as well as from Yucca Flat. The data from Frenchman Flat include data from the alluvium at Well ER-5-3 #3 near the northern testing area; Wells RNM-1, RNM-2, RNM-2s and ER-5-4 near the central testing area; and

Well WW-5A, WW-5B and WW-5C slightly to the south of the central testing area. The estimated permeabilities are at the low end of the range measured within NTS and Frenchman Flat Areas. The lower permeability estimated for the OAA compared to the AA is reasonable given the greater density and more pervasive zeolitization of the OAA (BN, 2005a). The permeabilities of the playa deposits (PCU1L, PCU1U, and PCU2T) embedded in the alluvium are assumed to be comparable to the permeability of the alluvium as a whole ([Table 5-5](#)). This result may be due to the very low sensitivity of the model calibration to the permeability of these units (see [Section 7.0](#)). The fine-grained nature of the playa deposits suggests that the permeability of these units could be much lower than the alluvium. However, there are no appropriate datasets against which to compare the estimated permeabilities of these deeply buried playa sediments in Frenchman Flat, because most of the known playa sediments that could serve as analogs are at land surface and act as groundwater discharge areas.

Volcanic rocks that are generally considered to be aquifers in Frenchman Flat include welded tuffs (TSA and TM-WTA), vitric nonwelded tuffs (TM-LVTA and LVTA), and basaltic lava flows (BLFA). Flow through the welded tuffs and basalts is probably through fractures, whereas flow through the vitric, nonwelded tuffs is probably through the matrix pores. The model permeabilities of these HSUs are compared to NTS data for welded tuffs, nonwelded tuffs, and lavas taken primarily from Yucca Mountain and Pahute Mesa, and to data measured in the Frenchman Flat area at Wells WW-4, WW-4a and ER-5-3 ([Figure 5-16](#)). A comparison with the data indicates that the model permeability values for the Timber Mountain tuffs (TM-WTA and TM-LVTA) are in good agreement with the data from these HSUs in Frenchman Flat. The permeability values for the BLFA and the TSA are at the low end of the observed range. The model permeability for the LVTA is near the middle of the data. The scatter in the data could be related to the diverse rock types, test configurations, interpretation, and structural settings associated with the data. As stated in [Section 3.6.1](#), similar basalt flows in the NTS region tends to have little connected fracturing, suggesting that the permeability for these units will be low.

The calibrated permeability of HSUs that are considered to be confining units in Frenchman Flat are compared to the permeability measured on tuffs from the Yucca Mountain area, other older tuffs at federal facilities north of the NTS ([Figure 5-15](#)), and to data from the LTCU at Well ER-5-4 #2. The test at ER-5-4 #2 straddled a fracture zone in the LTCU and was more permeable than the LTCU as a

whole. The model permeability of the LTCU, UTCU, and VCU are at, or lower than, the low end of the data range. The calibration targets were insensitive to the permeability of the UTCU (see [Section 7.0](#) for a complete description of parameter sensitivity), so this unit was poorly constrained during parameter optimization. The model permeability of the WCU is higher than the estimates of the other confining units and falls in the middle the observed range. The higher permeability used in the model for the WCU compared to other confining units may be due to the presence of numerous lava and breccia flows in this HSU in the western part of the model, which could make the WCU more conductive than other HSUs that are also classified as confining units (BN, 2005a, p. 4-19). In view of its diverse assemblage of rock types, it may be reasonable that the permeability of the WCU is intermediate between that of aquifers and true confining units.

The LCCU at the bottom of the model was removed to reduce the model size and because it is generally considered to form the hydraulic “basement.” Consequently, the UCCU is the only clastic confining unit in the model. Its model permeability is compared to permeability data for the UCCU from the Eleana Range and data for the LCCU from northwest Yucca Flat in [Figure 5-17](#). The model permeability used for the UCCU is in good agreement with the data.

The estimated permeabilities of the LCA and LCA3 HSUs are compared to permeability data for the carbonate aquifer in [Figure 5-14](#). The data include measurements both on and adjacent to the NTS and data from the vicinity of Frenchman Flat at Wells WW-C, WW-C1, TW-3, and ER-5-3 #2. The estimated permeabilities for both the LCA and LCA3 are in good agreement with the data. The relation between the LCA and LCA3 is counter to the relation suggested by Winograd and Thordarson (1975), who considered the upper plates of thrust faults in the LCA (that is, the LCA3) to be generally more broken (and, hence, more permeable), than the LCA as a whole. However, recent LCA hydraulic testing in southern Yucca Flat did not confirm Winograd and Thordarson’s postulated relationship between LCA and LCA3, as Wells ER-6-1 and ER-6-2 (open to the LCA and LCA3, respectively) both have high permeabilities (SNJV, 2005b and c).

Finally, estimated $fperm$ factors for each of the faults in the model are given in [Table 5-5](#). An $fperm$ factor greater than 1 means that permeability within the fault is increased relative to the rocks through which it passes, whereas an $fperm$ factor less than 1 means that permeability within the fault is reduced. An $fperm$ factor of 1 means that permeability within the fault is unchanged relative to the host rock.

As [Table 5-5](#) shows, the estimated $fperm$ factors in the BASE-USGSD flow model span more than seven orders of magnitude and included values both considerably greater than and considerably less than 1. The lowest $fperm$ factors were estimated for faults associated with the CP Hogback in the northwest part of the model (faults 11, 12, and 14-16) and for the Cane Spring fault (fault 3), which separates the CP basin from Frenchman Flat basin. Conversely, faults associated with the Rock Valley fault system (faults 21, 33, 34, 57, and 58) and faults 17 and 39 had estimated $fperm$ factors that indicated these faults were significant conduits for groundwater ([Table 5-5](#)). Unlike the faults associated with the Rock Valley fault system, the southern terminations of faults in Yucca Flat in the northern part of the model domain (faults 2, 22-25, and 27-29) were not estimated to be conductive relative to the surrounding host rock. The short faults near the central testing area (faults 35-37, 40-45, and 48-56) were estimated to have $fperm$ factors of about 1, indicating they will not serve as preferential pathways for radionuclide transport in this model. Of the faults in this group, only fault 38 had an $fperm$ value (5.0) that indicated it could preferentially transmit groundwater.

Except for fault 60 ($fperm = 1.45$) and fault 72 ($fperm = 1.39$), the southwest-trending faults in LCA in the southernmost part of the model (faults 59 to 73) had $fperm$ values equal to or less than 1, suggesting these faults would not be significant pathway for groundwater leaving Frenchman Flat. The relative sensitivity of the model calibration to individual $fperm$ factors is discussed in [Section 7.0](#).

The final permeabilities in the BASE-USGSD flow model depend on the values estimated for the reference permeability of the individual HSUs; the assumed depth-decay coefficients applied to the HSUs ([Table 3-6](#)); and the permeability changes imposed by the presence of the faults, as implemented through the $fperm$ factors ([Table 5-5](#)). [Figure 5-18](#) shows the calibrated permeability distribution at the water-table surface, and [Figures 5-19](#) and [5-20](#) show west-east cross sections of calibrated permeability values at the central and northern testing areas, respectively. The combined

effects of the spatial distribution of HSUs, the depth decay in permeability, and the overprint of permeability changes associated with faults serve to create a complex distribution of permeability within the BASE-USGSD flow model. The distribution of permeability in plan view, [Figure 5-18](#), shows that the central part of the Frenchman Flat basin is surrounded on the north, east, and south by a zone of low permeability that corresponds to the confining units that line the deepest parts of the basin and rise up along the flanks of the basin to intersect the water table ([Figures 5-19](#) and [5-20](#)). This zone of lower-permeability rock separates the basin hydraulically from the much more permeable LCA that lies outside of and beneath the Frenchman Flat basin. The higher permeability estimated for the WCU compared to the other confining units ([Figure 5-15](#)) allows a significantly stronger hydraulic connection between the central part of Frenchman Flat and the CP basin and Wahmonie Hills to the west ([Figure 5-19](#)).

An interval of high permeability lies between the base of the alluvium and the deep tuff confining units that line the Frenchman Flat basin ([Figures 5-19](#) and [5-20](#)). This high-permeability interval is comprised of volcanic aquifers (primarily the TM-WTA, TM-LVTA, and TSA) that have both higher reference permeabilities than the tuff confining units ([Table 5-5](#)) and lower rates of depth decay than the surrounding alluvium ([Table 3-6](#)). Near the central testing area ([Figure 5-19](#)) this high-permeability zone rises on the flanks of the basin toward the Wahmonie Hills before pinching out. Near the northern testing area ([Figure 5-20](#)), this high-permeability interval lies below the older alluvium (OAA). In plan view ([Figure 5-18](#)), this interval of high permeability manifests itself as an arcuate band of higher permeability ($k = 10^{-11} \text{ m}^2$) that wraps around the northern part of the basin and connects areas of higher hydraulic head in the CP basin to parts of the northern testing area in Frenchman Flat.

Table 5-5
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers for the BASE-USGSD Model
 (Page 1 of 3)

HSU Permeability at Ground Surface - log k_0 (m ²)	
AA	-11.30
PCU	-14.50
BLFA	-12.00
OAA	-12.00
PCU1L	-11.00
PCU1U	-11.00
TM-WTA	-9.15
TM-LVTA	-9.20
UTCU	-14.00
TSA	-11.00
LVTA	-10.50
LTCU	-13.50
WCU	-11.88
VCU	-13.60
LCA3	-11.00
UCCU	-13.50
LCA	-10.40
Fault Permeability Multiplier	
1	0.3
2	0.5
3	1.8E-04
4	1.0
5	0.5
6	1.0
7	1.0
8	1.1
9	1.0
10	0.3
11	1.0E-05
12	1.0E-05
13	1.0
14	1.0E-05
15	1.0E-05
16	5.0E-04
17	18.0
18	15.0
19	1.0
20	1.0
21 ^a	67.8
22	1.0
23	1.0

Table 5-5
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers for the BASE-USGSD Model
 (Page 2 of 3)

Fault Permeability Multiplier	
24	1.0
25	1.0
26	1.0
27	1.0
28	1.0
29	1.0
30	1.0
31	1.0
32	1.0
33 ^a	150.9
34 ^a	155.2
35	1.0
36	1.0
37	1.0
38	5.0
39	34.0
40	1.0
41	1.0
42	1.0
43	1.0
44	1.0
45	1.0
46	10.0
47	10.0
48	1.0
49	1.0
50	1.0
51	1.0
52	1.0
53	1.0
54	1.0
55	1.0
56	1.0
57 ^a	31.05
58 ^a	108.39
59	1.0
60	1.45
61	0.45
62	0.82
63	0.84
64	0.74
65	0.93

Table 5-5
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers for the BASE-USGSD Model
(Page 3 of 3)

Fault Permeability Multiplier	
66	0.88
67	0.92
68	0.98
69	0.35
70	1.0
71	1.0
72	1.39
73	1.0
74	1.0
75 ^b	1.8E+04
76	1.0
78	1.0

Note: Model used the USGSD recharge data and the associated boundary heads and flows from the UGTA regional model.

^a The Rock Valley fault system (faults 21, 33, 34, 57, and 58) have different properties only through the LCA. These faults are neutral throughout all other HSUs.

^b Fault 75 is the northern part of the Cane Spring fault (fault 3).

Figure 5-13
Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of AA

Figure 5-14
Calibrated Permeability in the BASE-USGSD Alternative Versus Measured Permeability of the LCA

Figure 5-15

Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of Confining HSUs

Figure 5-16

Calibrated Permeability in the BASE-USGSD Alternative Versus Measured Permeability of Volcanic Aquifers

Figure 5-17
Calibrated Permeability in the BASE-USGSD Model Versus Measured Permeability of the CCU

Figure 5-18
Calibrated Intrinsic Permeability at the Water Table for the BASE-USGSD Model

Figure 5-20
West-East Cross Section of Calibrated Intrinsic Permeability at the Northern Testing Area for the BASE-USGSD Model

5.5.5 Estimated Groundwater Flow Paths

To investigate the flow paths that radionuclides introduced by underground nuclear tests might follow, particles were placed either at the location of the CAMBRIC test or near the water table beneath the sites of each of the nine remaining underground nuclear tests in Frenchman Flat that were conducted in the vadose zone (see [Table 1-1](#)). [Figure 5-21](#) shows the trajectory of particles initially located near test locations in the northern and central testing areas. The particle tracks are colored by the location of the particle in the flow system as a function of HSU. Because these calculations are not intended to portray rates of potential radionuclide movement, an issue that will be addressed in detail in the transport modeling phase of the Frenchman Flat CAU study, some simplifying assumptions concerning transport behavior were made. For instance, effective transport porosity was set to a uniform value (0.01) in each of the HSUs rather than allow it to vary among the HSUs, and no diffusion or dispersion was allowed. In spite of these simplifications, the calculated particle tracks are useful for illustrating the directions of groundwater movement away from the testing areas.

Near the northern testing area, particle movement reflects the complex distribution of permeabilities in northern Frenchman Flat illustrated in [Figure 5-18](#) through [5-20](#). South of the detachment fault (fault 36), groundwater movement is southward out of the northern testing area through the OAA and BLFA. Eventually, groundwater moving beneath the northern testing area moves into the AA and travels toward the southeast, where it moves laterally through the VCU and enters the LCA along the Rock Valley fault system.

The trajectory of particles starting near the water table beneath the PIN STRIPE test is eastward within the TSA and LVTA ([Figure 5-21](#)). As shown in [Figure 5-18](#), the TSA and LVTA create an arcuate band of higher permeability where they intersect the water table along the northern flank of the Frenchman Flat basin. This continuous band of higher permeability creates a strong hydraulic connection in the model between the higher hydraulic heads in the CP basin to the west and locations beneath the PIN STRIPE test in the northern testing area. The higher hydraulic heads adjacent to the western part of the CP basin ([Figures 5-4](#) and [5-5](#)) cause groundwater to flow eastward through the LTCU toward a major fault in the Rock Valley fault system (fault 33) and enter the LCA. This trajectory, although unanticipated, is nonetheless consistent with the distribution of HSU and permeabilities within the BASE-USGSD flow model.

Figure 5-21
Particle Tracks Starting Near the Underground Nuclear Tests -
BASE-USGSD Model

In the central testing area of Frenchman Flat, groundwater flow is substantially less complex than in the northern testing area. The movement of particles near the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area will be through the alluvium toward the southeast. Eventually, these particles will encounter the Rock Valley fault system and exit the flow system along the southern part of the western boundary of the model.

5.6 Model Limitations

The Frenchman Flat CAU flow model covers an area of 570 km² and has a saturated thickness of nearly 5 km, for a total volume of about 2,850 km³. A total of 34 calibration targets of head and flux were used in the calibration. Thus, the overall density of the data versus the size of the model suggests that the calibration data are sparse. Additionally, wells within the Frenchman Flat basin are generally aligned along a north-south trend, so that head gradients are not as well constrained in the lateral direction, which some conceptual models hold is the predominant flow direction within the alluvium ([Section 2.3.1.2](#)). Hydraulic head data are also clustered in certain parts of the model domain, such as the ER-5-3 and ER-5-4 well clusters, with other parts having little or no data to allow rigorous evaluation of calibrated model parameters and results in those areas.

In addition to the uncertainty in heads and gradients throughout the Frenchman Flat basin, considerable uncertainty exists concerning heads and fluxes along the boundaries of the model due to inaccuracies and uncertainties in the regional models from which these boundary conditions were established. However, although these uncertainties influence flow directions and rates in the LCA within the model area, they are not expected to significantly influence flow directions or rates in the alluvium and tuffs because of the relative hydraulic isolation of the Frenchman Flat basin from the surrounding LCA due to thick tuff confining units that separate the basin-fill HSUs from the regional groundwater system.

The number of adjustable parameters in the model is relatively large (more than 100) compared to the number of target observations available to calibrate the model due to the hydrogeologic detail in the model. The large number of faults and HSUs in the model make it difficult to evaluate the values of individual parameters from the data alone without some subjective judgment as to which parameters can be appropriately grouped, or which parameters should be optimized and which should be held

fixed during calibration. However, although the large number of parameters poses challenges, it also means that the model has the flexibility to explore the effects of these geologic features on groundwater flow patterns through sensitivity analysis. This flexibility would not exist if the model had not included these features during its construction.

The model assumes that depth below land surface and the geometry of the HSUs and faults determine the distribution of permeability within the models. This deterministic approach thus ignores finer-scale heterogeneity that arises from random or stochastic processes during deposition of the alluvium and tuff and their subsequent alteration or faulting, or the effects of lumping an assemblage of volcanic units with different degrees of welding and fracturing into a single HSU. This last limitation makes it impossible to replicate features of the flow system (like the high hydraulic heads in the LTCU at ER-5-4 #2) with the current model without introducing additional complexity to an already geometrically complex model.

The CAU flow model was calibrated to estimated steady-state conditions and does not attempt to consider the transient conditions associated with either long-term climate change in the NTS area, or the effects of water withdrawals from the Frenchman Flat basin associated with either water-supply wells at the NTS or with the CAMBRIC RNM experiment. The higher heads in the alluvium in Frenchman Flat relative to the LCA could reflect the slow drainage of the alluvium through the tuff confining units and the relatively more rapid equilibration of water levels in the regional LCA following the transition from pluvial to arid conditions approximately 10,000 years ago. However, it was decided not to pursue this conceptual model through numerical modeling because the necessary data are qualitative at best, and it was evident that these models would require the presence of an extremely low-permeability confining unit separating the alluvium from the LCA for this conceptual model to be valid. The use of a steady-state flow model allowed consideration of more direct hydraulic connections between the alluvium and the LCA and thus was deemed more suitable for examining the extent of contaminant transport from underground nuclear tests.

In contrast, the use of a transient flow model to incorporate data on water withdrawals for water supply and the CAMBRIC RNM experiment into the calibration would have been highly desirable because the hydraulic stresses induced during pumping can be much better characterized than the natural stresses imposed by the regional fluxes. However, incomplete pumping histories at the water

supply wells and the absence of measurements of hydraulic head at suitable locations during the radionuclide migration experiment (SNJV, 2004d) made consideration of transient conditions impractical. The model was able to consider some of the information provided by MWATs done in Frenchman Flat by using the hydraulic conductivities provided by these tests to guide the adjustment of model parameters during calibration. This partially compensated for the inability of the model to use the water pumping data in the calibration.

Significant uncertainty exists in many aspects of the flow models described in this report, and this uncertainty affects the trajectories of particles leaving the testing areas over tens of thousands of years. However, because particle travel times were not considered in this analysis, it is expected that some of the differences exhibited in the long-term trajectories due to parameter and boundary conditions uncertainty may not be important over shorter time scales important to contaminant transport. Although it is not possible to demonstrate this in the absence of time-dependent particle tracking calculations, this possibility will be explored in the Frenchman Flat Phase II Transport Model that builds upon the results of the present study.

Although uncertain, the model calibration described in this section is subject to extensive sensitivity and uncertainty analyses. [Figure 6.0](#) examines the effects of parameter changes and conceptual model uncertainty on the model calibration and on groundwater flow directions near the testing areas. The calibrated BASE-USGSD model fits the data well, and as discussed in [Section 5.5.3](#), which compared calibrated permeabilities to the data, the model does so with parameters that are reasonable for their respective HSU type. Additionally, simulated heads in the AA matched the data with a high degree of accuracy and reflect the horizontal gradient and vertical gradient within the AA very well.

5.7 Summary

A steady-state groundwater flow model was created for Frenchman Flat CAU using the BASE HFM in conjunction with lateral boundary heads and fluxes and water-table recharge based on a water-balance model of infiltration and recharge model (designated the USGSD model) originally developed for the regional model area. The boundary conditions for the resulting Frenchman Flat flow model (designated the BASE-USGSD flow model) were taken from the regional model by interpolating hydraulic heads produced with the regional model onto the lateral boundaries of the BASE-USGSD model. The net groundwater fluxes calculated by the regional model along the planes

coinciding with the lateral boundaries of the BASE-USGSD flow model were calculated and used along with 30 hydraulic head measurements to calibrate the model. Measurement uncertainty and calibration weights were determined for the hydraulic head measurements by considering uncertainty in different aspects of the head measurements such as groundwater surface elevation, depth to groundwater, and borehole deviations from vertical. Permeability within the model varied among the HSUs and as a function both of depth and of the permeability modification factors that were applied to the faults during calibration.

Calibration of the BASE-USGSD flow model was accomplished through a combination of automated parameter estimation and manual adjustments to the model parameters that were guided by sensitivity analyses. Automated parameter estimation was successful in matching boundary fluxes but was less successful in matching hydraulic heads within the flow model area. Typically, manual adjustments to the model parameters were required to obtain a set of simulated heads within the uncertainty of the measured hydraulic heads. Simulated heads generally matched the measured heads to within the uncertainty limits estimated for the measurements except at wells in the LCA near the northern boundary of the model.

The simulated heads in the AA matched the head data with a high degree of accuracy and correctly simulated the near-absence of both lateral and vertical gradients within the AA indicated by the data. A comparison of measured heads at the ER-5-3 well complex with a vertical profile of simulated heads produced with the BASE-USGSD flow model indicated that both measured and modeled vertical head gradients are virtually non-existent between the alluvium and the underlying volcanic aquifers near the ER-5-3 well complex. Therefore, there seems to be very little potential for downward flow in the alluvium, despite the overall drop in heads between the alluvium and the carbonate aquifer. The data and the model results indicated that most of the head loss between the alluvium and the carbonate aquifer occurs across the thick confining units, like the LTCU, that are present beneath the northern testing area. A similar comparison between measured and simulated heads at the ER-5-4 well complex indicates that simulated heads in the BASE-USGSD model again accurately depict the near-constant heads in the alluvium between the water table at 734 m and sea level. Again, this would suggest that there is very little downward gradient through the alluvium that would create downward flow. Simulated heads show an almost 1-m increase between the lower alluvium and the TM-WTA, creating a pressure barrier that would also prevent groundwater

movement into the LCA. Although data do not exist to evaluate the presence of a pressure barrier in the TM-WTA, measured hydraulic heads of more than 754 m in the LTCU at Well ER-5-4 #2 indicate that the concept of a pressure barrier in the central part of Frenchman Flat is feasible. The results of the BASE-USGSD flow model indicate that this pressure barrier could arise when high-permeability units like the TM-WTA (or similar lithologies embedded within the thick LTCU) act as confined aquifers and connect the deep parts of the Frenchman Flat basin with areas of higher head to the west.

The permeabilities estimated during calibration of the BASE-USGSD flow model were compared to the data from the general NTS area and from Frenchman Flat. The match between the estimated and measured permeabilities is good in most cases. For some HSUs, such as the AA and the LTCU, the estimated permeabilities were toward the lower end of the observed data range. The effects of increasing the permeability in the AA to bring it into better agreement with the data would be to increase the rate of groundwater movement in the model if the horizontal head gradient were to remain the same. Alternative calibrations with improved matches to AA data are presented in the conceptual model uncertainty analysis (see [Section 6.0](#)).

The final permeability field associated with the calibrated models reflects differences among the permeabilities estimated for the different HSUs, the effect of the decay in permeability with increasing depth, and the effects of permeability changes associated with faults. The permeability fields that result from the superposition of these effects can be very complex in some areas, particularly in the northern testing area, where groundwater flow bifurcates, with flow north of a detachment fault flowing east or northeast, and groundwater to the south of the detachment fault flowing predominantly southward. In the central testing area, particle trajectories are toward the southeast. Eventually, all particles initially located beneath the testing areas eventually exit the model through the Rock Valley fault system in the southwest corner of the model.

6.0 CONCEPTUAL MODEL UNCERTAINTY ANALYSES

The CAIP addendum to the CAIP (NNSA/NV, 2001) states that the uncertainty analysis for the Frenchman Flat CAU will include “... alternative hydrostatigraphic models, boundary flux uncertainty, and parameter uncertainty for both flow and transport parameters ... Groundwater flow and transport model simulations with the range of parameter values will yield an assessment of the prediction uncertainty due to parameter uncertainty.” The conceptual model uncertainty includes the types of uncertainty specified in the CAIP addendum and a model calibrated with constant permeability with depth below ground surface in some of the basin-fill aquifers. For convenience, these analyses are referred to as analyses of conceptual model uncertainty and the results are presented separate from parameter sensitivity analysis ([Section 7.0](#)). For additional perspective on the interpretation and applicability of these analyses, brief background information is provided on the definitions of uncertainty used in this section and the role of these analyses in the overall modeling strategy.

6.1 Background

Recent applications of flow and transport modeling associated with complex environmental systems have recognized the importance of quantifying uncertainty with respect to input parameters, and model responses specific to the context of individual decision problems. The different types of uncertainty are variability (irreducible uncertainty) and the multiple components of knowledge uncertainty (parameter, model, structural and/or scenario uncertainty) (Morgan and Henrion, 1990; EPA, 1997; Cullen and Frey, 1999; Vose, 2000). The Nuclear Regulatory Commission has since 1997 sponsored a series of studies and workshops specifically to assess the application of groundwater modeling to support predictions required for programmatic applications. The results of these workshops and studies are an increasing recognition of the importance of alternative conceptual models in assessments of model uncertainty (Neuman and Wierenga, 2003). Iterative cycles of model development are proposed that include data gathering, development of alternative conceptual models, implementation of the conceptual model(s) as numerical models, and model simulations. The results

of the simulations are reviewed quantitatively using sensitivity and uncertainty analysis to identify critical modeling parameters/assumptions and assess the need for continued iteration. This section on uncertainty is intended to fulfill part of a critical and continuing role of model evaluation.

The approaches and techniques used for uncertainty and sensitivity analysis and parameter estimation continue to evolve rapidly (see, for example, ISCMEM, 2003) as do the definitions of what constitutes sensitivity and uncertainty analysis. Helton and Davis (2000) describe sample-based uncertainty and sensitivity analysis as an evaluation of a mapping from uncertain analysis inputs to analysis (model) results where the model results are represented by a vector function (Helton and Davis 2000; p. 101):

$$\mathbf{y} = [y_1, y_2, \dots, y_{ny}] \quad (6-1)$$

and input is represented by a vector

$$\mathbf{x} = [x_1, x_2, \dots, x_{nx}] \quad (6-2)$$

where nx and ny are the dimensions of $\mathbf{x}$ and $\mathbf{y}$, and each value of $\mathbf{x}$ produces a corresponding value of $\mathbf{y}(\mathbf{x})$. They define uncertainty as the uncertainty in $\mathbf{y}(\mathbf{x})$ given the uncertainty in $\mathbf{x}$, and sensitivity as the relative importance of individual elements of $\mathbf{x}$ with respect to the uncertainty in $\mathbf{y}(\mathbf{x})$. Saltelli (2000) in contrast uses a much broader definition of sensitivity analysis as the relationships between information flowing in and out of a model, a definition that overlaps with most definitions of uncertainty.

Uncertainty analyses in this section are evaluated in the context of the use of flow models to achieve the UGTA corrective action strategy specific to Frenchman Flat CAU. The overall flow and transport modeling strategy is to establish the horizontal and vertical extent and the uncertainty in contaminant migration for each CAU. The strategy is implemented through modeling phases described in the FFACO (1996), and in the CAIP (DOE/NV, 1999) and addendum to the CAIP (NNSA/NV, 2001), and includes completion, for Frenchman Flat, of a groundwater flow model, a contaminant transport model, and a total-system model. A primary goal of the flow model phase is to examine a range of permissible fits to the calibration data recognizing the non-unique nature of the multiple conceptual model and parameter sets (the *equifinality* problem of Beven and Freer, 2001).

The primary goal of the assessment of the conceptual model uncertainty is to define the uncertainty of the flow model responses associated with alternative HFM uncertainty, boundary condition uncertainty, and HSU or fault parameter uncertainty, and to provide guidance on how to include or represent that uncertainty in the transport simulation. The mechanisms to express model response uncertainty, are identified in the CAIP and include variability in simulating the groundwater flow paths and fluxes (DOE/NV, 1999). The approach followed is *not* to attempt to define all potential variations in flow paths and fluxes, but instead to establish the range of variation using multiple realistic combinations of alternative conceptual models and parameter sets. This assessment of model response uncertainty is described as conceptual model uncertainty following the usage of Neuman and Wierenga (2003). It could also be classified under the broad category of sensitivity analysis using the definition of Saltelli (2000).

6.2 Introduction

For the Frenchman Flat CAU flow model, four areas of uncertainty are considered:

- **HFM uncertainty:** *A Hydrostratigraphic Framework Model and Alternatives for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Clark, Lincoln and Nye Counties, Nevada* (BN, 2005a) documents four alternative HFMs along with the BASE HFM. These alternative HFMs were each calibrated with the USGSD boundary conditions to address HFM uncertainty.
- **HSU and fault parameter uncertainty:** Analysis of HSU and fault parameter uncertainty was performed using discrete uncertainty analysis. This approach, which relies on the analysts' experience with the flow model, is used to evaluate likely scenarios that would lead to longer-range contaminant transport. The discrete uncertainty analysis allows for the evaluation of the extreme values of select flow model parameters.
- **Boundary conditions uncertainty:** Boundary heads, boundary flows, and recharge distributions used for flow model calibration are derived from regional-scale models (see [Section 3.4](#) for overview). Over the entire NTS area, total recharge is significantly different among the recharge models (see [Section 2.2](#)), leading to considerably different modeled boundary heads and boundary flows in the Frenchman Flat area. While the total volume of recharge on the Frenchman Flat area is small, leading to limited impact on calibrated parameters, boundary conditions uncertainty for the Frenchman Flat CAU flow model is dominated by boundary heads derived from the various regional model calibrations. Alternative recharge distributions, boundary heads, and boundary flows were used to calibrate two HFMs to examine changes in flow paths near underground nuclear test locations. Both the UGTA regional model and the DVRFS model were used for this evaluation. Two sets of

recharge, boundary heads, and boundary flows are used from the UGTA regional model recalibrations, and one set of recharge and boundary heads and boundary flows are used from the DVRFS model. Additional uncertainty analysis was also completed to understand the impact of boundary head adjustment methodology on the flow paths of the BASE-USGSD model.

- **Implementation of Permeability Depth Decay:** Rates of permeability depth decay in the Frenchman Flat CAU model area are poorly constrained by site-specific data; therefore, an alternative model calibration was completed to examine the effect of removing depth decay from two of the basin-fill HSUs (AA and OAA) on the modeled flow fields.

6.3 HFM Uncertainty Analysis

The HFM report (BN, 2005a) lists alternatives, which are prioritized into A, B, C, and D groups. The priority A alternatives are those that are included in the BASE HFM. The BASE model calibration results are presented in [Section 5.0](#). The priority B alternatives represent permissive alternative interpretations of the structural and stratigraphic data for Frenchman Flat where these alternatives were judged to have a sufficiently significant impact on groundwater flow to merit development of a separate HFM. The priority B alternative HFMs are summarized in [Section 2.3.3](#), and model calibration results are described here. [Table 6-1](#) lists the priority C alternatives and a brief comment on how each was addressed. The priority D alternatives are judged to have either an insignificant effect on groundwater flow or are insufficiently supported by geologic and structural data to warrant evaluation as alternative models (BN, 2005a).

6.3.1 Alternative HFM Calibration Approach

The configuration of HSUs is somewhat different among the alternative HFMs, but the same set of HSUs exist in all HFMs. Thus, the approach used to calibrate the alternative HFMs was to first use the calibrated parameter set from the BASE-USGSD model. The model-calculated water levels and fluxes were then compared with their target values, and parameter changes were carried out or the model was accepted in its existing form. Sensitivity analysis results were utilized in developing revised parameters sets, if deemed necessary.

The use of the parameters estimated for the calibrated BASE-USGSD flow model in the BLFA and DETA alternative HFMs produced boundary fluxes and hydraulic heads in these models that were almost identical to the values already presented for the BASE-USGSD model at the target locations.

Table 6-1
List of Priority C Alternative Scenarios for the Frenchman Flat
3-D Hydrostratigraphic Model

Alternative (as described by BN, 2005a)	Comment/Discussion
Subdivide the volcaniclastic confining unit (VCU) in the southern portion of the model	The VCU is dominated by fine-grained clastic rocks and zeolitic tuff. However, lenses of gravel and freshwater carbonate beds have been observed in southern Frenchman Flat where the VCU outcrops. Observation of the outcrop exposures of the VCU and assessments of basin-fill carbonate and gravel deposits show that these deposits are generally of limited thickness and lateral extent, and probably are not a significant component of the VCU. Little is known about the VCU beneath the Frenchman Flat basin, where the VCU is overlain by a thick LTCU. Because the VCU is overlain by a thick LTCU, it is not likely that even large variations of the VCU properties under the Frenchman Flat basin will be of any significance to the resulting flow fields. However, the southern part of the VCU could be examined in further detail by varying model parameters to approximate the occurrence of aquifer-like rocks within the VCU. This was not necessary for calibration of the flow model, suggesting that changes to the VCU flow parameters are unnecessary for representing the flow field within the data constraints.
Add width to faults	The faults are represented in the model using the set of nodes around them. The node spacing depends on the level of discretization and the fault location. In general, these fault nodes are discretized using a finer mesh near the top, and the node spacing increases towards the bottom of the model. This fault representation is conceptual and does not reflect any attempt to model the fault widths. This representation is not likely to have any effect on the flow model results but could have significant effects on the transport model results in terms of travel times required to go through (or across) some of the faults. This could be dealt with during the transport model evaluation by assigning appropriate effective porosity values to the fault nodes that will reflect different fault width values. For example, if a narrow fault width is evaluated, a small effective porosity value can be assigned to the fault nodes.
Represent faults in model as multiple planes	This is similar to the previous alternative.
Vary fault dips for basin and range faults (from the 75 degrees used)	This alternative cannot be reasonably handled by the flow model because the fault locations have a significant effect on the node locations and spacing in the model mesh. However, it can be evaluated in a simplified total system model-context where the flow velocities and directions are obtained from the flow model, and different fault dip angle can be investigated using different fault lengths or distance to fault interception within different HSUs.

As a consequence, these two alternative HFMs did not require further calibration. The similar heads and fluxes produced with the BLFA-USGSD and DETA-USGSD alternatives and the BASE-USGSD models at the target locations do not necessarily mean that the models are identical, but rather that there were no data from locations that could reveal the differences in hydrologic behavior among the models. Pertinent results from the BLFA-USGSD and DETA-USGSD alternatives, and a description of the calibration process and results for the DISP-USGSD and CPBA-USGSD alternatives, are

provided in the following four sections. Table 6-2 summarizes the model parameters used for the final calibration of each alternative HFM.

Table 6-2
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers
(Page 1 of 3)

	Hydrostratigraphic Framework Model				
	BASE	BLFA	DETA	CPBA	DISP
HSU Permeability at Ground Surface - log (k_0 in m^2)					
AA	-11.30	-11.30	-11.30	-11.15	-10.90
PCU	-14.50	-14.50	-14.50	-14.04	-14.50
BLFA	-12.00	-12.00	-12.00	-12.20	-12.00
OAA	-12.00	-12.00	-12.00	-12.16	-11.40
PCU1L	-11.00	-11.00	-11.00	-14.19	-10.00
PCU1U	-11.00	-11.00	-11.00	-14.19	-11.00
TM-WTA	-9.15	-9.15	-9.15	-10.10	-9.79
TM-LVTA	-9.20	-9.20	-9.20	-9.29	-9.30
UTCU	-14.00	-14.00	-14.00	-14.04	-14.00
TSA	-11.00	-11.00	-11.00	-9.00	-9.75
LVTA	-10.50	-10.50	-10.50	-9.29	-10.50
LTCU	-13.50	-13.50	-13.50	-15.50	-13.20
WCU	-11.88	-11.88	-11.88	-11.50	-11.88
VCU	-13.60	-13.60	-13.60	-13.25	-13.80
LCA3	-11.00	-11.00	-11.00	-11.12	-11.00
UCCU	-13.50	-13.50	-13.50	-14.26	-13.50
LCA	-10.40	-10.40	-10.40	-10.15	-10.35
Fault Permeability Multiplier					
1	0.3	0.3	0.3	1.0	0.2
2	0.5	0.5	0.5	5.0	0.5
3	1.8E-04	1.8E-04	1.8E-04	1.0E-05	4.0E-02
4	1.0	1.0	1.0	0.2	1.0
5	0.5	0.5	0.5	0.2	0.5
6	1.0	1.0	1.0	0.2	1.0
7	1.0	1.0	1.0	5.0	1.0
8	1.1	1.1	1.1	0.2	1.06
9	1.0	1.0	1.0	0.2	1.0
10	0.3	0.3	0.3	0.2	0.29
11	1.0E-05	1.0E-05	1.0E-05	1.0	1.0E-05
12	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05
13	1.0	1.0	1.0	0.2	1.0
14	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05
15	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05
16	5.0E-04	5.0E-04	5.0E-04	1.0	5.0E-04
17	18.0	18.0	18.0	75.0	21.0

Table 6-2
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers
 (Page 2 of 3)

	Hydrostratigraphic Framework Model				
	BASE	BLFA	DETA	CPBA	DISP
18	15.0	15.0	15.0	1.0	15.0
19	1.0	1.0	1.0	1.0	1.0
20	1.0	1.0	1.0	1.0	1.0
Fault Permeability Multiplier					
21 ^a	67.8	67.8	67.8	75.0	67.833
22	1.0	1.0	1.0	5.0	1.0
23	1.0	1.0	1.0	5.0	1.0
24	1.0	1.0	1.0	5.0	1.0
25	1.0	1.0	1.0	5.0	1.0
26	1.0	1.0	1.0	1.0	1.0
27	1.0	1.0	1.0	5.0	1.0
28	1.0	1.0	1.0	5.0	1.01
29	1.0	1.0	1.0	5.0	1.0
30	1.0	1.0	1.0	1.0	1.0
31	1.0	1.0	1.0	1.0	1.0
32	1.0	1.0	1.0	1.0	1.0
33 ^a	150.9	150.9	150.9	75.0	150.9
34 ^a	155.2	155.2	155.2	75.0	1.96E-03
35	1.0	1.0	1.0	0.1	1.0
36	1.0	1.0	1.0	0.1	1.0
37	1.0	1.0	1.0	0.1	0.99
38	5.0	5.0	5.0	0.1	5.0
39	34.0	34.0	34.0	75.0	94.11
40	1.0	1.0	1.0	0.1	0.1
41	1.0	1.0	1.0	0.1	0.1
42	1.0	1.0	1.0	0.1	0.1
43	1.0	1.0	1.0	0.1	0.1
44	1.0	1.0	1.0	0.1	0.1
45	1.0	1.0	1.0	0.1	0.1
46	10.0	10.0	10.0	1.0	70.0
47	10.0	10.0	10.0	1.0	50.0
48	1.0	1.0	1.0	0.1	0.1
49	1.0	1.0	1.0	0.1	0.1
50	1.0	1.0	1.0	0.1	0.1
51	1.0	1.0	1.0	0.1	0.1
52	1.0	1.0	1.0	0.1	0.1
53	1.0	1.0	1.0	0.1	0.1
54	1.0	1.0	1.0	0.1	0.1
55	1.0	1.0	1.0	0.1	0.1
56	1.0	1.0	1.0	0.1	0.1

Table 6-2
Summary of Calibrated Reference Permeability Values
and Fault Permeability Multipliers
(Page 3 of 3)

	Hydrostratigraphic Framework Model				
	BASE	BLFA	DETA	CPBA	DISP
57 ^a	31.05	31.05	31.05	75.00	15.50
58 ^a	108.39	108.39	108.39	75.00	108.39
59	1.0	1.0	1.0	0.9	1.5
Fault Permeability Multiplier					
60	1.45	1.45	1.45	0.90	1.5
61	0.45	0.45	0.45	0.90	0.45
62	0.82	0.82	0.82	0.90	1.5
63	0.84	0.84	0.84	0.90	0.84
64	0.74	0.74	0.74	0.90	0.74
65	0.93	0.93	0.93	0.90	0.93
66	0.88	0.88	0.88	0.90	1.5
67	0.92	0.92	0.92	0.90	0.92
68	0.98	1.0	1.0	0.9	1.5
69	0.35	0.35	0.35	0.90	0.35
70	1.0	1.0	1.0	0.9	1.0
71	1.0	1.0	1.0	0.9	1.0
72	1.39	1.39	1.39	0.90	1.39
73	1.0	1.0	1.0	0.9	1.5
74	1.0	1.0	1.0	1.0	1.0
75 ^b	1.8E+04	1.8E+04	1.8E+04	0.32	1.8E+04
76	1.0	1.0	1.0	1.0	1.0
78	1.0	1.0	1.0	1.0	1.0
79 ^c	--	--	--	--	114.11
80 ^d	--	--	--	--	6.47E-2

Notes: All listed models used the USGSD recharge data and the associated boundary heads and flows from the UGTA regional model.

^aThe Rock Valley fault system (faults 21, 33, 34, 57, and 58) have different properties only through the LCA. These faults are neutral throughout all other HSUs.

^bFault 75 is the northern part of the Cane Spring fault (fault 3).

^cFault 79 is only defined for the DISP HFM. It is the part of fault 34 that crosses volcanic HSUs.

^dFault 80 is also defined only for the DISP HFM. It is the part of fault 34 within the AA HSU.

6.3.2 Basalt Lava Flow Aquifer (BLFA) Flow Model Calibration

The BLFA HFM is very similar to the BASE HFM except that the basalt lava flow aquifer in northern Frenchman Flat is reinterpreted in the BLFA HFM as a single, more extensive flow rather than three smaller, isolated basalt flows as in the BASE HFM (Plate 2; BN, 2005a, Fig. 5-1). As stated previously, hydraulic heads and boundary fluxes at the target locations simulated with the BLFA-USGSD alternative were nearly identical to those from the BASE-USGSD model when the calibrated BASE-USGSD parameters were used. Figure 6-1 compares the heads produced with the BLFA-USGSD alternative with the measured heads and the modeled heads from the calibrated USGSD-BASE model.

Despite the nearly identical heads at the target locations in the BLFA-USGSD and BASE-USGSD flow models, it is possible that the changes in the configuration of the BLFA could affect local flow directions near the northern and central testing areas without producing significant changes in the simulated heads. To examine this possibility, groundwater flow directions in the testing areas were determined by placing particles beneath the test locations (or at the test location, in the case of the CAMBRIC test). In the northern testing area, particles trajectories in the BLFA-USGSD alternative (Figure 6-2) appear to be similar to those in the BASE-USGSD model (Figure 5-21), except that particles travel through the more extensive BLFA HSU rather than the OAA. In the central testing area, no discernible differences are evident in the particle trajectories associated with the BLFA-USGSD (Figure 6-2) and BASE-USGSD (Figure 5-21) flow models.

Figure 6-1
Observed Versus Simulated Well Head - BLFA-USGSD Alternative

Figure 6-2
Particle Tracks Starting Near the Underground Nuclear Tests
for the BLFA-USGSD Alternative

6.3.3 Detachment Fault (DETA) Alternative Flow Model Calibration

The DETA HFM is similar to the BASE HFM except that the detachment fault (fault 36 in [Figure D.1-1](#)) that offsets volcanic aquifers such as the TM-WTA near the northern edge of the Frenchman Flat basin is absent. To accommodate this change, the volcanic aquifers have been reinterpreted as having greater continuity and dipping more steeply into the basin ([Plate 2](#); BN, 2005a, Fig. 5-2). As with the BLFA-USGSD alternative, calibration of the DETA-USGSD alternative was achieved using the parameters estimated during calibration of the BASE-USGSD flow model. [Figure 6-3](#) shows that simulated heads at the target locations produced with the DETA-USGSD and BASE-USGSD flow models are essentially identical.

To determine whether groundwater flow directions near the testing areas were affected by the removal of the detachment fault, particles were placed near the test locations in the northern and central testing areas. In the northern testing area, a comparison of particle trajectories calculated with the DETA-USGSD flow model ([Figure 6-4](#)) and trajectories calculated with the BASE-USGSD flow model ([Figure 5-21](#)) shows that particle trajectories appear to be similar except that particles placed near the PIN STRIPE test initially follow more northerly trajectory. In the central testing area, no discernible differences exist between particle trajectories in the DETA-USGSD ([Figure 6-4](#)) and BASE-USGSD ([Figure 5-21](#)) flow models.

Figure 6-3
Observed Versus Simulated Well Head - DETA-USGSD Alternative

Figure 6-4
Particle Tracks Starting Near the Underground Nuclear Tests
for the DETA-USGSD Alternative

6.3.4 Aquifer Displacement (DISP) Alternative Flow Model Calibration

As described in [Section 2.3.3.4](#), the displacement fault (aquifer juxtaposition or DISP) alternative HFM model is identical to the BASE HFM except that shallow volcanic aquifer HSUs (TM-WTA and TM-LVTA) are juxtaposed against the LCA across a major basin-forming fault (fault 34 of [Figure D.1-1](#) and [Plate 2](#)) to the southeast of the central testing area ([Plate 2](#); BN, 2005a, Fig. 5-3). This alternative HFM allows for the flow of groundwater directly from the volcanic aquifers into the regional LCA beneath Frenchman Flat.

When the parameters from the calibrated BASE-USGSD flow model were used in the DISP-USGSD alternative, water levels in the AA dropped by about 6 to 7 m ([Figure 6-5](#)). The drop in AA water levels was the result of the drainage of groundwater from the AA downward into and through the TM-WTA and other volcanic units to the LCA. Model calibrations attempting to maintain the connection between the AA and LCA by adjusting upgradient boundary heads in CP basin to supply water to the alluvial basin were unsuccessful in generating appropriate hydraulic heads in the basin-fill HSUs with reasonable permeability values for the HSUs.

To keep the simulated heads in the AA near their observed levels, some reduction of the fault permeability along the interface between the volcanic aquifers and the LCA was necessary. An initial attempt to reduce the hydraulic connection between the volcanic aquifers and the LCA by applying a permeability reduction factor of approximately 10^{-3} at their interface failed to improve the model fit sufficiently. In subsequent attempts to maintain higher water levels in the AA, two approaches were followed. First, the intrinsic permeability of the different HSUs in lateral contact with the LCA across faults was increased or decreased, as guided by the results of parameter sensitivity analyses. Changes of this nature alone again failed to reduce the residuals between measured and simulated water levels in the AA. Second, additional decreases were made in the permeability of the fault through the basin-fill units. This combination of approaches ultimately resulted in an acceptable calibration of the DISP-USGSD flow model.

As reviewed in [Section 3.6.4](#), faults through poorly consolidated sediments are usually low-permeability features. Reduction of permeability across faulted zones in poorly consolidated material may be two or more orders of magnitude less permeable than the surrounding material. The decrease in permeability of the displacement fault required to calibrate the DISP-USGSD alternative

is closer to three orders of magnitude ([Table 5-1](#)). The permeability distribution used to calibrate the DISP-USGSD alternative is shown for the area where the volcanic and carbonate aquifers are juxtaposed across the fault in [Figure 6-6](#). The permeability reduction across the displacement fault where the LCA is placed in contact with the volcanic aquifers is a reasonable calibration approach given the observations of cross-fault flow in nonwelded tuffs, where deformation bands in units similar to these have low absolute permeabilities (Wilson et al., 2003).

[Figure 6-7](#) shows a comparison between the heads produced by the calibrated DISP-USGSD alternative with the measured heads and the heads produced with the BASE-USGSD flow model. Overall, the model agreement with observations is improved in the DISP-USGSD alternative. Multiple facets of the model calibration show improvement; these include: LCA heads (WW-4, WW-4A, and ER-5-3 #2), head contrast between LTCU and AA (UE-5C Water Well Upper and Lower completions), and AA head agreement in the southern portion of the basin (WW-5B, WW-5C, and WW-5A).

A plot of posted weighted residuals associated with the calibrated DISP-USGSD alternative is shown in [Figure 6-8](#). The inserts to [Figure 6-8](#) indicate that wells in the northern testing area near the ER-5-3 well complex and near the central testing area have both small positive and negative residuals, suggesting that there no spatial bias in the simulated heads relative to the measured heads in the DISP-USGSD alternative.

A histogram of weighted residuals in the alluvium and tuffs produced by the DISP-USGSD alternative ([Figure 6-9](#)) shows that the distribution is negatively skewed, reflecting the tendency of the DISP-USGSD alternative to overpredict the measured heads within the LCA.

[Table 6-3](#) shows the metrics that characterize the goodness of fit associated with the DISP-USGSD alternative compared to the BASE-USGSD flow model and with other alternative models presented in [Section 6.0](#). The mean-weighted error calculated for the water levels in the DISP-USGSD flow model (-0.52 m) reflects the small tendency of this model to overestimate heads in the LCA. Despite this tendency, the contribution of the head observations to the objective function is comparable to many of the other models listed in [Table 6-3](#).

To determine whether groundwater flow directions near the testing areas were affected by the juxtaposition of the AA and volcanic aquifers with the LCA at the displacement fault, particles were placed near the test locations in the northern and central testing areas. In the northern testing area, a comparison of particle trajectories calculated with the DISP-USGSD alternative (Figure 6-10) and trajectories calculated with the BASE-USGSD flow model (Figure 5-21) shows that particle trajectories are considerably more easterly. With more flow to the east, the particle pathlines appear to enter the TM-WTA from several of the test locations, rather than moving south through the AA. In the central testing area, the particle trajectories in the DISP-USGSD (Figure 6-10) and BASE-USGSD (Figure 5-21) flow models are similar.

The application of a permeability reduction factor of approximately 10^{-3} along the faults interfaces adjacent to the juxtaposed volcanic aquifers and LCA ultimately produced a calibrated model. However, the need to limit the hydraulic connection between the volcanic and carbonate aquifers before a successful calibration could be achieved demonstrates that the hypothesized connection between shallow volcanic aquifer HSUs and the LCA is unlikely to be a primary route of water movement out of the alluvial basin into the regional flow system. Indeed, none of the particle shown in Figure 6-10 enter the LCA along fault 34.

Figure 6-5
Observed Versus Simulated Well Head - DISP-USGSD Alternative with
Calibrated Parameters from the BASE-USGSD Model

Figure 6-6
Cross Section of Calibrated Intrinsic Permeability for the DISP-USGSD
Alternative at the Aquifer Juxtaposition Interface

Figure 6-7
Observed Versus Simulated Well Head - Calibrated DISP-USGSD Alternative

Figure 6-8
Spatial Distribution of Weighted Residuals for the DISP-USGSD Alternative

Figure 6-9
Residual Histogram DISP-USGSD Alternative

Table 6-3
Summary Calibration Statistics for All HFMs Used with USGSD Recharge Model

MODEL	Calibration Data	Number of Data Observations	Mean-Weighted Error	Maximum Weighted Residual	Minimum Weighted Residual	Variance (m ² or kg ² /s ²)	Error Standard Deviation (m or kg/s)	Objective Function
BASE-USGSD	Well	30	-0.66	1.85	-8.24	4.50	2.12	134.8
	Flux	4	0.89	14.1	-9.57	74.4	8.63	297.7
CPBA-USGSD	Well	30	0.58	26.84	-13.90	44.75	6.69	1,342.0
	Flux	4	0.18	9.12	-6.77	40.24	6.34	161.0
DISP-USGSD	Well	30	-0.52	1.23	-7.88	3.86	1.97	115.9
	Flux	4	-0.59	7.42	-11.21	45.48	6.74	181.9
BLFA-USGSD	Well	30	-0.68	1.84	-8.25	4.51	2.12	135.4
	Flux	4	0.89	14.1	-9.59	74.81	8.65	299.2
DETA-USGSD	Well	30	-0.66	1.85	-8.24	4.50	2.12	134.9
	Flux	4	-0.89	14.1	-9.57	74.4	8.63	297.7

Figure 6-10
Particle Tracks Starting Near the Underground Nuclear Tests
for the DISP-USGSD Alternative

6.3.5 CP Basin Alternative Calibration

As described in [Section 2.3.3.5](#), the CP basin alternative geologic model is identical to the BASE HFM except that (1) the wedge of UCCU adjacent to the Cane Spring fault has been reinterpreted as a thinner unit extending beneath all of the CP basin ([Plate 2](#); BN, 2005a), and (2) faults 11 and 16 in the Base HFM have been combined into a single, more extensive fault (fault 74) in the CP basin alternative model. Although these changes to the Base HFM do not directly affect aquifer properties along expected flow paths from the testing areas or provide groundwater pathways between the alluvium and LCA, they may indirectly affect the calculation of groundwater flow rates and directions by changing the hydrologic relationship between Frenchman Flat basin and the CP basin. Groundwater flow from areas of higher hydraulic head in the CP basin into the alluvium and tuffs in Frenchman Flat has been invoked as a means by which to sustain the downward hydraulic gradient between the alluvium and underlying LCA in Frenchman Flat.

6.3.5.1 Calibration Strategy

The calibration of the CPBA-USGSD alternative was done in parallel with that of the BASE-USGSD model and evolved somewhat differently, as described below. Differences in the approach to calibrating the CPBA and BASE HFMs were a consequence of having several teams of analysts, and were considered desirable in that multiple approaches minimized the dependence of model results on the subjective decisions made during the calibration.

Similar to the BASE-USGSD model calibration, the CP basin alternative (CPBA) was calibrated using a combination of automated parameter estimation with PEST and manual trial-and-error approaches. Initial attempts to optimize more than a few parameters at a time with PEST proved unsuccessful, so PEST was ultimately used to estimate subsets of parameters that affected different aspects of the Frenchman Flat groundwater system. This was done by increasing the weights on specific observations of either flux or hydraulic head in the calibration objective function, and optimizing only those model parameters that were likely to affect the model's ability to match those observations, as determined by sensitivity studies with the BASE-USGSD model ([Section 7.2](#)).

Because of the large number of potentially adjustable parameters and the size of the numerical grid, the approach used to calibrate the CPBA-USGSD alternative was to group parameters in order to limit the amount of computational work. This approach acknowledged that the limited data available for the Frenchman Flat basin do not easily allow the estimation of many independent parameters. Grouping parameters for similar rock or sediment types provided a way of reducing the total number of adjustable parameters while retaining some flexibility to adjust the value of the parameter when it was absolutely necessary to do so. A drawback of this approach was that it relied on the somewhat subjective judgment of the modeler as to which parameters could appropriately be grouped. The grouping employed in the CPBA-USGSD calibration mostly involved grouping certain HSU permeabilities and fault permeability factors during initial calibration runs using PEST; these groupings were retained during later stages of the modeling when manual parameter adjustments were used to finalize the model calibration.

The following three sections describe calibration results for the CPBA HFM that is based on recharge rates and boundary conditions associated with the USGS infiltration with re-distribution (USGSD) map ([Section 2.2.1](#)).

6.3.5.2 CPBA-USGSD Simulated Hydraulic Heads

Simulated water-table elevations produced by the calibrated CPBA-USGSD alternative are shown in [Figure 6-11](#) for the water table, and [Figures 6-12](#) and [6-13](#) show two west-east cross sections of computed heads. [Figure 6-14](#) shows the calibrated boundary heads for the CPBA-USGSD model. These figures indicate that the horizontal hydraulic gradients produced with the CPBA-USGSD flow model are relatively low within the northern and central testing areas of Frenchman Flat. Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast, indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction ([Figure 6-11](#)). As with similar figures for the BASE-USGSD flow model calibration, simulated hydraulic heads in the CP basin are approximately 100 m higher than those in Frenchman Flat. Hydraulic gradients within each of these two areas are relatively flat, and most of the head loss between the CP basin and Frenchman Flat is predicted to occur across the Cane Spring fault (fault 3). The simulated heads in CP basin are also more than 100 m higher than heads in southwest Yucca Flat, indicating the potential for groundwater flow from the CP basin into southwest Yucca Flat.

Figure 6-11
Water-Table Contours for the Calibrated CPBA-USGSD Alternative

Figure 6-12
West-East Cross Section of Simulated Heads at the Northern Testing Area for the CPBA-USGSD Alternative

Figure 6-13
West-East Cross Section of Simulated Heads at the Northern Testing Area for the CPBA-USGSD Alternative

April 26, 2006

cpba_usgsd_head_bndrysec.ps

Figure 6-14
Calibrated Boundary Heads for the CPBA-USGSD Alternative

6.3.5.3 CPBA-USGSD Hydraulic Head and Flux Residuals

Figure 6-15 shows the groundwater fluxes calculated by the calibrated CPBA-USGSD alternative along the boundaries of the Frenchman Flat model domain as compared with the fluxes produced by the UGTA regional model. As the latter figure indicates, the net fluxes calculated by the CPBA-USGSD flow model are in good agreement with the net fluxes calculated with the UGTA model along each of the boundaries.

Figure 6-16 compares the heads simulated with the calibrated CPBA-USGSD alternative to the measured heads and to the heads produced with the BASE-USGSD model. The heads simulated with the CPBA-USGSD alternative are generally very similar to the heads simulated with the BASE-USGSD model and fall within the estimated uncertainty of the measured heads. However, the heads simulated with the CPBA-USGSD alternative do not match the measured heads at WW-C and WW-C1 or at WW-4 and WW-4A nearly as well as heads simulated with the BASE-USGSD model. The heads simulated with the CPBA model are about 34 m lower than the measured heads at WW-4 and WW-4A and about 20 m higher than the measured heads at WW-C and WW-C1. Additionally, the heads estimated with the CPBA-USGSD alternative in the LCA at Well ER-5-3 #2 are higher than either the measured heads or the heads simulated with the BASE-USGSD model. Thus, the CPBA-USGSD alternative underestimates the downward vertical gradient across the tuff confining units in the northern testing area near Well ER-5-3 #2.

A plot of posted weighted residuals associated with the calibrated CPBA-USGSD alternative is shown in Figure 6-17. Figure 6-17 shows that positive and negative weighted residuals are contained in each region of the flow model, indicating that there is no spatial bias in the simulated heads relative to the measured heads.

A histogram of weighted residuals produced by the CPBA-USGSD alternative shows that 24 of the 28 residuals calculated for observations in the tuff or alluvium are smaller than 1 m in magnitude (Figure 6-18). However, the two large positive residuals associated with Wells WW-4 and WW-4A introduce an overall positive bias to the histogram of residuals.

[Table 6-3](#) shows the metrics that characterize the goodness of fit associated with the calibration of the CPBA-USGSD alternative compared with the BASE-USGSD flow model and with other alternative models presented in [Section 6.0](#). The relatively large mean-weighted residual calculated for the water levels in the CPBA-USGSD alternative (0.58 m) reflects the large positive residuals associated with Wells WW-4 and WW-4A. Consequently, the contribution of the head residuals to the objective function in the CPBA-USGSD alternative is large compared to the other models and large compared to the contribution to the objective function from the flux residuals.

Figure 6-15
Groundwater Fluxes Simulated by the UGTA Regional Model and
the Frenchman Flat CPBA-USGSD Alternative

Figure 6-16
Observed Versus Simulated Well Head - CPBA-USGSD Alternative

Figure 6-17
Spatial Distribution of Weighted Residuals for the CPBA-USGSD Alternative

Figure 6-18
Residual Histogram CPBA-USGSD Alternative

6.3.5.4 CPBA-USGSD Estimated Hydraulic Parameters

The estimated hydraulic parameters in the model calibration include both the reference permeability of the HSUs in the model, as well as the permeability factors (*fperms*) associated with the faults in the model. The permeabilities of the HSUs estimated from calibration of the CPBA-USGSD alternative are shown as a function of depth and compared against permeability data from the Frenchman Flat and the general NTS area in [Figures 6-19](#) through [6-23](#). The values of reference permeability and the estimated *fperm* factors estimated during calibration of the CPBA-USGSD flow model are listed in [Table 6-2](#). [Figure 6-24](#) shows the calibrated intrinsic permeability at the water-table surface, and [Figures 6-25](#) and [6-26](#) show west-east cross sections of calibrated intrinsic permeability values at the northern and central testing areas, respectively.

The model permeability of the AA and OAA HSUs in the CPBA-USGSD alternative are compared to permeability measured in Frenchman Flat and in the general vicinity of the NTS in [Figure 6-19](#), and to data from just Frenchman Flat are highlighted in [Figure 6-19](#) for comparison to site-specific data. The model permeabilities are at the low end of the range of permeability measured in the vicinity of

the NTS and in Frenchman Flat. Further adjustments that could be made to the permeability to bring it into better agreement with the data include increases in the reference permeability, increases in anisotropy, or decreases in the depth-decay coefficient for the AA given in [Table 3-6](#). The latter adjustment would decrease the rate at which permeability decreases with depth. The overall lower permeability estimated for the OAA compared to the AA is reasonable given the greater density and more pervasive zeolitization of the OAA (BN, 2005a).

The model permeability of the LCA and LCA3 HSUs are compared to permeability data for the carbonate aquifer in [Figure 6-20](#). The data include measurements both on and adjacent to the NTS, and data from the vicinity of Frenchman Flat at Wells WW-C, WW-C1, TW-3 and ER-5-3 #2. The data suggest a more rapid reduction in permeability with depth than was assumed in the model is possible, but some of this apparent reduction could be due to heterogeneity associated with the diverse structural settings in which the data were measured. The model permeabilities for both the LCA and LCA3 are in reasonably good agreement with the data.

The permeabilities of HSUs that are considered to be confining units in Frenchman Flat are compared to those measured on tuffs from Yucca Mountain and other older tuffs at federal facilities north of the NTS ([Figure 6-21](#)). The single data point from Frenchman Flat is from hydraulic testing of the LTCU in Well ER-5-4 #2. As in the BASE-USGSD model, the model permeabilities of the LTCU, UTCU and VCU are at the low end of the range of permeabilities. The model permeability of the WCU is higher than the estimates of the other confining units and falls in the middle the observed range. As mentioned in [Section 6.5.7.4](#), the higher permeability estimated for the WCU compared to the other confining units may be due to the presence of numerous lava and breccia flows in this HSU in the western part of the model, which could make the WCU more conductive than other confining units (BN, 2005a, p. 4-19).

Volcanic rocks that are generally considered to be aquifers in Frenchman Flat include welded tuffs (TSA and TM-WTA), vitric nonwelded tuffs (TM-LVTA and LVTA), and basaltic lava flows (BLFA). The model permeabilities of these HSUs are compared to NTS data for welded tuffs, nonwelded tuffs, and lavas taken primarily from Yucca Mountain and Pahute Mesa, and to data measured in the Frenchman Flat area at Wells WW-4, WW-4A, and ER-5-3 ([Figure 6-22](#)). The model permeability estimates for the TSA, TM-LVTA, and LVTA are toward the high end of the observed range, and the

permeability estimates for the BLFA are at the low end of the observed range. The permeabilities estimated for the TM-WTA obtained with the CPBA-USGSD alternative are in good agreement with the data with the site-specific data.

The model permeabilities of the playa deposits (PCU1L, PCU1U, and PCU2T) in the flow model are generally lower than the permeabilities for the AA or OAA.

As with the BASE-USGSD model and other alternative HFMs, the LCCU at the base of the model was removed in the CPBA-USGSD flow model to reduce the model size and because it is generally considered to form the hydraulic “basement.” Consequently, the UCCU is the only clastic confining unit in the model. Its estimated permeability is compared to permeability data for the UCCU from the Eleana Range and data for the LCCU from northwest Yucca Flat in [Figure 6-23](#). The estimated permeability for the UCCU is within the range indicated by these data.

Finally, estimated *fperm* factors for each of the faults in the model are given in [Table 6-2](#). An *fperm* factor greater than 1 indicates that permeability within the fault is increased relative to the rocks through which it passes, whereas an *fperm* factor less than 1 indicates that permeability within the fault is reduced. An *fperm* factor of 1 indicates that permeability within the fault is unchanged relative to the host rock.

As in the BASE-USGSD flow model, estimated *fperm* factors for the CPBA-USGSD alternative spanned almost seven orders of magnitude and included values both considerably greater than and considerably less than 1. The identical values estimated for many faults in the model indicates that these *fperm* factors were estimated for these faults as a group. The lowest *fperm* factors were estimated for fault 3 (the Cane Spring fault), which separates the CP basin from Frenchman Flat basin, and for other faults associated with the CP Hogback in the northwest part of the model (faults 12, 14, and 15). As for the CPBA-USGSD and other alternative flow models, faults associated with the Rock Valley fault system (faults 21, 33, 34, 57, and 58) and faults 17 and 39 ([Figure D.1-1](#)) had estimated *fperm* factors that indicated these faults were significant conduits for groundwater. The southern terminations of faults in Yucca Flat in the northern part of the CPBA-USGSD model domain (faults 2, 7, 22-25, and 27-29) were also estimated to be relatively conductive, although much less so than the faults associated with the Rock Valley system. The short faults near the central testing area (faults 35-38, 40-45, and 48-56) were estimated to have an *fperm* factor of 0.1, indicating they would

not be expected to be preferential pathways for radionuclide transport in this model. Likewise, faults 59-73 in the southeast corner of the model had *fperm* factors less than 1 (0.9). The relative sensitivity of the model calibration to individual *fperm* factors is discussed in [Section 7.2.5](#).

As in other HFMs, the final permeabilities in the CPBA-USGSD alternative depend on the values estimated for the reference permeabilities of the individual HSUs, the assumed depth-decay coefficients applied to the HSUs ([Table 3-6](#)), and the permeability changes imposed by the presence of the faults, as implemented through the *fperm* factors ([Table 6-2](#)). The calibrated permeabilities associated with the CPBA-USGSD flow model are shown at the water table in [Figure 6-24](#) and in west-east cross sections in the northern and central testing areas in [Figures 6-25](#) and [6-26](#), respectively. As with the BASE-USGSD flow model, the combined effects of the spatial distribution of HSUs, the depth decay in permeability, and the overprint of permeability changes associated with faults serve to create a complex distribution of permeability within the CPBA-USGSD flow model. The distribution of permeability in at the water table ([Figure 6-24](#)) shows that the central part of the Frenchman Flat basin is surrounded on the north, east, and south by a zone of low permeability that corresponds to the confining units that line the deepest parts of the basin and which rise up along the flanks of the basin to intersect the water table ([Figures 6-25](#) and [6-26](#)). This zone of lower permeability rock separates the basin hydraulically from the much more permeable LCA that lies outside of and beneath the Frenchman Flat basin. As in the BASE-USGSD flow model, an arcuate band of higher permeability of about 10^{-12} m² associated with the TSA and LVTA HSUs wraps around the northern part of the basin in the CPBA flow model and connects areas of higher hydraulic head in the CP basin to parts of the northern testing areas in Frenchman Flat. As discussed in [Section 5.5.4](#), this high-permeability band plays an important role in the simulated movement of particles leaving the northern testing area of Frenchman Flat.

Like similar figures shown for the BASE-USGSD flow model, the distributions of permeability shown in cross section for the CPBA-USGSD alternative ([Figures 6-25](#) and [6-26](#)) indicate a high-permeability zone between the base of the alluvium and the tuff confining units that corresponds to the TM-WTA. The TM-WTA has a relatively high permeability at depth both because it has a higher reference permeability than the tuff confining units ([Table 6-2](#)) and because its permeability decays with depth at a slower rate than the alluvium ([Table 6-2](#)). As in the BASE-USGSD flow model, the high-permeability interval associated with the TM-WTA plays an important role in

diverting groundwater flow in the northern testing area, and in enhancing the hydraulic connection between the deep part of the Frenchman Flat basin near the central testing area and the areas of higher head to the west of Frenchman Flat basin to the west.

Figure 6-19
Calibrated Permeability in the CPBA-USGSD Alternative Versus Measured Permeability of AA

Figure 6-20
Calibrated Permeability in the CPBA-USGSD Alternative
Versus Measured Permeability of the LCA

Figure 6-21
Calibrated Permeability in the CPBA-USGSD Alternative
Versus Measured Permeability of Confining HSUs

Figure 6-22
Calibrated Permeability in the CPBA-USGSD Alternative
Versus Measured Permeability of Volcanic Aquifers

Figure 6-23
Calibrated Permeability in the CPBA-USGSD Alternative
Versus Measured Permeability of the UCCU

Figure 6-24
Calibrated Intrinsic Permeability at the Water Table in
the CPBA-USGSD Alternative

Figure 6-25
West-East Cross Section of Calibrated Intrinsic Permeability in the CPBA-USGSD Alternative through the Northern Testing Area

Figure 6-26
West-East Cross Section of Calibrated Intrinsic Permeability in the CPBA-USGSD Alternative at the Central Testing Area

6.3.5.5 Calculated Groundwater Flow Paths for the CPBA-USGSD Flow Model

Similar to the BASE-USGSD flow model, groundwater flow paths in the CPBA-USGSD alternative near the northern and central testing areas were determined by placing particles either at or near the test locations. [Figure 6-27](#) shows the trajectory of particles initially located near test locations in the northern and central testing areas. The particle locations are colored by the HSUs through which the particles pass.

Particles associated with each of tests south of the detachment fault (fault 36 in [Figure D.1-1](#)) in the northern testing area move southward in the CPBA-USGSD alternative ([Figure 6-27](#)). North of the detachment fault, groundwater movement near the PIN STRIPE test appears to be very similar in the BASE-USGSD and CPBA-USGSD flow models ([Figures 5-21](#) and [6-27](#)) initially, but as the flow moves through the basin in the CPBA-USGSD model, the particle track stays more shallow in the flow system rather than moving down to the LCA. In both models, particles originating near the test move eastward from the test location and eventually through the LTCU and into the LCA. Eventually, the particles move through the Rock Valley fault system and exit the models in the Rock Valley area in the southwest part of the model.

In the central testing area ([Figure 6-27](#)), particles originally located near the water table at the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area in the CPBA-USGSD alternative will be through the alluvium toward the southeast. Particle tracking results from analyses allowing all mobile particles to exit the flow system indicate that these particles will encounter the Rock Valley fault system and exit the flow system along the southern part of the western boundary of the model.

Figure 6-27
Particle Tracks Starting Near the Underground Nuclear Tests
for the CPBA-USGSD Alternative

6.3.6 Summary of Hydrostratigraphic Framework Model Conceptual Model Uncertainty Analysis

Steady-state groundwater flow models were used to assess conceptual model uncertainty use different HFMs that interpreted aspects of the Frenchman Flat hydrostratigraphy somewhat differently. Each of the HFMs included 17 HSUs, of which 8 were considered as aquifers and 9 as confining units, and more than 70 faults that were included based on their potential hydrologic significance. Each of these HFMs was used in conjunction with a map of recharge for the Frenchman Flat area that was taken from a water-balance model of infiltration and recharge model (designated the USGSD model) originally developed for the regional model area. Each alternative HFM model calibration above documents the final fit along with comparison plots for calibrated and measured permeability. Particle tracks from test locations are also shown.

Independently calibrated models for the BASE-USGSD and CPBA-USGSD models provide generally similar fits for boundary fluxes and simulated heads, with the exception of measured heads at WW-C, WW-C1, WW-4, and WW-4A, where the heads are better simulated by the BASE-USGSD model. Calibration fits are generally superior for the BASE-USGSD model compared to the CPBA-USGSD alternative for multiple statistical parameters that characterize goodness of fit. Particle tracks are generally similar for the northern test area for both models with the exception of particle tracks starting in the vicinity of PIN STRIPE. The DISP-USGSD model calibration indicated that a completely open connection between the alluvium and the LCA is unrealistic, but that modest adjustments to fault parameters allow for a good simulation of water-level observations. The BLFA-USGSD and DETA-USGSD model alternatives were calibrated using the parameters estimated during calibration of the BASE-USGSD model. Both models show similar patterns of particle tracks for the southern testing area compared to the BASE-USGSD model and show some variability in particles tracks compared to the BASE-USGSD model for the northern testing area. The primary differences are in the direction of the particle trajectories and in HSUs traversed along the pathways.

6.4 Discrete Uncertainty Analysis

As with most models covering large areas, considerable parameter uncertainty exists that may have significant effects on the resulting calculations made by the model, but cannot be identified based on model calibration data alone. In the context of the Frenchman Flat CAU flow model, the most relevant results involve the direction and velocity of travel for particles starting near the northern and central underground nuclear tests.

Discrete uncertainty analyses are used to evaluate the effect of these uncertainties on the likely travel paths for particles starting at the northern or central testing areas. As with all particle tracking calculations presented in this report, the calculations are completed assuming that particles do not diffuse and that the medium porosity is uniformly 0.01. This value is arbitrary and does not reflect the effective porosity that will be used to evaluate radionuclide transport. To map the groundwater flow paths, particle tracking is run for 100,000 years, until all reasonably mobile particles have left the flow model domain.

The approach is to define a possible pathway of enhanced or adjusted particle movement resulting from a change in the model parameters. Model parameters are adjusted until the calibration is significantly affected. For example, if a tested scenario involves vertical migration down a specific fault, the vertical permeability multiplier of the fault is increased to the point where the model is unable to simulate water levels around this fault reasonably. Ideally, parameters are adjusted up to the limit of either available data or until plausible limits for the value of the parameter are violated. However, available data for most of the calibrated parameters do not provide reliable upper or lower bounds for most of the parameter values. Therefore, parameter adjustments were made without imposing any bounds until the model-calculated water levels changed by about 1 m or, based on the analysts' judgment that the parameter adjustment was outside the range of observed values for other similar features in the Frenchman Flat flow model. At this point, vertical migration down the selected fault is evaluated.

This approach also addresses other questions related to calibrated model parameter uncertainty. For example, it is not clear whether local vertical or horizontal anisotropy of hydraulic conductivity exists at a critical location that would result in particles (starting near underground nuclear test locations)

migrating along these preferential pathways. Using the faults as physical features, the discrete uncertainty analysis approach can simulate the effects that such preferential pathways would have if they were present.

6.4.1 Northern Testing Area Travel Pathways

Two major sources of uncertainty exist in the northern testing area that could result in different trajectories of particle migration than those observed in the BASE-USGSD model. The first source is the fault multiplier value assigned to fault 35 ([Figure D.1-1](#)). This fault is situated very close to five of the underground nuclear tests (DERRINGER, NEW POINT, DIAGONAL LINE, MINUTE STEAK, and DIANA MOON). The other source is the potential pathway through the poorly characterized BLFA for which there are no reliable permeability data within Frenchman Flat or the NTS. The following sections describe the analyses made to address these uncertainties.

Fault 35 Uncertainty

Fault 35 runs west to east and is shown on [Figure D.1-1](#). Fault 35 is inferred from the large depth disparity of the top of volcanic rocks between UE-11b and UE-11g, and the shallow dip of the volcanic rocks observed on the seismic data in the area. The fault is not exposed at the surface, and offset of seismic reflections within the volcanic section is also not observed, probably due to the location of the fault near the edge of the seismic data where resolution is low. It is modeled as a detachment fault that flattens rapidly at depth within the basal portion of the volcanic section because seismic data do not show offset of the top of pre-Tertiary rocks, which image well in the seismic data in the area. Based on the depth disparity in drill holes and seismic data, offset along the central portion of fault 35 between UE-11b and UE-11g is approximately 548.6 m. This fault intersects the AA, OAA, BLFA, TM-WTA, TSA, UTCU, and LTCU HSUs. Three of the underground nuclear tests (DERRINGER, DIAGONAL LINE, and DIANA MOON) are located near this fault. Two other underground nuclear tests (NEW POINT and MINUTE STEAK) are also situated close to fault 35. As shown in [Table 6-2](#), this fault has a neutral permeability value for all but one of the HFM uncertainty analyses. That is, the permeability values for the nodes associated with this fault are set equal to the nodes surrounding them within each HSU. Changing the permeability around this fault could result in faster or further travel from the surrounding underground nuclear test locations. To evaluate this scenario, larger permeability multipliers in all three dimensions are used for this fault to

simulate a preferential flow path along and down the fault. [Figure 6-28](#) shows the impact on simulated head from increasing the permeability multiplier for fault nodes by a factor of 10^9 , and [Figure 6-29](#) shows the resulting particle tracks. Particle tracks are colored by the HSU through which the particles pass. Simulated heads at target well locations dropped slightly with an average drop of about 1 cm. Results show that using an extremely large factor for the fault permeability multiplier results in slightly enhanced advection to the east for particles starting near DERRINGER, DIAGONAL LINE, DIANA MOON, NEW POINT, and MINUTE STEAK. Groundwater flow paths in the TM-WTA appear to be the most influenced by the increased permeability of fault 35. Particle tracks originating near the underground nuclear tests adjacent to fault 35 have little vertical migration along this fault. The significance of this parameter change to transport calculations is unclear given the long duration and limited processes used for these flow path simulations.

BLFA Uncertainty

As explained in [Section 2.3.3.2](#), the BLFA HFM alternative contains a continuous BLFA near the water table and extends this HSU to the Rock Valley faults along the eastern edge of the Frenchman Flat basin. This could provide a lateral conduit for transport of radionuclides eastward to the faults and, ultimately, to the LCA. However, no data exist to constrain the reference permeability value associated with this HSU. To complicate the problem, no water-level data are sufficiently sensitive to the BLFA permeability, making the calibration of this permeability value unconstrained by available measurements.

To analyze the potential for lateral groundwater flow through the BLFA to intersect Rock Valley faults along the eastern edge of Frenchman Flat basin, the calibrated BLFA-USGSD model ([Section 6.3.2](#)) is used. The reference permeability value assigned to the BLFA HSU is increased until the water levels at nearby wells are significantly impacted. [Figure 6-30](#) shows the impact on simulated water levels when the BLFA reference permeability is increased by four orders of magnitude, and [Figure 6-31](#) shows the associated particle tracks for this model in the northern testing area. The largest change in simulated water levels is at Well UE-5f where the simulated water level decreased by about 0.6 m as a result of increasing the BLFA permeability by a factor of 10^4 compared to the BASE-USGSD calibration. A similar drop in simulated water levels also occurs at most of the wells in the northern testing area. Particle tracks originating near the underground nuclear tests in close proximity to the BLFA (DERRINGER, NEW POINT, and MILK SHAKE) converge and move

southward into the AA, compared to the BASE-USGSD flow field. Particle tracks originating near DERRINGER and NEW POINT have a strong easterly component and shift to the south before encountering fault 38. Particle tracts originating near MILK SHAKE travel west and shift to the south after crossing fault 38. These particle track results indicate that the potential flow path across a continuous BLFA unit to the Rock Valley faults on the eastern edge of the alluvial basin is unlikely in the northern testing area.

Figure 6-28
Observed Versus Simulated Well Head - BASE-USGSD Model
with Fault 35 Permeability Multiplier at 10^9

Figure 6-29
Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD
Model with Fault 35 Permeability Multiplier at 10^9

Figure 6-30
Observed Versus Simulated Well Head - BLFA-USGSD Model
with BLFA Permeability Increased by 10^4

Figure 6-31
Particle Tracks Starting Near the Underground Nuclear Tests - BLFA-USGSD
with BLFA HSU Reference Permeability Increased by 10^4

6.4.2 Central Testing Area Travel Pathways

Particles starting near the three tests located in central Frenchman Flat generally travel toward the south-southeast. If any of these particles reached fault 38 ([Figure D.1-1](#)), eventual transport to the Rock Valley fault system could be enhanced. As described before, the Rock Valley fault system provides the major drainage feature for the LCA under Frenchman Flat. Fault 38 runs north to south and truncates at fault 34. As shown in [Table 6-2](#), this fault has a neutral or close to neutral permeability value for all of the HFM uncertainty calibrations (fault permeability multipliers range between 0.1 and 5.0).

Two assessments are conducted to evaluate the potential impact of this fault upon the model-calculated flow pathways. The first evaluation involves changing the permeability along the fault to simulate a preferential pathway from the AA to the underlying volcanic HSUs. The second evaluation involves changing the vertical permeability along this fault to examine the potential downward migration from the AA along this fault and into the LCA.

Increasing the permeability in all directions for fault 38 by a factor of 20,000 results in lower hydraulic head throughout the AA. Hydraulic head decreased approximately 0.8 m with the largest drop in water level at Well ER-5-4 (lower). This result is expected because fault 38 extends from the southern edge of the AA to the northern testing area in the Frenchman Flat basin. [Figure 6-32](#) shows the impact on simulated water levels when the permeability for fault 38 nodes is increased by a factor of 20,000, and [Figure 6-33](#) shows the associated particle tracks for this model.

Increasing only the vertical permeability for fault 38 by a factor of 10^5 results in lower water levels throughout the AA. The hydraulic head decreased approximately 0.3 m with the largest drop in water level at WW-5C. [Figure 6-34](#) shows the impact on simulated water levels when the vertical permeability for fault 38 nodes is increased by a factor of 10^5 , and [Figure 6-35](#) shows the associated particle tracks for this model. Similar to the effect of increasing the permeability of fault 38 nodes, increasing the vertical permeability has limited effect on these particle tracks; however, it appears that an open vertical zone in the OAA serves to reduce the lateral particle advection to the edges of the basin-fill HSUs for some of the particle tracks. Particles moving vertically in fault 38 never leave the OAA during the 100,000-year particle tracking simulation.

Figure 6-32

Observed Versus Simulated Well Head - BASE-USGSD Model with Fault 38 Permeability Multiplier at 20,000

Figure 6-33

Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model with Fault 38 Permeability Multiplier at 20,000

Figure 6-34
Observed Versus Simulated Well Head - BASE-USGSD Model with Fault 38
Vertical Fault Permeability Multiplier at 10^5

Figure 6-35

Particle Tracks Starting Near the Underground Nuclear Tests - BASE-USGSD Model with Fault 38 Vertical Fault Permeability Multiplier at 10^5

6.4.3 Summary of Discrete Model Uncertainty Analysis

Discrete uncertainty analyses were conducted to evaluate likely scenarios that would lead to longer-range contaminant transport. Discrete uncertainty analyses were used to examine the effects of several model parameters on the model calibration and groundwater flow paths calculated by the BASE-USGSD and BLFA-USGSD models in the northern or central testing areas of the Frenchman Flat basin. The permeability of two faults (35 and 38) in the alluvial and volcanic sections and one HSU (BLFA) were increased to the point where the model calibration was significantly impacted. These parameters were selected because of their great uncertainty and conceptual possibility to affect flow from underground nuclear tests. Changes to parameters in the northern testing area suggest that flow trajectories may be modified through adjustment to the selected model parameters, but the ability of other model parameters to compensate for the model misfit was not determined. In this sense, the effects of these changes may be exaggerated. Changes to tested model parameters in the central testing area have little influence on the resulting flow field. The impact of these flow fields to contaminant transport for the time frame interest will be investigated during the contaminant migration analysis that will be documented in a later report.

6.5 Boundary Conditions Uncertainty Analyses

The Frenchman Flat CAIP (DOE/NV, 1999) states that boundary condition uncertainty must be considered in the flow model analysis, and that the two sources of boundary condition uncertainty are the recharge distribution and the model boundary flow derived from a regional model. These two factors control the water balance of the CAU-scale model, which in turn has a direct bearing on the overall flow rate, and hence groundwater velocity, through the model domain. By combining boundary condition uncertainty with HFMs, a variety of discrete models are produced that cover a reasonable range of uncertainty associated with each model component. This section briefly describes the approach used to address boundary conditions uncertainty and presents results for the BASE and CPBA HFM alternatives. Additional boundary condition uncertainty analysis to understand the impact of boundary head adjustments to heads provided by regional models is also documented in [Section 6.5.7](#).

In arid systems with deep groundwater, it is generally acknowledged that accurate estimation of recharge is difficult. There are some water-balance constraints for the entire Death Valley Regional Flow System (e.g., discharge at Ash Meadows, Oasis Valley, Death Valley), but there is no perennial surface water flow or spring discharge in the Frenchman Flat basin area that could be used to constrain local inflow and outflow. In order to bound the possible recharge volumes, three regional-scale recharge model approaches were used as described in [Section 2.2](#). They are the chloride mass-balance approach, DRIA and DRIAE (Russell and Minor, 2002); the modified Maxey-Eakin empirical method (Maxey and Eakin, 1949; DOE/NV, 1997; IT, 1996a through f; IT, 1997a and b; and SNJV, 2004d), MME and MME-revised; and the distributed parameter watershed model (Hevesi et al., 2003), USGSD, USGSND, and DVRFS. The areal distribution of these recharge models for the Frenchman Flat model domain are shown in [Section 2.2](#).

Each of the recharge models was incorporated into either the UGTA regional model or the DVRFS model to obtain boundary flows and heads for the Frenchman Flat CAU flow model (see [Section 4.5.2](#) and SNJV, 2004d, for procedure and results). The magnitude of total recharge over the Frenchman Flat flow model domain is very small. The most significant difference among these models is the resulting boundary heads and boundary flows. Therefore, only one version of each recharge model incorporated into the UGTA model is used for calibration and uncertainty analyses. The calibration of the BASE and CPBA HFM with the USGSD boundary conditions is described in [Section 5.5](#) and [Section 6.3.5](#). The BASE and CPBA HFMs are combined with the MME-, DRIA-, and DVRFS-boundary conditions in this section to address additional uncertainty in model parameters.

As described in [Sections 3.4](#) and [4.5.2](#), model boundary heads are based on heads interpolated from calibrated regional models onto nodes of the computational mesh along the lateral boundaries of the model domain. The starting points for the CAU model specified-head boundary conditions are the results from the UGTA regional model (SNJV, 2004d) and the DVRFS model (Faunt et al., 2004), as interpolated onto the Frenchman Flat flow model boundaries. As explained in [Section 5.3](#), boundary heads adjustments were considered at three locations:

- CP basin: The UGTA regional model and the recent DVRFS model had a persistent 80-m deviation from the measured heads at the Wells WW-4 and WW-4A just inside the western edge of the CAU model domain. Simulated heads in the area were close to 760 m amsl, and

head measurements in local wells were near 845 m amsl. Thus, if boundary heads in this part of the model had been used based on the results from the UGTA regional model or DVRFS model, a consistent error of about 80 m would have resulted that was entirely a consequence of an inaccurate boundary condition assignment.

- Southern Yucca Flat: Head measurements at Wells WW-C and WW-C1 showed that water levels in this area are about 8 m lower than comparable head results from either regional model. However, the adjustments necessary to bring the measured heads and heads calculated by the regional models into agreement were not made along the boundaries of the Frenchman Flat flow models because these adjustments caused groundwater to flow northward from Frenchman Flat into Yucca Flat within the LCA in the model, counter to the direction indicated by heads in the LCA.
- Well TW-3: This well is close to the eastern edge of the model boundary and has a water-level measurement that is about 2.5 m lower than the model-calculated heads. A reduction of head in the central-eastern edge of the model boundary was necessary to match the available water-level measurements at this well.

Boundary heads computed using the two regional models did not indicate significant vertical gradients in the vicinity of the model boundaries. Therefore, all boundary head corrections were made by adding or subtracting a constant head correction uniformly across the vertical dimension. The correction was made within a window centered around each well, and the correction linearly decayed to zero toward the edges of the window.

This approach to boundary head corrections results in higher heads than the surrounding heads taken from the regional calibrated models for some of the deep units in the BASE-USGSD model. Therefore, to assess the uncertainty in the calibrated flow field as a result of these boundary head adjustments, an alternative adjustment methodology was employed where boundary heads were lower in some HSUs while boundary heads were raised in other HSUs. The details of this approach will be presented in [Section 6.5.7](#).

Combining two of the HFMs with the three additional sets of boundary conditions from two regional-scale models generates six additional, calibrated Frenchman Flat CAU flow models. [Table 6-4](#) lists the boundary flow targets, and [Table 6-5](#) summarizes the calibrated permeability values and permeability multipliers for non-neutral faults for all calibrated models. The summary statistics for each of the models are listed in [Table 6-6](#). The model calibration results are discussed in the following section.

Table 6-4
Boundary Flows (kg/s) Considered for the Different Calibrated Models

UGTA Regional Model				DVRFS Model
Model Face	BASE- or CPBA-USGSD (also used for BLFA, DETA, and DISP HFM's)	BASE- or CPBA-DRIA	BASE- or CPBA-MME	BASE- or CPBA-DVRFS
East	-752	-961	-972	-97
North	-367	-553	-479	-450
West	1,020	1,500	1,500	341
South	113	69.4	-6	209
Total Outflow	1,133	1,569	1,500	550
Total Inflow	-1,119	-1,514	-1,457	-547

Table 6-5
Summary of Calibrated Reference Permeability Values and Permeability Multiplier for Non-Neutral Faults for
Calibrated Models with Varying Boundary Conditions
 (Page 1 of 4)

Hydrostratigraphic Framework Model and Boundary Conditions								
	BASE-USGSD	BASE-MME	BASE-DRIA	BASE-DVRFS	CPBA-USGSD	CPBA-MME	CPBA-DRIA	CPBA-DVRFS
HSU Permeability at Ground Surface - ($\log k_0$ in m^2)								
AA	-11.30	-11.30	-11.20	-11.00	-11.15	-11.15	-10.55	-10.60
PCU	-14.50	-14.50	-14.50	-14.50	-14.04	-14.50	-14.00	-13.50
BLFA	-12.00	-12.00	-12.00	-12.00	-12.20	-12.70	-10.00	-12.00
OAA	-12.00	-11.80	-12.00	-11.80	-12.16	-12.50	-10.98	-11.50
PCU1L	-11.00	-11.00	-14.00	-11.00	-14.19	-11.00	-14.00	-11.00
PCU1U	-11.00	-11.00	-14.00	-11.00	-14.19	-11.00	-14.00	-11.00
TM-WTA	-9.15	-9.15	-9.15	-9.00	-10.10	-7.90	-10.85	-9.00
TM-LVTA	-9.20	-9.25	-9.30	-9.00	-9.29	-7.90	-10.80	-9.00
UTCU	-14.00	-14.00	-14.00	-14.00	-14.04	-14.00	-11.00	-13.00
TSA	-11.00	-11.00	-12.00	-11.00	-9.00	-10.20	-10.20	-11.00
LVTA	-10.50	-10.50	-12.50	-10.50	-9.29	-10.50	-12.50	-10.50
LTCU	-13.50	-13.17	-13.50	-13.50	-15.50	-13.17	-13.00	-13.50
WCU	-11.88	-11.88	-11.88	-11.88	-11.50	-12.66	-11.88	-11.88
VCU	-13.60	-13.10	-13.10	-13.30	-13.25	-13.33	-12.45	-13.06
LCA3	-11.00	-11.00	-11.00	-10.50	-11.12	-11.00	-11.00	-10.50
UCCU	-13.50	-13.50	-14.50	-13.50	-14.26	-13.50	-13.50	-13.50
LCA	-10.40	-9.70	-9.99	-10.74	-10.15	-9.76	-10.00	-10.60
Permeability Multiplier for Faults ^a								
1	0.30	0.30	0.25	0.30	1.03	0.30	0.25	150.00
2	0.50	0.506	0.50	0.52	5.00	0.51	6.00	10.18
3	1.8E-04	1.8E-04	1.8E-04	1.4E-04	1.0E-05	1.8E-04	1.8E-04	1.4E-04
5	0.50	0.50	0.50	0.50	0.20	0.50	0.50	0.50
6	1.00	1.00	1.00	1.00	0.20	1.00	1.00	1.00
7	1.00	1.00	1.00	1.00	5.00	1.00	1.00	1.00
8	1.10	1.06	1.06	1.06	0.20	1.06	1.06	1.06
9	1.00	1.00	1.00	1.00	0.20	1.00	1.00	1.00

Table 6-5
Summary of Calibrated Reference Permeability Values and Permeability Multiplier for Non-Neutral Faults for
Calibrated Models with Varying Boundary Conditions
 (Page 2 of 4)

Hydrostratigraphic Framework Model and Boundary Conditions								
	BASE-USGSD	BASE-MME	BASE-DRIA	BASE-DVRFS	CPBA-USGSD	CPBA-MME	CPBA-DRIA	CPBA-DVRFS
Permeability Multiplier for Faults								
10	0.29	0.29	0.29	0.29	0.20	0.29	0.29	0.29
11	1.0E-05	1.0E-05	1.0E-05	1.0E-05	1.00	1.0E-05	1.00	1.00
12	1.0E-05	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05	1.0E-05	1.0E-05
14	1.0E-05	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05	1.0E-05	1.0E-05
15	1.0E-05	1.0E-05	1.0E-05	1.0E-05	2.0E-05	1.0E-05	1.0E-05	1.0E-05
16	5.0E-04	5.0E-04	5.0E-04	5.0E-04	1.00	5.0E-04	1.00	1.00
17	18.00	18.00	18.00	2.00	75.00	40.00	52.00	15.00
18	15.00	15.00	100.00	2.00	1.00	50.00	500.00	50.00
19	1.00	1.00	1.00	1.00	1.00	10.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	10.00	1.00	1.00
21	67.80	27.80	17.70	100.18	75.00	26.80	75.70	180.18
26	1.00	1.00	10.00	1.00	1.00	1.00	100.00	1.00
27	1.00	0.85	1.00	10.00	5.00	0.85	1.00	10.00
28	1.01	1.01	1.01	10.01	5.00	1.01	1.01	10.01
29	1.00	0.42	1.00	1.00	5.00	0.42	1.00	1.00
30	1.00	1.00	10.00	10.00	1.00	1.00	10.00	10.00
31	1.00	1.00	1.00	1.00	1.00	1.00	150.00	50.00
33	150.85	262.07	242.99	150.85	75.00	280.07	242.99	150.85
34	155.25	523.97	191.23	100.99	75.00	523.97	191.23	100.99
35	1.00	1.00	1.00	1.00	0.10	0.10	1.00	100.00
36	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
37	1.00	0.99	0.99	0.99	0.10	0.99	0.99	0.99
38	5.00	1.00	5.00	1.00	0.10	1.00	5.00	1.00
39	34.00	17.29	36.00	2.00	75.00	40.29	52.00	18.00
40	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
41	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
42	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00

Table 6-5
Summary of Calibrated Reference Permeability Values and Permeability Multiplier for Non-Neutral Faults for
Calibrated Models with Varying Boundary Conditions
 (Page 3 of 4)

Hydrostratigraphic Framework Model and Boundary Conditions								
	BASE-USGSD	BASE-MME	BASE-DRIA	BASE-DVRFS	CPBA-USGSD	CPBA-MME	CPBA-DRIA	CPBA-DVRFS
Permeability Multiplier for Faults								
43	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
44	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
45	1.00	1.00	1.00	1.00	0.10	1.00	1.00	10.00
46	10.00	10.00	12.00	4.35	1.03	50.00	24.00	14.35
47	10.00	10.00	12.00	10.00	1.03	1.00	24.00	10.00
48	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
49	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	0.10	0.10	1.00	10.00
51	1.00	1.00	1.00	0.50	0.10	0.05	1.00	0.25
52	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
53	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
54	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
55	1.01	1.01	1.01	1.01	0.10	0.05	1.01	10.01
56	1.00	1.00	1.00	1.00	0.10	1.00	1.00	1.00
57	31.05	31.05	31.05	31.05	75.00	25.05	31.05	31.05
58	108.39	108.39	112.79	108.39	75.00	50.39	112.79	108.39
59	1.00	2.09	1.00	1.00	0.90	0.19	1.00	1.00
60	1.45	1.45	1.45	1.45	0.90	0.11	1.45	1.45
61	0.45	0.65	0.45	25.00	0.90	1.00	0.45	25.00
62	0.82	0.82	0.82	0.82	0.90	1.00	0.82	0.82
63	0.84	2.00	0.84	100.84	0.90	1.00	0.84	100.84
64	0.74	0.74	0.74	0.74	0.90	1.01	0.74	0.74
65	0.93	0.93	0.93	0.93	0.90	1.01	0.93	0.93
66	0.88	0.88	0.88	0.88	0.90	1.00	0.88	0.88
67	0.92	0.92	0.92	0.92	0.90	1.01	0.92	0.92
68	0.98	0.98	0.98	0.98	0.90	1.01	0.98	0.98

Table 6-5

Summary of Calibrated Reference Permeability Values and Permeability Multiplier for Non-Neutral Faults for Calibrated Models with Varying Boundary Conditions

(Page 4 of 4)

Hydrostratigraphic Framework Model and Boundary Conditions								
	BASE-USGSD	BASE-MME	BASE-DRIA	BASE-DVRFS	CPBA-USGSD	CPBA-MME	CPBA-DRIA	CPBA-DVRFS
Permeability Multiplier for Faults								
69	0.35	0.39	0.35	25.00	0.90	1.00	0.35	25.00
71	1.00	1.00	1.00	25.00	0.90	1.00	1.00	25.00
72	1.39	1.40	1.39	1.39	0.90	1.40	1.39	1.39
73	1.00	0.66	1.00	1.00	0.90	1.06	1.00	1.00
75	1.8E+04	1.8E+04	1.8E+04	1.4E+04	3.2E-01	1.8E+04	1.8E+04	1.4E+04
76	1.00	10.00	1.00	1.00	1.00	10.00	1.00	1.00

^aFaults not shown have a permeability multiplier close to 1 (0.90 to 1.05).

Table 6-6
Model Summary Statistics for Frenchman Flat Steady-State Flow Model Calibrations
with Varying Boundary Conditions

MODEL	Calibration Data	Number of Observations	Mean-Weighted Error	Maximum Weighted Residual	Minimum Weighted Residual	Variance (m ² or kg ² /s ²)	Error Standard Deviation (m or kg/s)	Objective Function
BASE-USGSD	Well	30	-0.659	1.85	-8.24	4.50	2.12	134.8
	Flux	4	0.889	14.1	-9.57	74.4	8.63	297.7
CPBA-USGSD	Well	30	0.58	26.84	-13.90	44.75	6.69	1,342
	Flux	4	0.18	9.12	-6.77	40.24	6.34	161.0
BASE-MME	Well	30	-0.656	1.55	-5.94	2.78	1.67	83.5
	Flux	4	0.123	0.800	-0.680	0.297	0.545	1.19
BASE-DRIA	Well	30	-0.605	2.08	-8.51	4.80	2.19	144.0
	Flux	4	1.90	8.75	-5.26	46.7	6.84	186.9
BASE-DVRFS	Well	30	-0.875	2.21	-14.4	11.8	3.43	353.4
	Flux	4	-4.58E-02	3.55	-2.49	4.91	2.22	19.7
CPBA-MME	Well	30	-0.959	1.78	-6.02	4.18	2.04	125.3
	Flux	4	1.23	25.8	-10.6	210.3	14.5	841.2
CPBA-DRIA	Well	30	-0.657	5.96	-15.5	16.3	4.04	488.7
	Flux	4	1.89	11.8	-7.11	53.5	7.32	214.1
CPBA-DVRFS	Well	30	-1.25	2.11	-18.2	18.4	4.29	552.5
	Flux	4	-4.60E-02	5.79	-2.35	11.5	3.40	46.1

6.5.1 BASE HFM with Chloride Mass-Balance (DRIA) Boundary Conditions (BASE-DRIA)

The BASE HFM is calibrated with the DRIA recharge, boundary heads, and boundary flows.

Figure 6-36 shows the target and simulated fluxes across the four model boundaries, and Figure 6-37 shows the observed and simulated water levels calculated by the calibrated BASE-DRIA model. The model agreement to the measured hydraulic heads is generally good (within approximately 1 m); however, model results at ER-5-3 #2 and WW-C and WW-C1 have slightly higher residuals than the BASE-USGSD model (Figure 6-37). The increased error at WW-C and WW-C1 most likely reflects higher heads on the north edge of the model boundary compared to the BASE-USGSD model (Figures 6-38 and 5-3). It is likely that these higher heads are ubiquitous in the northern portion of the model and propagate to ER-5-3 #2. The comparatively large residuals are not expected to significantly impact simulated lateral groundwater movement through the alluvium and tuffs in the Frenchman Flat basin given the small residuals at Wells UE-5 PW-3, UE-5c WW, UE-5f, UE-11a, and UE-11b located on the perimeter of Frenchman Flat (Figure 6-39).

The DRIA boundary conditions yield a total regional flux in and out of the Frenchman Flat CAU model domain that is about 40 percent larger than for the USGSD model (Table 6-4). Therefore, the BASE-DRIA alternative has a larger value for the calibrated LCA reference permeability in order to transmit the additional water. Compared to the BASE-USGSD LCA reference permeability, the LCA reference permeability used for the BASE-DRIA calibration is larger by a factor of about 2.6 (Table 6-5). The other large change in calibrated reference permeability is for the VCU, which is also more permeable for this alternative (by a factor of about 3.2). The AA also has a slightly higher reference permeability value, which is about 1.3 times larger than that for the BASE-USGSD model.

Particle tracks in the vicinity of the northern and central testing areas are shown in Figure 6-40. The particle tracks are colored by the HSU in which the particle is located. Particle tracks originating near PIN STRIPE indicate a more easterly component of flow with advection into the shallow Timber Mountain aquifer (TM-WTA) compared to the BASE-USGSD particle tracks (Figure 5-21). Particle tracks originating near DERRINGER, DIANA MOON, MINUTE STEAK, MILK SHAKE, and NEW POINT indicate similar groundwater flow paths to the BASE-USGSD results. Particle tracks in the central testing area are also similar to the BASE-USGSD model, but have a slightly more southern component, possibly resulting from the enhanced outflow at the southern edge of the model

as a result of lower boundary heads on the south edge of the model ([Figures 4-3](#) and [6-38](#)). Changes in particle track directions indicate adjustments to local groundwater flow paths and are typically due to the subtle variations in boundary heads between the different calibrated regional models and from changes in the reference permeabilities for the HSUs or in the fault permeability multipliers. Because the gradients at both the central and northern testing areas are very flat, only a small change in head is required to generate significantly different particle trajectories.

Figure 6-36
Groundwater Fluxes Simulated by the UGTA Regional Model and the
Frenchman Flat Model - BASE-DRIA Alternative

Figure 6-37
Observed Versus Simulated Well Head - BASE-DRIA Alternative

April 26, 2006

baseR3_head_bndryxsec.ps

Figure 6-39
Spatial Distribution of Weighted Residuals for the BASE-DRIA Alternative

Figure 6-40
Particle Tracks Starting Near the Underground Nuclear Tests
for the BASE-DRIA Alternative

6.5.2 BASE HFM with Modified Maxey-Eakin (MME) Boundary Conditions (BASE-MME)

The BASE HFM was calibrated with the modified Maxey-Eakin (MME) recharge, boundary heads, and boundary flows. A comparison of simulated and target boundary flows is shown in [Figure 6-41](#). [Figure 6-42](#) shows the target and simulated water levels calculated by the calibrated BASE-MME alternative. The model agreement to the measured hydraulic heads is generally good (within approximately 1 m); however, model results in the central testing area have slightly greater residuals than the BASE-USGSD model and smaller residuals at WW-C and WW-C1 ([Figure 6-42](#)). Calibrated boundary heads for the BASE-MME model are very similar to the boundary heads for the BASE-USGSD model ([Figures 5-3](#) and [6-43](#)), thus providing similar results for the calculated LCA hydraulic heads.

The spatial distribution of weighted residuals at the target wells is shown in [Figure 6-44](#). Throughout the alluvium and volcanic units, there is no apparent spatial bias in the residual distribution as is indicated by [Figure 6-44](#), suggesting that there is no systematic bias in the lateral gradients within the basin in the BASE-MME model.

Similar to the BASE-DRIA model, the MME regional flux is about 30 percent larger than the USGSD model flux ([Table 6-4](#)). This results in a larger value for the calibrated LCA reference permeability. Compared to the BASE-USGSD calibrated LCA reference permeability, the LCA reference permeability for this model is larger by a factor of about 5 ([Table 6-5](#)). The other large change in calibrated reference permeability values is for the VCU, LTCU, and OAA, which are also more permeable for this alternative than for the BASE-USGSD model (by a factor of about 3). The AA has an identical calibrated reference permeability to the value used for the BASE-USGSD model.

[Figure 6-45](#) show the particle tracks in the vicinity of the underground nuclear tests in the northern and central testing areas. For MINUTE STEAK, DIANA MOON, and DIAGONAL LINE, particle advection is toward the northeast for some of the particle tracks, unlike the observed flow paths from the BASE-USGSD model where the particle tracks were predominantly toward the south for these test locations. A particle track originating near DIAGONAL LINE moves through the TM-WTA to the southeast until intersecting the edge of the basin where it travels through the LTCU to enter the LCA. For the BASE-MME alternative, advective particle tracks in the vicinity of the PIN STRIPE

test show a more abrupt shift to the north with more movement through the LTCU compared to the BASE-USGSD particle tracks ([Figure 6-45](#) compared to [Figure 5-21](#)). Particle tracks in the central testing area are similar to the BASE-USGSD model with a slight change in trajectory to the east. Particles from the central testing area, for the BASE-MME calibration, also appear to be more shallow in the flow system ([Figure 6-45](#) compared to [Figure 5-21](#)). These changes to the particle tracks in the central testing area seem to result from modest changes in reference permeabilities and boundary heads.

Figure 6-41
Groundwater Fluxes Simulated by the UGTA Regional Model and the BASE-MME Alternative

Figure 6-42
Observed Versus Simulated Well Head - BASE-MME Alternative

April 26, 2006

baseR1_head_bndrysec.ps

Figure 6-44
Spatial Distribution of Weighted Residuals for the BASE-MME Alternative

Figure 6-45
Particle Tracks Starting Near the Underground Nuclear Tests
for the BASE-MME Alternative

6.5.3 BASE HFM with Death Valley Regional Flow System (DVRFS) Model Boundary Conditions (BASE-DVRFS)

The BASE HFM is calibrated with the recharge distribution, boundary heads, and boundary flows from the DVRFS model (Faunt et al., 2004). [Figure 6-46](#) shows the target and simulated flows across the four model boundaries, and [Figure 6-47](#) shows the measured and simulated hydraulic heads at the observation wells. The model agreement to the measured hydraulic heads is generally good (within approximately 1 m); however, model results at ER-5-3 #2 and WW-C and WW-C1 have considerably greater residuals than the BASE-USGSD model ([Figure 6-47](#)). The increased error at these LCA wells reflect higher heads on the north edge of the model boundary compared to the BASE-USGSD model ([Figures 6-48 and 5-3](#)). The calculated LCA water levels throughout the northern section of the BASE-DVRFS model are greater than the observed hydraulic head in the OAA and volcanic aquifers, thus indicating that the gradient between the basin-fill units and the LCA is upward rather than downward. The large residuals in the BASE-DVRFS model do not seem to impact lateral groundwater movement through the shallow alluvium and tuffs in the Frenchman Flat basin given the small residuals at Wells UE-5 PW-3, UE-5c WW, UE-5f, UE-11a, and UE-11b located on the perimeter of Frenchman Flat and the good match to the overall gradient in the alluvial basin ([Figure 6-49](#)).

The regional flux through the Frenchman Flat CAU flow model domain in the DVRFS model is less (by about 50 percent) than the flux observed in the UGTA regional model with the USGSD recharge model ([Table 6-4](#)). In addition to a considerable change in the magnitude of the flux, the orientation of the flux is also different ([Table 6-4](#)). The dominant flux into the model domain from the DVRFS model is along the eastern boundary, consistent with the UGTA regional model and the overall regional conceptual model of the LCA flow; however, the flux into the domain in the DVRFS model is more balanced on the east and north faces of the model than observed in the UGTA regional model ([Table 6-4](#)). The primary flux out of the model domain in the DVRFS model is westward, similar to the UGTA regional model. To accommodate the changes to the magnitude of the boundary flows, the reference permeability of the LCA was decreased and the permeability multipliers for the Rock Valley fault system were increased ([Table 6-5](#)). The fault permeability multipliers for LCA faults along the southern edge of the model domain (61, 63, 69, and 71) were increased to enhance flow to the southern model boundary ([Table 6-5](#)).

Changes to the reference permeability of the alluvium and volcanic HSUs were necessary during model calibration. These changes included increasing the reference permeability of the AA, OAA, TM-WTA, TM-LVTA, and the VCU compared to the calibrated reference permeability for the BASE-USGSD model ([Table 6-5](#)). The change in reference permeability for all of the HSUs was less than one-half of an order of magnitude ([Table 6-5](#)).

Particle tracks in the vicinity of the northern and central testing areas are shown in [Figure 6-50](#). Particle tracks originating near PIN STRIPE indicate a more easterly component of flow with advection into the shallow TM-WTA compared to the BASE-USGSD particle tracks ([Figure 5-21](#)). Particle tracks from DERRINGER, DIANA MOON, MINUTE STEAK, and MILK SHAKE are similar to the BASE-USGSD particle results. Particle tracks in the central testing area are similar to the BASE-USGSD model, but have a slightly more southern component, possibly resulting from the influence of boundary heads consistent with the more north-to-south direction of flow observed in the DVRFS model. The reversed gradient between the AA and LCA also seems to result in the particles being advected in the more shallow portion of the AA compared to the BASE-USGSD model.

Figure 6-46
Groundwater Fluxes Simulated by the DVRFS Regional Model and BASE-DVRFS Alternative

Figure 6-47
Observed Versus Simulated Well Head - BASE-DVRFS Alternative

Figure 6-48
Boundary Heads from Calibrated BASE-DVRFS Alternative

Figure 6-49
Spatial Distribution of Weighted Residuals for the BASE-DVRFS Alternative

Figure 6-50
Particle Tracks Starting Near the Underground Nuclear Tests
for the BASE-DVRFS Alternative

6.5.4 CPBA Hydrostratigraphic Framework Model with Chloride Mass-Balance (DRIA) Boundary Conditions (CPBA-DRIA)

The CPBA HFM is calibrated with the DRIA recharge, boundary heads, and boundary flows.

Figure 6-51 shows the target and simulated fluxes across the four model boundaries, and Figure 6-52 shows the observed and simulated water levels calculated by the CPBA-DRIA model. The model agreement to the measured hydraulic heads is generally within the estimated error at the target locations; however, model results at ER-5-3#2, WW-C and WW-C1, TW-3, and UE-5 PW-3 have considerably greater residuals than the BASE-USGSD model (Figure 6-52). The calculated hydraulic head in the LCA in the northern portion of the model is greater than the observed hydraulic head in the OAA and volcanic aquifers, thus indicating that the gradient between the basin-fill units and the LCA is upward rather than downward. Further, the calculated hydraulic head at UE-5 PW-3 is greater than the observed head, indicating that the hydraulic head in the LTCU is too high. Residuals for WW-4 and WW-4A in CP basin are also greater than in many of the Frenchman Flat CAU flow model alternatives as a result of smaller boundary head adjustments (Figure 6-53).

The spatial distribution of weighted residuals at the target wells is shown in Figure 6-54. The large error at NN-4 and WW-4A does not seem to impact lateral groundwater movement through the shallow alluvium in the Frenchman Flat basin given the small residuals at Wells UE-5c WW Upper, UE-5f, and UE-11b located on the perimeter of Frenchman Flat and the good match to the overall gradient in the alluvial basin.

Similar to the BASE-DRIA model, the CPBA-DRIA boundary conditions have a total regional flux that is about 40 percent larger than that for the CPBA-USGSD model (Table 6-4). This results in a higher calibrated value for the LCA reference permeability. Compared to the CPBA-USGSD calibration, the LCA reference permeability for this model is larger by a factor of about 1.4 (Table 6-5). The other large change in calibrated reference permeability values is for the VCU, LTCU, and OAA, which are also more permeable for this alternative than for the CPBA-USGSD alternative.

Figure 6-55 shows the particle tracks in the vicinity of the underground nuclear tests in the northern and central testing areas. Particle tracks in the northern testing area are significantly different than those from the CPBA-USGSD model (Figure 6-27). Particle tracks for DERRINGER, NEW POINT,

MILK SHAKE, DIANA MOON, and MINUTE STEAK travel to the east rather than to the south (Figure 6-55). This result seems to be driven by the higher hydraulic heads at UE-11a and UE-5 PW-3 compared to the lower calculated hydraulic head in the ER-5-3 well cluster (Figure 6-52). Particle tracks originating beneath the PIN STRIPE test indicate a more easterly water flow and that the particles stay in the more shallow TM-WTA, OAA, and AA HSUs rather than moving into the LCA (Figure 6-55). Particle tracks originating at the central testing area appear to travel further to the south (Figure 6-55). The enhanced advection to the east and depth of the particle migration in the flow system is indicative of the HSU permeability changes and possibly the increased fault permeability multiplier for fault 38, which runs north to south within the basin (see Appendix D for fault traces at ground surface).

Figure 6-51
Groundwater Fluxes Simulated by the UGTA Regional Model and the
Frenchman Flat Model - CPBA-DRIA Alternative

Figure 6-52
Observed Versus Simulated Well Head - CPBA-DRIA Alternative

April 26, 2006

cpba_R3_head_bndrysec.ps

Figure 6-54
Spatial Distribution of Weighted Residuals for the CPBA-DRIA Alternative

Figure 6-55
Particle Tracks Starting Near the Underground Nuclear Tests
for the CPBA-DRIA Alternative

6.5.5 CPBA HFM with Modified Maxey-Eakin (MME) Boundary Conditions (CPBA-MME)

The CPBA HFM is calibrated with the MME recharge, boundary heads, and boundary flows.

Figure 6-56 shows the target and simulated fluxes across the four model boundaries, and Figure 6-57 shows the observed and simulated water levels calculated by the calibrated CPBA-MME alternative. The model agreement to the measured hydraulic heads is generally good (within approximately 1 m); however, model results in the central testing area have slightly greater residuals than the BASE-USGSD model and smaller residuals at WW-C and WW-C1 (Figure 6-57). These results are very similar to the hydraulic heads calculated by the BASE-MME alternative (Figure 6-42). Calibrated boundary heads for the CPBA-MME alternative (Figure 6-58) are similar to the boundary heads for the CPBA-USGSD, BASE-USGSD, and BASE-MME models (Figures 6-14, 5-3, and 6-43), thus providing similar results for the calculated LCA hydraulic heads.

The spatial distribution of weighted residuals at the target wells is shown in Figure 6-59. Although heads tend to be slightly higher than the calibration targets, the overall gradient in the basin-fill aquifers and volcanic units is well matched by the CPBA-MME alternative.

As discussed for the BASE-MME alternative, the CPBA-MME boundary conditions result in a larger magnitude of regional flux through the Frenchman Flat CAU model domain (Table 6-4). This results in a larger value for the calibrated LCA reference permeability. Compared to the CPBA-USGSD calibration the LCA reference permeability is larger by a factor of about 2.5 for this alternative (Table 6-5). The BLFA is less permeable in the CPBA-MME calibration than CPBA-USGSD calibration, but this has no effect on the model goodness of fit because the calibration targets tend to be insensitive to the reference permeability of the BLFA. The PCU, OAA, TSA, and VCU HSUs have reference permeability values lower than those for the CPBA-USGSD alternative, while the LCA3 and LTCU have higher reference permeability values.

Figure 6-60 shows the particle tracks in the vicinity of the underground nuclear tests in the northern and central testing areas. As previously discussed, changes in particle track directions are typically due to the interplay among variations in boundary heads, differences in calibrated regional models from changes in recharge distributions, changes in calibrated reference permeability of HSUs, and changes in fault multiplier values. Small changes in the flow field heads can generate considerably

different flow paths. This is evident in the particle tracking results from the northern and central testing areas. In the northern testing area, particles starting at the PIN STRIPE test travel further to the north than observed in the CPBA-USGSD alternative (Figure 6-27). Compared to the same model, particles starting below DIAGONAL LINE travel north and east in the TM-WTA. Because the TM-WTA has a higher permeability compared to the OAA in the CPBA-MME calibration (Table 6-5), groundwater in northern Frenchman Flat tends to flow toward and through the TM-WTA as shown in Figure 6-27. Particle advection from the central testing area shows a more eastward direction of flow compared to the CPBA-USGSD model results (Figure 6-52). More eastward flow may be the result of decreasing the reference permeability of the VCU in the CPBA-MME model compared to the value used in the CPBA-USGSD model.

Figure 6-56
Groundwater Fluxes Simulated by the UGTA Regional Model and the
Frenchman Flat Model - CPBA-MME Alternative

Figure 6-57
Observed Versus Simulated Well Head - CPBA-MME Alternative

April 26, 2006

cpba_R1_head_bndrysec.ps

Figure 6-59
Spatial Distribution of Weighted Residuals for the CPBA-MME Alternative

Figure 6-60
Particle Tracks Starting Near the Underground Nuclear Tests
for the CPBA-MME Alternative

6.5.6 CPBA HFM with Death Valley Regional Flow System (DVRFS) Model Boundary Conditions (CPBA-DVRFS)

The CPBA HFM is calibrated with the calibrated recharge distribution, boundary heads, and boundary flows from the DVRFS model (Faunt et al., 2004). [Figure 6-61](#) shows the target and simulated fluxes across the four model boundaries, and [Figure 6-62](#) shows the observed and simulated water levels calculated by the calibrated BASE-USGSD and CPBA-DVRFS model. The model agreement to the measured hydraulic heads is generally good (within approximately 1 m); however, model results at ER-5-3#2 and WW-C and WW-C1 have considerably greater residuals than the BASE-USGSD model ([Figure 6-62](#)). The increased error in these LCA wells reflect considerably higher heads on the north edge of the model boundary ([Figure 6-63](#)) compared to both the BASE-USGSD and CPBA-USGSD models ([Figures 5-3 and 6-14](#)). The modeled LCA hydraulic heads throughout the northern portion of the CPBA-DVRFS model are greater than the observed hydraulic heads in the OAA and volcanic aquifers, thus indicating that the gradient between the basin-fill units and the LCA is upward rather than downward. These comparatively large residuals do not seem to impact lateral groundwater movement through the shallow alluvium and tuffs in the Frenchman Flat basin given the small residuals at Wells UE-5 PW-3, UE-5c WW, UE-5f, UE-11a, and UE-11b located on the perimeter of Frenchman Flat and the good match to the overall gradient in the alluvial basin ([Figure 6-64](#)). This model has a particularly good match to the vertical gradient through the OAA in the ER-5-3 well cluster (as evidenced by the residuals for ER-5-3 #3 and ER-5-3 shallow, [Figure 6-64](#)).

As discussed in [Section 6.5.3](#), the regional flux through the Frenchman Flat CAU flow model domain in the DVRFS model is less (by about 50 percent) than the flux observed in the USGSD model ([Table 6-4](#)). The smaller total flux through the CPBA-DVRFS models results in a lower value for the LCA reference permeability (an adjustment of $0.20 \text{ m}^2 \log k_0$). The log of the reference permeability for the BASE-DVRFS and CPBA-DVRFS alternatives differs by only 0.14 m^2 . Most of the shallow volcanic and basin-fill HSUs are also more permeable for this alternative than for the CPBA-USGSD alternative.

[Figure 6-65](#) shows the particle tracks in the vicinity of the underground nuclear tests in the northern and central testing areas. In the northern testing area, particles starting beneath the PIN STRIPE test travel south then further to the east for this calibrated model (compared with the CPBA-USGSD

alternative, [Figure 6-27](#)). For the other tests in the northern testing area particle travel southward through the OAA, BLFA, and AA in a similar trajectory to those observed for the CPBA-USGSD alternative. Particle advection from the central testing area shows a very slight eastward direction of flow compared to the CPBA-USGSD alternative.

Figure 6-61
Groundwater Fluxes Simulated by the DVRFS Regional Model and the
Frenchman Flat Model - CPBA-DVRFS Alternative

Figure 6-62
Observed Versus Simulated Well Head - CPBA-DVRFS Alternative

April 26, 2006

Figure 6-64
Spatial Distribution of Weighted Residuals for the CPBA-DVRFS Alternative

Figure 6-65
Particle Tracks Starting Near the Underground Nuclear Tests
for the CPBA-DVRFS Alternative

6.5.7 Alternative Approach To Boundary Head Adjustments

The starting points for the CAU model specified-head boundary conditions are the results from the UGTA regional model (SNJV, 2004d) and the DVRFS model (Faunt et al., 2004), as interpolated onto the Frenchman Flat flow model boundaries. Considerable uncertainty exists in translating regional-scale model heads to CAU-specific model boundaries because of the scale differences between the models and differences in grid resolution. The boundary condition uncertainty analysis presented in [Section 6.5](#) evaluates this uncertainty by incorporating many conceptual models of recharge and two different regional models. During the course of the CAU model calibrations, it was deemed necessary to adjust the boundary heads supplied by these regional models because of consistent errors in the regional model matches to observed heads. Boundary heads computed using the two regional models did not indicate significant vertical gradients in the vicinity of the model boundaries. Therefore, all boundary head corrections were made by adding or subtracting a constant head correction uniformly in the vertical dimension. The correction was made within a narrow band, and the correction linearly decayed to zero away from the correction area. However, when boundary heads were adjusted with this method, the adjusted heads were not consistent with head observations in the unadjusted portion of the same HSU. To assess the uncertainty in the flow fields generated using this boundary head modification approach, an alternative approach was used. This section details the approach and results from a calibration of the BASE-USGSD model using the alternative approach to the boundary head corrections.

6.5.7.1 Boundary Head Adjustments

Boundary heads adjustments were made at the three locations:

- CP basin: The UGTA regional model had a persistent 85-m deviation from the measured heads at Wells WW-4 and WW-4A just inside the western edge of the CAU model domain. Simulated heads in the area were close to 760 m amsl and head measurements in local wells were near 845 m amsl. Thus, if boundary heads in this part of the model had been used had been based on the results from the UGTA regional model, a consistent error of about 85 m would have resulted that was entirely a consequence of an inaccurate boundary condition assignment.
- Southern Yucca Flat: Head measurements at Wells WW-C and WW-C1 showed that water levels in this area are about 8 m lower than simulated heads from either regional model.

- Well TW-3: This well is close to the eastern edge of the model boundary and has a water-level measurement that is about 2.5 m lower than the model-calculated heads. A reduction of water levels in the central-eastern edge of the model boundary was necessary to match the available water-level measurements at this well.

Results from the BASE-USGSD and alternative models showed that while matching the LCA water levels observed at the eastern boundary at Well TW-3, the model simulated higher LCA water levels elsewhere in the model. This was most notable at Well ER-5-3 #2, underneath the Frenchman Flat basin, where the simulated water level was 3 to 11 m higher than the observed water level.

Additionally, the inability to match the observed water levels in southern Yucca Flat at WW-C and WW-C1 suggested that the boundary heads in this area may be introducing model errors.

To improve the calibration of the model to the heads in the LCA, the boundary heads in the LCA in this model are dropped uniformly on all faces of the model by the value needed to match the observed water level at well TW-3. For the BASE-USGSD model, this adjustment was found to be 2.6 m. Another LCA adjustment was then made at the northwestern model boundary to match the observed water level at WW-C1 (within the measurements' range of uncertainty). Boundary heads in the LCA were decreased at the west end of the north face of the model. The boundary head correction was linearly decayed to zero to the east (along the north face of the model) and south (along the west face of the model) from WW-C1. For the BASE-USGSD model, this boundary head adjustment introduced a drop for the LCA boundary heads by as much as 1.6 m along the north edge of the model domain. Finally, an adjustment was made for the boundary heads on the western model boundary only for the volcanic HSUs (above the LCA) in order to match the observed water levels in CP basin at WW-4 and WW-4A (TM-WTA completions). The adjustment was also decayed linearly to zero north and south from the WW-4 and WW-4A wells. The value of this adjustment was used as a calibration parameter. [Figure 6-66](#) shows the final calibrated boundary heads obtained using this boundary head modification approach for the BASE-USGSD model.

April 25, 2006

base_final_head_bndrysec.ps

6.5.7.2 Simulated Hydraulic Heads for the Alternative BASE-USGSD Flow Model

The simulated hydraulic heads produced by the calibrated model are shown in [Figure 6-67](#) for the water table. [Figures 6-68](#) and [6-69](#) show cross sections through the calibrated head fields. Horizontal hydraulic gradients within the northern and central testing areas of Frenchman Flat are fairly flat. Although hydraulic heads in the CP basin are approximately 100 m higher than those in Frenchman Flat, hydraulic gradients within each of these two areas are relatively flat, and most of the head loss between the CP basin and Frenchman Flat is predicted to coincide with the Cane Spring fault. The movement of water in the volcanic aquifers and confining units across the Cane Spring fault is one of the main sources of water for the OAA in northern Frenchman Flat. Hydraulic heads are slightly higher in the volcanic HSUs on the west side of the basin and decrease to east. The majority of head loss between the OAA and the LCA occurs over the thick LTCU.

Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast ([Figure 6-67](#)) indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction. This decrease of the hydraulic heads in the AA toward the southeast occurs as the LTCU and VCU thin toward the edges of the basin. In the central portion of Frenchman Flat basin water is originating from CP basin and flowing south through the OAA into the AA, which comprises the central portion of the basin. Heads in the AA are higher along the western flank of the basin and decrease to the east ([Figure 6-69](#)). Compared to the BASE-USGSD flow model, this model has considerably less water entering the basin-fill units from the Wahmonie Hills.

The latest measurements of head in the LTCU at Well ER-5-4 #2 indicated that heads in the LTCU were in excess of 750 m and rising. Although these measurements were not used directly in the calibration of the model because the head had failed to stabilize, they indicate that high-permeability intervals (in this case, within the LTCU) may function as confined aquifers and connect the deep part of the Frenchman Flat basin with areas of higher head to the west. Thus, a pressure barrier between the basin-fill HSUs and the regional aquifer (LCA) probably exists in the vicinity of the central testing area. In the alternative calibration of the BASE-USGSD model, this pressure barrier corresponds to the interface of the WCU and LTCU; however, hydraulic tests in the LTCU indicated the presence of a high-permeability zone of approximately 10^{-13} m^2 within the LTCU that was probably associated with a fractured welded interval within this largely zeolitized, nonwelded HSU. This zone in the LTCU is the actual location of the measured high heads and may be a more likely source of this zone of high pressure.

Figure 6-67
Water-Table Contours for the Alternative Calibration of the BASE-USGSD Model

Figure 6-69
West-East Cross Section of Simulated Heads at the Central Testing Area for the Alternative Calibration of the BASE-USGSD Model

6.5.7.3 Hydraulic Head and Flux Residuals

The groundwater fluxes calculated along the perimeter of the Frenchman Flat model domain with the UGTA regional model are compared to the fluxes calculated with the flow model in [Figure 6-70](#). The net fluxes calculated by the Frenchman Flat model are in reasonable agreement with the net fluxes calculated with the UGTA model along each of the boundaries considering the boundary head adjustments ([Figure 6-70](#)).

Simulated hydraulic heads are compared to the measured hydraulic heads that were used as calibration targets in [Figure 6-71](#), and plots of posted weighted residuals are shown in [Figure 6-72](#).

[Figure 6-71](#) shows that the simulated heads within Frenchman Flat generally agree with the measured heads to within the estimated uncertainties, but somewhat larger residuals exist at Wells ER-5-3 #2, WW-1, WW-5B and WW-5C, WW-C, and WW-C1.

- The simulated head at Well ER-5-3 #2 is higher than the heads measured in the LCA at this well. The hydraulic head at this location is very uncertain because water levels have not stabilized to allow determination of a static water level (see [Appendix A](#)). The simulated head at Well ER-5-3 #2 is considerably lower than heads measured in the overlying alluvium and tuffs at nearby Wells ER-5-3 and ER-5-3 #3.
- The simulated head at Well WW-1 is about 3 m higher than the head reported for this well (725.25 +/- 4.4 m), but within the error bounds that result from uncertainty in nearby land surface elevation and long pumping history at this location.
- The simulated hydraulic heads at Wells WW-5B and WW-5C are about 1 m too low and too high, respectively, compared to the measured heads (734.68 +/- 1.15 m and 729.68 +/- 1.29 m) at these wells. The relatively low hydraulic head reported for Well WW-5C relative to heads measured at Well WW-5B to the north and Well WW-5A to the south (730.91 +/- 1.14 m) indicates that there may be a local change in permeability or basin morphology that is not captured by the model. The excellent match of the model to measured head at WW-5A indicates that any gradient along the edge of the alluvial basin in this area is well fit by the model.
- Simulated heads in the LCA at Well WW-C and WW-C1 in the northwest corner of the Frenchman Flat model exceed the measured heads at these wells by about 2 m. Considering the additional changes to the boundary heads in this area of the model, it suggests that uncertainty in this portion of the HFM may be controlling the match to the observed head (see [Section 3.1](#) for additional description). The misfit at these wells is not expected to

significantly impact simulated groundwater movement through the alluvium and tuffs in the Frenchman Flat basin given the small residuals at Wells UE-5 PW-3, UE-5c WW, UE-5f, and UE-11b located on the perimeter of Frenchman Flat basin.

The plot of posted weighted residuals associated with the alternative calibration of the BASE-USGSD flow model is shown in [Figure 6-72](#). [Figure 6-72](#) shows that positive and negative weighted residuals are contained in each region of the flow model, indicating that there is little spatial bias in the simulated heads relative to the measured heads in the testing areas.

[Table 6-7](#) shows the metrics that characterize the goodness of fit associated with the alternative calibration of the BASE-USGSD flow model. The table lists the mean-weighted error, maximum and minimum weighted residuals, the error variances and standard deviations, and the contributions to the objective function associated with water-level and flux target data in each of the models. The negative mean-weighted residual calculated for the water levels in the alternative calibration of the BASE-USGSD flow model (-0.26 m) reflects that there is a slight bias in the model calibration from overestimating WW-C, WW-C1, ER-5-3 #2 and WW-1. As indicated by [Figure 6-73](#), the weighted residuals are approximately normally distributed around zero.

Figure 6-70
Groundwater Fluxes Simulated by the UGTA Regional Model and the
Alternative Calibration of the BASE-USGSD Flow Model

Figure 6-71
Observed Versus Simulated Well Head - Alternative Calibration of BASE-USGSD Flow Model

Figure 6-72
Spatial Distribution of Weighted Residuals for the Alternative BASE-USGSD Model Calibration

Table 6-7
Summary Calibration Statistics for Alternative Calibration
of the BASE-USGSD Model

Calibration Data	Number of Data Observations	Mean Weighted Error	Maximum Weighted Residual	Minimum Weighted Residual	Variance (m ² or kg ² /s ²)	Error Standard Deviation (m or kg/s)	Objective Function
Well	30	-0.262	2.17	-2.48	0.91	0.95	27.16
Flux	4	9.0×10^{-3}	3.9×10^{-2}	-1.5×10^{-3}	4.6×10^{-4}	2.1×10^{-2}	1.85×10^{-3}

Figure 6-73
Residual Histogram Alternative Calibration of the BASE-USGSD Flow Model

6.5.7.4 Estimated Hydraulic Parameters

The estimated hydraulic parameters from the model calibration include the permeabilities of the HSUs in the model, the calibrated values of anisotropy, as well as the permeability modification factors (*fperm*) associated with the faults in the model. [Table 6-8](#) lists the reference permeabilities, *fperm* factors, and anisotropy ratios estimated from the alternative calibration of the BASE-USGSD model. The permeability of the HSUs estimated from the calibration are shown as a function of depth and compared against permeability data from the Frenchman Flat and the general NTS area in [Figures 6-74 through 6-77](#). The vertical extent of each line on these figures indicates the extent of this HSU in the flow model.

The estimated permeabilities of the AA and OAA HSUs in the alternative calibration of the BASE-USGSD flow model are compared to permeability measured in Frenchman Flat and in the general vicinity of the NTS in [Figure 6-74](#). The data for the NTS area include stream channel, floodplain, alluvial fan and playa deposits from Yucca Mountain, the Amargosa Desert, and basins north of the NTS, as well as from Yucca Flat. The data from Frenchman Flat include data from the alluvium at Well ER-5-3 #3 near the northern testing area; Wells RNM-1, RNM-2, RNM-2s, and ER-5-4 near the central testing area; and Wells WW-5A, WW-5B, and WW-5C slightly to the south of the central testing area. The estimated permeabilities are in the center of the data range. This model calibration was achieved by adjusting both the depth-decay coefficient for the basin-fill HSUs and the anisotropy of the units.

The depth-decay coefficient used for the BASE-USGSD model calibration ([Section 5.5](#)) was set at the mean (0.0056 m^{-1}) reported by IT (1996d) ([Table 3-6](#)), subsequent to this model calibration re-analysis of the NTS area alluvium permeability data indicated that the decay coefficient may be somewhat smaller (0.0021 m^{-1}) ([Appendix E](#)), indicating less permeability decrease with depth than reported by IT (1996d). To improve the model fit to the observed data, the depth-decay coefficient used for the calibration documented here was decreased to 0.0014 m^{-1} , which is within the 95 percent confidence interval of the analysis reported in [Appendix E](#); however, it is considerably smaller than expected based on analysis of ER-5-4 #2 flow logs (0.01 m^{-1}) ([Section 3.6.3.1](#)). Thus, the calibration of the alternative boundary head correction approach for the BASE-USGSD model has less permeability decrease with depth than in the BASE-USGSD model presented in [Section 5.5](#).

As discussed in [Section 3.6.3.2](#), decrease of permeability with depth imparts a modest anisotropy on the HSU permeability. To compensate for the higher horizontal hydraulic conductivity and less decrease in permeability with depth in the AA, OAA, and playa confining units, the anisotropy of these basin-fill HSUs was increased from 2 in the BASE-USGSD model ([Section 5.5](#)) to a calibrated value of 69.4 (k_h/k_v). This value of 69.4 is within the range of anisotropy ratios reported for the MWAT at RNM-2s (see [Section 3.6.2.3.4](#) for a complete discussion of anisotropy).

The estimated hydraulic conductivity of the LCA and LCA3 HSUs are compared to the permeability data for the carbonate aquifer in [Figure 6-75](#). The data include measurements both on and adjacent to the NTS, and data from the vicinity of Frenchman Flat at Wells WW-C, WW-C1, TW-3, and ER-5-3 #2. The data suggest a more rapid reduction in intrinsic permeability with depth than was assumed in the model, but some of this apparent reduction could be due to heterogeneity associated with the diverse structural settings in which the data were measured. The estimated permeability for both the LCA and LCA3 are in good agreement with the data.

The estimated permeability of HSUs that are considered to be confining units in Frenchman Flat are compared to the permeability measured on tuffs from Yucca Mountain and other older tuffs at federal facilities north of the NTS ([Figure 6-76](#)). The estimated permeability of the LTCU, UTCU, and VCU are near the low end of the measured permeability, but within the field measurements. The estimated permeability of the WCU is in the center of the observed range based on field measurements. The calibrated anisotropy for these units is between 3.6 and 10 (k_h/k_v), with the WCU having the greatest anisotropy ratio and the LTCU having the smallest. The permeability estimated for the WCU may reflect the presence of numerous lava and breccia flows in this HSU in the western part of the model, which could make the WCU more conductive than other HSUs that are also classified as confining units (BN, 2005a, p. 4-19). In view of its diverse assemblage of rock types, it may be reasonable that the permeability of the WCU is intermediate between that of aquifers and true confining units. It is not surprising that the calibrated permeability values are at the lower end of the hydraulic test data for most of the confining units given that most hydraulic testing programs focus on the most transmissive intervals for pumping-scale aquifer tests.

Volcanic rocks that are generally considered to be aquifers in Frenchman Flat include welded tuffs (TSA and TM-WTA), vitric nonwelded tuffs (TM-LVTA and LVTA), and basaltic lava flows (BLFA). Flow through the welded tuffs and basalts is probably through fractures, whereas flow through the vitric, nonwelded tuffs, is probably through the matrix pores. The estimated permeability of these HSUs are compared to NTS data for welded tuffs, nonwelded tuffs, and lavas taken primarily from Yucca Mountain and Pahute Mesa and to data measured in the Frenchman Flat area at ER-5-3 (Figure 6-77). Permeability measurements within the Frenchman Flat CAU model area were also measured at Wells WW-4 and WW-4A in CP basin. A comparison with the data indicates that the model permeability estimates for the Timber Mountain tuffs (TM-WTA and TM-LVTA), TSA, and LVTA are in good agreement with the NTS area data. The intrinsic permeability estimates for the BLFA are difficult to evaluate given that there are no site-specific data; however, basalt flows like the ones in northern Frenchman Flat should have little connected permeability (see Section 3.6.1).

Table 6-8 indicates that the estimated $fperm$ factors in the alternative calibration of the BASE-USGSD model spanned several orders of magnitude and included values both considerably greater than and considerably less than 1. The lowest $fperm$ factors were estimated for faults associated with the CP Hogback in the northwest part of the model (faults 11, 12, and 14-16) and for the Cane Spring fault (fault 3), which separates the CP basin from Frenchman Flat basin. Conversely, faults in the LCA associated with the Rock Valley fault system (faults 21, 33, 34, 57, and 58) and faults 17 and 39 had estimated $fperm$ factors that indicated these faults were significant conduits for groundwater (Table 6-8).

In this model calibration, the Cane Spring fault has been further subdivided to allow the high heads at the flow model boundary and in CP basin to propagate through the region beneath CP Hogback to supply water to the Frenchman Flat basin. The subdivision allows for the volcanic portion of fault 3 to be opened in a narrow window north of fault 17 and south of fault 12. The permeability multiplier for this portion of the fault is 62.1, thus allowing the water to move from CP basin to Frenchman Flat basin.

The definition of faults 17 and 39 was modified to separate the fault nodes in the LCA from the fault nodes in the tuffs to differentiate the fault properties as a function of HGU. The LCA nodes in these faults were then assigned a relatively high-permeability multiplier to enhance drainage in this portion

of the LCA, thus maintaining the simulated heads low enough to lower modeled heads in southern Yucca Flat at WW-C1 to improve the model agreement to the observations. Further, fault 39 is defined as two separate faults north and south from where it is intersected by fault 17 (see [Appendix D](#)). In the volcanic aquifers, the northern portion of this fault is assigned a higher-permeability multiplier (447), while the southern portion is assigned a lower multiplier (0.004). This was necessary to maintain the hydraulic heads in the OAA of the northern testing area.

The final permeabilities in the alternative calibration of the BASE-USGSD flow model depend on the values estimated for the reference permeability of the individual HSUs, the assumed depth-decay coefficients applied to the HSUs, and the permeability changes imposed by the presence of the faults, as implemented through the *fperm* factors ([Table 6-8](#)). [Figure 6-78](#) shows the calibrated permeability at the water-table surface, and [Figures 6-79 and 6-80](#) show west-east cross sections of calibrated permeability values at the central and northern testing areas, respectively. The combined effects of the spatial distribution of HSUs, the depth decay in permeability, and the overprint of permeability changes associated with faults serve to create a complex distribution of permeability within the flow model. The distribution of permeability in plan view ([Figure 6-78](#)) shows that the central part of the Frenchman Flat basin is surrounded on the north, east, and south by a zone of low permeability that corresponds to the confining units that line the deepest parts of the basin and rise up along the flanks of the basin to intersect the water table ([Figures 6-79 and 6-80](#)). This zone of lower permeability rock separates the basin from the regional flow system that is dominated by much more permeable LCA that lies outside of and beneath the Frenchman Flat basin. The higher permeability estimated for the WCU compared to the other confining units ([Figure 6-76](#)) allows a significantly stronger hydraulic connection between the central part of Frenchman Flat and the CP basin and Wahmonie Hills to the west ([Figure 6-79](#)).

Table 6-8
Summary of Reference Permeability Values
and Fault Permeability Multipliers for the Alternative Calibration
of the BASE-USGSD Flow Model
 (Page 1 of 3)

HSU	Permeability at Ground Surface - $\log k_0$ (m ²)	Calibrated Anisotropy Ratios (k_h/k_v)
AA	-11.41	22.90
PCU	-14.50	22.90
BLFA	-12.00	1
OAA	-11.96	22.90
PCU1L	-11.00	22.90
PCU1U	-11.00	22.90
TM-WTA	-9.10	13.32
TM-LVTA	-9.25	13.32
UTCU	-12.00	13.32
TSA	-10.09	13.32
LVTA	-10.50	13.32
LTCU	-13.10	3.60
WCU	-11.37	10.00
VCU	-12.81	5.34
LCA3	-11.00	1
UCCU	-13.50	13.32
LCA	-10.93	1
Fault Number	Fault Permeability Multipliers	
1	0.3	
2	345.30	
3	5.51E-07	
4	500.0	
5	500.0	
6	10.0	
7	1.0	
8	100.0	
9	10.0	
10	100.0	
11	1.0E-05	
12	1.0E-05	
13	10.0	
14	1.0E-05	
15	1.0E-05	
16	5.0E-04	
17	1.32	
18	122.78	
19	150.0	

Table 6-8
Summary of Reference Permeability Values
and Fault Permeability Multipliers for the Alternative Calibration
of the BASE-USGSD Flow Model
 (Page 2 of 3)

Fault Number	Fault Permeability Multipliers
20	150.0
21 ^a	400.0
22	1.0
23	1.0
24	1.0
25	1.0
26	10.0
27	10.0
28	10.0
29	10.0
30	200.0
31	10.0
32	10.0
33 ^a	6.24
34 ^a	1.56
35	1.0
36	1.0
37	1.0
38	5.0
39s ^b	4.44E-03
40	0.1
41	0.1
42	0.1
43	0.1
44	0.1
45	0.1
46	14.93
47	98.15
48	0.1
49	0.1
50	0.1
51	4.66E-02
52	0.1
53	0.1
54	0.1
55	0.1
56	0.1
57 ^a	31.1

Table 6-8
Summary of Reference Permeability Values
and Fault Permeability Multipliers for the Alternative Calibration
of the BASE-USGSD Flow Model
(Page 3 of 3)

Fault Number	Fault Permeability Multipliers
58 ^a	112.8
59	3.6
60	3.6
61	2.45
62	3.65
63	10.0
64	3.6
65	3.6
66	3.6
67	3.6
68	3.6
69	3.0
70	3.6
71	3.6
72	2.37
73	3.6
74	1.0
75 ^c	1.02
76	1.0
78	1.0
171 ^d	100.38
39n ^b	446.96
39l ^e	339.08
34l ^f	16.60
33l ^f	18.67
3t ^g	62.15

Notes: Faults not shown have a permeability multiplier value that is close to 1 (0.95 to 1.05).

^aThe Rock Valley fault system (faults 21, 33, 34, 57, and 58) have different properties only through the LCA. These faults are neutral throughout all other HSUs.

^bFaults 39n and 39s are, respectively, the northern and southern parts of fault 39 defined above the LCA in the volcanic HSUs.

^c Fault 75 is the northern part of the Cane Spring fault (fault 3).

^d Fault 171 is the part of fault 17 in the LCA. It has a relatively high-permeability multiplier to enhance drainage in that part of the LCA, thus maintaining the simulated heads low enough to match the observed LCA water levels in southern Yucca Flat at WW-C1.

^e Fault 39l includes all the nodes in fault 39 in the LCA only.

^f Faults 33l and 34l are the nodes in faults 33 and 34 in the LCA only.

^g Faults 3t is the top part of fault 3 (above the LCA).

Figure 6-74
Estimated Versus Measured Intrinsic Permeability of AA for the
Alternative Calibration of the BASE-USGSD Model

Figure 6-75
Estimated Versus Measured Intrinsic Permeability of the LCA
for the Alternative Calibration of the BASE-USGSD Model

Figure 6-76
Estimated Versus Measured Intrinsic Permeability of Aquitard HSUs
for the Alternative Calibration of the BASE-USGSD Model

Figure 6-77
Estimated Versus Measured Intrinsic Permeability of VAs
for the Alternative Calibration of the BASE-USGSD Model

Figure 6-78
Calibrated Permeability at the Water Table for the
Alternative Calibration of the BASE-USGSD Model

Figure 6-79
West-East Section of Calibrated Permeability at the Central Testing Area for the Alternative Calibration of the BASE-USGSD Model

Figure 6-80
West-East Section of Calibrated Permeability at the Northern Testing Area for the Alternative Calibration of the BASE-USGSD Model

6.5.7.5 Estimated Groundwater Flow Paths

Figure 6-81 shows the trajectory of particles initially located near test locations in the northern and central testing areas. The particle tracks are colored based on HSU and reflect the advective water movement through the CAU model.

Near the northern test area, particle movement reflected the complex distribution of permeabilities in northern Frenchman Flat. Particles starting beneath the NEW POINT, DERRINGER, DIANA MOON, and MINUTE STEAK test locations indicate movement to the northeast through the OAA and tuffs and to the southeast through the OAA into the AA (Figure 6-81). The flow conditions in the vicinity of these tests are not enhanced due the properties of nearby faults (see faults 35, 36, 45, 50, 51, 54 and 55), all of which have *fperm* factors of 1 or 0.1 (Table 6-8). The groundwater flow paths seem to be dominated by the influx of water along the northwestern edge of the Frenchman Flat basin-fill units from water moving from CP basin across the Cane Spring fault in the volcanic HSUs.

The trajectory of particles starting near the PIN STRIPE test is eastward within the TSA and LVTA (Figure 6-81). As shown in Figure 6-78, the TSA and LVTA create an arcuate band of higher permeability where they intersect the water table along the northern flank of the Frenchman Flat basin. This band of higher permeability creates a strong hydraulic connection in the model between the higher hydraulic heads in the CP basin to the west and locations beneath the PIN STRIPE test in the northern testing area. The higher hydraulic heads adjacent to the western part of the CP basin (Figures 6-67 and 6-68) cause groundwater to flow eastward through the LTCU toward a major fault in the Rock Valley fault system (fault 33) and enter the LCA.

In the central testing area of Frenchman Flat, groundwater flow is substantially less complex than in the northern testing area. The movement of particles initially located near the water table near the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area will be through the alluvium toward the southeast. Eventually, these particles will encounter the Rock Valley fault system and exit the flow system along the southern part of the western boundary of the model.

Figure 6-81
Particle Tracks Starting Near the Underground Nuclear Tests for the
Alternative Calibration of the BASE-USGSD Model

6.5.8 Summary of Model Boundary Condition Uncertainty Analysis

This section presents results from seven flow models where boundary condition uncertainty was evaluated. The two alternative HFMs that are most distinctly different based on calibration with the USGSD boundary conditions (BASE and CPBA HFM alternatives) were combined with the DRIA-, MME-, and DVRFS-boundary conditions. These alternatives were used to bound the uncertainty in the CAU flow system resulting from variations in boundary conditions that were determined through the use of two regional groundwater flow models. Because areal recharge provides limited water flux into the top of the Frenchman Flat CAU flow model domain, differences among the boundary heads and boundary fluxes dominated the effects of boundary condition uncertainty on the flow field. An additional analysis documenting an alternative approach to boundary head adjustments was used to evaluate additional uncertainty in the calibrated flow field arising from the calibration approach.

There is an almost unbounded range of combinations of alternative boundary conditions that could be proposed and evaluated through flow calibration and sensitivity analysis. The combination of the calibration results of [Section 5.0](#) and the uncertainty evaluation of [Section 6.0](#) likely bound the range of expected model responses and particle track results. These flow model results form a foundation that will be carried forward into transport modeling to evaluate the significance of model conceptualization and pathway variation on the location of the contaminant boundary.

Results from the MME boundary conditions using the BASE HFM and CPBA HFM are most similar to the BASE-USGSD model and provided the best overall match to the hydraulic head calibration data ([Table 6-6](#)). The simulated head in both models at Well ER-5-3 #2 is lower than heads measured in the overlying alluvium and tuffs at nearby Wells ER-5-3 and ER-5-3 #3. This signifies that the observed downward head gradient between the alluvium and LCA in northern Frenchman Flat is captured in these models. Groundwater flow paths near NEW POINT, DIAGONAL LINE, DIANA MOON, and MINUTE STEAK test locations indicate primarily southward flow. The groundwater flow path at the northern edge of Frenchman Flat basin appeared to be dominated by eastward advection. Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast in both models, as was observed in the BASE-USGSD model, indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction.

Results using the DVRFS regional model-derived boundary conditions using the BASE HFM and CPBA HFM are the most dissimilar to the BASE-USGSD model. These models provided as good a fit as other models to both the hydraulic head at the observations and boundary flows (Table 6-6). However, the simulated head in LCA for both models was higher than heads measured in the overlying alluvium and tuffs at the ER-5-3 well cluster. This indicates an upward head gradient between the alluvium and LCA, contrary to the both hydraulic head data and the conceptual understanding of the Frenchman Flat CAU flow system (Section 3.0). Lateral groundwater flow paths in the volcanic HSUs and basin-fill units did not appear to be impacted by the upward gradient as evidenced by the good match of the model to the hydraulic head data, and the randomly positive and negative residuals throughout the Frenchman Flat basin. Groundwater flow paths in the central testing area are similar to models with the USGSD- and MME-boundary conditions. The groundwater flow path at the northern edge of Frenchman Flat basin appeared to be dominated by eastward advection, as observed for the USGSD- and MME-model calibrations, but flow paths simulated using the DVRFS-boundary conditions indicated water conductance was from the LVTA into the TM-WTA rather than into the LTCU.

Given the consistency in groundwater flow paths generated by both the DVRFS- and MME-boundary conditions in the BASE HFM and CPBA HFM, the variation between these HFMs when they are calibrated using the DRIA boundary conditions is striking. For the CPBA-DRIA, the simulated head in LCA was higher than hydraulic head measured in the overlying alluvium and tuffs at the ER-5-3 well cluster. This indicates an upward head gradient between the alluvium and LCA, contrary to the local data and the conceptual understanding of the Frenchman Flat CAU flow system (Section 3.0). For the BASE-DRIA calibration, there is a slight downward gradient in the vicinity of the ER-5-3 well cluster between the alluvium and LCA. Groundwater flow paths simulated by the BASE-DRIA model in the northern testing area are similar to those observed in the BASE-DVRFS model. Groundwater flow paths in the central testing area for both the BASE-DRIA and CPBA-DRIA models indicate lateral flow in the alluvium to the southeast.

An alternative approach to boundary head modifications used to evaluate the BASE-USGSD model demonstrates that flow paths are similar to those generated during the boundary condition uncertainty analysis using alternative recharge distributions, boundary heads, and boundary flows. To improve the model simulation of observed heads in the LCA, a hydraulic connection in the volcanic units of

CP basin and Frenchman Flat basin was established to route the water from areas of higher head (CP basin) into the basin-fill material of Frenchman Flat basin. Heads on the boundary adjacent to CP basin were modified to greater than 1,000 m amsl, which is significantly higher than the observed head in these units within CP basin, to establish and maintain hydraulic heads in Frenchman Flat basin. Although the calibrated HSU permeabilities and hydraulic head simulations match the data very well, this large change in boundary heads suggests that this connection may not be plausible. Advective particle tracks show a strong eastern component of flow in the northern testing area. Particle trajectories in the central testing area were very similar to those observed in other calibrated flow models. The general orientation of flow paths appears to be within the range of the other calibrated flow models that were used to evaluate either boundary condition, HFM, or discrete uncertainty. Further consideration will be given to this flow model during transport calculations to determine whether the flow field demonstrates different transport behavior within the time of interest given reasonable transport parameters.

Overall, the boundary condition uncertainty analyses indicate that groundwater flow paths in the central testing area are similar among the calibrated flow models, but that the flow paths in the northern testing area are more sensitive to changes in boundary conditions than changes in HFM.

6.6 Constant Permeability with Depth Uncertainty Analysis

A review of the literature demonstrates that depth decay in permeability or hydraulic conductivity has been recognized for decades by investigators in many geologic environments and has also been routinely adopted in groundwater modeling studies. This reduction in permeability with depth has a sound technical basis. Initial depth-decay relationships based on site-specific data are valuable starting points for model parameterization that can then be modified during model calibration. An in-depth literature review and discussion of the technical basis for permeability depth decay is presented in [Appendix B](#).

For the Frenchman Flat CAU flow model, depth decay was applied to all alluvial, volcanic, and carbonate units. Mean depth-decay coefficients reported by IT (1996d) for alluvial, carbonate, and volcanic aquifers were selected for use in the Frenchman Flat flow model ([Table 3-6](#)). The larger the depth-decay coefficient, the more rapidly hydraulic conductivity (or intrinsic permeability in the case of the FEHM-based CAU-scale models) decreases with depth. Thus, based on the depth-decay

coefficients in [Table 3-6](#), the permeability of the alluvium decreases more rapidly with depth than that of either the volcanic or carbonate rocks.

Sufficient site-specific data to evaluate depth decay in permeability do not exist for HSUs other than the AA and OAA, and these data do not clearly support the use of depth decay in the alluvium of Frenchman Flat ([Figure 3-10](#)). Although the permeability data from Frenchman Flat alone do not clearly support the use of depth decay in permeability, SNJV (2004d) reported that some of the apparent scatter in hydraulic conductivity measurements was due to differences in the interpretation of the mean depths of the test intervals, and to differences in the assumptions and methods used to interpret the test response. Thus, at least some of the scatter in the AA data from Frenchman Flat represents uncertainty associated with the test interpretations and not heterogeneity associated with depositional processes. As discussed in [Section 3.6.3.1](#), the continued use of depth decay for the permeability of the AA in Frenchman Flat is supported by an analysis of borehole flow log data from Well ER-5-4, which demonstrates that depth decay is required to explain the vertical variations in flow rates measured at that well.

The fact that some of the scatter in the Frenchman Flat permeability data for the AA is attributable to uncertainty surrounding assumptions in the analysis methods, rather than to heterogeneity, combined with strong evidence from the re-analysis of the NTS data and the ER-5-4 flow log, demonstrates that depth decay should be considered for the AA (and other HSUs) in Frenchman Flat. For these reasons, the conceptual model for the flow system in Frenchman Flat continues to regard depth decay (with the decay coefficients listed in [Table 3-6](#)) as a likely conceptual model; however, this section documents a Frenchman Flat CAU model calibration that eliminates depth decay in the AA and OAA HSUs in order to understand the impact of the depth-decay model parameterization on the calculated flow paths in the Frenchman Flat CAU model.

6.6.1 Calibration Approach

The BASE-USGSD flow model documented in [Section 5.5](#) was selected as the starting point for a calibration with constant permeability assigned to the AA and OAA HSUs. These HSUs were selected because of the scatter in the site-specific data and because these units will be important in the transport analysis for the Frenchman Flat CAU. The calibrated parameters for the BASE-USGSD model were assigned to all HSUs in this model, but the depth-decay coefficients for the AA and OAA

were set to zero, thus eliminating any change in permeability with depth in the model. The model calibration proceeded using the same approach described in [Section 5.0](#). While maintaining the calibrated values from the BASE-USGSD model for the volcanic units and carbonate aquifers, model calibration was initially focused on only adjusting the permeability of the AA and OAA HSUs. However, attempts to maintain the permeability of these units within the range of the observed data while matching observed heads proved to be unsuccessful. For these model analyses, hydraulic heads in the AA were consistently below the observed head by approximately 4 m. Additional calibration attempts were focused on assigning a reasonable value of anisotropy to the AA and OAA; however, these model calibrations also failed to maintain high-enough heads in the basin-fill units (approximate error was 2 m). After both of these approaches proved unsuccessful, a full calibration was initiated where the permeability of all HSUs and all faults were carefully examined and adjusted manually or by using PEST in a piecemeal fashion. The sections below document the calibration of the BASE HFM with the USGSD boundary conditions with no depth decay in the AA and OAA, but using depth decay in the other HSUs within the flow model domain.

6.6.1.1 Simulated Hydraulic Heads for the BASE-USGSD with No Depth Decay in the AA and OAA Flow Model

The simulated hydraulic heads produced by the calibrated model are shown in [Figure 6-82](#) for the water table. [Figures 6-83](#) and [6-84](#) show cross sections through the calibrated head fields. Horizontal hydraulic gradients within the northern and central testing areas of Frenchman Flat are fairly flat. Although hydraulic heads in the CP basin are approximately 100 m higher than those in Frenchman Flat, hydraulic gradients within each of these two areas are relatively flat, and most of the head loss between the CP basin and Frenchman Flat coincides with the Cane Spring fault. The movement of water in the volcanic aquifers and confining units across the Cane Spring fault is one of the main sources of water for the OAA in northern Frenchman Flat. Hydraulic heads are slightly higher in the volcanic HSUs on the west side of the basin and decrease to east. The majority of head loss between the OAA and the LCA occurs over the thick LTCU. The observations are consistent with the BASE-USGSD flow model documented in [Section 5.5](#).

Simulated hydraulic heads in the central part of Frenchman Flat decline gently toward the southeast ([Figure 6-82](#)), indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction. This decrease of the hydraulic heads in the AA toward the southeast occurs as the

LTCU and VCU thin toward the edges of the basin. In the central portion of Frenchman Flat, the heads are higher in the WCU on the western edge of the model, likely indicating throughflow from the Wahmonie Hills ([Figure 6-84](#)). These higher heads decrease along the west flank of the basin-fill units as a result of a fault and the pinching out of the WCU into LTCU ([Figure 6-84](#)).

Figure 6-82
Water-Table Contours for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-84
West-East Cross Section of Simulated Heads at the Central Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

6.6.1.2 Hydraulic Head and Flux Residuals

The groundwater fluxes calculated along the perimeter of the Frenchman Flat model domain with the UGTA regional model are compared to the fluxes calculated with the CAU flow model in [Figure 6-85](#). The net fluxes are in good agreement along each of the boundaries ([Figure 6-85](#)).

Simulated hydraulic heads are compared to the measured hydraulic heads that were used as calibration targets in [Figure 6-86](#), and plots of posted weighted residuals are shown in [Figure 6-87](#).

[Figure 6-86](#) shows that the simulated heads within Frenchman Flat generally agree with the measured heads to within the estimated uncertainties, but somewhat larger residuals exist at Wells ER-5-3 #2, WW-5A, WW-5B, WW-5C, WW-C, WW-C1, and UE-5c Water Well (Upper and Lower).

- The simulated head at Well ER-5-3 #2 is higher than the heads measured in the LCA at this well. The hydraulic head at this location is very uncertain because water levels have not stabilized to allow determination of a static water level (see [Appendix A](#)). The simulated head at Well ER-5-3 #2 is, however, lower than heads measured in the overlying alluvium and tuffs at nearby Wells ER-5-3 and ER-5-3 #3. This signifies that the observed downward head gradient between the alluvium and LCA in northern Frenchman Flat is captured in the model, but that its magnitude maybe less than the observed vertical gradient.
- The simulated hydraulic heads at Wells WW-5A, WW-5B, and WW-5C are about 1 m too low or too high compared to the measured heads at these wells. The relatively low hydraulic head reported for Well WW-5C relative to heads measured at Well WW-5B to the north and Well WW-5A to the south suggests that local changes in permeability may be important in this area of the model. The low simulated head at WW-5A indicates that any gradient along the edge of the alluvial basin into the LCA may be overpredicted in this model.
- Simulated heads in the LCA at Well WW-C and WW-C1 in the northwest corner of the Frenchman Flat model exceed the measured heads at these wells by several meters. This portion of the model is structurally complex and is not well represented by the flow model. Model boundary heads have not been modified in the area adjacent to WW-C and WW-C1 in this calibration and may contribute to the error in this portion of the model.
- The residuals at Well UE-5c WW in the Upper and Lower completion suggest that the heads along the western flank of the alluvial basin are being overpredicted. The Lower completion of Well UE-5c WW is in the LTCU and this high residual may be indicative of the need to pressurize the LTCU to maintain the heads in the AA and OAA higher than the LCA, which lies beneath the LTCU.

The plot of posted weighted residuals associated the BASE-USGSD flow model with no permeability depth decay in the AA and OAA is shown in [Figure 6-87](#). [Figure 6-87](#) shows that weighted residuals along the western edge of the alluvial basin tend to be high and that residuals at the north edge of the alluvial basin are low (UE-11a and UE-11b). This suggests that there may be a spatial bias in the simulated heads relative to the measured heads.

[Table 6-9](#) shows the metrics that characterize the goodness of fit associated with the calibration of the BASE-USGSD flow model with no permeability depth decay in the AA or OAA. The table lists the mean-weighted error, maximum and minimum weighted residuals, the error variances and standard deviations, and the contributions to the objective function associated with water-level and flux target data for the model. The negative mean-weighted residual calculated for the water levels (-0.54 m) reflects that there is a slight bias in the model calibration from overestimating WW-C, WW-C1, ER-5-3 #2 and UE-5c WW. As indicated by [Figure 6-88](#), the weighted residuals are approximately normally distributed around zero.

Figure 6-85
Groundwater Fluxes Simulated by the UGTA Regional Model and the
Calibration of the BASE-USGSD Flow Model with No Permeability Depth Decay in the AA and OAA

Figure 6-86
Observed Versus Simulated Well Head - Calibration of the BASE-USGSD Flow Model
with No Permeability Depth Decay in the AA and OAA

Figure 6-87
Spatial Distribution of Weighted Residuals for the BASE-USGSD Model Calibration
with No Permeability Depth Decay in the AA and OAA

Table 6-9
Summary Calibration Statistics for the Calibration of the BASE-USGSD Flow Model
with No Permeability Depth Decay in the AA and OAA

Calibration Data	Number of Data Observations	Mean Weighted Error	Maximum Weighted Residual	Minimum Weighted Residual	Variance (m ² or kg ² /s ²)	Error Standard Deviation (m or kg/s)	Objective Function
Well	30	-0.54	7.199	-9.355	7.666	2.769	230.0
Flux	4	1.053	11.27	-5.878	41.00	6.403	164.0

Figure 6-88
Residual Histogram Calibration for the BASE-USGSD Flow Model with
No Permeability Depth Decay in the AA and OAA

6.6.1.3 Estimated Hydraulic Parameters

The estimated hydraulic parameters in the model calibration include the reference and constant permeabilities of the HSUs in the model, the calibrated values of anisotropy, as well as the permeability modification factors (*fperm*) associated with the faults in the model. [Table 6-10](#) lists the reference permeabilities and *fperm* factors estimated from the BASE-USGSD with no permeability depth decay in the AA and OAA. The permeability of the HSUs estimated from the parameter calibration are shown as a function of depth and compared against intrinsic permeability data from Frenchman Flat and the general NTS area in [Figures 6-89 through 6-92](#). The vertical extent of each line on these figures indicates the range of depth for this HSU in the flow model.

The estimated permeabilities of the AA and OAA with no permeability decay with depth in the calibration of the BASE-USGSD flow model are compared to permeability measured in Frenchman Flat and in the general vicinity of the NTS in [Figure 6-89](#). The data from Frenchman Flat include data from the alluvium at Well ER-5-3 #3 near the northern testing area; Wells RNM-1, RNM-2, RNM-2s, and ER-5-4 near the central testing area; and Wells WW-5A, WW-5B, and WW-5C slightly to the south of the central testing area. The estimated permeabilities are at the low end of the data range. The calibrated permeability value for the OAA matches the one data point measured in this unit at ER-5-3 #3. The calibrated permeability for the AA falls in the center of the MWAT data from the ER-5-4 well cluster. This model calibration was achieved, in part, by adjusting the anisotropy of the basin-fill HSUs.

Model simulations without changes to the anisotropy of the AA and OAA were unable to match observed hydraulic heads in these HSUs. The anisotropy of these basin-fill HSUs was increased during model calibration from 2 in the BASE-USGSD model to 125 (k_h/k_v). This value is within the range of anisotropy ratios reported for the MWAT at RNM-2s (see [Section 3.6.2.3.4](#) for a complete discussion of anisotropy).

The estimated hydraulic conductivity of the LCA and LCA3 HSUs are compared to the permeability data for the carbonate aquifer in [Figure 6-90](#). The data include measurements both on and adjacent to the NTS, and data from the vicinity of Frenchman Flat at Wells WW-C, WW-C1, TW-3, and ER-5-3 #2. The data suggest a more rapid reduction in intrinsic permeability with depth than was assumed in the model, but some of this apparent reduction could be due to heterogeneity associated

with the diverse structural settings in which the data were measured. The estimated permeability for both the LCA and LCA3 are in good agreement with the data.

The estimated permeability of HSUs that are considered to be confining units in Frenchman Flat are compared to the permeability measured on pre-Crater Flat tuffs from the Yucca Mountain and other older tuffs at federal facilities north of the NTS ([Figure 6-91](#)). The estimated intrinsic permeability of the LTCU and VCU are near the low end of the range of intrinsic permeability. The estimated permeability of the WCU is in the center of the observed range based on field measurements. It is not surprising that the calibrated permeability values are at the lower end of the hydraulic test data for most of the confining units given that most hydraulic testing programs focus on the most transmissive intervals for pumping-scale aquifer tests.

Volcanic rocks that are generally considered to be aquifers in Frenchman Flat include welded tuffs (TSA and TM-WTA), vitric nonwelded tuffs (TM-LVTA and LVTA), and basaltic lava flows (BLFA). Flow through the welded tuffs and basalts is probably through fractures, whereas flow through the vitric, nonwelded tuffs is probably through the matrix pores. The estimated permeability of these HSUs are compared to NTS data for welded tuffs, nonwelded tuffs, and lavas taken primarily from Yucca Mountain and Pahute Mesa and to data measured in the Frenchman Flat area at ER-5-3 ([Figure 6-92](#)). Intrinsic permeability measurements within the Frenchman Flat CAU model area were also measured at Wells WW-4 and WW-4A in CP basin. A comparison with the data indicates that the model permeability estimates for the Timber Mountain tuffs (TM-WTA and TM-LVTA), TSA, and LVTA are in good agreement with the Frenchman Flat and NTS area data. The permeability estimates for the BLFA are difficult to evaluate given that there are no site-specific data; however, basalt flows like these should have little connected permeability, which is consistent with the low permeability, of this unit in the model (see [Section 3.6.1](#)).

[Table 6-10](#) reports the estimated $fperm$ factors in the calibration of the BASE-USGSD model without permeability depth decay in the AA or OAA. These $fperm$ factors spanned several orders of magnitude and included values both considerably greater than and considerably less than 1. The lowest $fperm$ factors were estimated for faults associated with the CP Hogback in the northwest part of the model (faults 11, 12, and 14-16). The Cane Spring fault (fault 3), which separates the CP basin from Frenchman Flat basin is considerably more permeable in this model than in any other model of

the Frenchman Flat CAU. Faults in the LCA associated with the Rock Valley fault system (faults 21, 33, 34, 57, and 58) and faults 17 and 39 had estimated $fperm$ factors that indicated these faults were significant conduits for groundwater (Table 6-10).

The final permeabilities in the BASE-USGSD flow model with no permeability depth decay in the AA and OAA depend on the values estimated for the reference permeability of the individual HSUs, the assumed depth-decay coefficients applied to the HSUs, and the permeability changes imposed by the presence of the faults, as implemented through the $fperm$ factors (Table 6-10). Figure 6-93 shows the calibrated permeability at the water-table surface, and Figures 6-94 and 6-95 show west-east cross sections of calibrated permeability values at the central and northern testing areas, respectively. The combined effects of the spatial distribution of HSUs, the depth decay in permeability, and the overprint of permeability changes associated with faults serve to create a complex distribution of permeability within the flow model. The distribution of permeability in plan view (Figure 6-93) shows that the central part of the Frenchman Flat basin is surrounded on the north, east, and south by a zone of low permeability that corresponds to the confining units that line the deepest parts of the basin and rise up along the flanks of the basin to intersect the water table (Figures 6-94 and 6-95). This zone of lower permeability rock separates the basin hydraulically from the much more permeable LCA that lies outside of and beneath the Frenchman Flat basin. The higher permeability estimated for the WCU compared to the other confining units (Figure 6-95) allows a significantly stronger hydraulic connection between the central part of Frenchman Flat and the CP basin and Wahmonie Hills to the west (Figure 6-95).

Table 6-10
Summary of Reference Permeability Values and Fault Permeability Multipliers
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA
 (Page 1 of 3)

HSU	Permeability - log k or k_0 (m ²)	Calibrated Anisotropy Ratios (k_h/k_v)
AA	-13.00	125
PCU	-14.50	125
BLFA	-12.00	1
OAA	-13.50	125
PCU1L	-11.00	2
PCU1U	-11.00	2
TM-WTA	-8.50	2
TM-LVTA	-9.20	2
UTCU	-12.00	2
TSA	-11.00	2
LVTA	-10.50	2
LTCU	-13.50	66.67
WCU	-11.88	2
VCU	-13.00	2
LCA3	-11.00	1
UCCU	-13.50	2
LCA	-10.40	1
Fault Number	Fault Permeability Multipliers	
1	0.3	
2	0.5	
3	1.20E-01	
4	1.0	
5	1.0	
6	1.0	
7	1.0	
8	1.06	
9	1.0	
10	0.88	
11	1.0E-05	
12	1.0E-05	
13	1.0	
14	1.0E-05	
15	1.0E-05	
16	5.0E-04	
17	20.0	

Table 6-10
Summary of Reference Permeability Values and Fault Permeability Multipliers
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA
 (Page 2 of 3)

Fault Number	Fault Permeability Multipliers
18	15.0
19	1.0
20	1.0
21 ^a	88.83
22	1.0
23	1.0
24	1.0
25	1.0
26	1.0
27	1.0
28	1.0
29	1.0
30	1.0
31	1.0
32	1.0
33 ^a	150.85
34 ^a	155.25
35	1.0
36	1.0
37	0.99
38	5.0
39	30.0
40	0.1
41	0.1
42	0.1
43	0.1
44	0.1
45	1.0
46	22.0
47	22.0
48	0.1
49	0.1
50	1.0
51	1.0
52	0.1
53	0.1

Table 6-10
Summary of Reference Permeability Values and Fault Permeability Multipliers
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA
 (Page 3 of 3)

Fault Number	Fault Permeability Multipliers
54	1.0
55	1.01
56	1.0
57 ^a	31.05
58 ^a	108.39
59	1.0
60	3.0
61	0.45
62	3.0
63	0.84
64	0.74
65	0.93
66	0.88
67	0.92
68	0.98
69	0.35
70	1.0
71	1.0
72	1.39
73	3.0
74	1.0
75 ^b	1.0
76	1.0
78	1.0

^aThe Rock Valley fault system (faults 21, 33, 34, 57, and 58) have different properties only through the LCA. These faults are neutral throughout all other HSUs.

^bFault 75 is the northern part of the Cane Spring fault (fault 3).

Figure 6-89
Estimated Versus Measured Intrinsic Permeability of AA for the
BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-90
Estimated Versus Measured Intrinsic Permeability of the LCA
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-91
Estimated Versus Measured Intrinsic Permeability of Aquitard HSUs
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-92
Estimated Versus Measured Intrinsic Permeability of VAs
for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-93
Calibrated Permeability at the Water Table for the BASE-USGSD Model with
No Permeability Depth Decay in the AA and OAA

April 24, 2006

base_aniso_kxb_BBxsec.ps

Figure 6-94
West-East Section of Calibrated Permeability at the Central Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

Figure 6-95

West-East Cross Section of Calibrated Permeability at the Northern Testing Area for the BASE-USGSD Model with No Permeability Depth Decay in the AA and OAA

6.6.1.4 Estimated Groundwater Flow Paths

Figure 6-96 shows the trajectory of particles initially located near test locations in the northern and central testing areas. The particle tracks are colored based on HSU and reflect the orientation of advective water movement through the CAU model.

Particle movement in both the northern and central testing areas are very similar to the BASE-USGSD model. Near the northern test area, particles originating in the OAA generally move from north to south until they reach the AA. Once the particles starting beneath the NEW POINT, DERRINGER, DIANA MOON, and MINUTE STEAK test locations move into the AA, they move to the southeast until they reach the basin edge (Figure 6-96). The groundwater flow paths seem to be dominated by the influx of water along the northwestern edge of the basin-fill units from water moving across the Cane Spring fault in the volcanic HSUs.

The trajectory of particles starting near the PIN STRIPE test is eastward within the TSA and LVTA (Figure 6-96). As shown in Figure 6-93, the TSA and LVTA create an arcuate band of higher permeability where they intersect the water table along the northern flank of the Frenchman Flat basin. This band of higher permeability creates a strong hydraulic connection in the model between the higher hydraulic heads in the CP basin to the west and locations beneath the PIN STRIPE test in the northern testing area. This is similar to the particle movement in the BASE-USGSD model, however, the particles move through the volcanic aquifers into the LTCU in this model, rather than directly from the volcanic aquifers to the LCA, as was seen in the BASE-USGSD model. In the BASE-USGSD model with no depth decay in the AA and OAA the higher hydraulic heads adjacent to the western part of the CP basin (Figures 6-83 and 6-84) cause groundwater to flow eastward through the LTCU toward a major fault in the Rock Valley fault system (fault 33) and enter the LCA.

In the central testing area of Frenchman Flat, groundwater flow is substantially less complex than in the northern testing area. The movement of particles initially located near the water table near the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area will be through the alluvium toward the southeast. The observed particle pathways are very similar to the particle movement in the BASE-USGSD model. Eventually, all of the particles will encounter the Rock Valley fault system and exit the flow system along the southern part of the western boundary of the model.

Figure 6-96

Particle Tracks Starting Near the Underground Nuclear Tests for the BASE-USGSD Model with no Permeability Depth Decay in the AA and OAA

6.6.2 Summary of Constant Permeability with Depth Uncertainty Analysis

The reduction in permeability with depth has a sound technical basis. However, uncertainty exists in permeability decay coefficients, and the potential impact of permeability changes on the steady-state modeled flow fields for the Frenchman Flat CAU. Model calibration with permeability depth decay applied to volcanic and carbonate units, but not to the alluvium, was generally successful in matching the available head data within the constraints of the field-scale permeability data. However, model calibration did require higher values of anisotropy in the OAA and AA than used in previous models.

The BASE-USGSD model with constant permeability in the AA and OAA has similar flow paths to other models used to bound conceptual model uncertainty of the Frenchman Flat flow system. Thus, while there is uncertainty in the applicability of depth decay in the AA and OAA (the HSUs into which most of the underground nuclear test radionuclide source will be applied) as well as the value of the depth decay coefficients, the parameters required to calibrate the flow model in the absence of such effects do not greatly change the movement of groundwater. In the areas near the underground nuclear testing, the model tends to overpredict heads in the tuff confining units and the LCA while underpredicting heads at the edges of the basin-fill units. Assessment of radionuclide transport using realistic transport parameters will consider variability in the conceptual model of the flow system provided by this model calibration.

7.0 **PARAMETER SENSITIVITY ANALYSIS**

The Frenchman Flat CAIP Addendum (NNSA/NSO, 2001) and general modeling protocol (ASTM D5611-94 *Standard Guide for Conducting a Sensitivity Analysis for a Ground-Water Flow Model Application* [ASTM, 1994a]) require analysis of flow model parameter sensitivity. This section presents the sensitivity analyses.

Two approaches to local parameter sensitivity analysis were implemented for the Frenchman Flat flow model. In the first approach, parameter sensitivity and correlations were evaluated using PEST (Watermark Numerical Computing, 2004). The PEST code calculates a sensitivity coefficient for each parameter with respect to all weighted observations. This analysis is termed “local” because parameter values near the base calibrated value are investigated using only slight changes to parameter values. The second approach involves perturbing each of the parameters over a range, one at a time, from a reference value and computing the corresponding change in the model output (Anderson and Woessner, 1992). Parameter perturbation results are presented for five models:

- BASE HFM with USGSD recharge and boundary conditions (BASE-USGSD)
- BASE HFM with Death Valley Regional Ground-Water Flow System model recharge and boundary conditions (BASE-DVRFS)
- BLFA HFM with USGSD recharge and boundary conditions (BLFA-USGSD)
- DETA HFM with USGSD recharge and boundary conditions (DETA-USGSD)
- CPBA HFM with USGSD recharge and boundary conditions (CPBA-USGSD)

While sensitivity analyses are formally presented for the final calibrated models, such analyses were also carried out as an integral part of the calibration process.

7.1 Parameter Sensitivity Analysis

Sensitivity coefficients, computed as the change in output divided by the change in input, reflect the slope of the input-output relationship at a reference point. In the case of the sensitivity analysis presented here, the reference point refers to the parameter values at calibration. These sensitivity coefficients are, therefore, indicative of the parameter sensitivity in the vicinity of the calibration point and apply only to the parameter range over which the input-output relationship is linear. These sensitivities can be obtained quantitatively from the outputs of PEST (Watermark Numerical Computing, 2004), a non-linear parameter estimation code. In the process of optimizing a nonlinear model, PEST calculates the Jacobian matrix. The Jacobian matrix relates the model-calculated observations to the model input parameters where any element of the Jacobian matrix, J_{ij} , describes the derivative of the i 'th observation with respect to the j 'th parameter. Based on the Jacobian matrix, PEST calculates the composite sensitivity of each parameter with respect to all weighted observations. The composite sensitivity of parameter i (s_i) is defined as:

$$s_i = \frac{\sqrt{[J^t Q J]_{ii}}}{m} \quad (7-1)$$

where J is the Jacobian matrix; J^t is the transpose of the Jacobian matrix; Q is the cofactor matrix, an m -dimensional, square, diagonal matrix comprised of the squared observation weights; and m is the number of observations of non-zero weight (Watermark Numerical Computing, 2004). In other words, the sensitivity coefficient for a given parameter is the weighted average of the derivatives of all the observations with respect to that parameter.

The Jacobian matrix is also manipulated to derive the covariance matrix, which in turn can be used to estimate parameter correlations and confidence limits. The correlations and confidence limits are, themselves, subject to the same linearity constraint as sensitivity coefficients but still provide a useful semi-quantitative tool for understanding how model parameters interact and how the data support the model (Poeter and Hill, 1997).

To provide some estimate of the sensitivity of observations to all the adjustable parameters, PEST also calculates composite observation sensitivity. The composite observation sensitivity of observation j (s_j) is defined as:

$$s_j = \frac{\sqrt{[Q(JJ^t)]_{jj}}}{n} \quad (7-2)$$

where J and Q are the Jacobian and cofactor matrices, respectively, and n is the number of adjustable parameters (Watermark Numerical Computing, 2004). While the observation sensitivities do not generally provide as much useful information in guiding model calibration as the parameter sensitivities, they may provide some insight into which observations are sensitive to many parameters.

To describe the degree to which parameters are correlated to one another, PEST computes the correlation coefficient matrix. The correlation coefficient matrix is a symmetric, n -dimensional, square matrix, ρ_{ij} , where n is the number of adjustable parameters. Each element of the matrix ρ_{ij} represents the correlation between parameter i and parameter j . The diagonal elements of the correlation coefficient matrix are always equal to 1 because a parameter is perfectly correlated with itself. The off-diagonal elements range between -1 and 1 and, the closer the absolute value is to 1, the more highly (either directly or inversely) correlated the parameters are. Again, these values are subject to the assumption of linear model input-output response near the reference point.

7.1.1 Results

Because the Frenchman Flat flow model has more than 100 adjustable parameters and fewer than 40 observations, it is not feasible to calculate the full correlations among these parameters (the Hessian matrix is not invertible). However, some useful information from parameter correlations can be calculated for a limited number of parameters. The selection of parameters is subjective and is mainly guided by the experience gained throughout the model calibration process. Based on this experience, 13 parameters were selected for analysis with PEST ([Table 7-1](#)).

Table 7-1
PEST Composite Sensitivity Coefficients for Select
BASE-USGSD Model Calibration Parameters

HSU/Fault	Parameter Adjusted	Composite Sensitivity Coefficient
VCU	λ	608.3
AA	λ	127.3
TM-LVTA	λ	73.9
LCA	k_0	8.3
Fault 21 (Rock Valley fault)	Permeability multiplier	7.2
Fault 33 (Rock Valley fault)	Permeability multiplier	1.8
VCU	k_0	1.1
WCU	k_0	0.9
Fault 39 (Basin fault)	Permeability multiplier	0.8
AA	k_0	0.4
Fault 3 (Cane Spring fault)	Permeability multiplier	0.3
LTCU	k_0	0.2
TM-LVTA	k_0	0.2

Of the parameters that were tested, the BASE-USGSD model was most sensitive to the depth-decay coefficient for the VCU (Table 7-1). The permeability in the model is an exponential function of the depth-decay coefficient (λ) and reference permeability value (k_0). The correlation coefficient between these two parameters is 0.999 for the VCU (Figure 7-1), where a correlation coefficient of 1.0 indicates perfect correlation. The depth-decay coefficients for the AA and TM-LVTA were also very sensitive, but the correlation between the AA decay coefficient and reference permeability was noticeably smaller at 0.163. The reason for the lack of correlation between the decay coefficient and reference permeability for the AA is unknown. Nonlinear and slight precision effects can make correlation coefficients unreliable (Hill, 1998). The perturbation results indicate that the response of the model to the AA reference permeability is very nonlinear; thus, the results are to be considered approximate and limited by the conceptual model to understand the cause and effect reflected in the statistical analyses. The lack of correlation may be the combined result of almost no response of the flux portion of the objective function to the reference permeability of the AA and the small decay coefficients resulting in very little change in permeability with depth for the alluvium. The most sensitive reference permeability in the model is the LCA k_0 (Table 7-1). The reference permeability of the LCA is inversely correlated with fault 33 permeability multiplier (-0.91), one of the main Rock Valley faults. Fault 33 acts as a major water conduit in the LCA along the eastern edge for the Frenchman Flat basin and directs water to the western boundary of the model. The inverse

Figure 7-1
PEST Parameter Correlations Greater than 0.9 for the 13
Frenchman Flat CAU BASE-USGSD Model Parameters

correlation between these two parameters reflects their control on the water balance of the model. When permeability of the LCA increases, the conductivity of fault 33 must decrease to limit the routing of water to the western boundary of the model, where the majority of lateral outflow occurs. These faults were only adjusted in the LCA and had no expression in the volcanic or alluvium units and, therefore, limited correlation with permeability of these units (<0.3). Within the group of parameters tested, the LCA wells and Rock Valley faults as reflected by the model boundaries did not have high composite sensitivity values. It is likely that the low composite sensitivity values reflect the limited number of target observations in the LCA.

Among the 13 parameters tested, the most correlated HSUs were the AA and VCU as well as the LTCU and WCU. The AA and VCU are positively correlated, indicating that increasing or decreasing the permeability of these units results in similar model response. The majority of target well observations in the flow model domain are located in the AA in the central portion of the Frenchman Flat basin. The head at these targets is largely controlled by the permeability contrast between the AA and the VCU underlying the aquifers. The LTCU and WCU reference permeability values are also highly correlated, but in this case, it is an inverse correlation. This indicates that each

of these units serves to offset the behavior of the other unit. In all HFMs, the WCU is underlain by LTCU throughout the model domain. In the BASE-USGSD model, the LTCU acts as a very tight confining unit, while the WCU has a more intermediate permeability, tighter than an aquifer but not quite as tight as a confining unit. These units both introduced or maintained higher pressure in the AA compared to the LCA. Attempts to decrease the difference in calibrated reference permeabilities during calibration caused water levels in the AA to be too low. This result suggests that the gradient resulting from the low permeability of the LTCU was required to maintain pressure in the AA and OAA HSUs, thus greatly reducing the leakage of water from the basin-fill HSUs to the deep LCA regional flow system.

The calibration target sensitivity values calculated by PEST are presented in [Figure 7-2](#). The results indicate that the most sensitive of the targets is WW-5A, which is the southernmost head observation in the model domain. During calibration, this target was particularly sensitive to the VCU permeability, which underlies the alluvium in this portion of the basin. The next group of sensitive targets includes the ER-5-4 well cluster and Well UE-5n. These wells are also located in the southern portion of the Frenchman Flat alluvial basin and are completed in the AA and LTCU. During calibration, these wells were sensitive to the permeability difference of the WCU, and the permeability of the AA. It is important to note that the targets in the LCA (including wells and boundary flows) are relatively insensitive to the parameters tested. This result is also consistent with the observation that heads at target locations in the AA and OAA have little sensitivity to the LCA because they are separated from the LCA by low permeability units (e.g., LTCU, VCU).

Figure 7-2
Composite Observation Sensitivity from PEST for the BASE-USGSD
Frenchman Flat Flow Model

7.2 Parameter Perturbation Analysis

A common metric of model calibration is the goodness-of-fit parameter called the objective function. The objective function, or PHI, is the sum of the squares of the weighted residuals:

(7-3)

$$\Phi = \sum_{i=1}^m (w_i r_i)^2$$

where Φ is the objective function, w is the observation weight, r is the residual or difference between the simulated and measured values, and m is the number of observations of non-zero weight. For the Frenchman Flat flow model, PHI can be divided into two components representing different types of calibration target data. Head measurements at wells are described by the WELL component. The FLUX component represents lateral boundary flow estimates from the UGTA and DVRFS regional models.

In the perturbation analysis, input parameters were systematically increased and decreased while changes in the objective function, heads, and various fluxes were recorded. Estimated standard deviations in HSU permeability (Section 5.5, Table 5-3) and depth-decay coefficient were available (Table 3-6). It was assumed that these standard deviations were applicable in describing the uncertainty in the calibrated values of these parameters. For each HSU permeability and depth-decay coefficient, six simulations were completed where the input value was perturbed up and down one-half, one, and two standard deviations from the calibrated value. Because no reliable information is available for vertical anisotropies, fault permeability multipliers and the conductance of confining units at the lateral boundaries, they are perturbed over two orders of magnitude during the perturbation analysis.

For the BASE-USGSD model, 17 k_o parameters, 16 depth-decay coefficients, 4 vertical anisotropies, more than 70 fault permeability multipliers, and 1 boundary conductance were varied. This resulted in 115 parameters being evaluated. Generating results for each perturbation case required 691 model runs. In addition to the BASE-USGSD model, identical perturbation analyses were conducted for 5 calibrated alternate models (BLFA-USGSD, DETA-USGSD, CPBA-USGSD, BASE-DVRFS, and CPBA-DVRFS), requiring an additional 3,455 simulations.

To investigate the sensitivity of the vertical component of the fault permeability multipliers, a perturbation analysis in which 75 vertical and 75 horizontal fault permeability multipliers were varied individually was also conducted for the BASE model. This required 901 simulations.

Several different metrics of the model output were calculated. For the objective function and the individual portions contributing to it, a simple difference (D) was used:

$$D = \Phi_{sens} - \Phi_{cal} \quad (7-4)$$

where Φ_{sens} is the sensitivity simulation objective function and Φ_{cal} is the calibrated simulation objective function. Similarly, a simple difference was applied to the simulated flux output.

For the output heads, an additional metric was also computed; the mean difference (MD) between the sensitivity simulated output and the calibrated simulated output heads at each of the target wells was calculated as:

$$MD = \frac{1}{n} \sum_{i=1}^n (h_{sens,i} - h_{cal,i}) \quad (7-5)$$

where $h_{sens,i}$ is the perturbation simulation head at well i , $h_{cal,i}$ is the calibrated simulation head at well i , and n is the number of wells. This metric describes more than the objective function components; the direction of the head change can also be assessed. A positive value indicates that the sensitivity simulation has overall higher heads and a negative value has overall lower heads. Similarly, the mean difference in the water-table elevation within the AA, the OAA, and the BLFA was calculated for the perturbation analysis by comparing the head at the topmost nodes for each of these HSUs. A total of 11 model-output metrics were investigated for each model run. All data from these analyses are included in [Appendix C](#).

Direct data on fault permeability in the flow model area are unavailable. As a result, the majority of the calibration effort was focused on HSU permeability, and fault permeability was only adjusted to maintain the primary directions of boundary flows or to balance water levels at target locations in the Frenchman Flat and CP basins. These changes to fault permeability were treated as calibration parameters. The analysis of the perturbation results will, therefore, focus on the sensitivity of HSUs and a select group of faults that strategically controlled either boundary flows or hydraulic head in the central Frenchman Flat basin.

7.2.1 BASE Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (BASE-USGSD) Model

Sensitivity to HSU Reference Permeability (k_o)

The objective function is most sensitive (within two standard deviations of calibration) to the permeability of the LCA. The sensitivity is dominated by the effect of the LCA on boundary fluxes (or overall flow direction) (Figure 7-3), but the LCA k_o is also very important to the well portion of the objective function (Figure 7-4) by serving to maintain hydraulic heads in the deep portion of the model. The flow model domain is dominated on all edges by the LCA.

The well portion of the objective function is particularly sensitive to five other HSUs: the WCU, LTCU, VCU, LCA3 and AAs (Figure 7-4). The LTCU and VCU effectively separate the Frenchman Flat alluvial basin from the deep carbonate rock aquifer system; therefore, these units serve a pivotal role in the flow model calibration by maintaining hydraulic heads in the shallower portions of the basin. The AA sensitivity is dominated by the water-level observations at the target locations. The separation of the AA flow system from the regional LCA is apparent in the limited influence of the AA on the boundary flux portion of the objective function (Figure 7-3).

Because almost all of the underground nuclear testing in the Frenchman Flat basin was conducted at or near the water table, understanding the important hydrologic controls on the AA and OAA water-table elevations is paramount. Sensitivity results focused on the AA water-table elevation demonstrate that increasing the AA k_o results in decreasing the elevation of the water table (Figure 7-5). Also, increasing the Timber Mountain aquifers (TM-LVTA and TM-WTA) k_o results in an increase in AA water-table elevation, while increasing the reference permeability of the TSA results in a modest increase in the AA water-table elevation (Figure 7-5). The water-table elevation of the AA is insensitive to all of the HSUs interfingering with the AA, including the BLFA, PCU1U, PCU1L, and PCU. The water-table elevation is also insensitive to the OAA k_o (Figure 7-5). Unlike the other volcanic aquitard units, which increase the AA water-table elevation as their permeability decreases, decreasing the permeability of the WCU results in a lower water-table elevation. This may suggest that the water movement from the western edge of the model near the Wahmonie Hills and volcanic center is an important source of water to the alluvial basin, thus supporting one of the alternative conceptual models of alluvium flow: west-to-east flow.

Figure 7-3
FLUX Perturbation Plot for BASE-USGSD Model HSU Reference Permeability

Figure 7-4
WELL Perturbation Plot for BASE-USGSD HSU Reference Permeability

Figure 7-5

Mean Head Difference for AA Water Table from HSU Reference Permeability Perturbation of BASE-USGSD Model

Sensitivity to Depth-Decay Coefficients (λ)

The depth-decay coefficients were not used as adjustable parameters during model calibration. However, it is still important to understand the model sensitivity to these parameters. Boundary fluxes are only sensitive to the decay coefficient of the LCA. This is consistent with the observations of boundary flux sensitivity to the permeability of the LCA, but not to other HSUs. The overall effect of the depth-decay coefficient is not as strong as reference permeability; this simply reflects a smaller range of values over which the decay coefficient was perturbed. The head portion of the objective function is most sensitive to the LCA decay coefficient, which is expected given its role in maintaining the water balance of the model (Figure 7-6). For the volcanic units, the most sensitive decay coefficient is the VCU. Almost no model sensitivity is observed for the other decay coefficients. The model is generally insensitive to the decay coefficients of the shallow HSUs embedded in the AA and OAA because they are not sufficiently thick to have much permeability change with depth; however, increases or decreases in the decay coefficient for the AA result in a substantial increase in the well objective function (Figure 7-6). The sensitivity of the model to the AA decay coefficient may reflect the significant depth and extent of this unit in the model area compared to the other HSUs and the presence of calibration data throughout the unit.

Despite the lack of sensitivity of the objective function to the depth-decay coefficients used in the CAU model, the water-table elevation of the AA is sensitive to some of the decay coefficients within the error tolerance of the calibration (~0.5 m) (Figure 7-7). The water-table elevation is sensitive to decay coefficients of units relatively deep in the flow system (especially the VCU and LCA), and not the decay coefficients used for the shallow AAs and VAs. In the case of the VCU decay coefficient, the decrease in permeability with depth helps to maintain the pressure differential observed between the alluvial and volcanic units and the LCA. The decay coefficient of the LCA is important to the overall behavior of the flow system because of the ubiquity and depth of the LCA. Changes in hydraulic head due to increases or decreases in permeability directly impact the water balance of the model. This, in turn, affects the heads in the alluvium.

Figure 7-6
WELL Perturbation Plot for Depth-Decay Coefficients for BASE-USGSD Model

Figure 7-7
Mean Head Difference for AA from
Depth-Decay Coefficient Perturbation of BASE-USGSD Model

Sensitivity of Fault Permeability - BASE-USGSD Model

Rock Valley faults - The Rock Valley fault group is a dominant feature in the LCA underlying Frenchman Flat. These faults exert significant control on the regional direction of groundwater movement. The flow model calibration is particularly sensitive to the easternmost faults 21 and 33 (Figure 7-8 and Appendix C). The boundary flux portion of the objective function is highly sensitive to increases in fault 21 permeability multiplier. Increases in fault 21 permeability multiplier cause increased flux through both the northern and western boundaries of the CAU flow model. The sensitivity of the boundary flux decreases as the fault is tightened from its calibrated value, but is still greater than an 8,500 increase in the flux portion of the objective function with a decrease in fault permeability of half an order of magnitude. Fault 33 does not intersect the northern boundary of the model, so fault 21 dominates the northern boundary flux. Faults 60, 62, and 73 exhibit a threshold behavior where only increases in fault permeability greater than half an order of magnitude impact the objective function. Decreasing the permeability of these faults results in little change. The effect

Figure 7-8
FLUX Perturbation Plot for Rock Valley Fault
Permeability Multipliers of BASE-USGSD Model

of the Rock Valley fault group on the well portion of the objective function is very different than observed for the boundary flux portion. The magnitude of change to the WELL PHI is a much smaller than observed for the FLUX PHI (Figure 7-9). Fault 33 has the greatest influence on the calibrated head targets (Figure 7-9); this fault tends to decrease the hydraulic head at the target locations with increases in the fault permeability multiplier, and increase the hydraulic head with decreases in the fault permeability multiplier. Interestingly, not all faults have the same influence on water-table elevation. Faults in the more central portion of the basin appear to decrease the water-table elevation when they are made more open, but faults along the southern edge of the model increase the water-table elevation in the AA. This effect of the faults along the southern edge of the model suggests that reducing the permeability multiplier of these faults decreases the flux out of the model and therefore increases the pressure head throughout the model domain (Figure 7-9).

Cane Spring fault - The Cane Spring fault separates the CP basin area in the northwestern portion of the model domain from the Frenchman Flat basin. This fault has little bearing on the boundary fluxes computed in the CAU model, but it showed a pronounced effect on the hydraulic head portion of the objective function. During calibration, the fault was separated into two sections: one south and west

Figure 7-9
WELL Perturbation Plot for Rock Valley Fault Permeability
Multipliers for BASE-USGSD Model

of the CP Hogback, and one north and east of the CP Hogback ([Table D.1-1](#) and [Figure D.1-1](#)). In the calibrated model, the southern section of the fault has much lower permeability than the surrounding rocks, while the northern portion of the fault was assigned a permeability greater than that of the surrounding rock. Overall, the well portion of the objective function was observed to be very sensitive to changes in the fault permeability multiplier of the southern portion of the fault and showed almost no sensitivity to the permeability of the northern portion ([Figure 7-10](#) and [Appendix D](#)). The lack of sensitivity to the northern portion near the calibrated value suggests that there is a threshold behavior of this portion of the fault. During calibration, it was observed that if the entire fault were given a much lower permeability than the surrounding rocks, the modeled water-level elevation in the central portion of Frenchman Flat basin was lower than the observations. This indicated that a small flux from CP basin contributes to the water balance of the Frenchman Flat AA.

Figure 7-10
WELL Perturbation Plot for Cane Spring Fault Permeability Multipliers for
BASE-USGSD Model

Basin-bounding faults - The fault generally trending north to south along the western edge of the Frenchman Flat basin (fault 39) is important to the well portion of the objective function (Figure 7-11 and Appendix D). During calibration, fault 39 seemed to be directing water that entered the model domain from the Wahmonie Hills along the western edge of the Frenchman Flat basin. In addition, the well portion of the objective function was found to be sensitive to the permeability of fault 17 (Figure 7-11), although it is considerably less sensitive than the permeability of fault 39, thus making Figure 7-11 somewhat deceiving. This fault seemed to serve a similar role to that of fault 39, by directing water from southern Yucca Flat to the western edge of Frenchman Flat basin.

Anisotropy Sensitivity

The boundary flux portion of the objective function is most sensitive to the value of anisotropy selected for the lumped parameter used for the LCA, LCA3, and BLFA (Figure 7-12). These HSUs were combined during the perturbation analysis because during calibration, the anisotropy ratio for these units was equal to 1. Given the magnitude of change to the boundary flux portion of the objective function, it would seem that the sensitivity to anisotropy in this group is dominated by the

LCA. The anisotropy parameters for the volcanic and basin-fill materials have little influence on the boundary fluxes in the Frenchman Flat CAU model.

Figure 7-11
WELL Perturbation Plot for Other Basin-Forming Fault Permeability Multipliers for
BASE-USGSD Model

The well portion of the objective function is most sensitive to the anisotropy of the VCU and the LTCU (Figure 7-12). This observation is consistent with the observed sensitivity of the model to the permeability of these units (see Section 7.1.1). Unlike the results for HSU reference permeability, however, the sensitivity of the LTCU anisotropy is a threshold response where decreasing the anisotropy value (increasing the difference in the vertical to horizontal conductivity) results in little change to the well portion of the objective function (Figure 7-12). The hydraulic head at the target locations shows moderate sensitivity to the AA anisotropy. Given the layered deposition pattern of the AA and OAA HSUs, the anisotropy of the AA is an essential component to appropriately model the flow in the basin-fill units.

Figure 7-12
WELL and FLUX Perturbation Plots for Grouped Anisotropy Values
for BASE-USGSD Model

BASE-USGSD Model Fault Vertical Anisotropy

The permeability multipliers of faults in the Frenchman Flat model area were calibrated using one multiplier for the x , y , and z directions. The perturbation of the BASE-USGSD model was completed using this parameterization for the fault multipliers. The model calibration may, however, exhibit different sensitivity to the calibrated permeability if the vertical permeability (z) is varied relative to the horizontal permeability (x and y). The total objective function is most sensitive to the z -direction permeability of faults 39 and 21 ([Appendix D](#)). The BASE-USGSD model is, however, more sensitive to changes in both of these faults when they were adjusted in all directions simultaneously.

Perhaps more important than model sensitivity is the insensitivity of the CAU model calibration to fault permeability multiplier values in the vertical direction. When the model demonstrates no sensitivity to changes in z -direction permeability multiplier within two orders of magnitude, this may indicate an area of the model where vertical water migration down a fault is unconstrained by calibration data. These areas of the model are particularly important to identify, so that any vertical pathways that may accelerate the migration of contaminants from underground nuclear tests can be properly evaluated. Determining whether the model is truly insensitive to the vertical fault permeability is dependent not only on changes to the objective function, but also to changes to the modeled water table in the AA, OAA, and the hydraulic head at the targets. [Table 7-2](#) indicates which of the faults take one or more of the calibration metrics out of calibration tolerance. Notice that many of the vertical fault permeability multiplier values have no effect on the calibration of the model. Many of the insensitive faults are located along the model edges where there are few target locations and where contaminant migration is unlikely (see [Figures 2-13](#) and [D.1-1](#) for fault locations).

7.2.2 BASE Hydrostratigraphic Framework Model and Death Valley Regional Ground-Water Flow System Recharge and Boundary Heads (BASE-DVRFS)

Despite the significant changes in the calibrated parameter values between the BASE-USGSD and the BASE-DVRFS models, the model response to parameter perturbations from the calibrated value were very similar. The most significant change during calibration is the reference permeability (k_0) of the LCA. The boundary flux portion of the objective function for the BASE-DVRFS is considerably less sensitive to changes in the HSU reference permeability values than is observed for the BASE-USGSD model ([Figure 7-13](#) compared to [Figure 7-3](#)). The sensitivity is still dominated by the

effect of the LCA on boundary flux (or overall flow direction) (Figure 7-13), but the LCA k_0 is also very important in the well portion of the objective function (Figure 7-14). The model at both WELL and FLUX targets exhibits a threshold behavior with respect to changes in the LCA k_0 . With decreases in the LCA k_0 the flow model has a progressively poorer fit to measured data. However, with increases in LCA reference permeability, the flow model response stabilizes to a consistent error at the wells (Figure 7-14). The opposite is true with respect to the model fit to the observed lateral fluxes (Figure 7-13). Changes to the LCA k_0 result in a classic, somewhat nonlinear, response by the elevation of the AA water table (Figure 7-15). In all cases, the general trend in model response to changes in the LCA k_0 is identical to the BASE-USGSD model.

Table 7-2
Portions of Model Performance Metric Taken Out of
Calibration with Changes in Vertical Fault Permeability for the BASE-USGSD Model

Fault ID	AA Water-Table Elevation	OAA Water-Table Elevation	Total Objective Function	Average Hydraulic Head at Target
1	X	X	X	
3	X	X		X
10			X	
14	X			
17		X	X	X
19	X			
20	X			
21	X	X	X	
26	X	X		X
33			X	
34			X	
39	X	X	X	X
46	X	X	X	X
47	X	X		X
51		X	X	
54			X	
58			X	
CP thrust (NE 72)	X	X	X	

Note: Faults that displayed no sensitivity are not listed in this table.

Figure 7-13
FLUX Perturbation Plot for BASE-DVRFS HSU Reference Permeability

Figure 7-14
WELL Perturbation Plot for BASE HFM Model HSU Reference Permeability with DVRFS Boundary Heads and Fluxes

Figure 7-15
Mean Head Difference for AA Water Table from LCA Reference Permeability
Perturbation of BASE-DVRFS

7.2.3 BLFA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (BLFA-USGSD) Model

Calibration of the BLFA-USGSD alternative model required no changes to calibrated reference permeability values or fault multipliers from the BASE-USGSD model, as discussed in [Section 5.6](#). Despite the identical HSU k_0 s, depth-decay coefficients and fault multipliers, the sensitivity of the well portion of the objective function and AA water-table elevation to the model is enhanced for changes to the BLFA and decreased for the AA HSUs. The model had small changes in sensitivity to several other HSUs in the central portion of the Frenchman Flat basin, but the overall trends are identical. [Figure 7-16](#) shows the model sensitivity results (well objective function and AA water table) for both the BASE-USGSD and BLFA-USGSD models. Overall, the increase in model sensitivity to changes in the BLFA HSU in this alternative HFM is significant for the well portion of the objective function, but still modest with respect to the elevation of the AA water table ([Figure 7-16](#)).

Figure 7-16
Mean Head Difference for AA Water Table from HSU Reference Permeability
of BASE-USGSD and BLFA-USGSD Models

7.2.4 DETA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (DETA-USGSD) Model

Similar to the BLFA alternative HFM, the DETA alternative HFM required no changes to the calibrated reference permeability values or fault multipliers from the BASE-USGSD, as discussed in [Section 5.6](#). Changes to the HFM included more continuous and thicker Timber Mountain aquifers (TM-WTA and TM-LVTA), removal of the detachment fault (fault 36), and greater continuity of the TSA. Unlike the enhanced sensitivity seen of the BLFA HSU in the BLFA-USGSD perturbation analysis, no comparable changes in model sensitivity occurred in the DETA analysis for the changed HSUs.

7.2.5 CPBA Hydrostratigraphic Framework Model and USGS with Redistribution Recharge (CPBA-USGSD) Model

Although differences between the BASE and CPBA HFMs were isolated to the CP basin area, the calibration approach for the CPBA flow model was different and produced a different set of reference permeability and anisotropy values and fault multipliers (see [Section 6.3.5](#)) for more information). As a result, the flow field is slightly different and the sensitivity analysis reveals a somewhat different model response to parameter adjustments.

Sensitivity to HSU Reference Permeability (k_0)

The objective function is most sensitive within two standard deviations of calibration to the LCA k_0 (see [Appendix C](#), which contains perturbation plots for all model metrics). The sensitivity is dominated by the effect of the LCA on boundary flux (or overall flow direction) ([Figure 7-17](#)). The flow model domain is dominated on all edges by the LCA, and the perturbation analysis of the CPBA-USGSD HFM indicates that this flow model is more sensitive to the LCA than for the BASE-USGSD model ([Figure 7-3](#)). The boundary flux portion of the objective function, however, is noticeably less sensitive to the TSA k_0 while exhibiting enhanced sensitivity to the AA k_0 ([Figures 7-17](#) and [7-3](#)).

The well portion of the objective function is most sensitive to the LCA k_0 as observed in the BASE-USGSD perturbation analysis ([Figure 7-4](#)), but increases to the LCA k_0 in the CPBA-USGSD model result in greater model sensitivity than is observed for the BASE-USGSD model ([Figure 7-18](#)). Among the aquitard units, there are three units to which the well portion of the objective function is

sensitive: the VCU, LTCU, and WCU (Figure 7-18). The model sensitivity to the AA is dominated by many of the target wells being in the AA. The model demonstrates no sensitivity to the calibrated OAA k_0 within the four orders of magnitude tested (Figure 7-18). The largest change in model response to HSU k_0 is observed in the volcanic aquifer group (Figure 7-18). In the BASE-USGSD model, changes to the TM-LVTA k_0 have the largest impact to the well portion of the objective function (Figure 7-4); however, in the CPBA-USGSD calibration, the model is most sensitive to the TM-WTA k_0 (Figure 7-18). Additionally, decreasing the reference permeability of the TSA or TM-WTA would have resulted in reducing the well portion of the objective function in the CPBA-USGSD calibration (Figure 7-18). Whereas the BASE-USGSD model is most sensitive to the TM-LVTA, the CPBA-USGSD model exhibited very little sensitivity. The BASE-USGSD model also indicates that increasing the TM-LVTA k_0 results in a larger objective function, but in the CPBA-USGSD model, increasing the TM-LVTA k_0 results in decreasing the objective function.

In general, the sensitivity of the water-table elevation of the AA in the CPBA-USGSD model (Figure 7-19) has similar trends as those observed in the BASE-USGSD model analysis (Figure 7-7). Increasing the AA k_0 results in a decrease in the elevation of the water table (Figure 7-19). Conversely, increasing the Timber Mountain aquifers (TM-LVTA and TM-WTA) and TSA k_0 s results in an increase in the AA water-table elevation (Figure 7-19). The water-table elevation of the AA is insensitive to all HSUs interfingering with the AA, including the BLFA, PCU1U, PCU1L, and PCU. Unlike the other volcanic aquitard units, which increase the AA water-table elevation as their reference permeability decreases, decreasing the permeability of the WCU results in a lower water-table elevation. This result is consistent with the observed parameter sensitivity in the BASE-USGSD model.

Figure 7-17
FLUX Perturbation Plot for HSU Reference Permeability for CPBA-USGSD Model

Figure 7-18
WELL Perturbation Plot for HSU Reference Permeability for CPBA-USGSD Model

Figure 7-19

Mean Head Difference for AA Water Table from HSU Reference Permeability Perturbation of CPBA-USGSD Model

Sensitivity to Depth-Decay Coefficients (λ)

Boundary fluxes are most sensitive to the decay coefficient of the LCA ([Appendix C](#)). This is consistent with the observations of boundary flux sensitivity to the permeability of the LCA ([Figure 7-17](#)). The overall effect of the depth-decay coefficient is not as strong as permeability; this simply reflects a smaller range of values over which the decay coefficient was perturbed.

The head portion of the objective function is also very sensitive to the LCA, which is expected given its role in maintaining the water balance of the model ([Figure 7-20](#)). With the change in the CP basin configuration, the LCA3 decay coefficient is the most sensitive of the decay coefficients in the model ([Figure 7-20](#)). Given that the LCA3 has a limited lateral extent in the HFM compared to many of the HSUs, this is an unexpected outcome. This result probably reflects the role of the LCA3 in maintaining heads at WW-4 and WW-4A in the CP basin. Of the volcanic units, the most sensitive decay coefficients are for the VCU and TSA, but many of the other units demonstrate model sensitivity. The model is generally insensitive to the decay coefficients of the shallow basin units; however, both increases or decreases in the decay coefficient for the AA result in a substantial increase in the well objective function ([Figure 7-20](#)). The sensitivity of the model to the AA depth-decay coefficient may reflect the significant depth and extent of this unit in the model area.

Figure 7-20
WELL Perturbation Plot for Depth-Decay Coefficients for CPBA-USGSD Model

Sensitivity of Fault Permeability - CPBA-USGSD Model

Rock Valley faults - The Rock Valley fault group is a dominant feature of the LCA underlying Frenchman Flat. These faults provide significant control to the regional direction of groundwater movement. The flow model calibration is particularly sensitive to the easternmost faults 21 and 33, consistent with the observations from the BASE-USGSD model. The boundary flux portion of the objective function is highly sensitive to increases in fault 21 permeability. Increases in fault 21 permeability cause increased flux through both the northern and western boundaries of the CAU flow model. The sensitivity of the boundary flux decreases as the fault is tightened from its calibrated value. Fault 33 does not intersect the northern boundary of the model, so fault 21 dwarfs the total influence of this fault on the boundary flux. Faults 60, 62, and 73 exhibit a threshold behavior where only increases in fault permeability greater than half an order of magnitude impact the objective function, whereas decreasing the permeability of these faults results in little change (see [Appendix B](#) for perturbation figures). The effect of the Rock Valley fault group on the well portion of the objective function is very different than observed for the boundary flux portion. Of the Rock Valley faults, fault 33 has the greatest influence on the calibrated head targets ([Figure 7-21](#)).

Faults in the southern portion of the model domain (59, 60, 62, 68, and 73) exhibit a threshold behavior where decreasing the permeability of the faults results in no change to the well portion of the objective function, while increases in fault permeability result in a minor increase in the objective function.

Cane Spring fault - The Cane Spring fault separates the CP basin area in the northwestern portion of the model domain from the Frenchman Flat basin. This fault has little bearing on the boundary fluxes in the CAU model, but has a pronounced effect on the head portion of the objective function. During calibration, the fault was separated into two sections: one south and west of the CP Hogback, and one north and east of the CP Hogback ([Table D.1-1](#) and [Figure D.1-1](#)). The southern section of the fault is parameterized with much lower permeability than the surrounding rocks, while the northern portion of the fault has enhanced permeability compared to the surrounding rock. The well portion of the objective function is very sensitive to the southern portion of the fault and has almost no sensitivity to the northern portion ([Figure 7-22](#)).

Basin-bounding faults - The fault generally trending north to south along the western edge of the Frenchman Flat basin (fault 39) is important to the well portion of the objective function (Figure 7-23). Fault 39 seemed important in directing water that entered the model domain from the Wahmonie Hills. The permeability of faults in the southern portion of Yucca Flat are also sensitive in the CPBA model (Figure 7-23). These faults seemed to move water from areas of higher head along the northern model boundary to the northwest corner of the Frenchman Flat alluvial basin.

Figure 7-21
WELL Perturbation Plot for Rock Valley Fault Permeability Multipliers
for CPBA-USGSD Model

Figure 7-22
WELL Perturbation Plot for Cane Spring Fault
Permeability Multipliers for CPBA-USGSD Model

Figure 7-23
WELL Perturbation Plot for Other Fault Permeability Multipliers
for CPBA-USGSD Model

7.2.6 Summary of Parameter Sensitivity Analysis

Three techniques are used to examine the model parameter sensitivity and correlations. The first approach calculated the correlation between a selected set of model parameters. Results show the expected inverse correlation between the LCA permeability and the fault permeability multiplier for the Rock Valley fault system, as these two parameters control the boundary fluxes into and out of the model domain. The correlation analysis also shows that the permeability values for the AA and VCU are positively correlated, while those for the LTCU and WCU are negatively correlated. These results reflect the dependence of model-calculated AA heads on the difference between the permeability values for the AA and the confining units underlying the AA in the Frenchman Flat basin. The LTCU and WCU are both responsible for maintaining the heads in the AA at the observed levels. These heads are higher than those in the LCA under the basin.

The second approach used for sensitivity analyses provides composite sensitivity of the calibration targets. This can be thought of as an importance measure, relative to the flow model calibration, of each of the observations. These results indicated that the most sensitive target is WW-5A. This target well is particularly sensitive to the permeability of the VCU and AA, which reflects the strong positive correlation calculated between these two permeability values. Also shown is the relative lack of sensitivity of the model to the model targets most associated with the LCA (boundary fluxes and WW-C, WW-C1, TW-3, WW-4, and WW-4A).

The final approach used is a perturbation analysis, which is used to examine the sensitivity of model calculations (as measured using a variety of metrics) to the different parameters, which are either varied or fixed during the model calibration. It is important to note the sensitivity of AA and OAA water levels to model parameters. Not surprisingly, these water levels showed considerable sensitivity to the AA permeability for all calibrated models. Other important aquifer permeability values are those for the TM-WTA and TM-LVTA. Sensitive aquitard reference permeability is observed for the VCU, WCU, and LTCU.

Faults in the Rock Valley fault system are the dominant features in the LCA underlying Frenchman Flat and exert significant control on the direction of regional groundwater movement. The faults in the Rock Valley fault system are assumed not to propagate upward into the alluvial or volcanic units in the BASE-USGSD flow model. The effect of the Rock Valley fault system on the water levels at

target well locations was modest. Faults located in the central portion of the basin appear to decrease the water-table elevation when their permeability increases, but faults in the LCA along the southern edge of the model domain increase the water-table elevation in the AA as their permeability decreases.

The Cane Spring fault separates the CP basin in the northwestern portion of the model domain from the Frenchman Flat basin. This fault has little bearing on the boundary fluxes in the CAU model, but it has a pronounced effect on the simulated hydraulic heads. During calibration of the BASE-USGSD model, the fault was separated into two sections: one south and west of the CP Hogback, and the other north and east of the CP Hogback. In the BASE-USGSD model, the southern section of the fault has much lower permeability than the surrounding rocks. Overall, water levels in the AA within the Frenchman Flat basin are very sensitive to changes in the permeability of the southern portion of the fault and show almost no sensitivity to the northern portion. If the entire fault were much tighter than the surrounding rocks, the modeled water-level elevation in the central portion of Frenchman Flat basin was lower than observed. This indicates that a small flux from CP basin is necessary to maintain water levels in the Frenchman Flat OAA and AA.

The permeability of certain HSUs play a very important role in maintaining hydraulic heads and routing groundwater fluxes into and out of the Frenchman Flat AA. Sensitivity analyses demonstrate how hydraulic heads are affected by changes in HSU permeabilities. It was evident from these analyses that contrasts in the permeabilities of key HSUs were as important as the absolute magnitudes of the permeabilities in affecting water levels within the AA and underlying HSUs.

Just as simulated water levels in northern Frenchman Flat were significantly affected by permeabilities assigned to different parts of the Cane Spring fault, the AA permeability itself was found to be an important factor in determining these water levels. Sensitivity analyses that focused on the factors affecting water levels in the AA demonstrated that increasing the permeability of the AA decreased water levels in the AA. Conversely, increasing the permeability of the Timber Mountain aquifers (TM-LVTA and TM-WTA) and the TSA resulted in a modest increase in the AA water levels by increasing groundwater flux into the OAA and AA in northern Frenchman Flat from

CP basin. Water levels in the OAA and AA appeared to be insensitive to all of the HSUs embedded within these units, including the BLFA, PCU1U, PCU1L, and PCU.

Water levels in central Frenchman Flat are maintained through a balance of AA and VCU permeabilities at the southern end and by permeability values assigned to the WCU and LTCU in the northern end. The permeability values for the AA and VCU are positively correlated, indicating that changes to the calibrated values of these units results in similar model responses at the calibration targets. Because many of the water-level observations in the AA are located in the central portion of the Frenchman Flat basin, the ability for the model to match hydraulic head data is most strongly influenced by the permeability contrast between the AA and the VCU.

Unlike the other volcanic confining units, which tend to increase water levels in the AA as their permeability is decreased, a decrease in the permeability of the WCU produces lower water levels in the AA. This effect suggests that simulated water levels in the central part of Frenchman Flat are sustained by groundwater flow from the Wahmonie Hills near the western edge of the model in the BASE-USGSD model.

Changes in the permeability of the LCA strongly affect the magnitude and direction of the lateral boundary fluxes. This is not surprising given the thickness and extent of the LCA along the model boundaries. Water levels throughout the Frenchman Flat basin alluvial and volcanic HSUs also showed some sensitivity to small changes in the permeability of the LCA. The LCA permeability appeared to influence shallow water levels in the alluvium by changing the heads in the LCA and thus affecting hydraulic gradients across the confining units that separate the AA from the LCA.

However, the relative hydrologic isolation of the AA from the regional LCA was apparent in the limited influence that changes to the AA permeabilities had on boundary fluxes.

8.0 EVALUATION OF GROUNDWATER FLOW PATHS AND TRAVEL TIMES IN FRENCHMAN FLAT USING ^{14}C AND OTHER GEOCHEMICAL INDICATORS

In this section, groundwater geochemical and isotopic data are examined in the context of the overall hydrologic setting and paleoclimatic history of Frenchman Flat to estimate groundwater flow directions and velocities in the alluvium and tuff aquifers, thereby providing an independent basis for evaluating flow models presented in earlier sections of this report. To accomplish this goal, groundwater ^{14}C data are used to calculate groundwater ages and define evolutionary trends in other groundwater components (such as cation compositions) that help to identify groundwaters that lie along a flow path. The evolutionary trends in cation compositions are, in turn, used to provide estimates of groundwater age at locations where ^{14}C data are lacking. Selected flow paths identified from relative groundwater ages and cation compositions are also tested with geochemical inverse models to determine whether downgradient changes in other geochemical components could be explained through water/rock interactions. The accuracy of the estimated groundwater ^{14}C ages and the mobility of groundwater ^{14}C in the presence of potentially ^{14}C -sorbing mineral phases were evaluated by comparing the temporal variability in groundwater $^{36}\text{Cl}/\text{Cl}$ ratios based on these ^{14}C ages against theoretical reconstructions of past atmospheric ^{36}Cl production and against 40,000-year-long archives of past meteoric $^{36}\text{Cl}/\text{Cl}$ deposition preserved in regional packrat middens. The calculated groundwater ages are subsequently used to calculate transit times and flow velocities between well pairs that may be useful for evaluating the results of future transport models that will be developed from the flow models presented in this report.

The analysis presented in this section is intended to complement another recent groundwater geochemical study by Hershey et al. (2005) that focused primarily on groundwater flow and mixing in the LCA near Frenchman Flat. That study noted that large differences in the composition of groundwater in the alluvium and tuffs that fill the basin and the composition of LCA groundwater on the perimeter of the basin preclude the possibility of significant inflow from the LCA into the basin

fill. That conclusion is consistent with the observation that hydraulic heads in the tuff and alluvium within the basin are higher than in the LCA along the basin perimeter, a condition that eliminates the possibility of flow from the LCA into the tuffs and alluvium ([Section 3.0](#)). For this reason, groundwater hydrochemical and isotopic data from the LCA are not considered in this section.

8.1 Hydrogeologic Setting

Groundwater flow directions in the alluvium and tuffs of Frenchman Flat are difficult to identify from hydraulic data alone because of the small differences in hydraulic head across the basin, the sparseness and uncertainty of the water-level data, and possible water-level changes associated with poorly documented withdrawals from local water-supply wells in the 1950s (Winograd and Thordarson, 1975, p. C57-C62; SNJV, 2004d). To estimate groundwater flow velocities from groundwater ^{14}C data, however, it is first necessary to establish groundwater flow directions. In the absence of diagnostic hydraulic head data, this study relies on indirect evidence for groundwater flow directions provided by the hydrologic setting, as well as on expected evolutionary trends in the geochemical data themselves.

Hydrologic studies of the unsaturated alluvium in both Frenchman Flat and nearby Yucca Flat have clearly established that net infiltration below the root zone in the alluvium is nonexistent under the present climate (Tyler et al., 1996; Walvoord et al., 2002a and b). Using pore-water ages estimated from Cl deposition rates, data from the unsaturated zone at boreholes UE-5 PW-1 and UE-5 PW-3 in northern Frenchman Flat have been further interpreted to show that no significant recharge occurred through the thick alluvium filling the basin even under the relatively wet conditions that existed in the late Pleistocene. This was a time in which precipitation was 30 to 50 percent higher than today, based on paleoclimatic conditions reconstructed from fossilized vegetation preserved in packrat middens (Tyler et al., 1996; Forester et al., 1999, p. 32). The periodic infiltration pulses that did penetrate the root zone at boreholes UE-5 PW-1 and UE-5 PW-3 in the last 100,000 years were of insufficient magnitude or duration to reach the water table, which is at depths greater than 200 m at these boreholes (Tyler et al., 1996, Figure 3). At borehole UE-5 PW-2, also in northern Frenchman Flat, an infiltration event with a flux of approximately 4 mm/yr but of unknown duration occurred between 25,000 to 35,000 years ago that flushed Cl from the unsaturated zone; however, Cl has been accumulating near the root zone since that infiltration event occurred, indicating no deep infiltration since that time (Tyler et al., 1996).

The central part of the Frenchman Flat basin contains a dry playa that floods periodically, but it is likely that the floodwater remains on the playa surface until it evaporates without producing significant infiltration. Although no unsaturated zone studies have been done on Frenchman Flat playa to directly confirm this conclusion, indirect evidence is provided by a study of a playa in central Nevada where groundwater levels are shallow enough that groundwater is discharged from the playa (Thomas et al., 1996). This study shows that the upward hydraulic head gradients that produce groundwater discharge are relatively constant in time and that downward hydraulic gradients are not induced beneath the playa even when the playa is periodically flooded (Thomas et al., 1996, p. C10). The absence of significant recharge following flooding was attributed by the authors of the study to the fact that the playa sediments swell quickly when wet, closing cracks that initially allow some moisture to infiltrate.

From these observations, it appears that groundwater recharge in Frenchman Flat results primarily from infiltration on the low bedrock hills bordering the basin, such as Massachusetts Mountain in the northwest or the Wahmonie Hills to the west, or from runoff from these hills into the alluvium along the basin margins. In both cases, groundwater will be likely to move away from the basin margins toward the interior of the basin where recharge has been negligible for at least the last 25,000 years. Besides providing general indications of flow directions within the basin, this analysis also suggests that interpretations of travel times and flow velocities based on groundwater ^{14}C data from the basin interior will not be adversely affected by significant additions of groundwater recharge between the groundwater sampling locations. Infiltration on the low carbonate hills to the east of Frenchman Flat recharges the LCA which, as mentioned previously, is unlikely to contribute groundwater to the alluvium and volcanic rocks in Frenchman Flat due to its lower hydraulic head ([Figure 2-2](#)).

The conceptual model of net infiltration and recharge presented in this section is consistent with the recharge models developed by the USGS that predict modern recharge is present only beneath and adjacent to the bedrock hills bordering the basin ([Section 3.0](#)). Based on the analysis of the hydrogeologic setting presented here, it seems reasonable to assume as a working hypothesis that groundwater in the alluvium and tuffs flows southward or southeastward from the low hills on the northern and western perimeter of the basin toward the basin center.

8.2 Groundwater Carbon-Isotope Data

Naturally occurring isotopes of carbon of interest to this study include ^{13}C and ^{14}C . Carbon-13 is used to help interpret the mineral sources and water/rock interactions that have affected the dissolved inorganic carbon (DIC) in groundwater, whereas ^{14}C decreases along a flow path due to radioactive decay can be used to estimate groundwater transit times and velocities between locations in an aquifer (Clark and Fritz, 1997). Carbon-14 has been used for almost 40 years in hydrologic studies to interpret the age of groundwater and estimate its rate of movement (see Glynn and Plummer, 2005, for an overview of these applications).

The primary means used to date Frenchman Flat groundwater in this study is the ^{14}C associated with the DIC of the groundwater. The $\delta^{13}\text{C}$ and ^{14}C associated with the DIC, and also alkalinity data from the groundwater of the alluvium and tuff in Frenchman Flat, are presented in [Table 8-1](#). These data are plotted in [Figures 8-1](#) and [8-2](#). In addition, uncorrected and corrected groundwater ages are presented in [Table 8-1](#). The methods by which these ages are calculated are described later within this section.

Radiocarbon (^{14}C) is produced naturally in the upper atmosphere from the bombardment of nitrogen by neutrons generated from cosmic radiation and, more recently, from atmospheric nuclear testing (Clark and Fritz, 1997). The ^{14}C is then oxidized to carbon-14 dioxide ($^{14}\text{CO}_2$) which is dissolved in the ocean or incorporated into plants during photosynthesis and returned to the atmosphere during root respiration and by the decay of vegetation. Before atmospheric nuclear tests, the rate of ^{14}C production and its removal from the atmosphere by dissolution in the oceans, terrestrial burial, and radioactive decay were in approximate equilibrium, so atmospheric levels of ^{14}C have varied only slightly over most of the past 10,000 years. The relative constancy of atmospheric ^{14}C concentrations, combined with the relatively high solubility of CO_2 in groundwater and the long half-life of ^{14}C (5,730 years), have made ^{14}C a useful tool for dating groundwaters that are old enough for the ^{14}C to have undergone significant radioactive decay. The ^{14}C activity is reported as percent modern carbon (pmc), where modern carbon activity is defined as the approximate ^{14}C activity of wood grown in 1890 (13.56 disintegrations per minute per gram of carbon), before the dilution of ^{14}C in the atmosphere by the burning of fossil fuels. However, with the possible exception of groundwater from a few perched springs and groundwater that might have been affected by the CAMBRIC radionuclide

migration experiment (e.g., groundwater at Wells RNM-2s and UE-5n), most of the groundwater in the Frenchman Flat area is old enough that its ^{14}C is unaffected by either industrial activities or atmospheric nuclear testing.

Table 8-1
Groundwater Carbon Isotope Data, ^{14}C Dilution Factors, and Dissolved Inorganic Carbon Groundwater Ages (Uncorrected and Corrected)

Well	Alkalinity as HCO_3^- ^a (mg/L)	$\delta^{13}\text{C}^a$ (‰)	$^{14}\text{C}^a$ (pmc)	DIC Uncorrected Age (years)	q_{DIC}	DIC Corrected Age (years)	$q_{\delta^{13}\text{C}}$	$\delta^{13}\text{C}$ Corrected Age ^a (years)	Average Corrected Age (years)
Cane Spring	189	-9.6	86	1,246	0.79	Modern	0.87	121	50
ER-5-3	191	-7.9	8.5	20,373	0.79	18,376	0.72	17,637	18,006
ER-5-4	319	-4.6	1.5	34,708	0.54	29,680	0.42	27,592	28,636
ER-5-4 #2	404	-0.1	1	38,059	0.43	31,079	0.01	modern	----
UE-5 PW-1	159	-8.0	20	13,301	0.94	12,820	0.73	10,669	11,744
UE-5 PW-2	169	-8.6	30	9,950	0.89	8,965	0.78	7,916	8,440
UE-5 PW-3	156	-7.6	18	14,172	0.96	13,848	0.69	11,116	12,482
UE-5c WW	184	-7.5	6.6	22,464	0.82	20,775	0.68	19,298	20,037
UE-5n	182	-8.0	18.8	13,813	0.82	12,214	0.73	11,181	11,698
WW-4	166	-10.9	19	13,725	0.90	12,887	0.99	13,650	13,269
WW-4a	154	-8.8	18.3	14,035	0.97	13,818	0.80	12,191	13,004
WW-5a	376	-4.6	2.6	30,162	0.46	23,775	0.42	22,957	23,366
WW-5b	186	-10.4	13.1	16,798	0.81	15,020	0.95	16,334	15,677
WW-5c	321	-6.0	3.3	28,192	0.54	23,112	0.55	23,183	23,147

Note: All groundwater ages are calculated assuming that $^{14}\text{C}_{\text{rech}} = 100$ pmc.

^a Source: SNJV, 2006, Appendix A

mg/L = Milligrams per liter

pmc = Percent modern carbon

q_{DIC} = Dilution factor reflecting the fraction of groundwater dissolved inorganic carbon acquired during recharge

$q_{\delta^{13}\text{C}}$ = Dilution factor reflecting the change in the $\delta^{13}\text{C}$ of groundwater since recharge

Between 12,000 and 30,000 years ago, atmospheric ^{14}C concentrations have been as much as 50 “modern” levels because of changes in ^{14}C production associated with the strength of the earth’s geomagnetic field and changes in the earth’s carbon cycle (see, for example, Stuiver et al., 1998; Bard et al., 1998; Kitagawa and van der Plicht, 1998; Beck et al., 2001). Although accounting for these variations atmospheric ^{14}C activities is considered critical in disciplines such as anthropology, these variations are almost always ignored in hydrologic studies because they generally introduce errors that have little practical importance. For example, if ^{14}C ages are calculated assuming that original

Figure 8-1

Carbon-14 (^{14}C) Versus Delta Carbon-13 ($\delta^{13}\text{C}$) for Volcanic and Alluvial Groundwaters

Figure 8-2

Delta Carbon-13 ($\delta^{13}\text{C}$) Versus Inverse Alkalinity for Non-LCA Wells and Springs

atmospheric concentrations were 100 pmc when in fact they were 150 pmc, the calculated ages would underestimate the true age by about one ^{14}C half-life, or 5,730 years. Thus, a groundwater estimated to be 25,000 years old might actually be almost 31,000 years old. In most practical hydrologic applications, this is considered an acceptable approximation because in either case, the groundwater is extremely old. Like many other hydrologic studies (see, for example, Plummer et al., 2004), the present study ignores the complicating effects of atmospheric ^{14}C activities variations in the late Pleistocene on the calculated groundwater ages. Although this simplification introduces some imprecision to the calculated ^{14}C ages presented in this report, it does not change the overall conclusion of this report derived in the following sections that the groundwater in Frenchman Flat is very old and groundwater velocities are very slow.

Carbon-13 abundances are commonly expressed in delta (δ) notation as a function of the $^{13}\text{C}/^{12}\text{C}$ ratio in the sample relative to the $^{13}\text{C}/^{12}\text{C}$ ratio in a standard:

$$\delta^{13}\text{C} = [(^{13}\text{C}/^{12}\text{C})_{\text{sample}} / (^{13}\text{C}/^{12}\text{C})_{\text{PDB}} - 1.0] \cdot 1000 \quad (8-1)$$

where $(^{13}\text{C}/^{12}\text{C})_{\text{PDB}}$ is the isotopic ratio of the Pee Dee Belemnite, a marine invertebrate fossil from the Pee Dee Formation that forms the standard for $\delta^{13}\text{C}$ abundances. Groundwater $\delta^{13}\text{C}$ data are reported as differences in per mil (‰) relative to the standard.

Because most of the carbon initially in groundwater is derived by dissolving $\text{CO}_2(\text{g})$ respired by plants in the soil zone, groundwaters (as well as pedogenic carbonates) initially have $\delta^{13}\text{C}$ values that reflect soil-gas compositions. In the Great Basin, soil zone CO_2 has $\delta^{13}\text{C}$ values that decrease from about -12 ‰ at a 900 m elevation to about -20 ‰ at 2,700 m elevation for reasons related to plant type and density and moisture availability (Quade et al., 1989). Soil water and pedogenic carbonates precipitated from infiltrating water have equilibrium $\delta^{13}\text{C}$ values that are about 8 and 9 ‰ heavier, respectively, than the soil zone CO_2 because of isotopic fractionation of carbon between the gas, liquid, and solid phases (Clark and Fritz, 1997). For instance, at the average elevation of Rainier Mesa (~ 2,300 m), the expected $\delta^{13}\text{C}$ of soil zone CO_2 , soil water and pedogenic carbonate would be about -18, -10, and -9 ‰ based on these relationships. Less than complete equilibrium fractionation between soil gas and water, as might occur when rapid infiltration and recharge to the water table takes place, would result in slightly lighter $\delta^{13}\text{C}$ values for the recharge water than those estimated from assumed isotopic equilibrium. Once groundwater is isolated from soil zone CO_2 , its $\delta^{13}\text{C}$ is

unmodified unless it interacts with carbon-bearing minerals.

The DIC of groundwater can be modified through the dissolution of calcite (CaCO_3):

In this case, the isotopically light carbon associated with the dissolved CO_2 is mixed with the (usually) heavier carbon associated with calcite, so that the $\delta^{13}\text{C}$ of the DIC in the groundwater evolves to a value that is intermediate between the CO_2 and the calcite. Note that the DIC of groundwater includes the contributions from $\text{CO}_2(\text{aq})$, bicarbonate (HCO_3^-), and carbonate (CO_3^{2-}), whose relative importance shifts as a function of pH.

When dolomite [$\text{CaMg}(\text{CO}_3)_2$] is present in the alluvium, as would be expected toward the southern and southeastern parts of Frenchman Flat where the alluvium was shed from mountains formed partly by dolomitic carbonate rock (Warren et al., 2002), the dissolution of dolomite by calcite-saturated groundwater can occur, with calcite being precipitated as the dolomite dissolves:

In this case, the precipitation of calcite leaves the $\delta^{13}\text{C}$ of the groundwater relatively unchanged, whereas the dissolution of dolomite adds carbon with a $\delta^{13}\text{C}$ of ~ 0 ‰ (Thomas et al., 1996).

During calcite precipitation, the heavier carbon isotopes (^{14}C and ^{13}C) become preferentially incorporated into the calcite by isotope fractionation, so that the ^{14}C and ^{13}C concentrations of the groundwater are lower than before precipitation occurred. However, these effects on ^{14}C and $\delta^{13}\text{C}$ are secondary compared to the other uncertainties that affect the interpretation of groundwater ^{14}C data. For example, based on fractionation factors listed in Clark and Fritz (1997), if groundwater with a ^{14}C activity of 10 pmc and a $\delta^{13}\text{C}$ of -5.0 ‰ lost 20 percent of its DIC during calcite precipitation, the DIC remaining in the groundwater would have a ^{14}C of 9.95 pmc and a $\delta^{13}\text{C}$ of -5.2 ‰. Although somewhat more significant than for ^{14}C , isotope fractionation of ^{13}C during calcite precipitation introduces relatively little error when interpreting ^{14}C ages when compared to the uncertainty in the $\delta^{13}\text{C}$ values of the dissolving carbonate phases. For this reason, the effects of isotope fractionation during calcite precipitation are not considered further in this study.

8.3 Approach to Correcting Groundwater ^{14}C Ages

As in other study areas, the primary factor complicating the interpretation of groundwater ^{14}C data from Frenchman Flat is the possible interaction between groundwater and the trace amounts of calcite disseminated throughout the deeper layers of the alluvium (Warren et al., 2002) or present as fracture coatings in the tuff aquifers. These potential interactions include (1) the dissolution of ^{14}C -free calcite in groundwater, (2) loss of ^{14}C in groundwater through isotope exchange with calcite (sometimes interpreted as groundwater ^{14}C loss during calcite recrystallization [Glynn and Plummer, 2005]), and (3) sorption of ^{14}C (as $\text{H}^{14}\text{CO}_3^-$) onto calcite surfaces (Maloszewski and Zuber, 1991; Sheppard et al., 1998). Each of these processes tends to either lower the ^{14}C activity in the groundwater and/or retard its movement relative to the groundwater, thus resulting in estimates of groundwater age that are erroneously high or estimates of groundwater velocity that are erroneously low if they are not accounted for in the interpretation.

To correct for the first two types of interactions, two commonly utilized analytical correction methods are applied to the ^{14}C data from Frenchman Flat (Clark and Fritz, 1997). The first method uses the downgradient increase in DIC relative to recharge water to estimate the total fraction of the groundwater DIC that was acquired during recharge. This fraction (q_{DIC}) is calculated as:

$$q_{\text{DIC}} = \text{DIC}_{\text{rech}} / \text{DIC}_{\text{sample}} \quad (8-4)$$

where *rech* indicates recharge and *sample* indicates the groundwater sample at the well under consideration. Groundwater DIC includes dissolved $\text{CO}_2(\text{aq})$, HCO_3^- , and CO_3^{2-} and is essentially equivalent to alkalinity (the sum of milliequivalents per liter [meq/L] HCO_3^- and meq/L CO_3^{2-}) at the pH values typical of groundwater in the Frenchman Flat basin. Thus, alkalinity increases can be used to approximate the DIC increases between the recharge and downgradient groundwaters.

Under the assumption that the dissolved calcite was old enough that it essentially has no ^{14}C , the factor q_{DIC} represents the dilution of the ^{14}C originally in the sample at the time of recharge by dissolution of non-radiogenic carbon (mostly ^{12}C). This factor is then used to adjust the initial ^{14}C activity in the decay equation so that the calculated age reflects only the ^{14}C decrease associated with radioactive decay and not decreases in ^{14}C caused by water/rock interaction:

$$t_{\text{years}} = (1/\lambda) \cdot \ln(^{14}\text{C}_{\text{rech}} \cdot q_{\text{DIC}} / ^{14}\text{C}_{\text{sample}}) \quad (8-5)$$

where t_{years} is the ^{14}C age in years and λ is the decay constant for ^{14}C ($1.21 \times 10^{-4} \text{ years}^{-1}$).

The second correction method uses the differences in the $\delta^{13}\text{C}$ of recharge and of calcite in the aquifer to estimate an analogous dilution factor:

$$q_{\delta^{13}\text{C}} = (\delta^{13}\text{C}_{\text{sample}} - \delta^{13}\text{C}_{\text{calcite}}) / (\delta^{13}\text{C}_{\text{rech}} - \delta^{13}\text{C}_{\text{calcite}}) \quad (8-6)$$

Changes in the $\delta^{13}\text{C}$ of the groundwater since it was recharged, as expressed in the dilution factor $q_{\delta^{13}\text{C}}$, reflect the effects of both calcite dissolution and isotope exchange during calcite recrystallization on the ^{14}C originally in the recharge water. The dilution factor $q_{\delta^{13}\text{C}}$ is used in an identical manner to q_{DIC} in equation (8-5).

Equation (8-5) with the appropriate dilution factor (either q_{DIC} or $q_{\delta^{13}\text{C}}$) can be applied and interpreted in several ways. If the recharge composition is defined by sampling shallow groundwater from beneath the recharge area, the measured ^{14}C activity of the shallow groundwater can be less than atmospheric (or soil-gas) activity because of finite travel times through the unsaturated zone or interaction with calcite in the unsaturated zone. When $^{14}\text{C}_{\text{rech}}$ is defined by shallow groundwater compositions, the application of equation (8-5) produces ages that are, in fact, groundwater travel times from the recharge area to the downgradient sampling location. Alternatively, the age of the groundwater can be calculated with equation (8-5) if the atmospheric ^{14}C activity is used in the numerator, provided the dilution factors (either q_{DIC} or $q_{\delta^{13}\text{C}}$) also incorporate the effects of unsaturated zone processes like the dissolution of pedogenic calcite as well as water/rock interactions in the saturated zone. The latter approach is used in this report by postulating the characteristics of recharge before any water/rock interaction. These values are estimated graphically in the following section along with the isotopic composition of the carbonate mineral phase.

8.4 Corrections to Groundwater ^{14}C Ages in Frenchman Flat

To calculate the ^{14}C dilution factors q_{DIC} or $q_{\delta^{13}\text{C}}$ necessary to correct the groundwater ^{14}C ages in Frenchman Flat, the compositions of the recharge and mineral end-members were estimated graphically by plotting the groundwater $\delta^{13}\text{C}$ data against the inverse of the groundwater alkalinity data (Figure 8-2). When plotted this way, groundwaters less affected by water/rock interaction

should have lighter $\delta^{13}\text{C}$ values and lower alkalinity (higher inverse alkalinity) and fall in the lower right corner of the plot, whereas groundwaters more affected by water/rock interaction should have heavier $\delta^{13}\text{C}$ values and higher alkalinities (lower inverse alkalinity) and fall in the upper left part of the plot. If the recharge and calcite end-member compositions are relatively uniform, the groundwater data should plot along a roughly linear trend between the recharge and calcite end-members. A visual best-fit trend line was fit to the data shown in [Figure 8-2](#) (ignoring data from Well ER-5-4 #2) that defines the expected evolution of groundwater $\delta^{13}\text{C}$ values and alkalinity as the groundwater moves from the recharge area and undergoes progressive water/rock interaction with calcite or dolomite.

Several interpretations of the cluster of data that plot in the lower right corner of [Figure 8-2](#) are possible. One possible interpretation is that the scatter in these data represent the natural variability in $\delta^{13}\text{C}$ and alkalinity that arises because of differences in vegetation cover, plant types, and climate, and that none of these groundwaters have experienced significant interaction with carbonate rocks or minerals. In this case, average groundwater recharge is estimated to have a $\delta^{13}\text{C}$ of -8.7 ± 1.2 ‰ and an alkalinity of 174 ± 14 mg HCO_3^-/L . In support of the notion that these groundwaters did not interact with carbonate minerals, it can be noted that the average $\delta^{13}\text{C}$ of -8.7 ± 1.2 ‰ is as light as or lighter than the $\delta^{13}\text{C}$ value expected for groundwater in isotopic equilibrium with modern soil zone CO_2 in the hills surrounding Frenchman Flat. As noted earlier, the $\delta^{13}\text{C}$ of soil zone CO_2 in the southern Great Basin is strongly related to elevation because of elevation-dependent changes in plant types and precipitation (Quade et al., 1989). At elevations typical of the hills surrounding Frenchman Flat (1,200 to 1,400 m), present-day soil zone CO_2 would have a $\delta^{13}\text{C}$ of approximately -14 ‰, and the $\delta^{13}\text{C}$ of soil water in isotopic equilibrium with the CO_2 would be approximately 9 ‰ heavier at 15°C ($\delta^{13}\text{C} \sim -5$ ‰) because of isotope fractionation (Clark and Fritz, 1997, p. 121).

An alternative explanation of the data that plot in the lower right corner of [Figure 8-2](#) is that all of these groundwaters have experienced at least some water/rock interaction with carbonate rocks or minerals, and that the relatively light $\delta^{13}\text{C}$ values for this cluster of groundwaters reflect the compensating effects of the lighter $\delta^{13}\text{C}$ of soil-gas CO_2 that existed during the late Pleistocene, when vegetation and moisture conditions near Frenchman Flat were similar to those that exist today only at elevations of 2,000 m or higher (Quade et al., 1989). In support of this interpretation, similar arguments have been made to infer a Pleistocene origin for pedogenic calcite at Yucca Mountain

because its $\delta^{13}\text{C}$ is too light to be in isotopic equilibrium with modern CO_2 in the soil zone at the same elevation (Quade and Cerling, 1990).

The second alternative (all groundwaters have experienced some water/rock interaction with carbonate rocks or minerals) is adopted for the purpose of this study in order to calculate the youngest reasonable ^{14}C ages. The recharge end-member is estimated graphically to have an alkalinity of 150 $\text{mg HCO}_3^-/\text{L}$ (an inverse alkalinity of 0.0067) and a $\delta^{13}\text{C}$ of -11 ‰ so that it is both slightly more dilute and slightly lighter in $\delta^{13}\text{C}$ than all of the groundwater samples (each of which is thus assumed to have undergone at least some interaction with calcite after recharge). The assumed values for alkalinity and $\delta^{13}\text{C}$ of recharge are reasonable given the alkalinity of tunnel seepage at Rainier Mesa (~ 140 $\text{mg HCO}_3^-/\text{L}$) and the $\delta^{13}\text{C}$ of perched springs in the NTS area (-9.0 +/- 2.0 ‰), according to data compiled for a study of groundwater in nearby Yucca Flat (SNJV, 2006). Further support for this choice of recharge end-member compositions is provided by the observation that tritium-free perched groundwater discharging from Cane Spring has a ^{14}C activity of 86 pmc (Table 8-1). The absence of tritium from Cane Spring discharge indicates its age is at least 50 years old and thus that its ^{14}C activity was not affected by atmospheric nuclear tests. If larger corrections to its age were made by postulating recharge characteristics either more dilute or isotopically lighter than the assumed values, the age of Cane Spring groundwater becomes negative, indicating that the maximum reasonable corrections have been made with the assumed recharge end-member characteristics.

The carbonate end-member isotope composition necessary for use with the $q_{\delta^{13}\text{C}}$ factor was estimated by extending the groundwater evolution line from the estimated recharge through the cluster of three more concentrated and isotopically heavier groundwater samples (WW-5a, WW-5c, and ER-5-4) to its intersection with the y-axis (Figure 8-2). Because solid calcite has an essentially infinite concentration (its inverse alkalinity is zero), the y-intercept of $\delta^{13}\text{C} \sim 0$ ‰ is interpreted to be the representative composition of the carbonate end-member. A $\delta^{13}\text{C}$ of ~ 0 ‰ is typical of Paleozoic marine carbonate rocks in the NTS area and may thus be a reasonable estimate for carbonate lithic fragments contained in the alluvium. Based on unsaturated-zone data from Yucca Flat, however, the $\delta^{13}\text{C}$ of calcite coatings in the alluvium of Frenchman Flat could be somewhat lighter (-3.1 +/- 1.7 ‰) (Rose et al., 2000; Hershey et al., 2005).

The corrected groundwater ages calculated using the ^{14}C dilution factors q_{DIC} and $q_{\delta^{13}\text{C}}$ are listed in Table 8-1 and compared in Figure 8-3. The corrected ages using these two correction methods are generally in good agreement with each other, as indicated by the proximity of the results to the one-to-one line. This indicates that, in general, calcite dissolution rather than isotope exchange has been the process dominating the evolution of alkalinity and $\delta^{13}\text{C}$ in the tuff and alluvial aquifers of Frenchman Flat. Only the corrected ages for groundwater at Well ER-5-4 #2 are in significant disagreement with each other. The DIC-based correction method gives a ^{14}C age for this groundwater of nearly 31,000 years, whereas the $\delta^{13}\text{C}$ -based correction method indicates that this groundwater is essentially modern. The extremely heavy $\delta^{13}\text{C}$ of the Well ER-5-4 #2 groundwater (-0.1‰) and the fact that it plots far above the dissolution trend of Figure 8-2 indicates that this groundwater has probably undergone significant isotope exchange as a result of prolonged contact with calcite. This observation tends to favor the age based on the $\delta^{13}\text{C}$ -based correction method because this method theoretically accounts for isotope exchange. However, based on the great depth of the sample (1,023 to 1,075 m below sea level, its origin in a tuff confining unit (the LTCU), and the presence of old ($\sim 28,000$ years) groundwater in the overlying alluvium at nearby Well ER-5-4, it is unlikely that this groundwater has a recent origin. Alternative methods of estimating the groundwater age at Well ER-5-4 #2 are presented in later sections of this report that indicate an age for this groundwater in excess of 30,000 years.

The corrected ages indicate that groundwater younger than about 8,500 years is absent from both Frenchman Flat and nearby CP basin (represented by the WW-4 and WW-4a data). Only water at a perched spring (Cane Spring) appears to have any significant amount of post-Pleistocene recharge. The apparent absence of significant post-Pleistocene recharge in Frenchman Flat is consistent with paleo-climate interpretations from pack-rat midden data (Forester et al., 1999; Spaulding and Graumlich, 1986) and from regional spring-discharge deposits (Forester et al., 1999; Quade et al., 1995) which indicate that increasing aridity had caused plant communities to change and springs to cease flowing in nearby basins by 9,000 to 10,000 years before present.

8.5 Comparison of DI^{14}C and DO^{14}C Groundwater Ages

Groundwater samples from a limited number of wells in the Frenchman Flat area were also analyzed for the ^{14}C of the dissolved organic carbon (DOC). Theoretically, this ^{14}C (subsequently referred to as

Figure 8-3
Comparison of Groundwater ^{14}C Ages Calculated with the DIC-Based and $\delta^{13}\text{C}$ -Based Correction Methods

Note: The solid line is the one-to-one line.

DO^{14}C) is not affected by the water/rock interactions that complicate the interpretation of the ^{14}C of the DIC component (i.e., the DI^{14}C) so that the ages can be calculated from the DO^{14}C without any corrections. A comparison of the ages calculated from the DO^{14}C data and the average corrected age calculated from the DI^{14}C data is shown in [Figure 8-4](#).

Except for groundwater at WW-4a in CP basin, the DO^{14}C and corrected DI^{14}C ages are in significant disagreement with each other. The DO^{14}C data indicate that groundwaters at the majority of the wells shown in [Figure 8-4](#) are Holocene (less than 10,000 years) in age, with ages calculated from the groundwater DO^{14}C data being half or less of most of the corresponding corrected DI^{14}C ages. The DO^{14}C data also indicate that groundwater in the center of the basin at Well ER-5-4 is as young as groundwater on the perimeter of the basin at Wells PW-3 or UE-5c WW, an age relationship that seems unlikely based on the unsaturated zone studies described earlier which concluded that recharge through the alluvium has not occurred over the past 25,000 years (Tyler et al., 1996).

Figure 8-4
Comparison of DO¹⁴C Ages with Average Corrected DI¹⁴C Ages of Groundwater in Tuff and Alluvium in Frenchman Flat

Ages calculated with both the DO¹⁴C and DI¹⁴C data assumed that $^{14}C_{rech}$ is 100 pmc. For ages calculated using the DI¹⁴C data, $^{14}C_{rech}$ was modified by a dilution factor (either q_{DIC} or $q_{\delta 13C}$) between 0.4 and 1.0 to account for ¹⁴C dilution by carbon introduced through water/rock interactions (Table 8-1). These corrections had the effect of decreasing the DI¹⁴C ages compared to their uncorrected values, so the discrepancy between the DI¹⁴C and DO¹⁴C ages was decreased and not increased as a result of these corrections. Likewise, the value of $^{14}C_{rech}$ used with the DO¹⁴C data in this study is 100 pmc, whereas previous studies of Frenchman Flat groundwater (Hershey et al., 2005) used a value for $^{14}C_{rech}$ of 66 pmc based on the DO¹⁴C of tritium-bearing groundwater in Fortymile Canyon. The use of 66 pmc rather than 100 pmc would have made the groundwater DO¹⁴C ages in Frenchman Flat younger still (Hershey et al., 2005, Table 9).

Other possible causes of the discrepancy between the DO¹⁴C- and DI¹⁴C-based ages are (1) interaction between the DO¹⁴C and young organic matter in the alluvium (2) contamination of the DO¹⁴C by oil or other organic material introduced into the aquifer during drilling or sampling, or (3) sorption and retardation of DI¹⁴C on calcite, iron oxide or other minerals. Explanation (1) is

unlikely because the alluvium in Frenchman Flat is old enough (BN, 2005a) that any organic matter deposited within it would have a very low (< 1 pmc) ^{14}C activity. Also, groundwater from Well PW-3 is produced from a volcanic aquifer that has little or no organic carbon. Explanation (2) is also unlikely because oil introduced during drilling or pumping would be millions of years old and, therefore, also ^{14}C free. Explanation (3) is evaluated in the following section by comparing the temporal variations in atmospheric deposition of ^{36}Cl preserved in terrestrial records with groundwater ^{36}Cl data and their corresponding DI^{14}C and DO^{14}C ages. The groundwater record of ^{36}Cl variations should mimic the record of atmospheric ^{36}Cl deposition preserved in the terrestrial records if the groundwater ages are correct and the ^{14}C in the groundwater is moving at same rate as non-sorbing ions such as Cl.

8.5.1 Evaluation of Groundwater DO^{14}C and DI^{14}C Ages Using ^{36}Cl Data

Chlorine-36 is a radioactive isotope with a half-life of 301,000 that is produced naturally by (1) the cosmic-ray spallation of ^{40}Ar , and neutron activation of ^{36}Ar and ^{35}Cl in the atmosphere; (2) cosmic-ray spallation of K and Ca at or near ground surface; and (3) activation of ^{35}Cl by neutrons generated by U/Th decay in the subsurface (Moran and Rose, 2003). Measured ^{36}Cl is usually reported relative to the total Cl as the $^{36}\text{Cl}/\text{Cl}$ ratio. In situ subsurface production of ^{36}Cl from non-atmospheric sources is generally negligible compared to atmospheric sources, except in U-rich areas where radioactive decay creates relatively high neutron fluxes (Andrews et al., 1986).

The $^{36}\text{Cl}/\text{Cl}$ ratio of precipitation depends significantly on the distance from the oceans, which is a major source of stable Cl originating from dried sea spray (Moysey et al., 2003; Davis et al., 2003). Modern $^{36}\text{Cl}/\text{Cl}$ ratios in the vicinity of the NTS before nuclear weapons tests in the South Pacific in the late 1950s and early 1960s are estimated to be about 400 to 500×10^{-15} (Fabryka-Martin et al., 1993), but this ratio increased by more than two orders of magnitude as a result of the activation of ^{35}Cl in the ocean by the large neutron fluxes produced during those tests. However, even before atmospheric nuclear testing, the $^{36}\text{Cl}/\text{Cl}$ ratio in precipitation varied naturally, although in a much more subdued fashion, as a result of variations in ^{36}Cl production caused by changes in the strength of the earth's geomagnetic field and, possibly, by changes in atmospheric circulation patterns that affected the position of the jet stream during major climatic oscillations (Plummer et al., 1997).

Theoretical reconstructions of atmospheric ^{36}Cl production can be calculated from known variations in the strength of the earth's geomagnetic field (Tyler et al., 1996, Figure 6).

The variability in ^{36}Cl deposition within the Great Basin has also been estimated from pack-rat midden data (Plummer et al., 1997). Some pack-rat middens in the American Southwest have been continuously inhabited by pack-rats for tens of thousands of years and have been preserved from erosion by wind or dissolution by water at their location beneath rock ledges or shallow caves. The middens (or nests) are built in layers by successive generations of pack-rats using plant material from nearby areas that is cemented with rat urine that dries and hardens to consolidate the midden. The plant assemblages preserved in the middens have been carbon-dated, and the environmental conditions existing at different times in the southern Great Basin have been estimated based on the precipitation amounts, seasonality, and temperature ranges required by (or tolerated by) their modern plant equivalents (Spaulding, 1985; Forester et al., 1999). In addition to providing an archive of paleoclimatic conditions, pack-rat middens have also been used to estimate the variability in ^{36}Cl deposition within the Great Basin (Plummer et al., 1997). Pack-rats gain nearly all their moisture from the plant material they consume, and the $^{36}\text{Cl}/\text{Cl}$ ratio of the plant material reflects the ratio of the soil moisture and, ultimately, of the precipitation that sustained the plants. Evaporation of shallow infiltration in the root zone, or the further evaporation of the rat urine as it dries and crystallizes, do not alter the $^{36}\text{Cl}/\text{Cl}$ ratio of the precipitation from which soil moisture and urine were derived (Plummer et al., 1997).

Frenchman Flat groundwater $^{36}\text{Cl}/\text{Cl}$ ratios (Table 8-2) were plotted as a function of the DO^{14}C and DI^{14}C ages (Figure 8-5) and compared to the two estimates of ^{36}Cl deposition: (1) reconstructions of ^{36}Cl production estimated from known variations in the earth's geomagnetic field (Tyler et al., 1996, Figure 6), and (2) records of $^{36}\text{Cl}/\text{Cl}$ deposition in southern Nevada preserved in pack-rat middens (Plummer et al., 1997, Figures 2 and 3). As stated earlier, temporal variations in the groundwater $^{36}\text{Cl}/\text{Cl}$ record based on the corrected DI^{14}C ages should resemble the temporal variations of $^{36}\text{Cl}/\text{Cl}$ deposition recorded in the pack-rat midden data and estimated from the reconstructions of ^{36}Cl production, if the DI^{14}C travels without sorbing to calcite. Alternatively, it may be possible to eliminate either the groundwater DO^{14}C or DI^{14}C ages from further consideration if the temporal variations of $^{36}\text{Cl}/\text{Cl}$ deposition based on these ages are incompatible with the other records.

Table 8-2
Selected Groundwater Chemistry Data for Frenchman Flat

Well	Cl (mg/L)	³⁶ Cl/Cl (x 10 ¹⁵)	Na (mg/L)	Ca (mg/L)	δD (‰)	δ ¹⁸ O (‰)
Cane Spring	22	N/A	42	36	-90	-11.0
ER-5-3	14	842	64	12	-108	-14.0
ER-5-4	27	394	161	2.0	-108	-13.7
ER-5-4 #2	52	176	319	0.6	-102	-13.3
UE-11a	25	N/A	106	9.1	-111	-14.3
UE-5 PW-1	10	842	56	14	-107	-13.7
UE-5 PW-2	9	527	50	17	-106	-13.8
UE-5 PW-3	9	678	54	16	-104	-13.5
UE-5c WW	12	613	86	8.1	-106	-13.8
UE-5n	14	596,000	81	7.1	-106	-13.3
WW-1	6	N/A	73	5.5	N/A	N/A
WW-4	12	616	50	23	-94	-12.6
WW-4a	11	647	52	24	-99	-12.8
WW-5a	11	843	158	2.2	-108	-13.6
WW-5b	23	783	98	6.8	-107	-13.5
WW-5c	10	696	138	2	-108	-13.9

Data source: SNJV, 2006, Appendix A

N/A = Not available

First, it is worth noting that although they do not agree in their details, the estimated ³⁶Cl/Cl deposition ratios based theoretical reconstructions of ³⁶Cl production and the record of actual ³⁶Cl/Cl deposition preserved in the pack-rat midden data both indicate that ³⁶Cl/Cl ratios in precipitation prior to 10,000 years ago were, in general, a factor of 1.6 to 2 higher than they are at present in the NTS area (³⁶Cl/Cl ~500 x 10⁻¹⁵). Both records indicate a steep decline in ³⁶Cl/Cl ratios occurred 10,000 and 12,000 years ago, with ³⁶Cl/Cl ratios during the last 10,000 years slightly lower than they are at present. This indicates that unless there are other reasons (such as high tritium concentrations) to suspect that it was affected by nuclear weapons testing (as at Well UE-5n), groundwater with a ³⁶Cl/Cl ratio higher than about 600 x 10⁻¹⁵ must be late Pleistocene or very early Holocene in age.

Second, although the timing of the peaks and troughs in ³⁶Cl/Cl are not in complete accord, several large oscillations in deposition rates between 10,000 and 25,000 years ago are suggested by both the theory and the data. Some differences in these records are to be expected because actual ³⁶Cl/Cl deposition is a function not only of ³⁶Cl production rates, but also of stable Cl inputs from the oceans and nearby playas, as well as the degree of atmospheric mixing between the troposphere and the stratosphere where natural ³⁶Cl is produced (Plummer et al., 1997). According to Plummer et al., the peaks in ³⁶Cl/Cl deposition rates recorded in the pack-rat midden data between 10,000 to 12,000

Figure 8-5
Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratios, DO^{14}C and DI^{14}C Ages, Theoretical Reconstructions of ^{36}Cl Production, and $^{36}\text{Cl}/\text{Cl}$ Deposition Preserved in Pack-Rat Middens

The reconstruction of ^{36}Cl production is modified from Tyler et al. (1996, Figure 6) by assuming that past relative production rates scale directly with $^{36}\text{Cl}/\text{Cl}$ ratios in precipitation (presently estimated to be $\sim 500 \times 10^{-15}$). The pack-rat midden data are modified using scaling methods applied to data in Figures 2 and 3 of Plummer et al. (1997).

years, between 21,000 to 23,000 years, and at approximately 33,000 years may correspond with periods when the jet stream crossed into southern Nevada and brought with it periods of higher $^{36}\text{Cl}/\text{Cl}$ deposition associated with increased mixing across the tropopause.

In addition to the data shown in Figure 8-5, other $^{36}\text{Cl}/\text{Cl}$ data from the unsaturated zone at boreholes UE-5 PW-1, UE-5 PW-2, and UE-5 PW-3 in Frenchman Flat also had $^{36}\text{Cl}/\text{Cl}$ ratios of 600×10^{-15} to 900×10^{-15} between 20,000 and 40,000 years ago (Tyler et al., 1996, Figure 6). However, these pore-water data showed substantially smoother variations with time than the pack-rat midden data, possibly because of the effects of molecular diffusion within the pore water, and lack of information about $^{36}\text{Cl}/\text{Cl}$ variations during the last 20,000 years. These aspects of the pore-water data make them less suitable for evaluating the estimated groundwater ages than the more complete and detailed record provided by the pack-rat midden data. However, the elevated $^{36}\text{Cl}/\text{Cl}$ ratios in the pore water

indicate that the phenomena affecting $^{36}\text{Cl}/\text{Cl}$ ratios regionally in southern Nevada were also operative locally in Frenchman Flat at this time.

The comparison of the temporal variations in groundwater $^{36}\text{Cl}/\text{Cl}$ ratios using the DI^{14}C -based ages and the $^{36}\text{Cl}/\text{Cl}$ variations predicted by theory and measured from the pack-rat midden data indicate reasonably good consistency except at Well ER-5-4 (Figure 8-5). The highest groundwater $^{36}\text{Cl}/\text{Cl}$ ratios ($\sim 800 \times 10^{-15}$ or higher) are associated with peaks in the midden data at $\sim 12,000$ years (Well UE-5 PW-1) and at $\sim 23,000$ years (WW-5a), or in relatively data sparse periods between 15,000 and 20,000 years, with the theoretical reconstruction (WW-5b and Well ER-5-3). Likewise, the lower $^{36}\text{Cl}/\text{Cl}$ ratio and estimated DI^{14}C age of $\sim 8,500$ years of groundwater at Well UE-5 PW-2 are consistent with the pack-rat midden data and theoretical reconstruction in the early Holocene. In short, these general consistencies support the use of the corrected DI^{14}C ages and indicate that the DI^{14}C is moving together with conservative ions like Cl in the tuffaceous rocks and alluvium in Frenchman Flat.

Conversely, the DO^{14}C -based groundwater ages appear to be too young for at least four wells (WW-5c, UE-5 PW-3, UE-5c WW, and WW-5b) based on the comparison between the groundwater $^{36}\text{Cl}/\text{Cl}$ ratios at these wells with the pack-rat midden data and theoretical ^{36}Cl production curve. The $^{36}\text{Cl}/\text{Cl}$ data suggest that the groundwater DO^{14}C ages at these wells are at least several thousand years too young, although the earlier comparison with the DI^{14}C -based ages (Figure 8-4) suggests even larger errors in the DO^{14}C ages, including DO^{14}C ages at several other wells that cannot be refuted with the $^{36}\text{Cl}/\text{Cl}$ data (e.g., WW-5a and Well ER-5-4).

8.5.2 Estimation of the Original Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratio at Wells Affected by Halite Dissolution

The low groundwater $^{36}\text{Cl}/\text{Cl}$ ratios at Well ER-5-4 appear to support the use of the DO^{14}C -based age of $\sim 6,000$ years rather than the DI^{14}C -based age of $\sim 29,000$ years (Figure 8-5). However, it is likely that the incorporation of Cl through water/rock interaction has lowered the $^{36}\text{Cl}/\text{Cl}$ ratios at Well ER-5-4 and at the nearby Well ER-5-4 #2, based on the higher Cl concentrations at these wells relative to other groundwaters in the Frenchman Flat basin (Table 8-2 and Figure 8-6). It may be less obvious that Cl dissolution has lowered the $^{36}\text{Cl}/\text{Cl}$ ratio in groundwater at Well ER-5-4 because its $^{36}\text{Cl}/\text{Cl}$ ratio, unlike the $^{36}\text{Cl}/\text{Cl}$ ratio at Well ER-5-4 #2, is not clearly below any plausible meteoric

Figure 8-6
Evaluation of the Contribution of Dissolved Sodium (Na)
from Halite (NaCl) Dissolution in Frenchman Flat Groundwater

ratio; however, the proximity of Well ER-5-4 to Well ER-5-4 #2, the higher groundwater Cl concentrations at both wells, and their location near older playa sediments in the basin (BN, 2005a), suggest that the groundwater $^{36}\text{Cl}/\text{Cl}$ ratios at both wells have been affected by Cl dissolution. The effect of halite dissolution on $^{36}\text{Cl}/\text{Cl}$ ratios in groundwater at the NTS has previously been noted by Moran and Rose (2003) and Hershey et al. (2005).

To account for halite dissolution on the groundwater $^{36}\text{Cl}/\text{Cl}$ ratios at Wells ER-5-4 and ER-5-4 #2, it is assumed that halite in the sediments is completely free of ^{36}Cl . Given the ^{36}Cl half-life of 301,000 years, this condition will be approximately met after 2 to 3 million years, well within the range of possible ages of the basin fill in Frenchman Flat (BN, 2005a). In this case, the original $^{36}\text{Cl}/\text{Cl}$ ratio $(^{36}\text{Cl}/\text{Cl})_o$ can be calculated as:

$$(^{36}\text{Cl}/\text{Cl})_o = (^{36}\text{Cl}/\text{Cl}) \cdot (\text{Cl}/\text{Cl}_o) \quad (8-7)$$

where Cl_o is the original Cl concentration before halite dissolution and $^{36}Cl/Cl$ and Cl are the measured values. Using the average Cl concentration of the other Frenchman Flat groundwater (12.3 mg/L) as an estimate for Cl_o , the original $^{36}Cl/Cl$ ratios at Wells ER-5-4 and ER-5-4 #2 are calculated to be 852×10^{-15} and 743×10^{-15} , respectively. Thus, the estimate of the undiluted groundwater $^{36}Cl/Cl$ ratio at Well ER-5-4 suggests that this groundwater was also recharged during the Pleistocene, when higher $^{36}Cl/Cl$ ratios prevailed (Figure 8-5). Therefore, like the $DO^{14}C$ ages at Wells WW-5b, WW-5c, UE-5 PW-3, and UE-5c WW, the $DO^{14}C$ age of ~ 6,000 years at Well ER-5-4 is probably too young for this age to be plausible given that its original $^{36}Cl/Cl$ ratio is as high as estimated. The $DO^{14}C$ age of ~ 13,500 years at Well ER-5-4 #2 cannot be rejected because its adjusted $^{36}Cl/Cl$ ratio of 743×10^{-15} is similar to the values measured in the pack-rat middens at about this time. However, as presented in the following section, the age of Well ER-5-4 #2 groundwater estimated from its chemical evolution relative to other datable Frenchman Flat groundwaters is considerably older than 13,500 years.

8.5.3 Estimation of Groundwater Age Based on Groundwater Evolutionary Trends

It has long been recognized that groundwater in contact with rhyolitic tuffs at the NTS evolves toward a Na-HCO₃ type of water because the tuffs themselves are Na rich and because divalent cations like Ca, Mg, and Sr are removed from groundwater by cation exchange with Na on clays and zeolites (Schoff and Moore, 1964; Winograd and Thordarson, 1975; White et al., 1980). In this section, evolutionary trends involving Na and Ca concentrations are used qualitatively to establish which groundwaters are likely to have evolved from one another, and quantitatively, to calculate groundwater ages at Frenchman Flat wells where no carbon isotope data have been collected or where, as in the case of Well ER-5-4 #2, groundwater ^{14}C ages are ambiguous. Groundwater evolutionary trends have recently been used in ^{14}C studies at other sites to estimate groundwater ages beyond the effective limits of ^{14}C dating (~30,000 years) (Burton et al., 2002; Edmunds and Smedley, 2000).

The concentrations of Na (and Ca) versus Cl are presented in Figure 8-6. In addition, a halite (NaCl) dissolution line is represented in Figure 8-6 as the molar equivalents of Na (22.99 grams per mole [g/mole]) relative to chloride (35.45 g/mole). To account for Na that was incorporated into groundwater through evaporative concentration of salts dissolved in precipitation or dissolution of

halite within the basin, the original Na concentrations were then adjusted by subtracting the Na molar equivalent of the dissolved Cl in the groundwater sample (Figure 8-6). Although the potential contributions from halite dissolution to the dissolved Na concentrations are relatively small, these contributions were removed so that the adjusted Na concentrations reflect only the effects of glass and silicate weathering reactions and cation exchange processes, and not variable evaporative process or different amounts of halite dissolution. The adjusted Na concentrations as well as unadjusted Ca concentrations were then plotted as a function of the corrected DI^{14}C ages (Figure 8-7). The relatively strong correlations that exist between the corrected DI^{14}C ages and the Na ($R^2 = 0.81$) and Ca ($R^2 = 0.75$) concentrations suggest that these correlations can be used in a semi-quantitative way to date groundwaters where ^{14}C data are lacking or whose age is ambiguous based on ^{14}C dating techniques.

The relationships shown in Figure 8-7 were inverted in Figure 8-8 to show groundwater age as a function of cation concentrations along with the regression equations relating age (y) to cation concentration (x). Although data from Well ER-5-4 #2 were not used in developing the regression, the regression curves in Figure 8-8 are extrapolated to the adjusted Na and Ca concentrations at Well ER-5-4 #2 (285 and 0.6 mg/L, respectively). Using the regression equations shown in Figure 8-8, the age of groundwater at Well ER-5-4 #2 is calculated as 34,000 years based on its adjusted Na concentration (285 mg/L) and 33,200 years based on its Ca concentration (0.6 mg/L). This somewhat remarkable convergence of age estimates suggests that the age of groundwater at Well ER-5-4 #2 is ~ 33,600 years.

The relations between groundwater age and cation concentrations shown in Figure 8-8 were also used to estimate groundwater ages at Wells UE-11a and WW-1. At Well UE-11a, the Ca and adjusted Na concentrations yielded groundwater ages of 15,400 and 19,400 years, respectively, for an average age of ~17,400 years. At WW-1, the groundwater age based on the adjusted Na concentration is 16,100 years and the age based on Ca concentration is 18,700 years, for an average age of ~ 17,400 years.

The groundwater $^{36}\text{Cl}/\text{Cl}$ ratios versus corrected DI^{14}C ages previously shown in Figure 8-5 were replotted using the estimates for $(^{36}\text{Cl}/\text{Cl})_0$ at Wells ER-5-4 and ER-5-4 #2 calculated in the previous section and the estimated groundwater age of 33,600 years determined for Well ER-5-4 #2 from

Figure 8-7
Corrected Groundwater $D14C$ Ages Versus Cation Concentrations

Figure 8-8
Cation Concentrations Versus Corrected Groundwater $D14C$ Ages

cation concentrations (Figure 8-9). The adjustments to the $^{36}\text{Cl}/\text{Cl}$ ratios and the estimated groundwater age of 33,600 years result in $^{36}\text{Cl}/\text{Cl}$ ratio-to-age relationships at Wells ER-5-4 and Well ER-5-4 #2 that are broadly consistent with the $^{36}\text{Cl}/\text{Cl}$ ratios recorded in the pack-rat midden data between 29,000 and 33,000 years (Figure 8-9).

Figure 8-9
Groundwater $^{36}\text{Cl}/\text{Cl}$ Ratios, DO^{14}C and DI^{14}C Ages, Theoretical Reconstructions of ^{36}Cl Production, and $^{36}\text{Cl}/\text{Cl}$ Deposition Preserved in Pack-Rat Middens

*The groundwater $^{36}\text{Cl}/\text{Cl}$ ratios at Wells ER-5-4 and ER-5-4 #2 were adjusted to compensate for dissolution of NaCl and the age of groundwater at Well ER-5-4 #2 was estimated from groundwater cation concentrations.

8.6 Evaluation of Groundwater Ages Using Deuterium and Oxygen-18

The heavy isotopes of hydrogen (^2H or D) and oxygen (^{18}O) become part of the water molecule as HDO and H_2^{18}O . The abundances of these isotopes relative to the lighter isotopes (^1H or ^{16}O) in groundwater vary within an aquifer because of differences in the environmental conditions that existed in the recharge area at the time of recharge. The relative abundances of the heavy isotopes to the lighter isotopes are typically expressed in delta (δ) notation as:

$$\delta \text{ isotope} = ((R_{\text{sample}}/R_{\text{standard}})-1) \cdot 1000 \quad (8-8)$$

where *isotope* is either D or ^{18}O , *R* is the ratio of the heavy isotope to the lighter isotope ($^{18}\text{O}/^{16}\text{O}$ or $^2\text{H}/^1\text{H}$), and the subscripts *sample* and *standard* indicate the ratios in the groundwater sample and the standard (Vienna Standard Mean Ocean Water or VSMOW). Delta deuterium (δD) and delta oxygen-18 ($\delta^{18}\text{O}$) have units of parts per thousand or per mil (‰) (Figure 8-10).

Figure 8-10
Delta Deuterium (δD) Versus Delta Oxygen-18 ($\delta^{18}\text{O}$) of Groundwater
From the Tuffs and Alluvium in Frenchman Flat

In general, δD and $\delta^{18}\text{O}$ characteristics of groundwater in an area can vary both as a function of space and of time. This is because the δD and $\delta^{18}\text{O}$ characteristics of precipitation that produces the groundwater recharge depend on the temperature and isotopic characteristics of the moisture source area, the distance and topographic variations along the storm track path, and the condensation temperature (which is a function of elevation, season, and long-term climate variability). These factors, as well as other factors influencing the δD and $\delta^{18}\text{O}$ characteristics of precipitation, change with both location and with time (e.g., Benson and Klieforth, 1989; Friedman et al., 2002a and b; Smith et al., 2002). However, in some situations, either spatial or temporal factors are likely to dominate, and in these instances useful interpretations of groundwater δD and $\delta^{18}\text{O}$ characteristics are

possible. For instance, when groundwaters are of roughly comparable age, and the study area is large and includes regions with different elevation and topography, the differences in the δD and $\delta^{18}O$ characteristics of the groundwaters are likely to reflect differences in contemporaneous environmental conditions at the recharge locations. In this case, the δD and $\delta^{18}O$ characteristics of the groundwaters can be used to trace flow paths and identify mixing relationships (e.g., Rose et al., 2002). Conversely, when the study area is relatively small and the groundwaters were recharged over long time periods, the effect of long-term temporal variations in the isotopic composition of recharge probably controls the variability in the groundwater δD and $\delta^{18}O$ characteristics. In this latter case, the groundwater δD and $\delta^{18}O$ provide an archive of past climatic conditions in the study area. Obviously, many groundwater systems can include aspects of both of these conceptual end-members, particularly in the arid Southwest where, the groundwater system includes mountains and interlying basins, and where groundwater residence times can be large because of low recharge rates.

In Frenchman Flat, most of the groundwater in the alluvium and tuffs was probably recharged locally within a relatively small area (30 by 19 km). Because topography within this area is relatively subdued and because the estimated groundwater ages span almost 25,000 years (not including modern water from Cane Spring), it is likely that much of the variability in the Frenchman Flat groundwater δD and $\delta^{18}O$ data (Figure 8-10) is due to climatic fluctuations in the late Pleistocene. As mentioned earlier, these climate fluctuations are recognized at the NTS from (^{14}C) datable fossilized plant remnants preserved in pack-rat middens. These plant remnants have enabled paleo-environmental reconstructions based on the moisture and temperature requirements of their modern analogs (e.g., Spaulding and Graumlich, 1986; Forester et al., 1999).

To help evaluate the possible temporal influences on the groundwater δD and $\delta^{18}O$ data from the alluvium and tuff in Frenchman Flat, these data were plotted in against the corresponding corrected $DI^{14}C$ ages (and in the case of Wells UE-11a and ER-5-4 #2, against the average age estimated from the Na and Ca concentrations) (Figures 8-11 and 8-12). Many of the data from Frenchman Flat have $\delta^{18}O$ values of between -14.0 to -13.5 ‰ and δD values of between -110 to -105 ‰, whereas groundwaters from Well ER-5-4 #2 and UE-11a have slightly higher and lower $\delta^{18}O$ and δD values, respectively. The groundwater data from Wells WW-4 and WW-4a in the CP basin have higher $\delta^{18}O$ and δD values than groundwater from Frenchman Flat proper. The isotopic differences in the groundwaters from CP basin and Frenchman Flat were interpreted by Hershey et al. (2005) as

Figure 8-11
Groundwater $\delta^{18}\text{O}$ Values as a Function of Corrected DI^{14}C Age

Figure 8-12
Groundwater δD Values as a Function of Corrected DI^{14}C Age

evidence that there was little communication between the groundwaters in these basins. The much higher $\delta^{18}\text{O}$ and δD values of the perched water at Cane Spring were interpreted by Hershey et al. (2005) to reflect the shift to modern climatic conditions sometime in the early Holocene.

Sorting out the relative importance of temporal and spatial controls in these data is difficult. The perched water at Cane Spring appears to be slightly more evaporated than the other groundwaters shown in [Figure 8-10](#), possibly because of evaporation in the collection pool from which it was sampled (Ingraham et al., 1991). If the $\delta^{18}\text{O}$ and δD values at Cane Spring before evaporation are estimated by projecting the measured values back to the global meteoric water line (GMWL) along a theoretical evaporation line with a slope of 4 (Clark and Fritz, 1997; Davisson et al., 1999), the estimated $\delta^{18}\text{O}$ and δD values of -13.2 and -96 ‰ are similar to the values measured elsewhere in the CP basin at Wells WW-4 and WW-4a ([Table 8-2](#)). This implies that there has been no significant shift in the isotopic values of recharge in the CP basin during the past 13,000 years and that, for reasons that are not yet clear, recharge in CP basin is isotopically enriched relative to the bulk of the Frenchman Flat groundwater. Only the groundwaters from Well UE-5 PW-3, which is physically closest to Wells WW-4 and WW-4a in the CP basin, and Well ER-5-4 #2 display any isotopic similarity to the groundwaters from the CP basin. The isotopic similarity of groundwater at Well UE-5 PW-3 to groundwater at Wells WW-4 and WW-4a may result from these groundwaters having a common recharge area in the hills that separate the CP basin and northwest Frenchman Flat. The similarity of groundwater $\delta^{18}\text{O}$ and δD values at Well ER-5-4 #2 to groundwater in the CP basin is investigated in [Section 8.7](#), which describes the mixing models for this well developed using PHREEQC.

Another interesting feature of [Figures 8-10](#) through [8-12](#) is associated with the groundwater $\delta^{18}\text{O}$ and δD data from Well UE-11a. These $\delta^{18}\text{O}$ and δD values are the isotopically lightest values in the Frenchman Flat basin. The occurrence of these light $\delta^{18}\text{O}$ and δD values at approximately 17,000 years ago is consistent with the interpretation from pack-rat midden data that the glacial maximum which occurred between 16,000 and 21,000 years ago brought relatively cold, dry arctic air to the region at this time (Forester et al., 1999). Arctic air would have significantly lighter $\delta^{18}\text{O}$ and δD values than moisture arriving along other storm tracks, based on studies of the isotopic composition of modern precipitation in the Great Basin (Benson and Kleiforth, 1989; Friedman et al., 2002a). Thus, the groundwater age of 17,200 years estimated for Well UE-11a from the cation

concentration/age relationship (Figures 8-7 and 8-8) appears to be a reasonable estimate for the age of this groundwater.

8.7 Estimation of Groundwater Flow Paths and Travel Times with PHREEQC

This section describes geochemical models created with PHREEQC (Parkhurst and Appelo, 1999) that test the hypothesized groundwater relationships developed based on the hydrogeologic setting and the relative ages and evolutionary state of the Frenchman Flat groundwaters. These models investigate whether the selected groundwaters are truly evolutionary by attempting to determine whether a set of water/rock reactions can be identified that explain changes in the chemistry of the groundwater as it moves through the aquifer. For some geochemical models, groundwater mixing as well as water/rock interaction is investigated as a way to explain the evolution of the groundwater. The modeling presented here follows a similar strategy to that previously described by Hershey et al. (2005) in their investigation of other aspects of the Frenchman Flat groundwater system. In particular, it is assumed from the preceding analysis that the $\delta^{18}\text{O}$ and δD of groundwater in the CP basin has been relative invariant over time and can be used as a conservative tracer to identify how much of the groundwater from the CP basin could be present in the Frenchman Flat basin. However, one important difference between Hershey et al. (2005) and the present study is that, to obtain reaction models for certain wells, this study allows for the possible addition of Cl into groundwater through halite dissolution. Evidence that this process has affected the groundwater Cl and ^{36}Cl data at some wells in the alluvium and tuff in Frenchman Flat is based on data in Hershey et al. (2005, Figure 20) which show that the low $^{36}\text{Cl}/\text{Cl}$ at Wells ER-5-4 and ER-5-4 #2 is correlated with increases in the Cl concentrations at these wells relative to other Frenchman Flat groundwaters.

The mineralogy of the alluvium in Frenchman Flat was described by Warren et al. (2002). Minerals are partitioned among lithic fragments derived from the surrounding upland areas, authigenic and detrital crystals and pyroclasts. Lithic fragments of welded tuff or lava indicate that the Timber Mountain Group, Tiva Canyon and Topopah Springs Tuffs, and the Wahmonie Formation all contributed detritus to the basin. Lithic fragments also include ubiquitous glass throughout the depth of the basin, indicating only mild post-depositional alteration. Zeolites (mostly clinoptilolite) are primarily detrital but with lesser amounts of authigenic clinoptilolite occurring as small euhedral crystals throughout the alluvial sequence. Plagioclase, K-spar, and quartz form the majority of the

detrital crystals, with mafic minerals and magnetite present in minor amounts (Warren et al., 2002, Table 2). Based on textural evidence and mineral associations, clays (primarily smectite, kaolinite, illite, and mica) are both detrital and authigenic and coat many of the other minerals in the alluvium. Calcite is present in minor amounts (< 5 percent) throughout the alluvium, except in the deepest layers encountered in well ER-5-4, where it is abundant and accompanied by dolomite. Other authigenic phases include iron-oxides, silica polymorphs and possibly gypsum.

The mineral compositions and textural relations of the Frenchman Flat alluvium described in Warren et al. (2002) provided the basis for the mineral assemblages and phase dissolution/precipitation constraints used in the PHREEQC models (Table 8-3). The mineral compositions listed for the Timber Mountain (TM) mineral phases (TMglass, TMfeldspar, TMclay and TMzeolite) measured on samples from Timber Mountain tuff at Pahute Mesa were assumed to represent the mineral compositions of glass, feldspar, smectite, and clinoptilolite in Frenchman Flat. The other mineral phases use the mineral compositions provided in the PHREEQC database.

The following subsections present the results of the modeling done to investigate the evolution and mixing of groundwater in the Frenchman Flat basin.

8.7.1 Groundwater Flow from Well UE-5 PW-2 to Well UE-5 PW-1

The first set of models was developed to investigate whether groundwater from Well UE-5 PW-2 could flow southward and evolve into the groundwater at Well UE-5 PW-1. Ten sets of possible reactions were found that account for the evolution of groundwater along this flow path (Figure 8-13). Various combinations of feldspar or glass dissolution reactions along with clay or clinoptilolite precipitation, cation exchange, and a small amount of calcite precipitation can explain the evolution of groundwater as it flows from Well UE-5 PW-2 to Well UE-5 PW-1. These results indicate that groundwater flow from Well UE-5 PW-2 to Well UE-5 PW-1 is geochemically permissible and that these groundwaters could be considered to lie along a common flow path.

8.7.2 Groundwater Flow from Wells UE-5c WW and UE-5 PW-1 to Well ER-5-4

The possibility of groundwater flow from the northwest and north to the center of the basin was investigated by creating geochemical models that investigate the possible origin of groundwater at

Well ER-5-4 from Wells UE-5c WW and UE-5 PW-1. All of these wells are completed in the alluvium.

Table 8-3
Mineral Compositions and Constraints Used for PHREEQC Models

Mineral	Formula	Constraint	Isotope
Calcite ¹	CaCO ₃	precipitate	δ ¹³ C
Dolomite ²	CaMg(CO ₃) ₂	dissolve	δ ¹³ C
Halite ³	NaCl	dissolve	³⁶ Cl/Cl
TM-Feldspar ⁴	K _{0.565} Na _{0.428} Ca _{0.021} Fe _{0.006} Al _{1.007} Si _{2.980} O _{7.992}	dissolve	----
TM-Glass ⁴	K _{0.368} Na _{0.383} Ca _{0.024} Mg _{0.005} Fe _{0.026} Al _{0.789} Si _{4.173} O _{9.973}	dissolve	----
K-feldspar	KAlSi ₃ O ₈	dissolve	----
Ca-exchange	CaX ₂	sorption	----
Mg-exchange	MgX ₂	sorption	----
K-exchange	KX	sorption	----
Na-exchange	NaX	desorption	----
TM-Clay ⁴	K _{0.017} Na _{0.161} Ca _{0.141} Mg _{0.138} Fe _{0.050} Al _{2.438} Si _{3.462} O _{11.024}	precipitate	----
TM-Clinoptilolite ⁴	K _{0.295} Na _{0.217} Ca _{0.083} Al _{0.735} Si _{4.278} O _{9.998}	precipitate	----
Flourite	CaF ₂	none	----
Gypsum	CaSO ₄ ·2H ₂ O	dissolve	----
Alunite ⁵	KAl ₃ (SO ₄) ₂ (OH) ₆	none	----
Illite ⁵	K _{0.6} Mg _{0.25} Al _{2.3} Si _{3.5} O ₁₀ (OH) ₂	none	----
Pyrite ⁶	FeS ₂	dissolution	----
Calcite ¹	CaCO ₃	precipitate	δ ¹³ C
Dolomite ²	CaMg(CO ₃) ₂	dissolve	δ ¹³ C
Halite ³	NaCl	dissolve	³⁶ Cl/Cl

¹Calcite precipitated in inverse models for UE-5 PW-1, ER-5-4 and ER-5-4 #2. In these models, calcite was allowed to precipitate with δ¹³C values of -4 ± 4 ‰, approximately the δ¹³C of groundwater at these wells.

²Dolomite dissolved in inverse models for ER-5-4 and ER-5-4 #2. In these models, dolomite was assigned a δ¹³C value of -4 ± 4 ‰.

³The ³⁶Cl/Cl ratio in halite was assumed to be zero.

⁴Mineral phase composition representative of the Timber Mountain Tuff near Pahute Mesa.

⁵Alunite and illite were included only in the models for ER-5-4 and ER-5-4 #2.

⁶Pyrite was included as a potential mineral phase only in the models for UE-5 PW-1.

---- = Not applicable

The results of the PHREEQC models indicate that groundwater at Well ER-5-4 could originate either from a roughly equal mixture of groundwater near Well UE-5c WW to the northwest and groundwater near Well UE-5 PW-1 to the north (Figure 8-14), or from UE-5 PW-1 groundwater alone. Reactions that explain the evolution of groundwater from these wells to Well ER-5-4 are similar to those described for the Well UE-5 PW-2 to UE-5 PW-1 models except that dolomite is

Figure 8-13
Geochemical Reactions Accounting for the Evolution of
Groundwater from UE-5 PW-2 to UE-5 PW-1

Note that positive values indicate the mineral phase or element is entering into solution by dissolution or exchange, whereas negative values indicate the phase is leaving the solution by precipitation or exchange.

dissolved as calcite is precipitated, and alunite dissolution (with illite precipitation) is required to explain the large increase in SO_4^{2-} between the potential upgradient wells and Well ER-5-4. Gypsum, although included as a possible reactive phase, was not a possible source of SO_4^{2-} because the model could not balance the Ca^{2+} that would also enter solution. Alunite was not specifically listed as a mineral phase in Warren et al. (2002). However, approximately 12 percent of the lithic fragments at Well ER-5-4 had been hydrothermally altered before deposition, pointing to a source area in the Wahmonie Hills area about 17 km to the west of E-5-4 (Warren et al., 2002, p. 16). Although the mineralogy of these altered lithic fragments was not determined, alunite is probably present as an alteration phase in these lithic fragments. The models were successfully able to explain the decrease in the $^{36}\text{Cl}/\text{Cl}$ ratio of groundwater from either Well UE-5c WW or UE-5 PW-1 as it flowed to Well ER-5-4 as a result of halite dissolution. The models shown in Figures 8-14 and 8-15 thus support the concept outlined in Section 9.1 that groundwater flows from the perimeter of the basin toward the basin center.

Figure 8-14
Mixing Fractions of Groundwater from Wells UE-5c WW or UE-5 PW-1 in ER-5-4

Figure 8-15
Geochemical Reactions for ER-5-4 Inverse Models

Note that positive values indicate the mineral phase or element is entering into solution by dissolution or exchange, whereas negative values indicate the phase is leaving the solution by precipitation or exchange.

8.7.3 Groundwater Flow to Well ER-5-4#2

The PHREEQC models developed to explain the composition of groundwater in the LTCU at Well ER-5-4 #2 consider the possible mixing of groundwater from the CP basin at Wells WW-4 and WW-4a, and groundwater from UE-5c WW. The inclusion of wells from the CP basin in these models was motivated by the higher $\delta^{18}\text{O}$ and δD values at these wells and indications from the scatterplot in [Figure 8-10](#) that groundwater at Well ER-5-4 #2 could be a mixture of groundwater from either well WW-4 or WW-4a and Well UE-5c WW. As discussed in [Section 3.5](#), groundwater at ER-5-4 #2 has a hydraulic head in excess of 755 m. This also points to the CP basin area as a probable source of the groundwater at Well ER-5-4 #2.

The results of the PHREEQC models for this set of wells indicate that groundwater Well UE-5c WW could combine with lesser amounts of groundwater from the CP basin at Well WW-4 to produce the groundwater at Well ER-5-4 #2 ([Figure 8-16](#)). The reactions for these inverse models are shown in [Figure 8-17](#). The reaction amounts for this set of models is much higher than was calculated for the previous PHREEQC models shown in this section because the concentrations of some constituents such as Na are substantially higher at Well ER-5-4 #2 than in the other wells considered. Like the models described for Well ER-5-4, the models for Well ER-5-4 #2 require alunite dissolution and illite precipitate to explain the high SO_4^{2-} concentrations at the well. The models successfully match the low $^{36}\text{Cl}/\text{Cl}$ ratio at Well ER-5-4 #2 by dissolving halite that is assumed to be largely free of ^{36}Cl . The very heavy $\delta^{13}\text{C}$ of the ER-5-4 #2 groundwater was obtained by allowing the simultaneous dissolution of isotopically heavy dolomite and the precipitation of calcite, thereby mimicking the process of isotope exchange that may have resulted in the heavy $\delta^{13}\text{C}$ of the groundwater at the well.

The hydraulic head of 735 m at Well UE-5c WW is too low for groundwater to flow directly from this well to Well ER-5-4 #2. However, if the chemical and isotopic composition at this well is assumed to represent the composition of groundwater closer to the CP basin where higher heads exist, then both the geochemical and hydraulic constraints regarding the source of ER-5-4 #2 groundwater are satisfied. This assumption is plausible given the location of UE-5c WW in the northwest corner of the Frenchman Flat Basin.

In summary, inverse geochemical models for groundwater from Wells UE-5 PW-1 and ER-5-4 can be found with PHREEQC that support the concept that groundwater moves from areas on the northern

Figure 8-16
Mixing Model Results for the ER-5-4 #2 Inverse Models

Figure 8-17
Reactions for the ER-5-4 #2 Inverse Models

Note that positive values indicate the mineral phase or element is entering into solution by dissolution or exchange, whereas negative values indicate the phase is leaving the solution by precipitation or exchange.

and northwestern margins of the Frenchman Flat Basin toward the basin center. The inverse model results for Well ER-5-4 #2 indicate that the groundwater from this well is partly derived by groundwater flow from the vicinity of the CP basin, in agreement with the interpretation from hydraulic data that areas with high hydraulic heads to the west of Frenchman Flat must be hydrologically connected to Well ER-5-4 #2 in order to maintain the high heads (755 m) measured in the LTCU at this well.

8.8 Groundwater Velocities

Based on the analyses presented in the preceding sections, the corrected DI^{14}C ages together with the estimate of groundwater age at Well ER-5-4 #2 calculated from the Na and Ca concentrations seem to provide the best estimate of groundwater age in the Frenchman Flat area. These ages are shown in map view in [Figure 8-18](#) along with an indication of the type of HSU from which the samples were taken (AA, VA, or TCU). As discussed in [Section 8.1](#), it is likely that groundwater in the tuffs and alluvium flows south or southeastward from recharge areas in the hills along the northern and northwestern perimeter of the basin toward the basin center. Using this general constraint on groundwater flow paths, groundwater velocities were calculated between pairs of wells that were selected based on their common HSU and on their relative corrected DI^{14}C ages and chemical evolution ([Figures 8-19](#) and [8-20](#)). Although the relatively small number of wells with DI^{14}C data in any HSU and the predominantly north-south well coverage in Frenchman Flat severely limit the possible combinations of wells that could be considered to lie along a flow path, several pairs of closely spaced wells were identified that give an indication of flow velocities within the basin.

The first pair of wells to be considered is Wells UE-5 PW-2 and UE-5 PW-1 in northern Frenchman Flat ([Figure 8-19](#)). These wells were selected because (1) they are both in the AA, (2) they are separated by only 1,430 m along a north-south line in an area where groundwater flow is probably southward, and (3) their relative ages and chemical evolution suggest groundwater flow from Wells UE-5 PW-2 to UE-5 PW-1 is possible ([Figure 8-7](#) and [Section 8.7.1](#)). Based on the difference in the (average) corrected DI^{14}C ages of these wells (11,740 years – 8,440 years = 3,300 years) and their distance from each other, the groundwater velocity in the alluvium between these wells is 0.43 meters per year (m/yr) ([Table 8-4](#)). Thus, over 1,000 years, groundwater in the alluvium near the northern testing area would travel about 430 m. The groundwater flux (q) between Wells UE-5 PW-2 and

Figure 8-18
Estimated Groundwater Ages Calculated for Alluvial and Tuffaceous Aquifers in Frenchman Flat

Figure 8-19
Groundwater Velocities Calculated for Different Well Pairs in the Alluvium in Frenchman Flat

Figure 8-20
Groundwater Velocities Calculated Between the CP Basin and Well ER-5-4 #2

UE-5 PW-1 can be calculated from the groundwater velocity (v) and the average porosity ($\phi = 0.36$) using the relationship ($q = v\phi$) to obtain $q = 0.16$ m/yr.

The second pair of wells to be considered is WW-5b and WW-5c in southern Frenchman Flat (Figure 8-19). These wells were selected for analysis because (1) they are both in the AA, (2) they are separated by only 1,458 m along a southeasterly trajectory in an area where groundwater flow is likely to be southeastward because of an increasing component of flow from the Wahmonie Hills or CP basin, and (3) their relative ages and chemical evolution suggest that groundwater flow from WW-5b to WW-5c is possible (Figure 8-7). Based on the difference in the corrected $DI^{14}C$ ages of groundwater at WW-5c and WW-5b (23,147 years – 15,677 years = 7,470 years) and their distance between the wells, the average groundwater velocity is 0.20 m/yr (Table 8-4). Thus, groundwater in the alluvium near the central testing area would travel approximately 210 m in the next 1,000 years. By a similar calculation as outlined in the previous paragraph, the groundwater flux in the alluvium is estimated to be 0.072 m/yr. The PHREEQC models described in Section 8.7.2 indicated that groundwater at Well ER-5-4 could evolve either by the evolution of groundwater flowing south from Well PW-1, or by the evolution of groundwater flowing southeast from UE-5c WW. The distances and age differences between these combinations of wells lead to estimates of groundwater velocity between Well PW-1 and ER-5-4 of 0.19 to 0.25 m/yr and a groundwater velocity between Wells UE-5c WW and ER-5-4 of 0.12 to 0.85 m/yr.

Groundwater velocities were calculated between Wells UE-5 PW-1 and WW-1. These wells were selected because of the southeastward trajectory of particles leaving the central testing area in many of the flow models described in Section 4.0 and this combination of wells best approximated that trajectory. An average age of 17,200 years was used for the groundwater at WW-1 based on the ages estimated from the Ca and Na concentrations in Section 8.5.3. The groundwater velocity of 1.06 m/yr estimated for this combination of wells (Figure 8-19 and Table 8-4) is higher than the velocities estimated for the other well combinations. This velocity estimate is subject to greater uncertainty than velocities estimated for other flow paths because the age of groundwater at WW-1 was estimated indirectly.

The PHREEQC models presented in Section 8.7.3 interpreted the composition of groundwater at Well ER-5-4 #2 to result through the evolution of a groundwater mixture that included groundwater

from Wells WW-4 and UE-5c WW. Using the mixing fractions estimated in the inverse models for Well ER-5-4 #2 (Figure 8-17) and the DIC and ^{14}C activities at each well in the mixture, a ^{14}C activity for the mixture was calculated (11.1 pmc). Using the decay equation (8-5) with these values (adjusted using a q_{DIC} factor to account for dolomite dissolved in the inverse models) yielded travel times of 8,340 to 8,380 years. When combined with average upgradient location of the mixture calculated from the coordinates of the mixing end-members and their fractions of the mixture, these travel time estimates yielded a groundwater velocity of 0.60 m/yr. The groundwater velocity estimated from this analysis is shown in Figure 8-20.

Table 8-4
Estimated Groundwater Travel Times and Velocities

Well #1	Well #2	Distance (m)	Travel time (years)	Velocity (m/yr)
UE-5 PW-2	UE-5 PW-1	1,430	3,304	0.43
WW-5b	WW-5c	1,458	7,470	0.20
UE-5c WW	ER-5-4	1,909	2,321 to 15,712	0.12 to 0.85
UE-5 PW-1	ER-5-4	3,250	13,109 to 17,207	0.19 to 0.25
UE-5 PW-1	WW-1	5,972	5,631	1.1
WW-4 and UE-5c WW	ER-5-4 #2	5,010 ^a	8,340 to 8,380	0.60

^aThe distance between ER-5-4 #2 and the upgradient wells in the mixture was estimated using mixing-fraction-weighted coordinates of the upgradient wells.

m = Meter

m/yr = Meters per year

An interesting result associated with this analysis is that when the travel times of 8,340 to 8,380 years to Well ER-5-4 #2 are added to the age calculated for the upgradient mixture using the average DI^{14}C ages listed in Table 8-1, an average age of 26,000 years is obtained for the ER-5-4 #2 groundwater. This age is similar to the age of 33,000 years calculated from the cation concentrations in the groundwater at Well ER-5-4 #2, and supports the concept that groundwater at ER-5-4 #2 is quite old.

8.9 Summary and Conclusions

Groundwater ^{14}C data from the tuffs and alluvium in Frenchman Flat were used to calculate ages (residence times) for these groundwaters. The analysis of ^{14}C associated with the DIC (DI^{14}C) considered the effects of calcite dissolution and isotope exchange on the groundwater DI^{14}C through two simple correction methods that estimated the dilution of ^{14}C originally in the groundwater recharge. The two correction methods yielded estimates of groundwater ages that were in good

agreement for all but one of the wells (ER-5-4 #2). The corrected DI^{14}C ages of Frenchman Flat groundwater ranged from ~ 8,500 years to ~ 29,000 years. In general, younger groundwater is found near the low hills bordering the northern and northwestern parts of the basin, and older groundwater is found toward the basin center, reflecting the near absence of recharge through the alluvium in the basin even during the relatively wet conditions that existed in the late Pleistocene and early Holocene. The absence of groundwater DI^{14}C ages younger than the early Holocene, even along the basin margins, is consistent with paleo-climate reconstructions based on vegetation preserved in pack-rat middens and on the ages of paleo-discharge deposits that indicate modern-day arid conditions were established in the NTS area by about 9,000 years ago.

The corrected groundwater DI^{14}C ages were compared with groundwater ages calculated from ^{14}C associated with the dissolved organic carbon (DO^{14}C), which theoretically do not require adjustments to account for water/rock interactions. The ages of Frenchman Flat groundwater based on DO^{14}C were generally less than half of the corrected ages based on DI^{14}C . Both sets of groundwater ages were evaluated by comparing temporal variations in atmospheric $^{36}\text{Cl}/\text{Cl}$ deposition, as recorded in the groundwater $^{36}\text{Cl}/\text{Cl}$ and the estimated DI^{14}C - and DO^{14}C -based groundwater ages, with terrestrial records of $^{36}\text{Cl}/\text{Cl}$ deposition preserved in pack-rat middens that extend back almost 40,000 years. The temporal variations in groundwater $^{36}\text{Cl}/\text{Cl}$ ratios using the DI^{14}C -based ages were in good agreement with variations in atmospheric $^{36}\text{Cl}/\text{Cl}$ deposition recorded in the pack-rat midden data, whereas similar comparisons showed that the DO^{14}C ages were too young for at least half of the wells for which DO^{14}C data were available. Questions concerning the reliability of the DO^{14}C ages focused the remainder of the analysis on the corrected DI^{14}C ages.

Past studies of the geochemical evolution of groundwater at the NTS have established that groundwater in contact with tuffs and tuffaceous sediments tends to become enriched in Na and depleted in Ca and other divalent cations because the tuffs themselves are high in Na and because of cation exchange. These evolutionary trends, as represented in correlations developed between Na and Ca concentrations and corrected DI^{14}C ages, were used to estimate a groundwater age at ER-5-4 #2 of 33,000 years and to establish a basis for identifying pairs of wells that were likely to lie along a flow path.

Inverse geochemical models were done with the geochemical modeling code PHREEQC to investigate the origin of groundwater at selected wells within the basin. These models confirmed that groundwater at Well UE-5 PW-1 could originate by the southerly flow of groundwater from Well UE-5 PW-2, coupled with plausible water/rock interactions. Similar models done for Well ER-5-4 in the central part of the basin indicate this groundwater could originate from either the southerly flow of groundwater from Well UE-5 PW-1 or from a mixture of UE-5 PW-1 groundwater and groundwater flowing southeast from UE-5c WW. Geochemical inverse models for Well ER-5-4 #2 could only explain the composition of this groundwater using both mixing and water/rock interactions. This groundwater appears to originate from a mixture of groundwater from the CP basin and groundwater from northwestern Frenchman Flat, suggesting that this groundwater may have been recharged in the low hills separating these two basins. This result agrees with evidence from hydraulic heads that the groundwater near Well ER-5-4 #2 has a strong hydraulic connection with groundwater in the vicinity of the CP basin.

Groundwater velocities were calculated at pairs of wells in the alluvium that were likely to lie along a flow path based on their relative chemical evolution. Groundwater velocities in the alluvium between well pairs with ¹⁴C-based ages ranged between 0.12 m/yr to 0.85 m/yr. A higher groundwater velocity of 1.1 m/yr was estimated for a UE-5 PW-1 to WW-1 flow path, but this velocity is subject to greater uncertainty because it is based on an age for WW-1 groundwater estimated indirectly from its dissolved cation concentrations. An analysis of groundwater travel time for a mixture of groundwaters involving components from the CP basin (Well WW-4) and from Well UE-5c WW indicated groundwater velocities in the volcanic rocks along the flow path was about 0.60 m/yr.

The low rates of groundwater movement estimated for Frenchman Flat basin are consistent with the near absence of recharge to the basin over the last 8,500 years and with the nearly flat water table. The estimated groundwater velocities in the alluvium indicate that transport distance of between about 200 to 1,000 m can be expected over the next 1,000 years.

9.0 SUMMARY AND CONCLUSIONS

To understand the potential for lateral and vertical radionuclide migration, a 3-D, finite element, steady-state groundwater flow model of the Frenchman Flat CAU was constructed. The model was created to allow for evaluation of conceptual model uncertainty. Different combinations of hydrostratigraphic framework models, recharge models, hydrologic boundary conditions, and the application of permeability depth decay were considered in order to propagate the uncertainty associated with each of these elements of the model into the resulting flow fields. The approach resulted in several flow fields that were consistent with site-specific data and the conceptual understanding of the Frenchman Flat groundwater flow system. The modeling effort was able to synthesize an understanding of the regional hydrogeologic system and local data and observations while bounding flow field uncertainty resulting from geologic and hydrologic uncertainty. This study was undertaken to satisfy the groundwater flow model required by the *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada* (NNSA/NV, 2001).

The Frenchman Flat CAU flow model is calibrated to estimates of boundary flow from two regional models. This information is utilized to give the direction and velocity of groundwater flow, which will be used to compute contaminant transport in conjunction with the appropriate processes (e.g., advection, dispersion, retardation, and radioactive decay). However, the modeling of solute transport has profoundly different characteristics than groundwater flow alone (Anderson, 1979). Thus, there may be additional uncertainty associated with the flow model when it is used to make predictions of radionuclide transport.

The emphasis of the flow modeling studies is not on identification of a unique set of calibration parameters. Instead the groundwater flow framework and model uncertainties are assessed through the identification of a spectrum of particle trajectories from individual nuclear tests that will be further examined through future transport and total system modeling assessments.

The FFACO requires that the contaminant transport model predict the contaminant boundary at 1,000 years and “at a 95% level of confidence” (FFACO, 1996). The Frenchman Flat Phase II flow model described in this report provides, through the flow fields derived from alternative HFMs and boundary conditions, one of the tools required to compute the contaminant boundary. Other components include the simplified source model, which incorporates uncertainty and variability in the factors that control radionuclide release from an underground nuclear test, and the transport model with the contaminant parameter uncertainty. The synthesis of all of this information contributes to the calculation of the final contaminant boundary.

Frenchman Flat is a closed-drainage intermontane basin located in the southeastern portion of the NTS. It is bounded on the north by Massachusetts Mountain and the Halfpint Range, on the east by the Ranger Mountains and Buried Hills, on the south by the Spotted Range, and on the west by the Wahmonie Hills. The valley floor of the basin slopes gently from the surrounding highlands to a low-lying playa. Ground elevations range from over 1,463 m amsl in the surrounding mountains to approximately 938 m amsl at Frenchman Lake playa (BN, 2005a).

Sedimentary and volcanoclastic rocks, followed by ash-fall and ash-flow tuffs and finally alluvial and playa deposits, filled Frenchman Flat basin as it developed, along with lavas emanating from the Wahmonie volcanic center. Stratigraphic relationships between alluvium and tuffs within the basin indicate that formation of the main part of the basin was initiated after eruption of the Ammonia Tanks Tuff (11.45 Ma) and before the eruption of the Thirsty Canyon group had been completed at 9.14 Ma (BN, 2005b, p. 3-4). Basin development continued after deposition of the tuffs, as demonstrated by the faulted nature of the tuffs and the accumulation of more than 1,400 m of alluvium in the center of the basin. The alluvium thins toward and beyond the structural margins of the basin where it directly overlies the LCA (BN, 2005a). Along the northern, eastern, and southern margins, the tuff confining units that line the basin have been thinned by faulting and erosion, increasing the potential for hydraulic connections between the shallower material in the basin and the LCA in these areas.

The geology northwest of Frenchman Flat is structurally complex and diverse. This area includes: the CP basin, whose geology at depth is relatively uncertain; the strike-slip Cane Spring fault, which separates CP basin from Frenchman Flat basin; the Wahmonie volcanic center; and the CP thrust fault

(BN, 2005a). Numerous faults that underlie CP Hogback separate the CP basin from Yucca Flat. A zone of faults near Massachusetts Mountain accommodates changes in the structural styles south of Yucca Flat and further complicates the interpretation of the geologic structure in this area. Thus, the hydrologic relation between the CP basin and both Yucca Flat and Frenchman Flat is highly complicated and uncertain. In other parts of the Frenchman Flat model area, more than 70 faults with significant displacement have been recognized and are included in the groundwater model.

The present-day water table is deep enough that the alluvium and tuffs are unsaturated beyond the faulted margins of the Frenchman Flat basin, and the alluvial and tuff aquifers in Frenchman Flat are isolated by the LCA from volcanic or alluvial aquifers outside the basin except toward the west. Based on hydrochemical differences, as well as hydraulic head gradients, the LCA does not appear to be the source of groundwater in the tuffs and alluvium of Frenchman Flat (Hershey et al., 2005). Thus, the only possible source of the groundwater in tuffs and alluvium of Frenchman Flat is local recharge and groundwater flow from the CP basin or the Wahmonie Hills to the west. Although the Cane Spring fault appears to impede groundwater inflow from CP basin into Frenchman Flat (Winograd and Thordarson, 1975), the absence of major basin-bounding faults along the western margin of Frenchman Flat and the monoclinical structure and lateral continuity of the HSUs here probably permit some flow into the western part of the Frenchman Flat basin from areas to the west.

Three conceptual models for groundwater flow in the Frenchman Flat model area were proposed prior to the development of the Phase II Frenchman Flat CAU steady-state groundwater flow model. These conceptual models are not mutually exclusive. The first conceptual model was proposed by Winograd and Thordarson (1975) and updated by Lacznia et al. (1996). This conceptual model was based on an assumption that water in the AA is semiperched and is characterized by a vertical flow system from the AA to the LCA through an internal outlet in the vicinity of the Frenchman Lake playa or through another local sink. In addition, this conceptual model allowed for the possibility that water moves from the AA to the LCA through slow lateral flow to the basin edge. The second conceptual model suggests flow in the AA is consistent with LCA flow direction going from north to south. This conceptualization is based on regional flow model results, which indicated this flow direction (DOE/NV, 1997), rather than by site-specific data. The third conceptual model suggested that water in CP basin to the west/northwest of Frenchman Flat leaks through the Cane Spring fault into the Frenchman Flat basin (IT, 1999a) and the general flow in the Frenchman Flat basin is from

north to south/southeast. This conceptual model is supported by three observations: 1) observed water levels in CP basin are much higher than those in the Frenchman Flat basin, 2) observed water levels in the AA are lower to the south and east of the Frenchman Lake playa, and 3) water levels observed in Well UE-5c WW in the northwest alluvium are greater than those observed in the central or east basin. This conceptual model was chosen as the basis for the Frenchman Flat CAU Phase I flow model (IT, 1999a). The Phase II Frenchman Flat flow model does not make any presumptions regarding which of these three conceptual models is correct, but is designed in a way that allows aspects of all of these conceptual models to be investigated and flow directions to be determined as a result of model calibration.

Groundwater flow through the basin alluvial and volcanic units overlying the LCA is driven by recharge within the basin and groundwater flow from areas of higher head to the west of the basin. Hydraulic head data do not indicate large lateral or vertical gradients and suggest that groundwater flow is slow within the basin, a conclusion that is consistent with low rates of recharge and limited inflow to the basin across the Cane Spring fault inferred from the large water-level differences between the Frenchman Flat and CP basins. Rates of present-day recharge in the model area are 1 percent or less of the total fluxes estimated to pass through the model area, mostly through the LCA.

Water-level observations and aquifer tests indicate nearly absent vertical hydraulic gradients in the AA, combined with effects of depth decay in permeability and the possibility of k_h/k_v ratios much greater than unity indicate that groundwater flow in the AA will be predominantly lateral to the basin margins. Furthermore, the low recharge rates estimated for the basin, and the limited inflow across the Cane Spring fault, suggest that lateral groundwater movement within the basin will be slow.

Previous modeling and data analysis activities undertaken to understand the Frenchman Flat groundwater flow system include: three recharge models developed using different principles, two regional-scale groundwater models, and a geochemical analysis to understand both local and regional groundwater flow paths. Additionally, the hydrostratigraphy of the site was evaluated and one base (most likely) and four alternative hydrostratigraphic framework models were constructed using numerous boreholes, outcrop data, and geophysical studies to understand the subsurface geology of the Frenchman Flat area.

The foundation of the flow model analysis is the Phase II hydrostratigraphic framework model (HFM) prepared and documented by BN (2005a). The BASE HFM represents a consensus view of the currently most viable model based on existing data. To investigate the uncertainty in the BASE HFM, four alternative models were developed to assess the potential impact of alternative geologic interpretations on groundwater flow and the transport of contaminants in groundwater. The basalt lava flow aquifer (BLFA) alternative increases the lateral continuity of the basalt lava flow aquifer. The detachment fault (DETA) alternative removes a fault and increases the continuity of several volcanic aquifers. The displacement fault (DISP) alternative juxtaposes shallow volcanic aquifers against the LCA to evaluate the effects of increased hydraulic connections among these units. Finally, the CP thrust (CPBA) alternative includes an adjustment of the stratigraphy in the northwest corner of the model. Each of these HFMs was evaluated to determine uncertainty in the calibrated flow field of the BASE HFM.

The hydrostratigraphy of the Frenchman Flat CAU model area was translated into a computational grid using a grid refinement approach that was conditioned to capture the complex geometry of HSUs, structural faults, open intervals of wells, and underground nuclear test cavities. To improve model consistency and efficiency during calibration, a single finite element mesh was created that was flexible enough to allow each HFM to be easily substituted into the flow model. Mesh nodes were spaced with five levels of refinement. Nodes closer to the HSU interfaces and near fault planes had smaller spacing, with node spacing increasing where less detail was necessary to capture HFM and underground nuclear test features. Surfaces were generated for 17 HSUs and more than 70 faults, resulting in a grid with 1,250,721 nodes and 7,144,765 tetrahedral elements.

Boundary conditions for the Frenchman Flat flow model included specified recharge fluxes along the upper surface of the model and specified heads along the lateral boundaries. The recharge flux distributions for Frenchman Flat were developed from several recharge model approaches used in support of regional groundwater models of the flow system. The lateral boundary heads for the Frenchman Flat flow model were estimated by interpolation hydraulic heads from the regional models onto the lateral boundaries of the Frenchman Flat flow model.

Net groundwater fluxes calculated by the regional models across planes coinciding with the lateral boundaries of the Frenchman Flat flow model were calculated and used along with 30 hydraulic head

measurements as calibration targets. Measurement uncertainty and calibration weights were determined for the hydraulic head measurements by considering uncertainty in different aspects of the head measurements such as land-surface elevation, depth to groundwater, and borehole deviations from vertical. Permeability within the model varied among the HSUs and as a function both of depth and of the permeability modification factors that were applied to the faults during calibration. Permeability depth decay in the AA and OAA was subject to an uncertainty analysis in which a model calibration was completed without treating permeability as a function of depth.

The calibration strategy developed for the Frenchman Flat flow model was to: (1) optimize groundwater fluxes through the sides of the model by adjusting the permeability of the LCA and major faults that intersect the model boundaries using automated parameter estimation software; (2) match hydraulic heads in the CP basin and near other model boundaries by selectively adjusting heads along the model boundary, and, when applicable, by optimizing fault permeabilities within and adjacent to the CP basin; and (3) match hydraulic heads in the alluvium and tuffs within the Frenchman Flat basin by adjusting the permeabilities of the alluvium, tuffs, and minor faults that sensitivity studies indicated would have the desired impact to the calculated hydraulic heads.

The number of adjustable parameters in the model is relatively large (more than 100), due to the hydrogeologic detail in the model, compared to the number of target observations available to constrain the model. The large number of faults and HSUs in the model made it difficult to evaluate the values of individual parameters from the data alone. Hence, sensitivity studies, prior information on HSU permeabilities and expert judgement based on established conceptual models of the NTS flow system all played an important role in guiding model calibration. Although the large number of parameters created challenges, it also meant that the model had the flexibility to explore the impact of different geologic features and parameterization on the groundwater flow patterns.

The calibrated model fit the target head and flux data well, with parameters that are reasonable for their respective HSU type. Additionally, the simulated heads in the AA matched the head data with a high degree of accuracy, and correctly simulated the observed lateral gradient in the basin and the observed near-absence of a vertical gradient within the AA. Therefore, there seems to be little potential for downward flow in the alluvium, despite the overall drop in heads between the alluvial aquifers and the carbonate aquifer. The data and the model results indicate that most of the head loss

between the alluvial aquifers and the carbonate aquifer occurs across the thick confining units like the VCU and LTCU that line the bottom and flanks of Frenchman Flat basin.

The permeabilities estimated during calibration of the BASE-USGSD flow model were compared to the data from the general NTS area and Frenchman Flat. The match between the estimated and measured hydraulic conductivities was satisfactory in most cases. For AA, the estimated permeability was toward the lower end of the observed data range. The effects of increasing the estimated permeability in the AA to bring it into better agreement with the data would be to increase the lateral rate of groundwater movement in the model if the horizontal head gradient were to remain the same. However, with these increases in horizontal hydraulic conductivity of the AA, it is likely that either greater anisotropy or depth decay would be required, thus limiting vertical migration even further.

The simulated heads in the AA matched the head data with a high degree of accuracy and correctly simulated the near-absence of both vertical and lateral gradients within the AA indicated in the data. A comparison of measured heads at the ER-5-3 well complex with a vertical profile of simulated heads produced with the BASE-USGSD flow model indicated that both measured and modeled vertical head gradients are virtually non-existent between the alluvium and the underlying volcanic aquifers near the ER-5-3 well complex. Therefore, there seems to be very little potential for downward flow in the alluvium in the northern testing area, despite the overall drop in heads between the alluvium and the LCA. The data and the model results indicated that most of the head loss between the alluvium and the carbonate aquifer occurs across the thick confining units, like the LTCU, that are present beneath the northern testing area. A similar comparison between measured and simulated heads at the ER-5-4 well complex indicates that simulated heads in the BASE-USGSD model again accurately depict the near-constant heads in the alluvium. Again, this would suggest that there is very little downward gradient through the alluvium that would create downward flow in the central testing area. Simulated heads show an almost 1-m increase between the lower alluvium and the TM-WTA, creating a pressure barrier that would also prevent groundwater movement into the LCA. Although data do not exist to evaluate the presence of a pressure barrier in the TM-WTA, measured hydraulic heads of more than 754 m in the LTCU at Well ER-5-4 #2 indicate that the concept of a pressure barrier in the central part of Frenchman Flat is feasible. The results of the BASE-USGSD flow model indicate the this pressure barrier could arise when high-permeability units

like the TM-WTA (or similar lithologies embedded within the thick LTCU) act as confined aquifers and connect the deep parts of the Frenchman Flat basin with areas of higher head to the west.

The distribution of HSUs, combined with the superimposed effects of faults and depth decay of HSU permeability serves to create an extremely complex distribution of permeability within the model that results in a correspondingly complex flow field. Flow patterns in the northern testing area, identified from particle tracks, show that large contrasts in the permeability among the HSUs results in groundwater flow focused into certain units and around other HSUs. The geometry of the HSUs and their estimated permeability cause groundwater flow to bifurcate in the northern testing area, with flow north of a detachment fault flowing east or northeast, and groundwater to the south of the detachment fault flowing predominantly southward. In the central testing area, where the shallow hydrostratigraphy is considerably simpler, groundwater flow is toward the southeast. From particle tracking, it appears that most of the shallow groundwater flowing beneath the testing areas eventually exits the model through the Rock Valley fault system in the southwest corner of the model.

A sensitivity analyses using local techniques where all parameters are adjusted slightly over their range of uncertainty and perturbation analysis where parameters are changed significantly by multiple standard deviations or orders of magnitude were used to evaluate the influence of the model parameters on the model response. The perturbation analysis varied properties of HSUs and faults over their range of uncertainty, providing a comprehensive picture of model behavior (although this analysis does not evaluate changes to other model parameters that may be required to maintain model calibration when a selected parameter is perturbed). From these detailed sensitivity studies, considerable insight has been gained about the factors that influence the flow model's ability to match the target water levels and boundary fluxes, and, in the process, insight about the factors that influence the overall behavior of the groundwater flow system.

Faults in the Rock Valley fault system are the dominant features in the LCA underlying Frenchman Flat and exert significant control on the direction of regional groundwater movement. The faults in the Rock Valley fault system are assumed not to propagate upward into the alluvial or volcanic units in the BASE-USGSD flow model. The effect of the Rock Valley fault system on the water levels at target well locations was modest. Faults located in the central portion of the basin appear to decrease

the water-table elevation when their permeability increases, but faults in the LCA along the southern edge of the model domain increase the water-table elevation in the AA as their permeability decreases.

The Cane Spring fault separates the CP basin in the northwestern portion of the model domain from the Frenchman Flat basin. This fault has little bearing on the boundary fluxes in the CAU model, but it has a pronounced effect on the simulated hydraulic heads. During calibration of the BASE-USGSD model, the fault was separated into two sections: one south and west of the CP Hogback, and the other north and east of the CP Hogback. In the BASE-USGSD model, the southern section of the fault has much lower permeability than the surrounding rocks. Overall, water levels in the AA within the Frenchman Flat basin are very sensitive to changes in the permeability of the southern portion of the fault and show almost no sensitivity to the northern portion. If the entire fault were much tighter than the surrounding rocks, the modeled water-level elevation in the central portion of Frenchman Flat basin was lower than observed. This indicates that a small flux from CP basin is necessary to maintain water levels in the Frenchman Flat OAA and AA.

The permeability of certain HSUs play a very important role in maintaining hydraulic heads and routing groundwater fluxes into and out of the Frenchman Flat AA. Sensitivity analyses demonstrate how hydraulic heads are affected by changes in Hsu permeabilities. It was evident from these analyses that contrasts in the permeabilities of key HSUs were as important as the absolute magnitudes of the permeabilities in affecting water levels within the AA and underlying HSUs.

Just as simulated water levels in northern Frenchman Flat were significantly affected by permeabilities assigned to different parts of the Cane Spring fault, the AA permeability itself was found to be an important factor in determining these water levels. Sensitivity analyses that focused on the factors affecting water levels in the AA demonstrated that increasing the permeability of the AA decreased water levels in the AA. Conversely, increasing the permeability of the Timber Mountain aquifers (TM-LVTA and TM-WTA) and the TSA resulted in a modest increase in the AA water levels by increasing groundwater flux into the OAA and AA in northern Frenchman Flat from CP basin. Water levels in the OAA and AA appeared to be insensitive to all of the HSUs embedded within these units, including the BLFA, PCU1U, PCU1L, and PCU.

Water levels in central Frenchman Flat are maintained through a balance of AA and VCU permeabilities at the southern end and by permeability values assigned to the WCU and LTCU in the northern end. The permeability values for the AA and VCU are positively correlated, indicating that changes to the calibrated values of these units results in similar model responses at the calibration targets. Because many of the water-level observations in the AA are located in the central portion of the Frenchman Flat basin, the ability for the model to match hydraulic head data is most strongly influenced by the permeability contrast between the AA and the VCU.

Unlike the other volcanic confining units, which tend to increase water levels in the AA as their permeability is decreased, a decrease in the permeability of the WCU produces lower water levels in the AA. This effect suggests that simulated water levels in the central part of Frenchman Flat are sustained by groundwater flow from the Wahmonie Hills near the western edge of the model in the BASE-USGSD model.

Changes in the permeability of the LCA strongly affect the magnitude and direction of the lateral boundary fluxes. This is not surprising given the thickness and extent of the LCA along the model boundaries. Water levels throughout the Frenchman Flat basin alluvial and volcanic HSUs also showed some sensitivity to small changes in the permeability of the LCA. The LCA permeability appeared to influence shallow water levels in the alluvium by changing the heads in the LCA and thus affecting hydraulic gradients across the confining units that separate the AA from the LCA. However, the relative hydrologic isolation of the AA from the regional LCA was apparent in the limited influence that changes to the AA permeabilities had on boundary fluxes.

Steady-state groundwater flow models were used to assess conceptual model uncertainty of the Frenchman Flat flow system. The primary goal of this assessment was to define the uncertainty of the flow system associated with alternative HFM uncertainty, boundary condition uncertainty, and HSU or fault parameter uncertainty. The assessment is also intended to provide guidance on how to include or represent these uncertainties in the transport simulations used to calculate the contaminant boundary. The mechanisms to express model response uncertainty are identified in the CAIP and include variability in simulating the groundwater flow paths and fluxes (DOE/NV, 1999). The approach was *not* to define all potential variations in flow paths and fluxes, but instead to establish the range of variation using realistic combinations of alternative conceptual models and parameter sets.

To assess uncertainty in the geologic system, four alternative HFMs were considered. Each of the HFMs included 17 HSUs, of which 8 were considered as aquifers and 9 as confining units, and more than 70 faults that were included based on their potential hydrologic significance. Each of these HFMs was used in conjunction with a map of recharge for the Frenchman Flat area that was taken from a water-balance model of infiltration and recharge (designated the USGSD model) originally developed for the regional model area.

Independently calibrated models for the BASE and CPBA HFMs provide generally similar fits for boundary fluxes and simulated heads when calibrated with the USGSD boundary conditions, with the exception of measured heads at WW-C, WW-C1, WW-4, and WW-4A, where the heads are better simulated by the BASE-USGSD model. Calibration fits are generally superior for the BASE-USGSD model compared to the CPBA-USGSD alternative for multiple statistical parameters that characterize goodness of fit. Particle tracks demonstrate that the simulated groundwater flow fields are generally similar for the northern testing area in both models with the exception of particle tracks starting in the vicinity of the PIN STRIPE test location. The DISP-USGSD alternative indicated that a completely open connection between the alluvium and the LCA is unrealistic, but that modest adjustments to fault parameters allow for a good match of the model to water-level measurements. A decrease in the permeability along the trace of one of the main Rock Valley faults (fault 34) through the alluvial aquifer in the DISP-USGSD alternative provides a low permeability feature, first hypothesized by Winograd and Thordarson (1975), which improves the model fit to observed heads at WW-5B and WW-5C and matches the loss in head in the vicinity of the playa. Flow paths in the DISP-USGSD model were similar to the other HFMs in the central testing area, but the northern testing area had considerably more flow to the east. The BLFA-USGSD and DETA-USGSD model alternatives were calibrated using the identical parameters estimated during calibration of the BASE-USGSD model. Both models show similar patterns of groundwater flow in the southern testing area compared to the BASE-USGSD model and show some variability in particles tracks compared to the BASE-USGSD model for the northern testing area. The primary differences are in the direction of the particle trajectories and in HSUs traversed along the pathways (as a result of changes in the hydrostratigraphy). The significance of variability in the groundwater flow fields to contaminant transport that results from the use of different HFMs will be evaluated during transport modeling studies.

Discrete uncertainty analyses were also done with the BASE-USGSD and BLFA-USGSD flow models to examine the effects of changes in the properties of selected faults on the model calibration and resulting groundwater flow paths. The permeability of two faults (35 and 38) in the alluvial and volcanic sections and one HSU (BLFA) was increased to the point where the model calibration was significantly impacted. These parameters were selected because of their great uncertainty and their potential to affect flow from underground nuclear tests. Changes to parameters in the northern testing area suggest that flow trajectories may be modified through adjustment to the selected model parameters, but the ability of other model parameters to compensate for the model misfit was not determined. In this sense, the effects of these changes may be exaggerated. However, when these flow fields are used to compute contaminant transport for the time of interest while accounting for the appropriate transport processes, the extent of these small changes to groundwater flow may be inconsequential to predicted contaminant migration. Changes to tested model parameters in the central testing area have little influence on the resulting steady-state groundwater flow field.

To assess the impact of boundary condition uncertainty on groundwater flow paths in the Frenchman Flat CAU model, the two alternative HFMs that are most distinctly different based on calibration with the USGSD boundary conditions (BASE and CPBA HFM alternatives) were also calibrated with the DRIA-, MME-, and DVRFS-boundary conditions. These models were used to bound the uncertainty in the CAU flow system resulting from variations in boundary conditions that were produced through the use of multiple recharge distributions and two regional groundwater flow models. Because areal recharge along the top of the Frenchman Flat CAU flow model is small regardless of the recharge model, the differences among the calculated boundary heads and boundary fluxes dominated this component of the uncertainty analyses. Additional boundary condition uncertainty analysis was completed to determine the impact of boundary head adjustment methodology on calculated steady-state groundwater flow fields.

Results from the MME boundary conditions using the BASE HFM and CPBA HFM are most similar to the BASE-USGSD model and provided the best overall match to the hydraulic head calibration data among the models evaluating boundary conditions. The MME models matched the observed downward head gradient between the alluvium and LCA in northern Frenchman Flat. The groundwater flow paths at the northern edge of Frenchman Flat basin appeared to be dominated by eastward advection in both of these models. Simulated hydraulic heads in the central part of

Frenchman Flat decline gently toward the southeast in both models, as was observed in the BASE-USGSD model, indicating that shallow groundwater flow out of central Frenchman Flat will also be in this direction.

Results from the DVRFS boundary conditions using the BASE HFM and CPBA HFM are the most dissimilar to the BASE-USGSD model. These models provided as good an overall fit as other models to both the hydraulic head at the observations and boundary flows. However, the simulated head in LCA for both models was higher than heads measured in the overlying alluvium and tuffs. This indicates an upward head gradient between the alluvium and LCA, contrary to the both hydraulic head data and the conceptual understanding of the Frenchman Flat flow system. Lateral groundwater flow paths in the testing areas for the BASE-DVRFS and CPBA-DVRFS alternatives were similar to the MME- and USGSD- models indicating that flow paths in the volcanic and basin-fill HSUs did not appear to be impacted by the upward gradient. The impact of the higher heads in the LCA was probably attenuated by the low permeability of the LTCU that separates the local flow system from the regional flow system.

Given the consistency in groundwater flow paths generated by both the DVRFS- and MME-boundary conditions in the BASE HFM and CPBA HFM, the variation between these HFMs when they are calibrated using the DRIA boundary conditions is striking. For the CPBA-DRIA, the simulated head in LCA was higher than hydraulic head measured in the overlying alluvium and tuffs. This indicates an upward head gradient between the alluvium and LCA, contrary to the local data at ER-5-3 #2 and the conceptual understanding of the Frenchman Flat flow system. For the BASE-DRIA calibration, there is a slight downward gradient in the northern testing area between the alluvium and LCA. Groundwater flow paths simulated by the BASE-DRIA model in the northern testing area are similar to those observed in the BASE-DVRFS model. Groundwater flow paths in the central testing area for both the BASE-DRIA and CPBA-DRIA models indicate lateral flow in the alluvium to the southeast.

For the BASE-USGSD flow model, an alternative approach to boundary head modifications was investigated in which heads adjustment were differentiated based on HSU. In the LCA, heads were lowered on all faces of the model, to improve the match of modeled heads to measured water levels at the LCA calibration targets. In the CP basin area heads were increased only in the tuffs to improve the match of the model to measured water levels at WW-4 and WW-4A. To calibrate a model with these

changes, a hydraulic connection in the volcanic units of CP basin and Frenchman Flat basin was established to route the water from areas of higher head (CP basin) into the basin-fill material of Frenchman Flat basin. This hydraulic connection was implemented by further subdividing the Cane Spring fault and locally increasing the fault permeability. Heads on the boundary adjacent to CP basin were increased to greater than 1,000 m amsl, which is significantly higher than the observed head in these units within CP basin, to establish and maintain hydraulic heads in Frenchman Flat basin. Although the calibrated HSU permeabilities and hydraulic head simulations match the data very well, the required large change in boundary heads suggests that this connection may not be plausible with this HFM configuration. Advective particle tracks show a strong eastern component of flow in the northern testing area. Particle trajectories in the central testing area were very similar to those observed in other calibrated flow models. The general orientation of flow paths appears to be within the range of the other calibrated flow models that were used to evaluate either boundary condition, HFM, or discrete uncertainty. Further consideration will be given to this flow model during transport calculations to determine whether the flow field demonstrates different transport behavior within the time of interest given reasonable transport parameters.

Overall, the boundary condition uncertainty analyses indicate that groundwater flow paths in the central testing area are similar among the calibrated flow models, but that the flow paths in the northern testing area are more sensitive to changes in boundary conditions than changes in HFM.

A review of the hydrogeologic literature demonstrates that depth decay in permeability or hydraulic conductivity has been recognized for decades by investigators in many geologic environments and has also been routinely adopted in groundwater modeling studies. Thus, reduction in permeability with depth has a sound technical basis. Initial depth-decay relationships based on site-specific data are valuable starting points for model parameterization that can then be modified during model calibration. For the Frenchman Flat CAU flow model, depth decay was applied to all alluvial, volcanic, and carbonate units. Sufficient data to evaluate depth decay in permeability do not exist for HSUs other than the AA and OAA, and these site-specific data do not clearly support the use of depth decay in the alluvium of Frenchman Flat. Consequently, depth decay in permeability in the alluvium is considered as a conceptual model uncertainty that was investigated by considering an alternative model in which the permeability of the AA and OAA are constant with depth.

Calibration of an alternative BASE-USGSD flow model with permeability depth decay applied to volcanic and carbonate units, but not to the alluvium, was generally successful in matching the available head data within the constraints of the field-scale permeability data. However, model calibration did require higher values of anisotropy (than the BASE-USGSD with permeability depth decay) in the OAA and AA and similar values for horizontal permeability, nearly eliminating any vertical flow in the most shallow portion of the AA and OAA. The BASE-USGSD model with constant permeability in the AA and OAA has similar flow paths to other models used to bound conceptual model uncertainty of the Frenchman Flat flow system. Thus, while there is uncertainty in the applicability of depth decay in the AA and OAA (the HSUs into which most of the underground nuclear test radionuclide source will be applied) as well as the value of the depth decay coefficients, the parameters required to calibrate the flow model in the absence of such effects do not greatly change the direction of groundwater movement. In the areas near the underground nuclear testing, the model tends to overpredict heads in the tuff confining units and the LCA while underpredicting heads at the edges of the basin-fill units. Assessment of radionuclide transport using realistic transport parameters will consider variability in the conceptual model of the flow system provided by this model calibration.

The steady-state groundwater flow models that were used to assess conceptual model uncertainty of the Frenchman Flat groundwater flow system demonstrated that shallow groundwater flow near the testing areas is similar in these models despite considerably different hydrostratigraphy, approaches to defining boundary conditions, discrete HSU and fault permeability changes, and methods of model parameterization. All of the models evaluated demonstrated that the shallow flow system had lateral migration with only modest vertical flow until particles reached the edges of the basin. Upon reaching the edge of the basin, particles moved from the VCU or LTCU into the LCA and exited the flow system through the regional, Rock Valley fault system. To maintain higher heads in the basin-fill HSUs, compared to the lower heads present in the LCA, the calibrated head fields showed regions of higher head occurring in the volcanic HSUs. The presence of these high head zones in the volcanic HSUs effectively separates the shallow flow system from the regional flow system. Attempts to increase the vertical flow through the center of the basin by both decreasing and eliminating depth decay of permeability demonstrated that vertical flow unlikely based on the need to increase anisotropy and decrease HSU permeability. Additionally, attempts to create a connection between the alluvial and volcanic aquifers and the LCA across a basin-bounding fault in the DISP alternative

indicated that this hydrologic connection could not be maintained without a reduction in fault permeability. In this alternative a good match to heads in the area adjacent to Frenchman Lake playa was achieved through a reduction in fault permeability in the basin-fill materials.

The flow models demonstrated that the AA and OAA of Frenchman Flat basin are fed by water originating in CP basin and the Wahmonie Hills. The proportion of flow from either of these areas is highly uncertain, but through the application of two regional models and several sets of boundary conditions the relative magnitude of water entering the basin from these two areas was varied.

Overall, conceptual model uncertainty analyses indicate that groundwater flow in Frenchman Flat basin near the northern testing area tends to be north to south or northwest to southeast for flow paths near NEW POINT, DERRINGER, DIANA MOON, and MINUTE STEAK test locations. Water flows through the OAA and BLFA into the AA and TM-WTA and moves to the southeast until reaching the basin edge. The groundwater flow paths seem to be dominated by the influx of water moving across the Cane Spring fault in the volcanic HSUs and into the basin-fill units along the northwest edge of the Frenchman Flat basin.

Along the northern edge of the basin, water flows eastward within the TSA and LVTA. These units form an arcuate band of higher permeability where they intersect the water table along the northern flank of the Frenchman Flat basin. This band of higher permeability creates a strong hydraulic connection in the model between the higher hydraulic heads in the CP basin to the west and locations beneath the PIN STRIPE test.

In the central testing area of Frenchman Flat, groundwater flow is substantially less complex than in the northern testing area. The movement of particles initially located near the water table near the CAMBRIC test cavity and beneath the DILUTED WATERS and WISHBONE test locations indicate that groundwater flow out of the central testing area will be through the alluvium toward the southeast.

As a means to independently verify the flow paths generated by the Phase II Frenchman Flat CAU flow model, groundwater ^{14}C data from the tuffs and alluvium in Frenchman Flat were used to calculate ages (residence times) for these groundwaters. The calculated DI^{14}C ages of Frenchman Flat groundwater ranged from ~ 8,500 years to ~ 29,000 years. In general, younger groundwater is found

near the low hills bordering the northern and northwestern parts of the basin, and older groundwater is found toward the basin center, reflecting the near absence of recharge through the alluvium in the basin even during the relatively wet conditions that existed in the late Pleistocene and early Holocene. The absence of groundwater DI^{14}C ages younger than the early Holocene, even along the basin margins, is consistent with paleo-climate reconstructions based on vegetation preserved in pack-rat middens and on the ages of paleo-discharge deposits in nearby basins that indicate modern-day arid conditions were established in the NTS area by about 9,000 years ago. These age dates are consistent with the model flow paths that indicate water is moving from the northern and northwestern parts of the basin and flowing toward the basin center and out of the basin center to the southeast.

Inverse geochemical models were done with the geochemical modeling code PHREEQC to investigate the origin of groundwater at selected wells within the basin. These models confirmed that groundwater at Well PW-1 could originate by the southerly flow of groundwater from Well PW-2, coupled with plausible water/rock interactions. Similar models done for Well ER-5-4 in the central part of the basin indicate this groundwater could originate from either the southerly flow of groundwater from Well PW-1 or from a mixture of PW-1 groundwater and groundwater flowing southeast from UE-5c WW. Geochemical inverse models for Well ER-5-4 #2 could only explain the composition of this groundwater using both mixing and water/rock interactions. This groundwater appears to originate from a mixture of groundwater from the CP basin and groundwater from northwestern Frenchman Flat, suggesting that this groundwater may have been recharge in the low hills separating these two basins. This result agrees with evidence from hydraulic heads that the groundwater near Well ER-5-4 #2 has a strong hydraulic connection with groundwater in the vicinity of the CP basin.

Groundwater velocities were calculated at pairs of wells in the alluvium that were likely to lie along a flow path based on their relative chemical evolution. Groundwater velocities were calculated between well pairs with ^{14}C -based ages. Overall, groundwater flow paths between UE-5c WW and ER-5-4 had the largest uncertainty (0.12 to 0.85 m/yr). North-to-south flow paths in the alluvium were between 0.19 to 0.25 m/yr (the PW-1 to ER-5-4 flow path) to 0.43 m/yr (the PW-2 to PW-1 flow path). A higher groundwater velocity of 1.1 m/yr was estimated for a PW-1 to WW-1 flow path, but this velocity is subject to greater uncertainty because it is based on an age for WW-1 groundwater estimated indirectly from its dissolved cation concentrations. An analysis of groundwater travel time

for a mixture of groundwaters involving components from the CP basin (Wells WW-4 and WW-4A) and from UE-5c WW indicated that groundwater velocities in the volcanic rocks along the flow path was about 0.6 m/yr.

In summary, groundwater flow paths from the geochemical analysis generally support an overall northwest to southeast flow direction for shallow groundwater in the Frenchman Flat basin. The low rates of groundwater movement estimated for Frenchman Flat basin are consistent with the near absence of recharge to the basin over the last 8,500 years and with the nearly flat water table. The estimated groundwater velocities in the alluvium indicate that transport distance of between about 100 to 1,000 m can be expected over the next 1,000 years.

10.0 REFERENCES

ASTM, see American Society for Testing and Materials.

American Society for Testing and Materials. 1993a. *Standard Guide for Application of a Ground-Water Flow Model to a Site-Specific Problem*, ASTM D 5447-93. Philadelphia, PA.

American Society for Testing and Materials. 1993b. *Standard Guide for Comparing Ground-Water Flow Model Simulations to Site-Specific Information*, ASTM D 5490-93. Philadelphia, PA.

American Society for Testing and Materials. 1994a. *Standard Guide for Conducting a Sensitivity Analysis for a Ground-Water Flow Model Application*, ASTM D 5611-94. Philadelphia, PA.

American Society for Testing and Materials. 1994b. *Standard Guide for Defining Initial Conditions in Ground-Water Flow Modeling*, ASTM D 5610-94. Philadelphia, PA.

American Society for Testing and Materials. 1996. *Standard Guide for Calibrating a Ground-Water Flow Model Application*, ASTM D 5981-96. Philadelphia, PA.

Anderson, M.P. 1979. "Using Models To Simulate the Movement of Contaminants Through Groundwater Systems." In *CRC Critical Reviews in Environmental Control* 9(2), 97-156.

Anderson, M.P., and W.W. Woessner. 1992. *Applied Groundwater Modeling*. San Diego, CA: Academic Press.

Andrews, J.N., J.C. Fontes, J.L. Michelot, and D. Elmore. 1986. "In-situ Neutron Flux, ^{36}Cl Production and Groundwater Evolution in Crystalline Rocks at Stripa, Sweden." In *Earth and Planetary Science Letters*, 77:49-59.

Antonellini, M.A., and A. Aydin. 1994. "Effect of Faulting on Fluid Flow in Porous Sandstones: Petrophysical Properties." In *AAPG Bulletin*, v. 78: 355-377.

Antonellini, M.A., and A. Aydin. 1995. "Effect of Faulting on Fluid Flow in Porous Sandstones: Geometry and Spatial Distribution." In *AAPG Bulletin*, v. 79(0): 642-671.

Antonelli, M., A. Aydin, and L. Orr. 1999. "Outcrop-Aided Characterization of a Faulted Hydrocarbon Reservoir: Arroyo Grande Oil Field, California, USA." In *American Geophysical Union Monograph*, "Faults and Subsurface Fluid Flow in the Shallow Crust." (W. Haneberg, et al., eds.), v. 113: 7-26.

BN, see Bechtel Nevada.

BSC, see Bechtel SAIC Company.

Bard, E., M Arnold, B. Hamelin, N. Tisnerat-Laborde, and G. Cabioch. 1998. "Radiocarbon Calibration by Means of Mass Spectrometric $^{230}\text{Th}/^{234}\text{U}$ and ^{14}C Ages of Corals: An Updated Database Including Samples from Barbados, Mururoa and Tahiti. In *Radiocarbon* v.40(3): p1085-1092.

Bechtel Nevada. 2005a. *A Hydrostratigraphic Framework Model and Alternatives for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Clark, Lincoln, and Nye Counties, Nevada*, DOE/NV/11718--1064. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.

Bechtel Nevada. 2005b. *Completion Report for Well Cluster ER-5-3*, DOE/NV/11718-1093. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.

Bechtel SAIC Company. 2004. *Geochemical and Isotopic Constraints on Groundwater Flow Directions, Mixing, and Recharge at Yucca Mountain, Nevada*, ANL-NBS-HS-000021, Rev 1. Las Vegas, NV.

Beck, J.W., D.A. Richards, R.L. Edwards, B.W. Silverman, P.L. Smart, D.J. Donahue, S. Hererra-Osterheld, G.S. Burr, L. Calsoyas, A.J. T. Jull, and D. Biddulph. 2001. "Extremely Large Variations of Atmospheric ^{14}C Concentration During the Last Glacial Period." In *Science* v. 292: 2453-2458.

Belcher, W.R., J.B. Blainey, F.A. D'Agnesse, C.C. Faunt, M.C. Hill, R.J. Laczniaik, G.M. O'Brien, C.J. Potter, H.M. Putnam, C.A. San Juan, and D.S. Sweetkind. 2004. *Death Valley Regional Ground-Water Flow System, Nevada and California--Hydrogeologic Framework and Transient Ground-Water Flow Model*, Scientific Investigations Report 2004-5205. U.S. Geological Survey. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office.

Benedict, Jr. F.C., T.P. Rose, J.M. Thomas, R. Waddell, and R. Jacobson. 2003. *Geochemistry Technical Basis Document*, Report Publication No. 45205, DOE/NV/13609-34. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV: Desert Research Institute.

Benson, L., and H. Klieforth. 1989. "Stable Isotopes in Precipitation and Ground Water in the Yucca Mountain Region, Southern Nevada: Paleoclimatic Implications." In *Geophysical Monograph*, "Aspects of Climate Variability in the Pacific and the Western Americas." v. 55: 41-59. Washington, DC: American Geophysical Union.

- Beven, K., and J. Freer. 2001. "Equifinality, Data Assimilation, and Uncertainty Estimation in Mechanistic Modelling of Complex Environment Systems Using the GLUE Methodology." In *Journal of Hydrology*, 249, 11-29.
- Blankennagel, R.K., and J.E. Weir, Jr. 1973. *Geohydrology of the Eastern Part of Pahute Mesa, Nevada Test Site, Nye County, Nevada*, Professional Paper 712-B. Denver, CO: U.S. Geological Survey.
- Bright, D.J., S.A. Watkins, and B.A. Lisle. 2001. *Analysis of Water Levels in the Frenchman Flat Area, Nevada Test Site*, Water-Resources Investigations Report 00-4272. Denver, CO: U.S. Geological Survey.
- Budd, D.A. 2001. "Permeability Loss with Depth in the Cenozoic Carbonate Platform of West-Central Florida." In *American Association of Petroleum Geologists*. Bulletin v. 85: (7): 1253-1272.
- Burton, W.C., L.N. Plummer, E. Busenberg, B.D. Lindsey, and W.R. Gburek. 2002. "Influence of Fracture Anisotropy on Ground-Water Ages and Chemistry, Valley and Ridge Province, Pennsylvania." In *Ground Water* v. 40: 242-257.
- Byers, F.M., Jr., and C.H. Miller. 1966. *Geologic and Geophysical Log of the Ue5k Exploratory Hole, Frenchman Flat, Nevada Test Site*, USGS Technical Letter NTS-164. U.S. Geological Survey.
- Caine, J.S., J.P. Evans, and C.B. Forster. 1996. "Fault Zone Architecture and Permeability Structure." In *Geology*, v. 24(11): 1025-1028.
- Carle, S. F., M. Zavarin, and G. Pawloski. 2002. *Geostatistical Analysis of Spatial Variability of Mineral Abundance and Kd in Frenchman Flat, NTS, Alluvium*. Livermore, CA: Lawrence Livermore National Laboratory.
- Carr, W.J. 1974. *Summary of Tectonic and Structural Evidence for Stress Orientation at the Nevada Test Site*. Open File Report, 74-176, U.S. Geological Survey.
- Cashman, S., and K. Cashman. 2000. "Cataclasis and Deformation-Band Formation in Unconsolidated Marine Terrace Sand, Humboldt County, California." In *Geology*, v. 28(2): 111-114.
- Clark, I.D., and P. Fritz. 1997. *Environmental Isotopes in Hydrogeology*. Boca Raton, FL: Lewis Publishers.
- Crowe, B.M. 1990. *Basaltic Volcanic Episodes of the Yucca Mountain Region*, Preceding of the International Meeting on High-Level Radioactive Waste Management, American Nuclear Society, 65-73. Las Vegas, NV.

- Cullen, A.C., and H.C. Frey. 1999. *Probabilistic Techniques in Exposure Assessment*. New York, NY: Plenum Press.
- DOE, see U.S. Department of Energy.
- DOE/NV, see U.S. Department of Energy, Nevada Operations Office.
- DOE/ORD, see U.S. Department of Energy, Office of Civilian Radioactive Waste Management, Office of Repository Development.
- D'Agnese, F.A., C.C. Faunt, A.K. Turner, and M.C. Hill. 1997. *Hydrogeologic Evaluation and Numerical Simulation of the Death Valley Regional Ground-water Flow System, Nevada and California*, Water-Resources Investigations Report 96-4300. Denver, CO: U.S. Geological Survey.
- Davis, S.N., S. Moysey, L.D. Cecil, and M. Zreda. 2003. "Chlorine-36 in Groundwater of the United States: Empirical Data." In *Hydrogeology Journal* v. 11: 217-227.
- Davisson, M.L., D.K. Smith, J. Kenneally, and T.P. Rose. 1999. "Isotope Hydrology of Southern Nevada Groundwater: Stable Isotopes and Radiocarbon." In *Water Resources Research*, vol. 35 (1): 279-294.
- Dynamic Graphics, Inc. 2002. *EarthVision® 7: Software for 3-D Modeling and Visualization*. Alameda, CA.
- Edmunds, W.M., and P.L. Smedley. 2000. "Residence Time Indicators in Groundwater: The East Midlands Triassic Sandstone Aquifer." In *Applied Geochemistry*, v. 15: 737-752.
- EPA, see U.S. Environmental Protection Agency.
- FFACO, see *Federal Facility Agreement and Consent Order*.
- Fabryka-Martin, J., S.J. Wightman, W.J. Murphy, M.P. Wickham, M.W. Caffee, G.J. Nimz, J.R. Southon, and P. Sharma. 1993. *Distribution of Chlorine-36 in the Unsaturated Zone at Yucca Mountain: An Indicator of Fast Transport Paths*. Paper presented at FOCUS'93 Site Characterization and Model Validation. Las Vegas, NV.
- Faunt, C.C., F.A. D'Agnese, and G.M. O'Brien. 2004. "Hydrology," Chapter F, pp. 137-163. In *Death Valley Regional Ground-Water Flow System, Nevada and California- Hydrogeologic Framework and Transient Ground-Water Flow Model*, Belcher, W.R., ed., Scientific Investigations Report 2004-5205. As accessed at <http://water.usgs.gov/pub/sir/2004/5205/> on 28 October 2005.
- Federal Facility Agreement and Consent Order*. 1996, as amended. Agreed to by the State of Nevada, the U.S. Department of Energy, and the U.S. Department of Defense. Appendix VI,

which contains the Underground Test Area strategy, was last amended December 7, 2000.
Revision No. 1.

- Forester, R.M., J.P. Bradbury, C. Carter, A.B. Elvidge-Tuma, M.L. Hemphill, S.C. Lundstrom, S.A. Mahan, B.D. Marshall, L.A. Neymark, J.B. Paces, S.E. Sharpe, J.F. Whelan, and P.E. Wigand. 1999. *The Climatic and Hydrologic History of Southern Nevada During the Late Quaternary*, Open File Report 98-635. Denver, CO: U.S. Geological Survey.
- Forster, C.B., and J.P. Evans. 1991. "Hydrogeology of Fault Zones and Crystalline Thrust Sheets: Results of Field and Modeling Studies." In *Geophysical Research Letters*, v. 18: 979-982.
- Freeze, R.A., and J.A. Cherry. 1979. *Hydrology*. Englewood Cliffs, NJ: Prentice-Hall, Inc.
- French, R.H. 1986. *Daily, Seasonal, and Annual Precipitation at the Nevada Test Site, Nevada*, DOE/NV/10384/01, Publication No. 45042. Las Vegas, NV: Desert Research Institute.
- Freyberg, D.L. 1988. "An Exercise in Ground-Water Model Calibration and Prediction." In *Ground Water*, v. 26(N3): 350-360.
- Friedman, I., J.M. Harris, G.I. Smith, and C.A. Johnson. 2002a. "Stable Isotope Composition of Waters in the Great Basin, United States 1. Air-Mass Trajectories." In *Journal of Geophysical Research*, v. 107(D19): 14-1:14-14.
- Friedman, I., G.I. Smith, C.A. Johnson, and R.J. Moscat. 2002b. "Stable Isotope Compositions of Waters in the Great Basin, United States 2. Modern Precipitation." In *Journal of Geophysical Research*, v. 107(D19): 15-1:15-22.
- Fryar, D., R. Senger, N. Deeds, J. Pickens, T. Jones, A. Whallon, and K. Dean. 2003. "Groundwater Availability Modeling for the Northern Carrizo-Wilcox Aquifer." Contractor report for the Texas Water Development Board. Austin, TX.
- Geldon, A.L. 2004. "Hydraulic Tests of Miocene Volcanic Rocks at Yucca Mountain and Pahute Mesa and Implications for Groundwater Flow in the Southwest Nevada Volcanic Field, Nevada and California." In *Geological Society of America Special Paper 381*, p. 93. Boulder, CO.
- George, D.C. 1997. *Unstructured 3D Grid Toolbox for Modeling and Simulation*, LA-UR-97-3052. Los Alamos, NM: Los Alamos National Laboratory.
- Glynn, P.D., and L.N. Plummer. 2005. "Geochemistry and the Understanding of Ground-Water Systems." In *Hydrogeology Journal*, v. 13: 263-287.
- Grauch, V.J.S., and M.R. Hudson. 1995. "Preliminary Analysis of Major Structures and Lithologic Boundaries for the Frenchman Flat Model Area." Denver, CO: U.S. Geological Survey.

- Haneberg, W.C., P. Gomez, A. Gibson, and B. Allred. 1998. "Preliminary Measurements of Stress-Dependent Hydraulic Conductivity of Santa Fe Group Aquifer System Sediments from the 98th St Core Hole, Albuquerque, New Mexico, 14-20 February." In *New Mexico Geology*.
- Harbaugh, A.W., E.R. Banta, M.C. Hill, and M.G. McDonald. 2000. *MODFLOW-2000, the U.S. Geological Survey Modular Ground-Water Model -- User Guide to Modularization Concepts and the Ground-Water Flow Process*, Open-File Report 00-92. Reston, VA: U.S. Geological Survey.
- Helton, J.C., and F.J. Davis. 2000. "Sampling-Based Methods." In A. Saltelli, K. Chan, and E.M. Scott (Eds.), *Sensitivity Analysis* (pp. 101-153). Chichester, England: John Wiley & Sons, LTD.
- Hershey, R.L., O. Dahan, S.C. Calhoun, and R. Jacobson. 2001. *Geochemically Calibrated Discrete-State Cell Model of the Frenchman Flat Hydrographic Area*. Reno, NV: Desert Research Institute.
- Hershey, R.L., J.M. Thomas, T.P. Rose, J.B. Paces, I.M. Farnham and F.C. Benedict, Jr. 2005. *Evaluation of Groundwater Movement in the Frenchman Flat CAU Using Geochemical and Isotopic Analysis*, DOE/NV/13609-36, Publication No. 45207. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV: Desert Research Institute.
- Hevesi, J.A., A.L. Flint, and L.E. Flint. 2003. *Simulation of Net Infiltration and Potential Recharge Using a Distributed Parameter Watershed Model for the Death Valley Region, Nevada and California*, Water-Resources Investigations Report 03-4090. Sacramento, CA: U.S. Geological Survey.
- Heynekamp, M.R., L.B. Goodwin, and P.S. Mozley. 1999. "Controls on Fault-Zone Architecture in Poorly Lithified Sediments, Rio Grande Rift, New Mexico: Implications for Fault-Zone Permeability and Fluid Flow," In *Geophysical Monograph*, "Faults and Subsurface Fluid Flow in the Shallow Crust," v. 113: 27-48. Washington, DC: American Geophysical Union.
- Hill, M.C. 1998. *Methods and Guidelines for Effective Model Calibration*. Water-Resources Investigations Report 98-4005. Denver, CO: U.S. Geological Survey.
- Hinrichs, E.N., and E.J. McKay. 1965. "Geologic Map of the Plutonium Valley Quadrangle, Nye and Lincoln Counties, Nevada," Map GQ-384, Scale 1:24,000. Denver, CO: U.S. Geological Survey.
- ISCMEM, see Interagency Steering Committee on Multimedia Environmental Models.
- IT, see IT Corporation.

- Ingraham, N.L., B.F. Lyles, R.L. Jacobson, and J.W. Hess. 1991. "Stable Isotope Study of Precipitation and Spring Discharge in Southern Nevada." In *Journal of Hydrology* v. 125: 243-258.
- Interagency Steering Committee on Multimedia Environmental Models. 2003. *Proceedings of the International Workshop on Uncertainty, Sensitivity, and Parameter Estimation for Multimedia Environmental Modeling* (Tech. Rep. No. NUREG/CP-0187 ERDC SR-04-2 EPA/600/R-04/117). Rockville, MD: Federal Working Group on Uncertainty and Parameter Estimation.
- IT Corporation. 1996a. *Groundwater Recharge and Discharge Data Documentation Package (Phase I Data Analysis Documentation, Volume III)*, ITLV/10972--181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1996b. *Hydrologic Parameter Data Documentation Package (Phase I Data Analysis Documentation, Volume IV)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1996c. *Potentiometric Data Documentation Package (Phase I Data Analysis Documentation, Volume II)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1996d. *Regional Geologic Model Data Documentation Package (Phase I Data Analysis Documentation, Volume I)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1996e. *Transport Parameter and Source Term Data Documentation Package (Phase I Data Analysis Documentation, Volume V)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1996f. *Tritium Transport Model Documentation Package (Phase I Data Analysis Documentation, Volume VII)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1997a. *Groundwater Flow Model Documentation Package (Phase I Data Analysis Documentation, Volume VI)*, ITLV/10972-181. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1997b. *Value of Information Analysis for Corrective Action Unit No. 98: Frenchman Flat*, ITLV/10972--192. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1998. *Underground Test Area Project Corrective Action Unit 98: Frenchman Flat Data Analysis Task, Volume I - Hydrostratigraphic Model Documentation Package*, Rev. 0,

- DOE/NV/13052--044. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1999a. *External Peer Review Group Report on Frenchman Flat Data Analysis and Modeling Task, Underground Test Area Project*, Rev. 0, ITLV/13052--077. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 1999b. *Underground Test Area Project Corrective Action Unit 98: Frenchman Flat, Volume II - Groundwater Data Documentation Package*, Rev. 0, DOE/NV/13052--044. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 2000. *Lessons Learned from the Frenchman Flat Corrective Action Groundwater Flow and Radionuclide Transport Model*. Las Vegas, NV.
- IT Corporation. 2001a. *Addendum to the Frenchman Flat Hydrogeologic Investigation Wells Drilling and Completion Criteria*, ITLV/13052-094-Rev. 1-ADD. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Operations Office. Las Vegas, NV.
- IT Corporation. 2001b. *Modeling Approach for Corrective Action Unit 98, Frenchman Flat*, ITLV/13052--141. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Operations Office. Las Vegas, NV.
- Kernodle, J.M., D.P. McAda, and C.R. Thorne. 1995. *Simulation of Ground-Water Flow in the Albuquerque Basin, Central New Mexico, 1990 - 1994, with Projections to 2020*, USGS Water-Resources Investigations Report 98-4251. Denver, CO.
- Kitagawa, H. and J. van der Plicht. 1998. "A 40,000-year Varve Chronology from Lake Suigetsu, Japan: Extension of the ^{14}C Calibration Curve." In *Radiocarbon* v. 40(1): 505-515.
- Kuiper, L.K. 1994. *Nonlinear-Regression Flow Model of the Gulf Coast Aquifer Systems in the South-Central United States*, Water-Resources Investigations Report 93-4020. Denver, CO: U.S. Geological Survey.
- Laczniak, R.J., J. Cole, D.A. Sawyer, and D.A. Trudeau. 1996. *Summary of Hydrogeologic Controls and Ground-Water Flow at the Nevada Test Site, Nye County, Nevada*, Water-Resources Investigations Report 96-4109. Carson City, NV: U.S. Geological Survey.
- Laczniak, R.J., J.L. Smith, P.E. Elliott, G.A. DeMeo, M.A. Chatigny, and G. Roemer. 2001. *Ground-Water Discharge as Determined from Estimates of Evapotranspiration, Death Valley Regional Flow System, Nevada and California*, Water-Resources Investigations Report 01-4195. Carson City, NV: U.S. Geological Survey.
- Levy, S.S., S.J. Chipera, G. WoldeGabriel, J. Fabryka-Martin, J. Roach, and D. Sweetkind. 1999. "Flow-Path Textures and Mineralogy in Tuffs of the Unsaturated Zone." In *Geophysical*

- Monograph*, “Faults and Subsurface Fluid Flow in the Shallow Crust” (W. Haneberg, et al., eds.), v. 113:159-184. Washington, DC: American Geophysical Union.
- Loucks, R.G., M.M. Dodge, and W.E. Galloway. 1986. *Controls on Porosity and Permeability of Hydrocarbon Reservoirs in Lower Tertiary Sandstones along the Texas Gulf Coast*, Report of Investigations No. 149. Austin, TX: Bureau of Economic Geology, The University of Texas at Austin.
- Mace, R.E., and A.R. Dutton. 1994. “*Hydrogeologic Controls on Contaminant Transport in Weathered and Fractured Chalk.*” *Toxic Substances and the Hydrologic Sciences*, American Institute of Hydrology, p. 535-546.
- Mace, R.E. 1998. *Ground-Water Flow and Solute Transport in a Fractured Chalk Outcrop, North-Central Texas*. Ph.D. Dissertation, The University of Texas at Austin.
- Maloszewski, P. and A. Zuber. 1991. “Influence of Matrix Diffusion and Exchange Reactions on Radiocarbon Ages in Fissured Carbonate Aquifers.” In *Water Resources Research*, v. 27(8): 1937-1945.
- Maxey, G.B., and T.E. Eakin. 1949. *Groundwater in White River Valley, White Pine, Nye and Lincoln Counties, Nevada*, Water Resources Bulletin No. 8. Carson City, NV: State of Nevada, Office of the State Engineer.
- McAda, D.P., and P. Barroll. 2002. *Simulation of Ground-Water Flow in the Middle Rio Grande Basin Between Cochiti and San Acacia, New Mexico*, Water-Resources Investigations Report 02-4200, p. 81. Albuquerque, NM: U.S. Geological Survey.
- Moran, J.E. and T.P. Rose. 2003. “A Chlorine-36 Study of Regional Groundwater Flow and Vertical Transport in Southern Nevada.” In *Environmental Geology*, v. 43: 592-605.
- Morgan, M.G., and M. Henrion. 1990. *Uncertainty: A Guide to Dealing with Uncertainty in Quantitative Risk and Policy Analysis*. Cambridge UK: Cambridge University Press.
- Moysey, S., S.N. Davis, M. Zreda, and L.D. Cecil. 2003. “The Distribution of Meteoric $^{36}\text{Cl}/\text{Cl}$ in the United States: A Comparison of Models” In *Hydrogeology Journal* v. 11: 615-627.
- Mozley, P.S. and L.B. Goodwin. 1995. “Patterns of Cementation Along a Cenozoic Normal Fault: A Record of Paleoflow Orientations.” In *Geology*, v. 23(6): 539-542.
- NNSA/NSO, see U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office.
- NNSA/NV, see U.S. Department of Energy, National Nuclear Security Administration Nevada Operations Office.

- Neuman, S.P., and P.J. Wierenga. 2003. *A Comprehensive Strategy of Hydrogeologic Modeling and Uncertainty Analysis for Nuclear Facilities and Sites* (Tech. Rep. No. NUREG/CR-6806). Washington, DC: U.S. Nuclear Regulatory Commission.
- Oberlander, P.L. 2001. *Letter Report: Hydraulic Conductivity Profile with Depth for Monitor Wells ER-5-3, ER-5-3 #2, and ER-5-4*. Reno, NV: Desert Research Institute.
- Okabe, A., and B. Boots. 1992. *Spatial Tessellations: Concepts and Applications of Voronoi Diagrams*. Chichester, England: John Wiley & Sons, Inc.
- Parkhurst, D.L., and C.A.J. Appelo. 1999. *User's Guide to PHREEQC - A Computer Program for Speciation, Batch-Reaction, One-Dimensional Transport, and Inverse Geochemical Calculations*, Version 2. USGS Water Resources Investigation Report 99-4259, Denver, CO: U.S. Geological Survey.
- Perry, F.V., B.M. Crowe, G.A. Valentine, and L.M. Bowker. 1998. "Chapter 1: Overview", In *Volcanism Studies: Final Report for the Yucca Mountain Project*, LA-13478, pp 1-1 to 1-19. Los Alamos, NM: Los Alamos National Laboratory.
- Peters, R.R., E.A. Klavetter, I.J. Hall, S.C. Blair, P.R. Heller, and G.W. Gee. 1984. *Fracture and Matrix Hydrologic Characteristics of Tuffaceous Materials from Yucca Mountain, Nye County, Nevada*, SAND84-1471. Albuquerque, NM: Sandia National Laboratories Report.
- Phelps, G.A., L. Justet, B.C. Moring, and C.W. Roberts. 2005. *A Preliminary Investigation of the Structure of Southern Yucca Flat, Massachusetts Mountain, and CP Basin, Nevada Test Site, Nevada, Based on Geophysical Modeling*, Open-File Report (in press). U.S. Geological Survey.
- Plummer, L.N., E.C. Prestemon, and D.L. Parkurst. 1994. *An Interactive Code (NETPATH) for Modeling Net Geochemical Reactions Along a Flow Path*, Version 2.0, Water-Resources Investigations Report 94-4169. Denver, CO: U.S. Geological Survey.
- Plummer, M.A., F.M. Phillips, J. Farbryka-Martin, H.J. Turin, P.E. Wigand, and P. Sharma. 1997. "Chlorine-36 in Fossil Rat Urine: An Archive of Cosmogenic Nuclide Deposition During the Past 40,000 Years." In *Science*, v. 277(5325): 538-541.
- Plummer, L.N., L.M. Bexfield, S.K. Anderholm, W.E. Sandford, and E. Busenberg. 2004. *Geochemical characterization of ground-water flow in the Santa Fe Group aquifer system, Middle Rio Grande Basin, New Mexico*. U. S. Geological Survey Water-Resources Investigations Report 03-4131, 395 p.
- Poeter, E.P. and M.C. Hill. 1997. "Inverse Models: A Necessary Next Step in Ground-Water Modeling." In *Ground Water*, v. 35(N2): 250-260.

- Prudic, D.E. 1991. *Estimates of Hydraulic Conductivity from Aquifer-Test Analyses and Specific-Capacity Data, Gulf Coast Regional Aquifer Systems, South-Central United States*, Water-Resources Investigations Report 90-4121. Denver, CO: U.S. Geological Survey.
- Quade, J., T.E. Cerling, and J.R. Bowman. 1989. "Systematic Variations in the Carbon and Oxygen Isotopic Composition of Pedogenic Carbonate Along Elevation Transects in the Southern Great Basin, United States." In *Geological Society of America Bulletin*, v. 101: 464-475.
- Quade, J., and T.E. Cerlin. 1990. Stable Isotopic Evidence for a Pedogenic Origin of Carbonates in Trench 14 Near Yucca Mountain, Nevada." In *Science*, v. 250: 1549-1552.
- Quade, J., M.D. Mifflin, W.L. Pratt, W. McCoy, and L. Burckle. 1995. "Fossil Spring Deposits in the Southern Great Basin and Their Implications for Changes in Water-Table Levels Near Yucca Mountain, Nevada, During Quaternary Time." In *Geological Society of America Bulletin*, v. 107: 213-230.
- Rasmuson, A., and I. Neretnieks. 1986. "Radionuclide Transport in Fast Channels in Crystalline Rock." In *Water Resources Research*, v. 22: (8), 1247-1256. Washington DC: American Geophysical Union.
- Rawling, G.C., L.B. Goodwin, and J.L. Wilson. 2001. "Internal Architecture, Permeability Structure, and Hydrologic Significance of Contrasting Fault-Zone Types." In *Geology*, v. 29(1): 43-46.
- Rose, T.P., D.K. Smith, and J.K. Werner, Jr. 2000. "Lithologic, Mineralogic, and Petrographic Characterization of Alluvium from the U-1a 102C and 102D Drifts of the U-1a Tunnel Complex, Nevada Test Site." In D.K. Smith and G.F. Eaton (eds.), *Hydrologic Resources Management Program and Underground Test Area FY 1999 Progress Report*, UCRL-ID-139226, 77-110. Livermore, CA: Lawrence Livermore National Laboratory
- Rose, T.P., F.C. Benedict, J.M. Thomas, W.S. Sicke, R.L. Hershey, J.B. Paces, I.M. Farnham, and Z.E. Peterman. 2002. *Geochemical Data Analysis and Interpretation of the Pahute Mesa - Oasis Valley Groundwater Flow System, Nye County, Nevada*. Lawrence Livermore National Laboratory. Report attached to a memorandum to files by W. Drici (SNJV), 23 February 2004. Las Vegas, NV.
- Rousseau, J.P., E.M. Kwicklis, and D.C. Gillies. 1999. *Hydrogeology of the Unsaturated Zone, North Ramp Area of the Exploratory Studies Facility, Yucca Mountain, Nevada*, Water-Resources Investigations Report 98-4050. Denver, CO: U.S. Geological Survey.
- Russell, C.E., and T. Minor. 2002. *Reconnaissance Estimates of Recharge Based on an Elevation-dependent Chloride Mass-balance Approach*, DOE/NV/11508-37, Publication No. 45164. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Operations Office. Las Vegas, NV: Desert Research Institute.

- Russell, C.E. 2004. Personal Communication from C.E. Russell (Desert Research Institute) to N. DeNovio (SNJV) regarding Documentation of Data and Method for EDCMB Extended Analysis, 17 November. Las Vegas, NV
- Ryder, P.D., and A.F. Ardis. 1991. *Hydrology of the Texas Gulf Coast Aquifer Systems*, USGS Open-File Report 91-64. Denver, CO: U.S. Geological Survey.
- SNJV, see Stoller-Navarro Joint Venture.
- Saltelli, A. 2000. "What is Sensitivity Analysis?" In A. Saltelli, K. Chan, and E.M. Scott (Eds.), *Sensitivity Analysis* (pp. 3-13). Chichester, England: John Wiley & Sons, LTD.
- Schoff, S.L., and J.E. Moore. 1964. *Chemistry and Movement of Ground Water, Nevada Test Site, Trace Elements Investigations-838*. U.S. Geological Survey.
- Sheppard, S.C., K.V. Ticknor and W.G. Evenden. 1998. "Sorption of Inorganic ^{14}C on to Calcite, Montmorillonite and Soil." In *Applied Geochemistry*, v. 13: 43-47.
- Shott, G.J., L.E. Barker, S.E. Rawlison, M.J. Sully, and B.A. Moore. 1998. *Performance Assessment for the Area 5 Radioactive Waste Management Site at the Nevada Test Site, Nye County, Nevada*, Rev. 2.1, DOE/NV/11718-176, UC-721. Las Vegas, NV: Bechtel Nevada.
- Sigda, J.M., L.B. Goodwin, P.S. Mozley, and J.L. Wilson. 1999. "Permeability Alteration in Small-Displacement Faults in Poorly Lithified Sediments: Rio Grande Rift, Central New Mexico." In *Faults and Subsurface Fluid Flow in the Shallow Crust*, American Geophysical Union Monograph 113: 51-68. Washington, DC.
- Smith, G.I., I. Friedman, G. Veronda, and C.A. Johnson. 2002. "Stable Isotope Compositions of Waters in the Great Basin, United States 3. Comparison of Groundwaters with Modern Precipitation." In *Journal of Geophysical Research*, v. 107(D19): 16-1:16.
- Spaulding, W.G. 1985. *Vegetation and Climates of the Last 45,000 Years in the Vicinity of the Nevada Test Site, South-Central Nevada*, Professional Paper 1329: 83. U.S. Geological Survey.
- Spaulding, W.G., and L.J. Graumlich. 1986. "The Last Pluvial Climatic Episodes in the Deserts of Southwestern North America." In *Nature*, v. 320: 441-444.
- Stober, I. 1996. "Researchers Study Conductivity of Crystalline Rock in Proposed Radioactive Waste Site." In *Eos Trans. Am. Geophys. Union*, v. 77 (10): 93-94.
- Stoller-Navarro Joint Venture. 2004a. *Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Units 101 and 102: Central and Western Pahute Mesa, Nye County, Nevada*, Rev. 0, S-N/99205--002, Shaw/13052-204. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.

- Stoller-Navarro Joint Venture. 2004b. *Integrated Analysis Report for Single- and Multiple-Well Aquifer Testing at Frenchman Flat Well Cluster RNM-2s Nevada Test Site, Nevada*, Rev. 0, S-N/99205--029. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2004c. *Interpretation of Hydraulic Test and Multiple-Well Aquifer Test Data at Frenchman Flat Well Cluster ER-5-3*, S-N/99205--028. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2004d. *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada*, S-N/99205--032, Rev. 0. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2004e. *Transferability of Data Related to the Underground Test Area Project, Nevada Test Site, Nye County, Nevada*, S-N/99205--020. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2005a. *Phase II Contaminant Transport Parameters for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada*, S-N/99205--043. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2005b. *Analysis of Hydraulic Responses from the ER-6-1 Multiple-Well Aquifer Test, Yucca Flat FY 2004 Testing Program, Nevada Test Site, Nye County, Nevada*, Rev. 0, S-N/99205--051. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2005c. *Analysis of Well ER-6-2 Testing, Yucca Flat FY 2004 Testing Program, Nevada Test Site, Nye County, Nevada*, Rev. 0, S-N/99205--053. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2006. *Geochemical and Isotopic Evaluation of Groundwater Movement in Corrective Action Unit 97: Yucca Flat/Climax Mine, Nevada Test Site, Nevada*, Rev. 0, S-N/99205--070. Las Vegas, NV. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Las Vegas, NV.
- Stuiver, M., P.J. Reimer, E. Bard, J.W. Beck, G.S. Burr, K.A. Hughen, G. McCormac, and J. van der Plicht. 1998. "INTCAL98 Radiocarbon Age Calibration, 24000-0 cal BP." In *Radiocarbon*, V. 40(3): 1041-1083.
- Thomas, J.M., A.H. Welch, and M.D. Dettinger. 1996. *Geochemistry and Isotope Hydrology of Representative Aquifers in the Great Basin Region of Nevada, Utah and Adjacent States*, Professional Paper 1409-C: 100. U.S. Geological Survey.

- Thordarson, W. 1965. *Perched Ground Water in Zeolitized Bedded Tuff, Rainier Mesa and Vicinity, Nevada Test Site, Nevada*, Trace Elements Investigations-862. U.S. Geological Survey.
- Tiedman, C.R., J.R. Kernodle, and D.P. McAda. 1998. *Application of Nonlinear-Regression Methods to a Ground-Water Flow Model of the Albuquerque Basin*, USGS Water-Resources Investigations Report 98-4172. Denver, CO: U.S. Geological Survey.
- Tompson, A.F.B., C.J. Bruton, and G.A. Pawloski, eds. 1999. *Evaluation of the Hydrologic Source Term from Underground Nuclear Tests in Frenchman Flat at the Nevada Test Site: The CAMBRIC Test*, UCRL-ID-132300. Prepared for the U.S. Department of Energy, Nevada Operations Office. Livermore, CA: Lawrence Livermore National Laboratory.
- Tompson, A.F.B., S.F. Carle, R.M. Maxwell, G. Pawloski, and M. Zavarin. 2005. *Evaluation of the Non-Transient Hydrologic Source Term from the CAMBRIC Underground Nuclear Test in Frenchman Flat, Nevada Test Site*, UCRL-TR-217191. Prepared for the U.S. Department of Energy, National Nuclear Security Administration Nevada Site Office. Livermore, CA: Lawrence Livermore National Laboratory.
- Tyler, S.W., J.B. Chapman, S.H. Conrad, D.P. Hammermeister, D.O. Blout, J.J. Miller, M.J. Sully, and J.M. Ginanni. 1996. "Soil-Water Flux in the Southern Great Basin, United States: Temporal and Spatial Variations Over the Last 120,000 Years." In *Water Resources Research*, v. 32: 1481-1499.
- USGS, see U.S. Geological Survey.
- U.S. Department of Energy, National Nuclear Security Administration Nevada Operations Office. 2001. *Addendum to Revision 1 of the Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada*, DOE/NV--478-Rev. 1-ADD. Las Vegas, NV.
- U.S. Department of Energy, Nevada Operations Office. 1997. *Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada*, DOE/NV--477, UC-700. Las Vegas, NV.
- U.S. Department of Energy, Nevada Operations Office. 1999. *Corrective Action Investigation Plan for Corrective Action Unit 98: Frenchman Flat, Nevada Test Site, Nevada*, DOE/NV--478, Rev. 1. Las Vegas, NV.
- U.S. Department of Energy, Nevada Operations Office. 2000. *United States Nuclear Tests, July 1945 through September 1992*, DOE/NV--209, Rev. 15. Las Vegas, NV.
- U.S. Department of Energy, Office of Civilian Radioactive Waste Management Office of Repository Development. 2004. *Site-Scale Saturated Zone Transport*, MDL-NBS-HS-000010, Rev.1, ICN 00. Las Vegas, NV.

- U.S. Environmental Protection Agency. 1997. *Guiding Principles for Monte Carlo Analysis* (Tech. Rep. No. EPA/630/R-97-001). Washington, DC.
- U.S. Geological Survey. 1987. Digital Elevation Models: U.S. Geological Survey, *National Mapping Program Technical Instructions Data User's Guide 5*, 38p.
- U.S. Geological Survey. 1999. "National Elevation Dataset, NTS-E." As accessed at http://argis/mydata/NED_NLCD/ned.
- U.S. Geological Survey. 2004. "USGS/DOE Cooperative Studies in Nevada; Water-Use Wells, Nevada Test Site and Vicinity." As accessed at http://nevada.usgs.gov/doe_nv/wateruse/wu_map.htm on 23 July.
- U.S. Geological Survey. 2005. Digital Elevation Models 1:24,000 scale. As downloaded from <http://data.geocomm.com/catalog/US/61067/1785/group4-3.html>.
- Vose, D. 2000. *Risk Analysis: A Quantitative Guide*. Chichester, England: John Wiley & Sons, LTD.
- Walvoord, M.A., M.A. Plummer, F.M. Phillips, and A.V. Wolfsberg. 2002a. "Deep Arid System Hydrodynamics 1: Equilibrium States and Response Times in Thick Desert Vadose Zones." In *Water Resources Research*, v. 38: 15.
- Walvoord, M.A., F.M. Phillips, S.W. Tyler, and P.C. Hartsough. 2002b. "Deep Arid System Hydrodynamics 2: Application to Paleohydrologic Reconstruction Using Vadose-Zone Profiles from the Northern Mojave Desert." In *Water Resources Research*, v. 38: 12.
- Warren, J.E., and H.S. Price. 1961. "Flow I Heterogeneous Media" In *Soc. Petrol. Eng. J.*, v.1, p. 153-169.
- Warren, R.G., F.C. Benedict, Jr., T.P. Rose, D.K. Smith, S.J. Chipera, E.C. Kluk, and K.M. Raven. 2002. *Alluvial Layering and Distribution of Reactive Phases within Drill Holes ER-5-4 and UE-5n of Frenchman Flat*, LA-UR-02-6206. Los Alamos, NM: Los Alamos National Laboratory.
- Watermark Numerical Computing. 2004. *PEST Model-Independent Parameter Estimation Software*. Brisbane, Australia.
- White, A.F., H.C. Claassen, and L.V. Benson. 1980. *The Effect of Dissolution of Volcanic Glass on the Water Chemistry in a Tuffaceous Aquifer, Rainier Mesa, Nevada*, Water-Supply Paper 1535-Q: 34. U.S. Geological Survey.
- Williamson, A.K., and H.F. Grubb. 2001. *Ground-Water Flow in the Gulf Coast Aquifer Systems, South-Central United States*, Professional Paper 1416-F. Denver, CO: U.S. Geological Survey.

- Wilson, J.E., L.B. Goodwin, and C.J. Lewis. 2003. "Deformation Bands in Nonwelded Ignimbrites: Petrophysical Controls on Fault-Zone Deformation and Evidence of Preferential Fluid Flow." In *Geology*, v. 31(10): 837-840.
- Winograd, I.J., and W. Thordarson. 1975. *Hydrogeologic and Hydrochemical Framework, South-Central Great Basin, Nevada-California, with Special Reference to the Nevada Test Site*, Professional Paper 712-C. Denver, CO: U.S. Geological Survey.
- Winograd, I.J., and F.J. Pearson, Jr. 1976. "Major Carbon 14 Anomaly in a Regional Carbonate Aquifer: Possible Evidence for Megascala Channeling, South-Central Great Basin." In *Water Resources Research*, v. 12(6): 1125 - 1143.
- Wolfsberg, A., K. Campbell, and J. Fabryka-Martin. 2000. "Use of Chlorine-36 Data to Evaluate Fracture Flow and Transport Models at Yucca Mountain, Nevada," In *Dynamics of Fluids in Fractured Rock, Geophysical Monograph*, ed. by B. Faybishenko, P.A. Witherspoon, and S.M. Benson, v. 122: 349-362. Washington, DC: American Geophysical Union.
- Wolfsberg, A., L. Glascoe, G. Lu, A. Olson, P. Lichtner, M. McGraw, T. Cherry, and G. Roemer. 2002. *TYBO/BENHAM: Model Analysis of Groundwater Flow and Radionuclide Migration from Underground Nuclear Tests in Southwestern Pahute Mesa, Nevada*, LA-13977. Los Alamos, NM: Los Alamos National Laboratory.
- Zyvoloski, G.A., B.A. Robinson, Z.V. Dash, and L.L. Trease. 1997a. *Summary of Models and Methods for the FEHM Application - A Finite-Element Heat- and Mass-Transfer Code*, LA-13307-MS. Los Alamos, NM: Los Alamos National Laboratory.
- Zyvoloski, G.A., B.A. Robinson, Z.V. Dash, and I.L. Trease. 1997b. *User's Manual for the FEHM Application - A Finite-Element Heat- and Mass-Transfer Code*, LA-13306-M. Los Alamos, NM: Los Alamos National Laboratory.

Appendix A

Analysis of New Water-Level and Ground-Surface Elevation Measurements for Frenchman Flat Relative to the Phase II Frenchman Flat Hydrologic Data Document

A.1.0 ANALYSIS OF NEW WATER-LEVEL AND GROUND-SURFACE ELEVATION MEASUREMENTS FOR FRENCHMAN FLAT RELATIVE TO THE PHASE II FRENCHMAN FLAT HYDROLOGIC DATA DOCUMENT

On November 5-7, 2004, SNJV personnel measured the ground-surface elevation and the depth to water for several wells in the Frenchman Flat area. The purpose of this activity was to obtain highly accurate measurements of ground-surface elevation and current measurements of depth to water. In all cases, the ground-surface elevations measured during this activity differ from those used in the analysis of hydraulic heads reported in the Phase II Frenchman Flat hydrologic data document (SNJV, 2004).

The purpose of the analysis presented here was to calculate water-level elevations from the depths to water measured in November 2004, to compare the November 2004 water-level elevations to the historical data presented in the Frenchman Flat hydrologic data document, and to evaluate the difference between the steady-state heads reported in the Frenchman Flat hydrologic data document to those calculated using the ground-surface elevations measured in November 2004.

[Table A.1-1](#) summarizes the calculated water-level elevations for the depths to water measured in November 2004. This table includes the measured depth to water, the ground-surface elevation measured in November 2004, the water-level elevation calculated using the ground-surface elevation measured in November 2004 (in both feet and meters), the ground-surface elevation used in the Frenchman Flat hydrologic data document, the water-level elevation calculated using the ground-surface elevation from the Frenchman Flat hydrologic data document (in both feet and meters), and the difference between the water-level elevation calculated with the two ground-surface elevations. The largest difference in the calculated water-level elevations (5.51 m) is found for Well UE-5m. No steady-state head was determined for this well in the Frenchman Flat hydrologic data document. For all remaining wells, the difference ranges from 0.03 to 0.91 m. Note that this difference reflects the difference in the ground-surface elevation measured in November 2004 and the ground-surface elevation used in the Frenchman Flat hydrologic data document.

Table A.1-1
Calculated Water-Level Elevations from Depths to Water Measured in November 2004
 (Page 1 of 2)

Well Name	Nov. 2004 Depth to Water (ft)	Nov. 2004 Ground-Surface Elevation (ft)	WL Elevation Calculated with Nov. 2004 Ground-Surface Elevation (ft)	WL Elevation Calculated with Nov. 2004 Ground-Surface Elevation (m)	Ground-Surface Elevation in FF HDD (ft)	WL Elevation Calculated with Ground-Surface Elevation in FF HDD (ft)	WL Elevation Calculated with Ground-Surface Elevation in FF HDD (m)	Difference (Nov. 2004 minus FF HDD) in Calculated WL Elevation (m)
ER-5-3 (3 in. deep)	929.53	3,335.20	2,405.67	733.25	3,337.40	2,407.87	733.92	-0.67
ER-5-3 (3 in. shallow)	927.56	3,335.20	2,407.64	733.85	3,337.40	2,409.84	734.52	-0.67
ER-5-3 (main/composite)	927.57	3,335.20	2,407.63	733.84	3,337.40	2,409.83	734.52	-0.67
ER-5-3-2	949.59	3,335.23	2,385.64	727.14	3,337.40	2,387.81	727.80	-0.66
ER-5-3-3	927.44	3,335.24	2,407.80	733.90	3,337.40	2,409.96	734.56	-0.66
ER-5-4 (main/composite)	725.38	3,131.83	2,406.45	733.48	3,131.70	2,406.32	733.45	0.04
ER-5-4 (piezometer)	724.84	3,131.83	2,406.99	733.65	3,131.70	2,406.86	733.61	0.04
ER-5-4-2	656.29	3,131.95	2,475.72 ^a	754.60 ^a	3,131.70	2,475.47 ^a	754.52 ^a	0.08
RNM-1	789.11	3,135.38	2,398.68 ^a	731.12 ^a	3,135.17	2,398.4 ^a	731.05 ^a	0.06
RNM-2	722.01	3,128.71	2,406.70	733.56	3,128.80	2,406.79	733.59	-0.03
RNM-2s	723.37	3,130.58	2,407.21	733.72	3,130.45	2,407.08	733.68	0.04
UE-5m	540.67	3,481.93	2,941.26	896.50	3,500.00	2,959.33	902.00	-5.51
UE-5n	706.07	3,113.49	2,407.42	733.78	3,113.36	2,407.29	733.74	0.04

Table A.1-1
Calculated Water-Level Elevations from Depths to Water Measured in November 2004
 (Page 2 of 2)

Well Name	Nov. 2004 Depth to Water (ft)	Nov. 2004 Ground-Surface Elevation (ft)	WL Elevation Calculated with Nov. 2004 Ground-Surface Elevation (ft)	WL Elevation Calculated with Nov. 2004 Ground-Surface Elevation (m)	Ground-Surface Elevation in FF HDD (ft)	WL Elevation Calculated with Ground-Surface Elevation in FF HDD (ft)	WL Elevation Calculated with Ground-Surface Elevation in FF HDD (m)	Difference (Nov. 2004 minus FF HDD) in Calculated WL Elevation (m)
WW-4	839.25	3,604.43	2,765.23 ^a	842.84 ^a	3,601.50	2,762.30 ^a	841.95 ^a	0.89
WW-4A	839.26	3,604.41	2,765.15	842.82	3,606.00	2,766.74	843.30	-0.48
WW-5A	710.27	3,092.77	2,382.50	726.19	3,093.73	2,383.46	726.48	-0.29
WW-5C	715.38	3,081.63	2,366.25	721.23	3,083.09	2,367.71	721.68	-0.44

^aDepth to water corrected for borehole deviation.

The November 2004 water-level elevations calculated with the ground-surface elevations in the Frenchman Flat hydrologic data document were plotted with the historical data found in the hydrologic data report ([Figures A.1-1 through A.1-16](#)). In almost all cases, the November 2004 water level is consistent with the trend of the historical data and is consistent with the steady-state head reported in the Frenchman Flat hydrologic data document. The only well for which this is not true is Well WW-5C, where the November 2004 head is 1.09 m higher than the last historical head, which was assumed to represent contemporary steady-state conditions.

The steady-state heads reported in the Frenchman Flat hydrologic data document were recalculated using the ground-surface elevations measured in November 2004. [Table A.1-2](#) summarizes the steady-state heads reported in the Frenchman Flat hydrologic data document and those calculated with the November 2004 ground-surface elevations. The difference between the two steady-state heads ranges from 0.03 to 0.89 m. The average difference is 0.23 m for wells completed to the AA and 0.56 m for wells completed to the TM-WTA. The difference for the one well completed to the LCA is 0.07 m.

[Figures A.1-17 through A.1-21](#) show post plots of the historical and contemporary steady-state heads for the AA, TM-WTA (contemporary only), and LCA with the heads given in the Frenchman Flat hydrologic data document in blue and the heads calculated with the November 2004 ground-surface elevations in red. Based on these figures, the new ground-surface elevation data do not change any of the discussion found in the Frenchman Flat hydrologic data document regarding flow direction in these three aquifers.

Table A.1-2
Comparison of Steady-State Heads with Ground-Surface Elevations Measured in
November 2004 and Ground-Surface Elevations from the
Frenchman Flat Hydrologic Data Document
 (Page 1 of 2)

Well Name	Type Steady-State Head	Steady-State Head with Nov. 2004 GS Elevation (m)	Steady-State Head with FF HDD GS Elevation (m)	Difference (Nov. 2004 minus FF HDD) in Steady-State Head (m)	Primary HSU
Army-1 WW	Historical & contemporary	N/A	721.87	N/A	LCA
ER-5-3 (3 in. shallow)	Contemporary	733.90	734.57	-0.67	OAA
ER-5-3 (3 in. deep)	Contemporary	733.41	734.08	-0.67	TM-WTA
ER-5-3 (main/composite)	Contemporary	733.88	734.55	-0.67	OAA and TM-WTA
ER-5-3-2	N/A	N/A	N/A	N/A	LCA
ER-5-3-3	Contemporary	733.93	734.59	-0.66	OAA
ER-5-4 (piezometer)	Contemporary	733.53	733.49	0.04	AA
ER-5-4 (main/composite)	Contemporary	733.38	733.34	0.04	AA
ER-5-4-2	N/A	N/A	N/A	N/A	LTCU
RNM-1	Historical & contemporary	731.37	731.31	0.06	AA
RNM-2	Historical & contemporary	733.55	733.58	-0.03	AA
RNM-2s	Historical	734.64	734.60	0.04	AA
RNM-2s	Contemporary	733.68	733.64	0.04	AA
SM-23-1	Contemporary	N/A	725.01	N/A	LCA
TW-3	Historical & contemporary	N/A	725.52	N/A	LCA
TW-F	Historical & contemporary	N/A	730.51	N/A	LCA
UE-11a	Contemporary	733.86	733.79	0.07	TM-WTA
UE-11b	Historical & contemporary	N/A	743.71	N/A	TM-LVTA
UE-5 PW-1	Contemporary	N/A	733.79	N/A	AA

Table A.1-2
Comparison of Steady-State Heads with Ground-Surface Elevations Measured in
November 2004 and Ground-Surface Elevations from the
Frenchman Flat Hydrologic Data Document
 (Page 2 of 2)

Well Name	Type Steady-State Head	Steady-State Head with Nov. 2004 GS Elevation (m)	Steady-State Head with FF HDD GS Elevation (m)	Difference (Nov. 2004 minus FF HDD) in Steady-State Head (m)	Primary HSU
UE-5 PW-2	Contemporary	N/A	733.74	N/A	AA
UE-5 PW-3	Contemporary	N/A	733.75	N/A	TM-WTA
UE-5c WW	Historical	734.56	734.50	0.06	AA
UE-5c WW	Contemporary	733.35	733.28	0.07	AA
UE-5f	Historical	734.90	734.82	0.08	AA
UE-5j	N/A	N/A	N/A	N/A	AA
UE-5k	N/A	N/A	N/A	N/A	AA
UE-5m	N/A	N/A	N/A	N/A	AA
UE-5n	Contemporary	733.88	733.84	0.04	AA
WW-1	Historical	N/A	727.25	N/A	AA
WW-4	Historical	845.51	844.62	0.89	TM-WTA
WW-4A	Historical	844.10	844.59	-0.49	TM-WTA
WW-5A	Historical	730.61	730.91	-0.30	AA
WW-5A	Contemporary	725.88	726.17	-0.29	AA
WW-5B	Historical	N/A	734.68	N/A	AA
WW-5B	Contemporary	N/A	733.31	N/A	AA
WW-5C	Historical	729.23	729.68	-0.45	AA
WW-5C	Contemporary	720.15	720.59	-0.44	AA
WW-C	Historical	N/A	726.00	N/A	LCA
WW-C1	Historical & contemporary	727.69	727.62	0.07	LCA

Figure A.1-1
Well ER-5-3 (Shallow Piezometer) Water-Level History

Figure A.1-2
Well ER-5-3 (Deep Piezometer) Water-Level History

Figure A.1-3
Well ER-5-3 (Main/Composite) Water-Level History

Figure A.1-4
Well ER-5-3 #2 Water-Level History

Figure A.1-5
Well ER-5-3 #3 Water-Level History

Figure A.1-6
Well ER-5-4 (Piezometer) Water-Level History

Figure A.1-7
Well ER-5-4 (Main/Composite) Water-Level History

Figure A.1-8
Well ER-5-4 #2 Water-Level History

Figure A.1-9
Well RNM-1 Water-Level History

Figure A.1-10
Well RNM-2 Water-Level History

Figure A.1-11
Well RNM-2s Water-Level History

Figure A.1-12
Well UE-5n Water-Level History

Figure A.1-13
Well WW-4 Water-Level History

Figure A.1-14
Well WW-4A Water-Level History

Figure A.1-15
Well WW-5A Water-Level History

Figure A.1-16
Well WW-5C Water-Level History

Figure A.1-17
Post of Historical, Steady-State Heads in the AA

Figure A.1-18
Post of Contemporary, Steady-State Heads in the AA

Figure A.1-19
Post of Contemporary, Steady-State Heads in the TM-WTA

Figure A.1-20
Post of Historical, Steady-State Heads in the LCA

Figure A.1-21
Post of Contemporary, Steady-State Heads in the LCA

A.2.0 REFERENCES

Stoller-Navarro Joint Venture. 2004. *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada*, S-N/99205-032, Rev. 0. Prepared for the U.S. Department of Energy, National Nuclear Security Administration, Nevada Site Office. Las Vegas, NV.

Appendix B

Literature Review and Technical Basis for Permeability Depth Decay

B.1.0 LITERATURE REVIEW AND TECHNICAL BASIS FOR PERMEABILITY DEPTH DECAY

Since the 1960s, many authors have presented data and evaluations that identify and utilize a relationship of decreasing permeability or hydraulic conductivity with increasing depth. This reduction in permeability with depth is generally discussed in the context of porosity reduction (and correlated permeability reduction) with depth as a consequence of compaction and/or geochemical processes for unfractured formations, and as a consequence of fewer fractures present and fracture closure at higher *in situ* stresses for fractured formations. The literature listed in [Table B.1-1](#) demonstrates that permeability depth decay has been recognized by investigators in many geologic environments for decades and has been routinely employed in groundwater modeling studies. In addition, permeability depth decay has been incorporated as a standard capability in MODFLOW (the most widely distributed and used groundwater flow model in the world) code versions in recent years.

The most common types of permeability or hydraulic conductivity versus depth relationships use an exponential function of the form:

$$k = a 10^{-\lambda D} \quad (B-1)$$

or

$$k = b e^{-\gamma D} \quad (B-2)$$

where:

k = Permeability or hydraulic conductivity

a , b , λ , and γ = Constants (fitting parameters estimated generally from site-specific data)

D = Depth

Table B.1-1
Investigations Addressing Depth Dependence
of Permeability or Hydraulic Conductivity
 (Page 1 of 2)

Reference	Permeability or Hydraulic Conductivity Depth-Dependence Investigation	Inclusion of Permeability or Hydraulic Conductivity Depth-Dependence in Groundwater Modeling
Davis and Turk (1964)	X	
Davis and DeWiest (1966)	X	
Snow (1968)	X	
Carlsson and Olsson (1977)	X*	
Magara (1978)	X	
Gangi (1978)	X	
Freeze and Cherry (1979)	X	
Neglia (1979)	X*	
Rushton et al. (1982)	X	X
de Marsily (1986)	X*	
Rasmuson and Neretnieks (1986)	X	
Loucks et al. (1986)	X*	
Belitz and Bredehoeft (1988)	X	X
Williams and Narasimhan (1989)	X*	X
Rushton et al. (1989)	X	X
Lavenue et al. (1990)	X	X
Domenico and Schwartz (1990)	X	
Prudic (1991)	X*	
Whittemore et al. (1993)	X*	X
Kuiper (1994)	X*	X*
Mace and Dutton (1994)	X	
Lee et al. (1995)	X	
Stober (1996)	X	
DOE/NV (1997)	X*	X*
Haneberg et al. (1998)	X	
Mace (1998)	X*	

Table B.1-1
Investigations Addressing Depth Dependence
of Permeability or Hydraulic Conductivity
(Page 2 of 2)

Reference	Permeability or Hydraulic Conductivity Depth-Dependence Investigation	Inclusion of Permeability or Hydraulic Conductivity Depth-Dependence in Groundwater Modeling
Manning and Ingebritsen (1999)	X	
Ingebritsen and Manning (1999)	X	
Williamson and Grubb (2001)	X*	X*
Budd (2001)	X*	
Wilson et al. (2001)	X	X
Belcher et al. (2001)	X*	
Wilson (2003)	X	X
Casadel et al. (2003)	X*	X*
Anderman and Hill (2003)	X*	X*
Environment Agency (2003)	X*	X*
Belcher et al. (2004)	X*	X*

*Denotes investigations that use an exponential function to describe decreasing permeability or hydraulic conductivity with increasing depth.

Davis and Turk (1964) conducted an evaluation of well yields in crystalline rocks. They presented plots of log well yield versus log depth for several data groupings, including 2,336 wells in granite and schist in the eastern United States (depths to about 600 ft) and 239 wells in crystalline rocks of the Sierra Nevada, California (depths to about 350 ft); and a plot of log water-injection rate versus log depth for water-injection tests in granitic rocks of California (depths to about 300 ft). All of these plots showed an approximately linear relationship indicative of a logarithmic decrease in hydraulic conductivity with increasing depth. They discuss the dependence of hydraulic properties on the occurrence of joints and faults and the extent of weathering.

Davis and DeWiest (1966) present a book section titled “Permeability as a Function of Depth.” They discuss that average permeability of metamorphic and igneous plutonic rocks decreases rapidly with depth. They present a plot of decrease in well yield with depths (to 500 ft) for crystalline rocks in the

Statesville area of North Carolina that demonstrate an approximately exponential rate of decrease with depth. The decrease in permeability with depth was hypothesized to be the combined effect of the increasing weight of overlying rock and the tendency of surface disturbances to penetrate to limited depths; it is noted that fractures and faults tend to close at depth because of the weight of the overlying material.

Snow (1968) investigated the fractured metamorphic rocks of the front range of Colorado from pressure-test data from four dam sites and well-performance data from residential areas. A plot of the data with log permeability versus log depth is presented, along with the linear relationship that was fit to the relationship:

$$\log k = -8.9 - 1.67 \log d \quad (B-3)$$

where:

k = Permeability (ft²)

d = Depth (ft bgs) or overburden

The data showed relatively little scatter about the best-fit straight line. Permeabilities varied by three orders of magnitude over the depth range to 300 ft and were more dependent on depth than rock type or site location.

Hydraulic conductivity reduction as a function of depth in crystalline rocks was investigated by Carlsson and Olsson (1977) for various sites in Sweden. They used a relationship to estimate hydraulic conductivity based on water loss in packer-isolated intervals of drill holes. From a study of 55 drill holes at five sites, they determined functions for dependency of hydraulic conductivity with depth to about 75 m depth of the form:

$$K = 10^{-(0.04 D + 5.6)} \text{ (with coefficient of determination of 0.62)} \quad (B-4)$$

and

$$K = 10^{-(1.65 \log D + 4.5)} \text{ (with coefficient of determination of 0.65)} \quad (B-5)$$

where:

K = Hydraulic conductivity (m/s)

D = Depth below the rock surface (m)

Shale porosity-depth relationships for a variety of settings are discussed by Magara (1978), who cites Rubey and Hubbert (1959), who propose an exponential relationship between porosity and depth of the form:

$$\varphi = \varphi_o e^{-cZ} \quad (B-6)$$

where:

φ = Shale porosity at depth Z

φ_o = Shale porosity at the surface ($Z = 0$)

e = Base of the Napierian logarithms

c = Constant

Magara (1978) presented data for shales that show decreasing porosity and permeability with increasing depth.

Freeze and Cherry (1979; Chapter 4 on groundwater geology) suggest an interpretive framework for the distribution of permeability that is based on an understanding of the depositional environment. References are cited that show porosity of sandstones systematically decreasing with depth as a result of compaction and from cementation during groundwater circulation. A figure from Chilinger (1963) shows sand and sandstone are grouped according to grain-size categories (i.e., coarse- and very coarse-grained, coarse- and medium-grained, fine-grained, silty, and clayey) with log permeability versus porosity. The figure demonstrates well-defined trends of decreasing permeability with decreasing porosity for each grain-size category. In conjunction with the correlation of decreasing porosity with depth, the figure further illustrates that permeability decreases with depth.

Neglia (1979) conducted an evaluation of migration of water and hydrocarbons in sedimentary basins that found substantial decreases in porosity as burial depth increases and sediments are compacted. Data on a log-permeability versus linear-depth plot were presented, and linear lines representing an exponential relationship between permeability and depth bracketed the plotted data for the younger shales to depths of about 3,500 m.

The observation that hydraulic conductivity generally decreases with depth in fractured rocks has been discussed by numerous authors. This correlation is discussed by de Marsily (1986) as to the

result from the increase in mechanical stress with depth causing the fractures to close. Empirical relationships for crystalline rocks are reported from the literature as follows:

$$K(z) = (K_s) (10^{-z/m}) \quad (B-7)$$

$$K(z) = (K_s) (z^{-2.5}) \quad (B-8)$$

$$K(z) = (K_s) (z^{-1.6}) \quad (B-9)$$

where:

$K(z)$ = Hydraulic conductivity (m/s) at depth z (m bgs)

K_s = Hydraulic conductivity at ground surface

m = Depth (constant with a range of 100 to 500 m)

These relationships may apply under average conditions, but higher hydraulic conductivities may be encountered in a given borehole. Gangi (1978) provides theoretical arguments and relationships for permeability reduction of whole or fractured porous rock, with increasing confining pressure, that will occur with increasing depth. Decrease in permeability in the fractured rock is related to the effective modulus of the asperities, the distribution function of the asperity lengths, and effective pressure. Rasmuson and Neretnieks (1986) present a figure that shows a correlation of decreasing hydraulic conductivity with increasing depth (with total depth investigated to about 700 m) in crystalline rock of the Kamlunge site in Sweden. The data showed a relatively large amount of scatter about the approximated exponential curve through the data, on the log-hydraulic conductivity versus linear-depth plot. Lee et al. (1995) used fracture data from fractured andesite rock on the Taiwan Lan-Yu site in conjunction with hydromechanical coupling, geostatic stresses, and fracture geometry to demonstrate decreasing permeability with increasing depth. Empirical relations to estimate fracture closure with depth are presented, and graphical representations of permeability-depth curves based on assumptions for the underlying fracture model (i.e., single fracture set, three fracture sets, or random disc model). Stober (1996) presented data and a linear fit of log hydraulic conductivity versus log depth for gneiss rocks, demonstrating a decrease in hydraulic conductivity with depth. The data showed a relatively large amount of data scatter.

An investigation of the controls on porosity and permeability of the sedimentary formations along the Texas Gulf Coast is presented by Loucks et al. (1986), who provide both porosity-depth and core permeability-depth plots, based on several thousand data points, showing both porosity and

permeability decreasing with increasing depth. The data showed a trend but also a large scatter. A straight-line approximation on the log-permeability/linear-depth plot (representative of an exponential relationship) showed up to about four to five orders of magnitude decrease in permeability to depths of about 17,000 ft.

A quasi 3-D groundwater model of the Denver basin and adjacent Mid-Continent region was developed by Belitz and Bredehoeft (1988) that found a regional trend of east-to-west decreasing permeability with east-to-west increasing depth for the Dakota and basal sandstones. In the first modeling phase, which included the Dakota and basal Cretaceous sandstone layer, three different permeability-depth relationships (log-permeability versus depth, log-permeability versus log-depth, and log-permeability versus depth) were used. The best model results were obtained using the log log-permeability versus depth relationship:

$$\log \log-k \sim \text{depth} \quad (B-10)$$

Belitz and Bredehoeft (1988) originally proposed the log log-permeability versus depth relationship and noted that many researchers find a correlation between log-permeability and porosity and log-porosity and depth. Three functional relationships were illustrated graphically to depths of about 13,000 ft with permeability decreasing by about three orders of magnitude over the depth range. Also, depth-dependent hydraulic conductivity was incorporated into the groundwater model for the overlying Cretaceous shales using a log-permeability versus depth relationship. In the final modeling phase, which included the Dakota and basal sandstones overlying Cretaceous shales and underlying Paleozoic and Mesozoic sedimentary strata, the best match was obtained between observed and simulated potentiometric surfaces when the hydraulic conductivities of all lithologic units in the model were made dependent on depth. The same log log-permeability versus depth function was used for all lithologies, which resulted in a decrease in permeability of three orders of magnitude for depths up to about 10,000 ft.

Williams and Narasimhan (1989) developed a mathematical model to study the effects of hydrothermal circulation on heat flow along the San Andreas Fault and its effect on the state of stress on the fault for three cases (San Francisco peninsula, Cholame Hills, and San Gabriel Mountains/Mojave Desert) designed to investigate the effects of topography on the regional

groundwater flow system and heat flow. They chose an exponential relationship for permeability versus depth over 15 km of the form:

$$K = 10^{-(0.20 Z + 15)} \quad (B-11)$$

where:

k = Permeability (m^2)

Z = Depth (km)

Williams and Narasimhan (1989) included fault zone permeabilities of either $7.5 \times 10^{-17} \text{ m}^2$ or $4 \times 10^{-17} \text{ m}^2$ for the upper 5 km and decreasing exponentially with depth below 5 km. Simulation results for these cases that included the topographic effects on regional groundwater flow provided fair to reasonable matches to regional heat flow measurement profiles normal to the fault.

A calibrated regional-scale groundwater flow model for the Culebra dolomite at the Waste Isolation Pilot Plant site in southeastern New Mexico was developed by Lavenue et al. (1990). The depth of the Culebra dolomite, varying from about 8 to 420 m at well locations, exhibits an increasing trend from west to east across the modeled region. The initial kriged and the final calibrated transmissivity (or hydraulic conductivity) fields show a pronounced decrease in transmissivity (about seven orders of magnitude) from west to east. The reduction in transmissivity is the result of increased burial depth and reduction in fracturing that results when halite layers are removed by post-depositional dissolution from either above or below the Culebra dolomite layer. Regional dissolution is greatest in the west and decreases eastward as shown by an increase in the number and thickness of the halite beds.

Domenico and Schwartz (1990) discuss the physical and chemical changes that sediments undergo because of increases in overburden pressure and temperature, and chemical interaction between minerals and migrating porewater subsequent to the progressive burial of sediments in depositional environments. It was indicated that there is a reduction in porosity from compaction and pressure solution (grain dissolution at grain-to-grain contacts). There is also deformation from pressure solution accompanying basin loading and driven by the same stress that causes closer grain packing. A figure is presented that shows a relationship of porosity reduction as a function of increasing depth

for shales and sandstones, noting, “Whatever the mechanism, the reduction of porosity causes a rather large reduction in permeability.”

An evaluation of hydraulic conductivities from 1,500 aquifer-test analyses and more than 5,000 specific-capacity data is presented by Prudic (1991) from wells in sediments of the Gulf Coast region in the south-central United States. Additionally, the hydraulic conductivity of an unconsolidated sediment should decrease with depth because of sediment compaction from increasing overburden pressure. The depths of the middle of the screened test intervals varied down to depths below 3,000 ft. Analyses were performed to evaluate correlation between geographic areas, geologic layer, and depth to screen midpoint, and functional relationships were developed exhibiting decreasing hydraulic conductivity with depth for 31 of 42 area-layer combinations. The functional relation was of the form:

$$K = C / 10^{\lambda D} \quad (B-12)$$

where:

K = Hydraulic conductivity
 C and λ = Constants
 D = Depth

The sediments of the Gulf Coast region in the south-central United States were also studied by Kuiper (1994), who found that the hydraulic conductivity of the coarse-grained sediments decreased with depth due to decreasing porosity and increased due to decreased viscosity resulting from higher temperatures, with a net effect of decreasing hydraulic conductivity with depth. A functional relationship was provided that represented decreasing sand hydraulic conductivity with depth based on the data from Loucks et al. (1986) of the form:

$$K = C_1 10^{-0.8dd} \quad (B-13)$$

where:

C_1 = Constant
 dd = depth (km)

Kuiper (1994) stated that the hydraulic conductivity of the fine-grained sediments or clays tended to decrease with increasing depth as a consequence of compaction and provided a clay hydraulic conductivity-depth relationship:

$$K = C_2 10^{(-1.167dd + 0.0833dd^2)} \quad (B-14)$$

where C_2 is a constant.

Kuiper provided plots of the data (which showed a large amount of scatter about the trend line) and the functional relationships for the coarse- and fine-grained sediments, with hydraulic conductivity variations of about five and three orders of magnitude, respectively, for depths up to about 17,000 ft. A multiple-regression methodology was used to calibrate several groundwater flow models of the regional Gulf Coast aquifer system.

A groundwater investigation of the Austin chalk of North-Central Texas was conducted by Mace and Dutton (1994), who found that groundwater flow is controlled by fractures that decline in intensity with depth. They presented a data plot of log-hydraulic conductivity versus linear-depth that showed a corresponding decline in hydraulic conductivity with depth (data to about 380 m depth). Mace (1998) presented additional data and evaluations from the same study area to a depth of about 150 m for weathered and unweathered chalk. A data plot provided a log hydraulic conductivity versus linear-depth fitted with the exponential functional relation:

$$K = 10^{-4.35 \log(d/3.28)} \quad (B-15)$$

where:

K = Hydraulic conductivity (m/day)

d = Depth (m)

Hydraulic conductivity data varied over about eight orders of magnitude in both the Mace and Dutton (1994) and Mace (1998) investigations. The larger hydraulic conductivities at shallower depths were attributed to unloading and weathering, resulting in increased fracturing.

A calibrated regional groundwater flow model of the NTS and vicinity was developed by DOE/NV (1997), in which site-specific data were used to develop relationships between hydraulic conductivity and depth for each of the three rock types that form the major aquifers (alluvial, volcanic, and

carbonate). A linear trend in the logarithm of hydraulic conductivity, with increased depth, was expressed as:

$$K_{depth} = K_h 10^{-\lambda d} \quad (B-16)$$

where:

K_{depth} = Horizontal hydraulic conductivity at a specified depth

K_h = Horizontal hydraulic conductivity at land surface

λ = Hydraulic conductivity decay coefficient

d = Depth from land surface

This hydraulic conductivity depth-decay functional relation is the same type as that previously adopted by Prudic (1991) and Kuiper (1994). The site-specific hydraulic conductivity versus depth data showed a large amount of scatter about the functional line used to describe the relationship. Depth-dependent conductivity relationships were used for the entire model.

Haneberg et al. (1998) conducted laboratory measurements on core samples from a site in Albuquerque, New Mexico, to investigate the impact of effective stress on hydraulic conductivity. The investigation found that “the hydraulic conductivities of consolidated, undisturbed, and typically fine-grained sediments, decreased two to three orders of magnitude between vertical effective stresses of about 50 and 1,000 kPa.” A series of plots were shown with a linear relationship of log-hydraulic conductivity versus log-vertical effective stress for data from nine samples. Those data demonstrated the relationship of decreasing hydraulic conductivity that would be expected from increasing depth or effective stress.

A permeability-depth relationship for the continental crust based on geothermal and metamorphic data was evaluated by Manning and Ingebritsen (1999) and Ingebritsen and Manning (1999). Based on a variety of geologic settings in the United States and worldwide with depths to about 30 km, a relationship was developed of decaying permeability with depth of the form:

$$\log k = -3.2 \log z - 14 \quad (B-17)$$

where:

k = Permeability (m^2)

z = Depth (km)

The constant in the equation provides k at a depth of 1 km. Fault zones were noted but not addressed in the analysis, which may locally yield higher permeability values. The above relationship was presented based on geothermal and metamorphic data and also data from direct hydraulic measurements from two investigations (sedimentary facies in the Uinta basin in Utah and the Pierre Shale) that showed decreasing permeability with increasing depth. The direct hydraulic measurement permeability data plotted, as log-permeability versus linear-depth, showed about seven orders of magnitude variation over 4.5 km depth for the Uinta basin and about 4.5 orders of magnitude variation over 3.2 km depth for the Pierre Shale. The direct hydraulic measurement permeability data were fairly scattered. It was found that “the crustal-scale k - z relation from geothermal and metamorphic data was at least as coherent as typical k - z data relations determined from direct hydraulic measurements of the upper crust.”

Williamson and Grubb (2001) studied the sediments of the Gulf Coast region in the south-central United States, and used the equations of Kuiper (1994) for hydraulic conductivity as a function of depth for the coarse-grained sediments expressed as:

$$K = 30 \ 10^{-0.000243D} \quad (B-18)$$

and for the clays expressed as:

$$K = C \ 10^{-0.000356D + 0.0000254D^{-2}} \quad (B-19)$$

where:

D = Depth (ft)

C = Constant

For the coarse-grained sediments, Williamson and Grubb (2001) presented a plot of log hydraulic conductivity versus linear-depth with a straight-line approximation representing the hydraulic conductivity relation. The data showed a large amount of scatter about the best-fit line. Therefore, a regional groundwater flow model was developed consisting of 10 aquifers and 5 regional confining units.

An investigation of the relationship between permeability and depth (0 to 470 m) in the Cenozoic platform of west-central Florida was conducted by Budd (2001). Permeability-depth relationships were developed based on more than 12,000 minipermeameter measurements on 1,210 m of core from

limestones in Florida. It was found that the dolostones and low-permeability limestones did not exhibit permeability with depth trends, but the high-permeability limestones (high-mud packstones, low-mud packstones, very low-mud packstones, and grainstones) exhibited a systematic reduction in their mean and maximum permeabilities with increasing burial depth. For the high-permeability limestones, permeability decreased by about one order of magnitude over the 470 m depth. Petrographic observations on grainstones revealed mechanical and chemical (i.e., pressure solution) compaction features. There was no evidence of burial cementation. Permeability reduction with depth was interpreted to result from observed compaction phenomena including grain repacking and reorientation, grain breakage, grain interpenetrations, and grain-to-grain pressure solution. Budd (2001) developed least-squared exponential regressions between permeability and depth for the high-permeability limestones being investigated:

$$k = 145 e^{(-z/220)} \text{ for silty packstone} \quad (B-20)$$

$$k = 151 e^{(-z/270)} \text{ for high-mud packstone} \quad (B-21)$$

$$k = 295 e^{(-z/236)} \text{ for low-mud packstone} \quad (B-22)$$

$$k = 427 e^{(-z/236)} \text{ for very low-mud packstone} \quad (B-23)$$

where:

k = Permeability (millidarcy)

z = Depth (m)

The R^2 values ranged from 22 to 31 percent. The data showed decreasing permeability with depth but also a relatively large amount of scatter.

Geothermal convection of seawater in carbonate platforms and geochemical reactions related to dolomitization were investigated by Wilson et al. (2001), who adopted exponential relationships for porosity decreasing with depth of the form:

$$\phi = 0.4173 \exp (-z/2498) \text{ for medium- and coarse-grained sediments} \quad (B-24)$$

and

$$\phi = 0.4 \exp (-z/125) + 0.4 \exp (-z/6500) \text{ for fine-grained sediments} \quad (B-25)$$

where ϕ is porosity and z is depth below sea level (m). Then, the calculated permeability was used as a function of porosity using the relation:

$$k = a\phi^b \quad (B-26)$$

where:

k = Permeability in millidarcies in the direction of maximum permeability (assumed to be horizontal)
 a and b = Fit parameters for coarse-, medium-, and fine-grained sediments

Calculated permeabilities ranged seven orders of magnitude. Wilson et al. (2001) chose a horizontal-to-vertical permeability ratio of 1,000 and presented log-permeability versus linear-depth plots for the coarse-, medium-, and fine-grained sediments that were used in modeling studies of groundwater flow and geothermal circulation. In later modeling studies of geothermal convection in continental shelves, Wilson (2003) adopted similar permeability-depth relations for coarse-, medium-, and fine-grained carbonates and added relations for coarse- and fine-grained clastics.

Belcher et al. (2001) prepared hydraulic property estimates for use in developing a transient groundwater flow model of the Death Valley regional flow system. The relationship between hydraulic conductivity and depth for 10 HGUs was examined and a log-hydraulic conductivity versus linear-depth plot of data for the units in the Death Valley region was presented. It was noted that there is a trend as well as relatively high data scatter. The hydraulic-conductivity data spanned nine orders of magnitude over about 2,500 m depth. The linear regression analysis obtained the greatest correlation to depth with the $\log_{10}$ transform of the hydraulic-conductivity estimates (coefficient of determination is 0.296). The hydraulic conductivity depth-decay functional relationship is the same form as that adopted by Prudic (1991), Kuiper (1994), and DOE/NV (1997).

A spatially distributed runoff model was used by Casadel et al. (2003) in a study to predict landslides. The model assumed an exponential decay of hydraulic conductivity with depth for the colluvium and the underlying rock expressed as:

$$K = K_1 e^{-fza} \quad (B-27)$$

$$K = K_2 e^{-gzb} \quad (B-28)$$

where:

K = Hydraulic conductivity

K_1, K_2, f , and g = Parameters varied during model calibration

za = Depth in the colluvium measured from ground surface

zb = Depth in the rock measured from the soil-rock interface

Anderman and Hill (2003) published an update to the USGS groundwater flow model MODFLOW-2000, which included the addition of the capability to handle hydraulic-conductivity depth-dependence. The update discusses that hydraulic conductivity can decline systematically with depth and cites a field example in Whittemore et al. (1993). Whittemore et al. (1993) used a log-log vertical hydraulic-conductivity versus depth relationship to represent decreasing hydraulic conductivity, with depth for the aquitard in the regional-scale groundwater flow model of the Dakota aquifer system. Anderman and Hill (2003) include the hydraulic conductivity decrease with depth in MODFLOW-2000 using the function:

$$K_{Depth} = K_{Surface} 10^{-\lambda d} \quad (B-29)$$

where:

K_{Depth} = Hydraulic conductivity at depth

$K_{Surface}$ = Hydraulic conductivity projected to a reference surface

λ = Depth-dependence coefficient

d = Depth below the reference surface

The depth-dependence coefficient can be defined separately for different HGUs or for different regions in each HGU. The hydraulic conductivity depth-decay functional relation is the same form as adopted by Prudic (1991), Kuiper (1994), and DOE/NV (1997).

An enhancement to MODFLOW-96 that includes a variation of hydraulic conductivity with depth option (code called MODFLOW-VKD) was published by the Environment Agency (2003). The agency noted that hydraulic conductivity is a function of depth for many aquifers. The revised code package introduced two new layer types to represent aquifers where hydraulic conductivity reduces with depth within the layer. The conceptualization for varying hydraulic conductivity with depth is based on Rushton et al. (1982 and 1989), where hydraulic conductivity decreases continuously until reaching a reference level and is then constant below the reference level. This hydraulic conductivity

variation with depth was developed from an investigation in a chalk aquifer in the United Kingdom and was incorporated into their mathematical model of the groundwater flow system.

The USGS has developed a transient groundwater flow model (with 16 layers) of the Death Valley region that includes the NTS and vicinity (Belcher et al., 2004). Belcher et al. (2004) discussed that hydraulic conductivity is expected to decrease with depth as “geostatic load increases, compressing favorably oriented fractures, faults, and sedimentary units.” Depth decay of hydraulic conductivity is included in the model through use of the HUF package in MODFLOW-2000 (Anderman and Hill, 2003). The hydraulic conductivity depth-decay functional relation is the same form as adopted by Prudic (1991), Kuiper (1994), and DOE/NV (1997). Initial parameter estimates for hydraulic-conductivity decay with depth were based on the previous estimates in IT (1996) (these initial estimates were also used in the model in DOE/NV, 1997). Belcher et al. (2004) found that depth decay was important in all volcanic-rock and basin-fill units, and was of somewhat less importance in the carbonate-rock aquifer. It was also found that including depth decay in selected confining units improved the model. Belcher et al. (2004) provide comparison of the initial and calibrated depth-decay parameter for 10 HGUs, and a plot showing hydraulic conductivity relative to surface-hydraulic conductivity versus depth (to 3 km) for the calibrated depth-decay parameters for the 10 HGUs.

A regional-scale groundwater flow model was developed for the Pahute Mesa CAU. The area of interest for the Pahute Mesa CAU is defined by the potentially affected portion of the regional groundwater flow system, which includes a region stretching from the northern side of Pahute Mesa south and southwestward to Oasis Valley. The hydraulic conductivity data with plots of log hydraulic conductivity versus depth for selected HSUs are presented in SNJV (2004), which found that there is considerable scatter in the data at any particular depth. The model calibration approaches for parameterizing the HSUs for Pahute Mesa included no depth decay, no anisotropy; depth decay and anisotropy in selected units; and depth decay and anisotropy in all units. The no-depth-decay, no-anisotropy case was rejected as reasonable because of permeabilities and flow paths judged to be unrealistic. The calibration approaches with depth decay resulted in successful calibrations judged to be representative of the flow system based on matching head and flow calibration targets and examination of flow paths. The hydraulic conductivity depth-decay functional relation is the same form as that adopted by Prudic (1991), Kuiper (1994), DOE/NV (1997), and Belcher (2004).

The plots of measured hydraulic conductivities versus depth that are reported in the literature tend to show a relatively large amount of scatter, and thus a large amount of spread about any best-fit line, representing the functional relationship of decreasing permeability or hydraulic conductivity versus increasing depth (e.g., Rasmuson and Neretnieks, 1986; Loucks et al., 1986; Lavenue et al., 1990; Prudic, 1991; Kuiper, 1994; Mace and Dutton, 1994; Stober, 1996; DOE/NV, 1997; Mace, 1998; Williamson and Grubb, 2001; Budd, 2001; Belcher et al., 2001 and 2004). However, utilizing these depth-dependent relationships is a useful approach to assist in parameterizing groundwater flow models because often there are limited data available to characterize the full depth and lateral extent of all HSUs in large regional groundwater flow models. Initial depth-decay relationships based on site-specific data are valuable starting points for model parameterization that can then be modified during model calibration.

The technical basis for permeability to decrease with depth is reasonable (e.g., decreasing porosity with increased burial depth and overburden pressure due to compaction, pressure solution, and/or cementation; reduction in fracture frequency and aperture with depth in fractured formations) and is well supported by published data studies from many different geologic environments. The above literature review illustrates there is a solid foundation of scientific works that document reduction in permeability, with depth as a reasonable approximation to represent hydraulic properties, in regional-scale groundwater flow models.

B.2.0 REFERENCES

- Anderman, E.R., and M.C. Hill. 2003. *MODFLOW-2000, The U.S. Geological Survey Modular Ground-Water Model – Three Additions to the Hydrogeologic-Unit Flow (HUF) Package: Alternative Storage for the Uppermost Active Cells (SYTP Parameter Type), Flows in Hydrogeologic Units, and the Hydraulic-Conductivity Depth-Dependence (KDEP) Capability*, USGS Open-File Report 03-347. Denver, CO: U.S. Geological Survey.
- Belcher, W.R., P.E. Elliot, and A.L. Geldon. 2001. *Hydraulic-Property Estimates for Use With a Transient Ground-Water Flow Model for the Death Valley Regional Ground-Water Flow System, Nevada and California*, USGS Water-Resources Investigations Report 2001-4210, 28 p. U.S. Geological Survey.
- Belcher, W.R., J.B. Blainey, F.A. D’Agnese, C.C. Faunt, M.C. Hill, R.J. Laczniaik, G.M. O’Brien, C.J. Potter, H.M. Putnam, C.A. San Juan, and D.S. Sweetkind. 2004. *Death Valley Regional Model Ground-Water Flow System, Nevada and California - Hydrogeologic Framework and Transient Ground-Water Flow Model*, Scientific Investigations Report 2004-5205. U.S. Geological Survey.
- Belitz, K., and J.D. Bredehoeft. 1988. “Hydrodynamics of the Denver Basin: Explanation of Subnormal Fluid Pressures.” In *American Association of Petroleum Geologists. Bulletin v. 72*: 1334-1359.
- Budd, D.A. 2001. “Permeability Loss with Depth in the Cenozoic Carbonate Platform of West-Central Florida.” In *American Association of Petroleum Geologists. Bulletin v. 85*: (7): 1253-1272.
- Carlsson, A., and T. Olsson. 1977. “Hydraulic Properties of Swedish Crystalline Rocks: Hydraulic Conductivity and its Relation to Depth.” In *Bulletin of the Geological Institutions of the University of Uppsala*, 7, 71-84. Uppsala, Sweden.
- Casadel, M., W.E. Dietrich, and N.L. Miller. 2003. “Testing a Model for Predicting the Timing and Location of Shallow Landslide Initiation in Soil-Mantled Landscapes.” In *Earth Surf. Process. Landforms*, v. 28: 925-950. New York, NY: John Wiley & Sons, Ltd.
- Chilinger, G.V. 1963. “Relationship Between Porosity, Permeability, and Grain-Size Distribution of Sands and Sandstones.” *Proc. Intern. Sedimentol. Congr., Amsterdam, Antwerp*.
- DOE/NV, see U.S. Department of Energy, Nevada Operations Office.

- Davis, S.N., and R.J.M. DeWiest. 1966. *Hydrogeology*. New York, NY. John Wiley, 463 p.
- Davis, S.N., and L.J. Turk. 1964. Optimum Depth of Wells in Crystalline Rocks. In *Ground Water*, 2 (2), p. 6-11. National Water Well Association.
- de Marsily, G. 1986. *Quantitative Hydrogeology, Groundwater Hydrology for Engineers*. Orlando, FL: Academic Press, Inc.
- Domenico, P.A., and F.W. Schwartz. 1990. *Physical and Chemical Hydrogeology*. New York, NY: John Wiley & Sons.
- Environment Agency. 2003. *Enhancements to MODFLOW, User Guide for MODFLOW-VKD – A Modified Version of MODFLOW-96 to Include Variations in Hydraulic Conductivity with Depth*, Water Management Consultants Ltd. Prepared for National Groundwater & Contaminated Land Centre, UKEA, Project NC/00/23.
- Freeze, R.A., and J.A. Cherry. 1979. *Groundwater*. Englewood Cliffs, NJ: Prentice-Hall, Inc.
- Gangi, A.F. 1978. "Variation of Whole and Fractured Porous Rock Permeability with Confining Pressure." In *Int. J. Rock Mech. Min. Sci. Geomech. Abstr.*, v. 15: 249-257. Great Britain: Pergamon Press.
- Haneberg, W.C., P. Gomez, A. Gibson, and B. Allred. 1998. "Preliminary Measurements of Stress-Dependent Hydraulic Conductivity of Santa Fe Group Aquifer System Sediments from the 98th St Core Hole, Albuquerque, New Mexico, 14-20 February." In *New Mexico Geology*.
- Ingebritsen, S.E., and C.E. Manning. 1999. "Geological Implications of a Permeability-Depth Curve for the Continental Crust." In *Geology*, v. 27(12): 1107-1110.
- IT Corporation. 1996. Hydrologic Parameter Data Documentation Package (Phase I Data Analysis Documentation, Volume IV), ITLV/10972-181. Las Vegas, NV.
- Kuiper, L.K. 1994. *Nonlinear-Regression Flow Model of the Gulf Coast Aquifer Systems in the South-Central United States*, Water-Resources Investigations Report 93-4020. Denver, CO: U.S. Geological Survey.
- Lavenue, A.M., T.L. Cauffman, and J.F. Pickens. 1990. *Ground-Water Flow Modeling of the Culebra Dolomite, Volume I Model Calibration*, SAND88-7002. Albuquerque, NM: Sandia National Laboratories.
- Lee, C-H., B-W. Deng, and J-L. Chang. 1995. "A Continuum Approach for Estimating Permeability in Naturally Fractured Rocks." In *Engineering Geology*, v. 39: 71-85. New York, NY: Elsevier Publishing Co.

- Loucks, R.G., M.M. Dodge, and W.E. Galloway. 1986. *Controls on Porosity and Permeability of Hydrocarbon Reservoirs in Lower Tertiary Sandstones along the Texas Gulf Coast*, Report of Investigations No. 149. Austin, TX: Bureau of Economic Geology, The University of Texas at Austin.
- Mace, R.E. 1998. *Ground-Water Flow and Solute Transport in a Fractured Chalk Outcrop, North-Central Texas*. Ph.D. Dissertation, The University of Texas at Austin.
- Mace, R.E., and A.R. Dutton. 1994. "Hydrogeologic Controls on Contaminant Transport in Weathered and Fractured Chalk." *Toxic Substances and the Hydrologic Sciences*, American Institute of Hydrology, p. 535-546.
- Magara, K. 1978. *Compaction and Fluid Migration, Practical Petroleum Geology*. Amsterdam: Elsevier Scientific Publishing Company.
- Manning, C.E., and S.E. Ingebritsen. 1999. "Permeability of the Continental Crust: Implications of Geothermal Data and Metamorphic Systems." In *Reviews of Geophysics*, v. 37: 127-150. Washington DC: American Geophysical Union.
- Neglia, S. 1979. "Migration of Fluids in Sedimentary Basins." In *American Association of Petroleum Geologists. Bulletin*, v. 63: 573-597.
- Prudic, D.E. 1991. *Estimates of Hydraulic Conductivity from Aquifer-Test Analyses and Specific-Capacity Data, Gulf Coast Regional Aquifer Systems, South-Central United States*, Water-Resources Investigations Report 90-4121. Denver, CO: U.S. Geological Survey.
- Rasmuson, A., and I. Neretnieks. 1986. "Radionuclide Transport in Fast Channels in Crystalline Rock." In *Water Resources Research*, v. 22: (8), 1247-1256. Washington DC: American Geophysical Union.
- Rubey, W.W., and M.K. Hubbert. 1959. "Role of Fluid Pressure in Mechanics of Overthrust Faulting." In *Geol. Soc. Am. Bulletin*, 70, 167-206.
- Rushton, K.R., E.J. Smith, and L.M. Tomlinson. 1982. "An Improved Understanding of Flow in a Limestone Aquifer Using Field Evidence and Mathematical Models." In *Journal of the Institution of Water Engineers and Scientists*, v. 36 (5): 369-397.
- Rushton, K.R., B.J. Connorton, and L.M. Tomlinson. 1989. "Estimation of the Groundwater Resources of the Berkshire Downs Supported by Mathematical Modeling." In *Quarterly Journal of Engineering Geology*, v. 22 (4): 329-341.
- Snow, D.T. 1968. "Hydraulic Conductivity of Fractured Metamorphic Rocks of the Front Range and Implications to the Rocky Mountain Arsenal." In *Quarterly of the Colorado School of Mines*, v. 63 (1): 201-244.

- Stober, I. 1996. "Researchers Study Conductivity of Crystalline Rock in Proposed Radioactive Waste Site." In *Eos Trans. Am. Geophys. Union*, v. 77 (10): 93-94.
- Stoller-Navarro Joint Venture. 2004. *Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Units 101 and 102: Central and Western Pahute Mesa, Nye County, Nevada*, Rev. 0, S-N 199205--002; Shaw/13052-204. February. Prepared for the U.S. Department of Energy, Nevada Operations Office. Las Vegas, NV.
- U.S. Department of Energy, Nevada Operations Office. 1997. *Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada*, DOE/NV--477, UC-700. Las Vegas, NV.
- Whittemore, D.O., P.A. Macfarlane, J.H. Doveton, J.J. Butler, Jr., T-M. Chu, R. Bassler, M. Smith, J. Mitchell, and A. Wade. 1993. *The Dakota Aquifer Program Annual Report, FY92*. Kansas Geological Survey.
- Williams, C.F., and T.N. Narasimhan. 1989. "Hydrogeologic Constraints on Heat Flow Along the San Andreas Fault: A Testing of Hypotheses." In *Earth Planet. Sci. Lett.*, v. 92: 131-143. Amsterdam: Elsevier Science Publishers B.V.
- Williamson, A.K., and H.F. Grubb. 2001 *Ground-Water Flow in the Gulf Coast Aquifer Systems, South-Central United States*, Professional Paper 1416-F. Denver, CO: U.S. Geological Survey.
- Wilson, A.M. 2003. "The Occurrence and Chemical Implications of Geothermal Convection of Seawater in Continental Shelves." In *Geophysical Research Letters*, v. 30 (21): 2127, doi:10.1029/2003GL018499. Washington, DC: American Geophysical Union.
- Wilson, A.M., W. Sanford, F. Whitaker, and P. Smart. 2001. "Spatial Patterns of Diagenesis during Geothermal Circulation in Carbonate Platforms." In *American Journal of Science*, v. 301: 727-752.

Appendix C

Perturbation Sensitivity Analysis Plots

C.1.0 INTRODUCTION

This appendix contains perturbation sensitivity analysis figures for the Frenchman Flat area. Included are figures for the BASE and CPBA HFMs with boundary heads and fluxes originating from two regional models of the NTS area. The perturbation sensitivity for the BASE model faults in the Z direction and the BLFA and DETA HFMs are also included in this section.

C.2.0 DATA PRESENTATION

The data are presented in individual figures. These figures present the change in some model metric as a function of a change in one model parameter at a time. The model metrics in each file are as follows:

- Average head – change in calibration target head as defined in [Section 5.0](#).
- HSU head for AA, OAA, and BLFA - change in water-table elevation for nodes in a particular HSU.
- Lateral boundary flux west, south, east, and north – change in respective model edge flow objective function.
- Boundary flow goodness of fit – change in objective function for all boundary flows (PHI FLUX)
- Total objective function – change in PHI, overall model goodness of fit
- Observation well goodness of fit – change in observation well component of model goodness of fit (PHI WELL)

The HSU intrinsic permeability at land surface (k_0) model parameters are referred to as the HSU abbreviation. Depth-decay parameters for each HSU are referred to by the type of HSU, the index number, and the HSU name abbreviation. For example, aahsu01aa is an alluvium layer with HSU index number 1, which is also the AA. Fault permeability multipliers are referred to by number.

Vertical anisotropy is referred to as “vani” for the group of most HSUs: vani1 refers to the vertical anisotropy for the LCA, LCA3, and BLFA; vani2 refers to the vertical anisotropy for the LTCU; and vani3 refers to the vertical anisotropy for the VCU.

C.3.0 ACCESS TO DATA

The perturbation sensitivity analysis plots can be found on the accompanying compact disc in pdf format. The data files are listed in the following sections.

C.3.1 BASE HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.2 BASE HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model, Fault Permeability Multiplier in Z Direction Only

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.3 BASE HFM with Calibrated USGS with Redistribution Recharge and Boundary Heads, DVRFS Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf

- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.4 CPBA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.5 CPBA HFM with Calibrated USGS with Redistribution Recharge and Boundary Heads, DVRFS Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.6 DETA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

C.3.7 BLFA HFM with USGS with Redistribution Recharge and Boundary Heads, UGTA Regional Model

- Average Head.pdf
- Lateral Boundary – West Face Model Flow.pdf
- Lateral Boundary – South Face Model Flow.pdf
- Lateral Boundary – East Face Model Flow.pdf
- Lateral Boundary – North Face Model Flow.pdf
- AA Water Table.pdf
- OAA Water Table.pdf
- BLFA Water Table.pdf
- Boundary Flow Goodness of Fit.pdf
- Total Objective Function.pdf
- Observation Well Goodness of Fit.pdf

Appendix D

Fault Locations

Table D.1-1
Fault Names and Locations for Some Faults

Fault Name or Location	Fault Number(s) in Flow Model
Cane Spring fault	3
Faults associated with the CP Hogback	12,14, 15
Rock Valley fault system	21, 33, 34, 57-60, 62, 68, 73
Southern terminations of faults in Yucca Flat in the northern part of the Frenchman Flat CAU model domain	2, 7, 22-25, 27-29
Short faults near the northern testing area	35, 45, 50-51, 54-56
Short faults near the central testing area	37-38, 40-45, 48-56
Faults associated with Ranger Mountains, in southeast of model area	61, 63-67, 69-72
Detachment fault	36
Topgallant fault zone	10, 11
Faults associated with Yucca fault zone	4-6, 8, 9
Faults associated with Half-Pint Range	22-25, 27-29

Appendix E

Saturated Media Hydraulic Properties

E.1.0 SATURATED MEDIA HYDRAULIC PROPERTIES

Values used for the hydraulic properties of HSUs in the simulation of groundwater flow and transport should be consistent with available information to provide confidence in the simulation results. Specifically, hydraulic conductivity is a basic parameter for groundwater flow modeling that determines the volumetric flow rate and is sufficient for steady-state modeling. Representative hydraulic conductivities for the formations to be modeled, at the scale over which the model is discretized, are integral to producing defensible model predictions. The groundwater flow models incorporate depth decay of hydraulic conductivity, and this is also analyzed and characterized. Storage properties of the formations are also of interest as a basic hydraulic parameter needed for transient simulations of groundwater flow. There are many uncertainties in the determination of representative parameter values, which will be discussed in this section, and an uncertainty analysis accompanies the use of the available data.

The assessment and analysis of hydraulic parameter data presented in this section serve several project needs for Frenchman Flat CAU Phase II modeling. The analysis in this appendix produced statistical estimates for the distribution of hydraulic conductivity values, depth decay of hydraulic conductivity, and storage parameter values for the major HGUs in the Frenchman Flat CAU. The analysis was conducted using all of the regional data (NTS Investigation Area) for individual regional HGUs, which also apply to the Frenchman Flat HFM model (BN, 2005). The Frenchman Flat CAU-specific data do not provide data for all relevant HGUs or sufficient data to determine statistics for those HGUs for which there were data. The data were aggregated by HGU to provide sufficient data for each category for statistical analysis. Some HGUs are directly equivalent to HSUs while others generally represent a variety of HSUs of similar character. The basis for transferability of hydraulic parameter data is discussed. The discussion also addresses the relationship of hydraulic properties to the scale of measurement, the spatial variation of hydraulic properties, and the variation with depth. Information on anisotropy of hydraulic conductivity and variation due to temperature is presented.

This analysis differs from the analysis previously provided in the Frenchman Flat Phase II hydrologic data document (SNJV, 2004a) in several ways. The most significant change is aggregation by HGU rather than HSU, and associated with that change was the individual evaluation of each test interval for assignment to the appropriate HGU based on information in the database for lithology and stratigraphy. In previous analyses, test intervals were assigned to HSUs based on the regional HFM model, but it has been determined that this approach resulted in unintended mixing of results for different types of rocks due to the coarseness of the regional HFM model. Other changes include evaluation of the relationship of hydraulic conductivity with depth for all HGUs. Some additional data also have been added.

E.1.1 Objectives

The specific objectives for the hydraulic parameter assessment include the following:

- Compile and evaluate available hydraulic parameter data.
- Determine appropriate ranges and distributions for hydraulic conductivity, hydraulic conductivity depth decay, and specific storage for HGUs.

E.1.2 Data Types and Prioritization

Transmissivity, the product of the hydraulic conductivity and aquifer thickness, is the only hydraulic parameter needed to simulate groundwater flow under steady-state conditions. Conceptually, transmissivity is a property that varies at the scale of HSUs, which define units of hydrostratigraphic character and have consistent hydraulic properties. Transmissivity, as determined by nodal hydraulic conductivity values and node spacing, is a primary calibration parameter in the groundwater flow model. Storage is an additional parameter required for calibration of transient simulations. The HSU thickness is determined from the HFM. To modify transmissivity during calibration, the hydraulic conductivity must be varied, because the thickness of the HSU is fixed by the HFM. As a result, the calibration parameter for the flow model is hydraulic conductivity. Hydraulic conductivity is the variable that is analyzed for variability and uncertainty affecting transmissivity. Hydraulic conductivity is either obtained directly from analytic or numeric analysis of the hydraulic response measurements (drawdown or recovery data), or calculated by dividing the transmissivity obtained from analysis by the test interval thickness.

Storage information is secondary, because the transport model will be based on steady-state groundwater flow conditions. However, this information is needed to perform transient runs, which may be used for model verification.

E.1.3 Data Compilation and Evaluation

The SNJV maintains a working groundwater database that contains a hydraulic properties table with information on hydraulic testing and analysis results for a large area of southern Nevada. This database was originally developed to support regional flow modeling for the UGTA program and contains the transmissivity and/or hydraulic conductivity values compiled for interpretations of aquifer-, packer-, and slug-tests, laboratory permeability, and grain-size analyses. The database includes supporting information on the test such as well information for each test, test parameters, stratigraphy and lithology for the borehole, information on the analysis, and the data source. Storage parameter data were also compiled for MWATs, which are generally accepted as the only reliable basis for determining storage values. However, storage parameter data are less available because MWATs are not commonly performed.

The database used for this analysis was updated with additional data from recent Yucca Flat/Climax Mine Phase I data collection activities not included in the previous analyses for the Frenchman Flat Phase II hydrologic data document (SNJV, 2004a).

E.1.3.1 Data Sources

Hydraulic property data were obtained from published and unpublished sources. Published data were obtained from reports of the following organizations: DRI, IT Corporation, LANL, LLNL, Sandia National Laboratories, Shaw Environmental, Inc., SNJV, USGS, and a variety of other organizations. Publications providing hydraulic parameter values may or may not include the raw and/or reduced drawdown and/or recovery data and specifics for the interpretation. An effort was made to acquire full documentation for each test, and the extent of documentation acquired is reflected in the data documentation evaluation flag (DDE_F) qualifiers, as discussed in [Section E.1.3.3](#). Specific references for data sources are listed in the database. Evaluation of the actual drawdown or recovery data available was important for assessing the adequacy of the interpretation and for assigning the data confidence identifiers. Unpublished data and interpretations were obtained from the DRI and

USGS, and from the files of the Environmental Restoration Contractor as part of the Environmental Restoration Project. Unpublished test interpretations are only preliminary interpretations. Copies of all data sources, including unpublished data and interpretations for entries in the database, are filed in SNJV Central Files.

E.1.3.2 Supporting Data

Data necessary for the hydraulic parameter data analysis include site information, well construction, hydrostratigraphic information, and hydrologic test information and include the following data types:

Site Information

- Reporting name
- Site location
- Land-surface elevation

Test Interval Information

- Top and bottom elevations of the tested interval
- Stratigraphic unit for the test interval
- HSU designation

Hydraulic Test Information

- Test start date
- Pumping rate
- Pumping duration
- Data availability

Test Interpretation Information

- Method of analysis
- Organization performing the analysis
- Hydraulic conductivity
- Transmissivity
- Storage coefficient
- Data documentation evaluation flag
- Data quality evaluation flag

Most of these categories are self-explanatory except for the data quality identifiers, which are described later in this section.

E.1.3.3 Data Quality Assurance

Data qualification for the hydraulic parameters analysis was based on the requirements described in Section 4.0 of Frenchman Flat Phase II hydrologic data document (SNJV, 2004a) and were applied as described below.

Data Documentation Evaluation

Documentation of the data for the primary parameters of concern (i.e., hydraulic conductivity and storage) was evaluated, and values were assigned to the Flag DDE_F according to UGTA data documentation requirements in Section 4.0 of SNJV (2004a).

Data Quality Evaluation

Data quality relative to the use of the hydraulic parameter analysis results is a function of the representativeness of the derived parameter value statistics. It was decided that the most representative statistics would be determined using all data rather than only the highest-quality data. In cases where there were many data values for an HSU/HGU, the statistical analysis is expected to preclude the undue influence of any particular data value. In cases where there were few HSU/HGU data, there is an insufficient basis to identify questionable data. As had been recognized in the UGTA regional model report (DOE/NV, 1997), many historical test results actually may be high quality but cannot be objectively identified as such from the available records. Consequently, data quality evaluation flags were not assigned as they had been in the regional model report. Data quality evaluation procedures have been re-evaluated in the data transferability technical basis document (SNJV, 2004b), and revised procedures will be considered for future analyses. For this data analysis, data quality evaluation was handled according to ranking the suitability of the data for use in CAU modeling.

E.1.3.4 Data Transferability

Data transferability pertains to the use of hydraulic property data from the NTS Investigation Area to characterize the Frenchman Flat HSUs. When categorized at the HGU level, formations in Frenchman Flat are directly equivalent to formations at the regional scale.

All data from within the NTS Investigation Area were analyzed with respect to regional HGUs and the scale of the test. Data transfer of hydraulic property data from outside of the Frenchman Flat CAU was handled as a function of correlating the tested formation for each analysis to a breakdown of HGUs. The assignment for each analysis result was based on cross-referencing regional HSUs/HGUs with Frenchman Flat HSUs/HGUs, as well as evaluation of the stratigraphic and lithologic information specific for each well. The scale of the regional HFM, which does not perfectly honor the specific geology of each well, as well as situations where tested intervals included multiple HSUs/HGUs of different character, required individual interpretation of HSU/HGU applicability.

E.1.4 Hydraulic Parameters

Two hydraulic parameters are characterized in this section: hydraulic conductivity and specific storage. Hydraulic conductivity is the primary parameter of interest and is sufficient for steady-state modeling. The storage properties of the rock units are characterized in the form of specific storage, which would be used for transient modeling.

Hydraulic conductivity is a property that varies by location within a rock unit, and is necessarily averaged over a volume of rock in the process of testing. The value measured for hydraulic conductivity depends on the particular volume of rock tested (i.e., well location and radius of influence). Different test methods and specifications can produce different results at a location as a function of the scale of the test (i.e., the specific volume of rock tested). Characterization of hydraulic conductivity of an HSU can take several forms, and the appropriate form of the characterization depends on the intended use of the data. Conducting many tests at different locations or of different volumes within a particular rock unit (defined by HSUs for this analysis) produces a range of hydraulic conductivity values.

The data can be considered as location specific, pertaining to a specified volume of the rock unit for each test value. This characterizes the variability as a spatial property. However, when the subject rock unit (HSU across the area of interest) is very large, only a small percentage of the total volume of the subject unit is typically characterized, leaving much of the unit uncharacterized, even when many tests are conducted. An alternate type of characterization is determination of a parametric probability model for the test parameter values, which can then be used to define a probability density

function (PDF) for the data. The distribution fitted to the data provides information that can be used to constrain the fitting of generalized values for hydraulic conductivity to rock volumes that do not correspond to the original test volumes. Comparison of the parameter values used for HSUs in the calibrated model to the PDFs for the HSUs can provide confidence in the appropriateness of the calibrated value. This latter type of characterization is the primary approach used in this analysis.

In addition to the variability of the hydraulic conductivity values across the HSU, there are a variety of uncertainties inherent in the determination of the values that are embedded in the data. Uncertainty is related to the suitability of the test method, test measurement accuracy, appropriateness of the analysis method for the test, and assumptions made about the test and tested interval. The uncertainty in the analyses results is difficult to quantify and is not readily separable from the variability described by the parametric probability model. The total uncertainty resulting from these factors may be substantial and potentially exaggerate the apparent variability. This is evident in cases where several different analyses of the same test, or analyses of different tests on the same well, produced very different results.

E.1.4.1 Scales of Test Data and Applicability

The scale of the test is recognized as an important factor for the representativeness of the test result for use in modeling (Rovey and Cherkauer, 1995). For the purpose of modeling groundwater flow on a large scale, parameter values representative of groundwater flow at larger scales are more appropriate than values representative of smaller scales of measurement. The larger-scale data better reflect the overall hydraulic character of formations, which are modeled as consistent at the HSU scale. Additionally in fractured rocks, the scales of the data are important to capture the effect of fracturing on the overall properties. The data were analyzed in separate groups for the three distinct scales of tests as follows:

- Pumping-scale tests are considered to provide the most appropriate information for use in large-scale modeling, because they provide results representative of the greatest aquifer volume and are more likely to reflect high hydraulic conductivity structure in tested formations.
- Slug-test-scale tests (including packer tests) provide less representative information, testing smaller volumes of formations, both the vertical interval and radius, and are more affected by local variability and effects related to drilling, construction, and test methods.

- Laboratory-scale tests may provide data somewhat applicable to unfractured and/or granular media formations, but are not appropriate for characterizing large-scale formation properties for formations that are dominated by fractures. These data can provide hydraulic conductivity information on matrix properties of fractured formations.

The pumping-scale tests are conducted *in situ* on short to long test intervals (typically in the range of 30 to 305 m or more), moving relatively large volumes of water to induce pressure and possibly dewatering responses in the test formation over relatively long periods of time (typically 12 hours to 90 days). These methods test much larger volumes of rock extending relatively large distances from the borehole. The response in the pumping well may be substantially affected by near-borehole conditions reflecting drilling damage, but responses measured in remote observation wells provide data unaffected by local formation damage. Tests with observation wells can also provide directional property data. Depending on the length of the test, the test may reveal different aspects of the formation response that are related to time or distance from the well.

The slug- and packer-test scale tests are conducted *in situ* on fairly short test intervals (typically in the range of about 2 to 15 m) using small volumes of water (from several to hundreds of gallons) to induce pressure pulses that equilibrate in a relatively short period (ranging from seconds to days). These methods test a relatively small volume of rock in the immediate area of the borehole. The results may be substantially influenced by near-borehole conditions that reflect drilling damage to the formation and effects from the well completion. The small volumetric stress on the rock unit associated with these methods do not produce good results in high-conductivity media.

The laboratory-scale tests comprise measurements made on small samples (typically of about 1,000 to 2,000 cubic centimeters) removed from the natural environment by various means and placed into a test apparatus in the laboratory. Samples may be chosen to be representative for the purpose, but the criteria used to determine representativeness are not always documented and are not necessarily consistent between different test sets. Rock/core samples tested are intact and exclude features (such as fractures) that are not preserved in handling. Measurements are then made that generally represent the hydraulic conductivity of the intact matrix. Unconsolidated materials may be reasonably preserved in their natural state or repacked for testing. In some cases, the hydraulic conductivity for unconsolidated samples may be calculated from a grain-size analysis.

E.1.4.2 Test Analyses and Associated Uncertainties

Larger-scale tests average hydraulic responses across larger volumes of rock, but inhomogeneities that may be present within the larger test interval introduce uncertainties in the analysis of the test. The uncertainties are a function of undefined conditions or variability in the tested formation in the test interval that are not accounted for in the test analysis, and the interaction of multiple conditions resulting in a response that does not strictly conform to one or another analysis model. Usually, insufficiently detailed characterization data are collected during testing to determine the variation in response occurring in the test interval. Also, a particular weakness of much of the data is that it is based on analyses of single well tests, which have additional uncertainty due to the effects of production combined with the formation response. Analysis methods are generally based on relatively simple models reflecting one presumably dominant type of response. In many cases, it is difficult to determine which of several potentially appropriate conceptual models for the response is correct, much less separate out the parts of the overall response that may be attributed to miscellaneous conditions. Consequently, analysis results often reflect somewhat of an average of different additive responses.

E.1.4.3 Handling of Multiple Test Results for One Well

There are several situations that produce multiple test analysis results for one well. First, is the case in which there are multiple analyses of a single test. The multiple analyses can include analyses by different analysts, different analysis models applied to a test, or variations of assumptions made for a particular test analysis. Second, is the case with multiple, independent tests conducted in a well, usually with different test parameters. The third case is when there are multiple test intervals for a well resulting from changes in the well completion, temporary restrictions of the test interval for multiple tests, or different interpretations of the test interval based on various types of information.

The objective of this analysis was to identify independent measurements of hydraulic conductivity and to statistically characterize the variability of hydraulic conductivity within the context of similar formation character (lithology, stratigraphy, hydraulic character) that could be translated to the HFM. Where there were multiple results for the same well and the same transmissive interval, multiple hydraulic conductivity values were averaged. This included multiple tests and multiple analysis models, assuming these represented testing and analysis uncertainty. However, variations in analysis

assumptions that identified different tested intervals were treated as independent results because the particular volume of formation tested, embodied in the analysis, was interpreted to be different.

E.1.5 Analysis of Hydraulic Conductivity Data

Analysis of the hydraulic conductivity data included separate evaluations of pumping-scale, slug-test-scale, and laboratory-scale data to determine statistics for the hydraulic conductivity at each scale. A more detailed review of the pumping-scale data is presented, because these data are most relevant for use in large-scale modeling. The slug-test-scale analysis results may be viewed as supporting the pumping-scale results but are not as relevant due to the smaller scale of the tests. The laboratory-scale data analysis is relevant to matrix properties of the formation, which may be useful for some purposes but does not appropriately address the large-scale properties of the formation for flow modeling.

The database for hydraulic property information includes data for a large area encompassing the NTS, and the NTS Investigation Area (see [Figure E.1-1](#)). This area encompassed the UGTA regional model (DOE/NV, 1997) and was used to determine hydraulic property values for that model. The geology within this area is relatively consistent with the NTS geology, and data for this area are considered to be generally relevant to formation hydraulic properties across the NTS and to Frenchman Flat in particular. Analysis was conducted for data from this area based on generalized classification of the tested formations by HGU. The spatial distribution of the hydraulic conductivity data is discussed first to show the extent to which the available data represent the Frenchman Flat CAU; specifically, within the NTS Investigation Area.

The analysis provides statistics — including the mean, number of independent data points, and the data range — for each HGU at each test scale. For each CAU, an HGU-specific dataset having more than a few data points was evaluated for conformance to a log-normal distribution ([Section E.1.5.2](#)). The 95-percent confidence interval was calculated for datasets for which a distribution was determined.

Figure E.1-1
NTS Investigation Area Locations of Hydraulic Conductivity Data

E.1.5.1 Methodology

This subsection summarizes the approach and methods used during this reassessment of the hydraulic parameter dataset for the Frenchman Flat CAU. The following approach was used to define ranges for hydraulic conductivity and storage parameters for the HGUs in the NTS Investigation Area:

- Hydraulic parameter data have been compiled from published and unpublished sources into a database. Information associated with each entry includes the location, test date, type of test, test parameters, tested interval, method of analysis, borehole lithology and stratigraphy, HSU(s) corresponding to the tested interval, analysis results, and a source reference for the information.
- The analysis was conducted on hydraulic conductivity and specific storage parameter values. Hydraulic conductivity is essentially a unit value for formation transmissivity, and specific storage is a unit value for storativity. All hydraulic conductivity values are associated with a defined interval of the formation tested. Some test analysis methods return transmissivity values, which are scaled to hydraulic conductivity using the tested interval thickness, and others return hydraulic conductivity values based on the input interval thickness. In all cases, hydraulic conductivity values are based on interpretations of the tested interval thickness. The situation is similar for specific storage versus storativity. These normalized parameters allow evaluation of variations with depth (assigned to the midpoint of the tested interval) and location (assigned to the well location).
- The hydraulic parameter dataset included information for wells within a large area encompassing the NTS. Data analysis was conducted on the scale of the NTS Investigation Area, which encompasses the NTS. The NTS Investigation Area dataset was first filtered from the database.
- The NTS Investigation Area dataset was separated into three datasets based on the scale of the test from which the parameter values were derived. The three scales were pumping-scale, slug-test-scale, and laboratory-scale.
- The data at each scale were then separated into HGU-specific datasets for the transmissive interval, which are more generalized than HSUs and apply at both analysis scales. The HGUs correspond closely to HSUs for formations of distinct character (e.g., AA, MGCU, UCCU, LCA/UCA/LCA3, and LCCU) and generally characterize the multiplicity of volcanic HSUs within the categories of VAs, LFAs, and TCUs.
- A nominal hydraulic conductivity was identified for each data entry using (in priority order) the average hydraulic conductivity, horizontal hydraulic conductivity, fracture hydraulic conductivity value, or transmissivity divided by the specified transmissive interval thickness. Where a transmissive interval thickness was not specified, the total length between the top and

bottom of the transmissive interval was used. The midpoint depth of the test interval for each test result was also determined from the transmissive interval data.

- In fractured rocks, three types of hydraulic conductivities can be defined: bulk hydraulic conductivity, fracture hydraulic conductivity, and matrix hydraulic conductivity. A generalized measurement over a vertical interval is termed the bulk hydraulic conductivity. In cases where the formations are fractured, the hydraulic conductivity associated with the fracture system and associated with the matrix may be determined separately, depending upon the tests measurements and analysis methods. In general, the bulk hydraulic conductivity will be similar to the fracture-associated hydraulic conductivity, and matrix hydraulic conductivity will be significantly lower.
- In some cases, more than one test result or interpretation of a test for a test interval is available. Before further analysis, multiple results for a single test interval were arithmetically averaged. Results were not averaged for a well when different test intervals were specified or when different transmissive thicknesses were specified for the same test interval. The hydraulic conductivity data were then transformed to log base 10 values for analysis based on the assumption of log-normal distribution, to which hydraulic conductivity has been shown to conform.
- The resulting sets of unique location and depth-specific hydraulic conductivity values were then statistically analyzed to determine the range, mean, SD, the correspondence to a log-normal probability distribution, and the 95-percent confidence interval where there were sufficient data. The results are presented in tables and displayed graphically.
- For datasets containing a large number of unique hydraulic conductivity values, the relationship of log base 10 hydraulic conductivity to transmissive interval midpoint depth as evaluated by performing a regression, calculating 1 and 2 SDs for the K_0 (hydraulic conductivity surface intercept) and Lambda (regression slope).
- The dataset for each HGU at the pumping-scale was screened for storage parameter values: general specific storage and fracture specific storage. Where storativity was reported, the data were normalized to specific storage by dividing storativity values by the transmissive interval thickness (as previously specified). The mean and SD for these data were calculated on an HGU basis. Probability distributions were calculated for specific storage and are displayed graphically by HGU.

E.1.5.2 Kolmogorov-Smirnov Test for Log Normality

Typically hydraulic conductivity variability has been found to be distributed according to a log-normal distribution. To the extent possible, it was desirable to determine whether the hydraulic conductivity values for each HSU conformed to such a distribution. Where there were sufficient data, the datasets for each HSU, at each scale, were tested for conformance with a log-normal distribution.

A Kolmogorov-Smirnov (K-S) test (Benjamin and Cornell, 1970) was applied at the 5-percent level of significance to the empirical cumulative distribution function (ECDF) of the measured data. The test for log ECDF normality and an estimate of the range of uncertainty in the log-normal parameters is determined from the K-S statistic, D . The D is a measure of the maximum difference in cumulative probability between the data ECDF and the theoretical (log-normal) cumulative density function (CDF). The difference is calculated for each measured datum (i); therefore, the data frequency is defined as i/n , where n is the total number of independent data points. This differs from a normal probability plot, which is calculated using a frequency of $i/(n+1)$. A critical K-S statistic, D^* , is then defined based on the number of data samples and the significance level (0.05). If the observed difference between the ECDF and CDF, D , is greater than the critical difference between distributions, D^* , the null hypothesis (i.e., that the measured and theoretical distributions are statistically equal) is rejected.

For the figures illustrating the results of the K-S test, D is used to construct upper and lower bounding curves that define the smallest region of uncertainty for which the null hypothesis is not rejected. Similarly, D^* could be used to define the complete region of uncertainty for the measured data when the theoretical distribution and significance levels are specified. Within the K-S bounds, it is possible to observe the range of parameters describing the log-normal CDF. If the SD is held fixed (i.e., holding the slope constant), the mean can be shifted by some amount and remain within the bounds. Similarly, if the mean is held fixed but the slope of the CDF is varied, the SD could vary some amount. The two ranges cannot be varied simultaneously to their limits, or the model would no longer remain within the K-S bounds.

E.1.5.3 Spatial Distribution of Data

Figure E.1-1 shows the locations of wells and boreholes for which hydraulic conductivity (or permeability) data are available in the database. The locations are identified with three different symbols corresponding to the three scales of test information. In some cases, more than one scale of test is available at a single location. The data are not uniformly distributed throughout the NTS Investigation Area. Rather, the data are clustered in areas on the NTS where underground nuclear testing was performed, major construction facilities were located, or where Environmental Restoration drilling and testing activities have taken place. Off the NTS, data are generally located in

areas of human settlement and activity or in areas of interest for resources. Note the cluster of data on the southwestern border of the NTS associated with the YMP.

Figure E.1-2 shows the distribution of data within the Frenchman Flat CAU and the HGU to which the data pertain. As shown on the map, a relatively small number of locations with hydraulic property data are available for the Frenchman Flat CAU.

E.1.6 Analysis Results

This section provides summary tables and graphs of the results of the analyses. The following section provides detail on the individual HGU-specific analyses for the NTS Investigation Area data. Where available data supported testing for log-normal distributions, a graph of the K-S test result is shown.

E.1.7 Hydraulic Conductivity Analysis

Table E.1-1 presents a summary of the analyses of hydraulic conductivity data within the NTS Investigation Area. This table shows the results of the test by scale for each HGU (where data are available). The extent to which statistics could be developed for each dataset was dependent upon the number of unique data values available. The ultimate aim was to determine the type of distribution for the property and define the distribution with confidence; however, this requires a substantial number of values in the dataset. The column “Count” in these tables indicates the number of unique data values for each analysis. The column “Number of Entries” indicates the number of database entries for the category that were aggregated to determine unique data values. As can be seen in Table E.1-1, extensive datasets were available for many of the HGUs at the different test scales. The HGU basis for analysis resulted in a substantial increase in the size of the category datasets compared to the HSU analysis in SNJV (2004a). The HGU assignments, based on multiple criteria, allowed assignment of many more database entries as compared to HSUs assigned according to the HFM. A major factor in this improvement is that many transmissive intervals span multiple HSUs and could not be categorized within the HSU framework.

To indicate that the result of the K-S test (Section E.1.5.2) did not reject the log-normality hypotheses, “Yes” is listed in the column “Accept Log-Normal Hypothesis.” The log-normal hypothesis was not rejected for any datasets at the “Pumping-Scale” and “Slug-Test-Scale.” The

Figure E.1-2
Frenchman Flat Hydraulic Property Data Locations

Table E.1-1
Summary of NTS Investigation Area K Analysis

HGU	Mean	Standard Deviation	Count	Minimum	Maximum	K-S Critical Statistic D*	K-S Statistic D at 95 Percent	Accept Log-Normal Hypothesis	95-Percent Confidence Interval Bounds		Number of Entries
	log 10 K (m/day)			log 10 K (m/day)					Lower	Upper	
									log 10 K (m/day)		
Pumping-Scale											
AA	0.45	0.93	51	-1.47	2.54	0.06	0.19	Yes	-1.37	2.27	107
VA	-0.12	1.29	142	-4.80	3.41	0.07	0.11	Yes	-2.66	2.42	238
LFA	-0.26	0.95	29	-2.53	1.54	0.06	0.25	Yes	-2.12	1.61	83
TCU	-0.91	1.43	127	-4.82	1.90	0.06	0.12	Yes	-3.72	1.90	158
MGCU	-2.49	N/A	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1
UCCU	-2.64	1.15	3	-3.48	-1.33	N/A	N/A	N/A	N/A	N/A	3
LCA	0.16	1.34	77	-2.85	3.12	0.08	0.15	Yes	-2.46	2.78	296
LCCU	-0.78	2.02	2	-2.21	0.65	N/A	N/A	N/A	N/A	N/A	2
Slug-Test-Scale											
AA	-0.70	1.17	14	-3.60	0.53	0.15	0.36	Yes	-3.01	1.60	25
VA	-2.49	1.08	142	-5.51	3.34	0.06	0.11	Yes	-4.61	-0.38	536
LFA, TCU	-2.34	1.12	258	-6.00	0.08	0.08	0.08	Yes	-4.54	-0.13	645
MGCU	-1.16	1.78	3	-3.19	0.15	N/A	N/A	N/A	N/A	N/A	3
UCCU	-2.35	0.79	7	-3.58	-1.16	N/A	N/A	N/A	N/A	N/A	7
LCA	-1.16	1.09	24	-4.02	0.75	0.14	0.28	Yes	-3.29	0.98	26
Laboratory-Scale											
AA	-0.76	1.56	73	-6.54	0.84	0.20	0.16	No	-3.81	2.29	73
VA	-3.77	2.23	403	-7.67	2.51	0.10	0.07	No	-8.14	0.60	403
TCU	-4.42	1.55	637	-8.13	4.60	0.07	0.05	No	-7.46	-1.38	637
LCA	-4.39	1.28	32	-6.33	-1.67	0.13	0.24	Yes	-6.89	-1.89	32
LCCU	-6.56	0.66	30	-7.54	-4.69	0.16	0.25	Yes	-7.86	-5.26	30

N/A = Not applicable (less than 10 data points available).

log-normal hypothesis was rejected for several datasets at the “Laboratory-Scale”; however, these datasets were probably not populated with random data points, but rather data collected to characterize specific conditions or intervals in wells that could not be generally characterized by other methods. The 95-percent confidence interval bounds for log-normal distributions determined from the data analyses were calculated. Figure E.1-3 illustrates the relationships of the NTS study area hydraulic conductivity data distributions for the different HGU categories. The HGUs are shown in vertical order as they generally occur in the HFM.

Figure E.1-3
Relationship of HGU Hydraulic Conductivity Distributions

E.1.8 Depth Dependence of Hydraulic Conductivity Analysis

Appendix B presented a discussion of depth dependence of permeability or hydraulic conductivity. The relationship used in the analysis of the depth dependence of K is described by the equation:

$$K_{Depth} = K_0 (10^{-\lambda d}) \quad (E-1)$$

where:

K_{Depth} = Horizontal hydraulic conductivity at specified depth (m/d)

K_0 = Horizontal hydraulic conductivity at land surface (m/d)

λ = Decay coefficient (calculated from linear regression) (1/m)

d = Depth from land surface (m)

The rate of decrease of hydraulic conductivity with depth is determined by the value of λ , the decay coefficient. The depth dependence of hydraulic conductivity was analyzed for the complete NTS Investigation Area dataset and for individual HGU datasets of the NTS Investigation Area. Depth versus hydraulic conductivity trends are specific to individual HGUs according to variations in physical properties affecting the hydraulic conductivity and the response to increasing effective stress with depth. However, the lumped evaluation illustrates the overall trend and provides a frame of reference for the individual HGU assessments. [Table E.1-2](#) presents the results of regression analysis of the depth dependence of hydraulic conductivity for each dataset. [Figure E.1-4](#) shows a graph of the NTS Investigation Area dataset and the regression trendline as well as two SDs for both K_0 and λ .

Table E.1-2
Summary of Depth-Decay Analysis

Data	Coefficient	Value	Standard Error	t-Stat	P-value	Lower 95%	Upper 95%	Lower 68.27%	Upper 68.27%
All Data	K_0	8.74E-01	1.13E-01	7.75	6.84E-14	6.53E-01	1.10E+00	7.61E-01	9.87E-01
	λ	-1.64E-03	1.36E-04	-12.0	9.11E-29	-1.91E-03	-1.37E-03	-1.78E-03	-1.50E-03
AA	K_0	9.75E-01	1.82E-01	5.36	2.23E-06	6.10E-01	1.34E+00	7.92E-01	1.16E+00
	λ	-2.09E-03	5.59E-04	-3.74	4.85E-04	-3.21E-03	-9.67E-04	-2.65E-03	-1.53E-03
VA	K_0	1.23E+00	1.65E-01	7.46	9.40E-12	9.05E-01	1.56E+00	1.07E+00	1.40E+00
	λ	-1.85E-03	1.93E-04	-9.60	6.02E-17	-2.23E-03	-1.47E-03	-2.04E-03	-1.66E-03
TCU	K_0	1.16E+00	4.04E-01	2.87	4.82E-03	3.60E-01	1.96E+00	7.53E-01	1.56E+00
	λ	-2.60E-03	4.90E-04	-5.35	0.00E-00	-3.57E-03	-1.64E-03	-3.09E-03	-2.12E-03
LCA	K_0	1.06E+00	2.39E-01	4.45	3.11E-05	5.86E-01	1.54E+00	8.21E-01	1.30E+00
	λ	-1.28E-03	2.58E-04	-4.95	4.74E-06	-1.79E-03	-7.62E-04	-1.54E-03	-1.02E-03

E.1.9 Hydrogeologic Unit-Specific Hydraulic Conductivity Analyses

Analyses were conducted at the HGU level for each scale of test. As can be seen in [Table E.1-1](#), substantial datasets were available for many of the HGUs at all three scales. At the regional scale,

Figure E.1-4
Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset

there were pumping-scale data available for all of the HGUs represented. There are additional data at the slug-test-scale and laboratory-scale for these HGUs. The following subsections discuss the HGU datasets for which there were data.

E.1.9.1 Alluvial Aquifer Hydrogeologic Unit

The AA is most accessible, because it is the shallowest aquifer and, therefore, fairly well investigated. The reported hydraulic conductivity values come from analyses of both single-well and multi-well tests (tests with observation wells). The results of single-well tests may be significantly different from multi-well tests because of difficulties in accounting for well losses and other production and local effects in single-well tests. Multi-well tests provide more accurate results and may also provide information on anisotropy. [Figure E.1-5](#) shows the results of the log-normality test for the NTS Investigation Area Pumping-Scale AA data, and [Figure E.1-6](#) shows $\log_{10} K$ versus depth for this dataset. [Figure E.1-7](#) shows the results of the log-normality test for the NTS Investigation Area Slug-Test-Scale AA data.

Figure E.1-5
Alluvial Aquifer Pumping-Scale Hydraulic Conductivity
Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-6
Alluvial Aquifer Pumping-Scale Hydraulic Conductivity Versus
Depth for the NTS Investigation Area Dataset

Figure E.1-7
Alluvial Aquifer Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset

E.1.9.2 Volcanic Aquifer Hydrogeologic Unit

The VA HGUs are also used extensively for water supply, and there are a substantial number of data points. [Figure E.1-8](#) shows the results of the log-normality test for the NTS Investigation Area Pumping-Scale VA data, and [Figure E.1-9](#) shows $\log_{10} K$ versus depth for this dataset. [Figure E.1-10](#) shows the results of the log-normality test for the NTS Investigation Area Slug-Test-Scale VA data.

E.1.9.3 Lava Flow Aquifer Hydrogeologic Unit

The LFA HGU was also used extensively for water supply, and there are a substantial number of data points in the NTS Investigation Area dataset. [Figure E.1-11](#) shows the results of the log-normality test for the NTS Investigation Area Pumping-Scale LFA data. [Figure E.1-12](#) shows the results of the log-normality test for the NTS Investigation Area Slug-Test-Scale combined LFA, TCU dataset. The data for these two HGUs were combined at the slug-test-scale, because the formation character (lithology, stratigraphy, and fracturing, as well as regional HSU distinctions) in the tested intervals was indistinguishable between the LFA and the TCU HGUs. This dataset is representative of the TCU and the low-permeability portions the LFA that are not highly fractured.

Figure E.1-8
Volcanic Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-9
Volcanic Aquifer Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset

Figure E.1-10
Volcanic Aquifer Slug Test-Scale Hydraulic Conductivity Probability
Distribution for the NTS Investigation Area Dataset

E.1.9.4 Tuff Confining Unit Hydrogeologic Unit

Figure E.1-13 shows the results of the log-normality test for the NTS Investigation Area Pumping-Scale TCU data, and Figure E.1-14 shows $\log_{10} K$ versus depth for this dataset. As explained in Section E.1.10.1, at the slug-test-scale, the formation character (lithology, stratigraphy, and fracturing, as well as regional HSU distinctions) in the tested intervals between the LFA and the TCU HGUs were indistinguishable, so a combined dataset was extracted (Figure E.1-12). This dataset is generally representative of the TCU.

E.1.9.5 Lower Carbonate Aquifer Hydrogeologic Unit

The LCA is another HGU used extensively for water supply, and there are a substantial number of data points in the NTS Investigation Area. Figure E.1-15 shows the results of the log-normality test for the NTS Investigation Area Pumping-Scale LCA data, and Figure E.1-16 shows $\log_{10} K$ versus depth for this dataset. Figure E.1-17 shows the results of the log-normality test for the NTS Investigation Area Slug-Test-Scale LCA data.

Figure E.1-11
Lava Flow Aquifer Pumping-Scale Hydraulic Conductivity
Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-12
Lava Flow Aquifer, Tuff Confining Unit Slug Test-Scale Hydraulic Conductivity
Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-13
Tuff Confining Unit Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-14
Tuff Confining Unit Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset

Figure E.1-15
Lower Carbonate Aquifer Pumping-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset

Figure E.1-16
Lower Carbonate Aquifer Pumping-Scale Hydraulic Conductivity Versus Depth for the NTS Investigation Area Dataset

Figure E.1-17
Lower Carbonate Aquifer Slug Test-Scale Hydraulic Conductivity Probability Distribution for the NTS Investigation Area Dataset

E.1.10 Test-Scale and Spatial Variability

The hydraulic conductivity of natural geologic formations is known to be spatially variable. The data presented in this report support that observation. Not only is the hydraulic conductivity variable with depth, it varies laterally as demonstrated by distinctly different ranges of values of hydraulic conductivity at different well locations in the same HSU.

Vanmarcke (1983) has shown that as the scale of averaging increases, the variance of a random process decreases, and the correlation length increases. Rubin and Gomez-Hernandez (1990) present theoretical and numerical examples of the impact of scaling as a function of block size. As the block size increases relative to the correlation scale, the mean value of the block approaches the geometric mean, and the variance of the mean value is significantly reduced. In their examples, the variance was reduced by a factor of 10 when the block size was 6.5 times the correlation length. The difficulty with application of approaches such as Rubin and Gomez-Hernandez (1990) is that covariance information, especially correlation length, is needed. In reality, this covariance information is never available. However, several key observations from the theoretical studies can be made. First, the

geometric mean is a reasonable estimate of the average hydraulic conductivity of a block. Second, the uncertainty in the hydraulic conductivity as characterized by the $\log_{10}$ SD is larger than the uncertainty in the block-scale value assuming that the available data represent the full range of variability in the formation. These scaling relationships are all based on the assumption of a constant mean and uniform statistical properties within an HSU. If these assumptions are incorrect, the conclusions of the theoretical studies may not apply.

Table E.1-3 shows the variation of the mean and SD with the scale of measurement for each HSU. It can be seen that as the scale of measurement increases, the measured value of $\log_{10}$ hydraulic conductivity increases and $\log_{10}$ SD decreases. The spatial locations of data are shown in Figure E.1-1.

Table E.1-3
Variation of the Mean and SD of Hydraulic Conductivity Data
by Scale of Measurements, by HSU

Data Analysis HSUs	Pumping-Scale Data		Slug-Test-Scale Data		Laboratory-Scale Data	
	Mean	Standard Deviation	Mean	Standard Deviation	Mean	Standard Deviation
AA	0.45	0.93	-0.70	1.17	-0.76	1.56
VA	-0.12	1.29	-2.49	1.08	-3.77	2.23
LFA	-0.26	0.95	-2.34	1.12	N/A	N/A
TCU	-0.91	1.43	-2.34	1.12	-4.42	1.55
UCCU	-2.64	1.15	-2.35	0.79	N/A	N/A
LCA	0.16	1.34	-1.16	1.09	-4.39	1.28
LCCU	-0.78	2.02	N/A	N/A	-6.56	0.66

Similar observations have been made in other studies reported in the literature. In contrast, Zlotnik et al. (2000) have reviewed many of these other studies and conclude that there is little evidence for a scale effect in hydraulic conductivity. They conclude, as does this report, that the large increases in mean hydraulic conductivity from laboratory- to field-scale measurements are most likely due to sampling bias, not true scale dependence. They also point out the difficulty of quantifying the scale of measurement for field techniques such as pumping tests and slug tests. The analysis generalizes the scale of measurement by slug and constant rate but does not quantify the

difference. In addition, Zlotnik et al. (2000) provide six general principles to apply to screening and comparing data. One of the principles regards coverage. They caution that comparison of data collected by two different techniques over two different subdomains is not possible. In other words, if the slug-test data were not collected in the same borehole and same depth interval as the pumping data, the comparison of results is not meaningful. Most, if not all cases, generated under this analysis do not have overlapping domains. For the purposes of large-scale flow modeling, the pumping-scale data will be the primary choice and the slug-test-scale data will be consulted only for secondary reference. Laboratory-scale data are not applicable to formations characterized by fracture flow, but may have limited usefulness in defining hydraulic conductivity in porous formations and in the matrix of the fractured formations.

E.1.11 Aquifer Unit Versus Confining Unit Results

As shown in [Figure E.1-3](#), the pumping-scale data show that the mean hydraulic conductivity varies as would be expected with the unit designation, aquifer versus confining unit. This is true for all three scales of measurement as can be seen in [Table E.1-1](#). Also, the laboratory-scale data show that the matrix hydraulic conductivity of the volcanic and carbonate aquifer units are similar to the hydraulic conductivity of the confining units. This would bolster the interpretation that the large-scale hydraulic conductivity of those aquifer units is a function of the fracture system within those units.

E.1.12 Aquifer Storage Properties

The storage coefficient (S) is defined as the volume of water that an aquifer releases from or takes into storage per unit surface area of the aquifer per unit change in head (Freeze and Cherry, 1979). It is a dimensionless variable that is generally smaller than 0.005 in confined aquifers. It is called the specific yield in unconfined aquifers and is a measure of the drainable porosity, typically less than 0.30. Specific storage (S_s) is the amount of water that an aquifer releases from or takes into storage, per unit volume, and is calculated by dividing the storage coefficient by the saturated thickness (b): $S = S_s * b$. Specific storage is used to assess storage parameter variability, because it removes the effects of unequal test interval lengths from the data.

Specific storage values span six orders of magnitude. The specific storage values that are greater than 10^{-3} are suspect, because the associated storativities would require excessively high porosity. These

very high storativity values are for the LCA from a location where the LCA is shallow and karstic and may have been dewatered during testing. These data likely do not represent the conditions in the LCA where it is deeply buried within the model area. At the lower end, the values represent fracture specific storage.

The distributions of S_s for the HSUs with more than a few data points (the AA, VA, TCU, and LCA) are quite similar. However, it is not clear how representative the data are of the broader distribution over the entire NTS Investigation Area. Sanchez-Vila et al. (1999) show that in the presence of heterogeneity, which always occurs in reality, storativity estimates will often vary strongly as a function of the relative transmissivity of the flow path between the pumping and observation well. Thus, storativity estimates depend on the degree of transmissivity heterogeneity. Sanchez-Vila et al. (1999) also suggest that a good estimate of true storativity is rarely obtained in practice from pumping tests. It is possible that much of the apparent scatter in specific storage values is unrelated to the actual variability of storage properties. General survey information on storage properties of formations in southern Nevada can be found in Kilroy (1992).

Table E.1-4 presents a summary of the analyses for “Specific Storage” and “Fracture Specific Storage” for NTS Investigation Area datasets. The “Specific Storage” datasets generally had a sufficient number of independent values to calculate statistics; however, there are much fewer data for “Fracture Specific Storage.” Figure E.1-18 shows the distributions of the specific storage data for the NTS Investigation Area datasets, identified by HGU. The specific storage probability distribution for all data spans seven orders of magnitude, centered on approximately 1.00×10^{-5} . All five of the included HGUs (AA, LFA, VA, TCU, and LCA) are generally consistent in this distribution.

Figure E.1-19 shows the fracture specific storage probability distribution, which includes the VA, TCU, and LCA HGUs. The data for this parameter, which is generally not distinguished from the general specific storage parameter, are very limited. The LCA values shown in this plot reflect four identical values found in the database for one test with four different hydraulic conductivity analyses. The fracture-specific storage values span about 1.5 orders of magnitude.

E.1.13 Anisotropy

In the general case, hydraulic conductivity is not a scalar value, but a second-rank tensor, where hydraulic conductivity at a point in space is a function of direction. The determination of horizontal

Table E.1-4
Summary of Specific Storage Analysis

Specific Storage (1/m)						
HGU	Mean	Standard Deviation	Count	Minimum	Maximum	Number of Entries
AA	1.08E-04	2.00E-04	22	1.40E-07	7.90E-04	27
VA	4.04E-03	2.32E-02	37	3.71E-15	1.41E-01	72
LFA	8.84E-04	3.14E-03	13	1.49E-07	1.13E-02	33
TCU	7.02E-05	1.71E-04	36	1.40E-07	8.44E-04	52
LCA	3.58E-02	9.97E-02	32	5.58E-09	4.69E-01	162
Fracture Specific Storage (1/m)						
VA	1.79E-06	N/A	1	N/A	N/A	1
TCU	5.43E-06	8.65E-06	7	5.91E-07	2.43E-05	8
LCA	1.01E-05	3.84E-06	5	8.33E-06	1.69E-05	9

Figure E.1-18
Specific Storage Data for the NTS Investigation Area Dataset

Figure E.1-19
Fracture Specific Storage Data for the NTS Investigation Area Dataset

anisotropy requires data from multiple observation wells completed in the same depth interval as the pumping well during aquifer testing. Anisotropy in the vertical direction can be determined from observation wells set at depths that differ from the pumped well. However, such analyses are difficult and uncertain because the tests are affected by other factors that are poorly constrained. There are some laboratory data on vertical to horizontal anisotropy, but laboratory results are generally not applicable to large-scale modeling.

E.1.14 Limitations

The data presented in this summary come from a variety of sources and represent data measured at different scales. Formations that are generally productive and often exploited for groundwater supplies are generally well characterized. As mentioned previously, the confining unit HGUs generally have hydraulic conductivity too low to conduct pumping tests. Slug-test-scale measurements provide a few additional values for the confining unit HGUs. The NTS Investigation Area data provide considerably more bases for determining representative distributions of hydraulic conductivity for Frenchman Flat HGUs.

Overall, the data for hydraulic properties are of high quality and provide hydraulic property information for the tested volumes of formation. However, there are significant limitations in applying the results of the analysis to the identification of representative hydraulic properties for the Frenchman Flat HSUs. As mentioned previously in this section, the amount of site-specific data available to characterize hydraulic conductivity for Frenchman Flat HSUs is not great. The aggregation of large datasets for HGUs better supported the analyses for statistical distributions. The distributions indicate the potential range of properties for the different formation types (HGUs) as defined by general character of hydrogeology. However, many HSUs have their own distinct character, which may result in specific properties for the HSU that are not the same as the average for the HGU but presumably would be within the 95-percent confidence range of the overall HGU. Following are specific limitations to keep in mind when using the results of the hydraulic property analysis.

First, only pumping-scale data are appropriate for use in parameterization of CAU groundwater flow models. There are data distributions for all HGUs at the pumping scale, but the data specific to Frenchman Flat would only support a distribution determined for the AA. The confining unit HGUs are not characterized at the pumping-scale because they are not amenable to such testing. Consequently, only much smaller-scale data are available for those HGUs.

Second, the available data for the Frenchman Flat CAU are very scattered throughout the investigation area and do not provide complete, comprehensive characterization across the extent of the Frenchman Flat HFM area. The aggregate area, presumed to be tested by all of the tests for an HSU, only constitutes a small percentage of the total area of the HSU. The available data are not well distributed and cannot be shown to equally sample the range of properties that may be present or provide a sense of spatial variability. The NTS Investigation Area distributions are not specific to the Frenchman Flat CAU.

Third, the data sampling (tested part of the formation) is biased, because many of the wells tested were drilled for water supply purposes and were specifically targeted for the most productive intervals of the formations penetrated. Tests in wells generally do not characterize the entire HSU (or a specific formation) in aggregate but only shorter intervals selected during drilling or testing, usually because of the particular productivity of the interval. In general, the concept used for UGTA

characterization drilling and well completion decisions has been that the more productive intervals are of primary interest under the assumption that transport of contaminants will preferentially occur in those intervals. This bias is particularly evident in cases of high hydraulic conductivity values for ostensible confining units when the formation is considered at the CAU scale. This is generally the result from a short test of a fractured interval within an otherwise low-conductivity formation.

The hydraulic properties of interest (that are characterized at the pumping scale) for many of these formations result from the fracturing within the formation. The individual tests provide information about the fracturing of the formation at a particular location, but there is no basis for assuming the fracturing is consistent across the extent of the HSU, vertically or laterally. In addition, tests of fractured formations provide information on the hydraulic properties of the fracture system, but these properties are not necessarily consistent with properties to be applied to an equivalent porous media flow model like the steady-state flow models constructed for the UGTA Project.

In summary, the data available for hydraulic properties of the HSUs are not definitive for the HSUs in Frenchman Flat and do not necessarily provide specific characterization for the large-scale aggregate hydraulic properties of the HSUs. This section provided data compilation and analysis for the available data, which can serve as a guide to appropriate hydraulic parameters, but must be viewed with regard to these limitations and interpreted within the context of the difference between specific test results and the appropriate values for equivalent HSU properties in flow modeling.

E.2.0 REFERENCES

- Benjamin, J.R., and C.A. Cornell. 1970. *Probability, Statistics, and Decision for Civil Engineers*. New York, NY: McGraw-Hill Book Co.
- DOE/NV, see U.S. Department of Energy, Nevada Operations Office.
- Freeze, R.A., and J.A. Cherry. 1979. *Groundwater*. Englewood Cliffs, NJ: Prentice Hall.
- Kilroy, K.C. 1992. *Aquifer Storage Characteristics of Paleozoic Carbonate Rocks in Southeastern Nevada Estimated from Harmonic Analysis of Water-Level Fluctuations*. University of Nevada at Reno, Ph. D. Dissertation.
- Rubin, Y., and J.J. Gomez-Hernandez. 1990. "A Stochastic Approach to the Problem of Upscaling of Conductivity in Disordered Media: Theory and Unconditional Numerical Simulations." In *Water Resources Research*, v. 26(4): 691-701. Washington, DC: American Geophysical Union.
- Rovey, C.W., and D.S. Cherkauer. 1995. "Scale Dependency of Hydraulic Conductivity Measurements." In *Groundwater*, v. 33(5): 769-780.
- SNJV, see Stoller-Navarro Joint Venture.
- Sanchez-Vila, X., P.M. Meier, and J. Carrera. 1999. "Pumping Tests in Heterogeneous Aquifers: An Analytical Study of What Can Be Obtained from their Interpretation Using Jacob's Method." In *Water Resources Research*, v. 35(4): 943-952. Washington, DC: American Geophysical Union.
- Stoller-Navarro Joint Venture. 2004a. *Phase II Hydrologic Data for the Groundwater Flow and Contaminant Transport Model of Corrective Action Unit 98: Frenchman Flat, Nye County, Nevada*, Rev. 0, S-N/99205--032. Las Vegas, NV.
- Stoller-Navarro Joint Venture. 2004b. *Transferability of Data Related to the Underground Test Area Project, Nevada Test Site, Nye County, Nevada*, Rev. 0, S-N/99205--020. Las Vegas, NV.
- U.S. Department of Energy, Nevada Operations Office. 1997. *Regional Groundwater Flow and Tritium Transport Modeling and Risk Assessment of the Underground Test Area, Nevada Test Site, Nevada*, DOE/NV--477. Las Vegas, NV.
- Vanmarcke, E. 1983. *Random Fields: Analysis and Synthesis*. Cambridge, MA: The MIT Press.

Zlotnik, V.A., B.R. Zurburchen, T. Ptak, and G. Teutsch. 2000. "Support Volume and Scale Effect in Hydraulic Conductivity: Experimental Aspects." In *Theory, Modeling, and Field Investigation in Hydrogeology: A Special Volume in Honor of Shlomo P. Neuman's 60th Birthday Special Paper*, v. 348: 215-231. Boulder, CO: Geological Society of America, Inc.

DISTRIBUTION

Tim Murphy
State of Nevada
Division of Environmental Protection
1771 E. Flamingo Road, Suite 121A
Las Vegas, NV 89119

2 HC/2CD

Bill R. Wilborn
Environmental Restoration Project
U.S. Department of Energy
National Nuclear Security Administration
Nevada Site Office
P.O. Box 98518, MS/505
Las Vegas, NV 89193-8518

2 HC/2CD

Bruce Crowe
Environmental Restoration Project
U.S. Department of Energy
National Nuclear Security Administration
Nevada Site Office
P.O. Box 98518, MS/505
Las Vegas, NV 89193-8518

1 CD

Alicia Tauber
Environmental Management Records
U.S. Department of Energy
National Nuclear Security Administration
Nevada Site Office
P.O. Box 98518, MS/505
Las Vegas, NV 89193-8518

1 CD

U.S. Department of Energy
National Nuclear Security Administration
Nevada Site Office
Technical Library
P.O. Box 98518, M/S 505
Las Vegas, NV 89193-8518

1 HC

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062

1 CD

Southern Nevada Public Reading Facility c/o Nuclear Testing Archive P.O. Box 98521, M/S 400 Las Vegas, NV 89193-8521	1 HC
Manager, Northern Nevada FFACO Public Reading Facility c/o Nevada State Library & Archives 100 N Stewart Street Carson City, NV 89701-4285	1 HC
Edward M. Kwicklis Los Alamos National Laboratory Hydrology, Geochemistry, and Geology Group, EES-6 Earth and Environmental Sciences Division Bikini Atoll Rd., SM-30 Los Alamos, NM 87545	1 HD/1 CD
Naomi Becker Los Alamos National Laboratory, M/S F665 Bikini Atoll Rd., SM30 Los Alamos, NM 87545	1 CD
Carl Gable Los Alamos National Laboratory, M/S F665 Bikini Atoll Rd., SM30 Los Alamos, NM 87545	1 CD
Paul Reimus Los Alamos National Laboratory Chemical Science and Technology Division, MS-J514 Bikini Atoll Rd., SM-30 Los Alamos, NM 87545	1 CD
Andrew V. Wolfsberg Los Alamos National Laboratory Hydrology, Geochemistry, and Geology Group, EES-6 Earth and Environmental Sciences Division Bikini Atoll Rd., SM-30 Los Alamos, NM 87545	1 CD
Jeff Daniels Lawrence Livermore National Laboratory 7000 East Avenue Livermore, CA 94550-9234	1 CD

Tim P. Rose Lawrence Livermore National Laboratory 7000 East Avenue, L-231 Livermore, CA 94550-9234	1 CD
Gayle Pawloski Lawrence Livermore National Laboratory 7000 East Avenue, L-221 Livermore, CA 94550-9234	1 CD
Andrew Tompson Lawrence Livermore National Laboratory 7000 East Avenue, L-204 Livermore, CA 94550-9234	1 CD
Mavrik Zavarin Lawrence Livermore National Laboratory 7000 East Avenue, L-221 Livermore, CA 94550-9234	1 CD
Sig Drellack Bechtel Nevada P.O. Box 98521, M/S NLV 082 Las Vegas, NV 89193-8521	1 CD
Ken Ortego Bechtel Nevada P.O. Box 98521, M/S NLV 082 Las Vegas, NV 89193-8521	1 CD
Greg Pohll Desert Research Institute 2215 Raggio Parkway Reno, NV 89512	1 CD
Chuck E. Russell Desert Research Institute 755 E. Flamingo Las Vegas, NV 89119	1 CD
Richard K. Waddell GeoTrans, Inc. 363 Centennial Parkway, Suite 210 Louisville, CO 80027-1619	1 CD

Bonnie Thompson
USGS WRD
160 North Stephanie Street
Henderson, NV 89074

1 CD

Wayne Belcher
USGS WRD
160 North Stephanie Street
Henderson, NV 89074

1 CD

John Pickens
INTERA Inc.
9111A Research Blvd.
Austin, TX 78758

1 CD

Stoller-Navarro Joint Venture
Central Files
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 HC/1 CD

Stoller-Navarro Joint Venture
FFACO Support Office
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 HC/1 CD

Nicole DeNovio
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 HC/1 CD

John McCord
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 CD

Greg Ruskauff
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 CD

Bryan Dunlap
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

1 CD

Keely Brooks 1 CD
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

Irene Farnham 1 CD
Stoller-Navarro Joint Venture
7710 W. Cheyenne Ave., Bldg. 3
Las Vegas, NV 89129

West to East Profile (A-A') Through Drill Hole ER 5-3-#2

Southwest to Northeast Profile (C-C') Through Drill Hole ER-5-4

West to East Profile (B-B') Through Drill Hole ER-5-4

Northwest to Southwest Profile (D-D') Through Drill Hole ER-5-4

Northwest to Southeast Profile (E-E') Through Southwest Frenchman Flat

West to East Profile (F-F') Through Drill Hole WW-5C

Plate 1
Cross Sections for
BASE HFM

Map of Hydrostratigraphic Units
at the Surface with Profile Locations

Base Model

CP Basin
Alternative Model

Base Model

Map View of A-A' location with all HSUs removed above CP Thrust.

Map of Hydrostratigraphic Units at the surface with profile locations

Base Model

Aquifer Displacement (Juxtaposition)
Alternative Model

Base Model

Map View of G-G' location with all alluvium units removed. Arrow indicates fault along which LCA is in contact with Timber Mountain Aquifer units (TMWTA, TMLVTA) in the Aquifer Displacement Alternative. Colored Squares indicate drill hole locations.

Base Model

No Detachment
Alternative Model

Base Model

Map View of H-H' location with all alluvium units removed. Arrow indicates location of Detachment Fault in base model. The Detachment Fault is removed in the No Detachment Alternative Model. Green Squares indicate drill hole locations.

Profile Legend

Map View of BLFA Extent in Base Model with AA3 Removed

Note: See red box on HSU at surface base map for location of view.

Map View of BLFA Extent in BLFA Alternative Model with AA3 Removed

Note: See red box on HSU at surface base map for location of view.

Plate 2

Cross Sections and Plan View for Alternative HFMs Compared with BASE HFM