I-20032-0012

BJC/OR-2988

**ENVIRONMENTAL
MANAGEMENT**

**Calendar Year 2007
Resource Conservation
and Recovery Act
Annual Monitoring Report
for the
U.S. Department of Energy
Y-12 National Security Complex,
Oak Ridge, Tennessee**

**RCRA Post-Closure Permit Nos.
TNHW-113, TNHW-116, and TNHW-128**

EPA Identification No. TN3 89 009 0001

RECEIVED

Elvado Environmental LLC

contributed to the preparation of this document and should not be considered
eligible contractors for its review.

**Calendar Year 2007
Resource Conservation
and Recovery Act
Annual Monitoring Report
for the
U.S. Department of Energy
Y-12 National Security Complex,
Oak Ridge, Tennessee**

RCRA Post-Closure Permits: TNHW-113, TNHW-116, and TNHW-128
EPA Identification No.: TN3 89 009 0001

Date Issued-February 2008

Prepared by
Elvado Environmental LLC
under subcontract 23900-PO-ES845

Prepared for the
U.S. Department of Energy
Office of Environmental Management

BECHTEL JACOBS COMPANY LLC
managing the
Environmental Management Activities at the
East Tennessee Technology Park
Y-12 National Security Complex Oak Ridge National Laboratory
under contracts DE-AC05-98OR22700
for the
U.S. DEPARTMENT OF ENERGY

CONTENTS

DATA SUMMARY TABLES	v
ABBREVIATIONS	vii
RCRA FACILITY INFORMATION	ix
CERTIFICATION STATEMENT	ix
EXECUTIVE SUMMARY	xi
1. INTRODUCTION	1
2. RCRA POST-CLOSURE PERMITS AND TSD UNITS	3
2.1 BEAR CREEK HYDROGEOLOGIC REGIME	3
2.1.1 S-3 Site	3
2.1.2 Oil Landfarm	4
2.1.3 Bear Creek Burial Grounds/Walk-In Pits	4
2.2 UPPER EAST FORK POPLAR CREEK HYDROGEOLOGIC REGIME	4
2.2.1 Eastern S-3 Site Plume	5
2.2.2 New Hope Pond	5
2.3 CHESTNUT RIDGE HYDROGEOLOGIC REGIME	5
2.3.1 Chestnut Ridge Security Pits	6
2.3.2 Chestnut Ridge Sediment Disposal Basin	6
2.3.3 Kerr Hollow Quarry	6
2.3.4 East Chestnut Ridge Waste Pile	6
3. HYDROGEOLOGIC FRAMEWORK	7
3.1 TOPOGRAPHY AND BEDROCK GEOLOGY	7
3.1.1 Bear Creek Valley	8
3.1.2 Chestnut Ridge	8
3.2 SURFACE DRAINAGE	9
3.2.1 Bear Creek	9
3.2.2 Upper East Fork Poplar Creek	10
3.2.3 Chestnut Ridge	10
3.3 GROUNDWATER SYSTEM	10
3.3.1 Bear Creek Valley	10
3.3.2 Chestnut Ridge	12
3.4 GROUNDWATER CONTAMINATION	13
3.4.1 Bear Creek Hydrogeologic Regime	13
3.4.1.1 S-3 Site	13
3.4.1.2 Oil Landfarm Waste Management Area	14
3.4.1.3 Bear Creek Burial Grounds Waste Management Area	16
3.4.1.4 Maynardville Limestone Exit Pathway	17
3.4.2 Upper East Fork Poplar Creek Hydrogeologic Regime	18
3.4.3 Chestnut Ridge Hydrogeologic Regime	19
4. CY 2007 RCRA POST-CLOSURE GROUNDWATER SAMPLING AND ANALYSIS	21
4.1 SAMPLING LOCATIONS AND FREQUENCIES	21
4.1.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits	21
4.1.2 Eastern S-3 Site Plume	22

4.1.3 Chestnut Ridge Security Pits	22
4.1.4 Chestnut Ridge Sediment Disposal Basin	22
4.1.5 Kerr Hollow Quarry.....	23
4.1.6 East Chestnut Ridge Waste Pile	23
4.2 SAMPLING METHODS	23
4.3 FIELD MEASUREMENTS AND LABORATORY ANALYTES	24
4.3.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits.....	25
4.3.2 Eastern S-3 Site Plume	26
4.3.3 Chestnut Ridge Security Pits	26
4.3.4 Chestnut Ridge Sediment Disposal Basin	27
4.3.5 Kerr Hollow Quarry.....	28
4.3.6 East Chestnut Ridge Waste Pile	28
4.4 QUALITY ASSURANCE/QUALITY CONTROL SAMPLING.....	29
4.5 DATA MANAGEMENT	29
4.6 DATA QUALITY OBJECTIVES EVALUATION.....	30
5. CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING	
DATA EVALUATION	33
5.1 GROUNDWATER FLOW DIRECTION AND RATE	33
5.1.1 Bear Creek Valley.....	33
5.1.2 Chestnut Ridge.....	35
5.2 RCRA POINT-OF-COMPLIANCE MONITORING DATA	37
5.2.1 S-3 Site	37
5.2.2 Oil Landfarm	40
5.2.3 Bear Creek Burial Grounds/Walk-In Pits.....	42
5.2.4 Eastern S-3 Site Plume	44
5.2.5 Chestnut Ridge Security Pits.....	47
5.3 RCRA PLUME BOUNDARY MONITORING DATA	49
5.3.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits.....	49
5.3.2 Eastern S-3 Site Plume	51
5.3.3 Chestnut Ridge Security Pits	52
5.4 RCRA POST-CLOSURE DETECTION MONITORING DATA.....	52
5.4.1 Chestnut Ridge Sediment Disposal Basin	52
5.4.2 Kerr Hollow Quarry.....	52
5.4.3 East Chestnut Ridge Waste Pile	52
6. LEACHATE SAMPLING DATA	53
7. REFERENCES	555
APPENDIX A: FIGURES	A-1
APPENDIX B: TABLES.....	B-1
APPENDIX C: CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA FOR THE BEAR CREEK HYDROGEOLOGIC REGIME	C-1
APPENDIX D: CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA FOR THE UPPER EAST FORK POPLAR CREEK HYDROGEOLOGIC REGIME	D-1
APPENDIX E: CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA FOR THE CHESTNUT RIDGE HYDROGEOLOGIC REGIME.....	E-1

DATA SUMMARY TABLES

1	RCRA post-closure permits and effective dates for applicable TSD units at Y-12	1
2	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the S-3 Site, Oil Landfarm, and BCBG/WIP	25
3	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the Eastern S-3 Site Plume	26
4	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the CRSP	27
5	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at the CRSDB	27
6	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at KHQ	28
7	CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at the ECRWP	28
8	CY 2007 false-positive results for VOCs that are RCRA groundwater target compounds	31
9	Representative horizontal hydraulic gradients in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume, April 2007	34-35
10	Calculated rates of groundwater flow in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume	35
11	Representative horizontal hydraulic gradients in the uppermost aquifer at the CRSP, CRSDB, KHQ, and ECRWP, April 2007	36
12	Calculated rates of groundwater flow in the uppermost aquifer at the CRSP, CRSDB, KHQ and ECRWP	37
13	CY 2007 sampling results for the RCRA groundwater target compounds detected in S-3 Site POC well GW-276	38
14	CY 2007 sampling results for the RCRA groundwater target compounds detected in Oil Landfarm POC well GW-008	40
15	CY 2007 sampling results for the RCRA groundwater target compounds detected in BCBG/WIP POC well GW-046	43
16	CY 2007 sampling results for the RCRA groundwater target compounds detected in Eastern S-3 Site POC well GW-108	45

17	CY 2007 sampling results for the RCRA groundwater target compounds detected in CRSP POC well GW-177	48
18	CY 2007 sampling results for the RCRA groundwater target compounds detected in RCRA plume boundary wells GW-712, GW-713, and GW-714 in the Bear Creek Regime	50
19	CY 2007 sampling results for the RCRA groundwater target compounds detected in RCRA plume boundary spring SS-6 in the Bear Creek Regime	50-51
20	Summary of CY 2007 leachate sampling results for the ECRWP	54

ABBREVIATIONS

AGLLSF	Above Grade Low-Level Storage Facility
BCBG	Bear Creek Burial Grounds
BCK	Bear Creek kilometer
BCV	Bear Creek Valley
Bear Creek Regime	Bear Creek Hydrogeologic Regime
BG	Burial Grounds
bgs	below ground surface
BJC	Bechtel Jacobs Company LLC
BQR	blank qualification result
BT	buried tributary
BY/BY	Boneyard/Burnyard
CA	characterization area
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act of 1980
Chestnut Ridge Regime	Chestnut Ridge Hydrogeologic Regime
CRSP	Chestnut Ridge Security Pits
CRSDB	Chestnut Ridge Sediment Disposal Basin
CY	calendar year
DNAPL	dense nonaqueous phase liquid
DOE	U.S. Department of Energy
DQO	data quality objective
ECRWP	East Chestnut Ridge Waste Pile
EMWMF	Environmental Management Waste Management Facility
Energy Systems	Lockheed Martin Energy Systems, Inc. (formerly Martin Marietta Energy Systems, Inc.)
EPA	U.S. Environmental Protection Agency
FY	fiscal year
gpd	gallons per day
HCDA	Hazardous Chemical Disposal Area
HWDU	hazardous waste disposal unit
KHQ	Kerr Hollow Quarry
MCL	maximum contaminant level
MDA	minimum detectable activity
msl	mean sea level
NPDES	National Pollutant Discharge Elimination System
NT	north tributary (of Bear Creek)
ORNL	Oak Ridge National Laboratory
ORR	Oak Ridge Reservation
PCP	post-closure permit
PEMS	Project Environmental Measurement System
PCB	polychlorinated biphenyls
POC	point-of-compliance
PQL	project quantitation level
PVC	polyvinyl chloride
QA/QC	quality assurance/quality control
RCRA	Resource Conservation and Recovery Act of 1976
REDOX	oxidation-reduction potential
ROD	record of decision

RI	remedial investigation (CERCLA)
SAP	Sampling and Analysis Plan
SDWA	Safe Drinking Water Act of 1974
TDEC	Tennessee Department of Environment and Conservation
TDS	total dissolved solids
TPU	total propagated uncertainty
TSD	treatment, storage, and disposal (unit)
UEFPC	Upper East Fork Poplar Creek
Upper East Fork Regime	Upper East Fork Poplar Creek Hydrogeologic Regime
VOC	volatile organic compound
WIP	Walk-In Pits
WMA	Waste Management Area
WRRP	Water Resources Restoration Program
Y-12	Y-12 National Security Complex

RCRA FACILITY INFORMATION

Facility: U.S. Department of Energy Y-12 National Security Complex
(Formerly the U.S. Department of Energy Oak Ridge Y-12 Plant)
Address: P.O. Box 2001
Oak Ridge, Tennessee 37831
Identification No.: TN3 89 009 0001
Tennessee Permit Nos.: TNHW-113 – Upper East Fork Poplar Creek Hydrogeologic Regime
TNHW-116 – Bear Creek Hydrogeologic Regime
TNHW-128 – Chestnut Ridge Hydrogeologic Regime

CERTIFICATION STATEMENT

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Bechtel Jacobs Company LLC

Date Signed

EXECUTIVE SUMMARY

This report contains groundwater quality monitoring data obtained during calendar year (CY) 2007 at the following hazardous waste treatment, storage, and disposal (TSD) units located at the U.S. Department of Energy (DOE) Y-12 National Security Complex (hereafter referenced as Y-12) in Oak Ridge, Tennessee: the S-3 Site, Oil Landfarm, Bear Creek Burial Grounds/Walk-In Pits (BCBG/WIP), Eastern S-3 Site Plume, Chestnut Ridge Security Pits (CRSP), Chestnut Ridge Sediment Disposal Basin (CRSDB), Kerr Hollow Quarry (KHQ), and East Chestnut Ridge Waste Pile (ECRWP). The monitoring data were obtained in accordance with the applicable Resource Conservation and Recovery Act of 1976 (RCRA) hazardous waste post-closure permit (PCP). The Tennessee Department of Environment and Conservation (TDEC) – Division of Solid Waste Management issued the PCPs to define the requirements for RCRA post-closure inspection, maintenance, and groundwater monitoring at the specified TSD units located within the Bear Creek Hydrogeologic Regime (PCP no. TNHW-116), Upper East Fork Poplar Creek Hydrogeologic Regime (PCP no. TNHW-113), and Chestnut Ridge Hydrogeologic Regime (PCP no. TNHW-128). Each PCP requires the submittal of an annual RCRA groundwater monitoring report containing the groundwater sampling information and analytical results obtained at each applicable TSD unit during the preceding CY, along with an evaluation of groundwater flow rates and directions and the analytical results for specified RCRA groundwater target compounds; this report is the RCRA annual groundwater monitoring report for CY 2007.

The RCRA post-closure groundwater monitoring requirements specified in the above-referenced PCP for the Chestnut Ridge Regime replace those defined in the previous PCP (permit no. TNHW-088), which expired on September 18, 2005, but remained effective until the TDEC issued the new PCP in September 2006. The new PCP defines site-specific groundwater sampling and analysis requirements for the CRSDB, CRSP, and KHQ that differ from those established under the expired PCP, including modified suites of laboratory analytes (RCRA groundwater target compounds) for each site and annual rather than semiannual sampling frequencies for the CRSDB and KHQ. The new PCP also specifies the RCRA post-closure groundwater monitoring requirements for the ECRWP, a closed TSD unit that was not addressed in the expired PCP.

In accordance with the site-specific requirements of the respective PCP for each hydrogeologic regime, RCRA post-closure groundwater monitoring during CY 2007 involved the sampling locations and frequencies identified below:

- Semiannually from at least one of the site-specific point of compliance (POC) wells designated for RCRA post-closure corrective action monitoring at the S-3 Site (GW-276), Oil Landfarm (GW-008), BCBG/WIP (GW-046), Eastern S-3 Site Plume (GW-108), and the CRSP (GW-177), and the designated upgradient/background well for the CRSP (GW-521).
- Semiannually from the respective networks of RCRA plume boundary monitoring locations in the Bear Creek Regime (wells GW-712, GW-713, and GW-714 and spring SS-6), Upper East Fork Regime (wells GW-193, GW-605, GW-606, and GW-733), and Chestnut Ridge Regime (wells GW-301, GW-557, GW-562, GW-799, GW-801, and GW-831, and spring SCR4.3SP).
- Semiannually from the upgradient/background well (GW-294) and each POC well designated for RCRA post-closure detection monitoring at the ECRWP (GW-161, GW-292, GW-293, GW-296, and GW-298). The PCP for the Chestnut Ridge Regime requires sampling only three of the POC

wells during each semiannual sampling event, but samples were collected from all of the POC wells at the site during CY 2007 in order to provide additional baseline data for each well.

- Annually from the respective site-specific network of upgradient/background and POC wells designated for RCRA post-closure detection monitoring at the CRSDB (GW-156, GW-159, GW-731, and GW-732) and KHQ (GW-143, GW-144, GW-145, and GW-231). This reflects a change from the semiannual sampling frequency required under the previous PCP for the Chestnut Ridge Regime (permit no. TNHW-088).

As required by the general and site-specific conditions of the applicable PCP, the groundwater samples collected during CY 2007 from the POC wells at each TSD unit, upgradient/background wells at applicable sites, and the RCRA plume boundary monitoring locations in each regime were analyzed for the RCRA groundwater target constituents designated in each PCP. All but a relative few of the analytical results are consistent with previous RCRA post-closure groundwater monitoring data for each well and spring and meet other applicable data quality objectives (DQOs). Results that do not meet DQOs include low concentrations of volatile organic compounds (VOCs) detected in the POC wells for the S-3 Site (acetone and methylene chloride), Eastern S-3 Site Plume (acetone), and ECRWP (methylene chloride); the upgradient/background well at the ECRWP (methylene chloride); and the RCRA plume boundary sampling locations in the Bear Creek Regime (methylene chloride). Additionally, concentrations of trace metals reported for the groundwater samples from the upgradient/background well at the ECRWP (chromium, iron, and nickel) and a POC well at the site (manganese) are rejected based on DQO comparison with historical data for the well. Results that do not meet DQOs did not adversely impact evaluation of the RCRA post-closure groundwater monitoring data for each applicable site.

Site-specific conditions of the applicable PCP collectively require annual evaluation of the groundwater flow direction and rate in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, Eastern S-3 Site Plume, CRSP, CRSDB, KHQ, and ECRWP. Directions of groundwater flow at each site, as defined by groundwater elevation isopleths based on monitoring well depth-to-water measurements recorded in January 2007, are consistent with those observed during previous years. Based on the modified Darcy equation (and inherent assumptions), representative horizontal hydraulic gradients determined from the January 2007 groundwater elevation data for selected monitoring wells at each TSD unit and values for effective porosity and hydraulic conductivity from several hydrogeologic investigations at Y-12, calculated rates of groundwater flow in the uppermost aquifer at each site range over several orders of magnitude. The lowest flow rates (0.0002 ft per day) are representative of low-permeability matrix intervals in the predominately shale bedrock underlying the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume, and the highest flow rates (>1000 ft per day) are representative of the most permeable karst features in the carbonate bedrock beneath the CRSP, CRSDB, and ECRWP.

Quantitative trend analysis of the RCRA post-closure corrective action groundwater monitoring results for selected RCRA groundwater target constituents detected in the POC wells at the S-3 Site, Oil Landfarm, BCBG/WIP, Eastern S-3 Site Plume, and the CRSP during CY 2007 was performed as required by site-specific conditions of the PCPs for the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime. The trend analyses were based on time-series plots of analytical results obtained since January 1998 (which coincides with the programmatic change in the groundwater sampling method), with least-squares linear regression used to determine the relative direction (upward or downward) of each trend. Non-detected results were excluded from the trend analyses, as were results that do not meet applicable DQOs. Decreasing or indeterminate (not increasing or decreasing) concentration trends are indicated by the time-series plots of the data for selected RCRA groundwater target constituents detected in the POC wells at the S-3 Site, Oil Landfarm, BCBG/WIP, and CRSP, and the respective trend lines determined from linear regression of the data. These findings are consistent with

conceptual contaminant transport models developed for the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume and are expected in response to the closure and subsequent installation of the low-permeability cap at each TSD unit. However, the time-series plot of technetium-99 (Tc-99) results for Eastern S-3 Site Plume POC well GW-108 shows an increasing long-term concentration trend, although the CY 2007 RCRA sampling results suggest a decrease from the Tc-99 levels evident through July 2006. It is unclear why the Tc-99 levels increased over the long term, especially in light of the decreasing concentrations of other contaminants (e.g., nitrate) in the shallow groundwater from this well.

Site-specific conditions of the PCPs for the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime collectively require the RCRA post-closure corrective action monitoring data for the designated RCRA plume boundary monitoring locations in each regime to be evaluated annually for evidence of contaminant transport/migration from the S-3 Site, Oil Landfarm, BCBG/WIP, Eastern S-3 Site Plume, and CRSP. Evaluation of the respective CY 2007 sampling results indicates that each RCRA plume boundary monitoring location in the Bear Creek Regime and Chestnut Ridge Regime continue to yield uncontaminated groundwater samples and the RCRA plume boundary wells in the Upper East Fork Regime yield groundwater samples that do not contain Tc-99, the "signature" component of the Eastern S-3 Site Plume.

The CY 2007 results for RCRA post-closure detection monitoring at the CRSDB, KHQ, and ECRWP were evaluated in accordance with the procedures described in corresponding site-specific attachments to the PCP for the Chestnut Ridge Regime. Required statistical analyses of applicable data were completed within 90 days of the corresponding groundwater sampling event at each site, as required by the PCP for the Chestnut Ridge Regime. The groundwater sampling results for the wells at each site and the applicable statistical analyses do not indicate a release of contaminants to the uppermost aquifer at the any of these TSD units.

The PCP for the Chestnut Ridge Regime requires the sampling and analysis of leachate from the ECRWP, with the analytical results used to evaluate whether any constituents need to be added to the list of RCRA groundwater target compounds specified for the site. Evaluation of the CY 2007 leachate sampling results indicates that no changes to the list of RCRA groundwater target compounds is warranted at this time, aside from correcting the typographical error that identifies "chloromethane" as a target compound instead of "chloroethane" (chloromethane has not been detected in any of the leachate samples collected to date, whereas chloroethane was detected in several of the leachate samples, including both samples collected during CY 2007).

1. INTRODUCTION

This report contains groundwater quality monitoring data obtained during calendar year (CY) 2007 at several closed hazardous waste treatment, storage, and disposal (TSD) units located at the U.S. Department of Energy (DOE) Y-12 National Security Complex (hereafter referenced as Y-12) in Oak Ridge, Tennessee (Appendix A, Fig. 1; directions are in reference to the Y-12 grid). The groundwater quality monitoring data were obtained in accordance with the Resource Conservation and Recovery Act of 1976 (RCRA) hazardous waste post-closure permits (PCPs) issued by the Tennessee Department of Environment and Conservation (TDEC) – Division of Solid Waste Management. These PCPs define the requirements for RCRA post-closure inspection, maintenance, and monitoring of the specified TSD units, identified below in Table 1, located within the Bear Creek Hydrogeologic Regime (Bear Creek Regime), Upper East Fork Poplar Creek Hydrogeologic Regime (Upper East Fork Regime), and Chestnut Ridge Hydrogeologic Regime (Chestnut Ridge Regime).

Table 1. RCRA post-closure permits and effective dates for applicable TSD units at Y-12

PCP Number/ Hydrogeologic Regime	Effective Date	TSD Units
TNHW-113 Upper East Fork Regime	09/23/2003	Eastern S-3 Site Plume New Hope Pond
TNHW-116 Bear Creek Regime	12/10/2003	S-3 Site Oil Landfarm Bear Creek Burial Grounds (BCBG)/Walk-In Pits (WIP)
TNHW-128 Chestnut Ridge Regime	09/29/2006	Chestnut Ridge Security Pits (CRSP) Chestnut Ridge Sediment Disposal Basin (CRSDB) Kerr Hollow Quarry (KHQ) East Chestnut Ridge Waste Pile (ECRWP)

Site-specific requirements for RCRA post-closure groundwater monitoring at each of the above-listed TSD units, as defined in the associated PCP, are summarized in Appendix B, Table 1 (Bear Creek Regime), Table 2 (Upper East Fork Regime), and Table 3 (Chestnut Ridge Regime) and indexed to the corresponding sections of this report.

The RCRA post-closure groundwater monitoring requirements specified in the above-referenced PCP for the Chestnut Ridge Regime replace those defined in the previous PCP (permit no. TNHW-088), which expired on September 18, 2005 but remained effective until the TDEC issued the new PCP in September 2006. The new PCP defines site-specific groundwater sampling and analysis requirements for the CRSDB, CRSP, and KHQ that differ from those established under the expired PCP, including modified suites of laboratory analytes (RCRA groundwater target compounds) for each site and annual rather than semiannual sampling frequencies for the CRSDB and KHQ. The new PCP also specifies the RCRA post-closure groundwater monitoring requirements for the ECRWP, a closed TSD unit that was not addressed in the expired PCP.

The RCRA post-closure groundwater monitoring results contained in this report include the sampling and analysis data from the first 180-day reporting period for CY 2007, which were submitted previously to the TDEC before the September 1 reporting deadline specified in each respective PCP (Bechtel Jacobs Company LLC [BJC] 2007a). In addition, this report contains the groundwater sampling and analysis results from the second 180-day reporting period for CY 2007, which must be submitted to the TDEC before the March 1 reporting deadline specified in each respective PCP. Also included in this report are

the CY 2007 leachate sampling data obtained for the ECRWP as required by the PCP for the Chestnut Ridge Regime (Appendix B, Table 3).

Section 2 of this report includes brief descriptions of the TSD units in each hydrogeologic regime that are addressed in the corresponding PCP. Section 3 provides an overview of the hydrogeologic framework in each hydrogeologic regime, including short descriptions of the topography and bedrock geology, surface drainage, the uppermost aquifer at each TSD unit, and the overall extent of groundwater contamination in each regime. Section 4 presents a summary of the groundwater sampling and analysis activities performed for the purposes of RCRA post-closure groundwater monitoring during CY 2007. Results of the groundwater monitoring data evaluations required by the respective PCP for each hydrogeologic regime are in Sect. 5. An evaluation of the leachate sampling results for the ECRWP is in Sect. 6 and the documents cited for more detailed operational, regulatory, and technical information are listed in Sect. 7.

Illustrations (maps and trend graphs) and data tables referenced in this report are in Appendix A and Appendix B, respectively. The RCRA post-closure groundwater monitoring results obtained during CY 2007 are tabulated in Appendix C (Bear Creek Regime), Appendix D (Upper East Fork Regime), and Appendix E (Chestnut Ridge Regime).

2. RCRA POST-CLOSURE PERMITS AND TSD UNITS

The following sections provide brief descriptions of the hydrogeologic regimes at Y-12 and the RCRA TSD units that are addressed in the corresponding PCP for the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime.

2.1 BEAR CREEK HYDROGEOLOGIC REGIME

The PCP for the Bear Creek Regime defines the RCRA requirements for post-closure inspection, maintenance, and groundwater monitoring at the S-3 Site (formerly the S-3 Ponds), the Oil Landfarm hazardous waste disposal unit (HWDU), and the BCBG/WIP. The Bear Creek Regime is bound to the north by Pine Ridge and to the south by Chestnut Ridge and encompasses the portion of Bear Creek Valley (BCV) between a low topographic and hydrologic divide located near the western end of Y-12 and the western boundary of the Bear Creek watershed (Appendix A, Fig. 2).

In addition to the S-3 Site, Oil Landfarm, and BCBG/WIP, the Bear Creek Regime encompasses numerous other hazardous and nonhazardous waste management facilities (Appendix B, Table 4). With the exception of two operating facilities, the Environmental Management Waste Management Facility (EMWMF) and the Above Grade Low-Level Storage Facility (AGLLSF), all these facilities are closed and currently regulated under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) of 1980. The EMWMF, a hazardous and mixed-waste landfill that began operating in June 2002, is regulated under CERCLA, with RCRA as an applicable, or relevant and appropriate requirement. The AGLLSF is not regulated under CERCLA or RCRA. All of the closed waste management facilities in the Bear Creek Regime, including the S-3 Site, Oil Landfarm, and BCBG/WIP, have been inactive since the late 1980s and most of these sites have undergone some level of engineered closure (e.g., installation of multi-layer, low-permeability caps).

2.1.1 S-3 Site

The S-3 Site is located near the headwaters of Bear Creek at the western end of Y-12 (Appendix A, Fig. 2), just west of the groundwater and surface water flow divide between the Bear Creek Regime and the Upper East Fork Regime. The former S-3 Ponds were four contiguous, unlined surface impoundments that were used from 1951 to 1984 for the evaporation/infiltration of several million gallons of nitric acid effluent (with depleted uranium in solution) discharged into the ponds via a pipeline (the Abandoned Nitric Acid Pipeline) connected to process buildings in the central Y-12 area (see Sect. 2.2). Also, acidic liquid wastes containing technetium-99 (Tc-99) that were generated at other DOE facilities periodically were transported to Y-12 for disposal at the S-3 Ponds, which is the only site at Y-12 that received Tc-99 wastes. Closure of the site, initiated in 1988, involved neutralizing and removing the liquid wastes in the ponds and stabilizing the sludge that remained in each pond. The ponds then were filled and covered with a multi-layer, low-permeability cap installed to achieve RCRA final closure performance standards required for hazardous waste landfills. In 1989, an asphalt-paved parking lot was constructed on top of the cap. The TDEC accepted the certification of RCRA final closure of the S-3 Site on November 15, 1990.

2.1.2 Oil Landfarm

The Oil Landfarm HWDU is a component of a waste management area (WMA) in BCV that is located north of Bear Creek, approximately one mile west of Y-12 (Appendix A, Fig. 2). An estimated one million gal of waste oil and machine coolants generated at Y-12 were landfarmed at this HWDU between 1973 and 1982. Landfarming was intended to enhance the biodegradation of these wastes via their application to nutrient-adjusted surface soils during the dry months of the year (April through October). Final closure of the Oil Landfarm HWDU involved the excavation and removal of soils contaminated with polychlorinated biphenyls (PCBs) and the construction of a multi-layer, low-permeability cap (including associated cap drains and stormwater drainage system) installed to achieve RCRA final closure performance standards required for hazardous waste landfills. The TDEC accepted the certification of RCRA final closure of the Oil Landfarm HWDU on November 15, 1990.

Other components of the Oil Landfarm WMA are the Boneyard/Burnyard (BY/BY), the Hazardous Chemical Disposal Area (HCDA), and Sanitary Landfill I (Appendix B, Table 4). These non-RCRA waste management facilities are confirmed or suspected sources of groundwater contamination (see Sect. 3.4.1.2) and currently are regulated under CERCLA.

2.1.3 Bear Creek Burial Grounds/Walk-In Pits

The BCBG/WIP are components of a WMA located in BCV approximately two miles west of Y-12 that encompasses several closed waste disposal sites designated as Burial Grounds (BG)-A North, BG-A South, BG-B, BG-C East, BG-C West, BG-D, BG-E, and BG-J; the WIP; the Uranium Vaults; and the Oil Retention Ponds (No. 1 and No. 2), which were constructed to collect oils seeping from disposal trenches in BG-A South and BG-A North, respectively (Appendix A, Fig. 2). Of these, only BG-A North, BG-A South, BG-C West, and the WIP are RCRA HWDUs; the remaining sites are regulated only under CERCLA (Appendix B, Table 4). The RCRA and non-RCRA waste disposal sites each consist of a series of shallow (i.e., <25 ft below ground surface [bgs]) trenches. These trenches received a diverse mixture of solid wastes (1955 to 1993) and liquid wastes (1959 to 1979) generated at Y-12, including unknown volumes of borax (hydrated sodium borate) waste water, all or most of which may have contained varying amounts of radiological contamination.

Final RCRA closure of BG-A North, BG-A South, and BG-C West involved the construction of multi-layer, low-permeability caps (including associated cap drains and stormwater drainage systems) installed to achieve RCRA final closure performance standards required for hazardous waste landfills. The TDEC accepted the certification of RCRA final closure of these sites on December 15, 1989 (BG-A North and South) and May 17, 1993 (BG-C West).

The WIP and BG-B were closed jointly in 1994 and covered with an engineered concrete revetment mat cap, a gas venting system, and a stormwater drainage system. The TDEC accepted the certification of RCRA final closure of the WIP and BG-B on November 15, 1990.

2.2 UPPER EAST FORK POPLAR CREEK HYDROGEOLOGIC REGIME

The Upper East Fork Regime encompasses the bulk of the Y-12 process and support structures in BCV and, for the purposes of this report, is divided into: (1) the western Y-12 area, defined as the portion of the regime west of Y-12 grid coordinate easting 55,000; (2) the central Y-12 area, defined as the part of the regime between Y-12 grid coordinate eastings 55,000 and 62,000; and (3) the eastern Y-12 area, defined

as the portion of the regime east of Y-12 grid coordinate easting 62,000 (Appendix A, Fig. 3). The PCP for the Upper East Fork Regime defines the RCRA post-closure inspection, maintenance, and monitoring requirements applicable to the Eastern S-3 Site Plume and New Hope Pond.

2.2.1 Eastern S-3 Site Plume

The Eastern S-3 Site Plume is not a TSD unit as defined in the RCRA regulations, but instead is the portion of the subsurface contaminant plume that originates from the S-3 Site (see Sect. 2.1.1) and extends eastward into the western and central Y-12 areas (see Sect. 3.4.2). During operation of the site, a localized mound in the water table created by the infiltrating wastewater facilitated the subsurface transport of inorganic, organic, and radiological contaminants into areas that are east of the topographic and hydrologic divide separating the Upper East Fork Regime and the Bear Creek Regime. These contaminants intermingled in the groundwater with inorganic, organic, and radiological contaminants originating from other sources in the west and central Y-12 areas (Appendix B, Table 5).

2.2.2 New Hope Pond

New Hope Pond is a closed former surface impoundment located at the eastern end of Y-12, south of Lake Reality (Appendix A, Fig. 3). Constructed in 1963, New Hope Pond served to regulate the flow and quality of surface water in Upper East Fork Poplar Creek (UEFPC) until 1988, when it was closed in accordance with a TDEC-approved RCRA closure plan and replaced by Lake Reality. Sediments containing PCBs, mercury, and uranium were periodically removed from New Hope Pond, but testing indicated that the sediments did not exhibit any characteristic of a hazardous waste. Approximately 25,000 yd³ of sediment remained in New Hope Pond when it was closed. Closure of the site involved stabilizing the remaining sediments with coarse aggregate and covering the pond with a multi-layer, low-permeability cap installed to achieve RCRA final closure performance standards required for hazardous waste landfills. The TDEC accepted the certification of RCRA final closure of New Hope Pond on December 15, 1990.

New Hope Pond is not a source of groundwater contamination, and the PCP for the Upper East Fork Regime only defines the RCRA post-closure inspection and maintenance requirements for this site. Under the terms of the PCP, requirements for groundwater monitoring at New Hope Pond, if any, are deferred to the risk-based monitoring requirements to be defined in the applicable CERCLA record of decision (ROD).

2.3 CHESTNUT RIDGE HYDROGEOLOGIC REGIME

The PCP for the Chestnut Ridge Regime defines the requirements for RCRA post-closure inspection, maintenance, and groundwater monitoring at the CRSDB, CRSP, ECRWP, and KHQ, each of which had been granted RCRA interim status by the TDEC. The RCRA interim status periods for the CRSDB, CRSP, and KHQ which ended on the site-specific date that the expired PCP for the regime (see Sect. 1) became effective for the CRSDB (September 18, 1995), CRSP (March 8, 1996), and KHQ (June 11, 1996). The RCRA interim status for the ECRWP ended on the effective date of the new PCP for the Chestnut Ridge Regime (September 29, 2006).

In addition to the RCRA requirements specified in the PCP for the Chestnut Ridge Regime, the CRSDB, CRSP, ECRWP, and KHQ also are regulated under CERCLA. However, post-closure care and/or

groundwater monitoring requirements under CERCLA have not been defined for the CRSDB, CRSP, or ECRWP (DOE 1995a). Also, the final CERCLA ROD for KHQ, which was approved by the U.S. Environmental Protection Agency (EPA) in August 1995, defers groundwater monitoring requirements to the PCP for the Chestnut Ridge Regime (DOE 1995b).

Other non-RCRA waste management facilities are located within the Chestnut Ridge Regime, including both operating and closed non-hazardous solid waste landfills and a couple of CERCLA-regulated facilities (Appendix B, Table 6).

2.3.1 Chestnut Ridge Security Pits

The CRSP are located on the crest of Chestnut Ridge directly south of Y-12 (Appendix A, Fig. 4). This site encompasses two contiguous areas, each of which contains a series of unlined, east-west oriented waste disposal trenches that are about 8 to 10 ft wide, 10 to 18 ft deep, and 700 to 800 ft long. Beginning in 1973, the disposal trenches at the site received a variety of hazardous waste until December 1984 and nonhazardous wastes until the site was closed in November 1988. Closure of the site was completed in 1989 and involved installation of a multi-layer, low-permeability cap (including associated cap drains and stormwater drainage system) designed to achieve RCRA final closure performance standards required for hazardous waste landfills. The TDEC accepted the certification of RCRA final closure of the CRSP on December 15, 1989.

2.3.2 Chestnut Ridge Sediment Disposal Basin

The CRSDB is located on the crest of Chestnut Ridge about 4300 ft east-southeast of the CRSP (Appendix A, Fig. 4). This site was used between 1973 and 1987 for the disposal of contaminated soils and sediments removed from various areas within Y-12. Closure of the site was completed in 1989 and involved installation of a multi-layer, low-permeability cap (including associated cap drains and stormwater drainage system) designed to achieve RCRA final closure performance standards required for hazardous waste landfills. The TDEC accepted the certification of RCRA final closure of the CRSDB on December 15, 1989.

2.3.3 Kerr Hollow Quarry

Located on the southern flank of Chestnut Ridge about 3000 ft directly south of the CRSDB (Appendix A, Fig. 4), KHQ was a source of stone construction material until it filled with water and was abandoned in the late 1940s. From the early 1950s until November 1988, the quarry was used for the disposal of reactive materials from Y-12 and the Oak Ridge National Laboratory (ORNL). Wastes were removed from the quarry between mid-1990 and late 1993 to obtain certified clean-closure status from the TDEC, but the site was finally closed with some wastes remaining in place. The TDEC accepted the certification of RCRA final closure of KHQ on February 22, 1989.

2.3.4 East Chestnut Ridge Waste Pile

Located on the crest of Chestnut Ridge southwest of the eastern end of Y-12 and approximately 1500 ft west of the CRSDB (Appendix A, Fig. 4), the ECRWP forms a vegetated mound at the intersection of

South Patrol Road and East Patrol Road, with grass-covered drainage conveyances on the south, east, and west sides of the site that converge in a storm sewer north of the site.

The ECRWP was constructed in 1986-87 by excavating into the top and northern flank of Chestnut Ridge and installing an impermeable synthetic liner on the bottom and side walls of the excavation. Constructed with a maximum design capacity of 5000 yd³, the ECRWP presently contains approximately 3800 yd³ of wastes (primarily contaminated soil generated from environmental restoration activities at Y-12) capped by 1.0 – 1.5 ft of compacted clay that was covered with top soil and seeded with grass. Plastic sheeting was placed over the site (and weighted down with tires) in August 1990. Large sections of the sheeting deteriorated and, in 1999, the ECRWP was covered with a more durable, scrim-reinforced, 45-mil polypropylene liner with welded seams.

As part of the RCRA final closure of the ECRWP, the above-referenced plastic sheeting and polypropylene liner were removed and replaced with a multi-layer low-permeability cap consisting of (from bottom to top): a minimum of 12 in. of re-compacted clay fill overlain by a geosynthetic clay liner, a textured 40-mil polyethylene geomembrane, and a composite drainage layer and topped with 12 in. soil frost protection layer and 6 in. vegetative soil cover. The TDEC accepted the certification of RCRA final closure of the ECRWP on January 5, 2006.

The bottom and side walls of the ECRWP are sloped to direct rainwater infiltration (leachate) into the northeast quadrant of the site, where a subsurface drainpipe conveys the leachate into a concrete sump with an approximate capacity of 540 gal. Whenever a sufficient volume of leachate has accumulated in the sump (typically when the sump is judged to be approximately 75% full), the contents of the sump are pumped into a portable container and transported to the designated treatment/disposal facility. The PCP for the Chestnut Ridge Regime defines the requirements for the management (including periodic sampling and analysis) of leachate from the ECRWP (see Sect. 6).

3. HYDROGEOLOGIC FRAMEWORK

The following overview of the hydrogeologic framework in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime provides the context for the RCRA post-closure groundwater monitoring programs performed at the applicable TSD units addressed by the respective PCP for each regime. Included are brief discussions of the topography and bedrock geology (Sect. 3.1), surface water drainage (Sect. 3.2), groundwater flow system (Sect. 3.3), and the extent of groundwater contamination (Sect. 3.4).

3.1 TOPOGRAPHY AND BEDROCK GEOLOGY

Y-12 is located within the Valley and Ridge Physiographic Province, which is generally characterized by extensively folded and thrust-faulted bedrock that forms an imbricate series of northeast-southwest oriented valleys, often underlain by shale, and steep-sided ridges formed by more resistant carbonates and sandstones. The following overview of local topography and bedrock geology reflects the fact that the Bear Creek and Upper East Fork regimes share a common hydrogeologic system in BCV that has distinctively different hydrologic characteristics than evident in the Chestnut Ridge Regime.

3.1.1 Bear Creek Valley

As noted previously, the Bear Creek Regime encompasses a section of BCV west of Y-12 that historically has been used for waste management purposes (Appendix A, Fig. 5), whereas the Upper East Fork Regime encompasses the section of BCV that contains the bulk of the historical and current operations and process facilities at Y-12 (Appendix A, Fig. 6). Bear Creek Valley is bound to the north by Pine Ridge and to the south by Chestnut Ridge, and the valley floor slopes gently to the east and west of a low topographic divide located near the west end of Y-12. Surface elevations range from 900 ft above mean sea level (msl) along the floor of BCV to about 1200 ft above msl along the crests of Pine Ridge and Chestnut Ridge.

Up to 50 ft of several unconsolidated materials, including man-made fill, alluvium, colluvium, fine-grained residuum from the weathering of the bedrock, and saprolite (highly weathered bedrock) overlie the bedrock formations that form BCV. Also, much of BCV within the Upper East Fork Regime contains extensive cut-and-fill areas associated with the construction of the process and support facilities that comprise Y-12 (Appendix A, Fig. 3). Most of the fill material, which generally consists of a heterogeneous mixture of building debris and recompacted soil/residuum that contains numerous voids, was placed within the tributaries and main channel of UEFPC (Lockheed Martin Energy Systems, Inc. [Energy Systems] 1995a).

Bedrock in BCV consists of the following shale and limestone formations of the Conasauga Group (listed in order from oldest to youngest): Pumpkin Valley Shale, Rutledge Limestone, Rogersville Shale, Maryville Limestone, Nolichucky Shale, and Maynardville Limestone (Appendix A, Figs. 5 and 6). The Maynardville Limestone subcrops along the axis of BCV at the base of the steep northern (scarp) flank of Chestnut Ridge, with the remaining formations subcropping progressively to the north toward Pine Ridge. The strike (trend) and dip (inclination) of bedding is generally N55°E and 45°SE, respectively (as referenced to true north).

3.1.2 Chestnut Ridge

As noted previously, the Chestnut Ridge Regime encompasses a section of Chestnut Ridge directly south of Y-12. The northern flank of the ridge forms a steep slope rising more than 200 ft above the floor of BCV. The ridge crest slopes east-northeast from an elevation of about 1200 ft above msl southwest of Y-12 to about 1060 ft above msl east of the CRSDB (Appendix A, Fig. 7). A series of prominent hills dominates the central part of the broad southern flank of Chestnut Ridge, which is dissected by several tributary systems.

Bedrock on Chestnut Ridge is overlain by up to 100 ft of red-brown to yellow-orange residuum composed primarily of clays and iron sesquioxides. The residuum contains semi-continuous, relict beds of fractured chert and other lithologic inhomogeneities (such as silt bodies) that provide a weakly connected network through which saturated flow can occur (Energy Systems 1992a). The residuum is thin or nonexistent near karst features such as dolines (sink holes), swallets (sinking streams), and solution pan features and is thickest (>100 ft) along the crest of Chestnut Ridge (Energy Systems 1984).

Chestnut Ridge is formed by the carbonate strata of the Knox Group, which stratigraphically overlies the Conasauga Group in BCV. The Knox Group consists of about 2600 to 3300 ft of gray to blue-gray, thin- to thick-bedded cherty dolostone with interbedded limestone and is divided into the following five formations (listed from oldest to youngest): Copper Ridge Dolomite, Chepultepec Dolomite, Longview Dolomite, Kingsport Formation, and Mascot Dolomite (Appendix A, Fig. 7). Topographic features and

stratigraphic relationships suggest that the Copper Ridge Dolomite underlies the steep northern flank of the ridge, the Longview Dolomite forms the series of prominent hills across the middle of the southern flank of the ridge, and the Mascot Dolomite disconformably underlies the Chickamauga Group in Bethel Valley to the south (Energy Systems 1992a). As in BCV, strike and dip of bedding is generally N55°E and 45°SE, respectively (as referenced to true north).

3.2 SURFACE DRAINAGE

Bear Creek and UEFPC are the primary surface water drainage features in BCV. Bear Creek drains the sections of the valley, including all of the waste management facilities in the Bear Creek Regime, west of the topographic divide at the western end of Y-12. The section of BCV to the east of the divide, which includes the bulk of the heavily industrialized areas within Y-12, is drained by UEFPC. In the Chestnut Ridge Regime, surface runoff is drained by several named and un-named tributaries that traverse generally north-south across the southern flank of the ridge.

3.2.1 Bear Creek

From its headwaters near the western end of Y-12, Bear Creek flows southwest for approximately 4.5 miles, where it turns northward to flow into East Fork Poplar Creek. Monitoring locations along the main channel of Bear Creek are specified by the Bear Creek kilometer (BCK) value corresponding to the distance upstream from the confluence with East Fork Poplar Creek (e.g., BCK-09.40). Sections of the main channel are referenced as upper Bear Creek (upstream of BCK-11.97), middle Bear Creek (between BCK-11.97 and BCK-09.40), and lower Bear Creek (downstream of BCK-09.40). For reference purposes, each northern tributary (NT) of the creek is designated with a value representing the tributary number counted downstream from the headwaters (e.g., NT-3). Major springs along the southern side of Bear Creek are numbered in ascending order from the headwaters (e.g., SS-1).

Approximately half of the annual precipitation in BCV exits via surface water flow in Bear Creek, and possibly higher proportions exit during winter and early spring (DOE 1997). Flow in the creek increases rapidly during rainfall and afterward reflects the relative contributions of overland flow, stormflow, and groundwater discharge. Flow in the main channel and tributaries generally returns to pre-precipitation levels within one or two days. Major sections of upper and middle Bear Creek are seasonally dry, but flow is perennial in lower Bear Creek.

The main channel of Bear Creek functions as a major conduit of the shallow karst network within the Maynardville Limestone. Discharge from numerous springs located along the Maynardville Limestone/Copper Ridge Dolomite boundary on the northern slope of Chestnut Ridge dominate the hydrology of the creek, especially during droughts when they provide most of the flow in the main channel. Additionally, the main channel contains alternating gaining and losing reaches. Each gaining reach generally correlates with a major groundwater discharge area. Losing reaches in upper and middle Bear Creek, particularly a section of the main channel directly south of Sanitary Landfill I, play an important role in transferring contaminants from Bear Creek to the groundwater flow system (DOE 1997).

3.2.2 Upper East Fork Poplar Creek

Construction of the operations and support facilities at Y-12 substantially altered UEFPC. The headwaters and several thousand feet of the main channel in the upper reach of the creek, including all the northern tributaries of the creek in the western and central Y-12 areas, were filled and replaced with an extensive network of underground storm drains (Appendix A, Fig. 3). For reference purposes, each buried tributary (BT) of UEFPC is designated with a value representing the tributary number counted downstream from the headwaters (e.g., BT-1).

The underground network of storm drains in the western and central Y-12 areas directs surface runoff into the exposed portion of the UEFPC channel at Outfall 200 located approximately 6000 ft upstream of Lake Reality (Appendix A, Fig. 3). Constructed to replace New Hope Pond, Lake Reality is a lined surface impoundment that serves to help regulate the flow and quality of surface water exiting Y-12 through UEFPC. During normal operations, flow in UEFPC currently bypasses Lake Reality via a siphon system that has operated since December 1996; only a portion of the flow following heavy rainstorms passes through Lake Reality. Bypassing Lake Reality reduces mercury contributions to dry-weather flow in UEFPC.

The bulk (70%) of dry-weather flow in UEFPC, excluding flow management discussed below, is attributable to once-through noncontact cooling water, condensate, and cooling tower blowdown, and the remaining 30% is from groundwater discharge (Energy Systems 1994a). Beginning in July 1996, untreated water from the Clinch River has been discharged near Outfall 200 to augment flow in UEFPC, which decreased from 10-15 mil gallons per day (gpd) to about 2.5 mil gpd because of reduced operations at Y-12. Flow management is needed to achieve the National Pollutant Discharge Elimination System (NPDES) minimum daily flow requirement of 7 mil gpd at Station 17, where UEFPC exits the DOE Oak Ridge Reservation (ORR) downstream of Lake Reality (Appendix A, Fig. 3). Flow management also allows compliance with NPDES toxicity requirements and helps lower the otherwise elevated water temperature in UEFPC.

3.2.3 Chestnut Ridge

Surface streams in the Chestnut Ridge Regime include four primary drainage basins on the southern flank of Chestnut Ridge: Dunaway Branch and an unnamed tributary located east of Industrial Landfill II in the western part of the regime; the McCoy Branch drainage basin in the central part of the regime; and an unnamed drainage basin in the eastern part of the regime (Appendix A, Fig. 7). These tributaries are mainly intermittent above an elevation of 900 ft above msl and receive flow via surface runoff, stormflow discharge, and groundwater baseflow. Baseflow contributions increase downstream along the length of the streams, and spring discharge provides substantial contributions to the total flow in most of the tributaries. All of the tributaries discharge into Melton Hill Reservoir (Clinch River) south of the Chestnut Ridge Regime.

3.3 GROUNDWATER SYSTEM

3.3.1 Bear Creek Valley

There are two basic hydrogeologic units in BCV: (1) the Aquifer, consisting of the Maynardville Limestone (upper Conasauga Group) and Copper Ridge Dolomite (lower Knox Group); and (2) the

Aquitard, consisting of the remaining Conasauga Group formations and the underlying Rome Formation (Energy Systems 1992a). The Aquitard is the uppermost aquifer at the each of the TSD units addressed in the PCP for the Bear Creek Regime (S-3 Site, Oil Landfarm, BCBG/WIP), as well as the Eastern S-3 Site Plume in the Upper East Fork Regime. In both regimes, the Aquitard is hydraulically upgradient of the Aquifer, which functions as a hydrologic drain in BCBV. Fractures provide the principal groundwater flowpaths in both units, and dissolution of carbonates in the Aquifer has enlarged fractures and created solution cavities and conduits that greatly enhance its hydraulic conductivity relative to the Aquitard. Although negligible in both units, flow through the porous rock matrix plays an important role in contaminant migration because of matrix diffusion processes (Energy Systems 1992a).

Groundwater flow in the Aquitard and the Aquifer primarily occurs in directions that parallel the strike and dip of bedding, which in the Aquitard may or may not coincide with the direction of maximum hydraulic gradient inferred from water level isopleths. Flow across bedding occurs primarily along permeable zones formed by cross-cutting fractures or fracture zones (and possibly small faults). The northern tributaries of Bear Creek are probably the surface expression of these cross-cutting structures in the bedrock. Such structures provide preferred flowpaths that channel groundwater from the Aquitard to the Aquifer or act as barriers to lateral flow, causing groundwater from deeper intervals to upwell and discharge to the shallower flow system in each hydrogeologic unit (DOE 1997). In the Aquitard, most groundwater flow occurs in a highly permeable interval near the bedrock/residuum interface (the water table interval) and decreases substantially at depths more than 100 ft bgs, where upward hydraulic gradients predominate (DOE 1997). In the Aquifer, most groundwater flow occurs at shallow depths (i.e., <100 ft bgs) in an extensively interconnected network of solution conduits and cavities (karst network). Active groundwater circulation occurs at greater depth than in the Aquitard and, in the Bear Creek Regime west of Y-12, groundwater from the deeper flow system discharges along major gaining (influent) reaches of Bear Creek. These discharge areas are probably related to large-scale structural (e.g., cross-strike faults) or stratigraphic discontinuities in the Maynardville Limestone (DOE 1997).

The water table in the Bear Creek Regime (Appendix A, Fig. 8) and in the Upper East Fork Regime (Appendix A, Fig. 9) is a subdued replica of the ground surface in each regime, with steep gradients along the flanks of Pine Ridge and Chestnut Ridge and a gentle slope down the axis of BCBV toward the west in the Bear Creek Regime and toward the east in the Upper East Fork Regime. Horizontal hydraulic gradients are typically less than 0.05 across BCBV (strike-normal) in the Aquitard and are usually near 0.01 along the axis of BCBV (strike-parallel) in the Aquifer (Maynardville Limestone). Static water level data for several two- and three-well clusters indicate that vertical hydraulic gradients are predominately downward in the Aquifer and upward in the Aquitard, and they often reverse in response to seasonal (or episodic) groundwater flow conditions.

Local groundwater flow patterns in both the Aquitard and Aquifer throughout much of the Upper East Fork Regime are strongly influenced by the numerous industrial, process, and support buildings and structures and the extensive network of buried utilities, sumps, storm drains, sanitary sewers, and process lines. In the western Y-12 area, for instance, operation of sumps to suppress the local water table below the basement floors of Bldgs. 9204-4, 9201-5, and 9201-4 (Appendix A, Fig. 9) strongly influences local groundwater flow and contaminant transport patterns in both the shallow and deeper flow system in the Aquitard (DOE 1998). Similarly, in the eastern Y-12 area, groundwater flow directions at shallow depths in the Aquifer (Maynardville Limestone) are strongly influenced by the UEFPC distribution channel underdrain, which apparently functions as a highly permeable groundwater flow path and a constant head (recharge) boundary (BJC 1998). Additionally, operation of the Lake Reality Sump, which is a 6-ft diameter, 20-ft deep sump installed to reduce hydraulic pressure on the synthetic liner in Lake Reality, creates an elongated cone of depression in the Aquitard (Nolichucky Shale) oriented parallel with strike and decreases water levels in the Aquifer (Maynardville Limestone) along the main channel of UEFPC.

The sump is activated manually as required (very infrequently) to reduce pressure head and stop liner flotation. Once activated, the sump pump operates on an automatic level switch.

Complex local groundwater flow patterns in the Aquifer at the eastern end of Y-12 are indicated by the water level drawdown and recovery data obtained during aquifer pumping tests performed in July 1998, which showed: (1) rapid, large responses in wells located along strike to the east and across strike to the north of the pumping well (well GW-845); (2) more moderate responses in wells located oblique to strike near the contact with the Nolichucky Shale to the east of the pumping well; (3) weak responses in upgradient wells in the Maynardville Limestone to the west of the pumping well; and (4) little if any response in wells located adjacent to Lake Reality and the UEFPC distribution channel underdrain to the north and northwest of the pumping well. The maximum observed radius of influence from the pumping well encompassed the entire subcrop of the Maynardville Limestone in the eastern Y-12 area, with particularly strong anisotropies to the east (along strike) and north (up-dip) of the well and low-permeability boundary effects evident along the contact with the Nolichucky Shale. Additionally, the UEFPC distribution channel underdrain, the original UEFPC mainstem, and Lake Reality apparently represent constant head (recharge) sources to the shallow groundwater and may collectively function as a hydraulic boundary to the west and northwest of New Hope Pond. The UEFPC distribution channel underdrain in particular appears to function as a separate hydraulic system that may be connected to surface water flow in UEFPC (BJC 1998).

3.3.2 Chestnut Ridge

The principal hydrogeologic unit in the Chestnut Ridge Regime is the Knox Aquifer, which is comprised of the Knox Group and the underlying Maynardville Limestone formation of the Conasauga Group. The Knox Aquifer is the uppermost aquifer at the CRSDB, CRSP, ECRWP, and KHQ and generally consists of three vertically gradational subsystems: the stormflow zone, the vadose zone, and the groundwater zone. The subsystems are distinguished by groundwater flux, which decreases with depth (Energy Systems 1992a).

Although detailed studies have not been performed in the Chestnut Ridge Regime, investigations in Bethel Valley and Melton Valley near ORNL show that groundwater occurs intermittently above the water table in a shallow "stormflow zone" that extends to a depth of about 6 ft bgs (Energy Systems 1989a). Macropores and mesopores provide the primary channels for lateral flow in the stormflow zone, which lasts only a few days or weeks after rainfall. Most groundwater within the stormflow zone is either lost to evapotranspiration or recharge to the water table, and the remaining water discharges at nearby seeps, springs, or streams (Energy Systems 1989a).

The vadose zone occurs between the stormflow zone and the water table, which typically occurs near the bedrock/residuum interface. The vadose zone is unsaturated except in the capillary fringe above the water table and within wetting fronts during periods of vertical percolation from the stormflow zone (Energy Systems 1989a). Most recharge through the vadose zone is episodic and occurs along discrete permeable fractures that become saturated, although surrounding micropores remain unsaturated (Energy Systems 1992a).

Groundwater below the vadose zone occurs within orthogonal sets of permeable, planar fractures that form water-producing zones within an essentially impermeable matrix. Dissolution of bedrock carbonates has enlarged fractures and produced an interconnected conduit-flow system characteristic of karst aquifers. Because the occurrence of solution features and the frequency, aperture, and connectivity of permeable fractures decrease with depth, the bulk hydraulic conductivity of the groundwater zone is

vertically gradational. Most groundwater flux occurs within the transitional horizon between residuum and unweathered bedrock (water table interval); lower flux (and longer solute residence times) occurs at successively greater depths in the bedrock (Energy Systems 1992a).

The water table in the Chestnut Ridge Regime is a subdued replica of surface topography and occurs at the greatest depth (>100 ft bgs) along the crest of Chestnut Ridge, which is a groundwater flow divide and a recharge area. In the northern part of the regime, groundwater generally flows from west to east, parallel to the flow divide along the ridge crest, with radial components of flow north into BCV and south toward tributary headwaters on the southern flank of the ridge (Appendix A, Fig. 10). The central part of the regime is characterized by radial flow directions from local groundwater flow divides along hilltops between tributaries. Groundwater flow directions in the southern part of the regime are generally south toward Melton Hill Reservoir. The overall directions of groundwater flow throughout the Chestnut Ridge Regime do not significantly change during seasonal groundwater flow conditions. Seasonal horizontal hydraulic gradients are highest along the steep northern flank of Chestnut Ridge (i.e., across geologic strike) and in the upper reaches of tributaries on the southern ridge flank, but are nearly flat along the southern boundary of the regime.

3.4 GROUNDWATER CONTAMINATION

3.4.1 Bear Creek Hydrogeologic Regime

There are numerous sources of groundwater contamination in the Bear Creek Regime (Appendix B, Table 4), most of which are directly underlain by the low-permeability formations that comprise the Aquitard. The principal groundwater contaminants are inorganic compounds (primarily nitrate); trace metals (notably uranium); volatile organic compounds (VOCs), including chlorinated solvents and petroleum hydrocarbons; and several radionuclides, chiefly Tc-99 and uranium isotopes. Mobile contaminants from the various source areas are transported toward the Aquifer (Maynardville Limestone). In the Aquifer, intermingling of contaminants from multiple source areas has produced an essentially continuous groundwater contaminant plume of varying composition that extends from the western end of Y-12 to the western (downgradient) boundary of the BCBG WMA (Appendix A, Fig. 11). The following subsections describe the extent of contamination originating from the primary source areas in the Bear Creek Regime (the S-3 Site, the Oil Landfarm WMA, and the BCBG WMA) and the principal contaminant migration pathway (the Maynardville Limestone and Bear Creek) in the regime.

3.4.1.1 S-3 Site

Operation of the former S-3 Ponds emplaced a large reservoir of contamination in the Aquitard (Nolichucky Shale) containing a heterogeneous mix of inorganic, organic, and radioactive constituents. The principal groundwater contaminants are: nitrate; Tc-99 and uranium isotopes (primarily U-234 and U-238); several trace metals, which is the term used hereafter to differentiate metals that are typically minor constituents in groundwater (e.g., cadmium) from metals that are usually major ionic species (e.g., magnesium); and VOCs. Contaminant concentrations in the Aquitard nearest the site substantially exceed the applicable state or federal maximum contaminant level (MCL) established under the Safe Drinking Water Act (SDWA) of 1974. Also, the concentrations of most contaminants have probably achieved maximum levels and are expected to decrease as the center of mass of the plume slowly moves westward via strike-parallel groundwater flow/transport pathways in the Aquitard. Westward migration of

contaminants in the Aquitard occurs until they encounter a cross-cutting structure that promotes upward discharge into the shallow flow system, or cross-strike flow into the Aquifer (DOE 1997).

As indicated by the distribution of nitrate, which is a highly mobile and chemically stable contaminant that delineates the maximum extent of groundwater transport and effectively traces the principal migration pathways, the S-3 Site contaminant plume in the Aquitard west of Y-12 extends south toward the upper reach of Bear Creek and westward along strike in the water table interval (and the deeper bedrock) toward discharge areas in NT-1 and NT-2 (Appendix A, Fig. 11). Nitrate (as N) concentrations (hereafter synonymous with "nitrate" concentrations) within the plume exceed 10,000 milligrams per liter (mg/L) in the deep bedrock directly below the S-3 Site, 1000 mg/L in the shallow groundwater near the site, and 10 mg/L near the plume boundaries.

Radiological contaminants within the S-3 Site contaminant plume include both alpha- and beta-particle emitting radionuclides, including americium-241 (Am-241), neptunium-237 (Np-237), radium, and strontium-90 (Sr-90), but uranium isotopes (U-234 and U-238) and Tc-99 are the principal radiological contaminants. The highest levels of gross alpha activity within the plume exceed 1000 picoCuries per liter (pCi/L) and generally occur within the acidic groundwater nearest the S-3 Site, and the levels decrease rapidly in the more neutral pH groundwater encountered farther from the site. In contrast, substantially higher levels of gross beta activity (>10,000 pCi/L), which is primarily from Tc-99, dominates the other radiological contaminants within the plume. Under oxidizing conditions, Tc-99 occurs as the pertechnetate anion (TcO_4^-), which is soluble and highly mobile in the subsurface (Gee et al. 1983). Based on the distribution of elevated gross beta activity indicated by the current network of monitoring wells in BCV, the transport of Tc-99 in the groundwater appears to be similar to that of nitrate from the S-3 Site.

Lesser components of the S-3 Site contaminant plume are trace metals and VOCs. Some of the trace metals (e.g., uranium) were entrained in the acidic wastes disposed at the site, and others (e.g., barium) were dissolved from the underlying saprolite and bedrock minerals. Also, the distribution of trace metals is less extensive than that of nitrate and radioactivity, but the most mobile metals within the plume (e.g., barium) have been transported beyond the acidic groundwater (pH <5) nearest the site. Acetone and tetrachloroethene (PCE) are the principal VOCs within the plume. Very high PCE concentrations in wells adjacent to the site, which exceed 5000 micrograms per liter ($\mu\text{g/L}$), potentially indicate the presence of PCE as dense nonaqueous phase liquid (DNAPL) in the subsurface. Nevertheless, summed concentrations of dissolved VOCs in the groundwater only 500 ft downgradient of the site are less than 50 $\mu\text{g/L}$.

The S-3 Site contains varying amounts of sludge produced by denitrification of the wastewater during closure of the former S-3 Ponds. Sludge within the saturated zone may release Tc-99 and uranium isotopes to the shallow groundwater flow system in the Aquitard and may be transported westward through the water table interval toward discharge points in NT-1 (DOE 1997). Additionally, matrix diffusion and advective transport processes are slowly releasing contaminants (e.g., nitrate) from the deeper reservoir into the more active (shallow) Aquitard flow system.

3.4.1.2 Oil Landfarm Waste Management Area

The primary sources of groundwater contaminants in the Oil Landfarm WMA (listed in order of importance) are the BY/BY, the HCDA, the Oil Landfarm HWDU, and Sanitary Landfill I. Each site is a confirmed or suspected source of VOCs in the shallow groundwater, and the BY/BY was a major source of elemental uranium and alpha activity.

The Boneyard was used for the disposal of magnesium chips and construction debris (e.g., concrete) in unlined shallow trenches. Filled trenches were covered with topsoil and seeded with grass. The Burnyard consisted of two unlined trenches, each about 300 ft long by 40 ft wide, in which various types of refuse (including pesticide containers, metal shavings, solvents, oils, and laboratory chemicals) were burned. Waste materials containing high concentrations of uranium were within the saturated zone during seasonally high groundwater levels. Results of the CERCLA remedial investigation (RI) for the Bear Creek characterization area (CA) indicated that uranium isotopes leached from the wastes move with the shallow groundwater and discharge into NT-3, which drains the site, and recharges directly into the Maynardville Limestone (DOE 1997). Uranium isotopes from the BY/BY were the suspected source of the elevated levels (>1000 pCi/L) of gross alpha and gross beta activity in the shallow groundwater along NT-3, and the site was prioritized for CERCLA remedial action. Remedial action field work completed in November 2001 primarily involved construction of an upgradient subsurface drain to hydraulically isolate the buried wastes at the site in order to reduce the flux of contaminants from the site and to dry the site in preparation for the excavation, disposal, and consolidation of the wastes. Approximately 64,000 yd³ of waste materials with the highest concentrations of uranium that were in contact with groundwater were removed from the site by October 2002. These wastes were disposed in the EMWMF. Approximately 17,000 yd³ of other waste materials that had lower levels of uranium contamination and were not in contact with groundwater also were excavated, consolidated onsite, and covered with a low-permeability recompacted clay cap. Installation of the cap, including seeding/mulching the topsoil cover, was completed in November 2002. Additionally, field work to restore the NT-3 stream channel with natural meanders and gradients in order to reduce erosion of the bank and more efficiently transport water and sediment load through the BY/BY was completed in May 2003.

The HCDA was constructed on top of the Burnyard in 1975 and was used as an area for releasing compressed gas from cylinders with leaking or damaged valves and for disposal of reactive or explosive laboratory chemicals. The chemicals were handled to induce the expected reaction or explosion, and remaining liquids were discharged into a small unlined surface impoundment. A low permeability cap was constructed over the HCDA during closure of the Oil Landfarm HWDU. In June 2002, a section of the northwestern corner of the cap was excavated and removed during the CERCLA remedial action at the BY/BY. Excavated wastes were replaced with uncontaminated soil, and the filled area was graded to drain, mulched, and seeded with grass. The HCDA is the suspected source of a dissolved VOC plume in the shallow groundwater. Primary components of the plume are trichloroethene (TCE), cis-1,2-dichloroethene (c12DCE), and PCE. Maximum concentrations of these VOCs are less than one percent of solubility, indicating that DNAPLs are probably not present in the subsurface. The HCDA is most likely the principal source of the plume considering the distribution of VOCs relative to the radioactivity plume originating from the BY/BY (Appendix A, Fig. 11).

The primary groundwater contaminants at the Oil Landfarm HWDU are VOCs. The plume of VOCs in the groundwater contains two distinct suites of VOCs, one dominated by 1,1,1-trichloroethane (111TCA), 1,1-dichloroethane (11DCA), and 1,1-dichloroethene (11DCE) near the northeastern landfarm plots, and one dominated by PCE, c12DCE, trans-1,2-dichloroethene (t12DCE), and TCE near the southern landfarm plots. The primary VOCs in the plume are 111TCA and PCE. Both of these parent compounds are components of wastes that were landfarmed in each area, but the other VOCs in the groundwater may be present as degradation products of 111TCA (11DCA and 11DCE) and PCE (TCE and c12DCE). Although historical data show that summed VOC concentrations exceed 1000 µg/L in the northeastern part of the plume and 100 µg/L in the southern part of the plume, the maximum concentrations of individual plume constituents do not indicate the presence of DNAPLs in the subsurface (DOE 1997).

Sanitary Landfill I was used between 1968 and 1980 for disposal of combustible and decomposable solid wastes from Y-12, some of which may have included toxic chemicals. Disposal trenches at the landfill

were excavated to depths of about 20 ft bgs and backfilled to about 15 ft above grade. The landfill was graded and capped in 1985. This landfill is an unverified potential source of 11DCA, c12DCE, and t12DCE in the shallow groundwater (Aquitard and Aquifer) downgradient to the south and west of the site (Appendix A, Fig. 11). Maximum concentrations of these VOCs are typically less than 50 µg/L. In the Aquifer (Maynardville Limestone), these constituents have intermingled with VOCs (primarily TCE and c12DCE) originating from upgradient sources. Additionally, unusually high boron levels in the groundwater at several wells immediately downgradient (west) of the site also may be attributable to contaminant migrations from Sanitary Landfill I (DOE 1997).

3.4.1.3 Bear Creek Burial Grounds Waste Management Area

Groundwater in the Aquitard underlying the BCBG WMA is extensively contaminated with VOCs at both shallow (water table) and deep (bedrock) intervals (Appendix A, Fig. 11). There are five primary source areas: BG-A (North and South), BG-C (East and West), and the WIP. Dissolved VOC plumes in the shallow groundwater at several of these source areas are probably related to widespread occurrence of DNAPLs in the subsurface. Contamination in the deeper groundwater flow system reflects density-driven, downward migration of DNAPLs (DOE 1997).

The disposal trenches comprising BG-A (North and South) received almost two million gallons of waste oils and coolants, and DNAPLs have been encountered in monitoring wells down dip (south-southwest) of source trenches in BG-A South. Dissolved VOC plumes in the groundwater underlying both areas are dominated by PCE, TCE, and c12DCE. Other common plume constituents are 111TCA, 11DCA, and 1,2-dichloroethane (12DCA). Summed concentrations of these plume constituents exceed 100,000 µg/L. Groundwater in the water table interval transports the plume constituents along strike toward discharge areas in NT-7. Westward, strike-parallel migration also occurs below the water table interval, as indicated by PCE results for deeper bedrock wells at BG-A South (DOE 1997).

Separate plumes of dissolved VOCs apparently occur in the shallow groundwater at BG-C East and BG-C West, each plume dominated by c12DCE with lesser amounts of vinyl chloride (VC). Concentrations of VOCs within the plume are generally less than 500 µg/L. Groundwater containing these VOCs discharges to the NT-8 catchment on the northwestern side of BCBG WMA. Data for both source areas do not clearly indicate the presence of DNAPLs in the subsurface (DOE 1997).

Groundwater near the WIP contains a distinct plume of dissolved VOCs dominated by PCE. Concentrations exceed 2000 µg/L, which is about 1% of the maximum PCE solubility and possibly indicates DNAPLs in the subsurface. Contaminants in the shallow groundwater flow system may not discharge extensively to surface water (DOE 1997).

Although large quantities of uranium wastes were disposed in the BCBG WMA, few monitoring wells in the area yield radioactive groundwater samples (Appendix A, Fig. 11). However, analytical data for soil samples and surface water samples collected from Bear Creek tributaries NT-6, NT-7, and NT-8 indicate that BG-A South and BG-C East are probable sources of radioactivity (DOE 1998). Maximum gross alpha and gross beta activities in the samples from these tributaries ranged from about 20 pCi/L to more than 100 pCi/L. The disparity with the groundwater sample data may be an artifact of the monitoring well network (few wells are screened within the shallowest water table interval where radioactive contamination likely occurs), but the relatively low levels of radioactivity in the groundwater also suggest that the bulk of the uranium wastes in BG-A South and BG-C East are not within the saturated zone (DOE 1997).

Boron is the primary trace metal contaminant in the groundwater at the BCBG WMA. Elevated boron concentrations occur primarily in the shallow groundwater near BG-A South and BG-C (East and West) and probably resulted from disposal of borax wastewaters from Y-12. Boron is most likely present in the groundwater as borate $[B(OH)_3]$, which is chemically stable and relatively mobile, and is transported toward discharge points in Bear Creek tributaries NT-7 and NT-8.

3.4.1.4 Maynardville Limestone Exit Pathway

In the Bear Creek Regime, the principal groundwater contaminants in the Maynardville Limestone are nitrate, VOCs, radioactivity, and trace metals. These contaminants primarily originate from the S-3 Site (nitrate, trace metals, and radionuclides), the BY/BY (uranium isotopes), the HCDA (VOCs), Sanitary Landfill I (VOCs), the BCBG WMA (VOCs and radionuclides), and the Rust Spoil Area (VOCs) or a nearby unidentified VOC source area in the Bear Creek floodplain (DOE 1997). These contaminants enter the Maynardville Limestone through direct recharge, hydrologic communication with surface water in Bear Creek, and inflow of shallow groundwater from the Aquitard. Relative contributions from the source areas and the geochemical characteristics of the contaminants have produced two primary plumes of contamination in the groundwater: one containing nitrate and radioactivity, and another containing VOCs. These plumes occur in both the shallow karst network and the deeper fracture flowpaths and are commingled downgradient of the BY/BY and HCDA. Trace metal contaminants are more sporadically distributed and chiefly occur close to the primary source areas.

The nitrate plume in the Maynardville Limestone essentially delineates the maximum extent of contaminant transport in the Bear Creek Regime and effectively traces the primary migration pathways (Appendix A, Fig. 11). The plume is continuous in the deeper bedrock from south of the S-3 Site for about 10,000 ft along strike to the west, whereas attenuation from more active recharge and groundwater flux has reduced nitrate levels and produced a more discontinuous plume in the shallow karst network (DOE 1997). Nitrate concentrations within the plume exceed 500 mg/L south of the S-3 Site, but rapidly decrease to less than 50 mg/L south of the Oil Landfarm WMA, and are typically highest in the fracture-dominated groundwater flow system at depths greater than 100 ft bgs.

The distribution of VOCs in the Maynardville Limestone reflects the relative contributions of several source areas and commingling during downgradient transport (Appendix A, Fig. 11). Plume constituents in the upper part of BCBV are TCE, c12DCE, and PCE. Probable source areas are Spoil Area I, the S-3 Site, and possibly the Fire Training Facility located in the Upper East Fork Poplar Creek Hydrogeologic Regime. Major inputs to the plume occur from the Rust Spoil Area (TCE) or a nearby source in the Bear Creek floodplain, the Oil Landfarm HWDU and/or HCDA (TCE and c12DCE), Sanitary Landfill I (111TCA and 11DCA), and discharge from the Bear Creek tributary (NT-7) that traverses BG-A North and A South (c12DCE and 12DCA). The highest concentrations within the plume (i.e., >300 µg/L) occur in the deeper groundwater south (down dip) of the BY/BY. These high concentrations coincide with the downward vertical hydraulic gradients in the Maynardville Limestone in this area and the major losing reach of middle Bear Creek south of Sanitary Landfill I.

Radioactivity in the groundwater in the Maynardville Limestone is primarily from uranium isotopes and Tc-99. The extent of these radionuclides is generally delineated by gross alpha activity and gross beta activity, respectively. The distribution of gross beta activity mirrors that of nitrate, indicating a common source of nitrate and Tc-99 (the S-3 Site), migration along common flowpaths, and similar transport characteristics in the groundwater (Appendix A, Fig. 11). The sharply increased levels of gross alpha activity in the groundwater downstream (west-southwest) of NT-3 reflect the inflow of uranium isotopes from former sources in the former BY/BY (DOE 1997).

Most trace metal contamination in the Maynardville Limestone occurs in the shallow groundwater near the S-3 Site and the BY/BY. Near the S-3 Site, the principal trace metal contaminants are barium, boron, cadmium, copper, lead, mercury, strontium, and uranium. Some of these metals (e.g., cadmium) were entrained in the highly acidic wastes disposed at the site, and others (e.g., strontium) were dissolved from the underlying bedrock. Trace metal contamination is sporadic in the groundwater at the BY/BY, and the principal contaminants are beryllium, manganese, mercury, nickel, and uranium (DOE 1997). Boron and uranium are the most common trace metal contaminants in the Aquifer downgradient of the S-3 Site and BY/BY, which indicates that relatively mobile, ionic species of both metals are present in the groundwater.

3.4.2 Upper East Fork Poplar Creek Hydrogeologic Regime

Results of several investigations of subsurface contamination in the Upper East Fork Regime, including findings of the CERCLA RI for the UEFPC CA (DOE 1998), show that the principal groundwater contaminants in the regime are: nitrate; trace metals (notably uranium); VOCs, including chlorinated solvents and petroleum hydrocarbons; and several radionuclides, chiefly Tc-99 and uranium isotopes.

A plume of nitrate contamination originating from the former S-3 Ponds extends vertically in the Aquitard at least 150 ft bgs and laterally at least 5000 ft into the western Y-12 area (Appendix A, Fig. 12). Nitrate concentrations within the plume exceed 10,000 mg/L. As noted previously, nitrate is chemically stable and highly mobile in groundwater, and the elevated levels probably delineate the overall migration pattern for other similarly mobile groundwater contaminants from the former S-3 Ponds. Moreover, the geometry of the nitrate plume indicated by monitoring results for the network of wells located east-southeast of the site suggests two principal migration pathways: (1) relatively rapid migration along fairly short, shallow pathways (<30 ft bgs) that typically terminate in storm drains or other utilities, building sumps, and the buried tributaries and original mainstem of UEFPC; and (2) substantially slower migration along much longer strike-parallel pathways deeper in the bedrock toward basement sumps in Bldgs. 9204-4, 9201-5, and 9204-2 (DOE 1998).

The low pH groundwater within the contaminant plume adjacent to the former S-3 Ponds contains a diverse mix of metal ions and/or ion-complexes (beryllium, cadmium, cobalt, manganese, mercury, and nickel) that are usually not mobile (or are more readily attenuated) in less acidic groundwater, as well as metals that are mobile under a wider range of groundwater pH conditions (barium, boron, strontium, and uranium). As noted previously, some of these trace metals were entrained in the acidic wastes disposed at the site, and others were dissolved from the underlying saprolite and bedrock. Similarly elevated concentrations of several other trace metals (including boron, cadmium, cobalt, copper, mercury, and uranium) occur in the groundwater near other sources in the Upper East Fork Regime, notably the S-2 Site, but available data do not indicate that extensive plumes of metal ions and/or ion-complexes have developed in the groundwater beyond the immediate vicinity of these sites (DOE 1998).

Volatile organic compounds are the most pervasive groundwater contaminants in the Upper East Fork Regime (Appendix A, Fig. 12). Chloroethenes (primarily PCE, TCE, and DCE isomers) are the principal components of dissolved VOC plumes in the western and central Y-12 areas. Chloromethanes (primarily carbon tetrachloride and chloroform) are primary plume components in the eastern Y-12 area. Concentrations of individual plume constituents in the Aquitard near several source areas, notably the Waste Coolant Processing Area in the central Y-12 area, exceed 1000 µg/L and indicate the presence of DNAPLs in the subsurface. Data for the existing network of Aquifer (Maynardville Limestone) monitoring wells generally define a relatively continuous plume of dissolved VOCs in the water table interval/shallow bedrock that extends eastward from the Fire Training Facility in the western Y-12 area,

underneath New Hope Pond in the eastern Y-12 area, and into Union Valley at least 2000 ft east of the ORR boundary (Appendix A, Fig. 12).

Groundwater with radiological contamination occurs primarily in the Aquitard east of the former S-3 Ponds and at Tank 0134-U and Bldgs. 9204-4 and 9201-5. In the Aquifer, radiological contamination occurs near the S-2 Site and immediately upgradient of New Hope Pond (the Uranium Oxide Vault, wells GW-605 and GW-606 vicinity, and the former Oil Skimmer Basin) (Appendix A, Fig. 12). The S-3 Ponds are confirmed sources of uranium isotopes (primarily U-234 and U-238), but Tc-99 concentrations (and gross beta activity) exceed 10,000 pCi/L and completely dominate the other radiological contaminants within the Eastern S-3 Site Plume. Under the terms of the PCP for the Upper East Fork Regime, Tc-99 is considered a "signature" component of the Eastern S-3 Site Plume because, as noted previously, the former S-3 Ponds are the only site at Y-12 that routinely received wastes containing Tc-99. In any case, limited influx of radiological contaminants into the Aquifer (or extensive dilution) is indicated by the greatly decreased levels of gross alpha, gross beta, and isotopic uranium activity in the groundwater downgradient of confirmed source areas (e.g., S-2 Site and the former Oil Skimmer Basin).

3.4.3 Chestnut Ridge Hydrogeologic Regime

Operation of the CRSP emplaced a plume of dissolved VOCs in the groundwater that, based on the existing network of wells on Chestnut Ridge, extends at least 2500 ft to the east-northeast along the crest of Chestnut Ridge (parallel with geologic strike) and at least 500 ft to the north and south down the ridge flanks (Appendix A, Fig. 13). The primary components of the VOC plume are 111TCA, 11DCA, and 11DCE near the western trench area and PCE, TCE, and 12DCE isomers near the eastern trench area. The distribution of the VOCs relative to the respective source areas and the apparent elongation of the plume along the axis of Chestnut Ridge, despite steeper hydraulic gradients down the ridge flanks, suggest primarily strike-parallel lateral transport (west to east) in the groundwater (and possibly vapor phase transport). The maximum depth of vertical migration of the VOCs has not been conclusively determined, but is at least 150 ft bgs in the western trench area, 250 ft bgs near the middle of the site, and 270 ft bgs downgradient of the eastern trench area (Energy Systems 1996a). Historical data show maximum summed VOC concentrations above 1000 µg/L in wells located adjacent to the waste disposal trenches, but the concentrations rapidly decrease with distance from the site and are less than 100 µg/L in all wells more than 500 ft from the site. Additionally, VOC concentrations in most wells at the CRSP decreased sharply after the installation of the low-permeability cap during RCRA final closure of the site in 1989 (see Sect. 2.3.1).

Although groundwater transport of the VOCs from the CRSP is primarily from west to east via strike-parallel flowpaths in the bedrock (e.g., bedding-plane fractures), the continued presence of 111TCA and 11DCA in the groundwater from a well (GW-177) at the western end of the CRSP indicates that there is a local component of groundwater flow/VOC transport toward a slight topographic saddle located immediately west-southwest (downhill) of the site. However, extensive westward transport in the groundwater is not supported by the data from the existing network of monitoring wells on Chestnut Ridge.

The western waste disposal trenches at the CRSP are the suspected source of the VOCs (primarily 111TCA) detected in wells located approximately 500 ft directly south (GW-796) and 1500 ft east-southeast (GW-798) of the site (Appendix A, Fig. 13). Continued detection of VOCs in the groundwater samples from these downgradient wells reflects groundwater transport across geologic strike, possibly via "quickflow" conduits described in Energy Systems (1994b).

Results of RCRA interim status (1986–1995) and RCRA post-closure detection monitoring (1995–present) at the CRSDB have not confirmed any release of potential groundwater contaminants to the uppermost aquifer at the site. Results of RCRA interim status (1986–1996) and RCRA post-closure detection monitoring (1996–present) at KHQ show sporadic detection of VOCs (carbon tetrachloride, chloroform, and PCE) in the monitoring wells located hydraulically downgradient of the site, possibly as a direct consequence of wastes being disturbed during attempts to obtain clean closure of the site in the late 1980s and early 1990s (Energy Systems 1996a). Historical sampling data for the existing wells at the ECRWP are limited, but do not suggest a release of contaminants to the groundwater has occurred at the site (see Sect. 5.4.3).

4. CY 2007 RCRA POST-CLOSURE GROUNDWATER SAMPLING AND ANALYSIS

This section describes the CY 2007 groundwater sampling and analysis activities performed for the purposes of RCRA post-closure corrective action monitoring at the S-3 Site, Oil Landfarm, BCBG/WIP, Eastern S-3 Site Plume, and CRSP and RCRA post-closure detection monitoring at the CRSDB, KHQ, and ECRWP. These sampling and analysis activities were implemented under the BJC Water Resources Restoration Program (WRRP) sampling and analysis plan (SAP) for fiscal year (FY) 2007 (BJC 2006). The following subsections provide site-specific information regarding the RCRA post-closure groundwater sampling locations and frequencies, sampling methods, field measurements and laboratory analytes, quality assurance (QA) and quality control (QC) sampling, data management, and data quality objectives (DQO).

4.1 SAMPLING LOCATIONS AND FREQUENCIES

The groundwater sampling locations used for the purposes of RCRA post-closure groundwater monitoring during CY 2007 are shown in Appendix A, Fig. 14 (Bear Creek Regime), Appendix A, Fig. 15 (Upper East Fork Regime), and Appendix A, Fig. 16 (Chestnut Ridge Regime). Site-specific details regarding the monitoring networks and associated sampling frequencies are described in the following subsections.

4.1.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits

The CY 2007 RCRA monitoring well network in the Bear Creek Regime included one of the designated point of compliance (POC) wells at the S-3 Site (GW-276), the Oil Landfarm (GW-008), and the BCBG/WIP (GW-046), and the specified network of RCRA plume boundary sampling locations in the regime: wells GW-712, GW-713, and GW-714 and spring SS-6. The selected POC wells are completed at shallow depths (<30 ft bgs) in the water table interval in the Aquitard (Nolichucky Shale). Conversely, the RCRA plume boundary wells are completed in different hydrostratigraphic intervals in the Aquifer (Maynardville Limestone) at depths ranging from 145 ft bgs (GW-714) to 457 ft bgs (GW-712), and spring SS-6 discharges groundwater from the Maynardville Limestone into the main channel of Bear Creek approximately 400 ft west (downstream) of the RCRA plume boundary wells. Appendix A, Fig. 14 shows the locations of the POC wells at each site and the RCRA plume boundary wells and spring. Construction details for each well are included in Appendix B, Table 7.

Groundwater samples were collected semiannually from each selected POC well at the S-3 Site, Oil Landfarm, and BCBG/WIP and from the shared network of RCRA plume boundary sampling locations during CY 2007. Sampling was performed January 2-3, 2007 (seasonally high flow conditions) and July 2-9, 2007 (seasonally low flow conditions); specific sampling dates and times are included with the corresponding analytical results presented in Appendix C.

4.1.2 Eastern S-3 Site Plume

The CY 2007 RCRA post-closure corrective action monitoring network for the Eastern S-3 Site Plume included one selected POC well (GW-108) and the four designated RCRA plume boundary wells: GW-193, GW-605, GW-606, and GW-733. Completed at a depth of 58 ft bgs, POC well GW-108 yields groundwater from the water table interval in the Aquitard (Nolichucky Shale). Depths of the RCRA plume boundary wells range from less than 20 ft bgs (GW-193) to more than 250 ft bgs (GW-733), and all of these wells are completed in the Aquifer (Maynardville Limestone) in the water table interval (GW-193), shallow bedrock interval (GW-605), intermediate bedrock interval (GW-606), and deep bedrock interval (GW-733). Appendix A, Fig. 15 shows the locations of the POC well and RCRA plume boundary wells. Construction details for each well are included in Appendix B, Table 7.

Groundwater samples were collected semiannually from the POC well and the RCRA plume boundary wells during CY 2007. Sampling was performed January 3-4, 2007 (seasonally high flow conditions) and July 9-10, 2007 (seasonally low flow conditions); specific sampling dates and times are included with the corresponding analytical results presented in Appendix D.

4.1.3 Chestnut Ridge Security Pits

The CY 2007 RCRA post-closure corrective action monitoring network for the CRSP included upgradient/background well GW-521, POC well GW-177, and the following RCRA plume boundary sampling locations: spring SCR4.3SP and wells GW-301, GW-557, GW-562, GW-799, GW-801, and GW-831. All of these wells are completed in the (lower) Knox Group at depths ranging from 92 ft bgs (GW-799) to 200 ft bgs (GW-831). Construction details for each well are included in Appendix B, Table 7. Appendix A, Fig. 16 shows the location of each RCRA well and spring SCR4.3SP, which discharges into a surface drainage feature on the southern flank of Chestnut Ridge.

Groundwater samples were collected semiannually from the RCRA background well, POC well, and RCRA plume boundary wells and spring during CY 2007. Sampling was performed January 9-16, 2007 (seasonally high flow conditions) and July 11-17, 2007 (seasonally low flow conditions); specific sampling dates and times are included with the corresponding analytical results presented in Appendix E.1.

4.1.4 Chestnut Ridge Sediment Disposal Basin

The network of wells designated for RCRA post-closure detection monitoring at the CRSDB includes one upgradient/background well (GW-159) located northwest of the site and three POC wells located to the south (GW-731) and east (GW-156 and GW-732) of the site (Appendix A, Fig. 16). These wells are all completed in the (lower) Knox Group at total depths ranging from 157 ft bgs (GW-156 and GW-159) to 190 ft bgs (GW-732). Construction details for each well are included in Appendix B, Table 7.

Groundwater samples were collected annually from the RCRA background well and POC wells during CY 2007. Sampling was performed January 8-9, 2007 (seasonally high groundwater flow); specific sampling dates and times are included with the corresponding analytical results presented in Appendix E.2.

The PCP for the Chestnut Ridge Regime requires annual groundwater sampling for RCRA post-closure detection monitoring at the CRSDB to be performed during alternating seasonally high and low flow conditions. Accordingly, annual RCRA sampling at the CRSDB in CY 2008 is scheduled to be performed during seasonally low groundwater flow conditions (July 2008).

4.1.5 Kerr Hollow Quarry

The network of wells designated for RCRA post-closure detection monitoring at KHQ includes an upgradient/background well (GW-231) located northwest of the water-filled quarry, and POC wells located to the south (GW-143 and GW-144) and southwest (GW-145) of the site (Appendix A, Fig. 16). These wells are all completed in the (upper) Knox Group at depths ranging from 35 ft bgs (GW-231) to 253 ft bgs (GW-143). Construction details for each well are included in Appendix B, Table 7.

Groundwater samples were collected annually from the RCRA background well and POC wells during CY 2007. Sampling was performed January 4 and 8, 2007 (seasonally high groundwater flow); specific sampling dates and times for each well are included with the corresponding analytical results presented in Appendix E.3.

The PCP for the Chestnut Ridge Regime requires annual groundwater sampling for RCRA post-closure detection monitoring at KHQ to be performed during alternating seasonally high and low flow conditions. Accordingly, CY 2008 annual RCRA sampling at the KHQ is scheduled to be performed during seasonally low groundwater flow conditions (July 2008).

4.1.6 East Chestnut Ridge Waste Pile

The network of wells designated for RCRA post-closure detection monitoring at the ECRWP (Appendix A, Fig. 16) consists of an upgradient/background well (GW-294) located at the eastern end of the site, and POC wells located downhill of the site to the west (GW-296), north (GW-292 and GW-293), south (GW-161), and southeast (GW-298). Construction details for each well are included in Appendix B, Table 7.

Groundwater samples were collected semiannually from the RCRA background well and each POC well during CY 2007. Sampling was performed January 22-29, 2007 (seasonally high flow conditions) and July 9-11, 2007 (seasonally low flow conditions); specific sampling dates and times are included with the corresponding analytical results presented in Appendix E.4.

The PCP for the Chestnut Ridge Regime requires only three of the POC wells to be included in each RCRA sampling event. However, all of the POC wells were sampled during CY 2007 in order to obtain additional baseline groundwater quality data (see Sect. 5.4.3). Beginning in January 2008, wells GW-161, GW-296, and GW-298 will serve as the primary POC wells at the site, with wells GW-292 and GW-293 reserved as replacements for any of the primary POC wells that may become irreparably damaged or otherwise rendered unusable.

4.2 SAMPLING METHODS

The dedicated bladder pump in each well designated for RCRA post-closure groundwater monitoring at the applicable TSD units in the Bear Creek Regime, Upper East Fork Regime, and Chestnut

Ridge Regime was used to collect unfiltered groundwater samples during each RCRA groundwater sampling event. Sampling was performed in accordance with the low-flow minimal drawdown sampling method (hereafter referenced as low-flow sampling) described in Attachment 7, Section A of the PCP for the Bear Creek Regime; Attachment 6 of the PCP for the Upper East Fork Regime; and Attachment 6.1 of the PCP for the Chestnut Ridge Regime.

The TDEC in July 1997 approved the low-flow sampling method for RCRA post-closure groundwater monitoring at Y-12 (TDEC 1997), and implementation of this method at Y-12 began in January 1998. Under this method, unfiltered groundwater samples (including duplicates) are collected immediately after field measurements of selected indicator parameters (e.g., groundwater temperature) show stable values (minimal variation over four consecutive readings) for the groundwater purged from the well at a rate low enough (<300 milliliters per minute) to induce minimal drawdown of the water level in the well (<0.1 ft per quarter-hour). Low-flow sampling promotes groundwater inflow into the well from the water-producing feature(s) proximal to the pump intake. As shown in Appendix B, Table 7, the intake for the dedicated bladder pump in most of the RCRA post-closure groundwater wells that were sampled during CY 2007 is located within approximately 3 ft of the respective monitored interval midpoint.

Before January 1998, a “conventional” sampling method approved by the TDEC was used to obtain groundwater samples from the RCRA groundwater monitoring wells in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime. Under this method, groundwater samples were collected after purging at least three well volumes of groundwater at a pumping rate (1-2 gal per minute) that may substantially lower the water level in the well or purge the well dry. Conventional sampling promotes groundwater inflow from water-producing features throughout the screened or open-hole monitored interval in the well, including features that may not be proximal to the pump intake.

The container immersion sampling method (grab sampling) was used to obtain unfiltered groundwater samples from the springs used for RCRA post-closure groundwater monitoring in the Bear Creek Regime (spring SS-6) and Chestnut Ridge Regime (spring SCR4.3SP). Grab sampling was performed in accordance with the technical procedure specified in the PCP for each respective regime.

4.3 FIELD MEASUREMENTS AND LABORATORY ANALYTES

Field personnel measured the depth to the static water surface in each applicable RCRA well before collecting any groundwater samples, as required by the respective PCP for the Bear Creek Regime (Appendix B, Table 1), Upper East Fork Regime (Appendix B, Table 2), and Chestnut Ridge Regime (Appendix B, Table 3). The depth-to-water measurements were obtained and recorded per the corresponding technical procedure specified in each PCP. Field personnel also recorded measurements of pH, water temperature, conductivity, turbidity, dissolved oxygen, and oxidation-reduction potential (REDOX) when the groundwater samples were collected from each well and spring used for RCRA post-closure groundwater monitoring in each hydrogeologic regime.

All of the groundwater samples collected for the purposes of RCRA post-closure groundwater monitoring during CY 2007 were placed in appropriate containers provided by the analytical laboratory; preserved in accordance with the analytical method; labeled and logged; and transported in ice-filled coolers to the appropriate analytical laboratory. Fully qualified and trained personnel from the BJC environmental sampling subcontractor (Commodore Advanced Sciences, Inc.) were responsible for collecting and transporting the groundwater samples until chain-of-custody control was relinquished to the designated analytical laboratory.

Two commercial laboratories performed the analyses of the groundwater samples collected during CY 2007 for the purposes of RCRA post-closure groundwater monitoring in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime: Lionville Laboratory (inorganic analytes, excluding total uranium, and VOCs) and Paragon Laboratories, Inc. (radiological analytes and total uranium). Analytical results are presented in Appendix C (Bear Creek Regime), Appendix D (Upper East Fork Regime), and Appendix E (Chestnut Ridge Regime). These analyses were performed in accordance with the analytical methods specified in the PCP for each regime, and the analytical results were reported with the project quantitation levels (PQLs) specified for each analyte in the SAP referenced in Sect. 4. Additionally, as required by the PCP for the Chestnut Ridge Regime (Appendix B, Table 3), laboratory analyses of the groundwater samples collected during CY 2007 from the designated RCRA wells at the CRSDB, CRSP, ECRWP, and KHQ were completed within 60 days of each respective sampling date for each well.

The following subsections provide site-specific details regarding the field measurements and laboratory analyses associated with RCRA post-closure groundwater monitoring at the S-3 Site, Oil Landfarm, and BCBG/WIP; the Eastern S-3 Site Plume; and the CRSP, CRSDB, KHQ, and ECRWP.

4.3.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits

Presampling groundwater elevations in the POC wells at the S-3 Site, Oil Landfarm, and BCBG/WIP and the RCRA plume boundary wells during each CY 2007 RCRA groundwater sampling event are summarized below in Table 2. The corresponding depth-to-water measurements for each well are shown in Appendix C. The presampling groundwater elevations in each well are consistent with those recorded during previous RCRA groundwater sampling events and generally reflect the seasonal water table fluctuations that are typically evident in BCV west of Y-12, with groundwater elevations evident during January 2007 (i.e., seasonally high flow conditions) being from 1.5 ft (GW-046) to 2.14 ft (GW-008) higher than evident during July 2007 (i.e., seasonally low flow conditions).

Table 2. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the S-3 Site, Oil Landfarm, and BCBG/WIP

RCRA Well Network		1 st Semiannual Sampling Event		2 nd Semiannual Sampling Event	
Plume Boundary Well		Date Sampled	Groundwater Elevation (ft above msl)	Date Sampled	Groundwater Elevation (ft above msl)
POC Well					
•	GW-008	01/02/07	950.97	07/02/07	948.83
•	GW-046	01/03/07	917.15	07/02/07	915.65
•	GW-276	01/03/07	995.70	07/09/07	993.63
•	GW-712	01/02/07	845.20	07/02/07	843.10
•	GW-713	01/02/07	845.75	07/03/07	843.63
•	GW-714	01/02/07	846.90	07/02/07	844.80

The groundwater samples collected from the selected POC wells at the S-3 Site (GW-276), Oil Landfarm (GW-008), and BCBG/WIP (GW-046) were analyzed for each respective suite of inorganics, VOCs, and radioanalytes that the PCP for the Bear Creek Regime designates as RCRA groundwater target compounds for each site (Appendix B, Table 8). Complete analytical results are in Appendix C.

Groundwater samples collected from wells GW-712, GW-713, and GW-714 and from spring SS-6 were analyzed for the suite of inorganics, VOCs, and radioanalytes that the PCP for the Bear Creek Regime designates as RCRA groundwater target compounds for the RCRA plume boundary sampling locations (Appendix B, Table 8). Complete analytical results are in Appendix C.

4.3.2 Eastern S-3 Site Plume

Presampling groundwater elevations in the POC well and RCRA plume boundary wells for the Eastern S-3 Ponds Plume during each CY 2007 RCRA groundwater sampling event are summarized below in Table 3. The corresponding depth-to-water measurements for each well are presented in Appendix D. These presampling groundwater elevations in each well are similar to those recorded during previous RCRA groundwater sampling events, with fairly minor (<1 ft) seasonal water table fluctuations groundwater elevations evident in each well except GW-733 (2.23 ft), probably reflecting the minimal surface water recharge that occurs in areas with extensive impervious cover (e.g., buildings).

Table 3. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the Eastern S-3 Site Plume

RCRA Well Network		1 st Semiannual Sampling Event		2 nd Semiannual Sampling Event	
Plume Boundary Well		Date Sampled	Groundwater Elevation (ft above msl)	Date Sampled	Groundwater Elevation (ft above msl)
POC Well					
•	GW-108	01/04/07	992.02	07/10/07	991.73
•	GW-193	01/04/07	924.99	07/09/07	924.39
•	GW-605	01/03/07	907.81	07/09/07	907.71
•	GW-606	01/03/07	906.16	07/09/07	905.31
•	GW-733	01/04/07	902.26	07/09/07	900.03

The groundwater samples collected from POC well GW-108 were analyzed for the inorganics, VOCs, and radioanalytes that the PCP for the Upper East Fork Regime designates as RCRA groundwater target compounds for the POC wells at the Eastern S-3 Site Plume (Appendix B, Table 9). Note that the total uranium concentrations reported for this well were calculated from isotopic uranium measurements and specific activities for each isotope. This is because very high calcium concentrations (>1000 mg/L) in the groundwater samples from the well cause substantial analytical interferences for the kinetic phosphorescent analysis method used to perform the uranium analyses (ThermoNUTech 1999).

The groundwater samples collected from wells GW-193, GW-605, GW-606, and GW-733 were analyzed for Tc-99, which is the only analyte that the PCP for the Upper East Fork Regime designates as a RCRA groundwater target compound for these wells because (as noted in Sect. 3.4.2) Tc-99 is considered the “signature” component of the Eastern S-3 Site Plume.

4.3.3 Chestnut Ridge Security Pits

The CY 2007 presampling groundwater elevations in the RCRA background well, POC well, and RCRA plume boundary wells for the CRSP are summarized below in Table 4. The corresponding depth-to-water measurements for each well are presented in Appendix E.1. The presampling groundwater elevations are similar to those recorded for each well during previous RCRA groundwater sampling events and show seasonal water-table fluctuations ranging from less than 0.5 ft (GW-177 and GW-557) to more than 2 ft (wells GW-799 and GW-801).

Table 4. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure corrective action monitoring at the CRSP

RCRA Well Network			1 st Semiannual Sampling Event		2 nd Semiannual Sampling Event		
Background Well			Date Sampled	Groundwater Elevation (ft above msl)	Date Sampled	Groundwater Elevation (ft above msl)	
Plume Boundary Well							
POC Well							
•	•	•	GW-177	01/09/07	1038.78	07/11/07	1039.01
•	•	•	GW-301	01/09/07	951.12	07/12/07	951.52
•	•	•	GW-521	01/10/07	1095.55	07/12/07	1094.59
•	•	•	GW-557	01/11/07	956.08	07/16/07	955.85
•	•	•	GW-562	01/16/07	920.82	07/17/07	919.29
•	•	•	GW-799	01/16/07	958.61	07/17/07	956.14
•	•	•	GW-801	01/11/07	979.85	07/16/07	977.44
•	•	•	GW-831	01/09/07	959.74	07/11/07	959.16

The groundwater samples collected from the RCRA background well and the POC well during CY 2007 were analyzed for the inorganics, VOCs, and radioanalytes designated as site-specific RCRA groundwater target compounds for the CRSP (Appendix B, Table 10). The PCP for the Chestnut Ridge Regime requires the groundwater samples from the RCRA plume boundary wells and spring SCR4.3SP to be analyzed for the VOCs designated as RCRA groundwater target compounds, which are the only confirmed components of the groundwater contaminant plume originating from the CRSP (see Sect. 3.4.3). Analytical results are in Appendix E.1.

4.3.4 Chestnut Ridge Sediment Disposal Basin

The CY 2007 presampling groundwater elevations in the RCRA wells at the CRSDB, summarized below in Table 5, are similar to those recorded during previous RCRA groundwater sampling events and, as required by the PCP for the Chestnut Ridge Regime (Appendix B, Table 3), demonstrate that the POC wells at the CRSDB were hydraulically downgradient of the site when sampling was performed.

Table 5. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at the CRSDB

RCRA Well Network			Date Sampled	Groundwater Elevation (ft above msl)
Background Well				
POC Well				
•	•	GW-156	01/08/07	905.72
•	•	GW-159	01/08/07	933.38
•	•	GW-731	01/09/07	924.18
•	•	GW-732	01/09/07	906.66

The groundwater samples collected from each of the above-listed RCRA wells during CY 2007 were analyzed for the trace metals that the PCP for the Chestnut Ridge Regime designates as RCRA groundwater target compounds for the CRSDB (Appendix B, Table 10). Analytical results for the groundwater samples from each well are in Appendix E.2.

4.3.5 Kerr Hollow Quarry

The CY 2007 presampling groundwater elevations in the RCRA wells at KHQ, summarized below in Table 6, are similar to those recorded during previous RCRA sampling events. As shown below, the groundwater elevations in POC wells GW-143 and GW-145 were higher than evident in background well GW-231. However, these wells were sampled four days apart, and 1.33 in. of rain (as measured at a rain gauge located at the west end of the Y-12 Complex) occurred during this period (0.26 in. and 1.07 in. on January 5 and 7, 2007, respectively). Thus, the difference between the groundwater elevations probably reflects the response to recharge associated with the rainfall.

Table 6. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at KHQ

RCRA Well Network		Date Sampled	Groundwater Elevation (ft above msl)
Background Well			
POC Well			
•	GW-143	01/08/07	832.33
•	GW-144	01/04/07	831.44
•	GW-145	01/08/07	833.19
•	GW-231	01/04/07	832.23

The groundwater samples collected from each of the above-listed RCRA wells during CY 2007 were analyzed for the trace metals, VOCs, and radioanalytes that the PCP for the Chestnut Ridge Regime designates as RCRA groundwater target compounds for KHQ (Appendix B, Table 10). Analytical results for the groundwater samples from each well are in Appendix E.3.

4.3.6 East Chestnut Ridge Waste Pile

The CY 2007 presampling groundwater elevations in the RCRA background well and POC wells at the ECRWP are summarized below in Table 7. The corresponding depth-to-water measurements for each well are presented in Appendix E.4. The presampling groundwater elevations show seasonal water table fluctuations ranging from 1.15 ft (GW-296) to 6.03 ft (GW-294) and demonstrate, as required by the PCP for the Chestnut Ridge Regime (Appendix B, Table 3), that the POC wells at the ECRWP were hydraulically downgradient of the site during each RCRA semiannual groundwater sampling event.

Table 7. CY 2007 presampling groundwater elevations in wells used for RCRA post-closure detection monitoring at the ECRWP

RCRA Well Network			1 st Semiannual Sampling Event		2 nd Semiannual Sampling Event	
			Date Sampled	Groundwater Elevation (ft above msl)	Date Sampled	Groundwater Elevation (ft above msl)
Background Well						
	POC Well					
•	•	GW-161	01/25/07	933.42	07/10/07	931.56
•	•	GW-292	01/23/07	959.46	07/10/07	957.49
•	•	GW-293	01/24/07	947.91	07/10/07	946.31
•	•	GW-294	01/22/07	987.90	07/11/07	981.87
•	•	GW-296	01/22/07	972.48	07/10/07	971.33
•	•	GW-298	01/29/07	939.76	07/09/07	938.09

The groundwater samples collected from the RCRA background well and POC wells during CY 2007 were analyzed for the trace metals, VOCs, and radioanalytes that the PCP for the Chestnut Ridge Regime designates as RCRA groundwater target compounds for the ECRWP (Appendix B, Table 10). Analytical results for each well are in Appendix E.4.

The RCRA groundwater target compounds designated for the ECRWP were identified from an evaluation of the analytical results for the constituents that have been detected in samples of leachate from the site (see Sect. 6). However, as listed in Attachment 7.1, Table 7.1-1 (page 7.1-2) of the PCP for the Chestnut Ridge Regime, the VOCs identified as RCRA groundwater target compounds include chloromethane, which has not been detected in the leachate samples collected to date, but do not include chloroethane, which has been detected in several of the leachate samples. Listing chloromethane instead of chloroethane appears to be a typographical error and should be corrected as a Class 1 modification to the PCP.

4.4 QUALITY ASSURANCE/QUALITY CONTROL SAMPLING

The QA/QC samples associated with CY 2007 RCRA post-closure groundwater monitoring in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime include a total of 23 laboratory blanks and 39 trip blanks (Appendix B, Table 11). The laboratory blanks were samples of deionized water that were prepared at the applicable laboratory and analyzed in conjunction with groundwater samples from one or more RCRA sampling locations. The trip blanks were samples of deionized water that were transported in each cooler that contained RCRA groundwater samples collected for VOC analyses. Each laboratory blank and trip blank was analyzed for a suite of VOCs that includes all the organics designated as RCRA groundwater target compounds for the applicable TSD units in the Bear Creek, Upper East Fork, and Chestnut Ridge hydrogeologic regimes.

At least one of the following VOCs was detected in 32 (82%) of the trip blanks and in each of the laboratory blanks: acetone, bromoform, 2-butanone, chloroform, chloromethane, dibromochloromethane, 1,4-dichlorobenzene, ethylbenzene, 2-hexanone, methylene chloride, styrene, toluene, 1,2,4-trichlorobenzene, and xylenes. Of these, acetone and methylene chloride (common laboratory reagents) were detected the most frequently, with one or both compounds detected in all but one of the laboratory blank samples and in 27 (69%) of the trip blank samples. Estimated concentrations of 4 µg/L or less were reported for each VOC except acetone, which was detected at maximum concentrations of 5 µg/L in the laboratory blanks and 12 µg/L in the trip blanks, respectively (Appendix B, Table 12). These findings suggest systemic contamination of the QA/QC samples (and many of the associated groundwater samples) by methylene chloride and acetone during preparation, handling, analysis, or storage in the applicable laboratory.

4.5 DATA MANAGEMENT

The RCRA post-closure groundwater monitoring data obtained during CY 2007 at the applicable TSD units in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime were managed in accordance with the WRRP data management protocols and maintained in the Project Environmental Measurement System (PEMS) database. The BJC environmental sampling subcontractor initially pre-populated the PEMS database with information (e.g., sampling locations and laboratory analytes) specified in the SAP referenced in Sect. 4. As sampling activities progressed in accordance with the SAP, the BJC environmental sampling subcontractor manually input the associated field measurements and chain-of-custody information into the pre-populated PEMS database. The corresponding analytical results for each sampling location were loaded into the PEMS database by the laboratory that performed the

specified analyses. The applicable laboratory then transferred hardcopy reports containing the analytical results to the BJC Sample Management Organization that subsequently: (1) resolved any discrepancies between the PEMS database and the corresponding hardcopy reports; (2) verified that the field measurements and laboratory analytes specified for each sampling location were performed; and (3) reviewed the associated chain-of-custody information, analytical turnaround times, and sample holding times. The RCRA post-closure groundwater monitoring data presented in this report were prepared from data files extracted from the PEMS database. After all data were verified and validated, as appropriate, they were uploaded to the Oak Ridge Environmental Information System for long-term archival.

4.6 DATA QUALITY OBJECTIVES EVALUATION

Evaluation of the CY 2007 RCRA post-closure groundwater monitoring data for applicable TSD sites in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime was based on results that meet applicable DQO criteria. The screening process used to identify results that do not meet applicable DQOs involved: (1) comparison of the corresponding analytical results for duplicate groundwater samples; (2) identification of false-positive VOC results; (3) comparison of each radioanalyte result to the corresponding minimum detectable activity (MDA) and associated total propagated uncertainty (TPU); and (4) comparison for consistency with available historical monitoring data for each applicable RCRA sampling location.

Duplicate Samples

Duplicate groundwater samples were collected from the following wells included in the RCRA groundwater sampling event during CY 2007: RCRA plume boundary wells for the Bear Creek Regime (GW-713), the Eastern S-3 Site Plume (GW-605), and CRSP (GW-301); POC wells at the CRSDB (GW-156) and ECRWP (GW-293); and the RCRA background well at KHQ (GW-231). Corresponding analytical results for duplicate groundwater samples that differ by an order of magnitude or more are considered unusable. No such differences are evident between the duplicate sample results for any of the above listed RCRA wells; see data in Appendix C (GW-713), Appendix D (GW-605), and Appendix E (GW-156, GW-231, GW-293, and GW-301).

False-Positive VOC Results

False-positive results for VOCs (i.e., potential sampling and/or analytical artifacts) are considered the same as non-detect values (i.e., zero concentration) for the purposes of quantitative evaluation. Such results are defined as VOC concentrations reported for groundwater samples that are less than the respective blank qualification result (BQR) calculated from the associated laboratory and trip blank sample data. The BQRs for acetone, methylene chloride, toluene, and 2-butanone (common laboratory reagents) represent the highest concentration in either blank sample multiplied by a factor of 10, and the BQRs for all other VOCs are similarly calculated using a factor of 5 (EPA 1988). All false-positive VOC results are flagged with a qualifier (FP1 for false-positive results identified from laboratory BQRs or FP2 for false-positive results identified from trip BQRs).

False-positive results for VOCs that are RCRA groundwater target compounds were reported for one or more of the groundwater samples collected during CY 2007 from: the upgradient/background well at the ECRWP (GW-294); POC wells for the ECRWP (GW-161, GW-292, GW-293, GW-296, and GW-298),

the Eastern S-3 Site Plume (GW-108), and the S-3 Site (GW-276); and the RCRA plume boundary sampling locations in the Bear Creek Regime (wells GW-712, GW-713, and GW-714 and spring SS-6). As shown below in Table 8, the false-positive results are for acetone and methylene chloride, all the concentrations being below 10 µg/L (only two results exceed 5 µg/L), with just over half (12 of 22) identified from laboratory BQRs. The ubiquitous detection of one or both compounds in the laboratory blanks and trip blanks associated with RCRA post-closure groundwater monitoring during CY 2007 suggest that these results are properly considered analytical artifacts.

Table 8. CY 2007 false-positive results for VOCs that are RCRA groundwater target compounds

RCRA Groundwater Target Compound	RCRA Location	Date Sampled	Result (µg/L)	BQR (µg/L)		QA/QC Flag
				Lab. Blank	Trip Blank	
Acetone	GW-108	01/04/07	9 J	20	20	FP1
Acetone	GW-108	07/10/07	8 J	0	20	FP2
Acetone	GW-276	01/03/07	3 J	20	30	FP2
Methylene chloride	GW-161	01/25/07	1 J	10	20	FP2
Methylene chloride	GW-276	01/03/07	3 J	50	30	FP1
Methylene chloride	GW-276	07/09/07	1 J	10	30	FP2
Methylene chloride	GW-292	01/23/07	3 J	20	30	FP2
Methylene chloride	GW-292	07/10/07	1 J	7	10	FP2
Methylene chloride	GW-293	01/24/07	1 J	10	10	FP1
Methylene chloride	GW-293	07/10/07	2	10	10	FP1
Methylene chloride	GW-294	01/22/07	4 J	10	40	FP2
Methylene chloride	GW-296	01/22/07	3 J	10	40	FP2
Methylene chloride	GW-296	07/10/07	1 J	9	10	FP2
Methylene chloride	GW-298	01/29/07	2 J	20	20	FP1
Methylene chloride	GW-712	01/02/07	3 J	30	30	FP1
Methylene chloride	GW-712	07/02/07	1 J	10	10	FP1
Methylene chloride	GW-713	01/02/07	2 J	30	30	FP1
Methylene chloride	GW-713	07/03/07	2 J	10	10	FP1
Methylene chloride	GW-714	01/02/07	2 J	30	30	FP1
Methylene chloride	GW-714	07/02/07	1 J	10	10	FP1
Methylene chloride	SS-6	01/03/07	4 J	30	40	FP2
Methylene chloride	SS-6	07/02/07	1 J	10	0	FP1

Radiological Analyses

Analytical results for gross alpha activity, gross beta activity, and radioisotopes are qualified as unusable if the reported activity exceeds the specified MDA, but not the associated TPU reported with each result. The TPU expresses the degree of analytical uncertainty and is defined as twice the standard deviation for sample activity. The CY 2007 RCRA post-closure groundwater monitoring data include only two such results: the very low levels of U-235 (0.203 pCi/L) and U-238 (0.268 pCi/L) reported for the groundwater sample collected from RCRA plume boundary well GW-713 in January 2007 slightly exceed the corresponding MDA (0.184 pCi/L and 0.182 pCi/L, respectively), but not the associated TPU (0.241 pCi/L and 0.272 pCi/L, respectively).

Historical Data Comparison

The CY 2007 analytical results were evaluated for consistency with historical monitoring data for each applicable RCRA post-closure groundwater monitoring location in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime. For the purposes of this evaluation, a "Q" (questionable) data-evaluation qualifier is assigned to analytical results that are either less than one half the historical minimum value for the analyte, or are more than 2X the historical maximum value for the analyte. Based on these criteria, Q qualifiers were assigned to the following CY 2007 sampling results:

- Total concentrations of chromium (0.01 mg/L), iron (0.21 mg/L), and nickel (0.0541 mg/L) reported for the sample collected from ECRWP POC well GW-292 in January 2007 and the chromium (0.0257 mg/L) and iron (0.588 mg/L) detected in the sample collected from this well in July 2007. Chromium was not detected in the 21 samples previously collected from the well and nickel was detected in only one of these samples (0.013 mg/L in August 1991). Both CY 2007 sampling results for total iron substantially exceed the historical maximum concentration (0.059 mg/L in August 1993).
- The total magnesium concentration reported for the sample collected from ECRWP POC well GW-161 in July 2007 (0.262 mg/L) substantially exceeds the historical maximum concentration (0.03 mg/L in September 1992).

5. CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA EVALUATION

The following sections describe results of the annual evaluations of the RCRA post-closure groundwater monitoring data that are required by the respective PCPs for the Bear Creek Regime (Appendix B, Table 1), Upper East Fork Regime (Appendix B, Table 2), and Chestnut Ridge Regime (Appendix B, Table 3). Collectively, the PCPs require annual evaluation of: (1) the groundwater flow direction and rate in the uppermost aquifer at each specified TSD unit; (2) contaminant concentration trends in the groundwater from POC wells at the S-3 Site, Oil Landfarm, BCBG/WIP, Eastern S-3 Site Plume, and CRSP; (3) continued contaminant plume migration based on sampling results for the designated RCRA plume boundary monitoring locations in each hydrogeologic regime; and (4) evidence of contaminant releases to the groundwater at the CRSDB, ECRWP, and KHQ based on statistical analysis of the respective RCRA post-closure detection monitoring data.

5.1 GROUNDWATER FLOW DIRECTION AND RATE

Estimates of representative groundwater flow rates in the uppermost aquifer at the TSD units in BCV (Bear Creek Regime and Upper East Fork Regime) and the section of Chestnut Ridge south of Y-12 (Chestnut Ridge Regime) are described in the following subsections. The wide range of estimated flow rates probably occurs at various times under various conditions. However, the relatively limited migration of most groundwater contaminants in the Bear Creek Regime, Upper East Fork Regime, and Chestnut Ridge Regime suggests that the lower flow rates dominate (particularly in the Aquitard bedrock intervals) and that attenuation processes greatly reduce contaminant transport relative to groundwater flow rates.

5.1.1 Bear Creek Valley

Depth-to-water measurements obtained during April 2007 (i.e., seasonally high groundwater flow conditions) for 64 monitoring wells in the Bear Creek Regime (Appendix B, Table 13) and 55 monitoring wells in the Upper East Fork Regime (Appendix B, Table 14) were used to determine: (1) representative groundwater elevations in the vicinity of the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume; (2) site- and regime-wide groundwater flow directions; and (3) horizontal hydraulic gradient values needed to calculate groundwater flow rates. The groundwater elevations determined from the depth-to-water measurements recorded during each CY 2007 RCRA sampling event were not used for these purposes.

In the Bear Creek Regime, isopleths of groundwater surface elevations indicate southwesterly flow in the Aquitard, across geologic strike, toward the Aquifer (Maynardville Limestone), with more westerly flow in the Maynardville Limestone, parallel with geologic strike, toward the west end of BCV (Appendix A, Fig. 8). In the Upper East Fork Regime, isopleths of groundwater surface elevations generally show southeasterly flow in the Aquitard (across geologic strike) toward the Aquifer (Maynardville Limestone), and easterly (parallel with geologic strike) flow in the Maynardville Limestone toward the east end of Y-12 (Appendix A, Fig. 9). These findings do not indicate any significant change in the relative directions of groundwater flow in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and the Eastern S-3 Site Plume.

Rates of groundwater flow were estimated for the water table and shallow bedrock intervals in the Aquitard, which underly the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume, and the shallow karst network in the Aquifer, which is the primary pathway for groundwater transport of contaminants in the Bear Creek Regime and the Upper East Fork Regime. Groundwater flow rates in each hydrogeologic unit were estimated using the modified Darcy equation: $V = K/I/\eta$, where V is the flow velocity, K is the hydraulic conductivity of the medium, I is the horizontal hydraulic gradient, and η is the effective porosity. The calculated flow rates represent average velocities in the Aquitard and the Aquifer, assuming each hydrogeologic unit functions as an equivalent porous medium. Flow rates were not estimated for the stormflow zone in either hydrogeologic unit because most waste sources in each regime lie below this zone. Rates of groundwater flow in the intermediate and deep bedrock intervals in the Aquitard and the Aquifer also were not estimated, but are probably as low as a few centimeters per year in the Aquitard (Energy Systems 1992a).

Results of statistical analysis of hydraulic test data for wells in BCBV indicate hydraulic conductivity values of 0.03 to 3.25 ft per day (ft/d) at shallow depths (water table interval) in the geologic formations that comprise the Aquitard (Connell and Bailey 1989). In the shallow bedrock interval in the Aquitard, representative hydraulic conductivities are 0.0008 ft/d for matrix intervals (Energy Systems 1989a), 0.15 ft/d for permeable intervals (Energy Systems 1989a), and 0.6 ft/d for the continuum of permeable intervals (Energy Systems 1992b). Substantially higher hydraulic conductivity is evident in the shallow karst network in the Aquifer, with an average hydraulic conductivity of 22 ft/d indicated by falling-head permeability test results for wells completed in the Maynardville Limestone in BCBV west of Y-12 (Energy Systems 1989b), and a flow rate of 200 ft/d determined from results of a dye-tracer study in Bear Creek (Energy Systems 1989c). These estimated rates of groundwater flow may not be representative of hydraulic conductivity at shallow depths in the Aquitard and the Aquifer throughout much of the Upper East Fork Regime because of the extensive alteration of the shallow subsurface that occurred during construction of the Y-12 operations and support facilities.

Representative horizontal hydraulic gradients in uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and the Eastern S-3 Site Plume were determined from groundwater elevations in selected monitoring wells completed at shallow depths (water table interval) in the Aquitard formations that subcrop beneath each site. Also, selected wells completed at similarly shallow depths in the Maynardville Limestone were used to determine representative horizontal hydraulic gradients in the Aquifer throughout the Bear Creek Regime and Upper East Fork Regime. As shown below in Table 9, calculated horizontal hydraulic gradients in the Aquitard range from 0.029 near the Oil Landfarm to 0.047 at the former S-3 Ponds (Eastern S-3 Site Plume), with gradients in the Aquifer being near 0.01 in both the Upper East Fork Regime and Bear Creek Regime.

Table 9. Representative horizontal hydraulic gradients in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume, April 2007

Hydrogeologic Unit, Site, and Monitoring Well No.			Groundwater Elevation (ft above msl)	Lateral Distance (ft)	Horizontal Hydraulic Gradient (I)
Aquitard	S-3 Site	GW-276	994.73	1154.1	0.042
		GW-115	1043.44		
	Oil Landfarm	GW-008	951.09	515.4	0.029
		GW-001	966.05		
	BCBG/WIP	GW-291	937.13	565.8	0.034
		GW-287	917.75		
	Eastern S-3 Site Plume	GW-108	991.97	851.5	0.047
		GW-261	1031.82		

Table 9. (continued)

Hydrogeologic Unit, Site, and Monitoring Well No.			Groundwater Elevation (ft above msl)	Lateral Distance (ft)	Horizontal Hydraulic Gradient (<i>I</i>)
Aquifer	Bear Creek Regime	GW-309	967.50	1066.3	0.007
		GW-065	959.72		
	Upper East Fork Regime	GW-617	971.61	4802.8	0.01
		GW-193	925.15		

Several studies and evaluations of available hydrologic data provide estimates of the effective porosity of the geologic formations that comprise the Aquitard, with values ranging from 0.00035 (Energy Systems 1992b) to 0.099 (Energy Systems 1996b). Estimates of effective porosity in the Aquifer (Maynardville Limestone and Copper Ridge Dolomite) range from 0.0006 to 0.0813 (Energy Systems 1997b).

Based on range of input values for hydraulic conductivity, hydraulic gradient, and effective porosity described above, and on the assumptions inherent to the modified Darcy equation, calculated rates of groundwater flow in the Aquitard at the S-3 Site, Oil Landfarm, BCBG/WIP, and the Eastern S-3 Site Plume, summarized below (Table 10), range from 0.07 ft per year (0.0002 ft/d) to approximately 77 ft/d. A comparably wide range of groundwater flow rates likewise is indicated for the Aquifer (Maynardville Limestone) in the Bear Creek Regime and the Upper East Fork Regime.

Table 10. Calculated rates of groundwater flow in the uppermost aquifer at the S-3 Site, Oil Landfarm, BCBG/WIP, and Eastern S-3 Site Plume

Groundwater Flow Rates ($V = KI/\eta$)					
AQUITARD	V (ft/d)		K (ft/d)	I	η
	Water Table Interval				
	Min:	0.008	0.03	0.029	0.099
	Max:	34.8	3.25	0.047	0.0042
	Shallow Bedrock Interval				
	Min:	0.0002	0.0008	0.029	0.099
	Max:	77.1	0.6	0.047	0.00035
AQUIFER	V (ft/d)		K (ft/d)	I	η
	Min:	2.71	22	0.007	0.0813
	Max:	440.0	22	0.01	0.0006

5.1.2 Chestnut Ridge

Representative groundwater surface elevations throughout the Chestnut Ridge Regime were determined from depth to water measurements recorded for 77 monitoring wells (Appendix B, Table 15) during April 2007 (seasonally high flow conditions). Based on these data, regime-wide groundwater elevation isopleths were used to evaluate groundwater flow directions in the uppermost aquifer at the CRSP, CRSDB, KHQ, and ECRWP (Appendix A, Fig. 10). Note that the presampling groundwater elevations determined from the depth-to-water measurements recorded during the CY 2007 RCRA sampling events at each site were not used for this purpose.

Isopleths of groundwater elevations in the Chestnut Ridge Regime show steep hydraulic gradients down the northern flank of Chestnut Ridge (across geologic strike) near the CRSP. However, as noted in Sect. 3.4.3, the elongated shape of the VOC plume originating from this site and the orientation of the plume along the crest of the ridge indicate that the primary direction of groundwater flow (and contaminant transport) is from west to east (parallel with geologic strike). Seasonal groundwater elevations in monitoring wells at the CRSDB and ECRWP likewise indicate generally easterly flow, with components of flow to the north-northeast into BCV. Flow directions near KHQ are generally south toward Melton Hill Reservoir or southwest toward the unnamed tributary adjacent to the site. Horizontal hydraulic gradients determined from groundwater elevations in selected monitoring wells at each site are summarized below (Table 11).

Table 11. Representative horizontal hydraulic gradients in the uppermost aquifer at the CRSP, CRSDB, KHQ, and ECRWP, April 2007

Site/Monitoring Well No.		Groundwater Elevation (ft above msl)	Lateral Distance (ft)	Horizontal Hydraulic Gradient (<i>I</i>)
CRSP	Strike Normal:	GW-611	944.73	.
		GW-178	1052.16	0.273
		GW-511	981.44	0.141
	Strike Parallel:	GW-178	1052.16	.
		GW-179	1011.97	0.053
		GW-609	944.63	0.044
CRSDB		GW-159	933.86	0.051
		GW-156	906.23	
KHQ		GW-231	835.14	0.004
		GW-144	833.25	
ECRWP		GW-292	960.23	0.039
		GW-298	939.28	

The modified Darcy equation described in Sect. 5.1.1 was used to calculate representative rates of groundwater flow within the uppermost aquifer (Knox Group) at the CRSP, CRSDB, ECRWP, and KHQ. Flow rate calculations are based on: (1) the range of hydraulic conductivity values (0.0002 to 13.8 ft/d) indicated by results of straddle packer tests (Energy Systems 1988a) and falling-head permeability tests (Energy Systems 1997a); (2) effective porosity ranging from 0.0006 to 0.0813 (Energy Systems 1997b); and (3) the range of horizontal hydraulic gradients summarized above. Based on these input values and the inherent assumptions of the modified Darcy equation, calculated groundwater flow rates in the uppermost aquifer at each site, summarized below in Table 12, range from 0.0009 ft per year (0.00001 ft/d) at KHQ to more than 1000 ft/d at the CRSP and the CRSDB. Calculated groundwater flow rates at the lower end of the range seem reasonable for diffuse flow across matrix intervals in the Knox Group. The upper values are within the range of flow rates typical of highly permeable conduits in karst terrains (Quinlan and Ewers 1985) and are generally supported by the flow rates (490 to 1250 ft/d) indicated by a dye-tracer study performed on Chestnut Ridge near ORNL (Energy Systems 1984).

Table 12. Calculated rates of groundwater flow in the uppermost aquifer at the CRSP, CRSDB, KHQ, and ECRWP

Groundwater Flow Rates ($V = KI/\eta$)					
CRSP	Strike-normal flow:	V (ft/d)		K (ft/d)	I
		Min:	0.0003	0.0002	0.141
	Strike-parallel flow:	Max:	6279	13.8	0.273
		Min:	0.00011	0.0002	0.044
		Max:	1219	13.8	0.053
		Min:	0.00013	0.0002	0.051
CRSDB		Max:	1173	13.8	0.051
		Min:	0.00001	0.0002	0.004
KHQ		Max:	92	13.8	0.004
		Min:	0.0001	0.0002	0.039
ECRWP		Max:	897	13.8	0.039
		Min:	0.0001	0.0002	0.039

5.2 RCRA POINT-OF-COMPLIANCE MONITORING DATA

The following subsections present evaluations of the CY 2007 RCRA post-closure corrective action monitoring results for the POC wells at the S-3 Site (GW-276), Oil Landfarm (GW-008), BCBG/WIP (GW-046), the Eastern S-3 Site Plume (GW-108), and the CRSP (GW-177). As required by site-specific conditions of the PCPs for the Bear Creek Regime (Appendix B, Table 1), Upper East Fork Regime (Appendix B, Table 2), and Chestnut Ridge Regime (Appendix B, Table 3), each evaluation includes quantitative trend analysis of data for selected site-specific RCRA groundwater target compounds detected in the groundwater samples from the applicable POC well. Compounds selected for trend analysis are representative of the primary components of the groundwater contaminant plumes originating from each of these TSD units.

Concentration trends for the selected RCRA groundwater target compounds detected in each applicable POC well were determined from time-series plots of respective RCRA post-closure corrective action monitoring results obtained since January 1998, which coincides with the programmatic change from the conventional sampling method to the low-flow sampling method (see Sect. 4.2). The relative direction (upward or downward) of each concentration trend was determined by least-squares linear regression of the time-series data for each applicable RCRA groundwater target constituent. Non-detected results were excluded from the regression analyses, as were results that do not meet applicable DQOs (e.g., false-positive VOC results).

5.2.1 S-3 Site

S-3 Site POC well GW-276 yields groundwater from the water table interval in the Nolichucky Shale approximately 200 ft southeast of the S-3 Site (Appendix A, Fig. 14). Installed in July 1986, this well is constructed with nominal 4.5 in. diameter stainless steel riser casing and spiral-wound well screen (0.01 in. slot) and is completed with a monitored interval from 11.3 - 18.5 ft bgs (Appendix B, Table 7). The well has a nearly continuous 21-year groundwater sampling history that includes quarterly RCRA interim status assessment monitoring (1986-1990; 1994) and semiannual RCRA post-closure corrective action monitoring (1995-present). Analytical results for these samples show that the well yields acidic (pH <6) calcium-magnesium-bicarbonate groundwater containing several inorganic, organic, and

radiological contaminants originating from the former S-3 Ponds, including nitrate, trace metals, alpha and beta radioactivity, and VOCs (see Sect. 3.4.1.1).

The S-3 Site RCRA groundwater target compounds listed below in Table 13 were detected in at least one of the groundwater samples collected from well GW-276 during CY 2007. Analytical results for the full suite of RCRA groundwater target compounds are in Appendix C. Aside from the false-positive results for acetone and methylene chloride (see Sect. 4.6), analytical results for the other RCRA groundwater target compounds meet applicable DQO criteria and are generally consistent with historical data for the well.

Table 13. CY 2007 sampling results for RCRA groundwater target compounds detected in S-3 Site POC well GW-276

RCRA Groundwater Target Compound	MCL	January 2007	July 2007
Inorganics (mg/L)			
Barium	2	0.0794	0.1
Cadmium	0.005	0.0099	0.0074
Mercury	0.0004	0.00024	.
Nickel	0.1	0.125	0.102
Nitrate (as N)	10	19.4	29.6
Uranium	0.03	0.45	0.21
VOCs (µg/L)			
Acetone	-	FP2	.
Methylene chloride	-	FP1	FP2
PCE	5	5	4 J
Radioanalytes (pCi/L)			
Gross alpha activity	15	120 ± 20.6	109 ± 19.1
Gross beta activity	50*	151 ± 24.9	218 ± 35.5
Am-241	-	.	0.0427 ± 0.0388
Np-237	-	6.77 ± 2.72	4.6 ± 1.84
Total Radium	-	1.24 ± 0.593	0.177 ± 0.101
Sr-90	-	1.4 ± 0.659	2.41 ± 1.31
Tc-99	900*	233 ± 38.5	282 ± 46.1
U-234	-	57.2 ± 11	49.2 ± 9.15
U-235	-	3.2 ± 1.16	3.96 ± 1.36
U-236	-	118 ± 21.9	107 ± 18.7
Presampling Groundwater Elevation (ft above msl)		995.70	993.63
Notes: "." = Not detected (less than PQL or MDA). * = SDWA screening level for a 4 mrem/yr dose equivalent. FP1 = False-positive result (contaminated laboratory blank sample; see Sect. 4.6). FP2 = False-positive result (contaminated trip blank sample).			

Nitrate is the primary component of the groundwater contaminant plume originating from the former S-3 Ponds and, as shown in Table 13, is the principal inorganic RCRA groundwater target compound detected at the highest concentrations in the groundwater from well GW-276. Although both CY 2007 sampling results for nitrate exceed the drinking water MCL (10 mg/L), they reflect the substantial long-term concentration decrease illustrated by the time-series plot of the nitrate data (Appendix A, Fig. 17), with the concentrations evident in July 2006 (18.6 mg/L) and January 2007 (19.4 mg/L) being the lowest reported for the well to date. The decreasing nitrate concentration trend is characterized by significant short-term (seasonal) fluctuations, with the peak concentrations evident in July 1998 (139 mg/L),

July 2000 (105 mg/L), and July 2002 (73.7 mg/L) suggesting greater relative inflow of nitrate-contaminated groundwater into the well during seasonally dry flow conditions.

As shown in Table 13, the groundwater samples collected from well GW-276 during CY 2007 contained several trace metals designated as RCRA groundwater target compounds for the S-3 Site, with concentrations of cadmium, nickel, and uranium exceeding their drinking water MCLs (0.005 mg/L, 0.1 mg/L, and 0.03 mg/L, respectively). These results are consistent with previous RCRA sampling data, although the concentrations are several orders of magnitude lower than the cadmium, nickel, and uranium levels indicated by historical data (e.g., 0.34 mg/L, 4.8 mg/L, and 7.97 mg/L, respectively, in October 1987). The time-series plot of the RCRA sampling results for uranium (Appendix A, Fig. 17), which shows a variable but clearly decreasing long-term trend ($R^2 = 0.53$) through July 2007 (0.21 mg/L), is representative of the concentration trends evident for the other trace metals. Interestingly, the substantial decrease in trace metal concentrations occurred with only a modest change in the acidic pH of the groundwater, as illustrated by the field pH measurements recorded during RCRA sampling events in October 1987 (pH = 4.5) and July 2007 (pH = 4.94). This suggests that the decreasing concentrations of uranium and other trace metals are primarily attributable to substantially reduced advective flux of the metal ions via the groundwater flowpaths intercepted by the monitored interval in well GW-276.

Excluding the false-positive results for acetone and methylene chloride, PCE was the only VOC designated as a RCRA groundwater target compound for the S-3 Site that was detected in the groundwater samples collected from well GW-276 during CY 2007, with PCE concentrations at or below the 5 µg/L drinking water MCL (Table 13). These results are consistent with historical data and demonstrate, as noted in Sect. 3.4.1.1, that VOCs are secondary components of the S-3 Site contaminant plume and have never been dominant compounds in the shallow groundwater from well GW-276. A time-series plot of the PCE data (Appendix A, Fig. 17) shows variable concentrations dominated by temporal peak levels evident in July 1999 (14 µg/L) and July 2000 (14 µg/L), with a decreasing linear regression trend line ($R^2 = 0.58$). Also, none of the samples collected to date contained PCE degradation products (e.g., TCE and c12DCE), which suggests that the reduced PCE concentrations indicated by the more recent sampling results are not attributable to biologically-mediated degradation in the groundwater.

Each radiological analyte designated as a RCRA groundwater target compound was detected (i.e., >MDA and TPU) in one or both groundwater samples collected from well GW-276 in CY 2007. Results for each radiological analyte except Am-241 are consistent with historical data; the July 2007 sampling result for Am-241 (0.0427 pCi/L) just slightly exceeds the MDA (0.0232 pCi/L) and is a likely analytical artifact. In any case, gross alpha activity in the shallow groundwater from this well remains substantially above the MCL (15 pCi/L), with U-234 and U-238 being the primary alpha-emitting radionuclides (Table 13). Gross beta activity in the groundwater likewise remains above the SDWA screening level (50 pCi/L) for a 4 millirem per year (mrem/yr) dose equivalent (the MCL for beta activity). The principal beta-particle emitting radionuclide within the S-3 Site contaminant plume is Tc-99, although both groundwater samples collected from well GW-276 in CY 2007 had Tc-99 concentrations below the SDWA threshold value (900 pCi/L) for a 4 mrem/yr dose equivalent from Tc-99 (Table 13). Moreover, a time-series plot of the Tc-99 data for well GW-276 shows a clearly decreasing concentration trend ($R^2 = 0.82$) that generally mirrors the nitrate trend (Appendix A, Fig. 17).

The CY 2007 RCRA groundwater sampling results for well GW-276 generally continue the decreasing long-term concentrations trends evident for the representative components of the contaminant plume originating from the S-3 Site (nitrate, uranium, PCE, and Tc-99). These results are consistent with the conceptual model for contaminant migration from the S-3 Site, whereby contaminant concentrations are expected to decrease over time because of: (1) substantially reduced contaminant flux following cessation of waste disposal at the site and the subsequent installation of the low-permeability cap; (2) the

cumulative effects of various natural attenuation processes, including discharge of contaminated groundwater from the Aquitard into the Bear Creek tributary drainage system; and (3) the continued westward migration (parallel with geologic strike) of the center of mass of the contaminant plume originating from the former S-3 Ponds (DOE 1997).

5.2.2 Oil Landfarm

Oil Landfarm POC well GW-008 yields groundwater from the water table interval in the Nolichucky Shale directly south of the approximate mid-point of the Oil Landfarm HWDU (Appendix A, Fig. 14). Installed in September 1983, this well is constructed with nominal 2 in. diameter stainless steel riser casing and spiral-wound well screen (0.01 in. slot) and is completed with a monitored interval from 13 to 25.5 ft bgs (Appendix B, Table 7). The well has an intermittent groundwater sampling history initiated by pre-RCRA characterization monitoring (1983–1985), with a subsequent prolonged sampling gap (1986–1997) followed by nearly ten years of semiannual sampling for RCRA post-closure corrective action monitoring (1998–present). Analytical results for these samples show that the well yields acidic (pH < 5.5) calcium-magnesium bicarbonate groundwater distinguished by unusually low (<10 mg/L) total dissolved solids (TDS), which implies short groundwater residence time and suggests that the well intercepts hydraulically active flowpaths. Groundwater from the well contains a mixture of dissolved VOCs, primarily chlorinated hydrocarbons dominated by PCE, that are believed to originate from the southern landfarm plots at the site (see discussion in Sect. 3.4.1.2).

The RCRA groundwater target constituents for the Oil Landfarm listed below in Table 14 were detected in at least one of the groundwater samples collected from well GW-008 during CY 2007. Respective analytical results for these constituents meet applicable DQO criteria and are generally consistent with previous RCRA post-closure groundwater monitoring results for the well.

Table 14. CY 2007 sampling results for RCRA groundwater target compounds detected in Oil Landfarm POC well GW-008

RCRA Groundwater Target Compound	MCL	January 2007	July 2007
Inorganics (mg/L)			
Barium	2	0.093	0.121
Organics (µg/L)			
PCE	5	40	73
TCE	5	9	11
c12DCE	70	21	23
11DCE	7	6	4
Presampling Groundwater Elevation (ft above msl)		950.97	948.83

Barium is the only inorganic RCRA groundwater target constituent detected in either groundwater sample collected from well GW-008 during CY 2007 (Table 14). These results show that barium concentrations remain within the range of background levels in the Bear Creek Regime and at least an order of magnitude below the drinking water MCL.

As shown in Table 14, PCE, TCE, c12DCE, and 11DCE were detected in both groundwater samples collected from well GW-008 during CY 2007. As in previous years, PCE was the dominant VOC detected in each sample, the concentrations being at least two times higher than the concentrations reported for TCE, 11DCE, and c12DCE. These RCRA sampling results also show that the concentrations

of PCE and TCE remain above their drinking water MCLs (5 µg/L for both), with 11DCE concentrations being slightly below the MCL (7 µg/L), and the c12DCE concentrations being substantially below the MCL (70 µg/L). The dominance of PCE in the shallow groundwater from well GW-008 suggests that this compound was probably a principal component of the associated wastes disposed at the Oil Landfarm. Additionally, the suite of VOCs present in the groundwater reflects the complex composition of the dissolved VOC plume originating from the landfarm plots at the site (see Sect. 2.1.2). Anaerobic conditions (i.e., dissolved oxygen <0.5 ppm) in the subsurface nearest the source areas are conducive to biologically-mediated sequential degradation (reductive dechlorination) of PCE and its daughter products (TCE, TCE, DCE isomers, and VC), which intermingle in the groundwater and migrate hydraulically downgradient, ultimately encountering aerobic conditions where PCE and TCE will not biodegrade (Weidemeier et al. 1999). Aerobic conditions seem to prevail in the groundwater from the well GW-008, as indicated by pre-sampling field measurements that typically show dissolved oxygen above 1 ppm (e.g., 1.21 ppm in January and July 2007).

The PCE concentrations indicated by the RCRA sampling results from January 2007 (40 µg/L) and July 2007 (73 µg/L) illustrate the substantial short-term concentration fluctuations that dominate the time-series plot of the PCE results for well GW-008 (Appendix A, Fig. 18). Additionally, the linear regression trend line ($R^2 = 0.15$) is skewed upward by the relatively low PCE concentrations (e.g., 7 µg/L in July 1999) evident before a sharp increase in January 2000 (75 µg/L) and the subsequent indeterminate (not clearly increasing or decreasing) concentration trend through July 2007. It is not clear from the RCRA sampling results what may have caused the sharply higher PCE levels or why the concentrations exhibit such wide short-term fluctuations. However, there appears to be some correlation between PCE levels and groundwater flow conditions because each of the temporal peak concentrations indicated by the PCE results obtained after January 2000 were reported for seasonally dry RCRA groundwater sampling events in July 2001, July 2002, July 2003, July 2005, and July 2007 (Appendix A, Fig. 18). These findings suggest that the seasonal (or episodic) recharge may promote greater relative inflow of less PCE-contaminated groundwater into the well.

The TCE concentrations indicated by the RCRA groundwater sampling results from January 2007 (9 µg/L) and July 2007 (11 µg/L) continue a fairly indeterminate concentration trend evident since January 2000 (12 µg/L), when the TCE levels initially increased above the conspicuously lower levels indicated by previous RCRA sampling results for well GW-008 (e.g., 4 µg/L in July 1998). The lower TCE concentrations evident before January 2000, like the corresponding PCE results noted above, seem to skew the linear regression trend line ($R^2 = 0.35$) upward, as shown on the time-series plot of the TCE data (Appendix A, Fig. 18). Unlike PCE, however, the TCE concentrations evident after January 2000 exhibit clearly cyclic fluctuations, with temporal peak concentrations indicated by the TCE results from seasonally wet RCRA groundwater sampling events in January 2001, January 2002, January 2004, January 2005, and January 2006 (Appendix A, Fig. 18). This relationship suggests that seasonal (or episodic) recharge promotes greater relative inflow of TCE-contaminated groundwater into the well.

The CY 2007 RCRA groundwater sampling results show that c12DCE is the dominant DCE isomer in the groundwater from well GW-008, with concentrations nearly four times higher than those of 11DCE (Table 14). These results also show that the c12DCE concentrations remain higher than the levels of TCE, possibly because anaerobic biodegradation of DCE isomers occurs at a substantially slower rate than that of TCE (and PCE), and the REDOX conditions near the source area(s) may not be sufficiently reducing to degrade c12DCE to VC (Weidemeier et al. 1999). However, unlike both PCE and TCE, the linear regression trend line ($R^2 = 0.47$) shown on the time-series plot of the c12DCE results does not appear to be skewed upward by the concentrations evident before January 2000 (Appendix A, Fig. 18), which suggests that the trend reflects a general increase in the relative flux of c12DCE. Also, the c12DCE results obtained after January 2000 show cyclic concentration fluctuations similar to (and often

concurrent with) those evident for TCE, with four of the five temporal peak c12DCE concentrations reported for seasonally wet RCRA groundwater sampling events in January 2001, January 2004, January 2005, and January 2006 (Appendix A, Fig. 18). This relationship suggests that seasonal (or episodic) recharge promotes greater relative inflow of c12DCE-contaminated groundwater into the well.

It is not clear from the RCRA groundwater sampling results obtained to date if the above-noted concentration trends for PCE, TCE, and c12DCE are significant with respect to the overall flux of dissolved VOCs via the groundwater flowpaths intercepted by the monitored interval in well GW-008. Nevertheless, the concentrations of these VOCs are significantly lower than the summed levels ($>700\text{ }\mu\text{g/L}$) indicated by the pre-RCRA sampling results for the well (Energy Systems 1990). The lower levels of dissolved VOCs now evident in the groundwater from the well are primarily attributable to the closure and capping of the Oil Landfarm, which substantially reduced the flux of dissolved VOCs in the shallow groundwater, and the continued discharge of VOC-contaminated groundwater from the shallow flow system in the Aquitard into the Bear Creek tributary drainage system (DOE 1997). The reduced concentrations also reflect the cumulative effects of natural attenuation processes active within the VOC plume, including biologically-mediated reductive dechlorination in anaerobic zones near the source areas, and advection, dispersion, and sorption in aerobic zones within the VOC plume in the groundwater downgradient of the Oil Landfarm.

5.2.3 Bear Creek Burial Grounds/Walk-In Pits

POC well GW-046 at the BCBG/WIP yields groundwater from the water table interval in the Nolichucky Shale near the southwest corner of BG-A South (Appendix A, Fig. 14). Installed in October 1983, this well is constructed with nominal 2 in. diameter stainless steel riser casing and spiral-wound well screen (0.01 in. slot) and is completed with a monitored interval from 5 to 20.3 ft bgs (Appendix B, Table 7). The groundwater sampling history for the well includes pre-RCRA characterization monitoring (1983–1985), quarterly RCRA interim status assessment monitoring (1987–1990; 1995), and semiannual RCRA post-closure corrective action monitoring (1998–present). Analytical results for the samples collected to date show that the well yields acidic ($\text{pH} < 6$) calcium-magnesium bicarbonate groundwater distinguished by enriched levels of chloride ($>40\%$ of total anions). Groundwater from the well contains a mixture of dissolved VOCs, including petroleum products and chlorinated hydrocarbons, with the extremely high concentrations ($>1000\text{ }\mu\text{g/L}$) of several compounds (e.g., PCE and c12DCE) attributable to the presence of DNAPLs in the Nolichucky Shale down-dip (south) of BG-A South (see Sect. 3.4.1.3).

The VOCs listed below in Table 15 are the only RCRA groundwater target compounds for the BCBG/WIP that were detected in either of the groundwater samples collected from well GW-046 during CY 2007. Analytical results for each of these VOCs meet applicable DQO criteria, are generally consistent with previous RCRA sampling results for the well, and show that the concentrations of PCE, TCE, c12DCE, 11DCE, and VC remain substantially above respective drinking water MCLs. Benzene concentrations are significantly lower than those of the chlorinated hydrocarbons, but nonetheless exceed the MCL, whereas 111TCA concentrations are substantially below the MCL.

Table 15. CY 2007 monitoring results for RCRA groundwater target compounds detected in BCBG/WIP POC well GW-046

RCRA Groundwater Target Compound	MCL	January 2007	July 2007
Organics (µg/L)			
Benzene	5	9	9
PCE	5	370	420
TCE	5	730	620
c12DCE	70	2500	1700
11DCE	7	46	27
VC	2	240	170
111TCA	200	33	19
11DCA	-	95	70
Presampling Groundwater Elevation (ft above msl)		917.15	915.65

Several of the VOCs in the shallow groundwater from well GW-046 (e.g., benzene, PCE, and 111TCA) are probably principal components of the associated wastes disposed in the BCBG/WIP, whereas the other VOCs (e.g., c12DCA and 11DCA) are present because of the chemical and/or biological degradation of the related parent compounds. Biodegradation (sequential reductive dechlorination) of PCE and its daughter products also may account for the characteristically high levels of chloride in the shallow groundwater from the well (e.g., 37.8 mg/L in July 2004). Biodegradation most likely occurs under the anaerobic conditions in the subsurface nearest the source areas (including DNAPL) at the BCBG/WIP, with the relatively high concentrations of VC in well GW-046 indicating that REDOX conditions near the source areas are sufficiently reducing to degrade DCE isomers. As noted in Sect 5.2.2, PCE biodegrades more rapidly than c12DCE, which may explain why the c12DCE concentrations remain substantially higher than the PCE levels. Also, abiotic (chemical) processes may degrade 111TCA to acetic acid under either aerobic or anaerobic conditions (McCarty 1996), which may account for the acidic pH of the groundwater samples from well GW-046 (e.g., 5.37 in July 2007) and the significantly higher levels of 11DCA relative to 111TCA. The following discussion presents an evaluation of the concentration trends for selected parent compounds (benzene, PCE, and 111TCA) and degradation products (c12DCE and 11DCA) that are representative components of the dissolved plume of VOCs in the shallow groundwater downgradient of the BCBG/WIP.

Equal concentrations of benzene (9 µg/L) detected in the groundwater samples collected from well GW-046 during CY 2007 continue the generally indeterminate long-term concentration trend reflected by the flat linear regression trend line ($R^2 = 0.01$) shown on the time-series plot of the RCRA groundwater sampling results for benzene (Appendix A, Fig. 19). These results show decreasing benzene concentrations between July 1998 (49 µg/L) and July 2002 (9 µg/L), with successive sharp concentration increases in January 2003 (47 µg/L) and July 2003 (240 µg/L), followed by another decreasing trend through July 2007 (9 µg/L). The distinctive temporal peak concentration of benzene in July 2003, which substantially exceeds the previous maximum concentration (49 µg/L in July 1998), potentially reflects a corresponding "surge" in the relative flux of benzene in response to local recharge from nearly 3 in. of rainfall (as measured at a rain gauge in BGV) during the five days preceding the July 2003 groundwater sampling date. Subsequent natural attenuation appears to have gradually dissipated the increased mass of benzene associated with the "surge" such that the benzene concentrations appear to have returned to the lower, fairly asymptotic levels evident before July 2003 (Appendix A, Fig. 19).

Widely fluctuating long-term concentration trends are indicated by the time-series plots of the RCRA groundwater sampling results for PCE and c12DCE in well GW-046, with the linear regression of the respective data showing a slightly decreasing trend line ($R^2 = 0.09$) for PCE paralleled by the trend line for c12DCE ($R^2 = 0.13$) (Appendix A, Fig. 19). Short-term fluctuations in the concentrations of both compounds frequently coincide and often correlate with seasonally dry groundwater flow conditions, as illustrated by the concurrent peak levels of PCE and c12DCE indicated by sampling results from July 1998 (4600 µg/L and 6417 µg/L), July 2000 (8400 µg/L and 11,260 µg/L), and July 2003 (5100 µg/L and 7200 µg/L). Respective peak concentrations of PCE and c12DCE evident in July 2003, like the peak benzene concentration noted above, also presumably reflect a recharge-related flux increase in response to the pre-sampling rainfall. Previous temporal high concentrations of PCE and c12DCE evident in July 1998 and July 2000 likewise may reflect episodic recharge-related increases in contaminant flux, although the corresponding sampling results for benzene do not show temporal peak concentrations for either sampling event (Appendix A, Fig. 19).

Times-series plots of the RCRA groundwater sampling results for 111TCA and 11DCA in well GW-046 show a widely fluctuating long-term concentration trend for 111TCA that is similar to those than evident for PCE and c12DCE, with linear regression of the 111TCA data likewise showing a decreasing trend line ($R^2 = 0.176$), whereas the data for 11DCA exhibit much less temporal variability and define a flat or slightly increasing linear regression trend line ($R^2 = 0.003$) (Appendix A, Fig. 19). Although 111TCA and 11DCA concentrations both “spiked” in July 2003 in response to the recharge-related flux increase noted above, the previous and subsequent RCRA sampling results show temporal peak concentrations that are much more pronounced for 111TCA. Also, unlike the PCE and c12DCE levels, samples collected during seasonally high groundwater flow conditions often contain the highest concentrations of 111TCA, as illustrated by the peak 111TCA levels evident in January 2000 (300 µg/L), January 2001 (260 µg/L), and January 2006 (95 µg/L). This relationship suggests that the groundwater flowpaths intercepted by the monitored interval in the well allow greater relative inflow of 111TCA-contaminated groundwater into the well during seasonally (and episodically) high flow conditions.

The CY 2007 RCRA groundwater sampling data for well GW-046, as indicated by the preceding evaluation of long-term concentration trends for selected VOCs (parent compounds and associated degradation products), are generally consistent with the conceptual model for contaminant transport from sources at the BCBG/WIP, whereby VOC concentrations in the shallow groundwater are expected to slowly decrease in response to the reduced flux of VOCs following the closure and capping of the waste disposal areas, and from the combined cumulative effects of various natural attenuation processes (DOE 1997). Also, the DNAPL in the subsurface at the site, if undisturbed, will remain a long-term source of dissolved VOCs (parent compounds and related degradation products) in the deeper groundwater. Driven by the upward hydraulic gradients typical of the Aquitard formations in BCV west of Y-12, VOCs dissolved from the DNAPL ultimately may enter the shallow flow system and discharge into the Bear Creek drainage system (DOE 1997).

5.2.4 Eastern S-3 Site Plume

Eastern S-3 Site Plume POC well GW-108 yields groundwater from the shallow bedrock interval in the Nolichucky Shale approximately 800 ft southeast of the S-3 Site (Appendix A, Fig. 15). Installed in September 1984, the well is constructed of nominal 4 in. diameter polyvinyl chloride (PVC) riser casing and well screen (0.01 in. slot) and completed with a monitored interval from 41 to 58.6 ft bgs (Appendix B, Table 7). This well has an extensive sampling history that includes quarterly RCRA interim-status assessment monitoring (January 1986–January 1990) and semiannual RCRA post-closure corrective action monitoring (June 1995–present). Historical sampling results show that this well

yields acidic groundwater (pH<6) characterized by very high levels of nitrate (>10,000 mg/L), calcium (>10,000 mg/L), magnesium (>900 mg/L), sodium (>400 mg/L), and barium (>90 mg/L); a mixture of dissolved VOCs (primarily acetone, chloroform, and methylene chloride) with summed concentrations typically below 100 µg/L; very high beta radioactivity (>10,000 pCi/L), which is primarily from Tc-99; and elevated alpha radioactivity (>15 pCi/L), which is primarily from uranium isotopes. These RCRA groundwater sampling results are believed to be representative of contaminant concentrations within strike-parallel groundwater transport/migration pathways in the Nolichucky Shale to the east of the former S-3 Ponds (DOE 1998).

The RCRA groundwater target constituents listed below in Table 16 were detected in the groundwater samples collected from POC well GW-108 during CY 2007. Analytical results for each constituent except acetone meet applicable DQOs (both results for acetone are false positives as noted in Sect. 4.6) and are consistent with historical data for the well.

Table 16. CY 2007 sampling results for RCRA groundwater target compounds detected in Eastern S-3 Site Plume POC well GW-108

RCRA Groundwater Target Compound		MCL	January 2007	July 2007
Inorganics (mg/L)				
Barium	2	75.2	71.7	
Nickel	0.1	0.196	0.182	
Nitrate	10	6,580	6,370	
Uranium	0.03	[0.0166]	[0.0143]	
Organics (µg/L)				
Acetone	-	FP1	FP2	
Chloroform	80*	34	35	
Methylene chloride	5	50	48	
PCE	5	4 J	4 J	
TCE	5	4 J	3 J	
Radioanalytes (pCi/L)				
Gross alpha activity	15	331 ± 80.4	68.9 ± 38.2	
Gross beta activity	50**	18,400 ± 2950	14,900 ± 2390	
Tc-99	900**	30,000 ± 4780	29,000 ± 4620	
Presampling Groundwater Elevation (ft above msl)			992.02	991.73
Notes:				
[] = Calculated value (see Sect. 4.3.2).				
J = Estimated concentration.				
FP1 = False-positive result (contaminated laboratory blank sample; see Sect. 4.6).				
FP2 = False-positive result (contaminated trip blank sample).				
* = MCL is for total trihalomethanes.				
** = SDWA screening level for a 4 mrem/yr dose equivalent.				

Nitrate is the primary component of the groundwater contaminant plume originating from the former S-3 Ponds and, as shown in Table 16, the CY 2007 RCRA sampling results indicate that nitrate concentrations in the shallow groundwater from well GW-108 remain two orders of magnitude above the drinking water MCL (10 mg/L). Nevertheless, these nitrate results continue a clearly decreasing long-term concentration trend illustrated by the time-series plot of the nitrate data (Appendix A, Fig. 20), with the concentration evident in July 2007 (6370 mg/L) being the lowest reported for the well to date. Temporal peak nitrate concentrations in February 1999 (11,800 mg/L), July 2000 (13,300 mg/L), and January 2003 (10,400 mg/L) dominate the decreasing trend, but most of the RCRA sampling results for

nitrate, including the CY 2007 data, indicate fairly modest short-term concentration fluctuations. Also, the temporal changes in the nitrate concentrations do not exhibit any consistent relationship with seasonally wet or dry flow conditions. Moreover, the minimal seasonal water-table fluctuations indicated by the RCRA presampling groundwater elevations in the well (see Sect. 4.3.2), as illustrated by the 0.29 ft difference between groundwater elevations in January and July 2007 (Table 16), do not support substantial flow-related variations in the advective flux of nitrate (and other similarly mobile contaminants) via the flowpaths intercepted by the monitored interval in well GW-108.

As shown in Table 16, the groundwater samples collected from well GW-108 during CY 2007 contained three trace metals designated as RCRA groundwater target compounds for the Eastern S-3 Site Plume: (1) barium concentrations an order of magnitude above the MCL (1 mg/L); (2) nickel concentrations slightly above the drinking water MCL (0.1 mg/L); and (3) (calculated) uranium concentrations slightly below the MCL (0.03 mg/L). These results illustrate the heterogeneous distribution of trace metals in the acidic groundwater within the Eastern S-3 Site Plume.

Excluding false-positive results (acetone, see Sect. 4.6), chloroform, methylene chloride, PCE, and TCE are the VOCs designated as RCRA groundwater target constituents for the Eastern S-3 Site Plume that were detected in the groundwater samples collected from well GW-108 during CY 2007 (Table 16). These results are consistent with previous RCRA sampling data and show that the dominant VOCs in the groundwater are methylene chloride and chloroform. Methylene chloride was detected at the highest concentrations that substantially exceed the drinking water MCL (5 µg/L). Chloroform was detected at comparable but lower concentrations that continue a widely variable but generally increasing ($R^2 = 0.16$) long-term concentration trend (Appendix A, Fig. 20). In contrast, both PCE and TCE were detected at much lower levels that remain below the respective MCL for each compound (5 µg/L), and respective results continue the indeterminate long-term concentration trends illustrated by the TCE results from RCRA groundwater sampling in March 1998 (3 µg/L), July 2001 (3 µg/L), January 2004 (4 µg/L), and July 2007 (4 µg/L). It is not clear from the available data if such divergent concentration trends are significant with respect to the relative flux of VOCs via the groundwater flowpaths intercepted by the monitored interval in the well.

Gross alpha activity reported for the groundwater samples in January 2007 (331 pCi/L) and July 2007 (68.9 pCi/L) show that the levels of alpha radioactivity in the shallow groundwater from well GW-108 remain substantially above the drinking water MCL (15 pCi/L). These results also illustrate the significant short-term variability indicated by previous RCRA sampling results for gross alpha activity, which include a suspected outlier result (1334 pCi/L) from January 2003. The apparent temporal variability may be an artifact of the analytical interference associated with the very high levels of TDS in the (unfiltered) groundwater samples from this well. Also, gross alpha activity was detected (i.e., >MDA and TPU) in only two of the ten samples collected from the well between June 1995 and July 2000, but was detected in all but two of the 14 samples subsequently collected through July 2007. This suggests perhaps more accurate measurement of gross alpha activity rather than a potential overall increase in the flux of alpha-emitting radionuclides via the groundwater flowpaths intercepted by the monitored interval in well GW-108.

As shown in Table 16, both of the groundwater samples collected from well GW-108 during CY 2007 contained very high levels of gross beta activity and Tc-99, a beta-emitting radionuclide that is a principal component of the Eastern S-3 Ponds Plume (see Sect. 3.4.2). These results, which do not appear to be significantly effected by the high TDS of the groundwater samples, show that both gross beta activity and Tc-99 activity remain multiple orders of magnitude above the respective SDWA threshold levels (50 pCi/L and 900 pCi/L, respectively) for a 4 mrem/yr dose equivalent (the drinking water MCL for

gross beta activity). A time-series plot of the Tc-99 results shows a clearly increasing long-term concentration trend (Appendix A, Fig. 20), strongly supported by the linear regression trend line ($R^2=0.66$). However, the CY 2007 RCRA sampling results indicate that the Tc-99 levels have decreased from the historical peak evident in July 2006 (33,900 pCi/L). Considering the mobility of Tc-99 in the groundwater, the increased levels of Tc-99 may reflect a corresponding increase in the relative flux of Tc-99 in the shallow groundwater flow system east of the former S-3 Ponds. The increased levels (flux) of Tc-99 contrasts with the concurrently decreasing levels (flux) of nitrate, which seems unusual considering that both contaminants share a common source (the former S-3 Ponds) and are chemically stable and highly mobile in the groundwater. Such divergent concentration trends probably reflect the complex hydrochemical dynamics within the Eastern S-3 Site Plume. For example, Tc-99 levels in the groundwater may not be influenced by attenuation processes that work to reduce the concentrations of nitrate.

Under the conceptual groundwater flow and contaminant transport models presented in the CERCLA RI for the UEFPC CA (DOE 1998), the concentrations of contaminants in the shallow groundwater east of the S-3 Site are expected to decrease at various rates in response to the substantially reduced contaminant flux after the former S-3 Ponds were closed and capped; the continued eastward (strike-parallel) migration of the center of mass of the Eastern S-3 Site Plume; differential retardation and natural attenuation in the subsurface; and discharge of contaminated groundwater into the subsurface drainage system that replaced the headwaters of UEFPC (DOE 1998). The decreasing nitrate concentration trend continued by the CY 2007 RCRA post-closure groundwater monitoring results for well GW-108 is consistent with the conceptual flow/transport model. However, the increasing trend for Tc-99 suggests a corresponding increase in the relative flux of Tc-99 and does not conform to the model.

5.2.5 Chestnut Ridge Security Pits

The CRSP POC well GW-177 yields groundwater from the Knox Group (Copper Ridge Dolomite) at the western end of the former waste disposal trenches at the site (Appendix A, Fig. 16). Installed in October 1985, this well is constructed of nominal 4 in. diameter PVC riser casing and well screen (0.01 in. slot) and is completed with a monitored interval from 130 to 145 ft bgs (Appendix B, Table 7). The well has an extensive groundwater sampling history that includes quarterly RCRA interim status assessment monitoring (February 1986–February 1996), which spanned the closure of the CRSP and the installation of the low-permeability cap at the site, and semiannual RCRA post-closure corrective action monitoring (July 2001–present). Analytical results for these samples show that the well yields calcium-magnesium-bicarbonate groundwater containing a mixture of dissolved VOCs. As noted in Sect. 3.4.3, the presence of these VOCs in the groundwater at this well reflects their strike-parallel groundwater transport (or possibly vapor-phase transport) toward a localized depression in the water table located to the west of the western disposal trenches at the CRSP.

The RCRA groundwater target compounds listed below in Table 17 were detected in the groundwater samples collected from well GW-177 during CY 2007. All of these results meet applicable DQOs, are consistent with previous RCRA groundwater sampling results for the well, and show background levels of cadmium, chromium, nickel, and gross alpha activity along with modest levels of VOCs dominated by 11DCA.

Table 17. CY 2007 sampling results for RCRA groundwater target compounds detected in CRSP POC well GW-177

RCRA Groundwater Target Compound		MCL	January 2007	July 2007
Inorganics (mg/L)	Cadmium	0.005	.	0.0002
	Chromium	0.1	0.0127	0.0194
	Nickel	0.1	0.0113	0.0134
Organics (µg/L)	11DCA	-	26	25
	11DCE	7	5	6
	111TCA	200	8	7
Radioanalytes (pCi/L)				
Gross alpha activity		15	.	2.73 ± 1.56
Presampling Groundwater Elevation (ft above msl)			1038.78	1039.01
Notes: " ." = Not detected (less than the PQL or MDA).				

As shown in Table 17, the CY 2007 RCRA sampling results for well GW-177 show the highest concentrations for 11DCA with lower concentrations of 11DCE and 111TCA that are below respective drinking water MCLs of 7 µg/L and 200 µg/L. These compounds are confirmed components of the dissolved VOC plume originating from the western waste disposal trenches at the CRSP. Most likely, 111TCA was a component of the associated wastes and is probably the parent of 11DCA, which is an intermediate degradation product along with 11DCE. Indeed, degradation of the 111TCA most likely explains the observed change over time in the ratio between the concentrations of 11DCA and 111TCA (11DCA:111TCA), which steadily increased over time from near 0.25:1 in the late 1980s to more than 3:1 since January 2006 (Appendix A, Fig. 21). Additionally, 111TCA may degrade at a faster rate than either 11DCE or 11DCA (Weidemeier et al. 1999), which potentially accounts for the 11DCA concentrations remaining several times higher than the 111TCA levels.

The respective time-series plot of the RCRA groundwater sampling results for 111TCA (parent compound) and 11DCA (degradation product) show a widely fluctuating but decreasing concentration trend for 111TCA supported by linear regression trend line ($R^2 = 0.48$), and an indeterminate concentration trend for 11DCA with a nearly flat or slightly increasing linear regression trend line ($R^2 = 0.009$) (Appendix A, Fig. 21). Temporal peak concentrations of both VOCs often correlate with seasonally high groundwater flow conditions, which suggests seasonally (and episodically) variable flux of VOCs along the groundwater flowpaths intercepted by the monitored interval in well GW-177. Also, historical data show that the concentrations of VOCs in the groundwater from this well (and other wells at the CRSP) rapidly decreased after the CRSP were closed and capped. For example, the concentration of 111TCA decreased from almost 100 µg/L in February 1989 to less than 10 µg/L in July 1990. Since then, natural attenuation processes, including the chemical and/or microbiologically-mediated degradation noted above, have continued to slowly reduce the VOC concentrations such that asymptotic levels appear to have been achieved for some compounds (e.g., 11DCE).

5.3 RCRA PLUME BOUNDARY MONITORING DATA

The following subsections describe the required evaluations of CY 2007 RCRA post-closure corrective action monitoring data reported for the RCRA plume boundary sampling locations (wells and springs) designated under site-specific conditions of the respective PCP for the Bear Creek Regime (Appendix B, Table 1), Upper East Fork Regime (Appendix B, Table 2), and Chestnut Ridge Regime (Appendix B, Table 3).

5.3.1 S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits

The S-3 Site, Oil Landfarm, and BCBG/WIP share the following network of RCRA plume boundary monitoring locations: wells GW-712, GW-713, GW-714, and spring SS-6. The RCRA plume boundary wells were installed in June 1991 (GW-712) and January 1992 (GW-713 and GW-714) and are completed at various depths within different hydrostratigraphic zones along a strike-normal transect across the Maynardville Limestone located approximately 5000 ft west of the BCBG/WIP (Appendix A, Fig. 14). Each well has black steel well casing and an open-hole monitored interval; construction details are included in Appendix B, Table 7. Spring SS-6 discharges groundwater from the Maynardville Limestone south of the main channel of Bear Creek approximately 700 ft northwest of well GW-714 (Appendix A, Fig. 14). Detailed hydrologic data for the spring are not available, but flow appears to be perennial because the spring has never been dry during any scheduled sampling event over the past 16 years, including sampling performed during seasonally low flow conditions (summer and fall). More recently, a pond that forms behind a nearby beaver dam periodically submerges the spring.

The groundwater sampling histories for wells GW-712, GW-713, and GW-714 include non-RCRA exit-pathway/perimeter monitoring (1991–1994) and RCRA post-closure corrective action monitoring (1995–present). Respective analytical results for each well show distinctive differences in groundwater geochemistry. The deeper plume boundary wells, GW-712 (457.5 ft bgs) and GW-713 (315.2 ft bgs), typically yield sulfate-enriched (>50% of total anions) calcium-magnesium-bicarbonate groundwater distinguished by fluoride concentrations near 0.5 mg/L, total (and dissolved) strontium concentrations near 1 mg/L, and neutral to slightly basic pH (7.5–8.5). Conversely, the shallower plume boundary well, GW-714 (145.0 ft bgs), yields calcium-magnesium-bicarbonate groundwater distinguished by much lower proportions of sulfate (<10%), fluoride concentrations at or slightly above the PQL (0.1 mg/L), total (and dissolved) strontium concentrations near 0.1 mg/L, and neutral to slightly acidic pH (6.0–7.5).

As shown by the CY 2007 RCRA sampling results summarized below in Table 18, excluding the false-positive results for methylene chloride, none of the RCRA groundwater target compounds were detected in the groundwater samples collected from well GW-712; low (background) levels of a gross beta activity and U-234 were detected in one sample from well GW-713; and low levels of nitrate, U-234, and U-238 were detected in the samples from well GW-714. Complete analytical results for the groundwater samples from each well are in provided Appendix C.

Table 18. CY 2007 sampling results for RCRA groundwater target compounds detected in RCRA plume boundary wells GW-712, GW-713, and GW-714 in the Bear Creek Regime

RCRA Groundwater Target Compound	GW-712		GW-713		GW-714	
	January 2007	July 2007	January 2007	July 2007	January 2007	July 2007
Inorganics (mg/L) Nitrate	.	.	.	.	0.36	0.24
Organics (µg/L) Methylene Chloride	FP1	FP1	FP1	FP1	FP1	FP1
Radioanalytes (pCi/L) Gross Beta	.	.	.	3.72 ± 1.6	.	.
U-234	.	.	.	0.814 ± 0.51	0.888 ± 0.53	1.79 ± 0.96
U-238	.	.	.	.	0.666 ± 0.44	.
Groundwater elevation (ft above msl)	845.20	843.10	845.75	843.63	845.94	844.80
Notes: "." = Not detected (less than the PQL or MDA). FP1 = False-positive result (contaminated laboratory blank sample; see Sect. 4.6).						

Semiannual RCRA groundwater sampling for spring SS-6 began in June 2004 when the spring replaced a well (GW-715) formerly designated as a RCRA plume boundary sampling location. The previous groundwater sampling history for the spring includes quarterly sampling (January 1991–November 1993), semiannual sampling (1995, 1998, 1999, and 2000), and annual sampling (2003) events. Analytical results for the groundwater samples collected to date show that spring SS-6 yields calcium-magnesium-bicarbonate groundwater characterized by low molar proportions of chloride, potassium, sodium, and sulfate (i.e., <10% of total anions/cations); TDS ranging between 75 and 300 mg/L; pH ranging from 6.76 to 8.64 (field measurements); and total concentrations of trace metals that are either below respective PQLs or are within the range of background levels in the Bear Creek Regime.

The RCRA groundwater target compounds detected in the groundwater samples collected from spring SS-6 during CY 2007 are listed below in Table 19. Aside from the false-positive results for methylene chloride (see Sect. 4.6), these analytical results meet applicable DQOs, are consistent with historical sampling results for the spring, and are within the respective range of background levels in the Bear Creek Regime and/or inherent analytical variability.

Table 19. CY 2007 sampling results for RCRA groundwater target constituents detected in RCRA plume boundary spring SS-6 in the Bear Creek Regime

RCRA Groundwater Target Constituent	January 2007	July 2007
Inorganics (mg/L) Nitrate	0.38	0.71
Uranium	.	0.01
Organics (µg/L) Methylene Chloride	FP2	FP1

Table 19. (continued)

RCRA Groundwater Target Constituent	January 2007	July 2007
Radioanalytes (pCi/L)		
Gross alpha activity		4.77 ± 2.27
Gross beta activity	3.64 ± 1.9	6.33 ± 2.38
U-234	0.564 ± 0.321	0.743 ± 0.546
U-238	0.932 ± 0.422	
Notes: "." = Not detected (less than the PQL or MDA) FP1 = False-positive result (contaminated laboratory blank sample; see Sect. 4.6). FP2 = False-positive result (contaminated trip blank sample).		

The PCP for the Bear Creek Regime (Appendix A, Table 1) requires evaluation of the RCRA groundwater monitoring data for wells GW-712, GW-713, GW-714, and spring SS-6 to be based on quantitative trend analysis of the analytical results for nitrate, uranium, TCE, and Tc-99. These RCRA groundwater target compounds are representative of the most mobile and/or pervasive components of the commingled contaminant plume in the Aquifer (Maynardville Limestone) hydraulically upgradient to the east (see Sect. 3.4.1.4). However, none of these constituents have been detected consistently in the groundwater samples collected to date from wells GW-712 and GW-713, both of which intercept low permeability flowpaths at depth in the Maynardville Limestone. Also, TCE and Tc-99 are rarely if ever detected in the groundwater samples from any of the RCRA plume boundary monitoring locations. Based on these considerations, only the nitrate concentration trends for well GW-714 and spring SS-6 were evaluated per the requirements of the above-referenced permit conditions. Each trend analysis was based on a time-series plot of the RCRA post-closure groundwater monitoring results obtained since January 1998, with the relative direction (upward or downward) of each trend determined by least-squares linear regression of the respective time-series data. Non-detected results were excluded from the regression analyses, as were results that do not meet applicable DQOs, including nitrate results for samples with unacceptable charge-balance errors.

Respective time-series plots of the nitrate data for well GW-714 and spring SS-6 are shown on Appendix A, Fig. 22. The nitrate trend for well GW-714 is dominated by a peak concentration in January 2001 (3.7 mg/L) followed by lower and steadily decreasing levels that have remained below 1 mg/L since July 2004 and do not exhibit significant seasonal fluctuations. The RCRA sampling results for nitrate in groundwater from spring SS-6 show similarly low levels that exhibit much more temporal (seasonal) variability and define a decreasing linear regression trend line ($R^2 = 0.16$).

Based on the CY 2007 RCRA post-closure groundwater monitoring data for wells GW-712 and GW-713 and the respective trends of background nitrate concentrations continued by the CY 2007 sampling results for well GW-714 and spring SS-6, each of these groundwater sampling locations remain suitable for the RCRA plume boundary monitoring purposes defined in the PCP for the Bear Creek Regime.

5.3.2 Eastern S-3 Site Plume

In accordance with the PCP for the Upper East Fork Regime (Appendix A, Table 3), detection of Tc-99 (i.e., >MDA and TPU) in the groundwater samples from the designated RCRA plume boundary wells (GW-193, GW-605, GW-606, and GW-733) is considered indicative of contaminant migration from the Eastern S-3 Site Plume because no other site in the Upper East Fork regime received wastes that contained the radionuclide. The Tc-99 results reported for the groundwater samples collected from the

RCRA plume boundary wells during CY 2007 are all less than the applicable MDA (see data in Appendix D). Accordingly, these wells remain suitable for the RCRA plume boundary monitoring purposes defined in the PCP for the Upper East Fork Regime.

5.3.3 Chestnut Ridge Security Pits

As noted in Sect. 4.1.3, the RCRA plume boundary sampling locations designated for the CRSP are located more than 1000 ft to the east (GW-301), southeast (GW-562, GW-557, GW-799, and spring SCR4.3SP), south (GW-801), and southwest (GW-831) of the site (Appendix A, Fig. 16). The wells were installed between July 1987 (GW-301) and July 1996 (GW-831), each well constructed with stainless steel riser casing and continuous wire-wound screen (0.01 in. slot). Complete well construction information for each of these wells is provided in Appendix B, Table 7.

In accordance with the new PCP for the Chestnut Ridge Regime (see Sect. 1), VOCs are defined as RCRA groundwater target compounds for the RCRA plume boundary sampling locations (Appendix B, Table 10). None of these VOCs were detected in the groundwater samples collected from the RCRA plume boundary sampling locations during CY 2007 (see data in Appendix E.1). Accordingly, wells GW-301, GW-557, GW-799, GW-801, and GW-831 and spring SCR4.3SP remain suitable for the RCRA plume boundary monitoring purposes defined in the PCP for the Chestnut Ridge Regime.

5.4 RCRA POST-CLOSURE DETECTION MONITORING DATA

5.4.1 Chestnut Ridge Sediment Disposal Basin

None of the RCRA groundwater target constituents for the CRSDB (cadmium, chromium, lead, mercury, nickel, silver, and total uranium) were detected (i.e., >PQL) in the groundwater samples collected during CY 2007 from upgradient/background well GW-159 and POC wells GW-159, GW-731, and GW-732 at the site (see data in Appendix E.2). Accordingly, these results do not indicate a release of contaminants to the uppermost aquifer at the CRSDB.

5.4.2 Kerr Hollow Quarry

Uranium is the only RCRA groundwater target compound for KHQ that was detected in the groundwater samples collected during CY 2007 from upgradient/background well GW-231 and POC wells GW-143, GW-144, and GW-145 at the site (see data in Appendix E.3). Statistical evaluation of the uranium results in accordance with the procedure specified in the PCP for the Chestnut Ridge Regime was completed within 90 days of the annual RCRA groundwater sampling event, as required by the PCP (Appendix B, Table 3). The results of the statistical evaluations do not indicate a release of contaminants to the uppermost aquifer at KHQ (see the site-specific statistical data evaluation report in Appendix E.5).

5.4.3 East Chestnut Ridge Waste Pile

Ten inorganic constituents (e.g., metals and anions) and gross alpha activity are the RCRA groundwater target compounds for the ECRWP detected in the groundwater samples collected during CY 2007 from upgradient/background well GW-294 and POC wells GW-161, GW-292, GW-293, GW-296, and

GW-298 (see data in Appendix E.4). Analytical results for the groundwater samples from the POC wells indicate concentrations of barium (GW-292 and GW-293), chloride (GW-292 and GW-293), chromium (GW-292), and nickel (GW-292) above background levels. Statistical evaluation of these results in accordance with the procedure specified in the PCP for the Chestnut Ridge Regime was completed within 90 days of each semiannual RCRA groundwater sampling event, as required under by the PCP (Appendix B, Table 3). Based on evaluation of the data, the elevated concentrations of barium, chloride, chromium, and nickel are most likely attributable to natural or in-situ geochemical conditions and, as such, do not serve as reliable indicators of potential contaminant release for the ECRWP (see site-specific statistical data evaluation reports in Appendix E.5).

The elevated nickel and chromium concentrations reported for POC well GW-292 were reported to TDEC in March 2007 in a teleconference initiated by BJC personnel (BJC 2007b). It was agreed that the nickel and chromium concentrations do not indicate a release to groundwater from the ECRWP and are most likely attributable to chemical and/or microbiologically induced corrosion of the stainless steel well casing and/or screen. Furthermore, TDEC personnel suggested retaining well GW-292 in the monitoring network for the ECRWP because, regardless of the false-positive nickel and chromium results, the well is suitable for detection monitoring for the primary contaminants (VOCs and gross alpha activity).

The elevated barium and chloride concentrations in groundwater samples from POC wells GW-292 and GW-293 also were discussed with TDEC personnel. It was agreed that the concentrations reflect natural geochemical variation in the groundwater near the site and the low levels pose no risk to the environment.

As noted previously (see Sect. 4.1.6), the PCP for the Chestnut Ridge Regime requires only three of the five POC wells to be included in each sampling event. Beginning in CY 2008, wells GW-161, GW-296, and GW-298 will serve as the primary POC wells at the site.

6. LEACHATE SAMPLING DATA

As required by the PCP for the Chestnut Ridge Regime (Appendix A, Table 3), samples of the leachate in the collection tank at the ECRWP were collected during CY 2007 and were analyzed for the inorganic constituents, VOCs, and radioanalytes (gross alpha and gross beta activity) specified in the PCP (Attachment 3, Table 3-6). Although the PCP requires annual sample collection, the BJC environmental sampling subcontractor collected the leachate samples semiannually to evaluate the leachate with respect to treatment system waste acceptance criteria. Analytical results for the constituents detected in either leachate sample are summarized below; the complete analytical results for the samples are in Appendix B, Table 16. Note that the leachate sample collected in March 2007 was not analyzed for three of the inorganic analytes because of miscommunication with the analytical laboratory (only one of these analytes, boron, is a RCRA groundwater target compound for the ECRWP). Results for all analytes were obtained for the sample collected in August 2007.

As shown in Table 20, the principal inorganic constituents detected (>20 mg/L) in the leachate samples are chloride and sodium, and the principal VOCs (>10 μ g/L) are 1,1,1-TCA, 1,1-DCA, chloroethane, and 1,2-DCE. Each leachate sample had relatively low levels of gross alpha activity and gross beta activity. These analytical results are consistent with those reported for previous samples of leachate from the ECRWP.

Table 20. Summary of CY 2007 leachate sampling results for the ECRWP

Leachate Analytes	RCRA Groundwater Target Compound	March 2007	August 2007
Inorganics (mg/L)			
Barium	•	0.0406	0.0437
Boron	•	NA	0.332
Chloride	•	41	42.2
Iron	•	0.418	.
Lithium	•	0.136	0.151
Manganese	•	0.0196	.
Nitrate	•	0.34	0.75
Potassium	-	NA	7.88
Sodium	-	NA	20.2
Strontium	-	0.366	0.41
Sulfate	•	6	6.4
Uranium	•	0.0146	0.0115
Organics (µg/L)			
1,1,1-TCA	•	58	24
1,1-DCA	•	360	130
1,2-DCA	•	.	1 J
Chloroethane	-	13	45
PCE	•	2 J	.
c1,2-DCE	•	380	93
1,1-DCE	•	5	2 J
VC	•	.	2 J
trans-1,3-Dichloropropane	-	1 J	.
Radioanalytes (pCi/L)			
Gross alpha activity	•	9.42 ± 1.45	5.84 ± 1.17
Gross beta activity	-	11.5 ± 1.83	10 ± 1.85
Note: NA = Not analyzed. "." = Not detected. J = Estimated concentration.			

Under the site-specific requirements in the PCP for the Chestnut Ridge Regime (Appendix B, Table 3), analytical results for the leachate samples must be evaluated annually to determine if the results warrant the addition of any analytes to the list of RCRA groundwater target compounds specified for the ECRWP (Appendix B, Table 10). As shown in Table 20, the leachate samples contained six analytes that are not included on the list: potassium, sodium, strontium, chloroethane, trans-1,3-dichloropropane, and gross beta activity. Potassium, sodium, and strontium were originally on the list of groundwater target compounds; however, based on waste characterization, these inorganics were removed from the list during the comment/response process for the PCP (Comment #21). As noted in Sect. 4.3.6, chloroethane is not listed as a RCRA groundwater target compound because of a typographical error that identifies "chloromethane" instead (note that chloromethane was not detected in either of the leachate samples collected during CY 2007). The trace level of trans-1,3-dichloropropane detected in the leachate sample collected March 2007 is probably an analytical artifact considering that this compound was not detected in any of the previous leachate samples or in the sample collected in August 2007. Gross beta activity was detected at low levels (<15 pCi/L) in both leachate samples, which is substantially below the SDWA screening level (50 pCi/L) for a 4 millirem per year dose equivalent (the drinking water MCL for gross beta activity).

Aside from correcting the above-noted typographical error such that chloroethane is properly identified in the PCP (Attachment 7, Table 7.1-1), the CY 2007 leachate sampling results do not warrant any additions to the list of RCRA groundwater target compounds specified for the ECRWP. Notably, about half of the RCRA groundwater target compounds (12 trace metals and seven VOCs) were not detected in the leachate samples collected during CY 2007.

7. REFERENCES

- BJC (Bechtel Jacobs Company LLC) 1998. *East End VOC Plume Pump and Tracer Test Technical Memorandum*, BJC/OR-103, Bechtel Jacobs Company LLC, Oak Ridge, TN.
- BJC 2006. *Sampling and Analysis Plan for the Water Resources Restoration Program for Fiscal Year 2007, Oak Ridge Reservation, Oak Ridge, Tennessee*, BJC/OR-2518, Bechtel Jacobs Company LLC, Oak Ridge, TN.
- BJC 2007a. Thompson, R.W., August 28, 2007. BJC letter to M. Apple, TDEC; subject: "Semiannual Post-Closure Groundwater Monitoring Report for the Bear Creek, Chestnut Ridge, and Upper East Fork Poplar Creek Hydrogeologic Regimes at the Y-12 National Security Complex (TN3 89 009 0001); First Semiannual Reporting Period for Calendar Year 2007." Bechtel Jacobs Company LLC, Oak Ridge, TN.
- BJC 2007b. Ketelle, R. and Brucken, E. March 15, 2007. BJC teleconference with C. Bullington, TDEC; subject: Elevated nickel and chromium concentrations in groundwater samples from point-of-compliance well GW-292 at the East Chestnut Ridge Waste Pile.
- Connell, J.F. and Z.C. Bailey 1989. *Statistical and Simulation Analysis of Hydraulic Conductivity Data for Bear Creek and Melton Valleys, Oak Ridge Reservation, Tennessee*. U.S. Geological Survey Water-Resources Investigations Report 89-4062.
- DOE (U.S. Department of Energy) 1995a. *Oak Ridge Reservation Site Management Plan for the Environmental Restoration Program*, DOE/OR-1001/R4, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- DOE 1995b. *Record of Decision for Kerr Hollow Quarry at the Oak Ridge Y-12 Plant, Oak Ridge, Tennessee*, DOE/OR/02-1398&D2, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- DOE 1997. *Report on the Remedial Investigation of Bear Creek Valley at the Oak Ridge Y-12 Plant, Oak Ridge, Tennessee*, DOE/OR/01-1455/V1&D2, Volume 1, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- DOE 1998. *Report on the Remedial Investigation of the Upper East Fork Poplar Creek Characterization Area at the Oak Ridge Y-12 Plant, Oak Ridge, Tennessee*, DOE/OR/01-1641/D1&V1, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.

- DOE 1999. *Action Memorandum for the Oak Ridge Y-12 Plant East End Volatile Organic Compound Plume, Oak Ridge, Tennessee*, DOE/OR/01-1819&D2, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- DOE 2002a. *Record of Decision for Phase I Interim Source Control Actions in the Upper East Fork Poplar Creek Characterization Area at the Oak Ridge Y-12 Plant*, DOE/OR/01-1951&D3, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- DOE 2002b. *2001 Remediation Effectiveness Report/CERCLA Five-Year Review for the U.S. Department of Energy, Oak Ridge Reservation, Oak Ridge, Tennessee*, DOE/OR/01-1941&D2/R1, U.S. Department of Energy, Office of Environmental Management, Oak Ridge, TN.
- Dreier, R.B., Solomon, D.K., and Beaudoin, C.M. 1987. Fracture Characterization in the Unsaturated Zone of a Shallow Land Burial Facility. *Flow and Transport through Fractured Rock*. American Geophysical Union Monograph 42.
- Energy Systems (Martin Marietta Energy System, Inc.) 1984. *Site Characterization of the West Chestnut Ridge Site. Oak Ridge National Laboratory*, ORNL/TM-9229, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1987. *Subsurface-Controlled Geological Maps for the Y-12 Plant and Adjacent Areas of Bear Creek Valley*, TM-10112, Martin Marietta Energy Systems, Inc., Oak Ridge, TN [cited on maps in Appendix A, Fig. 5, pg A-5, and Appendix A, Fig. 6, pg A-6].
- Energy Systems 1988a. *Concepts of Groundwater Flow and Occurrence Near Oak Ridge National Laboratory, Tennessee*, ORNL/TM-10969, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1988. *Summary of Results and Preliminary Interpretation of Hydrogeologic Packer Testing in Core Holes GW-131 Through GW-135 and CH-157, Oak Ridge Y-12 Plant*, Y/TS-495, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1989a. *Groundwater Parameters and Flow System Near Oak Ridge National Laboratory*, ORNL/TM-11368, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1989b. *Development of Ground-Water Flow Models for the S-3 Waste Management Area, Y-12 Plant, Oak Ridge, Tennessee*, Y/SUB/89-00206C/1, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1989c. *Tracer Study of the Hydrologic System of Upper Bear Creek, Y-12 Plant, Oak Ridge, Tennessee*, Y/SUB/89-00206C/4, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1990. *Groundwater Quality Assessment for the Bear Creek Hydrogeologic Regime at the Y-12 Plant, 1989: Data Interpretations and Proposed Modifications*, Y/SUB/90-00206C/1 Part II, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1992a. *Status Report-A Hydrologic Framework for the Oak Ridge Reservation*, ORNL/TM-12053, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1992b. *Supplement to a Hydrogeologic Framework for the Oak Ridge Reservation, Oak Ridge, Tennessee*, ORNL/TM-12191, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.

- Energy Systems 1993a. *Summary of Fiscal Years 1991 and 1992 Construction, Hydrologic, and Geological Data Obtained from the Maynardville Limestone Exit Pathway Monitoring Program*, Y/TS-814, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1993b. *Final Report of the Second Dye-Tracer Test at the Chestnut Ridge Security Pits, Y-12 Plant, Oak Ridge, Tennessee*, Y/SUB/93-99928C/Y10/1, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1994a. *Water Balance Report for the Oak Ridge Y-12 Plant*, SUB/28B-99920C/92-4, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1994b. *Chemical Characteristics of Waters in Karst Formations at the Oak Ridge Y-12 Plant*, Y/TS-1001, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems (Lockheed Martin Energy Systems, Inc.) 1995a. *Distribution of Anthropogenic Fill Material within the Y-12 Plant Area, Oak Ridge, Tennessee*, Y/TS-1387, Lockheed Martin Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1995b. *Stratigraphic Variations and Secondary Porosity within the Maynardville Limestone in Bear Creek Valley, Y-12 Plant, Oak Ridge, Tennessee*, Y/TS-1093, Lockheed Martin Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1995c. *Evaluation of Cross Borehole Tests at Selected Wells in the Maynardville Limestone and Copper Ridge Dolomite at the Oak Ridge Y-12 Plant*, Y/TS-1166, Martin Marietta Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems (Lockheed Martin Energy Systems, Inc.) 1996a. *Calendar Year 1995 Groundwater Quality Report for the Chestnut Ridge Hydrogeologic Regime, Y-12 Plant, Oak Ridge, Tennessee, Part 2: 1995 Groundwater Quality Data Interpretations and Proposed Program Modifications*, Y/SUB/96-KDS15V/2, Lockheed Martin Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1996b. *Effective Porosity and Pore-Throat Sizes of Conasauga Group Mudrock: Application, Test, and Evaluation of Petrophysical Techniques*, ORNL/GWPO-021, Lockheed Martin Energy Systems, Inc., Oak Ridge, TN.
- Energy Systems 1997a. Jones, S.B. February 12, 1998. Energy Systems letter to J.R. Walker, AJA Technical Services, Inc.; subject: "Hydraulic Conductivity Estimates from Landfills in the Chestnut Ridge Hydrogeologic Regime at the Y-12 Plant, 1994-1997."
- Energy Systems 1997b. *Effective Porosity and Density of Carbonate Rocks (Maynardville Limestone and Copper Ridge Dolomite) within the Bear Creek Valley on the Oak Ridge Reservation Based on Modern Petrophysical Techniques*, ORNL/GWPO-026, Lockheed Martin Energy Systems, Inc., Oak Ridge, TN.
- EPA (U.S. Environmental Protection Agency) 1988. *Laboratory Validation Functional Guidelines for Evaluating Organics Analyses*.
- Gee, G.W., Rai, D., and Serne, R.J. 1983. Mobility of Radionuclides in Soil. In: *Chemical Mobility and Reactivity in Soil Systems*. Soil Science Society of America, Inc. Madison, WI (pp 203-227).

- McCarty, P.I. 1996. *Biotic and Abiotic Transformations of Chlorinated Solvents in Groundwater*. Reported in: Symposium on Natural Attenuation of Chlorinated Organics in Groundwater, EPA/540/R-96/509, U.S. Environmental Protection Agency, Office of Research and Development
- Moore, G.K. 1992. Hydrograph analysis in fractured rock terrain. *Ground Water*, Vol. 30, No. 3, pp. 390-395.
- Quinlan, J.F. and R.O. Ewers. 1985. *Groundwater Flow in Limestone Terrains: Strategy, Rationale and Procedure for Reliable, Efficient Monitoring of Groundwater Quality in Karst Areas*. National Symposium and Exposition on Aquifer Restoration and Groundwater Monitoring Proceedings, National Water Well Association, Worthington, OH (pp. 197-234).
- TDEC (Tennessee Department of Environment and Conservation) 1997. *Recognition of Class 1 and Class'1 Modifications, New Hope Pond and Eastern S-3 Pond Units (Post Closure Permit), Y-12, Upper East Fork Poplar Creek Hydrogeologic Regime*. Letter to the U.S. Department of Energy and Lockheed Martin Energy Systems, Inc.
- TDEC 2006. *Final Post-Closure Issuance, Chestnut Ridge Hydrogeologic Regime, U.S. DOE Y-12 National Security Complex, Oak Ridge, Tennessee, EPA ID Number: TN3 89 009 001, TN Permit Number: TNHW-128*, September 29, 2006.
- ThermoNUTech 1999. Personal communication from W. McDowell to T.R. Harrison, AJA Technical Services, Inc., regarding analytical interferences associated with kinetic phosphorescent analysis for uranium.
- Watson, K.W. and R.J. Luxmoore. 1986. *Estimating Macroporosity in a Forested Watershed by use of a Tension Infiltrometer*. Soil Science Society of America, Journal 50 (pp. 578-582).
- Weidemeier, T.H., H.S. Rifai, G.J. Newell, and J.T. Wilson. 1999. *Natural Attenuation of Fuels and Chlorinated Solvents in the Subsurface*. John Wiley & Sons, Inc., New York, NY.
- Wilson, G.V. and R.J. Luxmoore. 1988. *Infiltration, Macroporosity, and Mesoporosity Distributions of two Forested Watersheds*. Soil Science Society of America, Journal 52 (pp. 329-355).

APPENDIX A

FIGURES

FIGURES

1	Hydrogeologic regimes at the Y-12 National Security Complex.....	A-4
2	Waste management sites and regulated units in the Bear Creek Hydrogeologic Regime	A-5
3	Fill areas and preconstruction drainage features in the Upper East Fork Poplar Creek Hydrogeologic Regime.....	A-6
4	Waste management sites in the Chestnut Ridge Hydrogeologic Regime	A-7
5	Topography and bedrock geology in the Bear Creek Hydrogeologic Regime.....	A-8
6	Topography and bedrock geology in the Upper East Fork Poplar Creek Hydrogeologic Regime.....	A-9
7	Topography and bedrock geology in the Chestnut Ridge Hydrogeologic Regime	A-10
8	Groundwater elevations in the Bear Creek Hydrogeologic Regime, April 2007	A-11
9	Groundwater elevations in the Upper East Fork Poplar Creek Hydrogeologic Regime, April 2007	A-12
10	Groundwater elevations in the Chestnut Ridge Hydrogeologic Regime, April 2007	A-13
11	Generalized extent of groundwater contamination in the Bear Creek Hydrogeologic Regime.....	A-14
12	Generalized extent of groundwater contamination in the Upper East Fork Poplar Creek Hydrogeologic Regime.....	A-15
13	Generalized extent of groundwater contamination in the Chestnut Ridge Hydrogeologic Regime.....	A-16
14	RCRA post-closure groundwater monitoring locations in the Bear Creek Hydrogeologic Regime	A-17
15	RCRA post-closure groundwater monitoring locations in the Upper East Fork Poplar Creek Hydrogeologic Regime	A-18
16	RCRA post-closure groundwater monitoring locations in the Chestnut Ridge Hydrogeologic Regime	A-19
17	Nitrate, Tc-99, PCE, and uranium concentration trends at S-3 Site point-of-compliance well GW-276.....	A-20
18	PCE, TCE, and c12DCE concentration trends at Oil Landfarm point-of-compliance well GW-008.....	A-21

19	Concentration trends for selected VOCs at Bear Creek Burial Grounds/ Walk-In Pits point-of-compliance well GW-046	A-22
20	Nitrate, chloroform, and Tc-99 concentration trends at Eastern S-3 Site Plume point-of-compliance well GW-108	A-23
21	111TCA and 11DCA concentration trends at Chestnut Ridge Security Pits point-of-compliance well GW-177	A-24
22	Nitrate concentration trends at RCRA plume boundary well GW-714 and spring SS-6	A-25

Fig. 1. Hydrogeologic regimes at the Y-12 National Security Complex.

Fig. 2. Waste management sites and regulated units in the Bear Creek Hydrogeologic Regime.

Fig. 3. Fill areas and preconstruction drainage features in the Upper East Fork Poplar Creek Hydrogeologic Regime.

SOURCE: Energy Systems 1995b

0 1400
SCALE (ft)

EXPLANATION

- FILL THICKNESS GREATER THAN OR EQUAL TO 5 FT

- BURIED TRIBUTARY (BT-)

- SPRING

Fig. 4. Waste management sites in the Chestnut Ridge Hydrogeologic Regime.

Fig. 5. Topography and bedrock geology in the Bear Creek Hydrogeologic Regime.

A-8

SOURCE: Energy Systems 1987

0 1000
SCALE (ft)

SYSTEM	GROUP	HYDRO UNIT	FORMATION	MAP SYMBOL	THICKNESS (ft)
CAMBRIAN	UPPER	WINDY	COPPER RIDGE DOLOMITE	Ock	NOT DETERMINED
			MAYNARDVILLE LIMESTONE	Emn	418-450
	MIDDLE	CONASAUGA	NOLICHUCKY SHALE	En	422-550
			MARYVILLE LIMESTONE	Cm	346-445
			ROGERSVILLE SHALE	Cr	90-120
			RUTLEDGE LIMESTONE	Cr	90-120
			PUMPKIN VALLEY SHALE	Epv	260-320
	LOWER	AQUITARD	ROME	Cr	NOT DETERMINED

Fig. 6. Topography and bedrock geology in the Upper East Fork Poplar Creek Hydrogeologic Regime.

SOURCE: Energy Systems 1987

0 1800
SCALE (ft)

▲ AQUITARD ▲ AQUIFER

SYSTEM	GROUP	HYDRO UNIT	FORMATION	MAP SYMBOL	THICKNESS (ft)
CAMBRIAN	UPPER	AQUICL	COPPER RIDGE DOLOMITE	OSK	NOT DETERMINED
			WAYNADVILLE LIMESTONE	Cmn	418-450
	MIDDLE	AQUITARD	NOLICHUCKY SHALE	Cn	422-550
			MARYVILLE LIMESTONE	Cm	345-445
			ROGERSVILLE SHALE	Crg	90-120
			RUTLEDGE LIMESTONE	Crt	90-120
			PUMPKIN VALLEY SHALE	Cpv	260-320
			ROME FORMATION	Cr	NOT DETERMINED
	LOWER				

Fig. 7. Topography and bedrock geology in the Chestnut Ridge Hydrogeologic Regime.

SOURCES: Energy Systems 1987
Energy Systems 1992b

0 2000
SCALE (ft)

AQUITARD KNOX AQUIFER

SYSTEM		HYDRO UNIT	GROUP	FORMATION	MAP SYMBOL	THICKNESS (FT)
ORDOVICIAN	UPPER	AQUITARD	CHICKA-MAUGA	UNDIFFERENTIATED	Och	1500 TO 2000
	MIDDLE	KNOX AQUIFER	KNOX	MISSING SECTION (Subaerial Erosion)		
	LOWER			WASCOT DOLOMITE	Omd	250-400
				KINGSPOUT FORMATION	Ok	300-500
				LONGVIEW DOLOMITE	Oi	130-280
				CHEPULTEPEC DOLOMITE	Oc	500-700
CAMBRIAN	UPPER	AQUITARD	CONASAUGA	COPPER RIDGE DOLOMITE	Ocr	800-1,100
	MIDDLE			MAYNARDVILLE LIMESTONE	Oma	475-450
				NOLICHUCKY SHALE	Cn	490-590

Note: Plume boundary wells are located about 5,000 feet west of map area

GROUNDWATER ELEVATIONS APRIL 9-17, 2007

EXPLANATION

- WATER TABLE INTERIM MONITORING WELL
- RCR (POINT OF COMPLIANCE) MONITORING WELL
- WATER TABLE ELEVATION (FOOT)
- SURFACE DRAINAGE FEATURE

GROUNDWATER ELEVATIONS APRIL 9-12, 2007

EXPLANATION

- WATER TABLE INTERVAL MONITORING WELL
- RCRA POINT-OF-COMPLIANCE MONITORING WELL
- ★ RCRA PLUME DELINEATION MONITORING WELL

- APPROXIMATE WATER-LEVEL ISOPLETH (ft msl)
- SURFACE DRAINAGE FEATURE
- BUILDING 19201-2 SUMP
- EXTRACTION WELL AND APPROXIMATE ZONE OF INFLUENCE

Fig. 9. Groundwater elevations in the Upper East Fork Poplar Creek Hydrogeologic Regime, April 2007.

Fig. 10 Groundwater elevations in the Chestnut Ridge Hydrologic Regime, April 2007

Fig. 11. Generalized extent of groundwater contamination in the Bear Creek Hydrogeologic Regime.

EXPLANATION

VTPATL

VTCs

PAL DACTIVITY
(GROSS ALPHA AND GROSS BETA)

Fig. 12 Generalized extent of groundwater contamination in the Upper East Fork Poplar Creek Hydrogeologic Regime

Fig. 13. Generalized extent of groundwater contamination in the Chestnut Ridge Hydrogeologic Regime.

EXPLANATION

- — BEDROCK MONITORING WELL
- - - SURFACE DRAINAGE FEATURE
- BOUNDARY OF SITE
- ▨ — SLIMMED VOC's > 5µg/L

- 111TCA 1,1,1-TRICHLOROETHANE
- 11DCA 1,1-DICHLOROETHANE
- 11DCE 1,1-DICHLOROETHENE
- 112DCE CIS-1,2-DICHLOROETHENE
- PCE TETRACHLOROETHENE
- TCFM TRICHLOROFLUOROMETHANE
- — INFERRED GROUNDWATER CONTAMINANT PATHWAY

Fig. 14. RCRA post-closure groundwater monitoring locations in the Bear Creek Hydrogeologic Regime.

Fig. 15, RCRA post-closure groundwater monitoring locations in the Upper East Fork Poplar Creek Hydrogeologic Regime.

A-18

Fig. A.16. RCRA post-closure groundwater monitoring locations in the Chestnut Ridge Hydrogeologic Regime.

A-19

EXPLANATION

- ▲ - RCRA Background/Upgradient Monitoring Well
- ⊙ - RCRA Point-of-Compliance Monitoring Well
- ★ - RCRA Plume Delineation Monitoring Well
- - RCRA Plume Delineation Spring Sampling Location

Cmn	=	Waynesville Upland	- - -	Surface Drainage Feature
Ock	=	Knox Group	- - -	Boundary of SHs
Och	=	Chickamauga Group	- - -	Surface Geologic Contact

Notes: MCLs: Nitrate = 10 mg/L; PCE = 5 µg/L; Uranium = 0.03 mg/L.

Fig. 17. Nitrate, Tc-99, PCE, and uranium concentration trends at S-3 Site point-of-compliance well GW-276.

Fig. 18. PCE, TCE, and c12DCE concentration trends at Oil Landfarm point-of-compliance well GW-008.

Notes: MCLs: Benzene and PCB = 5 µg/L; c12DCE = 70 µg/L; 111TCA = 200 µg/L; 11DCA = not applicable.

TrendFigs07

Fig. 19. Concentration trends for selected VOCs at Bear Creek Burial Grounds/
Walk-in Pits point-of-compliance well GW-046.

TrendFigs07

Fig. 20. Nitrate, chloroform, and Tc-99 concentration trends at Eastern S-3 Site Plume point-of-compliance well GW-108.

Note: MCL for 111TCA = 200 µg/L

Results for 111TCA that are <5 µg/L are estimated values

TrendFigs07

Fig. 21. 111TCA and 11DCE concentration trends at Chestnut Ridge Security Pits point-of-compliance well GW-177.

Notes: Only results that meet DQOs are plotted; nitrate MCL = 10 mg/L.

Fig. 22. Nitrate concentration trends at RCRA plume boundary well GW-714 and spring SS-6.

APPENDIX B
TABLES

TABLES

1	Index of RCRA post-closure permit conditions for groundwater monitoring in the Bear Creek Hydrogeologic Regime	B-5
2	Index of RCRA post-closure permit conditions for groundwater monitoring in the Upper East Fork Poplar Creek Hydrogeologic Regime.....	B-6
3	Index of RCRA post-closure permit conditions for groundwater monitoring in the Chestnut Ridge Hydrogeologic Regime	B-7
4	Waste management sites and RCRA-regulated units in the Bear Creek Hydrogeologic Regime.....	B-9
5	Sources of groundwater contaminant signatures in the Upper East Fork Poplar Creek Hydrogeologic Regime.....	B-10
6	Waste management sites and RCRA-regulated units in the Chestnut Ridge Hydrogeologic Regime.....	B-11
7	Construction details for RCRA groundwater monitoring wells at the Y-12 National Security Complex	B-13
8	Field measurements and RCRA groundwater target compounds for the S-3 Site, Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits	B-20
9	Field measurements and RCRA groundwater target compounds for the Eastern S-3 Site Plume.....	B-22
10	Field measurements and RCRA groundwater target compounds for the Chestnut Ridge Security Pits, Chestnut Ridge Sediment Disposal Basin, Kerr Hollow Quarry, and East Chestnut Ridge Waste Pile	B-24
11	Laboratory blanks and trip blanks associated with CY 2007 RCRA post-closure groundwater monitoring at the Y-12 National Security Complex	B-26
12	Volatile organic compounds detected in the laboratory blanks and trip blanks associated with CY 2007 RCRA post-closure groundwater monitoring at the Y-12 National Security Complex.....	B-28
13	Depth-to-water measurements and groundwater elevations for selected wells in the Bear Creek Hydrogeologic Regime, April 2007.....	B-31
14	Depth-to-water measurements and groundwater elevations for selected wells in the Upper East Fork Poplar Creek Hydrogeologic Regime, April 2007.....	B-33
15	Depth-to-water measurements and groundwater elevations for selected wells in the Chestnut Ridge Hydrogeologic Regime, April 2007.....	B-36
16	CY 2007 leachate sampling results for the East Chestnut Ridge Waste Pile.....	B-39

This page intentionally left blank.

**Table 1. Index of RCRA post-closure permit conditions for groundwater monitoring
in the Bear Creek Hydrogeologic Regime**

Section(s) of RCRA Annual Monitoring Report				
Monitoring Requirement	Post-Closure Permit Condition/Attachment ¹			
	S-3 Site	Oil Landfarm	Burial Grounds/ Walk-In Pits	
Groundwater Monitoring System	IV.C	V.C	VI.C	4.
Point-of-Compliance Wells	IV.C.1(a)	IV.C.1(b)	IV.C.1(c)	4.1.1
Plume Boundary Wells	IV.C.2	IV.C.2	IV.C.2	4.1.1
Sampling and Analysis	IV.E	IV.E	IV.E	4.
Sampling Frequency	IV.D.1(a),(d)	IV.D.1(b),(d)	IV.D.1(c),(d)	4.1.1
Sample Collection	IV.D.2(a) Attach. 7, Sect. A	IV.D.2(a) Attach. 7, Sect. A	IV.D.2(a) Attach. 7, Sect. A	4.2
Sample Containers and Preservation	IV.D.2(b)	IV.D.2(b)	IV.D.2(b)	4.3
Sample Transportation	IV.D.2(c)	IV.D.2(c)	IV.D.2(c)	4.3
Sample Chain-of-Custody Control	IV.D.2(d)	IV.D.2(d)	IV.D.2(d)	4.3
Laboratory Analytes (RCRA groundwater target constituents) (RCRA plume boundary constituents)	IV.D.3(a),(d) Attach. 7, Sect. G Attach. 7, Sect. J	IV.D.3(b),(d) Attach. 7, Sect. H Attach. 7, Sect. J	IV.D.3(c),(d) Attach. 7, Sect. I Attach. 7, Sect. J	4.3.1
Analytical Methods	I.D.9(a) and IV.D.4	I.D.9(a) and IV.D.4	I.D.9(a) and IV.D.4	4.3
Groundwater Surface Elevation	IV.E	IV.E	IV.E	4.3.1
Monitoring Data Evaluation	IV.F	IV.F	IV.F	5.
Groundwater Flow Rate and Direction	IV.F.1(e)	IV.F.1(e)	IV.F.1(e)	5.1.1
Point-of-Compliance Concentration Data	IV.F.1(a)	IV.F.1(b)	IV.F.1(c)	5.2.1 5.2.2 5.2.3
Plume Boundary Concentration Data	IV.F.1(d)	IV.F.1(d)	IV.F.1(d)	5.3.1
Annual Reporting	I.D.11(g)	I.D.11(g)	I.D.11(g)	1.
Signed Certification Statement	II.E.3(d)	II.E.3(d)	II.E.3(d)	Pg. ix
RCRA Facility Information	II.E.3(a)	II.E.3(a)	II.E.3(a)	Pg. ix
Groundwater Monitoring Data (September 1 Deadline) (March 1 Deadline)	II.E.3(c) IV.G.2 IV.G.4	II.E.3(c) IV.G.2 IV.G.4	II.E.3(c) IV.G.2 IV.G.4	App. C

Note: 1. Tennessee Department of Environment and Conservation permit no. TNHW-116

**Table 2. Index of RCRA post-closure permit conditions for groundwater monitoring
in the Upper East Fork Poplar Creek Hydrogeologic Regime**

Monitoring Requirement	Post-Closure Permit Condition/Attachment¹	Section(s) of RCRA Annual Monitoring Report
Groundwater Monitoring System	IV.C	4.
Point-of-Compliance Wells	IV.C.1	4.1.2
Plume Boundary Wells	IV.C.2	4.1.2
Sampling and Analysis	IV.E	4.
Sampling Frequency	IV.D.1	4.1.2
Sample Collection	IV.D.2(a) Attach. 6, Sect D	4.2
Sample Containers and Preservation	IV.D.2(b)	4.3
Sample Transportation	IV.D.2(c)	4.3
Sample Chain-of-Custody Control	IV.D.2(d)	4.3
Laboratory Analytes (RCRA groundwater target constituents) (RCRA plume boundary constituents)	IV.D.3 Attach. 7, Sect. G Attach. 7, Sect. H	4.3.2
Analytical Methods	IV.D.4 and I.D.9(a)	4.3
Groundwater Surface Elevation	IV.E	4.3.2
Monitoring Data Evaluation	IV.F	5.
Groundwater Flow Direction and Rate	IV.F.1(c)	5.1.1
Point-of-Compliance Data	IV.F.1(a)	5.2.4
Plume Boundary Data	IV.F.1(b)	5.3.2
Annual Reporting	I.D.11(g)	1.
Signed Certification Statement	II.E.3(d)	Page ix
RCRA Facility Information	II.E.3(a)	Page ix
Groundwater Monitoring Data (September 1 Deadline) (March 1 Deadline)	II.E.3(e) IV.G.2 IV.G.4	Appendix D

Note: 1. Tennessee Department of Environment and Conservation permit no. TNHW-113

Table 3. Index of RCRA post-closure permit conditions for groundwater monitoring in the Chestnut Ridge Hydrogeologic Regime

Requirements	Section of Annual RCRA Monitoring Report				
	Post-Closure Permit Condition/Attachment ¹				
	CRSP	CRSDB	ECRWP	KHQ	
Groundwater Monitoring Program	IV.F.3.(b); Attach. 7.3, Sect. 7.3.3	IV.F.3.(a); Attach. 7.3, Sect. 7.3.2	IV.F.3.(a); Attach. 7.3, Sect. 7.3.2	IV.F.3.(a); Attach. 7.3, Sect. 7.3.2	
Groundwater Monitoring Network	IV.B.1 Attach. 7.2	IV.B.1 Attach. 7.2	IV.B.1 Attach. 7.2	IV.B.1 Attach. 7.2	4.
Upgradient/Background Wells	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	4.1.3 4.1.4 4.1.5 4.1.6
Point-of-Compliance Wells	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	4.1.3 4.1.4 4.1.5 4.1.6
Plume Boundary Wells	Attach. 7.3, Sect. 7.3.4 & Table 7.3-1	NA	NA	NA	4.1.3
Well Plugging and Abandonment	IV.B.2; Attach. 6.4	IV.B.2; Attach. 6.4	IV.B.2; Attach. 6.4	IV.B.2; Attach. 6.4	NA
Groundwater Sampling and Analysis	IV.C				4.
Groundwater Sampling Method	IV.C.1; Attach. 6.1	IV.C.1; Attach. 6.1	IV.C.1; Attach. 6.1	IV.C.1; Attach. 6.1	4.2
Surface Water Sampling Method	IV.C.2; Attach. 6.2	NA	NA	NA	4.2
Sampling Frequency	Attach. 7.3, Sect. 7.3.7	Attach. 7.3, Sect. 7.3.7	Attach. 7.3, Sect. 7.3.7	Attach. 7.3, Sect. 7.3.7	4.1.3 4.1.4 4.1.5 4.1.6
Sample Containers and Preservation	IV.C.3; Attach. 6.1 Attach. 6.2	IV.C.3; Attach. 6.1	IV.C.3; Attach. 6.1	IV.C.3; Attach. 6.1	4.3
Sample Transportation	IV.C.4; Attach. 6.1 Attach. 6.2	IV.C.4; Attach. 6.1	IV.C.4; Attach. 6.1	IV.C.4; Attach. 6.1	4.3
Sample Chain-of-Custody Control	IV.C.5; Attach. 6.1 Attach. 6.2	IV.C.5; Attach. 6.1	IV.C.5; Attach. 6.1	IV.C.5; Attach. 6.1	4.3
Timeframe for Laboratory Analyses	IV.C.6	IV.C.6	IV.C.6	IV.C.6	4.3
Laboratory Analytical Methods	IV.C.6; Attach. 6.6; Attach. 7.3, Sect. 7.3.6	IV.C.6; Attach. 6.6; Attach. 7.3, Sect. 7.3.6	IV.C.6; Attach. 6.6; Attach. 7.3, Sect. 7.3.6	IV.C.6; Attach. 6.6; Attach. 7.3, Sect. 7.3.6	4.3
QA/QC Sampling	IV.C.7; Attach. 6.6	IV.C.7; Attach. 6.6	IV.C.7; Attach. 6.6	IV.C.7; Attach. 6.6	4.4

Table 3 (continued)

Monitoring Requirement	Section of Annual RCRA Monitoring Report				
	Post-Closure Permit Condition/Attachment ¹				
	CRSP	CRSDB	ECRWP	KHQ	
RCRA Groundwater Target Compounds	IV.E.1; Attach. 7.1, Table 7.1-1; Attach. 7.3, Sect. 7.3.5	IV.E.1; Attach. 7.1, Table 7.1-1; Attach. 7.3, Sect. 7.3.5	IV.E.1; Attach. 7.1, Table 7.1-1; Attach. 7.3, Sect. 7.3.5	IV.E.1; Attach. 7.1, Table 7.1-1; Attach. 7.3, Sect. 7.3.5	4.3.3 4.3.4 4.3.5 4.3.6
Groundwater Surface Elevations	IV.D Attach. 6.1	IV.D Attach. 6.1	IV.D Attach. 6.1	IV.D Attach. 6.1	4.3.3 4.3.4 4.3.5 4.3.6
Monitoring Data Evaluation	IV.F				5.
Groundwater Flow Direction/Rate	IV.F.1	IV.F.1	IV.F.1	IV.F.1	5.1.2
Point-of-Compliance Concentration Data	Attach. 7.5, Sect. 7.5.3	Attach. 7.4, Sect. 7.4.3	Attach. 7.4, Sect. 7.4.3	Attach. 7.4, Sect. 7.4.3	5.2.5 5.4.1 5.4.2 5.4.3
Plume Boundary Data	Attach. 7.5, Sect. 7.5.5	NA	NA	NA	5.3.3
Elevated Concentration Verification	NA	Attach. 7.4, Sect. 7.4.5	Attach. 7.4, Sect. 7.4.5	Attach. 7.4, Sect. 7.4.5	5.4.1 5.4.2 5.4.3
Statistically Significant Concentration Increase	NA	Attach. 7.4, Sect. 7.4.6	Attach. 7.4, Sect. 7.4.6	Attach. 7.4, Sect. 7.4.6	5.4.1 5.4.2 5.4.3
Confirmation Sampling	NA	Attach. 7.4, Sect. 7.4.7	Attach. 7.4, Sect. 7.4.7	Attach. 7.4, Sect. 7.4.7	5.4.1 5.4.2 5.4.3
Annual Reporting	II.E; IV.G.4; Attach. 7.3, Sect. 7.3.8				1.
Certification Statement	II.E.3.(d)	II.E.3.(d)	II.E.3.(d)	II.E.3.(d)	Pg. ix
RCRA Facility Information	II.E.3.(a)	II.E.3.(a)	II.E.3.(a)	II.E.3.(a)	Pg. ix
Groundwater Monitoring Data (September 1 Deadline)	II.E.3.(c) IV.G.2	II.E.3.(c) IV.G.2	II.E.3.(c) IV.G.2	II.E.3.(c) IV.G.2	App. E
(March 1 Deadline)	IV.G.4	IV.G.4	IV.G.4	IV.G.4	
Monitoring Data Evaluation	IV.F.1 Attach. 7.3, Sect. 7.3.8	IV.F.1 Attach. 7.3, Sect. 7.3.8	IV.F.1 Attach. 7.3, Sect. 7.3.8	IV.F.1 Attach. 7.3, Sect. 7.3.8	5.
Leachate Data Summary and Evaluation	NA	NA	Attach. 7.3, Sect. 7.3.8	NA	6.

Note: 1. Tennessee Department of Environment and Conservation permit no. TNHW-128
NA = Not applicable

Table 4. Waste management sites and RCRA-regulated units in the Bear Creek Hydrogeologic Regime

Waste Management Site/ Regulated Unit	Regulatory Classification ¹	General Waste Inventory	Operational Status	
			Closed	Open
Above Grade Low-Level Storage Facility	NR	Low-level radioactive construction and demolition wastes.	.	●
Boneyard, Burnyard, and Hazardous Chemical Storage Area	CERCLA	Magnesium chips, construction debris, pesticide containers, metal shavings, solvents, oils, laboratory chemicals, acids, bases, organics, water-reactive compounds, and shock sensitive compounds.	●	.
Burial Grounds A (North and South)	RCRA/ CERCLA	Waste oils, coolants, and spent solvents.	●	.
Burial Grounds C (West)	RCRA/ CERCLA	Waste oils, coolants, and spent solvents.	●	.
Burial Grounds B, D, E, and J	CERCLA	Solid wastes including salts, metals (beryllium and uranium) and metal oxides, metal saw fines, and asbestos.	●	.
Environmental Management Waste Management Facility	CERCLA	Wastes generated from CERCLA remediation actions.	.	●
Oil Landfarm	RCRA/ CERCLA	Waste oils and coolants containing beryllium compounds, depleted uranium, polychlorinated biphenyls, and spent solvents.	●	.
Oil Retention Pond No. 1	CERCLA	Oil seepage from Burial Ground A South.	●	.
Oil Retention Pond No. 2	CERCLA	Oil seepage from Burial Ground A North.	●	.
Receptor Media	CERCLA	Contaminated groundwater, surface water, Bear Creek stream sediments, and Bear Creek flood plain soils.	Not Applicable	
Rust Spoil Area	CERCLA	Nonradioactive construction debris.	●	.
Sanitary Landfill I	CERCLA	Nonhazardous solid wastes.	●	.
Spoil Area I	CERCLA	Nonradioactive construction debris.	●	.
SY-200 Yard	CERCLA	Temporary storage of equipment, machinery, and miscellaneous items.	●	.
S-3 Site	RCRA/ CERCLA	Liquid, radioactive, nitric acid wastes and denitrification products.	●	.
Walk-In Pits	RCRA/ CERCLA	Chemical wastes, shock-sensitive reagents, and uranium metal saw fines.	●	.

Notes:

1 From: U.S. Department of Energy 1995. *Oak Ridge Reservation Site Management Plan for the Environmental Restoration Program*. U.S. Department of Energy Oak Ridge Field Office, DOE/OR-1001/R4.

CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act of 1980

RCRA = Resource Conservation and Recovery Act of 1976

NR = Not regulated under RCRA or CERCLA

**Table 5. Sources of groundwater contaminant signatures in the
Upper East Fork Poplar Creek Hydrogeologic Regime**

Confirmed and Suspected Sources of Contamination ¹	Groundwater Contaminant Signature			
	Inorganics	Organics	Metals	Radionuclides
Western Y-12 Area				
Eastern S-3 Site Plume	●	●	●	●
Salvage Yard		●	●	●
Rust Garage Area		●		
Waste Coolant Processing Area		●	●	●
Building 9204-4		●	●	
Fire Training Facility		●		
Interim Drum Yard Vicinity		●		
S-2 Site	●	●	●	●
Central Y-12 Area				
Buildings 9201-4 and 9201-5		●	●	
Building 9731 Vicinity		●		●
Building 9212 Vicinity		●		
Tank 0134-U		●	●	●
Building 81-10			●	●
Buildings 9201-1 and 9201-2		●	●	
Tank 2331-U		●	●	
Eastern Y-12 Area				
East End Garage (Building 9754-2)		●		
Uranium Oxide Vault			●	●
Wells GW-605 and GW-606 Vicinity				●
Former Oil Skimmer Basin			●	●
East End VOC Plume		●		
Building 9720-6 Vicinity		●		

Note:

¹ Modified from DOE (1998), Appendix D, Section D.5

Table 6. Waste management sites and RCRA-regulated units in the Chestnut Ridge Hydrogeologic Regime

Waste Management Site/ Regulated Unit	Regulatory Classification ¹	General Waste Inventory	Status	
			Active	Closed
Chestnut Ridge Sediment Disposal Basin	RCRA/ CERCLA	Approximately 11,100 yd ³ of sediments and soils from Y-12 that contain heavy metals; approximately 100,000 gallons of methanol-brine waste (70/30% water/methyl alcohol); and 55-110 gallons of toluene.	.	●
East Chestnut Ridge Waste Pile	RCRA/ CERCLA	Approximately 3800 yd ³ of contaminated soil from Y-12.	.	●
Kerr Hollow Quarry	RCRA/ CERCLA	Approximately 50 tons of water-reactive materials (alkali metals, metal hydrides); unstable organic materials (picric acid, ethers, peroxides, and hydrazone); reactive metals (phosphorous and magnesium); potentially explosive materials (e.g., gas cylinders); ammonia; and inorganic acids.	.	●
Chestnut Ridge Security Pits	RCRA/ CERCLA	Metals (lead); reactive materials (lithium hydride, lithium deuteride, zirconium); corrosive materials (acids); ignitable materials (alcohols); and chlorinated solvents.	.	●
Filled Coal Ash Pond (formerly the Ash Disposal Basin)	CERCLA	Coal fly-ash slurry from the Y-12 Steam Plant.	.	●
United Nuclear Corporation Site	CERCLA	Approximately 11,000 drums (55-gallon) of sludge fixed in cement, 18,000 drums of contaminated soil, and 288 boxes of contaminated process and demolition material.	.	●
Rogers Quarry	CERCLA	Coal fly-ash slurry that bypassed the Filled Coal Ash Pond via spillway into McCoy Branch.	.	●
Chestnut Ridge Borrow Area Waste Pile	CERCLA	Soils removed from the Oak Ridge Civic Center properties and the Oak Ridge Sewer Line Beltway contaminated with mercury and other metals, and possibly some organic compounds that originated from Y-12. All soil was removed from the site in CY 2000.	.	●
Industrial Landfill II	SWDF	Combustible and decomposable solid waste and construction spoil material including scrap metal, glass, paper products, plastics, wood, organic garbage, textile products, asphalt roofing materials, and special wastes such as asbestos and beryllium oxide.	.	●
Industrial Landfill IV	SWDF	Approximately 12,000 ft ³ per year of non-hazardous, nonradioactive industrial wastes including cardboard, plastics, rubber, scrap metal, wood, paper, and special waste.	●	.

Table 6 (continued)

Waste Management Site/ Regulated Unit	Regulatory Classification ¹	General Waste Inventory	Status	
			Active	Closed
Industrial Landfill V	SWDF	Combustible/decomposable solid wastes.	●	.
Construction/Demolition Landfill VI	SWDF	Construction spoil: concrete, wood, metal, plastic, roofing materials, and soil.	.	●
Construction/Demolition Landfill VII	SWDF	Construction spoil: concrete, wood, metal, plastic, roofing materials, and soil.	●	.

Notes:

1. CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act of 1980
RCRA = Resource Conservation and Recovery Act of 1976
SWDF = Solid Waste Disposal Facility (nonhazardous waste)

Table 7. Well construction details

Well Number Permit (TNHW-)	GW-008 116	GW-046 116	GW-108 113	GW-143 128	GW-144 128	GW-145 128
Hydrogeologic Regime ¹	BC	BC	EF	CR	CR	CR
Monitoring Program	C. Action	C. Action	C. Action	Detection	Detection	Detection
Monitoring Purpose ²	POC	POC	POC	POC	POC	POC
TSD Unit ³	OLF	BG	S3 East	KHQ	KHQ	KHQ
General Information⁴						
Date Installed	09/21/83	10/27/83	09/26/84	10/24/85	10/24/85	10/14/85
Total Depth Drilled	25.5	20.5	58.6	253.0	195.0	110.0
East Coordinate	47,596	43,284	53,207	63,522	63,502	63,266
North Coordinate	29,783	29,562	30,070	24,257	24,255	24,441
Measuring Point Elevation	965.39	921.17	999.00	913.98	913.54	840.24
Ground Surface Elevation	962.11	918.13	995.80	911.04	910.48	837.29
Hydrostratigraphic Unit	Aquitard	Aquitard	Aquitard	Aquifer	Aquifer	Aquifer
Geologic Formation	Cn	Cn	Cn	OCk	Ock/Och	OCk
Aquifer Zone	WT	WT	BDR	BDR	BDR	BDR
Weathered Rock-Depth	0.6	7.7	4.0	.	.	.
Fresh Rock-Depth	.	.	.	18.0	40.0	12.0
Surface Casing⁵						
Casing Depth	.	.	20.7	20.0	40.0	12.0
Outside Diameter	.	.	10.63	10.63	12.5	12.5
Casing Material	.	.	PVC40	PVC40	PVC40	PVC40
Well Casing⁶						
Borehole Depth	25.5	20.5	58.6	205.0	195.0	110.0
Borehole Diameter	4.5	6	9	10	11	11
Casing Depth	15.7	8.1	46.7	205.0	150.0	88.5
Outside Diameter	2.37	2.37	4.5	6.62	4.5	4.5
Casing Material	SS304	SS304	PVC40	SF25	PVC40	PVC40
Monitored Interval⁷						
Top-Depth	13.0	5.0	41.0	205.0	148.0	86.0
Top-Elevation	949.11	913.13	954.80	706.04	762.48	751.29
Midpoint-Depth	19.3	12.7	49.8	229.0	171.5	98.0
Midpoint-Elevation	942.86	905.48	946.00	682.04	738.98	739.29
Bottom-Depth	25.5	20.3	58.6	253.0	195.0	110.0
Bottom-Elevation	936.61	897.83	937.20	658.04	715.48	727.29
Screen Material	SS/sw/.01	SS/sw/.01	PVC/sl/.01	.	PVC/sw/.01	PVC/sw/.01
Screen Length	5	10	9	.	40	20
Open-Hole Length	.	.	.	48	.	.
Open-Hole Diameter	.	.	.	6	.	.
Dedicated Pump Intake⁸						
Depth	17.7	12.0	49.8	226.1	170.9	100.0
Elevation	944.39	906.17	946.00	684.98	739.54	737.24

Table 7 (continued)

Well Number Permit (TNHW-)	GW-156 128	GW-159 128	GW-160 128	GW-177 128	GW-193 113	GW-231 128
Hydrogeologic Regime ¹	CR	CR	CR	CR	EF	CR
Monitoring Program	Detection	Detection	Detection	C. Action	C. Action	Detection
Monitoring Purpose ²	POC	UPG	POC	POC	PLUME	UPG
TSD Unit ³	CRSDB	CRSDB	ECRWP	CRSP	S3 East	KHQ
General Information⁴						
Date Installed	10/18/85	10/18/85	07/18/87	10/24/85	08/04/89	10/02/85
Total Depth Drilled	157.6	157.0	235.0	145.0	18.5	35.0
East Coordinate	64,020	63,496	62,165	57,497	59,536	63,410
North Coordinate	27,626	27,764	27,803	28,483	29,344	24,725
Measuring Point Elevation	1,049.28	1,051.38	1,093.09	1,158.20	934.17	849.67
Ground Surface Elevation	1046.94	1048.79	1090.66	1155.52	931.11	846.90
Hydrostratigraphic Unit	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer
Geologic Formation	Ock	Ock	Ock	Ock	Cmn	Ock
Aquifer Zone	BDR	BDR	WT	BDR	WT	BDR
Weathered Rock-Depth	84.0	.	60.0	62.0	2.5	.
Fresh Rock-Depth	93.0	100.0	.	98.0	.	10.5
Surface Casing⁵						
Casing Depth	94.0	123.0	112.5	82.0	5.0	11.0
Outside Diameter	10.75	10.75	12.5	10.75	9.63	10.63
Casing Material	SF25	SF25	SF25	SF25	STL	PVC40
Well Casing⁶						
Borehole Depth	157.0	157.0	205.0	145.0	18.5	35.0
Borehole Diameter	8.5	8.5	11	8	8	11
Casing Depth	147.0	147.0	205.0	133.0	8.2	24.5
Outside Diameter	4.5	4.5	6.62	4.5	4.5	4.5
Casing Material	PVC40	PVC40	SF25	PVC40	SS304	PVC40
Monitored Interval⁷						
Top-Depth	145.0	145.0	205.0	130.0	5.5	22.8
Top-Elevation	901.94	903.79	885.66	1,025.52	925.61	824.10
Midpoint-Depth	151.3	151.0	220.0	137.5	12.0	28.9
Midpoint-Elevation	895.64	897.79	870.66	1,018.02	919.14	818.00
Bottom-Depth	157.6	157.0	235.0	145.0	18.5	35.0
Bottom-Elevation	889.34	891.79	855.66	1,010.52	912.66	811.90
Screen Material	PVC/sw/.01	PVC/sw/.01	.	PVC/sl/.01	SS/sw/.01	PVC/sw/.01
Screen Length	10	10	.	10	10.3	10
Open-Hole Length	.	.	30	.	.	.
Open-Hole Diameter	.	.	6	.	.	.
Dedicated Pump Intake⁸						
Depth	150.7	148.4	.	.	13.9	28.7
Elevation	896.28	900.38	.	.	917.17	818.17

Table 7 (continued)

Well Number	GW-276	GW-292	GW-293	GW-294	GW-296	GW-298
Permit (TNHW-)	116	128	128	128	128	128
Hydrogeologic Regime ¹	BC	CR	CR	CR	CR	CR
Monitoring Program	C. Action	Detection	Detection	Detection	Detection	Detection
Monitoring Purpose ²	POC	POC	POC	UPG	POC	POC
TSD Unit ³	S3	ECRWP	ECRWP	ECRWP	ECRWP	ECRWP
General Information⁴						
Date Installed	07/15/86	05/22/87	06/11/87	05/01/87	05/11/87	07/27/87
Total Depth Drilled	18.5	186.0	214.0	128.0	147.0	190.0
East Coordinate	52,557	62,146	62,321	62,483	62,023	62,445
North Coordinate	29,926	28,141	28,112	27,958	27,994	27,495
Measuring Point Elevation	1,001.57	1,073.00	1,063.90	1,083.60	1,090.99	1,049.01
Ground Surface Elevation	998.70	1070.11	1061.70	1083.67	1088.29	1046.40
Hydrostratigraphic Unit	Aquitard	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer
Geologic Formation	Cn	Ock	Ock	Ock	Ock	Ock
Aquifer Zone	WT	BDR	BDR	BDR	BDR	BDR
Weathered Rock-Depth	18.5	32.0	57.0	62.0	67.0	65.0
Fresh Rock-Depth	.	59.5	110.0	87.0	81.5	80.0
Surface Casing⁵						
Casing Depth	.	51.0	57.8	74.5	86.5	83.3
Outside Diameter	.	10.75	10.75	10.75	10.75	10.75
Casing Material	.	SF25	SF25	SF25	SF25	SF25
Well Casing⁶						
Borehole Depth	18.5	186.0	197.0	128.0	147.0	190.0
Borehole Diameter	8	10	10	10	10	10
Casing Depth	13.0	174.1	197.0	117.6	136.3	176.0
Outside Diameter	4.5	4.5	6.62	4.5	4.5	4.5
Casing Material	SS304	SS304	SF25	SS304	SS304	SS304
Monitored Interval⁷						
Top-Depth	11.3	172.1	197.0	113.0	134.4	171.1
Top-Elevation	987.40	898.01	864.70	970.67	953.89	875.30
Midpoint-Depth	14.9	179.1	205.5	120.5	140.7	180.6
Midpoint-Elevation	983.80	891.06	856.20	963.17	947.59	865.85
Bottom-Depth	18.5	186.0	214.0	128.0	147.0	190.0
Bottom-Elevation	980.20	884.11	847.70	955.67	941.29	856.40
Screen Material	SS/sw/.01	SS/sw/.01	.	SS/sw/.01	SS/sw/.01	SS/sw/.01
Screen Length	5.3	10.7	.	10.4	10.5	10
Open-Hole Length	.	.	17	.	.	.
Open-Hole Diameter	.	.	6	.	.	.
Dedicated Pump Intake⁸						
Depth	14.1	.	.	.	.	.
Elevation	984.57	.	.	.	.	.

Table 7 (continued)

Well Number	GW-301	GW-521	GW-557	GW-562	GW-605	GW-606
Permit (TNHW-)	128	128	128	128	113	113
Hydrogeologic Regime ¹	CR	CR	CR	CR	EF	EF
Monitoring Program	C. Action	C. Action	C. Action	C. Action	C. Action	C. Action
Monitoring Purpose ²	PLUME	UPG	PLUME	PLUME	PLUME	PLUME
TSD Unit ³	CRSP	CRSP	CRSP	CRSP	S3 East	S3 East
General Information⁴						
Date Installed	07/02/87	09/14/88	12/02/88	01/13/89	03/19/91	03/20/91
Total Depth Drilled	182.0	136.0	139.0	133.0	40.5	175.0
East Coordinate	61,964	52,040	59,520	61,640	62,002	61,951
North Coordinate	27,662	28,541	26,450	26,276	28,707	28,708
Measuring Point Elevation	1,086.55	1,182.88	1,081.36	934.69	919.06	919.59
Ground Surface Elevation	1083.94	1179.46	1078.63	931.86	916.97	916.98
Hydrostratigraphic Unit	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer
Geologic Formation	OCk	OCk	OCk	OCk	Cmn	Cmn
Aquifer Zone	BDR	BDR	WT	WT	BDR	BDR
Weathered Rock-Depth	94.0	.	113.8	.	.	.
Fresh Rock-Depth	136.0	54.0	134.0	52.0	9.5	10.8
Surface Casing⁵						
Casing Depth	105.0	60.5	85.0	.	9.5	64.7
Outside Diameter	10.75	10.75	10.75	.	11.75	7
Casing Material	SF25	STL	STL	.	SJ55	SJ55
Well Casing⁶						
Borehole Depth	163.5	136.0	138.0	60.0	40.5	175.0
Borehole Diameter	10	9.5	9.5	9.5	10.6	9.63
Casing Depth	151.0	124.9	115.8	38.0	29.7	161.0
Outside Diameter	4.5	4.5	4.5	4.5	4.25	4.25
Casing Material	SS304	SS304	SS304	SS304	SS304	SS304
Monitored Interval⁷						
Top-Depth	148.5	123.2	112.9	36.0	28.2	155.0
Top-Elevation	935.44	1,056.26	965.73	895.86	888.77	761.98
Midpoint-Depth	156.0	129.6	125.5	48.0	34.1	163.0
Midpoint-Elevation	927.94	1,049.86	953.18	883.86	882.92	753.98
Bottom-Depth	163.5	136.0	138.0	60.0	39.9	171.0
Bottom-Elevation	920.44	1,043.46	940.63	871.86	877.07	745.98
Screen Material	SS/sw/.01	SS/sw/.01	SS/sw/.01	SS/sw/.01	SS/sw/.01	SS/ppk/.01
Screen Length	10	10.3	20	20	10	10
Open-Hole Length	.	.	.	.	.	.
Open-Hole Diameter	.	.	.	.	.	.
Dedicated Pump Intake⁸						
Depth	157.4	129.0	123.6	48.2	33.9	166.4
Elevation	926.55	1,050.48	955.06	883.69	883.06	750.59

Table 7 (continued)

Well Number Permit (TNHW-)	GW-712 116	GW-713 116	GW-714 116	GW-731 128	GW-732 128	GW-733 113
Hydrogeologic Regime ¹	BC	BC	BC	CR	CR	EF
Monitoring Program	C. Action	C. Action	C. Action	Detection	Detection	C. Action
Monitoring Purpose ²	PLUME	PLUME	PLUME	POC	POC	PLUME
TSD Unit ³	EXP	EXP	EXP	CRSDB	CRSDB	S3 East
General Information⁴						
Date Installed	06/20/91	01/13/92	01/24/92	09/12/91	09/11/91	10/02/91
Total Depth Drilled	457.5	315.2	145.0	180.4	190.6	256.5
East Coordinate	36,507	36,434	36,435	63,863	64,268	65,067
North Coordinate	28,233	28,236	28,422	27,464	27,717	28,447
Measuring Point Elevation	877.89	881.43	875.88	1,049.38	1,064.29	959.84
Ground Surface Elevation	873.61	877.83	872.30	1045.75	1060.65	955.69
Hydrostratigraphic Unit	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer	Aquifer
Geologic Formation	Ock	Cmn	Cmn	Ock	Ock	Cmn
Aquifer Zone	BDR	BDR	BDR	BDR	BDR	BDR
Weathered Rock-Depth	12.0	26.8	27.0	95.4	85.0	42.5
Fresh Rock-Depth	66.0	63.8	35.0	129.4	96.0	47.1
Surface Casing⁵						
Casing Depth	44.8	80.2	40.5	122.0	100.7	51.8
Outside Diameter	11.75	.	11.75	11.75	11.75	11.75
Casing Material	SJ55	SJ55	SJ55	SJ55	SJ55	SJ55
Well Casing⁶						
Borehole Depth	441.5	305.0	115.1	175.4	189.5	240.1
Borehole Diameter	10.6	10.6	10.6	10.6	10.6	10.6
Casing Depth	440.2	303.7	113.8	165.2	179.3	238.8
Outside Diameter	7	7	7	4.5	4.5	7
Casing Material	SF25	SF25	SF25	SS304	SS304	SF25
Monitored Interval⁷						
Top-Depth	441.5	305.0	115.1	164.0	178.3	240.1
Top-Elevation	432.11	572.83	757.20	881.75	882.35	715.59
Midpoint-Depth	449.5	310.1	130.1	171.4	184.2	248.3
Midpoint-Elevation	424.11	567.73	742.25	874.40	876.50	707.39
Bottom-Depth	457.5	315.2	145.0	178.7	190.0	256.5
Bottom-Elevation	416.11	562.63	727.30	867.05	870.65	699.19
Screen Material	.	.	.	SS/sw/.01	SS/sw/.01	.
Screen Length	.	.	.	10	10	.
Open-Hole Length	16	10.2	29.9	.	.	16.4
Open-Hole Diameter	6.25	6.25	6.25	.	.	6.25
Dedicated Pump Intake⁸						
Depth	446.2	307.4	138.4	169.9	184.4	248.9
Elevation	427.39	570.43	733.88	875.88	876.29	706.84

Table 7 (continued)

Well Number	GW-799	GW-801	GW-831
Permit (TNHW-)	128	128	128
Hydrogeologic Regime ¹	CR	CR	CR
Monitoring Program	C. Action	C. Action	C. Action
Monitoring Purpose ²	PLUME	PLUME	PLUME
TSD Unit ³	CRSP	CRSP	CRSP
General Information⁴			
Date Installed	03/25/93	07/01/93	07/30/96
Total Depth Drilled	92.0	188.9	200.0
East Coordinate	59,961	58,780	56,593
North Coordinate	26,746	26,808	26,654
Measuring Point Elevation	981.29	1,097.16	1,091.29
Ground Surface Elevation	978.10	1093.82	1088.04
Hydrostratigraphic Unit	Aquifer	Aquifer	Aquifer
Geologic Formation	Ock	Ock	Ock
Aquifer Zone	BDR	BDR	BDR
Weathered Rock-Depth	60.8	112.5	134.8
Fresh Rock-Depth	62.8	113.4	140.8
Surface Casing⁵			
Casing Depth	65.0	115.4	138.3
Outside Diameter	10.75	10.75	10.75
Casing Material	SJ55	SJ55	STL
Well Casing⁶			
Borehole Depth	92.0	188.9	200.0
Borehole Diameter	9.5	9.87	9.87
Casing Depth	81.0	178.1	183.2
Outside Diameter	4.5	4.5	4.5
Casing Material	SS304	SS304	SS
Monitored Interval⁷			
Top-Depth	78.7	175.8	182.0
Top-Elevation	899.40	918.02	906.04
Midpoint-Depth	85.4	182.4	190.8
Midpoint-Elevation	892.75	911.47	897.24
Bottom-Depth	92.0	188.9	199.6
Bottom-Elevation	886.10	904.92	888.44
Screen Material	SS/sw/.01	SS/sw/.01	SS/sw/.01
Screen Length	9.9	9.9	10.4
Open-Hole Length			
Open-Hole Diameter			
Dedicated Pump Intake⁸			
Depth	84.8	177.7	188.8
Elevation	893.29	916.16	899.29

Table 7 (continued)

Notes:

Data compiled from: BWXT (BWXT Y-12, L.L.C.) 2003. *Updated Subsurface Data Base for Bear Creek Valley, Chestnut Ridge, and Parts of Bethel Valley on the U.S. Department of Energy Oak Ridge Reservation*, Y/TS-881/R5, Oak Ridge, TN.

1	BC = Bear Creek Hydrogeologic Regime
CR = Chestnut Ridge Hydrogeologic Regime
EF = Upper East Fork Poplar Creek Hydrogeologic Regime
2	PLUME = plume boundary
POC = point-of-compliance
UPG = upgradient/background
3	BG = Bear Creek Burial Grounds WMA
CRSDB = Chestnut Ridge Sediment Disposal Basin
CRSP = Chestnut Ridge Security Pits
ECRWP = East Chestnut Ridge Waste Pile
EXP = Exit Pathway for BG, OLF, and S3
KHQ = Kerr Hollow Quarry
OLF = Oil Landfarm WMA
S3 = S-3 Site
S3 East = Eastern S-3 Site Plume
4	Coordinates = Y-12 grid system
Elevations = feet above mean sea level
Depths = feet below ground surface
BDR = bedrock interval
WT = water table interval
Och = Chickamauga Group
Ock = Knox Group
Cm = Maryville Limestone
Cn = Nolichucky Shale
Cmn = Maynardville Limestone
6	Depth = feet below ground surface
Diameters = outside dimensions, in inches (nominal)
SS/#304 = stainless steel, schedule 304
F25/J55 = American Petroleum Institute Grade
PVC = polyvinyl chloride, schedule 40
Steel = carbon steel
7	Elevations = feet above mean sea level
Depths = feet below ground surface; pump intake is depth from measuring point (MP)
Lengths = feet
Top = depth to top of filter pack or open-hole
Bottom = depth to bottom of filter pack or open-hole
PVC/sl/.01 = polyvinyl chloride, 0.01-inch slot size
PVC/sw/.01 = polyvinyl chloride, spiral wound, 0.01-inch slot size
SS/pp/.01 = stainless steel prepacked screen, spiral wound, 0.01-inch slot size
SS/sw/.01 = stainless steel, spiral wound, 0.01-inch slot size
8	Depth = feet below the measuring point (approximate)
Elevation = feet above mean sea level

**Table 8. Field measurements and RCRA groundwater target compounds for the S-3 Site,
Oil Landfarm, and Bear Creek Burial Grounds/Walk-In Pits**

Measurement/Analyte	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	S-3	OLF	BG	PB		
Field Measurements						
Depth to Water	.	.	.	.	EDAM-SAMP-0100	NA
Water Temperature	.	.	.	.	EDAM-SAMP-1203	NA
pH	.	.	.	.	EDAM-SAMP-1204	NA
Conductivity	.	.	.	.	EDAM-SAMP-1208	NA
Dissolved Oxygen	.	.	.	.	EDAM-SAMP-1205	NA
Oxidation-Reduction Potential	.	.	.	.	EDAM-SAMP-1207	NA
Turbidity	.	.	.	.	EDAM-SAMP-1211	NA
Inorganics (milligrams per liter)						
Barium	o	o	.	.	SW846-6010B	0.005
Cadmium	o	o	.	.	SW846-6010B	0.00013*
Chromium	o	.	.	.	SW846-6010B	0.005
Mercury	o	o	.	.	SW846-7470	0.0002
Nickel	o	.	.	.	SW846-6010B	0.01
Nitrate (as N)	•	.	.	•	EPA-353.2	0.1
Uranium	•	o	o	o	ASTM-D5174-97 or SW846-6020A	0.004
Organics (micrograms per liter)						
Acetone	o	.	.	.	SW846-8260	10
Benzene	.	.	•	o	SW846-8260	2.5*
Chloroform	o	.	.	.	SW846-8260	5
1,1-Dichloroethane	.	.	•	.	SW846-8260	5
1,1-Dichloroethene	.	o	o	.	SW846-8260	3.5*
cis-1,2-Dichloroethene	o	•	•	o	SW846-8260	5
Methylene Chloride	o	.	.	o	SW846-8260	2.5*
Tetrachloroethene	•	•	•	o	SW846-8260	2.5*
1,1,1-Trichloroethane	.	.	•	o	SW846-8260	5
Trichloroethene	o	•	o	o	SW846-8260	2.5*
Vinyl Chloride	.	.	o	.	SW846-8260	1*
Radioanalytes (picoCuries per liter)						
Gross Alpha Activity	o	o	o	o	EPA-900.0	5
Gross Beta Activity	o	o	o	o	EPA-900.0	5
Americium-241	o	.	.	.	EPA-907.0	0.4
Neptunium-237	o	.	.	.	EPA-907.0	0.4
Total Radium	o	.	.	.	EPA-903.0	0.5
Strontium-90	o	.	.	.	EPA-905.0	4
Technetium-99	•	.	o	o	LSC	10
Uranium-234, -235, and -238	o	.	o	o	EPA-908.0	1

Table 8 (continued)

Notes:

1. Groundwater target list constituent specified in the RCRA post-closure permit for the Bear Creek Hydrogeologic Regime (permit number TNHW-116).

- S3 = S-3 Site point-of-compliance
- OLF = Oil Landfarm point-of-compliance
- BG = Bear Creek Burial Grounds/Walk-In Pits point-of-compliance
- PB = Plume Boundary
 - = RCRA groundwater target constituent for specified site
 - = RCRA groundwater target constituent for specified site selected for quantitative trend analysis
 - = Not a RCRA groundwater target constituent

2. Referenced field and laboratory methods and procedures are from:

- American Society for Testing and Materials 1992. *Annual Book of ASTM Standards for Water and Waste Water*.
- Commodore Advanced Sciences Team Environmental Data Acquisition and Management Technical Procedures (R4) 2005
- EPA 1983. *Methods for Chemical Analysis of Water and Wastes*.

LSC = Liquid scintillation count

3. Project Quantitation Level (PQL) for undiluted groundwater samples, as specified in:

Bechtel Jacobs Company LLC. 2006. *Sampling and Analysis Plan for the Water Resources Restoration Program for Fiscal Year 2007 Oak Ridge Reservation Oak Ridge, Tennessee*, BJC/OR-2518, Bechtel Jacobs Company LLC, Oak Ridge, TN.

- * In March 2007, an addendum to the above-referenced sampling and analysis plan (Addendum No. FY07-011) lowered the PQLs for several metals and VOCs that are RCRA groundwater target compounds. Analytical results for the groundwater samples collected during the second RCRA semiannual sampling event in CY 2007 reflect the lower PQLs.

Table 9. Field measurements and RCRA groundwater target compounds for the Eastern S-3 Site Plume

Measurement/Analyte	Target Constituents ¹		Procedure/ Analytical Method ²	PQL ³
	POC	PB		
FIELD MEASUREMENTS				
Depth to Water	.	.	EDAM-SAMP-0100	NA
Water Temperature	.	.	EDAM-SAMP-1203	NA
pH	.	.	EDAM-SAMP-1204	NA
Conductivity	.	.	EDAM-SAMP-1208	NA
Dissolved Oxygen	.	.	EDAM-SAMP-1205	NA
Oxidation-Reduction Potential	.	.	EDAM-SAMP-1207	NA
Turbidity	.	.	EDAM-SAMP-1211	NA
INORGANICS (milligrams per liter)				
Barium	○	.	SW846-6010B	0.005
Cadmium	○	.	SW846-6010B	0.00013*
Chromium	○	.	SW846-6010B	0.005
Mercury	○	.	SW846-7470	0.0002
Nickel	○	.	SW846-6010B	0.01
Nitrate (as N)	●	.	EPA-353.2	0.1
Uranium	○	.	ASTM-D5174-M/ SW846-6020A/ EPA-907.0 [C]	0.004
ORGANICS (micrograms per liter)				
Acetone	○	.	SW846-8260	5
Chloroform	●	.	SW846-8260	5
cis-1,2-Dichloroethene	○	.	SW846-8260	5
Methylene Chloride	○	.	SW846-8260	2.5*
Tetrachloroethene	○	.	SW846-8260	2.5*
Trichloroethene	○	.	SW846-8260	2.5*
RADIOANALYTES (picoCuries per liter)				
Gross Alpha Activity	○	.	EPA-900.0	5
Gross Beta Activity	○	.	EPA-900.0	5
Technetium-99	●	○	LSC	10

Notes:

1. Groundwater target list constituent specified in the RCRA post-closure permit for the Upper East Fork Poplar Creek Hydrogeologic Regime (permit number TNHW-113).

- PB = Plume Boundary (well)
 POC = Point of Compliance (well)
 ○ = RCRA groundwater target constituent for Eastern S-3 Ponds Plume
 ● = RCRA groundwater target constituent selected for quantitative trend analysis
 . = Not a RCRA groundwater target constituent

Table 9 (continued)

Notes (continued):

2. Referenced field and laboratory methods and procedures are from:

- American Society for Testing and Materials 1992. *Annual Book of ASTM Standards for Water and Waste Water*.
- Commodore Advanced Sciences Team Environmental Data Acquisition and Management Technical Procedures (R4) 2005
- EPA 1983. *Methods for Chemical Analysis of Water and Wastes*.

[C] = The total uranium concentration (mass) in samples from well GW-108 is calculated from isotopic results because the groundwater has very high calcium concentrations that cause interferences in the ASTM method.

LCS = Liquid scintillation count

3. Project Quantitation Level (PQL) for undiluted groundwater samples, as specified in:

Bechtel Jacobs Company LLC. 2006. *Sampling and Analysis Plan for the Water Resources Restoration Program for Fiscal Year 2007 Oak Ridge Reservation Oak Ridge, Tennessee*, BJC/OR-2518, Bechtel Jacobs Company LLC, Oak Ridge, TN.

- * In March 2007, an addendum to the above-referenced sampling and analysis plan (Addendum No. FY07-011) lowered the PQLs for several metals and VOCs that are RCRA groundwater target compounds. Analytical results for the groundwater samples collected during the second RCRA semiannual sampling event in CY 2007 reflect the lower PQLs.

Table 10. Field measurements and RCRA groundwater target compounds for the Chestnut Ridge Security Pits, Chestnut Ridge Sediment Disposal Basin, East Chestnut Ridge Waste Pile, and Kerr Hollow Quarry

Field Measurements	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	CRSP	CRSDB	ECRWP	KHQ		
Depth to Water	.	.	.	.	EDAM-SAMP-0100	NA
Water Temperature	.	.	.	.	EDAM-SAMP-1203	NA
pH	.	.	.	.	EDAM-SAMP-1204	NA
Conductivity	.	.	.	.	EDAM-SAMP-1208	NA
Dissolved Oxygen	.	.	.	.	EDAM-SAMP-1205	NA
Oxidation-Reduction Potential	.	.	.	.	EDAM-SAMP-1207	NA
Turbidity	.	.	.	.	EDAM-SAMP-1211	NA
Inorganics (milligrams per liter)	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	CRSP	CRSDB	ECRWP	KHQ		
Antimony	.	.	o	.	SW846-6010B	0.003*
Arsenic	.	.	o	.	SW846-6010B	0.005
Barium	.	.	o	.	SW846-6010B	0.005
Boron	.	.	o	.	SW846-6010B	0.01
Cadmium	o	o	o	o	SW846-6010B	0.00013*
Chromium	o	o	o	o	SW846-6010B	0.005
Chloride	.	.	o	.	EPA-300.0	0.1
Cobalt	.	.	o	.	SW846-6010B	0.005
Copper	.	.	o	.	SW846-6010B	0.005
Iron	.	.	o	.	SW846-6010B	0.01
Lead	.	o	o	o	SW846-6010B	0.002*
Lithium	.	.	o	.	SW846-6010B	0.01
Manganese	.	.	o	.	SW846-6010B	0.005
Mercury	o	o	o	o	SW846-7470	0.0002
Nickel	o	o	o	o	SW846-6010B	0.01
Nitrate (as N)	.	.	o	.	EPA-353.2	0.1
Selenium	.	.	o	.	SW846-6010B	0.0025*
Silver	.	o	.	.	EPA-353.2	0.10025*
Sulfate	.	.	o	.	SW846-6010B	
Thallium	.	.	o	.	SW846-6010B	0.001*
Uranium	o	o	o	o	ASTM-D5174-97 or SW846-6020A	0.004
Zinc	.	.	o	.		
Organics (micrograms per liter)	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	CRSP	CRSDB	ECRWP	KHQ		
Benzene	o	.	o	.	SW846-8260	2.5*
Bromoform	o	.	.	.	SW846-8260	5
Carbon Tetrachloride	o	.	o	o	SW846-8260	2.5*
Chloroform	o	.	o	o	SW846-8260	5
Chloroethane**	.	.	o	.	SW846-8260	10

Table 10 (continued)

Organics (micrograms per liter)	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	CRSP	CRSDB	ECRWP	KHQ		
1,1-Dichloroethane	•	.	○	.	SW846-8260	5
1,2-Dichloroethane	○	.	○	.	SW846-8260	2.5*
1,1-Dichloroethene	○	.	○	.	SW846-8260	3.5*
cis-1,2-Dichloroethene	○	.	○	.	SW846-8260	5
trans-1,2-Dichloroethene	○	.	○	.	SW846-8260	5
1,1,1-Trichloroethane	•	.	○	.	SW846-8260	5
Methylene Chloride	.	.	○	.	SW846-8260	2.5*
Tetrachloroethene	○	.	○	○	SW846-8260	2.5*
Trichloroethene	○	.	○	.	SW846-8260	2.5*
Vinyl chloride	○	.	○	.	SW846-8260	1*
Radioanalytes (picoCuries per liter)	Target Constituents ¹				Procedure/ Analytical Method ²	PQL ³
	CRSP	CRSDB	ECRWP	KHQ		
Gross Alpha Activity	○	.	○	○	EPA-900.0	5
Gross Beta Activity	○	.	.	○	EPA-900.0	5

Notes:

1. Groundwater target compound specified in the RCRA post-closure permit for the Chestnut Ridge Hydrogeologic Regime (permit number TNHW-128).

CRSP = Chestnut Ridge Security Pits

CRSDB = Chestnut Ridge Sediment Disposal Basin

ECRWP = East Chestnut Ridge Waste Pile

KHQ = Kerr Hollow Quarry

○ = RCRA groundwater target constituent for specified site

• = RCRA groundwater target constituent selected for quantitative trend analysis

.

** = Because of a typographical error, the PCP incorrectly identifies chloromethane instead of chloroethane as a RCRA groundwater target compound (see Sect. 6).

2. Referenced field and laboratory methods and procedures are from:

- American Society for Testing and Materials 1992. *Annual Book of ASTM Standards for Water and Waste Water*.
- Commodore Advanced Sciences Team Environmental Data Acquisition and Management Technical Procedures (R4) 2005
- EPA 1983. *Methods for Chemical Analysis of Water and Wastes*.

3. Project Quantitation Level (PQL) for undiluted groundwater samples, as specified in:

Bechtel Jacobs Company LLC. 2006. *Sampling and Analysis Plan for the Water Resources Restoration Program for Fiscal Year 2007 Oak Ridge Reservation Oak Ridge, Tennessee*, BJC/OR-2518, Bechtel Jacobs Company LLC, Oak Ridge, TN.

- In March 2007, an addendum to the above-referenced sampling and analysis plan (Addendum No. FY07-011) lowered the PQLs for several metals and VOCs that are RCRA groundwater target compounds. Analytical results for the groundwater samples collected during the second RCRA semiannual sampling event in CY 2007 reflect the lower PQLs.

Table 11. Laboratory blanks and trip blanks associated with CY 2007 RCRA post-closure groundwater monitoring at the Y-12 National Security Complex

Sampling Point ¹	TSD Unit/ Sampling Purpose ²		Date Sampled	Sample Number	
				Trip Blank	Laboratory Blank
GW-008	OLF	POC	01/02/07	Y020816-TB	07LVG008-MB1
GW-008	OLF	POC	07/02/07	Y021068-TB	07LVG087-MB1
GW-046	BG	POC	01/03/07	Y020818-TB	07LVG006-MB1
GW-046	Dil BG	POC	01/03/07	Y020818-TB	07LVG010-MB1
GW-046	BG	POC	07/02/07	Y021065-TB	07LVG087-MB1
GW-046	Dil BG	POC	07/02/07	Y021065-TB	07LVG087-MB1
GW-108	S3 East	POC	01/04/07	Y020890-TB	07LVG010-MB1
GW-108	S3 East	POC	07/10/07	Y021077-TB	07LVG093-MB1
GW-143	KHQ	POC	01/08/07	Y020894-TB	07LVX009-MB1
GW-144	KHQ	POC	01/04/07	Y020886-TB	07LVX008-MB1
GW-145	KHQ	POC	01/08/07	Y020896-TB	07LVX009-MB1
GW-161	ECRWP	POC	01/25/07	Y020906-TB	07LVX030-MB1
GW-161	ECRWP	POC	07/10/07	Y021082-TB	07LVG094-MB1
GW-177	CRSP	POC	01/09/07	Y020902-TB	07LVX009-MB1
GW-177	CRSP	POC	07/11/07	Y021081-TB	07LVE076-MB1
GW-231	KHQ	UPG	01/04/07	Y020886-TB	07LVX008-MB1
GW-231	Dup KHQ	UPG	01/04/07	Y020886-TB	07LVX008-MB1
GW-276	S3	POC	01/03/07	Y020819-TB	07LVG010-MB1
GW-276	S3	POC	07/09/07	Y021071-TB	07LVG097-MB1
GW-292	ECRWP	POC	01/23/07	Y020907-TB	07LVG024-MB1
GW-292	ECRWP	POC	07/10/07	Y021083-TB	07LVG094-MB1
GW-293	ECRWP	POC	01/24/07	Y020908-TB	07LVX030-MB1
GW-293	Dup ECRWP	POC	01/24/07	Y020908-TB	07LVX030-MB1
GW-293	ECRWP	POC	07/10/07	Y021084-TB	07LVG097-MB1
GW-293	Dup ECRWP	POC	07/10/07	Y021084-TB	07LVG097-MB1
GW-294	ECRWP	UPG	01/22/07	Y020910-TB	07LVX024-MB1
GW-294	ECRWP	UPG	07/11/07	Y021081-TB	07LVE076-MB1
GW-296	ECRWP	POC	01/22/07	Y020910-TB	07LVX024-MB1
GW-296	ECRWP	POC	07/10/07	Y021083-TB	07LVG098-MB1
GW-298	ECRWP	POC	01/29/07	Y020912-TB	07LVX032-MB1
GW-298	ECRWP	POC	07/09/07	Y021088-TB	07LVG094-MB1
GW-301	CRSP	PB	01/09/07	Y020903-TB	07LVX010-MB1
GW-301	Dup CRSP	PB	01/09/07	Y020903-TB	07LVX010-MB1
GW-301	CRSP	PB	07/12/07	Y021079-TB	07LVE079-MB1
GW-301	Dup CRSP	PB	07/12/07	Y021079-TB	07LVE079-MB1
GW-521	CRSP	UPG	01/10/07	LF02231	D7A170000443B
GW-521	CRSP	UPG	07/12/07	LF02391-TB	D7G250000664B
GW-557	CRSP	PB	01/11/07	LF02361	D7A230000381B
GW-557	CRSP	PB	07/16/07	LF02395-TB	D7G260000582B
GW-562	CRSP	PB	01/16/07	LF02325	D7A290000094B
GW-562	CRSP	PB	07/17/07	LF02403-TB	D7G310000182B

Table 11 (continued)

Sampling Point ¹	TSD Unit/ Sampling Purpose ²		Date Sampled	Sample Number	
				Trip Blank	Laboratory Blank
GW-712	EXP	PB	01/02/07	Y020813-TB	07LVG008-MB1
GW-712	EXP	PB	07/02/07	Y021065-TB	07LVG087-MB1
GW-713	EXP	PB	01/02/07	Y020813-TB	07LVG006-MB1
GW-713 Dup	EXP	PB	01/02/07	Y020813-TB	07LVG006-MB1
GW-713	EXP	PB	07/03/07	Y021066-TB	07LVG093-MB1
GW-713 Dup	EXP	PB	07/03/07	Y021066-TB	07LVG093-MB1
GW-714	EXP	PB	01/02/07	Y020816-TB	07LVG006-MB1
GW-714	EXP	PB	07/02/07	Y021068-TB	07LVG087-MB1
GW-799	CRSP	PB	01/16/07	LF02284	D7A290000094B
GW-799	CRSP	PB	07/17/07	LF02401-TB	D7G310000182B
GW-801	CRSP	PB	01/11/07	LF02277	D7A230000381B
GW-801	CRSP	PB	07/16/07	LF02390-TB	D7G260000582B
GW-831	CRSP	PB	01/09/07	Y020902-TB	07LVX009-MB1
GW-831	CRSP	PB	07/11/07	Y021078-TB	07LVE076-MB1
SCR4.3SP	CRSP	PB	01/16/07	LF02284	D7A290000094B
SCR4.3SP	CRSP	PB	07/17/07	LF02401-TB	D7G310000182B
SS-6	EXP	PB	01/03/07	Y020820-TB	07LVG008-MB1
SS-6	EXP	PB	07/02/07	Y021089-TB	07LVG087-MB1

Notes:

- Dil = Sample diluted for analysis

Dup = Duplicate sample
- BCBG/WIP = Bear Creek Burial Grounds/Walk-In Pits

CRSDB = Chestnut Ridge Sediment Disposal Basin

CRSP = Chestnut Ridge Security Pits

East S3 = Eastern S-3 Ponds Plume

ECRWP = East Chestnut Ridge Waste Pile

KHQ = Kerr Hollow Quarry

OLF = Oil Landfarm

PB = plume boundary

POC = point of compliance

S3 = S-3 Site

Table 12. Volatile organic compounds detected in laboratory blanks and trip blanks associated with CY 2007 RCRA post-closure groundwater monitoring at the Y-12 National Security Complex

QA/QC Sample Type and Number		Compound	Concentration (µg/L) ¹
Laboratory Blanks	07LVE076-MB1	2-Hexanone	0.1 J
	07LVG006-MB1	2-Butanone	3 J
	07LVG006-MB1	Acetone	2 J
	07LVG006-MB1	Methylene chloride	3 J
	07LVG008-MB1	2-Butanone	3 J
	07LVG008-MB1	Acetone	2 J
	07LVG008-MB1	Methylene chloride	3 J
	07LVG010-MB1	2-Butanone	3 J
	07LVG010-MB1	Acetone	2 J
	07LVG010-MB1	Methylene chloride	5
	07LVG024-MB1	Acetone	3 J
	07LVG024-MB1	Methylene chloride	2 J
	07LVG087-MB1	Methylene chloride	1 J
	07LVG093-MB1	Methylene chloride	1 J
	07LVG094-MB1	Methylene chloride	0.7 J
	07LVG097-MB1	Methylene chloride	1 J
	07LVG097-MB1	Total Xylene	1 J
	07LVG098-MB1	Methylene chloride	0.9 J
	07LVX008-MB1	Methylene chloride	4 J
	07LVX009-MB1	Methylene chloride	4 J
	07LVX010-MB1	Methylene chloride	5 J
	07LVX024-MB1	Acetone	2 J
	07LVX024-MB1	Methylene chloride	1 J
	07LVX030-MB1	Acetone	3 J
	07LVX030-MB1	Methylene chloride	1 J
	07LVX032-MB1	Methylene chloride	2 J
	D7A230000381B	Acetone	2.2 J
	D7A290000094B	Acetone	1.9 J
	D7G260000582B	Acetone	2 J

Table 12 (continued)

QA/QC Sample Type and Number	Compound	Concentration (µg/L) ¹
Trip Blanks	LF02231	1,4-Dichlorobenzene
	LF02231	Acetone
	LF02231	Ethylbenzene
	LF02231	Toluene
	LF02277	1,4-Dichlorobenzene
	LF02277	Acetone
	LF02277	Ethylbenzene
	LF02277	Toluene
	LF02284	1,4-Dichlorobenzene
	LF02284	2-Butanone
	LF02284	Acetone
	LF02284	Toluene
	LF02325	1,4-Dichlorobenzene
	LF02325	2-Butanone
	LF02325	Acetone
	LF02325	Toluene
	LF02361	1,4-Dichlorobenzene
	LF02361	2-Butanone
	LF02361	Acetone
	LF02361	Ethylbenzene
	LF02361	Toluene
	LF02390-TB	1,4-Dichlorobenzene
	LF02390-TB	Bromoform
	LF02390-TB	Chloroform
	LF02391-TB	1,4-Dichlorobenzene
	LF02391-TB	Bromoform
	LF02391-TB	Dibromochloromethane
	LF02395-TB	1,4-Dichlorobenzene
	LF02395-TB	Toluene
	LF02401-TB	Chloromethane
	LF02401-TB	Styrene
	LF02401-TB	Toluene
	LF02403-TB	Toluene
	Y020813-TB	2-Butanone
	Y020813-TB	Acetone
	Y020813-TB	Methylene chloride
	Y020816-TB	2-Butanone
	Y020816-TB	Acetone
	Y020816-TB	Methylene chloride
	Y020818-TB	2-Butanone
	Y020818-TB	Acetone
	Y020818-TB	Methylene chloride

Table 12 (continued)

QA/QC Sample Type and Number	Compound	Concentration ($\mu\text{g/L}$) ¹
Trip Blanks	Y020819-TB	2-Butanone
	Y020819-TB	4 J
	Y020819-TB	Acetone
	Y020819-TB	3 J
	Y020820-TB	Methylene chloride
	Y020820-TB	3 J
	Y020820-TB	2-Butanone
	Y020820-TB	3 J
	Y020820-TB	Acetone
	Y020820-TB	2 J
	Y020820-TB	Methylene chloride
	Y020820-TB	4 J
	Y020886-TB	Methylene chloride
	Y020886-TB	1 J
	Y020890-TB	Methylene chloride
	Y020890-TB	3 J
	Y020890-TB	2-Butanone
	Y020890-TB	4 J
	Y020890-TB	Acetone
	Y020890-TB	2 J
	Y020903-TB	Methylene chloride
	Y020903-TB	1 J
	Y020906-TB	Methylene chloride
	Y020906-TB	2 J
	Y020907-TB	1,1,2,2-Tetrachloroethane
	Y020907-TB	1 J
	Y020907-TB	2-Butanone
	Y020907-TB	4 J
	Y020907-TB	Acetone
	Y020907-TB	12
	Y020907-TB	Methylene chloride
	Y020907-TB	3 J
	Y020908-TB	Acetone
	Y020908-TB	5 J
	Y020908-TB	Methylene chloride
	Y020908-TB	1 J
	Y020910-TB	Acetone
	Y020910-TB	12
	Y020910-TB	Methylene chloride
	Y020910-TB	4 J
	Y020912-TB	Methylene chloride
	Y020912-TB	2 J
	Y021065-TB	Methylene chloride
	Y021065-TB	1 J
	Y021066-TB	Acetone
	Y021066-TB	7 J
	Y021066-TB	Methylene chloride
	Y021066-TB	1 J
	Y021068-TB	Acetone
	Y021068-TB	6 J
	Y021068-TB	Methylene chloride
	Y021068-TB	1 J
	Y021071-TB	Acetone
	Y021071-TB	3 J
	Y021071-TB	Methylene chloride
	Y021071-TB	3
	Y021077-TB	Acetone
	Y021077-TB	2 J
	Y021077-TB	Methylene chloride
	Y021077-TB	1 J
	Y021082-TB	Acetone
	Y021082-TB	2 J
	Y021082-TB	Methylene chloride
	Y021082-TB	3
	Y021083-TB	Acetone
	Y021083-TB	2 J
	Y021083-TB	Methylene chloride
	Y021083-TB	1 J
	Y021084-TB	Methylene chloride
	Y021084-TB	1 J
	Y021089-TB	Acetone
	Y021089-TB	6 J

Notes:

1. All results in micrograms per liter ($\mu\text{g/L}$).
J = Estimated concentration.

**Table 13. Depth-to-water measurements and groundwater elevations for selected wells
in the Bear Creek Hydrogeologic Regime, April 2007**

Well Number ¹	Location ²	Hydrogeologic Unit		Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
		Aquifer	Aquitard				
GW-001	OLF		●	981.00	04/12/07	14.95	966.05
GW-008*	OLF		●	965.39	04/12/07	14.30	951.09
GW-010	OLF		●	952.70	04/12/07	3.26	949.44
GW-012	OLF		●	955.57	04/12/07	6.50	949.07
GW-013	OLF		●	965.14	04/12/07	5.93	959.21
GW-014	BG		●	934.50	04/10/07	6.51	927.99
GW-016	BG		●	928.81	04/10/07	10.24	918.57
GW-041	BG		●	1008.10	04/10/07	15.58	992.52
GW-046 *	BG		●	921.17	04/10/07	3.96	917.21
GW-047	BG		●	929.00	04/10/07	7.80	921.20
GW-052	BG	●		905.70	04/10/07	14.16	891.54
GW-053	BG	●		903.42	04/10/07	8.67	894.75
GW-065	OLF	●		982.50	04/16/07	22.78	959.72
GW-080	BG		●	981.00	04/10/07	21.86	959.14
GW-084	OLF		●	997.18	04/16/07	9.90	987.28
GW-086	OLF		●	982.80	04/16/07	11.66	971.14
GW-090	BG		●	961.88	04/10/07	5.28	956.60
GW-091	BG		●	952.62	04/10/07	7.75	944.87
GW-097	OLF		●	945.41	04/12/07	9.42	935.99
GW-100	S3	●		987.40	04/09/07	5.95	981.45
GW-101	S3		●	1007.40	04/09/07	9.31	998.09
GW-115	S3		●	1055.01	04/10/07	11.57	1043.44
GW-127	S3		●	1005.90	04/09/07	13.84	992.06
GW-236	S3	●		983.21	04/16/07	8.31	974.90
GW-242	BG		●	978.69	04/10/07	5.91	972.78
GW-245	S3		●	1009.08	04/09/07	13.40	995.68
GW-249	BG		●	991.15	04/10/07	35.89	955.26
GW-257	BG		●	961.68	04/10/07	28.81	932.87
GW-276*	S3		●	1001.57	04/10/07	6.84	994.73
GW-287	BG		●	927.04	04/10/07	9.29	917.75
GW-289	BG		●	948.73	04/10/07	16.71	932.02
GW-291	BG		●	948.66	04/10/07	11.53	937.13
GW-307	RS	●		993.14	04/09/07	30.45	962.69
GW-309	RS	●		988.17	04/09/07	20.67	967.50
GW-310	RS	●		995.52	04/09/07	21.46	974.06
GW-316	SPI	●		1047.17	04/10/07	57.98	989.19
GW-323	SPI	●		1130.11	04/16/07	85.87	1044.24

Table 13 (continued)

Well Number ¹	Location ²	Hydrogeologic Unit		Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
		Aquifer	Aquitard				
GW-325	S3		●	1003.00	04/16/07	7.37	995.63
GW-345	S3		●	999.63	04/16/07	17.00	982.63
GW-347	S3	●		1001.05	04/09/07	17.00	984.05
GW-370	BG		●	960.81	04/10/07	15.04	945.77
GW-372	BG		●	983.16	04/10/07	18.59	964.57
GW-531	LD		●	1004.61	04/16/07	10.63	993.98
GW-537	OLF		●	976.65	04/16/07	5.38	971.27
GW-613	S3		●	1013.58	04/16/07	8.54	1005.04
GW-621	EXP-B	●		925.45	04/16/07	6.60	918.85
GW-622	BG		●	924.16	04/10/07	10.14	914.02
GW-624	BG		●	922.15	04/10/07	10.68	911.47
GW-630	LD		●	986.65	04/16/07	8.73	977.92
GW-638	OLF		●	941.77	04/12/07	5.72	936.05
GW-641	BG		●	946.66	04/12/07	17.85	928.81
GW-642	BG		●	1014.95	04/10/07	18.62	996.33
GW-645	OLF	●		1006.40	04/16/07	64.20	942.20
GW-648	RS	●		1029.20	04/16/07	61.17	968.03
GW-652	BG	●		900.83	04/10/07	9.94	890.89
GW-653	BG		●	931.84	04/10/07	22.78	909.06
GW-654	BG		●	940.79	04/10/07	6.92	933.87
GW-795	AGLLSF		●	926.18	04/12/07	3.10	923.08
GW-835	S3		●	1000.91	04/09/07	14.60	986.31
GW-916	EMWMF		●	1002.85	04/17/07	4.24	998.61
GW-917	EMWMF		●	997.10	04/12/07	22.91	974.19
GW-918	EMWMF		●	1067.96	04/12/07	5.37	1062.59
GW-923	EMWMF		●	1016.73	04/12/07	31.69	985.04
GW-924	EMWMF		●	968.90	04/17/07	6.37	962.53

Notes:

- 1 * = RCRA post-closure monitoring well sampled in calendar year 2007.
- 2 AGLLSF = Above Grade Low-Level Storage Facility
 BG = Bear Creek Burial Grounds Waste Management Area
 EMWMF = Environmental Management Waste Management Facility
 EXP-B = Exit Pathway (Maynardville Limestone) Picket B
 LD = Lysimeter Demonstration Site
 OLF = Oil Landfarm Waste Management Area
 RS = Rust Spoil Area
 SPI = Spoil Area I
 S3 = S-3 Site

3 The measuring point is the surveyed elevation of a mark on either the top of the innermost well casing or the top of dedicated sampling equipment, in feet above mean sea level.

4 The depth to water is in feet below the measuring point.

5 The groundwater elevation (measuring point depth to water) is in feet above mean sea level.

Table 14. Depth-to-water measurements and groundwater elevations for selected wells in the Upper East Fork Poplar Creek Hydrogeologic Regime, April 2007

Well Number ¹	Location ²	Hydrogeologic Unit		Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
		Aquifer	Aquitard				
55-1A	Y12		●	986.91	04/09/07	11.02	975.89
55-3A	Y12		●	972.46	04/09/07	11.75	960.71
55-6A	Y12		●	989.29	04/09/07	10.13	979.16
56-1A	Y12		●	969.25	04/09/07	7.57	961.68
56-2A	Y12		●	963.53	04/09/07	8.78	954.75
56-8A	Y12	●		962.46	04/09/07	20.19	942.27
60-1A	Y12	●		929.66	04/12/07	11.51	918.15
GW-105	S3		●	1018.20	04/10/07	8.28	1009.92
GW-108*	S3		●	999.00	04/10/07	7.03	991.97
GW-115	S3		●	1055.01	04/10/07	11.57	1043.44
GW-148	NHP	●		907.76	04/11/07	8.40	899.36
GW-152	NHP	●		921.18	04/11/07	20.07	901.11
GW-154	NHP	●		911.70	04/11/07	9.68	902.02
GW-167	EXP	●		931.95	04/11/07	31.80	900.15
GW-169	EXP-UV	●		932.12	04/11/07	31.25	900.87
GW-192	B4		●	1008.83	04/09/07	5.91	1002.92
GW-193 *	T2331	●		934.17	04/09/07	9.02	925.15
GW-195	B4		●	1002.90	04/09/07	6.57	996.33
GW-199	GRIDH1		●	961.08	04/12/07	17.12	943.96
GW-202	RDS		●	968.02	04/12/07	9.86	958.16
GW-204	T0134		●	958.74	04/09/07	8.69	950.05
GW-219	UOV	●		935.83	04/10/07	10.25	925.58
GW-253	S2	●		1004.24	04/10/07	10.20	994.04
GW-255	S2	●		1027.13	04/10/07	28.18	998.95
GW-261	SY		●	1049.99	04/10/07	18.17	1031.82
GW-263	SY		●	1057.73	04/10/07	29.97	1027.76
GW-334	WC		●	983.73	04/09/07	11.40	972.33
GW-335	WC		●	981.88	04/09/07	9.54	972.34
GW-349	S2	●		993.50	04/09/07	4.66	988.84
GW-380	NHP	●		913.55	04/12/07	10.22	903.33
GW-383	NHP		●	908.77	04/11/07	9.30	899.47
GW-605 *	EXP-I	●		919.06	04/12/07	11.04	908.02
GW-606 *	EXP-I	●		919.59	04/12/07	13.45	906.14
GW-617	EXP-E	●		985.28	04/09/07	13.67	971.61
GW-619	PTF	●		1015.42	04/10/07	25.20	990.22
GW-686	CPT	●		963.76	04/09/07	12.85	950.91
GW-691	CPT	●		968.59	04/09/07	12.35	956.24

Table 14 (continued)

Well Number ¹	Location ²	Hydrogeologic Unit		Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
		Aquifer	Aquitard				
GW-696	B8110	●		969.78	04/11/07	31.57	938.21
GW-733 *	EXP-J	●		959.84	04/11/07	59.36	900.48
GW-746	GRIDK1		●	906.88	04/11/07	8.03	898.85
GW-752	GRIDJ3		●	912.78	04/10/07	4.13	908.65
GW-754	GRIDJ2		●	928.78	04/10/07	10.89	917.89
GW-756	GRIDJ1		●	928.11	04/10/07	6.00	922.11
GW-759	GRIDG1		●	994.01	04/10/07	18.87	975.14
GW-761	GRIDG2		●	968.23	04/10/07	10.75	957.48
GW-763	GRIDJ3		●	915.03	04/12/07	8.96	906.07
GW-765	GRIDE1		●	1008.54	04/10/07	19.42	989.12
GW-767	GRIDJ2		●	948.54	04/12/07	10.46	938.08
GW-770	GRIDG3		●	944.72	04/12/07	10.60	934.12
GW-774	GRIDH2		●	963.16	04/12/07	9.84	953.32
GW-776	GRIDH3		●	931.25	04/12/07	13.08	918.17
GW-783	GRIDE3		●	948.49	04/12/07	10.28	938.21
GW-792	GRIDD2		●	992.74	04/09/07	25.39	967.35
GW-816	EXP-SR		●	898.42	04/10/07	12.14	886.28
GW-960	GRID F2		●	963.26	04/12/07	12.72	950.54

Notes:

- 1 * = RCRA monitoring well sampled in calendar year 2007.
 Note that wells GW-605, GW-606, and GW-733 are bedrock interval monitoring wells.
- 2 B4 = Beta-4 Security Pits
 B8110 = Building 81-10
 B9201-2 = Building 9201-2
 CPT = Coal Pile Trench
 EXP = Exit Pathway (Maynardville Limestone) monitoring well
 -E, -I, or -J: Maynardville Limestone Picket
 -UV: Offsite in Union Valley
 -SR: Along Scarboro Road in the gap through Pine Ridge
 FTF = Fire Training Facility
 GRID = Comprehensive Groundwater Monitoring Plan Grid Location
 NHP = New Hope Pond
 RDS = Ravine Disposal Site
 S2 = S-2 Site
 S3 = S-3 Site
 SY = Y-12 Plant Salvage Yard
 T0134 = Tank 0134-U
 T2331 = Tank 2331-U
 UOV = Uranium Oxide Vault
 WC = Waste Coolant Processing Area
 Y12 = Y-12 Complex

Table 14 (continued)

Notes: (continued)

- 3 The measuring point is the surveyed elevation of a mark on either the top of the innermost well casing or the top of dedicated sampling equipment, in feet above mean sea level.
- 4 The depth to water is in feet below the measuring point.
- 5 The groundwater elevation (measuring point depth to water) is in feet above mean sea level.

Table 15. Depth-to-water measurements and groundwater elevations for selected wells in the Chestnut Ridge Hydrogeologic Regime, April 2007

Well Number ¹	Location ²	Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
1082	ORSF	837.28	04/09/07	25.24	812.04
1084	ORSF	965.40	04/09/07	63.07	902.33
1090	UNCS	1104.48	04/10/07	55.11	1049.37
GW-141	LIV	1186.23	04/11/07	96.24	1089.99
GW-142	KHQ	971.15	04/16/07	136.72	834.43
GW-144 *	KHQ	913.54	04/16/07	80.29	833.25
GW-145 *	KHQ	840.24	04/16/07	5.90	834.34
GW-156 *	CRSDB	1049.28	04/11/07	143.05	906.23
GW-159 *	CRSDB	1051.38	04/11/07	117.52	933.86
GW-160	CRBAWP	1093.09	04/11/07	144.22	948.87
GW-173	CRSP	1115.00	04/10/07	149.89	965.11
GW-174	CRSP	1116.66	04/10/07	116.76	999.90
GW-175	CRSP	1084.19	04/10/07	122.11	962.08
GW-176	CRSP	1125.30	04/10/07	116.23	1009.07
GW-177 *	CRSP	1158.20	04/11/07	117.83	1040.37
GW-178	CRSP	1143.49	04/10/07	91.33	1052.16
GW-179	CRSP	1128.00	04/10/07	116.03	1011.97
GW-180	CRSP	1104.14	04/11/07	116.68	987.46
GW-184	RQ	927.63	04/09/07	110.21	817.42
GW-186	RQ	831.32	04/09/07	14.73	816.59
GW-188	RQ	837.09	04/09/07	20.28	816.81
GW-203	UNCS	1105.45	04/10/07	83.33	1022.12
GW-205	UNCS	1104.14	04/10/07	80.00	1024.14
GW-217	LIV	1177.03	04/10/07	112.18	1064.85
GW-221	UNCS	1106.16	04/10/07	84.68	1021.48
GW-231 *	KHQ	849.67	04/16/07	14.53	835.14
GW-241	CRSDB	982.84	04/16/07	44.92	937.92
GW-292	ECRWP	1073.00	04/11/07	112.77	960.23
GW-298	CRBAWP	1049.01	04/11/07	109.73	939.28
GW-299	CRBAWP	1053.86	04/11/07	101.70	952.16
GW-300	CRBAWP	1073.12	04/11/07	115.84	957.28
GW-301 *	CRBAWP	1086.55	04/11/07	135.22	951.33
GW-302	UNCS	1141.84	04/11/07	102.16	1039.68
GW-303	CRSDB	1007.16	04/11/07	87.65	919.51
GW-304	CRSDB	1045.49	04/11/07	117.19	928.30
GW-305	LIV	1183.72	04/16/07	121.82	1061.90
GW-322	CRSP	1134.98	04/10/07	159.20	975.78
GW-339	UNCS	1124.83	04/10/07	77.62	1047.21

Table 15 (continued)

Well Number ¹	Location ²	Measuring Point ³	Date Measured	Depth to Water ⁴	Groundwater Elevation ⁵
GW-511	CRSP	1093.21	04/10/07	111.77	981.44
GW-512	FCAP	1001.54	04/10/07	26.05	975.49
GW-521 *	LIV	1182.88	04/16/07	82.33	1100.55
GW-522	LIV	1175.48	04/16/07	103.34	1072.14
GW-539	LII	1093.20	04/16/07	110.21	982.99
GW-541	CDLVI	1058.40	04/16/07	64.17	994.23
GW-542	CDLVI	1051.81	04/16/07	69.90	981.91
GW-543	CDLVI	1024.01	04/16/07	60.64	963.37
GW-544	CDLVI	1045.19	04/16/07	54.66	990.53
GW-546	CDLVI	1072.21	04/16/07	86.09	986.12
GW-557 *	LV	1081.36	04/12/07	125.21	956.15
GW-558	SSCR	981.42	04/12/07	49.10	932.32
GW-559	SSCR	1102.79	04/12/07	139.50	963.29
GW-560	CDLVII	949.05	04/12/07	51.80	897.25
GW-562 *	CDLVII	934.69	04/16/07	12.71	921.98
GW-564	CDLVII	938.07	04/12/07	11.38	926.69
GW-608	CRSP	1075.38	04/11/07	138.47	936.91
GW-609	CRSP	1112.31	04/11/07	167.68	944.63
GW-610	CRSP	1059.44	04/10/07	97.72	961.72
GW-611	CRSP	1048.38	04/10/07	103.65	944.73
GW-612	CRSP	1131.03	04/10/07	123.42	1007.61
GW-674	FCAP	883.79	04/09/07	8.18	875.61
GW-676	FCAP	846.50	04/09/07	4.07	842.43
GW-677	FCAP	1030.40	04/10/07	27.76	1002.64
GW-678	FCAP	1000.70	04/10/07	21.39	979.31
GW-679	FCAP	1026.90	04/10/07	52.10	974.80
GW-680	FCAP	1001.50	04/12/07	28.96	972.54
GW-709	LII	906.81	04/16/07	20.35	886.46
GW-731 *	CRSDB	1049.38	04/11/07	125.21	924.17
GW-732 *	CRSDB	1064.29	04/11/07	158.00	906.29
GW-743	CRSP	1100.36	04/11/07	136.05	964.31
GW-757	LII	961.64	04/16/07	79.47	882.17
GW-796	LV	1052.62	04/10/07	84.38	968.24
GW-797	LV	1060.00	04/10/07	77.20	982.80
GW-798	CDLVII	1006.00	04/12/07	85.14	920.86
GW-799 *	LV	981.29	04/12/07	23.84	957.45
GW-801 *	LV	1097.16	04/12/07	114.95	982.21
GW-827	CDLVI	1051.60	04/16/07	42.58	1009.02
GW-831 *	FCAP	1091.29	04/10/07	130.60	960.69

Table 15 (continued)

Notes:

- 1 * = RCRA monitoring well sampled in calendar year 2007.

- 2 CDLVI = Construction/Demolition Landfill VI
 CDLVII = Construction/Demolition Landfill VII
 CRBAWP = Chestnut Ridge Borrow Area Waste Pile
 CRSDB = Chestnut Ridge Sediment Disposal Basin
 CRSP = Chestnut Ridge Security Pits
 ECRWP = East Chestnut Ridge Waste Pile
 FCAP = Filled Coal Ash Pond
 KHQ = Kerr Hollow Quarry
 LIJ = Industrial Landfill II
 LIV = Industrial Landfill IV
 LV = Industrial Landfill V
 ORSF = Oak Ridge Sludge Farm
 RQ = Rogers Quarry
 SSCR = South Side Chestnut Ridge
 UNCS = United Nuclear Corporation Site

- 3 The measuring point is the surveyed elevation of a mark on either the top of the innermost well casing or the top of dedicated sampling equipment, in feet above mean sea level.

- 4 The depth to water is in feet below the measuring point.

- 5 The groundwater elevation (measuring point - depth to water) is in feet above mean sea level.

Table 16. CY 2007 leachate sampling results for the East Chestnut Ridge Waste Pile

Analyte (units)	Target Compound ¹	March 12, 2007		August 21, 2007	
		Result ²	Det. Limit	Result ²	Det. Limit
Inorganics (mg/L)					
Aluminum		0.2 U	0.2	0.2 U	0.2
Antimony	Y	0.004 U	0.004	0.003 U	0.003
Arsenic	Y	0.004 U	0.004	0.004 U	0.004
Barium	Y	0.0406	0.004	0.0437	0.004
Beryllium		0.004 U	0.004	0.004 U	0.004
Boron	Y	NA		0.332	0.01
Cadmium	Y	0.004 U	0.004	0.00012 U	0.00012
Chloride	Y	41	2.5	42.2	2.5
Chromium	Y	0.004 U	0.004	0.004 U	0.004
Cobalt	Y	0.004 U	0.004	0.004 U	0.004
Copper	Y	0.004 U	0.004	0.004 U	0.004
Iron	Y	0.418	0.2	0.2 U	0.2
Lead	Y	0.004 U	0.004	0.002 U	0.002
Lithium	Y	0.136	0.01	0.151	0.01
Manganese	Y	0.0196	0.005	0.005 U	0.005
Mercury	Y	0.0002 U	0.0002	0.0002 U	0.0002
Nickel	Y	0.01 U	0.01	0.01 U	0.01
Nitrate (as N)	Y	0.34	0.02	0.75	0.02
Potassium		NA		7.88	0.025
Selenium	Y	0.005 U	0.005	0.0025 U	0.0025
Silver		0.005 U	0.005	0.0015 U	0.0015
Sodium		NA		20.2	0.01
Strontium		0.366	0.005	0.41	0.005
Sulfate	Y	6	0.25	6.4	0.25
Thallium	Y	0.002 U	0.002	0.002 U	0.002
Uranium	Y	0.0146	0.00104	0.0115	0.00105
Vanadium		0.01 U	0.01	0.01 U	0.01
Zinc	Y	0.2 U	0.2	0.2 U	0.2
Organics (µg/L)					
1,1,1-Trichloroethane	Y	58	5	24	5
1,1,2,2-Tetrachloroethane		5 U	5	5 U	5
1,1,2-Trichloroethane		5 U	5	5 U	5
1,1-Dichloroethane	Y	360	10	130	5
1,1-Dichloroethene	Y	5	5	2 J	5
1,2-Dichloroethane	Y	5 U	5	1 J	5
1,2-Dichloropropane		5 U	5	5 U	5
2-Butanone		[4] U	10	10 U	10
2-Hexanone		10 U	10	10 U	10
4-Methyl-2-pentanone		10 U	10	10 U	10
Acetone		[2] U	10	10 U	10
Benzene	Y	5 U	5	5 U	5
Bromodichloromethane		5 U	5	5 U	5
Bromoform		5 U	5	5 U	5
Bromomethane		10 U	10	10 U	10

Table 16 (continued)

Analyte	Target Compound ¹	March 12, 2007			August 21, 2007		
		Result ²	Det. Limit		Result ²	Det. Limit	
Organics (µg/L)							
Carbon disulfide		5 U	5		5 U	5	
Carbon tetrachloride	Y	5 U	5		5 U	5	
Chlorobenzene		5 U	5		5 U	5	
Chloroethane	*	13	10		45	10	
Chloroform	Y	5 U	5		5 U	5	
Chloromethane	Y*	10 U	10		10 U	10	
cis-1,2-Dichloroethene	Y	380	10		93	5	
cis-1,3-Dichloropropene		5 U	5		5 U	5	
Dibromochloromethane		5 U	5		5 U	5	
Ethylbenzene		5 U	5		5 U	5	
Methylene chloride	Y	[2] U	5		5 U	5	
Styrene		5 U	5		5 U	5	
Tetrachloroethene	Y	2 J	5		5 U	5	
Toluene		5 U	5		5 U	5	
Total Xylene		5 U	5		5 U	5	
trans-1,2-Dichloroethene	Y	5 U	5		5 U	5	
trans-1,3-Dichloropropene		1 J	5		5 U	5	
Trichloroethene	Y	2 U	2		5 U	5	
Vinyl chloride	Y	5 U	5		2 J	2	
Radioanalytes (pCi/L) ³							
		Result	TPU	MDA	Result	TPU	MDA
Alpha activity	Y	9.42	1.45	4.59	5.84	1.17	4.01
Beta activity		11.5	1.83	7.65	10	1.85	7.96

Notes:

- Y = RCRA Groundwater Target List Compound
* = Suspected typographical error; chloroethane incorrectly listed as chloromethane
- Bold type = Detected result
NA = Not analyzed
[] = False-positive result (not detected)
J = Estimated value
U = Not detected
- MDA = Minimum detectable activity
TPU = Total propagated uncertainty

APPENDIX C

**CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA
FOR THE BEAR CREEK HYDROGEOLOGIC REGIME**

EXPLANATION

SAMPLE TYPE:

Dup = field duplicate sample (Table 4 only)

UNITS:

Degrees C = water temperature in degrees of the Celsius scale
ft = feet; elevations are above mean sea level and depth to water
is the distance from the measuring point
µg/L = micrograms per liter
µmho/cm = micromhos per centimeter
mg/L = milligrams per liter
mV = millivolts
NTU = nephelometric turbidity units
pCi/L = picoCuries per liter
ppm = parts per million

DATA QUALIFIERS:

B = also detected in the associated method blank (organics)
D = analysis performed at a secondary dilution to achieve an optimum matrix
J = positively identified, estimated value below the quantitation level (organics)
U = not detected at or above the project quantitation level

NOTES:

. = not analyzed
Error = total propagated uncertainty (two standard deviations) (radiochemistry)
MDA = minimum detectable activity (radiochemistry)

This page intentionally left blank.

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 1. S-3 Site Point-of-Compliance

Well Date Sampled	GW-276					
	01/03/07			07/09/07		
Field Measurements	Result			Result		
Time Sampled	9:35			9:05		
Measuring Point Elev. (ft)	1001.57			1001.57		
Depth to Water (ft)	5.87			7.94		
Groundwater Elevation (ft)	995.70			993.63		
Conductivity (µmho/cm)	396			522		
Dissolved Oxygen (ppm)	7.65			1.2		
Oxidation/Reduction (mV)	255			254		
Temperature (degrees C)	12			23.8		
Turbidity (NTU)	1			8		
pH	4.94			5.81		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Barium	0.0794	0.005		0.1	0.005	
Cadmium	0.0099	0.001		0.0074	0.00012	
Chromium	0.005 U	0.005		0.005 U	0.005	
Mercury	0.00024	0.0002		0.0002 U	0.0002	
Nickel	0.125	0.01		0.102	0.01	
Nitrate (as N)	19.4	1		29.6	1	
Uranium	0.45	0.00009		0.21	0.00003	
Organics (µg/L)	Result	Det. Limit		Result	Det. Limit	
Acetone	3 BJ	10		10 U	10	
Chloroform	5 U	5		5 U	5	
cis-1,2-Dichloroethene	5 U	5		5 U	5	
Methylene chloride	3 BJ	5		1 BJ	2	
Tetrachloroethene	5	5		4	2	
Trichloroethene	5 U	5		2 U	2	
Radionuclides (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	120	20.6	2.65	109	19.1	2.26
Beta activity	151	24.9	5.42	218	35.5	4.79
Americium-241	0.0681	0.0886	0.123	0.0427	0.0388	0.0232
Neptunium-237	6.77	2.72	0.108	4.6	1.84	0.0663
Total Radium	1.24	0.593	0.408	0.177	0.101	0.132
Strontium-90	1.4	0.659	0.913	2.41	1.31	2.38
Technetium-99	233	38.5	6.47	282	46.1	6.09
Uranium-234	57.2	11	0.339	49.2	9.15	0.544
Uranium-235	3.2	1.16	0.216	3.96	1.36	0.488
Uranium-238	118	21.9	0.293	107	18.7	0.489

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 2. Oil Landfarm Point-of-Compliance

Well Date Sampled	GW-008					
	01/02/07			07/02/07		
Field Measurements	Result			Result		
Time Sampled	13:23			13:16		
Measuring Point Elev. (ft)	965.39			965.39		
Depth to Water (ft)	14.42			16.56		
Groundwater Elevation (ft)	950.97			948.83		
Conductivity (umho/cm)	222			135		
Dissolved Oxygen (ppm)	1.21			1.21		
Oxidation/Reduction (mV)	118			128		
Temperature (degrees C)	17			18		
Turbidity (NTU)	1			2		
pH	5.77			6.02		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Barium	0.093	0.005		0.121	0.005	
Cadmium	0.001 U	0.001		0.00012 U	0.00012	
Mercury	0.0002 U	0.0002		0.0002 U	0.0002	
Uranium	0.000054 B	0.000009		0.000046 B	0.0000046	
Organics (µg/L)	Result	Det. Limit		Result	Det. Limit	
1,1-Dichloroethene	6	5		4	3	
cis-1,2-Dichloroethene	21	5		23	5	
Tetrachloroethene	40	5		73	2	
Trichloroethene	9	5		11	2	
Radionuclides (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	-0.51	0.578	2.07	1.93	1.35	2.05
Beta activity	2.22	1.64	3.32	3.54	1.92	3.61

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 3. BC Burial Grounds/Walk-In Pits Point-of-Compliance

Well Date Sampled	GW-046					
	01/03/07			07/02/07		
Field Measurements	Result			Result		
Time Sampled	9:35			13:50		
Measuring Point Elev. (ft)	921.17			921.17		
Depth to Water (ft)	4.02			5.52		
Groundwater Elevation (ft)	917.15			915.65		
Conductivity (µmho/cm)	212			110		
Dissolved Oxygen (ppm)	0.42			0.24		
Oxidation/Reduction (mV)	202			180		
Temperature (degrees C)	14.5			18.1		
Turbidity (NTU)	3			6		
pH	5.56			5.37		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Uranium	0.000065 B	0.000009		0.000047 B	0.0000046	
Organics (µg/L)	Result	Det. Limit		Result	Det. Limit	
1,1,1-Trichloroethane	33	5		19	5	
1,1-Dichloroethane	95	5		70	5	
1,1-Dichloroethene	46	5		27	3	
Benzene	9	5		9	2	
cis-1,2-Dichloroethene	2,500 D	120		1,700 D	250	
Tetrachloroethene	370 D	120		420 D	100	
Trichloroethene	730 D	120		620 D	100	
Vinyl Chloride	240 D	50		170 D	50	
Radionuclides (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	0.873	1.01	2.02	1.13	1.07	1.85
Beta activity	2.19	1.9	3.95	2.16	1.78	3.65
Technetium-99	-3.69	3.44	6.15	0.518	4.07	6.95
Uranium-234	-0.0269	0.156	0.283	0.408	0.364	0.476
Uranium-235	0.0527	0.184	0.143	0.231	0.273	0.41
Uranium-238	0.0787	0.157	0.223	0.153	0.238	0.445

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 4. Plume boundary monitoring locations

Sampling Location Date Sampled Sample Type	GW-712				GW-713				
	01/02/07		07/02/07		01/02/07				
							Dup		
Field Measurements	Result		Result		Result		Result		
Time Sampled	9:55		9:20		13:45		.		
Measuring Point Elev. (ft)	877.89		877.89		881.43		.		
Depth to Water (ft)	32.69		34.79		35.68		.		
Groundwater Elevation (ft)	845.20		843.10		845.75		.		
Conductivity (µmho/cm)	279		288		250		.		
Dissolved Oxygen (ppm)	1.91		1.45		3.5		.		
Oxidation/Reduction (mV)	43		219		-154		.		
Temperature (degrees C)	11.4		17.9		10.4		.		
Turbidity (NTU)	3		9		3		.		
pH	7.75		8.01		7.96		.		
Inorganics (mg/L)	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit	
Nitrate (as N)	0.02 U	0.02	0.02 U	0.02	0.02 U	0.02	0.02 U	0.02	
Uranium	0.0002 B	0.000009	0.00013 B	0.0000046	0.000074 B	0.000009	0.000075 B	0.000009	
Organics (µg/L)	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit	
1,1,1-Trichloroethane	5 U	5	5 U	5	5 U	5	5 U	5	
Benzene	5 U	5	2 U	2	5 U	5	5 U	5	
cis-1,2-Dichloroethene	5 U	5	5 U	5	5 U	5	5 U	5	
Methylene Chloride	3 B J	5	1 B J	2	2 B J	5	2 B J	5	
Tetrachloroethene	5 U	5	2 U	2	5 U	5	5 U	5	
Trichloroethene	5 U	5	2 U	2	5 U	5	5 U	5	
Radionuclides (pCi/L)	Result	TPU	MDA	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	0.206	0.834	2.08	1.74	1.26	1.96	-0.102	0.878	2.34
Beta activity	2.49	1.82	3.68	3.56	1.93	3.63	0.862	1.8	3.92
Technetium-99	-1.13	3.55	6.18	0.135	3.59	6.16	-2.26	3.4	6.01
Uranium-234	0.436	0.4	0.59	0.91	0.66	0.953	0.247	0.276	0.373
Uranium-235	0.0383	0.241	0.567	0.312	0.413	0.774	0.203	0.241	0.184
Uranium-238	0.0438	0.241	0.376	0.297	0.414	0.797	0.111	0.239	0.373
							0.268	0.272	0.182

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 4. (continued)

Sampling Location Date Sampled Sample Type	GW-713		GW-714	
	07/03/07		01/02/07	07/02/07
	Dup			
Field Measurements	Result	Result	Result	Result
Time Sampled	9:25	.	9:40	9:20
Measuring Point Elev. (ft)	881.43	.	874.92	875.88
Depth to Water (ft)	37.8	.	28.98	31.08
Groundwater Elevation (ft)	843.63	.	845.94	844.80
Conductivity (umho/cm)	305	.	578	546
Dissolved Oxygen (ppm)	2.22	.	0.95	1.31
Oxidation/Reduction (mV)	-169	.	227	90
Temperature (degrees C)	19.2	.	9.2	19.2
Turbidity (NTU)	8	.	3	14
pH	8.04	.	7.66	7.57
Inorganics (mg/L)	Result	Det. Limit	Result	Det. Limit
Nitrate (as N)	0.02 U	0.02	0.02 U	0.02
Uranium	0.00002 B	0.0000059	0.000014 B	0.0000059
Organics (ug/L)	Result	Det. Limit	Result	Det. Limit
1,1,1-Trichloroethane	5 U	5	5 U	5
Benzene	2 U	2	2 U	2
cis-1,2-Dichloroethene	5 U	5	5 U	5
Methylene Chloride	2 BJ	2	1 BJ	2
Tetrachloroethene	2 U	2	2 U	2
Trichloroethene	2 U	2	2 U	2
Radioanalytes (pCi/L)	Result	TPU	MDA	Result
Alpha activity	0.465	0.694	1.45	1.11
Beta activity	3.72	1.6	2.87	2.77
Technetium-99	-1.72	3.56	6.25	-0.213
Uranium-234	0.814	0.511	0.435	0.476
Uranium-235	0.129	0.251	0.333	0.427
Uranium-238	0.142	0.251	0.193	0.441

**Appendix C: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Bear Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-116**

Table 4. (continued)

Sampling Location Date Sampled Sample Type	SS-6					
	01/03/07			07/02/07		
Field Measurements	Result			Result		
Time Sampled	13:25			8:18		
Measuring Point Elev. (ft)	.			.		
Depth to Water (ft)	.			.		
Groundwater Elevation (ft)	.			.		
Conductivity (µmho/cm)	285			432		
Dissolved Oxygen (ppm)	10.7			4.97		
Oxidation/Reduction (mV)	88.7			93.7		
Temperature (degrees C)	14.32			15.64		
Turbidity (NTU)	3.69			6		
pH	7.86			7.01		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Nitrate (as N)	0.38	0.02		0.71	0.02	
Uranium	0.0025 B	0.000009		0.01	0.0000046	
Organics (µg/L)	Result	Det. Limit		Result	Det. Limit	
1,1,1-Trichloroethane	5 U	5		5 U	5	
Benzene	5 U	5		2 U	2	
cis-1,2-Dichloroethene	5 U	5		5 U	5	
Methylene Chloride	4 BJ	5		1 BJ	2	
Tetrachloroethene	5 U	5		2 U	2	
Trichloroethene	5 U	5		2 U	2	
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	1.18	1.01	1.78	4.77	2.27	2.37
Beta activity	3.64	1.9	3.59	6.33	2.38	3.91
Technetium-99	2.05	3.75	6.24	4.81	4.17	6.63
Uranium-234	0.564	0.321	0.204	0.743	0.546	0.628
Uranium-235	0.0482	0.168	0.131	0.137	0.294	0.458
Uranium-238	0.932	0.422	0.204	0.0617	0.294	0.661

APPENDIX D

**CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA
FOR THE UPPER EAST FORK POPLAR CREEK HYDROGEOLOGIC REGIME**

EXPLANATION

SAMPLE TYPE:

Dup = field duplicate sample (Table 2 only)

UNITS:

Degrees C = water temperature in degrees of the Celsius scale
ft = feet; elevations are above mean sea level and depth to water
is the distance from the measuring point
µg/L = micrograms per liter
µmho/cm = micromhos per centimeter
mg/L = milligrams per liter
mV = millivolts
NTU = nephelometric turbidity units
pCi/L = picoCuries per liter
ppm = parts per million

DATA QUALIFIERS:

B = also detected in the associated method blank (organics)
[C] = uranium concentration was calculated from isotopic uranium results (GW-108)
J = positively identified, estimated value below the quantitation level (organics)
U = not detected at or above the project quantitation level

NOTES:

. = not analyzed
Error = total propagated uncertainty (two standard deviations) (radiochemistry)
MDA = minimum detectable activity (radiochemistry)

This page intentionally left blank.

**Appendix D: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Upper East Fork Poplar Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-113**

Table 1. S-3 Site Point-of-Compliance

Well Date Sampled	GW-108					
	01/04/07			07/10/07		
Field Measurements	Result			Result		
Time Sampled	14:00			9:15		
Measuring Point Elev. (ft)	999.00			999.00		
Depth to Water (ft)	6.98			7.27		
Groundwater Elevation (ft)	992.02			991.73		
Conductivity (µmho/cm)	55,700			55,500		
Dissolved Oxygen (ppm)	4.48			0.72		
Oxidation/Reduction (mV)	298			157		
Temperature (degrees C)	19.2			22		
Turbidity (NTU)	0			2		
pH	5.56			5.42		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Barium	75.2	0.06		71.7	0.06	
Cadmium	0.012 U	0.012		0.0015 U	0.00144	
Chromium	0.06 U	0.06		0.06 U	0.06	
Mercury	0.0002 U	0.0002		0.0002 U	0.0002	
Nickel	0.196	0.12		0.182	0.12	
Nitrate (as N)	6,580	400		6,370	200	
Uranium	0.0166 [C]	0		0.0143 [C]	0	
Organics (µg/L)	Result	Det. Limit		Result	Det. Limit	
Acetone	9 BJ	10		8 J	10	
Chloroform	34	5		35	5	
cis-1,2-Dichloroethene	5 U	5		5 U	5	
Methylene chloride	50 B	5		48 B	2	
Tetrachloroethene	4 J	5		4	2	
Trichloroethene	4 J	5		3	2	
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	331	80.4	70	68.9	38.2	55.5
Beta activity	18,400	2,950	105	14,900	2390	102
Technetium-99	30,000	4,780	6.43	29,000	4,620	10.7

**Appendix D: CY 2007 RCRA Post-Closure Groundwater Monitoring Data
for the Upper East Fork Poplar Creek Hydrogeologic Regime
Tennessee Permit Number: TNHW-113**

Table 2. Plume boundary monitoring locations

Well Date Sampled Sample Type	GW-193			GW-605		
	01/04/07		07/09/07	01/03/07		
				Dup		
Field Measurements	Result		Result	Result	Result	
Time Sampled	9:40		9:30	13:55	.	
Measuring Point Elev. (ft)	934.17		934.17	919.06	.	
Depth to Water (ft)	9.18		9.78	11.25	.	
Groundwater Elevation (ft)	924.99		924.39	907.81	.	
Conductivity (µmho/cm)	825		1,222	374	.	
Dissolved Oxygen (ppm)	2.01		2.46	1.43	.	
Oxidation/Reduction (mV)	220		31	121	.	
Temperature (degrees C)	11.5		25.8	16.1	.	
Turbidity (NTU)	1		1	2	.	
pH	7.6		7.46	7.11	.	
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Technetium-99	1.69	3.57	5.97	3.47	3.62	5.85
				1.23	3.67	6.19
				1.09	3.55	6

Well Date Sampled Sample Type	GW-605			GW-606		
	07/09/07			01/03/07	07/09/07	
			Dup			
Field Measurements	Result		Result	Result	Result	
Time Sampled	9:30		.	13:45	13:15	
Measuring Point Elev. (ft)	919.06		.	919.59	919.59	
Depth to Water (ft)	11.35		.	13.43	14.28	
Groundwater Elevation (ft)	907.71		.	906.16	905.31	
Conductivity (µmho/cm)	708		.	900	747	
Dissolved Oxygen (ppm)	1.24		.	1.22	1.34	
Oxidation/Reduction (mV)	75		.	178	137	
Temperature (degrees C)	20.9		.	15.2	21.7	
Turbidity (NTU)	1		.	3	1	
pH	7.32		.	7.52	7.48	
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Technetium-99	1.93	3.5	5.83	-0.123	3.5	6.01
				-1.18	3.67	6.39
				0.994	3.44	5.82

Well Date Sampled Sample Type	GW-733					
	01/04/07			07/09/07		
Field Measurements	Result			Result		
Time Sampled	9:30			14:15		
Measuring Point Elev. (ft)	959.84			959.84		
Depth to Water (ft)	57.58			59.81		
Groundwater Elevation (ft)	902.26			900.03		
Conductivity (µmho/cm)	210			209		
Dissolved Oxygen (ppm)	7.34			2.01		
Oxidation/Reduction (mV)	188			130		
Temperature (degrees C)	9.8			27.2		
Turbidity (NTU)	1			4		
pH	7.53			7.81		
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Technetium-99	0.87	3.51	5.95	0.314	3.45	5.9

APPENDIX E

**CY 2007 RCRA POST-CLOSURE GROUNDWATER MONITORING DATA
FOR THE CHESTNUT RIDGE HYDROGEOLOGIC REGIME**

EXPLANATION

LOCATION:

CDLVI = Construction/Demolition Landfill VII
CRBAWP = Chestnut Ridge Borrow Area Waste Pile
CRSP = Chestnut Ridge Security Pits
ECRWP = East Chestnut Ridge Waste Pile
FCAP = Filled Coal Ash Pond
LIV = Industrial Landfill IV
LV = Industrial Landfill V

SAMPLE TYPE:

Dup = field duplicate sample

UNITS:

Degrees C = water temperature in degrees of the Celsius scale
ft = feet; elevations are above mean sea level and depth to water
is the distance from the measuring point
 $\mu\text{g/L}$ = micrograms per liter
 $\mu\text{mho/cm}$ = micromhos per centimeter
 mg/L = milligrams per liter
mV = millivolts
NTU = nephelometric turbidity units
 pCi/L = picoCuries per liter
ppm = parts per million

DATA QUALIFIERS:

All Analytes:

U = not detected at or above the project quantitation level
Bold type = result exceeds background value (detection monitoring)

Inorganics:

B = less than the project quantitation level but above the instrument detection limit
J = estimated value

Organics:

B = also detected in the associated method blank
J = positively identified, estimated value below the quantitation level

NOTES:

. = not analyzed
TPU = total propagated uncertainty (two standard deviations) (radiochemistry)
MDA = minimum detectable activity (radiochemistry)

APPENDIX E.1

CHESTNUT RIDGE SECURITY PITS

**Appendix E.1: CY 2007 Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Pits
Tennessee Permit Number: TNHW-128**

Table 1. Upgradient/Background Well

Well Location Date Sampled	GW-521					
	LIV					
	01/10/07			07/12/07		
Field Measurements	Result			Result		
Time Sampled	10:30			11:10		
Measuring Point Elev. (ft)	1182.88			1182.88		
Depth to Water (ft)	87.33			88.29		
Groundwater Elev. (ft)	1095.55			1094.59		
Conductivity (umho/cm)	367			674		
Dissolved Oxygen (ppm)	6.01			6.15		
Oxidation/Reduction (mV)	165			80		
Temperature (degrees C)	15.1			18.8		
Turbidity (NTU)	4			1		
pH	8.41			8.03		
Inorganics (mg/L)	Result	Det. Limit		Result	Det. Limit	
Cadmium	0.001 U	0.00004		0.0001 U	0.00004	
Chromium	0.005 U	0.0026		0.005 U	0.0005	
Lead	0.003 U	0.0026		0.003 U	0.00018	
Mercury	0.0002 U	0.000027		0.0002 U	0.000027	
Nickel	0.04 U	0.0078		0.01 U	0.0003	
Uranium	-0.0000153 U	0.00031		0.004 U	0.00062	
Organics (ug/L)	Result	Det. Limit		Result	Det. Limit	
Benzene	5 U	0.16		5 U	0.16	
Bromoform	1 U	0.19		5 U	0.19	
Carbon tetrachloride	5 U	0.19		5 U	0.19	
Chloroform	1 U	0.16		5 U	0.16	
1,1-Dichloroethane	1 U	0.16		5 U	0.16	
1,1-Dichloroethene	1 U	0.14		5 U	0.14	
1,2-Dichloroethane	1 U	0.13		5 U	0.13	
cis-1,2-Dichloroethene	1 U	0.15		5 U	0.15	
trans-1,2-Dichloroethene	0.5 U	0.15		5 U	0.15	
Tetrachloroethene	1 U	0.2		5 U	0.2	
1,1,1-Trichloroethane	1 U	0.16		5 U	0.16	
Trichloroethene	1 U	0.16		5 U	0.16	
Vinyl chloride	1 U	0.17		2 U	0.17	
Radioanalytes (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	1.6	1.3	1.9	-0.1	0.65	1.8
Beta activity	1.2	1.4	2.3	0.6	1	2.2

**Appendix E.1: CY 2007 Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Pits
Tennessee Permit Number: TNHW-128**

Table 2. Point-of-Compliance Well

Well Location Date Sampled	GW-177					
	CRSP					
	01/09/07			07/11/07		
Field Measurements	Result	Result				
Time Sampled	12:55	9:25				
Measuring Point Elev. (ft)	1158.20	1158.20				
Depth to Water (ft)	119.42	119.19				
Groundwater Elev. (ft)	1038.78	1039.01				
Conductivity (umho/cm)	192	495				
Dissolved Oxygen (ppm)	7.41	3.78				
Oxidation/Reduction (mV)	105	134				
Temperature (degrees C)	13.9	21.6				
Turbidity (NTU)	1	1				
pH	7.3	7.54				
Inorganics (mg/L)	Result	Det. Limit	Result			
Cadmium	0.001 U	0.001	0.0002	0.00012		
Chromium	0.0127	0.005	0.0194	0.005		
Lead	0.003 U	0.003	0.002 U	0.002		
Mercury	0.0002 U	0.0002	0.0002 U	0.0002		
Nickel	0.0113	0.01	0.0134	0.01		
Uranium	0.0011 B	0.000009	0.0011 B	0.0000059		
Organics (µg/L)	Result	Det. Limit	Result	Det. Limit		
Benzene	5 U	5	2 U	2		
Bromoform	5 U	5	5 U	5		
Carbon tetrachloride	5 U	5	2 U	2		
Chloroform	5 U	5	5 U	5		
1,1-Dichloroethane	26	5	25	5		
1,1-Dichloroethene	5	5	6	3		
1,2-Dichloroethane	5 U	5	2 U	2		
cis-1,2-Dichloroethene	5 U	5	5 U	5		
trans-1,2-Dichloroethene	5 U	5	5 U	5		
Tetrachloroethene	5 U	5	2 U	2		
1,1,1-Trichloroethane	8	5	7	5		
Trichloroethene	5 U	5	2 U	2		
Vinyl chloride	2 U	2	1 U	1		
Radionuclides (pCi/L)	Result	TPU	MDA	Result	TPU	MDA
Alpha activity	1.57	1.48	2.62	2.73	1.56	2.14
Beta activity	3.57	2.04	3.88	2.72	1.85	3.67

**Appendix E.1: CY 2007 Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Pits
Tennessee Permit Number: TNHW-128**

Table 3. Plume Delineation Wells

Sampling Point	GW-301				GW-301			
Location	CRBAWP				CRBAWP			
Date Sampled	01/09/07				07/12/07			
Sample Type			Dup				Dup	
Field Measurements	Result		Result		Result		Result	
Time Sampled	12:55		.		12:55		.	
Measuring Point Elev. (ft)	1086.55		.		1086.55		.	
Depth to Water (ft)	135.43		.		136.03		.	
Groundwater Elev. (ft)	951.12		.		950.52		.	
Conductivity (umho/cm)	786		.		284		.	
Dissolved Oxygen (ppm)	5.4		.		9.19		.	
Oxidation/Reduction (mV)	124		.		241		.	
Temperature (degrees C)	12.8		.		21.3		.	
Turbidity (NTU)	1		.		12		.	
pH	7.96		.		7.93		.	
Organics (ug/L)	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit	Result	Det. Limit
Benzene	5 U	5	5 U	5	2 U	2	2 U	2
Bromoform	5 U	5	5 U	5	5 U	5	5 U	5
Carbon tetrachloride	5 U	5	5 U	5	2 U	2	2 U	2
Chloroform	5 U	5	5 U	5	5 U	5	5 U	5
1,1-Dichloroethane	5 U	5	5 U	5	5 U	5	5 U	5
1,1-Dichloroethene	5 U	5	5 U	5	3 U	3	3 U	3
1,2-Dichloroethane	5 U	5	5 U	5	2 U	2	2 U	2
cis-1,2-Dichloroethene	5 U	5	5 U	5	5 U	5	5 U	5
trans-1,2-Dichloroethene	5 U	5	5 U	5	5 U	5	5 U	5
Tetrachloroethene	5 U	5	5 U	5	2 U	2	2 U	2
1,1,1-Trichloroethane	5 U	5	5 U	5	5 U	5	5 U	5
Trichloroethene	5 U	5	5 U	5	2 U	2	2 U	2
Vinyl chloride	2 U	2	2 U	2	1 U	1	1 U	1

**Appendix E.1: CY 2007 Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Pits
Tennessee Permit Number: TNHW-128**

Table 3. (continued)

Sampling Point Location Date Sampled Sample Type	GW-557		GW-562	
	LV		CDLVII	
	01/11/07	07/16/07	01/16/07	07/17/07
Field Measurements	Result	Result	Result	Result
Time Sampled	10:10	12:45	9:35	10:15
Measuring Point Elev. (ft)	1081.36	1081.36	934.69	934.69
Depth to Water (ft)	125.28	125.51	13.87	15.40
Groundwater Elev. (ft)	956.08	955.85	920.82	919.29
Conductivity (umho/cm)	352	205	440	236
Dissolved Oxygen (ppm)	11.12	9.28	6.53	4.63
Oxidation/Reduction (mV)	176	105	213	228
Temperature (degrees C)	14.6	19.8	12.2	17.1
Turbidity (NTU)	2	9	1	68
pH	7.66	7.72	7.74	7.71
Organics (µg/L)	Result Det. Limit	Result Det. Limit	Result Det. Limit	Result Det. Limit
Benzene	5 U 0.16	5 U 0.16	5 U 0.16	5 U 0.16
Bromoform	1 U 0.19	5 U 0.19	1 U 0.19	5 U 0.19
Carbon tetrachloride	5 U 0.19	5 U 0.19	5 U 0.19	5 U 0.19
Chloroform	1 U 0.16	5 U 0.16	1 U 0.16	5 U 0.16
1,1-Dichloroethane	1 U 0.16	5 U 0.16	1 U 0.16	5 U 0.16
1,1-Dichloroethene	1 U 0.14	5 U 0.14	1 U 0.14	5 U 0.14
1,2-Dichloroethane	1 U 0.13	5 U 0.13	1 U 0.13	5 U 0.13
cis-1,2-Dichloroethene	1 U 0.15	5 U 0.15	1 U 0.15	5 U 0.15
trans-1,2-Dichloroethene	0.5 U 0.15	5 U 0.15	0.5 U 0.15	5 U 0.15
Tetrachloroethene	1 U 0.2	5 U 0.2	1 U 0.2	5 U 0.2
1,1,1-Trichloroethane	1 U 0.16	5 U 0.16	1 U 0.16	5 U 0.16
Trichloroethene	1 U 0.16	5 U 0.16	1 U 0.16	5 U 0.16
Vinyl chloride	1 U 0.17	2 U 0.17	1 U 0.17	2 U 0.17

**Appendix E.1: CY 2007 Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Plts
Tennessee Permit Number: TNHW-128**

Table 3. (continued)

Sampling Point Location Date Sampled Sample Type	GW-799		GW-801	
	LV		LV	
	01/16/07	07/17/07	01/18/07	07/16/07
Field Measurements	Result	Result	Result	Result
Time Sampled	10:05	8:50	10:00	13:00
Measuring Point Elev. (ft)	981.29	981.29	1097.16	1097.16
Depth to Water (ft)	22.68	25.15	117.31	119.72
Groundwater Elev. (ft)	958.61	956.14	979.85	977.44
Conductivity (µmho/cm)	165	163	181	626
Dissolved Oxygen (ppm)	4.98	5.34	11.1	7.52
Oxidation/Reduction (mV)	187	173	186	75
Temperature (degrees C)	11.7	17.8	9.1	17.6
Turbidity (NTU)	2	20	2	5
pH	8.09	8.46	7.39	7.85
Organics (µg/L)	Result	Det. Limit	Result	Det. Limit
Benzene	5 U	0.16	5 U	0.16
Bromoform	1 U	0.19	5 U	0.19
Carbon tetrachloride	5 U	0.19	5 U	0.19
Chloroform	1 U	0.16	1 U	0.16
1,1-Dichloroethane	1 U	0.16	1 U	0.16
1,1-Dichloroethene	1 U	0.14	1 U	0.14
1,2-Dichloroethane	1 U	0.13	1 U	0.13
cis-1,2-Dichloroethene	1 U	0.15	1 U	0.15
trans-1,2-Dichloroethene	0.5 U	0.15	0.5 U	0.15
Tetrachloroethene	1 U	0.2	1 U	0.2
1,1,1-Trichloroethane	1 U	0.16	1 U	0.16
Trichloroethene	1 U	0.16	1 U	0.16
Vinyl chloride	1 U	0.17	1 U	0.17

**Appendix E.1: CY 2007 RCRA Post-Closure Corrective Action Monitoring Data
for the Chestnut Ridge Security Pits
Tennessee Permit Number: TNHW-128**

Table 3. (continued)

Sampling Point Location Date Sampled Sample Type	GW-831		SCR4.3SP	
	FCAP		CDLVII	
	01/09/07	07/11/07	01/16/07	07/17/07
	Result	Result	Result	Result
Field Measurements				
Time Sampled	9:40	14:20	13:45	14:10
Measuring Point Elev. (ft)	1091.29	1091.29	-	-
Depth to Water (ft)	131.55	132.13	-	-
Groundwater Elev. (ft)	959.74	959.16	-	-
Conductivity (µmho/cm)	205	626	360	199
Dissolved Oxygen (ppm)	7.45	7.26	10.65	5.68
Oxidation/Reduction (mV)	206	84	144	147
Temperature (degrees C)	7.6	19.7	10.1	17.7
Turbidity (NTU)	1	2	49	14
pH	8.21	8.26	8.12	7.54
Organics (µg/L)	Result	Det. Limit	Result	Det. Limit
Benzene	5 U	5	5 U	0.16
Bromoform	5 U	5	1 U	0.19
Carbon tetrachloride	5 U	5	5 U	0.19
Chloroform	5 U	5	1 U	0.16
1,1-Dichloroethane	5 U	5	1 U	0.16
1,1-Dichloroethene	5 U	5	1 U	0.14
1,2-Dichloroethane	5 U	5	1 U	0.13
cis-1,2-Dichloroethene	5 U	5	1 U	0.15
trans-1,2-Dichloroethene	5 U	5	0.5 U	0.15
Tetrachloroethene	5 U	5	1 U	0.2
1,1,1-Trichloroethane	5 U	5	1 U	0.16
Trichloroethene	5 U	5	1 U	0.16
Vinyl chloride	2 U	2	1 U	0.17

APPENDIX E.2

CHESTNUT RIDGE SEDIMENT DISPOSAL BASIN

**Appendix E.2: CY 2007 RCRA Post-Closure Detection Monitoring Data
for the Chestnut Ridge Sediment Disposal Basin
Tennessee Permit Number: TNHW-128**

Table 1. Target constituents

Monitoring Purpose Well Date Sampled Sample Type	Upgradient/ Background	Point of Compliance			
	GW-159	GW-156		GW-731	GW-732
	01/08/07	01/08/07		01/09/07	01/09/07
			Dup		
Field Measurements					
Time Sampled	13:35	13:10	.	9:25	13:15
Measuring Point Elev. (ft)	1051.40	1049.30	.	1049.38	1064.29
Depth to Water (ft)	118.00	143.56	.	125.20	157.63
Groundwater Elev. (ft)	933.40	905.74	.	924.18	906.66
Conductivity (umho/cm)	438	362	.	269	369
Dissolved Oxygen (ppm)	6.62	10.03	.	5.75	6.88
Oxidation/Reduction (mV)	230	58	.	197	161
Temperature (degrees C)	12.1	11.2	.	11	14.2
Turbidity (NTU)	2	1	.	17	1
pH	7.84	7.32	.	8.3	7.62
Target Constituents (mg/L)					
Cadmium	0.001 U	0.001 U	0.001 U	0.001 U	0.001 U
Chromium	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Lead	0.003 U	0.003 U	0.003 U	0.003 U	0.003 U
Mercury	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U
Nickel	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Silver	0.004 U	0.004 U	0.004 U	0.004 U	0.004 U
Uranium	0.0012 B	0.002 B	0.0021 B	0.0003 B	0.00022 B

APPENDIX E.3

KERR HOLLOW QUARRY

**Appendix E.3: CY 2007 RCRA Post-Closure Detection Monitoring Data
for Kerr Hollow Quarry
Tennessee Permit Number: TNHW-128**

Table 1. Inorganic and organic constituents

Monitoring Purpose Well Date Sampled Sample Type	Upgradient/Background		Point of Compliance		
	GW-231		GW-143	GW-144	GW-145
	01/04/07		01/08/07	01/04/07	01/08/07
		Dup			
Field Measurements					
Time Sampled	13:45	.	10:20	15:10	9:55
Measuring Point Elev. (ft)	849.67	.	913.98	913.54	840.24
Depth to Water (ft)	17.44	.	81.65	82.1	7.05
Groundwater Elevation (ft)	832.23	.	832.33	831.44	833.19
Conductivity (umho/cm)	257	.	278	233	681
Dissolved Oxygen (ppm)	3.08	.	4.34	7.36	4.48
Oxidation/Reduction (mV)	129	.	-124	132	198
Temperature (degrees C)	14.3	.	9.8	14.6	8.5
Turbidity (NTU)	3	.	1	1	1
pH	7.26	.	7.73	7.5	7.7
Inorganics (mg/L)					
Cadmium	0.001 U	0.001 U	0.001 U	0.001 U	0.001 U
Chromium	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Lead	0.003 U	0.003 U	0.003 U	0.003 U	0.003 U
Mercury	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U
Nickel	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Uranium	0.00043 B	0.00043 B	0.00035 B	0.0011 B	0.012
Organic Compounds (µg/L)					
Carbon tetrachloride	5 U	5 U	5 U	5 U	5 U
Chloroform	5 U	5 U	5 U	5 U	5 U
Tetrachloroethene	5 U	5 U	5 U	5 U	5 U

**Appendix E.3: CY 2007 RCRA Post-Closure Detection Monitoring Data
for Kerr Hollow Quarry
Tennessee Permit Number: TNHW-128**

Table 2. Radiochemical constituents

Monitoring Purpose	Well	Date Sampled	Gross Alpha Activity (pCi/L)			Gross Beta Activity (pCi/L)		
			Result	TPU	MDA	Result	TPU	MDA
Upgradient/ Background	GW-231	01/04/07	1.63	1.43	2.4	4.27	2.16	3.98
	GW-231 Dup	01/04/07	0.673	1.12	2.38	2.85	1.95	3.9
Point of Compliance	GW-143	01/08/07	3.72	1.87	2.26	15.1	3.63	3.94
	GW-144	01/04/07	2.47	1.7	2.45	2.94	1.96	3.85
	GW-145	01/08/07	12.50	3.66	2.22	9.97	2.95	4.04

APPENDIX E.4

EAST CHESTNUT RIDGE WASTE PILE

**Appendix E.4: CY 2007 RCRA Post-Closure Detection Monitoring Data
for the East Chestnut Ridge Waste Pile,
Tennessee Permit Number: TNHW-128**

Table 1. Inorganic and organic constituents

Monitoring Purpose Well Date Sampled Sample Type	Upgradient/Background		Point of Compliance			
	GW-294		GW-161		GW-292	
	01/22/07	07/11/07	01/25/07	07/10/07	01/23/07	07/10/07
Field Measurements						
Time Sampled	10:45	13:30	13:25	14:20	9:30	9:35
Measuring Point Elev. (ft)	1083.60	1083.60	1093.54	1093.54	1073.00	1073.00
Depth to Water (ft)	95.70	101.73	160.12	161.98	113.54	115.51
Groundwater Elevation (ft)	987.90	981.87	933.42	931.56	959.46	957.49
Conductivity (umho/cm)	575	487	800	936	502	576
Dissolved Oxygen (ppm)	9.65	5.84	8.01	4.49	7.4	3.35
Oxidation/Reduction (mV)	292	155	104	87	211	180
Temperature (degrees C)	13.8	23.5	14.2	17.6	12.7	17.3
Turbidity (NTU)	1	1	6	17	3	5
pH	7.42	7.56	7.6	7.96	7.52	7.58
Inorganics (mg/L)						
Antimony	0.006 U	0.003 U	0.006 U	0.003 U	0.006 U	0.003 U
Arsenic	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Barium	0.0127	0.012	0.0148	0.0143	0.116	0.103
Boron	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Cadmium	0.001 U	0.00012 U	0.001 U	0.0002	0.001 U	0.00012 U
Chloride	13.5	9.6	2.6	2.6	11.5	10.5
Chromium	0.005 U	0.005 U	0.005 U	0.005 U	0.01	0.0257
Cobalt	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Copper	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.0055
Iron	0.0217	0.0181	2.59	4.14	0.21	0.588
Lead	0.003 U	0.002 U	0.003 U	0.002 U	0.003 U	0.002 U
Lithium	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Manganese	0.005 U	0.005 U	0.0079	0.262	0.005 U	0.0114
Mercury	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U
Nickel	0.01 U	0.01 U	0.01 U	0.01 U	0.0541	0.0747
Nitrate (as N)	1.7	1.3	0.22	0.02 U	0.39	0.35
Selenium	0.005 U	0.0025 U	0.005 U	0.0025 U	0.005 U	0.0025 U
Sulfate	2.9	2.6	1.5	0.58	4.1	4.5
Thallium	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U
Uranium	0.00016 B	0.00014 B	0.00035 B	0.000086 B	0.0002 B	0.00041 B
Zinc	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Organic Compounds (ug/L)						
Benzene	5 U	2 U	5 U	2 U	5 U	2 U
Carbon Tetrachloride	5 U	2 U	5 U	2 U	5 U	2 U
Chloroform	5 U	5 U	5 U	5 U	5 U	5 U
Chloromethane	10 U	10 U	10 U	10 U	10 U	10 U
1,1-Dichloroethane	5 U	5 U	5 U	5 U	5 U	5 U
1,1-Dichloroethene	5 U	3 U	5 U	3 U	5 U	3 U
1,2-Dichloroethane	5 U	2 U	5 U	2 U	5 U	2 U
cis-1,2-Dichloroethene	5 U	5 U	5 U	5 U	5 U	5 U
trans-1,2-Dichloroethene	5 U	5 U	5 U	5 U	5 U	5 U
Methylene Chloride	4 B1	2 U	1 B1	2 U	3 B1	1 U
Tetrachloroethene	5 U	2 U	5 U	2 U	5 U	2 U
1,1,1-Trichloroethane	5 U	5 U	5 U	5 U	5 U	5 U
Trichloroethene	5 U	2 U	5 U	2 U	5 U	2 U
Vinyl Chloride	2 U	1 U	2 U	1 U	2 U	1 U

**Appendix E.4: CY 2007 RCRA Post-Closure Detection Monitoring Data
for the East Chestnut Ridge Waste Pile,
Tennessee Permit Number: TNHW-128**

Table 1 (continued)

Monitoring Purpose Well	Point of Compliance							
	GW-293				GW-296		GW-298	
	01/24/07		07/10/07		01/22/07	07/10/07	01/29/07	07/09/07
		Dup		Dup				
Field Measurements								
Time Sampled	10:15	-	9:35	-	13:50	13:10	10:30	13:15
Measuring Point Elev. (ft)	1063.90	-	1063.90	-	1090.99	1090.99	1049.01	1049.01
Depth to Water (ft)	115.99	-	117.59	-	118.51	119.66	109.25	110.92
Groundwater Elevation (ft)	947.91	-	946.31	-	972.48	971.33	939.76	938.09
Conductivity (µmho/cm)	658	-	320	-	510	551	677	672
Dissolved Oxygen (ppm)	14.58	-	2.3	-	7.1	4.29	6.61	2.38
Oxidation/Reduction (mV)	243	-	248	-	207	134	189	20
Temperature (degrees C)	13.1	-	20.5	-	14.1	16.7	5.1	24.2
Turbidity (NTU)	6	-	100	-	0	2	3	3
pH	7.33	-	7.57	-	7.54	7.5	7.81	8.07
Inorganics (mg/L)								
Antimony	0.006 U	0.006 U	0.003 U	0.003 U	0.006 U	0.003 U	0.006 U	0.003 U
Arsenic	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Barium	0.204	0.203	0.165	0.157	0.0108	0.0101	0.0172	0.0147
Boron	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Cadmium	0.001 U	0.001 U	0.00012 U	0.00012 U	0.001 U	0.00012 U	0.001 U	0.00012 U
Chloride	15.2	14.6	14.4	14.3	3.4	3.4	1.1	0.98
Chromium	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.0083
Cobalt	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Copper	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U	0.005 U
Iron	0.561	0.488	7.97	4.02	0.0193	0.01 U	0.0184	0.01 U
Lead	0.003 U	0.003 U	0.002 U	0.002 U	0.003 U	0.002 U	0.003 U	0.002 U
Lithium	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Manganese	0.0954	0.095	0.101	0.101	0.005 U	0.005 U	0.005 U	0.005 U
Mercury	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U	0.0002 U
Nickel	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U
Nitrate (as N)	0.28	0.31	0.028	0.026	0.6	0.15	0.4	0.075
Selenium	0.005 U	0.005 U	0.0025 U	0.0025 U	0.005 U	0.0025 U	0.005 U	0.0025 U
Sulfate	4.5	4.3	2.4	2.5	1.6	0.79	6.4	5.5
Thallium	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U	0.002 U
Uranium	0.00054 B	0.00052 B	0.000072 B	0.00013 B	0.00014 B	0.000094 B	0.0013 B	0.0015 B
Zinc	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.01 U	0.0144	0.01 U
Organic Compounds (µg/L)								
Benzene	5 U	5 U	2 U	2 U	5 U	2 U	5 U	2 U
Carbon Tetrachloride	5 U	5 U	2 U	2 U	5 U	2 U	5 U	2 U
Chloroform	5 U	5 U	5 U	5 U	5 U	5 U	5 U	5 U
Chloromethane	10 U	10 U	10 U	10 U	10 U	10 U	10 U	10 U
1,1-Dichloroethane	5 U	5 U	5 U	5 U	5 U	5 U	5 U	5 U
1,1-Dichloroethene	5 U	5 U	3 U	3 U	5 U	3 U	5 U	3 U
1,2-Dichloroethane	5 U	5 U	2 U	2 U	5 U	2 U	5 U	2 U
cis-1,2-Dichloroethene	5 U	5 U	5 U	5 U	5 U	5 U	5 U	5 U
trans-1,2-Dichloroethene	5 U	5 U	5 U	5 U	5 U	5 U	5 U	5 U
Methylene Chloride	1 BJ	1 BJ	2 B	2 B	3 BJ	1 J	2 BJ	2 U
Tetrachloroethene	5 U	5 U	2 U	2 U	5 U	2 U	5 U	2 U
1,1,1-Trichloroethane	5 U	5 U	5 U	5 U	5 U	5 U	5 U	5 U
Trichloroethene	5 U	5 U	2 U	2 U	5 U	2 U	5 U	2 U
Vinyl Chloride	2 U	2 U	1 U	1 U	2 U	1 U	2 U	1 U

**Appendix E.4: CY 2007 RCRA Post-Closure Detection Monitoring Data
for the East Chestnut Ridge Waste Pile,
Tennessee Permit Number: TNHW-128**

Table 2. Radiochemical constituents

Monitoring Purpose	Well	Date Sampled	Gross Alpha Activity (pCi/L)		
			Result	TPU	MDA
Upgradient/ Background	GW-294	01/22/07	2.02	1.42	2.09
	GW-294	07/11/07	0.95	1.28	2.53
Point of Compliance	GW-161	01/25/07	0.592	1.23	2.82
	GW-161	07/10/07	1.08	1.19	2.19
	GW-292	01/23/07	0.908	1.26	2.6
	GW-292	07/10/07	2.23	1.82	2.99
	GW-293	01/24/07	1.04	1.26	2.47
	GW-293 Dup	01/24/07	0.971	1.02	1.78
	GW-293	07/10/07	0.935	1.26	2.5
	GW-293 Dup	07/10/07	-0.379	0.746	2.51
	GW-296	01/22/07	0.618	1.01	2.19
	GW-296	07/10/07	0.754	1.04	2.07
	GW-298	01/29/07	1.89	1.56	2.53
	GW-298	07/09/07	2.18	1.5	2.1

APPENDIX E.5

**CY 2007 RCRA POST-CLOSURE DETECTION MONITORING
DATA EVALUATION REPORTS**

CONTENTS

Summary of Post-Closure Detection Monitoring at the Chestnut Ridge Sediment Disposal Basin, First Semiannual Reporting Period of Calendar Year 2007	E.5-5
Summary of Post-Closure Detection Monitoring at Kerr Hollow Quarry, First Semiannual Reporting Period of Calendar Year 2007	E.5-9
Summary of Post-Closure Detection Monitoring at East Chestnut Ridge Waste Pile, First Semiannual Reporting Period of Calendar Year 2007	E.5-13
Summary of Post-Closure Detection Monitoring at East Chestnut Ridge Waste Pile, Second Semiannual Reporting Period of Calendar Year 2007	E.5-21

This page intentionally left blank.

**SUMMARY OF POST-CLOSURE DETECTION MONITORING
AT THE CHESTNUT RIDGE SEDIMENT DISPOSAL BASIN,
FIRST SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007**

1.0 DATA EVALUATION PROCEDURE

Section 7.4 of post-closure permit TNHW-128 describes the statistical evaluation of the semiannual Resource Conservation and Recovery Act (RCRA) post-closure detection monitoring results for the following site-specific target list constituents: cadmium, chromium, lead, mercury, nickel, silver, and uranium. The monitoring network at the Chestnut Ridge Sediment Disposal Basin (CRSDB) consists of background well GW-159 and point-of-compliance (POC) wells GW-156, GW-731, and GW-732. The technical approach for the statistical evaluation procedures specified in Permit TNHW-128 are presented in Fig. 1 and summarized as follows:

- A. **Background Comparison.** The analytical results for the CRSDB target list constituents detected in the groundwater samples from each POC are compared to corresponding background values assumed to be representative of uncontaminated groundwater from the uppermost aquifer on Chestnut Ridge. A background value will be determined for each target list constituent for each semiannual monitoring event. Upper tolerance limits (UTLs) to be used as background values will be calculated using data obtained since January 1986 from the designated upgradient well(s) at the site. If the monitoring results for each target list constituent do not exceed the corresponding background value in each POC well, then a release to groundwater is not indicated and no further statistical testing is performed. If a monitoring result exceeds the corresponding UTL, one of two evaluation criteria below is applied.
- B. **Quantitative Trend Analysis.** If the concentration of a target list constituent in a particular POC well exceeds its corresponding UTL, and the constituent has been detected in at least 15% of the groundwater samples obtained from the well since January 1991, then a quantitative trend analysis (Kendall-Tau or equivalent) of time-series data for the particular POC well(s) is required to determine if a statistically significant increasing concentration trend is evident. The trend analysis will be completed within 60 days of receiving the laboratory analytical report showing the elevated result. Confirmation sampling will be performed within 30 days if the trend analysis shows a statistically significant concentration increase, or if the concentration of a target list compound exceeds the UTL for two successive sampling events.
- C. **Elevated Result Verification.** Verification sampling will be performed if the concentration of a target list constituent in a POC well exceeds the corresponding UTL, but the constituent has been detected in less than 15% of the groundwater samples obtained from the well since January 1991. The verification sample must be collected from the well within 30 days and analyzed for the constituent(s) of concern. If necessary to ensure collection of a representative sample, the POC well may be redeveloped before verification sampling. Confirmation sampling will be performed within 30 days if verification sampling results support the elevated concentration of the applicable target list constituent.

Fig. 1. Technical approach for evaluation of and response to groundwater quality data from RCRA detection monitoring at the Chestnut Ridge Sediment Disposal Basin.

2.0 RESULTS FOR THE FIRST SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007

The site-specific background value (UTL) for each target list constituent was determined using data obtained since 1986 for a pool of wells located upgradient of the site and current monitoring results for well GW-159. As shown in the following summary (Table 1), analytical results for the target list constituents in each POC well obtained during the current monitoring event were then compared to the corresponding background value.

Table 1. Background values determined for the CRSDB compared to monitoring results

Target List Constituent	Site-Specific Background Value (mg/L)	Maximum POC Concentration (mg/L)	POC Well(s) With Elevated Concentration
Cadmium	0.003	0.001 U	None
Chromium	0.025	0.005 U	None
Lead	0.05	0.003 U	None
Mercury	0.0002	0.0002 U	None
Nickel	0.05	0.01 U	None
Silver	0.02	0.004 U	None
Uranium	0.004	0.002 J	None
Notes: mg/L=milligrams per liter; "U" = not detected at the concentration shown; "J" = estimated value below project reporting limit.			

As shown by the maximum concentration reported for the POC wells during this monitoring event, none of the results exceed the applicable background value (Table 1). Therefore, a release of target list constituents to groundwater is not indicated at the site and no further action is required.

This page intentionally left blank.

**SUMMARY OF POST-CLOSURE DETECTION MONITORING
AT KERR HOLLOW QUARRY,
FIRST SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007**

1.0 DATA EVALUATION PROCEDURE

Section 7.4 of post-closure permit TNHW-128 describes the statistical evaluation of semiannual Resource Conservation and Recovery Act (RCRA) post-closure detection monitoring results for the following site-specific target list constituents: cadmium, chromium, lead, mercury, nickel, uranium, carbon tetrachloride, tetrachloroethene, chloroform, gross alpha activity, and gross beta activity. The monitoring network at Kerr Hollow Quarry (KHQ) consists of background well GW-231 and point-of-compliance (POC) wells GW-143, GW-144, and GW-145. The technical approach for the statistical evaluation procedures specified in Permit TNHW-128 are presented in Fig. 1 and summarized as follows:

- C. **Background Comparison.** The analytical results for the KHQ target list constituents detected in the groundwater samples from each POC are compared to corresponding background values assumed to be representative of uncontaminated groundwater from the uppermost aquifer on Chestnut Ridge. A background value will be determined for each inorganic target list constituent for each semiannual monitoring event. Upper tolerance limits (UTLs) to be used as background values will be calculated using data obtained since January 1986 from the designated upgradient well(s) at the site. Section 7.4.3 of the post-closure permit sets background values for organic compounds at 0 micrograms per liter ($\mu\text{g/L}$), for gross alpha activity at 15 picoCuries per liter (pCi/L), and for gross beta activity at 50 pCi/L . If the monitoring results for each target list constituent do not exceed the corresponding background value in each POC well, then a release to groundwater is not indicated and no further statistical testing is performed. If a monitoring result exceeds the corresponding background value, then one of two evaluation criteria below is applied.
- D. **Quantitative Trend Analysis.** If the concentration of an inorganic or radiological target list constituent in a particular POC well exceeds its corresponding background value, and the constituent has been detected in at least 15% of the groundwater samples obtained from the well since January 1991, then quantitative trend analysis (Kendall-Tau or equivalent) of time-series data for the particular POC well(s) is required to determine if a statistically significant increasing concentration trend is evident. The trend analysis will be completed within 60 days of receiving the laboratory analytical report showing the elevated result. Confirmation sampling will be performed within 30 days if the trend analysis shows a statistically significant concentration increase, or if the concentration of a target list compound exceeds the background value for two successive sampling events.
- C. **Elevated Concentration Verification.** Verification sampling will be performed if: (1) the concentration of an organic target list constituent in a POC well is detected (excluding false positives), or (2) an inorganic or radiological target list constituent exceeds the corresponding background value but is detected in less than 15% of the groundwater samples collected from the well since January 1991. The verification sample must be collected from the well within 30 days and analyzed for the constituent(s) of concern. If necessary to ensure collection of a representative sample, the POC well may be redeveloped before verification sampling. Confirmation sampling will be performed within 30 days if verification sampling results support the elevated concentration of the applicable target list constituent.

Fig. 1. Technical approach for evaluation of and response to groundwater quality data from RCRA detection monitoring at Kerr Hollow Quarry.

2.0 RESULTS FOR THE FIRST SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007

The site-specific background value for each inorganic target list constituent was determined using the available pool of upgradient analytical results obtained since 1986 and incorporated current monitoring results for well GW-231 (Table 1). The background values for the organic and radiological target list constituents, as defined in the post-closure permit, are also shown below in Table 1. Analytical results for the target list constituents in each POC well obtained during the current monitoring event were then compared to the corresponding background value.

Table 1. Background values determined for KHQ compared to monitoring results

Target List Constituent	Site-Specific Background Value	Maximum POC Concentration	POC Well(s) With Elevated Concentration
Inorganics (mg/L)			
Cadmium	0.003	0.001 U	None
Chromium	0.011	0.005 U	None
Lead	0.016	0.003 U	None
Mercury	0.0002	0.0002 U	None
Nickel	0.019	0.01 U	None
Uranium	0.024	0.012	None
Organics (µg/L)			
Carbon Tetrachloride	0	5 U	None
Chloroform	0	5 U	None
Tetrachloroethene	0	5 U	None
Radiological (pCi/L)			
Gross Alpha Activity	15	12.5	None
Gross Beta Activity	50	15.1	None
Notes: mg/L=milligrams per liter; "U" = not detected at the concentration shown.			

As shown by the maximum concentration reported for the POC wells during this monitoring event, none of the results exceed the applicable background value (Table 1). Therefore, a release of target list constituents to groundwater is not indicated at the site and no further action is required.

This page intentionally left blank.

SUMMARY OF RCRA POST-CLOSURE DETECTION MONITORING AT THE EAST CHESTNUT RIDGE WASTE PILE, FIRST SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007

1.0 INTRODUCTION

This report presents an evaluation of the groundwater quality monitoring data obtained at the East Chestnut Ridge Waste Pile (ECRWP) in January 2007. Groundwater monitoring at the site is required by the Resource Conservation and Recovery Act (RCRA) post-closure permit (PCP) for the Chestnut Ridge Hydrogeologic Regime, which was issued by the Tennessee Department of Environment and Conservation (TDEC) in September 2006 (TDEC permit no. TNHW-128).

General and site-specific terms and conditions of the PCP, along with the TDEC hazardous waste management regulations incorporated by reference, define the site-specific groundwater sampling and analysis requirements for RCRA post-closure detection monitoring at the ECRWP. Implementation of this monitoring program is intended to provide the data needed to detect a release of contaminants to the uppermost aquifer underlying the site.

2.0 RCRA GROUNDWATER SAMPLING AND ANALYSIS

Unfiltered groundwater samples were collected during January 2007 from the upgradient/background well (GW-294) and from each of the point-of-compliance (POC) wells (GW-161, GW-292, GW-293, GW-296, and GW-298) that comprise the RCRA well network at the ECRWP. Groundwater samples were collected in accordance with the low-flow minimal drawdown sampling procedure referenced in the PCP.

The PCP requires only three of the POC wells at the ECRWP to be sampled during each semiannual RCRA groundwater sampling event. Nevertheless, all five POC wells were sampled in January 2007 in order to provide more recent monitoring data for these wells, which were last sampled in May 1996.

Groundwater samples collected from the RCRA wells at the ECRWP were analyzed for the site-specific suite of RCRA target list constituents designated in the PCP (Table 1), which include 21 inorganic analytes (e.g., metals and anions), 14 volatile organic compounds (VOCs), and gross alpha activity. Laboratory analyses of the groundwater samples were performed in accordance with the approved analytical methods referenced in the PCP.

3.0 DATA EVALUATION

The PCP requires the RCRA post-closure detection monitoring data obtained at the ECRWP to be evaluated in accordance with the procedure flowcharted on Fig. 1. This procedure defines a three-part technical approach whereby: (1) the analytical result for each RCRA target list constituent detected in each POC is compared to a site-specific background value; (2) if the analytical result exceeds the background value for the RCRA target list constituent, quantitative trend analysis of the data for the constituent is performed (if sufficient data are available) to determine if the elevated concentration reflects a statistically significant increasing temporal trend; and (3) re-sampling of each applicable POC well to verify the elevated (i.e., >background) and increasing concentration trend evident for the applicable RCRA target list constituent(s).

Table 1. Background values determined for the ECRWP compared to monitoring results

Target List Constituent	Site-Specific Background Value	Maximum POC Concentration	POC Well(s) With Elevated Concentration
Inorganics (mg/L)			
Antimony	0.05	0.006 U	None
Arsenic	0.05	0.005 U	None
Barium	0.043	0.204	GW-292, GW-293
Boron	0.12	0.01 U	None
Cadmium	0.003	0.001 U	None
Chloride	10	15.2	GW-292, GW-293
Chromium	0.025	0.01	None
Cobalt	0.02	0.005 U	None
Copper	0.027	0.005 U	None
Iron	15	2.59	None
Lead	0.05	0.003 U	None
Lithium	0.026	0.01 U	None
Manganese	0.29	0.095	None
Mercury	0.0002	0.0002 U	None
Nickel	0.05	0.0541	GW-292
Nitrate (as N)	3	0.6	None
Selenium	0.05	0.005 U	None
Sulfate	43	6.4	None
Thallium	0.01	0.002 U	None
Uranium	0.004	0.0013 J	None
Zinc	0.12	0.0144	None
Organics (µg/L)			
Benzene	0	5 U	None
Carbon Tetrachloride	0	5 U	None
Chloroform	0	5 U	None
Chloromethane	0	5 U	None
1,1-Dichloroethane	0	5 U	None
1,1-Dichloroethene	0	5 U	None
1,2-Dichloroethane	0	5 U	None
cis-1,2-Dichloroethene	0	5 U	None
trans-1,2-Dichloroethene	0	5 U	None
1,1,1-Trichloroethane	0	5 U	None
Methylene Chloride	0	4 BJ [FP]	None
Tetrachloroethene	0	5 U	None
Trichloroethene	0	5 U	None
Vinyl Chloride	0	2 U	None
Radiological (pCi/L)			
Gross Alpha Activity	15	<MDA	None
Notes: mg/L=milligrams per liter; "U" = not detected at the concentration shown; "J" = estimated value; "BJ" = also detected in associated laboratory blank; [FP] = false-positive result (not detected) "<MDA" = less than the associated minimum detectable activity.

Fig. 1. Technical approach for evaluation of and response to groundwater quality data from RCRA detection monitoring at the East Chestnut Ridge Waste Pile.

3.1 Background Comparison

The PCP requires background values to be recalculated for each inorganic RCRA target list constituent detected in each POC well during each semiannual sampling event at the ECRWP. The background value for each applicable inorganic constituent was determined by the upper tolerance limit (UTL) calculated from data obtained for a group of upgradient wells since January 1986, including current RCRA post-closure detection monitoring results for upgradient/background well GW-294 (Table 1). Based on comparison with respective background values, elevated concentrations of inorganic RCRA target list constituents were reported for the groundwater samples collected in January 2007 from POC wells GW-292 (barium, chloride, and nickel) and GW-293 (barium and chloride).

The PCP defines a concentration of zero micrograms per liter ($\mu\text{g/L}$) as the background value for each VOC designated as a RCRA target list constituent for the ECRWP. Excluding false-positive results, none of these VOCs were detected in the groundwater samples collected from the RCRA wells in January 2007.

The PCP sets the background value for gross alpha activity at the 15 picoCuries per liter (pCi/L) maximum contaminant level (MCL) for drinking water. Gross alpha activity reported for the groundwater samples collected from the RCRA wells in January 2007 are all below the background value.

3.2 Quantitative Trend Analysis

Under the data evaluation procedure required by the PCP (Fig. 1), quantitative trend analysis (Kendall-Tau or equivalent) is performed for each applicable RCRA target list constituent that has sufficient data; i.e., was detected in least 15% of the groundwater samples collected from the applicable POC well since January 1991. Based on this criteria, only the elevated concentrations of barium and chloride reported for POC wells GW-292 and GW-293 were evaluated; insufficient data preclude quantitative trend analysis of the elevated nickel concentration reported for POC well GW-292 (see Enclosure 3).

Results of the quantitative trend analysis (Kendall Tau b) indicate statistically significant increasing concentration trends for barium in groundwater at well GW-292 (Fig. 2) and for chloride in groundwater at well GW-293 (Fig. 3). However, regardless of the trends, the elevated barium and chloride concentrations at these wells probably reflect localized geochemical variability and are not indicative of a potential contaminant release from the ECRWP. Extensive historical data from the many wells located on Chestnut Ridge show that barium and chloride are naturally present in the groundwater at concentrations that may exhibit wide local variability. For example, the chloride concentration reported for the groundwater sample collected from upgradient/background well GW-294 in January 2007 (13.5 mg/L) exceeds the background value (10 mg/L).

Aside from the elevated nickel concentration reported for the groundwater sample collected from well GW-292 in January 2007 (0.0541 mg/L), nickel was detected in only one previous sample from the well; therefore, insufficient data are available to perform quantitative trend analysis. Elevated nickel concentrations in the groundwater at this well probably do not indicate a contaminant release from the ECRWP; nickel is not a principal component of the leachate from the site and typically is immobile under the neutral pH of the groundwater in the well. Based on experience with other wells on Chestnut Ridge, the elevated nickel concentrations may be an artifact of microbiologically-induced corrosion of the stainless steel well screen.

Fig. 3. Concentrations of barium and chloride in groundwater samples from POC well GW-292.

Fig. 3. Concentrations of barium and chloride in groundwater samples from POC well GW-293.

3.3 Elevated Concentration Verification and Confirmation

Under the data evaluation procedure defined in the PCP (Fig. 1), verification sampling of each applicable POC well is required if: (1) an organic RCRA target list constituent is detected (excluding false positives), or (2) the concentration of an inorganic or radiological RCRA target list constituent exceeds the corresponding background value, but is detected in less than 15% of the groundwater samples collected from the well since January 1991. Confirmation sampling is required if: (1) results of verification support the elevated concentration, or (2) the concentration of an inorganic or radiological RCRA target list constituent exceeds the corresponding background value and quantitative trend analysis of the available data indicate a statistically significant increasing trend.

Based on the preceding criteria, the elevated concentrations of RCRA target list constituents detected in the groundwater samples collected in January 2007 from POC wells GW-292 and GW-293 warrant verification (nickel at GW-292) or confirmation (barium at GW-292; chloride at GW-293) sampling. However, as discussed in the previous sections, the elevated concentrations of barium, chloride, and nickel are most likely attributable to natural or in-situ geochemical conditions and, as such, do not serve as reliable indicators of potential contaminant releases from the ECRWP. Consequently, sampling to verify/confirm the elevated concentrations was deemed unnecessary.

4.0 CONCLUSIONS

A release or potential release of contaminants to the uppermost aquifer at the ECRWP is not indicted by evaluation of the analytical results reported for the unfiltered groundwater samples collected during January 2007 from the RCRA wells at the site.

The PCP requires semiannual collection of groundwater samples from three POC wells at the ECRWP. Accordingly, wells GW-161, GW-296, and GW-298 will serve as the primary POC wells for future RCRA groundwater sampling events, with wells GW-292 and GW-293 reserved as replacements for any of the primary POC wells that are irreparably damaged or destroyed.

This page intentionally left blank.

SUMMARY OF RCRA POST-CLOSURE DETECTION MONITORING AT THE EAST CHESTNUT RIDGE WASTE PILE, SECOND SEMIANNUAL REPORTING PERIOD OF CALENDAR YEAR 2007

1.0 INTRODUCTION

This report presents an evaluation of the groundwater quality monitoring data obtained at the East Chestnut Ridge Waste Pile (ECRWP) in July 2007. Groundwater monitoring at the site is required by the Resource Conservation and Recovery Act (RCRA) post-closure permit (PCP) for the Chestnut Ridge Hydrogeologic Regime, which was issued by the Tennessee Department of Environment and Conservation (TDEC) in September 2006 (TDEC permit no. TNHW-128).

General and site-specific terms and conditions of the PCP, along with the TDEC hazardous waste management regulations incorporated by reference, define the site-specific groundwater sampling and analysis requirements for RCRA post-closure detection monitoring at the ECRWP. Implementation of this monitoring program is intended to provide the data needed to detect a release of contaminants to the uppermost aquifer underlying the site.

2.0 RCRA GROUNDWATER SAMPLING AND ANALYSIS

Unfiltered groundwater samples were collected in July 2007 from the upgradient/background well (GW-294) and from each of the point-of-compliance (POC) wells (GW-161, GW-292, GW-293, GW-296, and GW-298) that comprise the well network for RCRA post-closure detection monitoring at the ECRWP. Groundwater samples were collected in accordance with the low-flow minimal drawdown sampling procedure referenced in the PCP.

The PCP requires at least three of the POC wells at the ECRWP to be included each semiannual RCRA groundwater sampling event. Nevertheless, all five POC wells were sampled in January and July 2007 in order to determine the condition of each well and obtain recent seasonal monitoring data for these wells, which were last sampled in May 1996.

Groundwater samples collected from the RCRA wells at the ECRWP were analyzed for the site-specific suite of RCRA target list constituents designated in the PCP (Table 1), which include 21 inorganic analytes (e.g., metals and anions), 14 volatile organic compounds (VOCs), and gross alpha activity. Laboratory analyses of the groundwater samples were performed in accordance with the approved analytical methods referenced in the PCP.

3.0 DATA EVALUATION

The PCP requires the RCRA post-closure detection monitoring data obtained at the ECRWP to be evaluated in accordance with the procedure flowcharted on Fig. 1. This procedure defines a three-part technical approach whereby: (1) the analytical result for each RCRA target list constituent detected in each POC well is compared to a site-specific background value; (2) if the analytical result exceeds the background value for the RCRA target list constituent, quantitative trend analysis of the data for the constituent is performed (if sufficient data are available) to determine if the elevated concentration reflects a statistically significant increasing temporal trend; and (3) re-sampling of each applicable POC well to verify the elevated (i.e., >background) and increasing concentration trend evident for the applicable RCRA target list constituent(s).

**Table 1. Background values and maximum concentrations of RCRA target list constituents
in POC wells at the ECRWP, July 2007**

Target List Constituent	Site-Specific Background Value	July 2007 Maximum Concentration	POC Well(s) With Elevated Concentration				
			GW-161	GW-292	GW-293	GW-296	GW-298
Inorganics (mg/L)							
Antimony	0.05	0.003 U	.	.	.	.	.
Arsenic	0.05	0.005 U	.	.	.	.	.
Barium	0.043	0.165	.	0.103	0.165	.	.
Boron	0.12	0.01 U	.	.	.	.	.
Cadmium	0.003	0.0002	.	.	.	.	.
Chloride	10	14.4	.	10.5	14.4	.	.
Chromium	0.025	0.0257	.	0.0257	.	.	.
Cobalt	0.02	0.005 U	.	.	.	.	.
Copper	0.027	0.0055	.	.	.	.	.
Iron	15	4.14	.	.	.	.	.
Lead	0.05	0.002 U	.	.	.	.	.
Lithium	0.026	0.01 U	.	.	.	.	.
Manganese	0.29	0.262	.	.	.	.	.
Mercury	0.0002	0.0002 U	.	.	.	.	.
Nickel	0.05	0.0747	.	0.0747	.	.	.
Nitrate (as N)	3	0.35	.	.	.	.	.
Selenium	0.05	0.0025 U	.	.	.	.	.
Sulfate	43	5.5	.	.	.	.	.
Thallium	0.01	0.002 U	.	.	.	.	.
Uranium	0.004	0.0015 J	.	.	.	.	.
Zinc	0.12	0.01 U	.	.	.	.	.
Organics (µg/L)							
Benzene	0	2 U	.	.	.	.	.
Carbon Tetrachloride	0	2 U	.	.	.	.	.
Chloroform	0	5 U	.	.	.	.	.
Chloromethane	0	10 U	.	.	.	.	.
1,1-Dichloroethane	0	5 U	.	.	.	.	.
1,1-Dichloroethene	0	3 U	.	.	.	.	.
1,2-Dichloroethane	0	2 U	.	.	.	.	.
cis-1,2-Dichloroethene	0	5 U	.	.	.	.	.
trans-1,2-Dichloroethene	0	5 U	.	.	.	.	.
1,1,1-Trichloroethane	0	2 U	.	.	.	.	.
Methylene Chloride	0	2 B [FP]	.	.	.	.	.
Tetrachloroethene	0	2 U	.	.	.	.	.
Trichloroethene	0	2 U	.	.	.	.	.
Vinyl Chloride	0	1 U	.	.	.	.	.
Radiological (pCi/L)							
Gross Alpha Activity	15	2.18	.	.	.	.	.
Notes: mg/L=milligrams per liter; "U" = not detected at the concentration shown; "J" = estimated value; "B" = also detected in associated laboratory blank; [FP] = false-positive result (not detected); "." = not applicable.

Fig. 1. Technical approach for evaluation of and response to groundwater quality data from RCRA detection monitoring at the East Chestnut Ridge Waste File.

3.1 Background Comparison

The PCP requires background values to be recalculated for each inorganic RCRA target list constituent detected in each POC well during each semiannual sampling event at the ECRWP. The background value for each applicable inorganic constituent was determined by the upper tolerance limit (UTL) calculated using data obtained since January 1986 for a group of wells on Chestnut Ridge, including current RCRA post-closure detection monitoring results for upgradient/background well GW-294 (Table 1). Based on comparison to respective background values, elevated concentrations of inorganic RCRA target list constituents were reported for the groundwater samples collected in July 2007 from POC wells GW-292 (barium, chloride, chromium, and nickel) and GW-293 (barium and chloride).

The PCP defines a concentration of zero micrograms per liter ($\mu\text{g/L}$) as the background value for each VOC designated as a RCRA target list constituent for the ECRWP. Excluding false-positive results, none of these VOCs were detected in the groundwater samples collected from the RCRA wells in July 2007.

The PCP sets the background value for gross alpha activity at the 15 picoCuries per liter (pCi/L) maximum contaminant level (MCL) for drinking water. Gross alpha activity reported for the groundwater samples collected from the RCRA wells in July 2007 are all below the background value.

3.2 Quantitative Trend Analysis

Under the data evaluation procedure required by the PCP (Fig. 1), quantitative trend analysis (Kendall-Tau or equivalent) is performed for each applicable RCRA target list constituent that has sufficient data; i.e., was detected in at least 15% of the groundwater samples collected from the applicable POC well since January 1991. Trend analyses were performed to evaluate the elevated concentrations of barium and chloride reported for POC wells GW-292 and GW-293, but not for the elevated nickel and chromium concentrations reported for well GW-292. Based on previous experience, the elevated nickel and chromium concentrations are likely artifacts attributable to corrosion of the stainless steel well casing or screen used to construct the well and are not indicative of a contaminant release from the ECRWP; both metals also were detected in the groundwater sample collected from well GW-292 in January 2007 and personnel with TDEC were notified.

Results of the quantitative trend analysis (Kendall Tau b) indicate a statistically significant increasing concentration trend only for chloride in groundwater at well GW-293. However, regardless of the trends (see Figure 2 and Figure 3), the elevated barium and chloride concentrations at these wells probably reflect localized geochemical variability and are not indicative of a potential contaminant release from the ECRWP. Extensive historical data from many of the wells on Chestnut Ridge show that barium and chloride are naturally present in the groundwater at concentrations that may exhibit wide local variability. For example, the chloride concentration reported for the groundwater sample collected from upgradient/background well GW-294 in July 2007 (13.5 mg/L) exceeds the background value (10 mg/L).

Fig. 3. Concentrations of barium and chloride in groundwater samples from POC well GW-292.

Fig. 3. Concentrations of barium and chloride in groundwater samples from POC well GW-293.

3.3 Elevated Concentration Verification and Confirmation

Under the data evaluation procedure defined in the PCP (Fig. 1), verification sampling of each applicable POC well is required if: (1) an organic RCRA target list constituent is detected (excluding false positives), or (2) the concentration of an inorganic or radiological RCRA target list constituent exceeds the corresponding background value, but is detected in less than 15% of the groundwater samples collected from the well since January 1991. Subsequent confirmation sampling is required if: (1) results of verification sampling support the elevated concentration, or (2) the concentration of an inorganic or radiological RCRA target list constituent exceeds the corresponding background value and quantitative trend analysis of the available data indicate a statistically significant increasing trend.

Based on the preceding criteria, the elevated concentrations of RCRA target list constituents detected in the groundwater samples collected in July 2007 from POC wells GW-292 and GW-293 warrant verification (chromium and nickel at GW-292) or confirmation (chloride at GW-293) sampling. However, as discussed in the previous sections, the elevated concentrations of barium, chloride, chromium, and nickel are most likely attributable to natural or in-situ geochemical conditions and, as such, do not serve as reliable indicators of potential contaminant releases from the ECRWP. Based on consent from TDEC personnel regarding similar monitoring results for the January sampling event, sampling to verify/confirm the elevated concentrations was not performed for the second reporting period of CY 2007.

4.0 CONCLUSIONS

Evaluation of the analytical results reported for the unfiltered groundwater samples collected in July 2007 from the RCRA detection monitoring wells at the ECRWP does not indicate a release or potential release of contaminants to the uppermost aquifer at the site.

As noted in Sect. 2, the PCP requires semiannual collection of groundwater samples from three POC wells at the ECRWP. Accordingly, wells GW-161, GW-296, and GW-298 will serve as the primary POC wells for future RCRA groundwater sampling events, with wells GW-292 and GW-293 reserved as replacements for any of the primary POC wells that become irreparably damaged or destroyed.

RECORD COPY DISTRIBUTION

File—EMEF DMC—RC